## Realistic fire rendering

Garoe Dorta Perez

University of Bath Centre For Digital Entertainment

September 16, 2015



# Overview



Introduction

Previous Work

Methodology

Implementation

Results and Conclusion



# Outline



Introduction

Previous Work

Methodology

Implementation

Results and Conclusio



## Introduction



Manipulate fire in virtual scenes

- Create
- Edit
- Visualize



Real fire with paper as fuel, image courtesy of FireImg1 (2015).















# Volume rendering area






Diagram of light observed at p, image courtesy of Pharr and Humphreys (2004)



## The problem



- Render fire realistically
  - Participating media
  - Emission cannot be ignored
  - Varied fuel types



Real fire with paper as fuel, image courtesy of FireImg1 (2015).



# Outline



Introduction

Previous Work

Methodology

Implementation

Results and Conclusio

nplementation Results and Conclusion



#### Previous work



- Ray-tracing-based
  - Physically based
  - Accurate
  - Slow

Previous Work

- Raster-based
  - Many artefacts
  - Fast



## Previous work: Results 1








Left, methane fire pool Pegoraro and Parker (2006); right, a dragon emits a flame Hong et al. (2007).



#### Previous work: Results 2







Left, a dragon emits a flame Jamriška et al. (2015); right, sparse flame reconstruction Okabe et al. (2015).



# Outline



Introduction

Previous Work

Methodology

Implementation

Results and Conclusio



$$(\nabla)L_{\mathsf{x}} = -\sigma_{\mathsf{a}}L_{\mathsf{x}} + \sigma_{\mathsf{a}}L_{\mathsf{e}} - \sigma_{\mathsf{s}}L_{\mathsf{x}} + \sigma_{\mathsf{s}}\int L_{i}\Phi d\omega_{i}$$



$$\boxed{(\nabla)L_{\mathbf{x}}} = -\sigma_{a}L_{\mathbf{x}} + \sigma_{a}L_{e} - \sigma_{s}L_{\mathbf{x}} + \sigma_{s}\int L_{i}\Phi d\omega_{i}$$

Differential of radiance over a segment







$$(\nabla)L_{\mathbf{x}} = \boxed{-\sigma_{\mathbf{a}}L_{\mathbf{x}}} + \sigma_{\mathbf{a}}L_{\mathbf{e}} - \sigma_{\mathbf{s}}L_{\mathbf{x}} + \sigma_{\mathbf{s}}\int L_{i}\Phi d\omega_{i}$$

#### Absorption,

where  $\sigma_a$  is an absorption

coefficient



$$(\nabla)L_{\mathbf{x}} = -\sigma_{\mathbf{a}}L_{\mathbf{x}} + \boxed{\sigma_{\mathbf{a}}L_{\mathbf{e}}} - \sigma_{\mathbf{s}}L_{\mathbf{x}} + \sigma_{\mathbf{s}}\int L_{i}\Phi d\omega_{i}$$

Emission








$$(\nabla)L_{\mathbf{x}} = -\sigma_{a}L_{\mathbf{x}} + \sigma_{a}L_{e} - \sigma_{s}L_{\mathbf{x}} + \sigma_{s}\int L_{i}\Phi d\omega_{i}$$

## In-scattering,

where  $\sigma_s$  is a scattering coefficient,  $\Phi$  a scattering

function and  $\omega_i$  is


a incoming direction





$$(\nabla)L_{\mathbf{x}} = -\sigma_{a}L_{\mathbf{x}} + \sigma_{a}L_{e}\left[-\sigma_{s}L_{\mathbf{x}}\right] + \sigma_{s}\int L_{i}\Phi d\omega_{i}$$

Out-scattering








#### Analytical solution

$$\begin{split} L_{\mathbf{x}} &= e^{-\sigma_t \|\Delta \mathbf{x}\|} L_{\mathbf{x} + \Delta \mathbf{x}} + \left(1 - e^{-\sigma_t \|\Delta \mathbf{x}\|}\right) \frac{\sigma_a L_e + \sigma_s \int L_i \Phi d\omega_i}{\sigma_t} \\ \sigma_t &= \sigma_a + \sigma_s \end{split}$$

Segment increment  $\Delta x$ 



#### The model: Important quantities



- Fuel type  $\Rightarrow \sigma_a, \sigma_s$ 
  - Burning soot emission (Propane, Methane, ...)
  - Exotic chemicals (Copper, Lithium, ...)
- Black Body radiation  $\Rightarrow L_e$
- Refraction  $\Rightarrow \Delta x$
- Visual Adaptation  $\Rightarrow L_{x}$



# Outline



Introduction

Previous Work

Methodology

Implementation

Results and Conclusio

$$L_{\mathbf{x}} = e^{-\sigma_t \|\Delta \mathbf{x}\|} L_{\mathbf{x} + \Delta \mathbf{x}} + \left(1 - e^{-\sigma_t \|\Delta \mathbf{x}\|}\right) rac{\sigma_a L_e + \sigma_s \int L_i \Phi d\omega_i}{\sigma_t}$$

$$egin{aligned} L_{\mathbf{x}} &= e^{-\sigma_t \|\Delta \mathbf{x}\|} L_{\mathbf{x} + \Delta \mathbf{x}} + \left(1 - e^{-\sigma_t \|\Delta \mathbf{x}\|}\right) rac{\sigma_a L_e + \sigma_s \int L_i \Phi d\omega_i}{\sigma_t} \ \sigma_s &= 0. \end{aligned}$$

Implementation

## Prior simplifications



$$\sigma_t = \sigma_a + \sigma_s$$

$$L_{\mathbf{x}} = e^{-\sigma_t \|\Delta \mathbf{x}\|} L_{\mathbf{x} + \Delta \mathbf{x}} + \left(1 - e^{-\sigma_t \|\Delta \mathbf{x}\|}\right) \frac{\mathbf{x}_{\mathbf{x}} L_e + \sigma_s \mathbf{x}_{\mathbf{x}}}{\mathbf{x}_{\mathbf{x}}}$$


$$L_{\mathbf{x}} = e^{-\sigma_{\mathbf{a}} \|\Delta \mathbf{x}\|} L_{\mathbf{x} + \Delta \mathbf{x}} + \left(1 - e^{-\sigma_{\mathbf{a}} \|\Delta \mathbf{x}\|}\right) L_{\mathbf{e}}$$

Constant refraction indices

#### Implementation overview



- MentalRay shader in Maya
  - Ray marching divides the RTE into
    - ▶ Light Ray  $\rightarrow L_e$
    - Shadow Ray  $\rightarrow e^{-\sigma_a \|\Delta x\|} L_{x+\Delta x}$
    - Eye Ray  $\rightarrow L_x = e^{-\sigma_a ||\Delta x||} L_{x+\Delta x} + L_e$
  - Light shader
  - Volume/Shadow shader
  - Utility scripts



Rays diagram for a sample intersection point.



#### Other details



- Large memory requirements
  - Sparse voxel dataset library OpenVDB
- Validation with more data
  - Uintah simulation framework
- Different fuel types
  - NIST emission spectrum database



# Outline



Introduction

Previous Work

Methodology

Implementation

Results and Conclusion


Implementation

Results and Conclusion

Reference



#### Results I



The test scene.



### Results II






Propane flame.

•••••



#### Results III





Flame with copper fuel.

•••••



## Results IV






Flame with sulfur fuel.



# Results V





Visual adaptation to the flame; left, no adaptation, right, fully adapted.



#### Conclusions and Future Work



- Limitations
  - Difficult parametrization
  - Relies on tabulated data
  - Computationally intensive
  - Spherical particles
- Future work
  - Importance sampling
  - Automatic parameter estimation



#### Parameter Estimation



- Spectrum reconstruction
- Under constrained
- Prior knowledge
  - Camera sensitivity
- Previous work, Smits (1999), Sun et al. (2001), Drew and Finlayson (2003)

# Thank you

Questions?







- Drew, M. S. and Finlayson, G. D. (2003). Multispectral processing without spectra. *J. Opt. Soc. Am. A*, 20(7):1181–1193.
- FireImg1 (2015). Fire image 1.
  - https://en.wikipedia.org/wiki/File:Fire.JPG.

Accessed: 21-07-2015.

- Hong, J.-M., Shinar, T., and Fedkiw, R. (2007). Wrinkled flames and cellular patterns. *ACM Trans. Graph.*, 26(3).
- Jamriška, O., Fišer, J., Asente, P., Lu, J., Shechtman, E., and Sýkora, D. (2015). Lazyfluids: Appearance transfer for fluid animations. ACM Transactions on Graphics, 34(4).





- Okabe, M., Dobashi, Y., Anjyo, K., and Onai, R. (2015). Fluid volume modeling from sparse multi-view images by appearance transfer. *ACM Transactions on Graphics (Proc. SIGGRAPH 2015)*, 34(4):93:1–93:10.
- Pegoraro, V. and Parker, S. G. (2006). Physically-based realistic fire rendering. *Natural Phenomena*, pages 51–59.
- Pharr, M. and Humphreys, G. (2004). *Physically based rendering:* From theory to implementation. Morgan Kaufmann.
- Smits, B. (1999). An rgb-to-spectrum conversion for reflectances. *Journal of Graphics Tools*, 4(4):11–22.
- Sun, Y., Fracchia, F. D., Drew, M. S., and Calvert, T. W. (2001). A spectrally based framework for realistic image synthesis. *The Visual Computer*, 17(7):429–444.