

6 Greedy Algorithms Continued

6.1 Encodings Huffman's Encoding Algorithm

6.11 Explanation

Huffman's Encoding Algorithm is a greedy approach used for data compression, where symbols are encoded based on their frequencies. This algorithm prioritizes symbols that appear more frequently by assigning them shorter binary codes, while less frequent symbols receive longer codes. By doing so, Huffman encoding efficiently reduces the average code length, making it ideal for storage and transmission applications.

Consider a text file where the letters "E", "R", "D", "U", and "N" appear most frequently. Huffman encoding assigns shorter binary codes to these commonly occurring letters, while rarer letters receive longer codes. In my understanding, Huffman encoding is similar to how we arrange frequently used items within easy reach, and less commonly used items further away. Just as this organization reduces the time needed to find important items, Huffman encoding minimizes the space needed by assigning shorter codes to frequently used symbols.

Algorithm 1 Huffman's Encoding Algorithm

Input : A list of characters with their corresponding frequencies

Output: A Huffman tree with binary encodings for each character

Create a priority queue and insert all characters based on their frequencies

while *there is more than one node in the priority queue* **do**

 Remove the two nodes with the lowest frequencies

 Create a new node with these two nodes as children, with its frequency as the sum of their frequencies

 Insert the new node back into the priority queue

The last remaining node is the root of the Huffman tree

Traverse the tree to assign binary codes to each character, assigning '0' to the left branch and '1' to the right branch

Step-by-Step Explanation of the Pseudocode

- Begin by creating a priority queue, where each character is stored along with its frequency. Characters with lower frequencies will be dequeued before those with higher frequencies, ensuring that less common characters end up with longer codes.
- Building the Huffman Tree while there is more than one node in the queue, repeat the following steps:
 - Remove the two nodes with the lowest frequencies from the queue. These nodes will represent the least common characters or groups of characters.
 - Create a new internal node by combining these two nodes as children. This node's frequency will be the sum of the two nodes' frequencies, representing a cumulative weight.
 - Insert this newly created node back into the priority queue, ordered by its frequency.

- When only one node remains in the priority queue, it becomes the root of the Huffman tree. This root node now connects all characters based on their frequencies, forming the complete Huffman tree.
- Starting from the root node, traverse the tree to assign a binary code to each character:
 - Assign "0" for the left branch and "1" for the right branch as you descend each level of the tree.
 - Continue assigning binary codes until every character has a unique code determined by its position in the tree.

6.12 Exercise

Given the following characters with their frequencies, execute Huffman's Encoding Algorithm step-by-step to build the Huffman tree and determine each character's binary code.

- Characters: A, B, C, D, E, F
- Frequencies: 5, 9, 12, 13, 16, 45

6.13 Solution

Step 1: Initialize Priority Queue

- Insert each character into the priority queue based on frequency.

Priority Queue: $(A : 5), (B : 9), (C : 12), (D : 13), (E : 16), (F : 45)$



Figure 1: Initial Priority Queue with Characters and Frequencies

Step 2: First Iteration

- Remove nodes A (5) and B (9).
- Create a new node with frequency $5 + 9 = 14$.
- Insert the new node back into the priority queue.

Priority Queue: $(C : 12), (D : 13), (E : 16), (NewNode : 14), (F : 45)$




Figure 2: Merging A and B to create New Node with frequency 14

Step 3: Second Iteration

- Remove nodes C (12) and D (13).
- Create a new node with frequency $12 + 13 = 25$.
- Insert the new node back into the priority queue.

Priority Queue: $(E : 16), (NewNode : 14), (NewNode : 25), (F : 45)$




Figure 3: Merging C and D to create New Node with frequency 25

Step 4: Third Iteration

- Remove nodes E (16) and the first NewNode (14).
- Create a new node with frequency $16 + 14 = 30$.
- Insert the new node back into the priority queue.

Priority Queue: $(NewNode : 25), (NewNode : 30), (F : 45)$




Figure 4: Merging E and Node (14) to create New Node with frequency 30

Step 5: Fourth Iteration

- Remove nodes NewNode (25) and NewNode (30).
- Create a new node with frequency $25 + 30 = 55$.
- Insert the new node back into the priority queue.

Priority Queue: $(F : 45), (NewNode : 55)$




Figure 5: Merging Nodes 25 and 30 to create New Node with frequency 55

Step 6: Final Iteration

- Remove nodes F (45) and NewNode (55).
- Create a new root node with frequency $45 + 55 = 100$, completing the Huffman tree.




Figure 6: Final Huffman Tree with Root Node (100)

Step 7: Traverse the tree and assign a number

- Traverse the tree, assigning "0" to the left branches and "1" to the right branches




Figure 7: Final Huffman Tree with Binary Code Assignments

Step 8: Final Result

- F: 0
- C: 100
- D: 101
- E: 111
- A: 1100
- B: 1101

6.2 Greedy Algorithm Design

6.21 Problem

Given an array of non-negative integers, where each element represents the height of a vertical line on a coordinate plane, find two lines that together with the x-axis form a container that holds the most water. The container's height is determined by the shorter of the two lines, and its width is the distance between them.

For example, given the array `[1, 8, 6, 2, 5, 4, 8, 3, 7]`, where each element represents the height of a bar, our task is to identify two bars that, when combined, form the container with the largest possible area.

The array `[1, 8, 6, 2, 5, 4, 8, 3, 7]` can be visualized as a set of vertical bars with heights as follows:




Figure 8: Initial Bar Heights for the Container Problem

In this setup:

- The x-axis represents the positions of the bars.
- The y-axis represents the height of each bar.

The objective is to find two bars that maximize the area of the container they form. The area of the container is calculated as $\text{Area} = \text{width} \times \min(\text{height}[\text{left}], \text{height}[\text{right}])$ where width is the distance between the two chosen bars, and `height[left]` and `height[right]` represent their respective heights.

6.22 Pseudocode and Explanation

Algorithm 2 MaxWaterContainer

Input : Array of integers *height*, representing heights of vertical lines

Output: Maximum area of water container formed by any two lines

Initialize *left* pointer at 0

Initialize *right* pointer at $\text{length}(\text{height}) - 1$

Initialize *max_area* as 0

while *left* < *right* **do**

 Calculate *width* as *right* - *left*

 Calculate *current_area* as $\text{width} \times \min(\text{height}[\text{left}], \text{height}[\text{right}])$

 Update *max_area* to be the maximum of *max_area* and *current_area*

if $\text{height}[\text{left}] < \text{height}[\text{right}]$ **then**

 Move the *left* pointer to the right by 1

else

 Move the *right* pointer to the left by 1

return *max_area*

Step-by-Step Explanation of the Pseudocode

- The left pointer starts at the beginning of the array, and the right pointer starts at the end of the array (length - 1). These represent the two bars that could form a container.
- Start with maxarea set to 0, which will store the maximum area encountered.
- Continue the loop until left and right meet, maximizing the area by adjusting the pointers.
- Compute width as the distance between the left and right pointers.
- Calculate the area of the current container by multiplying the width by the shorter of the two heights at left and right.
- If the height[left] is smaller than the height[right], move the left pointer to the right to find a taller bar.
- If height[right] is smaller or equal to height[left], move the right pointer to the left.
- Return maxarea: After the loop, maxarea holds the largest area found.

6.23 Solution

Step 1: Initial Set up

- Array: [1, 8, 6, 2, 5, 4, 8, 3, 7]
- Left pointer: 0 as the height 1
- Right pointer: 8 as the height 7
- Max Area: 0




Figure 9: Step 1: Initial Setup with Left and Right Pointers

Step 2

- Calculate width: $\text{right} - \text{left} = 8 - 0 = 8$
- Calculate area: $\text{currentarea} = \text{width} \times \min(\text{height}[\text{left}], \text{height}[\text{right}]) = 8 \times \min(1, 7) = 8$
- Update Max Area: $\text{maxarea} = \max(0, 8) = 8$
- Move Pointers: Because $\text{height}[\text{left}] < \text{height}[\text{right}]$ so left pointer move right 1.




Figure 10: Step 2: Calculated Area = 8

Step 3

- Calculate width: $\text{right} - \text{left} = 8 - 1 = 7$
- Calculate area: $\text{current_area} = \text{width} \times \min(\text{height}[\text{left}], \text{height}[\text{right}]) = 7 \times \min(8, 7) = 49$
- Update Max Area: $\text{max_area} = \max(8, 49) = 49$
- Move Pointers: Since $\text{height}[\text{left}] > \text{height}[\text{right}]$, move right pointer left by 1.




Figure 11: Step 3: Calculated Area = 49

Step 4

- Calculate width: $\text{right} - \text{left} = 7 - 1 = 6$
- Calculate area: $\text{current_area} = \text{width} \times \min(\text{height}[\text{left}], \text{height}[\text{right}]) = 6 \times \min(8, 3) = 18$
- Max Area remains 49
- Move Pointers: Since $\text{height}[\text{left}] > \text{height}[\text{right}]$, move right pointer to the left by 1.




Figure 12: Step 4: Calculated Area = 18

Step 5

- Calculate width: $\text{right} - \text{left} = 6 - 1 = 5$
- Calculate area: $\text{current_area} = \text{width} \times \min(\text{height}[\text{left}], \text{height}[\text{right}]) = 5 \times \min(8, 8) = 40$
- Max Area remains 49
- Move Pointers: Since $\text{height}[\text{left}] > \text{height}[\text{right}]$, move right pointer to the left by 1.




Figure 13: Step 5: Calculated Area = 40

Step 6

- Calculate width: $\text{right} - \text{left} = 5 - 1 = 4$
- Calculate area: $\text{current_area} = \text{width} \times \min(\text{height}[\text{left}], \text{height}[\text{right}]) = 4 \times \min(8, 4) = 16$
- Max Area remains 49
- Move Pointers: Since $\text{height}[\text{left}] > \text{height}[\text{right}]$, move right pointer to the left by 1.




Figure 14: Step 6: Calculated Area = 16

Step 7

- Calculate width: $\text{right} - \text{left} = 4 - 1 = 3$
- Calculate area: $\text{current_area} = \text{width} \times \min(\text{height}[\text{left}], \text{height}[\text{right}]) = 3 \times \min(8, 5) = 15$
- Max Area remains 49
- Move Pointers: Since $\text{height}[\text{left}] > \text{height}[\text{right}]$, move right pointer to the left by 1.




Figure 15: Step 7: Calculated Area = 15

Step 8

- Calculate width: $\text{right} - \text{left} = 3 - 1 = 2$
- Calculate area: $\text{current_area} = \text{width} \times \min(\text{height}[\text{left}], \text{height}[\text{right}]) = 2 \times \min(8, 2) = 4$
- Max Area remains 49
- Move Pointers: Since $\text{height}[\text{left}] > \text{height}[\text{right}]$, move right pointer to the left by 1.




Figure 16: Step 8: Calculated Area = 4

Step 9

- Calculate width: $\text{right} - \text{left} = 2 - 1 = 1$
- Calculate area: $\text{current_area} = \text{width} \times \min(\text{height}[\text{left}], \text{height}[\text{right}]) = 1 \times \min(8, 6) = 6$
- Max Area remains 49
- Move Pointers: Since $\text{height}[\text{left}] > \text{height}[\text{right}]$, move right pointer to the left by 1.




Figure 17: Step 9: Calculated Area = 6

Step 10: Final Result

- Left pointer meets right pointer, loop finish
- And the max area is 49




Figure 18: Step 10: Final Result = 49

6.24 Correctness

I use a two-pointer approach to solve the Container With Most Water problem. Starting with the pointers at the ends of the array, my idea was to gradually move the pointers inside to maximize the area between the two lines.

1. I realize that the shorter line always constrains the area. So, I moved the pointer to the shorter line, hoping to find a taller line to increase the area. Moving the taller line wouldn't help here, as it wouldn't remove the height limitation caused by the shorter line.

2. By using this method, I ensure that I don't miss any possible maximum areas. If the initial lines produce the largest area, I capture that immediately. As the pointers progress inside, I consider every pair of lines that could give a greater area.

3. Moving the shorter line's pointer also helps me eliminate pairs that aren't likely to produce the maximum area. This allows me to zero in on promising configurations without wasting time on less effective choices.

Through this approach, I'm confident that by the time the two pointers meet, I've considered all possible situations and found the maximum area. This makes the algorithm both correct and efficient.

6.25 Time Complexity

I chose a two-pointer approach for the Container With Most Water problem due to its efficiency.

Time Complexity:

- I move each pointer inside only once, making a single pass through the array. This gives an $O(n)$ time complexity.

Space Complexity:

- I only use a few variables, so the space complexity is $O(1)$, requiring no extra memory.

7 Dynamic Programming

7.1 Technique Definition

7.11 Basic Definition

Dynamic Programming (DP) is a method used to solve complex problems by breaking them down into smaller, overlapping subproblems. Each subproblem is solved only once, and its solution is stored. This avoids redundant calculations and speeds up the overall process. DP is particularly effective for optimization problems where decisions depend on previously computed results.

And DP has two main strategies which are the following:

Top - Down (Memoization)

- Start with the full problem, recursively solve smaller subproblems, and store their results.

Bottom - Up (Tabulation)

- Start with the smallest subproblems, iteratively build up solutions, and solve the full problem last.

7.12 Top - Down Example

Imagine I am planning a trip that needs to go through multiple cities and I want to try to minimize the total cost. Each city has multiple routes to other cities, and some routes go through specific in-between cities. Instead of repeating the cost of each possible route, start at the final destination, work backward to calculate the cheapest cost to get to that destination, and store the cost for each city.

7.13 Pseudocode

Algorithm 3 Fibonacci (Top-Down DP)

Input : An integer n , where $n \geq 0$

Output: The n -th Fibonacci number

Define an array memo of size $n + 1$ and initialize all values to -1

Function Fibo(n):

```
    if  $n \leq 1$  then
        return  $n$ 
    if  $\text{memo}[n] \neq -1$  then
        return  $\text{memo}[n]$ 
     $\text{memo}[n] = \text{Fibo}(n - 1) + \text{Fibo}(n - 2)$ 
    return  $\text{memo}[n]$ 
```

Call Fibo(n) and return the result

Step-by-Step Explanation of the Pseudocode

- Create an array memo to store solutions for already solved subproblems. Initialize all values to -1 to indicate they haven't been computed.
- If n is 0 or 1, return n directly, as these are the smallest subproblems.
- Before calculating Fibo(n), check if $\text{memo}[n]$ has already been computed. If it has, return the stored value.
- If not, compute Fibo($n - 1$) and Fibo($n - 2$) recursively, store the result in $\text{memo}[n]$, and return it.
- The initial call to Fibo(n) solves the full problem, using previously computed subproblems as needed.

7.14 Bottom - Up Example

Imagine I am in the process of renovating my house and have a choice of building materials to choose from. Each material has a price and a quality score. The first calculate and store each material's price-to-quality ratio to save time. Later, when I choose materials for my renovation, I can refer to this stored information to quickly find the best combo without recalculating.

7.15 Pseudocode

Algorithm 4 Fibonacci (Bottom-Up DP)

Input : An integer n , where $n \geq 0$

Output: The n -th Fibonacci number

if $n \leq 1$ **then**

\perp **return** n

Initialize an array fib of size $n + 1$

Set $fib[0] = 0$

Set $fib[1] = 1$

for $i = 2$ **to** n **do**

\perp $fib[i] = fib[i - 1] + fib[i - 2]$

return $fib[n]$

Step-by-Step Explanation of the Pseudocode

- If n is 0 or 1, return n directly. These are the smallest subproblems with known solutions.
- Create an array fib to store Fibonacci numbers up to the n th position. Set $fib[0]$ to 0 and $fib[1]$ to 1.
- For each i from 2 to n , calculate $fib[i]$ by adding $fib[i - 1]$ and $fib[i - 2]$.
- The n th Fibonacci number is stored in $fib[n]$ and returned.

7.16 Difference

Summary of Top-Down vs. Bottom-Up

Aspect	Top-Down	Bottom-Up
Approach	Recursive	Iterative
Storage	Stores results only when computed	Precomputes all subproblems
Execution Order	Starts with full problem	Starts with smallest subproblems
Example	Traveling through cities	Renovation materials

Table 1: Comparison of Top-Down and Bottom-Up Approaches in Dynamic Programming

7.2 Edit-distance

7.21 Explanation

Edit Distance, also known as Levenshtein Distance, measures how similar two strings are by calculating the minimum number of operations needed to convert one string into the other. Edit Distance is a common dynamic programming problem and particularly useful for applications in natural language processing, such as spell checkers, DNA sequence analysis, and text similarity measures.

The allowed operations are:

- Insertion: Add a character to one string.
- Deletion: Remove a character from one string.
- Substitution: Replace one character with another.

Imagine I am editing a rough draft of a document to match the final version. Every typo or mistake in the draft requires me to insert a missing word, delete an unnecessary word, or replace a misspelled one. The edit distance tells me the minimum number of edits required to transform the draft into the polished version, ensuring the two are identical.

Algorithm 5 Edit Distance Algorithm (Bottom-Up DP)

Input : Two strings, *word1* of length *m* and *word2* of length *n*

Output: Minimum edit distance to transform *word1* into *word2*

Define a 2D array *dp* of size $(m + 1) \times (n + 1)$

for *i* = 0 **to** *m* **do**

$dp[i][0] = i$

for *j* = 0 **to** *n* **do**

$dp[0][j] = j$

for *i* = 1 **to** *m* **do**

for *j* = 1 **to** *n* **do**

if *word1*[*i* - 1] == *word2*[*j* - 1] **then**

$dp[i][j] = dp[i-1][j-1]$

else

$dp[i][j] = 1 + \min(dp[i-1][j], dp[i][j-1], dp[i-1][j-1])$

return $dp[m][n]$

Step-by-Step Explanation of the Pseudocode

Initialize the DP Table

- The table $dp[i][j]$ stores the minimum edit distance to convert the first *i* characters of *word1* into the first *j* characters of *word2*.
- If one of the words is empty, the distance is the length of the other word.

Base Cases

- $dp[i][0]$: Transforming the first *i* characters of *word1* into an empty *word2* requires *i* deletions.
- $dp[0][j]$: Transforming an empty *word1* into the first *j* characters of *word2* requires *j* insertions.

Recursive Transitions

- If the characters $\text{word1}[i-1]$ and $\text{word2}[j-1]$ are equal, no operation is required. The value is carried over from $\text{dp}[i-1][j-1]$.
- Otherwise, the value is $1 + \min(\dots)$, where:
 - $\text{dp}[i-1][j]$: Represents a deletion in word1.
 - $\text{dp}[i][j-1]$: Represents an insertion in word1.
 - $\text{dp}[i-1][j-1]$: Represents a substitution.

Final Result

- The value at $\text{dp}[m][n]$ gives the minimum number of edits required to transform word1 into word2.

7.22 Exercise

Using the bottom-up dynamic programming approach, calculate the minimum number of operations required to convert “editing” into “distance” by step-by-step execution of the algorithm.

7.23 Solution

Step 1: Initialization

- Initialize the table with the base cases. The first row and first column represent the costs of converting an empty string into prefixes of the other string.

		d	i	s	t	a	n	c	e
	0	1	2	3	4	5	6	7	8
e	1								
d	2								
i	3								
t	4								
i	5								
n	6								
g	7								

Table 2: Step 1: Initialization of Base Cases

Step 2: Comparing "e" with "d"

- Compute the cost for converting e to d. The values in the first row and first column remain unchanged.
- $\text{dp}[1][1] = 1 + \min(\text{dp}[0][1], \text{dp}[1][0], \text{dp}[0][0])$
- $\text{dp}[1][1] = 1 + \min(1, 1, 0) = 1$

		d	i	s	t	a	n	c	e
	0	1	2	3	4	5	6	7	8
e	1	1							
d	2								
i	3								
t	4								
i	5								
n	6								
g	7								

Table 3: Step 2: Comparing "e" with "d"

Step 3: Comparing "e" with "i"

- Compute the cost for converting "e" to "i".
- $dp[1][2] = 1 + \min(dp[0][2], dp[1][1], dp[0][1])$
- $dp[1][2] = 1 + \min(2, 1, 1) = 2$

		d	i	s	t	a	n	c	e
	0	1	2	3	4	5	6	7	8
e	1	1	2						
d	2								
i	3								
t	4								
i	5								
n	6								
g	7								

Table 4: Step 3: Comparing "e" with "i"

Step 4:

- Compute the cost for converting "e" to "s".
- $dp[1][3] = 1 + \min(dp[0][3], dp[1][2], dp[0][2])$
- $dp[1][3] = 1 + \min(3, 2, 2) = 3$

		d	i	s	t	a	n	c	e
	0	1	2	3	4	5	6	7	8
e	1	1	2	3					
d	2								
i	3								
t	4								
i	5								
n	6								
g	7								

Table 5: Step 4: Comparing "e" with "s"

Step 5: Comparing "e" with "t"

- Compute the cost for converting "e" to "t".
- $dp[1][4] = 1 + \min(dp[0][4], dp[1][3], dp[0][3])$
- $dp[1][4] = 1 + \min(4, 3, 3) = 4$

		d	i	s	t	a	n	c	e
	0	1	2	3	4	5	6	7	8
e	1	1	2	3	4				
d	2								
i	3								
t	4								
i	5								
n	6								
g	7								

Table 6: Step 5: Comparing "e" with "t"

Step 6: Comparing "e" with "a"

- Compute the cost for converting "e" to "a".
- $dp[1][5] = 1 + \min(dp[0][5], dp[1][4], dp[0][4])$
- $dp[1][5] = 1 + \min(5, 4, 4) = 5$

		d	i	s	t	a	n	c	e
	0	1	2	3	4	5	6	7	8
e	1	1	2	3	4	5			
d	2								
i	3								
t	4								
i	5								
n	6								
g	7								

Table 7: Step 6: Comparing "e" with "a"

Step 7: Comparing "e" with "n"

- Compute the cost for converting "e" to "n".
- $dp[1][6] = 1 + \min(dp[0][6], dp[1][5], dp[0][5])$
- $dp[1][6] = 1 + \min(6, 5, 5) = 6$

		d	i	s	t	a	n	c	e
	0	1	2	3	4	5	6	7	8
e	1	1	2	3	4	5	6		
d	2								
i	3								
t	4								
i	5								
n	6								
g	7								

Table 8: Step 7: Comparing "e" with "n"

Step 8: Comparing "e" with "c"

- Compute the cost for converting "e" to "c".
- $dp[1][7] = 1 + \min(dp[0][7], dp[1][6], dp[0][6])$
- $dp[1][7] = 1 + \min(7, 6, 6) = 7$

		d	i	s	t	a	n	c	e
	0	1	2	3	4	5	6	7	8
e	1	1	2	3	4	5	6	7	
d	2								
i	3								
t	4								
i	5								
n	6								
g	7								

Table 9: Step 8: Comparing "e" with "c"

Step 9: Comparing "e" with "e"

- Compute the cost for converting "e" to "e".
- Since they are the same, no operation is needed.
- $dp[1][8] = dp[0][7] = 7$

		d	i	s	t	a	n	c	e
	0	1	2	3	4	5	6	7	8
e	1	1	2	3	4	5	6	7	7
d	2								
i	3								
t	4								
i	5								
n	6								
g	7								

Table 10: Step 9: Comparing "e" with "e"

Step 10: Fill out the second row for "d"

- Compare "d" with each character in "distance"
- $dp[2][1]$:
 - Comparing "d" with "d".
 - Characters are the same, so no operation is needed
 - $dp[2][1] = dp[1][0] = 1$
- $dp[2][2]$:
 - Comparing "d" with "i"
 - $dp[2][2] = 1 + \min(dp[1][2], dp[2][1], dp[1][1])$
 - $dp[2][2] = 1 + \min(2, 1, 1) = 2$

- $dp[2][3]$:
 - Comparing "d" with "s".
 - $dp[2][3] = 1 + \min(dp[1][3], dp[2][2], dp[1][2])$
 - $dp[2][3] = 1 + \min(3, 2, 2) = 3$
- $dp[2][4]$:
 - Comparing "d" with "t".
 - $dp[2][4] = 1 + \min(dp[1][4], dp[2][3], dp[1][3])$
 - $dp[2][4] = 1 + \min(4, 3, 3) = 4$
- $dp[2][5]$:
 - Comparing "d" with "a".
 - $dp[2][5] = 1 + \min(dp[1][5], dp[2][4], dp[1][4])$
 - $dp[2][5] = 1 + \min(5, 4, 4) = 5$
- $dp[2][6]$:
 - Comparing "d" with "n".
 - $dp[2][6] = 1 + \min(dp[1][6], dp[2][5], dp[1][5])$
 - $dp[2][6] = 1 + \min(6, 5, 5) = 6$
- $dp[2][7]$:
 - Comparing "d" with "c".
 - $dp[2][7] = 1 + \min(dp[1][7], dp[2][6], dp[1][6])$
 - $dp[2][7] = 1 + \min(7, 6, 6) = 7$
- $dp[2][8]$:
 - Comparing "d" with "e".
 - $dp[2][8] = 1 + \min(dp[1][8], dp[2][7], dp[1][7])$
 - $dp[2][8] = 1 + \min(8, 7, 7) = 8$

		d	i	s	t	a	n	c	e
	0	1	2	3	4	5	6	7	8
e	1	1	2	3	4	5	6	7	7
d	2	1	2	3	4	5	6	7	8
i	3								
t	4								
i	5								
n	6								
g	7								

Table 11: Step 10: Fill out the second row for "d"

Step 11: Fill out the third row for "i"

- Compare "i" with each character in "distance"
- $dp[3][1]$:
 - Comparing "i" with "d".
 - $dp[3][1] = 1 + \min(dp[2][1], dp[3][0], dp[2][0])$
 - $dp[3][1] = 1 + \min(1, 3, 2) = 2$
- $dp[3][2]$:
 - Comparing "i" with "i".
 - Characters are the same, so no operation is needed.
 - $dp[3][2] = dp[2][1] = 1$
- $dp[3][3]$:
 - Comparing "i" with "s".
 - $dp[3][3] = 1 + \min(dp[2][3], dp[3][2], dp[2][2])$
 - $dp[3][3] = 1 + \min(3, 1, 2) = 2$
- $dp[3][4]$:
 - Comparing "i" with "t".
 - $dp[3][4] = 1 + \min(dp[2][4], dp[3][3], dp[2][3])$
 - $dp[3][4] = 1 + \min(4, 2, 3) = 3$
- $dp[3][5]$:
 - Comparing "i" with "a".
 - $dp[3][5] = 1 + \min(dp[2][5], dp[3][4], dp[2][4])$
 - $dp[3][5] = 1 + \min(5, 3, 4) = 4$
- $dp[3][6]$:
 - Comparing "i" with "n".
 - $dp[3][6] = 1 + \min(dp[2][6], dp[3][5], dp[2][5])$
 - $dp[3][6] = 1 + \min(6, 4, 5) = 5$
- $dp[3][7]$:
 - Comparing "i" with "c".
 - $dp[3][7] = 1 + \min(dp[2][7], dp[3][6], dp[2][6])$
 - $dp[3][7] = 1 + \min(7, 5, 6) = 6$
- $dp[3][8]$:
 - Comparing "i" with "e".
 - $dp[3][8] = 1 + \min(dp[2][8], dp[3][7], dp[2][7])$
 - $dp[3][8] = 1 + \min(8, 6, 7) = 7$

		d	i	s	t	a	n	c	e
	0	1	2	3	4	5	6	7	8
e	1	1	2	3	4	5	6	7	7
d	2	1	2	3	4	5	6	7	8
i	3	2	1	2	3	4	5	6	7
t	4								
i	5								
n	6								
g	7								

Table 12: Step 11: Fill out the third row for "i"

Step 12: Fill out the fourth row for "t"

- Compare "t" with each character in "distance"
- $dp[4][1]$:
 - Comparing "t" with "d".
 - $dp[4][1] = 1 + \min(dp[3][1], dp[4][0], dp[3][0])$
 - $dp[4][1] = 1 + \min(2, 4, 3) = 3$
- $dp[4][2]$:
 - Comparing "t" with "i".
 - $dp[4][2] = 1 + \min(dp[3][2], dp[4][1], dp[3][1])$
 - $dp[4][2] = 1 + \min(1, 3, 2) = 2$
- $dp[4][3]$:
 - Comparing "t" with "s".
 - $dp[4][3] = 1 + \min(dp[3][3], dp[4][2], dp[3][2])$
 - $dp[4][3] = 1 + \min(2, 2, 1) = 2$
- $dp[4][4]$:
 - Comparing "t" with "t".
 - Characters are the same, so no operation is needed.
 - $dp[4][4] = dp[3][3] = 2$
- $dp[4][5]$:
 - Comparing "t" with "a".
 - $dp[4][5] = 1 + \min(dp[3][5], dp[4][4], dp[3][4])$
 - $dp[4][5] = 1 + \min(4, 2, 3) = 3$
- $dp[4][6]$:
 - Comparing "t" with "n".
 - $dp[4][6] = 1 + \min(dp[3][6], dp[4][5], dp[3][5])$
 - $dp[4][6] = 1 + \min(5, 3, 4) = 4$
- $dp[4][7]$:
 - Comparing "t" with "c".

- $dp[4][7] = 1 + \min(dp[3][7], dp[4][6], dp[3][6])$
- $dp[4][7] = 1 + \min(6, 4, 5) = 5$
- $dp[4][8]$:
 - Comparing "t" with "e".
 - $dp[4][8] = 1 + \min(dp[3][8], dp[4][7], dp[3][7])$
 - $dp[4][8] = 1 + \min(7, 5, 6) = 6$

		d	i	s	t	a	n	c	e
	0	1	2	3	4	5	6	7	8
e	1	1	2	3	4	5	6	7	7
d	2	1	2	3	4	5	6	7	8
i	3	2	1	2	3	4	5	6	7
t	4	3	2	2	2	3	4	5	6
i	5								
n	6								
g	7								

Table 13: Step 12: Fill out the fourth row for "t"

Step 13: Fill out the fifth row for "i"

- Compare "i" with each character in "distance"
- $dp[5][1]$:
 - Comparing "i" with "d".
 - $dp[5][1] = 1 + \min(dp[4][1], dp[5][0], dp[4][0])$
 - $dp[5][1] = 1 + \min(3, 5, 4) = 4$
- $dp[5][2]$:
 - Comparing "i" with "i".
 - Characters are the same, so no operation is needed.
 - $dp[5][2] = dp[4][1] = 3$
- $dp[5][3]$:
 - Comparing "i" with "s".
 - $dp[5][3] = 1 + \min(dp[4][3], dp[5][2], dp[4][2])$
 - $dp[5][3] = 1 + \min(2, 3, 2) = 3$
- $dp[5][4]$:
 - Comparing "i" with "t".
 - $dp[5][4] = 1 + \min(dp[4][4], dp[5][3], dp[4][3])$
 - $dp[5][4] = 1 + \min(2, 3, 2) = 3$
- $dp[5][5]$:
 - Comparing "i" with "a".
 - $dp[5][5] = 1 + \min(dp[4][5], dp[5][4], dp[4][4])$
 - $dp[5][5] = 1 + \min(3, 3, 2) = 3$

- $dp[5][6]$:
 - Comparing "i" with "n".
 - $dp[5][6] = 1 + \min(dp[4][6], dp[5][5], dp[4][5])$
 - $dp[5][6] = 1 + \min(4, 3, 3) = 4$
- $dp[5][7]$:
 - Comparing "i" with "c".
 - $dp[5][7] = 1 + \min(dp[4][7], dp[5][6], dp[4][6])$
 - $dp[5][7] = 1 + \min(5, 4, 4) = 5$
- $dp[5][8]$:
 - Comparing "i" with "e".
 - $dp[5][8] = 1 + \min(dp[4][8], dp[5][7], dp[4][7])$
 - $dp[5][8] = 1 + \min(6, 5, 5) = 6$

		d	i	s	t	a	n	c	e
	0	1	2	3	4	5	6	7	8
e	1	1	2	3	4	5	6	7	7
d	2	1	2	3	4	5	6	7	8
i	3	2	1	2	3	4	5	6	7
t	4	3	2	2	2	3	4	5	6
i	5	4	3	3	3	3	4	5	6
n	6								
g	7								

Table 14: Step 13: Fill out the fifth row for "i"

Step 14: Fill out the sixth row for "n"

- Compare "n" with each character in "distance"
- $dp[6][1]$:
 - Comparing "n" with "d".
 - $dp[6][1] = 1 + \min(dp[5][1], dp[6][0], dp[5][0])$
 - $dp[6][1] = 1 + \min(4, 6, 5) = 5$
- $dp[6][2]$:
 - Comparing "n" with "i".
 - $dp[6][2] = 1 + \min(dp[5][2], dp[6][1], dp[5][1])$
 - $dp[6][2] = 1 + \min(3, 5, 4) = 4$
- $dp[6][3]$:
 - Comparing "n" with "s".
 - $dp[6][3] = 1 + \min(dp[5][3], dp[6][2], dp[5][2])$
 - $dp[6][3] = 1 + \min(3, 4, 3) = 4$
- $dp[6][4]$:

- Comparing "n" with "t".
- $dp[6][4] = 1 + \min(dp[5][4], dp[6][3], dp[5][3])$
- $dp[6][4] = 1 + \min(3, 4, 3) = 4$
- $dp[6][5]$:
 - Comparing "n" with "a".
 - $dp[6][5] = 1 + \min(dp[5][5], dp[6][4], dp[5][4])$
 - $dp[6][5] = 1 + \min(3, 4, 3) = 4$
- $dp[6][6]$:
 - Comparing "n" with "n".
 - Characters are the same, so no operation is needed.
 - $dp[6][6] = dp[5][5] = 3$
- $dp[6][7]$:
 - Comparing "n" with "c".
 - $dp[6][7] = 1 + \min(dp[5][7], dp[6][6], dp[5][6])$
 - $dp[6][7] = 1 + \min(5, 3, 4) = 4$
- $dp[6][8]$:
 - Comparing "n" with "e".
 - $dp[6][8] = 1 + \min(dp[5][8], dp[6][7], dp[5][7])$
 - $dp[6][8] = 1 + \min(6, 4, 5) = 5$

		d	i	s	t	a	n	c	e
	0	1	2	3	4	5	6	7	8
e	1	1	2	3	4	5	6	7	7
d	2	1	2	3	4	5	6	7	8
i	3	2	1	2	3	4	5	6	7
t	4	3	2	2	2	3	4	5	6
i	5	4	3	3	3	3	4	5	6
n	6	5	4	4	4	4	3	4	5
g	7								

Table 15: Step 14: Fill out the sixth row for "n"

Step 15: Fill out the seventh row for "g"

- Compare "g" with each character in "distance"
- $dp[7][1]$:
 - Comparing "g" with "d".
 - $dp[7][1] = 1 + \min(dp[6][1], dp[7][0], dp[6][0])$
 - $dp[7][1] = 1 + \min(5, 7, 6) = 6$
- $dp[7][2]$:
 - Comparing "g" with "i".
 - $dp[7][2] = 1 + \min(dp[6][2], dp[7][1], dp[6][1])$

- $dp[7][2] = 1 + \min(4, 6, 5) = 5$
- $dp[7][3]$:
 - Comparing "g" with "s".
 - $dp[7][3] = 1 + \min(dp[6][3], dp[7][2], dp[6][2])$
 - $dp[7][3] = 1 + \min(4, 5, 4) = 5$
- $dp[7][4]$:
 - Comparing "g" with "t".
 - $dp[7][4] = 1 + \min(dp[6][4], dp[7][3], dp[6][3])$
 - $dp[7][4] = 1 + \min(4, 5, 4) = 5$
- $dp[7][5]$:
 - Comparing "g" with "a".
 - $dp[7][5] = 1 + \min(dp[6][5], dp[7][4], dp[6][4])$
 - $dp[7][5] = 1 + \min(4, 5, 4) = 5$
- $dp[7][6]$:
 - Comparing "g" with "n".
 - $dp[7][6] = 1 + \min(dp[6][6], dp[7][5], dp[6][5])$
 - $dp[7][6] = 1 + \min(3, 5, 4) = 4$
- $dp[7][7]$:
 - Comparing "g" with "c".
 - $dp[7][7] = 1 + \min(dp[6][7], dp[7][6], dp[6][6])$
 - $dp[7][7] = 1 + \min(4, 4, 3) = 4$
- $dp[7][8]$:
 - Comparing "g" with "e".
 - $dp[7][8] = 1 + \min(dp[6][8], dp[7][7], dp[6][7])$
 - $dp[7][8] = 1 + \min(5, 4, 4) = 5$

		d	i	s	t	a	n	c	e
	0	1	2	3	4	5	6	7	8
e	1	1	2	3	4	5	6	7	7
d	2	1	2	3	4	5	6	7	8
i	3	2	1	2	3	4	5	6	7
t	4	3	2	2	2	3	4	5	6
i	5	4	3	3	3	3	4	5	6
n	6	5	4	4	4	4	3	4	5
g	7	6	5	5	5	5	4	4	5

Table 16: Step 15: Fill out the seventh row for "g"

Step 16: Final Result

- After completed the table, the final value in the bottom-right cell which $dp[7][8] = 5$ represents the minimum edit distance between "editing" and "distance".
- This means that a minimum of 5 operations (insertions, deletions, or substitutions) are required to transform the word "editing" into "distance".

7.3 Knapsack (both 0-1 and unrestrained)

7.31 Explanation

The knapsack problem is a classic optimization problem that involves selecting items with given weights and values to maximize the total value that can be carried in a knapsack of limited capacity. There are two primary variations of the knapsack problem:

0-1 Knapsack:

- Each item can either be included or excluded in its entirety. Fractional selections are not allowed.

Unbounded Knapsack:

- Items can be selected multiple times, allowing for unlimited quantities of each item.

For the 0-1 knapsack, the solution depends on whether to include or exclude an item, whereas for the unbounded knapsack, need to consider the possibility of repeatedly selecting an item.

Imagine you are at a grocery store with a fixed budget of \$50. Each grocery item has a price (weight) and a nutritional value (value). Your goal is to maximize the total nutritional value while staying within the budget:

- In the 0-1 scenario, you can only buy one unit of each item, one unit of milk, one unit of bread
- In the unbounded scenario, you can buy multiple units of the same item like 2 units of milk, or 3 units of bread, as long as you do not exceed the budget.

Pseudocode for 0-1 Knapsack

Algorithm 6 0-1 Knapsack Problem

Input : Weights array w , Values array v , Capacity C , Number of items n

Output: Maximum value that can be carried in the knapsack

Initialize a DP table $dp[n+1][C+1]$ with all zeros

```
for  $i \leftarrow 1$  to  $n$  do
    for  $j \leftarrow 1$  to  $C$  do
        if  $w[i-1] \leq j$  then
             $dp[i][j] \leftarrow \max(dp[i-1][j], v[i-1] + dp[i-1][j - w[i-1]])$ 
        else
             $dp[i][j] \leftarrow dp[i-1][j]$ 
```

return $dp[n][C]$

Step-by-Step Explanation for 0-1 Knapsack

- Initialize a DP table with dimensions $(n+1) \times (C+1)$, where n is the number of items and C is the capacity of the knapsack. Each cell $dp[i][j]$ represents the maximum value achievable with the first i items and capacity j .
- Iterate over each item. For each item i and capacity j , decide whether to include the item:
 - If the item's weight $w[i-1]$ exceeds the current capacity j , exclude it.
 - Otherwise, calculate the maximum value by including or excluding the item, and store the result in $dp[i][j]$.
- The final answer is stored in $dp[n][C]$, representing the maximum value achievable with all items and the given capacity.

Pseudocode for Unbounded Knapsack

Algorithm 7 Unbounded Knapsack Problem

Input : Weights array w , Values array v , Capacity C , Number of items n

Output: Maximum value that can be carried in the knapsack

Initialize a DP array $dp[C + 1]$ with all zeros

```
for  $i \leftarrow 0$  to  $n - 1$  do
    for  $j \leftarrow w[i]$  to  $C$  do
         $dp[j] \leftarrow \max(dp[j], v[i] + dp[j - w[i]])$ 
return  $dp[C]$ 
```

Step-by-Step Explanation for Unbounded Knapsack

- Initialize a DP array of size $C+1$, where each index j represents the maximum value achievable with capacity j .
- For each item i , iterate over all capacities j starting from $w[i]$. Update $dp[j]$ to include the maximum value achievable by repeatedly selecting item i .
- The final answer is stored in $dp[C]$, representing the maximum value achievable with unlimited quantities of each item and the given capacity.

7.32 Exercise

Consider the following scenario: You are an adventurer collecting treasures in a dungeon. Each treasure has a specific weight and value, and you have a backpack with a maximum capacity of 10 units. The goal is to maximize the total value of the treasures you can carry.

Items Available:

Item	Weight	Value
1 (Gold Coin)	1	1
2 (Silver Coin)	3	4
3 (Emerald)	4	5
4 (Diamond)	5	7
5 (Artifact)	6	10

Table 17: List of Items with Weight and Value

Knapsack Capacity: $C = 10$

Solve the problem using both the 0-1 knapsack and unbounded knapsack approaches:

- For the 0-1 Knapsack, each item can be picked at most once.
- For the Unbounded Knapsack, items can be picked multiple times as long as the total weight does not exceed the capacity.

Goal: Determine the maximum total value that can be carried in the knapsack under each scenario (0-1 and unbounded).

7.33 0-1 Knapsack Solution

Step 1: Initialize DP Table

- Initialize the DP table $dp[n+1][C+1]$, where n is the number of items, and C is the capacity it's 10 in this case.
- The base cases are:
 - $dp[0][j] = 0$ for all j (no items means no value).
 - $dp[i][0] = 0$ for all i (zero capacity means no value).

Item/Capacity	0	1	2	3	4	5	6	7	8	9	10
0	0	0	0	0	0	0	0	0	0	0	0
1 (Gold Coin)	0										
2 (Silver Coin)	0										
3 (Emerald)	0										
4 (Diamond)	0										
5 (Artifact)	0										

Table 18: Step 1: Initialize DP Table for 0-1 Knapsack

Step 2: Process Item 1 (Gold Coin, Weight = 1, Value = 1)

- For $j = 1$ to 10, calculate:
 - If $j \geq$ weight of item, $dp[1][j] = \max(dp[0][j], dp[0][j-1] + 1)$.
 - Otherwise, $dp[1][j] = dp[0][j]$.

Item/Capacity	0	1	2	3	4	5	6	7	8	9	10
0	0	0	0	0	0	0	0	0	0	0	0
1 (Gold Coin)	0	1	1	1	1	1	1	1	1	1	1
2 (Silver Coin)	0										
3 (Emerald)	0										
4 (Diamond)	0										
5 (Artifact)	0										

Table 19: Step 2: Update DP Table for Item 1 (Gold Coin)

Step 3: Process Item 2 (Silver Coin, Weight = 3, Value = 4)

- For $j = 1$ to 10, calculate:
 - If $j \geq$ weight of item, $dp[2][j] = \max(dp[1][j], dp[1][j-3] + 4)$.
 - Otherwise, $dp[2][j] = dp[1][j]$.

Item/Capacity	0	1	2	3	4	5	6	7	8	9	10
0	0	0	0	0	0	0	0	0	0	0	0
1 (Gold Coin)	0	1	1	1	1	1	1	1	1	1	1
2 (Silver Coin)	0	1	1	4	5	5	5	5	5	5	5
3 (Emerald)	0										
4 (Diamond)	0										
5 (Artifact)	0										

Table 20: Step 3: Update DP Table for Item 2 (Silver Coin)

Step 4: Process Item 3 (Emerald, Weight = 4, Value = 5)

- For $j = 1$ to 10, calculate:
 - If $j \geq \text{weight of item}$, $\text{dp}[3][j] = \max(\text{dp}[2][j], \text{dp}[2][j-4] + 5)$.
 - Otherwise, $\text{dp}[3][j] = \text{dp}[2][j]$.

Item/Capacity	0	1	2	3	4	5	6	7	8	9	10
0	0	0	0	0	0	0	0	0	0	0	0
1 (Gold Coin)	0	1	1	1	1	1	1	1	1	1	1
2 (Silver Coin)	0	1	1	4	5	5	5	5	5	5	5
3 (Emerald)	0	1	1	4	5	6	6	9	10	10	10
4 (Diamond)	0										
5 (Artifact)	0										

Table 21: Step 4: Update DP Table for Item 3 (Emerald)

Step 5: Process Item 4 (Diamond, Weight = 5, Value = 7)

- For $j = 1$ to 10, calculate:
 - If $j \geq \text{weight of item}$, $\text{dp}[4][j] = \max(\text{dp}[3][j], \text{dp}[3][j-5] + 7)$.
 - Otherwise, $\text{dp}[4][j] = \text{dp}[3][j]$.

Item/Capacity	0	1	2	3	4	5	6	7	8	9	10
0	0	0	0	0	0	0	0	0	0	0	0
1 (Gold Coin)	0	1	1	1	1	1	1	1	1	1	1
2 (Silver Coin)	0	1	1	4	5	5	5	5	5	5	5
3 (Emerald)	0	1	1	4	5	6	6	9	10	10	10
4 (Diamond)	0	1	1	4	5	7	8	9	10	11	12
5 (Artifact)	0										

Table 22: Step 5: Update DP Table for Item 4 (Diamond)

Step 6: Process Item 5 (Artifact, Weight = 6, Value = 10)

- For $j = 1$ to 10, calculate:
 - If $j \geq \text{weight of item}$, $\text{dp}[5][j] = \max(\text{dp}[4][j], \text{dp}[4][j-6] + 10)$.
 - Otherwise, $\text{dp}[5][j] = \text{dp}[4][j]$.

Item/Capacity	0	1	2	3	4	5	6	7	8	9	10
0	0	0	0	0	0	0	0	0	0	0	0
1 (Gold Coin)	0	1	1	1	1	1	1	1	1	1	1
2 (Silver Coin)	0	1	1	4	5	5	5	5	5	5	5
3 (Emerald)	0	1	1	4	5	6	6	9	10	10	10
4 (Diamond)	0	1	1	4	5	7	8	9	10	11	12
5 (Artifact)	0	1	1	4	5	7	10	11	11	14	15

Table 23: Step 6: Final DP Table for Item 5 (Artifact)

Step 7: Final Result

- Maximum Value for 0-1 Knapsack: $\text{dp}[5][10] = 15$

7.34 Unbounded Knapsack Solution

Step 1: Initialize DP Table

- Initialize the DP array $dp[C+1]$, where C is the capacity (10 in this case).
- The base case is $dp[0] = 0$ (zero capacity means no value).

Capacity	0	1	2	3	4	5	6	7	8	9	10
Value	0	0	0	0	0	0	0	0	0	0	0

Table 24: Step 1: Initialize DP Table for Unbounded Knapsack

Step 2: Process Item 1 (Gold Coin, Weight = 1, Value = 1)

- For each capacity $j = 1$ to 10, calculate $dp[j] = \max(dp[j], dp[j-1] + 1)$.

Capacity	0	1	2	3	4	5	6	7	8	9	10
Value	0	1	2	3	4	5	6	7	8	9	10

Table 25: Step 2: Update DP Table for Item 1 (Gold Coin)

Step 3: Process Item 2 (Silver Coin, Weight = 3, Value = 4)

- For each capacity $j = 3$ to 10, calculate $dp[j] = \max(dp[j], dp[j-3] + 4)$.

Capacity	0	1	2	3	4	5	6	7	8	9	10
Value	0	1	2	4	5	6	8	9	10	12	13

Table 26: Step 3: Update DP Table for Item 2 (Silver Coin)

Step 4: Process Item 3 (Emerald, Weight = 4, Value = 5)

- For each capacity $j = 4$ to 10, calculate $dp[j] = \max(dp[j], dp[j-4] + 5)$.

Capacity	0	1	2	3	4	5	6	7	8	9	10
Value	0	1	2	4	5	6	8	9	10	12	13

Table 27: Step 4: Update DP Table for Item 3 (Emerald)

Step 5: Process Item 4 (Diamond, Weight = 5, Value = 7)

- For each capacity $j = 5$ to 10, calculate $dp[j] = \max(dp[j], dp[j-5] + 7)$.

Capacity	0	1	2	3	4	5	6	7	8	9	10
Value	0	1	2	4	5	7	8	9	10	12	14

Table 28: Step 5: Update DP Table for Item 4 (Diamond)

Step 6: Process Item 5 (Artifact, Weight = 6, Value = 10)

- For each capacity $j = 6$ to 10 , calculate $dp[j] = \max(dp[j], dp[j-6] + 10)$.

Capacity	0	1	2	3	4	5	6	7	8	9	10
Value	0	1	2	4	5	7	10	11	12	14	15

Table 29: Step 6: Update DP Table for Item 5 (Artifact)

Final Result

- The maximum value that can be obtained with a capacity of 10 is $dp[10] = 15$.
- This value is achieved by selecting:
 - One Artifact (Weight = 6, Value = 10),
 - One Gold Coin (Weight = 1, Value = 1),
 - One Diamond (Weight = 3, Value = 4).
- Total Weight: $6 + 1 + 3 = 10$.
- Total Value: $10 + 1 + 4 = 15$.

7.4 Dynamic Programming Algorithm Design

7.41 Explanation

7.42 Exercise

7.43 Solution

8 Linear Programming

8.1 Technique Definition And Problem Specification

8.11 Basic Definition

8.12 Exercise

8.13 Solution

9 NP-Completeness

9.1 Definition (no problem/solution required)

9.11 Basic Definition

9.12 Exercise

9.13 Solution

9.2 SAT and 3SAT

9.21 Explanation

9.22 Exercise

9.23 Solution

9.3 Proving NP-Completeness)

9.31 Explanation

9.32 Exercise

9.33 Solution

9.4 Getting Around NP-Completeness (no problem/solution required)

9.41 Explanation

9.42 Exercise

9.43 Solution