

Optimization with Metaheuristics

CSE480 & CSE591- Week 3&4 - Local Search Fundamentals

Asst. Prof. Gizem Süngü Terci

October 23, 2025



Reminder for Metaheuristics

Definition

A **metaheuristic** is a general algorithm that can produce approximate solutions for a **class** of different optimization problems.

Class considers all problems that can be presented in the same optimization structure.

Reminder for Metaheuristics

Definition

A **metaheuristic** is a general algorithm that can produce approximate solutions for a **class** of different optimization problems.

Class considers all problems that can be presented in the same optimization structure.

Graph Coloring Problem

Reminder for Metaheuristics

Definition

A **metaheuristic** is a general algorithm that can produce approximate solutions for a **class** of different optimization problems.

Class considers all problems that can be presented in the same optimization structure.

University Timetabling \longrightarrow Graph Coloring Problem

Reminder for Metaheuristics

Definition

A **metaheuristic** is a general algorithm that can produce approximate solutions for a **class** of different optimization problems.

Class considers all problems that can be presented in the same optimization structure.


University Timetabling \longrightarrow Graph Coloring Problem \longleftarrow Map Coloring

Reminder for Metaheuristics

Definition

A **metaheuristic** is a general algorithm that can produce approximate solutions for a **class** of different optimization problems.

Class considers all problems that can be presented in the same optimization structure.
Why are metaheuristics general methods?



Random Sampling

- Random Sampling: Very first optimization algorithm.
- Recall JSSP: a Gantt chart for m machines and n jobs as an integer string of length $m \times n$.

	+++++
	instance B with 2 jobs and 2 machines
	2 2
job 0	0 10 1 20
job 1	1 20 0 10
	+++++

1. Put each of the numbers from 0 to $n - 1$ exactly m times in an integer array of length $m \times n$ (so we have a valid point $x_0 \in \mathcal{X}$), then
2. Randomly shuffle the values like a deck of cards (so we get a **random** valid point $x \in \mathcal{X}$), and
3. Apply the representation mapping γ to get a Gantt chart $y = \gamma(x)$, $y \in \mathcal{Y}$.

Experiment and Analysis



Experimental Study

Benchmark Instances


abz7

la24


swv15

yn4


Experimental Study




Experimental Study




Experimental Study




Experimental Study




Experimental Study




Experimental Study




Experimental Study



Experimental Study



Experimental Study



So what do we get?

- I execute the program 101 times for each of the instances abz7, la24, swv15, and yn4


So what do we get?

- I execute the program 101 times for each of the instances abz7, la24, swv15, and yn4

	makespan				last improvement	
\mathcal{I}	best	mean	med	sd	med(t)	med(FEs)
abz7	1'131	1'334	1'326	106	0s	1
la24	1'487	1'842	1'814	165	0s	1
swv15	5'935	6'600	6'563	346	0s	1
yn4	1'754	2'036	2'039	125	0s	1


So what do we get?

Median solution for abz7



So what do we get?


Median solution for abz7



... there is lots of white space between the operations...

So what do we get?


Median solution for 1a24



... there is lots of white space between the operations. . .

So what do we get?


Median solution for swv15



... there is lots of white space between the operations. . .

So what do we get?

Median solution for yn4



... there is lots of white space between the operations. . .

So what do we get?

- I execute the program 101 times for each of the instances abz7, la24, swv15, and yn4
- The results are not good, there is lots of white space \equiv wasted time.

	makespan				last improvement	
\mathcal{I}	best	mean	med	sd	med(t)	med(FEs)
abz7	1'131	1'334	1'326	106	0s	1
la24	1'487	1'842	1'814	165	0s	1
swv15	5'935	6'600	6'563	346	0s	1
yn4	1'754	2'036	2'039	125	0s	1

So what do we get?

- I execute the program 101 times for each of the instances abz7, la24, swv15, and yn4
- The results are not good, there is lots of white space \equiv wasted time. That was expected: Our solutions are random.

	makespan				last improvement	
\mathcal{I}	best	mean	med	sd	med(t)	med(FEs)
abz7	1'131	1'334	1'326	106	0s	1
la24	1'487	1'842	1'814	165	0s	1
swv15	5'935	6'600	6'563	346	0s	1
yn4	1'754	2'036	2'039	125	0s	1

So what do we get?

- I execute the program 101 times for each of the instances abz7, 1a24, swv15, and yn4
- The results are not good, there is lots of white space \equiv wasted time. That was expected: Our solutions are random.
- Notice 1. We can create and test the schedules very very fast (much faster than 3min).

	makespan				last improvement	
\mathcal{I}	best	mean	med	sd	med(t)	med(FEs)
abz7	1'131	1'334	1'326	106	0s	1
1a24	1'487	1'842	1'814	165	0s	1
swv15	5'935	6'600	6'563	346	0s	1
yn4	1'754	2'036	2'039	125	0s	1

So what do we get?

- I execute the program 101 times for each of the instances abz7, 1a24, swv15, and yn4
- The results are not good, there is lots of white space \equiv wasted time. That was expected: Our solutions are random.
- Notice 1. We can create and test the schedules very very fast (much faster than 3min).
- **Notice 2. There is a high variance in the results due to randomness.**

	makespan				last improvement	
\mathcal{I}	best	mean	med	sd	med(t)	med(FEs)
abz7	1'131	1'334	1'326	106	0s	1
1a24	1'487	1'842	1'814	165	0s	1
swv15	5'935	6'600	6'563	346	0s	1
yn4	1'754	2'036	2'039	125	0s	1

Exploit Variance: Random Sampling

We can keep generating schedules until the 3 minutes are up and keep the best one.

New idea: The Random sampling algorithm (also called random search) repeats creating random solutions until the computational budget is exhausted.


It works as follows:

- create new random candidate solution y (via random sampling from the search space)
- remember best solution ever encountered
- repeat until 3 min are exhausted

Experiment and Analysis 2



Experimental Study



So what do we get?

- I execute the program 101 times for each of the instances abz7, la24, swv15, and yn4


So what do we get?

- I execute the program 101 times for each of the instances abz7, la24, swv15, and yn4

\mathcal{I}	algo	makespan				last improvement	
		best	mean	med	sd	med(t)	med(FEs)
abz7	1rs	1131	1334	1326	106	0s	1
	rs	895	947	949	12	85s	6'512'505
la24	1rs	1487	1842	1814	165	0s	1
	rs	1153	1206	1208	15	82s	15'902'911
swv15	1rs	5935	6600	6563	346	0s	1
	rs	4988	5166	5172	50	87s	5'559'124
yn4	1rs	1754	2036	2039	125	0s	1
	rs	1460	1498	1499	15	76s	4'814'914


So what do we get?

1rs: median result of single random sample algorithm




So what do we get?

rs: median result of 3 min of random sampling algorithm




So what do we get?

1rs: median result of single random sample algorithm




So what do we get?

rs: median result of 3 min of random sampling algorithm




So what do we get?

1rs: median result of single random sample algorithm




So what do we get?

rs: median result of 3 min of random sampling algorithm




So what do we get?

1rs: median result of single random sample algorithm



So what do we get?


rs: median result of 3 min of random sampling algorithm




Progress over Time

What progress does the algorithm make over time?


Progress over Time




Progress over Time



Progress over Time



Progress over Time



Progress over Time

- Law of Diminishing Returns⁶


Progress over Time

- Law of Diminishing Returns⁶: Most improvements (of the makespan) are achieved with the initial, small investment (of runtime).


Progress over Time

- Law of Diminishing Returns⁶: Most improvements (of the makespan) are achieved with the initial, small investment (of runtime). Further improvements will cost more and more (time) and will be smaller and smaller.

Progress over Time







Progress over Time







Progress over Time

- Law of Diminishing Returns⁶: Most improvements (of the makespan) are achieved with the initial, small investment (of runtime). Further improvements will cost more and more (time) and will be smaller and smaller.







Progress over Time

- Law of Diminishing Returns⁶: Most improvements (of the makespan) are achieved with the initial, small investment (of runtime). Further improvements will cost more and more (time) and will be smaller and smaller.



Progress over Time

- Law of Diminishing Returns⁶: Most improvements (of the makespan) are achieved with the initial, small investment (of runtime). Further improvements will cost more and more (time) and will be smaller and smaller.
- This holds for runtime, but also for improvements of algorithms.



Information from Good Solutions

- Our first algorithm, random sampling, was not very efficient.
- It does not make any use of the information it “sees” during the optimization process.
- Each search step consists of creating an entirely new, entirely random candidate solution.
- Each search step is thus independent of all prior steps.
- Is this a good idea?
- Probably not.
- In almost all practical scenarios, good solutions are somewhat similar to other good solutions.
- In other words, every good solution we see is some useful information.

Basic Idea

- So how we can make use of the information we have seen during the search?

Basic Idea

- So how we can make use of the information we have seen during the search?
- Instead of generating a completely random new candidate solution in each step. . .

Basic Idea

- So how we can make use of the information we have seen during the search?
- Instead of generating a completely random new candidate solution in each step. . .
- . . . why can't we try to iteratively improve the best solution we have seen so far?

Stochastic Hill Climbing

- This is the concept of **Local Search**²⁻⁵ and its simplest realization is **Stochastic Hill Climbing**².

Stochastic Hill Climbing

- This is the concept of **Local Search**²⁻⁵ and its simplest realization is **Stochastic Hill Climbing**².
- Simple Concept



Stochastic Hill Climbing

- This is the concept of **Local Search**²⁻⁵ and its simplest realization is **Stochastic Hill Climbing**².
- Simple Concept:
 1. create random initial solution

Stochastic Hill Climbing

- This is the concept of **Local Search**²⁻⁵ and its simplest realization is **Stochastic Hill Climbing**².
- Simple Concept:
 1. create random initial solution
 2. make a modified copy of best-so-far solution

Stochastic Hill Climbing

- This is the concept of **Local Search**²⁻⁵ and its simplest realization is **Stochastic Hill Climbing**².
- Simple Concept:
 1. create random initial solution
 2. make a modified copy of best-so-far solution
 3. if it is better, it becomes the new best-so-far solution (if it is not better, discard it).

Stochastic Hill Climbing

- This is the concept of **Local Search**²⁻⁵ and its simplest realization is **Stochastic Hill Climbing**².
- Simple Concept:
 1. create random initial solution
 2. make a modified copy of best-so-far solution
 3. if it is better, it becomes the new best-so-far solution (if it is not better, discard it).
 4. go back to 2. (until the time is up)

Causality

- Local searches like hill climbers exploit a property of many optimization problems called **causality**⁶⁻⁹.

Causality

- Local searches like hill climbers exploit a property of many optimization problems called **causality**⁶⁻⁹.
- Causality means that small changes in the features of an object (or candidate solution) also lead to small changes in its behavior (or objective value).

Causality

- Local searches like hill climbers exploit a property of many optimization problems called **causality**⁶⁻⁹.
- Causality means that small changes in the features of an object (or candidate solution) also lead to small changes in its behavior (or objective value).
- If an optimization problem exhibits causality, then there should be good solutions that are similar to other good solutions.

Causality

- Local searches like hill climbers exploit a property of many optimization problems called **causality**⁶⁻⁹.
- Causality means that small changes in the features of an object (or candidate solution) also lead to small changes in its behavior (or objective value).
- If an optimization problem exhibits causality, then there should be good solutions that are similar to other good solutions.
- The idea is that if we have a good candidate solution, then there may exist similar solutions which are better.

Causality

- Local searches like hill climbers exploit a property of many optimization problems called **causality**⁶⁻⁹.
- Causality means that small changes in the features of an object (or candidate solution) also lead to small changes in its behavior (or objective value).
- If an optimization problem exhibits causality, then there should be good solutions that are similar to other good solutions.
- The idea is that if we have a good candidate solution, then there may exist similar solutions which are better.
- We hope to find one of them and then continue trying to do the same from there.

Ingredient: Unary Search Operator



Unary Search Operator

- Our hill climber must be able to make modified copies of an existing point $x \in \mathbb{X}$ in order to find these better points.

Unary Search Operator

- Our hill climber must be able to make modified copies of an existing point $x \in \mathbb{X}$ in order to find these better points.
- A unary search operator accepts an existing point $x \in \mathbb{X}$ and creates a modified copy of it.

Unary Search Operator

- Our hill climber must be able to make modified copies of an existing point $x \in \mathbb{X}$ in order to find these better points.
- A unary search operator accepts an existing point $x \in \mathbb{X}$ and creates a modified copy of it.
- It must make sure that the modified copy is still a valid element of \mathbb{X} .

Unary Search Operator

- Our hill climber must be able to make modified copies of an existing point $x \in \mathbb{X}$ in order to find these better points.
- A unary search operator accepts an existing point $x \in \mathbb{X}$ and creates a modified copy of it.
- It must make sure that the modified copy is still a valid element of \mathbb{X} .
- It should ideally be randomized, i.e., applying it twice to the same point x should yield different results.

Unary Search Operator

- Our hill climber must be able to make modified copies of an existing point $x \in \mathbb{X}$ in order to find these better points.
- A unary search operator accepts an existing point $x \in \mathbb{X}$ and creates a modified copy of it.
- It must make sure that the modified copy is still a valid element of \mathbb{X} .
- It should ideally be randomized, i.e., applying it twice to the same point x should yield different results.
- How can we implement this for our JSSP scenario?

Unary Search Operator

- Our hill climber must be able to make modified copies of an existing point $x \in \mathbb{X}$ in order to find these better points.
- A unary search operator accepts an existing point $x \in \mathbb{X}$ and creates a modified copy of it.
- It must make sure that the modified copy is still a valid element of \mathbb{X} .
- It should ideally be randomized, i.e., applying it twice to the same point x should yield different results.
- How can we implement this for our JSSP scenario?
- **Easy: Just swap two (different) job IDs in the string!**

Unary Search Operator

- Our hill climber must be able to make modified copies of an existing point $x \in \mathbb{X}$ in order to find these better points.
- A unary search operator accepts an existing point $x \in \mathbb{X}$ and creates a modified copy of it.
- It must make sure that the modified copy is still a valid element of \mathbb{X} .
- It should ideally be randomized, i.e., applying it twice to the same point x should yield different results.
- How can we implement this for our JSSP scenario?
- **Easy: Just swap two (different) job IDs in the string!**
- Since the numbers of occurrences of the IDs will not change, the new strings will be valid.

Example for our 1swap Operator



(2,0,1,0,1,1,2,3,2,3,
2,0,0,1,3,3,2,3,1,0)

Example for our 1swap Operator


X

(2,0,1,0,1,1,2,3,2,3,
2,0,0,1,3,3,2,3,1,0)



makespan: 180

Y



Example for our 1swap Operator


X

(2,0,1,0,1,1,2,3,2,3,
2,0,0,1,3,3,2,3,1,0)



makespan: 180

Y



Example for our 1swap Operator

X

(2,0,1,0,1,1,2,3,2,3,
2,0,0,1,3,3,2,3,1,0)


1swap

(2,0,1,0,1,1,2,3,2,3,
2,0,3,1,3,0,2,3,1,0)



makespan: 180

Y



Example for our 1swap Operator

X

(2,0,1,0,1,1,2,3,2,3,
2,0,0,1,3,3,2,3,1,0)


1swap

(2,0,1,0,1,1,2,3,2,3,
2,0,3,1,3,0,2,3,1,0)




makespan: 180

Y



makespan: 195



Example for our 1swap Operator

X

(2,0,1,0,1,1,2,3,2,3,
2,0,0,1,3,3,2,3,1,0)


1swap

(2,0,1,0,1,1,2,3,2,3,
2,0,3,1,3,0,2,3,1,0)




makespan: 180

Y



makespan: 195



Example for our 1swap Operator

X

(2,0,1,0,1,1,2,3,2,3,
2,0,0,1,3,3,2,3,1,0)


1swap

(2,0,1,0,1,1,2,3,2,3,
2,0,3,1,3,0,2,3,1,0)




makespan: 180

Y



makespan: 195



Experiment and Analysis



So what do we get?

- I execute the program 101 times for each of the instances abz7, la24, swv15, and yn4


So what do we get?

- I execute the program 101 times for each of the instances abz7, la24, swv15, and yn4

\mathcal{I}	algo	makespan				last improvement	
		best	mean	med	sd	med(t)	med(FEs)
abz7	rs	895	947	949	12	85s	6'512'505
	hc_1swap	717	800	798	28	0s	16'978
la24	rs	1153	1206	1208	15	82s	15'902'911
	hc_1swap	999	1095	1086	56	0s	6'612
swv15	rs	4988	5166	5172	50	87s	5'559'124
	hc_1swap	3837	4108	4108	137	1s	104'598
yn4	rs	1460	1498	1499	15	76s	4'814'914
	hc_1swap	1109	1222	1220	48	0s	31'789


So what do we get?

rs: median result of 3 min of random sampling




So what do we get?

hc_1swap: median result of 3 min of hill climber




So what do we get?

rs: median result of 3 min of random sampling




So what do we get?

hc_1swap: median result of 3 min of hill climber




So what do we get?

rs: median result of 3 min of random sampling




So what do we get?

hc_1swap: median result of 3 min of hill climber




So what do we get?

rs: median result of 3 min of random sampling



So what do we get?

hc_1swap: median result of 3 min of hill climber




Progress over Time

What progress does the algorithm make over time?


Progress over Time

What progress does the algorithm make over time?



Progress over Time


What progress does the algorithm make over time?



First we have much progress. . .

Progress over Time


What progress does the algorithm make over time?



First we have much progress. . .

Progress over Time


What progress does the algorithm make over time?



First we have much progress. . .

Progress over Time


What progress does the algorithm make over time?



First we have much progress. . .

Progress over Time

What progress does the algorithm make over time?




First we have much progress. . .
... but then the hill climber stagnates!

But we waste time...

What if we look at this without log-scaling the time axis?


But we waste time...

What if we look at this without log-scaling the time axis?



But we waste time...


What if we look at this without log-scaling the time axis?



Then it looks even much worse!

But we waste time...


What if we look at this without log-scaling the time axis?



Then it looks even much worse!

But we waste time...


What if we look at this without log-scaling the time axis?



Then it looks even much worse!

But we waste time...

What if we look at this without log-scaling the time axis?



Then it looks even much worse!

Indeed, we waste time!

\mathcal{I}	algo	makespan				last improvement	
		best	mean	med	sd	med(t)	med(FEs)
abz7	rs	895	947	949	12	85s	6'512'505
	hc_1swap	717	800	798	28	0s	16'978
la24	rs	1153	1206	1208	15	82s	15'902'911
	hc_1swap	999	1095	1086	56	0s	6'612
swv15	rs	4988	5166	5172	50	87s	5'559'124
	hc_1swap	3837	4108	4108	137	1s	104'598
yn4	rs	1460	1498	1499	15	76s	4'814'914
	hc_1swap	1109	1222	1220	48	0s	31'789

Indeed, we waste time!

		makespan				last improvement	
\mathcal{I}	algo	best	mean	med	sd	med(t)	med(FEs)
abz7	rs	895	947	949	12	85s	6'512'505
	hc_1swap	717	800	798	28	0s	16'978
la24	rs	1153	1206	1208	15	82s	15'902'911
	hc_1swap	999	1095	1086	56	0s	6'612
swv15	rs	4988	5166	5172	50	87s	5'559'124
	hc_1swap	3837	4108	4108	137	1s	104'598
yn4	rs	1460	1498	1499	15	76s	4'814'914
	hc_1swap	1109	1222	1220	48	0s	31'789

Indeed, we waste time!

\mathcal{I}	algo	makespan				last improvement	
		best	mean	med	sd	med(t)	med(FEs)
abz7	rs	895	947	949	12	85s	6'512'505
	hc_1swap	717	800	798	28	0s	16'978
la24	rs	1153	1206	1208	15	82s	15'902'911
	hc_1swap	999	1095	1086	56	0s	6'612
swv15	rs	4988	5166	5172	50	87s	5'559'124
	hc_1swap	3837	4108	4108	137	1s	104'598
yn4	rs	1460	1498	1499	15	76s	4'814'914
	hc_1swap	1109	1222	1220	48	0s	31'789

- We have three minutes but after about 1 second, our hc_1swap algorithm stops improving!

Premature Convergence

- Our algorithm makes most of its progress early during the search.

Premature Convergence

- Our algorithm makes most of its progress early during the search.
- Later, it basically stagnates and cannot improve.

Premature Convergence

- Our algorithm makes most of its progress early during the search.
- Later, it basically stagnates and cannot improve.
- Why is that?

Premature Convergence

- Our algorithm makes most of its progress early during the search.
- Later, it basically stagnates and cannot improve.
- Why is that?
- The search operator 1swap defines a neighborhood $N(x) \subset \mathbb{X}$ around a point x .

Premature Convergence

- Our algorithm makes most of its progress early during the search.
- Later, it basically stagnates and cannot improve.
- Why is that?
- The search operator 1swap defines a neighborhood $N(x) \subset \mathbb{X}$ around a point x .
- The hill climber can only find solutions which are in the neighborhood of the current best solution.

Premature Convergence

- Our algorithm makes most of its progress early during the search.
- Later, it basically stagnates and cannot improve.
- Why is that?
- The search operator `1swap` defines a neighborhood $N(x) \subset \mathbb{X}$ around a point x .
- The hill climber can only find solutions which are in the neighborhood of the current best solution.
- Only the schedules that I can reach by swapping two operations of two different jobs.

Premature Convergence

- Our algorithm makes most of its progress early during the search.
- Later, it basically stagnates and cannot improve.
- Why is that?
- The search operator `1swap` defines a neighborhood $N(x) \subset \mathbb{X}$ around a point x .
- The hill climber can only find solutions which are in the neighborhood of the current best solution.
- Only the schedules that I can reach by swapping two operations of two different jobs.
- Clearly $|N(x)| \lll |\mathbb{X}|$

Premature Convergence

- Our algorithm makes most of its progress early during the search.
- Later, it basically stagnates and cannot improve.
- Why is that?
- The search operator `1swap` defines a neighborhood $N(x) \subset \mathbb{X}$ around a point x .
- The hill climber can only find solutions which are in the neighborhood of the current best solution.
- Only the schedules that I can reach by swapping two operations of two different jobs.
- Clearly $|N(x)| \lll |\mathbb{X}|$
- What happens if $f(\gamma(x^\times)) \leq f(\gamma(x)) \forall x \in N(x^\times)$ but x^\times is not the global optimum?


Premature Convergence

- Our algorithm makes most of its progress early during the search.
- Later, it basically stagnates and cannot improve.
- Why is that?
- The search operator 1swap defines a neighborhood $N(x) \subset \mathbb{X}$ around a point x .
- The hill climber can only find solutions which are in the neighborhood of the current best solution.
- Only the schedules that I can reach by swapping two operations of two different jobs.
- Clearly $|N(x)| \lll |\mathbb{X}|$
- What happens if $f(\gamma(x^\times)) \leq f(\gamma(x)) \forall x \in N(x^\times)$ but x^\times is not the global optimum?
- Our algorithm gets trapped in the **local optimum** x^\times and cannot escape!

Premature Convergence

- Our algorithm makes most of its progress early during the search.
- Later, it basically stagnates and cannot improve.
- Why is that?
- The search operator 1swap defines a neighborhood $N(x) \subset \mathbb{X}$ around a point x .
- The hill climber can only find solutions which are in the neighborhood of the current best solution.
- Only the schedules that I can reach by swapping two operations of two different jobs.
- Clearly $|N(x)| \lll |\mathbb{X}|$
- What happens if $f(\gamma(x^\times)) \leq f(\gamma(x)) \forall x \in N(x^\times)$ but x^\times is not the global optimum?
- Our algorithm gets trapped in the **local optimum** x^\times and cannot escape!
- This is called **Premature Convergence**.^{8 9}

Premature Convergence



Improved Algorithm Concept 1



Stochastic Hill Climber with Restarts

- Idea: We have seen that the results of the hill climber exhibit a relatively **high standard deviation**.

\mathcal{I}	algo	makespan				last improvement	
		best	mean	med	sd	med(t)	med(FEs)
abz7	rs	895	947	949	12	85s	6'512'505
	hc_1swap	717	800	798	28	0s	16'978
la24	rs	1153	1206	1208	15	82s	15'902'911
	hc_1swap	999	1095	1086	56	0s	6'612
swv15	rs	4988	5166	5172	50	87s	5'559'124
	hc_1swap	3837	4108	4108	137	1s	104'598
yn4	rs	1460	1498	1499	15	76s	4'814'914
	hc_1swap	1109	1222	1220	48	0s	31'789

Stochastic Hill Climber with Restarts

- Idea: We have seen that the results of the hill climber exhibit a relatively high standard deviation.
- At the same time, a single *run* of the algorithm **converges quickly**.

\mathcal{I}	algo	makespan				last improvement	
		best	mean	med	sd	med(t)	med(FEs)
abz7	rs	895	947	949	12	85s	6'512'505
	hc_1swap	717	800	798	28	0s	16'978
la24	rs	1153	1206	1208	15	82s	15'902'911
	hc_1swap	999	1095	1086	56	0s	6'612
swv15	rs	4988	5166	5172	50	87s	5'559'124
	hc_1swap	3837	4108	4108	137	1s	104'598
yn4	rs	1460	1498	1499	15	76s	4'814'914
	hc_1swap	1109	1222	1220	48	0s	31'789

Stochastic Hill Climber with Restarts

- Idea: We have seen that the results of the hill climber exhibit a relatively high standard deviation.
- At the same time, a single *run* of the algorithm converges quickly.
- Let us exploit this variance!

Stochastic Hill Climber with Restarts

- Idea: We have seen that the results of the hill climber exhibit a relatively high standard deviation.
- At the same time, a single *run* of the algorithm converges quickly.
- Let us exploit this variance!
- Idea: If we did not make any progress for a number L of algorithm steps, we simply restart at a new random solution.

Stochastic Hill Climber with Restarts

- Idea: We have seen that the results of the hill climber exhibit a relatively high standard deviation.
- At the same time, a single *run* of the algorithm converges quickly.
- Let us exploit this variance!
- Idea: If we did not make any progress for a number L of algorithm steps, we simply restart at a new random solution.
- Of course, we will always remember the overall best solution we ever had (in another variable).

Configuring the Algorithm: Parameter L

- We now have an algorithm which, in theory, should be able to utilize some of the variance that we observe in the results of `hc_1swap`.

Configuring the Algorithm: Parameter L

- We now have an algorithm which, in theory, should be able to utilize some of the variance that we observe in the results of `hc_1swap`.
- We got one problem, though . . .

Configuring the Algorithm: Parameter L

- We now have an algorithm which, in theory, should be able to utilize some of the variance that we observe in the results of `hc_1swap`.
- We got one problem, though actually, it is not just one algorithm, it is an algorithm with a **parameter** L : `hcr_L_1swap`.


Configuring the Algorithm: Parameter L

- We now have an algorithm which, in theory, should be able to utilize some of the variance that we observe in the results of `hc_1swap`.
- We got one problem, though actually, it is not just one algorithm, it is an algorithm with a **parameter** L : `hcr_L_1swap`.
- What do we do with that?

Configuring the Algorithm: Parameter L

- We now have an algorithm which, in theory, should be able to utilize some of the variance that we observe in the results of `hc_1swap`.
- We got one problem, though actually, it is not just one algorithm, it is an algorithm with a **parameter** L : `hcr_L_1swap`.
- What do we do with that?
- Let's take a look.

Configuring the Algorithm: Parameter L



Configuring the Algorithm: Parameter L

- We now have an algorithm which, in theory, should be able to utilize some of the variance that we observe in the results of `hc_1swap`.
- We got one problem, though actually, it is not just one algorithm, it is an algorithm with a **parameter** L : `hcr_L_1swap`.
- What do we do with that?
- Let's take a look.
- If we choose L too small, we will restart the algorithm too early

Configuring the Algorithm: Parameter L

- We now have an algorithm which, in theory, should be able to utilize some of the variance that we observe in the results of `hc_1swap`.
- We got one problem, though actually, it is not just one algorithm, it is an algorithm with a **parameter** L : `hcr_L_1swap`.
- What do we do with that?
- Let's take a look.
- If we choose L too small, we will restart the algorithm too early, before it even arrives in a local optimum

Configuring the Algorithm: Parameter L

- We now have an algorithm which, in theory, should be able to utilize some of the variance that we observe in the results of `hc_1swap`.
- We got one problem, though actually, it is not just one algorithm, it is an algorithm with a **parameter** L : `hcr_L_1swap`.
- What do we do with that?
- Let's take a look.
- If we choose L too small, we will restart the algorithm too early, before it even arrives in a local optimum
- If we choose L too large, we will restart too late and thus waste time

Configuring the Algorithm: Parameter L

- We now have an algorithm which, in theory, should be able to utilize some of the variance that we observe in the results of `hc_1swap`.
- We got one problem, though actually, it is not just one algorithm, it is an algorithm with a **parameter** L : `hcr_L_1swap`.
- What do we do with that?
- Let's take a look.
- If we choose L too small, we will restart the algorithm too early, before it even arrives in a local optimum
- If we choose L too large, we will restart too late and thus waste time, that we could have used for more restarts

Configuring the Algorithm: Parameter L

- We now have an algorithm which, in theory, should be able to utilize some of the variance that we observe in the results of `hc_1swap`.
- We got one problem, though actually, it is not just one algorithm, it is an algorithm with a **parameter** L : `hcr_L_1swap`.
- What do we do with that?
- Let's take a look.
- If we choose L too small, we will restart the algorithm too early, before it even arrives in a local optimum
- If we choose L too large, we will restart too late and thus waste time, that we could have used for more restarts
- $L = 2^{14} = 16'384$ seems to be a reasonable choice.

So what do we get?

- I execute the program 101 times for each of the instances abz7, la24, swv15, and yn4


So what do we get?

- I execute the program 101 times for each of the instances abz7, la24, swv15, and yn4

\mathcal{I}	algo	makespan				last improvement	
		best	mean	med	sd	med(t)	med(FEs)
abz7	rs	895	947	949	12	85s	6'512'505
	hc_1swap	717	800	798	28	0s	16'978
	hcr_16384_1swap	714	732	733	6	91s	18'423'530
la24	rs	1153	1206	1208	15	82s	15'902'911
	hc_1swap	999	1095	1086	56	0s	6'612
	hcr_16384_1swap	953	976	976	7	80s	34'437'999
swv15	rs	4988	5166	5172	50	87s	5'559'124
	hc_1swap	3837	4108	4108	137	1s	104'598
	hcr_16384_1swap	3752	3859	3861	42	92s	11'756'497
yn4	rs	1460	1498	1499	15	76s	4'814'914
	hc_1swap	1109	1222	1220	48	0s	31'789
	hcr_16384_1swap	1081	1115	1115	11	91s	14'804'358


So what do we get?

hc_1swap: median result of 3 min of hill climber




So what do we get?

hcr_16384_1swap: median result of 3 min of hill climber which restarts after
 $L = 16'384$ search steps without improvement




So what do we get?

hc_1swap: median result of 3 min of hill climber




So what do we get?

hcr_16384_1swap: median result of 3 min of hill climber which restarts after $L = 16'384$ search steps without improvement




So what do we get?

hc_1swap: median result of 3 min of hill climber




So what do we get?

hcr_16384_1swap: median result of 3 min of hill climber which restarts after $L = 16'384$ search steps without improvement



So what do we get?


hcr_16384_1swap: median result of 3 min of hill climber which restarts after
 $L = 16'384$ search steps without improvement



Progress over Time


What progress does the algorithm make over time?

Progress over Time



What progress does the algorithm make over time?


Progress over Time



What progress does the algorithm make over time?

- First it behaves like the normal hill climber


Progress over Time



What progress does the algorithm make over time?

- First it behaves like the normal hill climber
- But it keeps improving.


Progress over Time



What progress does the algorithm make over time?

- First it behaves like the normal hill climber
- But it keeps improving.


Progress over Time



What progress does the algorithm make over time?

- First it behaves like the normal hill climber
- But it keeps improving.


Progress over Time



What progress does the algorithm make over time?

- First it behaves like the normal hill climber
- But it keeps improving.


Progress over Time



What progress does the algorithm make over time?

- First it behaves like the normal hill climber
- But it keeps improving.


Progress over Time



What progress does the algorithm make over time?

- First it behaves like the normal hill climber
- But it keeps improving.
- Although we still do not use the available time very well. . .


Progress over Time



What progress does the algorithm make over time?

- First it behaves like the normal hill climber
- But it keeps improving.
- Although we still do not use the available time very well. . .


Progress over Time



What progress does the algorithm make over time?

- First it behaves like the normal hill climber
- But it keeps improving.
- Although we still do not use the available time very well. . .

Progress over Time



What progress does the algorithm make over time?

- First it behaves like the normal hill climber
- But it keeps improving.
- Although we still do not use the available time very well. . .

Improved Algorithm Concept 2



Drawbacks of Restarts

- A restarted algorithm is still the same algorithm, just restarted.

Drawbacks of Restarts

- A restarted algorithm is still the same algorithm, just restarted.
- If there are many more local optima than global optima, every restart will probably end again in a local optimum.

Drawbacks of Restarts

- A restarted algorithm is still the same algorithm, just restarted.
- If there are many more local optima than global optima, every restart will probably end again in a local optimum.
- If there are many more “bad” local optima than “good” local optima, every restart will probably end in a “bad” local optimum.

Drawbacks of Restarts

- A restarted algorithm is still the same algorithm, just restarted.
- If there are many more local optima than global optima, every restart will probably end again in a local optimum.
- If there are many more “bad” local optima than “good” local optima, every restart will probably end in a “bad” local optimum.
- While restarts improve the chance to find better solutions, they cannot solve the intrinsic shortcomings of an algorithm.

Drawbacks of Restarts

- A restarted algorithm is still the same algorithm, just restarted.
- If there are many more local optima than global optima, every restart will probably end again in a local optimum.
- If there are many more “bad” local optima than “good” local optima, every restart will probably end in a “bad” local optimum.
- While restarts improve the chance to find better solutions, they cannot solve the intrinsic shortcomings of an algorithm.
- Another problem is: With every restart we throw away all accumulated knowledge and information of the current run.

Drawbacks of Restarts

- A restarted algorithm is still the same algorithm, just restarted.
- If there are many more local optima than global optima, every restart will probably end again in a local optimum.
- If there are many more “bad” local optima than “good” local optima, every restart will probably end in a “bad” local optimum.
- While restarts improve the chance to find better solutions, they cannot solve the intrinsic shortcomings of an algorithm.
- Another problem is: With every restart we throw away all accumulated knowledge and information of the current run.
- Restarts are therefore also wasteful.

How else can we stop premature convergence?

- Our `hc_1swap` hill climber will stop improving if it can no longer find better solutions.

How else can we stop premature convergence?

- Our `hc_1swap` hill climber will stop improving if it can no longer find better solutions.
- This happens when it reaches a local optimum.

How else can we stop premature convergence?

- Our `hc_1swap` hill climber will stop improving if it can no longer find better solutions.
- This happens when it reaches a local optimum.
- A local optimum is a point x^\times in \mathbb{X} where no 1swap-move can yield any improvement.

How else can we stop premature convergence?

- Our `hc_1swap` hill climber will stop improving if it can no longer find better solutions.
- This happens when it reaches a local optimum.
- A local optimum is a point x^\times in \mathbb{X} where no 1swap-move can yield any improvement.
- It does not matter which two job ids I exchange in the current best string x^\times , the result is not better than x^\times .

How else can we stop premature convergence?

- Our `hc_1swap` hill climber will stop improving if it can no longer find better solutions.
- This happens when it reaches a local optimum.
- A local optimum is a point x^\times in \mathbb{X} where no **1swap-move** can yield any improvement.
- It does not matter which **two job ids I exchange** in the current best string x^\times , the result is not better than x^\times .
- Notice: Whether or not a point x is a local optimum, is determined entirely by the **unary search operator**!

How else can we stop premature convergence?

- Our `hc_1swap` hill climber will stop improving if it can no longer find better solutions.
- This happens when it reaches a local optimum.
- A local optimum is a **point** x^\times in \mathbb{X} where no 1swap-move can yield any improvement.
- It does not matter which two job ids I exchange in the current best **string** x^\times , the result is not better than x^\times .
- Notice: Whether or not a point x is a local optimum, is determined entirely by the unary search operator!
- If we had a different operator with a bigger neighborhood, then maybe x^\times would no longer be a local optimum and we could still improve the results after reaching it. . .

Making the neighborhood bigger

- Two solutions x_1 and x_2 are “neighbors” if I can reach x_2 by applying the search operator one time to x_1 .

Making the neighborhood bigger

- Two solutions x_1 and x_2 are “neighbors” if I can reach x_2 by applying the search operator one time to x_1 .
- The search operator determines which solutions are “neighbors”.

Making the neighborhood bigger

- Two solutions x_1 and x_2 are “neighbors” if I can reach x_2 by applying the search operator one time to x_1 .
- The search operator determines which solutions are “neighbors”.
- The neighborhood determines what a local optimum is.

Making the neighborhood bigger

- Two solutions x_1 and x_2 are “neighbors” if I can reach x_2 by applying the search operator one time to x_1 .
- The search operator determines which solutions are “neighbors”.
- The neighborhood determines what a local optimum is.
- Let's make it bigger.

Making the neighborhood bigger

- Two solutions x_1 and x_2 are “neighbors” if I can reach x_2 by applying the search operator one time to x_1 .
- The search operator determines which solutions are “neighbors”.
- The neighborhood determines what a local optimum is.
- Let's make it bigger.
- It always helps to think about the extreme cases first.

Making the neighborhood bigger

- Two solutions x_1 and x_2 are “neighbors” if I can reach x_2 by applying the search operator one time to x_1 .
- The search operator determines which solutions are “neighbors”.
- The neighborhood determines what a local optimum is.
- Let’s make it bigger.
- It always helps to think about the extreme cases first.
- On one hand, we already have 1swap, which swaps two jobs.

Making the neighborhood bigger

- Two solutions x_1 and x_2 are “neighbors” if I can reach x_2 by applying the search operator one time to x_1 .
- The search operator determines which solutions are “neighbors”.
- The neighborhood determines what a local optimum is.
- Let’s make it bigger.
- It always helps to think about the extreme cases first.
- On one hand, we already have 1swap, which swaps two jobs. This is the smallest step I can imagine.

Making the neighborhood bigger

- Two solutions x_1 and x_2 are “neighbors” if I can reach x_2 by applying the search operator one time to x_1 .
- The search operator determines which solutions are “neighbors”.
- The neighborhood determines what a local optimum is.
- Let’s make it bigger.
- It always helps to think about the extreme cases first.
- On one hand, we already have 1swap, which swaps two jobs. This is the smallest step I can imagine.
- On the other end of the spectrum, we could simply swap all jobs in our points x randomly.

Making the neighborhood bigger

- Two solutions x_1 and x_2 are “neighbors” if I can reach x_2 by applying the search operator one time to x_1 .
- The search operator determines which solutions are “neighbors”.
- The neighborhood determines what a local optimum is.
- Let’s make it bigger.
- It always helps to think about the extreme cases first.
- On one hand, we already have 1swap, which swaps two jobs. This is the smallest step I can imagine.
- On the other end of the spectrum, we could simply swap all jobs in our points x randomly. Is this a good idea?

Making the neighborhood bigger

- Two solutions x_1 and x_2 are “neighbors” if I can reach x_2 by applying the search operator one time to x_1 .
- The search operator determines which solutions are “neighbors”.
- The neighborhood determines what a local optimum is.
- Let’s make it bigger.
- It always helps to think about the extreme cases first.
- On one hand, we already have 1swap, which swaps two jobs. This is the smallest step I can imagine.
- On the other end of the spectrum, we could simply swap all jobs in our points x randomly. Is this a good idea? Probably not: It would turn our algorithm into random sampling!

Making the neighborhood bigger

- Two solutions x_1 and x_2 are “neighbors” if I can reach x_2 by applying the search operator one time to x_1 .
- The search operator determines which solutions are “neighbors”.
- The neighborhood determines what a local optimum is.
- Let's make it bigger.
- It always helps to think about the extreme cases first.
- On one hand, we already have 1swap, which swaps two jobs. This is the smallest step I can imagine.
- On the other end of the spectrum, we could simply swap all jobs in our points x randomly. Is this a good idea? Probably not: It would turn our algorithm into random sampling!
- We should respect the causality: small changes to the solution cause small changes in the objective value – big changes will lead to unpredictable results.

Making the neighborhood bigger

- Idea: Let's most often swap 2 jobs

Making the neighborhood bigger

- Idea: Let's most often swap 2 jobs, but sometimes 3

Making the neighborhood bigger

- Idea: Let's most often swap 2 jobs, but sometimes 3, less often 4

Making the neighborhood bigger

- Idea: Let's most often swap 2 jobs, but sometimes 3, less often 4, from time to time 5

Making the neighborhood bigger

- Idea: Let's most often swap 2 jobs, but sometimes 3, less often 4, from time to time 5, rarely 6

Making the neighborhood bigger

- Idea: Let's most often swap 2 jobs, but sometimes 3, less often 4, from time to time 5, rarely 6, hardly ever 7

Making the neighborhood bigger

- Idea: Let's most often swap 2 jobs, but sometimes 3, less often 4, from time to time 5, rarely 6, hardly ever 7, ...

Making the neighborhood bigger

- Idea: Let's most often swap 2 jobs, but sometimes 3, less often 4, from time to time 5, rarely 6, hardly ever 7, ...
- nswap operator idea

Making the neighborhood bigger

- Idea: Let's most often swap 2 jobs, but sometimes 3, less often 4, from time to time 5, rarely 6, hardly ever 7, ...
- nswap operator idea:
 1. flip a coin: if it is heads (50% probability), we will swap 2 job ids (and stop).

Making the neighborhood bigger

- Idea: Let's most often swap 2 jobs, but sometimes 3, less often 4, from time to time 5, rarely 6, hardly ever 7, ...
- nswap operator idea:
 1. flip a coin: if it is heads (50% probability), we will swap 2 job ids (and stop).
 2. otherwise (it was tail), we again flip a coin.

Making the neighborhood bigger

- Idea: Let's most often swap 2 jobs, but sometimes 3, less often 4, from time to time 5, rarely 6, hardly ever 7, ...
- nswap operator idea:
 1. flip a coin: if it is heads (50% probability), we will swap 2 job ids (and stop).
 2. otherwise (it was tail), we again flip a coin. if it is heads (50% probability, now 25% in total), we will swap 3 job ids (and stop).

Making the neighborhood bigger

- Idea: Let's most often swap 2 jobs, but sometimes 3, less often 4, from time to time 5, rarely 6, hardly ever 7, ...
- nswap operator idea:
 1. flip a coin: if it is heads (50% probability), we will swap 2 job ids (and stop).
 2. otherwise (it was tail), we again flip a coin. if it is heads (50% probability, now 25% in total), we will swap 3 job ids (and stop).
 3. otherwise (it was tail), we again flip a coin.

Making the neighborhood bigger

- Idea: Let's most often swap 2 jobs, but sometimes 3, less often 4, from time to time 5, rarely 6, hardly ever 7, ...
- nswap operator idea:
 1. flip a coin: if it is heads (50% probability), we will swap 2 job ids (and stop).
 2. otherwise (it was tail), we again flip a coin. if it is heads (50% probability, now 25% in total), we will swap 3 job ids (and stop).
 3. otherwise (it was tail), we again flip a coin. if it is heads (50% probability, now 12.5% in total), we will swap 4 job ids (and stop).

Making the neighborhood bigger

- Idea: Let's most often swap 2 jobs, but sometimes 3, less often 4, from time to time 5, rarely 6, hardly ever 7, ...
- nswap operator idea:
 1. flip a coin: if it is heads (50% probability), we will swap 2 job ids (and stop).
 2. otherwise (it was tail), we again flip a coin. if it is heads (50% probability, now 25% in total), we will swap 3 job ids (and stop).
 3. otherwise (it was tail), we again flip a coin. if it is heads (50% probability, now 12.5% in total), we will swap 4 job ids (and stop).
 4. otherwise (it was tail), we again flip a coin.

Making the neighborhood bigger

- Idea: Let's most often swap 2 jobs, but sometimes 3, less often 4, from time to time 5, rarely 6, hardly ever 7, ...
- nswap operator idea:
 1. flip a coin: if it is heads (50% probability), we will swap 2 job ids (and stop).
 2. otherwise (it was tail), we again flip a coin. if it is heads (50% probability, now 25% in total), we will swap 3 job ids (and stop).
 3. otherwise (it was tail), we again flip a coin. if it is heads (50% probability, now 12.5% in total), we will swap 4 job ids (and stop).
 4. otherwise (it was tail), we again flip a coin. if it is heads (50% probability, now 6.25% in total), we will swap 5 job ids (and stop).

Making the neighborhood bigger

- Idea: Let's most often swap 2 jobs, but sometimes 3, less often 4, from time to time 5, rarely 6, hardly ever 7, ...
- nswap operator idea:
 1. flip a coin: if it is heads (50% probability), we will swap 2 job ids (and stop).
 2. otherwise (it was tail), we again flip a coin. if it is heads (50% probability, now 25% in total), we will swap 3 job ids (and stop).
 3. otherwise (it was tail), we again flip a coin. if it is heads (50% probability, now 12.5% in total), we will swap 4 job ids (and stop).
 4. otherwise (it was tail), we again flip a coin. if it is heads (50% probability, now 6.25% in total), we will swap 5 job ids (and stop).
 5. otherwise (it was tail), we again flip a coin.

Making the neighborhood bigger

- Idea: Let's most often swap 2 jobs, but sometimes 3, less often 4, from time to time 5, rarely 6, hardly ever 7, ...
- nswap operator idea:
 1. flip a coin: if it is heads (50% probability), we will swap 2 job ids (and stop).
 2. otherwise (it was tail), we again flip a coin. if it is heads (50% probability, now 25% in total), we will swap 3 job ids (and stop).
 3. otherwise (it was tail), we again flip a coin. if it is heads (50% probability, now 12.5% in total), we will swap 4 job ids (and stop).
 4. otherwise (it was tail), we again flip a coin. if it is heads (50% probability, now 6.25% in total), we will swap 5 job ids (and stop).
 5. otherwise (it was tail), we again flip a coin. if it is heads (50% probability, now 3.125% in total), we will swap 6 job ids (and stop).

Making the neighborhood bigger

- Idea: Let's most often swap 2 jobs, but sometimes 3, less often 4, from time to time 5, rarely 6, hardly ever 7, ...
- nswap operator idea:
 1. flip a coin: if it is heads (50% probability), we will swap 2 job ids (and stop).
 2. otherwise (it was tail), we again flip a coin. if it is heads (50% probability, now 25% in total), we will swap 3 job ids (and stop).
 3. otherwise (it was tail), we again flip a coin. if it is heads (50% probability, now 12.5% in total), we will swap 4 job ids (and stop).
 4. otherwise (it was tail), we again flip a coin. if it is heads (50% probability, now 6.25% in total), we will swap 5 job ids (and stop).
 5. otherwise (it was tail), we again flip a coin. if it is heads (50% probability, now 3.125% in total), we will swap 6 job ids (and stop).
 6. and so on.

Making the neighborhood bigger

- Idea: Let's most often swap 2 jobs, but sometimes 3, less often 4, from time to time 5, rarely 6, hardly ever 7, ...
- nswap operator idea:
 1. flip a coin: if it is heads (50% probability), we will swap 2 job ids (and stop).
 2. otherwise (it was tail), we again flip a coin. if it is heads (50% probability, now 25% in total), we will swap 3 job ids (and stop).
 3. otherwise (it was tail), we again flip a coin. if it is heads (50% probability, now 12.5% in total), we will swap 4 job ids (and stop).
 4. otherwise (it was tail), we again flip a coin. if it is heads (50% probability, now 6.25% in total), we will swap 5 job ids (and stop).
 5. otherwise (it was tail), we again flip a coin. if it is heads (50% probability, now 3.125% in total), we will swap 6 job ids (and stop).
 6. and so on.
- We most often make small moves, but sometimes bigger ones.

Making the neighborhood bigger

- Idea: Let's most often swap 2 jobs, but sometimes 3, less often 4, from time to time 5, rarely 6, hardly ever 7, ...
- nswap operator idea:
 1. flip a coin: if it is heads (50% probability), we will swap 2 job ids (and stop).
 2. otherwise (it was tail), we again flip a coin. if it is heads (50% probability, now 25% in total), we will swap 3 job ids (and stop).
 3. otherwise (it was tail), we again flip a coin. if it is heads (50% probability, now 12.5% in total), we will swap 4 job ids (and stop).
 4. otherwise (it was tail), we again flip a coin. if it is heads (50% probability, now 6.25% in total), we will swap 5 job ids (and stop).
 5. otherwise (it was tail), we again flip a coin. if it is heads (50% probability, now 3.125% in total), we will swap 6 job ids (and stop).
 6. and so on.
- We most often make small moves, but sometimes bigger ones.
- Theoretically, we could always escape from any local optimum.

Making the neighborhood bigger

- Idea: Let's most often swap 2 jobs, but sometimes 3, less often 4, from time to time 5, rarely 6, hardly ever 7, ...
- nswap operator idea:
 1. flip a coin: if it is heads (50% probability), we will swap 2 job ids (and stop).
 2. otherwise (it was tail), we again flip a coin. if it is heads (50% probability, now 25% in total), we will swap 3 job ids (and stop).
 3. otherwise (it was tail), we again flip a coin. if it is heads (50% probability, now 12.5% in total), we will swap 4 job ids (and stop).
 4. otherwise (it was tail), we again flip a coin. if it is heads (50% probability, now 6.25% in total), we will swap 5 job ids (and stop).
 5. otherwise (it was tail), we again flip a coin. if it is heads (50% probability, now 3.125% in total), we will swap 6 job ids (and stop).
 6. and so on.
- We most often make small moves, but sometimes bigger ones.
- Theoretically, we could always escape from any local optimum, but the probability may sometimes be very very small.

Experiment and Analysis



So what do we get?

- I execute the program 101 times for each of the instances abz7, la24, swv15, and yn4


So what do we get?

- I execute the program 101 times for each of the instances abz7, la24, swv15, and yn4

\mathcal{I}	algo	makespan				last improvement	
		best	mean	med	sd	med(t)	med(FEs)
abz7	hc_1swap	717	800	798	28	0s	16'978
	hcr_16384_1swap	714	732	733	**6	91s	18'423'530
	hc_nswap	724	758	758	17	35s	7'781'762
la24	hc_1swap	999	1095	1086	56	0s	6'612
	hcr_16384_1swap	953	976	976	7	80s	34'437'999
	hc_nswap	945	1018	1016	29	25s	9'072'935
swv15	hc_1swap	3837	4108	4108	137	1s	104'598
	hcr_16384_1swap	3752	3859	3861	42	92s	11'756'497
	hc_nswap	3602	3880	3872	112	70s	8'351'112
yn4	hc_1swap	1109	1222	1220	48	0s	31'789
	hcr_16384_1swap	1081	1115	1115	11	91s	14'804'358
	hc_nswap	1095	1162	1160	34	71s	11'016'757


So what do we get?

hc_1swap: median result of 3 min of hill climber using 1swap




So what do we get?

hc_nswap: median result of 3 min of hill climber using nswap




So what do we get?

hc_1swap: median result of 3 min of hill climber using 1swap




So what do we get?

hc_nswap: median result of 3 min of hill climber using nswap




So what do we get?

hc_1swap: median result of 3 min of hill climber using 1swap




So what do we get?

hc_nswap: median result of 3 min of hill climber using nswap




So what do we get?

hc_1swap: median result of 3 min of hill climber using 1swap



So what do we get?


hc_nswap: median result of 3 min of hill climber using nswap



Progress over Time


What progress does the algorithm make over time?

Progress over Time



What progress does the algorithm make over time?


Progress over Time



What progress does the algorithm make over time?

- `hc_nswap` first behaves like `hc_1swap`, because most of the `nswap` moves are the same as `1swap` moves.


Progress over Time



What progress does the algorithm make over time?

- The rare larger moves allow it to escape from local optima that would trap hc_1swap.


Progress over Time



What progress does the algorithm make over time?

- The rare larger moves allow it to escape from local optima that would trap **hc_1swap**.
- The hill climber with restarts seems to improve longer.


Progress over Time



What progress does the algorithm make over time?

- The rare larger moves allow it to escape from local optima that would trap `hc_1swap`.
- The hill climber with restarts seems to improve longer.


Progress over Time



What progress does the algorithm make over time?

- The rare larger moves allow it to escape from local optima that would trap **hc_1swap**.
- The hill climber with restarts seems to improve longer.

Progress over Time



What progress does the algorithm make over time?

- The rare larger moves allow it to escape from local optima that would trap `hc_1swap`.
- The hill climber with restarts seems to improve longer.

Combining the Two Improvements

- Now we know two ways to improve the performance of our hill climber.

Combining the Two Improvements

- Now we know two ways to improve the performance of our hill climber:
 1. we can restart it

Combining the Two Improvements

- Now we know two ways to improve the performance of our hill climber:
 1. we can restart it and
 2. we can use a unary operator with larger neighborhood that still mostly makes small steps.

Combining the Two Improvements

- Now we know two ways to improve the performance of our hill climber:
 1. we can restart it and
 2. we can use a unary operator with larger neighborhood that still mostly makes small steps.
- It is only natural to try to combine these two improvements.

Configuring the Algorithm

		makespan				last improvement	
\mathcal{I}	algo	best	mean	med	sd	med(t)	med(FEs)
abz7	hc_1swap	717	800	798	28	0s	16'978
	hc_nswap	724	758	758	17	35s	7'781'762
la24	hc_1swap	999	1095	1086	56	0s	6'612
	hc_nswap	945	1018	1016	29	25s	9'072'935
swv15	hc_1swap	3837	4108	4108	137	1s	104'598
	hc_nswap	3602	3880	3872	112	70s	8'351'112
yn4	hc_1swap	1109	1222	1220	48	0s	31'789
	hc_nswap	1095	1162	1160	34	71s	11'016'757

Configuring the Algorithm

- The hc_nswap improves longer than hc_1swap


		makespan				last improvement	
\mathcal{I}	algo	best	mean	med	sd	med(t)	med(FEs)
abz7	hc_1swap	717	800	798	28	0s	16'978
	hc_nswap	724	758	758	17	35s	7'781'762
la24	hc_1swap	999	1095	1086	56	0s	6'612
	hc_nswap	945	1018	1016	29	25s	9'072'935
swv15	hc_1swap	3837	4108	4108	137	1s	104'598
	hc_nswap	3602	3880	3872	112	70s	8'351'112
yn4	hc_1swap	1109	1222	1220	48	0s	31'789
	hc_nswap	1095	1162	1160	34	71s	11'016'757

Configuring the Algorithm

- The `hc_nswap` improves longer than `hc_1swap`
- We can expect that the number L of unsuccessful steps before a restart should be higher now.

		makespan				last improvement	
\mathcal{I}	algo	best	mean	med	sd	med(t)	med(FEs)
abz7	hc_1swap	717	800	798	28	0s	16'978
	hc_nswap	724	758	758	17	35s	7'781'762
la24	hc_1swap	999	1095	1086	56	0s	6'612
	hc_nswap	945	1018	1016	29	25s	9'072'935
swv15	hc_1swap	3837	4108	4108	137	1s	104'598
	hc_nswap	3602	3880	3872	112	70s	8'351'112
yn4	hc_1swap	1109	1222	1220	48	0s	31'789
	hc_nswap	1095	1162	1160	34	71s	11'016'757

Configuring the Algorithm



Configuring the Algorithm

- The `hc_nswap` improves longer than `hc_1swap`
- We can expect that the number L of unsuccessful steps before a restart should be higher now.
- Let's choose $L = 65'536$, i.e., `hcr_65536_nswap`.

\mathcal{I}	algo	makespan				last improvement	
		best	mean	med	sd	med(t)	med(FEs)
abz7	hc_1swap	717	800	798	28	0s	16'978
	hc_nswap	724	758	758	17	35s	7'781'762
la24	hc_1swap	999	1095	1086	56	0s	6'612
	hc_nswap	945	1018	1016	29	25s	9'072'935
swv15	hc_1swap	3837	4108	4108	137	1s	104'598
	hc_nswap	3602	3880	3872	112	70s	8'351'112
yn4	hc_1swap	1109	1222	1220	48	0s	31'789
	hc_nswap	1095	1162	1160	34	71s	11'016'757

Experiment and Analysis



So what do we get?

- I execute the program 101 times for each of the instances abz7, la24, swv15, and yn4


So what do we get?

- I execute the program 101 times for each of the instances abz7, la24, swv15, and yn4

\mathcal{I}	algo	makespan				last improvement	
		best	mean	med	sd	med(t)	med(FEs)
abz7	hcr_16384_1swap	714	732	733	6	91s	18'423'530
	hc_nswap	724	758	758	17	35s	7'781'762
	hcr_65536_nswap	712	731	732	6	96s	21'189'358
la24	hcr_16384_1swap	953	976	976	7	80s	34'437'999
	hc_nswap	945	1018	1016	29	25s	9'072'935
	hcr_65536_nswap	942	973	974	8	71s	31'466'420
swv15	hcr_16384_1swap	3752	3859	3861	42	92s	11'756'497
	hc_nswap	3602	3880	3872	112	70s	8'351'112
	hcr_65536_nswap	3740	3818	3826	35	89s	10'783'296
yn4	hcr_16384_1swap	1081	1115	1115	11	91s	14'804'358
	hc_nswap	1095	1162	1160	34	71s	11'016'757
	hcr_65536_nswap	1068	1109	1110	12	78s	18'756'636


So what do we get?

hcr_16384_1swap: median result of 3 min of hcr_16384_1swap




So what do we get?

hcr_65536_nswap: median result of 3 min of hcr_65536_nswap




So what do we get?

hcr_16384_1swap: median result of 3 min of hcr_16384_1swap




So what do we get?

hcr_65536_nswap: median result of 3 min of hcr_65536_nswap




So what do we get?

hcr_16384_1swap: median result of 3 min of hcr_16384_1swap




So what do we get?

hcr_65536_nswap: median result of 3 min of hcr_65536_nswap




So what do we get?

hcr_16384_1swap: median result of 3 min of hcr_16384_1swap



So what do we get?

hcr_65536_nswap: median result of 3 min of hcr_65536_nswap




Progress over Time

What progress does the algorithm make over time?


Progress over Time

What progress does the algorithm make over time?



Progress over Time


What progress does the algorithm make over time?



hcr_nswap tends to be a tiny little bit better than hcr_1swap ... but not much

Progress over Time


What progress does the algorithm make over time?



hcr_nswap tends to be a tiny little bit better than hcr_1swap ... but not much

Progress over Time


What progress does the algorithm make over time?



hcr_nswap tends to be a tiny little bit better than hcr_1swap ... but not much

Progress over Time


What progress does the algorithm make over time?



`hcr_nswap` tends to be a tiny little bit better than `hcr_1swap` ... but not much

Progress over Time

What progress does the algorithm make over time?



`hcr_nswap` tends to be a tiny little bit better than `hcr_1swap` ... but not much