

```

/*Author: Eric Gustin
Assignment: CPSC223-01 HW08 hw8_tests.cpp
Description: This program tests the binary search tree collection.
It tests every function in bst_collection.h, except for "remove"
*/
#include <iostream>
#include <string>
#include <gtest/gtest.h>
#include "bst_collection.h"

using namespace std;

// Test 1
TEST(BasicCollectionTest, CorrectSize) {
    BSTCollection<string,double> c;
    ASSERT_EQ(0, c.size());
    c.insert("a", 10.0);
    ASSERT_EQ(1, c.size());
    c.insert("b", 20.0);
    ASSERT_EQ(2, c.size());
}

// Test 2
TEST(BasicCollectionTest, InsertAndFind) {
    BSTCollection<string,double> c;
    double v;
    ASSERT_EQ(false, c.find("a", v));
    c.insert("a", 10.0);
    ASSERT_EQ(true, c.find("a", v));
    ASSERT_EQ(v, 10.0);
    ASSERT_EQ(false, c.find("b", v));
    c.insert("b", 20.0);
    ASSERT_EQ(true, c.find("b", v));
    ASSERT_EQ(20.0, v);
}

/*
// Test 3 -- THIS TEST SHOULD FAIL FOR HW8
TEST(BasicCollectionTest, RemoveElems) {
    BSTCollection<string,double> c;
    c.insert("a", 10.0);
    c.insert("b", 20.0);
    c.insert("c", 30.0);
    double v;
    c.remove("a");
    ASSERT_EQ(false, c.find("a", v));
    ASSERT_EQ(true, c.find("b", v));
    ASSERT_EQ(true, c.find("c", v));
    c.remove("b");
    ASSERT_EQ(false, c.find("b", v));
    ASSERT_EQ(true, c.find("c", v));
    c.remove("c");
    ASSERT_EQ(false, c.find("c", v));
    ASSERT_EQ(0, c.size());
}

*/
// Test 4
TEST(BasicCollectionTest, GetKeys) {
    BSTCollection<string,double> c;
    c.insert("a", 10.0);
    c.insert("b", 20.0);
    c.insert("c", 30.0);
    vector<string> ks;
    c.keys(ks);
    vector<string>::iterator iter;
    iter = find(ks.begin(), ks.end(), "a");
    ASSERT_NE(ks.end(), iter);
    iter = find(ks.begin(), ks.end(), "b");
    ASSERT_NE(ks.end(), iter);
    iter = find(ks.begin(), ks.end(), "c");
    ASSERT_NE(ks.end(), iter);
    iter = find(ks.begin(), ks.end(), "d");
    ASSERT_EQ(ks.end(), iter);
}

// Test 5

```

```

TEST(BasicCollectionTest, GetKeysAdvanced) {
    BSTCollection<string,double> c;
    c.insert("g", 10.0);
    c.insert("c", 20.0);
    c.insert("b", 30.0);
    c.insert("q", 10.0);
    c.insert("f", 20.0);
    c.insert("a", 30.0);
    c.insert("d", 10.0);
    c.insert("h", 20.0);
    c.insert("t", 30.0);
    c.insert("i", 10.0);
    c.insert("qq", 20.0);
    c.insert("qqq", 30.0);
    vector<string> ks;
    c.keys(ks);
    for (int i = 0; i < ks.size()-1; ++i)
        ASSERT_LE(ks[i], ks[i+1]);
}

// Test 6
TEST(BasicCollectionTest, GetKeyRange) {
    BSTCollection<string,double> c;
    c.insert("a", 10.0);
    c.insert("b", 20.0);
    c.insert("c", 30.0);
    c.insert("d", 40.0);
    c.insert("e", 50.0);
    vector<string> ks;
    c.find("b", "d", ks);
    vector<string>::iterator iter;
    iter = find(ks.begin(), ks.end(), "b");
    ASSERT_NE(ks.end(), iter);
    iter = find(ks.begin(), ks.end(), "c");
    ASSERT_NE(ks.end(), iter);
    iter = find(ks.begin(), ks.end(), "d");
    ASSERT_NE(ks.end(), iter);
    iter = find(ks.begin(), ks.end(), "a");
    ASSERT_EQ(ks.end(), iter);
    iter = find(ks.begin(), ks.end(), "e");
    ASSERT_EQ(ks.end(), iter);
}

// Test 7
TEST(BasicCollectionTest, GetKeyRangeAdvanced) {
    BSTCollection<string,double> c;
    c.insert("g", 10.0);
    c.insert("c", 20.0);
    c.insert("b", 30.0);
    c.insert("q", 10.0);
    c.insert("f", 20.0);
    c.insert("a", 30.0);
    c.insert("d", 10.0);
    c.insert("h", 20.0);
    c.insert("t", 30.0);
    c.insert("i", 10.0);
    c.insert("qq", 20.0);
    c.insert("qqq", 30.0);
    vector<string> ks;
    c.find("cd", "q", ks);
    ASSERT_EQ(ks.size(), 6);
}

// Test 8
TEST(BasicCollectionTest, KeySort) {
    BSTCollection<string,double > c;
    c.insert("a", 10.0);
    c.insert("e", 50.0);
    c.insert("c", 30.0);
    c.insert("b", 20.0);
    c.insert("d", 40.0);
    c.insert("aaa", 10.0);
    c.insert("dfe", 50.0);
    c.insert("chh", 30.0);
    c.insert("zsdb", 20.0);
    c.insert("zxsd", 40.0);
}

```

```

vector<string> sorted_ks;
c.sort(sorted_ks);
ASSERT_EQ(c.size(), sorted_ks.size());
for (int i = 0; i < int(sorted_ks.size())-1; ++i) {
    ASSERT_LE(sorted_ks[i], sorted_ks[i+1]);
}
}
// Test 9
TEST(BasicCollectionTest, AssignOpTest) {
    BSTCollection<string,int> c1;
    c1.insert("c", 10);
    c1.insert("sdb", 15);
    c1.insert("d", 20);
    c1.insert("fga", 20);
    c1.insert("kjhc", 10);
    c1.insert("ddb", 15);
    c1.insert("vcd", 20);
    c1.insert("asa", 20);
    BSTCollection<string,int> c2;
    c2.insert("naan", 20);
    c2.insert("none", 40);
    c2 = c1;
    vector<string> ks2;
    c2.keys(ks2);
    vector<string> ks1;
    c1.keys(ks1);
    for (int j = 0; j < ks2.size(); ++j)
        ASSERT_EQ(ks1[j], ks2[j]);
    ASSERT_EQ(c1.size(), c2.size());
    ASSERT_EQ(c1.height(), c2.height());
}
// Test 10
TEST(BasicCollectionTest, Height) {
    BSTCollection<string,int> d;
    d.insert("c", 10);
    d.insert("b", 15);
    d.insert("d", 20);
    d.insert("a", 20);
    d.insert("z", 10);
    d.insert("f", 15);
    d.insert("e", 20);
    d.insert("g", 20);
    ASSERT_EQ(d.height(), 5);
}
// Test 11
TEST(BasicCollectionTest, CopyList) {
    BSTCollection<string,int> w;
    w.insert("hi", 11);
    w.insert("computer", 12);
    w.insert("forever", 122);
    w.insert("never", 2110);
    w.insert("bye", 11);
    w.insert("laptop", 12);
    w.insert("infinite", 122);
    w.insert("none", 2110);
    BSTCollection<string,int> w_copy = w;
    ASSERT_EQ(w_copy.size(), w.size());

    vector<string> w_keys;
    vector<string> w_copy_keys;
    w.sort(w_keys);
    w_copy.sort(w_copy_keys);
    for (int i = 0; i <= 3; ++i)
    {
        ASSERT_EQ(w_keys[i], w_copy_keys[i]);
    }
    // copy constructor with empty hash table
    BSTCollection<string,int> empty;
    BSTCollection<string,int> empty_copy(empty);
    ASSERT_EQ(empty.size(), 0);
    ASSERT_EQ(empty_copy.size(), 0);
}
// Test 12

```

```

TEST(BasicCollectionTest, Assign) {
    BSTCollection<string,int> y;
    y.insert("gofish", 10);
    y.insert("safety", 20);
    y.insert("xyz", 30);
    y.insert("ergo", 40);
    y.insert("aapl", 50);
    y.insert("good", 60);

    BSTCollection<string,int> z;
    z.insert("n", 10);
    z.insert("a", 100);
    z.insert("s", 1000);
    z = y;

    ASSERT_EQ(z.size(), y.size());

    vector<string> z_keys;
    vector<string> y_keys;
    y.keys(y_keys);
    z.keys(z_keys);
    ASSERT_EQ(z.size(), 6);
    for (int i = 0; i <= 5; ++i)
    {
        ASSERT_EQ(y_keys[i], z_keys[i]);
    }
    // assignment operator will not do copying if trying to copy itself.
    z = z;
    ASSERT_EQ(z.size(), 6);
    ASSERT_EQ(z.height(), y.height());
}
// Test 13
TEST(BasicCollectionTest, Negatives) {
    BSTCollection<double,string>* l = new BSTCollection<double,string>;
    l->insert(999.0, "DigitalLogic");
    l->insert(400.4, "AlgsAndDataStruct");
    l->insert(-33.2, "discreteMath");
    l->insert(-0.1, "Globals");
    l->insert(0.0, "Human Nature");

    vector<double> sorted_ints;
    l->sort(sorted_ints);
    for (int i = 0; i < int(sorted_ints.size()-1); ++i)
    {
        ASSERT_LE(sorted_ints[i], sorted_ints[i+1]);
    }
    delete l;
}
// Test 14
TEST(BasicCollectionTest, SizeZero) {
    BSTCollection<int,int>* m = new BSTCollection<int,int>;
    ASSERT_EQ(m->size(), 0);
    m->remove(2);
    ASSERT_EQ(m->size(), 0);
    int my_val;
    ASSERT_EQ(m->find(0, my_val), false);
    vector<int> keys_ints;
    m->keys(keys_ints);
    ASSERT_EQ(keys_ints.size(), 0);
    m->sort(keys_ints);
    ASSERT_EQ(keys_ints.size(), 0);
    delete m;
}
int main(int argc, char** argv)
{
    testing::InitGoogleTest(&argc, argv);
    return RUN_ALL_TESTS();
}

```