

## Contents

1 Basic	1
1.1 Pragma/IO	1
1.2 Debug Macro	1
2 Data Structure	1
2.1 Heavy-Light Decomposition	1
2.2 Centroid Decomposition	1
2.3 Link Cut Tree	2
2.4 LiChaoST	2
2.5 Leftist Heap	2
2.6 Treap	3
2.7 Chtholly Tree	3
2.8 Persistent Segment Tree	3
2.9 Range Chmin Chmax Add Range Sum	3
2.10 Range Set	4
2.11 vEB Tree	5
2.12 KD Tree	5
2.13 pbds	6
3 Graph	6
3.1 SCC	6
3.2 BCC Vertex	6
3.3 Directed MST	6
3.4 Negative Cycle	6
3.5 Dominator Tree	7
3.6 Maximum Clique	7
3.7 Virtual Tree	7
3.8 Minimum Steiner Tree	7
4 Flow/Matching	8
4.1 Dinic	8
4.2 Min Cost Max Flow	8
4.3 Gomory Hu	9
4.4 SW Min Cut	9
4.5 Hopcroft Karp	9
4.6 Kuhn Munkres	9
4.7 General Graph Matching	10
4.8 Weighted General Graph Matching	10
4.9 Flow Models	12
5 String	12
5.1 Z-Value	12
5.2 KMP	12
5.3 Manacher	12
5.4 Suffix Array	12
5.5 SAIS	13
5.6 Suffix Automaton	13
5.7 Palindrome Tree	14
5.8 AC Automaton	14
5.9 Lyndon Factorization	14

6 Math	14
6.1 Miller Rabin	14
6.2 Pollard Rho	15
6.3 EXT GCD	15
6.4 Chinese Remainder Theorem	15
6.5 Powerful Number Sieve	15
6.6 Min25 Sieve	15
6.7 Floor Sum	16
6.8 Euclidean	16
6.9 Big Number	16
6.10 Determinant	17
6.11 Discrete Log	17
6.12 Berlekamp Massey	17
6.13 Gaussian Elimination	17
6.14 Golden Search	18
6.15 Pi Count	18
6.16 Quadratic Residue	18
6.17 Simplex	18
6.18 Simplex Construction	19
6.19 Theorem	19
7 Polynomial	19
7.1 NTT	19
7.2 FFT	19
7.3 Primes	19
7.4 Fast Walsh Transform	19
7.5 Fast Linear Recursion	20
7.6 Operations	20
8 Geometry	20
8.1 Basic	20
8.2 Convex Hull	20
8.3 Minkowski Sum	20
8.4 Intersection of Circle and Line	21
8.5 Intersection of Circles	21
8.6 Point in Convex	21
8.7 Minimum Enclosing Circle	21
8.8 Rotating Caliper	21
8.9 Rotating Sweep Line	21
8.10 Delaunay Triangulation	21
8.11 3D Point	22
8.12 3D Convex Hull	22
9 Misc	23
9.1 Binary Search on Fraction	23
9.2 Random	23
9.3 Bit Hack	23
9.4 Dynamic MST	23
9.5 Manhattan MST	24
9.6 DP Optimization Conditions	24
9.6.1 Totally Monotone (Concave/Convex)	24
9.6.2 Monge Condition (Concave/Convex)	24
9.6.3 Optimal Split Point	24
9.7 Mo's Algo With Modification	24
9.8 Mo's Algo On Tree	24
9.9 Mo's Algorithm	25
9.10 Hilbert Curve	25
9.11 SMAWK	25
9.12 Simulate Annealing	25
9.13 Python	25
9.14 Matroid	25

## 1.2 Debug Macro

```
void db() { cerr << endl; }
template <typename T, typename ...U>
void db(T i, U ...j) { cerr << i << ' ', db(j...); }
#ifdef ABS
#define bug(x...) db("[ " + string(#x) + "]", x)
#define safe cerr << __PRETTY_FUNCTION__
    << " line " << __LINE__ << " safe" << endl
#else
#define bug(x...) void(0)
#define safe void(0)
#endif
```

## 2 Data Structure

### 2.1 Heavy-Light Decomposition

```
int n, q, dfn = 0;
int val[maxn], sz[maxn], head[maxn], dep[maxn],
    st[maxn * 4], par[maxn], loc[maxn], id[maxn];
vector<int> adj[maxn];

void dfs(int pos, int prev){
    sz[pos] = 1;
    if(prev != -1) adj[pos].erase
        (find(adj[pos].begin(), adj[pos].end(), prev));
    for(auto &x : adj[pos]){
        par[x] = pos, dep[x] = dep[pos] + 1;
        dfs(x, pos);
        sz[pos] += sz[x];
        if(sz[x] > sz[adj[pos][0]]) swap(x, adj[pos][0]);
    }
}

void decompose(int pos, int h){
    id[dfn++] = pos;
    head[pos] = h, loc[pos] = dfn - 1;
    // upd(loc[pos], val[pos]);
    for(auto x : adj[pos]){
        if(x == adj[pos][0]) decompose(x, h);
        else decompose(x, x);
    }
}

void build(){
    dfs(0, -1);
    decompose(0, 0);
    //build_segtree();
}

int solve(int a, int b){
    int ret = 0;
    while(head[a] != head[b]){
        if(dep[head[a]] > dep[head[b]]) swap(a, b);
        ret = max(ret, qry(loc[head[b]], loc[b]));
        b = par[head[b]];
    }
    if(dep[a] > dep[b]) swap(a, b);
    return max(ret, qry(loc[a], loc[b]));
}
```

### 2.2 Centroid Decomposition

```
vector<pll> adj[maxn];
ll dist[20][maxn]; // distance to kth-layer-parent
int sz[maxn], del[maxn], par[maxn], cdep[maxn];
ll cnt[maxn], sum[maxn], re[maxn]; // re: subtree->par
int n, q;

void dfsz(int pos, int prev){
    sz[pos] = 1;
    for(auto [x, w] : adj[pos]){
        if(del[x] || x == prev) continue;
        dfsz(x, pos);
        sz[pos] += sz[x];
    }
}

int get_centroid(int pos, int prev, int siz){
    for(auto [x, w] : adj[pos]){
        if(!del[x] && x != prev && sz[x] >
            siz / 2) return get_centroid(x, pos, siz);
    }
    return pos;
}

void get_dist(int pos, int prev, int layer){
    for(auto [x, w] : adj[pos]){
        if(del[x] || x == prev) continue;
        dist[layer][x] = dist[layer][pos] + w;
        get_dist(x, pos, layer);
    }
}
```

## 1 Basic

### 1.1 Pragma/IO

```
#pragma GCC optimize("Ofast,no-stack-protector")
#pragma GCC optimize("no-math-errno,unroll-loops")
#pragma GCC target("sse,sse2,sse3,ssse3,sse4")
#pragma GCC target("popcnt,abm,mmx,avx,arch=skylake")
__builtin_ia32_ldmxcsr(__builtin_ia32_stmxcsr()|0x8040)
#include<unistd.h>
char OB[65536]; int OP;
inline char RC() {
    static char buf[65536], *p = buf, *q = buf;
    return p == q && (q = (p
        = buf) + read(0, buf, 65536)) == buf ? -1 : *p++;
}
inline int R() {
    static char c;
    while((c = RC()) < '0'); int a = c ^ '0';
    while((c = RC()) >= '0') a *= 10, a += c ^ '0';
    return a;
}
inline void W(int n) {
    static char buf[12], p;
    if (n == 0) OB[OP++] = '0'; p = 0;
    while (n) buf[p++] = '0' + (n % 10), n /= 10;
    for (--p; p >= 0; --p) OB[OP++] = buf[p];
    if (OP > 65520) write(1, OB, OP), OP = 0;
}
```

```

    }
}
void cd(int pos, int layer = 1, int p = 0){
    dfssz(pos, -1);
    int cen = get_centroid(pos, -1, sz[pos]);
    del[cen] = 1;
    dist[layer][cen] = 0;
    cdep[cen] = layer;
    par[cen] = p;
    get_dist(cen, -1, layer);
    for(auto [x, w] : adj[cen]){
        if(!del[x]){
            cd(x, layer + 1, cen);
        }
    }
}
void upd(int p){
    for(int x = p, d = cdep[x]; d; x = par[x], d--){
        sum[x] += dist[d][p];
        re[x] += dist[d - 1][p];
        cnt[x] ++;
    }
}
ll qry(int p){
    ll pre = 0, ans = 0;
    for(int x = p, d = cdep[x]; d; x = par[x], d--){
        ans += sum
            [x] - re[x] + (cnt[x] - pre) * dist[d][p];
        pre = cnt[x];
    }
    return ans;
}
}

```

## 2.3 Link Cut Tree

```

struct LCT{
    int ch[maxn]
        ][2], par[maxn], rev[maxn], xr[maxn], val[maxn];
    int get(int x){ return ch[par[x]][1] == x; }
    int isroot(int x){
        return ch[par[x]][0] != x && ch[par[x]][1] != x; }
    void push(int x){
        if(rev[x]){
            if(rs) swap(ch[rs][0], ch[rs][1]), rev[rs] ^= 1;
            if(ls) swap(ch[ls][0], ch[ls][1]), rev[ls] ^= 1;
            rev[x] = 0;
        }
    }
    void pull(int x){
        xr[x] = xr[ls] ^ xr[rs] ^ val[x];
    }
    void rotate(int x){
        int y = par[x], z = par[y], k = get(x);
        if(!isroot(y)) ch[z][ch[z][1] == y] = x;
        ch[y][k] = ch[x][!k], par[ch[x][!k]] = y;
        ch[x][!k] = y, par[y] = x;
        par[x] = z;
        pull(y), pull(x);
    }
    void update(int x){
        if(!isroot(x)) update(par[x]);
        push(x);
    }
    void splay(int x){
        update(x);
        for(int
            p = par[x]; !isroot(x); rotate(x), p = par[x]){
            if(!isroot(p)) rotate(get(p) == get(x) ? p : x);
        }
    }
    void access(int x){
        for(int p = 0; x != 0; p = x, x = par[x]){
            splay(x);
            ch[x][1] = p;
            pull(x);
        }
    }
    void make_root(int x){
        access(x);
        splay(x);
        swap(ls, rs);
        rev[x] ^= 1;
    }
    void link(int x, int y){
        make_root(x);
        splay(x);
        if(find_root(y) == x) return;
    }
}

```

```

    par[x] = y;
}
void cut(int x, int y){
    make_root(x);
    access(y);
    splay(x);
    if(par[y] != x || ch[y][0]) return;
    ch[x][1] = par[y] = 0;
}
int find_root(int x){
    access(x);
    splay(x);
    push(x);
    while(ls) x = ls, push(x);
    splay(x);
    return x;
}
void split(int x, int y){
    make_root(x);
    access(y);
    splay(y);
}
void upd(int x, int y){
    access(x);
    splay(x);
    val[x] = y;
    pull(x);
}
} st;

```

## 2.4 LiChaoST

```

struct line{
    ll m, k;
    line(){}
    line(ll _m, ll _k) : m(_m), k(_k){}
    ll val(ll x){ return m * x + k; }
};

struct node{
    line ans;
    node *l, *r;
    int siz;
    node(){}
    node(line l) : ans(l), l(nullptr), r(nullptr){ }
};

node sgt[maxn];

int root[maxn], cnt = 0;

struct segtree{
    node *rt;
    int n, siz;
    segtree() : n(maxc * 2), siz(0), rt(nullptr){}
    void insert(node* &k, int l, int r, line cur){
        if(!k){
            k = new node(cur);
            siz++;
            return;
        }
        if(l == r){
            if(k->ans.val(l) > cur.val(l)) k->ans = cur;
            return;
        }
        int m = (l + r) / 2;
        if(k->ans.val(m) > cur.val(m)) swap(k->ans, cur);
        if(cur.m > k->ans.m) insert(k->l, l, m, cur);
        else insert(k->r, m + 1, r, cur);
    }
    void insert
        (ll m, ll k) { insert(rt, 0, n, line(m, k)); }
    void insert(line l) { insert(rt, 0, n, l); }
    ll qry(node *k, int l, int r, int pos){
        if(!k) return INF;
        if(l == r) return k->ans.val(pos);
        int m = (l + r) / 2;
        return min(k->ans.val(pos), pos <= m ? qry
            (k->l, l, m, pos) : qry(k->r, m + 1, r, pos));
    }
    ll qry(int pos) { return qry(rt, 0, n, pos); }
};

```

## 2.5 Leftist Heap

```

struct LeftistTree{
    int cnt, rt[maxn]
        ], lc[maxn * 20], rc[maxn * 20], d[maxn * 20];
}

```

```

int v[maxn * 20];
LeftistTree(){
int newnode(pll nd){
    cnt++;
    v[cnt] = nd;
    return cnt;
}
int merge(int x, int y){
    if(!x || !y) return x + y;
    if(v[x] > v[y]) swap(x, y);
    int p = ++cnt;
    lc[p] = lc[x], v[p] = v[x];
    rc[p] = merge(rc[x], y);
    if(d[lc[p]] < d[rc[p]]) swap(lc[p], rc[p]);
    d[p] = d[rc[p]] + 1;
    return p;
}
} st;

```

## 2.6 Treap

```

struct node{
    int val, pri, c = 1;
    node *l, *r;
    node(int _val) :
        val(_val), pri(rand()), l(nullptr), r(nullptr){
        void recal();
    }
    *rt;
    int cnt(node *t){ return t ? t->c : 0; }
    void node::recal(){
        c = cnt(l) + cnt(r) + 1;
    }
    pair<node*, node*> split(node *t, int val){
        if(!t) return {nullptr, nullptr};
        if(cnt(t->l) < val){
            auto p = split(t->r, val - cnt(t->l) - 1);
            t->r = p.first;
            t->recal();
            return {t, p.second};
        }
        else{
            auto p = split(t->l, val);
            t->l = p.second;
            t->recal();
            return {p.first, t};
        }
    }
    node* merge(node *a, node *b){
        if(!a || !b) return a ? a : b;
        if(a->pri > b->pri){
            a->r = merge(a->r, b);
            a->recal();
            return a;
        }
        else{
            b->l = merge(a, b->l);
            b->recal();
            return b;
        }
    }
    node *insert(node *t, int k){
        auto [a, b] = split(t, k);
        return merge(merge(a, new node(k)), b);
    }
    node* remove(node *t, int k){
        auto [a, b] = split(t, k - 1);
        auto [b, c] = split(b, k);
        return merge(a, c);
    }
}

```

## 2.7 Chtholly Tree

```

struct ChthollyTree {
    struct interval {
        int l, r;
        ll v;
        interval (
            int _l, int _r, ll _v) : l(_l), r(_r), v(_v) {}
    };
    struct cmp {
        bool operator ()
            (const interval &a, const interval &b) const {
            return a.l < b.l;
        }
    };
    set <interval, cmp> s;
    vector <interval> split(int l, int r) {

```

```

// split
    into [0, l), [l, r), [r, n) and return [l, r)
    vector <interval> del, ans, re;
    auto it = s.lower_bound(interval(l, -1, 0));
    if (it
        != s.begin() && (it == s.end() || l < it->l)) {
        --it;
        del.pb(*it);
        if (r < it->r) {
            re.pb(interval(it->l, l, it->v));
            ans.pb(interval(l, r, it->v));
            re.pb(interval(r, it->r, it->v));
        } else {
            re.pb(interval(it->l, l, it->v));
            ans.pb(interval(l, it->r, it->v));
        }
        ++it;
    }
    for (; it != s.end() && it->r <= r; ++it) {
        ans.pb(*it);
        del.pb(*it);
    }
    if (it != s.end() && it->l < r) {
        del.pb(*it);
        ans.pb(interval(it->l, r, it->v));
        re.pb(interval(r, it->r, it->v));
    }
    for (interval &i : del)
        s.erase(i);
    for (interval &i : re)
        s.insert(i);
    return ans;
}
void merge(vector <interval> a) {
    for (interval &i : a)
        s.insert(i);
}
};

```

## 2.8 Persistent Segment Tree

```

struct Seg {
    // Persistent Segment
    // Tree, single point modify, range query sum
    // 0-indexed, [l, r)
    static Seg mem[M], *pt;
    int l, r, m, val;
    Seg* ch[2];
    Seg () = default;
    Seg (int _l
        , int _r) : l(_l), r(_r), m(l + r >> 1), val(0) {
        if (r - l > 1) {
            ch[0] = new (pt++) Seg(l, m);
            ch[1] = new (pt++) Seg(m, r);
        }
    }
    void pull() {val = ch[0]->val + ch[1]->val;}
    Seg* modify(int p, int v) {
        Seg *now = new (pt++) Seg(*this);
        if (r - l == 1) {
            now->val = v;
        } else {
            now->ch[p >= m] = ch[p >= m]->modify(p, v);
            now->pull();
        }
        return now;
    }
    int query(int a, int b) {
        if (a <= l && r <= b) return val;
        int ans = 0;
        if (a < m) ans += ch[0]->query(a, b);
        if (m < b) ans += ch[1]->query(a, b);
        return ans;
    }
} Seg::mem[M], *Seg::pt = mem;
// Init Tree
Seg *root = new (Seg::pt++) Seg(0, n);

```

## 2.9 Range Chmin Chmax Add Range Sum

```

#include <algorithm>
#include <iostream>
using namespace std;
typedef long long ll;

const int MAXC = 200005;
const ll INF = 1e18;

```

```

struct node {
    ll sum;
    ll mx, mxcnt, smx;
    ll mi, micnt, smi;
    ll lazymax, lazymin, lazyadd;
    node(ll k = 0) {
        : sum(k), mx(k), mxcnt(1), smx(-INF), mi(k),
          micnt(1), smi(INF), lazymax(-INF), lazymin(INF),
          lazyadd(0) {}
    }
    node operator+(const node &a) const {
        node rt;
        rt.sum = sum + a.sum;
        rt.mx = max(mx, a.mx);
        rt.mi = min(mi, a.mi);
        if (mx == a.mx) {
            rt.mxcnt = mxcnt + a.mxcnt;
            rt.smx = max(smx, a.smx);
        } else if (mx > a.mx) {
            rt.mxcnt = mxcnt;
            rt.smx = max(smx, a.mx);
        } else {
            rt.mxcnt = a.mxcnt;
            rt.smx = max(mx, a.smx);
        }
        if (mi == a.mi) {
            rt.micnt = micnt + a.micnt;
            rt.smi = min(smi, a.smi);
        } else if (mi < a.mi) {
            rt.micnt = micnt;
            rt.smi = min(smi, a.mi);
        } else {
            rt.micnt = a.micnt;
            rt.smi = min(mi, a.smi);
        }
        rt.lazymax = -INF;
        rt.lazymin = INF;
        rt.lazyadd = 0;
        return rt;
    }
} seg[MAXC << 2];

ll a[MAXC];

void give_tag_min(int rt, ll t) {
    if (t >= seg[rt].mx) return;
    seg[rt].lazymin = t;
    seg[rt].lazyadd = min(seg[rt].lazyadd, t);
    seg[rt].sum -= seg[rt].mx * (seg[rt].mx - t);
    if (seg[rt].mx == seg[rt].smi) seg[rt].smi = t;
    if (seg[rt].mx == seg[rt].mi) seg[rt].mi = t;
    seg[rt].mx = t;
}

void give_tag_max(int rt, ll t) {
    if (t <= seg[rt].mi) return;
    seg[rt].lazymax = t;
    seg[rt].sum += seg[rt].micnt * (t - seg[rt].mi);
    if (seg[rt].mi == seg[rt].smx) seg[rt].smx = t;
    if (seg[rt].mi == seg[rt].mx) seg[rt].mx = t;
    seg[rt].mi = t;
}

void give_tag_add(int l, int r, int rt, ll t) {
    seg[rt].lazyadd += t;
    if (seg[rt].lazyadd != -INF) seg[rt].lazyadd += t;
    if (seg[rt].lazyadd != INF) seg[rt].lazyadd += t;
    seg[rt].mx += t;
    if (seg[rt].smx != -INF) seg[rt].smx += t;
    seg[rt].mi += t;
    if (seg[rt].smi != INF) seg[rt].smi += t;
    seg[rt].sum += (ll)(r - l + 1) * t;
}

void tag_down(int l, int r, int rt) {
    if (seg[rt].lazyadd != 0) {
        int mid = (l + r) >> 1;
        give_tag_add(l, mid, rt << 1, seg[rt].lazyadd);
        give_tag_add(
            mid + 1, r, rt << 1 | 1, seg[rt].lazyadd);
        seg[rt].lazyadd = 0;
    }
    if (seg[rt].lazymin != INF) {
        give_tag_min(rt << 1, seg[rt].lazymin);
        give_tag_min(rt << 1 | 1, seg[rt].lazymin);
        seg[rt].lazymin = INF;
    }
}

```

```

}
if (seg[rt].lazyadd != -INF) {
    give_tag_max(rt << 1, seg[rt].lazyadd);
    give_tag_max(rt << 1 | 1, seg[rt].lazyadd);
    seg[rt].lazyadd = -INF;
}
}

void build(int l, int r, int rt) {
    if (l == r) return seg[rt] = node(a[l]), void();
    int mid = (l + r) >> 1;
    build(l, mid, rt << 1);
    build(mid + 1, r, rt << 1 | 1);
    seg[rt] = seg[rt << 1] + seg[rt << 1 | 1];
}

void modifymax(
    int L, int R, int l, int r, int rt, ll t) {
    if (L <= l && R >= r && t < seg[rt].smi)
        return give_tag_max(rt, t);
    if (l != r) tag_down(l, r, rt);
    int mid = (l + r) >> 1;
    if (L <= mid) modifymax(L, R, l, mid, rt << 1, t);
    if (R > mid)
        modifymax(L, R, mid + 1, r, rt << 1 | 1, t);
    seg[rt] = seg[rt << 1] + seg[rt << 1 | 1];
}

void modifymin(
    int L, int R, int l, int r, int rt, ll t) {
    if (L <= l && R >= r && t > seg[rt].smx)
        return give_tag_min(rt, t);
    if (l != r) tag_down(l, r, rt);
    int mid = (l + r) >> 1;
    if (L <= mid) modifymin(L, R, l, mid, rt << 1, t);
    if (R > mid)
        modifymin(L, R, mid + 1, r, rt << 1 | 1, t);
    seg[rt] = seg[rt << 1] + seg[rt << 1 | 1];
}

void modifyadd(
    int L, int R, int l, int r, int rt, ll t) {
    if (L <= l && R >= r)
        return give_tag_add(l, r, rt, t);
    if (l != r) tag_down(l, r, rt);
    int mid = (l + r) >> 1;
    if (L <= mid) modifyadd(L, R, l, mid, rt << 1, t);
    if (R > mid)
        modifyadd(L, R, mid + 1, r, rt << 1 | 1, t);
    seg[rt] = seg[rt << 1] + seg[rt << 1 | 1];
}

ll query(int L, int R, int l, int r, int rt) {
    if (L <= l && R >= r) return seg[rt].sum;
    if (l != r) tag_down(l, r, rt);
    int mid = (l + r) >> 1;
    if (R <= mid) return query(L, R, l, mid, rt << 1);
    if (L > mid)
        return query(L, R, mid + 1, r, rt << 1 | 1);
    return query(L, R, l, mid, rt << 1) +
        query(L, R, mid + 1, r, rt << 1 | 1);
}

int main() {
    ios::sync_with_stdio(0), cin.tie(0);
    int n, m;
    cin >> n >> m;
    for (int i = 1; i <= n; ++i) cin >> a[i];
    build(1, n, 1);
    while (m--) {
        int k, x, y;
        ll t;
        cin >> k >> x >> y, ++x;
        if (k == 0) cin >> t, modifymin(x, y, 1, n, 1, t);
        else if (k == 1)
            cin >> t, modifymax(x, y, 1, n, 1, t);
        else if (k == 2)
            cin >> t, modifyadd(x, y, 1, n, 1, t);
        else cout << query(x, y, 1, n, 1) << "\n";
    }
}

```

## 2.10 Range Set

```

struct RangeSet { // [l, r)
    set<pii> S;
    void cut(int x) {

```

```

    auto it = S.lower_bound({x + 1, -1});
    if (it == S.begin()) return;
    auto [l, r] = *prev(it);
    if (l >= x || x >= r) return;
    S.erase(prev(it));
    S.insert({l, x});
    S.insert({x, r});
}
vector<pii> split(int l, int r) {
    // remove and return ranges in [l, r)
    cut(l), cut(r);
    vector<pii> res;
    while (true) {
        auto it = S.lower_bound({l, -1});
        if (it == S.end() || r <= it->first) break;
        res.pb(*it), S.erase(it);
    }
    return res;
}
void insert(int l, int r) {
    // add a range [l, r), [l, r) not in S
    auto it = S.lower_bound({l, r});
    if (it != S.begin() && prev(it)->second == l)
        l = prev(it)->first, S.erase(prev(it));
    if (it != S.end() && r == it->first)
        r = it->second, S.erase(it);
    S.insert({l, r});
}
bool count(int x) {
    auto it = S.lower_bound({x + 1, -1});
    return it != S.begin() && prev(it)->first <= x
        && x < prev(it)->second;
}
};

```

## 2.11 vEB Tree

```

using u64=uint64_t;
constexpr int lsb(u64 x)
{ return x?__builtin_ctzll(x):1<<30; }
constexpr int msb(u64 x)
{ return x?63-__builtin_clzll(x):-1; }
template<int N, class T=void>
struct veb{
    static const int M=N>>1;
    veb<M> ch[1<<N-M];
    veb<N-M> aux;
    int mn,mx;
    veb():mn(1<<30),mx(-1){}
    constexpr int mask(int x){return x&((1<<M)-1);}
    bool empty(){return mx==-1;}
    int min(){return mn;}
    int max(){return mx;}
    bool have(int x){
        return x==mn?true:ch[x>>M].have(mask(x));
    }
    void insert_in(int x){
        if(empty()) return mn=mx=x,void();
        if(x<mn) swap(x,mn);
        if(x>mx) mx=x;
        if(ch[x>>M].empty()) aux.insert_in(x>>M);
        ch[x>>M].insert_in(mask(x));
    }
    void erase_in(int x){
        if(mn==mx) return mn=1<<30,mx=-1,void();
        if(x==mn) mn=x=(aux.min()<<M)^ch[aux.min()].min();
        ch[x>>M].erase_in(mask(x));
        if(ch[x>>M].empty()) aux.erase_in(x>>M);
        if(x==mx){
            if(aux.empty()) mx=mn;
            else mx=(aux.max()<<M)^ch[aux.max()].max();
        }
    }
    void insert(int x){
        if(!have(x)) insert_in(x);
    }
    void erase(int x){
        if(have(x)) erase_in(x);
    }
    int next(int x){// >=x
        if(x>mx) return 1<<30;
        if(x<mn) return mn;
        if(mask(x)<=ch[x>>M].max())
            return ((x>>M)<<M)^ch[x>>M].next(mask(x));
        int y=aux.next((x>>M)+1);
        return (y<<M)^ch[y].min();
    }
}

```

```

int prev(int x){// <x
    if(x<=mn) return -1;
    if(x>mx) return mx;
    if(x<=(aux.min()<<M)+ch[aux.min()].min())
        return mn;
    if(mask(x)>ch[x>>M].min())
        return ((x>>M)<<M)^ch[x>>M].prev(mask(x));
    int y=aux.prev(x>>M);
    return (y<<M)^ch[y].max();
}
};
template<int N>
struct veb<N,typename enable_if<N<=6>::type>{
    u64 a;
    veb():a(0){}
    void insert_in(int x){a|=1ull<<x;}
    void insert(int x){a|=1ull<<x;}
    void erase_in(int x){a&=~(1ull<<x);}
    void erase(int x){a&=~(1ull<<x);}
    bool have(int x){return a>>x&1;}
    bool empty(){return a==0;}
    int min(){return lsb(a);}
    int max(){return msb(a);}
    int next(int x){return lsb(a&~((1ull<<x)-1));}
    int prev(int x){return msb(a&((1ull<<x)-1));}
}
};

```

## 2.12 KD Tree

```

namespace kdt {
int root, lc[maxn], rc[maxn], xl[maxn], xr[maxn],
    yl[maxn], yr[maxn];
point p[maxn];
int build(int l, int r, int dep = 0) {
    if (l == r) return -1;
    function<bool(const point &, const point &)> f =
        [dep](const point &a, const point &b) {
            if (dep & 1) return a.x < b.x;
            else return a.y < b.y;
        };
    int m = (l + r) >> 1;
    nth_element(p + l, p + m, p + r, f);
    xl[m] = xr[m] = p[m].x;
    yl[m] = yr[m] = p[m].y;
    lc[m] = build(l, m, dep + 1);
    if (~lc[m]) {
        xl[m] = min(xl[m], xl[lc[m]]);
        xr[m] = max(xr[m], xr[lc[m]]);
        yl[m] = min(yl[m], yl[lc[m]]);
        yr[m] = max(yr[m], yr[lc[m]]);
    }
    rc[m] = build(m + 1, r, dep + 1);
    if (~rc[m]) {
        xl[m] = min(xl[m], xl[rc[m]]);
        xr[m] = max(xr[m], xr[rc[m]]);
        yl[m] = min(yl[m], yl[rc[m]]);
        yr[m] = max(yr[m], yr[rc[m]]);
    }
    return m;
}
bool bound(const point &q, int o, long long d) {
    double ds = sqrt(d + 1.0);
    if (q.x < xl[o] - ds || q.x > xr[o] + ds ||
        q.y < yl[o] - ds || q.y > yr[o] + ds)
        return false;
    return true;
}
long long dist(const point &a, const point &b) {
    return (a.x - b.x) * 1ll * (a.x - b.x) +
        (a.y - b.y) * 1ll * (a.y - b.y);
}
void dfs(
    const point &q, long long &d, int o, int dep = 0) {
    if (!bound(q, o, d)) return;
    long long cd = dist(p[o], q);
    if (cd != 0) d = min(d, cd);
    if ((dep & 1) && q.x < p[o].x ||
        !(dep & 1) && q.y < p[o].y) {
        if (~lc[o]) dfs(q, d, lc[o], dep + 1);
        if (~rc[o]) dfs(q, d, rc[o], dep + 1);
    } else {
        if (~rc[o]) dfs(q, d, rc[o], dep + 1);
        if (~lc[o]) dfs(q, d, lc[o], dep + 1);
    }
}
void init(const vector<point> &v) {
    for (int i = 0; i < v.size(); ++i) p[i] = v[i];
}
}

```

```

    root = build(0, v.size());
}
long long nearest(const point &q) {
    long long res = 1e18;
    dfs(q, res, root);
    return res;
}
// namespace kdt

```

## 2.13 pbds

```

#include <ext/pb_ds/assoc_container.hpp>
#include <ext/pb_ds/priority_queue.hpp>
using namespace __gnu_pbds;
// heap tags: paring/binary/binomial/rc_binomial/thin
template<typename T>
using pbds_heap = __gnu_pbds::priority_queue<T, less<T>, \
    pairing_heap_tag>;

// pbds_heap::point_iterator
// x = pq.push(10); pq.modify(x, 87); a.join(b);
// tree tags: rb_tree_tag/ov_tree_tag/splay_tree_tag
template<typename T>
using ordered_set = tree<T, null_type, less<T>,
    rb_tree_tag, tree_order_statistics_node_update>;
// find_by_order, order_of_key
// hash tables: cc_hash_table/gp_hash_table

```

## 3 Graph

### 3.1 SCC

```

struct SCC {
    int n, nscc, _id;
    vector<vector<int>> g;
    vector<int> dep, low, scc_id, stk;
    void dfs(int v) {
        dep[v] = low[v] = _id++;
        for (int u : g[v]) if (scc_id[u] == -1) {
            if (low[u] == -1) dfs(u);
            low[v] = min(low[v], low[u]);
        }
        if (low[v] == dep[v]) {
            int id = nscc++;
            do {
                x = stk.back(), stk.pop_back(), scc_id[x] = id;
            } while (x != v);
        }
    }
    void build() {
        for (int i = 0; i < n; ++i) if (low[i] == -1)
            dfs(i);
    }
    void add_edge(int u, int v) { g[u].pb(v); }
    SCC(int _n) : n(_n), nscc(0), _id(0), g(n), dep(n),
        low(n, -1), scc_id(n, -1), stk() {}
};

```

### 3.2 BCC Vertex

```

struct BCC { // 0-base
    int n, dft, nbcc;
    vector<int> low, dfn, bln, stk, is_ap, cir;
    vector<vector<int>> G, bcc, nG;
    void make_bcc(int u) {
        bcc.emplace_back(1, u);
        for (; stk.back() != u; stk.pop_back())
            bln[stk.back()] = nbcc, bcc[nbcc].pb(stk.back());
        stk.pop_back(), bln[u] = nbcc++;
    }
    void dfs(int u, int f) {
        int child = 0;
        low[u] = dfn[u] = ++dft, stk.pb(u);
        for (int v : G[u])
            if (!dfn[v]) {
                dfs(v, u), ++child;
                low[u] = min(low[u], low[v]);
                if (dfn[u] <= low[v]) {
                    is_ap[u] = 1, bln[u] = nbcc;
                    make_bcc(v), bcc.back().pb(u);
                }
            } else if (dfn[v] < dfn[u] && v != f)
                low[u] = min(low[u], dfn[v]);
        if (f == -1 && child < 2) is_ap[u] = 0;
        if (f == -1 && child == 0) make_bcc(u);
    }
    BCC(int _n) : n(_n), dft(0),
        nbcc(0), low(n), dfn(n), bln(n), is_ap(n), G(n) {}
};

```

```

void add_edge(int u, int v) {
    G[u].pb(v), G[v].pb(u);
}
void solve() {
    for (int i = 0; i < n; ++i)
        if (!dfn[i]) dfs(i, -1);
}
void block_cut_tree() {
    cir.resize(nbcc);
    for (int i = 0; i < n; ++i)
        if (is_ap[i])
            bln[i] = nbcc++;
    cir.resize(nbcc, 1), nG.resize(nbcc);
    for (int i = 0; i < nbcc && !cir[i]; ++i)
        for (int j : bcc[i])
            if (is_ap[j])
                nG[i].pb(bln[j]), nG[bln[j]].pb(i);
} // up to 2 * n - 2 nodes!! bln[i] for id
};

```

### 3.3 Directed MST

```

using D = int;
struct edge { int u, v; D w; };
// 0-based, return index of edges
vector<int> dmst(vector<edge> &e, int n, int root) {
    using T = pair<D, int>;
    using PQ = pair
        <priority_queue<T, vector<T>, greater<T>>, D>;
    auto push = [](PQ &pq, T v) {
        pq.first.emplace(v.first - pq.second, v.second);
    };
    auto top = [](const PQ &pq) -> T {
        auto r = pq.first.top();
        return {r.first + pq.second, r.second};
    };
    auto join = [&push, &top](PQ &a, PQ &b) {
        if (a.first.size() < b.first.size()) swap(a, b);
        while (!b.first.empty())
            push(a, top(b)), b.first.pop();
    };
    vector<PQ> h(n * 2);
    for (int i = 0; i < e.size(); ++i)
        push(h[e[i].v], {e[i].w, i});
    vector<int>
        a(n * 2), v(n * 2, -1), pa(n * 2, -1), r(n * 2);
    iota(all(a), 0);
    auto o = [&](int x) { int y;
        for (y = x; a[y] != y; y = a[y]);
        for (int ox = x; x != y; ox = x)
            x = a[x], a[ox] = y;
        return y;
    };
    v[root] = n + 1;
    int pc = n;
    for (int i = 0; i < n; ++i) if (v[i] == -1) {
        for (int p =
            i; v[p] == -1 || v[p] == i; p = o(e[r[p]].u)) {
            if (v[p] == i) {
                int q = p; p = pc++;
                do {
                    h[q].second = -h[q].first.top().first;
                    join(h[pa[q]] = a[q] = p, h[q]);
                } while ((q = o(e[r[q]].u)) != p);
            }
            v[p] = i;
            while (!h[p].first
                .empty() && o(e[top(h[p]).second].u) == p)
                h[p].first.pop();
            r[p] = top(h[p]).second;
        }
    }
    vector<int> ans;
    for (int i = pc - 1; i >= 0; i--)
        if (i != root && v[i] != n) {
            for (int f = e[r[i]].u)
                v; f != -1 && v[f] != n; f = pa[f]) v[f] = n;
            ans.pb(r[i]);
        }
    return ans;
}

```

### 3.4 Negative Cycle

```

vector<pll> adj[maxn];
template <typename T>
struct NegativeCycle {

```



```

vector<T> dis;
vector<int> rt;
int n; T INF;
vector<int> cycle;
NegativeCycle () = default;
NegativeCycle
    (int _n) : n(_n), INF(numeric_limits<T>::max()) {
    dis.assign(n, 0), rt.assign(n, -1);
    int relax = -1;
    for (int t = 0; t < n; ++t) {
        relax = -1;
        for (int i = 0; i < n; ++i) {
            for (auto [j, w] : adj[i]) if (dis[j] > dis[i] + w) {
                dis[j] = dis[i] + w, rt[j] = i;
                relax = j;
            }
        }
    }
    if (relax != -1) {
        int s = relax;
        for (int i = 0; i < n; ++i) s = rt[s];
        vector<bool> vis(n, false);
        while (!vis[s]) {
            cycle.push_back(s), vis[s] = true;
            s = rt[s];
        }
        reverse(cycle.begin(), cycle.end());
    }
};

```

### 3.5 Dominator Tree

```

int in[maxn], id[maxn], par[maxn], dfn = 0;
int mn[maxn], idom[maxn], sdom[maxn], ans[maxn];
int fa[maxn]; // dsu
int n, m;

struct edge{
    int to, id;
    edge(){}
    edge(int _to, int _id) : to(_to), id(_id){}
};
vector<edge> adj[3][maxn];

void dfs(int pos){
    in[pos] = ++dfn;
    id[dfn] = pos;
    for(auto [x, id] : adj[0][pos]){
        if(in[x]) continue;
        dfs(x);
        par[x] = pos;
    }
}

int find(int x){
    if(fa[x] == x) return x;
    int tmp = fa[x];
    fa[x] = find(fa[x]);
    if(in[sdom[mn[tmp]]] < in[sdom[mn[x]]]){
        mn[x] = mn[tmp];
    }
    return fa[x];
}

void tar(int st){
    dfs(st);
    for(int i = 0; i < n; i++) mn[i] = sdom[i] = fa[i] = i;
    for(int i = dfn; i >= 2; i--){
        int pos = id[i], res = INF; // res : in(x) of sdom
        for(auto [x, id] : adj[1][pos]){
            if(!in[x]) continue;
            find(x);
            if(in[pos] > in[x]) res = min(res, in[x]);
            else res = min(res, in[sdom[mn[x]]]);
        }
        sdom[pos] = id[res];
        fa[pos] = par[pos];
        adj[2][sdom[pos]].eb(pos, 0);
        pos = par[pos];
        for(auto [x, id] : adj[2][pos]){
            find(x);
            if(sdom[mn[x]] == pos){
                idom[x] = pos;
            }
        }
    }
}

```

```

    else{
        idom[x] = mn[x];
    }
}
adj[2][pos].clear();
}
for(int i = 2; i <= dfn; i++){
    int x = id[i];
    if(idom[x] != sdom[x]) idom[x] = idom[idom[x]];
}
}

```

### 3.6 Maximum Clique

```

struct MaximumClique{
    typedef bitset<maxn> bst;
    bst adj[maxn], empt;
    int p[maxn], n, ans;
    void init(int _n){
        n = _n;
        for(int i = 0; i < n; i++) adj[i].reset();
    }
    void BronKerbosch(bst R, bst P, bst X){
        if(P == empt && X == empt){
            ans = max(ans, (int)R.count());
            return;
        }
        bst tmp = P | X;
        if((R | P | X).count() <= ans) return;
        int u;
        for(int i = 0; i < n; i++){
            if(tmp[u == p[i]]) break;
        }
        bst lim = P & ~adj[u];
        for(int i = 0; i < n; i++){
            int v = p[i];
            if(lim[v]){
                R[v] = 1;
                BronKerbosch
                    (R, P & adj[v], X & adj[v]);
                R[v] = 0, P[v] = 0, X[v] = 1;
            }
        }
    }
    void add_edge(int a, int b){
        adj[a][b] = adj[b][a] = 1;
    }
    int solve(){
        bst R, P, X;
        ans = 0, P.flip();
        iota(p, p + n, 0);
        random_shuffle
            (p, p + n, BronKerbosch(R, P, X));
        return ans;
    }
};

```

### 3.7 Virtual Tree

```

// need lca, in, out
vector<pll> virtual_tree(vector<int> &v) {
    auto cmp = [&](int x, int y) {return in[x] < in[y];};
    sort(all(v), cmp);
    int sz = (int)v.size();
    for (int i = 0; i + 1 < sz; ++i)
        v.pb(lca(v[i], v[i + 1]));
    sort(all(v), cmp);
    v.resize(unique(all(v)) - v.begin());
    vector<int> stk(1, v[0]);
    vector<pll> res;
    for (int i = 1; i < (int)v.size(); ++i) {
        int x = v[i];
        while (out[stk.back()] < out[x]) stk.pop_back();
        res.emplace_back(stk.back(), x), stk.pb(x);
    }
    return res;
}

```

### 3.8 Minimum Steiner Tree

```

struct SteinerTree { // 0-base
    int n, dst[N][N], dp[1 << T][N], tdst[N];
    int vcst[N]; // the cost of vertices
    void init(int _n) {
        n = _n;
        for (int i = 0; i < n; ++i) {
            fill_n(dst[i], n, INF);
        }
    }
};

```

```

    dst[i][i] = vcst[i] = 0;
}
}
void chmin(int &x, int val) {
    x = min(x, val);
}
void add_edge(int ui, int vi, int wi) {
    chmin(dst[ui][vi], wi);
}
void shortest_path() {
    for (int k = 0; k < n; ++k)
        for (int i = 0; i < n; ++i)
            for (int j = 0; j < n; ++j)
                chmin(dst[i][j], dst[i][k] + dst[k][j]);
}
int solve(const vector<int>& ter) {
    shortest_path();
    int t = SZ(ter), full = (1 << t) - 1;
    for (int i = 0; i <= full; ++i)
        fill_n(dp[i], n, INF);
    copy_n(vcst, n, dp[0]);
    for (int msk = 1; msk <= full; ++msk) {
        if (!(msk & (msk - 1))) {
            int who = __lg(msk);
            for (int i = 0; i < n; ++i)
                dp[msk][i] = vcst[ter[who]] + dst[ter[who]][i];
        }
        for (int i = 0; i < n; ++i)
            for (int sub = (msk - 1) & msk; sub; sub = (sub - 1) & msk)
                chmin(dp[msk][i], dp[sub][i] + dp[msk ^ sub][i] - vcst[i]);
        for (int i = 0; i < n; ++i) {
            tdst[i] = INF;
            for (int j = 0; j < n; ++j)
                chmin(tdst[i], dp[msk][j] + dst[j][i]);
        }
        copy_n(tdst, n, dp[msk]);
    }
    return *min_element(dp[full], dp[full] + n);
}
}; // O(V 3^AT + V^2 2^AT)

```

## 4 Flow / Matching

### 4.1 Dinic

```

struct Dinic{
    struct edge{
        ll to, cap;
        edge(){}
        edge(int _to, ll _cap) : to(_to), cap(_cap){}
    };
    vector<edge> e;
    vector<vector<int>> adj;
    vector<int> iter, level;
    int n, s, t;
    void init(int _n, int _s, int _t){
        n = _n, s = _s, t = _t;
        adj = vector<vector<int>>(n);
        iter = vector<int>(n);
        level = vector<int>(n);
        e.clear();
    }
    void add_edge(int from, int to, ll cap){
        adj[from].pb(e.size()), adj[to].pb(e.size() + 1);
        e.pb(edge(to, cap)), e.pb(edge(from, 0));
    }
    void bfs(){
        fill(level.begin(), level.end(), -1);
        level[s] = 0;
        queue<int> q;
        q.push(s);
        while(!q.empty()){
            int cur = q.front(); q.pop();
            for(auto id : adj[cur]){
                auto [to, cap] = e[id];
                if(level[to] == -1 && cap){
                    level[to] = level[cur] + 1;
                    q.push(to);
                }
            }
        }
    }
    ll dfs(int pos, ll flow){
        if(pos == t) return flow;

```

```

        for(int &i = iter[pos]; i < adj[pos].size(); i++){
            auto [to, cap] = e[adj[pos][i]];
            if(level[to] == level[pos] + 1 && cap){
                ll tmp = dfs(to, min(flow, cap));
                if(tmp){
                    e[adj[pos][i]].cap -= tmp;
                    e[adj[pos][i] ^ 1].cap += tmp;
                    return tmp;
                }
            }
            iter[pos]++;
        }
        return 0;
    }
} flow;

```

### 4.2 Min Cost Max Flow

```

struct MCMF{
    using T = ll;
    struct edge{
        int to;
        T cap, cost;
        edge(){}
        edge(int _to, T _cap, T _cost) : to(_to), cap(_cap), cost(_cost){}
    };
    vector<edge> e;
    vector<vector<int>> adj;
    vector<int> iter, inq;
    vector<T> dist;
    int n, s, t;
    void init(int _n, int _s, int _t){
        n = _n, s = _s, t = _t;
        adj = vector<vector<int>>(n);
        iter = vector<int>(n);
        dist = vector<T>(n);
        inq = vector<int>(n);
        e.clear();
    }
    void add_edge(int from, int to, T cap, T cost = 0){
        adj[from].pb(e.size()), adj[to].pb(e.size() + 1);
        e.pb(edge(to, cap, cost)), e.pb(edge(from, 0, -cost));
    }
    bool spfa(){
        fill(dist.begin(), dist.end(), INF);
        queue<int> q;
        q.push(s);
        dist[s] = 0, inq[s] = 1;
        while(!q.empty()){
            int pos = q.front(); q.pop();
            inq[pos] = 0;
            for(auto id : adj[pos]){
                auto [to, cap, cost] = e[id];
                if(cap && dist[to] > dist[pos] + cost){
                    dist[to] = dist[pos] + cost;
                    if(!inq[to]) q.push(to), inq[to] = 1;
                }
            }
        }
        return dist[t] != INF;
    }
    T dfs(int pos, T flow){
        if(pos == t) return flow;
        inq[pos] = 1;
        for(int &i = iter[pos]; i < adj[pos].size(); i++){
            auto [to, cap, cost] = e[adj[pos][i]];
            if(!inq[to] && dist[to] == dist[pos] + cost && cap){
                T tmp = dfs(to, min(flow, cap));
                if(tmp){
                    inq[pos] = 0;
                    e[adj[pos][i]].cap -= tmp;
                    e[adj[pos][i] ^ 1].cap += tmp;
                    return tmp;
                }
            }
            iter[pos]++;
        }
        inq[pos] = 0;
        return 0;
    }
    pair<T, T> mcmf(){
        T flow = 0, cost = 0;
        while(true){

```



```

        if(!spfa()) break;
        fill(iter.begin(), iter.end(), 0);
        T tmp;
        while((tmp = dfs(s, INF)) > 0){
            flow += tmp, cost += tmp * dist[t];
        }
    }
    return {flow, cost};
}
} flow;

```

### 4.3 Gomory Hu

```

void Gomory_Hu_Tree(vector<int> st){
    if(st.size() <= 1) return;
    int s = st[0], t = st[1];
    flow.init(n, s, t);
    for(auto [a, b, w] : e) flow.add_edge(a, b, w);
    int cost = flow.flow();
    flow.bfs();
    adj[s].eb(t, cost), adj[t].eb(s, cost);
    vector<int> a, b;
    for(auto x : st){
        if(flow.level[x] == -1) a.pb(x);
        else b.pb(x);
    }
    Gomory_Hu_Tree(a);
    Gomory_Hu_Tree(b);
}

```

### 4.4 SW Min Cut

```

int edge[maxn][maxn], par[maxn], siz[maxn];
int dist[maxn], vis[maxn], done[maxn];
int n, m;
int root(int x)
{ return x == par[x] ? x : par[x] = root(par[x]); }
int contract(int &s, int &t){
    memset(dist, 0, sizeof(dist));
    memset(vis, 0, sizeof(vis));
    int mincut = INF, id, maxc;
    for(int i = 0; i < n; i++){
        id = maxc = -1;
        for(int j = 0; j < n; j++){
            if(!done[j] && !vis[j] && dist[j] > maxc){
                id = j;
                maxc = dist[j];
            }
        }
        if(id == -1) return mincut;
        s = t, t = id;
        mincut = maxc;
        vis[id] = true;
        for(int j = 0; j < n; j++){
            if(!done[j] && !vis[j]) dist[j] += edge[id][j];
        }
    }
    return mincut;
}
int Stoer_Wagner(){
    int mincut = INF, s, t, tmp;
    for(int i = 1; i < n; i++){
        tmp = contract(s, t);
        done[t] = true;
        mincut = min(mincut, tmp);
        if(!mincut) return 0;
        for(int j = 0; j < n; j++){
            if(!done[j] && !vis[j]){
                if(!done[j]) edge[s][j] = (edge[j][s] += edge[j][t]);
            }
        }
    }
    return mincut;
}

```

### 4.5 Hopcroft Karp

```

int mx[maxn], my[maxn], dx[maxn], dy[maxn], vis[maxn];
vector<int> adj[maxn];
int l, r, m;

int dfs(int pos){
    for(auto x : adj[pos]){
        if(!vis[x] && dy[x] == dx[pos] + 1){
            vis[x] = 1;
            if(my[x] != -1 && dy[x] == lim) continue;
            if(my[x] == -1 || dfs(my[x])){
                my[x] = pos, mx[pos] = x;
            }
        }
    }
}

```

```

        return true;
    }
}
return false;
}

int bfs(){
    fill(dx, dx + l, -1);
    fill(dy, dy + r, -1);
    queue<int> q;
    for(int i = 0; i < l; i++){
        if(mx[i] == -1) dx[i] = 0, q.push(i);
    }
    lim = INF;
    while(!q.empty()){
        int pos = q.front(); q.pop();
        if(dx[pos] > lim) break;
        for(auto x : adj[pos]){
            if(dy[x] == -1){
                dy[x] = dx[pos] + 1;
                if(my[x] == -1) lim = dy[x];
                else dx
                    [my[x]] = dy[x] + 1, q.push(my[x]);
            }
        }
    }
    return lim != INF;
}

```

```

void Hopcroft_Karp(){
    int res = 0;
    for(int i = 0; i < l; i++) mx[i] = -1;
    for(int i = 0; i < r; i++) my[i] = -1;
    while(bfs()){
        fill(vis, vis + l + r, 0);
        for(int i = 0; i < l; i++){
            if(mx[i] == -1 && dfs(i)) res++;
        }
    }
}

```

### 4.6 Kuhn Munkres

```

struct Hungarian{
    using T = ll;
    vector<T> lx, ly, slack;
    vector<int> vx, vy, match;
    vector<vector<T>> w;
    queue<int> q;
    int n;
    void init(int _n){
        n = _n;
        lx.resize(n), ly.resize(n), slack.resize(n);
        vx.resize
            (n), vy.resize(n), match.resize(n, -1);
        w.resize(n, vector<T>(n));
    }
    void inp(int x, int y, int val){
        w[x][y] = val;
        lx[x] = max(lx[x], val);
    }
    int dfs(int x){
        if(vx[x]) return false;
        vx[x] = 1;
        for(int i = 0; i < n; i++){
            if(lx[x] + ly[i] == w[x][i] && !vy[i]){
                vy[i] = true;
                if(match[i] == -1 || dfs(match[i])){
                    match[i] = x;
                    return true;
                }
            }
        }
    }
    return false;
}

int pdfs(int x){
    fill(vx.begin(), vx.end(), 0);
    fill(vy.begin(), vy.end(), 0);
    return dfs(x);
}

void upd(int x){
    for(int i = 0; i < n; i++){
        if(!slack[i]) continue;
        slack[i] =
            min(slack[i], lx[x] + ly[i] - w[x][i]);
    }
}

```

```

        if(!slack[i] && !vy[i]) q.push(i);
    }
}
void relabel(){
    T mn = numeric_limits<T>::max() / 3;
    for(int i = 0; i < n; i++){
        if(!vy[i]) mn = min(mn, slack[i]);
    }
    for(int i = 0; i < n; i++){
        if(vx[i]) lx[i] -= mn;
        if(vy[i]) ly[i] += mn;
        else{
            slack[i] -= mn;
            if(!slack[i]) q.push(i);
        }
    }
}
auto solve(){
    for(int i = 0; i < n; i++){
        if(pdfs(i)) continue;
        while(!q.empty()) q.pop();
        fill(slack.begin(), slack.end(), INF);
        for(int j = 0; j < n; j++) if(vx[j]) upd(j);
        int ok = 0;
        while(!ok){
            relabel();
            while(!q.empty()){
                int j = q.front(); q.pop();
                if(match[j] == -1){
                    pdfs(i);
                    ok = 1;
                    break;
                }
            }
            vy[j] = vx
            [match[j]] = 1, upd(match[j]);
        }
    }
    T ans = 0;
    for(int i = 0; i < n; i++){
        ans += w[match[i]][i];
    }
    for(int i = 0; i < n; i++) lx[match[i]] = i;
    return make_pair(ans, lx);
}
} h;

```

## 4.7 General Graph Matching

```

struct Matching { // 0-based
    int n, tk;
    vector<vector<int>> g;
    vector<int> fa, pre, match, s, t;
    queue<int> q;
    int Find(int u) {
        return u == fa[u] ? u : fa[u] = Find(fa[u]);
    }
    int lca(int x, int y) {
        tk++;
        x = Find(x), y = Find(y);
        for (; ; swap(x, y)) {
            if (x != n) {
                if (t[x] == tk) return x;
                t[x] = tk;
                x = Find(pre[match[x]]);
            }
        }
    }
    void blossom(int x, int y, int l) {
        while (Find(x) != l) {
            pre[x] = y, y = match[x];
            if (s[y] == 1) q.push(y), s[y] = 0;
            if (fa[x] == x) fa[x] = l;
            if (fa[y] == y) fa[y] = l;
            x = pre[y];
        }
    }
    bool bfs(int r) {
        iota(all(fa), 0), fill(all(s), -1);
        while (!q.empty()) q.pop();
        q.push(r);
        s[r] = 0;
        while (!q.empty()) {
            int x = q.front(); q.pop();
            for (int u : g[x]) {
                if (s[u] == -1) {

```

```

                    pre[u] = x, s[u] = 1;
                    if (match[u] == n) {
                        for (int a = u, b =
                            x, last; b != n; a = last, b = pre[a])
                            last =
                                match[b], match[b] = a, match[a] = b;
                        return true;
                    }
                    q.push(match[u]);
                    s[match[u]] = 0;
                } else if (!s[u] && Find(u) != Find(x)) {
                    int l = lca(u, x);
                    blossom(x, u, l);
                    blossom(u, x, l);
                }
            }
        }
        return false;
    }
    int solve() {
        int res = 0;
        for (int x = 0; x < n; ++x) {
            if (match[x] == n) res += bfs(x);
        }
        return res;
    }
    void add_edge(int u, int v) {
        g[u].push_back(v), g[v].push_back(u);
    }
    Matching (int _n) : n(_n), tk(0), g(n), fa(n + 1),
        pre(n + 1, n), match(n + 1, n), s(n + 1), t(n) {}
};

```

## 4.8 Weighted General Graph Matching

```

struct WeightGraph { // 1-based
    static const int inf = INT_MAX;
    static const int maxn = 514;
    struct edge {
        int u, v, w;
        edge(){}
        edge(int u, int v, int w): u(u), v(v), w(w) {}
    };
    int n, n_x;
    edge g[maxn * 2][maxn * 2];
    int lab[maxn * 2];
    int match[maxn * 2], slack[maxn * 2], st[maxn * 2], pa[maxn * 2];
    int flo_from [maxn * 2][maxn + 1], S[maxn * 2], vis[maxn * 2];
    vector<int> flo[maxn * 2];
    queue<int> q;
    int e_delta(const edge &e) {
        return lab[e.u] + lab[e.v] - g[e.u][e.v].w * 2;
    }
    void update_slack (int u, int x) { if (!slack[x] || e_delta(g[u][x]) < e_delta(g[slack[x]][x])) slack[x] = u; }
    void set_slack(int x) {
        slack[x] = 0;
        for (int u = 1; u <= n; ++u)
            if (g[u][x].w > 0 && st[u] != x && S[st[u]] == 0)
                update_slack(u, x);
    }
    void q_push(int x) {
        if (x <= n) q.push(x);
        else for (size_t i
            = 0; i < flo[x].size(); i++) q_push(flo[x][i]);
    }
    void set_st(int x, int b) {
        st[x] = b;
        if (x > n) for (size_t i = 0;
            i < flo[x].size(); ++i) set_st(flo[x][i], b);
    }
    int get_pr(int b, int xr) {
        int pr = find(flo[b].begin(), flo[b].end(), xr) - flo[b].begin();
        if (pr % 2 == 1) {
            reverse(flo[b].begin() + 1, flo[b].end());
            return (int)flo[b].size() - pr;
        }
        return pr;
    }
    void set_match(int u, int v) {
        match[u] = g[u][v].v;
        if (u <= n) return;
        edge e = g[u][v];
        int xr = flo_from[u][e.u], pr = get_pr(u, xr);
    }
};

```

```

    for (int i = 0; i
        < pr; ++i) set_match(flo[u][i], flo[u][i ^ 1]);
    set_match(xr, v);
    rotate(flo[
        u].begin(), flo[u].begin() + pr, flo[u].end());
}
void augment(int u, int v) {
    for (; ; ) {
        int xnv = st[match[u]];
        set_match(u, v);
        if (!xnv) return;
        set_match(xnv, st[pa[xnv]]);
        u = st[pa[xnv]], v = xnv;
    }
}
int get_lca(int u, int v) {
    static int t = 0;
    for (++t; u || v; swap(u, v)) {
        if (u == 0) continue;
        if (vis[u] == t) return u;
        vis[u] = t;
        u = st[match[u]];
        if (u) u = st[pa[u]];
    }
    return 0;
}
void add_blossom(int u, int lca, int v) {
    int b = n + 1;
    while (b <= n_x && st[b]) ++b;
    if (b > n_x) ++n_x;
    lab[b] = 0, S[b] = 0;
    match[b] = match[lca];
    flo[b].clear();
    flo[b].push_back(lca);
    for (int x = u, y; x != lca; x = st[pa[y]])
        flo[b].push_back(x), flo
            [b].push_back(y = st[match[x]]), q_push(y);
    reverse(flo[b].begin() + 1, flo[b].end());
    for (int x = v, y; x != lca; x = st[pa[y]])
        flo[b].push_back(x), flo
            [b].push_back(y = st[match[x]]), q_push(y);
    set_st(b, b);
    for (int x
        = 1; x <= n_x; ++x) g[b][x].w = g[x][b].w = 0;
    for (int x = 1; x <= n; ++x) flo_from[b][x] = 0;
    for (size_t i = 0; i < flo[b].size(); ++i) {
        int xs = flo[b][i];
        for (int x = 1; x <= n_x; ++x)
            if (g[b][x].w ==
                0 || e_delta(g[xs][x]) < e_delta(g[b][x]))
                g[b][x] = g[xs][x], g[x][b] = g[x][xs];
        for (int x = 1; x <= n; ++x)
            if (flo_from[xs][x]) flo_from[b][x] = xs;
    }
    set_slack(b);
}
void expand_blossom(int b) {
    for (size_t i = 0; i < flo[b].size(); ++i)
        set_st(flo[b][i], flo[b][i]);
    int xr =
        flo_from[b][g[b][pa[b]].u], pr = get_pr(b, xr);
    for (int i = 0; i < pr; i += 2) {
        int xs = flo[b][i], xns = flo[b][i + 1];
        pa[xs] = g[xns][xs].u;
        S[xs] = 1, S[xns] = 0;
        slack[xs] = 0, set_slack(xns);
        q_push(xns);
    }
    S[xr] = 1, pa[xr] = pa[b];
    for (size_t i = pr + 1; i < flo[b].size(); ++i) {
        int xs = flo[b][i];
        S[xs] = -1, set_slack(xs);
    }
    st[b] = 0;
}
bool on_found_edge(const edge &e) {
    int u = st[e.u], v = st[e.v];
    if (S[v] == -1) {
        pa[v] = e.u, S[v] = 1;
        int nu = st[match[v]];
        slack[v] = slack[nu] = 0;
        S[nu] = 0, q_push(nu);
    } else if (S[v] == 0) {
        int lca = get_lca(u, v);
        if (!
            lca) return augment(u, v), augment(v, u), true;
    }
    else add_blossom(u, lca, v);
}
return false;
}
bool matching() {
    memset(S + 1, -1, sizeof(int) * n_x);
    memset(slack + 1, 0, sizeof(int) * n_x);
    q = queue<int>();
    for (int x = 1; x <= n_x; ++x)
        if (st[x] == x
            && !match[x]) pa[x] = 0, S[x] = 0, q_push(x);
    if (q.empty()) return false;
    for (; ; ) {
        while (q.size()) {
            int u = q.front(); q.pop();
            if (S[st[u]] == 1) continue;
            for (int v = 1; v <= n; ++v)
                if (g[u][v].w > 0 && st[u] != st[v]) {
                    if (e_delta(g[u][v]) == 0) {
                        if (on_found_edge(g[u][v])) return true;
                    } else update_slack(u, st[v]);
                }
        }
        int d = inf;
        for (int b = n + 1; b <= n_x; ++b)
            if (st[b]
                == b && S[b] == 1) d = min(d, lab[b] / 2);
        for (int x = 1; x <= n_x; ++x)
            if (st[x] == x && slack[x]) {
                if (S[x] ==
                    -1) d = min(d, e_delta(g[slack[x]][x]));
                else if (S[x] == 0)
                    d = min(d, e_delta(g[slack[x]][x]) / 2);
            }
        for (int u = 1; u <= n; ++u) {
            if (S[st[u]] == 0) {
                if (lab[u] <= d) return 0;
                lab[u] -= d;
            } else if (S[st[u]] == 1) lab[u] += d;
        }
        for (int b = n + 1; b <= n_x; ++b)
            if (st[b] == b) {
                if (S[st[b]] == 0) lab[b] += d * 2;
                else if (S[st[b]] == 1) lab[b] -= d * 2;
            }
        q = queue<int>();
        for (int x = 1; x <= n_x; ++x)
            if (st[x] == x && slack[x] && st[slack
                [x]] != x && e_delta(g[slack[x]][x]) == 0)
                if (on_found_edge
                    (g[slack[x]][x])) return true;
        for (int b = n + 1; b <= n_x; ++b)
            if (st[b] == b && S
                [b] == 1 && lab[b] == 0) expand_blossom(b);
    }
    return false;
}
pair<long long, int> solve() {
    memset(match + 1, 0, sizeof(int) * n);
    n_x = n;
    int n_matches = 0;
    long long tot_weight = 0;
    for (int
        u = 0; u <= n; ++u) st[u] = u, flo[u].clear();
    int w_max = 0;
    for (int u = 1; u <= n; ++u)
        for (int v = 1; v <= n; ++v) {
            flo_from[u][v] = (u == v ? u : 0);
            w_max = max(w_max, g[u][v].w);
        }
    for (int u = 1; u <= n; ++u) lab[u] = w_max;
    while (matching()) ++n_matches;
    for (int u = 1; u <= n; ++u)
        if (match[u] && match[u] < u)
            tot_weight += g[u][match[u]].w;
    return make_pair(tot_weight, n_matches);
}
void add_edge(int ui, int
    vi, int wi) { g[ui][vi].w = g[vi][ui].w = wi; }
void init(int _n) {
    n = _n;
    for (int u = 1; u <= n; ++u)
        for (int v = 1; v <= n; ++v)
            g[u][v] = edge(u, v, 0);
}
};

```

## 4.9 Flow Models

- Maximum/Minimum flow with lower bound / Circulation problem
  - Construct super source  $S$  and sink  $T$ .
  - For each edge  $(x, y, l, u)$ , connect  $x \rightarrow y$  with capacity  $u - l$ .
  - For each vertex  $v$ , denote by  $in(v)$  the difference between the sum of incoming lower bounds and the sum of outgoing lower bounds.
  - If  $in(v) > 0$ , connect  $S \rightarrow v$  with capacity  $in(v)$ , otherwise, connect  $v \rightarrow T$  with capacity  $-in(v)$ .
    - To maximize, connect  $t \rightarrow s$  with capacity  $\infty$  (skip this in circulation problem), and let  $f$  be the maximum flow from  $S$  to  $T$ . If  $f \neq \sum_{v \in V, in(v) > 0} in(v)$ , there's no solution. Otherwise, the maximum flow from  $s$  to  $t$  is the answer.
    - To minimize, let  $f$  be the maximum flow from  $S$  to  $T$ . Connect  $t \rightarrow s$  with capacity  $\infty$  and let the flow from  $S$  to  $T$  be  $f'$ . If  $f + f' \neq \sum_{v \in V, in(v) > 0} in(v)$ , there's no solution. Otherwise,  $f'$  is the answer.
  - The solution of each edge  $e$  is  $l_e + f_e$ , where  $f_e$  corresponds to the flow of edge  $e$  on the graph.
- Construct minimum vertex cover from maximum matching  $M$  on bipartite graph  $(X, Y)$ 
  - Redirect every edge:  $y \rightarrow x$  if  $(x, y) \in M$ ,  $x \rightarrow y$  otherwise.
  - DFS from unmatched vertices in  $X$ .
  - $x \in X$  is chosen iff  $x$  is unvisited.
  - $y \in Y$  is chosen iff  $y$  is visited.
- Minimum cost cyclic flow
  - Construct super source  $S$  and sink  $T$
  - For each edge  $(x, y, c)$ , connect  $x \rightarrow y$  with  $(cost, cap) = (c, 1)$  if  $c > 0$ , otherwise connect  $y \rightarrow x$  with  $(cost, cap) = (-c, 1)$
  - For each edge with  $c < 0$ , sum these cost as  $K$ , then increase  $d(y)$  by 1, decrease  $d(x)$  by 1
  - For each vertex  $v$  with  $d(v) > 0$ , connect  $S \rightarrow v$  with  $(cost, cap) = (0, d(v))$
  - For each vertex  $v$  with  $d(v) < 0$ , connect  $v \rightarrow T$  with  $(cost, cap) = (0, -d(v))$
  - Flow from  $S$  to  $T$ , the answer is the cost of the flow  $C + K$
- Maximum density induced subgraph
  - Binary search on answer, suppose we're checking answer  $T$
  - Construct a max flow model, let  $K$  be the sum of all weights
  - Connect source  $s \rightarrow v, v \in G$  with capacity  $K$
  - For each edge  $(u, v, w)$  in  $G$ , connect  $u \rightarrow v$  and  $v \rightarrow u$  with capacity  $w$
  - For  $v \in G$ , connect it with sink  $v \rightarrow t$  with capacity  $K + 2T - (\sum_{e \in E(v)} w(e)) - 2w(v)$
  - $T$  is a valid answer if the maximum flow  $f < K|V|$
- Minimum weight edge cover
  - For each  $v \in V$  create a copy  $v'$ , and connect  $u' \rightarrow v'$  with weight  $w(u, v)$ .
  - Connect  $v \rightarrow v'$  with weight  $2\mu(v)$ , where  $\mu(v)$  is the cost of the cheapest edge incident to  $v$ .
  - Find the minimum weight perfect matching on  $G'$ .
- Project selection problem
  - If  $p_v > 0$ , create edge  $(s, v)$  with capacity  $p_v$ ; otherwise, create edge  $(v, t)$  with capacity  $-p_v$ .
  - Create edge  $(u, v)$  with capacity  $w$  with  $w$  being the cost of choosing  $u$  without choosing  $v$ .
  - The mincut is equivalent to the maximum profit of a subset of projects.
- Dual of minimum cost maximum flow
  - Capacity  $c_{uv}$ , Flow  $f_{uv}$ , Cost  $w_{uv}$ , Required Flow difference for vertex  $b_u$ .
  - If all  $w_{uv}$  are integers, then optimal solution can happen when all  $p_u$  are integers.

$$\min \sum_{uv} w_{uv} f_{uv} \quad \min \sum_u b_u p_u + \sum_{uv} c_{uv} \max(0, p_v - p_u - w_{uv})$$

$$-f_{uv} \geq -c_{uv} \Leftrightarrow \sum_v f_{vu} - \sum_v f_{uv} = -b_u \quad p_u \geq 0$$

## 5 String

### 5.1 Z-Value

```
vector<int> z(string s){
    vector<int> z(s.size());
    int x = 0, y = 0;
    for(int i = 1; i < s.size(); i++){
        z[i] = max(0LL, min(z[i - x], y - i));
        while(i +
            z[i] < s.size() && s[i + z[i]] == s[z[i]]){
            x = i, y = i + z[i], z[i]++;
        }
    }
    return z;
}
```

### 5.2 KMP

```
vector<int> KMP(string s){
    vector<int> f(s.size());
    for(int i = 1; i < s.size(); i++){
        f[i] = f[i - 1];
        while(f
            [i] && s[i] != s[f[i]]) f[i] = f[f[i] - 1];
        if(s[f[i]] == s[i]) f[i]++;
    }
    return f;
}
```

### 5.3 Manacher

```
vector<int> manacher(string s){
    int n = 2 * s.size() + 1;
    string ss(n, '#');
    for(int
        i = 0; i < n / 2; i++) ss[i * 2 + 1] = s[i];
    swap(s, ss);
    vector<int> f(n);
    int m = 0, len = 0;
    for(int i = 0; i < n; i++){
        f[i]
            = max(0LL, min(f[m + m - i], m + len - i));
        while(i + f[i] < n && i
            - f[i] >= 0 && s[i + f[i]] == s[i - f[i]]){
            m = i, len = f[i], f[i]++;
        }
    }
    return f;
}
```

### 5.4 Suffix Array

```
struct SuffixArray{
    int ch[2][maxn], sa[maxn], cnt[maxn], n;
    string s;
    void init(string _s){
        s = _s, n = s.size();
        Get_SA();
        Get_LCP();
    }
    void Get_SA(){
        int *x = ch[0], *y = ch[1], m = 256;
        for(int i = 0; i < n; i++) cnt[i] = 0;
        for(int i = 0; i < n; i++) cnt[x[i]]++;
        for(int
            i = 1; i < m; i++) cnt[i] += cnt[i - 1];
        for(int i = 0; i < n; i++) sa[--cnt[x[i]]] = i;
        for(int k = 1; k <= 1){
            for(int i = 0; i < m; i++) cnt[i] = 0;
            for(int i = 0; i < n; i++) cnt[x[i]]++;
            for(int i
                = 1; i < m; i++) cnt[i] += cnt[i - 1];
            int p = 0;
            for(int i = n - k; i < n; i++) y[p++] = i;
            for(int i = 0; i < n; i++)
                if(sa[i] >= k) y[p++] = sa[i] - k;
            for(int i = n - 1;
                i >= 0; i--) sa[--cnt[x[y[i]]]] = y[i];
            y[sa[0]] = p = 0;
            for(int i = 1; i < n; i++){
                int a = sa[i], b = sa[i - 1];
                if(a + k < n && b + k < n && x[a
                    ] == x[b] && x[a + k] == x[b + k]){
                    else p++;
                    y[a] = p;
                }
                if(p == n - 1) break;
                swap(x, y);
                m = p + 1;
            }
        }
        int rnk[maxn], lcp[maxn];
        void Get_LCP(){
            for(int i = 0; i < n; i++) rnk[sa[i]] = i;
            int val = 0;
            for(int i = 0; i < n; i++){
                if(val) val--;
                if(!rnk[i]){
                    lcp[0] = val = 0;
                    continue;
                }
                int b = sa[rnk[i] - 1];
                while(b + val < n && i + val
                    < n && s[b + val] == s[i + val]) val++;
            }
        }
    }
}
```

```

        lcp[rnk[i]] = val;
    }
}
} sa;

```

## 5.5 SAIS

```

int sa[N << 1], rk[N], lcp[N];
// string ASCII value need > 0
namespace sfx {
    bool _t[N << 1];
    int _s[N << 1], _c[N << 1], x[N], _p[N], _q[N << 1];
    void pre(int *sa, int *c, int n, int z) {
        fill_n(sa, n, 0), copy_n(c, z, x);
    }
    void induce
        (int *sa, int *c, int *s, bool *t, int n, int z) {
        copy_n(c, z - 1, x + 1);
        for (int i = 0; i < n; ++i)
            if (sa[i] && !t[sa[i] - 1])
                sa[x[s[sa[i] - 1]]++] = sa[i] - 1;
        copy_n(c, z, x);
        for (int i = n - 1; i >= 0; --i)
            if (sa[i] && t[sa[i] - 1])
                sa[--x[s[sa[i] - 1]]] = sa[i] - 1;
    }
    void sais(int *s, int *sa
        , int *p, int *q, bool *t, int *c, int n, int z) {
        bool uniq = t[n - 1] = true;
        int nn = 0,
            nmzx = -1, *nsa = sa + n, *ns = s + n, last = -1;
        fill_n(c, z, 0);
        for (int i = 0; i < n; ++i) uniq &= ++c[s[i]] < 2;
        partial_sum(c, c + z, c);
        if (uniq) {
            for (int i = 0; i < n; ++i) sa[--c[s[i]]] = i;
            return;
        }
        for (int i = n - 2; i >= 0; --i)
            if (s[i] == s[i + 1]) t[i] = t[i + 1];
            else t[i] = s[i] < s[i + 1];
        pre(sa, c, n, z);
        for (int i = 1; i <= n - 1; ++i)
            if (t[i] && !t[i - 1])
                sa[--x[s[i]]] = p[q[i] = nn++] = i;
        induce(sa, c, s, t, n, z);
        for (int i = 0; i < n; ++i)
            if (sa[i] && t[sa[i]] && !t[sa[i] - 1]) {
                bool neq = last < 0 || !equal
                    (s + sa[i], s + p[q[sa[i]] + 1], s + last);
                ns[q[last = sa[i]]] = nmzx += neq;
            }
        sais(nsa,
            nsa, p + nn, q + n, t + n, c + z, nn, nmzx + 1);
        pre(nsa, c, n, z);
        for (int i = nn - 1; i >= 0; --i)
            sa[--x[s[p[nsa[i]]]]] = p[nsa[i]];
        induce(sa, c, s, t, n, z);
    }
    void buildSA(string s) {
        int n = s.length();
        for (int i = 0; i < n; ++i) _s[i] = s[i];
        _s[n] = 0;
        sais(_s, sa, _p, _q, _t, _c, n + 1, 256);
        for (int i = 1; i <= n; ++i) sa[i - 1] = sa[i];
    } // buildLCP()...
}

```

## 5.6 Suffix Automaton

```

struct SuffixAutomaton {
    int len[maxn], link[maxn]; // maxn >= 2 * n - 1
    map<char, int> nxt[maxn];
    int cnt[maxn], distinct[maxn];
    bool is_clone[maxn];
    int first_pos[maxn];
    vector<int> inv_link[maxn]; // suffix references
    int sz = 1, last = 0;
    void init(string s) {
        link[0] = -1;
        for (auto x : s) sa_extend(x);
    }
    void sa_extend(char c) {
        int cur = sz++;
        cnt[cur] = 1;
        len[cur] = len[last] + 1;
        first_pos[cur] = len[cur] - 1;
    }
}

```

```

int p = last;
while(p != -1 && !nxt[p].count(c)){
    nxt[p][c] = cur;
    p = link[p];
}
if(p == -1) link[cur] = 0;
else{
    int q = nxt[p][c];
    if(len[q] == len[p] + 1) link[cur] = q;
    else{
        int clone = sz++;
        is_clone[clone] = true;
        first_pos[clone] = q;
        len[clone] = len[p] + 1;
        nxt[clone] = nxt[q];
        link[clone] = link[q];
        while(p != -1 && nxt[p][c] == q) {
            nxt[p][c] = clone;
            p = link[p];
        }
        link[cur] = link[q] = clone;
    }
}
last = cur;
}
ll getDistinct(int pos){ // number
    of distinct substr. starting at pos(inc. empty)
    if(distinct[pos]) return distinct[pos];
    distinct[pos] = 1;
    for(auto [c, next]
        : nxt[pos]) distinct[pos] += getDistinct(next);
    return cnt[pos];
}
ll numDistinct(){
    return getDistinct
        (0) - 1; // excluding an empty string
}
ll numDistinct2(){
    ll tot = 0;
    for(int i
        = 1; i < sz; i++) tot += len[i] - len[link[i]];
    return tot;
}
void compute_cnt(){ // endpos set size
    vector<vector<int>> v(sz);
    for(int i = 1; i < sz; i++) v[len[i]].pb(i);
    for(int
        i = sz - 1; i > 0; i--) for(auto x : v[i]) {
        cnt[link[x]] += cnt[x];
    }
}
string distinct_kth(ll k){
    // substring
    kth (not distinct) -> compute_cnt()
    numDistinct();
    string s;
    ll cur = 0, tally = 0;
    while(tally < k){
        for(auto [c, next] : nxt[cur]){
            if(tally + distinct[next] >= k){
                tally += 1;
                s += c;
                cur = next;
                break;
            }
            tally += distinct[next];
        }
    }
    return s;
}
//inverse links
void genLink(){
    for(int i = 1; i < sz; i++){
        inv_link[link[i]].pb(i);
    }
}
void get_all_occur(vector<int>& oc, int v){
    if(!is_clone[v]) oc.pb(first_pos[v]);
    for(auto u : inv_link[v]) get_all_occur(oc, u);
}
vector<int> all_occ(string s){ // get all occ of s
    int cur = 0;
    for(auto x : s){
        if(!nxt[cur].count(x)) return {};
        cur = nxt[cur][x];
    }
}

```

```

vector<int> oc;
get_all_occur(oc, cur);
for(auto &x : oc
    ) x += 1 - s.length(); // starting positions
sort(oc.begin(), oc.end());
return oc;
}
int lcs(string t){
    int v = 0, l = 0, ans = 0;
    for(auto x : t){
        while(v && !nxt[v].count(x)){
            v = link[v];
            l = len[v];
        }
        if(nxt[v].count(x)){
            v = nxt[v][x];
            l++;
        }
        ans = max(ans, l);
    }
    return ans;
}
};

```

## 5.7 Palindrome Tree

```

struct EERTREE{
    int sz, tot, last;
    int cnt[maxn], ch[maxn][26],
        len[maxn], fail[maxn], dif[maxn], slink[maxn];
    int g[maxn], dp[maxn];
    char s[maxn];
    int node(int l){
        sz++;
        memset(ch[sz], 0, sizeof(ch[sz]));
        len[sz] = l;
        fail[sz] = cnt[sz] = 0;
        return sz;
    }
    void init(){
        sz = -1;
        last = 0;
        s[tot = 0] = '$';
        node(0);
        node(-1);
        fail[0] = 1;
    }
    int getfail(int x){
        while(s[tot - len[x] - 1] != s[tot]) x = fail[x];
        return x;
    }
    void insert(char c){
        s[++tot] = c;
        int now = getfail(last);
        if(!ch[now][c - 'a']){
            int x = node(len[now] + 2);
            fail[x] = ch[getfail(fail[now])][c - 'a'];
            ch[now][c - 'a'] = x;
            dif[x] = len[x] - len[fail[x]];
            if(dif[x] == dif[fail[x]]){
                slink[x] = slink[fail[x]];
            }
            else slink[x] = fail[x];
        }
        last = ch[now][c - 'a'];
        cnt[last]++;
    }
    int process
        (string s){ // minimum palindrome partitioning
        for(int i = 0; i < s.size(); i++){
            insert(s[i]);
            dp[i] = INF;
            for(int x = last; x > -1; x = slink[x]){
                if(i - len[slink[x]] - dif[x] >=
                    0) g[x] = dp[i - len[slink[x]] - dif[x]];
                if(dif[x] ==
                    dif[fail[x]]) g[x] = min(g[x], g[fail[x]]);
                dp[i] = min(dp[i], g[x] + 1);
            }
        }
        return dp[s.size() - 1];
    }
} pam;

```

## 5.8 AC Automaton

```
namespace AC{
```

```

int ch[maxn][26],
    fail[maxn], idx[maxn], last[maxn], pt[maxn];
int val[maxn], cnt[maxn], tot = 0;
// val[i] = # of times node
// (i) is visited, cnt[i] = # of occ. of str(i)
void init(){
    memset(ch,
        0, sizeof(ch)), memset(fail, 0, sizeof(fail));
    memset(idx,
        0, sizeof(idx)), memset(last, 0, sizeof(last));
    memset(val,
        0, sizeof(val)), memset(cnt, 0, sizeof(cnt));
    tot = 0;
}
void insert(string &s, int id){ // id is 1-based
    int cur = 0;
    for(int i = 0; i < s.size(); i++){
        if(!ch[cur
            ][s[i] - 'a']) ch[cur][s[i] - 'a'] = ++tot;
        cur = ch[cur][s[i] - 'a'];
    }
    if(idx[cur] == 0) idx[cur] = id;
    else pt[id] = idx[cur];
}
void build(){
    queue<int> q;
    for(int i = 0; i < 26; i++){
        if(ch[0][i]) q.push(ch[0][i]);
    }
    while(!q.empty()){
        int u = q.front(); q.pop();
        for(int i = 0; i < 26; i++){
            if(ch[u][i]) {
                fail[ch[u][i]] = ch[fail[u]][i];
                q.push(ch[u][i]);
            }
            else ch[u][i] = ch[fail[u]][i];
            last[ch[u][i]] = idx[fail[ch[u][i]]]
                ? fail[ch[u][i]] : last[fail[ch[u][i]]];
        }
    }
}
int qry(string &s){
    int u = 0, ret = 0;
    for(int i = 0; i < s.size(); i++){
        u = ch[u][s[i] - 'a'];
        for(int j = u; j; j = last[j]) val[j] ++;
    }
    for(int i = 0; i <= tot; i++){
        if(idx[i])
            ret = max(ret, val[i]), cnt[idx[i]] = val[i];
    }
    return ret;
}
};

```

## 5.9 Lyndon Factorization

```

vector<string> duval(string s){
    int n = s.length(), i = 0;
    vector<string> fac;
    while(i < n){
        int j = i + 1, k = i; // i <= k < j
        while(j < n && s[k] <= s[j]){
            if(s[k] < s[j]) k = i;
            else k++;
        }
        j++;
        while(i <= k){
            fac.pb(s.substr(i, j - k));
            i += j - k;
        }
    }
    return fac;
}

```

## 6 Math

### 6.1 Miller Rabin

```

using u64 = uint64_t;
using u128 = __uint128_t;

u64 fpow(u64 a, u64 b, u64 n){
    u64 ret = 1;
    while(b > 0){
        if(b & 1) ret = (u128)ret * a % n;
    }
}

```



```

    a = (u128)a * a % n;
    b >= 1;
}
return ret;
}
bool check_composite(u64 n, u64 a, u64 d, int s){
    u64 x = fpow(a, d, n);
    if(x == 1 || x == n - 1) return false;
    for(int r = 1; r < s; r++){
        x = (u128)x * x % n;
        if(x == n - 1) return false;
    }
    return true;
}
bool MillerRabin(u64 n){
    if(n < 2) return false;
    int s = 0;
    u64 d = n - 1;
    while(!(d & 1)){
        d >= 1;
        s++;
    }
    for(auto a : {2, 3, 5, 7, 11, 13, 17,
        19, 23, 29, 31, 37}){ // sufficient for n < 2^64
        if(n == a) return true;
        if(check_composite(n, a, d, s)) return false;
    }
    return true;
}

```

## 6.2 Pollard Rho

```

ll f(ll t, ll c, ll n){
    return (t * t + c) % n;
}

ll Pollard_Rho(ll x){
    ll t = 0;
    ll c = rand() % (x - 1) + 1;
    ll s = t;
    ll val = 1;
    for(int goal = 1; goal <= 1, s = t, val = 1){
        for(int step = 1; step <= goal; step++){
            t = f(t, c, x);
            val = val * abs(t - s) % x;
            if(!val) return x;
            if(step % 127 == 0){
                ll d = __gcd(val, x);
                if(d > 1) return d;
            }
        }
        ll d = __gcd(val, x);
        if(d > 1) return d;
    }
}

```

## 6.3 EXT GCD

```

ll extgcd(ll a, ll b, ll &x, ll &y){
    if(b == 0){
        x = 1, y = 0;
        return a;
    }
    int res = extgcd(b, a % b, y, x);
    y -= (a / b) * x;
    return res;
}

```

## 6.4 Chinese Remainder Theorem

```

ll CRT(vector<ll> p, vector<ll> a){
    ll n = p.size(), prod = 1, ret = 0;
    for(int i = 0; i < n; i++) prod *= p[i];
    for(int i = 0; i < n; i++){
        ll m = (prod / p[i]);
        ll x, y;
        extgcd(m, p[i], x, y);
        ret = ((ret + a[i] * m * x) % prod + prod) % prod;
    }
    return ret;
}

```

## 6.5 Powerful Number Sieve

```

void linearsieve(){
    phi[1] = 1;
    for(int i = 2; i < maxn; i++){
        if(!lp[i]) pr.pb(i), lp[i] = i, phi[i] = i - 1;
    }
}

```

```

for(auto x : pr){
    if(i * x >= maxn) break;
    lp[i * x] = x;
    if(lp[i] == x){
        phi[i * x] = phi[i] * x;
        break;
    }
    phi[i * x] = phi[i] * (x - 1);
}
}
for(int i = 1; i < maxn; i++){
    sum[i] = (sum[i - 1] + i * phi[i]) % N;
}

int s2(int n){
    static const int inv6 = inv(6);
    n %= N;
    return n * (n + 1) % N * (2 * n + 1) % N * inv6 % N;
}

int G(int n){
    static const int inv2 = inv(2);
    if(n < maxn) return sum[n];
    if(mp_G.count(n)) return mp_G[n];
    int ans = s2(n);
    for(int i = 2, j; i <= n; i = j + 1){
        j = n / (n / i);
        (ans -= (i + j) % N * (j - i + 1) % N * inv2 % N * G(n / i) % N - N) %= N;
    }
    return mp_G[n] = ans;
}

void dfs(int d, int hd, int p){ // dfs 出所有 PN
    (ans += hd * G(n / d)) %= N;
    for(int i = p; i < pr.size(); i++){
        if(d > n / pr[i] / pr[i]) break;
        int c = 2;
        for(int x = d * pr[i] * pr[i]; x <= n; x *= pr[i], c++){
            if(!vis[i][c]){
                int f = fpow(pr[i], c);
                f = f * (f - 1) % N;
                int g = pr[i] * (pr[i] - 1) % N;
                int t = pr[i] * pr[i] % N;
                for(int j = 1; j <= c; j++){
                    (f -= g * h[i][c - j] % N - N) %= N;
                    (g *= t) %= N;
                }
                h[i][c] = f;
                vis[i][c] = true;
            }
            if(h[i][c]) dfs(x, hd * h[i][c] % N, i + 1);
        }
    }
}

```

```

linearsieve();
for(int i = 0; i < pr.size(); i++) h[i][0] = 1;
dfs(1, 1, 0);

```

## 6.6 Min25 Sieve

```

template <typename U, typename V> struct min25 {
    lld n; int sq;
    vector<U> Ss, Sl, Spre; vector<V> Rs, Rl;
    Sieve sv; vector<lld> quo;
    U &S(lld d) { return d < sq ? Ss[d] : Sl[n / d]; }
    V &R(lld d) { return d < sq ? Rs[d] : Rl[n / d]; }
    min25(lld n_) : n(n_), sq((int)sqrt(n) + 1),
        Ss(sq), Sl(sq), Spre(sq), Rs(sq), Rl(sq), sv(sq) {
        for (lld i = 1, Q; i <= n; i = n / Q + 1)
            quo.push_back(Q = n / i);
    }
    U F_prime(auto &&f, auto &&F) {
        for (lld p : sv.primes) Spre[p] = f(p);
        for (
            int i = 1; i < sq; i++) Spre[i] += Spre[i - 1];
        for (lld i : quo) S(i) = F(i) - F(1);
        for (lld p : sv.primes)
            for (lld i : quo) {
                if (p * p > i) break;
                S(i) -= f(p) * (S(i / p) - Spre[p - 1]);
            }
        return S(n);
    } // F_prime: \sum_{p is prime, p <= n} f(p)
    V F_comp(auto &&g) {

```

```

for (lld i : quo) R(i) = V(S(i));
for (lld p : sv.primes | views::reverse)
    for (lld i : quo) {
        if (p * p > i) break;
        lld prod = p;
        for (
            int c = 1; prod * p <= i; ++c, prod *= p) {
            R(i) += g(p, c) * (R(i / prod) - V(Spre[p]));
            R(i) += g(p, c + 1);
        }
    }
return R(n);
} // F_comp: \sum_{2 <= i <= n} g(i)
}; // O(n^{3/4} / log n)
/* U, V 都是環，記 h: U -> V 代表 U 轉變成 V 的函數。
要求 h(x + y) = h(x) + h(y); f: lld -> U 是完全積性；
g 是積性函數且 h(f(p)) = g(p) 對於質數 p。
呼叫 F_comp 前需要呼叫 F_prime 得到 S(i)。
S(i), R(i) 是 F_prime 和 F_comp 在 n/k 點的值。
F(i) = \sum_{j <= i} f(j) 和 f(i) 需要快速求值。
g(p, c) := g(pow(p, c)) 需要快速求值。
例如若 g(p) 是度數 d 的多項式則可以構造 f(p) 是維護
pow(p, c) 的 (d+1)-tuple */

```

## 6.7 Floor Sum

```

//f(n, a, b, c) = sum_{0<=i<=n}{(ai + b)/c},
//g(n, a, b, c) = sum_{0<=i<=n}{i(ai + b)/c},
//h(n, a, b, c) = sum_{0<=i<=n}{((ai + b)/c)^2},
const int N = 998244353;
const int i2 = (N + 1) / 2, i6 = 166374059;
struct info{
    ll f, g, h;
    info(){f = g = h = 0;}
};
info calc(ll n, ll a, ll b, ll c){
    ll ac = a / c, bc = b / c,
        m = (a * n + b) / c, n1 = n + 1, n21 = n * 2 + 1;
    info d;
    if(a == 0){
        d.f = bc * n1 % N;
        d.g = bc * n % N * n1 % N * i2 % N;
        d.h = bc * bc % N * n1 % N;
        return d;
    }
    if(a >= c || b >= c){
        d.f = n * n1 % N * i2 % N * ac % N + bc * n1 % N;
        d.g = ac * n % N * n1 % N * n21 % N * i6 % N + bc * n % N * i2 % N;
        d.h = ac * ac % N * n % N * n1 % N * n21 % N * i6 % N + bc * bc % N * n1 % N + ac * bc % N * n % N * n1 % N;
    }
    info e = calc(n, a % c, b % c, c);
    d.h += e.h + 2 * bc * e.f % N + 2 * ac % N * e.g % N;
    d.g += e.g, d.f += e.f;
    d.f %= N, d.g %= N, d.h %= N;
    return d;
}
info e = calc(m - 1, c, c - b - 1, a);
d.f = (n * m % N - e.f + N) % N;
d.g = m * n % N * n1 % N - e.h - e.f; d.g = (d.g * i2 % N + N) % N;
d.h = n * m % N * (m + 1) % N - 2 * e.g - 2 * e.f - d.f; d.h = (d.h % N + N) % N;
return d;
}

```

## 6.8 Euclidean

$$m = \lfloor \frac{an+b}{c} \rfloor$$

$$\begin{aligned}
 g(a, b, c, n) &= \sum_{i=0}^n i \lfloor \frac{ai+b}{c} \rfloor \\
 &= \begin{cases} \lfloor \frac{a}{c} \rfloor^2 \cdot \frac{n(n+1)(2n+1)}{6} + \lfloor \frac{b}{c} \rfloor \cdot \frac{n(n+1)}{2} + \lfloor \frac{a}{c} \rfloor \cdot \lfloor \frac{b}{c} \rfloor \cdot n(n+1) + h(a \bmod c, b \bmod c, c, n) & a \geq c \vee b \geq c \\ 0, & n < 0 \vee a = 0 \\ \frac{1}{2} \cdot (n(n+1)m - f(c, c-b-1, a, m-1) - h(c, c-b-1, a, m-1)), & \text{otherwise} \end{cases}
 \end{aligned}$$

$$\begin{aligned}
 h(a, b, c, n) &= \sum_{i=0}^n \lfloor \frac{ai+b}{c} \rfloor^2 \\
 &= \begin{cases} \lfloor \frac{a}{c} \rfloor^2 \cdot \frac{n(n+1)(2n+1)}{6} + \lfloor \frac{b}{c} \rfloor^2 \cdot (n+1) + \lfloor \frac{a}{c} \rfloor \cdot \lfloor \frac{b}{c} \rfloor \cdot n(n+1) + h(a \bmod c, b \bmod c, c, n) \\ + 2 \lfloor \frac{a}{c} \rfloor \cdot g(a \bmod c, b \bmod c, c, n) + 2 \lfloor \frac{b}{c} \rfloor \cdot f(a \bmod c, b \bmod c, c, n), & a \geq c \vee b \geq c \\ 0, & n < 0 \vee a = 0 \\ nm(m+1) - 2g(c, c-b-1, a, m-1) - 2f(c, c-b-1, a, m-1) - f(a, b, c, n), & \text{otherwise} \end{cases}
 \end{aligned}$$

## 6.9 Big Number

```

template<typename T>
inline string to_string(const T& x){
    stringstream ss;
    return ss<<x, ss.str();
}
struct bigN:vector<ll>{
    const static int base=1000000000,width=log10(base);
    bool negative;
    bigN(const_iterator a,const_iterator b):vector<ll>(a,b){}
    bigN(string s){
        if(s.empty())return;
        if(s[0]=='-')negative=1,s=s.substr(1);
        else negative=0;
        for(int i=int(s.size())-1;i>=0;i-=width){
            ll t=0;
            for(int j=max(0,i-width+1);j<=i;++j)
                t=t*10+s[j]-'0';
            push_back(t);
        }
        trim();
    }
    template<typename T>
    bigN(const T &x):bigN(to_string(x)){}
    bigN():negative(0){}
    void trim(){
        while(size()&&!back())pop_back();
        if(empty())negative=0;
    }
    void carry(int _base=base){
        for(size_t i=0;i<size();++i){
            if(at(i)>=_base&&at(i)<_base)continue;
            if(i+1==size())push_back(0);
            int r=at(i)%_base;
            if(r<0)r+=_base;
            at(i+1)+=(at(i)-r)/_base,at(i)=r;
        }
    }
    int abscmp(const bigN &b)const{
        if(size()>b.size())return 1;
        if(size()<b.size())return -1;
        for(int i=int(size())-1;i>=0;--i){
            if(at(i)>b[i])return 1;
            if(at(i)<b[i])return -1;
        }
        return 0;
    }
    int cmp(const bigN &b)const{
        if(negative!=b.negative)return negative?-1:1;
        return negative?-abscmp(b):abscmp(b);
    }
    bool operator<(const bigN&b)const{return cmp(b)<0;}
    bool operator>(const bigN&b)const{return cmp(b)>0;}
    bool operator<=(const bigN&b)const{return cmp(b)<=0;}
    bool operator>=(const bigN&b)const{return cmp(b)>=0;}
    bool operator==(const bigN&b)const{return !cmp(b);}
    bool operator!=(const bigN&b)const{return cmp(b)!=0;}
    bigN abs()const{
        bigN res=*this;
        return res.negative=0, res;
    }
    bigN operator-()const{
        bigN res=*this;
        return res.negative=!negative, res.trim(), res;
    }
    bigN operator+(const bigN &b)const{
        if(negative)return -(*this)+(-b);
        if(b.negative)return *this+(-b);
        bigN res=*this;
        if(b.size()>size())res.resize(b.size());
        for(size_t i=0;i<b.size();++i)res[i]+=b[i];
    }
}

```

```

    return res.carry(),res.trim(),res;
}
bigN operator-(const bigN &b)const{
    if(negative)return -(-(*this)-(-b));
    if(b.negative)return *this+(-b);
    if(abscmp(b)<0)return -(b-(*this));
    bigN res=*this;
    if(b.size()>size())res.resize(b.size());
    for(size_t i=0;i<b.size();++i)res[i]-=b[i];
    return res.carry(),res.trim(),res;
}
bigN operator*(const bigN &b)const{
    bigN res;
    res.negative=negative!=b.negative;
    res.resize(size()+b.size());
    for(size_t i=0;i<size();++i)
        for(size_t j=0;j<b.size();++j)
            if((res[i+j]+at(i)*b[j])>=base){
                res[i+j+1]+=res[i+j]/base;
                res[i+j]%=base;
            }//%k%icarry· /· ,i
    return res.trim(),res;
}
bigN operator/(const bigN &b)const{
    int norm=base/(b.back()+1);
    bigN x=abs()*norm;
    bigN y=b.abs()*norm;
    bigN q,r;
    q.resize(x.size());
    for(int i=int(x.size())-1;i>=0;--i){
        r=r*base+x[i];
        int s1=r.size()<=y.size()?0:r[y.size()];
        int s2=r.size()<y.size()?0:r[y.size()-1];
        int d=(ll(base)*s1+s2)/y.back();
        r=r-y*d;
        while(r.negative)r=r+y,--d;
        q[i]=d;
    }
    q.negative=negative!=b.negative;
    return q.trim(),q;
}
bigN operator%(const bigN &b)const{
    return *this-(*this/b)*b;
}
friend istream& operator>>(istream &ss, bigN &b){
    string s;
    return ss>>s, b=s, ss;
}
friend
    ostream& operator<<(ostream &ss, const bigN &b){
        if(b.negative)ss<<'-';
        ss<<(b.empty()?0:b.back());
        for(int i=int(b.size())-2;i>=0;--i)
            ss<<setw(width)<<setfill('0')<<b[i];
        return ss;
    }
template<typename T>
operator T(){
    stringstream ss;
    ss<<*this;
    T res;
    return ss>>res,res;
}
};

```

## 6.10 Determinant

```

struct Matrix {
    int n, m;
    ll M[MAXN][MAXN];
    int row_swap(int i, int j) {
        if (i == j) return 0;
        for (int k = 0; k < m; ++k)
            swap(M[i][k], M[j][k]);
        return 1;
    }
    ll det() { // return the number of swaps
        int rt = 0;
        for (int i = 0; i < n; ++i) {
            int piv = i;
            while (piv < n && !M[piv][i]) ++piv;
            if (piv == n) continue;
            rt += row_swap(i, piv);
            for (int j = i + 1; j < n; ++j) {
                while (M[j][i]) {
                    int tmp = P - M[i][i] / M[j][i];
                    for (int k = i; k < m; ++k)

```

```

                        M[i][k] = (M[j][k] * tmp + M[i][k]) % P;
                        rt += row_swap(i, j);
                    }
                }
            }
            rt = (rt & 1) ? P - 1 : 1;
            for (int i = 0; i < n; ++i)
                rt = rt * M[i][i] % P;
            return rt;
        } // round(rt) if using double to cal. int. det
    };
};

```

## 6.11 Discrete Log

```

int DiscreteLog(int s, int x, int y, int m) {
    constexpr int kStep = 32000;
    unordered_map<int, int> p;
    int b = 1;
    for (int i = 0; i < kStep; ++i) {
        p[y] = i;
        y = 1LL * y * x % m;
        b = 1LL * b * x % m;
    }
    for (int i = 0; i < m + 10; i += kStep) {
        s = 1LL * s * b % m;
        if (p.find(s) != p.end()) return i + kStep - p[s];
    }
    return -1;
}
int DiscreteLog(int x, int y, int m) {
    if (m == 1) return 0;
    int s = 1;
    for (int i = 0; i < 100; ++i) {
        if (s == y) return i;
        s = 1LL * s * x % m;
    }
    if (s == y) return 100;
    int p = 100 + DiscreteLog(s, x, y, m);
    if (fpow(x, p, m) != y) return -1;
    return p;
}

```

## 6.12 Berlekamp Massey

```

// need add, sub, mul
vector<int> BerlekampMassey(vector<int> a) {
    // find min |c|
    // such that a_n = sum c_j * a_{n-j-1}, 0-based
    // 0(N^2), if |c| = k, |a| >= 2k sure correct
    auto f = [&](vector<int> v, ll c) {
        for (int &x : v) x = mul(x, c);
        return v;
    };
    vector<int> c, best;
    int pos = 0, n = (int)a.size();
    for (int i = 0; i < n; ++i) {
        int error = a[i];
        for (int j = 0; j < (int)c.size(); ++j)
            error = sub(error, mul(c[j], a[i-1-j]));
        if (error == 0) continue;
        int inv = Pow(error, mod - 2);
        if (c.empty()) {
            c.resize(i+1), pos = i, best.pb(inv);
        } else {
            vector<int> fix = f(best, error);
            fix.insert(fix.begin(), i-pos-1, 0);
            if (fix.size() >= c.size()) {
                best = f(c, sub(0, inv));
                best.insert(best.begin(), inv);
                pos = i, c.resize(fix.size());
            }
            for (int j = 0; j < (int)fix.size(); ++j)
                c[j] = add(c[j], fix[j]);
        }
    }
    return c;
}

```

## 6.13 Gaussian Elimination

```

using VI = vector<int>; // be careful if A.empty()
using VVI = vector<VI>; // ensure that 0 <= x < mod
pair<VI, VVI> gauss(VVI A, VI b) { // solve Ax=b
    const int N = (int)A.size(), M = (int)A[0].size();
    vector<int> depv, free(M, true); int rk = 0;
    for (int i = 0; i < M; i++) {

```

```

int p = -1;
for (int j = rk; j < N; j++)
    if (p == -1 || abs(A[j][i]) > abs(A[p][i]))
        p = j;
if (p == -1 || A[p][i] == 0) continue;
swap(A[p], A[rk]); swap(b[p], b[rk]);
const int inv = modinv(A[rk][i]);
for (int &x : A[rk]) x = mul(x, inv);
b[rk] = mul(b[rk], inv);
for (int j = 0; j < N; j++) if (j != rk) {
    int z = A[j][i];
    for (int k = 0; k < M; k++)
        A[j][k] = sub(A[j][k], mul(z, A[rk][k]));
    b[j] = sub(b[j], mul(z, b[rk]));
}
depv.push_back(i); free[i] = false; ++rk;
}
for (int i = rk; i < N; i++)
    if (b[i] != 0) return {{}, {}}; // not consistent
VI x(M); VVI h;
for (int i = 0; i < rk; i++) x[depv[i]] = b[i];
for (int i = 0; i < M; i++) if (free[i]) {
    h.emplace_back(M); h.back()[i] = 1;
    for (int j = 0; j < rk; j++)
        h.back()[depv[j]] = sub(0, A[j][i]);
}
return {x, h}; // solution = x + span(h[i])
}

```

## 6.14 Golden Search

```

llf gss(llf a, llf b, auto &&f) {
    llf r = (sqrt(5)-1)/2, eps = 1e-7;
    llf x1 = b - r*(b-a), x2 = a + r*(b-a);
    llf f1 = f(x1), f2 = f(x2);
    while (b-a > eps)
        if (f1 < f2) { //change to > to find maximum
            b = x2; x2 = x1; f2 = f1;
            x1 = b - r*(b-a); f1 = f(x1);
        } else {
            a = x1; x1 = x2; f1 = f2;
            x2 = a + r*(b-a); f2 = f(x2);
        }
    return a;
}

```

## 6.15 Pi Count

```

struct S { int rough; lld large; int id; };
lld PrimeCount(lld n) { // n ~ 10^13 => < 1s
    if (n <= 1) return 0;
    const int v = static_cast<int>(sqrtl(n)); int pc = 0;
    vector<int> smalls(v+1), skip(v+1); vector<S> z;
    for (int i = 2; i <= v; ++i) smalls[i] = (i+1)/2;
    for (int i : views::iota(0, (v+1)/2))
        z.emplace_back(2*i+1, (n/(2*i+1)+1)/2, i);
    for (int p = 3; p <= v; ++p)
        if (smalls[p] > smalls[p-1]) {
            const int q = p * p; ++pc;
            if (1LL * q * q > n) break;
            skip[p] = 1;
            for (int i = q; i <= v; i += 2 * p) skip[i] = 1;
            int ns = 0;
            for (auto e : z) if (!skip[e.rough]) {
                lld d = 1LL * e.rough * p;
                e.large += pc - (d <=
                    v ? z[smalls[d] - pc].large : smalls[n/d]);
                e.id = ns; z[ns++] = e;
            }
            z.resize(ns);
            for (int j = v/p; j >= p; --j) {
                int c
                    = smalls[j] - pc, e = min(j * p + p, v+1);
                for (int i = j * p; i < e; ++i) smalls[i] -= c;
            }
        }
    lld ans = z[0].large; z.erase(z.begin());
    for (auto &[rough, large, k] : z) {
        const lld m = n / rough; --k;
        ans -= large - (pc + k);
        for (auto [p, _, l] : z)
            if (l >= k || p * p > m) break;
            else ans += smalls[m/p] - (pc + l);
    }
    return ans;
}
// test @ yosupo library checker w/ n=1e11, 68ms

```

## 6.16 Quadratic Residue

```

int get_root(int n, int P) { // ensure 0 <= n < P
    if (P == 2 || n == 0) return n;
    auto check = [&](lld x) {
        return modpow(int(x), (P-1)/2, P);
    };
    if (check(n) != 1) return -1;
    mt19937 rnd(7122); lld z = 1, w;
    while (check(w = (z * z - n + P) % P) != P-1)
        z = rnd() % P;
    const auto M = [P, w](auto &u, auto &v) {
        auto [a, b] = u; auto [c, d] = v;
        return make_pair((a * c + b * d % P * w) % P,
            (a * d + b * c) % P);
    };
    pair<lld, lld> r(1, 0), e(z, 1);
    for (int q = (P+1)/2; q; q >= 1, e = M(e, e))
        if (q & 1) r = M(r, e);
    return
        int(r.first); // sqrt(n) mod P where P is prime
}

```

## 6.17 Simplex

```

namespace simplex {
    // maximize c^T x under Ax <= B and x >= 0
    // return VD(n, -inf) if the solution doesn't exist
    // return VD(n, +inf) if the solution is unbounded
    using VD = vector<llf>;
    using VVD = vector<vector<llf>>;
    const llf eps = 1e-9, inf = 1e+9;
    int n, m; VVD d; vector<int> p, q;
    void pivot(int r, int s) {
        llf inv = 1.0 / d[r][s];
        for (int i = 0; i < m+2; ++i)
            for (int j = 0; j < n+2; ++j)
                if (i != r && j != s)
                    d[i][j] -= d[r][j] * d[i][s] * inv;
        for (int i=0; i<m+2; ++i) if (i != r) d[i][s] *= -inv;
        for (int j=0; j<n+2; ++j) if (j != s) d[r][j] *= +inv;
        d[r][s] = inv; swap(p[r], q[s]);
    }
    bool phase(int z) {
        int x = m+2;
        while (true) {
            int s = -1;
            for (int i = 0; i <= n; ++i) {
                if (!z && q[i] == -1) continue;
                if (s == -1 || d[x][i] < d[x][s]) s = i;
            }
            if (s == -1 || d[x][s] > -eps) return true;
            int r = -1;
            for (int i = 0; i < m; ++i) {
                if (d[i][s] < eps) continue;
                if (r == -1 ||
                    d[i][n+1]/d[i][s] < d[r][n+1]/d[r][s]) r = i;
            }
            if (r == -1) return false;
            pivot(r, s);
        }
    }
    VD solve(const VVD &a, const VD &b, const VD &c) {
        m = (int)b.size(), n = (int)c.size();
        d = VVD(m+2, VD(n+2));
        for (int i = 0; i < m; ++i)
            for (int j = 0; j < n; ++j) d[i][j] = a[i][j];
        p.resize(m), q.resize(n+1);
        for (int i = 0; i < m; ++i)
            p[i] = n+i, d[i][n] = -1, d[i][n+1] = b[i];
        for (int i = 0; i < n; ++i) q[i] = i, d[m][i] = -c[i];
        q[n] = -1, d[m+1][n] = 1;
        int r = 0;
        for (int i = 1; i < m; ++i)
            if (d[i][n+1] < d[r][n+1]) r = i;
        if (d[r][n+1] < -eps) {
            pivot(r, n);
            if (!phase(1) || d[m+1][n+1] < -eps)
                return VD(n, -inf);
            for (int i = 0; i < m; ++i) if (p[i] == -1) {
                int s = min_element(d[i].begin(), d[i].end() - 1)
                    - d[i].begin();
                pivot(i, s);
            }
        }
        if (!phase(0)) return VD(n, inf);
        VD x(n);
        for (int i = 0; i < m; ++i)

```

```

    if (p[i] < n) x[p[i]] = d[i][n + 1];
    return x;
} // use double instead of long double if possible

```

## 6.18 Simplex Construction

Standard form: maximize  $\sum_{1 \leq i \leq n} c_i x_i$  such that  $\sum_{1 \leq i \leq n} A_{ji} x_i \leq b_j$  for all  $1 \leq j \leq m$  and  $x_i \geq 0$  for all  $1 \leq i \leq n$ .

1. In case of minimization, let  $c'_i = -c_i$
2.  $\sum_{1 \leq i \leq n} A_{ji} x_i \geq b_j \rightarrow \sum_{1 \leq i \leq n} -A_{ji} x_i \leq -b_j$
3.  $\sum_{1 \leq i \leq n} A_{ji} x_i = b_j \rightarrow$  add  $\leq$  and  $\geq$ .
4. If  $x_i$  has no lower bound, replace  $x_i$  with  $x_i - x'_i$

## 6.19 Theorem

- Kirchhoff's Theorem  
Denote  $L$  be a  $n \times n$  matrix as the Laplacian matrix of graph  $G$ , where  $L_{ii} = d(i)$ ,  $L_{ij} = -c$  where  $c$  is the number of edge  $(i, j)$  in  $G$ .

- The number of undirected spanning in  $G$  is  $|\det(\tilde{L}_{11})|$ .
- The number of directed spanning tree rooted at  $r$  in  $G$  is  $|\det(\tilde{L}_{rr})|$ .

- Tutte's Matrix

Let  $D$  be a  $n \times n$  matrix, where  $d_{ij} = x_{ij}$  ( $x_{ij}$  is chosen uniformly at random) if  $i < j$  and  $(i, j) \in E$ , otherwise  $d_{ij} = -d_{ji}$ .  $\frac{\text{rank}(D)}{2}$  is the maximum matching on  $G$ .

- Cayley's Formula

- Given a degree sequence  $d_1, d_2, \dots, d_n$  for each *labeled* vertices, there are

$$\frac{(n-2)!}{(d_1-1)!(d_2-1)!\dots(d_n-1)!}$$

spanning trees.

- Let  $T_{n,k}$  be the number of *labeled* forests on  $n$  vertices with  $k$  components, such that vertex  $1, 2, \dots, k$  belong to different components. Then  $T_{n,k} = kn^{n-k-1}$ .

- Erdős–Gallai Theorem

A sequence of non-negative integers  $d_1 \geq d_2 \geq \dots \geq d_n$  can be represented as the degree sequence of a finite simple graph on  $n$  vertices if and only if  $d_1 + d_2 + \dots + d_n$  is even and

$$\sum_{i=1}^k d_i \leq k(k-1) + \sum_{i=k+1}^n \min(d_i, k)$$

holds for all  $1 \leq k \leq n$ .

- Burnside's Lemma

Let  $X$  be a set and  $G$  be a group that acts on  $X$ . For  $g \in G$ , denote by  $X^g$  the elements fixed by  $g$ :

$$X^g = \{x \in X \mid gx = x\}$$

Then

$$|X/G| = \frac{1}{|G|} \sum_{g \in G} |X^g|.$$

- Gale–Ryser theorem

A pair of sequences of nonnegative integers  $a_1 \geq \dots \geq a_n$  and  $b_1, \dots, b_n$

is bigraphic if and only if  $\sum_{i=1}^n a_i = \sum_{i=1}^n b_i$  and  $\sum_{i=1}^k a_i \leq \sum_{i=1}^n \min(b_i, k)$  holds for every  $1 \leq k \leq n$ . Sequences  $a$  and  $b$  called bigraphic if there is a labeled simple bipartite graph such that  $a$  and  $b$  is the degree sequence of this bipartite graph.

- Fulkerson–Chen–Anstee theorem

A sequence  $(a_1, b_1), \dots, (a_n, b_n)$  of nonnegative integer pairs

with  $a_1 \geq \dots \geq a_n$  is digraphic if and only if  $\sum_{i=1}^n a_i = \sum_{i=1}^n b_i$  and

$$\sum_{i=1}^k a_i \leq \sum_{i=1}^k \min(b_i, k-1) + \sum_{i=k+1}^n \min(b_i, k) \text{ holds for every } 1 \leq k \leq n.$$

Sequences  $a$  and  $b$  called digraphic if there is a labeled simple directed graph such that each vertex  $v_i$  has indegree  $a_i$  and outdegree  $b_i$ .

- Pick's theorem

For simple polygon, when points are all integer, we have  $A = \#\{\text{lattice points in the interior}\} + \frac{\#\{\text{lattice points on the boundary}\}}{2} - 1$

- Möbius inversion formula

$$\begin{aligned} - f(n) &= \sum_{d|n} g(d) \Leftrightarrow g(n) = \sum_{d|n} \mu\left(\frac{n}{d}\right) f\left(\frac{n}{d}\right) \\ - f(n) &= \sum_{n|d} g(d) \Leftrightarrow g(n) = \sum_{n|d} \mu\left(\frac{d}{n}\right) f(d) \end{aligned}$$

## 7 Polynomial

### 7.1 NTT

```

const int N = 998244353, g = 3;

void NTT(vector<ll> &a, bool invert = 0){ // iterative version
    int n = a.size();
    int lg_n = __lg(n);
    for(int i = 1, j = 0; i < n; i++){
        int bit = n >> 1;
        for(; j & bit; bit >>= 1) j ^= bit;
        j ^= bit;
        if(i < j) swap(a[i], a[j]);
    }
    for(int len = 2; len <= n; len <= 1){
        ll wn = fpow(g, (N - 1) / len);
        if(invert) wn = inv(wn);
        for(int i = 0; i < n; i += len){
            ll w = 1;
            for(int j = 0; j < len / 2; j++){
                ll u = a[i + j], v = a[i + j + len / 2] * w % N;
                a[i + j] = (u + v) % N;
                a[i + j + len / 2] = (u - v + N) % N;
                (w *= wn) %= N;
            }
        }
        ll n_1 = inv(n);
        if(invert) for(auto &x : a) (x *= n_1) %= N;
    }
}

```

### 7.2 FFT

```

using cd = complex<double>;
const double PI = acos(-1);

void FFT(vector<cd> &a, bool invert = 0){ // iterative version
    int n = a.size();
    int lg_n = __lg(n);
    for(int i = 1, j = 0; i < n; i++){ //bit-reversal permutation
        int bit = n >> 1;
        for(; j & bit; bit >>= 1) j ^= bit;
        j ^= bit;
        if(i < j) swap(a[i], a[j]);
    }
    for(int len = 2; len <= n; len <= 1){
        double ang = 2 * PI / len * (invert? -1 : 1);
        cd wlen(cos(ang), sin(ang));
        for(int i = 0; i < n; i += len){
            cd w(1);
            for(int j = 0; j < len / 2; j++){
                cd u = a[i + j], v = a[i + j + len / 2] * w;
                a[i + j] = u + v;
                a[i + j + len / 2] = u - v;
                w *= wlen;
            }
        }
        if(invert) for(auto &x : a) x /= n;
    }
}

```

### 7.3 Primes

Prime	Root	Prime	Root
7681	17	167772161	3
12289	11	104857601	3
40961	3	985661441	3
65537	3	998244353	3
786433	10	1107296257	10
5767169	3	2013265921	31
7340033	3	2810183681	11
23068673	3	2885681153	3
469762049	3	605028353	3
2061584302081	7	1945555039024054273	5
2748779069441	3	9223372036737335297	3

### 7.4 Fast Walsh Transform

```

void fwt(vector<int> &a, bool inv){
    int n = 1;
    while(n < a.size()) n *= 2;
    a.resize(n);
    for(int len = 1; 2 * len <= n; len <= 1){
        for(int i = 0; i < n; i += 2 * len){

```

```

    for(int j = 0; j < len; j++){
        int &u =
            a[i + j], &v = a[i + j + len]; tie(u, v) =
            // inv ? pll(u - v, v) : pll(u + v, v); // and
            // inv ? pll(u, v - u) : pll(u, u + v); // or
            pll(u + v, u - v); // xor
    }
}
if(inv) for(auto &x : a) x /= n; // xor only
}

```

## 7.5 Fast Linear Recursion

```

int FastLinearRecursion
(vector<int> a, vector<int> c, ll k) {
    // a_n = sigma c_j * a_{n-j-1}, 0-based
    // O(NlogNlogK), |a| = |c|
    int n = a.size();
    if (k < n) return a[k];
    vector<int> base(n + 1, 1);
    for (int i = 0; i < n; ++i)
        base[i] = sub(0, c[n - i - 1]);
    vector<int> poly(n);
    (n == 1 ? poly[0] = c[n - 1] : poly[1] = 1);
    auto calc = [&](vector<int> p1, vector<int> p2) {
        // O(n^2) brute force or O(nlogn) NTT
        return Divide(Mul(p1, p2), base).second;
    };
    vector<int> res(n, 0); res[0] = 1;
    for (; k >= 1, poly = calc(poly, poly)) {
        if (k & 1) res = calc(res, poly);
    }
    int ans = 0;
    for (int i = 0; i < n; ++i)
        ans = add(ans, mul(res[i], a[i]));
    return ans;
}

```

## 7.6 Operations

```

int get_root(int n, int P) { // ensure 0 <= n < P
    if (P == 2 || n == 0) return n;
    auto check = [&](lld x) {
        return modpow(int(x), (P - 1) / 2, P);
    };
    if (check(n) != 1) return -1;
    mt19937 rnd(7122); lld z = 1, w;
    while (check(w = (z * z - n + P) % P) != P - 1)
        z = rnd() % P;
    const auto M = [P, w](auto &u, auto &v) {
        auto [a, b] = u; auto [c, d] = v;
        return make_pair((a * c + b * d % P * w) % P,
            (a * d + b * c) % P);
    };
    pair<lld, lld> r(1, 0), e(z, 1);
    for (int q = (P + 1) / 2; q; q >= 1, e = M(e, e))
        if (q & 1) r = M(r, e);
    return
        int(r.first); // sqrt(n) mod P where P is prime
}

```

## 8 Geometry

### 8.1 Basic

```

struct pt{
    double x, y;
    pt(){}
    pt(double _x, double _y) : x(_x), y(_y){}
};
pt operator + (pt a, pt b)
{ return pt(a.x + b.x, a.y + b.y); }
pt operator - (pt a, pt b)
{ return pt(a.x - b.x, a.y - b.y); }
pt operator * (pt a, double p)
{ return pt(a.x * p, a.y * p); }
pt operator / (pt a, double p)
{ return pt(a.x / p, a.y / p); }
bool operator < (const pt &a, const pt &b)
{ return a.x < b.x || (a.x == b.x && a.y < b.y); }
bool operator == (const pt &a, const pt &b)
{ return a.x == b.x && a.y == b.y; }
double dot(pt a, pt b)
{ return a.x * b.x + a.y * b.y; }
double cross(pt a, pt b)
{ return a.x * b.y - a.y * b.x; }
double len(pt a)

```

```

{ return sqrt(dot(a, a)); }
double angle(pt a, pt b)
{ return acos(dot(a, b) / len(a) / len(b)); }
double area2(pt a, pt b, pt c)
{ return cross(b - a, c - a); }

```

```

const double eps = 1e-9;
int dcmp(double x){
    if(fabs(x) < eps) return 0;
    return x < 0 ? -1 : 1;
}

```

```

inline int ori(pt a, pt b, pt c){
    double area = cross(b - a, c - a);
    if(area > -eps && area < eps) return 0;
    return area > 0 ? 1 : -1;
}

inline int btw(pt a, pt b, pt c){ // [a, c, b]
    if(fabs(cross(b - a, c - a)) > eps) return false;
    if(dot(b - a, c - a)
        > -eps && len(c - a) <= len(b - a)) return true;
    return false;
}

```

```

bool intersect(pt a, pt b, pt c, pt d){
    if(a == c || a == d || b == c || b == d) return true;
    int a123 = ori(a, b, c), a124 = ori(a,
        b, d), a341 = ori(c, d, a), a342 = ori(c, d, b);
    if(a123 == 0 && a124 == 0){
        if(btw(a, b, c) || btw(a, b, d)
            || btw(c, d, a) || btw(c, d, b)) return true;
        else return false;
    }
    else if(a123
        * a124 <= 0 && a341 * a342 <= 0) return true;
    return false;
}

```

```

istream &operator>>(istream &s, pt &a){
    s >> a.x >> a.y;
    return s;
}

```

### 8.2 Convex Hull

```

vector<pt> ConvexHull(vector<pt> a) {
    int n = a.size();
    sort(a.begin(), a.end());
    vector<pt> ans = {a[0]};
    for (int t : {0, 1}) {
        int m = ans.size();
        for (int i = 1; i < n; ++i) {
            while (ans.size() > m && ori(ans[ans.size() - 2],
                ans.back(), pt[i]) <= 0) ans.pop_back();
            ans.pb(pt[i]);
        }
        reverse(all(pt));
    }
    if (ans.size() > 1) ans.pop_back();
    return ans;
}

```

### 8.3 Minkowski Sum

```

void reorder(vector<pt> &a){
    int pos = 0;
    for(int j = 1; j < a.size(); j++){
        if(a[j].x < a[pos].x || (a[j].x
            == a[pos].x && a[j].y < a[pos].y)) pos = j;
    }
    rotate(a.begin(), a.begin() + pos, a.end());
}

vector<pt> minkowski(vector<pt> a, vector<pt> b){
    // for(int i = 0;
        i < b.size(); i++) b[i] = {-b[i].x, -b[i].y};
    // 最短距離: 把 Q 鏡像, 找凸包到 (0, 0) 的最短距離
    reorder(a), reorder(b);
    a.pb(a[0]), a.pb(a[1]);
    b.pb(b[0]), b.pb(b[1]);
    vector<pt> res;
    int i = 0, j = 0;
    while(i < a.size() - 2 || j < b.size() - 2){
        res.pb(a[i] + b[j]);
        int c
            = cross(a[i + 1] - a[i], b[j + 1] - b[j]);
    }
}

```



```

    if(c >= 0 && i < a.size() - 2) i++;
    if(c <= 0 && j < b.size() - 2) j++;
}
return res;
}

```

## 8.4 Intersection of Circle and Line

```

vector<Pt> CircleLineInter(Cir c, Line l) {
    Pt p = l.a + (l.b - l.a)
        * ((c.o - l.a) * (l.b - l.a)) / abs2(l.b - l.a);
    double s = (l.b - l.a) ^ (c.o - l.a), h2 = c.r * c.r - s * s / abs2(l.b - l.a);
    if (sign(h2) == -1) return {};
    if (sign(h2) == 0) return {p};
    Pt h = (l.b - l.a) / abs(l.b - l.a) * sqrt(h2);
    return {p - h, p + h};
}

```

## 8.5 Intersection of Circles

```

vector<Pt> CirclesInter(Cir c1, Cir c2) {
    double d2 = abs2(c1.o - c2.o), d = sqrt(d2);
    if (d < max(c1.r, c2.r) - min(c1.r, c2.r) || d > c1.r + c2.r) return {};
    Pt u = (c1.o + c2.o) / 2 + (c1.o - c2.o) * ((c2.r * c2.r - c1.r * c1.r) / (2 * d2));
    double A = sqrt((c1.r + c2.r + d) * (c1.r - c2.r + d) * (c1.r + c2.r - d) * (-c1.r + c2.r + d));
    Pt v = Pt(c1.o.y - c2.o.y, -c1.o.x + c2.o.x) * A / (2 * d2);
    if (sign(v.x) == 0 && sign(v.y) == 0) return {u};
    return {u + v, u - v};
}

```

## 8.6 Point in Convex

```

bool PointInConvex(
    const vector<Pt> &C, Pt p, bool strict = true) {
    // only works when no three points are collinear
    int a = 1, b = int(C.size()) - 1, r = !strict;
    if (C.size() == 0) return false;
    if (C.size() < 3) return r && btw(C[0], C.back(), p);
    if (ori(C[0], C[a], C[b]) > 0) swap(a, b);
    if (ori(C[0], C[a], p) >= r || ori(C[0], C[b], p) <= -r) return false;
    while (abs(a - b) > 1) {
        int c = (a + b) / 2;
        if (ori(C[0], C[c], p) > 0 ? b : a) = c;
    }
    return ori(C[a], C[b], p) < r;
}

```

## 8.7 Minimum Enclosing Circle

```

Pt circle(Pt a, Pt b, Pt c) {
    Pt m1 = (a + b) / 2, m2 = (a + c) / 2,
        d1 = (b - a).rot().norm(), d2 = (c - a).norm();
    double tar = dot(m2, d2) - dot(m1, d2);
    double k = tar / dot(d1, d2);
    return m1 + d1 * k;
}

```

```

pair<Pt, double> min_enclosing(vector<Pt> &a) {
    random_shuffle(a.begin(), a.end());
    Pt c = {0, 0};
    double r2 = 0;
    for(int i = 0; i < n; i++) {
        if((a[i] - c).len2() <= r2) continue;
        c = a[i], r2 = 0;
        for(int j = 0; j < i; j++) {
            if((a[j] - c).len2() <= r2) continue;
            c = (a[i] + a[j]) / 2, r2 = (a[i] - c).len2();
            for(int k = 0; k < j; k++) {
                if((a[k] - c).len2() <= r2) continue;
                c = circle(a[i], a[j], a[k]), r2 = (a[k] - c).len2();
            }
        }
    }
    return make_pair(c, sqrt(r2));
}

```

## 8.8 Rotating Caliper

```

void RotatingCaliper(vector<Pt> &pts) {
    int n = pts.size();
    for(int i = 0, j = 2; i < n; ++i) {

```

```

        int ni = (i + 1) % n;
        while (true) {
            int nj = (j + 1) % n;
            if (area(pts[j], pts[i], pts[ni]) < area(pts[nj], pts[i], pts[ni]))
                j = nj;
            else break;
        }
        // do something
    }
}

```

## 8.9 Rotating Sweep Line

```

struct Event {
    Pt d; int u, v;
    bool operator < (const Event &b) const {
        return sign(d ^ b.d) > 0;
    };
};
Pt ref(Pt o) {return pos(o) == 1 ? Pt(-o.x, -o.y) : o;}
void RotatingSweepLine(vector<Pt> &pts) {
    int n = pts.size();
    vector<int> ord(n), pos(n);
    vector<Event> e;
    for (int i = 0; i < n; ++i)
        for (int j = i + 1; j < n; ++j) if (i ^ j)
            e.pb({ref(pts[i] - pts[j]), i, j});
    sort(all(e));
    iota(all(ord), 0);
    sort(all(ord), [&](int i, int j) {
        return sign(pts[i].y - pts[j].y) == 0 ?
            pts[i].x < pts[j].x : pts[i].y < pts[j].y;
    });
    for (int i = 0; i < n; ++i) pos[ord[i]] = i;
    const auto makeReverse = [&](auto &v) {
        sort(all(v)); v.resize(unique(all(v)) - v.begin());
        vector<pii> segs;
        for (int i = 0, j = 0; i < v.size(); i = j) {
            for (;
                j < v.size() && v[j].y - v[i].y <= j - i; ++j);
            segs.emplace_back(v[i], v[j - 1] + 1 + 1);
        }
        return segs;
    };
    for (int i = 0, j = 0; i < e.size(); i = j) {
        vector<int> tmp;
        for (; j < e.size() && !(e[i] < e[j]); j++)
            tmp.pb(min(pos[e[j].u], pos[e[j].v]));
        for (auto [l, r] : makeReverse(tmp)) {
            reverse(ord.begin() + l, ord.begin() + r);
            for (int t = l; t < r; ++t) pos[ord[t]] = t;
            // update value here
        }
    }
}

```

## 8.10 Delaunay Triangulation

```

/* Delaunay Triangulation:
Given a sets of points on 2D plane, find a
triangulation such that no points will strictly
inside circumcircle of any triangle.
find : return a triangle contain given point
add_point : add a point into triangulation
A Triangle is in triangulation iff. its has_chd is 0.
Region of triangle u: iterate each u.edge[i].tri,
each points are u.p[(i+1)%3], u.p[(i+2)%3]
Voronoi diagram: for each triangle in triangulation,
the bisector of all its edges will split the region.
nearest point will belong to the triangle containing it
*/
const ll inf = MAXC * MAXC * 100; // lower_bound unknown
struct Tri;
struct Edge {
    Tri* tri; int side;
    Edge(): tri(0), side(0){}
    Edge(Tri* _tri, int _side): tri(_tri), side(_side){}
};
struct Tri {
    pll p[3];
    Edge edge[3];
    Tri* chd[3];
    Tri() {}
    Tri(const pll& p0, const pll& p1, const pll& p2) {
        p[0] = p0; p[1] = p1; p[2] = p2;
        chd[0] = chd[1] = chd[2] = 0;
    }
}

```

```

bool has_chd() const { return chd[0] != 0; }
int num_chd() const {
    return !!chd[0] + !!chd[1] + !!chd[2];
}
bool contains(pll const& q) const {
    for (int i = 0; i < 3; ++i)
        if (ori(p[i], p[(i + 1) % 3], q) < 0)
            return 0;
    return 1;
}
} pool[N * 10], *tris;
void edge(Edge a, Edge b) {
    if(a.tri) a.tri->edge[a.side] = b;
    if(b.tri) b.tri->edge[b.side] = a;
}
struct Trig { // Triangulation
    Trig() {
        the_root
            = // Tri should at least contain all points
              new(tris++) Tri(pll(-inf, -inf),
                             pll(inf + inf, -inf), pll(-inf, inf + inf));
    }
    Tri* find(pll p) { return find(the_root, p); }
    void add_point(const pll &p) { add_point(find(the_root, p), p); }
    Tri* the_root;
    static Tri* find(Tri* root, const pll &p) {
        while (1) {
            if (!root->has_chd())
                return root;
            for (int i = 0; i < 3 && root->chd[i]; ++i)
                if (root->chd[i]->contains(p)) {
                    root = root->chd[i];
                    break;
                }
        }
        assert(0); // "point not found"
    }
    void add_point(Tri* root, pll const& p) {
        Tri* t[3];
        /* split it into three triangles */
        for (int i = 0; i < 3; ++i)
            t[i] = new(tris
                ++ Tri(root->p[i], root->p[(i + 1) % 3], p);
        for (int i = 0; i < 3; ++i)
            edge(Edge(t[i], 0), Edge(t[(i + 1) % 3], 1));
        for (int i = 0; i < 3; ++i)
            edge(Edge(t[i], 2), root->edge[(i + 2) % 3]);
        for (int i = 0; i < 3; ++i)
            root->chd[i] = t[i];
        for (int i = 0; i < 3; ++i)
            flip(t[i], 2);
    }
    void flip(Tri* tri, int pi) {
        Tri* trj = tri->edge[pi].tri;
        int pj = tri->edge[pi].side;
        if (!trj) return;
        if (!in_cc(tri->p
            [0], tri->p[1], tri->p[2], trj->p[pj])) return;
        /* flip edge between tri, trj */
        Tri* trk = new(tris++) Tri
            (tri->p[(pi + 1) % 3], trj->p[pj], tri->p[pi]);
        Tri* trl = new(tris++) Tri
            (trj->p[(pj + 1) % 3], tri->p[pi], trj->p[pj]);
        edge(Edge(trk, 0), Edge(trl, 0));
        edge(Edge(trk, 1), tri->edge[(pi + 2) % 3]);
        edge(Edge(trk, 2), trj->edge[(pj + 1) % 3]);
        edge(Edge(trl, 1), trj->edge[(pj + 2) % 3]);
        edge(Edge(trl, 2), tri->edge[(pi + 1) % 3]);
        tri->chd
            [0] = trk; tri->chd[1] = trl; tri->chd[2] = 0;
        trj->chd
            [0] = trk; trj->chd[1] = trl; trj->chd[2] = 0;
        flip(trk, 1); flip(trk, 2);
        flip(trl, 1); flip(trl, 2);
    }
};
vector<Tri*> triang; // vector of all triangle
set<Tri*> vst;
void go(Tri* now) { // store all tri into triang
    if (vst.find(now) != vst.end())
        return;
    vst.insert(now);
    if (!now->has_chd())
        return triang.pb(now);
    for (int i = 0; i < now->num_chd(); ++i)

```

```

        go(now->chd[i]);
    }
}
void build(int n, pll* ps) { // build triangulation
    tris = pool; triang.clear(); vst.clear();
    random_shuffle(ps, ps + n);
    Trig tri; // the triangulation structure
    for (int i = 0; i < n; ++i)
        tri.add_point(ps[i]);
    go(tri.the_root);
}

```

## 8.11 3D Point

```

struct Pt {
    double x, y, z;
    Pt(double _x = 0, double
        _y = 0, double _z = 0): x(_x), y(_y), z(_z){}
    Pt operator + (const Pt &o) const
        { return Pt(x + o.x, y + o.y, z + o.z); }
    Pt operator - (const Pt &o) const
        { return Pt(x - o.x, y - o.y, z - o.z); }
    Pt operator * (const double &k) const
        { return Pt(x * k, y * k, z * k); }
    Pt operator / (const double &k) const
        { return Pt(x / k, y / k, z / k); }
    double operator * (const Pt &o) const
        { return x * o.x + y * o.y + z * o.z; }
    Pt operator ^ (const Pt &o) const
        { return {Pt(y * o.z - z
            * o.y, z * o.x - x * o.z, x * o.y - y * o.x)}; }
};
double abs2(Pt o) { return o * o; }
double abs(Pt o) { return sqrt(abs2(o)); }
Pt cross3(Pt a, Pt b, Pt c)
{ return (b - a) ^ (c - a); }
double area(Pt a, Pt b, Pt c)
{ return abs(cross3(a, b, c)); }
double volume(Pt a, Pt b, Pt c, Pt d)
{ return cross3(a, b, c) * (d - a); }
bool coplaner(Pt a, Pt b, Pt c, Pt d)
{ return sign(volume(a, b, c, d)) == 0; }
Pt proj(Pt o, Pt a, Pt b, Pt c) // o proj to plane abc
{ Pt n = cross3(a, b, c);
    return o - n * ((o - a) * (n / abs2(n))); }
Pt LinePlaneInter(Pt u, Pt v, Pt a, Pt b, Pt c) {
    // intersection of line uv and plane abc
    Pt n = cross3(a, b, c);
    double s = n * (u - v);
    if (sign(s) == 0) return {-1, -1, -1}; // not found
    return v + (u - v) * ((n * (a - v)) / s);
}

```

## 8.12 3D Convex Hull

```

struct CH3D {
    struct face{int a, b, c; bool ok;} F[8 * N];
    double dblcmp(Pt &p, face &f)
    { return
        cross3(P[f.a], P[f.b], P[f.c]) * (p - P[f.a]); }
    int g[N][N], num, n;
    Pt P[N];
    void deal(int p, int a, int b) {
        int f = g[a][b];
        face add;
        if (F[f].ok) {
            if (dblcmp(P[p], F[f]) > eps) dfs(p, f);
            else
                add.a =
                    b, add.b = a, add.c = p, add.ok = 1, g[p][
                    b] = g[a][p] = g[b][a] = num, F[num++] = add;
        }
    }
    void dfs(int p, int now) {
        F[now].ok = 0;
        deal(p, F[now].b, F[now].a), deal(p, F[
            now].c, F[now].b), deal(p, F[now].a, F[now].c);
    }
    bool same(int s, int t){
        Pt &a = P[F[s].a];
        Pt &b = P[F[s].b];
        Pt &c = P[F[s].c];
        return fabs(volume(a, b, c, P[F[t].a
            ])) < eps && fabs(volume(a, b, c, P[F[t].b])) <
            eps && fabs(volume(a, b, c, P[F[t].c])) < eps;
    }
    void init(int _n){n = _n, num = 0;}
    void solve() {

```

```

face add;
num = 0;
if(n < 4) return;
if([&](){
    for (int i = 1; i < n; ++i)
        if (abs(P[0] - P[i]) > eps)
            return swap(P[1], P[i]), 0;
    return 1;
}() || [&](){
    for (int i = 2; i < n; ++i)
        if (abs(cross3(P[i], P[0], P[1])) > eps)
            return swap(P[2], P[i]), 0;
    return 1;
}() || [&](){
    for (int i = 3; i < n; ++i)
        if (fabs(((P[0] - P[1])
            ^ (P[1] - P[2])) * (P[0] - P[i])) > eps)
            return swap(P[3], P[i]), 0;
    return 1;
}())return;
for (int i = 0; i < 4; ++i) {
    add.a = (i + 1) % 4, add.b = (i
        + 2) % 4, add.c = (i + 3) % 4, add.ok = true;
    if (dblcmp(P[i], add) > 0) swap(add.b, add.c);
    g[add.a][add.
        b] = g[add.b][add.c] = g[add.c][add.a] = num;
    F[num++] = add;
}
for (int i = 4; i < n; ++i)
    for (int j = 0; j < num; ++j)
        if (F[j].ok && dblcmp(P[i], F[j]) > eps) {
            dfs(i, j);
            break;
        }
for (int tmp = num, i = (num = 0); i < tmp; ++i)
    if (F[i].ok) F[num++] = F[i];
}
double get_area() {
    double res = 0.0;
    if (n == 3)
        return abs(cross3(P[0], P[1], P[2])) / 2.0;
    for (int i = 0; i < num; ++i)
        res += area(P[F[i].a], P[F[i].b], P[F[i].c]);
    return res / 2.0;
}
double get_volume() {
    double res = 0.0;
    for (int i = 0; i < num; ++i)
        res += volume(Pt
            (0, 0, 0), P[F[i].a], P[F[i].b], P[F[i].c]);
    return fabs(res / 6.0);
}
int triangle() {return num;}
int polygon() {
    int res = 0;
    for (int i = 0,
        flag = 1; i < num; ++i, res += flag, flag = 1)
        for (int j = 0; j < i && flag; ++j)
            flag &= !same(i, j);
    return res;
}
Pt getcent(){
    Pt ans(0, 0, 0), temp = P[F[0].a];
    double v = 0.0, t2;
    for (int i = 0; i < num; ++i)
        if (F[i].ok == true) {
            Pt p1 =
                P[F[i].a], p2 = P[F[i].b], p3 = P[F[i].c];
            t2 = volume(temp, p1, p2, p3) / 6.0;
            if (t2 > 0)
                ans.x += (p1.x + p2.
                    x + p3.x + temp.x) * t2, ans.y += (p1.y +
                    p2.y + p3.y + temp.y) * t2, ans.z += (p1
                    .z + p2.z + p3.z + temp.z) * t2, v += t2;
        }
    ans.x
        /= (4 * v), ans.y /= (4 * v), ans.z /= (4 * v);
    return ans;
}
double pointmindis(Pt p) {
    double rt = 99999999;
    for(int i = 0; i < num; ++i)
        if(F[i].ok == true) {
            Pt p1 =
                P[F[i].a], p2 = P[F[i].b], p3 = P[F[i].c];

```

```

        double a = (p2.y - p1.y) * (p3
            .z - p1.z) - (p2.z - p1.z) * (p3.y - p1.y);
        double b = (p2.z - p1.z) * (p3
            .x - p1.x) - (p2.x - p1.x) * (p3.z - p1.z);
        double c = (p2.x - p1.x) * (p3
            .y - p1.y) - (p2.y - p1.y) * (p3.x - p1.x);
        double
            d = 0 - (a * p1.x + b * p1.y + c * p1.z);
        double temp = fabs(a * p.x + b * p.y +
            c * p.z + d) / sqrt(a * a + b * b + c * c);
        rt = min(rt, temp);
    }
    return rt;
};

```

## 9 Misc

### 9.1 Binary Search on Fraction

```

struct Q {
    ll p, q;
    Q go(Q b, ll d) { return {p + b.p*d, q + b.q*d}; }
};
bool pred(Q);
// returns smallest p/q in [lo, hi] such that
// pred(p/q) is true, and 0 <= p, q <= N
Q frac_bs(ll N) {
    Q lo{0, 1}, hi{1, 0};
    if (pred(lo)) return lo;
    assert(pred(hi));
    bool dir = 1, L = 1, H = 1;
    for (; L || H; dir = !dir) {
        ll len = 0, step = 1;
        for (int t = 0; t < 2 && (t ? step/=2 : step*=2);)
            if (Q mid = hi.go(lo, len + step);
                mid.p > N || mid.q > N || dir ^ pred(mid))
                t++;
            else len += step;
        swap(lo, hi = hi.go(lo, len));
        (dir ? L : H) = !!len;
    }
    return dir ? hi : lo;
}

```

### 9.2 Random

```

struct custom_hash {
    static uint64_t splitmix64(uint64_t x) {
        x += 0x9e3779b97f4a7c15;
        x = (x ^ (x >> 30)) * 0xbf58476d1ce4e5b9;
        x = (x ^ (x >> 27)) * 0x94d049bb133111eb;
        return x ^ (x >> 31);
    }
    size_t operator()(uint64_t a) const {
        static const uint64_t FIXED_RANDOM = chrono::
            steady_clock::now().time_since_epoch().count();
        return splitmix64(a + FIXED_RANDOM);
    }
};
unordered_map<int, int, custom_hash> m1;
random_device rd; mt19937 rng(rd());

```

### 9.3 Bit Hack

```

ll next_perm(ll v) { ll t = v | (v - 1);
    return (t + 1) |
        (((~t & ~t) - 1) >> (__builtin_ctz(v) + 1)); }

```

### 9.4 Dynamic MST

```

int cnt[maxn], cost[maxn], st[maxn], ed[maxn];
pair<int, int> qr[maxn];
// qr[i].first = id of edge to
// be changed, qr[i].second = weight after operation
// cnt[i] = number of operation on edge i
// call solve(0, q - 1, v,
// 0), where v contains edges i such that cnt[i] == 0
void contract(int l, int
    r, vector<int> v, vector<int> &x, vector<int> &y) {
    sort(v.begin(), v.end(), [&](int i, int j) {
        if (cost[i] == cost[j]) return i < j;
        return cost[i] < cost[j];
    });
    djs.save();
    for (int i = l; i <= r;
        ++i) djs.merge(st[qr[i].first], ed[qr[i].first]);
}

```

```

for (int i = 0; i < (int)v.size(); ++i) {
    if (djs.find(st[v[i]]) != djs.find(ed[v[i]])) {
        x.push_back(v[i]);
        djs.merge(st[v[i]], ed[v[i]]);
    }
}
djs.undo();
djs.save();
for (int i = 0; i < (int)x.size(); ++i) djs.merge(st[x[i]], ed[x[i]]);
for (int i = 0; i < (int)v.size(); ++i) {
    if (djs.find(st[v[i]]) != djs.find(ed[v[i]])) {
        y.push_back(v[i]);
        djs.merge(st[v[i]], ed[v[i]]);
    }
}
djs.undo();
}

void solve(int l, int r, vector<int> v, long long c) {
    if (l == r) {
        cost[qr[l].first] = qr[l].second;
        if (st[qr[l].first] == ed[qr[l].first]) {
            printf("%lld\n", c);
            return;
        }
        int minv = qr[l].second;
        for (int i = 0; i < (int)v.size(); ++i) minv = min(minv, cost[v[i]]);
        printf("%lld\n", c + minv);
        return;
    }
    int m = (l + r) >> 1;
    vector<int> lv = v, rv = v;
    vector<int> x, y;
    for (int i = m + 1; i <= r; ++i) {
        cnt[qr[i].first]--;
        if (cnt[qr[i].first] == 0) lv.push_back(qr[i].first);
    }
    contract(l, m, lv, x, y);
    long long lc = c, rc = c;
    djs.save();
    for (int i = 0; i < (int)x.size(); ++i) {
        lc += cost[x[i]];
        djs.merge(st[x[i]], ed[x[i]]);
    }
    solve(l, m, y, lc);
    djs.undo();
    x.clear(), y.clear();
    for (int i = m + 1; i <= r; ++i) cnt[qr[i].first]++;
    for (int i = l; i <= m; ++i) {
        cnt[qr[i].first]--;
        if (cnt[qr[i].first] == 0) rv.push_back(qr[i].first);
    }
    contract(m + 1, r, rv, x, y);
    djs.save();
    for (int i = 0; i < (int)x.size(); ++i) {
        rc += cost[x[i]];
        djs.merge(st[x[i]], ed[x[i]]);
    }
    solve(m + 1, r, y, rc);
    djs.undo();
    for (int i = l; i <= m; ++i) cnt[qr[i].first]++;
}

```

## 9.5 Manhattan MST

```

void solve(Point *a, int n) {
    sort(a, a + n, [](const Point &p, const Point &q) {
        return p.x + p.y < q.x + q.y;
    });
    set<Point> st; // greater<Point::x>
    for (int i = 0; i < n; ++i) {
        for (auto it = st.lower_bound(a[i]); it != st.end(); it = st.erase(it)) {
            if (it -> x - it -> y < a[i].x - a[i].y) break;
            es.push_back({it -> u, a[i].u, dist(*it, a[i])});
        }
        st.insert(a[i]);
    }
}

void MST(Point *a, int n) {
    for (int t = 0; t < 2; ++t) {

```

```

        solve(a, n);
        for (int i = 0; i < n; ++i) swap(a[i].x, a[i].y);
        solve(a, n);
        for (int i = 0; i < n; ++i) a[i].x = -a[i].x;
    }
}

```

## 9.6 DP Optimization Conditions

### 9.6.1 Totally Monotone (Concave/Convex)

$$\forall i < i', j < j', B[i][j] \leq B[i'][j] \implies B[i][j'] \leq B[i'][j']$$

### 9.6.2 Monge Condition (Concave/Convex)

$$\forall i < i', j < j', B[i][j] + B[i'][j'] \geq B[i][j'] + B[i'][j]$$

$$\forall i < i', j < j', B[i][j] + B[i'][j'] \leq B[i][j'] + B[i'][j]$$

### 9.6.3 Optimal Split Point

If

$$B[i][j] + B[i+1][j+1] \geq B[i][j+1] + B[i+1][j]$$

then

$$H_{i,j-1} \leq H_{i,j} \leq H_{i+1,j}$$

## 9.7 Mo's Algo With Modification

```

/*
Mo's Algorithm With modification
Block: N^{2/3}, Complexity: N^{5/3}
*/
struct Query {
    int L, R, LBid, RBid, T;
    Query(int l, int r, int t):
        L(l), R(r), LBid(l / blk), RBid(r / blk), T(t) {}
    bool operator<(const Query &q) const {
        if (LBid != q.LBid) return LBid < q.LBid;
        if (RBid != q.RBid) return RBid < q.RBid;
        return T < q.T;
    }
};

void solve(vector<Query> query) {
    sort(ALL(query));
    int L = 0, R = 0, T = -1;
    for (auto q : query) {
        while (T < q.T) addTime(L, R, ++T); // TODO
        while (T > q.T) subTime(L, R, T--); // TODO
        while (R < q.R) add(arr[++R]); // TODO
        while (L > q.L) add(arr[--L]); // TODO
        while (R > q.R) sub(arr[R--]); // TODO
        while (L < q.L) sub(arr[L--]); // TODO
        // answer query
    }
}

```

## 9.8 Mo's Algo On Tree

```

/*
Mo's Algorithm On Tree
Preprocess:
1) LCA
2) dfs with in[u] = dft++, out[u] = dft++
3) ord[in[u]] = ord[out[u]] = u
4) bitset<MAXN> inset
*/
struct Query {
    int L, R, LBid, lca;
    Query(int u, int v) {
        int c = LCA(u, v);
        if (c == u || c == v)
            q.lca = -1, q.L = out[c ^ u ^ v], q.R = out[c];
        else if (out[u] < in[v])
            q.lca = c, q.L = out[u], q.R = in[v];
        else
            q.lca = c, q.L = out[v], q.R = in[u];
        q.Lid = q.L / blk;
    }
    bool operator<(const Query &q) const {
        if (LBid != q.LBid) return LBid < q.LBid;
        return R < q.R;
    }
};

void flip(int x) {
    if (inset[x]) sub(arr[x]); // TODO
    else add(arr[x]); // TODO
    inset[x] = ~inset[x];
}

void solve(vector<Query> query) {
    sort(ALL(query));
    int L = 0, R = 0;

```

```

for (auto q : query) {
    while (R < q.R) flip(ord[++R]);
    while (L > q.L) flip(ord[--L]);
    while (R > q.R) flip(ord[R--]);
    while (L < q.L) flip(ord[L++]);
    if (~q.lca) add(arr[q.lca]);
    // answer query
    if (~q.lca) sub(arr[q.lca]);
}
}

```

## 9.9 Mo's Algorithm

- Mo's Algorithm With Addition Only
  - Sort queries same as the normal Mo's algorithm.
  - For each query  $[l, r]$ :
    - If  $l/blk = r/blk$ , brute-force.
    - If  $l/blk \neq curL/blk$ , initialize  $curL := (l/blk + 1) \cdot blk$ ,  $curR := curL - 1$
    - If  $r > curR$ , increase  $curR$
    - decrease  $curL$  to fit  $l$ , and then undo after answering
- Mo's Algorithm With Offline Second Time
  - Require: Changing answer  $\equiv$  adding  $f([l, r], r+1)$ .
  - Require:  $f([l, r], r+1) = f([l, r], r+1) - f([l, l], r+1)$ .
  - Part1: Answer all  $f([l, r], r+1)$  first.
  - Part2: Store  $curR \rightarrow R$  for  $curL$  (reduce the space to  $O(N)$ ), and then answer them by the second offline algorithm.
  - Note: You must do the above symmetrically for the left boundaries.

## 9.10 Hilbert Curve

```

ll hilbert(int n, int x, int y) {
    ll res = 0;
    for (int s = n / 2; s; s >>= 1) {
        int rx = (x & s) > 0;
        int ry = (y & s) > 0;
        res += s * 1ll * s * ((3 * rx) ^ ry);
        if (ry == 0) {
            if (rx == 1) x = s - 1 - x, y = s - 1 - y;
            swap(x, y);
        }
    }
    return res;
} // n = 2^k

```

## 9.11 SMAWK

```

bool select(int r, int u, int v){
    // if f(r, v) is better than f(r, u), return true
    return f(r, u) < f(r, v);
}
// For all 2x2 submatrix: (x < y => y is better than x)
// If M[1][0] < M[1][1], M[0][0] < M[0][1]
// If M[1][0] == M[1][1], M[0][0] <= M[0][1]
// M[i][ans[i]] is the best value in the i-th row
vector<int> solve(vector<int> &r, vector<int> &c){
    if(r.size() == 1){
        vector<int> opt(1, 0);
        for(int i = 1; i < c.size(); i++){
            if(select(r[0], c[opt[0]], c[i])){
                opt[0] = i;
            }
        }
        return opt;
    }
    //reduce
    vector<int> st, rev;
    for(int i = 0; i < c.size(); i++){
        while(!st.empty()
            && select(r[st.size() - 1], st.back(), c[i])){
            st.pop_back();
            rev.pop_back();
        }
        if(st.size() < r.size()){
            st.pb(c[i]);
            rev.pb(i);
        }
    }
    //interpolate
    vector<int> half;
    for(int i = 0; i < r.size(); i += 2){
        half.pb(r[i]);
    }
    vector<int> ans(r.size());
    auto interp = solve(half, st);
    for(int i = 0;
        i < interp.size(); i++) ans[i * 2] = interp[i];
    for(int i = 1; i < ans.size(); i += 2){
        int s = ans[i - 1], e = (i
            + 1 < ans.size() ? ans[i + 1] : st.size() - 1);

```

```

        ans[i] = s;
        for(int j = s + 1; j <= e; j++){
            if(select(r[i], st[ans[i]], st[j])) ans[i] = j;
        }
    }
    for(int
        i = 0; i < ans.size(); i++) ans[i] = rev[ans[i]];
    return ans;
}

```

```

vector<int> smawk(int n, int m){
    vector<int> r(n), c(m);
    iota(r.begin(), r.end(), 0);
    iota(c.begin(), c.end(), 0);
    return solve(r, c);
}

```

## 9.12 Simulate Annealing

```

double anneal() {
    mt19937 rnd_engine(time(0));
    uniform_real_distribution<double> rng(0, 1);
    const double dT = 0.001;
    // Argument p
    double S_cur = calc(p), S_best = S_cur;
    for (double T = 2000; T > eps; T -= dT) {
        // Modify p to p_prime
        const double S_prime = calc(p_prime);
        const double delta_c = S_prime - S_cur;
        double prob = min((double)1, exp(-delta_c / T));
        if (rng(rnd_engine) <= prob)
            S_cur = S_prime, p = p_prime;
        if (S_prime < S_best) // find min
            S_best = S_prime, p_best = p_prime;
    }
    return S_best;
}

```

## 9.13 Python

```

from [decimal, fractions, math, random] import *
arr = list(map(int, input().split())) # input
setcontext(Context
    (prec=10, Emax=MAX_EMAX, rounding=ROUND_FLOOR))
Decimal('1.1') / Decimal('0.2')
Fraction(3, 7)
Fraction(Decimal('1.14'))
Fraction('1.2').limit_denominator(4).numerator
Fraction(cos(pi / 3)).limit_denominator()
S = set(), S.add((a, b)), S.remove((a, b)) # set
if not (a, b) in S:
D = dict(), D[(a, b)] = 1, del D[(a, b)] # dict
for (a, b) in D.items():
    arr = [randint(1, C) for i in range(N)]
choice([8, 6, 4, 1]) # random pick one

```

## 9.14 Matroid

Start from  $S = \emptyset$ . In each iteration, let

- $Y_1 = \{x \notin S \mid S \cup \{x\} \in I_1\}$
- $Y_2 = \{x \notin S \mid S \cup \{x\} \in I_2\}$

If there exists  $x \in Y_1 \cap Y_2$ , insert  $x$  into  $S$ . Otherwise for each  $x \in S, y \notin S$ , create edges

- $x \rightarrow y$  if  $S - \{x\} \cup \{y\} \in I_1$ .
- $y \rightarrow x$  if  $S - \{x\} \cup \{y\} \in I_2$ .

Find a *shortest* path (with BFS) starting from a vertex in  $Y_1$  and ending at a vertex in  $Y_2$  which doesn't pass through any other vertices in  $Y_2$ , and alternate the path. The size of  $S$  will be incremented by 1 in each iteration. For the weighted case, assign weight  $w(x)$  to vertex  $x$  if  $x \in S$  and  $-w(x)$  if  $x \notin S$ . Find the path with the minimum number of edges among all minimum length paths and alternate it.