

FORMATING COMMANDS:

BREAK. The BREAK command specifies action based on a change of a value of a column or an expression, or when a row is returned. The general syntax is

BREAK [ON column/expression/ROW/REPORT]

BTITLE. The BTITLE command specifies the format of the title at the bottom of each page. The general syntax is

BTITLE [ON/OFF] [printspec [text/variable]....]

**ON/OFF turns the title on or off. The printspecs are COL n, SKIP n, LEFT, CENTER, RIGHT, and BOLD. The text is a character string to be printed, and the variable is a user-defined or system variable.

COMPUTE. The COMPUTE command calculates using standard mathematics functions and displays the summary lines. The general syntax is

*COMPUTE [function OF column/alias/expression.... ON
column/alias/expression/REPORT/ROW]*

The functions are SUM, AVG, COUNT, MAX, MIN, NUM, STD, VAR. The ON clause must match the BREAK statement.

TTITLE. The TTITLE command specifies the title's format, which is displayed at the top of each page. The general syntax is

TTITLE ON/OFF] [printspec [text/variable]....]

**ON/OFF turns the title on or off. The printspecs are COL n, SKIP n, LEFT, CENTER, RIGHT, and BOLD. The text is a character string to be printed, and the variable is a user-defined or system variable.

LINESIZE. The LINESIZE command is used to set the total number of character displayed by SQL*PLUS per each line before wrapping. The default line size is 80. The general syntax is

LINESIZE n

PAGESIZE. The PAGESIZE command sets the number of lines per each page. The default is 24. You can change it to 0 to suppress all titles, headings, and page breaks. The general syntax is

PAGESIZE n