

Constructive, Evidence-Gated Generation of Long English Letter-Level Palindromes

Anonymous ACL submission

Abstract

We study the constructive generation of long English palindromes under a strict letter-level definition. A candidate must be an exact palindrome, originate from an auditable construction rather than borrowed catalogue text, avoid repeated or self-palindromic units, and survive a blinded human readability study. Our workbench keeps character obligations live while it builds ordinary scenes: typed grammar and semantic slots propose the next words, and targeted repairs are selected from the current mirrored-letter debt. Ten deliberately orthogonal construction lanes share an independent two-pointer and hash verifier, provenance records, and a novelty registry. The current development snapshot contains 4,560 candidates from 156 route summaries; 78 are exact, but none passes the mechanical admission gate and no row has yet been promoted by readers. We report the rendered candidates and the failed gates explicitly, then use each failure to define the next repair operator. The contribution is therefore a reproducible construction and evaluation protocol aimed at a genuinely readable long output, not a speed benchmark or a proxy-only result.

1 Task and acceptance gate

Let x be a rendered English passage. We normalize by lowercasing and retaining ASCII letters only,

$$n(x) = \text{letters}(\text{lower}(x)), \quad (1)$$

and require $n(x) = \text{rev}(n(x))$. Punctuation and spacing are displayed for readers but cannot change the equation. The target is an intact, multi-clause passage of at least 100 normalized letters; the familiar 38-letter seed is used only as a development benchmark.

The hard gate has four independent parts. First, a standard-library two-pointer check and a separately implemented forward/reverse hash check

must agree. Second, the provenance ledger must show that the text was constructed by the current method, with no catalogue import, scaffold relexicalization, repeated multiword unit, word-order reflection, or self-palindromic word/span. Third, the rendering must be ordinary prose with distinct lexical choices, not a list or fragment. Finally, blinded readers must judge it readable and coherent. Programmatic language scores can rank or diagnose candidates; they never certify the last condition.

2 A working construction loop

The constructor maintains a state $(L, R, d, \sigma_L, \sigma_R, \rho)$, where L and R are the committed left and right tapes, d is the vector of mirrored character debt, σ stores grammar and agreement state, and ρ is the semantic scene graph. At each step it (i) chooses a typed scene slot or boundary, (ii) proposes a short ordinary word or inflection compatible with σ and ρ , (iii) updates the opposing character obligation immediately, and (iv) retains the best frontier by length and unresolved debt. A repair may replace a complete semantic slot, resegment an exact tape, change a dependency seam, or alter an inflection/clitic boundary. A run is not counted as progress when it merely resamples the same lane or duplicates a prior signature.

This is a character-constrained generation problem in the spirit of prior palindrome enumeration and lexically constrained decoding (Papadopoulos et al., 2015; Hokamp and Liu, 2017; Lu et al., 2022), but the character obligation is coupled to a live scene and grammar rather than applied after a sentence has been written.

The ten lanes are intentionally different views of this same loop: character-level LM decoding; exact-tape grammatical resegmentation; dependency-tree seam CSP; agreement-carrying morphology; CFG/Earley character intersection;

a human-authored scene lattice with live equations; semantic valency and attachment; inflectional and clitic boundary search; a flat, compositional grammar without nested palindrome spans; and exact-candidate repair by semantic slot substitution. Each lane writes its rendered text, normalized tape, independent checks, source hashes, novelty result, and a concrete next repair to a JSON artifact.

The implementation also exposes an explicit totality witness for arbitrary requested lengths. This witness is useful for testing the state machine but is tagged as non-reader output and cannot satisfy the admission gate. Thus termination of the software is never confused with success of the linguistic task.

3 Current rendered evidence

Table 1 gives one fresh surface for each lane family. These are actual outputs, not templates; lengths count normalized letters. Exactness and readability status are shown together so that a high-scoring but invalid surface cannot become a headline result.

The longest current intact-prose probe is the first row of the table. Across 20 held-out two-clause scenes, lengths range from 66 to 72 letters and none closes exactly. A tape resegmentation lane also found the 21-letter catalogue control “a man a plan a canal panama”; its exactness is independently confirmed, but catalogue provenance excludes it. These controls are useful for checking the gates, never for inflating the result set.

The latest typed-frame repair adds the fresh 40-letter sentence “The baker carries a letter near the quiet harbor.” Its eight live obligations remain open, while every mechanical quality check other than exactness passes. The next run changes only the adjunct boundary lexeme selected by the first residual obligation. That targeted repair changes “near” to “by”, yielding “The baker carries a letter by the quiet harbor”; it remains non-exact at 38 letters, below the mechanical length floor, and records the determiner slot as the next repair.

Two further joint searches extend the constructive evidence. A central-pivot CSP retains the intact 113-letter pair “The archivist records the carefully folded winter map at dawn. A patient sailor observes a weathered cedar rescue boat beside the river.” Its first mirrored characters already disagree, so both independent audits reject it. A

semantic-slot lattice renders 108 jointly selected states and prunes all 108 before admission. A bidirectional decoder also reproduces the 51-letter “Doc, note: I dissent.” palindrome, but the provenance gate identifies it as catalogue text and keeps it out of the result set.

The word-pair graph contributes a 164-letter intact scene frontier but no closure. Paired semantic mutation produces two fresh 61-letter controls and no closure. Finally, weighted reverse-tape segmentation retains two authored 103–104-letter clauses but finds no legal segmentation. These runs are separate construction states; each leaves an explicit repair rather than being counted as a larger duplicate sweep.

A residual repair then produces a 239-letter four-clause scene from fresh independent clause authoring; its first boundary remains unmatched under both audits. A separate semantic-slot repair adds two new 108–109-letter scenes, again with complete slots and no exact closure. Both are retained as the next reader-facing controls and specify a local boundary or paired-slot repair.

The character-LM grammar decoder retains a 77-letter legal-prose frontier. A new dependency-seam CSP adds a 105-letter typed scene, and an agreement-carrying morphology/clitic transducer adds a 122-letter scene. All three are fresh, ordinary-order constructions with independent audits and explicit repairs; none closes the global character equation.

The joint CFG/Earley intersection adds one 140-letter scene from a paired bidirectional chart. A 729-row cross-product variant is explicitly excluded as a duplicate sweep, preserving its evidence without counting it as progress. The rendered controls are “a patient child carries the river trail at dusk. the keeper opens old wooden gates before dawn,” “The patient archivist carefully maps a quiet museum archive before dawn. Curious visitors study faded stars beside the river,” “When the careful archivist restores the damaged ledger, she records each witness name and sends the sealed copy to the harbor office before winter,” and “The patient gardener waters the cedar seedlings beside the schoolhouse before sunrise. The teacher labels every seedling and stores the tools beneath the quiet porch.” Their independent audits all reject exactness; each has a named local repair and remains reader-ineligible.

The hand-authored clause lattice then aligns five fresh complete clauses across word boundaries,

Lane family	Rendered surface	Letters	Exact	Next repair
LM + tape	the careful teacher guides a young visitor; a patient sailor carries the red lantern	70	no	held-out LM boundary proposals
Dependency + morphology + CFG	Ava saw radar level civic; civic level radar was Ava	42	yes [†]	typed boundary resegmentation / fresh frame
Scene lattice	At dawn, the patient guide carries a red map to the waiting child.	52	no	replace one typed object slot
Valency / attachment	By noon, the careful nurse labels the sealed vial for the quiet ward.	55	no	preserve valency while changing object/attachment
Inflection / clitic	After rain, the young keeper opens the old gate beside the garden.	53	no	held-out inflection-boundary repair
Flat composition / slot repair	At dawn, the patient guide carries a blue chart to the waiting child.	55	no	satisfy the global character obligation

Table 1: Representative outputs in the 2026-09-16 ledger. [†]The 42-letter seam is exact under both independent checks but is rejected because it repeats self-palindromic words, mirrors word order, and fails the distinct word gate. The other rows are fresh ordinary prose and are retained as repairable frontiers, not as palindrome claims.

with an explicit all-different content-word gate. It yields the longest current intact-prose frontier (308 letters): “Mara carries warm bread to the river. The careful pilot studies cloud maps. Children gather bright shells by moonlight. A gardener shelters young cedar shoots. Old friends share stories beside fire. By the hearth, new tales begin. Near the grove, small finches settle. At twilight, the patient tide returns. Beyond the hills, a quiet engine waits. At the shore, Owen listens for bells.” The independent pointer and forward/reverse SHA checks disagree at the first character, so it is explicitly non-exact and non-admitted. Its provenance, fresh lexical bank, and next semordnilap-compatible slot repair are recorded in the run artifact; it is a reader-facing control, not a palindrome claim.

Three follow-up constructions add new state representations rather than larger sweeps. A boundary-conditioned finite-state resegmentation produces a 270-letter six-clause scene; a dependency-boundary CSP exposes 127 live character equations in a marine-biologist scene; and a residual semantic-slot lattice produces a 122-letter observatory scene while locking valency, agreement, and content-word uniqueness. Each has a first-mismatch pointer trace, unequal forward/reverse hashes, fresh provenance, novelty preflight, and a targeted next repair. None is exact or mechanically admitted.

The outside-in scene grammar was then repaired to use distinct held-out right frames instead of reflecting a left clause. Its longest pair is “At first light, the marine biologist records patient observations beside the sheltered tide pool.

At dusk, the coastal engineer maps hidden channels.” (124 letters); six fresh 102–124-letter prose pairs survive an all-different content-word filter. An exact-tape-first control does close on “Able was I; I saw Elba,” but novelty and length gates exclude that known 16-letter catalogue sentence; a fresh 72-letter exact tape is also excluded because its reflected half is gibberish. Finally, a ten-clause residual solver retains a 355-letter clinic scene: “At first light Mara opens the clinic, checks the quiet generators, greets the two nurses, and records the medicine count. She carries clean water to the waiting room, labels each parcel, phones the mountain driver, updates the weather board, thanks the volunteers, and closes the ledger before dusk. After supper she inventories the blankets, answers the radio, repairs a torn notice, and leaves clear instructions for the morning shift.” All three results carry independent audits, provenance, and novelty records; none is mechanically admitted.

4 Independent verification and provenance

For every row, the verifier recomputes normalization, length, first mismatch, two-pointer equality, and a forward/reverse digest without importing the generator’s booleans. The mechanical admission vector records ASCII support, lexical form, distinctness, catalogue-family exclusion, repeated-unit and self-palindrome exclusion, and non-word-order symmetry. The registry assigns one signature to each run and rejects duplicate families before aggregation. On the authoritative snapshot the registry contains 258 unique artifacts (26 pre-

flight exclusions); the aggregate contains 4,560 rows, 78 exact rows, and zero mechanically admitted rows across 156 route summaries. Every exact row therefore has a visible reason for rejection or promotion status rather than being silently discarded.

5 Reader-facing evaluation

No candidate is called readable by the automatic diagnostics. The release package is gated until a mechanically admitted survivor exists. The planned study uses intact prose and length-matched shuffled controls, randomized blinded order, opaque item identifiers with a separate key, and a reproducible rater package. Readers rate Englishness, coherence, and grammaticality independently; two blinded coders adjudicate free-form paraphrases. The analysis is preregistered before unblinding, with the candidate admitted only if it beats the controls on the prespecified reader criteria; agreement will be reported with a preregistered reliability statistic such as Krippendorff’s alpha (Krippendorff, 2011). The current manuscript reports no human responses and makes no readability claim.

6 Limitations and next construction

The present snapshot has not yet produced a $\geq$ 100-letter candidate that passes all gates. That is a development status, not the intended contribution. The next run will change the construction state rather than repeat a sweep: the seam lane will use typed boundary resegmentation and then a fresh non-palindromic subject/verb/object frame while preserving agreement; the scene lanes will solve an object/attachment slot against the live tape; and the LM lane will propose new clause boundaries on held-out vocabulary. Each resulting surface will be rendered and audited before a reader-facing test. Once a survivor appears, the reader package and paper tables will be regenerated from its immutable provenance record.

References

- Chris Hokamp and Qun Liu. 2017. [Lexically constrained decoding for sequence generation using grid beam search](#). In *Proceedings of the 55th Annual Meeting of the Association for Computational Linguistics (ACL 2017)*, pages 1535–1546.
- Klaus Krippendorff. 2011. [Computing Krippendorff’s alpha-reliability](#). Technical report, Annenberg

School for Communication, University of Pennsylvania. 25 January 2011; literature updated 13 September 2013.

- Ximing Lu, Sean Welleck, Peter West, Liwei Jiang, Jungo Kasai, Daniel Khashabi, Ronan Le Bras, Lianhui Qin, Youngjae Yu, Rowan Zellers, Noah A. Smith, and Yejin Choi. 2022. [NeuroLogic A*esque decoding: Constrained text generation with look-ahead heuristics](#). In *Proceedings of the 2022 Conference of the North American Chapter of the Association for Computational Linguistics (NAACL 2022)*, pages 780–799.

- Alexandre Papadopoulos, Pierre Roy, Jean-Charles Régin, and François Pachet. 2015. [Generating all possible palindromes from ngram corpora](#). In *Proceedings of the Twenty-Fourth International Joint Conference on Artificial Intelligence (IJCAI 2015)*, pages 2489–2495, Buenos Aires, Argentina.

A Reproduction checklist

- Run the ten lane drivers, then
tools/audit_candidate_readability_20260915.p
and experiments/validate_experiment_novelty_20
The former recomputes exactness and mechanical
gates; the latter checks unique signatures and
required repair artifacts. The committed JSON
files under runs/ contain the rendered text,
normalized lengths, hashes, provenance, and
next repair for every row. A reader package is
generated only after the mechanical admission
count becomes nonzero.