

Columbia University: CU Later Team Reference Document

Kevin Yang, Innokentiy Kaurov, Eric Yuang Shao

May 21th 2024

Contents

Templates	2
Ken's template	2
Kevin's template	2
Kevin's Template Extended	2
Geometry	2
Strings	4
Manacher's algorithm	4
Flows	4
$O(N^2M)$, on unit networks $O(N^{1/2}M)$	4
MCMF – maximize flow, then minimize its cost. $O(Fmn)$	5
Graphs	6
Kuhn's algorithm for bipartite matching . . .	6
Hungarian algorithm for Assignment Problem	6
Dijkstra's Algorithm	6
Eulerian Cycle DFS	6
SCC and 2-SAT	6
Finding Bridges	7
Virtual Tree	7
HLD on Edges DFS	7
Centroid Decomposition	7
Math	7
Binary exponentiation	7
Matrix Exponentiation: $O(n^3 \log b)$	8
Extended Euclidean Algorithm	8
Linear Sieve	8
Gaussian Elimination	8
is_prime	9
Berlekamp-Massey	9
Calculating k-th term of a linear recurrence .	9
Partition Function	10
NTT	10
FFT	10
MIT's FFT/NTT, Polynomial mod/log/exp Template	10
Data Structures	12
Fenwick Tree	12
Lazy Propagation SegTree	13
Sparse Table	13

Suffix Array and LCP array	14
Aho Corasick Trie	14
Convex Hull Trick	15
Li-Chao Segment Tree	15
Persistent Segment Tree	15
Miscellaneous	16
Ordered Set	16
Measuring Execution Time	16
Setting Fixed D.P. Precision	16
Common Bugs and General Advice	16

Templates

Ken's template

```
1 #include <bits/stdc++.h>
2 using namespace std;
3 #define all(v) (v).begin(), (v).end()
4 typedef long long ll;
5 typedef long double ld;
6 #define pb push_back
7 #define sz(x) (int)(x).size()
8 #define fi first
9 #define se second
10 #define endl '\n'
```

Kevin's template

```
1 // paste Kaurov's Template, minus last line
2 typedef vector<int> vi;
3 typedef vector<ll> vll;
4 typedef pair<int, int> pii;
5 typedef pair<ll, ll> pll;
6 const char nl = '\n';
7 #define forn(i, n) for (int i = 0; i < int(n); i++)
8 ll k, n, m, u, v, w, x, y, z;
9 string s, t;
10
11 bool multiTest = 1;
12 void solve(int tt){
13 }
14
15 int main(){
16     ios::sync_with_stdio(0);cin.tie(0);cout.tie(0);
17     cout<<fixed<< setprecision(14);
18
19     int t = 1;
20     if (multiTest) cin >> t;
21     forn(ii, t) solve(ii);
22 }
```

Kevin's Template Extended

- to type after the start of the contest

```
1 typedef pair<double, double> pdd;
2 const ld PI = acos(-1);
3 const ll mod7 = 1e9 + 7;
4 const ll mod9 = 998244353;
5 const ll INF = 2*1024*1024*1023;
6 #pragma GCC target("avx2,bmi,bmi2,lzcnt,popcnt")
7 #include <ext/pb_ds/assoc_container.hpp>
8 #include <ext/pb_ds/tree_policy.hpp>
9 using namespace __gnu_pbds;
10 template<class T> using ordered_set = tree<T, null_type,
11     ⇨ less<T>, rb_tree_tag,
12     ⇨ tree_order_statistics_node_update>;
13 vi d4x = {1, 0, -1, 0};
```

```
12 vi d4y = {0, 1, 0, -1};
13 vi d8x = {1, 0, -1, 0, 1, 1, -1, -1};
14 vi d8y = {0, 1, 0, -1, 1, -1, 1, -1};
15 mt19937
16     ⇨ rng(chrono::steady_clock::now().time_since_epoch().count())
```

Geometry

- Basic stuff

```
1 template<typename T>
2 struct TPoint{
3     T x, y;
4     int id;
5     static constexpr T eps = static_cast<T>(1e-9);
6     TPoint() : x(0), y(0), id(-1) {}
7     TPoint(const T& x_, const T& y_) : x(x_), y(y_),
8     ⇨ id(-1) {}
9     TPoint(const T& x_, const T& y_, const int id_) :
10     ⇨ x(x_), y(y_), id(id_) {}
11
12     TPoint operator + (const TPoint& rhs) const {
13         return TPoint(x + rhs.x, y + rhs.y);
14     }
15     TPoint operator - (const TPoint& rhs) const {
16         return TPoint(x - rhs.x, y - rhs.y);
17     }
18     TPoint operator * (const T& rhs) const {
19         return TPoint(x * rhs, y * rhs);
20     }
21     TPoint operator / (const T& rhs) const {
22         return TPoint(x / rhs, y / rhs);
23     }
24     TPoint ort() const {
25         return TPoint(-y, x);
26     }
27     T abs2() const {
28         return x * x + y * y;
29     }
30 };
31 template<typename T>
32 bool operator< (TPoint<T>& A, TPoint<T>& B){
33     return make_pair(A.x, A.y) < make_pair(B.x, B.y);
34 }
35 template<typename T>
36 bool operator==(TPoint<T>& A, TPoint<T>& B){
37     return abs(A.x - B.x) <= TPoint<T>::eps && abs(A.y -
38     ⇨ B.y) <= TPoint<T>::eps;
39 }
40 template<typename T>
41 struct TLine{
42     T a, b, c;
43     TLine() : a(0), b(0), c(0) {}
44     TLine(const T& a_, const T& b_, const T& c_) : a(a_),
45     ⇨ b(b_), c(c_) {}
46     TLine(const TPoint<T>& p1, const TPoint<T>& p2){
47         a = p1.y - p2.y;
```

```
44     b = p2.x - p1.x;
45     c = -a * p1.x - b * p1.y;
46 }
47 };
48 template<typename T>
49 T det(const T& a1, const T& a2, const T& a21, const T&
50     ⇨ a22){
51     return a1 * a22 - a12 * a21;
52 }
53 template<typename T>
54 T sq(const T& a){
55     return a * a;
56 }
57 template<typename T>
58 T smul(const TPoint<T>& a, const TPoint<T>& b){
59     return a.x * b.x + a.y * b.y;
60 }
61 template<typename T>
62 T vmul(const TPoint<T>& a, const TPoint<T>& b){
63     return det(a.x, a.y, b.x, b.y);
64 }
65 template<typename T>
66 bool parallel(const TLine<T>& l1, const TLine<T>& l2){
67     return abs(vmul(TPoint<T>(l1.a, l1.b), TPoint<T>(l2.a,
68     ⇨ l2.b))) <= TPoint<T>::eps;
69 }
70 template<typename T>
71 bool equivalent(const TLine<T>& l1, const TLine<T>& l2){
72     return parallel(l1, l2) &&
73     abs(det(l1.b, l1.c, l2.b, l2.c)) <= TPoint<T>::eps &&
74     abs(det(l1.a, l1.c, l2.a, l2.c)) <= TPoint<T>::eps;
75 }
```

- Intersection

```
1 template<typename T>
2 TPoint<T> intersection(const TLine<T>& l1, const
3     ⇨ TLine<T>& l2){
4     return TPoint<T>(
5     det(-l1.c, l1.b, -l2.c, l2.b) / det(l1.a, l1.b,
6     ⇨ l2.a, l2.b),
7     det(l1.a, -l1.c, l2.a, -l2.c) / det(l1.a, l1.b,
8     ⇨ l2.a, l2.b)
9     );
10 }
11 template<typename T>
12 int sign(const T& x){
13     if (abs(x) <= TPoint<T>::eps) return 0;
14     return x > 0? +1 : -1;
15 }
```

- Area

```
1 template<typename T>
2 T area(const vector<TPoint<T>>& pts){
3     int n = sz(pts);
4     T ans = 0;
5     for (int i = 0; i < n; i++){
6         ans += vmul(pts[i], pts[(i + 1) % n]);
```

```

7     }
8     return abs(ans) / 2;
9 }
10 template<typename T>
11 T dist_pp(const TPoint<T>& a, const TPoint<T>& b){
12     return sqrt(sq(a.x - b.x) + sq(a.y - b.y));
13 }
14 template<typename T>
15 TLine<T> perp_line(const TLine<T>& l, const TPoint<T>&
    ↪ p){
16     T na = -l.b, nb = l.a, nc = - na * p.x - nb * p.y;
17     return TLine<T>(na, nb, nc);
18 }

    • Projection

1 template<typename T>
2 TPoint<T> projection(const TPoint<T>& p, const TLine<T>&
    ↪ l){
3     return intersection(l, perp_line(l, p));
4 }
5 template<typename T>
6 T dist_pl(const TPoint<T>& p, const TLine<T>& l){
7     return dist_pp(p, projection(p, l));
8 }
9 template<typename T>
10 struct TRay{
11     TLine<T> l;
12     TPoint<T> start, dirvec;
13     TRay() : l(), start(), dirvec() {}
14     TRay(const TPoint<T>& p1, const TPoint<T>& p2){
15         l = TLine<T>(p1, p2);
16         start = p1, dirvec = p2 - p1;
17     }
18 };
19 template<typename T>
20 bool is_on_line(const TPoint<T>& p, const TLine<T>& l){
21     return abs(l.a * p.x + l.b * p.y + l.c) <=
    ↪ TPoint<T>::eps;
22 }
23 template<typename T>
24 bool is_on_ray(const TPoint<T>& p, const TRay<T>& r){
25     if (is_on_line(p, r.l)){
26         return sign(smul(r.dirvec, TPoint<T>(p - r.start)))
    ↪ != -1;
27     }
28     else return false;
29 }
30 template<typename T>
31 bool is_on_seg(const TPoint<T>& P, const TPoint<T>& A,
    ↪ const TPoint<T>& B){
32     return is_on_ray(P, TRay<T>(A, B)) && is_on_ray(P,
    ↪ TRay<T>(B, A));
33 }
34 template<typename T>
35 T dist_pr(const TPoint<T>& P, const TRay<T>& R){
36     auto H = projection(P, R.l);
37     return is_on_ray(H, R)? dist_pp(P, H) : dist_pp(P,
    ↪ R.start);
38 }
39 template<typename T>
40 T dist_ps(const TPoint<T>& P, const TPoint<T>& A, const
    ↪ TPoint<T>& B){
41     auto H = projection(P, TLine<T>(A, B));
42     if (is_on_seg(H, A, B)) return dist_pp(P, H);
43     else return min(dist_pp(P, A), dist_pp(P, B));
44 }

    • acw

1 template<typename T>
2 bool acw(const TPoint<T>& A, const TPoint<T>& B){
3     T mul = vmul(A, B);
4     return mul > 0 || abs(mul) <= TPoint<T>::eps;
5 }

    • cw

1 template<typename T>
2 bool cw(const TPoint<T>& A, const TPoint<T>& B){
3     T mul = vmul(A, B);
4     return mul < 0 || abs(mul) <= TPoint<T>::eps;
5 }

    • Convex Hull

1 template<typename T>
2 vector<TPoint<T>> convex_hull(vector<TPoint<T>> pts){
3     sort(all(pts));
4     pts.erase(unique(all(pts)), pts.end());
5     vector<TPoint<T>> up, down;
6     for (auto p : pts){
7         while (sz(up) > 1 && acw(up.end()[-1] -
    ↪ up.end()[-2], p - up.end()[-2])) up.pop_back();
8         while (sz(down) > 1 && cw(down.end()[-1] -
    ↪ down.end()[-2], p - down.end()[-2]))
    ↪ down.pop_back();
9         up.pb(p), down.pb(p);
10    }
11    for (int i = sz(up) - 2; i >= 1; i--) down.pb(up[i]);
12    return down;
13 }

    • in_triangle

1 template<typename T>
2 bool in_triangle(TPoint<T>& P, TPoint<T>& A, TPoint<T>&
    ↪ B, TPoint<T>& C){
3     if (is_on_seg(P, A, B) || is_on_seg(P, B, C) ||
    ↪ is_on_seg(P, C, A)) return true;
4     return cw(P - A, B - A) == cw(P - B, C - B) &&
    ↪ cw(P - A, B - A) == cw(P - C, A - C);
5 }

    • prep_convex_poly

1 template<typename T>
2 void prep_convex_poly(vector<TPoint<T>>& pts){
3     rotate(pts.begin(), min_element(all(pts)), pts.end());
4 }

    • in_convex_poly:

1 // 0 - Outside, 1 - Exclusively Inside, 2 - On the
    ↪ Border
2 template<typename T>
3 int in_convex_poly(TPoint<T>& p, vector<TPoint<T>>&
    ↪ pts){
4     int n = sz(pts);
5     if (!n) return 0;
6     if (n <= 2) return is_on_seg(p, pts[0], pts.back());
7     int l = 1, r = n - 1;
8     while (r - l > 1){
9         int mid = (l + r) / 2;
10        if (acw(pts[mid] - pts[0], p - pts[0])) l = mid;
11        else r = mid;
12    }
13    if (!in_triangle(p, pts[0], pts[l], pts[l + 1]))
    ↪ return 0;
14    if (is_on_seg(p, pts[l], pts[l + 1]) ||
    ↪ is_on_seg(p, pts[0], pts.back()) ||
    ↪ is_on_seg(p, pts[0], pts[l]))
15        return 2;
16    return 1;
17 }

    • in_simple_poly

1 // 0 - Outside, 1 - Exclusively Inside, 2 - On the
    ↪ Border
2 template<typename T>
3 int in_simple_poly(TPoint<T> p, vector<TPoint<T>>& pts){
4     int n = sz(pts);
5     bool res = 0;
6     for (int i = 0; i < n; i++){
7         auto a = pts[i], b = pts[(i + 1) % n];
8         if (is_on_seg(p, a, b)) return 2;
9         if (((a.y > p.y) - (b.y > p.y)) * vmul(b - p, a - p)
    ↪ > TPoint<T>::eps){
10             res ^= 1;
11         }
12    }
13    return res;
14 }

    • minkowski_rotate

1 template<typename T>
2 void minkowski_rotate(vector<TPoint<T>>& P){
3     int pos = 0;
4     for (int i = 1; i < sz(P); i++){
5         if (abs(P[i].y - P[pos].y) <= TPoint<T>::eps){
6             if (P[i].x < P[pos].x) pos = i;
7         }
8         else if (P[i].y < P[pos].y) pos = i;
9     }
10    rotate(P.begin(), P.begin() + pos, P.end());
11 }

```

• minkowski_sum

```

1 // P and Q are strictly convex, points given in
  ↪ counterclockwise order
2 template<typename T>
3 vector<TPoint<T>> minkowski_sum(vector<TPoint<T>> P,
  ↪ vector<TPoint<T>> Q){
4     minkowski_rotate(P);
5     minkowski_rotate(Q);
6     P.pb(P[0]);
7     Q.pb(Q[0]);
8     vector<TPoint<T>> ans;
9     int i = 0, j = 0;
10    while (i < sz(P) - 1 || j < sz(Q) - 1){
11        ans.pb(P[i] + Q[j]);
12        T curmul;
13        if (i == sz(P) - 1) curmul = -1;
14        else if (j == sz(Q) - 1) curmul = +1;
15        else curmul = vmul(P[i + 1] - P[i], Q[j + 1] -
  ↪ Q[j]);
16        if (abs(curmul) < TPoint<T>::eps || curmul > 0) i++;
17        if (abs(curmul) < TPoint<T>::eps || curmul < 0) j++;
18    }
19    return ans;
20 }
21 using Point = TPoint<ll>; using Line = TLine<ll>; using
  ↪ Ray = TRay<ll>; const ld PI = acos(-1);

```

Strings

```

1 vector<int> prefix_function(string s){
2     int n = sz(s);
3     vector<int> pi(n);
4     for (int i = 1; i < n; i++){
5         int k = pi[i - 1];
6         while (k > 0 && s[i] != s[k]){
7             k = pi[k - 1];
8         }
9         pi[i] = k + (s[i] == s[k]);
10    }
11    return pi;
12 }
13 vector<int> kmp(string s, string k){
14     string st = k + "#" + s;
15     vector<int> res;
16     auto pi = pf(st);
17     for (int i = 0; i < sz(st); i++){
18         if (pi[i] == sz(k)){
19             res.pb(i - 2 * sz(k));
20         }
21     }
22     return res;
23 }
24 vector<int> z_function(string s){
25     int n = sz(s);
26     vector<int> z(n);
27     int l = 0, r = 0;

```

```

28     for (int i = 1; i < n; i++){
29         if (r >= i) z[i] = min(z[i - 1], r - i + 1);
30         while (i + z[i] < n && s[z[i]] == s[i + z[i]]){
31             z[i]++;
32         }
33         if (i + z[i] - 1 > r){
34             l = i, r = i + z[i] - 1;
35         }
36     }
37     return z;
38 }

```

Manacher's algorithm

```

1 string longest_palindrome(string& s) {
2     // init "abc" -> "~$a#b#c$"
3     vector<char> t{'~', '#'};
4     for (char c : s) t.push_back(c), t.push_back('#');
5     t.push_back('$');
6     // manacher
7     int n = t.size(), r = 0, c = 0;
8     vector<int> p(n, 0);
9     for (int i = 1; i < n - 1; i++) {
10        if (i < r + c) p[i] = min(p[2 * c - i], r + c - i);
11        while (t[i + p[i] + 1] == t[i - p[i] - 1]) p[i]++;
12        if (i + p[i] > r + c) r = p[i], c = i;
13    }
14    // s[i] -> p[2 * i + 2] (even), p[2 * i + 2] (odd)
15    // output answer
16    int index = 0;
17    for (int i = 0; i < n; i++)
18        if (p[index] < p[i]) index = i;
19    return s.substr((index - p[index]) / 2, p[index]);
20 }

```

Flows

$O(N^2M)$, on unit networks $O(N^{1/2}M)$

```

1 struct FlowEdge {
2     int v, u;
3     ll cap, flow = 0;
4     FlowEdge(int v, int u, ll cap) : v(v), u(u),
  ↪ cap(cap) {}
5 };
6 struct Dinic {
7     const ll flow_inf = 1e18;
8     vector<FlowEdge> edges;
9     vector<vector<int>> adj;
10    int n, m = 0;
11    int s, t;
12    vector<int> level, ptr;
13    queue<int> q;
14    Dinic(int n, int s, int t) : n(n), s(s), t(t) {
15        adj.resize(n);
16        level.resize(n);

```

```

17        ptr.resize(n);
18    }
19    void add_edge(int v, int u, ll cap) {
20        edges.emplace_back(v, u, cap);
21        edges.emplace_back(u, v, 0);
22        adj[v].push_back(m);
23        adj[u].push_back(m + 1);
24        m += 2;
25    }
26    bool bfs() {
27        while (!q.empty()) {
28            int v = q.front();
29            q.pop();
30            for (int id : adj[v]) {
31                if (edges[id].cap - edges[id].flow < 1)
32                    continue;
33                if (level[edges[id].u] != -1)
34                    continue;
35                level[edges[id].u] = level[v] + 1;
36                q.push(edges[id].u);
37            }
38        }
39        return level[t] != -1;
40    }
41    ll dfs(int v, ll pushed) {
42        if (pushed == 0)
43            return 0;
44        if (v == t)
45            return pushed;
46        for (int& cid = ptr[v]; cid <
  ↪ (int)adj[v].size(); cid++) {
47            int id = adj[v][cid];
48            int u = edges[id].u;
49            if (level[v] + 1 != level[u] ||
  ↪ edges[id].cap - edges[id].flow < 1)
50                continue;
51            ll tr = dfs(u, min(pushed, edges[id].cap -
  ↪ edges[id].flow));
52            if (tr == 0)
53                continue;
54            edges[id].flow += tr;
55            edges[id ^ 1].flow -= tr;
56            return tr;
57        }
58        return 0;
59    }
60    ll flow() {
61        ll f = 0;
62        while (true) {
63            fill(level.begin(), level.end(), -1);
64            level[s] = 0;
65            q.push(s);
66            if (!bfs())
67                break;
68            fill(ptr.begin(), ptr.end(), 0);
69            while (ll pushed = dfs(s, flow_inf)) {
70                f += pushed;
71            }

```

```

72     }
73     return f;
74 }
75 };
76 // To recover flow through original edges: iterate over
    even indices in edges.

```

MCMF – maximize flow, then minimize its cost. $O(Fmn)$.

```

1  #include <ext/pb_ds/priority_queue.hpp>
2  template <typename T, typename C>
3  class MCMF {
4  public:
5      static constexpr T eps = (T) 1e-9;
6
7      struct edge {
8          int from;
9          int to;
10         T c;
11         T f;
12         C cost;
13     };
14
15     int n;
16     vector<vector<int>> g;
17     vector<edge> edges;
18     vector<C> d;
19     vector<C> pot;
20     __gnu_pbds::priority_queue<pair<C, int>> q;
21     vector<typename decltpe(q)::point_iterator> its;
22     vector<int> pe;
23     const C INF_C = numeric_limits<C>::max() / 2;
24
25     explicit MCMF(int n_) : n(n_), g(n), d(n), pot(n, 0) {}
26     ↪ its(n), pe(n) {}
27
28     int add(int from, int to, T forward_cap, C edge_cost,
29     ↪ T backward_cap = 0) {
30         assert(0 <= from && from < n && 0 <= to && to < n);
31         assert(forward_cap >= 0 && backward_cap >= 0);
32         int id = static_cast<int>(edges.size());
33         g[from].push_back(id);
34         edges.push_back({from, to, forward_cap, 0,
35     ↪ edge_cost});
36         g[to].push_back(id + 1);
37         edges.push_back({to, from, backward_cap, 0,
38     ↪ -edge_cost});
39         return id;
40     }
41
42     void expath(int st) {
43         fill(d.begin(), d.end(), INF_C);
44         q.clear();
45         fill(its.begin(), its.end(), q.end());
46         its[st] = q.push({pot[st], st});
47         d[st] = 0;

```

```

44     while (!q.empty()) {
45         int i = q.top().second;
46         q.pop();
47         its[i] = q.end();
48         for (int id : g[i]) {
49             const edge &e = edges[id];
50             int j = e.to;
51             if (e.c - e.f > eps && d[i] + e.cost < d[j]) {
52                 d[j] = d[i] + e.cost;
53                 pe[j] = id;
54                 if (its[j] == q.end()) {
55                     its[j] = q.push({pot[j] - d[j], j});
56                 } else {
57                     q.modify(its[j], {pot[j] - d[j], j});
58                 }
59             }
60         }
61         swap(d, pot);
62     }
63 }
64
65 pair<T, C> max_flow(int st, int fin) {
66     T flow = 0;
67     C cost = 0;
68     bool ok = true;
69     for (auto& e : edges) {
70         if (e.c - e.f > eps && e.cost + pot[e.from] -
71     ↪ pot[e.to] < 0) {
72             ok = false;
73             break;
74         }
75     }
76     if (ok) {
77         expath(st);
78     } else {
79         vector<int> deg(n, 0);
80         for (int i = 0; i < n; i++) {
81             for (int eid : g[i]) {
82                 auto& e = edges[eid];
83                 if (e.c - e.f > eps) {
84                     deg[e.to] += 1;
85                 }
86             }
87         }
88         vector<int> que;
89         for (int i = 0; i < n; i++) {
90             if (deg[i] == 0) {
91                 que.push_back(i);
92             }
93         }
94         for (int b = 0; b < (int) que.size(); b++) {
95             for (int eid : g[que[b]]) {
96                 auto& e = edges[eid];
97                 if (e.c - e.f > eps) {
98                     deg[e.to] -= 1;
99                     if (deg[e.to] == 0) {
100                         que.push_back(e.to);
101                     }
102                 }
103             }
104         }
105     }
106     while (pot[fin] < INF_C) {
107         T push = numeric_limits<T>::max();
108         int v = fin;
109         while (v != st) {
110             const edge &e = edges[pe[v]];
111             push = min(push, e.c - e.f);
112             v = e.from;
113         }
114         v = fin;
115         while (v != st) {
116             edge &e = edges[pe[v]];
117             e.f += push;
118             edge &back = edges[pe[v] ^ 1];
119             back.f -= push;
120             v = e.from;
121         }
122         flow += push;
123     }
124 }

```

```

101     }
102 }
103 }
104 fill(pot.begin(), pot.end(), INF_C);
105 pot[st] = 0;
106 if (static_cast<int>(que.size()) == n) {
107     for (int v : que) {
108         if (pot[v] < INF_C) {
109             for (int eid : g[v]) {
110                 auto& e = edges[eid];
111                 if (e.c - e.f > eps) {
112                     if (pot[v] + e.cost < pot[e.to]) {
113                         pot[e.to] = pot[v] + e.cost;
114                         pe[e.to] = eid;
115                     }
116                 }
117             }
118         }
119     }
120 } else {
121     que.assign(1, st);
122     vector<bool> in_queue(n, false);
123     in_queue[st] = true;
124     for (int b = 0; b < (int) que.size(); b++) {
125         int i = que[b];
126         in_queue[i] = false;
127         for (int id : g[i]) {
128             const edge &e = edges[id];
129             if (e.c - e.f > eps && pot[i] + e.cost <
130     ↪ pot[e.to]) {
131                 pot[e.to] = pot[i] + e.cost;
132                 pe[e.to] = id;
133                 if (!in_queue[e.to]) {
134                     que.push_back(e.to);
135                     in_queue[e.to] = true;
136                 }
137             }
138         }
139     }
140 }
141 while (pot[fin] < INF_C) {
142     T push = numeric_limits<T>::max();
143     int v = fin;
144     while (v != st) {
145         const edge &e = edges[pe[v]];
146         push = min(push, e.c - e.f);
147         v = e.from;
148     }
149     v = fin;
150     while (v != st) {
151         edge &e = edges[pe[v]];
152         e.f += push;
153         edge &back = edges[pe[v] ^ 1];
154         back.f -= push;
155         v = e.from;
156     }
157     flow += push;

```

```

158     cost += push * pot[fin];
159     expath(st);
160 }
161 return {flow, cost};
162 }
163 };
164
165 // Examples: MCMF<int, int> g(n); g.add(u,v,c,w,0);
166 // To recover flow through original edges: iterate over
    ↪ even indices in edges.

```

Graphs

Kuhn's algorithm for bipartite matching

```

1  /*
2  The graph is split into 2 halves of n1 and n2 vertices.
3  Complexity: O(n1 * m). Usually runs much faster. MUCH
    ↪ FASTER!!!
4  */
5  const int N = 305;
6
7  vector<int> g[N]; // Stores edges from left half to
    ↪ right.
8  bool used[N]; // Stores if vertex from left half is
    ↪ used.
9  int mt[N]; // For every vertex in right half, stores to
    ↪ which vertex in left half it's matched (-1 if not
    ↪ matched).
10
11 bool try_dfs(int v){
12     if (used[v]) return false;
13     used[v] = 1;
14     for (auto u : g[v]){
15         if (mt[u] == -1 || try_dfs(mt[u])){
16             mt[u] = v;
17             return true;
18         }
19     }
20     return false;
21 }
22
23 int main(){
24     // .....
25     for (int i = 1; i <= n2; i++) mt[i] = -1;
26     for (int i = 1; i <= n1; i++) used[i] = 0;
27     for (int i = 1; i <= n1; i++){
28         if (try_dfs(i)){
29             for (int j = 1; j <= n1; j++) used[j] = 0;
30         }
31     }
32     vector<pair<int, int>> ans;
33     for (int i = 1; i <= n2; i++){
34         if (mt[i] != -1) ans.pb({mt[i], i});
35     }
36 }

```

```

37
38 // Finding maximal independent set: size = # of nodes -
    ↪ # of edges in matching.
39 // To construct: launch Kuhn-like DFS from unmatched
    ↪ nodes in the left half.
40 // Independent set = visited nodes in left half +
    ↪ unvisited in right half.
41 // Finding minimal vertex cover: complement of maximal
    ↪ independent set.

```

Hungarian algorithm for Assignment Problem

- Given a 1-indexed $(n \times m)$ matrix A , select a number in each row such that each column has at most 1 number selected, and the sum of the selected numbers is minimized.

```

1  int INF = 1e9; // constant greater than any number in
    ↪ the matrix
2  vector<int> u(n+1), v(m+1), p(m+1), way(m+1);
3  for (int i=1; i<=n; ++i) {
4      p[0] = i;
5      int j0 = 0;
6      vector<int> minv (m+1, INF);
7      vector<bool> used (m+1, false);
8      do {
9          used[j0] = true;
10         int i0 = p[j0], delta = INF, j1;
11         for (int j=1; j<=m; ++j)
12             if (!used[j]) {
13                 int cur = A[i0][j]-u[i0]-v[j];
14                 if (cur < minv[j])
15                     minv[j] = cur, way[j] = j0;
16                 if (minv[j] < delta)
17                     delta = minv[j], j1 = j;
18             }
19         for (int j=j0; j<=m; ++j)
20             if (used[j])
21                 u[p[j]] += delta, v[j] -= delta;
22             else
23                 minv[j] -= delta;
24         j0 = j1;
25     } while (p[j0] != 0);
26     do {
27         int j1 = way[j0];
28         p[j0] = p[j1];
29         j0 = j1;
30     } while (j0);
31 }
32 vector<int> ans (n+1); // ans[i] stores the column
    ↪ selected for row i
33 for (int j=1; j<=m; ++j)
34     ans[p[j]] = j;
35 int cost = -v[0]; // the total cost of the matching

```

Dijkstra's Algorithm

```

1  priority_queue<pair<ll, ll>, vector<pair<ll, ll>>,
    ↪ greater<pair<ll, ll>>> q;
2  dist[start] = 0;
3  q.push({0, start});
4  while (!q.empty()){
5      auto [d, v] = q.top();
6      q.pop();
7      if (d != dist[v]) continue;
8      for (auto [u, w] : g[v]){
9          if (dist[u] > dist[v] + w){
10             dist[u] = dist[v] + w;
11             q.push({dist[u], u});
12         }
13     }
14 }

```

Eulerian Cycle DFS

```

1  void dfs(int v){
2      while (!g[v].empty()){
3          int u = g[v].back();
4          g[v].pop_back();
5          dfs(u);
6          ans.pb(v);
7      }
8  }

```

SCC and 2-SAT

```

1  void scc(vector<vector<int>>& g, int* idx) {
2      int n = g.size(), ct = 0;
3      int out[n];
4      vector<int> ginv[n];
5      memset(out, -1, sizeof out);
6      memset(idx, -1, n * sizeof(int));
7      function<void(int)> dfs = [&](int cur) {
8          out[cur] = INT_MAX;
9          for(int v : g[cur]) {
10             ginv[v].push_back(cur);
11             if(out[v] == -1) dfs(v);
12         }
13         ct++; out[cur] = ct;
14     };
15     vector<int> order;
16     for(int i = 0; i < n; i++) {
17         order.push_back(i);
18         if(out[i] == -1) dfs(i);
19     }
20     sort(order.begin(), order.end(), [&](int& u, int& v) {
21         return out[u] > out[v];
22     });
23     ct = 0;
24     stack<int> s;
25     auto dfs2 = [&](int start) {

```



```

26     s.push(start);
27     while(!s.empty()) {
28         int cur = s.top();
29         s.pop();
30         idx[cur] = ct;
31         for(int v : ginv[cur])
32             if(idx[v] == -1) s.push(v);
33     }
34 };
35 for(int v : order) {
36     if(idx[v] == -1) {
37         dfs2(v);
38         ct++;
39     }
40 }
41 }
42
43 // 0 => impossible, 1 => possible
44 pair<int, vector<int>> sat2(int n, vector<pair<int, int>>&
    ↪ clauses) {
45     vector<int> ans(n);
46     vector<vector<int>> g(2*n + 1);
47     for(auto [x, y] : clauses) {
48         x = x < 0 ? -x + n : x;
49         y = y < 0 ? -y + n : y;
50         int nx = x <= n ? x + n : x - n;
51         int ny = y <= n ? y + n : y - n;
52         g[nx].push_back(y);
53         g[ny].push_back(x);
54     }
55     int idx[2*n + 1];
56     scc(g, idx);
57     for(int i = 1; i <= n; i++) {
58         if(idx[i] == idx[i + n]) return {0, {}};
59         ans[i - 1] = idx[i + n] < idx[i];
60     }
61     return {1, ans};
62 }

```

Finding Bridges

```

1  /*
2  Bridges.
3  Results are stored in a map "is_bridge".
4  For each connected component, call "dfs(starting vertex,
    ↪ starting vertex)".
5  */
6  const int N = 2e5 + 10; // Careful with the constant!
7
8  vector<int> g[N];
9  int tin[N], fup[N], timer;
10 map<pair<int, int>, bool> is_bridge;
11
12 void dfs(int v, int p){
13     tin[v] = ++timer;
14     fup[v] = tin[v];
15     for (auto u : g[v]){
16         if (!tin[u]){

```

```

17         dfs(u, v);
18         if (fup[u] > tin[v]){
19             is_bridge[{u, v}] = is_bridge[{v, u}] = true;
20         }
21         fup[v] = min(fup[v], fup[u]);
22     }
23     else{
24         if (u != p) fup[v] = min(fup[v], tin[u]);
25     }
26 }
27 }

```

Virtual Tree

```

1 // order stores the nodes in the queried set
2 sort(all(order), [&] (int u, int v){return tin[u] <
    ↪ tin[v];});
3 int m = sz(order);
4 for (int i = 1; i < m; i++){
5     order.pb(lca(order[i], order[i - 1]));
6 }
7 sort(all(order), [&] (int u, int v){return tin[u] <
    ↪ tin[v];});
8 order.erase(unique(all(order)), order.end());
9 vector<int> stk{order[0]};
10 for (int i = 1; i < sz(order); i++){
11     int v = order[i];
12     while (tout[stk.back()] < tout[v]) stk.pop_back();
13     int u = stk.back();
14     vg[u].pb({v, dep[v] - dep[u]});
15     stk.pb(v);
16 }

```

HLD on Edges DFS

```

1 void dfs1(int v, int p, int d){
2     par[v] = p;
3     for (auto e : g[v]){
4         if (e.fi == p){
5             g[v].erase(find(all(g[v]), e));
6             break;
7         }
8     }
9     dep[v] = d;
10    sz[v] = 1;
11    for (auto [u, c] : g[v]){
12        dfs1(u, v, d + 1);
13        sz[v] += sz[u];
14    }
15    if (!g[v].empty()) iter_swap(g[v].begin(),
    ↪ max_element(all(g[v]), comp));
16 }
17 void dfs2(int v, int rt, int c){
18     pos[v] = sz(a);
19     a.pb(c);
20     root[v] = rt;
21     for (int i = 0; i < sz(g[v]); i++){

```

```

22     auto [u, c] = g[v][i];
23     if (!i) dfs2(u, rt, c);
24     else dfs2(u, u, c);
25 }
26 }
27 int getans(int u, int v){
28     int res = 0;
29     for (; root[u] != root[v]; v = par[root[v]]){
30         if (dep[root[u]] > dep[root[v]]) swap(u, v);
31         res = max(res, rmq(0, 0, n - 1, pos[root[v]],
    ↪ pos[v]));
32     }
33     if (pos[u] > pos[v]) swap(u, v);
34     return max(res, rmq(0, 0, n - 1, pos[u] + 1, pos[v]));
35 }

```

Centroid Decomposition

```

1 vector<char> res(n), seen(n), sz(n);
2 function<int(int, int)> get_size = [&](int node, int fa)
    ↪ {
3     sz[node] = 1;
4     for (auto& ne : g[node]) {
5         if (ne == fa || seen[ne]) continue;
6         sz[node] += get_size(ne, node);
7     }
8     return sz[node];
9 };
10 function<int(int, int, int)> find_centroid = [&](int
    ↪ node, int fa, int t) {
11     for (auto& ne : g[node])
12         if (ne != fa && !seen[ne] && sz[ne] > t / 2) return
    ↪ find_centroid(ne, node, t);
13     return node;
14 };
15 function<void(int, char)> solve = [&](int node, char
    ↪ cur) {
16     get_size(node, -1); auto c = find_centroid(node, -1,
    ↪ sz[node]);
17     seen[c] = 1, res[c] = cur;
18     for (auto& ne : g[c]) {
19         if (seen[ne]) continue;
20         solve(ne, char(c + 1)); // we can pass c here to
    ↪ build tree
21     }
22 };

```

Math

Binary exponentiation

```

1 ll power(ll a, ll b){
2     ll res = 1;
3     for (; b; a = a * a % MOD, b >>= 1){

```



```

4     if (b & 1) res = res * a % MOD;
5 }
6 return res;
7 }

```

Matrix Exponentiation: $O(n^3 \log b)$

```

1 const int N = 100, MOD = 1e9 + 7;
2
3 struct matrix{
4     ll m[N][N];
5     int n;
6     matrix(){
7         n = N;
8         memset(m, 0, sizeof(m));
9     };
10    matrix(int n){
11        n = n;
12        memset(m, 0, sizeof(m));
13    };
14    matrix(int n_, ll val){
15        n = n_;
16        memset(m, 0, sizeof(m));
17        for (int i = 0; i < n; i++) m[i][i] = val;
18    };
19
20    matrix operator* (matrix oth){
21        matrix res(n);
22        for (int i = 0; i < n; i++){
23            for (int j = 0; j < n; j++){
24                for (int k = 0; k < n; k++){
25                    res.m[i][j] = (res.m[i][j] + m[i][k] *
↳ oth.m[k][j]) % MOD;
26                }
27            }
28        }
29        return res;
30    }
31 };
32
33 matrix power(matrix a, ll b){
34     matrix res(a.n, 1);
35     for (; b; a = a * a, b >>= 1){
36         if (b & 1) res = res * a;
37     }
38     return res;
39 }

```

Extended Euclidean Algorithm

```

1 // gives (x, y) for ax + by = g
2 // solutions given (x0, y0): a(x0 + kb/g) + b(y0 - ka/g)
↳ = g
3 int gcd(int a, int b, int& x, int& y) {
4     x = 1, y = 0; int sum1 = a;
5     int x2 = 0, y2 = 1, sum2 = b;
6     while (sum2) {

```

```

7     int q = sum1 / sum2;
8     tie(x, x2) = make_tuple(x2, x - q * x2);
9     tie(y, y2) = make_tuple(y2, y - q * y2);
10    tie(sum1, sum2) = make_tuple(sum2, sum1 - q * sum2);
11 }
12 return sum1;
13 }

```

Linear Sieve

• Mobius Function

```

1 vector<int> prime;
2 bool is_composite[MAX_N];
3 int mu[MAX_N];
4
5 void sieve(int n){
6     fill(is_composite, is_composite + n, 0);
7     mu[1] = 1;
8     for (int i = 2; i < n; i++){
9         if (!is_composite[i]){
10            prime.push_back(i);
11            mu[i] = -1; //i is prime
12        }
13        for (int j = 0; j < prime.size() && i * prime[j] < n;
↳ j++){
14            is_composite[i * prime[j]] = true;
15            if (i % prime[j] == 0){
16                mu[i * prime[j]] = 0; //prime[j] divides i
17                break;
18            } else {
19                mu[i * prime[j]] = -mu[i]; //prime[j] does not
↳ divide i
20            }
21        }
22    }
23 }

```

• Euler's Totient Function

```

1 vector<int> prime;
2 bool is_composite[MAX_N];
3 int phi[MAX_N];
4
5 void sieve(int n){
6     fill(is_composite, is_composite + n, 0);
7     phi[1] = 1;
8     for (int i = 2; i < n; i++){
9         if (!is_composite[i]){
10            prime.push_back(i);
11            phi[i] = i - 1; //i is prime
12        }
13        for (int j = 0; j < prime.size() && i * prime[j] < n;
↳ j++){
14            is_composite[i * prime[j]] = true;
15            if (i % prime[j] == 0){
16                phi[i * prime[j]] = phi[i] * prime[j]; //prime[j]
↳ divides i

```

```

17        break;
18    } else {
19        phi[i * prime[j]] = phi[i] * phi[prime[j]];
↳ //prime[j] does not divide i
20    }
21 }
22 }
23 }

```

Gaussian Elimination

```

1 bool is_0(Z v) { return v.x == 0; }
2 Z abs(Z v) { return v; }
3 bool is_0(double v) { return abs(v) < 1e-9; }
4
5 // 1 => unique solution, 0 => no solution, -1 =>
↳ multiple solutions
6 template <typename T>
7 int gaussian_elimination(vector<vector<T>> &a, int
↳ limit) {
8     if (a.empty() || a[0].empty()) return -1;
9     int h = (int)a.size(), w = (int)a[0].size(), r = 0;
10    for (int c = 0; c < limit; c++) {
11        int id = -1;
12        for (int i = r; i < h; i++) {
13            if (!is_0(a[i][c]) && (id == -1 || abs(a[id][c]) <
↳ abs(a[i][c]))) {
14                id = i;
15            }
16        }
17        if (id == -1) continue;
18        if (id > r) {
19            swap(a[r], a[id]);
20            for (int j = c; j < w; j++) a[id][j] = -a[id][j];
21        }
22        vector<int> nonzero;
23        for (int j = c; j < w; j++) {
24            if (!is_0(a[r][j])) nonzero.push_back(j);
25        }
26        T inv_a = 1 / a[r][c];
27        for (int i = r + 1; i < h; i++) {
28            if (is_0(a[i][c])) continue;
29            T coeff = -a[i][c] * inv_a;
30            for (int j : nonzero) a[i][j] += coeff * a[r][j];
31        }
32        ++r;
33    }
34    for (int row = h - 1; row >= 0; row--) {
35        for (int c = 0; c < limit; c++) {
36            if (!is_0(a[row][c])) {
37                T inv_a = 1 / a[row][c];
38                for (int i = row - 1; i >= 0; i--) {
39                    if (is_0(a[i][c])) continue;
40                    T coeff = -a[i][c] * inv_a;
41                    for (int j = c; j < w; j++) a[i][j] += coeff *
↳ a[row][j];

```

```

42     }
43     break;
44 }
45 }
46 } // not-free variables: only it on its line
47 for(int i = r; i < h; i++) if(!is_0(a[i][limit]))
48     return 0;
49 return (r == limit) ? 1 : -1;
50 }
51 template <typename T>
52 pair<int, vector<T>> solve_linear(vector<vector<T>> a,
53     ↪ const vector<T> &b, int w) {
54     int h = (int)a.size();
55     for (int i = 0; i < h; i++) a[i].push_back(b[i]);
56     int sol = gaussian_elimination(a, w);
57     if(!sol) return {0, vector<T>()};
58     vector<T> x(w, 0);
59     for (int i = 0; i < h; i++) {
60         for (int j = 0; j < w; j++) {
61             if (!is_0(a[i][j])) {
62                 x[j] = a[i][w] / a[i][j];
63                 break;
64             }
65         }
66     }
67     return {sol, x};
68 }

```

is_prime

- (Miller–Rabin primality test)

```

1 typedef __int128_t i128;
2
3 i128 power(i128 a, i128 b, i128 MOD = 1, i128 res = 1) {
4     for (; b; b /= 2, (a *= a) %= MOD)
5         if (b & 1) (res *= a) %= MOD;
6     return res;
7 }
8
9 bool is_prime(ll n) {
10     if (n < 2) return false;
11     static constexpr int A[] = {2, 3, 5, 7, 11, 13, 17,
12     ↪ 19, 23};
13     int s = __builtin_ctzll(n - 1);
14     ll d = (n - 1) >> s;
15     for (auto a : A) {
16         if (a == n) return true;
17         ll x = (ll)power(a, d, n);
18         if (x == 1 || x == n - 1) continue;
19         bool ok = false;
20         for (int i = 0; i < s - 1; ++i) {
21             x = ll(((i128)x * x % n); // potential overflow!
22             if (x == n - 1) {
23                 ok = true;
24                 break;
25             }
26         }
27     }
28 }

```

```

25     }
26     if (!ok) return false;
27 }
28 return true;
29 }
30
31 typedef __int128_t i128;
32
33 ll pollard_rho(ll x) {
34     ll s = 0, t = 0, c = rng() % (x - 1) + 1;
35     ll stp = 0, goal = 1, val = 1;
36     for (goal = 1; goal <= 2, s = t, val = 1) {
37         for (stp = 1; stp <= goal; ++stp) {
38             t = ll(((i128)t * t + c) % x);
39             val = ll(((i128)val * abs(t - s) % x);
40             if ((stp % 127) == 0) {
41                 ll d = gcd(val, x);
42                 if (d > 1) return d;
43             }
44         }
45         ll d = gcd(val, x);
46         if (d > 1) return d;
47     }
48 }
49
50 ll get_max_factor(ll _x) {
51     ll max_factor = 0;
52     function<void(ll)> fac = [&](ll x) {
53         if (x <= max_factor || x < 2) return;
54         if (is_prime(x)) {
55             max_factor = max_factor > x ? max_factor : x;
56             return;
57         }
58         ll p = x;
59         while (p >= x) p = pollard_rho(x);
60         while ((x % p) == 0) x /= p;
61         fac(x), fac(p);
62     };
63     fac(_x);
64     return max_factor;
65 }

```

Berlekamp-Massey

- Recovers any n -order linear recurrence relation from the first $2n$ terms of the sequence.
- Input s is the sequence to be analyzed.
- Output c is the shortest sequence c_1, \dots, c_n , such that

$$s_m = \sum_{i=1}^n c_i \cdot s_{m-i}, \text{ for all } m \geq n.$$

- Be careful since c is returned in 0-based indexation.
- Complexity: $O(N^2)$

```

1 vector<ll> berlekamp_massey(vector<ll> s) {
2     int n = sz(s), l = 0, m = 1;
3     vector<ll> b(n), c(n);
4     ll ldd = b[0] = c[0] = 1;
5     for (int i = 0; i < n; i++, m++) {
6         ll d = s[i];
7         for (int j = 1; j <= l; j++) d = (d + c[j] * s[i -
8     ↪ j]) % MOD;
9         if (d == 0) continue;
10        vector<ll> temp = c;
11        ll coef = d * power(ldd, MOD - 2) % MOD;
12        for (int j = m; j < n; j++){
13            c[j] = (c[j] + MOD - coef * b[j - m]) % MOD;
14            if (c[j] < 0) c[j] += MOD;
15        }
16        if (2 * l <= i) {
17            l = i + 1 - l;
18            b = temp;
19            ldd = d;
20            m = 0;
21        }
22    }
23    c.resize(l + 1);
24    c.erase(c.begin());
25    for (ll &x : c)
26        x = (MOD - x) % MOD;
27    return c;
28 }

```

Calculating k -th term of a linear recurrence

- Given the first n terms s_0, s_1, \dots, s_{n-1} and the sequence c_1, c_2, \dots, c_n such that

$$s_m = \sum_{i=1}^n c_i \cdot s_{m-i}, \text{ for all } m \geq n,$$

the function `calc_kth` computes s_k .

- Complexity: $O(n^2 \log k)$

```

1 vector<ll> poly_mult_mod(vector<ll> p, vector<ll> q,
2     ↪ vector<ll> &c){
3     vector<ll> ans(sz(p) + sz(q) - 1);
4     for (int i = 0; i < sz(p); i++){
5         for (int j = 0; j < sz(q); j++){
6             ans[i + j] = (ans[i + j] + p[i] * q[j]) % MOD;
7         }
8     }
9     int n = sz(ans), m = sz(c);
10    for (int i = n - 1; i >= m; i--){
11        for (int j = 0; j < m; j++){

```

```

11     ans[i - 1 - j] = (ans[i - 1 - j] + c[j] * ans[i]) % MOD;
12     }
13 }
14 ans.resize(m);
15 return ans;
16 }
17
18 ll calc_kth(vector<ll> s, vector<ll> c, ll k){
19     assert(sz(s) >= sz(c)); // size of s can be greater
20     // than c, but not less
21     if (k < sz(s)) return s[k];
22     vector<ll> res{1};
23     for (vector<ll> poly = {0, 1}; k; poly =
24     poly_mult_mod(poly, poly, c), k >= 1){
25         if (k & 1) res = poly_mult_mod(res, poly, c);
26     }
27     ll ans = 0;
28     for (int i = 0; i < min(sz(res), sz(c)); i++) ans =
29     (ans + s[i] * res[i]) % MOD;
30     return ans;
31 }

```

Partition Function

- Returns number of partitions of n in $O(n^{1.5})$

```

1 int partition(int n) {
2     int dp[n + 1];
3     dp[0] = 1;
4     for (int i = 1; i <= n; i++) {
5         dp[i] = 0;
6         for (int j = 1, r = 1; i - (3 * j * j - j) / 2 >= 0;
7         ++j, r += -1) {
8             dp[i] += dp[i - (3 * j * j - j) / 2] * r;
9             if (i - (3 * j * j + j) / 2 >= 0) dp[i] += dp[i -
10             (3 * j * j + j) / 2] * r;
11         }
12     }
13     return dp[n];
14 }

```

NTT

```

1 void ntt(vector<ll>& a, int f) {
2     int n = a.size();
3     vector<ll> w(n);
4     vector<int> rev(n);
5     for (int i = 0; i < n; i++) rev[i] = (rev[i / 2] / 2) %
6     ((i & 1) * (n / 2));
7     for (int i = 0; i < n; i++) {
8         if (i < rev[i]) swap(a[i], a[rev[i]]);
9     }
10     ll wn = power(f ? (MOD + 1) / 3 : 3, (MOD - 1) / n);
11     w[0] = 1;
12     for (int i = 1; i < n; i++) w[i] = w[i - 1] * wn %
13     MOD;

```

```

14     for (int mid = 1; mid < n; mid *= 2) {
15         for (int i = 0; i < n; i += 2 * mid) {
16             for (int j = 0; j < mid; j++) {
17                 ll x = a[i + j], y = a[i + j + mid] * w[n / (2 *
18                 mid)] % MOD;
19                 a[i + j] = (x + y) % MOD, a[i + j + mid] = (x -
20                 y) % MOD;
21             }
22         }
23     }
24     if (f) {
25         ll iv = power(n, MOD - 2);
26         for (auto& x : a) x = x * iv % MOD;
27     }
28 }
29
30 vector<ll> mul(vector<ll> a, vector<ll> b) {
31     int n = 1, m = (int)a.size() + (int)b.size() - 1;
32     while (n < m) n *= 2;
33     a.resize(n), b.resize(n);
34     ntt(a, 0), ntt(b, 0); // if squaring, you can save one
35     // NTT here
36     for (int i = 0; i < n; i++) a[i] = a[i] * b[i] % MOD;
37     ntt(a, 1);
38     a.resize(m);
39     return a;
40 }

```

FFT

```

1 const ld PI = acos(-1);
2 auto mul = [&](const vector<ld>& aa, const vector<ld>&
3     bb) {
4     int n = (int)aa.size(), m = (int)bb.size(), bit = 1;
5     while ((1 << bit) < n + m - 1) bit++;
6     int len = 1 << bit;
7     vector<complex<ld>> a(len), b(len);
8     vector<int> rev(len);
9     for (int i = 0; i < n; i++) a[i].real(aa[i]);
10    for (int i = 0; i < m; i++) b[i].real(bb[i]);
11    for (int i = 0; i < len; i++) rev[i] = (rev[i >> 1] ^
12    1) | ((i & 1) << (bit - 1));
13    auto fft = [&](vector<complex<ld>>& p, int inv) {
14        for (int i = 0; i < len; i++)
15            if (i < rev[i]) swap(p[i], p[rev[i]]);
16        for (int mid = 1; mid < len; mid *= 2) {
17            auto w1 = complex<ld>(cos(PI / mid), (inv ? -1 :
18            1) * sin(PI / mid));
19            for (int i = 0; i < len; i += mid * 2) {
20                auto wk = complex<ld>(1, 0);
21                for (int j = 0; j < mid; j++, wk = wk * w1) {
22                    auto x = p[i + j], y = wk * p[i + j + mid];
23                    p[i + j] = x + y, p[i + j + mid] = x - y;
24                }
25            }
26        }
27        if (inv == 1) {
28            for (int i = 0; i < len; i++)
29                p[i].real(p[i].real() / len);
30        }
31    };

```

```

32    }
33    fft(a, 0), fft(b, 0);
34    for (int i = 0; i < len; i++) a[i] = a[i] * b[i];
35    fft(a, 1);
36    a.resize(n + m - 1);
37    vector<ld> res(n + m - 1);
38    for (int i = 0; i < n + m - 1; i++) res[i] =
39    a[i].real();
40    return res;
41 };

```

MIT's FFT/NTT, Polynomial mod/log/exp Template

- For integers rounding works if $(|a| + |b|) \max(a, b) < \sim 10^9$, or in theory maybe 10^6
- $\frac{1}{P(x)}$ in $O(n \log n)$, $e^{P(x)}$ in $O(n \log n)$, $\ln(P(x))$ in $O(n \log n)$, $P(x)^k$ in $O(n \log n)$, Evaluates $P(x_1), \dots, P(x_n)$ in $O(n \log^2 n)$, Lagrange Interpolation in $O(n \log^2 n)$

```

1 // use #define FFT 1 to use FFT instead of NTT (default)
2 // Examples:
3 // poly a(n+1); // constructs degree n poly
4 // a[0].v = 10; // assigns constant term a_0 = 10
5 // poly b = exp(a);
6 // poly is vector<num>
7 // for NTT, num stores just one int named v
8 // for FFT, num stores two doubles named x (real), y
9 // (imag)
10 #define sz(x) ((int)x.size())
11 #define rep(i, j, k) for (int i = int(j); i < int(k); i++)
12 #define trav(a, x) for (auto &a : x)
13 #define per(i, a, b) for (int i = (b)-1; i >= (a); --i)
14 using ll = long long;
15 using vi = vector<int>;
16
17 namespace fft {
18     #if FFT
19     // FFT
20     using dbl = double;
21     struct num {
22         dbl x, y;
23         num(dbl x_ = 0, dbl y_ = 0): x(x_), y(y_) {}
24     };
25     inline num operator+(num a, num b) {
26         return num(a.x + b.x, a.y + b.y);
27     }
28     inline num operator-(num a, num b) {
29         return num(a.x - b.x, a.y - b.y);
30     }
31 }

```

```

31 inline num operator*(num a, num b) {
32     return num(a.x * b.x - a.y * b.y, a.x * b.y + a.y *
33         ↪ b.x);
34 }
35 inline num conj(num a) { return num(a.x, -a.y); }
36 inline num inv(num a) {
37     dbl n = (a.x * a.x + a.y * a.y);
38     return num(a.x / n, -a.y / n);
39 }
40 #else
41 // NTT
42 const int mod = 998244353, g = 3;
43 // For  $p < 2^{30}$  there is also  $(5 \ll 25, 3)$ ,  $(7 \ll 26,$ 
44 ↪  $3)$ ,
45 //  $(479 \ll 21, 3)$  and  $(483 \ll 21, 5)$ . Last two are  $>$ 
46 ↪  $10^9$ .
47 struct num {
48     int v;
49     num(ll v_ = 0): v(int(v_ % mod)) {
50         if (v < 0) v += mod;
51     }
52     explicit operator int() const { return v; }
53 };
54 inline num operator+(num a, num b) { return num(a.v +
55     ↪ b.v); }
56 inline num operator-(num a, num b) {
57     return num(a.v + mod - b.v);
58 }
59 inline num operator*(num a, num b) {
60     return num(1ll * a.v * b.v);
61 }
62 inline num pow(num a, int b) {
63     num r = 1;
64     do {
65         if (b & 1) r = r * a;
66         a = a * a;
67     } while (b >= 1);
68     return r;
69 }
70 inline num inv(num a) { return pow(a, mod - 2); }
71 #endif
72 using vn = vector<num>;
73 vi rev({0, 1});
74 vn rt(2, num(1)), fa, fb;
75 inline void init(int n) {
76     if (n <= sz(rt)) return;
77     rev.resize(n);
78     rep(i, 0, n) rev[i] = (rev[i >> 1] | ((i & 1) * n))
79     ↪ 1;
80     rt.reserve(n);
81     for (int k = sz(rt); k < n; k *= 2) {
82         rt.resize(2 * k);
83         #if FFT
84         double a = M_PI / k;
85         num z(cos(a), sin(a)); // FFT
86         #else
87         num z = pow(num(g), (mod - 1) / (2 * k)); // NTT
88         #endif
89         rep(i, k / 2, k) rt[2 * i] = rt[i],
90             rt[2 * i + 1] = rt[i] * z;
91     }
92 }
93 inline void fft(vector<num>& a, int n) {
94     init(n);
95     int s = __builtin_ctz(sz(rev) / n);
96     rep(i, 0, n) if (i < rev[i] >> s) swap(a[i], a[rev[i]
97     ↪ >> s]);
98     for (int k = 1; k < n; k *= 2)
99         for (int i = 0; i < n; i += 2 * k) rep(j, 0, k) {
100             num t = rt[j + k] * a[i + j + k];
101             a[i + j + k] = a[i + j] - t;
102             a[i + j] = a[i + j] + t;
103         }
104 }
105 // Complex/NTT
106 vn multiply(vn a, vn b) {
107     int s = sz(a) + sz(b) - 1;
108     if (s <= 0) return {};
109     int L = s > 1 ? 32 - __builtin_clz(s - 1) : 0, n = 1
110     ↪ << L;
111     a.resize(n), b.resize(n);
112     fft(a, n);
113     fft(b, n);
114     num d = inv(num(n));
115     rep(i, 0, n) a[i] = a[i] * b[i] * d;
116     reverse(a.begin() + 1, a.end());
117     fft(a, n);
118     a.resize(s);
119     return a;
120 }
121 // Complex/NTT power-series inverse
122 // Doubles b as  $b[:n] = (2 - a[:n] * b[:n/2]) * b[:n/2]$ 
123 vn inverse(const vn& a) {
124     if (a.empty()) return {};
125     vn b({inv(a[0])});
126     b.reserve(2 * a.size());
127     while (sz(b) < sz(a)) {
128         int n = 2 * sz(b);
129         b.resize(2 * n, 0);
130         if (sz(fa) < 2 * n) fa.resize(2 * n);
131         fill(fa.begin(), fa.begin() + 2 * n, 0);
132         copy(a.begin(), a.begin() + min(n, sz(a)),
133             ↪ fa.begin());
134         fft(b, 2 * n);
135         fft(fa, 2 * n);
136         num d = inv(num(2 * n));
137         rep(i, 0, 2 * n) b[i] = b[i] * (2 - fa[i] * b[i])
138         ↪ d;
139         reverse(b.begin() + 1, b.end());
140         fft(b, 2 * n);
141         b.resize(n);
142     }
143     b.resize(a.size());
144     return b;
145 }
146 }
147 #if FFT
148 // Double multiply (num = complex)
149 using vd = vector<double>;
150 vd multiply(const vd& a, const vd& b) {
151     int s = sz(a) + sz(b) - 1;
152     if (s <= 0) return {};
153     int L = s > 1 ? 32 - __builtin_clz(s - 1) : 0, n = 1
154     ↪ << L;
155     if (sz(fa) < n) fa.resize(n);
156     if (sz(fb) < n) fb.resize(n);
157     fill(fa.begin(), fa.begin() + n, 0);
158     rep(i, 0, sz(a)) fa[i].x = a[i];
159     rep(i, 0, sz(b)) fa[i].y = b[i];
160     fft(fa, n);
161     trav(x, fa) x = x * x;
162     rep(i, 0, n) fb[i] = fa[(n - i) & (n - 1)] -
163     ↪ conj(fa[i]);
164     fft(fb, n);
165     vd r(s);
166     rep(i, 0, s) r[i] = fb[i].y / (4 * n);
167     return r;
168 }
169 // Integer multiply mod m (num = complex)
170 vi multiply_mod(const vi& a, const vi& b, int m) {
171     int s = sz(a) + sz(b) - 1;
172     if (s <= 0) return {};
173     int L = s > 1 ? 32 - __builtin_clz(s - 1) : 0, n = 1
174     ↪ << L;
175     if (sz(fa) < n) fa.resize(n);
176     if (sz(fb) < n) fb.resize(n);
177     rep(i, 0, sz(a)) fa[i] =
178         num(a[i] & ((1 << 15) - 1), a[i] >> 15);
179     fill(fa.begin() + sz(a), fa.begin() + n, 0);
180     rep(i, 0, sz(b)) fb[i] =
181         num(b[i] & ((1 << 15) - 1), b[i] >> 15);
182     fill(fb.begin() + sz(b), fb.begin() + n, 0);
183     fft(fa, n);
184     fft(fb, n);
185     double r0 = 0.5 / n; // 1/2n
186     rep(i, 0, n / 2 + 1) {
187         int j = (n - i) & (n - 1);
188         num g0 = (fb[i] + conj(fb[j])) * r0;
189         num g1 = (fb[i] - conj(fb[j])) * r0;
190         swap(g1.x, g1.y);
191         g1.y *= -1;
192         if (j != i) {
193             swap(fa[j], fa[i]);
194             fb[j] = fa[j] * g1;
195             fa[j] = fa[j] * g0;
196         }
197         fb[i] = fa[i] * conj(g1);
198         fa[i] = fa[i] * conj(g0);
199     }
200     fft(fa, n);
201     fft(fb, n);
202     vi r(s);

```

```

192     rep(i, 0, s) r[i] =
193         int((ll(fa[i].x + 0.5) + (ll(fa[i].y + 0.5) % m < 15) +
194             (ll(fb[i].x + 0.5) % m < 15) +
195             (ll(fb[i].y + 0.5) % m < 30)) %
196             m);
197     return r;
198 }
199 #endif
200 } // namespace fft
201 // For multiply_mod, use num = modnum, poly =
202     vector<num>
203 using fft::num;
204 using poly = fft::vn;
205 using fft::multiply;
206 using fft::inverse;
207
208 poly& operator+=(poly& a, const poly& b) {
209     if (sz(a) < sz(b)) a.resize(b.size());
210     rep(i, 0, sz(b)) a[i] = a[i] + b[i];
211     return a;
212 }
213
214 poly operator+(const poly& a, const poly& b) {
215     poly r = a;
216     r += b;
217     return r;
218 }
219
220 poly& operator-=(poly& a, const poly& b) {
221     if (sz(a) < sz(b)) a.resize(b.size());
222     rep(i, 0, sz(b)) a[i] = a[i] - b[i];
223     return a;
224 }
225
226 poly operator-(const poly& a, const poly& b) {
227     poly r = a;
228     r -= b;
229     return r;
230 }
231
232 poly operator*(const poly& a, const poly& b) {
233     return multiply(a, b);
234 }
235
236 poly& operator*=(poly& a, const poly& b) { return a = a * b; }
237
238 poly& operator*=(poly& a, const num& b) { // Optional
239     trav(x, a) x = x * b;
240     return a;
241 }
242
243 poly operator*(const poly& a, const num& b) {
244     poly r = a;
245     r *= b;
246     return r;
247 }
248
249 // Polynomial floor division; no leading 0's please
250 poly operator/(poly a, poly b) {
251     if (sz(a) < sz(b)) return {};
252     int s = sz(a) - sz(b) + 1;
253     reverse(a.begin(), a.end());
254     reverse(b.begin(), b.end());
255
256     a.resize(s);
257     b.resize(s);
258     a = a * inverse(move(b));
259     a.resize(s);
260     reverse(a.begin(), a.end());
261     return a;
262 }
263
264 poly& operator/=(poly& a, const poly& b) { return a = a / b; }
265
266 poly& operator%=(poly& a, const poly& b) {
267     if (sz(a) >= sz(b)) {
268         poly c = (a / b) * b;
269         a.resize(sz(b) - 1);
270         rep(i, 0, sz(a)) a[i] = a[i] - c[i];
271     }
272     return a;
273 }
274
275 poly operator%(const poly& a, const poly& b) {
276     poly r = a;
277     r %= b;
278     return r;
279 }
280
281 // Log/exp/pow
282 poly deriv(const poly& a) {
283     if (a.empty()) return {};
284     poly b(sz(a) - 1);
285     rep(i, 1, sz(a)) b[i - 1] = a[i] * i;
286     return b;
287 }
288
289 poly integ(const poly& a) {
290     poly b(sz(a) + 1);
291     b[1] = 1; // mod p
292     rep(i, 2, sz(b)) b[i] =
293         b[fft::mod % i] * (-fft::mod / i); // mod p
294     rep(i, 1, sz(b)) b[i] = a[i - 1] * b[i]; // mod p
295     // rep(i, 1, sz(b)) b[i] = a[i - 1] * inv(num(i)); // else
296     return b;
297 }
298
299 poly log(const poly& a) { // MUST have a[0] == 1
300     poly b = integ(deriv(a) * inverse(a));
301     b.resize(a.size());
302     return b;
303 }
304
305 poly exp(const poly& a) { // MUST have a[0] == 0
306     poly b(1, num(1));
307     if (a.empty()) return b;
308     while (sz(b) < sz(a)) {
309         int n = min(sz(b) * 2, sz(a));
310         b.resize(n);
311         poly v = poly(a.begin(), a.begin() + n) - log(b);
312         v[0] = v[0] + num(1);
313         b *= v;
314         b.resize(n);
315     }
316     return b;
317 }
318
319 poly pow(const poly& a, int m) { // m >= 0
320     poly b(a.size());
321
322     if (!m) {
323         b[0] = 1;
324         return b;
325     }
326     while (p < sz(a) && a[p].v == 0) ++p;
327     if (1ll * m * p >= sz(a)) return b;
328     num mu = pow(a[p], m), di = inv(a[p]);
329     poly c(sz(a) - m * p);
330     rep(i, 0, sz(c)) c[i] = a[i + p] * di;
331     c = log(c);
332     trav(v, c) v = v * m;
333     c = exp(c);
334     rep(i, 0, sz(c)) b[i + m * p] = c[i] * mu;
335     return b;
336 }
337
338 // Multipoint evaluation/interpolation
339
340 vector<num> eval(const poly& a, const vector<num>& x) {
341     int n = sz(x);
342     if (!n) return {};
343     vector<poly> up(2 * n);
344     rep(i, 0, n) up[i + n] = poly({0 - x[i], 1});
345     per(i, 1, n) up[i] = up[2 * i] * up[2 * i + 1];
346     vector<poly> down(2 * n);
347     down[1] = a % up[1];
348     rep(i, 2, 2 * n) down[i] = down[i / 2] % up[i];
349     vector<num> y(n);
350     rep(i, 0, n) y[i] = down[i + n][0];
351     return y;
352 }
353
354 poly interp(const vector<num>& x, const vector<num>& y)
355     {
356     int n = sz(x);
357     assert(n);
358     vector<poly> up(n * 2);
359     rep(i, 0, n) up[i + n] = poly({0 - x[i], 1});
360     per(i, 1, n) up[i] = up[2 * i] * up[2 * i + 1];
361     vector<num> a = eval(deriv(up[1]), x);
362     vector<poly> down(2 * n);
363     rep(i, 0, n) down[i + n] = poly({y[i] * inv(a[i])});
364     per(i, 1, n) down[i] =
365         down[i * 2] * up[i * 2 + 1] + down[i * 2 + 1] * up[i
366         * 2];
367     return down[1];
368 }

```

Data Structures

Fenwick Tree

```

1 ll sum(int r) {
2     ll ret = 0;
3     for (; r >= 0; r = (r & r + 1) - 1) ret += bit[r];
4     return ret;

```

```

5 }
6 void add(int idx, ll delta) {
7     for (; idx < n; idx |= idx + 1) bit[idx] += delta;
8 }

Lazy Propagation SegTree

1 // Clear: clear() or build()
2 const int N = 2e5 + 10; // Change the constant!
3 template<typename T>
4 struct LazySegTree{
5     T t[4 * N];
6     T lazy[4 * N];
7     int n;

8     // Change these functions, default return, and lazy
9     ↪ mark.
10    T default_return = 0, lazy_mark =
11    ↪ numeric_limits<T>::min();
12    // Lazy mark is how the algorithm will identify that
13    ↪ no propagation is needed.
14    function<T(T, T)> f = [&] (T a, T b){
15        return a + b;
16    };
17    // f_on_seg calculates the function f, knowing the
18    ↪ lazy value on segment,
19    // segment's size and the previous value.
20    // The default is segment modification for RSQ. For
21    ↪ increments change to:
22    // return cur_seg_val + seg_size * lazy_val;
23    // For RMQ. Modification: return lazy_val;
24    ↪ Increments: return cur_seg_val + lazy_val;
25    function<T(T, int, T)> f_on_seg = [&] (T cur_seg_val,
26    ↪ int seg_size, T lazy_val){
27        return seg_size * lazy_val;
28    };
29    // upd_lazy updates the value to be propagated to
30    ↪ child segments.
31    // Default: modification. For increments change to:
32    // lazy[v] = (lazy[v] == lazy_mark? val : lazy[v]
33    ↪ + val);
34    function<void(int, T)> upd_lazy = [&] (int v, T val){
35        lazy[v] = val;
36    };
37    // Tip: for "get element on single index" queries, use
38    ↪ max() on segment: no overflows.

39    LazySegTree(int n_) : n(n_) {
40        clear(n);
41    }

42    void build(int v, int tl, int tr, vector<T>& a){
43        if (tl == tr) {
44            t[v] = a[tl];
45            return;
46        }
47        int tm = (tl + tr) / 2;
48        // left child: [tl, tm]

```

```

49        // right child: [tm + 1, tr]
50        build(2 * v + 1, tl, tm, a);
51        build(2 * v + 2, tm + 1, tr, a);
52        t[v] = f(t[2 * v + 1], t[2 * v + 2]);
53    }

54    LazySegTree(vector<T>& a){
55        build(a);
56    }

57    void push(int v, int tl, int tr){
58        if (lazy[v] == lazy_mark) return;
59        int tm = (tl + tr) / 2;
60        t[2 * v + 1] = f_on_seg(t[2 * v + 1], tm - tl + 1,
61        ↪ lazy[v]);
62        t[2 * v + 2] = f_on_seg(t[2 * v + 2], tr - tm,
63        ↪ lazy[v]);
64        upd_lazy(2 * v + 1, lazy[v]), upd_lazy(2 * v + 2,
65        ↪ lazy[v]);
66        lazy[v] = lazy_mark;
67    }

68    void modify(int v, int tl, int tr, int l, int r, T
69    ↪ val){
70        if (l > r) return;
71        if (tl == l && tr == r){
72            t[v] = f_on_seg(t[v], tr - tl + 1, val);
73            upd_lazy(v, val);
74            return;
75        }
76        push(v, tl, tr);
77        int tm = (tl + tr) / 2;
78        modify(2 * v + 1, tl, tm, l, min(r, tm), val);
79        modify(2 * v + 2, tm + 1, tr, max(l, tm + 1), r,
80        ↪ val);
81        t[v] = f(t[2 * v + 1], t[2 * v + 2]);
82    }

83    T query(int v, int tl, int tr, int l, int r) {
84        if (l > r) return default_return;
85        if (tl == l && tr == r) return t[v];
86        push(v, tl, tr);
87        int tm = (tl + tr) / 2;
88        return f(
89            query(2 * v + 1, tl, tm, l, min(r, tm)),
90            query(2 * v + 2, tm + 1, tr, max(l, tm + 1), r)
91        );
92    }

93    void modify(int l, int r, T val){
94        modify(0, 0, n - 1, l, r, val);
95    }

96    T query(int l, int r){
97        return query(0, 0, n - 1, l, r);
98    }

99    T get(int pos){

```

```

100        return query(pos, pos);
101    }

102    // Change clear() function to t.clear() if using
103    ↪ unordered_map for SegTree!!!
104    void clear(int n_){
105        n = n_;
106        for (int i = 0; i < 4 * n; i++) t[i] = 0, lazy[i] =
107        ↪ lazy_mark;
108    }

109    void build(vector<T>& a){
110        n = sz(a);
111        clear(n);
112        build(0, 0, n - 1, a);
113    }
114};

Sparse Table

1 const int N = 2e5 + 10, LOG = 20; // Change the
2 ↪ constant!
3 template<typename T>
4 struct SparseTable{
5     int lg[N];
6     T st[N][LOG];
7     int n;

8     // Change this function
9     function<T(T, T)> f = [&] (T a, T b){
10        return min(a, b);
11    };

12    void build(vector<T>& a){
13        n = sz(a);
14        lg[1] = 0;
15        for (int i = 2; i <= n; i++) lg[i] = lg[i / 2] + 1;

16        for (int k = 0; k < LOG; k++){
17            for (int i = 0; i < n; i++){
18                if (!k) st[i][k] = a[i];
19                else st[i][k] = f(st[i][k - 1], st[min(n - 1, i +
20                ↪ (1 << (k - 1)))] [k - 1]);
21            }
22        }
23    }

24    T query(int l, int r){
25        int sz = r - l + 1;
26        return f(st[l][lg[sz]], st[r - (1 << lg[sz]) +
27        ↪ 1][lg[sz]]);
28    }

29    T get(int pos){
30    };

```


Suffix Array and LCP array

- (uses SparseTable above)

```

1 struct SuffixArray{
2     vector<int> p, c, h;
3     SparseTable<int> st;
4     /*
5      In the end, array c gives the position of each suffix
6      ↪ in p
7      using 1-based indexation!
8      */
9     SuffixArray() {}
10
11     SuffixArray(string s){
12         buildArray(s);
13         buildLCP(s);
14         buildSparse();
15     }
16
17     void buildArray(string s){
18         int n = sz(s) + 1;
19         p.resize(n), c.resize(n);
20         for (int i = 0; i < n; i++) p[i] = i;
21         sort(all(p), [&](int a, int b){return s[a] <
22             ↪ s[b];});
23         c[p[0]] = 0;
24         for (int i = 1; i < n; i++){
25             c[p[i]] = c[p[i - 1]] + (s[p[i]] != s[p[i - 1]]);
26         }
27         vector<int> p2(n), c2(n);
28         // w is half-length of each string.
29         for (int w = 1; w < n; w <= 1){
30             for (int i = 0; i < n; i++){
31                 p2[i] = (p[i] - w + n) % n;
32             }
33             vector<int> cnt(n);
34             for (auto i : c) cnt[i]++;
35             for (int i = 1; i < n; i++) cnt[i] += cnt[i - 1];
36             for (int i = n - 1; i >= 0; i--){
37                 p[--cnt[c[p2[i]]]] = p2[i];
38             }
39             c2[p[0]] = 0;
40             for (int i = 1; i < n; i++){
41                 c2[p[i]] = c2[p[i - 1]] +
42                     (c[p[i]] != c[p[i - 1]] ||
43                      c[(p[i] + w) % n] != c[(p[i - 1] + w) % n]);
44             }
45             c.swap(c2);
46             p.erase(p.begin());
47         }
48
49         void buildLCP(string s){
50             // The algorithm assumes that suffix array is
51             ↪ already built on the same string.
52             int n = sz(s);
53             h.resize(n - 1);

```

```

53         int k = 0;
54         for (int i = 0; i < n; i++){
55             if (c[i] == n){
56                 k = 0;
57                 continue;
58             }
59             int j = p[c[i]];
60             while (i + k < n && j + k < n && s[i + k] == s[j +
61                 ↪ k]) k++;
62             h[c[i] - 1] = k;
63             if (k) k--;
64         }
65         /*
66          Then an RMQ Sparse Table can be built on array h
67          to calculate LCP of 2 non-consecutive suffixes.
68          */
69     }
70
71     void buildSparse(){
72         st.build(h);
73     }
74
75     // l and r must be in 0-BASED INDEXATION
76     int lcp(int l, int r){
77         l = c[l] - 1, r = c[r] - 1;
78         if (l > r) swap(l, r);
79         return st.query(l, r - 1);
80     }
81 };
82
83 Aho Corasick Trie
84
85 • For each node in the trie, the suffix link points to
86   the longest proper suffix of the represented string.
87   The terminal-link tree has square-root height (can
88   be constructed by DFS).
89
90 const int S = 26;
91
92 // Function converting char to int.
93 int ctoi(char c){
94     return c - 'a';
95 }
96
97 // To add terminal links, use DFS
98 struct Node{
99     vector<int> nxt;
100     int link;
101     bool terminal;
102
103     Node() {
104         nxt.assign(S, -1), link = 0, terminal = 0;
105     }
106 };
107
108 vector<Node> trie(1);

```

```

21 // add_string returns the terminal vertex.
22 int add_string(string& s){
23     int v = 0;
24     for (auto c : s){
25         int cur = ctoi(c);
26         if (trie[v].nxt[cur] == -1){
27             trie[v].nxt[cur] = sz(trie);
28             trie.emplace_back();
29         }
30         v = trie[v].nxt[cur];
31     }
32     trie[v].terminal = 1;
33     return v;
34 }
35
36 /*
37 Suffix links are compressed.
38 This means that:
39 If vertex v has a child by letter x, then:
40     trie[v].nxt[x] points to that child.
41 If vertex v doesn't have such child, then:
42     trie[v].nxt[x] points to the suffix link of that
43     ↪ child
44     if we would actually have it.
45 */
46 void add_links(){
47     queue<int> q;
48     q.push(0);
49     while (!q.empty()){
50         auto v = q.front();
51         int u = trie[v].link;
52         q.pop();
53         for (int i = 0; i < S; i++){
54             int& ch = trie[v].nxt[i];
55             if (ch == -1){
56                 ch = v? trie[u].nxt[i] : 0;
57             }
58             else{
59                 trie[ch].link = v? trie[u].nxt[i] : 0;
60                 q.push(ch);
61             }
62         }
63     }
64
65     bool is_terminal(int v){
66         return trie[v].terminal;
67     }
68
69     int get_link(int v){
70         return trie[v].link;
71     }
72
73     int go(int v, char c){
74         return trie[v].nxt[ctoi(c)];
75     }

```


Convex Hull Trick

- Allows to insert a linear function to the hull in (1) and get the minimum/maximum value of the stored function at a point in $O(\log n)$.
- NOTE: The lines must be added in the order of decreasing/increasing gradients. CAREFULLY CHECK THE SETUP BEFORE USING!
- IMPORTANT: THE DEFAULT VERSION SURELY WORKS. IF MODIFIED VERSIONS DON'T WORK, TRY TRANSFORMING THEM TO THE DEFAULT ONE BY CHANGING SIGNS.

```

1 struct line{
2     ll k, b;
3     ll f(ll x){
4         return k * x + b;
5     };
6 };
7
8 vector<line> hull;
9
10 void add_line(line nl){
11     if (!hull.empty() && hull.back().k == nl.k){
12         nl.b = min(nl.b, hull.back().b); // Default:
13         ↪ minimum. For maximum change "min" to "max".
14         hull.pop_back();
15     }
16     while (sz(hull) > 1){
17         auto& l1 = hull.end()[-2], l2 = hull.back();
18         if ((nl.b - l1.b) * (l2.k - nl.k) >= (nl.b - l2.b) *
19             ↪ (l1.k - nl.k)) hull.pop_back(); // Default:
20         ↪ decreasing gradient k. For increasing k change the
21         ↪ sign to <=.
22         else break;
23     }
24     hull.pb(nl);
25 }
26
27 ll get(ll x){
28     int l = 0, r = sz(hull);
29     while (r - l > 1){
30         int mid = (l + r) / 2;
31         if (hull[mid - 1].f(x) >= hull[mid].f(x)) l = mid;
32         ↪ // Default: minimum. For maximum change the sign to
33         ↪ <=.
34         else r = mid;
35     }
36     return hull[l].f(x);
37 }

```

Li-Chao Segment Tree

- allows to add linear functions in any order and query minimum/maximum value of those at a point, all in $O(\log n)$.
- Clear: clear()

```

const ll INF = 1e18; // Change the constant!
struct LiChaoTree{
    struct line{
        ll k, b;
        line(){
            k = b = 0;
        };
        line(ll k_, ll b_){
            k = k_, b = b_;
        };
        ll f(ll x){
            return k * x + b;
        };
    };
    int n;
    bool minimum, on_points;
    vector<ll> pts;
    vector<line> t;

    void clear(){
        for (auto& l : t) l.k = 0, l.b = minimum? INF :
        ↪ -INF;
    }

    LiChaoTree(int n_, bool min_){ // This is a default
        ↪ constructor for numbers in range [0, n - 1].
        n = n_, minimum = min_, on_points = false;
        t.resize(4 * n);
        clear();
    };

    LiChaoTree(vector<ll> pts_, bool min_){ // This
        ↪ constructor will build LCT on the set of points you
        ↪ pass. The points may be in any order and contain
        ↪ duplicates.
        pts = pts_, minimum = min_;
        sort(all(pts));
        pts.erase(unique(all(pts)), pts.end());
        on_points = true;
        n = sz(pts);
        t.resize(4 * n);
        clear();
    };

    void add_line(int v, int l, int r, line nl){
        // Adding on segment [l, r)
        int m = (l + r) / 2;
        ll lval = on_points? pts[l] : l, mval = on_points?
        ↪ pts[m] : m;

```

```

        if ((minimum && nl.f(mval) < t[v].f(mval)) ||
        ↪ (!minimum && nl.f(mval) > t[v].f(mval))) swap(t[v],
        ↪ nl);
        if (r - l == 1) return;
        if ((minimum && nl.f(lval) < t[v].f(lval)) ||
        ↪ (!minimum && nl.f(lval) > t[v].f(lval))) add_line(2
        ↪ * v + 1, l, m, nl);
        else add_line(2 * v + 2, m, r, nl);
    }

    ll get(int v, int l, int r, int x){
        int m = (l + r) / 2;
        if (r - l == 1) return t[v].f(on_points? pts[x] :
        ↪ x);
        else{
            if (minimum) return min(t[v].f(on_points? pts[x] :
            ↪ x), x < m? get(2 * v + 1, l, m, x) : get(2 * v + 2,
            ↪ m, r, x));
            else return max(t[v].f(on_points? pts[x] : x), x <
            ↪ m? get(2 * v + 1, l, m, x) : get(2 * v + 2, m, r,
            ↪ x));
        }
    }

    void add_line(ll k, ll b){
        add_line(0, 0, n, line(k, b));
    }

    ll get(ll x){
        return get(0, 0, n, on_points? lower_bound(all(pts),
        ↪ x) - pts.begin() : x);
        ↪ // Always pass the actual value of x, even if LCT
        ↪ is on points.
    };
};

```

Persistent Segment Tree

- for RSQ

```

1 struct Node {
2     ll val;
3     Node *l, *r;

4     Node(ll x) : val(x), l(nullptr), r(nullptr) {}
5     Node(Node *ll, Node *rr) {
6         l = ll, r = rr;
7         val = 0;
8         if (l) val += l->val;
9         if (r) val += r->val;
10    }
11    Node(Node *cp) : val(cp->val), l(cp->l), r(cp->r) {}
12 };
13
14 const int N = 2e5 + 20;
15 ll a[N];
16 Node *roots[N];
17 int n, cnt = 1;
18 Node *build(int l = 1, int r = n) {
19     if (l == r) return new Node(a[l]);

```

```

20     int mid = (l + r) / 2;
21     return new Node(build(l, mid), build(mid + 1, r));
22 }
23 Node *update(Node *node, int val, int pos, int l = 1,
    ↪ int r = n) {
24     if (l == r) return new Node(val);
25     int mid = (l + r) / 2;
26     if (pos > mid)
27         return new Node(node->l, update(node->r, val,
    ↪ pos, mid + 1, r));
28     else return new Node(update(node->l, val, pos, l,
    ↪ mid), node->r);
29 }
30 ll query(Node *node, int a, int b, int l = 1, int r = n)
    ↪ {
31     if (l > b || r < a) return 0;
32     if (l >= a && r <= b) return node->val;
33     int mid = (l + r) / 2;
34     return query(node->l, a, b, l, mid) + query(node->r,
    ↪ a, b, mid + 1, r);
35 }

```

- Write stuff down!
- Don't get stuck on one approach!

Miscellaneous

Ordered Set

```

1  #include <ext/pb_ds/assoc_container.hpp>
2  #include <ext/pb_ds/tree_policy.hpp>
3  using namespace __gnu_pbds;
4  typedef tree<int, null_type, less<int>, rb_tree_tag,
    ↪ tree_order_statistics_node_update> ordered_set;

```

Measuring Execution Time

```

1  ld tic = clock();
2  // execute algo...
3  ld tac = clock();
4  // Time in milliseconds
5  cerr << (tac - tic) / CLOCKS_PER_SEC * 1000 << endl;
6  // No need to comment out the print because it's done to
    ↪ cerr.

```

Setting Fixed D.P. Precision

```

1  cout << setprecision(d) << fixed;
2  // Each number is rounded to d digits after the decimal
    ↪ point, and truncated.

```

Common Bugs and General Advice

- Check overflow, array bounds
- Check variable overloading
- Check special cases (n=1?)
- Do something instead of nothing, stay organized