

# Columbia University: CU Later Team Reference Document

Kevin Yang, Innokentiy Kaurov, Eric Yuang Shao

May 21th 2024

# Contents

<b>Templates</b>	<b>2</b>
Ken's template . . . . .	2
Kevin's template . . . . .	2
Kevin's Template Extended . . . . .	2
<b>Geometry</b>	<b>2</b>
Point basics . . . . .	2
Line basics . . . . .	2
<b>Line and segment intersections</b>	<b>3</b>
Distances from a point to line and segment . . . . .	3
Polygon area . . . . .	3
Convex hull . . . . .	3
Point location in a convex polygon . . . . .	3
Point location in a simple polygon . . . . .	3
Minkowski Sum . . . . .	3
Half-plane intersection . . . . .	4
<b>Strings</b>	<b>4</b>
Manacher's algorithm . . . . .	5
Aho-Corasick Trie . . . . .	5
Suffix Automaton . . . . .	5
<b>Flows</b>	<b>6</b>
$O(N^2M)$ , on unit networks $O(N^{1/2}M)$ . . . . .	6
MCMF – maximize flow, then minimize its cost. $O(mn + Fm \log n)$ . . . . .	7
<b>Graphs</b>	<b>7</b>
Kuhn's algorithm for bipartite matching . . . . .	7
Hungarian algorithm for Assignment Problem . . . . .	8
Dijkstra's Algorithm . . . . .	8
Eulerian Cycle DFS . . . . .	8
SCC and 2-SAT . . . . .	8
Finding Bridges . . . . .	8
Virtual Tree . . . . .	9
HLD on Edges DFS . . . . .	9
Centroid Decomposition . . . . .	9
Biconnected Components and Block-Cut Tree . . . . .	9
<b>Math</b>	<b>10</b>
Binary exponentiation . . . . .	10
Matrix Exponentiation: $O(n^3 \log b)$ . . . . .	10
Extended Euclidean Algorithm . . . . .	10
CRT . . . . .	10
Linear Sieve . . . . .	10
Gaussian Elimination . . . . .	11
Pollard-Rho Factorization . . . . .	11
Modular Square Root . . . . .	12
Berlekamp-Massey . . . . .	12
Calculating k-th term of a linear recurrence . . . . .	12
Partition Function . . . . .	12
NTT . . . . .	12
FFT . . . . .	13
MIT's FFT/NTT, Polynomial mod/log/exp Template . . . . .	13
Simplex method for linear programs . . . . .	15
Matroid Intersection . . . . .	16
<b>Data Structures</b>	<b>17</b>
Fenwick Tree . . . . .	17
Lazy Propagation SegTree . . . . .	17

Sparse Table . . . . .	18
Suffix Array and LCP array . . . . .	18
Aho Corasick Trie . . . . .	18
Convex Hull Trick . . . . .	19
Li-Chao Segment Tree . . . . .	19
Persistent Segment Tree . . . . .	20
<b>Dynamic Programming</b>	<b>20</b>
Sum over Subset DP . . . . .	20
Divide and Conquer DP . . . . .	20
Knuth's DP Optimization . . . . .	20
<b>Miscellaneous</b>	<b>21</b>
Ordered Set . . . . .	21
Measuring Execution Time . . . . .	21
Setting Fixed D.P. Precision . . . . .	21
Common Bugs and General Advice . . . . .	21

# Templates

## Ken's template

```
1 #include <bits/stdc++.h>
2 using namespace std;
3 #define all(v) (v).begin(), (v).end()
4 typedef long long ll;
5 typedef long double ld;
6 #define pb push_back
7 #define sz(x) (int)(x).size()
8 #define fi first
9 #define se second
10 #define endl '\n'
```

## Kevin's template

```
1 // paste Kaurov's Template, minus last line
2 typedef vector<int> vi;
3 typedef vector<ll> vll;
4 typedef pair<int, int> pii;
5 typedef pair<ll, ll> pll;
6 const char nl = '\n';
7 #define forn(i, n) for (int i = 0; i < int(n); i++)
8 ll k, n, m, u, v, w, x, y, z;
9 string s;
10
11 bool multiTest = 1;
12 void solve(int tt){
13 }
14
15 int main(){
16     ios::sync_with_stdio(0);cin.tie(0);cout.tie(0);
17     cout<<fixed<< setprecision(14);
18
19     int t = 1;
20     if (multiTest) cin >> t;
21     forn(ii, t) solve(ii);
22 }
```

## Kevin's Template Extended

- to type after the start of the contest

```
1 typedef pair<double, double> pdd;
2 const ld PI = acos(-1);
3 const ll mod7 = 1e9 + 7;
4 const ll mod9 = 998244353;
5 const ll INF = 2*1024*1024*1023;
6 #pragma GCC target("avx2,bmi,bmi2,lzcnt,popcnt")
7 #include <ext/pb_ds/assoc_container.hpp>
8 #include <ext/pb_ds/tree_policy.hpp>
9 using namespace __gnu_pbds;
10 template<class T> using ordered_set = tree<T, null_type,
11     ↪ less<T>, rb_tree_tag, tree_order_statistics_node_update>;
12 vi d4x = {1, 0, -1, 0};
13 vi d4y = {0, 1, 0, -1};
14 vi d8x = {1, 0, -1, 0, 1, 1, -1, -1};
15 vi d8y = {0, 1, 0, -1, 1, -1, 1, -1};
16 mt19937
17     ↪ rng(chrono::steady_clock::now().time_since_epoch().count());
```

# Geometry

## Point basics

```
1 const ld EPS = 1e-9;
2
3 struct point{
4     ld x, y;
5     point() : x(0), y(0) {}
6     point(ld x_, ld y_) : x(x_), y(y_) {}
7
8     point operator+ (point rhs) const{
9         return point(x + rhs.x, y + rhs.y);
```

```
10     }
11     point operator- (point rhs) const{
12         return point(x - rhs.x, y - rhs.y);
13     }
14     point operator* (ld rhs) const{
15         return point(x * rhs, y * rhs);
16     }
17     point operator/ (ld rhs) const{
18         return point(x / rhs, y / rhs);
19     }
20     point ort() const{
21         return point(-y, x);
22     }
23     ld abs2() const{
24         return x * x + y * y;
25     }
26     ld len() const{
27         return sqrt(abs2());
28     }
29     point unit() const{
30         return point(x, y) / len();
31     }
32     point rotate(ld a) const{
33         return point(x * cos(a) - y * sin(a), x * sin(a) + y *
34     ↪ cos(a));
35     friend ostream& operator<<(ostream& os, point p){
36         return os << "(" << p.x << ", " << p.y << ")";
37     }
38
39     bool operator< (point rhs) const{
40         return make_pair(x, y) < make_pair(rhs.x, rhs.y);
41     }
42     bool operator== (point rhs) const{
43         return abs(x - rhs.x) < EPS && abs(y - rhs.y) < EPS;
44     }
45 };
46
47 ld sq(ld a){
48     return a * a;
49 }
50 ld smul(point a, point b){
51     return a.x * b.x + a.y * b.y;
52 }
53 ld vmul(point a, point b){
54     return a.x * b.y - a.y * b.x;
55 }
56 ld dist(point a, point b){
57     return (a - b).len();
58 }
59 bool acw(point a, point b){
60     return vmul(a, b) > -EPS;
61 }
62 bool cw(point a, point b){
63     return vmul(a, b) < EPS;
64 }
65 int sgn(ld x){
66     return (x > EPS) - (x < EPS);
67 }
```

## Line basics

```
1 struct line{
2     ld a, b, c;
3     line() : a(0), b(0), c(0) {}
4     line(ld a_, ld b_, ld c_) : a(a_), b(b_), c(c_) {}
5     line(point p1, point p2){
6         a = p1.y - p2.y;
7         b = p2.x - p1.x;
8         c = -a * p1.x - b * p1.y;
9     }
10 };
11
12 ld det(ld a11, ld a12, ld a21, ld a22){
13     return a11 * a22 - a12 * a21;
14 }
15 bool parallel(line l1, line l2){
```

```

16     return abs(vmul(point(l1.a, l1.b), point(l2.a, l2.b))) <
    ↪ EPS;
17 }
18 bool operator==(line l1, line l2){
19     return parallel(l1, l2) &&
20     abs(det(l1.b, l1.c, l2.b, l2.c)) < EPS &&
21     abs(det(l1.a, l1.c, l2.a, l2.c)) < EPS;
22 }

```

## Line and segment intersections

```

1 // {p, 0} - unique intersection, {p, 1} - infinite, {p, 2} -
    ↪ none
2 pair<point, int> line_inter(line l1, line l2){
3     if (parallel(l1, l2)){
4         return {point(), l1 == l2? 1 : 2};
5     }
6     return {point(
7         det(-l1.c, l1.b, -l2.c, l2.b) / det(l1.a, l1.b, l2.a,
    ↪ l2.b),
8         det(l1.a, -l1.c, l2.a, -l2.c) / det(l1.a, l1.b, l2.a,
    ↪ l2.b)
9     ), 0};
10 }
11
12 // Checks if p lies on ab
13 bool is_on_seg(point p, point a, point b){
14     return abs(vmul(p - a, p - b)) < EPS && smul(p - a, p - b) <
    ↪ EPS;
15 }
16
17 /*
18 If a unique intersection point between the line segments going
    ↪ from a to b and from c to d exists then it is returned.
19 If no intersection point exists an empty vector is returned.
20 If infinitely many exist a vector with 2 elements is returned,
    ↪ containing the endpoints of the common line segment.
21 */
22 vector<point> segment_inter(point a, point b, point c, point
    ↪ d) {
23     auto oa = vmul(d - c, a - c), ob = vmul(d - c, b - c), oc =
    ↪ vmul(b - a, c - a), od = vmul(b - a, d - a);
24     if (sgn(oa) * sgn(ob) < 0 && sgn(oc) * sgn(od) < 0) return
    ↪ {(a * ob - b * oa) / (ob - oa)};
25     set<point> s;
26     if (is_on_seg(a, c, d)) s.insert(a);
27     if (is_on_seg(b, c, d)) s.insert(b);
28     if (is_on_seg(c, a, b)) s.insert(c);
29     if (is_on_seg(d, a, b)) s.insert(d);
30     return {all(s)};
31 }
32 }

```

## Distances from a point to line and segment

```

1 // Distance from p to line ab
2 ld line_dist(point p, point a, point b){
3     return vmul(b - a, p - a) / (b - a).len();
4 }
5
6 // Distance from p to segment ab
7 ld segment_dist(point p, point a, point b){
8     if (a == b) return (p - a).len();
9     auto d = (a - b).abs2(), t = min(d, max((ld)0, smul(p - a, b
    ↪ - a)));
10     return ((p - a) * d - (b - a) * t).len() / d;
11 }

```

## Polygon area

```

1 ld area(vector<point> pts){
2     int n = sz(pts);
3     ld ans = 0;
4     for (int i = 0; i < n; i++){

```

```

5         ans += vmul(pts[i], pts[(i + 1) % n]);
6     }
7     return abs(ans) / 2;
8 }

```

## Convex hull

- Complexity:  $O(n \log n)$ .

```

1 vector<point> convex_hull(vector<point> pts){
2     sort(all(pts));
3     pts.erase(unique(all(pts)), pts.end());
4     vector<point> up, down;
5     for (auto p : pts){
6         while (sz(up) > 1 && acw(up.end()[-1] - up.end()[-2], p -
    ↪ up.end()[-2])) up.pop_back();
7         while (sz(down) > 1 && cw(down.end()[-1] - down.end()[-2],
    ↪ p - down.end()[-2])) down.pop_back();
8         up.pb(p), down.pb(p);
9     }
10    for (int i = sz(up) - 2; i >= 1; i--) down.pb(up[i]);
11    return down;
12 }

```

## Point location in a convex polygon

- Complexity:  $O(n)$  precalculation and  $O(\log n)$  query.

```

1 void prep_convex_poly(vector<point>& pts){
2     rotate(pts.begin(), min_element(all(pts)), pts.end());
3 }
4
5 // 0 - Outside, 1 - Exclusively Inside, 2 - On the Border
6 int in_convex_poly(point p, vector<point>& pts){
7     int n = sz(pts);
8     if (!n) return 0;
9     if (n <= 2) return is_on_seg(p, pts[0], pts.back());
10    int l = 1, r = n - 1;
11    while (r - l > 1){
12        int mid = (l + r) / 2;
13        if (acw(pts[mid] - pts[0], p - pts[0])) l = mid;
14        else r = mid;
15    }
16    if (!in_triangle(p, pts[0], pts[l], pts[l + 1])) return 0;
17    if (is_on_seg(p, pts[l], pts[l + 1]) ||
18        is_on_seg(p, pts[0], pts.back()) ||
19        is_on_seg(p, pts[0], pts[l]))
20        return 2;
21    return 1;
22 }

```

## Point location in a simple polygon

- Complexity:  $O(n)$ .

```

1 // 0 - Outside, 1 - Exclusively Inside, 2 - On the Border
2 int in_simple_poly(point p, vector<point>& pts){
3     int n = sz(pts);
4     bool res = 0;
5     for (int i = 0; i < n; i++){
6         auto a = pts[i], b = pts[(i + 1) % n];
7         if (is_on_seg(p, a, b)) return 2;
8         if (((a.y > p.y) - (b.y > p.y)) * vmul(b - p, a - p) >
    ↪ EPS){
9             res ^= 1;
10        }
11    }
12    return res;
13 }

```

## Minkowski Sum

- For two convex polygons  $P$  and  $Q$ , returns the set of points  $(p + q)$ , where  $p \in P, q \in Q$ .

- This set is also a convex polygon.
- Complexity:  $O(n)$ .

```

1 void minkowski_rotate(vector<point>& P){
2     int pos = 0;
3     for (int i = 1; i < sz(P); i++){
4         if (abs(P[i].y - P[pos].y) <= EPS){
5             if (P[i].x < P[pos].x) pos = i;
6         }
7         else if (P[i].y < P[pos].y) pos = i;
8     }
9     rotate(P.begin(), P.begin() + pos, P.end());
10 }
11 // P and Q are strictly convex, points given in
12 // counterclockwise order.
13 vector<point> minkowski_sum(vector<point> P, vector<point> Q){
14     minkowski_rotate(P);
15     minkowski_rotate(Q);
16     P.pb(P[0]);
17     Q.pb(Q[0]);
18     vector<point> ans;
19     int i = 0, j = 0;
20     while (i < sz(P) - 1 || j < sz(Q) - 1){
21         ans.pb(P[i] + Q[j]);
22         ld curmul;
23         if (i == sz(P) - 1) curmul = -1;
24         else if (j == sz(Q) - 1) curmul = +1;
25         else curmul = vmul(P[i + 1] - P[i], Q[j + 1] - Q[j]);
26         if (abs(curmul) < EPS || curmul > 0) i++;
27         if (abs(curmul) < EPS || curmul < 0) j++;
28     }
29     return ans;
30 }

```

## Half-plane intersection

- Given  $N$  half-plane conditions in the form of a ray, computes the vertices of their intersection polygon.
- Complexity:  $O(N \log N)$ .
- A ray is defined by a point  $p$  and direction vector  $dp$ . The half-plane is to the **left** of the direction vector.

```

1 // Extra functions needed: point operations, smul, vmul
2 const ld EPS = 1e-9;
3
4 int sgn(ld a){
5     return (a > EPS) - (a < -EPS);
6 }
7 int half(point p){
8     return p.y != 0 ? sgn(p.y) : -sgn(p.x);
9 }
10 bool angle_comp(point a, point b){
11     int A = half(a), B = half(b);
12     return A == B ? vmul(a, b) > 0 : A < B;
13 }
14 struct ray{
15     point p, dp; // origin, direction
16     ray(point p_, point dp_){
17         p = p_, dp = dp_;
18     }
19     point isect(ray l){
20         return p + dp * (vmul(l.dp, l.p - p) / vmul(l.dp, dp));
21     }
22     bool operator<(ray l){
23         return angle_comp(dp, l.dp);
24     }
25 };
26 vector<point> half_plane_isect(vector<ray> rays, ld DX = 1e9,
27 // constrain the area to [0, DX] x [0, DY]
28 // ld DY = 1e9){
29     rays.pb({point(0, 0), point(1, 0)});
30     rays.pb({point(DX, 0), point(0, 1)});
31     rays.pb({point(DX, DY), point(-1, 0)});
32     rays.pb({point(0, DY), point(0, -1)});
33     sort(all(rays));
34 }

```

```

34 vector<ray> nrays;
35 for (auto t : rays){
36     if (nrays.empty() || vmul(nrays.back().dp, t.dp) > EPS){
37         nrays.pb(t);
38         continue;
39     }
40     if (vmul(t.dp, t.p - nrays.back().p) > 0) nrays.back() =
41     ↪ t;
42     swap(rays, nrays);
43 }
44 auto bad = [&] (ray a, ray b, ray c){
45     point p1 = a.isect(b), p2 = b.isect(c);
46     if (smul(p2 - p1, b.dp) <= EPS){
47         if (vmul(a.dp, c.dp) <= 0) return 2;
48         return 1;
49     }
50     return 0;
51 };
52 #define reduce(t) \
53     while (sz(poly) > 1){ \
54         int b = bad(poly[sz(poly) - 2], poly.back(), t); \
55         if (b == 2) return {}; \
56         if (b == 1) poly.pop_back(); \
57         else break; \
58     }
59 deque<ray> poly;
60 for (auto t : rays){
61     reduce(t);
62     poly.pb(t);
63 }
64 for (; poly.pop_front()){
65     reduce(poly[0]);
66     if (!bad(poly.back(), poly[0], poly[1])) break;
67 }
68 assert(sz(poly) >= 3); // expect nonzero area
69 vector<point> poly_points;
70 for (int i = 0; i < sz(poly); i++){
71     poly_points.pb(poly[i].isect(poly[(i + 1) % sz(poly)]));
72 }
73 return poly_points;
74 }

```

## Strings

```

1 vector<int> prefix_function(string s){
2     int n = sz(s);
3     vector<int> pi(n);
4     for (int i = 1; i < n; i++){
5         int k = pi[i - 1];
6         while (k > 0 && s[i] != s[k]){
7             k = pi[k - 1];
8         }
9         pi[i] = k + (s[i] == s[k]);
10    }
11    return pi;
12 }
13 // Returns the positions of the first character
14 vector<int> kmp(string s, string k){
15     string st = k + "#" + s;
16     vector<int> res;
17     auto pi = prefix_function(st);
18     for (int i = 0; i < sz(st); i++){
19         if (pi[i] == sz(k)){
20             res.pb(i - 2 * sz(k));
21         }
22     }
23     return res;
24 }
25 vector<int> z_function(string s){
26     int n = sz(s);
27     vector<int> z(n);
28     int l = 0, r = 0;
29     for (int i = 1; i < n; i++){
30         if (r >= i) z[i] = min(z[i - l], r - i + 1);
31         while (i + z[i] < n && s[z[i]] == s[i + z[i]]){

```

```

32     z[i]++;
33 }
34 if (i + z[i] - 1 > r){
35     l = i, r = i + z[i] - 1;
36 }
37 }
38 return z;
39 }

```

## Manacher's algorithm

```

1  /*
2  Finds longest palindromes centered at each index
3  even[i] = d --> [i - d, i + d - 1] is a max-palindrome
4  odd[i] = d --> [i - d, i + d] is a max-palindrome
5  */
6  pair<vector<int>, vector<int>> manacher(string s) {
7      vector<char> t{'^', '#'};
8      for (char c : s) t.push_back(c), t.push_back('#');
9      t.push_back('$');
10     int n = t.size(), r = 0, c = 0;
11     vector<int> p(n, 0);
12     for (int i = 1; i < n - 1; i++) {
13         if (i < r + c) p[i] = min(p[2 * c - i], r + c - i);
14         while (t[i + p[i] + 1] == t[i - p[i] - 1]) p[i]++;
15         if (i + p[i] > r + c) r = p[i], c = i;
16     }
17     vector<int> even(sz(s)), odd(sz(s));
18     for (int i = 0; i < sz(s); i++){
19         even[i] = p[2 * i + 1] / 2, odd[i] = p[2 * i + 2] / 2;
20     }
21     return {even, odd};
22 }

```

## Aho-Corasick Trie

- Given a set of strings, constructs a trie with suffix links.
- For a particular node, *link* points to the longest proper suffix of this node that's contained in the trie.
- nxt* encodes suffix links in a compressed format:
  - If vertex *v* has a child by letter *x*, then *trie[v].nxt[x]* points to that child.
  - If vertex *v* doesn't have such child, then *trie[v].nxt[x]* points to the suffix link of that child if we would actually have it.
- Facts:** suffix link graph can be seen as a tree; terminal link tree has height  $O(\sqrt{N})$ , where *N* is the sum of strings' lengths.
- Usage:** add all strings, then call *add\_links()*.

```

1  const int S = 26;
2
3  // Function converting char to int.
4  int ctoi(char c){
5      return c - 'a';
6  }
7
8  // To add terminal links, use DFS
9  struct Node{
10     vector<int> nxt;
11     int link;
12     bool terminal;
13
14     Node() {
15         nxt.assign(S, -1), link = 0, terminal = 0;
16     }
17 };
18
19 vector<Node> trie(1);
20
21 // add_string returns the terminal vertex.
22 int add_string(string& s){
23     int v = 0;

```

```

24     for (auto c : s){
25         int cur = ctoi(c);
26         if (trie[v].nxt[cur] == -1){
27             trie[v].nxt[cur] = sz(trie);
28             trie.emplace_back();
29         }
30         v = trie[v].nxt[cur];
31     }
32     trie[v].terminal = 1;
33     return v;
34 }
35
36 void add_links(){
37     queue<int> q;
38     q.push(0);
39     while (!q.empty()){
40         auto v = q.front();
41         int u = trie[v].link;
42         q.pop();
43         for (int i = 0; i < S; i++){
44             int& ch = trie[v].nxt[i];
45             if (ch == -1){
46                 ch = v? trie[u].nxt[i] : 0;
47             }
48             else{
49                 trie[ch].link = v? trie[u].nxt[i] : 0;
50                 q.push(ch);
51             }
52         }
53     }
54 }
55
56 bool is_terminal(int v){
57     return trie[v].terminal;
58 }
59
60 int get_link(int v){
61     return trie[v].link;
62 }
63
64 int go(int v, char c){
65     return trie[v].nxt[ctoi(c)];
66 }

```

## Suffix Automaton

- Given a string *S*, constructs a DAG that is an automaton of all suffixes of *S*.
- The automaton has  $\leq 2n$  nodes and  $\leq 3n$  edges.
- Properties (let all paths start at node 0):
  - Every path represents a unique substring of *S*.
  - A path ends at a terminal node iff it represents a suffix of *S*.
  - All paths ending at a fixed node *v* have the same set of right endpoints of their occurrences in *S*.
  - Let *endpos(v)* represent this set. Then, *link(v)* := *u* such that *endpos(v)*  $\subset$  *endpos(u)* and  $|endpos(u)|$  is smallest possible. *link(0)* := -1. Links form a tree.
  - Let *len(v)* be the longest path ending at *v*. All paths ending at *v* have distinct lengths: every length from interval  $[len(link(v)) + 1, len(v)]$ .
- One of the main applications is dealing with **distinct** substrings. Such problems can be solved with DFS and DP.
- Complexity:  $O(|S| \cdot \log |\Sigma|)$ . Perhaps replace map with vector if  $|\Sigma|$  is small.

```

1  const int MAXLEN = 1e5 + 20;
2
3  struct suffix_automaton{

```

```

4 struct state {
5     int len, link;
6     bool terminal = 0, used = 0;
7     map<char, int> next;
8 };
9
10 state st[MAXLEN * 2];
11 int sz = 0, last;
12
13 suffix_automaton(){
14     st[0].len = 0;
15     st[0].link = -1;
16     sz++;
17     last = 0;
18 };
19
20 void extend(char c) {
21     int cur = sz++;
22     st[cur].len = st[last].len + 1;
23     int p = last;
24     while (p != -1 && !st[p].next.count(c)) {
25         st[p].next[c] = cur;
26         p = st[p].link;
27     }
28     if (p == -1) {
29         st[cur].link = 0;
30     } else {
31         int q = st[p].next[c];
32         if (st[p].len + 1 == st[q].len) {
33             st[cur].link = q;
34         } else {
35             int clone = sz++;
36             st[clone].len = st[p].len + 1;
37             st[clone].next = st[q].next;
38             st[clone].link = st[q].link;
39             while (p != -1 && st[p].next[c] == q) {
40                 st[p].next[c] = clone;
41                 p = st[p].link;
42             }
43             st[q].link = st[cur].link = clone;
44         }
45     }
46     last = cur;
47 }
48
49 void mark_terminal(){
50     int cur = last;
51     while (cur) st[cur].terminal = 1, cur = st[cur].link;
52 }
53 };
54 /*
55 Usage:
56 suffix_automaton sa;
57 for (int i = 0; i < sz(str); i++) sa.extend(str[i]);
58 sa.mark_terminal();
59 */

```

## Flows

$O(N^2M)$ , on unit networks  $O(N^{1/2}M)$

```

1 struct FlowEdge {
2     int from, to;
3     ll cap, flow = 0;
4     FlowEdge(int u, int v, ll cap) : from(u), to(v), cap(cap) {}
5 };
6 struct Dinic {
7     const ll flow_inf = 1e18;
8     vector<FlowEdge> edges;
9     vector<vector<int>> adj;
10     int n, m = 0;
11     int s, t;
12     vector<int> level, ptr;
13     vector<bool> used;
14     queue<int> q;

```

```

15 Dinic(int n, int s, int t) : n(n), s(s), t(t) {
16     adj.resize(n);
17     level.resize(n);
18     ptr.resize(n);
19 }
20 void add_edge(int u, int v, ll cap) {
21     edges.emplace_back(u, v, cap);
22     edges.emplace_back(v, u, 0);
23     adj[u].push_back(m);
24     adj[v].push_back(m + 1);
25     m += 2;
26 }
27 bool bfs() {
28     while (!q.empty()) {
29         int v = q.front();
30         q.pop();
31         for (int id : adj[v]) {
32             if (edges[id].cap - edges[id].flow < 1)
33                 continue;
34             if (level[edges[id].to] != -1)
35                 continue;
36             level[edges[id].to] = level[v] + 1;
37             q.push(edges[id].to);
38         }
39     }
40     return level[t] != -1;
41 }
42 ll dfs(int v, ll pushed) {
43     if (pushed == 0)
44         return 0;
45     if (v == t)
46         return pushed;
47     for (int& cid = ptr[v]; cid < (int)adj[v].size(); cid++) {
48         int id = adj[v][cid];
49         int u = edges[id].to;
50         if (level[v] + 1 != level[u] || edges[id].cap -
51             ↪ edges[id].flow < 1)
52             continue;
53         ll tr = dfs(u, min(pushed, edges[id].cap -
54             ↪ edges[id].flow));
55         if (tr == 0)
56             continue;
57         edges[id].flow += tr;
58         edges[id ^ 1].flow -= tr;
59         return tr;
60     }
61     return 0;
62 }
63 ll flow() {
64     ll f = 0;
65     while (true) {
66         fill(level.begin(), level.end(), -1);
67         level[s] = 0;
68         q.push(s);
69         if (!bfs())
70             break;
71         fill(ptr.begin(), ptr.end(), 0);
72         while (ll pushed = dfs(s, flow_inf)) {
73             f += pushed;
74         }
75     }
76     return f;
77 }
78 void cut_dfs(int v){
79     used[v] = 1;
80     for (auto i : adj[v]){
81         if (edges[i].flow < edges[i].cap && !used[edges[i].to]){
82             cut_dfs(edges[i].to);
83         }
84     }
85 }
86 // Assumes that max flow is already calculated
87 // true -> vertex is in S, false -> vertex is in T
88 vector<bool> min_cut(){
89     used = vector<bool>(n);

```

```

90     cut_dfs(s);
91     return used;
92 }
93 };
94 // To recover flow through original edges: iterate over even
  ↪ indices in edges.

```

**MCMF** – maximize flow, then minimize its cost.  $O(mn + Fm \log n)$ .

```

1  #include <bits/stdc++.h> // include-line, keep-include
2
3  const ll INF = LLONG_MAX / 4;
4
5  struct MCMF {
6      struct edge {
7          int from, to, rev;
8          ll cap, cost, flow;
9      };
10     int N;
11     vector<vector<edge>> ed;
12     vector<int> seen;
13     vector<ll> dist, pi;
14     vector<edge*> par;
15
16     MCMF(int N) : N(N), ed(N), seen(N), dist(N), pi(N), par(N)
  ↪ {}
17
18     void add_edge(int from, int to, ll cap, ll cost) {
19         if (from == to) return;
20         ed[from].push_back(edge{ from, to, sz(ed[to]), cap, cost, 0 });
21         ed[to].push_back(edge{ to, from, sz(ed[from])-1, 0, -cost, 0
  ↪ });
22     }
23
24     void path(int s) {
25         fill(all(seen), 0);
26         fill(all(dist), INF);
27         dist[s] = 0; ll di;
28
29         __gnu_pbds::priority_queue<pair<ll, int>> q;
30         vector<decltype(q)::point_iterator> its(N);
31         q.push({ 0, s });
32
33         while (!q.empty()) {
34             s = q.top().second; q.pop();
35             seen[s] = 1; di = dist[s] + pi[s];
36             for (edge& e : ed[s]) if (!seen[e.to]) {
37                 ll val = di - pi[e.to] + e.cost;
38                 if (e.cap - e.flow > 0 && val < dist[e.to]) {
39                     dist[e.to] = val;
40                     par[e.to] = &e;
41                     if (its[e.to] == q.end())
42                         its[e.to] = q.push({ -dist[e.to], e.to });
43                     else
44                         q.modify(its[e.to], { -dist[e.to], e.to });
45                 }
46             }
47         }
48         for (int i = 0; i < N; i++) pi[i] = min(pi[i] + dist[i],
  ↪ INF);
49     }
50
51     pair<ll, ll> max_flow(int s, int t) {
52         ll totflow = 0, totcost = 0;
53         while (path(s), seen[t]) {
54             ll fl = INF;
55             for (edge* x = par[t]; x; x = par[x->from])
56                 fl = min(fl, x->cap - x->flow);
57
58             totflow += fl;
59             for (edge* x = par[t]; x; x = par[x->from]) {
60                 x->flow += fl;
61                 ed[x->to][x->rev].flow -= fl;
62             }
63         }

```

```

64         for (int i = 0; i < N; i++) for(edge& e : ed[i]) totcost
  ↪ += e.cost * e.flow;
65         return {totflow, totcost/2};
66     }
67
68     // If some costs can be negative, call this before maxflow:
69     void setpi(int s) { // (otherwise, leave this out)
70         fill(all(pi), INF); pi[s] = 0;
71         int it = N, ch = 1; ll v;
72         while (ch-- && it--)
73             for (int i = 0; i < N; i++) if (pi[i] != INF)
74                 for (edge& e : ed[i]) if (e.cap)
75                     if ((v = pi[i] + e.cost) < pi[e.to])
76                         pi[e.to] = v, ch = 1;
77         assert(it >= 0); // negative cost cycle
78     }
79 };
80 // Usage: MCMF g(n); g.add_edge(u,v,c,w); g.max_flow(s,t).
81 // To recover flow through original edges: iterate over even
  ↪ indices in edges.

```

## Graphs

### Kuhn's algorithm for bipartite matching

```

1  /*
2  The graph is split into 2 halves of n1 and n2 vertices.
3  Complexity: O(n1 * m). Usually runs much faster. MUCH
  ↪ FASTER!!!
4  */
5  const int N = 305;
6
7  vector<int> g[N]; // Stores edges from left half to right.
8  bool used[N]; // Stores if vertex from left half is used.
9  int mt[N]; // For every vertex in right half, stores to which
  ↪ vertex in left half it's matched (-1 if not matched).
10
11 bool try_dfs(int v){
12     if (used[v]) return false;
13     used[v] = 1;
14     for (auto u : g[v]){
15         if (mt[u] == -1 || try_dfs(mt[u])){
16             mt[u] = v;
17             return true;
18         }
19     }
20     return false;
21 }
22
23 int main(){
24     // .....
25     for (int i = 1; i <= n2; i++) mt[i] = -1;
26     for (int i = 1; i <= n1; i++) used[i] = 0;
27     for (int i = 1; i <= n1; i++){
28         if (try_dfs(i)){
29             for (int j = 1; j <= n1; j++) used[j] = 0;
30         }
31     }
32     vector<pair<int, int>> ans;
33     for (int i = 1; i <= n2; i++){
34         if (mt[i] != -1) ans.pb({mt[i], i});
35     }
36 }
37
38 // Finding maximal independent set: size = # of nodes - # of
  ↪ edges in matching.
39 // To construct: launch Kuhn-like DFS from unmatched nodes in
  ↪ the left half.
40 // Independent set = visited nodes in left half + unvisited in
  ↪ right half.
41 // Finding minimal vertex cover: complement of maximal
  ↪ independent set.

```



## Hungarian algorithm for Assignment Problem

- Given a 1-indexed  $(n \times m)$  matrix  $A$ , select a number in each row such that each column has at most 1 number selected, and the sum of the selected numbers is minimized.

```
1 int INF = 1e9; // constant greater than any number in the
  ↪ matrix
2 vector<int> u(n+1), v(m+1), p(m+1), way(m+1);
3 for (int i=1; i<=n; ++i) {
4     p[0] = i;
5     int j0 = 0;
6     vector<int> minv (m+1, INF);
7     vector<bool> used (m+1, false);
8     do {
9         used[j0] = true;
10        int i0 = p[j0], delta = INF, j1;
11        for (int j=1; j<=m; ++j)
12            if (!used[j]) {
13                int cur = A[i0][j]-u[i0]-v[j];
14                if (cur < minv[j])
15                    minv[j] = cur, way[j] = j0;
16                if (minv[j] < delta)
17                    delta = minv[j], j1 = j;
18            }
19        for (int j=0; j<=m; ++j)
20            if (used[j])
21                u[p[j]] += delta, v[j] -= delta;
22            else
23                minv[j] -= delta;
24        j0 = j1;
25    } while (p[j0] != 0);
26    do {
27        int j1 = way[j0];
28        p[j0] = p[j1];
29        j0 = j1;
30    } while (j0);
31 }
32 vector<int> ans (n+1); // ans[i] stores the column selected
  ↪ for row i
33 for (int j=1; j<=m; ++j)
34     ans[p[j]] = j;
35 int cost = -v[0]; // the total cost of the matching
```

## Dijkstra's Algorithm

```
1 priority_queue<pair<ll, ll>, vector<pair<ll, ll>>,
  ↪ greater<pair<ll, ll>>> q;
2 dist[start] = 0;
3 q.push({0, start});
4 while (!q.empty()){
5     auto [d, v] = q.top();
6     q.pop();
7     if (d != dist[v]) continue;
8     for (auto [u, w] : g[v]){
9         if (dist[u] > dist[v] + w){
10             dist[u] = dist[v] + w;
11             q.push({dist[u], u});
12         }
13     }
14 }
```

## Eulerian Cycle DFS

```
1 void dfs(int v){
2     while (!g[v].empty()){
3         int u = g[v].back();
4         g[v].pop_back();
5         dfs(u);
6         ans.pb(v);
7     }
8 }
```

## SCC and 2-SAT

```
1 void scc(vector<vector<int>>& g, int* idx) {
2     int n = g.size(), ct = 0;
3     int out[n];
4     vector<int> ginv[n];
5     memset(out, -1, sizeof out);
6     memset(idx, -1, n * sizeof(int));
7     function<void(int)> dfs = [&](int cur) {
8         out[cur] = INT_MAX;
9         for(int v : g[cur]) {
10             ginv[v].push_back(cur);
11             if(out[v] == -1) dfs(v);
12         }
13         ct++; out[cur] = ct;
14     };
15     vector<int> order;
16     for(int i = 0; i < n; i++) {
17         order.push_back(i);
18         if(out[i] == -1) dfs(i);
19     }
20     sort(order.begin(), order.end(), [&](int& u, int& v) {
21         return out[u] > out[v];
22     });
23     ct = 0;
24     stack<int> s;
25     auto dfs2 = [&](int start) {
26         s.push(start);
27         while(!s.empty()) {
28             int cur = s.top();
29             s.pop();
30             idx[cur] = ct;
31             for(int v : ginv[cur])
32                 if(idx[v] == -1) s.push(v);
33         }
34     };
35     for(int v : order) {
36         if(idx[v] == -1) {
37             dfs2(v);
38             ct++;
39         }
40     }
41 }
42
43 // 0 => impossible, 1 => possible
44 pair<int, vector<int>> sat2(int n, vector<pair<int, int>>&
  ↪ clauses) {
45     vector<int> ans(n);
46     vector<vector<int>> g(2*n + 1);
47     for(auto [x, y] : clauses) {
48         x = x < 0 ? -x + n : x;
49         y = y < 0 ? -y + n : y;
50         int nx = x <= n ? x + n : x - n;
51         int ny = y <= n ? y + n : y - n;
52         g[nx].push_back(y);
53         g[ny].push_back(x);
54     }
55     int idx[2*n + 1];
56     scc(g, idx);
57     for(int i = 1; i <= n; i++) {
58         if(idx[i] == idx[i + n]) return {0, {}};
59         ans[i - 1] = idx[i + n] < idx[i];
60     }
61     return {1, ans};
62 }
```

## Finding Bridges

```
1 /*
2 Bridges.
3 Results are stored in a map "is_bridge".
4 For each connected component, call "dfs(starting vertex,
  ↪ starting vertex)".
5 */
6 const int N = 2e5 + 10; // Careful with the constant!
7
8 vector<int> g[N];
```

```

9  int tin[N], fup[N], timer;
10 map<pair<int, int>, bool> is_bridge;
11
12 void dfs(int v, int p){
13     tin[v] = ++timer;
14     fup[v] = tin[v];
15     for (auto u : g[v]){
16         if (!tin[u]){
17             dfs(u, v);
18             if (fup[u] > tin[v]){
19                 is_bridge[{u, v}] = is_bridge[{v, u}] = true;
20             }
21             fup[v] = min(fup[v], fup[u]);
22         }
23         else{
24             if (u != p) fup[v] = min(fup[v], tin[u]);
25         }
26     }
27 }

```

## Virtual Tree

```

1  // order stores the nodes in the queried set
2  sort(all(order), [&] (int u, int v){return tin[u] < tin[v]});
3  int m = sz(order);
4  for (int i = 1; i < m; i++){
5      order.pb(lca(order[i], order[i - 1]));
6  }
7  sort(all(order), [&] (int u, int v){return tin[u] < tin[v]});
8  order.erase(unique(all(order)), order.end());
9  vector<int> stk{order[0]};
10 for (int i = 1; i < sz(order); i++){
11     int v = order[i];
12     while (tout[stk.back()] < tout[v]) stk.pop_back();
13     int u = stk.back();
14     vg[u].pb({v, dep[v] - dep[u]});
15     stk.pb(v);
16 }

```

## HLD on Edges DFS

```

1  void dfs1(int v, int p, int d){
2      par[v] = p;
3      for (auto e : g[v]){
4          if (e.fi == p){
5              g[v].erase(find(all(g[v]), e));
6              break;
7          }
8      }
9      dep[v] = d;
10     sz[v] = 1;
11     for (auto [u, c] : g[v]){
12         dfs1(u, v, d + 1);
13         sz[v] += sz[u];
14     }
15     if (!g[v].empty()) iter_swap(g[v].begin(),
16     ↪ max_element(all(g[v]), comp));
17 }
18 void dfs2(int v, int rt, int c){
19     pos[v] = sz(a);
20     a.pb(c);
21     root[v] = rt;
22     for (int i = 0; i < sz(g[v]); i++){
23         auto [u, c] = g[v][i];
24         if (!i) dfs2(u, rt, c);
25         else dfs2(u, u, c);
26     }
27 }
28 int getans(int u, int v){
29     int res = 0;
30     for (; root[u] != root[v]; v = par[root[v]]){
31         if (dep[root[u]] > dep[root[v]]) swap(u, v);
32         res = max(res, rmq(0, 0, n - 1, pos[root[v]], pos[v]));
33     }
34     if (pos[u] > pos[v]) swap(u, v);
35     return max(res, rmq(0, 0, n - 1, pos[u] + 1, pos[v]));

```

```

35 }

```

## Centroid Decomposition

```

1  vector<char> res(n), seen(n), sz(n);
2  function<int(int, int)> get_size = [&](int node, int fa) {
3      sz[node] = 1;
4      for (auto& ne : g[node]) {
5          if (ne == fa || seen[ne]) continue;
6          sz[node] += get_size(ne, node);
7      }
8      return sz[node];
9  };
10 function<int(int, int, int)> find_centroid = [&](int node, int
11     ↪ fa, int t) {
12     for (auto& ne : g[node])
13         if (ne != fa && !seen[ne] && sz[ne] > t / 2) return
14         ↪ find_centroid(ne, node, t);
15     return node;
16 };
17 function<void(int, char)> solve = [&](int node, char cur) {
18     get_size(node, -1); auto c = find_centroid(node, -1,
19     ↪ sz[node]);
20     seen[c] = 1, res[c] = cur;
21     for (auto& ne : g[c]) {
22         if (seen[ne]) continue;
23         solve(ne, char(cur + 1)); // we can pass c here to build
24         ↪ tree
25     }
26 };

```

## Biconnected Components and Block-Cut Tree

- Biconnected components are the ones that have no articulation points.
- They are defined by edge sets that are “bounded” by articulation points in the original graph.
- The corresponding vertex sets are stored in *comps*.
- Block-Cut tree is constructed by creating a fictive node for each component, and attaching edges to its members.
- Articulation points in the original graph are the non-leaf non-fictive nodes in the BC tree.
- Complexity:  $O(n)$ .

```

1  // Usage: pass in adjacency list in 0-based indexation.
2  // Return: adjacency list of block-cut tree (nodes 0...n-1
3  ↪ represent original nodes, the rest are component nodes).
4  vector<vector<int>> biconnected_components(vector<vector<int>>
5  ↪ g) {
6      int n = sz(g);
7      vector<vector<int>> comps;
8      vector<int> stk, num(n), low(n);
9      int timer = 0;
10     // Finds the biconnected components
11     function<void(int, int)> dfs = [&](int v, int p) {
12         num[v] = low[v] = ++timer;
13         stk.pb(v);
14         for (int son : g[v]) {
15             if (son == p) continue;
16             if (num[son]) low[v] = min(low[v], num[son]);
17             else{
18                 dfs(son, v);
19                 low[v] = min(low[v], low[son]);
20                 if (low[son] >= num[v]){
21                     comps.pb({v});
22                     while (comps.back().back() != son){
23                         comps.back().pb(stk.back());
24                         stk.pop_back();
25                     }
26                 }
27             }
28         }
29     };
30     dfs(0, -1);
31     return comps;
32 }

```

```

27     };
28     dfs(0, -1);
29     // Build the block-cut tree
30     auto build_tree = [&]() {
31         vector<vector<int>>> t(n);
32         for (auto &comp : comps){
33             t.push_back({});
34             for (int u : comp){
35                 t.back().pb(u);
36             }
37             t[u].pb(sz(t) - 1);
38         }
39         return t;
40     };
41     return build_tree();
42 }

```

## Math

### Binary exponentiation

```

1 ll power(ll a, ll b){
2     ll res = 1;
3     for (; b; a = a * a % MOD, b >>= 1){
4         if (b & 1) res = res * a % MOD;
5     }
6     return res;
7 }

```

### Matrix Exponentiation: $O(n^3 \log b)$

```

1 const int N = 100, MOD = 1e9 + 7;
2
3 struct matrix{
4     ll m[N][N];
5     int n;
6     matrix(){
7         n = N;
8         memset(m, 0, sizeof(m));
9     };
10    matrix(int n_){
11        n = n_;
12        memset(m, 0, sizeof(m));
13    };
14    matrix(int n_, ll val){
15        n = n_;
16        memset(m, 0, sizeof(m));
17        for (int i = 0; i < n; i++) m[i][i] = val;
18    };
19
20    matrix operator* (matrix oth){
21        matrix res(n);
22        for (int i = 0; i < n; i++){
23            for (int j = 0; j < n; j++){
24                for (int k = 0; k < n; k++){
25                    res.m[i][j] = (res.m[i][j] + m[i][k] * oth.m[k][j])
26                    ↪ % MOD;
27                }
28            }
29        }
30        return res;
31    };
32
33    matrix power(matrix a, ll b){
34        matrix res(a.n, 1);
35        for (; b; a = a * a, b >>= 1){
36            if (b & 1) res = res * a;
37        }
38        return res;
39    }

```

## Extended Euclidean Algorithm

- $O(\max(\log a, \log b))$
- Finds solution  $(x, y)$  to  $ax + by = \gcd(a, b)$
- Can find all solutions given  $(x_0, y_0) : \forall k, a(x_0 + kb/g) + b(y_0 - ka/g) = \gcd(a, b)$ .

```

1 ll euclid(ll a, ll b, ll &x, ll &y) {
2     if (!b) return x = 1, y = 0, a;
3     ll d = euclid(b, a % b, y, x);
4     return y -= a/b * x, d;
5 }

```

## CRT

- $\text{crt}(a, m, b, n)$  computes  $x$  such that  $x \equiv a \pmod{m}, x \equiv b \pmod{n}$
- If  $|a| < m$  and  $|b| < n$ ,  $x$  will obey  $0 \leq x < \text{lcm}(m, n)$ .
- Assumes  $mn < 2^{62}$ .
- $O(\max(\log m, \log n))$

```

1 ll crt(ll a, ll m, ll b, ll n) {
2     if (n > m) swap(a, b), swap(m, n);
3     ll x, y, g = euclid(m, n, x, y);
4     assert((a - b) % g == 0); // else no solution
5     // can replace assert with whatever needed
6     x = (b - a) % n * x % n / g * m + a;
7     return x < 0 ? x + m*n/g : x;
8 }

```

## Linear Sieve

- Mobius Function

```

1 vector<int> prime;
2 bool is_composite[MAX_N];
3 int mu[MAX_N];
4
5 void sieve(int n){
6     fill(is_composite, is_composite + n, 0);
7     mu[1] = 1;
8     for (int i = 2; i < n; i++){
9         if (!is_composite[i]){
10             prime.push_back(i);
11             mu[i] = -1; // i is prime
12         }
13         for (int j = 0; j < prime.size() && i * prime[j] < n; j++){
14             is_composite[i * prime[j]] = true;
15             if (i % prime[j] == 0){
16                 mu[i * prime[j]] = 0; // prime[j] divides i
17                 break;
18             } else {
19                 mu[i * prime[j]] = -mu[i]; // prime[j] does not divide i
20             }
21         }
22     }
23 }

```

- Euler's Totient Function

```

1 vector<int> prime;
2 bool is_composite[MAX_N];
3 int phi[MAX_N];
4
5 void sieve(int n){
6     fill(is_composite, is_composite + n, 0);
7     phi[1] = 1;
8     for (int i = 2; i < n; i++){
9         if (!is_composite[i]){
10             prime.push_back(i);
11             phi[i] = i - 1; // i is prime
12         }
13         for (int j = 0; j < prime.size() && i * prime[j] < n; j++){
14             is_composite[i * prime[j]] = true;
15             if (i % prime[j] == 0){

```

```

16     phi[i * prime[j]] = phi[i] * prime[j]; //prime[j]
17     ↪ divides i
18     } else {
19     phi[i * prime[j]] = phi[i] * phi[prime[j]]; //prime[j]
20     ↪ does not divide i
21     }
22 }
23 }

```

## Gaussian Elimination

```

1 bool is_0(Z v) { return v.x == 0; }
2 Z abs(Z v) { return v; }
3 bool is_0(double v) { return abs(v) < 1e-9; }
4
5 // 1 => unique solution, 0 => no solution, -1 => multiple
6 ↪ solutions
7 template <typename T>
8 int gaussian_elimination(vector<vector<T>> &a, int limit) {
9     if (a.empty() || a[0].empty()) return -1;
10    int h = (int)a.size(), w = (int)a[0].size(), r = 0;
11    for (int c = 0; c < limit; c++) {
12        int id = -1;
13        for (int i = r; i < h; i++) {
14            if (!is_0(a[i][c]) && (id == -1 || abs(a[id][c]) <
15            ↪ abs(a[i][c]))) {
16                id = i;
17            }
18        }
19        if (id == -1) continue;
20        if (id > r) {
21            swap(a[r], a[id]);
22            for (int j = c; j < w; j++) a[id][j] = -a[id][j];
23        }
24        vector<int> nonzero;
25        for (int j = c; j < w; j++) {
26            if (!is_0(a[r][j])) nonzero.push_back(j);
27        }
28        T inv_a = 1 / a[r][c];
29        for (int i = r + 1; i < h; i++) {
30            if (is_0(a[i][c])) continue;
31            T coeff = -a[i][c] * inv_a;
32            for (int j : nonzero) a[i][j] += coeff * a[r][j];
33        }
34        ++r;
35    }
36    for (int row = h - 1; row >= 0; row--) {
37        for (int c = 0; c < limit; c++) {
38            if (!is_0(a[row][c])) {
39                T inv_a = 1 / a[row][c];
40                for (int i = row - 1; i >= 0; i--) {
41                    if (is_0(a[i][c])) continue;
42                    T coeff = -a[i][c] * inv_a;
43                    for (int j = c; j < w; j++) a[i][j] += coeff *
44                    ↪ a[row][j];
45                }
46                break;
47            }
48        }
49        // not-free variables: only it on its line
50        for (int i = r; i < h; i++) if (!is_0(a[i][limit])) return 0;
51        return (r == limit) ? 1 : -1;
52    }
53 }
54
55 template <typename T>
56 pair<int, vector<T>> solve_linear(vector<vector<T>> a, const
57 ↪ vector<T> &b, int w) {
58     int h = (int)a.size();
59     for (int i = 0; i < h; i++) a[i].push_back(b[i]);
60     int sol = gaussian_elimination(a, w);
61     if (!sol) return {0, vector<T>()};
62     vector<T> x(w, 0);
63     for (int i = 0; i < h; i++) {
64         for (int j = 0; j < w; j++) {
65             if (!is_0(a[i][j])) {

```

```

61         x[j] = a[i][w] / a[i][j];
62         break;
63     }
64 }
65 }
66 return {sol, x};
67 }

```

## Pollard-Rho Factorization

- Uses Miller–Rabin primality test
- $O(n^{1/4})$  (heuristic estimation)

```

1 typedef __int128_t i128;
2
3 i128 power(i128 a, i128 b, i128 MOD = 1, i128 res = 1) {
4     for (; b; b /= 2, (a *= a) %= MOD)
5         if (b & 1) (res *= a) %= MOD;
6     return res;
7 }
8
9 bool is_prime(ll n) {
10    if (n < 2) return false;
11    static constexpr int A[] = {2, 3, 5, 7, 11, 13, 17, 19, 23};
12    int s = __builtin_ctzll(n - 1);
13    ll d = (n - 1) >> s;
14    for (auto a : A) {
15        if (a == n) return true;
16        ll x = (ll)power(a, d, n);
17        if (x == 1 || x == n - 1) continue;
18        bool ok = false;
19        for (int i = 0; i < s - 1; ++i) {
20            x = ll((i128)x * x % n); // potential overflow!
21            if (x == n - 1) {
22                ok = true;
23                break;
24            }
25        }
26        if (!ok) return false;
27    }
28    return true;
29 }
30
31 ll pollard_rho(ll x) {
32     ll s = 0, t = 0, c = rng() % (x - 1) + 1;
33     ll stp = 0, goal = 1, val = 1;
34     for (goal = 1;; goal *= 2, s = t, val = 1) {
35         for (stp = 1; stp <= goal; ++stp) {
36             t = ll(((i128)t * t + c) % x);
37             val = ll((i128)val * abs(t - s) % x);
38             if ((stp % 127) == 0) {
39                 ll d = gcd(val, x);
40                 if (d > 1) return d;
41             }
42         }
43         ll d = gcd(val, x);
44         if (d > 1) return d;
45     }
46 }
47
48 ll get_max_factor(ll _x) {
49     ll max_factor = 0;
50     function<void(ll)> fac = [&](ll x) {
51         if (x <= max_factor || x < 2) return;
52         if (is_prime(x)) {
53             max_factor = max_factor > x ? max_factor : x;
54             return;
55         }
56         ll p = x;
57         while (p >= x) p = pollard_rho(x);
58         while ((x % p) == 0) x /= p;
59         fac(x), fac(p);
60     };
61     fac(_x);
62     return max_factor;
63 }

```

## Modular Square Root

- $O(\log^2 p)$  in worst case, typically  $O(\log p)$  for most  $p$

```

1 ll sqrt(ll a, ll p) {
2     a %= p; if (a < 0) a += p;
3     if (a == 0) return 0;
4     assert(pow(a, (p-1)/2, p) == 1); // else no solution
5     if (p % 4 == 3) return pow(a, (p+1)/4, p);
6     // a^(n+3)/8 or 2^(n+3)/8 * 2^(n-1)/4 works if p % 8 == 5
7     ll s = p - 1, n = 2;
8     int r = 0, m;
9     while (s % 2 == 0)
10         ++r, s /= 2;
11     /// find a non-square mod p
12     while (pow(n, (p - 1) / 2, p) != p - 1) ++n;
13     ll x = pow(a, (s + 1) / 2, p);
14     ll b = pow(a, s, p), g = pow(n, s, p);
15     for (; r = m) {
16         ll t = b;
17         for (m = 0; m < r && t != 1; ++m)
18             t = t * t % p;
19         if (m == 0) return x;
20         ll gs = pow(g, 1LL << (r - m - 1), p);
21         g = gs * gs % p;
22         x = x * gs % p;
23         b = b * g % p;
24     }
25 }

```

## Berlekamp-Massey

- Recovers any  $n$ -order linear recurrence relation from the first  $2n$  terms of the sequence.
- Input  $s$  is the sequence to be analyzed.
- Output  $c$  is the shortest sequence  $c_1, \dots, c_n$ , such that

$$s_m = \sum_{i=1}^n c_i \cdot s_{m-i}, \text{ for all } m \geq n.$$

- Be careful since  $c$  is returned in 0-based indexation.
- Complexity:  $O(N^2)$

```

1 vector<ll> berlekamp_massey(vector<ll> s) {
2     int n = sz(s), l = 0, m = 1;
3     vector<ll> b(n), c(n);
4     ll ldd = b[0] = c[0] = 1;
5     for (int i = 0; i < n; i++, m++) {
6         ll d = s[i];
7         for (int j = 1; j <= l; j++) d = (d + c[j] * s[i - j]) %
8         MOD;
9         if (d == 0) continue;
10        vector<ll> temp = c;
11        ll coef = d * power(ldd, MOD - 2) % MOD;
12        for (int j = m; j < n; j++){
13            c[j] = (c[j] + MOD - coef * b[j - m]) % MOD;
14            if (c[j] < 0) c[j] += MOD;
15        }
16        if (2 * l <= i) {
17            l = i + 1 - l;
18            b = temp;
19            ldd = d;
20            m = 0;
21        }
22    }
23    c.resize(l + 1);
24    c.erase(c.begin());
25    for (ll &x : c)
26        x = (MOD - x) % MOD;
27    return c;
28 }

```

## Calculating k-th term of a linear recurrence

- Given the first  $n$  terms  $s_0, s_1, \dots, s_{n-1}$  and the sequence  $c_1, c_2, \dots, c_n$  such that

$$s_m = \sum_{i=1}^n c_i \cdot s_{m-i}, \text{ for all } m \geq n,$$

the function `calc_kth` computes  $s_k$ .

- Complexity:  $O(n^2 \log k)$

```

1 vector<ll> poly_mult_mod(vector<ll> p, vector<ll> q,
2     vector<ll>& c){
3     vector<ll> ans(sz(p) + sz(q) - 1);
4     for (int i = 0; i < sz(p); i++){
5         for (int j = 0; j < sz(q); j++){
6             ans[i + j] = (ans[i + j] + p[i] * q[j]) % MOD;
7         }
8     }
9     int n = sz(ans), m = sz(c);
10    for (int i = n - 1; i >= m; i--){
11        for (int j = 0; j < m; j++){
12            ans[i - 1 - j] = (ans[i - 1 - j] + c[j] * ans[i]) % MOD;
13        }
14    }
15    ans.resize(m);
16    return ans;
17 }
18 ll calc_kth(vector<ll> s, vector<ll> c, ll k){
19     assert(sz(s) >= sz(c)); // size of s can be greater than c,
20     // but not less
21     if (k < sz(s)) return s[k];
22     vector<ll> res{1};
23     for (vector<ll> poly = {0, 1}; k; poly = poly_mult_mod(poly,
24         poly, c), k >>= 1){
25         if (k & 1) res = poly_mult_mod(res, poly, c);
26     }
27     ll ans = 0;
28     for (int i = 0; i < min(sz(res), sz(c)); i++) ans = (ans +
29         s[i] * res[i]) % MOD;
30     return ans;
31 }

```

## Partition Function

- Returns number of partitions of  $n$  in  $O(n^{1.5})$

```

1 int partition(int n) {
2     int dp[n + 1];
3     dp[0] = 1;
4     for (int i = 1; i <= n; i++) {
5         dp[i] = 0;
6         for (int j = 1, r = 1; i - (3 * j * j - j) / 2 >= 0; ++j,
7             r *= -1) {
8             dp[i] += dp[i - (3 * j * j - j) / 2] * r;
9             if (i - (3 * j * j + j) / 2 >= 0) dp[i] += dp[i - (3 * j * j + j) / 2] * r;
10        }
11    }
12    return dp[n];
13 }

```

## NTT

```

1 void ntt(vector<ll>& a, int f) {
2     int n = int(a.size());
3     vector<ll> w(n);
4     vector<int> rev(n);
5     for (int i = 0; i < n; i++) rev[i] = (rev[i / 2] / 2) | ((i
6         & 1) * (n / 2));
7     for (int i = 0; i < n; i++) {
8         if (i < rev[i]) swap(a[i], a[rev[i]]);
9     }
10    ll wn = power(f ? (MOD + 1) / 3 : 3, (MOD - 1) / n);

```

```

10 w[0] = 1;
11 for (int i = 1; i < n; i++) w[i] = w[i - 1] * wn % MOD;
12 for (int mid = 1; mid < n; mid *= 2) {
13     for (int i = 0; i < n; i += 2 * mid) {
14         for (int j = 0; j < mid; j++) {
15             ll x = a[i + j], y = a[i + j + mid] * w[n / (2 * mid)
↵ * j] % MOD;
16             a[i + j] = (x + y) % MOD, a[i + j + mid] = (x + MOD -
↵ y) % MOD;
17         }
18     }
19 }
20 if (f) {
21     ll iv = power(n, MOD - 2);
22     for (auto& x : a) x = x * iv % MOD;
23 }
24 }
25 vector<ll> mul(vector<ll> a, vector<ll> b) {
26     int n = 1, m = (int)a.size() + (int)b.size() - 1;
27     while (n < m) n *= 2;
28     a.resize(n), b.resize(n);
29     ntt(a, 0), ntt(b, 0); // if squaring, you can save one NTT
↵ here
30     for (int i = 0; i < n; i++) a[i] = a[i] * b[i] % MOD;
31     ntt(a, 1);
32     a.resize(m);
33     return a;
34 }

```

## FFT

```

1 const ld PI = acos(-1);
2 auto mul = [&](const vector<ld>& aa, const vector<ld>& bb) {
3     int n = (int)aa.size(), m = (int)bb.size(), bit = 1;
4     while ((1 << bit) < n + m - 1) bit++;
5     int len = 1 << bit;
6     vector<complex<ld>> a(len), b(len);
7     vector<int> rev(len);
8     for (int i = 0; i < n; i++) a[i].real(aa[i]);
9     for (int i = 0; i < m; i++) b[i].real(bb[i]);
10    for (int i = 0; i < len; i++) rev[i] = (rev[i >> 1] >> 1) |
↵ ((i & 1) << (bit - 1));
11    auto fft = [&](vector<complex<ld>>& p, int inv) {
12        for (int i = 0; i < len; i++)
13            if (i < rev[i]) swap(p[i], p[rev[i]]);
14        for (int mid = 1; mid < len; mid *= 2) {
15            auto w1 = complex<ld>(cos(PI / mid), (inv ? -1 : 1) *
↵ sin(PI / mid));
16            for (int i = 0; i < len; i += mid * 2) {
17                auto wk = complex<ld>(1, 0);
18                for (int j = 0; j < mid; j++, wk = wk * w1) {
19                    auto x = p[i + j], y = wk * p[i + j + mid];
20                    p[i + j] = x + y, p[i + j + mid] = x - y;
21                }
22            }
23        }
24        if (inv == 1) {
25            for (int i = 0; i < len; i++) p[i].real(p[i].real() /
↵ len);
26        }
27    };
28    fft(a, 0), fft(b, 0);
29    for (int i = 0; i < len; i++) a[i] = a[i] * b[i];
30    fft(a, 1);
31    a.resize(n + m - 1);
32    vector<ld> res(n + m - 1);
33    for (int i = 0; i < n + m - 1; i++) res[i] = a[i].real();
34    return res;
35 };

```

## MIT's FFT/NTT, Polynomial mod/log/exp Template

- For integers rounding works if  $(|a| + |b|) \max(a, b) < \sim 10^9$ , or in theory maybe  $10^6$

- $\frac{1}{P(x)}$  in  $O(n \log n)$ ,  $e^{P(x)}$  in  $O(n \log n)$ ,  $\ln(P(x))$  in  $O(n \log n)$ ,  $P(x)^k$  in  $O(n \log n)$ , Evaluates  $P(x_1), \dots, P(x_n)$  in  $O(n \log^2 n)$ , Lagrange Interpolation in  $O(n \log^2 n)$

```

1 // use #define FFT 1 to use FFT instead of NTT (default)
2 // Examples:
3 // poly a(n+1); // constructs degree n poly
4 // a[0].v = 10; // assigns constant term a_0 = 10
5 // poly b = exp(a);
6 // poly is vector<num>
7 // for NTT, num stores just one int named v
8 // for FFT, num stores two doubles named x (real), y (imag)
9
10 #define sz(x) ((int)x.size())
11 #define rep(i, j, k) for (int i = int(j); i < int(k); i++)
12 #define trav(a, x) for (auto &a : x)
13 #define per(i, a, b) for (int i = (b)-1; i >= (a); --i)
14 using ll = long long;
15 using vi = vector<int>;
16
17 namespace fft {
18     #if FFT
19     // FFT
20     using dbl = double;
21     struct num {
22         dbl x, y;
23         num(dbl x_ = 0, dbl y_ = 0): x(x_), y(y_) {}
24     };
25     inline num operator+(num a, num b) {
26         return num(a.x + b.x, a.y + b.y);
27     }
28     inline num operator-(num a, num b) {
29         return num(a.x - b.x, a.y - b.y);
30     }
31     inline num operator*(num a, num b) {
32         return num(a.x * b.x - a.y * b.y, a.x * b.y + a.y * b.x);
33     }
34     inline num conj(num a) { return num(a.x, -a.y); }
35     inline num inv(num a) {
36         dbl n = (a.x * a.x + a.y * a.y);
37         return num(a.x / n, -a.y / n);
38     }
39
40     #else
41     // NTT
42     const int mod = 998244353, g = 3;
43     // For p < 2^30 there is also (5 << 25, 3), (7 << 26, 3),
44     // (479 << 21, 3) and (483 << 21, 5). Last two are > 10^9.
45     struct num {
46         int v;
47         num(ll v_ = 0): v(int(v_ % mod)) {
48             if (v < 0) v += mod;
49         }
50         explicit operator int() const { return v; }
51     };
52     inline num operator+(num a, num b) { return num(a.v + b.v); }
53     inline num operator-(num a, num b) {
54         return num(a.v + mod - b.v);
55     }
56     inline num operator*(num a, num b) {
57         return num(1ll * a.v * b.v);
58     }
59     inline num pow(num a, int b) {
60         num r = 1;
61         do {
62             if (b & 1) r = r * a;
63             a = a * a;
64         } while (b >>= 1);
65         return r;
66     }
67     inline num inv(num a) { return pow(a, mod - 2); }
68
69     #endif
70     using vn = vector<num>;
71     vi rev({0, 1});

```



```

72 vn rt(2, num(1)), fa, fb;
73 inline void init(int n) {
74     if (n <= sz(rt)) return;
75     rev.resize(n);
76     rep(i, 0, n) rev[i] = (rev[i >> 1] | ((i & 1) * n)) >> 1;
77     rt.reserve(n);
78     for (int k = sz(rt); k < n; k *= 2) {
79         rt.resize(2 * k);
80     #if FFT
81         double a = M_PI / k;
82         num z(cos(a), sin(a)); // FFT
83     #else
84         num z = pow(num(g), (mod - 1) / (2 * k)); // NTT
85     #endif
86     rep(i, k / 2, k) rt[2 * i] = rt[i],
87         rt[2 * i + 1] = rt[i] * z;
88     }
89 }
90 inline void fft(vector<num>& a, int n) {
91     init(n);
92     int s = __builtin_ctz(sz(rev) / n);
93     rep(i, 0, n) if (i < rev[i] >> s) swap(a[i], a[rev[i] >>
94     s]);
95     for (int k = 1; k < n; k *= 2)
96         for (int i = 0; i < n; i += 2 * k) rep(j, 0, k) {
97             num t = rt[j + k] * a[i + j + k];
98             a[i + j + k] = a[i + j] - t;
99             a[i + j] = a[i + j] + t;
100         }
101     // Complex/NTT
102     vn multiply(vn a, vn b) {
103         int s = sz(a) + sz(b) - 1;
104         if (s <= 0) return {};
105         int L = s > 1 ? 32 - __builtin_clz(s - 1) : 0, n = 1 << L;
106         a.resize(n), b.resize(n);
107         fft(a, n);
108         fft(b, n);
109         num d = inv(num(n));
110         rep(i, 0, n) a[i] = a[i] * b[i] * d;
111         reverse(a.begin() + 1, a.end());
112         fft(a, n);
113         a.resize(s);
114         return a;
115     }
116     // Complex/NTT power-series inverse
117     // Doubles b as b[:n] = (2 - a[:n] * b[:n/2]) * b[:n/2]
118     vn inverse(const vn& a) {
119         if (a.empty()) return {};
120         vn b({inv(a[0])});
121         b.reserve(2 * a.size());
122         while (sz(b) < sz(a)) {
123             int n = 2 * sz(b);
124             b.resize(2 * n, 0);
125             if (sz(fa) < 2 * n) fa.resize(2 * n);
126             fill(fa.begin(), fa.begin() + 2 * n, 0);
127             copy(a.begin(), a.begin() + min(n, sz(a)), fa.begin());
128             fft(b, 2 * n);
129             fft(fa, 2 * n);
130             num d = inv(num(2 * n));
131             rep(i, 0, 2 * n) b[i] = b[i] * (2 - fa[i] * b[i]) * d;
132             reverse(b.begin() + 1, b.end());
133             fft(b, 2 * n);
134             b.resize(n);
135         }
136         b.resize(a.size());
137         return b;
138     }
139     #if FFT
140     // Double multiply (num = complex)
141     using vd = vector<double>;
142     vd multiply(const vd& a, const vd& b) {
143         int s = sz(a) + sz(b) - 1;
144         if (s <= 0) return {};
145         int L = s > 1 ? 32 - __builtin_clz(s - 1) : 0, n = 1 << L;
146         if (sz(fa) < n) fa.resize(n);
147         if (sz(fb) < n) fb.resize(n);

```

```

148         fill(fa.begin(), fa.begin() + n, 0);
149         rep(i, 0, sz(a)) fa[i].x = a[i];
150         rep(i, 0, sz(b)) fa[i].y = b[i];
151         fft(fa, n);
152         trav(x, fa) x = x * x;
153         rep(i, 0, n) fb[i] = fa[(n - i) & (n - 1)] - conj(fa[i]);
154         fft(fb, n);
155         vd r(s);
156         rep(i, 0, s) r[i] = fb[i].y / (4 * n);
157         return r;
158     }
159     // Integer multiply mod m (num = complex)
160     vi multiply_mod(const vi& a, const vi& b, int m) {
161         int s = sz(a) + sz(b) - 1;
162         if (s <= 0) return {};
163         int L = s > 1 ? 32 - __builtin_clz(s - 1) : 0, n = 1 << L;
164         if (sz(fa) < n) fa.resize(n);
165         if (sz(fb) < n) fb.resize(n);
166         rep(i, 0, sz(a)) fa[i] =
167             num(a[i] & ((1 << 15) - 1), a[i] >> 15);
168         fill(fa.begin() + sz(a), fa.begin() + n, 0);
169         rep(i, 0, sz(b)) fb[i] =
170             num(b[i] & ((1 << 15) - 1), b[i] >> 15);
171         fill(fb.begin() + sz(b), fb.begin() + n, 0);
172         fft(fa, n);
173         fft(fb, n);
174         double r0 = 0.5 / n; // 1/2n
175         rep(i, 0, n / 2 + 1) {
176             int j = (n - i) & (n - 1);
177             num g0 = (fb[i] + conj(fb[j])) * r0;
178             num g1 = (fb[i] - conj(fb[j])) * r0;
179             swap(g1.x, g1.y);
180             g1.y *= -1;
181             if (j != i) {
182                 swap(fa[j], fa[i]);
183                 fb[j] = fa[j] * g1;
184                 fa[j] = fa[j] * g0;
185             }
186             fb[i] = fa[i] * conj(g1);
187             fa[i] = fa[i] * conj(g0);
188         }
189         fft(fa, n);
190         fft(fb, n);
191         vi r(s);
192         rep(i, 0, s) r[i] =
193             int((ll(fa[i].x + 0.5) + (ll(fa[i].y + 0.5) % m << 15) +
194                 (ll(fb[i].x + 0.5) % m << 15) +
195                 (ll(fb[i].y + 0.5) % m << 30)) %
196                 m);
197         return r;
198     }
199     #endif
200 } // namespace fft
201 // For multiply_mod, use num = modnum, poly = vector<num>
202 using fft::num;
203 using poly = fft::vn;
204 using fft::multiply;
205 using fft::inverse;
206
207 poly& operator+=(poly& a, const poly& b) {
208     if (sz(a) < sz(b)) a.resize(b.size());
209     rep(i, 0, sz(b)) a[i] = a[i] + b[i];
210     return a;
211 }
212 poly operator+(const poly& a, const poly& b) {
213     poly r = a;
214     r += b;
215     return r;
216 }
217 poly& operator-=(poly& a, const poly& b) {
218     if (sz(a) < sz(b)) a.resize(b.size());
219     rep(i, 0, sz(b)) a[i] = a[i] - b[i];
220     return a;
221 }
222 poly operator-(const poly& a, const poly& b) {
223     poly r = a;
224     r -= b;

```

```

225     return r;
226 }
227 poly operator*(const poly& a, const poly& b) {
228     return multiply(a, b);
229 }
230 poly& operator*=(poly& a, const poly& b) { return a = a * b; }
231
232 poly& operator*=(poly& a, const num& b) { // Optional
233     trav(x, a) x = x * b;
234     return a;
235 }
236 poly operator*(const poly& a, const num& b) {
237     poly r = a;
238     r *= b;
239     return r;
240 }
241 // Polynomial floor division; no leading 0's please
242 poly operator/(poly a, poly b) {
243     if (sz(a) < sz(b)) return {};
244     int s = sz(a) - sz(b) + 1;
245     reverse(a.begin(), a.end());
246     reverse(b.begin(), b.end());
247     a.resize(s);
248     b.resize(s);
249     a = a * inverse(move(b));
250     a.resize(s);
251     reverse(a.begin(), a.end());
252     return a;
253 }
254 poly& operator/=(poly& a, const poly& b) { return a = a / b; }
255 poly& operator%=(poly& a, const poly& b) {
256     if (sz(a) >= sz(b)) {
257         poly c = (a / b) * b;
258         a.resize(sz(b) - 1);
259         rep(i, 0, sz(a)) a[i] = a[i] - c[i];
260     }
261     return a;
262 }
263 poly operator%(const poly& a, const poly& b) {
264     poly r = a;
265     r %= b;
266     return r;
267 }
268 // Log/exp/pow
269 poly deriv(const poly& a) {
270     if (a.empty()) return {};
271     poly b(sz(a) - 1);
272     rep(i, 1, sz(a)) b[i - 1] = a[i] * i;
273     return b;
274 }
275 poly integ(const poly& a) {
276     poly b(sz(a) + 1);
277     b[1] = 1; // mod p
278     rep(i, 2, sz(b)) b[i] =
279         b[fft::mod % i] * (-fft::mod / i); // mod p
280     rep(i, 1, sz(b)) b[i] = a[i - 1] * b[i]; // mod p
281     // rep(i, 1, sz(b)) b[i] = a[i - 1] * inv(num(i)); // else
282     return b;
283 }
284 poly log(const poly& a) { // MUST have a[0] == 1
285     poly b = integ(deriv(a) * inverse(a));
286     b.resize(a.size());
287     return b;
288 }
289 poly exp(const poly& a) { // MUST have a[0] == 0
290     poly b(1, num(1));
291     if (a.empty()) return b;
292     while (sz(b) < sz(a)) {
293         int n = min(sz(b) * 2, sz(a));
294         b.resize(n);
295         poly v = poly(a.begin(), a.begin() + n) - log(b);
296         v[0] = v[0] + num(1);
297         b *= v;
298         b.resize(n);
299     }
300     return b;
301 }

```

```

302 poly pow(const poly& a, int m) { // m >= 0
303     poly b(a.size());
304     if (!m) {
305         b[0] = 1;
306         return b;
307     }
308     int p = 0;
309     while (p < sz(a) && a[p].v == 0) ++p;
310     if (1ll * m * p >= sz(a)) return b;
311     num mu = pow(a[p], m), di = inv(a[p]);
312     poly c(sz(a) - m * p);
313     rep(i, 0, sz(c)) c[i] = a[i + p] * di;
314     c = log(c);
315     trav(v, c) v = v * m;
316     c = exp(c);
317     rep(i, 0, sz(c)) b[i + m * p] = c[i] * mu;
318     return b;
319 }
320 // Multipoint evaluation/interpolation
321
322 vector<num> eval(const poly& a, const vector<num>& x) {
323     int n = sz(x);
324     if (!n) return {};
325     vector<poly> up(2 * n);
326     rep(i, 0, n) up[i + n] = poly({0 - x[i], 1});
327     per(i, 1, n) up[i] = up[2 * i] * up[2 * i + 1];
328     vector<poly> down(2 * n);
329     down[1] = a % up[1];
330     rep(i, 2, 2 * n) down[i] = down[i / 2] % up[i];
331     vector<num> y(n);
332     rep(i, 0, n) y[i] = down[i + n][0];
333     return y;
334 }
335
336 poly interp(const vector<num>& x, const vector<num>& y) {
337     int n = sz(x);
338     assert(n);
339     vector<poly> up(n * 2);
340     rep(i, 0, n) up[i + n] = poly({0 - x[i], 1});
341     per(i, 1, n) up[i] = up[2 * i] * up[2 * i + 1];
342     vector<num> a = eval(deriv(up[1]), x);
343     vector<poly> down(2 * n);
344     rep(i, 0, n) down[i + n] = poly({y[i] * inv(a[i])});
345     per(i, 1, n) down[i] =
346         down[i * 2] * up[i * 2 + 1] + down[i * 2 + 1] * up[i * 2];
347     return down[1];
348 }

```

## Simplex method for linear programs

- Maximize  $c^T x$  subject to  $Ax \leq b, x \geq 0$ .
- Returns  $-\infty$  if there is no solution,  $+\infty$  if there are arbitrarily good solutions, or the maximum value of  $c^T x$  otherwise. The (arbitrary) input vector is set to an optimal  $x$  (or in the unbounded case, an arbitrary solution fulfilling the constraints). Numerical stability is not guaranteed. For better performance, define variables such that  $x = 0$  is viable.
- Complexity:  $O(NM \cdot \text{pivots})$ .  $O(2^n)$  in general (very hard to achieve).

```

1  typedef double T; // might be much slower with long doubles
2  typedef vector<T> vd;
3  typedef vector<vd> vvd;
4  const T eps = 1e-8, inf = 1/.0;
5  #define MP make_pair
6  #define ltj(X) if(s == -1 || MP(X[j], N[j]) < MP(X[s], N[s]))
7  //   s=j
8  #define rep(i, a, b) for(int i = a; i < (b); ++i)
9
10 struct LPSolver {
11     int m, n;
12     vector<int> N, B;
13     vvd D;

```



```

13  LPSolver(const vvd& A, const vd& b, const vd& c) : m(sz(b)),
↳ n(sz(c)), N(n+1), B(m), D(m+2, vd(n+2)){
14      rep(i,0,m) rep(j,0,n) D[i][j] = A[i][j];
15      rep(i,0,m) { B[i] = n+i; D[i][n] = -1; D[i][n+1] = b[i]; }
↳ rep(j,0,n) { N[j] = j; D[m][j] = -c[j]; }
16      N[n] = -1; D[m+1][n] = 1;
17  };
18  void pivot(int r, int s){
19      T *a = D[r].data(), inv = 1 / a[s];
20      rep(i,0,m+2) if (i != r && abs(D[i][s]) > eps) {
21          T *b = D[i].data(), inv2 = b[s] * inv;
22          rep(j,0,n+2) b[j] -= a[j] * inv2;
23          b[s] = a[s] * inv2;
24      }
25      rep(j,0,n+2) if (j != s) D[r][j] *= inv;
26      rep(i,0,m+2) if (i != r) D[i][s] *= -inv;
27      D[r][s] = inv;
28      swap(B[r], N[s]);
29  }
30  bool simplex(int phase){
31      int x = m + phase - 1;
32      for (;;) {
33          int s = -1;
34          rep(j,0,n+1) if (N[j] != -phase) ltj(D[x]); if (D[x][s]
↳ >= -eps) return true;
35          int r = -1;
36          rep(i,0,m) {
37              if (D[i][s] <= eps) continue;
38              if (r == -1 || MP(D[i][n+1] / D[i][s], B[i]) <
↳ MP(D[r][n+1] / D[r][s], B[r])) r = i;
39          }
40          if (r == -1) return false;
41          pivot(r, s);
42      }
43  }
44  T solve(vd &x){
45      int r = 0;
46      rep(i,1,m) if (D[i][n+1] < D[r][n+1]) r = i;
47      if (D[r][n+1] < -eps) {
48          pivot(r, n);
49          if (!simplex(2) || D[m+1][n+1] < -eps) return -inf;
50      }
51      rep(i,0,m) if (B[i] == -1) {
52          int s = 0;
53          rep(j,1,n+1) ltj(D[i]);
54          pivot(i, s);
55      }
56      bool ok = simplex(1); x = vd(n);
57      rep(i,0,m) if (B[i] < n) x[B[i]] = D[i][n+1];
58      return ok ? D[m][n+1] : inf;
59  }
60  };

```

## Matroid Intersection

- Matroid is a pair  $\langle X, I \rangle$ , where  $X$  is a finite set and  $I$  is a family of subsets of  $X$  satisfying:
  - $\emptyset \in I$ .
  - If  $A \in I$  and  $B \subseteq A$ , then  $B \in I$ .
  - If  $A, B \in I$  and  $|A| > |B|$ , then there exists  $x \in A \setminus B$  such that  $B \cup \{x\} \in I$ .
- Set  $S$  is called **independent** if  $S \in I$ .
- Common matroids:** uniform (sets of bounded size); colorful (sets of colored elements where each color only appears once); graphic (acyclic sets of edges in a graph); linear-algebraic (sets of linearly independent vectors).
- Matroid Intersection Problem:** Given two matroids, find the largest common independent set.
- A matroid has 3 functions:
  - $check(int\ x)$ : returns if current matroid can add  $x$  without becoming dependent.
  - $add(int\ x)$ : adds an element to the matroid (guar-

anteed to never make it dependent).

–  $clear()$ : sets the matroid to the empty matroid.

- The matroid is given an *int* representing the element, and is expected to convert it (e.g: color or edge endpoints)
- Pass the matroid with more expensive add/clear operations to M1.
- Complexity:**  $R^2 \cdot N \cdot (M2.add + M1.check + M2.check) + R^3 \cdot (M1.add) + R^2 \cdot (M1.clear) + R \cdot N \cdot (M2.clear)$ , where  $R = answer$ .

```

1  // Example matroid
2  struct GraphicMatroid{
3      vector<pair<int, int>> e;
4      int n;
5      DSU dsu;
6
7
8      GraphicMatroid(vector<pair<int, int>> edges, int vertices){
9          e = edges, n = vertices;
10         dsu = DSU(n);
11     };
12     bool check(int idx){
13         return !dsu.same(e[idx].fi, e[idx].se);
14     }
15     void add(int idx){
16         dsu.unite(e[idx].fi, e[idx].se);
17     }
18     void clear(){
19         dsu = DSU(n);
20     }
21 };
22
23 template <class M1, class M2> struct MatroidIsect {
24     int n;
25     vector<char> iset;
26     M1 m1; M2 m2;
27     MatroidIsect(M1 m1, M2 m2, int n) : n(n), iset(n + 1),
↳ m1(m1), m2(m2) {}
28     vector<int> solve() {
29         for (int i = 0; i < n; i++) if (m1.check(i) &&
↳ m2.check(i))
30             iset[i] = true, m1.add(i), m2.add(i);
31         while (augment());
32         vector<int> ans;
33         for (int i = 0; i < n; i++) if (iset[i])
↳ ans.push_back(i);
34         return ans;
35     }
36     bool augment() {
37         vector<int> frm(n, -1);
38         queue<int> q({n}); // starts at dummy node
39         auto fwdE = [&](int a) {
40             vector<int> ans;
41             m1.clear();
42             for (int v = 0; v < n; v++) if (iset[v] && v != a)
↳ m1.add(v);
43             for (int b = 0; b < n; b++) if (!iset[b] && frm[b]
↳ == -1 && m1.check(b))
44                 ans.push_back(b), frm[b] = a;
45             return ans;
46         };
47         auto backE = [&](int b) {
48             m2.clear();
49             for (int cas = 0; cas < 2; cas++) for (int v = 0;
↳ v < n; v++){
50                 if ((v == b || iset[v]) && (frm[v] == -1) ==
↳ cas) {
51                     if (!m2.check(v))
52                         return cas ? q.push(v), frm[v] = b, v
↳ : -1;
53                     m2.add(v);
54                 }
55             }
56             return n;
57         };

```

```

58     while (!q.empty()) {
59         int a = q.front(), c; q.pop();
60         for (int b : fwdE(a))
61             while ((c = backE(b)) >= 0) if (c == n) {
62                 while (b != n) iset[b] ^= 1, b = frm[b];
63                 return true;
64             }
65     }
66     return false;
67 }
68 };
69
70 /*
71 Usage:
72 MatroidIsect<GraphicMatroid, ColorfulMatroid> solver(matroid1,
73     ↪ matroid2, n);
74 vector<int> answer = solver.solve();
75 */

```

## Data Structures

### Fenwick Tree

```

1 ll sum(int r) {
2     ll ret = 0;
3     for (; r >= 0; r = (r & r + 1) - 1) ret += bit[r];
4     return ret;
5 }
6 void add(int idx, ll delta) {
7     for (; idx < n; idx |= idx + 1) bit[idx] += delta;
8 }

```

### Lazy Propagation SegTree

```

1 // Clear: clear() or build()
2 const int N = 2e5 + 10; // Change the constant!
3 template<typename T>
4 struct LazySegTree{
5     T t[4 * N];
6     T lazy[4 * N];
7     int n;
8
9     // Change these functions, default return, and lazy mark.
10    T default_return = 0, lazy_mark = numeric_limits<T>::min();
11    // Lazy mark is how the algorithm will identify that no
12    ↪ propagation is needed.
13    function<T(T, T)> f = [&] (T a, T b){
14        return a + b;
15    };
16    // f_on_seg calculates the function f, knowing the lazy
17    ↪ value on segment,
18    // segment's size and the previous value.
19    // The default is segment modification for RSQ. For
20    ↪ increments change to:
21    //     return cur_seg_val + seg_size * lazy_val;
22    // For RMQ. Modification: return lazy_val; Increments:
23    ↪ return cur_seg_val + lazy_val;
24    function<T(T, int, T)> f_on_seg = [&] (T cur_seg_val, int
25    ↪ seg_size, T lazy_val){
26        return seg_size * lazy_val;
27    };
28    // upd_lazy updates the value to be propagated to child
29    ↪ segments.
30    // Default: modification. For increments change to:
31    //     lazy[v] = (lazy[v] == lazy_mark? val : lazy[v] +
32    ↪ val);
33    function<void(int, T)> upd_lazy = [&] (int v, T val){
34        lazy[v] = val;
35    };
36    // Tip: for "get element on single index" queries, use max()
37    ↪ on segment: no overflows.
38
39    LazySegTree(int n_) : n(n_) {
40        clear(n);
41    }
42 }

```

```

34
35 void build(int v, int tl, int tr, vector<T>& a){
36     if (tl == tr) {
37         t[v] = a[tl];
38         return;
39     }
40     int tm = (tl + tr) / 2;
41     // left child: [tl, tm]
42     // right child: [tm + 1, tr]
43     build(2 * v + 1, tl, tm, a);
44     build(2 * v + 2, tm + 1, tr, a);
45     t[v] = f(t[2 * v + 1], t[2 * v + 2]);
46 }
47
48 LazySegTree(vector<T>& a){
49     build(a);
50 }
51
52 void push(int v, int tl, int tr){
53     if (lazy[v] == lazy_mark) return;
54     int tm = (tl + tr) / 2;
55     t[2 * v + 1] = f_on_seg(t[2 * v + 1], tm - tl + 1,
56     ↪ lazy[v]);
57     t[2 * v + 2] = f_on_seg(t[2 * v + 2], tr - tm, lazy[v]);
58     upd_lazy(2 * v + 1, lazy[v]), upd_lazy(2 * v + 2,
59     ↪ lazy[v]);
60     lazy[v] = lazy_mark;
61 }
62
63 void modify(int v, int tl, int tr, int l, int r, T val){
64     if (l > r) return;
65     if (tl == l && tr == r){
66         t[v] = f_on_seg(t[v], tr - tl + 1, val);
67         upd_lazy(v, val);
68         return;
69     }
70     push(v, tl, tr);
71     int tm = (tl + tr) / 2;
72     modify(2 * v + 1, tl, tm, l, min(r, tm), val);
73     modify(2 * v + 2, tm + 1, tr, max(l, tm + 1), r, val);
74     t[v] = f(t[2 * v + 1], t[2 * v + 2]);
75 }
76
77 T query(int v, int tl, int tr, int l, int r) {
78     if (l > r) return default_return;
79     if (tl == l && tr == r) return t[v];
80     push(v, tl, tr);
81     int tm = (tl + tr) / 2;
82     return f(
83         query(2 * v + 1, tl, tm, l, min(r, tm)),
84         query(2 * v + 2, tm + 1, tr, max(l, tm + 1), r)
85     );
86 }
87
88 void modify(int l, int r, T val){
89     modify(0, 0, n - 1, l, r, val);
90 }
91
92 T query(int l, int r){
93     return query(0, 0, n - 1, l, r);
94 }
95
96 T get(int pos){
97     return query(pos, pos);
98 }
99
100 // Change clear() function to t.clear() if using
101 ↪ unordered_map for SegTree!!!
102 void clear(int n_){
103     n = n_;
104     for (int i = 0; i < 4 * n; i++) t[i] = 0, lazy[i] =
105     ↪ lazy_mark;
106 }
107
108 void build(vector<T>& a){
109     n = sz(a);
110     clear(n);
111 }

```

```

107     build(0, 0, n - 1, a);
108 }
109 };

```

## Sparse Table

```

1  const int N = 2e5 + 10, LOG = 20; // Change the constant!
2  template<typename T>
3  struct SparseTable{
4      int lg[N];
5      T st[N][LOG];
6      int n;
7
8      // Change this function
9      function<T(T, T)> f = [&] (T a, T b){
10         return min(a, b);
11     };
12
13     void build(vector<T>& a){
14         n = sz(a);
15         lg[1] = 0;
16         for (int i = 2; i <= n; i++) lg[i] = lg[i / 2] + 1;
17
18         for (int k = 0; k < LOG; k++){
19             for (int i = 0; i < n; i++){
20                 if (!k) st[i][k] = a[i];
21                 else st[i][k] = f(st[i][k - 1], st[min(n - 1, i + (1 <<
22                     (k - 1))))][k - 1]);
23             }
24         }
25
26         T query(int l, int r){
27             int sz = r - l + 1;
28             return f(st[l][lg[sz]], st[r - (1 << lg[sz]) + 1][lg[sz]]);
29         }
30     };

```

## Suffix Array and LCP array

- (uses SparseTable above)

```

1  struct SuffixArray{
2      vector<int> p, c, h;
3      SparseTable<int> st;
4      /*
5       * In the end, array c gives the position of each suffix in p
6       * using 1-based indexation!
7       */
8
9      SuffixArray() {}
10
11     SuffixArray(string s){
12         buildArray(s);
13         buildLCP(s);
14         buildSparse();
15     }
16
17     void buildArray(string s){
18         int n = sz(s) + 1;
19         p.resize(n), c.resize(n);
20         for (int i = 0; i < n; i++) p[i] = i;
21         sort(all(p), [&] (int a, int b){return s[a] < s[b];});
22         c[p[0]] = 0;
23         for (int i = 1; i < n; i++){
24             c[p[i]] = c[p[i - 1]] + (s[p[i]] != s[p[i - 1]]);
25         }
26         vector<int> p2(n), c2(n);
27         // w is half-length of each string.
28         for (int w = 1; w < n; w <= 1){
29             for (int i = 0; i < n; i++){
30                 p2[i] = (p[i] - w + n) % n;
31             }
32             vector<int> cnt(n);
33             for (auto i : c) cnt[i]++;
34             for (int i = 1; i < n; i++) cnt[i] += cnt[i - 1];

```

```

35         for (int i = n - 1; i >= 0; i--){
36             p[--cnt[c[p2[i]]]] = p2[i];
37         }
38         c2[p[0]] = 0;
39         for (int i = 1; i < n; i++){
40             c2[p[i]] = c2[p[i - 1]] +
41                 (c[p[i]] != c[p[i - 1]] ||
42                  c[(p[i] + w) % n] != c[(p[i - 1] + w) % n]);
43         }
44         c.swap(c2);
45     }
46     p.erase(p.begin());
47 }
48
49 void buildLCP(string s){
50     // The algorithm assumes that suffix array is already
51     // built on the same string.
52     int n = sz(s);
53     h.resize(n - 1);
54     int k = 0;
55     for (int i = 0; i < n; i++){
56         if (c[i] == n){
57             k = 0;
58             continue;
59         }
60         int j = p[c[i]];
61         while (i + k < n && j + k < n && s[i + k] == s[j + k])
62             k++;
63         h[c[i] - 1] = k;
64         if (k) k--;
65     }
66     /*
67     Then an RMQ Sparse Table can be built on array h
68     to calculate LCP of 2 non-consecutive suffixes.
69     */
70 }
71
72 void buildSparse(){
73     st.build(h);
74 }
75
76 // l and r must be in 0-BASED INDEXATION
77 int lcp(int l, int r){
78     l = c[l] - 1, r = c[r] - 1;
79     if (l > r) swap(l, r);
80     return st.query(l, r - 1);
81 }

```

## Aho Corasick Trie

- For each node in the trie, the suffix link points to the longest proper suffix of the represented string. The terminal-link tree has square-root height (can be constructed by DFS).

```

1  const int S = 26;
2
3  // Function converting char to int.
4  int ctoi(char c){
5      return c - 'a';
6  }
7
8  // To add terminal links, use DFS
9  struct Node{
10     vector<int> nxt;
11     int link;
12     bool terminal;
13
14     Node() {
15         nxt.assign(S, -1), link = 0, terminal = 0;
16     }
17 };
18
19 vector<Node> trie(1);
20

```

```

21 // add_string returns the terminal vertex.
22 int add_string(string& s){
23     int v = 0;
24     for (auto c : s){
25         int cur = ctoi(c);
26         if (trie[v].nxt[cur] == -1){
27             trie[v].nxt[cur] = sz(trie);
28             trie.emplace_back();
29         }
30         v = trie[v].nxt[cur];
31     }
32     trie[v].terminal = 1;
33     return v;
34 }
35
36 /*
37 Suffix links are compressed.
38 This means that:
39 If vertex v has a child by letter x, then:
40     trie[v].nxt[x] points to that child.
41 If vertex v doesn't have such child, then:
42     trie[v].nxt[x] points to the suffix link of that child
43     if we would actually have it.
44 */
45 void add_links(){
46     queue<int> q;
47     q.push(0);
48     while (!q.empty()){
49         auto v = q.front();
50         int u = trie[v].link;
51         q.pop();
52         for (int i = 0; i < S; i++){
53             int& ch = trie[v].nxt[i];
54             if (ch == -1){
55                 ch = v? trie[u].nxt[i] : 0;
56             }
57             else{
58                 trie[ch].link = v? trie[u].nxt[i] : 0;
59                 q.push(ch);
60             }
61         }
62     }
63 }
64
65 bool is_terminal(int v){
66     return trie[v].terminal;
67 }
68
69 int get_link(int v){
70     return trie[v].link;
71 }
72
73 int go(int v, char c){
74     return trie[v].nxt[ctoi(c)];
75 }

```

## Convex Hull Trick

- Allows to insert a linear function to the hull in  $O(1)$  and get the minimum/maximum value of the stored function at a point in  $O(\log n)$ .
- NOTE: The lines must be added in the order of decreasing/increasing gradients. CAREFULLY CHECK THE SETUP BEFORE USING!
- IMPORTANT: THE DEFAULT VERSION SURELY WORKS. IF MODIFIED VERSIONS DON'T WORK, TRY TRANSFORMING THEM TO THE DEFAULT ONE BY CHANGING SIGNS.

```

1 struct line{
2     ll k, b;
3     ll f(ll x){
4         return k * x + b;
5     };

```

```

6 };
7
8 vector<line> hull;
9
10 void add_line(line nl){
11     if (!hull.empty() && hull.back().k == nl.k){
12         nl.b = min(nl.b, hull.back().b); // Default: minimum. For
        ↪ maximum change "min" to "max".
13         hull.pop_back();
14     }
15     while (sz(hull) > 1){
16         auto& l1 = hull.end()[-2], l2 = hull.back();
17         if ((nl.b - l1.b) * (l2.k - nl.k) >= (nl.b - l2.b) * (l1.k
        ↪ - nl.k)) hull.pop_back(); // Default: decreasing gradient
        ↪ k. For increasing k change the sign to <=.
18         else break;
19     }
20     hull.pb(nl);
21 }
22
23 ll get(ll x){
24     int l = 0, r = sz(hull);
25     while (r - l > 1){
26         int mid = (l + r) / 2;
27         if (hull[mid - 1].f(x) >= hull[mid].f(x)) l = mid; //
        ↪ Default: minimum. For maximum change the sign to <=.
28         else r = mid;
29     }
30     return hull[l].f(x);
31 }

```

## Li-Chao Segment Tree

- allows to add linear functions in any order and query minimum/maximum value of those at a point, all in  $O(\log n)$ .
- Clear: clear()

```

1 const ll INF = 1e18; // Change the constant!
2 struct LiChaoTree{
3     struct line{
4         ll k, b;
5         line(){
6             k = b = 0;
7         };
8         line(ll k_, ll b_){
9             k = k_, b = b_;
10        };
11        ll f(ll x){
12            return k * x + b;
13        };
14    };
15    int n;
16    bool minimum, on_points;
17    vector<ll> pts;
18    vector<line> t;
19
20    void clear(){
21        for (auto& l : t) l.k = 0, l.b = minimum? INF : -INF;
22    }
23
24    LiChaoTree(int n_, bool min_){ // This is a default
        ↪ constructor for numbers in range [0, n - 1].
25        n = n_, minimum = min_, on_points = false;
26        t.resize(4 * n);
27        clear();
28    };
29
30    LiChaoTree(vector<ll> pts_, bool min_){ // This constructor
        ↪ will build LCT on the set of points you pass. The points
        ↪ may be in any order and contain duplicates.
31        pts = pts_, minimum = min_;
32        sort(all(pts));
33        pts.erase(unique(all(pts)), pts.end());
34        on_points = true;
35        n = sz(pts);

```

```

36     t.resize(4 * n);
37     clear();
38 };
39
40 void add_line(int v, int l, int r, line nl){
41     // Adding on segment [l, r)
42     int m = (l + r) / 2;
43     ll lval = on_points? pts[l] : l, mval = on_points? pts[m]
↪ : m;
44     if ((minimum && nl.f(mval) < t[v].f(mval)) || (!minimum &&
↪ nl.f(mval) > t[v].f(mval))) swap(t[v], nl);
45     if (r - l == 1) return;
46     if ((minimum && nl.f(lval) < t[v].f(lval)) || (!minimum &&
↪ nl.f(lval) > t[v].f(lval))) add_line(2 * v + 1, l, m, nl);
47     else add_line(2 * v + 2, m, r, nl);
48 }
49
50 ll get(int v, int l, int r, int x){
51     int m = (l + r) / 2;
52     if (r - l == 1) return t[v].f(on_points? pts[x] : x);
53     else{
54         if (minimum) return min(t[v].f(on_points? pts[x] : x), x
↪ < m? get(2 * v + 1, l, m, x) : get(2 * v + 2, m, r, x));
55         else return max(t[v].f(on_points? pts[x] : x), x < m?
↪ get(2 * v + 1, l, m, x) : get(2 * v + 2, m, r, x));
56     }
57 }
58
59 void add_line(ll k, ll b){
60     add_line(0, 0, n, line(k, b));
61 }
62
63 ll get(ll x){
64     return get(0, 0, n, on_points? lower_bound(all(pts), x) -
↪ pts.begin() : x);
65 }; // Always pass the actual value of x, even if LCT is on
↪ points.
66 };

```

## Persistent Segment Tree

- for RSQ

```

1 struct Node {
2     ll val;
3     Node *l, *r;
4
5     Node(ll x) : val(x), l(nullptr), r(nullptr) {}
6     Node(Node *ll, Node *rr) {
7         l = ll, r = rr;
8         val = 0;
9         if (l) val += l->val;
10        if (r) val += r->val;
11    }
12    Node(Node *cp) : val(cp->val), l(cp->l), r(cp->r) {}
13 };
14 const int N = 2e5 + 20;
15 ll a[N];
16 Node *roots[N];
17 int n, cnt = 1;
18 Node *build(int l = 1, int r = n) {
19     if (l == r) return new Node(a[l]);
20     int mid = (l + r) / 2;
21     return new Node(build(l, mid), build(mid + 1, r));
22 }
23 Node *update(Node *node, int val, int pos, int l = 1, int r =
↪ n) {
24     if (l == r) return new Node(val);
25     int mid = (l + r) / 2;
26     if (pos > mid)
27         return new Node(node->l, update(node->r, val, pos, mid +
↪ 1, r));
28     else return new Node(update(node->l, val, pos, l, mid),
↪ node->r);
29 }
30 ll query(Node *node, int a, int b, int l = 1, int r = n) {
31     if (l > b || r < a) return 0;

```

```

32     if (l >= a && r <= b) return node->val;
33     int mid = (l + r) / 2;
34     return query(node->l, a, b, l, mid) + query(node->r, a, b,
↪ mid + 1, r);
35 }

```

## Dynamic Programming

### Sum over Subset DP

- Computes  $f[A] = \sum_{B \subseteq A} a[B]$ .
- Complexity:  $O(2^n \cdot n)$ .

```

1 for (int i = 0; i < (1 << n); i++) f[i] = a[i];
2 for (int i = 0; i < n; i++) for (int mask = 0; mask < (1 <<
↪ n); mask++) if ((mask >> i) & 1){
3     f[mask] += f[mask ^ (1 << i)];
4 }

```

### Divide and Conquer DP

- Helps to compute 2D DP of the form:
- $dp[i][j] = \min_{0 \leq k \leq j-1} (dp[i-1][k] + cost(k+1, j))$
- **Necessary condition:** let  $opt(i, j)$  be the optimal  $k$  for the state  $(i, j)$ . Then,  $opt(i, j) \leq opt(i, j+1)$ .
- **Sufficient condition:**  $cost(a, d) + cost(b, c) \geq cost(a, c) + cost(b, d)$  where  $a < b < c < d$ .
- Complexity:  $O(M \cdot N \cdot \log N)$  for computing  $dp[M][N]$ .

```

1 vector<ll> dp_old(N), dp_new(N);
2
3 void rec(int l, int r, int optl, int optr){
4     if (l > r) return;
5     int mid = (l + r) / 2;
6     pair<ll, int> best = {INF, optl};
7     for (int i = optl; i <= min(mid - 1, optr); i++){ // If k
↪ can be j, change to "i <= min(mid, optr)".
8         ll cur = dp_old[i] + cost(i + 1, mid);
9         if (cur < best.fi) best = {cur, i};
10    }
11    dp_new[mid] = best.fi;
12
13    rec(l, mid - 1, optl, best.se);
14    rec(mid + 1, r, best.se, optr);
15 }
16
17 // Computes the DP "by layers"
18 fill(all(dp_old), INF);
19 dp_old[0] = 0;
20 while (layers--){
21     rec(0, n, 0, n);
22     dp_old = dp_new;
23 }

```

### Knuth's DP Optimization

- Computes DP of the form
- $dp[i][j] = \min_{i \leq k \leq j-1} (dp[i][k] + dp[k+1][j] + cost(i, j))$
- **Necessary Condition:**  $opt(i, j-1) \leq opt(i, j) \leq opt(i+1, j)$
- **Sufficient Condition:** For  $a \leq b \leq c \leq d$ ,  $cost(b, c) \leq cost(a, d)$  AND  $cost(a, d) + cost(b, c) \geq cost(a, c) + cost(b, d)$
- Complexity:  $O(n^2)$

```

1 int N;
2 int dp[N][N], opt[N][N];
3 auto C = [&](int i, int j) {
4     // Implement cost function C.
5 };

```

```

6  for (int i = 0; i < N; i++) {
7      opt[i][i] = i;
8      // Initialize dp[i][i] according to the problem
9  }
10 for (int i = N-2; i >= 0; i--) {
11     for (int j = i+1; j < N; j++) {
12         int mn = INT_MAX;
13         int cost = C(i, j);
14         for (int k = opt[i][j-1]; k <= min(j-1, opt[i+1][j]); k++)
15             ↪ {
16                 if (mn >= dp[i][k] + dp[k+1][j] + cost) {
17                     opt[i][j] = k;
18                     mn = dp[i][k] + dp[k+1][j] + cost;
19                 }
20             }
21     }
22 }

```

## Miscellaneous

### Ordered Set

```

1  #include <ext/pb_ds/assoc_container.hpp>
2  #include <ext/pb_ds/tree_policy.hpp>
3  using namespace __gnu_pbds;
4  typedef tree<int, null_type, less<int>, rb_tree_tag,
5      ↪ tree_order_statistics_node_update> ordered_set;

```

### Measuring Execution Time

```

1  ld tic = clock();
2  // execute algo...
3  ld tac = clock();
4  // Time in milliseconds
5  cerr << (tac - tic) / CLOCKS_PER_SEC * 1000 << endl;
6  // No need to comment out the print because it's done to cerr.

```

### Setting Fixed D.P. Precision

```

1  cout << setprecision(d) << fixed;
2  // Each number is rounded to d digits after the decimal point,
3  ↪ and truncated.

```

### Common Bugs and General Advice

- Check overflow, array bounds
- Check variable overloading
- Check special cases (n=1?)
- Do something instead of nothing, stay organized
- Write stuff down!
- Don't get stuck on one approach!