

# ELITE 110|65

## True Dual Operation

Five Workstations and Two Independent Power Plants  
Super-size Punch Throat Depth of 17-3/4" Universal Open Tooling Cavity  
ANSI B11.5-1988R(02) Compliant and ETL/UL Approved Controls

## ELITE Integrated Features:

Hydraulic Hold-Down	Swing-Away Stripper Assembly
E-Stop / Lockout-Tagout	Roller Encoder Measuring System
Electric Stroke Control	Quick Change Punch Assembly
Hydraulic Accessory Pack	Premium Gauging Tables
Central Lubrication System	LED Lighting

### PUNCH

Rating: 110 Tons  
Max. Capacity: 1-3/8" Dia. in 3/4" A36  
Stroke: 3"  
Throat Depth: 17-3/4"  
Open Height: 9-3/4"  
Shut Height: 6-9/16"  
Work Height: 37-1/2"

### OPEN CAVITY

Height: 9"  
Width: 11-3/4"  
Work Height: 40-7/8"

### DIMENSIONS

Height: 65-1/8"  
Width: 91-9/16"  
Depth: 44-7/8"  
Shipping Weight: 8580 lb

### FLAT BAR SHEAR

Rating: 65 Tons  
Max. Capacity: 3/8" x 24"  
1/2" x 14"  
1" x 4"

Max. Round: 1"  
Max. Square: 1"  
Work Height: 33-1/2"

### ANGLE SHEAR

Max. Capacity: 5" x 5" x 3/8"  
Work Height: 44"

### COPER NOTCHER

Max. Capacity: 2-1/2" x 6" x 3/8"  
Work Height: 35-5/8"

### GENERAL SPECIFICATIONS

Standard Motor: 7.5 HP 3~ 208 V or 230 V  
1765 RPM 22 A

Optional Motors: 7.5 HP 3~ 460 V  
1765 RPM 11 A  
7.5 HP 3~ 575 V  
1770 RPM 8 A  
7.5 HP 1~ 230 V  
1765 RPM 36 A

Hydraulic Pump: 10-1/2 GPM - 2 Stage  
Valve Pressure: 3000 PSI  
Reservoir: 17 Gallons  
Cylinder (Punch Side): 7-1/2" Bore / 3" Ram  
Cylinder (Shear Side): 6" Bore / 3-1/2" Ram



Shown with optional Pipe Notcher

CALL (800) 373-8206

WWW.EDWARDSIRONWORKERS.COM