

ELITE 110|65

True Dual Operation

Five Workstations and Two Independent Power Plants
Super-size Punch Throat Depth of 451mm Universal Open Tooling Cavity
ANSI B11.5-1988R(02) Compliant and ETL/UL Approved Controls

ELITE Integrated Features:

| | |
|----------------------------|---------------------------------|
| Hydraulic Hold-Down | Swing-Away Stripper Assembly |
| E-Stop / Lockout-Tagout | Roller Encoder Measuring System |
| Electric Stroke Control | Quick Change Punch Assembly |
| Hydraulic Accessory Pack | Premium Gauging Tables |
| Central Lubrication System | LED Lighting |

PUNCH

Rating: 110 Tons
Max. Capacity: 35mm Dia. in 25mm A36
Stroke: 76mm
Throat Depth: 451mm
Open Height: 248mm
Shut Height: 167mm
Work Height: 953mm

OPEN CAVITY

Height: 229mm
Width: 298mm
Work Height: 1038mm

DIMENSIONS

Height: 1654mm
Width: 2326mm
Depth: 1140mm
Shipping Weight: 3891.8 kg

FLAT BAR SHEAR

Rating: 65 Tons
Max. Capacity: 10mm x 610mm
13mm x 356mm
25mm x 102mm
Max. Round: 25mm
Max. Square: 25mm
Work Height: 851mm

ANGLE SHEAR

Max. Capacity: 127mm x 127mm x 10mm
Work Height: 1118mm

COPER NOTCHER

Max. Capacity: 64mm x 152mm x 10mm
Work Height: 905mm

GENERAL SPECIFICATIONS

Standard Motor: 7.5 HP 3~ 208 V or 230 V
1765 RPM 22 A
Optional Motors: 7.5 HP 3~ 460 V
1765 RPM 11 A
7.5 HP 3~ 575 V
1770 RPM 8 A
7.5 HP 1~ 230 V
1765 RPM 36 A
Hydraulic Pump: 39.7 LPM - 2 Stage
Valve Pressure: 20684.3 kPa
Reservoir: 64.4 Liters
Cylinder (Punch Side): 191mm Bore / 76mm Ram
Cylinder (Shear Side): 152mm Bore / 89mm Ram



CALL (800) 373-8206

WWW.EDWARDSIRONWORKERS.COM