ELITE 110|65

True Dual Operation

Five Workstations and Two Independent Power Plants
Super-size Punch Throat Depth of 17-3/4”
Universal Open Tooling Cavity
ANSI B11.5-1988R(02) Compliant and ETL/UL Approved Controls

ELITE Integrated Features:

- Hydraulic Hold-Down
- E-Stop / Lockout-Tagout
- Electric Stroke Control
- Hydraulic Accessory Pack
- Central Lubrication System
- Swing-Away Stripper Assembly
- Roller Encoder Measuring System
- Quick Change Punch Assembly
- Premium Gauging Tables
- LED Lighting

PUNCH

Rating: 110 Tons
Max. Capacity: 1-3/8” Dia. in 3/4” A36
Stroke: 3”
Throat Depth: 17-3/4”
Open Height: 9-3/4”
Shut Height: 6-9/16”
Work Height: 37-1/2”

FLAT BAR SHEAR

Rating: 65 Tons
Max. Capacity: 3/8” x 24”
1/2” x 14”
1” x 4”
Max. Round: 1”
Max. Square: 1”
Work Height: 33-1/2”

ANGLE SHEAR

Max. Capacity: 5” x 5” x 1/4”
Work Height: 44”

COPER NOTCHER

Max. Capacity: 2-1/2” x 6” x 3/8”
Work Height: 35-5/8”

GENERAL SPECIFICATIONS

Standard Motor:	7.5 HP 3 Phase 208/240v 1765 RPM 21 AMP
Optional Motors:	7.5 HP 3 Phase 440/480v 1765 RPM 12 AMP
	7.5 HP 3 Phase 575v 1770 RPM 8 AMP
	7.5 HP 1 Phase 208/240v 1765 RPM 36 AMP
Hydraulic Pump:	10-1/2 GPM - 2 Stage
Valve Pressure:	3000 PSI
Reservoir:	17 Gallons
Cylinder (Punch Side):	7-1/2” Bore / 3” Ram
Cylinder (Shear Side):	6” Bore / 3-1/2” Ram

OPEN CAVITY

Width: 11-3/4”
Height: 9”
Work Height: 40-7/8”

DIMENSIONS

Height:	65-1/8”
Width:	91-9/16”
Depth:	44-7/8”
Shipping Weight:	8580 lb

Shown with optional Pipe Notcher

CALL (800) 373-8206

WWW.EDWARDSIRONWORKERS.COM