



75 TON

The Shop Standard

Four Available Workstations
Punch Assembly Designed for
Optional Tooling
Dedicated Coper Notcher Station

Electric Stroke Control
ANSI B11.5-1988R(02) Compliant
ETL/UL Approved Controls

The Edwards 75 Ton JAWS Ironworker offers you greater capacity to accomplish larger tasks. Its standard features include a Punch Assembly with Pedestal Die Table, a 356mm wide Flat Bar Shear, Angle Shear and Coper Notcher. The Punch Assembly is easily converted to an open station designed to accept optional Tooling Accessories, allowing flexibility to customize your Ironworker according to your needs.

PUNCH

Rating: 75 Tons
Max. Capacity: 27mm Dia. in 22mm A36
Stroke: 46mm
Throat Depth: 254mm
Open Height: 222mm
Shut Height: 176mm
Work Height: 992mm

ANGLE SHEAR

Max. Capacity: 127mm x 127mm x 13mm
Work Height: 1115mm

FLAT BAR SHEAR

Max. Width: 13mm x 356mm
19mm x 254mm
Max. Round: 25mm
Max. Square: 25mm
Work Height: 940mm

COPER NOTCHER

Max. Capacity: 64mm x 127mm x 13mm
Work Height: 1067mm

GENERAL SPECIFICATIONS

Standard Motor: 7.5 HP 3~ 208 V or 230 V
1765 RPM 22 A
Optional Motors: 7.5 HP 3~ 460 V
1765 RPM 11 A
7.5 HP 3~ 575 V
1770 RPM 8 A
5 HP 1~ 230 V
1725 RPM 23 A
*7.5 HP 1~ 230 V
1765 RPM 36 A

**Required for 1~ Hydraulic Accessory Pack*

Hydraulic Pump: 39.8 LPM - 2 Stage
Valve Pressure: 24131.7 kPa
Reservoir: 64.4 Liters
Cylinder: 89mm Ram

DIMENSIONS

Height: 1530mm
Width: 1270mm
Depth: 1143mm
Shipping Weight: 1859.7 kg



CALL (800) 373-8206

WWW.EDWARDSIRONWORKERS.COM