



50 TON

Compact and Versatile

Four Available Workstations
 Punch Assembly Designed for Optional Tooling
 Dedicated Coper Notcher Station
 Electric Stroke Control
 ANSI B11.5-1988R(02) Compliant
 ETL/UL Approved Controls

The Edwards 50 Ton JAWS Ironworker is the ideal Ironworker for the small shop that needs a powerful, versatile tool for all kinds of tasks. Standard features include a Punch Assembly with Pedestal Die Table, Flat Bar Shear, Angle Shear, and a dedicated Coper Notcher station. The Punch Assembly quickly converts to an open tooling station designed to accept optional Tooling Accessories.

PUNCH

Rating: 50 Tons
 Max. Capacity: 25mm Dia. in 16mm A36
 Stroke: 48mm
 Throat Depth: 178mm
 Open Height: 206mm
 Shut Height: 159mm
 Work Height: 928mm

ANGLE SHEAR

Max. Capacity: 76mm x 76mm x 10mm
 102mm x 102mm x 6mm
 Work Height: 876mm

FLAT BAR SHEAR

Max. Width: 13mm x 254mm
 19mm x 102mm
 Max. Round: 19mm
 Max. Square: 19mm
 Work Height: 876mm

COPER NOTCHER

Max. Capacity: 51mm x 76mm x 8mm
 Work Height: 1003mm

GENERAL SPECIFICATIONS

Standard Motor: 5 HP 3~ 208 V or 230 V
 1725 RPM 14 A
 Optional Motors: 5 HP 3~ 460 V
 1725 RPM 7 A
 5 HP 3~ 575 V
 1725 RPM 6 A
 5 HP 1~ 230 V
 1725 RPM 23 A
 Hydraulic Pump: 13.25 LPM - 1 Stage
 Valve Pressure: 17236.9 kPa
 Reservoir: 26.5 Liters
 Cylinder: 64mm Ram

DIMENSIONS

Height: 1384mm
 Width: 933mm
 Depth: 918mm
 Shipping Weight: 916.3 kg

CALL (800) 373-8206

WWW.EDWARDSIRONWORKERS.COM