

65 TON

Our Most Versatile Machine

Five Available Workstations
Universal Open Tooling Station
610mm Flat Bar Shear
Dedicated Coper Notcher

Electric Stroke Control
ANSI B11.5-1988R(02) Compliant
ETL/UL Approved Controls

The five workstations of the Edwards 65 Ton JAWS Ironworker give you the power to handle any size job and the flexibility to tailor it to your specific needs. Standard features include a Punch Assembly with Pedestal Die Table, 610mm wide Flat Bar Shear, Angle Shear, Coper Notcher and a universal open tooling station designed for optional Tooling Accessories.

PUNCH

Rating: 65 Tons
Max. Capacity: 27mm Dia. in 19mm A36
Stroke: 46mm
Throat Depth: 248mm
Open Height: 222mm
Shut Height: 176mm
Work Height: 928mm

ANGLE SHEAR

Max. Capacity: 127mm x 127mm x 10mm
Work Height: 1092mm

FLAT BAR SHEAR

Max. Width: 10mm x 610mm
13mm x 356mm
25mm x 102mm

Max. Round: 25mm
Max. Square: 25mm
Work Height: 864mm

COPER NOTCHER

Max. Capacity: 64mm x 127mm x 10mm
Work Height: 991mm

OPEN CAVITY

Height: 241mm
Width: 305mm
Work Height: 1092mm

GENERAL SPECIFICATIONS

Standard Motor: 7.5 HP 3~ 208 V or 230 V
1765 RPM 22 A
Optional Motors: 7.5 HP 3~ 460 V
1765 RPM 11 A
7.5 HP 3~ 575 V
1770 RPM 8 A
5 HP 1~ 230 V
1725 RPM 23 A
*7.5 HP 1~ 230 V
1765 RPM 36 A

**Required for 1~ Hydraulic Accessory Pack*

Hydraulic Pump: 39.75 LPM - 2 Stage
Valve Pressure: 24131.7 kPa
Reservoir: 64.4 Liters
Cylinder: 89mm Ram

DIMENSIONS

Height: 1448mm
Width: 1578mm
Depth: 1143mm
Shipping Weight: 2154.6 kg



CALL (800) 373-8206

WWW.EDWARDSIRONWORKERS.COM