Top Plate Analysis Report



Analyzed File:	topPlate.ipt
Autodesk Inventor Version:	2020 (Build 240168000, 168)
Creation Date:	7/29/2021, 6:51 AM
Study Author:	Bisqwit2.0
Summary:	

□ Project Info (iProperties)

■ Summary

Author joelm

□ Project

Part Number	topPlate	
Designer	joelm	
Cost	\$0.00	
Date Created	6/13/2021	

□ Status

Design Status WorkInProgress

■ Physical

Material	Stainless Steel	
Density	8 g/cm^3	
Mass	1.40291 kg	
Area	31493.5 mm^2	
Volume	175364 mm^3	
Center of Gravity	x=0 mm y=10.3391 mm z=-41 mm	

Note: Physical values could be different from Physical values used by FEA reported below.

■ Static Analysis:1

General objective and settings:

Design Objective	Single Point
Study Type	Static Analysis
Last Modification Date	7/29/2021, 6:50 AM
Detect and Eliminate Rigid Body Modes	No

Mesh settings:

Avg. Element Size (fraction of model diameter)	
Min. Element Size (fraction of avg. size)	0.2
Grading Factor	1.5
Max. Turn Angle	60 deg

Yes

■ Material(s)


Name	Stainless Steel	
	Mass Density	8 g/cm^3
General	Yield Strength	250 MPa
	Ultimate Tensile Strength	540 MPa
	Young's Modulus	193 GPa
Stress	Poisson's Ratio	0.3 ul
	Shear Modulus	74.2308 GPa
Part Name(s)	topPlate.ipt	


□ Operating conditions

□ Gravity

Load Type	Gravity	
Magnitude	9810.000 mm/s^2	
Vector X	0.000 mm/s^2	
Vector Y	-9810.000 mm/s^2	
Vector Z	0.000 mm/s^2	

□ Selected Face(s)







□ Force:1

Load Type	Force
Magnitude	100000.000 N
Vector X	0.000 N
Vector Y	-100000.000 N
Vector Z	0.000 N

□ Selected Face(s)







☐ Fixed Constraint:1

Constraint Type Fixed Constraint

□ Selected Face(s)





□ Results

☐ Reaction Force and Moment on Constraints


Constraint Name	Reaction Force		Reaction Moment	
Constraint Name	Magnitude	Component (X,Y,Z)	Magnitude	Component (X,Y,Z)
		0 N		0 N m
Fixed Constraint: 1	l 100014 N	100014 N	0 N m	0 N m
		0 N		0 N m

☐ Result Summary


Name	Minimum	Maximum
Volume	175364 mm^3	
Mass	1.40291 kg	
Von Mises Stress	2.71267 MPa	382.655 MPa
1st Principal Stress	-132.168 MPa	449.62 MPa
3rd Principal Stress	-545.386 MPa	98.7437 MPa
Displacement	0 mm	0.0347143 mm
Safety Factor	0.653331 ul	15 ul
Stress XX	-457.745 MPa	351.125 MPa
Stress XY	-147.176 MPa	148.139 MPa
Stress XZ	-131.429 MPa	122.826 MPa
Stress YY	-203.266 MPa	164.913 MPa
Stress YZ	-113.872 MPa	104.618 MPa
Stress ZZ	-312.061 MPa	232.598 MPa
X Displacement	-0.00730153 mm	0.00732624 mm
Y Displacement	-0.0347142 mm	0.000306306 mm
Z Displacement	-0.00283307 mm	0.00284397 mm
Equivalent Strain	0.0000123432 ul	0.00192176 ul
1st Principal Strain	-0.0000000670111 ul	0.00191772 ul
3rd Principal Strain	-0.00230443 ul	-0.00000669802 ul
Strain XX	-0.0017141 ul	0.00142398 ul
Strain XY	-0.000991342 ul	0.00099783 ul
Strain XZ	-0.000885275 ul	0.000827326 ul
Strain YY	-0.000457162 ul	0.000631634 ul
Strain YZ	-0.000767017 ul	0.000704683 ul
Strain ZZ	-0.0012121 ul	0.000955014 ul

□ Figures


□ Von Mises Stress



□ 1st Principal Stress





∃ 3rd Principal Stress






□ Displacement








□ Safety Factor




∃ Stress XX










∃ Stress XZ




☐ Stress YY









Stress ZZ





☐ X Displacement






☐ Y Displacement







☐ Z Displacement





□ Equivalent Strain






■ 1st Principal Strain








∃ 3rd Principal Strain




☐ Strain XX










☐ Strain XZ




☐ Strain YY







☐ Strain ZZ



D:\Carreer 4.1\Manufacturing Tech\CAMDieSets\topPlate.ipt