

White test 5- rhcsa 8

Initialization : Systems set up

System1 :

Hostname – system1.eight.example.com

IP – 192.168.55.150/24

Dns – 8.8.8.8

GW – 192.168.5.1

System2 :

Hostname – system2.eight.example.com

IP – 192.168.55.151/24

Dns – 8.8.8.8

GW – 192.168.5.1

Questions

Ensure all the tasks are implemented with firewall and selinux enabled. Your server should be able to survive a reboot.

- 1- Interrupt the boot process and reset root password. Change it to « root » to gain access to the system.
- 2- Repos are available from the repo server at the following local urls for you to use during the exam :
[/var/ftp/repo/BaseOS](#)
[/var/ftp/repo/AppStream](#)

Vim /etc/

- 3- The system time should be set to your (or nearest to you) timezone and ensure NTP sync is configured.

Timedatectl set-timezone (Command to search for time zones)

- 4- Create a container with the name, “examserver” from rhel8/rsyslog image from registry.lab.example.com registry. Configure the container with systemd services as the student user using the service name, “container-examserver” so that it can be persistent across reboot.

By default don't have a /var/log/journal file

We need to change the storage as persistent and then we do

systemctl restart systemd-journald.service

```
[client@system1 client]$ systemctl enable --now container-examserver.service
```

Failed to enable unit: Unit file container-examserver.service does not exist. ??

Configure your host journal to store all journal across reboot. Copy all journal from /var/log/journal and all subdirectories to /home/student/container-examserver. Create and mount /home/student/container-examserver as a persistent storage to the container as /var/log/journal when container start.

Use "administrator" as the username and "admin1234" as the credentials for the image registry.

- 5- Add the following secondary IP addresses statically to your current running interface. Do this in a way that doesn't compromise your existing settings :

- a. IPV4 – 10.0.0.5/24
- b. IPV6 – fd01 ::100/64

- 6- Enable packet forwarding on system1. This should persist after reboot

```
net.ipv4.ip_forward = 0 from to net.ipv4.ip_forward = 1
in /etc/sysctl.conf
```

```
to check : sysctl net.ipv4.ip_forward => returns 1
```

- 7- System1 should into the graphical target by default and boot messages (debug) should be present (not silenced).

Grub => file :

```
vim /etc/sysconfig/grub => rhgb quiet" => not persistent
```

```
vim /etc/default/grub => not persistent Too with only deleting rhgb quite
```

to make it persistent just change directory to system default settings

1) vim /etc/default/grub

```
GRUB_CMDLINE_LINUX="crashkernel=auto resume=UUID=e9234616-fb98-444e-862d-6aad77b6a7dd systemd.log_level=debug"
```

```
:wq
```

2) sudo grub2-mkconfig -o /boot/grub2/grub.cfg

- 8- Configuration de autofs : Partie serveur (server1) et client (server2) :

Configurez autofs pour monter automatiquement le home de l'utilisateur remoteuser1.

Le répertoire de base de remoteuser1 sur le serveur nfs est : /rhome.

Le répertoire de base de remoteuser1 sur le client nfs est : /clienthome.

In system2 :

Man vdo

/fstab

9- create a new 2GB volume group named « vgprac » (add a new hard disk of 2GB to your system)

10- Create a 500MB logical volume named « lvprac » inside the « vgprac » volume group.

11- The « lvprac » logical volume should be formatted with the xfs filesystem and mount persistently on the /mnt/lvprac directory

12- Extend the xfs filesystem on « lvprac » by 500MB

Lvextend -r

Lvextend -n lvprac -r -L +500M vgprac / extending with inner content

13- Use the appropriate utility to create a 5TiB thin provisioned volume (add a new hard disk of 5GB to your system).

14- In system1, configure a basic web server that displays « RHCSA Exam in december 2021 » once connected to it. Ensure the firewall allows the http/https services in the 2 systems and ensure that the message can be displayed in system2 localhost.

15- Find all files that are larger than 10MB in the /etc directory and copy them to /find/largefiles

```
Awk '{print $9 ' : ' $5}'
```

```
ls -lh /etc/ | awk '{print $9 ":" $5}' | cut -d: -f2 | grep [0-9][0-9]"K"
```

```
ls -lh /etc/ | awk '{print $9 ":" $5}' | grep [0-9][0-9]"K"
```

16- Write a script named exam.sh in the root directory on system1

- If « rhcsa8 » is given as an argument, then the script should output « yes, is valid. »
- If « rhcsa7 » is given as an argument, then the script should output « no, isn't valid »

```
#!/bin/bash
```

```
if [[ "$1" == "rhcsa8" ]]
```

```
then
```

```
    echo "Yes, is valid"
```

```
elif [[ "$1" == "rhcsa7" ]]
```

```
then
```

```
    echo "No, isn't valid"
```

```
else
```

```
    echo "usage ./exam.sh rhcsa8|rhcsa7"
```

```
fi
```

- c. If the argument is empty or anything else is given, the script should output « usage ./exam.sh rhcsa8|rhcsa7 ».

17- In your system1, Create users phil, laura, stewart and kevin

- a. All new users should have a file named « welcome » in their home folder after account creation. => skel

```
su - root -c "echo "Welcome" >/etc/skel/Welcome"
```

- b. All user passwords should expire after 120 days and be at least 6 characters in length.
- c. Phil and laura should be part of the « accounting » group. If the group doesn't already exist, create it.
- d. Stewart and kevin should be part of the « marketing » group. If the group doesn't ready exist, create it.

18- Only members of the accounting group should have access to the « /accounting » directory. Make laura the owner of this directory. Make the accounting group the group owner of the « /accounting » directory.

19- Only members of the marketing group should have access to the « /marketing » directory. Make stewart the owner of this directory. Make the marketing group the group owner of the « /marketing » directory.

20- New files should be owned by the group owner and only the file creator should have the permissions to delete their own files.

21- Create a cron job that writes « this practice exam was easy » to /var/log/messages at 7pm and 10pm only on weekdays.

```
* 19,22 * * 0-6 logger "This practice exam was easy"
```

```
Am /pm ??
```

After cracking password webmin.service failed

