

White test 1

1.set the root password to “tekup”

2.set the network configuration as follows:

*ip : 192.168.4.210

*subnet mask : 255.255.255.0

*gateway: 192.168.4.2

* dns :192.168.4.210

*hostname: exam.example.com

* (this part you had to do it with the three methods) nmcli ,nmtui
and the file of configuration

5.create groups redhat and tekup

6.create users : amal1 , amal2 and amal3 as follow:

* all users have their password set to “redhat”

*amal1 has 1300 as uid and a comment “trainer”

*amal2 has “/bin/bash” as a shell

*amal3 has a home directory “/home/test” and uid of 1301

*amal1 has tekup as his primary group , amal2 has redhat as primary group and tekup as secondary, amal3 has both groups as secondary

7. amal2 password will expire on april 5th 2020 , has a minimum password age of 5 , 7 days of warning flouen3’s password is inactive.

8.create directory “/home/tekup”. owned by root and its group is redhat.

redhat members has access permission , others have none files

created in this directory inherit the group too and cannot be deleted only by their owners or root

9. amal1 has 0 permission on tekup. tekup group has full permissions

10. copy '/etc/passwd' under '/tmp'.

amal1 has the right to read and change it amal2 has none

11. copy all files owned by "user" under "/opt/dir" (cmd , find)

12. copy "/etc/shadow" under "/home/tekup/", cp -r /etc/shadow /home/tekup create a new file called nopass containing all lines that have "!!" in them.

13. change in the file nopass , '!!' with "nopass" 19. under '/home/tekup' create a file called start containing all system targets cd

14. create a file with the kernel version called version

15. create a file with all packages that starts with s , call it sp

16. change in the previous file every "/" with ":"

17. change the umask in 024

Exercise guide ACL

1. Open a root terminal.

2. Use setfacl -m g:account:rx /data/sales to give the group account read permissions on the /data/sales directory, and use setfacl -m g:sales:rx /data/account to give the group sales read permissions on the /data/account directory.

3. Use getfacl /data/ to verify that the permissions have been set the way you intended to.

4. Use setfacl -m d:g:account:rx,g:sales:rwx /data/sales to set the default ACL for the directory sales.

5. Add the default ACL for the directory /data/account by using setfacl -m d:g:sales:rx,g:account:rwx /data/account.

6. Verify that the ACL settings are effective by adding a new file in /data/sales. Use `touch /data/sales/newfile` and use `getfacl /data/sales/newfile` to check the current permission assignments