

White test N°6 - RHCSA 8

Initialization : Systems set up

System1 :

Hostname – system1.eight.example.com

IP – 192.168.55.150/24

Dns – 192.168.5.1

GW – 192.168.5.1

System2 :

Hostname – system2.eight.example.com

IP – 192.168.55.151/24

Dns – 192.168.5.1

GW – 192.168.5.1

Questions

System1 :

- 1- The system administrator has just resigned from your organisation abruptly, as the new administrator reset the root password of the system1 server to « password123 »
- 2- create a backup file named « /root/backup.tar.bz2 ». the backup file should contain the content of « /usr/local » and should be zipped with bzip2 compression format.
- 3- Ensure selinux is in enforcing mode. If it is not, change selinux to enforcing mode.
- 4- As the student user (create a user « student »), create a detached apache http web server container with the name, (site1) and with the tag that has the lowest version1 from rhel8/httpd-24 image. Use the registry.redhat.io.registry you can use the username administrator and the password admin123.
- 5- Create and mount the ~/storage/html/ directory as a persistent storage to the container as /var/www/. The content of ~/storage/html should be extracted from /tmp/image/containers.tgz

Also, port 8080 on the container should be mapped to port 8080 on the host. Declare the environment variables, httpd_user and httpd_password and use admin as their values.

- 6- Configure the container as a service using systemd and make the web server/container persistent across reboot.
- 7- Install a FTP server, and request to anonymous download from /var/ftp/pub catalog. (it needs you to configure yum direct to the already existing file server.)
- 8- Upgrade the kernel to kernel-5.15.13-193.14.3.el8_2.x86_64, and configure the system to Start with the default kernel. Also, keep the old kernel available.
- 9- Configure a task : plan to run echo hello command at 7:13 every first day of each month.
- 10- Find the files owned by the user student, and copy it to catalog : /opt/dir
- 11- Find the rows that contain nologin from file /etc/passwd, and write it to the file /tmp/testfile.
- 12- Configure the system synchronous as 192.168.55.151 (system2).
- 13- Add user1, user2 and user3. The additional group of the two users : user2, user3 is the admin group. Password : redhat
- 14- Add admin group and set gid=6000
- 15- Create a shared directory /home/admins, make it has the following characteristics :

/home/admins belongs to group administrator
This directory can read and written by members of group adminuser. Any files created in /home/admins must has adminuser as owner group.
- 16- Copy /etc/fstab to /var/tmp/fstab. Owner of the file /var/tmp/fstab is root, belongs to group root, and this file can not be executed by any user, the user1 could read, write and modify it, while user2 without any permission.
- 17- Write a replace.sh script which receives as parameters a file name Fich1 and a directory dir. The file file1, the directory dir and the script replace.sh are in the current directory.
 - o After the execution of the script, any file in rep must have its contents replaced by that of file1.
 - o This script must also calculate the number of elements contained in rep. (x files and y directories).
- 18- Open the ip_forward, and take effect permanently.
- 19- The firewall must be open
- 20- Configure your NFS services. Share the directory by the NFS shared services.

System2 :

- 21- Create a 512M partition (/dev/sdb of 2GB), make it as ext4 file system, mounted automatically under /mnt/data1 and which take effect automatically at boot-start
- 22- Make a swap partition having 100MB (/dev/sdb of 2GB). Make automatically usable at system boot time.
- 23- Create a volume group vg (dev/sdc of 3GB), and set 16M as a extends. And divided a volume group containing 50 extends on 2 logical volumes lvo1 and lvo2, make it as ext4 file system, and mounted automatically under /mnt/lv1 and /mnt/lvo2. And the size of the floating range should set between 380M and 400M.
- 24- Adjust the size of the logical volume lvo1 , its file system size should be 890M. Make sure that the content of this system is complete.
- 25- (/dev/sdc of 10GB) : create a VDO volume with the name (class1_vdo) and a logical size of 30GB. Format the VDO volume with the xfs filesystem, mount it on /class1_mnt and make it persistent across reboot.