

# Humuhumunukunukuapua'a

## UFMG

Bruno Monteiro, Emanuel Silva e Bernardo Amorim

13 de janeiro de 2023

## Índice

<b>1</b>	<b>Primitivas</b>	<b>4</b>	2.7	Centroid decomposition . . . . .	26
1.1	Aritmetica Modular . . . . .	4	2.8	Centroid Tree . . . . .	26
1.2	Big Integer . . . . .	5	2.9	Dijkstra . . . . .	27
1.3	Matroid . . . . .	8	2.10	Dinitz . . . . .	27
1.4	Primitivas de fracao . . . . .	11	2.11	Dominator Tree - Kawakami . . . . .	28
1.5	Primitivas de matriz - exponenciacao . . . . .	11	2.12	Euler Path / Euler Cycle . . . . .	29
1.6	Primitivas Geometricas . . . . .	12	2.13	Euler Tour Tree . . . . .	30
1.7	Primitivas Geometricas 3D . . . . .	16	2.14	Floyd-Warshall . . . . .	32
1.8	Primitivas Geometricas Inteiras . . . . .	19	2.15	Functional Graph . . . . .	32
<b>2</b>	<b>Grafos</b>	<b>22</b>	2.16	Heavy-Light Decomposition - aresta . . . . .	34
2.1	AGM Direcionada . . . . .	22	2.17	Heavy-Light Decomposition - vertice . . . . .	34
2.2	Bellman-Ford . . . . .	23	2.18	Heavy-Light Decomposition sem Update . . . . .	35
2.3	Block-Cut Tree . . . . .	23	2.19	Isomorfismo de arvores . . . . .	36
2.4	Blossom - matching maximo em grafo geral . . . . .	24	2.20	Kosaraju . . . . .	36
2.5	Centro de arvore . . . . .	25	2.21	Kruskal . . . . .	37
2.6	Centroid . . . . .	25	2.22	Kuhn . . . . .	37
			2.23	LCA com binary lifting . . . . .	38
			2.24	LCA com HLD . . . . .	39

2.25	LCA com RMQ . . . . .	39	3.12	Distancia maxima entre dois pontos . . . . .	57
2.26	Line Tree . . . . .	40	3.13	Distinct Range Query . . . . .	58
2.27	Link-cut Tree . . . . .	41	3.14	Distinct Range Query com Update . . . . .	58
2.28	Link-cut Tree - aresta . . . . .	41	3.15	Dominator Points . . . . .	59
2.29	Link-cut Tree - vertice . . . . .	43	3.16	DP de Dominacao 3D . . . . .	60
2.30	Max flow com lower bound nas arestas . . . . .	44	3.17	Gray Code . . . . .	61
2.31	MinCostMaxFlow . . . . .	45	3.18	Half-plane intersection . . . . .	61
2.32	Prufer code . . . . .	46	3.19	Heap Sort . . . . .	61
2.33	Sack (DSU em arvores) . . . . .	47	3.20	Inversion Count . . . . .	61
2.34	Tarjan para SCC . . . . .	47	3.21	LIS - Longest Increasing Subsequence . . . . .	62
2.35	Topological Sort . . . . .	48	3.22	LIS2 - Longest Increasing Subsequence . . . . .	62
2.36	Vertex cover . . . . .	48	3.23	Minimum Enclosing Circle . . . . .	62
2.37	Virtual Tree . . . . .	49	3.24	Minkowski Sum . . . . .	63
<b>3</b>	<b>Problemas</b>	<b>49</b>	3.25	MO - DSU . . . . .	64
3.1	Algoritmo Hungaro . . . . .	49	3.26	Mo - numero de distintos em range . . . . .	64
3.2	Algoritmo MO - queries em caminhos de arvore . . . . .	50	3.27	Palindromic Factorization . . . . .	65
3.3	Angle Range Intersection . . . . .	51	3.28	Parsing de Expressao . . . . .	66
3.4	Area da Uniao de Retangulos . . . . .	51	3.29	RMQ com Divide and Conquer . . . . .	67
3.5	Area Maxima de Histograma . . . . .	52	3.30	Segment Intersection . . . . .	67
3.6	Binomial modular . . . . .	53	3.31	Sequencia de de Bruijn . . . . .	68
3.7	Closest pair of points . . . . .	54	3.32	Shortest Addition Chain . . . . .	68
3.8	Coloracao de Grafo de Intervalo . . . . .	54	3.33	Simple Polygon . . . . .	68
3.9	Conectividade Dinamica . . . . .	54	3.34	Sweep Direction . . . . .	69
3.10	Conectividade Dinamica 2 . . . . .	55	3.35	Triangulacao de Delaunay . . . . .	69
3.11	Conj. Indep. Maximo com Peso em Grafo de Intervalo . . . . .	57	3.36	Triangulos em Grafos . . . . .	71

<b>4</b>	<b>Strings</b>	<b>72</b>	5.11 Range color . . . . .	89
4.1	Aho-corasick . . . . .	72	5.12 RMQ $<O(n), O(1)>$ - min queue . . . . .	90
4.2	Algoritmo Z . . . . .	72	5.13 SegTreap . . . . .	90
4.3	Automato de Sufixo . . . . .	72	5.14 SegTree . . . . .	91
4.4	eertree . . . . .	73	5.15 SegTree 2D Iterativa . . . . .	93
4.5	KMP . . . . .	74	5.16 SegTree Beats . . . . .	93
4.6	Manacher . . . . .	74	5.17 SegTree Colorida . . . . .	95
4.7	Min/max suffix/cyclic shift . . . . .	75	5.18 SegTree Esparsa - Lazy . . . . .	96
4.8	String Hashing . . . . .	75	5.19 SegTree Esparsa - $O(q)$ memoria . . . . .	97
4.9	String Hashing - modulo $2^{61} - 1$ . . . . .	76	5.20 SegTree Iterativa . . . . .	98
4.10	Suffix Array - $O(n \log n)$ . . . . .	76	5.21 SegTree Iterativa com Lazy Propagation . . . . .	98
4.11	Suffix Array - $O(n)$ . . . . .	77	5.22 SegTree PA . . . . .	99
4.12	Suffix Array Dinamico . . . . .	79	5.23 SegTree Persistente . . . . .	100
4.13	Trie . . . . .	81	5.24 Sparse Table . . . . .	101
<b>5</b>	<b>Estruturas</b>	<b>82</b>	5.25 Sparse Table Disjunta . . . . .	101
5.1	BIT . . . . .	82	5.26 Splay Tree . . . . .	102
5.2	BIT 2D . . . . .	83	5.27 Splay Tree Implicita . . . . .	103
5.3	BIT com update em range . . . . .	83	5.28 Split-Merge Set . . . . .	105
5.4	DSU . . . . .	84	5.29 SQRT Tree . . . . .	107
5.5	Li-Chao Tree . . . . .	85	5.30 Treap . . . . .	108
5.6	MergeSort Tree . . . . .	86	5.31 Treap Implicita . . . . .	109
5.7	Min queue - deque . . . . .	87	5.32 Treap Persistent Implicita . . . . .	110
5.8	Min queue - stack . . . . .	87	5.33 Wavelet Tree . . . . .	111
5.9	Order Statistic Set . . . . .	88	<b>6</b>	<b>Matematica</b>
5.10	Priority Queue DS . . . . .	88	6.1	2-SAT . . . . .
				111

6.2	Algoritmo de Euclides estendido	112
6.3	Avaliacao de Interpolacao	112
6.4	Berlekamp-Massey	113
6.5	Binomial Distribution	114
6.6	Convolucao de GCD / LCM	114
6.7	Coprime Basis	114
6.8	Crivo de Eratosthenes	115
6.9	Deteccao de ciclo - Tortoise and Hare	117
6.10	Division Trick	117
6.11	Eliminacao Gaussiana	117
6.12	Eliminacao Gaussiana Z2	118
6.13	Equacao Diofantina Linear	118
6.14	Exponenciacao rapida	119
6.15	Fast Walsh Hadamard Transform	119
6.16	FFT	119
6.17	Integracao Numerica - Metodo de Simpson 3/8	121
6.18	Inverso Modular	121
6.19	Karatsuba	121
6.20	Logaritmo Discreto	122
6.21	Miller-Rabin	122
6.22	Pollard's Rho Alg	123
6.23	Produto de dois long long mod m	124
6.24	Simplex	124
6.25	Teorema Chines do Resto	124
6.26	Totiente	125

<b>7</b>	<b>DP</b>	<b>125</b>
7.1	Convex Hull Trick (Rafael)	125
7.2	Convex Hull Trick Dinamico	125
7.3	Divide and Conquer DP	126
7.4	Longest Common Subsequence	126
7.5	Mochila	127
7.6	SOS DP	128
<b>8</b>	<b>Extra</b>	<b>129</b>
8.1	rand.cpp	129
8.2	template.cpp	129
8.3	hash.sh	129
8.4	stress.sh	129
8.5	fastIO.cpp	129
8.6	debug.cpp	129
8.7	vimrc	130
8.8	timer.cpp	130
8.9	linehash.sh	130
8.10	makefile	130

## 1 Primitivas

### 1.1 Aritmetica Modular

```
// 0 mod tem q ser primo
// 5a6efb

429 template<int p> struct mod_int {
02c     ll pow(ll b, ll e) {
```

```

a63         if (e == 0) return 1;
630         ll r = pow(b*b%p, e/2);
475         if (e%2 == 1) r = (r*b)%p;
4c1         return r;
cbb     }
ae3     ll inv(ll b) { return pow(b, p-2); }

4d7     using m = mod_int;
d93     int v;
fe0     mod_int() : v(0) {}
e12     mod_int(ll v_) {
019         if (v_ >= p or v_ <= -p) v_ %= p;
bc6         if (v_ < 0) v_ += p;
2e7         v = v_;
cbb     }
74d     m& operator+=(const m &a) {
2fd         v += a.v;
ba5         if (v >= p) v -= p;
357         return *this;
cbb     }
eff     m& operator-=(const m &a) {
8b4         v -= a.v;
cc8         if (v < 0) v += p;
357         return *this;
cbb     }
4c4     m& operator*=(const m &a) {
8a5         v = v * ll(a.v) % p;
357         return *this;
cbb     }
3f9     m& operator/=(const m &a) {
5d6         v = v * inv(a.v) % p;
357         return *this;
cbb     }
d65     m operator-(){ return m(-v); }
b3e     m& operator^=(ll e) {
06d         if (e < 0){
6e2             v = inv(v);
00c             e = -e;
cbb         }
ebf         v = pow(v, e%(p-1));
357         return *this;
cbb     }
423     bool operator==(const m &a) { return v == a.v; }
69f     bool operator!=(const m &a) { return v != a.v; }

1c6     friend istream &operator>>(istream &in, m& a) {

```

```

d1c         ll val; in >> val;
d48         a = m(val);
091         return in;
cbb     }
44f     friend ostream &operator<<(ostream &out, m a) {
5a0         return out << a.v;
cbb     }
399     friend m operator+(m a, m b) { return a+=b; }
f9e     friend m operator-(m a, m b) { return a-=b; }
9c1     friend m operator*(m a, m b) { return a*=b; }
51b     friend m operator/(m a, m b) { return a/=b; }
08f     friend m operator^(m a, ll e) { return a^=e; }
214 };

```

```

055     typedef mod_int<(int)1e9+7> mint;

```

## 1.2 Big Integer

```

// Complexidades: (para n digitos)
// Soma, subtracao, comparacao - O(n)
// Multiplicacao - O(n log(n))
// Divisao, resto - O(n^2)
// 6c3c3a

```

```

864     struct bint {
669         static const int BASE = 1e9;
990         vector<int> v;
3bd         bool neg;

609         bint() : neg(0) {}
d53         bint(int val) : bint() { *this = val; }
e8f         bint(long long val) : bint() { *this = val; }

a0f         void trim() {
f42             while (v.size() and v.back() == 0) v.pop_back();
df8             if (!v.size()) neg = 0;
cbb         }

        // converter de/para string | cin/cout
294         bint(const char* s) : bint() { from_string(string(s)); }
548         bint(const string& s) : bint() { from_string(s); }
4ab         void from_string(const string& s) {
0a6             v.clear(), neg = 0;
d72             int ini = 0;

```

```

8e2         while (ini < s.size() and (s[ini] == '-' or s[ini] ==
'+', or s[ini] == '0'))
71d             if (s[ini++] == '-') neg = 1;
883         for (int i = s.size()-1; i >= ini; i -= 9) {
05e             int at = 0;
5b1             for (int j = max(ini, i - 8); j <= i; j++) at =
10*at + (s[j] - '0');
1fd             v.push_back(at);
cbb         }
df8         if (!v.size()) neg = 0;
cbb     }
2ff     string to_string() const {
8be         if (!v.size()) return "0";
793         string ret;
73e         if (neg) ret += '-';
3e9         for (int i = v.size()-1; i >= 0; i--) {
582             string at = ::to_string(v[i]);
ced             int add = 9 - at.size();
75e             if (i+1 < v.size()) for (int j = 0; j < add; j++)
ret += '0';
f9f             ret += at;
cbb         }
edf         return ret;
cbb     }
d2f     friend istream& operator>>(istream& in, bint& val) {
eb6         string s; in >> s;
966         val = s;
091         return in;
cbb     }
99d     friend ostream& operator<<(ostream& out, const bint& val) {
8b9         string s = val.to_string();
396         out << s;
fe8         return out;
cbb     }

// operators
60a     friend bint abs(bint val) {
c5f         val.neg = 0;
d94         return val;
cbb     }
bee     friend bint operator-(bint val) {
815         if (val != 0) val.neg ^= 1;
d94         return val;
cbb     }
41f     bint& operator=(const bint& val) { v = val.v, neg =
val.neg; return *this; }

```

```

249     bint& operator=(long long val) {
0a6         v.clear(), neg = 0;
3a6         if (val < 0) neg = 1, val *= -1;
fdc         for (; val; val /= BASE) v.push_back(val % BASE);
357         return *this;
cbb     }
3bd     int cmp(const bint& r) const { // menor: -1 | igual: 0 |
maior: 1
b14         if (neg != r.neg) return neg ? -1 : 1;
0bb         if (v.size() != r.v.size()) {
ff7             int ret = v.size() < r.v.size() ? -1 : 1;
91b             return neg ? -ret : ret;
cbb         }
478         for (int i = int(v.size())-1; i >= 0; i--) {
405             if (v[i] != r.v[i]) {
2e5                 int ret = v[i] < r.v[i] ? -1 : 1;
91b                 return neg ? -ret : ret;
cbb             }
cbb         }
bb3         return 0;
cbb     }
152     friend bool operator<(const bint& l, const bint& r) {
return l.cmp(r) == -1; }
c7a     friend bool operator>(const bint& l, const bint& r) {
return l.cmp(r) == 1; }
edd     friend bool operator<=(const bint& l, const bint& r) {
return l.cmp(r) <= 0; }
954     friend bool operator>=(const bint& l, const bint& r) {
return l.cmp(r) >= 0; }
a67     friend bool operator==(const bint& l, const bint& r) {
return l.cmp(r) == 0; }
10b     friend bool operator!=(const bint& l, const bint& r) {
return l.cmp(r) != 0; }

38e     bint& operator+=(const bint& r) {
6bf         if (!r.v.size()) return *this;
a93         if (neg != r.neg) return *this -= -r;
256         for (int i = 0, c = 0; i < r.v.size() or c; i++) {
e28             if (i == v.size()) v.push_back(0);
08f             v[i] += c + (i < r.v.size() ? r.v[i] : 0);
baa             if ((c = v[i] >= BASE)) v[i] -= BASE;
cbb         }
357         return *this;
cbb     }
54c     friend bint operator+(bint a, const bint& b) { return a +=
b; }

```

```

9c8 bint& operator -=(const bint& r) {
6bf     if (!r.v.size()) return *this;
524     if (neg != r.neg) return *this += -r;
358     if ((!neg and *this < r) or (neg and r < *this)) {
b10         *this = r - *this;
a10         neg ^= 1;
357     return *this;
cbb }
256     for (int i = 0, c = 0; i < r.v.size() or c; i++) {
9ef         v[i] -= c + (i < r.v.size() ? r.v[i] : 0);
c8c         if ((c = v[i] < 0)) v[i] += BASE;
cbb     }
0eb     trim();
357     return *this;
cbb }
f44 friend bint operator-(bint a, const bint& b) { return a -=
b; }

// operators de * / %
6b0 bint& operator *=(int val) {
bca     if (val < 0) val *= -1, neg ^= 1;
566     for (int i = 0, c = 0; i < v.size() or c; i++) {
e28         if (i == v.size()) v.push_back(0);
352         long long at = (long long) v[i] * val + c;
6a3         v[i] = at % BASE;
b3d         c = at / BASE;
cbb     }
0eb     trim();
357     return *this;
cbb }
480 friend bint operator *(bint a, int b) { return a *= b; }
d5c friend bint operator *(int a, bint b) { return b *= a; }
13b using cplx = complex<double>;
bfb void fft(vector<cplx>& a, bool f, int N, vector<int>& rev)
const {
bc7     for (int i = 0; i < N; i++) if (i < rev[i]) swap(a[i],
a[rev[i]]);
bad     vector<cplx> roots(N);
192     for (int n = 2; n <= N; n *= 2) {
4e9         const static double PI = acos(-1);
71a         for (int i = 0; i < n/2; i++) {
40d             double alpha = (2*PI*i)/n;
1a1             if (f) alpha = -alpha;
3f6             roots[i] = cplx(cos(alpha), sin(alpha));
cbb         }
3e9         for (int pos = 0; pos < N; pos += n)

```

```

898         for (int l = pos, r = pos+n/2, m = 0; m < n/2;
l++, r++, m++) {
297             auto t = roots[m]*a[r];
254             a[r] = a[l] - t;
b8f             a[l] = a[l] + t;
cbb         }
cbb     }
3f1     if (!f) return;
08b     auto invN = cplx(1)/cplx(N);
873     for (int i = 0; i < N; i++) a[i] *= invN;
cbb }
0e0 vector<long long> convolution(const vector<int>& a, const
vector<int>& b) const {
ff9     vector<cplx> l(a.begin(), a.end()), r(b.begin(),
b.end());
996     int ln = l.size(), rn = r.size(), N = ln+rn+1, n = 1,
log_n = 0;
821     while (n <= N) n <= 1, log_n++;
808     vector<int> rev(n);
603     for (int i = 0; i < n; i++) {
434         rev[i] = 0;
f44         for (int j = 0; j < log_n; j++) if (i>>j&1)
4ff             rev[i] |= 1 << (log_n-1-j);
cbb     }
230     l.resize(n), r.resize(n);
a89     fft(l, false, n, rev), fft(r, false, n, rev);
917     for (int i = 0; i < n; i++) l[i] *= r[i];
88b     fft(l, true, n, rev);
7ae     vector<long long> ret;
c14     for (auto& i : l) ret.push_back(round(i.real()));
edf     return ret;
cbb }
633 vector<int> convert_base(const vector<int>& a, int from,
int to) const {
498     static vector<long long> pot(10, 1);
671     if (pot[1] == 1) for (int i = 1; i < 10; i++) pot[i] =
10*pot[i-1];
4b8     vector<int> ret;
156     long long at = 0;
608     int digits = 0;
941     for (int i : a) {
412         at += i * pot[digits];
035         digits += from;
684         while (digits >= to) {
0c8             ret.push_back(at % pot[to]);
cf9             at /= pot[to];

```

```

fd4         digits -= to;
cbb         }
cbb         }
944         ret.push_back(at);
384         while (ret.size() and ret.back() == 0) ret.pop_back();
edf         return ret;
cbb     }
edb     bint operator*(const bint& r) const { // O(n log(n))
2af         bint ret;
968         ret.neg = neg ^ r.neg;
d5d         auto conv = convolution(convert_base(v, 9, 4),
convert_base(r.v, 9, 4));
a0e         long long c = 0;
a74         for (auto i : conv) {
f6d             long long at = i+c;
4cb             ret.v.push_back(at % 10000);
a25             c = at / 10000;
cbb         }
3cb         for (; c; c /= 10000) ret.v.push_back(c%10000);
0e2         ret.v = convert_base(ret.v, 4, 9);
25c         if (!ret.v.size()) ret.neg = 0;
edf         return ret;
cbb     }
359     bint& operator*=(const bint& r) { return *this = *this * r;
};

9a3     bint& operator/=(int val) {
d9a         if (val < 0) neg ^= 1, val *= -1;
f18         for (int i = int(v.size())-1, c = 0; i >= 0; i--) {
2a7             long long at = v[i] + c * (long long) BASE;
e02             v[i] = at / val;
fb1             c = at % val;
cbb         }
0eb         trim();
357         return *this;
cbb     }
e74     friend bint operator/(bint a, int b) { return a /= b; }
4a9     int operator %=(int val) {
23b         if (val < 0) val *= -1;
156         long long at = 0;
f31         for (int i = int(v.size())-1; i >= 0; i--)
1b3             at = (BASE * at + v[i]) % val;
d22         if (neg) at *= -1;
ce6         return at;
cbb     }
2fb     friend int operator%(bint a, int b) { return a %= b; }
13b     friend pair<bint, bint> divmod(const bint& a_, const bint&

```

```

b_) { // O(n^2)
611         if (a_ == 0) return {0, 0};
d8a         int norm = BASE / (b_.v.back() + 1);
b4e         bint a = abs(a_) * norm;
027         bint b = abs(b_) * norm;
14d         bint q, r;
c91         for (int i = a.v.size() - 1; i >= 0; i--) {
b71             r *= BASE, r += a.v[i];
4ff             long long upper = b.v.size() < r.v.size() ?
r.v[b.v.size()] : 0;
86d             int lower = b.v.size() - 1 < r.v.size() ?
r.v[b.v.size() - 1] : 0;
431             int d = (upper * BASE + lower) / b.v.back();
5d4             r -= b*d;
30f             while (r < 0) r += b, d--; // roda O(1) vezes
738             q.v.push_back(d);
cbb         }
a48         reverse(q.v.begin(), q.v.end());
ae2         q.neg = a_.neg ^ b_.neg;
88b         r.neg = a_.neg;
8e5         q.trim(), r.trim();
0ef         return {q, r / norm};
cbb     }
1d8     bint operator/(const bint& val) { return divmod(*this,
val).first; }
7f9     bint& operator/=(const bint& val) { return *this = *this /
val; }
1f9     bint operator%(const bint& val) { return divmod(*this,
val).second; }
df5     bint& operator%=(const bint& val) { return *this = *this %
val; }
214 };

```

### 1.3 Matroid

```

// Matroids de Grafo e Particao
// De modo geral, toda Matroid contem um build() linear
// e uma funcao constante oracle()
// oracle(i) responde se o conjunto continua independente
// apos adicao do elemento i
// oracle(i, j) responde se o conjunto continua indepenete
// apos trocar o elemento i pelo elemento j
//
// Intersecao sem peso O(r^2 n)

```



```

// em que n eh o tamanho do conjunto e r eh o tamanho da resposta

// Matroid Grafica
// Matroid das florestas de um grafo
// Um conjunto de arestas eh independente se formam uma floresta
//
// build() : O(n)
// oracle() : O(1)
// 691847

fda struct graphic_matroid {
5da     int n, m, t;
32c     vector<array<int, 2>> edges;
789     vector<vector<int>> g;
62e     vector<int> comp, in, out;
513     graphic_matroid(int n_, vector<array<int, 2>> edges_)
a1f         : n(n_), m(edges_.size()), edges(edges_), g(n),
comp(n), in(n), out(n) {}
315     void dfs(int u) {
ab8         in[u] = t++;
17d         for (auto v : g[u]) if (in[v] == -1)
863             comp[v] = comp[u], dfs(v);
677         out[u] = t;
cbb     }
945     void build(vector<int> I) {
a34         t = 0;
741         for (int u = 0; u < n; u++) g[u].clear(), in[u] = -1;
667         for (int e : I) {
d00             auto [u, v] = edges[e];
125             g[u].push_back(v), g[v].push_back(u);
cbb         }
809         for (int u = 0; u < n; u++) if (in[u] == -1)
a7d             comp[u] = u, dfs(u);
cbb     }
f31     bool is_ancestor(int u, int v) {
a68         return in[u] <= in[v] and in[v] < out[u];
cbb     }
e6b     bool oracle(int e) {
453         return comp[edges[e][0]] != comp[edges[e][1]];
cbb     }
f75     bool oracle(int e, int f) {
574         if (oracle(f)) return true;
622         int u = edges[e][in[edges[e][0]] < in[edges[e][1]]];
ff2         return is_ancestor(u, edges[f][0]) != is_ancestor(u,
edges[f][1]);
cbb     }

```

```

214 };

// Matroid de particao ou cores
// Um conjunto eh independente se a quantidade de elementos
// de cada cor nao excede a capacidade da cor
// Quando todas as capacidades sao 1, um conjunto eh
// independente
// se todas as suas cores sao distintas
//
// build() : O(n)
// oracle() : O(1)
// caa72a

994 struct partition_matroid {
501     vector<int> cap, color, d;
608     partition_matroid(vector<int> cap_, vector<int> color_)
04d         : cap(cap_), color(color_), d(cap.size()) {}
945     void build(vector<int> I) {
def         fill(d.begin(), d.end(), 0);
e9d         for (int u : I) d[color[u]]++;
cbb     }
514     bool oracle(int u) {
0a1         return d[color[u]] < cap[color[u]];
cbb     }
f7f     bool oracle(int u, int v) {
2f7         return color[u] == color[v] or oracle(v);
cbb     }
214 };

// Intersecao de matroid sem pesos
// Dadas duas matroids M1 e M2 definidas sobre o mesmo
// conjunto I, retorna o maior subconjunto de I
// que eh independente tanto para M1 quanto para M2
//
// O(r^2*n)
// 899f94

// Matroid "pesada" deve ser a M2
132 template<typename Matroid1, typename Matroid2>
801 vector<int> matroid_intersection(int n, Matroid1 M1, Matroid2
M2) {
f5b     vector<bool> b(n);
a64     vector<int> I[2];
a8b     bool converged = false;
0c1     while (!converged) {
742         I[0].clear(), I[1].clear();

```

```

99d         for (int u = 0; u < n; u++) I[b[u]].push_back(u);

09d     M1.build(I[1]), M2.build(I[1]);
289     vector<bool> target(n), pushed(n);
26a     queue<int> q;
5c5     for (int u : I[0]) {
2b2         target[u] = M2.oracle(u);
c1b         if (M1.oracle(u)) pushed[u] = true, q.push(u);
cbb     }
3fe     vector<int> p(n, -1);
07a     converged = true;
402     while (q.size()) {
be1         int u = q.front(); q.pop();
5c6         if (target[u]) {
101             converged = false;
c32             for (int v = u; v != -1; v = p[v]) b[v] = !b[v];
c2b             break;
cbb         }
e78         for (int v : I[!b[u]]) if (!pushed[v]) {
34d             if ((b[u] and M1.oracle(u, v)) or (b[v] and
M2.oracle(v, u)))
bae                 p[v] = u, pushed[v] = true, q.push(v);
cbb         }
cbb     }
cbb     }
b68     return I[1];
cbb }

// Intersecao de matroid com pesos
// Dadas duas matroids M1 e M2 e uma funcao de pesos w, todas
// definidas sobre
// um conjunto I retorna o maior subconjunto de I (desempatado
// pelo menor peso)
// que eh independente tanto para M1 quanto para M2
// A resposta eh construida incrementando o tamanho conjunto I
// de 1 em 1
// Se nao tiver custo negativo, nao precisa de SPFA
//
// O(r^3*n) com SPFA
// O(r^2*n*log(n)) com Dijkstra e potencial
// 3a09d1

42a template<typename T, typename Matroid1, typename Matroid2>
2b5 vector<int> weighted_matroid_intersection(int n, vector<T> w,
Matroid1 M1, Matroid2 M2) {
6c9     vector<bool> b(n), target(n), is_inside(n);

```

```

563     vector<int> I[2], from(n);
e35     vector<pair<T, int>> d(n);
169     auto check_edge = [&](int u, int v) {
249         return (b[u] and M1.oracle(u, v)) or (b[v] and
M2.oracle(v, u));
214     };
667     while (true) {
742         I[0].clear(), I[1].clear();
99d         for (int u = 0; u < n; u++) I[b[u]].push_back(u);
// I[1] contem o conjunto de tamanho I[1].size() de
menor peso
09d         M1.build(I[1]), M2.build(I[1]);
687         for (int u = 0; u < n; u++) {
ea5             target[u] = false, is_inside[u] = false, from[u] =
-1;
961             d[u] = {numeric_limits<T>::max(), INF};
cbb         }
8d3         deque<T> q;
476         sort(I[0].begin(), I[0].end(), [&](int i, int j){
return w[i] < w[j]; });
5c5         for (int u : I[0]) {
2b2             target[u] = M2.oracle(u);
5a7             if (M1.oracle(u)) {
4ef                 if (is_inside[u]) continue;
7cc                 d[u] = {w[u], 0};
427                 if (!q.empty() and d[u] > d[q.front()])
q.push_back(u);
655                 else q.push_front(u);
4ae                 is_inside[u] = true;
cbb             }
cbb         }
402         while (q.size()) {
97a             int u = q.front(); q.pop_front();
6f3             is_inside[u] = false;
57a             for (int v : I[!b[u]]) if (check_edge(u, v)) {
9de                 pair<T, int> nd(d[u].first + w[v], d[u].second
+ 1);
61b                 if (nd < d[v]) {
6ac                     from[v] = u, d[v] = nd;
bd7                     if (is_inside[v]) continue;
eec                     if (q.size() and d[v] > d[q.front()])
q.push_back(v);
275                     else q.push_front(v);
587                     is_inside[v] = true;
cbb                 }
cbb             }

```

```

cbb      }
cc8      pair<T, int> mini = pair(numeric_limits<T>::max(), INF);
489      int targ = -1;
259      for (int u : I[0]) if (target[u] and d[u] < mini)
2b9          mini = d[u], targ = u;
e14      if (targ != -1) for (int u = targ; u != -1; u = from[u])
d89          b[u] = !b[u], w[u] *= -1;
f97      else break;
cbb      }
b68      return I[1];
cbb }

```

## 1.4 Primitivas de fracao

```

// Funciona com o Big Int
// cdb445

```

```

a4e template<typename T = int> struct frac {
a40     T num, den;
e3f     template<class U, class V>
61d     frac(U num_ = 0, V den_ = 1) : num(num_), den(den_) {
bad         assert(den != 0);
583         if (den < 0) num *= -1, den *= -1;
a51         T g = gcd(abs(num), den);
572         num /= g, den /= g;
cbb     }

51f     friend bool operator<(const frac& l, const frac& r) {
fa0         return l.num * r.den < r.num * l.den;
cbb     }
4b5     friend frac operator+(const frac& l, const frac& r) {
b61         return {l.num*r.den + l.den*r.num, l.den*r.den};
cbb     }
74d     friend frac operator-(const frac& l, const frac& r) {
2cd         return {l.num*r.den - l.den*r.num, l.den*r.den};
cbb     }
c80     friend frac operator*(const frac& l, const frac& r) {
510         return {l.num*r.num, l.den*r.den};
cbb     }
a1b     friend frac operator/(const frac& l, const frac& r) {
8f3         return {l.num*r.den, l.den*r.num};
cbb     }
012     friend ostream& operator<<(ostream& out, frac f) {
37a         out << f.num << '/' << f.den;

```

```

fe8         return out;
cbb     }
214 };

```

## 1.5 Primitivas de matriz - exponenciacao

```

// d05c24

```

```

945 #define MODULAR false
5ed template<typename T> struct matrix : vector<vector<T>> {
14e     int n, m;

30f     void print() {
603         for (int i = 0; i < n; i++) {
70f             for (int j = 0; j < m; j++) cout << (*this)[i][j]
<< " ";
1fb             cout << endl;
cbb         }
cbb     }

aa3     matrix(int n_, int m_, bool ident = false) :
b14         vector<vector<T>>(n_, vector<T>(m_, 0)), n(n_),
m(m_) {
94e         if (ident) {
df7             assert(n == m);
a89             for (int i = 0; i < n; i++) (*this)[i][i] = 1;
cbb         }
cbb     }
b83     matrix(const vector<vector<T>>& c) : vector<vector<T>>(c),
a3d         n(c.size()), m(c[0].size()) {}
efc     matrix(const initializer_list<initializer_list<T>>& c) {
f7e         vector<vector<T>> val;
212         for (auto& i : c) val.push_back(i);
303         *this = matrix(val);
cbb     }

388     matrix<T> operator*(matrix<T>& r) {
1e2         assert(m == r.n);
82c         matrix<T> M(n, r.m);
d69         for (int i = 0; i < n; i++) for (int k = 0; k < m; k++)
df4             for (int j = 0; j < r.m; j++) {
e34                 T add = (*this)[i][k] * r[k][j];
f98             #if MODULAR

```

```

d41 #warning Usar matrix<ll> e soh colocar valores em [0, MOD) na
    matriz!
8b6         M[i][j] += add%MOD;
983         if (M[i][j] >= MOD) M[i][j] -= MOD;
8c1 #else
7bb         M[i][j] += add;
f2e #endif
cbb     }
474     return M;
cbb }
528     matrix<T> operator^(ll e){
f10         matrix<T> M(n, n, true), at = *this;
c87         while (e) {
2e2             if (e&1) M = M*at;
cc2             e >>= 1;
c80             at = at*at;
cbb         }
474     return M;
cbb }
582     void apply_transform(matrix M, ll e){
1c3         auto& v = *this;
c87         while (e) {
9ba             if (e&1) v = M*v;
cc2             e >>= 1;
419             M = M*M;
cbb         }
cbb     }
214 };

```

## 1.6 Primitivas Geometricas

```

c83 typedef double ld;
e3b const ld DINF = 1e18;
43a const ld pi = acos(-1.0);
107 const ld eps = 1e-9;

b32 #define sq(x) ((x)*(x))

d97 bool eq(ld a, ld b) {
ba0     return abs(a - b) <= eps;
cbb }

// a8b7d6
b2a struct pt { // ponto

```

```

c1e     ld x, y;
3dd     pt(ld x_ = 0, ld y_ = 0) : x(x_), y(y_) {}
5bc     bool operator < (const pt p) const {
059         if (!eq(x, p.x)) return x < p.x;
f98         if (!eq(y, p.y)) return y < p.y;
bb3         return 0;
cbb     }
a83     bool operator == (const pt p) const {
ed0         return eq(x, p.x) and eq(y, p.y);
cbb     }
cb9     pt operator + (const pt p) const { return pt(x+p.x, y+p.y);
    }
a24     pt operator - (const pt p) const { return pt(x-p.x, y-p.y);
    }
4a8     pt operator * (const ld c) const { return pt(x*c, y*c);
    }
a60     pt operator / (const ld c) const { return pt(x/c, y/c);
    }

3b6     ld operator * (const pt p) const { return x*p.x + y*p.y; }
6df     ld operator ^ (const pt p) const { return x*p.y - y*p.x; }
5ed     friend istream& operator >> (istream& in, pt& p) {
e37         return in >> p.x >> p.y;
cbb     }
214 };

// 7ab617
b3a struct line { // reta
730     pt p, q;
0d6     line() {}
4b8     line(pt p_, pt q_) : p(p_), q(q_) {}
8d7     friend istream& operator >> (istream& in, line& r) {
4cb         return in >> r.p >> r.q;
cbb     }
214 };

// PONTO & VETOR

// c684fb
364 ld dist(pt p, pt q) { // distancia
5f3     return hypot(p.y - q.y, p.x - q.x);
cbb }

// 80f2b6
9d7 ld dist2(pt p, pt q) { // quadrado da distancia
f24     return sq(p.x - q.x) + sq(p.y - q.y);
cbb }

```

```

// cf7f33
483 ld norm(pt v) { // norma do vetor
490     return dist(pt(0, 0), v);
cbb }

// 404df7
589 ld angle(pt v) { // angulo do vetor com o eixo x
587     ld ang = atan2(v.y, v.x);
6f8     if (ang < 0) ang += 2*pi;
19c     return ang;
cbb }

// 1b1d4a
298 ld sarea(pt p, pt q, pt r) { // area com sinal
606     return ((q-p)^(r-q))/2;
cbb }

// 98c42f
e32 bool col(pt p, pt q, pt r) { // se p, q e r sao colin.
e7d     return eq(sarea(p, q, r), 0);
cbb }

// 85d09d
0cd bool ccw(pt p, pt q, pt r) { // se p, q, r sao ccw
fa7     return sarea(p, q, r) > eps;
cbb }

// 41a7b4
1ef pt rotate(pt p, ld th) { // rotaciona o ponto th radianos
e5c     return pt(p.x * cos(th) - p.y * sin(th),
ff1         p.x * sin(th) + p.y * cos(th));
cbb }

// e4ad5e
ab1 pt rotate90(pt p) { // rotaciona 90 graus
a0d     return pt(-p.y, p.x);
cbb }

// RETA

// 0fb984
edc bool isvert(line r) { // se r eh vertical
87d     return eq(r.p.x, r.q.x);
cbb }

```

```

// 726d68
099 bool isinseg(pt p, line r) { // se p pertence ao seg de r
f65     pt a = r.p - p, b = r.q - p;
b04     return eq((a ^ b), 0) and (a * b) < eps;
cbb }

// a0a30b
98d ld get_t(pt v, line r) { // retorna t tal que t*v pertence a
    reta r
6ee     return (r.p^r.q) / ((r.p-r.q)^v);
cbb }

// 2329fe
256 pt proj(pt p, line r) { // projecao do ponto p na reta r
bea     if (r.p == r.q) return r.p;
97a     r.q = r.q - r.p; p = p - r.p;
9f8     pt proj = r.q * ((p*r.q) / (r.q*r.q));
2cd     return proj + r.p;
cbb }

// 111fd2
d5c pt inter(line r, line s) { // r inter s
146     if (eq((r.p - r.q) ^ (s.p - s.q), 0)) return pt(DINF, DINF);
205     r.q = r.q - r.p, s.p = s.p - r.p, s.q = s.q - r.p;
543     return r.q * get_t(r.q, s) + r.p;
cbb }

// 35998c
676 bool interseg(line r, line s) { // se o seg de r intersecta o
    seg de s
19b     if (isinseg(r.p, s) or isinseg(r.q, s)
c21         or isinseg(s.p, r) or isinseg(s.q, r)) return 1;

9fa     return ccw(r.p, r.q, s.p) != ccw(r.p, r.q, s.q) and
413         ccw(s.p, s.q, r.p) != ccw(s.p, s.q, r.q);
cbb }

// 1b72e1
fcb ld disttoline(pt p, line r) { // distancia do ponto a reta
89a     return 2 * abs(sarea(p, r.p, r.q)) / dist(r.p, r.q);
cbb }

// 3679c0
bcc ld disttoseg(pt p, line r) { // distancia do ponto ao seg
73d     if ((r.q - r.p)*(p - r.p) < 0) return dist(r.p, p);
951     if ((r.p - r.q)*(p - r.q) < 0) return dist(r.q, p);

```

```

a19     return disttoline(p, r);
cbb }

// 222358
11d ld distseg(line a, line b) { // distancia entre seg
4df     if (interseg(a, b)) return 0;

349     ld ret = DINF;
341     ret = min(ret, disttoseg(a.p, b));
ceb     ret = min(ret, disttoseg(a.q, b));
093     ret = min(ret, disttoseg(b.p, a));
448     ret = min(ret, disttoseg(b.q, a));

edf     return ret;
cbb }

// POLIGONO

// corta poligono com a reta r deixando os pontos p tal que
// ccw(r.p, r.q, p)
// 2538f9
1a9 vector<pt> cut_polygon(vector<pt> v, line r) { // 0(n)
8af     vector<pt> ret;
8a4     for (int j = 0; j < v.size(); j++) {
dac         if (ccw(r.p, r.q, v[j])) ret.push_back(v[j]);
dce         if (v.size() == 1) continue;
030         line s(v[j], v[(j+1)%v.size()]);
ae3         pt p = inter(r, s);
a3d         if (isinseg(p, s)) ret.push_back(p);
cbb     }
8a1     ret.erase(unique(ret.begin(), ret.end()), ret.end());
24d     if (ret.size() > 1 and ret.back() == ret[0]) ret.pop_back();
edf     return ret;
cbb }

// distancia entre os retangulos a e b (lados paralelos aos
// eixos)
// assume que ta representado (inferior esquerdo, superior
// direito)
// 630253
5f5 ld dist_rect(pair<pt, pt> a, pair<pt, pt> b) {
080     ld hor = 0, vert = 0;
34b     if (a.second.x < b.first.x) hor = b.first.x - a.second.x;
f5f     else if (b.second.x < a.first.x) hor = a.first.x -
b.second.x;
4fd     if (a.second.y < b.first.y) vert = b.first.y - a.second.y;

```

```

80a     else if (b.second.y < a.first.y) vert = a.first.y -
b.second.y;
96f     return dist(pt(0, 0), pt(hor, vert));
cbb }

// 5df9cf
13d ld polarea(vector<pt> v) { // area do poligono
9c5     ld ret = 0;
c6e     for (int i = 0; i < v.size(); i++)
80f         ret += sarea(pt(0, 0), v[i], v[(i + 1) % v.size()]);
d03     return abs(ret);
cbb }

// se o ponto ta dentro do poligono: retorna 0 se ta fora,
// 1 se ta no interior e 2 se ta na borda
// a6423f
8e7 int inpol(vector<pt>& v, pt p) { // 0(n)
8de     int qt = 0;
f14     for (int i = 0; i < v.size(); i++) {
bda         if (p == v[i]) return 2;
6af         int j = (i+1)%v.size();
e38         if (eq(p.y, v[i].y) and eq(p.y, v[j].y)) {
97f             if ((v[i]-p)*(v[j]-p) < eps) return 2;
5e2             continue;
cbb         }
388         bool baixo = v[i].y+eps < p.y;
464         if (baixo == (v[j].y+eps < p.y)) continue;
366         auto t = (p-v[i])^(v[j]-v[i]);
1b4         if (eq(t, 0)) return 2;
839         if (baixo == (t > eps)) qt += baixo ? 1 : -1;
cbb     }
b84     return qt != 0;
cbb }

// c58350
6ff bool interpol(vector<pt> v1, vector<pt> v2) { // se dois
poligonos se intersectam - 0(n*m)
7d1     int n = v1.size(), m = v2.size();
c36     for (int i = 0; i < n; i++) if (inpol(v2, v1[i])) return 1;
ab8     for (int i = 0; i < n; i++) if (inpol(v1, v2[i])) return 1;
523     for (int i = 0; i < n; i++) for (int j = 0; j < m; j++)
0c8         if (interseg(line(v1[i], v1[(i+1)%n]), line(v2[j],
v2[(j+1)%m]))) return 1;
bb3     return 0;
cbb }

```

```

// 12559f
494 ld distpol(vector<pt> v1, vector<pt> v2) { // distancia entre
    poligonos
f6b     if (interpol(v1, v2)) return 0;

349     ld ret = DINF;

1c8     for (int i = 0; i < v1.size(); i++) for (int j = 0; j <
        v2.size(); j++)
6c2         ret = min(ret, distseg(line(v1[i], v1[(i + 1) %
            v1.size()]),
9d9             line(v2[j], v2[(j + 1) % v2.size()]))) );
edf     return ret;
cbb }

// 10d7e0
138 vector<pt> convex_hull(vector<pt> v) { // convex hull - O(n
    log(n))
fca     sort(v.begin(), v.end());
d76     v.erase(unique(v.begin(), v.end()), v.end());
52d     if (v.size() <= 1) return v;
526     vector<pt> l, u;
f14     for (int i = 0; i < v.size(); i++) {
fb2         while (l.size() > 1 and !ccw(l.end()[-2], l.end()[-1],
            v[i]))
364             l.pop_back();
c35         l.push_back(v[i]);
cbb     }
3e9     for (int i = v.size() - 1; i >= 0; i--) {
f19         while (u.size() > 1 and !ccw(u.end()[-2], u.end()[-1],
            v[i]))
7a8             u.pop_back();
a95         u.push_back(v[i]);
cbb     }
cfc     l.pop_back(); u.pop_back();
82b     for (pt i : u) l.push_back(i);
792     return l;
cbb }

483 struct convex_pol {
f50     vector<pt> pol;

// nao pode ter ponto colinear no convex hull
d98     convex_pol() {}
a04     convex_pol(vector<pt> v) : pol(convex_hull(v)) {}

```

```

// se o ponto ta dentro do hull - O(log(n))
// 800813
8af bool is_inside(pt p) {
eae     if (pol.size() == 1) return p == pol[0];
67f     int l = 1, r = pol.size();
40c     while (l < r) {
ee4         int m = (l+r)/2;
48f         if (ccw(p, pol[0], pol[m])) l = m+1;
ef3         else r = m;
cbb     }
00a     if (l == 1) return isinseg(p, line(pol[0], pol[1]));
9e7     if (l == pol.size()) return false;
1c0     return !ccw(p, pol[l], pol[l-1]);
cbb }

// ponto extremo em relacao a cmp(p, q) = p mais extremo q
// (copiado de https://github.com/gustavoM32/caderno-zika)
// 56ccd2
719 int extreme(const function<bool(pt, pt)>& cmp) {
b1c     int n = pol.size();
4a2     auto extr = [&](int i, bool& cur_dir) {
22a         cur_dir = cmp(pol[(i+1)%n], pol[i]);
61a         return !cur_dir and !cmp(pol[(i+n-1)%n], pol[i]);
214     };
63d     bool last_dir, cur_dir;
a0d     if (extr(0, last_dir)) return 0;
993     int l = 0, r = n;
ead     while (l+1 < r) {
ee4         int m = (l+r)/2;
f29         if (extr(m, cur_dir)) return m;
44a         bool rel_dir = cmp(pol[m], pol[l]);
b18         if ((!last_dir and cur_dir) or
261             (last_dir == cur_dir and rel_dir ==
                cur_dir)) {
8a6             l = m;
1f1             last_dir = cur_dir;
b6c         } else r = m;
cbb     }
792     return l;
cbb }

316 int max_dot(pt v) {
ec1     return extreme([&](pt p, pt q) { return p*v > q*v; });
cbb }

a54 pair<int, int> tangents(pt p) {
08c     auto L = [&](pt q, pt r) { return ccw(p, q, r); };
422     auto R = [&](pt q, pt r) { return ccw(p, r, q); };
fa8     return {extreme(L), extreme(R)};

```

```

cbb    }
214 };

    // CIRCUNFERENCIA

    // a125e4
911 pt getcenter(pt a, pt b, pt c) { // centro da circunf dado 3
    pontos
174     b = (a + b) / 2;
2ae     c = (a + c) / 2;
98b     return inter(line(b, b + rotate90(a - b)),
3f8         line(c, c + rotate90(a - c)));
cbb }

    // cd80c0
4b3 vector<pt> circ_line_inter(pt a, pt b, pt c, ld r) { //
    intersecao da circunf (c, r) e reta ab
8af     vector<pt> ret;
f2b     b = b-a, a = a-c;
4b1     ld A = b*b;
20a     ld B = a*b;
2e9     ld C = a*a - r*r;
1fa     ld D = B*B - A*C;
818     if (D < -eps) return ret;
dc5     ret.push_back(c+a+b*(-B+sqrt(D+eps))/A);
20e     if (D > eps) ret.push_back(c+a+b*(-B-sqrt(D))/A);
edf     return ret;
cbb }

    // fb11d8
ad2 vector<pt> circ_inter(pt a, pt b, ld r, ld R) { // intersecao
    da circunf (a, r) e (b, R)
8af     vector<pt> ret;
b7e     ld d = dist(a, b);
5ce     if (d > r+R or d+min(r, R) < max(r, R)) return ret;
398     ld x = (d*d-R*R+r*r)/(2*d);
183     ld y = sqrt(r*r-x*x);
325     pt v = (b-a)/d;
76e     ret.push_back(a+v*x + rotate90(v)*y);
2cb     if (y > 0) ret.push_back(a+v*x - rotate90(v)*y);
edf     return ret;
cbb }

    // 3a44fb
6e0 bool operator <(const line& a, const line& b) { // comparador
    pra reta

```

```

    // assume que as retas tem p < q
a13     pt v1 = a.q - a.p, v2 = b.q - b.p;
f82     if (!eq(angle(v1), angle(v2))) return angle(v1) < angle(v2);
780     return ccw(a.p, a.q, b.p); // mesmo angulo
cbb }

b14 bool operator ==(const line& a, const line& b) {
76c     return !(a < b) and !(b < a);
cbb }

    // comparador pro set pra fazer sweep line com segmentos
    // 36729f
2c4 struct cmp_sweepline {
d80     bool operator () (const line& a, const line& b) const {
        // assume que os segmentos tem p < q
191         if (a.p == b.p) return ccw(a.p, a.q, b.q);
231         if (!eq(a.p.x, a.q.x) and (eq(b.p.x, b.q.x) or
a.p.x+eps < b.p.x))
780             return ccw(a.p, a.q, b.p);
dc0         return ccw(a.p, b.q, b.p);
cbb     }
214 };

    // comparador pro set pra fazer sweep angle com segmentos
    // f778aa
bef pt dir;
5b0 struct cmp_sweepangle {
d80     bool operator () (const line& a, const line& b) const {
522         return get_t(dir, a) + eps < get_t(dir, b);
cbb     }
214 };

1.7 Primitivas Geometricas 3D

c83 typedef double ld;
e3b const ld DINF = 1e18;
107 const ld eps = 1e-9;

b32 #define sq(x) ((x)*(x))

d97 bool eq(ld a, ld b) {
ba0     return abs(a - b) <= eps;
cbb }

    // 3eef01

```



```

b2a struct pt { // ponto
2eb     ld x, y, z;
a50     pt(ld x_ = 0, ld y_ = 0, ld z_ = 0) : x(x_), y(y_),
        z(z_) {}
5bc     bool operator < (const pt p) const {
059         if (!eq(x, p.x)) return x < p.x;
f98         if (!eq(y, p.y)) return y < p.y;
44c         if (!eq(z, p.z)) return z < p.z;
bb3         return 0;
cbb     }
a83     bool operator == (const pt p) const {
41c         return eq(x, p.x) and eq(y, p.y) and eq(z, p.z);
cbb     }
44b     pt operator + (const pt p) const { return pt(x+p.x,
y+p.y, z+p.z); }
392     pt operator - (const pt p) const { return pt(x-p.x,
y-p.y, z-p.z); }
fb7     pt operator * (const ld c) const { return pt(x*c , y*c
, z*c ); }
7a1     pt operator / (const ld c) const { return pt(x/c , y/c
, z/c ); }
a65     ld operator * (const pt p) const { return x*p.x + y*p.y
+ z*p.z; }
7f6     pt operator ^ (const pt p) const { return pt(y*p.z -
z*p.y, z*p.x - x*p.z, x*p.y - y*p.x); }
5ed     friend istream& operator >> (istream& in, pt& p) {
9bf         return in >> p.x >> p.y >> p.z;
cbb     }
214 };

// 7ab617
b3a struct line { // reta
730     pt p, q;
0d6     line() {}
4b8     line(pt p_, pt q_) : p(p_), q(q_) {}
8d7     friend istream& operator >> (istream& in, line& r) {
4cb         return in >> r.p >> r.q;
cbb     }
214 };

// d5d580
79b struct plane { // plano
7e1     array<pt, 3> p; // pontos que definem o plano
29b     array<ld, 4> eq; // equacao do plano
bb7     plane() {}
fb0     plane(pt p_, pt q_, pt r_) : p({p_, q_, r_}) { build();

```

```

}

ca9     friend istream& operator >> (istream& in, plane& P) {
2ab         return in >> P.p[0] >> P.p[1] >> P.p[2];
70e         P.build();
cbb     }
0a8     void build() {
da2         pt dir = (p[1] - p[0]) ^ (p[2] - p[0]);
7d5         eq = {dir.x, dir.y, dir.z, dir*p[0]*(-1)};
cbb     }
214 };

// converte de coordenadas polares para cartesianas
// (angulos devem estar em radianos)
// phi eh o angulo com o eixo z (cima) theta eh o angulo de
// rotacao ao redor de z
// a4f17f
2fb pt convert(ld rho, ld th, ld phi) {
cf4     return pt(sin(phi) * cos(th), sin(phi) * sin(th),
cos(phi)) * rho;
cbb }

// projecao do ponto p na reta r
// 2329fe
256 pt proj(pt p, line r) {
bea     if (r.p == r.q) return r.p;
97a     r.q = r.q - r.p; p = p - r.p;
9f8     pt proj = r.q * ((p*r.q) / (r.q*r.q));
2cd     return proj + r.p;
cbb }

// projecao do ponto p no plano P
// 4a0d14
b1a pt proj(pt p, plane P) {
7b6     p = p - P.p[0], P.p[1] = P.p[1] - P.p[0], P.p[2] =
P.p[2] - P.p[0];
b69     pt norm = P.p[1] ^ P.p[2];
6ab     pt proj = p - (norm * (norm * p) / (norm*norm));
467     return proj + P.p[0];
cbb }

// distancia
// 2d06b0
a45 ld dist(pt a, pt b) {
fd9     return sqrt(sq(a.x-b.x) + sq(a.y-b.y) + sq(a.z-b.z));
cbb }

```

```

// distancia ponto reta
// 3c4e1b
137 ld distline(pt p, line r) {
ce1     return dist(p, proj(p, r));
cbb }

// distancia de ponto para segmento
// 42cbbd
d43 ld distseg(pt p, line r) {
73d     if ((r.q - r.p)*(p - r.p) < 0) return dist(r.p, p);
951     if ((r.p - r.q)*(p - r.q) < 0) return dist(r.q, p);
200     return distline(p, r);
cbb }

// distancia de ponto a plano com sinal
// d490d9
7cc ld sdist(pt p, plane P) {
150     return P.eq[0]*p.x + P.eq[1]*p.y + P.eq[2]*p.z +
P.eq[3];
cbb }

// distancia de ponto a plano
// 33dc8c
768 ld distplane(pt p, plane P) {
c3e     return abs(sdist(p, P));
cbb }

// se ponto pertence a reta
// 31a295
099 bool isinseg(pt p, line r) {
a32     return eq(distseg(p, r), 0);
cbb }

// se ponto pertence ao triangulo definido por P.p
// c81f7e
cd2 bool isinpol(pt p, vector<pt> v) {
fad     assert(v.size() >= 3);
bf4     pt norm = (v[1]-v[0]) ^ (v[2]-v[1]);
8a4     bool inside = true;
cec     int sign = -1;
f14     for (int i = 0; i < v.size(); i++) {
834         line r(v[(i+1)%3], v[i]);
2a9         if (isinseg(p, r)) return true;

4ef         pt ar = v[(i+1)%3] - v[i];

```

```

320         if (sign == -1) sign = ((ar^(p-v[i]))*norm > 0);
82b         else if (((ar^(p-v[i]))*norm > 0) != sign)
inside = false;
cbb     }
aca     return inside;
cbb }

// distancia de ponto ate poligono
// a8d4c2
361 ld distpol(pt p, vector<pt> v) {
3e7     pt p2 = proj(p, plane(v[0], v[1], v[2]));
61a     if (isinpol(p2, v)) return dist(p, p2);
349     ld ret = DINF;
f14     for (int i = 0; i < v.size(); i++) {
6af         int j = (i+1)%v.size();
5ee         ret = min(ret, distseg(p, line(v[i], v[j])));
cbb     }
edf     return ret;
cbb }

// intersecao de plano e segmento
// BOTH = o segmento esta no plano
// ONE = um dos pontos do segmento esta no plano
// PARAL = segmento paralelo ao plano
// CONCOR = segmento concorrente ao plano
// e2ecac
e51 enum RETCODE {BOTH, ONE, PARAL, CONCOR};
26b pair<RETCODE, pt> intersect(plane P, line r) {
fac     ld d1 = sdist(r.p, P);
f8f     ld d2 = sdist(r.q, P);
53a     if (eq(d1, 0) and eq(d2, 0))
504         return pair(BOTH, r.p);
72c     if (eq(d1, 0))
847         return pair(ONE, r.p);
485     if (eq(d2, 0))
168         return pair(ONE, r.q);
3fb     if ((d1 > 0 and d2 > 0) or (d1 < 0 and d2 < 0)) {
463         if (eq(d1-d2, 0)) return pair(PARAL, pt());
406         return pair(CONCOR, pt());
cbb     }
c84     ld frac = d1 / (d1 - d2);
3ff     pt res = r.p + ((r.q - r.p) * frac);
394     return pair(ONE, res);
cbb }

// rotaciona p ao redor do eixo u por um angulo a

```

```

// 7f0a40
787 pt rotate(pt p, pt u, ld a) {
773     u = u / dist(u, pt());
e6f     return u * (u * p) + (u ^ p ^ u) * cos(a) + (u ^ p) *
sin(a);
cbb }

1.8 Primitivas Geometricas Inteiras

2de #define sq(x) ((x)*(ll)(x))

// 840720
b2a struct pt { // ponto
e91     int x, y;
df1     pt(int x_ = 0, int y_ = 0) : x(x_), y(y_) {}
5bc     bool operator < (const pt p) const {
95a         if (x != p.x) return x < p.x;
89c         return y < p.y;
cbb     }
a83     bool operator == (const pt p) const {
d74         return x == p.x and y == p.y;
cbb     }
cb9     pt operator + (const pt p) const { return pt(x+p.x, y+p.y);
}
a24     pt operator - (const pt p) const { return pt(x-p.x, y-p.y);
}
0ef     pt operator * (const int c) const { return pt(x*c, y*c); }
60d     ll operator * (const pt p) const { return x*(ll)p.x +
y*(ll)p.y; }
d86     ll operator ^ (const pt p) const { return x*(ll)p.y -
y*(ll)p.x; }
5ed     friend istream& operator >> (istream& in, pt& p) {
e37         return in >> p.x >> p.y;
cbb     }
214 };

// 7ab617
b3a struct line { // reta
730     pt p, q;
0d6     line() {}
4b8     line(pt p_, pt q_) : p(p_), q(q_) {}
8d7     friend istream& operator >> (istream& in, line& r) {
4cb         return in >> r.p >> r.q;
cbb     }

```

```

214 };

// PONTO & VETOR

// 51563e
ea8 ll dist2(pt p, pt q) { // quadrado da distancia
f24     return sq(p.x - q.x) + sq(p.y - q.y);
cbb }

// bf431d
5a2 ll sarea2(pt p, pt q, pt r) { // 2 * area com sinal
586     return (q-p)^(r-q);
cbb }

// a082d3
e32 bool col(pt p, pt q, pt r) { // se p, q e r sao colin.
034     return sarea2(p, q, r) == 0;
cbb }

// 42bb09
0cd bool ccw(pt p, pt q, pt r) { // se p, q, r sao ccw
276     return sarea2(p, q, r) > 0;
cbb }

// fcf924
c31 int quad(pt p) { // quadrante de um ponto
dbb     return (p.x<0)^3*(p.y<0);
cbb }

// 77187b
2df bool compare_angle(pt p, pt q) { // retorna se ang(p) < ang(q)
9fc     if (quad(p) != quad(q)) return quad(p) < quad(q);
ea1     return ccw(q, pt(0, 0), p);
cbb }

// e4ad5e
ab1 pt rotate90(pt p) { // rotaciona 90 graus
a0d     return pt(-p.y, p.x);
cbb }

// RETA

// c9f07f
099 bool isinseg(pt p, line r) { // se p pertence ao seg de r
f65     pt a = r.p - p, b = r.q - p;
2ac     return (a ^ b) == 0 and (a * b) <= 0;

```

```

cbb }

// 35998c
676 bool interseg(line r, line s) { // se o seg de r intersecta o
seg de s
19b     if (isinseg(r.p, s) or isinseg(r.q, s)
c21         or isinseg(s.p, r) or isinseg(s.q, r)) return 1;

9fa     return ccw(r.p, r.q, s.p) != ccw(r.p, r.q, s.q) and
413         ccw(s.p, s.q, r.p) != ccw(s.p, s.q, r.q);
cbb }

// dd8702
9e0 int segpoints(line r) { // numero de pontos inteiros no segmento
9ce     return 1 + __gcd(abs(r.p.x - r.q.x), abs(r.p.y - r.q.y));
cbb }

// d273be
88a double get_t(pt v, line r) { // retorna t tal que t*v pertence
a reta r
1ad     return (r.p^r.q) / (double) ((r.p-r.q)^v);
cbb }

// POLIGONO

// quadrado da distancia entre os retangulos a e b (lados
paralelos aos eixos)
// assume que ta representado (inferior esquerdo, superior
direito)
// e13018
485 ll dist2_rect(pair<pt, pt> a, pair<pt, pt> b) {
c59     int hor = 0, vert = 0;
34b     if (a.second.x < b.first.x) hor = b.first.x - a.second.x;
f5f     else if (b.second.x < a.first.x) hor = a.first.x -
b.second.x;
4fd     if (a.second.y < b.first.y) vert = b.first.y - a.second.y;
80a     else if (b.second.y < a.first.y) vert = a.first.y -
b.second.y;
869     return sq(hor) + sq(vert);
cbb }

// d5f693
9c3 ll polarea2(vector<pt> v) { // 2 * area do poligono
b73     ll ret = 0;
c6e     for (int i = 0; i < v.size(); i++)
532         ret += sarea2(pt(0, 0), v[i], v[(i + 1) % v.size()]);

```

```

d03     return abs(ret);
cbb }

// se o ponto ta dentro do poligono: retorna 0 se ta fora,
// 1 se ta no interior e 2 se ta na borda
// afd587
8e7 int inpol(vector<pt>& v, pt p) { // 0(n)
8de     int qt = 0;
f14     for (int i = 0; i < v.size(); i++) {
bda         if (p == v[i]) return 2;
6af         int j = (i+1)%v.size();
cc6         if (p.y == v[i].y and p.y == v[j].y) {
547             if ((v[i]-p)*(v[j]-p) <= 0) return 2;
5e2             continue;
cbb         }
78c         bool baixo = v[i].y < p.y;
057         if (baixo == (v[j].y < p.y)) continue;
366         auto t = (p-v[i])^(v[j]-v[i]);
2ad         if (!t) return 2;
0bb         if (baixo == (t > 0)) qt += baixo ? 1 : -1;
cbb     }
b84     return qt != 0;
cbb }

// 10d7e0
138 vector<pt> convex_hull(vector<pt> v) { // convex hull - 0(n
log(n))
fca     sort(v.begin(), v.end());
d76     v.erase(unique(v.begin(), v.end()), v.end());
52d     if (v.size() <= 1) return v;
526     vector<pt> l, u;
f14     for (int i = 0; i < v.size(); i++) {
fb2         while (l.size() > 1 and !ccw(l.end()[-2], l.end()[-1],
v[i]))
364             l.pop_back();
c35         l.push_back(v[i]);
cbb     }
3e9     for (int i = v.size() - 1; i >= 0; i--) {
f19         while (u.size() > 1 and !ccw(u.end()[-2], u.end()[-1],
v[i]))
7a8             u.pop_back();
a95         u.push_back(v[i]);
cbb     }
cfc     l.pop_back(); u.pop_back();
82b     for (pt i : u) l.push_back(i);
792     return l;

```

```

cbb }

// af2d96
786 ll interior_points(vector<pt> v) { // pontos inteiros dentro de
    um poligono simples
c4e    ll b = 0;
c6e    for (int i = 0; i < v.size(); i++)
0ce        b += segpoints(line(v[i], v[(i+1)%v.size()])) - 1;
a1c    return (polarea2(v) - b) / 2 + 1;
cbb }

483 struct convex_pol {
f50    vector<pt> pol;

    // nao pode ter ponto colinear no convex hull
d98    convex_pol() {}
a04    convex_pol(vector<pt> v) : pol(convex_hull(v)) {}

    // se o ponto ta dentro do hull - O(log(n))
    // 800813
8af    bool is_inside(pt p) {
eae        if (pol.size() == 1) return p == pol[0];
67f        int l = 1, r = pol.size();
40c        while (l < r) {
ee4            int m = (l+r)/2;
48f            if (ccw(p, pol[0], pol[m])) l = m+1;
ef3            else r = m;
cbb        }
00a        if (l == 1) return isinseg(p, line(pol[0], pol[1]));
9e7        if (l == pol.size()) return false;
1c0        return !ccw(p, pol[1], pol[l-1]);
cbb    }

    // ponto extremo em relacao a cmp(p, q) = p mais extremo q
    // (copiado de https://github.com/gustavoM32/caderno-zika)
    // 56ccd2
719    int extreme(const function<bool(pt, pt)>& cmp) {
b1c        int n = pol.size();
4a2        auto extr = [&](int i, bool& cur_dir) {
22a            cur_dir = cmp(pol[(i+1)%n], pol[i]);
61a            return !cur_dir and !cmp(pol[(i+n-1)%n], pol[i]);
214        };
63d        bool last_dir, cur_dir;
a0d        if (extr(0, last_dir)) return 0;
993        int l = 0, r = n;
ead        while (l+1 < r) {
ee4            int m = (l+r)/2;

```

```

f29            if (extr(m, cur_dir)) return m;
44a            bool rel_dir = cmp(pol[m], pol[l]);
b18            if ((!last_dir and cur_dir) or
261                (last_dir == cur_dir and rel_dir ==
                    cur_dir)) {
8a6                l = m;
1f1                last_dir = cur_dir;
b6c            } else r = m;
cbb        }
792        return l;
cbb    }
316    int max_dot(pt v) {
ec1        return extreme([&](pt p, pt q) { return p*v > q*v; });
cbb    }
a54    pair<int, int> tangents(pt p) {
08c        auto L = [&](pt q, pt r) { return ccw(p, q, r); };
422        auto R = [&](pt q, pt r) { return ccw(p, r, q); };
fa8        return {extreme(L), extreme(R)};
cbb    }
214 };

// dca598
6e0 bool operator <(const line& a, const line& b) { // comparador
    pra reta
    // assume que as retas tem p < q
a13    pt v1 = a.q - a.p, v2 = b.q - b.p;
036    bool b1 = compare_angle(v1, v2), b2 = compare_angle(v2, v1);
73c    if (b1 or b2) return b1;
780    return ccw(a.p, a.q, b.p); // mesmo angulo
cbb }
b14 bool operator ==(const line& a, const line& b) {
76c    return !(a < b) and !(b < a);
cbb }

    // comparador pro set pra fazer sweep line com segmentos
    // 6774df
2c4 struct cmp_sweepeline {
d80    bool operator () (const line& a, const line& b) const {
        // assume que os segmentos tem p < q
191        if (a.p == b.p) return ccw(a.p, a.q, b.q);
614        if (a.p.x != a.q.x and (b.p.x == b.q.x or a.p.x <
            b.p.x))
780            return ccw(a.p, a.q, b.p);
dc0            return ccw(a.p, b.q, b.p);
cbb        }
214 };

```

```

// comparador pro set pra fazer sweep angle com segmentos
// 1ee7f5
bef pt dir;
5b0 struct cmp_sweepangle {
d80     bool operator () (const line& a, const line& b) const {
261         return get_t(dir, a) < get_t(dir, b);
cbb     }
214 };

```

## 2 Grafos

### 2.1 AGM Direcionada

```

// Fala o menor custo para selecionar arestas tal que
// o vertice 'r' alcance todos
// Se nao tem como, retorna LINF
//
// 0(m log(n))
// dc345b

3c9 struct node {
f31     pair<ll, int> val;
4e4     ll lazy;
b19     node *l, *r;
f93     node() {}
c53     node(pair<int, int> v) : val(v), lazy(0), l(NULL), r(NULL)
{}

a9c     void prop() {
768         val.first += lazy;
b87         if (l) l->lazy += lazy;
d3b         if (r) r->lazy += lazy;
c60         lazy = 0;
cbb     }
214 };
de5 void merge(node*& a, node* b) {
c11     if (!a) swap(a, b);
802     if (!b) return;
626     a->prop(), b->prop();
d04     if (a->val > b->val) swap(a, b);
4b0     merge(rand()%2 ? a->l : a->r, b);
cbb }

```

```

d01 pair<ll, int> pop(node*& R) {
e8f     R->prop();
22e     auto ret = R->val;
af0     node* tmp = R;
3f3     merge(R->l, R->r);
6c9     R = R->l;
3e4     if (R) R->lazy -= ret.first;
7c3     delete tmp;
edf     return ret;
cbb }

6f6 void apaga(node* R) { if (R) apaga(R->l), apaga(R->r), delete
R; }

f13 ll dmst(int n, int r, vector<pair<pair<int, int>, int>>& ar) {
94e     vector<int> p(n); iota(p.begin(), p.end(), 0);
a23     function<int(int)> find = [&](int k) { return
p[k]==k?k:p[k]=find(p[k]); };
2d7     vector<node*> h(n);
56f     for (auto e : ar) merge(h[e.first.second], new
node({e.second, e.first.first}));
fd1     vector<int> pai(n, -1), path(n);
66e     pai[r] = r;
04b     ll ans = 0;

603     for (int i = 0; i < n; i++) { // vai conectando todo mundo
2a3         int u = i, at = 0;
cae         while (pai[u] == -1) {
daa             if (!h[u]) { // nao tem
947                 for (auto i : h) apaga(i);
77c                 return LINF;
cbb             }
167             path[at++] = u, pai[u] = i;
55e             auto [mi, v] = pop(h[u]);
64c             ans += mi;

5e2             if (pai[u = find(v)] == i) { // ciclo
86f                 while (find(v = path[--at]) != u)
621                     merge(h[u], h[v]), h[v] = NULL, p[find(v)]
= u;
57a                 pai[u] = -1;
cbb             }
cbb         }
cbb     }
947     for (auto i : h) apaga(i);
ba7     return ans;
cbb }

```

## 2.2 Bellman-Ford

```
// Calcula a menor distancia
// entre a e todos os vertices e
// detecta ciclo negativo
// Retorna 1 se ha ciclo negativo
// Nao precisa representar o grafo,
// soh armazenar as arestas
//
// O(nm)
// 03059b

14e int n, m;
248 int d[MAX];
e93 vector<pair<int, int>> ar; // vetor de arestas
9e2 vector<int> w;           // peso das arestas

6be bool bellman_ford(int a) {
8ec     for (int i = 0; i < n; i++) d[i] = INF;
8a8     d[a] = 0;

4e3     for (int i = 0; i <= n; i++)
891         for (int j = 0; j < m; j++) {
6e4             if (d[ar[j].second] > d[ar[j].first] + w[j]) {
705                 if (i == n) return 1;

e93                 d[ar[j].second] = d[ar[j].first] + w[j];
cbb             }
cbb         }

bb3     return 0;
cbb }
```

## 2.3 Block-Cut Tree

```
// Cria a block-cut tree, uma arvore com os blocos
// e os pontos de articulacao
// Blocos sao componentes 2-vertice-conexos maximais
// Uma 2-coloracao da arvore eh tal que uma cor sao
// os blocos, e a outra cor sao os pontos de art.
// Funciona para grafo nao conexo
//
// art[i] responde o numero de novas componentes conexas
// criadas apos a remocao de i do grafo g
```

```
// Se art[i] >= 1, i eh ponto de articulacao
//
// Para todo i <= blocks.size()
// blocks[i] eh uma componente 2-vertice-conexa maximal
// edgblocks[i] sao as arestas do bloco i
// tree[i] eh um vertice da arvore que corresponde ao bloco i
//
// pos[i] responde a qual vertice da arvore vertice i pertence
// Arvore tem no maximo 2n vertices
//
// O(n+m)
// 056fa2

d10 struct block_cut_tree {
d8e     vector<vector<int>> g, blocks, tree;
43b     vector<vector<pair<int, int>>> edgblocks;
4ce     stack<int> s;
6c0     stack<pair<int, int>> s2;
2bb     vector<int> id, art, pos;

763     block_cut_tree(vector<vector<int>> g_) : g(g_) {
af1         int n = g.size();
37a         id.resize(n, -1), art.resize(n), pos.resize(n);
6f2         build();
cbb     }

df6     int dfs(int i, int& t, int p = -1) {
cf0         int lo = id[i] = t++;
18e         s.push(i);

827         if (p != -1) s2.emplace(i, p);
53f         for (int j : g[i]) if (j != p and id[j] != -1)
s2.emplace(i, j);

cac         for (int j : g[i]) if (j != p) {
9a3             if (id[j] == -1) {
121                 int val = dfs(j, t, i);
0c3                 lo = min(lo, val);

588                 if (val >= id[i]) {
66a                     art[i]++;
483                     blocks.emplace_back(1, i);
110                     while (blocks.back().back() != j)
138                         blocks.back().push_back(s.top()),
s.pop();
```

```

128         edgblocks.emplace_back(1, s2.top()),
s2.pop();
47e         while (edgblocks.back().back() != pair(j,
i))
bce             edgblocks.back().push_back(s2.top()),
s2.pop();
cbb     }
        // if (val > id[i]) aresta i-j eh ponte
cbb     }
328     else lo = min(lo, id[j]);
cbb     }

3bd     if (p == -1 and art[i]) art[i]--;
253     return lo;
cbb     }

0a8     void build() {
6bb         int t = 0;
abf         for (int i = 0; i < g.size(); i++) if (id[i] == -1)
dfs(i, t, -1);

56c         tree.resize(blocks.size());
f7d         for (int i = 0; i < g.size(); i++) if (art[i])
965             pos[i] = tree.size(), tree.emplace_back();

973         for (int i = 0; i < blocks.size(); i++) for (int j :
blocks[i]) {
403             if (!art[j]) pos[j] = i;
101             else tree[i].push_back(pos[j]),
tree[pos[j]].push_back(i);
cbb         }
cbb     }
214 };

```

## 2.4 Blossom - matching maximo em grafo geral

```

// O(n^3)
// Se for bipartido, nao precisa da funcao
// 'contract', e roda em O(nm)
// 4426a4

042 vector<int> g[MAX];
128 int match[MAX]; // match[i] = com quem i esta matchzado ou -1
1f1 int n, pai[MAX], base[MAX], vis[MAX];

```

```

26a queue<int> q;

107 void contract(int u, int v, bool first = 1) {
165     static vector<bool> bloss;
fbc     static int l;
418     if (first) {
a47         bloss = vector<bool>(n, 0);
042         vector<bool> teve(n, 0);
ddf         int k = u; l = v;
31e         while (1) {
297             teve[k = base[k]] = 1;
116             if (match[k] == -1) break;
dfa             k = pai[match[k]];
cbb         }
d31         while (!teve[l = base[l]]) l = pai[match[l]];
cbb     }
2e9     while (base[u] != l) {
e29         bloss[base[u]] = bloss[base[match[u]]] = 1;
8fa         pai[u] = v;
0b0         v = match[u];
a51         u = pai[match[u]];
cbb     }
71c     if (!first) return;
95e     contract(v, u, 0);
6ee     for (int i = 0; i < n; i++) if (bloss[base[i]]) {
594         base[i] = l;
ca7         if (!vis[i]) q.push(i);
29a         vis[i] = 1;
cbb     }
cbb }

f10 int getpath(int s) {
88f     for (int i = 0; i < n; i++) base[i] = i, pai[i] = -1,
vis[i] = 0;
ded     vis[s] = 1; q = queue<int>(); q.push(s);
402     while (q.size()) {
be1         int u = q.front(); q.pop();
bdc         for (int i : g[u]) {
7a2             if (base[i] == base[u] or match[u] == i) continue;
e35             if (i == s or (match[i] != -1 and pai[match[i]] !=
-1))
4f2                 contract(u, i);
e2e             else if (pai[i] == -1) {
545                 pai[i] = u;
f6a                 if (match[i] == -1) return i;
818                 i = match[i];

```



```

29d         vis[i] = 1; q.push(i);
cbb     }
cbb     }
cbb     }
daa     return -1;
cbb }

83f int blossom() {
1a4     int ans = 0;
315     memset(match, -1, sizeof(match));
2e3     for (int i = 0; i < n; i++) if (match[i] == -1)
f76         for (int j : g[i]) if (match[j] == -1) {
1bc             match[i] = j;
f1d             match[j] = i;
0df             ans++;
c2b             break;
cbb         }
da8     for (int i = 0; i < n; i++) if (match[i] == -1) {
7e3         int j = getpath(i);
5f2         if (j == -1) continue;
0df         ans++;
3a0         while (j != -1) {
ef0             int p = pai[j], pp = match[p];
348             match[p] = j;
fe9             match[j] = p;
55d             j = pp;
cbb         }
cbb     }
ba7     return ans;
cbb }

```

## 2.5 Centro de arvore

```

// Retorna o diametro e o(s) centro(s) da arvore
// Uma arvore tem sempre um ou dois centros e estes estao no meio
// do diametro
//
// 0(n)
// cladeb

042 vector<int> g[MAX];
df1 int d[MAX], par[MAX];

544 pair<int, vector<int>> center() {

```

```

a95     int f, df;
36d     function<void(int)> dfs = [&] (int v) {
d47         if (d[v] > df) f = v, df = d[v];
e68         for (int u : g[v]) if (u != par[v])
1a5             d[u] = d[v] + 1, par[u] = v, dfs(u);
214     };

1b0     f = df = par[0] = -1, d[0] = 0;
41e     dfs(0);
c2d     int root = f;
0f6     f = df = par[root] = -1, d[root] = 0;
14e     dfs(root);

761     vector<int> c;
87e     while (f != -1) {
999         if (d[f] == df/2 or d[f] == (df+1)/2) c.push_back(f);
19c         f = par[f];
cbb     }

00f     return {df, c};
cbb }

```

## 2.6 Centroid

```

// Computa os 2 centroids da arvore
//
// 0(n)
// e16075

97a int n, subsize[MAX];
042 vector<int> g[MAX];

98f void dfs(int k, int p=-1) {
bd2     subsize[k] = 1;
6e5     for (int i : g[k]) if (i != p) {
801         dfs(i, k);
2e3         subsize[k] += subsize[i];
cbb     }
cbb }

2e8 int centroid(int k, int p=-1, int size=-1) {
e73     if (size == -1) size = subsize[k];
8df     for (int i : g[k]) if (i != p) if (subsize[i] > size/2)
bab         return centroid(i, k, size);

```

```

839     return k;
cbb }

f20 pair<int, int> centroids(int k=0) {
051     dfs(k);
909     int i = centroid(k), i2 = i;
8dd     for (int j : g[i]) if (2*subsize[j] == subsize[k]) i2 = j;
0cb     return {i, i2};
cbb }

```

## 2.7 Centroid decomposition

```

// decomp(0, k) computa numero de caminhos com 'k' arestas
// Mudar depois do comentario
//
// O(n log(n))
// fe2541

042 vector<int> g[MAX];
ba8 int sz[MAX], rem[MAX];

747 void dfs(vector<int>& path, int i, int l=-1, int d=0) {
547     path.push_back(d);
75f     for (int j : g[i]) if (j != l and !rem[j]) dfs(path, j, i,
d+1);
cbb }

071 int dfs_sz(int i, int l=-1) {
02c     sz[i] = 1;
e5c     for (int j : g[i]) if (j != l and !rem[j]) sz[i] +=
dfs_sz(j, i);
191     return sz[i];
cbb }

85a int centroid(int i, int l, int size) {
994     for (int j : g[i]) if (j != l and !rem[j] and sz[j] > size
/ 2)
735         return centroid(j, i, size);
d9a     return i;
cbb }

d79 ll decomp(int i, int k) {
106     int c = centroid(i, i, dfs_sz(i));
a67     rem[c] = 1;

```

```

// gasta O(n) aqui - dfs sem ir pros caras removidos
04b ll ans = 0;
020 vector<int> cnt(sz[i]);
878 cnt[0] = 1;
0a8 for (int j : g[c]) if (!rem[j]) {
5b4     vector<int> path;
baf     dfs(path, j);
1a1     for (int d : path) if (0 <= k-d-1 and k-d-1 < sz[i])
285         ans += cnt[k-d-1];
e8b     for (int d : path) cnt[d+1]++;
cbb }

1c1 for (int j : g[c]) if (!rem[j]) ans += decomp(j, k);
3f1 rem[c] = 0;
ba7 return ans;
cbb }

```

## 2.8 Centroid Tree

```

// Constroi a centroid tree
// p[i] eh o pai de i na centroid-tree
// dist[i][k] = distancia na arvore original entre i
// e o k-esimo ancestral na arvore da centroid
//
// O(n log(n)) de tempo e memoria
// a0e7c7

845 vector<int> g[MAX], dist[MAX];
c1e int sz[MAX], rem[MAX], p[MAX];

071 int dfs_sz(int i, int l=-1) {
02c     sz[i] = 1;
e5c     for (int j : g[i]) if (j != l and !rem[j]) sz[i] +=
dfs_sz(j, i);
191     return sz[i];
cbb }

85a int centroid(int i, int l, int size) {
994     for (int j : g[i]) if (j != l and !rem[j] and sz[j] > size
/ 2)
735         return centroid(j, i, size);
d9a     return i;
cbb }

```

```

324 void dfs_dist(int i, int l, int d=0) {
541     dist[i].push_back(d);
5a1     for (int j : g[i]) if (j != l and !rem[j])
82a         dfs_dist(j, i, d+1);
cbb }

27e void decomp(int i, int l = -1) {
106     int c = centroid(i, i, dfs_sz(i));
1b9     rem[c] = 1, p[c] = 1;
534     dfs_dist(c, c);
a2a     for (int j : g[c]) if (!rem[j]) decomp(j, c);
cbb }

76c void build(int n) {
235     for (int i = 0; i < n; i++) rem[i] = 0, dist[i].clear();
867     decomp(0);
96b     for (int i = 0; i < n; i++) reverse(dist[i].begin(),
dist[i].end());
cbb }

```

## 2.9 Dijkstra

```

// encontra menor distancia de x
// para todos os vertices
// se ao final do algoritmo d[i] = LINF,
// entao x nao alcanca i
//
// O(m log(n))
// 695ac4

eff ll d[MAX];
c0d vector<pair<int, int>> g[MAX]; // {vizinho, peso}

1a8 int n;

abc void dijkstra(int v) {
22c     for (int i = 0; i < n; i++) d[i] = LINF;
a7f     d[v] = 0;
88c     priority_queue<pair<ll, int>> pq;
b32     pq.emplace(0, v);

265     while (pq.size()) {
a25         auto [ndist, u] = pq.top(); pq.pop();

```

```

953         if (-ndist > d[u]) continue;

cda         for (auto [idx, w] : g[u]) if (d[idx] > d[u] + w) {
331             d[idx] = d[u] + w;
a84             pq.emplace(-d[idx], idx);
cbb         }
cbb     }
cbb }

```

## 2.10 Dinitz

```

// O(min(m * max_flow, n^2 m))
// Grafo com capacidades 1: O(min(m sqrt(m), m * n^(2/3)))
// Todo vertice tem grau de entrada ou saida 1: O(m sqrt(n))

// 67ce89
472 struct dinitz {
61f     const bool scaling = false; // com scaling -> O(nm
log(MAXCAP)),
206     int lim; // com constante alta
670     struct edge {
358         int to, cap, rev, flow;
7f9         bool res;
d36         edge(int to_, int cap_, int rev_, bool res_)
a94             : to(to_), cap(cap_), rev(rev_), flow(0), res(res_)
        {}
214     };

002     vector<vector<edge>> g;
216     vector<int> lev, beg;
a71     ll F;
190     dinitz(int n) : g(n), F(0) {}

087     void add(int a, int b, int c) {
bae         g[a].emplace_back(b, c, g[b].size(), false);
4c6         g[b].emplace_back(a, 0, g[a].size()-1, true);
cbb     }
123     bool bfs(int s, int t) {
90f         lev = vector<int>(g.size(), -1); lev[s] = 0;
64c         beg = vector<int>(g.size(), 0);
8b2         queue<int> q; q.push(s);
402         while (q.size()) {
be1             int u = q.front(); q.pop();
bd9             for (auto& i : g[u]) {

```

```

dbc         if (lev[i.to] != -1 or (i.flow == i.cap))
continue;
b4f         if (scaling and i.cap - i.flow < lim) continue;
185         lev[i.to] = lev[u] + 1;
8ca         q.push(i.to);
cbb     }
cbb     }
0de     return lev[t] != -1;
cbb     }
dfb     int dfs(int v, int s, int f = INF) {
50b         if (!f or v == s) return f;
88f         for (int& i = beg[v]; i < g[v].size(); i++) {
027             auto& e = g[v][i];
206             if (lev[e.to] != lev[v] + 1) continue;
ee0             int foi = dfs(e.to, s, min(f, e.cap - e.flow));
749             if (!foi) continue;
3c5             e.flow += foi, g[e.to][e.rev].flow -= foi;
45c             return foi;
cbb         }
bb3         return 0;
cbb     }
ff6     ll max_flow(int s, int t) {
a86         for (lim = scaling ? (1<<30) : 1; lim; lim /= 2)
9d1             while (bfs(s, t)) while (int ff = dfs(s, t)) F +=
ff;
4ff         return F;
cbb     }
214 };

// Recupera as arestas do corte s-t
// d23977
dbd vector<pair<int, int>> get_cut(dinitz& g, int s, int t) {
f07     g.max_flow(s, t);
68c     vector<pair<int, int>> cut;
1b0     vector<int> vis(g.g.size(), 0), st = {s};
321     vis[s] = 1;
3c6     while (st.size()) {
b17         int u = st.back(); st.pop_back();
322         for (auto e : g.g[u]) if (!vis[e.to] and e.flow < e.cap)
c17             vis[e.to] = 1, st.push_back(e.to);
cbb     }
481     for (int i = 0; i < g.g.size(); i++) for (auto e : g.g[i])
9d2         if (vis[i] and !vis[e.to] and !e.res)
cut.emplace_back(i, e.to);
d1b     return cut;
cbb }

```

## 2.11 Dominator Tree - Kawakami

```

// Se vira pra usar ai
//
// build - O(m log(n))
// dominates - O(1)
// c80920

1a8 int n;

bbf namespace d_tree {
042     vector<int> g[MAX];

// The dominator tree
b39     vector<int> tree[MAX];
5af     int dfs_l[MAX], dfs_r[MAX];

// Auxiliary data
a2e     vector<int> rg[MAX], bucket[MAX];
3ef     int idom[MAX], sdom[MAX], prv[MAX], pre[MAX];
44b     int ancestor[MAX], label[MAX];
563     vector<int> preorder;

76a     void dfs(int v) {
6a1         static int t = 0;
db6         pre[v] = ++t;
767         sdom[v] = label[v] = v;
a3d         preorder.push_back(v);
d08         for (int nxt: g[v]) {
56c             if (sdom[nxt] == -1) {
eed                 prv[nxt] = v;
900                 dfs(nxt);
cbb             }
2b5             rg[nxt].push_back(v);
cbb         }
cbb     }

62e     int eval(int v) {
c93         if (ancestor[v] == -1) return v;
a75         if (ancestor[ancestor[v]] == -1) return label[v];
f33         int u = eval(ancestor[v]);
b49         if (pre[sdom[u]] < pre[sdom[label[v]]]) label[v] = u;
66e         ancestor[v] = ancestor[u];
c24         return label[v];
cbb     }

4b2     void dfs2(int v) {
6a1         static int t = 0;

```

```

330     dfs_l[v] = t++;
5e0     for (int nxt: tree[v]) dfs2(nxt);
8e2     dfs_r[v] = t++;
cbb }
c2c void build(int s) {
603     for (int i = 0; i < n; i++) {
e6f         sdom[i] = pre[i] = ancestor[i] = -1;
2e1         rg[i].clear();
50a         tree[i].clear();
666         bucket[i].clear();
cbb     }
772     preorder.clear();
c6c     dfs(s);
12b     if (preorder.size() == 1) return;
3c7     for (int i = int(preorder.size()) - 1; i >= 1; i--) {
6c6         int w = preorder[i];
a52         for (int v: rg[w]) {
5c1             int u = eval(v);
a17             if (pre[sdom[u]] < pre[sdom[w]]) sdom[w] =
sdom[u];
cbb         }
680         bucket[sdom[w]].push_back(w);
ea7         ancestor[w] = prv[w];
b99         for (int v: bucket[prv[w]]) {
5c1             int u = eval(v);
977             idom[v] = (u == v) ? sdom[v] : u;
cbb         }
2cc         bucket[prv[w]].clear();
cbb     }
d0c     for (int i = 1; i < preorder.size(); i++) {
6c6         int w = preorder[i];
14b         if (idom[w] != sdom[w]) idom[w] = idom[idom[w]];
32f         tree[idom[w]].push_back(w);
cbb     }
8ac     idom[s] = sdom[s] = -1;
1b6     dfs2(s);
cbb }

// Whether every path from s to v passes through u
490 bool dominates(int u, int v) {
c75     if (pre[v] == -1) return 1; // vacuously true
2ea     return dfs_l[u] <= dfs_l[v] && dfs_r[v] <= dfs_r[u];
cbb }
214 };

```

## 2.12 Euler Path / Euler Cycle

```

// Para declarar: 'euler<true> E(n);' se quiser
// direcionado e com 'n' vertices
// As funcoes retornam um par com um booleano
// indicando se possui o cycle/path que voce pediu,
// e um vector de {vertice, id da aresta para chegar no vertice}
// Se for get_path, na primeira posicao o id vai ser -1
// get_path(src) tenta achar um caminho ou ciclo euleriano
// começando no vertice 'src'.
// Se achar um ciclo, o primeiro e ultimo vertice serao 'src'.
// Se for um P3, um possiveo retorno seria [0, 1, 2, 0]
// get_cycle() acha um ciclo euleriano se o grafo for euleriano.
// Se for um P3, um possivel retorno seria [0, 1, 2]
// (vertie inicial nao repete)
//
// 0(n+m)
// 7113df

63f template<bool directed=false> struct euler {
1a8     int n;
4c0     vector<vector<pair<int, int>>> g;
d63     vector<int> used;

30f     euler(int n_) : n(n_), g(n) {}
50f     void add(int a, int b) {
4cd         int at = used.size();
c51         used.push_back(0);
74e         g[a].emplace_back(b, at);
fab         if (!directed) g[b].emplace_back(a, at);
cbb     }
d41 #warning chamar para o src certo!
eed     pair<bool, vector<pair<int, int>>> get_path(int src) {
baf         if (!used.size()) return {true, {}};
b25         vector<int> beg(n, 0);
4ec         for (int& i : used) i = 0;
// {{vertice, anterior}, label}
363         vector<pair<pair<int, int>, int>> ret, st = {{{src,
-1}, -1}};
3c6         while (st.size()) {
8ff             int at = st.back().first.first;
002             int& it = beg[at];
8a1             while (it < g[at].size() and
used[g[at][it].second]) it++;
8e4             if (it == g[at].size()) {
9dd                 if (ret.size() and ret.back().first.second !=

```

```

    at)
b82         return {false, {}};
420         ret.push_back(st.back()), st.pop_back();
9d9     } else {
daa         st.push_back({g[at][it].first, at},
g[at][it].second});
eb8         used[g[at][it].second] = 1;
cbb     }
cbb     }
a19     if (ret.size() != used.size()+1) return {false, {}};
f77     vector<pair<int, int>> ans;
fdf     for (auto i : ret) ans.emplace_back(i.first.first,
i.second);
459     reverse(ans.begin(), ans.end());
997     return {true, ans};
cbb     }
9b6     pair<bool, vector<pair<int, int>>> get_cycle() {
baf         if (!used.size()) return {true, {}};
ad1         int src = 0;
34b         while (!g[src].size()) src++;
687         auto ans = get_path(src);
33c         if (!ans.first or ans.second[0].first !=
ans.second.back().first)
b82             return {false, {}};
350         ans.second[0].second = ans.second.back().second;
8b8         ans.second.pop_back();
ba7         return ans;
cbb     }
214 };

```

## 2.13 Euler Tour Tree

```

// Mantem uma floresta enraizada dinamicamente
// e permite queries/updates em sub-arvore
//
// Chamar ETT E(n, v), passando n = numero de vertices
// e v = vector com os valores de cada vertice (se for vazio,
// constroi tudo com 0
//
// link(v, u) cria uma aresta de v pra u, de forma que u se torna
// o pai de v (eh preciso que v seja raiz anteriormente)
// cut(v) corta a resta de v para o pai
// query(v) retorna a soma dos valores da sub-arvore de v
// update(v, val) soma val em todos os vertices da sub-arvore de v

```

```

// update_v(v, val) muda o valor do vertice v para val
// is_in_subtree(v, u) responde se o vertice u esta na sub-arvore
// de v
//
// Tudo O(log(n)) com alta probabilidade
// c97d63

878 mt19937 rng((int)
    chrono::steady_clock::now().time_since_epoch().count());

9f9 template<typename T> struct ETT {
    // treap
3c9     struct node {
ed1         node *l, *r, *p;
fa4         int pr, sz;
875         T val, sub, lazy;
53e         int id;
ffd         bool f; // se eh o 'first'
5ef         int qt_f; // numero de firsts na subarvore
7a8         node(int id_, T v, bool f_ = 0) : l(NULL), r(NULL),
p(NULL), pr(rng()),
62b             sz(1), val(v), sub(v), lazy(), id(id_), f(f_),
qt_f(f_) {}
a9c         void prop() {
d09             if (lazy != T()) {
021                 if (f) val += lazy;
971                 sub += lazy*sz;
b87                 if (l) l->lazy += lazy;
d3b                 if (r) r->lazy += lazy;
cbb             }
bfd             lazy = T();
cbb         }
01e         void update() {
8da             sz = 1, sub = val, qt_f = f;
171             if (l) l->prop(), sz += l->sz, sub += l->sub, qt_f
+= l->qt_f;
117             if (r) r->prop(), sz += r->sz, sub += r->sub, qt_f
+= r->qt_f;
cbb         }
214     };

bb7     node* root;

73c     int size(node* x) { return x ? x->sz : 0; }
bcf     void join(node* l, node* r, node*& i) { // assume que l < r
986         if (!l or !r) return void(i = l ? l : r);

```

```

161     l->prop(), r->prop();
ff5     if (l->pr > r->pr) join(l->r, r, l->r), l->r->p = i = l;
982     else join(l, r->l, r->l), r->l->p = i = r;
bda     i->update();
cbb }
a20 void split(node* i, node*& l, node*& r, int v, int key = 0)
{
26a     if (!i) return void(r = l = NULL);
c89     i->prop();
d9e     if (key + size(i->l) < v) {
448         split(i->r, i->r, r, v, key+size(i->l)+1), l = i;
a21         if (r) r->p = NULL;
6e8         if (i->r) i->r->p = i;
9d9     } else {
98d         split(i->l, l, i->l, v, key), r = i;
5a3         if (l) l->p = NULL;
899         if (i->l) i->l->p = i;
cbb     }
bda     i->update();
cbb }
ac7 int get_idx(node* i) {
6cf     int ret = size(i->l);
482     for (; i->p; i = i->p) {
fbf         node* pai = i->p;
8a6         if (i != pai->l) ret += size(pai->l) + 1;
cbb     }
edf     return ret;
cbb }
048 node* get_min(node* i) {
433     if (!i) return NULL;
f8e     return i->l ? get_min(i->l) : i;
cbb }
f03 node* get_max(node* i) {
433     if (!i) return NULL;
424     return i->r ? get_max(i->r) : i;
cbb }
// fim da treap

4fb     vector<node*> first, last;

f82     ETT(int n, vector<T> v = {}) : root(NULL), first(n),
last(n) {
c5e         if (!v.size()) v = vector<T>(n);
603         for (int i = 0; i < n; i++) {
a00             first[i] = last[i] = new node(i, v[i], 1);
469             join(root, first[i], root);

```

```

cbb     }
cbb }
83f ETT(const ETT& t) { throw logic_error("Nao copiar a ETT!");
}

c09 ~ETT() {
609     vector<node*> q = {root};
402     while (q.size()) {
e5d         node* x = q.back(); q.pop_back();
ee9         if (!x) continue;
1c7         q.push_back(x->l), q.push_back(x->r);
bf0         delete x;
cbb     }
cbb }

153 pair<int, int> get_range(int i) {
670     return {get_idx(first[i]), get_idx(last[i])};
cbb }
7af void link(int v, int u) { // 'v' tem que ser raiz
890     auto [lv, rv] = get_range(v);
f13     int ru = get_idx(last[u]);

4b4     node* V;
df9     node *L, *M, *R;
117     split(root, M, R, rv+1), split(M, L, M, lv);
f1e     V = M;
a28     join(L, R, root);

e66     split(root, L, R, ru+1);
367     join(L, V, L);
7e8     join(L, last[u] = new node(u, T() /* elemento neutro
*/, L);
a28     join(L, R, root);
cbb }
4e6 void cut(int v) {
892     auto [l, r] = get_range(v);

df9     node *L, *M, *R;
dca     split(root, M, R, r+1), split(M, L, M, l);
de6     node *LL = get_max(L), *RR = get_min(R);
710     if (LL and RR and LL->id == RR->id) { // remove
duplicata
e8b         if (last[RR->id] == RR) last[RR->id] = LL;
992         node *A, *B;
6b3         split(R, A, B, 1);
10c         delete A;
9d5         R = B;

```

```

cbb      }
a28      join(L, R, root);
a0d      join(root, M, root);
cbb    }
808    T query(int v) {
892      auto [l, r] = get_range(v);
df9      node *L, *M, *R;
dca      split(root, M, R, r+1), split(M, L, M, l);
d43      T ans = M->sub;
69d      join(L, M, M), join(M, R, root);
ba7      return ans;
cbb    }
93b    void update(int v, T val) { // soma val em todo mundo da
subarvore
892      auto [l, r] = get_range(v);
df9      node *L, *M, *R;
dca      split(root, M, R, r+1), split(M, L, M, l);
409      M->lazy += val;
69d      join(L, M, M), join(M, R, root);
cbb    }
129    void update_v(int v, T val) { // muda o valor de v pra val
ac1      int l = get_idx(first[v]);
df9      node *L, *M, *R;
d0c      split(root, M, R, l+1), split(M, L, M, l);
25e      M->val = M->sub = val;
69d      join(L, M, M), join(M, R, root);
cbb    }
934    bool is_in_subtree(int v, int u) { // se u ta na subtree de
v
890      auto [lv, rv] = get_range(v);
6ec      auto [lu, ru] = get_range(u);
732      return lv <= lu and ru <= rv;
cbb    }

355    void print(node* i) {
eae      if (!i) return;
a1e      print(i->l);
743      cout << i->id+1 << " ";
f15      print(i->r);
cbb    }
065    void print() { print(root); cout << endl; }
214 };

```

## 2.14 Floyd-Warshall

```

// encontra o menor caminho entre todo
// par de vertices e detecta ciclo negativo
// retorna 1 sse ha ciclo negativo
// d[i][i] deve ser 0
// para i != j, d[i][j] deve ser w se ha uma aresta
// (i, j) de peso w, INF caso contrario
//
// O(n^3)
// ea05be

1a8 int n;
ae5 int d[MAX][MAX];

73c bool floyd_warshall() {
e22   for (int k = 0; k < n; k++)
830   for (int i = 0; i < n; i++)
f90   for (int j = 0; j < n; j++)
0ab     d[i][j] = min(d[i][j], d[i][k] + d[k][j]);

830   for (int i = 0; i < n; i++)
753     if (d[i][i] < 0) return 1;

bb3   return 0;
cbb }

```

## 2.15 Functional Graph

```

// rt[i] fala o ID da raiz associada ao vertice i
// d[i] fala a profundidade (0 sse ta no ciclo)
// pos[i] fala a posicao de i no array que eh a concat. dos ciclos
// build(f, val) recebe a funcao f e o custo de ir de
// i para f[i] (por default, val = f)
// f_k(i, k) fala onde i vai parar se seguir k arestas
// path(i, k) fala o custo (soma) seguir k arestas a partir de i
// Se quiser outra operacao, da pra alterar facil o codigo
//Codigo um pouco louco, tenho que admitir
//
// build - O(n)
// f_k    - O(log(min(n, k)))
// path   - O(log(min(n, k)))
// 51fabe

6ef namespace func_graph {
1a8   int n;

```



```

ce2     int f[MAX], vis[MAX], d[MAX];
f82     int p[MAX], pp[MAX], rt[MAX], pos[MAX];
ebd     int sz[MAX], comp;
6a9     vector<vector<int>> ciclo;
405     ll val[MAX], jmp[MAX], seg[2*MAX];

97c     ll op(ll a, ll b) { return a+b; }; // mudar a operacao aqui
27b     void dfs(int i, int t = 2) {
9c9         vis[i] = t;
f09         if (vis[f[i]] >= 2) { // começa ciclo - f[i] eh o rep.
e0a             d[i] = 0, rt[i] = comp;
74c             sz[comp] = t - vis[f[i]] + 1;
97b             p[i] = pp[i] = i, jmp[i] = val[i];
15c             ciclo.emplace_back();
bfb             ciclo.back().push_back(i);
9d9         } else {
c16             if (!vis[f[i]]) dfs(f[i], t+1);
8c0             rt[i] = rt[f[i]];
195             if (sz[comp]+1) { // to no ciclo
d0f                 d[i] = 0;
97b                 p[i] = pp[i] = i, jmp[i] = val[i];
bfb                 ciclo.back().push_back(i);
9d9             } else { // nao to no ciclo
00d                 d[i] = d[f[i]]+1, p[i] = f[i];
511                 pp[i] = 2*d[pp[f[i]]] ==
d[pp[pp[f[i]]]]+d[f[i]] ? pp[pp[f[i]]] : f[i];
114                 jmp[i] = pp[i] == f[i] ? val[i] : op(val[i],
op(jmp[f[i]], jmp[pp[f[i]]]));
cbb             }
cbb         }
e4a         if (f[ciclo[rt[i]][0]] == i) comp++; // fim do ciclo
29a         vis[i] = 1;
cbb     }
1da     void build(vector<int> f_, vector<int> val_ = {}) {
bcb         n = f_.size(), comp = 0;
527         if (!val_.size()) val_ = f_;
830         for (int i = 0; i < n; i++)
998             f[i] = f_[i], val[i] = val_[i], vis[i] = 0, sz[i] =
-1;

e74     ciclo.clear();
158     for (int i = 0; i < n; i++) if (!vis[i]) dfs(i);
6bb     int t = 0;
daa     for (auto& c : ciclo) {
336         reverse(c.begin(), c.end());
ea5         for (int j : c) {

```

```

85b             pos[j] = t;
948             seg[n+t] = val[j];
c82             t++;
cbb         }
cbb     }
dc1     for (int i = n-1; i; i--) seg[i] = op(seg[2*i],
seg[2*i+1]);
cbb     }

283     int f_k(int i, ll k) {
1b1         while (d[i] and k) {
77b             int big = d[i] - d[pp[i]];
ded             if (big <= k) k -= big, i = pp[i];
584             else k--, i = p[i];
cbb         }
77e         if (!k) return i;
a19         return ciclo[rt[i]][(pos[i] - pos[ciclo[rt[i]][0]] + k)
% sz[rt[i]]];
cbb     }
047     ll path(int i, ll k) {
3cf         auto query = [&](int l, int r) {
3e4             ll q = 0;
47a             for (l += n, r += n; l <= r; ++l/=2, --r/=2) {
27e                 if (l%2 == 1) q = op(q, seg[l]);
1f2                 if (r%2 == 0) q = op(q, seg[r]);
cbb             }
bef             return q;
214         };
b73         ll ret = 0;
1b1         while (d[i] and k) {
77b             int big = d[i] - d[pp[i]];
327             if (big <= k) k -= big, ret = op(ret, jmp[i]), i =
pp[i];
f9e             else k--, ret = op(ret, val[i]), i = p[i];
cbb         }
e3c         if (!k) return ret;
a9e         int first = pos[ciclo[rt[i]][0]], last =
pos[ciclo[rt[i]].back()];

// k/sz[rt[i]] voltas completas
430         if (k/sz[rt[i]]) ret = op(ret, k/sz[rt[i]] *
query(first, last));

9af         k %= sz[rt[i]];
e3c         if (!k) return ret;
8ea         int l = pos[i], r = first + (pos[i] - first + k - 1) %

```

```

        sz[rt[i]];
982         if (l <= r) return op(ret, query(l, r));
687         return op(ret, op(query(l, last), query(first, r)));
cbb     }
cbb }

```

## 2.16 Heavy-Light Decomposition - aresta

```

// SegTree de soma
// query / update de soma das arestas
//
// Complexidades:
// build - O(n)
// query_path - O(log^2 (n))
// update_path - O(log^2 (n))
// query_subtree - O(log(n))
// update_subtree - O(log(n))

// namespace seg { ... }

// 599946
826 namespace hld {
c0d     vector<pair<int, int> > g[MAX];
e65     int pos[MAX], sz[MAX];
7c0     int sobe[MAX], pai[MAX];
096     int h[MAX], v[MAX], t;

0ce     void build_hld(int k, int p = -1, int f = 1) {
180         v[pos[k] = t++] = sobe[k]; sz[k] = 1;
418         for (auto& i : g[k]) if (i.first != p) {
dd2             auto [u, w] = i;
a76             sobe[u] = w; pai[u] = k;
0c1             h[u] = (i == g[k][0] ? h[k] : u);
da7             build_hld(u, k, f); sz[k] += sz[u];

865             if (sz[u] > sz[g[k][0].first] or g[k][0].first == p)
9a3                 swap(i, g[k][0]);
cbb         }
667         if (p*f == -1) build_hld(h[k] = k, -1, t = 0);
cbb     }
1f8     void build(int root = 0) {
a34         t = 0;
295         build_hld(root);
c83         seg::build(t, v);

```

```

cbb     }
3fc     ll query_path(int a, int b) {
2d5         if (a == b) return 0;
aa1         if (pos[a] < pos[b]) swap(a, b);

29b         if (h[a] == h[b]) return seg::query(pos[b]+1, pos[a]);
fca         return seg::query(pos[h[a]], pos[a]) +
            query_path(pai[h[a]], b);
cbb     }
920     void update_path(int a, int b, int x) {
d54         if (a == b) return;
aa1         if (pos[a] < pos[b]) swap(a, b);

881         if (h[a] == h[b]) return (void)seg::update(pos[b]+1,
pos[a], x);
701         seg::update(pos[h[a]], pos[a], x);
            update_path(pai[h[a]], b, x);
cbb     }
d0a     ll query_subtree(int a) {
b9f         if (sz[a] == 1) return 0;
2f6         return seg::query(pos[a]+1, pos[a]+sz[a]-1);
cbb     }
acc     void update_subtree(int a, int x) {
a5a         if (sz[a] == 1) return;
9cd         seg::update(pos[a]+1, pos[a]+sz[a]-1, x);
cbb     }
7be     int lca(int a, int b) {
aa1         if (pos[a] < pos[b]) swap(a, b);
ca5         return h[a] == h[b] ? b : lca(pai[h[a]], b);
cbb     }
cbb }

```

## 2.17 Heavy-Light Decomposition - vertice

```

// SegTree de soma
// query / update de soma dos vertices
//
// Complexidades:
// build - O(n)
// query_path - O(log^2 (n))
// update_path - O(log^2 (n))
// query_subtree - O(log(n))
// update_subtree - O(log(n))

```

```

// namespace seg { ... }

// de3d84
826 namespace hld {
042     vector<int> g[MAX];
e65     int pos[MAX], sz[MAX];
bd4     int peso[MAX], pai[MAX];
096     int h[MAX], v[MAX], t;

0ce     void build_hld(int k, int p = -1, int f = 1) {
b18         v[pos[k] = t++] = peso[k]; sz[k] = 1;
b94         for (auto& i : g[k]) if (i != p) {
78d             pai[i] = k;
26e             h[i] = (i == g[k][0] ? h[k] : i);
193             build_hld(i, k, f); sz[k] += sz[i];

cd1             if (sz[i] > sz[g[k][0]] or g[k][0] == p) swap(i,
g[k][0]);
cbb         }
667         if (p*f == -1) build_hld(h[k] = k, -1, t = 0);
cbb     }
1f8     void build(int root = 0) {
a34         t = 0;
295         build_hld(root);
c83         seg::build(t, v);
cbb     }
3fc     ll query_path(int a, int b) {
aa1         if (pos[a] < pos[b]) swap(a, b);

4bf         if (h[a] == h[b]) return seg::query(pos[b], pos[a]);
fca         return seg::query(pos[h[a]], pos[a]) +
query_path(pai[h[a]], b);
cbb     }
920     void update_path(int a, int b, int x) {
aa1         if (pos[a] < pos[b]) swap(a, b);

198         if (h[a] == h[b]) return (void)seg::update(pos[b],
pos[a], x);
701         seg::update(pos[h[a]], pos[a], x);
update_path(pai[h[a]], b, x);
cbb     }
d0a     ll query_subtree(int a) {
b3e         return seg::query(pos[a], pos[a]+sz[a]-1);
cbb     }
acc     void update_subtree(int a, int x) {
a22         seg::update(pos[a], pos[a]+sz[a]-1, x);

```

```

cbb     }
7be     int lca(int a, int b) {
aa1         if (pos[a] < pos[b]) swap(a, b);
ca5         return h[a] == h[b] ? b : lca(pai[h[a]], b);
cbb     }
cbb }

```

## 2.18 Heavy-Light Decomposition sem Update

```

// query de min do caminho
//
// Complexidades:
// build - O(n)
// query_path - O(log(n))
// ee6991

```

```

826 namespace hld {
c0d     vector<pair<int, int> > g[MAX];
e65     int pos[MAX], sz[MAX];
7c0     int sobe[MAX], pai[MAX];
096     int h[MAX], v[MAX], t;
ea2     int men[MAX], seg[2*MAX];

0ce     void build_hld(int k, int p = -1, int f = 1) {
180         v[pos[k] = t++] = sobe[k]; sz[k] = 1;
418         for (auto& i : g[k]) if (i.first != p) {
1f5             sobe[i.first] = i.second; pai[i.first] = k;
6fa             h[i.first] = (i == g[k][0] ? h[k] : i.first);
87b             men[i.first] = (i == g[k][0] ? min(men[k],
i.second) : i.second);
4b2             build_hld(i.first, k, f); sz[k] += sz[i.first];

bc3             if (sz[i.first] > sz[g[k][0].first] or
g[k][0].first == p)
9a3                 swap(i, g[k][0]);
cbb             }
667         if (p*f == -1) build_hld(h[k] = k, -1, t = 0);
cbb     }
1f8     void build(int root = 0) {
a34         t = 0;
295         build_hld(root);
3ae         for (int i = 0; i < t; i++) seg[i+t] = v[i];
8db         for (int i = t-1; i; i--) seg[i] = min(seg[2*i],
seg[2*i+1]);

```

```

cbb    }
f04    int query_path(int a, int b) {
490        if (a == b) return INF;
aal        if (pos[a] < pos[b]) swap(a, b);

98f        if (h[a] != h[b]) return min(men[a],
query_path(pai[h[a]], b));
46b        int ans = INF, x = pos[b]+1+t, y = pos[a]+t;
646        for (; x <= y; ++x/=2, --y/=2) ans = min({ans, seg[x],
seg[y]});
ba7        return ans;
cbb    }
214 };

```

## 2.19 Isomorfismo de arvores

```

// thash() retorna o hash da arvore (usando centroids como vertices
// especiais).
// Duas arvores sao isomorfas sse seu hash eh o mesmo
//
// 0(|V|.log(|V|))
// 8fb6bb

```

```

91f map<vector<int>, int> mphash;

```

```

df6 struct tree {
1a8     int n;
789     vector<vector<int>> g;
347     vector<int> sz, cs;

1b5     tree(int n_) : n(n_), g(n_), sz(n_) {}

76b     void dfs_centroid(int v, int p) {
588         sz[v] = 1;
fa7         bool cent = true;
18e         for (int u : g[v]) if (u != p) {
365             dfs_centroid(u, v), sz[v] += sz[u];
e90             if(sz[u] > n/2) cent = false;
cbb         }
1f6         if (cent and n - sz[v] <= n/2) cs.push_back(v);
cbb     }

784     int fhash(int v, int p) {
544         vector<int> h;
332         for (int u : g[v]) if (u != p) h.push_back(fhash(u, v));

```

```

1c9         sort(h.begin(), h.end());
3ac         if (!mphash.count(h)) mphash[h] = mphash.size();
bbc         return mphash[h];
cbb     }
38f     ll thash() {
23a         cs.clear();
3a5         dfs_centroid(0, -1);
16d         if (cs.size() == 1) return fhash(cs[0], -1);
772         ll h1 = fhash(cs[0], cs[1]), h2 = fhash(cs[1], cs[0]);
fae         return (min(h1, h2) << 30) + max(h1, h2);
cbb     }
214 };

```

## 2.20 Kosaraju

```

// 0(n + m)
// a4f310

```

```

1a8 int n;
042 vector<int> g[MAX];
58d vector<int> gi[MAX]; // grafo invertido
c5a int vis[MAX];
ee6 stack<int> S;
a52 int comp[MAX]; // componente conexo de cada vertice

```

```

1ca void dfs(int k) {
59a     vis[k] = 1;
54f     for (int i = 0; i < (int) g[k].size(); i++)
8d5         if (!vis[g[k][i]]) dfs(g[k][i]);

58f     S.push(k);
cbb }

```

```

436 void scc(int k, int c) {
59a     vis[k] = 1;
52c     comp[k] = c;
ff0     for (int i = 0; i < (int) gi[k].size(); i++)
bf6         if (!vis[gi[k][i]]) scc(gi[k][i], c);
cbb }

```

```

db8 void kosaraju() {
991     for (int i = 0; i < n; i++) vis[i] = 0;
158     for (int i = 0; i < n; i++) if (!vis[i]) dfs(i);

```

```

991     for (int i = 0; i < n; i++) vis[i] = 0;
d32     while (S.size()) {
70b         int u = S.top();
7de         S.pop();
f43         if (!vis[u]) scc(u, u);
cbb     }
cbb }

```

## 2.21 Kruskal

```

// Gera e retorna uma AGM e seu custo total a partir do vetor de
// arestas (edg)
// do grafo
//
// O(m log(m) + m a(m))
// 864875

1b9 vector<tuple<int, int, int>> edg; // {peso,[x,y]}

// DSU em O(a(n))
4a6 void dsu_build();
d78 int find(int a);
369 void unite(int a, int b);

c67 pair<ll, vector<tuple<int, int, int>>> kruskal(int n) {
8d2     dsu_build(n);
e31     sort(edg.begin(), edg.end());

854     ll cost = 0;
979     vector<tuple<int, int, int>> mst;
fea     for (auto [w,x,y] : edg) if (find(x) != find(y)) {
9de         mst.emplace_back(w, x, y);
45f         cost += w;
05a         unite(x,y);
cbb     }
5df     return {cost, mst};
cbb }

```

## 2.22 Kuhn

```

// Computa matching maximo em grafo bipartido
// 'n' e 'm' sao quantos vertices tem em cada particao

```

```

// chamar add(i, j) para add aresta entre o cara i
// da particao A, e o cara j da particao B
// (entao i < n, j < m)
// Para recuperar o matching, basta olhar 'ma' e 'mb'
// 'recover' recupera o min vertex cover como um par de
// {caras da particao A, caras da particao B}
//
// O(|V| * |E|)
// Na pratica, parece rodar tao rapido quanto o Dinic

878 mt19937 rng((int)
    chrono::steady_clock::now().time_since_epoch().count());

// b0dda3
6c6 struct kuhn {
14e     int n, m;
789     vector<vector<int>>> g;
d3f     vector<int> vis, ma, mb;

40e     kuhn(int n_, int m_) : n(n_), m(m_), g(n),
8af         vis(n+m), ma(n, -1), mb(m, -1) {}

ba6     void add(int a, int b) { g[a].push_back(b); }

caf     bool dfs(int i) {
29a         vis[i] = 1;
29b         for (int j : g[i]) if (!vis[n+j]) {
8c9             vis[n+j] = 1;
2cf             if (mb[j] == -1 or dfs(mb[j])) {
bfe                 ma[i] = j, mb[j] = i;
8a6                 return true;
cbb             }
cbb         }
d1f         return false;
cbb     }

bf7     int matching() {
1ae         int ret = 0, aum = 1;
5a8         for (auto& i : g) shuffle(i.begin(), i.end(), rng);
392         while (aum) {
618             for (int j = 0; j < m; j++) vis[n+j] = 0;
c5d             aum = 0;
830             for (int i = 0; i < n; i++)
01f                 if (ma[i] == -1 and dfs(i)) ret++, aum = 1;
cbb             }
edf         return ret;
cbb     }

```

```

214 };

// 55fb67
ebf pair<vector<int>, vector<int>> recover(kuhn& K) {
e80     K.matching();
50c     int n = K.n, m = K.m;
9d0     for (int i = 0; i < n+m; i++) K.vis[i] = 0;
bde     for (int i = 0; i < n; i++) if (K.ma[i] == -1) K.dfs(i);
8ad     vector<int> ca, cb;
576     for (int i = 0; i < n; i++) if (!K.vis[i]) ca.push_back(i);
f24     for (int i = 0; i < m; i++) if (K.vis[n+i]) cb.push_back(i);
aad     return {ca, cb};
cbb }

```

## 2.23 LCA com binary lifting

```

// Assume que um vertice eh ancestral dele mesmo, ou seja,
// se a eh ancestral de b, lca(a, b) = a
// MAX2 = ceil(log(MAX))
//
// Complexidades:
// build - O(n log(n))
// lca - O(log(n))
// b674ca

```

```

677 vector<vector<int> > g(MAX);
41c int n, p;
e75 int pai[MAX2][MAX];
999 int in[MAX], out[MAX];

```

```

1ca void dfs(int k) {
fdf     in[k] = p++;
54f     for (int i = 0; i < (int) g[k].size(); i++)
9b7         if (in[g[k][i]] == -1) {
ba6             pai[0][g[k][i]] = k;
c38             dfs(g[k][i]);
cbb         }
26f     out[k] = p++;
cbb }

```

```

c11 void build(int raiz) {
a67     for (int i = 0; i < n; i++) pai[0][i] = i;
c63     p = 0, memset(in, -1, sizeof in);
ecb     dfs(raiz);

```

```

// pd dos pais
511     for (int k = 1; k < MAX2; k++) for (int i = 0; i < n; i++)
d38         pai[k][i] = pai[k - 1][pai[k - 1][i]];
cbb }

```

```

00f bool anc(int a, int b) { // se a eh ancestral de b
bfe     return in[a] <= in[b] and out[a] >= out[b];
cbb }

```

```

7be int lca(int a, int b) {
86d     if (anc(a, b)) return a;
e52     if (anc(b, a)) return b;

```

```

// sobe a
f70     for (int k = MAX2 - 1; k >= 0; k--)
acf         if (!anc(pai[k][a], b)) a = pai[k][a];

```

```

847     return pai[0][a];
cbb }

```

```

// Alternativamente:
// 'binary lifting' gastando O(n) de memoria
// Da pra add folhas e fazer queries online
// 3 vezes o tempo do binary lifting normal
//
// build - O(n)
// kth, lca, dist - O(log(n))
// 89a97a

```

```

9c6 int d[MAX], p[MAX], pp[MAX];

```

```

d40 void set_root(int i) { p[i] = pp[i] = i, d[i] = 0; }

```

```

e9d void add_leaf(int i, int u) {
e0b     p[i] = u, d[i] = d[u]+1;
b15     pp[i] = 2*d[pp[u]] == d[pp[pp[u]]]+d[u] ? pp[pp[u]] : u;
cbb }

```

```

c37 int kth(int i, int k) {
4e3     int dd = max(0, d[i]-k);
935     while (d[i] > dd) i = d[pp[i]] >= dd ? pp[i] : p[i];
d9a     return i;
cbb }

```

```

7be int lca(int a, int b) {

```

```

a69     if (d[a] < d[b]) swap(a, b);
6cd     while (d[a] > d[b]) a = d[pp[a]] >= d[b] ? pp[a] : p[a];
984     while (a != b) {
932         if (pp[a] != pp[b]) a = pp[a], b = pp[b];
e7c         else a = p[a], b = p[b];
cbb     }
3f5     return a;
cbb }

4fe int dist(int a, int b) { return d[a]+d[b]-2*d[lca(a,b)]; }

042 vector<int> g[MAX];

3ab void build(int i, int pai=-1) {
5cf     if (pai == -1) set_root(i);
15f     for (int j : g[i]) if (j != pai) {
d31         add_leaf(j, i);
b21         build(j, i);
cbb     }
cbb }

```

## 2.24 LCA com HLD

```

// Assume que um vertice eh ancestral dele mesmo, ou seja,
// se a eh ancestral de b, lca(a, b) = a
// Para construir pasta chamar build(root)
// anc(a, b) responde se 'a' eh ancestral de 'b'
//
// Complexidades:
// build - O(n)
// lca - O(log(n))
// anc - O(1)
// fb22c1

```

```

042 vector<int> g[MAX];
713 int pos[MAX], h[MAX], sz[MAX];
ff1 int pai[MAX], t;

8bf void build(int k, int p = -1, int f = 1) {
bce     pos[k] = t++; sz[k] = 1;
e26     for (int& i : g[k]) if (i != p) {
78d         pai[i] = k;
26e         h[i] = (i == g[k][0] ? h[k] : i);
cb8         build(i, k, f); sz[k] += sz[i];

```

```

cd1         if (sz[i] > sz[g[k][0]] or g[k][0] == p) swap(i,
g[k][0]);
cbb     }
3da     if (p*f == -1) t = 0, h[k] = k, build(k, -1, 0);
cbb }

7be int lca(int a, int b) {
aa1     if (pos[a] < pos[b]) swap(a, b);
ca5     return h[a] == h[b] ? b : lca(pai[h[a]], b);
cbb }

00f bool anc(int a, int b) {
db5     return pos[a] <= pos[b] and pos[b] <= pos[a]+sz[a]-1;
cbb }

```

## 2.25 LCA com RMQ

```

// Assume que um vertice eh ancestral dele mesmo, ou seja,
// se a eh ancestral de b, lca(a, b) = a
// dist(a, b) retorna a distancia entre a e b
//
// Complexidades:
// build - O(n)
// lca - O(1)
// dist - O(1)
// 22cde8 - rmq + lca

// 0214e8
1a5 template<typename T> struct rmq {
517     vector<T> v;
fcc     int n; static const int b = 30;
70e     vector<int> mask, t;

18e     int op(int x, int y) { return v[x] < v[y] ? x : y; }
ee1     int msb(int x) { return __builtin_clz(1)-__builtin_clz(x); }
6ad     rmq() {}
43c     rmq(const vector<T>& v_) : v(v_), n(v.size()), mask(n),
t(n) {
2e5         for (int i = 0, at = 0; i < n; mask[i++] = at |= 1) {
a61             at = (at<<1)&((1<<b)-1);
76a             while (at and op(i, i-msb(at&-at)) == i) at ^=
at&-at;
cbb         }

```

```

243         for (int i = 0; i < n/b; i++) t[i] =
b*i+b-1-msb(mask[b*i+b-1]);
39d         for (int j = 1; (1<<j) <= n/b; j++) for (int i = 0;
i+(1<<j) <= n/b; i++)
ba5             t[n/b*j+i] = op(t[n/b*(j-1)+i],
t[n/b*(j-1)+i+(1<<(j-1))]);
cbb     }
c92     int small(int r, int sz = b) { return
r-msb(mask[r]&((1<<sz)-1)); }
b7a     T query(int l, int r) {
27b         if (r-l+1 <= b) return small(r, r-l+1);
7bf         int ans = op(small(l+b-1), small(r));
e80         int x = l/b+1, y = r/b-1;
e25         if (x <= y) {
a4e             int j = msb(y-x+1);
002             ans = op(ans, op(t[n/b*j+x], t[n/b*j+y-(1<<j)+1]));
cbb         }
ba7         return ans;
cbb     }
214 };

// 645120
065 namespace lca {
042     vector<int> g[MAX];
8ec     int v[2*MAX], pos[MAX], dep[2*MAX];
8bd     int t;
2de     rmq<int> RMQ;

4cf     void dfs(int i, int d = 0, int p = -1) {
c97         v[t] = i, pos[i] = t, dep[t++] = d;
cac         for (int j : g[i]) if (j != p) {
8ec             dfs(j, d+1, i);
cf2             v[t] = i, dep[t++] = d;
cbb         }
cbb     }
789     void build(int n, int root) {
a34         t = 0;
14e         dfs(root);
3f4         RMQ = rmq<int>(vector<int>(dep, dep+2*n-1));
cbb     }
7be     int lca(int a, int b) {
ab7         a = pos[a], b = pos[b];
9c0         return v[RMQ.query(min(a, b), max(a, b))];
cbb     }
b5d     int dist(int a, int b) {
670         return dep[pos[a]] + dep[pos[b]] - 2*dep[pos[lca(a,

```

```

b)]];
cbb     }
cbb }

```

## 2.26 Line Tree

```

// Reduz min-query em arvore para RMQ
// Se o grafo nao for uma arvore, as queries
// sao sobre a arvore geradora maxima
// Queries de minimo
//
// build - O(n log(n))
// query - O(log(n))
// b1f418

1a8 int n;

3ae namespace linetree {
f37     int id[MAX], seg[2*MAX], pos[MAX];
43f     vector<int> v[MAX], val[MAX];
430     vector<pair<int, pair<int, int> > > ar;

dc6     void add(int a, int b, int p) { ar.push_back({p, {a, b}}); }
0a8     void build() {
b09         sort(ar.rbegin(), ar.rend());
0e3         for (int i = 0; i < n; i++) id[i] = i, v[i] = {i},
val[i].clear();
8bb         for (auto i : ar) {
c91             int a = id[i.second.first], b = id[i.second.second];
f6f             if (a == b) continue;
c58             if (v[a].size() < v[b].size()) swap(a, b);
fb8             for (auto j : v[b]) id[j] = a, v[a].push_back(j);
482             val[a].push_back(i.first);
78b             for (auto j : val[b]) val[a].push_back(j);
e39             v[b].clear(), val[b].clear();
cbb         }
8e8         vector<int> vv;
2ce         for (int i = 0; i < n; i++) for (int j = 0; j <
v[i].size(); j++) {
e52             pos[v[i][j]] = vv.size();
941             if (j + 1 < v[i].size()) vv.push_back(val[i][j]);
1cb             else vv.push_back(0);
cbb         }
bb4         for (int i = n; i < 2*n; i++) seg[i] = vv[i-n];

```



```

69e         for (int i = n-1; i; i--) seg[i] = min(seg[2*i],
seg[2*i+1]);
cbb     }
4ea     int query(int a, int b) {
596         if (id[a] != id[b]) return 0; // nao estao conectados
ab7         a = pos[a], b = pos[b];
d11         if (a > b) swap(a, b);
199         b--;
38a         int ans = INF;
513         for (a += n, b += n; a <= b; ++a/=2, --b/=2) ans =
min({ans, seg[a], seg[b]});
ba7         return ans;
cbb     }
214 };

```

## 2.27 Link-cut Tree

```

// Link-cut tree padrao
//
// Todas as operacoes sao O(log(n)) amortizado
// e4e663

1ef namespace lct {
3c9     struct node {
19f         int p, ch[2];
062         node() { p = ch[0] = ch[1] = -1; }
214     };

5f3     node t[MAX];

971     bool is_root(int x) {
657         return t[x].p == -1 or (t[t[x].p].ch[0] != x and
t[t[x].p].ch[1] != x);
cbb     }
ed6     void rotate(int x) {
497         int p = t[x].p, pp = t[p].p;
fc4         if (!is_root(p)) t[pp].ch[t[pp].ch[1] == p] = x;
251         bool d = t[p].ch[0] == x;
461         t[p].ch[!d] = t[x].ch[d], t[x].ch[d] = p;
a76         if (t[p].ch[!d]+1) t[t[p].ch[!d]].p = p;
8fa         t[x].p = pp, t[p].p = x;
cbb     }
07c     void splay(int x) {
18c         while (!is_root(x)) {

```

```

497         int p = t[x].p, pp = t[p].p;
0c5         if (!is_root(p)) rotate((t[pp].ch[0] ==
p)^(t[p].ch[0] == x) ? x : p);
64f         rotate(x);
cbb     }
cbb     }
f16     int access(int v) {
0eb         int last = -1;
01a         for (int w = v; w+1; last = w, splay(v), w = t[v].p)
024             splay(w), t[w].ch[1] = (last == -1 ? -1 : v);
3d3         return last;
cbb     }
e89     int find_root(int v) {
5e3         access(v);
3de         while (t[v].ch[0]+1) v = t[v].ch[0];
f05         return splay(v), v;
cbb     }
142     void link(int v, int w) { // v deve ser raiz
5e3         access(v);
10d         t[v].p = w;
cbb     }
4e6     void cut(int v) { // remove aresta de v pro pai
5e3         access(v);
264         t[v].ch[0] = t[t[v].ch[0]].p = -1;
cbb     }
bbb     int lca(int v, int w) {
948         return access(v), access(w);
cbb     }
cbb }

```

## 2.28 Link-cut Tree - aresta

```

// Valores nas arestas
// rootify(v) torna v a raiz de sua arvore
// query(v, w) retorna a soma do caminho v--w
// update(v, w, x) soma x nas arestas do caminho v--w
//
// Todas as operacoes sao O(log(n)) amortizado
// 9ce48f

1ef namespace lct {
3c9     struct node {
19f         int p, ch[2];
810         ll val, sub;

```

```

aa6      bool rev;
04a      int sz, ar;
4e4      ll lazy;
f93      node() {}
7a8      node(int v, int ar_) :
546      p(-1), val(v), sub(v), rev(0), sz(ar_), ar(ar_),
      lazy(0) {
b07          ch[0] = ch[1] = -1;
cbb      }
214      };

c53      node t[2*MAX]; // MAXN + MAXQ
99e      map<pair<int, int>, int> aresta;
e4d      int sz;

95a      void prop(int x) {
dc1          if (t[x].lazy) {
25e              if (t[x].ar) t[x].val += t[x].lazy;
2ab              t[x].sub += t[x].lazy*t[x].sz;
edc              if (t[x].ch[0]+1) t[t[x].ch[0]].lazy += t[x].lazy;
942              if (t[x].ch[1]+1) t[t[x].ch[1]].lazy += t[x].lazy;
cbb          }
aa2          if (t[x].rev) {
f95              swap(t[x].ch[0], t[x].ch[1]);
379              if (t[x].ch[0]+1) t[t[x].ch[0]].rev ^= 1;
c3d              if (t[x].ch[1]+1) t[t[x].ch[1]].rev ^= 1;
cbb          }
230          t[x].lazy = 0, t[x].rev = 0;
cbb      }

564      void update(int x) {
1a3          t[x].sz = t[x].ar, t[x].sub = t[x].val;
8ca          for (int i = 0; i < 2; i++) if (t[x].ch[i]+1) {
621              prop(t[x].ch[i]);
c4f              t[x].sz += t[t[x].ch[i]].sz;
269              t[x].sub += t[t[x].ch[i]].sub;
cbb          }
cbb      }

971      bool is_root(int x) {
657          return t[x].p == -1 or (t[t[x].p].ch[0] != x and
t[t[x].p].ch[1] != x);
cbb      }

ed6      void rotate(int x) {
497          int p = t[x].p, pp = t[p].p;
fc4          if (!is_root(p)) t[pp].ch[t[pp].ch[1] == p] = x;
251          bool d = t[p].ch[0] == x;
461          t[p].ch[!d] = t[x].ch[d], t[x].ch[d] = p;

```

```

a76          if (t[p].ch[!d]+1) t[t[p].ch[!d]].p = p;
8fa          t[x].p = pp, t[p].p = x;
444          update(p), update(x);
cbb      }

238      int splay(int x) {
18c          while (!is_root(x)) {
497              int p = t[x].p, pp = t[p].p;
77b              if (!is_root(p)) prop(pp);
be5              prop(p), prop(x);
0c5              if (!is_root(p)) rotate((t[pp].ch[0] ==
p)^(t[p].ch[0] == x) ? x : p);
64f              rotate(x);
cbb          }
aab          return prop(x), x;
cbb      }

f16      int access(int v) {
0eb          int last = -1;
d9f          for (int w = v; w+1; update(last = w), splay(v), w =
t[v].p)
024              splay(w), t[w].ch[1] = (last == -1 ? -1 : v);
3d3              return last;
cbb          }

9f1      void make_tree(int v, int w=0, int ar=0) { t[v] = node(w,
ar); }

e89      int find_root(int v) {
13f          access(v), prop(v);
9f0          while (t[v].ch[0]+1) v = t[v].ch[0], prop(v);
637          return splay(v);
cbb      }

82f      bool conn(int v, int w) {
2cf          access(v), access(w);
b9b          return v == w ? true : t[v].p != -1;
cbb      }

277      void rootify(int v) {
5e3          access(v);
a02          t[v].rev ^= 1;
cbb      }

971      ll query(int v, int w) {
b54          rootify(w), access(v);
249          return t[v].sub;
cbb      }

3fa      void update(int v, int w, int x) {
b54          rootify(w), access(v);
12c          t[v].lazy += x;
cbb      }

204      void link_(int v, int w) {

```

```

821     rootify(w);
389     t[w].p = v;
cbb }
6b8 void link(int v, int w, int x) { // v--w com peso x
379     int id = MAX + sz++;
110     aresta[make_pair(v, w)] = id;
a88     make_tree(id, x, 1);
c88     link_(v, id), link_(id, w);
cbb }
e63 void cut_(int v, int w) {
b54     rootify(w), access(v);
264     t[v].ch[0] = t[t[v].ch[0]].p = -1;
cbb }
031 void cut(int v, int w) {
b0f     int id = aresta[make_pair(v, w)];
a4a     cut_(v, id), cut_(id, w);
cbb }
bbb int lca(int v, int w) {
5e3     access(v);
a8b     return access(w);
cbb }
cbb }

```

## 2.29 Link-cut Tree - vertice

```

// Valores nos vertices
// make_tree(v, w) cria uma nova arvore com um
// vertice soh com valor 'w'
// rootify(v) torna v a raiz de sua arvore
// query(v, w) retorna a soma do caminho v--w
// update(v, w, x) soma x nos vertices do caminho v--w
//
// Todas as operacoes sao O(log(n)) amortizado
// f9f489

```

```

1ef namespace lct {
3c9     struct node {
19f         int p, ch[2];
810         ll val, sub;
aa6         bool rev;
e4d         int sz;
4e4         ll lazy;
f93         node() {}

```

```

aa0         node(int v) : p(-1), val(v), sub(v), rev(0), sz(1),
lazy(0) {
b07             ch[0] = ch[1] = -1;
cbb         }
214     };

5f3     node t[MAX];

95a     void prop(int x) {
dc1         if (t[x].lazy) {
9f7             t[x].val += t[x].lazy, t[x].sub +=
t[x].lazy*t[x].sz;
edc             if (t[x].ch[0]+1) t[t[x].ch[0]].lazy += t[x].lazy;
942             if (t[x].ch[1]+1) t[t[x].ch[1]].lazy += t[x].lazy;
cbb         }
aa2         if (t[x].rev) {
f95             swap(t[x].ch[0], t[x].ch[1]);
379             if (t[x].ch[0]+1) t[t[x].ch[0]].rev ^= 1;
c3d             if (t[x].ch[1]+1) t[t[x].ch[1]].rev ^= 1;
cbb         }
230         t[x].lazy = 0, t[x].rev = 0;
cbb     }

564     void update(int x) {
ec2         t[x].sz = 1, t[x].sub = t[x].val;
8ca         for (int i = 0; i < 2; i++) if (t[x].ch[i]+1) {
621             prop(t[x].ch[i]);
c4f             t[x].sz += t[t[x].ch[i]].sz;
269             t[x].sub += t[t[x].ch[i]].sub;
cbb         }
cbb     }

971     bool is_root(int x) {
657         return t[x].p == -1 or (t[t[x].p].ch[0] != x and
t[t[x].p].ch[1] != x);
cbb     }

ed6     void rotate(int x) {
497         int p = t[x].p, pp = t[p].p;
fc4         if (!is_root(p)) t[pp].ch[t[pp].ch[1] == p] = x;
251         bool d = t[p].ch[0] == x;
461         t[p].ch[!d] = t[x].ch[d], t[x].ch[d] = p;
a76         if (t[p].ch[!d]+1) t[t[p].ch[!d]].p = p;
8fa         t[x].p = pp, t[p].p = x;
444         update(p), update(x);
cbb     }

238     int splay(int x) {
18c         while (!is_root(x)) {
497             int p = t[x].p, pp = t[p].p;

```

```

77b         if (!is_root(p)) prop(pp);
be5         prop(p), prop(x);
0c5         if (!is_root(p)) rotate((t[pp].ch[0] ==
p)^(t[p].ch[0] == x) ? x : p);
64f         rotate(x);
cbb     }
aab     return prop(x), x;
cbb }
f16 int access(int v) {
0eb     int last = -1;
d9f     for (int w = v; w+1; update(last = w), splay(v), w =
t[v].p)
024         splay(w), t[w].ch[1] = (last == -1 ? -1 : v);
3d3     return last;
cbb }
f17 void make_tree(int v, int w) { t[v] = node(w); }
e89 int find_root(int v) {
13f     access(v), prop(v);
9f0     while (t[v].ch[0]+1) v = t[v].ch[0], prop(v);
637     return splay(v);
cbb }
f94 bool connected(int v, int w) {
2cf     access(v), access(w);
b9b     return v == w ? true : t[v].p != -1;
cbb }
277 void rootify(int v) {
5e3     access(v);
a02     t[v].rev ^= 1;
cbb }
971 ll query(int v, int w) {
b54     rootify(w), access(v);
249     return t[v].sub;
cbb }
3fa void update(int v, int w, int x) {
b54     rootify(w), access(v);
12c     t[v].lazy += x;
cbb }
142 void link(int v, int w) {
821     rootify(w);
389     t[w].p = v;
cbb }
031 void cut(int v, int w) {
b54     rootify(w), access(v);
264     t[v].ch[0] = t[t[v].ch[0]].p = -1;
cbb }
bbb int lca(int v, int w) {

```

```

5e3     access(v);
a8b     return access(w);
cbb }
cbb }

```

## 2.30 Max flow com lower bound nas arestas

```

// add(a, b, l, r):
// adiciona aresta de a pra b, onde precisa passar f de fluxo, l
// <= f <= r
// add(a, b, c):
// adiciona aresta de a pra b com capacidade c
//
// Mesma complexidade do Dinic
// 5f2379

919 struct lb_max_flow : dinic {
5ce     vector<int> d;
331     lb_max_flow(int n) : dinic(n + 2), d(n, 0) {}
b12     void add(int a, int b, int l, int r) {
c97         d[a] -= l;
f1b         d[b] += l;
017         dinic::add(a, b, r - l);
cbb     }
087     void add(int a, int b, int c) {
107         dinic::add(a, b, c);
cbb     }
7a1     bool has_circulation() {
50c         int n = d.size();

854         ll cost = 0;
603         for (int i = 0; i < n; i++) {
c69             if (d[i] > 0) {
f56                 cost += d[i];
d06                 dinic::add(n, i, d[i]);
9c7             } else if (d[i] < 0) {
76b                 dinic::add(i, n+1, -d[i]);
cbb             }
cbb         }

283         return (dinic::max_flow(n, n+1) == cost);
cbb     }
7bd     bool has_flow(int src, int snk) {
65d         dinic::add(snk, src, INF);

```

```

e40         return has_circulation();
cbb     }
4eb     ll max_flow(int src, int snk) {
ee8         if (!has_flow(src, snk)) return -1;
ea5         dinic::F = 0;
626         return dinic::max_flow(src, snk);
cbb     }
214 };

```

## 2.31 MinCostMaxFlow

```

// min_cost_flow(s, t, f) computa o par (fluxo, custo)
// com max(fluxo) <= f que tenha min(custo)
// min_cost_flow(s, t) -> Fluxo maximo de custo minimo de s pra t
// Se for um dag, da pra substituir o SPFA por uma DP pra nao
// pagar O(nm) no comeco
// Se nao tiver aresta com custo negativo, nao precisa do SPFA
//
// O(nm + f * m log n)
// 697b4c

```

```

123 template<typename T> struct mcmf {
670     struct edge {
b75         int to, rev, flow, cap; // para, id da reversa, fluxo,
        capacidade
7f9         bool res; // se eh reversa
635         T cost; // custo da unidade de fluxo
892         edge() : to(0), rev(0), flow(0), cap(0), cost(0),
        res(false) {}
1d7         edge(int to_, int rev_, int flow_, int cap_, T cost_,
        bool res_)
f8d             : to(to_), rev(rev_), flow(flow_), cap(cap_),
        res(res_), cost(cost_) {}
214     };

002     vector<vector<edge>> g;
168     vector<int> par_idx, par;
f1e     T inf;
a03     vector<T> dist;

b22     mcmf(int n) : g(n), par_idx(n), par(n),
        inf(numeric_limits<T>::max()/3) {}

```

```

91c     void add(int u, int v, int w, T cost) { // de u pra v com
        cap w e custo cost
2fc         edge a = edge(v, g[v].size(), 0, w, cost, false);
234         edge b = edge(u, g[u].size(), 0, 0, -cost, true);

b24         g[u].push_back(a);
c12         g[v].push_back(b);
cbb     }

8bc     vector<T> spfa(int s) { // nao precisa se nao tiver custo
        negativo
871         deque<int> q;
3d1         vector<bool> is_inside(g.size(), 0);
577         dist = vector<T>(g.size(), inf);

a93         dist[s] = 0;
a30         q.push_back(s);
ecb         is_inside[s] = true;

14d         while (!q.empty()) {
b1e             int v = q.front();
ced             q.pop_front();
48d             is_inside[v] = false;

76e             for (int i = 0; i < g[v].size(); i++) {
9d4                 auto [to, rev, flow, cap, res, cost] = g[v][i];
e61                 if (flow < cap and dist[v] + cost < dist[to]) {
943                     dist[to] = dist[v] + cost;

ed6                     if (is_inside[to]) continue;
020                     if (!q.empty() and dist[to] >
                        dist[q.front()]) q.push_back(to);
b33                     else q.push_front(to);
b52                     is_inside[to] = true;
cbb                 }
cbb             }
cbb         }
8d7         return dist;
cbb     }

2a2     bool dijkstra(int s, int t, vector<T>& pot) {
489         priority_queue<pair<T, int>, vector<pair<T, int>>,
        greater<>> q;
577         dist = vector<T>(g.size(), inf);
a93         dist[s] = 0;
115         q.emplace(0, s);
402         while (q.size()) {

```

```

91b         auto [d, v] = q.top();
833         q.pop();
68b         if (dist[v] < d) continue;
76e         for (int i = 0; i < g[v].size(); i++) {
9d4             auto [to, rev, flow, cap, res, cost] = g[v][i];
e8c             cost += pot[v] - pot[to];
e61             if (flow < cap and dist[v] + cost < dist[to]) {
943                 dist[to] = dist[v] + cost;
441                 q.emplace(dist[to], to);
88b                 par_idx[to] = i, par[to] = v;
cbb             }
cbb         }
cbb     }
1d4     return dist[t] < inf;
cbb }

3d2 pair<int, T> min_cost_flow(int s, int t, int flow = INF) {
3dd     vector<T> pot(g.size(), 0);
9e4     pot = spfa(s); // mudar algoritmo de caminho minimo aqui

d22     int f = 0;
ce8     T ret = 0;
4a0     while (f < flow and dijkstra(s, t, pot)) {
bda         for (int i = 0; i < g.size(); i++)
d2a             if (dist[i] < inf) pot[i] += dist[i];

71b         int mn_flow = flow - f, u = t;
045         while (u != s){
90f             mn_flow = min(mn_flow,
07d                 g[par[u]][par_idx[u]].cap -
g[par[u]][par_idx[u]].flow);
3d1             u = par[u];
cbb         }

1f2         ret += pot[t] * mn_flow;

476         u = t;
045         while (u != s) {
e09             g[par[u]][par_idx[u]].flow += mn_flow;
d98             g[u][g[par[u]][par_idx[u]].rev].flow -= mn_flow;
3d1             u = par[u];
cbb         }

04d         f += mn_flow;
cbb     }

```

```

15b         return make_pair(f, ret);
cbb     }

// Opcional: retorna as arestas originais por onde passa
// flow = cap
182     vector<pair<int,int>> recover() {
24a         vector<pair<int,int>> used;
2a4         for (int i = 0; i < g.size(); i++) for (edge e : g[i])
587             if(e.flow == e.cap && !e.res) used.push_back({i,
e.to});
f6b         return used;
cbb     }
214 };

```

## 2.32 Prufer code

```

// Traduz de lista de arestas para prufer code
// e vice-versa
// Os vertices tem label de 0 a n-1
// Todo array com n-2 posicoes e valores de
// 0 a n-1 sao prufer codes validos
//
// 0(n)

// d3b324
47d vector<int> to_prufer(vector<pair<int, int>> tree) {
1fa     int n = tree.size()+1;
2cf     vector<int> d(n, 0);
4aa     vector<vector<int>> g(n);
f87     for (auto [a, b] : tree) d[a]++, d[b]++,
f60         g[a].push_back(b), g[b].push_back(a);
c5a     vector<int> pai(n, -1);
260     queue<int> q; q.push(n-1);
402     while (q.size()) {
be1         int u = q.front(); q.pop();
34c         for (int v : g[u]) if (v != pai[u])
9c9             pai[v] = u, q.push(v);
cbb     }
399     int idx, x;
897     idx = x = find(d.begin(), d.end(), 1) - d.begin();
4b8     vector<int> ret;
b28     for (int i = 0; i < n-2; i++) {
d4b         int y = pai[x];
e81         ret.push_back(y);

```

```

666         if (--d[y] == 1 and y < idx) x = y;
367         else idx = x = find(d.begin()+idx+1, d.end(), 1) -
d.begin();
cbb     }
edf     return ret;
cbb }

// 765413
4d8 vector<pair<int, int>> from_prufer(vector<int> p) {
455     int n = p.size()+2;
126     vector<int> d(n, 1);
650     for (int i : p) d[i]++;
85b     p.push_back(n-1);
399     int idx, x;
897     idx = x = find(d.begin(), d.end(), 1) - d.begin();
1df     vector<pair<int, int>> ret;
b06     for (int y : p) {
dab         ret.push_back({x, y});
666         if (--d[y] == 1 and y < idx) x = y;
367         else idx = x = find(d.begin()+idx+1, d.end(), 1) -
d.begin();
cbb     }
edf     return ret;
cbb }

```

## 2.33 Sack (DSU em arvores)

```

// Responde queries de todas as sub-arvores
// offline
//
// O(n log(n))
// bb361f

```

```

6bf int sz[MAX], cor[MAX], cnt[MAX];
042 vector<int> g[MAX];

6df void build(int k, int d=0) {
e8f     sz[k] = 1;
01a     for (auto& i : g[k]) {
30f         build(i, d+1); sz[k] += sz[i];
925         if (sz[i] > sz[g[k][0]]) swap(i, g[k][0]);
cbb     }
cbb }

```

```

74f void compute(int k, int x, bool dont=1) {
de9     cnt[cor[k]] += x;
828     for (int i = dont; i < g[k].size(); i++)
b5c         compute(g[k][i], x, 0);
cbb }

dc4 void solve(int k, bool keep=0) {
32a     for (int i = int(g[k].size())-1; i >= 0; i--)
b4c         solve(g[k][i], !i);
4a0     compute(k, 1);

// agora cnt[i] tem quantas vezes a cor
// i aparece na sub-arvore do k

830     if (!keep) compute(k, -1, 0);
cbb }

```

## 2.34 Tarjan para SCC

```

// O(n + m)
// 573bfa

```

```

042 vector<int> g[MAX];
4ce stack<int> s;
a42 int vis[MAX], comp[MAX];
3fd int id[MAX];

// se quiser comprimir ciclo ou achar ponte em grafo nao
// direcionado,
// colocar um if na dfs para nao voltar pro pai da DFS tree
f32 int dfs(int i, int& t) {
cf0     int lo = id[i] = t++;
18e     s.push(i);
0c2     vis[i] = 2;

48e     for (int j : g[i]) {
740         if (!vis[j]) lo = min(lo, dfs(j, t));
994         else if (vis[j] == 2) lo = min(lo, id[j]);
cbb     }

// aresta de i pro pai eh uma ponte (no caso nao
// direcionado)
3de     if (lo == id[i]) while (1) {
3c3         int u = s.top(); s.pop();

```

```

9c5         vis[u] = 1, comp[u] = i;
2ef         if (u == i) break;
cbb     }

253     return lo;
cbb }

f93 void tarjan(int n) {
6bb     int t = 0;
991     for (int i = 0; i < n; i++) vis[i] = 0;

3be     for (int i = 0; i < n; i++) if (!vis[i]) dfs(i, t);
cbb }

```

## 2.35 Topological Sort

```

// Retorna uma ordenacao topologica de g
// Se g nao for DAG retorna um vetor vaziao
//
// O(n + m)
// bdc95e

042 vector<int> g[MAX];

b6a vector<int> topo_sort(int n) {
46e     vector<int> ret(n,-1), vis(n,0);

f51     int pos = n-1, dag = 1;
36d     function<void(int)> dfs = [&](int v) {
cca         vis[v] = 1;
440         for (auto u : g[v]) {
152             if (vis[u] == 1) dag = 0;
532             else if (!vis[u]) dfs(u);
cbb         }
d44         ret[pos--] = v, vis[v] = 2;
214     };

158     for (int i = 0; i < n; i++) if (!vis[i]) dfs(i);

d8f     if (!dag) ret.clear();
edf     return ret;
cbb }

```

## 2.36 Vertex cover

```

// Encontra o tamanho do vertex cover minimo
// Da pra alterar facil pra achar os vertices
// Parece rodar com < 2 s pra N = 90
//
// O(n * 1.38^n)
// 9c5024

76a namespace cover {
5a4     const int MAX = 96;
042     vector<int> g[MAX];
823     bitset<MAX> bs[MAX];
1a8     int n;

697     void add(int i, int j) {
bd0         if (i == j) return;
78c         n = max({n, i+1, j+1});
200         bs[i][j] = bs[j][i] = 1;
cbb     }

6c0     int rec(bitset<MAX> m) {
1a4         int ans = 0;
25b         for (int x = 0; x < n; x++) if (m[x]) {
002             bitset<MAX> comp;
4bf             function<void(int)> dfs = [&](int i) {
b96                 comp[i] = 1, m[i] = 0;
0c3                 for (int j : g[i]) if (m[j]) dfs(j);
214             };
963             dfs(x);

d34             int ma, deg = -1, cyc = 1;
417             for (int i = 0; i < n; i++) if (comp[i]) {
d0b                 int d = (bs[i]&comp).count();
18a                 if (d <= 1) cyc = 0;
c1f                 if (d > deg) deg = d, ma = i;
cbb             }
269             if (deg <= 2) { // caminho ou ciclo
340                 ans += (comp.count() + cyc) / 2;
5e2                 continue;
cbb             }
3f9             comp[ma] = 0;

// ou ta no cover, ou nao ta no cover
1dd             ans += min(1 + rec(comp), deg + rec(comp & ~
bs[ma]));

```



```

cbb    }
ba7    return ans;
cbb    }
f5c    int solve() {
3c5        bitset<MAX> m;
603        for (int i = 0; i < n; i++) {
939            m[i] = 1;
f90            for (int j = 0; j < n; j++)
741                if (bs[i][j]) g[i].push_back(j);
cbb        }
4f9        return rec(m);
cbb    }
cbb }

```

## 2.37 Virtual Tree

```

// Comprime uma arvore dado um conjunto S de vertices, de forma que
// o conjunto de vertices da arvore comprimida contenha S e seja
// minimal e fechado sobre a operacao de LCA
// Se |S| = k, a arvore comprimida tem menos que 2k vertices
// As arestas de virt possuem a distancia do vertice ate o vizinho
// Retorna a raiz da virtual tree
//
// lca::pos deve ser a ordem de visitacao no dfs
// voce pode usar o LCAcomHLD, por exemplo
//
// O(k log(k))
// 42d990

b36 vector<pair<int, int>> virt[MAX];

d41 #warning lembrar de buildar o LCA antes
c14 int build_virt(vector<int> v) {
b46     auto cmp = [&](int i, int j) { return lca::pos[i] <
        lca::pos[j]; };
074     sort(v.begin(), v.end(), cmp);
e85     for (int i = v.size()-1; i; i--) v.push_back(lca::lca(v[i],
        v[i-1]));
074     sort(v.begin(), v.end(), cmp);
d76     v.erase(unique(v.begin(), v.end()), v.end());
37c     for (int i = 0; i < v.size(); i++) virt[v[i]].clear();
197     for (int i = 1; i < v.size(); i++) virt[lca::lca(v[i-1],
        v[i])].clear();
ad7     for (int i = 1; i < v.size(); i++) {

```

```

51b         int parent = lca::lca(v[i-1], v[i]);
290         int d = lca::dist(parent, v[i]);
d41 #warning soh to colocando aresta descendo
4d0         virt[parent].emplace_back(v[i], d);
cbb     }
832     return v[0];
cbb }

```

## 3 Problemas

### 3.1 Algoritmo Hungaro

```

// Resolve o problema de assignment (matriz n x n)
// Colocar os valores da matriz em 'a' (pode < 0)
// assignment() retorna um par com o valor do
// assignment minimo, e a coluna escolhida por cada linha
//
// O(n^3)
// 64c53e

a6a template<typename T> struct hungarian {
1a8     int n;
a08     vector<vector<T>> a;
f36     vector<T> u, v;
5ff     vector<int> p, way;
f1e     T inf;

c3f     hungarian(int n_) : n(n_), u(n+1), v(n+1), p(n+1), way(n+1)
    {
b2f         a = vector<vector<T>>(n, vector<T>(n));
1f3         inf = numeric_limits<T>::max();
cbb     }
d67     pair<T, vector<int>> assignment() {
78a         for (int i = 1; i <= n; i++) {
8c9             p[0] = i;
625             int j0 = 0;
ce7             vector<T> minv(n+1, inf);
241             vector<int> used(n+1, 0);
016             do {
472                 used[j0] = true;
d24                 int i0 = p[j0], j1 = -1;
7e5                 T delta = inf;
9ac                 for (int j = 1; j <= n; j++) if (!used[j]) {

```

```

7bf          T cur = a[i0-1][j-1] - u[i0] - v[j];
9f2          if (cur < minv[j]) minv[j] = cur, way[j] =
j0;
821          if (minv[j] < delta) delta = minv[j], j1 =
j;
cbb      }
f63      for (int j = 0; j <= n; j++)
2c5          if (used[j]) u[p[j]] += delta, v[j] -=
delta;
6ec          else minv[j] -= delta;
6d4          j0 = j1;
233      } while (p[j0] != 0);
016      do {
4c5          int j1 = way[j0];
0d7          p[j0] = p[j1];
6d4          j0 = j1;
ca1      } while (j0);
cbb  }
306  vector<int> ans(n);
6db  for (int j = 1; j <= n; j++) ans[p[j]-1] = j-1;
da3  return make_pair(-v[0], ans);
cbb  }
214 };

```

## 3.2 Algoritmo MO - queries em caminhos de arvore

```

// Problema que resolve: https://www.spoj.com/problems/COT2/
//
// Complexidade sendo c = O(update) e SQ = sqrt(n):
// O((n + q) * sqrt(n) * c)
// 395329

```

```
1bc const int MAX = 40010, SQ = 400;
```

```
042 vector<int> g[MAX];
```

```
c54 namespace LCA { ... }
```

```
249 int in[MAX], out[MAX], vtx[2 * MAX];
```

```
81b bool on[MAX];
```

```
4c3 int dif, freq[MAX];
```

```
9e2 vector<int> w;
```

```

d9a void dfs(int v, int p, int &t) {
659     vtx[t] = v, in[v] = t++;
18e     for (int u : g[v]) if (u != p) {
c53         dfs(u, v, t);
cbb     }
217     vtx[t] = v, out[v] = t++;
cbb }

e5f void update(int p) { // faca alteracoes aqui
bbc     int v = vtx[p];
0ec     if (not on[v]) { // insere vtx v
31c         dif += (freq[w[v]] == 0);
b20         freq[w[v]]++;
cbb     }
4e6     else { // retira o vertice v
0a9         dif -= (freq[w[v]] == 1);
fd3         freq[w[v]]--;
cbb     }
73e     on[v] = not on[v];
cbb }

```

```

a3a vector<tuple<int, int, int>> build_queries(const
vector<pair<int, int>>& q) {
ea6     LCA::build(0);
f77     vector<tuple<int, int, int>> ret;
aa9     for (auto [l, r] : q) {
d24         if (in[r] < in[l]) swap(l, r);
6f9         int p = LCA::lca(l, r);
826         int init = (p == l) ? in[l] : out[l];
07a         ret.emplace_back(init, in[r], in[p]);
cbb     }
edf     return ret;
cbb }

```

```

f31 vector<int> mo_tree(const vector<pair<int, int>>& vq) {
6bb     int t = 0;
dab     dfs(0, -1, t);

```

```
af1     auto q = build_queries(vq);
```

```

f48     vector<int> ord(q.size());
be8     iota(ord.begin(), ord.end(), 0);
d01     sort(ord.begin(), ord.end(), [&] (int l, int r) {
d8d         int bl = get<0>(q[l]) / SQ, br = get<0>(q[r]) / SQ;
596         if (bl != br) return bl < br;
158         else if (bl % 2 == 1) return get<1>(q[l]) <

```

```

    get<1>(q[r]);
f1d    else return get<1>(q[l]) > get<1>(q[r]);
c0c    });

80e    memset(freq, 0, sizeof freq);
bf6    dif = 0;

ff2    vector<int> ret(q.size());
3d9    int l = 0, r = -1;
8b0    for (int i : ord) {
3c7        auto [ql, qr, qp] = q[i];
af7        while (r < qr) update(++r);
d6b        while (l > ql) update(--l);
951        while (l < ql) update(l++);
6a1        while (r > qr) update(r--);

3d8        if (qp < l or qp > r) { // se LCA estah entre as pontas
74b            update(qp);
2e1            ret[i] = dif;
74b            update(qp);
cbb        }
0fe        else ret[i] = dif;
cbb    }
edf    return ret;
cbb }

```

### 3.3 Angle Range Intersection

```

// Computa intersecao de angulos
// Os angulos (arcos) precisam ter comprimento < pi
// (caso contrario a intersecao eh estranha)
//
// Tudo O(1)
// 5e1c85

32a struct angle_range {
75e     static constexpr ld ALL = 1e9, NIL = -1e9;
395     ld l, r;
c77     angle_range() : l(ALL), r(ALL) {}
894     angle_range(ld l_, ld r_) : l(l_), r(r_) { fix(l), fix(r); }

4ee     void fix(ld& theta) {
da7         if (theta == ALL or theta == NIL) return;
323         if (theta > 2*pi) theta -= 2*pi;

```

```

868         if (theta < 0) theta += 2*pi;
cbb     }
2ee     bool empty() { return l == NIL; }
931     bool contains(ld q) {
40f         fix(q);
4d7         if (l == ALL) return true;
fec         if (l == NIL) return false;
6a6         if (l < r) return l < q and q < r;
075         return q > l or q < r;
cbb     }
9c7     friend angle_range operator &(angle_range p, angle_range q)
{
743         if (p.l == ALL or q.l == NIL) return q;
20f         if (q.l == ALL or p.l == NIL) return p;
7d5         if (p.l > p.r and q.l > q.r) return {max(p.l, q.l) ,
min(p.r, q.r)};
aa6         if (q.l > q.r) swap(p.l, q.l), swap(p.r, q.r);
8d8         if (p.l > p.r) {
249             if (q.r > p.l) return {max(q.l, p.l) , q.r};
6f7             else if (q.l < p.r) return {q.l, min(q.r, p.r)};
270             return {NIL, NIL};
cbb         }
5a8         if (max(p.l, q.l) > min(p.r, q.r)) return {NIL, NIL};
bcb         return {max(p.l, q.l), min(p.r, q.r)};
cbb     }
214 };

```

### 3.4 Area da Uniao de Retangulos

```

// O(n log(n))
// 5d8d2f

aa4 namespace seg {
6b3     pair<int, ll> seg[4*MAX];
b1b     ll lazy[4*MAX], *v;
1a8     int n;

e01     pair<int, ll> merge(pair<int, ll> l, pair<int, ll> r){
719         if (l.second == r.second) return {l.first+r.first,
l.second};
53b         else if (l.second < r.second) return l;
aa0         else return r;
cbb     }

```

```

6fc     pair<int, ll> build(int p=1, int l=0, int r=n-1) {
3c7         lazy[p] = 0;
bf8         if (l == r) return seg[p] = {1, v[l]};
ee4         int m = (l+r)/2;
432         return seg[p] = merge(build(2*p, l, m), build(2*p+1,
m+1, r));
cbb     }
d9e     void build(int n2, ll* v2) {
680         n = n2, v = v2;
6f2         build();
cbb     }
ceb     void prop(int p, int l, int r) {
208         seg[p].second += lazy[p];
2c9         if (l != r) lazy[2*p] += lazy[p], lazy[2*p+1] +=
lazy[p];
3c7         lazy[p] = 0;
cbb     }
693     pair<int, ll> query(int a, int b, int p=1, int l=0, int
r=n-1) {
6b9         prop(p, l, r);
527         if (a <= l and r <= b) return seg[p];
9b7         if (b < l or r < a) return {0, LINF};
ee4         int m = (l+r)/2;
eeb         return merge(query(a, b, 2*p, l, m), query(a, b, 2*p+1,
m+1, r));
cbb     }
07c     pair<int, ll> update(int a, int b, int x, int p=1, int l=0,
int r=n-1) {
6b9         prop(p, l, r);
9a3         if (a <= l and r <= b) {
b94             lazy[p] += x;
6b9             prop(p, l, r);
534             return seg[p];
cbb         }
e9f         if (b < l or r < a) return seg[p];
ee4         int m = (l+r)/2;
086         return seg[p] = merge(update(a, b, x, 2*p, l, m),
579             update(a, b, x, 2*p+1, m+1, r));
cbb     }
214 };

eb5 ll seg_vec[MAX];

8be ll area_sq(vector<pair<pair<int, int>, pair<int, int>>> &sq){
28c     vector<pair<pair<int, int>, pair<int, int>>> up;
60a     for (auto it : sq){

```

```

619         int x1, y1, x2, y2;
ae0         tie(x1, y1) = it.first;
68e         tie(x2, y2) = it.second;
80f         up.push_back({x1+1, 1}, {y1, y2});
aee         up.push_back({x2+1, -1}, {y1, y2});
cbb     }
092     sort(up.begin(), up.end());
049     memset(seg_vec, 0, sizeof seg_vec);
6fe     ll H_MAX = MAX;
156     seg::build(H_MAX-1, seg_vec);
7ba     auto it = up.begin();
04b     ll ans = 0;
f14     while (it != up.end()){
07f         ll L = (*it).first.first;
718         while (it != up.end() && (*it).first.first == L){
127             int x, inc, y1, y2;
d35             tie(x, inc) = it->first;
d3d             tie(y1, y2) = it->second;
5d1             seg::update(y1+1, y2, inc);
40d             it++;
cbb         }
852         if (it == up.end()) break;
d8a         ll R = (*it).first.first;

f59         ll W = R-L;
efd         auto jt = seg::query(0, H_MAX-1);
91a         ll H = H_MAX - 1;
e8a         if (jt.second == 0) H -= jt.first;
8df         ans += W*H;
cbb     }
ba7     return ans;
cbb }

```

### 3.5 Area Maxima de Histograma

```

// Assume que todas as barras tem largura 1,
// e altura dada no vetor v
//
// 0(n)
// e43846

```

```

15e ll area(vector<int> v) {
b73     ll ret = 0;
4ce     stack<int> s;

```

```

// valores iniciais pra dar tudo certo
447 v.insert(v.begin(), -1);
d56 v.insert(v.end(), -1);
1f8 s.push(0);

0be for(int i = 0; i < (int) v.size(); i++) {
78e     while (v[s.top()] > v[i]) {
265         ll h = v[s.top()]; s.pop();
de1         ret = max(ret, h * (i - s.top() - 1));
cbb     }
18e     s.push(i);
cbb }

edf return ret;
cbb }

```

### 3.6 Binomial modular

```

// Computa C(n, k) mod m em O(m + log(m) log(n))
// = O(rapido)
// ed4344

97c ll divi[MAX];

398 ll expo(ll a, ll b, ll m) {
1c1     if (!b) return 1;
399     ll ans = expo(a*a%m, b/2, m);
751     if (b%2) ans *= a;
2e9     return ans%m;
cbb }

f0a ll inv(ll a, ll b){
bca     return 1<a ? b - inv(b%a,a)*b/a : 1;
cbb }

153 template<typename T> tuple<T, T, T> ext_gcd(T a, T b) {
3bd     if (!a) return {b, 0, 1};
550     auto [g, x, y] = ext_gcd(b%a, a);
c59     return {g, y - b/a*x, x};
cbb }

bfe template<typename T = ll> struct crt {
627     T a, m;

```

```

5f3 crt() : a(0), m(1) {}
7eb crt(T a_, T m_) : a(a_), m(m_) {}
911 crt operator * (crt C) {
238     auto [g, x, y] = ext_gcd(m, C.m);
dc0     if ((a - C.a) % g) a = -1;
4f9     if (a == -1 or C.a == -1) return crt(-1, 0);
d09     T lcm = m/g*C.m;
eb2     T ans = a + (x*(C.a-a)/g % (C.m/g))*m;
d8d     return crt((ans % lcm + lcm) % lcm, lcm);
cbb }
214 };

6f2 pair<ll, ll> divide_show(ll n, int p, int k, int pak) {
4f7     if (n == 0) return {0, 1};
d02     ll blocos = n/pak, falta = n%pak;
2ce     ll periodo = divi[pak], resto = divi[falta];
616     ll r = expo(periodo, blocos, pak)*resto%pak;

445     auto rec = divide_show(n/p, p, k, pak);
a51     ll y = n/p + rec.first;
bb9     r = r*rec.second % pak;

90f     return {y, r};
cbb }

6e6 ll solve_pak(ll n, ll x, int p, int k, int pak) {
d34     divi[0] = 1;
f2b     for (int i = 1; i <= pak; i++) {
901         divi[i] = divi[i-1];
840         if (i%p) divi[i] = divi[i] * i % pak;
cbb     }

4ac     auto dn = divide_show(n, p, k, pak), dx = divide_show(x, p,
k, pak),
162         dnx = divide_show(n-x, p, k, pak);
768     ll y = dn.first-dx.first-dnx.first, r =
b64         (dn.second*inv(dx.second, pak)%pak)*inv(dnx.second,
pak)%pak;
035     return expo(p, y, pak) * r % pak;
cbb }

9dd ll solve(ll n, ll x, int mod) {
490     vector<pair<int, int>> f;
c3b     int mod2 = mod;
7b4     for (int i = 2; i*i <= mod2; i++) if (mod2%i==0) {
aff         int c = 0;

```

```

75b         while (mod2%i==0) mod2 /= i, c++;
2a1         f.push_back({i, c});
cbb     }
0ff     if (mod2 > 1) f.push_back({mod2, 1});
e96     crt ans(0, 1);
a13     for (int i = 0; i < f.size(); i++) {
702         int pak = 1;
7e4         for (int j = 0; j < f[i].second; j++) pak *= f[i].first;
304         ans = ans * crt(solve_pak(n, x, f[i].first,
f[i].second, pak), pak);
cbb     }
5fb     return ans.a;
cbb }

```

### 3.7 Closest pair of points

```

// O(nlogn)
// f90265

915 pair<pt, pt> closest_pair_of_points(vector<pt> v) {
3d2     int n = v.size();
fca     sort(v.begin(), v.end());
31c     for (int i = 1; i < n; i++) if (v[i] == v[i-1]) return
{v[i-1], v[i]};
c20     auto cmp_y = [&](const pt &l, const pt &r) {
b53         if (l.y != r.y) return l.y < r.y;
920         return l.x < r.x;
214     };
62e     set<pt, decltype(cmp_y)> s(cmp_y);
3d9     int l = 0, r = -1;
6a2     ll d2_min = numeric_limits<ll>::max();
4d5     pt pl, pr;
bd1     const int magic = 5;
a55     while (r+1 < n) {
7f1         auto it = s.insert(v[++r]).first;
c92         int cnt = magic/2;
773         while (cnt-- and it != s.begin()) it--;
a01         cnt = 0;
d68         while (cnt++ < magic and it != s.end()) {
f19             if (!((*it) == v[r])) {
67e                 ll d2 = dist2(*it, v[r]);
74e                 if (d2_min > d2) {
229                     d2_min = d2;
841                     pl = *it;

```

```

4f2             pr = v[r];
cbb         }
cbb     }
40d         it++;
cbb     }
eb0         while (l < r and sq(v[l].x-v[r].x) > d2_min)
s.erase(v[l++]);
cbb     }
c74     return {pl, pr};
cbb }

```

### 3.8 Coloracao de Grafo de Intervalo

```

// Colore os intervalos com o numero minimo
// de cores de tal forma que dois intervalos
// que se interceptam tem cores diferentes
// As cores vao de 1 ate n
//
// O(n log(n))
// 83a32d

615 vector<int> coloring(vector<pair<int, int>>& v) {
3d2     int n = v.size();
c08     vector<pair<int, pair<int, int>>> ev;
603     for (int i = 0; i < n; i++) {
150         ev.push_back({v[i].first, {1, i}});
cda         ev.push_back({v[i].second, {0, i}});
cbb     }
49e     sort(ev.begin(), ev.end());
360     vector<int> ans(n), avl(n);
265     for (int i = 0; i < n; i++) avl.push_back(n-i);
4bf     for (auto i : ev) {
cbe         if (i.second.first == 1) {
021             ans[i.second.second] = avl.back();
a00             avl.pop_back();
296         } else avl.push_back(ans[i.second.second]);
cbb     }
ba7     return ans;
cbb }

```

### 3.9 Conectividade Dinamica

```

// Offline com Divide and Conquer e
// DSU com rollback
// O(n log^2(n))
// 043d93

8f2 typedef pair<int, int> T;

1cd namespace data {
553     int n, ans;
573     int p[MAX], sz[MAX];
ee6     stack<int> S;

e5b     void build(int n2) {
1e3         n = n2;
8a6         for (int i = 0; i < n; i++) p[i] = i, sz[i] = 1;
0b2         ans = n;
cbb     }
1b1     int find(int k) {
006         while (p[k] != k) k = p[k];
839         return k;
cbb     }
072     void add(T x) {
700         int a = x.first, b = x.second;
605         a = find(a), b = find(b);
843         if (a == b) return S.push(-1);
e7d         ans--;
3c6         if (sz[a] > sz[b]) swap(a, b);
4c2         S.push(a);
582         sz[b] += sz[a];
84b         p[a] = b;
cbb     }
5eb     int query() {
ba7         return ans;
cbb     }
5cf     void rollback() {
465         int u = S.top(); S.pop();
61c         if (u == -1) return;
270         sz[p[u]] -= sz[u];
546         p[u] = u;
0df         ans++;
cbb     }
214 };

357 int ponta[MAX]; // outra ponta do intervalo ou -1 se for query
4f0 int ans[MAX], n, q;
487 T qu[MAX];

```

```

47b void solve(int l = 0, int r = q-1) {
0b1     if (l >= r) {
8c0         ans[l] = data::query(); // agora a estrutura ta certa
505         return;
cbb     }
962     int m = (l+r)/2, qnt = 1;
fc7     for (int i = m+1; i <= r; i++) if (ponta[i]+1 and ponta[i]
    < 1)
37d         data::add(qu[i]), qnt++;
221     solve(l, m);
593     while (--qnt) data::rollback();
a2c     for (int i = l; i <= m; i++) if (ponta[i]+1 and ponta[i] >
    r)
37d         data::add(qu[i]), qnt++;
37b     solve(m+1, r);
281     while (qnt--) data::rollback();
cbb }

```

### 3.10 Conectividade Dinamica 2

```

// Offline com link-cut trees
// O(n log(n))
// d38e4e

1ef namespace lct {
3c9     struct node {
19f         int p, ch[2];
a2a         int val, sub;
aa6         bool rev;
f93         node() {}
54e         node(int v) : p(-1), val(v), sub(v), rev(0) { ch[0] =
    ch[1] = -1; }
214     };

c53     node t[2*MAX]; // MAXN + MAXQ
99e     map<pair<int, int>, int> aresta;
e4d     int sz;

95a     void prop(int x) {
aa2         if (t[x].rev) {
f95             swap(t[x].ch[0], t[x].ch[1]);
379             if (t[x].ch[0]+1) t[t[x].ch[0]].rev ^= 1;
c3d             if (t[x].ch[1]+1) t[t[x].ch[1]].rev ^= 1;

```

```

cbb      }
693      t[x].rev = 0;
cbb      }
564      void update(int x) {
e8d          t[x].sub = t[x].val;
8ca          for (int i = 0; i < 2; i++) if (t[x].ch[i]+1) {
621              prop(t[x].ch[i]);
78d              t[x].sub = min(t[x].sub, t[t[x].ch[i]].sub);
cbb          }
cbb      }
971      bool is_root(int x) {
657          return t[x].p == -1 or (t[t[x].p].ch[0] != x and
t[t[x].p].ch[1] != x);
cbb      }
ed6      void rotate(int x) {
497          int p = t[x].p, pp = t[p].p;
fc4          if (!is_root(p)) t[pp].ch[t[pp].ch[1] == p] = x;
251          bool d = t[p].ch[0] == x;
461          t[p].ch[!d] = t[x].ch[d], t[x].ch[d] = p;
a76          if (t[p].ch[!d]+1) t[t[p].ch[!d]].p = p;
8fa          t[x].p = pp, t[p].p = x;
444          update(p), update(x);
cbb      }
238      int splay(int x) {
18c          while (!is_root(x)) {
497              int p = t[x].p, pp = t[p].p;
77b              if (!is_root(pp)) prop(pp);
be5              prop(p), prop(x);
0c5              if (!is_root(p)) rotate((t[pp].ch[0] ==
p)^(t[p].ch[0] == x) ? x : p);
64f              rotate(x);
cbb          }
aab          return prop(x), x;
cbb      }
f16      int access(int v) {
0eb          int last = -1;
d9f          for (int w = v; w+1; update(last = w), splay(v), w =
t[v].p)
024              splay(w), t[w].ch[1] = (last == -1 ? -1 : v);
3d3          return last;
cbb      }
952      void make_tree(int v, int w=INF) { t[v] = node(w); }
82f      bool conn(int v, int w) {
2cf          access(v), access(w);
b9b          return v == w ? true : t[v].p != -1;
cbb      }

```

```

277      void rootify(int v) {
5e3          access(v);
a02          t[v].rev ^= 1;
cbb      }
a1d      int query(int v, int w) {
b54          rootify(w), access(v);
249          return t[v].sub;
cbb      }
204      void link_(int v, int w) {
821          rootify(w);
389          t[w].p = v;
cbb      }
6b8      void link(int v, int w, int x) { // v--w com peso x
379          int id = MAX + sz++;
110          aresta[make_pair(v, w)] = id;
ab6          make_tree(id, x);
c88          link_(v, id), link_(id, w);
cbb      }
e63      void cut_(int v, int w) {
b54          rootify(w), access(v);
264          t[v].ch[0] = t[t[v].ch[0]].p = -1;
cbb      }
031      void cut(int v, int w) {
b0f          int id = aresta[make_pair(v, w)];
a4a          cut_(v, id), cut_(id, w);
cbb      }
cbb }

893      void dyn_conn() {
c5f          int n, q; cin >> n >> q;
d6e          vector<int> p(2*q, -1); // outra ponta do intervalo
b4f          for (int i = 0; i < n; i++) lct::make_tree(i);
fbf          vector<pair<int, int>> qu(q);
139          map<pair<int, int>, int> m;
abf          for (int i = 0; i < q; i++) {
3c2              char c; cin >> c;
ef6              if (c == '?') continue;
602              int a, b; cin >> a >> b; a--, b--;
d11              if (a > b) swap(a, b);
8a1              qu[i] = {a, b};
8d7              if (c == '+') {
94b                  p[i] = i+q, p[i+q] = i;
906                  m[make_pair(a, b)] = i;
9d9              } else {
412                  int j = m[make_pair(a, b)];
ac2                  p[i] = j, p[j] = i;

```



```

cbb    }
cbb    }
447    int ans = n;
abf    for (int i = 0; i < q; i++) {
87d        if (p[i] == -1) {
886            cout << ans << endl; // numero de comp conexos
5e2            continue;
cbb        }
69d        int a = qu[i].first, b = qu[i].second;
c4d        if (p[i] > i) { // +
ac5            if (lct::conn(a, b)) {
18f                int mi = lct::query(a, b);
993                if (p[i] < mi) {
dd3                    p[p[i]] = p[i];
5e2                    continue;
cbb                }
6f7                lct::cut(qu[p[mi]].first, qu[p[mi]].second),
ans++;
6ea                p[mi] = mi;
cbb            }
d1d            lct::link(a, b, p[i]), ans--;
cb5        } else if (p[i] != i) lct::cut(a, b), ans++; // -
cbb    }
cbb }

```

### 3.11 Conj. Indep. Maximo com Peso em Grafo de Intervalo

```

// Retorna os indices ordenados dos intervalos selecionados
// Se tiver empate, retorna o que minimiza o comprimento total
//
// O(n log(n))
// c4dbe2

```

```

31e vector<int> ind_set(vector<tuple<int, int, int>>& v) {
b27     vector<tuple<int, int, int>> w;
f14     for (int i = 0; i < v.size(); i++) {
e85         w.push_back(tuple(get<0>(v[i]), 0, i));
6f0         w.push_back(tuple(get<1>(v[i]), 1, i));
cbb     }
d1d     sort(w.begin(), w.end());

844     vector<int> nxt(v.size());
c22     vector<pair<ll, int>> dp(v.size());
0eb     int last = -1;

```

```

723     for (auto [fim, t, i] : w) {
25a         if (t == 0) {
4ca             nxt[i] = last;
5e2             continue;
cbb         }
78b         dp[i] = {0, 0};
cb8         if (last != -1) dp[i] = max(dp[i], dp[last]);
911         pair<ll, int> pega = {get<2>(v[i]), -(get<1>(v[i]) -
get<0>(v[i]) + 1)};
5d3         if (nxt[i] != -1) pega.first += dp[nxt[i]].first,
pega.second += dp[nxt[i]].second;
b08         if (pega > dp[i]) dp[i] = pega;
7cb         else nxt[i] = last;
381         last = i;
cbb     }
977     pair<ll, int> ans = {0, 0};
919     int idx = -1;
ceb     for (int i = 0; i < v.size(); i++) if (dp[i] > ans) ans =
dp[i], idx = i;
4b8     vector<int> ret;
fdd     while (idx != -1) {
d69         if (get<2>(v[idx]) > 0 and
a05             (nxt[idx] == -1 or get<1>(v[nxt[idx]]) <
get<0>(v[idx]))) ret.push_back(idx);
e4f         idx = nxt[idx];
cbb     }
0ea     sort(ret.begin(), ret.end());
edf     return ret;
cbb }

```

### 3.12 Distancia maxima entre dois pontos

```

// max_dist2(v) - O(n log(n))
// max_dist_manhattan - O(n)

// Quadrado da Distancia Euclidiana (precisa copiar convex_hull,
// ccw e pt)
// bdace4
859 ll max_dist2(vector<pt> v) {
221     v = convex_hull(v);
a14     if (v.size() <= 2) return dist2(v[0], v[1%v.size()]);
04b     ll ans = 0;
323     int n = v.size(), j = 0;
603     for (int i = 0; i < n; i++) {

```

```

057         while (!ccw(v[(i+1)%n]-v[i], pt(0, 0),
v[(j+1)%n]-v[j])) j = (j+1)%n;
e7a         ans = max({ans, dist2(v[i], v[j]), dist2(v[(i+1)%n],
v[j])});
cbb     }
ba7     return ans;
cbb }

// Distancia de Manhattan
// 4e96f0
c51 template<typename T> T max_dist_manhattan(vector<pair<T, T>> v)
{
8eb     T min_sum, max_sum, min_dif, max_dif;
4f5     min_sum = max_sum = v[0].first + v[0].second;
271     min_dif = max_dif = v[0].first - v[0].second;
c25     for (auto [x, y] : v) {
1cb         min_sum = min(min_sum, x+y);
683         max_sum = max(max_sum, x+y);
782         min_dif = min(min_dif, x-y);
af7         max_dif = max(max_dif, x-y);
cbb     }
9f0     return max(max_sum - min_sum, max_dif - min_dif);
cbb }

```

### 3.13 Distinct Range Query

```

// build - O(n (log n + log(sigma)))
// query - O(log(sigma))
// 5c7aa1

```

```

789 namespace perseg { };

```

```

53d int qt[MAX];

```

```

edc void build(vector<int>& v) {
3d2     int n = v.size();
16b     perseg::build(n);
663     map<int, int> last;
05e     int at = 0;
603     for (int i = 0; i < n; i++) {
817         if (last.count(v[i])) {
a58             perseg::update(last[v[i]], -1);
69a             at++;
cbb         }

```

```

4f2         perseg::update(i, 1);
460         qt[i] = ++at;
efe         last[v[i]] = i;
cbb     }
cbb }

9e3 int query(int l, int r) {
080     return perseg::query(l, r, qt[r]);
cbb }

```

### 3.14 Distinct Range Query com Update

```

// build - O(n log(n))
// query - O(log^2(n))
// update - O(log^2(n))
// 2306f3

```

```

774 #include <ext/pb_ds/assoc_container.hpp>
30f #include <ext/pb_ds/tree_policy.hpp>
0d7 using namespace __gnu_pbds;
4fc template <class T>
def     using ord_set = tree<T, null_type, less<T>, rb_tree_tag,
3a1     tree_order_statistics_node_update>;

```

```

042 int v[MAX], n, nxt[MAX], prv[MAX];
f60 map<int, set<int>> > ocor;

```

```

e04 namespace bit {
686     ord_set<pair<int, int>> bit[MAX];

```

```

0a8     void build() {
3e1         for (int i = 1; i <= n; i++) bit[i].insert({nxt[i-1],
i-1});
78a         for (int i = 1; i <= n; i++) {
edf             int j = i + (i&-i);
d03             if (j <= n) for (auto x : bit[i]) bit[j].insert(x);
cbb         }
cbb     }
d3f     int pref(int p, int x) {
7c9         int ret = 0;
bbf         for (; p; p -= p&-p) ret += bit[p].order_of_key({x,
-INF});
edf         return ret;
cbb     }

```

```

d50     int query(int l, int r, int x) {
e55         return pref(r+1, x) - pref(l, x);
cbb     }
ff3     void update(int p, int x) {
f17         int p2 = p;
5ed         for (p++; p <= n; p += p&-p) {
ca8             bit[p].erase({nxt[p2], p2});
f6b             bit[p].insert({x, p2});
cbb         }
cbb     }
cbb }

0a8 void build() {
383     for (int i = 0; i < n; i++) nxt[i] = INF;
7b3     for (int i = 0; i < n; i++) prv[i] = -INF;
d07     vector<pair<int, int>> t;
348     for (int i = 0; i < n; i++) t.push_back({v[i], i});
3fd     sort(t.begin(), t.end());
603     for (int i = 0; i < n; i++) {
b40         if (i and t[i].first == t[i-1].first)
565             prv[t[i].second] = t[i-1].second;
a8b         if (i+1 < n and t[i].first == t[i+1].first)
12f             nxt[t[i].second] = t[i+1].second;
cbb     }

a23     for (int i = 0; i < n; i++) ocor[v[i]].insert(i);

1d7     bit::build();
cbb }

aae void muda(int p, int x) {
f92     bit::update(p, x);
c3d     nxt[p] = x;
cbb }

4ea int query(int a, int b) {
a0a     return b-a+1 - bit::query(a, b, b+1);
cbb }

ff3 void update(int p, int x) { // mudar valor na pos. p para x
c0b     if (prv[p] > -INF) muda(prv[p], nxt[p]);
4ae     if (nxt[p] < INF) prv[nxt[p]] = prv[p];

5bf     ocor[v[p]].erase(p);
4b4     if (!ocor[x].size()) {
19d         muda(p, INF);

```

```

8d4         prv[p] = -INF;
a69     } else if (*ocor[x].rbegin() < p) {
5b5         int i = *ocor[x].rbegin();
f64         prv[p] = i;
19d         muda(p, INF);
5f2         muda(i, p);
9d9     } else {
d46         int i = *ocor[x].lower_bound(p);
33f         if (prv[i] > -INF) {
f17             muda(prv[i], p);
8f9             prv[p] = prv[i];
94f         } else prv[p] = -INF;
523         prv[i] = p;
597         muda(p, i);
cbb     }
c96     v[p] = x; ocor[x].insert(p);
cbb }

```

### 3.15 Dominator Points

```

// Se um ponto A tem ambas as coordenadas >= B, dizemos
// que A domina B
// is_dominated(p) fala se existe algum ponto no conjunto
// que domina p
// insert(p) insere p no conjunto
// (se p for dominado por alguem, nao vai inserir)
// o multiset 'quina' guarda informacao sobre os pontos
// nao dominados por um elemento do conjunto que nao dominam
// outro ponto nao dominado por um elemento do conjunto
// No caso, armazena os valores de x+y esses pontos
//
// Complexidades:
// is_dominated - O(log(n))
// insert - O(log(n)) amortizado
// query - O(1)
// 09ffdc

e2a struct dominator_points {
baf     set<pair<int, int>> se;
4dd     multiset<int> quina;

a85     bool is_dominated(pair<int, int> p) {
80f         auto it = se.lower_bound(p);
633         if (it == se.end()) return 0;

```

```

ab4         return it->second >= p.second;
cbb     }
99b     void mid(pair<int, int> a, pair<int, int> b, bool rem) {
29a         pair<int, int> m = {a.first+1, b.second+1};
b19         int val = m.first + m.second;
638         if (!rem) quina.insert(val);
731         else quina.erase(quina.find(val));
cbb     }
7c4     bool insert(pair<int, int> p) {
fb4         if (is_dominated(p)) return 0;
80f         auto it = se.lower_bound(p);
ca9         if (it != se.begin() and it != se.end())
d4a             mid(*prev(it), *it, 1);
1fa         while (it != se.begin()) {
049             it--;
23c             if (it->second > p.second) break;
b86             if (it != se.begin()) mid(*prev(it), *it, 1);
316             it = se.erase(it);
cbb         }
433         it = se.insert(p).first;
69e         if (it != se.begin()) mid(*prev(it), *it, 0);
96d         if (next(it) != se.end()) mid(*it, *next(it), 0);
6a5         return 1;
cbb     }
5eb     int query() {
956         if (!quina.size()) return INF;
add         return *quina.begin();
cbb     }
214 };

```

### 3.16 DP de Dominacao 3D

```

// Computa para todo ponto i,
// dp[i] = 1 + max_{j dominado por i} dp[j]
// em que ser dominado eh ter as 3 coordenadas menores
// Da pra adaptar facil para outras dps
//
// O(n log^2 n), O(n) de memoria
// 7c8896

c53 void lis2d(vector<vector<tuple<int, int, int>>>& v,
vector<int>& dp, int l, int r) {
893     if (l == r) {
56f         for (int i = 0; i < v[l].size(); i++) {

```

```

8b5         int ii = get<2>(v[l][i]);
1ce         dp[ii] = max(dp[ii], 1);
cbb     }
505     return;
cbb }
ee4     int m = (l+r)/2;
62b     lis2d(v, dp, l, m);

325     vector<tuple<int, int, int>> vv[2];
d44     vector<int> Z;
871     for (int i = l; i <= r; i++) for (auto it : v[i]) {
2ef         vv[i > m].push_back(it);
042         Z.push_back(get<1>(it));
cbb     }
e9f     sort(vv[0].begin(), vv[0].end());
9b5     sort(vv[1].begin(), vv[1].end());
0d1     sort(Z.begin(), Z.end());
573     auto get_z = [&](int z) { return lower_bound(Z.begin(),
Z.end(), z) - Z.begin(); };
c51     vector<int> bit(Z.size());

181     int i = 0;
e9a     for (auto [y, z, id] : vv[1]) {
6bd         while (i < vv[0].size() and get<0>(vv[0][i]) < y) {
397             auto [y2, z2, id2] = vv[0][i++];
ea0             for (int p = get_z(z2)+1; p <= Z.size(); p += p&-p)
300                 bit[p-1] = max(bit[p-1], dp[id2]);
cbb         }
d3b         int q = 0;
fd9         for (int p = get_z(z); p; p -= p&-p) q = max(q,
bit[p-1]);
614         dp[id] = max(dp[id], q + 1);
cbb     }
c25     lis2d(v, dp, m+1, r);
cbb }

4de vector<int> solve(vector<tuple<int, int, int>> v) {
3d2     int n = v.size();
cd4     vector<tuple<int, int, int, int>> vv;
603     for (int i = 0; i < n; i++) {
9be         auto [x, y, z] = v[i];
5bb         vv.emplace_back(x, y, z, i);
cbb     }
bd3     sort(vv.begin(), vv.end());

e11     vector<vector<tuple<int, int, int>>> V;

```

```

603     for (int i = 0; i < n; i++) {
a5b         int j = i;
808         V.emplace_back();
c01         while (j < n and get<0>(vv[j]) == get<0>(vv[i])) {
ba6             auto [x, y, z, id] = vv[j++];
cbb             V.back().emplace_back(y, z, id);
cbb         }
452         i = j-1;
cbb     }
388     vector<int> dp(n);
839     lis2d(V, dp, 0, V.size()-1);
898     return dp;
cbb }

```

### 3.17 Gray Code

```

// Gera uma permutacao de 0 a 2^n-1, de forma que
// duas posicoes adjacentes diferem em exatamente 1 bit
//
// 0(2^n)
// 840df4

```

```

df6 vector<int> gray_code(int n) {
73f     vector<int> ret(1<<n);
f29     for (int i = 0; i < (1<<n); i++) ret[i] = i^(i>>1);
edf     return ret;
cbb }

```

### 3.18 Half-plane intersection

```

// Cada half-plane eh identificado por uma reta e a regioao ccw a ela
//
// 0(n log n)
// f56e1c

```

```

f4f vector<pt> hp_intersection(vector<line> &v) {
9bc     deque<pt> dq = {{INF, INF}, {-INF, INF}, {-INF, -INF},
{INF, -INF}};

```

```

d41 #warning considerar trocar por compare_angle
de3     sort(v.begin(), v.end(), [&](line r, line s) { return
angle(r.q-r.p) < angle(s.q-s.p); });

```

```

5e9     for(int i = 0; i < v.size() and dq.size() > 1; i++) {
c69         pt p1 = dq.front(), p2 = dq.back();
6c6         while (dq.size() and !ccw(v[i].p, v[i].q, dq.back()))
47b             p1 = dq.back(), dq.pop_back();
0a2         while (dq.size() and !ccw(v[i].p, v[i].q, dq.front()))
7cf             p2 = dq.front(), dq.pop_front();

4d9         if (!dq.size()) break;
606         if (p1 == dq.front() and p2 == dq.back()) continue;
c9b         dq.push_back(inter(v[i], line(dq.back(), p1)));
65c         dq.push_front(inter(v[i], line(dq.front(), p2)));

fdd         if (dq.size() > 1 and dq.back() == dq.front())
dq.pop_back();
cbb     }
b2b     return vector<pt>(dq.begin(), dq.end());
cbb }

```

### 3.19 Heap Sort

```

// 0(n log n)
// 385e91

```

```

f18 void down(vector<int>& v, int n, int i) {
e1f     while ((i = 2*i+1) < n) {
583         if (i+1 < n and v[i] < v[i+1]) i++;
b27         if (v[i] < v[(i-1)/2]) break;
322         swap(v[i], v[(i-1)/2]);
cbb     }
cbb }
eb6 void heap_sort(vector<int>& v) {
3d2     int n = v.size();
61d     for (int i = n/2-1; i >= 0; i--) down(v, n, i);
917     for (int i = n-1; i > 0; i--)
37f         swap(v[0], v[i]), down(v, i, 0);
cbb }

```

### 3.20 Inversion Count

```

// Computa o numero de inversoes para transformar
// l em r (se nao tem como, retorna -1)

```

```

//
// O(n log(n))
// eef01f

37b template<typename T> ll inv_count(vector<T> l, vector<T> r =
    {}){
bb6     if (!r.size()) {
796         r = l;
1bc         sort(r.begin(), r.end());
cbb     }
874     int n = l.size();
8c0     vector<int> v(n), bit(n);
4e9     vector<pair<T, int>> w;
61c     for (int i = 0; i < n; i++) w.push_back({r[i], i+1});
d1d     sort(w.begin(), w.end());
603     for (int i = 0; i < n; i++) {
bf3         auto it = lower_bound(w.begin(), w.end(),
make_pair(l[i], 0));
1bf         if (it == w.end() or it->first != l[i]) return -1; //
nao da
962         v[i] = it->second;
6c0         it->second = -1;
cbb     }

04b     ll ans = 0;
45b     for (int i = n-1; i >= 0; i--) {
2d9         for (int j = v[i]-1; j >= 0; j -= j&-j) ans += bit[j];
3a1         for (int j = v[i]; j < n; j += j&-j) bit[j]++;
cbb     }
ba7     return ans;
cbb }

```

### 3.21 LIS - Longest Increasing Subsequence

```

// Calcula e retorna uma LIS
//
// O(n.log(n))
// 4749e8

```

```

121 template<typename T> vector<T> lis(vector<T>& v) {
1fa     int n = v.size(), m = -1;
f0c     vector<T> d(n+1, INF);
aec     vector<int> l(n);
007     d[0] = -INF;

```

```

603     for (int i = 0; i < n; i++) {
        // Para non-decreasing use upper_bound()
4fd         int t = lower_bound(d.begin(), d.end(), v[i]) -
d.begin();
3ad         d[t] = v[i], l[i] = t, m = max(m, t);
cbb     }

4ff     int p = n;
5a9     vector<T> ret;
cdf     while (p-->0) if (l[p] == m) {
883         ret.push_back(v[p]);
76b         m--;
cbb     }
969     reverse(ret.begin(), ret.end());

edf     return ret;
cbb }

```

### 3.22 LIS2 - Longest Increasing Subsequence

```

// Calcula o tamanho da LIS
//
// O(n log(n))
// 402def

```

```

84b template<typename T> int lis(vector<T> &v){
2da     vector<T> ans;
5e0     for (T t : v){
        // Para non-decreasing use upper_bound()
fe6         auto it = lower_bound(ans.begin(), ans.end(), t);
d7f         if (it == ans.end()) ans.push_back(t);
b94         else *it = t;
cbb     }
1eb     return ans.size();
cbb }

```

### 3.23 Minimum Enclosing Circle

```

// O(n) com alta probabilidade
// b0a6ba

```

```

22c const double EPS = 1e-12;
878 mt19937 rng((int)
    chrono::steady_clock::now().time_since_epoch().count());

b2a struct pt {
662     double x, y;
be7     pt(double x_ = 0, double y_ = 0) : x(x_), y(y_) {}
7af     pt operator + (const pt& p) const { return pt(x+p.x,
    y+p.y); }
b23     pt operator - (const pt& p) const { return pt(x-p.x,
    y-p.y); }
254     pt operator * (double c) const { return pt(x*c, y*c); }
701     pt operator / (double c) const { return pt(x/c, y/c); }
214 };

2f9 double dot(pt p, pt q) { return p.x*q.x+p.y*q.y; }
dd5 double cross(pt p, pt q) { return p.x*q.y-p.y*q.x; }
e7c double dist(pt p, pt q) { return sqrt(dot(p-q, p-q)); }

3f4 pt center(pt p, pt q, pt r) {
5d9     pt a = p-r, b = q-r;
e84     pt c = pt(dot(a, p+r)/2, dot(b, q+r)/2);
e01     return pt(cross(c, pt(a.y, b.y)), cross(pt(a.x, b.x), c)) /
    cross(a, b);
cbb }

aa8 struct circle {
f41     pt cen;
c12     double r;
898     circle(pt cen_, double r_) : cen(cen_), r(r_) {}
83c     circle(pt a, pt b, pt c) {
13d         cen = center(a, b, c);
1f1         r = dist(cen, a);
cbb     }
cd5     bool inside(pt p) { return dist(p, cen) < r+EPS; }
214 };

806 circle minCirc(vector<pt> v) {
f21     shuffle(v.begin(), v.end(), rng);
ae0     circle ret = circle(pt(0, 0), 0);
618     for (int i = 0; i < v.size(); i++) if (!ret.inside(v[i])) {
16a         ret = circle(v[i], 0);
f11         for (int j = 0; j < i; j++) if (!ret.inside(v[j])) {
881             ret = circle((v[i]+v[j])/2, dist(v[i], v[j])/2);
b8c             for (int k = 0; k < j; k++) if (!ret.inside(v[k]))
43f                 ret = circle(v[i], v[j], v[k]);

```

```

cbb     }
cbb     }
edf     return ret;
cbb }

```

### 3.24 Minkowski Sum

```

// Computa A+B = {a+b : a \in A, b \in B}, em que
// A e B sao poligonos convexos
// A+B eh um poligono convexo com no max |A|+|B| pontos
//
// O(|A|+|B|)

// d7cca8
539 vector<pt> minkowski(vector<pt> p, vector<pt> q) {
051     auto fix = [](vector<pt>& P) {
515         rotate(P.begin(), min_element(P.begin(), P.end()),
    P.end());
018         P.push_back(P[0]), P.push_back(P[1]);
214     };
889     fix(p), fix(q);
8af     vector<pt> ret;
692     int i = 0, j = 0;
2ee     while (i < p.size()-2 or j < q.size()-2) {
898         ret.push_back(p[i] + q[j]);
732         auto c = ((p[i+1] - p[i]) ^ (q[j+1] - q[j]));
ebc         if (c >= 0) i = min<int>(i+1, p.size()-2);
81e         if (c <= 0) j = min<int>(j+1, q.size()-2);
cbb     }
edf     return ret;
cbb }

// 2f5dd2
c3e ld dist_convex(vector<pt> p, vector<pt> q) {
dc2     for (pt& i : p) i = i * -1;
44c     auto s = minkowski(p, q);
95d     if (inpol(s, pt(0, 0))) return 0;
6a5     return 1;
921     ld ans = DINF;
073     for (int i = 0; i < s.size(); i++) ans = min(ans,
f04         disttoseg(pt(0, 0), line(s[(i+1)%s.size()], s[i])));
ba7     return ans;
cbb }

```

### 3.25 MO - DSU

```
// Dado uma lista de arestas de um grafo, responde
// para cada query(l, r), quantos componentes conexos
// o grafo tem se soh considerar as arestas l, l+1, ..., r
// Da pra adaptar pra usar MO com qualquer estrutura rollbackavel
//
// O(m sqrt(q) log(n))
// f98540

8d3 struct dsu {
553     int n, ans;
2e3     vector<int> p, sz;
ee6     stack<int> S;

4b8     dsu(int n_) : n(n_), ans(n), p(n), sz(n) {
8a6         for (int i = 0; i < n; i++) p[i] = i, sz[i] = 1;
cbb     }
1b1     int find(int k) {
006         while (p[k] != k) k = p[k];
839         return k;
cbb     }
553     void add(pair<int, int> x) {
700         int a = x.first, b = x.second;
605         a = find(a), b = find(b);
843         if (a == b) return S.push(-1);
e7d         ans--;
3c6         if (sz[a] > sz[b]) swap(a, b);
4c2         S.push(a);
582         sz[b] += sz[a];
84b         p[a] = b;
cbb     }
35c     int query() { return ans; }
5cf     void rollback() {
465         int u = S.top(); S.pop();
61c         if (u == -1) return;
270         sz[p[u]] -= sz[u];
546         p[u] = u;
0df         ans++;
cbb     }
214 };

1a8 int n;
e93 vector<pair<int, int>> ar; // vetor com as arestas

617 vector<int> MO(vector<pair<int, int>> &q) {
```

```
d4d     int SQ = ar.size() / sqrt(q.size()) + 1;
c23     int m = q.size();
3f8     vector<int> ord(m);
be8     iota(ord.begin(), ord.end(), 0);
d01     sort(ord.begin(), ord.end(), [&](int l, int r) {
9c9         if (q[l].first / SQ != q[r].first / SQ) return
q[l].first < q[r].first;
a66         return q[l].second < q[r].second;
c0c     });
435     vector<int> ret(m);

dd5     for (int i = 0; i < m; i++) {
176         dsu D(n);
ae9         int fim = q[ord[i]].first/SQ*SQ + SQ - 1;
e25         int last_r = fim;
ebc         int j = i-1;
00c         while (j+1 < m and q[ord[j+1]].first / SQ ==
q[ord[i]].first / SQ) {
a0e             auto [l, r] = q[ord[++j]];

acc             if (l / SQ == r / SQ) {
ce9                 dsu D2(n);
495                 for (int k = l; k <= r; k++) D2.add(ar[k]);
fdf                 ret[ord[j]] = D2.query();
5e2                 continue;
cbb             }

59b             while (last_r < r) D.add(ar[++last_r]);
2cf             for (int k = l; k <= fim; k++) D.add(ar[k]);

9b2             ret[ord[j]] = D.query();

572             for (int k = l; k <= fim; k++) D.rollback();
cbb         }
bdf         i = j;
cbb     }
edf     return ret;
cbb }
```

### 3.26 Mo - numero de distintos em range

```
// Para ter o bound abaixo, escolher
// SQ = n / sqrt(q)
//
```



```

// 0(n * sqrt(q))
// e94f60

0d2 const int MAX = 1e5+10;
6ff const int SQ = sqrt(MAX);
b69 int v[MAX];

b65 int ans, freq[MAX];

9da inline void insert(int p) {
ae0     int o = v[p];
591     freq[o]++;
992     ans += (freq[o] == 1);
cbb }

a25 inline void erase(int p) {
ae0     int o = v[p];
7ee     ans -= (freq[o] == 1);
ba2     freq[o]--;
cbb }

e51 inline ll hilbert(int x, int y) {
71e     static int N = 1 << (__builtin_clz(0) - __builtin_clz(MAX));
100     int rx, ry, s;
b72     ll d = 0;
43b     for (s = N/2; s > 0; s /= 2) {
c95         rx = (x & s) > 0, ry = (y & s) > 0;
e3e         d += s * ll(s) * ((3 * rx) ^ ry);
d2e         if (ry == 0) {
5aa             if (rx == 1) x = N-1 - x, y = N-1 - y;
9dd             swap(x, y);
cbb         }
cbb     }
be2     return d;
cbb }

bac #define HILBERT true
617 vector<int> M0(vector<pair<int, int>> &q) {
c3b     ans = 0;
c23     int m = q.size();
3f8     vector<int> ord(m);
be8     iota(ord.begin(), ord.end(), 0);
6a6 #if HILBERT
8c4     vector<ll> h(m);
74c     for (int i = 0; i < m; i++) h[i] = hilbert(q[i].first,
q[i].second);

```

```

075     sort(ord.begin(), ord.end(), [&](int l, int r) { return
h[l] < h[r]; });
8c1 #else
d01     sort(ord.begin(), ord.end(), [&](int l, int r) {
9c9         if (q[l].first / SQ != q[r].first / SQ) return
q[l].first < q[r].first;
0db         if ((q[l].first / SQ) % 2) return q[l].second >
q[r].second;
a66         return q[l].second < q[r].second;
c0c     });
f2e #endif
435     vector<int> ret(m);
3d9     int l = 0, r = -1;

8b0     for (int i : ord) {
6c6         int ql, qr;
4f5         tie(ql, qr) = q[i];
026         while (r < qr) insert(++r);
232         while (l > ql) insert(--l);
75e         while (l < ql) erase(l++);
fe8         while (r > qr) erase(r--);
381         ret[i] = ans;
cbb     }
edf     return ret;
cbb }

```

### 3.27 Palindromic Factorization

```

// Precisa da eertree
// Computa o numero de formas de particionar cada
// prefixo da string em strings palindromicas
//
// 0(n log n), considerando alfabeto 0(1)
// 9e6e22

070 struct eertree { ... };

0e7 ll factorization(string s) {
b19     int n = s.size(), sz = 2;
580     eertree PT(n);
147     vector<int> diff(n+2), slink(n+2), sans(n+2), dp(n+1);
0ec     dp[0] = 1;
78a     for (int i = 1; i <= n; i++) {
c58         PT.add(s[i-1]);

```

```

a7c     if (PT.size()+2 > sz) {
6c4         diff[sz] = PT.len[sz] - PT.len[PT.link[sz]];
241         if (diff[sz] == diff[PT.link[sz]])
d6f             slink[sz] = slink[PT.link[sz]];
f53         else slink[sz] = PT.link[sz];
eb9         sz++;
cbb     }
911     for (int v = PT.last; PT.len[v] > 0; v = slink[v]) {
297         sans[v] = dp[i - (PT.len[slink[v]] + diff[v])];
85d         if (diff[v] == diff[PT.link[v]])
f20             sans[v] = (sans[v] + sans[PT.link[v]]) % MOD;
071         dp[i] = (dp[i] + sans[v]) % MOD;
cbb     }
cbb     }
5f0     return dp[n];
cbb }

```

## 3.28 Parsing de Expressao

```

// Operacoes associativas a esquerda por default
// Para mudar isso, colocar em r_assoc
// Operacoes com maior prioridade sao feitas primeiro
//
// 9ad15a

```

```

cc1 bool blank(char c) {
f34     return c == ' ';
cbb }

8e4 bool is_unary(char c) {
f9c     return c == '+' or c == '-';
cbb }

76d bool is_op(char c) {
010     if (is_unary(c)) return true;
31c     return c == '*' or c == '/' or c == '+' or c == '-';
cbb }

fa3 bool r_assoc(char op) {
// operator unario - deve ser assoc. a direita
cf0     return op < 0;
cbb }

79d int priority(char op) {

```

```

// operator unario - deve ter precedencia maior
103     if (op < 0) return INF;

727     if (op == '*' or op == '/') return 2;
439     if (op == '+' or op == '-') return 1;
daa     return -1;
cbb }

c15 void process_op(stack<int>& st, stack<int>& op) {
88c     char o = op.top(); op.pop();
91c     if (o < 0) {
4e6         o *= -1;
1e2         int l = st.top(); st.pop();
0ff         if (o == '+') st.push(l);
7e9         if (o == '-') st.push(-l);
9d9     } else {
14c         int r = st.top(); st.pop();
1e2         int l = st.top(); st.pop();
1e4         if (o == '*') st.push(l * r);
f55         if (o == '/') st.push(l / r);
605         if (o == '+') st.push(l + r);
c40         if (o == '-') st.push(l - r);
cbb     }
cbb }

439 int eval(string& s) {
212     stack<int> st, op;
d0c     bool un = true;
1cf     for (int i = 0; i < s.size(); i++) {
68d         if (blank(s[i])) continue;

139         if (s[i] == '(') {
367             op.push('(');
99d             un = true;
130         } else if (s[i] == ')') {
709             while (op.top() != '(') process_op(st, op);
75e             op.pop();
ce2             un = false;
146         } else if (is_op(s[i])) {
4d0             char o = s[i];
37c             if (un and is_unary(o)) o *= -1;
ae3             while (op.size() and (
cd6                 (!r_assoc(o) and priority(op.top()) >=
priority(o)) or
c41                 (r_assoc(o) and priority(op.top()) >
priority(o))))

```

```

c47         process_op(st, op);
c00         op.push(o);
99d         un = true;
9d9     } else {
da8         int val = 0;
c2b         while (i < s.size() and isalnum(s[i]))
8a3             val = val * 10 + s[i++] - '0';
169         i--;
25d         st.push(val);
ce2         un = false;
cbb     }
cbb }

```

```

7f6     while (op.size()) process_op(st, op);
123     return st.top();
cbb }

```

## 3.29 RMQ com Divide and Conquer

```

// Responde todas as queries em
// O(n log(n))
// 5a6ebd

```

```

f74 typedef pair<pair<int, int>, int> iii;
7c6 #define f first
0ab #define s second

```

```

87d int n, q, v[MAX];
e3f iii qu[MAX];
aeb int ans[MAX], pref[MAX], sulf[MAX];

0e3 void solve(int l=0, int r=n-1, int ql=0, int qr=q-1) {
8a3     if (l > r or ql > qr) return;
ee4     int m = (l+r)/2;
1b1     int qL = partition(qu+ql, qu+qr+1, [=](iii x){return x.f.s
< m;}) - qu;
eb0     int qR = partition(qu+qL, qu+qr+1, [=](iii x){return x.f.f
<=m;}) - qu;

```

```

3cd     pref[m] = sulf[m] = v[m];
9f9     for (int i = m-1; i >= l; i--) pref[i] = min(v[i],
pref[i+1]);
ea8     for (int i = m+1; i <= r; i++) sulf[i] = min(v[i],
sulf[i-1]);

```

```

b2a     for (int i = qL; i < qR; i++)
f3a         ans[qu[i].s] = min(pref[qu[i].f.f], sulf[qu[i].f.s]);

364     solve(l, m-1, ql, qL-1), solve(m+1, r, qR, qr);
cbb }

```

## 3.30 Segment Intersection

```

// Verifica, dado n segmentos, se existe algum par de segmentos
// que se intersecta
//
// O(n log n)
// 3957d8

```

```

6e0 bool operator< (const line& a, const line& b) { // comparador
pro sweepline
191     if (a.p == b.p) return ccw(a.p, a.q, b.q);
231     if (!eq(a.p.x, a.q.x) and (eq(b.p.x, b.q.x) or a.p.x+eps <
b.p.x))
780         return ccw(a.p, a.q, b.p);
dc0     return ccw(a.p, b.q, b.p);
cbb }

```

```

8e2 bool has_intersection(vector<line> v) {
576     auto intersects = [&](pair<line, int> a, pair<line, int> b)
{
a08         return interseg(a.first, b.first);
214     };
e1b     vector<pair<pt, pair<int, int>>> w;
f14     for (int i = 0; i < v.size(); i++) {
876         if (v[i].q < v[i].p) swap(v[i].p, v[i].q);
e1d         w.push_back({v[i].p, {0, i}});
034         w.push_back({v[i].q, {1, i}});
cbb     }
d1d     sort(w.begin(), w.end());
7f2     set<pair<line, int>> se;
e58     for (auto i : w) {
bfd         line at = v[i.second.second];
292         if (i.second.first == 0) {
145             auto nxt = se.lower_bound({at, i.second.second});
d1e             if (nxt != se.end() and intersects(*nxt, {at,
i.second.second})) return 1;

```

```

257         if (nxt != se.begin() and intersects(*(--nxt), {at,
i.second.second})) return 1;
78f         se.insert({at, i.second.second});
9d9     } else {
884         auto nxt = se.upper_bound({at, i.second.second}),
cur = nxt, prev = --cur;
b64         if (nxt != se.end() and prev != se.begin()
4fb             and intersects(*nxt, *(--prev))) return 1;
cca             se.erase(cur);
cbb     }
cbb     }
bb3     return 0;
cbb }

```

### 3.31 Sequencia de de Bruijn

```

// Se passar sem o terceiro parametro, gera um vetor com valores
// em [0, k) de tamanho k^n de forma que todos os subarrays ciclicos
// de tamanho n ocorrem exatamente uma vez
// Se passar com um limite lim, gera o menor vetor com valores
// em [0, k) que possui lim subarrays de tamanho n distintos
// (assume que lim <= k^n)
//
// Linear no tamanho da resposta
// 19720c

860 vector<int> de_bruijn(int n, int k, int lim = INF) {
b55     if (k == 1) return vector<int>(lim == INF ? 1 : n, 0);
5f6     vector<int> l = {0}, ret; // l eh lyndon word
667     while (true) {
c86         if (l.size() == 0) {
1b9             if (lim == INF) break;
d4f             l.push_back(0);
cbb         }
686         if (n % l.size() == 0) for (int i : l) {
728             ret.push_back(i);
c99             if (ret.size() == n+lim-1) return ret;
cbb         }
630         int p = l.size();
905         while (l.size() < n) l.push_back(l[l.size()%p]);
e7f         while (l.size() and l.back() == k-1) l.pop_back();
88a         if (l.size()) l.back()++;
cbb     }
edf     return ret;

```

cbb }

### 3.32 Shortest Addition Chain

```

// Computa o menor numero de adicoes para construir
// cada valor, começando com 1 (e podendo salvar variaveis)
// Retorna um par com a dp e o pai na arvore
// A arvore eh tao que o tamanho da raiz (1) ate x
// contem os valores que devem ser criados para gerar x
// A profundidade de x na arvore eh dp[x]
// DP funciona para ateh 300, mas a arvore soh funciona
// para ateh 148
//
// 84fcff

// recuperacao certa soh ateh 148 (erra para 149, 233, 298)
3de pair<vector<int>, vector<int>> addition_chain() {
16f     int MAX = 301;
875     vector<int> dp(MAX), p(MAX);
1ab     for (int n = 2; n < MAX; n++) {
7c0         pair<int, int> val = {INF, -1};
212         for (int i = 1; i < n; i++) for (int j = i; j; j = p[j])
94a             if (j == n-i) val = min(val, pair(dp[i]+1, i));
eb3         tie(dp[n], p[n]) = val;
efe         if (n == 9) p[n] = 8;
ba1         if (n == 149 or n == 233) dp[n]--;
cbb     }
717     return {dp, p};
cbb }

```

### 3.33 Simple Polygon

```

// Verifica se um poligono com n pontos eh simples
//
// O(n log n)
// c724a4

6e0 bool operator < (const line& a, const line& b) { // comparador
    pro sweepline
191     if (a.p == b.p) return ccw(a.p, a.q, b.q);
231     if (!eq(a.p.x, a.q.x) and (eq(b.p.x, b.q.x) or a.p.x+eps <
        b.p.x))

```

```

780         return ccw(a.p, a.q, b.p);
dc0     return ccw(a.p, b.q, b.p);
cbb }

6f3 bool simple(vector<pt> v) {
576     auto intersects = [&](pair<line, int> a, pair<line, int> b)
{
e72         if ((a.second+1)%v.size() == b.second or
80e             (b.second+1)%v.size() == a.second) return false;
a08         return interseg(a.first, b.first);
214     };
41a     vector<line> seg;
e1b     vector<pair<pt, pair<int, int>>> w;
f14     for (int i = 0; i < v.size(); i++) {
0a8         pt at = v[i], nxt = v[(i+1)%v.size()];
828         if (nxt < at) swap(at, nxt);
937         seg.push_back(line(at, nxt));
f7e         w.push_back({at, {0, i}});
69c         w.push_back({nxt, {1, i}});
// casos degenerados estranhos
ae8         if (isinseg(v[(i+2)%v.size()], line(at, nxt))) return 0;
88d         if (isinseg(v[(i+v.size()-1)%v.size()], line(at, nxt)))
return 0;
cbb     }
d1d     sort(w.begin(), w.end());
7f2     set<pair<line, int>> se;
e58     for (auto i : w) {
ff8         line at = seg[i.second.second];
292         if (i.second.first == 0) {
145             auto nxt = se.lower_bound({at, i.second.second});
7c4             if (nxt != se.end() and intersects(*nxt, {at,
i.second.second})) return 0;
b34             if (nxt != se.begin() and intersects(*(--nxt), {at,
i.second.second})) return 0;
78f             se.insert({at, i.second.second});
9d9         } else {
884             auto nxt = se.upper_bound({at, i.second.second}),
cur = nxt, prev = --cur;
b64             if (nxt != se.end() and prev != se.begin()
403                 and intersects(*nxt, *(--prev))) return 0;
cca             se.erase(cur);
cbb         }
cbb     }
6a5     return 1;
cbb }

```

### 3.34 Sweep Direction

```

// Passa por todas as ordenacoes dos pontos definitas por "direcoes"
// Assume que nao existem pontos coincidentes
//
// 0(n^2 log n)
// 6bb68d

4b8 void sweep_direction(vector<pt> v) {
3d2     int n = v.size();
163     sort(v.begin(), v.end(), [](pt a, pt b) {
3a5         if (a.x != b.x) return a.x < b.x;
572         return a.y > b.y;
c0c     });
b89     vector<int> at(n);
516     iota(at.begin(), at.end(), 0);
b79     vector<pair<int, int>> swapp;
25e     for (int i = 0; i < n; i++) for (int j = i+1; j < n; j++)
95f         swapp.push_back({i, j}), swapp.push_back({j, i});

269     sort(swapp.begin(), swapp.end(), [&](auto a, auto b) {
134         pt A = rotate90(v[a.first] - v[a.second]);
247         pt B = rotate90(v[b.first] - v[b.second]);
615         if (quad(A) == quad(B) and !sarea2(pt(0, 0), A, B))
return a < b;
224         return compare_angle(A, B);
c0c     });
4e6     for (auto par : swapp) {
e24         assert(abs(at[par.first] - at[par.second]) == 1);
a96         int l = min(at[par.first], at[par.second]),
0d3         r = n-1 - max(at[par.first], at[par.second]);
// l e r sao quantos caras tem de cada lado do par de
// pontos
// (cada par eh visitado duas vezes)
9cf         swap(v[at[par.first]], v[at[par.second]]);
1c0         swap(at[par.first], at[par.second]);
cbb     }
cbb }

```

### 3.35 Triangulacao de Delaunay

```

// Computa a triangulacao de Delaunay, o dual
// do diagrama de Voronoi (a menos de casos degenerados)
// Retorna um grafo indexado pelos indices dos pontos, e as arestas

```

```

// sao as arestas da triangulacao
// As arestas partindo de um vertice ja vem ordenadas por angulo,
// ou seja, se o vertice v nao esta no convex hull, (v, v_i,
//   v_{i+1})
// eh um triangulo da triangulacao, em que v_i eh o i-esimo vizinho
// Usa o alg d&c, precisa representar MAX_COORD^4, por isso __int128
// pra aguentar valores ateh 1e9
//
// Propriedades:
// 1 - O grafo tem no max 3n-6 arestas
// 2 - Para todo triangulo, a circunf. que passa pelos 3 pontos
//     nao contem estritamente nenhum ponto
// 3 - A MST euclidiana eh subgrafo desse grafo
// 4 - Cada ponto eh vizinho do ponto mais proximo dele
//
// O(n log n)
// 362c83

2ad typedef struct QuadEdge* Q;
ba5 struct QuadEdge {
53e     int id;
114     pt o;
41e     Q rot, nxt;
3e5     bool used;

3fc     QuadEdge(int id_ = -1, pt o_ = pt(INF, INF)) :
4ba         id(id_), o(o_), rot(nullptr), nxt(nullptr), used(false)
        {}

00f     Q rev() const { return rot->rot; }
c3c     Q next() const { return nxt; }
188     Q prev() const { return rot->next()->rot; }
0d4     pt dest() const { return rev()->o; }
214 };

91b Q edge(pt from, pt to, int id_from, int id_to) {
c6e     Q e1 = new QuadEdge(id_from, from);
61b     Q e2 = new QuadEdge(id_to, to);
8f6     Q e3 = new QuadEdge;
5ca     Q e4 = new QuadEdge;
e69     tie(e1->rot, e2->rot, e3->rot, e4->rot) = {e3, e4, e2, e1};
f22     tie(e1->nxt, e2->nxt, e3->nxt, e4->nxt) = {e1, e2, e4, e3};
1ad     return e1;
cbb }

d8d void splice(Q a, Q b) {

```

```

a6f     swap(a->nxt->rot->nxt, b->nxt->rot->nxt);
da4     swap(a->nxt, b->nxt);
cbb }

167 void del_edge(Q& e, Q ne) { // delete e and assign e <- ne
cc0     splice(e, e->prev());
eec     splice(e->rev(), e->rev()->prev());
7ea     delete e->rev()->rot, delete e->rev();
524     delete e->rot; delete e;
6b2     e = ne;
cbb }

d08 Q conn(Q a, Q b) {
cc5     Q e = edge(a->dest(), b->o, a->rev()->id, b->id);
f2b     splice(e, a->rev()->prev());
d37     splice(e->rev(), b);
6bf     return e;
cbb }

d64 bool in_c(pt a, pt b, pt c, pt p) { // p ta na circunf. (a, b,
c) ?
268     __int128 p2 = p*p, A = a*a - p2, B = b*b - p2, C = c*c - p2;
cbe     return sarea2(p, a, b) * C + sarea2(p, b, c) * A +
        sarea2(p, c, a) * B > 0;
cbb }

540 pair<Q, Q> build_tr(vector<pt>& p, int l, int r) {
09d     if (r-l+1 <= 3) {
2eb         Q a = edge(p[l], p[l+1], l, l+1), b = edge(p[l+1],
p[r], l+1, r);
912         if (r-l+1 == 2) return {a, a->rev()};
0ec         splice(a->rev(), b);
c3c         ll ar = sarea2(p[l], p[l+1], p[r]);
1af         Q c = ar ? conn(b, a) : 0;
021         if (ar >= 0) return {a, b->rev()};
9db         return {c->rev(), c};
cbb     }
ee4     int m = (l+r)/2;
328     auto [la, ra] = build_tr(p, l, m);
b93     auto [lb, rb] = build_tr(p, m+1, r);
667     while (true) {
b99         if (ccw(lb->o, ra->o, ra->dest())) ra =
ra->rev()->prev();
458         else if (ccw(lb->o, ra->o, lb->dest())) lb =
lb->rev()->next();
f97         else break;

```

```

cbb      }
ca5      Q b = conn(lb->rev(), ra);
713      auto valid = [&](Q e) { return ccw(e->dest(), b->dest(),
b->o); };
ee1      if (ra->o == la->o) la = b->rev();
63f      if (lb->o == rb->o) rb = b;
667      while (true) {
71e          Q L = b->rev()->next();
d11          if (valid(L)) while (in_c(b->dest(), b->o, L->dest(),
L->next()->dest()))
1c0              del_edge(L, L->next());
c76          Q R = b->prev();
2b0          if (valid(R)) while (in_c(b->dest(), b->o, R->dest(),
R->prev()->dest()))
541              del_edge(R, R->prev());
a3a          if (!valid(L) and !valid(R)) break;
ccd          if (!valid(L) or (valid(R) and in_c(L->dest(), L->o,
R->o, R->dest())))
36c              b = conn(R, b->rev());
666          else b = conn(b->rev(), L->rev());
cbb      }
a2b      return {la, rb};
cbb }

```

```

b58 vector<vector<int>> delaunay(vector<pt> v) {
3d2     int n = v.size();
397     auto tmp = v;
135     vector<int> idx(n);
295     iota(idx.begin(), idx.end(), 0);
fe9     sort(idx.begin(), idx.end(), [&](int l, int r) { return
v[l] < v[r]; });
5d8     for (int i = 0; i < n; i++) v[i] = tmp[idx[i]];
780     assert(unique(v.begin(), v.end()) == v.end());
4aa     vector<vector<int>> g(n);
4ec     bool col = true;
a96     for (int i = 2; i < n; i++) if (sarea2(v[i], v[i-1],
v[i-2])) col = false;
bf5     if (col) {
aa4         for (int i = 1; i < n; i++)
839             g[idx[i-1]].push_back(idx[i]),
g[idx[i]].push_back(idx[i-1]);
96b         return g;
cbb     }
d36     Q e = build_tr(v, 0, n-1).first;
113     vector<Q> edg = {e};
5d1     for (int i = 0; i < edg.size(); e = edg[i++]) {

```

```

3ed         for (Q at = e; !at->used; at = at->next()) {
60d             at->used = true;
cf8             g[idx[at->id]].push_back(idx[at->rev()->id]);
15d             edg.push_back(at->rev());
cbb         }
cbb     }
96b     return g;
cbb }

```

### 3.36 Triangulos em Grafos

```

// get_triangles(i) encontra todos os triangulos ijk no grafo
// Custo nas arestas
// retorna {custo do triangulo, {j, k}}
//
// O(m sqrt(m) log(n)) se chamar para todos os vertices
// fladbc

```

```

c0d vector<pair<int, int>> g[MAX]; // {para, peso}

```

```

d41 #warning o 'g' deve estar ordenado
9a5 vector<pair<int, pair<int, int>>> get_triangles(int i) {
771     vector<pair<int, pair<int, int>>> tri;
b23     for (pair<int, int> j : g[i]) {
2b3         int a = i, b = j.first;
6dd         if (g[a].size() > g[b].size()) swap(a, b);
eb0         for (pair<int, int> c : g[a]) if (c.first != b and
c.first > j.first) {
525             auto it = lower_bound(g[b].begin(), g[b].end(),
make_pair(c.first, -INF));
f55             if (it == g[b].end() or it->first != c.first)
continue;
0aa             tri.push_back({j.second+c.second+it->second, {a ==
i ? b : a, c.first}});
cbb         }
cbb     }
f5e     return tri;
cbb }

```

## 4 Strings

### 4.1 Aho-corasick

```
// query retorna o somatorio do numero de matches de
// todas as stringuinhas na stringona
//
// insert - O(|s| log(SIGMA))
// build - O(N), onde N = somatorio dos tamanhos das strings
// query - O(|s|)
// a30d6e

ea1 namespace aho {
807     map<char, int> to[MAX];
c87     int link[MAX], idx, term[MAX], exit[MAX], sobe[MAX];

bfc     void insert(string& s) {
05e         int at = 0;
b4f         for (char c : s) {
b68             auto it = to[at].find(c);
1c9             if (it == to[at].end()) at = to[at][c] = ++idx;
361             else at = it->second;
cbb         }
142         term[at]++, sobe[at]++;
cbb     }
d41 #warning nao esquece de chamar build() depois de inserir
0a8     void build() {
26a         queue<int> q;
537         q.push(0);
dff         link[0] = exit[0] = -1;
402         while (q.size()) {
379             int i = q.front(); q.pop();
3c4             for (auto [c, j] : to[i]) {
5da                 int l = link[i];
102                 while (l != -1 and !to[l].count(c)) l = link[l];
7a5                 link[j] = l == -1 ? 0 : to[l][c];
3ab                 exit[j] = term[link[j]] ? link[j] :
exit[link[j]];
6f2                 if (exit[j]+1) sobe[j] += sobe[exit[j]];
113                 q.push(j);
cbb             }
cbb         }
cbb     }
bc0     int query(string& s) {
86d         int at = 0, ans = 0;
```

```
b4f         for (char c : s){
1ca             while (at != -1 and !to[at].count(c)) at = link[at];
5b9             at = at == -1 ? 0 : to[at][c];
2b1             ans += sobe[at];
cbb         }
ba7         return ans;
cbb     }
cbb }
```

### 4.2 Algoritmo Z

```
// z[i] = lcp(s, s[i..n))
//
// Complexidades:
// z - O(|s|)
// match - O(|s| + |p|)
// 74a9e1

a19 vector<int> get_z(string s) {
163     int n = s.size();
2b1     vector<int> z(n, 0);

fae     int l = 0, r = 0;
6f5     for (int i = 1; i < n; i++) {
0af         if (i <= r) z[i] = min(r - i + 1, z[i - 1]);
457         while (i + z[i] < n and s[z[i]] == s[i + z[i]]) z[i]++;
65e         if (i + z[i] - 1 > r) l = i, r = i + z[i] - 1;
cbb     }

070     return z;
cbb }
```

### 4.3 Automato de Sufixo

```
// Automato que aceita os sufixos de uma string
// Todas as funcoes sao lineares
// c37a72

16e namespace sam {
c1a     int cur, sz, len[2*MAX], link[2*MAX], acc[2*MAX];
0b8     int nxt[2*MAX][26];
```



```

e6a void add(int c) {
17a int at = cur;
9a6 len[sz] = len[cur]+1, cur = sz++;
500 while (at != -1 and !nxt[at][c]) nxt[at][c] = cur, at =
link[at];
7ea if (at == -1) { link[cur] = 0; return; }
654 int q = nxt[at][c];
fd9 if (len[q] == len[at]+1) { link[cur] = q; return; }
31f int qq = sz++;
2c3 len[qq] = len[at]+1, link[qq] = link[q];
9a9 for (int i = 0; i < 26; i++) nxt[qq][i] = nxt[q][i];
e76 while (at != -1 and nxt[at][c] == q) nxt[at][c] = qq,
at = link[at];
8b8 link[cur] = link[q] = qq;
cbb }
94e void build(string& s) {
889 cur = 0, sz = 0, len[0] = 0, link[0] = -1, sz++;
9fe for (auto i : s) add(i-'a');
17a int at = cur;
121 while (at) acc[at] = 1, at = link[at];
cbb }

// coisas que da pra fazer:
28c ll distinct_substrings() {
04b ll ans = 0;
a1e for (int i = 1; i < sz; i++) ans += len[i] -
len[link[i]];
ba7 return ans;
cbb }
a6c string longest_common_substring(string& S, string& T) {
419 build(S);
111 int at = 0, l = 0, ans = 0, pos = -1;
d59 for (int i = 0; i < T.size(); i++) {
f2c while (at and !nxt[at][T[i]-'a']) at = link[at], l
= len[at];
efa if (nxt[at][T[i]-'a']) at = nxt[at][T[i]-'a'], l++;
749 else at = 0, l = 0;
a1a if (l > ans) ans = l, pos = i;
cbb }
20f return T.substr(pos-ans+1, ans);
cbb }
46e ll dp[2*MAX];
455 ll paths(int i) {
2a8 auto& x = dp[i];
dee if (x) return x;
483 x = 1;

```

```

71c for (int j = 0; j < 26; j++) if (nxt[i][j]) x +=
paths(nxt[i][j]);
ea5 return x;
cbb }
105 void kth_substring(int k, int at=0) { // k=1 : menor
substring lexicog.
9d2 for (int i = 0; i < 26; i++) if (k and nxt[at][i]) {
d58 if (paths(nxt[at][i]) >= k) {
d02 cout << char('a'+i);
c43 kth_substring(k-1, nxt[at][i]);
505 return;
cbb }
5f4 k -= paths(nxt[at][i]);
cbb }
cbb }
214 };

```

#### 4.4 eertree

```

// Constroi a eertree, caractere a caractere
// Inicializar com a quantidade de caracteres maxima
// size() retorna a quantidade de substrings pal. distintas
// depois de chamar propagate(), cada substring palindromica
// ocorre qt[i] vezes. 0 propagate() retorna o numero de
// substrings pal. com repeticao
//
// 0(n) amortizado, considerando alfabeto 0(1)
// a2e693

8eb struct eertree {
7cc vector<vector<int>> t;
42e int n, last, sz;
745 vector<int> s, len, link, qt;

d36 eertree(int N) {
ec8 t = vector(N+2, vector(26, int()));
cee s = len = link = qt = vector<int>(N+2);
cd1 s[0] = -1;
288 link[0] = 1, len[0] = 0, link[1] = 1, len[1] = -1;
688 sz = 2, last = 0, n = 1;
cbb }

244 void add(char c) {
692 s[n++] = c -= 'a';

```

```

34f         while (s[n-len[last]-2] != c) last = link[last];
289         if (!t[last][c]) {
dab             int prev = link[last];
553             while (s[n-len[prev]-2] != c) prev = link[prev];
fb2             link[sz] = t[prev][c];
3f5             len[sz] = len[last]+2;
1f8             t[last][c] = sz++;
cbb         }
344         qt[last = t[last][c]]++;
cbb     }
f17     int size() { return sz-2; }
2af     ll propagate() {
b73         ll ret = 0;
ebb         for (int i = n; i > 1; i--) {
fd3             qt[link[i]] += qt[i];
db5             ret += qt[i];
cbb         }
edf         return ret;
cbb     }
214 };

```

## 4.5 KMP

```

// matching(s, t) retorna os indices das ocorrencias
// de s em t
// autKMP constroi o automato do KMP
//
// Complexidades:
// pi - O(n)
// match - O(n + m)
// construir o automato - O(|sigma|*n)
// n = |padrao| e m = |texto|

// f50359
ea8 template<typename T> vector<int> pi(T s) {
019     vector<int> p(s.size());
725     for (int i = 1, j = 0; i < s.size(); i++) {
a51         while (j and s[j] != s[i]) j = p[j-1];
973         if (s[j] == s[i]) j++;
f8c         p[i] = j;
cbb     }
74e     return p;
cbb }

```

```

// c82524
c10 template<typename T> vector<int> matching(T& s, T& t) {
658     vector<int> p = pi(s), match;
a1b     for (int i = 0, j = 0; i < t.size(); i++) {
6be         while (j and s[j] != t[i]) j = p[j-1];
c4d         if (s[j] == t[i]) j++;
310         if (j == s.size()) match.push_back(i-j+1), j = p[j-1];
cbb     }
ed8     return match;
cbb }

// 79bd9e
a2d struct KMPaut : vector<vector<int>>> {
47c     KMPaut(){}
6c7     KMPaut (string& s) : vector<vector<int>>>(26,
vector<int>(s.size()+1)) {
503         vector<int> p = pi(s);
04b         auto& aut = *this;
4fa         aut[s[0]-'a'][0] = 1;
19a         for (char c = 0; c < 26; c++)
5d3             for (int i = 1; i <= s.size(); i++)
42b                 aut[c][i] = s[i]-'a' == c ? i+1 :
aut[c][p[i-1]];
cbb     }
214 };

```

## 4.6 Manacher

```

// manacher recebe um vetor de T e retorna o vetor com tamanho dos
// palindromos
// ret[2*i] = tamanho do maior palindromo centrado em i
// ret[2*i+1] = tamanho maior palindromo centrado em i e i+1
//
// Complexidades:
// manacher - O(n)
// palindrome - <O(n), O(1)>
// pal_end - O(n)

// ebb184
28a template<typename T> vector<int> manacher(const T& s) {
18f     int l = 0, r = -1, n = s.size();
fc9     vector<int> d1(n), d2(n);
603     for (int i = 0; i < n; i++) {
821         int k = i > r ? 1 : min(d1[l+r-i], r-i);

```

```

61a         while (i+k < n && i-k >= 0 && s[i+k] == s[i-k]) k++;
61e         d1[i] = k--;
9f6         if (i+k > r) l = i-k, r = i+k;
cbb     }
e03     l = 0, r = -1;
603     for (int i = 0; i < n; i++) {
a64         int k = i > r ? 0 : min(d2[l+r-i+1], r-i+1); k++;
2c6         while (i+k <= n && i-k >= 0 && s[i+k-1] == s[i-k]) k++;
eaa         d2[i] = --k;
26d         if (i+k-1 > r) l = i-k, r = i+k-1;
cbb     }
c41     vector<int> ret(2*n-1);
e6b     for (int i = 0; i < n; i++) ret[2*i] = 2*d1[i]-1;
e1d     for (int i = 0; i < n-1; i++) ret[2*i+1] = 2*d2[i+1];
edf     return ret;
cbb }

// 60c6f5
// verifica se a string s[i..j] eh palindromo
cac template<typename T> struct palindrome {
f97     vector<int> man;

b2d     palindrome(const T& s) : man(manacher(s)) {}
9d7     bool query(int i, int j) {
bad         return man[i+j] >= j-i+1;
cbb     }
214 };

// 8bd4d5
// tamanho do maior palindromo que termina em cada posicao
7cb template<typename T> vector<int> pal_end(const T& s) {
e57     vector<int> ret(s.size());
fde     palindrome<T> p(s);
d51     ret[0] = 1;
88e     for (int i = 1; i < s.size(); i++) {
a32         ret[i] = min(ret[i-1]+2, i+1);
6ea         while (!p.query(i-ret[i]+1, i)) ret[i]--;
cbb     }
edf     return ret;
cbb }

```

## 4.7 Min/max suffix/cyclic shift

```
// Computa o indice do menor/maior sufixo/cyclic shift
```

```

// da string, lexicograficamente
//
// 0(n)
// af0367

016 template<typename T> int max_suffix(T s, bool mi = false) {
476     s.push_back(*min_element(s.begin(), s.end())-1);
1a4     int ans = 0;
88e     for (int i = 1; i < s.size(); i++) {
eec         int j = 0;
708         while (ans+j < i and s[i+j] == s[ans+j]) j++;
7a2         if (s[i+j] > s[ans+j]) {
b52             if (!mi or i != s.size()-2) ans = i;
c05         } else if (j) i += j-1;
cbb     }
ba7     return ans;
cbb }

a1a template<typename T> int min_suffix(T s) {
76b     for (auto& i : s) i *= -1;
09d     s.push_back(*max_element(s.begin(), s.end())+1);
925     return max_suffix(s, true);
cbb }

97c template<typename T> int max_cyclic_shift(T s) {
163     int n = s.size();
1ad     for (int i = 0; i < n; i++) s.push_back(s[i]);
20a     return max_suffix(s);
cbb }

08a template<typename T> int min_cyclic_shift(T s) {
76b     for (auto& i : s) i *= -1;
7be     return max_cyclic_shift(s);
cbb }

```

## 4.8 String Hashing

```

// Complexidades:
// construtor - O(|s|)
// operator() - O(1)
// 918dfb

878 mt19937 rng((int)
    chrono::steady_clock::now().time_since_epoch().count());

```

```

463 int uniform(int l, int r) {
a7f     uniform_int_distribution<int> uid(l, r);
f54     return uid(rng);
cbb }

9e0 template<int MOD> struct str_hash { // 116fcb
c63     static int P;
dcf     vector<ll> h, p;
ea8     str_hash(string s) : h(s.size()), p(s.size()) {
7a2         p[0] = 1, h[0] = s[0];
ad7         for (int i = 1; i < s.size(); i++)
84c             p[i] = p[i - 1]*P%MOD, h[i] = (h[i - 1]*P +
s[i])%MOD;
cbb     }
af7     ll operator()(int l, int r) { // retorna hash s[l...r]
749         ll hash = h[r] - (l ? h[l - 1]*p[r - l + 1]%MOD : 0);
dfd         return hash < 0 ? hash + MOD : hash;
cbb     }
214 };
217 template<int MOD> int str_hash<MOD>::P = uniform(256, MOD - 1);
// 1 > |sigma|

```

## 4.9 String Hashing - modulo $2^{61} - 1$

```

// Quase duas vezes mais lento
//
// Complexidades:
// build -  $O(|s|)$ 
// operator() -  $O(1)$ 
//
// d3c0f0

9d0 const ll MOD = (1ll<<61) - 1;
e38 ll mulmod(ll a, ll b) {
ff3     const static ll LOWER = (1ll<<30) - 1, GET31 = (1ll<<31) -
1;
410     ll l1 = a&LOWER, h1 = a>>30, l2 = b&LOWER, h2 = b>>30;
d54     ll m = l1*h2 + l2*h1, h = h1*h2;
784     ll ans = l1*l2 + (h>>1) + ((h&1)<<60) + (m>>31) +
((m&GET31)<<30) + 1;
1dd     ans = (ans&MOD) + (ans>>61), ans = (ans&MOD) + (ans>>61);
c0f     return ans - 1;
cbb }

```

```

798 mt19937_64
rng(chrono::steady_clock::now().time_since_epoch().count());

f89 ll uniform(ll l, ll r) {
969     uniform_int_distribution<ll> uid(l, r);
f54     return uid(rng);
cbb }

d7d struct str_hash {
c20     static ll P;
dcf     vector<ll> h, p;
ea8     str_hash(string s) : h(s.size()), p(s.size()) {
7a2         p[0] = 1, h[0] = s[0];
ad7         for (int i = 1; i < s.size(); i++)
632             p[i] = mulmod(p[i - 1], P), h[i] = (mulmod(h[i -
1], P) + s[i])%MOD;
cbb     }
af7     ll operator()(int l, int r) { // retorna hash s[l...r]
538         ll hash = h[r] - (l ? mulmod(h[l - 1], p[r - l + 1]) :
0);
dfd         return hash < 0 ? hash + MOD : hash;
cbb     }
214 };
6c5 ll str_hash::P = uniform(256, MOD - 1); // 1 > |sigma|

```

## 4.10 Suffix Array - $O(n \log n)$

```

// kasai recebe o suffix array e calcula lcp[i],
// o lcp entre s[sa[i],...,n-1] e s[sa[i+1],...,n-1]
//
// Complexidades:
// suffix_array -  $O(n \log(n))$ 
// kasai -  $O(n)$ 
// d3a6ce

733 vector<int> suffix_array(string s) {
b38     s += "$";
043     int n = s.size(), N = max(n, 260);
2f3     vector<int> sa(n), ra(n);
29b     for(int i = 0; i < n; i++) sa[i] = i, ra[i] = s[i];

0a2     for(int k = 0; k < n; k ? k *= 2 : k++) {
5ce         vector<int> nsa(sa), nra(n), cnt(N);

```

```

fae      for(int i = 0; i < n; i++) nsa[i] = (nsa[i]-k+n)%n,
cnt[ra[i]]++;
4c4      for(int i = 1; i < N; i++) cnt[i] += cnt[i-1];
368      for(int i = n-1; i+1; i--) sa[--cnt[ra[nsa[i]]]] =
nsa[i];

28f      for(int i = 1, r = 0; i < n; i++) nra[sa[i]] = r +=
ra[sa[i]] !=
f86          ra[sa[i-1]] or ra[(sa[i]+k)%n] != ra[(sa[i-1]+k)%n];
26b      ra = nra;
d5e      if (ra[sa[n-1]] == n-1) break;
cbb      }
057      return vector<int>(sa.begin()+1, sa.end());
cbb      }

481 vector<int> kasai(string s, vector<int> sa) {
232     int n = s.size(), k = 0;
408     vector<int> ra(n), lcp(n);
676     for (int i = 0; i < n; i++) ra[sa[i]] = i;

740     for (int i = 0; i < n; i++, k -= !!k) {
199         if (ra[i] == n-1) { k = 0; continue; }
1de         int j = sa[ra[i]+1];
891         while (i+k < n and j+k < n and s[i+k] == s[j+k]) k++;
d98         lcp[ra[i]] = k;
cbb     }
5ed     return lcp;
cbb     }

```

## 4.11 Suffix Array - $O(n)$

```

// Rapidaeo
// Computa o suffix array em 'sa', o rank em 'rnk'
// e o lcp em 'lcp'
// query(i, j) retorna o LCP entre s[i..n-1] e s[j..n-1]
//
// Complexidades
//  $O(n)$  para construir
// query -  $O(1)$ 

// hash do arquivo inteiro: fa533e

// bab412

```

```

1a5 template<typename T> struct rmq {
517     vector<T> v;
fcc     int n; static const int b = 30;
70e     vector<int> mask, t;

183     int op(int x, int y) { return v[x] <= v[y] ? x : y; }
ee1     int msb(int x) { return __builtin_clz(1)-__builtin_clz(x); }
c92     int small(int r, int sz = b) { return
r-msb(mask[r]&((1<<sz)-1)); }

6ad     rmq() {}
43c     rmq(const vector<T>& v_) : v(v_), n(v.size()), mask(n),
t(n) {
2e5         for (int i = 0, at = 0; i < n; mask[i++] = at |= 1) {
a61             at = (at<<1)&((1<<b)-1);
c00             while (at and op(i-msb(at&-at), i) == i) at ^=
at&-at;
cbb         }
ea4         for (int i = 0; i < n/b; i++) t[i] = small(b*i+b-1);
39d         for (int j = 1; (1<<j) <= n/b; j++) for (int i = 0;
i+(1<<j) <= n/b; i++)
ba5             t[n/b*j+i] = op(t[n/b*(j-1)+i],
t[n/b*(j-1)+i+(1<<(j-1))]);
cbb     }
e34     int index_query(int l, int r) {
27b         if (r-l+1 <= b) return small(r, r-l+1);
e80         int x = l/b+1, y = r/b-1;
fd3         if (x > y) return op(small(l+b-1), small(r));
a4e         int j = msb(y-x+1);
ea3         int ans = op(small(l+b-1), op(t[n/b*j+x],
t[n/b*j+y-(1<<j)+1]));
be6         return op(ans, small(r));
cbb     }
093     T query(int l, int r) { return v[index_query(l, r)]; }
214 };

9d7 struct suffix_array {
ac0     string s;
1a8     int n;
5b4     vector<int> sa, cnt, rnk, lcp;
2de     rmq<int> RMQ;

d6e     bool cmp(int a1, int b1, int a2, int b2, int a3=0, int
b3=0) {
91d         return a1 != b1 ? a1 < b1 : (a2 != b2 ? a2 < b2 : a3 <
b3);
cbb     }

```

```

4a4     template<typename T> void radix(int* fr, int* to, T* r, int
N, int k) {
c17         cnt = vector<int>(k+1, 0);
bac         for (int i = 0; i < N; i++) cnt[r[fr[i]]]++;
703         for (int i = 1; i <= k; i++) cnt[i] += cnt[i-1];
000         for (int i = N-1; i+1; i--) to[--cnt[r[fr[i]]]] = fr[i];
cbb     }
d66     void rec(vector<int>& v, int k) {
a76         auto &tmp = rnk, &m0 = lcp;
3a9         int N = v.size()-3, sz = (N+2)/3, sz2 = sz+N/3;
7f8         vector<int> R(sz2+3);
74f         for (int i = 1, j = 0; j < sz2; i += i%3) R[j++] = i;

b30         radix(&R[0], &tmp[0], &v[0]+2, sz2, k);
207         radix(&tmp[0], &R[0], &v[0]+1, sz2, k);
5f1         radix(&R[0], &tmp[0], &v[0]+0, sz2, k);

af5         int dif = 0;
ed9         int l0 = -1, l1 = -1, l2 = -1;
d81         for (int i = 0; i < sz2; i++) {
8de             if (v[tmp[i]] != l0 or v[tmp[i]+1] != l1 or
v[tmp[i]+2] != l2)
b43                 l0 = v[tmp[i]], l1 = v[tmp[i]+1], l2 =
v[tmp[i]+2], dif++;
199             if (tmp[i]%3 == 1) R[tmp[i]/3] = dif;
1f5             else R[tmp[i]/3+sz] = dif;
cbb         }

47f         if (dif < sz2) {
146             rec(R, dif);
746             for (int i = 0; i < sz2; i++) R[sa[i]] = i+1;
8b7         } else for (int i = 0; i < sz2; i++) sa[R[i]-1] = i;

6f4         for (int i = 0, j = 0; j < sz2; i++) if (sa[i] < sz)
tmp[j++] = 3*sa[i];
7ce         radix(&tmp[0], &m0[0], &v[0], sz, k);
74d         for (int i = 0; i < sz2; i++)
c9e             sa[i] = sa[i] < sz ? 3*sa[i]+1 : 3*(sa[i]-sz)+2;

332         int at = sz2+sz-1, p = sz-1, p2 = sz2-1;
1c9         while (p >= 0 and p2 >= 0) {
3b3             if ((sa[p2]%3==1 and cmp(v[m0[p]], v[sa[p2]]),
R[m0[p]/3],
0ce             R[sa[p2]/3+sz])) or (sa[p2]%3==2 and
cmp(v[m0[p]], v[sa[p2]]),
af6             v[m0[p]+1], v[sa[p2]+1], R[m0[p]/3+sz],

```

```

R[sa[p2]/3+1]))))
300             sa[at--] = sa[p2--];
cb0             else sa[at--] = m0[p--];
cbb         }
f2b         while (p >= 0) sa[at--] = m0[p--];
eb6         if (N%3==1) for (int i = 0; i < N; i++) sa[i] = sa[i+1];
cbb     }

938     suffix_array(const string& s_) : s(s_), n(s.size()),
sa(n+3),
e62         cnt(n+1), rnk(n), lcp(n-1) {
9fe         vector<int> v(n+3);
f9b         for (int i = 0; i < n; i++) v[i] = i;
eba         radix(&v[0], &rnk[0], &s[0], n, 256);
e6d         int dif = 1;
830         for (int i = 0; i < n; i++)
419             v[rnk[i]] = dif += (i and s[rnk[i]] != s[rnk[i-1]]);
7cf         if (n >= 2) rec(v, dif);
fb9         sa.resize(n);

76f         for (int i = 0; i < n; i++) rnk[sa[i]] = i;
892         for (int i = 0, k = 0; i < n; i++, k -= !!k) {
668             if (rnk[i] == n-1) {
5a4                 k = 0;
5e2                 continue;
cbb             }
39a             int j = sa[rnk[i]+1];
891             while (i+k < n and j+k < n and s[i+k] == s[j+k])
k++;

825             lcp[rnk[i]] = k;
cbb         }
9ff         RMQ = rmq<int>(lcp);
cbb     }

// hash ateh aqui (sem o RMQ): 1ff700

588     int query(int i, int j) {
d97         if (i == j) return n-i;
223         i = rnk[i], j = rnk[j];
c3a         return RMQ.query(min(i, j), max(i, j)-1);
cbb     }

71c     pair<int, int> next(int L, int R, int i, char c) {
024         int l = L, r = R+1;
40c         while (l < r) {
ee4             int m = (l+r)/2;
e7e             if (i+sa[m] >= n or s[i+sa[m]] < c) l = m+1;
ef3             else r = m;

```

```

cbb      }
575      if (l == R+1 or s[i+sa[l]] > c) return {-1, -1};
eb7      L = l;

9e2      l = L, r = R+1;
40c      while (l < r) {
ee4          int m = (l+r)/2;
1a1          if (i+sa[m] >= n or s[i+sa[m]] <= c) l = m+1;
ef3          else r = m;
cbb      }
56a      R = l-1;
e13      return {L, R};
cbb    }
// quantas vezes 't' ocorre em 's' - O(|t| log n)
66d    int count_substr(string& t) {
b2b        int L = 0, R = n-1;
c9d        for (int i = 0; i < t.size(); i++) {
de0            tie(L, R) = next(L, R, i, t[i]);
4fc            if (L == -1) return 0;
cbb        }
fbf        return R-L+1;
cbb    }

// exemplo de f que resolve o problema
//
https://codeforces.com/edu/course/2/lesson/2/5/practice/contest/269656/problem/D
57e    ll f(ll k) { return k*(k+1)/2; }

e68    ll dfs(int L, int R, int p) { // dfs na suffix tree chamado
em pre ordem
c54        int ext = L != R ? RMQ.query(L, R-1) : n - sa[L];

// Tem 'ext - p' substrings diferentes que ocorrem
// 'R-L+1' vezes
// 0 LCP de todas elas eh 'ext'
f80    ll ans = (ext-p)*f(R-L+1);

// L eh terminal, e folha sse L == R
63c    if (sa[L]+ext == n) L++;

/* se for um SA de varias strings separadas como
s#t$u&, usar no lugar do if de cima
(separadores < 'a', diferentes e inclusive no final)
while (L <= R && (sa[L]+ext == n || s[sa[L]+ext] <
'a')) {
f49        L++;

```

```

792    } */

add      while (L <= R) {
5a8          int idx = L != R ? RMQ.index_query(L, R-1) : -1;
5ef          if (idx == -1 or lcp[idx] != ext) idx = R;

478          ans += dfs(L, idx, ext);
28d          L = idx+1;
cbb      }
ba7      return ans;
cbb    }

// sum over substrings: computa, para toda substring t
// distinta de s,
// \sum f(# ocorrencias de t em s) - O(n)
ca8    ll sos() { return dfs(0, n-1, 0); }
214 };

4.12 Suffix Array Dinamico

// Mantem o suffix array, lcp e rank de uma string,
// permitindo push_front e pop_front
// 0 operador [i] return um par com sa[i] e lcp[i]
// lcp[i] tem o lcp entre sa[i] e sa[i-1] (lcp[0] = 0)
//
// Complexidades:
// Construir sobre uma string de tamanho n: O(n log n)
// push_front e pop_front: O(log n) amortizado
// 4c2a2e

2fe struct dyn_sa {
3c9     struct node {
1d4         int sa, lcp;
ed1         node *l, *r, *p;
f0d         int sz, mi;
17b         node(int sa_, int lcp_, node* p_) : sa(sa_), lcp(lcp_),
543             l(NULL), r(NULL), p(p_), sz(1), mi(lcp) {}
01e         void update() {
58f             sz = 1, mi = lcp;
bd7             if (l) sz += l->sz, mi = min(mi, l->mi);
a54             if (r) sz += r->sz, mi = min(mi, r->mi);
cbb         }
214     };

```

```

bb7  node* root;
295  vector<ll> tag; // tag of a suffix (reversed id)
ac0  string s; // reversed

cf4  dyn_sa() : root(NULL) {}
e45  dyn_sa(string s_) : dyn_sa() {
ae4      reverse(s_.begin(), s_.end());
519      for (char c : s_) push_front(c);
cbb  }
a86  ~dyn_sa() {
609      vector<node*> q = {root};
402      while (q.size()) {
e5d          node* x = q.back(); q.pop_back();
ee9          if (!x) continue;
1c7          q.push_back(x->l), q.push_back(x->r);
bf0          delete x;
cbb      }
cbb  }

73c  int size(node* x) { return x ? x->sz : 0; }
08e  int mirror(int i) { return s.size()-1 - i; }
580  bool cmp(int i, int j) {
a29      if (s[i] != s[j]) return s[i] < s[j];
5b4      if (i == 0 or j == 0) return i < j;
988      return tag[i-1] < tag[j-1];
cbb  }
919  void fix_path(node* x) { while (x) x->update(), x = x->p; }
245  void flatten(vector<node*>& v, node* x) {
8c8      if (!x) return;
e96      flatten(v, x->l);
2a2      v.push_back(x);
42d      flatten(v, x->r);
cbb  }
964  void build(vector<node*>& v, node*& x, node* p, int L, int
R, ll l, ll r) {
04c      if (L > R) return void(x = NULL);
331      int M = (L+R)/2;
3e3      ll m = (l+r)/2;
7e5      x = v[M];
63e      x->p = p;
bb3      tag[x->sa] = m;
ae0      build(v, x->l, x, L, M-1, l, m-1), build(v, x->r, x,
M+1, R, m+1, r);
ca8      x->update();
cbb  }
82f  void fix(node*& x, node* p, ll l, ll r) {

```

```

7f0      if (3*max(size(x->l), size(x->r)) <= 2*size(x)) return
x->update();
3d1      vector<node*> v;
0cc      flatten(v, x);
ea9      build(v, x, p, 0, v.size()-1, l, r);
cbb  }
b19  node* next(node* x) {
728      if (x->r) {
a91          x = x->r;
347          while (x->l) x = x->l;
ea5          return x;
cbb      }
402      while (x->p and x->p->r == x) x = x->p;
137      return x->p;
cbb  }
b68  node* prev(node* x) {
e41      if (x->l) {
a26          x = x->l;
93c          while (x->r) x = x->r;
ea5          return x;
cbb      }
6a1      while (x->p and x->p->l == x) x = x->p;
137      return x->p;
cbb  }

4f7  int get_lcp(node* x, node* y) {
75a      if (!x or !y) return 0; // change default value here
e51      if (s[x->sa] != s[y->sa]) return 0;
843      if (x->sa == 0 or y->sa == 0) return 1;
4d0      return 1 + query(mirror(x->sa-1), mirror(y->sa-1));
cbb  }
ad6  void add_suf(node*& x, node* p, int id, ll l, ll r) {
91e      if (!x) {
8e3          x = new node(id, 0, p);
8e2          node *prv = prev(x), *nxt = next(x);
65d          int lcp_cur = get_lcp(prv, x), lcp_nxt = get_lcp(x,
nxt);
ca3          if (nxt) nxt->lcp = lcp_nxt, fix_path(nxt);
71f          x->lcp = lcp_cur;
7b4          tag[id] = (l+r)/2;
ca8          x->update();
505          return;
cbb      }
4a3      if (cmp(id, x->sa)) add_suf(x->l, x, id, l,
tag[x->sa]-1);
c3a      else add_suf(x->r, x, id, tag[x->sa]+1, r);

```



```

3db      fix(x, p, l, r);
cbb    }
ec2    void push_front(char c) {
cc7      s += c;
493      tag.push_back(-1);
05e      add_suf(root, NULL, s.size() - 1, 0, 1e18);
cbb    }

7f3    void rem_suf(node*& x, int id) {
6cf      if (x->sa != id) {
864        if (tag[id] < tag[x->sa]) return rem_suf(x->l, id);
e6f        return rem_suf(x->r, id);
cbb      }
2cf      node* nxt = next(x);
09b      if (nxt) nxt->lcp = min(nxt->lcp, x->lcp),
fix_path(nxt);

b20      node *p = x->p, *tmp = x;
f3f      if (!x->l or !x->r) {
2fd        x = x->l ? x->l : x->r;
753        if (x) x->p = p;
9d9      } else {
7f7        for (tmp = x->l, p = x; tmp->r; tmp = tmp->r) p =
tmp;
f2a        x->sa = tmp->sa, x->lcp = tmp->lcp;
482        if (tmp->l) tmp->l->p = p;
14c        if (p->l == tmp) p->l = tmp->l;
a94        else p->r = tmp->l;
cbb      }
b5e      fix_path(p);
7c3      delete tmp;
cbb    }
15b    void pop_front() {
abe      if (!s.size()) return;
342      s.pop_back();
436      rem_suf(root, s.size());
c6e      tag.pop_back();
cbb    }

530    int query(node* x, ll l, ll r, ll a, ll b) {
e51      if (!x or tag[x->sa] == -1 or r < a or b < l) return
s.size();
ef5      if (a <= l and r <= b) return x->mi;
8eb      int ans = s.size();
e1f      if (a <= tag[x->sa] and tag[x->sa] <= b) ans = min(ans,
x->lcp);

```

```

d99      ans = min(ans, query(x->l, l, tag[x->sa]-1, a, b));
261      ans = min(ans, query(x->r, tag[x->sa]+1, r, a, b));
ba7      return ans;
cbb    }
588    int query(int i, int j) { // lcp(s[i..], s[j..])
209      if (i == j) return s.size() - i;
29e      ll a = tag[mirror(i)], b = tag[mirror(j)];
710      int ret = query(root, 0, 1e18, min(a, b)+1, max(a, b));
edf      return ret;
cbb    }
// optional: get rank[i], sa[i] and lcp[i]
044    int rank(int i) {
396      i = mirror(i);
52f      node* x = root;
7c9      int ret = 0;
f4c      while (x) {
33e        if (tag[x->sa] < tag[i]) {
f9d          ret += size(x->l)+1;
a91          x = x->r;
eb5        } else x = x->l;
cbb      }
edf      return ret;
cbb    }
649    pair<int, int> operator[](int i) {
52f      node* x = root;
31e      while (1) {
d4d        if (i < size(x->l)) x = x->l;
4e6        else {
85f          i -= size(x->l);
e03          if (!i) return {mirror(x->sa), x->lcp};
040          i--, x = x->r;
cbb        }
cbb      }
cbb    }
214 };

```

## 4.13 Trie

```

// trie T() constroi uma trie para o alfabeto das letras minusculas
// trie T(tamanho do alfabeto, menor caracter) tambem pode ser usado
//
// T.insert(s) - O(|s|*sigma)
// T.erase(s) - O(|s|)
// T.find(s) retorna a posicao, 0 se nao achar - O(|s|)

```

```

// T.count_pref(s) numero de strings que possuem s como prefixo -
// 0(|s|)
//
// Nao funciona para string vazia
// 979609

ab5 struct trie {
e1a     vector<vector<int>> to;
450     vector<int> end, pref;
af0     int sigma; char norm;
bb1     trie(int sigma_=26, char norm_='a') : sigma(sigma_),
        norm(norm_) {
58a         to = {vector<int>(sigma)};
86e         end = {0}, pref = {0};
cbb     }
64e     void insert(string s) {
c67         int x = 0;
7e7         for(auto c : s) {
008             int &nxt = to[x][c-norm];
dd7             if(!nxt) {
0aa                 nxt = to.size();
526                 to.push_back(vector<int>(sigma));
770                 end.push_back(0), pref.push_back(0);
cbb             }
827             x = nxt, pref[x]++;
cbb         }
e4e         end[x]++;
cbb     }
6b2     void erase(string s) {
c67         int x = 0;
b4f         for(char c : s) {
008             int &nxt = to[x][c-norm];
10c             x = nxt, pref[x]--;
d8e             if(!pref[x]) nxt = 0;
cbb         }
bf0         end[x]--;
cbb     }
aee     int find(string s) {
c67         int x = 0;
7e7         for(auto c : s) {
2ec             x = to[x][c-norm];
a66             if(!x) return 0;
cbb         }
ea5         return x;
cbb     }
839     int count_pref(string s) {

```

```

e2f         return pref[find(s)];
cbb     }
214 };

```

## 5 Estruturas

### 5.1 BIT

```

// BIT de soma 1-based, v 0-based
// Para mudar o valor da posicao p para x,
// faca: poe(x - query(p, p), p)
// l_bound(x) retorna o menor p tal que
// query(1, p+1) > x (0 based!)
//
// Complexidades:
// build - O(n)
// poe - O(log(n))
// query - O(log(n))
// l_bound - O(log(n))
// d432a4

1a8 int n;
7f4 int bit[MAX];
b69 int v[MAX];

0a8 void build() {
b91     bit[0] = 0;
33c     for (int i = 1; i <= n; i++) bit[i] = v[i - 1];

78a     for (int i = 1; i <= n; i++) {
edf         int j = i + (i & -i);
b8a         if (j <= n) bit[j] += bit[i];
cbb     }
cbb }

// soma x na posicao p
235 void poe(int x, int p) {
9c7     for (; p <= n; p += p & -p) bit[p] += x;
cbb }

// soma [1, p]
0bf int pref(int p) {
7c9     int ret = 0;

```

```

805     for (; p; p -= p & -p) ret += bit[p];
edf     return ret;
cbb }

    // soma [a, b]
4ea int query(int a, int b) {
70c     return pref(b) - pref(a - 1);
cbb }

e4a int l_bound(ll x) {
1ba     int p = 0;
676     for (int i = MAX2; i+1; i--) if (p + (1<<i) <= n
729         and bit[p + (1<<i)] <= x) x -= bit[p += (1<<i)];
74e     return p;
cbb }

```

## 5.2 BIT 2D

```

// BIT de soma, update incrementa posicao
// Tem que construir com um vetor com todos os pontos
// que vc quer um dia atualizar (os pontos q vc vai chamar update)
//
// Complexidades:
// construir - O(n log(n))
// update e query - O(log^2(n))
// 6a760a

```

```

a6b template<class T = int> struct bit2d {
acf     vector<T> X;
a84     vector<vector<T>> Y, t;

709     int ub(vector<T>& v, T x) {
dde         return upper_bound(v.begin(), v.end(), x) - v.begin();
cbb     }
5cb     bit2d(vector<pair<T, T>> v) {
2e1         for (auto [x, y] : v) X.push_back(x);
fd4         sort(X.begin(), X.end());
1ee         X.erase(unique(X.begin(), X.end()), X.end());

d56         t.resize(X.size() + 1);
d12         Y.resize(t.size());
3d0         sort(v.begin(), v.end(), [](auto a, auto b) {
43d             return a.second < b.second; });

```

```

961         for (auto [x, y] : v) for (int i = ub(X, x); i <
t.size(); i += i&-i)
b75             if (!Y[i].size() or Y[i].back() != y)
Y[i].push_back(y);

7c7         for (int i = 0; i < t.size(); i++)
t[i].resize(Y[i].size() + 1);
cbb     }

e78     void update(T x, T y, T v) {
2a9         for (int i = ub(X, x); i < t.size(); i += i&-i)
cd2             for (int j = ub(Y[i], y); j < t[i].size(); j +=
j&-j) t[i][j] += v;
cbb     }

5d2     T query(T x, T y) {
966         T ans = 0;
c54         for (int i = ub(X, x); i; i -= i&-i)
4fb             for (int j = ub(Y[i], y); j; j -= j&-j) ans +=
t[i][j];
ba7         return ans;
cbb     }
46d     T query(T x1, T y1, T x2, T y2) {
fcf         return query(x2, y2) - query(x2, y1-1) - query(x1-1,
y2) + query(x1-1, y1-1);
cbb     }
214 };

```

## 5.3 BIT com update em range

```

// Operacoes 0-based
// query(l, r) retorna a soma de v[l..r]
// update(l, r, x) soma x em v[l..r]
//
// Complexidades:
// build - O(n)
// query - O(log(n))
// update - O(log(n))
// f91737

```

```

e04 namespace bit {
3ba     ll bit[2][MAX+2];
1a8     int n;

```

```

61c void build(int n2, int* v) {
1e3     n = n2;
535     for (int i = 1; i <= n; i++)
edd         bit[1][min(n+1, i+(i&-i))] += bit[1][i] += v[i-1];
cbb }
637 ll get(int x, int i) {
b73     ll ret = 0;
360     for (; i; i -= i&-i) ret += bit[x][i];
edf     return ret;
cbb }
20c void add(int x, int i, ll val) {
503     for (; i <= n; i += i&-i) bit[x][i] += val;
cbb }
162 ll get2(int p) {
c7c     return get(0, p) * p + get(1, p);
cbb }
02a ll query(int l, int r) {
ff5     return get2(r+1) - get2(l);
cbb }
089 void update(int l, int r, ll x) {
e5f     add(0, l+1, x), add(0, r+2, -x);
f58     add(1, l+1, -x*1), add(1, r+2, x*(r+1));
cbb }
214 };

```

## 5.4 DSU

```

// Une dois conjuntos e acha a qual conjunto um elemento pertence
// por seu id
//
// find e unite:  $O(a(n)) \sim O(1)$  amortizado
// 8e197e

```

```

8d3 struct dsu {
825     vector<int> id, sz;

b33     dsu(int n) : id(n), sz(n, 1) { iota(id.begin(), id.end(),
0); }

0cf     int find(int a) { return a == id[a] ? a : id[a] =
find(id[a]); }

440     void unite(int a, int b) {
605         a = find(a), b = find(b);

```

```

d54         if (a == b) return;
956         if (sz[a] < sz[b]) swap(a, b);
6d0         sz[a] += sz[b], id[b] = a;
cbb     }
214 };

// DSU de bipartido
//
// Une dois vertices e acha a qual componente um vertice
// pertence
// Informa se a componente de um vertice e bipartida
//
// find e unite:  $O(\log(n))$ 
// 118050

8d3 struct dsu {
6f7     vector<int> id, sz, bip, c;

5b4     dsu(int n) : id(n), sz(n, 1), bip(n, 1), c(n) {
db8         iota(id.begin(), id.end(), 0);
cbb     }

ef0     int find(int a) { return a == id[a] ? a : find(id[a]); }
f30     int color(int a) { return a == id[a] ? c[a] : c[a] ^
color(id[a]); }

440     void unite(int a, int b) {
263         bool change = color(a) == color(b);
605         a = find(a), b = find(b);
a89         if (a == b) {
4ed             if (change) bip[a] = 0;
505             return;
cbb         }

956         if (sz[a] < sz[b]) swap(a, b);
efe         if (change) c[b] = 1;
2cd         sz[a] += sz[b], id[b] = a, bip[a] ^= bip[b];
cbb     }
214 };

// DSU Persistente
//
// Persistencia parcial, ou seja, tem que ir
// incrementando o 't' no une
//

```

```

// find e unite: O(log(n))
// 6c63a4

8d3 struct dsu {
33c     vector<int> id, sz, ti;

733     dsu(int n) : id(n), sz(n, 1), ti(n, -INF) {
db8         iota(id.begin(), id.end(), 0);
cbb     }

5e6     int find(int a, int t) {
6ba         if (id[a] == a or ti[a] > t) return a;
ea5         return find(id[a], t);
cbb     }

fa0     void unite(int a, int b, int t) {
84f         a = find(a, t), b = find(b, t);
d54         if (a == b) return;
956         if (sz[a] < sz[b]) swap(a, b);
35d         sz[a] += sz[b], id[b] = a, ti[b] = t;
cbb     }
214 };

// DSU com rollback
//
// checkpoint(): salva o estado atual de todas as variaveis
// rollback(): retorna para o valor das variaveis para
// o ultimo checkpoint
//
// Sempre que uma variavel muda de valor, adiciona na stack
//
// find e unite: O(log(n))
// checkpoint: O(1)
// rollback: O(m) em que m e o numero de vezes que alguma
// variavel mudou de valor desde o ultimo checkpoint
// c6e923

8d3 struct dsu {
825     vector<int> id, sz;
27c     stack<stack<pair<int&, int>>> st;

98d     dsu(int n) : id(n), sz(n, 1) {
1cc         iota(id.begin(), id.end(), 0), st.emplace();
cbb     }

bdf     void save(int &x) { st.top().emplace(x, x); }

```

```

30d     void checkpoint() { st.emplace(); }

5cf     void rollback() {
ba9         while(st.top().size()) {
6bf             auto [end, val] = st.top().top(); st.top().pop();
149             end = val;
cbb         }
25a         st.pop();
cbb     }

ef0     int find(int a) { return a == id[a] ? a : find(id[a]); }

440     void unite(int a, int b) {
605         a = find(a), b = find(b);
d54         if (a == b) return;
956         if (sz[a] < sz[b]) swap(a, b);
803         save(sz[a]), save(id[b]);
6d0         sz[a] += sz[b], id[b] = a;
cbb     }
214 };

```

## 5.5 Li-Chao Tree

```

// Adiciona retas (ax+b), e computa o minimo entre as retas
// em um dado 'x'
// Cuidado com overflow!
// Se tiver overflow, tenta comprimir o 'x' ou usar
// convex hull trick
//
// O(log(MA-MI)), O(n) de memoria
// 59ba68

5b0 template<ll MI = ll(-1e9), ll MA = ll(1e9)> struct lichao {
b3a     struct line {
12d         ll a, b;
cef         array<int, 2> ch;
fdf         line(ll a_ = 0, ll b_ = LINF) :
423             a(a_), b(b_), ch({-1, -1}) {}
888         ll operator()(ll x) { return a*x + b; }
214     };
17b     vector<line> ln;

df8     int ch(int p, int d) {

```

```

e85         if (ln[p].ch[d] == -1) {
9af             ln[p].ch[d] = ln.size();
cdc             ln.emplace_back();
cbb         }
ef2         return ln[p].ch[d];
cbb     }
021     lichao() { ln.emplace_back(); }

c33     void add(line s, ll l=MI, ll r=MA, int p=0) {
3e3         ll m = (l+r)/2;
911         bool L = s(l) < ln[p](l);
d37         bool M = s(m) < ln[p](m);
03b         bool R = s(r) < ln[p](r);
825         if (M) swap(ln[p], s), swap(ln[p].ch, s.ch);
cac         if (s.b == LINF) return;
f6d         if (L != M) add(s, l, m-1, ch(p, 0));
898         else if (R != M) add(s, m+1, r, ch(p, 1));
cbb     }
092     ll query(int x, ll l=MI, ll r=MA, int p=0) {
11b         ll m = (l+r)/2, ret = ln[p](x);
9db         if (ret == LINF) return ret;
529         if (x < m) return min(ret, query(x, l, m-1, ch(p, 0)));
81a         return min(ret, query(x, m+1, r, ch(p, 1)));
cbb     }
214 };

```

## 5.6 MergeSort Tree

```

// Se for construida sobre um array:
//     count(i, j, a, b) retorna quantos
//     elementos de v[i..j] pertencem a [a, b]
//     report(i, j, a, b) retorna os indices dos
//     elementos de v[i..j] que pertencem a [a, b]
//     retorna o vetor ordenado
// Se for construida sobre pontos (x, y):
//     count(x1, x2, y1, x2) retorna quantos pontos
//     pertencem ao retangulo (x1, y1), (x2, y2)
//     report(x1, x2, y1, y2) retorna os indices dos pontos que
//     pertencem ao retangulo (x1, y1), (x2, y2)
//     retorna os pontos ordenados lexicograficamente
//     (assume x1 <= x2, y1 <= y2)
//
// kth(y1, y2, k) retorna o indice do ponto com k-esimo menor
// x dentre os pontos que possuem y em [y1, y2] (0 based)

```

```

// Se quiser usar para achar k-esimo valor em range, construir
// com ms_tree t(v, true), e chamar kth(l, r, k)
//
// Usa O(n log(n)) de memoria
//
// Complexidades:
// construir - O(n log(n))
// count - O(log(n))
// report - O(log(n) + k) para k indices retornados
// kth - O(log(n))
// 1cef03

c6c     template <typename T = int> struct ms_tree {
6f7         vector<tuple<T, T, int>>> v;
1a8         int n;
5ee         vector<vector<tuple<T, T, int>>> t; // {y, idx, left}
6ae         vector<T> vy;

78c         ms_tree(vector<pair<T, T>>& vv) : n(vv.size()), t(4*n),
vy(n) {
e80             for (int i = 0; i < n; i++) v.push_back({vv[i].first,
vv[i].second, i});
fca             sort(v.begin(), v.end());
224             build(1, 0, n-1);
01a             for (int i = 0; i < n; i++) vy[i] = get<0>(t[1][i+1]);
cbb         }
dac         ms_tree(vector<T>& vv, bool inv = false) { // inv: inverte
indice e valor
8e8             vector<pair<T, T>> v2;
e1e             for (int i = 0; i < vv.size(); i++)
196                 inv ? v2.push_back({vv[i], i}) : v2.push_back({i,
vv[i]});
cca             *this = ms_tree(v2);
cbb         }
2c6         void build(int p, int l, int r) {
1d2             t[p].push_back({get<0>(v[l]), get<0>(v[r]), 0}); //
{min_x, max_x, 0}
5c8             if (l == r) return t[p].push_back({get<1>(v[l]),
get<2>(v[l]), 0});
ee4             int m = (l+r)/2;
bd9             build(2*p, l, m), build(2*p+1, m+1, r);

32d             int L = 0, R = 0;
a03             while (t[p].size() <= r-l+1) {
68e                 int left = get<2>(t[p].back());
4aa                 if (L > m-l or (R+m+1 <= r and t[2*p+1][1+R] <

```

```

t[2*p][1+L])) {
8cf          t[p].push_back(t[2*p+1][1 + R++]);
da0          get<2>(t[p].back()) = left;
5e2          continue;
cbb      }
249          t[p].push_back(t[2*p][1 + L++]);
339          get<2>(t[p].back()) = left+1;
cbb      }
cbb  }

dd3      int get_l(T y) { return lower_bound(vy.begin(), vy.end(),
y) - vy.begin(); }
ebb      int get_r(T y) { return upper_bound(vy.begin(), vy.end(),
y) - vy.begin(); }

f62      int count(T x1, T x2, T y1, T y2) {
902          function<int(int, int, int)> dfs = [&](int p, int l,
int r) {
7c6              if (l == r or x2 < get<0>(t[p][0]) or
get<1>(t[p][0]) < x1) return 0;
2bb              if (x1 <= get<0>(t[p][0]) and get<1>(t[p][0]) <=
x2) return r-l;
784              int nl = get<2>(t[p][1]), nr = get<2>(t[p][r]);
eb6              return dfs(2*p, nl, nr) + dfs(2*p+1, l-nl, r-nr);
214          };
7cb          return dfs(1, get_l(y1), get_r(y2));
cbb      }
002      vector<int> report(T x1, T x2, T y1, T y2) {
4b8          vector<int> ret;
85e          function<void(int, int, int)> dfs = [&](int p, int l,
int r) {
882              if (l == r or x2 < get<0>(t[p][0]) or
get<1>(t[p][0]) < x1) return;
8da              if (x1 <= get<0>(t[p][0]) and get<1>(t[p][0]) <=
x2) {
e00                  for (int i = l; i < r; i++)
ret.push_back(get<1>(t[p][i+1]));
505                  return;
cbb              }
784              int nl = get<2>(t[p][1]), nr = get<2>(t[p][r]);
194              dfs(2*p, nl, nr), dfs(2*p+1, l-nl, r-nr);
214          };
8ad          dfs(1, get_l(y1), get_r(y2));
edf          return ret;
cbb      }
985      int kth(T y1, T y2, int k) {

```

```

902          function<int(int, int, int)> dfs = [&](int p, int l,
int r) {
150              if (k >= r-l) {
941                  k -= r-l;
daa                  return -1;
cbb              }
8da              if (r-l == 1) return get<1>(t[p][1+1]);
784              int nl = get<2>(t[p][1]), nr = get<2>(t[p][r]);
072              int left = dfs(2*p, nl, nr);
3b6              if (left != -1) return left;
04d              return dfs(2*p+1, l-nl, r-nr);
214          };
7cb          return dfs(1, get_l(y1), get_r(y2));
cbb      }
214 };

```

## 5.7 Min queue - deque

```

// Tudo O(1) amortizado
// c13c57

```

```

1dc template<class T> struct minqueue {
2d8     deque<pair<T, int>> q;

3fc     void push(T x) {
56e         int ct = 1;
953         while (q.size() and x < q.front().first)
75f             ct += q.front().second, q.pop_front();
987         q.emplace_front(x, ct);
cbb     }
42d     void pop() {
aa2         if (q.back().second > 1) q.back().second--;
c51         else q.pop_back();
cbb     }
ea6     T min() { return q.back().first; }
214 };

```

## 5.8 Min queue - stack

```

// Tudo O(1) amortizado
// fe0cad

```

```

557 template<class T> struct minstack {
81f     stack<pair<T, T>> s;

3fc     void push(T x) {
12b         if (!s.size()) s.push({x, x});
9d9         else s.emplace(x, std::min(s.top().second, x));
cbb     }
4f0     T top() { return s.top().first; }
94a     T pop() {
1f2         T ans = s.top().first;
2eb         s.pop();
ba7         return ans;
cbb     }
614     int size() { return s.size(); }
13b     T min() { return s.top().second; }
214 };

1dc template<class T> struct minqueue {
cdc     minstack<T> s1, s2;

7cd     void push(T x) { s1.push(x); }
c96     void move() {
d4d         if (s2.size()) return;
d92         while (s1.size()) {
7ae             T x = s1.pop();
489             s2.push(x);
cbb         }
cbb     }
787     T front() { return move(), s2.top(); }
23a     T pop() { return move(), s2.pop(); }
7f3     int size() { return s1.size()+s2.size(); }
19c     T min() {
cd6         if (!s1.size()) return s2.min();
58e         else if (!s2.size()) return s1.min();
31d         return std::min(s1.min(), s2.min());
cbb     }
214 };

```

## 5.9 Order Statistic Set

```
// Funciona do C++11 pra cima
```

```
// 901923
```

```
774 #include <ext/pb_ds/assoc_container.hpp>
```

```

30f #include <ext/pb_ds/tree_policy.hpp>
0d7 using namespace __gnu_pbds;
4fc template <class T>
def     using ord_set = tree<T, null_type, less<T>, rb_tree_tag,
3a1     tree_order_statistics_node_update>;

// para declarar:
// ord_set<int> s;
// coisas do set normal funcionam:
// for (auto i : s) cout << i << endl;
// cout << s.size() << endl;
// k-esimo maior elemento O(log|s|):
// k=0: menor elemento
// cout << *s.find_by_order(k) << endl;
// quantos sao menores do que k O(log|s|):
// cout << s.order_of_key(k) << endl;

// Para fazer um multiset, tem que
// usar ord_set<pair<int, int>> com o
// segundo parametro sendo algo para diferenciar
// os elementos iguais.
// s.order_of_key({k, -INF}) vai retornar o
// numero de elementos < k

```

## 5.10 Priority Queue DS

```

// Mantem updates aplicados em uma estrutura de dados
// que permita rollback e nao seja amortizada.
// Cada update possui uma prioridade,
// sendo possivel remover o update com maior prioridade.
// Os updates devem ser comutativos, ou seja, o estado
// da estrutura deve ser o mesmo independente da ordem
// que eles sejam aplicados.
//
// Complexidades:
// update - O(log(n) + T(n))
// query - T(n)
// pop - O(log(n) * T(n)) amortizado
//
// onde T(n) eh a complexidade do update
//
// 54a75e

// assumes all priorities are distinct

```



```

945 template<typename DS, typename UPD> struct priority_queue_ds {
df4     DS D;
a7e     vector<tuple<UPD, int, int>> upd; // {u, p, idx_in_pos}
866     set<pair<int, int>> st;
927     vector<int> pos;

cf0     priority_queue_ds(int n) : D(n) {}

6af     void update(UPD u, int p) {
9ab         D.update(u);
d07         st.emplace(p, pos.size());
6ca         upd.emplace_back(u, p, pos.size());
e3d         pos.push_back(upd.size() - 1);
cbb     }

427     int query(int a) {
aa3         return D.find(a);
cbb     }

42d     void pop() {
25f         int k = 1, min_p; // k = number of pops we will do
43e         vector<tuple<UPD, int, int>> small, big;
639         auto it = st.end();
231         for (int qt = 0; qt++ < (k+1)/2;) {
049             it--;
3ab             min_p = it->first;
80f             int i = pos[it->second];
e82             if (qt > 1) big.push_back(upd[i]);
84b             k = max<int>(k, upd.size() - i);
cbb         }

b3d         for (int i = 0; i < k; i++) {
a62             D.rollback();
6d8             auto [u, p, idx] = upd.rbegin()[i];
86d             if (p < min_p) small.emplace_back(u, p, idx);
cbb         }

23e         st.erase(prev(st.end()));
623         upd.erase(upd.end() - k, upd.end());

a25         small.insert(small.end(), big.rbegin(), big.rend());
06f         for (auto [u, p, idx] : small) {
9ab             D.update(u);
c8e             upd.emplace_back(u, p, idx);
a7d             pos[idx] = upd.size() - 1;
cbb         }

```

```

cbb     }
214 };

```

## 5.11 Range color

```

// update(l, r, c) colore o range [l, r] com a cor c,
// e retorna os ranges que foram coloridos {l, r, cor}
// query(i) retorna a cor da posicao i
//
// Complexidades (para q operacoes):
// update - O(log(q)) amortizado
// query - O(log(q))
// 9e9cab

```

```

df6 template<typename T> struct color {
f0c     set<tuple<int, int, T>> se;

071     vector<tuple<int, int, T>> update(int l, int r, T val) {
9c4         auto it = se.upper_bound({r, INF, val});
753         if (it != se.begin() and get<1>(*prev(it)) > r) {
e91             auto [L, R, V] = *--it;
3f0             se.erase(it);
bfd             se.emplace(L, r, V), se.emplace(r+1, R, V);
cbb         }
d9e         it = se.lower_bound({l, -INF, val});
516         if (it != se.begin() and get<1>(*prev(it)) >= l) {
e91             auto [L, R, V] = *--it;
3f0             se.erase(it);
75a             se.emplace(L, l-1, V), it = se.emplace(l, R,
V).first;
cbb         }
d7b         vector<tuple<int, int, T>> ret;
7a1         for (; it != se.end() and get<0>(*it) <= r; it =
se.erase(it))
8c0             ret.push_back(*it);
b4a         se.emplace(l, r, val);
edf         return ret;
cbb     }

ff9     T query(int i) {
c31         auto it = se.upper_bound({i, INF, T()});
8e7         if (it == se.begin() or get<1>(*--it) < i) return -1;
// nao tem
53d         return get<2>(*it);
cbb     }

```

```
214 };
```

## 5.12 RMQ $<O(n), O(1)>$ - min queue

```
// O(n) pra buildar, query O(1)
// Se tiver varios minimos, retorna
// o de menor indice
// bab412

1a5 template<typename T> struct rmq {
517     vector<T> v;
fcc     int n; static const int b = 30;
70e     vector<int> mask, t;

183     int op(int x, int y) { return v[x] <= v[y] ? x : y; }
ee1     int msb(int x) { return __builtin_clz(1)-__builtin_clz(x); }
c92     int small(int r, int sz = b) { return
r-msb(mask[r]&((1<<sz)-1)); }
6ad     rmq() {}
43c     rmq(const vector<T>& v_) : v(v_), n(v.size()), mask(n),
t(n) {
2e5         for (int i = 0, at = 0; i < n; mask[i++] = at |= 1) {
a61             at = (at<<1)&((1<<b)-1);
c00             while (at and op(i-msb(at&-at), i) == i) at ^=
at&-at;
cbb         }
ea4         for (int i = 0; i < n/b; i++) t[i] = small(b*i+b-1);
39d         for (int j = 1; (1<<j) <= n/b; j++) for (int i = 0;
i+(1<<j) <= n/b; i++)
ba5             t[n/b*j+i] = op(t[n/b*(j-1)+i],
t[n/b*(j-1)+i+(1<<(j-1))]);
cbb     }
e34     int index_query(int l, int r) {
27b         if (r-l+1 <= b) return small(r, r-l+1);
e80         int x = l/b+1, y = r/b-1;
fd3         if (x > y) return op(small(l+b-1), small(r));
a4e         int j = msb(y-x+1);
ea3         int ans = op(small(l+b-1), op(t[n/b*j+x],
t[n/b*j+y-(1<<j)+1]));
be6         return op(ans, small(r));
cbb     }
093     T query(int l, int r) { return v[index_query(l, r)]; }
214 };
```

## 5.13 SegTreap

```
// Muda uma posicao do plano, e faz query de operacao
// associativa e comutativa em retangulo
// Mudar ZERO e op
// Esparso nas duas coordenadas, inicialmente eh tudo ZERO
//
// Para query com distancia de manhattan <= d, faca
// nx = x+y, ny = x-y
// Update em (nx, ny), query em ((nx-d, ny-d), (nx+d, ny+d))
//
// Valores no X tem que ser de 0 ateh NX
// Para q operacoes, usa O(q log(NX)) de memoria, e as
// operacoes custa O(log(q) log(NX))
// 75f2d0

55b const int ZERO = INF;
560 const int op(int l, int r) { return min(l, r); }

878 mt19937 rng((int)
chrono::steady_clock::now().time_since_epoch().count());

aa1 template<typename T> struct treap {
3c9     struct node {
b19         node *l, *r;
ee1         int p;
850         pair<ll, ll> idx; // {y, x}
36d         T val, mi;
bc2         node(ll x, ll y, T val_) : l(NULL), r(NULL), p(rng()),
1b5             idx(pair(y, x)), val(val_), mi(val) {}
01e         void update() {
d6e             mi = val;
182             if (l) mi = op(mi, l->mi);
b68             if (r) mi = op(mi, r->mi);
cbb         }
214     };

bb7     node* root;

84b     treap() { root = NULL; }
cec     ~treap() {
609         vector<node*> q = {root};
402         while (q.size()) {
e5d             node* x = q.back(); q.pop_back();
ee9             if (!x) continue;
1c7             q.push_back(x->l), q.push_back(x->r);
}
```

```

bf0         delete x;
cbb     }
cbb     }
225     treap(treap&& t) : treap() { swap(root, t.root); }

bcf     void join(node* l, node* r, node&& i) { // assume que l < r
986         if (!l or !r) return void(i = l ? l : r);
80e         if (l->p > r->p) join(l->r, r, l->r), i = l;
fa0         else join(l, r->l, r->l), i = r;
bda         i->update();
cbb     }
c82     void split(node* i, node&& l, node&& r, pair<ll, ll> idx) {
26a         if (!i) return void(r = l = NULL);
13c         if (i->idx < idx) split(i->r, i->r, r, idx), l = i;
d26         else split(i->l, l, i->l, idx), r = i;
bda         i->update();
cbb     }
d3b     void update(ll x, ll y, T v) {
df9         node *L, *M, *R;
8b2         split(root, M, R, pair(y, x+1)), split(M, L, M, pair(y,
x));
1e4         if (M) M->val = M->mi = v;
9e5         else M = new node(x, y, v);
69d         join(L, M, M), join(M, R, root);
cbb     }
91b     T query(ll ly, ll ry) {
df9         node *L, *M, *R;
1c0         split(root, M, R, pair(ry, LINF)), split(M, L, M,
pair(ly, 0));
0f7         T ret = M ? M->mi : ZERO;
69d         join(L, M, M), join(M, R, root);
edf         return ret;
cbb     }
214 };

46a     template<typename T> struct segtreap {
c4f         vector<treap<T>> seg;
6e7         vector<int> ch[2];
e4e         ll NX;

253         segtreap(ll NX_) : seg(1), NX(NX_) { ch[0].push_back(-1),
ch[1].push_back(-1); }

a71         int get_ch(int i, int d){
e51             if (ch[d][i] == -1) {
2d6                 ch[d][i] = seg.size();

```

```

23e             seg.emplace_back();
842             ch[0].push_back(-1), ch[1].push_back(-1);
cbb         }
968         return ch[d][i];
cbb     }

10c     T query(ll lx, ll rx, ll ly, ll ry, int p, ll l, ll r) {
003         if (rx < l or r < lx) return ZERO;
f0f         if (lx <= l and r <= rx) return seg[p].query(ly, ry);

e6a         ll m = l + (r-l)/2;
354         return op(query(lx, rx, ly, ry, get_ch(p, 0), l, m),
060             query(lx, rx, ly, ry, get_ch(p, 1), m+1, r));
cbb     }
f48     T query(ll lx, ll rx, ll ly, ll ry) { return query(lx, rx,
ly, ry, 0, 0, NX); }

249     void update(ll x, ll y, T val, int p, ll l, ll r) {
73c         if (l == r) return seg[p].update(x, y, val);
e6a         ll m = l + (r-l)/2;
cc5         if (x <= m) update(x, y, val, get_ch(p, 0), l, m);
5a2         else update(x, y, val, get_ch(p, 1), m+1, r);
980         seg[p].update(x, y, val);
cbb     }
517     void update(ll x, ll y, T val) { update(x, y, val, 0, 0,
NX); }
214 };

```

## 5.14 SegTree

```

// Recursiva com Lazy Propagation
// Query: soma do range [a, b]
// Update: soma x em cada elemento do range [a, b]
// Pode usar a seguinte funcao para indexar os nohs:
// f(l, r) = (l+r)|(l!=r), usando 2N de memoria
//
// Complexidades:
// build - O(n)
// query - O(log(n))
// update - O(log(n))

// 0afec1
aa4     namespace seg {
005         ll seg[4*MAX], lazy[4*MAX];

```

```

052     int n, *v;

d22     ll build(int p=1, int l=0, int r=n-1) {
3c7         lazy[p] = 0;
6cd         if (l == r) return seg[p] = v[l];
ee4         int m = (l+r)/2;
193         return seg[p] = build(2*p, l, m) + build(2*p+1, m+1, r);
cbb     }
0d8     void build(int n2, int* v2) {
680         n = n2, v = v2;
6f2         build();
cbb     }
ceb     void prop(int p, int l, int r) {
cdf         seg[p] += lazy[p]*(r-l+1);
2c9         if (l != r) lazy[2*p] += lazy[p], lazy[2*p+1] +=
lazy[p];
3c7         lazy[p] = 0;
cbb     }
2c3     ll query(int a, int b, int p=1, int l=0, int r=n-1) {
6b9         prop(p, l, r);
527         if (a <= l and r <= b) return seg[p];
786         if (b < l or r < a) return 0;
ee4         int m = (l+r)/2;
b1f         return query(a, b, 2*p, l, m) + query(a, b, 2*p+1, m+1,
r);
cbb     }
cfb     ll update(int a, int b, int x, int p=1, int l=0, int r=n-1)
{
6b9         prop(p, l, r);
9a3         if (a <= l and r <= b) {
b94             lazy[p] += x;
6b9             prop(p, l, r);
534             return seg[p];
cbb         }
e9f         if (b < l or r < a) return seg[p];
ee4         int m = (l+r)/2;
fdb         return seg[p] = update(a, b, x, 2*p, l, m) +
7fd             update(a, b, x, 2*p+1, m+1, r);
cbb     }
214 };

// Se tiver uma seg de max, da pra descobrir em O(log(n))
// o primeiro e ultimo elemento >= val numa range:

// primeira posicao >= val em [a, b] (ou -1 se nao tem)

```

```

// 68c3e5
119 int get_left(int a, int b, int val, int p=1, int l=0, int
r=n-1) {
6b9     prop(p, l, r);
f38     if (b < l or r < a or seg[p] < val) return -1;
205     if (r == l) return l;
ee4     int m = (l+r)/2;
753     int x = get_left(a, b, val, 2*p, l, m);
50e     if (x != -1) return x;
c3c     return get_left(a, b, val, 2*p+1, m+1, r);
cbb }

// ultima posicao >= val em [a, b] (ou -1 se nao tem)
// 1b71df
992 int get_right(int a, int b, int val, int p=1, int l=0, int
r=n-1) {
6b9     prop(p, l, r);
f38     if (b < l or r < a or seg[p] < val) return -1;
205     if (r == l) return l;
ee4     int m = (l+r)/2;
1b1     int x = get_right(a, b, val, 2*p+1, m+1, r);
50e     if (x != -1) return x;
6a7     return get_right(a, b, val, 2*p, l, m);
cbb }

// Se tiver uma seg de soma sobre um array nao negativo v, da
// pra
// descobrir em O(log(n)) o maior j tal que
// v[i]+v[i+1]+...+v[j-1] < val
// 2b8ea7
6a9 int lower_bound(int i, ll& val, int p, int l, int r) {
6b9     prop(p, l, r);
6e8     if (r < i) return n;
b5d     if (i <= l and seg[p] < val) {
bff         val -= seg[p];
041         return n;
cbb     }
3ce     if (l == r) return l;
ee4     int m = (l+r)/2;
514     int x = lower_bound(i, val, 2*p, l, m);
ee0     if (x != n) return x;
8b9     return lower_bound(i, val, 2*p+1, m+1, r);
cbb }

```

## 5.15 SegTree 2D Iterativa

```
// Consultas 0-based
// Um valor inicial em (x, y) deve ser colocado em seg[x+n][y+n]
// Query: soma do retangulo ((x1, y1), (x2, y2))
// Update: muda o valor da posicao (x, y) para val
// Nao pergunte como que essa coisa funciona
//
// Para query com distancia de manhattan <= d, faca
// nx = x+y, ny = x-y
// Update em (nx, ny), query em ((nx-d, ny-d), (nx+d, ny+d))
//
// Se for de min/max, pode tirar os if's da 'query', e fazer
// sempre as 4 operacoes. Fica mais rapido
//
// Complexidades:
// build - O(n^2)
// query - O(log^2(n))
// update - O(log^2(n))
// 67b9e5

731 int seg[2*MAX][2*MAX], n;

0a8 void build() {
919     for (int x = 2*n; x; x--) for (int y = 2*n; y; y--) {
c81         if (x < n) seg[x][y] = seg[2*x][y] + seg[2*x+1][y];
fe9         if (y < n) seg[x][y] = seg[x][2*y] + seg[x][2*y+1];
cbb     }
cbb }

251 int query(int x1, int y1, int x2, int y2) {
827     int ret = 0, y3 = y1 + n, y4 = y2 + n;
83e     for (x1 += n, x2 += n; x1 <= x2; ++x1 /= 2, --x2 /= 2)
0f2         for (y1 = y3, y2 = y4; y1 <= y2; ++y1 /= 2, --y2 /= 2) {
554             if (x1%2 == 1 and y1%2 == 1) ret += seg[x1][y1];
6b0             if (x1%2 == 1 and y2%2 == 0) ret += seg[x1][y2];
c01             if (x2%2 == 0 and y1%2 == 1) ret += seg[x2][y1];
5d4             if (x2%2 == 0 and y2%2 == 0) ret += seg[x2][y2];
cbb         }

edf     return ret;
cbb }

767 void update(int x, int y, int val) {
66a     int y2 = y += n;
192     for (x += n; x; x /= 2, y = y2) {
```

```
970         if (x >= n) seg[x][y] = val;
ba9         else seg[x][y] = seg[2*x][y] + seg[2*x+1][y];

3b1         while (y /= 2) seg[x][y] = seg[x][2*y] + seg[x][2*y+1];
cbb     }
cbb }
```

## 5.16 SegTree Beats

```
// query(a, b) - {{min(v[a..b]), max(v[a..b])}, sum(v[a..b])}
// updatemin(a, b, x) faz com que v[i] <- min(v[i], x),
// para i em [a, b]
// updatemax faz o mesmo com max, e updatesum soma x
// em todo mundo do intervalo [a, b]
//
// Complexidades:
// build - O(n)
// query - O(log(n))
// update - O(log^2(n)) amortizado
// (se nao usar updatesum, fica log(n) amortizado)
// 41672b
```

```
7c6 #define f first
0ab #define s second

f39 namespace beats {
3c9     struct node {
526         int tam;
125         ll sum, lazy; // lazy pra soma
4f3         ll mi1, mi2, mi; // mi = #mi1
c61         ll ma1, ma2, ma; // ma = #ma1

426         node(ll x = 0) {
ba6             sum = mi1 = ma1 = x;
b29             mi2 = LINF, ma2 = -LINF;
62c             mi = ma = tam = 1;
c60             lazy = 0;
cbb         }

770         node(const node& l, const node& r) {
a95             sum = l.sum + r.sum, tam = l.tam + r.tam;
c60             lazy = 0;
797             if (l.mi1 > r.mi1) {
230                 mi1 = r.mi1, mi = r.mi;
ea2                 mi2 = min(l.mi1, r.mi2);
```

```

dcd      } else if (l.mi1 < r.mi1) {
e34          mi1 = l.mi1, mi = l.mi;
4b3          mi2 = min(r.mi1, l.mi2);
9d9      } else {
a39          mi1 = l.mi1, mi = l.mi+r.mi;
83d          mi2 = min(l.mi2, r.mi2);
cbb      }
cd0      if (l.ma1 < r.ma1) {
6a0          ma1 = r.ma1, ma = r.ma;
96d          ma2 = max(l.ma1, r.ma2);
5f0      } else if (l.ma1 > r.ma1) {
ae0          ma1 = l.ma1, ma = l.ma;
2ca          ma2 = max(r.ma1, l.ma2);
9d9      } else {
db2          ma1 = l.ma1, ma = l.ma+r.ma;
c05          ma2 = max(l.ma2, r.ma2);
cbb      }
cbb      }
4b4      void setmin(ll x) {
55e          if (x >= ma1) return;
463          sum += (x - ma1)*ma;
be5          if (mi1 == ma1) mi1 = x;
0a0          if (mi2 == ma1) mi2 = x;
b81          ma1 = x;
cbb      }
6cb      void setmax(ll x) {
e25          if (x <= mi1) return;
7e8          sum += (x - mi1)*mi;
0bb          if (ma1 == mi1) ma1 = x;
c32          if (ma2 == mi1) ma2 = x;
1ff          mi1 = x;
cbb      }
4cf      void setsum(ll x) {
fe8          mi1 += x, mi2 += x, ma1 += x, ma2 += x;
620          sum += x*tam;
c46          lazy += x;
cbb      }
214      };

62b      node seg[4*MAX];
052      int n, *v;

93b      node build(int p=1, int l=0, int r=n-1) {
d84          if (l == r) return seg[p] = {v[l]};
ee4          int m = (l+r)/2;
3d6          return seg[p] = {build(2*p, l, m), build(2*p+1, m+1,

```

```

r)}};
cbb      }
0d8      void build(int n2, int* v2) {
680          n = n2, v = v2;
6f2          build();
cbb      }
ceb      void prop(int p, int l, int r) {
8ce          if (l == r) return;
abd          for (int k = 0; k < 2; k++) {
d07              if (seg[p].lazy) seg[2*p+k].setsum(seg[p].lazy);
843              seg[2*p+k].setmin(seg[p].ma1);
f79              seg[2*p+k].setmax(seg[p].mi1);
cbb          }
431          seg[p].lazy = 0;
cbb      }
055      pair<pair<ll, ll>, ll> query(int a, int b, int p=1, int
l=0, int r=n-1) {
e07          if (b < l or r < a) return {{LINF, -LINF}, 0};
9be          if (a <= l and r <= b) return {{seg[p].mi1,
seg[p].ma1}, seg[p].sum};
6b9          prop(p, l, r);
ee4          int m = (l+r)/2;
e6f          auto L = query(a, b, 2*p, l, m), R = query(a, b, 2*p+1,
m+1, r);
96d          return {{min(L.f.f, R.f.f), max(L.f.s, R.f.s)},
L.s+R.s};
cbb      }
2c8      node updatemin(int a, int b, ll x, int p=1, int l=0, int
r=n-1) {
744          if (b < l or r < a or seg[p].ma1 <= x) return seg[p];
309          if (a <= l and r <= b and seg[p].ma2 < x) {
ccd              seg[p].setmin(x);
534              return seg[p];
cbb          }
6b9          prop(p, l, r);
ee4          int m = (l+r)/2;
96a          return seg[p] = {updatemin(a, b, x, 2*p, l, m),
faf              updatemin(a, b, x, 2*p+1, m+1, r)};
cbb      }
044      node updatemax(int a, int b, ll x, int p=1, int l=0, int
r=n-1) {
b59          if (b < l or r < a or seg[p].mi1 >= x) return seg[p];
a9e          if (a <= l and r <= b and seg[p].mi2 > x) {
e8a              seg[p].setmax(x);
534              return seg[p];
cbb          }

```

```

6b9         prop(p, l, r);
ee4         int m = (l+r)/2;
ee3         return seg[p] = {updatemax(a, b, x, 2*p, l, m),
bd2             updatemax(a, b, x, 2*p+1, m+1, r)};
cbb     }
aee     node updatesum(int a, int b, ll x, int p=1, int l=0, int
r=n-1) {
e9f         if (b < l or r < a) return seg[p];
9a3         if (a <= l and r <= b) {
8f4             seg[p].setsum(x);
534             return seg[p];
cbb         }
6b9         prop(p, l, r);
ee4         int m = (l+r)/2;
7b6         return seg[p] = {updatesum(a, b, x, 2*p, l, m),
ddb             updatesum(a, b, x, 2*p+1, m+1, r)};
cbb     }
214 };

```

## 5.17 SegTree Colorida

```

// Cada posicao tem um valor e uma cor
// 0 construtor recebe um vector de {valor, cor}
// e o numero de cores (as cores devem estar em [0, c-1])
// query(c, a, b) retorna a soma dos valores
// de todo mundo em [a, b] que tem cor c
// update(c, a, b, x) soma x em todo mundo em
// [a, b] que tem cor c
// paint(c1, c2, a, b) faz com que todo mundo
// em [a, b] que tem cor c1 passe a ter cor c2
//
// Complexidades:
// construir - O(n log(n)) espaco e tempo
// query - O(log(n))
// update - O(log(n))
// paint - O(log(n)) amortizado
// 2938e8

04f struct seg_color {
3c9     struct node {
b19         node *l, *r;
0f9         int cnt;
9ca         ll val, lazy;
277         node() : l(NULL), r(NULL), cnt(0), val(0), lazy(0) {}

```

```

01e     void update() {
d0a         cnt = 0, val = 0;
bc4         for (auto i : {l, r}) if (i) {
c89             i->prop();
281             cnt += i->cnt, val += i->val;
cbb         }
cbb     }
a9c     void prop() {
2dd         if (!lazy) return;
3f7         val += lazy*(ll)cnt;
b64         for (auto i : {l, r}) if (i) i->lazy += lazy;
c60         lazy = 0;
cbb     }
214 };

1a8     int n;
9b0     vector<node*> seg;

6e0     seg_color(vector<pair<int, int>>& v, int c) : n(v.size()),
seg(c, NULL) {
830         for (int i = 0; i < n; i++)
9b7             seg[v[i].second] = insert(seg[v[i].second], i,
v[i].first, 0, n-1);
cbb     }
3c7     ~seg_color() {
dde         queue<node*> q;
3a6         for (auto i : seg) q.push(i);
402         while (q.size()) {
20b             auto i = q.front(); q.pop();
dab             if (!i) continue;
7c7             q.push(i->l), q.push(i->r);
5ce             delete i;
cbb         }
cbb     }

40b     node* insert(node* at, int idx, int val, int l, int r) {
1a4         if (!at) at = new node();
232         if (l == r) return at->cnt = 1, at->val = val, at;
ee4         int m = (l+r)/2;
137         if (idx <= m) at->l = insert(at->l, idx, val, l, m);
3e6         else at->r = insert(at->r, idx, val, m+1, r);
cff         return at->update(), at;
cbb     }
870     ll query(node* at, int a, int b, int l, int r) {
61b         if (!at or b < l or r < a) return 0;
d9f         at->prop();

```

```

cb2         if (a <= l and r <= b) return at->val;
ee4         int m = (l+r)/2;
4c4         return query(at->l, a, b, l, m) + query(at->r, a, b,
m+1, r);
cbb     }
e54     ll query(int c, int a, int b) { return query(seg[c], a, b,
0, n-1); }
91c     void update(node* at, int a, int b, int x, int l, int r) {
fba         if (!at or b < l or r < a) return;
d9f         at->prop();
9a3         if (a <= l and r <= b) {
e9a             at->lazy += x;
cb2             return void(at->prop());
cbb         }
ee4         int m = (l+r)/2;
0b0         update(at->l, a, b, x, l, m), update(at->r, a, b, x,
m+1, r);
7b4         at->update();
cbb     }
a40     void update(int c, int a, int b, int x) { update(seg[c], a,
b, x, 0, n-1); }
70c     void paint(node*& from, node*& to, int a, int b, int l, int
r) {
10f         if (to == from or !from or b < l or r < a) return;
e85         from->prop();
889         if (to) to->prop();
9a3         if (a <= l and r <= b) {
24d             if (!to) {
38f                 to = from;
140                 from = NULL;
505                 return;
cbb             }
ee4             int m = (l+r)/2;
1cb             paint(from->l, to->l, a, b, l, m), paint(from->r,
to->r, a, b, m+1, r);
72d             to->update();
270             delete from;
140             from = NULL;
505             return;
cbb         }
019         if (!to) to = new node();
ee4         int m = (l+r)/2;
1cb         paint(from->l, to->l, a, b, l, m), paint(from->r,
to->r, a, b, m+1, r);
45a         from->update(), to->update();
cbb     }

```

```

471     void paint(int c1, int c2, int a, int b) { paint(seg[c1],
seg[c2], a, b, 0, n-1); }
214 };

```

## 5.18 SegTree Esparsa - Lazy

```

// Query: soma do range [a, b]
// Update: flipa os valores de [a, b]
// 0 MAX tem q ser Q log N para Q updates
//
// Complexidades:
// build - O(1)
// query - O(log(n))
// update - O(log(n))
// dc37e6

```

```

aa4 namespace seg {
6de     int seg[MAX], lazy[MAX], R[MAX], L[MAX], ptr;
e9a     int get_l(int i){
3db         if (L[i] == 0) L[i] = ptr++;
a96         return L[i];
cbb     }
943     int get_r(int i){
71b         if (R[i] == 0) R[i] = ptr++;
283         return R[i];
cbb     }

e71     void build() { ptr = 2; }

ceb     void prop(int p, int l, int r) {
b77         if (!lazy[p]) return;
76c         seg[p] = r-l+1 - seg[p];
213         if (l != r) lazy[get_l(p)] ^= lazy[p],
lazy[get_r(p)] ^= lazy[p];
3c7         lazy[p] = 0;
cbb     }

158     int query(int a, int b, int p=1, int l=0, int r=N-1) {
6b9         prop(p, l, r);
786         if (b < l or r < a) return 0;
527         if (a <= l and r <= b) return seg[p];

ee4         int m = (l+r)/2;

```



```

818         return query(a, b, get_l(p), l, m)+query(a, b,
get_r(p), m+1, r);
cbb     }

51f     int update(int a, int b, int p=1, int l=0, int r=N-1) {
6b9         prop(p, l, r);
e9f         if (b < l or r < a) return seg[p];
9a3         if (a <= l and r <= b) {
ab6             lazy[p] ^= 1;
6b9             prop(p, l, r);
534             return seg[p];
cbb         }
ee4         int m = (l+r)/2;
43a         return seg[p] = update(a, b, get_l(p), l, m)+update(a,
b, get_r(p), m+1, r);
cbb     }
214 };

```

## 5.19 SegTree Esparsa - $O(q)$ memoria

```

// Query: min do range [a, b]
// Update: troca o valor de uma posicao
// Usa  $O(q)$  de memoria para q updates
//
// Complexidades:
// query -  $O(\log(n))$ 
// update -  $O(\log(n))$ 
// 072a21

```

```

13d template<typename T> struct seg {
3c9     struct node {
d53         node* ch[2];
970         char d;
ca0         T v;

c4e         T mi;

d4e         node(int d_, T v_, T val) : d(d_), v(v_) {
e71             ch[0] = ch[1] = NULL;
d6e             mi = val;
cbb         }
b32         node(node* x) : d(x->d), v(x->v), mi(x->mi) {
c99             ch[0] = x->ch[0], ch[1] = x->ch[1];
cbb         }

```

```

01e     void update() {
909         mi = numeric_limits<T>::max();
151         for (int i = 0; i < 2; i++) if (ch[i])
b5a             mi = min(mi, ch[i]->mi);
cbb     }
214 };

bb7     node* root;
9c5     char n;

ba7     seg() : root(NULL), n(0) {}
512 ~seg() {
4c0         std::vector<node*> q = {root};
402         while (q.size()) {
e5d             node* x = q.back(); q.pop_back();
ee9             if (!x) continue;
73f             q.push_back(x->ch[0]), q.push_back(x->ch[1]);
bf0             delete x;
cbb         }
cbb     }

1a6     char msb(T v, char l, char r) { // msb in range (l, r]
8e4         for (char i = r; i > l; i--) if (v>>i&1) return i;
daa         return -1;
cbb     }

430     void cut(node* at, T v, char i) {
677         char d = msb(v ^ at->v, at->d, i);
23b         if (d == -1) return; // no need to split
ebf         node* nxt = new node(at);
d43         at->ch[v>>d&1] = NULL;
34f         at->ch[!(v>>d&1)] = nxt;
150         at->d = d;
cbb     }

6e5     node* update(node* at, T idx, T val, char i) {
c8c         if (!at) return new node(-1, idx, val);
d67         cut(at, idx, i);
1a2         if (at->d == -1) { // leaf
792             at->mi = val;
ce6             return at;
cbb         }
b29         bool dir = idx>>at->d&1;
c8f         at->ch[dir] = update(at->ch[dir], idx, val, at->d-1);
7b4         at->update();
ce6         return at;
cbb     }

```

```

85c void update(T idx, T val) {
8f4 while (idx>>n) n++;
61e root = update(root, idx, val, n-1);
cbb }

9d8 T query(node* at, T a, T b, T l, T r, char i) {
df0 if (!at or b < l or r < a) return
numeric_limits<T>::max();
fd3 if (a <= l and r <= b) return at->mi;
841 T m = l + (r-l)/2;
c85 if (at->d < i) {
c59 if ((at->v>>i&1) == 0) return query(at, a, b, l, m,
i-1);
ca4 else return query(at, a, b, m+1, r, i-1);
cbb }
373 return min(query(at->ch[0], a, b, l, m, i-1),
query(at->ch[1], a, b, m+1, r, i-1));
cbb }
6f6 T query(T l, T r) { return query(root, l, r, 0, (1<<n)-1,
n-1); }
214 };

```

## 5.20 SegTree Iterativa

```

// Consultas 0-based
// Valores iniciais devem estar em (seg[n], ... , seg[2*n-1])
// Query: soma do range [a, b]
// Update: muda o valor da posicao p para x
//
// Complexidades:
// build - O(n)
// query - O(log(n))
// update - O(log(n))
// 779519

6a4 int seg[2 * MAX];
1a8 int n;

0a8 void build() {
d15 for (int i = n - 1; i; i--) seg[i] = seg[2*i] + seg[2*i+1];
cbb }

4ea int query(int a, int b) {
7c9 int ret = 0;

```

```

728 for(a += n, b += n; a <= b; ++a /= 2, --b /= 2) {
4ea if (a % 2 == 1) ret += seg[a];
244 if (b % 2 == 0) ret += seg[b];
cbb }
edf return ret;
cbb }

ff3 void update(int p, int x) {
37d seg[p += n] = x;
c8c while (p /= 2) seg[p] = seg[2*p] + seg[2*p+1];
cbb }

```

## 5.21 SegTree Iterativa com Lazy Propagation

```

// Query: soma do range [a, b]
// Update: soma x em cada elemento do range [a, b]
// Para mudar, mudar as funcoes junta, poe e query
// LOG = ceil(log2(MAX))
//
// Complexidades:
// build - O(n)
// query - O(log(n))
// update - O(log(n))
// 6dc475

aa4 namespace seg {
6db ll seg[2*MAX], lazy[2*MAX];
1a8 int n;

9b3 ll junta(ll a, ll b) {
534 return a+b;
cbb }

// soma x na posicao p de tamanho tam
1b4 void poe(int p, ll x, int tam, bool prop=1) {
517 seg[p] += x*tam;
6ae if (prop and p < n) lazy[p] += x;
cbb }

// atualiza todos os pais da folha p
b1e void sobe(int p) {
d5a for (int tam = 2; p /= 2; tam *= 2) {
4ca seg[p] = junta(seg[2*p], seg[2*p+1]);
388 poe(p, lazy[p], tam, 0);

```

```

cbb      }
cbb      }

// propaga o caminho da raiz ate a folha p
a0a void prop(int p) {
076     int tam = 1 << (LOG-1);
0a8     for (int s = LOG; s; s--, tam /= 2) {
4b1         int i = p >> s;
27c         if (lazy[i]) {
860             poe(2*i, lazy[i], tam);
e38             poe(2*i+1, lazy[i], tam);
b97             lazy[i] = 0;
cbb         }
cbb     }
cbb }

61c void build(int n2, int* v) {
1e3     n = n2;
95f     for (int i = 0; i < n; i++) seg[n+i] = v[i];
c41     for (int i = n-1; i; i--) seg[i] = junta(seg[2*i],
seg[2*i+1]);
f4c     for (int i = 0; i < 2*n; i++) lazy[i] = 0;
cbb }

4f3 ll query(int a, int b) {
b73     ll ret = 0;
b48     for (prop(a+=n), prop(b+=n); a <= b; ++a/=2, --b/=2) {
a8e         if (a%2 == 1) ret = junta(ret, seg[a]);
c58         if (b%2 == 0) ret = junta(ret, seg[b]);
cbb     }
edf     return ret;
cbb }

a28 void update(int a, int b, int x) {
c2d     int a2 = a += n, b2 = b += n, tam = 1;
0ff     for (; a <= b; ++a/=2, --b/=2, tam *= 2) {
32a         if (a%2 == 1) poe(a, x, tam);
9da         if (b%2 == 0) poe(b, x, tam);
cbb     }
0f7     sobe(a2), sobe(b2);
cbb }
214 };

```

## 5.22 SegTree PA

```

// Segtree de PA
// update_set(l, r, A, R) seta [l, r] para PA(A, R),
// update_add soma PA(A, R) em [l, r]
// query(l, r) retorna a soma de [l, r]
//
// PA(A, R) eh a PA: [A+R, A+2R, A+3R, ... ]
//
// Complexidades:
// construir - O(n)
// update_set, update_add, query - O(log(n))
// bc4746

dc7 struct seg_pa {
350     struct Data {
8f5         ll sum;
662         ll set_a, set_r, add_a, add_r;
9b7         Data() : sum(0), set_a(LINF), set_r(0), add_a(0),
add_r(0) {}
214     };
16a     vector<Data> seg;
1a8     int n;

d45     seg_pa(int n_) {
e95         n = n_;
fc3         seg = vector<Data>(4*n);
cbb     }

ceb     void prop(int p, int l, int r) {
d5a         int tam = r-l+1;
c3f         ll &sum = seg[p].sum, &set_a = seg[p].set_a, &set_r =
seg[p].set_r,
a1b         &add_a = seg[p].add_a, &add_r = seg[p].add_r;

c02         if (set_a != LINF) {
660             set_a += add_a, set_r += add_r;
06e             sum = set_a*tam + set_r*tam*(tam+1)/2;
579             if (l != r) {
ee4                 int m = (l+r)/2;

886                 seg[2*p].set_a = set_a;
358                 seg[2*p].set_r = set_r;
ed6                 seg[2*p].add_a = seg[2*p].add_r = 0;

f0c                 seg[2*p+1].set_a = set_a + set_r * (m-l+1);
471                 seg[2*p+1].set_r = set_r;
d48                 seg[2*p+1].add_a = seg[2*p+1].add_r = 0;

```

```

cbb        }
823        set_a = LINF, set_r = 0;
953        add_a = add_r = 0;
105    } else if (add_a or add_r) {
18b        sum += add_a*tam + add_r*tam*(tam+1)/2;
579        if (l != r) {
ee4            int m = (l+r)/2;

ffa0        seg[2*p].add_a += add_a;
ec0        seg[2*p].add_r += add_r;

06c        seg[2*p+1].add_a += add_a + add_r * (m-l+1);
a6d        seg[2*p+1].add_r += add_r;
cbb    }
953    add_a = add_r = 0;
cbb    }
cbb    }

0b7    int inter(pair<int, int> a, pair<int, int> b) {
98c        if (a.first > b.first) swap(a, b);
eef        return max(0, min(a.second, b.second) - b.first + 1);
cbb    }
be1    ll set(int a, int b, ll aa, ll rr, int p, int l, int r) {
6b9        prop(p, l, r);
457        if (b < l or r < a) return seg[p].sum;
9a3        if (a <= l and r <= b) {
91c            seg[p].set_a = aa;
774            seg[p].set_r = rr;
6b9            prop(p, l, r);
254            return seg[p].sum;
cbb        }
ee4        int m = (l+r)/2;
963        int tam_l = inter({l, m}, {a, b});
c34        return seg[p].sum = set(a, b, aa, rr, 2*p, l, m) +
365            set(a, b, aa + rr * tam_l, rr, 2*p+1, m+1, r);
cbb    }
f55    void update_set(int l, int r, ll aa, ll rr) {
6f7        set(l, r, aa, rr, 1, 0, n-1);
cbb    }
5f6    ll add(int a, int b, ll aa, ll rr, int p, int l, int r) {
6b9        prop(p, l, r);
457        if (b < l or r < a) return seg[p].sum;
9a3        if (a <= l and r <= b) {
359            seg[p].add_a += aa;
1ee            seg[p].add_r += rr;
6b9            prop(p, l, r);

```

```

254        return seg[p].sum;
cbb    }
ee4    int m = (l+r)/2;
963    int tam_l = inter({l, m}, {a, b});
586    return seg[p].sum = add(a, b, aa, rr, 2*p, l, m) +
695        add(a, b, aa + rr * tam_l, rr, 2*p+1, m+1, r);
cbb    }
848    void update_add(int l, int r, ll aa, ll rr) {
afa        add(l, r, aa, rr, 1, 0, n-1);
cbb    }
f45    ll query(int a, int b, int p, int l, int r) {
6b9        prop(p, l, r);
786        if (b < l or r < a) return 0;
e9a        if (a <= l and r <= b) return seg[p].sum;
ee4        int m = (l+r)/2;
b1f        return query(a, b, 2*p, l, m) + query(a, b, 2*p+1, m+1,
r);
cbb    }
bfc    ll query(int l, int r) { return query(l, r, 1, 0, n-1); }
214 };

```

## 5.23 SegTree Persistente

```

// SegTree de soma, update de somar numa posicao
//
// query(a, b, t) retorna a query de [a, b] na versao t
// update(a, x, t) faz um update v[a]+=x a partir da
// versao de t, criando uma nova versao e retornando seu id
// Por default, faz o update a partir da ultima versao
//
// build - O(n)
// query - O(log(n))
// update - O(log(n))
// 50ab73

```

```

54a const int MAX = 1e5+10, UPD = 1e5+10, LOG = 18;
6de const int MAXS = 2*MAX+UPD*LOG;

```

```

f6e namespace perseg {
bd6     ll seg[MAXS];
f4e     int rt[UPD], L[MAXS], R[MAXS], cnt, t;
052     int n, *v;

```

```

3c4     ll build(int p, int l, int r) {

```

```

6cd         if (l == r) return seg[p] = v[l];
855         L[p] = cnt++, R[p] = cnt++;
ee4         int m = (l+r)/2;
275         return seg[p] = build(L[p], l, m) + build(R[p], m+1, r);
cbb     }
0d8     void build(int n2, int* v2) {
680         n = n2, v = v2;
856         rt[0] = cnt++;
c50         build(0, 0, n-1);
cbb     }
f45     ll query(int a, int b, int p, int l, int r) {
786         if (b < l or r < a) return 0;
527         if (a <= l and r <= b) return seg[p];
ee4         int m = (l+r)/2;
1ed         return query(a, b, L[p], l, m) + query(a, b, R[p], m+1,
r);
cbb     }
182     ll query(int a, int b, int tt) {
c13         return query(a, b, rt[tt], 0, n-1);
cbb     }
bb3     ll update(int a, int x, int lp, int p, int l, int r) {
747         if (l == r) return seg[p] = seg[lp]+x;
ee4         int m = (l+r)/2;
ab8         if (a <= m)
b48             return seg[p] = update(a, x, L[lp], L[p]=cnt++, l,
m) + seg[R[p]=R[lp]];
8a9         return seg[p] = seg[L[p]=L[lp]] + update(a, x, R[lp],
R[p]=cnt++, m+1, r);
cbb     }
6f6     int update(int a, int x, int tt=t) {
ab3         update(a, x, rt[tt], rt[tt]=cnt++, 0, n-1);
e0d         return t;
cbb     }
214 };

```

## 5.24 Sparse Table

```

// Resolve RMQ
// MAX2 = log(MAX)
//
// Complexidades:
// build - O(n log(n))
// query - O(1)
// 7aa4c9

```

```

cca namespace sparse {
710     int m[MAX2][MAX], n;
61c     void build(int n2, int* v) {
1e3         n = n2;
78e         for (int i = 0; i < n; i++) m[0][i] = v[i];
a1c         for (int j = 1; (1<<j) <= n; j++) for (int i = 0;
i+(1<<j) <= n; i++)
5d5             m[j][i] = min(m[j-1][i], m[j-1][i+(1<<(j-1))]);
cbb     }
4ea     int query(int a, int b) {
ee5         int j = __builtin_clz(1) - __builtin_clz(b-a+1);
dc3         return min(m[j][a], m[j][b-(1<<j)+1]);
cbb     }
cbb }

```

## 5.25 Sparse Table Disjunta

```

// Resolve qualquer operacao associativa
// MAX2 = log(MAX)
//
// Complexidades:
// build - O(n log(n))
// query - O(1)
// fd81ae

```

```

cca namespace sparse {
9bf     int m[MAX2][2*MAX], n, v[2*MAX];
5f7     int op(int a, int b) { return min(a, b); }
0d8     void build(int n2, int* v2) {
1e3         n = n2;
df4         for (int i = 0; i < n; i++) v[i] = v2[i];
a84         while (n&(n-1)) n++;
3d2         for (int j = 0; (1<<j) < n; j++) {
1c0             int len = 1<<j;
d9b             for (int c = len; c < n; c += 2*len) {
332                 m[j][c] = v[c], m[j][c-1] = v[c-1];
668                 for (int i = c+1; i < c+len; i++) m[j][i] =
op(m[j][i-1], v[i]);
432                 for (int i = c-2; i >= c-len; i--) m[j][i] =
op(v[i], m[j][i+1]);
cbb             }
cbb         }
cbb     }

```

```

9e3     int query(int l, int r) {
f13         if (l == r) return v[l];
e6d         int j = __builtin_clz(l) - __builtin_clz(l^r);
d67         return op(m[j][l], m[j][r]);
cbb     }
cbb }

```

## 5.26 Splay Tree

```

// SEMPRE QUE DESCER NA ARVORE, DAR SPLAY NO
// NODE MAIS PROFUNDO VISITADO
// Todas as operacoes sao O(log(n)) amortizado
// Se quiser colocar mais informacao no node,
// mudar em 'update'
// 4ff2b3

```

```

538 template<typename T> struct splaytree {
3c9     struct node {
183         node *ch[2], *p;
e4d         int sz;
f48         T val;
da0         node(T v) {
696             ch[0] = ch[1] = p = NULL;
a26             sz = 1;
250             val = v;
cbb         }
01e         void update() {
a26             sz = 1;
c7c             for (int i = 0; i < 2; i++) if (ch[i]) {
d5f                 sz += ch[i]->sz;
cbb             }
cbb         }
214     };

bb7     node* root;

fbc     splaytree() { root = NULL; }
214     splaytree(const splaytree& t) {
cbf         throw logic_error("Nao copiar a splaytree!");
cbb     }
891     ~splaytree() {
609         vector<node*> q = {root};
402         while (q.size()) {
e5d             node* x = q.back(); q.pop_back();

```

```

ee9         if (!x) continue;
73f         q.push_back(x->ch[0]), q.push_back(x->ch[1]);
bf0         delete x;
cbb     }
cbb }

94f void rotate(node* x) { // x vai ficar em cima
d9b     node *p = x->p, *pp = p->p;
ecf     if (pp) pp->ch[pp->ch[1] == p] = x;
286     bool d = p->ch[0] == x;
d63     p->ch[!d] = x->ch[d], x->ch[d] = p;
bad     if (p->ch[!d]) p->ch[!d]->p = p;
fc2     x->p = pp, p->p = x;
1ea     p->update(), x->update();
cbb }
3fa node* splay(node* x) {
a39     if (!x) return x;
4ea     root = x;
3cf     while (x->p) {
d9b         node *p = x->p, *pp = p->p;
359         if (!pp) return rotate(x), x; // zig
e3c         if ((pp->ch[0] == p)^(p->ch[0] == x))
a2b             rotate(x), rotate(x); // zigzag
4b2         else rotate(p), rotate(x); // zigzig
cbb     }
ea5     return x;
cbb }
313 node* insert(T v, bool lb=0) {
b64     if (!root) return lb ? NULL : root = new node(v);
002     node *x = root, *last = NULL;;
31e     while (1) {
5d7         bool d = x->val < v;
0fd         if (!d) last = x;
c2e         if (x->val == v) break;
c16         if (x->ch[d]) x = x->ch[d];
4e6         else {
dea             if (lb) break;
055             x->ch[d] = new node(v);
99c             x->ch[d]->p = x;
30e             x = x->ch[d];
c2b             break;
cbb         }
cbb     }
0b6     splay(x);
61c     return lb ? splay(last) : x;
cbb }

```

```

c0c    int size() { return root ? root->sz : 0; }
2ca    int count(T v) { return insert(v, 1) and root->val == v; }
111    node* lower_bound(T v) { return insert(v, 1); }
26b    void erase(T v) {
446        if (!count(v)) return;
bce        node *x = root, *l = x->ch[0];
268        if (!l) {
8b1            root = x->ch[1];
32e            if (root) root->p = NULL;
8f3            return delete x;
cbb        }
5e7        root = l, l->p = NULL;
902        while (l->ch[1]) l = l->ch[1];
bab        splay(l);
f0e        l->ch[1] = x->ch[1];
7d9        if (l->ch[1]) l->ch[1]->p = l;
bf0        delete x;
62a        l->update();
cbb    }
24a    int order_of_key(T v) {
62b        if (!lower_bound(v)) return root ? root->sz : 0;
1cc        return root->ch[0] ? root->ch[0]->sz : 0;
cbb    }
db6    node* find_by_order(int k) {
084        if (k >= size()) return NULL;
52f        node* x = root;
31e        while (1) {
20f            if (x->ch[0] and x->ch[0]->sz >= k+1) x = x->ch[0];
4e6            else {
a1c                if (x->ch[0]) k -= x->ch[0]->sz;
1dc                if (!k) return splay(x);
eb8                k--, x = x->ch[1];
cbb            }
cbb        }
cbb    }
19c    T min() {
52f        node* x = root;
6f6        while (x->ch[0]) x = x->ch[0]; // max -> ch[1]
3e9        return splay(x)->val;
cbb    }
214 };

```

## 5.27 Splay Tree Implicita

```

// vector da NASA
// Um pouco mais rapido q a treap
// 0 construtor a partir do vector
// eh linear, todas as outras operacoes
// custam O(log(n)) amortizado
// a3575a

081 template<typename T> struct splay {
3c9     struct node {
183         node *ch[2], *p;
e4d         int sz;
875         T val, sub, lazy;
aa6         bool rev;
da0         node(T v) {
696             ch[0] = ch[1] = p = NULL;
a26             sz = 1;
1e4             sub = val = v;
c60             lazy = 0;
b67             rev = false;
cbb         }
a9c         void prop() {
0ec             if (lazy) {
924                 val += lazy, sub += lazy*sz;
091                 if (ch[0]) ch[0]->lazy += lazy;
1a8                 if (ch[1]) ch[1]->lazy += lazy;
cbb             }
1bb             if (rev) {
80a                 swap(ch[0], ch[1]);
628                 if (ch[0]) ch[0]->rev ^= 1;
adc                 if (ch[1]) ch[1]->rev ^= 1;
cbb             }
a32             lazy = 0, rev = 0;
cbb         }
01e         void update() {
0c3             sz = 1, sub = val;
c7c             for (int i = 0; i < 2; i++) if (ch[i]) {
05f                 ch[i]->prop();
d5f                 sz += ch[i]->sz;
4a1                 sub += ch[i]->sub;
cbb             }
cbb         }
214     };

bb7     node* root;

5d9     splay() { root = NULL; }

```

```

9b1  splay(node* x) {
4ea      root = x;
32e      if (root) root->p = NULL;
cbb  }
1b7  splay(vector<T> v) { // O(n)
950      root = NULL;
806      for (T i : v) {
2a0          node* x = new node(i);
bd1          x->ch[0] = root;
37a          if (root) root->p = x;
4ea          root = x;
a0a          root->update();
cbb      }
cbb  }
a9e  splay(const splay& t) {
e62      throw logic_error("Nao copiar a splay!");
cbb  }
5ab  ~splay() {
609      vector<node*> q = {root};
402      while (q.size()) {
e5d          node* x = q.back(); q.pop_back();
ee9          if (!x) continue;
73f          q.push_back(x->ch[0]), q.push_back(x->ch[1]);
bf0          delete x;
cbb      }
cbb  }

73c  int size(node* x) { return x ? x->sz : 0; }
94f  void rotate(node* x) { // x vai ficar em cima
d9b      node *p = x->p, *pp = p->p;
ecf      if (pp) pp->ch[pp->ch[1] == p] = x;
286      bool d = p->ch[0] == x;
d63      p->ch[!d] = x->ch[d], x->ch[d] = p;
bad      if (p->ch[!d]) p->ch[!d]->p = p;
fc2      x->p = pp, p->p = x;
1ea      p->update(), x->update();
cbb  }

6a0  node* splaya(node* x) {
a39      if (!x) return x;
be6      root = x, x->update();
3cf      while (x->p) {
d9b          node *p = x->p, *pp = p->p;
359          if (!pp) return rotate(x), x; // zig
e3c          if ((pp->ch[0] == p)^(p->ch[0] == x))
a2b              rotate(x), rotate(x); // zigzag
4b2          else rotate(p), rotate(x); // zigzig

```

```

cbb      }
ea5      return x;
cbb  }
a7f  node* find(int v) {
a2e      if (!root) return NULL;
52f      node *x = root;
6cd      int key = 0;
31e      while (1) {
857          x->prop();
ba1          bool d = key + size(x->ch[0]) < v;
877          if (key + size(x->ch[0]) != v and x->ch[d]) {
15e              if (d) key += size(x->ch[0])+1;
30e              x = x->ch[d];
9af          } else break;
cbb      }
152      return splaya(x);
cbb  }
c0c  int size() { return root ? root->sz : 0; }
c26  void join(splay<T>& l) { // assume que l < *this
690      if (!size()) swap(root, l.root);
579      if (!size() or !l.size()) return;
bee      node* x = l.root;
31e      while (1) {
857          x->prop();
34d          if (!x->ch[1]) break;
bd8          x = x->ch[1];
cbb      }
147      l.splaya(x), root->prop(), root->update();
42b      x->ch[1] = root, x->ch[1]->p = x;
0aa      root = l.root, l.root = NULL;
a0a      root->update();
cbb  }
5ed  node* split(int v) { // retorna os elementos < v
398      if (v <= 0) return NULL;
060      if (v >= size()) {
f87          node* ret = root;
950          root = NULL;
8c9          ret->update();
edf          return ret;
cbb      }
adc      find(v);
a59      node* l = root->ch[0];
4df      root->ch[0] = NULL;
5a3      if (l) l->p = NULL;
a0a      root->update();
792      return l;

```



```

cbb     }
511     T& operator [] (int i) {
9d4         find(i);
ae0         return root->val;
cbb     }
231     void push_back(T v) { // 0(1)
a01         node* r = new node(v);
0de         r->ch[0] = root;
b11         if (root) root->p = r;
b13         root = r, root->update();
cbb     }
b7a     T query(int l, int r) {
95f         splay<T> M(split(r+1));
5ff         splay<T> L(M.split(l));
d1c         T ans = M.root->sub;
49c         M.join(L), join(M);
ba7         return ans;
cbb     }
41f     void update(int l, int r, T s) {
95f         splay<T> M(split(r+1));
5ff         splay<T> L(M.split(l));
996         M.root->lazy += s;
49c         M.join(L), join(M);
cbb     }
8c1     void reverse(int l, int r) {
95f         splay<T> M(split(r+1));
5ff         splay<T> L(M.split(l));
945         M.root->rev ^= 1;
49c         M.join(L), join(M);
cbb     }
2fb     void erase(int l, int r) {
95f         splay<T> M(split(r+1));
5ff         splay<T> L(M.split(l));
dcc         join(L);
cbb     }
214 };

```

## 5.28 Split-Merge Set

```

// Representa um conjunto de inteiros nao negativos
// Todas as operacoes custam O(log(N)),
// em que N = maior elemento do set,
// exceto o merge, que custa O(log(N)) amortizado
// Usa O(min(N, n log(N))) de memoria, sendo 'n' o

```

```

// numero de elementos distintos no set
// 2d2d8a

2dc template<typename T, bool MULTI=false, typename SIZE_T=int>
    struct sms {
3c9         struct node {
b19             node *l, *r;
15f             SIZE_T cnt;
658             node() : l(NULL), r(NULL), cnt(0) {}
01e             void update() {
a01                 cnt = 0;
d8a                 if (l) cnt += l->cnt;
e49                 if (r) cnt += r->cnt;
cbb             }
214         };

bb7         node* root;
fd0         T N;

f34         sms() : root(NULL), N(0) {}
83b         sms(T v) : sms() { while (v >= N) N = 2*N+1; }
5e1         sms(const sms& t) : root(NULL), N(t.N) {
3af             for (SIZE_T i = 0; i < t.size(); i++) {
a0f                 T at = t[i];
e6d                 SIZE_T qt = t.count(at);
a43                 insert(at, qt);
f42                 i += qt-1;
cbb             }
cbb         }
a96         sms(initializer_list<T> v) : sms() { for (T i : v)
insert(i); }
2dd         ~sms() {
609             vector<node*> q = {root};
402             while (q.size()) {
e5d                 node* x = q.back(); q.pop_back();
ee9                 if (!x) continue;
1c7                 q.push_back(x->l), q.push_back(x->r);
bf0                 delete x;
cbb             }
cbb         }

fdc         friend void swap(sms& a, sms& b) {
49e             swap(a.root, b.root), swap(a.N, b.N);
cbb         }
83e         sms& operator =(const sms& v) {
768             sms tmp = v;

```

```

420         swap(tmp, *this);
357         return *this;
cbb     }
d06     SIZE_T size() const { return root ? root->cnt : 0; }
17f     SIZE_T count(node* x) const { return x ? x->cnt : 0; }
75a     void clear() {
0a0         sms tmp;
4ac         swap(*this, tmp);
cbb     }
a06     void expand(T v) {
bc3         for (; N < v; N = 2*N+1) if (root) {
63c             node* nroot = new node();
956             nroot->l = root;
897             root = nroot;
a0a             root->update();
cbb         }
cbb     }

b14     node* insert(node* at, T idx, SIZE_T qt, T l, T r) {
1a4         if (!at) at = new node();
893         if (l == r) {
435             at->cnt += qt;
beb             if (!MULTI) at->cnt = 1;
ce6             return at;
cbb         }
841         T m = l + (r-1)/2;
a02         if (idx <= m) at->l = insert(at->l, idx, qt, l, m);
8d9         else at->r = insert(at->r, idx, qt, m+1, r);
cff         return at->update(), at;
cbb     }
cf7     void insert(T v, SIZE_T qt=1) { // insere 'qt' ocorrencias
de 'v'
882         if (qt <= 0) return erase(v, -qt);
72b         assert(v >= 0);
f52         expand(v);
5e9         root = insert(root, v, qt, 0, N);
cbb     }

f06     node* erase(node* at, T idx, SIZE_T qt, T l, T r) {
28c         if (!at) return at;
54b         if (l == r) at->cnt = at->cnt < qt ? 0 : at->cnt - qt;
4e6         else {
841             T m = l + (r-1)/2;
281             if (idx <= m) at->l = erase(at->l, idx, qt, l, m);
ba1             else at->r = erase(at->r, idx, qt, m+1, r);
7b4             at->update();

```

```

cbb         }
135         if (!at->cnt) delete at, at = NULL;
ce6         return at;
cbb     }
43d     void erase(T v, SIZE_T qt=1) { // remove 'qt' ocorrencias
de 'v'
9c3         if (v < 0 or v > N or !qt) return;
9dc         if (qt < 0) insert(v, -qt);
b1d         root = erase(root, v, qt, 0, N);
cbb     }
8d6     void erase_all(T v) { // remove todos os 'v'
347         if (v < 0 or v > N) return;
9f2         root = erase(root, v, numeric_limits<SIZE_T>::max(), 0,
N);
cbb     }

0fe     SIZE_T count(node* at, T a, T b, T l, T r) const {
61b         if (!at or b < l or r < a) return 0;
0fe         if (a <= l and r <= b) return at->cnt;
841         T m = l + (r-1)/2;
84a         return count(at->l, a, b, l, m) + count(at->r, a, b,
m+1, r);
cbb     }
0a9     SIZE_T count(T v) const { return count(root, v, v, 0, N); }
ffc     SIZE_T order_of_key(T v) { return count(root, 0, v-1, 0,
N); }
df2     SIZE_T lower_bound(T v) { return order_of_key(v); }

e68     const T operator [] (SIZE_T i) const { // i-esimo menor
elemento
809         assert(i >= 0 and i < size());
c43         node* at = root;
4a5         T l = 0, r = N;
40c         while (l < r) {
841             T m = l + (r-1)/2;
5c2             if (count(at->l) > i) at = at->l, r = m;
4e6             else {
b4a                 i -= count(at->l);
ded                 at = at->r; l = m+1;
cbb             }
cbb         }
792         return l;
cbb     }

78c     node* merge(node* l, node* r) {
347         if (!l or !r) return l ? l : r;

```

```

504     if (!l->l and !l->r) { // folha
599         if (MULTI) l->cnt += r->cnt;
55d         delete r;
792         return l;
cbb     }
f58     l->l = merge(l->l, r->l), l->r = merge(l->r, r->r);
f4f     l->update(), delete r;
792     return l;
cbb }
f59 void merge(sms& s) { // mergeia dois sets
068     if (N > s.N) swap(*this, s);
785     expand(s.N);
938     root = merge(root, s.root);
ee2     s.root = NULL;
cbb }

dc6 node* split(node*& x, SIZE_T k) {
7ca     if (k <= 0 or !x) return NULL;
6d0     node* ret = new node();
386     if (!x->l and !x->r) x->cnt -= k, ret->cnt += k;
4e6     else {
85e         if (k <= count(x->l)) ret->l = split(x->l, k);
4e6         else {
06f             ret->r = split(x->r, k - count(x->l));
cfd             swap(x->l, ret->l);
cbb         }
674         ret->update(), x->update();
cbb     }
d5b     if (!x->cnt) delete x, x = NULL;
edf     return ret;
cbb }
02b void split(SIZE_T k, sms& s) { // pega os 'k' menores
e63     s.clear();
6e5     s.root = split(root, min(k, size()));
e3c     s.N = N;
cbb }
// pega os menores que 'k'
131 void split_val(T k, sms& s) { split(order_of_key(k), s); }
214 };

```

## 5.29 SQRT Tree

// RMQ em  $O(\log \log n)$  com  $O(n \log \log n)$  pra construir  
// Funciona com qualquer operacao associativa

```

// Tao rapido quanto a sparse table, mas usa menos memoria
// (log log (1e9)) < 5, entao a query eh praticamente  $O(1)$ )
//
// build -  $O(n \log \log n)$ 
// query -  $O(\log \log n)$ 
// 8ff986

97a namespace sqrtTree {
052     int n, *v;
ec7     int pref[4][MAX], sulf[4][MAX], getl[4][MAX],
        entre[4][MAX], sz[4];

5f7     int op(int a, int b) { return min(a, b); }
c72     inline int getblk(int p, int i) { return
(i-getl[p][i])/sz[p]; }
2c6     void build(int p, int l, int r) {
bc8         if (l+1 >= r) return;
368         for (int i = l; i <= r; i++) getl[p][i] = l;
f16         for (int L = l; L <= r; L += sz[p]) {
191             int R = min(L+sz[p]-1, r);
89c             pref[p][L] = v[L], sulf[p][R] = v[R];
59f             for (int i = L+1; i <= R; i++) pref[p][i] =
op(pref[p][i-1], v[i]);
d9a             for (int i = R-1; i >= L; i--) sulf[p][i] =
op(v[i], sulf[p][i+1]);
221             build(p+1, L, R);
cbb         }
695         for (int i = 0; i <= sz[p]; i++) {
ca5             int at = entre[p][l+i*sz[p]+i] = sulf[p][l+i*sz[p]];
759             for (int j = i+1; j <= sz[p]; j++)
entre[p][l+i*sz[p]+j] = at =
23a                 op(at, sulf[p][l+j*sz[p]]);
cbb         }
cbb     }
0d8     void build(int n2, int* v2) {
680         n = n2, v = v2;
44c         for (int p = 0; p < 4; p++) sz[p] = n2 = sqrt(n2);
c50         build(0, 0, n-1);
cbb     }
9e3     int query(int l, int r) {
792         if (l+1 >= r) return l == r ? v[l] : op(v[l], v[r]);
1ba         int p = 0;
4ba         while (getblk(p, l) == getblk(p, r)) p++;
9e4         int ans = sulf[p][l], a = getblk(p, l)+1, b = getblk(p,
r)-1;
8bf         if (a <= b) ans = op(ans,

```

```

    entre[p][getl[p][l]+a*sz[p]+b));
dea    return op(ans, pref[p][r]);
cbb    }
cbb }

```

### 5.30 Treap

```

// Todas as operacoes custam
// O(log(n)) com alta probabilidade, exceto meld
// meld custa O(log^2 n) amortizado com alta prob.,
// e permite unir duas treaps sem restricao adicional
// Na pratica, esse meld tem constante muito boa e
// o pior caso eh meio estranho de acontecer
// bd93e2

878 mt19937 rng((int)
    chrono::steady_clock::now().time_since_epoch().count());

aal template<typename T> struct treap {
3c9     struct node {
b19         node *l, *r;
284         int p, sz;
36d         T val, mi;
4c7         node(T v) : l(NULL), r(NULL), p(rng()), sz(1), val(v),
mi(v) {}
01e         void update() {
a26             sz = 1;
d6e             mi = val;
bd7             if (l) sz += l->sz, mi = min(mi, l->mi);
a54             if (r) sz += r->sz, mi = min(mi, r->mi);
cbb         }
214     };

bb7     node* root;

84b     treap() { root = NULL; }
2d8     treap(const treap& t) {
465         throw logic_error("Nao copiar a treap!");
cbb     }
cec     ~treap() {
609         vector<node*> q = {root};
402         while (q.size()) {
e5d             node* x = q.back(); q.pop_back();
ee9             if (!x) continue;

```

```

1c7         q.push_back(x->l), q.push_back(x->r);
bf0         delete x;
cbb     }
cbb }

73c     int size(node* x) { return x ? x->sz : 0; }
b2b     int size() { return size(root); }
bcf     void join(node* l, node* r, node*& i) { // assume que l < r
986         if (!l or !r) return void(i = l ? l : r);
80e         if (l->p > r->p) join(l->r, r, l->r), i = l;
fa0         else join(l, r->l, r->l), i = r;
bda         i->update();
cbb     }
ece     void split(node* i, node*& l, node*& r, T v) {
26a         if (!i) return void(r = l = NULL);
f05         if (i->val < v) split(i->r, i->r, r, v), l = i;
807         else split(i->l, l, i->l, v), r = i;
bda         i->update();
cbb     }
3fc     void split_leq(node* i, node*& l, node*& r, T v) {
26a         if (!i) return void(r = l = NULL);
181         if (i->val <= v) split_leq(i->r, i->r, r, v), l = i;
58f         else split_leq(i->l, l, i->l, v), r = i;
bda         i->update();
cbb     }
e13     int count(node* i, T v) {
6b4         if (!i) return 0;
352         if (i->val == v) return 1;
8d0         if (v < i->val) return count(i->l, v);
4d0         return count(i->r, v);
cbb     }
26d     void index_split(node* i, node*& l, node*& r, int v, int
key = 0) {
26a         if (!i) return void(r = l = NULL);
c10         if (key + size(i->l) < v) index_split(i->r, i->r, r, v,
key+size(i->l)+1), l = i;
e5a         else index_split(i->l, l, i->l, v, key), r = i;
bda         i->update();
cbb     }
a1f     int count(T v) {
e06         return count(root, v);
cbb     }
c27     void insert(T v) {
980         if (count(v)) return;
031         node *L, *R;
d42         split(root, L, R, v);

```

```

585     node* at = new node(v);
59f     join(L, at, L);
a28     join(L, R, root);
cbb }
26b void erase(T v) {
df9     node *L, *M, *R;
b6b     split_leq(root, M, R, v), split(M, L, M, v);
f17     if (M) delete M;
f38     M = NULL;
a28     join(L, R, root);
cbb }
e77 void meld(treap& t) { // segmented merge
4a6     node *L = root, *R = t.root;
950     root = NULL;
6b1     while (L or R) {
fe2         if (!L or (L and R and L->mi > R->mi)) std::swap(L,
R);
5e1         if (!R) join(root, L, root), L = NULL;
3c9         else if (L->mi == R->mi) {
a76             node* LL;
439             split(L, LL, L, R->mi+1);
359             delete LL;
9d9         } else {
a76             node* LL;
537             split(L, LL, L, R->mi);
dbb             join(root, LL, root);
cbb         }
cbb     }
689     t.root = NULL;
cbb }
214 };

```

### 5.31 Treap Implicita

```

// Todas as operacoes custam
// O(log(n)) com alta probabilidade
// 63ba4d

```

```

878 mt19937 rng((int)
chrono::steady_clock::now().time_since_epoch().count());

```

```

aa1 template<typename T> struct treap {
3c9     struct node {
b19         node *l, *r;

```

```

284     int p, sz;
875     T val, sub, lazy;
aa6     bool rev;
8dc     node(T v) : l(NULL), r(NULL), p(rng()), sz(1), val(v),
sub(v), lazy(0), rev(0) {}
a9c     void prop() {
0ec         if (lazy) {
924             val += lazy, sub += lazy*sz;
b87             if (l) l->lazy += lazy;
d3b             if (r) r->lazy += lazy;
cbb         }
1bb         if (rev) {
e4f             swap(l, r);
dc8             if (l) l->rev ^= 1;
f2f             if (r) r->rev ^= 1;
cbb         }
a32         lazy = 0, rev = 0;
cbb     }
01e     void update() {
0c3         sz = 1, sub = val;
a09         if (l) l->prop(), sz += l->sz, sub += l->sub;
095         if (r) r->prop(), sz += r->sz, sub += r->sub;
cbb     }
214 };

bb7     node* root;

84b     treap() { root = NULL; }
2d8     treap(const treap& t) {
465         throw logic_error("Nao copiar a treap!");
cbb     }
cec     ~treap() {
609         vector<node*> q = {root};
402         while (q.size()) {
e5d             node* x = q.back(); q.pop_back();
ee9             if (!x) continue;
1c7             q.push_back(x->l), q.push_back(x->r);
bf0             delete x;
cbb         }
cbb     }

73c     int size(node* x) { return x ? x->sz : 0; }
b2b     int size() { return size(root); }
bcf     void join(node* l, node* r, node*& i) { // assume que l < r
986         if (!l or !r) return void(i = l ? l : r);
161         l->prop(), r->prop();

```

```

80e         if (l->p > r->p) join(l->r, r, l->r), i = l;
fa0         else join(l, r->l, r->l), i = r;
bda         i->update();
cbb     }
a20     void split(node* l, node*& l, node*& r, int v, int key = 0)
{
26a         if (!i) return void(r = l = NULL);
c89         i->prop();
5bd         if (key + size(i->l) < v) split(i->r, i->r, r, v,
key+size(i->l)+1), l = i;
219         else split(i->l, l, i->l, v, key), r = i;
bda         i->update();
cbb     }
231     void push_back(T v) {
2e0         node* i = new node(v);
7ab         join(root, i, root);
cbb     }
b7a     T query(int l, int r) {
df9         node *L, *M, *R;
dca         split(root, M, R, r+1), split(M, L, M, l);
d43         T ans = M->sub;
69d         join(L, M, M), join(M, R, root);
ba7         return ans;
cbb     }
41f     void update(int l, int r, T s) {
df9         node *L, *M, *R;
dca         split(root, M, R, r+1), split(M, L, M, l);
8f6         M->lazy += s;
69d         join(L, M, M), join(M, R, root);
cbb     }
8c1     void reverse(int l, int r) {
df9         node *L, *M, *R;
dca         split(root, M, R, r+1), split(M, L, M, l);
66a         M->rev ^= 1;
69d         join(L, M, M), join(M, R, root);
cbb     }
214 };

```

## 5.32 Treap Persistent Implicita

```

// Todas as operacoes custam
// O(log(n)) com alta probabilidade
// fb8013

```

```

6cf mt19937_64 rng((int)
chrono::steady_clock::now().time_since_epoch().count());

3c9 struct node {
b19     node *l, *r;
f14     ll sz, val, sub;
304     node(ll v) : l(NULL), r(NULL), sz(1), val(v), sub(v) {}
c12     node(node* x) : l(x->l), r(x->r), sz(x->sz), val(x->val),
sub(x->sub) {}
01e     void update() {
0c3         sz = 1, sub = val;
77e         if (l) sz += l->sz, sub += l->sub;
d6e         if (r) sz += r->sz, sub += r->sub;
124         sub %= MOD;
cbb     }
214 };

bc9 ll size(node* x) { return x ? x->sz : 0; }
761 void update(node* x) { if (x) x->update(); }
828 node* copy(node* x) { return x ? new node(x) : NULL; }

b02 node* join(node* l, node* r) {
e1f     if (!l or !r) return l ? copy(l) : copy(r);
48b     node* ret;
49f     if (rng() % (size(l) + size(r)) < size(l)) {
7eb         ret = copy(l);
cc1         ret->r = join(ret->r, r);
9d9     } else {
4c5         ret = copy(r);
551         ret->l = join(l, ret->l);
cbb     }
74f     return update(ret), ret;
cbb }

723 void split(node* x, node*& l, node*& r, ll v, ll key = 0) {
421     if (!x) return void(l = r = NULL);
b4b     if (key + size(x->l) < v) {
72f         l = copy(x);
d70         split(l->r, l->r, r, v, key+size(l->l)+1);
9d9     } else {
303         r = copy(x);
417         split(r->l, l, r->l, v, key);
cbb     }
da2     update(l), update(r);
cbb }

```

```

f9e vector<node*> treap;

139 void init(const vector<ll>& v) {
bbd     treap = {NULL};
969     for (auto i : v) treap[0] = join(treap[0], new node(i));
cbb }

```

### 5.33 Wavelet Tree

```

// Usa O(sigma + n log(sigma)) de memoria,
// onde sigma = MAXN - MINN
// Depois do build, o v fica ordenado
// count(i, j, x, y) retorna o numero de elementos de
// v[i, j] que pertencem a [x, y]
// kth(i, j, k) retorna o elemento que estaria
// na posicao k-1 de v[i, j], se ele fosse ordenado
// sum(i, j, x, y) retorna a soma dos elementos de
// v[i, j] que pertencem a [x, y]
// sumk(i, j, k) retorna a soma dos k-esimos menores
// elementos de v[i, j] (sum(i, j, 1) retorna o menor)
//
// Complexidades:
// build - O(n log(sigma))
// count - O(log(sigma))
// kth - O(log(sigma))
// sum - O(log(sigma))
// sumk - O(log(sigma))
// 782344

597 int n, v[MAX];
578 vector<int> esq[4*(MAXN-MINN)], pref[4*(MAXN-MINN)];

f8d void build(int b = 0, int e = n, int p = 1, int l = MINN, int r = MAXN) {
58f     int m = (l+r)/2; esq[p].push_back(0); pref[p].push_back(0);
f2f     for (int i = b; i < e; i++) {
6b9         esq[p].push_back(esq[p].back()+(v[i]<=m));
26f         pref[p].push_back(pref[p].back()+v[i]);
cbb     }
8ce     if (l == r) return;
3a7     int m2 = stable_partition(v+b, v+e, [=](int i){return i <=
m;}) - v;
347     build(b, m2, 2*p, l, m), build(m2, e, 2*p+1, m+1, r);
cbb }

```

```

540 int count(int i, int j, int x, int y, int p = 1, int l = MINN,
int r = MAXN) {
2ad     if (y < l or r < x) return 0;
4db     if (x <= l and r <= y) return j-i;
ddc     int m = (l+r)/2, ei = esq[p][i], ej = esq[p][j];
0a5     return count(ei, ej, x, y, 2*p, l, m)+count(i-ei, j-ej, x,
y, 2*p+1, m+1, r);
cbb }

f62 int kth(int i, int j, int k, int p=1, int l = MINN, int r = MAXN) {
3ce     if (l == r) return l;
ddc     int m = (l+r)/2, ei = esq[p][i], ej = esq[p][j];
585     if (k <= ej-ei) return kth(ei, ej, k, 2*p, l, m);
28b     return kth(i-ei, j-ej, k-(ej-ei), 2*p+1, m+1, r);
cbb }

f2c int sum(int i, int j, int x, int y, int p = 1, int l = MINN,
int r = MAXN) {
2ad     if (y < l or r < x) return 0;
2a9     if (x <= l and r <= y) return pref[p][j]-pref[p][i];
ddc     int m = (l+r)/2, ei = esq[p][i], ej = esq[p][j];
43b     return sum(ei, ej, x, y, 2*p, l, m) + sum(i-ei, j-ej, x, y,
2*p+1, m+1, r);
cbb }

b84 int sumk(int i, int j, int k, int p = 1, int l = MINN, int r = MAXN) {
8a1     if (l == r) return l*k;
ddc     int m = (l+r)/2, ei = esq[p][i], ej = esq[p][j];
50c     if (k <= ej-ei) return sumk(ei, ej, k, 2*p, l, m);
4c9     return pref[2*p][ej]-pref[2*p][ei]+sumk(i-ei, j-ej,
k-(ej-ei), 2*p+1, m+1, r);
cbb }

```

## 6 Matematica

### 6.1 2-SAT

```

// solve() retorna um par, o first fala se eh possivel
// atribuir, o second fala se cada variavel eh verdadeira
//

```

```

// 0(|V|+|E|) = 0(#variaveis + #restricoes)
// ef6b3b

138 struct sat {
e6c     int n, tot;
789     vector<vector<int>> g;
0ca     vector<int> vis, comp, id, ans;
4ce     stack<int> s;

141     sat() {}
172     sat(int n_) : n(n_), tot(n), g(2*n) {}

f32     int dfs(int i, int& t) {
cf0         int lo = id[i] = t++;
efc         s.push(i), vis[i] = 2;
48e         for (int j : g[i]) {
740             if (!vis[j]) lo = min(lo, dfs(j, t));
994             else if (vis[j] == 2) lo = min(lo, id[j]);
cbb         }
3de         if (lo == id[i]) while (1) {
3c3             int u = s.top(); s.pop();
9c5             vis[u] = 1, comp[u] = i;
91d             if ((u>>1) < n and ans[u>>1] == -1) ans[u>>1] = ~
u&1;
2ef                 if (u == i) break;
cbb             }
253         return lo;
cbb     }

74a     void add_impl(int x, int y) { // x -> y = !x ou y
26a         x = x >= 0 ? 2*x : -2*x-1;
2b8         y = y >= 0 ? 2*y : -2*y-1;
a1e         g[x].push_back(y);
1e2         g[y^1].push_back(x^1);
cbb     }
e85     void add_cl(int x, int y) { // x ou y
0b5         add_impl(~x, y);
cbb     }
487     void add_xor(int x, int y) { // x xor y
0b7         add_cl(x, y), add_cl(~x, ~y);
cbb     }
978     void add_eq(int x, int y) { // x = y
c86         add_xor(~x, y);
cbb     }
b10     void add_true(int x) { // x = T
18b         add_impl(~x, x);

```

```

cbb     }
d14     void at_most_one(vector<int> v) { // no max um verdadeiro
54d         g.resize(2*(tot+v.size()));
f14         for (int i = 0; i < v.size(); i++) {
8c9             add_impl(tot+i, ~v[i]);
a8f             if (i) {
b6a                 add_impl(tot+i, tot+i-1);
3d3                 add_impl(v[i], tot+i-1);
cbb             }
cbb         }
258         tot += v.size();
cbb     }

a8e     pair<bool, vector<int>> solve() {
27b         ans = vector<int>(n, -1);
6bb         int t = 0;
0de         vis = comp = id = vector<int>(2*tot, 0);
53c         for (int i = 0; i < 2*tot; i++) if (!vis[i]) dfs(i, t);
f88         for (int i = 0; i < tot; i++)
4c9             if (comp[2*i] == comp[2*i+1]) return {false, {}};
997         return {true, ans};
cbb     }
214 };

```

## 6.2 Algoritmo de Euclides estendido

```

// Acha x e y tal que ax + by = mdc(a, b) (nao eh unico)
// Assume a, b >= 0
//
// 0(log(min(a, b)))
// 35411d

```

```

2be tuple<ll, ll, ll> ext_gcd(ll a, ll b) {
3bd     if (!a) return {b, 0, 1};
550     auto [g, x, y] = ext_gcd(b%a, a);
c59     return {g, y - b/a*x, x};
cbb }

```

## 6.3 Avaliacao de Interpolacao

```

// Dado 'n' pontos (i, y[i]), i \in [0, n),
// avalia o polinomio de grau n-1 que passa

```



```

// por esses pontos em 'x'
// Tudo modular, precisa do mint
//
// 0(n)
// 4fe929

ee8 mint evaluate_interpolation(int x, vector<mint> y) {
80e     int n = y.size();

184     vector<mint> sulf(n+1, 1), fat(n, 1), ifat(n);
6fa     for (int i = n-1; i >= 0; i--) sulf[i] = sulf[i+1] * (x -
        i);
29b     for (int i = 1; i < n; i++) fat[i] = fat[i-1] * i;
0da     ifat[n-1] = 1/fat[n-1];
3db     for (int i = n-2; i >= 0; i--) ifat[i] = ifat[i+1] * (i +
        1);

ca1     mint pref = 1, ans = 0;
5ea     for (int i = 0; i < n; pref *= (x - i++)) {
42f         mint num = pref * sulf[i+1];

b4e         mint den = ifat[i] * ifat[n-1 - i];
0bd         if ((n-1 - i)%2) den *= -1;

03f         ans += y[i] * num * den;
cbb     }
ba7     return ans;
cbb }

```

## 6.4 Berlekamp-Massey

```

// guess_kth(s, k) chuta o k-esimo (0-based) termo
// de uma recorrência linear que gera s
// Para uma rec. lin. de ordem x, se passar 2x termos
// vai gerar a certa
// Usar aritmetica modular
//
// 0(n^2 log k), em que n = |s|
// 8644e3

b7c template<typename T> T evaluate(vector<T> c, vector<T> s, ll k)
{
ff2     int n = c.size();
9ee     assert(c.size() <= s.size());

```

```

d09     auto mul = [&](const vector<T> &a, const vector<T> &b) {
564         vector<T> ret(a.size() + b.size() - 1);
d75         for (int i = 0; i < a.size(); i++) for (int j = 0; j <
            b.size(); j++)
cff             ret[i+j] += a[i] * b[j];
83d         for (int i = ret.size()-1; i >= n; i--) for (int j =
            n-1; j >= 0; j--)
112             ret[i-j-1] += ret[i] * c[j];
16d         ret.resize(min<int>(ret.size(), n));
edf         return ret;
214     };

1a6     vector<T> a = n == 1 ? vector<T>({c[0]}) : vector<T>({0,
        1}), x = {1};
95f     while (k) {
7f1         if (k&1) x = mul(x, a);
b28         a = mul(a, a), k >>= 1;
cbb     }
dd6     x.resize(n);

ce8     T ret = 0;
e72     for (int i = 0; i < n; i++) ret += x[i] * s[i];
edf     return ret;
cbb }

192 template<typename T> vector<T> berlekamp_massey(vector<T> s) {
ce8     int n = s.size(), l = 0, m = 1;
222     vector<T> b(n), c(n);
46e     T ld = b[0] = c[0] = 1;
620     for (int i = 0; i < n; i++, m++) {
793         T d = s[i];
ab6         for (int j = 1; j <= l; j++) d += c[j] * s[i-j];
5f0         if (d == 0) continue;
8b4         vector<T> temp = c;
369         T coef = d / ld;
ba6         for (int j = m; j < n; j++) c[j] -= coef * b[j-m];
88f         if (2 * l <= i) l = i + 1 - l, b = temp, ld = d, m = 0;
cbb     }
90c     c.resize(l + 1);
844     c.erase(c.begin());
0dc     for (T& x : c) x = -x;
807     return c;
cbb }

2cf template<typename T> T guess_kth(const vector<T>& s, ll k) {

```

```

cc3      auto c = berlekamp_massey(s);
96a      return evaluate(c, s, k);
cbb }

```

## 6.5 Binomial Distribution

```

// binom(n, k, p) retorna a probabilidade de k sucessos
// numa binomial(n, p)
// 00d38f

361 double logfact[MAX];

9e4 void calc() {
7a0     logfact[0] = 0;
152     for (int i = 1; i < MAX; i++) logfact[i] = logfact[i-1] +
        log(i);
cbb }

94c double binom(int n, int k, double p) {
271     return exp(logfact[n] - logfact[k] - logfact[n-k] + k *
        log(p) + (n-k) * log(1 - p));
cbb }

```

## 6.6 Convolucao de GCD / LCM

```

// O(n log(n))

// multiple_transform(a)[i] = \sum_d a[d * i]
// 338be8
bbe template<typename T> void multiple_transform(vector<T>& v, bool
    inv = false) {
64a     vector<int> I(v.size()-1);
847     iota(I.begin(), I.end(), 1);
674     if (inv) reverse(I.begin(), I.end());
dad     for (int i : I) for (int j = 2; i*j < v.size(); j++)
a8a         v[i] += (inv ? -1 : 1) * v[i*j];
cbb }

// gcd_convolution(a, b)[k] = \sum_{gcd(i, j) = k} a_i * b_j
// 984f53
fe2 template<typename T> vector<T> gcd_convolution(vector<T> a,
    vector<T> b) {

```

```

bdf     multiple_transform(a), multiple_transform(b);
799     for (int i = 0; i < a.size(); i++) a[i] *= b[i];
dea     multiple_transform(a, true);
3f5     return a;
cbb }

// divisor_transform(a)[i] = \sum_{d|i} a[i/d]
// aa74e5
be7 template<typename T> void divisor_transform(vector<T>& v, bool
    inv = false) {
64a     vector<int> I(v.size()-1);
847     iota(I.begin(), I.end(), 1);
5ea     if (!inv) reverse(I.begin(), I.end());
dad     for (int i : I) for (int j = 2; i*j < v.size(); j++)
14f         v[i*j] += (inv ? -1 : 1) * v[i];
cbb }

// lcm_convolution(a, b)[k] = \sum_{lcm(i, j) = k} a_i * b_j
// f5acc1
b1b template<typename T> vector<T> lcm_convolution(vector<T> a,
    vector<T> b) {
3af     divisor_transform(a), divisor_transform(b);
799     for (int i = 0; i < a.size(); i++) a[i] *= b[i];
d8f     divisor_transform(a, true);
3f5     return a;
cbb }

```

## 6.7 Coprime Basis

```

// Dado um conjunto de elementos A constroi uma base B
// de fatores coprimos tal que todo elemento A[i]
// pode ser fatorado como A[i] = \prod B[j]^p_ij
//
// Sendo n o numero de inserts, a complexidade esperada fica
// O(n*(n*loglog(MAX) + log(MAX)^2))
//
// No pior caso, podemos trocar n*loglog(MAX) por
// se MAX <= 1e6 fica 8*n
// se MAX <= 1e9 fica 10*n
// se MAX <= 1e18 fica 16*n
// se MAX <= 1e36 fica 26*n
//
// 6714d3

```

```

ebc template <typename T> struct coprime_basis {
a00     vector<T> basis;

60e     coprime_basis() {}
055     coprime_basis(vector<T> v) { for (T i : v) insert(i); }

845     void insert(T z) {
c3c         int n = basis.size();
efe         basis.push_back(z);
43c         for (int i = n; i < basis.size(); i++) {
21c             for (int j = (i != n) ? i+1 : 0; j < basis.size();
j++) {
4ce                 if (i == j) continue;
024                 T &x = basis[i];
c91                 if (x == 1) {
fac                     j = INF;
5e2                     continue;
cbb                 }
544                 T &y = basis[j];
3c9                 T g = gcd(x, y);
e10                 if (g == 1) continue;
15b                 y /= g, x /= g;
8c6                 basis.push_back(g);
cbb             }
cbb         }
fe8         basis.erase(remove(basis.begin(), basis.end(), 1),
basis.end());
cbb     }

4ba     vector<int> factor(T x) {
21d         vector<int> fat(basis.size());
6fd         for (int i = 0; i < basis.size(); i++) {
25c             while (x % basis[i] == 0) x /= basis[i], fat[i]++;
cbb         }
6a7         return fat;
cbb     }
214 };

```

## 6.8 Crivo de Eratosthenes

```

// "0" crivo
//
// Encontra maior divisor primo
// Um numero eh primo sse divi[x] == x

```

```

// fact fatora um numero <= lim
// A fatoracao sai ordenada
//
// crivo - O(n log(log(n)))
// fact - O(log(n))

// hash (crivo e fact): def8f3
f12 int divi[MAX];

fb9 void crivo(int lim) {
f53     for (int i = 1; i <= lim; i++) divi[i] = 1;

d46     for (int i = 2; i <= lim; i++) if (divi[i] == 1)
018         for (int j = i; j <= lim; j += i) divi[j] = i;
cbb }

470 void fact(vector<int>& v, int n) {
ac8     if (n != divi[n]) fact(v, n/divi[n]);
ab4     v.push_back(divi[n]);
cbb }

// Crivo linear
//
// Mesma coisa que o de cima, mas tambem
// calcula a lista de primos
//
// O(n)

// 792458
f12 int divi[MAX];
fd3 vector<int> primes;

fb9 void crivo(int lim) {
d5a     divi[1] = 1;
f70     for (int i = 2; i <= lim; i++) {
3eb         if (divi[i] == 0) divi[i] = i, primes.push_back(i);
3ba         for (int j : primes) {
522             if (j > divi[i] or i*j > lim) break;
00b             divi[i*j] = j;
cbb         }
cbb     }
cbb }

// Crivo de divisores
//
// Encontra numero de divisores

```

```

// ou soma dos divisores
//
// O(n log(n))

// 9bf7b6
f12 int divi[MAX];

fb9 void crivo(int lim) {
f53     for (int i = 1; i <= lim; i++) divi[i] = 1;

424     for (int i = 2; i <= lim; i++)
594         for (int j = i; j <= lim; j += i) {
// para numero de divisores
9e0             divi[j]++;
// para soma dos divisores
278             divi[j] += i;
cbb         }
cbb }

// Crivo de totiente
//
// Encontra o valor da funcao
// totiente de Euler
//
// O(n log(log(n)))

// 266461
5f4 int tot[MAX];

fb9 void crivo(int lim) {
a27     for (int i = 1; i <= lim; i++) {
bc9         tot[i] += i;
feb         for (int j = 2*i; j <= lim; j += i)
837             tot[j] -= tot[i];
cbb     }
cbb }

// Crivo de funcao de mobius
//
// O(n log(log(n)))

// 58d036
4e1 char meb[MAX];

fb9 void crivo(int lim) {
649     for (int i = 2; i <= lim; i++) meb[i] = 2;

```

```

ace     meb[1] = 1;
842     for (int i = 2; i <= lim; i++) if (meb[i] == 2)
8d8         for (int j = i; j <= lim; j += i) if (meb[j]) {
686             if (meb[j] == 2) meb[j] = 1;
ae1             meb[j] *= j/i%i ? -1 : 0;
cbb         }
cbb }

// Crivo linear de funcao multiplicativa
//
// Computa f(i) para todo 1 <= i <= n, sendo f
// uma funcao multiplicativa (se gcd(a,b) = 1,
// entao f(a*b) = f(a)*f(b))
// f_prime tem que computar f de um primo, e
// add_prime tem que computar f(p^(k+1)) dado f(p^k) e p
// Se quiser computar f(p^k) dado p e k, usar os comentarios
//
// O(n)

// 66886a

fd3 vector<int> primes;
623 int f[MAX], pot[MAX];
//int expo[MAX];

5c4 void sieve(int lim) {
// Funcoes para soma dos divisores:
fc9     auto f_prime = [](int p) { return p+1; };
31c     auto add_prime = [](int fpak, int p) { return fpak*p+1; };
//auto f_pak = [](int p, int k) {};

02d     f[1] = 1;
f70     for (int i = 2; i <= lim; i++) {
e6b         if (!pot[i]) {
e74             primes.push_back(i);
f05             f[i] = f_prime(i), pot[i] = i;
//expo[i] = 1;

cbb         }
3b9         for (int p : primes) {
b9f             if (i*p > lim) break;
569             if (i%p == 0) {
b97                 f[i*p] = f[i / pot[i]] * add_prime(f[pot[i]],
p);

// se for descomentar, tirar a linha de cima
tambem
//f[i*p] = f[i / pot[i]] * f_pak(p, expo[i]+1);

```

```

        //expo[i*p] = expo[i]+1;
51f    pot[i*p] = pot[i] * p;
c2b    break;
9d9    } else {
9ef        f[i*p] = f[i] * f[p];
638    pot[i*p] = p;
        //expo[i*p] = 1;

cbb    }
cbb    }
cbb    }
cbb }

```

## 6.9 Deteccao de ciclo - Tortoise and Hare

```

// Linear no tanto que tem que andar pra ciclar,
// O(1) de memoria
// Retorna um par com o tanto que tem que andar
// do f0 ate o inicio do ciclo e o tam do ciclo
// 899f20

```

```

58d pair<ll, ll> find_cycle() {
273     ll tort = f(f0);
b2b     ll hare = f(f(f0));
b1b     ll t = 0;
683     while (tort != hare) {
b4d         tort = f(tort);
4b2         hare = f(f(hare));
c82         t++;
cbb     }
0e8     ll st = 0;
909     tort = f0;
683     while (tort != hare) {
b4d         tort = f(tort);
1a2         hare = f(hare);
397         st++;
cbb     }

73d     ll len = 1;
3cd     hare = f(tort);
683     while (tort != hare) {
1a2         hare = f(hare);
040         len++;
cbb     }
ebd     return {st, len};

```

```
cbb }
```

## 6.10 Division Trick

```

// Gera o conjunto n/i, pra todo i, em O(sqrt(n))
// copieei do github do tfg50
// 5bf9bf

```

```

79c for(int l = 1, r; l <= n; l = r + 1) {
746     r = n / (n / l);
        // n / i has the same value for l <= i <= r

cbb }

```

## 6.11 Eliminacao Gaussiana

```

// Resolve sistema linear
// Retornar um par com o numero de solucoes
// e alguma solucao, caso exista
//
// O(n^2 * m)
// 1d10b5

```

```

67a template<typename T>
728 pair<int, vector<T>> gauss(vector<vector<T>> a, vector<T> b) {
6ca     const double eps = 1e-6;
f92     int n = a.size(), m = a[0].size();
2f0     for (int i = 0; i < n; i++) a[i].push_back(b[i]);

3cb     vector<int> where(m, -1);
237     for (int col = 0, row = 0; col < m and row < n; col++) {
f05         int sel = row;
b95         for (int i=row; i<n; ++i)
e55             if (abs(a[i][col]) > abs(a[sel][col])) sel = i;
2c4         if (abs(a[sel][col]) < eps) continue;
1ae         for (int i = col; i <= m; i++)
dd2             swap(a[sel][i], a[row][i]);
2c3         where[col] = row;

0c0         for (int i = 0; i < n; i++) if (i != row) {
96c             T c = a[i][col] / a[row][col];
d5c             for (int j = col; j <= m; j++)
c8f                 a[i][j] -= a[row][j] * c;

```

```

cbb      }
b70      row++;
cbb      }

b1d      vector<T> ans(m, 0);
e1a      for (int i = 0; i < m; i++) if (where[i] != -1)
12a          ans[i] = a[where[i]][m] / a[where[i]][i];
603      for (int i = 0; i < n; i++) {
501          T sum = 0;
a75          for (int j = 0; j < m; j++)
5a9              sum += ans[j] * a[i][j];
b1f          if (abs(sum - a[i][m]) > eps)
6cd              return pair(0, vector<T>());
cbb      }

12e      for (int i = 0; i < m; i++) if (where[i] == -1)
018          return pair(INF, ans);
280      return pair(1, ans);
cbb }

```

## 6.12 Eliminacao Gaussiana Z2

```

// D eh dimensao do espaco vetorial
// add(v) - adiciona o vetor v na base (retorna se ele jah
//          pertencia ao span da base)
// coord(v) - retorna as coordenadas (c) de v na base atual
//            (basis^T.c = v)
// recover(v) - retorna as coordenadas de v nos vetores na ordem em
//             que foram inseridos
// coord(v).first e recover(v).first - se v pertence ao span
//
// Complexidade:
// add, coord, recover: O(D^2 / 64)
// d0a4b3

2a3 template<int D> struct Gauss_z2 {
3c1     bitset<D> basis[D], keep[D];
b16     int rk, in;
482     vector<int> id;

37f     Gauss_z2 () : rk(0), in(-1), id(D, -1) {};

04e     bool add(bitset<D> v) {
42c         in++;

```

```

fb0         bitset<D> k;
659         for (int i = D - 1; i >= 0; i--) if (v[i]) {
189             if (basis[i][i]) v ^= basis[i], k ^= keep[i];
4e6             else {
ea6                 k[i] = true, id[i] = in, keep[i] = k;
6ce                 basis[i] = v, rk++;
8a6                 return true;
cbb             }
cbb         }
d1f         return false;
cbb     }
0f6     pair<bool, bitset<D>> coord(bitset<D> v) {
944         bitset<D> c;
659         for (int i = D - 1; i >= 0; i--) if (v[i]) {
a39             if (basis[i][i]) v ^= basis[i], c[i] = true;
8af             else return {false, bitset<D>()};
cbb         }
5db         return {true, c};
cbb     }
330     pair<bool, vector<int>> recover(bitset<D> v) {
22e         auto [span, bc] = coord(v);
af8         if (not span) return {false, {}};
f79         bitset<D> aux;
5a0         for (int i = D - 1; i >= 0; i--) if (bc[i]) aux ^=
keep[i];
ea9         vector<int> oc;
ef2         for (int i = D - 1; i >= 0; i--) if (aux[i])
oc.push_back(id[i]);
001         return {true, oc};
cbb     }
214 };

```

## 6.13 Equacao Diofantina Linear

```

// Encontra o numero de solucoes de a*x + b*y = c,
// em que x \in [lx, rx] e y \in [ly, ry]
// Usar o comentario para recuperar as solucoes
// (note que o b ao final eh b/gcd(a, b))
// Cuidado com overflow! Tem que caber o quadrado dos valores
//
// O(log(min(a, b)))
// 2e8259

c5e template<typename T> tuple<ll, T, T> ext_gcd(ll a, ll b) {

```

```

3bd     if (!a) return {b, 0, 1};
c4b     auto [g, x, y] = ext_gcd<T>(b%a, a);
c59     return {g, y - b/a*x, x};
cbb }

// numero de solucoes de a*[lx, rx] + b*[ly, ry] = c
14c template<typename T = ll> // usar __int128 se for ate 1e18
2a4 ll diophantine(ll a, ll b, ll c, ll lx, ll rx, ll ly, ll ry) {
c80     if (lx > rx or ly > ry) return 0;
a98     if (a == 0 and b == 0) return c ? 0 : (rx-lx+1)*(ry-ly+1);
8ce     auto [g, x, y] = ext_gcd<T>(abs(a), abs(b));
9c3     if (c % g != 0) return 0;
249     if (a == 0) return (rx-lx+1)*(ly <= c/b and c/b <= ry);
4ce     if (b == 0) return (ry-ly+1)*(lx <= c/a and c/a <= rx);
fb1     x *= a/abs(a) * c/g, y *= b/abs(b) * c/g, a /= g, b /= g;

b20     auto shift = [&](T qt) { x += qt*b, y -= qt*a; };
efa     auto test = [&](T& k, ll mi, ll ma, ll coef, int t) {
866         shift((mi - k)*t / coef);
79d         if (k < mi) shift(coef > 0 ? t : -t);
74d         if (k > ma) return pair<T, T>(rx+2, rx+1);
41f         T x1 = x;
633         shift((ma - k)*t / coef);
c5b         if (k > ma) shift(coef > 0 ? -t : t);
4a9         return pair<T, T>(x1, x);
214     };

639     auto [l1, r1] = test(x, lx, rx, b, 1);
38e     auto [l2, r2] = test(y, ly, ry, a, -1);
c43     if (l2 > r2) swap(l2, r2);
50a     T l = max(l1, l2), r = min(r1, r2);
339     if (l > r) return 0;
42f     ll k = (r-l) / abs(b) + 1;
839     return k; // solucoes: x = l + [0, k)*|b|
cbb }

```

## 6.14 Exponenciacao rapida

```

// (x^y mod m) em O(log(y))

// 12b2f8
03c ll pow(ll x, ll y, ll m) { // iterativo
c85     ll ret = 1;
1b8     while (y) {

```

```

895         if (y & 1) ret = (ret * x) % m;
23b         y >>= 1;
cc5         x = (x * x) % m;
cbb     }
edf     return ret;
cbb }

// 7d427b
03c ll pow(ll x, ll y, ll m) { // recursivo
13a     if (!y) return 1;
426     ll ans = pow(x*x%m, y/2, m);
88d     return y%2 ? x*ans%m : ans;
cbb }

```

## 6.15 Fast Walsh Hadamard Transform

```

// FWHT<'|'|>(f) eh SOS DP
// FWHT<'&'>(f) eh soma de superset DP
// Se chamar com ^, usar tamanho potencia de 2!!
//
// O(n log(n))
// 50e84f

382 template<char op, class T> vector<T> FWHT(vector<T> f, bool inv
= false) {
b75     int n = f.size();
d78     for (int k = 0; (n-1)>>k; k++) for (int i = 0; i < n; i++)
        if (i>>k&1) {
29e         int j = i^(1<<k);
627         if (op == '^') f[j] += f[i], f[i] = f[j] - 2*f[i];
a38         if (op == '|') f[i] += (inv ? -1 : 1) * f[j];
93c         if (op == '&') f[j] += (inv ? -1 : 1) * f[i];
cbb     }
578     if (op == '^' and inv) for (auto& i : f) i /= n;
abe     return f;
cbb }

```

## 6.16 FFT

```

// Chamar convolution com vector<complex<double>> para FFT
// Precisa do mint para NTT
//

```

```

// O(n log(n))

// Para FFT
// de56b9
488 void get_roots(bool f, int n, vector<complex<double>>& roots) {
f26     const static double PI = acos(-1);
71a     for (int i = 0; i < n/2; i++) {
b1e         double alpha = i*((2*PI)/n);
1a1         if (f) alpha = -alpha;
069         roots[i] = {cos(alpha), sin(alpha)};
cbb     }
cbb }

// Para NTT
// 91cd08
9f7 template<int p>
97b void get_roots(bool f, int n, vector<mod_int<p>>& roots) {
1e6     mod_int<p> r;
de9     int ord;
57a     if (p == 998244353) {
9b6         r = 102292;
81b         ord = (1 << 23);
1cc     } else if (p == 754974721) {
43a         r = 739831874;
f0a         ord = (1 << 24);
b60     } else if (p == 167772161) {
a2a         r = 243;
033         ord = (1 << 25);
6e0     } else assert(false);

547     if (f) r = r^(p - 1 -ord/n);
ee2     else r = r^(ord/n);
be4     roots[0] = 1;
078     for (int i = 1; i < n/2; i++) roots[i] = roots[i-1]*r;
cbb }

// d5c432
8a2 template<typename T> void fft(vector<T> &a, bool f, int N,
vector<int> &rev) {
bc7     for (int i = 0; i < N; i++) if (i < rev[i]) swap(a[i],
a[rev[i]]);
12b     int l, r, m;
cb4     vector<T> roots(N);
192     for (int n = 2; n <= N; n *= 2) {
0f4         get_roots(f, n, roots);

```

```

5dc         for (int pos = 0; pos < N; pos += n) {
432             l = pos+0, r = pos+n/2, m = 0;
a88             while (m < n/2) {
297                 auto t = roots[m]*a[r];
254                 a[r] = a[l] - t;
b8f                 a[l] = a[l] + t;
925                 l++; r++; m++;
cbb             }
cbb         }
cbb     }
235     if (f) {
1c5         auto invN = T(1)/T(N);
557         for (int i = 0; i < N; i++) a[i] = a[i]*invN;
cbb     }
cbb }
bf5 template<typename T> vector<T> convolution(vector<T> &a,
vector<T> &b) {
279     vector<T> l(a.begin(), a.end());
f41     vector<T> r(b.begin(), b.end());
7c6     int ln = l.size(), rn = r.size();
287     int N = ln+rn-1;
f03     int n = 1, log_n = 0;
ac4     while (n <= N) { n <<= 1; log_n++; }
808     vector<int> rev(n);
bae     for (int i = 0; i < n; ++i) {
434         rev[i] = 0;
920         for (int j = 0; j < log_n; ++j)
836             if (i & (1<<j)) rev[i] |= 1 << (log_n-1-j);
cbb     }
143     assert(N <= n);
fa4     l.resize(n);
7e4     r.resize(n);
56e     fft(l, false, n, rev);
fcf     fft(r, false, n, rev);
917     for (int i = 0; i < n; i++) l[i] *= r[i];
88b     fft(l, true, n, rev);
5e1     l.resize(N);
792     return l;
cbb }

// NTT
// 3bf256
6c8 template<int p, typename T> vector<mod_int<p>> ntt(vector<T>&
a, vector<T>& b) {
d52     vector<mod_int<p>> A(a.begin(), a.end()), B(b.begin(),
b.end());

```



```

d29     return convolution(A, B);
cbb }

// Convolucao de inteiro
//
// Precisa do CRT
//
// Tabela de valores:
// [0,1]      - <int, 1>
// [-1e5, 1e5] - <ll, 2>
// [-1e9, 1e9] - <__int128, 3>
//
// 053a7d
b3c template<typename T, int mods>
eec vector<T> int_convolution(vector<int>& a, vector<int>& b) {
fe8     static const int M1 = 998244353, M2 = 754974721, M3 =
167772161;

bf5     auto c1 = ntt<M1>(a, b);
221     auto c2 = (mods >= 2 ? ntt<M2>(a, b) :
vector<mod_int<M2>>());
f9b     auto c3 = (mods >= 3 ? ntt<M3>(a, b) :
vector<mod_int<M3>>());

2da     vector<T> ans;
5c5     for (int i = 0; i < c1.size(); i++) {
c09         crt<T> at(c1[i].v, M1);
316         if (mods >= 2) at = at * crt<T>(c2[i].v, M2);
987         if (mods >= 3) at = at * crt<T>(c3[i].v, M3);
b2b         ans.push_back(at.a);
26d         if (at.a > at.m/2) ans.back() -= at.m;
cbb     }
ba7     return ans;
cbb }

```

## 6.17 Integracao Numerica - Metodo de Simpson 3/8

```

// Integra f no intervalo [a, b], erro cresce proporcional a (b -
a)^5
// 352415

676 const int N = 3*100; // multiplo de 3
287 ld integrate(ld a, ld b, function<ld(ld)> f) {
b4d     ld s = 0, h = (b - a)/N;

```

```

067     for (int i = 1 ; i < N; i++) s += f(a + i*h)*(i%3 ? 3 : 2);
0da     return (f(a) + s + f(b))*3*h/8;
cbb }

```

## 6.18 Inverso Modular

```

// Computa o inverso de a modulo b
// Se b eh primo, basta fazer
// a^(b-2)

// cf94fe
f0a ll inv(ll a, ll b) {
ae1     return a > 1 ? b - inv(b%a, a)*b/a : 1;
cbb }

// computa o inverso modular de 1..MAX-1 modulo um primo
// 7e4e3
a88 ll inv[MAX]:
0f2 inv[1] = 1;
0fa for (int i = 2; i < MAX; i++) inv[i] = MOD -
MOD/i*inv[MOD%i]%MOD;

```

## 6.19 Karatsuba

```

// Os pragmas podem ajudar
// Para n ~ 2e5, roda em < 1 s
//
// 0(n^1.58)
// 8065d6

// #pragma GCC optimize("Ofast")
// #pragma GCC target ("avx,avx2")
77a template<typename T> void kar(T* a, T* b, int n, T* r, T* tmp) {
d4c     if (n <= 64) {
510         for (int i = 0; i < n; i++) for (int j = 0; j < n; j++)
212             r[i+j] += a[i] * b[j];
505         return;
cbb     }
194     int mid = n/2;
2d7     T *atmp = tmp, *btmp = tmp+mid, *E = tmp+n;
4f1     memset(E, 0, sizeof(E[0])*n);
c65     for (int i = 0; i < mid; i++) {

```

```

c72         atmp[i] = a[i] + a[i+mid];
4b9         btmp[i] = b[i] + b[i+mid];
cbb     }
38a     kar(atmp, btmp, mid, E, tmp+2*n);
b1e     kar(a, b, mid, r, tmp+2*n);
229     kar(a+mid, b+mid, mid, r+n, tmp+2*n);
c65     for (int i = 0; i < mid; i++) {
735         T temp = r[i+mid];
de7         r[i+mid] += E[i] - r[i] - r[i+2*mid];
f1e         r[i+2*mid] += E[i+mid] - temp - r[i+3*mid];
cbb     }
cbb }

e38 template<typename T> vector<T> karatsuba(vector<T> a, vector<T>
    b) {
ba3     int n = max(a.size(), b.size());
a84     while (n&(n-1)) n++;
ca9     a.resize(n), b.resize(n);
ae0     vector<T> ret(2*n), tmp(4*n);
644     kar(&a[0], &b[0], n, &ret[0], &tmp[0]);
edf     return ret;
cbb }

```

## 6.20 Logaritmo Discreto

```

// Resolve logaritmo discreto com o algoritmo baby step giant step
// Encontra o menor x tal que a^x = b (mod m)
// Se nao tem, retorna -1
//
// 0(sqrt(m) * log(sqrt(m)))
// 739fa8
d41
da8 int dlog(int b, int a, int m) {
9f8     if (a == 0) return b ? -1 : 1; // caso nao definido
d41
a6e     a %= m, b %= m;
a10     int k = 1, shift = 0;
31e     while (1) {
6e3         int g = gcd(a, m);
d47         if (g == 1) break;
d41
9bc         if (b == k) return shift;
642         if (b % g) return -1;
c36         b /= g, m /= g, shift++;

```

```

9ab         k = (ll) k * a / g % m;
cbb     }
d41
af7     int sq = sqrt(m)+1, giant = 1;
975     for (int i = 0; i < sq; i++) giant = (ll) giant * a % m;
d41
0b5     vector<pair<int, int>> baby;
33f     for (int i = 0, cur = b; i <= sq; i++) {
496         baby.emplace_back(cur, i);
16c         cur = (ll) cur * a % m;
cbb     }
eb4     sort(baby.begin(), baby.end());
d41
9c9     for (int j = 1, cur = k; j <= sq; j++) {
ace         cur = (ll) cur * giant % m;
78b         auto it = lower_bound(baby.begin(), baby.end(),
pair(cur, INF));
d26         if (it != baby.begin() and (--it)->first == cur)
ac3             return sq * j - it->second + shift;
cbb     }
d41
daa     return -1;
cbb }

```

## 6.21 Miller-Rabin

```

// Testa se n eh primo, n <= 3 * 10^18
//
// 0(log(n)), considerando multiplicacao
// e exponenciacao constantes
// 4ebecc
d8b ll mul(ll a, ll b, ll m) {
e7a     ll ret = a*b - ll((long double)1/m*a*b+0.5)*m;
074     return ret < 0 ? ret+m : ret;
cbb }

03c ll pow(ll x, ll y, ll m) {
13a     if (!y) return 1;
dbc     ll ans = pow(mul(x, x, m), y/2, m);
7fa     return y%2 ? mul(x, ans, m) : ans;
cbb }

1a2 bool prime(ll n) {

```

```

1aa     if (n < 2) return 0;
237     if (n <= 3) return 1;
9de     if (n % 2 == 0) return 0;
f6a     ll r = __builtin_ctzll(n - 1), d = n >> r;

        // com esses primos, o teste funciona garantido para n <=
        // 2^64
        // funciona para n <= 3*10^24 com os primos ate 41
771     for (int a : {2, 325, 9375, 28178, 450775, 9780504,
795265022}) {
da0         ll x = pow(a, d, n);
709         if (x == 1 or x == n - 1 or a % n == 0) continue;

4a2         for (int j = 0; j < r - 1; j++) {
10f             x = mul(x, x, n);
df0             if (x == n - 1) break;
cbb         }
e1b         if (x != n - 1) return 0;
cbb     }
6a5     return 1;
cbb }

```

## 6.22 Pollard's Rho Alg

```

// Usa o algoritmo de deteccao de ciclo de Floyd
// com uma otimizacao na qual o gcd eh acumulado
// A fatoracao nao sai necessariamente ordenada
// O algoritmo rho encontra um fator de n,
// e funciona muito bem quando n possui um fator pequeno
//
// Complexidades (considerando mul constante):
// rho - esperado  $O(n^{1/4})$  no pior caso
// fact - esperado menos que  $O(n^{1/4} \log(n))$  no pior caso
// b00653

d8b ll mul(ll a, ll b, ll m) {
e7a     ll ret = a*b - ll((long double)1/m*a*b+0.5)*m;
074     return ret < 0 ? ret+m : ret;
cbb }

03c ll pow(ll x, ll y, ll m) {
13a     if (!y) return 1;
dbc     ll ans = pow(mul(x, x, m), y/2, m);
7fa     return y%2 ? mul(x, ans, m) : ans;

```

```

cbb }

1a2 bool prime(ll n) {
1aa     if (n < 2) return 0;
237     if (n <= 3) return 1;
9de     if (n % 2 == 0) return 0;

f6a     ll r = __builtin_ctzll(n - 1), d = n >> r;
771     for (int a : {2, 325, 9375, 28178, 450775, 9780504,
795265022}) {
da0         ll x = pow(a, d, n);
709         if (x == 1 or x == n - 1 or a % n == 0) continue;

4a2         for (int j = 0; j < r - 1; j++) {
10f             x = mul(x, x, n);
df0             if (x == n - 1) break;
cbb         }
e1b         if (x != n - 1) return 0;
cbb     }
6a5     return 1;
cbb }

9cf ll rho(ll n) {
0f9     if (n == 1 or prime(n)) return n;
f7c     auto f = [n](ll x) {return mul(x, x, n) + 1;};

8a5     ll x = 0, y = 0, t = 30, prd = 2, x0 = 1, q;
533     while (t % 40 != 0 or gcd(prd, n) == 1) {
8a0         if (x==y) x = ++x0, y = f(x);
e13         q = mul(prd, abs(x-y), n);
21f         if (q != 0) prd = q;
450         x = f(x), y = f(f(y)), t++;
cbb     }
002     return gcd(prd, n);
cbb }

5b7 vector<ll> fact(ll n) {
1b9     if (n == 1) return {};
0ec     if (prime(n)) return {n};
0ed     ll d = rho(n);
1de     vector<ll> l = fact(d), r = fact(n / d);
3af     l.insert(l.end(), r.begin(), r.end());
792     return l;
cbb }

```

## 6.23 Produto de dois long long mod m

```
// 0(1)
// 2f3a79

d8b 11 mul(11 a, 11 b, 11 m) { // a*b % m
e7a     11 ret = a*b - 11((long double)1/m*a*b+0.5)*m;
074     return ret < 0 ? ret+m : ret;
cbb }
```

## 6.24 Simplex

```
// Maximiza c^T x s.t. Ax <= b, x >= 0
//
// 0(2^n), porem executa em 0(n^3) no caso medio
// 3a08e5

395 const double eps = 1e-7;

493 namespace Simplex {
69c     vector<vector<double>> T;
14e     int n, m;
43e     vector<int> X, Y;

c51     void pivot(int x, int y) {
8e6         swap(X[y], Y[x-1]);
d03         for (int i = 0; i <= m; i++) if (i != y) T[x][i] /=
T[x][y];
33c         T[x][y] = 1/T[x][y];
38b         for (int i = 0; i <= n; i++) if (i != x and
abs(T[i][y]) > eps) {
774             for (int j = 0; j <= m; j++) if (j != y) T[i][j] -=
T[i][y] * T[x][j];
3d8             T[i][y] = -T[i][y] * T[x][y];
cbb         }
cbb     }

// Retorna o par (valor maximo, vetor solucao)
6f8     pair<double, vector<double>> simplex(
e9d         vector<vector<double>> A, vector<double> b,
vector<double> c) {
5bb         n = b.size(), m = c.size();
002         T = vector(n + 1, vector<double>(m + 1));
2d9         X = vector<int>(m);
```

```
0c2         Y = vector<int>(n);
115         for (int i = 0; i < m; i++) X[i] = i;
51f         for (int i = 0; i < n; i++) Y[i] = i+m;
5b5         for (int i = 0; i < m; i++) T[0][i] = -c[i];
603         for (int i = 0; i < n; i++) {
ba6             for (int j = 0; j < m; j++) T[i+1][j] = A[i][j];
eca             T[i+1][m] = b[i];
cbb         }
667         while (true) {
714             int x = -1, y = -1;
2db             double mn = -eps;
c29             for (int i = 1; i <= n; i++) if (T[i][m] < mn) mn =
T[i][m], x = i;
af2             if (x < 0) break;
882             for (int i = 0; i < m; i++) if (T[x][i] < -eps) { y
= i; break; }

4a6             if (y < 0) return {-1e18, {}}; // sem solucao para
Ax <= b
7fb                 pivot(x, y);
cbb             }
667             while (true) {
714                 int x = -1, y = -1;
2db                 double mn = -eps;
562                 for (int i = 0; i < m; i++) if (T[0][i] < mn) mn =
T[0][i], y = i;
9b0                 if (y < 0) break;
034                 mn = 1e200;
5af                 for (int i = 1; i <= n; i++) if (T[i][y] > eps and
T[i][m] / T[i][y] < mn)
48f                     mn = T[i][m] / T[i][y], x = i;

53b                 if (x < 0) return {1e18, {}}; // c^T x eh ilimitado
7fb                 pivot(x, y);
cbb             }
290             vector<double> r(m);
32f             for(int i = 0; i < n; i++) if (Y[i] < m) r[Y[i]] =
T[i+1][m];
e59             return {T[0][m], r};
cbb         }
cbb }
```

## 6.25 Teorema Chines do Resto

```
// Combina equacoes modulares lineares: x = a (mod m)
// 0 m final eh o lcm dos m's, e a resposta eh unica mod o lcm
// Os m nao precisam ser coprimos
// Se nao tiver solucao, o 'a' vai ser -1
// 7cd7b3
```

```
153 template<typename T> tuple<T, T, T> ext_gcd(T a, T b) {
3bd     if (!a) return {b, 0, 1};
550     auto [g, x, y] = ext_gcd(b%a, a);
c59     return {g, y - b/a*x, x};
cbb }
```

```
bfe template<typename T = ll> struct crt {
627     T a, m;

5f3     crt() : a(0), m(1) {}
7eb     crt(T a_, T m_) : a(a_), m(m_) {}
911     crt operator * (crt C) {
238         auto [g, x, y] = ext_gcd(m, C.m);
dc0         if ((a - C.a) % g) a = -1;
4f9         if (a == -1 or C.a == -1) return crt(-1, 0);
d09         T lcm = m/g*C.m;
eb2         T ans = a + (x*(C.a-a)/g % (C.m/g))*m;
d8d         return crt((ans % lcm + lcm) % lcm, lcm);
cbb     }
214 };
```

## 6.26 Totiente

```
// 0(sqrt(n))
// faeca3

a7e int tot(int n){
0f6     int ret = n;

505     for (int i = 2; i*i <= n; i++) if (n % i == 0) {
b0c         while (n % i == 0) n /= i;
125         ret -= ret / i;
cbb     }
af4     if (n > 1) ret -= ret / n;

edf     return ret;
cbb }
```

## 7 DP

### 7.1 Convex Hull Trick (Rafael)

```
// adds tem que serem feitos em ordem de slope
// queries tem que ser feitas em ordem de x
//
// linear
// 30323e

4b5 struct CHT {
942     int it;
ac1     vector<ll> a, b;
45e     CHT():it(0){}
0bb     ll eval(int i, ll x){
93d         return a[i]*x + b[i];
cbb     }
63a     bool useless(){
a20         int sz = a.size();
35f         int r = sz-1, m = sz-2, l = sz-3;
d71         return (b[l] - b[r])*(a[m] - a[l]) <
413             (b[l] - b[m])*(a[r] - a[l]);
cbb     }
bf4     void add(ll A, ll B){
7f5         a.push_back(A); b.push_back(B);
565         while (!a.empty()){
233             if ((a.size() < 3) || !useless()) break;
ecb             a.erase(a.end() - 2);
568             b.erase(b.end() - 2);
cbb         }
cbb     }
81b     ll get(ll x){
d27         it = min(it, int(a.size()) - 1);
46a         while (it+1 < a.size()){
3c4             if (eval(it+1, x) > eval(it, x)) it++;
f97             else break;
cbb         }
420         return eval(it, x);
cbb     }
214 };
```

### 7.2 Convex Hull Trick Dinamico

```

// para double, use LINF = 1/.0, div(a, b) = a/b
// update(x) atualiza o ponto de intersecao da reta x
// overlap(x) verifica se a reta x sobrepoe a proxima
// add(a, b) adiciona reta da forma ax + b
// query(x) computa maximo de ax + b para entre as retas
//
// O(log(n)) amortizado por insercao
// O(log(n)) por query
// 978376

72c struct Line {
073     mutable ll a, b, p;
8e3     bool operator<(const Line& o) const { return a < o.a; }
abf     bool operator<(ll x) const { return p < x; }
214 };

326 struct dynamic_hull : multiset<Line, less<>> {
33a     ll div(ll a, ll b) {
a20         return a / b - ((a ^ b) < 0 and a % b);
cbb     }

bbb     void update(iterator x) {
b2a         if (next(x) == end()) x->p = LINF;
772         else if (x->a == next(x)->a) x->p = x->b >= next(x)->b
? LINF : -LINF;
424         else x->p = div(next(x)->b - x->b, x->a - next(x)->a);
cbb     }

71c     bool overlap(iterator x) {
f18         update(x);
cfa         if (next(x) == end()) return 0;
a4a         if (x->a == next(x)->a) return x->b >= next(x)->b;
d40         return x->p >= next(x)->p;
cbb     }

176     void add(ll a, ll b) {
1c7         auto x = insert({a, b, 0});
4ab         while (overlap(x)) erase(next(x)), update(x);
dbc         if (x != begin() and !overlap(prev(x))) x = prev(x),
update(x);
0fc         while (x != begin() and overlap(prev(x)))
4d2             x = prev(x), erase(next(x)), update(x);
cbb     }

4ad     ll query(ll x) {
229         assert(!empty());

```

```

7d1         auto l = *lower_bound(x);
aba         return l.a * x + l.b;
cbb     }
214 };

```

## 7.3 Divide and Conquer DP

```

// Particiona o array em k subarrays
// minimizando o somatorio das queries
//
// O(k n log n), assumindo quer query(l, r) eh O(1)
// 4efe6b

```

```

547 ll dp[MAX][2];

```

```

94b void solve(int k, int l, int r, int lk, int rk) {
de6     if (l > r) return;
109     int m = (l+r)/2, p = -1;
d2b     auto& ans = dp[m][k&1] = LINF;
6e2     for (int i = max(m, lk); i <= rk; i++) {
324         int at = dp[i+1][~k&1] + query(m, i);
57d         if (at < ans) ans = at, p = i;
cbb     }
1ee     solve(k, l, m-1, lk, p), solve(k, m+1, r, p, rk);
cbb }

cf1 ll DC(int n, int k) {
321     dp[n][0] = dp[n][1] = 0;
f27     for (int i = 0; i < n; i++) dp[i][0] = LINF;
b76     for (int i = 1; i <= k; i++) solve(i, 0, n-i, 0, n-i);
8e7     return dp[0][k&1];
cbb }

```

## 7.4 Longest Common Subsequence

```

// Computa a LCS entre dois arrays usando
// o algoritmo de Hirschberg para recuperar
//
// O(n*m), O(n+m) de memoria
// 337bb3

```

```

eaf int lcs_s[MAX], lcs_t[MAX];

```

```

a6d int dp[2][MAX];

// dp[0][j] = max lcs(s[li...ri], t[lj, lj+j])
d12 void dp_top(int li, int ri, int lj, int rj) {
d13     memset(dp[0], 0, (rj-lj+1)*sizeof(dp[0][0]));
753     for (int i = li; i <= ri; i++) {
9aa         for (int j = rj; j >= lj; j--)
83b             dp[0][j - lj] = max(dp[0][j - lj],
741             (lcs_s[i] == lcs_t[j]) + (j > lj ? dp[0][j-1 - lj]
: 0));
04c         for (int j = lj+1; j <= rj; j++)
939             dp[0][j - lj] = max(dp[0][j - lj], dp[0][j-1 - lj]);
cbb     }
cbb }

// dp[1][j] = max lcs(s[li...ri], t[lj+j, rj])
ca0 void dp_bottom(int li, int ri, int lj, int rj) {
0dd     memset(dp[1], 0, (rj-lj+1)*sizeof(dp[1][0]));
3a2     for (int i = ri; i >= li; i--) {
49c         for (int j = lj; j <= rj; j++)
dbb             dp[1][j - lj] = max(dp[1][j - lj],
4da             (lcs_s[i] == lcs_t[j]) + (j < rj ? dp[1][j+1 - lj]
: 0));
6ca         for (int j = rj-1; j >= lj; j--)
769             dp[1][j - lj] = max(dp[1][j - lj], dp[1][j+1 - lj]);
cbb     }
cbb }

93c void solve(vector<int>& ans, int li, int ri, int lj, int rj) {
2ad     if (li == ri){
49c         for (int j = lj; j <= rj; j++)
f5b             if (lcs_s[li] == lcs_t[j]){
a66                 ans.push_back(lcs_t[j]);
c2b                 break;
cbb             }
505         return;
cbb     }
534     if (lj == rj){
753         for (int i = li; i <= ri; i++){
88f             if (lcs_s[i] == lcs_t[lj]){
531                 ans.push_back(lcs_s[i]);
c2b                 break;
cbb             }
cbb         }
505         return;
cbb     }
}

```

```

a57     int mi = (li+ri)/2;
ade     dp_top(li, mi, lj, rj), dp_bottom(mi+1, ri, lj, rj);

d7a     int j_ = 0, mx = -1;

aee     for (int j = lj-1; j <= rj; j++) {
da8         int val = 0;
2bb         if (j >= lj) val += dp[0][j - lj];
b9e         if (j < rj) val += dp[1][j+1 - lj];

ba8         if (val >= mx) mx = val, j_ = j;
cbb     }
6f1     if (mx == -1) return;
c2a     solve(ans, li, mi, lj, j_), solve(ans, mi+1, ri, j_+1, rj);
cbb }

058 vector<int> lcs(const vector<int>& s, const vector<int>& t) {
953     for (int i = 0; i < s.size(); i++) lcs_s[i] = s[i];
577     for (int i = 0; i < t.size(); i++) lcs_t[i] = t[i];
dab     vector<int> ans;
599     solve(ans, 0, s.size()-1, 0, t.size()-1);
ba7     return ans;
cbb }

```

## 7.5 Mochila

```

// Resolve mochila, recuperando a resposta
//
// O(n * cap), O(n + cap) de memoria
// 400885

add int v[MAX], w[MAX]; // valor e peso
582 int dp[2][MAX_CAP];

// DP usando os itens [l, r], com capacidade = cap
0d6 void get_dp(int x, int l, int r, int cap) {
f8f     memset(dp[x], 0, (cap+1)*sizeof(dp[x][0]));
574     for (int i = l; i <= r; i++) for (int j = cap; j >= 0; j--)
3a9         if (j - w[i] >= 0) dp[x][j] = max(dp[x][j], v[i] +
dp[x][j - w[i]]);
cbb }

5ab void solve(vector<int>& ans, int l, int r, int cap) {
893     if (l == r) {

```

```

9ff         if (w[l] <= cap) ans.push_back(l);
505         return;
cbb     }
ee4     int m = (l+r)/2;
283     get_dp(0, l, m, cap), get_dp(1, m+1, r, cap);
056     int left_cap = -1, opt = -INF;
c94     for (int j = 0; j <= cap; j++)
2f2         if (int at = dp[0][j] + dp[1][cap - j]; at > opt)
91d             opt = at, left_cap = j;
da3     solve(ans, l, m, left_cap), solve(ans, m+1, r, cap -
left_cap);
cbb }

0d7 vector<int> knapsack(int n, int cap) {
dab     vector<int> ans;
1e0     solve(ans, 0, n-1, cap);
ba7     return ans;
cbb }

```

## 7.6 SOS DP

```

// 0(n 2^n)

// soma de sub-conjunto
// bec381
e03 vector<ll> sos_dp(vector<ll> f) {
6c0     int N = __builtin_ctz(f.size());
e59     assert((1<<N) == f.size());

5a5     for (int i = 0; i < N; i++) for (int mask = 0; mask <
(1<<N); mask++)
796         if (mask>>i&1) f[mask] += f[mask^(1<<i)];
abe     return f;
cbb }

// soma de super-conjunto
// dbd121
e03 vector<ll> sos_dp(vector<ll> f) {
6c0     int N = __builtin_ctz(f.size());
e59     assert((1<<N) == f.size());

5a5     for (int i = 0; i < N; i++) for (int mask = 0; mask <
(1<<N); mask++)
a3c         if (~mask>>i&1) f[mask] += f[mask^(1<<i)];

```

```

abe     return f;
cbb }

```



## 8 Extra

### 8.1 rand.cpp

```
mt19937 rng((int)
    chrono::steady_clock::now().time_since_epoch().count());

int uniform(int l, int r){
    uniform_int_distribution<int> uid(l, r);
    return uid(rng);
}
```

### 8.2 template.cpp

```
#include <bits/stdc++.h>

using namespace std;

#define _ ios_base::sync_with_stdio(0);cin.tie(0);
#define endl '\n'

typedef long long ll;

const int INF = 0x3f3f3f3f;
const ll LINF = 0x3f3f3f3f3f3f3f3fll;

int main() { _
    exit(0);
}
```

### 8.3 hash.sh

```
# Para usar (hash das linhas [l1, l2]):
# bash hash.sh arquivo.cpp l1 l2
sed -n $2', '$3' p' $1 | sed '/^#w/d' | cpp -dD -P -fpreprocessed |
    tr -d '[:space:]' | md5sum | cut -c-6
```

### 8.4 stress.sh

```
P=a
make ${P} ${P}2 gen || exit 1
for ((i = 1; ; i++)) do
    ./gen $i > in
    ./${P} < in > out
    ./${P}2 < in > out2
    if (! cmp -s out out2) then
        echo "--> entrada:"
        cat in
        echo "--> saida1:"
        cat out
        echo "--> saida2:"
        cat out2
        break;
    fi
    echo $i
done
```

### 8.5 fastIO.cpp

```
int read_int() {
    bool minus = false;
    int result = 0;
    char ch;
    ch = getchar();
    while (1) {
        if (ch == '-') break;
        if (ch >= '0' && ch <= '9') break;
        ch = getchar();
    }
    if (ch == '-') minus = true;
    else result = ch - '0';
    while (1) {
        ch = getchar();
        if (ch < '0' || ch > '9') break;
        result = result*10 + (ch - '0');
    }
    if (minus) return -result;
    else return result;
}
```

### 8.6 debug.cpp

```

void debug_out(string s, int line) { cerr << endl; }
template<typename H, typename... T>
void debug_out(string s, int line, H h, T... t) {
    if (s[0] != ',') cerr << "Line(" << line << ") ";
    do { cerr << s[0]; s = s.substr(1);
    } while (s.size() and s[0] != ',');
    cerr << " = " << h;
    debug_out(s, line, t...);
}
#ifdef DEBUG
#define debug(...) debug_out(__VA_ARGS__, __LINE__, __VA_ARGS__)
#else
#define debug(...)
#endif

```

## 8.7 vimrc

```

set ts=4 si ai sw=4 nu mouse=a undofile
syntax on

```

## 8.8 timer.cpp

```

// timer T; T() -> retorna o tempo em ms desde que declarou
using namespace chrono;
struct timer : high_resolution_clock {
    const time_point start;
    timer(): start(now()) {}
    int operator()() {
        return duration_cast<milliseconds>(now() - start).count();
    }
};

```

## 8.9 linehash.sh

```

# Para usar:
# bash linehash.sh arquivo.cpp
while read l; do
    echo $l > tmp.txt
    h=$(echo $(bash hash.sh tmp.txt 1 1) | cut -c-3)
    echo "$h $l"
done < "$1"

```

## 8.10 makefile

```

CXX = g++
CXXFLAGS = -fsanitize=address,undefined -fno-omit-frame-pointer -g
           -Wall -Wshadow -std=c++17 -Wno-unused-result -Wno-sign-compare
           -Wno-char-subscripts #-fuse-ld=gold

```