

M.Sc. Thesis proposal

Classifying brain activity using low-cost biosensors and automated time tracking

Erik Bjäreholt

(dat13ebj@student.lu.se, erik@bjareho.lt)

Student Erik Bjäreholt
 Supervisor Markus Borg
 Examiner Elizabeth Bjarnarson
 Start date 10th June (realistic?)
 End date 30th September (realistic?)

- attention span among media multitasking adults [TODO]
- psychological well-being [4].

Companies like RescueTime, HubStaff, etc. offer automated time tracking as a service. These services let the user track their screen time by installing a program on their device which tracks the active application and sends the data to their servers for storage and analysis. The user can then view their data in a dashboard on the service's website. These services are marketed towards teams and professionals, who want to keep track of individual and team productivity.

However, by collecting detailed and non-anonymized behavioral data on the user these services bring significant privacy concerns, especially in cases where the data is shared with a team or an employer.

CONTENTS

I	Background	1
I-A	Device use	1
I-B	Low-cost functional brain imaging . . .	1
II	Problem description, research goals and questions	1
III	Methodology	2
IV	Scientific contributions	2
V	Resources	2
VI	References	2

B. Low-cost functional brain imaging

Functional brain imaging methods such as fMRI and fNIRS, have been used to study the relationship between cognitive or physical activity, and brain activity [1][3]. The more accurate methods such as fMRI are costly and inflexible/impractical for many uses. However, the recent availability of low-cost biosensors such as EEG, HEG, and fNIRS, enables studying brain activity during real-life tasks.

Functional brain imaging techniques hold the promise of relating cognition to physical activities and brain structures. As an example it has been shown that it is possible to classify what task a participant is undertaking using fMRI[1], which has been replicated using EEG and low-cost sensors[2]. EEG-based BCIs are not without their limitations [5], yet visual evoked potentials (VEPs) have been shown to be sufficient for high-speed BCI applications [6].

I. BACKGROUND

A. Device use

People spend more time than ever using computing devices[TODO]. As services, entertainment, and work, moves online this trend is expected to continue. While several studies have been tracking how people spend their screen time, and how that varies with demographics, is not publicly available [TODO].

Furthermore, how different computer activities affects the user behaviorally and neurologically is of interest for many areas of research, including:

- the impact of screen time for adolescents [TODO]

II. PROBLEM DESCRIPTION, RESEARCH GOALS AND QUESTIONS

We want to investigate whether EEG and other low-cost biosensors can be used to accurately classify device activity in a broader context than previous studies.

III. METHODOLOGY

IV. SCIENTIFIC CONTRIBUTIONS

- The open source automated time-tracker ActivityWatch.
- Relationships between device activity and brain activity, as measured by EEG.

V. RESOURCES

- ActivityWatch, an open source automated time tracker (already developed by the author, but never before used in a scientific publication)
- OpenBCI Cyton biosensing board (8 channel) and Ultra-cortex headset
- HEGduino

VI. REFERENCES

REFERENCES

- [1] Benjamin Floyd, Tyler Santander, and Westley Weimer. “Decoding the Representation of Code in the Brain: An fMRI Study of Code Review and Expertise”. In: *2017 IEEE/ACM 39th International Conference on Software Engineering (ICSE)*. 2017 IEEE/ACM 39th International Conference on Software Engineering (ICSE). ISSN: 1558-1225. May 2017, pp. 175–186. DOI: 10.1109/ICSE.2017.24.
- [2] Davide Fucci et al. “A Replication Study on Code Comprehension and Expertise using Lightweight Biometric Sensors”. In: *2019 IEEE/ACM 27th International Conference on Program Comprehension (ICPC)*. 2019 IEEE/ACM 27th International Conference on Program Comprehension (ICPC). ISSN: 2643-7171. May 2019, pp. 311–322. DOI: 10.1109/ICPC.2019.00050.
- [3] Keum-Shik Hong, Noman Naseer, and Yun-Hee Kim. “Classification of prefrontal and motor cortex signals for three-class fNIRS-BCI”. In: *Neuroscience Letters* 587 (Feb. 5, 2015), pp. 87–92. ISSN: 0304-3940. DOI: 10.1016/j.neulet.2014.12.029. URL: <http://www.sciencedirect.com/science/article/pii/S0304394014009744> (visited on 05/22/2020).
- [4] Chiungjung Huang. “Time Spent on Social Network Sites and Psychological Well-Being: A Meta-Analysis”. In: *Cyberpsychology, Behavior, and Social Networking* 20.6 (June 1, 2017). Publisher: Mary Ann Liebert, Inc., publishers, pp. 346–354. ISSN: 2152-2715. DOI: 10.1089/cyber.2016.0758. URL: <https://www.liebertpub.com/doi/10.1089/cyber.2016.0758> (visited on 05/13/2020).
- [5] D. J. McFarland and J. R. Wolpaw. “EEG-based brain–computer interfaces”. In: *Current Opinion in Biomedical Engineering*. Synthetic Biology and Biomedical Engineering / Neural Engineering 4 (Dec. 1, 2017), pp. 194–200. ISSN: 2468-4511. DOI: 10.1016/j.cobme.2017.11.004. URL: <http://www.sciencedirect.com/science/article/pii/S246845111730082X> (visited on 05/13/2020).
- [6] Martin Spüler. “A high-speed brain-computer interface (BCI) using dry EEG electrodes”. In: *PLoS ONE* 12.2 (Feb. 22, 2017). ISSN: 1932-6203. DOI: 10.1371/journal.pone.0172400. URL: <https://www.ncbi.nlm.nih.gov/pmc/articles/PMC5321409/> (visited on 05/13/2020).