

Description:

The AN-SGCNV is a 14 channel AD-card designed to operate together with the P906 transducers and Pt100/Pt1000 RTC's.

Key functions:

- Hitachi H8 micro controller
- 1 RS485 serial communication line.
- AD7715, 16 bits ad-converter.
- 14 input channels and two channels for calibration.
- 1 mA / 10 mA current generator.
- DS2430 interface from sensors.
- Self calibration.

Page references:

 $\langle 1 \rangle$ = This pin drives the signal and is connected to page i.e. 1.

(1) = This signal is driven from a pin on page i.e. 1.

This pin drives the signal and is connected to the current page.

() = This signal is driven from a pin on current page.

X = Not connected.

Copyright.

All copyrights for the product, the product name Surveyor and the name ARISTON to be owned by ARISTON Norway as. It is not allowed, without written acceptance from ARISTON Norway as, to copy or use the product or parts of the product.

Pages:

- 1: This page
- 2: Power supply and CPU
- 3: AD-converter and current generator
- 4: Channel 1 8
- 5: Channel 9 14 and calibration

RELEASE NOTES:

RELEASE 0: 1-AUG-96 FIRST RELEASE
RELEASE 1: 1-JAN-97 CHANGED LAYOUT IC4, NEW R19-24

PARISTON NORWAY

PORSCRUNN
NORWAY

AN -SGCNV

DRAWN
AST

REV.

1 DATE
1-JAN-97

DWG.NO.
AN4-SPCB0-08







