

## Hive Assignment

### Section 1:

Create a database named **hive\_test** and create three tables

**salesman**

**customer**

**orders**

#### 1. Create a database

```
CREATE DATABASE IF NOT EXISTS hive_test;
```

```
USE hive_test;
```

#### 2. Create the salesman table

```
CREATE TABLE salesman (  
    salesman_id INT,  
    name STRING,  
    city STRING,  
    commission DOUBLE  
)  
ROW FORMAT DELIMITED  
FIELDS TERMINATED BY ','  
STORED AS TEXTFILE;
```

Load Data:

```
LOAD DATA LOCAL INPATH '/path/to/salesman.csv'  
INTO TABLE salesman;
```

#### 3. Create the customer table:

```
CREATE TABLE customer (  
    customer_id INT,  
    cust_name STRING,  
    city STRING,  
    grade INT,  
    salesman_id INT  
)  
ROW FORMAT DELIMITED  
FIELDS TERMINATED BY ','  
STORED AS TEXTFILE;
```

Load Data:

```
LOAD DATA LOCAL INPATH '/path/to/customer.csv'  
INTO TABLE customer;
```

**4. Create orders table:**

```
CREATE TABLE orders (  
  ord_no INT,  
  purch_amt DOUBLE,  
  ord_date DATE,  
  customer_id INT,  
  salesman_id INT  
)  
ROW FORMAT DELIMITED  
FIELDS TERMINATED BY ','  
STORED AS TEXTFILE;
```

Load data:

```
LOAD DATA LOCAL INPATH '/path/to/orders.csv'  
INTO TABLE orders;
```