

Package ‘lulcc’

July 30, 2015

Title Land Use Change Modelling in R

Version 1.0.0

Author Simon Moulds <simon.moulds10@imperial.ac.uk>

Maintainer Simon Moulds <simon.moulds10@imperial.ac.uk>

Description Classes and methods for spatially explicit land use change modelling in R.

Depends methods, raster, R (>= 3.1.0)

License GPL (>= 2)

LazyData true

Imports ROCR, lattice, rasterVis

Suggests caret, rpart, randomForest, gsubfn, Hmisc, plyr,
RColorBrewer,

Collate 'class-CategoryLabel.R' 'class-PredictiveModelList.R'
'class-ObsLulcRasterStack.R' 'class-NeighbRasterStack.R'
'class-ExpVarRasterList.R' 'class-Model.R'
'class-ThreeMapComparison.R' 'AgreementBudget.R'
'ExpVarRasterList.R' 'FigureOfMerit.R' 'Model.R'
'NeighbRasterStack.R' 'ObsLulcRasterStack.R'
'class-PerformanceList.R' 'PerformanceList.R'
'class-PredictionList.R' 'PredictionList.R'
'ThreeMapComparison.R' 'allocate.R' 'allow.R' 'allowNeighb.R'
'approxExtrapDemand.R' 'as.data.frame.R'
'c.PredictiveModelList.R' 'index.R' 'coerce.R' 'compareAUC.R'
'crossTabulate.R' 'data.R' 'getPredictiveModelInputData.R'
'length.R' 'lulcc-package.R' 'models.R' 'names.R' 'partition.R'
'performance.rocr.R' 'plot.AgreementBudget.R'
'plot.FigureOfMerit.R' 'plot.Performance.R' 'plot.R'
'predict.R' 'resample.R' 'show.R' 'subset.R' 'summary.R'
'total.R'

R topics documented:

lulcc-package	3
AgreementBudget	6
AgreementBudget-class	7
allocate	8

allow	9
allowNeighb	11
approxExtrapDemand	12
as.data.frame.ExpVarRasterList	13
c.PredictiveModelList	14
CategoryLabel-class	15
CluesModel	16
CluesModel-class	17
compareAUC	18
crossTabulate	19
ExpVarRasterList	20
ExpVarRasterList-class	21
Extract by index	22
FigureOfMerit	23
FigureOfMerit-class	24
getPredictiveModelInputData	24
Model fitting	25
Model-class	25
NeighbRasterStack	26
NeighbRasterStack-class	27
ObsLulcRasterStack	28
ObsLulcRasterStack-class	29
OrderedModel	30
OrderedModel-class	31
partition	32
performance	33
PerformanceList	34
PerformanceList-class	34
pie	35
plot	35
plot.AgreementBudget	36
plot.FigureOfMerit	38
plot.PerformanceList	39
predict.PredictiveModelList	40
PredictionList	41
PredictionList-class	42
PredictiveModelList-class	42
resample,ExpVarRasterList,Raster-method	43
roundSum	44
show,ExpVarRasterList-method	45
sibuyan	45
subset,ExpVarRasterList-method	46
summary	47
ThreeMapComparison	48
ThreeMapComparison-class	49
total	50

Description

The lulcc package is an open and extensible framework for land use change modelling in R.

Details

The aims of the package are as follows:

1. to improve the reproducibility of scientific results and encourage reuse of code within the land use change modelling community
2. to make it easy to directly compare and combine different model structures
3. to allow users to perform several aspects of the modelling process within the same environment

To achieve these aims the package utilises an object-oriented approach based on the S4 system, which provides a formal structure for the modelling framework. Generic methods implemented for the lulcc classes include summary, show, and plot.

Land use change models are represented by objects inheriting from the superclass `Model`. This class is designed to represent general information required by all models while specific models are represented by its subclasses. Currently the package includes two inductive land use change models: the first is an implementation of the Change in Land Use and its Effects at Small Regional extent (CLUE-S) model (Verburg et al., 2002) (class `CluesModel`), while the second is an ordered procedure based on the algorithm described by Fuchs et al. (2013) but modified to allow stochastic transitions (class `OrderedModel`).

The main input to inductive land use change models is a set of predictive models relating observed land use or land use change to spatially explicit explanatory variables. A predictive model is usually obtained for each category or transition. In lulcc these models are represented by the class `PredictiveModelList`. Currently lulcc supports binary logistic regression, provided by base R (`glm`), recursive partitioning and regression trees, provided by package `rpart` and random forest, provided by package `randomForest`. To a large extent the success of the allocation routine depends on the strength of the predictive models: this is one reason why an R package for land use change modelling is attractive.

To validate model output lulcc includes a method developed by Pontius et al. (2011) that simultaneously compares a reference map for time 1, a reference map for time 2 and a simulated map for time 2 at multiple resolutions. In lulcc the results of the comparison are represented by the class `ThreeMapComparison`. From objects of this class it is straightforward to extract information about different sources of agreement and disagreement, represented by the class `AgreementBudget`, which can then be plotted. The results of the comparison are conveniently summarised by the figure of merit, represented by the class `FigureOfMerit`.

In addition to the core functionality described above, lulcc includes several utility functions to assist with the model building process. Two example datasets are also included.

Author(s)

Simon Moulds

References

- Fuchs, R., Herold, M., Verburg, P.H., and Clevers, J.G.P.W. (2013). A high-resolution and harmonized model approach for reconstructing and analysing historic land changes in Europe, *Biogeosciences*, 10:1543-1559.
- Pontius Jr, R.G., Peethambaram, S., Castella, J.C. (2011). Comparison of three maps at multiple resolutions: a case study of land change simulation in Cho Don District, Vietnam. *Annals of the Association of American Geographers* 101(1): 45-62.
- Verburg, P.H., Soepboer, W., Veldkamp, A., Limpiada, R., Espaldon, V., Mastura, S.S. (2002). Modeling the spatial dynamics of regional land use: the CLUE-S model. *Environmental management*, 30(3):391-405.

Examples

```
## Not run:

## Plum Island Ecosystems

## load data
data(pie)

## observed maps
obs <- ObsLulcRasterStack(x=pie,
                          pattern="lu",
                          categories=c(1,2,3),
                          labels=c("Forest", "Built", "Other"),
                          t=c(0,6,14))

obs

plot(obs)

crossTabulate(obs, times=c(0,14))

## explanatory variables
ef <- ExpVarRasterList(x=pie, pattern="ef")
ef

part <- partition(x=obs[[1]], size=0.1, spatial=TRUE)
train.data <- getPredictiveModelInputData(obs=obs, ef=ef, cells=part[["train"]])

forms <- list(Built ~ ef_001+ef_002+ef_003,
              Forest ~ ef_001+ef_002,
              Other ~ ef_001+ef_002)

glm.models <- glmModels(formula=forms, family=binomial, data=train.data, obs=obs)
rpart.models <- rpartModels(formula=forms, data=train.data, obs=obs)
rf.models <- randomForestModels(formula=forms, data=train.data, obs=obs)

## test ability of models to predict allocation of forest, built and other
## land uses in testing partition
test.data <- getPredictiveModelInputData(obs=obs, ef=ef, cells=part[["test"]])

glm.pred <- PredictionList(models=glm.models, newdata=test.data)
glm.perf <- PerformanceList(pred=glm.pred, measure="rch")

rpart.pred <- PredictionList(models=rpart.models, newdata=test.data)
```

```

rpart.perf <- PerformanceList(pred=rpart.pred, measure="rch")

rf.pred <- PredictionList(models=rf.models, newdata=test.data)
rf.perf <- PerformanceList(pred=rf.pred, measure="rch")

plot(list(glm=glm.perf, rpart=rpart.perf, rf=rf.perf))

## test ability of models to predict location of urban gain 1985 to 1991
part <- rasterToPoints(obs[[1]], fun=function(x) x != 2, spatial=TRUE)
test.data <- getPredictiveModelInputData(obs=obs, ef=ef, cells=part, t=6)

glm.pred <- PredictionList(models=glm.models[[2]], newdata=test.data)
glm.perf <- PerformanceList(pred=glm.pred, measure="rch")

plot(list(glm=glm.perf))

## obtain demand scenario
dmd <- approxExtrapDemand(obs=obs, tout=0:14)
matplot(dmd, type="l", ylab="Demand (no. of cells)", xlab="Time point",
        lty=1, col=c("Green", "Red", "Blue"))
legend("topleft", legend=obs@labels, col=c("Green", "Red", "Blue"), lty=1)

## get neighbourhood values
w <- matrix(data=1, nrow=3, ncol=3)
nb <- NeighbRasterStack(x=obs[[1]], weights=w, categories=2)

## create CLUE-S model object
clues.rules <- matrix(data=1, nrow=3, ncol=3, byrow=TRUE)

clues.parms <- list(jitter.f=0.0002,
                   scale.f=0.000001,
                   max.iter=1000,
                   max.diff=50,
                   ave.diff=50)

clues.model <- CluesModel(obs=obs,
                        ef=ef,
                        models=glm.models,
                        time=0:14,
                        demand=dmd,
                        elas=c(0.2, 0.2, 0.2),
                        rules=clues.rules,
                        params=clues.parms)

## Create Ordered model
ordered.model <- OrderedModel(obs=obs,
                             ef=ef,
                             models=glm.models,
                             time=0:14,
                             demand=dmd,
                             order=c(2, 1, 3))

## perform allocation
clues.model <- allocate(clues.model)
ordered.model <- allocate(ordered.model, stochastic=TRUE)

## pattern validation

```

```

## CLUE-S
clues.tabs <- ThreeMapComparison(x=clues.model,
                                factors=2^(1:8),
                                timestep=14)

plot(clues.tabs)
plot(clues.tabs, category=1, factors=2^(1:8)[c(1,3,5,7)])

## Ordered
ordered.tabs <- ThreeMapComparison(x=ordered.model,
                                   factors=2^(1:8),
                                   timestep=14)

plot(ordered.tabs)
plot(ordered.tabs, category=1, factors=2^(1:8)[c(1,3,5,7)])

## calculate agreement budget and plot

## CLUE-S
clues.agr <- AgreementBudget(x=clues.tabs)
plot(clues.agr, from=1, to=2)

## Ordered
ordered.agr <- AgreementBudget(x=ordered.tabs)
plot(ordered.agr, from=1, to=2)

## calculate Figure of Merit and plot

## CLUE-S
clues.fom <- FigureOfMerit(x=clues.tabs)
p1 <- plot(clues.fom, from=1, to=2)

## Ordered
ordered.fom <- FigureOfMerit(x=ordered.tabs)
p2 <- plot(ordered.fom, from=1, to=2)

## End(Not run)

```

AgreementBudget

Create an AgreementBudget object

Description

This function quantifies sources of agreement and disagreement between a reference map for time 1, a reference map for time 2 and a simulated map for time 2 to provide meaningful information about the performance of land use change simulations.

Usage

```
AgreementBudget(x, ...)
```

```
## S4 method for signature ThreeMapComparison
AgreementBudget(x, ...)
```

```
## S4 method for signature RasterLayer
AgreementBudget(x, ...)
```

Arguments

<code>x</code>	a ThreeMapComparison object or RasterLayer
<code>...</code>	additional arguments to ThreeMapComparison. Only required if <code>x</code> is not a ThreeMapComparison object

Details

The types of agreement and disagreement considered are those described in Pontius et al. (2011):

1. Persistence simulated correctly (agreement)
2. Persistence simulated as change (disagreement)
3. Change simulated incorrectly (disagreement)
4. Change simulated correctly (agreement)
5. Change simulated as persistence (disagreement)

Value

An AgreementBudget object.

References

Pontius Jr, R.G., Peethambaram, S., Castella, J.C. (2011). Comparison of three maps at multiple resolutions: a case study of land change simulation in Cho Don District, Vietnam. *Annals of the Association of American Geographers* 101(1): 45-62.

See Also

[AgreementBudget-class](#), [plot.AgreementBudget](#), [ThreeMapComparison](#), [FigureOfMerit](#)

Examples

```
## see lulcc-package examples
```

AgreementBudget-class *Class AgreementBudget*

Description

An S4 class for information about sources of agreement and disagreement between three categorical raster maps.

Slots

`tables` list of data.frames that depict the three dimensional table described by Pontius et al. (2011) at different resolutions

`factors` numeric vector of aggregation factors

`maps` list of RasterStack objects containing land use maps at different resolutions

`categories` numeric vector of land use categories

`labels` character vector corresponding to categories

`overall` data.frame containing the overall agreement budget

`category` list of data.frames showing the agreement budget for each category

`transition` list of data.frames showing the agreement budget for all possible transitions

allocate

Allocate land use change spatially

Description

Perform spatially explicit allocation of land use change using different models. Currently the function provides an implementation of the Change in Land Use and its Effects at Small regional extent (CLUE-S) model (Verburg et al., 2002) and an ordered procedure based on the algorithm described by Fuchs et al., (2013), modified to allow stochastic transitions.

Usage

```
allocate(model, ...)

## S4 method for signature 'CluesModel'
allocate(model, ...)

## S4 method for signature 'OrderedModel'
allocate(model, stochastic = TRUE, ...)
```

Arguments

<code>model</code>	an object inheriting from class <code>Model</code>
<code>stochastic</code>	logical indicating whether the model should be run stochastically. Only used if <code>model</code> is an <code>OrderedModel</code> object
<code>...</code>	additional arguments for specific methods

Value

An updated `Model` object.

References

Fuchs, R., Herold, M., Verburg, P.H., and Clevers, J.G.P.W. (2013). A high-resolution and harmonized model approach for reconstructing and analysing historic land changes in Europe, *Biogeosciences*, 10:1543-1559.

Verburg, P.H., Soepboer, W., Veldkamp, A., Limpiada, R., Espaldon, V., Mastura, S.S. (2002). Modeling the spatial dynamics of regional land use: the CLUE-S model. *Environmental management*, 30(3):391-405.

See Also

[CluesModel](#), [OrderedModel](#)

Examples

```
## see lulcc-package examples
```

allow	<i>Implement decision rules for land use change</i>
-------	---

Description

Identify legitimate transitions based on land use history and specific transition rules.

Usage

```
allow(x, categories, cd, rules, hist = NULL, ...)
```

Arguments

x	numeric vector containing the land use pattern for the current timestep
categories	numeric vector containing land use categories in the study region
cd	numeric vector indicating the direction of change for each land use category. A value of 1 means demand is increasing (i.e. the number of cells belonging to the category must increase), -1 means decreasing demand and 0 means demand is static
rules	matrix. See details
hist	numeric vector containing land use history (values represent the number of timesteps the cell has contained the current land use category). Only required for rules 2 and 3
...	additional arguments (none)

Details

Decision rules are based on those described by Verburg et al. (2002). The rules input argument is a square matrix with dimensions equal to the number of land use categories in the study region where rows represent the current land use and columns represent future transitions. The value of each element should represent a rule from the following list:

1. rule == 0 | rule == 1: this rule concerns specific land use transitions that are allowed (1) or not (0)
2. rule > 100 & rule < 1000: this rule imposes a time limit (rule - 100) on land use transitions, after which land use change is not allowed. Time is taken from hist
3. rule > 1000: this rule imposes a minimum period of time (rule-1000) before land use is allowed to change

allow should be called from [allocate](#) methods. The output is a matrix with the same dimensions as the matrix used internally by allocation functions to store land use suitability. Thus, by multiplying the two matrices together, disallowed transitions are removed from the allocation procedure.

Value

A matrix.

References

Verburg, P.H., Soepboer, W., Veldkamp, A., Limpiada, R., Espaldon, V., Mastura, S.S. (2002). Modeling the spatial dynamics of regional land use: the CLUE-S model. *Environmental management*, 30(3):391-405.

See Also

[allowNeighb](#)

Examples

```
## Plum Island Ecosystems

## load observed land use data
obs <- ObsLulcRasterStack(x=pie,
                          pattern="lu",
                          categories=c(1,2,3),
                          labels=c("forest","built","other"),
                          t=c(0,6,14))

## get land use values
x <- getValues(obs[[1]])
x <- x[!is.na(x)]

## create vector of arbitrary land use history values
hist <- sample(1:10, length(x), replace=TRUE)

## calculate demand and get change direction for first timestep
dmd <- approxExtrapDemand(obs=obs, tout=0:14)
cd <- dmd[2,] - dmd[1,]

## create rules matrix, only allowing forest to change if the cell has
## belonged to forest for more than 8 years
rules <- matrix(data=c(1,1008,1008,
                       1,1,1,
                       1,1,1), nrow=3, ncol=3, byrow=TRUE)

allow <- allow(x=x,
              hist=hist,
              categories=obs@categories,
              cd=cd,
              rules=rules)

## create raster showing cells that are allowed to change from forest to built
r <- obs[[1]]
r[!is.na(r)] <- allow[,2]
r[obs[[1]] != 1] <- NA
plot(r)

## NB output is only useful when used within allocation routine
```

allowNeighb

*Implement neighbourhood decision rules***Description**

Identify legitimate transitions for each cell according to neighbourhood decision rules.

Usage

```
allowNeighb(neighb, x, categories, rules, ...)
```

Arguments

neighb	a NeighbRasterStack object
x	a categorical RasterLayer to which neighbourhood rules should be applied. If neighb is supplied it is updated with this map
categories	numeric vector containing land use categories. If allowNeighb is called from an allocation model this argument should contain all categories in the simulation, regardless of whether they're associated with a neighbourhood decision rule
rules	a numeric vector with neighbourhood decision rules. Each rule is a value between 0 and 1 representing the threshold neighbourhood value above which change is allowed. Rules should correspond with x@categories
...	additional arguments (none)

Value

A matrix.

See Also

[allow](#), [NeighbRasterStack](#)

Examples

```
## Plum Island Ecosystems

## load observed land use data
obs <- ObsLulcRasterStack(x=pie,
                          pattern="lu",
                          categories=c(1,2,3),
                          labels=c("forest","built","other"),
                          t=c(0,6,14))

## create a NeighbRasterStack object for forest only
w <- matrix(data=1, nrow=3, ncol=3)
nb <- NeighbRasterStack(x=obs[[1]], weights=w, categories=1)

## only allow change to forest within neighbourhood of current forest cells
## note that rules can be any value between zero (less restrictive) and one
## (more restrictive)
nb.allow <- allowNeighb(neighb=nb,
                       x=obs[[1]],
```



```

t=c(0,6,14))

## obtain demand scenario by interpolating between observed maps
dmd <- approxExtrapDemand(obs=obs, tout=c(0:14))

## plot
matplot(dmd, type="l", ylab="Demand (no. of cells)", xlab="Time point",
        lty=1, col=c("Green","Red","Blue"))
legend("topleft", legend=obs@labels, col=c("Green","Red","Blue"), lty=1)

## linear extrapolation is also possible
dmd <- approxExtrapDemand(obs=obs, tout=c(0:50))

## plot
matplot(dmd, type="l", ylab="Demand (no. of cells)", xlab="Time point",
        lty=1, col=c("Green","Red","Blue"))
legend("topleft", legend=obs@labels, col=c("Green","Red","Blue"), lty=1)

```

as.data.frame.ExpVarRasterList

Coerce objects to data.frame

Description

This function extracts data from all raster objects in [ObsLulcRasterStack](#) or [ExpVarRasterList](#) objects for a specified timestep.

Usage

```

## S3 method for class ExpVarRasterList
as.data.frame(x, row.names = NULL,
              optional = FALSE, cells, t = 0, ...)

## S3 method for class ObsLulcRasterStack
as.data.frame(x, row.names = NULL,
              optional = FALSE, cells, t = 0, ...)

## S4 method for signature ExpVarRasterList
as.data.frame(x, row.names = NULL,
              optional = FALSE, cells, t = 0, ...)

## S4 method for signature ObsLulcRasterStack
as.data.frame(x, row.names = NULL,
              optional = FALSE, cells, t = 0, ...)

```

Arguments

x	an ExpVarRasterList or ObsLulcRasterStack object
row.names	NULL or a character vector giving the row.names for the data.frame. Missing values are not allowed
optional	logical. If TRUE, setting row names and converting column names (to syntactic names: see make.names) is optional

cells	index of cells to be extracted, which may be a <code>SpatialPoints*</code> object or a numeric vector representing cell numbers (see <code>raster::extract</code>)
t	numeric indicating the time under consideration
...	additional arguments (none)

Details

If `x` is an `ObsLulcRasterStack` object the raster corresponding to `t` is first transformed to a `RasterBrick` with a boolean layer for each class with `raster::layerize`.

Value

A `data.frame`.

See Also

`as.data.frame`, `ObsLulcRasterStack`, `ExpVarRasterList`, `partition`

Examples

```
## Not run:

## Plum Island Ecosystems

## observed maps
obs <- ObsLulcRasterStack(x=pie,
                          pattern="lu",
                          categories=c(1,2,3),
                          labels=c("Forest","Built","Other"),
                          t=c(0,6,14))

## explanatory variables
ef <- ExpVarRasterList(x=pie, pattern="ef")

## separate data into training and testing partitions
part <- partition(x=obs[[1]], size=0.1, spatial=TRUE)
df1 <- as.data.frame(x=obs, cells=part[["all"]], t=0)
df2 <- as.data.frame(x=ef, cells=part[["all"]], t=0)

## End(Not run)
```

`c.PredictiveModelList` *Merge PredictiveModelList objects*

Description

Combine different `PredictiveModelList` objects into one

Usage

```
## S3 method for class PredictiveModelList
c(..., recursive = FALSE)
```

Arguments

... two or more PredictiveModelList objects
 recursive for consistency with generic method (ignored)

Value

a PredictiveModelList object

Examples

```
## Not run:

## Plum Island Ecosystems

## load data
data(pie)

## observed maps
obs <- ObsLulcRasterStack(x=pie,
                          pattern="lu",
                          categories=c(1,2,3),
                          labels=c("Forest","Built","Other"),
                          t=c(0,6,14))

## explanatory variables
ef <- ExpVarRasterList(x=pie, pattern="ef")

part <- partition(x=obs[[1]], size=0.1, spatial=TRUE)
train.data <- getPredictiveModelInputData(obs=obs, ef=ef, cells=part[["train"]], t=0)

forms <- list(Built ~ ef_001+ef_002+ef_003,
              Forest ~ 1,
              Other ~ ef_001+ef_002)

glm.models <- glmModels(formula=forms, family=binomial, data=train.data, obs=obs)
glm.models

## separate glm.models into two PredictiveModelList objects
mod1 <- glm.models[[1]]
mod2 <- glm.models[[2:3]]

## put them back together again
glm.models <- c(mod1, mod2)
glm.models

## End(Not run)
```

CategoryLabel-class *Virtual class CategoryLabel*

Description

A virtual S4 class to represent information about categorical Raster* objects.

Slots

categories numeric vector of land use categories
 labels character vector corresponding to categories

 CluesModel

Create a CluesModel object

Description

Methods to create a CluesModel object to supply to [allocate](#).

Usage

```
CluesModel(obs, ef, models, ...)
```

```
## S4 method for signature
## ObsLulcRasterStack,ExpVarRasterList,PredictiveModelList
CluesModel(obs,
  ef, models, time, demand, hist, mask, neighb = NULL, elas, rules = NULL,
  nb.rules = NULL, params, output = NULL, ...)
```

Arguments

obs	an ObsLulcRasterStack
ef	an ExpVarRasterList object
models	a PredictiveModelList object
time	numeric vector containing timesteps over which simulation will occur
demand	matrix with demand for each land use category in terms of number of cells to be allocated. The first row should be the number of cells allocated to the initial observed land use map (i.e. the land use map for time 0)
hist	RasterLayer containing land use history (values represent the number of years the cell has contained the current land use category)
mask	RasterLayer containing binary values where 0 indicates cells that are not allowed to change
neighb	an object of class NeighbRasterStack
elas	numeric indicating the elasticity of each land use category to change. Elasticity varies between 0 and 1, with 0 indicating a low resistance to change and 1 indicating a high resistance to change
rules	matrix with land use change decision rules
nb.rules	numeric with neighbourhood decision rules
params	list with model parameters
output	either a RasterStack containing output maps or NULL
...	additional arguments (none)

Details

The `params` argument is a list of parameter values which should contain the following components:

`jitter.f` Parameter controlling the amount of perturbation applied to the probability surface prior to running the CLUE-S iterative algorithm. Higher values result in more perturbation. Default is 0.0001

`scale.f` Scale factor which controls the amount by which suitability is increased if demand is not met. Default is 0.0005

`max.iter` The maximum number of iterations in the simulation

`max.diff` The maximum allowed difference between allocated and demanded area of any land use type. Default is 5

`ave.diff` The average allowed difference between allocated and demanded area. Default is 5

Note that, in order to achieve convergence, it is likely that some adjustment of these parameters will be required.

Value

A `CluesModel` object.

References

Verburg, P.H., Soepboer, W., Veldkamp, A., Limpiada, R., Espaldon, V., Mastura, S.S. (2002). Modeling the spatial dynamics of regional land use: the CLUE-S model. *Environmental management*, 30(3):391-405.

See Also

[CluesModel-class](#), [allocate](#)

Examples

```
## see lulcc-package examples
```

`CluesModel-class`

Class CluesModel

Description

An S4 class to represent inputs to the CLUE-S land use change model.

Slots

`obs` an `ObsLulcRasterStack` object

`ef` an `ExpVarRasterList` object

`models` a `PredictiveModelList` object

`time` numeric vector of timesteps over which simulation will occur

`demand` matrix containing demand scenario

`hist` `RasterLayer` showing land use history or `NULL`

mask RasterLayer showing masked areas or NULL
 neighb NeighbRasterStack object or NULL
 categories numeric vector of land use categories
 labels character vector corresponding to categories
 rules matrix with land use change decision rules
 nb.rules numeric with neighbourhood decision rules
 elas numeric indicating elasticity to change (only required for
 params list with model parameters
 output RasterStack containing simulated land use maps or NULL

compareAUC	<i>Calculate the area under the ROC curve (AUC)</i>
------------	---

Description

Estimate the AUC for each ROCR: `:prediction` object in a `PredictionList` object.

Usage

```

compareAUC(pred, ...)

## S4 method for signature PredictionList
compareAUC(pred, digits = 4, ...)

## S4 method for signature list
compareAUC(pred, digits = 4, ...)

```

Arguments

pred	a PredictionList object or a list of these
digits	numeric indicating the number of digits to be displayed after the decimal point for AUC values
...	additional arguments (none)

Details

The user can compare the performance of different statistical models by providing a list of `PredictionList` objects. Note that `compareAUC` should be used in conjunction with other comparison methods because the AUC does not contain as much information as, for instance, the ROC curve itself (Pontius and Parmentier, 2014).

Value

A data.frame.

References

- Sing, T., Sander, O., Beerenwinkel, N., Lengauer, T. (2005). ROCr: visualizing classifier performance in R. *Bioinformatics* 21(20):3940-3941.
- Pontius Jr, R. G., & Parmentier, B. (2014). Recommendations for using the relative operating characteristic (ROC). *Landscape ecology*, 29(3), 367-382.

See Also

[PredictionList](#), [ROCr::performance](#)

Examples

```
## see PredictiveModelList examples
```

crossTabulate	<i>Cross tabulate land use transitions</i>
---------------	--

Description

Cross tabulate land use transitions using `raster::crosstab`. This step should form the basis of further research into the processes driving the most important transitions in the study region (Pontius et al., 2004).

Usage

```
crossTabulate(x, y, ...)

## S4 method for signature RasterLayer,RasterLayer
crossTabulate(x, y, categories,
  labels = as.character(categories), ...)

## S4 method for signature ObsLulcRasterStack,ANY
crossTabulate(x, y, times, ...)
```

Arguments

<code>x</code>	RasterLayer representing land use map from an earlier timestep or an ObsLulcRasterStack object containing at least two land use maps for different points in time
<code>y</code>	RasterLayer representing land use map from a later timestep. Not used if <code>x</code> is an ObsLulcRasterStack object
<code>categories</code>	numeric vector containing land use categories to consider. Not used if <code>x</code> is an ObsLulcRasterStack object
<code>labels</code>	character vector (optional) with labels corresponding to categories. Not used if <code>x</code> is an ObsLulcRasterStack object
<code>times</code>	numeric vector representing the time points of two land use maps from ObsLulcRasterStack
<code>...</code>	additional arguments to <code>raster::crosstab</code>

Value

A data.frame.

References

Pontius Jr, R.G., Shusas, E., McEachern, M. (2004). Detecting important categorical land changes while accounting for persistence. *Agriculture, Ecosystems & Environment* 101(2):251-268.

See Also

[ObsLulcRasterStack](#), [raster::crosstab](#)

Examples

```
## Plum Island Ecosystems

## Load observed land use maps
obs <- ObsLulcRasterStack(x=pie,
                          pattern="lu",
                          categories=c(1,2,3),
                          labels=c("forest","built","other"),
                          t=c(0,6,14))

crossTabulate(x=obs, times=c(0,14))

## RasterLayer input
crossTabulate(x=obs[[1]],
              y=obs[[3]],
              categories=c(1,2,3),
              labels=c("forest","built","other"))
```

ExpVarRasterList

Create an ExpVarRasterList object

Description

Methods to load maps of explanatory variables, which may be created from file, an existing Raster* object or a list of Raster* objects.

Usage

```
ExpVarRasterList(x, ...)

## S4 method for signature missing
ExpVarRasterList(x, pattern = NULL, ...)

## S4 method for signature character
ExpVarRasterList(x, pattern = NULL, ...)

## S4 method for signature RasterStack
ExpVarRasterList(x, pattern = NULL, ...)

## S4 method for signature list
ExpVarRasterList(x, pattern = NULL, ...)
```

Arguments

<code>x</code>	path (character) to directory containing observed land use maps, a Raster* object or a list of Raster* objects
<code>pattern</code>	regular expression (character). Only filenames (if <code>x</code> is a path) or Raster* objects (if <code>x</code> is a list) matching the regular expression will be returned. See <code>raster::raster</code> for more information about supported filetypes
<code>...</code>	additional arguments to <code>raster::stack</code>

Details

Explanatory variables should follow a naming convention to identify them as static (one map provided for the study period) or dynamic (one map provided for each year of the study period). The name should consist of two (static) or three (dynamic) parts: firstly, the prefix should differentiate explanatory variables from other maps in the directory, list or RasterStack. This should be followed by a unique number to differentiate the explanatory variables (note that the order of variables in the ExpVarRasterList object is determined by this value) If the variable is dynamic this number should be followed by a second number representing the timestep to which the map applies. Dynamic variables should include a map for time 0 (corresponding to the initial observed map) and every subsequent timestep in the simulation. The different parts should be separated by a period or underscore.

Maps of different explanatory variables should have the same coordinate reference system but do not have to have the same extent and resolution as long as the minimum extent is that of the study region defined by an ObsLulcRasterStack object. However, maps for different timesteps of the same dynamic variable should have the same extent and resolution because these are stored as RasterStack objects.

Value

An ExpVarRasterList object.

See Also

`raster::stack`

Examples

```
## Plum Island Ecosystems
ef <- ExpVarRasterList(x=pie, pattern="ef")

## Sibuyan
ef <- ExpVarRasterList(x=sibuyan$maps, pattern="ef")
```

ExpVarRasterList-class

Class ExpVarRasterList

Description

An S4 class for explanatory variables.

Slots

maps list of RasterStack objects. The length of the list corresponds to the number of explanatory variables and the number of layers in each RasterStack represents time

names character vector with the name of each variable in maps

dynamic logical indicating whether dynamic variables are present

 Extract by index

Extract by index

Description

object[[i]] can be used to extract individual objects from container classes such as ExpVarRasterList, PredictiveModelList, PredictionList and PerformanceList.

Usage

```
## S4 method for signature ExpVarRasterList,ANY,ANY
x[[i, j, ...]]
```

```
## S4 method for signature CategoryLabel,ANY,ANY
x[[i, j, ...]]
```

Arguments

x	an object of class ExpVarRasterList or any object inheriting from the virtual class CategoryLabel
i	layer number (if 'x' inherits from a RasterStack) or list index (if 'x' stores data as a list)
j	numeric (not used)
...	additional arguments (none)

Examples

```
## Plum Island Ecosystems
```

```
## Load observed land use maps
```

```
obs <- ObsLulcRasterStack(x=pie,
  pattern="lu",
  categories=c(1,2,3),
  labels=c("forest","built","other"),
  t=c(0,6,14))
```

```
summary(obs[[1]])
```

```
summary(obs[[1:2]])
```

FigureOfMerit	Create a FigureOfMerit object
---------------	-------------------------------

Description

Calculate the figure of merit at different levels and at different resolutions for a reference map at time 1, a reference map at time 2 and a simulated map at time 2.

Usage

```
FigureOfMerit(x, ...)

## S4 method for signature RasterLayer
FigureOfMerit(x, ...)

## S4 method for signature ThreeMapComparison
FigureOfMerit(x, ...)
```

Arguments

x	a ThreeMapComparison object or RasterLayer
...	additional arguments to ThreeMapComparison. Only required if x is not a ThreeMapComparison object

Details

In land use change modelling the figure of merit is the intersection of observed change and simulated change divided by the union of these, with a range of 0 (perfect disagreement) to 1 (perfect agreement). It is useful to calculate the figure of merit at three levels: (1) considering all possible transitions from all land use categories, (2) considering all transitions from specific land use categories and (3) considering a specific transition from one land use category to another.

Value

A FigureOfMerit object.

References

Pontius Jr, R.G., Peethambaram, S., Castella, J.C. (2011). Comparison of three maps at multiple resolutions: a case study of land change simulation in Cho Don District, Vietnam. *Annals of the Association of American Geographers* 101(1): 45-62.

See Also

[plot.FigureOfMerit, ThreeMapComparison](#)

Examples

```
## see lulcc-package examples
```

FigureOfMerit-class *Class FigureOfMerit*

Description

An S4 class for different figure of merit scores.

Slots

tables list of data.frames that depict the three dimensional table described by Pontius et al. (2011) at different resolutions
factors numeric vector of aggregation factors
maps list of RasterStack objects containing land use maps at different resolutions
categories numeric vector of land use categories
labels character vector corresponding to categories
overall list containing the overall figure of merit score for each aggregation factor
category list of numeric vectors containing category specific scores
transition list of matrices containing transition specific scores

getPredictiveModelInputData
Extract data to fit predictive models

Description

Extract a data.frame containing variables required for fitting predictive models.

Usage

```
getPredictiveModelInputData(obs, ef, cells, ...)
```

Arguments

obs	an ObsLulcRasterStack object
ef	an ExpVarRasterList object
cells	index of cells to be extracted, which may be a SpatialPoints* object or a numeric vector representing cell numbers (see raster::extract)
...	additional arguments to as.data.frame

Value

A data.frame.

See Also

[as.data.frame](#), [ObsLulcRasterStack](#), [ExpVarRasterList](#), [partition](#)

Examples

```
## TODO
```

Model fitting	<i>Fit predictive models</i>
---------------	------------------------------

Description

These functions fit parametric and non-parametric models to data.

Usage

```
glmModels(formula, family = binomial, model = FALSE, ..., obs,
           categories = NA, labels = NA)
```

```
randomForestModels(formula, ..., obs, categories = NA, labels = NA)
```

```
rpartModels(formula, ..., obs, categories = NA, labels = NA)
```

Arguments

formula	list containing formula objects
family	see glm . Default is 'binomial'. Only used by <code>glmModels</code>
model	see glm . Default is FALSE. Only used by <code>glmModels</code>
...	additional arguments to specific functions
obs	an <code>ObsLulcRasterStack</code> object
categories	numeric vector of land use categories in observed maps. Only required if 'obs' is missing
labels	character vector (optional) with labels corresponding to categories. Only required if 'obs' is missing

Value

A `PredictiveModelList` object.

See Also

[glm](#), `rpart::rpart`, `randomForest::randomForest`

Examples

```
## see lulcc-package examples
```

Model-class	<i>Virtual class Model</i>
-------------	----------------------------

Description

A virtual S4 class to represent land use change models.

Slots

output RasterStack containing simulated land use maps or NULL

NeighbRasterStack	<i>Create a NeighbRasterStack object</i>
-------------------	--

Description

Methods to calculate neighbourhood values for cells in raster maps using `raster::focal`. By default the fraction of non-NA cells within the moving window (i.e. the size of the weights matrix) devoted to each land use category is calculated. This behaviour can be changed by altering the weights matrix or providing an alternative function. The resulting object can be used as the basis of neighbourhood decision rules.

Usage

```
NeighbRasterStack(x, weights, neighb, ...)

## S4 method for signature RasterLayer,list,ANY
NeighbRasterStack(x, weights, neighb,
  categories, fun = mean, ...)

## S4 method for signature RasterLayer,matrix,ANY
NeighbRasterStack(x, weights, neighb,
  categories, fun = mean, ...)

## S4 method for signature RasterLayer,ANY,NeighbRasterStack
NeighbRasterStack(x, weights,
  neighb)
```

Arguments

<code>x</code>	RasterLayer containing categorical data
<code>weights</code>	list containing a matrix of weights (the <code>w</code> argument in <code>raster::focal</code>) for each land use category. The order of list or vector elements should correspond to the order of land use categories in <code>categories</code>
<code>neighb</code>	NeighbRasterStack object. Only used if <code>categories</code> and <code>weights</code> are not provided. This option can be useful when existing NeighbRasterStack objects need to be updated because a new land use map is available, such as during the allocation procedure.
<code>categories</code>	numeric vector containing land use categories for which neighbourhood values should be calculated
<code>fun</code>	function. Input argument to <code>focal</code> . Default is <code>mean</code>
<code>...</code>	additional arguments to <code>raster::focal</code>

Value

A NeighbRasterStack object.

See Also

[NeighbRasterStack-class](#), [allowNeighb](#), `raster::focal`

Examples

```
## Plum Island Ecosystems

## observed data
obs <- ObsLulcRasterStack(x=pie,
                          pattern="lu",
                          categories=c(1,2,3),
                          labels=c("forest","built","other"),
                          t=c(0,6,14))

## create a NeighbRasterStack object for 1985 land use map
w1 <- matrix(data=1, nrow=3, ncol=3, byrow=TRUE)
w2 <- w1
w3 <- w1

nb1 <- NeighbRasterStack(x=obs[[1]],
                        categories=c(1,2,3),
                        weights=list(w1,w2,w3))

## update nb2 for 1991
nb2 <- NeighbRasterStack(x=obs[[2]],
                        neighb=nb1)

## plot neighbourhood map for forest
plot(nb2[[1]])
```

NeighbRasterStack-class

Class NeighbRasterStack

Description

An S4 class for neighbourhood maps.

Slots

filename see raster::[Raster-class](#)

layers see raster::[Raster-class](#)

title see raster::[Raster-class](#)

extent see raster::[Raster-class](#)

rotated see raster::[Raster-class](#)

rotation see raster::[Raster-class](#)

ncols see raster::[Raster-class](#)

nrows see raster::[Raster-class](#)

crs see raster::[Raster-class](#)

history see raster::[Raster-class](#)

z see raster::[Raster-class](#)

calls list containing each call to raster::[focal](#)

categories numeric vector of land use categories for which neighbourhood maps exist

ObsLulcRasterStack	<i>Create an ObsLulcRasterStack object</i>
--------------------	--

Description

Methods to create an ObsLulcRasterStack object, which may be created from file, an existing Raster* object or a list of Raster* objects.

Usage

```
ObsLulcRasterStack(x, pattern, ...)

## S4 method for signature missing,character
ObsLulcRasterStack(x, pattern, ...)

## S4 method for signature character,character
ObsLulcRasterStack(x, pattern, ...)

## S4 method for signature list,character
ObsLulcRasterStack(x, pattern, ...)

## S4 method for signature RasterLayer,ANY
ObsLulcRasterStack(x, pattern, ...)

## S4 method for signature RasterStack,ANY
ObsLulcRasterStack(x, pattern, categories, labels,
  t)
```

Arguments

x	path (character), Raster* object or list of Raster* objects. Default behaviour is to search for files in the working directory
pattern	regular expression (character). Only filenames (if x is a path) or Raster* objects (if x is a list) matching the regular expression will be returned. See <code>raster::raster</code> for more information about supported filetypes
categories	numeric vector of land use categories in observed maps
labels	character vector (optional) with labels corresponding to categories
t	numeric vector containing the timestep of each observed map. The first timestep must be 0
...	additional arguments to <code>raster::stack</code>

Details

Observed land use maps should have the same extent and resolution. The location of non-NA cells in ObsLulcRasterStack objects defines the region for subsequent analysis.

Value

An ObsLulcRasterStack object.

See Also

[ObsLulcRasterStack-class](#), [raster::stack](#)

Examples

```
## Plum Island Ecosystems
obs <- ObsLulcRasterStack(x=pie,
  pattern="lu",
  categories=c(1,2,3),
  labels=c("forest","built","other"),
  t=c(0,6,14))

## Sibuyan Island
obs <- ObsLulcRasterStack(x=sibuyan$maps,
  pattern="lu",
  categories=c(1,2,3,4,5),
  labels=c("forest","coconut","grass","rice","other"),
  t=c(0,14))
```

ObsLulcRasterStack-class

Class ObsLulcRasterStack

Description

An S4 class for observed land use maps.

Slots

filename see [raster::Raster-class](#)
 layers see [raster::Raster-class](#)
 title see [raster::Raster-class](#)
 extent see [raster::Raster-class](#)
 rotated see [raster::Raster-class](#)
 rotation see [raster::Raster-class](#)
 ncols see [raster::Raster-class](#)
 nrows see [raster::Raster-class](#)
 crs see [raster::Raster-class](#)
 history see [raster::Raster-class](#)
 z see [raster::Raster-class](#)
 t numeric vector with timesteps corresponding to each observed map
 categories numeric vector of land use categories
 labels character vector corresponding to categories

OrderedModel	Create an OrderedModel object
--------------	-------------------------------

Description

Methods to create a OrderedModel object to supply to [allocate](#).

Usage

```
OrderedModel(obs, ef, models, ...)
```

```
## S4 method for signature
## ObsLulcRasterStack,ExpVarRasterList,PredictiveModelList
OrderedModel(obs,
  ef, models, time, demand, hist, mask, neighb = NULL, rules = NULL,
  nb.rules = NULL, order, params, output = NULL, ...)
```

Arguments

obs	an ObsLulcRasterStack object
ef	an ExpVarRasterList object
models	a PredictiveModelList object
time	numeric vector containing timesteps over which simulation will occur
demand	matrix with demand for each land use category in terms of number of cells to be allocated. The first row should be the number of cells allocated to the initial observed land use map (i.e. the land use map for time 0)
hist	RasterLayer containing land use history (values represent the number of years the cell has contained the current land use category)
mask	RasterLayer containing binary values where 0 indicates cells that are not allowed to change
neighb	an object of class NeighbRasterStack
rules	matrix with land use change decision rules
nb.rules	numeric with neighbourhood decision rules
order	numeric vector of land use categories in the order that change should be allocated. See Details
params	list with model parameters
output	either a RasterStack containing output maps or NULL
...	additional arguments (none)

Details

The params argument is a list of parameter values which should contain the following components:

`max.diff` The maximum allowed difference between allocated and demanded area of any land use type. Default is 5

Value

An OrderedModel object.

References

Fuchs, R., Herold, M., Verburg, P.H., and Clevers, J.G.P.W. (2013). A high-resolution and harmonized model approach for reconstructing and analysing historic land changes in Europe, *Biogeosciences*, 10:1543-1559.

See Also

[OrderedModel-class](#), [allocate](#)

Examples

```
## see lulcc-package examples
```

OrderedModel-class	<i>Class OrderedModel</i>
--------------------	---------------------------

Description

An S4 class to represent inputs to the Ordered allocation procedure

Slots

obs an ObsLulcRasterStack object
 ef an ExpVarRasterList object
 models a PredictiveModelList object
 time numeric vector of timesteps over which simulation will occur
 demand matrix containing demand scenario
 hist RasterLayer showing land use history or NULL
 mask RasterLayer showing masked areas or NULL
 neighb NeighbRasterStack object or NULL
 categories numeric vector of land use categories
 labels character vector corresponding to categories
 rules matrix with land use change decision rules
 nb.rules numeric with neighbourhood decision rules
 order numeric vector of land use categories in the order that change should be allocated
 params list with model parameters
 output RasterStack containing simulated land use maps or NULL

partition	<i>Partition raster data</i>
-----------	------------------------------

Description

Divide a categorical raster map into training and testing partitions. A wrapper function for `caret::createDataPartition` (Kuhn, 2008) to divide a categorical raster map into training and testing partitions.

Usage

```
partition(x, size = 0.5, spatial = TRUE, ...)
```

Arguments

x	RasterLayer with categorical data
size	numeric value between zero and one indicating the proportion of non-NA cells that should be included in the training partition. Default is 0.5, which results in equally sized partitions
spatial	logical. If TRUE, the function returns a SpatialPoints object with the coordinates of cells in each partition. If FALSE, the cell numbers are returned
...	additional arguments (none)

Value

A list containing the following components:

train a `SpatialPoints` object or numeric vector indicating the cells in the training partition

test a `SpatialPoints` object or numeric vector indicating the cells in the testing partition

all a SpatialPoints object or numeric vector indicating all non-NA cells in the study region

References

Kuhn, M. (2008). Building predictive models in R using the caret package. *Journal of Statistical Software*, 28(5), 1-26.

See Also

```
caret::createDataPartition
```

Examples

[illegible]


```

t=c(0,6,14))

## create equally sized training and testing partitions
part <- partition(x=obs[[1]], size=0.1, spatial=FALSE)
names(part)

## End(Not run)

```

performance

Create ROCR performance objects

Description

A wrapper function for ROCR: [:performance](#) (Sing et al, 2005) to create performance objects from a list of prediction objects.

Usage

```

performance(prediction.obj, ...)

## S4 method for signature list
performance(prediction.obj, measure, x.measure = "cutoff",
  ...)

```

Arguments

`prediction.obj` a list of ROCR: [:prediction](#) objects

`measure` performance measure to use for the evaluation. See ROCR: [:performance](#)

`x.measure` a second performance measure. See ROCR: [:performance](#)

`...` additional arguments to ROCR: [:performance](#)

Value

A list of performance objects.

References

Sing, T., Sander, O., Beerenwinkel, N., Lengauer, T. (2005). ROCR: visualizing classifier performance in R. *Bioinformatics* 21(20):3940-3941.

See Also

ROCR: [:prediction](#), ROCR: [:performance](#)

PerformanceList	Create a PerformanceList object
-----------------	---------------------------------

Description

This function uses different measures to evaluate multiple ROCR: [:prediction](#) objects stored in a [PredictionList](#) object.

Usage

```
PerformanceList(pred, measure, x.measure = "cutoff", ...)
```

Arguments

pred	an object of class PredictionList
measure	performance measure to use for the evaluation. See ROCR: :performance
x.measure	a second performance measure. See ROCR: :performance
...	additional arguments to ROCR: :performance

Value

A PerformanceList object.

References

Sing, T., Sander, O., Beerenwinkel, N., Lengauer, T. (2005). ROCR: visualizing classifier performance in R. Bioinformatics 21(20):3940-3941.

See Also

[performance](#), [PredictionList](#)

Examples

```
## see lulcc-package examples
```

PerformanceList-class	Class PerformanceList
-----------------------	-----------------------

Description

An S4 class that extends ROCR: [:performance-class](#) to hold the results of multiple model evaluations.

Slots

performance	list of ROCR performance objects. Each object is calculated for the corresponding ROCR prediction object held in the PredictionList object supplied to the constructor function
auc	numeric vector containing the area under the curve for each performance object
categories	numeric vector of land use categories for which performance objects were created
labels	character vector with labels corresponding to categories

 pie

Land use change dataset for Plum Island Ecosystem

Description

Dataset containing land use maps for 1985, 1991 and 1999 and several explanatory variables derived from Pontius and Parmentier (2014).

Usage

```
pie
```

Format

A list containing the following elements:

lu_pie_1985 RasterLayer showing land use in 1985 (forest, built, other)

lu_pie_1991 RasterLayer showing land use in 1991

lu_pie_1999 RasterLayer showing land use in 1999

ef_001 RasterLayer showing elevation

ef_002 RasterLayer showing slope

ef_003 RasterLayer showing distance to built land in 1985

References

Pontius Jr, R. G., & Parmentier, B. (2014). Recommendations for using the relative operating characteristic (ROC). *Landscape ecology*, 29(3), 367-382.

Examples

```
data(pie)
```

 plot

Plot method for objects based on Raster data*

Description

Plot lulcc objects based on Raster* data

Usage

```
## S3 method for class ObsLulcRasterStack
plot(x, y, ...)

## S3 method for class Model
plot(x, y, ...)

## S3 method for class ThreeMapComparison
plot(x, y, category, factors, ...)

## S4 method for signature ObsLulcRasterStack,ANY
plot(x, y, ...)

## S4 method for signature Model,ANY
plot(x, y, ...)

## S4 method for signature ThreeMapComparison,ANY
plot(x, y, category, factors, ...)
```

Arguments

x	an object from lulcc containing Raster data
y	not used
category	numeric
factors	numeric
...	additional arguments to rasterVis:: levelplot

Value

A trellis object.

See Also

rasterVis::[levelplot](#)

Examples

```
## see lulcc-package examples
```

plot.AgreementBudget *Plot method for AgreementBudget objects*

Description

Plot an [AgreementBudget](#) object.

Usage

```
## S3 method for class AgreementBudget
plot(x, y, from, to,
     col = RColorBrewer::brewer.pal(5, "Set2"), key, scales, xlab, ylab, ...)

## S4 method for signature AgreementBudget,ANY
plot(x, y, from, to,
     col = RColorBrewer::brewer.pal(5, "Set2"), key, scales, xlab, ylab, ...)
```

Arguments

x	an AgreementBudget object
y	not used
from	optional numeric value representing a land use category. If provided without to the figure of merit for all transitions from this category will be plotted
to	similar to from. If provided with a valid from argument the transition defined by these two arguments (i.e. from -> to) will be plotted
col	character specifying the plotting colour. Default is to use the 'Set2' palette from RColorBrewer
key	list. See lattice::xyplot
scales	list. See lattice::xyplot
xlab	character or expression. See lattice::xyplot
ylab	character or expression. See lattice::xyplot
...	additional arguments to lattice::xyplot

Details

The plot layout is based on work presented in Pontius et al. (2011)

Value

A trellis object.

References

Pontius Jr, R.G., Peethambaram, S., Castella, J.C. (2011). Comparison of three maps at multiple resolutions: a case study of land change simulation in Cho Don District, Vietnam. *Annals of the Association of American Geographers* 101(1): 45-62.

See Also

[AgreementBudget](#), [lattice::xyplot](#)

Examples

```
## see lulcc-package examples
```

plot.FigureOfMerit *Plot method for FigureOfMerit objects*

Description

Plot the overall, category-specific or transition-specific figure of merit at different resolutions.

Usage

```
## S3 method for class FigureOfMerit
plot(x, y, ..., from, to,
     col = RColorBrewer::brewer.pal(8, "Set2"), type = "b", key, scales, xlab,
     ylab)

## S4 method for signature FigureOfMerit,ANY
plot(x, y, ..., from, to,
     col = RColorBrewer::brewer.pal(8, "Set2"), type = "b", key, scales, xlab,
     ylab)
```

Arguments

x	a FigureOfMerit object
y	not used
from	optional numeric value representing a land use category. If provided without to the figure of merit for all transitions from this category will be plotted
to	similar to from. If provided with a valid from argument the transition defined by these two arguments (i.e. from-> to) will be plotted. It is possible to include more than one category in which case the different transitions will be included on the same plot
col	character specifying the plotting colour. Default is to use the 'Set2' palette from RColorBrewer
type	character. See <code>lattice::panel.xyplot</code>
key	list. See <code>lattice::xyplot</code>
scales	list. See <code>lattice::xyplot</code>
xlab	character or expression. See <code>lattice::xyplot</code>
ylab	character or expression. See <code>lattice::xyplot</code>
...	additional arguments to <code>lattice::xyplot</code>

Value

A trellis object.

See Also

`FigureOfMerit`, `lattice::xyplot`, `lattice::panel.xyplot`

Examples

```
## see lulcc-package examples
```

plot.PerformanceList *Plot method for PerformanceList objects*

Description

Plot the the ROC curve for each performance object in a [PerformanceList](#) object. If more than one PerformanceList objects are provided ROC curves for the same land use category from different objects are included on the same plot for model comparison.

Usage

```
## S3 method for class PerformanceList
plot(x, y, multipanel = TRUE, type = "l",
     abline = list(c(0, 1), col = "grey"), col = RColorBrewer::brewer.pal(9,
     "Set1"), key.args = NULL, ...)

## S4 method for signature list,ANY
plot(x, y, multipanel = TRUE, type = "l",
     abline = list(c(0, 1), col = "grey"), col = RColorBrewer::brewer.pal(9,
     "Set1"), key.args = NULL, ...)
```

Arguments

x	either a single PerformanceList object or a list of these. If a list is provided it must be named.
y	not used
multipanel	logical. If TRUE, create a trellis plot where the number of panels equals the number of PerformanceList objects. Otherwise, create a single plot for each PerformanceList object
type	character. See lattice::panel.xyplot
abline	list. See lattice::panel.xyplot
col	character. Plotting colour
key.args	list containing additional components to be passed to the key argument of lattice::xyplot
...	additional arguments to lattice::xyplot

Value

A trellis object.

See Also

[PerformanceList](#), [lattice::xyplot](#)

Examples

```
## see lulcc-package examples
```

```
predict.PredictiveModelList
      Predict location suitability
```

Description

Estimate location suitability with predictive models.

Usage

```
## S3 method for class PredictiveModelList
predict(object, newdata, data.frame = FALSE,
        ...)

## S4 method for signature PredictiveModelList
predict(object, newdata, data.frame = FALSE,
        ...)
```

Arguments

object	a PredictiveModelList object
newdata	data.frame containing new data
data.frame	logical indicating whether the function should return a matrix (default) or data.frame
...	additional arguments to predict methods

Details

This function is usually called from `allocate` to calculate land use suitability at each timestep. However, it may also be used to produce suitability maps (see examples).

Value

A matrix.

See Also

[Model fitting](#), [allocate](#)

Examples

```
## Not run:

## Sibuyan Island

## load observed land use data
obs <- ObsLulcRasterStack(x=sibuyan$maps,
                          pattern="lu",
                          categories=c(1,2,3,4,5),
                          labels=c("Forest","Coconut","Grass","Rice","Other"),
                          t=c(0,14))

## load explanatory variables
```



```

ef <- ExpVarRasterList(x=sibuyan$maps, pattern="ef")

## separate data into training and testing partitions
part <- partition(x=obs[[1]], size=0.1, spatial=TRUE)
train.data <- getPredictiveModelInputData(obs=obs, ef=ef, cells=part[["train"]])
all.data <- getPredictiveModelInputData(obs=obs, ef=ef, cells=part[["all"]])

## get glm.models from data
forms <- list(Forest ~ ef_001+ef_002+ef_003+ef_004+ef_005+ef_006+ef_007+ef_008+ef_010+ef_012,
              Coconut ~ ef_001+ef_002+ef_005+ef_007+ef_008+ef_009+ef_010+ef_011+ef_012,
              Grass~ef_001+ef_002+ef_004+ef_005+ef_007+ef_008+ef_009+ef_010+ef_011+ef_012+ef_013,
              Rice~ef_009+ef_010+ef_011,
              Other~1)

glm.models <- glmModels(formula=forms, family=binomial, data=train.data, obs=obs)

## create suitability maps
suitability.maps <- predict(object=glm.models, newdata=all.data, data.frame=TRUE)
points <- rasterToPoints(obs[[1]], spatial=TRUE)
suitability.maps <- SpatialPointsDataFrame(coords=points, data=suitability.maps)
r <- stack(rasterize(x=suitability.maps, y=obs[[1]], field=names(suitability.maps)))
plot(r)

## library(rasterVis)
## levelplot(r)

## End(Not run)

```

PredictionList

Create a PredictionList object

Description

This function creates a `ROCR::prediction` object for each predictive model in a `PredictiveModelList` object. It should be used with `PerformanceList` to evaluate multiple models with exactly the same criteria while keeping track of which model corresponds to which land use category.

Usage

```
PredictionList(models, newdata, ...)
```

Arguments

<code>models</code>	a <code>PredictiveModelList</code> object
<code>newdata</code>	a data.frame containing new data
<code>...</code>	additional arguments to <code>ROCR::prediction</code>

Value

A `PredictionList` object.

References

Sing, T., Sander, O., Beerenwinkel, N., Lengauer, T. (2005). ROCR: visualizing classifier performance in R. Bioinformatics 21(20):3940-3941.

See Also

link{PerformanceList}, ROCR::prediction

Examples

```
## see lulcc-package examples
```

PredictionList-class *Class PredictionList*

Description

An S4 class that extends ROCR::prediction-class to hold the results of multiple model predictions.

Slots

prediction a list of ROCR::prediction-class objects. These objects are calculated for each statistical model in the PredictiveModelList object supplied to the constructor function

categories numeric vector of land use categories for which prediction objects were created

labels character vector with labels corresponding to categories

PredictiveModelList-class
 Class PredictiveModelList

Description

An S4 class to hold multiple mathematical models for different land use categories belonging to the same map.

Slots

models list of predictive models

categories numeric vector of land use categories

labels character vector with labels corresponding to categories

resample,ExpVarRasterList,Raster-method

Resample maps in ExpVarRasterList object or list

Description

A wrapper function for `raster::resample` to resample raster objects in an `ExpVarRasterList` object or list.

Usage

```
## S4 method for signature ExpVarRasterList,Raster
resample(x, y, method = "ngb", ...)
```

```
## S4 method for signature list,Raster
resample(x, y, method = "ngb", ...)
```

Arguments

<code>x</code>	an <code>ExpVarRasterList</code> object or list of <code>Raster*</code> maps to be resampled
<code>y</code>	<code>Raster*</code> object with parameters that <code>x</code> should be resampled to
<code>method</code>	method used to compute values for the new <code>RasterLayer</code> , should be "bilinear" for bilinear interpolation, or "ngb" for nearest neighbour
<code>...</code>	additional arguments to <code>raster::resample</code>

Value

An `ExpVarRasterList` object or list, depending on `x`.

See Also

[ExpVarRasterList](#), `raster::resample`

Examples

```
## Not run:

## Plum Island Ecosystems

## observed data
obs <- ObsLulcRasterStack(x=pie,
                          pattern="lu",
                          categories=c(1,2,3),
                          labels=c("forest","built","other"),
                          t=c(0,6,14))

## explanatory variables
ef <- ExpVarRasterList(x=pie, pattern="ef")

## resample to ensure maps have same characteristics as observed maps
ef <- resample(x=ef, y=obs, method="ngb")
```

```
## End(Not run)
```

roundSum	<i>Round elements in matrix or data.frame rows</i>
----------	--

Description

Round all numbers in a matrix or data.frame while ensuring that all rows sum to the same value.

Usage

```
roundSum(x, ncell, ...)
```

Arguments

x	matrix or data.frame
ncell	numeric specifying the target sum for each row in x
...	additional arguments (none)

Details

The main application of roundSum is to ensure that each row in the demand matrix specifies exactly the number of cells to be allocated to each land use category for the respective timestep. It may also be used to convert the units of demand to number of cells.

Value

A matrix.

Examples

```
## Sibuyan Island

## load observed land use data and create demand scenario
obs <- ObsLulcRasterStack(x=sibuyan$maps,
                          pattern="lu",
                          categories=c(1,2,3,4,5),
                          labels=c("Forest","Coconut","Grass","Rice","Other"),
                          t=c(0,14))

dmd <- approxExtrapDemand(obs, tout=0:14)
apply(dmd, 1, sum)

## artificially perturb for illustration purposes
dmd <- dmd * runif(1)
apply(dmd, 1, sum)

## use roundSum to correct demand scenario
ncell <- length(which(!is.na(getValues(sibuyan$maps$lu_sib_1997))))
ncell
dmd <- roundSum(dmd, ncell=ncell)
apply(dmd, 1, sum)
```

show,ExpVarRasterList-method
Show

Description

Show objects

Usage

```
## S4 method for signature ExpVarRasterList
show(object)

## S4 method for signature PredictiveModelList
show(object)

## S4 method for signature PredictionList
show(object)

## S4 method for signature PerformanceList
show(object)

## S4 method for signature Model
show(object)

## S4 method for signature ThreeMapComparison
show(object)
```

Arguments

object an object belonging to one of the classes in lulcc

sibuyan *Land use change dataset for Sibuyan Island*

Description

Dataset containing land use map for 1997 and several explanatory variables for Sibuyan Island derived from Verburg et al. (2002). Data are modified by Peter Verburg to demonstrate the CLUE-s model; as such the dataset should not be used for purposes other than demonstration.

Usage

sibuyan

Format

A list containing the following components:

maps list containing the following RasterLayers:

lu_sib_1997 RasterLayer with land use in 1997 (forest, coconut, grassland, rice, other)

ef_001 RasterLayer showing distance to sea

ef_002 RasterLayer showing mean population density

ef_003 RasterLayer showing occurrence of diorite rock

ef_004 RasterLayer showing occurrence of ultramafic rock

ef_005 RasterLayer showing occurrence of sediments

ef_006 RasterLayer showing areas with no erosion

ef_007 RasterLayer showing areas with moderate erosion

ef_008 RasterLayer showing elevation

ef_009 RasterLayer showing slope

ef_010 RasterLayer showing aspect

ef_011 RasterLayer showing distance to roads in 1997

ef_012 RasterLayer showing distance to urban areas in 1997

ef_013 RasterLayer showing distance to streams

restr1 RasterLayer showing location of current national park

restr2 RasterLayer showing location of proposed national park

demand list of matrices with different demand scenarios:

demand1 data.frame with demand scenario representing slow growth scenario

demand2 data.frame with demand scenario representing fast growth scenario

demand3 data.frame with demand scenario representing land use change primarily for food production

References

Verburg, P.H., Soepboer, W., Veldkamp, A., Limpiada, R., Espaldon, V., Mastura, S.S (2002). Modeling the Spatial Dynamics of Regional Land Use: The CLUE-S Model. *Environmental Management* 30(3): 391-405.

Examples

```
data(sibuyan)
```

```
subset,ExpVarRasterList-method
```

Subset

Description

Extract a subset of objects from container classes such as ExpVarRasterList, PredictiveModelList, PredictionList and PerformanceList.

Usage

```
## S4 method for signature ExpVarRasterList
subset(x, subset, ...)

## S4 method for signature PredictiveModelList
subset(x, subset, ...)

## S4 method for signature PerformanceList
subset(x, subset, ...)

## S4 method for signature PredictionList
subset(x, subset, ...)
```

Arguments

x	an object of class ExpVarRasterList, PredictiveModelList, PredictionList or PerformanceList
subset	integer or character indicating the objects to be extracted
...	additional arguments (none)

Examples

```
## Sibuyan Island

## load observed land use data
obs <- ObsLulcRasterStack(x=sibuyan$maps,
                          pattern="lu",
                          categories=c(1,2,3,4,5),
                          labels=c("Forest", "Coconut", "Grass", "Rice", "Other"),
                          t=c(0,14))

summary(obs)
obs <- subset(obs, subset=names(obs)[1])
summary(obs)

## load explanatory variables
ef <- ExpVarRasterList(x=sibuyan$maps, pattern="ef")

summary(ef)
ef <- subset(ef, subset=1:5)
summary(ef)
```

summary

*Summary***Description**

Summarise lulcc objects containing Raster* data or predictive models

Usage

```
summary(object, ...)

## S4 method for signature ObsLulcRasterStack
summary(object, ...)

## S4 method for signature ExpVarRasterList
summary(object, ...)

## S4 method for signature NeighbRasterStack
summary(object, ...)

## S4 method for signature PredictiveModelList
summary(object, ...)

## S4 method for signature Model
summary(object, ...)
```

Arguments

object	an object belonging to one of the classes in lulcc
...	additional arguments (none)

Value

A matrix, data.frame or list

ThreeMapComparison	<i>Evaluate allocation performance with three maps</i>
--------------------	--

Description

An implementation of the method described by Pontius et al. (2011), which compares a reference map at time 1, a reference map at time 2 and a simulated map at time 2 to evaluate allocation performance at multiple resolutions while taking into account persistence. The method quantifies disagreement within coarse squares (minor allocation disagreement), disagreement between coarse squares (major allocation disagreement), disagreement about the quantity of land use change and agreement.

Usage

```
ThreeMapComparison(x, x1, y1, ...)

## S4 method for signature Model,ANY,ANY
ThreeMapComparison(x, x1, y1, factors, timestep, ...)

## S4 method for signature RasterLayer,RasterLayer,RasterLayer
ThreeMapComparison(x, x1, y1,
  factors, categories, labels, ...)
```


Arguments

x	either a RasterLayer of observed land use at time 0 or an object inheriting from class Model
x1	a RasterLayer of observed land use at a subsequent time. Only required if x is also a RasterLayer
y1	a RasterLayer of simulated land use corresponding to x1. Only required if x is also a RasterLayer
factors	numeric vector of aggregation factors (equivalent to the 'fact' argument to raster::aggregate representing the resolutions at which model performance should be tested
timestep	numeric value indicating the timestep of the simulated land use map. Only required if x is a Model object
categories	numeric vector of land use categories in observed maps. Only required if x is a RasterLayer
labels	character vector (optional) with labels corresponding to categories. Only required if x is a RasterLayer
...	additional arguments to raster::aggregate

Value

A ThreeMapComparison object.

References

Pontius Jr, R.G., Peethambaram, S., Castella, J.C. (2011). Comparison of three maps at multiple resolutions: a case study of land change simulation in Cho Don District, Vietnam. Annals of the Association of American Geographers 101(1): 45-62.

See Also

[AgreementBudget](#), [FigureOfMerit](#), raster::aggregate

Examples

```
## see lulcc-package examples
```

ThreeMapComparison-class

Class ThreeMapComparison

Description

An S4 class to hold results of a comparison between a reference map for time 1, a reference map for time 2 and a simulation map for time 2 using the the method described by Pontius et al. (2011).

Slots

`tables` list of data.frames that depict the three dimensional table described by Pontius et al. (2011) at different resolutions

`factors` numeric vector of aggregation factors

`maps` list of RasterStack objects containing land use maps at different resolutions

`categories` numeric vector of land use categories

`labels` character vector corresponding to categories

References

Pontius Jr, R.G., Peethambaram, S., Castella, J.C. (2011). Comparison of three maps at multiple resolutions: a case study of land change simulation in Cho Don District, Vietnam. *Annals of the Association of American Geographers* 101(1): 45-62.

<code>total</code>	<i>Total number of cells in a categorical Raster* object</i>
--------------------	--

Description

Count the number of cells belonging to each category in a Raster* object.

Usage

```
total(x, categories)
```

Arguments

<code>x</code>	Raster* object
<code>categories</code>	numeric vector containing land use categories. Only cells belonging to these categories will be counted

Value

A list containing the following components:

`total` a matrix containing the total number of cells belonging to each category. Rows represent layers in the input Raster* object

`categories` the categories included in the calculation

Examples

```
## Sibuyan Island

## load observed land use data
obs <- ObsLulcRasterStack(x=sibuyan$maps,
                          pattern="lu",
                          categories=c(1,2,3,4,5),
                          labels=c("Forest","Coconut","Grass","Rice","Other"),
                          t=c(0,14))

total(x=obs)
total(x=obs[[1]])
total(x=obs[[2]])
```


- levelplot, [36](#)
- lulcc-package, [3](#)
- Model fitting, [25](#)
- Model-class, [25](#)
- NeighbRasterStack, [11](#), [26](#)
- NeighbRasterStack, RasterLayer, ANY, NeighbRasterStack-method
(NeighbRasterStack), [26](#)
- NeighbRasterStack, RasterLayer, list, ANY-method
(NeighbRasterStack), [26](#)
- NeighbRasterStack, RasterLayer, matrix, ANY-method
(NeighbRasterStack), [26](#)
- NeighbRasterStack-class, [27](#)
- ObsLulcRasterStack, [13](#), [14](#), [20](#), [24](#), [28](#)
- ObsLulcRasterStack, character, character-method
(ObsLulcRasterStack), [28](#)
- ObsLulcRasterStack, list, character-method
(ObsLulcRasterStack), [28](#)
- ObsLulcRasterStack, missing, character-method
(ObsLulcRasterStack), [28](#)
- ObsLulcRasterStack, RasterLayer, ANY-method
(ObsLulcRasterStack), [28](#)
- ObsLulcRasterStack, RasterStack, ANY-method
(ObsLulcRasterStack), [28](#)
- ObsLulcRasterStack-class, [29](#)
- OrderedModel, [9](#), [30](#)
- OrderedModel, ObsLulcRasterStack, ExpVarRasterList, PredictiveModelList-method
(OrderedModel), [30](#)
- OrderedModel-class, [31](#)
- panel.xyplot, [38](#), [39](#)
- partition, [14](#), [24](#), [32](#)
- performance, [19](#), [33](#), [33](#), [34](#)
- performance, list-method (performance),
[33](#)
- PerformanceList, [34](#), [39](#), [41](#)
- PerformanceList-class, [34](#)
- pie, [35](#)
- plot, [35](#)
- plot, AgreementBudget, ANY-method
(plot, AgreementBudget), [36](#)
- plot, FigureOfMerit, ANY-method
(plot, FigureOfMerit), [38](#)
- plot, list, ANY-method
(plot, PerformanceList), [39](#)
- plot, Model, ANY-method (plot), [35](#)
- plot, ObsLulcRasterStack, ANY-method
(plot), [35](#)
- plot, ThreeMapComparison, ANY-method
(plot), [35](#)
- plot, AgreementBudget, [7](#), [36](#)
- plot, FigureOfMerit, [23](#), [38](#)
- plot, Model (plot), [35](#)
- plot, ObsLulcRasterStack (plot), [35](#)
- plot, PerformanceList, [39](#)
- plot, ThreeMapComparison (plot), [35](#)
- predict, PredictiveModelList-method
(predict, PredictiveModelList),
[40](#)
- predict, PredictiveModelList, [40](#)
- prediction, [18](#), [33](#), [34](#), [41](#), [42](#)
- PredictionList, [18](#), [19](#), [34](#), [41](#)
- PredictionList-class, [42](#)
- PredictiveModelList-class, [42](#)
- randomForest, [25](#)
- randomForestModels (Model fitting), [25](#)
- raster, [21](#), [28](#)
- resample, [43](#)
- resample, ExpVarRasterList, Raster-method,
[43](#)
- resample, list, Raster-method
(resample, ExpVarRasterList, Raster-method),
[43](#)
- roundSum, [44](#)
- rpart, [25](#)
- rpartModels (Model fitting), [25](#)
- show, ExpVarRasterList-method, [45](#)
- show, Model-method
(show, ExpVarRasterList-method),
[45](#)
- show, PerformanceList-method
(show, ExpVarRasterList-method),
[45](#)
- show, PredictionList-method
(show, ExpVarRasterList-method),
[45](#)
- show, PredictiveModelList-method
(show, ExpVarRasterList-method),
[45](#)
- show, ThreeMapComparison-method
(show, ExpVarRasterList-method),
[45](#)
- sibuyan, [45](#)
- stack, [21](#), [28](#), [29](#)
- subset, ExpVarRasterList-method, [46](#)
- subset, PerformanceList-method
(subset, ExpVarRasterList-method),
[46](#)
- subset, PredictionList-method
(subset, ExpVarRasterList-method),
[46](#)

subset, PredictiveModelList-method
 (subset, ExpVarRasterList-method),
 46

summary, 47

summary, ExpVarRasterList-method
 (summary), 47

summary, Model-method (summary), 47

summary, NeighbRasterStack-method
 (summary), 47

summary, ObsLulcRasterStack-method
 (summary), 47

summary, PredictiveModelList-method
 (summary), 47

ThreeMapComparison, 7, 23, 48

ThreeMapComparison, Model, ANY, ANY-method
 (ThreeMapComparison), 48

ThreeMapComparison, RasterLayer, RasterLayer, RasterLayer-method
 (ThreeMapComparison), 48

ThreeMapComparison-class, 49

total, 50

xyplot, 37–39