HL7 FHIR R4 — Chapter 4: Terminology Module — part 1 of 6 (sections 4 – 4.3.14.430)

Source: HL7 FHIR R4 (v4.0.1) specification, https://hl7.org/fhir/R4/ — text-only rendition for AI ingestion; page order follows toc.html.

4 Terminology Module

URL: https://hl7.org/fhir/R4/terminology-module.html
Work Group Vocabulary | Standards Status: Informative

4.0 Terminology Module

4.0.1 Introduction

The Terminology Module provides an overview and guide to the FHIR resources, operations, coded data types and externally-defined standard and FHIR-defined terminologies that are used for representing and communicating coded, structured data in the FHIR core specification and profiles. Collectively, these capabilities are used to provide the terminology service functionality required for supporting the use of coded data in FHIR resources throughout the specification as described in the other modules.

The primary terminology-related structures and their relationships are shown below:

Example: Condition profile with Condition.code slice bound to "SNOMED CT fracture codes" value set

[Note: The ElementDefinition type (shown with a dotted box) is described elsewhere in the specification in the Foundation and Conformance modules.]

4.0.2 Index

The Terminology Module covers the following:

Resources

CodeSystem ValueSet | ConceptMap NamingSystem | TerminologyCapabilities

Terminology Service

Terminology Service Documentation

Operations

CodeSystem $lookup $validate-code $subsumes $find-matches | ValueSet $expand $validate-code | ConceptMap $translate $closure

Coded Data Types

code | Coding | CodeableConcept

Documentation

Using Codes in Resources Code Systems Defined/Referenced in FHIR Value Sets Defined in FHIR | Mappings (FHIR-defined) Between Related Value Set Concepts Known Identifier Systems

4.0.3 Security and Privacy

For security considerations for terminology services, see the Terminology Service page Security section. For more general considerations, see the Security and Privacy module.

4.0.4 Common Use Cases

- Create or reference a code system
- Create or reference a value set
- Record data using pre-coordinated codes
- Record data using post-coordinated expressions
- Record data using multiple local or standard code systems (translations)
- Expand a value set
- Validate a code
- Look up a display term for a code
- Translate a code from one value set to another
- Maintain a client-side transitive closure table on subsumption relationships
- Test subsumption between concepts
- For a set of property/concept pairs, return the set of concepts for the requested properties
- Map data between different terminologies
- Declare the capabilities of a terminology service

4.0.5 Development Roadmap

The following terminology resources have been tested and are being used in production tooling and now are normative or are expected soon to progress to normative.

• ValueSet N

• CodeSystem N

• ConceptMap 3

Other terminology resources are still in earlier stages of development. We intend to continue to develop and test these resources and advance them through the Maturity Levels at Connectathons and elsewhere.

• NamingSystem 1

• TerminologyCapabilities 0

4.1 Using Codes in Resources

URL: https://hl7.org/fhir/R4/terminologies.html
FHIR Infrastructure Work Group | Maturity Level: Normative | Standards Status: Normative

| This page has been approved as part of an ANSI standard. See the Infrastructure Package for further details.

Many elements in the FHIR resources have a coded value: some fixed string (a sequence of characters) assigned elsewhere that identifies some defined "concept". The sequence of characters and its meaning may be defined in one of several places:

• As one of a set of fixed values defined in this specification

• In an internet RFC (e.g. mime type, language)

• An HL7 specification (HL7 v3 code system, or HL7 v2 table)

• Some external terminology or ontology such as LOINC , or SNOMED CT

• A locally maintained dictionary, look up table or enumeration in an application (for further discussion of locally defined value sets, see "Profiling FHIR"

These methods of defining codes are collectively called "code systems". This list is far from complete; there are many ways to define code systems, and they vary widely in sophistication and size.

Throughout this specification, coded values are always treated as a pair composed of "system" and "code", where the system is a URL that identifies the code system that defines the codes. Note that system values are always case sensitive. Different code systems make their own rules as to whether the codes they define are case sensitive or not. Note that all the codes defined by FHIR itself are case sensitive and SHALL be used in the provided case (usually, but not always, lowercase).

The FHIR framework for using coded values is based on the fundamental framework defined in section 5 of the HL7 v3 Core Principles document, including the separation between code systems and value sets.

The general pattern for representing coded elements is using the following four elements:

system | A URI that identifies the system (see below)
version | Identifies the version of the system (see Code System Versioning)
code | A string pattern that identifies a concept as defined by the code system
display | A description of the concept as defined by the code system

The Coding data type represents this pattern. This example shows a LOINC code with the LOINC system, the version of LOINC used for the definition, and the display assigned by LOINC:

```
{
  "system" : "http://loinc.org",
  "version" : "2.62",
  "code" : "55423-8",
  "display" : "Number of steps in unspecified time Pedometer"
}
```

When codes are carried in resources, one of several different data types is used:
code | The instance represents the code only. The system is implicit - it is defined as part of the definition of the element, and not carried in the instance.
Coding | A data type that has a code and a system element that identifies where the definition of the code comes from
CodeableConcept | A type that represents a concept by plain text and/or one or more coding elements (See the datatype notes for a discussion of code translations and using text in CodeableConcept)
In addition, the following data types also carry coded values, or content that can be treated as a code and bound to a valueset:
Quantity | The instance has system and code elements for carrying a code for the type of unit, and these can be bound to a value set
string | The instance carries a string. In some cases, applications may wish to control the set of valid strings for a particular element, so the string value can be treated as a coded element (like code)
uri | Like string, URIs can be treated as a coded element

Notes:

• Generally, the choice of data type is dictated by the resource itself. When choosing a data type for an extension, see the FHIR Confluence pages for advice about data type choice .

• See below for more information about binding the types string and uri to a value set.

4.1.1 Coded Values, Code Systems, and Value Sets

The set of coded values that is allowed in an element is known as a "value set". Anywhere these data types are used, the specification "binds" a value set to the element, and for the types code, Coding, and CodeableConcept, always does.

• Code Systems define concepts and give them meaning through formal definitions, and assign codes that represent the concepts

• Value Sets specifies a set of codes defined by code systems that can be used in a specific context

The difference between a code system and a value set is an important distinction that is easily missed by implementers, since the difference is often overlooked in system design. For instance, it's not unusual to see an application table that is a mixed list of codes, containing some LOINC codes and also some additional in-house codes. Quite often, there is no explicit differentiation between them; only the fact that a code happens to look like a LOINC code betrays its origin.

For data exchange, on the other hand, explicitly tracking the source of the code is both important and necessary. In order to do this, each code system that defines codes is assigned a URL that identifies it, and all the codes it defines are actually a pair ("Code Pair": a name with a namespace). So in the case of this mixed list example from the previous paragraph, there are two code systems: LOINC (http://loinc.org) and a local one (let's say it has been given the URL: http://example.com/codesystems/additional-test-codes). The application table is a single value set (a set of Code Pairs) that includes codes from each of those two namespaces. The value set itself is given its own URL as an identifier (e.g. "http://example.com/fhir/ValueSet/test-codes"). This identifies the set of Code Pairs, but is never used as the namespace in an actual code pair, or in an instance. In FHIR, Code Pairs are always represented as "code" and "system", except for the simple data type code where the namespace (e.g. the system element/property) is fixed in the schema and not represented explicitly.

Note that for some code systems, there is a single correct mechanism by which to represent codes defined by the system as a single URL. These single URLs are used in the context of the RDF format to enable ontological reasoning. The URL is often a direct reference to a web source that can provide additional definitional material about the concept. Where the mechanism is known, and defined by the code system, it is described in this specification.

4.1.2 Choosing a system

The URL in a system is always a reference to a code system, not to a value set. The system ensures that codes can be unambiguously traced back to their original definition, and that logical comparisons, matching and inferences can be performed consistently by different systems. For this reason, choice of the correct URI for the system attribute is critical.

The correct value to use in the system for a given code system can be determined by working through the following list, in order:

• The specification Code System Registry - if a code system is listed here, it SHALL be used

• A system URI or OID defined as the correct value to use in FHIR by the publisher of the code system

• The FHIR community code system registry - if a code system is listed here with status = active, it SHALL be used

• An OID registered in the HL7 OID registry - if a code system is registered here, the OID SHOULD be used (using the syntax urn:oid:[oid])

If a code system is not resolved by this list, and there is no publisher to consult, implementers must choose a URI to use. The priority should be to choose a unique value that won't accidentally be used by another implementer for a different purpose - or a very similar purpose with a different scope. See Registering Code Systems for further advice.

For publishers of code systems, the following considerations should be kept in mind when defining the correct URI to use:

• Once defined, the URI will require agreement from all implementers to change, and some might not be able to change (stored resources). If the set of users is not closed, it will usually not be possible to change the URI

• Implementers strongly prefer a human readable URI. http://acme.com/patients/mrn is a great deal easier to work with than urn:oid:1.2.3.4.5.6.7

• An http: address SHOULD resolve to some useful description of the code system. Ideally, if a user makes a request of the address with the media type set to a FHIR media type, the server will respond with a CodeSystem resource, but some other human or computable definition is allowed

• HTTP addresses should be permalinks which may re-direct to the current correct content

• A scope of the code system URI and the correct usage of codes and displays in its namespace SHOULD be clearly defined. See examples for SNOMED CT, RxNorm, LOINC, NDC

• Generally, allocation of URLs is hierarchical, and most care is required in choosing the Base URL. Once sub-URL policies are clearly defined, URIs can often be automatically assigned

Note: if the code system is made available packaged inside a ValueSet resource, the correct URL for the system value is ValueSet.codeSystem.system, not ValueSet.uri.

4.1.3 Complex Code Systems

All code systems define a set of concepts, assign specific codes to them, and provide definitional material to guide implementers in the correct use and understanding of the codes. Many code systems define relationships between the different concepts - is-a, part-of, classifies-with, and many other relationships. These features are represented in the CodeSystem resource, and exchanged using one of the code data types described above.

Some code systems define rules for how complex expressions can be built using the basic concepts defined by the code system. This is sometimes referred to as "post-coordination". Some of the more notable code systems that define grammars for expressions are:

- SNOMED CT
- UCUM
- Mime Types
- Language
- ICD-[X]

There are many others. Any expression defined by the code system is still regarded as a 'code' and represented as such.

This example shows a SNOMED CT expression:

```
{
  "system" : "http://snomed.info/sct",
  "code" : "128045006:{363698007=56459004}"
}
```

Note that there is no display defined for SNOMED CT expressions.

4.1.4 Controlling the use of Coded Values

When an element is bound to a value set, the binding has these properties:

Name | A descriptive name used when presenting information about the binding
Strength | How the binding should be understood - see below
Reference | A URL that defines the value set. Usually, this is a direct reference to a ValueSet resource, but can be a more indirect reference, where the value set is inferred
Description | A text description of the use of the codes. If there is no reference, this must be populated. When there is a reference, this can be used to make additional notes about the use and implementation of the value set

A binding is always represented using an ElementDefinition.binding.

4.1.4.1 Value Set References

There are a number of places in the specification where value sets are referenced in order to bind a coded value to a value set:

ElementDefinition.binding.valueSet | Used to bind a defined element to a value set
ConceptMap.source[x] and .target[x] | Used to indicate the scope of the mapping in the Concept Map - from one value set to another
Questionnaire.item.answerValueSet | Indicates that answers to a set of questions come from a value set
ValueSet.compose.include.valueSet | The content of a value set includes the content in the imported value set too
OperationDefinition.parameter.binding.valueSet | Used to bind a defined parameter to a value set
ValueSet Reference Extension | Indicates that a coded value was chosen from the specified value set

When referencing value sets, the reference is usually made to the definition of a value set - that is, a value set that defines what codes are in the value set. A terminology server is required to convert this definition to the actual expansion that specifies what codes are in the value set in the context of operation.

There are two types of value set references in this list, direct and logical.

4.1.4.1.1 Direct Value Set references

A direct value set reference has the type Reference, and refers directly to a ValueSet based on a URL, usually to a terminology server running a FHIR RESTful API. When accessing a value set based on this kind of reference, a system should access the URL directly (after converting a relative reference to an absolute reference according to the local context). If this process fails, the system is unable to resolve the value set and must handle the error appropriately.

Example:

```
GET fhir/Questionnaire/234

<Questionnaire>
  ...
  <question>
    <options>
      <reference value="ValueSet/234234"/>
```

```
    </options>
  </question>
  ....
</Questionnaire>
```

This specifies that the values for a questionnaire come from the ValueSet with id 234234 on the same FHIR end-point. To resolve this, the system would GET fhir/ValueSet/234234

Typically, a direct reference like this is good for in-process references, in closed or carefully managed eco-systems. In a more general context, these references tend to be fragile over time because web URLs - including RESTful API URLS - are easily reassigned. For this reason, systems are encouraged to use logical value set references.

4.1.4.1.2 Logical Value Set references

A logical value set reference has the type uri, where an absolute URI is provided that matches the one in ValueSet.url. The value set URL can - and is preferred to be - a web address that resolves directly to a fixed web address that serves as the authoritative source for that value set. Alternatively, the system can query its terminology server(s) to resolve a value set with that URL as its identity.

Example:

```
<StructureDefinition>
  ...
  <element>
    ...
    <binding>
      ...
      <valueSet value="http://hl7.org/fhir/ValueSet/clinical-findings"/>
    </binding>
    ...
  </element>
  ....
</StructureDefinition>
```

This specifies that the element is bound to the value set with a ValueSet.url of http://hl7.org/fhir/ValueSet/clinical-findings . One way to access this value set is to try GET http://hl7.org/fhir/ValueSet/clinical-findings - which works, for this value set - http://hl7.org/fhir/ValueSet/clinical-findings returns the authoritative value set for this URL.

Alternatively, the value set could be resolved using a local terminology server. If that's running a FHIR Terminology Server, then this would work like this:

```
GET fhir/ValueSet?url=http://hl7.org/fhir/ValueSet/clinical-findings
```

if the terminology server knows the value set, then it will return the value set. If the URL doesn't resolve to an authoritative value set, and the terminology server(s) don't know the value set, the system is unable to resolve the value set and must handle the error appropriately.

The value set URL is allowed to be a URI such as a UUID (e.g. urn:uuid:c0e0d027-1250-4278-8f44-33a49dc67916). These value sets can never be accessed directly, and must come from a terminology server. Note that this specification defines many value sets that have a logical URL that is not resolvable (examples for SNOMED CT, RxNorm, LOINC)

Using a logical reference which is a direct reference to the authoritative value set is the easiest and most reliable approach. However, this requires suitable hosting arrangements, and cannot always be guaranteed, so it is not required.

Version specific Logical References

A value set has a two-part identifier: a url, and a version. Some value sets only ever have a single 'version'; a revision of the value set contents will cause a new url to be assigned. Others, however, maintain the same URL, and change the version. A terminology server may have multiple value sets for the same ValueSet.url with different versions.

To be precise about which version of a value set is being referred to in a value set reference, append the version to the canonical URL with a '|' like this:

```
<valueSet value="http://hl7.org/fhir/ValueSet/clinical-findings|0.8"/>
```

This is a version specific reference to a value set. Searching for this on a terminology server would look like this:

```
GET fhir/ValueSet?url=http://hl7.org/fhir/ValueSet/clinical-findings&version=0.8
```

Note that if a value set reference does not have a version, and the server finds multiple versions for the value set, the system using the value set should pick the latest version of the value set and use that. Note that this applies to all conformance resources.

4.1.4.1.3 Unbound

Note that as a matter of ongoing development, a few elements that have coded data types are not bound to any value set at all. Bindings are to be provided for these elements.

4.1.5 Binding Strengths

Almost all the elements that have a coded data type are bound to a value set. The bindings are associated with various degrees of flexibility as to how closely the value set should be followed:

required | To be conformant, the concept in this element SHALL be from the specified value set.
extensible | To be conformant, the concept in this element SHALL be from the specified value set if any of the codes within the value set can apply to the concept being communicated. If the value set does not cover the concept (based on human review), alternate codings (or, data type allowing, text) may be included instead.
preferred | Instances are encouraged to draw from the specified codes for interoperability purposes but are not required to do so to be considered conformant.
example | Instances are not expected or even encouraged to draw from the specified value set. The value set merely provides examples of the types of concepts intended to be included.

The precise conformance criteria for 'required' and 'extensible' binding strengths vary by the data type to which they are applied, as described in the paragraphs below.

Irrespective of the binding strength, when a StructureDefinition is used to describe local usage, it can bind the element to a different value set in order to be much more precise about exactly which coded values can be used for these elements, and/or increase the strength of the binding. There are different rules for this, depending on the binding strength, as discussed below. Generally it is expected that jurisdictions, projects and vendors will work together to choose actual working value sets.

4.1.5.1 Required

To be conformant, codes in this element SHALL be from the specified value set.

In the standard, this is generally used for elements where the value needs to be strictly controlled so that everyone can interpret it with confidence. Generally, this is used for elements with type code:

• the element is bound to a value set that contains a list of distinct codes with a specified system (and version, where required)

• the element is bound to some external standard that defines the set of valid codes that can be used (typical examples are Mime Types , Language Codes , UCUM , etc.)

The other place where this is used is when profiling resources, and there is agreement within a context of use that a specified set of codes are the only ones that can be used. In these cases, the data type SHALL contain one of the values in the value set.

The following rules apply when required bindings are used with the CodeableConcept data type:

• at least one Coding element SHALL be present

• one of the Coding values SHALL be from the specified value set

• text can be provided as well, and is always recommended, but is not an acceptable substitute for the required code

If a required binding is applied to an element with maximum cardinality > 1, the binding applies to all the elements.

The following rules apply when required bindings are used with the code data type:

• Where the value set is defined by FHIR, the list of allowed codes will be fixed in the XML schema

• Comparison between codes is always case sensitive unless the codes are selected by reference (e.g. ValueSet.compose), and the referenced specification clearly states otherwise

• The list of codes that can be used can only be extended in subsequent releases of the FHIR specification

When an element is bound to a required value set, derived profiles may state rules on which codes can be used, including removing codes from allowed use, but cannot specify new or additional codes for these elements.

4.1.5.2 Extensible

To be conformant, codes in this element SHALL be from the specified value set if any of the codes within the value set can apply to the concept being communicated.

Note that it is the value set binding that is extensible, not the value set itself.

If there is no applicable concept in value set (based on human review), an alternate concept (either system/code pair, or text) may be used instead. The alternate concept can have any level of specificity in an is-a hierarchy (see Condition instance #2).

If there is at least one applicable concept in the extensibly-bound value set with a meaning which includes but is more general than the meaning that is intended to be represented by the element in the resource instance, then the code that is used in the instance SHALL be taken from the value set and should be the closest available match for the intended element instance meaning (i.e. neither more general or more specific). However, a more specific code that more completely represents the intended meaning may also be included in the instance as an additional Coding if the data type is CodeableConcept, but it cannot be used instead of the code from the value set. This helps ensure that systems know which codes they should expect to receive and build logic for and it facilitates interoperability.

When a code for an applicable concept in the extensibly-bound value set is used it should always be the closest available match for the intended element instance meaning, regardless of hierarchical (i.e. "is-a")

relationships in the underlying code system(s) or hierarchical "level" of the concept. However, as noted above, a code for a concept that is outside of the extensibly-bound value set with a meaning which is "covered by" (i.e. is more specific than or has an "is-a" relationship to) a concept that is included in the value set cannot be used. In that case a code for a concept that is in the extensibly-bound value set SHALL be used in the element instance and it should be the code for the concept that most closely matches the intended element instance meaning.

If the data type is CodeableConcept, then, as noted above, one of the Coding values SHALL be from the specified extensibly-bound value set if a code in that value set applies, but if no applicable code exists in the value set alternate code(s) from outside the value set may be used instead. If no codes, including local codes, are available, then text alone (in CodeableConcept.text) may be used.

If the data type is Coding, then the code/system SHALL be from the specified value set if a code applies, but if no suitable code exists in the value set, an alternate code may be provided in its place.

If an extensible binding is applied to an element with maximum cardinality > 1, the binding applies to all the elements.

Identified gaps in value sets should be submitted to the organization administering the value set in order to improve interoperability in the future.

Extensible bindings are used when there is consensus at the specification or profiling level about the coded values that should be used, but it is impossible to create a bounded list of codes that are known to cover all use cases, including ones that are yet to arise.

When an element is extensibly-bound to a value set, derived profiles may state rules on which codes can be used, but cannot select new or additional codes for these elements unless no codes with appropriate meanings are found in the base value set.

Note that if the valueset-reference extension is being used and the code in the element instance is from outside the extensibly-bound value set, the extension must reference a different value set that the code was chosen from (or if no other value set reference is available the extension cannot be used in that instance).

4.1.5.2.1 Examples for Extensible Bindings

See examples to help explain the difficult but important subject of Extensible bindings.

4.1.5.3 Preferred

Instances are encouraged to draw from the specified codes for interoperability purposes but are not required to do so to be considered conformant.

If the data type is CodeableConcept, then one of the Coding values SHOULD be from the specified value set, but another code and/or text can be used in its place.

Preferred bindings are used when there is consensus at the specification level about the coded values that are the best to be used, but there is recognition that some implementation contexts are unable to use the recommended codes for a variety of reasons. Applications should consider adopting the preferred value set wherever possible, as these preferred value sets are the most likely to serve interoperability purposes in the future.

When an element is bound to a preferred value set, derived profiles may bind the element to any value set they choose.

4.1.5.3.1 Examples for Preferred Bindings

See examples of how Preferred bindings work.

4.1.5.3.2 Example Bindings

Instances are not expected or even encouraged to draw from the specified value set. The value set merely provides examples of the types of concepts intended to be included.

Example bindings are used when an element has a very broad meaning (such as List.code), or there is no consensus over the correct codes to be used. For these bindings:

- Coding: the system/code values MAY be one of the codes in the value set.
- CodeableConcept: one of the coding elements MAY contain a system/code that is in the value set.

Some other coded value MAY be used, or (for a CodeableConcept), a text alternative MAY be provided. Example value sets are provided to assist implementers to understand the correct use of an element. Value sets based on code systems such as SNOMED CT that have restrictive license terms will only be used as example bindings in the base FHIR specification, though implementation guides for particular jurisdictions may adopt value sets that require licenses. In addition, well-specified realm-specific ValueSets may also be used as example bindings in the base specification.

When an element is bound to an example value set, derived profiles may bind the element to any value set they choose.

4.1.6 Other notes

• Subsequent versions of FHIR may replace example value sets with preferred bindings if enough consensus emerges in the relevant sphere.

• Bindings to value sets provided as part of the specification are always specific to the version of the value set published with the specification. The value set may be sealed by defining a simple list of enumerated codes, or it may include codes by their properties, along with a non-version specific reference to an underlying code system, in which case the list of valid concepts may change over time.

4.1.6.1 Binding String Values

In a few special cases, humans customarily use codes directly for elements that have type "string". A typical case is codes for states, and there are several places where a URI must come from a set of controlled values. An element of type string or uri can also be bound to a value set. When a string or URI is bound to a value set, the value property SHALL contain the code specified by the value set, and the system and display values are ignored.

4.1.6.2 Terminology Service

FHIR has defined a Terminology Service specification which sets requirements for systems that support the use of codes, value sets and code systems.

4.2 Terminology Binding Examples

URL: https://hl7.org/fhir/R4/terminologies-binding-examples.html
Vocabulary Work Group | Maturity Level: 0 | Standards Status: Trial Use

4.2.1 Extensible binding examples

4.2.1.1 Condition.code with Extensible binding

For example, we have a Condition.code and the applicable profile binds the code to the value set http://hl7.org/fhir/ValueSet/condition-code with an Extensible binding:

```
{
  "path": "Condition.code",
  "definition" : "Identification of the condition, problem or diagnosis."
  "binding": {
    "strength": "extensible",
    "valueSetCanonical": "http://hl7.org/fhir/ValueSet/condition-code"
  }
}
```

This value set includes all SNOMED CT concepts that are clinical findings.

4.2.1.2 Condition instance #1

```
{
  "resourceType": "Condition",
  "code": {
    "coding": [
      {
        "system": "http://snomed.info/sct",
        "code": "39065001",
        "display": "Burn of ear"
      }
    ],
    "text": "Burnt Ear"
  },
  "subject": {
    "reference": "Patient/example"
  }
}
```

This concept (code = 39065001) is included in the value set so the instance is valid.

4.2.1.3 Condition instance #2

```
{
  "resourceType": "Condition",
  "code": {
    "coding": [
      {
        "system": "http://snomed.info/sct",
        "code": "312824007",
        "display": "Family history of cancer of colon"
      }
    ]
  },
  "subject": {
    "reference": "Patient/example"
  }
}
```

This SNOMED CT concept is not a clinical finding. So is it valid? With the extensible binding 2 questions must be answered:

• Is there an applicable code in the bound value set (condition-code) for ‘family history of cancer of colon’? That doesn’t appear to be the case, so the instance is valid in that respect.

• Does this code fit into the definition of the element in the profile: “Identification of the condition, problem or diagnosis.”? That also appears likely to be the case. But that isn’t entirely clear, which is the challenge of extensible bindings.

So this example is most likely valid (based on human review).

4.2.1.4 Condition instance #3

```
{
  "resourceType": "Condition",
  "code": {
    "coding": [
      {
        "system": "http://my-local-organization.com",
        "code": "XYZ123",
        "display": "Severe pneumococcal pneumonia"
      }
    ]
  },
  "subject": {
    "reference": "Patient/example"
  }
}
```

This Condition instance contains a local code. Is it a valid instance? With the extensible binding, the same questions as before have to be answered:

• Is there an applicable code in the bound value set (condition-code) for ‘Severe pneumococcal pneumonia’? In this case SNOMED CT does have the code 233607000 for ‘Pneumococcal pneumonia’. Since ‘Pneumococcal pneumonia’ is a more general meaning which "covers" (i.e. includes or subsumes) ‘Severe pneumococcal pneumonia’, this Condition instance is not valid and the SNOMED CT code 233607000 for ‘Pneumococcal pneumonia’ SHALL be used instead.

• Does this code fit into the definition of the element in the profile: “Identification of the condition, problem or diagnosis.”? Yes, it does. But since it was already determined that there is an applicable code in the bound value set that should be used instead, this instance is not valid.

4.2.1.5 Condition instance #4

What if we would like to send our local code for ‘Severe pneumococcal pneumonia’ in the instance along with the SNOMED CT code 233607000 for ‘Pneumococcal pneumonia’? Because the data type for Condition.code is CodeableConcept, we can do that using an additional Coding (as a translation):

```
{
  "resourceType": "Condition",
  "code": {
    "coding": [
      {
        "system": "http://snomed.info/sct",
        "code": "233607000",
        "display": "Pneumococcal pneumonia"
      },
      {
        "system": "http://my-local-organization.com",
        "code": "XYZ123",
        "display": "Severe pneumococcal pneumonia"
      }
    ]
  },
  "subject": {
    "reference": "Patient/example"
  }
}
```

So this is a valid Condition instance which contains both the applicable SNOMED CT code from the extensibly bound condition-code value set for ‘Pneumococcal pneumonia’ as well as my organization's local code for ‘Severe pneumococcal pneumonia’.

4.2.2 Preferred binding examples

The choice of code with a Preferred binding is considerably simpler than for an Extensional binding, because the Preferred binding is a suggestion from the developers of the resource or profile about which codes they believe would be best to use to represent this data. However, in a particular instance you are free to choose to follow that suggestion or not, depending on your particular desires and needs, and there are no specific conformance expectations regarding that choice.

So in this case we have a Condition.code and the applicable profile binds the code to the value set http://hl7.org/fhir/ValueSet/condition-code with a Preferred binding:

4.2.2.1 Condition.code with Preferred binding

```
{
```

```
  "path": "Condition.code",
  "definition" : "Identification of the condition, problem or diagnosis."
  "binding": {
    "strength": "preferred",
    "valueSetCanonical": "http://hl7.org/fhir/ValueSet/condition-code"
  }
}
```

With the Preferred binding all of the following instances (and many other possibilities) are valid instances of the Condition resource:

4.2.2.2 Condition instance #5

```
{
  "resourceType": "Condition",
  "code": {
    "coding": [
      {
        "system": "http://snomed.info/sct",
        "code": "39065001",
        "display": "Burn of ear"
      }
    ],
    "text": "Burnt Ear"
  },
  "subject": {
    "reference": "Patient/example"
  }
}
```

4.2.2.3 Condition instance #6

```
{
  "resourceType": "Condition",
  "code": {
    "coding": [
      {
        "system": "http://snomed.info/sct",
        "code": "312824007",
        "display": "Family history of cancer of colon"
      }
    ]
  },
  "subject": {
    "reference": "Patient/example"
  }
}
```

4.2.2.4 Condition instance #7

```
{
  "resourceType": "Condition",
  "code": {
    "coding": [
      {
        "system": "http://my-local-organization.com",
        "code": "XYZ123",
        "display": "Severe pneumococcal pneumonia"
      }
    ]
  },
  "subject": {
    "reference": "Patient/example"
  }
}
```

4.2.2.5 Condition instance #8

```
{
  "resourceType": "Condition",
  "code": {
    "coding": [
      {
        "system": "http://snomed.info/sct",
        "code": "233607000",
        "display": "Pneumococcal pneumonia"
      },
      {
        "system": "http://my-local-organization.com",
        "code": "XYZ123",
        "display": "Severe pneumococcal pneumonia"
      }
    ]
  },
  "subject": {
    "reference": "Patient/example"
  }
}
```

4.3 Code Systems

URL: https://hl7.org/fhir/R4/terminologies-systems.html

4.3.0 Code Systems

Vocabulary Work Group | Maturity Level: 3 | Standards Status: Trial Use

The following names (URIs) may be used in the system element of the Coding data type. If a URI is defined here, it SHALL be used in preference to any other identifying mechanisms. If a code system is not listed here, the correct URI may be determined by working through the following list, in order:

• the HL7 OID Registry

• the documentation associated with the code system

• consulting the owner of the code system

• asking on the HL7 vocabulary mailing list

See also the list of known identifier systems that can be used in the system element of the Identifier data type. Additional identifier systems may be registered on the HL7 FHIR registry at http://hl7.org/fhir/registry .

Important Notes:

• This list of names is incomplete and subject to change. Some values may be dropped, and others will likely be added in the coming months as HL7 institutes formal processes around URIs in vocabulary

• Note that some of the URNs in this list follow the URN specification in RFC 5141 for referring to standards published by ISO, such as urn:iso:std:iso:11073:10101. Where ISO standards define codes with meanings, and there is no entry in the list above, and they are not registered in the HL7 OID registry, the default URN for the code system is that defined by the RFC 5141.

• For several of the code systems in this list, multiple systems are given. This means that the variants identified are different code systems, not just variants of the same code system

• Any URL in http://example.org is reserved for testing and documentation purposes.

Note that the code systems are available as FHIR resources - see the Downloads Page (as part of the FHIR definitions) (excluding the External code systems.

UMLS Note: The UMLS includes many code systems that do not have an entry in the table below, or in the HL7 OID registry, or on http://registry.fhir.org. Until these code systems are registered, implementers may use the pattern http://www.nlm.nih.gov/research/umls/[SAB], where [SAB] is the lowercase of abbreviation of the code system as provided by UMLS. e.g. The system for "Multum MediSource Lexicon" would then be http://www.nlm.nih.gov/research/umls/mmsl. Implementers choosing to use this pattern should be aware that very often, when the code system is registered, it will use a different system.

Don't see what you're looking here? See Registering Code Systems for further advice.

• External

• Internal (FHIR)

• External (FHIR)

• HL7 v3

• HL7 v2

URI | Source | Comment | OID (for non-FHIR systems)
Externally Published code systems
http://snomed.info/sct | SNOMED CT (IHTSDO) | See Using SNOMED CT with FHIR | 2.16.840.1.113883.6.96
http://www.nlm.nih.gov/research/umls/rxnorm | RxNorm (US NLM) | See Using RxNorm with FHIR | 2.16.840.1.113883.6.88
http://loinc.org | LOINC (LOINC.org) | See Using LOINC with FHIR | 2.16.840.1.113883.6.1
http://unitsofmeasure.org | UCUM: (UnitsOfMeasure.org) Case Sensitive Codes | See Using UCUM with FHIR | 2.16.840.1.113883.6.8
http://ncimeta.nci.nih.gov | NCI Metathesaurus | See Using NCI Metathesaurus with FHIR | 2.16.840.1.113883.3.26.1.2
http://www.ama-assn.org/go/cpt | AMA CPT codes | See Using CPT with FHIR | 2.16.840.1.113883.6.12
http://hl7.org/fhir/ndfrt | NDF-RT (National Drug File – Reference Terminology) | See Using NDF-RT with FHIR | 2.16.840.1.113883.6.209
http://fdasis.nlm.nih.gov | Unique Ingredient Identifier (UNII) | See Using UNII with FHIR | 2.16.840.1.113883.4.9
http://hl7.org/fhir/sid/ndc | NDC/NHRIC Codes | See Using NDC with FHIR | 2.16.840.1.113883.6.69
http://hl7.org/fhir/sid/cvx | CVX (Vaccine Administered) | See Using CVX with FHIR | 2.16.840.1.113883.12.292
urn:iso:std:iso:3166 | ISO Country & Regional Codes | See Using ISO 3166 Codes with FHIR | 1.0.3166.1.2.2
http://hl7.org/fhir/sid/dsm5 | DSM-5 | Diagnostic and Statistical Manual of Mental Disorders, Fifth Edition (DSM-5) | 2.16.840.1.113883.6.344
http://www.nubc.org/patient-discharge | NUBC code system for Patient Discharge Status | National Uniform Billing Committee, manual UB-04, UB form locator 17 | 2.16.840.1.113883.6.301.5
http://www.radlex.org | RadLex | (Includes play book codes) | 2.16.840.1.113883.6.256
ICD-9, ICD-10 | WHO) & National Variants | See Using ICD-[x] with FHIR | See ICD page for details
http://hl7.org/fhir/sid/icpc-1 http://hl7.org/fhir/sid/icpc-1-nl http://hl7.org/fhir/sid/icpc-2 | ICPC (International Classification of Primary Care) (PH3C) | NHG Table 24 ICPC-1 (NL) | 2.16.840.1.113883.2.4.4.31.1 2.16.840.1.113883.6.139
http://hl7.org/fhir/sid/icf-nl | ICF (International Classification of Functioning, Disability and Health) (WHO) | | 2.16.840.1.113883.6.254
http://terminology.hl7.org/CodeSystem/v2-[X](/v) | Version 2 tables | [X] is the 4 digit identifier for a table; e.g. http://terminology.hl7.org/CodeSystem/v2-0203 Note: only some tables may be treated in this fashion. For some tables, the

meaning of the code is version dependent, and so additional information must be included in the namespace, e.g. http://terminology.hl7.org/CodeSystem/v2-0123/2.3+, as defined in the v2 table namespace list. Version 2 codes are case sensitive. | 2.16.840.1.113883.12.[X]

http://terminology.hl7.org/CodeSystem/v3-[X] | A HL7 v3 code system | [X] is the code system name; e.g. http://terminology.hl7.org/CodeSystem/v3-GenderStatus. HL7 v3 code systems are case sensitive. | see v3 list

https://www.gs1.org/gtin | GTIN (GS1) | Note: GTINs may be used in both Codes and Identifiers | 1.3.160

http://www.whocc.no/atc | Anatomical Therapeutic Chemical Classification System (WHO) | | 2.16.840.1.113883.6.73

urn:ietf:bcp:47 | IETF language (see Tags for Identifying Languages - BCP 47) | This is used for identifying language throughout FHIR. Note that usually these codes are in a code and the system is assumed

urn:ietf:bcp:13 | Mime Types (see Multipurpose Internet Mail Extensions (MIME) Part Four - BCP 13) | This is used for identifying the mime type system throughout FHIR. Note that these codes are in a code (e.g. Attachment.contentType and in these elements the system is assumed). This system is defined for when constructing value sets of mime type codes

urn:iso:std:iso:11073:10101 | Medical Device Codes (ISO 11073-10101) | See Using MDC Codes with FHIR | 2.16.840.1.113883.6.24

http://dicom.nema.org/resources/ontology/DCM | DICOM Code Definitions | The meanings of codes defined in DICOM, either explicitly or by reference to another part of DICOM or an external reference document or standard | 1.2.840.10008.2.16.4

http://hl7.org/fhir/NamingSystem/ca-hc-din | Health Canada Drug Identification Number | A computer-generated eight-digit number assigned by Health Canada to a drug product prior to being marketed in Canada. Canada Health Drug Product Database contains product specific information on drugs approved for use in Canada. | 2.16.840.1.113883.5.1105

http://hl7.org/fhir/sid/ca-hc-npn | Health Canada Natural Product Number | A computer-generated number assigned by Health Canada to a natural health product prior to being marketed in Canada. | 2.16.840.1.113883.5.1105

http://nucc.org/provider-taxonomy | NUCC Provider Taxonomy | The Health Care Provider Taxonomy code is a unique alphanumeric code, ten characters in length. The code set is structured into three distinct "Levels" including Provider Type, Classification, and Area of Specialization. Copyright statement for NUCC value sets: This value set includes content from NUCC Health Care Provider Taxonomy Code Set for providers which is copyright © 2016+ American Medical Association. For commercial use, including sales or licensing, a license must be obtained | 2.16.840.1.113883.6.101

Code Systems for Genetics

http://www.genenames.org | HGNC: Human Gene Nomenclature Committee | | 2.16.840.1.113883.6.281

http://www.ensembl.org | ENSEMBL reference sequence identifiers | Maintained jointly by the European Bioinformatics Institute and Welcome Trust Sanger Institute | not assigned yet

http://www.ncbi.nlm.nih.gov/refseq | RefSeq: National Center for Biotechnology Information (NCBI) Reference Sequences | | 2.16.840.1.113883.6.280

http://www.ncbi.nlm.nih.gov/clinvar | ClinVar Variant ID | NCBI central repository for curating pathogenicity of potentially clinically relevant variants | not assigned yet

http://sequenceontology.org | Sequence Ontology | | not assigned yet

http://varnomen.hgvs.org | HGVS : Human Genome Variation Society | | 2.16.840.1.113883.6.282

http://www.ncbi.nlm.nih.gov/projects/SNP | DBSNP : Single Nucleotide Polymorphism database | | 2.16.840.1.113883.6.284

http://cancer.sanger.ac.uk/ cancergenome/projects/cosmic | COSMIC : Catalogue Of Somatic Mutations In Cancer | | 2.16.840.1.113883.3.912

http://www.lrg-sequence.org | LRG : Locus Reference Genomic Sequences | | 2.16.840.1.113883.6.283

http://www.omim.org | OMIM : Online Mendelian Inheritance in Man | | 2.16.840.1.113883.6.174

http://www.ncbi.nlm.nih.gov/pubmed | PubMed | | 2.16.840.1.113883.13.191

http://www.pharmgkb.org | PHARMGKB : Pharmacogenomic Knowledge Base | PharmGKB Accession ID | 2.16.840.1.113883.3.913

http://clinicaltrials.gov | ClinicalTrials.gov | | 2.16.840.1.113883.3.1077

http://www.ebi.ac.uk/ipd/imgt/hla | European Bioinformatics Institute | | 2.16.840.1.113883.6.341

URI (all prefixed with http://hl7.org/fhir/) | Description | OID

ACMECholCodesBlood | ACME Codes for Cholesterol in Serum/Plasma: This is an example code system that includes all the ACME codes for serum/plasma cholesterol from v2.36.

CholCodeLegacyStatus

CholCodeLegacyStatus

ACMECholCodesBlood | ACME Codes for Cholesterol in Serum/Plasma: This is an example code system that includes all the ACME codes for serum/plasma cholesterol from v2.36.

Medication Status Codes | Medication status codes: Medication Status Codes | 2.16.840.1.113883.4.642.4.1379

Medication Status Codes | Medication status codes: Medication Status Codes | 2.16.840.1.113883.4.642.4.1380

medicationRequest Intent | Medication request intent: MedicationRequest Intent Codes | 2.16.840.1.113883.4.642.4.1378

medicationrequest Status | Medicationrequest status: MedicationRequest Status Codes | 2.16.840.1.113883.4.642.4.1377

status | Status: The validation status of the target | 2.16.840.1.113883.4.642.1.885

Code system summary example for ACME body sites | This is an example code system summary for the ACME codes for body site.

Code system summary example for ACME body sites | This is an example code system summary for the ACME codes for body site.

TaskCode | Task Codes: Codes indicating the type of action that is expected to be performed | 2.16.840.1.113883.4.642.4.1397

FHIRVersion N | FHIRVersion: All published FHIR Versions. | 2.16.840.1.113883.4.642.4.1310

AbstractType N | AbstractType: A list of the base types defined by this version of the FHIR specification - types that are defined, but for which only specializations actually are created.

AccountStatus | AccountStatus: Indicates whether the account is available to be used. | 2.16.840.1.113883.4.642.4.727

ActionCardinalityBehavior | ActionCardinalityBehavior: Defines behavior for an action or a group for how many times that item may be repeated. | 2.16.840.1.113883.4.642.4.808

ActionConditionKind | ActionConditionKind: Defines the kinds of conditions that can appear on actions. | 2.16.840.1.113883.4.642.4.816

ActionGroupingBehavior | ActionGroupingBehavior: Defines organization behavior of a group. | 2.16.840.1.113883.4.642.4.800

ActionParticipantType | ActionParticipantType: The type of participant for the action. | 2.16.840.1.113883.4.642.4.812

ActionPrecheckBehavior | ActionPrecheckBehavior: Defines selection frequency behavior for an action or group. | 2.16.840.1.113883.4.642.4.806

ActionRelationshipType | ActionRelationshipType: Defines the types of relationships between actions. | 2.16.840.1.113883.4.642.4.814

ActionRequiredBehavior | ActionRequiredBehavior: Defines expectations around whether an action or action group is required. | 2.16.840.1.113883.4.642.4.804
ActionSelectionBehavior | ActionSelectionBehavior: Defines selection behavior of a group. | 2.16.840.1.113883.4.642.4.802
AdditionalMaterialCodes | Additional Material Codes: This value set includes sample additional material type codes. | 2.16.840.1.113883.4.642.4.530
AddressType N | AddressType: The type of an address (physical / postal). | 2.16.840.1.113883.4.642.4.70
AddressUse N | AddressUse: The use of an address. | 2.16.840.1.113883.4.642.4.68
AdministrativeGender N | AdministrativeGender: The gender of a person used for administrative purposes. | 2.16.840.1.113883.4.642.4.2
AdverseEventActuality | AdverseEventActuality: Overall nature of the adverse event, e.g. real or potential. | 2.16.840.1.113883.4.642.4.832
AllergyIntoleranceCategory | AllergyIntoleranceCategory: Category of an identified substance associated with allergies or intolerances. | 2.16.840.1.113883.4.642.4.134
AllergyIntoleranceCriticality | AllergyIntoleranceCriticality: Estimate of the potential clinical harm, or seriousness, of a reaction to an identified substance. | 2.16.840.1.113883.4.642.4.130
AllergyIntoleranceType | AllergyIntoleranceType: Identification of the underlying physiological mechanism for a Reaction Risk. | 2.16.840.1.113883.4.642.4.132
GenderStatus | Gender status: This example value set defines a set of codes that can be used to indicate the current state of the animal's reproductive organs. | 2.16.840.1.113883.4.642.4.419
AnimalSpecies | Animal species: This example value set defines a set of codes that can be used to indicate species of animal patients. | 2.16.840.1.113883.4.642.4.421
AppointmentStatus | AppointmentStatus: The free/busy status of an appointment. | 2.16.840.1.113883.4.642.4.485
AssertionDirectionType | AssertionDirectionType: The type of direction to use for assertion. | 2.16.840.1.113883.4.642.4.707
AssertionOperatorType | AssertionOperatorType: The type of operator to use for assertion. | 2.16.840.1.113883.4.642.4.709
AssertionResponseTypes | AssertionResponseTypes: The type of response code to use for assertion. | 2.16.840.1.113883.4.642.4.711
ContractResourceAssetAvailiabilityCodes | Contract Resource Asset Availiability codes: This value set has asset availability codes. | 2.16.840.1.113883.4.642.4.1296
AuditEventAction | AuditEventAction: Indicator for type of action performed during the event that generated the event. | 2.16.840.1.113883.4.642.4.453
AuditEventOutcome | AuditEventOutcome: Indicates whether the event succeeded or failed. | 2.16.840.1.113883.4.642.4.455
BindingStrength N | BindingStrength: Indication of the degree of conformance expectations associated with a binding. | 2.16.840.1.113883.4.642.4.44
BundleType N | BundleType: Indicates the purpose of a bundle - how it is intended to be used. | 2.16.840.1.113883.4.642.4.621
CapabilityStatementKind N | CapabilityStatementKind: How a capability statement is intended to be used. | 2.16.840.1.113883.4.642.4.199
CarePlanActivityStatus | CarePlanActivityStatus: Codes that reflect the current state of a care plan activity within its overall life cycle. | 2.16.840.1.113883.4.642.4.147
CareTeamStatus | CareTeamStatus: Indicates the status of the care team. | 2.16.840.1.113883.4.642.4.154
ChargeItemStatus | ChargeItemStatus: Codes identifying the lifecycle stage of a ChargeItem. | 2.16.840.1.113883.4.642.4.847
Use | Use: The purpose of the Claim: predetermination, preauthorization, claim. | 2.16.840.1.113883.4.642.4.545
CodeSearchSupport | CodeSearchSupport: The degree to which the server supports the code search parameter on ValueSet, if it is supported. | 2.16.840.1.113883.4.642.4.861
CodeSystemContentMode N | CodeSystemContentMode: The extent of the content of the code system (the concepts and codes it defines) are represented in a code system resource. | 2.16.840.1.113883.4.642.4.783
CodeSystemHierarchyMeaning N | CodeSystemHierarchyMeaning: The meaning of the hierarchy of concepts in a code system. | 2.16.840.1.113883.4.642.4.785
CompartmentType | CompartmentType: Which type a compartment definition describes. | 2.16.840.1.113883.4.642.4.787
CompositionAttestationMode | CompositionAttestationMode: The way in which a person authenticated a composition. | 2.16.840.1.113883.4.642.4.239
CompositionStatus | CompositionStatus: The workflow/clinical status of the composition. | 2.16.840.1.113883.4.642.4.242
ConceptMapEquivalence | ConceptMapEquivalence: The degree of equivalence between concepts. | 2.16.840.1.113883.4.642.4.18
FHIR Defined Concept Properties N | A set of common concept properties for use on coded systems throughout the FHIR eco-system.
PropertyType N | PropertyType: The type of a property value. | 2.16.840.1.113883.4.642.4.781
ConceptSubsumptionOutcome | ConceptSubsumptionOutcome: The subsumption relationship between code/Coding "A" and code/Coding "B". There are 4 possible codes to be returned: equivalent, subsumes, subsumed-by, and not-subsumed. If the server is unable to determine the relationship between the codes/Codings, then it returns an error (i.e. an OperationOutcome). | 2.16.840.1.113883.4.642.4.1239
ConceptMapGroupUnmappedMode | ConceptMapGroupUnmappedMode: Defines which action to take if there is no match in the group. | 2.16.840.1.113883.4.642.4.481
ConditionalDeleteStatus N | ConditionalDeleteStatus: A code that indicates how the server supports conditional delete. | 2.16.840.1.113883.4.642.4.195
ConditionalReadStatus N | ConditionalReadStatus: A code that indicates how the server supports conditional read. | 2.16.840.1.113883.4.642.4.201
ConsentDataMeaning | ConsentDataMeaning: How a resource reference is interpreted when testing consent restrictions. | 2.16.840.1.113883.4.642.4.760
ConsentProvisionType | ConsentProvisionType: How a rule statement is applied, such as adding additional consent or removing consent. | 2.16.840.1.113883.4.642.4.758
ConsentState | ConsentState: Indicates the state of the consent. | 2.16.840.1.113883.4.642.4.756
PerformerRoleCodes | Performer Role Codes: This value set includes sample Performer Role codes. | 2.16.840.1.113883.4.642.4.1017
ConstraintSeverity N | ConstraintSeverity: SHALL applications comply with this constraint? | 2.16.840.1.113883.4.642.4.82
ContactPointSystem N | ContactPointSystem: Telecommunications form for contact point. | 2.16.840.1.113883.4.642.4.72
ContactPointUse N | ContactPointUse: Use of contact point. | 2.16.840.1.113883.4.642.4.74

ContractResourceActionStatusCodes | Contract Resource Action Status codes: This value set contract specific codes for action status. | 2.16.840.1.113883.4.642.4.1304
ContractResourceAssetContextCodes | Contract Resource Asset Context codes: This value set contract specific codes for asset context. | 2.16.840.1.113883.4.642.4.1298
ContractResourceAssetScopeCodes | Contract Resource Asset Scope codes: This value set contract specific codes for asset scope. | 2.16.840.1.113883.4.642.4.1294
ContractResourceAssetSub-TypeCodes | Contract Resource Asset Sub-Type codes: This value set contract specific codes for asset subtype. | 2.16.840.1.113883.4.642.4.1302
ContractResourceAssetTypeCodes | Contract Resource Asset Type codes: This value set contract specific codes for asset type. | 2.16.840.1.113883.4.642.4.1300
ContractResourceDecisionModeCodes | Contract Resource Decision Mode codes: This value set contract specific codes for decision modes. | 2.16.840.1.113883.4.642.4.1292
ContractResourceDefinitionSubtypeCodes | Contract Resource Definition Subtype codes: This value set contract specific codes for status. | 2.16.840.1.113883.4.642.4.1213
ContractResourceDefinitionTypeCodes | Contract Resource Definition Type codes: This value set contract specific codes for status. | 2.16.840.1.113883.4.642.4.1211
ContractResourceExpirationTypeCodes | Contract Resource Expiration Type codes: This value set contract specific codes for status. | 2.16.840.1.113883.4.642.4.1215
ContractResourceLegalStateCodes | Contract Resource Legal State codes: This value set contract specific codes for status. | 2.16.840.1.113883.4.642.4.1207
ContractResourcePartyRoleCodes | Contract Resource Party Role codes: This value set contract specific codes for offer party participation. | 2.16.840.1.113883.4.642.4.1225
ContractResourcePublicationStatusCodes | Contract Resource Publication Status codes: This value set contract specific codes for status. | 2.16.840.1.113883.4.642.4.1209
ContractResourceScopeCodes | Contract Resource Scope codes: This value set contract specific codes for scope. | 2.16.840.1.113883.4.642.4.1217
ContractResourceScopeCodes | Contract Resource Scope codes: This value set contract specific codes for security category. | 2.16.840.1.113883.4.642.4.1221
ContractResourceScopeCodes | Contract Resource Scope codes: This value set contract specific codes for security classification. | 2.16.840.1.113883.4.642.4.1219
ContractResourceSecurityControlCodes | Contract Resource Security Control codes: This value set contract specific codes for security control. | 2.16.840.1.113883.4.642.4.1223
ContractResourceStatusCodes | Contract Resource Status Codes: This value set contract specific codes for status. | 2.16.840.1.113883.4.642.4.744
ContributorType | ContributorType: The type of contributor. | 2.16.840.1.113883.4.642.4.94
DataType N | DataType: A version specific list of the data types defined by the FHIR specification for use as an element type (any of the FHIR defined data types).
DaysOfWeek N | DaysOfWeek: The days of the week. | 2.16.840.1.113883.4.642.4.513
DefinitionResourceType | DefinitionResourceType: A list of all the definition resource types defined in this version of the FHIR specification. | 2.16.840.1.113883.4.642.4.1057
DetectedIssueSeverity | DetectedIssueSeverity: Indicates the potential degree of impact of the identified issue on the patient. | 2.16.840.1.113883.4.642.4.207
ProcedureDeviceActionCodes | Procedure Device Action Codes: Example codes indicating the change that happened to the device during the procedure. Note that these are in no way complete and might not even be appropriate for some uses. | 2.16.840.1.113883.4.642.4.426
FHIRDeviceStatus | FHIRDeviceStatus: Codes representing the current status of the device - on, off, suspended, etc. | 2.16.840.1.113883.4.642.4.1308
DeviceNameType | DeviceNameType: The type of name the device is referred by. | 2.16.840.1.113883.4.642.4.1084
DeviceUseStatementStatus | DeviceUseStatementStatus: A coded concept indicating the current status of the Device Usage. | 2.16.840.1.113883.4.642.4.215
FHIRDeviceStatus | FHIRDeviceStatus: The availability status of the device. | 2.16.840.1.113883.4.642.4.210
DiagnosticReportStatus | DiagnosticReportStatus: The status of the diagnostic report. | 2.16.840.1.113883.4.642.4.236
DiscriminatorType N | DiscriminatorType: How an element value is interpreted when discrimination is evaluated. | 2.16.840.1.113883.4.642.4.92
DocumentMode N | DocumentMode: Whether the application produces or consumes documents. | 2.16.840.1.113883.4.642.4.187
DocumentReferenceStatus | DocumentReferenceStatus: The status of the document reference. | 2.16.840.1.113883.4.642.4.8
DocumentRelationshipType | DocumentRelationshipType: The type of relationship between documents. | 2.16.840.1.113883.4.642.4.245
EligibilityRequestPurpose | EligibilityRequestPurpose: A code specifying the types of information being requested. | 2.16.840.1.113883.4.642.4.1183
EligibilityResponsePurpose | EligibilityResponsePurpose: A code specifying the types of information being requested. | 2.16.840.1.113883.4.642.4.1185
EncounterLocationStatus | EncounterLocationStatus: The status of the location. | 2.16.840.1.113883.4.642.4.263
EncounterStatus | EncounterStatus: Current state of the encounter. | 2.16.840.1.113883.4.642.4.247
EndpointStatus | EndpointStatus: The status of the endpoint. | 2.16.840.1.113883.4.642.4.495
EpisodeOfCareStatus | EpisodeOfCareStatus: The status of the episode of care. | 2.16.840.1.113883.4.642.4.665
EventCapabilityMode N | EventCapabilityMode: The mode of a message capability statement. | 2.16.840.1.113883.4.642.4.183
EventResourceType | EventResourceType: A list of all the event resource types defined in this version of the FHIR specification. | 2.16.840.1.113883.4.642.4.1061
EventStatus | EventStatus: Codes identifying the lifecycle stage of an event. | 2.16.840.1.113883.4.642.4.110
EventTiming N | EventTiming: Real world event relating to the schedule. | 2.16.840.1.113883.4.642.4.76
ClaimItemTypeCodes | Claim Item Type Codes: This value set includes sample Item Type codes. | 2.16.840.1.113883.4.642.4.549
TeethCodes | Teeth Codes: This value set includes the FDI Teeth codes. | 2.16.840.1.113883.4.642.4.551
ExampleOnsetType(Reason)Codes | Example Onset Type (Reason) Codes: This value set includes example Onset Type codes which are used to identify the event for which the onset, starting date, is required. | 2.16.840.1.113883.4.642.4.579

OralProsthoMaterialTypeCodes | Oral Prostho Material type Codes: This value set includes sample Oral Prosthodontic Material type codes. | 2.16.840.1.113883.4.642.4.539
ExamplePharmacyServiceCodes | Example Pharmacy Service Codes: This value set includes a smattering of Pharmacy Service codes. | 2.16.840.1.113883.4.642.4.563
ExampleServiceModifierCodes | Example Service Modifier Codes: This value set includes sample Service Modifier codes which may support differential payment. | 2.16.840.1.113883.4.642.4.573
ExampleService/ProductCodes | Example Service/Product Codes: This value set includes a smattering of Service/Product codes. | 2.16.840.1.113883.4.642.4.561
UDICodes | UDI Codes: This value set includes sample UDI codes. | 2.16.840.1.113883.4.642.4.555
ExampleScenarioActorType | ExampleScenarioActorType: The type of actor - system or human. | 2.16.840.1.113883.4.642.4.859
ExplanationOfBenefitStatus | ExplanationOfBenefitStatus: A code specifying the state of the resource instance. | 2.16.840.1.113883.4.642.4.619
ExposureState | ExposureState: Whether the results by exposure is describing the results for the primary exposure of interest (exposure) or the alternative state (exposureAlternative). | 2.16.840.1.113883.4.642.4.1352
ExpressionLanguage | ExpressionLanguage: The media type of the expression language. | 2.16.840.1.113883.4.642.4.106
ExtensionContextType N | ExtensionContextType: How an extension context is interpreted. | 2.16.840.1.113883.4.642.4.1013
ExtraActivityType | This value set includes coded concepts not well covered in any of the included valuesets.
FeedingDeviceCodes | Feeding Device Codes: Materials used or needed to feed the patient. | 2.16.840.1.113883.4.642.4.962
FilterOperator N | FilterOperator: The kind of operation to perform as a part of a property based filter. | 2.16.840.1.113883.4.642.4.479
FlagPriorityCodes | Flag Priority Codes: This value set is provided as an exemplar. The value set is driven by IHE Table B.8-4: Abnormal Flags, Alert Priority. | 2.16.840.1.113883.4.642.4.951
FlagStatus | FlagStatus: Indicates whether this flag is active and needs to be displayed to a user, or whether it is no longer needed or was entered in error. | 2.16.840.1.113883.4.642.4.121
FMConditionCodes | FM Condition Codes: This value set includes sample Conditions codes. | 2.16.840.1.113883.4.642.4.557
FinancialResourceStatusCodes | Financial Resource Status Codes: This value set includes Status codes. | 2.16.840.1.113883.4.642.4.593
GenderIdentity | Gender identity: This example value set defines a set of codes that can be used to indicate a patient's gender identity. | 2.16.840.1.113883.4.642.4.973
GoalLifecycleStatus | GoalLifecycleStatus: Codes that reflect the current state of a goal and whether the goal is still being targeted. | 2.16.840.1.113883.4.642.4.272
GoalStatusReason | Goal status reason: Example codes indicating the reason for a current status. Note that these are in no way complete and might not even be appropriate for some uses. | 2.16.840.1.113883.4.642.4.278
GraphCompartmentRule | GraphCompartmentRule: How a compartment must be linked. | 2.16.840.1.113883.4.642.4.281
GraphCompartmentUse | GraphCompartmentUse: Defines how a compartment rule is used. | 2.16.840.1.113883.4.642.4.283
GroupMeasure | GroupMeasure: Possible group measure aggregates (E.g. Mean, Median). | 2.16.840.1.113883.4.642.4.1346
GroupType | GroupType: Types of resources that are part of group. | 2.16.840.1.113883.4.642.4.285
GuidanceResponseStatus | GuidanceResponseStatus: The status of a guidance response. | 2.16.840.1.113883.4.642.4.818
GuidePageGeneration | GuidePageGeneration: A code that indicates how the page is generated. | 2.16.840.1.113883.4.642.4.999
GuideParameterCode | GuideParameterCode: Code of parameter that is input to the guide. | 2.16.840.1.113883.4.642.4.997
FamilyHistoryStatus | FamilyHistoryStatus: A code that identifies the status of the family history record. | 2.16.840.1.113883.4.642.4.268
TestScriptRequestMethodCode | TestScriptRequestMethodCode: The allowable request method or HTTP operation codes. | 2.16.840.1.113883.4.642.4.717
HTTPVerb N | HTTPVerb: HTTP verbs (in the HTTP command line). See [HTTP rfc](https://tools.ietf.org/html/rfc7231) for details. | 2.16.840.1.113883.4.642.4.625
IdentifierUse N | IdentifierUse: Identifies the purpose for this identifier, if known . | 2.16.840.1.113883.4.642.4.58
IdentityAssuranceLevel | IdentityAssuranceLevel: The level of confidence that this link represents the same actual person, based on NIST Authentication Levels. | 2.16.840.1.113883.4.642.4.657
ImagingStudyStatus | ImagingStudyStatus: The status of the ImagingStudy. | 2.16.840.1.113883.4.642.4.991
InterventionCodes | Intervention Codes: This value set includes sample Intervention codes. | 2.16.840.1.113883.4.642.4.533
InvoicePriceComponentType | InvoicePriceComponentType: Codes indicating the kind of the price component. | 2.16.840.1.113883.4.642.4.869
InvoiceStatus | InvoiceStatus: Codes identifying the lifecycle stage of an Invoice. | 2.16.840.1.113883.4.642.4.867
IssueSeverity N | IssueSeverity: How the issue affects the success of the action. | 2.16.840.1.113883.4.642.4.409
IssueType N | IssueType: A code that describes the type of issue. | 2.16.840.1.113883.4.642.4.411
QuestionnaireItemType | QuestionnaireItemType: Distinguishes groups from questions and display text and indicates data type for questions. | 2.16.840.1.113883.4.642.4.445
KnowledgeResourceType | KnowledgeResourceType: A list of all the knowledge resource types defined in this version of the FHIR specification. | 2.16.840.1.113883.4.642.4.1063
LanguagePreferenceType | Language preference type: This value set defines the set of codes for describing the type or mode of the patient's preferred language. | 2.16.840.1.113883.4.642.4.1023
LinkType N | LinkType: The type of link between this patient resource and another patient resource. | 2.16.840.1.113883.4.642.4.424
LinkageType | LinkageType: Used to distinguish different roles a resource can play within a set of linked resources. | 2.16.840.1.113883.4.642.4.315
ListMode | ListMode: The processing mode that applies to this list. | 2.16.840.1.113883.4.642.4.319
ListStatus | ListStatus: The current state of the list. | 2.16.840.1.113883.4.642.4.327
LocationMode | LocationMode: Indicates whether a resource instance represents a specific location or a class of locations. | 2.16.840.1.113883.4.642.4.331
LocationStatus | LocationStatus: Indicates whether the location is still in use. | 2.16.840.1.113883.4.642.4.333
StructureMapContextType | StructureMapContextType: How to interpret the context. | 2.16.840.1.113883.4.642.4.680
StructureMapGroupTypeMode | StructureMapGroupTypeMode: If this is the default rule set to apply for the source type, or this combination of types. | 2.16.840.1.113883.4.642.4.688
StructureMapInputMode | StructureMapInputMode: Mode for this instance of data. | 2.16.840.1.113883.4.642.4.678

StructureMapModelMode | StructureMapModelMode: How the referenced structure is used in this mapping. | 2.16.840.1.113883.4.642.4.676
StructureMapSourceListMode | StructureMapSourceListMode: If field is a list, how to manage the source. | 2.16.840.1.113883.4.642.4.684
StructureMapTargetListMode | StructureMapTargetListMode: If field is a list, how to manage the production. | 2.16.840.1.113883.4.642.4.686
StructureMapTransform | StructureMapTransform: How data is copied/created. | 2.16.840.1.113883.4.642.4.682
MeasureReportStatus | MeasureReportStatus: The status of the measure report. | 2.16.840.1.113883.4.642.4.777
MeasureReportType | MeasureReportType: The type of the measure report. | 2.16.840.1.113883.4.642.4.779
MessageEvent | MessageEvent: One of the message events defined as part of this version of FHIR.
MessageSignificanceCategory | MessageSignificanceCategory: The impact of the content of a message. | 2.16.840.1.113883.4.642.4.189
messageheader-response-request | messageheader-response-request: HL7-defined table of codes which identify conditions under which acknowledgments are required to be returned in response to a message. | 2.16.840.1.113883.4.642.4.925
DeviceMetricCalibrationState | DeviceMetricCalibrationState: Describes the state of a metric calibration. | 2.16.840.1.113883.4.642.4.653
DeviceMetricCalibrationType | DeviceMetricCalibrationType: Describes the type of a metric calibration. | 2.16.840.1.113883.4.642.4.651
DeviceMetricCategory | DeviceMetricCategory: Describes the category of the metric. | 2.16.840.1.113883.4.642.4.649
DeviceMetricColor | DeviceMetricColor: Describes the typical color of representation. | 2.16.840.1.113883.4.642.4.655
DeviceMetricOperationalStatus | DeviceMetricOperationalStatus: Describes the operational status of the DeviceMetric. | 2.16.840.1.113883.4.642.4.647
NameUse N | NameUse: The use of a human name. | 2.16.840.1.113883.4.642.4.66
NamingSystemIdentifierType | NamingSystemIdentifierType: Identifies the style of unique identifier used to identify a namespace. | 2.16.840.1.113883.4.642.4.493
NamingSystemType | NamingSystemType: Identifies the purpose of the naming system. | 2.16.840.1.113883.4.642.4.491
NarrativeStatus | NarrativeStatus: The status of a resource narrative. | 2.16.840.1.113883.4.642.4.56
AuditEventAgentNetworkType | AuditEventAgentNetworkType: The type of network access point of this agent in the audit event. | 2.16.840.1.113883.4.642.4.457
NoteType | NoteType: The presentation types of notes. | 2.16.840.1.113883.4.642.4.16
ObservationRangeCategory | ObservationRangeCategory: Codes identifying the category of observation range. | 2.16.840.1.113883.4.642.4.1334
ObservationStatus N | ObservationStatus: Codes providing the status of an observation. | 2.16.840.1.113883.4.642.4.401
OperationKind N | OperationKind: Whether an operation is a normal operation or a query. | 2.16.840.1.113883.4.642.4.507
OperationParameterUse N | OperationParameterUse: Whether an operation parameter is an input or an output parameter. | 2.16.840.1.113883.4.642.4.509
OrganizationAffiliationRole | Organization Affiliation Role: This example value set defines a set of codes that can be used to indicate the role of one Organization in relation to another. | 2.16.840.1.113883.4.642.4.881
orientationType | orientationType: Type for orientation. | 2.16.840.1.113883.4.642.4.988
ParticipantRequired | ParticipantRequired: Is the Participant required to attend the appointment. | 2.16.840.1.113883.4.642.4.489
ParticipationStatus | ParticipationStatus: The Participation status of an appointment. | 2.16.840.1.113883.4.642.4.487
ObservationDataType | ObservationDataType: Permitted data type for observation value. | 2.16.840.1.113883.4.642.4.1332
PractitionerSpecialty | Practitioner specialty: This example value set defines a set of codes that can be used to indicate the specialty of a Practitioner. | 2.16.840.1.113883.4.642.4.442
ProcedureProgressStatusCodes | Procedure Progress Status Codes: This value set is provided as an example. The value set to instantiate this attribute should be drawn from a robust terminology code system that consists of or contains concepts to support the procedure performance process. | 2.16.840.1.113883.4.642.4.947
BiologicallyDerivedProductCategory | BiologicallyDerivedProductCategory: Biologically Derived Product Category. | 2.16.840.1.113883.4.642.4.901
BiologicallyDerivedProductStatus | BiologicallyDerivedProductStatus: Biologically Derived Product Status. | 2.16.840.1.113883.4.642.4.903
BiologicallyDerivedProductStorageScale | BiologicallyDerivedProductStorageScale: BiologicallyDerived Product Storage Scale. | 2.16.840.1.113883.4.642.4.905
PropertyRepresentation N | PropertyRepresentation: How a property is represented when serialized. | 2.16.840.1.113883.4.642.4.88
ProvenanceEntityRole | ProvenanceEntityRole: How an entity was used in an activity. | 2.16.840.1.113883.4.642.4.437
ProvenanceParticipantRole | Provenance participant role: The role that a provenance participant played | 2.16.840.1.113883.4.642.4.1306
PublicationStatus N | PublicationStatus: The lifecycle status of an artifact. | 2.16.840.1.113883.4.642.4.4
qualityType | qualityType: Type for quality report. | 2.16.840.1.113883.4.642.4.229
QuantityComparator N | QuantityComparator: How the Quantity should be understood and represented. | 2.16.840.1.113883.4.642.4.60
QuestionnaireResponseStatus | QuestionnaireResponseStatus: Lifecycle status of the questionnaire response. | 2.16.840.1.113883.4.642.4.448
QuestionnaireTextCategories | Questionnaire Text Categories: Codes defining the purpose of a Questionnaire item of type 'text'. | 2.16.840.1.113883.4.642.4.936
EnableWhenBehavior | EnableWhenBehavior: Controls how multiple enableWhen values are interpreted - whether all or any must be true. | 2.16.840.1.113883.4.642.4.1008
QuestionnaireItemOperator | QuestionnaireItemOperator: The criteria by which a question is enabled. | 2.16.840.1.113883.4.642.4.1006
QuestionnaireItemUIControlCodes | Questionnaire Item UI Control Codes: Starter set of user interface control/display mechanisms that might be used when rendering an item in a questionnaire. | 2.16.840.1.113883.4.642.4.932
AllergyIntoleranceSeverity | AllergyIntoleranceSeverity: Clinical assessment of the severity of a reaction event as a whole, potentially considering multiple different manifestations. | 2.16.840.1.113883.4.642.4.136

SNOMEDCTReasonMedicationNotGivenCodes | SNOMED CT Reason Medication Not Given Codes: This value set includes all medication refused, medication not administered, and non-administration of necessary drug or medicine codes from SNOMED CT - provided as an exemplar value set. | 2.16.840.1.113883.4.642.4.343
ReferenceHandlingPolicy N | ReferenceHandlingPolicy: A set of flags that defines how references are supported. | 2.16.840.1.113883.4.642.4.203
ReferenceVersionRules N | ReferenceVersionRules: Whether a reference needs to be version specific or version independent, or whether either can be used. | 2.16.840.1.113883.4.642.4.90
RelatedArtifactType | RelatedArtifactType: The type of relationship to the related artifact. | 2.16.840.1.113883.4.642.4.100
CatalogEntryRelationType | CatalogEntryRelationType: The type of relations between entries. | 2.16.840.1.113883.4.642.4.1029
Beneficiary Relationship Codes | This value set includes the Patient to subscriber relationship codes. | 2.16.840.1.113883.4.642.4.36
ClaimProcessingCodes | Claim Processing Codes: This value set includes Claim Processing Outcome codes. | 2.16.840.1.113883.4.642.4.14
TestReportActionResult | TestReportActionResult: The results of executing an action. | 2.16.840.1.113883.4.642.4.721
TestReportParticipantType | TestReportParticipantType: The type of participant. | 2.16.840.1.113883.4.642.4.723
TestReportResult | TestReportResult: The reported execution result. | 2.16.840.1.113883.4.642.4.719
TestReportStatus | TestReportStatus: The current status of the test report. | 2.16.840.1.113883.4.642.4.725
repositoryType | repositoryType: Type for access of external URI. | 2.16.840.1.113883.4.642.4.231
RequestIntent | RequestIntent: Codes indicating the degree of authority/intentionality associated with a request. | 2.16.840.1.113883.4.642.4.114
RequestPriority | RequestPriority: Identifies the level of importance to be assigned to actioning the request. | 2.16.840.1.113883.4.642.4.116
RequestResourceType | RequestResourceType: A list of all the request resource types defined in this version of the FHIR specification. | 2.16.840.1.113883.4.642.4.1059
RequestStatus | RequestStatus: Codes identifying the lifecycle stage of a request. | 2.16.840.1.113883.4.642.4.112
ResearchElementType | ResearchElementType: The possible types of research elements (E.g. Population, Exposure, Outcome). | 2.16.840.1.113883.4.642.4.1342
ResearchStudyStatus | ResearchStudyStatus: Codes that convey the current status of the research study. | 2.16.840.1.113883.4.642.4.820
ResearchSubjectStatus | ResearchSubjectStatus: Indicates the progression of a study subject through a study. | 2.16.840.1.113883.4.642.4.830
AggregationMode N | AggregationMode: How resource references can be aggregated. | 2.16.840.1.113883.4.642.4.86
SlicingRules N | SlicingRules: How slices are interpreted when evaluating an instance. | 2.16.840.1.113883.4.642.4.84
Canonical Status Codes for FHIR Resources | The master set of status codes used throughout FHIR. All status codes are mapped to one of these codes.
ResourceType N | ResourceType: One of the resource types defined as part of this version of FHIR.
ResourceValidationMode | ResourceValidationMode: Codes indicating the type of validation to perform. | 2.16.840.1.113883.4.642.4.119
ResponseType | ResponseType: The kind of response to a message. | 2.16.840.1.113883.4.642.4.381
RestfulCapabilityMode N | RestfulCapabilityMode: The mode of a RESTful capability statement. | 2.16.840.1.113883.4.642.4.177
FHIR Restful Interactions N | The set of interactions defined by the RESTful part of the FHIR specification.
SearchComparator | SearchComparator: What Search Comparator Codes are supported in search. | 2.16.840.1.113883.4.642.4.638
SearchEntryMode N | SearchEntryMode: Why an entry is in the result set - whether it's included as a match or because of an _include requirement, or to convey information or warning information about the search process. | 2.16.840.1.113883.4.642.4.623
SearchModifierCode | SearchModifierCode: A supported modifier for a search parameter. | 2.16.840.1.113883.4.642.4.640
SearchParamType N | SearchParamType: Data types allowed to be used for search parameters. | 2.16.840.1.113883.4.642.4.12
XPathUsageType | XPathUsageType: How a search parameter relates to the set of elements returned by evaluating its xpath query. | 2.16.840.1.113883.4.642.4.636
ObservationCategoryCodes | Observation Category Codes: Codes to denote a guideline or policy statement.when a genetic test result is being shared as a secondary finding. | 2.16.840.1.113883.4.642.4.1286
sequenceType | sequenceType: Type if a sequence -- DNA, RNA, or amino acid sequence. | 2.16.840.1.113883.4.642.4.220
ICD-10ProcedureCodes | ICD-10 Procedure Codes: This value set includes sample ICD-10 Procedure codes. | 2.16.840.1.113883.4.642.4.575
SlotStatus | SlotStatus: The free/busy status of the slot. | 2.16.840.1.113883.4.642.4.483
SortDirection | SortDirection: The possible sort directions, ascending or descending. | 2.16.840.1.113883.4.642.4.980
SPDXLicense | SPDXLicense: The license that applies to an Implementation Guide (using an SPDX license Identifiers, or 'not-open-source'). The binding is required but new SPDX license Identifiers are allowed to be used (https://spdx.org/licenses/). | 2.16.840.1.113883.4.642.4.1027
SpecimenContainedPreference | SpecimenContainedPreference: Degree of preference of a type of conditioned specimen. | 2.16.840.1.113883.4.642.4.853
SpecimenStatus | SpecimenStatus: Codes providing the status/availability of a specimen. | 2.16.840.1.113883.4.642.4.472
strandType | strandType: Type for strand. | 2.16.840.1.113883.4.642.4.986
StructureDefinitionKind N | StructureDefinitionKind: Defines the type of structure that a definition is describing. | 2.16.840.1.113883.4.642.4.669
SubscriptionChannelType | SubscriptionChannelType: The type of method used to execute a subscription. | 2.16.840.1.113883.4.642.4.501
SubscriptionStatus | SubscriptionStatus: The status of a subscription. | 2.16.840.1.113883.4.642.4.503
FHIRSubstanceStatus | FHIRSubstanceStatus: A code to indicate if the substance is actively used. | 2.16.840.1.113883.4.642.4.475
SupplyDeliveryStatus | SupplyDeliveryStatus: Status of the supply delivery. | 2.16.840.1.113883.4.642.4.701
SupplyRequestStatus | SupplyRequestStatus: Status of the supply request. | 2.16.840.1.113883.4.642.4.696
TaskIntent | TaskIntent: Distinguishes whether the task is a proposal, plan or full order. | 2.16.840.1.113883.4.642.4.1241
TaskStatus | TaskStatus: The current status of the task. | 2.16.840.1.113883.4.642.4.791
TransactionMode | TransactionMode: A code that indicates how transactions are supported. | 2.16.840.1.113883.4.642.4.193

TriggerType | TriggerType: The type of trigger. | 2.16.840.1.113883.4.642.4.104
TypeDerivationRule N | TypeDerivationRule: How a type relates to its baseDefinition. | 2.16.840.1.113883.4.642.4.674
UDIEntryType | UDIEntryType: Codes to identify how UDI data was entered. | 2.16.840.1.113883.4.642.4.212
UnknownContentCode | UnknownContentCode: A code that indicates whether an application accepts unknown elements or extensions when reading resources. | 2.16.840.1.113883.4.642.4.197
EvidenceVariableType | EvidenceVariableType: The possible types of variables for exposures or outcomes (E.g. Dichotomous, Continuous, Descriptive). | 2.16.840.1.113883.4.642.4.1344
ResourceVersionPolicy N | ResourceVersionPolicy: How the system supports versioning for a resource. | 2.16.840.1.113883.4.642.4.191
VisionBase | VisionBase: A coded concept listing the base codes. | 2.16.840.1.113883.4.642.4.663
VisionEyes | VisionEyes: A coded concept listing the eye codes. | 2.16.840.1.113883.4.642.4.661
W3cProvenanceActivityType | This value set includes W3C PROV Data Model Activity concepts, which are treated as codes in this valueset. Some adaptations were made to make these concepts suitable values for the Provenance.activity element. Coded concepts are from PROV-DM and the display names are their counterparts in PROV-N (human readable notation syntax specification).[code system OID: http://www.w3.org/TR/2013/REC-prov-dm-20130430/ and http://www.w3.org/TR/2013/REC-prov-n-20130430/]

URI (all prefixed with http://terminology.hl7.org/CodeSystem/) | Description | OID
SurfaceCodes | Surface Codes: This value set includes a smattering of FDI tooth surface codes. | 2.16.840.1.113883.4.642.4.1154
ActionType | ActionType: The type of action to be performed. | 2.16.840.1.113883.4.642.4.1246
ActivityDefinitionCategory | ActivityDefinitionCategory: High-level categorization of the type of activity. | 2.16.840.1.113883.4.642.4.1243
AdjudicationValueCodes | Adjudication Value Codes: This value set includes a smattering of Adjudication Value codes which includes codes to indicate the amounts eligible under the plan, the amount of benefit, copays etc. | 2.16.840.1.113883.4.642.4.1171
Adjudication Error Codes | This value set includes a smattering of adjudication codes. | 2.16.840.1.113883.4.642.4.1053
AdjudicationReasonCodes | Adjudication Reason Codes: This value set includes smattering of Adjudication Reason codes. | 2.16.840.1.113883.4.642.4.1172
AdmitSource | Admit source: This value set defines a set of codes that can be used to indicate from where the patient came in. | 2.16.840.1.113883.4.642.4.1092
AdverseEventCategory | AdverseEventCategory: Overall categorization of the event, e.g. product-related or situational. | 2.16.840.1.113883.4.642.4.1251
AdverseEventCausalityAssessment | AdverseEventCausalityAssessment: Codes for the assessment of whether the entity caused the event. | 2.16.840.1.113883.4.642.4.1254
AdverseEventCausalityMethod | AdverseEventCausalityMethod: TODO. | 2.16.840.1.113883.4.642.4.1255
AdverseEventOutcome | AdverseEventOutcome: TODO (and should this be required?). | 2.16.840.1.113883.4.642.4.1252
AdverseEventSeriousness | AdverseEventSeriousness: Overall seriousness of this event for the patient. | 2.16.840.1.113883.4.642.4.1253
AdverseEventSeverity | AdverseEventSeverity: The severity of the adverse event itself, in direct relation to the subject. | 2.16.840.1.113883.4.642.4.1256
AllergyIntoleranceSubstanceExposureRisk | AllergyIntoleranceSubstanceExposureRisk: The risk of an adverse reaction (allergy or intolerance) for this patient upon exposure to the substance (including pharmaceutical products). | 2.16.840.1.113883.4.642.4.1275
AllergyIntoleranceClinicalStatusCodes | AllergyIntolerance Clinical Status Codes: Preferred value set for AllergyIntolerance Clinical Status. | 2.16.840.1.113883.4.642.4.1373
AllergyIntoleranceVerificationStatusCodes | AllergyIntolerance Verification Status Codes: Preferred value set for AllergyIntolerance Verification Status. | 2.16.840.1.113883.4.642.4.1371
BenefitCostApplicability | Benefit cost applicability: Whether the cost applies to in-network or out-of-network providers. | 2.16.840.1.113883.4.642.1.0
AppointmentCancellationReason | Appointment cancellation reason: This example value set defines a set of reasons for the cancellation of an appointment. | 2.16.840.1.113883.4.642.4.1382
AuditEventEntityType | Audit event entity type: Code for the entity type involved in the audit event. | 2.16.840.1.113883.4.642.4.1134
AuditEventID | Audit Event ID: Event Types for Audit Events - defined by DICOM with some FHIR specific additions. | 2.16.840.1.113883.4.642.4.1136
BasicResourceTypes | Basic Resource Types: This value set defines codes for resources not yet supported by (or which will never be supported by) FHIR. Many of the codes listed here will eventually be turned into official resources. However, there is no guarantee that any particular resource will be created nor that the scope will be exactly as defined by the codes presented here. Codes in this set will be deprecated if/when formal resources are defined that encompass these concepts. | 2.16.840.1.113883.4.642.4.1072
NetworkTypeCodes | Network Type Codes: This value set includes a smattering of Network type codes. | 2.16.840.1.113883.4.642.4.1177
BenefitTermCodes | Benefit Term Codes: This value set includes a smattering of Benefit Term codes. | 2.16.840.1.113883.4.642.4.1179
BenefitTypeCodes | Benefit Type Codes: This value set includes a smattering of Benefit type codes. | 2.16.840.1.113883.4.642.4.1176
UnitTypeCodes | Unit Type Codes: This value set includes a smattering of Unit type codes. | 2.16.840.1.113883.4.642.4.1178
can-push-updates | Can-push-updates: Ability of the primary source to push updates/alerts | 2.16.840.1.113883.4.642.1.897
CatalogType | CatalogType: The type of catalog. | 2.16.840.1.113883.4.642.4.1288
CertaintySubcomponentRating | CertaintySubcomponentRating: The quality rating of the subcomponent of a quality of evidence rating. | 2.16.840.1.113883.4.642.4.1362
CertaintySubcomponentType | CertaintySubcomponentType: The subcomponent classification of quality of evidence rating systems. | 2.16.840.1.113883.4.642.4.1360
ChargeItemCode | ChargeItemCode: Example set of codes that can be used for billing purposes. | 2.16.840.1.113883.4.642.4.1257
ChoiceListOrientation | ChoiceListOrientation: Direction in which lists of possible answers should be displayed. | 2.16.840.1.113883.4.642.4.1273

chromosome-human | chromosome-human: Chromosome number for human. | 2.16.840.1.113883.4.642.4.1086
ExceptionCodes | Exception Codes: This value set includes sample Exception codes. | 2.16.840.1.113883.4.642.4.1162
ClaimTypeCodes | Claim Type Codes: This value set includes Claim Type codes. | 2.16.840.1.113883.4.642.4.1156
ClaimCareTeamRoleCodes | Claim Care Team Role Codes: This value set includes sample Claim Care Team Role codes. | 2.16.840.1.113883.4.642.4.1165
ClaimInformationCategoryCodes | Claim Information Category Codes: This value set includes sample Information Category codes. | 2.16.840.1.113883.4.642.4.1163
AlternativeCodeKind | AlternativeCodeKind: Indicates the type of use for which the code is defined. | 2.16.840.1.113883.4.642.4.1284
CommonTags | Common Tags: Common Tag Codes defined by FHIR project | 2.16.840.1.113883.4.642.4.1067
CommunicationCategory | CommunicationCategory: Codes for general categories of communications such as alerts, instructions, etc. | 2.16.840.1.113883.4.642.4.1076
CommunicationNotDoneReason | CommunicationNotDoneReason: Codes for the reason why a communication did not happen. | 2.16.840.1.113883.4.642.4.1077
CommunicationTopic | CommunicationTopic: Codes describing the purpose or content of the communication. | 2.16.840.1.113883.4.642.4.1078
CompositeMeasureScoring | CompositeMeasureScoring: The composite scoring method of the measure. | 2.16.840.1.113883.4.642.4.1235
AlternativeCodeKind | AlternativeCodeKind: Indicates the type of use for which the code is defined. | 2.16.840.1.113883.4.642.4.1406
ConditionCategoryCodes | Condition Category Codes: Preferred value set for Condition Categories. | 2.16.840.1.113883.4.642.4.1073
ConditionClinicalStatusCodes | Condition Clinical Status Codes: Preferred value set for Condition Clinical Status. | 2.16.840.1.113883.4.642.4.1074
ConditionState | ConditionState: Enumeration indicating whether the condition is currently active, inactive, or has been resolved. | 2.16.840.1.113883.4.642.4.1287
ConditionVerificationStatus | ConditionVerificationStatus: The verification status to support or decline the clinical status of the condition or diagnosis. | 2.16.840.1.113883.4.642.4.1075
ConformanceExpectation | ConformanceExpectation: Indicates the degree of adherence to a specified behavior or capability expected for a system to be deemed conformant with a specification. | 2.16.840.1.113883.4.642.4.1271
ConsentActionCodes | Consent Action Codes: This value set includes sample Consent Action codes. | 2.16.840.1.113883.4.642.4.1227
ConsentCategoryCodes | Consent Category Codes: This value set includes sample Consent Directive Type codes, including several consent directive related LOINC codes; HL7 VALUE SET: ActConsentType(2.16.840.1.113883.1.11.19897); examples of US realm consent directive legal descriptions and references to online and/or downloadable forms such as the SSA-827 Authorization to Disclose Information to the Social Security Administration; and other anticipated consent directives related to participation in a clinical trial, medical procedures, reproductive procedures; health care directive (Living Will); advance directive, do not resuscitate (DNR); Physician Orders for Life-Sustaining Treatment (POLST) | 2.16.840.1.113883.4.642.4.1226
ConsentPolicyRuleCodes | Consent PolicyRule Codes: This value set includes sample Regulatory consent policy types from the US and other regions. | 2.16.840.1.113883.4.642.4.1229
ConsentScopeCodes | Consent Scope Codes: This value set includes the four Consent scope codes. | 2.16.840.1.113883.4.642.4.1228
ContactEntityType | Contact entity type: This example value set defines a set of codes that can be used to indicate the purpose for which you would contact a contact party. | 2.16.840.1.113883.4.642.4.1129
ContainerCap | ContainerCap: Color of the container cap. | 2.16.840.1.113883.4.642.4.1258
ContractContentDerivationCodes | Contract Content Derivation Codes: This is an example set of Content Derivative type codes, which represent the minimal content derived from the basal information source at a specific stage in its lifecycle, which is sufficient to manage that source information, for example, in a repository, registry, processes and workflows, for making access control decisions, and providing query responses. | 2.16.840.1.113883.4.642.4.1204
ContractDataMeaning | ContractDataMeaning: How a resource reference is interpreted when evaluating contract offers. | 2.16.840.1.113883.4.642.4.1205
ContractTypeCodes | Contract Type Codes: This value set includes sample Contract Type codes. | 2.16.840.1.113883.4.642.4.1330
ContractActionCodes | Contract Action Codes: This value set includes sample Contract Action codes. | 2.16.840.1.113883.4.642.4.1202
ContractActorRoleCodes | Contract Actor Role Codes: This value set includes sample Contract Actor Role codes. | 2.16.840.1.113883.4.642.4.1203
ContractSignerTypeCodes | Contract Signer Type Codes: This value set includes sample Contract Signer Type codes. | 2.16.840.1.113883.4.642.4.1201
ContractSubtypeCodes | Contract Subtype Codes: This value set includes sample Contract Subtype codes. | 2.16.840.1.113883.4.642.4.1198
ContractTermSubtypeCodes | Contract Term Subtype Codes: This value set includes sample Contract Term SubType codes. | 2.16.840.1.113883.4.642.4.1200
ContractTermTypeCodes | Contract Term Type Codes: This value set includes sample Contract Term Type codes. | 2.16.840.1.113883.4.642.4.1199
CopyNumberEvent | CopyNumberEvent: Copy Number Event. | 2.16.840.1.113883.4.642.4.1087
CoverageClassCodes | Coverage Class Codes: This value set includes Coverage Class codes. | 2.16.840.1.113883.4.642.4.1147
CoverageCopayTypeCodes | Coverage Copay Type Codes: This value set includes sample Coverage Copayment Type codes. | 2.16.840.1.113883.4.642.4.1149
CoverageSelfPayCodes | Coverage SelfPay Codes: This value set includes Coverage SelfPay codes. | 2.16.840.1.113883.4.642.4.1148
CoverageEligibilityResponseAuthSupportCodes | CoverageEligibilityResponse Auth Support Codes: This value set includes CoverageEligibilityResponse Auth Support codes. | 2.16.840.1.113883.4.642.4.1394
DataAbsentReason N | DataAbsentReason: Used to specify why the normally expected content of the data element is missing. | 2.16.840.1.113883.4.642.4.1048
DefinitionStatus | DefinitionStatus: Codes identifying the lifecycle stage of a definition. | 2.16.840.1.113883.4.642.4.1070

DefinitionTopic | DefinitionTopic: High-level categorization of the definition, used for searching, sorting, and filtering. | 2.16.840.1.113883.4.642.4.1244

DefinitionUseCodes N | Structure Definition Use Codes / Keywords: Structure Definition Use Codes / Keywords | 2.16.840.1.113883.4.642.4.1191

FHIRDeviceStatusReason | FHIRDeviceStatusReason: The availability status reason of the device. | 2.16.840.1.113883.4.642.4.1082

DiagnosisRole | This value set defines a set of codes that can be used to express the role of a diagnosis on the Encounter or EpisodeOfCare record. | 2.16.840.1.113883.4.642.4.1054

DICOM Audit Message Record Lifecycle Events | Attached is vocabulary for the record lifecycle events, as per DICOM Audit Message,

Diet | Diet: This value set defines a set of codes that can be used to indicate dietary preferences or restrictions a patient may have. | 2.16.840.1.113883.4.642.4.1091

DischargeDisposition | Discharge disposition: This value set defines a set of codes that can be used to where the patient left the hospital. | 2.16.840.1.113883.4.642.4.1093

DoseAndRateType | DoseAndRateType: The kind of dose or rate specified. | 2.16.840.1.113883.4.642.4.1069

EffectEstimateType | EffectEstimateType: Whether the effect estimate is an absolute effect estimate (absolute difference) or a relative effect estimate (relative difference), and the specific type of effect estimate (eg relative risk or median difference). | 2.16.840.1.113883.4.642.4.1356

SpecialArrangements | Special arrangements: This value set defines a set of codes that can be used to indicate the kinds of special arrangements in place for a patients visit. | 2.16.840.1.113883.4.642.4.1090

EncounterType | Encounter type: This example value set defines a set of codes that can be used to indicate the type of encounter: a specific code indicating type of service provided. | 2.16.840.1.113883.4.642.4.1088

EndpointConnectionType | Endpoint Connection Type: This is an example value set defined by the FHIR project, that could be used to represent possible connection type profile values. | 2.16.840.1.113883.4.642.4.1140

EndpointPayloadType | Endpoint Payload Type: This is an example value set defined by the FHIR project, that could be used to represent possible payload document types. | 2.16.840.1.113883.4.642.4.1139

EnteralFormulaAdditiveTypeCode | Enteral Formula Additive Type Code: EnteralFormulaAdditiveType: Codes for the type of modular component such as protein, carbohydrate or fiber to be provided in addition to or mixed with the base formula. This value set is provided as a suggestive example. | 2.16.840.1.113883.4.642.4.1123

EpisodeOfCareType | Episode of care type: This example value set defines a set of codes that can be used to express the usage type of an EpisodeOfCare record. | 2.16.840.1.113883.4.642.4.1189

QualityOfEvidenceRating | QualityOfEvidenceRating: A rating system that describes the quality of evidence such as the GRADE, DynaMed, or Oxford CEBM systems. | 2.16.840.1.113883.4.642.4.1267

EvidenceVariantState | EvidenceVariantState: Used for results by exposure in variant states such as low-risk, medium-risk and high-risk states. | 2.16.840.1.113883.4.642.4.1354

USCLSCodes | USCLS Codes: This value set includes a smattering of USCLS codes. | 2.16.840.1.113883.4.642.4.1153

BenefitCategoryCodes | Benefit Category Codes: This value set includes examples of Benefit Category codes. | 2.16.840.1.113883.4.642.4.1175

ExampleClaimSubTypeCodes | Example Claim SubType Codes: This value set includes sample Claim SubType codes which are used to distinguish the claim types for example within type institutional there may be subtypes for emergency services, bed stay and transportation. | 2.16.840.1.113883.4.642.4.1158

ExampleCoverageFinancialExceptionCodes | Example Coverage Financial Exception Codes: This value set includes Example Coverage Financial Exception Codes. | 2.16.840.1.113883.4.642.4.1329

ExampleDiagnosisOnAdmissionCodes | Example Diagnosis on Admission Codes: This value set includes example Diagnosis on Admission codes. | 2.16.840.1.113883.4.642.4.1170

ExampleDiagnosisRelatedGroupCodes | Example Diagnosis Related Group Codes: This value set includes example Diagnosis Related Group codes. | 2.16.840.1.113883.4.642.4.1166

ExampleDiagnosisTypeCodes | Example Diagnosis Type Codes: This value set includes example Diagnosis Type codes. | 2.16.840.1.113883.4.642.4.1167

ClaimPayeeResourceType | ClaimPayeeResourceType: The type of Claim payee Resource. | 2.16.840.1.113883.4.642.4.1164

ExamplePaymentTypeCodes | Example Payment Type Codes: This value set includes example Payment Type codes. | 2.16.840.1.113883.4.642.4.1181

ExampleProcedureTypeCodes | Example Procedure Type Codes: This value set includes example Procedure Type codes. | 2.16.840.1.113883.4.642.4.1388

ExampleProgramReasonCodes | Example Program Reason Codes: This value set includes sample Program Reason Span codes. | 2.16.840.1.113883.4.642.4.1161

ExampleProviderQualificationCodes | Example Provider Qualification Codes: This value set includes sample Provider Qualification codes. | 2.16.840.1.113883.4.642.4.1160

ExampleRelatedClaimRelationshipCodes | Example Related Claim Relationship Codes: This value set includes sample Related Claim Relationship codes. | 2.16.840.1.113883.4.642.4.1159

ExampleRevenueCenterCodes | Example Revenue Center Codes: This value set includes sample Revenue Center codes. | 2.16.840.1.113883.4.642.4.1168

ExampleServicePlaceCodes | Example Service Place Codes: This value set includes a smattering of Service Place codes. | 2.16.840.1.113883.4.642.4.1157

OralSiteCodes | Oral Site Codes: This value set includes a smattering of FDI oral site codes. | 2.16.840.1.113883.4.642.4.1152

ExampleVisionPrescriptionProductCodes | Example Vision Prescription Product Codes: This value set includes a smattering of Prescription Product codes. | 2.16.840.1.113883.4.642.4.1188

ExpansionParameterSource | ExpansionParameterSource: Declares what the source of a parameter is. | 2.16.840.1.113883.4.642.4.1279

ExpansionProcessingRule | ExpansionProcessingRule: Defines how concepts are processed into the expansion when it's for UI presentation. | 2.16.840.1.113883.4.642.4.1281

SecurityRoleType | This CodeSystem contains Additional FHIR-defined Security Role types not defined elsewhere

failure-action | Failure-action: The result if validation fails | 2.16.840.1.113883.4.642.1.891

FinancialTaskCodes | Financial Task Codes: This value set includes Financial Task codes. | 2.16.840.1.113883.4.642.4.1390

FinancialTaskInputTypeCodes | Financial Task Input Type Codes: This value set includes Financial Task Input Type codes. | 2.16.840.1.113883.4.642.4.1392

FlagCategory | Flag Category: Example list of general categories for flagged issues. (Not complete or necessarily appropriate.) | 2.16.840.1.113883.4.642.4.1071

Form Codes | This value set includes a sample set of Forms codes. | 2.16.840.1.113883.4.642.4.1052

Funds Reservation Codes | This value set includes sample funds reservation type codes. | 2.16.840.1.113883.4.642.4.1051

GoalAcceptanceStatus | GoalAcceptanceStatus: Codes indicating whether the goal has been accepted by a stakeholder. | 2.16.840.1.113883.4.642.4.1270

GoalAchievementStatus | Goal achievement status: Describes the progression, or lack thereof, towards the goal against the target. | 2.16.840.1.113883.4.642.4.1375

GoalCategory | Goal category: Example codes for grouping goals to use for filtering or presentation. | 2.16.840.1.113883.4.642.4.1097

GoalPriority | Goal priority: Indicates the level of importance associated with reaching or sustaining a goal. | 2.16.840.1.113883.4.642.4.1096

GoalRelationshipType | GoalRelationshipType: Types of relationships between two goals. | 2.16.840.1.113883.4.642.4.1269

HandlingConditionSet | HandlingConditionSet: Set of handling instructions prior testing of the specimen. | 2.16.840.1.113883.4.642.4.1259

FamilyHistoryAbsentReason | FamilyHistoryAbsentReason: Codes describing the reason why a family member's history is not available. | 2.16.840.1.113883.4.642.4.1094

HL7Workgroup | HL7Workgroup: An HL7 administrative unit that owns artifacts in the FHIR specification. | 2.16.840.1.113883.4.642.4.1277

ImmunizationEvaluationDoseStatusCodes | Immunization Evaluation Dose Status codes: The value set to instantiate this attribute should be drawn from a terminologically robust code system that consists of or contains concepts to support describing the validity of a dose relative to a particular recommended schedule. This value set is provided as a suggestive example. | 2.16.840.1.113883.4.642.4.1102

ImmunizationEvaluationDoseStatusReasonCodes | Immunization Evaluation Dose Status Reason codes: The value set to instantiate this attribute should be drawn from a terminologically robust code system that consists of or contains concepts to support describing the reason why an administered dose has been assigned a particular status. Often, this reason describes why a dose is considered invalid. This value set is provided as a suggestive example. | 2.16.840.1.113883.4.642.4.1103

ImmunizationFundingSource | Immunization Funding Source: The value set to instantiate this attribute should be drawn from a terminologically robust code system that consists of or contains concepts to support describing the source of the vaccine administered. This value set is provided as a suggestive example. | 2.16.840.1.113883.4.642.4.1100

ImmunizationOriginCodes | Immunization Origin Codes: The value set to instantiate this attribute should be drawn from a terminologically robust code system that consists of or contains concepts to support describing the source of the data when the report of the immunization event is not based on information from the person, entity or organization who administered the vaccine. This value set is provided as a suggestive example. | 2.16.840.1.113883.4.642.4.1101

ImmunizationProgramEligibility | Immunization Program Eligibility: The value set to instantiate this attribute should be drawn from a terminologically robust code system that consists of or contains concepts to support describing the patient's eligibility for a vaccination program. This value set is provided as a suggestive example. | 2.16.840.1.113883.4.642.4.1099

ImmunizationRecommendationStatusCodes | Immunization Recommendation Status Codes: The value set to instantiate this attribute should be drawn from a terminologically robust code system that consists of or contains concepts to support describing the status of the patient towards perceived immunity against a vaccine preventable disease. This value set is provided as a suggestive example. | 2.16.840.1.113883.4.642.4.1104

ImmunizationSubpotentReason | Immunization Subpotent Reason: The value set to instantiate this attribute should be drawn from a terminologically robust code system that consists of or contains concepts to support describing the reason why a dose is considered to be subpotent. This value set is provided as a suggestive example. | 2.16.840.1.113883.4.642.4.1098

Implant Status | Implant Status: A set codes that define the functional status of an implanted device. | 2.16.840.1.113883.4.642.4.1283

InsurancePlanType | Insurance plan type: This example value set defines a set of codes that can be used to indicate a type of insurance plan. | 2.16.840.1.113883.4.642.4.1261

ISO 21089-2017 Health Record Lifecycle Events | Attached is vocabulary for the 27 record lifecycle events, as per ISO TS 21089-2017, Health Informatics - Trusted End-to-End Information Flows, Section 3, Terms and Definitions (2017, at ISO Central Secretariat, passed ballot and ready for publication). This will also be included in the FHIR EHR Record Lifecycle Event Implementation Guide, balloted and (to be) published with FHIR STU-3.

LibraryType | LibraryType: The type of knowledge asset this library contains. | 2.16.840.1.113883.4.642.4.1230

ListEmptyReasons | List Empty Reasons: General reasons for a list to be empty. Reasons are either related to a summary list (i.e. problem or medication list) or to a workflow related list (i.e. consultation list). | 2.16.840.1.113883.4.642.4.1106

ExampleUseCodesForList | Example Use Codes for List: Example use codes for the List resource - typical kinds of use. | 2.16.840.1.113883.4.642.4.1105

ListOrderCodes | List Order Codes: Base values for the order of the items in a list resource. | 2.16.840.1.113883.4.642.4.1107

LocationType | Location type: This example value set defines a set of codes that can be used to indicate the physical form of the Location. | 2.16.840.1.113883.4.642.4.1108

MatchGrade | MatchGrade: A Master Patient Index (MPI) assessment of whether a candidate patient record is a match or not. | 2.16.840.1.113883.4.642.4.1289

MeasureDataUsage | MeasureDataUsage: The intended usage for supplemental data elements in the measure. | 2.16.840.1.113883.4.642.4.1234

MeasureImprovementNotation | MeasureImprovementNotation: Observation values that indicate what change in a measurement value or score is indicative of an improvement in the measured item or scored issue. | 2.16.840.1.113883.4.642.4.1395

MeasurePopulationType | MeasurePopulationType: The type of population. | 2.16.840.1.113883.4.642.4.1231

MeasureScoring | MeasureScoring: The scoring type of the measure. | 2.16.840.1.113883.4.642.4.1232

MeasureType | MeasureType: The type of measure (includes codes from 2.16.840.1.113883.1.11.20368). | 2.16.840.1.113883.4.642.4.1233

MedicationAdministration Performer Function Codes | Medication administration performer function codes: MedicationAdministration Performer Function Codes | 2.16.840.1.113883.4.642.4.1112

MediaModality | Media Modality: Detailed information about the type of the image - its kind, purpose, or the kind of equipment used to generate it. | 2.16.840.1.113883.4.642.4.1109

MediaType | Media Type: Codes for high level media categories. | 2.16.840.1.113883.4.642.1.326

MedicationAdministration Category Codes | Medication administration category codes: MedicationAdministration Category Codes | 2.16.840.1.113883.4.642.4.1111
MedicationAdministration Status Codes | Medication administration status codes: MedicationAdministration Status Codes | 2.16.840.1.113883.4.642.4.1311
Medication usage category codes | Medication usage category codes: Medication Status Codes | 2.16.840.1.113883.4.642.4.1120
MedicationDispense Performer Function Codes | Medication dispense performer function codes: MedicationDispense Performer Function Codes | 2.16.840.1.113883.4.642.4.1319
MedicationDispense Status Codes | Medication dispense status codes: MedicationDispense Status Codes | 2.16.840.1.113883.4.642.4.1313
medicationKnowledge Characteristic Codes | Medication knowledge characteristic codes: MedicationKnowledge Characteristic Codes | 2.16.840.1.113883.4.642.4.1338
medicationKnowledge Package Type Codes | Medication knowledge package type codes: MedicationKnowledge Package Type Codes | 2.16.840.1.113883.4.642.4.1340
MedicationKnowledge Status Codes | Medication knowledge status codes: MedicationKnowledge Status Codes | 2.16.840.1.113883.4.642.4.1336
medicationRequest Category Codes | Medication request category codes: MedicationRequest Category Codes | 2.16.840.1.113883.4.642.4.1323
medicationRequest Course of Therapy Codes | Medication request course of therapy codes: MedicationRequest Course of Therapy Codes | 2.16.840.1.113883.4.642.4.1327
medicationRequest Status Reason Codes | Medication request status reason codes: MedicationRequest Status Reason Codes | 2.16.840.1.113883.4.642.4.1325
ExampleMessageReasonCodes | Example Message Reason Codes: Example Message Reasons. These are the set of codes that might be used an updating an encounter using admin-update. | 2.16.840.1.113883.4.642.4.1122
MessageTransport N | MessageTransport: The protocol used for message transport. | 2.16.840.1.113883.4.642.4.1080
MissingToothReasonCodes | Missing Tooth Reason Codes: This value set includes sample Missing Tooth Reason codes. | 2.16.840.1.113883.4.642.4.1150
ModifierTypeCodes | Modifier type Codes: This value set includes sample Modifier type codes. | 2.16.840.1.113883.4.642.4.1151
HumanNameAssemblyOrder | HumanNameAssemblyOrder: A code that represents the preferred display order of the components of a human name. | 2.16.840.1.113883.4.642.4.1266
need | Need: The frequency with which the target must be validated | 2.16.840.1.113883.4.642.1.883
AuditEventEntityRole | AuditEventEntityRole: Code representing the role the entity played in the audit event. | 2.16.840.1.113883.4.642.4.1135
ObservationCategoryCodes | Observation Category Codes: Observation Category codes. | 2.16.840.1.113883.4.642.4.1125
StatisticsCode | StatisticsCode: The statistical operation parameter -"statistic" codes. | 2.16.840.1.113883.4.642.4.1126
OperationOutcomeCodes | Operation Outcome Codes: Operation Outcome codes used by FHIR test servers (see Implementation file translations.xml) | 2.16.840.1.113883.4.642.4.1127
OrganizationType | Organization type: This example value set defines a set of codes that can be used to indicate a type of organization. | 2.16.840.1.113883.4.642.4.1128
DeviceDefinitionParameterGroup | DeviceDefinitionParameterGroup: Codes identifying groupings of parameters; e.g. Cardiovascular. | 2.16.840.1.113883.4.642.4.1264
ParticipantType | Participant type: This value set defines a set of codes that can be used to indicate how an individual participates in an encounter. | 2.16.840.1.113883.4.642.4.1089
Claim Payee Type Codes | This value set includes sample Payee Type codes. | 2.16.840.1.113883.4.642.4.1050
PaymentAdjustmentReasonCodes | Payment Adjustment Reason Codes: This value set includes smattering of Payment Adjustment Reason codes. | 2.16.840.1.113883.4.642.4.1173
PaymentTypeCodes | Payment Type Codes: This value set includes sample Payment Type codes. | 2.16.840.1.113883.4.642.4.1186
PaymentStatusCodes | Payment Status Codes: This value set includes a sample set of Payment Status codes. | 2.16.840.1.113883.4.642.4.1187
PlanDefinitionType | PlanDefinitionType: The type of PlanDefinition. | 2.16.840.1.113883.4.642.4.1245
PractitionerRole | Practitioner role: This example value set defines a set of codes that can be used to indicate the role of a Practitioner. | 2.16.840.1.113883.4.642.4.1132
PrecisionEstimateType | PrecisionEstimateType: Method of reporting variability of estimates, such as confidence intervals, interquartile range or standard deviation. | 2.16.840.1.113883.4.642.4.1358
primary-source-type | Primary-source-type: Type of the validation primary source | 2.16.840.1.113883.4.642.1.893
ProcessPriorityCodes | Process Priority Codes: This value set includes the financial processing priority codes. | 2.16.840.1.113883.4.642.4.1155
Program | Program: This value set defines an example set of codes that could be can be used to classify groupings of service-types/specialties. | 2.16.840.1.113883.4.642.4.1384
ProvenanceParticipantType | Provenance participant type: The type of participation a provenance participant. | 2.16.840.1.113883.4.642.4.1131
push-type-available | Push-type-available: Type of alerts/updates the primary source can send | 2.16.840.1.113883.4.642.1.899
MaxOccurs | MaxOccurs: Flags an element as having unlimited repetitions. | 2.16.840.1.113883.4.642.4.1272
QuestionnaireItemUsageMode | QuestionnaireItemUsageMode: Identifies the modes of usage of a questionnaire that should enable a particular questionnaire item. | 2.16.840.1.113883.4.642.4.1274
AllergyIntoleranceCertainty | AllergyIntoleranceCertainty: Statement about the degree of clinical certainty that a specific substance was the cause of the manifestation in a reaction event. | 2.16.840.1.113883.4.642.4.1276
ReasonMedicationGivenCodes | Reason Medication Given Codes: This value set is provided as an example. The value set to instantiate this attribute should be drawn from a robust terminology code system that consists of or contains concepts to support the medication process. | 2.16.840.1.113883.4.642.4.1110
StrengthOfRecommendationRating | StrengthOfRecommendationRating: A rating system that describes the strength of the recommendation, such as the GRADE, DynaMed, or HGPS systems. | 2.16.840.1.113883.4.642.4.1268
ObservationReferenceRangeMeaningCodes | Observation Reference Range Meaning Codes: This value set defines a set of codes that can be used to indicate the meaning/use of a reference range for a particular target population. | 2.16.840.1.113883.4.642.4.1124

RejectionCriterion | RejectionCriterion: Criterion for rejection of the specimen by laboratory. | 2.16.840.1.113883.4.642.4.1260
ResearchStudyObjectiveType | ResearchStudyObjectiveType: Codes for the kind of study objective. | 2.16.840.1.113883.4.642.4.1248
ResearchStudyPhase | ResearchStudyPhase: Codes for the stage in the progression of a therapy from initial experimental use in humans in clinical trials to post-market evaluation. | 2.16.840.1.113883.4.642.4.1247
ResearchStudyPrimaryPurposeType | ResearchStudyPrimaryPurposeType: Codes for the main intent of the study. | 2.16.840.1.113883.4.642.4.1250
ResearchStudyReasonStopped | ResearchStudyReasonStopped: Codes for why the study ended prematurely. | 2.16.840.1.113883.4.642.4.1249
ResourceSecurityCategory | ResourceSecurityCategory: Provides general guidance around the kind of access Control to Read, Search, Create, Update, or Delete a resource. | 2.16.840.1.113883.4.642.4.1404
PayeeResourceType | PayeeResourceType: The type of payee Resource. | 2.16.840.1.113883.4.642.4.1180
RestfulSecurityService N | RestfulSecurityService: Types of security services used with FHIR. | 2.16.840.1.113883.4.642.4.1079
RiskEstimateType | RiskEstimateType: Whether the risk estimate is dichotomous, continuous or qualitative and the specific type of risk estimate (eg proportion or median). | 2.16.840.1.113883.4.642.4.1364
RiskProbability | Risk Probability: Codes representing the likelihood of a particular outcome in a risk assessment. | 2.16.840.1.113883.4.642.4.1133
AuditEventSourceType | Audit Event Source Type: The type of process where the audit event originated from. | 2.16.840.1.113883.4.642.4.1137
ServiceCategory | Service category: This value set defines an example set of codes that can be used to classify groupings of service-types/specialties. | 2.16.840.1.113883.4.642.4.1144
ServiceProvisionConditions | ServiceProvisionConditions: The code(s) that detail the conditions under which the healthcare service is available/offered. | 2.16.840.1.113883.4.642.4.1143
ReferralMethod | ReferralMethod: The methods of referral can be used when referring to a specific HealthCareService resource. | 2.16.840.1.113883.4.642.4.1142
ServiceType | Service type: This value set defines an example set of codes of service-types. | 2.16.840.1.113883.4.642.4.1145
SmartCapabilities | SmartCapabilities: Codes that define what the server is capable of. | 2.16.840.1.113883.4.642.4.1265
SpecialValues | SpecialValues: A set of generally useful codes defined so they can be included in value sets. | 2.16.840.1.113883.4.642.4.1049
StandardsStatus | StandardsStatus: HL7 Ballot/Standards status of artifact. | 2.16.840.1.113883.4.642.4.1366
StudyType | StudyType: Types of research studies (types of research methods). | 2.16.840.1.113883.4.642.4.1350
SubscriberRelationshipCodes | SubscriberPolicyholder Relationship Codes: This value set includes codes for the relationship between the Subscriber and the Beneficiary (insured/covered party/patient). | 2.16.840.1.113883.4.642.4.1386
SubscriptionTag | SubscriptionTag: Tags to put on a resource after subscriptions have been sent. | 2.16.840.1.113883.4.642.4.1141
SubstanceCategoryCodes | Substance Category Codes: Substance category codes | 2.16.840.1.113883.4.642.4.1138
SupplyItemType | Supply Item Type: This value sets refers to a specific supply item. | 2.16.840.1.113883.4.642.4.1194
SupplyType | Supply Type: This value sets refers to a Category of supply. | 2.16.840.1.113883.4.642.4.1192
SupplyRequestReason | SupplyRequestReason: The reason why the supply item was requested. | 2.16.840.1.113883.4.642.4.1193
SynthesisType | SynthesisType: Types of combining results from a body of evidence (eg. summary data meta-analysis). | 2.16.840.1.113883.4.642.4.1348
TestScriptOperationCode | Test script operation code: This value set defines a set of codes that are used to indicate the supported operations of a testing engine or tool. | 2.16.840.1.113883.4.642.4.1195
TestScriptProfileDestinationType | Test script profile destination type: This value set defines a set of codes that are used to indicate the profile type of a test system when acting as the destination within a TestScript. | 2.16.840.1.113883.4.642.4.1197
TestScriptProfileOriginType | Test script profile origin type: This value set defines a set of codes that are used to indicate the profile type of a test system when acting as the origin within a TestScript. | 2.16.840.1.113883.4.642.4.1196
UsageContextType | UsageContextType: A code that specifies a type of context being specified by a usage context. | 2.16.840.1.113883.4.642.4.1068
validation-process | Validation-process: The primary process by which the target is validated | 2.16.840.1.113883.4.642.1.889
validation-status | Validation-status: Status of the validation of the target against the primary source | 2.16.840.1.113883.4.642.1.895
validation-type | Validation-type: What the target is validated against | 2.16.840.1.113883.4.642.1.887
sequenceStatus | sequenceStatus: Codes providing the status of the variant test result. | 2.16.840.1.113883.4.642.4.1085
verificationresult-communication-method | VerificationResult Communication Method: Attested information may be validated by process that are manual or automated. For automated processes it may accomplished by the system of record reaching out through another system's API or information may be sent to the system of record. This value set defines a set of codes to describing the process, the how, a resource or data element is validated. | 2.16.840.1.113883.4.642.4.1402

Name (URI = http://terminology.hl7.org/CodeSystem/v3-...) | Description | OID
AcknowledgementCondition | The codes identify the conditions under which accept acknowledgements are required to be returned in response to this message. Note that accept acknowledgement address two different issues at the same time: reliable transport as well as syntactical correctness | 2.16.840.1.113883.5.1050
AcknowledgementDetailCode | OpenIssue: Missing description. | 2.16.840.1.113883.5.1100
AcknowledgementDetailType | A code identifying the specific message to be provided. Discussion: A textual value may be specified as the print name, or for non-coded messages, as the original text. Examples: 'Required attribute xxx is missing', 'System will be unavailable March 19 from 0100 to 0300' | 2.16.840.1.113883.5.1082
AcknowledgementType | This attribute contains an acknowledgement code as described in the HL7 message processing rules. OpenIssue: Description was copied from attribute and needs to be improved to be appropriate for a code system. | 2.16.840.1.113883.5.18
ActClass | **** MISSING DEFINITIONS **** | 2.16.840.1.113883.5.6
ActCode | A code specifying the particular kind of Act that the Act-instance represents within its class. Constraints: The kind of Act (e.g. physical examination, serum potassium, inpatient encounter, charge financial transaction, etc.) is specified with a code from one of several, typically external, coding systems. The coding system will depend on the class of Act, such as LOINC for observations, etc. Conceptually, the Act.code must be a specialization of the Act.classCode. This is why the structure of ActClass domain should be reflected in the superstructure of the ActCode domain and then individual codes or externally referenced

vocabularies subordinated under these domains that reflect the ActClass structure. Act.classCode and Act.code are not modifiers of each other but the Act.code concept should really imply the Act.classCode concept. For a negative example, it is not appropriate to use an Act.code "potassium" together with and Act.classCode for "laboratory observation" to somehow mean "potassium laboratory observation" and then use the same Act.code for "potassium" together with Act.classCode for "medication" to mean "substitution of potassium". This mutually modifying use of Act.code and Act.classCode is not permitted. | 2.16.840.1.113883.5.4

ActExposureLevelCode | A qualitative measure of the degree of exposure to the causative agent. This includes concepts such as "low", "medium" and "high". This quantifies how the quantity that was available to be administered to the target differs from typical or background levels of the substance. | 2.16.840.1.113883.5.1114

ActInvoiceElementModifier | Processing consideration and clarification codes. | 2.16.840.1.113883.5.1051

ActMood | OpenIssue: In Ballot 2009May, a strong Negative vote was lodged against several of the concept definitions in the vocabulary used for Act.moodCode. The vote was found "Persuasive With Mod", with the understanding that M and M would undertake a detailed review of these concept definitions for a future release of the RIM. | 2.16.840.1.113883.5.1001

ActPriority | A set of codes (e.g., for routine, emergency), specifying the urgency under which the Act happened, can happen, is happening, is intended to happen, or is requested/demanded to happen. | 2.16.840.1.113883.5.7

ActReason | A set of codes specifying the motivation, cause, or rationale of an Act, when such rationale is not reasonably represented as an ActRelationship of type "has reason" linking to another Act. Examples: Example reasons that might qualify for being coded in this field might be: "routine requirement", "infectious disease reporting requirement", "on patient request", "required by law". | 2.16.840.1.113883.5.8

ActRelationshipCheckpoint | **** MISSING DEFINITIONS **** | 2.16.840.1.113883.5.10

ActRelationshipJoin | **** MISSING DEFINITIONS **** | 2.16.840.1.113883.5.12

ActRelationshipSplit | **** MISSING DEFINITIONS **** | 2.16.840.1.113883.5.13

ActRelationshipSubset | <ns1:p>Used to indicate that the target of the relationship will be a filtered subset of the total related set of targets.</ns1:p><ns1:p>Used when there is a need to limit the number of components to the first, the last, the next, the total, the average or some other filtered or calculated subset.</ns1:p> | 2.16.840.1.113883.5.1099

ActRelationshipType | The source is an excerpt from the target. | 2.16.840.1.113883.5.1002

ActSite | An anatomical location on an organism which can be the focus of an act. | 2.16.840.1.113883.5.1052

ActStatus | Codes representing the defined possible states of an Act, as defined by the Act class state machine. | 2.16.840.1.113883.5.14

ActUSPrivacyLaw | A jurisdictional mandate in the US relating to privacy. Deprecation Comment: Content moved to ActCode under _ActPrivacyLaw; use that instead. | 2.16.840.1.113883.5.1138

ActUncertainty | OpenIssue: Missing Description | 2.16.840.1.113883.5.1053

AddressPartType | Description: Code that specifies whether an address part names the street, city, country, postal code, post box, etc. Discussion: The hierarchical nature of these concepts shows composition. E.g. "Street Name" is part of "Street Address Line" | 2.16.840.1.113883.5.16

AddressUse | Codes that provide guidance around the circumstances in which a given address should be used. | 2.16.840.1.113883.5.1119

AdministrativeGender | The gender of a person used for adminstrative purposes (as opposed to clinical gender) | 2.16.840.1.113883.5.1

AmericanIndianAlaskaNativeLanguages | American Indian and Alaska Native languages currently being used in the United States. | 2.16.840.1.113883.5.1054

Calendar | **** MISSING DEFINITIONS **** | 2.16.840.1.113883.5.1055

CalendarCycle | Calendar cycle identifiers | 2.16.840.1.113883.5.9

CalendarType | **** MISSING DEFINITIONS **** | 2.16.840.1.113883.5.1017

Charset | Internet Assigned Numbers Authority (IANA) Charset Types | 2.16.840.1.113883.5.21

CodingRationale | Identifies how to interpret the instance of the code, codeSystem value in a set of translations. Since HL7 (or a government body) may mandate that codes from certain code systems be sent in conformant messages, other synonyms that are sent in the translation set need to be distinguished among the originally captured source, the HL7 specified code, or some future role. When this code is NULL, it indicates that the translation is an undefined type. When valued, this property must contain one of the following values: SRC - Source (or original) code HL7 - HL7 Specified or Mandated SH - both HL7 mandated and the original code (precoordination) There may be additional values added to this value set as we work through the use of codes in messages and determine other Use Cases requiring special interpretation of the translations. | 2.16.840.1.113883.5.1074

CommunicationFunctionType | Describes the type of communication function that the associated entity plays in the associated transmission. | 2.16.840.1.113883.5.1056

CompressionAlgorithm | **** MISSING DEFINITIONS **** | 2.16.840.1.113883.5.1009

Confidentiality | A set of codes specifying the security classification of acts and roles in accordance with the definition for concept domain "Confidentiality". | 2.16.840.1.113883.5.25

ContainerCap | The type of cap associated with a container | 2.16.840.1.113883.5.26

ContainerSeparator | A material in a blood collection container that facilites the separation of of blood cells from serum or plasma | 2.16.840.1.113883.5.27

ContentProcessingMode | Description: Identifies the order in which content should be processed. | 2.16.840.1.113883.5.1110

ContextControl | A code that specifies how an ActRelationship or Participation contributes to the context of an Act, and whether it may be propagated to descendent Acts whose association allows such propagation (see also attributes Participation.contextControlCode, ActRelationship.contextControlCode, ActRelationship.contextConductionInd). | 2.16.840.1.113883.5.1057

DataOperation | **** MISSING DEFINITIONS **** | 2.16.840.1.113883.5.1123

Dentition | **** MISSING DEFINITIONS **** | 2.16.840.1.113883.5.1080

DeviceAlertLevel | Domain values for the Device.Alert_levelCode | 2.16.840.1.113883.5.31

DocumentCompletion | Identifies the current completion state of a clinical document. | 2.16.840.1.113883.5.33

DocumentStorage | Identifies the storage status of a document. | 2.16.840.1.113883.5.34

EducationLevel | Years of education that a person has completed | 2.16.840.1.113883.5.1077

EmployeeJobClass | **** MISSING DEFINITIONS **** | 2.16.840.1.113883.5.1059

EncounterAdmissionSource | **** MISSING DEFINITIONS **** | 2.16.840.1.113883.5.37

EncounterSpecialCourtesy | **** MISSING DEFINITIONS **** | 2.16.840.1.113883.5.40

EntityClass | Classifies the Entity class and all of its subclasses. The terminology is hierarchical. At the top is this HL7-defined domain of high-level categories (such as represented by the Entity subclasses). Each of these terms must be harmonized and is specializable. The value sets beneath are drawn from multiple, frequently external, domains that reflect much more fine-grained typing. | 2.16.840.1.113883.5.41

EntityCode | OpenIssue: Missing description. | 2.16.840.1.113883.5.1060

EntityDeterminer | EntityDeterminer in natural language grammar is the class of words that comprises articles, demonstrative pronouns, and quantifiers. In the RIM, determiner is a structural code in the Entity class to distinguish whether any given Entity object stands for some, any one, or a specific thing. | 2.16.840.1.113883.5.30

EntityHandling | **** MISSING DEFINITIONS **** | 2.16.840.1.113883.5.42

EntityNamePartQualifier | OpenIssue: Needs description | 2.16.840.1.113883.5.43

EntityNamePartQualifierR2 | Description: The qualifier is a set of codes each of which specifies a certain subcategory of the name part in addition to the main name part type. For example, a given name may be flagged as a nickname, a family name may be a pseudonym or a name of public records. | 2.16.840.1.113883.5.1122

EntityNamePartType | **** MISSING DEFINITIONS **** | 2.16.840.1.113883.5.44

EntityNamePartTypeR2 | Description: Indicates whether the name part is a given name, family name, prefix, suffix, etc. | 2.16.840.1.113883.5.1121

EntityNameUse | **** MISSING DEFINITIONS **** | 2.16.840.1.113883.5.45

EntityNameUseR2 | Description: A set of codes advising a system or user which name in a set of names to select for a given purpose. | 2.16.840.1.113883.5.1120

EntityRisk | Kinds of risks associated with the handling of the material.. | 2.16.840.1.113883.5.46

EntityStatus | Codes representing the defined possible states of an Entity, as defined by the Entity class state machine. | 2.16.840.1.113883.5.1061

EquipmentAlertLevel | **** MISSING DEFINITIONS **** | 2.16.840.1.113883.5.49

Ethnicity | In the United States, federal standards for classifying data on ethnicity determine the categories used by federal agencies and exert a strong influence on categorization by state and local agencies and private sector organizations. The federal standards do not conceptually define ethnicity, and they recognize the absence of an anthropological or scientific basis for ethnicity classification. Instead, the federal standards acknowledge that ethnicity is a social-political construct in which an individual's own identification with a particular ethnicity is preferred to observer identification. The standards specify two minimum ethnicity categories: Hispanic or Latino, and Not Hispanic or Latino. The standards define a Hispanic or Latino as a person of "Mexican, Puerto Rican, Cuban, South or Central America, or other Spanish culture or origin, regardless of race." The standards stipulate that ethnicity data need not be limited to the two minimum categories, but any expansion must be collapsible to those categories. In addition, the standards stipulate that an individual can be Hispanic or Latino or can be Not Hispanic or Latino, but cannot be both. | 2.16.840.1.113883.5.50

ExposureMode | Code for the mechanism by which the exposure agent was exchanged or potentially exchanged by the participants involved in the exposure. | 2.16.840.1.113883.5.1113

GTSAbbreviation | Open Issue: It appears that the printnames are suboptimal and should be improved for many of the existing codes. | 2.16.840.1.113883.5.1022

GenderStatus | **** MISSING DEFINITIONS **** | 2.16.840.1.113883.5.51

HL7ContextConductionStyle | The styles of context conduction usable by relationships within a static model derived from tyhe HL7 Reference Information Model. | 2.16.840.1.113883.5.1129

HL7StandardVersionCode | This code system holds version codes for the Version 3 standards. Values are to be determined by HL7 and added with each new version of the HL7 Standard. | 2.16.840.1.113883.5.1097

HL7UpdateMode | The possible modes of updating that occur when an attribute is received by a system that already contains values for that attribute. | 2.16.840.1.113883.5.57

HtmlLinkType | HtmlLinkType values are drawn from HTML 4.0 and describe the relationship between the current document and the anchor that is the target of the link | 2.16.840.1.113883.5.58

IdentifierReliability | Specifies the reliability with which the identifier is known. This attribute MAY be used to assist with identifier matching algorithms. | 2.16.840.1.113883.5.1117

IdentifierScope | Description: Codes to specify the scope in which the identifier applies to the object with which it is associated, and used in the datatype property II. | 2.16.840.1.113883.5.1116

IntegrityCheckAlgorithm | **** MISSING DEFINITIONS **** | 2.16.840.1.113883.5.1010

LanguageAbilityMode | A value representing the method of expression of the language. Example: Expressed spoken, expressed written, expressed signed, received spoken, received written, received signed. OpenIssue: Description copied from Concept Domain of same name. Must be verified. | 2.16.840.1.113883.5.60

LanguageAbilityProficiency | A value representing the level of proficiency in a language. Example: Excellent, good, fair, poor. OpenIssue: Description copied from Concept Domain of same name. Must be verified. | 2.16.840.1.113883.5.61

LivingArrangement | A code depicting the living arrangements of a person | 2.16.840.1.113883.5.63

LocalMarkupIgnore | Tells a receiver to ignore just the local markup tags (local_markup, local_header, local_attr) when value="markup", or to ignore the local markup tags and all contained content when value="all" | 2.16.840.1.113883.5.65

LocalRemoteControlState | **** MISSING DEFINITIONS **** | 2.16.840.1.113883.5.66

ManagedParticipationStatus | Codes representing the defined possible states of a Managed Participation, as defined by the Managed Participation class state machine. | 2.16.840.1.113883.5.1062

MapRelationship | The closeness or quality of the mapping between the HL7 concept (as represented by the HL7 concept identifier) and the source coding system. The values are patterned after the similar relationships used in the UMLS Metathesaurus. Because the HL7 coding sy | 2.16.840.1.113883.5.67

MaritalStatus | * * * No description supplied * * * Open Issue: The specific meanings of these codes can vary somewhat by jurisdiction and implementation so caution should be used when determining equivalency. | 2.16.840.1.113883.5.2

MessageWaitingPriority | Indicates that the receiver has messages for the sender OpenIssue: Description does not make sense relative to name of coding system. Must be reviewed and improved. | 2.16.840.1.113883.5.1083

ModifyIndicator | **** MISSING DEFINITIONS **** | 2.16.840.1.113883.5.81

NullFlavor | A collection of codes specifying why a valid value is not present. | 2.16.840.1.113883.5.1008

ObservationCategory | High level observation categories for the general type of observation being made. URL: http://hl7-fhir.github.io/valueset-observation-category.html This is an inline code system http://hl7.org/fhir/observation-category. | 2.16.840.1.113883.4.642.1.222

ObservationInterpretation | One or more codes providing a rough qualitative interpretation of the observation, such as "normal" / "abnormal", "low" / "high", "better" / "worse", "resistant" / "susceptible", "expected" / "not expected". The value set is intended to

be for ANY use where coded representation of an interpretation is needed. | 2.16.840.1.113883.5.83

ObservationMethod | A code that provides additional detail about the means or technique used to ascertain the observation. Examples: Blood pressure measurement method: arterial puncture vs. sphygmomanometer (Riva-Rocci), sitting vs. supine position, etc. OpenIssue: Description copied from Concept Domain of same name. Must be verified. Note that the Domain has a full discussion about use of the attribute and constraining that is not appropriate for the code system description. Needs to be improved. | 2.16.840.1.113883.5.84

ObservationValue | This domain is the root domain to which all HL7-recognized value sets for the Observation.value attribute will be linked when Observation.value has a coded data type. OpenIssue: Description copied from Concept Domain of same name. Must be corrected.. | 2.16.840.1.113883.5.1063

ParticipationFunction | This code is used to specify the exact function an actor had in a service in all necessary detail. This domain may include local extensions (CWE). | 2.16.840.1.113883.5.88

ParticipationMode | A set of codes specifying the modality by which the Entity playing the Role is participating in the Act. Examples: Physically present, over the telephone, written communication. Rationale: Particularly for author (originator) participants this is used to specify whether the information represented by the act was initially provided verbally, (hand-)written, or electronically. Open Issue: There needs to be a reexamination of the hierarchies as there seems to be some muddling between ELECTRONIC and other concepts that involve electronic communication that are in other hierarchies. | 2.16.840.1.113883.5.1064

ParticipationSignature | A set of codes specifying whether and how the participant has attested his participation through a signature and or whether such a signature is needed. Examples: A surgical Procedure act object (representing a procedure report) requires a signature of the performing and responsible surgeon, and possibly other participants. (See also: Participation.signatureText.) | 2.16.840.1.113883.5.89

ParticipationType | **** MISSING DEFINITIONS **** | 2.16.840.1.113883.5.90

PatientImportance | Patient VIP code | 2.16.840.1.113883.5.1075

PaymentTerms | Describes payment terms for a financial transaction, used in an invoice. This is typically expressed as a responsibility of the acceptor or payor of an invoice. | 2.16.840.1.113883.5.91

PersonDisabilityType | A code identifying a person's disability. | 2.16.840.1.113883.5.93

ProbabilityDistributionType | **** MISSING DEFINITIONS **** | 2.16.840.1.113883.5.1020

ProcessingID | Codes used to specify whether a message is part of a production, training, or debugging system. | 2.16.840.1.113883.5.100

ProcessingMode | **** MISSING DEFINITIONS **** | 2.16.840.1.113883.5.101

QueryParameterValue | The domain of coded values used as parameters within QueryByParameter queries. | 2.16.840.1.113883.5.1096

QueryPriority | **** MISSING DEFINITIONS **** | 2.16.840.1.113883.5.102

QueryRequestLimit | Definition: Defines the units associated with the magnitude of the maximum size limit of a query response that can be accepted by the requesting application. | 2.16.840.1.113883.5.1112

QueryResponse | A code classifying the general nature of the response to a given query. Includes whether or not data was found, or whether an error occurred. | 2.16.840.1.113883.5.1067

QueryStatusCode | A code specifying the state of the Query. | 2.16.840.1.113883.5.103

Race | In the United States, federal standards for classifying data on race determine the categories used by federal agencies and exert a strong influence on categorization by state and local agencies and private sector organizations. The federal standards do not conceptually define race, and they recognize the absence of an anthropological or scientific basis for racial classification. Instead, the federal standards acknowledge that race is a social-political construct in which an individual's own identification with one more race categories is preferred to observer identification. The standards use a variety of features to define five minimum race categories. Among these features are descent from "the original peoples" of a specified region or nation. The minimum race categories are American Indian or Alaska Native, Asian, Black or African American, Native Hawaiian or Other Pacific Islander, and White. The federal standards stipulate that race data need not be limited to the five minimum categories, but any expansion must be collapsible to those categories. | 2.16.840.1.113883.5.104

RelationalOperator | **** MISSING DEFINITIONS **** | 2.16.840.1.113883.5.105

RelationshipConjunction | **** MISSING DEFINITIONS **** | 2.16.840.1.113883.5.106

ReligiousAffiliation | Assigment of spiritual faith affiliation | 2.16.840.1.113883.5.1076

ResponseLevel | Specifies whether a response is expected from the addressee of this interaction and what level of detail that response should include | 2.16.840.1.113883.5.108

ResponseModality | Defines the timing and grouping of the response instances. OpenIssue: Description copied from Concept Domain of same name. Must be verified. | 2.16.840.1.113883.5.109

ResponseMode | Specifies the mode, immediate versus deferred or queued, by which a receiver should communicate its receiver responsibilities. | 2.16.840.1.113883.5.1126

RoleClass | Codes for the Role class hierarchy. The values in this hierarchy, represent a Role which is an association or relationship between two entities - the entity that plays the role and the entity that scopes the role. Roles names are derived from the name of the playing entity in that role. The role hierarchy stems from three core concepts, or abstract domains: RoleClassOntological is an abstract domain that collects roles in which the playing entity is defined or specified by the scoping entity. RoleClassPartitive collects roles in which the playing entity is in some sense a "part" of the scoping entity. RoleClassAssociative collects all of the remaining forms of association between the playing entity and the scoping entity. This set of roles is further partitioned between: RoleClassPassive which are roles in which the playing entity is used, known, treated, handled, built, or destroyed, etc. under the auspices of the scoping entity. The playing entity is passive in these roles in that the role exists without an agreement from the playing entity. RoleClassMutualRelationship which are relationships based on mutual behavior of the two entities. The basis of these relationship may be formal agreements or they may bede facto behavior. Thus, this sub-domain is further divided into: RoleClassRelationshipFormal in which the relationship is formally defined, frequently by a contract or agreement. Personal relationship which inks two people in a personal relationship. The hierarchy discussed above is represented In the current vocabulary tables as a set of abstract domains, with the exception of the "Personal relationship" which is a leaf concept. OpenIssue: Description copied from Concept Domain of same name. Must be verified. | 2.16.840.1.113883.5.110

RoleCode | A set of codes further specifying the kind of Role; specific classification codes for further qualifying RoleClass codes. | 2.16.840.1.113883.5.111

RoleLinkStatus | Description: Codes representing possible states of a RoleLink, as defined by the RoleLink class state machine. | 2.16.840.1.113883.5.1137

RoleLinkType | **** MISSING DEFINITIONS **** | 2.16.840.1.113883.5.107

RoleStatus | Codes representing the defined possible states of an Role, as defined by the Role class state machine. | 2.16.840.1.113883.5.1068

RouteOfAdministration | The path the administered medication takes to get into the body or into contact with the body. | 2.16.840.1.113883.5.112

Sequencing | Specifies sequence of sort order. | 2.16.840.1.113883.5.113

SetOperator | **** MISSING DEFINITIONS **** | 2.16.840.1.113883.5.1069

SpecimenType | **** MISSING DEFINITIONS **** | 2.16.840.1.113883.5.129

SubstitutionCondition | Identifies what sort of change is permitted or has occurred between the item that was ordered/requested and the one that was/will be provided. | 2.16.840.1.113883.5.1071

TableCellHorizontalAlign | These values are defined within the XHTML 4.0 Table Model | 2.16.840.1.113883.5.131

TableCellScope | These values are defined within the XHTML 4.0 Table Model | 2.16.840.1.113883.5.132

TableCellVerticalAlign | These values are defined within the XHTML 4.0 Table Model | 2.16.840.1.113883.5.133

TableFrame | These values are defined within the XHTML 4.0 Table Model | 2.16.840.1.113883.5.134

TableRules | These values are defined within the XHTML 4.0 Table Model | 2.16.840.1.113883.5.136

TargetAwareness | **** MISSING DEFINITIONS **** | 2.16.840.1.113883.5.137

TelecommunicationCapabilities | Description: Concepts that define the telecommunication capabilities of a particular device. Used to identify the expected capabilities to be found at a particular telecommunication address. | 2.16.840.1.113883.5.1118

TimingEvent | **** MISSING DEFINITIONS **** | 2.16.840.1.113883.5.139

TransmissionRelationshipTypeCode | Description: A code specifying the meaning and purpose of every TransmissionRelationship instance. Each of its values implies specific constraints to what kinds of Transmission objects can be related and in which way. | 2.16.840.1.113883.5.1111

TribalEntityUS | INDIAN ENTITIES RECOGNIZED AND ELIGIBLE TO RECEIVE SERVICES FROM THE UNITED STATES BUREAU OF INDIAN AFFAIRS | 2.16.840.1.113883.5.140

VaccineManufacturer | The manufacturer of a vaccine. | 2.16.840.1.113883.5.144

WorkClassificationODH | Code system of concepts representing a person's job type as defined by compensation and sector (e.g. paid vs. unpaid, self-employed vs. not self-employed, government vs. private, etc.). | 2.16.840.1.113883.5.1139

hl7ApprovalStatus | Description: Codes for concepts describing the approval level of HL7 artifacts. This code system reflects the concepts expressed in HL7's Governance & Operations Manual (GOM) past and present. | 2.16.840.1.113883.5.1130

hl7CMETAttribution | **** MISSING DEFINITIONS **** | 2.16.840.1.113883.5.1132

hl7ITSType | Description: Codes identifying types of HL7 Implementation Technology Specifications | 2.16.840.1.113883.5.1135

hl7ITSVersionCode | HL7 implementation technology specification versions. These codes will document the ITS type and version for message encoding. The code will appear in the instances based upon rules expressed in the ITS, and do not appear in the abstract message, either as it is presented to received from the ITS. | 2.16.840.1.113883.5.1092

hl7PublishingDomain | Description: Codes for HL7 publishing domains (specific content area) | 2.16.840.1.113883.5.1136

hl7PublishingSection | Description: Codes for HL7 publishing sections (major business categories) | 2.16.840.1.113883.5.1133

hl7PublishingSubSection | Description: Codes for HL7 publishing sub-sections (business sub-categories) | 2.16.840.1.113883.5.1134

hl7Realm | Description: Coded concepts representing Binding Realms (used for Context Binding of terminology in HL7 models) and/or Namespace Realms (used to help ensure unique identification of HL7 artifacts). This code system is partitioned into three sections: Affiliate realms, Binding realms and Namespace realms. All affiliate realm codes may automatically be used as both binding realms and namespace realms. Furthermore, affiliate realms are the only realms that have authority over the creation of binding realms. (Note that 'affiliate' includes the idea of both international affiliates and the HL7 International organization.) All other codes must be associated with an owning affiliate realm and must appear as a specialization of _BindingRealm or _NamespaceRealm. For affiliates whose concepts align with nations, the country codes from ISO 3166-1 2-character alpha are used for the code when possible so these codes should not be used for other realm types. It is recommended that binding realm and namespace codes submitted by affiliates use the realm code as a prefix to avoid possible collisions with ISO codes. However, tooling does not currently support namepace realm codes greater than 2 characters. Open Issue: The name of the concept property "owningAffiliate" should be changed to better reflect that the property value is the human readable name of the organizational entity that manages the Realm identified by the Realm Code. Open Issue: In spite of the inability of tooling to process codes longer than 2 characters, there is at least one realm codes ('SOA') that was added that is 3 characters in length. | 2.16.840.1.113883.5.1124

hl7V3Conformance | Description: Identifies allowed codes for HL7aTMs v3 conformance property. | 2.16.840.1.113883.5.1125

hl7VoteResolution | Description: Based on concepts for resolutions from HL7 ballot spreadsheet according to HL7's Governance & Operations Manual (GOM). | 2.16.840.1.113883.5.1131

orderableDrugForm | OpenIssue: Missing description. | 2.16.840.1.113883.5.85

policyHolderRole | This vocabulary is defined by Implementation Guide for CDA Release 2 - Level 1 - Care Record Summary (US realm). It describes roles recognized through the issuance of an insurance policy to a policyholder who a relationship with the covered party, such as spouse, child, etc. This vocabulary is essentially an inversion of the role relations of the HL7 CoverageRoleType vocabulary. It provides more detailed roles with respect to the underwriter (the scoping organization) for those participants in the policyholder role for a patient. Open Issue: The code values for this coding system must be extracted from the CDA documentation and brought forward through Harmonization for instantiation in this repository. | 2.16.840.1.113883.5.1128

styleType | <ns1:p>The style code is used within the CDA/SPL narrative block to give the instance author some control over various aspects of style</ns1:p> | 2.16.840.1.113883.5.1095

substanceAdminSubstitution | Identifies what sort of change is permitted or has occurred between the therapy that was ordered and the therapy that was/will be provided. | 2.16.840.1.113883.5.1070

triggerEventID | Description: This code system contains all HL7 artifacts of type TE (Trigger Event) that are created by HL7 or its affiliates or their designates using the realm namespacing rules approved by HL7. Local implementations who create trigger events outside of these namespacing rules, (e.g. using the ZZ realm code) must register their own code system. The specific list of legal codes can be found by consulting the HL7 publications (editions, ballots, implementation guides, etc.) published by HL7 Inc. and by the various HL7 affiliates and their designates. Codes shall be expressed in upper case, with separator as shown in HL7 publications with no version id. E.g. PORX_TE123456UV. | 2.16.840.1.113883.1.18

Note: v2 code systems may or may not be case sensitive. v2 Code systems will have the CodeSystem.caseSensitive correctly populated in a future version of this specification.

URI (all prefixed with http://terminology.hl7.org/CodeSystem/v2-/) | ID | OID

0001 | Administrative Sex

0002 | Marital Status

0003 | Event Type

0004 | Patient Class
0006 | ReligionVersion Dependent. Use one of: 2.1+ 2.4+
0007 | Admission Type
0008 | Acknowledgment code
0009 | Ambulatory Status
0012 | STOCK LOCATION
0017 | Transaction Type
0023 | Admit Source
0027 | Priority
0033 | ROUTE
0034 | SITE ADMINISTERED
0038 | Order status
0043 | Condition Code
0048 | What subject filter
0052 | Diagnosis Type
0061 | Check Digit Scheme
0062 | Event Reason
0063 | Relationship
0065 | Specimen Action Code
0066 | Employment Status
0069 | Hospital Service
0070 | Specimen Source Codes
0074 | Diagnostic Service Section ID
0076 | Message Type
0078 | Interpretation Codes
0080 | Nature of Abnormal Testing
0083 | Outlier Type
0085 | Observation Result Status Codes Interpretation
0091 | Query Priority
0092 | Re-Admission Indicator
0098 | Type of Agreement
0100 | Invocation event
0102 | Delayed acknowledgment type
0103 | Processing ID
0104 | Version ID
0105 | Source of Comment
0106 | Query/response format code
0107 | Deferred response type
0108 | Query results level
0109 | Report priority
0116 | Bed Status
0119 | Order Control Codes
0121 | Response Flag
0122 | Charge Type
0123 | Result Status
0124 | Transportation Mode
0126 | Quantity Limited Request
0127 | Allergen Type
0128 | Allergy Severity
0130 | Visit User Code
0131 | Contact Role
0133 | Procedure Practitioner Identifier Code Type
0135 | Assignment of Benefits
0136 | Yes/no Indicator
0137 | Mail Claim Party
0140 | Military Service
0141 | Military Rank/Grade
0142 | Military Status
0144 | Eligibility Source
0145 | Room Type
0146 | Amount Type
0147 | Policy Type
0148 | Money or Percentage Indicator
0149 | Day Type
0150 | Certification Patient Type
0153 | Value Code
0155 | Accept/Application Acknowledgment Conditions
0156 | Which date/time qualifier
0157 | Which date/time status qualifier
0158 | Date/time selection qualifier
0159 | Diet Code Specification Type
0160 | Tray Type

0161 | Allow Substitution
0162 | Route of Administration
0163 | Body Site
0164 | Administration Device
0165 | Administration Method
0166 | RX Component Type
0167 | Substitution Status
0168 | Processing Priority
0169 | Reporting Priority
0170 | Derived Specimen
0173 | Coordination of Benefits
0174 | Nature of Service/Test/Observation
0175 | Master File Identifier Code
0177 | Confidentiality Code
0178 | File Level Event Code
0179 | Response Level
0180 | Masterfile Action Code
0181 | MFN Record-level Error Return
0183 | Active/Inactive
0185 | Preferred Method of Contact
0187 | Provider Billing
0189 | Ethnic Group
0190 | Address Type
0191 | Type of Referenced Data
0193 | Amount Class
0200 | Name Type
0201 | Telecommunication Use Code
0202 | Telecommunication Equipment Type
0203 | Identifier Type
0204 | Organizational Name Type
0205 | Price Type
0206 | Segment Action Code
0207 | Processing Mode
0208 | Query Response Status
0209 | Relational Operator
0210 | Relational Conjunction
0211 | Alternate Character Sets
0213 | Purge Status Code
0214 | Special Program Code
0215 | Publicity Code
0216 | Patient Status Code
0217 | Visit Priority Code
0220 | Living Arrangement
0223 | Living Dependency
0224 | Transport Arranged
0225 | Escort Required
0227 | Manufacturers of Vaccines (code=MVX)
0228 | Diagnosis Classification
0229 | DRG Payor
0230 | Procedure Functional Type
0231 | Student Status
0232 | - Insurance Company Contact Reason
0234 | Report Timing
0235 | Report Source
0236 | Event Reported To
0237 | Event Qualification
0238 | Event Seriousness
0239 | Event Expected
0240 | Event Consequence
0241 | Patient Outcome
0242 | Primary Observer's Qualification
0243 | Identity May Be Divulged
0247 | Status of Evaluation
0248 | Product Source
0250 | Relatedness Assessment
0251 | Action Taken in Response to the Event
0252 | Causality Observations
0253 | Indirect Exposure Mechanism
0254 | Kind of Quantity
0255 | Duration Categories
0256 | Time Delay Post Challenge
0257 | Nature of Challenge

0258 | Relationship Modifier
0259 | Modality
0260 | Patient Location Type
0261 | Location Equipment
0262 | Privacy Level
0263 | Level of Care
0265 | Specialty Type
0267 | Days of the Week
0268 | Override
0269 | Charge On Indicator
0270 | Document Type
0271 | Document Completion Status
0272 | Document Confidentiality Status
0273 | Document Availability Status
0275 | Document Storage Status
0276 | Appointment reason codes
0277 | Appointment Type Codes
0278 | Filler status codes
0279 | Allow Substitution Codes
0280 | Referral Priority
0281 | Referral Type
0282 | Referral Disposition
0283 | Referral Status
0284 | Referral Category
0286 | Provider Role
0287 | Problem/Goal Action Code
0290 | MIME base64 encoding characters
0291 | Subtype of Referenced Data
0292 | Vaccines Administered
0294 | Time Selection Criteria Parameter Class Codes
0298 | CP Range Type
0299 | Encoding
0301 | Universal ID Type
0305 | Person Location Type
0309 | Coverage Type
0311 | Job Status
0315 | Living Will Code
0316 | Organ Donor Code
0317 | Annotations
0321 | Dispense Method
0322 | Completion Status
0323 | Action Code
0324 | Location Characteristic ID
0325 | Location Relationship ID
0326 | Visit Indicator
0329 | Quantity Method
0330 | Marketing Basis
0331 | Facility Type
0332 | Source Type
0334 | Disabled Person Code
0335 | Repeat Pattern
0336 | Referral Reason
0337 | Certification Status
0338 | Practitioner ID Number Type
0339 | Advanced Beneficiary Notice Code
0344 | Patient's Relationship to Insured
0350 | Occurrence Code
0351 | Occurrence Span
0354 | Message Structure
0355 | Primary Key Value Type
0356 | Alternate Character Set Handling Scheme
0357 | Message Error Condition Codes
0359 | Diagnosis Priority
0360 | Degree/License/CertificateVersion Dependent. Use one of: 2.3.1+ 2.7+
0363 | Assigning Authority
0364 | Comment Type
0365 | Equipment State
0366 | Local/Remote Control State
0367 | Alert Level
0368 | Remote Control Command
0369 | Specimen Role
0370 | Container Status

0371 | Additive/Preservative
0372 | Specimen Component
0373 | Treatment
0374 | System Induced Contaminants
0375 | Artificial Blood
0376 | Special Handling Code
0377 | Other Environmental Factors
0383 | Substance Status
0384 | Substance Type
0387 | Command Response
0388 | Processing Type
0389 | Analyte Repeat Status
0391 | Segment GroupVersion Dependent. Use one of: 2.4+ 2.6+
0392 | Match Reason
0393 | Match Algorithms
0394 | Response Modality
0395 | Modify Indicator
0396 | Coding System
0397 | Sequencing
0398 | Continuation Style Code
0401 | Government Reimbursement Program
0402 | School Type
0403 | Language Ability
0404 | Language Proficiency
0406 | Participant Organization Unit Type
0409 | Application Change Type
0411 | Supplemental Service Information Values
0415 | Transfer Type
0416 | Procedure DRG Type
0417 | Tissue Type Code
0418 | Procedure Priority
0421 | Severity of Illness Code
0422 | Triage Code
0423 | Case Category Code
0424 | Gestation Category Code
0425 | Newborn Code
0426 | Blood Product Code
0427 | Risk Management Incident Code
0428 | Incident Type Code
0429 | Production Class Code
0430 | Mode of Arrival Code
0431 | Recreational Drug Use Code
0432 | Admission Level of Care Code
0433 | Precaution Code
0434 | Patient Condition Code
0435 | Advance Directive Code
0436 | Sensitivity to Causative Agent Code
0437 | Alert Device Code
0438 | Allergy Clinical Status
0440 | Data Types
0441 | Immunization Registry Status
0442 | Location Service Code
0443 | Provider Role
0444 | Name Assembly Order
0445 | Identity Reliability Code
0450 | Event Type
0455 | Type of Bill Code
0456 | Revenue code
0457 | Overall Claim Disposition Code
0459 | Reimbursement Action Code
0460 | Denial or Rejection Code
0465 | Name/Address Representation
0466 | Ambulatory Payment Classification Code
0468 | Payment Adjustment Code
0469 | Packaging Status Code
0470 | Reimbursement Type Code
0472 | TQ Conjunction ID
0473 | Formulary Status
0474 | Practitioner Organization Unit Type
0475 | Charge Type Reason
0477 | Controlled Substance Schedule
0478 | Formulary Status

0480 | Pharmacy Order Types
0482 | Order Type
0483 | Authorization Mode
0484 | Dispense Type
0485 | Extended Priority Codes
0487 | Specimen Type
0488 | Specimen Collection Method
0489 | Risk Codes
0490 | Specimen Reject Reason
0491 | Specimen Quality
0492 | Specimen Appropriateness
0493 | Specimen Condition
0494 | Specimen Child Role
0495 | Body Site Modifier
0496 | Consent Type
0497 | Consent Mode
0498 | Consent Status
0499 | Consent Bypass Reason
0500 | Consent Disclosure Level
0501 | Consent Non-Disclosure Reason
0502 | Non-Subject Consenter Reason
0503 | Sequence/Results Flag
0504 | Sequence Condition Code
0505 | Cyclic Entry/Exit Indicator
0506 | Service Request Relationship
0507 | Observation Result Handling
0508 | Blood Product Processing Requirements
0510 | Blood Product Dispense Status
0511 | BP Observation Status Codes Interpretation
0513 | Blood Product Transfusion/Disposition Status
0514 | Transfusion Adverse Reaction
0516 | Error Severity
0517 | Inform Person Code
0518 | Override Type
0520 | Message Waiting Priority
0523 | Computation Type
0524 | Sequence condition
0527 | Calendar Alignment
0528 | Event Related Period
0529 | Precision
0530 | Organization, Agency, Department
0534 | Notify Clergy Code
0535 | Signature Code
0536 | Certificate Status
0538 | Institution Relationship Type
0540 | Inactive Reason Code
0544 | Container Condition
0547 | Jurisdictional Breadth
0548 | Signatory's Relationship to Subject
0550 | Body Parts
0553 | Invoice Control Code
0554 | Invoice Reason Codes
0555 | Invoice Type
0556 | Benefit Group
0557 | Payee Type
0558 | Payee Relationship to Invoice
0559 | Product/Service Status
0561 | Product/Services Clarification Codes
0562 | Processing Consideration Codes
0564 | Adjustment Category Code
0565 | Provider Adjustment Reason Code
0566 | Blood Unit Type
0569 | Adjustment Action
0570 | Payment Method Code
0571 | Invoice Processing Results Status
0572 | Tax status
0615 | User Authentication Credential Type Code
0616 | Address Expiration Reason
0617 | Address Usage
0618 | Protection Code
0625 | Item Status Codes
0634 | Item Importance Codes

0642 | Reorder Theory Codes
0651 | Labor Calculation Type
0653 | Date Format
0657 | Device Type
0659 | Lot Control
0667 | Device Data State
0669 | Load Status
0682 | Device Status
0702 | Cycle Type
0717 | Access Restriction Value
0719 | Access Restriction Reason Code
0725 | Mood Codes
0728 | CCL Value
0731 | DRG Diagnosis Determination Status
0734 | Grouper Status
0739 | DRG Status Patient
0742 | DRG Status Financial Calculation
0749 | DRG Grouping Status
0755 | Status Weight At Birth
0757 | DRG Status Respiration Minutes
0759 | Status Admission
0761 | DRG Procedure Determination Status
0763 | DRG Procedure Relevance
0776 | Item Status
0778 | Item Type
0790 | Approving Regulatory Agency
0793 | Ruling Act
0806 | Sterilization Type
0818 | Package
0834 | MIME Types
0868 | Telecommunication Expiration Reason
0871 | Supply Risk Codes
0881 | Role Executing Physician
0882 | Medical Role Executing Physician
0894 | Side of body
0895 | Present On Admission (POA) Indicator
0904 | Security Check Scheme
0905 | Shipment Status
0906 | ActPriority
0907 | Confidentiality
0909 | Patient Results Release Categorization Scheme
0912 | Participation
0914 | Root Cause
0916 | Relevant Clinicial Information
0917 | Bolus Type
0918 | PCA Type
0919 | Exclusive Test
0920 | Preferred Specimen/Attribute Status
0921 | Certification Type Code
0922 | Certification Category Code
0923 | Process Interruption
0924 | Cumulative Dosage Limit UoM
0925 | Phlebotomy Issue
0926 | Phlebotomy Status
0927 | Arm Stick
0933 | Intended Procedure Type
0935 | Process Interruption Reason
4000 | Name/address representation

4.3.0.3 ICD-10

URL: https://hl7.org/fhir/R4/sid/icd-10/index.html

4.3.0.3.0 ICD-10

FHIR Infrastructure Work Group | Maturity Level: N/A | Standards Status: Informative

The URL "http://hl7.org/fhir/sid/icd-10" is the FHIR system identifier for codes defined in the ICD-10 International code system. The source of this code system is the WHO, at http://www.who.int/classifications/icd/en/ .

4.3.1 Using SNOMED CT with FHIR

URL: https://hl7.org/fhir/R4/snomedct.html

If any ConceptMap resources exist with an identifier that conforms to the URL pattern specified below, the content of the resource must conform to the template provided. Canonical references to ConceptMap resource instances are made using their URI.

4.3.1.0 Using SNOMED CT with FHIR

Vocabulary Work Group | Maturity Level: 5 | Standards Status: Trial Use

4.3.1.0.1 Summary

Source | SNOMED CT is owned, maintained and distributed by SNOMED International . SNOMED International is the organization which publishes the International Edition of SNOMED CT. SNOMED International Members may also distribute their own SNOMED CT National Edition, which contains the international release plus local extension content and derivatives.

System | The URI http://snomed.info/sct identifies the SNOMED CT code system.

Version | Where a code system version is used, it should be specified as a URI that represents a specific SNOMED CT Edition published on a particular date (e.g. the International Edition or a National Edition, with a version date), following the SNOMED CT URI Specification (see note below).

Code | The following SNOMED CT artifacts are valid in the code element for the http://snomed.info/sct namespace: Concept IDs and SNOMED CT Expressions (using SNOMED CT Compositional Grammar). SNOMED CT Terms and Description Identifiers are not valid as codes in FHIR, nor are other alternative identifiers associated with SNOMED CT Concepts. Note: When SNOMED CT Terms must be exchanged, use the Description Id Extension.

Display | The correct display for a SNOMED CT concept is one of the terms associated with that concept. The best display is the preferred term in the relevant language or dialect, as specified in the associated language reference set. SNOMED CT synonyms may be case sensitive. SNOMED International does not define terms for expressions. If a SNOMED terminology producer publishes human-readable terms for expressions in an expression repository, this term may be used as the display. Similarly, if a SNOMED terminology producer publishes an official template for generating terms from an expression, a term generated using the template may be used as the display. If no term or description template has been published, the full expression with terms embedded may be used. Note that Display is not intended to contain terms entered by the user that have not been officially published by a SNOMED CT Terminology Producer.

Inactive | Inactive codes are identified using the 'inactive' property (see below)

Subsumption | SNOMED CT Subsumption testing for concepts is based on the |is a| relationship defined by SNOMED CT

Filter Properties | Several filter properties are defined, as described below

This specification publishes a canonical SNOMED CT CodeSystem resource. See also the SNOMED CT Usage Summary.

Note: The SNOMED International glossary explains some of these SNOMED CT specific terms.

4.3.1.0.2 Copyright and Licenses

This specification includes content from SNOMED Clinical Terms® (SNOMED CT®) which is copyright of the International Health Terminology Standards Development Organisation (IHTSDO) (trading as SNOMED International). Implementers of these specifications must have the appropriate SNOMED CT Affiliate license - for more information contact http://www.snomed.org/snomed-ct/get-snomed-ct or info@snomed.org.

4.3.1.0.3 Versions

There is no single distribution that contains all defined SNOMED CT codes in all contexts of use. Instead the International Edition contains all concepts shared and agreed to be internationally relevant and each National Release Centre distributes this International Edition plus additional national content (to extend the international set). Other release authorities may also be designated. The SNOMED CT URI Specification describes how to unambiguously reference a particular version of a SNOMED CT edition:

```
http://snomed.info/sct/[sctid]/version/[YYYYMMDD]
```

where [sctid] is the concept id that identifies the given SNOMED CT edition (based on the identifier of the most dependent module), and "YYYYMMDD" is the date of release. Examples of sctids that identify a specific edition are listed here .

Note that many implementations are in the habit of simply using the date of release in the form YYYYMMDD (e.g. "20140531"), and assuming that the edition is known. However, this is not always safe, so implementations that populate the version element SHOULD use the URI form.

Servers SHOULD regard provision of the date only for the version (without an sctid) as an error, and refuse to process the interaction or operation. At minimum the URI SHOULD contain the sctid of the SNOMED CT distribution:

```
http://snomed.info/sct/[sctid]
```

Implementers must note, if no version URI is provided when utilizing SNOMED CT, the Terminology Service may default to the most recent version of the SNOMED CT International Edition available on the service (or the latest available of another edition that may be preferred for the locale). Further, if the date of release is not provided, the Terminology Service may default to the most recent version of the named SNOMED CT distribution (e.g. 32506021000036107 for Australia).

In terms of the CodeSystem resource definitions, this means that SNOMED CT is distributed as a set of overlapping fragments that contain different parts of the entire code system that is SNOMED CT. Terminology servers and users always need to be aware of which fragment(s) are in use at any time, though implementations can sometimes safely assume that a national distribution is the only scope. Note that

because of SNOMED CT's large size, there is no expectation that implementers will ever use a CodeSystem resource instead of the SNOMED CT RF2 format as a way to distribute SNOMED CT content.

4.3.1.0.4 Display Terms for Specific Languages

In the ValueSet resource any number of terms ('designations ') in additional languages and dialects can be specified for a particular concept in a value set definition using the ValueSet.compose.include.concept.designation element. The language is specified as a BCP-47 language code as required by the 'designation.language ' element, with the value taken from the 'languageCode' field of the RF2 Descriptions file ('languageCode' is ISO-639-1, a subset of BCP-47). The type of the term (e.g., the SNOMED CT code for "Fully specified name", "Synonym" or "Definition") can be specified in 'designation.use '.

[Note that ValueSet.compose.include.concept is only used when the value set is defined extensionally (i.e. as an enumerated list of concepts). For intensionally-defined value sets (i.e. using one or more filters) additional terms could be added using CodeSystem.concept.designation, as noted below.]

The CodeSystem resource can also similarly be used to specify additional terms ('designations ') for a concept using the CodeSystem.concept.designation element (the additional terms may be from a published national or other localized SNOMED CT edition or provided in a code system supplement). If supported by the terminology server, the additional terms are available to be returned in a value set expansion (controlled by the $expand operation 'includeDesignations' input parameter).

4.3.1.0.5 SNOMED CT Expressions

A SNOMED CT Expression is a structured combination of one or more clinical concepts, stated using Compositional Grammar Syntax . Expressions may optionally contain display terms.

4.3.1.0.6 RDF

The SNOMED International URI specification uses the namespace http://snomed.info/sct for the code system, and the URI http://snomed.info/id for the individual concepts in the code system. This means that when a SNOMED CT concept is converted from the system::code pair, where the system is http://snomed.info/sct, to the RDF ontological form, the representation is http://snomed.info/id/[concept-id]. Expressions are represented using the URI pattern http://snomed.info/scg/[expression]. Expressions represented in this way SHALL NOT contain whitespace, terms or comments.

4.3.1.0.7 SNOMED CT Properties

In addition to the standard properties, the following properties are defined for SNOMED CT:

Property Name | Data Type | Comments
inactive | boolean | Whether the code is active or not (defaults to false). This is derived from the active column in the Concept file of the RF2 Distribution (by inverting the value).
sufficientlyDefined | boolean | True if the description logic definition of the concept includes sufficient conditions. This is derived from the definitionStatusId value in the Concept file of the RF2 distribution (i.e. If 900000000000073002 |Sufficiently defined concept definition status| then true).
moduleId | code | The SNOMED CT concept id of the module that the concept belongs to.
normalForm | string | Generated Necessary Normal Form expression for the provided code or expression, with terms. The normal form expressions are not suitable for use in subsumption testing.
normalFormTerse | string | Generated Necessary Normal form expression for the provided code or expression, concept ids only. The normal form expressions are not suitable for use in subsumption testing.

SNOMED CT relationships, where the relationship type is subsumed by 410662002 |Concept model attribute|, also automatically become properties. Properties that represent SNOMED CT concept model attributes are referred to using their concept id, rather than their human readable term.

For example, the laterality property is represented using the concept id '272741003', rather than the term 'laterality':

Property Name | Data Type | Comments
272741003 | code | The value of the laterality attribute in the definition of the given code or expression. The equivalent URI for the laterality property is http://snomed.info/id/272741003 (see the code system definition).

Note that when a $lookup operation is performed on a SNOMED CT concept, servers SHALL return the URI for the edition and version being used (see above) in the version property. Other properties are at the discretion of the server and the client.

4.3.1.0.8 SNOMED CT Filters

This section documents the property filters that can be used with the SNOMED CT code system in value set composition statements. For implementer convenience, some of the property filters are documented in terms of the SNOMED CT Expression Constraint Language , but this does not imply that its use is required.

4.3.1.0.8.1 By Subsumption

Description | Select a set of concepts based on subsumption testing
Property Name | concept
Operations Allowed | is-a
Values Allowed | [concept id]

Comments | Includes all concept ids that have a transitive is-a relationship with the concept id provided as the value (including the concept itself)
Example | Administration Methods
SCT ECL | << [concept] (Long syntax: descendantOrSelfOf [concept])

4.3.1.0.8.2 By Reference Set

Description | Select a set of concepts based on their membership of a SNOMED CT reference set
Property Name | concept
Operations Allowed | in
Values Allowed | [concept id]
Comments | Includes all concept ids that are active members of the reference set identified by the concept id provided as the value
SCT ECL | ^ [concept] (Long syntax: memberOf [concept])

4.3.1.0.8.3 By SNOMED Expression Constraint

Description | Select a set of concepts based on a formal expression constraint
Property Name | constraint
Operations Allowed | =
Values Allowed | [expression constraint]
Comments | The result of the filter is the result of executing the given SNOMED CT Expression Constraint . Example: "compose": { "include": [{ "system": "http://snomed.info/sct", "filter": [{ "property": "constraint", "op": "=", "value": "<< 30506011000036107 |Australian product|: 700000101000036108 |hasTP| = 17311000168105 |Panadol|" }] }] }

4.3.1.0.8.4 By whether post-coordination is allowed

Description | Specify whether post-coordination is allowed or not
Property Name | expressions
Operations Allowed | =
Values Allowed | true or false
Comments | Expressions, if allowed, are subject to the same rules as precoordinated concepts. [Note: Simple reference sets do not include expressions.]
Example | Administration Methods
SCT ECL | n/a

4.3.1.0.9 Implicit Value Sets

Implicit value sets are those whose specification can be predicted based on the grammar of the underlying code system, and the known structure of the URL that identifies them. SNOMED CT has two common sets of implicit value sets defined: By Subsumption, and By Reference Set. These implicit value sets do not use complex queries. Implicit value sets can also be defined using an expression constraint. The implicit value set capability allows a single URL to serve as a value set definition, and can serve as the basis for the $expand operation and for other value set references.

If any value set resources exist with an identifier that conforms to the URL patterns specified below, the content of the resource must conform to the template provided. Profiles and other value set references can reference these value sets directly (by reference as a URI, rather than by a literal value set reference).

A SNOMED CT implicit value set URL has two parts:

• The base URL is either http://snomed.info/sct , or the URI for the edition version, in the format specified by SNOMED International in the SNOMED CT URI Specification

• A query portion that specifies the scope of the content

The URL http://snomed.info/sct should be understood to mean an unspecified edition/version. This defines an incomplete value set whose actual membership will depend on the edition used when it is expanded. If no version or edition is specified, the terminology service SHALL use the latest version available for its default edition (or the International Edition, if no other edition is the default).

For the second part of the URL (the query part), the 5 possible values are:

• ?fhir_vs - all concept ids in the edition/version. If the base URI is http://snomed.info/sct , this means all possible SNOMED CT concepts

• ?fhir_vs=isa/[sctid] - all concept ids that are subsumed by the specified concept.

• ?fhir_vs=refset - all concept ids that correspond to reference sets that are explicitly defined in the specified SNOMED CT edition

• ?fhir_vs=refset/[sctid] - all concept ids in the specified reference set

• ?fhir_vs=ecl/[ecl] - all concept ids that match the supplied (URI-encoded) expression constraint

A value set with a URL that follows the pattern "[edition/version]?fhir_vs=isa/[sctid]" follows this template:

```
<ValueSet xmlns="http://hl7.org/fhir">
  <text>
    <status value="generated"/>
    <div xmlns="http://www.w3.org/1999/xhtml">
     [Some HTML that describes this value set as all concepts subsumed by sctid]
    </div>
```

```
  </text>
  <url value="[edition/version]?fhir_vs=isa/[sctid]"/>
  <version value="[edition/version]"/>
  <name value="SNOMED CT Concept [sctid] and descendants"/>
  <description value="All SNOMED CT concepts for [sctid or preferred description]"/>
  <copyright value="This value set includes content from SNOMED CT, which is copyright © 2002+ International Health
    Terminology Standards Development Organisation (SNOMED International), and distributed by agreement between SNOMED
    International and HL7. Implementer use of SNOMED CT is not covered by this agreement"/>
  <status value="active"/>
  <compose>
    <include>
      <system value="http://snomed.info/sct"/>
      <filter>
        <property value="concept"/>
        <op value="is-a"/>
        <value value="[sctid]"/>
      </filter>
    </include>
  </compose>
</ValueSet>
```

The value set with a url that follows the pattern "[edition/version]?fhir_vs=refset" follows this template:

```
<ValueSet xmlns="http://hl7.org/fhir">
  <text>
    <status value="generated"/>
    <div xmlns="http://www.w3.org/1999/xhtml">
     [Some HTML that describes this value set as all concepts with associated reference sets]
    </div>
  </text>
  <url value="[edition/version]?fhir_vs=refset"/>
  <version value="[edition/version]"/>
  <name value="SNOMED CT Reference Sets"/>
  <description value="All SNOMED CT concepts associated with a reference set"/>
  <copyright value="This value set includes content from SNOMED CT, which is copyright © 2002+ International Health
    Terminology Standards Development Organisation (SNOMED International), and distributed by agreement between SNOMED
    International and HL7. Implementer use of SNOMED CT is not covered by this agreement"/>
  <status value="active"/>
  <compose>
    <include>
      <system value="http://snomed.info/sct"/>
      <!-- repeat: one concept element with a code for each concept that has an associated reference set -->
      <concept>
        <code value="[sctid]"/>
      </concept>
      <!-- end repeat -->
    </include>
  </compose>
</ValueSet>
```

For each concept that is associated with a reference set, there will be one 'concept' element with a contained 'code' element that contains the sctid.

A value set with a url that follows the pattern "[edition/version]?fhir_vs=refset/[sctid]" follows this template:

```
<ValueSet xmlns="http://hl7.org/fhir">
  <text>
    <status value="generated"/>
    <div xmlns="http://www.w3.org/1999/xhtml">
     [Some HTML that describes this value set as all concepts in the reference set identified by sctid]
    </div>
  </text>
  <url value="[edition/version]?fhir_vs=refset/[sctid]"/>
  <version value="[edition/version]"/>
  <name value="SNOMED CT Reference Set [sctid]"/>
  <description value="All SNOMED CT concepts in the reference set [sctid or preferred description]"/>
  <copyright value="This value set includes content from SNOMED CT, which is copyright © 2002+ International Health
    Terminology Standards Development Organisation (SNOMED International), and distributed by agreement between SNOMED
    International and HL7. Implementer use of SNOMED CT is not covered by this agreement"/>
  <status value="active"/>
  <compose>
    <include>
      <system value="http://snomed.info/sct"/>
      <filter>
        <property value="concept"/>
        <op value="in"/>
        <value value="[sctid]"/>
      </filter>
    </include>
  </compose>
</ValueSet>
```

A value set with a url that follows the pattern "[edition/version]?fhir_vs=ecl/[ecl]" follows this template:

```
<ValueSet xmlns="http://hl7.org/fhir">
  <text>
    <status value="generated"/>
    <div xmlns="http://www.w3.org/1999/xhtml">
     [Some HTML that describes this value set as all concepts that match the expression constraint ecl]
    </div>
  </text>
  <url value="[edition/version]?fhir_vs=ecl/[ecl]"/>
```

```
  <version value="[edition/version]"/>
  <name value="SNOMED CT Concepts matching [ecl]"/>
  <description value="All SNOMED CT concepts that match the expression constraint [ecl]"/>
  <copyright value="This value set includes content from SNOMED CT, which is copyright © 2002+ International Health
    Terminology Standards Development Organisation (SNOMED International), and distributed by agreement between SNOMED
    International and HL7. Implementer use of SNOMED CT is not covered by this agreement"/>
  <status value="active"/>
  <compose>
    <include>
      <system value="http://snomed.info/sct"/>
      <filter>
        <property value="constraint"/>
        <op value="="/>
        <value value="[ecl]"/>
      </filter>
    </include>
  </compose>
</ValueSet>
```

4.3.1.0.10 Implicit Concept Maps

Implicit concept maps are those whose specification can be predicted based on the grammar and/or content of the underlying code system, and the known structure of the URL that identifies them. This allows a single URL to serve as a concept map definition that defines a mapping between two sets of concepts, and which can serve as the basis for the $translate operation. SNOMED CT has two common sets of implicit concept maps defined:

• Association Reference Sets

• Simple Map Reference Sets

Association Reference Sets are part of the core SNOMED CT distribution. The following standard Association Reference sets can be used for implicit concept maps:

Name	Concept Id	Relationship
POSSIBLY EQUIVALENT TO	900000000000523009	inexact
REPLACED BY	900000000000526001	equivalent
SAME AS	900000000000527005	equal
ALTERNATIVE	900000000000530003	inexact

Simple Map Reference Sets (reference sets which are descendants of 900000000000496009 "Simple map") also define an implicit concept map.

A SNOMED CT implicit concept map URL has two parts:

• The base URL is either http://snomed.info/sct , or the URI for the edition version, in the format specified by SNOMED International in the SNOMED CT URI Specification

• A query portion that specifies the scope of the content

The URL http://snomed.info/sct should be understood to mean an unspecified edition/version. This defines an incomplete concept map whose actual membership will depend on the edition being used. If no version or edition is specified, the terminology service SHALL use the latest version available for its default edition (or the International Edition, if no other edition is the default).

For the second part of the URL (the query part), there is only one possible value:

• ?fhir_cm=[sctid] - where [sctid] is a value from the table above

A concept map with a URL that follows the pattern "[edition/version]?fhir_cm=[sctid]" follows this template, where [name], [sctid] and [relationship] are taken from the table above:

```
<ConceptMap xmlns="http://hl7.org/fhir">
  <text>
    <status value="generated"/>
    <div xmlns="http://www.w3.org/1999/xhtml">
     [Some HTML that describes this concept map]
    </div>
  </text>
  <url value="[edition/version]?fhir_cm=[sctid]"/>
  <version value="[edition/version]"/>
  <name value="SNOMED CT [name] Concept Map"/>
  <description value="The concept map implicitly defined by the [name] Association Reference Set"/>
  <copyright value="This value set includes content from SNOMED CT, which is copyright © 2002+ International Health
    Terminology Standards Development Organisation (SNOMED International), and distributed by agreement between SNOMED
    International and HL7. Implementer use of SNOMED CT is not covered by this agreement"/>
  <status value="active"/>

  <sourceUri value="[edition/version]?fhir_vs"/>
  <targetUri value="[edition/version]?fhir_vs"/>
  <group>  <!-- 0..* Same source and target systems -->
    <source value="http://snomed.info/sct"/>
    <sourceVersion value="[edition/version]"/>
    <target value="http://snomed.info/sct"/>
    <targetVersion value="[edition/version]"/>

    <!-- a mapping for each member of the reference set -->
    <element>
      <code value="[member]"/>
```

```
      <target>
        <code value="[reference set value]"/>
        <equivalence value="[relationship]"/>
      </target>
    </element>
  </group>
</ConceptMap>
```

4.3.1.1 SNOMED CT in FHIR

URL: https://hl7.org/fhir/R4/snomedct-usage.html

4.3.1.1 SNOMED CT in FHIR

FHIR Infrastructure Work Group | Maturity Level: N/A | Standards Status: Informative

This page summarizes the use of SNOMED CT in the base FHIR Specification. It is used by HL7 and IHTSDO to help with SNOMED CT licensing management.

In principle, this base FHIR Specification only uses concepts defined in the International distribution of SNOMED CT, while FHIR implementation guides that use SNOMED CT are generally published by HL7 Affiliates under agreements with National distribution centers. However, there are some US specific codes on this page; HL7 is working with IHTSDO towards remove these from the specification (hopefully they will be elevated to the international SNOMED CT distribution).

4.3.1.1.1 Value Sets

The following value sets reference SNOMED CT. The table lists the value sets,the places they are used, and the binding strengths.

Name | Definition | CLD | Usage

SNOMED CT Additional Dosage Instructions | This value set includes all SNOMED CT Additional Dosage Instructions. | is-a Additional dosage instructions | This value set is not currently used

SNOMED CT Additional Dosage Instructions | This value set includes all SNOMED CT Additional Dosage Instructions. | is-a Additional dosage instructions | This value set is not currently used

SNOMED CT Administration Method Codes | This value set includes some method codes from SNOMED CT - provided as an exemplar | is-a Dosing instruction fragment | Resource: MedicationAdministration.dosage.method (CodeableConcept / Example)

SNOMED CT Administration Method Codes | This value set includes some method codes from SNOMED CT - provided as an exemplar | is-a Dosing instruction fragment | Resource: MedicationAdministration.dosage.method (CodeableConcept / Example)

SNOMED CT Clinical Findings | This value set includes all SNOMED CT Clinical Findings. | is-a Clinical finding | Resource: AdverseEvent.event (CodeableConcept / Example)

SNOMED CT Clinical Findings | This value set includes all SNOMED CT Clinical Findings. | is-a Clinical finding | Resource: AdverseEvent.event (CodeableConcept / Example)

AllergyIntolerance Substance/Product, Condition and Negation Codes | This value set includes concept codes for specific substances/pharmaceutical products, allergy or intolerance conditions, and negation/exclusion codes to specify the absence of specific types of allergies or intolerances. | is-a Propensity to adverse reactions to substance is-a Lactose intolerance is-a Syndrome of carbohydrate intolerance is-a Lysine intolerance is-a Sucrose intolerance is-a Acquired fructose intolerance is-a No known allergy other code systems | Resource: AllergyIntolerance.code (CodeableConcept / Example)

AllergyIntolerance Substance/Product, Condition and Negation Codes | This value set includes concept codes for specific substances/pharmaceutical products, allergy or intolerance conditions, and negation/exclusion codes to specify the absence of specific types of allergies or intolerances. | is-a Propensity to adverse reactions to substance is-a Lactose intolerance is-a Syndrome of carbohydrate intolerance is-a Lysine intolerance is-a Sucrose intolerance is-a Acquired fructose intolerance is-a No known allergy other code systems | Resource: AllergyIntolerance.code (CodeableConcept / Example)

Animal breeds | This example value set defines a set of codes that can be used to indicate breeds of species. | 2370 enumerated concepts | Extension: http://hl7.org/fhir/StructureDefinition/patient-animal: animal (CodeableConcept / Example)

Animal breeds | This example value set defines a set of codes that can be used to indicate breeds of species. | 2370 enumerated concepts | Extension: http://hl7.org/fhir/StructureDefinition/patient-animal: animal (CodeableConcept / Example)

Animal species | This example value set defines a set of codes that can be used to indicate species of animal patients. | 10 enumerated concepts | Extension: http://hl7.org/fhir/StructureDefinition/practitioner-animalSpecies: animalSpecies (CodeableConcept / Example) Extension: http://hl7.org/fhir/StructureDefinition/patient-animal: animal (CodeableConcept / Example)

Animal species | This example value set defines a set of codes that can be used to indicate species of animal patients. | 10 enumerated concepts | Extension: http://hl7.org/fhir/StructureDefinition/practitioner-animalSpecies: animalSpecies (CodeableConcept / Example) Extension: http://hl7.org/fhir/StructureDefinition/patient-animal: animal (CodeableConcept / Example)

SNOMED CT Anatomical Structure for Administration Site Codes | This value set includes Anatomical Structure codes from SNOMED CT - provided as an exemplar. | is-a Anatomical structure | Resource: MedicationAdministration.dosage.site (CodeableConcept / Example) Resource: Dosage.site (CodeableConcept / Example)

SNOMED CT Anatomical Structure for Administration Site Codes | This value set includes Anatomical Structure codes from SNOMED CT - provided as an exemplar. | is-a Anatomical structure | Resource: MedicationAdministration.dosage.site (CodeableConcept / Example) Resource: Dosage.site (CodeableConcept / Example)

SNOMED CT Body Structures | This value set includes all codes from [SNOMED CT](http://snomed.info/sct) where concept is-a 442083009 (Anatomical or acquired body site (body structure)). | is-a Anatomical or acquired body structure | Resource: ServiceRequest.bodySite (CodeableConcept / Example) Profile: ServiceRequest-Genetics: ServiceRequest.bodySite (CodeableConcept / Example) Resource: BodyStructure.location (CodeableConcept / Example) Resource: ImagingStudy.series.bodySite (Coding / Example) Resource: ChargeItem.bodysite (CodeableConcept / Example) Resource: ActivityDefinition.bodySite (CodeableConcept / Example) Profile: ShareableActivityDefinition: ActivityDefinition.bodySite (CodeableConcept / Example) Resource: DeviceUseStatement.bodySite (CodeableConcept / Example) Resource: Specimen.collection.bodySite (CodeableConcept / Example) Resource: Procedure.bodySite (CodeableConcept / Example) Resource: Media.bodySite (CodeableConcept / Example) Resource: Observation.bodySite (CodeableConcept / Example) Profile:

DeviceMetricObservation: Observation.bodySite (CodeableConcept / Example) Profile: Observation-Genetics: Observation.bodySite (CodeableConcept / Example) Profile: VitalSigns: Observation.bodySite (CodeableConcept / Example) Profile: BodyWeight: Observation.bodySite (CodeableConcept / Example) Profile: VitalsPanel: Observation.bodySite (CodeableConcept / Example) Profile: BodyHeight: Observation.bodySite (CodeableConcept / Example) Profile: RespRate: Observation.bodySite (CodeableConcept / Example) Profile: HeartRate: Observation.bodySite (CodeableConcept / Example) Profile: BodyTemp: Observation.bodySite (CodeableConcept / Example) Profile: HeadCircum: Observation.bodySite (CodeableConcept / Example) Profile: OxygenSat: Observation.bodySite (CodeableConcept / Example) Profile: BMI: Observation.bodySite (CodeableConcept / Example) Profile: BP: Observation.bodySite (CodeableConcept / Example) Profile: Cholesterol: Observation.bodySite (CodeableConcept / Example) Profile: Triglyceride: Observation.bodySite (CodeableConcept / Example) Profile: HDLCholesterol: Observation.bodySite (CodeableConcept / Example) Profile: LDLCholesterol: Observation.bodySite (CodeableConcept / Example) Resource: Condition.bodySite (CodeableConcept / Example) Extension: http://hl7.org/fhir/StructureDefinition/openEHR-location: location (CodeableConcept / Extensible)

SNOMED CT Body Structures | This value set includes all codes from [SNOMED CT](http://snomed.info/sct) where concept is-a 442083009 (Anatomical or acquired body site (body structure)). | is-a Anatomical or acquired body structure | Resource: ServiceRequest.bodySite (CodeableConcept / Example) Profile: ServiceRequest-Genetics: ServiceRequest.bodySite (CodeableConcept / Example) Resource: BodyStructure.location (CodeableConcept / Example) Resource: ImagingStudy.series.bodySite (Coding / Example) Resource: ChargeItem.bodysite (CodeableConcept / Example) Resource: ActivityDefinition.bodySite (CodeableConcept / Example) Profile: ShareableActivityDefinition: ActivityDefinition.bodySite (CodeableConcept / Example) Resource: DeviceUseStatement.bodySite (CodeableConcept / Example) Resource: Specimen.collection.bodySite (CodeableConcept / Example) Resource: Procedure.bodySite (CodeableConcept / Example) Resource: Media.bodySite (CodeableConcept / Example) Resource: Observation.bodySite (CodeableConcept / Example) Profile: DeviceMetricObservation: Observation.bodySite (CodeableConcept / Example) Profile: Observation-Genetics: Observation.bodySite (CodeableConcept / Example) Profile: VitalSigns: Observation.bodySite (CodeableConcept / Example) Profile: BodyWeight: Observation.bodySite (CodeableConcept / Example) Profile: VitalsPanel: Observation.bodySite (CodeableConcept / Example) Profile: BodyHeight: Observation.bodySite (CodeableConcept / Example) Profile: RespRate: Observation.bodySite (CodeableConcept / Example) Profile: HeartRate: Observation.bodySite (CodeableConcept / Example) Profile: BodyTemp: Observation.bodySite (CodeableConcept / Example) Profile: HeadCircum: Observation.bodySite (CodeableConcept / Example) Profile: OxygenSat: Observation.bodySite (CodeableConcept / Example) Profile: BMI: Observation.bodySite (CodeableConcept / Example) Profile: BP: Observation.bodySite (CodeableConcept / Example) Profile: Cholesterol: Observation.bodySite (CodeableConcept / Example) Profile: Triglyceride: Observation.bodySite (CodeableConcept / Example) Profile: HDLCholesterol: Observation.bodySite (CodeableConcept / Example) Profile: LDLCholesterol: Observation.bodySite (CodeableConcept / Example) Resource: Condition.bodySite (CodeableConcept / Example) Extension: http://hl7.org/fhir/StructureDefinition/openEHR-location: location (CodeableConcept / Extensible)

Laterality | Laterality: SNOMED-CT concepts for 'left', 'right', and 'bilateral' | 3 enumerated concepts | Resource: ImagingStudy.series.laterality (Coding / Example)

Laterality | Laterality: SNOMED-CT concepts for 'left', 'right', and 'bilateral' | 3 enumerated concepts | Resource: ImagingStudy.series.laterality (Coding / Example)

SNOMED CT Morphologic Abnormalities | This value set includes all codes from [SNOMED CT](http://snomed.info/sct) where concept is-a 442083009 (Anatomical or acquired body site (body structure)). | is-a Abnormal tissue appearance | Resource: BodyStructure.morphology (CodeableConcept / Example)

SNOMED CT Morphologic Abnormalities | This value set includes all codes from [SNOMED CT](http://snomed.info/sct) where concept is-a 442083009 (Anatomical or acquired body site (body structure)). | is-a Abnormal tissue appearance | Resource: BodyStructure.morphology (CodeableConcept / Example)

Bodystructure Location Qualifier | SNOMED-CT concepts modifying the anatomic location | 12 enumerated concepts | Resource: BodyStructure.locationQualifier (CodeableConcept / Example)

Bodystructure Location Qualifier | SNOMED-CT concepts modifying the anatomic location | 12 enumerated concepts | Resource: BodyStructure.locationQualifier (CodeableConcept / Example)

Facility Type Code Value Set | This is the code representing the type of organizational setting where the clinical encounter, service, interaction, or treatment occurred. The value set used for Healthcare Facility Type has been defined by HITSP to be the value set reproduced from HITSP C80 Table 2-147. | 79 enumerated concepts | Resource: DocumentReference.context.facilityType (CodeableConcept / Example)

Facility Type Code Value Set | This is the code representing the type of organizational setting where the clinical encounter, service, interaction, or treatment occurred. The value set used for Healthcare Facility Type has been defined by HITSP to be the value set reproduced from HITSP C80 Table 2-147. | 79 enumerated concepts | Resource: DocumentReference.context.facilityType (CodeableConcept / Example)

Practice Setting Code Value Set | This is the code representing the clinical specialty of the clinician or provider who interacted with, treated, or provided a service to/for the patient. The value set used for clinical specialty has been limited by HITSP to the value set reproduced from HITSP C80 Table 2-149 Clinical Specialty Value Set Definition. | 117 enumerated concepts | Resource: Appointment.specialty (CodeableConcept / Preferred) Resource: DocumentReference.context.practiceSetting (CodeableConcept / Example) Resource: PractitionerRole.specialty (CodeableConcept / Preferred) Resource: Slot.specialty (CodeableConcept / Preferred) Resource: OrganizationAffiliation.specialty (CodeableConcept / Preferred) Resource: HealthcareService.specialty (CodeableConcept / Preferred) Resource: Schedule.specialty (CodeableConcept / Preferred)

Practice Setting Code Value Set | This is the code representing the clinical specialty of the clinician or provider who interacted with, treated, or provided a service to/for the patient. The value set used for clinical specialty has been limited by HITSP to the value set reproduced from HITSP C80 Table 2-149 Clinical Specialty Value Set Definition. | 117 enumerated concepts | Resource: Appointment.specialty (CodeableConcept / Preferred) Resource: DocumentReference.context.practiceSetting (CodeableConcept / Example) Resource: PractitionerRole.specialty (CodeableConcept / Preferred) Resource: Slot.specialty (CodeableConcept / Preferred) Resource: OrganizationAffiliation.specialty (CodeableConcept / Preferred) Resource: HealthcareService.specialty (CodeableConcept / Preferred) Resource: Schedule.specialty (CodeableConcept / Preferred)

Care Plan Activity Outcome | Example codes indicating the outcome of a care plan activity. Note that these are in no way complete and might not even be appropriate for some uses. | is-a Healthcare knowledge finding | Resource: CarePlan.activity.outcomeCodeableConcept (CodeableConcept / Example)

Care Plan Activity Outcome | Example codes indicating the outcome of a care plan activity. Note that these are in no way complete and might not even be appropriate for some uses. | is-a Healthcare knowledge finding | Resource: CarePlan.activity.outcomeCodeableConcept (CodeableConcept / Example)

Care Plan Category | Example codes indicating the category a care plan falls within. Note that these are in no way complete and might not even be appropriate for some uses. | is-a Care plan | Resource: CarePlan.category (CodeableConcept / Example)

Care Plan Category | Example codes indicating the category a care plan falls within. Note that these are in no way complete and might not even be appropriate for some uses. | is-a Care plan | Resource: CarePlan.category (CodeableConcept / Example)

SNOMED CT Clinical Findings | This value set includes all the "Clinical finding" [SNOMED CT](http://snomed.info/sct) codes - concepts where concept is-a 404684003 (Clinical finding (finding)). | is-a Clinical finding | Resource: Goal.description (CodeableConcept / Example) Resource: Goal.outcomeCode (CodeableConcept / Example) Resource: CareTeam.reasonCode (CodeableConcept / Example) Resource: FamilyMemberHistory.reasonCode (CodeableConcept / Example) Profile: FamilyMemberHistory-Genetic: FamilyMemberHistory.reasonCode (CodeableConcept / Example) Resource: Communication.reasonCode (CodeableConcept / Example) Resource: AllergyIntolerance.reaction.manifestation (CodeableConcept / Example) Resource: CarePlan.activity.detail.reasonCode (CodeableConcept / Example) Resource: DiagnosticReport.conclusionCode (CodeableConcept / Example) Profile: LipidProfile: DiagnosticReport.conclusionCode (CodeableConcept / Example) Profile: DiagnosticReport-Genetics: DiagnosticReport.conclusionCode (CodeableConcept / Example) Profile: HLAResult: DiagnosticReport.conclusionCode (CodeableConcept / Example) Resource: PlanDefinition.goal.description (CodeableConcept / Example) Profile: ShareablePlanDefinition: PlanDefinition.goal.description (CodeableConcept / Example) Profile: ComputablePlanDefinition: PlanDefinition.goal.description (CodeableConcept / Example) Profile: CDSHooksServicePlanDefinition: PlanDefinition.goal.description (CodeableConcept / Example)

SNOMED CT Clinical Findings | This value set includes all the "Clinical finding" [SNOMED CT](http://snomed.info/sct) codes - concepts where concept is-a 404684003 (Clinical finding (finding)). | is-a Clinical finding | Resource: Goal.description (CodeableConcept / Example) Resource: Goal.outcomeCode (CodeableConcept / Example) Resource: CareTeam.reasonCode (CodeableConcept / Example) Resource: FamilyMemberHistory.reasonCode (CodeableConcept / Example) Profile: FamilyMemberHistory-Genetic: FamilyMemberHistory.reasonCode (CodeableConcept / Example) Resource: Communication.reasonCode (CodeableConcept / Example) Resource: AllergyIntolerance.reaction.manifestation (CodeableConcept / Example) Resource: CarePlan.activity.detail.reasonCode (CodeableConcept / Example) Resource: DiagnosticReport.conclusionCode (CodeableConcept / Example) Profile: LipidProfile: DiagnosticReport.conclusionCode (CodeableConcept / Example) Profile: DiagnosticReport-Genetics: DiagnosticReport.conclusionCode (CodeableConcept / Example) Profile: HLAResult: DiagnosticReport.conclusionCode (CodeableConcept / Example) Resource: PlanDefinition.goal.description (CodeableConcept / Example) Profile: ShareablePlanDefinition: PlanDefinition.goal.description (CodeableConcept / Example) Profile: ComputablePlanDefinition: PlanDefinition.goal.description (CodeableConcept / Example) Profile: CDSHooksServicePlanDefinition: PlanDefinition.goal.description (CodeableConcept / Example)

Clinical Impression Prognosis | Example value set for clinical impression prognosis. | is-a Prognosis/outlook finding | Resource: ClinicalImpression.prognosisCodeableConcept (CodeableConcept / Example)

Clinical Impression Prognosis | Example value set for clinical impression prognosis. | is-a Prognosis/outlook finding | Resource: ClinicalImpression.prognosisCodeableConcept (CodeableConcept / Example)

Condition Cause Codes | Example value set for Cause of Condition codes | any SCT concept | Extension: http://hl7.org/fhir/StructureDefinition/condition-dueTo: dueTo (CodeableConcept, Reference / Example) Extension: http://hl7.org/fhir/StructureDefinition/workflow-reasonCode: reasonCode (CodeableConcept / Example)

Condition Cause Codes | Example value set for Cause of Condition codes | any SCT concept | Extension: http://hl7.org/fhir/StructureDefinition/condition-dueTo: dueTo (CodeableConcept, Reference / Example) Extension: http://hl7.org/fhir/StructureDefinition/workflow-reasonCode: reasonCode (CodeableConcept / Example)

Condition/Problem/Diagnosis Codes | Example value set for Condition/Problem/Diagnosis codes. | is-a Clinical finding 1 enumerated concepts | Resource: FamilyMemberHistory.condition.code (CodeableConcept / Example) Profile: FamilyMemberHistory-Genetic: FamilyMemberHistory.condition.code (CodeableConcept / Example) Resource: DeviceRequest.reasonCode (CodeableConcept / Example) Resource: ResearchStudy.condition (CodeableConcept / Example) Resource: Procedure.complication (CodeableConcept / Example) Resource: MedicationRequest.reasonCode (CodeableConcept / Example) Resource: MedicationStatement.reasonCode (CodeableConcept / Example) Resource: Condition.code (CodeableConcept / Example) Resource: ClinicalImpression.finding.itemCodeableConcept (CodeableConcept / Example) Resource: PlanDefinition.goal.addresses (CodeableConcept / Example) Profile: ShareablePlanDefinition: PlanDefinition.goal.addresses (CodeableConcept / Example) Profile: ComputablePlanDefinition: PlanDefinition.goal.addresses (CodeableConcept / Example) Profile: CDSHooksServicePlanDefinition: PlanDefinition.goal.addresses (CodeableConcept / Example)

Condition/Problem/Diagnosis Codes | Example value set for Condition/Problem/Diagnosis codes. | is-a Clinical finding 1 enumerated concepts | Resource: FamilyMemberHistory.condition.code (CodeableConcept / Example) Profile: FamilyMemberHistory-Genetic: FamilyMemberHistory.condition.code (CodeableConcept / Example) Resource: DeviceRequest.reasonCode (CodeableConcept / Example) Resource: ResearchStudy.condition (CodeableConcept / Example) Resource: Procedure.complication (CodeableConcept / Example) Resource: MedicationRequest.reasonCode (CodeableConcept / Example) Resource: MedicationStatement.reasonCode (CodeableConcept / Example) Resource: Condition.code (CodeableConcept / Example) Resource: ClinicalImpression.finding.itemCodeableConcept (CodeableConcept / Example) Resource: PlanDefinition.goal.addresses (CodeableConcept / Example) Profile: ShareablePlanDefinition: PlanDefinition.goal.addresses (CodeableConcept / Example) Profile: ComputablePlanDefinition: PlanDefinition.goal.addresses (CodeableConcept / Example) Profile: CDSHooksServicePlanDefinition: PlanDefinition.goal.addresses (CodeableConcept / Example)

Condition Outcome Codes | Example value set for condition outcomes. | is-a Clinical finding | Resource: FamilyMemberHistory.condition.outcome (CodeableConcept / Example) Profile: FamilyMemberHistory-Genetic: FamilyMemberHistory.condition.outcome (CodeableConcept / Example) Extension: http://hl7.org/fhir/StructureDefinition/condition-outcome: outcome (CodeableConcept / Example)

Condition Outcome Codes | Example value set for condition outcomes. | is-a Clinical finding | Resource: FamilyMemberHistory.condition.outcome (CodeableConcept / Example) Profile: FamilyMemberHistory-Genetic: FamilyMemberHistory.condition.outcome (CodeableConcept / Example) Extension: http://hl7.org/fhir/StructureDefinition/condition-outcome: outcome (CodeableConcept / Example)

Condition Predecessor Codes | Example value set for condition predecessor codes. | any SCT concept | Extension: http://hl7.org/fhir/StructureDefinition/condition-occurredFollowing: occurredFollowing (CodeableConcept, Reference / Example)

Condition Predecessor Codes | Example value set for condition predecessor codes. | any SCT concept | Extension: http://hl7.org/fhir/StructureDefinition/condition-occurredFollowing: occurredFollowing (CodeableConcept, Reference / Example)

Condition/Diagnosis Severity | Preferred value set for Condition/Diagnosis severity grading. | 3 enumerated concepts | Resource: Condition.severity (CodeableConcept / Preferred) Extension: http://hl7.org/fhir/StructureDefinition/familymemberhistory-severity: severity (CodeableConcept / Example)

Condition/Diagnosis Severity | Preferred value set for Condition/Diagnosis severity grading. | 3 enumerated concepts | Resource: Condition.severity (CodeableConcept / Preferred) Extension: http://hl7.org/fhir/StructureDefinition/familymemberhistory-severity: severity (CodeableConcept / Example)

Condition Stage | Example value set for stages of cancer and other conditions. | is-a Tumour stage finding | Resource: Condition.stage.summary (CodeableConcept / Example)

Condition Stage | Example value set for stages of cancer and other conditions. | is-a Tumour stage finding | Resource: Condition.stage.summary (CodeableConcept / Example)

Condition Stage Type | Example value set for the type of stages of cancer and other conditions | 1 enumerated concepts 1 enumerated concepts is-a Staging and scales | Resource: Condition.stage.type (CodeableConcept / Example)

Condition Stage Type | Example value set for the type of stages of cancer and other conditions | 1 enumerated concepts 1 enumerated concepts is-a Staging and scales | Resource: Condition.stage.type (CodeableConcept / Example)

Fluid Consistency Type Codes | FluidConsistencyType : Codes used to represent the consistency of fluids and liquids provided to the patient. This value set includes concepts from [SNOMED CT](http://snomed.info/sct)(US Extension) where concept is a 435681000124103 (Dietary liquid consistency diet (regime/therapy)). It is provided as a suggestive example. | 4 enumerated concepts | Resource: NutritionOrder.oralDiet.fluidConsistencyType (CodeableConcept / Example)

Fluid Consistency Type Codes | FluidConsistencyType : Codes used to represent the consistency of fluids and liquids provided to the patient. This value set includes concepts from [SNOMED CT](http://snomed.info/sct)(US Extension) where concept is a 435681000124103 (Dietary liquid consistency diet (regime/therapy)). It is provided as a suggestive example. | 4 enumerated concepts | Resource: NutritionOrder.oralDiet.fluidConsistencyType (CodeableConcept / Example)

Types of material for specimen containers | This value set includes SNOMED CT codes for materials that specimen containers are made of | 3 enumerated concepts | Resource: SpecimenDefinition.typeTested.container.material (CodeableConcept / Example)

Types of material for specimen containers | This value set includes SNOMED CT codes for materials that specimen containers are made of | 3 enumerated concepts | Resource: SpecimenDefinition.typeTested.container.material (CodeableConcept / Example)

DataElement SDC Object Class | The allowed codes for identifying the ISO 11179 ObjectClass for a particular data element if intended for registration/use within the U.S. Structured Data Capture (SDC) project. | any SCT concept other code systems | Extension: http://hl7.org/fhir/StructureDefinition/11179-objectClass: objectClass (Coding / Example)

DataElement SDC Object Class | The allowed codes for identifying the ISO 11179 ObjectClass for a particular data element if intended for registration/use within the U.S. Structured Data Capture (SDC) project. | any SCT concept other code systems | Extension: http://hl7.org/fhir/StructureDefinition/11179-objectClass: objectClass (Coding / Example)

DataElement SDC Object Class | The allowed codes for identifying the ISO 11179 ObjectClass Property for a particular data element if intended for registration/use within the U.S. Structured Data Capture (SDC) project. | any SCT concept other code systems | Extension: http://hl7.org/fhir/StructureDefinition/11179-objectClassProperty: objectClassProperty (Coding / Example)

DataElement SDC Object Class | The allowed codes for identifying the ISO 11179 ObjectClass Property for a particular data element if intended for registration/use within the U.S. Structured Data Capture (SDC) project. | any SCT concept other code systems | Extension: http://hl7.org/fhir/StructureDefinition/11179-objectClassProperty: objectClassProperty (Coding / Example)

Designation Use | Details of how a designation would be used | 2 enumerated concepts | Resource: ValueSet.compose.include.concept.designation.use (Coding / Extensible) Profile: ShareableValueSet: ValueSet.compose.include.concept.designation.use (Coding / Extensible) Resource: CodeSystem.concept.designation.use (Coding / Extensible) Profile: ShareableCodeSystem: CodeSystem.concept.designation.use (Coding / Extensible)

Designation Use | Details of how a designation would be used | 2 enumerated concepts | Resource: ValueSet.compose.include.concept.designation.use (Coding / Extensible) Profile: ShareableValueSet: ValueSet.compose.include.concept.designation.use (Coding / Extensible) Resource: CodeSystem.concept.designation.use (Coding / Extensible) Profile: ShareableCodeSystem: CodeSystem.concept.designation.use (Coding / Extensible)

Procedure Device Action Codes | Example codes indicating the change that happened to the device during the procedure. Note that these are in no way complete and might not even be appropriate for some uses. | is-a Action | Resource: Procedure.focalDevice.action (CodeableConcept / Preferred)

Procedure Device Action Codes | Example codes indicating the change that happened to the device during the procedure. Note that these are in no way complete and might not even be appropriate for some uses. | is-a Action | Resource: Procedure.focalDevice.action (CodeableConcept / Preferred)

FHIR Device Types | Codes used to identify medical devices. Includes concepts from SNOMED CT (http://www.snomed.org/) where concept is-a 49062001 (Device) and is provided as a suggestive example. | is-a Device | Resource: ChargeItem.product[x] (Reference(Device|Medication|Substance)|CodeableConcept / Example) Resource: DeviceRequest.code[x] (Reference(Device)|CodeableConcept / Example) Resource: Procedure.usedCode (CodeableConcept / Example) Resource: DeviceDefinition.type (CodeableConcept / Example) Extension: http://hl7.org/fhir/StructureDefinition/observation-deviceCode: deviceCode (CodeableConcept / Example)

FHIR Device Types | Codes used to identify medical devices. Includes concepts from SNOMED CT (http://www.snomed.org/) where concept is-a 49062001 (Device) and is provided as a suggestive example. | is-a Device | Resource: ChargeItem.product[x] (Reference(Device|Medication|Substance)|CodeableConcept / Example) Resource: DeviceRequest.code[x] (Reference(Device)|CodeableConcept / Example) Resource: Procedure.usedCode (CodeableConcept / Example) Resource: DeviceDefinition.type (CodeableConcept / Example) Extension: http://hl7.org/fhir/StructureDefinition/observation-deviceCode: deviceCode (CodeableConcept / Example)

Device Type | Codes used to identify medical devices. Includes concepts from SNOMED CT (http://www.snomed.org/) where concept is-a 49062001 (Device) and is provided as a suggestive example. | is-a Device | Resource: Device.type (CodeableConcept / Example)

Device Type | Codes used to identify medical devices. Includes concepts from SNOMED CT (http://www.snomed.org/) where concept is-a 49062001 (Device) and is provided as a suggestive example. | is-a Device | Resource: Device.type (CodeableConcept / Example)

Diagnostic attachment type | Diagnostic Attachment Type codes from [SNOMED CT](http://snomed.info/sct) where concept is-a 182836005 (Review of medication (procedure)) or is-a 404684003 (Clinical finding (finding)) | is-a Medication review is-a Clinical finding | Extension: http://hl7.org/fhir/StructureDefinition/DiagnosticReport-geneticsReferences: References (CodeableConcept / Example)

Diagnostic attachment type | Diagnostic Attachment Type codes from [SNOMED CT](http://snomed.info/sct) where concept is-a 182836005 (Review of medication (procedure)) or is-a 404684003 (Clinical finding (finding)) | is-a Medication review is-a Clinical finding | Extension: http://hl7.org/fhir/StructureDefinition/DiagnosticReport-geneticsReferences: References (CodeableConcept / Example)

Diet Codes | Codes that can be used to indicate the type of food being ordered for a patient. This value set is provided as a suggestive example. It includes codes from [SNOMED CT](http://snomed.info/sct) where concept is-a 182922004 (Dietary regime (regime/therapy)) | is-a Dietary regime | Resource: NutritionOrder.oralDiet.type (CodeableConcept / Example)

Diet Codes | Codes that can be used to indicate the type of food being ordered for a patient. This value set is provided as a suggestive example. It includes codes from [SNOMED CT](http://snomed.info/sct) where concept is-a 182922004 (Dietary regime (regime/therapy)) | is-a Dietary regime | Resource: NutritionOrder.oralDiet.type (CodeableConcept / Example)

Encounter Reason Codes | This examples value set defines the set of codes that can be used to indicate reasons for an encounter. | is-a Clinical finding is-a Procedure is-a Context-dependent categories is-a Events | Resource: Appointment.reasonCode (CodeableConcept / Preferred) Resource: Encounter.reasonCode (CodeableConcept / Preferred)

Encounter Reason Codes | This examples value set defines the set of codes that can be used to indicate reasons for an encounter. | is-a Clinical finding is-a Procedure is-a Context-dependent categories is-a Events | Resource: Appointment.reasonCode (CodeableConcept / Preferred) Resource: Encounter.reasonCode (CodeableConcept / Preferred)

Enteral Formula Type Codes | EnteralFormulaType : Codes for type of enteral formula to be administered to patient. This value set is composed of SNOMED CT (US Extension) Concepts from SCTID 470581016 (Enteral+supplement feeds hierarchy (product)) and is provided as a suggestive example. | 36 enumerated concepts | Resource: NutritionOrder.enteralFormula.baseFormulaType (CodeableConcept / Example)

Enteral Formula Type Codes | EnteralFormulaType : Codes for type of enteral formula to be administered to patient. This value set is composed of SNOMED CT (US Extension) Concepts from SCTID 470581016 (Enteral+supplement feeds hierarchy (product)) and is provided as a suggestive example. | 36 enumerated concepts | Resource: NutritionOrder.enteralFormula.baseFormulaType (CodeableConcept / Example)

Feeding Device Codes | Materials used or needed to feed the patient. | is-a Eating/Drinking assistive device other code systems | Extension: http://hl7.org/fhir/StructureDefinition/nutritionorder-adaptiveFeedingDevice: adaptiveFeedingDevice (CodeableConcept / Example)

Feeding Device Codes | Materials used or needed to feed the patient. | is-a Eating/Drinking assistive device other code systems | Extension: http://hl7.org/fhir/StructureDefinition/nutritionorder-adaptiveFeedingDevice: adaptiveFeedingDevice (CodeableConcept / Example)

Flag Code | Example list of detail codes for flagged issues. (Not complete or necessarily appropriate.) | is-a Clinical finding | Resource: Flag.code (CodeableConcept / Example)

Flag Code | Example list of detail codes for flagged issues. (Not complete or necessarily appropriate.) | is-a Clinical finding | Resource: Flag.code (CodeableConcept / Example)

Focal Subject Codes | Example value set composed from SNOMED CT and HL7 V3 codes for observation targets such as donor, fetus or spouse. As use cases are discovered, more values may be added. | 1 enumerated concepts other code systems | Extension: http://hl7.org/fhir/StructureDefinition/observation-focusCode: focusCode (CodeableConcept / Example)

Focal Subject Codes | Example value set composed from SNOMED CT and HL7 V3 codes for observation targets such as donor, fetus or spouse. As use cases are discovered, more values may be added. | 1 enumerated concepts other code systems | Extension: http://hl7.org/fhir/StructureDefinition/observation-focusCode: focusCode (CodeableConcept / Example)

Food Type Codes | This value set represents codes for types of foods and is provided as a suggestive example. It include codes from [SNOMED CT](http://snomed.info/sct) where concept is-a 255620007 (Foods (substance)). | is-a Foods | Resource: NutritionOrder.excludeFoodModifier (CodeableConcept / Example)

Food Type Codes | This value set represents codes for types of foods and is provided as a suggestive example. It include codes from [SNOMED CT](http://snomed.info/sct) where concept is-a 255620007 (Foods (substance)). | is-a Foods | Resource: NutritionOrder.excludeFoodModifier (CodeableConcept / Example)

Goal start event | Identifies types of events that might trigger the start of a goal. | 4 enumerated concepts | Resource: Goal.start[x] (date|CodeableConcept / Example) Resource: PlanDefinition.goal.start (CodeableConcept / Example) Profile: ShareablePlanDefinition: PlanDefinition.goal.start (CodeableConcept / Example) Profile: ComputablePlanDefinition: PlanDefinition.goal.start (CodeableConcept / Example) Profile: CDSHooksServicePlanDefinition: PlanDefinition.goal.start (CodeableConcept / Example)

Goal start event | Identifies types of events that might trigger the start of a goal. | 4 enumerated concepts | Resource: Goal.start[x] (date|CodeableConcept / Example) Resource: PlanDefinition.goal.start (CodeableConcept / Example) Profile: ShareablePlanDefinition: PlanDefinition.goal.start (CodeableConcept / Example) Profile: ComputablePlanDefinition: PlanDefinition.goal.start (CodeableConcept / Example) Profile: CDSHooksServicePlanDefinition: PlanDefinition.goal.start (CodeableConcept / Example)

Immunization Evaluation Target Disease Codes | The value set to instantiate this attribute should be drawn from a terminologically robust code system that consists of or contains concepts to support describing the disease that the evaluation is against. This value set is provided as a suggestive example and includes the SNOMED CT concepts from the 64572001 (Disease) hierarchy. | 9 enumerated concepts | Resource: ImmunizationEvaluation.targetDisease (CodeableConcept / Example)

Immunization Evaluation Target Disease Codes | The value set to instantiate this attribute should be drawn from a terminologically robust code system that consists of or contains concepts to support describing the disease that the evaluation is against. This value set is provided as a suggestive example and includes the SNOMED CT concepts from the 64572001 (Disease) hierarchy. | 9 enumerated concepts | Resource: ImmunizationEvaluation.targetDisease (CodeableConcept / Example)

Immunization Reason Codes | The value set to instantiate this attribute should be drawn from a terminologically robust code system that consists of or contains concepts to support describing the reason why a dose of vaccine was administered. This value set is provided as a suggestive example. | 2 enumerated concepts | Resource: Immunization.reasonCode (CodeableConcept / Example)

Immunization Reason Codes | The value set to instantiate this attribute should be drawn from a terminologically robust code system that consists of or contains concepts to support describing the reason why a dose of vaccine was administered. This value set is provided as a suggestive example. | 2 enumerated concepts | Resource: Immunization.reasonCode (CodeableConcept / Example)

Immunization Recommendation Reason Codes | The value set to instantiate this attribute should be drawn from a terminologically robust code system that consists of or contains concepts to support describing the reasons why a given recommendation status is assigned. This value set is provided as a suggestive example and includes SNOMED CT concepts. | 2 enumerated concepts | Resource: ImmunizationRecommendation.recommendation.forecastReason (CodeableConcept / Example)

Immunization Recommendation Reason Codes | The value set to instantiate this attribute should be drawn from a terminologically robust code system that consists of or contains concepts to support describing the reasons why a given recommendation status is assigned. This value set is provided as a suggestive example and includes SNOMED CT concepts. | 2 enumerated concepts | Resource: ImmunizationRecommendation.recommendation.forecastReason (CodeableConcept / Example)

Immunization Recommendation Target Disease Codes | The value set to instantiate this attribute should be drawn from a terminologically robust code system that consists of or contains concepts to support describing the disease targeted by a vaccination recommendation. This value set is provided as a suggestive example and includes the SNOMED CT concepts from the 64572001 (Disease) hierarchy. | 9 enumerated concepts | Resource: ImmunizationRecommendation.recommendation.targetDisease (CodeableConcept / Example)

Immunization Recommendation Target Disease Codes | The value set to instantiate this attribute should be drawn from a terminologically robust code system that consists of or contains concepts to support describing the disease targeted by a

vaccination recommendation. This value set is provided as a suggestive example and includes the SNOMED CT concepts from the 64572001 (Disease) hierarchy. | 9 enumerated concepts | Resource: ImmunizationRecommendation.recommendation.targetDisease (CodeableConcept / Example)

Immunization Status Reason Codes | The value set to instantiate this attribute should be drawn from a terminologically robust code system that consists of or contains concepts to support describing the reason why a dose of vaccine was not administered. This value set is provided as a suggestive example. | is-a Immunization consent not given other code systems | Resource: Immunization.statusReason (CodeableConcept / Example)

Immunization Status Reason Codes | The value set to instantiate this attribute should be drawn from a terminologically robust code system that consists of or contains concepts to support describing the reason why a dose of vaccine was not administered. This value set is provided as a suggestive example. | is-a Immunization consent not given other code systems | Resource: Immunization.statusReason (CodeableConcept / Example)

Immunization Target Disease Codes | The value set to instantiate this attribute should be drawn from a terminologically robust code system that consists of or contains concepts to support describing the disease that the dose is being administered against. This value set is provided as a suggestive example and includes the SNOMED CT concepts from the 64572001 (Disease) hierarchy. | 9 enumerated concepts | Resource: Immunization.protocolApplied.targetDisease (CodeableConcept / Example)

Immunization Target Disease Codes | The value set to instantiate this attribute should be drawn from a terminologically robust code system that consists of or contains concepts to support describing the disease that the dose is being administered against. This value set is provided as a suggestive example and includes the SNOMED CT concepts from the 64572001 (Disease) hierarchy. | 9 enumerated concepts | Resource: Immunization.protocolApplied.targetDisease (CodeableConcept / Example)

Investigation Type | Example value set for investigation type. | 2 enumerated concepts | Resource: ClinicalImpression.investigation.code (CodeableConcept / Example)

Investigation Type | Example value set for investigation type. | 2 enumerated concepts | Resource: ClinicalImpression.investigation.code (CodeableConcept / Example)

Manifestation and Symptom Codes | Example value set for Manifestation and Symptom codes. | is-a Clinical finding | Resource: Condition.evidence.code (CodeableConcept / Example) Resource: DetectedIssue.evidence.code (CodeableConcept / Example)

Manifestation and Symptom Codes | Example value set for Manifestation and Symptom codes. | is-a Clinical finding | Resource: Condition.evidence.code (CodeableConcept / Example) Resource: DetectedIssue.evidence.code (CodeableConcept / Example)

Media Collection View/Projection | Codes defined in SNOMED CT that can be used to record Media Recording views. | is-a Projection | Resource: Media.view (CodeableConcept / Example)

Media Collection View/Projection | Codes defined in SNOMED CT that can be used to record Media Recording views. | is-a Projection | Resource: Media.view (CodeableConcept / Example)

SNOMED CT Medication As Needed Reason Codes | This value set includes all clinical findings from SNOMED CT - provided as an exemplar value set. | is-a Clinical finding | Resource: ServiceRequest.asNeeded[x] (boolean|CodeableConcept / Example) Profile: ServiceRequest-Genetics: ServiceRequest.asNeeded[x] (boolean, CodeableConcept / Example)

SNOMED CT Medication As Needed Reason Codes | This value set includes all clinical findings from SNOMED CT - provided as an exemplar value set. | is-a Clinical finding | Resource: ServiceRequest.asNeeded[x] (boolean|CodeableConcept / Example) Profile: ServiceRequest-Genetics: ServiceRequest.asNeeded[x] (boolean, CodeableConcept / Example)

SNOMED CT Medication Codes | This value set includes all drug or medicament substance codes and all pharmaceutical/biologic products from SNOMED CT - provided as an exemplar value set. | is-a Drug or medicament is-a Pharmaceutical / biologic product is-a Immunologic substance | Resource: ActivityDefinition.product[x] (Reference(Medication|Substance)|CodeableConcept / Example) Profile: ShareableActivityDefinition: ActivityDefinition.product[x] (Reference, CodeableConcept / Example) Resource: CarePlan.activity.detail.product[x] (CodeableConcept|Reference(Medication|Substance) / Example) Resource: MedicationRequest.medication[x] (CodeableConcept|Reference(Medication) / Example) Resource: MedicationAdministration.medication[x] (CodeableConcept|Reference(Medication) / Example) Resource: MedicationStatement.medication[x] (CodeableConcept|Reference(Medication) / Example) Resource: MedicationDispense.medication[x] (CodeableConcept|Reference(Medication) / Example) Resource: MedicationKnowledge.code (CodeableConcept / Example)

SNOMED CT Medication Codes | This value set includes all drug or medicament substance codes and all pharmaceutical/biologic products from SNOMED CT - provided as an exemplar value set. | is-a Drug or medicament is-a Pharmaceutical / biologic product is-a Immunologic substance | Resource: ActivityDefinition.product[x] (Reference(Medication|Substance)|CodeableConcept / Example) Profile: ShareableActivityDefinition: ActivityDefinition.product[x] (Reference, CodeableConcept / Example) Resource: CarePlan.activity.detail.product[x] (CodeableConcept|Reference(Medication|Substance) / Example) Resource: MedicationRequest.medication[x] (CodeableConcept|Reference(Medication) / Example) Resource: MedicationAdministration.medication[x] (CodeableConcept|Reference(Medication) / Example) Resource: MedicationStatement.medication[x] (CodeableConcept|Reference(Medication) / Example) Resource: MedicationDispense.medication[x] (CodeableConcept|Reference(Medication) / Example) Resource: MedicationKnowledge.code (CodeableConcept / Example)

SNOMED CT Form Codes | This value set includes all dose form codes from SNOMED CT - provided as an exemplar. | is-a Drug dose form | Resource: MedicationKnowledge.doseForm (CodeableConcept / Example)

SNOMED CT Form Codes | This value set includes all dose form codes from SNOMED CT - provided as an exemplar. | is-a Drug dose form | Resource: MedicationKnowledge.doseForm (CodeableConcept / Example)

Texture Modified Food Type Codes | TextureModifiedFoodType: Codes for types of foods that are texture-modified. This value set is composed SNOMED CT Concepts from SCTID 255620007 Foods (substance) and is provided as a suggestive example. | 14 enumerated concepts | Resource: NutritionOrder.oralDiet.texture.foodType (CodeableConcept / Example)

Texture Modified Food Type Codes | TextureModifiedFoodType: Codes for types of foods that are texture-modified. This value set is composed SNOMED CT Concepts from SCTID 255620007 Foods (substance) and is provided as a suggestive example. | 14 enumerated concepts | Resource: NutritionOrder.oralDiet.texture.foodType (CodeableConcept / Example)

Nutrient Modifier Codes | NutrientModifier : Codes for types of nutrients that are being modified such as carbohydrate or sodium. This value set includes codes from [SNOMED CT](http://snomed.info/sct) where concept is-a 226355009 (Nutrients(substance)), and the concepts for Sodium, Potassium and Fluid. This is provided as a suggestive example. | 3 enumerated concepts is-a Nutrients | Resource: NutritionOrder.oralDiet.nutrient.modifier (CodeableConcept / Example)

Nutrient Modifier Codes | NutrientModifier : Codes for types of nutrients that are being modified such as carbohydrate or sodium. This value set includes codes from [SNOMED CT](http://snomed.info/sct) where concept is-a 226355009 (Nutrients(substance)), and the concepts for Sodium, Potassium and Fluid. This is provided as a suggestive example. | 3 enumerated concepts is-a Nutrients | Resource: NutritionOrder.oralDiet.nutrient.modifier (CodeableConcept / Example)

Observation Methods | Observation Method codes from [SNOMED CT](http://snomed.info/sct) where concept is-a 272394005 (Technique (qualifier value)) or is-a 129264002 (Action (qualifier value)) or is-a 386053000 (Evaluation procedure(procedure)) |

is-a Technique is-a Action is-a Patient evaluation procedure | Resource: ObservationDefinition.method (CodeableConcept / Example) Profile: DeviceMetricObservation: Observation.method (CodeableConcept / Example) Profile: Observation-Genetics: Observation.method (CodeableConcept / Example) Profile: VitalSigns: Observation.method (CodeableConcept / Example) Profile: BodyWeight: Observation.method (CodeableConcept / Example) Profile: VitalsPanel: Observation.method (CodeableConcept / Example) Profile: BodyHeight: Observation.method (CodeableConcept / Example) Profile: RespRate: Observation.method (CodeableConcept / Example) Profile: HeartRate: Observation.method (CodeableConcept / Example) Profile: BodyTemp: Observation.method (CodeableConcept / Example) Profile: HeadCircum: Observation.method (CodeableConcept / Example) Profile: OxygenSat: Observation.method (CodeableConcept / Example) Profile: BMI: Observation.method (CodeableConcept / Example) Profile: BP: Observation.method (CodeableConcept / Example) Profile: Cholesterol: Observation.method (CodeableConcept / Example) Profile: Triglyceride: Observation.method (CodeableConcept / Example) Profile: HDLCholesterol: Observation.method (CodeableConcept / Example) Profile: LDLCholesterol: Observation.method (CodeableConcept / Example)

Observation Methods | Observation Method codes from [SNOMED CT](http://snomed.info/sct) where concept is-a 272394005 (Technique (qualifier value)) or is-a 129264002 (Action (qualifier value)) or is-a 386053000 (Evaluation procedure(procedure)) | is-a Technique is-a Action is-a Patient evaluation procedure | Resource: ObservationDefinition.method (CodeableConcept / Example) Profile: DeviceMetricObservation: Observation.method (CodeableConcept / Example) Profile: Observation-Genetics: Observation.method (CodeableConcept / Example) Profile: VitalSigns: Observation.method (CodeableConcept / Example) Profile: BodyWeight: Observation.method (CodeableConcept / Example) Profile: VitalsPanel: Observation.method (CodeableConcept / Example) Profile: BodyHeight: Observation.method (CodeableConcept / Example) Profile: RespRate: Observation.method (CodeableConcept / Example) Profile: HeartRate: Observation.method (CodeableConcept / Example) Profile: BodyTemp: Observation.method (CodeableConcept / Example) Profile: HeadCircum: Observation.method (CodeableConcept / Example) Profile: OxygenSat: Observation.method (CodeableConcept / Example) Profile: BMI: Observation.method (CodeableConcept / Example) Profile: BP: Observation.method (CodeableConcept / Example) Profile: Cholesterol: Observation.method (CodeableConcept / Example) Profile: Triglyceride: Observation.method (CodeableConcept / Example) Profile: HDLCholesterol: Observation.method (CodeableConcept / Example) Profile: LDLCholesterol: Observation.method (CodeableConcept / Example)

Participant Roles | Roles of participants that may be included in a care team. Defined as: Is a Person, Healthcare professional (occupation) or Healthcare related organization (qualifier value). | is-a Person is-a Healthcare professional is-a Healthcare related organisation | Resource: ServiceRequest.performerType (CodeableConcept / Example) Profile: ServiceRequest-Genetics: ServiceRequest.performerType (CodeableConcept / Example) Resource: CareTeam.participant.role (CodeableConcept / Example) Resource: DeviceRequest.performerType (CodeableConcept / Example)

Participant Roles | Roles of participants that may be included in a care team. Defined as: Is a Person, Healthcare professional (occupation) or Healthcare related organization (qualifier value). | is-a Person is-a Healthcare professional is-a Healthcare related organisation | Resource: ServiceRequest.performerType (CodeableConcept / Example) Profile: ServiceRequest-Genetics: ServiceRequest.performerType (CodeableConcept / Example) Resource: CareTeam.participant.role (CodeableConcept / Example) Resource: DeviceRequest.performerType (CodeableConcept / Example)

Procedure Performer Role Codes | This example value set defines the set of codes that can be used to indicate a role of a procedure performer. | is-a Healthcare professional | Resource: ChargeItem.performer.function (CodeableConcept / Example) Resource: Task.performerType (CodeableConcept / Preferred) Resource: Procedure.performer.function (CodeableConcept / Example) Resource: MedicationRequest.performerType (CodeableConcept / Example)

Procedure Performer Role Codes | This example value set defines the set of codes that can be used to indicate a role of a procedure performer. | is-a Healthcare professional | Resource: ChargeItem.performer.function (CodeableConcept / Example) Resource: Task.performerType (CodeableConcept / Preferred) Resource: Procedure.performer.function (CodeableConcept / Example) Resource: MedicationRequest.performerType (CodeableConcept / Example)

Practitioner role | This example value set defines a set of codes that can be used to indicate the role of a Practitioner. | is-a Healthcare professional other code systems | Resource: PractitionerRole.code (CodeableConcept / Example)

Practitioner role | This example value set defines a set of codes that can be used to indicate the role of a Practitioner. | is-a Healthcare professional other code systems | Resource: PractitionerRole.code (CodeableConcept / Example)

Patient preparation prior specimen collection | Checks on the patient prior specimen collection. All SNOMED CT concepts descendants of 703763000 |Precondition value (qualifier value)| | is-a Precondition value | Resource: SpecimenDefinition.patientPreparation (CodeableConcept / Example)

Patient preparation prior specimen collection | Checks on the patient prior specimen collection. All SNOMED CT concepts descendants of 703763000 |Precondition value (qualifier value)| | is-a Precondition value | Resource: SpecimenDefinition.patientPreparation (CodeableConcept / Example)

Procedure Category Codes (SNOMED CT) | Procedure Category code: A selection of relevant SNOMED CT codes. | 7 enumerated concepts | Resource: Procedure.category (CodeableConcept / Example)

Procedure Category Codes (SNOMED CT) | Procedure Category code: A selection of relevant SNOMED CT codes. | 7 enumerated concepts | Resource: Procedure.category (CodeableConcept / Example)

Procedure Codes (SNOMED CT) | Procedure Code: All SNOMED CT procedure codes. | is-a Procedure | Resource: ServiceRequest.code (CodeableConcept / Example) Profile: ServiceRequest-Genetics: ServiceRequest.code (CodeableConcept / Example) Resource: ActivityDefinition.code (CodeableConcept / Example) Profile: ShareableActivityDefinition: ActivityDefinition.code (CodeableConcept / Example) Resource: CarePlan.activity.detail.code (CodeableConcept / Example) Resource: Procedure.code (CodeableConcept / Example) Resource: BiologicallyDerivedProduct.processing.procedure (CodeableConcept / Example)

Procedure Codes (SNOMED CT) | Procedure Code: All SNOMED CT procedure codes. | is-a Procedure | Resource: ServiceRequest.code (CodeableConcept / Example) Profile: ServiceRequest-Genetics: ServiceRequest.code (CodeableConcept / Example) Resource: ActivityDefinition.code (CodeableConcept / Example) Profile: ShareableActivityDefinition: ActivityDefinition.code (CodeableConcept / Example) Resource: CarePlan.activity.detail.code (CodeableConcept / Example) Resource: Procedure.code (CodeableConcept / Example) Resource: BiologicallyDerivedProduct.processing.procedure (CodeableConcept / Example)

Procedure Follow up Codes (SNOMED CT) | Procedure follow up codes: A selection of SNOMED CT codes relevant to procedure follow up. | 10 enumerated concepts | Resource: Procedure.followUp (CodeableConcept / Example)

Procedure Follow up Codes (SNOMED CT) | Procedure follow up codes: A selection of SNOMED CT codes relevant to procedure follow up. | 10 enumerated concepts | Resource: Procedure.followUp (CodeableConcept / Example)

Procedure Not Performed Reason (SNOMED-CT) | Situation codes describing the reason that a procedure, which might otherwise be expected, was not performed, or a procedure that was started and was not completed. Consists of SNOMED CT codes, children of procedure contraindicated (183932001), procedure discontinued (416406003), procedure not done (416237000), procedure not indicated (428119001), procedure not offered (416064006), procedure not wanted (416432009), procedure refused (183944003), and procedure stopped (394908001). | is-a Procedure contraindicated is-a Procedure discontinued is-a Procedure not done is-a Procedure not indicated is-a Procedure not offered is-a Procedure not wanted is-a Procedure refused is-a Procedure stopped |

Resource: Procedure.statusReason (CodeableConcept / Example)

Procedure Not Performed Reason (SNOMED-CT) | Situation codes describing the reason that a procedure, which might otherwise be expected, was not performed, or a procedure that was started and was not completed. Consists of SNOMED CT codes, children of procedure contraindicated (183932001), procedure discontinued (416406003), procedure not done (416237000), procedure not indicated (428119001), procedure not offered (416064006), procedure not wanted (416432009), procedure refused (183944003), and procedure stopped (394908001). | is-a Procedure contraindicated is-a Procedure discontinued is-a Procedure not done is-a Procedure not indicated is-a Procedure not offered is-a Procedure not wanted is-a Procedure refused is-a Procedure stopped | Resource: Procedure.statusReason (CodeableConcept / Example)

Procedure Outcome Codes (SNOMED CT) | Procedure Outcome code: A selection of relevant SNOMED CT codes. | 3 enumerated concepts | Resource: Procedure.outcome (CodeableConcept / Example)

Procedure Outcome Codes (SNOMED CT) | Procedure Outcome code: A selection of relevant SNOMED CT codes. | 3 enumerated concepts | Resource: Procedure.outcome (CodeableConcept / Example)

Procedure Reason Codes | This example value set defines the set of codes that can be used to indicate a reason for a procedure. | is-a Clinical finding is-a Procedure | Resource: ServiceRequest.reasonCode (CodeableConcept / Example) Profile: ServiceRequest-Genetics: ServiceRequest.reasonCode (CodeableConcept / Example) Resource: ImagingStudy.reasonCode (CodeableConcept / Example) Resource: Procedure.reasonCode (CodeableConcept / Example) Resource: Media.reasonCode (CodeableConcept / Example)

Procedure Reason Codes | This example value set defines the set of codes that can be used to indicate a reason for a procedure. | is-a Clinical finding is-a Procedure | Resource: ServiceRequest.reasonCode (CodeableConcept / Example) Profile: ServiceRequest-Genetics: ServiceRequest.reasonCode (CodeableConcept / Example) Resource: ImagingStudy.reasonCode (CodeableConcept / Example) Resource: Procedure.reasonCode (CodeableConcept / Example) Resource: Media.reasonCode (CodeableConcept / Example)

Questionnaire Answer Codes | Example list of codes for answers to questions. (Not complete or necessarily appropriate.) | any SCT concept | Resource: Questionnaire.item.enableWhen.answer[x] (boolean|decimal|integer|date|dateTime|time|string|Coding|Quantity|Reference(Any) / Example) Profile: CQF-Questionnaire: Questionnaire.item.enableWhen.answer[x] (boolean, decimal, integer, date, dateTime, time, string, Coding, Quantity, Reference / Example) Profile: CQF-Questionnaire: Questionnaire.item.answerOption.value[x] (integer, date, time, string, Coding, Reference / Example) Profile: CQF-Questionnaire: Questionnaire.item.initial.value[x] (boolean, decimal, integer, date, dateTime, time, string, uri, Attachment, Coding, Quantity, Reference / Example) Resource: QuestionnaireResponse.item.answer.value[x] (boolean|decimal|integer|date|dateTime|time|string|uri|Attachment|Coding|Quantity|Reference(Any) / Example)

Questionnaire Answer Codes | Example list of codes for answers to questions. (Not complete or necessarily appropriate.) | any SCT concept | Resource: Questionnaire.item.enableWhen.answer[x] (boolean|decimal|integer|date|dateTime|time|string|Coding|Quantity|Reference(Any) / Example) Profile: CQF-Questionnaire: Questionnaire.item.enableWhen.answer[x] (boolean, decimal, integer, date, dateTime, time, string, Coding, Quantity, Reference / Example) Profile: CQF-Questionnaire: Questionnaire.item.answerOption.value[x] (integer, date, time, string, Coding, Reference / Example) Profile: CQF-Questionnaire: Questionnaire.item.initial.value[x] (boolean, decimal, integer, date, dateTime, time, string, uri, Attachment, Coding, Quantity, Reference / Example) Resource: QuestionnaireResponse.item.answer.value[x] (boolean|decimal|integer|date|dateTime|time|string|uri|Attachment|Coding|Quantity|Reference(Any) / Example)

Questionnaire Category Codes | Example list of potential categories for questionnaires. | 5 enumerated concepts | This value set is not currently used

Questionnaire Category Codes | Example list of potential categories for questionnaires. | 5 enumerated concepts | This value set is not currently used

SNOMED CT Reason Medication Not Given Codes | This value set includes all medication refused, medication not administered, and non-administration of necessary drug or medicine codes from SNOMED CT - provided as an exemplar value set. | is-a Drug not available for administration is-a Drug declined by patient | Resource: MedicationAdministration.statusReason (CodeableConcept / Example)

SNOMED CT Reason Medication Not Given Codes | This value set includes all medication refused, medication not administered, and non-administration of necessary drug or medicine codes from SNOMED CT - provided as an exemplar value set. | is-a Drug not available for administration is-a Drug declined by patient | Resource: MedicationAdministration.statusReason (CodeableConcept / Example)

SNOMED CT Drug Therapy Status codes | This value set includes some taken and not taken reason codes from SNOMED CT - provided as an exemplar | is-a Drugs not taken/completed is-a Drug therapy status | Resource: MedicationStatement.statusReason (CodeableConcept / Example)

SNOMED CT Drug Therapy Status codes | This value set includes some taken and not taken reason codes from SNOMED CT - provided as an exemplar | is-a Drugs not taken/completed is-a Drug therapy status | Resource: MedicationStatement.statusReason (CodeableConcept / Example)

Observation Reference Range Applies To Codes | This value set defines a set of codes that can be used to indicate the particular target population the reference range applies to. | 3 enumerated concepts other code systems | Resource: ObservationDefinition.qualifiedInterval.appliesTo (CodeableConcept / Example) Profile: DeviceMetricObservation: Observation.referenceRange.appliesTo (CodeableConcept / Example) Profile: Observation-Genetics: Observation.referenceRange.appliesTo (CodeableConcept / Example) Profile: VitalSigns: Observation.referenceRange.appliesTo (CodeableConcept / Example) Profile: BodyWeight: Observation.referenceRange.appliesTo (CodeableConcept / Example) Profile: VitalsPanel: Observation.referenceRange.appliesTo (CodeableConcept / Example) Profile: BodyHeight: Observation.referenceRange.appliesTo (CodeableConcept / Example) Profile: RespRate: Observation.referenceRange.appliesTo (CodeableConcept / Example) Profile: HeartRate: Observation.referenceRange.appliesTo (CodeableConcept / Example) Profile: BodyTemp: Observation.referenceRange.appliesTo (CodeableConcept / Example) Profile: HeadCircum: Observation.referenceRange.appliesTo (CodeableConcept / Example) Profile: OxygenSat: Observation.referenceRange.appliesTo (CodeableConcept / Example) Profile: BMI: Observation.referenceRange.appliesTo (CodeableConcept / Example) Profile: BP: Observation.referenceRange.appliesTo (CodeableConcept / Example) Profile: Cholesterol: Observation.referenceRange.appliesTo (CodeableConcept / Example) Profile: Triglyceride: Observation.referenceRange.appliesTo (CodeableConcept / Example) Profile: HDLCholesterol: Observation.referenceRange.appliesTo (CodeableConcept / Example) Profile: LDLCholesterol: Observation.referenceRange.appliesTo (CodeableConcept / Example)

Observation Reference Range Applies To Codes | This value set defines a set of codes that can be used to indicate the particular target population the reference range applies to. | 3 enumerated concepts other code systems | Resource: ObservationDefinition.qualifiedInterval.appliesTo (CodeableConcept / Example) Profile: DeviceMetricObservation: Observation.referenceRange.appliesTo (CodeableConcept / Example) Profile: Observation-Genetics: Observation.referenceRange.appliesTo (CodeableConcept / Example) Profile: VitalSigns: Observation.referenceRange.appliesTo (CodeableConcept / Example) Profile: BodyWeight: Observation.referenceRange.appliesTo (CodeableConcept / Example) Profile:

VitalsPanel: Observation.referenceRange.appliesTo (CodeableConcept / Example) Profile: BodyHeight: Observation.referenceRange.appliesTo (CodeableConcept / Example) Profile: RespRate: Observation.referenceRange.appliesTo (CodeableConcept / Example) Profile: HeartRate: Observation.referenceRange.appliesTo (CodeableConcept / Example) Profile: BodyTemp: Observation.referenceRange.appliesTo (CodeableConcept / Example) Profile: HeadCircum: Observation.referenceRange.appliesTo (CodeableConcept / Example) Profile: OxygenSat: Observation.referenceRange.appliesTo (CodeableConcept / Example) Profile: BMI: Observation.referenceRange.appliesTo (CodeableConcept / Example) Profile: BP: Observation.referenceRange.appliesTo (CodeableConcept / Example) Profile: Cholesterol: Observation.referenceRange.appliesTo (CodeableConcept / Example) Profile: Triglyceride: Observation.referenceRange.appliesTo (CodeableConcept / Example) Profile: HDLCholesterol: Observation.referenceRange.appliesTo (CodeableConcept / Example) Profile: LDLCholesterol: Observation.referenceRange.appliesTo (CodeableConcept / Example)

SNOMED CT Route Codes | This value set includes all Route codes from SNOMED CT - provided as an exemplar. | is-a Route of administration values | Resource: AllergyIntolerance.reaction.exposureRoute (CodeableConcept / Example) Resource: MedicationAdministration.dosage.route (CodeableConcept / Example) Resource: MedicationKnowledge.intendedRoute (CodeableConcept / Example)

SNOMED CT Route Codes | This value set includes all Route codes from SNOMED CT - provided as an exemplar. | is-a Route of administration values | Resource: AllergyIntolerance.reaction.exposureRoute (CodeableConcept / Example) Resource: MedicationAdministration.dosage.route (CodeableConcept / Example) Resource: MedicationKnowledge.intendedRoute (CodeableConcept / Example)

SNOMED CT Codes for species | Codes identifying atomic results of observations when value is type codeableConcept. This value set includes all the children of SNOMED CT Concepts from SCTIDs 404684003 Clinical finding (finding), 410607006 Organism (organism),362981000 Qualifier value (qualifier value), 105590001 Substance (substance), and 123037004 Body structure (body structure). It is provided as a suggestive example | any SCT concept | This value set is not currently used

SNOMED CT Codes for species | Codes identifying atomic results of observations when value is type codeableConcept. This value set includes all the children of SNOMED CT Concepts from SCTIDs 404684003 Clinical finding (finding), 410607006 Organism (organism),362981000 Qualifier value (qualifier value), 105590001 Substance (substance), and 123037004 Body structure (body structure). It is provided as a suggestive example | any SCT concept | This value set is not currently used

Service Request Category Codes | An example value set of SNOMED CT concepts that can classify a requested service | 5 enumerated concepts | Resource: ServiceRequest.category (CodeableConcept / Example) Profile: ServiceRequest-Genetics: ServiceRequest.category (CodeableConcept / Example)

Service Request Category Codes | An example value set of SNOMED CT concepts that can classify a requested service | 5 enumerated concepts | Resource: ServiceRequest.category (CodeableConcept / Example) Profile: ServiceRequest-Genetics: ServiceRequest.category (CodeableConcept / Example)

Service Request Order Details Codes | An example value set of Codified order entry details concepts. These concepts only make sense in the context of what is being ordered. This example is for a patient ventilation order | 5 enumerated concepts | Resource: ServiceRequest.orderDetail (CodeableConcept / Example) Profile: ServiceRequest-Genetics: ServiceRequest.orderDetail (CodeableConcept / Example)

Service Request Order Details Codes | An example value set of Codified order entry details concepts. These concepts only make sense in the context of what is being ordered. This example is for a patient ventilation order | 5 enumerated concepts | Resource: ServiceRequest.orderDetail (CodeableConcept / Example) Profile: ServiceRequest-Genetics: ServiceRequest.orderDetail (CodeableConcept / Example)

Specimen collection methods | Actions that can be taken for the collection of specimen from a subject. | 10 enumerated concepts | Resource: SpecimenDefinition.collection (CodeableConcept / Example)

Specimen collection methods | Actions that can be taken for the collection of specimen from a subject. | 10 enumerated concepts | Resource: SpecimenDefinition.collection (CodeableConcept / Example)

FHIR Specimen Collection Method | This example value set defines a set of codes that can be used to indicate the method by which a specimen was collected. | 10 enumerated concepts | Resource: Specimen.collection.method (CodeableConcept / Example)

FHIR Specimen Collection Method | This example value set defines a set of codes that can be used to indicate the method by which a specimen was collected. | 10 enumerated concepts | Resource: Specimen.collection.method (CodeableConcept / Example)

Specimen Container Type | Checks on the patient prior specimen collection. All SNOMED CT concepts descendants of 706041008 |Device for body fluid and tissue collection/transfer/processing (physical object)| | is-a Device for body fluid and tissue collection/transfer/processing | Resource: SpecimenDefinition.typeTested.container.type (CodeableConcept / Example)

Specimen Container Type | Checks on the patient prior specimen collection. All SNOMED CT concepts descendants of 706041008 |Device for body fluid and tissue collection/transfer/processing (physical object)| | is-a Device for body fluid and tissue collection/transfer/processing | Resource: SpecimenDefinition.typeTested.container.type (CodeableConcept / Example)

Substance Code | This value set contains concept codes for specific substances. It includes codes from [SNOMED](http://snomed.info/sct) where concept is-a 105590001 (Substance (substance)) and where concept is-a 373873005 (Pharmaceutical / biologic product (product)) | is-a Substance is-a Pharmaceutical / biologic product | Resource: Substance.ingredient.substance[x] (CodeableConcept|Reference(Substance) / Example) Resource: AllergyIntolerance.reaction.substance (CodeableConcept / Example) Extension: http://hl7.org/fhir/StructureDefinition/allergyintolerance-substanceExposureRisk: substanceExposureRisk (CodeableConcept / Example)

Substance Code | This value set contains concept codes for specific substances. It includes codes from [SNOMED](http://snomed.info/sct) where concept is-a 105590001 (Substance (substance)) and where concept is-a 373873005 (Pharmaceutical / biologic product (product)) | is-a Substance is-a Pharmaceutical / biologic product | Resource: Substance.ingredient.substance[x] (CodeableConcept|Reference(Substance) / Example) Resource: AllergyIntolerance.reaction.substance (CodeableConcept / Example) Extension: http://hl7.org/fhir/StructureDefinition/allergyintolerance-substanceExposureRisk: substanceExposureRisk (CodeableConcept / Example)

Supplement Type Codes | SupplementType : Codes for nutritional supplements to be provided to the patient. This value set is composed of SNOMED CT (US Extension) Concepts from SCTID 470581016 (Enteral+supplement feeds hierarchy (product)) and is provided as a suggestive example. | 45 enumerated concepts | Resource: NutritionOrder.supplement.type (CodeableConcept / Example)

Supplement Type Codes | SupplementType : Codes for nutritional supplements to be provided to the patient. This value set is composed of SNOMED CT (US Extension) Concepts from SCTID 470581016 (Enteral+supplement feeds hierarchy (product)) and is provided as a suggestive example. | 45 enumerated concepts | Resource: NutritionOrder.supplement.type (CodeableConcept / Example)

SNOMED CT Supply Item | This value set includes [SNOMED CT](http://snomed.info/sct) where concept is-a 105590001 (Substance (substance)) or concept is-a 260787004 (Physical object) and provided as an example value set. | is-a Substance is-a Physical

object | Resource: SupplyRequest.item[x] (CodeableConcept|Reference(Medication|Substance|Device) / Example) Resource: SupplyDelivery.suppliedItem.item[x] (CodeableConcept|Reference(Medication|Substance|Device) / Example)

SNOMED CT Supply Item | This value set includes [SNOMED CT](http://snomed.info/sct) where concept is-a 105590001 (Substance (substance)) or concept is-a 260787004 (Physical object) and provided as an example value set. | is-a Substance is-a Physical object | Resource: SupplyRequest.item[x] (CodeableConcept|Reference(Medication|Substance|Device) / Example) Resource: SupplyDelivery.suppliedItem.item[x] (CodeableConcept|Reference(Medication|Substance|Device) / Example)

Texture Modifier Codes | TextureModifier: Codes for food consistency types or texture modifications to apply to foods. This value set is composed of SNOMED CT (US Extension and Core) Concepts from SCTID 229961002 Food consistency types (substance) hierarchy and is provided as a suggestive example. | 14 enumerated concepts | Resource: NutritionOrder.oralDiet.texture.modifier (CodeableConcept / Example)

Texture Modifier Codes | TextureModifier: Codes for food consistency types or texture modifications to apply to foods. This value set is composed of SNOMED CT (US Extension and Core) Concepts from SCTID 229961002 Food consistency types (substance) hierarchy and is provided as a suggestive example. | 14 enumerated concepts | Resource: NutritionOrder.oralDiet.texture.modifier (CodeableConcept / Example)

ConformanceUseContext | This value set defines a base set of codes that can be used to indicate that the content in a resource was developed with a focus and intent of supporting use within particular contexts. | is-a Medical specialties is-a Kingdom Animalia other code systems | Resource: UsageContext.value[x] (CodeableConcept|Quantity|Range|Reference(PlanDefinition|ResearchStudy|InsurancePlan|HealthcareService|Group|Location|Organization) / Example) Extension: http://hl7.org/fhir/StructureDefinition/elementdefinition-bestpractice: bestpractice (boolean, CodeableConcept / Extensible)

ConformanceUseContext | This value set defines a base set of codes that can be used to indicate that the content in a resource was developed with a focus and intent of supporting use within particular contexts. | is-a Medical specialties is-a Kingdom Animalia other code systems | Resource: UsageContext.value[x] (CodeableConcept|Quantity|Range|Reference(PlanDefinition|ResearchStudy|InsurancePlan|HealthcareService|Group|Location|Organization) / Example) Extension: http://hl7.org/fhir/StructureDefinition/elementdefinition-bestpractice: bestpractice (boolean, CodeableConcept / Extensible)

4.3.1.1.2 Concept References

The value sets that reference SNOMED CT explicitly reference the following SNOMED CT concepts. The table lists the concepts, and then the value sets and places they are used from, and includes the binding strengths. The table does not include codes published in the expansions.

Code | Display | ValueSets

1006005 | Percheron horse (organism) | Animal breeds Animal breeds

10206005 | Hospital outpatient dental clinic | Facility Type Code Value Set Facility Type Code Value Set

102263004 | Eggs | Texture Modified Food Type Codes Texture Modified Food Type Codes

10261003 | Belgium landrace pig (organism) | Animal breeds Animal breeds

103693007 | Diagnostic procedure | Procedure Category Codes (SNOMED CT) Procedure Category Codes (SNOMED CT)

10531005 | Free-standing ambulatory surgery facility | Facility Type Code Value Set Facility Type Code Value Set

105590001 | Substance | Substance Code Substance Code

106181007 | Immunologic substance | SNOMED CT Medication Codes SNOMED CT Medication Codes

10643004 | Arucana chicken (organism) | Animal breeds Animal breeds

108252007 | Laboratory procedure | Service Request Category Codes Service Request Category Codes

11161001 | Dekalb hybrid pig line 77 (organism) | Animal breeds Animal breeds

1118004 | Viking horse (organism) | Animal breeds Animal breeds

112485003 | Gujarati cattle breed (organism) | Animal breeds Animal breeds

112486002 | No-tail sheep (organism) | Animal breeds Animal breeds

112487006 | Romnelet sheep (organism) | Animal breeds Animal breeds

112488001 | Hackney horse (organism) | Animal breeds Animal breeds

112489009 | Berkshire pig (organism) | Animal breeds Animal breeds

112490000 | Dekalb hybrid pig line 63 (organism) | Animal breeds Animal breeds

112495005 | Rumpless chicken (organism) | Animal breeds Animal breeds

112496006 | Pilgrim goose (organism) | Animal breeds Animal breeds

11424001 | Ambulance-based care | Facility Type Code Value Set Facility Type Code Value Set

11830008 | Delaware chicken (organism) | Animal breeds Animal breeds

11967001 | Kerry Hill sheep (organism) | Animal breeds Animal breeds

12360007 | Missouri fox trotting horse (organism) | Animal breeds Animal breeds

12407009 | Swedish landrace pig (organism) | Animal breeds Animal breeds

12419001 | Redcap chicken (organism) | Animal breeds Animal breeds

1247002 | Clydesdale horse (organism) | Animal breeds Animal breeds

125074003 | Hereford cattle superbreed (organism) | Animal breeds Animal breeds

125084002 | Equus caballus gmelini (organism) | Animal breeds Animal breeds

125086000 | Equus caballus gmelini X Equus caballus caballus (organism) | Animal breeds Animal breeds

125092006 | Bos frontalis (organism) | Animal breeds Animal breeds

125097000 | Capra hircus (organism) | Animal breeds Animal breeds

125099002 | Ovis aries (organism) | Animal breeds Animal breeds

125101009 | Merino sheep superbreed (organism) | Animal breeds Animal breeds

125102002 | Anas platyrhynchos (organism) | Animal breeds Animal breeds

125104001 | Anser anser (organism) | Animal breeds Animal breeds

125676002 | Person | Participant Roles Participant Roles

12874007 | Crevecoeur chicken (organism) | Animal breeds Animal breeds

129264002 | Action | Procedure Device Action Codes Procedure Device Action Codes

129300006 | Puncture - action | Specimen collection methods Specimen collection methods

129304002 | Excision - action | Specimen collection methods Specimen collection methods

129314006 | Biopsy - action | Specimen collection methods Specimen collection methods

129316008 | Aspiration - action | Specimen collection methods Specimen collection methods

129323009 | Scraping - action | Specimen collection methods Specimen collection methods
131426006 | Africander cattle breed (organism) | Animal breeds Animal breeds
131427002 | Ankole cattle breed (organism) | Animal breeds Animal breeds
131428007 | Ankole-Watusi cattle breed (organism) | Animal breeds Animal breeds
131429004 | Baladi cattle breed (organism) | Animal breeds Animal breeds
131430009 | Belmont Red cattle breed (organism) | Animal breeds Animal breeds
131431008 | Bonsmara cattle breed (organism) | Animal breeds Animal breeds
131432001 | Damietta cattle breed (organism) | Animal breeds Animal breeds
131433006 | Horro cattle breed (organism) | Animal breeds Animal breeds
131434000 | Kuri cattle breed (organism) | Animal breeds Animal breeds
131435004 | Nguni cattle breed (organism) | Animal breeds Animal breeds
131436003 | Philippine Native cattle breed (organism) | Animal breeds Animal breeds
131437007 | Romagnola cattle breed (organism) | Animal breeds Animal breeds
131438002 | Sanhe cattle breed (organism) | Animal breeds Animal breeds
131439005 | Tswana cattle breed (organism) | Animal breeds Animal breeds
131440007 | Tuli cattle breed (organism) | Animal breeds Animal breeds
131441006 | Aliab Dinka cattle breed (organism) | Animal breeds Animal breeds
131442004 | Alur cattle breed (organism) | Animal breeds Animal breeds
131443009 | Ankina cattle breed (organism) | Animal breeds Animal breeds
131444003 | Apulian Podolian cattle breed (organism) | Animal breeds Animal breeds
131445002 | Arado cattle breed (organism) | Animal breeds Animal breeds
131446001 | Aweil Dinka cattle breed (organism) | Animal breeds Animal breeds
131447005 | Bahima cattle breed (organism) | Animal breeds Animal breeds
131448000 | Bapedi cattle breed (organism) | Animal breeds Animal breeds
131449008 | Baria (Vietnam/Madagascar) cattle breed (organism) | Animal breeds Animal breeds
131450008 | Barotse cattle breed (organism) | Animal breeds Animal breeds
131451007 | Barra do Cuanzo cattle breed (organism) | Animal breeds Animal breeds
131452000 | Bashi cattle breed (organism) | Animal breeds Animal breeds
131453005 | Basuto cattle breed (organism) | Animal breeds Animal breeds
131454004 | Batangas cattle breed (organism) | Animal breeds Animal breeds
131455003 | Bavenda cattle breed (organism) | Animal breeds Animal breeds
131456002 | Beja cattle breed (organism) | Animal breeds Animal breeds
131457006 | Calabrian cattle breed (organism) | Animal breeds Animal breeds
131458001 | Blonde-du Cap Bon cattle breed (organism) | Animal breeds Animal breeds
131459009 | Chan-Doc cattle breed (organism) | Animal breeds Animal breeds
131460004 | Chernigov cattle breed (organism) | Animal breeds Animal breeds
131461000 | Chino Santandereano cattle breed (organism) | Animal breeds Animal breeds
131462007 | Cinisara cattle breed (organism) | Animal breeds Animal breeds
131463002 | Cuprem Hybrid cattle breed (organism) | Animal breeds Animal breeds
131464008 | Dabieshan cattle breed (organism) | Animal breeds Animal breeds
131465009 | Damara cattle breed (organism) | Animal breeds Animal breeds
131466005 | Danakil cattle breed (organism) | Animal breeds Animal breeds
131467001 | Dnieper cattle breed (organism) | Animal breeds Animal breeds
131468006 | Doayo cattle breed (organism) | Animal breeds Animal breeds
131469003 | Eastern Nuer cattle breed (organism) | Animal breeds Animal breeds
131470002 | Egyptian cattle breed (organism) | Animal breeds Animal breeds
131471003 | Fogera cattle breed (organism) | Animal breeds Animal breeds
131472005 | Garfagnina cattle breed (organism) | Animal breeds Animal breeds
131473000 | Grati cattle breed (organism) | Animal breeds Animal breeds
131474006 | Gaunling cattle breed (organism) | Animal breeds Animal breeds
131475007 | Halhin Gol cattle breed (organism) | Animal breeds Animal breeds
131476008 | Holmonger cattle breed (organism) | Animal breeds Animal breeds
131477004 | Ilocos cattle breed (organism) | Animal breeds Animal breeds
131478009 | Iloilo cattle breed (organism) | Animal breeds Animal breeds
131479001 | Inkuku cattle breed (organism) | Animal breeds Animal breeds
131480003 | Iskar cattle breed (organism) | Animal breeds Animal breeds
131481004 | Istrian cattle breed (organism) | Animal breeds Animal breeds
131482006 | Javanese Ongole cattle breed (organism) | Animal breeds Animal breeds
131483001 | Javanese Zebu cattle breed (organism) | Animal breeds Animal breeds
131484007 | Jinnan cattle breed (organism) | Animal breeds Animal breeds
131485008 | Kalmyk cattle breed (organism) | Animal breeds Animal breeds
131486009 | Kaokoveld cattle breed (organism) | Animal breeds Animal breeds
131487000 | Kazakh Whitehead cattle breed (organism) | Animal breeds Animal breeds
131488005 | Kedah-Kelantan cattle breed (organism) | Animal breeds Animal breeds
131489002 | Kigezi cattle breed (organism) | Animal breeds Animal breeds
131490006 | Kisantu cattle breed (organism) | Animal breeds Animal breeds
131491005 | Kolubara cattle breed (organism) | Animal breeds Animal breeds
131492003 | Kurgan cattle breed (organism) | Animal breeds Animal breeds
131493008 | Kyoga cattle breed (organism) | Animal breeds Animal breeds
131494002 | Lucanian cattle breed (organism) | Animal breeds Animal breeds
131495001 | Maremmana cattle breed (organism) | Animal breeds Animal breeds
131496000 | Marianas cattle breed (organism) | Animal breeds Animal breeds

131497009 | Maryuti cattle breed (organism) | Animal breeds Animal breeds
131498004 | Mauritius Créole cattle breed (organism) | Animal breeds Animal breeds
131499007 | Menufi cattle breed (organism) | Animal breeds Animal breeds
131500003 | Mezzalina cattle breed (organism) | Animal breeds Animal breeds
131501004 | Modicana cattle breed (organism) | Animal breeds Animal breeds
131502006 | Moi cattle breed (organism) | Animal breeds Animal breeds
131503001 | Nama cattle breed (organism) | Animal breeds Animal breeds
131504007 | Nanyang cattle breed (organism) | Animal breeds Animal breeds
131505008 | N'Dama Sanga cattle breed (organism) | Animal breeds Animal breeds
131506009 | Nganda cattle breed (organism) | Animal breeds Animal breeds
131507000 | Nilotic Sanga cattle breed (organism) | Animal breeds Animal breeds
131508005 | Nkone cattle breed (organism) | Animal breeds Animal breeds
131509002 | North Malawi Angoni cattle breed (organism) | Animal breeds Animal breeds
131510007 | Nuer cattle breed (organism) | Animal breeds Animal breeds
131511006 | Nuras cattle breed (organism) | Animal breeds Animal breeds
131512004 | Nyoro cattle breed (organism) | Animal breeds Animal breeds
131513009 | Ovambo cattle breed (organism) | Animal breeds Animal breeds
131514003 | Pantelleria cattle breed (organism) | Animal breeds Animal breeds
131515002 | Pinzhou cattle breed (organism) | Animal breeds Animal breeds
131516001 | Porto Amboim cattle breed (organism) | Animal breeds Animal breeds
131517005 | Posavina cattle breed (organism) | Animal breeds Animal breeds
131518000 | Romanian Steppe cattle breed (organism) | Animal breeds Animal breeds
131519008 | Saidi cattle breed (organism) | Animal breeds Animal breeds
131520002 | Sardo-Modicana cattle breed (organism) | Animal breeds Animal breeds
131521003 | Sengologa cattle breed (organism) | Animal breeds Animal breeds
131522005 | Serere cattle breed (organism) | Animal breeds Animal breeds
131523000 | Seshaga cattle breed (organism) | Animal breeds Animal breeds
131524006 | Siberian Black Pied cattle breed (organism) | Animal breeds Animal breeds
131525007 | Socotra cattle breed (organism) | Animal breeds Animal breeds
131526008 | Southern Tswana cattle breed (organism) | Animal breeds Animal breeds
131527004 | Spreca cattle breed (organism) | Animal breeds Animal breeds
131528009 | Sunkuma cattle breed (organism) | Animal breeds Animal breeds
131529001 | Taiwan Zebu cattle breed (organism) | Animal breeds Animal breeds
131530006 | Thai cattle breed (organism) | Animal breeds Animal breeds
131531005 | Thailand Fighting Zebu cattle breed (organism) | Animal breeds Animal breeds
131532003 | Thanh-Hoa cattle breed (organism) | Animal breeds Animal breeds
131533008 | Tibetan cattle breed (organism) | Animal breeds Animal breeds
131534002 | Tonga cattle breed (organism) | Animal breeds Animal breeds
131535001 | Toro cattle breed (organism) | Animal breeds Animal breeds
131536000 | Tuni cattle breed (organism) | Animal breeds Animal breeds
131537009 | Turkish Gray Steppe cattle breed (organism) | Animal breeds Animal breeds
131538004 | Tuy-Hoa cattle breed (organism) | Animal breeds Animal breeds
131539007 | Ujumqin cattle breed (organism) | Animal breeds Animal breeds
131540009 | Abigar cattle breed (organism) | Animal breeds Animal breeds
131541008 | Africangus cattle breed (organism) | Animal breeds Animal breeds
131542001 | Agerolese cattle breed (organism) | Animal breeds Animal breeds
131543006 | Albese cattle breed (organism) | Animal breeds Animal breeds
131544000 | Ukrainian Gray cattle breed (organism) | Animal breeds Animal breeds
131545004 | Vietnamese Yellow cattle breed (organism) | Animal breeds Animal breeds
131546003 | Watusi (United States of America) cattle breed (organism) | Animal breeds Animal breeds
131547007 | Wenshan cattle breed (organism) | Animal breeds Animal breeds
131548002 | Yakut cattle breed (organism) | Animal breeds Animal breeds
131549005 | Yunnan Zebu cattle breed (organism) | Animal breeds Animal breeds
131550005 | Zambia Angoni cattle breed (organism) | Animal breeds Animal breeds
131551009 | Drakensberger cattle breed (organism) | Animal breeds Animal breeds
131552002 | Modicana lowland cattle breed (organism) | Animal breeds Animal breeds
131553007 | Taiwan Yellow cattle breed (organism) | Animal breeds Animal breeds
131554001 | Menggu cattle breed (organism) | Animal breeds Animal breeds
131555000 | Albères cattle breed (organism) | Animal breeds Animal breeds
131556004 | Alentejana cattle breed (organism) | Animal breeds Animal breeds
131557008 | American White Park cattle breed (organism) | Animal breeds Animal breeds
131558003 | Amerifaxcattle breed (organism) | Animal breeds Animal breeds
131559006 | Anatolian Black cattle breed (organism) | Animal breeds Animal breeds
131560001 | Andalusian Black cattle breed (organism) | Animal breeds Animal breeds
13156006 | Spanish chicken (organism) | Animal breeds Animal breeds
131561002 | Andalusian Gray cattle breed (organism) | Animal breeds Animal breeds
131562009 | Angeln cattle breed (organism) | Animal breeds Animal breeds
131563004 | Asturian Mountain cattle breed (organism) | Animal breeds Animal breeds
131564005 | Asturian Valley cattle breed (organism) | Animal breeds Animal breeds
131565006 | Aubrac cattle breed (organism) | Animal breeds Animal breeds
131566007 | Aulie-Ata cattle breed (organism) | Animal breeds Animal breeds
131567003 | Australian Lowline cattle breed (organism) | Animal breeds Animal breeds

131568008 | Barzona cattle breed (organism) | Animal breeds Animal breeds
131569000 | Bazadais cattle breed (organism) | Animal breeds Animal breeds
131570004 | Beefmaker cattle breed (organism) | Animal breeds Animal breeds
131571000 | Belarus Red cattle breed (organism) | Animal breeds Animal breeds
131572007 | Belgian Blue cattle breed (organism) | Animal breeds Animal breeds
131573002 | Belgian Red cattle breed (organism) | Animal breeds Animal breeds
131574008 | Belmont Adaptaur cattle breed (organism) | Animal breeds Animal breeds
131575009 | Berrendas cattle breed (organism) | Animal breeds Animal breeds
131576005 | Blacksided Trondheim and Norland cattle breed (organism) | Animal breeds Animal breeds
131577001 | Blanco Orejinegro cattle breed (organism) | Animal breeds Animal breeds
131578006 | Braunvieh cattle breed (organism) | Animal breeds Animal breeds
131579003 | British White cattle breed (organism) | Animal breeds Animal breeds
131580000 | Cachena cattle breed (organism) | Animal breeds Animal breeds
131581001 | Canary Island cattle breed (organism) | Animal breeds Animal breeds
131582008 | Carinthian Blond cattle breed (organism) | Animal breeds Animal breeds
131583003 | Caucasian cattle breed (organism) | Animal breeds Animal breeds
131584009 | Charolais cattle breed (organism) | Animal breeds Animal breeds
131585005 | Chinese Black-and-White cattle breed (organism) | Animal breeds Animal breeds
131586006 | Corriente cattle breed (organism) | Animal breeds Animal breeds
131587002 | Costeño con Cuernos cattle breed (organism) | Animal breeds Animal breeds
131588007 | Damascus cattle breed (organism) | Animal breeds Animal breeds
131589004 | Danish Red cattle breed (organism) | Animal breeds Animal breeds
131590008 | Devon cattle breed (organism) | Animal breeds Animal breeds
131591007 | Dølafe cattle breed (organism) | Animal breeds Animal breeds
131592000 | Dutch Belted cattle breed (organism) | Animal breeds Animal breeds
131593005 | Dutch Friesian cattle breed (organism) | Animal breeds Animal breeds
131594004 | English Longhorn cattle breed (organism) | Animal breeds Animal breeds
131595003 | Estonian Red cattle breed (organism) | Animal breeds Animal breeds
131596002 | Evolène cattle breed (organism) | Animal breeds Animal breeds
131597006 | Fighting Bull cattle breed (organism) | Animal breeds Animal breeds
131598001 | Fjall cattle breed (organism) | Animal breeds Animal breeds
131599009 | Florida Cracker/Pineywoods cattle breed (organism) | Animal breeds Animal breeds
131600007 | Galician Blond cattle breed (organism) | Animal breeds Animal breeds
131601006 | Gascon cattle breed (organism) | Animal breeds Animal breeds
131602004 | German Red Pied cattle breed (organism) | Animal breeds Animal breeds
131603009 | Glan cattle breed (organism) | Animal breeds Animal breeds
131604003 | Gloucester cattle breed (organism) | Animal breeds Animal breeds
131605002 | Groningen Whiteheaded cattle breed (organism) | Animal breeds Animal breeds
131606001 | Hartón cattle breed (organism) | Animal breeds Animal breeds
131607005 | Mixed Breed Goat (organism) | Animal breeds Animal breeds
131608000 | Australian Goat breed (organism) | Animal breeds Animal breeds
131609008 | Arapawa Island goat breed (organism) | Animal breeds Animal breeds
131610003 | Maltese goat breed (organism) | Animal breeds Animal breeds
131611004 | Provençale goat breed (organism) | Animal breeds Animal breeds
131612006 | Negra Serrana goat breed (organism) | Animal breeds Animal breeds
131613001 | Orobica goat breed (organism) | Animal breeds Animal breeds
131614007 | Roya-Vesubie goat breed (organism) | Animal breeds Animal breeds
131615008 | Retinta Extremena goat breed (organism) | Animal breeds Animal breeds
131616009 | Appenzell goat breed (organism) | Animal breeds Animal breeds
131617000 | American Cashmere goat breed (organism) | Animal breeds Animal breeds
131618005 | Altai Mountain goat breed (organism) | Animal breeds Animal breeds
131619002 | Pyrenean goat breed (organism) | Animal breeds Animal breeds
131620008 | Bagot goat breed (organism) | Animal breeds Animal breeds
131621007 | Russian White goat breed (organism) | Animal breeds Animal breeds
131622000 | Moxotó goat breed (organism) | Animal breeds Animal breeds
131623005 | Myotonic goat breed (organism) | Animal breeds Animal breeds
131624004 | Nachi goat breed (organism) | Animal breeds Animal breeds
131625003 | Nigerian Dwarf goat breed (organism) | Animal breeds Animal breeds
131626002 | Sarda goat breed (organism) | Animal breeds Animal breeds
131627006 | Serpentina goat breed (organism) | Animal breeds Animal breeds
131628001 | Serrana goat breed (organism) | Animal breeds Animal breeds
131629009 | Verata goat breed (organism) | Animal breeds Animal breeds
131630004 | Verzasca black goat breed (organism) | Animal breeds Animal breeds
131631000 | Norwegian goat breed (organism) | Animal breeds Animal breeds
131632007 | Oberhasli goat breed (organism) | Animal breeds Animal breeds
131633002 | Peacock Goat breed (organism) | Animal breeds Animal breeds
131634008 | Philippine goat breed (organism) | Animal breeds Animal breeds
131635009 | Loashan goat breed (organism) | Animal breeds Animal breeds
131636005 | San Clemente goat breed (organism) | Animal breeds Animal breeds
131637001 | Somali goat breed (organism) | Animal breeds Animal breeds
131638006 | Spanish goat breed (organism) | Animal breeds Animal breeds
131639003 | Rove goat breed (organism) | Animal breeds Animal breeds

131640001 | SRD goat breed (organism) | Animal breeds Animal breeds
131641002 | Swedish Landrace goat breed (organism) | Animal breeds Animal breeds
131642009 | Thuringian goat breed (organism) | Animal breeds Animal breeds
131643004 | Uzbek Black goat breed (organism) | Animal breeds Animal breeds
131644005 | Zhongwei goat breed (organism) | Animal breeds Animal breeds
131645006 | Barbari goat breed (organism) | Animal breeds Animal breeds
131646007 | Poitou goat breed (organism) | Animal breeds Animal breeds
131647003 | Repartida goat breed (organism) | Animal breeds Animal breeds
131648008 | Booted Goat breed (organism) | Animal breeds Animal breeds
131649000 | Corsican goat breed (organism) | Animal breeds Animal breeds
131650000 | Chapar goat breed (organism) | Animal breeds Animal breeds
131651001 | Canindé goat breed (organism) | Animal breeds Animal breeds
131652008 | Canary Island goat breed (organism) | Animal breeds Animal breeds
131653003 | Daera Din Panah goat breed (organism) | Animal breeds Animal breeds
131654009 | British Alpine goat breed (organism) | Animal breeds Animal breeds
131655005 | Bhuj goat breed (organism) | Animal breeds Animal breeds
131656006 | Boer goat breed (organism) | Animal breeds Animal breeds
131657002 | Benadir goat breed (organism) | Animal breeds Animal breeds
131658007 | Créole Antilles goat breed (organism) | Animal breeds Animal breeds
131659004 | Beetal goat breed (organism) | Animal breeds Animal breeds
131660009 | Golden Guernsey goat breed (organism) | Animal breeds Animal breeds
131661008 | Danish Landrace goat breed (organism) | Animal breeds Animal breeds
131662001 | Kaghani goat breed (organism) | Animal breeds Animal breeds
131663006 | Irish Goat breed (organism) | Animal breeds Animal breeds
131664000 | Grisons Striped goat breed (organism) | Animal breeds Animal breeds
131665004 | Jining Gray goat breed (organism) | Animal breeds Animal breeds
131666003 | Finnish Landrace goat breed (organism) | Animal breeds Animal breeds
131667007 | Erzgebirg goat breed (organism) | Animal breeds Animal breeds
131668002 | Kamori goat breed (organism) | Animal breeds Animal breeds
131669005 | Don goat breed (organism) | Animal breeds Animal breeds
131670006 | Kiko goat breed (organism) | Animal breeds Animal breeds
131671005 | Kinder goat breed (organism) | Animal breeds Animal breeds
131672003 | Pygora goat breed (organism) | Animal breeds Animal breeds
131673008 | Wooden Leg goat breed (organism) | Animal breeds Animal breeds
131674002 | Alpine Chamoisee goat breed (organism) | Animal breeds Animal breeds
131675001 | Massif Central goat breed (organism) | Animal breeds Animal breeds
131676000 | Malagueña goat breed (organism) | Animal breeds Animal breeds
131677009 | Algarvia goat breed (organism) | Animal breeds Animal breeds
131678004 | British Saanen goat breed (organism) | Animal breeds Animal breeds
131679007 | British Toggenburg goat breed (organism) | Animal breeds Animal breeds
131680005 | Bündner goat breed (organism) | Animal breeds Animal breeds
131681009 | Blanca Andaluza goat breed (organism) | Animal breeds Animal breeds
131682002 | Blanca Celtiberica goat breed (organism) | Animal breeds Animal breeds
131683007 | Bravia goat breed (organism) | Animal breeds Animal breeds
131684001 | Black Grisonne goat breed (organism) | Animal breeds Animal breeds
131685000 | Chamois of the Alps goat breed (organism) | Animal breeds Animal breeds
131686004 | Charnequeria goat breed (organism) | Animal breeds Animal breeds
131687008 | Carpathe goat breed (organism) | Animal breeds Animal breeds
131688003 | Col Noir du Valais goat breed (organism) | Animal breeds Animal breeds
131689006 | Damani goat breed (organism) | Animal breeds Animal breeds
131690002 | Des Fosses (Communes de l'Ouest) goat breed (organism) | Animal breeds Animal breeds
131691003 | English goat breed (organism) | Animal breeds Animal breeds
131692005 | English Guernsey goat breed (organism) | Animal breeds Animal breeds
131693000 | German colored goat breed (organism) | Animal breeds Animal breeds
131694006 | Guadarrama goat breed (organism) | Animal breeds Animal breeds
131695007 | Garganica goat breed (organism) | Animal breeds Animal breeds
131696008 | Girgentana goat breed (organism) | Animal breeds Animal breeds
131697004 | Jonica goat breed (organism) | Animal breeds Animal breeds
131698009 | Murciana-Granadina goat breed (organism) | Animal breeds Animal breeds
131699001 | Bündner Oberland sheep breed (organism) | Animal breeds Animal breeds
131700000 | British Milk Sheep breed (organism) | Animal breeds Animal breeds
131701001 | Brillenschaf sheep breed (organism) | Animal breeds Animal breeds
131702008 | Brecknock Hill Cheviot sheep breed (organism) | Animal breeds Animal breeds
131703003 | Cholistani sheep breed (organism) | Animal breeds Animal breeds
131704009 | Bibrik sheep breed (organism) | Animal breeds Animal breeds
131705005 | Columbia sheep breed (organism) | Animal breeds Animal breeds
131706006 | Black Welsh Mountain Sheep breed (organism) | Animal breeds Animal breeds
131707002 | Blackhead Persian sheep breed (organism) | Animal breeds Animal breeds
131708007 | Bleu du Maine sheep breed (organism) | Animal breeds Animal breeds
131709004 | Bluefaced Leicester sheep breed (organism) | Animal breeds Animal breeds
131710009 | Bond sheep breed (organism) | Animal breeds Animal breeds
131711008 | Border Leicester sheep breed (organism) | Animal breeds Animal breeds

131712001 | Boreray sheep breed (organism) | Animal breeds Animal breeds
131713006 | Bovska sheep breed (organism) | Animal breeds Animal breeds
131714000 | Braunes Bergschaf sheep breed (organism) | Animal breeds Animal breeds
131715004 | Brazilian Somali sheep breed (organism) | Animal breeds Animal breeds
131716003 | Beulah Speckled-Face sheep breed (organism) | Animal breeds Animal breeds
131717007 | Dartmoor sheep breed (organism) | Animal breeds Animal breeds
131718002 | Fabrianese sheep breed (organism) | Animal breeds Animal breeds
131719005 | Exmoor Horn sheep breed (organism) | Animal breeds Animal breeds
131720004 | Elliottdale sheep breed (organism) | Animal breeds Animal breeds
131721000 | Drysdale sheep breed (organism) | Animal breeds Animal breeds
131722007 | Dorset Down sheep breed (organism) | Animal breeds Animal breeds
131723002 | German Blackheaded Mutton sheep breed (organism) | Animal breeds Animal breeds
131724008 | Kooka sheep breed (organism) | Animal breeds Animal breeds
131725009 | Friesian Milk Sheep breed (organism) | Animal breeds Animal breeds
131726005 | Gansu Alpine Fine-wool sheep breed (organism) | Animal breeds Animal breeds
131727001 | German Whiteheaded Mutton sheep breed (organism) | Animal breeds Animal breeds
131728006 | Graue Gehoernte Heidschnucke sheep breed (organism) | Animal breeds Animal breeds
131729003 | Han sheep breed (organism) | Animal breeds Animal breeds
131730008 | Gromark sheep breed (organism) | Animal breeds Animal breeds
131731007 | Gulf Coast Native sheep breed (organism) | Animal breeds Animal breeds
131732000 | Dorper sheep breed (organism) | Animal breeds Animal breeds
131733005 | Devon Closewool sheep breed (organism) | Animal breeds Animal breeds
131734004 | Deutsches Blaukoepfiges Fleischschaf sheep breed (organism) | Animal breeds Animal breeds
131735003 | Derbyshire Gritstone sheep breed (organism) | Animal breeds Animal breeds
131736002 | Coburger Fuchsschaf sheep breed (organism) | Animal breeds Animal breeds
131737006 | Danish Landrace sheep breed (organism) | Animal breeds Animal breeds
131738001 | Gute sheep breed (organism) | Animal breeds Animal breeds
131739009 | Hampshire sheep breed (organism) | Animal breeds Animal breeds
131740006 | Gentile di Puglia sheep breed (organism) | Animal breeds Animal breeds
131741005 | German Mountain sheep breed (organism) | Animal breeds Animal breeds
131742003 | Luzein sheep breed (organism) | Animal breeds Animal breeds
131743008 | Katahdin sheep breed (organism) | Animal breeds Animal breeds
131744002 | Leineschaf sheep breed (organism) | Animal breeds Animal breeds
131745001 | Lincoln Longwool sheep breed (organism) | Animal breeds Animal breeds
131746000 | Llanwenog sheep breed (organism) | Animal breeds Animal breeds
131747009 | Lleyn sheep breed (organism) | Animal breeds Animal breeds
131748004 | Damara sheep breed (organism) | Animal breeds Animal breeds
131749007 | Damani sheep breed (organism) | Animal breeds Animal breeds
131750007 | Dalesbred sheep breed (organism) | Animal breeds Animal breeds
131751006 | Dala sheep breed (organism) | Animal breeds Animal breeds
131752004 | Criollo sheep breed (organism) | Animal breeds Animal breeds
131753009 | Cormo sheep breed (organism) | Animal breeds Animal breeds
131754003 | Lati sheep breed (organism) | Animal breeds Animal breeds
131755002 | Lonk sheep breed (organism) | Animal breeds Animal breeds
131756001 | Langhe sheep breed (organism) | Animal breeds Animal breeds
131757005 | Manx Loaghtan sheep breed (organism) | Animal breeds Animal breeds
131758000 | Masai sheep breed (organism) | Animal breeds Animal breeds
131759008 | Merinolandschaf sheep breed (organism) | Animal breeds Animal breeds
131760003 | Lohi sheep breed (organism) | Animal breeds Animal breeds
131761004 | Ile-de-France sheep breed (organism) | Animal breeds Animal breeds
131762006 | Hasht Nagri sheep breed (organism) | Animal breeds Animal breeds
131763001 | Hazaragie sheep breed (organism) | Animal breeds Animal breeds
131764007 | Coopworth sheep breed (organism) | Animal breeds Animal breeds
131765008 | Comisana sheep breed (organism) | Animal breeds Animal breeds
131766009 | Comeback sheep breed (organism) | Animal breeds Animal breeds
131767000 | Sicilian Barbary sheep breed (organism) | Animal breeds Animal breeds
131768005 | Africana sheep breed (organism) | Animal breeds Animal breeds
131769002 | Welsh Mountain Badger Faced sheep breed (organism) | Animal breeds Animal breeds
131770001 | Hebridean sheep breed (organism) | Animal breeds Animal breeds
131771002 | Heidschnucke sheep breed (organism) | Animal breeds Animal breeds
131772009 | Herdwick sheep breed (organism) | Animal breeds Animal breeds
131773004 | Hill Radnor sheep breed (organism) | Animal breeds Animal breeds
131774005 | Icelandic sheep breed (organism) | Animal breeds Animal breeds
131775006 | Harnai sheep breed (organism) | Animal breeds Animal breeds
131776007 | Istrian Pramenka sheep breed (organism) | Animal breeds Animal breeds
131777003 | Jacob sheep breed (organism) | Animal breeds Animal breeds
131778008 | Jezerskosolcavska sheep breed (organism) | Animal breeds Animal breeds
131779000 | Kachhi sheep breed (organism) | Animal breeds Animal breeds
131780002 | Wensleydale sheep breed (organism) | Animal breeds Animal breeds
131781003 | West African Dwarf sheep breed (organism) | Animal breeds Animal breeds
131782005 | White Suffolk sheep breed (organism) | Animal breeds Animal breeds
131783000 | Whiteface Dartmoor sheep breed (organism) | Animal breeds Animal breeds

131784006 | Whiteface Woodland sheep breed (organism) | Animal breeds Animal breeds
131785007 | Xinjiang Finewool sheep breed (organism) | Animal breeds Animal breeds
131786008 | Kajli sheep breed (organism) | Animal breeds Animal breeds
131787004 | Hog Island Sheep breed (organism) | Animal breeds Animal breeds
131788009 | Biellese sheep breed (organism) | Animal breeds Animal breeds
131789001 | Chios sheep breed (organism) | Animal breeds Animal breeds
131790005 | Santa Cruz sheep breed (organism) | Animal breeds Animal breeds
131791009 | Charollais sheep breed (organism) | Animal breeds Animal breeds
131792002 | Castlemilk Moorit sheep breed (organism) | Animal breeds Animal breeds
131793007 | Campanian Barbary sheep breed (organism) | Animal breeds Animal breeds
131794001 | California Variegated Mutant sheep breed (organism) | Animal breeds Animal breeds
131795000 | California Red sheep breed (organism) | Animal breeds Animal breeds
131796004 | Sopravissana sheep breed (organism) | Animal breeds Animal breeds
131797008 | Somali sheep breed (organism) | Animal breeds Animal breeds
131798003 | Welsh Hill Speckled Face sheep breed (organism) | Animal breeds Animal breeds
131799006 | Skudde sheep breed (organism) | Animal breeds Animal breeds
131800005 | Waziri sheep breed (organism) | Animal breeds Animal breeds
131801009 | Shetland sheep breed (organism) | Animal breeds Animal breeds
131802002 | Cambridge sheep breed (organism) | Animal breeds Animal breeds
131803007 | Solognote sheep breed (organism) | Animal breeds Animal breeds
131804001 | Colombian Criollo horse breed (organism) | Animal breeds Animal breeds
131805000 | Comtois horse breed (organism) | Animal breeds Animal breeds
131806004 | Corsican horse breed (organism) | Animal breeds Animal breeds
131807008 | Costa Rican Saddle Horse horse breed (organism) | Animal breeds Animal breeds
131808003 | Costeno horse breed (organism) | Animal breeds Animal breeds
131809006 | Cuban Paso horse breed (organism) | Animal breeds Animal breeds
131810001 | Cayuga breed duck (organism) | Animal breeds Animal breeds
131811002 | Runner breed duck (organism) | Animal breeds Animal breeds
131812009 | Call breed duck (organism) | Animal breeds Animal breeds
131813004 | Orpington breed duck (organism) | Animal breeds Animal breeds
131814005 | Crested breed duck (organism) | Animal breeds Animal breeds
131815006 | Pommeranian breed duck (organism) | Animal breeds Animal breeds
131816007 | Rough Fell sheep breed (organism) | Animal breeds Animal breeds
131817003 | Blue Swedish breed duck (organism) | Animal breeds Animal breeds
131818008 | Golden 300 hybrid breed duck (organism) | Animal breeds Animal breeds
131819000 | Danish Warmblood horse breed (organism) | Animal breeds Animal breeds
131820006 | Ancona breed duck (organism) | Animal breeds Animal breeds
131821005 | Australian Spotted breed duck (organism) | Animal breeds Animal breeds
131822003 | Swaledale sheep breed (organism) | Animal breeds Animal breeds
131823008 | Polypay sheep breed (organism) | Animal breeds Animal breeds
131824002 | Aylesbury breed duck (organism) | Animal breeds Animal breeds
131825001 | Black East Indies breed duck (organism) | Animal breeds Animal breeds
131826000 | Coast breed duck (organism) | Animal breeds Animal breeds
131827009 | Kromsnaveleend breed duck (organism) | Animal breeds Animal breeds
131828004 | Magpie breed duck (organism) | Animal breeds Animal breeds
131829007 | Silver appleyard breed duck (organism) | Animal breeds Animal breeds
131830002 | Pagliarola sheep breed (organism) | Animal breeds Animal breeds
131831003 | Pomeranian Coarsewool sheep breed (organism) | Animal breeds Animal breeds
131832005 | Sheep, Breed Undetermined sheep breed (organism) | Animal breeds Animal breeds
131833000 | Orkney sheep breed (organism) | Animal breeds Animal breeds
131834006 | Old Norwegian sheep breed (organism) | Animal breeds Animal breeds
131835007 | Old Format Sheep breed (organism) | Animal breeds Animal breeds
131836008 | Norwegian Fur sheep breed (organism) | Animal breeds Animal breeds
131837004 | Norfolk Horn sheep breed (organism) | Animal breeds Animal breeds
131838009 | Navajo-Churro sheep breed (organism) | Animal breeds Animal breeds
131839001 | Swedish yellow breed duck (organism) | Animal breeds Animal breeds
131840004 | Diepholz goose breed (organism) | Animal breeds Animal breeds
131841000 | African goose breed (organism) | Animal breeds Animal breeds
131843002 | Embden goose breed (organism) | Animal breeds Animal breeds
131844008 | Chinese white goose breed (organism) | Animal breeds Animal breeds
131845009 | Chinese brown goose breed (organism) | Animal breeds Animal breeds
131846005 | Toulouse goose breed (organism) | Animal breeds Animal breeds
131847001 | American buff goose breed (organism) | Animal breeds Animal breeds
131848006 | Pomeranian goose breed (organism) | Animal breeds Animal breeds
131849003 | Roman goose breed (organism) | Animal breeds Animal breeds
131850003 | Scania goose breed (organism) | Animal breeds Animal breeds
131851004 | Racka sheep breed (organism) | Animal breeds Animal breeds
131852006 | Rasa Aragonesa sheep breed (organism) | Animal breeds Animal breeds
131853001 | Red Engadine sheep breed (organism) | Animal breeds Animal breeds
131854007 | Rhoenschaf sheep breed (organism) | Animal breeds Animal breeds
131855008 | Sebastopol goose breed (organism) | Animal breeds Animal breeds
131856009 | Swedish Island goose breed (organism) | Animal breeds Animal breeds

131857000 | Bronze turkey breed (organism) | Animal breeds Animal breeds
131858005 | Auburn turkey breed (organism) | Animal breeds Animal breeds
131859002 | Bourbon Red turkey breed (organism) | Animal breeds Animal breeds
131860007 | Buff turkey breed (organism) | Animal breeds Animal breeds
131861006 | Hucul horse breed (organism) | Animal breeds Animal breeds
131862004 | AraAppaloosa horse breed (organism) | Animal breeds Animal breeds
131863009 | Argentine Criollo horse breed (organism) | Animal breeds Animal breeds
131864003 | Argentine Polo Pony horse breed (organism) | Animal breeds Animal breeds
131865002 | Australian Pony horse breed (organism) | Animal breeds Animal breeds
131866001 | Auxois horse breed (organism) | Animal breeds Animal breeds
131867005 | Avelignese horse breed (organism) | Animal breeds Animal breeds
131868000 | Azerbaijan horse breed (organism) | Animal breeds Animal breeds
131869008 | Azores horse breed (organism) | Animal breeds Animal breeds
131870009 | Bali horse breed (organism) | Animal breeds Animal breeds
131871008 | Balikun horse breed (organism) | Animal breeds Animal breeds
131872001 | Waziri horse breed (organism) | Animal breeds Animal breeds
131873006 | Banker Horse horse breed (organism) | Animal breeds Animal breeds
131874000 | Bardigiano horse breed (organism) | Animal breeds Animal breeds
131875004 | Batak horse breed (organism) | Animal breeds Animal breeds
131876003 | Bavarian Warmblood horse breed (organism) | Animal breeds Animal breeds
131877007 | Belgian Ardennais horse breed (organism) | Animal breeds Animal breeds
131878002 | Belgian Halfblood horse breed (organism) | Animal breeds Animal breeds
131879005 | Belgian Warmblood horse breed (organism) | Animal breeds Animal breeds
131880008 | Bhutia horse breed (organism) | Animal breeds Animal breeds
131881007 | Black Sea Horse horse breed (organism) | Animal breeds Animal breeds
131882000 | Bosnian horse breed (organism) | Animal breeds Animal breeds
131883005 | Boulonnais horse breed (organism) | Animal breeds Animal breeds
131884004 | Brandenburg horse breed (organism) | Animal breeds Animal breeds
131885003 | Brazilian Sport Horse horse breed (organism) | Animal breeds Animal breeds
131886002 | British Appaloosa horse breed (organism) | Animal breeds Animal breeds
131887006 | British Riding Pony horse breed (organism) | Animal breeds Animal breeds
131888001 | British Spotted Pony horse breed (organism) | Animal breeds Animal breeds
131889009 | Buohai horse breed (organism) | Animal breeds Animal breeds
131890000 | Buryat horse breed (organism) | Animal breeds Animal breeds
131891001 | Calabrian horse breed (organism) | Animal breeds Animal breeds
131892008 | Camargue horse breed (organism) | Animal breeds Animal breeds
131893003 | Canadian Cutting Horse horse breed (organism) | Animal breeds Animal breeds
131894009 | Canadian Rustic Pony horse breed (organism) | Animal breeds Animal breeds
131895005 | Canadian Sport Horse horse breed (organism) | Animal breeds Animal breeds
131896006 | Canik horse breed (organism) | Animal breeds Animal breeds
131897002 | Cape Horse horse breed (organism) | Animal breeds Animal breeds
131898007 | Cerbat horse breed (organism) | Animal breeds Animal breeds
131899004 | Chakouyi horse breed (organism) | Animal breeds Animal breeds
131900009 | Chara Horse horse breed (organism) | Animal breeds Animal breeds
131901008 | Chickasaw horse breed (organism) | Animal breeds Animal breeds
131902001 | Chilote horse breed (organism) | Animal breeds Animal breeds
131903006 | Chinese Kazakh horse breed (organism) | Animal breeds Animal breeds
131904000 | Chinese Mongolian horse breed (organism) | Animal breeds Animal breeds
131905004 | Chumbivilcas horse breed (organism) | Animal breeds Animal breeds
131906003 | Chumysh horse breed (organism) | Animal breeds Animal breeds
131907007 | Cirit horse breed (organism) | Animal breeds Animal breeds
131908002 | Irish Draft horse breed (organism) | Animal breeds Animal breeds
131909005 | Irish Hunter horse breed (organism) | Animal breeds Animal breeds
131910000 | Cuban Trotter horse breed (organism) | Animal breeds Animal breeds
131911001 | Italian Heavy Draft horse breed (organism) | Animal breeds Animal breeds
131912008 | Jabe horse breed (organism) | Animal breeds Animal breeds
131913003 | Java horse breed (organism) | Animal breeds Animal breeds
131914009 | Vendéen sheep breed (organism) | Animal breeds Animal breeds
131915005 | Czech Warmblood horse breed (organism) | Animal breeds Animal breeds
131916006 | Jinhong horse breed (organism) | Animal breeds Animal breeds
131917002 | Jinzhou horse breed (organism) | Animal breeds Animal breeds
131918007 | Saxony breed duck (organism) | Animal breeds Animal breeds
131919004 | Danubian horse breed (organism) | Animal breeds Animal breeds
131920005 | Karachai horse breed (organism) | Animal breeds Animal breeds
131921009 | Karakacan horse breed (organism) | Animal breeds Animal breeds
131922002 | Kathiawari horse breed (organism) | Animal breeds Animal breeds
131923007 | Ke-Er-Qin horse breed (organism) | Animal breeds Animal breeds
131924001 | Kirgiz horse breed (organism) | Animal breeds Animal breeds
131925000 | Kuznet horse breed (organism) | Animal breeds Animal breeds
131926004 | Landais horse breed (organism) | Animal breeds Animal breeds
131927008 | Lewitzer horse breed (organism) | Animal breeds Animal breeds
131928003 | Lichuan horse breed (organism) | Animal breeds Animal breeds

131929006 | Lijiang horse breed (organism) | Animal breeds Animal breeds
131930001 | Llanero horse breed (organism) | Animal breeds Animal breeds
131931002 | Lombok horse breed (organism) | Animal breeds Animal breeds
131932009 | Lundy Pony horse breed (organism) | Animal breeds Animal breeds
131933004 | Malakan horse breed (organism) | Animal breeds Animal breeds
131934005 | Malopolski horse breed (organism) | Animal breeds Animal breeds
131935006 | Datong horse breed (organism) | Animal breeds Animal breeds
131936007 | Mangalarga Paulista horse breed (organism) | Animal breeds Animal breeds
131937003 | Dulmen Pony horse breed (organism) | Animal breeds Animal breeds
131938008 | Maremmana horse breed (organism) | Animal breeds Animal breeds
131939000 | Marwari horse breed (organism) | Animal breeds Animal breeds
131940003 | Megezh horse breed (organism) | Animal breeds Animal breeds
131941004 | Megrel horse breed (organism) | Animal breeds Animal breeds
131942006 | Merens horse breed (organism) | Animal breeds Animal breeds
131943001 | Messara horse breed (organism) | Animal breeds Animal breeds
131944007 | Sumba horse breed (organism) | Animal breeds Animal breeds
131945008 | Sumbawa horse breed (organism) | Animal breeds Animal breeds
131946009 | Swedish Ardennes horse breed (organism) | Animal breeds Animal breeds
131947000 | Dutch Tuigpaard horse breed (organism) | Animal breeds Animal breeds
131948005 | East and Southeast Anadolu horse breed (organism) | Animal breeds Animal breeds
131949002 | Thai Pony horse breed (organism) | Animal breeds Animal breeds
131950002 | Thessalonian horse breed (organism) | Animal breeds Animal breeds
131951003 | Tibetan horse breed (organism) | Animal breeds Animal breeds
131952005 | Tieling horse breed (organism) | Animal breeds Animal breeds
131953000 | Timor horse breed (organism) | Animal breeds Animal breeds
131954006 | Trakya horse breed (organism) | Animal breeds Animal breeds
131955007 | Trote en Gallope horse breed (organism) | Animal breeds Animal breeds
131956008 | Turkoman horse breed (organism) | Animal breeds Animal breeds
131957004 | Tushin horse breed (organism) | Animal breeds Animal breeds
131958009 | Tuva horse breed (organism) | Animal breeds Animal breeds
131959001 | Uzunyayla horse breed (organism) | Animal breeds Animal breeds
131960006 | Voronezh Coach Horse horse breed (organism) | Animal breeds Animal breeds
131961005 | Elegant Warmblood horse breed (organism) | Animal breeds Animal breeds
131962003 | Welsh Cob horse breed (organism) | Animal breeds Animal breeds
131963008 | Welsh Mountain Pony horse breed (organism) | Animal breeds Animal breeds
131964002 | English Hack horse breed (organism) | Animal breeds Animal breeds
131965001 | Wurttemberg horse breed (organism) | Animal breeds Animal breeds
131966000 | Xilingol horse breed (organism) | Animal breeds Animal breeds
131967009 | Yanqi horse breed (organism) | Animal breeds Animal breeds
131968004 | Yemeni Horses horse breed (organism) | Animal breeds Animal breeds
131969007 | Yili horse breed (organism) | Animal breeds Animal breeds
131970008 | Yiwu horse breed (organism) | Animal breeds Animal breeds
131971007 | Yunnan horse breed (organism) | Animal breeds Animal breeds
131972000 | German Riding Pony horse breed (organism) | Animal breeds Animal breeds
131973005 | Guanzhong horse breed (organism) | Animal breeds Animal breeds
131974004 | Guizhou horse breed (organism) | Animal breeds Animal breeds
131975003 | Guoxia horse breed (organism) | Animal breeds Animal breeds
131976002 | Erlunchun horse breed (organism) | Animal breeds Animal breeds
131977006 | Half Saddlebred horse breed (organism) | Animal breeds Animal breeds
131978001 | Flores horse breed (organism) | Animal breeds Animal breeds
131979009 | Freiberg horse breed (organism) | Animal breeds Animal breeds
131980007 | Hessen horse breed (organism) | Animal breeds Animal breeds
131981006 | Hinis horse breed (organism) | Animal breeds Animal breeds
131982004 | Hirzai horse breed (organism) | Animal breeds Animal breeds
131983009 | Hungarian Coldblood horse breed (organism) | Animal breeds Animal breeds
131984003 | Hungarian Dun horse breed (organism) | Animal breeds Animal breeds
131985002 | Hungarian Sport Horse horse breed (organism) | Animal breeds Animal breeds
131986001 | International Striped Horse horse breed (organism) | Animal breeds Animal breeds
131987005 | Irish Cob horse breed (organism) | Animal breeds Animal breeds
131988000 | Mezen horse breed (organism) | Animal breeds Animal breeds
131989008 | Mezohegyes Sport Horse horse breed (organism) | Animal breeds Animal breeds
131990004 | French Cob horse breed (organism) | Animal breeds Animal breeds
131991000 | French Saddle pony horse breed (organism) | Animal breeds Animal breeds
131992007 | Murakoz horse breed (organism) | Animal breeds Animal breeds
131993002 | Finnhorse Draft horse breed (organism) | Animal breeds Animal breeds
131994008 | Mecklenburg horse breed (organism) | Animal breeds Animal breeds
131995009 | Baheij chicken breed (organism) | Animal breeds Animal breeds
131996005 | Aseel chicken breed (organism) | Animal breeds Animal breeds
131997001 | Bandara chicken breed (organism) | Animal breeds Animal breeds
131998006 | Catalana chicken breed (organism) | Animal breeds Animal breeds
131999003 | Australian Gamefowl chicken breed (organism) | Animal breeds Animal breeds
132000009 | Ayam Cemani chicken breed (organism) | Animal breeds Animal breeds

132001008 | Swedish Spotted Hen chicken breed (organism) | Animal breeds Animal breeds
132002001 | Belgian Booted Bantam chicken breed (organism) | Animal breeds Animal breeds
132003006 | Brabanter chicken breed (organism) | Animal breeds Animal breeds
132004000 | Braekel chicken breed (organism) | Animal breeds Animal breeds
132005004 | Cochin, Standard chicken breed (organism) | Animal breeds Animal breeds
132006003 | Old English Bantam Game chicken breed (organism) | Animal breeds Animal breeds
132007007 | Gotland chicken breed (organism) | Animal breeds Animal breeds
132008002 | Groninger Meeuwen chicken breed (organism) | Animal breeds Animal breeds
132009005 | Haiti Créole pig breed (organism) | Animal breeds Animal breeds
132010000 | Manor Hybrid pig breed (organism) | Animal breeds Animal breeds
132011001 | Hamline pig breed (organism) | Animal breeds Animal breeds
132012008 | Manor Ranger pig breed (organism) | Animal breeds Animal breeds
132013003 | Manor Meishan pig breed (organism) | Animal breeds Animal breeds
132014009 | Cotswold Gold pig breed (organism) | Animal breeds Animal breeds
132015005 | Cotswold Platinum pig breed (organism) | Animal breeds Animal breeds
132016006 | Cotswold 16 pig breed (organism) | Animal breeds Animal breeds
132017002 | Cotswold 29 pig breed (organism) | Animal breeds Animal breeds
132018007 | Cotswold 90 pig breed (organism) | Animal breeds Animal breeds
132019004 | Hampen pig breed (organism) | Animal breeds Animal breeds
132020005 | SPM pig breed (organism) | Animal breeds Animal breeds
132021009 | High Conformation White pig breed (organism) | Animal breeds Animal breeds
132022002 | Line 32 pig breed (organism) | Animal breeds Animal breeds
132023007 | Line 21 pig breed (organism) | Animal breeds Animal breeds
132024001 | Meatline pig breed (organism) | Animal breeds Animal breeds
132025000 | Hampline pig breed (organism) | Animal breeds Animal breeds
132026004 | Euroline pig breed (organism) | Animal breeds Animal breeds
132027008 | Norline pig breed (organism) | Animal breeds Animal breeds
132028003 | Premier pig breed (organism) | Animal breeds Animal breeds
132029006 | Tribred pig breed (organism) | Animal breeds Animal breeds
132030001 | American Essex pig breed (organism) | Animal breeds Animal breeds
132031002 | Sino-Gascony pig breed (organism) | Animal breeds Animal breeds
132032009 | Guadeloupe Créole pig breed (organism) | Animal breeds Animal breeds
132033004 | Managra pig breed (organism) | Animal breeds Animal breeds
132034005 | Canadian Landrace pig breed (organism) | Animal breeds Animal breeds
132035006 | Canadian Yorkshire pig breed (organism) | Animal breeds Animal breeds
132037003 | Pineywoods pig breed (organism) | Animal breeds Animal breeds
132038008 | Catalina Island pig breed (organism) | Animal breeds Animal breeds
132039000 | Ras-n-Lansa pig breed (organism) | Animal breeds Animal breeds
132040003 | Pitman-Moore Miniature pig breed (organism) | Animal breeds Animal breeds
132041004 | Vita Vet Lab Minipig pig breed (organism) | Animal breeds Animal breeds
132042006 | Hanford Miniature pig breed (organism) | Animal breeds Animal breeds
132043001 | Black Hampshire pig breed (organism) | Animal breeds Animal breeds
132044007 | Red Hamprace pig breed (organism) | Animal breeds Animal breeds
132045008 | American Yorkshire pig breed (organism) | Animal breeds Animal breeds
132046009 | American Berkshire pig breed (organism) | Animal breeds Animal breeds
132047000 | Camborough Blue pig breed (organism) | Animal breeds Animal breeds
132048005 | Camborough 12 pig breed (organism) | Animal breeds Animal breeds
132049002 | Westrain pig breed (organism) | Animal breeds Animal breeds
132050002 | Dalland 030 pig breed (organism) | Animal breeds Animal breeds
132051003 | Razor-Back pig breed (organism) | Animal breeds Animal breeds
132052005 | Macau pig breed (organism) | Animal breeds Animal breeds
132053000 | Moura pig breed (organism) | Animal breeds Animal breeds
132054006 | Canastra pig breed (organism) | Animal breeds Animal breeds
132055007 | Pirapetinga pig breed (organism) | Animal breeds Animal breeds
132056008 | Piau pig breed (organism) | Animal breeds Animal breeds
132057004 | Nilo-Canastra pig breed (organism) | Animal breeds Animal breeds
132058009 | Canastrão pig breed (organism) | Animal breeds Animal breeds
132059001 | Canastrão, Junqueira pig breed (organism) | Animal breeds Animal breeds
132060006 | Canastrão, Capitão Chico pig breed (organism) | Animal breeds Animal breeds
132061005 | Canastrão, Zabumba pig breed (organism) | Animal breeds Animal breeds
132062003 | Canastrão, Cabano pig breed (organism) | Animal breeds Animal breeds
132063008 | Canastrão, Vermelho pig breed (organism) | Animal breeds Animal breeds
132064002 | Piau, Caruncho Piau pig breed (organism) | Animal breeds Animal breeds
132065001 | Canastrinho pig breed (organism) | Animal breeds Animal breeds
132066000 | Honduras Switch-Tail pig breed (organism) | Animal breeds Animal breeds
132067009 | Mastergilt pig breed (organism) | Animal breeds Animal breeds
132068004 | Sovereign pig breed (organism) | Animal breeds Animal breeds
132069007 | Poltava pig breed (organism) | Animal breeds Animal breeds
132070008 | Lipetsk pig breed (organism) | Animal breeds Animal breeds
132071007 | Soviet Meat pig breed (organism) | Animal breeds Animal breeds
132072000 | Central Russian pig breed (organism) | Animal breeds Animal breeds
132073005 | Steppe Meat pig breed (organism) | Animal breeds Animal breeds

132074004 | Kharkov pig breed (organism) | Animal breeds Animal breeds
132075003 | Dnepropetrovsk pig breed (organism) | Animal breeds Animal breeds
132076002 | Russian Large White pig breed (organism) | Animal breeds Animal breeds
132077006 | Forest Mountain pig breed (organism) | Animal breeds Animal breeds
132078001 | Dnieper pig breed (organism) | Animal breeds Animal breeds
132079009 | Iberian pig breed (organism) | Animal breeds Animal breeds
132080007 | Iberian, Extremadura Red pig breed (organism) | Animal breeds Animal breeds
132081006 | Iberian, Jabugo Spotted pig breed (organism) | Animal breeds Animal breeds
132082004 | Iberian, Black Iberian pig breed (organism) | Animal breeds Animal breeds
132083009 | Philippine Native, Ilocos pig breed (organism) | Animal breeds Animal breeds
132084003 | Philippine Native, Jalajala pig breed (organism) | Animal breeds Animal breeds
132085002 | Mangalizta pig breed (organism) | Animal breeds Animal breeds
132086001 | Alentejana pig breed (organism) | Animal breeds Animal breeds
132087005 | Belgian Landrace, BN pig breed (organism) | Animal breeds Animal breeds
132088000 | French Large White pig breed (organism) | Animal breeds Animal breeds
132089008 | Hyper Large White pig breed (organism) | Animal breeds Animal breeds
132090004 | Tia Meslan pig breed (organism) | Animal breeds Animal breeds
132091000 | Pen ar Lan 77 pig breed (organism) | Animal breeds Animal breeds
132092007 | Penshire pig breed (organism) | Animal breeds Animal breeds
132093002 | Laconie pig breed (organism) | Animal breeds Animal breeds
132094008 | Murcian pig breed (organism) | Animal breeds Animal breeds
132095009 | Cavallino pig breed (organism) | Animal breeds Animal breeds
132096005 | Calabrian pig breed (organism) | Animal breeds Animal breeds
132097001 | Apulian pig breed (organism) | Animal breeds Animal breeds
132098006 | Siena Belted pig breed (organism) | Animal breeds Animal breeds
132099003 | Calascibetta pig breed (organism) | Animal breeds Animal breeds
132100006 | Güssing Forest Pig pig breed (organism) | Animal breeds Animal breeds
132101005 | Swiss Edelschwein pig breed (organism) | Animal breeds Animal breeds
132102003 | North Caucasus pig breed (organism) | Animal breeds Animal breeds
132103008 | Don pig breed (organism) | Animal breeds Animal breeds
132104002 | Rostov pig breed (organism) | Animal breeds Animal breeds
132105001 | Russian Long-Eared White pig breed (organism) | Animal breeds Animal breeds
132106000 | Russian Short-Eared White pig breed (organism) | Animal breeds Animal breeds
132107009 | Prisheksninsk pig breed (organism) | Animal breeds Animal breeds
132108004 | Breitov pig breed (organism) | Animal breeds Animal breeds
132109007 | Livny pig breed (organism) | Animal breeds Animal breeds
132110002 | Tsivilsk pig breed (organism) | Animal breeds Animal breeds
132111003 | Urzhum pig breed (organism) | Animal breeds Animal breeds
132112005 | Minisib pig breed (organism) | Animal breeds Animal breeds
132113000 | Sakhalin White pig breed (organism) | Animal breeds Animal breeds
132114006 | North Siberian pig breed (organism) | Animal breeds Animal breeds
132115007 | Siberian Black Pied pig breed (organism) | Animal breeds Animal breeds
132116008 | Kemerovo pig breed (organism) | Animal breeds Animal breeds
132117004 | KM-1 pig breed (organism) | Animal breeds Animal breeds
132118009 | Aksaî Black Pied pig breed (organism) | Animal breeds Animal breeds
132119001 | Semirechensk pig breed (organism) | Animal breeds Animal breeds
132120007 | Min pig breed (organism) | Animal breeds Animal breeds
132121006 | Sanjiang White pig breed (organism) | Animal breeds Animal breeds
132122004 | Basque Black Pied pig breed (organism) | Animal breeds Animal breeds
132123009 | Corsican pig breed (organism) | Animal breeds Animal breeds
132124003 | Créole pig breed (organism) | Animal breeds Animal breeds
132125002 | Gascony pig breed (organism) | Animal breeds Animal breeds
132126001 | Limousin pig breed (organism) | Animal breeds Animal breeds
132127005 | Harbin White pig breed (organism) | Animal breeds Animal breeds
132128000 | Heilongjiang Spotted pig breed (organism) | Animal breeds Animal breeds
132129008 | Liaoning Black pig breed (organism) | Animal breeds Animal breeds
132130003 | Huang-Huai-Hai Black, Shenxian pig breed (organism) | Animal breeds Animal breeds
132131004 | Huang-Huai-Hai Black pig breed (organism) | Animal breeds Animal breeds
132132006 | Bamei pig breed (organism) | Animal breeds Animal breeds
132133001 | Hanjiang Black pig breed (organism) | Animal breeds Animal breeds
132134007 | Ding pig breed (organism) | Animal breeds Animal breeds
132135008 | Huai pig breed (organism) | Animal breeds Animal breeds
132136009 | New Huai pig breed (organism) | Animal breeds Animal breeds
132137000 | Mashen pig breed (organism) | Animal breeds Animal breeds
132138005 | Yimeng Black pig breed (organism) | Animal breeds Animal breeds
132139002 | Hetao Lop-Ear pig breed (organism) | Animal breeds Animal breeds
132140000 | Korean Native pig breed (organism) | Animal breeds Animal breeds
132141001 | Korean Improved pig breed (organism) | Animal breeds Animal breeds
132142008 | Penbuk pig breed (organism) | Animal breeds Animal breeds
132143003 | Beijing Black pig breed (organism) | Animal breeds Animal breeds
132144009 | Chenghua pig breed (organism) | Animal breeds Animal breeds
132145005 | Taoyuan pig breed (organism) | Animal breeds Animal breeds

132146006 | Taiwan Small Black pig breed (organism) | Animal breeds Animal breeds
132147002 | Taiwan Small Red pig breed (organism) | Animal breeds Animal breeds
132148007 | Guanling pig breed (organism) | Animal breeds Animal breeds
132149004 | Huchuan Mountain pig breed (organism) | Animal breeds Animal breeds
132150004 | Rongchang pig breed (organism) | Animal breeds Animal breeds
132151000 | Wujin pig breed (organism) | Animal breeds Animal breeds
132152007 | Dahe pig breed (organism) | Animal breeds Animal breeds
132153002 | Yanan pig breed (organism) | Animal breeds Animal breeds
132154008 | South Yunnan Short-Eared pig breed (organism) | Animal breeds Animal breeds
132155009 | Hainan, Lingao pig breed (organism) | Animal breeds Animal breeds
132156005 | Hainan, Tunchang pig breed (organism) | Animal breeds Animal breeds
132157001 | Hainan, Wenchang pig breed (organism) | Animal breeds Animal breeds
132158006 | Liang Guang Small Spotted pig breed (organism) | Animal breeds Animal breeds
132159003 | German Pasture pig breed (organism) | Animal breeds Animal breeds
132160008 | Piau, Sorocaba pig breed (organism) | Animal breeds Animal breeds
132161007 | Nilo pig breed (organism) | Animal breeds Animal breeds
132162000 | Bahia pig breed (organism) | Animal breeds Animal breeds
132163005 | Perna-Curta pig breed (organism) | Animal breeds Animal breeds
132164004 | Carunchinho pig breed (organism) | Animal breeds Animal breeds
132165003 | Mandi pig breed (organism) | Animal breeds Animal breeds
132166002 | Orehla de Colher pig breed (organism) | Animal breeds Animal breeds
132167006 | Venezuelan Black pig breed (organism) | Animal breeds Animal breeds
132168001 | Bolivian pig breed (organism) | Animal breeds Animal breeds
132169009 | Pelón pig breed (organism) | Animal breeds Animal breeds
132170005 | Mexican Wattled pig breed (organism) | Animal breeds Animal breeds
132171009 | Dalland 080 pig breed (organism) | Animal breeds Animal breeds
132173007 | Monarch pig breed (organism) | Animal breeds Animal breeds
132174001 | Bisaro pig breed (organism) | Animal breeds Animal breeds
132175000 | Black Hairless pig breed (organism) | Animal breeds Animal breeds
132176004 | Black Mangalitsa pig breed (organism) | Animal breeds Animal breeds
132178003 | Borghigiana pig breed (organism) | Animal breeds Animal breeds
132179006 | Chianina pig breed (organism) | Animal breeds Animal breeds
132180009 | Cosentina pig breed (organism) | Animal breeds Animal breeds
132181008 | Cuino pig breed (organism) | Animal breeds Animal breeds
132182001 | Friuli Black pig breed (organism) | Animal breeds Animal breeds
132183006 | Fumati pig breed (organism) | Animal breeds Animal breeds
132184000 | Galician pig breed (organism) | Animal breeds Animal breeds
132185004 | German Berkshire pig breed (organism) | Animal breeds Animal breeds
132186003 | Ghori pig breed (organism) | Animal breeds Animal breeds
132187007 | Jianli pig breed (organism) | Animal breeds Animal breeds
132188002 | Lucanian pig breed (organism) | Animal breeds Animal breeds
132189005 | Maremmana pig breed (organism) | Animal breeds Animal breeds
132190001 | Miami pig breed (organism) | Animal breeds Animal breeds
132191002 | Montmorillon pig breed (organism) | Animal breeds Animal breeds
132192009 | Old Swedish Spotted pig breed (organism) | Animal breeds Animal breeds
132193004 | Oliventina pig breed (organism) | Animal breeds Animal breeds
132194005 | Parmense pig breed (organism) | Animal breeds Animal breeds
132195006 | Romagnola pig breed (organism) | Animal breeds Animal breeds
132196007 | Siberian pig breed (organism) | Animal breeds Animal breeds
132197003 | Small White pig breed (organism) | Animal breeds Animal breeds
132198008 | Baltaret pig breed (organism) | Animal breeds Animal breeds
132199000 | Tunchang pig breed (organism) | Animal breeds Animal breeds
132200002 | Sterling pig breed (organism) | Animal breeds Animal breeds
132201003 | Vich pig breed (organism) | Animal breeds Animal breeds
132202005 | Vietnamese pig breed (organism) | Animal breeds Animal breeds
132203000 | Vitoria pig breed (organism) | Animal breeds Animal breeds
132204006 | Wai Chow pig breed (organism) | Animal breeds Animal breeds
132205007 | Yorkshire Blue and White pig breed (organism) | Animal breeds Animal breeds
132206008 | Dalland 020 pig breed (organism) | Animal breeds Animal breeds
132207004 | Wiltshire pig breed (organism) | Animal breeds Animal breeds
132208009 | Hamroc pig breed (organism) | Animal breeds Animal breeds
132209001 | DRU (TM) Terminals pig breed (organism) | Animal breeds Animal breeds
132210006 | Camborough 22 pig breed (organism) | Animal breeds Animal breeds
132211005 | Camborough 15 pig breed (organism) | Animal breeds Animal breeds
132212003 | PR 1050 pig breed (organism) | Animal breeds Animal breeds
132213008 | PR 1075 pig breed (organism) | Animal breeds Animal breeds
132214002 | Chryak PIC pig breed (organism) | Animal breeds Animal breeds
132215001 | Canadian Royal Blue pig breed (organism) | Animal breeds Animal breeds
132216000 | Line 500 Duroc pig breed (organism) | Animal breeds Animal breeds
132217009 | Bodmin 950 pig breed (organism) | Animal breeds Animal breeds
132218004 | Canadian Duroc pig breed (organism) | Animal breeds Animal breeds
132219007 | Canadian Hampshire pig breed (organism) | Animal breeds Animal breeds

132220001 | Ba Xuyen pig breed (organism) | Animal breeds Animal breeds
132221002 | Arapawa Island pig breed (organism) | Animal breeds Animal breeds
132222009 | Wuzhishan pig breed (organism) | Animal breeds Animal breeds
132223004 | Philippine Native pig breed (organism) | Animal breeds Animal breeds
132224005 | Sinclair Miniature pig breed (organism) | Animal breeds Animal breeds
132225006 | Saddleback pig breed (organism) | Animal breeds Animal breeds
132226007 | Yucatan Miniature pig breed (organism) | Animal breeds Animal breeds
132227003 | Bantu pig breed (organism) | Animal breeds Animal breeds
132228008 | Tibetan pig breed (organism) | Animal breeds Animal breeds
132229000 | Turopolje pig breed (organism) | Animal breeds Animal breeds
132230005 | Vietnamese Pot-Bellied Pig pig breed (organism) | Animal breeds Animal breeds
132231009 | American Landrace pig breed (organism) | Animal breeds Animal breeds
132232002 | Swallow Belied Mangalitza pig breed (organism) | Animal breeds Animal breeds
132233007 | Fengjing pig breed (organism) | Animal breeds Animal breeds
132234001 | Finnish Landrace pig breed (organism) | Animal breeds Animal breeds
132235000 | Guinea Hog pig breed (organism) | Animal breeds Animal breeds
132236004 | Hezuo pig breed (organism) | Animal breeds Animal breeds
132237008 | Ossabaw Island pig breed (organism) | Animal breeds Animal breeds
132238003 | Kele pig breed (organism) | Animal breeds Animal breeds
132239006 | Krskopolje pig breed (organism) | Animal breeds Animal breeds
132240008 | Kunekune pig breed (organism) | Animal breeds Animal breeds
132241007 | Large Black-White pig breed (organism) | Animal breeds Animal breeds
132242000 | Lithuanian Native pig breed (organism) | Animal breeds Animal breeds
132243005 | Meishan pig breed (organism) | Animal breeds Animal breeds
132244004 | Jinhua pig breed (organism) | Animal breeds Animal breeds
132245003 | Ningxiang pig breed (organism) | Animal breeds Animal breeds
132246002 | Mora Romagnola pig breed (organism) | Animal breeds Animal breeds
132247006 | Mukota pig breed (organism) | Animal breeds Animal breeds
132248001 | Minzhu pig breed (organism) | Animal breeds Animal breeds
132249009 | Neijiang pig breed (organism) | Animal breeds Animal breeds
132250009 | Mulefoot pig breed (organism) | Animal breeds Animal breeds
132251008 | Normand pig breed (organism) | Animal breeds Animal breeds
132252001 | Angeln Saddleback pig breed (organism) | Animal breeds Animal breeds
132253006 | Greek Local pig breed (organism) | Animal breeds Animal breeds
132254000 | Icelandic pig breed (organism) | Animal breeds Animal breeds
132255004 | Casertana pig breed (organism) | Animal breeds Animal breeds
132256003 | Madonie-Sicilian pig breed (organism) | Animal breeds Animal breeds
132257007 | Sardinian pig breed (organism) | Animal breeds Animal breeds
132258002 | Sicilian pig breed (organism) | Animal breeds Animal breeds
132259005 | Zlotniki Spotted pig breed (organism) | Animal breeds Animal breeds
132260000 | Zlotniki White pig breed (organism) | Animal breeds Animal breeds
132261001 | Siska pig breed (organism) | Animal breeds Animal breeds
132262008 | Sumadija pig breed (organism) | Animal breeds Animal breeds
132263003 | Froxfield Pygmy pig breed (organism) | Animal breeds Animal breeds
132264009 | Danish Large White pig breed (organism) | Animal breeds Animal breeds
132265005 | Danish Duroc pig breed (organism) | Animal breeds Animal breeds
132266006 | Danish Hampshire pig breed (organism) | Animal breeds Animal breeds
132267002 | Piggham pig breed (organism) | Animal breeds Animal breeds
132268007 | New York Red pig breed (organism) | Animal breeds Animal breeds
132269004 | Finnish Yorkshire pig breed (organism) | Animal breeds Animal breeds
132270003 | Dutch Yorkshire pig breed (organism) | Animal breeds Animal breeds
132271004 | Pulawy pig breed (organism) | Animal breeds Animal breeds
132272006 | Pomeranian pig breed (organism) | Animal breeds Animal breeds
132273001 | Polish Landrace pig breed (organism) | Animal breeds Animal breeds
132274007 | Estonian Bacon pig breed (organism) | Animal breeds Animal breeds
132275008 | Latvian White pig breed (organism) | Animal breeds Animal breeds
132276009 | Lithuanian White pig breed (organism) | Animal breeds Animal breeds
132277000 | BKB-1 pig breed (organism) | Animal breeds Animal breeds
132278005 | Belorus Black Pied pig breed (organism) | Animal breeds Animal breeds
132279002 | Mirgorod pig breed (organism) | Animal breeds Animal breeds
132280004 | Liang Guang Small Spotted, Luchuan pig breed (organism) | Animal breeds Animal breeds
132281000 | Fujian Small pig breed (organism) | Animal breeds Animal breeds
132282007 | North Fujian Black-and-White pig breed (organism) | Animal breeds Animal breeds
132283002 | Fuan Spotted pig breed (organism) | Animal breeds Animal breeds
132284008 | Putian pig breed (organism) | Animal breeds Animal breeds
132285009 | Fuzhou Black pig breed (organism) | Animal breeds Animal breeds
132286005 | Minbei Spotted pig breed (organism) | Animal breeds Animal breeds
132287001 | Lantang pig breed (organism) | Animal breeds Animal breeds
132288006 | Liang Guang Small Spotted, Guangdong Small Ear pig breed (organism) | Animal breeds Animal breeds
132289003 | Longlin pig breed (organism) | Animal breeds Animal breeds
132290007 | Yuedong Black pig breed (organism) | Animal breeds Animal breeds
132291006 | Xiang pig breed (organism) | Animal breeds Animal breeds

132292004 | Cantonese pig breed (organism) | Animal breeds Animal breeds
132293009 | Jinhua, Dongyang pig breed (organism) | Animal breeds Animal breeds
132294003 | Jinhua, Yongkang pig breed (organism) | Animal breeds Animal breeds
132295002 | Daweizi pig breed (organism) | Animal breeds Animal breeds
132296001 | Huazhong Two-End Black pig breed (organism) | Animal breeds Animal breeds
132297005 | Huazhong Two-End Black, Jianli pig breed (organism) | Animal breeds Animal breeds
132298000 | Huazhong Two-End Black, Tongcheng pig breed (organism) | Animal breeds Animal breeds
132299008 | Huazhong Two-End Black, Satzeling pig breed (organism) | Animal breeds Animal breeds
132300000 | Ganzhongnan Spotted pig breed (organism) | Animal breeds Animal breeds
132301001 | Hang pig breed (organism) | Animal breeds Animal breeds
132302008 | Leping pig breed (organism) | Animal breeds Animal breeds
132303003 | Longyou Black pig breed (organism) | Animal breeds Animal breeds
132304009 | Wuyi Black pig breed (organism) | Animal breeds Animal breeds
132305005 | Lee-Sung pig breed (organism) | Animal breeds Animal breeds
132306006 | Lan-Yu pig breed (organism) | Animal breeds Animal breeds
132307002 | Vietnamese Yorkshire pig breed (organism) | Animal breeds Animal breeds
132308007 | Yujiang pig breed (organism) | Animal breeds Animal breeds
132309004 | Wanzhe Spotted pig breed (organism) | Animal breeds Animal breeds
132310009 | Wanzhe Spotted, Chunan Spotted pig breed (organism) | Animal breeds Animal breeds
132311008 | Wanzhe Spotted, Wannan Spotted pig breed (organism) | Animal breeds Animal breeds
132312001 | Shengxian Spotted pig breed (organism) | Animal breeds Animal breeds
132313006 | Qingping pig breed (organism) | Animal breeds Animal breeds
132314000 | Xiangxi Black pig breed (organism) | Animal breeds Animal breeds
132315004 | Bamaxiang pig breed (organism) | Animal breeds Animal breeds
132316003 | Taihu pig breed (organism) | Animal breeds Animal breeds
132317007 | Erhulian pig breed (organism) | Animal breeds Animal breeds
132318002 | Jiaxing Black pig breed (organism) | Animal breeds Animal breeds
132319005 | Mi pig breed (organism) | Animal breeds Animal breeds
132320004 | Shahutou pig breed (organism) | Animal breeds Animal breeds
132321000 | Jiaoxi pig breed (organism) | Animal breeds Animal breeds
132322007 | Shanghai White pig breed (organism) | Animal breeds Animal breeds
132323002 | Hubei White pig breed (organism) | Animal breeds Animal breeds
132324008 | Xinjin pig breed (organism) | Animal breeds Animal breeds
132325009 | Xinjin, Jilin Black pig breed (organism) | Animal breeds Animal breeds
132326005 | Xinjin, Ning-an pig breed (organism) | Animal breeds Animal breeds
132327001 | Í pig breed (organism) | Animal breeds Animal breeds
132328006 | DBI pig breed (organism) | Animal breeds Animal breeds
132329003 | Xinjin, Xinjin pig breed (organism) | Animal breeds Animal breeds
132330008 | Meixin pig breed (organism) | Animal breeds Animal breeds
132331007 | North East China Spotted pig breed (organism) | Animal breeds Animal breeds
132332000 | Fannong Spotted pig breed (organism) | Animal breeds Animal breeds
132333005 | Laoshan pig breed (organism) | Animal breeds Animal breeds
132334004 | Nanjing Black pig breed (organism) | Animal breeds Animal breeds
132335003 | Shanxi Black pig breed (organism) | Animal breeds Animal breeds
132336002 | Ganzhou White pig breed (organism) | Animal breeds Animal breeds
132337006 | Guangxi White pig breed (organism) | Animal breeds Animal breeds
132338001 | Hanzhong White pig breed (organism) | Animal breeds Animal breeds
132339009 | Lutai White pig breed (organism) | Animal breeds Animal breeds
132340006 | Yili White pig breed (organism) | Animal breeds Animal breeds
132341005 | Xinjiang White pig breed (organism) | Animal breeds Animal breeds
132342003 | BSI pig breed (organism) | Animal breeds Animal breeds
132343008 | Mong Cai pig breed (organism) | Animal breeds Animal breeds
132344002 | Lang Hong pig breed (organism) | Animal breeds Animal breeds
132345001 | Muong Khuong pig breed (organism) | Animal breeds Animal breeds
132346000 | Meo pig breed (organism) | Animal breeds Animal breeds
132347009 | Tong Con pig breed (organism) | Animal breeds Animal breeds
132348004 | Ha Bac pig breed (organism) | Animal breeds Animal breeds
132349007 | Thai Binh pig breed (organism) | Animal breeds Animal breeds
132350007 | Co pig breed (organism) | Animal breeds Animal breeds
132351006 | Swiss Improved Landrace pig breed (organism) | Animal breeds Animal breeds
132352004 | German Landrace B pig breed (organism) | Animal breeds Animal breeds
132353009 | Edelschwein pig breed (organism) | Animal breeds Animal breeds
132354003 | Swabian-Hall pig breed (organism) | Animal breeds Animal breeds
132355002 | Bentheim Black Pied pig breed (organism) | Animal breeds Animal breeds
132356001 | Baldinger Spotted pig breed (organism) | Animal breeds Animal breeds
132357005 | German Red Pied pig breed (organism) | Animal breeds Animal breeds
132358000 | German Cornwall pig breed (organism) | Animal breeds Animal breeds
132359008 | Göttingen Miniature pig breed (organism) | Animal breeds Animal breeds
132360003 | Munich Miniature pig breed (organism) | Animal breeds Animal breeds
132361004 | Leicoma pig breed (organism) | Animal breeds Animal breeds
132362006 | Schwerfurt Meat pig breed (organism) | Animal breeds Animal breeds
132363001 | Hungarian White pig breed (organism) | Animal breeds Animal breeds

132364007 | Hungahyb pig breed (organism) | Animal breeds Animal breeds
132365008 | Bulgarian Native pig breed (organism) | Animal breeds Animal breeds
132366009 | East Balkan pig breed (organism) | Animal breeds Animal breeds
132367000 | Kula pig breed (organism) | Animal breeds Animal breeds
132368005 | Nghia Binh pig breed (organism) | Animal breeds Animal breeds
132681007 | Bergamasca sheep breed (organism) | Animal breeds Animal breeds
132682000 | Portland sheep breed (organism) | Animal breeds Animal breeds
132684004 | Weisse Hornlose Heidschnucke sheep breed (organism) | Animal breeds Animal breeds
132685003 | Drents Heideschaap sheep breed (organism) | Animal breeds Animal breeds
132686002 | Kameroen sheep breed (organism) | Animal breeds Animal breeds
132687006 | Mergelland sheep breed (organism) | Animal breeds Animal breeds
132688001 | Ouessant sheep breed (organism) | Animal breeds Animal breeds
132689009 | Canadian Arcott sheep breed (organism) | Animal breeds Animal breeds
132690000 | Noordhollander sheep breed (organism) | Animal breeds Animal breeds
132691001 | Chocolate turkey breed (organism) | Animal breeds Animal breeds
132692008 | Lilac turkey breed (organism) | Animal breeds Animal breeds
132693003 | Silver Auburn turkey breed (organism) | Animal breeds Animal breeds
132695005 | Wild cross turkey (organism) | Animal breeds Animal breeds
132696006 | Matrouh chicken breed (organism) | Animal breeds Animal breeds
132697002 | Rijnlam-A sheep breed (organism) | Animal breeds Animal breeds
132698007 | Schoonebeker sheep breed (organism) | Animal breeds Animal breeds
132699004 | Wallis Blacknosed Sheep breed (organism) | Animal breeds Animal breeds
132700003 | Khaki Campbell breed duck (organism) | Animal breeds Animal breeds
132701004 | Newfoundland sheep breed (organism) | Animal breeds Animal breeds
132702006 | Wallis Country Sheep breed (organism) | Animal breeds Animal breeds
132703001 | Rideau Arcott sheep breed (organism) | Animal breeds Animal breeds
132704007 | Tukidale sheep breed (organism) | Animal breeds Animal breeds
132705008 | Polwarth sheep breed (organism) | Animal breeds Animal breeds
132706009 | Ryeland sheep breed (organism) | Animal breeds Animal breeds
132707000 | Thalli sheep breed (organism) | Animal breeds Animal breeds
132708005 | Tong sheep breed (organism) | Animal breeds Animal breeds
132709002 | Touabire sheep breed (organism) | Animal breeds Animal breeds
132710007 | Tunis sheep breed (organism) | Animal breeds Animal breeds
132711006 | Tyrol Mountain sheep breed (organism) | Animal breeds Animal breeds
132712004 | Uda sheep breed (organism) | Animal breeds Animal breeds
132713009 | Gray chicken breed (organism) | Animal breeds Animal breeds
132714003 | Hamburgs chicken breed (organism) | Animal breeds Animal breeds
132715002 | Gimmizah chicken breed (organism) | Animal breeds Animal breeds
132716001 | German Mutton Merino sheep breed (organism) | Animal breeds Animal breeds
132717005 | Medium-Wool Merino sheep breed (organism) | Animal breeds Animal breeds
132718000 | Fonthill Merino sheep breed (organism) | Animal breeds Animal breeds
132719008 | South African Mutton Merino sheep breed (organism) | Animal breeds Animal breeds
132720002 | Strong Wool Merino sheep breed (organism) | Animal breeds Animal breeds
132721003 | Poll Merino sheep breed (organism) | Animal breeds Animal breeds
132722005 | Fine Merino sheep breed (organism) | Animal breeds Animal breeds
132723000 | South African Merino sheep breed (organism) | Animal breeds Animal breeds
132724006 | Superfine Merino sheep breed (organism) | Animal breeds Animal breeds
132725007 | Dutch Bantam chicken breed (organism) | Animal breeds Animal breeds
132726008 | Silver Montazah chicken breed (organism) | Animal breeds Animal breeds
132727004 | Swiss Hen chicken breed (organism) | Animal breeds Animal breeds
132728009 | Styrian chicken breed (organism) | Animal breeds Animal breeds
132729001 | Old English Game chicken breed (organism) | Animal breeds Animal breeds
132730006 | Appenzell Bearded Hen chicken breed (organism) | Animal breeds Animal breeds
132731005 | Baden Wurttemburg horse breed (organism) | Animal breeds Animal breeds
132732003 | British Warmblood horse breed (organism) | Animal breeds Animal breeds
132733008 | Israeli horse breed (organism) | Animal breeds Animal breeds
132734002 | French Ardennais horse breed (organism) | Animal breeds Animal breeds
132735001 | Booroola Merino sheep breed (organism) | Animal breeds Animal breeds
132736000 | Cukurova horse breed (organism) | Animal breeds Animal breeds
132737009 | Czech Coldblood horse breed (organism) | Animal breeds Animal breeds
132738004 | Czechoslovakian Small Riding Horse horse breed (organism) | Animal breeds Animal breeds
132739007 | Jianchang horse breed (organism) | Animal breeds Animal breeds
132740009 | Jielin horse breed (organism) | Animal breeds Animal breeds
132741008 | Wielkopolski horse breed (organism) | Animal breeds Animal breeds
132742001 | Eleia horse breed (organism) | Animal breeds Animal breeds
132743006 | English Cob horse breed (organism) | Animal breeds Animal breeds
132744000 | Welsh Pony horse breed (organism) | Animal breeds Animal breeds
132745004 | Welsh Pony of Cob Type horse breed (organism) | Animal breeds Animal breeds
132746003 | English Hunter horse breed (organism) | Animal breeds Animal breeds
132747007 | Eriskay Pony horse breed (organism) | Animal breeds Animal breeds
132748002 | Hackney Pony horse breed (organism) | Animal breeds Animal breeds
132749005 | Estonian Draft horse breed (organism) | Animal breeds Animal breeds

132750005 | Heihe horse breed (organism) | Animal breeds Animal breeds
132751009 | Heilongkaing horse breed (organism) | Animal breeds Animal breeds
132752002 | Sulmtaler chicken breed (organism) | Animal breeds Animal breeds
132753007 | Svart Höna chicken breed (organism) | Animal breeds Animal breeds
132754001 | Vorwerks chicken breed (organism) | Animal breeds Animal breeds
132755000 | Westfalische Totleger chicken breed (organism) | Animal breeds Animal breeds
132756004 | Yamato Gunkei chicken breed (organism) | Animal breeds Animal breeds
132757008 | Danish Sport Pony horse breed (organism) | Animal breeds Animal breeds
132758003 | Kabarda horse breed (organism) | Animal breeds Animal breeds
132759006 | Kalmyk horse breed (organism) | Animal breeds Animal breeds
132760001 | Mangalarga Marchador horse breed (organism) | Animal breeds Animal breeds
132761002 | Don horse breed (organism) | Animal breeds Animal breeds
132762009 | Manipuri horse breed (organism) | Animal breeds Animal breeds
132763004 | Swiss Warmblood horse breed (organism) | Animal breeds Animal breeds
132764005 | Tavda horse breed (organism) | Animal breeds Animal breeds
132765006 | East Bulgarian horse breed (organism) | Animal breeds Animal breeds
132766007 | East Friesian (Old Type) horse breed (organism) | Animal breeds Animal breeds
132767003 | East Friesian Warmblood (Modern Type) horse breed (organism) | Animal breeds Animal breeds
132768008 | Kakhetian pig breed (organism) | Animal breeds Animal breeds
132769000 | West French White pig breed (organism) | Animal breeds Animal breeds
132770004 | Miniature Hereford cattle breed (organism) | Animal breeds Animal breeds
132771000 | Jem-Jem Zebu cattle breed (organism) | Animal breeds Animal breeds
132772007 | Minusin horse breed (organism) | Animal breeds Animal breeds
132773002 | Morochuco horse breed (organism) | Animal breeds Animal breeds
132774008 | French Trotter horse breed (organism) | Animal breeds Animal breeds
132775009 | Furioso horse breed (organism) | Animal breeds Animal breeds
132776005 | Murghese horse breed (organism) | Animal breeds Animal breeds
132777001 | Mytilene horse breed (organism) | Animal breeds Animal breeds
132778006 | Namib Desert Horse horse breed (organism) | Animal breeds Animal breeds
132779003 | Danish Oldenborg horse breed (organism) | Animal breeds Animal breeds
132780000 | Volynsk cattle breed (organism) | Animal breeds Animal breeds
132781001 | Senepol cattle breed (organism) | Animal breeds Animal breeds
132782008 | Shilluk cattle breed (organism) | Animal breeds Animal breeds
132783003 | Sar Planina sheep breed (organism) | Animal breeds Animal breeds
132784009 | Santa Inês sheep breed (organism) | Animal breeds Animal breeds
132785005 | Sahel-type sheep breed (organism) | Animal breeds Animal breeds
132786006 | Rygja sheep breed (organism) | Animal breeds Animal breeds
132787002 | Rya sheep breed (organism) | Animal breeds Animal breeds
132788007 | Moghani sheep breed (organism) | Animal breeds Animal breeds
132789004 | Rouge de l'Quest sheep breed (organism) | Animal breeds Animal breeds
132790008 | Soay sheep breed (organism) | Animal breeds Animal breeds
132791007 | South Suffolk sheep breed (organism) | Animal breeds Animal breeds
132792000 | South Wales Mountain sheep breed (organism) | Animal breeds Animal breeds
132793005 | Spælsau sheep breed (organism) | Animal breeds Animal breeds
132794004 | Spiegel sheep breed (organism) | Animal breeds Animal breeds
132795003 | St. Croix sheep breed (organism) | Animal breeds Animal breeds
132796002 | Steigar sheep breed (organism) | Animal breeds Animal breeds
132797006 | Steinschaf sheep breed (organism) | Animal breeds Animal breeds
132798001 | Welsh Mountain sheep breed (organism) | Animal breeds Animal breeds
132799009 | Swedish Fur Sheep breed (organism) | Animal breeds Animal breeds
132800008 | Teeswater sheep breed (organism) | Animal breeds Animal breeds
132801007 | Texel sheep breed (organism) | Animal breeds Animal breeds
132802000 | Pelibüey sheep breed (organism) | Animal breeds Animal breeds
132803005 | Morada Nova sheep breed (organism) | Animal breeds Animal breeds
132804004 | Balkhi sheep breed (organism) | Animal breeds Animal breeds
132805003 | Bavarian Forest sheep breed (organism) | Animal breeds Animal breeds
132806002 | Barbados Blackbelly sheep breed (organism) | Animal breeds Animal breeds
132807006 | Romney sheep breed (organism) | Animal breeds Animal breeds
132808001 | Awassi sheep breed (organism) | Animal breeds Animal breeds
132809009 | Arapawa Island sheep breed (organism) | Animal breeds Animal breeds
132810004 | Arabi sheep breed (organism) | Animal breeds Animal breeds
132811000 | Apennine sheep breed (organism) | Animal breeds Animal breeds
132812007 | American Tunis sheep breed (organism) | Animal breeds Animal breeds
132813002 | Balwen Welsh Mountain sheep breed (organism) | Animal breeds Animal breeds
132814008 | Priangan sheep breed (organism) | Animal breeds Animal breeds
132815009 | Rabo Largo sheep breed (organism) | Animal breeds Animal breeds
132816005 | Frieslands chicken breed (organism) | Animal breeds Animal breeds
132817001 | Ameraucana chicken breed (organism) | Animal breeds Animal breeds
132818006 | Åsbos chicken breed (organism) | Animal breeds Animal breeds
132819003 | Augsburger chicken breed (organism) | Animal breeds Animal breeds
132820009 | Bielefelder chicken breed (organism) | Animal breeds Animal breeds
132821008 | Norfolk Gray chicken breed (organism) | Animal breeds Animal breeds

132822001 | Hedemora chicken breed (organism) | Animal breeds Animal breeds
132823006 | Hungarian Yellow chicken breed (organism) | Animal breeds Animal breeds
132824000 | Iowa blue chicken breed (organism) | Animal breeds Animal breeds
132825004 | Red jungle fowl type chicken (organism) | Animal breeds Animal breeds
132826003 | Ko Shamo chicken breed (organism) | Animal breeds Animal breeds
132827007 | Kraienkoppe chicken breed (organism) | Animal breeds Animal breeds
132828002 | Lincolnshire Buff chicken breed (organism) | Animal breeds Animal breeds
132829005 | Tomaru chicken breed (organism) | Animal breeds Animal breeds
132830000 | Onagadori chicken breed (organism) | Animal breeds Animal breeds
132831001 | Manx Rumpies chicken breed (organism) | Animal breeds Animal breeds
132832008 | Maline chicken breed (organism) | Animal breeds Animal breeds
132833003 | Nankin chicken breed (organism) | Animal breeds Animal breeds
132834009 | Øland chicken breed (organism) | Animal breeds Animal breeds
132835005 | Ölansk Bantam chicken breed (organism) | Animal breeds Animal breeds
132836006 | Orust chicken breed (organism) | Animal breeds Animal breeds
132837002 | Penedesenca chicken breed (organism) | Animal breeds Animal breeds
132838007 | Rhode Island White chicken breed (organism) | Animal breeds Animal breeds
132839004 | Rosecomb Bantam chicken breed (organism) | Animal breeds Animal breeds
132840002 | Sablepoot chicken breed (organism) | Animal breeds Animal breeds
132841003 | Saipan Jungle Fowl chicken breed (organism) | Animal breeds Animal breeds
132842005 | Scots Dumpy chicken breed (organism) | Animal breeds Animal breeds
132843000 | Muban pig breed (organism) | Animal breeds Animal breeds
132844006 | Iban pig breed (organism) | Animal breeds Animal breeds
132845007 | Altay sheep breed (organism) | Animal breeds Animal breeds
132846008 | Faeroes sheep breed (organism) | Animal breeds Animal breeds
132847004 | Green chicken breed (organism) | Animal breeds Animal breeds
132848009 | Gallus Inauris chicken breed (organism) | Animal breeds Animal breeds
132849001 | Pitt Island sheep breed (organism) | Animal breeds Animal breeds
132850001 | Golden Montazah chicken breed (organism) | Animal breeds Animal breeds
132851002 | Pinzirita sheep breed (organism) | Animal breeds Animal breeds
132852009 | Sardinian sheep breed (organism) | Animal breeds Animal breeds
132853004 | East Friesian sheep breed (organism) | Animal breeds Animal breeds
132854005 | Ujumqin sheep breed (organism) | Animal breeds Animal breeds
132855006 | DLS sheep breed (organism) | Animal breeds Animal breeds
132856007 | Walachenschaf sheep breed (organism) | Animal breeds Animal breeds
132857003 | Outaouais Arcott sheep breed (organism) | Animal breeds Animal breeds
132858008 | Ossimi sheep breed (organism) | Animal breeds Animal breeds
132859000 | Bentheimer Landschaf sheep breed (organism) | Animal breeds Animal breeds
132860005 | Barbado sheep breed (organism) | Animal breeds Animal breeds
132861009 | Baluchi sheep breed (organism) | Animal breeds Animal breeds
132862002 | Shamo chicken breed (organism) | Animal breeds Animal breeds
132950000 | mule | Animal species Animal species
132951001 | American Indian Horse horse breed (organism) | Animal breeds Animal breeds
132952008 | American Mustang horse breed (organism) | Animal breeds Animal breeds
132953003 | American Quarter Horse horse breed (organism) | Animal breeds Animal breeds
132954009 | American Shetland pony horse breed (organism) | Animal breeds Animal breeds
132955005 | Anadolu horse breed (organism) | Animal breeds Animal breeds
132956006 | Andean horse breed (organism) | Animal breeds Animal breeds
132957002 | Anglo-Kabarda horse breed (organism) | Animal breeds Animal breeds
132958007 | Poitou Donkey breed (organism) | Animal breeds Animal breeds
132959004 | Mammoth Jack Stock Donkey breed (organism) | Animal breeds Animal breeds
132960009 | Narym horse breed (organism) | Animal breeds Animal breeds
132961008 | National Spotted Saddle Horse horse breed (organism) | Animal breeds Animal breeds
132962001 | Nigerian horse breed (organism) | Animal breeds Animal breeds
132963006 | North Swedish Trotter horse breed (organism) | Animal breeds Animal breeds
132964000 | Oriental Horse horse breed (organism) | Animal breeds Animal breeds
132965004 | Rhineland Heavy Draft horse breed (organism) | Animal breeds Animal breeds
132966003 | Romanian Saddle Horse horse breed (organism) | Animal breeds Animal breeds
132967007 | Rottal horse breed (organism) | Animal breeds Animal breeds
132968002 | Royal Canadian Mounted Police Horse horse breed (organism) | Animal breeds Animal breeds
132969005 | Russian Saddle Horse horse breed (organism) | Animal breeds Animal breeds
132970006 | Sable Island Horse horse breed (organism) | Animal breeds Animal breeds
132971005 | Panje horse breed (organism) | Animal breeds Animal breeds
132972003 | Patibarcina horse breed (organism) | Animal breeds Animal breeds
132973008 | Pechora horse breed (organism) | Animal breeds Animal breeds
132974002 | Peneia horse breed (organism) | Animal breeds Animal breeds
132975001 | Periangan horse breed (organism) | Animal breeds Animal breeds
132976000 | Persian Arab horse breed (organism) | Animal breeds Animal breeds
132977009 | Petiso Argentino horse breed (organism) | Animal breeds Animal breeds
132978004 | Polish Draft horse breed (organism) | Animal breeds Animal breeds
132979007 | Priob horse breed (organism) | Animal breeds Animal breeds
132980005 | Rahvan horse breed (organism) | Animal breeds Animal breeds

132981009 | Salerno horse breed (organism) | Animal breeds Animal breeds
132982002 | Sandalwood horse breed (organism) | Animal breeds Animal breeds
132983007 | Sandan horse breed (organism) | Animal breeds Animal breeds
132984001 | Pindos horse breed (organism) | Animal breeds Animal breeds
132985000 | Piquira Pony horse breed (organism) | Animal breeds Animal breeds
132986004 | Pleven horse breed (organism) | Animal breeds Animal breeds
132987008 | Large standard donkey (organism) | Animal breeds Animal breeds
132988003 | Standard donkey (organism) | Animal breeds Animal breeds
132989006 | Miniature donkey (organism) | Animal breeds Animal breeds
132990002 | Garrano tarpan horse X domestic horse breed (organism) | Animal breeds Animal breeds
132991003 | Konink tarpan horse X domestic horse breed (organism) | Animal breeds Animal breeds
132992005 | Asturian tarpan horse X domestic horse breed (organism) | Animal breeds Animal breeds
132993000 | Pottok tarpan horse X domestic horse breed (organism) | Animal breeds Animal breeds
132994006 | Russian Trotter horse breed (organism) | Animal breeds Animal breeds
132995007 | West African Barb horse breed (organism) | Animal breeds Animal breeds
132996008 | Fell Pony horse breed (organism) | Animal breeds Animal breeds
132997004 | National Show Horse horse breed (organism) | Animal breeds Animal breeds
132998009 | Zhemaichu horse breed (organism) | Animal breeds Animal breeds
132999001 | Yonaguni horse breed (organism) | Animal breeds Animal breeds
133000000 | Yakut horse breed (organism) | Animal breeds Animal breeds
133001001 | Tawleed horse breed (organism) | Animal breeds Animal breeds
133002008 | Western Sudan Pony horse breed (organism) | Animal breeds Animal breeds
133003003 | Welera Pony horse breed (organism) | Animal breeds Animal breeds
133004009 | Vyatka horse breed (organism) | Animal breeds Animal breeds
133005005 | Vladimir Heavy Draft horse breed (organism) | Animal breeds Animal breeds
133006006 | Vlaamperd horse breed (organism) | Animal breeds Animal breeds
133007002 | Ukrainian Saddle Horse horse breed (organism) | Animal breeds Animal breeds
133008007 | Tori horse breed (organism) | Animal breeds Animal breeds
133009004 | Tokara horse breed (organism) | Animal breeds Animal breeds
133010009 | New Kirgiz horse breed (organism) | Animal breeds Animal breeds
133011008 | Oldenburg horse breed (organism) | Animal breeds Animal breeds
133012001 | Misaki horse breed (organism) | Animal breeds Animal breeds
133013006 | Miyako horse breed (organism) | Animal breeds Animal breeds
133014000 | Mongolian horse breed (organism) | Animal breeds Animal breeds
133015004 | Waler horse breed (organism) | Animal breeds Animal breeds
133016003 | Dutch Draft horse breed (organism) | Animal breeds Animal breeds
133017007 | Egyptian horse breed (organism) | Animal breeds Animal breeds
133018002 | Estonian Native horse breed (organism) | Animal breeds Animal breeds
133019005 | Exmoor Pony horse breed (organism) | Animal breeds Animal breeds
133020004 | Faeroes Island Horse horse breed (organism) | Animal breeds Animal breeds
133021000 | Falabella horse breed (organism) | Animal breeds Animal breeds
133022007 | Dutch Warmblood horse breed (organism) | Animal breeds Animal breeds
133023002 | Dongola horse breed (organism) | Animal breeds Animal breeds
133024008 | Døle horse breed (organism) | Animal breeds Animal breeds
133025009 | Djerma horse breed (organism) | Animal breeds Animal breeds
133026005 | Deliboz horse breed (organism) | Animal breeds Animal breeds
133027001 | Dartmoor Pony horse breed (organism) | Animal breeds Animal breeds
133028006 | Crioulo horse breed (organism) | Animal breeds Animal breeds
133029003 | Finnhorse horse breed (organism) | Animal breeds Animal breeds
133030008 | Sanfratello horse breed (organism) | Animal breeds Animal breeds
133031007 | Morab horse breed (organism) | Animal breeds Animal breeds
133032000 | Moyle horse breed (organism) | Animal breeds Animal breeds
133033005 | Mustang horse breed (organism) | Animal breeds Animal breeds
133034004 | M'Bayar horse breed (organism) | Animal breeds Animal breeds
133035003 | Lusitano horse breed (organism) | Animal breeds Animal breeds
133036002 | Newfoundland Pony horse breed (organism) | Animal breeds Animal breeds
133037006 | Noma horse breed (organism) | Animal breeds Animal breeds
133038001 | Nooitgedacht Pony horse breed (organism) | Animal breeds Animal breeds
133039009 | Nordland horse breed (organism) | Animal breeds Animal breeds
133040006 | Noric horse breed (organism) | Animal breeds Animal breeds
133041005 | North Swedish Horse horse breed (organism) | Animal breeds Animal breeds
133042003 | Northeastern horse breed (organism) | Animal breeds Animal breeds
133043008 | Kisber Felver horse breed (organism) | Animal breeds Animal breeds
133044002 | Anglo-Arab horse breed (organism) | Animal breeds Animal breeds
133045001 | Nonius horse breed (organism) | Animal breeds Animal breeds
133046000 | Nooitgedacht horse breed (organism) | Animal breeds Animal breeds
133047009 | Iomud horse breed (organism) | Animal breeds Animal breeds
133048004 | Jutland horse breed (organism) | Animal breeds Animal breeds
133049007 | Karabair horse breed (organism) | Animal breeds Animal breeds
133050007 | Karabakh horse breed (organism) | Animal breeds Animal breeds
133051006 | Kazakh horse breed (organism) | Animal breeds Animal breeds
133052004 | Mangalarga horse breed (organism) | Animal breeds Animal breeds

133053009 | Kirdi Pony horse breed (organism) | Animal breeds Animal breeds
133054003 | Kiso horse breed (organism) | Animal breeds Animal breeds
133055002 | Kladruby horse breed (organism) | Animal breeds Animal breeds
133056001 | Knabstrup horse breed (organism) | Animal breeds Animal breeds
133057005 | Kushum horse breed (organism) | Animal breeds Animal breeds
133058000 | Kustanai horse breed (organism) | Animal breeds Animal breeds
133059008 | Latvian horse breed (organism) | Animal breeds Animal breeds
133060003 | Lithuanian Heavy Draft horse breed (organism) | Animal breeds Animal breeds
133061004 | Lokai horse breed (organism) | Animal breeds Animal breeds
133062006 | Kiger Mustang horse breed (organism) | Animal breeds Animal breeds
133063001 | Pony of the Americas horse breed (organism) | Animal breeds Animal breeds
133064007 | Pintabian horse breed (organism) | Animal breeds Animal breeds
133065008 | Pantaneiro horse breed (organism) | Animal breeds Animal breeds
133066009 | Orlov Trotter horse breed (organism) | Animal breeds Animal breeds
133067000 | Northern Ardennais horse breed (organism) | Animal breeds Animal breeds
133068005 | Abtenauer horse breed (organism) | Animal breeds Animal breeds
133069002 | Adaev horse breed (organism) | Animal breeds Animal breeds
133070001 | Albanian horse breed (organism) | Animal breeds Animal breeds
133071002 | Alter Real horse breed (organism) | Animal breeds Animal breeds
133072009 | American Bashkir Curly horse breed (organism) | Animal breeds Animal breeds
133073004 | Poitou Mule Producer horse breed (organism) | Animal breeds Animal breeds
133074005 | Polesian horse breed (organism) | Animal breeds Animal breeds
133075006 | Sardinian Anglo-Arab horse breed (organism) | Animal breeds Animal breeds
133076007 | Sardinian Pony horse breed (organism) | Animal breeds Animal breeds
133077003 | Sarvar horse breed (organism) | Animal breeds Animal breeds
133078008 | Schleswig horse breed (organism) | Animal breeds Animal breeds
133079000 | Schwarzwalder Fuchse horse breed (organism) | Animal breeds Animal breeds
133080002 | Senne horse breed (organism) | Animal breeds Animal breeds
133081003 | Shan horse breed (organism) | Animal breeds Animal breeds
133082005 | Silesian horse breed (organism) | Animal breeds Animal breeds
133083000 | Sini horse breed (organism) | Animal breeds Animal breeds
133084006 | Skyros horse breed (organism) | Animal breeds Animal breeds
133085007 | Slovak Warmblood horse breed (organism) | Animal breeds Animal breeds
133086008 | Sokolka horse breed (organism) | Animal breeds Animal breeds
133087004 | South African Miniature horse breed (organism) | Animal breeds Animal breeds
133088009 | South German Coldblood horse breed (organism) | Animal breeds Animal breeds
133089001 | Southwest Spanish Mustang horse breed (organism) | Animal breeds Animal breeds
133090005 | Spanish-American Horse horse breed (organism) | Animal breeds Animal breeds
133091009 | Spanish Anglo-Arab horse breed (organism) | Animal breeds Animal breeds
133092002 | Spanish Colonial Horse horse breed (organism) | Animal breeds Animal breeds
133093007 | Spiti horse breed (organism) | Animal breeds Animal breeds
133094001 | Sulawesi horse breed (organism) | Animal breeds Animal breeds
133095000 | Criollo horse breed (organism) | Animal breeds Animal breeds
133096004 | Hequ horse breed (organism) | Animal breeds Animal breeds
133097008 | Connemara Pony horse breed (organism) | Animal breeds Animal breeds
133098003 | Colorado Ranger horse breed (organism) | Animal breeds Animal breeds
133099006 | Dales Pony horse breed (organism) | Animal breeds Animal breeds
133100003 | Gotland horse breed (organism) | Animal breeds Animal breeds
133101004 | Chincoteague Pony horse breed (organism) | Animal breeds Animal breeds
133102006 | Hokkaido horse breed (organism) | Animal breeds Animal breeds
133103001 | Highland Pony horse breed (organism) | Animal breeds Animal breeds
133104007 | Groningen horse breed (organism) | Animal breeds Animal breeds
133105008 | Cuban Pinto horse breed (organism) | Animal breeds Animal breeds
133106009 | Fleuve horse breed (organism) | Animal breeds Animal breeds
133107000 | Golden American Saddlebred horse breed (organism) | Animal breeds Animal breeds
133108005 | Gidran horse breed (organism) | Animal breeds Animal breeds
133109002 | Gelderland horse breed (organism) | Animal breeds Animal breeds
133110007 | Galician Pony horse breed (organism) | Animal breeds Animal breeds
133111006 | Friesian horse breed (organism) | Animal breeds Animal breeds
133112004 | Frederiksborg horse breed (organism) | Animal breeds Animal breeds
133113009 | Fouta horse breed (organism) | Animal breeds Animal breeds
133114003 | Florida Cracker horse breed (organism) | Animal breeds Animal breeds
133115002 | Guangxi horse breed (organism) | Animal breeds Animal breeds
133116001 | Ardennes horse breed (organism) | Animal breeds Animal breeds
133117005 | American Walking Pony horse breed (organism) | Animal breeds Animal breeds
133118000 | Azteca horse breed (organism) | Animal breeds Animal breeds
133119008 | American Cream Draft horse breed (organism) | Animal breeds Animal breeds
133120002 | Altai horse breed (organism) | Animal breeds Animal breeds
133121003 | Akhal-Teke horse breed (organism) | Animal breeds Animal breeds
133122005 | Abyssinian horse breed (organism) | Animal breeds Animal breeds
133123000 | Bhirum Pony horse breed (organism) | Animal breeds Animal breeds
133124006 | Cheju horse breed (organism) | Animal breeds Animal breeds

133125007 | Cayuse horse breed (organism) | Animal breeds Animal breeds
133126008 | Caspian horse breed (organism) | Animal breeds Animal breeds
133127004 | Carthusian horse breed (organism) | Animal breeds Animal breeds
133128009 | Campolina horse breed (organism) | Animal breeds Animal breeds
133129001 | Byelorussian Harness horse breed (organism) | Animal breeds Animal breeds
133130006 | Budyonny horse breed (organism) | Animal breeds Animal breeds
133131005 | Australian Brumby horse breed (organism) | Animal breeds Animal breeds
133132003 | Australian Stock Horse horse breed (organism) | Animal breeds Animal breeds
133133008 | Basuto Pony horse breed (organism) | Animal breeds Animal breeds
133134002 | Bashkir Curly horse breed (organism) | Animal breeds Animal breeds
133135001 | Bashkir horse breed (organism) | Animal breeds Animal breeds
133136000 | Barb horse breed (organism) | Animal breeds Animal breeds
133137009 | Ban-ei horse breed (organism) | Animal breeds Animal breeds
133138004 | Carpathian Pony horse breed (organism) | Animal breeds Animal breeds
133139007 | Baluchi horse breed (organism) | Animal breeds Animal breeds
133140009 | Balearic horse breed (organism) | Animal breeds Animal breeds
133141008 | Chilean Corralero horse breed (organism) | Animal breeds Animal breeds
133142001 | Breton horse breed (organism) | Animal breeds Animal breeds
133143006 | Taishuh horse breed (organism) | Animal breeds Animal breeds
133144000 | Swedish Warmblood horse breed (organism) | Animal breeds Animal breeds
133145004 | Sudan Country-Bred horse breed (organism) | Animal breeds Animal breeds
133146003 | Spanish-Norman horse breed (organism) | Animal breeds Animal breeds
133147007 | Spanish Barb horse breed (organism) | Animal breeds Animal breeds
133148002 | Soviet Heavy Draft horse breed (organism) | Animal breeds Animal breeds
133149005 | Sorraia horse breed (organism) | Animal breeds Animal breeds
133150005 | Somali Pony horse breed (organism) | Animal breeds Animal breeds
133151009 | Tersk horse breed (organism) | Animal breeds Animal breeds
133152002 | Shagya horse breed (organism) | Animal breeds Animal breeds
133153007 | Selle Francais horse breed (organism) | Animal breeds Animal breeds
133154001 | Sanhe horse breed (organism) | Animal breeds Animal breeds
133155000 | Russian Heavy Draft horse breed (organism) | Animal breeds Animal breeds
133156004 | Rocky Mountain Horse horse breed (organism) | Animal breeds Animal breeds
133157008 | Racking Horse horse breed (organism) | Animal breeds Animal breeds
133158003 | Quarter Pony horse breed (organism) | Animal breeds Animal breeds
133159006 | Quarab horse breed (organism) | Animal breeds Animal breeds
133160001 | Single-Footing Horse horse breed (organism) | Animal breeds Animal breeds
133161002 | Tuy Hoa Hairless pig breed (organism) | Animal breeds Animal breeds
133162009 | Hainan pig breed (organism) | Animal breeds Animal breeds
133163004 | Sino-Vietnamese pig breed (organism) | Animal breeds Animal breeds
133164005 | Bo Xu pig breed (organism) | Animal breeds Animal breeds
133165006 | Thuoc Nhieu pig breed (organism) | Animal breeds Animal breeds
133166007 | Burmese pig breed (organism) | Animal breeds Animal breeds
133167003 | Chin pig breed (organism) | Animal breeds Animal breeds
133168008 | Siamese pig breed (organism) | Animal breeds Animal breeds
133169000 | Hailum pig breed (organism) | Animal breeds Animal breeds
133170004 | Kwai pig breed (organism) | Animal breeds Animal breeds
133171000 | Raad pig breed (organism) | Animal breeds Animal breeds
133172007 | Akha pig breed (organism) | Animal breeds Animal breeds
133173002 | South China pig breed (organism) | Animal breeds Animal breeds
133174008 | South China Black pig breed (organism) | Animal breeds Animal breeds
133175009 | Balinese pig breed (organism) | Animal breeds Animal breeds
133176005 | Diani pig breed (organism) | Animal breeds Animal breeds
133177001 | Kaman pig breed (organism) | Animal breeds Animal breeds
133178006 | Ashanti Dwarf pig breed (organism) | Animal breeds Animal breeds
133179003 | Koronadal pig breed (organism) | Animal breeds Animal breeds
133180000 | Ohmini pig breed (organism) | Animal breeds Animal breeds
133181001 | Clawn pig breed (organism) | Animal breeds Animal breeds
133182008 | Sus scrofa domestic pig X Japanese wild boar intragenus hybrid (organism) | Animal breeds Animal breeds
133183003 | Kangaroo Island pig breed (organism) | Animal breeds Animal breeds
133184009 | Captain Cooker pig breed (organism) | Animal breeds Animal breeds
133185005 | West African pig breed (organism) | Animal breeds Animal breeds
133186006 | Nigerian pig breed (organism) | Animal breeds Animal breeds
133187002 | Bakosi pig breed (organism) | Animal breeds Animal breeds
133188007 | Windsnyer pig breed (organism) | Animal breeds Animal breeds
133189004 | Kolbroek pig breed (organism) | Animal breeds Animal breeds
133190008 | South African Landrace pig breed (organism) | Animal breeds Animal breeds
133191007 | Bulgarian White pig breed (organism) | Animal breeds Animal breeds
133192000 | Bulgarian Landrace pig breed (organism) | Animal breeds Animal breeds
133193005 | Danube White pig breed (organism) | Animal breeds Animal breeds
133194004 | Dermantsi Pied pig breed (organism) | Animal breeds Animal breeds
133195003 | Romanian Native, Stocli pig breed (organism) | Animal breeds Animal breeds
133196002 | Romanian Native, Baltaret pig breed (organism) | Animal breeds Animal breeds

133197006 | Banat White pig breed (organism) | Animal breeds Animal breeds
133198001 | Bazna pig breed (organism) | Animal breeds Animal breeds
133199009 | Dobrogea Black pig breed (organism) | Animal breeds Animal breeds
133200007 | Strei pig breed (organism) | Animal breeds Animal breeds
133201006 | Romanian Large White pig breed (organism) | Animal breeds Animal breeds
133202004 | Romanian Meat Pig pig breed (organism) | Animal breeds Animal breeds
133203009 | Gurktal pig breed (organism) | Animal breeds Animal breeds
133204003 | Black Slavonian pig breed (organism) | Animal breeds Animal breeds
133205002 | Resava pig breed (organism) | Animal breeds Animal breeds
133206001 | Morava pig breed (organism) | Animal breeds Animal breeds
133207005 | Dzumalia pig breed (organism) | Animal breeds Animal breeds
133208000 | Macedonian pig breed (organism) | Animal breeds Animal breeds
133209008 | Albanian Native pig breed (organism) | Animal breeds Animal breeds
133210003 | Shkodra pig breed (organism) | Animal breeds Animal breeds
133211004 | Slovenian White pig breed (organism) | Animal breeds Animal breeds
133212006 | Subotica White pig breed (organism) | Animal breeds Animal breeds
133213001 | Prestice pig breed (organism) | Animal breeds Animal breeds
133214007 | Slovakian Black Pied pig breed (organism) | Animal breeds Animal breeds
133215008 | Czech Improved White pig breed (organism) | Animal breeds Animal breeds
133216009 | Moravian Large Yorkshire pig breed (organism) | Animal breeds Animal breeds
133217000 | Slovakian White pig breed (organism) | Animal breeds Animal breeds
133218005 | Slovhyb-1 pig breed (organism) | Animal breeds Animal breeds
133219002 | Nitra Hybrid pig breed (organism) | Animal breeds Animal breeds
133220008 | Synthetic SL98 pig breed (organism) | Animal breeds Animal breeds
133221007 | SL96 pig breed (organism) | Animal breeds Animal breeds
133222000 | Czech Meat pig breed (organism) | Animal breeds Animal breeds
133223005 | Czech Miniature pig breed (organism) | Animal breeds Animal breeds
133224004 | Small Polish Prick-Eared pig breed (organism) | Animal breeds Animal breeds
133225003 | Polesian pig breed (organism) | Animal breeds Animal breeds
133226002 | Nadbuzanska pig breed (organism) | Animal breeds Animal breeds
133227006 | Sarny pig breed (organism) | Animal breeds Animal breeds
133228001 | Krolevets pig breed (organism) | Animal breeds Animal breeds
133229009 | Polish Marsh pig breed (organism) | Animal breeds Animal breeds
133230004 | Large Polish Long-Eared pig breed (organism) | Animal breeds Animal breeds
133231000 | Herens cattle breed (organism) | Animal breeds Animal breeds
133232007 | Hinterwald cattle breed (organism) | Animal breeds Animal breeds
133233002 | Hungarian Gray cattle breed (organism) | Animal breeds Animal breeds
133234008 | Icelandic cattle breed (organism) | Animal breeds Animal breeds
133235009 | Illawarra cattle breed (organism) | Animal breeds Animal breeds
133236005 | Irish Moiled cattle breed (organism) | Animal breeds Animal breeds
133237001 | Israeli Holstein cattle breed (organism) | Animal breeds Animal breeds
133238006 | Istoben cattle breed (organism) | Animal breeds Animal breeds
133239003 | Jaulan cattle breed (organism) | Animal breeds Animal breeds
133240001 | Kazakh cattle breed (organism) | Animal breeds Animal breeds
133241002 | Kerry cattle breed (organism) | Animal breeds Animal breeds
133242009 | Kholmogory cattle breed (organism) | Animal breeds Animal breeds
133243004 | Latvian Brown cattle breed (organism) | Animal breeds Animal breeds
133244005 | Lincoln Red Shorthorn cattle breed (organism) | Animal breeds Animal breeds
133245006 | Lithuanian Red cattle breed (organism) | Animal breeds Animal breeds
133246007 | Mashona cattle breed (organism) | Animal breeds Animal breeds
133247003 | Milking Devon cattle breed (organism) | Animal breeds Animal breeds
133248008 | Mirandesa cattle breed (organism) | Animal breeds Animal breeds
133249000 | Mixed dairy cattle breed (organism) | Animal breeds Animal breeds
133250000 | Mongolian cattle breed (organism) | Animal breeds Animal breeds
133251001 | Morucha cattle breed (organism) | Animal breeds Animal breeds
133252008 | Kurdi cattle breed (organism) | Animal breeds Animal breeds
133253003 | N'dama cattle breed (organism) | Animal breeds Animal breeds
133254009 | Norwegian Red cattle breed (organism) | Animal breeds Animal breeds
133255005 | Parthenais cattle breed (organism) | Animal breeds Animal breeds
133256006 | Polish Red cattle breed (organism) | Animal breeds Animal breeds
133257002 | Rätien Gray cattle breed (organism) | Animal breeds Animal breeds
133258007 | Red and White cattle breed (organism) | Animal breeds Animal breeds
133259004 | Red Angus cattle breed (organism) | Animal breeds Animal breeds
133260009 | Red Polled Østland cattle breed (organism) | Animal breeds Animal breeds
133261008 | Red Steppe cattle breed (organism) | Animal breeds Animal breeds
133262001 | Reggiana cattle breed (organism) | Animal breeds Animal breeds
133263006 | Retinta cattle breed (organism) | Animal breeds Animal breeds
133264000 | Romosinuano cattle breed (organism) | Animal breeds Animal breeds
133265004 | Russian Black Pied cattle breed (organism) | Animal breeds Animal breeds
133266003 | RX3 cattle breed (organism) | Animal breeds Animal breeds
133267007 | Salorn cattle breed (organism) | Animal breeds Animal breeds
133268002 | Murboden cattle breed (organism) | Animal breeds Animal breeds

133269005 | San Martinero cattle breed (organism) | Animal breeds Animal breeds
133270006 | Sarabi cattle breed (organism) | Animal breeds Animal breeds
133271005 | Sharabi cattle breed (organism) | Animal breeds Animal breeds
133272003 | Shetland cattle breed (organism) | Animal breeds Animal breeds
133273008 | Simbrah cattle breed (organism) | Animal breeds Animal breeds
133274002 | South Devon cattle breed (organism) | Animal breeds Animal breeds
133275001 | Suffolk cattle breed (organism) | Animal breeds Animal breeds
133276000 | Sussex cattle breed (organism) | Animal breeds Animal breeds
133277009 | Swedish Red Polled cattle breed (organism) | Animal breeds Animal breeds
133278004 | Telemark cattle breed (organism) | Animal breeds Animal breeds
133279007 | Texas Longhorn cattle breed (organism) | Animal breeds Animal breeds
133280005 | Texon cattle breed (organism) | Animal breeds Animal breeds
133281009 | Vestland Fjord cattle breed (organism) | Animal breeds Animal breeds
133282002 | Vestland Red Polled cattle breed (organism) | Animal breeds Animal breeds
133283007 | Wagyu cattle breed (organism) | Animal breeds Animal breeds
133284001 | White Cáceres cattle breed (organism) | Animal breeds Animal breeds
133285000 | Xinjiang Brown cattle breed (organism) | Animal breeds Animal breeds
133286004 | Yanbian cattle breed (organism) | Animal breeds Animal breeds
133287008 | Zaobei cattle breed (organism) | Animal breeds Animal breeds
133288003 | Zavot cattle breed (organism) | Animal breeds Animal breeds
133289006 | Znamensk cattle breed (organism) | Animal breeds Animal breeds
133290002 | Alistana-Sanabresa cattle breed (organism) | Animal breeds Animal breeds
133291003 | Andalusian Blond cattle breed (organism) | Animal breeds Animal breeds
133292005 | Aosta Black Pied cattle breed (organism) | Animal breeds Animal breeds
133293000 | Aosta Chestnut cattle breed (organism) | Animal breeds Animal breeds
133294006 | Aosta Red Pied cattle breed (organism) | Animal breeds Animal breeds
133295007 | Aracena cattle breed (organism) | Animal breeds Animal breeds
133296008 | Argentine Friesian cattle breed (organism) | Animal breeds Animal breeds
133297004 | Armorican cattle breed (organism) | Animal breeds Animal breeds
133298009 | Arouquesa cattle breed (organism) | Animal breeds Animal breeds
133299001 | Aure et Saint-Girons cattle breed (organism) | Animal breeds Animal breeds
133300009 | Australian White cattle breed (organism) | Animal breeds Animal breeds
133301008 | Austrian Simmental cattle breed (organism) | Animal breeds Animal breeds
133302001 | Austrian Yellow cattle breed (organism) | Animal breeds Animal breeds
133303006 | Avetonou cattle breed (organism) | Animal breeds Animal breeds
133304000 | Avilena cattle breed (organism) | Animal breeds Animal breeds
133305004 | Avilena-Black Iberian cattle breed (organism) | Animal breeds Animal breeds
133306003 | Bakosi cattle breed (organism) | Animal breeds Animal breeds
133307007 | Bakwiri cattle breed (organism) | Animal breeds Animal breeds
133308002 | Baltic Black Pied cattle breed (organism) | Animal breeds Animal breeds
133309005 | Baoule cattle breed (organism) | Animal breeds Animal breeds
133310000 | Barrosa cattle breed (organism) | Animal breeds Animal breeds
133311001 | Barroso cattle breed (organism) | Animal breeds Animal breeds
133312008 | Bearnais cattle breed (organism) | Animal breeds Animal breeds
133313003 | Beef shorthorn cattle breed (organism) | Animal breeds Animal breeds
133314009 | Beef synthetic cattle breed (organism) | Animal breeds Animal breeds
133315005 | Beijing Black Pied cattle breed (organism) | Animal breeds Animal breeds
133316006 | Beiroa cattle breed (organism) | Animal breeds Animal breeds
133317002 | Belgian Black Pied Holsteincattle breed (organism) | Animal breeds Animal breeds
133318007 | Belgian Red Pied cattle breed (organism) | Animal breeds Animal breeds
133319004 | Belgian White and Red cattle breed (organism) | Animal breeds Animal breeds
133320005 | Belted Welsh cattle breed (organism) | Animal breeds Animal breeds
133321009 | Bestuzhev cattle breed (organism) | Animal breeds Animal breeds
133322002 | Betizuak cattle breed (organism) | Animal breeds Animal breeds
133323007 | Black Baldy cattle breed (organism) | Animal breeds Animal breeds
133324001 | Black Forest cattle breed (organism) | Animal breeds Animal breeds
133325000 | Black Iberian cattle breed (organism) | Animal breeds Animal breeds
133326004 | Northern Blue cattle breed (organism) | Animal breeds Animal breeds
133327008 | Bragado do Sorraia cattle breed (organism) | Animal breeds Animal breeds
133328003 | Braganca cattle breed (organism) | Animal breeds Animal breeds
133329006 | Brandrood Ijsselvee cattle breed (organism) | Animal breeds Animal breeds
133330001 | Brazilian Polled cattle breed (organism) | Animal breeds Animal breeds
133331002 | Breton Black Pied cattle breed (organism) | Animal breeds Animal breeds
133332009 | Brown Atlas cattle breed (organism) | Animal breeds Animal breeds
133333004 | Bulgarian Brown cattle breed (organism) | Animal breeds Animal breeds
133334005 | Bulgarian Red cattle breed (organism) | Animal breeds Animal breeds
133335006 | Burlina cattle breed (organism) | Animal breeds Animal breeds
133336007 | Burwash cattle breed (organism) | Animal breeds Animal breeds
133337003 | Byelorussian Red cattle breed (organism) | Animal breeds Animal breeds
133338008 | Byelorussian Synthetic cattle breed (organism) | Animal breeds Animal breeds
133339000 | Cabannina cattle breed (organism) | Animal breeds Animal breeds
133340003 | Caldeano cattle breed (organism) | Animal breeds Animal breeds

133341004 | Caldelana cattle breed (organism) | Animal breeds Animal breeds
133342006 | Calvana cattle breed (organism) | Animal breeds Animal breeds
133343001 | Camargue cattle breed (organism) | Animal breeds Animal breeds
133344007 | Cambodian cattle breed (organism) | Animal breeds Animal breeds
133345008 | Caracu cattle breed (organism) | Animal breeds Animal breeds
133346009 | Carpathian Brown cattle breed (organism) | Animal breeds Animal breeds
133347000 | Casanareno cattle breed (organism) | Animal breeds Animal breeds
133348005 | Central Russian Black Pied cattle breed (organism) | Animal breeds Animal breeds
133349002 | Chaouia cattle breed (organism) | Animal breeds Animal breeds
133350002 | Charollandais cattle breed (organism) | Animal breeds Animal breeds
133351003 | Char-swiss cattle breed (organism) | Animal breeds Animal breeds
133352005 | Korean Black cattle breed (organism) | Animal breeds Animal breeds
133353000 | Chesi cattle breed (organism) | Animal breeds Animal breeds
133354006 | Cheurfa cattle breed (organism) | Animal breeds Animal breeds
133355007 | Chiford cattle breed (organism) | Animal breeds Animal breeds
133356008 | Chimaine cattle breed (organism) | Animal breeds Animal breeds
133357004 | Chinampo cattle breed (organism) | Animal breeds Animal breeds
133358009 | Cildir cattle breed (organism) | Animal breeds Animal breeds
133359001 | COOPELSO 93 cattle breed (organism) | Animal breeds Animal breeds
133360006 | Thrace cattle breed (organism) | Animal breeds Animal breeds
133361005 | Corsican cattle breed (organism) | Animal breeds Animal breeds
133362003 | Cretan Lowland cattle breed (organism) | Animal breeds Animal breeds
133363008 | Cretan Mountain cattle breed (organism) | Animal breeds Animal breeds
133364002 | Croatian Red cattle breed (organism) | Animal breeds Animal breeds
133365001 | Cukurova cattle breed (organism) | Animal breeds Animal breeds
133366000 | Curraleiro cattle breed (organism) | Animal breeds Animal breeds
133367009 | Cyprus cattle breed (organism) | Animal breeds Animal breeds
133368004 | Czech Pied cattle breed (organism) | Animal breeds Animal breeds
133369007 | Dagestan Mountain cattle breed (organism) | Animal breeds Animal breeds
133370008 | Dairy Shorthorn cattle breed (organism) | Animal breeds Animal breeds
133371007 | Dairy Synthetic cattle breed (organism) | Animal breeds Animal breeds
133372000 | Danish Red Pied cattle breed (organism) | Animal breeds Animal breeds
133373005 | Dengchuan cattle breed (organism) | Animal breeds Animal breeds
133374004 | Dexter-Kerry cattle breed (organism) | Animal breeds Animal breeds
133375003 | Doran cattle breed (organism) | Animal breeds Animal breeds
133376002 | Dorna cattle breed (organism) | Animal breeds Animal breeds
133377006 | Dortyol cattle breed (organism) | Animal breeds Animal breeds
133378001 | East Anatolian Red cattle breed (organism) | Animal breeds Animal breeds
133379009 | East Finnish cattle breed (organism) | Animal breeds Animal breeds
133380007 | East Macedonian cattle breed (organism) | Animal breeds Animal breeds
133381006 | Epirus cattle breed (organism) | Animal breeds Animal breeds
133382004 | Estonian Black Pied cattle breed (organism) | Animal breeds Animal breeds
133383009 | Ferrandais cattle breed (organism) | Animal breeds Animal breeds
133384003 | Finnish Ayrshire cattle breed (organism) | Animal breeds Animal breeds
133385002 | Flemish cattle breed (organism) | Animal breeds Animal breeds
133386001 | Red Flemish cattle breed (organism) | Animal breeds Animal breeds
133387005 | Fort Cross cattle breed (organism) | Animal breeds Animal breeds
133388000 | Frati cattle breed (organism) | Animal breeds Animal breeds
133389008 | Estonian Native cattle breed (organism) | Animal breeds Animal breeds
133390004 | Faeroes cattle breed (organism) | Animal breeds Animal breeds
133391000 | French Brown cattle breed (organism) | Animal breeds Animal breeds
133392007 | Frijolillo cattle breed (organism) | Animal breeds Animal breeds
133393002 | FRS cattle breed (organism) | Animal breeds Animal breeds
133394008 | Gacko cattle breed (organism) | Animal breeds Animal breeds
133395009 | Gado da Terra cattle breed (organism) | Animal breeds Animal breeds
133396005 | Georgian Mountain cattle breed (organism) | Animal breeds Animal breeds
133397001 | German Black Pied cattle breed (organism) | Animal breeds Animal breeds
133398006 | German Black Pied Dairy cattle breed (organism) | Animal breeds Animal breeds
133399003 | Pechora cattle breed (organism) | Animal breeds Animal breeds
133400005 | Pee Wee cattle breed (organism) | Animal breeds Animal breeds
133401009 | Peloponnesus cattle breed (organism) | Animal breeds Animal breeds
133402002 | Pester cattle breed (organism) | Animal breeds Animal breeds
133403007 | Pie Rouge de l'Est cattle breed (organism) | Animal breeds Animal breeds
133404001 | Pisana cattle breed (organism) | Animal breeds Animal breeds
133405000 | German Brown cattle breed (organism) | Animal breeds Animal breeds
133406004 | German Shorthorn cattle breed (organism) | Animal breeds Animal breeds
133407008 | Ghana Shorthorn cattle breed (organism) | Animal breeds Animal breeds
133408003 | Glan-Donnersberg cattle breed (organism) | Animal breeds Animal breeds
133409006 | Gole cattle breed (organism) | Animal breeds Animal breeds
133410001 | Golpayegani cattle breed (organism) | Animal breeds Animal breeds
133411002 | Gorbatov Red cattle breed (organism) | Animal breeds Animal breeds
133412009 | Goryn cattle breed (organism) | Animal breeds Animal breeds

133413004 | Greater Caucasus cattle breed (organism) | Animal breeds Animal breeds
133414005 | Polish Black and White Lowland cattle breed (organism) | Animal breeds Animal breeds
133415006 | Polish Simmental cattle breed (organism) | Animal breeds Animal breeds
133416007 | Polled Jersey cattle breed (organism) | Animal breeds Animal breeds
133417003 | Polled Lincoln Red cattle breed (organism) | Animal breeds Animal breeds
133418008 | Polled Shorthorn (United States of America) cattle breed (organism) | Animal breeds Animal breeds
133419000 | Polled Simmental cattle breed (organism) | Animal breeds Animal breeds
133420006 | Greek Shorthorn cattle breed (organism) | Animal breeds Animal breeds
133421005 | Greek Steppe cattle breed (organism) | Animal breeds Animal breeds
133422003 | Gray Alpine cattle breed (organism) | Animal breeds Animal breeds
133423008 | Guadiana Spotted cattle breed (organism) | Animal breeds Animal breeds
133424002 | Guelma cattle breed (organism) | Animal breeds Animal breeds
133425001 | Harz Red cattle breed (organism) | Animal breeds Animal breeds
133426000 | Hawaiian wild cattle breed (organism) | Animal breeds Animal breeds
133427009 | Hereland cattle breed (organism) | Animal breeds Animal breeds
133428004 | Holgus cattle breed (organism) | Animal breeds Animal breeds
133429007 | Hrbinecky cattle breed (organism) | Animal breeds Animal breeds
133430002 | Polled Sussex cattle breed (organism) | Animal breeds Animal breeds
133431003 | Polled Welsh Black cattle breed (organism) | Animal breeds Animal breeds
133432005 | Pontremolese cattle breed (organism) | Animal breeds Animal breeds
133433000 | Preta cattle breed (organism) | Animal breeds Animal breeds
133434006 | Puerto Rican Criollo cattle breed (organism) | Animal breeds Animal breeds
133435007 | Pyrenean cattle breed (organism) | Animal breeds Animal breeds
133436008 | Huertana cattle breed (organism) | Animal breeds Animal breeds
133437004 | Hungarian Pied cattle breed (organism) | Animal breeds Animal breeds
133438009 | Hungarofries cattle breed (organism) | Animal breeds Animal breeds
133439001 | Improved Rodopi cattle breed (organism) | Animal breeds Animal breeds
133440004 | INRA 95 cattle breed (organism) | Animal breeds Animal breeds
133441000 | Italian Brown cattle breed (organism) | Animal breeds Animal breeds
133442007 | Italian Red Pied cattle breed (organism) | Animal breeds Animal breeds
133443002 | Japanese Black cattle breed (organism) | Animal breeds Animal breeds
133444008 | Japanese Brown cattle breed (organism) | Animal breeds Animal breeds
133445009 | Japanese Poll cattle breed (organism) | Animal breeds Animal breeds
133446005 | Qinchuan cattle breed (organism) | Animal breeds Animal breeds
133447001 | Ramo Grande cattle breed (organism) | Animal breeds Animal breeds
133448006 | Randall Lineback cattle breed (organism) | Animal breeds Animal breeds
133449003 | Red Galloway cattle breed (organism) | Animal breeds Animal breeds
133450003 | Regus cattle breed (organism) | Animal breeds Animal breeds
133451004 | Rendena cattle breed (organism) | Animal breeds Animal breeds
133452006 | Japanese Shorthorn cattle breed (organism) | Animal breeds Animal breeds
133453001 | Jarmelista cattle breed (organism) | Animal breeds Animal breeds
133454007 | Kabyle cattle breed (organism) | Animal breeds Animal breeds
133455008 | Kapsiki cattle breed (organism) | Animal breeds Animal breeds
133456009 | Katerini cattle breed (organism) | Animal breeds Animal breeds
133457000 | Kenran cattle breed (organism) | Animal breeds Animal breeds
133458005 | Khevsurian cattle breed (organism) | Animal breeds Animal breeds
133459002 | Kilis cattle breed (organism) | Animal breeds Animal breeds
133460007 | Kochi cattle breed (organism) | Animal breeds Animal breeds
133461006 | Korean Native cattle breed (organism) | Animal breeds Animal breeds
133462004 | Rhaetian Gray cattle breed (organism) | Animal breeds Animal breeds
133463009 | Rio Limon Dairy Criollo cattle breed (organism) | Animal breeds Animal breeds
133464003 | Rodopi cattle breed (organism) | Animal breeds Animal breeds
133465002 | Romanian Red cattle breed (organism) | Animal breeds Animal breeds
133466001 | Romanian Brown cattle breed (organism) | Animal breeds Animal breeds
133467005 | Russian Brown cattle breed (organism) | Animal breeds Animal breeds
133468000 | Kostroma cattle breed (organism) | Animal breeds Animal breeds
133469008 | Kravarsky cattle breed (organism) | Animal breeds Animal breeds
133470009 | Kuchinoshima cattle breed (organism) | Animal breeds Animal breeds
133471008 | Murray Gray cattle breed (organism) | Animal breeds Animal breeds
133472001 | Australian Shorthorn cattle breed (organism) | Animal breeds Animal breeds
133473006 | Kumamoto cattle breed (organism) | Animal breeds Animal breeds
133474000 | Lagune cattle breed (organism) | Animal breeds Animal breeds
133475004 | Lakenvelder cattle breed (organism) | Animal breeds Animal breeds
133476003 | Latvian Blue Roan cattle breed (organism) | Animal breeds Animal breeds
133477007 | La Velasquez cattle breed (organism) | Animal breeds Animal breeds
133478002 | Sardinian cattle breed (organism) | Animal breeds Animal breeds
133479005 | Sardinian brown cattle breed (organism) | Animal breeds Animal breeds
133480008 | Savinja Gray cattle breed (organism) | Animal breeds Animal breeds
133481007 | Sayaguesa cattle breed (organism) | Animal breeds Animal breeds
133482000 | Seferihisar cattle breed (organism) | Animal breeds Animal breeds
133483005 | Shkodra Red cattle breed (organism) | Animal breeds Animal breeds
133484004 | Lebanese cattle breed (organism) | Animal breeds Animal breeds

133485003 | Lebedin cattle breed (organism) | Animal breeds Animal breeds
133486002 | Lesser Caucasus cattle breed (organism) | Animal breeds Animal breeds
133487006 | Liberian Dwarf cattle breed (organism) | Animal breeds Animal breeds
133488001 | Libyan cattle breed (organism) | Animal breeds Animal breeds
133489009 | Lim cattle breed (organism) | Animal breeds Animal breeds
133490000 | Limiana cattle breed (organism) | Animal breeds Animal breeds
133491001 | Limpurger cattle breed (organism) | Animal breeds Animal breeds
133492008 | Lobi cattle breed (organism) | Animal breeds Animal breeds
133493003 | Lourdais cattle breed (organism) | Animal breeds Animal breeds
133494009 | Slovakian Pied cattle breed (organism) | Animal breeds Animal breeds
133495005 | Slovakian Pinzgau cattle breed (organism) | Animal breeds Animal breeds
133496006 | Slovenian Brown cattle breed (organism) | Animal breeds Animal breeds
133497002 | Somba cattle breed (organism) | Animal breeds Animal breeds
133498007 | South African Brown Swiss cattle breed (organism) | Animal breeds Animal breeds
133499004 | South Anatolian Red cattle breed (organism) | Animal breeds Animal breeds
133500008 | Lucerna cattle breed (organism) | Animal breeds Animal breeds
133501007 | Luxi cattle breed (organism) | Animal breeds Animal breeds
133502000 | Macedonian Busa cattle breed (organism) | Animal breeds Animal breeds
133503005 | Makaweli cattle breed (organism) | Animal breeds Animal breeds
133504004 | Marinhoa cattle breed (organism) | Animal breeds Animal breeds
133505003 | Maronesa cattle breed (organism) | Animal breeds Animal breeds
133506002 | Mazury cattle breed (organism) | Animal breeds Animal breeds
133507006 | Messaoria cattle breed (organism) | Animal breeds Animal breeds
133508001 | Metohija Red cattle breed (organism) | Animal breeds Animal breeds
133509009 | Mingrelian Red cattle breed (organism) | Animal breeds Animal breeds
133510004 | Southern Ukrainian cattle breed (organism) | Animal breeds Animal breeds
133511000 | Spanish Brown Alpine cattle breed (organism) | Animal breeds Animal breeds
133512007 | Suksun cattle breed (organism) | Animal breeds Animal breeds
133513002 | Swiss Black Pied cattle breed (organism) | Animal breeds Animal breeds
133514008 | Sychevka cattle breed (organism) | Animal breeds Animal breeds
133515009 | Sykia cattle breed (organism) | Animal breeds Animal breeds
133516005 | Minhota cattle breed (organism) | Animal breeds Animal breeds
133517001 | Minorcan cattle breed (organism) | Animal breeds Animal breeds
133518006 | Mishima cattle breed (organism) | Animal breeds Animal breeds
133519003 | Modenese cattle breed (organism) | Animal breeds Animal breeds
133520009 | Monchina cattle breed (organism) | Animal breeds Animal breeds
133521008 | Montafon cattle breed (organism) | Animal breeds Animal breeds
133522001 | Montbeliard cattle breed (organism) | Animal breeds Animal breeds
133523006 | Morenas del Noroeste cattle breed (organism) | Animal breeds Animal breeds
133524000 | Murcian cattle breed (organism) | Animal breeds Animal breeds
133525004 | Murnau-Werdenfels cattle breed (organism) | Animal breeds Animal breeds
133526003 | Tagil cattle breed (organism) | Animal breeds Animal breeds
133527007 | Tajma cattle breed (organism) | Animal breeds Animal breeds
133528002 | Tambov Red cattle breed (organism) | Animal breeds Animal breeds
133529005 | Tarina cattle breed (organism) | Animal breeds Animal breeds
133530000 | Thessaly cattle breed (organism) | Animal breeds Animal breeds
133531001 | Tinima cattle breed (organism) | Animal breeds Animal breeds
133532008 | Nantais cattle breed (organism) | Animal breeds Animal breeds
133533003 | Nejdi cattle breed (organism) | Animal breeds Animal breeds
133534009 | N'Gabou cattle breed (organism) | Animal breeds Animal breeds
133535005 | North Finncattle cattle breed (organism) | Animal breeds Animal breeds
133536006 | Oropa cattle breed (organism) | Animal breeds Animal breeds
133537002 | Oulmes Blond cattle breed (organism) | Animal breeds Animal breeds
133538007 | Pajuna cattle breed (organism) | Animal breeds Animal breeds
133539004 | Palmera cattle breed (organism) | Animal breeds Animal breeds
133540002 | Pankota Red cattle breed (organism) | Animal breeds Animal breeds
133541003 | Paphos cattle breed (organism) | Animal breeds Animal breeds
133542005 | Tinos cattle breed (organism) | Animal breeds Animal breeds
133543000 | Transylvanian Pinzgau cattle breed (organism) | Animal breeds Animal breeds
133544006 | Tropical Dairy Cattle cattle breed (organism) | Animal breeds Animal breeds
133545007 | Tropicana cattle breed (organism) | Animal breeds Animal breeds
133546008 | Tudanca cattle breed (organism) | Animal breeds Animal breeds
133547004 | Turino cattle breed (organism) | Animal breeds Animal breeds
133548009 | Turkish Brown cattle breed (organism) | Animal breeds Animal breeds
133549001 | Tux-Zillertal cattle breed (organism) | Animal breeds Animal breeds
133550001 | Tyrol Gray cattle breed (organism) | Animal breeds Animal breeds
133551002 | Abondance cattle breed (organism) | Animal breeds Animal breeds
133552009 | Ala-Tau cattle breed (organism) | Animal breeds Animal breeds
133553004 | Albanian Illyrian cattle breed (organism) | Animal breeds Animal breeds
133554005 | Albanian Dwarf cattle breed (organism) | Animal breeds Animal breeds
133555006 | Ukrainian Whiteheaded cattle breed (organism) | Animal breeds Animal breeds
133556007 | Ural Black Pied cattle breed (organism) | Animal breeds Animal breeds

133557003 | Valdres cattle breed (organism) | Animal breeds Animal breeds
133558008 | Vaynol cattle breed (organism) | Animal breeds Animal breeds
133559000 | Verinesa cattle breed (organism) | Animal breeds Animal breeds
133560005 | Vianesa cattle breed (organism) | Animal breeds Animal breeds
133561009 | Villard-de-Lans cattle breed (organism) | Animal breeds Animal breeds
133562002 | Vogelsberg cattle breed (organism) | Animal breeds Animal breeds
133563007 | Pie Rouge des Plaines cattle breed (organism) | Animal breeds Animal breeds
133564001 | Vorderwald cattle breed (organism) | Animal breeds Animal breeds
133565000 | West African Dwarf Shorthorn cattle breed (organism) | Animal breeds Animal breeds
133566004 | West Finnish cattle breed (organism) | Animal breeds Animal breeds
133567008 | West Macedonian cattle breed (organism) | Animal breeds Animal breeds
133568003 | Whitebred Shorthorn cattle breed (organism) | Animal breeds Animal breeds
133569006 | White Galloway cattle breed (organism) | Animal breeds Animal breeds
133570007 | White Welsh cattle breed (organism) | Animal breeds Animal breeds
133571006 | Witrik cattle breed (organism) | Animal breeds Animal breeds
133572004 | Yacumento cattle breed (organism) | Animal breeds Animal breeds
133573009 | Yaroslavl cattle breed (organism) | Animal breeds Animal breeds
133574003 | Yurino cattle breed (organism) | Animal breeds Animal breeds
133575002 | Aleppo cattle breed (organism) | Animal breeds Animal breeds
133576001 | Schwyz cattle breed (organism) | Animal breeds Animal breeds
133577005 | Busa cattle breed (organism) | Animal breeds Animal breeds
133578000 | Chiangus cattle breed (organism) | Animal breeds Animal breeds
133579008 | Hallingdal cattle breed (organism) | Animal breeds Animal breeds
133580006 | Danish Jersey cattle breed (organism) | Animal breeds Animal breeds
133581005 | Enderby Island cattle breed (organism) | Animal breeds Animal breeds
133582003 | German Angus cattle breed (organism) | Animal breeds Animal breeds
133583008 | Israeli Red cattle breed (organism) | Animal breeds Animal breeds
133584002 | Lineback cattle breed (organism) | Animal breeds Animal breeds
133585001 | Mertolenga cattle breed (organism) | Animal breeds Animal breeds
133586000 | Red Friesian cattle breed (organism) | Animal breeds Animal breeds
133587009 | Senegus cattle breed (organism) | Animal breeds Animal breeds
133588004 | Southern Crioulo cattle breed (organism) | Animal breeds Animal breeds
133589007 | Vosges cattle breed (organism) | Animal breeds Animal breeds
133590003 | Montanara cattle breed (organism) | Animal breeds Animal breeds
133591004 | Almanzorena cattle breed (organism) | Animal breeds Animal breeds
133592006 | Lorquina cattle breed (organism) | Animal breeds Animal breeds
133593001 | Calasparrena cattle breed (organism) | Animal breeds Animal breeds
133594007 | Amritmahal cattle breed (organism) | Animal breeds Animal breeds
133595008 | Bachaur cattle breed (organism) | Animal breeds Animal breeds
133596009 | Barka cattle breed (organism) | Animal breeds Animal breeds
133597000 | Bengali cattle breed (organism) | Animal breeds Animal breeds
133598005 | Bhagnari cattle breed (organism) | Animal breeds Animal breeds
133599002 | Boran cattle breed (organism) | Animal breeds Animal breeds
133600004 | Channi cattle breed (organism) | Animal breeds Animal breeds
133601000 | Cholistani cattle breed (organism) | Animal breeds Animal breeds
133602007 | Dajal cattle breed (organism) | Animal breeds Animal breeds
133603002 | Dangi cattle breed (organism) | Animal breeds Animal breeds
133604008 | Deoni cattle breed (organism) | Animal breeds Animal breeds
133605009 | Dhanni cattle breed (organism) | Animal breeds Animal breeds
133606005 | Gaolao cattle breed (organism) | Animal breeds Animal breeds
133607001 | Hallikar cattle breed (organism) | Animal breeds Animal breeds
133608006 | Hariana cattle breed (organism) | Animal breeds Animal breeds
133609003 | Indo-Brazilian cattle breed (organism) | Animal breeds Animal breeds
133610008 | Kangayam cattle breed (organism) | Animal breeds Animal breeds
133611007 | Kankrej cattle breed (organism) | Animal breeds Animal breeds
133612000 | Kenkatha cattle breed (organism) | Animal breeds Animal breeds
133613005 | Kherigarh cattle breed (organism) | Animal breeds Animal breeds
133614004 | Khillari cattle breed (organism) | Animal breeds Animal breeds
133615003 | Krishna Valley cattle breed (organism) | Animal breeds Animal breeds
133616002 | Lohani cattle breed (organism) | Animal breeds Animal breeds
133617006 | Malvi cattle breed (organism) | Animal breeds Animal breeds
133618001 | Mewati cattle breed (organism) | Animal breeds Animal breeds
133619009 | Nagori cattle breed (organism) | Animal breeds Animal breeds
133620003 | Nelore cattle breed (organism) | Animal breeds Animal breeds
133621004 | Nimari cattle breed (organism) | Animal breeds Animal breeds
133622006 | Ponwar cattle breed (organism) | Animal breeds Animal breeds
133623001 | Rath cattle breed (organism) | Animal breeds Animal breeds
133624007 | Rathi cattle breed (organism) | Animal breeds Animal breeds
133625008 | Red Sindhi cattle breed (organism) | Animal breeds Animal breeds
133626009 | Rojhan cattle breed (organism) | Animal breeds Animal breeds
133627000 | Sahiwal cattle breed (organism) | Animal breeds Animal breeds
133628005 | Siri zebu cattle breed (organism) | Animal breeds Animal breeds

133629002 | Tharparkar cattle breed (organism) | Animal breeds Animal breeds
133630007 | Zanzibar Zebu cattle breed (organism) | Animal breeds Animal breeds
133631006 | Arsi cattle breed (organism) | Animal breeds Animal breeds
133632004 | Atpadi Mahal cattle breed (organism) | Animal breeds Animal breeds
133633009 | Azaouak cattle breed (organism) | Animal breeds Animal breeds
133634003 | Azerbaijan Zebu cattle breed (organism) | Animal breeds Animal breeds
133635002 | Baggara cattle breed (organism) | Animal breeds Animal breeds
133636001 | Bambawa cattle breed (organism) | Animal breeds Animal breeds
133637005 | Bami cattle breed (organism) | Animal breeds Animal breeds
133638000 | Banyo cattle breed (organism) | Animal breeds Animal breeds
133639008 | Bargur cattle breed (organism) | Animal breeds Animal breeds
133640005 | Bari cattle breed (organism) | Animal breeds Animal breeds
133641009 | Bimal cattle breed (organism) | Animal breeds Animal breeds
133642002 | Borneo Zebu cattle breed (organism) | Animal breeds Animal breeds
133643007 | Butana cattle breed (organism) | Animal breeds Animal breeds
133644001 | Chittagong Red cattle breed (organism) | Animal breeds Animal breeds
133645000 | Cutchi cattle breed (organism) | Animal breeds Animal breeds
133646004 | Dairy Zebu of Uberaba cattle breed (organism) | Animal breeds Animal breeds
133647008 | Dashtiari cattle breed (organism) | Animal breeds Animal breeds
133648003 | Diali cattle breed (organism) | Animal breeds Animal breeds
133649006 | Didinga cattle breed (organism) | Animal breeds Animal breeds
133650006 | Dongola cattle breed (organism) | Animal breeds Animal breeds
133651005 | Fellata cattle breed (organism) | Animal breeds Animal breeds
133652003 | Turkmen zebu cattle breed (organism) | Animal breeds Animal breeds
133653008 | Abyssinian Highland Zebu cattle breed (organism) | Animal breeds Animal breeds
133654002 | Abyssinian Shorthorned Zebu cattle breed (organism) | Animal breeds Animal breeds
133655001 | Aceh cattle breed (organism) | Animal breeds Animal breeds
133656000 | Achham cattle breed (organism) | Animal breeds Animal breeds
133657009 | Garre cattle breed (organism) | Animal breeds Animal breeds
133658004 | Gasara cattle breed (organism) | Animal breeds Animal breeds
133659007 | Gobra cattle breed (organism) | Animal breeds Animal breeds
133660002 | Goomsur cattle breed (organism) | Animal breeds Animal breeds
133661003 | Gujamavu cattle breed (organism) | Animal breeds Animal breeds
133662005 | Leiqiong cattle breed (organism) | Animal breeds Animal breeds
133663000 | Hissar cattle breed (organism) | Animal breeds Animal breeds
133664006 | Ingessana cattle breed (organism) | Animal breeds Animal breeds
133665007 | Jamaica Brahman cattle breed (organism) | Animal breeds Animal breeds
133666008 | Jellicut cattle breed (organism) | Animal breeds Animal breeds
133667004 | Adamawa cattle breed (organism) | Animal breeds Animal breeds
133668009 | Aden Zebu cattle breed (organism) | Animal breeds Animal breeds
133669001 | Afghan cattle breed (organism) | Animal breeds Animal breeds
133670000 | Alambadi cattle breed (organism) | Animal breeds Animal breeds
133671001 | Umblachery cattle breed (organism) | Animal breeds Animal breeds
133672008 | Venezuelan Zebu cattle breed (organism) | Animal breeds Animal breeds
133673003 | Pantaneiro cattle breed (organism) | Animal breeds Animal breeds
133674009 | Jenubi cattle breed (organism) | Animal breeds Animal breeds
133675005 | Jiddu cattle breed (organism) | Animal breeds Animal breeds
133676006 | Jijjiga Zebu cattle breed (organism) | Animal breeds Animal breeds
133677002 | Kabota cattle breed (organism) | Animal breeds Animal breeds
133678007 | Kachcha Siri cattle breed (organism) | Animal breeds Animal breeds
133679004 | Kalakheri cattle breed (organism) | Animal breeds Animal breeds
133680001 | Kamdhino cattle breed (organism) | Animal breeds Animal breeds
133681002 | Kandahari cattle breed (organism) | Animal breeds Animal breeds
133682009 | Kaningan cattle breed (organism) | Animal breeds Animal breeds
133683004 | Wakwa cattle breed (organism) | Animal breeds Animal breeds
133684005 | White Fulani cattle breed (organism) | Animal breeds Animal breeds
133685006 | Yemeni Zebu cattle breed (organism) | Animal breeds Animal breeds
133686007 | Iranian Zebu cattle breed (organism) | Animal breeds Animal breeds
133687003 | Khorsan cattle breed (organism) | Animal breeds Animal breeds
133688008 | Polled Gir cattle breed (organism) | Animal breeds Animal breeds
133689000 | Kappiliyan cattle breed (organism) | Animal breeds Animal breeds
133690009 | Karamajong cattle breed (organism) | Animal breeds Animal breeds
133691008 | Kenana cattle breed (organism) | Animal breeds Animal breeds
133692001 | Kenya Boran cattle breed (organism) | Animal breeds Animal breeds
133693006 | Kenya Zebu cattle breed (organism) | Animal breeds Animal breeds
133694000 | Khamala cattle breed (organism) | Animal breeds Animal breeds
133695004 | Khurasani zebu cattle breed (organism) | Animal breeds Animal breeds
133696003 | Kilara cattle breed (organism) | Animal breeds Animal breeds
133697007 | Kinniya cattle breed (organism) | Animal breeds Animal breeds
133698002 | Konari cattle breed (organism) | Animal breeds Animal breeds
133699005 | Guzerat cattle breed (organism) | Animal breeds Animal breeds
133700006 | Tadzhik zebu cattle breed (organism) | Animal breeds Animal breeds

133701005 | Deogir cattle breed (organism) | Animal breeds Animal breeds
133702003 | Gayal cattle breed (organism) | Animal breeds Animal breeds
133703008 | American bison X cattle breed (organism) | Animal breeds Animal breeds
133704002 | Australian Braford cattle breed (organism) | Animal breeds Animal breeds
133705001 | Krishnagari cattle breed (organism) | Animal breeds Animal breeds
133706000 | Kumauni cattle breed (organism) | Animal breeds Animal breeds
133707009 | Ladakhi cattle breed (organism) | Animal breeds Animal breeds
133708004 | Latuka cattle breed (organism) | Animal breeds Animal breeds
133709007 | Lugware cattle breed (organism) | Animal breeds Animal breeds
133710002 | Madagascar Zebu cattle breed (organism) | Animal breeds Animal breeds
133711003 | Madaripur cattle breed (organism) | Animal breeds Animal breeds
133712005 | Magal cattle breed (organism) | Animal breeds Animal breeds
133713000 | Malawi Zebu cattle breed (organism) | Animal breeds Animal breeds
133714006 | Malnad Gidda cattle breed (organism) | Animal breeds Animal breeds
133715007 | Australian Friesian Sahiwal cattle breed (organism) | Animal breeds Animal breeds
133716008 | Braford cattle breed (organism) | Animal breeds Animal breeds
133717004 | Brahmousin cattle breed (organism) | Animal breeds Animal breeds
133718009 | Canchim cattle breed (organism) | Animal breeds Animal breeds
133719001 | Charbray cattle breed (organism) | Animal breeds Animal breeds
133720007 | Droughtmaster cattle breed (organism) | Animal breeds Animal breeds
133721006 | Mampati cattle breed (organism) | Animal breeds Animal breeds
133722004 | Manapari cattle breed (organism) | Animal breeds Animal breeds
133723009 | Maure cattle breed (organism) | Animal breeds Animal breeds
133724003 | Mazandarani cattle breed (organism) | Animal breeds Animal breeds
133725002 | Merauke cattle breed (organism) | Animal breeds Animal breeds
133727005 | Mhaswad cattle breed (organism) | Animal breeds Animal breeds
133728000 | Miniature Zebu cattle breed (organism) | Animal breeds Animal breeds
133729008 | Mongalla cattle breed (organism) | Animal breeds Animal breeds
133730003 | Morang cattle breed (organism) | Animal breeds Animal breeds
133731004 | Gelbray cattle breed (organism) | Animal breeds Animal breeds
133732006 | Jamaica Black cattle breed (organism) | Animal breeds Animal breeds
133733001 | Jamaica Hope cattle breed (organism) | Animal breeds Animal breeds
133734007 | Jamaica Red cattle breed (organism) | Animal breeds Animal breeds
133735008 | Karan Fries cattle breed (organism) | Animal breeds Animal breeds
133736009 | Karan Swiss cattle breed (organism) | Animal breeds Animal breeds
133737000 | Mozambique Angoni cattle breed (organism) | Animal breeds Animal breeds
133738005 | Mpwapwa cattle breed (organism) | Animal breeds Animal breeds
133739002 | Murle cattle breed (organism) | Animal breeds Animal breeds
133740000 | Nakali cattle breed (organism) | Animal breeds Animal breeds
133741001 | Nepalese Hill Zebu cattle breed (organism) | Animal breeds Animal breeds
133742008 | N'Gaoundere cattle breed (organism) | Animal breeds Animal breeds
133743003 | Nkedi cattle breed (organism) | Animal breeds Animal breeds
133744009 | North Bangladesh Gray cattle breed (organism) | Animal breeds Animal breeds
133745005 | North Somali Zebu cattle breed (organism) | Animal breeds Animal breeds
133746006 | Polled Guzerat cattle breed (organism) | Animal breeds Animal breeds
133747002 | Mandalong cattle breed (organism) | Animal breeds Animal breeds
133748007 | Australian Milking Zebu cattle breed (organism) | Animal breeds Animal breeds
133749004 | Red Brangus cattle breed (organism) | Animal breeds Animal breeds
133750004 | Santa Cruz cattle breed (organism) | Animal breeds Animal breeds
133751000 | Siboney cattle breed (organism) | Animal breeds Animal breeds
133752007 | Bambara cattle breed (organism) | Animal breeds Animal breeds
133753002 | Polled Nelore cattle breed (organism) | Animal breeds Animal breeds
133754008 | Prewakwa cattle breed (organism) | Animal breeds Animal breeds
133755009 | Pul-M'bor cattle breed (organism) | Animal breeds Animal breeds
133756005 | Punganur cattle breed (organism) | Animal breeds Animal breeds
133757001 | Ramgarhi cattle breed (organism) | Animal breeds Animal breeds
133758006 | Red Bororo cattle breed (organism) | Animal breeds Animal breeds
133759003 | Red Desert cattle breed (organism) | Animal breeds Animal breeds
133760008 | Red Kandhari cattle breed (organism) | Animal breeds Animal breeds
133761007 | Shakhansurri cattle breed (organism) | Animal breeds Animal breeds
133762000 | Sheko cattle breed (organism) | Animal breeds Animal breeds
133763005 | Bambey cattle breed (organism) | Animal breeds Animal breeds
133764004 | Batanes Black cattle breed (organism) | Animal breeds Animal breeds
133765003 | Borgou cattle breed (organism) | Animal breeds Animal breeds
133766002 | Brahorn cattle breed (organism) | Animal breeds Animal breeds
133767006 | Bralers cattle breed (organism) | Animal breeds Animal breeds
133768001 | Bra-Maine cattle breed (organism) | Animal breeds Animal breeds
133769009 | Shendi cattle breed (organism) | Animal breeds Animal breeds
133770005 | Shuwa cattle breed (organism) | Animal breeds Animal breeds
133771009 | Sinhala cattle breed (organism) | Animal breeds Animal breeds
133772002 | Sistani cattle breed (organism) | Animal breeds Animal breeds
133773007 | Small East African Zebu cattle breed (organism) | Animal breeds Animal breeds

133774001 | Sokoto Gudali cattle breed (organism) | Animal breeds Animal breeds
133775000 | Somali cattle breed (organism) | Animal breeds Animal breeds
133776004 | Sonkheri cattle breed (organism) | Animal breeds Animal breeds
133777008 | Son Valley cattle breed (organism) | Animal breeds Animal breeds
133778003 | South China Zebu cattle breed (organism) | Animal breeds Animal breeds
133779006 | Bra-Swiss cattle breed (organism) | Animal breeds Animal breeds
133780009 | Bravon cattle breed (organism) | Animal breeds Animal breeds
133781008 | Brazilian Dairy hybrid cattle (organism) | Animal breeds Animal breeds
133782001 | Burmese cattle breed (organism) | Animal breeds Animal breeds
133783006 | Bushuev cattle breed (organism) | Animal breeds Animal breeds
133784000 | Caiua cattle breed (organism) | Animal breeds Animal breeds
133785004 | South Malawi Zebu cattle breed (organism) | Animal breeds Animal breeds
133786003 | Sudanese Fulani cattle breed (organism) | Animal breeds Animal breeds
133787007 | Tabapua cattle breed (organism) | Animal breeds Animal breeds
133788002 | Tamankaduwa cattle breed (organism) | Animal breeds Animal breeds
133789005 | Tanzanian Zebu cattle breed (organism) | Animal breeds Animal breeds
133790001 | Tarai cattle breed (organism) | Animal breeds Animal breeds
133791002 | Thillari cattle breed (organism) | Animal breeds Animal breeds
133792009 | Toposa cattle breed (organism) | Animal breeds Animal breeds
133793004 | Toronke cattle breed (organism) | Animal breeds Animal breeds
133794005 | Toupouri cattle breed (organism) | Animal breeds Animal breeds
133795006 | Carazebu cattle breed (organism) | Animal breeds Animal breeds
133796007 | Central Asian Zebu cattle breed (organism) | Animal breeds Animal breeds
133797003 | Charford cattle breed (organism) | Animal breeds Animal breeds
133798008 | Cuban Criollo cattle breed (organism) | Animal breeds Animal breeds
133799000 | Cuban Zebu cattle breed (organism) | Animal breeds Animal breeds
133800001 | Dishty cattle breed (organism) | Animal breeds Animal breeds
133801002 | Djakore cattle breed (organism) | Animal breeds Animal breeds
133802009 | Gambian N'Dama cattle breed (organism) | Animal breeds Animal breeds
133803004 | Ghana Sanga cattle breed (organism) | Animal breeds Animal breeds
133804005 | Girolando cattle breed (organism) | Animal breeds Animal breeds
133805006 | Guzerando cattle breed (organism) | Animal breeds Animal breeds
133806007 | Hatton cattle breed (organism) | Animal breeds Animal breeds
133807003 | Ibage cattle breed (organism) | Animal breeds Animal breeds
133808008 | Iraqi cattle breed (organism) | Animal breeds Animal breeds
133809000 | Jerdi cattle breed (organism) | Animal breeds Animal breeds
133810005 | Jersind cattle breed (organism) | Animal breeds Animal breeds
133811009 | Jotko cattle breed (organism) | Animal breeds Animal breeds
133812002 | Kanem cattle breed (organism) | Animal breeds Animal breeds
133813007 | Keteku cattle breed (organism) | Animal breeds Animal breeds
133814001 | Lavinia cattle breed (organism) | Animal breeds Animal breeds
133815000 | Local Indian Dairy cattle breed (organism) | Animal breeds Animal breeds
133816004 | Mantiqueira cattle breed (organism) | Animal breeds Animal breeds
133817008 | Ndagu cattle breed (organism) | Animal breeds Animal breeds
133818003 | Normanzu cattle breed (organism) | Animal breeds Animal breeds
133819006 | Nuba Mountain cattle breed (organism) | Animal breeds Animal breeds
133820000 | Pabna cattle breed (organism) | Animal breeds Animal breeds
133821001 | Mixed Perijanero cattle breed (organism) | Animal breeds Animal breeds
133822008 | Pitangueiras cattle breed (organism) | Animal breeds Animal breeds
133823003 | Quasah cattle breed (organism) | Animal breeds Animal breeds
133824009 | Rana cattle (organism) | Animal breeds Animal breeds
133825005 | Ranger cattle (organism) | Animal breeds Animal breeds
133826006 | Renitelo cattle breed (organism) | Animal breeds Animal breeds
133827002 | Riopardenze cattle breed (organism) | Animal breeds Animal breeds
133828007 | Rustaqi cattle breed (organism) | Animal breeds Animal breeds
133829004 | Sabre cattle breed (organism) | Animal breeds Animal breeds
133830009 | Sahford cattle breed (organism) | Animal breeds Animal breeds
133831008 | Schwyz-Zeboid cattle breed (organism) | Animal breeds Animal breeds
133832001 | Suia cattle breed (organism) | Animal breeds Animal breeds
133833006 | Suisbu cattle breed (organism) | Animal breeds Animal breeds
133834000 | Sunandini cattle breed (organism) | Animal breeds Animal breeds
133835004 | Taino cattle breed (organism) | Animal breeds Animal breeds
133836003 | Thibar cattle breed (organism) | Animal breeds Animal breeds
133837007 | Toubou cattle breed (organism) | Animal breeds Animal breeds
133838002 | Tropical cattle breed (organism) | Animal breeds Animal breeds
133839005 | TSSH-1 cattle breed (organism) | Animal breeds Animal breeds
133840007 | Victoria cattle breed (organism) | Animal breeds Animal breeds
133841006 | Wokalup cattle breed (organism) | Animal breeds Animal breeds
133842004 | Madura cattle breed (organism) | Animal breeds Animal breeds
13487004 | Shire horse (organism) | Animal breeds Animal breeds
13544004 | Belted Galloway cattle breed (organism) | Animal breeds Animal breeds
13934009 | Panama sheep (organism) | Animal breeds Animal breeds

14063001 | FHC elite pig 9 (organism) | Animal breeds Animal breeds
14189004 | Measles | Immunization Target Disease Codes Immunization Target Disease Codes
14866005 | Hospital outpatient mental health center | Facility Type Code Value Set Facility Type Code Value Set
15443006 | Yuca pig (organism) | Animal breeds Animal breeds
15778005 | goose | Animal species Animal species
15961007 | British saddleback pig (organism) | Animal breeds Animal breeds
16015002 | Anglo nubian goat (organism) | Animal breeds Animal breeds
160237006 | History/symptoms | Investigation Type Investigation Type
160245001 | No current problems or disability | Condition/Problem/Diagnosis Codes Condition/Problem/Diagnosis Codes
16042001 | Beefmaster cattle breed (organism) | Animal breeds Animal breeds
17717005 | Pic Cambourgh pig (organism) | Animal breeds Animal breeds
1773006 | Free-standing radiology facility | Facility Type Code Value Set Facility Type Code Value Set
1789009 | Trakehner horse (organism) | Animal breeds Animal breeds
1814000 | Hospital outpatient geriatric health center | Facility Type Code Value Set Facility Type Code Value Set
18212001 | Boar power pig 72 (organism) | Animal breeds Animal breeds
182836005 | Medication review | Diagnostic attachment type Diagnostic attachment type
182895007 | Drug declined by patient | SNOMED CT Reason Medication Not Given Codes SNOMED CT Reason Medication Not Given Codes
182922004 | Dietary regime | Diet Codes Diet Codes
18299006 | Orpington chicken (organism) | Animal breeds Animal breeds
183932001 | Procedure contraindicated | Procedure Not Performed Reason (SNOMED-CT) Procedure Not Performed Reason (SNOMED-CT)
183944003 | Procedure refused | Procedure Not Performed Reason (SNOMED-CT) Procedure Not Performed Reason (SNOMED-CT)
1857005 | Gestational rubella syndrome | Immunization Target Disease Codes Immunization Target Disease Codes
18949003 | Change of dressing | Procedure Follow up Codes (SNOMED CT) Procedure Follow up Codes (SNOMED CT)
190753003 | Sucrose intolerance | AllergyIntolerance Substance/Product, Condition and Negation Codes AllergyIntolerance Substance/Product, Condition and Negation Codes
19356005 | Hunter horse (organism) | Animal breeds Animal breeds
19602009 | Fee-for-service private physicians' group office | Facility Type Code Value Set Facility Type Code Value Set
19770007 | Hereford pig (organism) | Animal breeds Animal breeds
20044005 | Pietrain pig (organism) | Animal breeds Animal breeds
20078004 | Substance abuse treatment center | Facility Type Code Value Set Facility Type Code Value Set
20280002 | Hampshire pig (organism) | Animal breeds Animal breeds
2034000 | White turkey (organism) | Animal breeds Animal breeds
20657003 | Meleagris gallopavo (organism) | Animal breeds Animal breeds
2081004 | Hospital ship | Facility Type Code Value Set Facility Type Code Value Set
21021000 | Large black pig (organism) | Animal breeds Animal breeds
21208000 | Saanen goat (organism) | Animal breeds Animal breeds
2124007 | Rambouillet sheep (organism) | Animal breeds Animal breeds
21295007 | Morgan horse (organism) | Animal breeds Animal breeds
21553004 | Luing cattle breed (organism) | Animal breeds Animal breeds
21921002 | Canadian cattle breed (organism) | Animal breeds Animal breeds
22330003 | Commercial white egg layer type chicken (organism) | Animal breeds Animal breeds
223366009 | Healthcare professional | Participant Roles Participant Roles
224687002 | Hospital-prison | Facility Type Code Value Set Facility Type Code Value Set
22506004 | British lop pig (organism) | Animal breeds Animal breeds
225113003 | Timed urine collection | Specimen collection methods Specimen collection methods
225164002 | Removal of ligature | Procedure Follow up Codes (SNOMED CT) Procedure Follow up Codes (SNOMED CT)
2253004 | Marans chicken (organism) | Animal breeds Animal breeds
22549003 | Hospital outpatient gynecology clinic | Facility Type Code Value Set Facility Type Code Value Set
225732001 | Hospital-community | Facility Type Code Value Set Facility Type Code Value Set
226355009 | Nutrients | Nutrient Modifier Codes Nutrient Modifier Codes
226529007 | Starchy food | Texture Modified Food Type Codes Texture Modified Food Type Codes
226760005 | Dairy foods | Texture Modified Food Type Codes Texture Modified Food Type Codes
226887002 | Dietary Fats and Oils | Texture Modified Food Type Codes Texture Modified Food Type Codes
22720009 | Belgian horse (organism) | Animal breeds Animal breeds
227210005 | Vegetables plus herbs and spices | Texture Modified Food Type Codes Texture Modified Food Type Codes
227415002 | Fruit Nuts and Seeds | Texture Modified Food Type Codes Texture Modified Food Type Codes
227518002 | Sauce seasonings and soups | Texture Modified Food Type Codes Texture Modified Food Type Codes
228049004 | Chopped food | Texture Modifier Codes Texture Modifier Codes
228053002 | Cut-up food | Texture Modifier Codes Texture Modifier Codes
228055009 | Liquidized food | Texture Modifier Codes Texture Modifier Codes
228056005 | Lumpy food | Texture Modifier Codes Texture Modifier Codes
228057001 | Semi-solid food | Texture Modifier Codes Texture Modifier Codes
228058006 | Single texture food | Texture Modifier Codes Texture Modifier Codes
228059003 | Soft food | Texture Modifier Codes Texture Modifier Codes
228060008 | Solid food | Texture Modifier Codes Texture Modifier Codes
22836000 | Vegetables | Texture Modified Food Type Codes Texture Modified Food Type Codes
229506003 | Scar tissue massage | Procedure Follow up Codes (SNOMED CT) Procedure Follow up Codes (SNOMED CT)
2333000 | Japanese chicken (organism) | Animal breeds Animal breeds
23392004 | Hospital outpatient otorhinolaryngology clinic | Facility Type Code Value Set Facility Type Code Value Set
23469003 | Domestic goose (organism) | Animal breeds Animal breeds

23629009 | Hays converter cattle breed (organism) | Animal breeds Animal breeds
23992007 | Black-winged bronze turkey (organism) | Animal breeds Animal breeds
241031001 | Removal of drain | Procedure Follow up Codes (SNOMED CT) Procedure Follow up Codes (SNOMED CT)
24111007 | FHC elite pig 3 (organism) | Animal breeds Animal breeds
242990004 | Drug not available for administration | SNOMED CT Reason Medication Not Given Codes SNOMED CT Reason Medication Not Given Codes
243144002 | Patient triggered inspiratory assistance (procedure) | Service Request Order Details Codes Service Request Order Details Codes
243150007 | Assisted controlled mandatory ventilation (procedure) | Service Request Order Details Codes Service Request Order Details Codes
24319000 | Boar power pig 414 (organism) | Animal breeds Animal breeds
243796009 | Context-dependent categories | Encounter Reason Codes Encounter Reason Codes
24438005 | Pekin duck (organism) | Animal breeds Animal breeds
24484000 | Severe | Condition/Diagnosis Severity Condition/Diagnosis Severity
24642003 | Psychiatry procedure or service | Procedure Category Codes (SNOMED CT) Procedure Category Codes (SNOMED CT)
248152002 | Female | Observation Reference Range Applies To Codes Observation Reference Range Applies To Codes
248153007 | Male | Observation Reference Range Applies To Codes Observation Reference Range Applies To Codes
24840008 | CPF pig (organism) | Animal breeds Animal breeds
24886005 | Penna palm turkey (organism) | Animal breeds Animal breeds
25327001 | Dorset sheep superbreed (organism) | Animal breeds Animal breeds
25369002 | Westphalian horse (organism) | Animal breeds Animal breeds
254291000 | Staging and scales | Condition Stage Type Condition Stage Type
255551008 | Posterior | Bodystructure Location Qualifier Bodystructure Location Qualifier
255561001 | Medial | Bodystructure Location Qualifier Bodystructure Location Qualifier
255604002 | Mild | Condition/Diagnosis Severity Condition/Diagnosis Severity
255620007 | Foods | Texture Modified Food Type Codes Texture Modified Food Type Codes
25660007 | Barbados sheep (organism) | Animal breeds Animal breeds
25681007 | Sexually transmitted disease health center | Facility Type Code Value Set Facility Type Code Value Set
25813002 | Holsteiner horse (organism) | Animal breeds Animal breeds
25854005 | Small white turkey (organism) | Animal breeds Animal breeds
25856007 | Boar power pig 929 (organism) | Animal breeds Animal breeds
260419006 | Projection | Media Collection View/Projection Media Collection View/Projection
260787004 | Physical object | SNOMED CT Supply Item SNOMED CT Supply Item
260998006 | Clinical staging (qualifier value) | Condition Stage Type Condition Stage Type
261023001 | Pathological staging (qualifier value) | Condition Stage Type Condition Stage Type
26105007 | Holstein-Friesian cattle breed (organism) | Animal breeds Animal breeds
261089000 | Inferior | Bodystructure Location Qualifier Bodystructure Location Qualifier
261122009 | Lower | Bodystructure Location Qualifier Bodystructure Location Qualifier
261183002 | Upper | Bodystructure Location Qualifier Bodystructure Location Qualifier
264217000 | Superior | Bodystructure Location Qualifier Bodystructure Location Qualifier
264331002 | Grain | Texture Modified Food Type Codes Texture Modified Food Type Codes
26525003 | White Park cattle breed (organism) | Animal breeds Animal breeds
266710000 | Drugs not taken/completed | SNOMED CT Drug Therapy Status codes SNOMED CT Drug Therapy Status codes
26699009 | New Forest pony (organism) | Animal breeds Animal breeds
267425008 | Lactose intolerance | AllergyIntolerance Substance/Product, Condition and Negation Codes AllergyIntolerance Substance/Product, Condition and Negation Codes
26837006 | American cream horse (organism) | Animal breeds Animal breeds
26973000 | American trotter horse (organism) | Animal breeds Animal breeds
271336007 | Examination / signs | Investigation Type Investigation Type
272379006 | Events | Encounter Reason Codes Encounter Reason Codes
272394005 | Technique | Observation Methods Observation Methods
272501009 | Sports facility | Facility Type Code Value Set Facility Type Code Value Set
273384008 | Consumer satisfaction questionnaire | Questionnaire Category Codes Questionnaire Category Codes
273479001 | General health questionnaire | Questionnaire Category Codes Questionnaire Category Codes
273601006 | Mental status questionnaire | Questionnaire Category Codes Questionnaire Category Codes
273820006 | Social support questionnaire | Questionnaire Category Codes Questionnaire Category Codes
274441001 | Suction drainage | Procedure Follow up Codes (SNOMED CT) Procedure Follow up Codes (SNOMED CT)
275576008 | Elderly assessment clinic | Facility Type Code Value Set Facility Type Code Value Set
27836007 | Pertussis | Immunization Target Disease Codes Immunization Target Disease Codes
278450005 | Finger-prick sampling | Specimen collection methods Specimen collection methods
28138009 | Slate turkey (organism) | Animal breeds Animal breeds
281657000 | Travel vaccinations | Immunization Reason Codes Immunization Reason Codes
28336001 | Brangus cattle breed (organism) | Animal breeds Animal breeds
28360002 | Swiss alpine goat (organism) | Animal breeds Animal breeds
284009009 | Route of administration values | SNOMED CT Route Codes SNOMED CT Route Codes
284546000 | Hospice facility | Facility Type Code Value Set Facility Type Code Value Set
28483003 | Simmental cattle breed (organism) | Animal breeds Animal breeds
2849009 | Hospital outpatient infectious disease clinic | Facility Type Code Value Set Facility Type Code Value Set
28647000 | Meat | Texture Modified Food Type Codes Texture Modified Food Type Codes
286812008 | Pressure controlled ventilation (procedure) | Service Request Order Details Codes Service Request Order Details Codes
28744004 | Black Welsh cattle breed (organism) | Animal breeds Animal breeds
29223008 | Boar power pig 565 (organism) | Animal breeds Animal breeds

29235007 | Pic line pig 26 (organism) | Animal breeds Animal breeds
29546006 | Faverolle chicken (organism) | Animal breeds Animal breeds
29615001 | La Fleche chicken (organism) | Animal breeds Animal breeds
29736007 | Syndrome of carbohydrate intolerance | AllergyIntolerance Substance/Product, Condition and Negation Codes AllergyIntolerance Substance/Product, Condition and Negation Codes
29881002 | Connor prairie pig (organism) | Animal breeds Animal breeds
30089001 | Toggenburg goat (organism) | Animal breeds Animal breeds
30221007 | Belgian bearded chicken (organism) | Animal breeds Animal breeds
30384003 | Brahma cattle breed (organism) | Animal breeds Animal breeds
30432005 | Broad breasted bronze turkey (organism) | Animal breeds Animal breeds
30448006 | Lacombe pig (organism) | Animal breeds Animal breeds
304784009 | Administrative form | Questionnaire Category Codes Questionnaire Category Codes
30549001 | Removal of suture | Procedure Follow up Codes (SNOMED CT) Procedure Follow up Codes (SNOMED CT)
30634003 | Tamworth pig (organism) | Animal breeds Animal breeds
30720007 | Boar power pig 84 (organism) | Animal breeds Animal breeds
308283009 | Discharge from hospital | Goal start event Goal start event
309898008 | Psychogeriatric day hospital | Facility Type Code Value Set Facility Type Code Value Set
309900005 | Care of the elderly day hospital | Facility Type Code Value Set Facility Type Code Value Set
3099004 | Romney marsh sheep (organism) | Animal breeds Animal breeds
310205006 | Private residential home | Facility Type Code Value Set Facility Type Code Value Set
310376006 | Immunization consent not given | Immunization Status Reason Codes Immunization Status Reason Codes
31628002 | Hospital outpatient family medicine clinic | Facility Type Code Value Set Facility Type Code Value Set
31633003 | Yorkshire coach horse (organism) | Animal breeds Animal breeds
32039001 | glass | Types of material for specimen containers Types of material for specimen containers
32074000 | Hospital-long term care | Facility Type Code Value Set Facility Type Code Value Set
32145006 | Romanov sheep (organism) | Animal breeds Animal breeds
3216001 | Lincoln red cattle breed (organism) | Animal breeds Animal breeds
32297006 | Boar power pig 48 (organism) | Animal breeds Animal breeds
32485007 | Admission to hospital | Goal start event Goal start event
32509001 | Black turkey (organism) | Animal breeds Animal breeds
32540008 | Commercial meat type chicken (organism) | Animal breeds Animal breeds
3260001 | Duroc pig (organism) | Animal breeds Animal breeds
32683006 | FHC elite pig 7 (organism) | Animal breeds Animal breeds
32938007 | Gir cattle breed (organism) | Animal breeds Animal breeds
33022008 | Hospital-based outpatient clinic or department--OTHER-NOT LISTED | Facility Type Code Value Set Facility Type Code Value Set
331006 | Hospital outpatient rheumatology clinic | Facility Type Code Value Set Facility Type Code Value Set
33212007 | Boar power pig 616 (organism) | Animal breeds Animal breeds
33224000 | Phoenix chicken (organism) | Animal breeds Animal breeds
33463005 | Fluid | Nutrient Modifier Codes Nutrient Modifier Codes
33551003 | Kentucky red berkshire pig (organism) | Animal breeds Animal breeds
33607002 | Buttercup chicken (organism) | Animal breeds Animal breeds
340519003 | Lysine intolerance | AllergyIntolerance Substance/Product, Condition and Negation Codes AllergyIntolerance Substance/Product, Condition and Negation Codes
34200004 | Standardbred horse (organism) | Animal breeds Animal breeds
34595003 | Boar power pig 828 (organism) | Animal breeds Animal breeds
34618005 | Bos taurus (organism) | Animal breeds Animal breeds
351726001 | Below | Bodystructure Location Qualifier Bodystructure Location Qualifier
35229007 | Chianina cattle breed (organism) | Animal breeds Animal breeds
352730000 | Above | Bodystructure Location Qualifier Bodystructure Location Qualifier
35354009 | Equus caballus (organism) | Animal breeds Animal breeds
3566006 | Southdown sheep (organism) | Animal breeds Animal breeds
35839008 | Leghorn chicken (organism) | Animal breeds Animal breeds
35963001 | Removal of staples | Procedure Follow up Codes (SNOMED CT) Procedure Follow up Codes (SNOMED CT)
35971002 | Ambulatory care site--OTHER--NOT LISTED | Facility Type Code Value Set Facility Type Code Value Set
359825008 | Cytopathology, review of bronchioalveolar lavage specimen | Procedure Follow up Codes (SNOMED CT) Procedure Follow up Codes (SNOMED CT)
359839008 | Domestic fowl (organism) | Animal breeds Animal breeds
360957003 | Hospital outpatient allergy clinic | Facility Type Code Value Set Facility Type Code Value Set
360966004 | Hospital outpatient immunology clinic | Facility Type Code Value Set Facility Type Code Value Set
36111002 | Kleen leen black pig (organism) | Animal breeds Animal breeds
36125001 | Hospital-trauma center | Facility Type Code Value Set Facility Type Code Value Set
36187006 | Spotted pig (organism) | Animal breeds Animal breeds
36293008 | Hospital outpatient pain clinic | Facility Type Code Value Set Facility Type Code Value Set
363679005 | Imaging | Service Request Category Codes Service Request Category Codes
36570001 | Dekalb hybrid pig line 31 (organism) | Animal breeds Animal breeds
365858006 | Prognosis/outlook finding | Clinical Impression Prognosis Clinical Impression Prognosis
36653000 | Rubella | Immunization Target Disease Codes Immunization Target Disease Codes
36989005 | Mumps | Immunization Target Disease Codes Immunization Target Disease Codes
3729002 | Hospital outpatient pediatric clinic | Facility Type Code Value Set Facility Type Code Value Set
373873005 | Pharmaceutical / biologic product | Substance Code Substance Code
37546005 | Hospital outpatient rehabilitation clinic | Facility Type Code Value Set Facility Type Code Value Set
37550003 | Hospital outpatient dermatology clinic | Facility Type Code Value Set Facility Type Code Value Set

37812004 | Broad breasted white turkey (organism) | Animal breeds Animal breeds
38238005 | Hospital outpatient neurology clinic | Facility Type Code Value Set Facility Type Code Value Set
385356007 | Tumour stage finding | Condition Stage Condition Stage
385669000 | Successful | Procedure Outcome Codes (SNOMED CT) Procedure Outcome Codes (SNOMED CT)
385670004 | Partially successful | Procedure Outcome Codes (SNOMED CT) Procedure Outcome Codes (SNOMED CT)
385671000 | Unsuccessful | Procedure Outcome Codes (SNOMED CT) Procedure Outcome Codes (SNOMED CT)
386053000 | Patient evaluation procedure | Observation Methods Observation Methods
386089008 | Collection of coughed sputum | Specimen collection methods Specimen collection methods
386216000 | Childbirth | Goal start event Goal start event
3872000 | Beltsville white turkey (organism) | Animal breeds Animal breeds
387713003 | Surgical procedure | Procedure Category Codes (SNOMED CT) Procedure Category Codes (SNOMED CT)
387961004 | Kingdom Animalia | ConformanceUseContext ConformanceUseContext
388445009 | horse | Animal species Animal species
39350007 | Private physicians' group office | Facility Type Code Value Set Facility Type Code Value Set
394539006 | Pediatric surgery | Practice Setting Code Value Set Practice Setting Code Value Set
394576009 | Surgical-Accident & emergency | Practice Setting Code Value Set Practice Setting Code Value Set
394577000 | Anesthetics | Practice Setting Code Value Set Practice Setting Code Value Set
394578005 | Audiological medicine | Practice Setting Code Value Set Practice Setting Code Value Set
394579002 | Cardiology | Practice Setting Code Value Set Practice Setting Code Value Set
394580004 | Clinical genetics | Practice Setting Code Value Set Practice Setting Code Value Set
394581000 | Community medicine | Practice Setting Code Value Set Practice Setting Code Value Set
394582007 | Dermatology | Practice Setting Code Value Set Practice Setting Code Value Set
394583002 | Endocrinology | Practice Setting Code Value Set Practice Setting Code Value Set
394584008 | Gastroenterology | Practice Setting Code Value Set Practice Setting Code Value Set
394585009 | Obstetrics and gynecology | Practice Setting Code Value Set Practice Setting Code Value Set
394586005 | Gynecology | Practice Setting Code Value Set Practice Setting Code Value Set
394587001 | Psychiatry | Practice Setting Code Value Set Practice Setting Code Value Set
394588006 | Pediatric (Child and adolescent) psychiatry | Practice Setting Code Value Set Practice Setting Code Value Set
394589003 | Nephrology | Practice Setting Code Value Set Practice Setting Code Value Set
394590007 | Thoracic medicine | Practice Setting Code Value Set Practice Setting Code Value Set
394591006 | Neurology | Practice Setting Code Value Set Practice Setting Code Value Set
394592004 | Clinical oncology | Practice Setting Code Value Set Practice Setting Code Value Set
394593009 | Medical oncology | Practice Setting Code Value Set Practice Setting Code Value Set
394594003 | Ophthalmology | Practice Setting Code Value Set Practice Setting Code Value Set
394597005 | Histopathology | Practice Setting Code Value Set Practice Setting Code Value Set
394598000 | Immunopathology | Practice Setting Code Value Set Practice Setting Code Value Set
394599008 | Neuropathology | Practice Setting Code Value Set Practice Setting Code Value Set
394600006 | Clinical pharmacology | Practice Setting Code Value Set Practice Setting Code Value Set
394601005 | Clinical physiology | Practice Setting Code Value Set Practice Setting Code Value Set
394602003 | Rehabilitation | Practice Setting Code Value Set Practice Setting Code Value Set
394604002 | Surgery-Ear, nose and throat surgery | Practice Setting Code Value Set Practice Setting Code Value Set
394605001 | Surgery-Dental-Oral surgery | Practice Setting Code Value Set Practice Setting Code Value Set
394606000 | Surgery-Dentistry-Restorative dentistry | Practice Setting Code Value Set Practice Setting Code Value Set
394607009 | Pediatric dentistry | Practice Setting Code Value Set Practice Setting Code Value Set
394608004 | Surgery-Dental-Orthodontics | Practice Setting Code Value Set Practice Setting Code Value Set Practice Setting Code Value Set Practice Setting Code Value Set
394609007 | Surgery-general | Practice Setting Code Value Set Practice Setting Code Value Set
394610002 | Surgery-Neurosurgery | Practice Setting Code Value Set Practice Setting Code Value Set
394611003 | Surgery-Plastic surgery | Practice Setting Code Value Set Practice Setting Code Value Set
394612005 | Urology | Practice Setting Code Value Set Practice Setting Code Value Set
394649004 | Nuclear medicine | Practice Setting Code Value Set Practice Setting Code Value Set
394725008 | Diabetes medication review | Procedure Follow up Codes (SNOMED CT) Procedure Follow up Codes (SNOMED CT)
394730007 | Healthcare related organisation | Participant Roles Participant Roles
394732004 | Surgical specialty--OTHER-NOT LISTED | Practice Setting Code Value Set Practice Setting Code Value Set
394733009 | Medical specialties | ConformanceUseContext ConformanceUseContext
394759007 | Independent ambulatory care provider site--OTHER--NOT LISTED | Facility Type Code Value Set Facility Type Code Value Set
394777002 | Health encounter site--NOT LISTED | Facility Type Code Value Set Facility Type Code Value Set
394801008 | Surgery-Trauma and orthopedics | Practice Setting Code Value Set Practice Setting Code Value Set
394802001 | General medicine | Practice Setting Code Value Set Practice Setting Code Value Set
394803006 | Clinical hematology | Practice Setting Code Value Set Practice Setting Code Value Set
394804000 | Clinical cytogenetics and molecular genetics | Practice Setting Code Value Set Practice Setting Code Value Set
394806003 | Palliative medicine | Practice Setting Code Value Set Practice Setting Code Value Set
394807007 | Infectious diseases | Practice Setting Code Value Set Practice Setting Code Value Set
394808002 | Genito-urinary medicine | Practice Setting Code Value Set Practice Setting Code Value Set
394809005 | Clinical neuro-physiology | Practice Setting Code Value Set Practice Setting Code Value Set
394810000 | Rheumatology | Practice Setting Code Value Set Practice Setting Code Value Set
394811001 | Geriatric medicine | Practice Setting Code Value Set Practice Setting Code Value Set
394812008 | Dental medicine specialties | Practice Setting Code Value Set Practice Setting Code Value Set
394813003 | Medical ophthalmology | Practice Setting Code Value Set Practice Setting Code Value Set
394814009 | General practice | Practice Setting Code Value Set Practice Setting Code Value Set
394821009 | Occupational medicine | Practice Setting Code Value Set Practice Setting Code Value Set

394882004 | Pain management | Practice Setting Code Value Set Practice Setting Code Value Set
394908001 | Procedure stopped | Procedure Not Performed Reason (SNOMED-CT) Procedure Not Performed Reason (SNOMED-CT)
394913002 | Psychotherapy | Practice Setting Code Value Set Practice Setting Code Value Set
394914008 | Radiology | Practice Setting Code Value Set Practice Setting Code Value Set
394915009 | General pathology | Practice Setting Code Value Set Practice Setting Code Value Set
394916005 | Hematopathology | Practice Setting Code Value Set Practice Setting Code Value Set
39532001 | Norman coach horse (organism) | Animal breeds Animal breeds
39571003 | Buckeye chicken (organism) | Animal breeds Animal breeds
396488006 | Ariégeois pony breed (organism) | Animal breeds Animal breeds
396620009 | duck | Animal species Animal species
397430003 | Diphtheria due to Corynebacterium diphtheriae | Immunization Target Disease Codes Immunization Target Disease Codes
397640006 | Healthcare knowledge finding | Care Plan Activity Outcome Care Plan Activity Outcome
398102009 | Acute poliomyelitis | Immunization Target Disease Codes Immunization Target Disease Codes
39855006 | Wiltshire horn sheep (organism) | Animal breeds Animal breeds
39913001 | Residential school infirmary | Facility Type Code Value Set Facility Type Code Value Set
3997000 | Pony (organism) | Animal breeds Animal breeds
39972003 | Sodium | Nutrient Modifier Codes Nutrient Modifier Codes
400003 | Pinzgauer cattle breed (organism) | Animal breeds Animal breeds
404684003 | Clinical finding | Flag Code Flag Code
405607001 | Ambulatory surgery center | Facility Type Code Value Set Facility Type Code Value Set
406660008 | Galway sheep breed (organism) | Animal breeds Animal breeds
406663005 | Ukrainian steppe white pig (organism) | Animal breeds Animal breeds
406711007 | Brabant horse (organism) | Animal breeds Animal breeds
406714004 | Gypsy Vanner horse (organism) | Animal breeds Animal breeds
406715003 | Murgese horse (organism) | Animal breeds Animal breeds
406721004 | Mixed breed horse (organism) | Animal breeds Animal breeds
406722006 | Mixed breed sheep (organism) | Animal breeds Animal breeds
406723001 | Mixed breed chicken (organism) | Animal breeds Animal breeds
407402001 | Warmblood horse breed (organism) | Animal breeds Animal breeds
408440000 | Public health medicine | Practice Setting Code Value Set Practice Setting Code Value Set
408441001 | Surgery-Dental-Endodontics | Practice Setting Code Value Set Practice Setting Code Value Set
408443003 | General medical practice | Practice Setting Code Value Set Practice Setting Code Value Set
408444009 | Dental-General dental practice | Practice Setting Code Value Set Practice Setting Code Value Set
408446006 | Gynecological oncology | Practice Setting Code Value Set Practice Setting Code Value Set
408447002 | Respite care | Practice Setting Code Value Set Practice Setting Code Value Set
408448007 | Tropical medicine | Practice Setting Code Value Set Practice Setting Code Value Set
408449004 | Surgery-Dentistry--surgical | Practice Setting Code Value Set Practice Setting Code Value Set
408450004 | Sleep studies | Practice Setting Code Value Set Practice Setting Code Value Set
408454008 | Clinical microbiology | Practice Setting Code Value Set Practice Setting Code Value Set
408455009 | Radiology-Interventional radiology | Practice Setting Code Value Set Practice Setting Code Value Set
408459003 | Pediatric cardiology | Practice Setting Code Value Set Practice Setting Code Value Set
408460008 | Surgery-Dental-Prosthetic dentistry (Prosthodontics) | Practice Setting Code Value Set Practice Setting Code Value Set Practice Setting Code Value Set Practice Setting Code Value Set
408461007 | Surgery-Dental-Periodontal surgery | Practice Setting Code Value Set Practice Setting Code Value Set
408462000 | Burns care | Practice Setting Code Value Set Practice Setting Code Value Set
408463005 | Surgery-Vascular | Practice Setting Code Value Set Practice Setting Code Value Set
408464004 | Surgery-Colorectal surgery | Practice Setting Code Value Set Practice Setting Code Value Set
408465003 | Surgery-Dental-Oral and maxillofacial surgery | Practice Setting Code Value Set Practice Setting Code Value Set
408466002 | Surgery-Cardiac surgery | Practice Setting Code Value Set Practice Setting Code Value Set
408467006 | Adult mental illness | Practice Setting Code Value Set Practice Setting Code Value Set
408468001 | Learning disability | Practice Setting Code Value Set Practice Setting Code Value Set
408469009 | Surgery-Breast surgery | Practice Setting Code Value Set Practice Setting Code Value Set
408470005 | Obstetrics | Practice Setting Code Value Set Practice Setting Code Value Set
408471009 | Surgery-Cardiothoracic transplantation | Practice Setting Code Value Set Practice Setting Code Value Set
408472002 | Hepatology | Practice Setting Code Value Set Practice Setting Code Value Set
408474001 | Surgery-Hepatobiliary and pancreatic surgery | Practice Setting Code Value Set Practice Setting Code Value Set
408475000 | Diabetic medicine | Practice Setting Code Value Set Practice Setting Code Value Set
408476004 | Surgery-Bone and marrow transplantation | Practice Setting Code Value Set Practice Setting Code Value Set
408477008 | Surgery-Transplantation surgery | Practice Setting Code Value Set Practice Setting Code Value Set
408478003 | Critical care medicine | Practice Setting Code Value Set Practice Setting Code Value Set
408480009 | Clinical immunology | Practice Setting Code Value Set Practice Setting Code Value Set
409063005 | Counselling | Procedure Category Codes (SNOMED CT) Procedure Category Codes (SNOMED CT)
409073007 | Education | Procedure Category Codes (SNOMED CT) Procedure Category Codes (SNOMED CT)
409519008 | Contained casualty setting | Facility Type Code Value Set Facility Type Code Value Set
409905004 | Black Angus cattle breed (organism) | Animal breeds Animal breeds
409906003 | Mixed breed cattle (organism) | Animal breeds Animal breeds
409908002 | Masai cattle breed (organism) | Animal breeds Animal breeds
409909005 | Antwerp bearded bantam (organism) | Animal breeds Animal breeds
409910000 | Bantam (organism) | Animal breeds Animal breeds
409911001 | Moulard duck breed (organism) | Animal breeds Animal breeds
409967009 | Toxicology | Practice Setting Code Value Set Practice Setting Code Value Set

409968004 | Preventive medicine | Practice Setting Code Value Set Practice Setting Code Value Set
410001006 | Military medicine | Practice Setting Code Value Set Practice Setting Code Value Set
410005002 | Dive medicine | Practice Setting Code Value Set Practice Setting Code Value Set
410606002 | Social service procedure | Procedure Category Codes (SNOMED CT) Procedure Category Codes (SNOMED CT)
410684002 | Drug therapy status | SNOMED CT Drug Therapy Status codes SNOMED CT Drug Therapy Status codes
41092008 | Cleveland bay horse (organism) | Animal breeds Animal breeds
410942007 | Drug or medicament | SNOMED CT Medication Codes SNOMED CT Medication Codes
41290008 | Plymouth Rock chicken (organism) | Animal breeds Animal breeds
413427002 | Acquired fructose intolerance | AllergyIntolerance Substance/Product, Condition and Negation Codes AllergyIntolerance Substance/Product, Condition and Negation Codes
413456002 | Adult day care center | Facility Type Code Value Set Facility Type Code Value Set
413817003 | Child day care center | Facility Type Code Value Set Facility Type Code Value Set
41437006 | Jungle fowl chicken (organism) | Animal breeds Animal breeds
41561001 | Dekalb hybrid pig line 30 (organism) | Animal breeds Animal breeds
416064006 | Procedure not offered | Procedure Not Performed Reason (SNOMED-CT) Procedure Not Performed Reason (SNOMED-CT)
416237000 | Procedure not done | Procedure Not Performed Reason (SNOMED-CT) Procedure Not Performed Reason (SNOMED-CT)
416304004 | Osteopathic manipulative medicine | Practice Setting Code Value Set Practice Setting Code Value Set
416406003 | Procedure discontinued | Procedure Not Performed Reason (SNOMED-CT) Procedure Not Performed Reason (SNOMED-CT)
416432009 | Procedure not wanted | Procedure Not Performed Reason (SNOMED-CT) Procedure Not Performed Reason (SNOMED-CT)
417012009 | Mixed breed pig (organism) | Animal breeds Animal breeds
41706005 | Perendale sheep (organism) | Animal breeds Animal breeds
41738000 | Palomino horse (organism) | Animal breeds Animal breeds
41754002 | Lipizzaner horse (organism) | Animal breeds Animal breeds
418002000 | Pediatric oncology | Practice Setting Code Value Set Practice Setting Code Value Set
418018006 | Surgery-Dermatologic surgery | Practice Setting Code Value Set Practice Setting Code Value Set
418038007 | Propensity to adverse reactions to substance | AllergyIntolerance Substance/Product, Condition and Negation Codes AllergyIntolerance Substance/Product, Condition and Negation Codes
418058008 | Pediatric gastroenterology | Practice Setting Code Value Set Practice Setting Code Value Set
418112009 | Pulmonary medicine | Practice Setting Code Value Set Practice Setting Code Value Set
41844007 | Free-standing geriatric health center | Facility Type Code Value Set Facility Type Code Value Set
418518002 | Dialysis unit--hospital | Facility Type Code Value Set Facility Type Code Value Set
418535003 | Pediatric immunology | Practice Setting Code Value Set Practice Setting Code Value Set
418652005 | Pediatric hematology | Practice Setting Code Value Set Practice Setting Code Value Set
418862001 | Pediatric infectious diseases | Practice Setting Code Value Set Practice Setting Code Value Set
418960008 | Otolaryngology | Practice Setting Code Value Set Practice Setting Code Value Set
419043006 | Urological oncology | Practice Setting Code Value Set Practice Setting Code Value Set
419161000 | Unilateral left | Laterality Laterality
419170002 | Pediatric pulmonology | Practice Setting Code Value Set Practice Setting Code Value Set
419192003 | Internal medicine | Practice Setting Code Value Set Practice Setting Code Value Set
419321007 | Surgical oncology | Practice Setting Code Value Set Practice Setting Code Value Set
419365004 | Pediatric nephrology | Practice Setting Code Value Set Practice Setting Code Value Set
419465000 | Unilateral right | Laterality Laterality
419472004 | Pediatric rheumatology | Practice Setting Code Value Set Practice Setting Code Value Set
419492006 | Additional dosage instructions | SNOMED CT Additional Dosage Instructions SNOMED CT Additional Dosage Instructions
419610006 | Pediatric endocrinology | Practice Setting Code Value Set Practice Setting Code Value Set
419772000 | Family practice | Practice Setting Code Value Set Practice Setting Code Value Set
419815003 | Radiation oncology | Practice Setting Code Value Set Practice Setting Code Value Set
419955002 | Residential institution | Facility Type Code Value Set Facility Type Code Value Set
419983000 | Pediatric ophthalmology | Practice Setting Code Value Set Practice Setting Code Value Set
420112009 | Pediatric surgery-bone marrow transplantation | Practice Setting Code Value Set Practice Setting Code Value Set
420208008 | Pediatric genetics | Practice Setting Code Value Set Practice Setting Code Value Set
421661004 | Blood banking and transfusion medicine | Practice Setting Code Value Set Practice Setting Code Value Set
421967003 | Drug dose form | SNOMED CT Form Codes SNOMED CT Form Codes
422096002 | Dosing instruction fragment | SNOMED CT Administration Method Codes SNOMED CT Administration Method Codes
422191005 | Ophthalmic surgery | Practice Setting Code Value Set Practice Setting Code Value Set
424705003 | Bison bison X Simmental hybrid cattle breed (organism) | Animal breeds Animal breeds
425134008 | turkey | Animal species Animal species
425181009 | Bison bison X Bos taurus hybrid (organism) | Animal breeds Animal breeds
425620007 | metal | Types of material for specimen containers Types of material for specimen containers
42602001 | Minorca chicken (organism) | Animal breeds Animal breeds
42665001 | Nursing home | Facility Type Code Value Set Facility Type Code Value Set
427136006 | Saddlebred horse superbreed (organism) | Animal breeds Animal breeds
42724005 | American saddlebred horse (organism) | Animal breeds Animal breeds
428119001 | Procedure not indicated | Procedure Not Performed Reason (SNOMED-CT) Procedure Not Performed Reason (SNOMED-CT)
42840001 | Jersey giant chicken (organism) | Animal breeds Animal breeds
4288003 | Thoroughbred horse (organism) | Animal breeds Animal breeds
429060002 | Procedure to meet occupational requirement | Immunization Reason Codes Immunization Reason Codes
42948007 | Norwegian landrace pig (organism) | Animal breeds Animal breeds

4322002 | Hospital-military field | Facility Type Code Value Set Facility Type Code Value Set
43223009 | Yokohama chicken (organism) | Animal breeds Animal breeds
43500007 | Boar power pig 454 (organism) | Animal breeds Animal breeds
43869002 | Rouen duck breed (organism) | Animal breeds Animal breeds
439021000124105 | nectar thick liquid | Fluid Consistency Type Codes Fluid Consistency Type Codes
439031000124108 | honey thick liquid | Fluid Consistency Type Codes Fluid Consistency Type Codes
439041000124103 | spoon thick liquid | Fluid Consistency Type Codes Fluid Consistency Type Codes
439081000124109 | thin liquid | Fluid Consistency Type Codes Fluid Consistency Type Codes
439091000124107 | Easy to chew food | Texture Modifier Codes Texture Modifier Codes
440034003 | Polled dorset sheep breed (organism) | Animal breeds Animal breeds
44027008 | Seafood | Texture Modified Food Type Codes Texture Modified Food Type Codes
441531000124102 | Standard Enteral Formula | Enteral Formula Type Codes Enteral Formula Type Codes
441561000124106 | Standard enteral formula with fiber | Enteral Formula Type Codes Enteral Formula Type Codes
441571000124104 | High energy enteral formula with fiber | Enteral Formula Type Codes Enteral Formula Type Codes
441591000124103 | Diabetic enteral formula with fiber | Enteral Formula Type Codes Enteral Formula Type Codes
441601000124106 | Diabetic high calorie high protein enteral formula with fiber | Enteral Formula Type Codes Enteral Formula Type Codes
441671000124100 | Hydrolyzed peptide-based high protein enteral formula | Enteral Formula Type Codes Enteral Formula Type Codes
441714000 | Rhinelander horse breed (organism) | Animal breeds Animal breeds
441751000124100 | Mashed food | Texture Modifier Codes Texture Modifier Codes
441761000124103 | Minced food | Texture Modifier Codes Texture Modifier Codes
441771000124105 | Moist food | Texture Modifier Codes Texture Modifier Codes
441791000124106 | Strained food | Texture Modifier Codes Texture Modifier Codes
441881000124103 | Ground food | Texture Modifier Codes Texture Modifier Codes
442083009 | Anatomical or acquired body structure | SNOMED CT Body Structures SNOMED CT Body Structures
442137000 | Completion time of procedure | Goal start event Goal start event
44230005 | Brown Swiss cattle breed (organism) | Animal breeds Animal breeds
442651000124102 | Adult formula | Enteral Formula Type Codes Enteral Formula Type Codes
442901000124106 | Adult clear liquid supplement | Supplement Type Codes Supplement Type Codes
442911000124109 | Adult elemental formula | Enteral Formula Type Codes Enteral Formula Type Codes
442921000124101 | Adult standard formula | Enteral Formula Type Codes Enteral Formula Type Codes
442931000124103 | Adult soy protein isolate formula | Enteral Formula Type Codes Enteral Formula Type Codes
442941000124108 | Adult renal specialty formula | Enteral Formula Type Codes Enteral Formula Type Codes
442951000124105 | Adult pulmonary specialty formula | Enteral Formula Type Codes Enteral Formula Type Codes
442961000124107 | Adult low carbohydrate formula | Enteral Formula Type Codes Enteral Formula Type Codes
442971000124100 | Adult high energy formula | Enteral Formula Type Codes Enteral Formula Type Codes
442981000124102 | Adult hydrolyzed protein formula | Enteral Formula Type Codes Enteral Formula Type Codes
442991000124104 | Adult high protein formula | Enteral Formula Type Codes Enteral Formula Type Codes
443011000124100 | Adult high protein high fiber formula | Enteral Formula Type Codes Enteral Formula Type Codes
443021000124108 | Adult hepatic specialty formula | Enteral Formula Type Codes Enteral Formula Type Codes
443031000124106 | Adult critical care formula | Enteral Formula Type Codes Enteral Formula Type Codes
443051000124104 | Adult diabetes specialty formula | Enteral Formula Type Codes Enteral Formula Type Codes
443111000124101 | High protein formula | Enteral Formula Type Codes Enteral Formula Type Codes
443351000124102 | Increased fiber formula | Enteral Formula Type Codes Enteral Formula Type Codes
443361000124100 | Pediatric Formula | Enteral Formula Type Codes Enteral Formula Type Codes
443391000124108 | Pediatric clear liquid supplement | Supplement Type Codes Supplement Type Codes
443401000124105 | Pediatric elemental formula | Enteral Formula Type Codes Enteral Formula Type Codes
443411000124108 | Elemental Formula | Enteral Formula Type Codes Enteral Formula Type Codes
443421000124100 | Pediatric hydrolyzed protein formula | Enteral Formula Type Codes Enteral Formula Type Codes
443431000124102 | High Energy Formula | Enteral Formula Type Codes Enteral Formula Type Codes
443441000124107 | Clear liquid supplement | Supplement Type Codes Supplement Type Codes
443451000124109 | Pediatric standard formula | Enteral Formula Type Codes Enteral Formula Type Codes
443461000124106 | Standard Formula | Enteral Formula Type Codes Enteral Formula Type Codes
443471000124104 | Pediatric increased fiber formula | Enteral Formula Type Codes Enteral Formula Type Codes
443481000124101 | Renal Formula | Enteral Formula Type Codes Enteral Formula Type Codes
443491000124103 | Pediatric high energy formula | Enteral Formula Type Codes Enteral Formula Type Codes
443501000124106 | Pediatric high energy formula with increased fiber | Enteral Formula Type Codes Enteral Formula Type Codes
443561000124107 | Soy based formula | Enteral Formula Type Codes Enteral Formula Type Codes
443771000124106 | Hydrolyzed protein formula | Enteral Formula Type Codes Enteral Formula Type Codes
444321000124108 | Standard pudding oral supplement | Supplement Type Codes Supplement Type Codes
444331000124106 | Diabetic meal replacement bar | Supplement Type Codes Supplement Type Codes
444361000124102 | Electrolyte replacement supplement | Supplement Type Codes Supplement Type Codes
444371000124109 | Powdered electrolyte replacement supplement | Supplement Type Codes Supplement Type Codes
444381000124107 | Liquid electrolyte replacement supplement | Supplement Type Codes Supplement Type Codes
444401000124107 | Frozen electrolyte replacement supplement | Supplement Type Codes Supplement Type Codes
444431000124104 | Pediatric reduced energy formula | Enteral Formula Type Codes Enteral Formula Type Codes
445729005 | Tarpan horse breed (organism) | Animal breeds Animal breeds
447346005 | Cardiopulmonary exercise test | Procedure Follow up Codes (SNOMED CT) Procedure Follow up Codes (SNOMED CT)
44835005 | Debouillet sheep (organism) | Animal breeds Animal breeds
45284002 | Maine Anjou cattle breed (organism) | Animal breeds Animal breeds
45618002 | Skilled nursing facility | Facility Type Code Value Set Facility Type Code Value Set

45635003 | FHC elite pig 1 (organism) | Animal breeds Animal breeds
45690005 | Mouflon sheep (organism) | Animal breeds Animal breeds
4574003 | Shropshire sheep (organism) | Animal breeds Animal breeds
45790002 | American Albino horse (organism) | Animal breeds Animal breeds
45899008 | Free-standing laboratory facility | Facility Type Code Value Set Facility Type Code Value Set
46224007 | Vaccination clinic | Facility Type Code Value Set Facility Type Code Value Set
46392004 | Delaine merino sheep (organism) | Animal breeds Animal breeds
46408008 | American pony (organism) | Animal breeds Animal breeds
46830002 | Midget white turkey (organism) | Animal breeds Animal breeds
46947000 | Chiropractic manipulation | Procedure Category Codes (SNOMED CT) Procedure Category Codes (SNOMED CT)
47290002 | Gallus gallus (organism) | Animal breeds Animal breeds
47314009 | Dark brown turkey (organism) | Animal breeds Animal breeds
47545007 | Continuous positive airway pressure ventilation treatment (regime/therapy) | Service Request Order Details Codes Service Request Order Details Codes
47745005 | Java chicken (organism) | Animal breeds Animal breeds
47795006 | FHC elite pig 4 (organism) | Animal breeds Animal breeds
47842004 | Canadian horse (organism) | Animal breeds Animal breeds
48255007 | Silkie chicken (organism) | Animal breeds Animal breeds
48311003 | Hospital-Veterans' Administration | Facility Type Code Value Set Facility Type Code Value Set
48394005 | Beltsville pig (organism) | Animal breeds Animal breeds
48470006 | Boar power pig 656 (organism) | Animal breeds Animal breeds
48697009 | Clun Forest sheep (organism) | Animal breeds Animal breeds
48702000 | Limousin cattle breed (organism) | Animal breeds Animal breeds
4880003 | Piedmontese cattle breed (organism) | Animal breeds Animal breeds
49062001 | Device | FHIR Device Types FHIR Device Types
49240006 | Palouse pig (organism) | Animal breeds Animal breeds
49370004 | Lateral | Bodystructure Location Qualifier Bodystructure Location Qualifier
49407004 | Lankenvelder chicken (organism) | Animal breeds Animal breeds
49462008 | FHC elite pig 6 (organism) | Animal breeds Animal breeds
4960000 | Peruvian Paso horse (organism) | Animal breeds Animal breeds
49755003 | Abnormal tissue appearance | SNOMED CT Morphologic Abnormalities SNOMED CT Morphologic Abnormalities
50569004 | Hospital outpatient urology clinic | Facility Type Code Value Set Facility Type Code Value Set
50710008 | Blue slate turkey (organism) | Animal breeds Animal breeds
50717006 | Cheviot sheep (organism) | Animal breeds Animal breeds
50959000 | Tarentaise cattle breed (organism) | Animal breeds Animal breeds
51023000 | Tennessee walking horse (organism) | Animal breeds Animal breeds
5114005 | Fayoumi chicken (organism) | Animal breeds Animal breeds
51440002 | Bilateral | Laterality Laterality
51563005 | Free-standing mental health center | Facility Type Code Value Set Facility Type Code Value Set
5164003 | Montdale sheep (organism) | Animal breeds Animal breeds
51937006 | Jersey cattle breed (organism) | Animal breeds Animal breeds
5227002 | Oxford sandy block pig (organism) | Animal breeds Animal breeds
52668009 | Hospital birthing center | Facility Type Code Value Set Facility Type Code Value Set
52882006 | Dominique chicken (organism) | Animal breeds Animal breeds
53031002 | Dexter cattle breed (organism) | Animal breeds Animal breeds
53360003 | Oxford Down sheep (organism) | Animal breeds Animal breeds
53431006 | Boar power pig 59 (organism) | Animal breeds Animal breeds
5345000 | Santa Gertrudis cattle breed (organism) | Animal breeds Animal breeds
5350006 | Rhode Island red chicken (organism) | Animal breeds Animal breeds
53567001 | Suffolk horse (organism) | Animal breeds Animal breeds
54098002 | Arabian horse (organism) | Animal breeds Animal breeds
54218009 | New Hampshire chicken (organism) | Animal breeds Animal breeds
54232006 | Welsh pig (organism) | Animal breeds Animal breeds
54251000 | Australorp chicken (organism) | Animal breeds Animal breeds
5438004 | French alpine goat (organism) | Animal breeds Animal breeds
54447000 | Haflinger horse (organism) | Animal breeds Animal breeds
54604007 | Gray turkey (organism) | Animal breeds Animal breeds
54699009 | American miniature horse (organism) | Animal breeds Animal breeds
55074002 | Jersey buff turkey (organism) | Animal breeds Animal breeds
55167009 | Appaloosa horse (organism) | Animal breeds Animal breeds
55530007 | La Mancha goat (organism) | Animal breeds Animal breeds
5584006 | Hospital outpatient peripheral vascular clinic | Facility Type Code Value Set Facility Type Code Value Set
56084008 | Boar power pig 292 (organism) | Animal breeds Animal breeds
56086005 | Paso Fino horse (organism) | Animal breeds Animal breeds
56189001 | Hospital outpatient obstetrical clinic | Facility Type Code Value Set Facility Type Code Value Set
56293002 | Hospital outpatient hematology clinic | Facility Type Code Value Set Facility Type Code Value Set
56764001 | Holland chicken (organism) | Animal breeds Animal breeds
57159002 | Hospital outpatient respiratory disease clinic | Facility Type Code Value Set Facility Type Code Value Set
57364006 | Brahma chicken (organism) | Animal breeds Animal breeds
57613003 | Kleen leen white pig (organism) | Animal breeds Animal breeds
57950004 | Spitzhauben chicken (organism) | Animal breeds Animal breeds
58264006 | Pinto (organism) | Animal breeds Animal breeds

58311005 | Dutch landrace pig (organism) | Animal breeds Animal breeds
58482006 | Hospital outpatient gastroenterology clinic | Facility Type Code Value Set Facility Type Code Value Set
59210004 | Navajo sheep (organism) | Animal breeds Animal breeds
59374000 | Traveler's aid clinic | Facility Type Code Value Set Facility Type Code Value Set
59427005 | Synchronized intermittent mandatory ventilation (procedure) | Service Request Order Details Codes Service Request Order Details Codes
59667000 | FHC elite pig 2 (organism) | Animal breeds Animal breeds
6053007 | Dekalb hybrid pig line 33 (organism) | Animal breeds Animal breeds
60786005 | Lilac buff turkey (organism) | Animal breeds Animal breeds
60958006 | Maryland pig (organism) | Animal breeds Animal breeds
61036003 | Boar power pig 545 (organism) | Animal breeds Animal breeds
61083001 | Minnesota pig (organism) | Animal breeds Animal breeds
61088005 | plastic | Types of material for specimen containers Types of material for specimen containers
6112002 | Meusse-Rhine-Ijssel cattle breed (organism) | Animal breeds Animal breeds
61204004 | Dorking chicken (organism) | Animal breeds Animal breeds
61839006 | Cornish chicken (organism) | Animal breeds Animal breeds
61843005 | Polish chicken (organism) | Animal breeds Animal breeds
61973002 | Dekalb hybrid pig line 61 (organism) | Animal breeds Animal breeds
62124009 | Royal palm turkey (organism) | Animal breeds Animal breeds
62153005 | Blonde d'Aquitaine (organism) | Animal breeds Animal breeds
6220006 | Galiceno horse (organism) | Animal breeds Animal breeds
62480006 | Hospital-psychiatric | Facility Type Code Value Set Facility Type Code Value Set
63257005 | Chantecler chicken (organism) | Animal breeds Animal breeds
64158000 | Angora goat (organism) | Animal breeds Animal breeds
6431001 | Leicester sheep (organism) | Animal breeds Animal breeds
64591001 | Karakul sheep (organism) | Animal breeds Animal breeds
65136005 | Light brown turkey (organism) | Animal breeds Animal breeds
65187008 | Black faced Highland sheep (organism) | Animal breeds Animal breeds
65344003 | Marchigiana cattle breed (organism) | Animal breeds Animal breeds
65492002 | Lincoln sheep (organism) | Animal breeds Animal breeds
65873005 | Barnevelder chicken (organism) | Animal breeds Animal breeds
66168008 | Hanoverian horse (organism) | Animal breeds Animal breeds
66314009 | Longhorn cattle breed (organism) | Animal breeds Animal breeds
66911005 | Galloway cattle breed (organism) | Animal breeds Animal breeds
67021006 | Sebright chicken (organism) | Animal breeds Animal breeds
67209003 | Turken chicken (organism) | Animal breeds Animal breeds
6736007 | Moderate | Condition/Diagnosis Severity Condition/Diagnosis Severity
67414001 | Cotswold sheep (organism) | Animal breeds Animal breeds
67448000 | German Fleck-Vieh cattle breed (organism) | Animal breeds Animal breeds
67515002 | Corriedale sheep (organism) | Animal breeds Animal breeds
67720004 | FHC elite pig 5 (organism) | Animal breeds Animal breeds
6827000 | Local community health center | Facility Type Code Value Set Facility Type Code Value Set
684003 | Pygmy goat (organism) | Animal breeds Animal breeds
68412000 | Sultan chicken (organism) | Animal breeds Animal breeds
68512002 | Boar power pig 141 (organism) | Animal breeds Animal breeds
69067004 | Shetland pony (organism) | Animal breeds Animal breeds
69362002 | Hospital ambulatory surgery facility | Facility Type Code Value Set Facility Type Code Value Set
69461005 | Chester white pig (organism) | Animal breeds Animal breeds
69575001 | Ancona chicken (organism) | Animal breeds Animal breeds
69602006 | Kleen leen pig (organism) | Animal breeds Animal breeds
70210006 | Orloff chicken (organism) | Animal breeds Animal breeds
70308007 | Langshan chicken (organism) | Animal breeds Animal breeds
70326005 | Cubalaya chicken (organism) | Animal breeds Animal breeds
703763000 | Precondition value | Patient preparation prior specimen collection Patient preparation prior specimen collection
70429002 | Game chicken (organism) | Animal breeds Animal breeds
70431006 | Alpine goat (organism) | Animal breeds Animal breeds
70457009 | Icelandic horse (organism) | Animal breeds Animal breeds
705383004 | Eating/Drinking assistive device | Feeding Device Codes Feeding Device Codes
706041008 | Device for body fluid and tissue collection/transfer/processing | Specimen Container Type Specimen Container Type
70777001 | Urine specimen collection, catheterized | Specimen collection methods Specimen collection methods
70881005 | Anser anser anser (organism) | Animal breeds Animal breeds
709410003 | Haemophilus influenzae type b infection | Immunization Target Disease Codes Immunization Target Disease Codes
71238008 | Commercial brown egg layer type chicken (organism) | Animal breeds Animal breeds
71388002 | Procedure | Encounter Reason Codes Encounter Reason Codes
716186003 | No known allergy | AllergyIntolerance Substance/Product, Condition and Negation Codes AllergyIntolerance Substance/Product, Condition and Negation Codes
71923001 | Italian landrace pig (organism) | Animal breeds Animal breeds
72311000 | Health maintenance organization | Facility Type Code Value Set Facility Type Code Value Set
72329005 | Finnish landrace sheep (organism) | Animal breeds Animal breeds
72394007 | American tunis horse (organism) | Animal breeds Animal breeds
72511004 | Fruit | Texture Modified Food Type Codes Texture Modified Food Type Codes
72648002 | Suffolk sheep (organism) | Animal breeds Animal breeds

73005003 | FHC elite pig 8 (organism) | Animal breeds Animal breeds
73012007 | Penna white turkey (organism) | Animal breeds Animal breeds
73191001 | American merino sheep (organism) | Animal breeds Animal breeds
73416001 | Urine specimen collection, clean catch | Specimen collection methods Specimen collection methods
734163000 | Care plan | Care Plan Category Care Plan Category
73644007 | Hospital outpatient endocrinology clinic | Facility Type Code Value Set Facility Type Code Value Set
73648005 | Wessex saddleback pig (organism) | Animal breeds Animal breeds
73770003 | Emergency department--hospital | Facility Type Code Value Set Facility Type Code Value Set
73944009 | Minnesota pig #1 (organism) | Animal breeds Animal breeds
74242007 | Food Starch | Texture Modified Food Type Codes Texture Modified Food Type Codes
74517004 | Montana pig (organism) | Animal breeds Animal breeds
74568001 | Red wattle pig (organism) | Animal breeds Animal breeds
74745008 | Rock alpine goat (organism) | Animal breeds Animal breeds
74899005 | Boar power pig (organism) | Animal breeds Animal breeds
74921000 | Dekalb hybrid pig line (organism) | Animal breeds Animal breeds
74970001 | Boar power pig 161 (organism) | Animal breeds Animal breeds
75709004 | Pic pig (organism) | Animal breeds Animal breeds
7598004 | Wyandotte chicken (organism) | Animal breeds Animal breeds
7623008 | American paint horse (organism) | Animal breeds Animal breeds
76268003 | Campine chicken (organism) | Animal breeds Animal breeds
76302002 | Spanish mustang horse (organism) | Animal breeds Animal breeds
76364003 | Boar power pig 27 (organism) | Animal breeds Animal breeds
76467006 | Quarter horse (organism) | Animal breeds Animal breeds
76497003 | Gelbveih cattle breed (organism) | Animal breeds Animal breeds
76604009 | Nellore cattle breed (organism) | Animal breeds Animal breeds
76902006 | Tetanus | Immunization Target Disease Codes Immunization Target Disease Codes
7700003 | Nebraskan spotted turkey (organism) | Animal breeds Animal breeds
77176002 | Smoker | Immunization Recommendation Reason Codes Immunization Recommendation Reason Codes
77236002 | Large white pig (organism) | Animal breeds Animal breeds
77386006 | Pregnancy not delivered | Immunization Recommendation Reason Codes Immunization Recommendation Reason Codes
7767003 | Lamona chicken (organism) | Animal breeds Animal breeds
77839002 | Thuringer chicken (organism) | Animal breeds Animal breeds
77931003 | Rural health center | Facility Type Code Value Set Facility Type Code Value Set
78001009 | Hospital outpatient orthopedics clinic | Facility Type Code Value Set Facility Type Code Value Set
78088001 | Hospital outpatient ophthalmology clinic | Facility Type Code Value Set Facility Type Code Value Set
78154009 | Malay chicken (organism) | Animal breeds Animal breeds
78375007 | Andalusian chicken (organism) | Animal breeds Animal breeds
7843000 | Horned Hereford (organism) | Animal breeds Animal breeds
78541007 | Milking Shorthorn cattle breed (organism) | Animal breeds Animal breeds
78678003 | Sus scrofa (organism) | Animal breeds Animal breeds
78994007 | British landrace pig (organism) | Animal breeds Animal breeds
79491001 | Hospital radiology facility | Facility Type Code Value Set Facility Type Code Value Set
79603002 | Romedale sheep (organism) | Animal breeds Animal breeds
79814001 | Poland China pig (organism) | Animal breeds Animal breeds
79993009 | Hospital-government | Facility Type Code Value Set Facility Type Code Value Set
80084005 | Lucie pig (organism) | Animal breeds Animal breeds
80131009 | Landrace pig (organism) | Animal breeds Animal breeds
80204002 | Hungarian chicken (organism) | Animal breeds Animal breeds
80522000 | Hospital-rehabilitation | Facility Type Code Value Set Facility Type Code Value Set
80610007 | Narragansett turkey (organism) | Animal breeds Animal breeds
80777007 | Andalusian horse (organism) | Animal breeds Animal breeds
80835003 | Shorthorn cattle breed (organism) | Animal breeds Animal breeds
80886008 | Rosecomb chicken (organism) | Animal breeds Animal breeds
8089006 | Welsh walking horse (organism) | Animal breeds Animal breeds
80979001 | San Pierre pig (organism) | Animal breeds Animal breeds
80993008 | Sussex chicken (organism) | Animal breeds Animal breeds
81234003 | Walk-in clinic | Facility Type Code Value Set Facility Type Code Value Set
81267004 | Normandie cattle breed (organism) | Animal breeds Animal breeds
82242000 | Hospital-children's | Facility Type Code Value Set Facility Type Code Value Set
82249009 | California chicken (organism) | Animal breeds Animal breeds
82440005 | Hampshire Down sheep (organism) | Animal breeds Animal breeds
82848009 | Houdan chicken (organism) | Animal breeds Animal breeds
82909008 | Middle white pig (organism) | Animal breeds Animal breeds
83173002 | Scottish Highland cattle breed (organism) | Animal breeds Animal breeds
83418008 | Fetus | Focal Subject Codes Focal Subject Codes
83842004 | Hungarian goose (organism) | Animal breeds Animal breeds
83891005 | Solo practice private office | Facility Type Code Value Set Facility Type Code Value Set
83996001 | Criollo cattle breed (organism) | Animal breeds Animal breeds
84081007 | Boar power pig 747 (organism) | Animal breeds Animal breeds
84232003 | Kleen leen red pig (organism) | Animal breeds Animal breeds
84315000 | Boar power pig 474 (organism) | Animal breeds Animal breeds

84528008 | Danish landrace pig (organism) | Animal breeds Animal breeds
84839000 | Guernsey cattle breed (organism) | Animal breeds Animal breeds
84923006 | Aberdeen Angus cattle breed (organism) | Animal breeds Animal breeds
8516002 | Dekalb hybrid pig line 51 (organism) | Animal breeds Animal breeds
85315007 | Yorkshire pig (organism) | Animal breeds Animal breeds
85626006 | Equus asinus (organism) | Animal breeds Animal breeds
86440008 | Pic line pig 24 (organism) | Animal breeds Animal breeds
86694007 | Hormel miniature pig (organism) | Animal breeds Animal breeds
86920006 | Horned dorset sheep breed (organism) | Animal breeds Animal breeds
87061000 | Boar power pig 282 (organism) | Animal breeds Animal breeds
87530001 | Welsummer chicken (organism) | Animal breeds Animal breeds
8763002 | German landrace pig (organism) | Animal breeds Animal breeds
87833007 | Sumatra chicken (organism) | Animal breeds Animal breeds
87962009 | North County cheviot sheep (organism) | Animal breeds Animal breeds
88480006 | Potassium | Nutrient Modifier Codes Nutrient Modifier Codes
88807001 | Red Poll cattle breed (organism) | Animal breeds Animal breeds
89648005 | Fjord horse (organism) | Animal breeds Animal breeds
89665001 | Targhee sheep (organism) | Animal breeds Animal breeds
8970009 | French landrace pig (organism) | Animal breeds Animal breeds
89708009 | Chamoisee goat (organism) | Animal breeds Animal breeds
8989009 | Ayrshire cattle breed (organism) | Animal breeds Animal breeds
89928000 | FHC pig (organism) | Animal breeds Animal breeds
89972002 | Hospital outpatient oncology clinic | Facility Type Code Value Set Facility Type Code Value Set
900000000000003001 | Fully specified name | Designation Use Designation Use
900000000000013009 | Synonym | Designation Use Designation Use
90050009 | American Buckskin horse (organism) | Animal breeds Animal breeds
901005 | Helicopter-based care | Facility Type Code Value Set Facility Type Code Value Set
90484001 | Hospital outpatient general surgery clinic | Facility Type Code Value Set Facility Type Code Value Set
90612002 | Salers cattle breed (organism) | Animal breeds Animal breeds
90885005 | Gloucester old spot pig (organism) | Animal breeds Animal breeds
91154008 | Free-standing birthing center | Facility Type Code Value Set Facility Type Code Value Set
9135003 | OIC pig (organism) | Animal breeds Animal breeds
91401000 | Black Spanish turkey (organism) | Animal breeds Animal breeds
91427000 | Frizzle chicken (organism) | Animal breeds Animal breeds
91460002 | Chinese goose (organism) | Animal breeds Animal breeds
91723000 | Anatomical structure | SNOMED CT Anatomical Structure for Administration Site Codes SNOMED CT Anatomical Structure for Administration Site Codes
9230001 | Camarron goat (organism) | Animal breeds Animal breeds
9277006 | Polled Hereford (organism) | Animal breeds Animal breeds
944009 | Brown Welsh cattle breed (organism) | Animal breeds Animal breeds

4.3.2 Using RxNorm with FHIR

URL: https://hl7.org/fhir/R4/rxnorm.html

4.3.2 Using RxNorm with FHIR

Vocabulary Work Group | Maturity Level: 3 | Standards Status: Trial Use

4.3.2.1 Summary

Source | RxNorm is made available by the US National Library of Medicine at http://www.nlm.nih.gov/research/umls/rxnorm
System | The URI http://www.nlm.nih.gov/research/umls/rxnorm identifies the RxNorm code system
Version | Where a version is used, it should be the date of release, encoded as in the download files, e.g. "07092014"
Code | The code value for an RxNorm code is a Concept Identifier (CUI), and only CUIs for which there is an SAB=RXNORM
Display | The string description for the CUI that is associated with the source RXNORM. For further information, see below
Inactive | Todo: Describe how it is determined which concepts are inactive
Subsumption | No Subsumption relationships are defined by RxNorm
Filter Properties | Several properties are defined as described below

4.3.2.2 RxNorm MySQL Database

The RxNorm scripts are able to populate a MySQL database that contains the data from RxNorm. This page provides SQL statements that describe how to implement the features of the RxNorm terminology correctly against this database. These are provided for implementer convenience, and do not imply that any particular approach is required to be used in implementations.

4.3.2.3 Correct RxNorm Display

The correct display for a CUI is the string description for it associated with the source RXNORM. Given the RxNorm MySQL database, the correct display for a CUI can generally be determined by the SQL:

```
Select STR from rxnconso where RXCUI = :code and SAB = 'RXNORM' and TTY in ('SCD', 'SBD')
```

Display values are not case sensitive, though case SHOULD be preserved.

4.3.2.4 Copyright/License Issues

Using RxNorm codes of type SAB=RXNORM as this specification describes does not require a UMLS license. Access to the full set of RxNorm definitions, and/or additional use of other RxNorm structures and information requires a UMLS license. The use of RxNorm in this specification is pursuant to HL7's status as a licensee of the NLM UMLS. HL7's license does not convey the right to use RxNorm to any users of this specification; implementers must acquire a license to use RxNorm in their own right.

4.3.2.5 RxNorm Filter Properties

This section documents the property filters that can be used with the RxNorm code system in value set composition statements.

The base SQL statement for returning a list of CUIs that conform to these filters is:

```
Select RXCUI from rxnconso where SAB = 'RXNORM' and TTY <> 'SY'
```

4.3.2.5.1 Semantic Type

Description | Allows for the selection of a set of CUIs based on their Semantic Type
Property Name | STY
Operations Allowed | = / in
Values Allowed | [column:]value
Comments | If no column is specified, the default column is TUI
SQL | and RXCUI in (select RXCUI from rxnsty where [:column] = :value)

4.3.2.5.2 Source

Description | Allows for the selection of a set of concepts that have mappings to a particular RxNorm concept
Property Name | SAB
Operations Allowed | = / in
Values Allowed | Values from RxNorm SAB table (e.g. select RSAB from rxnsab)
SQL | and RXCUI in (select RXCUI from rxnconso where SAB = :value)

4.3.2.5.3 Term Type

Description | Allows for the selection of a concept based on its designated type
Property Name | TTY
Operations Allowed | = / in
Values Allowed | TTY values from the RxNorm Concept table (e.g. select distinct TTY from rxnconso)
SQL | and TTY = :value

4.3.2.5.4 Relationship

Description | Allows for the selection of a concept based on its relationships
Property Name | [REL]
Operations Allowed | = / in
Values Allowed | CUI:[RXCUI] or AUI:[RXAUI] must be a valid CUI or AUI. Note that a CUI does not need to have an SAB=RXNORM entry to be used here
Comments | [REL] (:rel) is one of SY, SIB, RN, PAR, CHD, RB or RO
SQL | for CUI: and (RXCUI in (select RXCUI from rxnconso where RXCUI in (select RXCUI1 from rxnrel where REL = :rel and RXCUI2 = :value)) for AUI: and (RXCUI in (select RXCUI from rxnconso where RXAUI in (select RXAUI1 from rxnrel where REL = :rel and RXAUI2 = :value))

4.3.2.5.5 Relationship Type

Description | Allows for the selection of a concept based on the type of its relationships
Property Name | [RELA]
Operations Allowed | = / in
Values Allowed | CUI:[RXCUI] or AUI:[RXAUI] must be a valid CUI or AUI. Note that a CUI does not need to have an SAB=RXNORM entry to be used here
Comments | [RELA] (:rela) is one of the relationship types defined in RxNorm Appendix 1 (the "RELA" column)
SQL | for CUI: and (RXCUI in (select RXCUI from rxnconso where RXCUI in (select RXCUI1 from rxnrel where RELA = :rel and RXCUI2 = :value)) for AUI: and (RXCUI in (select RXCUI from rxnconso where RXAUI in (select RXAUI1 from rxnrel where RELA = :rel and RXAUI2 = :value))

4.3.2.6 RxNorm Properties

In addition to the standard properties, the following properties are defined for RxNorm:

(Yet to be done).

4.3.2.7 Implicit Value Sets

Implicit value sets are those whose specification can be predicted based on the grammar of the underlying code system, and the known structure of the URL that refers to them. At the time of this publication, RxNorm does not define implicit value sets.

The identifier http://www.nlm.nih.gov/research/umls/rxnorm/vs represents a value set that contains all RxNorm CUIs.

4.3.3 Using LOINC with FHIR

URL: https://hl7.org/fhir/R4/loinc.html

4.3.3 Using LOINC with FHIR

Vocabulary Work Group | Maturity Level: 5 | Standards Status: Trial Use

4.3.3.1 Summary

Source | LOINC is made available by the Regenstrief Institute at http://loinc.org
System | The URI http://loinc.org identifies LOINC codes
Version | Where a version is used, it should be the standard LOINC version e.g. 2.48
Code | The LOINC Code Identifier e.g. 21176-3. LOINC codes are not case sensitive. In addition, LOINC part codes and LOINC answer string ids can be used where appropriate
Display | Use either the SHORTNAME or LONG_COMMON_NAME field for the display
Inactive | Codes with Property STATUS = DEPRECATED are considered inactive for use in ValueSet.compose.inactive
Subsumption | LOINC defines the Multi-Axial Hierarchy, which is the basis for subsumption logic in LOINC
Filter Properties | Several properties are defined as described below

4.3.3.2 Copyright Issues

The terms of use for LOINC require that a notice be included with any use of LOINC codes. This notice must appear in the copyright element of any value set that includes LOINC codes (either in the code or filter elements, or in an expansion):

```
<copyright value="This content LOINC® is copyright © 1995 Regenstrief Institute, Inc. and the LOINC Committee, and
    available at no cost under the license at http://loinc.org/terms-of-use"/>
```

Additional copyright statements may also be found in the copyright element. Some LOINC codes have 3rd party copyright statements. When these codes are included in a value set, they must carry their own copyright statement as well.

4.3.3.3 Case Sensitivity

For comparison purposes, LOINC codes, displays, and property values are not case sensitive, though implementers SHOULD maintain the correct case when using LOINC codes and property values.

4.3.3.4 Use of LOINC PARTS

As described in the LOINC Manual section 10.2, LOINC Parts are a coded representation of a value for a dimension used to specify a LOINC Term which are assigned a non-semantic identifier with a "LP" prefix and a mod-10 check digit. Following the LOINC license, these part codes may be used in the following ways:

• In filter properties, as described below

• In Structure Definitions, where the structure describes the use of a set of LOINC codes

• In a ConceptMap resource, where mappings between LOINC codes and other codes are being defined

Part codes are the same LOINC system (http://loinc.org) and SHALL be represented in uppercase (e.g. LP31755-9).

4.3.3.5 Use of LOINC Answer Lists

LOINC also allocates Answer List and Answer String Ids for use in various forms and questionnaires. LOINC Answer String IDs are also valid LOINC codes:

```
<coding>
  <system value="http://loinc.org"/>
  <code value="LA11165-0"/>
  <display value="Platelet anisocytosis"/>
</coding>
```

LOINC Answer List Ids are actually value set identifiers. See below for how to use these.

4.3.3.6 RDF

LOINC uses the namespace http://loinc.org/rdf# as the root for LOINC concepts in the RDF space. This means that when a LOINC code is converted from the system:code pair, where the system is http://loinc.org, to the RDF ontological form, the representation is http://loinc.org/rdf#[code].

4.3.3.7 LOINC Properties

In addition to the standard properties, the following LOINC table fields are defined as code system properties when using LOINC in FHIR:

STATUS | string | Status of the term
COMPONENT | code | First major axis-component or analyte: Analyte Name, Analyte sub-class, Challenge
PROPERTY | code | Second major axis-property observed: Kind of Property (also called kind of quantity)
TIME_ASPCT | code | Third major axis-timing of the measurement: Time Aspect (Point or moment in time vs. time interval)
SYSTEM | code | Fourth major axis-type of specimen or system: System (Sample) Type
SCALE_TYP | code | Fifth major axis-scale of measurement: Type of Scale
METHOD_TYP | code | Sixth major axis-method of measurement: Type of Method

CLASS | string | An arbitrary classification of the terms for grouping related observations together
CONSUMER_NAME | string | An experimental (beta) consumer friendly name for this item. The intent is to provide a test name that health care consumers will recognize; it will be similar to the names that might appear on a lab report
CLASSTYPE | string | 1=Laboratory class; 2=Clinical class; 3=Claims attachments; 4=Surveys
ORDER_OBS | string | Provides users with an idea of the intended use of the term by categorizing it as an order only, observation only, or both
DOCUMENT_SECTION | string | Classification of whether this LOINC code can be used a full document, a section of a document, or both

Note that when a $lookup operation is performed on a LOINC code, servers SHALL return the version being used (see above) in the version property. Other properties are at the discretion of the server and the client.

4.3.3.8 LOINC Filters

This section documents the property filters that can be used with the LOINC code system in value set composition statements.

4.3.3.8.1 LOINC Property filter

Description | Allows the selection of a set of LOINC codes with a common property value (see list above)
Property Name | One of the names listed in the "Field Name" column in LOINC Database Structure (Appendix A of the LOINC manual)
Operations Allowed | = / regex
Values Allowed | [string value]
Comments | The 6 properties COMPONENT, PROPERTY, TIME_ASPCT, SYSTEM, SCALE_TYP, and METHOD_TYP are most likely to be useful.

4.3.3.8.2 3rd Party Copyright

Description | Allows for the inclusion or exclusion of LOINC codes that include 3rd party copyright notices
Property Name | copyright
Operations Allowed | =
Values Allowed | LOINC | 3rdParty
Comments | LOINC = only codes with a sole copyright by Regenstrief. 3rdParty = only codes with a 3rd party copyright in addition to the one from Regenstrief.

4.3.3.8.3 Multi-Axial Hierarchy

Description | Allows for the selection of a set of codes base on their appearance in the LOINC multi-axial hierarchy
Property Name | parent | ancestor
Operations Allowed | = / in
Values Allowed | Part Code (or, for "in", multiple part codes separated by commas)
Comments | "parent" selects immediate parents only. For example, the code "44022-2" has the parent "LP52960-9". Ancestor includes parents transitively, e.g. "LP52960-9" eventually has a parent "LP31755-9", so the code "44022-2" is in the set of codes that have ancestor=LP31755-9

TODO: Document Ontology

4.3.3.9 Implicit Value Sets

Implicit value sets are those whose specification can be predicted based on the grammar of the underlying code system, and the known structure of the URL that refers to them. LOINC defines one set of implicit value sets: By Multi-Axial Hierarchy Entry.

If any value set resources exist with an identifier that conforms to the URL patterns specified below, the content of the resource must conform to the template provided. Profiles and other value set references are allowed to reference these value sets directly. todo: can LOINC actually host a service that returns these?

The value set identifier http://loinc.org/vs is a value set that contains all LOINC codes.

4.3.3.9.1 LOINC Answer List

LOINC defines a set of Answer lists, each of which contains a set of LOINC codes. LOINC answer lists are value sets. The value set identifier "http://loinc.org/vs/[id]" identifies a value set that contains a set of LOINC codes. For instance, the value set identifier http://loinc.org/vs/LL715-4 has the following definition for LOINC 2.52:

```
<ValueSet xmlns="http://hl7.org/fhir">
  <text>
    <status value="generated"/>
    <div xmlns="http://www.w3.org/1999/xhtml">
      [some html that identifies that this value set
      includes all LOINC codes in this answer list]
    </div>
  </text>
  <url value="http://loinc.org/vs/LL715-4"/>
  <version value="2.52"/>
  <name value="Platelet morph"/>
  <description value="LOINC Answer List for Platelet morph"/>
  <status value="active"/>
  <date value="[optional date of LOINC release]"/>
  <compose>
    <include>
      <system value="http://loinc.org"/>
      <concept>
```

```
        <code value="LA11165-0"/>
        <display value="Platelet anisocytosis"/>
      </concept>
      <concept>
        <code value="LA11168-4"/>
        <display value="Platelet clump"/>
      </concept>
      <concept>
        <code value="LA11167-6"/>
        <display value="Platelet large fragments"/>
      </concept>
      <concept>
        <code value="LA11166-8"/>
        <display value="Platelet satellitism"/>
      </concept>
      <concept>
        <code value="LA11169-2"/>
        <display value="Platelets.agranular"/>
      </concept>
      <concept>
        <code value="LA11170-0"/>
        <display value="Platelets.giant"/>
      </concept>
      <concept>
        <code value="LA11172-6"/>
        <display value="Platelets.large"/>
      </concept>
      <concept>
        <code value="LA11171-8"/>
        <display value="Platelets.small"/>
      </concept>
    </include>
  </compose>
</ValueSet>
```

Here is an example of a LOINC Answer list used in a Questionnaire question:

```
<question>
  <concept>
    <system value="http://loinc.org"/>
    <code value="11125-2"/>
    <display value="Plat morph Bld"/>
  </concept>
  <type value="choice"/>
  <options>
    <reference value="http://loinc.org/vs/LL715-4"/>
  </options>
</question>
```

4.3.3.9.2 Multi-Axial Hierarchy Entry

A value set with an identifier of "http://loinc.org/vs/[partcode]" must conform to this template, where [partcode] is a part code from the multi-axial hierarchy:

```
<ValueSet xmlns="http://hl7.org/fhir">
  <text>
    <status value="generated"/>
    <div xmlns="http://www.w3.org/1999/xhtml">
      [some html that identifies that this value set
      includes all LOINC codes subsumed by the identified
      Multi-Axial Hierarchy Part Code]
    </div>
  </text>
  <url value="http://loinc.org/vs/[partcode]"/>
  <version value="[optional - but strongly recommended - LOINC version]"/>
  <name value="LOINC Value Set from Multi-Axial Hierarchy code [partcode]"/>
  <description value="All LOINC codes for [partcode or name]"/>
  <status value="active"/>
  <date value="[optional date of LOINC release]"/>
  <compose>
    <include>
      <system value="http://loinc.org"/>
      <filter>
        <property value="ancestor"/>
        <op value="="/>
        <value value="[partcode]"/>
      </filter>
    </include>
  </compose>
</ValueSet>
```

4.3.3.9.3 LOINC and Data Elements

LOINC codes and their properties are describing a data element that can have a value. Functionally, this overlaps with FHIR's notion of a Logical Data Model. A logical data model can be created for each LOINC code based on it's properties. The representation of each logical model is aligned with LOINC's RDF representation.

```
<StructureDefinition xmlns="http://hl7.org/fhir">
  <id value="[LOINC code]"/>
  <url value="http://loinc.org/owl#[LOINC code]"/>
```

```
  <version value="{LOINC version number]"/>  <!-- though this is not required -->
  <name value="[display - adjusted]"/> <!-- converted to meet regex by removing spaces, non-supported characters -->
  <title value="[display]"/>
  <status value="[derived from STATUS]"/>
  <experimental value="false"/>
  <date value="[last changed date]"/>
  <publisher value="http://loinc.org"/>
  <copyright value="This content LOINC® is copyright © 1995 Regenstrief Institute, Inc.
      and the LOINC Committee, and available at no cost under the license at
      http://loinc.org/terms-of-use"/>
  <differential>
    <element>
      <path value="[LOINC code]"/>
      <short value="[display]"/>
      <definition value="[definition]"/>
      <min value="0"/>
      <max value="1"/>
      <type>
        <code value="[mapped type - see below]"/>
      </type>
      <!-- if this is a LOINC question with linked answers -->
      <binding>
        <strength value="required"/>
        <valueSet value="http://loinc.org/vs/[linked answer list code]"/>
      </binding>
    </element>
  </differential>
</StructureDefinition>
```

The canonical URL http://loinc.org/rdf#[LOINC code] can be used to refer to logical model elements defined by LOINC such as e.g. in Questionnaire.item.definition.

The appropriate type is determined by mapping from the LOINC specified SCALE_TYP for v3 to FHIR using this table:

SCALE_TYP | FHIR data type
Qn | Quantity
Ord | CodeableConcept
OrdQn | Quantity and CodeableConcept (e.g. both in the data element; either is allowed)
Nom | CodeableConcept (and string?)
Nar | markdown (?)
Multi | Attachment
Doc | Attachment

4.3.4 Using UCUM with FHIR

URL: https://hl7.org/fhir/R4/ucum.html

4.3.4 Using UCUM with FHIR

Vocabulary Work Group | Maturity Level: 5 | Standards Status: Trial Use

The Units of Measure Coding System (UCUM) is recommended for use with the Quantity data type.

4.3.4.1 Summary

Source | UCUM is made available by the Regenstrief Institute, Inc and The UCUM Organization at http://unitsofmeasure.org
System | The URI http://unitsofmeasure.org identifies UCUM codes
Version | Where a version is used, it should be the standard UCUM version e.g. 1.9. There is no need to use version in the Coding data type, only in Value sets that use UCUM codes
Code | Valid expressions using the case sensitive symbols
Display | There is no defined display; the UCUM code is used directly for the display
Inactive | A few codes in UCUM are marked as deprecated (e.g. ppb, pptr)
Subsumption | No Subsumption relationships are defined by UCUM
Filter Properties | Two filter properties are defined as described below

4.3.4.2 Copyright

UCUM is Copyright © 1999-2013 Regenstrief Institute, Inc. and The UCUM Organization, Indianapolis, IN. All rights reserved. See TermsOfUse for details.

4.3.4.3 UCUM Expressions

UCUM is inherently a compositional code system; almost all UCUM codes are expressions composed using the UCUM expression syntax. Many servers, however, do not implement full support for the syntax, and rely on a large library of pre-built valid UCUM codes (FHIR includes a common UCUM codes value set for this purpose).

UCUM us always documented as a compositional code system. If a server does not support the full grammar, it should document that in its Terminology Capabilities Statement.

4.3.4.4 UCUM Filter Properties

This section documents the property filters that can be used with the UCUM code system in value set composition statements.

4.3.4.4.1 Property filter

Description | Restricts the expression to a describe a particular UCUM base property
Property Name | property
Operations Allowed | =
Values Allowed | [string name of property]
Comments | Restricts expressions to any expression that is comparable to a base unit with a matching property value. Note: this does not match the property on units, only base units

4.3.4.4.2 Canonical Filter

Description | Allows for any expression that is comparable to the named unit
Property Name | canonical
Operations Allowed | = / in
Values Allowed | UCUM expression
Comments | This allows any expression that is comparable to the given unit(s)

4.3.4.5 Implicit Value Sets

Implicit value sets are those whose specification can be predicted based on the grammar of the underlying code system, and the known structure of the URL that refers to them. There is one set of implicit value sets defined for UCUM: By Canonical Value.

If any value set resources exist with an identifier that conforms to the URL patterns specified below, the content of the resource must conform to the template provided. Profiles and other value set references are allowed to reference these value sets directly.

The value set identifier http://unitsofmeasure.org/vs is a value set that contains all UCUM codes.

4.3.4.5.1 UCUM Comparable Value Set

A value set with an identifier of "http://unitsofmeasure.org/vs/[expression]" must conform to this template, where [expression] is a valid UCUM expression:

```
<ValueSet xmlns="http://hl7.org/fhir">
  <text>
    <status value="generated"/>
    <div xmlns="http://www.w3.org/1999/xhtml">
      [some html that identifies that this value set
      includes all UCUM expressions that are comparable to the provided expression]
    </div>
  </text>
  <identifier value="http://unitsofmeasure.org/vs/[expression]"/>
  <version value="[optional - but recommended - UCUM version]"/>
  <name value="Ucum Expressions comparable to [expression]"/>
  <description value="Ucum Expressions comparable to [expression]"/>
  <status value="active"/>
  <date value="[optional date of UCUM release]"/>
  <compose>
    <include>
      <system value="http://unitsofmeasure.org"/>
      <filter>
        <property value="comparable"/>
        <op value="="/>
        <value value="[expression]"/>
      </filter>
    </include>
  </compose>
</ValueSet>
```

4.3.5 Using the NCI Metathesaurus with FHIR

URL: https://hl7.org/fhir/R4/ncimeta.html

4.3.5 Using the NCI Metathesaurus with FHIR

Vocabulary Work Group | Maturity Level: 2 | Standards Status: Trial Use

4.3.5.1 Summary

Source | NCI Metathesaurus the NCI Center for Biomedical Informatics and Information Technology (CBIIT)
System | The URI http://ncimeta.nci.nih.gov identifies the NCI Metathesaurus
Version | There is no version or versioning associated with the NCI metathesaurus
Code | The Concept Unique Identifier (CUI) is used for the code value for a Metathesaurus concept
Display | The name should be used as the display for English usage (e.g. "Aerosol Dose Form" for CUI C1112870)
Inactive | Todo: Describe how it is determined which concepts are inactive
Subsumption | No Subsumption relationships are defined for the NCI Metathesaurus
Filter Properties | None are described yet

4.3.5.2 Version Issues

There are no staged releases of the NCI metathesaurus, so there is no versioning policy.

4.3.5.3 Copyright/License Issues

The NCI metathesaurus is in the public domain, so there are no copyright notices needed in value sets that refer to NCI metathesaurus concepts, and there are no licensing requirements limiting use of NCI metathesaurus concepts in instances or systems.

4.3.5.4 MCI Metathesaurus MySQL Database

Like RxNorm, the RRF files that are the distributed source of the NCI Metathesaurus can be used to populate a MySQL database that contains the data. This page provides SQL statements that describe how to implement the features of the NCI Metathesaurus correctly against this database. They are provided only for implementer convenience, and do not imply that any particular approach must be used in implementations. (Note: for consistency, the RxNorm table and column names are used and the CUIs are 1 character longer, so the scripts must be updated).

For example, the correct display name for a CUI is

```
select STR from rxnconso where RXCUI = :code and SAB = 'RXNORM' and TTY <> 'SY'
```

4.3.5.5 NCI metathesaurus Filter Properties

This section documents the property filters that can be used with the RxNorm code system in value set composition statements.

The base SQL statement for returning a list of CUIs that conform to these filters is:

```
select RXCUI from RXNCONSO where SAB = 'RXNORM' and TTY <> 'SY'
```

4.3.5.5.1 Semantic Type

Description | Allows for selection of a set of CUIs based on their Semantic Type
Property Name | STY
Operations Allowed | = / in
Values Allowed | [column:]value
Comments | If a column is not specified, the default is TUI
SQL | and RXCUI in (select RXCUI from RXNSTY where [:column] = :value)

4.3.5.5.2 Source

Description | Allows for selection of the set of concepts that have mappings to a particular RxNorm source
Property Name | SAB
Operations Allowed | = / in
Values Allowed | Values from the SAB table (e.g. select RSAB from RXNsab)
SQL | and RXCUI in (select RXCUI from RXNconso where SAB = :value)

4.3.5.5.3 Term Type

Description | Allows for selection of a concept based on its designated type
Property Name | TTY
Operations Allowed | = / in
Values Allowed | TTY values from the RxNorm Concept table (e.g. select distinct TTY from rxnconso)
SQL | and TTY = :value

4.3.5.5.4 Relationship

Description | Allows for selection of a concept based on its relationships
Property Name | [REL]
Operations Allowed | = / in
Values Allowed | CUI:[RXCUI] or AUI:[RXAUI] must be a valid CUI or AUI. Note that a CUI does not need to have a SAB=RXNORM entry to be used here
Comments | [REL] (:rel) is one of AQ, CHD, PAR, QB, RB, RN, RO, RQ, SIB or SY
SQL | for CUI: and (RXCUI in (select RXCUI from rxnconso where RXCUI in (select RXCUI1 from rxnrel where REL = :rel and RXCUI2 = :value)) for AUI: and (RXCUI in (select RXCUI from rxnconso where RXAUI in (select RXAUI1 from rxnrel where REL = :rel and RXAUI2 = :value))

4.3.5.5.5 Relationship Type

Description | Allows for selection of a concept based on the type of its relationships
Property Name | [RELA]
Operations Allowed | = / in
Values Allowed | CUI:[RXCUI] or AUI:[RXAUI] must be a valid CUI or AUI. Note that a CUI does not need to have a SAB=RXNORM entry to be used here
Comments | [RELA] (:rela) is one of the relationship types listed in the NCI file "Relationships_Help_Page.txt" - the current list (nearly 1000 types) is at the end of the page
SQL | for CUI: and (RXCUI in (select RXCUI from rxnconso where RXCUI in (select RXCUI1 from rxnrel where RELA = :rel and RXCUI2 = :value)) for AUI: and (RXCUI in (select RXCUI from rxnconso where RXAUI in (select RXAUI1 from rxnrel where RELA = :rel and RXAUI2 = :value))

4.3.5.6 Implicit Value Sets

This section needs investigation

4.3.5.7 Current NCI Metathesaurus relationship types

- 3_UTR_of
- 5_UTR_of
- Abnormal_Cell_Affected_By_Chemical_Or_Drug
- Abnormality_Associated_With_Allele
- Abstract_of
- access_device_used_by
- access_of
- action_of
- active_ingredient_of
- active_metabolites_of
- Activity_Of_Allele
- adheres_to
- adjacent_to
- afferent_to
- agent_in
- alias_of
- Allele_Absent_From_Wild-type_Chromosomal_Location
- Allele_Has_Abnormality
- Allele_Has_Activity
- Allele_In_Chromosomal_Location
- Allele_of
- Allele_Plays_Altered_Role_In_Process
- Allele_Plays_Role_In_Metabolism_Of_Chemical_Or_Drug
- allelic_variant_of
- Amino_Acid_Variant_of
- analyzed_by
- analyzes
- Anatomic_Structure_Has_Location
- Anatomic_Structure_Is_Physical_Part_Of
- anatomical_site
- Anatomy_Originated_From_Biological_Process
- Aneuploidy_Addition_of
- Aneuploidy_Deletion_of
- anterior_to
- application_of
- Arm_Location_of
- Arm_of
- arterial_supply_of
- articulates_with
- associated_disease
- associated_finding_of
- associated_genetic_condition
- associated_morphology_of
- associated_procedure_of
- associated_with
- Associated_With_Malfunction_Of_Gene_Product
- attaches_to
- attributed_constitutional_part_of
- attributed_continuous_with

- attributed_part_of
- attributed_regional_part_of
- Author_of
- Band_Location_of
- Band_of
- bearer_of
- Biological_Process_Has_Associated_Location
- Biological_Process_Has_Initiator_Chemical_Or_Drug
- Biological_Process_Has_Initiator_Process
- Biological_Process_Has_Result_Anatomy
- Biological_Process_Has_Result_Biological_Process
- Biological_Process_Has_Result_Chemical_Or_Drug
- Biological_Process_Involves_Chemical_Or_Drug
- Biological_Process_Involves_Gene_Product
- Biological_Process_Is_Part_Of_Process
- Biological_Process_Results_From_Biological_Process
- Biomarker_Type_Includes_Gene
- Biomarker_Type_Includes_Gene_Product
- blood_supply_of
- bounded_by
- bounds
- branch_of
- branch_part_of
- causative_agent_of
- cause_of
- cell_connecting_part_of
- cell_shape_of
- cell_surface_specialization_of
- Cell_Type_Is_Associated_With_EO_Disease
- Cell_Type_Or_Tissue_Affected_By_Chemical_Or_Drug
- Centromere_of
- CH3_Status_of
- Chemical_Or_Drug_Affects_Abnormal_Cell
- Chemical_Or_Drug_Affects_Cell_Type_Or_Tissue
- Chemical_Or_Drug_Affects_Gene_Product
- Chemical_Or_Drug_Has_Mechanism_Of_Action
- Chemical_Or_Drug_Has_Physiologic_Effect
- Chemical_Or_Drug_Initiates_Biological_Process
- Chemical_Or_Drug_Is_Metabolized_By_Enzyme
- Chemical_Or_Drug_Is_Product_Of_Biological_Process
- Chemical_Or_Drug_Metabolism_Is_Associated_With_Allele
- Chemical_Or_Drug_Plays_Role_In_Biological_Process
- chemical_structure_of
- Chemotherapy_Regimen_Has_Component
- Chromosomal_Location_of
- Chromosomal_Location_Of_Allele
- Chromosomal_Location_of_Wild-type_Gene
- Chromosomal_Structural_Variant
- Chromosome_Involved_In_Cytogenetic_Abnormality
- Chromosome_Mapped_To_Disease
- class_code_classified_by
- classified_as

- classifies
- classifies_class_code
- clinical_course_of
- common_name_of
- Completely_Excised_Anatomy_Has_Procedure
- Completely_Excised_Anatomy_May_Have_Procedure
- Complex_Has_Physical_Part
- component_of
- Concept_In_Subset
- conceptual_part_of
- conjugate_component_of
- consider
- consider_from
- consists_of
- Constituent_Amino_Acid_of
- Constituent_Element_of
- Constituent_Protein_of
- Constituent_Variant_of
- constitutes
- constitutional_part_of
- contained_in
- contains
- context_binding_of
- continuation_branch_of
- continuous_with
- continuous_with_distally
- continuous_with_proximally
- contraindicated_with_disease
- contraindicating_class_of
- contraindicating_mechanism_of_action_of
- contraindicating_physiologic_effect_of
- Cytogenetic_Abnormality_Involves_Chromosome
- Data_Element_Of
- definitional_manifestation_of
- degree_of
- Deleted_Region_End_Band
- Deleted_Region_Start_Band
- denoted_by
- denotes
- dependent_of
- derivatized_to
- derives_from
- determines_parameter_for
- determines_property
- develops_from
- device_used_by
- diagnosed_by
- diagnoses
- direct_device_of
- direct_morphology_of
- direct_procedure_site_of
- direct_substance_of

- Disease_Excludes_Abnormal_Cell
- Disease_Excludes_Cytogenetic_Abnormality
- Disease_Excludes_Finding
- Disease_Excludes_Molecular_Abnormality
- Disease_Excludes_Normal_Cell_Origin
- Disease_Excludes_Normal_Tissue_Origin
- Disease_Excludes_Primary_Anatomic_Site
- Disease_Has_Abnormal_Cell
- Disease_Has_Accepted_Treatment_With_Regimen
- Disease_Has_Associated_Anatomic_Site
- Disease_Has_Associated_Disease
- Disease_Has_Associated_Gene
- Disease_Has_Cytogenetic_Abnormality
- Disease_Has_Finding
- Disease_Has_Metastatic_Anatomic_Site
- Disease_Has_Molecular_Abnormality
- Disease_Has_Normal_Cell_Origin
- Disease_Has_Normal_Tissue_Origin
- Disease_Has_Primary_Anatomic_Site
- Disease_Is_Grade
- Disease_Is_Marked_By_Gene
- Disease_Is_Stage
- Disease_Mapped_To_Chromosome
- Disease_Mapped_To_Gene
- Disease_May_Have_Abnormal_Cell
- Disease_May_Have_Associated_Disease
- Disease_May_Have_Cytogenetic_Abnormality
- Disease_May_Have_Finding
- Disease_May_Have_Molecular_Abnormality
- Disease_May_Have_Normal_Cell_Origin
- Disease_Pathogenesis_Involves_Gene
- disease_with_contraindication
- distal_to
- DOI_of
- dose_form_of
- doseformgroup_of
- drains_into
- drug_contraindicated_for
- due_to
- Duplicated_Region_End_Band
- Duplicated_Region_Start_Band
- effect_may_be_inhibited_by
- Effect_of
- efferent_to
- encapsulated_component_of
- Encoded_by
- Encodes
- Endogenous_Product_Related_To
- energy_used_by
- entrapment_site_of
- entrapped_component_of
- entry_version_of

- Enzyme_Metabolizes_Chemical_Or_Drug
- EO_Anatomy_Is_Associated_With_EO_Disease
- EO_Disease_Has_Associated_Cell_Type
- EO_Disease_Has_Associated_EO_Anatomy
- EO_Disease_Has_Property_Or_Attribute
- EO_Disease_Maps_To_Human_Disease
- epithelial_cell_shape_of
- evaluation_of
- Excised_Anatomy_Has_Procedure
- Excised_Anatomy_May_Have_Procedure
- exhibited_by
- exhibits
- Exon_of
- expanded_form_of
- external_to
- fascicular_architecture_of
- Feature_of
- finding_context_of
- finding_informer_of
- finding_method_of
- finding_site_of
- focus_of
- form_of
- function_of
- Gene_Associated_With_Disease
- Gene_Encodes_Gene_Product
- Gene_Found_In_Organism
- Gene_Has_Abnormality
- Gene_Has_Physical_Location
- Gene_In_Chromosomal_Location
- Gene_Involved_In_Molecular_Abnormality
- Gene_Involved_In_Pathogenesis_Of_Disease
- Gene_Is_Biomarker_Of
- Gene_Is_Biomarker_Type
- Gene_Is_Element_In_Pathway
- Gene_Location_of
- Gene_Mapped_To_Disease
- Gene_Mutant_Encodes_Gene_Product_Sequence_Variation
- Gene_of
- Gene_Plays_Role_In_Process
- Gene_Product_Affected_By_Chemical_Or_Drug
- Gene_Product_Encoded_By_Gene
- Gene_Product_Expressed_In_Tissue
- Gene_Product_Has_Abnormality
- Gene_Product_Has_Associated_Anatomy
- Gene_Product_Has_Biochemical_Function
- Gene_Product_Has_Chemical_Classification
- Gene_Product_Has_Organism_Source
- Gene_Product_Has_Structural_Domain_Or_Motif
- Gene_Product_Is_Biomarker_Of
- Gene_Product_Is_Biomarker_Type
- Gene_Product_Is_Element_In_Pathway

- Gene_Product_Is_Physical_Part_Of
- Gene_Product_Malfunction_Associated_With_Disease
- Gene_Product_Plays_Role_In_Biological_Process
- Gene_Product_Sequence_Variation_Encoded_By_Gene_Mutant
- Genomic_Mutation_Of
- germ_origin_of
- gives_rise_to
- Has_3_UTR
- Has_5_UTR
- has_Abstract
- has_access
- has_action
- has_active_ingredient
- has_active_metabolites
- has_additive
- has_adherent
- has_affiliation
- has_agent
- has_alias
- Has_Allele
- has_allelic_variant
- Has_Amino_Acid_Variant
- Has_Aneuploidy_Addition
- Has_Aneuploidy_Deletion
- has_application
- Has_Arm
- Has_Arm_Location
- has_arterial_supply
- has_associated_finding
- has_associated_morphology
- has_associated_procedure
- has_atmospheric_component
- has_attributed_constitutional_part
- has_attributed_part
- has_attributed_regional_part
- has_Author
- Has_Band
- Has_Band_Location
- has_been_treated
- has_bioassay_data
- has_bioassays
- has_biomaterial_characteristics
- has_blood_supply
- has_branch
- has_branch_part
- has_cancer_site
- has_category
- has_causative_agent
- Has_CDRH_Parent
- has_cell_connecting_part
- has_cell_shape
- has_cell_surface_specialization

- Has_Centromere
- Has_CH3_Status
- has_chemical_structure
- has_chromosomal_aberration_classification
- Has_Chromosomal_Location
- has_citation
- has_clinical_course
- has_clinical_finding
- has_clinical_record
- has_clinical_treatment
- has_common_name
- has_component
- has_component_part
- has_compound
- has_conceptual_part
- has_conjugated_component_part
- Has_Constituent_Amino_Acid
- Has_Constituent_Element
- Has_Constituent_Protein
- Has_Constituent_Variant
- has_constitutional_part
- has_context_binding
- has_continuation_branch
- has_contraindicated_drug
- has_contraindicating_class
- has_contraindicating_mechanism_of_action
- has_contraindicating_physiologic_effect
- has_cubic_volume
- Has_Data_Element
- has_database
- has_database_entry_type
- has_datum_value
- has_definitional_manifestation
- has_degree
- has_dependent
- has_diameter
- has_direct_device
- has_direct_morphology
- has_direct_procedure_site
- has_direct_substance
- has_disease_location
- has_disease_staging
- has_disease_state
- has_DOI
- has_donor
- has_dose_form
- has_doseformgroup
- Has_Effect
- has_encapsulated_component_part
- has_endpoint_of_measurement
- has_entrapment_site
- has_entrapped_component_part

- has_entry_version
- has_epithelial_cell_shape
- has_evaluation
- Has_Exon
- has_expanded_form
- has_experiment_design
- has_experiment_design_type
- has_experiment_factors
- has_factor_value
- has_factor_value_ontology_entry
- has_family_member
- has_family_relationship
- has_fascicular_architecture
- Has_Feature
- has_feature_shape
- has_fiducials
- has_finding_context
- has_finding_informer
- has_finding_method
- has_finding_site
- has_focus
- has_form
- Has_Free_Acid_Or_Base_Form
- has_function
- Has_Gene
- Has_Gene_Location
- Has_Gene_Product_Element
- Has_Genomic_Mutation
- has_germ_origin
- has_hardware
- has_height
- has_host
- has_host_part
- has_identification_type
- has_image_format
- has_indicator
- has_indirect_device
- has_indirect_morphology
- has_indirect_procedure_site
- has_individual
- has_individual_genetic_characteristics
- has_ingredient
- has_ingredients
- has_inherent_3d_shape
- has_inheritance_type
- has_initial_time_point
- has_innervation_source
- has_input_participant
- has_insertion
- has_integral_part
- has_intent
- has_interpretation

- Has_Intron
- has_Journal_Name
- has_laterality
- has_length
- has_location
- has_lymphatic_drainage
- has_MAGE_description
- has_manifestation
- has_manufacturer
- has_mapping_qualifier
- has_mass
- Has_Maternal_Uniparental_Disomy
- has_maximum_measurement
- has_measure
- has_measurement
- has_measurement_method
- has_measurement_type
- has_mechanism_of_action
- has_member
- has_method
- Has_Mode_of_Inheritance
- has_multi_level_category
- has_muscle_attachment
- has_muscle_insertion
- has_muscle_origin
- has_nerve_supply
- Has_NICHD_Parent
- has_node_value
- has_node_value_type
- has_nodes
- Has_Nucleotide_Repeat
- Has_Nucleotide_Variant
- has_nutrient_component
- has_occurrence
- has_organism_part
- has_orientation
- has_origin
- has_output_participant
- has_owner
- has_owning_affiliate
- has_owning_section
- has_owning_subsection
- has_parent_organization
- has_part
- has_part_modified
- has_participant
- Has_Paternal_Uniparental_Disomy
- has_pathological_process
- has_performer
- has_permuted_term
- has_pharmacokinetics
- Has_Physical_Part_Of_Anatomic_Structure

- has_physical_state
- has_physiologic_effect
- has_precise_ingredient
- has_primary_segmental_supply
- has_print_name
- has_prior_disease_state
- has_priority
- has_procedure_context
- has_procedure_device
- has_procedure_morphology
- has_procedure_site
- has_product_component
- has_property
- has_property_set
- has_protocol
- has_providers
- has_Publication_Year
- has_PubMedID
- has_quality
- has_quantified_form
- has_reason_for_deprecation
- has_recipient_category
- has_regional_part
- has_result
- has_revision_status
- has_role
- has_route_of_administration
- Has_RT_Product
- Has_Salt_Form
- has_scale
- has_scale_type
- has_secondary_segmental_supply
- has_segment
- has_segmental_composition
- has_segmental_supply
- has_severity
- has_shape
- has_single_level_category
- has_software
- has_sort_version
- has_species
- has_specimen
- has_specimen_procedure
- has_specimen_source_identity
- has_specimen_source_morphology
- has_specimen_source_topography
- has_specimen_substance
- has_subject_relationship_context
- Has_Subset
- has_supported_concept_property
- has_supported_concept_relationship
- has_surgical_approach

- has_systemic_part
- Has_Target
- Has_Telomere
- has_temperature_condition
- has_temporal_context
- has_test_result
- has_test_type
- has_therapeutic_class
- has_time_period
- has_tradename
- Has_Transcript
- has_treatment
- has_tributary
- has_type
- has_unit
- has_unit_of_measure
- has_units
- has_URI
- has_venous_drainage
- has_version
- Human_Disease_Maps_To_EO_Disease
- Human_Sex_Determinant
- icd_dagger
- identification_type_of
- Imaged_Anatomy_Has_Procedure
- included_in
- includes
- indicator_of
- indirect_device_of
- indirect_morphology_of
- indirect_procedure_site_of
- induced_by
- induces
- inferior_to
- ingredient_of
- ingredients_of
- inherence_for
- inherent_3d_shape_of
- inheres_in
- inheritance_type_of
- innervates
- insertion_of
- instrument_used_by
- intent_of
- internal_to
- interpretation_of
- interprets
- Intron_of
- INV_Chromosomal_Structural_Variant
- INV_Deleted_Region_End_Band
- INV_Deleted_Region_Start_Band
- INV_Duplicated_Region_End_Band

- INV_Duplicated_Region_Start_Band
- INV_Human_Sex_Determinant
- INV_Inverted_Region_End_Band
- INV_Inverted_Region_End_Exon
- INV_Inverted_Region_End_Gene
- INV_Inverted_Region_End_UTR
- INV_Inverted_Region_Start_Band
- INV_Inverted_Region_Start_Exon
- INV_Inverted_Region_Start_Gene
- INV_Inverted_Region_Start_Intron
- INV_Involves
- INV_Isochromosome_Origin
- INV_Karyotype_Class
- INV_Source_Band
- INV_Source_Exon
- INV_Source_Gene
- INV_Source_Intron
- INV_Target_Band
- INV_Target_Exon
- INV_Target_Gene
- INV_Target_Intron
- inverse_has_additive
- inverse_has_affiliation
- inverse_has_atmospheric_component
- inverse_has_been_treated
- inverse_has_bioassay_data
- inverse_has_bioassays
- inverse_has_biomaterial_characteristics
- inverse_has_cancer_site
- inverse_has_category
- inverse_has_chromosomal_aberration_classification
- inverse_has_citation
- inverse_has_clinical_finding
- inverse_has_clinical_record
- inverse_has_clinical_treatment
- inverse_has_compound
- inverse_has_cubic_volume
- inverse_has_database
- inverse_has_database_entry_type
- inverse_has_diameter
- inverse_has_disease_location
- inverse_has_disease_staging
- inverse_has_disease_state
- inverse_has_donor
- inverse_has_experiment_design
- inverse_has_experiment_design_type
- inverse_has_experiment_factors
- inverse_has_factor_value
- inverse_has_factor_value_ontology_entry
- inverse_has_family_member
- inverse_has_family_relationship
- inverse_has_feature_shape

- inverse_has_fiducials
- inverse_has_hardware
- inverse_has_height
- inverse_has_host
- inverse_has_host_part
- inverse_has_image_format
- inverse_has_individual
- inverse_has_individual_genetic_characteristics
- inverse_has_initial_time_point
- inverse_has_length
- inverse_has_MAGE_description
- inverse_has_manufacturer
- inverse_has_mass
- inverse_has_maximum_measurement
- inverse_has_measurement_type
- inverse_has_node_value
- inverse_has_node_value_type
- inverse_has_nodes
- inverse_has_nutrient_component
- inverse_has_organism_part
- inverse_has_owner
- inverse_has_parent_organization
- inverse_has_part_modified
- inverse_has_performer
- inverse_has_prior_disease_state
- inverse_has_property_set
- inverse_has_protocol
- inverse_has_providers
- inverse_has_reason_for_deprecation
- inverse_has_software
- inverse_has_species
- inverse_has_test_result
- inverse_has_test_type
- inverse_has_treatment
- inverse_has_type
- inverse_has_units
- inverse_has_URI
- inverse_isa
- inverse_was_tested_for
- Inverted_Region_End_Band
- Inverted_Region_End_Exon
- Inverted_Region_End_Gene
- Inverted_Region_End_UTR
- Inverted_Region_Start_Band
- Inverted_Region_Start_Exon
- Inverted_Region_Start_Gene
- Inverted_Region_Start_Intron
- Involves
- Is_Abnormal_Cell_Of_Disease
- Is_Abnormality_Of_Gene
- Is_Abnormality_Of_Gene_Product
- is_anatomical_site_of

- Is_Associated_Anatomic_Site_Of
- Is_Associated_Anatomy_Of_Gene_Product
- Is_Associated_Disease_Of
- Is_Biochemical_Function_Of_Gene_Product
- is_borne_by
- Is_Chemical_Classification_Of_Gene_Product
- Is_Chromosomal_Location_Of_Gene
- Is_Component_Of_Chemotherapy_Regimen
- Is_Cytogenetic_Abnormality_Of_Disease
- is_datum_of
- Is_Finding_Of_Disease
- Is_Grade_Of_Disease
- is_integral_part_of
- is_interpreted_by
- Is_Location_Of
- Is_Location_Of_Anatomic_Structure
- Is_Location_Of_Biological_Process
- Is_Marked_By_Gene_Product
- is_measurement_endpoint_of
- Is_Mechanism_Of_Action_Of_Chemical_Or_Drug
- Is_Metastatic_Anatomic_Site_Of_Disease
- Is_Molecular_Abnormality_Of_Disease
- Is_Normal_Cell_Origin_Of_Disease
- Is_Normal_Tissue_Origin_Of_Disease
- Is_Not_Abnormal_Cell_Of_Disease
- Is_Not_Cytogenetic_Abnormality_Of_Disease
- Is_Not_Finding_Of_Disease
- Is_Not_Molecular_Abnormality_Of_Disease
- Is_Not_Normal_Cell_Origin_Of_Disease
- Is_Not_Normal_Tissue_Origin_Of_Disease
- Is_Not_Primary_Anatomic_Site_Of_Disease
- Is_Organism_Source_Of_Gene_Product
- Is_Physical_Location_Of_Gene
- Is_Physiologic_Effect_Of_Chemical_Or_Drug
- Is_Primary_Anatomic_Site_Of_Disease
- Is_Property_Or_Attribute_Of_EO_Disease
- Is_Qualified_By
- is_realized_in
- Is_Related_To_Endogenous_Product
- Is_Stage_Of_Disease
- Is_Structural_Domain_Or_Motif_Of_Gene_Product
- Is_Target_Of_Agent
- is_temperature_of
- is_time_period_of
- isa
- Isochromosome_Origin
- Journal_Name_of
- Karyotype_Class
- Kind_Is_Domain_Of
- Kind_Is_Range_Of
- larger_than
- laterality_of

- location_of
- lymphatic_drainage_of
- manifestation_of
- mapped_from
- mapped_to
- mapping_qualifier_of
- Maternal_Uniparental_Disomy_of
- May_Be_Abnormal_Cell_Of_Disease
- May_Be_Associated_Disease_Of_Disease
- may_be_caused_by
- May_Be_Cytogenetic_Abnormality_Of_Disease
- may_be_diagnosed_by
- May_Be_Finding_Of_Disease
- May_Be_Molecular_Abnormality_Of_Disease
- May_Be_Normal_Cell_Origin_Of_Disease
- may_be_prevented_by
- may_be_qualified_by
- may_be_treated_by
- may_cause
- may_diagnose
- may_inhibit_effect_of
- may_prevent
- may_qualify
- may_treat
- measure_of
- measured_by
- measurement_method_of
- measurement_of
- measures
- mechanism_of_action_of
- member_of
- metabolic_site_of
- method_of
- modality_is_related_to
- Mode_of_Inheritance
- Molecular_Abnormality_Involves_Gene
- mth_british_form_of
- mth_expanded_form_of
- mth_has_british_form
- mth_has_expanded_form
- mth_has_plain_text_form
- mth_has_xml_form
- mth_plain_text_form_of
- mth_xml_form_of
- muscle_attachment_of
- muscle_insertion_of
- muscle_origin_of
- Negative_Protein_Expression
- Negatively_Expressed_By
- negatively_regulated_by
- negatively_regulates
- nerve_supply_of

- Nucleotide_Repeat_of
- Nucleotide_Variant_of
- occurs_after
- occurs_before
- occurs_in
- Organism_Has_Gene
- orientation_of
- origin_of
- owning_affiliate_of
- owning_section_of
- owning_subsection_of
- parameter_determined_from
- Parent_Is_CDRH
- Parent_Is_NICHD
- part_component_of
- part_of
- Partially_Excised_Anatomy_Has_Procedure
- Partially_Excised_Anatomy_May_Have_Procedure
- participates_in
- Paternal_Uniparental_Disomy_of
- pathological_process_of
- Pathway_Has_Gene_Element
- permuted_term_of
- pharmacokinetics_of
- physical_state_of
- physiologic_effect_of
- Positive_Protein_Expression
- Positively_Expressed_By
- positively_regulated_by
- positively_regulates
- posterior_to
- precise_ingredient_of
- primary_segmental_supply_of
- print_name_of
- priority_of
- procedure_context_of
- procedure_device_of
- Procedure_Has_Completely_Excised_Anatomy
- Procedure_Has_Excised_Anatomy
- Procedure_Has_Imaged_Anatomy
- Procedure_Has_Partially_Excised_Anatomy
- Procedure_Has_Target_Anatomy
- Procedure_May_Have_Completely_Excised_Anatomy
- Procedure_May_Have_Excised_Anatomy
- Procedure_May_Have_Partially_Excised_Anatomy
- procedure_morphology_of
- procedure_site_of
- Process_Altered_By_Allele
- Process_Includes_Biological_Process
- Process_Initiates_Biological_Process
- Process_Involves_Gene
- product_component_of

- projects_from
- projects_to
- projects_towards
- property_determined_from
- property_of
- proximal_to
- Publication_Year_of
- PubMedID_of
- Qualifier_Applies_To
- quality_of
- quantified_form_of
- reagent_used_in
- realizes
- receives_attachment
- receives_drainage_from
- receives_input_from
- receives_projection_from
- recipient_category_of
- reformulated_to
- reformulation_of
- Regimen_Has_Accepted_Use_For_Disease
- regional_part_of
- regulated_by
- regulates
- related_modality
- related_to
- replaced_by
- replaces
- responsive_to_stimulus
- result_of
- result_of_regulation
- results_in
- revision_status_of
- Role_Has_Domain
- Role_Has_Parent
- Role_Has_Range
- Role_Is_Parent_Of
- role_of
- route_of_administration_of
- RT_Product_of
- scale_of
- scale_type_of
- secondary_segmental_supply_of
- see
- see_from
- Segment_of
- segmental_composition_of
- segmental_supply_of
- sends_output_to
- severity_of
- shape_of
- sib_in_branch_of

- sib_in_isa
- sib_in_part_of
- sib_in_tributary_of
- site_of_metabolism
- smaller_than
- sort_version_of
- Source_Band
- Source_Exon
- Source_Gene
- Source_Intron
- specifies_value
- specimen_of
- specimen_procedure_of
- specimen_source_identity_of
- specimen_source_morphology_of
- specimen_source_topography_of
- specimen_substance_of
- stimulus_causes_response
- subject_relationship_context_of
- Subset_Includes_Concept
- Subset_of
- substance_used_by
- Subsumed_By
- Subsumes
- superior_to
- supported_concept_property_in
- supported_concept_relationship_in
- surgical_approach_of
- surrounded_by
- surrounds
- systemic_part_of
- Target_Anatomy_Has_Procedure
- Target_Band
- Target_Exon
- Target_Gene
- Target_Intron
- technique_used_for
- Telomere_of
- temporal_context_of
- therapeutic_class_of
- Tissue_Is_Expression_Site_Of_Gene_Product
- tradename_of
- Transcript_of
- treated_by
- treats
- tributary_of
- unit_of
- unit_of_measurement_of
- use
- used_by
- used_for
- uses

- uses_access_device
- uses_device
- uses_energy
- uses_instrument
- uses_reagent
- uses_substance
- uses_technique
- value_specified_at
- venous_drainage_of
- version_of
- was_tested_for

4.3.6 Using NDF-RT (the National Drug File - Reference Terminology) with FHIR

URL: https://hl7.org/fhir/R4/ndfrt.html

4.3.6 Using NDF-RT (the National Drug File - Reference Terminology) with FHIR

Vocabulary Work Group | Maturity Level: 2 | Standards Status: Trial Use

4.3.6.1 Summary

Source | the National Drug File - Reference Terminology - prepared by Veterans Health Administration , and distributed as part of UMLS by the NLM (direct link)
System | The URI to identify NDF-RT is not resolved. As a temporary arrangement, the URL "http://hl7.org/fhir/ndfrt" is to be used
Version | A version is not needed. (Use the date of the UMLS release for the version of NDF-RT if a version is desired.)
Code | The NUI is used for the code value for an NDF-RT concept
Display | ??
Inactive | Todo: Describe how it is determined which concepts are inactive
Subsumption | Subsumption testing is based in the Is-a relationship defined by NDFRT
Filter Properties | None are described yet

This URL is temporary while the NDF-RT and FHIR teams discuss the long term arrangements. Further documentation can be found in evs .

4.3.6.2 Version Issues

NDF-RT is released as part of UMLS. Therefore, each successive release has the date of the UMLS release as its version.

4.3.6.3 Copyright/License Issues

NDF-RT has no copyright acknowledgement required. However, users must adhere to the UMLS license.

4.3.6.4 NDF-RT Filter Properties

This section documents the property filters that can be used with the SNOMED CT code system in value set composition statements.

4.3.6.4.1 By Subsumption

Description | Select a set of concepts based on subsumption testing
Property Name | concept
Operations Allowed | is-a
Values Allowed | NUI
Comments | Includes all concepts that have a transitive is-a relationship with the concept Id provided in the value as an NUI (including the concept itself)

Others yet to be done.

4.3.6.5 Implicit Value Sets

Yet to be done.

4.3.7 Using Unique Ingredient Identifier (UNII) with FHIR

URL: https://hl7.org/fhir/R4/unii.html

4.3.7 Using Unique Ingredient Identifier (UNII) with FHIR

Vocabulary Work Group | Maturity Level: 3 | Standards Status: Trial Use

4.3.7.1 Summary

Source | FDA Substance Registration System
System | The URI to identify UNII codes is http://fdasis.nlm.nih.gov
Version | If it is desired to exchange the version, use the date of the file in the UNII list download in the format YYYYMMDD
Code | Use the value of the UNII column in the UNII List
Display | Use the value of the PT (Preferred Term) column in the UNII List
Inactive | Todo: Describe how it is determined which concepts are inactive
Subsumption | No Subsumption relationships are defined by UNII
Filter Properties | None are described yet

4.3.7.2 Version Issues

To be investigated

4.3.7.3 Copyright/License Issues

UNII has no copyright acknowledgement needed, nor are there any license terms to adhere to.

4.3.7.4 NDF-RT Filter Properties

No need for filters identified yet.

4.3.7.5 Implicit Value Sets

No need for implicit value sets identified yet.

4.3.8 Using CVX (Vaccine Administered) with FHIR

URL: https://hl7.org/fhir/R4/cvx.html

4.3.8 Using CVX (Vaccine Administered) with FHIR

Vocabulary Work Group | Maturity Level: 3 | Standards Status: Trial Use

4.3.8.1 Summary

Source | Available at http://www2a.cdc.gov/vaccines/iis/iisstandards/vaccines.asp?rpt=cvx . Developed by The CDC's National Center of Immunization and Respiratory Diseases (NCIRD)
System | The URI to identify CVX codes is http://hl7.org/fhir/sid/cvx
Version | If it is desired to exchange the version, use the date of the last updated code in the format YYYYMMDD
Code | Use the value of "CVX Code" column in the web page
Display | Use the value of the "Short Description" column in the web page
Inactive | Todo: Describe how it is determined which concepts are inactive
Subsumption | No Subsumption relationships are defined by CVX
Filter Properties | None are described yet

4.3.8.2 Version Issues

If it is desired to exchange the version, use the date of the last updated code in the format YYYYMMDD.

4.3.8.3 Copyright/License Issues

CVX has no copyright acknowledgement needed, nor are there any license terms to adhere to.

4.3.8.4 CVX Filter Properties

No need for filters identified yet.

4.3.8.5 Implicit Value Sets

No need for implicit value sets identified yet.

4.3.9 Using CPT with FHIR

URL: https://hl7.org/fhir/R4/cpt.html

4.3.9 Using CPT with FHIR

Vocabulary Work Group | Maturity Level: 2 | Standards Status: Trial Use

4.3.9.1 Summary

Source | CPT is made managed by the American Medical Association
System | The URI http://www.ama-assn.org/go/cpt identifies the CPT code system
Version | Where a version is appropriate, use the year of release e.g. 2014
Code | "Code" in the CPT tables (a 5-character code)
Display | "Description" in the CPT tables
Inactive | Todo: Describe how it is determined which concepts are inactive
Subsumption | No Subsumption relationships are defined by CPT
Filter Properties | None defined

4.3.9.2 Version Issues

CPT is released each October. CPT versions are identified simply by the year of their release.

4.3.9.3 Example Usage

```
<coding>
  <system value="http://www.ama-assn.org/go/cpt"/>
  <version value="2014"/>
  <code value="31502"/>
  <display value="Tracheotomy tube change prior to establishment of fistula tract"/>
</coding>
```

4.3.9.4 Copyright/License Issues

CPT is a registered trademark of the American Medical Association. The AMA holds the copyright for the CPT coding system.

When Value Sets include CPT codes, the copyright element should include the text "CPT copyright 2014 American Medical Association. All rights reserved.".

4.3.9.5 CPT Filter Properties

No filter properties have been defined at this time.

4.3.9.6 Implicit Value Sets

The value set URL http://hl7.org/fhir/ValueSet/cpt-all is a value set that includes all CPT codes.

4.3.10 Using NDC and NHRIC Codes with FHIR

URL: https://hl7.org/fhir/R4/ndc.html

4.3.10 Using NDC and NHRIC Codes with FHIR

Vocabulary Work Group | Maturity Level: 2 | Standards Status: Trial Use

The National Drug Codes (NDC) and National Health Related Items Code (NHRIC) codes are codes issued by the FDA for tracking drugs and devices. Note that the NHRIC codes are being replaced by the UDI system .

4.3.10.1 Summary

Source | National Drug Code Directory and the NHRIC Labeler Codes
System | The URI to identify NDC/NHRIC codes is http://hl7.org/fhir/sid/ndc
Version | Use YYYYMMDD for the date of publication, but see note below
Code | The 10 digit NDC code, with "-" included. Note that different NDC codes have different positions for the "-": 1234-5678-90, 12345-6789-0, or 12345-678-90. The "-" must be correct for each NDC code
Display | Use the PACKAGEDESCRIPTION column value from the TSV or Excel distribution file
Inactive | Todo: Describe how it is determined which concepts are inactive
Subsumption | No Subsumption relationships are defined for the NDC codes
Filter Properties | None are described yet

4.3.10.2 Version Issues

The FDA published list of NDC codes for finished drug products is updated daily. Use the format YYYYMMDD to refer to a particular distribution. Note that while only valid NDC codes appear in the distribution file, there are other NDC codes that organizations have assigned but not yet reported to FDA. Therefore, the full set of NDCs that exists in the marketplace is unknown and cannot be versioned completely.

4.3.10.3 Copyright/License Issues

NDC codes have no copyright acknowledgment or license requirements.

4.3.10.4 NDF-RT Filter Properties

No need for filters identified yet.

4.3.10.5 Implicit Value Sets

No need for implicit value sets identified yet.

4.3.11 Using ICD-[X] Codes with FHIR

URL: https://hl7.org/fhir/R4/icd.html

or, with the + and * characters included:

4.3.11 Using ICD-[X] Codes with FHIR

Vocabulary Work Group | Maturity Level: 2 | Standards Status: Trial Use

ICD is a family of code systems maintained by WHO , with many countries publishing their own variants.

There are two principal revisions of ICD in use - ICD-10 and ICD-9 (note that while US usage has recently updated to ICD-10, there is still a lot of legacy data coded in ICD-9). Though these can be referred to as

different versions of ICD, they are entirely distinct sets of codes, with significant differences in organization and coding rules. Plus, if period ('.') characters are disregarded (as occurs in some systems), a few of the codes are overlapping between ICD-9 and ICD-10. Given these considerations, ICD-9 and ICD-10 are represented as entirely separate code systems. The next revision, ICD-11, is scheduled for release in 2017.

4.3.11.1 Summary

| ICD-10 | ICD-9
Source | WHO or see below | (CDC)
System | http://hl7.org/fhir/sid/icd-10 and http://hl7.org/fhir/sid/icd-10-[x] (see below) | http://hl7.org/fhir/sid/icd-9-cm
OID | 2.16.840.1.113883.6.3 | 2.16.840.1.113883.6.42
Version | The versioning convention and frequency may vary between the various ICD revisions and variants. WHO publishes a new version of ICD-10 annually in October (with minor updates annually, and major updates, if required, every 3 years - the versions are identified as 'YYYY', e.g. '2016'). The national variants (which in some cases are used multi-nationally) are also typically published on an annual basis (refer to the documentation for a particular variant for details).
Code | Either an ICD-10 or ICD-9 code, or a dual (multiple) coding expression - see below. ICD codes SHALL be represented with the period included, e.g. 123.4
Display | There are no specific conventions required or described for obtaining the complete display string for use for each code.
Inactive | ICD-9 and ICD-10 do not have codes that are identified as inactive (although in some cases previously included codes may have been removed or changed in meaning in subsequent versions).
Hierarchy | The tabular representations are organized with headings and multiple levels of codes (typically based on the numbers of digits contained in each code), but an explicit hierarchy is not defined.
Filter Properties | None are described yet.

4.3.11.2 ICD-10 variants

Variants (other variants exist which are not listed here):

Germany | http://fhir.de/CodeSystem/dimdi/icd-10-gm | see HL7 Germany page
Netherlands | http://hl7.org/fhir/sid/icd-10-nl | 2.16.840.1.113883.6.3.2
United States | http://hl7.org/fhir/sid/icd-10-cm | 2.16.840.1.113883.6.90

4.3.11.3 Multiple Coding

4.3.11.3.1 Dual Coding (“dagger and asterisk” system)

For dual ("two code", “dagger and asterisk”) coding see volume 2 ICD-10 Manual), section 3.1.3 Two codes for certain conditions. In cases where two codes are required, the primary recommendation for representing this coding in FHIR (in Coding.code) is to simply use the two ICD-10 codes separated by a space, e.g. "J21.8 B95.6", as the code value (string). This is a simple form of post-coordination syntax. Alternatively, another possible syntax that may be used (which may be desirable or required in some situations) is to include the characters of the dagger (represented as † or +) for the primary code and the asterisk (*) for the secondary code as part of the post-coordinated code value, e.g. "J21.8+ B95.6*". In either case, it is recommended that the primary (+) code for the underlying generalized disease is listed first, followed by the secondary (*) code for the specific manifestation in a particular organ or site.

Dual coding in ICD-10 is used for the following (and potentially other) reasons:

• Coding for diagnostic statements containing information about both (1) an underlying generalized disease and (2) a manifestation in a particular organ or site which is a clinical problem in its own right. This is referred to as the "dagger and asterisk" system, as it marks the primary code for the underlying disease with a dagger (†) and an optional additional code for the manifestation with an asterisk (*).

• Other optional dual coding (noted in the tabular representation as “Use additional code, if desired ...”)

• For local infections, classifiable to the “body systems” chapters, codes from Chapter I may be added to identify the infecting organism, where this information does not appear in the title of the rubric.

• For neoplasms with functional activity. To the code from Chapter II may be added the appropriate code from Chapter IV to indicate the type of functional activity.

• For neoplasms, the morphology code from Volume 1, although not part of the main ICD, may be added to the Chapter II code to identify the morphological type of the tumour.

• For conditions classifiable to F00-F09 (Organic, including symptomatic, mental disorders) in Chapter V, where a code from another chapter may be added to indicate the cause, i.e. the underlying disease, injury or other insult to the brain.

• Where a condition is caused by a toxic agent, a code from Chapter XX may be added to identify that agent.

• Where two codes can be used to describe an injury, poisoning or other adverse effect: a code from Chapter XIX, which describes the nature of the injury, and a code from Chapter XX, which describes the cause.

Dual Coding Example: "Staph aureus bronchiolitis" is coded using ICD-10 codes J21.8 "Acute bronchiolitis due to other specified organisms" and B95.6 "Staphylococcus aureus as the cause of diseases classified to other chapters" as:

```
<coding>
  <system value="http://hl7.org/fhir/sid/icd-10"/>
  <code value="J21.8 B95.6"/>
</coding>
```

```
<coding>
  <system value="http://hl7.org/fhir/sid/icd-10"/>
  <code value="J21.8+ B95.6*"/>
</coding>
```

4.3.11.3.2 Additional Characters

Some jurisdictions (e.g. Germany) have additional coding requirements that go beyond the dual coding “dagger and asterisk” coding approach (syntax). In ICD-10-GM used in Germany the ! character is used to indicate a secondary diagnosis.

Primary diagnosis

• S62.32 - Fracture of shaft of metacarpal bone

Secondary diagnosis

• Z33! - Pregnancy as a secondary diagnosis

The recommended syntax for representing these combinations of codes in FHIR (in Coding.code) is to include the additional (+*!) characters when they are present and to separate the code groups with a space, as:

```
<coding>
  <system value="http://fhir.de/CodeSystem/dimdi/icd-10-gm"/>
  <version value="2017"/>
  <code value="S62.32 Z33!"/>
</coding>
```

4.3.11.3.3 Three or More Codes

The coding also may require three or sometimes more codes for a complete representation of the intended meaning. A further German coding example (from the Deutsche Kodierrichtlinien manual) includes an additional secondary diagnosis and a monitoring code.

Additional secondary diagnosis and monitoring codes

• O09.1! - Duration of pregnancy between 5 and 13 weeks

• Z34 - Monitoring of a regular pregnancy

A proper interpretation of this extended example is: "A patient is admitted to hospital due to a fracture of the metacarpal shaft. Since she is six weeks pregnant, the pregnancy and the monitoring of the pregnancy are coded as secondary diagnoses." The recommended FHIR representation is:

```
<coding>
  <system value="http://fhir.de/CodeSystem/dimdi/icd-10-gm"/>
  <version value="2017"/>
  <code value="S62.32 Z33! O09.1! Z34"/>
</coding>
```

Other jurisdictions may have similar needs for multiple coding but with different specific coding requirements. In those cases local coding manuals and authorities should be consulted to determine the recommended or expected syntax to use in a FHIR Coding instance.

4.3.11.4 Copyright/License Issues

ICD-10 is ©Copyright World Health Organization (WHO). WHO licenses its published material widely, in order to encourage maximum use and dissemination. See Licensing WHO classifications for details. The ICD variants have their own separate copyright and licensing (refer to the documentation for the particular variant for details).

4.3.11.5 ICD-X Filter Properties

No need for filters identified yet.

4.3.11.6 Implicit Value Sets

No need for implicit value sets identified yet.

4.3.12 Using ISO 3166 Country Codes with FHIR

URL: https://hl7.org/fhir/R4/iso3166.html

4.3.12 Using ISO 3166 Country Codes with FHIR

Vocabulary Work Group | Maturity Level: 3 | Standards Status: Trial Use

4.3.12.1 Summary

Source | ISO 3166 Home Page

System | ISO 3166 is a 3 part standard, each of which defines a code system: urn:iso:std:iso:3166: Part 1, Country Codes (2-letter and 3-letter, and numerical codes) urn:iso:std:iso:3166:-2: Part 2, Subdivision (State/Province) Codes urn:iso:std:iso:3166:-3: Part 3, Historical Country Names Note: the URI used for Part 1 would be urn:iso:std:iso:3166:-1 if it were consistent with the other URIs, but urn:iso:std:iso:3166 is used for legacy reasons.

Version | If necessary to exchange the version (see below), use the year of release in the format YYYY

Code | Part 1: Any of the 2-letter, 3-letter, or numerical country name codes defined in Part 1 Part 2: Any of the codes for principal subdivisions (e.g province or state) of countries coded in Part 1 Part 3: One of the 4 letter historical country name codes defined in

Part 3 The codes SHALL always be represented in upper case, but (for robustness) comparisons are case insensitive.
Display | Use the Country or State/Province Name
Inactive | There are no codes that are inactive
Subsumption | No Subsumption relationships are defined amongst the Country Codes
Filter Properties | Regex on code - see below

4.3.12.2 Version Issues

A few country codes have been reused (e.g. CS). If a version is needed, simply use the year of publication e.g. 1998.

4.3.12.3 Copyright/License Issues

ISO Maintains the copyright on the country codes, and controls it's use carefully. For further details, see the ISO 3166 Home Page

4.3.12.4 ISO-3166 Filter Properties

The Part 1 Code system identified by the URI urn:iso:std:iso:3166 contains 3 types of codes for country:

• 2-letter

• 3-letter

• Numeric

In almost all contexts of use, only one of these 3 subsets of codes are used / allowed. Value sets can be defined for these by enumerating the relevant codes. Alternatively, a regex can be used to define the value set intensionally. For example, this filter specifies only 3 letter codes:

```
"filter" : [{
  "property" : "code",
  "op" : "regex",
  "value" : "[A-Z]{3}"
}]
```

4.3.12.5 Value Sets

This specification defines 3 commonly used value sets for use with ISO 3166 Country Codes:

• 2 letter Country Codes

• 3 letter Country Codes

• Numerical Country Codes

The latter two value sets are defined intensionally in this specification as a consequence of ISO Intellectual Property Restrictions.

4.3.13 Using MDC Codes with FHIR

URL: https://hl7.org/fhir/R4/mdc.html

A. No. If you wish to obtain the official 11073-10101 standard you will need to purchase that document. However, if you are just interested in using the codes, Ref-ids, and even descriptions, they are freely available in the NIST RTMMS tool. A. No. A. No. A. Yes In addition to the standard properties, the following properties are defined for MDC: Status Property

4.3.13 Using MDC Codes with FHIR

Health Care Devices Work Group | Maturity Level: 1 | Standards Status: Trial Use

4.3.13.1 Summary

Source | Medical Device Communications (MDC) codes are from ISO/IEEE 11073-10101 Nomenclature standard and amendments. This is a detailed system of codes used in personal health devices and and acute-care (point-of-care) medical devices for identification of physiological measurements and also for alerts, alarms, and numerous technical conditions such as calibration state and battery state. The physiological measurements can in most common cases be mapped to LOINC if desired using a table of equivalences developed by LOINC. Medical Codes and related values are available from the Rosetta Terminology Mapping Management System (RTMMS) , maintained by the U.S. National Institute of Standards and Technology. RTMMS includes new codes in the process of being published in the standard.
System | The URI urn:iso:std:iso:11073:10101 identifies the MDC code system.
Version | Date (in FHIR date format YYYY-MM-DD) that this version of the code system was published.
Code | MDC codes are 32-bit unsigned decimal integers where the upper 16 bits are the partition (a usage category - see below) and the lower 16 bits are the term codes. The codes are available as CF_CODE10 in the RTMMS database.
Display | The standard provides a Reference Identifier (REFID in RTMMS) for each code, which can placed in this element. If defined, Systematic Name, Common Term, and Acronym are added as designations for use as alternative display values
Inactive | Codes with status withdrawn (see properties below) are considered inactive
Specification | The normative specification is defined in the documents ISO/IEEE Standard 11073-10101 (2004) Health informatics — Point-of-care medical device communication — Part 10101:Nomenclature.
http://standards.ieee.org/findstds/standard/11073-10101-2004.html 11073-10101a (2015) IEEE Standard Health informatics — Point-of-care medical device communication — Part 10101: Nomenclature Amendment 1: Additional Definitions.
https://standards.ieee.org/findstds/standard/11073-10101a-2015.html

4.3.13.2 Copyright Issues

IEEE holds copyright in the standards referenced. IEEE, as part of its support of the RTMMS database and on-going, royalty-free agreement with the NIST, makes these terms available for the development of IEEE11073 compliant products and supporting material (e.g. in user documentation, collateral, etc.). Any use of IEEE terms beyond compliant products and support material may require prior approval from IEEE. Please notify IEEE of any request to use, modify, or reproduce these terms in any manner beyond the permitted use described above. To request permission, please submit your request to stds-ipr@ieee.org.

The following information is provided free of charge to all NIST RTMMS users via the IEEE-SA and NIST Royalty Free Agreement:

• Reference ID ('REFID' in RTMMS)

• Terminology Code ('CODE10', 'CF_CODE10', 'UCODE10', 'CF_UCODE10', 'ECODE10', and 'CF_ECODE10' in RTMMS)

• Description ('Term Description' in RTMMS)

• Systematic Name ('Systematic Name' in RTMMS)

• Common Term ('Common term' in RTMMS)

(Source: https://rtmms.nist.gov/rtmms/index.htm#!ieee).

4.3.13.3 Frequently Asked Questions on Use of MDC Nomenclature

Source: 11073.org Our Standards > Conditions of Use

Q. If I am writing a commercial application that takes medical measurements (perhaps from a proprietary device) and transcodes it to an HL7 V2 message or V3 document or FHIR resources using IEEE 11073 nomenclature codes, ref-ids, and descriptions obtained from RTMMS or are my own, am I required to pay any type of fee to IEEE?

Q. If I am writing a commercial application that decodes HL7 V2 messages, V3 documents, and FHIR resources, and displays the contents in a human readable form where the descriptions of the codes are my own or are from RTMMS, am I required to pay any type of fee to IEEE?

Q. If I make a commercial library with source where one of the source files contains all the codes, ref-id, and descriptions (either my own or from the RTMMS tool) needed for the type of application it supports, am I required to pay any type of fee to IEEE?

Q. Am I freely able to use the codes, refids and above descriptions in customer-facing documentation?

4.3.13.4 Reference Identifiers

Text reference identifiers are given in the standards for each numeric code identifying a concept. Since they were constructed in simple patterns that are usually easy for humans to deduce meanings from, they are convenient for human readers, where the numeric codes are not. They are generally composed of upper case letters such as MDC_ECG_HEART_RATE. The few exceptions are cases that where mixed-case identifiers are familiar to end users, such as identifiers for certain ECG leads.

4.3.13.5 Partition Codes

The MDC codes are 32-bit, four-byte, integers. The most significant 16 bits are partition codes. Partitions define terminology groups, for example the dimension partition contains all the unit codes. There are currently the following partitions defined:

Name	Reference Identifier	Code
Unspecified	MDC_PART_UNSPEC	0
Object infrastructure	MDC_PART_OBJ	1
Supervisory Control And DataAcquisition (SCADA)	MDC_PART_SCADA	2
Event	MDC_PART_EVT	3
Dimension	MDC_PART_DIM	4
Virtual Attribute	MDC_PART_VATTR	5
Parameter Group	MDC_PART_PGRP	6
Body Sites	MDC_PART_SITES	7
Infrastructure	MDC_PART_INFRA	8
File Exchange Format	MDC_PART_FEF	9
ECG Extension	MDC_PART_ECG_EXTN	10
IDCO Extension	MDC_PART_IDCO_EXTN	11
Disease Management	MDC_PART_PHD_DM	128
Health and Fitness	MDC_PART_PHD_HF	129
Assisted Independent Living	MDC_PART_PHD_AI	130
Return codes	MDC_PART_RET_CODE	255
External Nomenclature	MDC_PART_EXT_NOM	256
Device settings	MDC_PART_SETTINGS	258
Private	MDC_PART_PVT	1024

Some of the partitions are currently used only for Personal Health Devices (PHDs) such as the Health and Fitness partition. Others, such as the virtual attribute partition, are only used by Point of Care Devices

(PoCDs). However, there is nothing in either the 11073-10201, 11073-20601, or 11073-10101 standards that limit the use of any partition to either PoCDs or PHDs

4.3.13.6 Term Codes

The least significant 16-bits are term codes. While there are only a few partitions, for many of the partitions there are thousands of term codes. The term code, along with the partition, identifies the item. The example below shows a heart rate measurement encoding from an ECG device in XML and JSON:

```
<coding>
  <system value="urn:iso:std:iso:11073:10101"/>
  <code value="147842"/>
  <display value="MDC_ECG_HEART_RATE"/>
</coding>
```

```
coding": [{
  "system": "urn:iso:std:iso:11073:10101",
  "code": "147842",
  "display": "MDC_ECG_HEART_RATE"
}]
```

If one converts the code 147842 into HEX, the value becomes 0x24182. The most significant 16 bits indicates that the code comes from the SCADA partition (2) and the term code is 0x4182 or 16770. Implementers can easily obtain the partition and term codes using simple binary AND and SHIFT operations. If one looks up this code in the RTMMS tool one will find an array of information about the code, for example, the term description “Rate of cardiac beats”.

4.3.13.7 MDC Properties

status | Coding | Life cycle status of the term code in RTMMS
harmonized | boolean | Indicates whether the term code has been agreed upon during the open consensus-based Rosetta harmonization process
partition | code | Partition is a group for type+types of semantics that are assigned to a contiguous term code range and have a categorical relationship. Partition codes are listed in the table above

[Final definitions still to be determined from what's available at RTMMS]

Status | Description
provisional | Terms with provisional reference identifier and term code that may be used for development and interoperability testing. Provisional terms shall not be released in production devices
approved | Terms that got final approval for inclusion to RTMMS. Approved terms may be used in production devices
zombie | Provisional terms that didn't get final approval. Reference identifier and term code will not be allocated to new terms
published | Terms that are included in in a revision of the IEEE 11073-10101 standard
deprecated | Deprecated terms shall be removed from use in production devices
withdrawn | Use of withdrawn terms shall be indicated as an error

4.3.14.1 Code System http://terminology.hl7.org/CodeSystem/resource-type-link

URL: https://hl7.org/fhir/R4/codesystem-resource-type-link.html
Vocabulary Work Group | Maturity Level: 0 | Informative | Use Context: Any

This is a code system defined by the FHIR project.

Summary

Defining URL: | http://terminology.hl7.org/CodeSystem/resource-type-link
Version: | 4.0.1
Name: | PayeeResourceType
Title: | PayeeResourceType
Definition: | The type of payee Resource.
Committee: | ??
OID: | 2.16.840.1.113883.4.642.4.1180 (for OID based terminology systems)
Source Resource | XML / JSON

This Code system is used in the following value sets:

• ValueSet: PayeeResourceType (The type of payee Resource.)

• ValueSet: PayeeResourceType (The type of payee Resource.)

4.3.14.1.1 Content

4.3.14.1.2 PayeeResourceType

The type of payee Resource.

This code system http://terminology.hl7.org/CodeSystem/resource-type-link defines the following codes:

Code | Display | Definition
organization | Organization | Organization resource.
patient | Patient | Patient resource.
practitioner | Practitioner | Practitioner resource.

relatedperson | RelatedPerson | RelatedPerson resource.

See the full registry of code systems defined as part of FHIR.

Explanation of the columns that may appear on this page:

Level | A few code lists that FHIR defines are hierarchical - each code is assigned a level. See Code System for further information.
Source | The source of the definition of the code (when the value set draws in codes defined elsewhere)
Code | The code (used as the code in the resource instance). If the code is in italics, this indicates that the code is not selectable ('Abstract')
Display | The display (used in the display element of a Coding). If there is no display, implementers should not simply display the code, but map the concept into their application
Definition | An explanation of the meaning of the concept
Comments | Additional notes about how to use the code

4.3.14.2 Code System http://hl7.org/fhir/participantrequired

URL: https://hl7.org/fhir/R4/codesystem-participantrequired.html
Patient Administration Work Group | Maturity Level: 3 | Trial Use | Use Context: Any

This is a code system defined by the FHIR project.

Summary

Defining URL: | http://hl7.org/fhir/participantrequired
Version: | 4.0.1
Name: | ParticipantRequired
Title: | ParticipantRequired
Definition: | Is the Participant required to attend the appointment.
Committee: | Patient Administration Work Group
OID: | 2.16.840.1.113883.4.642.4.489 (for OID based terminology systems)
Source Resource | XML / JSON

This Code system is used in the following value sets:

• ValueSet: ParticipantRequired (Is the Participant required to attend the appointment.)

• ValueSet: ParticipantRequired (Is the Participant required to attend the appointment.)

4.3.14.2.1 Content

4.3.14.2.2 ParticipantRequired

Is the Participant required to attend the appointment.

This code system http://hl7.org/fhir/participantrequired defines the following codes:

Code | Display | Definition
required | Required | The participant is required to attend the appointment.
optional | Optional | The participant may optionally attend the appointment.
information-only | Information Only | The participant is excluded from the appointment, and might not be informed of the appointment taking place. (Appointment is about them, not for them - such as 2 doctors discussing results about a patient's test).

See the full registry of code systems defined as part of FHIR.

Explanation of the columns that may appear on this page:

Level | A few code lists that FHIR defines are hierarchical - each code is assigned a level. See Code System for further information.
Source | The source of the definition of the code (when the value set draws in codes defined elsewhere)
Code | The code (used as the code in the resource instance). If the code is in italics, this indicates that the code is not selectable ('Abstract')
Display | The display (used in the display element of a Coding). If there is no display, implementers should not simply display the code, but map the concept into their application
Definition | An explanation of the meaning of the concept
Comments | Additional notes about how to use the code

4.3.14.3 Code System http://terminology.hl7.org/CodeSystem/object-role

URL: https://hl7.org/fhir/R4/codesystem-object-role.html
Security Work Group | Maturity Level: 3 | Trial Use | Use Context: Any

This is a code system defined by the FHIR project.

Summary

Defining URL: | http://terminology.hl7.org/CodeSystem/object-role
Version: | 4.0.1
Name: | AuditEventEntityRole
Title: | AuditEventEntityRole
Definition: | Code representing the role the entity played in the audit event.
Committee: | Security Work Group

OID: | 2.16.840.1.113883.4.642.4.1135 (for OID based terminology systems)
Source Resource | XML / JSON

This Code system is used in the following value sets:

• ValueSet: AuditEventEntityRole (Code representing the role the entity played in the audit event.)

• ValueSet: AuditEventEntityRole (Code representing the role the entity played in the audit event.)

4.3.14.3.1 Content

4.3.14.3.2 AuditEventEntityRole

Code representing the role the entity played in the audit event.

This code system http://terminology.hl7.org/CodeSystem/object-role defines the following codes:

Code | Display | Definition
1 | Patient | This object is the patient that is the subject of care related to this event. It is identifiable by patient ID or equivalent. The patient may be either human or animal.
2 | Location | This is a location identified as related to the event. This is usually the location where the event took place. Note that for shipping, the usual events are arrival at a location or departure from a location.
3 | Report | This object is any kind of persistent document created as a result of the event. This could be a paper report, film, electronic report, DICOM Study, etc. Issues related to medical records life cycle management are conveyed elsewhere.
4 | Domain Resource | A logical object related to a health record event. This is any healthcare specific resource (object) not restricted to FHIR defined Resources.
5 | Master file | This is any configurable file used to control creation of documents. Examples include the objects maintained by the HL7 Master File transactions, Value Sets, etc.
6 | User | A human participant not otherwise identified by some other category.
7 | List | (deprecated).
8 | Doctor | Typically, a licensed person who is providing or performing care related to the event, generally a physician. The key distinction between doctor and practitioner is with regards to their role, not the licensing. The doctor is the human who actually performed the work. The practitioner is the human or organization that is responsible for the work.
9 | Subscriber | A person or system that is being notified as part of the event. This is relevant in situations where automated systems provide notifications to other parties when an event took place.
10 | Guarantor | Insurance company, or any other organization who accepts responsibility for paying for the healthcare event.
11 | Security User Entity | A person or active system object involved in the event with a security role.
12 | Security User Group | A person or system object involved in the event with the authority to modify security roles of other objects.
13 | Security Resource | A passive object, such as a role table, that is relevant to the event.
14 | Security Granularity Definition | (deprecated) Relevant to certain RBAC security methodologies.
15 | Practitioner | Any person or organization responsible for providing care. This encompasses all forms of care, licensed or otherwise, and all sorts of teams and care groups. Note the distinction between practitioner and the doctor that actually provided the care to the patient.
16 | Data Destination | The source or destination for data transfer, when it does not match some other role.
17 | Data Repository | A source or destination for data transfer that acts as an archive, database, or similar role.
18 | Schedule | An object that holds schedule information. This could be an appointment book, availability information, etc.
19 | Customer | An organization or person that is the recipient of services. This could be an organization that is buying services for a patient, or a person that is buying services for an animal.
20 | Job | An order, task, work item, procedure step, or other description of work to be performed; e.g. a particular instance of an MPPS.
21 | Job Stream | A list of jobs or a system that provides lists of jobs; e.g. an MWL SCP.
22 | Table | (Deprecated).
23 | Routing Criteria | An object that specifies or controls the routing or delivery of items. For example, a distribution list is the routing criteria for mail. The items delivered may be documents, jobs, or other objects.
24 | Query | The contents of a query. This is used to capture the contents of any kind of query. For security surveillance purposes knowing the queries being made is very important.

See the full registry of code systems defined as part of FHIR.

Explanation of the columns that may appear on this page:

Level | A few code lists that FHIR defines are hierarchical - each code is assigned a level. See Code System for further information.
Source | The source of the definition of the code (when the value set draws in codes defined elsewhere)
Code | The code (used as the code in the resource instance). If the code is in italics, this indicates that the code is not selectable ('Abstract')
Display | The display (used in the display element of a Coding). If there is no display, implementers should not simply display the code, but map the concept into their application
Definition | An explanation of the meaning of the concept
Comments | Additional notes about how to use the code

4.3.14.4 Code System http://hl7.org/fhir/contract-definition-type

URL: https://hl7.org/fhir/R4/codesystem-contract-definition-type.html
Financial Management Work Group | Maturity Level: 1 | Draft | Use Context: Any

This is a code system defined by the FHIR project.

Summary

Defining URL: | http://hl7.org/fhir/contract-definition-type
Version: | 4.0.1
Name: | ContractResourceDefinitionTypeCodes
Title: | Contract Resource Definition Type codes
Definition: | This value set contract specific codes for status.
Committee: | Financial Management Work Group
OID: | 2.16.840.1.113883.4.642.4.1211 (for OID based terminology systems)
Copyright: | HL7 International.
Source Resource | XML / JSON

This Code system is used in the following value sets:

• ValueSet: Contract Resource Definition Type codes (This value set contract specific codes for status.)

• ValueSet: Contract Resource Definition Type codes (This value set contract specific codes for status.)

4.3.14.4.1 Content

Each definition includes usage notes explaining the precedence order in contract lifecycle - i.e., while only some stages are required, the order in which they may occur is deterministic; and a map to comparable FHIR and v.3 status codes. It follows guidance about use of status codes in FHIR at http://build.fhir.org/sc.html.

4.3.14.4.2 Contract Resource Definition Type codes

This value set contract specific codes for status.

Copyright Statement:

HL7 International.

This code system http://hl7.org/fhir/contract-definition-type defines the following codes:

Code | Display | Definition
temp | Temporary Value | To be completed

See the full registry of code systems defined as part of FHIR.

Explanation of the columns that may appear on this page:

Level | A few code lists that FHIR defines are hierarchical - each code is assigned a level. See Code System for further information.
Source | The source of the definition of the code (when the value set draws in codes defined elsewhere)
Code | The code (used as the code in the resource instance). If the code is in italics, this indicates that the code is not selectable ('Abstract')
Display | The display (used in the display element of a Coding). If there is no display, implementers should not simply display the code, but map the concept into their application
Definition | An explanation of the meaning of the concept
Comments | Additional notes about how to use the code

4.3.14.5 Code System http://terminology.hl7.org/CodeSystem/coverage-selfpay

URL: https://hl7.org/fhir/R4/codesystem-coverage-selfpay.html
Vocabulary Work Group | Maturity Level: 0 | Informative | Use Context: Any

This is a code system defined by the FHIR project.

Summary

Defining URL: | http://terminology.hl7.org/CodeSystem/coverage-selfpay
Version: | 4.0.1
Name: | CoverageSelfPayCodes
Title: | Coverage SelfPay Codes
Definition: | This value set includes Coverage SelfPay codes.
Committee: | ??
OID: | 2.16.840.1.113883.4.642.4.1148 (for OID based terminology systems)
Copyright: | HL7 International.
Source Resource | XML / JSON

This Code system is used in the following value sets:

• ValueSet: Coverage SelfPay Codes (This value set includes Coverage SelfPay codes.)

• ValueSet: Coverage Type and Self-Pay Codes (This value set includes Coverage Type codes.)

• ValueSet: Coverage Type and Self-Pay Codes (This value set includes Coverage Type codes.)

• ValueSet: Coverage SelfPay Codes (This value set includes Coverage SelfPay codes.)

4.3.14.5.1 Content

4.3.14.5.2 Coverage SelfPay Codes

This value set includes Coverage SelfPay codes.

Copyright Statement:

HL7 International.

This code system http://terminology.hl7.org/CodeSystem/coverage-selfpay defines the following codes:

Code | Display | Definition
pay | Pay | An individual or organization is paying directly for goods and services.

See the full registry of code systems defined as part of FHIR.

Explanation of the columns that may appear on this page:

Level | A few code lists that FHIR defines are hierarchical - each code is assigned a level. See Code System for further information.
Source | The source of the definition of the code (when the value set draws in codes defined elsewhere)
Code | The code (used as the code in the resource instance). If the code is in italics, this indicates that the code is not selectable ('Abstract')
Display | The display (used in the display element of a Coding). If there is no display, implementers should not simply display the code, but map the concept into their application
Definition | An explanation of the meaning of the concept
Comments | Additional notes about how to use the code

4.3.14.6 Code System http://terminology.hl7.org/CodeSystem/match-grade

URL: https://hl7.org/fhir/R4/codesystem-match-grade.html
Vocabulary Work Group | Maturity Level: 0 | Informative | Use Context: Any

This is a code system defined by the FHIR project.

Summary

Defining URL: | http://terminology.hl7.org/CodeSystem/match-grade
Version: | 4.0.1
Name: | MatchGrade
Title: | MatchGrade
Definition: | A Master Patient Index (MPI) assessment of whether a candidate patient record is a match or not.
Committee: | ??
OID: | 2.16.840.1.113883.4.642.4.1289 (for OID based terminology systems)
Source Resource | XML / JSON

This Code system is used in the following value sets:

• ValueSet: MatchGrade (A Master Patient Index (MPI) assessment of whether a candidate patient record is a match or not.)

• ValueSet: MatchGrade (A Master Patient Index (MPI) assessment of whether a candidate patient record is a match or not.)

4.3.14.6.1 Content

4.3.14.6.2 MatchGrade

A Master Patient Index (MPI) assessment of whether a candidate patient record is a match or not.

This code system http://terminology.hl7.org/CodeSystem/match-grade defines the following codes:

Code | Display | Definition
certain | Certain Match | This record meets the matching criteria to be automatically considered as a full match.
probable | Probable Match | This record is a close match, but not a certain match. Additional review (e.g. by a human) may be required before using this as a match.
possible | Possible Match | This record may be a matching one. Additional review (e.g. by a human) SHOULD be performed before using this as a match.
certainly-not | Certainly Not a Match | This record is known not to be a match. Note that usually non-matching records are not returned, but in some cases records previously or likely considered as a match may specifically be negated by the matching engine.

See the full registry of code systems defined as part of FHIR.

Explanation of the columns that may appear on this page:

Level | A few code lists that FHIR defines are hierarchical - each code is assigned a level. See Code System for further information.
Source | The source of the definition of the code (when the value set draws in codes defined elsewhere)
Code | The code (used as the code in the resource instance). If the code is in italics, this indicates that the code is not selectable ('Abstract')
Display | The display (used in the display element of a Coding). If there is no display, implementers should not simply display the code, but map the concept into their application
Definition | An explanation of the meaning of the concept
Comments | Additional notes about how to use the code

4.3.14.7 Code System http://terminology.hl7.org/CodeSystem/financialtaskcode

URL: https://hl7.org/fhir/R4/codesystem-financial-taskcode.html
Vocabulary Work Group | Maturity Level: 0 | Informative | Use Context: Any

This is a code system defined by the FHIR project.

Summary

Defining URL: | http://terminology.hl7.org/CodeSystem/financialtaskcode
Version: | 4.0.1
Name: | FinancialTaskCodes
Title: | Financial Task Codes
Definition: | This value set includes Financial Task codes.
Committee: | ??
OID: | 2.16.840.1.113883.4.642.4.1390 (for OID based terminology systems)
Copyright: | This is an example set.
Source Resource | XML / JSON

This Code system is used in the following value sets:

• ValueSet: Financial Task Codes (This value set includes Financial Task codes.)

• ValueSet: Financial Task Codes (This value set includes Financial Task codes.)

4.3.14.7.1 Content

4.3.14.7.2 Financial Task Codes

This value set includes Financial Task codes.

Copyright Statement:

This is an example set.

This code system http://terminology.hl7.org/CodeSystem/financialtaskcode defines the following codes:

Code | Display | Definition
cancel | Cancel | Cancel or reverse a resource, such as a claim or preauthorization, which is in-process or complete.
poll | Poll | Retrieve selected or all queued resources or messages.
release | Release | Release any reserved funds or material obligations associated with a resource. For example, any unused but reserved funds or treatment allowance associated with a preauthorization once treatment is complete.
reprocess | Reprocess | Indication that the processing of a resource, such as a claim, for some or all of the required work is now being requested.
status | Status check | Check on the processing status of a resource such as the adjudication of a claim.

See the full registry of code systems defined as part of FHIR.

Explanation of the columns that may appear on this page:

Level | A few code lists that FHIR defines are hierarchical - each code is assigned a level. See Code System for further information.
Source | The source of the definition of the code (when the value set draws in codes defined elsewhere)
Code | The code (used as the code in the resource instance). If the code is in italics, this indicates that the code is not selectable ('Abstract')
Display | The display (used in the display element of a Coding). If there is no display, implementers should not simply display the code, but map the concept into their application
Definition | An explanation of the meaning of the concept
Comments | Additional notes about how to use the code

4.3.14.8 Code System http://hl7.org/fhir/repository-type

URL: https://hl7.org/fhir/R4/codesystem-repository-type.html
Clinical Genomics Work Group | Maturity Level: 1 | Trial Use | Use Context: Any

This is a code system defined by the FHIR project.

Summary

Defining URL: | http://hl7.org/fhir/repository-type
Version: | 4.0.1
Name: | repositoryType
Title: | repositoryType
Definition: | Type for access of external URI.
Committee: | Clinical Genomics Work Group
OID: | 2.16.840.1.113883.4.642.4.231 (for OID based terminology systems)
Source Resource | XML / JSON

This Code system is used in the following value sets:

• ValueSet: repositoryType (Type for access of external URI.)

• ValueSet: repositoryType (Type for access of external URI.)

4.3.14.8.1 Content

4.3.14.8.2 repositoryType

Type for access of external URI.

This code system http://hl7.org/fhir/repository-type defines the following codes:

Code | Display | Definition
directlink | Click and see | When URL is clicked, the resource can be seen directly (by webpage or by download link format).
openapi | The URL is the RESTful or other kind of API that can access to the result. | When the API method (e.g. [base_url]/[parameter]) related with the URL of the website is executed, the resource can be seen directly (usually in JSON or XML format).
login | Result cannot be access unless an account is logged in | When logged into the website, the resource can be seen.
oauth | Result need to be fetched with API and need LOGIN(or cookies are required when visiting the link of resource) | When logged in and follow the API in the website related with URL, the resource can be seen.
other | Some other complicated or particular way to get resource from URL. | Some other complicated or particular way to get resource from URL.

See the full registry of code systems defined as part of FHIR.

Explanation of the columns that may appear on this page:

Level | A few code lists that FHIR defines are hierarchical - each code is assigned a level. See Code System for further information.
Source | The source of the definition of the code (when the value set draws in codes defined elsewhere)
Code | The code (used as the code in the resource instance). If the code is in italics, this indicates that the code is not selectable ('Abstract')
Display | The display (used in the display element of a Coding). If there is no display, implementers should not simply display the code, but map the concept into their application
Definition | An explanation of the meaning of the concept
Comments | Additional notes about how to use the code

4.3.14.9 Code System http://terminology.hl7.org/CodeSystem/substance-category

URL: https://hl7.org/fhir/R4/codesystem-substance-category.html
Orders and Observations Work Group | Maturity Level: 2 | Trial Use | Use Context: Any

This is a code system defined at http://www.hl7.org/Special/committees/orders/index.cfm .

Summary

Defining URL: | http://terminology.hl7.org/CodeSystem/substance-category
Version: | 4.0.1
Name: | SubstanceCategoryCodes
Title: | Substance Category Codes
Definition: | Substance category codes
Committee: | Orders and Observations Work Group
OID: | 2.16.840.1.113883.4.642.4.1138 (for OID based terminology systems)
Source Resource | XML / JSON

This Code system is used in the following value sets:

• ValueSet: Substance Category Codes (Substance category codes)

• ValueSet: Substance Category Codes (Substance category codes)

4.3.14.9.1 Content

4.3.14.9.2 Substance Category Codes

Substance category codes

This code system http://terminology.hl7.org/CodeSystem/substance-category defines the following codes:

Code | Display | Definition
allergen | Allergen | A substance that causes an allergic reaction.
biological | Biological Substance | A substance that is produced by or extracted from a biological source.
body | Body Substance | A substance that comes directly from a human or an animal (e.g. blood, urine, feces, tears, etc.).
chemical | Chemical | Any organic or inorganic substance of a particular molecular identity, including -- (i) any combination of such substances occurring in whole or in part as a result of a chemical reaction or occurring in nature and (ii) any element or uncombined radical (http://www.epa.gov/opptintr/import-export/pubs/importguide.pdf).
food | Dietary Substance | A food, dietary ingredient, or dietary supplement for human or animal.
drug | Drug or Medicament | A substance intended for use in the diagnosis, cure, mitigation, treatment, or prevention of disease in man or other animals (Federal Food Drug and Cosmetic Act).
material | Material | A finished product which is not normally ingested, absorbed or injected (e.g. steel, iron, wood, plastic and paper).

See the full registry of code systems defined as part of FHIR.

Explanation of the columns that may appear on this page:

Level | A few code lists that FHIR defines are hierarchical - each code is assigned a level. See Code System for further information.

Source | The source of the definition of the code (when the value set draws in codes defined elsewhere)
Code | The code (used as the code in the resource instance). If the code is in italics, this indicates that the code is not selectable ('Abstract')
Display | The display (used in the display element of a Coding). If there is no display, implementers should not simply display the code, but map the concept into their application
Definition | An explanation of the meaning of the concept
Comments | Additional notes about how to use the code

4.3.14.10 Code System http://terminology.hl7.org/CodeSystem/ex-visionprescriptionproduct

URL: https://hl7.org/fhir/R4/codesystem-vision-product.html
Financial Management Work Group | Maturity Level: 1 | Draft | Use Context: Any

This is a code system defined by the FHIR project.

Summary

Defining URL: | http://terminology.hl7.org/CodeSystem/ex-visionprescriptionproduct
Version: | 4.0.1
Name: | ExampleVisionPrescriptionProductCodes
Title: | Example Vision Prescription Product Codes
Definition: | This value set includes a smattering of Prescription Product codes.
Committee: | Financial Management Work Group
OID: | 2.16.840.1.113883.4.642.4.1188 (for OID based terminology systems)
Copyright: | This is an example set.
Source Resource | XML / JSON

This Code system is used in the following value sets:

• ValueSet: Example Vision Prescription Product Codes (This value set includes a smattering of Prescription Product codes.)

• ValueSet: Example Vision Prescription Product Codes (This value set includes a smattering of Prescription Product codes.)

4.3.14.10.1 Content

4.3.14.10.2 Example Vision Prescription Product Codes

This value set includes a smattering of Prescription Product codes.

Copyright Statement:

This is an example set.

This code system http://terminology.hl7.org/CodeSystem/ex-visionprescriptionproduct defines the following codes:

Code | Display | Definition
lens | Lens | A lens to be fitted to a frame to comprise a pair of glasses.
contact | Contact Lens | A lens to be fitted for wearing directly on an eye.

See the full registry of code systems defined as part of FHIR.

Explanation of the columns that may appear on this page:

Level | A few code lists that FHIR defines are hierarchical - each code is assigned a level. See Code System for further information.
Source | The source of the definition of the code (when the value set draws in codes defined elsewhere)
Code | The code (used as the code in the resource instance). If the code is in italics, this indicates that the code is not selectable ('Abstract')
Display | The display (used in the display element of a Coding). If there is no display, implementers should not simply display the code, but map the concept into their application
Definition | An explanation of the meaning of the concept
Comments | Additional notes about how to use the code

4.3.14.11 Code System http://terminology.hl7.org/CodeSystem/adverse-event-causality-assess

URL: https://hl7.org/fhir/R4/codesystem-adverse-event-causality-assess.html
Patient Care Work Group | Maturity Level: 1 | Draft | Use Context: Any

This is a code system defined by the FHIR project.

Summary

Defining URL: | http://terminology.hl7.org/CodeSystem/adverse-event-causality-assess
Version: | 4.0.1
Name: | AdverseEventCausalityAssessment
Title: | AdverseEventCausalityAssessment
Definition: | Codes for the assessment of whether the entity caused the event.

Committee: | Patient Care Work Group
OID: | 2.16.840.1.113883.4.642.4.1254 (for OID based terminology systems)
Source Resource | XML / JSON

This Code system is used in the following value sets:

• ValueSet: AdverseEventCausalityAssessment (Codes for the assessment of whether the entity caused the event.)

• ValueSet: AdverseEventCausalityAssessment (Codes for the assessment of whether the entity caused the event.)

4.3.14.11.1 Content

4.3.14.11.2 AdverseEventCausalityAssessment

Codes for the assessment of whether the entity caused the event.

This code system http://terminology.hl7.org/CodeSystem/adverse-event-causality-assess defines the following codes:

Code | Display | Definition
Certain | Certain | i) Event or laboratory test abnormality, with plausible time relationship to drug intake; ii) Cannot be explained by disease or other drugs; iii) Response to withdrawal plausible (pharmacologically, pathologically); iv) Event definitive pharmacologically or phenomenologically (i.e. an objective and specific medical disorder or a recognized pharmacological phenomenon); or v) Re-challenge satisfactory, if necessary.
Probably-Likely | Probably/Likely | i) Event or laboratory test abnormality, with reasonable time relationship to drug intake; ii) Unlikely to be attributed to disease or other drugs; iii) Response to withdrawal clinically reasonable; or iv) Re-challenge not required.
Possible | Possible | i) Event or laboratory test abnormality, with reasonable time relationship to drug intake; ii) Could also be explained by disease or other drugs; or iii) Information on drug withdrawal may be lacking or unclear.
Unlikely | Unlikely | i) Event or laboratory test abnormality, with a time to drug intake that makes a relationship improbable (but not impossible); or ii) Disease or other drugs provide plausible explanations.
Conditional-Classified | Conditional/Classified | i) Event or laboratory test abnormality; ii) More data for proper assessment needed; or iii) Additional data under examination.
Unassessable-Unclassifiable | Unassessable/Unclassifiable | i) Report suggesting an adverse reaction; ii) Cannot be judged because information is insufficient or contradictory; or iii) Data cannot be supplemented or verified.

See the full registry of code systems defined as part of FHIR.

Explanation of the columns that may appear on this page:

Level | A few code lists that FHIR defines are hierarchical - each code is assigned a level. See Code System for further information.
Source | The source of the definition of the code (when the value set draws in codes defined elsewhere)
Code | The code (used as the code in the resource instance). If the code is in italics, this indicates that the code is not selectable ('Abstract')
Display | The display (used in the display element of a Coding). If there is no display, implementers should not simply display the code, but map the concept into their application
Definition | An explanation of the meaning of the concept
Comments | Additional notes about how to use the code

4.3.14.12 Code System http://terminology.hl7.org/CodeSystem/risk-estimate-type

URL: https://hl7.org/fhir/R4/codesystem-risk-estimate-type.html
Clinical Decision Support Work Group | Maturity Level: 0 | Trial Use | Use Context: Any

This is a code system defined by the FHIR project.

Summary

Defining URL: | http://terminology.hl7.org/CodeSystem/risk-estimate-type
Version: | 4.0.1
Name: | RiskEstimateType
Title: | RiskEstimateType
Definition: | Whether the risk estimate is dichotomous, continuous or qualitative and the specific type of risk estimate (eg proportion or median).
Committee: | Clinical Decision Support Work Group
OID: | 2.16.840.1.113883.4.642.4.1364 (for OID based terminology systems)
Source Resource | XML / JSON

This Code system is used in the following value sets:

• ValueSet: RiskEstimateType (Whether the risk estimate is dichotomous, continuous or qualitative and the specific type of risk estimate (eg proportion or median).)

• ValueSet: RiskEstimateType (Whether the risk estimate is dichotomous, continuous or qualitative and the specific type of risk estimate (eg proportion or median).)

4.3.14.12.1 Content

4.3.14.12.2 RiskEstimateType

Whether the risk estimate is dichotomous, continuous or qualitative and the specific type of risk estimate (eg proportion or median).

This code system http://terminology.hl7.org/CodeSystem/risk-estimate-type defines the following codes:

Code | Display | Definition
proportion | proportion | dichotomous measure (present or absent) reported as a ratio compared to the denominator of 1 (A percentage is a proportion with denominator of 100).
derivedProportion | derivedProportion | A special use case where the proportion is derived from a formula rather than derived from summary evidence.
mean | mean | continuous numerical measure reported as an average.
median | median | continuous numerical measure reported as the middle of the range.
count | count | descriptive measure reported as total number of items.
descriptive | descriptive | descriptive measure reported as narrative.

See the full registry of code systems defined as part of FHIR.

Explanation of the columns that may appear on this page:

Level | A few code lists that FHIR defines are hierarchical - each code is assigned a level. See Code System for further information.
Source | The source of the definition of the code (when the value set draws in codes defined elsewhere)
Code | The code (used as the code in the resource instance). If the code is in italics, this indicates that the code is not selectable ('Abstract')
Display | The display (used in the display element of a Coding). If there is no display, implementers should not simply display the code, but map the concept into their application
Definition | An explanation of the meaning of the concept
Comments | Additional notes about how to use the code

4.3.14.13 Code System http://terminology.hl7.org/CodeSystem/need

URL: https://hl7.org/fhir/R4/codesystem-verificationresult-need.html
Patient Administration Work Group | Maturity Level: 0 | Informative | Use Context: Any

This is a code system defined by the FHIR project.

Summary

Defining URL: | http://terminology.hl7.org/CodeSystem/need
Version: | 4.0.1
Name: | need
Title: | Need
Definition: | The frequency with which the target must be validated
Committee: | Patient Administration Work Group
OID: | 2.16.840.1.113883.4.642.1.883 (for OID based terminology systems)
Source Resource | XML / JSON

This Code system is used in the following value sets:

• ValueSet: Need (The frequency with which the target must be validated)

• ValueSet: Need (The frequency with which the target must be validated)

4.3.14.13.1 Content

4.3.14.13.2 Need

The frequency with which the target must be validated

This code system http://terminology.hl7.org/CodeSystem/need defines the following codes:

Code | Display | Definition
none | None | ***TODO***
initial | Initial | ***TODO***
periodic | Periodic | ***TODO***

See the full registry of code systems defined as part of FHIR.

Explanation of the columns that may appear on this page:

Level | A few code lists that FHIR defines are hierarchical - each code is assigned a level. See Code System for further information.
Source | The source of the definition of the code (when the value set draws in codes defined elsewhere)
Code | The code (used as the code in the resource instance). If the code is in italics, this indicates that the code is not selectable ('Abstract')
Display | The display (used in the display element of a Coding). If there is no display, implementers should not simply display the code, but map the concept into their application
Definition | An explanation of the meaning of the concept
Comments | Additional notes about how to use the code

4.3.14.14 Code System http://terminology.hl7.org/CodeSystem/medicationknowledge-package-type

URL: https://hl7.org/fhir/R4/codesystem-medicationknowledge-package-type.html
Pharmacy Work Group | Maturity Level: 1 | Draft | Use Context: Any

This is a code system defined by the FHIR project.

Summary

Defining URL: | http://terminology.hl7.org/CodeSystem/medicationknowledge-package-type
Version: | 4.0.1
Name: | medicationKnowledge Package Type Codes
Title: | Medication knowledge package type codes
Definition: | MedicationKnowledge Package Type Codes
Committee: | Pharmacy Work Group
OID: | 2.16.840.1.113883.4.642.4.1340 (for OID based terminology systems)
Source Resource | XML / JSON

This Code system is used in the following value sets:

• ValueSet: Medication knowledge package type codes (MedicationKnowledge Package Type Codes)
• ValueSet: Medication knowledge package type codes (MedicationKnowledge Package Type Codes)

4.3.14.14.1 Content

4.3.14.14.2 Medication knowledge package type codes

MedicationKnowledge Package Type Codes

This code system http://terminology.hl7.org/CodeSystem/medicationknowledge-package-type defines the following codes:

Code | Display | Definition
amp | Ampule
bag | Bag
blstrpk | Blister Pack
bot | Bottle
box | Box
can | Can
cart | Cartridge
disk | Disk
doset | Dosette
jar | Jar
jug | Jug
minim | Minim
nebamp | Nebule Amp
ovul | Ovule
pch | Pouch
pkt | Packet
sash | Sashet
strip | Strip
tin | Tin
tub | Tub
tube | Tube
vial | Vial

See the full registry of code systems defined as part of FHIR.

Explanation of the columns that may appear on this page:

Level | A few code lists that FHIR defines are hierarchical - each code is assigned a level. See Code System for further information.
Source | The source of the definition of the code (when the value set draws in codes defined elsewhere)
Code | The code (used as the code in the resource instance). If the code is in italics, this indicates that the code is not selectable ('Abstract')
Display | The display (used in the display element of a Coding). If there is no display, implementers should not simply display the code, but map the concept into their application
Definition | An explanation of the meaning of the concept
Comments | Additional notes about how to use the code

4.3.14.15 Code System http://terminology.hl7.org/CodeSystem/insurance-plan-type

URL: https://hl7.org/fhir/R4/codesystem-insuranceplan-type.html
Patient Administration Work Group | Maturity Level: 1 | Draft | Use Context: Any

This is a code system defined by the FHIR project.

Summary

Defining URL: | http://terminology.hl7.org/CodeSystem/insurance-plan-type
Version: | 4.0.1
Name: | InsurancePlanType
Title: | Insurance plan type
Definition: | This example value set defines a set of codes that can be used to indicate a type of insurance plan.
Committee: | Patient Administration Work Group
OID: | 2.16.840.1.113883.4.642.4.1261 (for OID based terminology systems)
Source Resource | XML / JSON

This Code system is used in the following value sets:

• ValueSet: Insurance plan type (This example value set defines a set of codes that can be used to indicate a type of insurance plan.)

• ValueSet: Insurance plan type (This example value set defines a set of codes that can be used to indicate a type of insurance plan.)

4.3.14.15.1 Content

4.3.14.15.2 Insurance plan type

This example value set defines a set of codes that can be used to indicate a type of insurance plan.

This code system http://terminology.hl7.org/CodeSystem/insurance-plan-type defines many codes, of which the following are a subset:

Code | Display | Definition
medical | Medical
dental | Dental
mental | Mental Health
subst-ab | Substance Abuse
vision | Vision
Drug | Drug
short-term | Short Term
long-term | Long Term Care
hospice | Hospice
home | Home Health

See the full registry of code systems defined as part of FHIR.

Explanation of the columns that may appear on this page:

Level | A few code lists that FHIR defines are hierarchical - each code is assigned a level. See Code System for further information.
Source | The source of the definition of the code (when the value set draws in codes defined elsewhere)
Code | The code (used as the code in the resource instance). If the code is in italics, this indicates that the code is not selectable ('Abstract')
Display | The display (used in the display element of a Coding). If there is no display, implementers should not simply display the code, but map the concept into their application
Definition | An explanation of the meaning of the concept
Comments | Additional notes about how to use the code

4.3.14.16 Code System http://hl7.org/fhir/questionnaire-enable-operator

URL: https://hl7.org/fhir/R4/codesystem-questionnaire-enable-operator.html
FHIR Infrastructure Work Group | Maturity Level: 3 | Trial Use | Use Context: Any

This is a code system defined by the FHIR project.

Summary

Defining URL: | http://hl7.org/fhir/questionnaire-enable-operator
Version: | 4.0.1
Name: | QuestionnaireItemOperator
Title: | QuestionnaireItemOperator
Definition: | The criteria by which a question is enabled.
Committee: | FHIR Infrastructure Work Group
OID: | 2.16.840.1.113883.4.642.4.1006 (for OID based terminology systems)
Source Resource | XML / JSON

This Code system is used in the following value sets:

• ValueSet: QuestionnaireItemOperator (The criteria by which a question is enabled.)

• ValueSet: QuestionnaireItemOperator (The criteria by which a question is enabled.)

4.3.14.16.1 Content

4.3.14.16.2 QuestionnaireItemOperator

The criteria by which a question is enabled.

This code system http://hl7.org/fhir/questionnaire-enable-operator defines the following codes:

Code	Display	Definition
exists	Exists	True if whether an answer exists is equal to the enableWhen answer (which must be a boolean).
=	Equals	True if whether at least one answer has a value that is equal to the enableWhen answer.
!=	Not Equals	True if whether at least no answer has a value that is equal to the enableWhen answer.
>	Greater Than	True if whether at least no answer has a value that is greater than the enableWhen answer.
<	Less Than	True if whether at least no answer has a value that is less than the enableWhen answer.
>=	Greater or Equals	True if whether at least no answer has a value that is greater or equal to the enableWhen answer.
<=	Less or Equals	True if whether at least no answer has a value that is less or equal to the enableWhen answer.

See the full registry of code systems defined as part of FHIR.

Explanation of the columns that may appear on this page:

Level	A few code lists that FHIR defines are hierarchical - each code is assigned a level. See Code System for further information.
Source	The source of the definition of the code (when the value set draws in codes defined elsewhere)
Code	The code (used as the code in the resource instance). If the code is in italics, this indicates that the code is not selectable ('Abstract')
Display	The display (used in the display element of a Coding). If there is no display, implementers should not simply display the code, but map the concept into their application
Definition	An explanation of the meaning of the concept
Comments	Additional notes about how to use the code

4.3.14.17 Code System http://terminology.hl7.org/CodeSystem/can-push-updates

URL: https://hl7.org/fhir/R4/codesystem-verificationresult-can-push-updates.html
Patient Administration Work Group | Maturity Level: 0 | Informative | Use Context: Any

This is a code system defined by the FHIR project.

Summary

Defining URL:	http://terminology.hl7.org/CodeSystem/can-push-updates
Version:	4.0.1
Name:	can-push-updates
Title:	Can-push-updates
Definition:	Ability of the primary source to push updates/alerts
Committee:	Patient Administration Work Group
OID:	2.16.840.1.113883.4.642.1.897 (for OID based terminology systems)
Source Resource	XML / JSON

This Code system is used in the following value sets:

• ValueSet: Can-push-updates (Ability of the primary source to push updates/alerts)

• ValueSet: Can-push-updates (Ability of the primary source to push updates/alerts)

4.3.14.17.1 Content

4.3.14.17.2 Can-push-updates

Ability of the primary source to push updates/alerts

This code system http://terminology.hl7.org/CodeSystem/can-push-updates defines the following codes:

Code	Display	Definition
yes	Yes	
no	No	
undetermined	Undetermined	

See the full registry of code systems defined as part of FHIR.

Explanation of the columns that may appear on this page:

Level	A few code lists that FHIR defines are hierarchical - each code is assigned a level. See Code System for further information.
Source	The source of the definition of the code (when the value set draws in codes defined elsewhere)
Code	The code (used as the code in the resource instance). If the code is in italics, this indicates that the code is not selectable ('Abstract')
Display	The display (used in the display element of a Coding). If there is no display, implementers should not simply display the code, but map the concept into their application
Definition	An explanation of the meaning of the concept
Comments	Additional notes about how to use the code

4.3.14.18 Code System http://terminology.hl7.org/CodeSystem/composition-altcode-kind

URL: https://hl7.org/fhir/R4/codesystem-composition-altcode-kind.html

Vocabulary Work Group | Maturity Level: 0 | Informative | Use Context: Any

This is a code system defined by the FHIR project.

Summary

Defining URL: | http://terminology.hl7.org/CodeSystem/composition-altcode-kind
Version: | 4.0.1
Name: | AlternativeCodeKind
Title: | AlternativeCodeKind
Definition: | Indicates the type of use for which the code is defined.
Committee: | ??
OID: | 2.16.840.1.113883.4.642.4.1406 (for OID based terminology systems)
Source Resource | XML / JSON

This Code system is used in the following value sets:

• ValueSet: AlternativeCodeKind (Indicates the type of use for which the code is defined.)

• ValueSet: AlternativeCodeKind (Indicates the type of use for which the code is defined.)

4.3.14.18.1 Content

4.3.14.18.2 AlternativeCodeKind

Indicates the type of use for which the code is defined.

This code system http://terminology.hl7.org/CodeSystem/composition-altcode-kind defines the following codes:

Code | Display | Definition
alternate | Alternate Code | The code is an alternative code that can be used in any of the circumstances that the primary code can be used.
deprecated | Deprecated | The code should no longer be used, but was used in the past.
case-insensitive | Case Insensitive | The code is an alternative to be used when a case insensitive code is required (when the primary codes are case sensitive).
case-sensitive | Case Sensitive | The code is an alternative to be used when a case sensitive code is required (when the primary codes are case insensitive).
expression | Expression | The code is an alternative for the primary code that is built using the expression grammar defined by the code system.

See the full registry of code systems defined as part of FHIR.

Explanation of the columns that may appear on this page:

Level | A few code lists that FHIR defines are hierarchical - each code is assigned a level. See Code System for further information.
Source | The source of the definition of the code (when the value set draws in codes defined elsewhere)
Code | The code (used as the code in the resource instance). If the code is in italics, this indicates that the code is not selectable ('Abstract')
Display | The display (used in the display element of a Coding). If there is no display, implementers should not simply display the code, but map the concept into their application
Definition | An explanation of the meaning of the concept
Comments | Additional notes about how to use the code

4.3.14.19 Code System http://hl7.org/fhir/FHIR-version

URL: https://hl7.org/fhir/R4/codesystem-FHIR-version.html
Vocabulary Work Group | Maturity Level: N | Normative (from v4.0.0) | Use Context: Any

| This page has been approved as part of an ANSI standard. See the Conformance Package for further details.

This is a code system defined by the FHIR project.

Summary

Defining URL: | http://hl7.org/fhir/FHIR-version
Version: | 4.0.1
Name: | FHIRVersion
Title: | FHIRVersion
Definition: | All published FHIR Versions.
Committee: | Vocabulary Work Group
OID: | 2.16.840.1.113883.4.642.4.1310 (for OID based terminology systems)
Source Resource | XML / JSON

This Code system is used in the following value sets:

• ValueSet: FHIRVersion (All published FHIR Versions.)

• ValueSet: FHIRVersion (All published FHIR Versions.)

4.3.14.19.1 Content

4.3.14.19.2 FHIRVersion

All published FHIR Versions.

This code system http://hl7.org/fhir/FHIR-version defines the following codes:

Code | Display | Definition
0.01 | 0.01 | Oldest archived version of FHIR.
0.05 | 0.05 | 1st Draft for Comment (Sept 2012 Ballot).
0.06 | 0.06 | 2nd Draft for Comment (January 2013 Ballot).
0.11 | 0.11 | DSTU 1 Ballot version.
0.0.80 | 0.0.80 | DSTU 1 Official version.
0.0.81 | 0.0.81 | DSTU 1 Official version Technical Errata #1.
0.0.82 | 0.0.82 | DSTU 1 Official version Technical Errata #2.
0.4.0 | 0.4.0 | Draft For Comment (January 2015 Ballot).
0.5.0 | 0.5.0 | DSTU 2 Ballot version (May 2015 Ballot).
1.0.0 | 1.0.0 | DSTU 2 QA Preview + CQIF Ballot (Sep 2015).
1.0.1 | 1.0.1 | DSTU 2 (Official version).
1.0.2 | 1.0.2 | DSTU 2 (Official version) with 1 technical errata.
1.1.0 | 1.1.0 | GAO Ballot + draft changes to main FHIR standard.
1.4.0 | 1.4.0 | CQF on FHIR Ballot + Connectathon 12 (Montreal).
1.6.0 | 1.6.0 | FHIR STU3 Ballot + Connectathon 13 (Baltimore).
1.8.0 | 1.8.0 | FHIR STU3 Candidate + Connectathon 14 (San Antonio).
3.0.0 | 3.0.0 | FHIR Release 3 (STU).
3.0.1 | 3.0.1 | FHIR Release 3 (STU) with 1 technical errata.
3.3.0 | 3.3.0 | R4 Ballot #1.
3.5.0 | 3.5.0 | R4 Ballot #2.
4.0.0 | 4.0.0 | FHIR Release 4 (Normative + STU).
4.0.1 | 4.0.1 | FHIR Release 4 Technical Correction.

See the full registry of code systems defined as part of FHIR.

Explanation of the columns that may appear on this page:

Level | A few code lists that FHIR defines are hierarchical - each code is assigned a level. See Code System for further information.
Source | The source of the definition of the code (when the value set draws in codes defined elsewhere)
Code | The code (used as the code in the resource instance). If the code is in italics, this indicates that the code is not selectable ('Abstract')
Display | The display (used in the display element of a Coding). If there is no display, implementers should not simply display the code, but map the concept into their application
Definition | An explanation of the meaning of the concept
Comments | Additional notes about how to use the code

4.3.14.20 Code System http://terminology.hl7.org/CodeSystem/verificationresult-communication-method

URL: https://hl7.org/fhir/R4/codesystem-verificationresult-communication-method.html
Patient Administration Work Group | Maturity Level: 1 | Draft | Use Context: Any

This is a code system defined by the FHIR project.

Summary

Defining URL: | http://terminology.hl7.org/CodeSystem/verificationresult-communication-method
Version: | 4.0.1
Name: | verificationresult-communication-method
Title: | VerificationResult Communication Method
Definition: | Attested information may be validated by process that are manual or automated. For automated processes it may accomplished by the system of record reaching out through another system's API or information may be sent to the system of record. This value set defines a set of codes to describing the process, the how, a resource or data element is validated.
Committee: | Patient Administration Work Group
OID: | 2.16.840.1.113883.4.642.4.1402 (for OID based terminology systems)
Source Resource | XML / JSON

This Code system is used in the following value sets:

• ValueSet: VerificationResult Communication Method (Attested information may be validated by process that are manual or automated. For automated processes it may accomplished by the system of record reaching out through another system's API or information may be sent to the system of record. This value set defines a set of codes to describing the process, the how, a resource or data element is validated.)

• ValueSet: VerificationResult Communication Method (Attested information may be validated by process that are manual or automated. For automated processes it may accomplished by the system of record reaching out through another system's API or information may be sent to the system of record. This value set defines a set of codes to describing the process, the how, a resource or data element is validated.)

4.3.14.20.1 Content

4.3.14.20.2 VerificationResult Communication Method

Attested information may be validated by process that are manual or automated. For automated processes it may accomplished by the system of record reaching out through another system's API or information may be sent to the system of record. This value set defines a set of codes to describing the process, the how, a resource or data element is validated.

This code system http://terminology.hl7.org/CodeSystem/verificationresult-communication-method defines the following codes:

Code | Display | Definition
manual | Manual | The information is submitted/retrieved manually (e.g. by phone, fax, paper-based)
portal | Portal | The information is submitted/retrieved via a portal
pull | Pull | The information is retrieved (i.e. pulled) from a source (e.g. over an API)
push | Push | The information is sent (i.e. pushed) from a source (e.g. over an API, asynchronously, secure messaging)

See the full registry of code systems defined as part of FHIR.

Explanation of the columns that may appear on this page:

Level | A few code lists that FHIR defines are hierarchical - each code is assigned a level. See Code System for further information.
Source | The source of the definition of the code (when the value set draws in codes defined elsewhere)
Code | The code (used as the code in the resource instance). If the code is in italics, this indicates that the code is not selectable ('Abstract')
Display | The display (used in the display element of a Coding). If there is no display, implementers should not simply display the code, but map the concept into their application
Definition | An explanation of the meaning of the concept
Comments | Additional notes about how to use the code

4.3.14.21 Code System http://terminology.hl7.org/CodeSystem/reaction-event-certainty

URL: https://hl7.org/fhir/R4/codesystem-reaction-event-certainty.html
Vocabulary Work Group | Maturity Level: 0 | Informative | Use Context: Any

This is a code system defined by the FHIR project.

Summary

Defining URL: | http://terminology.hl7.org/CodeSystem/reaction-event-certainty
Version: | 4.0.1
Name: | AllergyIntoleranceCertainty
Title: | AllergyIntoleranceCertainty
Definition: | Statement about the degree of clinical certainty that a specific substance was the cause of the manifestation in a reaction event.
Committee: | ??
OID: | 2.16.840.1.113883.4.642.4.1276 (for OID based terminology systems)
Source Resource | XML / JSON

This Code system is used in the following value sets:

• ValueSet: AllergyIntoleranceCertainty (Statement about the degree of clinical certainty that a specific substance was the cause of the manifestation in a reaction event.)

• ValueSet: AllergyIntoleranceCertainty (Statement about the degree of clinical certainty that a specific substance was the cause of the manifestation in a reaction event.)

4.3.14.21.1 Content

4.3.14.21.2 AllergyIntoleranceCertainty

Statement about the degree of clinical certainty that a specific substance was the cause of the manifestation in a reaction event.

This code system http://terminology.hl7.org/CodeSystem/reaction-event-certainty defines the following codes:

Code | Display | Definition
unlikely | Unlikely | There is a low level of clinical certainty that the reaction was caused by the identified substance.
likely | Likely | There is a high level of clinical certainty that the reaction was caused by the identified substance.
confirmed | Confirmed | There is a very high level of clinical certainty that the reaction was due to the identified substance, which may include clinical evidence by testing or rechallenge.
unknown | Unknown | The clinical certainty that the reaction was caused by the identified substance is unknown. It is an explicit assertion that certainty is not known.

See the full registry of code systems defined as part of FHIR.

Explanation of the columns that may appear on this page:

Level | A few code lists that FHIR defines are hierarchical - each code is assigned a level. See Code System for further information.
Source | The source of the definition of the code (when the value set draws in codes defined elsewhere)
Code | The code (used as the code in the resource instance). If the code is in italics, this indicates that the code is not selectable ('Abstract')
Display | The display (used in the display element of a Coding). If there is no display, implementers should not simply display the code, but map the concept into their application

Definition | An explanation of the meaning of the concept
Comments | Additional notes about how to use the code

4.3.14.22 Code System http://hl7.org/fhir/action-selection-behavior

URL: https://hl7.org/fhir/R4/codesystem-action-selection-behavior.html
Clinical Decision Support Work Group | Maturity Level: 2 | Trial Use | Use Context: Any

This is a code system defined by the FHIR project.

Summary

Defining URL: | http://hl7.org/fhir/action-selection-behavior
Version: | 4.0.1
Name: | ActionSelectionBehavior
Title: | ActionSelectionBehavior
Definition: | Defines selection behavior of a group.
Committee: | Clinical Decision Support Work Group
OID: | 2.16.840.1.113883.4.642.4.802 (for OID based terminology systems)
Source Resource | XML / JSON

This Code system is used in the following value sets:

• ValueSet: ActionSelectionBehavior (Defines selection behavior of a group.)

• ValueSet: ActionSelectionBehavior (Defines selection behavior of a group.)

4.3.14.22.1 Content

4.3.14.22.2 ActionSelectionBehavior

Defines selection behavior of a group.

This code system http://hl7.org/fhir/action-selection-behavior defines the following codes:

Code | Display | Definition
any | Any | Any number of the actions in the group may be chosen, from zero to all.
all | All | All the actions in the group must be selected as a single unit.
all-or-none | All Or None | All the actions in the group are meant to be chosen as a single unit: either all must be selected by the end user, or none may be selected.
exactly-one | Exactly One | The end user must choose one and only one of the selectable actions in the group. The user SHALL NOT choose none of the actions in the group.
at-most-one | At Most One | The end user may choose zero or at most one of the actions in the group.
one-or-more | One Or More | The end user must choose a minimum of one, and as many additional as desired.

See the full registry of code systems defined as part of FHIR.

Explanation of the columns that may appear on this page:

Level | A few code lists that FHIR defines are hierarchical - each code is assigned a level. See Code System for further information.
Source | The source of the definition of the code (when the value set draws in codes defined elsewhere)
Code | The code (used as the code in the resource instance). If the code is in italics, this indicates that the code is not selectable ('Abstract')
Display | The display (used in the display element of a Coding). If there is no display, implementers should not simply display the code, but map the concept into their application
Definition | An explanation of the meaning of the concept
Comments | Additional notes about how to use the code

4.3.14.23 Code System http://hl7.org/fhir/history-status

URL: https://hl7.org/fhir/R4/codesystem-history-status.html
Patient Care Work Group | Maturity Level: 2 | Trial Use | Use Context: Any

This is a code system defined by the FHIR project.

Summary

Defining URL: | http://hl7.org/fhir/history-status
Version: | 4.0.1
Name: | FamilyHistoryStatus
Title: | FamilyHistoryStatus
Definition: | A code that identifies the status of the family history record.
Committee: | Patient Care Work Group
OID: | 2.16.840.1.113883.4.642.4.268 (for OID based terminology systems)
Source Resource | XML / JSON

This Code system is used in the following value sets:

• ValueSet: FamilyHistoryStatus (A code that identifies the status of the family history record.)

• ValueSet: FamilyHistoryStatus (A code that identifies the status of the family history record.)

4.3.14.23.1 Content

4.3.14.23.2 FamilyHistoryStatus

A code that identifies the status of the family history record.

This code system http://hl7.org/fhir/history-status defines the following codes:

Code | Display | Definition
partial | Partial | Some health information is known and captured, but not complete - see notes for details.
completed | Completed | All available related health information is captured as of the date (and possibly time) when the family member history was taken.
entered-in-error | Entered in Error | This instance should not have been part of this patient's medical record.
health-unknown | Health Unknown | Health information for this family member is unavailable/unknown.

See the full registry of code systems defined as part of FHIR.

Explanation of the columns that may appear on this page:

Level | A few code lists that FHIR defines are hierarchical - each code is assigned a level. See Code System for further information.
Source | The source of the definition of the code (when the value set draws in codes defined elsewhere)
Code | The code (used as the code in the resource instance). If the code is in italics, this indicates that the code is not selectable ('Abstract')
Display | The display (used in the display element of a Coding). If there is no display, implementers should not simply display the code, but map the concept into their application
Definition | An explanation of the meaning of the concept
Comments | Additional notes about how to use the code

4.3.14.24 Code System http://terminology.hl7.org/CodeSystem/failure-action

URL: https://hl7.org/fhir/R4/codesystem-verificationresult-failure-action.html
Patient Administration Work Group | Maturity Level: 0 | Informative | Use Context: Any

This is a code system defined by the FHIR project.

Summary

Defining URL: | http://terminology.hl7.org/CodeSystem/failure-action
Version: | 4.0.1
Name: | failure-action
Title: | Failure-action
Definition: | The result if validation fails
Committee: | Patient Administration Work Group
OID: | 2.16.840.1.113883.4.642.1.891 (for OID based terminology systems)
Source Resource | XML / JSON

This Code system is used in the following value sets:

• ValueSet: Failure-action (The result if validation fails)

• ValueSet: Failure-action (The result if validation fails)

4.3.14.24.1 Content

4.3.14.24.2 Failure-action

The result if validation fails

This code system http://terminology.hl7.org/CodeSystem/failure-action defines the following codes:

Code | Display | Definition
fatal | Fatal
warn | Warning
rec-only | Record only
none | None

See the full registry of code systems defined as part of FHIR.

Explanation of the columns that may appear on this page:

Level | A few code lists that FHIR defines are hierarchical - each code is assigned a level. See Code System for further information.
Source | The source of the definition of the code (when the value set draws in codes defined elsewhere)
Code | The code (used as the code in the resource instance). If the code is in italics, this indicates that the code is not selectable ('Abstract')
Display | The display (used in the display element of a Coding). If there is no display, implementers should not simply display the code, but map the concept into their application
Definition | An explanation of the meaning of the concept
Comments | Additional notes about how to use the code

4.3.14.25 Code System http://hl7.org/fhir/vision-eye-codes

URL: https://hl7.org/fhir/R4/codesystem-vision-eye-codes.html
Financial Management Work Group | Maturity Level: 2 | Trial Use | Use Context: Any

This is a code system defined by the FHIR project.

Summary

Defining URL: | http://hl7.org/fhir/vision-eye-codes
Version: | 4.0.1
Name: | VisionEyes
Title: | VisionEyes
Definition: | A coded concept listing the eye codes.
Committee: | Financial Management Work Group
OID: | 2.16.840.1.113883.4.642.4.661 (for OID based terminology systems)
Source Resource | XML / JSON

This Code system is used in the following value sets:

• ValueSet: VisionEyes (A coded concept listing the eye codes.)

• ValueSet: VisionEyes (A coded concept listing the eye codes.)

4.3.14.25.1 Content

4.3.14.25.2 VisionEyes

A coded concept listing the eye codes.

This code system http://hl7.org/fhir/vision-eye-codes defines the following codes:

Code | Display | Definition
right | Right Eye | Right Eye.
left | Left Eye | Left Eye.

See the full registry of code systems defined as part of FHIR.

Explanation of the columns that may appear on this page:

Level | A few code lists that FHIR defines are hierarchical - each code is assigned a level. See Code System for further information.
Source | The source of the definition of the code (when the value set draws in codes defined elsewhere)
Code | The code (used as the code in the resource instance). If the code is in italics, this indicates that the code is not selectable ('Abstract')
Display | The display (used in the display element of a Coding). If there is no display, implementers should not simply display the code, but map the concept into their application
Definition | An explanation of the meaning of the concept
Comments | Additional notes about how to use the code

4.3.14.26 Code System http://hl7.org/fhir/contract-definition-subtype

URL: https://hl7.org/fhir/R4/codesystem-contract-definition-subtype.html
Financial Management Work Group | Maturity Level: 1 | Draft | Use Context: Any

This is a code system defined by the FHIR project.

Summary

Defining URL: | http://hl7.org/fhir/contract-definition-subtype
Version: | 4.0.1
Name: | ContractResourceDefinitionSubtypeCodes
Title: | Contract Resource Definition Subtype codes
Definition: | This value set contract specific codes for status.
Committee: | Financial Management Work Group
OID: | 2.16.840.1.113883.4.642.4.1213 (for OID based terminology systems)
Copyright: | HL7 International.
Source Resource | XML / JSON

This Code system is used in the following value sets:

• ValueSet: Contract Resource Definition Subtype codes (This value set contract specific codes for status.)

• ValueSet: Contract Resource Definition Subtype codes (This value set contract specific codes for status.)

4.3.14.26.1 Content

Each definition includes usage notes explaining the precedence order in contract lifecycle - i.e., while only some stages are required, the order in which they may occur is deterministic; and a map to comparable FHIR and v.3 status codes. It follows guidance about use of status codes in FHIR at http://build.fhir.org/sc.html.

4.3.14.26.2 Contract Resource Definition Subtype codes

This value set contract specific codes for status.

Copyright Statement:

HL7 International.

This code system http://hl7.org/fhir/contract-definition-subtype defines the following codes:

Code | Display | Definition
temp | Temporary Value | To be completed

See the full registry of code systems defined as part of FHIR.

Explanation of the columns that may appear on this page:

Level | A few code lists that FHIR defines are hierarchical - each code is assigned a level. See Code System for further information.
Source | The source of the definition of the code (when the value set draws in codes defined elsewhere)
Code | The code (used as the code in the resource instance). If the code is in italics, this indicates that the code is not selectable ('Abstract')
Display | The display (used in the display element of a Coding). If there is no display, implementers should not simply display the code, but map the concept into their application
Definition | An explanation of the meaning of the concept
Comments | Additional notes about how to use the code

4.3.14.27 Code System http://hl7.org/fhir/care-team-status

URL: https://hl7.org/fhir/R4/codesystem-care-team-status.html
Patient Care Work Group | Maturity Level: 2 | Trial Use | Use Context: Any

This is a code system defined by the FHIR project.

Summary

Defining URL: | http://hl7.org/fhir/care-team-status
Version: | 4.0.1
Name: | CareTeamStatus
Title: | CareTeamStatus
Definition: | Indicates the status of the care team.
Committee: | Patient Care Work Group
OID: | 2.16.840.1.113883.4.642.4.154 (for OID based terminology systems)
Source Resource | XML / JSON

This Code system is used in the following value sets:

• ValueSet: CareTeamStatus (Indicates the status of the care team.)

• ValueSet: CareTeamStatus (Indicates the status of the care team.)

4.3.14.27.1 Content

4.3.14.27.2 CareTeamStatus

Indicates the status of the care team.

This code system http://hl7.org/fhir/care-team-status defines the following codes:

Code | Display | Definition
proposed | Proposed | The care team has been drafted and proposed, but not yet participating in the coordination and delivery of patient care.
active | Active | The care team is currently participating in the coordination and delivery of care.
suspended | Suspended | The care team is temporarily on hold or suspended and not participating in the coordination and delivery of care.
inactive | Inactive | The care team was, but is no longer, participating in the coordination and delivery of care.
entered-in-error | Entered in Error | The care team should have never existed.

See the full registry of code systems defined as part of FHIR.

Explanation of the columns that may appear on this page:

Level | A few code lists that FHIR defines are hierarchical - each code is assigned a level. See Code System for further information.
Source | The source of the definition of the code (when the value set draws in codes defined elsewhere)
Code | The code (used as the code in the resource instance). If the code is in italics, this indicates that the code is not selectable ('Abstract')
Display | The display (used in the display element of a Coding). If there is no display, implementers should not simply display the code, but map the concept into their application
Definition | An explanation of the meaning of the concept
Comments | Additional notes about how to use the code

4.3.14.28 Code System http://hl7.org/fhir/invoice-priceComponentType

URL: https://hl7.org/fhir/R4/codesystem-invoice-priceComponentType.html
Patient Administration Work Group | Maturity Level: 0 | Trial Use | Use Context: Any

This is a code system defined by the FHIR project.

Summary

Defining URL: | http://hl7.org/fhir/invoice-priceComponentType
Version: | 4.0.1
Name: | InvoicePriceComponentType
Title: | InvoicePriceComponentType
Definition: | Codes indicating the kind of the price component.
Committee: | Patient Administration Work Group
OID: | 2.16.840.1.113883.4.642.4.869 (for OID based terminology systems)
Source Resource | XML / JSON

This Code system is used in the following value sets:

• ValueSet: InvoicePriceComponentType (Codes indicating the kind of the price component.)

• ValueSet: InvoicePriceComponentType (Codes indicating the kind of the price component.)

4.3.14.28.1 Content

4.3.14.28.2 InvoicePriceComponentType

Codes indicating the kind of the price component.

This code system http://hl7.org/fhir/invoice-priceComponentType defines the following codes:

Code | Display | Definition
base | base price | the amount is the base price used for calculating the total price before applying surcharges, discount or taxes.
surcharge | surcharge | the amount is a surcharge applied on the base price.
deduction | deduction | the amount is a deduction applied on the base price.
discount | discount | the amount is a discount applied on the base price.
tax | tax | the amount is the tax component of the total price.
informational | informational | the amount is of informational character, it has not been applied in the calculation of the total price.

See the full registry of code systems defined as part of FHIR.

Explanation of the columns that may appear on this page:

Level | A few code lists that FHIR defines are hierarchical - each code is assigned a level. See Code System for further information.
Source | The source of the definition of the code (when the value set draws in codes defined elsewhere)
Code | The code (used as the code in the resource instance). If the code is in italics, this indicates that the code is not selectable ('Abstract')
Display | The display (used in the display element of a Coding). If there is no display, implementers should not simply display the code, but map the concept into their application
Definition | An explanation of the meaning of the concept
Comments | Additional notes about how to use the code

4.3.14.29 Code System http://terminology.hl7.org/CodeSystem/contractaction

URL: https://hl7.org/fhir/R4/codesystem-contract-action.html
Financial Management Work Group | Maturity Level: 1 | Draft | Use Context: Any

This is a code system defined by the FHIR project.

Summary

Defining URL: | http://terminology.hl7.org/CodeSystem/contractaction
Version: | 4.0.1
Name: | ContractActionCodes
Title: | Contract Action Codes
Definition: | This value set includes sample Contract Action codes.
Committee: | Financial Management Work Group
OID: | 2.16.840.1.113883.4.642.4.1202 (for OID based terminology systems)
Copyright: | This is an example set.
Source Resource | XML / JSON

This Code system is used in the following value sets:

• ValueSet: Contract Action Codes (This value set includes sample Contract Action codes.)

• ValueSet: Contract Action Codes (This value set includes sample Contract Action codes.)

4.3.14.29.1 Content

4.3.14.29.2 Contract Action Codes

This value set includes sample Contract Action codes.

Copyright Statement:

This is an example set.

This code system http://terminology.hl7.org/CodeSystem/contractaction defines the following codes:

Code | Display | Definition

action-a | Action A | Definition for Action A
action-b | Action B | Definition for Action B

See the full registry of code systems defined as part of FHIR.

Explanation of the columns that may appear on this page:

Level | A few code lists that FHIR defines are hierarchical - each code is assigned a level. See Code System for further information.
Source | The source of the definition of the code (when the value set draws in codes defined elsewhere)
Code | The code (used as the code in the resource instance). If the code is in italics, this indicates that the code is not selectable ('Abstract')
Display | The display (used in the display element of a Coding). If there is no display, implementers should not simply display the code, but map the concept into their application
Definition | An explanation of the meaning of the concept
Comments | Additional notes about how to use the code

4.3.14.30 Code System http://hl7.org/fhir/CodeSystem/medication-statement-status

URL: https://hl7.org/fhir/R4/codesystem-medication-statement-status.html
Pharmacy Work Group | Maturity Level: 3 | Trial Use | Use Context: Any

This is a code system defined by the FHIR project.

Summary

Defining URL: | http://hl7.org/fhir/CodeSystem/medication-statement-status
Version: | 4.0.1
Name: | Medication Status Codes
Title: | Medication status codes
Definition: | Medication Status Codes
Committee: | Pharmacy Work Group
OID: | 2.16.840.1.113883.4.642.4.1379 (for OID based terminology systems)
Source Resource | XML / JSON

This Code system is used in the following value sets:

• ValueSet: Medication status codes (Medication Status Codes)

• ValueSet: Medication status codes (Medication Status Codes)

4.3.14.30.1 Content

4.3.14.30.2 Medication status codes

Medication Status Codes

This code system http://hl7.org/fhir/CodeSystem/medication-statement-status defines the following codes:

Code | Display | Definition
active | Active | The medication is still being taken.
completed | Completed | The medication is no longer being taken.
entered-in-error | Entered in Error | Some of the actions that are implied by the medication statement may have occurred. For example, the patient may have taken some of the medication. Clinical decision support systems should take this status into account.
intended | Intended | The medication may be taken at some time in the future.
stopped | Stopped | Actions implied by the statement have been permanently halted, before all of them occurred. This should not be used if the statement was entered in error.
on-hold | On Hold | Actions implied by the statement have been temporarily halted, but are expected to continue later. May also be called 'suspended'.
unknown | Unknown | The state of the medication use is not currently known.
not-taken | Not Taken | The medication was not consumed by the patient

See the full registry of code systems defined as part of FHIR.

Explanation of the columns that may appear on this page:

Level | A few code lists that FHIR defines are hierarchical - each code is assigned a level. See Code System for further information.
Source | The source of the definition of the code (when the value set draws in codes defined elsewhere)
Code | The code (used as the code in the resource instance). If the code is in italics, this indicates that the code is not selectable ('Abstract')
Display | The display (used in the display element of a Coding). If there is no display, implementers should not simply display the code, but map the concept into their application
Definition | An explanation of the meaning of the concept
Comments | Additional notes about how to use the code

4.3.14.31 Code System http://terminology.hl7.org/CodeSystem/evidence-quality

URL: https://hl7.org/fhir/R4/codesystem-evidence-quality.html

Clinical Decision Support Work Group | Maturity Level: 0 | Trial Use | Use Context: Any

This is a code system defined by the FHIR project.

Summary

Defining URL: | http://terminology.hl7.org/CodeSystem/evidence-quality
Version: | 4.0.1
Name: | QualityOfEvidenceRating
Title: | QualityOfEvidenceRating
Definition: | A rating system that describes the quality of evidence such as the GRADE, DynaMed, or Oxford CEBM systems.
Committee: | Clinical Decision Support Work Group
OID: | 2.16.840.1.113883.4.642.4.1267 (for OID based terminology systems)
Source Resource | XML / JSON

This Code system is used in the following value sets:

• ValueSet: QualityOfEvidenceRating (A rating system that describes the quality of evidence such as the GRADE, DynaMed, or Oxford CEBM systems.)

• ValueSet: QualityOfEvidenceRating (A rating system that describes the quality of evidence such as the GRADE, DynaMed, or Oxford CEBM systems.)

4.3.14.31.1 Content

4.3.14.31.2 QualityOfEvidenceRating

A rating system that describes the quality of evidence such as the GRADE, DynaMed, or Oxford CEBM systems.

This code system http://terminology.hl7.org/CodeSystem/evidence-quality defines the following codes:

Code | Display | Definition
high | High quality | High quality evidence.
moderate | Moderate quality | Moderate quality evidence.
low | Low quality | Low quality evidence.
very-low | Very low quality | Very low quality evidence.

See the full registry of code systems defined as part of FHIR.

Explanation of the columns that may appear on this page:

Level | A few code lists that FHIR defines are hierarchical - each code is assigned a level. See Code System for further information.
Source | The source of the definition of the code (when the value set draws in codes defined elsewhere)
Code | The code (used as the code in the resource instance). If the code is in italics, this indicates that the code is not selectable ('Abstract')
Display | The display (used in the display element of a Coding). If there is no display, implementers should not simply display the code, but map the concept into their application
Definition | An explanation of the meaning of the concept
Comments | Additional notes about how to use the code

4.3.14.32 Code System http://hl7.org/fhir/specimen-status

URL: https://hl7.org/fhir/R4/codesystem-specimen-status.html
Orders and Observations Work Group | Maturity Level: 2 | Trial Use | Use Context: Any

This is a code system defined by the FHIR project.

Summary

Defining URL: | http://hl7.org/fhir/specimen-status
Version: | 4.0.1
Name: | SpecimenStatus
Title: | SpecimenStatus
Definition: | Codes providing the status/availability of a specimen.
Committee: | Orders and Observations Work Group
OID: | 2.16.840.1.113883.4.642.4.472 (for OID based terminology systems)
Source Resource | XML / JSON

This Code system is used in the following value sets:

• ValueSet: SpecimenStatus (Codes providing the status/availability of a specimen.)

• ValueSet: SpecimenStatus (Codes providing the status/availability of a specimen.)

4.3.14.32.1 Content

4.3.14.32.2 SpecimenStatus

Codes providing the status/availability of a specimen.

This code system http://hl7.org/fhir/specimen-status defines the following codes:

Code | Display | Definition
available | Available | The physical specimen is present and in good condition.

unavailable | Unavailable | There is no physical specimen because it is either lost, destroyed or consumed.
unsatisfactory | Unsatisfactory | The specimen cannot be used because of a quality issue such as a broken container, contamination, or too old.
entered-in-error | Entered in Error | The specimen was entered in error and therefore nullified.

See the full registry of code systems defined as part of FHIR.

Explanation of the columns that may appear on this page:

Level | A few code lists that FHIR defines are hierarchical - each code is assigned a level. See Code System for further information.
Source | The source of the definition of the code (when the value set draws in codes defined elsewhere)
Code | The code (used as the code in the resource instance). If the code is in italics, this indicates that the code is not selectable ('Abstract')
Display | The display (used in the display element of a Coding). If there is no display, implementers should not simply display the code, but map the concept into their application
Definition | An explanation of the meaning of the concept
Comments | Additional notes about how to use the code

4.3.14.33 Code System http://hl7.org/fhir/contract-publicationstatus

URL: https://hl7.org/fhir/R4/codesystem-contract-publicationstatus.html
Financial Management Work Group | Maturity Level: 1 | Trial Use | Use Context: Any

This is a code system defined by the FHIR project.

Summary

Defining URL: | http://hl7.org/fhir/contract-publicationstatus
Version: | 4.0.1
Name: | ContractResourcePublicationStatusCodes
Title: | Contract Resource Publication Status codes
Definition: | This value set contract specific codes for status.
Committee: | Financial Management Work Group
OID: | 2.16.840.1.113883.4.642.4.1209 (for OID based terminology systems)
Copyright: | HL7 International.
Source Resource | XML / JSON

This Code system is used in the following value sets:

• ValueSet: Contract Resource Publication Status codes (This value set contract specific codes for status.)

• ValueSet: Contract Resource Publication Status codes (This value set contract specific codes for status.)

4.3.14.33.1 Content

Each definition includes usage notes explaining the precedence order in contract lifecycle - i.e., while only some stages are required, the order in which they may occur is deterministic; and a map to comparable FHIR and v.3 status codes. It follows guidance about use of status codes in FHIR at http://build.fhir.org/sc.html.

4.3.14.33.2 Contract Resource Publication Status codes

This value set contract specific codes for status.

Copyright Statement:

HL7 International.

This code system http://hl7.org/fhir/contract-publicationstatus defines the following codes:

Code | Display | Definition
amended | Amended | Contract is augmented with additional information to correct errors in a predecessor or to updated values in a predecessor. Usage: Contract altered within effective time. Precedence Order = 9. Comparable FHIR and v.3 status codes: revised; replaced.
appended | Appended | Contract is augmented with additional information that was missing from a predecessor Contract. Usage: Contract altered within effective time. Precedence Order = 9. Comparable FHIR and v.3 status codes: updated, replaced.
cancelled | Cancelled | Contract is terminated due to failure of the Grantor and/or the Grantee to fulfil one or more contract provisions. Usage: Abnormal contract termination. Precedence Order = 10. Comparable FHIR and v.3 status codes: stopped; failed; aborted.
disputed | Disputed | Contract is pended to rectify failure of the Grantor or the Grantee to fulfil contract provision(s). E.g., Grantee complaint about Grantor's failure to comply with contract provisions. Usage: Contract pended. Precedence Order = 7. Comparable FHIR and v.3 status codes: on hold; pended; suspended.
entered-in-error | Entered in Error | Contract was created in error. No Precedence Order. Status may be applied to a Contract with any status.
executable | Executable | Contract execution pending; may be executed when either the Grantor or the Grantee accepts the contract provisions by signing. I.e., where either the Grantor or the Grantee has signed, but not both. E.g., when an insurance applicant signs the insurers application, which references the policy. Usage: Optional first step of contract execution activity. May be skipped and contracting activity moves directly to executed state. Precedence Order = 3. Comparable FHIR and v.3 status codes: draft; preliminary; planned; intended; active.
executed | Executed | Contract is activated for period stipulated when both the Grantor and Grantee have signed it. Usage: Required state for normal completion of contracting activity. Precedence Order = 6. Comparable FHIR and v.3 status codes: accepted; completed.

negotiable | Negotiable | Contract execution is suspended while either or both the Grantor and Grantee propose and consider new or revised contract provisions. I.e., where the party which has not signed proposes changes to the terms. E .g., a life insurer declines to agree to the signed application because the life insurer has evidence that the applicant, who asserted to being younger or a non-smoker to get a lower premium rate - but offers instead to agree to a higher premium based on the applicants actual age or smoking status. Usage: Optional contract activity between executable and executed state. Precedence Order = 4. Comparable FHIR and v.3 status codes: in progress; review; held.

offered | Offered | Contract is a proposal by either the Grantor or the Grantee. Aka - A Contract hard copy or electronic 'template', 'form' or 'application'. E.g., health insurance application; consent directive form. Usage: Beginning of contract negotiation, which may have been completed as a precondition because used for 0..* contracts. Precedence Order = 2. Comparable FHIR and v.3 status codes: requested; new.

policy | Policy | Contract template is available as the basis for an application or offer by the Grantor or Grantee. E.g., health insurance policy; consent directive policy. Usage: Required initial contract activity, which may have been completed as a precondition because used for 0..* contracts. Precedence Order = 1. Comparable FHIR and v.3 status codes: proposed; intended.

rejected | Rejected | Execution of the Contract is not completed because either or both the Grantor and Grantee decline to accept some or all of the contract provisions. Usage: Optional contract activity between executable and abnormal termination. Precedence Order = 5. Comparable FHIR and v.3 status codes: stopped; cancelled.

renewed | Renewed | Beginning of a successor Contract at the termination of predecessor Contract lifecycle. Usage: Follows termination of a preceding Contract that has reached its expiry date. Precedence Order = 13. Comparable FHIR and v.3 status codes: superseded.

revoked | Revoked | A Contract that is rescinded. May be required prior to replacing with an updated Contract. Comparable FHIR and v.3 status codes: nullified.

resolved | Resolved | Contract is reactivated after being pended because of faulty execution. *E.g., competency of the signer(s), or where the policy is substantially different from and did not accompany the application/form so that the applicant could not compare them. Aka - ''reactivated''. Usage: Optional stage where a pended contract is reactivated. Precedence Order = 8. Comparable FHIR and v.3 status codes: reactivated.

terminated | Terminated | Contract reaches its expiry date. It might or might not be renewed or renegotiated. Usage: Normal end of contract period. Precedence Order = 12. Comparable FHIR and v.3 status codes: Obsoleted.

See the full registry of code systems defined as part of FHIR.

Explanation of the columns that may appear on this page:

Level | A few code lists that FHIR defines are hierarchical - each code is assigned a level. See Code System for further information.

Source | The source of the definition of the code (when the value set draws in codes defined elsewhere)

Code | The code (used as the code in the resource instance). If the code is in italics, this indicates that the code is not selectable ('Abstract')

Display | The display (used in the display element of a Coding). If there is no display, implementers should not simply display the code, but map the concept into their application

Definition | An explanation of the meaning of the concept

Comments | Additional notes about how to use the code

4.3.14.34 Code System http://hl7.org/fhir/reference-version-rules

URL: https://hl7.org/fhir/R4/codesystem-reference-version-rules.html

FHIR Infrastructure Work Group | Maturity Level: N | Normative (from v4.0.0) | Use Context: Any

This is a code system defined by the FHIR project.

Summary

Defining URL: | http://hl7.org/fhir/reference-version-rules

Version: | 4.0.1

Name: | ReferenceVersionRules

Title: | ReferenceVersionRules

Definition: | Whether a reference needs to be version specific or version independent, or whether either can be used.

Committee: | FHIR Infrastructure Work Group

OID: | 2.16.840.1.113883.4.642.4.90 (for OID based terminology systems)

Source Resource | XML / JSON

This Code system is used in the following value sets:

• ValueSet: ReferenceVersionRules (Whether a reference needs to be version specific or version independent, or whether either can be used.)

• ValueSet: ReferenceVersionRules (Whether a reference needs to be version specific or version independent, or whether either can be used.)

4.3.14.34.1 Content

4.3.14.34.2 ReferenceVersionRules

Whether a reference needs to be version specific or version independent, or whether either can be used.

This code system http://hl7.org/fhir/reference-version-rules defines the following codes:

Code | Display | Definition

either | Either Specific or independent | The reference may be either version independent or version specific.

independent | Version independent | The reference must be version independent.

specific | Version Specific | The reference must be version specific.

See the full registry of code systems defined as part of FHIR.

Explanation of the columns that may appear on this page:

Level | A few code lists that FHIR defines are hierarchical - each code is assigned a level. See Code System for further information.
Source | The source of the definition of the code (when the value set draws in codes defined elsewhere)
Code | The code (used as the code in the resource instance). If the code is in italics, this indicates that the code is not selectable ('Abstract')
Display | The display (used in the display element of a Coding). If there is no display, implementers should not simply display the code, but map the concept into their application
Definition | An explanation of the meaning of the concept
Comments | Additional notes about how to use the code

4.3.14.35 Code System http://hl7.org/fhir/map-context-type

URL: https://hl7.org/fhir/R4/codesystem-map-context-type.html
FHIR Infrastructure Work Group | Maturity Level: 2 | Trial Use | Use Context: Any

This is a code system defined by the FHIR project.

Summary

Defining URL: | http://hl7.org/fhir/map-context-type
Version: | 4.0.1
Name: | StructureMapContextType
Title: | StructureMapContextType
Definition: | How to interpret the context.
Committee: | FHIR Infrastructure Work Group
OID: | 2.16.840.1.113883.4.642.4.680 (for OID based terminology systems)
Source Resource | XML / JSON

This Code system is used in the following value sets:

• ValueSet: StructureMapContextType (How to interpret the context.)
• ValueSet: StructureMapContextType (How to interpret the context.)

4.3.14.35.1 Content

4.3.14.35.2 StructureMapContextType

How to interpret the context.

This code system http://hl7.org/fhir/map-context-type defines the following codes:

Code | Display | Definition
type | Type | The context specifies a type.
variable | Variable | The context specifies a variable.

See the full registry of code systems defined as part of FHIR.

Explanation of the columns that may appear on this page:

Level | A few code lists that FHIR defines are hierarchical - each code is assigned a level. See Code System for further information.
Source | The source of the definition of the code (when the value set draws in codes defined elsewhere)
Code | The code (used as the code in the resource instance). If the code is in italics, this indicates that the code is not selectable ('Abstract')
Display | The display (used in the display element of a Coding). If there is no display, implementers should not simply display the code, but map the concept into their application
Definition | An explanation of the meaning of the concept
Comments | Additional notes about how to use the code

4.3.14.36 Code System http://hl7.org/fhir/concept-subsumption-outcome

URL: https://hl7.org/fhir/R4/codesystem-concept-subsumption-outcome.html
Vocabulary Work Group | Maturity Level: 0 | Informative | Use Context: Any

This is a code system defined by the FHIR project.

Summary

Defining URL: | http://hl7.org/fhir/concept-subsumption-outcome
Version: | 4.0.1
Name: | ConceptSubsumptionOutcome
Title: | ConceptSubsumptionOutcome
Definition: | The subsumption relationship between code/Coding "A" and code/Coding "B". There are 4 possible codes to be returned: equivalent, subsumes, subsumed-by, and not-subsumed. If the server is unable to determine the relationship between the codes/Codings, then it returns an error (i.e. an OperationOutcome).
Committee: | ??
OID: | 2.16.840.1.113883.4.642.4.1239 (for OID based terminology systems)
Source Resource | XML / JSON

This Code system is used in the following value sets:

• ValueSet: ConceptSubsumptionOutcome (The subsumption relationship between code/Coding "A" and code/Coding "B". There are 4 possible codes to be returned: equivalent, subsumes, subsumed-by, and not-subsumed. If the server is unable to determine the relationship between the codes/Codings, then it returns an error (i.e. an OperationOutcome).)

• ValueSet: ConceptSubsumptionOutcome (The subsumption relationship between code/Coding "A" and code/Coding "B". There are 4 possible codes to be returned: equivalent, subsumes, subsumed-by, and not-subsumed. If the server is unable to determine the relationship between the codes/Codings, then it returns an error (i.e. an OperationOutcome).)

4.3.14.36.1 Content

4.3.14.36.2 ConceptSubsumptionOutcome

The subsumption relationship between code/Coding "A" and code/Coding "B". There are 4 possible codes to be returned: equivalent, subsumes, subsumed-by, and not-subsumed. If the server is unable to determine the relationship between the codes/Codings, then it returns an error (i.e. an OperationOutcome).

This code system http://hl7.org/fhir/concept-subsumption-outcome defines the following codes:

Code | Display | Definition
equivalent | Equivalent | The two concepts are equivalent (have the same properties).
subsumes | Subsumes | Coding/code "A" subsumes Coding/code "B" (e.g. B has all the properties A has, and some of it's own).
subsumed-by | Subsumed-By | Coding/code "A" is subsumed by Coding/code "B" (e.g. A has all the properties B has, and some of it's own).
not-subsumed | Not-Subsumed | Coding/code "A" and Coding/code "B" are disjoint (e.g. each has propeties that the other doesn't have).

See the full registry of code systems defined as part of FHIR.

Explanation of the columns that may appear on this page:

Level | A few code lists that FHIR defines are hierarchical - each code is assigned a level. See Code System for further information.
Source | The source of the definition of the code (when the value set draws in codes defined elsewhere)
Code | The code (used as the code in the resource instance). If the code is in italics, this indicates that the code is not selectable ('Abstract')
Display | The display (used in the display element of a Coding). If there is no display, implementers should not simply display the code, but map the concept into their application
Definition | An explanation of the meaning of the concept
Comments | Additional notes about how to use the code

4.3.14.37 Code System http://hl7.org/fhir/list-mode

URL: https://hl7.org/fhir/R4/codesystem-list-mode.html
Structured Documents Work Group | Maturity Level: 2 | Trial Use | Use Context: Any

This is a code system defined by the FHIR project.

Summary

Defining URL: | http://hl7.org/fhir/list-mode
Version: | 4.0.1
Name: | ListMode
Title: | ListMode
Definition: | The processing mode that applies to this list.
Committee: | Structured Documents Work Group
OID: | 2.16.840.1.113883.4.642.4.319 (for OID based terminology systems)
Source Resource | XML / JSON

This Code system is used in the following value sets:

• ValueSet: ListMode (The processing mode that applies to this list.)

• ValueSet: ListMode (The processing mode that applies to this list.)

4.3.14.37.1 Content

4.3.14.37.2 ListMode

The processing mode that applies to this list.

This code system http://hl7.org/fhir/list-mode defines the following codes:

Code | Display | Definition
working | Working List | This list is the master list, maintained in an ongoing fashion with regular updates as the real world list it is tracking changes.
snapshot | Snapshot List | This list was prepared as a snapshot. It should not be assumed to be current.
changes | Change List | A point-in-time list that shows what changes have been made or recommended. E.g. a discharge medication list showing what was added and removed during an encounter.

See the full registry of code systems defined as part of FHIR.

Explanation of the columns that may appear on this page:

Level | A few code lists that FHIR defines are hierarchical - each code is assigned a level. See Code System for further information.
Source | The source of the definition of the code (when the value set draws in codes defined elsewhere)
Code | The code (used as the code in the resource instance). If the code is in italics, this indicates that the code is not selectable ('Abstract')
Display | The display (used in the display element of a Coding). If there is no display, implementers should not simply display the code, but map the concept into their application
Definition | An explanation of the meaning of the concept
Comments | Additional notes about how to use the code

4.3.14.38 Code System http://hl7.org/fhir/concept-property-type

URL: https://hl7.org/fhir/R4/codesystem-concept-property-type.html
Vocabulary Work Group | Maturity Level: N | Normative (from v4.0.0) | Use Context: Any

| This page has been approved as part of an ANSI standard. See the Conformance Package for further details.

This is a code system defined by the FHIR project.

Summary

Defining URL: | http://hl7.org/fhir/concept-property-type
Version: | 4.0.1
Name: | PropertyType
Title: | PropertyType
Definition: | The type of a property value.
Committee: | Vocabulary Work Group
OID: | 2.16.840.1.113883.4.642.4.781 (for OID based terminology systems)
Source Resource | XML / JSON

This Code system is used in the following value sets:

• ValueSet: PropertyType (The type of a property value.)

• ValueSet: PropertyType (The type of a property value.)

4.3.14.38.1 Content

4.3.14.38.2 PropertyType

The type of a property value.

This code system http://hl7.org/fhir/concept-property-type defines the following codes:

Code | Display | Definition
code | code (internal reference) | The property value is a code that identifies a concept defined in the code system.
Coding | Coding (external reference) | The property value is a code defined in an external code system. This may be used for translations, but is not the intent.
string | string | The property value is a string.
integer | integer | The property value is a string (often used to assign ranking values to concepts for supporting score assessments).
boolean | boolean | The property value is a boolean true | false.
dateTime | dateTime | The property is a date or a date + time.
decimal | decimal | The property value is a decimal number.

See the full registry of code systems defined as part of FHIR.

Explanation of the columns that may appear on this page:

Level | A few code lists that FHIR defines are hierarchical - each code is assigned a level. See Code System for further information.
Source | The source of the definition of the code (when the value set draws in codes defined elsewhere)
Code | The code (used as the code in the resource instance). If the code is in italics, this indicates that the code is not selectable ('Abstract')
Display | The display (used in the display element of a Coding). If there is no display, implementers should not simply display the code, but map the concept into their application
Definition | An explanation of the meaning of the concept
Comments | Additional notes about how to use the code

4.3.14.39 Code System http://terminology.hl7.org/CodeSystem/ex-payee-resource-type

URL: https://hl7.org/fhir/R4/codesystem-ex-payee-resource-type.html
Vocabulary Work Group | Maturity Level: 0 | Informative | Use Context: Any

This is a code system defined by the FHIR project.

Summary

Defining URL: | http://terminology.hl7.org/CodeSystem/ex-payee-resource-type
Version: | 4.0.1
Name: | ClaimPayeeResourceType
Title: | ClaimPayeeResourceType
Definition: | The type of Claim payee Resource.
Committee: | ??
OID: | 2.16.840.1.113883.4.642.4.1164 (for OID based terminology systems)
Source Resource | XML / JSON

This Code system is used in the following value sets:

• ValueSet: ClaimPayeeResourceType (The type of Claim payee Resource.)

• ValueSet: ClaimPayeeResourceType (The type of Claim payee Resource.)

4.3.14.39.1 Content

4.3.14.39.2 ClaimPayeeResourceType

The type of Claim payee Resource.

This code system http://terminology.hl7.org/CodeSystem/ex-payee-resource-type defines the following codes:

Code | Display | Definition
organization | Organization | Organization resource.
patient | Patient | Patient resource.
practitioner | Practitioner | Practitioner resource.
relatedperson | RelatedPerson | RelatedPerson resource.

See the full registry of code systems defined as part of FHIR.

Explanation of the columns that may appear on this page:

Level | A few code lists that FHIR defines are hierarchical - each code is assigned a level. See Code System for further information.
Source | The source of the definition of the code (when the value set draws in codes defined elsewhere)
Code | The code (used as the code in the resource instance). If the code is in italics, this indicates that the code is not selectable ('Abstract')
Display | The display (used in the display element of a Coding). If there is no display, implementers should not simply display the code, but map the concept into their application
Definition | An explanation of the meaning of the concept
Comments | Additional notes about how to use the code

4.3.14.40 Code System http://terminology.hl7.org/CodeSystem/name-assembly-order

URL: https://hl7.org/fhir/R4/codesystem-name-assembly-order.html
Vocabulary Work Group | Maturity Level: 0 | Informative | Use Context: Any

This is a code system defined by the FHIR project.

Summary

Defining URL: | http://terminology.hl7.org/CodeSystem/name-assembly-order
Version: | 4.0.1
Name: | HumanNameAssemblyOrder
Title: | HumanNameAssemblyOrder
Definition: | A code that represents the preferred display order of the components of a human name.
Committee: | ??
OID: | 2.16.840.1.113883.4.642.4.1266 (for OID based terminology systems)
Source Resource | XML / JSON

This Code system is used in the following value sets:

• ValueSet: HumanNameAssemblyOrder (A code that represents the preferred display order of the components of a human name.)

• ValueSet: HumanNameAssemblyOrder (A code that represents the preferred display order of the components of a human name.)

4.3.14.40.1 Content

4.3.14.40.2 HumanNameAssemblyOrder

A code that represents the preferred display order of the components of a human name.

This code system http://terminology.hl7.org/CodeSystem/name-assembly-order defines the following codes:

Code | Display | Definition
NL1 | Own Name
NL2 | Partner Name
NL3 | Partner Name followed by Maiden Name
NL4 | Own Name followed by Partner Name

See the full registry of code systems defined as part of FHIR.

Explanation of the columns that may appear on this page:

Level | A few code lists that FHIR defines are hierarchical - each code is assigned a level. See Code System for further information.
Source | The source of the definition of the code (when the value set draws in codes defined elsewhere)
Code | The code (used as the code in the resource instance). If the code is in italics, this indicates that the code is not selectable ('Abstract')
Display | The display (used in the display element of a Coding). If there is no display, implementers should not simply display the code, but map the concept into their application
Definition | An explanation of the meaning of the concept
Comments | Additional notes about how to use the code

4.3.14.41 Code System http://hl7.org/fhir/transaction-mode

URL: https://hl7.org/fhir/R4/codesystem-transaction-mode.html
Vocabulary Work Group | Maturity Level: 0 | Informative | Use Context: Any

This is a code system defined by the FHIR project.

Summary

Defining URL: | http://hl7.org/fhir/transaction-mode
Version: | 4.0.1
Name: | TransactionMode
Title: | TransactionMode
Definition: | A code that indicates how transactions are supported.
Committee: | ??
OID: | 2.16.840.1.113883.4.642.4.193 (for OID based terminology systems)
Source Resource | XML / JSON

This Code system is used in the following value sets:

• ValueSet: TransactionMode (A code that indicates how transactions are supported.)

• ValueSet: TransactionMode (A code that indicates how transactions are supported.)

4.3.14.41.1 Content

4.3.14.41.2 TransactionMode

A code that indicates how transactions are supported.

This code system http://hl7.org/fhir/transaction-mode defines the following codes:

Code | Display | Definition
not-supported | None | Neither batch or transaction is supported.
batch | Batches supported | Batches are supported.
transaction | Transactions Supported | Transactions are supported.
both | Batches & Transactions | Both batches and transactions are supported.

See the full registry of code systems defined as part of FHIR.

Explanation of the columns that may appear on this page:

Level | A few code lists that FHIR defines are hierarchical - each code is assigned a level. See Code System for further information.
Source | The source of the definition of the code (when the value set draws in codes defined elsewhere)
Code | The code (used as the code in the resource instance). If the code is in italics, this indicates that the code is not selectable ('Abstract')
Display | The display (used in the display element of a Coding). If there is no display, implementers should not simply display the code, but map the concept into their application
Definition | An explanation of the meaning of the concept
Comments | Additional notes about how to use the code

4.3.14.42 Code System http://terminology.hl7.org/CodeSystem/audit-event-type

URL: https://hl7.org/fhir/R4/codesystem-audit-event-type.html
Security Work Group | Maturity Level: 3 | Trial Use | Use Context: Any

This is a code system defined by the FHIR project.

Summary

Defining URL: | http://terminology.hl7.org/CodeSystem/audit-event-type
Version: | 4.0.1
Name: | AuditEventID
Title: | Audit Event ID
Definition: | Event Types for Audit Events - defined by DICOM with some FHIR specific additions.
Committee: | Security Work Group
OID: | 2.16.840.1.113883.4.642.4.1136 (for OID based terminology systems)

Copyright: | These codes are excerpted from Digital Imaging and Communications in Medicine (DICOM) Standard, Part 16: Content Mapping Resource, Copyright © 2011 by the National Electrical Manufacturers Association.
Source Resource | XML / JSON

This Code system is used in the following value sets:

• ValueSet: Audit Event ID (Event Types for Audit Events - defined by DICOM with some FHIR specific additions.)

• ValueSet: Audit Event ID (Event Types for Audit Events - defined by DICOM with some FHIR specific additions.)

4.3.14.42.1 Content

4.3.14.42.2 Audit Event ID

Event Types for Audit Events - defined by DICOM with some FHIR specific additions.

Copyright Statement:

These codes are excerpted from Digital Imaging and Communications in Medicine (DICOM) Standard, Part 16: Content Mapping Resource, Copyright © 2011 by the National Electrical Manufacturers Association.

This code system http://terminology.hl7.org/CodeSystem/audit-event-type defines the following codes:

Code | Display | Definition
rest | RESTful Operation | Audit Event: Execution of a RESTful operation as defined by FHIR.

See the full registry of code systems defined as part of FHIR.

Explanation of the columns that may appear on this page:

Level | A few code lists that FHIR defines are hierarchical - each code is assigned a level. See Code System for further information.
Source | The source of the definition of the code (when the value set draws in codes defined elsewhere)
Code | The code (used as the code in the resource instance). If the code is in italics, this indicates that the code is not selectable ('Abstract')
Display | The display (used in the display element of a Coding). If there is no display, implementers should not simply display the code, but map the concept into their application
Definition | An explanation of the meaning of the concept
Comments | Additional notes about how to use the code

4.3.14.43 Code System http://hl7.org/fhir/intervention

URL: https://hl7.org/fhir/R4/codesystem-intervention.html
Vocabulary Work Group | Maturity Level: 0 | Informative | Use Context: Any

This is a code system defined by the FHIR project.

Summary

Defining URL: | http://hl7.org/fhir/intervention
Version: | 4.0.1
Name: | InterventionCodes
Title: | Intervention Codes
Definition: | This value set includes sample Intervention codes.
Committee: | ??
OID: | 2.16.840.1.113883.4.642.4.533 (for OID based terminology systems)
Copyright: | This is an example set.
Source Resource | XML / JSON

This Code system is used in the following value sets:

• ValueSet: Intervention Codes (This value set includes sample Intervention codes.)

• ValueSet: Intervention Codes (This value set includes sample Intervention codes.)

4.3.14.43.1 Content

4.3.14.43.2 Intervention Codes

This value set includes sample Intervention codes.

Copyright Statement:

This is an example set.

This code system http://hl7.org/fhir/intervention defines the following codes:

Code | Display | Definition
unknown | Unknown | Unknown
other | Other | Other

See the full registry of code systems defined as part of FHIR.

Explanation of the columns that may appear on this page:

Level | A few code lists that FHIR defines are hierarchical - each code is assigned a level. See Code System for further information.

Source | The source of the definition of the code (when the value set draws in codes defined elsewhere)
Code | The code (used as the code in the resource instance). If the code is in italics, this indicates that the code is not selectable ('Abstract')
Display | The display (used in the display element of a Coding). If there is no display, implementers should not simply display the code, but map the concept into their application
Definition | An explanation of the meaning of the concept
Comments | Additional notes about how to use the code

4.3.14.44 Code System http://hl7.org/fhir/measure-report-type

URL: https://hl7.org/fhir/R4/codesystem-measure-report-type.html
Clinical Quality Information Work Group | Maturity Level: 2 | Trial Use | Use Context: Any

This is a code system defined by the FHIR project.

Summary

Defining URL: | http://hl7.org/fhir/measure-report-type
Version: | 4.0.1
Name: | MeasureReportType
Title: | MeasureReportType
Definition: | The type of the measure report.
Committee: | Clinical Quality Information Work Group
OID: | 2.16.840.1.113883.4.642.4.779 (for OID based terminology systems)
Source Resource | XML / JSON

This Code system is used in the following value sets:

• ValueSet: MeasureReportType (The type of the measure report.)
• ValueSet: MeasureReportType (The type of the measure report.)

4.3.14.44.1 Content

4.3.14.44.2 MeasureReportType

The type of the measure report.

This code system http://hl7.org/fhir/measure-report-type defines the following codes:

Code | Display | Definition
individual | Individual | An individual report that provides information on the performance for a given measure with respect to a single subject.
subject-list | Subject List | A subject list report that includes a listing of subjects that satisfied each population criteria in the measure.
summary | Summary | A summary report that returns the number of members in each population criteria for the measure.
data-collection | Data Collection | A data collection report that contains data-of-interest for the measure.

See the full registry of code systems defined as part of FHIR.

Explanation of the columns that may appear on this page:

Level | A few code lists that FHIR defines are hierarchical - each code is assigned a level. See Code System for further information.
Source | The source of the definition of the code (when the value set draws in codes defined elsewhere)
Code | The code (used as the code in the resource instance). If the code is in italics, this indicates that the code is not selectable ('Abstract')
Display | The display (used in the display element of a Coding). If there is no display, implementers should not simply display the code, but map the concept into their application
Definition | An explanation of the meaning of the concept
Comments | Additional notes about how to use the code

4.3.14.45 Code System http://terminology.hl7.org/CodeSystem/standards-status

URL: https://hl7.org/fhir/R4/codesystem-standards-status.html
Vocabulary Work Group | Maturity Level: 0 | Informative | Use Context: Any

This is a code system defined by the FHIR project.

Summary

Defining URL: | http://terminology.hl7.org/CodeSystem/standards-status
Version: | 4.0.1
Name: | StandardsStatus
Title: | StandardsStatus
Definition: | HL7 Ballot/Standards status of artifact.
Committee: | ??
OID: | 2.16.840.1.113883.4.642.4.1366 (for OID based terminology systems)
Source Resource | XML / JSON

This Code system is used in the following value sets:

• ValueSet: StandardsStatus (HL7 Ballot/Standards status of artifact.)

• ValueSet: StandardsStatus (HL7 Ballot/Standards status of artifact.)

4.3.14.45.1 Content

4.3.14.45.2 StandardsStatus

HL7 Ballot/Standards status of artifact.

This code system http://terminology.hl7.org/CodeSystem/standards-status defines the following codes:

Code | Display | Definition
draft | Draft | This portion of the specification is not considered to be complete enough or sufficiently reviewed to be safe for implementation. It may have known issues or still be in the "in development" stage. It is included in the publication as a place-holder, to solicit feedback from the implementation community and/or to give implementers some insight as to functionality likely to be included in future versions of the specification. Content at this level should only be implemented by the brave or desperate and is very much "use at your own risk". The content that is Draft that will usually be elevated to Trial Use once review and correction is complete after it has been subjected to ballot.
normative | Normative | This content has been subject to review and production implementation in a wide variety of environments. The content is considered to be stable and has been 'locked', subjecting it to FHIR Inter-version Compatibility Rules. While changes are possible, they are expected to be infrequent and are tightly constrained. Compatibility Rules.
trial-use | Trial-Use | This content has been well reviewed and is considered by the authors to be ready for use in production systems. It has been subjected to ballot and approved as an official standard. However, it has not yet seen widespread use in production across the full spectrum of environments it is intended to be used in. In some cases, there may be documented known issues that require implementation experience to determine appropriate resolutions for. Future versions of FHIR may make significant changes to Trial Use content that are not compatible with previously published content.
informative | Informative | This portion of the specification is provided for implementer assistance, and does not make rules that implementers are required to follow. Typical examples of this content in the FHIR specification are tables of contents, registries, examples, and implementer advice.
deprecated | Deprecated | This portion of the specification is provided for implementer assistance, and does not make rules that implementers are required to follow. Typical examples of this content in the FHIR specification are tables of contents, registries, examples, and implementer advice.
external | External | This is content that is managed outside the FHIR Specification, but included for implementer convenience.

See the full registry of code systems defined as part of FHIR.

Explanation of the columns that may appear on this page:

Level | A few code lists that FHIR defines are hierarchical - each code is assigned a level. See Code System for further information.
Source | The source of the definition of the code (when the value set draws in codes defined elsewhere)
Code | The code (used as the code in the resource instance). If the code is in italics, this indicates that the code is not selectable ('Abstract')
Display | The display (used in the display element of a Coding). If there is no display, implementers should not simply display the code, but map the concept into their application
Definition | An explanation of the meaning of the concept
Comments | Additional notes about how to use the code

4.3.14.46 Code System http://hl7.org/fhir/action-required-behavior

URL: https://hl7.org/fhir/R4/codesystem-action-required-behavior.html
Clinical Decision Support Work Group | Maturity Level: 2 | Trial Use | Use Context: Any

This is a code system defined by the FHIR project.

Summary

Defining URL: | http://hl7.org/fhir/action-required-behavior
Version: | 4.0.1
Name: | ActionRequiredBehavior
Title: | ActionRequiredBehavior
Definition: | Defines expectations around whether an action or action group is required.
Committee: | Clinical Decision Support Work Group
OID: | 2.16.840.1.113883.4.642.4.804 (for OID based terminology systems)
Source Resource | XML / JSON

This Code system is used in the following value sets:

• ValueSet: ActionRequiredBehavior (Defines expectations around whether an action or action group is required.)

• ValueSet: ActionRequiredBehavior (Defines expectations around whether an action or action group is required.)

4.3.14.46.1 Content

4.3.14.46.2 ActionRequiredBehavior

Defines expectations around whether an action or action group is required.

This code system http://hl7.org/fhir/action-required-behavior defines the following codes:

Code | Display | Definition
must | Must | An action with this behavior must be included in the actions processed by the end user; the end user SHALL NOT choose not to include this action.
could | Could | An action with this behavior may be included in the set of actions processed by the end user.
must-unless-documented | Must Unless Documented | An action with this behavior must be included in the set of actions processed by the end user, unless the end user provides documentation as to why the action was not included.

See the full registry of code systems defined as part of FHIR.

Explanation of the columns that may appear on this page:

Level | A few code lists that FHIR defines are hierarchical - each code is assigned a level. See Code System for further information.
Source | The source of the definition of the code (when the value set draws in codes defined elsewhere)
Code | The code (used as the code in the resource instance). If the code is in italics, this indicates that the code is not selectable ('Abstract')
Display | The display (used in the display element of a Coding). If there is no display, implementers should not simply display the code, but map the concept into their application
Definition | An explanation of the meaning of the concept
Comments | Additional notes about how to use the code

4.3.14.47 Code System http://terminology.hl7.org/CodeSystem/ex-procedure-type

URL: https://hl7.org/fhir/R4/codesystem-ex-procedure-type.html
Financial Management Work Group | Maturity Level: 1 | Draft | Use Context: Any

This is a code system defined by the FHIR project.

Summary

Defining URL: | http://terminology.hl7.org/CodeSystem/ex-procedure-type
Version: | 4.0.1
Name: | ExampleProcedureTypeCodes
Title: | Example Procedure Type Codes
Definition: | This value set includes example Procedure Type codes.
Committee: | Financial Management Work Group
OID: | 2.16.840.1.113883.4.642.4.1388 (for OID based terminology systems)
Copyright: | This is an example set.
Source Resource | XML / JSON

This Code system is used in the following value sets:

• ValueSet: Example Procedure Type Codes (This value set includes example Procedure Type codes.)
• ValueSet: Example Procedure Type Codes (This value set includes example Procedure Type codes.)

4.3.14.47.1 Content

4.3.14.47.2 Example Procedure Type Codes

This value set includes example Procedure Type codes.

Copyright Statement:

This is an example set.

This code system http://terminology.hl7.org/CodeSystem/ex-procedure-type defines the following codes:

Code | Display | Definition
primary | Primary procedure | The first procedure in a series required to produce and overall patient outcome.
secondary | Secondary procedure | The second procedure in a series required to produce and overall patient outcome.

See the full registry of code systems defined as part of FHIR.

Explanation of the columns that may appear on this page:

Level | A few code lists that FHIR defines are hierarchical - each code is assigned a level. See Code System for further information.
Source | The source of the definition of the code (when the value set draws in codes defined elsewhere)
Code | The code (used as the code in the resource instance). If the code is in italics, this indicates that the code is not selectable ('Abstract')
Display | The display (used in the display element of a Coding). If there is no display, implementers should not simply display the code, but map the concept into their application
Definition | An explanation of the meaning of the concept
Comments | Additional notes about how to use the code

4.3.14.48 Code System http://hl7.org/fhir/metric-color

URL: https://hl7.org/fhir/R4/codesystem-metric-color.html
Health Care Devices Work Group | Maturity Level: 1 | Trial Use | Use Context: Any

This is a code system defined by the FHIR project.

Summary

Defining URL: | http://hl7.org/fhir/metric-color
Version: | 4.0.1
Name: | DeviceMetricColor
Title: | DeviceMetricColor
Definition: | Describes the typical color of representation.
Committee: | Health Care Devices Work Group
OID: | 2.16.840.1.113883.4.642.4.655 (for OID based terminology systems)
Source Resource | XML / JSON

This Code system is used in the following value sets:

• ValueSet: DeviceMetricColor (Describes the typical color of representation.)

• ValueSet: DeviceMetricColor (Describes the typical color of representation.)

4.3.14.48.1 Content

4.3.14.48.2 DeviceMetricColor

Describes the typical color of representation.

This code system http://hl7.org/fhir/metric-color defines the following codes:

Code | Display | Definition
black | Color Black | Color for representation - black.
red | Color Red | Color for representation - red.
green | Color Green | Color for representation - green.
yellow | Color Yellow | Color for representation - yellow.
blue | Color Blue | Color for representation - blue.
magenta | Color Magenta | Color for representation - magenta.
cyan | Color Cyan | Color for representation - cyan.
white | Color White | Color for representation - white.

See the full registry of code systems defined as part of FHIR.

Explanation of the columns that may appear on this page:

Level | A few code lists that FHIR defines are hierarchical - each code is assigned a level. See Code System for further information.
Source | The source of the definition of the code (when the value set draws in codes defined elsewhere)
Code | The code (used as the code in the resource instance). If the code is in italics, this indicates that the code is not selectable ('Abstract')
Display | The display (used in the display element of a Coding). If there is no display, implementers should not simply display the code, but map the concept into their application
Definition | An explanation of the meaning of the concept
Comments | Additional notes about how to use the code

4.3.14.49 Code System http://hl7.org/fhir/restful-capability-mode

URL: https://hl7.org/fhir/R4/codesystem-restful-capability-mode.html
FHIR Infrastructure Work Group | Maturity Level: N | Normative (from v4.0.0) | Use Context: Any

| This page has been approved as part of an ANSI standard. See the Conformance Package for further details.

This is a code system defined by the FHIR project.

Summary

Defining URL: | http://hl7.org/fhir/restful-capability-mode
Version: | 4.0.1
Name: | RestfulCapabilityMode
Title: | RestfulCapabilityMode
Definition: | The mode of a RESTful capability statement.
Committee: | FHIR Infrastructure Work Group
OID: | 2.16.840.1.113883.4.642.4.177 (for OID based terminology systems)
Source Resource | XML / JSON

This Code system is used in the following value sets:

• ValueSet: RestfulCapabilityMode (The mode of a RESTful capability statement.)

• ValueSet: RestfulCapabilityMode (The mode of a RESTful capability statement.)

4.3.14.49.1 Content

4.3.14.49.2 RestfulCapabilityMode

The mode of a RESTful capability statement.

This code system http://hl7.org/fhir/restful-capability-mode defines the following codes:

Code | Display | Definition

client | Client | The application acts as a client for this resource.
server | Server | The application acts as a server for this resource.

See the full registry of code systems defined as part of FHIR.

Explanation of the columns that may appear on this page:

Level | A few code lists that FHIR defines are hierarchical - each code is assigned a level. See Code System for further information.
Source | The source of the definition of the code (when the value set draws in codes defined elsewhere)
Code | The code (used as the code in the resource instance). If the code is in italics, this indicates that the code is not selectable ('Abstract')
Display | The display (used in the display element of a Coding). If there is no display, implementers should not simply display the code, but map the concept into their application
Definition | An explanation of the meaning of the concept
Comments | Additional notes about how to use the code

4.3.14.50 Code System http://hl7.org/fhir/ex-oralprostho

URL: https://hl7.org/fhir/R4/codesystem-oral-prosthodontic-material.html
Vocabulary Work Group | Maturity Level: 0 | Informative | Use Context: Any

This is a code system defined by the FHIR project.

Summary

Defining URL: | http://hl7.org/fhir/ex-oralprostho
Version: | 4.0.1
Name: | OralProsthoMaterialTypeCodes
Title: | Oral Prostho Material type Codes
Definition: | This value set includes sample Oral Prosthodontic Material type codes.
Committee: | ??
OID: | 2.16.840.1.113883.4.642.4.539 (for OID based terminology systems)
Copyright: | This is an example set.
Source Resource | XML / JSON

This Code system is used in the following value sets:

• ValueSet: Oral Prostho Material type Codes (This value set includes sample Oral Prosthodontic Material type codes.)

• ValueSet: Oral Prostho Material type Codes (This value set includes sample Oral Prosthodontic Material type codes.)

4.3.14.50.1 Content

4.3.14.50.2 Oral Prostho Material type Codes

This value set includes sample Oral Prosthodontic Material type codes.

Copyright Statement:

This is an example set.

This code system http://hl7.org/fhir/ex-oralprostho defines the following codes:

Code | Display | Definition
1 | Fixed Bridge | Fixed Bridge
2 | Maryland Bridge | Maryland Bridge
3 | Denture Acrylic | Denture Acrylic
4 | Denture Chrome Cobalt | Denture Chrome Cobalt

See the full registry of code systems defined as part of FHIR.

Explanation of the columns that may appear on this page:

Level | A few code lists that FHIR defines are hierarchical - each code is assigned a level. See Code System for further information.
Source | The source of the definition of the code (when the value set draws in codes defined elsewhere)
Code | The code (used as the code in the resource instance). If the code is in italics, this indicates that the code is not selectable ('Abstract')
Display | The display (used in the display element of a Coding). If there is no display, implementers should not simply display the code, but map the concept into their application
Definition | An explanation of the meaning of the concept
Comments | Additional notes about how to use the code

4.3.14.51 Code System http://hl7.org/fhir/graph-compartment-use

URL: https://hl7.org/fhir/R4/codesystem-graph-compartment-use.html
FHIR Infrastructure Work Group | Maturity Level: 1 | Trial Use | Use Context: Any

This is a code system defined by the FHIR project.

Summary

Defining URL: | http://hl7.org/fhir/graph-compartment-use
Version: | 4.0.1
Name: | GraphCompartmentUse
Title: | GraphCompartmentUse
Definition: | Defines how a compartment rule is used.
Committee: | FHIR Infrastructure Work Group
OID: | 2.16.840.1.113883.4.642.4.283 (for OID based terminology systems)
Source Resource | XML / JSON

This Code system is used in the following value sets:

• ValueSet: GraphCompartmentUse (Defines how a compartment rule is used.)

• ValueSet: GraphCompartmentUse (Defines how a compartment rule is used.)

4.3.14.51.1 Content

4.3.14.51.2 GraphCompartmentUse

Defines how a compartment rule is used.

This code system http://hl7.org/fhir/graph-compartment-use defines the following codes:

Code | Display | Definition
condition | Condition | This compartment rule is a condition for whether the rule applies.
requirement | Requirement | This compartment rule is enforced on any relationships that meet the conditions.

See the full registry of code systems defined as part of FHIR.

Explanation of the columns that may appear on this page:

Level | A few code lists that FHIR defines are hierarchical - each code is assigned a level. See Code System for further information.
Source | The source of the definition of the code (when the value set draws in codes defined elsewhere)
Code | The code (used as the code in the resource instance). If the code is in italics, this indicates that the code is not selectable ('Abstract')
Display | The display (used in the display element of a Coding). If there is no display, implementers should not simply display the code, but map the concept into their application
Definition | An explanation of the meaning of the concept
Comments | Additional notes about how to use the code

4.3.14.52 Code System http://terminology.hl7.org/CodeSystem/validation-process

URL: https://hl7.org/fhir/R4/codesystem-verificationresult-validation-process.html
Patient Administration Work Group | Maturity Level: 1 | Draft | Use Context: Any

This is a code system defined by the FHIR project.

Summary

Defining URL: | http://terminology.hl7.org/CodeSystem/validation-process
Version: | 4.0.1
Name: | validation-process
Title: | Validation-process
Definition: | The primary process by which the target is validated
Committee: | Patient Administration Work Group
OID: | 2.16.840.1.113883.4.642.1.889 (for OID based terminology systems)
Source Resource | XML / JSON

This Code system is used in the following value sets:

• ValueSet: Validation-process (The primary process by which the target is validated)

• ValueSet: Validation-process (The primary process by which the target is validated)

4.3.14.52.1 Content

4.3.14.52.2 Validation-process

The primary process by which the target is validated

This code system http://terminology.hl7.org/CodeSystem/validation-process defines the following codes:

Code | Display | Definition
edit-check | edit check
valueset | value set
primary | primary source
multi | multiple sources
standalone | standalone
in-context | in context

See the full registry of code systems defined as part of FHIR.

Explanation of the columns that may appear on this page:

Level | A few code lists that FHIR defines are hierarchical - each code is assigned a level. See Code System for further information.
Source | The source of the definition of the code (when the value set draws in codes defined elsewhere)
Code | The code (used as the code in the resource instance). If the code is in italics, this indicates that the code is not selectable ('Abstract')
Display | The display (used in the display element of a Coding). If there is no display, implementers should not simply display the code, but map the concept into their application
Definition | An explanation of the meaning of the concept
Comments | Additional notes about how to use the code

4.3.14.53 Code System http://terminology.hl7.org/CodeSystem/parameter-group

URL: https://hl7.org/fhir/R4/codesystem-parameter-group.html
Vocabulary Work Group | Maturity Level: 0 | Informative | Use Context: Any

This is a code system defined by the FHIR project.

Summary

Defining URL: | http://terminology.hl7.org/CodeSystem/parameter-group
Version: | 4.0.1
Name: | DeviceDefinitionParameterGroup
Title: | DeviceDefinitionParameterGroup
Definition: | Codes identifying groupings of parameters; e.g. Cardiovascular.
Committee: | ??
OID: | 2.16.840.1.113883.4.642.4.1264 (for OID based terminology systems)
Source Resource | XML / JSON

This Code system is used in the following value sets:

• ValueSet: DeviceDefinitionParameterGroup (Codes identifying groupings of parameters; e.g. Cardiovascular.)

• ValueSet: DeviceDefinitionParameterGroup (Codes identifying groupings of parameters; e.g. Cardiovascular.)

4.3.14.53.1 Content

4.3.14.53.2 DeviceDefinitionParameterGroup

Codes identifying groupings of parameters; e.g. Cardiovascular.

This code system http://terminology.hl7.org/CodeSystem/parameter-group defines the following codes:

Code | Display | Definition
haemodynamic | Haemodynamic Parameter Group | Haemodynamic Parameter Group - MDC_PGRP_HEMO.
ecg | ECG Parameter Group | ECG Parameter Group - MDC_PGRP_ECG.
respiratory | Respiratory Parameter Group | Respiratory Parameter Group - MDC_PGRP_RESP.
ventilation | Ventilation Parameter Group | Ventilation Parameter Group - MDC_PGRP_VENT.
neurological | Neurological Parameter Group | Neurological Parameter Group - MDC_PGRP_NEURO.
drug-delivery | Drug Delivery Parameter Group | Drug Delivery Parameter Group - MDC_PGRP_DRUG.
fluid-chemistry | Fluid Chemistry Parameter Group | Fluid Chemistry Parameter Group - MDC_PGRP_FLUID.
blood-chemistry | Blood Chemistry Parameter Group | Blood Chemistry Parameter Group - MDC_PGRP_BLOOD_CHEM.
miscellaneous | Miscellaneous Parameter Group | Miscellaneous Parameter Group - MDC_PGRP_MISC.

See the full registry of code systems defined as part of FHIR.

Explanation of the columns that may appear on this page:

Level | A few code lists that FHIR defines are hierarchical - each code is assigned a level. See Code System for further information.
Source | The source of the definition of the code (when the value set draws in codes defined elsewhere)
Code | The code (used as the code in the resource instance). If the code is in italics, this indicates that the code is not selectable ('Abstract')
Display | The display (used in the display element of a Coding). If there is no display, implementers should not simply display the code, but map the concept into their application
Definition | An explanation of the meaning of the concept
Comments | Additional notes about how to use the code

4.3.14.54 Code System http://terminology.hl7.org/CodeSystem/immunization-evaluation-dose-status-reason

URL: https://hl7.org/fhir/R4/codesystem-immunization-evaluation-dose-status-reason.html
Public Health and Emergency Response Work Group | Maturity Level: 1 | Draft | Use Context: Any

This is a code system defined by the FHIR project.

Summary

Defining URL: | http://terminology.hl7.org/CodeSystem/immunization-evaluation-dose-status-reason
Version: | 4.0.1
Name: | ImmunizationEvaluationDoseStatusReasonCodes
Title: | Immunization Evaluation Dose Status Reason codes
Definition: | The value set to instantiate this attribute should be drawn from a terminologically robust code system that consists of or contains concepts to support describing the reason why an administered dose has been assigned a particular status. Often, this reason describes why a dose is considered invalid. This value set is provided as a suggestive example.
Committee: | Public Health and Emergency Response Work Group
OID: | 2.16.840.1.113883.4.642.4.1103 (for OID based terminology systems)
Source Resource | XML / JSON

This Code system is used in the following value sets:

• ValueSet: Immunization Evaluation Dose Status Reason codes (The value set to instantiate this attribute should be drawn from a terminologically robust code system that consists of or contains concepts to support describing the reason why an administered dose has been assigned a particular status. Often, this reason describes why a dose is considered invalid. This value set is provided as a suggestive example.)

• ValueSet: Immunization Evaluation Dose Status Reason codes (The value set to instantiate this attribute should be drawn from a terminologically robust code system that consists of or contains concepts to support describing the reason why an administered dose has been assigned a particular status. Often, this reason describes why a dose is considered invalid. This value set is provided as a suggestive example.)

4.3.14.54.1 Content

4.3.14.54.2 Immunization Evaluation Dose Status Reason codes

The value set to instantiate this attribute should be drawn from a terminologically robust code system that consists of or contains concepts to support describing the reason why an administered dose has been assigned a particular status. Often, this reason describes why a dose is considered invalid. This value set is provided as a suggestive example.

This code system http://terminology.hl7.org/CodeSystem/immunization-evaluation-dose-status-reason defines the following codes:

Code | Display | Definition
advstorage | Adverse storage condition | The product was stored in a manner inconsistent with manufacturer guidelines potentially reducing the effectiveness of the product.
coldchbrk | Cold chain break | The product was stored at a temperature inconsistent with manufacturer guidelines potentially reducing the effectiveness of the product.
explot | Expired lot | The product was administered after the expiration date associated with lot of vaccine.
outsidesched | Administered outside recommended schedule | The product was administered at a time inconsistent with the documented schedule.
prodrecall | Product recall | The product administered has been recalled by the manufacturer.

See the full registry of code systems defined as part of FHIR.

Explanation of the columns that may appear on this page:

Level | A few code lists that FHIR defines are hierarchical - each code is assigned a level. See Code System for further information.
Source | The source of the definition of the code (when the value set draws in codes defined elsewhere)
Code | The code (used as the code in the resource instance). If the code is in italics, this indicates that the code is not selectable ('Abstract')
Display | The display (used in the display element of a Coding). If there is no display, implementers should not simply display the code, but map the concept into their application
Definition | An explanation of the meaning of the concept
Comments | Additional notes about how to use the code

4.3.14.55 Code System http://terminology.hl7.org/CodeSystem/immunization-evaluation-dose-status

URL: https://hl7.org/fhir/R4/codesystem-immunization-evaluation-dose-status.html
Public Health and Emergency Response Work Group | Maturity Level: 1 | Draft | Use Context: Any

This is a code system defined by the FHIR project.

Summary

Defining URL: | http://terminology.hl7.org/CodeSystem/immunization-evaluation-dose-status
Version: | 4.0.1
Name: | ImmunizationEvaluationDoseStatusCodes
Title: | Immunization Evaluation Dose Status codes
Definition: | The value set to instantiate this attribute should be drawn from a terminologically robust code system that consists of or contains concepts to support describing the validity of a dose relative to a particular recommended schedule. This value set is provided as a suggestive example.
Committee: | Public Health and Emergency Response Work Group
OID: | 2.16.840.1.113883.4.642.4.1102 (for OID based terminology systems)
Source Resource | XML / JSON

This Code system is used in the following value sets:

• ValueSet: Immunization Evaluation Dose Status codes (The value set to instantiate this attribute should be drawn from a terminologically robust code system that consists of or contains concepts to support describing the validity of a dose relative to a particular recommended schedule. This value set is provided as a suggestive example.)

• ValueSet: Immunization Evaluation Dose Status codes (The value set to instantiate this attribute should be drawn from a terminologically robust code system that consists of or contains concepts to support describing the validity of a dose relative to a particular recommended schedule. This value set is provided as a suggestive example.)

4.3.14.55.1 Content

4.3.14.55.2 Immunization Evaluation Dose Status codes

The value set to instantiate this attribute should be drawn from a terminologically robust code system that consists of or contains concepts to support describing the validity of a dose relative to a particular recommended schedule. This value set is provided as a suggestive example.

This code system http://terminology.hl7.org/CodeSystem/immunization-evaluation-dose-status defines the following codes:

Code | Display | Definition
valid | Valid | The dose counts toward fulfilling a path to immunity for a patient, providing protection against the target disease.
notvalid | Not valid | The dose does not count toward fulfilling a path to immunity for a patient.

See the full registry of code systems defined as part of FHIR.

Explanation of the columns that may appear on this page:

Level | A few code lists that FHIR defines are hierarchical - each code is assigned a level. See Code System for further information.
Source | The source of the definition of the code (when the value set draws in codes defined elsewhere)
Code | The code (used as the code in the resource instance). If the code is in italics, this indicates that the code is not selectable ('Abstract')
Display | The display (used in the display element of a Coding). If there is no display, implementers should not simply display the code, but map the concept into their application
Definition | An explanation of the meaning of the concept
Comments | Additional notes about how to use the code

4.3.14.56 Code System http://terminology.hl7.org/CodeSystem/service-type

URL: https://hl7.org/fhir/R4/codesystem-service-type.html
Patient Administration Work Group | Maturity Level: 1 | Draft | Use Context: Any

This is a code system defined by the FHIR project.

Summary

Defining URL: | http://terminology.hl7.org/CodeSystem/service-type
Version: | 4.0.1
Name: | ServiceType
Title: | Service type
Definition: | This value set defines an example set of codes of service-types.
Committee: | Patient Administration Work Group
OID: | 2.16.840.1.113883.4.642.4.1145 (for OID based terminology systems)
Source Resource | XML / JSON

This Code system is used in the following value sets:

• ValueSet: Service type (This value set defines an example set of codes of service-types.)

• ValueSet: Service type (This value set defines an example set of codes of service-types.)

4.3.14.56.1 Content

4.3.14.56.2 Service type

This value set defines an example set of codes of service-types.

This code system http://terminology.hl7.org/CodeSystem/service-type defines many codes, of which the following are some examples:

Code | Display | Definition
1 | Adoption/Permanent Care Info/Support | Adoption & permanent care information/support
2 | Aged Care Assessment | Aged care assessment
3 | Aged Care Information/Referral | Aged Care information/referral
4 | Aged Residential Care | Aged Residential Care
5 | Case Management for Older Persons | Case management for older persons
6 | Delivered Meals (Meals On Wheels) | Delivered meals (meals on wheels)

7 | Friendly Visiting | Friendly visiting
8 | Home Care/Housekeeping Assistance | Home care/housekeeping assistance
9 | Home Maintenance and Repair | Home maintenance and repair
10 | Personal Alarms/Alerts | Personal alarms/alerts
11 | Personal Care for Older Persons | Personal care for older persons
12 | Planned Activity Groups | Planned activity groups
13 | Acupuncture | Acupuncture
14 | Alexander Technique Therapy | Alexander technique therapy
15 | Aromatherapy | Aromatherapy
16 | Biorhythm Services | Biorhythm services
17 | Bowen Therapy | Bowen therapy
18 | Chinese Herbal Medicine | Chinese herbal medicine
19 | Feldenkrais | Feldenkrais
20 | Homoeopathy | Homoeopathy
21 | Hydrotherapy | Hydrotherapy
22 | Hypnotherapy | Hypnotherapy
23 | Kinesiology | Kinesiology
24 | Magnetic Therapy | Magnetic therapy
25 | Massage Therapy | Massage therapy
26 | Meditation | Meditation
27 | Myotherapy | Myotherapy
28 | Naturopathy | Naturopathy
29 | Reflexology | Reflexology
30 | Reiki | Reiki
31 | Relaxation Therapy | Relaxation therapy
32 | Shiatsu | Shiatsu
33 | Western Herbal Medicine | Western herbal medicine
34 | Family Day care | Family day care
35 | Holiday Programs | Holiday programs
36 | Kindergarten Inclusion Support | Kindergarten inclusion support for children with a disability
37 | Kindergarten/Preschool | Kindergarten/preschool
38 | Long Day Child Care | Long day child care
39 | Occasional Child Care | Occasional child care
40 | Outside School Hours Care | Outside school hours care
41 | Children's Play Programs | Children's play programs
42 | Parenting/Family Support/Education | Parenting & family management support/education
43 | Playgroup | Playgroup
44 | School Nursing | School nursing
45 | Toy Library | Toy library
46 | Child Protection/Child Abuse Report | Child protection/child abuse report
47 | Foster Care | Foster care
48 | Residential/Out-of-Home Care | Residential/ out of home care
49 | Support - Young People Leaving Care | Support for young people leaving care
50 | Audiology | Audiology
51 | Blood Donation | Blood donation
52 | Chiropractic | Chiropractic
53 | Dietetics | Dietetics
54 | Family Planning | Family planning
55 | Health Advocacy/Liaison Service | Health advocacy/Liaison service
56 | Health Information/Referral | Health information/referral
57 | Immunization | Immunization
58 | Maternal & Child Health | Maternal & child health
59 | Nursing | Nursing
60 | Nutrition | Nutrition
61 | Occupational Therapy | Occupational therapy
62 | Optometry | Optometry
63 | Osteopathy | Osteopathy
64 | Pharmacy | Pharmacy
65 | Physiotherapy | Physiotherapy
66 | Podiatry | Podiatry
67 | Sexual Health | Sexual health
68 | Speech Pathology/Therapy | Speech pathology/therapy
69 | Bereavement Counselling | Bereavement counselling
70 | Crisis Counselling | Crisis counselling
71 | Family Counselling/Therapy | Family counselling and/or family therapy
72 | Family Violence Counselling | Family violence counselling
73 | Financial Counselling | Financial counselling
74 | Generalist Counselling | Generalist counselling
75 | Genetic Counselling | Genetic counselling
76 | Health Counselling | Health counselling
77 | Mediation | Mediation
78 | Problem Gambling Counselling | Problem gambling counselling

79 | Relationship Counselling | Relationship counselling
80 | Sexual Assault Counselling | Sexual assault counselling
81 | Trauma Counselling | Trauma counselling
82 | Victims of Crime Counselling | Victims of crime counselling
83 | Cemetery Operation | Cemetery operation
84 | Cremation | Cremation
85 | Death Service Information | Death service information
86 | Funeral Services | Funeral services
87 | Endodontic | Endodontic
88 | General Dental | General dental
89 | Oral Medicine | Oral medicine
90 | Oral Surgery | Oral surgery
91 | Orthodontic | Orthodontic
92 | Paediatric Dentistry | Paediatric Dentistry
93 | Periodontic | Periodontic
94 | Prosthodontic | Prosthodontic
95 | Acquired Brain Injury Info/Referral | Acquired brain injury information/referral
96 | Disability Advocacy | Disability advocacy
97 | Disability Aids & Equipment | Disability aids & equipment
98 | Disability Case Management | Disability case management
99 | Disability Day Programs/Activities | Disability day programs & activities
100 | Disability Information/Referral | Disability information/referral
101 | Disability Support Packages | Disability support packages
102 | Disability Supported Accommodation | Disability supported accommodation
103 | Early Childhood Intervention | Early childhood intervention
104 | Hearing Aids & Equipment | Hearing aids & equipment
105 | Drug and/or Alcohol Counselling | Drug and/or alcohol counselling
106 | Drug/Alcohol Information/Referral | Drug and/or alcohol information/referral
107 | Needle & Syringe Exchange | Needle & Syringe exchange
108 | Non-resid. Alcohol/Drug Treatment | Non-residential alcohol and/or drug dependence treatment
109 | Pharmacotherapy | Pharmacotherapy (eg. methadone) program
110 | Quit Program | Quit program
111 | Residential Alcohol/Drug Treatment | Residential alcohol and/or drug dependence treatment
112 | Adult/Community Education | Adult/community education
113 | Higher Education | Higher education
114 | Primary Education | Primary education
115 | Secondary Education | Secondary education
116 | Training & Vocational Education | Training & vocational education
117 | Emergency Medical | Emergency medical
118 | Employment Placement and/or Support | Employment placement and/or support
119 | Vocational Rehabilitation | Vocational Rehabilitation
120 | Work Safety/Accident Prevention | Workplace safety and/or accident prevention
121 | Financial Assistance | Financial assistance
122 | Financial Information/Advice | Financial information/advice
123 | Material Aid | Material aid
124 | General Practice | General Practice/GP (doctor)
125 | Accommodation Placement/Support | Accommodation placement and/or support
126 | Crisis/Emergency Accommodation | Crisis/emergency accommodation
127 | Homelessness Support | Homelessness support
128 | Housing Information/Referral | Housing information/referral
129 | Public Rental Housing | Public rental housing
130 | Interpreting/Multilingual Service | Interpreting/Multilingual/Language service
131 | Juvenile Justice | Juvenile Justice
132 | Legal Advocacy | Legal advocacy
133 | Legal Information/Advice/Referral | Legal information/advice/referral
134 | Mental Health Advocacy | Mental health advocacy
135 | Mental Health Assess/Triage/Crisis Response | Mental health assessment/triage/crisis response
136 | Mental Health Case Management | Mental health case management/continuing care
137 | Mental Health Information/Referral | Mental health information/referral
138 | Mental Health Inpatient Services | Mental health inpatient services (hospital psychiatric unit) - requires referral
139 | Mental Health Non-residential Rehab | Mental health non-residential rehabilitation
140 | Mental Health Residential Rehab/CCU | Mental health residential rehabilitation/community care unit
141 | Psychiatry (Requires Referral) | Psychiatry (requires referral)
142 | Psychology | Psychology
143 | Martial Arts | Martial arts
144 | Personal Fitness Training | Personal fitness training
145 | Physical Activity Group | Physical activity group
146 | Physical Activity Programs | Physical activity programs
147 | Physical Fitness Testing | Physical fitness testing
148 | Pilates | Pilates
149 | Self-Defence | Self defence
150 | Sporting Club | Sporting club

151 | Yoga | Yoga
152 | Food Safety | Food safety
153 | Health Regulatory /Inspection /Cert. | Health regulatory, inspection and/or certification
154 | Work Health/Safety Inspection/Cert. | Workplace health and/or safety inspection and/or certification
155 | Carer Support | Carer support
156 | Respite Care | Respite care
157 | Anatomical Pathology | Anatomical Pathology (including Cytopathology & Forensic Pathology)
158 | Pathology - Clinical Chemistry | Pathology - Clinical Chemistry
159 | Pathology - General | Pathology - General
160 | Pathology - Genetics | Pathology - Genetics
161 | Pathology - Haematology | Pathology - Haematology
162 | Pathology - Immunology | Pathology - Immunology
163 | Pathology - Microbiology | Pathology - Microbiology
164 | Anaesthesiology - Pain Medicine | Anaesthesiology - Pain Medicine
165 | Cardiology | Cardiology
166 | Clinical Genetics | Clinical Genetics
167 | Clinical Pharmacology | Clinical Pharmacology
168 | Dermatology | Dermatology
169 | Endocrinology | Endocrinology
170 | Gastroenterology & Hepatology | Gastroenterology & Hepatology
171 | Geriatric Medicine | Geriatric medicine
172 | Immunology & Allergy | Immunology & Allergy
173 | Infectious Diseases | Infectious diseases
174 | Intensive Care Medicine | Intensive care medicine
175 | Medical Oncology | Medical Oncology
176 | Nephrology | Nephrology
177 | Neurology | Neurology
178 | Occupational Medicine | Occupational Medicine
179 | Palliative Medicine | Palliative Medicine
180 | Public Health Medicine | Public Health Medicine
181 | Rehabilitation Medicine | Rehabilitation Medicine
182 | Rheumatology | Rheumatology
183 | Sleep Medicine | Sleep Medicine
184 | Thoracic Medicine | Thoracic medicine
185 | Gynaecological Oncology | Gynaecological Oncology
186 | Obstetrics & Gynaecology | Obstetrics & Gynaecology
187 | Reproductive Endocrinology/Infertility | Reproductive Endocrinology & Infertility
188 | Urogynaecology | Urogynaecology
189 | Neonatology & Perinatology | Neonatology & Perinatology
190 | Paediatric Cardiology | Paediatric Cardiology
191 | Paediatric Clinical Genetics | Paediatric Clinical Genetics
192 | Paediatric Clinical Pharmacology | Paediatric Clinical Pharmacology
193 | Paediatric Endocrinology | Paediatric Endocrinology
194 | Paed. Gastroenterology/Hepatology | Paediatric Gastroenterology & Hepatology
195 | Paediatric Haematology | Paediatric Haematology
196 | Paediatric Immunology & Allergy | Paediatric Immunology & Allergy
197 | Paediatric Infectious Diseases | Paediatric Infectious diseases
198 | Paediatric Intensive Care Medicine | Paediatric intensive care medicine
199 | Paediatric Medical Oncology | Paediatric Medical Oncology
200 | Paediatric Medicine | Paediatric Medicine
201 | Paediatric Nephrology | Paediatric Nephrology
202 | Paediatric Neurology | Paediatric Neurology
203 | Paediatric Nuclear Medicine | Paediatric Nuclear Medicine
204 | Paediatric Rehabilitation Medicine | Paediatric Rehabilitation Medicine
205 | Paediatric Rheumatology | Paediatric Rheumatology
206 | Paediatric Sleep Medicine | Paediatric Sleep Medicine
207 | Paediatric Surgery | Paediatric Surgery
208 | Paediatric Thoracic Medicine | Paediatric Thoracic Medicine
209 | Diag. Radiology /Xray /CT /Fluoroscopy | Diagnostic Radiology/Xray/CT/Fluoroscopy
210 | Diagnostic Ultrasound | Diagnostic Ultrasound
211 | Magnetic Resonance Imaging (MRI) | Magnetic Resonance Imaging (MRI)
212 | Nuclear Medicine | Nuclear Medicine
213 | Obstetric/Gynaecological Ultrasound | Obstetric & Gynaecological Ultrasound
214 | Radiation Oncology | Radiation oncology
215 | Cardiothoracic Surgery | Cardiothoracic surgery
216 | Neurosurgery | Neurosurgery
217 | Ophthalmology | Ophthalmology
218 | Orthopaedic Surgery | Orthopaedic surgery
219 | Otolaryngology/Head & Neck Surgery | Otolaryngology - Head & Neck Surgery
220 | Plastic & Reconstructive Surgery | Plastic & Reconstructive Surgery
221 | Surgery - General | Surgery - General
222 | Urology | Urology

223 | Vascular Surgery | Vascular surgery
224 | Support Groups | Support groups
225 | Air ambulance | Air ambulance
226 | Ambulance | Ambulance
227 | Blood Transport | Blood transport
228 | Community Bus | Community bus
229 | Flying Doctor Service | Flying doctor service
230 | Patient Transport | Patient transport
231 | A&E | A&E
232 | A&EP | A&EP
233 | Abuse | Abuse
234 | ACAS | ACAS
235 | Access | Access
236 | Accident | Accident
237 | Acute Inpatient Serv | Acute Inpatient Service's
238 | Adult Day Programs | Adult Day Programs
239 | Adult Mental Health Services | Adult Mental Health Services
240 | Advice | Advice
241 | Advocacy | Advocacy
242 | Aged Persons Mental | Aged Persons Mental Health Residential Units
243 | Aged Persons Mental | Aged Persons Mental Health Services
244 | Aged Persons Mental | Aged Persons Mental Health Teams
245 | Aids | Aids
246 | Al-Anon | Al-Anon
247 | Alcohol | Alcohol
248 | Al-Teen | Al-Teen
249 | Antenatal | Antenatal
250 | Anxiety | Anxiety
251 | Arthritis | Arthritis
252 | Assessment | Assessment
253 | Assistance | Assistance
254 | Asthma | Asthma
255 | ATSS | ATSS
256 | Attendant Care | Attendant Care
257 | Babies | Babies
258 | Bathroom Modificatio | Bathroom Modification
259 | Behavior | Behavior
260 | Behavior Interventi | Behavior Intervention
261 | Bereavement | Bereavement
262 | Bipolar | Bipolar
263 | Birth | Birth
264 | Birth Control | Birth Control
265 | Birthing Options | Birthing Options
266 | BIST | BIST
267 | Blood | Blood
268 | Bone | Bone
269 | Bowel | Bowel
270 | Brain | Brain
271 | Breast Feeding | Breast Feeding
272 | Breast Screen | Breast Screen
273 | Brokerage | Brokerage
274 | Cancer | Cancer
275 | Cancer Support | Cancer Support
276 | Cardiovascular Disea | Cardiovascular Disease
277 | Care Packages | Care Packages
278 | Carer | Carer
279 | Case Management | Case Management
280 | Casualty | Casualty
281 | Centrelink | Centrelink
282 | Chemists | Chemists
283 | Child And Adolescent | Child And Adolescent Mental Health Services
284 | Child Care | Child Care
285 | Child Services | Child Services
286 | Children | Children
287 | Children's Services | Children's Services
288 | Cholesterol | Cholesterol
289 | Clothing | Clothing
290 | Community Based Acco | Community Based Accommodation
291 | Community Care Unit | Community Care Unit
292 | Community Child And | Community Child And Adolescent Mental Health Services
293 | Community Health | Community Health
294 | Community Residentia | Community Residential Unit

295 | Community Transport | Community Transport
296 | Companion Visiting | Companion Visiting
297 | Companionship | Companionship
298 | Consumer Advice | Consumer Advice
299 | Consumer Issues | Consumer Issues
300 | Continuing Care Serv | Continuing Care Services
301 | Contraception Inform | Contraception Information
302 | Coordinating Bodies | Coordinating Bodies
303 | Correctional Service | Correctional Services
304 | Council Environmenta | Council Environmental Health
305 | Counselling | Counselling
306 | Criminal | Criminal
307 | Crises | Crises
308 | Crisis Assessment An | Crisis Assessment And Treatment Services (Cats)
309 | Crisis Assistance | Crisis Assistance
310 | Crisis Refuge | Crisis Refuge
311 | Day Program | Day Program
312 | Deaf | Deaf
313 | Dental Hygiene | Dental Hygiene
314 | Dentistry | Dentistry
315 | Dentures | Dentures
316 | Depression | Depression
317 | Detoxification | Detoxification
318 | Diabetes | Diabetes
319 | Diaphragm Fitting | Diaphragm Fitting
320 | Dieticians | Dieticians
321 | Disabled Parking | Disabled Parking
322 | District Nursing | District Nursing
323 | Divorce | Divorce
324 | Doctors | Doctors
325 | Drink-Drive | Drink-Drive
326 | Dual Diagnosis Servi | Dual Diagnosis Services
327 | Early Choice | Early Choice
328 | Eating Disorder | Eating Disorder
330 | Emergency Relief | Emergency Relief
331 | Employment And Train | Employment And Training
332 | Environment | Environment
333 | Equipment | Equipment
334 | Exercise | Exercise
335 | Facility | Facility
336 | Family Choice | Family Choice
337 | Family Law | Family Law
338 | Family Options | Family Options
339 | Family Services | Family Services
340 | FFYA | FFYA
341 | Financial Aid | Financial Aid
342 | Fitness | Fitness
343 | Flexible Care Packag | Flexible Care Packages
344 | Food | Food
345 | Food Vouchers | Food Vouchers
346 | Forensic Mental Heal | Forensic Mental Health Services
347 | Futures | Futures
348 | Futures For Young Ad | Futures For Young Adults
349 | General Practitioner | General Practitioners
350 | Grants | Grants
351 | Grief | Grief
352 | Grief Counselling | Grief Counselling
353 | HACC | HACC
354 | Heart Disease | Heart Disease
355 | Help | Help
356 | High Blood Pressure | High Blood Pressure
357 | Home Help | Home Help
358 | Home Nursing | Home Nursing
359 | Homefirst | Homefirst
360 | Hospice Care | Hospice Care
361 | Hospital Services | Hospital Services
362 | Hospital To Home | Hospital To Home
364 | Hostel | Hostel
365 | Hostel Accommodation | Hostel Accommodation
366 | Household Items | Household Items
367 | Hypertension | Hypertension
368 | Illness | Illness

369 | Independent Living | Independent Living
370 | Information | Information
371 | Injury | Injury
372 | Intake | Intake
373 | Intensive Mobile You | Intensive Mobile Youth Outreach Services (Imyos)
374 | Intervention | Intervention
375 | Job Searching | Job Searching
376 | Justice | Justice
377 | Leisure | Leisure
378 | Loans | Loans
379 | Low Income Earners | Low Income Earners
380 | Lung | Lung
381 | Making A Difference | Making A Difference
382 | Medical Services | Medical Services
383 | Medical Specialists | Medical Specialists
384 | Medication Administr | Medication Administration
385 | Menstrual Informatio | Menstrual Information
386 | Methadone | Methadone
387 | Mobile Support And T | Mobile Support And Treatment Services (MSTS)
388 | Motor Neurone | Motor Neurone
389 | Multiple Sclerosis | Multiple Sclerosis
390 | Neighbourhood House | Neighbourhood House
391 | Nursing Home | Nursing Home
392 | Nursing Mothers | Nursing Mothers
393 | Obesity | Obesity
394 | Occupational Health | Occupational Health & Safety
395 | Optometrist | Optometrist
396 | Oral Hygiene | Oral Hygiene
397 | Outpatients | Outpatients
398 | Outreach Service | Outreach Service
399 | PADP | PADP
400 | Pain | Pain
401 | Pap Smear | Pap Smear
402 | Parenting | Parenting
403 | Peak Organizations | Peak Organizations
404 | Personal Care | Personal Care
405 | Pharmacies | Pharmacies
406 | Phobias | Phobias
407 | Physical | Physical
408 | Physical Activity | Physical Activity
409 | Postnatal | Postnatal
410 | Pregnancy | Pregnancy
411 | Pregnancy Tests | Pregnancy Tests
412 | Preschool | Preschool
413 | Prescriptions | Prescriptions
414 | Primary Mental Healt | Primary Mental Health And Early Intervention Teams
415 | Property Maintenance | Property Maintenance
416 | Prostate | Prostate
417 | Psychiatric | Psychiatric
418 | Psychiatric Disabili | Psychiatric Disability Support Services - Home-Based Outreach
419 | Psychiatric Disabili | Psychiatric Disability Support Services - Planned Respite
420 | Psychiatric Disabili | Psychiatric Disability Support Services - Residential Rehabilitation
421 | Psychiatric Disabili | Psychiatric Disability Support Services Home-Based Outreach
422 | Psychiatric Disabili | Psychiatric Disability Support Services Mutual Support And Self Help
423 | Psychiatric Support | Psychiatric Support
424 | Recreation | Recreation
425 | Referral | Referral
426 | Refuge | Refuge
427 | Rent Assistance | Rent Assistance
428 | Residential Faciliti | Residential Facilities
429 | Residential Respite | Residential Respite
430 | Respiratory | Respiratory
431 | Response | Response
432 | Rooming Houses | Rooming Houses
433 | Safe Sex | Safe Sex
434 | Secure Extended Care | Secure Extended Care Inpatient Services
435 | Self Help | Self Help
436 | Separation | Separation
437 | Services | Services
438 | Sex Education | Sex Education
439 | Sexual Abuse | Sexual Abuse
440 | Sexual Issues | Sexual Issues

441 | Sexually Transmitted | Sexually Transmitted Diseases
442 | SIDS | SIDS
443 | Social Support | Social Support
444 | Socialisation | Socialisation
445 | Special Needs | Special Needs
446 | Speech Therapist | Speech Therapist
447 | Splinting | Splinting
448 | Sport | Sport
449 | Statewide And Specia | Statewide And Specialist Services
450 | STD | STD
451 | STI | STI
452 | Stillbirth | Stillbirth
453 | Stomal Care | Stomal Care
454 | Stroke | Stroke
455 | Substance Abuse | Substance Abuse
456 | Support | Support
457 | Syringes | Syringes
458 | Teeth | Teeth
459 | Tenancy Advice | Tenancy Advice
460 | Terminal Illness | Terminal Illness
461 | Therapy | Therapy
462 | Transcription | Transcription
463 | Translating Services | Translating Services
464 | Translator | Translator
465 | Transport | Transport
466 | Vertebrae | Vertebrae
467 | Violence | Violence
468 | Vocational Guidance | Vocational Guidance
469 | Weight | Weight
470 | Welfare Assistance | Welfare Assistance
471 | Welfare Counselling | Welfare Counselling
472 | Wheelchairs | Wheelchairs
473 | Wound Management | Wound Management
474 | Young People At Risk | Young People At Risk
475 | Further Desc. - Community Health Care | Further Description - Community Health Care
476 | Library | Library
477 | Community Hours | Community Hours
478 | Further Desc. - Specialist Medical | Further Description - Specialist Medical
479 | Hepatology | Hepatology
480 | Gastroenterology | Gastroenterology
481 | Gynaecology | Gynaecology
482 | Obstetrics | Obstetrics
483 | Further Desc. - Specialist Surgical | Further Description - Specialist Surgical
484 | Placement Protection | Placement Protection
485 | Family Violence | Family Violence
486 | Integrated Family Services | Integrated Family Services
488 | Diabetes Educator | Diabetes Educator
489 | Kinship Care | Kinship Care
490 | General Mental Health Services | General Mental Health Services
491 | Exercise Physiology | Exercise Physiology
492 | Medical Research | Medical Research
493 | Youth | Youth
494 | Youth Services | Youth Services
495 | Youth Health | Youth Health
496 | Child and Family Ser | Child and Family Services
497 | Home Visits | Home Visits
498 | Mobile Services | Mobile Services
500 | Before and/or After | Before and/or After School Care
501 | Cancer Services | Cancer Services
502 | Integrated Cancer Se | Integrated Cancer Services
503 | Multidisciplinary Se | Multidisciplinary Services
504 | Multidisciplinary Ca | Multidisciplinary Cancer Services
505 | Meetings | Meetings
506 | Blood pressure monit | Blood pressure monitoring
507 | Dose administration | Dose administration aid
508 | Medical Equipment Hi | Medical Equipment Hire
509 | Parenting/Family Support/Education | Parenting & family support/education
510 | Deputising Service | Deputising Service
513 | Cancer Support Groups | Cancer Support Groups
514 | Community Cancer Services | Community Cancer Services
530 | Disability Care Transport | Disability Care Transport
531 | Aged Care Transport | Aged Care Transport

532 | Diabetes Education s | Diabetes Education service
533 | Cardiac Rehabilitati | Cardiac Rehabilitation Service
534 | Young Adult Diabetes | Young Adult Diabetes services (YADS)
535 | Pulmonary Rehabilita | Pulmonary Rehabilitation Service
536 | Art therapy | Art therapy
537 | Medication Reviews | Medication Reviews
538 | Telephone Counselling | Telephone Counselling
539 | Telephone Help Line | Telephone Help Line
540 | Online Service | Online Service
541 | Crisis - Mental Health | Crisis - Mental Health
542 | Youth Crisis | Youth Crisis
543 | Sexual Assault | Sexual Assault
544 | GPAH Other | GPAH Other
545 | Paediatric Dermatology | Paediatric Dermatology
546 | Veterans Services | Veterans Services
547 | Veterans | Veterans
548 | Food Relief/Food/Meals | Food Relief/food/meals
550 | Dementia Care | Dementia Care
551 | Alzheimer | Alzheimer
552 | Drug and/or Alcohol Support Groups | Drug and/or alcohol support groups
553 | 1-on-1 Support /Mentoring /Coaching | One on One Support/Mentoring/Coaching
554 | Chronic Disease Management | Chronic Disease Management
555 | Liaison Services | Liaison Services
556 | Walk-in Centre /Non-Emergency | Walk in Centre / non emergency
557 | Inpatients | Inpatients
558 | Spiritual Counselling | Spiritual Counselling
559 | Women's Health | Women's Health
560 | Men's Health | Men's Health
561 | Health Education/Awareness Program | Health education/Health awareness program
562 | Test Message | Test Message
563 | Remedial Massage | Remedial Massage
564 | Adolescent Mental Health Services | Adolescent Mental Health Services
565 | Youth Drop In/Assistance/Support | Youth drop in/assistance/support
566 | Aboriginal Health Worker | Aboriginal Health Worker
567 | Women's Health Clinic | Women's Health Clinic
568 | Men's Health Clinic | Men's Health Clinic
569 | Migrant Health Clinic | Migrant Health Clinic
570 | Refugee Health Clinic | Refugee Health Clinic
571 | Aboriginal Health Clinic | Aboriginal Health Clinic
572 | Nurse Practitioner Lead Clinic/s | Nurse Practitioner lead Clinic/s
573 | Nurse Lead Clinic/s | Nurse lead Clinic/s
574 | Culturally Tailored Support Groups | Culturally tailored support groups
575 | Culturally Tailored Health Promotion | Culturally tailored health promotion
576 | Rehabilitation | Rehabilitation
577 | Education Information/Referral | Education information/referral
580 | Social Work | Social Work
581 | Haematology | Haematology
582 | Maternity Shared Car | Maternity Shared Care
583 | Rehabilitation Servi | Rehabilitation Service
584 | Cranio-sacral Therapy | Cranio-Sacral Therapy
585 | Prosthetics & Orthotics | Prosthetics & Orthotics
589 | Home Medicine Review | Home Medicine Review
590 | GPAH - Medical | GPAH - Medical
591 | Music Therapy | Music Therapy
593 | Falls Prevention | Falls Prevention
599 | Accommodation/Tenancy | Accommodation/Tenancy
600 | Assess-Skill, Ability, Needs | Assess-Skill, Ability, Needs
601 | Assist Access/Maintain Employ | Assist Access/Maintain Employ
602 | Assist Prod-Pers Care/Safety | Assist Prod-Pers Care/Safety
603 | Assist-Integrate School/Ed | Assist-Integrate School/Ed
604 | Assist-Life Stage, Transition | Assist-Life Stage, Transition
605 | Assist-Personal Activities | Assist-Personal Activities
606 | Assist-Travel/Transport | Assist-Travel/Transport
607 | Assistive Equip-General Tasks | Assistive Equip-General Tasks
608 | Assistive Equip-Recreation | Assistive Equip-Recreation
609 | Assistive Prod-Household Task | Assistive Prod-Household Task
610 | Behavior Support | Behavior Support
611 | Comms & Info Equipment | Comms & Info Equipment
612 | Community Nursing Care | Community Nursing Care
613 | Daily Tasks/Shared Living | Daily Tasks/Shared Living
614 | Development-Life Skills | Development-Life Skills
615 | Early Childhood Supports | Early Childhood Supports

616 | Equipment Special Assess Setup | Equipment Special Assess Setup
617 | Hearing Equipment | Hearing Equipment
618 | Home Modification | Home Modification
619 | Household Tasks | Household Tasks
620 | Interpret/Translate | Interpret/Translate
621 | Other Innovative Supports | Other Innovative Supports
622 | Participate Community | Participate Community
623 | Personal Mobility Equipment | Personal Mobility Equipment
624 | Physical Wellbeing | Physical Wellbeing
625 | Plan Management | Plan Management
626 | Therapeutic Supports | Therapeutic Supports
627 | Training-Travel Independence | Training-Travel Independence
628 | Vehicle modifications | Vehicle modifications
629 | Vision Equipment | Vision Equipment

See the full registry of code systems defined as part of FHIR.

Explanation of the columns that may appear on this page:

Level | A few code lists that FHIR defines are hierarchical - each code is assigned a level. See Code System for further information.
Source | The source of the definition of the code (when the value set draws in codes defined elsewhere)
Code | The code (used as the code in the resource instance). If the code is in italics, this indicates that the code is not selectable ('Abstract')
Display | The display (used in the display element of a Coding). If there is no display, implementers should not simply display the code, but map the concept into their application
Definition | An explanation of the meaning of the concept
Comments | Additional notes about how to use the code

4.3.14.57 Code System http://hl7.org/fhir/eligibilityresponse-purpose

URL: https://hl7.org/fhir/R4/codesystem-eligibilityresponse-purpose.html
Financial Management Work Group | Maturity Level: 2 | Trial Use | Use Context: Any

This is a code system defined by the FHIR project.

Summary

Defining URL: | http://hl7.org/fhir/eligibilityresponse-purpose
Version: | 4.0.1
Name: | EligibilityResponsePurpose
Title: | EligibilityResponsePurpose
Definition: | A code specifying the types of information being requested.
Committee: | Financial Management Work Group
OID: | 2.16.840.1.113883.4.642.4.1185 (for OID based terminology systems)
Source Resource | XML / JSON

This Code system is used in the following value sets:

• ValueSet: EligibilityResponsePurpose (A code specifying the types of information being requested.)
• ValueSet: EligibilityResponsePurpose (A code specifying the types of information being requested.)

4.3.14.57.1 Content

4.3.14.57.2 EligibilityResponsePurpose

A code specifying the types of information being requested.

This code system http://hl7.org/fhir/eligibilityresponse-purpose defines the following codes:

Code | Display | Definition
auth-requirements | Coverage auth-requirements | The prior authorization requirements for the listed, or discovered if specified, converages for the categories of service and/or specifed biling codes are requested.
benefits | Coverage benefits | The plan benefits and optionally benefits consumed for the listed, or discovered if specified, converages are requested.
discovery | Coverage Discovery | The insurer is requested to report on any coverages which they are aware of in addition to any specifed.
validation | Coverage Validation | A check that the specified coverages are in-force is requested.

See the full registry of code systems defined as part of FHIR.

Explanation of the columns that may appear on this page:

Level | A few code lists that FHIR defines are hierarchical - each code is assigned a level. See Code System for further information.
Source | The source of the definition of the code (when the value set draws in codes defined elsewhere)
Code | The code (used as the code in the resource instance). If the code is in italics, this indicates that the code is not selectable ('Abstract')
Display | The display (used in the display element of a Coding). If there is no display, implementers should not simply display the code, but map the concept into their application
Definition | An explanation of the meaning of the concept

Comments | Additional notes about how to use the code

4.3.14.58 Code System http://terminology.hl7.org/CodeSystem/copy-number-event

URL: https://hl7.org/fhir/R4/codesystem-copy-number-event.html
Vocabulary Work Group | Maturity Level: 0 | Informative | Use Context: Any

This is a code system defined by the FHIR project.

Summary

Defining URL: | http://terminology.hl7.org/CodeSystem/copy-number-event
Version: | 4.0.1
Name: | CopyNumberEvent
Title: | CopyNumberEvent
Definition: | Copy Number Event.
Committee: | ??
OID: | 2.16.840.1.113883.4.642.4.1087 (for OID based terminology systems)
Source Resource | XML / JSON

This Code system is used in the following value sets:

• ValueSet: CopyNumberEvent (Copy Number Event.)

• ValueSet: CopyNumberEvent (Copy Number Event.)

4.3.14.58.1 Content

4.3.14.58.2 CopyNumberEvent

Copy Number Event.

This code system http://terminology.hl7.org/CodeSystem/copy-number-event defines the following codes:

Code | Display | Definition
amp | amplification | amplification.
del | deletion | deletion.
lof | loss of function | loss of function.

See the full registry of code systems defined as part of FHIR.

Explanation of the columns that may appear on this page:

Level | A few code lists that FHIR defines are hierarchical - each code is assigned a level. See Code System for further information.
Source | The source of the definition of the code (when the value set draws in codes defined elsewhere)
Code | The code (used as the code in the resource instance). If the code is in italics, this indicates that the code is not selectable ('Abstract')
Display | The display (used in the display element of a Coding). If there is no display, implementers should not simply display the code, but map the concept into their application
Definition | An explanation of the meaning of the concept
Comments | Additional notes about how to use the code

4.3.14.59 Code System http://terminology.hl7.org/CodeSystem/ex-diagnosis-on-admission

URL: https://hl7.org/fhir/R4/codesystem-ex-diagnosis-on-admission.html
Financial Management Work Group | Maturity Level: 1 | Draft | Use Context: Any

This is a code system defined by the FHIR project.

Summary

Defining URL: | http://terminology.hl7.org/CodeSystem/ex-diagnosis-on-admission
Version: | 4.0.1
Name: | ExampleDiagnosisOnAdmissionCodes
Title: | Example Diagnosis on Admission Codes
Definition: | This value set includes example Diagnosis on Admission codes.
Committee: | Financial Management Work Group
OID: | 2.16.840.1.113883.4.642.4.1170 (for OID based terminology systems)
Copyright: | These codes have been appropriated from the UB04 code set owned and managed by the AHA . Users require a license from the AHA in order to use these codes. Note: the codes have been withdrawn in a later version
Source Resource | XML / JSON

This Code system is used in the following value sets:

• ValueSet: Example Diagnosis on Admission Codes (This value set includes example Diagnosis on Admission codes.)

• ValueSet: Example Diagnosis on Admission Codes (This value set includes example Diagnosis on Admission codes.)

4.3.14.59.1 Content

4.3.14.59.2 Example Diagnosis on Admission Codes

This value set includes example Diagnosis on Admission codes.

Copyright Statement:

These codes have been appropriated from the UB04 code set owned and managed by the AHA . Users require a license from the AHA in order to use these codes. Note: the codes have been withdrawn in a later version

This code system http://terminology.hl7.org/CodeSystem/ex-diagnosis-on-admission defines the following codes:

Code | Display | Definition
y | Yes | Diagnosis was present at time of inpatient admission.
n | No | Diagnosis was not present at time of inpatient admission.
u | Unknown | Documentation insufficient to determine if condition was present at the time of inpatient admission.
w | Undetermined | Clinically undetermined. Provider unable to clinically determine whether the condition was present at the time of inpatient admission.

See the full registry of code systems defined as part of FHIR.

Explanation of the columns that may appear on this page:

Level | A few code lists that FHIR defines are hierarchical - each code is assigned a level. See Code System for further information.
Source | The source of the definition of the code (when the value set draws in codes defined elsewhere)
Code | The code (used as the code in the resource instance). If the code is in italics, this indicates that the code is not selectable ('Abstract')
Display | The display (used in the display element of a Coding). If there is no display, implementers should not simply display the code, but map the concept into their application
Definition | An explanation of the meaning of the concept
Comments | Additional notes about how to use the code

4.3.14.60 Code System http://hl7.org/fhir/task-status

URL: https://hl7.org/fhir/R4/codesystem-task-status.html
Orders and Observations Work Group | Maturity Level: 2 | Trial Use | Use Context: Any

This is a code system defined by the FHIR project.

Summary

Defining URL: | http://hl7.org/fhir/task-status
Version: | 4.0.1
Name: | TaskStatus
Title: | TaskStatus
Definition: | The current status of the task.
Committee: | Orders and Observations Work Group
OID: | 2.16.840.1.113883.4.642.4.791 (for OID based terminology systems)
Source Resource | XML / JSON

This Code system is used in the following value sets:

• ValueSet: TaskStatus (The current status of the task.)

• ValueSet: TaskStatus (The current status of the task.)

4.3.14.60.1 Content

4.3.14.60.2 TaskStatus

The current status of the task.

This code system http://hl7.org/fhir/task-status defines the following codes:

Code | Display | Definition
draft | Draft | The task is not yet ready to be acted upon.
requested | Requested | The task is ready to be acted upon and action is sought.
received | Received | A potential performer has claimed ownership of the task and is evaluating whether to perform it.
accepted | Accepted | The potential performer has agreed to execute the task but has not yet started work.
rejected | Rejected | The potential performer who claimed ownership of the task has decided not to execute it prior to performing any action.
ready | Ready | The task is ready to be performed, but no action has yet been taken. Used in place of requested/received/accepted/rejected when request assignment and acceptance is a given.
cancelled | Cancelled | The task was not completed.
in-progress | In Progress | The task has been started but is not yet complete.
on-hold | On Hold | The task has been started but work has been paused.
failed | Failed | The task was attempted but could not be completed due to some error.
completed | Completed | The task has been completed.
entered-in-error | Entered in Error | The task should never have existed and is retained only because of the possibility it may have used.

See the full registry of code systems defined as part of FHIR.

Explanation of the columns that may appear on this page:

Level | A few code lists that FHIR defines are hierarchical - each code is assigned a level. See Code System for further information.
Source | The source of the definition of the code (when the value set draws in codes defined elsewhere)
Code | The code (used as the code in the resource instance). If the code is in italics, this indicates that the code is not selectable ('Abstract')
Display | The display (used in the display element of a Coding). If there is no display, implementers should not simply display the code, but map the concept into their application
Definition | An explanation of the meaning of the concept
Comments | Additional notes about how to use the code

4.3.14.61 Code System http://terminology.hl7.org/CodeSystem/operation-outcome

URL: https://hl7.org/fhir/R4/codesystem-operation-outcome.html
FHIR Infrastructure Work Group | Maturity Level: 1 | Draft | Use Context: Any

This is a code system defined by the FHIR project.

Summary

Defining URL: | http://terminology.hl7.org/CodeSystem/operation-outcome
Version: | 4.0.1
Name: | OperationOutcomeCodes
Title: | Operation Outcome Codes
Definition: | Operation Outcome codes used by FHIR test servers (see Implementation file translations.xml)
Committee: | FHIR Infrastructure Work Group
OID: | 2.16.840.1.113883.4.642.4.1127 (for OID based terminology systems)
Source Resource | XML / JSON

This Code system is used in the following value sets:

• ValueSet: Operation Outcome Codes (Operation Outcome codes used by FHIR test servers (see Implementation file translations.xml))

• ValueSet: Operation Outcome Codes (Operation Outcome codes used by FHIR test servers (see Implementation file translations.xml))

4.3.14.61.1 Content

• All Languages
• English
• Spanish
• French
• Italian
• Nederlands (Dutch)
• Polskie (Polish)
• Русский (Russian)
• □□ (Chinese)

This code system http://terminology.hl7.org/CodeSystem/operation-outcome defines the following codes:

Code | Display | Definition
DELETE_MULTIPLE_MATCHES | en: Error: Multiple matches exist for the conditional delete nl: Fout: er is meer dan één resultaat voor de conditionele delete
MSG_AUTH_REQUIRED | en: You must authenticate before you can use this service it: Autenticazione richiesta prima di usare questo servizio pl: Wymagana autentykacja przed użyciem tego serwisu fr: Vous devez être authentifié avant de pouvoir utiliser ce service nl: U moet zich authenticeren voor gebruik van deze service zh: □□□□□□□□□ es: Debe autenticarse antes de poder usar este servicio
MSG_BAD_FORMAT | en: Bad Syntax: "%s" must be a %s' ru: Неверный синтакс: "%s" должен быть %s it: Sintassi Errata: "%s" deve essere un %s' pl: Błąd składni: "%s" powinno być %s' fr: Erreur de Syntaxe : "%s" doit être un %s nl: Verkeerde syntax: "%s" moet een %s zijn zh: □□□□: "%s" □□□□□ %s' es: Sintaxis Incorrecta: "%s" debe de ser un %s'
MSG_BAD_SYNTAX | en: Bad Syntax in %s ru: Неверный синтакс: %s it: Sintassi errata in %s pl: Błąd składni w %s fr: Erreur de Syntaxe dans %s nl: Verkeerde syntax in %s zh: %s □□□□□ es: Sintaxis Incorrecta en %s
MSG_CANT_PARSE_CONTENT | en: Unable to parse feed (entry content type = "%s") it: Impossibile effettuare il parsing del feed (tipo del contenuto della entry = "%s") pl: Błąd parsowania (typ zawartości wejściowej = "%s") fr: Impossible d'analyser le flux (type de contenu de l'entrée = "%s") nl: Kan feed niet verwerken (contenttype inhoud = "%s") zh: □□□□feed (□□□□□□□ = "%s") es: No se pudo parsear el feed (el tipo de contenido de la entry = "%s")
MSG_CANT_PARSE_ROOT | en: Unable to parse feed (root element name = "%s") ru: Не удалось разобрать данные (корневой элемент = "%s") it: Impossibile effettuare il parsing del feed (nome elemento root = "%s") pl: Błąd parsowania (nazwa elementu root = "%s") fr: Impossible d'analyser le flux (nom de l'élément racine = "%s") nl: Kan feed niet verwerken (rootelementnaam = "%s") zh: □□□□feed (□□□□ = "%s") es: No se pudo parsear el feed (nombre del elemento raiz = "%s")
MSG_CREATED | en: New resource created nl: Nieuwe resource gemaakt

MSG_DATE_FORMAT | en: The Date value %s is not in the correct format (Xml Date Format required) ru: Значение Date %s в неверном формате (требуется Xml Date формат) it: Il valore %s per la data non è nel formato corretto (richiesto il Formato Data Xml) pl: Niepoprawny format wartości daty %s (wymagany format XML) fr: Le format de la date %s est incorrect (format Date Xml attendu) nl: De Datum-waarde %s heeft niet de juiste structuur (Xml Date vereist) zh: □□□□ %s □□□□□ (□□□Xml Date□□) es: El valor de la fecha %s no está en el formato correcto (se requiere un formato de fecha Xml)

MSG_DELETED | en: This resource has been deleted ru: Данный ресурс был удалён it: Questa risorsa è stata cancellata pl: Ten zasób został usunięty fr: La ressource a été supprimée nl: Deze resource is verwijderd zh: □□□□□□ es: Este recurso ha sido borrado

MSG_DELETED_DONE | en: Resource deleted ru: Ресурс удалён it: Risorsa cancellata pl: Zasób usunięto fr: Ressource supprimée nl: Resource verwijderd zh: □□□□□ es: Recurso borrado

MSG_DELETED_ID | en: The resource "%s" has been deleted ru: Ресурс "%s" был удалён it: La risorsa "%s" è stata eliminata pl: Zasób "%s" został usunięty fr: La ressource "%s" a été supprimée nl: De resource "%s" is verwijderd zh: □□ "%s" □□□□ es: El recurso "%s" ha sido borrado

MSG_DUPLICATE_ID | en: Duplicate Id %s for resource type %s ru: Дублирующий Id %s для типа ресурса %s it: Id %s duplicato per il tipo di risorsa %s pl: Zdublowany identyfikator %s dla zasobu typu %s fr: Id %s en double pour le type de ressource %s nl: Duplicaat-id %s voor resourcetype %s zh: ID %s □□□□□□□ %s□ es: Id %s duplicada para el recurso de tipo %s

MSG_ERROR_PARSING | en: Error parsing resource Xml (%s) ru: Ошибка синтаксического разбора ресурса Xml (%s) it: Errore nel parsing della risorsa Xml (%s) pl: Błąd w trakcie parsowania zasobu XML (%s) fr: Erreur d'analyse de la ressource Xml (%s) nl: Fout in verwerking resource Xml (%s) zh: □□□□Xml□□□ (%s) es: Error parseando el recurso Xml (%s)

MSG_ID_INVALID | en: Id "%s" has an invalid character "%s" ru: Id "%s" содержит недопустимые символы "%s" it: L''Id "%s" ha un carattere non valido: "%s" pl: Identyfikator "%s" zawiera niepoprawny znak "%s" fr: Id "%s" possède un caractère invalide "%s" nl: Id "%s" heeft een ongeldig teken "%s" zh: ID "%s" □□□□□□: "%s" es: El Id "%s" contiene el caracter inválido "%s"

MSG_ID_TOO_LONG | en: Id "%s" too long (length limit 36) ru: Недопустимая длина Id "%s" (ограничение 36) it: Id "%s" troppo lunga (limite di lunghezza: 36) pl: Identyfikator "%s" jest zbyt długi (limit długości 36) fr: Id "%s" trop long (la longueur limite est 36) nl: Id "%s" te lang (max lengte 36) zh: Id "%s" □□ (□□□□: 36) es: El Id "%s" es demasiado largo (limite de longitud: 36)

MSG_INVALID_ID | en: Id not accepted ru: Id не принято it: Id non accettato pl: Identyfikator nie zaakceptowany fr: Id non accepté nl: Id niet geaccepteerd zh: Id□□□□ es: Id no aceptada

MSG_JSON_OBJECT | en: Json Source for a resource should start with an object ru: Json Source для ресурса должен начинаться с объекта it: Il sorgente Json di una risorsa dovrebbe iniziare con un oggetto pl: Źródło json dla zasobu powinno rozpoczynać się od obiektu fr: La source Json pour une ressource doit commencer par un objet nl: Json Source van een resource moeten beginnen met een object zh: □□□Json□□□□□object□□ es: La fuente Json para un recurso debería empezar con un objeto

MSG_LOCAL_FAIL | en: Unable to resolve local reference to resource %s ru: Невозможно определить локальную ссылку на ресурс %s it: Impossibile risolvere il riferimento locale alla risorsa %s pl: Zasób wskazywany przez loklaną referencję %s nie został odnaleziony fr: Impossible de résourdre la référence locale à la ressource %s nl: De resource met lokale referentie %s is niet gevonden zh: □□□□□□□ %s □□□□□ es: Imposible resolver la referencia al recurso %s

MSG_NO_EXIST | en: Resource Id "%s" does not exist ru: Ресурс Id "%s" не существует it: La risorsa con Id "%s" non esiste pl: Zasób o identyfikatorze "%s" nie istnieje fr: La ressource avec l'Id "%s" n'existe pas nl: Resource-id "%s" bestaat niet zh: □□Id "%s"□□□ es: El recurso con Id "%s" no existe

MSG_NO_MATCH | en: No Resource found matching the query "%s" it: Nessuna Risorsa soddisfa la query "%s" nl: Geen resource gevonden met query "%s"

MSG_NO_MODULE | en: No module could be found to handle the request "%s" ru: Модуль для обработки запроса "%s" не найден it: Impossibile trovare un modulo per gestire la richiesta "%s" pl: Nie można odnaleźć modułu, aby obsłużyć żądanie "%s" fr: Aucun module disponible pour traiter la requête "%s" nl: Er kon geen module worden gevonden om verzoek "%s" te verwerken zh: □□□□□□□□"%s"□□□ es: No se encontró un modulo que gestione la petición "%s"

MSG_NO_SUMMARY | en: No Summary for this resource ru: Отсутствует Summary для данного ресурса it: Nessun riepilogo per questa risorsa pl: Brak podsumowania (Summary) dla tego zasobu fr: Aucun résumé disponible pour cette ressource nl: Geen samenvatting voor deze resource zh: □□□□summary es: No existe un resumen para este recurso

MSG_OP_NOT_ALLOWED | en: Operation %s not allowed for resource %s (due to local configuration) ru: Операция %s недопустима для ресурса %s (по причине локальной конфигурации) it: Operazione %s non consentita per la risorsa %s (a causa di configurazioni locali) pl: Niedozwolona operacja %s dla zasobu %s (ze względu na lokalną konfigurację) fr: L'opération %s n'est pas permise pour la ressource %s (à cause de la configuration locale) nl: Bewerking %s niet toegestaan voor resource %s (vanwege lokale configuratie) zh: □□ %s □□□□□□□□ %s (□□□□□□) es: Operación %s no permitida para el recurso %s (debido a la configuración local)

MSG_PARAM_CHAINED | en: Unknown chained parameter name "%s" ru: Неизвестое вложенное наименование параметра "%s" it: Nome di parametro concatenato sconosciuto: "%s" pl: Nieznana nazwa parametru powiązanego "%s" fr: Nom du paramètre chainé inconnu : "%s" nl: Onbekende geschakelde parameternaam "%s" zh: □□□□□□□□: "%s" es: Nombre de parametro encadenado desconocido: "%s"

MSG_PARAM_INVALID | en: Parameter "%s" content is invalid it: Il contenuto del Parametro "%s" non è valido nl: Waarde van parameter "%s" is ongeldig

MSG_PARAM_MODIFIER_INVALID | en: Parameter "%s" modifier is invalid nl: Modifier van parameter "%s" is ongeldig

MSG_PARAM_NO_REPEAT | en: Parameter "%s" is not allowed to repeat ru: Параметр "%s" не может быть повторён it: Non &#65533; consentito ripetere il parametro "%s" pl: Parametr "%s" nie może zostać powtórzony fr: Le paramètre "%s" ne peut pas être répété nl: Parameter "%s" mag niet herhalen zh: □□"%s"□□□□ es: No se permite la repetición del parámetro "%s"

MSG_PARAM_UNKNOWN | en: Parameter "%s" not understood ru: Параметр "%s" не понят it: Parametro "%s" non riconosciuto pl: Niezrozumiały parametr "%s" fr: Paramètre "%s" non reconnu nl: Parameter "%s" onbekend zh: □□□□□□"%s" es: Parámetro "%s" no reconocido

MSG_RESOURCE_EXAMPLE_PROTECTED | en: Resources with identity "example" cannot be deleted (for testing/training purposes) ru: Ресурс с идентификатором "example" не может быть удалён (для случаев тестирования/обучения) it: Le Risorse aventi l'identità "example" non possono essere cancellate (per finalità di test/formazione) pl: Zasoby oznaczone jako "example" nie mogą zostać usunięte (dla celów testów/szkoleń) fr: Les ressources ayant l'identité "example" ne peuvent pas être supprimées (utilisées pour les tests/formations) nl: Resources met identiteit "voorbeeld" kunnen niet worden verwijderd (ten behoeve van testen/training) zh: □"example" □ID□□□□□□□□ (□□□□/□□) es: Recursos con la identidad "example" no pueden ser borrados (son usados para pruebas/entrenamiento)

MSG_RESOURCE_ID_FAIL | en: unable to allocate resource id ru: невозможно выделить идентификатор ресурса it: impossibile allocare l''id della risorsa pl: nie można nadać identyfikatora zasobu fr: impossible d'allouer l'id de la ressource nl: kan geen resource-id reserveren zh: □□□□□□ID es: imposible encontrar el id del recurso

MSG_RESOURCE_ID_MISMATCH | en: Resource Id Mismatch fr: Problème de correspondance d'Id de la Ressource nl: Resource ID's komen niet overeen

MSG_RESOURCE_ID_MISSING | en: Resource Id Missing it: Id della Risorsa mancante fr: Id de la Ressource manquante nl: Resource ID ontbreekt

MSG_RESOURCE_NOT_ALLOWED | en: Not allowed to submit a resource for this operation ru: Для данной операции отправка ресурса недопустима it: Non è consentito sottomettere una risorsa per questa operazione pl: Nie można zgłosić zasobu dla tej operacji fr: Non autorisé à soumettre une ressource pour cette opération nl: Niet toegestaan om een resource in te dienen voor deze bewerking zh: □□□□□□□□□□ es: No se permite el envío de un recurso para esta operación

MSG_RESOURCE_REQUIRED | en: A resource is required ru: Требуется ресурс it: E'' richiesta una risorsa pl: Zasób jest wymagany fr: Une ressource est requise nl: Een resource is verplicht zh: □□□□□□□□ es: Se requiere un recurso

MSG_RESOURCE_TYPE_MISMATCH | en: Resource Type Mismatch ru: Несоответствие типа ресурса it: Tipo Risorsa non corrispondente pl: Niepoprawny typ zasobu fr: Type de ressource incorrect nl: Verkeerd resourcetype zh: □□□□□□□ es: Los Tipos de los recursos no coinciden

MSG_SORT_UNKNOWN | en: Unknown sort parameter name "%s" ru: Неизвестное имя параметра сортировки "%s" it: Nome del parametro di ordinamento "%s" non riconosciuto pl: Nieznany parametr sortowania "%s" fr: Nom du paramètre de tri inconnu "%s" nl: Onbekende parameternaam "%s" voor sortering zh: □□□□□□□□□"%s" es: Nombre del parámetro de ordenación "%s" desconocido

MSG_TRANSACTION_DUPLICATE_ID | en: Duplicate Identifier in transaction: %s ru: Дублирующий идентификатор в транзакции: %s pl: Zdublowany identyfikator w transakcji: %s fr: Identifiant en double dans la transaction : %s nl: Dubbele identificatie in transactie: %s zh: □□□□□□□Id: %s es: Identificador duplicado en la transacción: %s

MSG_TRANSACTION_MISSING_ID | en: Missing Identifier in transaction - an entry.id must be provided ru: Отсутствует идентификатор в транзакции - требуется entry.id pl: Brak identyfikatora w transakcji - należy podać entry.id fr: Identifiant manquant dans la transaction - un élément entry.id doit être fourni nl: Ontbrekende identificatie in transactie - entry.id is verplicht zh: □□□□□Id - □□□□□□entry.id es: Identificador de la transacción no encontrado - se debe proporcionar un entry.id

MSG_UNHANDLED_NODE_TYPE | en: Unhandled xml node type "%s" ru: Не обработанный xml узел "%s" it: Tipo di nodo Xml non gestito "%s" pl: Nieobsługiwany typ węzła XML "%s" fr: Type de noeud xml "%s" non traité nl: Kan xml nodetype "%s" niet verwerken zh: □□□□XML□□□□"%s" es: Tipo de nodo Xml no soportado "%s"

MSG_UNKNOWN_CONTENT | en: Unknown Content (%s) at %s ru: Неизвестный контент (%s) в %s it: Contenuto Sconosciuto (%s) at %s pl: Nieznana zawartość (%s) dla %s fr: Contenu inconnu (%s) à %s nl: Onbekende content (%s) at %s zh: □□□□ (%s) □□ %s es: Contenido desconocido (%s) en %s

MSG_UNKNOWN_OPERATION | en: unknown FHIR http operation ru: неизвестная операция FHIR http it: operazione http FHIR sconosciuta pl: nieznana operacja FHIR http fr: operation http FHIR inconnue nl: onbekende FHIR http operation zh: □□□FHIR HTTP□□ es: Operación http FHIR desconocida

MSG_UNKNOWN_TYPE | en: Resource Type "%s" not recognised ru: Тип ресурса "%s" не распознан it: Tipo di Risorsa "%s" non riconosciuto pl: Nie rozpoznany typ zasobu: "%s" fr: Type de ressource "%s" non reconnu nl: Resourcetype "%s" niet herkend zh: □□□□"%s"□□□ es: Tipo de Recurso "%s" no reconocido

MSG_UPDATED | en: existing resource updated ru: существующий ресурс обновлён it: risorsa esistente aggiornata pl: uaktualniono istniejący zasób fr: ressource existante mise à jour nl: bestaande resource updated zh: □□□□□□□ es: Recurso existente actualizado

MSG_VERSION_AWARE | en: Version aware updates are required for this resource ru: Для данного ресурса необходимы обновления с учётом версии it: Questa risorsa richiede aggiornamenti per versione pl: Uaktualnienia zakładające wersjonowanie są wymagane dla tego zasobu fr: Des mises à jour en relation avec la version sont requises pour cette ressource nl: Versie-bewuste updates zijn vereist voor deze resource zh: □□□□□□□□□□□□ es: Este recurso requiere actualizaciones en base a versiones

MSG_VERSION_AWARE_CONFLICT | en: Update Conflict (server current version = "%s", client version referenced = "%s") ru: Конфликт обновления (текущая версия сервера = "%s", указанная версия клиента = "%s") it: Conflitto nell''aggiornamento (attuale = "%s", quotato = "%s") pl: Konflikt podczas uaktualnienia (obecna wersja na serwerze = "%s", wersja wskazana przez klienta = "%s") fr: Conflit de mise à jour (version courante du serveur = "%s", version référencée du client = "%s") nl: Updateconflict (huidige serverversie = "%s", opgegeven clientversie = "%s") zh: □□□□ (□□□□□□□ = "%s", □□□□□□□□ = "%s") es: Conflicto de actualizaciones (versión actual del servidor = "%s", versión del cliente referenciada = "%s")

MSG_VERSION_AWARE_URL | en: Version specific URL not recognised ru: URL для указанной версии не распознан it: URL specifico alla versione non riconosciuto pl: Nie rozpoznany URL specyficzny dla wersji fr: URL spécifique à une version non reconnue nl: Versie-specifieke URL niet herkend zh: □□□□□□□□URL es: URL especifica de la versión no reconocida

MSG_WRONG_NS | en: This does not appear to be a FHIR element or resource (wrong namespace "%s") nl: Dit lijkt geen FHIR element of resource te zijn (verkeerde namespace "%s")

SEARCH_MULTIPLE | en: Error: Multiple matches exist for %s search parameters "%s" ru: Ошибка: множественные совпадения для %s с параметрами поиска "%s" it: Errore: Trovate corrispondenze multiple per %s parametri di ricerca "%s" pl: Błąd: Istnieją wielokrotne dopasowania dla %s parametrów wyszukiwania "%s" fr: Erreur : Plusieurs correspondances existent pour ce paramètre de recherche %s nl: Fout: er is meer dan één resultaat voor %s zoekparameters "%s" zh: □□: □□ %s □□□□□ "%s"□□□□□□ es: Error: Multiples ocurrencias existen para %s parametros de búsqueda "%s"

SEARCH_NONE | en: Error: no processable search found for %s search parameters "%s" ru: Ошибка: обрабатываемых результатов поиска для %s с параметрами поиска "%s" не найдено it: Errore: non è stato trovato alcun parametro di ricerca processabile per %s parametri di ricerca "%s" pl: Błąd: Niewykonalne wyszukiwanie dla %s parametrów wyszukiwania "%s" fr: Erreur : aucune recherche trouvée pour les paramètres %s "%s" nl: Fout: geen verwerkbare zoekactie gevonden voor %s zoekparameters "%s" zh: □□: □%s□□□□"%s"□□□□□□□□□ es: Error: no se encontro una búsqueda apropiada para %s parametros de búsqueda "%s"

UPDATE_MULTIPLE_MATCHES | en: Error: Multiple matches exist for the conditional update nl: Fout: er is meer dan één resultaat voor de conditionele update

This code system http://terminology.hl7.org/CodeSystem/operation-outcome defines the following codes:

Code | Display | Definition

DELETE_MULTIPLE_MATCHES | Error: Multiple matches exist for the conditional delete

MSG_AUTH_REQUIRED | You must authenticate before you can use this service

MSG_BAD_FORMAT | Bad Syntax: "%s" must be a %s'

MSG_BAD_SYNTAX | Bad Syntax in %s

MSG_CANT_PARSE_CONTENT | Unable to parse feed (entry content type = "%s")

MSG_CANT_PARSE_ROOT | Unable to parse feed (root element name = "%s")

MSG_CREATED | New resource created

MSG_DATE_FORMAT | The Date value %s is not in the correct format (Xml Date Format required)

MSG_DELETED | This resource has been deleted
MSG_DELETED_DONE | Resource deleted
MSG_DELETED_ID | The resource "%s" has been deleted
MSG_DUPLICATE_ID | Duplicate Id %s for resource type %s
MSG_ERROR_PARSING | Error parsing resource Xml (%s)
MSG_ID_INVALID | Id "%s" has an invalid character "%s"
MSG_ID_TOO_LONG | Id "%s" too long (length limit 36)
MSG_INVALID_ID | Id not accepted
MSG_JSON_OBJECT | Json Source for a resource should start with an object
MSG_LOCAL_FAIL | Unable to resolve local reference to resource %s
MSG_NO_EXIST | Resource Id "%s" does not exist
MSG_NO_MATCH | No Resource found matching the query "%s"
MSG_NO_MODULE | No module could be found to handle the request "%s"
MSG_NO_SUMMARY | No Summary for this resource
MSG_OP_NOT_ALLOWED | Operation %s not allowed for resource %s (due to local configuration)
MSG_PARAM_CHAINED | Unknown chained parameter name "%s"
MSG_PARAM_INVALID | Parameter "%s" content is invalid
MSG_PARAM_MODIFIER_INVALID | Parameter "%s" modifier is invalid
MSG_PARAM_NO_REPEAT | Parameter "%s" is not allowed to repeat
MSG_PARAM_UNKNOWN | Parameter "%s" not understood
MSG_RESOURCE_EXAMPLE_PROTECTED | Resources with identity "example" cannot be deleted (for testing/training purposes)
MSG_RESOURCE_ID_FAIL | unable to allocate resource id
MSG_RESOURCE_ID_MISMATCH | Resource Id Mismatch
MSG_RESOURCE_ID_MISSING | Resource Id Missing
MSG_RESOURCE_NOT_ALLOWED | Not allowed to submit a resource for this operation
MSG_RESOURCE_REQUIRED | A resource is required
MSG_RESOURCE_TYPE_MISMATCH | Resource Type Mismatch
MSG_SORT_UNKNOWN | Unknown sort parameter name "%s"
MSG_TRANSACTION_DUPLICATE_ID | Duplicate Identifier in transaction: %s
MSG_TRANSACTION_MISSING_ID | Missing Identifier in transaction - an entry.id must be provided
MSG_UNHANDLED_NODE_TYPE | Unhandled xml node type "%s"
MSG_UNKNOWN_CONTENT | Unknown Content (%s) at %s
MSG_UNKNOWN_OPERATION | unknown FHIR http operation
MSG_UNKNOWN_TYPE | Resource Type "%s" not recognised
MSG_UPDATED | existing resource updated
MSG_VERSION_AWARE | Version aware updates are required for this resource
MSG_VERSION_AWARE_CONFLICT | Update Conflict (server current version = "%s", client version referenced = "%s")
MSG_VERSION_AWARE_URL | Version specific URL not recognised
MSG_WRONG_NS | This does not appear to be a FHIR element or resource (wrong namespace "%s")
SEARCH_MULTIPLE | Error: Multiple matches exist for %s search parameters "%s"
SEARCH_NONE | Error: no processable search found for %s search parameters "%s"
UPDATE_MULTIPLE_MATCHES | Error: Multiple matches exist for the conditional update

This code system http://terminology.hl7.org/CodeSystem/operation-outcome defines the following codes:

Code | Display | Definition
DELETE_MULTIPLE_MATCHES
MSG_AUTH_REQUIRED | Debe autenticarse antes de poder usar este servicio
MSG_BAD_FORMAT | Sintaxis Incorrecta: "%s" debe de ser un %s'
MSG_BAD_SYNTAX | Sintaxis Incorrecta en %s
MSG_CANT_PARSE_CONTENT | No se pudo parsear el feed (el tipo de contenido de la entry = "%s")
MSG_CANT_PARSE_ROOT | No se pudo parsear el feed (nombre del elemento raiz = "%s")
MSG_CREATED
MSG_DATE_FORMAT | El valor de la fecha %s no está en el formato correcto (se requiere un formato de fecha Xml)
MSG_DELETED | Este recurso ha sido borrado
MSG_DELETED_DONE | Recurso borrado
MSG_DELETED_ID | El recurso "%s" ha sido borrado
MSG_DUPLICATE_ID | Id %s duplicada para el recurso de tipo %s
MSG_ERROR_PARSING | Error parseando el recurso Xml (%s)
MSG_ID_INVALID | El Id "%s" contiene el caracter inválido "%s"
MSG_ID_TOO_LONG | El Id "%s" es demasiado largo (limite de longitud: 36)
MSG_INVALID_ID | Id no aceptada
MSG_JSON_OBJECT | La fuente Json para un recurso debería empezar con un objeto
MSG_LOCAL_FAIL | Imposible resolver la referencia al recurso %s
MSG_NO_EXIST | El recurso con Id "%s" no existe
MSG_NO_MATCH
MSG_NO_MODULE | No se encontró un modulo que gestione la petición "%s"
MSG_NO_SUMMARY | No existe un resumen para este recurso
MSG_OP_NOT_ALLOWED | Operación %s no permitida para el recurso %s (debido a la configuración local)
MSG_PARAM_CHAINED | Nombre de parametro encadenado desconocido: "%s"
MSG_PARAM_INVALID
MSG_PARAM_MODIFIER_INVALID
MSG_PARAM_NO_REPEAT | No se permite la repetición del parámetro "%s"

MSG_PARAM_UNKNOWN | Parámetro "%s" no reconocido
MSG_RESOURCE_EXAMPLE_PROTECTED | Recursos con la identidad "example" no pueden ser borrados (son usados para pruebas/entrenamiento)
MSG_RESOURCE_ID_FAIL | imposible encontrar el id del recurso
MSG_RESOURCE_ID_MISMATCH
MSG_RESOURCE_ID_MISSING
MSG_RESOURCE_NOT_ALLOWED | No se permite el envío de un recurso para esta operación
MSG_RESOURCE_REQUIRED | Se requiere un recurso
MSG_RESOURCE_TYPE_MISMATCH | Los Tipos de los recursos no coinciden
MSG_SORT_UNKNOWN | Nombre del parámetro de ordenación "%s" desconocido
MSG_TRANSACTION_DUPLICATE_ID | Identificador duplicado en la transacción: %s
MSG_TRANSACTION_MISSING_ID | Identificador de la transacción no encontrado - se debe proporcionar un entry.id
MSG_UNHANDLED_NODE_TYPE | Tipo de nodo Xml no soportado "%s"
MSG_UNKNOWN_CONTENT | Contenido desconocido (%s) en %s
MSG_UNKNOWN_OPERATION | Operación http FHIR desconocida
MSG_UNKNOWN_TYPE | Tipo de Recurso "%s" no reconocido
MSG_UPDATED | Recurso existente actualizado
MSG_VERSION_AWARE | Este recurso requiere actualizaciones en base a versiones
MSG_VERSION_AWARE_CONFLICT | Conflicto de actualizaciones (versión actual del servidor = "%s", versión del cliente referenciada = "%s")
MSG_VERSION_AWARE_URL | URL especifica de la versión no reconocida
MSG_WRONG_NS
SEARCH_MULTIPLE | Error: Multiples ocurrencias existen para %s parametros de búsqueda "%s"
SEARCH_NONE | Error: no se encontro una búsqueda apropiada para %s parametros de búsqueda "%s"
UPDATE_MULTIPLE_MATCHES

This code system http://terminology.hl7.org/CodeSystem/operation-outcome defines the following codes:

Code | Display | Definition
DELETE_MULTIPLE_MATCHES
MSG_AUTH_REQUIRED | Vous devez être authentifié avant de pouvoir utiliser ce service
MSG_BAD_FORMAT | Erreur de Syntaxe : "%s" doit être un %s
MSG_BAD_SYNTAX | Erreur de Syntaxe dans %s
MSG_CANT_PARSE_CONTENT | Impossible d'analyser le flux (type de contenu de l'entrée = "%s")
MSG_CANT_PARSE_ROOT | Impossible d'analyser le flux (nom de l'élément racine = "%s")
MSG_CREATED
MSG_DATE_FORMAT | Le format de la date %s est incorrect (format Date Xml attendu)
MSG_DELETED | La ressource a été supprimée
MSG_DELETED_DONE | Ressource supprimée
MSG_DELETED_ID | La ressource "%s" a été supprimée
MSG_DUPLICATE_ID | Id %s en double pour le type de ressource %s
MSG_ERROR_PARSING | Erreur d'analyse de la ressource Xml (%s)
MSG_ID_INVALID | Id "%s" possède un caractère invalide "%s"
MSG_ID_TOO_LONG | Id "%s" trop long (la longueur limite est 36)
MSG_INVALID_ID | Id non accepté
MSG_JSON_OBJECT | La source Json pour une ressource doit commencer par un objet
MSG_LOCAL_FAIL | Impossible de résourdre la référence locale à la ressource %s
MSG_NO_EXIST | La ressource avec l'Id "%s" n'existe pas
MSG_NO_MATCH
MSG_NO_MODULE | Aucun module disponible pour traiter la requête "%s"
MSG_NO_SUMMARY | Aucun résumé disponible pour cette ressource
MSG_OP_NOT_ALLOWED | L'opération %s n'est pas permise pour la ressource %s (à cause de la configuration locale)
MSG_PARAM_CHAINED | Nom du paramètre chainé inconnu : "%s"
MSG_PARAM_INVALID
MSG_PARAM_MODIFIER_INVALID
MSG_PARAM_NO_REPEAT | Le paramètre "%s" ne peut pas être répété
MSG_PARAM_UNKNOWN | Paramètre "%s" non reconnu
MSG_RESOURCE_EXAMPLE_PROTECTED | Les ressources ayant l'identité "example" ne peuvent pas être supprimées (utilisées pour les tests/formations)
MSG_RESOURCE_ID_FAIL | impossible d'allouer l'id de la ressource
MSG_RESOURCE_ID_MISMATCH | Problème de correspondance d'Id de la Ressource
MSG_RESOURCE_ID_MISSING | Id de la Ressource manquante
MSG_RESOURCE_NOT_ALLOWED | Non autorisé à soumettre une ressource pour cette opération
MSG_RESOURCE_REQUIRED | Une ressource est requise
MSG_RESOURCE_TYPE_MISMATCH | Type de ressource incorrect
MSG_SORT_UNKNOWN | Nom du paramètre de tri inconnu "%s"
MSG_TRANSACTION_DUPLICATE_ID | Identifiant en double dans la transaction : %s
MSG_TRANSACTION_MISSING_ID | Identifiant manquant dans la transaction - un élément entry.id doit être fourni
MSG_UNHANDLED_NODE_TYPE | Type de noeud xml "%s" non traité
MSG_UNKNOWN_CONTENT | Contenu inconnu (%s) à %s
MSG_UNKNOWN_OPERATION | operation http FHIR inconnue
MSG_UNKNOWN_TYPE | Type de ressource "%s" non reconnu
MSG_UPDATED | ressource existante mise à jour
MSG_VERSION_AWARE | Des mises à jour en relation avec la version sont requises pour cette ressource

MSG_VERSION_AWARE_CONFLICT | Conflit de mise à jour (version courante du serveur = "%s", version référencée du client = "%s")
MSG_VERSION_AWARE_URL | URL spécifique à une version non reconnue
MSG_WRONG_NS
SEARCH_MULTIPLE | Erreur : Plusieurs correspondances existent pour ce paramètre de recherche %s
SEARCH_NONE | Erreur : aucune recherche trouvée pour les paramètres %s "%s"
UPDATE_MULTIPLE_MATCHES

This code system http://terminology.hl7.org/CodeSystem/operation-outcome defines the following codes:

Code | Display | Definition
DELETE_MULTIPLE_MATCHES
MSG_AUTH_REQUIRED | Autenticazione richiesta prima di usare questo servizio
MSG_BAD_FORMAT | Sintassi Errata: "%s" deve essere un %s'
MSG_BAD_SYNTAX | Sintassi errata in %s
MSG_CANT_PARSE_CONTENT | Impossibile effettuare il parsing del feed (tipo del contenuto della entry = "%s")
MSG_CANT_PARSE_ROOT | Impossibile effettuare il parsing del feed (nome elemento root = "%s")
MSG_CREATED
MSG_DATE_FORMAT | Il valore %s per la data non è nel formato corretto (richiesto il Formato Data Xml)
MSG_DELETED | Questa risorsa è stata cancellata
MSG_DELETED_DONE | Risorsa cancellata
MSG_DELETED_ID | La risorsa "%s" è stata eliminata
MSG_DUPLICATE_ID | Id %s duplicato per il tipo di risorsa %s
MSG_ERROR_PARSING | Errore nel parsing della risorsa Xml (%s)
MSG_ID_INVALID | L''Id "%s" ha un carattere non valido: "%s"
MSG_ID_TOO_LONG | Id "%s" troppo lunga (limite di lunghezza: 36)
MSG_INVALID_ID | Id non accettato
MSG_JSON_OBJECT | Il sorgente Json di una risorsa dovrebbe iniziare con un oggetto
MSG_LOCAL_FAIL | Impossibile risolvere il riferimento locale alla risorsa %s
MSG_NO_EXIST | La risorsa con Id "%s" non esiste
MSG_NO_MATCH | Nessuna Risorsa soddisfa la query "%s"
MSG_NO_MODULE | Impossibile trovare un modulo per gestire la richiesta "%s"
MSG_NO_SUMMARY | Nessun riepilogo per questa risorsa
MSG_OP_NOT_ALLOWED | Operazione %s non consentita per la risorsa %s (a causa di configurazioni locali)
MSG_PARAM_CHAINED | Nome di parametro concatenato sconosciuto: "%s"
MSG_PARAM_INVALID | Il contenuto del Parametro "%s" non è valido
MSG_PARAM_MODIFIER_INVALID
MSG_PARAM_NO_REPEAT | Non &#65533; consentito ripetere il parametro "%s"
MSG_PARAM_UNKNOWN | Parametro "%s" non riconosciuto
MSG_RESOURCE_EXAMPLE_PROTECTED | Le Risorse aventi l'identità "example" non possono essere cancellate (per finalità di test/formazione)
MSG_RESOURCE_ID_FAIL | impossibile allocare l''id della risorsa
MSG_RESOURCE_ID_MISMATCH
MSG_RESOURCE_ID_MISSING | Id della Risorsa mancante
MSG_RESOURCE_NOT_ALLOWED | Non è consentito sottomettere una risorsa per questa operazione
MSG_RESOURCE_REQUIRED | E'' richiesta una risorsa
MSG_RESOURCE_TYPE_MISMATCH | Tipo Risorsa non corrispondente
MSG_SORT_UNKNOWN | Nome del parametro di ordinamento "%s" non riconosciuto
MSG_TRANSACTION_DUPLICATE_ID
MSG_TRANSACTION_MISSING_ID
MSG_UNHANDLED_NODE_TYPE | Tipo di nodo Xml non gestito "%s"
MSG_UNKNOWN_CONTENT | Contenuto Sconosciuto (%s) at %s
MSG_UNKNOWN_OPERATION | operazione http FHIR sconosciuta
MSG_UNKNOWN_TYPE | Tipo di Risorsa "%s" non riconosciuto
MSG_UPDATED | risorsa esistente aggiornata
MSG_VERSION_AWARE | Questa risorsa richiede aggiornamenti per versione
MSG_VERSION_AWARE_CONFLICT | Conflitto nell''aggiornamento (attuale = "%s", quotato = "%s")
MSG_VERSION_AWARE_URL | URL specifico alla versione non riconosciuto
MSG_WRONG_NS
SEARCH_MULTIPLE | Errore: Trovate corrispondenze multiple per %s parametri di ricerca "%s"
SEARCH_NONE | Errore: non è stato trovato alcun parametro di ricerca processabile per %s parametri di ricerca "%s"
UPDATE_MULTIPLE_MATCHES

Dit code systeem http://terminology.hl7.org/CodeSystem/operation-outcome definieert de volgende codes:

Code | Display | Definition
DELETE_MULTIPLE_MATCHES | Fout: er is meer dan één resultaat voor de conditionele delete
MSG_AUTH_REQUIRED | U moet zich authenticeren voor gebruik van deze service
MSG_BAD_FORMAT | Verkeerde syntax: "%s" moet een %s zijn
MSG_BAD_SYNTAX | Verkeerde syntax in %s
MSG_CANT_PARSE_CONTENT | Kan feed niet verwerken (contenttype inhoud = "%s")
MSG_CANT_PARSE_ROOT | Kan feed niet verwerken (rootelementnaam = "%s")
MSG_CREATED | Nieuwe resource gemaakt
MSG_DATE_FORMAT | De Datum-waarde %s heeft niet de juiste structuur (Xml Date vereist)
MSG_DELETED | Deze resource is verwijderd

MSG_DELETED_DONE | Resource verwijderd
MSG_DELETED_ID | De resource "%s" is verwijderd
MSG_DUPLICATE_ID | Duplicaat-id %s voor resourcetype %s
MSG_ERROR_PARSING | Fout in verwerking resource Xml (%s)
MSG_ID_INVALID | Id "%s" heeft een ongeldig teken "%s"
MSG_ID_TOO_LONG | Id "%s" te lang (max lengte 36)
MSG_INVALID_ID | Id niet geaccepteerd
MSG_JSON_OBJECT | Json Source van een resource moeten beginnen met een object
MSG_LOCAL_FAIL | De resource met lokale referentie %s is niet gevonden
MSG_NO_EXIST | Resource-id "%s" bestaat niet
MSG_NO_MATCH | Geen resource gevonden met query "%s"
MSG_NO_MODULE | Er kon geen module worden gevonden om verzoek "%s" te verwerken
MSG_NO_SUMMARY | Geen samenvatting voor deze resource
MSG_OP_NOT_ALLOWED | Bewerking %s niet toegestaan voor resource %s (vanwege lokale configuratie)
MSG_PARAM_CHAINED | Onbekende geschakelde parameternaam "%s"
MSG_PARAM_INVALID | Waarde van parameter "%s" is ongeldig
MSG_PARAM_MODIFIER_INVALID | Modifier van parameter "%s" is ongeldig
MSG_PARAM_NO_REPEAT | Parameter "%s" mag niet herhalen
MSG_PARAM_UNKNOWN | Parameter "%s" onbekend
MSG_RESOURCE_EXAMPLE_PROTECTED | Resources met identiteit "voorbeeld" kunnen niet worden verwijderd (ten behoeve van testen/training)
MSG_RESOURCE_ID_FAIL | kan geen resource-id reserveren
MSG_RESOURCE_ID_MISMATCH | Resource ID's komen niet overeen
MSG_RESOURCE_ID_MISSING | Resource ID ontbreekt
MSG_RESOURCE_NOT_ALLOWED | Niet toegestaan om een resource in te dienen voor deze bewerking
MSG_RESOURCE_REQUIRED | Een resource is verplicht
MSG_RESOURCE_TYPE_MISMATCH | Verkeerd resourcetype
MSG_SORT_UNKNOWN | Onbekende parameternaam "%s" voor sortering
MSG_TRANSACTION_DUPLICATE_ID | Dubbele identificatie in transactie: %s
MSG_TRANSACTION_MISSING_ID | Ontbrekende identificatie in transactie - entry.id is verplicht
MSG_UNHANDLED_NODE_TYPE | Kan xml nodetype "%s" niet verwerken
MSG_UNKNOWN_CONTENT | Onbekende content (%s) at %s
MSG_UNKNOWN_OPERATION | onbekende FHIR http operation
MSG_UNKNOWN_TYPE | Resourcetype "%s" niet herkend
MSG_UPDATED | bestaande resource updated
MSG_VERSION_AWARE | Versie-bewuste updates zijn vereist voor deze resource
MSG_VERSION_AWARE_CONFLICT | Updateconflict (huidige serverversie = "%s", opgegeven clientversie = "%s")
MSG_VERSION_AWARE_URL | Versie-specifieke URL niet herkend
MSG_WRONG_NS | Dit lijkt geen FHIR element of resource te zijn (verkeerde namespace "%s")
SEARCH_MULTIPLE | Fout: er is meer dan één resultaat voor %s zoekparameters "%s"
SEARCH_NONE | Fout: geen verwerkbare zoekactie gevonden voor %s zoekparameters "%s"
UPDATE_MULTIPLE_MATCHES | Fout: er is meer dan één resultaat voor de conditionele update

This code system http://terminology.hl7.org/CodeSystem/operation-outcome defines the following codes:

Code | Display | Definition
DELETE_MULTIPLE_MATCHES
MSG_AUTH_REQUIRED | Wymagana autentykacja przed użyciem tego serwisu
MSG_BAD_FORMAT | Błąd składni: "%s" powinno być %s'
MSG_BAD_SYNTAX | Błąd składni w %s
MSG_CANT_PARSE_CONTENT | Błąd parsowania (typ zawartości wejściowej = "%s")
MSG_CANT_PARSE_ROOT | Błąd parsowania (nazwa elementu root = "%s")
MSG_CREATED
MSG_DATE_FORMAT | Niepoprawny format wartości daty %s (wymagany format XML)
MSG_DELETED | Ten zasób został usunięty
MSG_DELETED_DONE | Zasób usunięto
MSG_DELETED_ID | Zasób "%s" został usunięty
MSG_DUPLICATE_ID | Zdublowany identyfikator %s dla zasobu typu %s
MSG_ERROR_PARSING | Błąd w trakcie parsowania zasobu XML (%s)
MSG_ID_INVALID | Identyfikator "%s" zawiera niepoprawny znak "%s"
MSG_ID_TOO_LONG | Identyfikator "%s" jest zbyt długi (limit długości 36)
MSG_INVALID_ID | Identyfikator nie zaakceptowany
MSG_JSON_OBJECT | Źródło json dla zasobu powinno rozpoczynać się od obiektu
MSG_LOCAL_FAIL | Zasób wskazywany przez loklaną referencję %s nie został odnaleziony
MSG_NO_EXIST | Zasób o identyfikatorze "%s" nie istnieje
MSG_NO_MATCH
MSG_NO_MODULE | Nie można odnaleźć modułu, aby obsłużyć żądanie "%s"
MSG_NO_SUMMARY | Brak podsumowania (Summary) dla tego zasobu
MSG_OP_NOT_ALLOWED | Niedozwolona operacja %s dla zasobu %s (ze względu na lokalną konfigurację)
MSG_PARAM_CHAINED | Nieznana nazwa parametru powiązanego "%s"
MSG_PARAM_INVALID
MSG_PARAM_MODIFIER_INVALID
MSG_PARAM_NO_REPEAT | Parametr "%s" nie może zostać powtórzony
MSG_PARAM_UNKNOWN | Niezrozumiały parametr "%s"

MSG_RESOURCE_EXAMPLE_PROTECTED | Zasoby oznaczone jako "example" nie mogą zostać usunięte (dla celów testów/szkoleń)
MSG_RESOURCE_ID_FAIL | nie można nadać identyfikatora zasobu
MSG_RESOURCE_ID_MISMATCH
MSG_RESOURCE_ID_MISSING
MSG_RESOURCE_NOT_ALLOWED | Nie można zgłosić zasobu dla tej operacji
MSG_RESOURCE_REQUIRED | Zasób jest wymagany
MSG_RESOURCE_TYPE_MISMATCH | Niepoprawny typ zasobu
MSG_SORT_UNKNOWN | Nieznany parametr sortowania "%s"
MSG_TRANSACTION_DUPLICATE_ID | Zdublowany identyfikator w transakcji: %s
MSG_TRANSACTION_MISSING_ID | Brak identyfikatora w transakcji - należy podać entry.id
MSG_UNHANDLED_NODE_TYPE | Nieobsługiwany typ węzła XML "%s"
MSG_UNKNOWN_CONTENT | Nieznana zawartość (%s) dla %s
MSG_UNKNOWN_OPERATION | nieznana operacja FHIR http
MSG_UNKNOWN_TYPE | Nie rozpoznany typ zasobu: "%s"
MSG_UPDATED | uaktualniono istniejący zasób
MSG_VERSION_AWARE | Uaktualnienia zakładające wersjonowanie są wymagane dla tego zasobu
MSG_VERSION_AWARE_CONFLICT | Konflikt podczas uaktualnienia (obecna wersja na serwerze = "%s", wersja wskazana przez klienta = "%s")
MSG_VERSION_AWARE_URL | Nie rozpoznany URL specyficzny dla wersji
MSG_WRONG_NS
SEARCH_MULTIPLE | Błąd: Istnieją wielokrotne dopasowania dla %s parametrów wyszukiwania "%s"
SEARCH_NONE | Błąd: Niewykonalne wyszukiwanie dla %s parametrów wyszukiwania "%s"
UPDATE_MULTIPLE_MATCHES

This code system http://terminology.hl7.org/CodeSystem/operation-outcome defines the following codes:

Code | Display | Definition
DELETE_MULTIPLE_MATCHES
MSG_AUTH_REQUIRED
MSG_BAD_FORMAT | Неверный синтакс: "%s" должен быть %s
MSG_BAD_SYNTAX | Неверный синтакс: %s
MSG_CANT_PARSE_CONTENT
MSG_CANT_PARSE_ROOT | Не удалось разобрать данные (корневой элемент = "%s")
MSG_CREATED
MSG_DATE_FORMAT | Значение Date %s в неверном формате (требуется Xml Date формат)
MSG_DELETED | Данный ресурс был удалён
MSG_DELETED_DONE | Ресурс удалён
MSG_DELETED_ID | Ресурс "%s" был удалён
MSG_DUPLICATE_ID | Дублирующий Id %s для типа ресурса %s
MSG_ERROR_PARSING | Ошибка синтаксического разбора ресурса Xml (%s)
MSG_ID_INVALID | Id "%s" содержит недопустимые символы "%s"
MSG_ID_TOO_LONG | Недопустимая длина Id "%s" (ограничение 36)
MSG_INVALID_ID | Id не принято
MSG_JSON_OBJECT | Json Source для ресурса должен начинаться с объекта
MSG_LOCAL_FAIL | Невозможно определить локальную ссылку на ресурс %s
MSG_NO_EXIST | Ресурс Id "%s" не существует
MSG_NO_MATCH
MSG_NO_MODULE | Модуль для обработки запроса "%s" не найден
MSG_NO_SUMMARY | Отсутствует Summary для данного ресурса
MSG_OP_NOT_ALLOWED | Операция %s недопустима для ресурса %s (по причине локальной конфигурации)
MSG_PARAM_CHAINED | Неизвестное вложенное наименование параметра "%s"
MSG_PARAM_INVALID
MSG_PARAM_MODIFIER_INVALID
MSG_PARAM_NO_REPEAT | Параметр "%s" не может быть повторён
MSG_PARAM_UNKNOWN | Параметр "%s" не понят
MSG_RESOURCE_EXAMPLE_PROTECTED | Ресурс с идентификатором "example" не может быть удалён (для случаев тестирования/обучения)
MSG_RESOURCE_ID_FAIL | невозможно выделить идентификатор ресурса
MSG_RESOURCE_ID_MISMATCH
MSG_RESOURCE_ID_MISSING
MSG_RESOURCE_NOT_ALLOWED | Для данной операции отправка ресурса недопустима
MSG_RESOURCE_REQUIRED | Требуется ресурс
MSG_RESOURCE_TYPE_MISMATCH | Несоответствие типа ресурса
MSG_SORT_UNKNOWN | Неизвестное имя параметра сортировки "%s"
MSG_TRANSACTION_DUPLICATE_ID | Дублирующий идентификатор в транзакции: %s
MSG_TRANSACTION_MISSING_ID | Отсутствует идентификатор в транзакции - требуется entry.id
MSG_UNHANDLED_NODE_TYPE | Не обработанный xml узел "%s"
MSG_UNKNOWN_CONTENT | Неизвестный контент (%s) в %s
MSG_UNKNOWN_OPERATION | неизвестная операция FHIR http
MSG_UNKNOWN_TYPE | Тип ресурса "%s" не распознан
MSG_UPDATED | существующий ресурс обновлён
MSG_VERSION_AWARE | Для данного ресурса необходимы обновления с учётом версии
MSG_VERSION_AWARE_CONFLICT | Конфликт обновления (текущая версия сервера = "%s", указанная версия клиента = "%s")

MSG_VERSION_AWARE_URL | URL для указанной версии не распознан
MSG_WRONG_NS
SEARCH_MULTIPLE | Ошибка: множественные совпадения для %s с параметрами поиска "%s"
SEARCH_NONE | Ошибка: обрабатываемых результатов поиска для %s с параметрами поиска "%s" не найдено
UPDATE_MULTIPLE_MATCHES

This code system http://terminology.hl7.org/CodeSystem/operation-outcome defines the following codes:

Code | Display | Definition
DELETE_MULTIPLE_MATCHES
MSG_AUTH_REQUIRED | □□□□□□□□□□
MSG_BAD_FORMAT | □□□□: "%s" □□□□□ %s'
MSG_BAD_SYNTAX | %s □□□□□
MSG_CANT_PARSE_CONTENT | □□□□feed (□□□□□□□ = "%s")
MSG_CANT_PARSE_ROOT | □□□□feed (□□□□ = "%s")
MSG_CREATED
MSG_DATE_FORMAT | □□□□ %s □□□□□ (□□□Xml Date□□)
MSG_DELETED | □□□□□□
MSG_DELETED_DONE | □□□□□
MSG_DELETED_ID | □□ "%s" □□□□
MSG_DUPLICATE_ID | ID %s □□□□□□□ %s□
MSG_ERROR_PARSING | □□□□Xml□□□ (%s)
MSG_ID_INVALID | ID "%s" □□□□□□: "%s"
MSG_ID_TOO_LONG | Id "%s" □□ (□□□□: 36)
MSG_INVALID_ID | Id□□□□
MSG_JSON_OBJECT | □□□Json□□□□□object□□
MSG_LOCAL_FAIL | □□□□□□□ %s □□□□□
MSG_NO_EXIST | □□Id "%s"□□□
MSG_NO_MATCH
MSG_NO_MODULE | □□□□□□□□"%s"□□□
MSG_NO_SUMMARY | □□□□summary
MSG_OP_NOT_ALLOWED | □□ %s □□□□□□□□ %s (□□□□□□)
MSG_PARAM_CHAINED | □□□□□□□□: "%s"
MSG_PARAM_INVALID
MSG_PARAM_MODIFIER_INVALID
MSG_PARAM_NO_REPEAT | □□"%s"□□□□
MSG_PARAM_UNKNOWN | □□□□□□"%s"
MSG_RESOURCE_EXAMPLE_PROTECTED | □"example" □ID□□□□□□□□ (□□□□/□□)
MSG_RESOURCE_ID_FAIL | □□□□□□ID
MSG_RESOURCE_ID_MISMATCH
MSG_RESOURCE_ID_MISSING
MSG_RESOURCE_NOT_ALLOWED | □□□□□□□□□□
MSG_RESOURCE_REQUIRED | □□□□□□□□
MSG_RESOURCE_TYPE_MISMATCH | □□□□□□□
MSG_SORT_UNKNOWN | □□□□□□□□□"%s"
MSG_TRANSACTION_DUPLICATE_ID | □□□□□□□Id: %s
MSG_TRANSACTION_MISSING_ID | □□□□□Id - □□□□□□entry.id
MSG_UNHANDLED_NODE_TYPE | □□□□XML□□□□"%s"
MSG_UNKNOWN_CONTENT | □□□□ (%s) □□ %s
MSG_UNKNOWN_OPERATION | □□□FHIR HTTP□□
MSG_UNKNOWN_TYPE | □□□□"%s"□□□
MSG_UPDATED | □□□□□□□
MSG_VERSION_AWARE | □□□□□□□□□□□□□
MSG_VERSION_AWARE_CONFLICT | □□□□ (□□□□□□□ = "%s", □□□□□□□□ = "%s")
MSG_VERSION_AWARE_URL | □□□□□□□□URL
MSG_WRONG_NS
SEARCH_MULTIPLE | □□: □□ %s □□□□□ "%s"□□□□□□
SEARCH_NONE | □□: □%s□□□□"%s"□□□□□□□□□
UPDATE_MULTIPLE_MATCHES

See the full registry of code systems defined as part of FHIR.

Explanation of the columns that may appear on this page:

Level | A few code lists that FHIR defines are hierarchical - each code is assigned a level. See Code System for further information.
Source | The source of the definition of the code (when the value set draws in codes defined elsewhere)
Code | The code (used as the code in the resource instance). If the code is in italics, this indicates that the code is not selectable ('Abstract')
Display | The display (used in the display element of a Coding). If there is no display, implementers should not simply display the code, but map the concept into their application
Definition | An explanation of the meaning of the concept
Comments | Additional notes about how to use the code

4.3.14.62 Code System http://hl7.org/fhir/permitted-data-type

URL: https://hl7.org/fhir/R4/codesystem-permitted-data-type.html
Orders and Observations Work Group | Maturity Level: 0 | Trial Use | Use Context: Any

This is a code system defined by the FHIR project.

Summary

Defining URL: | http://hl7.org/fhir/permitted-data-type
Version: | 4.0.1
Name: | ObservationDataType
Title: | ObservationDataType
Definition: | Permitted data type for observation value.
Committee: | Orders and Observations Work Group
OID: | 2.16.840.1.113883.4.642.4.1332 (for OID based terminology systems)
Source Resource | XML / JSON

This Code system is used in the following value sets:

• ValueSet: ObservationDataType (Permitted data type for observation value.)

• ValueSet: ObservationDataType (Permitted data type for observation value.)

4.3.14.62.1 Content

4.3.14.62.2 ObservationDataType

Permitted data type for observation value.

This code system http://hl7.org/fhir/permitted-data-type defines the following codes:

Code | Display | Definition
Quantity | Quantity | A measured amount.
CodeableConcept | CodeableConcept | A coded concept from a reference terminology and/or text.
string | string | A sequence of Unicode characters.
boolean | boolean | true or false.
integer | integer | A signed integer.
Range | Range | A set of values bounded by low and high.
Ratio | Ratio | A ratio of two Quantity values - a numerator and a denominator.
SampledData | SampledData | A series of measurements taken by a device.
time | time | A time during the day, in the format hh:mm:ss.
dateTime | dateTime | A date, date-time or partial date (e.g. just year or year + month) as used in human communication.
Period | Period | A time range defined by start and end date/time.

See the full registry of code systems defined as part of FHIR.

Explanation of the columns that may appear on this page:

Level | A few code lists that FHIR defines are hierarchical - each code is assigned a level. See Code System for further information.
Source | The source of the definition of the code (when the value set draws in codes defined elsewhere)
Code | The code (used as the code in the resource instance). If the code is in italics, this indicates that the code is not selectable ('Abstract')
Display | The display (used in the display element of a Coding). If there is no display, implementers should not simply display the code, but map the concept into their application
Definition | An explanation of the meaning of the concept
Comments | Additional notes about how to use the code

4.3.14.63 Code System http://terminology.hl7.org/CodeSystem/testscript-profile-origin-types

URL: https://hl7.org/fhir/R4/codesystem-testscript-profile-origin-types.html
FHIR Infrastructure Work Group | Maturity Level: 2 | Trial Use | Use Context: Any

This is a code system defined by the FHIR project.

Summary

Defining URL: | http://terminology.hl7.org/CodeSystem/testscript-profile-origin-types
Version: | 4.0.1
Name: | TestScriptProfileOriginType
Title: | Test script profile origin type
Definition: | This value set defines a set of codes that are used to indicate the profile type of a test system when acting as the origin within a TestScript.
Committee: | FHIR Infrastructure Work Group
OID: | 2.16.840.1.113883.4.642.4.1196 (for OID based terminology systems)
Source Resource | XML / JSON

This Code system is used in the following value sets:

• ValueSet: Test script profile origin type (This value set defines a set of codes that are used to indicate the profile type of a test system when acting as the origin within a TestScript.)

• ValueSet: Test script profile origin type (This value set defines a set of codes that are used to indicate the profile type of a test system when acting as the origin within a TestScript.)

4.3.14.63.1 Content

4.3.14.63.2 Test script profile origin type

This value set defines a set of codes that are used to indicate the profile type of a test system when acting as the origin within a TestScript.

This code system http://terminology.hl7.org/CodeSystem/testscript-profile-origin-types defines the following codes:

Code | Display | Definition
FHIR-Client | FHIR Client | General FHIR client used to initiate operations against a FHIR server.
FHIR-SDC-FormFiller | FHIR SDC FormFiller | A FHIR client acting as a Structured Data Capture Form Filler.

See the full registry of code systems defined as part of FHIR.

Explanation of the columns that may appear on this page:

Level | A few code lists that FHIR defines are hierarchical - each code is assigned a level. See Code System for further information.
Source | The source of the definition of the code (when the value set draws in codes defined elsewhere)
Code | The code (used as the code in the resource instance). If the code is in italics, this indicates that the code is not selectable ('Abstract')
Display | The display (used in the display element of a Coding). If there is no display, implementers should not simply display the code, but map the concept into their application
Definition | An explanation of the meaning of the concept
Comments | Additional notes about how to use the code

4.3.14.64 Code System http://terminology.hl7.org/CodeSystem/subscription-tag

URL: https://hl7.org/fhir/R4/codesystem-subscription-tag.html
Vocabulary Work Group | Maturity Level: 0 | Informative | Use Context: Any

This is a code system defined by the FHIR project.

Summary

Defining URL: | http://terminology.hl7.org/CodeSystem/subscription-tag
Version: | 4.0.1
Name: | SubscriptionTag
Title: | SubscriptionTag
Definition: | Tags to put on a resource after subscriptions have been sent.
Committee: | ??
OID: | 2.16.840.1.113883.4.642.4.1141 (for OID based terminology systems)
Source Resource | XML / JSON

This Code system is used in the following value sets:

• ValueSet: SubscriptionTag (Tags to put on a resource after subscriptions have been sent.)

• ValueSet: SubscriptionTag (Tags to put on a resource after subscriptions have been sent.)

4.3.14.64.1 Content

4.3.14.64.2 SubscriptionTag

Tags to put on a resource after subscriptions have been sent.

This code system http://terminology.hl7.org/CodeSystem/subscription-tag defines the following codes:

Code | Display | Definition
queued | Queued | The message has been queued for processing on a destination systems.
delivered | Delivered | The message has been delivered to its intended recipient.

See the full registry of code systems defined as part of FHIR.

Explanation of the columns that may appear on this page:

Level | A few code lists that FHIR defines are hierarchical - each code is assigned a level. See Code System for further information.
Source | The source of the definition of the code (when the value set draws in codes defined elsewhere)
Code | The code (used as the code in the resource instance). If the code is in italics, this indicates that the code is not selectable ('Abstract')
Display | The display (used in the display element of a Coding). If there is no display, implementers should not simply display the code, but map the concept into their application
Definition | An explanation of the meaning of the concept
Comments | Additional notes about how to use the code

4.3.14.65 Code System http://terminology.hl7.org/CodeSystem/questionnaire-usage-mode

URL: https://hl7.org/fhir/R4/codesystem-questionnaire-usage-mode.html
Vocabulary Work Group | Maturity Level: 0 | Informative | Use Context: Any

This is a code system defined by the FHIR project.

Summary

Defining URL: | http://terminology.hl7.org/CodeSystem/questionnaire-usage-mode
Version: | 4.0.1
Name: | QuestionnaireItemUsageMode
Title: | QuestionnaireItemUsageMode
Definition: | Identifies the modes of usage of a questionnaire that should enable a particular questionnaire item.
Committee: | ??
OID: | 2.16.840.1.113883.4.642.4.1274 (for OID based terminology systems)
Source Resource | XML / JSON

This Code system is used in the following value sets:

• ValueSet: QuestionnaireItemUsageMode (Identifies the modes of usage of a questionnaire that should enable a particular questionnaire item.)

• ValueSet: QuestionnaireItemUsageMode (Identifies the modes of usage of a questionnaire that should enable a particular questionnaire item.)

4.3.14.65.1 Content

4.3.14.65.2 QuestionnaireItemUsageMode

Identifies the modes of usage of a questionnaire that should enable a particular questionnaire item.

This code system http://terminology.hl7.org/CodeSystem/questionnaire-usage-mode defines the following codes:

Code | Display | Definition
capture-display | Capture & Display | Render the item regardless of usage mode.
capture | Capture Only | Render the item only when capturing data.
display | Display Only | Render the item only when displaying a completed form.
display-non-empty | Display when Answered | Render the item only when displaying a completed form and the item has been answered (or has child items that have been answered).
capture-display-non-empty | Capture or, if answered, Display | Render the item when capturing data or when displaying a completed form and the item has been answered (or has child items that have been answered).

See the full registry of code systems defined as part of FHIR.

Explanation of the columns that may appear on this page:

Level | A few code lists that FHIR defines are hierarchical - each code is assigned a level. See Code System for further information.
Source | The source of the definition of the code (when the value set draws in codes defined elsewhere)
Code | The code (used as the code in the resource instance). If the code is in italics, this indicates that the code is not selectable ('Abstract')
Display | The display (used in the display element of a Coding). If there is no display, implementers should not simply display the code, but map the concept into their application
Definition | An explanation of the meaning of the concept
Comments | Additional notes about how to use the code

4.3.14.66 Code System http://terminology.hl7.org/CodeSystem/payment-adjustment-reason

URL: https://hl7.org/fhir/R4/codesystem-payment-adjustment-reason.html
Financial Management Work Group | Maturity Level: 1 | Draft | Use Context: Any

This is a code system defined by the FHIR project.

Summary

Defining URL: | http://terminology.hl7.org/CodeSystem/payment-adjustment-reason
Version: | 4.0.1
Name: | PaymentAdjustmentReasonCodes
Title: | Payment Adjustment Reason Codes
Definition: | This value set includes smattering of Payment Adjustment Reason codes.
Committee: | Financial Management Work Group
OID: | 2.16.840.1.113883.4.642.4.1173 (for OID based terminology systems)
Copyright: | This is an example set.
Source Resource | XML / JSON

This Code system is used in the following value sets:

• ValueSet: Payment Adjustment Reason Codes (This value set includes smattering of Payment Adjustment Reason codes.)

• ValueSet: Payment Adjustment Reason Codes (This value set includes smattering of Payment Adjustment Reason codes.)

4.3.14.66.1 Content

4.3.14.66.2 Payment Adjustment Reason Codes

This value set includes smattering of Payment Adjustment Reason codes.

Copyright Statement:

This is an example set.

This code system http://terminology.hl7.org/CodeSystem/payment-adjustment-reason defines the following codes:

Code | Display | Definition
a001 | Prior Payment Reversal | Prior Payment Reversal
a002 | Prior Overpayment | Prior Overpayment

See the full registry of code systems defined as part of FHIR.

Explanation of the columns that may appear on this page:

Level | A few code lists that FHIR defines are hierarchical - each code is assigned a level. See Code System for further information.
Source | The source of the definition of the code (when the value set draws in codes defined elsewhere)
Code | The code (used as the code in the resource instance). If the code is in italics, this indicates that the code is not selectable ('Abstract')
Display | The display (used in the display element of a Coding). If there is no display, implementers should not simply display the code, but map the concept into their application
Definition | An explanation of the meaning of the concept
Comments | Additional notes about how to use the code

4.3.14.67 Code System http://hl7.org/fhir/report-status-codes

URL: https://hl7.org/fhir/R4/codesystem-report-status-codes.html
FHIR Infrastructure Work Group | Maturity Level: 0 | Trial Use | Use Context: Any

This is a code system defined by the FHIR project.

Summary

Defining URL: | http://hl7.org/fhir/report-status-codes
Version: | 4.0.1
Name: | TestReportStatus
Title: | TestReportStatus
Definition: | The current status of the test report.
Committee: | FHIR Infrastructure Work Group
OID: | 2.16.840.1.113883.4.642.4.725 (for OID based terminology systems)
Source Resource | XML / JSON

This Code system is used in the following value sets:

• ValueSet: TestReportStatus (The current status of the test report.)

• ValueSet: TestReportStatus (The current status of the test report.)

4.3.14.67.1 Content

4.3.14.67.2 TestReportStatus

The current status of the test report.

This code system http://hl7.org/fhir/report-status-codes defines the following codes:

Code | Display | Definition
completed | Completed | All test operations have completed.
in-progress | In Progress | A test operations is currently executing.
waiting | Waiting | A test operation is waiting for an external client request.
stopped | Stopped | The test script execution was manually stopped.
entered-in-error | Entered In Error | This test report was entered or created in error.

See the full registry of code systems defined as part of FHIR.

Explanation of the columns that may appear on this page:

Level | A few code lists that FHIR defines are hierarchical - each code is assigned a level. See Code System for further information.
Source | The source of the definition of the code (when the value set draws in codes defined elsewhere)
Code | The code (used as the code in the resource instance). If the code is in italics, this indicates that the code is not selectable ('Abstract')
Display | The display (used in the display element of a Coding). If there is no display, implementers should not simply display the code, but map the concept into their application

Definition | An explanation of the meaning of the concept
Comments | Additional notes about how to use the code

4.3.14.68 Code System http://hl7.org/fhir/versioning-policy

URL: https://hl7.org/fhir/R4/codesystem-versioning-policy.html
FHIR Infrastructure Work Group | Maturity Level: N | Normative (from v4.0.0) | Use Context: Any

| This page has been approved as part of an ANSI standard. See the Conformance Package for further details.

This is a code system defined by the FHIR project.

Summary

Defining URL: | http://hl7.org/fhir/versioning-policy
Version: | 4.0.1
Name: | ResourceVersionPolicy
Title: | ResourceVersionPolicy
Definition: | How the system supports versioning for a resource.
Committee: | FHIR Infrastructure Work Group
OID: | 2.16.840.1.113883.4.642.4.191 (for OID based terminology systems)
Source Resource | XML / JSON

This Code system is used in the following value sets:

• ValueSet: ResourceVersionPolicy (How the system supports versioning for a resource.)

• ValueSet: ResourceVersionPolicy (How the system supports versioning for a resource.)

4.3.14.68.1 Content

4.3.14.68.2 ResourceVersionPolicy

How the system supports versioning for a resource.

This code system http://hl7.org/fhir/versioning-policy defines the following codes:

Code | Display | Definition
no-version | No VersionId Support | VersionId meta-property is not supported (server) or used (client).
versioned | Versioned | VersionId meta-property is supported (server) or used (client).
versioned-update | VersionId tracked fully | VersionId must be correct for updates (server) or will be specified (If-match header) for updates (client).

See the full registry of code systems defined as part of FHIR.

Explanation of the columns that may appear on this page:

Level | A few code lists that FHIR defines are hierarchical - each code is assigned a level. See Code System for further information.
Source | The source of the definition of the code (when the value set draws in codes defined elsewhere)
Code | The code (used as the code in the resource instance). If the code is in italics, this indicates that the code is not selectable ('Abstract')
Display | The display (used in the display element of a Coding). If there is no display, implementers should not simply display the code, but map the concept into their application
Definition | An explanation of the meaning of the concept
Comments | Additional notes about how to use the code

4.3.14.69 Code System http://hl7.org/fhir/animal-genderstatus

URL: https://hl7.org/fhir/R4/codesystem-animal-genderstatus.html
Vocabulary Work Group | Maturity Level: 0 | Informative | Use Context: Any

This is a code system defined by the FHIR project.

Summary

Defining URL: | http://hl7.org/fhir/animal-genderstatus
Version: | 4.0.1
Name: | GenderStatus
Title: | Gender status
Definition: | This example value set defines a set of codes that can be used to indicate the current state of the animal's reproductive organs.
Committee: | ??
OID: | 2.16.840.1.113883.4.642.4.419 (for OID based terminology systems)
Source Resource | XML / JSON

This Code system is used in the following value sets:

• ValueSet: Gender status (This example value set defines a set of codes that can be used to indicate the current state of the animal's reproductive organs.)

• ValueSet: Gender status (This example value set defines a set of codes that can be used to indicate the current state of the animal's reproductive organs.)

4.3.14.69.1 Content

• All Languages
• English
• Nederlands (Dutch)

This code system http://hl7.org/fhir/animal-genderstatus defines the following codes:

Code | Display | Definition
neutered | Neutered | The animal has been sterilized, castrated or otherwise made infertile.
intact | Intact | The animal's reproductive organs are intact.
unknown | Unknown | Unable to determine whether the animal has been neutered.

This code system http://hl7.org/fhir/animal-genderstatus defines the following codes:

Code | Display | Definition
neutered | Neutered | The animal has been sterilized, castrated or otherwise made infertile.
intact | Intact | The animal's reproductive organs are intact.
unknown | Unknown | Unable to determine whether the animal has been neutered.

Dit code systeem http://hl7.org/fhir/animal-genderstatus definieert de volgende codes:

Code | Display | Definition
neutered
intact
unknown

See the full registry of code systems defined as part of FHIR.

Explanation of the columns that may appear on this page:

Level | A few code lists that FHIR defines are hierarchical - each code is assigned a level. See Code System for further information.
Source | The source of the definition of the code (when the value set draws in codes defined elsewhere)
Code | The code (used as the code in the resource instance). If the code is in italics, this indicates that the code is not selectable ('Abstract')
Display | The display (used in the display element of a Coding). If there is no display, implementers should not simply display the code, but map the concept into their application
Definition | An explanation of the meaning of the concept
Comments | Additional notes about how to use the code

4.3.14.70 Code System http://hl7.org/fhir/ex-servicemodifier

URL: https://hl7.org/fhir/R4/codesystem-service-modifiers.html
Vocabulary Work Group | Maturity Level: 0 | Informative | Use Context: Any

This is a code system defined by the FHIR project.

Summary

Defining URL: | http://hl7.org/fhir/ex-servicemodifier
Version: | 4.0.1
Name: | ExampleServiceModifierCodes
Title: | Example Service Modifier Codes
Definition: | This value set includes sample Service Modifier codes which may support differential payment.
Committee: | ??
OID: | 2.16.840.1.113883.4.642.4.573 (for OID based terminology systems)
Copyright: | This is an example set.
Source Resource | XML / JSON

This Code system is used in the following value sets:

• ValueSet: Example Service Modifier Codes (This value set includes sample Service Modifier codes.)
• ValueSet: Example Service Modifier Codes (This value set includes sample Service Modifier codes.)

4.3.14.70.1 Content

4.3.14.70.2 Example Service Modifier Codes

This value set includes sample Service Modifier codes which may support differential payment.

Copyright Statement:

This is an example set.

This code system http://hl7.org/fhir/ex-servicemodifier defines the following codes:

Code | Display | Definition
sr | Side of the Road | Services provided on the side of the road or such other non-conventional setting.
ah | After hours | Services provided outside or normal business hours.

See the full registry of code systems defined as part of FHIR.

Explanation of the columns that may appear on this page:

Level | A few code lists that FHIR defines are hierarchical - each code is assigned a level. See Code System for further information.

Source | The source of the definition of the code (when the value set draws in codes defined elsewhere)
Code | The code (used as the code in the resource instance). If the code is in italics, this indicates that the code is not selectable ('Abstract')
Display | The display (used in the display element of a Coding). If there is no display, implementers should not simply display the code, but map the concept into their application
Definition | An explanation of the meaning of the concept
Comments | Additional notes about how to use the code

4.3.14.71 Code System http://terminology.hl7.org/CodeSystem/paymentstatus

URL: https://hl7.org/fhir/R4/codesystem-payment-status.html
Financial Management Work Group | Maturity Level: 1 | Draft | Use Context: Any

This is a code system defined by the FHIR project.

Summary

Defining URL: | http://terminology.hl7.org/CodeSystem/paymentstatus
Version: | 4.0.1
Name: | PaymentStatusCodes
Title: | Payment Status Codes
Definition: | This value set includes a sample set of Payment Status codes.
Committee: | Financial Management Work Group
OID: | 2.16.840.1.113883.4.642.4.1187 (for OID based terminology systems)
Copyright: | This is an example set.
Source Resource | XML / JSON

This Code system is used in the following value sets:

• ValueSet: Payment Status Codes (This value set includes a sample set of Payment Status codes.)
• ValueSet: Payment Status Codes (This value set includes a sample set of Payment Status codes.)

4.3.14.71.1 Content

4.3.14.71.2 Payment Status Codes

This value set includes a sample set of Payment Status codes.

Copyright Statement:

This is an example set.

This code system http://terminology.hl7.org/CodeSystem/paymentstatus defines the following codes:

Code | Display | Definition
paid | Paid | The payment has been sent physically or electronically.
cleared | Cleared | The payment has been received by the payee.

See the full registry of code systems defined as part of FHIR.

Explanation of the columns that may appear on this page:

Level | A few code lists that FHIR defines are hierarchical - each code is assigned a level. See Code System for further information.
Source | The source of the definition of the code (when the value set draws in codes defined elsewhere)
Code | The code (used as the code in the resource instance). If the code is in italics, this indicates that the code is not selectable ('Abstract')
Display | The display (used in the display element of a Coding). If there is no display, implementers should not simply display the code, but map the concept into their application
Definition | An explanation of the meaning of the concept
Comments | Additional notes about how to use the code

4.3.14.72 Code System http://terminology.hl7.org/CodeSystem/med-admin-perform-function

URL: https://hl7.org/fhir/R4/codesystem-med-admin-perform-function.html
Pharmacy Work Group | Maturity Level: 1 | Draft | Use Context: Any

This is a code system defined by the FHIR project.

Summary

Defining URL: | http://terminology.hl7.org/CodeSystem/med-admin-perform-function
Version: | 4.0.1
Name: | MedicationAdministration Performer Function Codes
Title: | Medication administration performer function codes
Definition: | MedicationAdministration Performer Function Codes
Committee: | Pharmacy Work Group
OID: | 2.16.840.1.113883.4.642.4.1112 (for OID based terminology systems)
Source Resource | XML / JSON

This Code system is used in the following value sets:

• ValueSet: Medication administration performer function codes (MedicationAdministration Performer Function Codes)

• ValueSet: Medication administration performer function codes (MedicationAdministration Performer Function Codes)

4.3.14.72.1 Content

4.3.14.72.2 Medication administration performer function codes

MedicationAdministration Performer Function Codes

This code system http://terminology.hl7.org/CodeSystem/med-admin-perform-function defines the following codes:

Code | Display | Definition
performer | Performer | A person, non-person living subject, organization or device that who actually and principally carries out the action
verifier | Verifier | A person who verifies the correctness and appropriateness of the service (plan, order, event, etc.) and hence takes on accountability.
witness | Witness | A person witnessing the action happening without doing anything. A witness is not necessarily aware, much less approves of anything stated in the service event. Example for a witness is students watching an operation or an advanced directive witness.

See the full registry of code systems defined as part of FHIR.

Explanation of the columns that may appear on this page:

Level | A few code lists that FHIR defines are hierarchical - each code is assigned a level. See Code System for further information.
Source | The source of the definition of the code (when the value set draws in codes defined elsewhere)
Code | The code (used as the code in the resource instance). If the code is in italics, this indicates that the code is not selectable ('Abstract')
Display | The display (used in the display element of a Coding). If there is no display, implementers should not simply display the code, but map the concept into their application
Definition | An explanation of the meaning of the concept
Comments | Additional notes about how to use the code

4.3.14.73 Code System http://terminology.hl7.org/CodeSystem/condition-state

URL: https://hl7.org/fhir/R4/codesystem-condition-state.html
Vocabulary Work Group | Maturity Level: 0 | Informative | Use Context: Any

This is a code system defined by the FHIR project.

Summary

Defining URL: | http://terminology.hl7.org/CodeSystem/condition-state
Version: | 4.0.1
Name: | ConditionState
Title: | ConditionState
Definition: | Enumeration indicating whether the condition is currently active, inactive, or has been resolved.
Committee: | ??
OID: | 2.16.840.1.113883.4.642.4.1287 (for OID based terminology systems)
Source Resource | XML / JSON

This Code system is used in the following value sets:

• ValueSet: ConditionState (Enumeration indicating whether the condition is currently active, inactive, or has been resolved.)

• ValueSet: ConditionState (Enumeration indicating whether the condition is currently active, inactive, or has been resolved.)

4.3.14.73.1 Content

4.3.14.73.2 ConditionState

Enumeration indicating whether the condition is currently active, inactive, or has been resolved.

This code system http://terminology.hl7.org/CodeSystem/condition-state defines the following codes:

Code | Display | Definition
active | Active | The condition is active.
inactive | Inactive | The condition is inactive, but not resolved.
resolved | Resolved | The condition is resolved.

See the full registry of code systems defined as part of FHIR.

Explanation of the columns that may appear on this page:

Level | A few code lists that FHIR defines are hierarchical - each code is assigned a level. See Code System for further information.
Source | The source of the definition of the code (when the value set draws in codes defined elsewhere)
Code | The code (used as the code in the resource instance). If the code is in italics, this indicates that the code is not selectable ('Abstract')
Display | The display (used in the display element of a Coding). If there is no display, implementers should not simply display the code, but map the concept into their application
Definition | An explanation of the meaning of the concept
Comments | Additional notes about how to use the code

4.3.14.74 Code System http://terminology.hl7.org/CodeSystem/common-tags

URL: https://hl7.org/fhir/R4/codesystem-common-tags.html
FHIR Infrastructure Work Group | Maturity Level: 1 | Draft | Use Context: Any

This is a code system defined by the FHIR project.

Summary

Defining URL: | http://terminology.hl7.org/CodeSystem/common-tags
Version: | 4.0.1
Name: | CommonTags
Title: | Common Tags
Definition: | Common Tag Codes defined by FHIR project
Committee: | FHIR Infrastructure Work Group
OID: | 2.16.840.1.113883.4.642.4.1067 (for OID based terminology systems)
Source Resource | XML / JSON

This Code system is used in the following value sets:

• ValueSet: Common Tags (Common Tag Codes defined by FHIR project)
• ValueSet: Common Tags (Common Tag Codes defined by FHIR project)

4.3.14.74.1 Content

4.3.14.74.2 Common Tags

Common Tag Codes defined by FHIR project

This code system http://terminology.hl7.org/CodeSystem/common-tags defines the following codes:

Code | Display | Definition
actionable | Actionable | This request is intended to be acted upon, not merely stored

See the full registry of code systems defined as part of FHIR.

Explanation of the columns that may appear on this page:

Level | A few code lists that FHIR defines are hierarchical - each code is assigned a level. See Code System for further information.
Source | The source of the definition of the code (when the value set draws in codes defined elsewhere)
Code | The code (used as the code in the resource instance). If the code is in italics, this indicates that the code is not selectable ('Abstract')
Display | The display (used in the display element of a Coding). If there is no display, implementers should not simply display the code, but map the concept into their application
Definition | An explanation of the meaning of the concept
Comments | Additional notes about how to use the code

4.3.14.75 Code System http://terminology.hl7.org/CodeSystem/measure-scoring

URL: https://hl7.org/fhir/R4/codesystem-measure-scoring.html
Clinical Quality Information Work Group | Maturity Level: 2 | Trial Use | Use Context: Any

This is a code system defined by the FHIR project.

Summary

Defining URL: | http://terminology.hl7.org/CodeSystem/measure-scoring
Version: | 4.0.1
Name: | MeasureScoring
Title: | MeasureScoring
Definition: | The scoring type of the measure.
Committee: | Clinical Quality Information Work Group
OID: | 2.16.840.1.113883.4.642.4.1232 (for OID based terminology systems)
Source Resource | XML / JSON

This Code system is used in the following value sets:

• ValueSet: MeasureScoring (The scoring type of the measure.)
• ValueSet: MeasureScoring (The scoring type of the measure.)

4.3.14.75.1 Content

4.3.14.75.2 MeasureScoring

The scoring type of the measure.

This code system http://terminology.hl7.org/CodeSystem/measure-scoring defines the following codes:

Code | Display | Definition
proportion | Proportion | The measure score is defined using a proportion.
ratio | Ratio | The measure score is defined using a ratio.
continuous-variable | Continuous Variable | The score is defined by a calculation of some quantity.
cohort | Cohort | The measure is a cohort definition.

See the full registry of code systems defined as part of FHIR.

Explanation of the columns that may appear on this page:

Level | A few code lists that FHIR defines are hierarchical - each code is assigned a level. See Code System for further information.
Source | The source of the definition of the code (when the value set draws in codes defined elsewhere)
Code | The code (used as the code in the resource instance). If the code is in italics, this indicates that the code is not selectable ('Abstract')
Display | The display (used in the display element of a Coding). If there is no display, implementers should not simply display the code, but map the concept into their application
Definition | An explanation of the meaning of the concept
Comments | Additional notes about how to use the code

4.3.14.76 Code System http://terminology.hl7.org/CodeSystem/question-max-occurs

URL: https://hl7.org/fhir/R4/codesystem-question-max-occurs.html
Vocabulary Work Group | Maturity Level: 0 | Informative | Use Context: Any

This is a code system defined by the FHIR project.

Summary

Defining URL: | http://terminology.hl7.org/CodeSystem/question-max-occurs
Version: | 4.0.1
Name: | MaxOccurs
Title: | MaxOccurs
Definition: | Flags an element as having unlimited repetitions.
Committee: | ??
OID: | 2.16.840.1.113883.4.642.4.1272 (for OID based terminology systems)
Source Resource | XML / JSON

This Code system is used in the following value sets:

• ValueSet: MaxOccurs (Flags an element as having unlimited repetitions.)
• ValueSet: MaxOccurs (Flags an element as having unlimited repetitions.)

4.3.14.76.1 Content

4.3.14.76.2 MaxOccurs

Flags an element as having unlimited repetitions.

This code system http://terminology.hl7.org/CodeSystem/question-max-occurs defines the following codes:

Code | Display | Definition
* | Repeating | Element can repeat an unlimited number of times.

See the full registry of code systems defined as part of FHIR.

Explanation of the columns that may appear on this page:

Level | A few code lists that FHIR defines are hierarchical - each code is assigned a level. See Code System for further information.
Source | The source of the definition of the code (when the value set draws in codes defined elsewhere)
Code | The code (used as the code in the resource instance). If the code is in italics, this indicates that the code is not selectable ('Abstract')
Display | The display (used in the display element of a Coding). If there is no display, implementers should not simply display the code, but map the concept into their application
Definition | An explanation of the meaning of the concept
Comments | Additional notes about how to use the code

4.3.14.77 Code System http://hl7.org/fhir/spdx-license

URL: https://hl7.org/fhir/R4/codesystem-spdx-license.html
FHIR Infrastructure Work Group | Maturity Level: 1 | Trial Use | Use Context: Any

This is a code system defined by the FHIR project.

Summary

Defining URL: | http://hl7.org/fhir/spdx-license
Version: | 4.0.1
Name: | SPDXLicense
Title: | SPDXLicense
Definition: | The license that applies to an Implementation Guide (using an SPDX license Identifiers, or 'not-open-source'). The binding is required but new SPDX license Identifiers are allowed to be used (https://spdx.org/licenses/).
Committee: | FHIR Infrastructure Work Group
OID: | 2.16.840.1.113883.4.642.4.1027 (for OID based terminology systems)
Source Resource | XML / JSON

This Code system is used in the following value sets:

• ValueSet: SPDXLicense (The license that applies to an Implementation Guide (using an SPDX license Identifiers, or 'not-open-source'). The binding is required but new SPDX license Identifiers are allowed to be used (https://spdx.org/licenses/).)

• ValueSet: SPDXLicense (The license that applies to an Implementation Guide (using an SPDX license Identifiers, or 'not-open-source'). The binding is required but new SPDX license Identifiers are allowed to be used (https://spdx.org/licenses/).)

4.3.14.77.1 Content

4.3.14.77.2 SPDXLicense

The license that applies to an Implementation Guide (using an SPDX license Identifiers, or 'not-open-source'). The binding is required but new SPDX license Identifiers are allowed to be used (https://spdx.org/licenses/).

This code system http://hl7.org/fhir/spdx-license defines the following codes:

Code | Display | Definition
not-open-source | Not open source | Not an open source license.
0BSD | BSD Zero Clause License | BSD Zero Clause License.
AAL | Attribution Assurance License | Attribution Assurance License.
Abstyles | Abstyles License | Abstyles License.
Adobe-2006 | Adobe Systems Incorporated Source Code License Agreement | Adobe Systems Incorporated Source Code License Agreement.
Adobe-Glyph | Adobe Glyph List License | Adobe Glyph List License.
ADSL | Amazon Digital Services License | Amazon Digital Services License.
AFL-1.1 | Academic Free License v1.1 | Academic Free License v1.1.
AFL-1.2 | Academic Free License v1.2 | Academic Free License v1.2.
AFL-2.0 | Academic Free License v2.0 | Academic Free License v2.0.
AFL-2.1 | Academic Free License v2.1 | Academic Free License v2.1.
AFL-3.0 | Academic Free License v3.0 | Academic Free License v3.0.
Afmparse | Afmparse License | Afmparse License.
AGPL-1.0-only | Affero General Public License v1.0 only | Affero General Public License v1.0 only.
AGPL-1.0-or-later | Affero General Public License v1.0 or later | Affero General Public License v1.0 or later.
AGPL-3.0-only | GNU Affero General Public License v3.0 only | GNU Affero General Public License v3.0 only.
AGPL-3.0-or-later | GNU Affero General Public License v3.0 or later | GNU Affero General Public License v3.0 or later.
Aladdin | Aladdin Free Public License | Aladdin Free Public License.
AMDPLPA | AMD's plpa_map.c License | AMD's plpa_map.c License.
AML | Apple MIT License | Apple MIT License.
AMPAS | Academy of Motion Picture Arts and Sciences BSD | Academy of Motion Picture Arts and Sciences BSD.
ANTLR-PD | ANTLR Software Rights Notice | ANTLR Software Rights Notice.
Apache-1.0 | Apache License 1.0 | Apache License 1.0.
Apache-1.1 | Apache License 1.1 | Apache License 1.1.
Apache-2.0 | Apache License 2.0 | Apache License 2.0.
APAFML | Adobe Postscript AFM License | Adobe Postscript AFM License.
APL-1.0 | Adaptive Public License 1.0 | Adaptive Public License 1.0.
APSL-1.0 | Apple Public Source License 1.0 | Apple Public Source License 1.0.
APSL-1.1 | Apple Public Source License 1.1 | Apple Public Source License 1.1.
APSL-1.2 | Apple Public Source License 1.2 | Apple Public Source License 1.2.
APSL-2.0 | Apple Public Source License 2.0 | Apple Public Source License 2.0.
Artistic-1.0-cl8 | Artistic License 1.0 w/clause 8 | Artistic License 1.0 w/clause 8.
Artistic-1.0-Perl | Artistic License 1.0 (Perl) | Artistic License 1.0 (Perl).
Artistic-1.0 | Artistic License 1.0 | Artistic License 1.0.
Artistic-2.0 | Artistic License 2.0 | Artistic License 2.0.
Bahyph | Bahyph License | Bahyph License.
Barr | Barr License | Barr License.
Beerware | Beerware License | Beerware License.
BitTorrent-1.0 | BitTorrent Open Source License v1.0 | BitTorrent Open Source License v1.0.
BitTorrent-1.1 | BitTorrent Open Source License v1.1 | BitTorrent Open Source License v1.1.
Borceux | Borceux license | Borceux license.
BSD-1-Clause | BSD 1-Clause License | BSD 1-Clause License.
BSD-2-Clause-FreeBSD | BSD 2-Clause FreeBSD License | BSD 2-Clause FreeBSD License.

BSD-2-Clause-NetBSD | BSD 2-Clause NetBSD License | BSD 2-Clause NetBSD License.
BSD-2-Clause-Patent | BSD-2-Clause Plus Patent License | BSD-2-Clause Plus Patent License.
BSD-2-Clause | BSD 2-Clause "Simplified" License | BSD 2-Clause "Simplified" License.
BSD-3-Clause-Attribution | BSD with attribution | BSD with attribution.
BSD-3-Clause-Clear | BSD 3-Clause Clear License | BSD 3-Clause Clear License.
BSD-3-Clause-LBNL | Lawrence Berkeley National Labs BSD variant license | Lawrence Berkeley National Labs BSD variant license.
BSD-3-Clause-No-Nuclear-License-2014 | BSD 3-Clause No Nuclear License 2014 | BSD 3-Clause No Nuclear License 2014.
BSD-3-Clause-No-Nuclear-License | BSD 3-Clause No Nuclear License | BSD 3-Clause No Nuclear License.
BSD-3-Clause-No-Nuclear-Warranty | BSD 3-Clause No Nuclear Warranty | BSD 3-Clause No Nuclear Warranty.
BSD-3-Clause | BSD 3-Clause "New" or "Revised" License | BSD 3-Clause "New" or "Revised" License.
BSD-4-Clause-UC | BSD-4-Clause (University of California-Specific) | BSD-4-Clause (University of California-Specific).
BSD-4-Clause | BSD 4-Clause "Original" or "Old" License | BSD 4-Clause "Original" or "Old" License.
BSD-Protection | BSD Protection License | BSD Protection License.
BSD-Source-Code | BSD Source Code Attribution | BSD Source Code Attribution.
BSL-1.0 | Boost Software License 1.0 | Boost Software License 1.0.
bzip2-1.0.5 | bzip2 and libbzip2 License v1.0.5 | bzip2 and libbzip2 License v1.0.5.
bzip2-1.0.6 | bzip2 and libbzip2 License v1.0.6 | bzip2 and libbzip2 License v1.0.6.
Caldera | Caldera License | Caldera License.
CATOSL-1.1 | Computer Associates Trusted Open Source License 1.1 | Computer Associates Trusted Open Source License 1.1.
CC-BY-1.0 | Creative Commons Attribution 1.0 Generic | Creative Commons Attribution 1.0 Generic.
CC-BY-2.0 | Creative Commons Attribution 2.0 Generic | Creative Commons Attribution 2.0 Generic.
CC-BY-2.5 | Creative Commons Attribution 2.5 Generic | Creative Commons Attribution 2.5 Generic.
CC-BY-3.0 | Creative Commons Attribution 3.0 Unported | Creative Commons Attribution 3.0 Unported.
CC-BY-4.0 | Creative Commons Attribution 4.0 International | Creative Commons Attribution 4.0 International.
CC-BY-NC-1.0 | Creative Commons Attribution Non Commercial 1.0 Generic | Creative Commons Attribution Non Commercial 1.0 Generic.
CC-BY-NC-2.0 | Creative Commons Attribution Non Commercial 2.0 Generic | Creative Commons Attribution Non Commercial 2.0 Generic.
CC-BY-NC-2.5 | Creative Commons Attribution Non Commercial 2.5 Generic | Creative Commons Attribution Non Commercial 2.5 Generic.
CC-BY-NC-3.0 | Creative Commons Attribution Non Commercial 3.0 Unported | Creative Commons Attribution Non Commercial 3.0 Unported.
CC-BY-NC-4.0 | Creative Commons Attribution Non Commercial 4.0 International | Creative Commons Attribution Non Commercial 4.0 International.
CC-BY-NC-ND-1.0 | Creative Commons Attribution Non Commercial No Derivatives 1.0 Generic | Creative Commons Attribution Non Commercial No Derivatives 1.0 Generic.
CC-BY-NC-ND-2.0 | Creative Commons Attribution Non Commercial No Derivatives 2.0 Generic | Creative Commons Attribution Non Commercial No Derivatives 2.0 Generic.
CC-BY-NC-ND-2.5 | Creative Commons Attribution Non Commercial No Derivatives 2.5 Generic | Creative Commons Attribution Non Commercial No Derivatives 2.5 Generic.
CC-BY-NC-ND-3.0 | Creative Commons Attribution Non Commercial No Derivatives 3.0 Unported | Creative Commons Attribution Non Commercial No Derivatives 3.0 Unported.
CC-BY-NC-ND-4.0 | Creative Commons Attribution Non Commercial No Derivatives 4.0 International | Creative Commons Attribution Non Commercial No Derivatives 4.0 International.
CC-BY-NC-SA-1.0 | Creative Commons Attribution Non Commercial Share Alike 1.0 Generic | Creative Commons Attribution Non Commercial Share Alike 1.0 Generic.
CC-BY-NC-SA-2.0 | Creative Commons Attribution Non Commercial Share Alike 2.0 Generic | Creative Commons Attribution Non Commercial Share Alike 2.0 Generic.
CC-BY-NC-SA-2.5 | Creative Commons Attribution Non Commercial Share Alike 2.5 Generic | Creative Commons Attribution Non Commercial Share Alike 2.5 Generic.
CC-BY-NC-SA-3.0 | Creative Commons Attribution Non Commercial Share Alike 3.0 Unported | Creative Commons Attribution Non Commercial Share Alike 3.0 Unported.
CC-BY-NC-SA-4.0 | Creative Commons Attribution Non Commercial Share Alike 4.0 International | Creative Commons Attribution Non Commercial Share Alike 4.0 International.
CC-BY-ND-1.0 | Creative Commons Attribution No Derivatives 1.0 Generic | Creative Commons Attribution No Derivatives 1.0 Generic.
CC-BY-ND-2.0 | Creative Commons Attribution No Derivatives 2.0 Generic | Creative Commons Attribution No Derivatives 2.0 Generic.
CC-BY-ND-2.5 | Creative Commons Attribution No Derivatives 2.5 Generic | Creative Commons Attribution No Derivatives 2.5 Generic.
CC-BY-ND-3.0 | Creative Commons Attribution No Derivatives 3.0 Unported | Creative Commons Attribution No Derivatives 3.0 Unported.
CC-BY-ND-4.0 | Creative Commons Attribution No Derivatives 4.0 International | Creative Commons Attribution No Derivatives 4.0 International.
CC-BY-SA-1.0 | Creative Commons Attribution Share Alike 1.0 Generic | Creative Commons Attribution Share Alike 1.0 Generic.
CC-BY-SA-2.0 | Creative Commons Attribution Share Alike 2.0 Generic | Creative Commons Attribution Share Alike 2.0 Generic.
CC-BY-SA-2.5 | Creative Commons Attribution Share Alike 2.5 Generic | Creative Commons Attribution Share Alike 2.5 Generic.
CC-BY-SA-3.0 | Creative Commons Attribution Share Alike 3.0 Unported | Creative Commons Attribution Share Alike 3.0 Unported.
CC-BY-SA-4.0 | Creative Commons Attribution Share Alike 4.0 International | Creative Commons Attribution Share Alike 4.0 International.
CC0-1.0 | Creative Commons Zero v1.0 Universal | Creative Commons Zero v1.0 Universal.
CDDL-1.0 | Common Development and Distribution License 1.0 | Common Development and Distribution License 1.0.
CDDL-1.1 | Common Development and Distribution License 1.1 | Common Development and Distribution License 1.1.
CDLA-Permissive-1.0 | Community Data License Agreement Permissive 1.0 | Community Data License Agreement Permissive 1.0.

CDLA-Sharing-1.0 | Community Data License Agreement Sharing 1.0 | Community Data License Agreement Sharing 1.0.
CECILL-1.0 | CeCILL Free Software License Agreement v1.0 | CeCILL Free Software License Agreement v1.0.
CECILL-1.1 | CeCILL Free Software License Agreement v1.1 | CeCILL Free Software License Agreement v1.1.
CECILL-2.0 | CeCILL Free Software License Agreement v2.0 | CeCILL Free Software License Agreement v2.0.
CECILL-2.1 | CeCILL Free Software License Agreement v2.1 | CeCILL Free Software License Agreement v2.1.
CECILL-B | CeCILL-B Free Software License Agreement | CeCILL-B Free Software License Agreement.
CECILL-C | CeCILL-C Free Software License Agreement | CeCILL-C Free Software License Agreement.
ClArtistic | Clarified Artistic License | Clarified Artistic License.
CNRI-Jython | CNRI Jython License | CNRI Jython License.
CNRI-Python-GPL-Compatible | CNRI Python Open Source GPL Compatible License Agreement | CNRI Python Open Source GPL Compatible License Agreement.
CNRI-Python | CNRI Python License | CNRI Python License.
Condor-1.1 | Condor Public License v1.1 | Condor Public License v1.1.
CPAL-1.0 | Common Public Attribution License 1.0 | Common Public Attribution License 1.0.
CPL-1.0 | Common Public License 1.0 | Common Public License 1.0.
CPOL-1.02 | Code Project Open License 1.02 | Code Project Open License 1.02.
Crossword | Crossword License | Crossword License.
CrystalStacker | CrystalStacker License | CrystalStacker License.
CUA-OPL-1.0 | CUA Office Public License v1.0 | CUA Office Public License v1.0.
Cube | Cube License | Cube License.
curl | curl License | curl License.
D-FSL-1.0 | Deutsche Freie Software Lizenz | Deutsche Freie Software Lizenz.
diffmark | diffmark license | diffmark license.
DOC | DOC License | DOC License.
Dotseqn | Dotseqn License | Dotseqn License.
DSDP | DSDP License | DSDP License.
dvipdfm | dvipdfm License | dvipdfm License.
ECL-1.0 | Educational Community License v1.0 | Educational Community License v1.0.
ECL-2.0 | Educational Community License v2.0 | Educational Community License v2.0.
EFL-1.0 | Eiffel Forum License v1.0 | Eiffel Forum License v1.0.
EFL-2.0 | Eiffel Forum License v2.0 | Eiffel Forum License v2.0.
eGenix | eGenix.com Public License 1.1.0 | eGenix.com Public License 1.1.0.
Entessa | Entessa Public License v1.0 | Entessa Public License v1.0.
EPL-1.0 | Eclipse Public License 1.0 | Eclipse Public License 1.0.
EPL-2.0 | Eclipse Public License 2.0 | Eclipse Public License 2.0.
ErlPL-1.1 | Erlang Public License v1.1 | Erlang Public License v1.1.
EUDatagrid | EU DataGrid Software License | EU DataGrid Software License.
EUPL-1.0 | European Union Public License 1.0 | European Union Public License 1.0.
EUPL-1.1 | European Union Public License 1.1 | European Union Public License 1.1.
EUPL-1.2 | European Union Public License 1.2 | European Union Public License 1.2.
Eurosym | Eurosym License | Eurosym License.
Fair | Fair License | Fair License.
Frameworx-1.0 | Frameworx Open License 1.0 | Frameworx Open License 1.0.
FreeImage | FreeImage Public License v1.0 | FreeImage Public License v1.0.
FSFAP | FSF All Permissive License | FSF All Permissive License.
FSFUL | FSF Unlimited License | FSF Unlimited License.
FSFULLR | FSF Unlimited License (with License Retention) | FSF Unlimited License (with License Retention).
FTL | Freetype Project License | Freetype Project License.
GFDL-1.1-only | GNU Free Documentation License v1.1 only | GNU Free Documentation License v1.1 only.
GFDL-1.1-or-later | GNU Free Documentation License v1.1 or later | GNU Free Documentation License v1.1 or later.
GFDL-1.2-only | GNU Free Documentation License v1.2 only | GNU Free Documentation License v1.2 only.
GFDL-1.2-or-later | GNU Free Documentation License v1.2 or later | GNU Free Documentation License v1.2 or later.
GFDL-1.3-only | GNU Free Documentation License v1.3 only | GNU Free Documentation License v1.3 only.
GFDL-1.3-or-later | GNU Free Documentation License v1.3 or later | GNU Free Documentation License v1.3 or later.
Giftware | Giftware License | Giftware License.
GL2PS | GL2PS License | GL2PS License.
Glide | 3dfx Glide License | 3dfx Glide License.
Glulxe | Glulxe License | Glulxe License.
gnuplot | gnuplot License | gnuplot License.
GPL-1.0-only | GNU General Public License v1.0 only | GNU General Public License v1.0 only.
GPL-1.0-or-later | GNU General Public License v1.0 or later | GNU General Public License v1.0 or later.
GPL-2.0-only | GNU General Public License v2.0 only | GNU General Public License v2.0 only.
GPL-2.0-or-later | GNU General Public License v2.0 or later | GNU General Public License v2.0 or later.
GPL-3.0-only | GNU General Public License v3.0 only | GNU General Public License v3.0 only.
GPL-3.0-or-later | GNU General Public License v3.0 or later | GNU General Public License v3.0 or later.
gSOAP-1.3b | gSOAP Public License v1.3b | gSOAP Public License v1.3b.
HaskellReport | Haskell Language Report License | Haskell Language Report License.
HPND | Historical Permission Notice and Disclaimer | Historical Permission Notice and Disclaimer.
IBM-pibs | IBM PowerPC Initialization and Boot Software | IBM PowerPC Initialization and Boot Software.
ICU | ICU License | ICU License.
IJG | Independent JPEG Group License | Independent JPEG Group License.
ImageMagick | ImageMagick License | ImageMagick License.

iMatix | iMatix Standard Function Library Agreement | iMatix Standard Function Library Agreement.
Imlib2 | Imlib2 License | Imlib2 License.
Info-ZIP | Info-ZIP License | Info-ZIP License.
Intel-ACPI | Intel ACPI Software License Agreement | Intel ACPI Software License Agreement.
Intel | Intel Open Source License | Intel Open Source License.
Interbase-1.0 | Interbase Public License v1.0 | Interbase Public License v1.0.
IPA | IPA Font License | IPA Font License.
IPL-1.0 | IBM Public License v1.0 | IBM Public License v1.0.
ISC | ISC License | ISC License.
JasPer-2.0 | JasPer License | JasPer License.
JSON | JSON License | JSON License.
LAL-1.2 | Licence Art Libre 1.2 | Licence Art Libre 1.2.
LAL-1.3 | Licence Art Libre 1.3 | Licence Art Libre 1.3.
Latex2e | Latex2e License | Latex2e License.
Leptonica | Leptonica License | Leptonica License.
LGPL-2.0-only | GNU Library General Public License v2 only | GNU Library General Public License v2 only.
LGPL-2.0-or-later | GNU Library General Public License v2 or later | GNU Library General Public License v2 or later.
LGPL-2.1-only | GNU Lesser General Public License v2.1 only | GNU Lesser General Public License v2.1 only.
LGPL-2.1-or-later | GNU Lesser General Public License v2.1 or later | GNU Lesser General Public License v2.1 or later.
LGPL-3.0-only | GNU Lesser General Public License v3.0 only | GNU Lesser General Public License v3.0 only.
LGPL-3.0-or-later | GNU Lesser General Public License v3.0 or later | GNU Lesser General Public License v3.0 or later.
LGPLLR | Lesser General Public License For Linguistic Resources | Lesser General Public License For Linguistic Resources.
Libpng | libpng License | libpng License.
libtiff | libtiff License | libtiff License.
LiLiQ-P-1.1 | Licence Libre du Québec – Permissive version 1.1 | Licence Libre du Québec – Permissive version 1.1.
LiLiQ-R-1.1 | Licence Libre du Québec – Réciprocité version 1.1 | Licence Libre du Québec – Réciprocité version 1.1.
LiLiQ-Rplus-1.1 | Licence Libre du Québec – Réciprocité forte version 1.1 | Licence Libre du Québec – Réciprocité forte version 1.1.
Linux-OpenIB | Linux Kernel Variant of OpenIB.org license | Linux Kernel Variant of OpenIB.org license.
LPL-1.0 | Lucent Public License Version 1.0 | Lucent Public License Version 1.0.
LPL-1.02 | Lucent Public License v1.02 | Lucent Public License v1.02.
LPPL-1.0 | LaTeX Project Public License v1.0 | LaTeX Project Public License v1.0.
LPPL-1.1 | LaTeX Project Public License v1.1 | LaTeX Project Public License v1.1.
LPPL-1.2 | LaTeX Project Public License v1.2 | LaTeX Project Public License v1.2.
LPPL-1.3a | LaTeX Project Public License v1.3a | LaTeX Project Public License v1.3a.
LPPL-1.3c | LaTeX Project Public License v1.3c | LaTeX Project Public License v1.3c.
MakeIndex | MakeIndex License | MakeIndex License.
MirOS | MirOS License | MirOS License.
MIT-0 | MIT No Attribution | MIT No Attribution.
MIT-advertising | Enlightenment License (e16) | Enlightenment License (e16).
MIT-CMU | CMU License | CMU License.
MIT-enna | enna License | enna License.
MIT-feh | feh License | feh License.
MIT | MIT License | MIT License.
MITNFA | MIT +no-false-attribs license | MIT +no-false-attribs license.
Motosoto | Motosoto License | Motosoto License.
mpich2 | mpich2 License | mpich2 License.
MPL-1.0 | Mozilla Public License 1.0 | Mozilla Public License 1.0.
MPL-1.1 | Mozilla Public License 1.1 | Mozilla Public License 1.1.
MPL-2.0-no-copyleft-exception | Mozilla Public License 2.0 (no copyleft exception) | Mozilla Public License 2.0 (no copyleft exception).
MPL-2.0 | Mozilla Public License 2.0 | Mozilla Public License 2.0.
MS-PL | Microsoft Public License | Microsoft Public License.
MS-RL | Microsoft Reciprocal License | Microsoft Reciprocal License.
MTLL | Matrix Template Library License | Matrix Template Library License.
Multics | Multics License | Multics License.
Mup | Mup License | Mup License.
NASA-1.3 | NASA Open Source Agreement 1.3 | NASA Open Source Agreement 1.3.
Naumen | Naumen Public License | Naumen Public License.
NBPL-1.0 | Net Boolean Public License v1 | Net Boolean Public License v1.
NCSA | University of Illinois/NCSA Open Source License | University of Illinois/NCSA Open Source License.
Net-SNMP | Net-SNMP License | Net-SNMP License.
NetCDF | NetCDF license | NetCDF license.
Newsletr | Newsletr License | Newsletr License.
NGPL | Nethack General Public License | Nethack General Public License.
NLOD-1.0 | Norwegian Licence for Open Government Data | Norwegian Licence for Open Government Data.
NLPL | No Limit Public License | No Limit Public License.
Nokia | Nokia Open Source License | Nokia Open Source License.
NOSL | Netizen Open Source License | Netizen Open Source License.
Noweb | Noweb License | Noweb License.
NPL-1.0 | Netscape Public License v1.0 | Netscape Public License v1.0.
NPL-1.1 | Netscape Public License v1.1 | Netscape Public License v1.1.
NPOSL-3.0 | Non-Profit Open Software License 3.0 | Non-Profit Open Software License 3.0.

NRL | NRL License | NRL License.
NTP | NTP License | NTP License.
OCCT-PL | Open CASCADE Technology Public License | Open CASCADE Technology Public License.
OCLC-2.0 | OCLC Research Public License 2.0 | OCLC Research Public License 2.0.
ODbL-1.0 | ODC Open Database License v1.0 | ODC Open Database License v1.0.
OFL-1.0 | SIL Open Font License 1.0 | SIL Open Font License 1.0.
OFL-1.1 | SIL Open Font License 1.1 | SIL Open Font License 1.1.
OGTSL | Open Group Test Suite License | Open Group Test Suite License.
OLDAP-1.1 | Open LDAP Public License v1.1 | Open LDAP Public License v1.1.
OLDAP-1.2 | Open LDAP Public License v1.2 | Open LDAP Public License v1.2.
OLDAP-1.3 | Open LDAP Public License v1.3 | Open LDAP Public License v1.3.
OLDAP-1.4 | Open LDAP Public License v1.4 | Open LDAP Public License v1.4.
OLDAP-2.0.1 | Open LDAP Public License v2.0.1 | Open LDAP Public License v2.0.1.
OLDAP-2.0 | Open LDAP Public License v2.0 (or possibly 2.0A and 2.0B) | Open LDAP Public License v2.0 (or possibly 2.0A and 2.0B).
OLDAP-2.1 | Open LDAP Public License v2.1 | Open LDAP Public License v2.1.
OLDAP-2.2.1 | Open LDAP Public License v2.2.1 | Open LDAP Public License v2.2.1.
OLDAP-2.2.2 | Open LDAP Public License 2.2.2 | Open LDAP Public License 2.2.2.
OLDAP-2.2 | Open LDAP Public License v2.2 | Open LDAP Public License v2.2.
OLDAP-2.3 | Open LDAP Public License v2.3 | Open LDAP Public License v2.3.
OLDAP-2.4 | Open LDAP Public License v2.4 | Open LDAP Public License v2.4.
OLDAP-2.5 | Open LDAP Public License v2.5 | Open LDAP Public License v2.5.
OLDAP-2.6 | Open LDAP Public License v2.6 | Open LDAP Public License v2.6.
OLDAP-2.7 | Open LDAP Public License v2.7 | Open LDAP Public License v2.7.
OLDAP-2.8 | Open LDAP Public License v2.8 | Open LDAP Public License v2.8.
OML | Open Market License | Open Market License.
OpenSSL | OpenSSL License | OpenSSL License.
OPL-1.0 | Open Public License v1.0 | Open Public License v1.0.
OSET-PL-2.1 | OSET Public License version 2.1 | OSET Public License version 2.1.
OSL-1.0 | Open Software License 1.0 | Open Software License 1.0.
OSL-1.1 | Open Software License 1.1 | Open Software License 1.1.
OSL-2.0 | Open Software License 2.0 | Open Software License 2.0.
OSL-2.1 | Open Software License 2.1 | Open Software License 2.1.
OSL-3.0 | Open Software License 3.0 | Open Software License 3.0.
PDDL-1.0 | ODC Public Domain Dedication & License 1.0 | ODC Public Domain Dedication & License 1.0.
PHP-3.0 | PHP License v3.0 | PHP License v3.0.
PHP-3.01 | PHP License v3.01 | PHP License v3.01.
Plexus | Plexus Classworlds License | Plexus Classworlds License.
PostgreSQL | PostgreSQL License | PostgreSQL License.
psfrag | psfrag License | psfrag License.
psutils | psutils License | psutils License.
Python-2.0 | Python License 2.0 | Python License 2.0.
Qhull | Qhull License | Qhull License.
QPL-1.0 | Q Public License 1.0 | Q Public License 1.0.
Rdisc | Rdisc License | Rdisc License.
RHeCos-1.1 | Red Hat eCos Public License v1.1 | Red Hat eCos Public License v1.1.
RPL-1.1 | Reciprocal Public License 1.1 | Reciprocal Public License 1.1.
RPL-1.5 | Reciprocal Public License 1.5 | Reciprocal Public License 1.5.
RPSL-1.0 | RealNetworks Public Source License v1.0 | RealNetworks Public Source License v1.0.
RSA-MD | RSA Message-Digest License | RSA Message-Digest License.
RSCPL | Ricoh Source Code Public License | Ricoh Source Code Public License.
Ruby | Ruby License | Ruby License.
SAX-PD | Sax Public Domain Notice | Sax Public Domain Notice.
Saxpath | Saxpath License | Saxpath License.
SCEA | SCEA Shared Source License | SCEA Shared Source License.
Sendmail | Sendmail License | Sendmail License.
SGI-B-1.0 | SGI Free Software License B v1.0 | SGI Free Software License B v1.0.
SGI-B-1.1 | SGI Free Software License B v1.1 | SGI Free Software License B v1.1.
SGI-B-2.0 | SGI Free Software License B v2.0 | SGI Free Software License B v2.0.
SimPL-2.0 | Simple Public License 2.0 | Simple Public License 2.0.
SISSL-1.2 | Sun Industry Standards Source License v1.2 | Sun Industry Standards Source License v1.2.
SISSL | Sun Industry Standards Source License v1.1 | Sun Industry Standards Source License v1.1.
Sleepycat | Sleepycat License | Sleepycat License.
SMLNJ | Standard ML of New Jersey License | Standard ML of New Jersey License.
SMPPL | Secure Messaging Protocol Public License | Secure Messaging Protocol Public License.
SNIA | SNIA Public License 1.1 | SNIA Public License 1.1.
Spencer-86 | Spencer License 86 | Spencer License 86.
Spencer-94 | Spencer License 94 | Spencer License 94.
Spencer-99 | Spencer License 99 | Spencer License 99.
SPL-1.0 | Sun Public License v1.0 | Sun Public License v1.0.
SugarCRM-1.1.3 | SugarCRM Public License v1.1.3 | SugarCRM Public License v1.1.3.
SWL | Scheme Widget Library (SWL) Software License Agreement | Scheme Widget Library (SWL) Software License Agreement.

TCL | TCL/TK License | TCL/TK License.
TCP-wrappers | TCP Wrappers License | TCP Wrappers License.
TMate | TMate Open Source License | TMate Open Source License.
TORQUE-1.1 | TORQUE v2.5+ Software License v1.1 | TORQUE v2.5+ Software License v1.1.
TOSL | Trusster Open Source License | Trusster Open Source License.
Unicode-DFS-2015 | Unicode License Agreement - Data Files and Software (2015) | Unicode License Agreement - Data Files and Software (2015).
Unicode-DFS-2016 | Unicode License Agreement - Data Files and Software (2016) | Unicode License Agreement - Data Files and Software (2016).
Unicode-TOU | Unicode Terms of Use | Unicode Terms of Use.
Unlicense | The Unlicense | The Unlicense.
UPL-1.0 | Universal Permissive License v1.0 | Universal Permissive License v1.0.
Vim | Vim License | Vim License.
VOSTROM | VOSTROM Public License for Open Source | VOSTROM Public License for Open Source.
VSL-1.0 | Vovida Software License v1.0 | Vovida Software License v1.0.
W3C-19980720 | W3C Software Notice and License (1998-07-20) | W3C Software Notice and License (1998-07-20).
W3C-20150513 | W3C Software Notice and Document License (2015-05-13) | W3C Software Notice and Document License (2015-05-13).
W3C | W3C Software Notice and License (2002-12-31) | W3C Software Notice and License (2002-12-31).
Watcom-1.0 | Sybase Open Watcom Public License 1.0 | Sybase Open Watcom Public License 1.0.
Wsuipa | Wsuipa License | Wsuipa License.
WTFPL | Do What The F*ck You Want To Public License | Do What The F*ck You Want To Public License.
X11 | X11 License | X11 License.
Xerox | Xerox License | Xerox License.
XFree86-1.1 | XFree86 License 1.1 | XFree86 License 1.1.
xinetd | xinetd License | xinetd License.
Xnet | X.Net License | X.Net License.
xpp | XPP License | XPP License.
XSkat | XSkat License | XSkat License.
YPL-1.0 | Yahoo! Public License v1.0 | Yahoo! Public License v1.0.
YPL-1.1 | Yahoo! Public License v1.1 | Yahoo! Public License v1.1.
Zed | Zed License | Zed License.
Zend-2.0 | Zend License v2.0 | Zend License v2.0.
Zimbra-1.3 | Zimbra Public License v1.3 | Zimbra Public License v1.3.
Zimbra-1.4 | Zimbra Public License v1.4 | Zimbra Public License v1.4.
zlib-acknowledgement | zlib/libpng License with Acknowledgement | zlib/libpng License with Acknowledgement.
Zlib | zlib License | zlib License.
ZPL-1.1 | Zope Public License 1.1 | Zope Public License 1.1.
ZPL-2.0 | Zope Public License 2.0 | Zope Public License 2.0.
ZPL-2.1 | Zope Public License 2.1 | Zope Public License 2.1.

See the full registry of code systems defined as part of FHIR.

Explanation of the columns that may appear on this page:

Level | A few code lists that FHIR defines are hierarchical - each code is assigned a level. See Code System for further information.
Source | The source of the definition of the code (when the value set draws in codes defined elsewhere)
Code | The code (used as the code in the resource instance). If the code is in italics, this indicates that the code is not selectable ('Abstract')
Display | The display (used in the display element of a Coding). If there is no display, implementers should not simply display the code, but map the concept into their application
Definition | An explanation of the meaning of the concept
Comments | Additional notes about how to use the code

4.3.14.78 Code System http://hl7.org/fhir/contract-asset-scope

URL: https://hl7.org/fhir/R4/codesystem-contract-assetscope.html
Financial Management Work Group | Maturity Level: 1 | Draft | Use Context: Any

This is a code system defined by the FHIR project.

Summary

Defining URL: | http://hl7.org/fhir/contract-asset-scope
Version: | 4.0.1
Name: | ContractResourceAssetScopeCodes
Title: | Contract Resource Asset Scope codes
Definition: | This value set contract specific codes for asset scope.
Committee: | Financial Management Work Group
OID: | 2.16.840.1.113883.4.642.4.1294 (for OID based terminology systems)
Copyright: | HL7 International.
Source Resource | XML / JSON

This Code system is used in the following value sets:

• ValueSet: Contract Resource Asset Scope codes (This value set contract specific codes for asset scope.)
• ValueSet: Contract Resource Asset Scope codes (This value set contract specific codes for asset scope.)

4.3.14.78.1 Content

Each definition includes usage notes explaining the precedence order in contract lifecycle - i.e., while only some stages are required, the order in which they may occur is deterministic; and a map to comparable FHIR and v.3 status codes. It follows guidance about use of status codes in FHIR at http://build.fhir.org/sc.html.

4.3.14.78.2 Contract Resource Asset Scope codes

This value set contract specific codes for asset scope.

Copyright Statement:

HL7 International.

This code system http://hl7.org/fhir/contract-asset-scope defines the following codes:

Code | Display | Definition
thing | Thing | To be completed

See the full registry of code systems defined as part of FHIR.

Explanation of the columns that may appear on this page:

Level | A few code lists that FHIR defines are hierarchical - each code is assigned a level. See Code System for further information.
Source | The source of the definition of the code (when the value set draws in codes defined elsewhere)
Code | The code (used as the code in the resource instance). If the code is in italics, this indicates that the code is not selectable ('Abstract')
Display | The display (used in the display element of a Coding). If there is no display, implementers should not simply display the code, but map the concept into their application
Definition | An explanation of the meaning of the concept
Comments | Additional notes about how to use the code

4.3.14.79 Code System http://hl7.org/fhir/resource-types

URL: https://hl7.org/fhir/R4/codesystem-resource-types.html
Infrastructure And Messaging Work Group | Maturity Level: N | Normative (from v4.0.0) | Use Context: Any

| This page has been approved as part of an ANSI standard. See the Conformance Package for further details.

This is a code system defined by the FHIR project.

Summary

Defining URL: | http://hl7.org/fhir/resource-types
Version: | 4.0.1
Name: | ResourceType
Title: | ResourceType
Definition: | One of the resource types defined as part of this version of FHIR.
Committee: | Infrastructure And Messaging Work Group
OID: | (for OID based terminology systems)
Source Resource | XML / JSON

This Code System is normative - it is generated based on the information defined in this specification. The definition will remain fixed across versions, but the actual contents will change from version to version

This Code system is used in the following value sets:

• ValueSet: Care Plan Activity Kind (Resource types defined as part of FHIR that can be represented as in-line definitions of a care plan activity.)

• ValueSet: Care Plan Activity Kind (Resource types defined as part of FHIR that can be represented as in-line definitions of a care plan activity.)

• ValueSet: FHIRDefinedType (A list of all the concrete types defined in this version of the FHIR specification - Data Types and Resource Types.)

• ValueSet: Subject type (Possible types of subjects.)

• ValueSet: Audit event entity type (Code for the entity type involved in the audit event.)

• ValueSet: FHIRAllTypes (A list of all the concrete types defined in this version of the FHIR specification - Abstract Types, Data Types and Resource Types.)

• ValueSet: Consent Content Class (This value set includes the FHIR resource types, along with some other important content class codes)

• ValueSet: ResourceType (One of the resource types defined as part of this version of FHIR.)

• ValueSet: Audit event entity type (Code for the entity type involved in the audit event.)

• ValueSet: FHIRAllTypes (A list of all the concrete types defined in this version of the FHIR specification - Abstract Types, Data Types and Resource Types.)

• ValueSet: ResourceType (One of the resource types defined as part of this version of FHIR.)

• ValueSet: FHIRDefinedType (A list of all the concrete types defined in this version of the FHIR specification - Data Types and Resource Types.)

• ValueSet: Consent Content Class (This value set includes the FHIR resource types, along with some other important content class codes)

• ValueSet: Subject type (Possible types of subjects.)

4.3.14.79.1 Content

• All Languages

• English

• English (English)

• Spanish

• French

• Italian

• □□ (Chinese)

This code system http://hl7.org/fhir/resource-types defines the following codes:

Code | Display | Definition

Account | en: Account es: Cuenta zh: □□ | A financial tool for tracking value accrued for a particular purpose. In the healthcare field, used to track charges for a patient, cost centers, etc.

ActivityDefinition | en: ActivityDefinition it: DefinizioneAttivita es: DefinicionDeActividad zh: □□□□ | This resource allows for the definition of some activity to be performed, independent of a particular patient, practitioner, or other performance context.

AdverseEvent | en: AdverseEvent it: EventoAvverso es: EventoAdverso zh: □□□□ | Actual or potential/avoided event causing unintended physical injury resulting from or contributed to by medical care, a research study or other healthcare setting factors that requires additional monitoring, treatment, or hospitalization, or that results in death.

AllergyIntolerance | en: AllergyIntolerance it: AllergiaIntolleranza fr: IntoléranceAllergique es: AllergiaIntolerancia zh: □□□□□□□□ | Risk of harmful or undesirable, physiological response which is unique to an individual and associated with exposure to a substance.

Appointment | en: Appointment it: Appuntamento fr: RendezVous es: Cita zh: □□ | A booking of a healthcare event among patient(s), practitioner(s), related person(s) and/or device(s) for a specific date/time. This may result in one or more Encounter(s).

AppointmentResponse | en: AppointmentResponse it: RispostaAppuntamento fr: RéponseRendezVous es: CitaRespuesta zh: □□□□ | A reply to an appointment request for a patient and/or practitioner(s), such as a confirmation or rejection.

AuditEvent | en: AuditEvent fr: ÉvènementSécurité es: EventoSeguridad zh: □□□□ | A record of an event made for purposes of maintaining a security log. Typical uses include detection of intrusion attempts and monitoring for inappropriate usage.

Basic | en: Basic fr: Basique es: Basico zh: □□□□ | Basic is used for handling concepts not yet defined in FHIR, narrative-only resources that don't map to an existing resource, and custom resources not appropriate for inclusion in the FHIR specification.

Binary | en: Binary it: Binario fr: Binaire es: Binario zh: □□□□□ | A resource that represents the data of a single raw artifact as digital content accessible in its native format. A Binary resource can contain any content, whether text, image, pdf, zip archive, etc.

BiologicallyDerivedProduct | BiologicallyDerivedProduct | A material substance originating from a biological entity intended to be transplanted or infused into another (possibly the same) biological entity.

BodyStructure | en: BodyStructure it: StrutturaDelCorpo fr: MorphologieDeCorps es: EstructuraDelCuerpo zh: □□□□ | Record details about an anatomical structure. This resource may be used when a coded concept does not provide the necessary detail needed for the use case.

Bundle | en: Bundle fr: Paquet es: Paquete zh: □□ | A container for a collection of resources.

CapabilityStatement | en: CapabilityStatement es: DeclaracionDeCapacidad zh: □□□□ | A Capability Statement documents a set of capabilities (behaviors) of a FHIR Server for a particular version of FHIR that may be used as a statement of actual server functionality or a statement of required or desired server implementation.

CarePlan | en: CarePlan it: PianoDiCura fr: PlanDeSoins es: PlanDeCuidado zh: □□□□ | Describes the intention of how one or more practitioners intend to deliver care for a particular patient, group or community for a period of time, possibly limited to care for a specific condition or set of conditions.

CareTeam | en: CareTeam es: EquipoDeCuidado zh: □□□□ | The Care Team includes all the people and organizations who plan to participate in the coordination and delivery of care for a patient.

CatalogEntry | en: CatalogEntry es: EntradaDeCatalogo zh: □□□□ | Catalog entries are wrappers that contextualize items included in a catalog.

ChargeItem | en: ChargeItem es: CargoDeItem zh: □□□□ | The resource ChargeItem describes the provision of healthcare provider products for a certain patient, therefore referring not only to the product, but containing in addition details of the provision, like date, time, amounts and participating organizations and persons. Main Usage of the ChargeItem is to enable the billing process and internal cost allocation.

ChargeItemDefinition | ChargeItemDefinition | The ChargeItemDefinition resource provides the properties that apply to the (billing) codes necessary to calculate costs and prices. The properties may differ largely depending on type and realm, therefore this resource gives only a rough structure and requires profiling for each type of billing code system.

Claim | en: Claim fr: Réclamation es: Reclamación / Factura zh: □□ | A provider issued list of professional services and products which have been provided, or are to be provided, to a patient which is sent to an insurer for reimbursement.

ClaimResponse | en: ClaimResponse fr: RéponseARéclamation zh: □□□□ | This resource provides the adjudication details from the processing of a Claim resource.

ClinicalImpression | en: ClinicalImpression it: ImpressioneClinica fr: ImpressionClinique es: HallazgoClinico zh: □□□□ | A record of a clinical assessment performed to determine what problem(s) may affect the patient and before planning the treatments or management strategies that are best to manage a patient's condition. Assessments are often 1:1 with a clinical consultation / encounter, but this varies greatly depending on the clinical workflow. This resource is called "ClinicalImpression" rather than "ClinicalAssessment" to avoid confusion with the recording of assessment tools such as Apgar score.

CodeSystem | en: CodeSystem it: SistemaDiCodifica es: SistemaDeCodigos zh: □□□□ | The CodeSystem resource is used to declare the existence of and describe a code system or code system supplement and its key properties, and optionally define a part or all of its content.

Communication | en: Communication it: Comunicazione es: Comunicación zh: □□ | An occurrence of information being transmitted; e.g. an alert that was sent to a responsible provider, a public health agency that was notified about a reportable condition.

CommunicationRequest | en: CommunicationRequest it: RichiestaDiComunicazione fr: DemandeDeCommunication es: ComunicaciónRequerimiento zh: □□□□ | A request to convey information; e.g. the CDS system proposes that an alert be sent to a responsible provider, the CDS system proposes that the public health agency be notified about a reportable condition.

CompartmentDefinition | en: CompartmentDefinition es: DefinicionDeCompartimento zh: □□□□□□ | A compartment definition that defines how resources are accessed on a server.

Composition | en: Composition it: Composizione es: Composición zh: □□□□□ | A set of healthcare-related information that is assembled together into a single logical package that provides a single coherent statement of meaning, establishes its own context and that has clinical attestation with regard to who is making the statement. A Composition defines the structure and narrative content necessary for a document. However, a Composition alone does not constitute a document. Rather, the Composition must be the first entry in a Bundle where Bundle.type=document, and any other resources referenced from Composition must be included as subsequent entries in the Bundle (for example Patient, Practitioner, Encounter, etc.).

ConceptMap | en: ConceptMap it: MappaDiConcetti fr: CarteDeConcepts es: MapaDeConceptos zh: □□□□ | A statement of relationships from one set of concepts to one or more other concepts - either concepts in code systems, or data element/data element concepts, or classes in class models.

Condition | en: Condition it: Condizione es: Condición zh: □□ | A clinical condition, problem, diagnosis, or other event, situation, issue, or clinical concept that has risen to a level of concern.

Consent | en: Consent it: Consenso es: Consentimiento zh: □□□ | A record of a healthcare consumer’s choices, which permits or denies identified recipient(s) or recipient role(s) to perform one or more actions within a given policy context, for specific purposes and periods of time.

Contract | en: Contract it: Contratto fr: Contrat es: Contato zh: □□ | Legally enforceable, formally recorded unilateral or bilateral directive i.e., a policy or agreement.

Coverage | en: Coverage it: Copertura fr: Couverture es: Cobertura zh: □□□□ | Financial instrument which may be used to reimburse or pay for health care products and services. Includes both insurance and self-payment.

CoverageEligibilityRequest | en: CoverageEligibilityRequest it: RichiestaEleggibilitaCopertura fr: CouvertureDemandeEligibilité zh: □□□□ | The CoverageEligibilityRequest provides patient and insurance coverage information to an insurer for them to respond, in the form of an CoverageEligibilityResponse, with information regarding whether the stated coverage is valid and in-force and optionally to provide the insurance details of the policy.

CoverageEligibilityResponse | en: CoverageEligibilityResponse it: RispostaEleggibilitaCopertura fr: RéponseEligibilitéCouverture zh: □□□□ | This resource provides eligibility and plan details from the processing of an CoverageEligibilityRequest resource.

DetectedIssue | en: DetectedIssue it: ProblemaRilevato fr: Problème Détecté es: Problema-Detectado /ProblemaDetectado zh: □□□□□ | Indicates an actual or potential clinical issue with or between one or more active or proposed clinical actions for a patient; e.g. Drug-drug interaction, Ineffective treatment frequency, Procedure-condition conflict, etc.

Device | en: Device it: Dispositivo fr: Dispositif es: Dispositivo zh: □□ | A type of a manufactured item that is used in the provision of healthcare without being substantially changed through that activity. The device may be a medical or non-medical device.

DeviceDefinition | en: DeviceDefinition fr: DéfinitionDeDispositif es: DefiniciónDeDispositivo zh: □□□□ | The characteristics, operational status and capabilities of a medical-related component of a medical device.

DeviceMetric | en: DeviceMetric fr: MétriqueDispositif es: MetricaDeDispositivo zh: □□□□ | Describes a measurement, calculation or setting capability of a medical device.

DeviceRequest | en: DeviceRequest it: RichiestaDispositivo fr: DemandeUtilisationDispositif es: SolicitudDeDispositivo zh: □□□□ | Represents a request for a patient to employ a medical device. The device may be an implantable device, or an external assistive device, such as a walker.

DeviceUseStatement | en: DeviceUseStatement zh: □□□□□□ | A record of a device being used by a patient where the record is the result of a report from the patient or another clinician.

DiagnosticReport | en: DiagnosticReport it: RefertoDiagnostico fr: RapportDiagnostique zh: □□□□ es: InformeDiagnostico | The findings and interpretation of diagnostic tests performed on patients, groups of patients, devices, and locations, and/or specimens derived from these. The report includes clinical context such as requesting and provider information, and some mix of atomic results, images, textual and coded interpretations, and formatted representation of diagnostic reports.

DocumentManifest | en: DocumentManifest fr: Manifeste zh: □□□□ es: ManifestoDocumento | A collection of documents compiled for a purpose together with metadata that applies to the collection.

DocumentReference | en: DocumentReference it: RiferimentoDocumento fr: RéférenceDocument es: ReferenciaDocumento zh: □□□□ | A reference to a document of any kind for any purpose. Provides metadata about the document so that the document can be discovered and managed. The scope of a document is any seralized object with a mime-type, so includes formal patient centric documents (CDA), cliical notes, scanned paper, and non-patient specific documents like policy text.

DomainResource | en: DomainResource es: RecursoDeDominio zh: □□□□ | A resource that includes narrative, extensions, and contained resources.

EffectEvidenceSynthesis | EffectEvidenceSynthesis | The EffectEvidenceSynthesis resource describes the difference in an outcome between exposures states in a population where the effect estimate is derived from a combination of research studies.

Encounter | en: Encounter fr: Venue zh: □□□□ es: Encuentro | An interaction between a patient and healthcare provider(s) for the purpose of providing healthcare service(s) or assessing the health status of a patient.

Endpoint | en: Endpoint zh: □□ | The technical details of an endpoint that can be used for electronic services, such as for web services providing XDS.b or a REST endpoint for another FHIR server. This may include any security context information.

EnrollmentRequest | en: EnrollmentRequest it: RichiestaIscrizione fr: DemandeInscription es: SolicitudDeEnrolamiento zh: □□□□□□ | This resource provides the insurance enrollment details to the insurer regarding a specified coverage.

EnrollmentResponse | en: EnrollmentResponse it: RispostaIscrizione fr: RéponseInscription es: RespuestaDeEnrolamiento zh: □□□□□□ | This resource provides enrollment and plan details from the processing of an EnrollmentRequest resource.

EpisodeOfCare | en: EpisodeOfCare it: EpisodioDiCura fr: ÉpisodeDeSoins es: EpisodioDeCuidado zh: □□□□□□ | An association between a patient and an organization / healthcare provider(s) during which time encounters may occur. The managing organization assumes a level of responsibility for the patient during this time.

EventDefinition | en: EventDefinition it: DefinizioneEvento es: DefinitionDeEvento zh: □□□□ | The EventDefinition resource provides a reusable description of when a particular event can occur.

Evidence | Evidence | The Evidence resource describes the conditional state (population and any exposures being compared within the population) and outcome (if specified) that the knowledge (evidence, assertion, recommendation) is about.

EvidenceVariable | EvidenceVariable | The EvidenceVariable resource describes a "PICO" element that knowledge (evidence, assertion, recommendation) is about.

ExampleScenario | en: ExampleScenario it: ScenarioDiEsempio es: EjemploDeEscenario zh: □□□□ | Example of workflow instance.

ExplanationOfBenefit | en: ExplanationOfBenefit fr: ExplicationDuBénéfice zh: □□□□ | This resource provides: the claim details; adjudication details from the processing of a Claim; and optionally account balance information, for informing the subscriber of the

benefits provided.

FamilyMemberHistory | en: FamilyMemberHistory fr: HistoireMembreFamille es: HistorialMiembroFamiliar zh: □□□ | Significant health conditions for a person related to the patient relevant in the context of care for the patient.

Flag | en: Flag fr: Drapeau es: Bandera zh: □□ | Prospective warnings of potential issues when providing care to the patient.

Goal | en: Goal fr: But es: Objetivo zh: □□ | Describes the intended objective(s) for a patient, group or organization care, for example, weight loss, restoring an activity of daily living, obtaining herd immunity via immunization, meeting a process improvement objective, etc.

GraphDefinition | en: GraphDefinition es: DefinitionGrafico zh: □□□□ | A formal computable definition of a graph of resources - that is, a coherent set of resources that form a graph by following references. The Graph Definition resource defines a set and makes rules about the set.

Group | en: Group it: Gruppo fr: Groupe es: Grupo zh: □□ | Represents a defined collection of entities that may be discussed or acted upon collectively but which are not expected to act collectively, and are not formally or legally recognized; i.e. a collection of entities that isn't an Organization.

GuidanceResponse | en: GuidanceResponse es: RespuestaDeOrientacion zh: □□□□□□ | A guidance response is the formal response to a guidance request, including any output parameters returned by the evaluation, as well as the description of any proposed actions to be taken.

HealthcareService | en: HealthcareService it: ServizioSanitario fr: ServiceDeSanté es: ServicioDeCuidado zh: □□□□□□□□ | The details of a healthcare service available at a location.

ImagingStudy | en: ImagingStudy fr: EtudeImagerie es: EstudioImagen / EstudioImagen zh: □□□□ | Representation of the content produced in a DICOM imaging study. A study comprises a set of series, each of which includes a set of Service-Object Pair Instances (SOP Instances - images or other data) acquired or produced in a common context. A series is of only one modality (e.g. X-ray, CT, MR, ultrasound), but a study may have multiple series of different modalities.

Immunization | en: Immunization it: Immunizzazione fr: Immunisation zh: □□□□ es: Inmunización | Describes the event of a patient being administered a vaccine or a record of an immunization as reported by a patient, a clinician or another party.

ImmunizationEvaluation | ImmunizationEvaluation | Describes a comparison of an immunization event against published recommendations to determine if the administration is "valid" in relation to those recommendations.

ImmunizationRecommendation | en: ImmunizationRecommendation fr: RecommendationImmunisation zh: □□□□□□ es: RecomendaciónInmunización / | A patient's point-in-time set of recommendations (i.e. forecasting) according to a published schedule with optional supporting justification.

ImplementationGuide | en: ImplementationGuide es: GuiaDeImplementacion zh: □□□□ | A set of rules of how a particular interoperability or standards problem is solved - typically through the use of FHIR resources. This resource is used to gather all the parts of an implementation guide into a logical whole and to publish a computable definition of all the parts.

InsurancePlan | InsurancePlan | Details of a Health Insurance product/plan provided by an organization.

Invoice | Invoice | Invoice containing collected ChargeItems from an Account with calculated individual and total price for Billing purpose.

Library | en: Library es: Librería zh: □ | The Library resource is a general-purpose container for knowledge asset definitions. It can be used to describe and expose existing knowledge assets such as logic libraries and information model descriptions, as well as to describe a collection of knowledge assets.

Linkage | en: Linkage es: Enlace / Conexión / Vinculo / Acoplamiento zh: □□□□ | Identifies two or more records (resource instances) that refer to the same real-world "occurrence".

List | en: List it: Lista fr: Liste zh: □□ es: Lista | A list is a curated collection of resources.

Location | en: Location fr: Localisation zh: □□ es: Locacion | Details and position information for a physical place where services are provided and resources and participants may be stored, found, contained, or accommodated.

Measure | en: Measure it: Misura es: Medida zh: □□ | The Measure resource provides the definition of a quality measure.

MeasureReport | en: MeasureReport es: ReporteMedida zh: □□□□ | The MeasureReport resource contains the results of the calculation of a measure; and optionally a reference to the resources involved in that calculation.

Media | en: Media fr: Média es: Medio zh: □□ | A photo, video, or audio recording acquired or used in healthcare. The actual content may be inline or provided by direct reference.

Medication | en: Medication fr: Médication zh: □□ es: Medicación /Medicamento | This resource is primarily used for the identification and definition of a medication for the purposes of prescribing, dispensing, and administering a medication as well as for making statements about medication use.

MedicationAdministration | en: MedicationAdministration fr: AdministrationMédicaments zh: □□□□ es: AdministraciónMedicación / AdministracionMedicamento | Describes the event of a patient consuming or otherwise being administered a medication. This may be as simple as swallowing a tablet or it may be a long running infusion. Related resources tie this event to the authorizing prescription, and the specific encounter between patient and health care practitioner.

MedicationDispense | en: MedicationDispense fr: DispensationMédicaments zh: □□□□ es: DispensaciónMedicación /DispensacionMedicamento | Indicates that a medication product is to be or has been dispensed for a named person/patient. This includes a description of the medication product (supply) provided and the instructions for administering the medication. The medication dispense is the result of a pharmacy system responding to a medication order.

MedicationKnowledge | MedicationKnowledge | Information about a medication that is used to support knowledge.

MedicationRequest | en: MedicationRequest fr: PrescriptionMédicamenteuseTODO zh: □□□□ es: PrescripciónMedicaciónTODO /PrescripcionMedicamento | An order or request for both supply of the medication and the instructions for administration of the medication to a patient. The resource is called "MedicationRequest" rather than "MedicationPrescription" or "MedicationOrder" to generalize the use across inpatient and outpatient settings, including care plans, etc., and to harmonize with workflow patterns.

MedicationStatement | en: MedicationStatement fr: ÉtatMédication zh: □□□□ es: ResumenMedicación /ResumenMedicamento | A record of a medication that is being consumed by a patient. A MedicationStatement may indicate that the patient may be taking the medication now or has taken the medication in the past or will be taking the medication in the future. The source of this information can be the patient, significant other (such as a family member or spouse), or a clinician. A common scenario where this information is captured is during the history taking process during a patient visit or stay. The medication information may come from sources such as the patient's memory, from a prescription bottle, or from a list of medications the patient, clinician or other party maintains. The primary difference between a medication statement and a medication administration is that the medication administration has complete administration information and is based on actual administration information from the person who administered the medication. A medication statement is often, if not always, less specific. There is no required date/time when the medication was administered, in fact we only know that a source has reported the patient is taking this medication, where details such as time, quantity, or rate or even medication product may be incomplete or missing or less precise. As stated earlier, the medication statement information may come from the patient's memory, from a prescription bottle or from a list of medications the patient, clinician or other party maintains. Medication administration is more formal and is not

missing detailed information.
MedicinalProduct | en: MedicinalProduct it: ProdottoMedicinale | Detailed definition of a medicinal product, typically for uses other than direct patient care (e.g. regulatory use).
MedicinalProductAuthorization | en: MedicinalProductAuthorization it: AutorizzazioneProdottoMedicinale | The regulatory authorization of a medicinal product.
MedicinalProductContraindication | MedicinalProductContraindication | The clinical particulars - indications, contraindications etc. of a medicinal product, including for regulatory purposes.
MedicinalProductIndication | en: MedicinalProductIndication en: MedicinalProductInteraction | Indication for the Medicinal Product.
MedicinalProductIngredient | en: MedicinalProductIngredient it: IngredienteProdottoMedicinale | An ingredient of a manufactured item or pharmaceutical product.
MedicinalProductInteraction | MedicinalProductInteraction | The interactions of the medicinal product with other medicinal products, or other forms of interactions.
MedicinalProductManufactured | MedicinalProductManufactured | The manufactured item as contained in the packaged medicinal product.
MedicinalProductPackaged | MedicinalProductPackaged | A medicinal product in a container or package.
MedicinalProductPharmaceutical | MedicinalProductPharmaceutical | A pharmaceutical product described in terms of its composition and dose form.
MedicinalProductUndesirableEffect | MedicinalProductUndesirableEffect | Describe the undesirable effects of the medicinal product.
MessageDefinition | en: MessageDefinition it: DefinizioneMessaggio es: DefinicionMensaje zh: □□□□ | Defines the characteristics of a message that can be shared between systems, including the type of event that initiates the message, the content to be transmitted and what response(s), if any, are permitted.
MessageHeader | en: MessageHeader fr: EntêteMessage zh: □□□□ es: CabeceraMensaje | The header for a message exchange that is either requesting or responding to an action. The reference(s) that are the subject of the action as well as other information related to the action are typically transmitted in a bundle in which the MessageHeader resource instance is the first resource in the bundle.
MolecularSequence | en: MolecularSequence es: SecuenciaMolecular zh: □□□□ | Raw data describing a biological sequence.
NamingSystem | en: NamingSystem fr: SystèmeDeNommage es: SistemaDeNombres zh: □□□□ | A curated namespace that issues unique symbols within that namespace for the identification of concepts, people, devices, etc. Represents a "System" used within the Identifier and Coding data types.
NutritionOrder | en: NutritionOrder fr: OrdreNutrition es: OrdenNutrición zh: □□□□ | A request to supply a diet, formula feeding (enteral) or oral nutritional supplement to a patient/resident.
Observation | en: Observation it: Osservazione zh: □□ es: Observación | Measurements and simple assertions made about a patient, device or other subject.
ObservationDefinition | en: ObservationDefinition it: DefinizioneOsservazione es: DefinicionDeEspecimen zh: □□□□ | Set of definitional characteristics for a kind of observation or measurement produced or consumed by an orderable health care service.
OperationDefinition | en: OperationDefinition it: DefinizioneOperazione fr: DéfinitionOpération es: DefinicionDeOperacion zh: □□□□ | A formal computable definition of an operation (on the RESTful interface) or a named query (using the search interaction).
OperationOutcome | en: OperationOutcome it: RisultatoOperazione fr: RésultatOpération zh: □□□□ es: ResultadoOperación | A collection of error, warning, or information messages that result from a system action.
Organization | en: Organization it: Organizzazione fr: Organisation zh: □□□□ es: Organización | A formally or informally recognized grouping of people or organizations formed for the purpose of achieving some form of collective action. Includes companies, institutions, corporations, departments, community groups, healthcare practice groups, payer/insurer, etc.
OrganizationAffiliation | OrganizationAffiliation | Defines an affiliation/assotiation/relationship between 2 distinct oganizations, that is not a part-of relationship/sub-division relationship.
Parameters | en: Parameters es: Parametros zh: □□ | This resource is a non-persisted resource used to pass information into and back from an [operation](operations.html). It has no other use, and there is no RESTful endpoint associated with it.
Patient | en: Patient it: Paziente zh: □□ es: Paciente | Demographics and other administrative information about an individual or animal receiving care or other health-related services.
PaymentNotice | en: PaymentNotice it: AvvisoDiPagamento fr: AvisPaiement es: AvisoDePago zh: □□□□ | This resource provides the status of the payment for goods and services rendered, and the request and response resource references.
PaymentReconciliation | en: PaymentReconciliation it: RiconciliazionePagamento fr: RéconciliationPaiement es: ConciliacionDePago zh: □□□□ | This resource provides the details including amount of a payment and allocates the payment items being paid.
Person | en: Person it: Persona fr: Personne es: Persona zh: □□ | Demographics and administrative information about a person independent of a specific health-related context.
PlanDefinition | en: PlanDefinition es: DefinicionDePlan zh: □□□□ | This resource allows for the definition of various types of plans as a sharable, consumable, and executable artifact. The resource is general enough to support the description of a broad range of clinical artifacts such as clinical decision support rules, order sets and protocols.
Practitioner | en: Practitioner fr: Praticien zh: □□□□ es: Practicante / Profesional | A person who is directly or indirectly involved in the provisioning of healthcare.
PractitionerRole | en: PractitionerRole es: RolProfesional zh: □□□□□□ | A specific set of Roles/Locations/specialties/services that a practitioner may perform at an organization for a period of time.
Procedure | en: Procedure it: Procedura fr: Procédure zh: □□□□ es: Procedimiento | An action that is or was performed on or for a patient. This can be a physical intervention like an operation, or less invasive like long term services, counseling, or hypnotherapy.
Provenance | en: Provenance it: Provenienza zh: □□ es: Procedencia | Provenance of a resource is a record that describes entities and processes involved in producing and delivering or otherwise influencing that resource. Provenance provides a critical foundation for assessing authenticity, enabling trust, and allowing reproducibility. Provenance assertions are a form of contextual metadata and can themselves become important records with their own provenance. Provenance statement indicates clinical significance in terms of confidence in authenticity, reliability, and trustworthiness, integrity, and stage in lifecycle (e.g. Document Completion - has the artifact been legally authenticated), all of which may impact security, privacy, and trust policies.
Questionnaire | en: Questionnaire it: Questionario zh: □□□□ es: Cuestionario | A structured set of questions intended to guide the collection of answers from end-users. Questionnaires provide detailed control over order, presentation, phraseology and grouping to allow coherent, consistent data collection.
QuestionnaireResponse | en: QuestionnaireResponse it: RispostaQuestionario fr: RéponseQuestionnaire es: RespuestaAlCuestionario zh: □□□□□□ | A structured set of questions and their answers. The questions are ordered and grouped into

coherent subsets, corresponding to the structure of the grouping of the questionnaire being responded to.

RelatedPerson | en: RelatedPerson it: PersonaCorrelata fr: PersonneEnRelation es: PersonaRelacionada zh: □□□□ | Information about a person that is involved in the care for a patient, but who is not the target of healthcare, nor has a formal responsibility in the care process.

RequestGroup | en: RequestGroup it: GruppoDiRichieste es: GrupoDeSolicitudes zh: □□□□ | A group of related requests that can be used to capture intended activities that have inter-dependencies such as "give this medication after that one".

ResearchDefinition | ResearchDefinition | The ResearchDefinition resource describes the conditional state (population and any exposures being compared within the population) and outcome (if specified) that the knowledge (evidence, assertion, recommendation) is about.

ResearchElementDefinition | ResearchElementDefinition | The ResearchElementDefinition resource describes a "PICO" element that knowledge (evidence, assertion, recommendation) is about.

ResearchStudy | en: ResearchStudy es: EstudioDeInvestigacion zh: □□□□ | A process where a researcher or organization plans and then executes a series of steps intended to increase the field of healthcare-related knowledge. This includes studies of safety, efficacy, comparative effectiveness and other information about medications, devices, therapies and other interventional and investigative techniques. A ResearchStudy involves the gathering of information about human or animal subjects.

ResearchSubject | en: ResearchSubject es: SujetoDeInvestigacion zh: □□□□ | A physical entity which is the primary unit of operational and/or administrative interest in a study.

Resource | en: Resource es: Recurso zh: □□ | This is the base resource type for everything.

RiskAssessment | en: RiskAssessment fr: ÉvaluationRisques es: EvaluacionDeRiesgo zh: □□□□ | An assessment of the likely outcome(s) for a patient or other subject as well as the likelihood of each outcome.

RiskEvidenceSynthesis | RiskEvidenceSynthesis | The RiskEvidenceSynthesis resource describes the likelihood of an outcome in a population plus exposure state where the risk estimate is derived from a combination of research studies.

Schedule | en: Schedule es: Agenda zh: □□□□ | A container for slots of time that may be available for booking appointments.

SearchParameter | en: SearchParameter it: ParametroDiRicerca fr: ParamètreRecherche es: ParametroDeBusqueda zh: □□□□ | A search parameter that defines a named search item that can be used to search/filter on a resource.

ServiceRequest | en: ServiceRequest it: RichiestaDiServizio fr: DemandeService es: PeticiónServicio zh: □□□□□□ | A record of a request for service such as diagnostic investigations, treatments, or operations to be performed.

Slot | en: Slot zh: □□ es: Hueco / Zocalo / Espacio | A slot of time on a schedule that may be available for booking appointments.

Specimen | en: Specimen it: Campione fr: Spécimen zh: □□ es: Especimen | A sample to be used for analysis.

SpecimenDefinition | en: SpecimenDefinition it: DefinizioneCampione es: DefinicionDeEspecimen zh: □□□□ | A kind of specimen with associated set of requirements.

StructureDefinition | en: StructureDefinition it: DefinizioneStruttura fr: DéfinitionStructure es: DefinicionDeEstructura zh: □□□□ | A definition of a FHIR structure. This resource is used to describe the underlying resources, data types defined in FHIR, and also for describing extensions and constraints on resources and data types.

StructureMap | en: StructureMap es: MapaDeEstructura zh: □□□□ | A Map of relationships between 2 structures that can be used to transform data.

Subscription | en: Subscription it: Sottoscrizione fr: Souscription zh: □□ es: Suscripción | The subscription resource is used to define a push-based subscription from a server to another system. Once a subscription is registered with the server, the server checks every resource that is created or updated, and if the resource matches the given criteria, it sends a message on the defined "channel" so that another system can take an appropriate action.

Substance | en: Substance it: Sostanza zh: □□ es: Sustancia | A homogeneous material with a definite composition.

SubstanceNucleicAcid | SubstanceNucleicAcid | Nucleic acids are defined by three distinct elements: the base, sugar and linkage. Individual substance/moiety IDs will be created for each of these elements. The nucleotide sequence will be always entered in the 5’-3’ direction.

SubstancePolymer | SubstancePolymer | Todo.

SubstanceProtein | SubstanceProtein | A SubstanceProtein is defined as a single unit of a linear amino acid sequence, or a combination of subunits that are either covalently linked or have a defined invariant stoichiometric relationship. This includes all synthetic, recombinant and purified SubstanceProteins of defined sequence, whether the use is therapeutic or prophylactic. This set of elements will be used to describe albumins, coagulation factors, cytokines, growth factors, peptide/SubstanceProtein hormones, enzymes, toxins, toxoids, recombinant vaccines, and immunomodulators.

SubstanceReferenceInformation | SubstanceReferenceInformation | Todo.

SubstanceSourceMaterial | SubstanceSourceMaterial | Source material shall capture information on the taxonomic and anatomical origins as well as the fraction of a material that can result in or can be modified to form a substance. This set of data elements shall be used to define polymer substances isolated from biological matrices. Taxonomic and anatomical origins shall be described using a controlled vocabulary as required. This information is captured for naturally derived polymers (. starch) and structurally diverse substances. For Organisms belonging to the Kingdom Plantae the Substance level defines the fresh material of a single species or infraspecies, the Herbal Drug and the Herbal preparation. For Herbal preparations, the fraction information will be captured at the Substance information level and additional information for herbal extracts will be captured at the Specified Substance Group 1 information level. See for further explanation the Substance Class: Structurally Diverse and the herbal annex.

SubstanceSpecification | SubstanceSpecification | The detailed description of a substance, typically at a level beyond what is used for prescribing.

SupplyDelivery | en: SupplyDelivery fr: Supply Livraison zh: □□□□ es: Entrega de Suministro | Record of delivery of what is supplied.

SupplyRequest | en: SupplyRequest fr: Demande d'approvisionnement zh: □□□□ es: Solicitud de Suministro | A record of a request for a medication, substance or device used in the healthcare setting.

Task | en: Task es: Tarea zh: □□ | A task to be performed.

TerminologyCapabilities | en: TerminologyCapabilities es: CapacidadTerminologica zh: □□□□□□ | A TerminologyCapabilities resource documents a set of capabilities (behaviors) of a FHIR Terminology Server that may be used as a statement of actual server functionality or a statement of required or desired server implementation.

TestReport | en: TestReport fr: RapportTest es: ReporteDePrueba zh: □□□□ | A summary of information based on the results of executing a TestScript.

TestScript | en: TestScript fr: ScriptTest es: ScriptDePrueba zh: □□□□ | A structured set of tests against a FHIR server or client implementation to determine compliance against the FHIR specification.

ValueSet | en: ValueSet fr: EnsembleValeurs zh: □□□□ es: ConjuntoValores / ConjuntoDeValores | A ValueSet resource instance specifies a set of codes drawn from one or more code systems, intended for use in a particular context. Value sets link between [[[CodeSystem]]] definitions and their use in [coded elements](terminologies.html).

VerificationResult | VerificationResult | Describes validation requirements, source(s), status and dates for one or more elements.

VisionPrescription | en: VisionPrescription fr: PrescriptionVision es: PrescripcionDeVision zh: □□□□ | An authorization for the provision of glasses and/or contact lenses to a patient.

This code system http://hl7.org/fhir/resource-types defines the following codes:

Code | Display | Definition

Account | Account | A financial tool for tracking value accrued for a particular purpose. In the healthcare field, used to track charges for a patient, cost centers, etc.

ActivityDefinition | ActivityDefinition | This resource allows for the definition of some activity to be performed, independent of a particular patient, practitioner, or other performance context.

AdverseEvent | AdverseEvent | Actual or potential/avoided event causing unintended physical injury resulting from or contributed to by medical care, a research study or other healthcare setting factors that requires additional monitoring, treatment, or hospitalization, or that results in death.

AllergyIntolerance | AllergyIntolerance | Risk of harmful or undesirable, physiological response which is unique to an individual and associated with exposure to a substance.

Appointment | Appointment | A booking of a healthcare event among patient(s), practitioner(s), related person(s) and/or device(s) for a specific date/time. This may result in one or more Encounter(s).

AppointmentResponse | AppointmentResponse | A reply to an appointment request for a patient and/or practitioner(s), such as a confirmation or rejection.

AuditEvent | AuditEvent | A record of an event made for purposes of maintaining a security log. Typical uses include detection of intrusion attempts and monitoring for inappropriate usage.

Basic | Basic | Basic is used for handling concepts not yet defined in FHIR, narrative-only resources that don't map to an existing resource, and custom resources not appropriate for inclusion in the FHIR specification.

Binary | Binary | A resource that represents the data of a single raw artifact as digital content accessible in its native format. A Binary resource can contain any content, whether text, image, pdf, zip archive, etc.

BiologicallyDerivedProduct | BiologicallyDerivedProduct | A material substance originating from a biological entity intended to be transplanted or infused into another (possibly the same) biological entity.

BodyStructure | BodyStructure | Record details about an anatomical structure. This resource may be used when a coded concept does not provide the necessary detail needed for the use case.

Bundle | Bundle | A container for a collection of resources.

CapabilityStatement | CapabilityStatement | A Capability Statement documents a set of capabilities (behaviors) of a FHIR Server for a particular version of FHIR that may be used as a statement of actual server functionality or a statement of required or desired server implementation.

CarePlan | CarePlan | Describes the intention of how one or more practitioners intend to deliver care for a particular patient, group or community for a period of time, possibly limited to care for a specific condition or set of conditions.

CareTeam | CareTeam | The Care Team includes all the people and organizations who plan to participate in the coordination and delivery of care for a patient.

CatalogEntry | CatalogEntry | Catalog entries are wrappers that contextualize items included in a catalog.

ChargeItem | ChargeItem | The resource ChargeItem describes the provision of healthcare provider products for a certain patient, therefore referring not only to the product, but containing in addition details of the provision, like date, time, amounts and participating organizations and persons. Main Usage of the ChargeItem is to enable the billing process and internal cost allocation.

ChargeItemDefinition | ChargeItemDefinition | The ChargeItemDefinition resource provides the properties that apply to the (billing) codes necessary to calculate costs and prices. The properties may differ largely depending on type and realm, therefore this resource gives only a rough structure and requires profiling for each type of billing code system.

Claim | Claim | A provider issued list of professional services and products which have been provided, or are to be provided, to a patient which is sent to an insurer for reimbursement.

ClaimResponse | ClaimResponse | This resource provides the adjudication details from the processing of a Claim resource.

ClinicalImpression | ClinicalImpression | A record of a clinical assessment performed to determine what problem(s) may affect the patient and before planning the treatments or management strategies that are best to manage a patient's condition. Assessments are often 1:1 with a clinical consultation / encounter, but this varies greatly depending on the clinical workflow. This resource is called "ClinicalImpression" rather than "ClinicalAssessment" to avoid confusion with the recording of assessment tools such as Apgar score.

CodeSystem | CodeSystem | The CodeSystem resource is used to declare the existence of and describe a code system or code system supplement and its key properties, and optionally define a part or all of its content.

Communication | Communication | An occurrence of information being transmitted; e.g. an alert that was sent to a responsible provider, a public health agency that was notified about a reportable condition.

CommunicationRequest | CommunicationRequest | A request to convey information; e.g. the CDS system proposes that an alert be sent to a responsible provider, the CDS system proposes that the public health agency be notified about a reportable condition.

CompartmentDefinition | CompartmentDefinition | A compartment definition that defines how resources are accessed on a server.

Composition | Composition | A set of healthcare-related information that is assembled together into a single logical package that provides a single coherent statement of meaning, establishes its own context and that has clinical attestation with regard to who is making the statement. A Composition defines the structure and narrative content necessary for a document. However, a Composition alone does not constitute a document. Rather, the Composition must be the first entry in a Bundle where Bundle.type=document, and any other resources referenced from Composition must be included as subsequent entries in the Bundle (for example Patient, Practitioner, Encounter, etc.).

ConceptMap | ConceptMap | A statement of relationships from one set of concepts to one or more other concepts - either concepts in code systems, or data element/data element concepts, or classes in class models.

Condition | Condition | A clinical condition, problem, diagnosis, or other event, situation, issue, or clinical concept that has risen to a level of concern.

Consent | Consent | A record of a healthcare consumer’s choices, which permits or denies identified recipient(s) or recipient role(s) to perform one or more actions within a given policy context, for specific purposes and periods of time.

Contract | Contract | Legally enforceable, formally recorded unilateral or bilateral directive i.e., a policy or agreement.

Coverage | Coverage | Financial instrument which may be used to reimburse or pay for health care products and services. Includes both insurance and self-payment.

CoverageEligibilityRequest | CoverageEligibilityRequest | The CoverageEligibilityRequest provides patient and insurance coverage information to an insurer for them to respond, in the form of an CoverageEligibilityResponse, with information regarding whether the stated coverage is valid and in-force and optionally to provide the insurance details of the policy.

CoverageEligibilityResponse | CoverageEligibilityResponse | This resource provides eligibility and plan details from the processing of an CoverageEligibilityRequest resource.

DetectedIssue | DetectedIssue | Indicates an actual or potential clinical issue with or between one or more active or proposed clinical actions for a patient; e.g. Drug-drug interaction, Ineffective treatment frequency, Procedure-condition conflict, etc.

Device | Device | A type of a manufactured item that is used in the provision of healthcare without being substantially changed through that activity. The device may be a medical or non-medical device.

DeviceDefinition | DeviceDefinition | The characteristics, operational status and capabilities of a medical-related component of a medical device.

DeviceMetric | DeviceMetric | Describes a measurement, calculation or setting capability of a medical device.

DeviceRequest | DeviceRequest | Represents a request for a patient to employ a medical device. The device may be an implantable device, or an external assistive device, such as a walker.

DeviceUseStatement | DeviceUseStatement | A record of a device being used by a patient where the record is the result of a report from the patient or another clinician.

DiagnosticReport | DiagnosticReport | The findings and interpretation of diagnostic tests performed on patients, groups of patients, devices, and locations, and/or specimens derived from these. The report includes clinical context such as requesting and provider information, and some mix of atomic results, images, textual and coded interpretations, and formatted representation of diagnostic reports.

DocumentManifest | DocumentManifest | A collection of documents compiled for a purpose together with metadata that applies to the collection.

DocumentReference | DocumentReference | A reference to a document of any kind for any purpose. Provides metadata about the document so that the document can be discovered and managed. The scope of a document is any seralized object with a mime-type, so includes formal patient centric documents (CDA), cliical notes, scanned paper, and non-patient specific documents like policy text.

DomainResource | DomainResource | A resource that includes narrative, extensions, and contained resources.

EffectEvidenceSynthesis | EffectEvidenceSynthesis | The EffectEvidenceSynthesis resource describes the difference in an outcome between exposures states in a population where the effect estimate is derived from a combination of research studies.

Encounter | Encounter | An interaction between a patient and healthcare provider(s) for the purpose of providing healthcare service(s) or assessing the health status of a patient.

Endpoint | Endpoint | The technical details of an endpoint that can be used for electronic services, such as for web services providing XDS.b or a REST endpoint for another FHIR server. This may include any security context information.

EnrollmentRequest | EnrollmentRequest | This resource provides the insurance enrollment details to the insurer regarding a specified coverage.

EnrollmentResponse | EnrollmentResponse | This resource provides enrollment and plan details from the processing of an EnrollmentRequest resource.

EpisodeOfCare | EpisodeOfCare | An association between a patient and an organization / healthcare provider(s) during which time encounters may occur. The managing organization assumes a level of responsibility for the patient during this time.

EventDefinition | EventDefinition | The EventDefinition resource provides a reusable description of when a particular event can occur.

Evidence | Evidence | The Evidence resource describes the conditional state (population and any exposures being compared within the population) and outcome (if specified) that the knowledge (evidence, assertion, recommendation) is about.

EvidenceVariable | EvidenceVariable | The EvidenceVariable resource describes a "PICO" element that knowledge (evidence, assertion, recommendation) is about.

ExampleScenario | ExampleScenario | Example of workflow instance.

ExplanationOfBenefit | ExplanationOfBenefit | This resource provides: the claim details; adjudication details from the processing of a Claim; and optionally account balance information, for informing the subscriber of the benefits provided.

FamilyMemberHistory | FamilyMemberHistory | Significant health conditions for a person related to the patient relevant in the context of care for the patient.

Flag | Flag | Prospective warnings of potential issues when providing care to the patient.

Goal | Goal | Describes the intended objective(s) for a patient, group or organization care, for example, weight loss, restoring an activity of daily living, obtaining herd immunity via immunization, meeting a process improvement objective, etc.

GraphDefinition | GraphDefinition | A formal computable definition of a graph of resources - that is, a coherent set of resources that form a graph by following references. The Graph Definition resource defines a set and makes rules about the set.

Group | Group | Represents a defined collection of entities that may be discussed or acted upon collectively but which are not expected to act collectively, and are not formally or legally recognized; i.e. a collection of entities that isn't an Organization.

GuidanceResponse | GuidanceResponse | A guidance response is the formal response to a guidance request, including any output parameters returned by the evaluation, as well as the description of any proposed actions to be taken.

HealthcareService | HealthcareService | The details of a healthcare service available at a location.

ImagingStudy | ImagingStudy | Representation of the content produced in a DICOM imaging study. A study comprises a set of series, each of which includes a set of Service-Object Pair Instances (SOP Instances - images or other data) acquired or produced in a common context. A series is of only one modality (e.g. X-ray, CT, MR, ultrasound), but a study may have multiple series of different modalities.

Immunization | Immunization | Describes the event of a patient being administered a vaccine or a record of an immunization as reported by a patient, a clinician or another party.

ImmunizationEvaluation | ImmunizationEvaluation | Describes a comparison of an immunization event against published recommendations to determine if the administration is "valid" in relation to those recommendations.

ImmunizationRecommendation | ImmunizationRecommendation | A patient's point-in-time set of recommendations (i.e. forecasting) according to a published schedule with optional supporting justification.

ImplementationGuide | ImplementationGuide | A set of rules of how a particular interoperability or standards problem is solved - typically through the use of FHIR resources. This resource is used to gather all the parts of an implementation guide into a logical whole and to publish a computable definition of all the parts.

InsurancePlan | InsurancePlan | Details of a Health Insurance product/plan provided by an organization.

Invoice | Invoice | Invoice containing collected ChargeItems from an Account with calculated individual and total price for Billing purpose.

Library | Library | The Library resource is a general-purpose container for knowledge asset definitions. It can be used to describe and expose existing knowledge assets such as logic libraries and information model descriptions, as well as to describe a collection of knowledge assets.

Linkage | Linkage | Identifies two or more records (resource instances) that refer to the same real-world "occurrence".

List | List | A list is a curated collection of resources.

Location | Location | Details and position information for a physical place where services are provided and resources and participants may be stored, found, contained, or accommodated.

Measure | Measure | The Measure resource provides the definition of a quality measure.

MeasureReport | MeasureReport | The MeasureReport resource contains the results of the calculation of a measure; and optionally a reference to the resources involved in that calculation.

Media | Media | A photo, video, or audio recording acquired or used in healthcare. The actual content may be inline or provided by direct reference.

Medication | Medication | This resource is primarily used for the identification and definition of a medication for the purposes of prescribing, dispensing, and administering a medication as well as for making statements about medication use.

MedicationAdministration | MedicationAdministration | Describes the event of a patient consuming or otherwise being administered a medication. This may be as simple as swallowing a tablet or it may be a long running infusion. Related resources tie this event to the authorizing prescription, and the specific encounter between patient and health care practitioner.

MedicationDispense | MedicationDispense | Indicates that a medication product is to be or has been dispensed for a named person/patient. This includes a description of the medication product (supply) provided and the instructions for administering the medication. The medication dispense is the result of a pharmacy system responding to a medication order.

MedicationKnowledge | MedicationKnowledge | Information about a medication that is used to support knowledge.

MedicationRequest | MedicationRequest | An order or request for both supply of the medication and the instructions for administration of the medication to a patient. The resource is called "MedicationRequest" rather than "MedicationPrescription" or "MedicationOrder" to generalize the use across inpatient and outpatient settings, including care plans, etc., and to harmonize with workflow patterns.

MedicationStatement | MedicationStatement | A record of a medication that is being consumed by a patient. A MedicationStatement may indicate that the patient may be taking the medication now or has taken the medication in the past or will be taking the medication in the future. The source of this information can be the patient, significant other (such as a family member or spouse), or a clinician. A common scenario where this information is captured is during the history taking process during a patient visit or stay. The medication information may come from sources such as the patient's memory, from a prescription bottle, or from a list of medications the patient, clinician or other party maintains. The primary difference between a medication statement and a medication administration is that the medication administration has complete administration information and is based on actual administration information from the person who administered the medication. A medication statement is often, if not always, less specific. There is no required date/time when the medication was administered, in fact we only know that a source has reported the patient is taking this medication, where details such as time, quantity, or rate or even medication product may be incomplete or missing or less precise. As stated earlier, the medication statement information may come from the patient's memory, from a prescription bottle or from a list of medications the patient, clinician or other party maintains. Medication administration is more formal and is not missing detailed information.

MedicinalProduct | MedicinalProduct | Detailed definition of a medicinal product, typically for uses other than direct patient care (e.g. regulatory use).

MedicinalProductAuthorization | MedicinalProductAuthorization | The regulatory authorization of a medicinal product.

MedicinalProductContraindication | MedicinalProductContraindication | The clinical particulars - indications, contraindications etc. of a medicinal product, including for regulatory purposes.

MedicinalProductIndication | MedicinalProductIndication | Indication for the Medicinal Product.

MedicinalProductIngredient | MedicinalProductIngredient | An ingredient of a manufactured item or pharmaceutical product.

MedicinalProductInteraction | MedicinalProductInteraction | The interactions of the medicinal product with other medicinal products, or other forms of interactions.

MedicinalProductManufactured | MedicinalProductManufactured | The manufactured item as contained in the packaged medicinal product.

MedicinalProductPackaged | MedicinalProductPackaged | A medicinal product in a container or package.

MedicinalProductPharmaceutical | MedicinalProductPharmaceutical | A pharmaceutical product described in terms of its composition and dose form.

MedicinalProductUndesirableEffect | MedicinalProductUndesirableEffect | Describe the undesirable effects of the medicinal product.

MessageDefinition | MessageDefinition | Defines the characteristics of a message that can be shared between systems, including the type of event that initiates the message, the content to be transmitted and what response(s), if any, are permitted.

MessageHeader | MessageHeader | The header for a message exchange that is either requesting or responding to an action. The reference(s) that are the subject of the action as well as other information related to the action are typically transmitted in a bundle in which the MessageHeader resource instance is the first resource in the bundle.

MolecularSequence | MolecularSequence | Raw data describing a biological sequence.

NamingSystem | NamingSystem | A curated namespace that issues unique symbols within that namespace for the identification of concepts, people, devices, etc. Represents a "System" used within the Identifier and Coding data types.

NutritionOrder | NutritionOrder | A request to supply a diet, formula feeding (enteral) or oral nutritional supplement to a patient/resident.

Observation | Observation | Measurements and simple assertions made about a patient, device or other subject.

ObservationDefinition | ObservationDefinition | Set of definitional characteristics for a kind of observation or measurement produced or consumed by an orderable health care service.

OperationDefinition | OperationDefinition | A formal computable definition of an operation (on the RESTful interface) or a named query (using the search interaction).

OperationOutcome | OperationOutcome | A collection of error, warning, or information messages that result from a system action.

Organization | Organization | A formally or informally recognized grouping of people or organizations formed for the purpose of achieving some form of collective action. Includes companies, institutions, corporations, departments, community groups, healthcare practice groups, payer/insurer, etc.

OrganizationAffiliation | OrganizationAffiliation | Defines an affiliation/assotiation/relationship between 2 distinct oganizations, that is not a part-of relationship/sub-division relationship.

Parameters | Parameters | This resource is a non-persisted resource used to pass information into and back from an [operation](operations.html). It has no other use, and there is no RESTful endpoint associated with it.

Patient | Patient | Demographics and other administrative information about an individual or animal receiving care or other health-related services.

PaymentNotice | PaymentNotice | This resource provides the status of the payment for goods and services rendered, and the request and response resource references.

PaymentReconciliation | PaymentReconciliation | This resource provides the details including amount of a payment and allocates the payment items being paid.

Person | Person | Demographics and administrative information about a person independent of a specific health-related context.

PlanDefinition | PlanDefinition | This resource allows for the definition of various types of plans as a sharable, consumable, and executable artifact. The resource is general enough to support the description of a broad range of clinical artifacts such as clinical decision support rules, order sets and protocols.

Practitioner | Practitioner | A person who is directly or indirectly involved in the provisioning of healthcare.

PractitionerRole | PractitionerRole | A specific set of Roles/Locations/specialties/services that a practitioner may perform at an organization for a period of time.

Procedure | Procedure | An action that is or was performed on or for a patient. This can be a physical intervention like an operation, or less invasive like long term services, counseling, or hypnotherapy.

Provenance | Provenance | Provenance of a resource is a record that describes entities and processes involved in producing and delivering or otherwise influencing that resource. Provenance provides a critical foundation for assessing authenticity, enabling trust, and allowing reproducibility. Provenance assertions are a form of contextual metadata and can themselves become important records with their own provenance. Provenance statement indicates clinical significance in terms of confidence in authenticity, reliability, and trustworthiness, integrity, and stage in lifecycle (e.g. Document Completion - has the artifact been legally authenticated), all of which may impact security, privacy, and trust policies.

Questionnaire | Questionnaire | A structured set of questions intended to guide the collection of answers from end-users. Questionnaires provide detailed control over order, presentation, phraseology and grouping to allow coherent, consistent data collection.

QuestionnaireResponse | QuestionnaireResponse | A structured set of questions and their answers. The questions are ordered and grouped into coherent subsets, corresponding to the structure of the grouping of the questionnaire being responded to.

RelatedPerson | RelatedPerson | Information about a person that is involved in the care for a patient, but who is not the target of healthcare, nor has a formal responsibility in the care process.

RequestGroup | RequestGroup | A group of related requests that can be used to capture intended activities that have inter-dependencies such as "give this medication after that one".

ResearchDefinition | ResearchDefinition | The ResearchDefinition resource describes the conditional state (population and any exposures being compared within the population) and outcome (if specified) that the knowledge (evidence, assertion, recommendation) is about.

ResearchElementDefinition | ResearchElementDefinition | The ResearchElementDefinition resource describes a "PICO" element that knowledge (evidence, assertion, recommendation) is about.

ResearchStudy | ResearchStudy | A process where a researcher or organization plans and then executes a series of steps intended to increase the field of healthcare-related knowledge. This includes studies of safety, efficacy, comparative effectiveness and other information about medications, devices, therapies and other interventional and investigative techniques. A ResearchStudy involves the gathering of information about human or animal subjects.

ResearchSubject | ResearchSubject | A physical entity which is the primary unit of operational and/or administrative interest in a study.

Resource | Resource | This is the base resource type for everything.

RiskAssessment | RiskAssessment | An assessment of the likely outcome(s) for a patient or other subject as well as the likelihood of each outcome.

RiskEvidenceSynthesis | RiskEvidenceSynthesis | The RiskEvidenceSynthesis resource describes the likelihood of an outcome in a population plus exposure state where the risk estimate is derived from a combination of research studies.

Schedule | Schedule | A container for slots of time that may be available for booking appointments.

SearchParameter | SearchParameter | A search parameter that defines a named search item that can be used to search/filter on a resource.

ServiceRequest | ServiceRequest | A record of a request for service such as diagnostic investigations, treatments, or operations to be performed.

Slot | Slot | A slot of time on a schedule that may be available for booking appointments.

Specimen | Specimen | A sample to be used for analysis.

SpecimenDefinition | SpecimenDefinition | A kind of specimen with associated set of requirements.

StructureDefinition | StructureDefinition | A definition of a FHIR structure. This resource is used to describe the underlying resources, data types defined in FHIR, and also for describing extensions and constraints on resources and data types.

StructureMap | StructureMap | A Map of relationships between 2 structures that can be used to transform data.

Subscription | Subscription | The subscription resource is used to define a push-based subscription from a server to another system. Once a subscription is registered with the server, the server checks every resource that is created or updated, and if the resource matches the given criteria, it sends a message on the defined "channel" so that another system can take an appropriate action.

Substance | Substance | A homogeneous material with a definite composition.

SubstanceNucleicAcid | SubstanceNucleicAcid | Nucleic acids are defined by three distinct elements: the base, sugar and linkage. Individual substance/moiety IDs will be created for each of these elements. The nucleotide sequence will be always entered in the 5’-3’ direction.

SubstancePolymer | SubstancePolymer | Todo.

SubstanceProtein | SubstanceProtein | A SubstanceProtein is defined as a single unit of a linear amino acid sequence, or a combination of subunits that are either covalently linked or have a defined invariant stoichiometric relationship. This includes all synthetic, recombinant and purified SubstanceProteins of defined sequence, whether the use is therapeutic or prophylactic. This set of elements will be used to describe albumins, coagulation factors, cytokines, growth factors, peptide/SubstanceProtein hormones, enzymes, toxins, toxoids, recombinant vaccines, and immunomodulators.

SubstanceReferenceInformation | SubstanceReferenceInformation | Todo.

SubstanceSourceMaterial | SubstanceSourceMaterial | Source material shall capture information on the taxonomic and anatomical origins as well as the fraction of a material that can result in or can be modified to form a substance. This set of data elements shall be used to define polymer substances isolated from biological matrices. Taxonomic and anatomical origins shall be described using a controlled vocabulary as required. This information is captured for naturally derived polymers (. starch) and structurally diverse substances. For Organisms belonging to the Kingdom Plantae the Substance level defines the fresh material of a single species or infraspecies, the Herbal Drug and the Herbal preparation. For Herbal preparations, the fraction information will be

captured at the Substance information level and additional information for herbal extracts will be captured at the Specified Substance Group 1 information level. See for further explanation the Substance Class: Structurally Diverse and the herbal annex.

SubstanceSpecification | SubstanceSpecification | The detailed description of a substance, typically at a level beyond what is used for prescribing.

SupplyDelivery | SupplyDelivery | Record of delivery of what is supplied.

SupplyRequest | SupplyRequest | A record of a request for a medication, substance or device used in the healthcare setting.

Task | Task | A task to be performed.

TerminologyCapabilities | TerminologyCapabilities | A TerminologyCapabilities resource documents a set of capabilities (behaviors) of a FHIR Terminology Server that may be used as a statement of actual server functionality or a statement of required or desired server implementation.

TestReport | TestReport | A summary of information based on the results of executing a TestScript.

TestScript | TestScript | A structured set of tests against a FHIR server or client implementation to determine compliance against the FHIR specification.

ValueSet | ValueSet | A ValueSet resource instance specifies a set of codes drawn from one or more code systems, intended for use in a particular context. Value sets link between [[[CodeSystem]]] definitions and their use in [coded elements](terminologies.html).

VerificationResult | VerificationResult | Describes validation requirements, source(s), status and dates for one or more elements.

VisionPrescription | VisionPrescription | An authorization for the provision of glasses and/or contact lenses to a patient.

This code system http://hl7.org/fhir/resource-types defines the following codes:

Code | Display | Definition

Account | Account | A financial tool for tracking value accrued for a particular purpose. In the healthcare field, used to track charges for a patient, cost centers, etc.

ActivityDefinition | ActivityDefinition | This resource allows for the definition of some activity to be performed, independent of a particular patient, practitioner, or other performance context.

AdverseEvent | AdverseEvent | Actual or potential/avoided event causing unintended physical injury resulting from or contributed to by medical care, a research study or other healthcare setting factors that requires additional monitoring, treatment, or hospitalization, or that results in death.

AllergyIntolerance | AllergyIntolerance | Risk of harmful or undesirable, physiological response which is unique to an individual and associated with exposure to a substance.

Appointment | Appointment | A booking of a healthcare event among patient(s), practitioner(s), related person(s) and/or device(s) for a specific date/time. This may result in one or more Encounter(s).

AppointmentResponse | AppointmentResponse | A reply to an appointment request for a patient and/or practitioner(s), such as a confirmation or rejection.

AuditEvent | AuditEvent | A record of an event made for purposes of maintaining a security log. Typical uses include detection of intrusion attempts and monitoring for inappropriate usage.

Basic | Basic | Basic is used for handling concepts not yet defined in FHIR, narrative-only resources that don't map to an existing resource, and custom resources not appropriate for inclusion in the FHIR specification.

Binary | Binary | A resource that represents the data of a single raw artifact as digital content accessible in its native format. A Binary resource can contain any content, whether text, image, pdf, zip archive, etc.

BiologicallyDerivedProduct | BiologicallyDerivedProduct | A material substance originating from a biological entity intended to be transplanted or infused into another (possibly the same) biological entity.

BodyStructure | BodyStructure | Record details about an anatomical structure. This resource may be used when a coded concept does not provide the necessary detail needed for the use case.

Bundle | Bundle | A container for a collection of resources.

CapabilityStatement | CapabilityStatement | A Capability Statement documents a set of capabilities (behaviors) of a FHIR Server for a particular version of FHIR that may be used as a statement of actual server functionality or a statement of required or desired server implementation.

CarePlan | CarePlan | Describes the intention of how one or more practitioners intend to deliver care for a particular patient, group or community for a period of time, possibly limited to care for a specific condition or set of conditions.

CareTeam | CareTeam | The Care Team includes all the people and organizations who plan to participate in the coordination and delivery of care for a patient.

CatalogEntry | CatalogEntry | Catalog entries are wrappers that contextualize items included in a catalog.

ChargeItem | ChargeItem | The resource ChargeItem describes the provision of healthcare provider products for a certain patient, therefore referring not only to the product, but containing in addition details of the provision, like date, time, amounts and participating organizations and persons. Main Usage of the ChargeItem is to enable the billing process and internal cost allocation.

ChargeItemDefinition | ChargeItemDefinition | The ChargeItemDefinition resource provides the properties that apply to the (billing) codes necessary to calculate costs and prices. The properties may differ largely depending on type and realm, therefore this resource gives only a rough structure and requires profiling for each type of billing code system.

Claim | Claim | A provider issued list of professional services and products which have been provided, or are to be provided, to a patient which is sent to an insurer for reimbursement.

ClaimResponse | ClaimResponse | This resource provides the adjudication details from the processing of a Claim resource.

ClinicalImpression | ClinicalImpression | A record of a clinical assessment performed to determine what problem(s) may affect the patient and before planning the treatments or management strategies that are best to manage a patient's condition. Assessments are often 1:1 with a clinical consultation / encounter, but this varies greatly depending on the clinical workflow. This resource is called "ClinicalImpression" rather than "ClinicalAssessment" to avoid confusion with the recording of assessment tools such as Apgar score.

CodeSystem | CodeSystem | The CodeSystem resource is used to declare the existence of and describe a code system or code system supplement and its key properties, and optionally define a part or all of its content.

Communication | Communication | An occurrence of information being transmitted; e.g. an alert that was sent to a responsible provider, a public health agency that was notified about a reportable condition.

CommunicationRequest | CommunicationRequest | A request to convey information; e.g. the CDS system proposes that an alert be sent to a responsible provider, the CDS system proposes that the public health agency be notified about a reportable condition.

CompartmentDefinition | CompartmentDefinition | A compartment definition that defines how resources are accessed on a server.

Composition | Composition | A set of healthcare-related information that is assembled together into a single logical package that provides a single coherent statement of meaning, establishes its own context and that has clinical attestation with regard to who

is making the statement. A Composition defines the structure and narrative content necessary for a document. However, a Composition alone does not constitute a document. Rather, the Composition must be the first entry in a Bundle where Bundle.type=document, and any other resources referenced from Composition must be included as subsequent entries in the Bundle (for example Patient, Practitioner, Encounter, etc.).

ConceptMap | ConceptMap | A statement of relationships from one set of concepts to one or more other concepts - either concepts in code systems, or data element/data element concepts, or classes in class models.

Condition | Condition | A clinical condition, problem, diagnosis, or other event, situation, issue, or clinical concept that has risen to a level of concern.

Consent | Consent | A record of a healthcare consumer’s choices, which permits or denies identified recipient(s) or recipient role(s) to perform one or more actions within a given policy context, for specific purposes and periods of time.

Contract | Contract | Legally enforceable, formally recorded unilateral or bilateral directive i.e., a policy or agreement.

Coverage | Coverage | Financial instrument which may be used to reimburse or pay for health care products and services. Includes both insurance and self-payment.

CoverageEligibilityRequest | CoverageEligibilityRequest | The CoverageEligibilityRequest provides patient and insurance coverage information to an insurer for them to respond, in the form of an CoverageEligibilityResponse, with information regarding whether the stated coverage is valid and in-force and optionally to provide the insurance details of the policy.

CoverageEligibilityResponse | CoverageEligibilityResponse | This resource provides eligibility and plan details from the processing of an CoverageEligibilityRequest resource.

DetectedIssue | DetectedIssue | Indicates an actual or potential clinical issue with or between one or more active or proposed clinical actions for a patient; e.g. Drug-drug interaction, Ineffective treatment frequency, Procedure-condition conflict, etc.

Device | Device | A type of a manufactured item that is used in the provision of healthcare without being substantially changed through that activity. The device may be a medical or non-medical device.

DeviceDefinition | DeviceDefinition | The characteristics, operational status and capabilities of a medical-related component of a medical device.

DeviceMetric | DeviceMetric | Describes a measurement, calculation or setting capability of a medical device.

DeviceRequest | DeviceRequest | Represents a request for a patient to employ a medical device. The device may be an implantable device, or an external assistive device, such as a walker.

DeviceUseStatement | DeviceUseStatement | A record of a device being used by a patient where the record is the result of a report from the patient or another clinician.

DiagnosticReport | DiagnosticReport | The findings and interpretation of diagnostic tests performed on patients, groups of patients, devices, and locations, and/or specimens derived from these. The report includes clinical context such as requesting and provider information, and some mix of atomic results, images, textual and coded interpretations, and formatted representation of diagnostic reports.

DocumentManifest | DocumentManifest | A collection of documents compiled for a purpose together with metadata that applies to the collection.

DocumentReference | DocumentReference | A reference to a document of any kind for any purpose. Provides metadata about the document so that the document can be discovered and managed. The scope of a document is any seralized object with a mime-type, so includes formal patient centric documents (CDA), cliical notes, scanned paper, and non-patient specific documents like policy text.

DomainResource | DomainResource | A resource that includes narrative, extensions, and contained resources.

EffectEvidenceSynthesis | EffectEvidenceSynthesis | The EffectEvidenceSynthesis resource describes the difference in an outcome between exposures states in a population where the effect estimate is derived from a combination of research studies.

Encounter | Encounter | An interaction between a patient and healthcare provider(s) for the purpose of providing healthcare service(s) or assessing the health status of a patient.

Endpoint | Endpoint | The technical details of an endpoint that can be used for electronic services, such as for web services providing XDS.b or a REST endpoint for another FHIR server. This may include any security context information.

EnrollmentRequest | EnrollmentRequest | This resource provides the insurance enrollment details to the insurer regarding a specified coverage.

EnrollmentResponse | EnrollmentResponse | This resource provides enrollment and plan details from the processing of an EnrollmentRequest resource.

EpisodeOfCare | EpisodeOfCare | An association between a patient and an organization / healthcare provider(s) during which time encounters may occur. The managing organization assumes a level of responsibility for the patient during this time.

EventDefinition | EventDefinition | The EventDefinition resource provides a reusable description of when a particular event can occur.

Evidence | Evidence | The Evidence resource describes the conditional state (population and any exposures being compared within the population) and outcome (if specified) that the knowledge (evidence, assertion, recommendation) is about.

EvidenceVariable | EvidenceVariable | The EvidenceVariable resource describes a "PICO" element that knowledge (evidence, assertion, recommendation) is about.

ExampleScenario | ExampleScenario | Example of workflow instance.

ExplanationOfBenefit | ExplanationOfBenefit | This resource provides: the claim details; adjudication details from the processing of a Claim; and optionally account balance information, for informing the subscriber of the benefits provided.

FamilyMemberHistory | FamilyMemberHistory | Significant health conditions for a person related to the patient relevant in the context of care for the patient.

Flag | Flag | Prospective warnings of potential issues when providing care to the patient.

Goal | Goal | Describes the intended objective(s) for a patient, group or organization care, for example, weight loss, restoring an activity of daily living, obtaining herd immunity via immunization, meeting a process improvement objective, etc.

GraphDefinition | GraphDefinition | A formal computable definition of a graph of resources - that is, a coherent set of resources that form a graph by following references. The Graph Definition resource defines a set and makes rules about the set.

Group | Group | Represents a defined collection of entities that may be discussed or acted upon collectively but which are not expected to act collectively, and are not formally or legally recognized; i.e. a collection of entities that isn't an Organization.

GuidanceResponse | GuidanceResponse | A guidance response is the formal response to a guidance request, including any output parameters returned by the evaluation, as well as the description of any proposed actions to be taken.

HealthcareService | HealthcareService | The details of a healthcare service available at a location.

ImagingStudy | ImagingStudy | Representation of the content produced in a DICOM imaging study. A study comprises a set of series, each of which includes a set of Service-Object Pair Instances (SOP Instances - images or other data) acquired or produced in a common context. A series is of only one modality (e.g. X-ray, CT, MR, ultrasound), but a study may have multiple series of

different modalities.

Immunization | Immunization | Describes the event of a patient being administered a vaccine or a record of an immunization as reported by a patient, a clinician or another party.

ImmunizationEvaluation | ImmunizationEvaluation | Describes a comparison of an immunization event against published recommendations to determine if the administration is "valid" in relation to those recommendations.

ImmunizationRecommendation | ImmunizationRecommendation | A patient's point-in-time set of recommendations (i.e. forecasting) according to a published schedule with optional supporting justification.

ImplementationGuide | ImplementationGuide | A set of rules of how a particular interoperability or standards problem is solved - typically through the use of FHIR resources. This resource is used to gather all the parts of an implementation guide into a logical whole and to publish a computable definition of all the parts.

InsurancePlan | InsurancePlan | Details of a Health Insurance product/plan provided by an organization.

Invoice | Invoice | Invoice containing collected ChargeItems from an Account with calculated individual and total price for Billing purpose.

Library | Library | The Library resource is a general-purpose container for knowledge asset definitions. It can be used to describe and expose existing knowledge assets such as logic libraries and information model descriptions, as well as to describe a collection of knowledge assets.

Linkage | Linkage | Identifies two or more records (resource instances) that refer to the same real-world "occurrence".

List | List | A list is a curated collection of resources.

Location | Location | Details and position information for a physical place where services are provided and resources and participants may be stored, found, contained, or accommodated.

Measure | Measure | The Measure resource provides the definition of a quality measure.

MeasureReport | MeasureReport | The MeasureReport resource contains the results of the calculation of a measure; and optionally a reference to the resources involved in that calculation.

Media | Media | A photo, video, or audio recording acquired or used in healthcare. The actual content may be inline or provided by direct reference.

Medication | Medication | This resource is primarily used for the identification and definition of a medication for the purposes of prescribing, dispensing, and administering a medication as well as for making statements about medication use.

MedicationAdministration | MedicationAdministration | Describes the event of a patient consuming or otherwise being administered a medication. This may be as simple as swallowing a tablet or it may be a long running infusion. Related resources tie this event to the authorizing prescription, and the specific encounter between patient and health care practitioner.

MedicationDispense | MedicationDispense | Indicates that a medication product is to be or has been dispensed for a named person/patient. This includes a description of the medication product (supply) provided and the instructions for administering the medication. The medication dispense is the result of a pharmacy system responding to a medication order.

MedicationKnowledge | MedicationKnowledge | Information about a medication that is used to support knowledge.

MedicationRequest | MedicationRequest | An order or request for both supply of the medication and the instructions for administration of the medication to a patient. The resource is called "MedicationRequest" rather than "MedicationPrescription" or "MedicationOrder" to generalize the use across inpatient and outpatient settings, including care plans, etc., and to harmonize with workflow patterns.

MedicationStatement | MedicationStatement | A record of a medication that is being consumed by a patient. A MedicationStatement may indicate that the patient may be taking the medication now or has taken the medication in the past or will be taking the medication in the future. The source of this information can be the patient, significant other (such as a family member or spouse), or a clinician. A common scenario where this information is captured is during the history taking process during a patient visit or stay. The medication information may come from sources such as the patient's memory, from a prescription bottle, or from a list of medications the patient, clinician or other party maintains. The primary difference between a medication statement and a medication administration is that the medication administration has complete administration information and is based on actual administration information from the person who administered the medication. A medication statement is often, if not always, less specific. There is no required date/time when the medication was administered, in fact we only know that a source has reported the patient is taking this medication, where details such as time, quantity, or rate or even medication product may be incomplete or missing or less precise. As stated earlier, the medication statement information may come from the patient's memory, from a prescription bottle or from a list of medications the patient, clinician or other party maintains. Medication administration is more formal and is not missing detailed information.

MedicinalProduct | MedicinalProduct | Detailed definition of a medicinal product, typically for uses other than direct patient care (e.g. regulatory use).

MedicinalProductAuthorization | MedicinalProductAuthorization | The regulatory authorization of a medicinal product.

MedicinalProductContraindication | MedicinalProductContraindication | The clinical particulars - indications, contraindications etc. of a medicinal product, including for regulatory purposes.

MedicinalProductIndication | MedicinalProductIndication | Indication for the Medicinal Product.

MedicinalProductIngredient | MedicinalProductIngredient | An ingredient of a manufactured item or pharmaceutical product.

MedicinalProductInteraction | MedicinalProductInteraction | The interactions of the medicinal product with other medicinal products, or other forms of interactions.

MedicinalProductManufactured | MedicinalProductManufactured | The manufactured item as contained in the packaged medicinal product.

MedicinalProductPackaged | MedicinalProductPackaged | A medicinal product in a container or package.

MedicinalProductPharmaceutical | MedicinalProductPharmaceutical | A pharmaceutical product described in terms of its composition and dose form.

MedicinalProductUndesirableEffect | MedicinalProductUndesirableEffect | Describe the undesirable effects of the medicinal product.

MessageDefinition | MessageDefinition | Defines the characteristics of a message that can be shared between systems, including the type of event that initiates the message, the content to be transmitted and what response(s), if any, are permitted.

MessageHeader | MessageHeader | The header for a message exchange that is either requesting or responding to an action. The reference(s) that are the subject of the action as well as other information related to the action are typically transmitted in a bundle in which the MessageHeader resource instance is the first resource in the bundle.

MolecularSequence | MolecularSequence | Raw data describing a biological sequence.

NamingSystem | NamingSystem | A curated namespace that issues unique symbols within that namespace for the identification of concepts, people, devices, etc. Represents a "System" used within the Identifier and Coding data types.

NutritionOrder | NutritionOrder | A request to supply a diet, formula feeding (enteral) or oral nutritional supplement to a patient/resident.

Observation | Observation | Measurements and simple assertions made about a patient, device or other subject.

ObservationDefinition | ObservationDefinition | Set of definitional characteristics for a kind of observation or measurement produced or consumed by an orderable health care service.

OperationDefinition | OperationDefinition | A formal computable definition of an operation (on the RESTful interface) or a named query (using the search interaction).

OperationOutcome | OperationOutcome | A collection of error, warning, or information messages that result from a system action.

Organization | Organization | A formally or informally recognized grouping of people or organizations formed for the purpose of achieving some form of collective action. Includes companies, institutions, corporations, departments, community groups, healthcare practice groups, payer/insurer, etc.

OrganizationAffiliation | OrganizationAffiliation | Defines an affiliation/assotiation/relationship between 2 distinct oganizations, that is not a part-of relationship/sub-division relationship.

Parameters | Parameters | This resource is a non-persisted resource used to pass information into and back from an [operation](operations.html). It has no other use, and there is no RESTful endpoint associated with it.

Patient | Patient | Demographics and other administrative information about an individual or animal receiving care or other health-related services.

PaymentNotice | PaymentNotice | This resource provides the status of the payment for goods and services rendered, and the request and response resource references.

PaymentReconciliation | PaymentReconciliation | This resource provides the details including amount of a payment and allocates the payment items being paid.

Person | Person | Demographics and administrative information about a person independent of a specific health-related context.

PlanDefinition | PlanDefinition | This resource allows for the definition of various types of plans as a sharable, consumable, and executable artifact. The resource is general enough to support the description of a broad range of clinical artifacts such as clinical decision support rules, order sets and protocols.

Practitioner | Practitioner | A person who is directly or indirectly involved in the provisioning of healthcare.

PractitionerRole | PractitionerRole | A specific set of Roles/Locations/specialties/services that a practitioner may perform at an organization for a period of time.

Procedure | Procedure | An action that is or was performed on or for a patient. This can be a physical intervention like an operation, or less invasive like long term services, counseling, or hypnotherapy.

Provenance | Provenance | Provenance of a resource is a record that describes entities and processes involved in producing and delivering or otherwise influencing that resource. Provenance provides a critical foundation for assessing authenticity, enabling trust, and allowing reproducibility. Provenance assertions are a form of contextual metadata and can themselves become important records with their own provenance. Provenance statement indicates clinical significance in terms of confidence in authenticity, reliability, and trustworthiness, integrity, and stage in lifecycle (e.g. Document Completion - has the artifact been legally authenticated), all of which may impact security, privacy, and trust policies.

Questionnaire | Questionnaire | A structured set of questions intended to guide the collection of answers from end-users. Questionnaires provide detailed control over order, presentation, phraseology and grouping to allow coherent, consistent data collection.

QuestionnaireResponse | QuestionnaireResponse | A structured set of questions and their answers. The questions are ordered and grouped into coherent subsets, corresponding to the structure of the grouping of the questionnaire being responded to.

RelatedPerson | RelatedPerson | Information about a person that is involved in the care for a patient, but who is not the target of healthcare, nor has a formal responsibility in the care process.

RequestGroup | RequestGroup | A group of related requests that can be used to capture intended activities that have inter-dependencies such as "give this medication after that one".

ResearchDefinition | ResearchDefinition | The ResearchDefinition resource describes the conditional state (population and any exposures being compared within the population) and outcome (if specified) that the knowledge (evidence, assertion, recommendation) is about.

ResearchElementDefinition | ResearchElementDefinition | The ResearchElementDefinition resource describes a "PICO" element that knowledge (evidence, assertion, recommendation) is about.

ResearchStudy | ResearchStudy | A process where a researcher or organization plans and then executes a series of steps intended to increase the field of healthcare-related knowledge. This includes studies of safety, efficacy, comparative effectiveness and other information about medications, devices, therapies and other interventional and investigative techniques. A ResearchStudy involves the gathering of information about human or animal subjects.

ResearchSubject | ResearchSubject | A physical entity which is the primary unit of operational and/or administrative interest in a study.

Resource | Resource | This is the base resource type for everything.

RiskAssessment | RiskAssessment | An assessment of the likely outcome(s) for a patient or other subject as well as the likelihood of each outcome.

RiskEvidenceSynthesis | RiskEvidenceSynthesis | The RiskEvidenceSynthesis resource describes the likelihood of an outcome in a population plus exposure state where the risk estimate is derived from a combination of research studies.

Schedule | Schedule | A container for slots of time that may be available for booking appointments.

SearchParameter | SearchParameter | A search parameter that defines a named search item that can be used to search/filter on a resource.

ServiceRequest | ServiceRequest | A record of a request for service such as diagnostic investigations, treatments, or operations to be performed.

Slot | Slot | A slot of time on a schedule that may be available for booking appointments.

Specimen | Specimen | A sample to be used for analysis.

SpecimenDefinition | SpecimenDefinition | A kind of specimen with associated set of requirements.

StructureDefinition | StructureDefinition | A definition of a FHIR structure. This resource is used to describe the underlying resources, data types defined in FHIR, and also for describing extensions and constraints on resources and data types.

StructureMap | StructureMap | A Map of relationships between 2 structures that can be used to transform data.

Subscription | Subscription | The subscription resource is used to define a push-based subscription from a server to another system. Once a subscription is registered with the server, the server checks every resource that is created or updated, and if the resource matches the given criteria, it sends a message on the defined "channel" so that another system can take an appropriate action.

Substance | Substance | A homogeneous material with a definite composition.
SubstanceNucleicAcid | SubstanceNucleicAcid | Nucleic acids are defined by three distinct elements: the base, sugar and linkage. Individual substance/moiety IDs will be created for each of these elements. The nucleotide sequence will be always entered in the 5’-3’ direction.
SubstancePolymer | SubstancePolymer | Todo.
SubstanceProtein | SubstanceProtein | A SubstanceProtein is defined as a single unit of a linear amino acid sequence, or a combination of subunits that are either covalently linked or have a defined invariant stoichiometric relationship. This includes all synthetic, recombinant and purified SubstanceProteins of defined sequence, whether the use is therapeutic or prophylactic. This set of elements will be used to describe albumins, coagulation factors, cytokines, growth factors, peptide/SubstanceProtein hormones, enzymes, toxins, toxoids, recombinant vaccines, and immunomodulators.
SubstanceReferenceInformation | SubstanceReferenceInformation | Todo.
SubstanceSourceMaterial | SubstanceSourceMaterial | Source material shall capture information on the taxonomic and anatomical origins as well as the fraction of a material that can result in or can be modified to form a substance. This set of data elements shall be used to define polymer substances isolated from biological matrices. Taxonomic and anatomical origins shall be described using a controlled vocabulary as required. This information is captured for naturally derived polymers (. starch) and structurally diverse substances. For Organisms belonging to the Kingdom Plantae the Substance level defines the fresh material of a single species or infraspecies, the Herbal Drug and the Herbal preparation. For Herbal preparations, the fraction information will be captured at the Substance information level and additional information for herbal extracts will be captured at the Specified Substance Group 1 information level. See for further explanation the Substance Class: Structurally Diverse and the herbal annex.
SubstanceSpecification | SubstanceSpecification | The detailed description of a substance, typically at a level beyond what is used for prescribing.
SupplyDelivery | SupplyDelivery | Record of delivery of what is supplied.
SupplyRequest | SupplyRequest | A record of a request for a medication, substance or device used in the healthcare setting.
Task | Task | A task to be performed.
TerminologyCapabilities | TerminologyCapabilities | A TerminologyCapabilities resource documents a set of capabilities (behaviors) of a FHIR Terminology Server that may be used as a statement of actual server functionality or a statement of required or desired server implementation.
TestReport | TestReport | A summary of information based on the results of executing a TestScript.
TestScript | TestScript | A structured set of tests against a FHIR server or client implementation to determine compliance against the FHIR specification.
ValueSet | ValueSet | A ValueSet resource instance specifies a set of codes drawn from one or more code systems, intended for use in a particular context. Value sets link between [[[CodeSystem]]] definitions and their use in [coded elements](terminologies.html).
VerificationResult | VerificationResult | Describes validation requirements, source(s), status and dates for one or more elements.
VisionPrescription | VisionPrescription | An authorization for the provision of glasses and/or contact lenses to a patient.

This code system http://hl7.org/fhir/resource-types defines the following codes:

Code | Display | Definition
Account | Cuenta
ActivityDefinition | DefinicionDeActividad
AdverseEvent | EventoAdverso
AllergyIntolerance | AllergiaIntolerancia
Appointment | Cita
AppointmentResponse | CitaRespuesta
AuditEvent | EventoSeguridad
Basic | Basico
Binary | Binario
BiologicallyDerivedProduct
BodyStructure | EstructuraDelCuerpo
Bundle | Paquete
CapabilityStatement | DeclaracionDeCapacidad
CarePlan | PlanDeCuidado
CareTeam | EquipoDeCuidado
CatalogEntry | EntradaDeCatalogo
ChargeItem | CargoDeItem
ChargeItemDefinition
Claim | Reclamación / Factura
ClaimResponse
ClinicalImpression | HallazgoClinico
CodeSystem | SistemaDeCodigos
Communication | Comunicación
CommunicationRequest | ComunicaciónRequerimiento
CompartmentDefinition | DefinicionDeCompartimento
Composition | Composición
ConceptMap | MapaDeConceptos
Condition | Condición
Consent | Consentimiento
Contract | Contato
Coverage | Cobertura
CoverageEligibilityRequest
CoverageEligibilityResponse
DetectedIssue | Problema-Detectado /ProblemaDetectado
Device | Dispositivo
DeviceDefinition | DefiniciónDeDispositivo

DeviceMetric | MetricaDeDispositivo
DeviceRequest | SolicitudDeDispositivo
DeviceUseStatement
DiagnosticReport | InformeDiagnostico
DocumentManifest | ManifestoDocumento
DocumentReference | ReferenciaDocumento
DomainResource | RecursoDeDominio
EffectEvidenceSynthesis
Encounter | Encuentro
Endpoint | Endpoint
EnrollmentRequest | SolicitudDeEnrolamiento
EnrollmentResponse | RespuestaDeEnrolamiento
EpisodeOfCare | EpisodioDeCuidado
EventDefinition | DefinitionDeEvento
Evidence
EvidenceVariable
ExampleScenario | EjemploDeEscenario
ExplanationOfBenefit
FamilyMemberHistory | HistorialMiembroFamiliar
Flag | Bandera
Goal | Objetivo
GraphDefinition | DefinitionGrafico
Group | Grupo
GuidanceResponse | RespuestaDeOrientacion
HealthcareService | ServicioDeCuidado
ImagingStudy | EstudioImagen / EstudioImagen
Immunization | Inmunización
ImmunizationEvaluation
ImmunizationRecommendation | RecomendaciónInmunización /
ImplementationGuide | GuiaDeImplementacion
InsurancePlan
Invoice
Library | Librería
Linkage | Enlace / Conexión / Vinculo / Acoplamiento
List | Lista
Location | Locacion
Measure | Medida
MeasureReport | ReporteMedida
Media | Medio
Medication | Medicación /Medicamento
MedicationAdministration | AdministraciónMedicación / AdministracionMedicamento
MedicationDispense | DispensaciónMedicación /DispensacionMedicamento
MedicationKnowledge
MedicationRequest | PrescripciónMedicaciónTODO /PrescripcionMedicamento
MedicationStatement | ResumenMedicación /ResumenMedicamento
MedicinalProduct
MedicinalProductAuthorization
MedicinalProductContraindication
MedicinalProductIndication
MedicinalProductIngredient
MedicinalProductInteraction
MedicinalProductManufactured
MedicinalProductPackaged
MedicinalProductPharmaceutical
MedicinalProductUndesirableEffect
MessageDefinition | DefinicionMensaje
MessageHeader | CabeceraMensaje
MolecularSequence | SecuenciaMolecular
NamingSystem | SistemaDeNombres
NutritionOrder | OrdenNutrición
Observation | Observación
ObservationDefinition | DefinicionDeEspecimen
OperationDefinition | DefinicionDeOperacion
OperationOutcome | ResultadoOperación
Organization | Organización
OrganizationAffiliation
Parameters | Parametros
Patient | Paciente
PaymentNotice | AvisoDePago
PaymentReconciliation | ConciliacionDePago
Person | Persona
PlanDefinition | DefinicionDePlan

Practitioner | Practicante / Profesional
PractitionerRole | RolProfesional
Procedure | Procedimiento
Provenance | Procedencia
Questionnaire | Cuestionario
QuestionnaireResponse | RespuestaAlCuestionario
RelatedPerson | PersonaRelacionada
RequestGroup | GrupoDeSolicitudes
ResearchDefinition
ResearchElementDefinition
ResearchStudy | EstudioDeInvestigacion
ResearchSubject | SujetoDeInvestigacion
Resource | Recurso
RiskAssessment | EvaluacionDeRiesgo
RiskEvidenceSynthesis
Schedule | Agenda
SearchParameter | ParametroDeBusqueda
ServiceRequest | PeticiónServicio
Slot | Hueco / Zocalo / Espacio
Specimen | Especimen
SpecimenDefinition | DefinicionDeEspecimen
StructureDefinition | DefinicionDeEstructura
StructureMap | MapaDeEstructura
Subscription | Suscripción
Substance | Sustancia
SubstanceNucleicAcid
SubstancePolymer
SubstanceProtein
SubstanceReferenceInformation
SubstanceSourceMaterial
SubstanceSpecification
SupplyDelivery | Entrega de Suministro
SupplyRequest | Solicitud de Suministro
Task | Tarea
TerminologyCapabilities | CapacidadTerminologica
TestReport | ReporteDePrueba
TestScript | ScriptDePrueba
ValueSet | ConjuntoValores / ConjuntoDeValores
VerificationResult
VisionPrescription | PrescripcionDeVision

This code system http://hl7.org/fhir/resource-types defines the following codes:

Code | Display | Definition
Account
ActivityDefinition
AdverseEvent
AllergyIntolerance | IntoléranceAllergique
Appointment | RendezVous
AppointmentResponse | RéponseRendezVous
AuditEvent | ÉvènementSécurité
Basic | Basique
Binary | Binaire
BiologicallyDerivedProduct
BodyStructure | MorphologieDeCorps
Bundle | Paquet
CapabilityStatement
CarePlan | PlanDeSoins
CareTeam
CatalogEntry
ChargeItem
ChargeItemDefinition
Claim | Réclamation
ClaimResponse | RéponseARéclamation
ClinicalImpression | ImpressionClinique
CodeSystem
Communication | Communication
CommunicationRequest | DemandeDeCommunication
CompartmentDefinition
Composition | Composition
ConceptMap | CarteDeConcepts
Condition | Condition
Consent

Contract | Contrat
Coverage | Couverture
CoverageEligibilityRequest | CouvertureDemandeEligibilité
CoverageEligibilityResponse | RéponseEligibilitéCouverture
DetectedIssue | Problème Détecté
Device | Dispositif
DeviceDefinition | DéfinitionDeDispositif
DeviceMetric | MétriqueDispositif
DeviceRequest | DemandeUtilisationDispositif
DeviceUseStatement
DiagnosticReport | RapportDiagnostique
DocumentManifest | Manifeste
DocumentReference | RéférenceDocument
DomainResource
EffectEvidenceSynthesis
Encounter | Venue
Endpoint
EnrollmentRequest | DemandeInscription
EnrollmentResponse | RéponseInscription
EpisodeOfCare | ÉpisodeDeSoins
EventDefinition
Evidence
EvidenceVariable
ExampleScenario
ExplanationOfBenefit | ExplicationDuBénéfice
FamilyMemberHistory | HistoireMembreFamille
Flag | Drapeau
Goal | But
GraphDefinition
Group | Groupe
GuidanceResponse
HealthcareService | ServiceDeSanté
ImagingStudy | EtudeImagerie
Immunization | Immunisation
ImmunizationEvaluation
ImmunizationRecommendation | RecommendationImmunisation
ImplementationGuide
InsurancePlan
Invoice
Library
Linkage
List | Liste
Location | Localisation
Measure
MeasureReport
Media | Média
Medication | Médication
MedicationAdministration | AdministrationMédicaments
MedicationDispense | DispensationMédicaments
MedicationKnowledge
MedicationRequest | PrescriptionMédicamenteuseTODO
MedicationStatement | ÉtatMédication
MedicinalProduct
MedicinalProductAuthorization
MedicinalProductContraindication
MedicinalProductIndication
MedicinalProductIngredient
MedicinalProductInteraction
MedicinalProductManufactured
MedicinalProductPackaged
MedicinalProductPharmaceutical
MedicinalProductUndesirableEffect
MessageDefinition
MessageHeader | EntêteMessage
MolecularSequence
NamingSystem | SystèmeDeNommage
NutritionOrder | OrdreNutrition
Observation | Observation
ObservationDefinition
OperationDefinition | DéfinitionOpération
OperationOutcome | RésultatOpération
Organization | Organisation

OrganizationAffiliation
Parameters
Patient | Patient
PaymentNotice | AvisPaiement
PaymentReconciliation | RéconciliationPaiement
Person | Personne
PlanDefinition
Practitioner | Praticien
PractitionerRole
Procedure | Procédure
Provenance | Provenance
Questionnaire | Questionnaire
QuestionnaireResponse | RéponseQuestionnaire
RelatedPerson | PersonneEnRelation
RequestGroup
ResearchDefinition
ResearchElementDefinition
ResearchStudy
ResearchSubject
Resource
RiskAssessment | ÉvaluationRisques
RiskEvidenceSynthesis
Schedule
SearchParameter | ParamètreRecherche
ServiceRequest | DemandeService
Slot | Slot
Specimen | Spécimen
SpecimenDefinition
StructureDefinition | DéfinitionStructure
StructureMap
Subscription | Souscription
Substance | Substance
SubstanceNucleicAcid
SubstancePolymer
SubstanceProtein
SubstanceReferenceInformation
SubstanceSourceMaterial
SubstanceSpecification
SupplyDelivery | Supply Livraison
SupplyRequest | Demande d'approvisionnement
Task
TerminologyCapabilities
TestReport | RapportTest
TestScript | ScriptTest
ValueSet | EnsembleValeurs
VerificationResult
VisionPrescription | PrescriptionVision

This code system http://hl7.org/fhir/resource-types defines the following codes:

Code | Display | Definition
Account
ActivityDefinition | DefinizioneAttivita
AdverseEvent | EventoAvverso
AllergyIntolerance | AllergiaIntolleranza
Appointment | Appuntamento
AppointmentResponse | RispostaAppuntamento
AuditEvent
Basic
Binary | Binario
BiologicallyDerivedProduct
BodyStructure | StrutturaDelCorpo
Bundle
CapabilityStatement
CarePlan | PianoDiCura
CareTeam
CatalogEntry
ChargeItem
ChargeItemDefinition
Claim
ClaimResponse
ClinicalImpression | ImpressioneClinica
CodeSystem | SistemaDiCodifica

Communication | Comunicazione
CommunicationRequest | RichiestaDiComunicazione
CompartmentDefinition
Composition | Composizione
ConceptMap | MappaDiConcetti
Condition | Condizione
Consent | Consenso
Contract | Contratto
Coverage | Copertura
CoverageEligibilityRequest | RichiestaEleggibilitaCopertura
CoverageEligibilityResponse | RispostaEleggibilitaCopertura
DetectedIssue | ProblemaRilevato
Device | Dispositivo
DeviceDefinition
DeviceMetric
DeviceRequest | RichiestaDispositivo
DeviceUseStatement
DiagnosticReport | RefertoDiagnostico
DocumentManifest
DocumentReference | RiferimentoDocumento
DomainResource
EffectEvidenceSynthesis
Encounter
Endpoint
EnrollmentRequest | RichiestaIscrizione
EnrollmentResponse | RispostaIscrizione
EpisodeOfCare | EpisodioDiCura
EventDefinition | DefinizioneEvento
Evidence
EvidenceVariable
ExampleScenario | ScenarioDiEsempio
ExplanationOfBenefit
FamilyMemberHistory
Flag
Goal
GraphDefinition
Group | Gruppo
GuidanceResponse
HealthcareService | ServizioSanitario
ImagingStudy
Immunization | Immunizzazione
ImmunizationEvaluation
ImmunizationRecommendation
ImplementationGuide
InsurancePlan
Invoice
Library
Linkage
List | Lista
Location
Measure | Misura
MeasureReport
Media | Media
Medication
MedicationAdministration
MedicationDispense
MedicationKnowledge
MedicationRequest
MedicationStatement
MedicinalProduct | ProdottoMedicinale
MedicinalProductAuthorization | AutorizzazioneProdottoMedicinale
MedicinalProductContraindication
MedicinalProductIndication
MedicinalProductIngredient | IngredienteProdottoMedicinale
MedicinalProductInteraction
MedicinalProductManufactured
MedicinalProductPackaged
MedicinalProductPharmaceutical
MedicinalProductUndesirableEffect
MessageDefinition | DefinizioneMessaggio
MessageHeader
MolecularSequence

NamingSystem
NutritionOrder
Observation | Osservazione
ObservationDefinition | DefinizioneOsservazione
OperationDefinition | DefinizioneOperazione
OperationOutcome | RisultatoOperazione
Organization | Organizzazione
OrganizationAffiliation
Parameters
Patient | Paziente
PaymentNotice | AvvisoDiPagamento
PaymentReconciliation | RiconciliazionePagamento
Person | Persona
PlanDefinition
Practitioner
PractitionerRole
Procedure | Procedura
Provenance | Provenienza
Questionnaire | Questionario
QuestionnaireResponse | RispostaQuestionario
RelatedPerson | PersonaCorrelata
RequestGroup | GruppoDiRichieste
ResearchDefinition
ResearchElementDefinition
ResearchStudy
ResearchSubject
Resource
RiskAssessment
RiskEvidenceSynthesis
Schedule
SearchParameter | ParametroDiRicerca
ServiceRequest | RichiestaDiServizio
Slot
Specimen | Campione
SpecimenDefinition | DefinizioneCampione
StructureDefinition | DefinizioneStruttura
StructureMap
Subscription | Sottoscrizione
Substance | Sostanza
SubstanceNucleicAcid
SubstancePolymer
SubstanceProtein
SubstanceReferenceInformation
SubstanceSourceMaterial
SubstanceSpecification
SupplyDelivery
SupplyRequest
Task
TerminologyCapabilities
TestReport
TestScript
ValueSet
VerificationResult
VisionPrescription

This code system http://hl7.org/fhir/resource-types defines the following codes:

Code | Display | Definition
Account | □□
ActivityDefinition | □□□□
AdverseEvent | □□□□
AllergyIntolerance | □□□□□□□□
Appointment | □□
AppointmentResponse | □□□□
AuditEvent | □□□□
Basic | □□□□
Binary | □□□□□
BiologicallyDerivedProduct
BodyStructure | □□□□
Bundle | □□
CapabilityStatement | □□□□
CarePlan | □□□□
CareTeam | □□□□

CatalogEntry | □□□□
ChargeItem | □□□□
ChargeItemDefinition
Claim | □□
ClaimResponse | □□□□
ClinicalImpression | □□□□
CodeSystem | □□□□
Communication | □□
CommunicationRequest | □□□□
CompartmentDefinition | □□□□□□
Composition | □□□□□
ConceptMap | □□□□
Condition | □□
Consent | □□□
Contract | □□
Coverage | □□□□
CoverageEligibilityRequest | □□□□
CoverageEligibilityResponse | □□□□
DetectedIssue | □□□□□
Device | □□
DeviceDefinition | □□□□
DeviceMetric | □□□□
DeviceRequest | □□□□
DeviceUseStatement | □□□□□□
DiagnosticReport | □□□□
DocumentManifest | □□□□
DocumentReference | □□□□
DomainResource | □□□□
EffectEvidenceSynthesis
Encounter | □□□□
Endpoint | □□
EnrollmentRequest | □□□□□□
EnrollmentResponse | □□□□□□
EpisodeOfCare | □□□□□□
EventDefinition | □□□□
Evidence
EvidenceVariable
ExampleScenario | □□□□
ExplanationOfBenefit | □□□□
FamilyMemberHistory | □□□
Flag | □□
Goal | □□
GraphDefinition | □□□□
Group | □□
GuidanceResponse | □□□□□□
HealthcareService | □□□□□□□□□
ImagingStudy | □□□□
Immunization | □□□□
ImmunizationEvaluation
ImmunizationRecommendation | □□□□□□
ImplementationGuide | □□□□
InsurancePlan
Invoice
Library | □
Linkage | □□□□
List | □□
Location | □□
Measure | □□
MeasureReport | □□□□
Media | □□
Medication | □□
MedicationAdministration | □□□□
MedicationDispense | □□□□
MedicationKnowledge
MedicationRequest | □□□□
MedicationStatement | □□□□
MedicinalProduct
MedicinalProductAuthorization
MedicinalProductContraindication
MedicinalProductIndication
MedicinalProductIngredient
MedicinalProductInteraction

MedicinalProductManufactured
MedicinalProductPackaged
MedicinalProductPharmaceutical
MedicinalProductUndesirableEffect
MessageDefinition | □□□□
MessageHeader | □□□□
MolecularSequence | □□□□
NamingSystem | □□□□
NutritionOrder | □□□□
Observation | □□
ObservationDefinition | □□□□
OperationDefinition | □□□□
OperationOutcome | □□□□
Organization | □□□□
OrganizationAffiliation
Parameters | □□
Patient | □□
PaymentNotice | □□□□
PaymentReconciliation | □□□□
Person | □□
PlanDefinition | □□□□
Practitioner | □□□□
PractitionerRole | □□□□□□
Procedure | □□□□
Provenance | □□
Questionnaire | □□□□
QuestionnaireResponse | □□□□□□
RelatedPerson | □□□□
RequestGroup | □□□□
ResearchDefinition
ResearchElementDefinition
ResearchStudy | □□□□
ResearchSubject | □□□□
Resource | □□
RiskAssessment | □□□□
RiskEvidenceSynthesis
Schedule | □□□□
SearchParameter | □□□□
ServiceRequest | □□□□□□
Slot | □□
Specimen | □□
SpecimenDefinition | □□□□
StructureDefinition | □□□□
StructureMap | □□□□
Subscription | □□
Substance | □□
SubstanceNucleicAcid
SubstancePolymer
SubstanceProtein
SubstanceReferenceInformation
SubstanceSourceMaterial
SubstanceSpecification
SupplyDelivery | □□□□
SupplyRequest | □□□□
Task | □□
TerminologyCapabilities | □□□□□□
TestReport | □□□□
TestScript | □□□□
ValueSet | □□□□
VerificationResult
VisionPrescription | □□□□

See the full registry of code systems defined as part of FHIR.

Explanation of the columns that may appear on this page:

Level | A few code lists that FHIR defines are hierarchical - each code is assigned a level. See Code System for further information.
Source | The source of the definition of the code (when the value set draws in codes defined elsewhere)
Code | The code (used as the code in the resource instance). If the code is in italics, this indicates that the code is not selectable ('Abstract')
Display | The display (used in the display element of a Coding). If there is no display, implementers should not simply display the code, but map the concept into their application
Definition | An explanation of the meaning of the concept
Comments | Additional notes about how to use the code

4.3.14.80 Code System http://terminology.hl7.org/CodeSystem/supplyrequest-reason

URL: https://hl7.org/fhir/R4/codesystem-supplyrequest-reason.html
Orders and Observations Work Group | Maturity Level: 1 | Draft | Use Context: Any

This is a code system defined by the FHIR project.

Summary

Defining URL: | http://terminology.hl7.org/CodeSystem/supplyrequest-reason
Version: | 4.0.1
Name: | SupplyRequestReason
Title: | SupplyRequestReason
Definition: | The reason why the supply item was requested.
Committee: | Orders and Observations Work Group
OID: | 2.16.840.1.113883.4.642.4.1193 (for OID based terminology systems)
Source Resource | XML / JSON

This Code system is used in the following value sets:

• ValueSet: SupplyRequestReason (The reason why the supply item was requested.)

• ValueSet: SupplyRequestReason (The reason why the supply item was requested.)

4.3.14.80.1 Content

4.3.14.80.2 SupplyRequestReason

The reason why the supply item was requested.

This code system http://terminology.hl7.org/CodeSystem/supplyrequest-reason defines the following codes:

Code | Display | Definition
patient-care | Patient Care | The supply has been requested for use in direct patient care.
ward-stock | Ward Stock | The supply has been requested for creating or replenishing ward stock.

See the full registry of code systems defined as part of FHIR.

Explanation of the columns that may appear on this page:

Level | A few code lists that FHIR defines are hierarchical - each code is assigned a level. See Code System for further information.
Source | The source of the definition of the code (when the value set draws in codes defined elsewhere)
Code | The code (used as the code in the resource instance). If the code is in italics, this indicates that the code is not selectable ('Abstract')
Display | The display (used in the display element of a Coding). If there is no display, implementers should not simply display the code, but map the concept into their application
Definition | An explanation of the meaning of the concept
Comments | Additional notes about how to use the code

4.3.14.81 Code System http://terminology.hl7.org/CodeSystem/practitioner-role

URL: https://hl7.org/fhir/R4/codesystem-practitioner-role.html
Patient Administration Work Group | Maturity Level: 1 | Draft | Use Context: Any

This is a code system defined by the FHIR project.

Summary

Defining URL: | http://terminology.hl7.org/CodeSystem/practitioner-role
Version: | 4.0.1
Name: | PractitionerRole
Title: | Practitioner role
Definition: | This example value set defines a set of codes that can be used to indicate the role of a Practitioner.
Committee: | Patient Administration Work Group
OID: | 2.16.840.1.113883.4.642.4.1132 (for OID based terminology systems)
Copyright: | This resource includes content from SNOMED Clinical Terms® (SNOMED CT®) which is copyright of the International Health Terminology Standards Development Organisation (IHTSDO). Implementers of these specifications must have the appropriate SNOMED CT Affiliate license - for more information contact http://www.snomed.org/snomed-ct/get-snomed-ct or info@snomed.org
Source Resource | XML / JSON

This Code system is used in the following value sets:

• ValueSet: Practitioner role (This example value set defines a set of codes that can be used to indicate the role of a Practitioner.)

• ValueSet: Practitioner role (This example value set defines a set of codes that can be used to indicate the role of a Practitioner.)

4.3.14.81.1 Content

4.3.14.81.2 Practitioner role

This example value set defines a set of codes that can be used to indicate the role of a Practitioner.

Copyright Statement:

This resource includes content from SNOMED Clinical Terms® (SNOMED CT®) which is copyright of the International Health Terminology Standards Development Organisation (IHTSDO). Implementers of these specifications must have the appropriate SNOMED CT Affiliate license - for more information contact http://www.snomed.org/snomed-ct/get-snomed-ct or info@snomed.org

This code system http://terminology.hl7.org/CodeSystem/practitioner-role defines the following codes:

Code | Display | Definition
doctor | Doctor | A qualified/registered medical practitioner
nurse | Nurse | A practitioner with nursing experience that may be qualified/registered
pharmacist | Pharmacist | A qualified/registered/licensed pharmacist
researcher | Researcher | A practitioner that may perform research
teacher | Teacher/educator | Someone who is able to provide educational services
ict | ICT professional | Someone who is qualified in Information and Communication Technologies

See the full registry of code systems defined as part of FHIR.

Explanation of the columns that may appear on this page:

Level | A few code lists that FHIR defines are hierarchical - each code is assigned a level. See Code System for further information.
Source | The source of the definition of the code (when the value set draws in codes defined elsewhere)
Code | The code (used as the code in the resource instance). If the code is in italics, this indicates that the code is not selectable ('Abstract')
Display | The display (used in the display element of a Coding). If there is no display, implementers should not simply display the code, but map the concept into their application
Definition | An explanation of the meaning of the concept
Comments | Additional notes about how to use the code

4.3.14.82 Code System http://hl7.org/fhir/assert-direction-codes

URL: https://hl7.org/fhir/R4/codesystem-assert-direction-codes.html
FHIR Infrastructure Work Group | Maturity Level: 2 | Trial Use | Use Context: Any

This is a code system defined by the FHIR project.

Summary

Defining URL: | http://hl7.org/fhir/assert-direction-codes
Version: | 4.0.1
Name: | AssertionDirectionType
Title: | AssertionDirectionType
Definition: | The type of direction to use for assertion.
Committee: | FHIR Infrastructure Work Group
OID: | 2.16.840.1.113883.4.642.4.707 (for OID based terminology systems)
Source Resource | XML / JSON

This Code system is used in the following value sets:

• ValueSet: AssertionDirectionType (The type of direction to use for assertion.)

• ValueSet: AssertionDirectionType (The type of direction to use for assertion.)

4.3.14.82.1 Content

4.3.14.82.2 AssertionDirectionType

The type of direction to use for assertion.

This code system http://hl7.org/fhir/assert-direction-codes defines the following codes:

Code | Display | Definition
response | response | The assertion is evaluated on the response. This is the default value.
request | request | The assertion is evaluated on the request.

See the full registry of code systems defined as part of FHIR.

Explanation of the columns that may appear on this page:

Level | A few code lists that FHIR defines are hierarchical - each code is assigned a level. See Code System for further information.
Source | The source of the definition of the code (when the value set draws in codes defined elsewhere)
Code | The code (used as the code in the resource instance). If the code is in italics, this indicates that the code is not selectable ('Abstract')
Display | The display (used in the display element of a Coding). If there is no display, implementers should not simply display the code, but map the concept into their application
Definition | An explanation of the meaning of the concept
Comments | Additional notes about how to use the code

4.3.14.83 Code System http://hl7.org/fhir/resource-validation-mode

URL: https://hl7.org/fhir/R4/codesystem-resource-validation-mode.html
Vocabulary Work Group | Maturity Level: 0 | Informative | Use Context: Any

This is a code system defined by the FHIR project.

Summary

Defining URL: | http://hl7.org/fhir/resource-validation-mode
Version: | 4.0.1
Name: | ResourceValidationMode
Title: | ResourceValidationMode
Definition: | Codes indicating the type of validation to perform.
Committee: | ??
OID: | 2.16.840.1.113883.4.642.4.119 (for OID based terminology systems)
Source Resource | XML / JSON

This Code system is used in the following value sets:

• ValueSet: ResourceValidationMode (Codes indicating the type of validation to perform.)

• ValueSet: ResourceValidationMode (Codes indicating the type of validation to perform.)

4.3.14.83.1 Content

4.3.14.83.2 ResourceValidationMode

Codes indicating the type of validation to perform.

This code system http://hl7.org/fhir/resource-validation-mode defines the following codes:

Code | Display | Definition
create | Validate for Create | The server checks the content, and then checks that the content would be acceptable as a create (e.g. that the content would not violate any uniqueness constraints).
update | Validate for Update | The server checks the content, and then checks that it would accept it as an update against the nominated specific resource (e.g. that there are no changes to immutable fields the server does not allow to change and checking version integrity if appropriate).
delete | Validate for Delete | The server ignores the content and checks that the nominated resource is allowed to be deleted (e.g. checking referential integrity rules).
profile | Validate Against a Profile | The server checks an existing resource (must be nominated by id, not provided as a parameter) as valid against the nominated profile.

See the full registry of code systems defined as part of FHIR.

Explanation of the columns that may appear on this page:

Level | A few code lists that FHIR defines are hierarchical - each code is assigned a level. See Code System for further information.
Source | The source of the definition of the code (when the value set draws in codes defined elsewhere)
Code | The code (used as the code in the resource instance). If the code is in italics, this indicates that the code is not selectable ('Abstract')
Display | The display (used in the display element of a Coding). If there is no display, implementers should not simply display the code, but map the concept into their application
Definition | An explanation of the meaning of the concept
Comments | Additional notes about how to use the code

4.3.14.84 Code System http://hl7.org/fhir/conceptmap-unmapped-mode

URL: https://hl7.org/fhir/R4/codesystem-conceptmap-unmapped-mode.html
Vocabulary Work Group | Maturity Level: 3 | Trial Use | Use Context: Any

This is a code system defined by the FHIR project.

Summary

Defining URL: | http://hl7.org/fhir/conceptmap-unmapped-mode
Version: | 4.0.1
Name: | ConceptMapGroupUnmappedMode
Title: | ConceptMapGroupUnmappedMode
Definition: | Defines which action to take if there is no match in the group.
Committee: | Vocabulary Work Group
OID: | 2.16.840.1.113883.4.642.4.481 (for OID based terminology systems)
Source Resource | XML / JSON

This Code system is used in the following value sets:

• ValueSet: ConceptMapGroupUnmappedMode (Defines which action to take if there is no match in the group.)

• ValueSet: ConceptMapGroupUnmappedMode (Defines which action to take if there is no match in the group.)

4.3.14.84.1 Content

4.3.14.84.2 ConceptMapGroupUnmappedMode

Defines which action to take if there is no match in the group.

This code system http://hl7.org/fhir/conceptmap-unmapped-mode defines the following codes:

Code | Display | Definition
provided | Provided Code | Use the code as provided in the $translate request.
fixed | Fixed Code | Use the code explicitly provided in the group.unmapped.
other-map | Other Map | Use the map identified by the canonical URL in the url element.

See the full registry of code systems defined as part of FHIR.

Explanation of the columns that may appear on this page:

Level | A few code lists that FHIR defines are hierarchical - each code is assigned a level. See Code System for further information.
Source | The source of the definition of the code (when the value set draws in codes defined elsewhere)
Code | The code (used as the code in the resource instance). If the code is in italics, this indicates that the code is not selectable ('Abstract')
Display | The display (used in the display element of a Coding). If there is no display, implementers should not simply display the code, but map the concept into their application
Definition | An explanation of the meaning of the concept
Comments | Additional notes about how to use the code

4.3.14.85 Code System http://hl7.org/fhir/administrative-gender

URL: https://hl7.org/fhir/R4/codesystem-administrative-gender.html
Patient Administration Work Group | Maturity Level: N | Normative (from v4.0.0) | Use Context: Any

| This page has been approved as part of an ANSI standard. See the Patient Package for further details.

This is a code system defined by the FHIR project.

Summary

Defining URL: | http://hl7.org/fhir/administrative-gender
Version: | 4.0.1
Name: | AdministrativeGender
Title: | AdministrativeGender
Definition: | The gender of a person used for administrative purposes.
Committee: | Patient Administration Work Group
OID: | 2.16.840.1.113883.4.642.4.2 (for OID based terminology systems)
Source Resource | XML / JSON

This Code system is used in the following value sets:

• ValueSet: AdministrativeGender (The gender of a person used for administrative purposes.)

• ValueSet: AdministrativeGender (The gender of a person used for administrative purposes.)

4.3.14.85.1 Content

4.3.14.85.2 AdministrativeGender

The gender of a person used for administrative purposes.

This code system http://hl7.org/fhir/administrative-gender defines the following codes:

Code | Display | Definition | Comments
male | Male | Male. | Male
female | Female | Female. | Female
other | Other | Other. | The administrative gender is a value other than male/female/unknown. Where this value is selected, systems may often choose to include an extension with the localized more specific value.
unknown | Unknown | Unknown. | A proper value is applicable, but not known. Usage Notes: This means the actual value is not known. If the only thing that is unknown is how to properly express the value in the necessary constraints (value set, datatype, etc.), then the OTH or UNC flavor should be used. No properties should be included for a datatype with this property unless: Those properties themselves directly translate to a semantic of "unknown". (E.g. a local code sent as a translation that conveys 'unknown') Those properties further qualify the nature of what is unknown. (E.g. specifying a use code of "H" and a URL prefix of "tel:" to convey that it is the home phone number that is unknown.)

See the full registry of code systems defined as part of FHIR.

Explanation of the columns that may appear on this page:

Level | A few code lists that FHIR defines are hierarchical - each code is assigned a level. See Code System for further information.
Source | The source of the definition of the code (when the value set draws in codes defined elsewhere)
Code | The code (used as the code in the resource instance). If the code is in italics, this indicates that the code is not selectable ('Abstract')

Display | The display (used in the display element of a Coding). If there is no display, implementers should not simply display the code, but map the concept into their application
Definition | An explanation of the meaning of the concept
Comments | Additional notes about how to use the code

4.3.14.86 Code System http://hl7.org/fhir/extra-activity-type

URL: https://hl7.org/fhir/R4/codesystem-extra-activity-type.html
Vocabulary Work Group | Maturity Level: 0 | Informative | Use Context: Not Intended for Production use

This is a code system defined by the FHIR project.

Summary

Defining URL: | http://hl7.org/fhir/extra-activity-type
Version: | 4.0.1
Name: | ExtraActivityType
Title:
Definition: | This value set includes coded concepts not well covered in any of the included valuesets.
Committee: | ??
OID: | (for OID based terminology systems)
Source Resource | XML / JSON

This Code system is not currently used

4.3.14.86.1 Content

4.3.14.86.2 ExtraActivityType

This value set includes coded concepts not well covered in any of the included valuesets.

This code system http://hl7.org/fhir/extra-activity-type defines the following codes:

Code | Display | Definition
aggregate | aggregate | Activity resulting in a structured collection of preexisting content that does not necessarily result in an integral object with semantic context making it more than the sum of component parts, from which components could be disaggregated without loss of semantic context, e.g., the assembly of multiple stand-alone documents.
compose | compose | Activity resulting in the structured compilation of new and preexisting content for the purposes of forming an integral object with semantic context making it more than the sum of component parts, which would be lost if decomposed. For example, the composition of a document that includes in whole or part other documents along with new content that result in a new document that has unique semantic meaning.
label | label | The means used to associate a set of security attributes with a specific information object as part of the data structure for that object. [ISO-10181-3 Access Control]

See the full registry of code systems defined as part of FHIR.

Explanation of the columns that may appear on this page:

Level | A few code lists that FHIR defines are hierarchical - each code is assigned a level. See Code System for further information.
Source | The source of the definition of the code (when the value set draws in codes defined elsewhere)
Code | The code (used as the code in the resource instance). If the code is in italics, this indicates that the code is not selectable ('Abstract')
Display | The display (used in the display element of a Coding). If there is no display, implementers should not simply display the code, but map the concept into their application
Definition | An explanation of the meaning of the concept
Comments | Additional notes about how to use the code

4.3.14.87 Code System http://hl7.org/fhir/contract-asset-subtype

URL: https://hl7.org/fhir/R4/codesystem-contract-assetsubtype.html
Financial Management Work Group | Maturity Level: 1 | Draft | Use Context: Any

This is a code system defined by the FHIR project.

Summary

Defining URL: | http://hl7.org/fhir/contract-asset-subtype
Version: | 4.0.1
Name: | ContractResourceAssetSub-TypeCodes
Title: | Contract Resource Asset Sub-Type codes
Definition: | This value set contract specific codes for asset subtype.
Committee: | Financial Management Work Group
OID: | 2.16.840.1.113883.4.642.4.1302 (for OID based terminology systems)
Copyright: | HL7 International.
Source Resource | XML / JSON

This Code system is used in the following value sets:

• ValueSet: Contract Resource Asset Sub-Type codes (This value set contract specific codes for asset subtype.)

• ValueSet: Contract Resource Asset Sub-Type codes (This value set contract specific codes for asset subtype.)

4.3.14.87.1 Content

Each definition includes usage notes explaining the precedence order in contract lifecycle - i.e., while only some stages are required, the order in which they may occur is deterministic; and a map to comparable FHIR and v.3 status codes. It follows guidance about use of status codes in FHIR at http://build.fhir.org/sc.html.

4.3.14.87.2 Contract Resource Asset Sub-Type codes

This value set contract specific codes for asset subtype.

Copyright Statement:

HL7 International.

This code system http://hl7.org/fhir/contract-asset-subtype defines the following codes:

Code | Display | Definition
participation | Participation | To be completed

See the full registry of code systems defined as part of FHIR.

Explanation of the columns that may appear on this page:

Level | A few code lists that FHIR defines are hierarchical - each code is assigned a level. See Code System for further information.
Source | The source of the definition of the code (when the value set draws in codes defined elsewhere)
Code | The code (used as the code in the resource instance). If the code is in italics, this indicates that the code is not selectable ('Abstract')
Display | The display (used in the display element of a Coding). If there is no display, implementers should not simply display the code, but map the concept into their application
Definition | An explanation of the meaning of the concept
Comments | Additional notes about how to use the code

4.3.14.88 Code System http://hl7.org/fhir/map-target-list-mode

URL: https://hl7.org/fhir/R4/codesystem-map-target-list-mode.html
FHIR Infrastructure Work Group | Maturity Level: 2 | Trial Use | Use Context: Any

This is a code system defined by the FHIR project.

Summary

Defining URL: | http://hl7.org/fhir/map-target-list-mode
Version: | 4.0.1
Name: | StructureMapTargetListMode
Title: | StructureMapTargetListMode
Definition: | If field is a list, how to manage the production.
Committee: | FHIR Infrastructure Work Group
OID: | 2.16.840.1.113883.4.642.4.686 (for OID based terminology systems)
Source Resource | XML / JSON

This Code system is used in the following value sets:

• ValueSet: StructureMapTargetListMode (If field is a list, how to manage the production.)

• ValueSet: StructureMapTargetListMode (If field is a list, how to manage the production.)

4.3.14.88.1 Content

4.3.14.88.2 StructureMapTargetListMode

If field is a list, how to manage the production.

This code system http://hl7.org/fhir/map-target-list-mode defines the following codes:

Code | Display | Definition
first | First | when the target list is being assembled, the items for this rule go first. If more than one rule defines a first item (for a given instance of mapping) then this is an error.
share | Share | the target instance is shared with the target instances generated by another rule (up to the first common n items, then create new ones).
last | Last | when the target list is being assembled, the items for this rule go last. If more than one rule defines a last item (for a given instance of mapping) then this is an error.
collate | Collate | re-use the first item in the list, and keep adding content to it.

See the full registry of code systems defined as part of FHIR.

Explanation of the columns that may appear on this page:

Level | A few code lists that FHIR defines are hierarchical - each code is assigned a level. See Code System for further information.
Source | The source of the definition of the code (when the value set draws in codes defined elsewhere)

Code | The code (used as the code in the resource instance). If the code is in italics, this indicates that the code is not selectable ('Abstract')
Display | The display (used in the display element of a Coding). If there is no display, implementers should not simply display the code, but map the concept into their application
Definition | An explanation of the meaning of the concept
Comments | Additional notes about how to use the code

4.3.14.89 Code System http://hl7.org/fhir/request-status

URL: https://hl7.org/fhir/R4/codesystem-request-status.html
Patient Care Work Group | Maturity Level: 2 | Trial Use | Use Context: Any

This is a code system defined by the FHIR project.

Summary

Defining URL: | http://hl7.org/fhir/request-status
Version: | 4.0.1
Name: | RequestStatus
Title: | RequestStatus
Definition: | Codes identifying the lifecycle stage of a request.
Committee: | Patient Care Work Group
OID: | 2.16.840.1.113883.4.642.4.112 (for OID based terminology systems)
Source Resource | XML / JSON

This Code system is used in the following value sets:

• ValueSet: RequestStatus (Codes identifying the lifecycle stage of a request.)
• ValueSet: RequestStatus (Codes identifying the lifecycle stage of a request.)

4.3.14.89.1 Content

4.3.14.89.2 RequestStatus

Codes identifying the lifecycle stage of a request.

This code system http://hl7.org/fhir/request-status defines the following codes:

Code | Display | Definition
draft | Draft | The request has been created but is not yet complete or ready for action.
active | Active | The request is in force and ready to be acted upon.
on-hold | On Hold | The request (and any implicit authorization to act) has been temporarily withdrawn but is expected to resume in the future.
revoked | Revoked | The request (and any implicit authorization to act) has been terminated prior to the known full completion of the intended actions. No further activity should occur.
completed | Completed | The activity described by the request has been fully performed. No further activity will occur.
entered-in-error | Entered in Error | This request should never have existed and should be considered 'void'. (It is possible that real-world decisions were based on it. If real-world activity has occurred, the status should be "revoked" rather than "entered-in-error".).
unknown | Unknown | The authoring/source system does not know which of the status values currently applies for this request. Note: This concept is not to be used for "other" - one of the listed statuses is presumed to apply, but the authoring/source system does not know which.

See the full registry of code systems defined as part of FHIR.

Explanation of the columns that may appear on this page:

Level | A few code lists that FHIR defines are hierarchical - each code is assigned a level. See Code System for further information.
Source | The source of the definition of the code (when the value set draws in codes defined elsewhere)
Code | The code (used as the code in the resource instance). If the code is in italics, this indicates that the code is not selectable ('Abstract')
Display | The display (used in the display element of a Coding). If there is no display, implementers should not simply display the code, but map the concept into their application
Definition | An explanation of the meaning of the concept
Comments | Additional notes about how to use the code

4.3.14.90 Code System http://terminology.hl7.org/CodeSystem/security-source-type

URL: https://hl7.org/fhir/R4/codesystem-audit-source-type.html
Security Work Group | Maturity Level: 3 | Trial Use | Use Context: Any

This is a code system defined by the FHIR project.

Summary

Defining URL: | http://terminology.hl7.org/CodeSystem/security-source-type
Version: | 4.0.1
Name: | AuditEventSourceType
Title: | Audit Event Source Type

Definition: | The type of process where the audit event originated from.
Committee: | Security Work Group
OID: | 2.16.840.1.113883.4.642.4.1137 (for OID based terminology systems)
Source Resource | XML / JSON

This Code system is used in the following value sets:

• ValueSet: Audit Event Source Type (The type of process where the audit event originated from.)

• ValueSet: Audit Event Source Type (The type of process where the audit event originated from.)

4.3.14.90.1 Content

4.3.14.90.2 Audit Event Source Type

The type of process where the audit event originated from.

This code system http://terminology.hl7.org/CodeSystem/security-source-type defines the following codes:

Code | Display | Definition
1 | User Device | End-user display device, diagnostic device.
2 | Data Interface | Data acquisition device or instrument.
3 | Web Server | Web Server process or thread.
4 | Application Server | Application Server process or thread.
5 | Database Server | Database Server process or thread.
6 | Security Server | Security server, e.g. a domain controller.
7 | Network Device | ISO level 1-3 network component.
8 | Network Router | ISO level 4-6 operating software.
9 | Other | Other kind of device (defined by DICOM, but some other code/system can be used).

See the full registry of code systems defined as part of FHIR.

Explanation of the columns that may appear on this page:

Level | A few code lists that FHIR defines are hierarchical - each code is assigned a level. See Code System for further information.
Source | The source of the definition of the code (when the value set draws in codes defined elsewhere)
Code | The code (used as the code in the resource instance). If the code is in italics, this indicates that the code is not selectable ('Abstract')
Display | The display (used in the display element of a Coding). If there is no display, implementers should not simply display the code, but map the concept into their application
Definition | An explanation of the meaning of the concept
Comments | Additional notes about how to use the code

4.3.14.91 Code System http://hl7.org/fhir/organization-role

URL: https://hl7.org/fhir/R4/codesystem-organization-role.html
Patient Administration Work Group | Maturity Level: 1 | Draft | Use Context: Any

This is a code system defined by the FHIR project.

Summary

Defining URL: | http://hl7.org/fhir/organization-role
Version: | 4.0.1
Name: | OrganizationAffiliationRole
Title: | Organization Affiliation Role
Definition: | This example value set defines a set of codes that can be used to indicate the role of one Organization in relation to another.
Committee: | Patient Administration Work Group
OID: | 2.16.840.1.113883.4.642.4.881 (for OID based terminology systems)
Source Resource | XML / JSON

This Code system is used in the following value sets:

• ValueSet: Organization Affiliation Role (This example value set defines a set of codes that can be used to indicate the role of one Organization in relation to another.)

• ValueSet: Organization Affiliation Role (This example value set defines a set of codes that can be used to indicate the role of one Organization in relation to another.)

4.3.14.91.1 Content

4.3.14.91.2 Organization Affiliation Role

This example value set defines a set of codes that can be used to indicate the role of one Organization in relation to another.

This code system http://hl7.org/fhir/organization-role defines the following codes:

Code | Display | Definition
provider | Provider
agency | Agency | An organization such as a public health agency, community/social services provider, etc.

research | Research | An organization providing research-related services such as conducting research, recruiting research participants, analyzing data, etc.
payer | Payer | An organization providing reimbursement, payment, or related services
diagnostics | Diagnostics | An organization providing diagnostic testing/laboratory services
supplier | Supplier | An organization that provides medical supplies (e.g. medical devices, equipment, pharmaceutical products, etc.)
HIE/HIO | HIE/HIO | An organization that facilitates electronic clinical data exchange between entities
member | Member | A type of non-ownership relationship between entities (encompasses partnerships, collaboration, joint ventures, etc.)

See the full registry of code systems defined as part of FHIR.

Explanation of the columns that may appear on this page:

Level | A few code lists that FHIR defines are hierarchical - each code is assigned a level. See Code System for further information.
Source | The source of the definition of the code (when the value set draws in codes defined elsewhere)
Code | The code (used as the code in the resource instance). If the code is in italics, this indicates that the code is not selectable ('Abstract')
Display | The display (used in the display element of a Coding). If there is no display, implementers should not simply display the code, but map the concept into their application
Definition | An explanation of the meaning of the concept
Comments | Additional notes about how to use the code

4.3.14.92 Code System http://hl7.org/fhir/invoice-status

URL: https://hl7.org/fhir/R4/codesystem-invoice-status.html
Financial Management Work Group | Maturity Level: 0 | Trial Use | Use Context: Any

This is a code system defined by the FHIR project.

Summary

Defining URL: | http://hl7.org/fhir/invoice-status
Version: | 4.0.1
Name: | InvoiceStatus
Title: | InvoiceStatus
Definition: | Codes identifying the lifecycle stage of an Invoice.
Committee: | Financial Management Work Group
OID: | 2.16.840.1.113883.4.642.4.867 (for OID based terminology systems)
Source Resource | XML / JSON

This Code system is used in the following value sets:

• ValueSet: InvoiceStatus (Codes identifying the lifecycle stage of an Invoice.)

• ValueSet: InvoiceStatus (Codes identifying the lifecycle stage of an Invoice.)

4.3.14.92.1 Content

4.3.14.92.2 InvoiceStatus

Codes identifying the lifecycle stage of an Invoice.

This code system http://hl7.org/fhir/invoice-status defines the following codes:

Code | Display | Definition
draft | draft | the invoice has been prepared but not yet finalized.
issued | issued | the invoice has been finalized and sent to the recipient.
balanced | balanced | the invoice has been balaced / completely paid.
cancelled | cancelled | the invoice was cancelled.
entered-in-error | entered in error | the invoice was determined as entered in error before it was issued.

See the full registry of code systems defined as part of FHIR.

Explanation of the columns that may appear on this page:

Level | A few code lists that FHIR defines are hierarchical - each code is assigned a level. See Code System for further information.
Source | The source of the definition of the code (when the value set draws in codes defined elsewhere)
Code | The code (used as the code in the resource instance). If the code is in italics, this indicates that the code is not selectable ('Abstract')
Display | The display (used in the display element of a Coding). If there is no display, implementers should not simply display the code, but map the concept into their application
Definition | An explanation of the meaning of the concept
Comments | Additional notes about how to use the code

4.3.14.93 Code System http://hl7.org/fhir/questionnaire-display-category

URL: https://hl7.org/fhir/R4/codesystem-questionnaire-display-category.html
Vocabulary Work Group | Maturity Level: 0 | Informative | Use Context: Any

This is a code system defined at http://www.hl7.org/Special/committees/patientcare .

Summary

Defining URL: | http://hl7.org/fhir/questionnaire-display-category
Version: | 4.0.1
Name: | QuestionnaireTextCategories
Title: | Questionnaire Text Categories
Definition: | Codes defining the purpose of a Questionnaire item of type 'text'.
Committee: | ??
OID: | 2.16.840.1.113883.4.642.4.936 (for OID based terminology systems)
Source Resource | XML / JSON

This Code system is used in the following value sets:

• ValueSet: Questionnaire Text Categories (Codes defining the purpose of a Questionnaire item of type 'text'.)

• ValueSet: Questionnaire Text Categories (Codes defining the purpose of a Questionnaire item of type 'text'.)

4.3.14.93.1 Content

4.3.14.93.2 Questionnaire Text Categories

Codes defining the purpose of a Questionnaire item of type 'text'.

This code system http://hl7.org/fhir/questionnaire-display-category defines the following codes:

Code | Display | Definition
instructions | Instructions | The text provides guidance on how to populate or use a portion of the questionnaire (or the questionnaire as a whole).
security | Security | The text provides guidance on how the information should be or will be handled from a security/confidentiality/access control perspective when completed
help | Help | The text provides additional guidance on populating the containing item. Help text isn't necessarily expected to be rendered as part of the form, but may instead be made available through fly-over, pop-up button, link to a "help" page, etc.

See the full registry of code systems defined as part of FHIR.

Explanation of the columns that may appear on this page:

Level | A few code lists that FHIR defines are hierarchical - each code is assigned a level. See Code System for further information.
Source | The source of the definition of the code (when the value set draws in codes defined elsewhere)
Code | The code (used as the code in the resource instance). If the code is in italics, this indicates that the code is not selectable ('Abstract')
Display | The display (used in the display element of a Coding). If there is no display, implementers should not simply display the code, but map the concept into their application
Definition | An explanation of the meaning of the concept
Comments | Additional notes about how to use the code

4.3.14.94 Code System http://hl7.org/fhir/flag-status

URL: https://hl7.org/fhir/R4/codesystem-flag-status.html
Patient Care Work Group | Maturity Level: 1 | Trial Use | Use Context: Any

This is a code system defined by the FHIR project.

Summary

Defining URL: | http://hl7.org/fhir/flag-status
Version: | 4.0.1
Name: | FlagStatus
Title: | FlagStatus
Definition: | Indicates whether this flag is active and needs to be displayed to a user, or whether it is no longer needed or was entered in error.
Committee: | Patient Care Work Group
OID: | 2.16.840.1.113883.4.642.4.121 (for OID based terminology systems)
Source Resource | XML / JSON

This Code system is used in the following value sets:

• ValueSet: FlagStatus (Indicates whether this flag is active and needs to be displayed to a user, or whether it is no longer needed or was entered in error.)

• ValueSet: FlagStatus (Indicates whether this flag is active and needs to be displayed to a user, or whether it is no longer needed or was entered in error.)

4.3.14.94.1 Content

4.3.14.94.2 FlagStatus

Indicates whether this flag is active and needs to be displayed to a user, or whether it is no longer needed or was entered in error.

This code system http://hl7.org/fhir/flag-status defines the following codes:

Code | Display | Definition
active | Active | A current flag that should be displayed to a user. A system may use the category to determine which user roles should view the flag.
inactive | Inactive | The flag no longer needs to be displayed.
entered-in-error | Entered in Error | The flag was added in error and should no longer be displayed.

See the full registry of code systems defined as part of FHIR.

Explanation of the columns that may appear on this page:

Level | A few code lists that FHIR defines are hierarchical - each code is assigned a level. See Code System for further information.
Source | The source of the definition of the code (when the value set draws in codes defined elsewhere)
Code | The code (used as the code in the resource instance). If the code is in italics, this indicates that the code is not selectable ('Abstract')
Display | The display (used in the display element of a Coding). If there is no display, implementers should not simply display the code, but map the concept into their application
Definition | An explanation of the meaning of the concept
Comments | Additional notes about how to use the code

4.3.14.95 Code System http://hl7.org/fhir/goal-status-reason

URL: https://hl7.org/fhir/R4/codesystem-goal-status-reason.html
Vocabulary Work Group | Maturity Level: 0 | Informative | Use Context: Any

This is a code system defined at http://www.hl7.org/Special/committees/patientcare/ .

Summary

Defining URL: | http://hl7.org/fhir/goal-status-reason
Version: | 4.0.1
Name: | GoalStatusReason
Title: | Goal status reason
Definition: | Example codes indicating the reason for a current status. Note that these are in no way complete and might not even be appropriate for some uses.
Committee: | ??
OID: | 2.16.840.1.113883.4.642.4.278 (for OID based terminology systems)
Source Resource | XML / JSON

This Code system is used in the following value sets:

• ValueSet: Goal status reason (Example codes indicating the reason for a current status. Note that these are in no way complete and might not even be appropriate for some uses.)

• ValueSet: Goal status reason (Example codes indicating the reason for a current status. Note that these are in no way complete and might not even be appropriate for some uses.)

4.3.14.95.1 Content

4.3.14.95.2 Goal status reason

Example codes indicating the reason for a current status. Note that these are in no way complete and might not even be appropriate for some uses.

This code system http://hl7.org/fhir/goal-status-reason defines the following codes:

Code | Display | Definition
surgery | Surgery | Goal suspended or ended because of a surgical procedure.
life-event | Life Event | Goal suspended or ended because of a significant life event (marital change, bereavement, etc.).
replaced | Replaced | Goal has been superseded by a new goal.
patient-request | Patient Request | Patient wishes the goal to be set aside, at least temporarily.
temp-not-attainable | Goal Not Attainable Temporarily | Goal cannot be reached temporarily.
permanent-not-attainable | Goal Not Attainable Permanently | Goal cannot be reached permanently.
financial-barrier | Financial Reason | Goal cannot be reached due to financial barrier or reason.
lack-of-transportation | Lack Of Transportation | Goal cannot be reached due to a lack of transportation.
lack-of-social-support | Lack Of Social Support | Goal cannot be reached due to a lack of social support.

See the full registry of code systems defined as part of FHIR.

Explanation of the columns that may appear on this page:

Level | A few code lists that FHIR defines are hierarchical - each code is assigned a level. See Code System for further information.
Source | The source of the definition of the code (when the value set draws in codes defined elsewhere)
Code | The code (used as the code in the resource instance). If the code is in italics, this indicates that the code is not selectable ('Abstract')
Display | The display (used in the display element of a Coding). If there is no display, implementers should not simply display the code, but map the concept into their application
Definition | An explanation of the meaning of the concept
Comments | Additional notes about how to use the code

4.3.14.96 Code System http://terminology.hl7.org/CodeSystem/special-values

URL: https://hl7.org/fhir/R4/codesystem-special-values.html
FHIR Infrastructure Work Group | Maturity Level: 0 | Informative | Use Context: Any

This is a code system defined by the FHIR project.

Summary

Defining URL: | http://terminology.hl7.org/CodeSystem/special-values
Version: | 4.0.1
Name: | SpecialValues
Title: | SpecialValues
Definition: | A set of generally useful codes defined so they can be included in value sets.
Committee: | FHIR Infrastructure Work Group
OID: | 2.16.840.1.113883.4.642.4.1049 (for OID based terminology systems)
Source Resource | XML / JSON

This Code system is used in the following value sets:

• ValueSet: SpecialValues (A set of generally useful codes defined so they can be included in value sets.)
• ValueSet: SpecialValues (A set of generally useful codes defined so they can be included in value sets.)

4.3.14.96.1 Content

4.3.14.96.2 SpecialValues

A set of generally useful codes defined so they can be included in value sets.

This code system http://terminology.hl7.org/CodeSystem/special-values defines the following codes:

Code | Display | Definition | Comments
true | true | Boolean true.
false | false | Boolean false.
trace | Trace Amount Detected | The content is greater than zero, but too small to be quantified.
sufficient | Sufficient Quantity | The specific quantity is not known, but is known to be non-zero and is not specified because it makes up the bulk of the material. | used in formulations (e.g. 'Add 10mg of ingredient X, 50mg of ingredient Y, and sufficient quantity of water to 100mL.' This code would be used to express the quantity of water.)
withdrawn | Value Withdrawn | The value is no longer available.
nil-known | Nil Known | The are no known applicable values in this context. | The existence of this subject to review

See the full registry of code systems defined as part of FHIR.

Explanation of the columns that may appear on this page:

Level | A few code lists that FHIR defines are hierarchical - each code is assigned a level. See Code System for further information.
Source | The source of the definition of the code (when the value set draws in codes defined elsewhere)
Code | The code (used as the code in the resource instance). If the code is in italics, this indicates that the code is not selectable ('Abstract')
Display | The display (used in the display element of a Coding). If there is no display, implementers should not simply display the code, but map the concept into their application
Definition | An explanation of the meaning of the concept
Comments | Additional notes about how to use the code

4.3.14.97 Code System http://hl7.org/fhir/link-type

URL: https://hl7.org/fhir/R4/codesystem-link-type.html
Patient Administration Work Group | Maturity Level: N | Normative (from v4.0.0) | Use Context: Any

| This page has been approved as part of an ANSI standard. See the Patient Package for further details.

This is a code system defined by the FHIR project.

Summary

Defining URL: | http://hl7.org/fhir/link-type
Version: | 4.0.1
Name: | LinkType
Title: | LinkType
Definition: | The type of link between this patient resource and another patient resource.
Committee: | Patient Administration Work Group
OID: | 2.16.840.1.113883.4.642.4.424 (for OID based terminology systems)
Source Resource | XML / JSON

This Code system is used in the following value sets:

• ValueSet: LinkType (The type of link between this patient resource and another patient resource.)
• ValueSet: LinkType (The type of link between this patient resource and another patient resource.)

4.3.14.97.1 Content

• All Languages
• English
• Nederlands (Dutch)

This code system http://hl7.org/fhir/link-type defines the following codes:

Code | Display | Definition
replaced-by | Replaced-by | The patient resource containing this link must no longer be used. The link points forward to another patient resource that must be used in lieu of the patient resource that contains this link.
replaces | Replaces | The patient resource containing this link is the current active patient record. The link points back to an inactive patient resource that has been merged into this resource, and should be consulted to retrieve additional referenced information.
refer | Refer | The patient resource containing this link is in use and valid but not considered the main source of information about a patient. The link points forward to another patient resource that should be consulted to retrieve additional patient information.
seealso | See also | The patient resource containing this link is in use and valid, but points to another patient resource that is known to contain data about the same person. Data in this resource might overlap or contradict information found in the other patient resource. This link does not indicate any relative importance of the resources concerned, and both should be regarded as equally valid.

This code system http://hl7.org/fhir/link-type defines the following codes:

Code | Display | Definition
replaced-by | Replaced-by | The patient resource containing this link must no longer be used. The link points forward to another patient resource that must be used in lieu of the patient resource that contains this link.
replaces | Replaces | The patient resource containing this link is the current active patient record. The link points back to an inactive patient resource that has been merged into this resource, and should be consulted to retrieve additional referenced information.
refer | Refer | The patient resource containing this link is in use and valid but not considered the main source of information about a patient. The link points forward to another patient resource that should be consulted to retrieve additional patient information.
seealso | See also | The patient resource containing this link is in use and valid, but points to another patient resource that is known to contain data about the same person. Data in this resource might overlap or contradict information found in the other patient resource. This link does not indicate any relative importance of the resources concerned, and both should be regarded as equally valid.

Dit code systeem http://hl7.org/fhir/link-type definieert de volgende codes:

Code | Display | Definition
replaced-by
replaces
refer
seealso

See the full registry of code systems defined as part of FHIR.

Explanation of the columns that may appear on this page:

Level | A few code lists that FHIR defines are hierarchical - each code is assigned a level. See Code System for further information.
Source | The source of the definition of the code (when the value set draws in codes defined elsewhere)
Code | The code (used as the code in the resource instance). If the code is in italics, this indicates that the code is not selectable ('Abstract')
Display | The display (used in the display element of a Coding). If there is no display, implementers should not simply display the code, but map the concept into their application
Definition | An explanation of the meaning of the concept
Comments | Additional notes about how to use the code

4.3.14.98 Code System http://terminology.hl7.org/CodeSystem/library-type

URL: https://hl7.org/fhir/R4/codesystem-library-type.html
Clinical Decision Support Work Group | Maturity Level: 2 | Trial Use | Use Context: Any

This is a code system defined by the FHIR project.

Summary

Defining URL: | http://terminology.hl7.org/CodeSystem/library-type
Version: | 4.0.1
Name: | LibraryType
Title: | LibraryType
Definition: | The type of knowledge asset this library contains.
Committee: | Clinical Decision Support Work Group
OID: | 2.16.840.1.113883.4.642.4.1230 (for OID based terminology systems)
Source Resource | XML / JSON

This Code system is used in the following value sets:

• ValueSet: LibraryType (The type of knowledge asset this library contains.)
• ValueSet: LibraryType (The type of knowledge asset this library contains.)

4.3.14.98.1 Content

4.3.14.98.2 LibraryType

The type of knowledge asset this library contains.

This code system http://terminology.hl7.org/CodeSystem/library-type defines the following codes:

Code | Display | Definition
logic-library | Logic Library | The resource is a shareable library of formalized knowledge.
model-definition | Model Definition | The resource is a definition of an information model.
asset-collection | Asset Collection | The resource is a collection of knowledge assets.
module-definition | Module Definition | The resource defines the dependencies, parameters, and data requirements for a particular module or evaluation context.

See the full registry of code systems defined as part of FHIR.

Explanation of the columns that may appear on this page:

Level | A few code lists that FHIR defines are hierarchical - each code is assigned a level. See Code System for further information.
Source | The source of the definition of the code (when the value set draws in codes defined elsewhere)
Code | The code (used as the code in the resource instance). If the code is in italics, this indicates that the code is not selectable ('Abstract')
Display | The display (used in the display element of a Coding). If there is no display, implementers should not simply display the code, but map the concept into their application
Definition | An explanation of the meaning of the concept
Comments | Additional notes about how to use the code

4.3.14.99 Code System http://terminology.hl7.org/CodeSystem/service-category

URL: https://hl7.org/fhir/R4/codesystem-service-category.html
Patient Administration Work Group | Maturity Level: 1 | Draft | Use Context: Any

This is a code system defined by the FHIR project.

Summary

Defining URL: | http://terminology.hl7.org/CodeSystem/service-category
Version: | 4.0.1
Name: | ServiceCategory
Title: | Service category
Definition: | This value set defines an example set of codes that can be used to classify groupings of service-types/specialties.
Committee: | Patient Administration Work Group
OID: | 2.16.840.1.113883.4.642.4.1144 (for OID based terminology systems)
Source Resource | XML / JSON

This Code system is used in the following value sets:

• ValueSet: Service category (This value set defines an example set of codes that can be used to classify groupings of service-types/specialties.)

• ValueSet: Service category (This value set defines an example set of codes that can be used to classify groupings of service-types/specialties.)

4.3.14.99.1 Content

4.3.14.99.2 Service category

This value set defines an example set of codes that can be used to classify groupings of service-types/specialties.

This code system http://terminology.hl7.org/CodeSystem/service-category defines many codes, of which the following are some examples:

Code | Display | Definition
1 | Adoption | Adoption
2 | Aged Care | Aged Care
34 | Allied Health | Allied Health
3 | Alternative/Complementary Therapies | Alternative & Complementary Therapies
4 | Child Care /Kindergarten | Child Care and/or Kindergarten
5 | Child Development | Child Development
6 | Child Protection & Family Services | Child Protection & Family Services
7 | Community Health Care | Community Health Care
8 | Counselling | Counselling
36 | Crisis Line (GPAH use only) | Crisis Line (GPAH use only)
9 | Death Services | Death Services
10 | Dental | Dental
11 | Disability Support | Disability Support
12 | Drug/Alcohol | Drug/Alcohol
13 | Education & Learning | Education & Learning
14 | Emergency Department | Emergency Department

15 | Employment | Employment
16 | Financial & Material Aid | Financial & Material aid
17 | General Practice | General Practice/GP (doctor)
35 | Hospital | Hospital
18 | Housing/Homelessness | Housing/Homelessness
19 | Interpreting | Interpreting
20 | Justice | Justice
21 | Legal | Legal
22 | Mental Health | Mental Health
38 | NDIA | NDIA
23 | Physical Activity & Recreation | Physical Activity & Recreation
24 | Regulation | Regulation
25 | Respite/Carer Support | Respite/Carer Support
26 | Specialist Clinical Pathology | Specialist Clinical Pathology - requires referral
27 | Specialist Medical | Specialist Medical - requires referral
28 | Specialist Obstetrics & Gynecology | Specialist Obstetrics & Gynecology - requires referral
29 | Specialist Paediatric | Specialist Paediatric - requires referral
30 | Specialist Radiology/Imaging | Specialist Radiology/Imaging - requires referral
31 | Specialist Surgical | Specialist Surgical - requires referral
32 | Support Group/s | Support group/s
37 | Test Message (HSD admin) | Test Message (HSD admin use only)
33 | Transport | Transport

See the full registry of code systems defined as part of FHIR.

Explanation of the columns that may appear on this page:

Level | A few code lists that FHIR defines are hierarchical - each code is assigned a level. See Code System for further information.
Source | The source of the definition of the code (when the value set draws in codes defined elsewhere)
Code | The code (used as the code in the resource instance). If the code is in italics, this indicates that the code is not selectable ('Abstract')
Display | The display (used in the display element of a Coding). If there is no display, implementers should not simply display the code, but map the concept into their application
Definition | An explanation of the meaning of the concept
Comments | Additional notes about how to use the code

4.3.14.100 Code System http://hl7.org/fhir/operation-parameter-use

URL: https://hl7.org/fhir/R4/codesystem-operation-parameter-use.html
FHIR Infrastructure Work Group | Maturity Level: N | Normative (from v4.0.0) | Use Context: Any

| This page has been approved as part of an ANSI standard. See the Conformance Package for further details.

This is a code system defined by the FHIR project.

Summary

Defining URL: | http://hl7.org/fhir/operation-parameter-use
Version: | 4.0.1
Name: | OperationParameterUse
Title: | OperationParameterUse
Definition: | Whether an operation parameter is an input or an output parameter.
Committee: | FHIR Infrastructure Work Group
OID: | 2.16.840.1.113883.4.642.4.509 (for OID based terminology systems)
Source Resource | XML / JSON

This Code system is used in the following value sets:

• ValueSet: OperationParameterUse (Whether an operation parameter is an input or an output parameter.)
• ValueSet: OperationParameterUse (Whether an operation parameter is an input or an output parameter.)

4.3.14.100.1 Content

4.3.14.100.2 OperationParameterUse

Whether an operation parameter is an input or an output parameter.

This code system http://hl7.org/fhir/operation-parameter-use defines the following codes:

Code | Display | Definition
in | In | This is an input parameter.
out | Out | This is an output parameter.

See the full registry of code systems defined as part of FHIR.

Explanation of the columns that may appear on this page:

Level | A few code lists that FHIR defines are hierarchical - each code is assigned a level. See Code System for further information.
Source | The source of the definition of the code (when the value set draws in codes defined elsewhere)

Code | The code (used as the code in the resource instance). If the code is in italics, this indicates that the code is not selectable ('Abstract')
Display | The display (used in the display element of a Coding). If there is no display, implementers should not simply display the code, but map the concept into their application
Definition | An explanation of the meaning of the concept
Comments | Additional notes about how to use the code

4.3.14.101 Code System http://hl7.org/fhir/search-entry-mode

URL: https://hl7.org/fhir/R4/codesystem-search-entry-mode.html
FHIR Infrastructure Work Group | Maturity Level: N | Normative (from v4.0.0) | Use Context: Any

| This page has been approved as part of an ANSI standard. See the Infrastructure Package for further details.

This is a code system defined by the FHIR project.

Summary

Defining URL: | http://hl7.org/fhir/search-entry-mode
Version: | 4.0.1
Name: | SearchEntryMode
Title: | SearchEntryMode
Definition: | Why an entry is in the result set - whether it's included as a match or because of an _include requirement, or to convey information or warning information about the search process.
Committee: | FHIR Infrastructure Work Group
OID: | 2.16.840.1.113883.4.642.4.623 (for OID based terminology systems)
Source Resource | XML / JSON

This Code system is used in the following value sets:

• ValueSet: SearchEntryMode (Why an entry is in the result set - whether it's included as a match or because of an _include requirement, or to convey information or warning information about the search process.)

• ValueSet: SearchEntryMode (Why an entry is in the result set - whether it's included as a match or because of an _include requirement, or to convey information or warning information about the search process.)

4.3.14.101.1 Content

4.3.14.101.2 SearchEntryMode

Why an entry is in the result set - whether it's included as a match or because of an _include requirement, or to convey information or warning information about the search process.

This code system http://hl7.org/fhir/search-entry-mode defines the following codes:

Code | Display | Definition
match | Match | This resource matched the search specification.
include | Include | This resource is returned because it is referred to from another resource in the search set.
outcome | Outcome | An OperationOutcome that provides additional information about the processing of a search.

See the full registry of code systems defined as part of FHIR.

Explanation of the columns that may appear on this page:

Level | A few code lists that FHIR defines are hierarchical - each code is assigned a level. See Code System for further information.
Source | The source of the definition of the code (when the value set draws in codes defined elsewhere)
Code | The code (used as the code in the resource instance). If the code is in italics, this indicates that the code is not selectable ('Abstract')
Display | The display (used in the display element of a Coding). If there is no display, implementers should not simply display the code, but map the concept into their application
Definition | An explanation of the meaning of the concept
Comments | Additional notes about how to use the code

4.3.14.102 Code System http://hl7.org/fhir/contract-asset-context

URL: https://hl7.org/fhir/R4/codesystem-contract-assetcontext.html
Financial Management Work Group | Maturity Level: 1 | Draft | Use Context: Any

This is a code system defined by the FHIR project.

Summary

Defining URL: | http://hl7.org/fhir/contract-asset-context
Version: | 4.0.1
Name: | ContractResourceAssetContextCodes
Title: | Contract Resource Asset Context codes
Definition: | This value set contract specific codes for asset context.
Committee: | Financial Management Work Group
OID: | 2.16.840.1.113883.4.642.4.1298 (for OID based terminology systems)
Copyright: | HL7 International.

Source Resource | XML / JSON

This Code system is used in the following value sets:

• ValueSet: Contract Resource Asset Context codes (This value set contract specific codes for asset context.)

• ValueSet: Contract Resource Asset Context codes (This value set contract specific codes for asset context.)

4.3.14.102.1 Content

Each definition includes usage notes explaining the precedence order in contract lifecycle - i.e., while only some stages are required, the order in which they may occur is deterministic; and a map to comparable FHIR and v.3 status codes. It follows guidance about use of status codes in FHIR at http://build.fhir.org/sc.html.

4.3.14.102.2 Contract Resource Asset Context codes

This value set contract specific codes for asset context.

Copyright Statement:

HL7 International.

This code system http://hl7.org/fhir/contract-asset-context defines the following codes:

Code | Display | Definition
custodian | Custodian | To be completed

See the full registry of code systems defined as part of FHIR.

Explanation of the columns that may appear on this page:

Level | A few code lists that FHIR defines are hierarchical - each code is assigned a level. See Code System for further information.
Source | The source of the definition of the code (when the value set draws in codes defined elsewhere)
Code | The code (used as the code in the resource instance). If the code is in italics, this indicates that the code is not selectable ('Abstract')
Display | The display (used in the display element of a Coding). If there is no display, implementers should not simply display the code, but map the concept into their application
Definition | An explanation of the meaning of the concept
Comments | Additional notes about how to use the code

4.3.14.103 Code System http://hl7.org/fhir/event-status

URL: https://hl7.org/fhir/R4/codesystem-event-status.html
Patient Care Work Group | Maturity Level: 3 | Trial Use | Use Context: Any

This is a code system defined by the FHIR project.

Summary

Defining URL: | http://hl7.org/fhir/event-status
Version: | 4.0.1
Name: | EventStatus
Title: | EventStatus
Definition: | Codes identifying the lifecycle stage of an event.
Committee: | Patient Care Work Group
OID: | 2.16.840.1.113883.4.642.4.110 (for OID based terminology systems)
Source Resource | XML / JSON

This Code system is used in the following value sets:

• ValueSet: Clinical Impression Status (Codes that reflect the current state of a clinical impression within its overall lifecycle.)

• ValueSet: Immunization Status Codes (The value set to instantiate this attribute should be drawn from a terminologically robust code system that consists of or contains concepts to support describing the current status of the administered dose of vaccine.)

• ValueSet: Immunization Status Codes (The value set to instantiate this attribute should be drawn from a terminologically robust code system that consists of or contains concepts to support describing the current status of the administered dose of vaccine.)

• ValueSet: EventStatus (Codes identifying the lifecycle stage of an event.)

• ValueSet: EventStatus (Codes identifying the lifecycle stage of an event.)

• ValueSet: Clinical Impression Status (Codes that reflect the current state of a clinical impression within its overall lifecycle.)

4.3.14.103.1 Content

4.3.14.103.2 EventStatus

Codes identifying the lifecycle stage of an event.

This code system http://hl7.org/fhir/event-status defines the following codes:

Code | Display | Definition
preparation | Preparation | The core event has not started yet, but some staging activities have begun (e.g. surgical suite preparation). Preparation stages may be tracked for billing purposes.
in-progress | In Progress | The event is currently occurring.
not-done | Not Done | The event was terminated prior to any activity beyond preparation. I.e. The 'main' activity has not yet begun. The boundary between preparatory and the 'main' activity is context-specific.
on-hold | On Hold | The event has been temporarily stopped but is expected to resume in the future.
stopped | Stopped | The event was terminated prior to the full completion of the intended activity but after at least some of the 'main' activity (beyond preparation) has occurred.
completed | Completed | The event has now concluded.
entered-in-error | Entered in Error | This electronic record should never have existed, though it is possible that real-world decisions were based on it. (If real-world activity has occurred, the status should be "stopped" rather than "entered-in-error".).
unknown | Unknown | The authoring/source system does not know which of the status values currently applies for this event. Note: This concept is not to be used for "other" - one of the listed statuses is presumed to apply, but the authoring/source system does not know which.

See the full registry of code systems defined as part of FHIR.

Explanation of the columns that may appear on this page:

Level | A few code lists that FHIR defines are hierarchical - each code is assigned a level. See Code System for further information.
Source | The source of the definition of the code (when the value set draws in codes defined elsewhere)
Code | The code (used as the code in the resource instance). If the code is in italics, this indicates that the code is not selectable ('Abstract')
Display | The display (used in the display element of a Coding). If there is no display, implementers should not simply display the code, but map the concept into their application
Definition | An explanation of the meaning of the concept
Comments | Additional notes about how to use the code

4.3.14.104 Code System http://hl7.org/fhir/device-statement-status

URL: https://hl7.org/fhir/R4/codesystem-device-statement-status.html
Orders and Observations Work Group | Maturity Level: 0 | Trial Use | Use Context: Any

This is a code system defined by the FHIR project.

Summary

Defining URL: | http://hl7.org/fhir/device-statement-status
Version: | 4.0.1
Name: | DeviceUseStatementStatus
Title: | DeviceUseStatementStatus
Definition: | A coded concept indicating the current status of the Device Usage.
Committee: | Orders and Observations Work Group
OID: | 2.16.840.1.113883.4.642.4.215 (for OID based terminology systems)
Source Resource | XML / JSON

This Code system is used in the following value sets:

• ValueSet: DeviceUseStatementStatus (A coded concept indicating the current status of the Device Usage.)
• ValueSet: DeviceUseStatementStatus (A coded concept indicating the current status of the Device Usage.)

4.3.14.104.1 Content

4.3.14.104.2 DeviceUseStatementStatus

A coded concept indicating the current status of the Device Usage.

This code system http://hl7.org/fhir/device-statement-status defines the following codes:

Code | Display | Definition
active | Active | The device is still being used.
completed | Completed | The device is no longer being used.
entered-in-error | Entered in Error | The statement was recorded incorrectly.
intended | Intended | The device may be used at some time in the future.
stopped | Stopped | Actions implied by the statement have been permanently halted, before all of them occurred.
on-hold | On Hold | Actions implied by the statement have been temporarily halted, but are expected to continue later. May also be called "suspended".

See the full registry of code systems defined as part of FHIR.

Explanation of the columns that may appear on this page:

Level | A few code lists that FHIR defines are hierarchical - each code is assigned a level. See Code System for further information.
Source | The source of the definition of the code (when the value set draws in codes defined elsewhere)
Code | The code (used as the code in the resource instance). If the code is in italics, this indicates that the code is not selectable ('Abstract')
Display | The display (used in the display element of a Coding). If there is no display, implementers should not simply display the code, but map the concept into their application
Definition | An explanation of the meaning of the concept

Comments | Additional notes about how to use the code

4.3.14.105 Code System http://hl7.org/fhir/consent-data-meaning

URL: https://hl7.org/fhir/R4/codesystem-consent-data-meaning.html
Community Based Collaborative Care Work Group | Maturity Level: 2 | Trial Use | Use Context: Any

This is a code system defined by the FHIR project.

Summary

Defining URL: | http://hl7.org/fhir/consent-data-meaning
Version: | 4.0.1
Name: | ConsentDataMeaning
Title: | ConsentDataMeaning
Definition: | How a resource reference is interpreted when testing consent restrictions.
Committee: | Community Based Collaborative Care Work Group
OID: | 2.16.840.1.113883.4.642.4.760 (for OID based terminology systems)
Source Resource | XML / JSON

This Code system is used in the following value sets:

• ValueSet: ConsentDataMeaning (How a resource reference is interpreted when testing consent restrictions.)
• ValueSet: ConsentDataMeaning (How a resource reference is interpreted when testing consent restrictions.)

4.3.14.105.1 Content

4.3.14.105.2 ConsentDataMeaning

How a resource reference is interpreted when testing consent restrictions.

This code system http://hl7.org/fhir/consent-data-meaning defines the following codes:

Code | Display | Definition
instance | Instance | The consent applies directly to the instance of the resource.
related | Related | The consent applies directly to the instance of the resource and instances it refers to.
dependents | Dependents | The consent applies directly to the instance of the resource and instances that refer to it.
authoredby | AuthoredBy | The consent applies to instances of resources that are authored by.

See the full registry of code systems defined as part of FHIR.

Explanation of the columns that may appear on this page:

Level | A few code lists that FHIR defines are hierarchical - each code is assigned a level. See Code System for further information.
Source | The source of the definition of the code (when the value set draws in codes defined elsewhere)
Code | The code (used as the code in the resource instance). If the code is in italics, this indicates that the code is not selectable ('Abstract')
Display | The display (used in the display element of a Coding). If there is no display, implementers should not simply display the code, but map the concept into their application
Definition | An explanation of the meaning of the concept
Comments | Additional notes about how to use the code

4.3.14.106 Code System http://terminology.hl7.org/CodeSystem/contracttermtypecodes

URL: https://hl7.org/fhir/R4/codesystem-contract-term-type.html
Financial Management Work Group | Maturity Level: 1 | Draft | Use Context: Any

This is a code system defined by the FHIR project.

Summary

Defining URL: | http://terminology.hl7.org/CodeSystem/contracttermtypecodes
Version: | 4.0.1
Name: | ContractTermTypeCodes
Title: | Contract Term Type Codes
Definition: | This value set includes sample Contract Term Type codes.
Committee: | Financial Management Work Group
OID: | 2.16.840.1.113883.4.642.4.1199 (for OID based terminology systems)
Copyright: | This is an example set.
Source Resource | XML / JSON

This Code system is used in the following value sets:

• ValueSet: Contract Term Type Codes (This value set includes sample Contract Term Type codes.)
• ValueSet: Contract Term Type Codes (This value set includes sample Contract Term Type codes.)

4.3.14.106.1 Content

4.3.14.106.2 Contract Term Type Codes

This value set includes sample Contract Term Type codes.

Copyright Statement:

This is an example set.

This code system http://terminology.hl7.org/CodeSystem/contracttermtypecodes defines the following codes:

Code | Display | Definition
statutory | Statutory | Based on specialized statutes that deal with particular subjects.
subject-to | Subject To | Execution of the term in the contract is conditional on the execution of other actions.

See the full registry of code systems defined as part of FHIR.

Explanation of the columns that may appear on this page:

Level | A few code lists that FHIR defines are hierarchical - each code is assigned a level. See Code System for further information.
Source | The source of the definition of the code (when the value set draws in codes defined elsewhere)
Code | The code (used as the code in the resource instance). If the code is in italics, this indicates that the code is not selectable ('Abstract')
Display | The display (used in the display element of a Coding). If there is no display, implementers should not simply display the code, but map the concept into their application
Definition | An explanation of the meaning of the concept
Comments | Additional notes about how to use the code

4.3.14.107 Code System http://terminology.hl7.org/CodeSystem/supply-kind

URL: https://hl7.org/fhir/R4/codesystem-supplyrequest-kind.html
Orders and Observations Work Group | Maturity Level: 1 | Draft | Use Context: Any

This is a code system defined by the FHIR project.

Summary

Defining URL: | http://terminology.hl7.org/CodeSystem/supply-kind
Version: | 4.0.1
Name: | SupplyType
Title: | Supply Type
Definition: | This value sets refers to a Category of supply.
Committee: | Orders and Observations Work Group
OID: | 2.16.840.1.113883.4.642.4.1192 (for OID based terminology systems)
Source Resource | XML / JSON

This Code system is used in the following value sets:

• ValueSet: Supply Type (This value sets refers to a Category of supply.)

• ValueSet: Supply Type (This value sets refers to a Category of supply.)

4.3.14.107.1 Content

4.3.14.107.2 Supply Type

This value sets refers to a Category of supply.

This code system http://terminology.hl7.org/CodeSystem/supply-kind defines the following codes:

Code | Display | Definition
central | Central Supply | Supply is stored and requested from central supply.
nonstock | Non-Stock | Supply is not onsite and must be requested from an outside vendor using a non-stock requisition.

See the full registry of code systems defined as part of FHIR.

Explanation of the columns that may appear on this page:

Level | A few code lists that FHIR defines are hierarchical - each code is assigned a level. See Code System for further information.
Source | The source of the definition of the code (when the value set draws in codes defined elsewhere)
Code | The code (used as the code in the resource instance). If the code is in italics, this indicates that the code is not selectable ('Abstract')
Display | The display (used in the display element of a Coding). If there is no display, implementers should not simply display the code, but map the concept into their application
Definition | An explanation of the meaning of the concept
Comments | Additional notes about how to use the code

4.3.14.108 Code System http://terminology.hl7.org/CodeSystem/testscript-profile-destination-types

URL: https://hl7.org/fhir/R4/codesystem-testscript-profile-destination-types.html
FHIR Infrastructure Work Group | Maturity Level: 2 | Trial Use | Use Context: Any

This is a code system defined by the FHIR project.

Summary

Defining URL: | http://terminology.hl7.org/CodeSystem/testscript-profile-destination-types
Version: | 4.0.1
Name: | TestScriptProfileDestinationType
Title: | Test script profile destination type
Definition: | This value set defines a set of codes that are used to indicate the profile type of a test system when acting as the destination within a TestScript.
Committee: | FHIR Infrastructure Work Group
OID: | 2.16.840.1.113883.4.642.4.1197 (for OID based terminology systems)
Source Resource | XML / JSON

This Code system is used in the following value sets:

• ValueSet: Test script profile destination type (This value set defines a set of codes that are used to indicate the profile type of a test system when acting as the destination within a TestScript.)

• ValueSet: Test script profile destination type (This value set defines a set of codes that are used to indicate the profile type of a test system when acting as the destination within a TestScript.)

4.3.14.108.1 Content

4.3.14.108.2 Test script profile destination type

This value set defines a set of codes that are used to indicate the profile type of a test system when acting as the destination within a TestScript.

This code system http://terminology.hl7.org/CodeSystem/testscript-profile-destination-types defines the following codes:

Code | Display | Definition
FHIR-Server | FHIR Server | General FHIR server used to respond to operations sent from a FHIR client.
FHIR-SDC-FormManager | FHIR SDC FormManager | A FHIR server acting as a Structured Data Capture Form Manager.
FHIR-SDC-FormProcessor | FHIR SDC FormProcessor | A FHIR server acting as a Structured Data Capture Form Processor.
FHIR-SDC-FormReceiver | FHIR SDC FormReceiver | A FHIR server acting as a Structured Data Capture Form Receiver.

See the full registry of code systems defined as part of FHIR.

Explanation of the columns that may appear on this page:

Level | A few code lists that FHIR defines are hierarchical - each code is assigned a level. See Code System for further information.
Source | The source of the definition of the code (when the value set draws in codes defined elsewhere)
Code | The code (used as the code in the resource instance). If the code is in italics, this indicates that the code is not selectable ('Abstract')
Display | The display (used in the display element of a Coding). If there is no display, implementers should not simply display the code, but map the concept into their application
Definition | An explanation of the meaning of the concept
Comments | Additional notes about how to use the code

4.3.14.109 Code System http://hl7.org/fhir/binding-strength

URL: https://hl7.org/fhir/R4/codesystem-binding-strength.html
FHIR Infrastructure Work Group | Maturity Level: N | Normative (from v4.0.0) | Use Context: Any

| This page has been approved as part of an ANSI standard. See the Conformance Package for further details.

This is a code system defined by the FHIR project.

Summary

Defining URL: | http://hl7.org/fhir/binding-strength
Version: | 4.0.1
Name: | BindingStrength
Title: | BindingStrength
Definition: | Indication of the degree of conformance expectations associated with a binding.
Committee: | FHIR Infrastructure Work Group
OID: | 2.16.840.1.113883.4.642.4.44 (for OID based terminology systems)
Source Resource | XML / JSON

This Code system is used in the following value sets:

• ValueSet: BindingStrength (Indication of the degree of conformance expectations associated with a binding.)

• ValueSet: BindingStrength (Indication of the degree of conformance expectations associated with a binding.)

4.3.14.109.1 Content

4.3.14.109.2 BindingStrength

Indication of the degree of conformance expectations associated with a binding.

This code system http://hl7.org/fhir/binding-strength defines the following codes:

Code | Display | Definition
required | Required | To be conformant, the concept in this element SHALL be from the specified value set.
extensible | Extensible | To be conformant, the concept in this element SHALL be from the specified value set if any of the codes within the value set can apply to the concept being communicated. If the value set does not cover the concept (based on human review), alternate codings (or, data type allowing, text) may be included instead.
preferred | Preferred | Instances are encouraged to draw from the specified codes for interoperability purposes but are not required to do so to be considered conformant.
example | Example | Instances are not expected or even encouraged to draw from the specified value set. The value set merely provides examples of the types of concepts intended to be included.

See the full registry of code systems defined as part of FHIR.

Explanation of the columns that may appear on this page:

Level | A few code lists that FHIR defines are hierarchical - each code is assigned a level. See Code System for further information.
Source | The source of the definition of the code (when the value set draws in codes defined elsewhere)
Code | The code (used as the code in the resource instance). If the code is in italics, this indicates that the code is not selectable ('Abstract')
Display | The display (used in the display element of a Coding). If there is no display, implementers should not simply display the code, but map the concept into their application
Definition | An explanation of the meaning of the concept
Comments | Additional notes about how to use the code

4.3.14.110 Code System http://hl7.org/fhir/property-representation

URL: https://hl7.org/fhir/R4/codesystem-property-representation.html
FHIR Infrastructure Work Group | Maturity Level: N | Normative (from v4.0.0) | Use Context: Any

This is a code system defined by the FHIR project.

Summary

Defining URL: | http://hl7.org/fhir/property-representation
Version: | 4.0.1
Name: | PropertyRepresentation
Title: | PropertyRepresentation
Definition: | How a property is represented when serialized.
Committee: | FHIR Infrastructure Work Group
OID: | 2.16.840.1.113883.4.642.4.88 (for OID based terminology systems)
Source Resource | XML / JSON

This Code system is used in the following value sets:

• ValueSet: PropertyRepresentation (How a property is represented when serialized.)

• ValueSet: PropertyRepresentation (How a property is represented when serialized.)

4.3.14.110.1 Content

4.3.14.110.2 PropertyRepresentation

How a property is represented when serialized.

This code system http://hl7.org/fhir/property-representation defines the following codes:

Code | Display | Definition
xmlAttr | XML Attribute | In XML, this property is represented as an attribute not an element.
xmlText | XML Text | This element is represented using the XML text attribute (primitives only).
typeAttr | Type Attribute | The type of this element is indicated using xsi:type.
cdaText | CDA Text Format | Use CDA narrative instead of XHTML.
xhtml | XHTML | The property is represented using XHTML.

See the full registry of code systems defined as part of FHIR.

Explanation of the columns that may appear on this page:

Level | A few code lists that FHIR defines are hierarchical - each code is assigned a level. See Code System for further information.
Source | The source of the definition of the code (when the value set draws in codes defined elsewhere)
Code | The code (used as the code in the resource instance). If the code is in italics, this indicates that the code is not selectable ('Abstract')
Display | The display (used in the display element of a Coding). If there is no display, implementers should not simply display the code, but map the concept into their application
Definition | An explanation of the meaning of the concept
Comments | Additional notes about how to use the code

4.3.14.111 Code System http://terminology.hl7.org/CodeSystem/medication-statement-category

URL: https://hl7.org/fhir/R4/codesystem-medication-statement-category.html
Pharmacy Work Group | Maturity Level: 0 | Informative | Use Context: Any

This is a code system defined by the FHIR project.

Summary

Defining URL: | http://terminology.hl7.org/CodeSystem/medication-statement-category
Version: | 4.0.1
Name: | Medication usage category codes
Title: | Medication usage category codes
Definition: | Medication Status Codes
Committee: | Pharmacy Work Group
OID: | 2.16.840.1.113883.4.642.4.1120 (for OID based terminology systems)
Source Resource | XML / JSON

This Code system is used in the following value sets:

• ValueSet: Medication usage category codes (Medication Status Codes)

• ValueSet: Medication usage category codes (Medication Status Codes)

4.3.14.111.1 Content

4.3.14.111.2 Medication usage category codes

Medication Status Codes

This code system http://terminology.hl7.org/CodeSystem/medication-statement-category defines the following codes:

Code | Display | Definition
inpatient | Inpatient | Includes orders for medications to be administered or consumed in an inpatient or acute care setting
outpatient | Outpatient | Includes orders for medications to be administered or consumed in an outpatient setting (for example, Emergency Department, Outpatient Clinic, Outpatient Surgery, Doctor's office)
community | Community | Includes orders for medications to be administered or consumed by the patient in their home (this would include long term care or nursing homes, hospices, etc.).
patientspecified | Patient Specified | Includes statements about medication use, including over the counter medication, provided by the patient, agent or another provider

See the full registry of code systems defined as part of FHIR.

Explanation of the columns that may appear on this page:

Level | A few code lists that FHIR defines are hierarchical - each code is assigned a level. See Code System for further information.
Source | The source of the definition of the code (when the value set draws in codes defined elsewhere)
Code | The code (used as the code in the resource instance). If the code is in italics, this indicates that the code is not selectable ('Abstract')
Display | The display (used in the display element of a Coding). If there is no display, implementers should not simply display the code, but map the concept into their application
Definition | An explanation of the meaning of the concept
Comments | Additional notes about how to use the code

4.3.14.112 Code System http://hl7.org/fhir/namingsystem-identifier-type

URL: https://hl7.org/fhir/R4/codesystem-namingsystem-identifier-type.html
FHIR Infrastructure Work Group | Maturity Level: 1 | Trial Use | Use Context: Any

This is a code system defined by the FHIR project.

Summary

Defining URL: | http://hl7.org/fhir/namingsystem-identifier-type
Version: | 4.0.1
Name: | NamingSystemIdentifierType
Title: | NamingSystemIdentifierType
Definition: | Identifies the style of unique identifier used to identify a namespace.
Committee: | FHIR Infrastructure Work Group
OID: | 2.16.840.1.113883.4.642.4.493 (for OID based terminology systems)
Source Resource | XML / JSON

This Code system is used in the following value sets:

• ValueSet: NamingSystemIdentifierType (Identifies the style of unique identifier used to identify a namespace.)

• ValueSet: NamingSystemIdentifierType (Identifies the style of unique identifier used to identify a namespace.)

4.3.14.112.1 Content

4.3.14.112.2 NamingSystemIdentifierType

Identifies the style of unique identifier used to identify a namespace.

This code system http://hl7.org/fhir/namingsystem-identifier-type defines the following codes:

Code | Display | Definition
oid | OID | An ISO object identifier; e.g. 1.2.3.4.5.
uuid | UUID | A universally unique identifier of the form a5afddf4-e880-459b-876e-e4591b0acc11.
uri | URI | A uniform resource identifier (ideally a URL - uniform resource locator); e.g. http://unitsofmeasure.org.
other | Other | Some other type of unique identifier; e.g. HL7-assigned reserved string such as LN for LOINC.

See the full registry of code systems defined as part of FHIR.

Explanation of the columns that may appear on this page:

Level | A few code lists that FHIR defines are hierarchical - each code is assigned a level. See Code System for further information.
Source | The source of the definition of the code (when the value set draws in codes defined elsewhere)
Code | The code (used as the code in the resource instance). If the code is in italics, this indicates that the code is not selectable ('Abstract')
Display | The display (used in the display element of a Coding). If there is no display, implementers should not simply display the code, but map the concept into their application
Definition | An explanation of the meaning of the concept
Comments | Additional notes about how to use the code

4.3.14.113 Code System http://terminology.hl7.org/fhir/CodeSystem/medicationdispense-status-reason

URL: https://hl7.org/fhir/R4/codesystem-medicationdispense-status-reason.html
Pharmacy Work Group | Maturity Level: 1 | Draft | Use Context: Any

This is a code system defined by the FHIR project.

Summary

Defining URL: | http://terminology.hl7.org/fhir/CodeSystem/medicationdispense-status-reason
Version: | 4.0.1
Name: | MedicationDispense Status Reason Codes
Title: | Medication dispense status reason codes
Definition: | MedicationDispense Status Codes
Committee: | Pharmacy Work Group
OID: | 2.16.840.1.113883.4.642.4.1317 (for OID based terminology systems)
Source Resource | XML / JSON

This Code system is used in the following value sets:

• ValueSet: Medication dispense status reason codes (MedicationDispense Status Codes)
• ValueSet: Medication dispense status reason codes (MedicationDispense Status Codes)

4.3.14.113.1 Content

4.3.14.113.2 Medication dispense status reason codes

MedicationDispense Status Codes

This code system http://terminology.hl7.org/fhir/CodeSystem/medicationdispense-status-reason defines the following codes:

Code | Display | Definition
frr01 | Order Stopped | The order has been stopped by the prescriber but this fact has not necessarily captured electronically. Example: A verbal stop, a fax, etc.
frr02 | Stale-dated Order | Order has not been fulfilled within a reasonable amount of time, and might not be current.
frr03 | Incomplete data | Data needed to safely act on the order which was expected to become available independent of the order is not yet available. Example: Lab results, diagnostic imaging, etc.
frr04 | Product unavailable | Product not available or manufactured. Cannot supply.
frr05 | Ethical/religious | The dispenser has ethical, religious or moral objections to fulfilling the order/dispensing the product.
frr06 | Unable to provide care | Fulfiller not able to provide appropriate care associated with fulfilling the order. Example: Therapy requires ongoing monitoring by fulfiller and fulfiller will be ending practice, leaving town, unable to schedule necessary time, etc.
altchoice | Try another treatment first | This therapy has been ordered as a backup to a preferred therapy. This order will be released when and if the preferred therapy is unsuccessful.
clarif | Prescription/Request requires clarification | Clarification is required before the order can be acted upon.
drughigh | Drug level too high | The current level of the medication in the patient's system is too high. The medication is suspended to allow the level to subside to a safer level.
hospadm | Admission to hospital | The patient has been admitted to a care facility and their community medications are suspended until hospital discharge.
labint | Lab interference issues | The therapy would interfere with a planned lab test and the therapy is being withdrawn until the test is completed.

non-avail | Patient not available | Patient not available for a period of time due to a scheduled therapy, leave of absence or other reason.
preg | Patient is pregnant or breastfeeding | The patient is pregnant or breast feeding. The therapy will be resumed when the pregnancy is complete and the patient is no longer breastfeeding.
saig | Allergy | The patient is believed to be allergic to a substance that is part of the therapy and the therapy is being temporarily withdrawn to confirm.
sddi | Drug interacts with another drug | The drug interacts with a short-term treatment that is more urgently required. This order will be resumed when the short-term treatment is complete.
sdupther | Duplicate therapy | Another short-term co-occurring therapy fulfills the same purpose as this therapy. This therapy will be resumed when the co-occuring therapy is complete.
sintol | Suspected intolerance | The patient is believed to have an intolerance to a substance that is part of the therapy and the therapy is being temporarily withdrawn to confirm.
surg | Patient scheduled for surgery | The drug is contraindicated for patients receiving surgery and the patient is scheduled to be admitted for surgery in the near future. The drug will be resumed when the patient has sufficiently recovered from the surgery.
washout | Washout | The patient was previously receiving a medication contraindicated with the current medication. The current medication will remain on hold until the prior medication has been cleansed from their system.
outofstock | Drug not available - out of stock | Drug out of stock. Cannot supply.
offmarket | Drug not available - off market | Drug no longer marketed Cannot supply.

See the full registry of code systems defined as part of FHIR.

Explanation of the columns that may appear on this page:

Level | A few code lists that FHIR defines are hierarchical - each code is assigned a level. See Code System for further information.
Source | The source of the definition of the code (when the value set draws in codes defined elsewhere)
Code | The code (used as the code in the resource instance). If the code is in italics, this indicates that the code is not selectable ('Abstract')
Display | The display (used in the display element of a Coding). If there is no display, implementers should not simply display the code, but map the concept into their application
Definition | An explanation of the meaning of the concept
Comments | Additional notes about how to use the code

4.3.14.114 Code System http://terminology.hl7.org/CodeSystem/measure-type

URL: https://hl7.org/fhir/R4/codesystem-measure-type.html
Clinical Quality Information Work Group | Maturity Level: 2 | Trial Use | Use Context: Any

This is a code system defined by the FHIR project.

Summary

Defining URL: | http://terminology.hl7.org/CodeSystem/measure-type
Version: | 4.0.1
Name: | MeasureType
Title: | MeasureType
Definition: | The type of measure (includes codes from 2.16.840.1.113883.1.11.20368).
Committee: | Clinical Quality Information Work Group
OID: | 2.16.840.1.113883.4.642.4.1233 (for OID based terminology systems)
Source Resource | XML / JSON

This Code system is used in the following value sets:

• ValueSet: MeasureType (The type of measure (includes codes from 2.16.840.1.113883.1.11.20368).)
• ValueSet: MeasureType (The type of measure (includes codes from 2.16.840.1.113883.1.11.20368).)

4.3.14.114.1 Content

4.3.14.114.2 MeasureType

The type of measure (includes codes from 2.16.840.1.113883.1.11.20368).

This code system http://terminology.hl7.org/CodeSystem/measure-type defines the following codes:

Code | Display | Definition
process | Process | A measure which focuses on a process which leads to a certain outcome, meaning that a scientific basis exists for believing that the process, when executed well, will increase the probability of achieving a desired outcome.
outcome | Outcome | A measure that indicates the result of the performance (or non-performance) of a function or process.
structure | Structure | A measure that focuses on a health care provider's capacity, systems, and processes to provide high-quality care.
patient-reported-outcome | Patient Reported Outcome | A measure that focuses on patient-reported information such as patient engagement or patient experience measures.
composite | Composite | A measure that combines multiple component measures in to a single quality measure.

See the full registry of code systems defined as part of FHIR.

Explanation of the columns that may appear on this page:

Level | A few code lists that FHIR defines are hierarchical - each code is assigned a level. See Code System for further information.
Source | The source of the definition of the code (when the value set draws in codes defined elsewhere)

Code | The code (used as the code in the resource instance). If the code is in italics, this indicates that the code is not selectable ('Abstract')
Display | The display (used in the display element of a Coding). If there is no display, implementers should not simply display the code, but map the concept into their application
Definition | An explanation of the meaning of the concept
Comments | Additional notes about how to use the code

4.3.14.115 Code System http://hl7.org/fhir/composition-attestation-mode

URL: https://hl7.org/fhir/R4/codesystem-composition-attestation-mode.html
Structured Documents Work Group | Maturity Level: 2 | Trial Use | Use Context: Any

This is a code system defined by the FHIR project.

Summary

Defining URL: | http://hl7.org/fhir/composition-attestation-mode
Version: | 4.0.1
Name: | CompositionAttestationMode
Title: | CompositionAttestationMode
Definition: | The way in which a person authenticated a composition.
Committee: | Structured Documents Work Group
OID: | 2.16.840.1.113883.4.642.4.239 (for OID based terminology systems)
Source Resource | XML / JSON

This Code system is used in the following value sets:

• ValueSet: CompositionAttestationMode (The way in which a person authenticated a composition.)
• ValueSet: CompositionAttestationMode (The way in which a person authenticated a composition.)

4.3.14.115.1 Content

4.3.14.115.2 CompositionAttestationMode

The way in which a person authenticated a composition.

This code system http://hl7.org/fhir/composition-attestation-mode defines the following codes:

Code | Display | Definition
personal | Personal | The person authenticated the content in their personal capacity.
professional | Professional | The person authenticated the content in their professional capacity.
legal | Legal | The person authenticated the content and accepted legal responsibility for its content.
official | Official | The organization authenticated the content as consistent with their policies and procedures.

See the full registry of code systems defined as part of FHIR.

Explanation of the columns that may appear on this page:

Level | A few code lists that FHIR defines are hierarchical - each code is assigned a level. See Code System for further information.
Source | The source of the definition of the code (when the value set draws in codes defined elsewhere)
Code | The code (used as the code in the resource instance). If the code is in italics, this indicates that the code is not selectable ('Abstract')
Display | The display (used in the display element of a Coding). If there is no display, implementers should not simply display the code, but map the concept into their application
Definition | An explanation of the meaning of the concept
Comments | Additional notes about how to use the code

4.3.14.116 Code System http://terminology.hl7.org/CodeSystem/condition-ver-status

URL: https://hl7.org/fhir/R4/codesystem-condition-ver-status.html
Patient Care Work Group | Maturity Level: 3 | Trial Use | Use Context: Any

This is a code system defined by the FHIR project.

Summary

Defining URL: | http://terminology.hl7.org/CodeSystem/condition-ver-status
Version: | 4.0.1
Name: | ConditionVerificationStatus
Title: | ConditionVerificationStatus
Definition: | The verification status to support or decline the clinical status of the condition or diagnosis.
Committee: | Patient Care Work Group
OID: | 2.16.840.1.113883.4.642.4.1075 (for OID based terminology systems)
Source Resource | XML / JSON

This Code system is used in the following value sets:

• ValueSet: ConditionVerificationStatus (The verification status to support or decline the clinical status of the condition or diagnosis.)

• ValueSet: ConditionVerificationStatus (The verification status to support or decline the clinical status of the condition or diagnosis.)

4.3.14.116.1 Content

4.3.14.116.2 ConditionVerificationStatus

The verification status to support or decline the clinical status of the condition or diagnosis.

This code system http://terminology.hl7.org/CodeSystem/condition-ver-status defines the following codes:

Lvl | Code | Display | Definition
1 | unconfirmed | Unconfirmed | There is not sufficient diagnostic and/or clinical evidence to treat this as a confirmed condition.
2 | provisional | Provisional | This is a tentative diagnosis - still a candidate that is under consideration.
2 | differential | Differential | One of a set of potential (and typically mutually exclusive) diagnoses asserted to further guide the diagnostic process and preliminary treatment.
1 | confirmed | Confirmed | There is sufficient diagnostic and/or clinical evidence to treat this as a confirmed condition.
1 | refuted | Refuted | This condition has been ruled out by diagnostic and clinical evidence.
1 | entered-in-error | Entered in Error | The statement was entered in error and is not valid.

See the full registry of code systems defined as part of FHIR.

Explanation of the columns that may appear on this page:

Level | A few code lists that FHIR defines are hierarchical - each code is assigned a level. See Code System for further information.
Source | The source of the definition of the code (when the value set draws in codes defined elsewhere)
Code | The code (used as the code in the resource instance). If the code is in italics, this indicates that the code is not selectable ('Abstract')
Display | The display (used in the display element of a Coding). If there is no display, implementers should not simply display the code, but map the concept into their application
Definition | An explanation of the meaning of the concept
Comments | Additional notes about how to use the code

4.3.14.117 Code System http://terminology.hl7.org/CodeSystem/reason-medication-given

URL: https://hl7.org/fhir/R4/codesystem-reason-medication-given-codes.html
Pharmacy Work Group | Maturity Level: 1 | Draft | Use Context: Any

This is a code system defined by the FHIR project.

Summary

Defining URL: | http://terminology.hl7.org/CodeSystem/reason-medication-given
Version: | 4.0.1
Name: | ReasonMedicationGivenCodes
Title: | Reason Medication Given Codes
Definition: | This value set is provided as an example. The value set to instantiate this attribute should be drawn from a robust terminology code system that consists of or contains concepts to support the medication process.
Committee: | Pharmacy Work Group
OID: | 2.16.840.1.113883.4.642.4.1110 (for OID based terminology systems)
Source Resource | XML / JSON

This Code system is used in the following value sets:

• ValueSet: Reason Medication Given Codes (This value set is provided as an example. The value set to instantiate this attribute should be drawn from a robust terminology code system that consists of or contains concepts to support the medication process.)

• ValueSet: Reason Medication Given Codes (This value set is provided as an example. The value set to instantiate this attribute should be drawn from a robust terminology code system that consists of or contains concepts to support the medication process.)

4.3.14.117.1 Content

4.3.14.117.2 Reason Medication Given Codes

This value set is provided as an example. The value set to instantiate this attribute should be drawn from a robust terminology code system that consists of or contains concepts to support the medication process.

This code system http://terminology.hl7.org/CodeSystem/reason-medication-given defines the following codes:

Code | Display | Definition
a | None | No reason known.
b | Given as Ordered | The administration was following an ordered protocol.
c | Emergency | The administration was needed to treat an emergency.

See the full registry of code systems defined as part of FHIR.

Explanation of the columns that may appear on this page:

Level | A few code lists that FHIR defines are hierarchical - each code is assigned a level. See Code System for further information.
Source | The source of the definition of the code (when the value set draws in codes defined elsewhere)
Code | The code (used as the code in the resource instance). If the code is in italics, this indicates that the code is not selectable ('Abstract')
Display | The display (used in the display element of a Coding). If there is no display, implementers should not simply display the code, but map the concept into their application
Definition | An explanation of the meaning of the concept
Comments | Additional notes about how to use the code

4.3.14.118 Code System http://terminology.hl7.org/CodeSystem/medicationdispense-status

URL: https://hl7.org/fhir/R4/codesystem-medicationdispense-status.html
Pharmacy Work Group | Maturity Level: 2 | Trial Use | Use Context: Any

This is a code system defined by the FHIR project.

Summary

Defining URL: | http://terminology.hl7.org/CodeSystem/medicationdispense-status
Version: | 4.0.1
Name: | MedicationDispense Status Codes
Title: | Medication dispense status codes
Definition: | MedicationDispense Status Codes
Committee: | Pharmacy Work Group
OID: | 2.16.840.1.113883.4.642.4.1313 (for OID based terminology systems)
Source Resource | XML / JSON

This Code system is used in the following value sets:

• ValueSet: Medication dispense status codes (MedicationDispense Status Codes)

• ValueSet: Medication dispense status codes (MedicationDispense Status Codes)

4.3.14.118.1 Content

4.3.14.118.2 Medication dispense status codes

MedicationDispense Status Codes

This code system http://terminology.hl7.org/CodeSystem/medicationdispense-status defines the following codes:

Code | Display | Definition
preparation | Preparation | The core event has not started yet, but some staging activities have begun (e.g. initial compounding or packaging of medication). Preparation stages may be tracked for billing purposes.
in-progress | In Progress | The dispensed product is ready for pickup.
cancelled | Cancelled | The dispensed product was not and will never be picked up by the patient.
on-hold | On Hold | The dispense process is paused while waiting for an external event to reactivate the dispense. For example, new stock has arrived or the prescriber has called.
completed | Completed | The dispensed product has been picked up.
entered-in-error | Entered in Error | The dispense was entered in error and therefore nullified.
stopped | Stopped | Actions implied by the dispense have been permanently halted, before all of them occurred.
declined | Declined | The dispense was declined and not performed.
unknown | Unknown | The authoring system does not know which of the status values applies for this medication dispense. Note: this concept is not to be used for other - one of the listed statuses is presumed to apply, it's just now known which one.

See the full registry of code systems defined as part of FHIR.

Explanation of the columns that may appear on this page:

Level | A few code lists that FHIR defines are hierarchical - each code is assigned a level. See Code System for further information.
Source | The source of the definition of the code (when the value set draws in codes defined elsewhere)
Code | The code (used as the code in the resource instance). If the code is in italics, this indicates that the code is not selectable ('Abstract')
Display | The display (used in the display element of a Coding). If there is no display, implementers should not simply display the code, but map the concept into their application
Definition | An explanation of the meaning of the concept
Comments | Additional notes about how to use the code

4.3.14.119 Code System http://terminology.hl7.org/CodeSystem/applicability

URL: https://hl7.org/fhir/R4/codesystem-insuranceplan-applicability.html
Patient Administration Work Group | Maturity Level: 0 | Trial Use | Use Context: Any

This is a code system defined by the FHIR project.

Summary

Defining URL: | http://terminology.hl7.org/CodeSystem/applicability
Version: | 4.0.1
Name: | BenefitCostApplicability
Title: | Benefit cost applicability
Definition: | Whether the cost applies to in-network or out-of-network providers.
Committee: | Patient Administration Work Group
OID: | 2.16.840.1.113883.4.642.1.0 (for OID based terminology systems)
Source Resource | XML / JSON

This Code system is used in the following value sets:

• ValueSet: Benefit cost applicability (Whether the cost applies to in-network or out-of-network providers.)

• ValueSet: Benefit cost applicability (Whether the cost applies to in-network or out-of-network providers.)

4.3.14.119.1 Content

4.3.14.119.2 Benefit cost applicability

Whether the cost applies to in-network or out-of-network providers.

This code system http://terminology.hl7.org/CodeSystem/applicability defines the following codes:

Code | Display | Definition
in-network | In Network | Provider is contracted with the health insurance company to provide services to plan members for specific pre-negotiated rates
out-of-network | Out of Network | Provider is not contracted with the health insurance company to provide services to plan members for specific pre-negotiated rates
other | Other | Other applicability

See the full registry of code systems defined as part of FHIR.

Explanation of the columns that may appear on this page:

Level | A few code lists that FHIR defines are hierarchical - each code is assigned a level. See Code System for further information.
Source | The source of the definition of the code (when the value set draws in codes defined elsewhere)
Code | The code (used as the code in the resource instance). If the code is in italics, this indicates that the code is not selectable ('Abstract')
Display | The display (used in the display element of a Coding). If there is no display, implementers should not simply display the code, but map the concept into their application
Definition | An explanation of the meaning of the concept
Comments | Additional notes about how to use the code

4.3.14.120 Code System http://terminology.hl7.org/CodeSystem/consentscope

URL: https://hl7.org/fhir/R4/codesystem-consent-scope.html
Community Based Collaborative Care Work Group | Maturity Level: 2 | Trial Use | Use Context: Any

This is a code system defined by the FHIR project.

Summary

Defining URL: | http://terminology.hl7.org/CodeSystem/consentscope
Version: | 4.0.1
Name: | ConsentScopeCodes
Title: | Consent Scope Codes
Definition: | This value set includes the four Consent scope codes.
Committee: | Community Based Collaborative Care Work Group
OID: | 2.16.840.1.113883.4.642.4.1228 (for OID based terminology systems)
Copyright: | This is an example set.
Source Resource | XML / JSON

This Code system is used in the following value sets:

• ValueSet: Consent Scope Codes (This value set includes the four Consent scope codes.)

• ValueSet: Consent Scope Codes (This value set includes the four Consent scope codes.)

4.3.14.120.1 Content

4.3.14.120.2 Consent Scope Codes

This value set includes the four Consent scope codes.

Copyright Statement:

This is an example set.

This code system http://terminology.hl7.org/CodeSystem/consentscope defines the following codes:

Code | Display | Definition
adr | Advanced Care Directive | Actions to be taken if they are no longer able to make decisions for themselves
research | Research | Consent to participate in research protocol and information sharing required
patient-privacy | Privacy Consent | Agreement to collect, access, use or disclose (share) information
treatment | Treatment | Consent to undergo a specific treatment

See the full registry of code systems defined as part of FHIR.

Explanation of the columns that may appear on this page:

Level | A few code lists that FHIR defines are hierarchical - each code is assigned a level. See Code System for further information.
Source | The source of the definition of the code (when the value set draws in codes defined elsewhere)
Code | The code (used as the code in the resource instance). If the code is in italics, this indicates that the code is not selectable ('Abstract')
Display | The display (used in the display element of a Coding). If there is no display, implementers should not simply display the code, but map the concept into their application
Definition | An explanation of the meaning of the concept
Comments | Additional notes about how to use the code

4.3.14.121 Code System http://terminology.hl7.org/CodeSystem/adverse-event-category

URL: https://hl7.org/fhir/R4/codesystem-adverse-event-category.html
Patient Care Work Group | Maturity Level: 0 | Trial Use | Use Context: Any

This is a code system defined by the FHIR project.

Summary

Defining URL: | http://terminology.hl7.org/CodeSystem/adverse-event-category
Version: | 4.0.1
Name: | AdverseEventCategory
Title: | AdverseEventCategory
Definition: | Overall categorization of the event, e.g. product-related or situational.
Committee: | Patient Care Work Group
OID: | 2.16.840.1.113883.4.642.4.1251 (for OID based terminology systems)
Source Resource | XML / JSON

This Code system is used in the following value sets:

• ValueSet: AdverseEventCategory (Overall categorization of the event, e.g. product-related or situational.)
• ValueSet: AdverseEventCategory (Overall categorization of the event, e.g. product-related or situational.)

4.3.14.121.1 Content

4.3.14.121.2 AdverseEventCategory

Overall categorization of the event, e.g. product-related or situational.

This code system http://terminology.hl7.org/CodeSystem/adverse-event-category defines the following codes:

Lvl | Code | Display | Definition
1 | product-problem | Product Problem | The adverse event pertains to a product problem.
1 | product-quality | Product Quality | The adverse event pertains to product quality.
1 | product-use-error | Product Use Error | The adverse event pertains to a product use error.
2 | wrong-dose | Wrong Dose | The adverse event pertains to a wrong dose.
2 | incorrect-prescribing-information | Incorrect Prescribing Information | The adverse event pertains to incorrect perscribing information.
2 | wrong-technique | Wrong Technique | The adverse event pertains to a wrong technique.
2 | wrong-route-of-administration | Wrong Route of Administration | The adverse event pertains to a wrong route of administration.
2 | wrong-rate | Wrong Rate | The adverse event pertains to a wrong rate.
2 | wrong-duration | Wrong Duration | The adverse event pertains to a wrong duration.
2 | wrong-time | Wrong Time | The adverse event pertains to a wrong time.
2 | expired-drug | Expired Drug | The adverse event pertains to an expired drug.
1 | medical-device-use-error | Medical Device Use Error | The adverse event pertains to a medical device use error.
1 | problem-different-manufacturer | Problem with Different Manufacturer of Same Medicine | The adverse event pertains to a problem with a different manufacturer of the same medication.
1 | unsafe-physical-environment | Unsafe Physical Environment | The adverse event pertains to an unsafe physical environment.

See the full registry of code systems defined as part of FHIR.

Explanation of the columns that may appear on this page:

Level | A few code lists that FHIR defines are hierarchical - each code is assigned a level. See Code System for further information.
Source | The source of the definition of the code (when the value set draws in codes defined elsewhere)
Code | The code (used as the code in the resource instance). If the code is in italics, this indicates that the code is not selectable ('Abstract')
Display | The display (used in the display element of a Coding). If there is no display, implementers should not simply display the code, but map the concept into their application
Definition | An explanation of the meaning of the concept

Comments | Additional notes about how to use the code

4.3.14.122 Code System http://hl7.org/fhir/consentperformer

URL: https://hl7.org/fhir/R4/codesystem-consent-performer.html
Vocabulary Work Group | Maturity Level: 0 | Informative | Use Context: Any

This is a code system defined by the FHIR project.

Summary

Defining URL: | http://hl7.org/fhir/consentperformer
Version: | 4.0.1
Name: | PerformerRoleCodes
Title: | Performer Role Codes
Definition: | This value set includes sample Performer Role codes.
Committee: | ??
OID: | 2.16.840.1.113883.4.642.4.1017 (for OID based terminology systems)
Copyright: | This is an example set.
Source Resource | XML / JSON

This Code system is used in the following value sets:

• ValueSet: Performer Role Codes (This value set includes sample Performer Role codes.)

• ValueSet: Performer Role Codes (This value set includes sample Performer Role codes.)

4.3.14.122.1 Content

4.3.14.122.2 Performer Role Codes

This value set includes sample Performer Role codes.

Copyright Statement:

This is an example set.

This code system http://hl7.org/fhir/consentperformer defines the following codes:

Code | Display | Definition
consenter | Consenter | An entity or an entity's delegatee who is the grantee in an agreement such as a consent for services, advanced directive, or a privacy consent directive in accordance with jurisdictional, organizational, or patient policy.
grantee | Grantee | An entity which accepts certain rights or authority from a grantor.
grantor | Grantor | An entity which agrees to confer certain rights or authority to a grantee.
delegatee | Delegatee | A party to whom some right or authority is granted by a delegator.
delegator | Delegator | A party that grants all or some portion its right or authority to another party.

See the full registry of code systems defined as part of FHIR.

Explanation of the columns that may appear on this page:

Level | A few code lists that FHIR defines are hierarchical - each code is assigned a level. See Code System for further information.
Source | The source of the definition of the code (when the value set draws in codes defined elsewhere)
Code | The code (used as the code in the resource instance). If the code is in italics, this indicates that the code is not selectable ('Abstract')
Display | The display (used in the display element of a Coding). If there is no display, implementers should not simply display the code, but map the concept into their application
Definition | An explanation of the meaning of the concept
Comments | Additional notes about how to use the code

4.3.14.123 Code System http://hl7.org/fhir/fm-status

URL: https://hl7.org/fhir/R4/codesystem-fm-status.html
Financial Management Work Group | Maturity Level: 2 | Trial Use | Use Context: Any

This is a code system defined by the FHIR project.

Summary

Defining URL: | http://hl7.org/fhir/fm-status
Version: | 4.0.1
Name: | FinancialResourceStatusCodes
Title: | Financial Resource Status Codes
Definition: | This value set includes Status codes.
Committee: | Financial Management Work Group
OID: | 2.16.840.1.113883.4.642.4.593 (for OID based terminology systems)
Copyright: | HL7 International.
Source Resource | XML / JSON

This Code system is used in the following value sets:

• ValueSet: Financial Resource Status Codes (This value set includes Status codes.)

• ValueSet: Financial Resource Status Codes (This value set includes Status codes.)

4.3.14.123.1 Content

4.3.14.123.2 Financial Resource Status Codes

This value set includes Status codes.

Copyright Statement:

HL7 International.

This code system http://hl7.org/fhir/fm-status defines the following codes:

Code | Display | Definition
active | Active | The instance is currently in-force.
cancelled | Cancelled | The instance is withdrawn, rescinded or reversed.
draft | Draft | A new instance the contents of which is not complete.
entered-in-error | Entered in Error | The instance was entered in error.

See the full registry of code systems defined as part of FHIR.

Explanation of the columns that may appear on this page:

Level | A few code lists that FHIR defines are hierarchical - each code is assigned a level. See Code System for further information.
Source | The source of the definition of the code (when the value set draws in codes defined elsewhere)
Code | The code (used as the code in the resource instance). If the code is in italics, this indicates that the code is not selectable ('Abstract')
Display | The display (used in the display element of a Coding). If there is no display, implementers should not simply display the code, but map the concept into their application
Definition | An explanation of the meaning of the concept
Comments | Additional notes about how to use the code

4.3.14.124 Code System http://hl7.org/fhir/request-priority

URL: https://hl7.org/fhir/R4/codesystem-request-priority.html
Vocabulary Work Group | Maturity Level: 0 | Informative | Use Context: Any

This is a code system defined by the FHIR project.

Summary

Defining URL: | http://hl7.org/fhir/request-priority
Version: | 4.0.1
Name: | RequestPriority
Title: | RequestPriority
Definition: | Identifies the level of importance to be assigned to actioning the request.
Committee: | ??
OID: | 2.16.840.1.113883.4.642.4.116 (for OID based terminology systems)
Source Resource | XML / JSON

This Code system is used in the following value sets:

• ValueSet: Request priority (The clinical priority of a diagnostic order.)

• ValueSet: Request priority (The clinical priority of a diagnostic order.)

4.3.14.124.1 Content

4.3.14.124.2 RequestPriority

Identifies the level of importance to be assigned to actioning the request.

This code system http://hl7.org/fhir/request-priority defines the following codes:

Code | Display | Definition
routine | Routine | The request has normal priority.
urgent | Urgent | The request should be actioned promptly - higher priority than routine.
asap | ASAP | The request should be actioned as soon as possible - higher priority than urgent.
stat | STAT | The request should be actioned immediately - highest possible priority. E.g. an emergency.

See the full registry of code systems defined as part of FHIR.

Explanation of the columns that may appear on this page:

Level | A few code lists that FHIR defines are hierarchical - each code is assigned a level. See Code System for further information.
Source | The source of the definition of the code (when the value set draws in codes defined elsewhere)
Code | The code (used as the code in the resource instance). If the code is in italics, this indicates that the code is not selectable ('Abstract')
Display | The display (used in the display element of a Coding). If there is no display, implementers should not simply display the code, but map the concept into their application
Definition | An explanation of the meaning of the concept
Comments | Additional notes about how to use the code

4.3.14.125 Code System http://terminology.hl7.org/CodeSystem/ex-coverage-financial-exception

URL: https://hl7.org/fhir/R4/codesystem-coverage-financial-exception.html
Financial Management Work Group | Maturity Level: 1 | Draft | Use Context: Any

This is a code system defined by the FHIR project.

Summary

Defining URL: | http://terminology.hl7.org/CodeSystem/ex-coverage-financial-exception
Version: | 4.0.1
Name: | ExampleCoverageFinancialExceptionCodes
Title: | Example Coverage Financial Exception Codes
Definition: | This value set includes Example Coverage Financial Exception Codes.
Committee: | Financial Management Work Group
OID: | 2.16.840.1.113883.4.642.4.1329 (for OID based terminology systems)
Copyright: | This is an example set.
Source Resource | XML / JSON

This Code system is used in the following value sets:

• ValueSet: Example Coverage Financial Exception Codes (This value set includes Example Coverage Financial Exception Codes.)

• ValueSet: Example Coverage Financial Exception Codes (This value set includes Example Coverage Financial Exception Codes.)

4.3.14.125.1 Content

4.3.14.125.2 Example Coverage Financial Exception Codes

This value set includes Example Coverage Financial Exception Codes.

Copyright Statement:

This is an example set.

This code system http://terminology.hl7.org/CodeSystem/ex-coverage-financial-exception defines the following codes:

Code | Display | Definition
retired | Retired | Retired persons have all copays and deductibles reduced.
foster | Foster child | Children in the foster care have all copays and deductibles waived.

See the full registry of code systems defined as part of FHIR.

Explanation of the columns that may appear on this page:

Level | A few code lists that FHIR defines are hierarchical - each code is assigned a level. See Code System for further information.
Source | The source of the definition of the code (when the value set draws in codes defined elsewhere)
Code | The code (used as the code in the resource instance). If the code is in italics, this indicates that the code is not selectable ('Abstract')
Display | The display (used in the display element of a Coding). If there is no display, implementers should not simply display the code, but map the concept into their application
Definition | An explanation of the meaning of the concept
Comments | Additional notes about how to use the code

4.3.14.126 Code System http://terminology.hl7.org/CodeSystem/ex-tooth

URL: https://hl7.org/fhir/R4/codesystem-tooth.html
Financial Management Work Group | Maturity Level: 1 | Draft | Use Context: Any

This is a code system defined by the FHIR project.

Summary

Defining URL: | http://terminology.hl7.org/CodeSystem/ex-tooth
Version: | 4.0.1
Name: | OralSiteCodes
Title: | Oral Site Codes
Definition: | This value set includes a smattering of FDI oral site codes.
Committee: | Financial Management Work Group
OID: | 2.16.840.1.113883.4.642.4.1152 (for OID based terminology systems)
Copyright: | This is an example set.
Source Resource | XML / JSON

This Code system is used in the following value sets:

• ValueSet: Oral Site Codes (This value set includes a smattering of FDI oral site codes.)

• ValueSet: Oral Site Codes (This value set includes a smattering of FDI oral site codes.)

4.3.14.126.1 Content

4.3.14.126.2 Oral Site Codes

This value set includes a smattering of FDI oral site codes.

Copyright Statement:

This is an example set.

This code system http://terminology.hl7.org/CodeSystem/ex-tooth defines the following codes:

Code | Display | Definition
0 | Oral cavity | Oral cavity.
1 | 1 | Permanent teeth Maxillary right.
2 | 2 | Permanent teeth Maxillary left.
3 | 3 | Permanent teeth Mandibular right.
4 | 4 | Permanent teeth Mandibular left.
5 | 5 | Deciduous teeth Maxillary right.
6 | 6 | Deciduous teeth Maxillary left.
7 | 7 | Deciduous teeth Mandibular right.
8 | 8 | Deciduous teeth Mandibular left.
11 | 11 | Upper Right Tooth 1 from the central axis, permanent dentition.
12 | 12 | Upper Right Tooth 2 from the central axis, permanent dentition.
13 | 13 | Upper Right Tooth 3 from the central axis, permanent dentition.
14 | 14 | Upper Right Tooth 4 from the central axis, permanent dentition.
15 | 15 | Upper Right Tooth 5 from the central axis, permanent dentition.
16 | 16 | Upper Right Tooth 6 from the central axis, permanent dentition.
17 | 17 | Upper Right Tooth 7 from the central axis, permanent dentition.
18 | 18 | Upper Right Tooth 8 from the central axis, permanent dentition.
21 | 21 | Upper Left Tooth 1 from the central axis, permanent dentition.
22 | 22 | Upper Left Tooth 2 from the central axis, permanent dentition.
23 | 23 | Upper Left Tooth 3 from the central axis, permanent dentition.
24 | 24 | Upper Left Tooth 4 from the central axis, permanent dentition.
25 | 25 | Upper Left Tooth 5 from the central axis, permanent dentition.
26 | 26 | Upper Left Tooth 6 from the central axis, permanent dentition.
27 | 27 | Upper Left Tooth 7 from the central axis, permanent dentition.
28 | 28 | Upper Left Tooth 8 from the central axis, permanent dentition.
31 | 31 | Lower Left Tooth 1 from the central axis, permanent dentition.
32 | 32 | Lower Left Tooth 2 from the central axis, permanent dentition.
33 | 33 | Lower Left Tooth 3 from the central axis, permanent dentition.
34 | 34 | Lower Left Tooth 4 from the central axis, permanent dentition.
35 | 35 | Lower Left Tooth 5 from the central axis, permanent dentition.
36 | 36 | Lower Left Tooth 6 from the central axis, permanent dentition.
37 | 37 | Lower Left Tooth 7 from the central axis, permanent dentition.
38 | 38 | Lower Left Tooth 8 from the central axis, permanent dentition.
41 | 41 | Lower Right Tooth 1 from the central axis, permanent dentition.
42 | 42 | Lower Right Tooth 2 from the central axis, permanent dentition.
43 | 43 | Lower Right Tooth 3 from the central axis, permanent dentition.
44 | 44 | Lower Right Tooth 4 from the central axis, permanent dentition.
45 | 45 | Lower Right Tooth 5 from the central axis, permanent dentition.
46 | 46 | Lower Right Tooth 6 from the central axis, permanent dentition.
47 | 47 | Lower Right Tooth 7 from the central axis, permanent dentition.
48 | 48 | Lower Right Tooth 8 from the central axis, permanent dentition.

See the full registry of code systems defined as part of FHIR.

Explanation of the columns that may appear on this page:

Level | A few code lists that FHIR defines are hierarchical - each code is assigned a level. See Code System for further information.
Source | The source of the definition of the code (when the value set draws in codes defined elsewhere)
Code | The code (used as the code in the resource instance). If the code is in italics, this indicates that the code is not selectable ('Abstract')
Display | The display (used in the display element of a Coding). If there is no display, implementers should not simply display the code, but map the concept into their application
Definition | An explanation of the meaning of the concept
Comments | Additional notes about how to use the code

4.3.14.127 Code System http://hl7.org/fhir/action-relationship-type

URL: https://hl7.org/fhir/R4/codesystem-action-relationship-type.html
Clinical Decision Support Work Group | Maturity Level: 2 | Trial Use | Use Context: Any

This is a code system defined by the FHIR project.

Summary

Defining URL: | http://hl7.org/fhir/action-relationship-type
Version: | 4.0.1
Name: | ActionRelationshipType
Title: | ActionRelationshipType
Definition: | Defines the types of relationships between actions.
Committee: | Clinical Decision Support Work Group
OID: | 2.16.840.1.113883.4.642.4.814 (for OID based terminology systems)
Source Resource | XML / JSON

This Code system is used in the following value sets:

• ValueSet: ActionRelationshipType (Defines the types of relationships between actions.)

• ValueSet: ActionRelationshipType (Defines the types of relationships between actions.)

4.3.14.127.1 Content

4.3.14.127.2 ActionRelationshipType

Defines the types of relationships between actions.

This code system http://hl7.org/fhir/action-relationship-type defines the following codes:

Code | Display | Definition
before-start | Before Start | The action must be performed before the start of the related action.
before | Before | The action must be performed before the related action.
before-end | Before End | The action must be performed before the end of the related action.
concurrent-with-start | Concurrent With Start | The action must be performed concurrent with the start of the related action.
concurrent | Concurrent | The action must be performed concurrent with the related action.
concurrent-with-end | Concurrent With End | The action must be performed concurrent with the end of the related action.
after-start | After Start | The action must be performed after the start of the related action.
after | After | The action must be performed after the related action.
after-end | After End | The action must be performed after the end of the related action.

See the full registry of code systems defined as part of FHIR.

Explanation of the columns that may appear on this page:

Level | A few code lists that FHIR defines are hierarchical - each code is assigned a level. See Code System for further information.
Source | The source of the definition of the code (when the value set draws in codes defined elsewhere)
Code | The code (used as the code in the resource instance). If the code is in italics, this indicates that the code is not selectable ('Abstract')
Display | The display (used in the display element of a Coding). If there is no display, implementers should not simply display the code, but map the concept into their application
Definition | An explanation of the meaning of the concept
Comments | Additional notes about how to use the code

4.3.14.128 Code System urn:oid:2.16.840.1.113883.3.1937.98.5.8

URL: https://hl7.org/fhir/R4/codesystem-tldc.html
Vocabulary Work Group | Maturity Level: 0 | Informative | Use Context: Any

This is a code system defined by the FHIR project.

Summary

Defining URL: | urn:oid:2.16.840.1.113883.3.1937.98.5.8
Version: | null
Name: | TemplateStatusCodeLifeCycle
Title: | TemplateStatusCode LifeCycle
Definition: | Life cycle of the Status Code of a Template Design (Version)
Committee: | ??
OID: | (for OID based terminology systems)
Source Resource | XML / JSON

This Code system is used in the following value sets:

• ValueSet: TemplateStatusCode (The status indicates the level of maturity of the design and may be used to manage the use of the design.)

• ValueSet: TemplateStatusCode (The status indicates the level of maturity of the design and may be used to manage the use of the design.)

4.3.14.128.1 Content

4.3.14.128.2 TemplateStatusCode LifeCycle

Life cycle of the Status Code of a Template Design (Version)

This code system urn:oid:2.16.840.1.113883.3.1937.98.5.8 defines the following codes:

Code | Display | Definition
draft | Draft | Design is under development (nascent).
pending | Under pre-publication review | Design is completed and is being reviewed.
active | active | Design has been deemed fit for the intended purpose and is published by the governance group.
review | In Review | Design is active, but is under review. The review may result in a change to the design. The change may necessitate a new version to be created. This in turn may result in the prior version of the template to be retired. Alternatively, the review may result in a change to the design that does not require a new version to be created, or it may result in no change to the design at all.
cancelled | Cancelled | A drafted design is determined to be erroneous or not fit for intended purpose and is discontinued before ever being published in an active state.
rejected | Rejected | A previously drafted design is determined to be erroneous or not fit for intended purpose and is discontinued before ever being published for consideration in a pending state.
retired | retired | A previously active design is discontinued from use. It should no longer be used for future designs, but for historical purposes may be used to process data previously recorded using this design. A newer design may or may not exist. The design is published in the retired state.
terminated | Terminated | A design is determined to be erroneous or not fit for the intended purpose and should no longer be used, even for historical purposes. No new designs can be developed for this template. The associated template no longer needs to be published, but if published, is shown in the terminated state.

See the full registry of code systems defined as part of FHIR.

Explanation of the columns that may appear on this page:

Level | A few code lists that FHIR defines are hierarchical - each code is assigned a level. See Code System for further information.
Source | The source of the definition of the code (when the value set draws in codes defined elsewhere)
Code | The code (used as the code in the resource instance). If the code is in italics, this indicates that the code is not selectable ('Abstract')
Display | The display (used in the display element of a Coding). If there is no display, implementers should not simply display the code, but map the concept into their application
Definition | An explanation of the meaning of the concept
Comments | Additional notes about how to use the code

4.3.14.129 Code System http://hl7.org/fhir/action-participant-type

URL: https://hl7.org/fhir/R4/codesystem-action-participant-type.html
Clinical Decision Support Work Group | Maturity Level: 2 | Trial Use | Use Context: Any

This is a code system defined by the FHIR project.

Summary

Defining URL: | http://hl7.org/fhir/action-participant-type
Version: | 4.0.1
Name: | ActionParticipantType
Title: | ActionParticipantType
Definition: | The type of participant for the action.
Committee: | Clinical Decision Support Work Group
OID: | 2.16.840.1.113883.4.642.4.812 (for OID based terminology systems)
Source Resource | XML / JSON

This Code system is used in the following value sets:

• ValueSet: ActionParticipantType (The type of participant for the action.)
• ValueSet: ActionParticipantType (The type of participant for the action.)

4.3.14.129.1 Content

4.3.14.129.2 ActionParticipantType

The type of participant for the action.

This code system http://hl7.org/fhir/action-participant-type defines the following codes:

Code | Display | Definition
patient | Patient | The participant is the patient under evaluation.
practitioner | Practitioner | The participant is a practitioner involved in the patient's care.
related-person | Related Person | The participant is a person related to the patient.
device | Device | The participant is a system or device used in the care of the patient.

See the full registry of code systems defined as part of FHIR.

Explanation of the columns that may appear on this page:

Level | A few code lists that FHIR defines are hierarchical - each code is assigned a level. See Code System for further information.
Source | The source of the definition of the code (when the value set draws in codes defined elsewhere)
Code | The code (used as the code in the resource instance). If the code is in italics, this indicates that the code is not selectable ('Abstract')
Display | The display (used in the display element of a Coding). If there is no display, implementers should not simply display the code, but map the concept into their application
Definition | An explanation of the meaning of the concept

Comments | Additional notes about how to use the code

4.3.14.130 Code System http://hl7.org/fhir/animal-species

URL: https://hl7.org/fhir/R4/codesystem-animal-species.html
Vocabulary Work Group | Maturity Level: 0 | Informative | Use Context: Any

This is a code system defined by the FHIR project.

Summary

Defining URL: | http://hl7.org/fhir/animal-species
Version: | 4.0.1
Name: | AnimalSpecies
Title: | Animal species
Definition: | This example value set defines a set of codes that can be used to indicate species of animal patients.
Committee: | ??
OID: | 2.16.840.1.113883.4.642.4.421 (for OID based terminology systems)
Copyright: | This resource includes content from SNOMED Clinical Terms® (SNOMED CT®) which is copyright of the International Health Terminology Standards Development Organisation (IHTSDO). Implementers of these specifications must have the appropriate SNOMED CT Affiliate license - for more information contact http://www.snomed.org/snomed-ct/get-snomed-ct or info@snomed.org
Source Resource | XML / JSON

This Code system is not currently used

4.3.14.130.1 Content

4.3.14.130.2 Animal species

This example value set defines a set of codes that can be used to indicate species of animal patients.

Copyright Statement:

This resource includes content from SNOMED Clinical Terms® (SNOMED CT®) which is copyright of the International Health Terminology Standards Development Organisation (IHTSDO). Implementers of these specifications must have the appropriate SNOMED CT Affiliate license - for more information contact http://www.snomed.org/snomed-ct/get-snomed-ct or info@snomed.org

This code system http://hl7.org/fhir/animal-species defines the following codes:

Code | Display | Definition
canislf | Dog | Canis lupus familiaris
ovisa | Sheep | Ovis aries
serinuscd | Domestic Canary | Serinus canaria domestica

See the full registry of code systems defined as part of FHIR.

Explanation of the columns that may appear on this page:

Level | A few code lists that FHIR defines are hierarchical - each code is assigned a level. See Code System for further information.
Source | The source of the definition of the code (when the value set draws in codes defined elsewhere)
Code | The code (used as the code in the resource instance). If the code is in italics, this indicates that the code is not selectable ('Abstract')
Display | The display (used in the display element of a Coding). If there is no display, implementers should not simply display the code, but map the concept into their application
Definition | An explanation of the meaning of the concept
Comments | Additional notes about how to use the code

4.3.14.131 Code System http://hl7.org/fhir/action-condition-kind

URL: https://hl7.org/fhir/R4/codesystem-action-condition-kind.html
Clinical Decision Support Work Group | Maturity Level: 2 | Trial Use | Use Context: Any

This is a code system defined by the FHIR project.

Summary

Defining URL: | http://hl7.org/fhir/action-condition-kind
Version: | 4.0.1
Name: | ActionConditionKind
Title: | ActionConditionKind
Definition: | Defines the kinds of conditions that can appear on actions.
Committee: | Clinical Decision Support Work Group
OID: | 2.16.840.1.113883.4.642.4.816 (for OID based terminology systems)
Source Resource | XML / JSON

This Code system is used in the following value sets:

• ValueSet: ActionConditionKind (Defines the kinds of conditions that can appear on actions.)

• ValueSet: ActionConditionKind (Defines the kinds of conditions that can appear on actions.)

4.3.14.131.1 Content

4.3.14.131.2 ActionConditionKind

Defines the kinds of conditions that can appear on actions.

This code system http://hl7.org/fhir/action-condition-kind defines the following codes:

Code | Display | Definition
applicability | Applicability | The condition describes whether or not a given action is applicable.
start | Start | The condition is a starting condition for the action.
stop | Stop | The condition is a stop, or exit condition for the action.

See the full registry of code systems defined as part of FHIR.

Explanation of the columns that may appear on this page:

Level | A few code lists that FHIR defines are hierarchical - each code is assigned a level. See Code System for further information.
Source | The source of the definition of the code (when the value set draws in codes defined elsewhere)
Code | The code (used as the code in the resource instance). If the code is in italics, this indicates that the code is not selectable ('Abstract')
Display | The display (used in the display element of a Coding). If there is no display, implementers should not simply display the code, but map the concept into their application
Definition | An explanation of the meaning of the concept
Comments | Additional notes about how to use the code

4.3.14.132 Code System http://hl7.org/fhir/structure-definition-kind

URL: https://hl7.org/fhir/R4/codesystem-structure-definition-kind.html
FHIR Infrastructure Work Group | Maturity Level: N | Normative (from v4.0.0) | Use Context: Any

| This page has been approved as part of an ANSI standard. See the Conformance Package for further details.

This is a code system defined by the FHIR project.

Summary

Defining URL: | http://hl7.org/fhir/structure-definition-kind
Version: | 4.0.1
Name: | StructureDefinitionKind
Title: | StructureDefinitionKind
Definition: | Defines the type of structure that a definition is describing.
Committee: | FHIR Infrastructure Work Group
OID: | 2.16.840.1.113883.4.642.4.669 (for OID based terminology systems)
Source Resource | XML / JSON

This Code system is used in the following value sets:

• ValueSet: StructureDefinitionKind (Defines the type of structure that a definition is describing.)
• ValueSet: StructureDefinitionKind (Defines the type of structure that a definition is describing.)

4.3.14.132.1 Content

4.3.14.132.2 StructureDefinitionKind

Defines the type of structure that a definition is describing.

This code system http://hl7.org/fhir/structure-definition-kind defines the following codes:

Code | Display | Definition
primitive-type | Primitive Data Type | A primitive type that has a value and an extension. These can be used throughout complex datatype, Resource and extension definitions. Only the base specification can define primitive types.
complex-type | Complex Data Type | A complex structure that defines a set of data elements that is suitable for use in 'resources'. The base specification defines a number of complex types, and other specifications can define additional types. These structures do not have a maintained identity.
resource | Resource | A 'resource' - a directed acyclic graph of elements that aggregrates other types into an identifiable entity. The base FHIR resources are defined by the FHIR specification itself but other 'resources' can be defined in additional specifications (though these will not be recognised as 'resources' by the FHIR specification (i.e. they do not get end-points etc, or act as the targets of references in FHIR defined resources - though other specificatiosn can treat them this way).
logical | Logical | A pattern or a template that is not intended to be a real resource or complex type.

See the full registry of code systems defined as part of FHIR.

Explanation of the columns that may appear on this page:

Level | A few code lists that FHIR defines are hierarchical - each code is assigned a level. See Code System for further information.
Source | The source of the definition of the code (when the value set draws in codes defined elsewhere)
Code | The code (used as the code in the resource instance). If the code is in italics, this indicates that the code is not selectable ('Abstract')

Display | The display (used in the display element of a Coding). If there is no display, implementers should not simply display the code, but map the concept into their application
Definition | An explanation of the meaning of the concept
Comments | Additional notes about how to use the code

4.3.14.133 Code System http://hl7.org/fhir/contract-security-category

URL: https://hl7.org/fhir/R4/codesystem-contract-security-category.html
Financial Management Work Group | Maturity Level: 1 | Draft | Use Context: Any

This is a code system defined by the FHIR project.

Summary

Defining URL: | http://hl7.org/fhir/contract-security-category
Version: | 4.0.1
Name: | ContractResourceScopeCodes
Title: | Contract Resource Scope codes
Definition: | This value set contract specific codes for security category.
Committee: | Financial Management Work Group
OID: | 2.16.840.1.113883.4.642.4.1221 (for OID based terminology systems)
Copyright: | HL7 International.
Source Resource | XML / JSON

This Code system is used in the following value sets:

• ValueSet: Contract Resource Scope codes (This value set contract specific codes for security category.)

• ValueSet: Contract Resource Scope codes (This value set contract specific codes for security category.)

4.3.14.133.1 Content

Each definition includes usage notes explaining the precedence order in contract lifecycle - i.e., while only some stages are required, the order in which they may occur is deterministic; and a map to comparable FHIR and v.3 status codes. It follows guidance about use of status codes in FHIR at http://build.fhir.org/sc.html.

4.3.14.133.2 Contract Resource Scope codes

This value set contract specific codes for security category.

Copyright Statement:

HL7 International.

This code system http://hl7.org/fhir/contract-security-category defines the following codes:

Code | Display | Definition
policy | Policy | To be completed

See the full registry of code systems defined as part of FHIR.

Explanation of the columns that may appear on this page:

Level | A few code lists that FHIR defines are hierarchical - each code is assigned a level. See Code System for further information.
Source | The source of the definition of the code (when the value set draws in codes defined elsewhere)
Code | The code (used as the code in the resource instance). If the code is in italics, this indicates that the code is not selectable ('Abstract')
Display | The display (used in the display element of a Coding). If there is no display, implementers should not simply display the code, but map the concept into their application
Definition | An explanation of the meaning of the concept
Comments | Additional notes about how to use the code

4.3.14.134 Code System http://terminology.hl7.org/CodeSystem/ex-relatedclaimrelationship

URL: https://hl7.org/fhir/R4/codesystem-related-claim-relationship.html
Financial Management Work Group | Maturity Level: 1 | Draft | Use Context: Any

This is a code system defined by the FHIR project.

Summary

Defining URL: | http://terminology.hl7.org/CodeSystem/ex-relatedclaimrelationship
Version: | 4.0.1
Name: | ExampleRelatedClaimRelationshipCodes
Title: | Example Related Claim Relationship Codes
Definition: | This value set includes sample Related Claim Relationship codes.
Committee: | Financial Management Work Group
OID: | 2.16.840.1.113883.4.642.4.1159 (for OID based terminology systems)
Copyright: | This is an example set.

Source Resource | XML / JSON

This Code system is used in the following value sets:

• ValueSet: Example Related Claim Relationship Codes (This value set includes sample Related Claim Relationship codes.)

• ValueSet: Example Related Claim Relationship Codes (This value set includes sample Related Claim Relationship codes.)

4.3.14.134.1 Content

4.3.14.134.2 Example Related Claim Relationship Codes

This value set includes sample Related Claim Relationship codes.

Copyright Statement:

This is an example set.

This code system http://terminology.hl7.org/CodeSystem/ex-relatedclaimrelationship defines the following codes:

Code	Display	Definition
prior	Prior Claim	A prior claim instance for the same intended suite of services.
associated	Associated Claim	A claim for a different suite of services which is related the suite claimed here.

See the full registry of code systems defined as part of FHIR.

Explanation of the columns that may appear on this page:

Level	A few code lists that FHIR defines are hierarchical - each code is assigned a level. See Code System for further information.
Source	The source of the definition of the code (when the value set draws in codes defined elsewhere)
Code	The code (used as the code in the resource instance). If the code is in italics, this indicates that the code is not selectable ('Abstract')
Display	The display (used in the display element of a Coding). If there is no display, implementers should not simply display the code, but map the concept into their application
Definition	An explanation of the meaning of the concept
Comments	Additional notes about how to use the code

4.3.14.135 Code System http://hl7.org/fhir/observation-range-category

URL: https://hl7.org/fhir/R4/codesystem-observation-range-category.html
Orders and Observations Work Group | Maturity Level: 0 | Trial Use | Use Context: Any

This is a code system defined by the FHIR project.

Summary

Defining URL:	http://hl7.org/fhir/observation-range-category
Version:	4.0.1
Name:	ObservationRangeCategory
Title:	ObservationRangeCategory
Definition:	Codes identifying the category of observation range.
Committee:	Orders and Observations Work Group
OID:	2.16.840.1.113883.4.642.4.1334 (for OID based terminology systems)

Source Resource | XML / JSON

This Code system is used in the following value sets:

• ValueSet: ObservationRangeCategory (Codes identifying the category of observation range.)

• ValueSet: ObservationRangeCategory (Codes identifying the category of observation range.)

4.3.14.135.1 Content

4.3.14.135.2 ObservationRangeCategory

Codes identifying the category of observation range.

This code system http://hl7.org/fhir/observation-range-category defines the following codes:

Code	Display	Definition
reference	reference range	Reference (Normal) Range for Ordinal and Continuous Observations.
critical	critical range	Critical Range for Ordinal and Continuous Observations.
absolute	absolute range	Absolute Range for Ordinal and Continuous Observations. Results outside this range are not possible.

See the full registry of code systems defined as part of FHIR.

Explanation of the columns that may appear on this page:

Level	A few code lists that FHIR defines are hierarchical - each code is assigned a level. See Code System for further information.
Source	The source of the definition of the code (when the value set draws in codes defined elsewhere)

Code | The code (used as the code in the resource instance). If the code is in italics, this indicates that the code is not selectable ('Abstract')
Display | The display (used in the display element of a Coding). If there is no display, implementers should not simply display the code, but map the concept into their application
Definition | An explanation of the meaning of the concept
Comments | Additional notes about how to use the code

4.3.14.136 Code System http://terminology.hl7.org/CodeSystem/data-absent-reason

URL: https://hl7.org/fhir/R4/codesystem-data-absent-reason.html
Orders and Observations Work Group | Maturity Level: N | Normative (from v4.0.0) | Use Context: Any

| This page has been approved as part of an ANSI standard. See the Observation Package for further details.

This is a code system defined by the FHIR project.

Summary

Defining URL: | http://terminology.hl7.org/CodeSystem/data-absent-reason
Version: | 4.0.1
Name: | DataAbsentReason
Title: | DataAbsentReason
Definition: | Used to specify why the normally expected content of the data element is missing.
Committee: | Orders and Observations Work Group
OID: | 2.16.840.1.113883.4.642.4.1048 (for OID based terminology systems)
Source Resource | XML / JSON

This Code system is used in the following value sets:

• ValueSet: DataAbsentReason (Used to specify why the normally expected content of the data element is missing.)

• ValueSet: DataAbsentReason (Used to specify why the normally expected content of the data element is missing.)

4.3.14.136.1 Content

4.3.14.136.2 DataAbsentReason

Used to specify why the normally expected content of the data element is missing.

This code system http://terminology.hl7.org/CodeSystem/data-absent-reason defines the following codes:

Lvl | Code | Display | Definition | Comments
1 | unknown | Unknown | The value is expected to exist but is not known.
2 | asked-unknown | Asked But Unknown | The source was asked but does not know the value.
2 | temp-unknown | Temporarily Unknown | There is reason to expect (from the workflow) that the value may become known.
2 | not-asked | Not Asked | The workflow didn't lead to this value being known.
2 | asked-declined | Asked But Declined | The source was asked but declined to answer.
1 | masked | Masked | The information is not available due to security, privacy or related reasons. | Using "masked" may be breach of security or confidentiality, but there are times when its use is required to support alternate workflows for gaining access to denied information.
1 | not-applicable | Not Applicable | There is no proper value for this element (e.g. last menstrual period for a male).
1 | unsupported | Unsupported | The source system wasn't capable of supporting this element.
1 | as-text | As Text | The content of the data is represented in the resource narrative. | It may be linked by internal references (e.g. xml:id). This usually implies that the value could not be represented in the correct format - this may be due to system limitations, or this particular data value.
1 | error | Error | Some system or workflow process error means that the information is not available.
2 | not-a-number | Not a Number (NaN) | The numeric value is undefined or unrepresentable due to a floating point processing error. | This is sometimes an output value from measuring devices.
2 | negative-infinity | Negative Infinity (NINF) | The numeric value is excessively low and unrepresentable due to a floating point processing error. | This is sometimes an output value from measuring devices.
2 | positive-infinity | Positive Infinity (PINF) | The numeric value is excessively high and unrepresentable due to a floating point processing error. | This is sometimes an output value from measuring devices.
1 | not-performed | Not Performed | The value is not available because the observation procedure (test, etc.) was not performed.
1 | not-permitted | Not Permitted | The value is not permitted in this context (e.g. due to profiles, or the base data types). | This is most often associated with required bindings that do not include the actual code used, but may be used with other data types.

See the full registry of code systems defined as part of FHIR.

Explanation of the columns that may appear on this page:

Level | A few code lists that FHIR defines are hierarchical - each code is assigned a level. See Code System for further information.
Source | The source of the definition of the code (when the value set draws in codes defined elsewhere)
Code | The code (used as the code in the resource instance). If the code is in italics, this indicates that the code is not selectable ('Abstract')
Display | The display (used in the display element of a Coding). If there is no display, implementers should not simply display the code, but map the concept into their application
Definition | An explanation of the meaning of the concept

Comments | Additional notes about how to use the code

4.3.14.137 Code System http://hl7.org/fhir/subscription-status

URL: https://hl7.org/fhir/R4/codesystem-subscription-status.html
FHIR Infrastructure Work Group | Maturity Level: 3 | Trial Use | Use Context: Any

This is a code system defined by the FHIR project.

Summary

Defining URL: | http://hl7.org/fhir/subscription-status
Version: | 4.0.1
Name: | SubscriptionStatus
Title: | SubscriptionStatus
Definition: | The status of a subscription.
Committee: | FHIR Infrastructure Work Group
OID: | 2.16.840.1.113883.4.642.4.503 (for OID based terminology systems)
Source Resource | XML / JSON

This Code system is used in the following value sets:

• ValueSet: SubscriptionStatus (The status of a subscription.)

• ValueSet: SubscriptionStatus (The status of a subscription.)

4.3.14.137.1 Content

4.3.14.137.2 SubscriptionStatus

The status of a subscription.

This code system http://hl7.org/fhir/subscription-status defines the following codes:

Code | Display | Definition
requested | Requested | The client has requested the subscription, and the server has not yet set it up.
active | Active | The subscription is active.
error | Error | The server has an error executing the notification.
off | Off | Too many errors have occurred or the subscription has expired.

See the full registry of code systems defined as part of FHIR.

Explanation of the columns that may appear on this page:

Level | A few code lists that FHIR defines are hierarchical - each code is assigned a level. See Code System for further information.
Source | The source of the definition of the code (when the value set draws in codes defined elsewhere)
Code | The code (used as the code in the resource instance). If the code is in italics, this indicates that the code is not selectable ('Abstract')
Display | The display (used in the display element of a Coding). If there is no display, implementers should not simply display the code, but map the concept into their application
Definition | An explanation of the meaning of the concept
Comments | Additional notes about how to use the code

4.3.14.138 Code System http://hl7.org/fhir/additionalmaterials

URL: https://hl7.org/fhir/R4/codesystem-additionalmaterials.html
Vocabulary Work Group | Maturity Level: 0 | Informative | Use Context: Any

This is a code system defined by the FHIR project.

Summary

Defining URL: | http://hl7.org/fhir/additionalmaterials
Version: | 4.0.1
Name: | AdditionalMaterialCodes
Title: | Additional Material Codes
Definition: | This value set includes sample additional material type codes.
Committee: | ??
OID: | 2.16.840.1.113883.4.642.4.530 (for OID based terminology systems)
Copyright: | This is an example set.
Source Resource | XML / JSON

This Code system is used in the following value sets:

• ValueSet: Additional Material Codes (This value set includes sample additional material type codes.)

• ValueSet: Additional Material Codes (This value set includes sample additional material type codes.)

4.3.14.138.1 Content

4.3.14.138.2 Additional Material Codes

This value set includes sample additional material type codes.

Copyright Statement:

This is an example set.

This code system http://hl7.org/fhir/additionalmaterials defines the following codes:

Code | Display | Definition
xray | XRay | XRay
image | Image | Image
email | Email | Email
model | Model | Model
document | Document | Document
other | Other | Other

See the full registry of code systems defined as part of FHIR.

Explanation of the columns that may appear on this page:

Level | A few code lists that FHIR defines are hierarchical - each code is assigned a level. See Code System for further information.
Source | The source of the definition of the code (when the value set draws in codes defined elsewhere)
Code | The code (used as the code in the resource instance). If the code is in italics, this indicates that the code is not selectable ('Abstract')
Display | The display (used in the display element of a Coding). If there is no display, implementers should not simply display the code, but map the concept into their application
Definition | An explanation of the meaning of the concept
Comments | Additional notes about how to use the code

4.3.14.139 Code System http://terminology.hl7.org/CodeSystem/appointment-cancellation-reason

URL: https://hl7.org/fhir/R4/codesystem-appointment-cancellation-reason.html
Patient Administration Work Group | Maturity Level: 1 | Draft | Use Context: Any

This is a code system defined by the FHIR project.

Summary

Defining URL: | http://terminology.hl7.org/CodeSystem/appointment-cancellation-reason
Version: | 4.0.1
Name: | AppointmentCancellationReason
Title: | Appointment cancellation reason
Definition: | This example value set defines a set of reasons for the cancellation of an appointment.
Committee: | Patient Administration Work Group
OID: | 2.16.840.1.113883.4.642.4.1382 (for OID based terminology systems)
Source Resource | XML / JSON

This Code system is used in the following value sets:

• ValueSet: Appointment cancellation reason (This example value set defines a set of reasons for the cancellation of an appointment.)

• ValueSet: Appointment cancellation reason (This example value set defines a set of reasons for the cancellation of an appointment.)

4.3.14.139.1 Content

4.3.14.139.2 Appointment cancellation reason

This example value set defines a set of reasons for the cancellation of an appointment.

This code system http://terminology.hl7.org/CodeSystem/appointment-cancellation-reason defines many codes, of which the following are some examples:

Lvl | Code | Display | Definition
1 | pat | Patient
2 | pat-crs | Patient: Canceled via automated reminder system
2 | pat-cpp | Patient: Canceled via Patient Portal
2 | pat-dec | Patient: Deceased
2 | pat-fb | Patient: Feeling Better
2 | pat-lt | Patient: Lack of Transportation
2 | pat-mt | Patient: Member Terminated
2 | pat-mv | Patient: Moved
2 | pat-preg | Patient: Pregnant
2 | pat-swl | Patient: Scheduled from Wait List
2 | pat-ucp | Patient: Unhappy/Changed Provider
1 | prov | Provider
2 | prov-pers | Provider: Personal
2 | prov-dch | Provider: Discharged
2 | prov-edu | Provider: Edu/Meeting
2 | prov-hosp | Provider: Hospitalized

2 | prov-labs | Provider: Labs Out of Acceptable Range
2 | prov-mri | Provider: MRI Screening Form Marked Do Not Proceed
2 | prov-onc | Provider: Oncology Treatment Plan Changes
1 | maint | Equipment Maintenance/Repair
1 | meds-inc | Prep/Med Incomplete
1 | other | Other
2 | oth-cms | Other: CMS Therapy Cap Service Not Authorized
2 | oth-err | Other: Error
2 | oth-fin | Other: Financial
2 | oth-iv | Other: Improper IV Access/Infiltrate IV
2 | oth-int | Other: No Interpreter Available
2 | oth-mu | Other: Prep/Med/Results Unavailable
2 | oth-room | Other: Room/Resource Maintenance
2 | oth-oerr | Other: Schedule Order Error
2 | oth-swie | Other: Silent Walk In Error
2 | oth-weath | Other: Weather

See the full registry of code systems defined as part of FHIR.

Explanation of the columns that may appear on this page:

Level | A few code lists that FHIR defines are hierarchical - each code is assigned a level. See Code System for further information.
Source | The source of the definition of the code (when the value set draws in codes defined elsewhere)
Code | The code (used as the code in the resource instance). If the code is in italics, this indicates that the code is not selectable ('Abstract')
Display | The display (used in the display element of a Coding). If there is no display, implementers should not simply display the code, but map the concept into their application
Definition | An explanation of the meaning of the concept
Comments | Additional notes about how to use the code

4.3.14.140 Code System http://terminology.hl7.org/CodeSystem/usage-context-type

URL: https://hl7.org/fhir/R4/codesystem-usage-context-type.html
FHIR Infrastructure Work Group | Maturity Level: 5 | Trial Use | Use Context: Any

This is a code system defined by the FHIR project.

Summary

Defining URL: | http://terminology.hl7.org/CodeSystem/usage-context-type
Version: | 4.0.1
Name: | UsageContextType
Title: | UsageContextType
Definition: | A code that specifies a type of context being specified by a usage context.
Committee: | FHIR Infrastructure Work Group
OID: | 2.16.840.1.113883.4.642.4.1068 (for OID based terminology systems)
Source Resource | XML / JSON

This Code system is used in the following value sets:

• ValueSet: UsageContextType (A code that specifies a type of context being specified by a usage context.)
• ValueSet: UsageContextType (A code that specifies a type of context being specified by a usage context.)

4.3.14.140.1 Content

4.3.14.140.2 UsageContextType

A code that specifies a type of context being specified by a usage context.

This code system http://terminology.hl7.org/CodeSystem/usage-context-type defines the following codes:

Code | Display | Definition
gender | Gender | The gender of the patient. For this context type, appropriate values can be found in the http://hl7.org/fhir/ValueSet/administrative-gender value set.
age | Age Range | The age of the patient. For this context type, the value could be a range that specifies the applicable ages or a code from an appropriate value set such as the MeSH value set http://terminology.hl7.org/ValueSet/v3-AgeGroupObservationValue.
focus | Clinical Focus | The clinical concept(s) addressed by the artifact. For example, disease, diagnostic test interpretation, medication ordering as in http://hl7.org/fhir/ValueSet/condition-code.
user | User Type | The clinical specialty of the context in which the patient is being treated - For example, PCP, Patient, Cardiologist, Behavioral Professional, Oral Health Professional, Prescriber, etc... taken from a specialty value set such as the NUCC Health Care provider taxonomy value set http://hl7.org/fhir/ValueSet/provider-taxonomy.
workflow | Workflow Setting | The settings in which the artifact is intended for use. For example, admission, pre-op, etc. For example, the ActEncounterCode value set http://terminology.hl7.org/ValueSet/v3-ActEncounterCode.
task | Workflow Task | The context for the clinical task(s) represented by this artifact. For example, this could be any task context represented by the HL7 ActTaskCode value set http://terminology.hl7.org/ValueSet/v3-ActTaskCode. General categories include: order entry, patient documentation and patient information review.

venue | Clinical Venue | The venue in which an artifact could be used. For example, Outpatient, Inpatient, Home, Nursing home. The code value may originate from the HL7 ServiceDeliveryLocationRoleType value set (http://terminology.hl7.org/ValueSet/v3-ServiceDeliveryLocationRoleType).
species | Species | The species to which an artifact applies. For example, SNOMED - 387961004 | Kingdom Animalia (organism).
program | Program | A program/project of work for which this artifact is applicable.

See the full registry of code systems defined as part of FHIR.

Explanation of the columns that may appear on this page:

Level | A few code lists that FHIR defines are hierarchical - each code is assigned a level. See Code System for further information.
Source | The source of the definition of the code (when the value set draws in codes defined elsewhere)
Code | The code (used as the code in the resource instance). If the code is in italics, this indicates that the code is not selectable ('Abstract')
Display | The display (used in the display element of a Coding). If there is no display, implementers should not simply display the code, but map the concept into their application
Definition | An explanation of the meaning of the concept
Comments | Additional notes about how to use the code

4.3.14.141 Code System http://hl7.org/fhir/code-search-support

URL: https://hl7.org/fhir/R4/codesystem-code-search-support.html
Vocabulary Work Group | Maturity Level: 0 | Trial Use | Use Context: Any

This is a code system defined by the FHIR project.

Summary

Defining URL: | http://hl7.org/fhir/code-search-support
Version: | 4.0.1
Name: | CodeSearchSupport
Title: | CodeSearchSupport
Definition: | The degree to which the server supports the code search parameter on ValueSet, if it is supported.
Committee: | Vocabulary Work Group
OID: | 2.16.840.1.113883.4.642.4.861 (for OID based terminology systems)
Source Resource | XML / JSON

This Code system is used in the following value sets:

• ValueSet: CodeSearchSupport (The degree to which the server supports the code search parameter on ValueSet, if it is supported.)

• ValueSet: CodeSearchSupport (The degree to which the server supports the code search parameter on ValueSet, if it is supported.)

4.3.14.141.1 Content

4.3.14.141.2 CodeSearchSupport

The degree to which the server supports the code search parameter on ValueSet, if it is supported.

This code system http://hl7.org/fhir/code-search-support defines the following codes:

Code | Display | Definition
explicit | Explicit Codes | The search for code on ValueSet only includes codes explicitly detailed on includes or expansions.
all | Implicit Codes | The search for code on ValueSet only includes all codes based on the expansion of the value set.

See the full registry of code systems defined as part of FHIR.

Explanation of the columns that may appear on this page:

Level | A few code lists that FHIR defines are hierarchical - each code is assigned a level. See Code System for further information.
Source | The source of the definition of the code (when the value set draws in codes defined elsewhere)
Code | The code (used as the code in the resource instance). If the code is in italics, this indicates that the code is not selectable ('Abstract')
Display | The display (used in the display element of a Coding). If there is no display, implementers should not simply display the code, but map the concept into their application
Definition | An explanation of the meaning of the concept
Comments | Additional notes about how to use the code

4.3.14.142 Code System http://terminology.hl7.org/CodeSystem/contract-data-meaning

URL: https://hl7.org/fhir/R4/codesystem-contract-data-meaning.html
Vocabulary Work Group | Maturity Level: 0 | Informative | Use Context: Any

This is a code system defined by the FHIR project.

Summary

Defining URL: | http://terminology.hl7.org/CodeSystem/contract-data-meaning

Version: | 4.0.1
Name: | ContractDataMeaning
Title: | ContractDataMeaning
Definition: | How a resource reference is interpreted when evaluating contract offers.
Committee: | ??
OID: | 2.16.840.1.113883.4.642.4.1205 (for OID based terminology systems)
Source Resource | XML / JSON

This Code system is used in the following value sets:

• ValueSet: ContractDataMeaning (How a resource reference is interpreted when evaluating contract offers.)

• ValueSet: ContractDataMeaning (How a resource reference is interpreted when evaluating contract offers.)

4.3.14.142.1 Content

4.3.14.142.2 ContractDataMeaning

How a resource reference is interpreted when evaluating contract offers.

This code system http://terminology.hl7.org/CodeSystem/contract-data-meaning defines the following codes:

Code | Display | Definition
instance | Instance | The consent applies directly to the instance of the resource.
related | Related | The consent applies directly to the instance of the resource and instances it refers to.
dependents | Dependents | The consent applies directly to the instance of the resource and instances that refer to it.
authoredby | AuthoredBy | The consent applies to instances of resources that are authored by.

See the full registry of code systems defined as part of FHIR.

Explanation of the columns that may appear on this page:

Level | A few code lists that FHIR defines are hierarchical - each code is assigned a level. See Code System for further information.
Source | The source of the definition of the code (when the value set draws in codes defined elsewhere)
Code | The code (used as the code in the resource instance). If the code is in italics, this indicates that the code is not selectable ('Abstract')
Display | The display (used in the display element of a Coding). If there is no display, implementers should not simply display the code, but map the concept into their application
Definition | An explanation of the meaning of the concept
Comments | Additional notes about how to use the code

4.3.14.143 Code System http://terminology.hl7.org/CodeSystem/ex-programcode

URL: https://hl7.org/fhir/R4/codesystem-ex-program-code.html
Financial Management Work Group | Maturity Level: 1 | Draft | Use Context: Any

This is a code system defined by the FHIR project.

Summary

Defining URL: | http://terminology.hl7.org/CodeSystem/ex-programcode
Version: | 4.0.1
Name: | ExampleProgramReasonCodes
Title: | Example Program Reason Codes
Definition: | This value set includes sample Program Reason Span codes.
Committee: | Financial Management Work Group
OID: | 2.16.840.1.113883.4.642.4.1161 (for OID based terminology systems)
Copyright: | This is an example set.
Source Resource | XML / JSON

This Code system is used in the following value sets:

• ValueSet: Example Program Reason Codes (This value set includes sample Program Reason Span codes.)

• ValueSet: Example Program Reason Codes (This value set includes sample Program Reason Span codes.)

4.3.14.143.1 Content

4.3.14.143.2 Example Program Reason Codes

This value set includes sample Program Reason Span codes.

Copyright Statement:

This is an example set.

This code system http://terminology.hl7.org/CodeSystem/ex-programcode defines the following codes:

Code | Display | Definition
as | Child Asthma | Child Asthma Program
hd | Hemodialysis | Hemodialysis Program.
auscr | Autism Screening | Autism Screening Program.

none | None | No program code applies.

See the full registry of code systems defined as part of FHIR.

Explanation of the columns that may appear on this page:

Level | A few code lists that FHIR defines are hierarchical - each code is assigned a level. See Code System for further information.
Source | The source of the definition of the code (when the value set draws in codes defined elsewhere)
Code | The code (used as the code in the resource instance). If the code is in italics, this indicates that the code is not selectable ('Abstract')
Display | The display (used in the display element of a Coding). If there is no display, implementers should not simply display the code, but map the concept into their application
Definition | An explanation of the meaning of the concept
Comments | Additional notes about how to use the code

4.3.14.144 Code System http://hl7.org/fhir/remittance-outcome

URL: https://hl7.org/fhir/R4/codesystem-remittance-outcome.html
Financial Management Work Group | Maturity Level: 2 | Trial Use | Use Context: Any

This is a code system defined by the FHIR project.

Summary

Defining URL: | http://hl7.org/fhir/remittance-outcome
Version: | 4.0.1
Name: | ClaimProcessingCodes
Title: | Claim Processing Codes
Definition: | This value set includes Claim Processing Outcome codes.
Committee: | Financial Management Work Group
OID: | 2.16.840.1.113883.4.642.4.14 (for OID based terminology systems)
Copyright: | HL7 Inc.
Source Resource | XML / JSON

This Code system is used in the following value sets:

• ValueSet: Claim Processing Codes (This value set includes Claim Processing Outcome codes.)

• ValueSet: Claim Processing Codes (This value set includes Claim Processing Outcome codes.)

4.3.14.144.1 Content

4.3.14.144.2 Claim Processing Codes

This value set includes Claim Processing Outcome codes.

Copyright Statement:

HL7 Inc.

This code system http://hl7.org/fhir/remittance-outcome defines the following codes:

Code | Display | Definition
queued | Queued | The Claim/Pre-authorization/Pre-determination has been received but processing has not begun.
complete | Processing Complete | The processing has completed without errors
error | Error | One or more errors have been detected in the Claim
partial | Partial Processing | No errors have been detected in the Claim and some of the adjudication has been performed.

See the full registry of code systems defined as part of FHIR.

Explanation of the columns that may appear on this page:

Level | A few code lists that FHIR defines are hierarchical - each code is assigned a level. See Code System for further information.
Source | The source of the definition of the code (when the value set draws in codes defined elsewhere)
Code | The code (used as the code in the resource instance). If the code is in italics, this indicates that the code is not selectable ('Abstract')
Display | The display (used in the display element of a Coding). If there is no display, implementers should not simply display the code, but map the concept into their application
Definition | An explanation of the meaning of the concept
Comments | Additional notes about how to use the code

4.3.14.145 Code System urn:oid:1.2.36.1.2001.1001.101.104.16592

URL: https://hl7.org/fhir/R4/codesystem-list-item-flag.html
FHIR Infrastructure Work Group | Maturity Level: 1 | Draft | Use Context: Any

This is a code system defined at http://www.nehta.gov.au .

Summary

Defining URL: | urn:oid:1.2.36.1.2001.1001.101.104.16592

Version: | 4.0.1
Name: | PatientMedicineChangeTypes
Title: | Patient Medicine Change Types
Definition: | Example Item Flags for the List Resource. In this case, these are the kind of flags that would be used on a medication list at the end of a consultation.
Committee: | FHIR Infrastructure Work Group
OID: | 2.16.840.1.113883.4.642.4.321 (for OID based terminology systems)
Copyright: | Copyright © 2012-2013 National E-Health Transition Authority Ltd : This document contains information which is protected by copyright. All Rights Reserved. No part of this work may be reproduced or used in any form or by any means--graphic, electronic, or mechanical, including photocopying, recording, taping, or information storage and retrieval systems--without the permission of NEHTA. All copies of this document must include the copyright and other information contained on this page. Revision 1 Telephone: 1300 901 001 or email: servicedesk@nehta.gov.au Disclaimer: The National E-Health Transition Authority Ltd (NEHTA) makes the information and other material ('Information') in this document available in good faith but without any representation or warranty as to its accuracy or completeness. NEHTA cannot accept any responsibility for the consequences of any use of the Information. As the Information is of a general nature only, it is up to any person using or relying on the Information to ensure that it is accurate, complete and suitable for the circumstances of its use.
Source Resource | XML / JSON

This Code system is used in the following value sets:

• ValueSet: Patient Medicine Change Types (Example Item Flags for the List Resource. In this case, these are the kind of flags that would be used on a medication list at the end of a consultation.)

• ValueSet: Patient Medicine Change Types (Example Item Flags for the List Resource. In this case, these are the kind of flags that would be used on a medication list at the end of a consultation.)

4.3.14.145.1 Content

4.3.14.145.2 Patient Medicine Change Types

Example Item Flags for the List Resource. In this case, these are the kind of flags that would be used on a medication list at the end of a consultation.

Copyright Statement:

Copyright © 2012-2013 National E-Health Transition Authority Ltd : This document contains information which is protected by copyright. All Rights Reserved. No part of this work may be reproduced or used in any form or by any means--graphic, electronic, or mechanical, including photocopying, recording, taping, or information storage and retrieval systems--without the permission of NEHTA. All copies of this document must include the copyright and other information contained on this page. Revision 1 Telephone: 1300 901 001 or email: servicedesk@nehta.gov.au Disclaimer: The National E-Health Transition Authority Ltd (NEHTA) makes the information and other material ('Information') in this document available in good faith but without any representation or warranty as to its accuracy or completeness. NEHTA cannot accept any responsibility for the consequences of any use of the Information. As the Information is of a general nature only, it is up to any person using or relying on the Information to ensure that it is accurate, complete and suitable for the circumstances of its use.

This code system urn:oid:1.2.36.1.2001.1001.101.104.16592 defines the following codes:

Code | Display | Definition
01 | Unchanged | No change has been made to the status of this medicine item.
02 | Changed | The medicine item has changed. The change may be described in an extension (not defined yet)
03 | Cancelled | The prescription for this medicine item was cancelled by an authorized health care provider. The patient may be advised to complete the course of the prescribed medicine. This advice is a clinical decision made based on assessment of the patient's clinical condition.
04 | Prescribed | A new medicine item has been prescribed
05 | Ceased | Administration of this medication item that the patient is currently taking is stopped or recommended to be stopped (i.e. instructed to be ceased by a health care provider). This cessation is anticipated to be permanent. The Change Description should describe the reason for cessation. Example uses: the medication in question is considered ineffective or has caused serious adverse effects. This value applies both to the cessation of a medication that is prescribed by another healthcare provider or patient self-administration of OTC medicines.
06 | Suspended | Administration of this medication item that the patient is currently taking is on hold, or instructed or recommended by a health care provider to be temporarily stopped, or subject to clinical review (i.e. the stop may be temporary or permanent depending on the outcome of clinical review), or temporarily suspended as a pre-requisite to certain surgical or diagnostic procedures.

See the full registry of code systems defined as part of FHIR.

Explanation of the columns that may appear on this page:

Level | A few code lists that FHIR defines are hierarchical - each code is assigned a level. See Code System for further information.
Source | The source of the definition of the code (when the value set draws in codes defined elsewhere)
Code | The code (used as the code in the resource instance). If the code is in italics, this indicates that the code is not selectable ('Abstract')
Display | The display (used in the display element of a Coding). If there is no display, implementers should not simply display the code, but map the concept into their application
Definition | An explanation of the meaning of the concept
Comments | Additional notes about how to use the code

4.3.14.146 Code System http://hl7.org/fhir/definition-resource-types

URL: https://hl7.org/fhir/R4/codesystem-definition-resource-types.html
Vocabulary Work Group | Maturity Level: 0 | Informative | Use Context: Any

This is a code system defined by the FHIR project.

Summary

Defining URL: | http://hl7.org/fhir/definition-resource-types
Version: | 4.0.1
Name: | DefinitionResourceType
Title: | DefinitionResourceType
Definition: | A list of all the definition resource types defined in this version of the FHIR specification.
Committee: | Vocabulary Work Group
OID: | 2.16.840.1.113883.4.642.4.1057 (for OID based terminology systems)
Source Resource | XML / JSON

This Code system is used in the following value sets:

• ValueSet: DefinitionResourceType (A list of all the definition resource types defined in this version of the FHIR specification.)

• ValueSet: DefinitionResourceType (A list of all the definition resource types defined in this version of the FHIR specification.)

4.3.14.146.1 Content

4.3.14.146.2 DefinitionResourceType

A list of all the definition resource types defined in this version of the FHIR specification.

This code system http://hl7.org/fhir/definition-resource-types defines the following codes:

Code | Display | Definition
ActivityDefinition | ActivityDefinition | This resource allows for the definition of some activity to be performed, independent of a particular patient, practitioner, or other performance context.
EventDefinition | EventDefinition | The EventDefinition resource provides a reusable description of when a particular event can occur.
Measure | Measure | The Measure resource provides the definition of a quality measure.
OperationDefinition | OperationDefinition | A formal computable definition of an operation (on the RESTful interface) or a named query (using the search interaction).
PlanDefinition | PlanDefinition | This resource allows for the definition of various types of plans as a sharable, consumable, and executable artifact. The resource is general enough to support the description of a broad range of clinical artifacts such as clinical decision support rules, order sets and protocols.
Questionnaire | Questionnaire | A structured set of questions intended to guide the collection of answers from end-users. Questionnaires provide detailed control over order, presentation, phraseology and grouping to allow coherent, consistent data collection.

See the full registry of code systems defined as part of FHIR.

Explanation of the columns that may appear on this page:

Level | A few code lists that FHIR defines are hierarchical - each code is assigned a level. See Code System for further information.
Source | The source of the definition of the code (when the value set draws in codes defined elsewhere)
Code | The code (used as the code in the resource instance). If the code is in italics, this indicates that the code is not selectable ('Abstract')
Display | The display (used in the display element of a Coding). If there is no display, implementers should not simply display the code, but map the concept into their application
Definition | An explanation of the meaning of the concept
Comments | Additional notes about how to use the code

4.3.14.147 Code System http://hl7.org/fhir/response-code

URL: https://hl7.org/fhir/R4/codesystem-response-code.html
Infrastructure And Messaging Work Group | Maturity Level: 4 | Trial Use | Use Context: Any

This is a code system defined by the FHIR project.

Summary

Defining URL: | http://hl7.org/fhir/response-code
Version: | 4.0.1
Name: | ResponseType
Title: | ResponseType
Definition: | The kind of response to a message.
Committee: | Infrastructure And Messaging Work Group
OID: | 2.16.840.1.113883.4.642.4.381 (for OID based terminology systems)
Source Resource | XML / JSON

This Code system is used in the following value sets:

• ValueSet: ResponseType (The kind of response to a message.)

• ValueSet: ResponseType (The kind of response to a message.)

4.3.14.147.1 Content

4.3.14.147.2 ResponseType

The kind of response to a message.

This code system http://hl7.org/fhir/response-code defines the following codes:

Code | Display | Definition
ok | OK | The message was accepted and processed without error.
transient-error | Transient Error | Some internal unexpected error occurred - wait and try again. Note - this is usually used for things like database unavailable, which may be expected to resolve, though human intervention may be required.
fatal-error | Fatal Error | The message was rejected because of a problem with the content. There is no point in re-sending without change. The response narrative SHALL describe the issue.

See the full registry of code systems defined as part of FHIR.

Explanation of the columns that may appear on this page:

Level | A few code lists that FHIR defines are hierarchical - each code is assigned a level. See Code System for further information.
Source | The source of the definition of the code (when the value set draws in codes defined elsewhere)
Code | The code (used as the code in the resource instance). If the code is in italics, this indicates that the code is not selectable ('Abstract')
Display | The display (used in the display element of a Coding). If there is no display, implementers should not simply display the code, but map the concept into their application
Definition | An explanation of the meaning of the concept
Comments | Additional notes about how to use the code

4.3.14.148 Code System http://hl7.org/fhir/unknown-content-code

URL: https://hl7.org/fhir/R4/codesystem-unknown-content-code.html
Vocabulary Work Group | Maturity Level: 0 | Informative | Use Context: Any

This is a code system defined by the FHIR project.

Summary

Defining URL: | http://hl7.org/fhir/unknown-content-code
Version: | 4.0.1
Name: | UnknownContentCode
Title: | UnknownContentCode
Definition: | A code that indicates whether an application accepts unknown elements or extensions when reading resources.
Committee: | ??
OID: | 2.16.840.1.113883.4.642.4.197 (for OID based terminology systems)
Source Resource | XML / JSON

This Code system is used in the following value sets:

• ValueSet: UnknownContentCode (A code that indicates whether an application accepts unknown elements or extensions when reading resources.)

• ValueSet: UnknownContentCode (A code that indicates whether an application accepts unknown elements or extensions when reading resources.)

4.3.14.148.1 Content

4.3.14.148.2 UnknownContentCode

A code that indicates whether an application accepts unknown elements or extensions when reading resources.

This code system http://hl7.org/fhir/unknown-content-code defines the following codes:

Code | Display | Definition
no | Neither Elements or Extensions | The application does not accept either unknown elements or extensions.
extensions | Unknown Extensions | The application accepts unknown extensions, but not unknown elements.
elements | Unknown Elements | The application accepts unknown elements, but not unknown extensions.
both | Unknown Elements and Extensions | The application accepts unknown elements and extensions.

See the full registry of code systems defined as part of FHIR.

Explanation of the columns that may appear on this page:

Level | A few code lists that FHIR defines are hierarchical - each code is assigned a level. See Code System for further information.
Source | The source of the definition of the code (when the value set draws in codes defined elsewhere)

Code | The code (used as the code in the resource instance). If the code is in italics, this indicates that the code is not selectable ('Abstract')
Display | The display (used in the display element of a Coding). If there is no display, implementers should not simply display the code, but map the concept into their application
Definition | An explanation of the meaning of the concept
Comments | Additional notes about how to use the code

4.3.14.149 Code System http://terminology.hl7.org/CodeSystem/medication-admin-status

URL: https://hl7.org/fhir/R4/codesystem-medication-admin-status.html
Pharmacy Work Group | Maturity Level: 2 | Trial Use | Use Context: Any

This is a code system defined by the FHIR project.

Summary

Defining URL: | http://terminology.hl7.org/CodeSystem/medication-admin-status
Version: | 4.0.1
Name: | MedicationAdministration Status Codes
Title: | Medication administration status codes
Definition: | MedicationAdministration Status Codes
Committee: | Pharmacy Work Group
OID: | 2.16.840.1.113883.4.642.4.1311 (for OID based terminology systems)
Source Resource | XML / JSON

This Code system is used in the following value sets:

• ValueSet: Immunization Evaluation Status Codes (The value set to instantiate this attribute should be drawn from a terminologically robust code system that consists of or contains concepts to support describing the current status of the evaluation for vaccine administration event.)

• ValueSet: Immunization Evaluation Status Codes (The value set to instantiate this attribute should be drawn from a terminologically robust code system that consists of or contains concepts to support describing the current status of the evaluation for vaccine administration event.)

• ValueSet: Medication administration status codes (MedicationAdministration Status Codes)

• ValueSet: Medication administration status codes (MedicationAdministration Status Codes)

4.3.14.149.1 Content

4.3.14.149.2 Medication administration status codes

MedicationAdministration Status Codes

This code system http://terminology.hl7.org/CodeSystem/medication-admin-status defines the following codes:

Code | Display | Definition
in-progress | In Progress | The administration has started but has not yet completed.
not-done | Not Done | The administration was terminated prior to any impact on the subject (though preparatory actions may have been taken)
on-hold | On Hold | Actions implied by the administration have been temporarily halted, but are expected to continue later. May also be called 'suspended'.
completed | Completed | All actions that are implied by the administration have occurred.
entered-in-error | Entered in Error | The administration was entered in error and therefore nullified.
stopped | Stopped | Actions implied by the administration have been permanently halted, before all of them occurred.
unknown | Unknown | The authoring system does not know which of the status values currently applies for this request. Note: This concept is not to be used for 'other' - one of the listed statuses is presumed to apply, it's just not known which one.

See the full registry of code systems defined as part of FHIR.

Explanation of the columns that may appear on this page:

Level | A few code lists that FHIR defines are hierarchical - each code is assigned a level. See Code System for further information.
Source | The source of the definition of the code (when the value set draws in codes defined elsewhere)
Code | The code (used as the code in the resource instance). If the code is in italics, this indicates that the code is not selectable ('Abstract')
Display | The display (used in the display element of a Coding). If there is no display, implementers should not simply display the code, but map the concept into their application
Definition | An explanation of the meaning of the concept
Comments | Additional notes about how to use the code

4.3.14.150 Code System http://terminology.hl7.org/CodeSystem/variant-state

URL: https://hl7.org/fhir/R4/codesystem-variant-state.html
Vocabulary Work Group | Maturity Level: 0 | Informative | Use Context: Any

This is a code system defined by the FHIR project.

Summary

Defining URL: | http://terminology.hl7.org/CodeSystem/variant-state
Version: | 4.0.1
Name: | sequenceStatus
Title: | sequenceStatus
Definition: | Codes providing the status of the variant test result.
Committee: | ??
OID: | 2.16.840.1.113883.4.642.4.1085 (for OID based terminology systems)
Source Resource | XML / JSON

This Code system is used in the following value sets:

• ValueSet: sequenceStatus (Codes providing the status of the variant test result.)

• ValueSet: sequenceStatus (Codes providing the status of the variant test result.)

4.3.14.150.1 Content

4.3.14.150.2 sequenceStatus

Codes providing the status of the variant test result.

This code system http://terminology.hl7.org/CodeSystem/variant-state defines the following codes:

Code | Display | Definition
positive | positive | the variant is detected.
negative | negative | no variant is detected.
absent | absent | result of the variant is missing.

See the full registry of code systems defined as part of FHIR.

Explanation of the columns that may appear on this page:

Level | A few code lists that FHIR defines are hierarchical - each code is assigned a level. See Code System for further information.
Source | The source of the definition of the code (when the value set draws in codes defined elsewhere)
Code | The code (used as the code in the resource instance). If the code is in italics, this indicates that the code is not selectable ('Abstract')
Display | The display (used in the display element of a Coding). If there is no display, implementers should not simply display the code, but map the concept into their application
Definition | An explanation of the meaning of the concept
Comments | Additional notes about how to use the code

4.3.14.151 Code System http://hl7.org/fhir/conditional-read-status

URL: https://hl7.org/fhir/R4/codesystem-conditional-read-status.html
FHIR Infrastructure Work Group | Maturity Level: N | Normative (from v4.0.0) | Use Context: Any

| This page has been approved as part of an ANSI standard. See the Conformance Package for further details.

This is a code system defined by the FHIR project.

Summary

Defining URL: | http://hl7.org/fhir/conditional-read-status
Version: | 4.0.1
Name: | ConditionalReadStatus
Title: | ConditionalReadStatus
Definition: | A code that indicates how the server supports conditional read.
Committee: | FHIR Infrastructure Work Group
OID: | 2.16.840.1.113883.4.642.4.201 (for OID based terminology systems)
Source Resource | XML / JSON

This Code system is used in the following value sets:

• ValueSet: ConditionalReadStatus (A code that indicates how the server supports conditional read.)

• ValueSet: ConditionalReadStatus (A code that indicates how the server supports conditional read.)

4.3.14.151.1 Content

4.3.14.151.2 ConditionalReadStatus

A code that indicates how the server supports conditional read.

This code system http://hl7.org/fhir/conditional-read-status defines the following codes:

Code | Display | Definition
not-supported | Not Supported | No support for conditional reads.
modified-since | If-Modified-Since | Conditional reads are supported, but only with the If-Modified-Since HTTP Header.
not-match | If-None-Match | Conditional reads are supported, but only with the If-None-Match HTTP Header.

full-support | Full Support | Conditional reads are supported, with both If-Modified-Since and If-None-Match HTTP Headers.

See the full registry of code systems defined as part of FHIR.

Explanation of the columns that may appear on this page:

Level | A few code lists that FHIR defines are hierarchical - each code is assigned a level. See Code System for further information.
Source | The source of the definition of the code (when the value set draws in codes defined elsewhere)
Code | The code (used as the code in the resource instance). If the code is in italics, this indicates that the code is not selectable ('Abstract')
Display | The display (used in the display element of a Coding). If there is no display, implementers should not simply display the code, but map the concept into their application
Definition | An explanation of the meaning of the concept
Comments | Additional notes about how to use the code

4.3.14.152 Code System http://terminology.hl7.org/CodeSystem/definition-use

URL: https://hl7.org/fhir/R4/codesystem-definition-use.html
FHIR Infrastructure Work Group | Maturity Level: N | Normative (from v4.0.0) | Use Context: Any

| This page has been approved as part of an ANSI standard. See the Conformance Package for further details.

This is a code system defined by the FHIR project.

Summary

Defining URL: | http://terminology.hl7.org/CodeSystem/definition-use
Version: | 4.0.1
Name: | DefinitionUseCodes
Title: | Structure Definition Use Codes / Keywords
Definition: | Structure Definition Use Codes / Keywords
Committee: | FHIR Infrastructure Work Group
OID: | 2.16.840.1.113883.4.642.4.1191 (for OID based terminology systems)
Source Resource | XML / JSON

This Code system is used in the following value sets:

• ValueSet: Structure Definition Use Codes / Keywords (Structure Definition Use Codes / Keywords)
• ValueSet: Structure Definition Use Codes / Keywords (Structure Definition Use Codes / Keywords)

4.3.14.152.1 Content

4.3.14.152.2 Structure Definition Use Codes / Keywords

Structure Definition Use Codes / Keywords

This code system http://terminology.hl7.org/CodeSystem/definition-use defines the following codes:

Code | Display | Definition
fhir-structure | FHIR Structure | This structure is defined as part of the base FHIR Specification
custom-resource | Custom Resource | This structure is intended to be treated like a FHIR resource (e.g. on the FHIR API)
dam | Domain Analysis Model | This structure captures an analysis of a domain
wire-format | Wire Format | This structure represents and existing structure (e.g. CDA, HL7 v2)
archetype | Domain Analysis Model | This structure captures an analysis of a domain
template | Template | This structure is a template (n.b: 'template' has many meanings)

See the full registry of code systems defined as part of FHIR.

Explanation of the columns that may appear on this page:

Level | A few code lists that FHIR defines are hierarchical - each code is assigned a level. See Code System for further information.
Source | The source of the definition of the code (when the value set draws in codes defined elsewhere)
Code | The code (used as the code in the resource instance). If the code is in italics, this indicates that the code is not selectable ('Abstract')
Display | The display (used in the display element of a Coding). If there is no display, implementers should not simply display the code, but map the concept into their application
Definition | An explanation of the meaning of the concept
Comments | Additional notes about how to use the code

4.3.14.153 Code System http://hl7.org/fhir/product-storage-scale

URL: https://hl7.org/fhir/R4/codesystem-product-storage-scale.html
Orders and Observations Work Group | Maturity Level: 0 | Trial Use | Use Context: Any

This is a code system defined by the FHIR project.

Summary

Defining URL: | http://hl7.org/fhir/product-storage-scale

Version: | 4.0.1
Name: | BiologicallyDerivedProductStorageScale
Title: | BiologicallyDerivedProductStorageScale
Definition: | BiologicallyDerived Product Storage Scale.
Committee: | Orders and Observations Work Group
OID: | 2.16.840.1.113883.4.642.4.905 (for OID based terminology systems)
Source Resource | XML / JSON

This Code system is used in the following value sets:

• ValueSet: BiologicallyDerivedProductStorageScale (BiologicallyDerived Product Storage Scale.)

• ValueSet: BiologicallyDerivedProductStorageScale (BiologicallyDerived Product Storage Scale.)

4.3.14.153.1 Content

4.3.14.153.2 BiologicallyDerivedProductStorageScale

BiologicallyDerived Product Storage Scale.

This code system http://hl7.org/fhir/product-storage-scale defines the following codes:

Code | Display | Definition
farenheit | Fahrenheit | Fahrenheit temperature scale.
celsius | Celsius | Celsius or centigrade temperature scale.
kelvin | Kelvin | Kelvin absolute thermodynamic temperature scale.

See the full registry of code systems defined as part of FHIR.

Explanation of the columns that may appear on this page:

Level | A few code lists that FHIR defines are hierarchical - each code is assigned a level. See Code System for further information.
Source | The source of the definition of the code (when the value set draws in codes defined elsewhere)
Code | The code (used as the code in the resource instance). If the code is in italics, this indicates that the code is not selectable ('Abstract')
Display | The display (used in the display element of a Coding). If there is no display, implementers should not simply display the code, but map the concept into their application
Definition | An explanation of the meaning of the concept
Comments | Additional notes about how to use the code

4.3.14.154 Code System http://hl7.org/fhir/ex-udi

URL: https://hl7.org/fhir/R4/codesystem-udi.html
Vocabulary Work Group | Maturity Level: 0 | Informative | Use Context: Any

This is a code system defined by the FHIR project.

Summary

Defining URL: | http://hl7.org/fhir/ex-udi
Version: | 4.0.1
Name: | UDICodes
Title: | UDI Codes
Definition: | This value set includes sample UDI codes.
Committee: | ??
OID: | 2.16.840.1.113883.4.642.4.555 (for OID based terminology systems)
Copyright: | This is an example set.
Source Resource | XML / JSON

This Code system is used in the following value sets:

• ValueSet: UDI Codes (This value set includes sample UDI codes.)

• ValueSet: UDI Codes (This value set includes sample UDI codes.)

4.3.14.154.1 Content

4.3.14.154.2 UDI Codes

This value set includes sample UDI codes.

Copyright Statement:

This is an example set.

This code system http://hl7.org/fhir/ex-udi defines the following codes:

Code | Display | Definition
gudid | GUDID (FDA) | GUDID (FDA) US Repository

See the full registry of code systems defined as part of FHIR.

Explanation of the columns that may appear on this page:

Level | A few code lists that FHIR defines are hierarchical - each code is assigned a level. See Code System for further information.
Source | The source of the definition of the code (when the value set draws in codes defined elsewhere)

Code | The code (used as the code in the resource instance). If the code is in italics, this indicates that the code is not selectable ('Abstract')
Display | The display (used in the display element of a Coding). If there is no display, implementers should not simply display the code, but map the concept into their application
Definition | An explanation of the meaning of the concept
Comments | Additional notes about how to use the code

4.3.14.155 Code System http://hl7.org/fhir/account-status

URL: https://hl7.org/fhir/R4/codesystem-account-status.html
Patient Administration Work Group | Maturity Level: 2 | Trial Use | Use Context: Any

This is a code system defined by the FHIR project.

Summary

Defining URL: | http://hl7.org/fhir/account-status
Version: | 4.0.1
Name: | AccountStatus
Title: | AccountStatus
Definition: | Indicates whether the account is available to be used.
Committee: | Patient Administration Work Group
OID: | 2.16.840.1.113883.4.642.4.727 (for OID based terminology systems)
Source Resource | XML / JSON

This Code system is used in the following value sets:

• ValueSet: AccountStatus (Indicates whether the account is available to be used.)
• ValueSet: AccountStatus (Indicates whether the account is available to be used.)

4.3.14.155.1 Content

4.3.14.155.2 AccountStatus

Indicates whether the account is available to be used.

This code system http://hl7.org/fhir/account-status defines the following codes:

Code | Display | Definition
active | Active | This account is active and may be used.
inactive | Inactive | This account is inactive and should not be used to track financial information.
entered-in-error | Entered in error | This instance should not have been part of this patient's medical record.
on-hold | On Hold | This account is on hold.
unknown | Unknown | The account status is unknown.

See the full registry of code systems defined as part of FHIR.

Explanation of the columns that may appear on this page:

Level | A few code lists that FHIR defines are hierarchical - each code is assigned a level. See Code System for further information.
Source | The source of the definition of the code (when the value set draws in codes defined elsewhere)
Code | The code (used as the code in the resource instance). If the code is in italics, this indicates that the code is not selectable ('Abstract')
Display | The display (used in the display element of a Coding). If there is no display, implementers should not simply display the code, but map the concept into their application
Definition | An explanation of the meaning of the concept
Comments | Additional notes about how to use the code

4.3.14.156 Code System http://terminology.hl7.org/CodeSystem/benefit-term

URL: https://hl7.org/fhir/R4/codesystem-benefit-term.html
Financial Management Work Group | Maturity Level: 1 | Draft | Use Context: Any

This is a code system defined by the FHIR project.

Summary

Defining URL: | http://terminology.hl7.org/CodeSystem/benefit-term
Version: | 4.0.1
Name: | BenefitTermCodes
Title: | Benefit Term Codes
Definition: | This value set includes a smattering of Benefit Term codes.
Committee: | Financial Management Work Group
OID: | 2.16.840.1.113883.4.642.4.1179 (for OID based terminology systems)
Copyright: | This is an example set.
Source Resource | XML / JSON

This Code system is used in the following value sets:

• ValueSet: Benefit Term Codes (This value set includes a smattering of Benefit Term codes.)

• ValueSet: Benefit Term Codes (This value set includes a smattering of Benefit Term codes.)

4.3.14.156.1 Content

4.3.14.156.2 Benefit Term Codes

This value set includes a smattering of Benefit Term codes.

Copyright Statement:

This is an example set.

This code system http://terminology.hl7.org/CodeSystem/benefit-term defines the following codes:

Code | Display | Definition
annual | Annual | Annual, renewing on the anniversary
day | Day | Per day
lifetime | Lifetime | For the total term, lifetime, of the policy or coverage

See the full registry of code systems defined as part of FHIR.

Explanation of the columns that may appear on this page:

Level | A few code lists that FHIR defines are hierarchical - each code is assigned a level. See Code System for further information.
Source | The source of the definition of the code (when the value set draws in codes defined elsewhere)
Code | The code (used as the code in the resource instance). If the code is in italics, this indicates that the code is not selectable ('Abstract')
Display | The display (used in the display element of a Coding). If there is no display, implementers should not simply display the code, but map the concept into their application
Definition | An explanation of the meaning of the concept
Comments | Additional notes about how to use the code

4.3.14.157 Code System http://hl7.org/fhir/data-types

URL: https://hl7.org/fhir/R4/codesystem-data-types.html
FHIR Infrastructure Work Group | Maturity Level: N | Normative (from v4.0.0) | Use Context: Any

| This page has been approved as part of an ANSI standard. See the Conformance Package for further details.

This is a code system defined by the FHIR project.

Summary

Defining URL: | http://hl7.org/fhir/data-types
Version: | 4.0.1
Name: | DataType
Title: | DataType
Definition: | A version specific list of the data types defined by the FHIR specification for use as an element type (any of the FHIR defined data types).
Committee: | FHIR Infrastructure Work Group
OID: | (for OID based terminology systems)
Source Resource | XML / JSON

This Code System is normative - it is generated based on the information defined in this specification. The definition will remain fixed across versions, but the actual contents will change from version to version

This Code system is used in the following value sets:

• ValueSet: FHIRDefinedType (A list of all the concrete types defined in this version of the FHIR specification - Data Types and Resource Types.)

• ValueSet: FHIRAllTypes (A list of all the concrete types defined in this version of the FHIR specification - Abstract Types, Data Types and Resource Types.)

• ValueSet: FHIRAllTypes (A list of all the concrete types defined in this version of the FHIR specification - Abstract Types, Data Types and Resource Types.)

• ValueSet: DataType (A version specific list of the data types defined by the FHIR specification for use as an element type (any of the FHIR defined data types).)

• ValueSet: DataType (A version specific list of the data types defined by the FHIR specification for use as an element type (any of the FHIR defined data types).)

• ValueSet: FHIRDefinedType (A list of all the concrete types defined in this version of the FHIR specification - Data Types and Resource Types.)

4.3.14.157.1 Content

4.3.14.157.2 DataType

A version specific list of the data types defined by the FHIR specification for use as an element type (any of the FHIR defined data types).

This code system http://hl7.org/fhir/data-types defines the following codes:

Code | Display | Definition | Comments
Address | Address | An address expressed using postal conventions (as opposed to GPS or other location definition formats). This data type may be used to convey addresses for use in delivering mail as well as for visiting locations which might not be valid for mail delivery. There are a variety of postal address formats defined around the world.
Age | Age | A duration of time during which an organism (or a process) has existed.
Annotation | Annotation | A text note which also contains information about who made the statement and when.
Attachment | Attachment | For referring to data content defined in other formats.
BackboneElement | BackboneElement | Base definition for all elements that are defined inside a resource - but not those in a data type.
CodeableConcept | CodeableConcept | A concept that may be defined by a formal reference to a terminology or ontology or may be provided by text.
Coding | Coding | A reference to a code defined by a terminology system.
ContactDetail | ContactDetail | Specifies contact information for a person or organization.
ContactPoint | ContactPoint | Details for all kinds of technology mediated contact points for a person or organization, including telephone, email, etc.
Contributor | Contributor | A contributor to the content of a knowledge asset, including authors, editors, reviewers, and endorsers.
Count | Count | A measured amount (or an amount that can potentially be measured). Note that measured amounts include amounts that are not precisely quantified, including amounts involving arbitrary units and floating currencies.
DataRequirement | DataRequirement | Describes a required data item for evaluation in terms of the type of data, and optional code or date-based filters of the data.
Distance | Distance | A length - a value with a unit that is a physical distance.
Dosage | Dosage | Indicates how the medication is/was taken or should be taken by the patient.
Duration | Duration | A length of time.
Element | Element | Base definition for all elements in a resource.
ElementDefinition | ElementDefinition | Captures constraints on each element within the resource, profile, or extension.
Expression | Expression | A expression that is evaluated in a specified context and returns a value. The context of use of the expression must specify the context in which the expression is evaluated, and how the result of the expression is used.
Extension | Extension | Optional Extension Element - found in all resources.
HumanName | HumanName | A human's name with the ability to identify parts and usage.
Identifier | Identifier | An identifier - identifies some entity uniquely and unambiguously. Typically this is used for business identifiers.
MarketingStatus | MarketingStatus | The marketing status describes the date when a medicinal product is actually put on the market or the date as of which it is no longer available.
Meta | Meta | The metadata about a resource. This is content in the resource that is maintained by the infrastructure. Changes to the content might not always be associated with version changes to the resource.
Money | Money | An amount of economic utility in some recognized currency.
MoneyQuantity | MoneyQuantity
Narrative | Narrative | A human-readable summary of the resource conveying the essential clinical and business information for the resource.
ParameterDefinition | ParameterDefinition | The parameters to the module. This collection specifies both the input and output parameters. Input parameters are provided by the caller as part of the $evaluate operation. Output parameters are included in the GuidanceResponse.
Period | Period | A time period defined by a start and end date and optionally time.
Population | Population | A populatioof people with some set of grouping criteria.
ProdCharacteristic | ProdCharacteristic | The marketing status describes the date when a medicinal product is actually put on the market or the date as of which it is no longer available.
ProductShelfLife | ProductShelfLife | The shelf-life and storage information for a medicinal product item or container can be described using this class.
Quantity | Quantity | A measured amount (or an amount that can potentially be measured). Note that measured amounts include amounts that are not precisely quantified, including amounts involving arbitrary units and floating currencies.
Range | Range | A set of ordered Quantities defined by a low and high limit.
Ratio | Ratio | A relationship of two Quantity values - expressed as a numerator and a denominator.
Reference | Reference | A reference from one resource to another.
RelatedArtifact | RelatedArtifact | Related artifacts such as additional documentation, justification, or bibliographic references.
SampledData | SampledData | A series of measurements taken by a device, with upper and lower limits. There may be more than one dimension in the data.
Signature | Signature | A signature along with supporting context. The signature may be a digital signature that is cryptographic in nature, or some other signature acceptable to the domain. This other signature may be as simple as a graphical image representing a hand-written signature, or a signature ceremony Different signature approaches have different utilities.
SimpleQuantity | SimpleQuantity
SubstanceAmount | SubstanceAmount | Chemical substances are a single substance type whose primary defining element is the molecular structure. Chemical substances shall be defined on the basis of their complete covalent molecular structure; the presence of a salt (counter-ion) and/or solvates (water, alcohols) is also captured. Purity, grade, physical form or particle size are not taken into account in the definition of a chemical substance or in the assignment of a Substance ID.
Timing | Timing | Specifies an event that may occur multiple times. Timing schedules are used to record when things are planned, expected or requested to occur. The most common usage is in dosage instructions for medications. They are also used when planning care of various kinds, and may be used for reporting the schedule to which past regular activities were carried out.
TriggerDefinition | TriggerDefinition | A description of a triggering event. Triggering events can be named events, data events, or periodic, as determined by the type element.
UsageContext | UsageContext | Specifies clinical/business/etc. metadata that can be used to retrieve, index and/or categorize an artifact. This metadata can either be specific to the applicable population (e.g., age category, DRG) or the specific context of care (e.g., venue, care setting, provider of care).
base64Binary | base64Binary | A stream of bytes
boolean | boolean | Value of "true" or "false"
canonical | canonical | A URI that is a reference to a canonical URL on a FHIR resource

code | code | A string which has at least one character and no leading or trailing whitespace and where there is no whitespace other than single spaces in the contents
date | date | A date or partial date (e.g. just year or year + month). There is no time zone. The format is a union of the schema types gYear, gYearMonth and date. Dates SHALL be valid dates.
dateTime | dateTime | A date, date-time or partial date (e.g. just year or year + month). If hours and minutes are specified, a time zone SHALL be populated. The format is a union of the schema types gYear, gYearMonth, date and dateTime. Seconds must be provided due to schema type constraints but may be zero-filled and may be ignored. Dates SHALL be valid dates.
decimal | decimal | A rational number with implicit precision
id | id | Any combination of letters, numerals, "-" and ".", with a length limit of 64 characters. (This might be an integer, an unprefixed OID, UUID or any other identifier pattern that meets these constraints.) Ids are case-insensitive.
instant | instant | An instant in time - known at least to the second
integer | integer | A whole number
markdown | markdown | A string that may contain Github Flavored Markdown syntax for optional processing by a mark down presentation engine
oid | oid | An OID represented as a URI
positiveInt | positiveInt | An integer with a value that is positive (e.g. >0)
string | string | A sequence of Unicode characters
time | time | A time during the day, with no date specified
unsignedInt | unsignedInt | An integer with a value that is not negative (e.g. >= 0)
uri | uri | String of characters used to identify a name or a resource
url | url | A URI that is a literal reference
uuid | uuid | A UUID, represented as a URI
xhtml | XHTML | XHTML format, as defined by W3C, but restricted usage (mainly, no active content) | Special case: xhtml can only be used in the narrative Data Type

See the full registry of code systems defined as part of FHIR.

Explanation of the columns that may appear on this page:

Level | A few code lists that FHIR defines are hierarchical - each code is assigned a level. See Code System for further information.
Source | The source of the definition of the code (when the value set draws in codes defined elsewhere)
Code | The code (used as the code in the resource instance). If the code is in italics, this indicates that the code is not selectable ('Abstract')
Display | The display (used in the display element of a Coding). If there is no display, implementers should not simply display the code, but map the concept into their application
Definition | An explanation of the meaning of the concept
Comments | Additional notes about how to use the code

4.3.14.158 Code System http://hl7.org/fhir/questionnaire-answers-status

URL: https://hl7.org/fhir/R4/codesystem-questionnaire-answers-status.html
FHIR Infrastructure Work Group | Maturity Level: 3 | Trial Use | Use Context: Any

This is a code system defined by the FHIR project.

Summary

Defining URL: | http://hl7.org/fhir/questionnaire-answers-status
Version: | 4.0.1
Name: | QuestionnaireResponseStatus
Title: | QuestionnaireResponseStatus
Definition: | Lifecycle status of the questionnaire response.
Committee: | FHIR Infrastructure Work Group
OID: | 2.16.840.1.113883.4.642.4.448 (for OID based terminology systems)
Source Resource | XML / JSON

This Code system is used in the following value sets:

• ValueSet: QuestionnaireResponseStatus (Lifecycle status of the questionnaire response.)
• ValueSet: QuestionnaireResponseStatus (Lifecycle status of the questionnaire response.)

4.3.14.158.1 Content

4.3.14.158.2 QuestionnaireResponseStatus

Lifecycle status of the questionnaire response.

This code system http://hl7.org/fhir/questionnaire-answers-status defines the following codes:

Code | Display | Definition
in-progress | In Progress | This QuestionnaireResponse has been partially filled out with answers but changes or additions are still expected to be made to it.
completed | Completed | This QuestionnaireResponse has been filled out with answers and the current content is regarded as definitive.
amended | Amended | This QuestionnaireResponse has been filled out with answers, then marked as complete, yet changes or additions have been made to it afterwards.
entered-in-error | Entered in Error | This QuestionnaireResponse was entered in error and voided.

stopped | Stopped | This QuestionnaireResponse has been partially filled out with answers but has been abandoned. It is unknown whether changes or additions are expected to be made to it.

See the full registry of code systems defined as part of FHIR.

Explanation of the columns that may appear on this page:

Level | A few code lists that FHIR defines are hierarchical - each code is assigned a level. See Code System for further information.
Source | The source of the definition of the code (when the value set draws in codes defined elsewhere)
Code | The code (used as the code in the resource instance). If the code is in italics, this indicates that the code is not selectable ('Abstract')
Display | The display (used in the display element of a Coding). If there is no display, implementers should not simply display the code, but map the concept into their application
Definition | An explanation of the meaning of the concept
Comments | Additional notes about how to use the code

4.3.14.159 Code System http://hl7.org/fhir/research-study-status

URL: https://hl7.org/fhir/R4/codesystem-research-study-status.html
Biomedical Research and Regulation Work Group | Maturity Level: 1 | Trial Use | Use Context: Any

This is a code system defined by the FHIR project.

Summary

Defining URL: | http://hl7.org/fhir/research-study-status
Version: | 4.0.1
Name: | ResearchStudyStatus
Title: | ResearchStudyStatus
Definition: | Codes that convey the current status of the research study.
Committee: | Biomedical Research and Regulation Work Group
OID: | 2.16.840.1.113883.4.642.4.820 (for OID based terminology systems)
Source Resource | XML / JSON

This Code system is used in the following value sets:

• ValueSet: ResearchStudyStatus (Codes that convey the current status of the research study.)

• ValueSet: ResearchStudyStatus (Codes that convey the current status of the research study.)

4.3.14.159.1 Content

4.3.14.159.2 ResearchStudyStatus

Codes that convey the current status of the research study.

This code system http://hl7.org/fhir/research-study-status defines the following codes:

Code | Display | Definition
active | Active | Study is opened for accrual.
administratively-completed | Administratively Completed | Study is completed prematurely and will not resume; patients are no longer examined nor treated.
approved | Approved | Protocol is approved by the review board.
closed-to-accrual | Closed to Accrual | Study is closed for accrual; patients can be examined and treated.
closed-to-accrual-and-intervention | Closed to Accrual and Intervention | Study is closed to accrual and intervention, i.e. the study is closed to enrollment, all study subjects have completed treatment or intervention but are still being followed according to the primary objective of the study.
completed | Completed | Study is closed to accrual and intervention, i.e. the study is closed to enrollment, all study subjects have completed treatment or intervention but are still being followed according to the primary objective of the study.
disapproved | Disapproved | Protocol was disapproved by the review board.
in-review | In Review | Protocol is submitted to the review board for approval.
temporarily-closed-to-accrual | Temporarily Closed to Accrual | Study is temporarily closed for accrual; can be potentially resumed in the future; patients can be examined and treated.
temporarily-closed-to-accrual-and-intervention | Temporarily Closed to Accrual and Intervention | Study is temporarily closed for accrual and intervention and potentially can be resumed in the future.
withdrawn | Withdrawn | Protocol was withdrawn by the lead organization.

See the full registry of code systems defined as part of FHIR.

Explanation of the columns that may appear on this page:

Level | A few code lists that FHIR defines are hierarchical - each code is assigned a level. See Code System for further information.
Source | The source of the definition of the code (when the value set draws in codes defined elsewhere)
Code | The code (used as the code in the resource instance). If the code is in italics, this indicates that the code is not selectable ('Abstract')
Display | The display (used in the display element of a Coding). If there is no display, implementers should not simply display the code, but map the concept into their application
Definition | An explanation of the meaning of the concept
Comments | Additional notes about how to use the code

4.3.14.160 Code System http://hl7.org/fhir/address-use

URL: https://hl7.org/fhir/R4/codesystem-address-use.html
FHIR Infrastructure Work Group | Maturity Level: N | Normative (from v4.0.0) | Use Context: Any

This is a code system defined by the FHIR project.

Summary

Defining URL: | http://hl7.org/fhir/address-use
Version: | 4.0.1
Name: | AddressUse
Title: | AddressUse
Definition: | The use of an address.
Committee: | FHIR Infrastructure Work Group
OID: | 2.16.840.1.113883.4.642.4.68 (for OID based terminology systems)
Source Resource | XML / JSON

This Code system is used in the following value sets:

• ValueSet: AddressUse (The use of an address.)

• ValueSet: AddressUse (The use of an address.)

4.3.14.160.1 Content

4.3.14.160.2 AddressUse

The use of an address.

This code system http://hl7.org/fhir/address-use defines the following codes:

Code | Display | Definition
home | Home | A communication address at a home.
work | Work | An office address. First choice for business related contacts during business hours.
temp | Temporary | A temporary address. The period can provide more detailed information.
old | Old / Incorrect | This address is no longer in use (or was never correct but retained for records).
billing | Billing | An address to be used to send bills, invoices, receipts etc.

See the full registry of code systems defined as part of FHIR.

Explanation of the columns that may appear on this page:

Level | A few code lists that FHIR defines are hierarchical - each code is assigned a level. See Code System for further information.
Source | The source of the definition of the code (when the value set draws in codes defined elsewhere)
Code | The code (used as the code in the resource instance). If the code is in italics, this indicates that the code is not selectable ('Abstract')
Display | The display (used in the display element of a Coding). If there is no display, implementers should not simply display the code, but map the concept into their application
Definition | An explanation of the meaning of the concept
Comments | Additional notes about how to use the code

4.3.14.161 Code System http://hl7.org/fhir/CodeSystem/medicationrequest-status

URL: https://hl7.org/fhir/R4/codesystem-medicationrequest-status.html
Pharmacy Work Group | Maturity Level: 3 | Trial Use | Use Context: Any

This is a code system defined by the FHIR project.

Summary

Defining URL: | http://hl7.org/fhir/CodeSystem/medicationrequest-status
Version: | 4.0.1
Name: | medicationrequest Status
Title: | Medicationrequest status
Definition: | MedicationRequest Status Codes
Committee: | Pharmacy Work Group
OID: | 2.16.840.1.113883.4.642.4.1377 (for OID based terminology systems)
Source Resource | XML / JSON

This Code system is used in the following value sets:

• ValueSet: Medicationrequest status (MedicationRequest Status Codes)

• ValueSet: Medicationrequest status (MedicationRequest Status Codes)

4.3.14.161.1 Content

4.3.14.161.2 Medicationrequest status

MedicationRequest Status Codes

This code system http://hl7.org/fhir/CodeSystem/medicationrequest-status defines the following codes:

Code | Display | Definition
active | Active | The prescription is 'actionable', but not all actions that are implied by it have occurred yet.
on-hold | On Hold | Actions implied by the prescription are to be temporarily halted, but are expected to continue later. May also be called 'suspended'.
cancelled | Cancelled | The prescription has been withdrawn before any administrations have occurred
completed | Completed | All actions that are implied by the prescription have occurred.
entered-in-error | Entered in Error | Some of the actions that are implied by the medication request may have occurred. For example, the medication may have been dispensed and the patient may have taken some of the medication. Clinical decision support systems should take this status into account
stopped | Stopped | Actions implied by the prescription are to be permanently halted, before all of the administrations occurred. This should not be used if the original order was entered in error
draft | Draft | The prescription is not yet 'actionable', e.g. it is a work in progress, requires sign-off, verification or needs to be run through decision support process.
unknown | Unknown | The authoring/source system does not know which of the status values currently applies for this observation. Note: This concept is not to be used for 'other' - one of the listed statuses is presumed to apply, but the authoring/source system does not know which.

See the full registry of code systems defined as part of FHIR.

Explanation of the columns that may appear on this page:

Level | A few code lists that FHIR defines are hierarchical - each code is assigned a level. See Code System for further information.
Source | The source of the definition of the code (when the value set draws in codes defined elsewhere)
Code | The code (used as the code in the resource instance). If the code is in italics, this indicates that the code is not selectable ('Abstract')
Display | The display (used in the display element of a Coding). If there is no display, implementers should not simply display the code, but map the concept into their application
Definition | An explanation of the meaning of the concept
Comments | Additional notes about how to use the code

4.3.14.162 Code System http://terminology.hl7.org/CodeSystem/participant-type

URL: https://hl7.org/fhir/R4/codesystem-encounter-participant-type.html
Patient Administration Work Group | Maturity Level: 3 | Trial Use | Use Context: Any

This is a code system defined by the FHIR project.

Summary

Defining URL: | http://terminology.hl7.org/CodeSystem/participant-type
Version: | 4.0.1
Name: | ParticipantType
Title: | Participant type
Definition: | This value set defines a set of codes that can be used to indicate how an individual participates in an encounter.
Committee: | Patient Administration Work Group
OID: | 2.16.840.1.113883.4.642.4.1089 (for OID based terminology systems)
Source Resource | XML / JSON

This Code system is used in the following value sets:

• ValueSet: Participant type (This value set defines a set of codes that can be used to indicate how an individual participates in an encounter.)

• ValueSet: Participant type (This value set defines a set of codes that can be used to indicate how an individual participates in an encounter.)

4.3.14.162.1 Content

4.3.14.162.2 Participant type

This value set defines a set of codes that can be used to indicate how an individual participates in an encounter.

This code system http://terminology.hl7.org/CodeSystem/participant-type defines the following codes:

Code | Display | Definition
translator | Translator | A translator who is facilitating communication with the patient during the encounter.
emergency | Emergency | A person to be contacted in case of an emergency during the encounter.

See the full registry of code systems defined as part of FHIR.

Explanation of the columns that may appear on this page:

Level | A few code lists that FHIR defines are hierarchical - each code is assigned a level. See Code System for further information.
Source | The source of the definition of the code (when the value set draws in codes defined elsewhere)
Code | The code (used as the code in the resource instance). If the code is in italics, this indicates that the code is not selectable ('Abstract')
Display | The display (used in the display element of a Coding). If there is no display, implementers should not simply display the code, but map the concept into their application

Definition | An explanation of the meaning of the concept
Comments | Additional notes about how to use the code

4.3.14.163 Code System http://terminology.hl7.org/CodeSystem/history-absent-reason

URL: https://hl7.org/fhir/R4/codesystem-history-absent-reason.html
Patient Care Work Group | Maturity Level: 1 | Draft | Use Context: Any

This is a code system defined by the FHIR project.

Summary

Defining URL: | http://terminology.hl7.org/CodeSystem/history-absent-reason
Version: | 4.0.1
Name: | FamilyHistoryAbsentReason
Title: | FamilyHistoryAbsentReason
Definition: | Codes describing the reason why a family member's history is not available.
Committee: | Patient Care Work Group
OID: | 2.16.840.1.113883.4.642.4.1094 (for OID based terminology systems)
Source Resource | XML / JSON

This Code system is used in the following value sets:

• ValueSet: FamilyHistoryAbsentReason (Codes describing the reason why a family member's history is not available.)

• ValueSet: FamilyHistoryAbsentReason (Codes describing the reason why a family member's history is not available.)

4.3.14.163.1 Content

4.3.14.163.2 FamilyHistoryAbsentReason

Codes describing the reason why a family member's history is not available.

This code system http://terminology.hl7.org/CodeSystem/history-absent-reason defines the following codes:

Code | Display | Definition
subject-unknown | Subject Unknown | Patient does not know the subject, e.g. the biological parent of an adopted patient.
withheld | Information Withheld | The patient withheld or refused to share the information.
unable-to-obtain | Unable To Obtain | Information cannot be obtained; e.g. unconscious patient.
deferred | Deferred | Patient does not have the information now, but can provide the information at a later date.

See the full registry of code systems defined as part of FHIR.

Explanation of the columns that may appear on this page:

Level | A few code lists that FHIR defines are hierarchical - each code is assigned a level. See Code System for further information.
Source | The source of the definition of the code (when the value set draws in codes defined elsewhere)
Code | The code (used as the code in the resource instance). If the code is in italics, this indicates that the code is not selectable ('Abstract')
Display | The display (used in the display element of a Coding). If there is no display, implementers should not simply display the code, but map the concept into their application
Definition | An explanation of the meaning of the concept
Comments | Additional notes about how to use the code

4.3.14.164 Code System http://hl7.org/fhir/trigger-type

URL: https://hl7.org/fhir/R4/codesystem-trigger-type.html
FHIR Infrastructure Work Group | Maturity Level: 5 | Trial Use | Use Context: Any

This is a code system defined by the FHIR project.

Summary

Defining URL: | http://hl7.org/fhir/trigger-type
Version: | 4.0.1
Name: | TriggerType
Title: | TriggerType
Definition: | The type of trigger.
Committee: | FHIR Infrastructure Work Group
OID: | 2.16.840.1.113883.4.642.4.104 (for OID based terminology systems)
Source Resource | XML / JSON

This Code system is used in the following value sets:

• ValueSet: TriggerType (The type of trigger.)

• ValueSet: TriggerType (The type of trigger.)

4.3.14.164.1 Content

4.3.14.164.2 TriggerType

The type of trigger.

This code system http://hl7.org/fhir/trigger-type defines the following codes:

Lvl | Code | Display | Definition
1 | named-event | Named Event | The trigger occurs in response to a specific named event, and no other information about the trigger is specified. Named events are completely pre-coordinated, and the formal semantics of the trigger are not provided.
1 | periodic | Periodic | The trigger occurs at a specific time or periodically as described by a timing or schedule. A periodic event cannot have any data elements, but may have a name assigned as a shorthand for the event.
1 | data-changed | Data Changed | The trigger occurs whenever data of a particular type is changed in any way, either added, modified, or removed.
2 | data-added | Data Added | The trigger occurs whenever data of a particular type is added.
2 | data-modified | Data Updated | The trigger occurs whenever data of a particular type is modified.
2 | data-removed | Data Removed | The trigger occurs whenever data of a particular type is removed.
1 | data-accessed | Data Accessed | The trigger occurs whenever data of a particular type is accessed.
1 | data-access-ended | Data Access Ended | The trigger occurs whenever access to data of a particular type is completed.

See the full registry of code systems defined as part of FHIR.

Explanation of the columns that may appear on this page:

Level | A few code lists that FHIR defines are hierarchical - each code is assigned a level. See Code System for further information.
Source | The source of the definition of the code (when the value set draws in codes defined elsewhere)
Code | The code (used as the code in the resource instance). If the code is in italics, this indicates that the code is not selectable ('Abstract')
Display | The display (used in the display element of a Coding). If there is no display, implementers should not simply display the code, but map the concept into their application
Definition | An explanation of the meaning of the concept
Comments | Additional notes about how to use the code

4.3.14.165 Code System http://terminology.hl7.org/CodeSystem/ex-diagnosistype

URL: https://hl7.org/fhir/R4/codesystem-ex-diagnosistype.html
Financial Management Work Group | Maturity Level: 1 | Draft | Use Context: Any

This is a code system defined by the FHIR project.

Summary

Defining URL: | http://terminology.hl7.org/CodeSystem/ex-diagnosistype
Version: | 4.0.1
Name: | ExampleDiagnosisTypeCodes
Title: | Example Diagnosis Type Codes
Definition: | This value set includes example Diagnosis Type codes.
Committee: | Financial Management Work Group
OID: | 2.16.840.1.113883.4.642.4.1167 (for OID based terminology systems)
Copyright: | This is an example set.
Source Resource | XML / JSON

This Code system is used in the following value sets:

• ValueSet: Example Diagnosis Type Codes (This value set includes example Diagnosis Type codes.)

• ValueSet: Example Diagnosis Type Codes (This value set includes example Diagnosis Type codes.)

4.3.14.165.1 Content

4.3.14.165.2 Example Diagnosis Type Codes

This value set includes example Diagnosis Type codes.

Copyright Statement:

This is an example set.

This code system http://terminology.hl7.org/CodeSystem/ex-diagnosistype defines the following codes:

Code | Display | Definition
admitting | Admitting Diagnosis | The diagnosis given as the reason why the patient was admitted to the hospital.
clinical | Clinical Diagnosis | A diagnosis made on the basis of medical signs and patient-reported symptoms, rather than diagnostic tests.
differential | Differential Diagnosis | One of a set of the possible diagnoses that could be connected to the signs, symptoms, and lab findings.
discharge | Discharge Diagnosis | The diagnosis given when the patient is discharged from the hospital.
laboratory | Laboratory Diagnosis | A diagnosis based significantly on laboratory reports or test results, rather than the physical examination of the patient.
nursing | Nursing Diagnosis | A diagnosis which identifies people's responses to situations in their lives, such as a readiness to change or a willingness to accept assistance.
prenatal | Prenatal Diagnosis | A diagnosis determined prior to birth.

principal | Principal Diagnosis | The single medical diagnosis that is most relevant to the patient's chief complaint or need for treatment.
radiology | Radiology Diagnosis | A diagnosis based primarily on the results from medical imaging studies.
remote | Remote Diagnosis | A diagnosis determined using telemedicine techniques.
retrospective | Retrospective Diagnosis | The labeling of an illness in a specific historical event using modern knowledge, methods and disease classifications.
self | Self Diagnosis | A diagnosis determined by the patient.

See the full registry of code systems defined as part of FHIR.

Explanation of the columns that may appear on this page:

Level | A few code lists that FHIR defines are hierarchical - each code is assigned a level. See Code System for further information.
Source | The source of the definition of the code (when the value set draws in codes defined elsewhere)
Code | The code (used as the code in the resource instance). If the code is in italics, this indicates that the code is not selectable ('Abstract')
Display | The display (used in the display element of a Coding). If there is no display, implementers should not simply display the code, but map the concept into their application
Definition | An explanation of the meaning of the concept
Comments | Additional notes about how to use the code

4.3.14.166 Code System http://hl7.org/fhir/expression-language

URL: https://hl7.org/fhir/R4/codesystem-expression-language.html
FHIR Infrastructure Work Group | Maturity Level: 5 | Trial Use | Use Context: Any

This is a code system defined by the FHIR project.

Summary

Defining URL: | http://hl7.org/fhir/expression-language
Version: | 4.0.1
Name: | ExpressionLanguage
Title: | ExpressionLanguage
Definition: | The media type of the expression language.
Committee: | FHIR Infrastructure Work Group
OID: | 2.16.840.1.113883.4.642.4.106 (for OID based terminology systems)
Source Resource | XML / JSON

This Code system is used in the following value sets:

• ValueSet: ExpressionLanguage (The media type of the expression language.)

• ValueSet: ExpressionLanguage (The media type of the expression language.)

4.3.14.166.1 Content

4.3.14.166.2 ExpressionLanguage

The media type of the expression language.

This code system http://hl7.org/fhir/expression-language defines the following codes:

Code | Display | Definition
text/cql | CQL | Clinical Quality Language.
text/fhirpath | FHIRPath | FHIRPath.
application/x-fhir-query | FHIR Query | FHIR's RESTful query syntax - typically independent of base URL.

See the full registry of code systems defined as part of FHIR.

Explanation of the columns that may appear on this page:

Level | A few code lists that FHIR defines are hierarchical - each code is assigned a level. See Code System for further information.
Source | The source of the definition of the code (when the value set draws in codes defined elsewhere)
Code | The code (used as the code in the resource instance). If the code is in italics, this indicates that the code is not selectable ('Abstract')
Display | The display (used in the display element of a Coding). If there is no display, implementers should not simply display the code, but map the concept into their application
Definition | An explanation of the meaning of the concept
Comments | Additional notes about how to use the code

4.3.14.167 Code System http://hl7.org/fhir/care-plan-activity-status

URL: https://hl7.org/fhir/R4/codesystem-care-plan-activity-status.html
Patient Care Work Group | Maturity Level: 2 | Trial Use | Use Context: Any

This is a code system defined by the FHIR project.

Summary

Defining URL: | http://hl7.org/fhir/care-plan-activity-status
Version: | 4.0.1
Name: | CarePlanActivityStatus
Title: | CarePlanActivityStatus
Definition: | Codes that reflect the current state of a care plan activity within its overall life cycle.
Committee: | Patient Care Work Group
OID: | 2.16.840.1.113883.4.642.4.147 (for OID based terminology systems)
Source Resource | XML / JSON

This Code system is used in the following value sets:

• ValueSet: CarePlanActivityStatus (Codes that reflect the current state of a care plan activity within its overall life cycle.)

• ValueSet: CarePlanActivityStatus (Codes that reflect the current state of a care plan activity within its overall life cycle.)

4.3.14.167.1 Content

4.3.14.167.2 CarePlanActivityStatus

Codes that reflect the current state of a care plan activity within its overall life cycle.

This code system http://hl7.org/fhir/care-plan-activity-status defines the following codes:

Lvl | Code | Display | Definition
1 | not-started | Not Started | Care plan activity is planned but no action has yet been taken.
1 | scheduled | Scheduled | Appointment or other booking has occurred but activity has not yet begun.
1 | in-progress | In Progress | Care plan activity has been started but is not yet complete.
1 | on-hold | On Hold | Care plan activity was started but has temporarily ceased with an expectation of resumption at a future time.
1 | completed | Completed | Care plan activity has been completed (more or less) as planned.
1 | cancelled | Cancelled | The planned care plan activity has been withdrawn.
2 | stopped | Stopped | The planned care plan activity has been ended prior to completion after the activity was started.
1 | unknown | Unknown | The current state of the care plan activity is not known. Note: This concept is not to be used for "other" - one of the listed statuses is presumed to apply, but the authoring/source system does not know which one.
1 | entered-in-error | Entered in Error | Care plan activity was entered in error and voided.

See the full registry of code systems defined as part of FHIR.

Explanation of the columns that may appear on this page:

Level | A few code lists that FHIR defines are hierarchical - each code is assigned a level. See Code System for further information.
Source | The source of the definition of the code (when the value set draws in codes defined elsewhere)
Code | The code (used as the code in the resource instance). If the code is in italics, this indicates that the code is not selectable ('Abstract')
Display | The display (used in the display element of a Coding). If there is no display, implementers should not simply display the code, but map the concept into their application
Definition | An explanation of the meaning of the concept
Comments | Additional notes about how to use the code

4.3.14.168 Code System http://terminology.hl7.org/CodeSystem/FDI-surface

URL: https://hl7.org/fhir/R4/codesystem-surface.html
Financial Management Work Group | Maturity Level: 1 | Draft | Use Context: Any

This is a code system defined by the FHIR project.

Summary

Defining URL: | http://terminology.hl7.org/CodeSystem/FDI-surface
Version: | 4.0.1
Name: | SurfaceCodes
Title: | Surface Codes
Definition: | This value set includes a smattering of FDI tooth surface codes.
Committee: | Financial Management Work Group
OID: | 2.16.840.1.113883.4.642.4.1154 (for OID based terminology systems)
Copyright: | This is an example set.
Source Resource | XML / JSON

This Code system is used in the following value sets:

• ValueSet: Surface Codes (This value set includes a smattering of FDI tooth surface codes.)

• ValueSet: Surface Codes (This value set includes a smattering of FDI tooth surface codes.)

4.3.14.168.1 Content

4.3.14.168.2 Surface Codes

This value set includes a smattering of FDI tooth surface codes.

Copyright Statement:

This is an example set.

This code system http://terminology.hl7.org/CodeSystem/FDI-surface defines the following codes:

Code | Display | Definition
M | Mesial | The surface of a tooth that is closest to the midline (middle) of the face.
O | Occlusal | The chewing surface of posterior teeth.
I | Incisal | The biting edge of anterior teeth.
D | Distal | The surface of a tooth that faces away from the midline of the face.
B | Buccal | The surface of a posterior tooth facing the cheeks.
V | Ventral | The surface of a tooth facing the lips.
L | Lingual | The surface of a tooth facing the tongue.
MO | Mesioclusal | The Mesioclusal surfaces of a tooth.
DO | Distoclusal | The Distoclusal surfaces of a tooth.
DI | Distoincisal | The Distoincisal surfaces of a tooth.
MOD | Mesioclusodistal | The Mesioclusodistal surfaces of a tooth.

See the full registry of code systems defined as part of FHIR.

Explanation of the columns that may appear on this page:

Level | A few code lists that FHIR defines are hierarchical - each code is assigned a level. See Code System for further information.
Source | The source of the definition of the code (when the value set draws in codes defined elsewhere)
Code | The code (used as the code in the resource instance). If the code is in italics, this indicates that the code is not selectable ('Abstract')
Display | The display (used in the display element of a Coding). If there is no display, implementers should not simply display the code, but map the concept into their application
Definition | An explanation of the meaning of the concept
Comments | Additional notes about how to use the code

4.3.14.169 Code System http://terminology.hl7.org/CodeSystem/location-physical-type

URL: https://hl7.org/fhir/R4/codesystem-location-physical-type.html
Patient Administration Work Group | Maturity Level: 1 | Draft | Use Context: Any

This is a code system defined by the FHIR project.

Summary

Defining URL: | http://terminology.hl7.org/CodeSystem/location-physical-type
Version: | 4.0.1
Name: | LocationType
Title: | Location type
Definition: | This example value set defines a set of codes that can be used to indicate the physical form of the Location.
Committee: | Patient Administration Work Group
OID: | 2.16.840.1.113883.4.642.4.1108 (for OID based terminology systems)
Source Resource | XML / JSON

This Code system is used in the following value sets:

• ValueSet: Location type (This example value set defines a set of codes that can be used to indicate the physical form of the Location.)

• ValueSet: Location type (This example value set defines a set of codes that can be used to indicate the physical form of the Location.)

4.3.14.169.1 Content

4.3.14.169.2 Location type

This example value set defines a set of codes that can be used to indicate the physical form of the Location.

This code system http://terminology.hl7.org/CodeSystem/location-physical-type defines the following codes:

Code | Display | Definition
si | Site | A collection of buildings or other locations such as a site or a campus.
bu | Building | Any Building or structure. This may contain rooms, corridors, wings, etc. It might not have walls, or a roof, but is considered a defined/allocated space.
wi | Wing | A Wing within a Building, this often contains levels, rooms and corridors.
wa | Ward | A Ward is a section of a medical facility that may contain rooms and other types of location.
lvl | Level | A Level in a multi-level Building/Structure.
co | Corridor | Any corridor within a Building, that may connect rooms.
ro | Room | A space that is allocated as a room, it may have walls/roof etc., but does not require these.
bd | Bed | A space that is allocated for sleeping/laying on. This is not the physical bed/trolley that may be moved about, but the space it may occupy.
ve | Vehicle | A means of transportation.

ho | House | A residential dwelling. Usually used to reference a location that a person/patient may reside.
ca | Cabinet | A container that can store goods, equipment, medications or other items.
rd | Road | A defined path to travel between 2 points that has a known name.
area | Area | A defined physical boundary of something, such as a flood risk zone, region, postcode
jdn | Jurisdiction | A wide scope that covers a conceptual domain, such as a Nation (Country wide community or Federal Government - e.g. Ministry of Health), Province or State (community or Government), Business (throughout the enterprise), Nation with a business scope of an agency (e.g. CDC, FDA etc.) or a Business segment (UK Pharmacy), not just an physical boundary

See the full registry of code systems defined as part of FHIR.

Explanation of the columns that may appear on this page:

Level | A few code lists that FHIR defines are hierarchical - each code is assigned a level. See Code System for further information.
Source | The source of the definition of the code (when the value set draws in codes defined elsewhere)
Code | The code (used as the code in the resource instance). If the code is in italics, this indicates that the code is not selectable ('Abstract')
Display | The display (used in the display element of a Coding). If there is no display, implementers should not simply display the code, but map the concept into their application
Definition | An explanation of the meaning of the concept
Comments | Additional notes about how to use the code

4.3.14.170 Code System http://terminology.hl7.org/CodeSystem/fundsreserve

URL: https://hl7.org/fhir/R4/codesystem-fundsreserve.html
Financial Management Work Group | Maturity Level: 1 | Draft | Use Context: Not Intended for Production use

This is a code system defined by the FHIR project.

Summary

Defining URL: | http://terminology.hl7.org/CodeSystem/fundsreserve
Version: | 4.0.1
Name: | Funds Reservation Codes
Title:
Definition: | This value set includes sample funds reservation type codes.
Committee: | Financial Management Work Group
OID: | 2.16.840.1.113883.4.642.4.1051 (for OID based terminology systems)
Copyright: | This is an example set.
Source Resource | XML / JSON

This Code system is used in the following value sets:

• ValueSet: FundsReserve (This value set includes sample funds reservation type codes.)

• ValueSet: FundsReserve (This value set includes sample funds reservation type codes.)

4.3.14.170.1 Content

4.3.14.170.2 Funds Reservation Codes

This value set includes sample funds reservation type codes.

Copyright Statement:

This is an example set.

This code system http://terminology.hl7.org/CodeSystem/fundsreserve defines the following codes:

Code | Display | Definition
patient | Patient | The payor is requested to reserve funds for the provision of the named services by any provider for settlement of future claims related to this request.
provider | Provider | The payor is requested to reserve funds solely for the named provider for settlement of future claims related to this request.
none | None | The payor is not being requested to reserve any funds for the settlement of future claims.

See the full registry of code systems defined as part of FHIR.

Explanation of the columns that may appear on this page:

Level | A few code lists that FHIR defines are hierarchical - each code is assigned a level. See Code System for further information.
Source | The source of the definition of the code (when the value set draws in codes defined elsewhere)
Code | The code (used as the code in the resource instance). If the code is in italics, this indicates that the code is not selectable ('Abstract')
Display | The display (used in the display element of a Coding). If there is no display, implementers should not simply display the code, but map the concept into their application
Definition | An explanation of the meaning of the concept
Comments | Additional notes about how to use the code

4.3.14.171 Code System http://hl7.org/fhir/ex-fdi

URL: https://hl7.org/fhir/R4/codesystem-teeth.html

Vocabulary Work Group | Maturity Level: 0 | Informative | Use Context: Any

This is a code system defined by the FHIR project.

Summary

Defining URL: | http://hl7.org/fhir/ex-fdi
Version: | 4.0.1
Name: | TeethCodes
Title: | Teeth Codes
Definition: | This value set includes the FDI Teeth codes.
Committee: | ??
OID: | 2.16.840.1.113883.4.642.4.551 (for OID based terminology systems)
Copyright: | This is an example set.
Source Resource | XML / JSON

This Code system is used in the following value sets:

• ValueSet: Teeth Codes (This value set includes the FDI Teeth codes.)

• ValueSet: Teeth Codes (This value set includes the FDI Teeth codes.)

4.3.14.171.1 Content

4.3.14.171.2 Teeth Codes

This value set includes the FDI Teeth codes.

Copyright Statement:

This is an example set.

This code system http://hl7.org/fhir/ex-fdi defines the following codes:

Code | Display | Definition
11 | 11 | Upper Right Tooth 1 from the central axis, permanent dentition.
12 | 12 | Upper Right Tooth 2 from the central axis, permanent dentition.
13 | 13 | Upper Right Tooth 3 from the central axis, permanent dentition.
14 | 14 | Upper Right Tooth 4 from the central axis, permanent dentition.
15 | 15 | Upper Right Tooth 5 from the central axis, permanent dentition.
16 | 16 | Upper Right Tooth 6 from the central axis, permanent dentition.
17 | 17 | Upper Right Tooth 7 from the central axis, permanent dentition.
18 | 18 | Upper Right Tooth 8 from the central axis, permanent dentition.
21 | 21 | Upper Left Tooth 1 from the central axis, permanent dentition.
22 | 22 | Upper Left Tooth 2 from the central axis, permanent dentition.
23 | 23 | Upper Left Tooth 3 from the central axis, permanent dentition.
24 | 24 | Upper Left Tooth 4 from the central axis, permanent dentition.
25 | 25 | Upper Left Tooth 5 from the central axis, permanent dentition.
26 | 26 | Upper Left Tooth 6 from the central axis, permanent dentition.
27 | 27 | Upper Left Tooth 7 from the central axis, permanent dentition.
28 | 28 | Upper Left Tooth 8 from the central axis, permanent dentition.
31 | 31 | Lower Left Tooth 1 from the central axis, permanent dentition.
32 | 32 | Lower Left Tooth 2 from the central axis, permanent dentition.
33 | 33 | Lower Left Tooth 3 from the central axis, permanent dentition.
34 | 34 | Lower Left Tooth 4 from the central axis, permanent dentition.
35 | 35 | Lower Left Tooth 5 from the central axis, permanent dentition.
36 | 36 | Lower Left Tooth 6 from the central axis, permanent dentition.
37 | 37 | Lower Left Tooth 7 from the central axis, permanent dentition.
38 | 38 | Lower Left Tooth 8 from the central axis, permanent dentition.
41 | 41 | Lower Right Tooth 1 from the central axis, permanent dentition.
42 | 42 | Lower Right Tooth 2 from the central axis, permanent dentition.
43 | 43 | Lower Right Tooth 3 from the central axis, permanent dentition.
44 | 44 | Lower Right Tooth 4 from the central axis, permanent dentition.
45 | 45 | Lower Right Tooth 5 from the central axis, permanent dentition.
46 | 46 | Lower Right Tooth 6 from the central axis, permanent dentition.
47 | 47 | Lower Right Tooth 7 from the central axis, permanent dentition.
48 | 48 | Lower Right Tooth 8 from the central axis, permanent dentition.

See the full registry of code systems defined as part of FHIR.

Explanation of the columns that may appear on this page:

Level | A few code lists that FHIR defines are hierarchical - each code is assigned a level. See Code System for further information.
Source | The source of the definition of the code (when the value set draws in codes defined elsewhere)
Code | The code (used as the code in the resource instance). If the code is in italics, this indicates that the code is not selectable ('Abstract')
Display | The display (used in the display element of a Coding). If there is no display, implementers should not simply display the code, but map the concept into their application
Definition | An explanation of the meaning of the concept
Comments | Additional notes about how to use the code

4.3.14.172 Code System http://terminology.hl7.org/CodeSystem/goal-achievement

URL: https://hl7.org/fhir/R4/codesystem-goal-achievement.html
Patient Care Work Group | Maturity Level: 0 | Informative | Use Context: Any

This is a code system defined at http://www.hl7.org/Special/committees/patientcare/ .

Summary

Defining URL: | http://terminology.hl7.org/CodeSystem/goal-achievement
Version: | 4.0.1
Name: | GoalAchievementStatus
Title: | Goal achievement status
Definition: | Describes the progression, or lack thereof, towards the goal against the target.
Committee: | Patient Care Work Group
OID: | 2.16.840.1.113883.4.642.4.1375 (for OID based terminology systems)
Source Resource | XML / JSON

This Code system is used in the following value sets:

• ValueSet: Goal achievement status (Describes the progression, or lack thereof, towards the goal against the target.)

• ValueSet: Goal achievement status (Describes the progression, or lack thereof, towards the goal against the target.)

4.3.14.172.1 Content

4.3.14.172.2 Goal achievement status

Describes the progression, or lack thereof, towards the goal against the target.

This code system http://terminology.hl7.org/CodeSystem/goal-achievement defines the following codes:

Lvl | Code | Display | Definition
1 | in-progress | In Progress | The goal is being sought but has not yet been reached. (Also applies if the goal was reached in the past but there has been regression and the goal is again being sought).
2 | improving | Improving | The goal is being sought, and is progressing.
2 | worsening | Worsening | The goal is being sought, but is regressing.
2 | no-change | No Change | The goal is being sought, but the trend is flat.
1 | achieved | Achieved | The goal has been met.
2 | sustaining | Sustaining | The goal has been met, but ongoing activity is needed to sustain the goal objective.
1 | not-achieved | Not Achieved | The goal has not been met and there might or might not have been progress towards target.
2 | no-progress | No Progress | The goal has not been met and little to no progress towards target.
2 | not-attainable | Not Attainable | The goal is not possible to be met.

See the full registry of code systems defined as part of FHIR.

Explanation of the columns that may appear on this page:

Level | A few code lists that FHIR defines are hierarchical - each code is assigned a level. See Code System for further information.
Source | The source of the definition of the code (when the value set draws in codes defined elsewhere)
Code | The code (used as the code in the resource instance). If the code is in italics, this indicates that the code is not selectable ('Abstract')
Display | The display (used in the display element of a Coding). If there is no display, implementers should not simply display the code, but map the concept into their application
Definition | An explanation of the meaning of the concept
Comments | Additional notes about how to use the code

4.3.14.173 Code System http://terminology.hl7.org/CodeSystem/adverse-event-severity

URL: https://hl7.org/fhir/R4/codesystem-adverse-event-severity.html
Patient Care Work Group | Maturity Level: 0 | Trial Use | Use Context: Any

This is a code system defined by the FHIR project.

Summary

Defining URL: | http://terminology.hl7.org/CodeSystem/adverse-event-severity
Version: | 4.0.1
Name: | AdverseEventSeverity
Title: | AdverseEventSeverity
Definition: | The severity of the adverse event itself, in direct relation to the subject.
Committee: | Patient Care Work Group
OID: | 2.16.840.1.113883.4.642.4.1256 (for OID based terminology systems)
Source Resource | XML / JSON

This Code system is used in the following value sets:

• ValueSet: AdverseEventSeverity (The severity of the adverse event itself, in direct relation to the subject.)

• ValueSet: AdverseEventSeverity (The severity of the adverse event itself, in direct relation to the subject.)

4.3.14.173.1 Content

4.3.14.173.2 AdverseEventSeverity

The severity of the adverse event itself, in direct relation to the subject.

This code system http://terminology.hl7.org/CodeSystem/adverse-event-severity defines the following codes:

Code | Display | Definition
mild | Mild
moderate | Moderate
severe | Severe

See the full registry of code systems defined as part of FHIR.

Explanation of the columns that may appear on this page:

Level | A few code lists that FHIR defines are hierarchical - each code is assigned a level. See Code System for further information.
Source | The source of the definition of the code (when the value set draws in codes defined elsewhere)
Code | The code (used as the code in the resource instance). If the code is in italics, this indicates that the code is not selectable ('Abstract')
Display | The display (used in the display element of a Coding). If there is no display, implementers should not simply display the code, but map the concept into their application
Definition | An explanation of the meaning of the concept
Comments | Additional notes about how to use the code

4.3.14.174 Code System http://terminology.hl7.org/CodeSystem/program

URL: https://hl7.org/fhir/R4/codesystem-program.html
Patient Administration Work Group | Maturity Level: 1 | Draft | Use Context: Any

This is a code system defined by the FHIR project.

Summary

Defining URL: | http://terminology.hl7.org/CodeSystem/program
Version: | 4.0.1
Name: | Program
Title: | Program
Definition: | This value set defines an example set of codes that could be can be used to classify groupings of service-types/specialties.
Committee: | Patient Administration Work Group
OID: | 2.16.840.1.113883.4.642.4.1384 (for OID based terminology systems)
Source Resource | XML / JSON

This Code system is used in the following value sets:

• ValueSet: Program (This value set defines an example set of codes that could be can be used to classify groupings of service-types/specialties.)

• ValueSet: Program (This value set defines an example set of codes that could be can be used to classify groupings of service-types/specialties.)

4.3.14.174.1 Content

4.3.14.174.2 Program

This value set defines an example set of codes that could be can be used to classify groupings of service-types/specialties.

This code system http://terminology.hl7.org/CodeSystem/program defines many codes, of which the following are some examples:

Code | Display | Definition
1 | Acquired Brain Injury (ABI) Program
2 | ABI Slow To Recover (ABI STR) Program
3 | Access Programs
4 | Adult and Further Education (ACFE) Program
5 | Adult Day Activity and Support Services (ADASS) Program
6 | Adult Day Care Program
7 | ATSS (Adult Training Support Service)
8 | Community Aged Care Packages (CACP)
9 | Care Coordination & Supplementary Services (CCSS)
10 | Cognitive Dementia Memory Service (CDAMS)
11 | ChildFIRST
12 | Children's Contact Services

13 | Community Visitors Scheme
14 | CPP (Community Partners Program)
15 | Closing the Gap (CTG)
16 | Coordinated Veterans' Care (CVC) Program
17 | Day Program
18 | Drop In Program
19 | Early Years Program
20 | Employee Assistance Program
21 | Home And Community Care (HACC)
22 | Hospital Admission Risk Program (HARP)
23 | Hospital in the Home (HITH) Program
24 | ICTP (Intensive Community Treatment Program)
25 | IFSS (Intensive Family Support Program)
26 | JPET (Job Placement, Education and Training)
27 | Koori Juvenile Justice Program
28 | Language Literacy and Numeracy Program
29 | Life Skills Program
30 | LMP (Lifestyle Modification Program)
31 | MedsCheck Program
32 | Methadone/Buprenorphine Program
33 | National Disabilities Insurance Scheme (NDIS)
34 | National Diabetes Services Scheme (NDSS)
35 | Needle/Syringe Program
36 | nPEP Program
37 | Personal Support Program
38 | Partners in Recovery (PIR) Program
39 | Pre-employment Program
40 | Reconnect Program
41 | Sexual Abuse Counselling and Prevention Program (SACPP)
42 | Social Support Programs
43 | Supported Residential Service (SRS)
44 | Tasmanian Aboriginal Centre (TAC)
45 | Victim's Assistance Program

See the full registry of code systems defined as part of FHIR.

Explanation of the columns that may appear on this page:

Level | A few code lists that FHIR defines are hierarchical - each code is assigned a level. See Code System for further information.
Source | The source of the definition of the code (when the value set draws in codes defined elsewhere)
Code | The code (used as the code in the resource instance). If the code is in italics, this indicates that the code is not selectable ('Abstract')
Display | The display (used in the display element of a Coding). If there is no display, implementers should not simply display the code, but map the concept into their application
Definition | An explanation of the meaning of the concept
Comments | Additional notes about how to use the code

4.3.14.175 Code System http://hl7.org/fhir/product-category

URL: https://hl7.org/fhir/R4/codesystem-product-category.html
Orders and Observations Work Group | Maturity Level: 0 | Trial Use | Use Context: Any

This is a code system defined by the FHIR project.

Summary

Defining URL: | http://hl7.org/fhir/product-category
Version: | 4.0.1
Name: | BiologicallyDerivedProductCategory
Title: | BiologicallyDerivedProductCategory
Definition: | Biologically Derived Product Category.
Committee: | Orders and Observations Work Group
OID: | 2.16.840.1.113883.4.642.4.901 (for OID based terminology systems)
Source Resource | XML / JSON

This Code system is used in the following value sets:

• ValueSet: BiologicallyDerivedProductCategory (Biologically Derived Product Category.)
• ValueSet: BiologicallyDerivedProductCategory (Biologically Derived Product Category.)

4.3.14.175.1 Content

4.3.14.175.2 BiologicallyDerivedProductCategory

Biologically Derived Product Category.

This code system http://hl7.org/fhir/product-category defines the following codes:

Code | Display | Definition
organ | Organ | A collection of tissues joined in a structural unit to serve a common function.
tissue | Tissue | An ensemble of similar cells and their extracellular matrix from the same origin that together carry out a specific function.
fluid | Fluid | Body fluid.
cells | Cells | Collection of cells.
biologicalAgent | BiologicalAgent | Biological agent of unspecified type.

See the full registry of code systems defined as part of FHIR.

Explanation of the columns that may appear on this page:

Level | A few code lists that FHIR defines are hierarchical - each code is assigned a level. See Code System for further information.
Source | The source of the definition of the code (when the value set draws in codes defined elsewhere)
Code | The code (used as the code in the resource instance). If the code is in italics, this indicates that the code is not selectable ('Abstract')
Display | The display (used in the display element of a Coding). If there is no display, implementers should not simply display the code, but map the concept into their application
Definition | An explanation of the meaning of the concept
Comments | Additional notes about how to use the code

4.3.14.176 Code System http://terminology.hl7.org/CodeSystem/push-type-available

URL: https://hl7.org/fhir/R4/codesystem-verificationresult-push-type-available.html
Patient Administration Work Group | Maturity Level: 0 | Informative | Use Context: Any

This is a code system defined by the FHIR project.

Summary

Defining URL: | http://terminology.hl7.org/CodeSystem/push-type-available
Version: | 4.0.1
Name: | push-type-available
Title: | Push-type-available
Definition: | Type of alerts/updates the primary source can send
Committee: | Patient Administration Work Group
OID: | 2.16.840.1.113883.4.642.1.899 (for OID based terminology systems)
Source Resource | XML / JSON

This Code system is used in the following value sets:

• ValueSet: Push-type-available (Type of alerts/updates the primary source can send)

• ValueSet: Push-type-available (Type of alerts/updates the primary source can send)

4.3.14.176.1 Content

4.3.14.176.2 Push-type-available

Type of alerts/updates the primary source can send

This code system http://terminology.hl7.org/CodeSystem/push-type-available defines the following codes:

Code | Display | Definition
specific | Specific requested changes
any | Any changes
source | As defined by source

See the full registry of code systems defined as part of FHIR.

Explanation of the columns that may appear on this page:

Level | A few code lists that FHIR defines are hierarchical - each code is assigned a level. See Code System for further information.
Source | The source of the definition of the code (when the value set draws in codes defined elsewhere)
Code | The code (used as the code in the resource instance). If the code is in italics, this indicates that the code is not selectable ('Abstract')
Display | The display (used in the display element of a Coding). If there is no display, implementers should not simply display the code, but map the concept into their application
Definition | An explanation of the meaning of the concept
Comments | Additional notes about how to use the code

4.3.14.177 Code System http://hl7.org/fhir/restful-interaction

URL: https://hl7.org/fhir/R4/codesystem-restful-interaction.html
FHIR Infrastructure Work Group | Maturity Level: N | Normative (from v4.0.0) | Use Context: Any

| This page has been approved as part of an ANSI standard. See the Conformance Package for further details.

This is a code system defined by the FHIR project.

Summary

Defining URL: | http://hl7.org/fhir/restful-interaction
Version: | 4.0.1
Name: | FHIR Restful Interactions
Title:
Definition: | The set of interactions defined by the RESTful part of the FHIR specification.
Committee: | FHIR Infrastructure Work Group
OID: | (for OID based terminology systems)
Source Resource | XML / JSON

This Code system is used in the following value sets:

• ValueSet: Audit Event Sub-Type (More detailed code concerning the type of the audit event - defined by DICOM with some FHIR specific additions.)

• ValueSet: SystemRestfulInteraction (Operations supported by REST at the system level.)

• ValueSet: SystemRestfulInteraction (Operations supported by REST at the system level.)

• ValueSet: TypeRestfulInteraction (Operations supported by REST at the type or instance level.)

• ValueSet: TypeRestfulInteraction (Operations supported by REST at the type or instance level.)

• ValueSet: Audit Event Sub-Type (More detailed code concerning the type of the audit event - defined by DICOM with some FHIR specific additions.)

4.3.14.177.1 Content

4.3.14.177.2 FHIR Restful Interactions

The set of interactions defined by the RESTful part of the FHIR specification.

This code system http://hl7.org/fhir/restful-interaction defines the following codes:

Lvl | Code | Display | Definition
1 | read | read | Read the current state of the resource.
1 | vread | vread | Read the state of a specific version of the resource.
1 | update | update | Update an existing resource by its id (or create it if it is new).
1 | patch | patch | Update an existing resource by posting a set of changes to it.
1 | delete | delete | Delete a resource.
1 | history | history | Retrieve the change history for a particular resource, type of resource, or the entire system.
2 | history-instance | history-instance | Retrieve the change history for a particular resource.
2 | history-type | history-type | Retrieve the change history for all resources of a particular type.
2 | history-system | history-system | Retrieve the change history for all resources on a system.
1 | create | create | Create a new resource with a server assigned id.
1 | search | search | Search a resource type or all resources based on some filter criteria.
2 | search-type | search-type | Search all resources of the specified type based on some filter criteria.
2 | search-system | search-system | Search all resources based on some filter criteria.
1 | capabilities | capabilities | Get a Capability Statement for the system.
1 | transaction | transaction | Update, create or delete a set of resources as a single transaction.
1 | batch | batch | perform a set of a separate interactions in a single http operation
1 | operation | operation | Perform an operation as defined by an OperationDefinition.

See the full registry of code systems defined as part of FHIR.

Explanation of the columns that may appear on this page:

Level | A few code lists that FHIR defines are hierarchical - each code is assigned a level. See Code System for further information.
Source | The source of the definition of the code (when the value set draws in codes defined elsewhere)
Code | The code (used as the code in the resource instance). If the code is in italics, this indicates that the code is not selectable ('Abstract')
Display | The display (used in the display element of a Coding). If there is no display, implementers should not simply display the code, but map the concept into their application
Definition | An explanation of the meaning of the concept
Comments | Additional notes about how to use the code

4.3.14.178 Code System http://hl7.org/fhir/event-timing

URL: https://hl7.org/fhir/R4/codesystem-event-timing.html
FHIR Infrastructure Work Group | Maturity Level: N | Normative (from v4.0.0) | Use Context: Any

This is a code system defined by the FHIR project.

Summary

Defining URL: | http://hl7.org/fhir/event-timing
Version: | 4.0.1
Name: | EventTiming
Title: | EventTiming
Definition: | Real world event relating to the schedule.
Committee: | FHIR Infrastructure Work Group
OID: | 2.16.840.1.113883.4.642.4.76 (for OID based terminology systems)
Source Resource | XML / JSON

This Code system is used in the following value sets:

• ValueSet: EventTiming (Real world event relating to the schedule.)

• ValueSet: EventTiming (Real world event relating to the schedule.)

4.3.14.178.1 Content

4.3.14.178.2 EventTiming

Real world event relating to the schedule.

This code system http://hl7.org/fhir/event-timing defines the following codes:

Code | Display | Definition
MORN | Morning | Event occurs during the morning. The exact time is unspecified and established by institution convention or patient interpretation.
MORN.early | Early Morning | Event occurs during the early morning. The exact time is unspecified and established by institution convention or patient interpretation.
MORN.late | Late Morning | Event occurs during the late morning. The exact time is unspecified and established by institution convention or patient interpretation.
NOON | Noon | Event occurs around 12:00pm. The exact time is unspecified and established by institution convention or patient interpretation.
AFT | Afternoon | Event occurs during the afternoon. The exact time is unspecified and established by institution convention or patient interpretation.
AFT.early | Early Afternoon | Event occurs during the early afternoon. The exact time is unspecified and established by institution convention or patient interpretation.
AFT.late | Late Afternoon | Event occurs during the late afternoon. The exact time is unspecified and established by institution convention or patient interpretation.
EVE | Evening | Event occurs during the evening. The exact time is unspecified and established by institution convention or patient interpretation.
EVE.early | Early Evening | Event occurs during the early evening. The exact time is unspecified and established by institution convention or patient interpretation.
EVE.late | Late Evening | Event occurs during the late evening. The exact time is unspecified and established by institution convention or patient interpretation.
NIGHT | Night | Event occurs during the night. The exact time is unspecified and established by institution convention or patient interpretation.
PHS | After Sleep | Event occurs [offset] after subject goes to sleep. The exact time is unspecified and established by institution convention or patient interpretation.

See the full registry of code systems defined as part of FHIR.

Explanation of the columns that may appear on this page:

Level | A few code lists that FHIR defines are hierarchical - each code is assigned a level. See Code System for further information.
Source | The source of the definition of the code (when the value set draws in codes defined elsewhere)
Code | The code (used as the code in the resource instance). If the code is in italics, this indicates that the code is not selectable ('Abstract')
Display | The display (used in the display element of a Coding). If there is no display, implementers should not simply display the code, but map the concept into their application
Definition | An explanation of the meaning of the concept
Comments | Additional notes about how to use the code

4.3.14.179 Code System http://terminology.hl7.org/CodeSystem/testscript-operation-codes

URL: https://hl7.org/fhir/R4/codesystem-testscript-operation-codes.html
FHIR Infrastructure Work Group | Maturity Level: 2 | Trial Use | Use Context: Any

This is a code system defined by the FHIR project.

Summary

Defining URL: | http://terminology.hl7.org/CodeSystem/testscript-operation-codes
Version: | 4.0.1
Name: | TestScriptOperationCode
Title: | Test script operation code
Definition: | This value set defines a set of codes that are used to indicate the supported operations of a testing engine or tool.
Committee: | FHIR Infrastructure Work Group
OID: | 2.16.840.1.113883.4.642.4.1195 (for OID based terminology systems)
Source Resource | XML / JSON

This Code system is used in the following value sets:

• ValueSet: Test script operation code (This value set defines a set of codes that are used to indicate the supported operations of a testing engine or tool.)

• ValueSet: Test script operation code (This value set defines a set of codes that are used to indicate the supported operations of a testing engine or tool.)

4.3.14.179.1 Content

4.3.14.179.2 Test script operation code

This value set defines a set of codes that are used to indicate the supported operations of a testing engine or tool.

This code system http://terminology.hl7.org/CodeSystem/testscript-operation-codes defines the following codes:

Code | Display | Definition
read | Read | Read the current state of the resource.
vread | Version Read | Read the state of a specific version of the resource.
update | Update | Update an existing resource by its id.
updateCreate | Create using Update | Update an existing resource by its id (or create it if it is new).
patch | Patch | Patch an existing resource by its id.
delete | Delete | Delete a resource.
deleteCondSingle | Conditional Delete Single | Conditionally delete a single resource based on search parameters.
deleteCondMultiple | Conditional Delete Multiple | Conditionally delete one or more resources based on search parameters.
history | History | Retrieve the change history for a particular resource or resource type.
create | Create | Create a new resource with a server assigned id.
search | Search | Search based on some filter criteria.
batch | Batch | Update, create or delete a set of resources as independent actions.
transaction | Transaction | Update, create or delete a set of resources as a single transaction.
capabilities | Capabilities | Get a capability statement for the system.
apply | $apply | Realizes an ActivityDefinition in a specific context
closure | $closure | Closure Table Maintenance
find-matches | $find-matches | Finding Codes based on supplied properties
conforms | $conforms | Compare two systems CapabilityStatements
data-requirements | $data-requirements | Aggregates and returns the parameters and data requirements for a resource and all its dependencies as a single module definition
document | $document | Generate a Document
evaluate | $evaluate | Request clinical decision support guidance based on a specific decision support module
evaluate-measure | $evaluate-measure | Invoke an eMeasure and obtain the results
everything | $everything | Return all the related information as described in the Encounter or Patient
expand | $expand | Value Set Expansion
find | $find | Find a functional list
graphql | $graphql | Invoke a GraphQL query
implements | $implements | Test if a server implements a client's required operations
lastn | $lastn | Last N Observations Query
lookup | $lookup | Concept Look Up and Decomposition
match | $match | Find patient matches using MPI based logic
meta | $meta | Access a list of profiles, tags, and security labels
meta-add | $meta-add | Add profiles, tags, and security labels to a resource
meta-delete | $meta-delete | Delete profiles, tags, and security labels for a resource
populate | $populate | Populate Questionnaire
populatehtml | $populatehtml | Generate HTML for Questionnaire
populatelink | $populatelink | Generate a link to a Questionnaire completion webpage
process-message | $process-message | Process a message according to the defined event
questionnaire | $questionnaire | Build Questionnaire
stats | $stats | Observation Statistics
subset | $subset | Fetch a subset of the CapabilityStatement resource
subsumes | $subsumes | CodeSystem Subsumption Testing
transform | $transform | Model Instance Transformation
translate | $translate | Concept Translation
validate | $validate | Validate a resource
validate-code | $validate-code | ValueSet based Validation

See the full registry of code systems defined as part of FHIR.

Explanation of the columns that may appear on this page:

Level | A few code lists that FHIR defines are hierarchical - each code is assigned a level. See Code System for further information.
Source | The source of the definition of the code (when the value set draws in codes defined elsewhere)
Code | The code (used as the code in the resource instance). If the code is in italics, this indicates that the code is not selectable ('Abstract')
Display | The display (used in the display element of a Coding). If there is no display, implementers should not simply display the code, but map the concept into their application
Definition | An explanation of the meaning of the concept
Comments | Additional notes about how to use the code

4.3.14.180 Code System http://hl7.org/fhir/measure-report-status

URL: https://hl7.org/fhir/R4/codesystem-measure-report-status.html

Clinical Quality Information Work Group | Maturity Level: 2 | Trial Use | Use Context: Any

This is a code system defined by the FHIR project.

Summary

Defining URL: | http://hl7.org/fhir/measure-report-status
Version: | 4.0.1
Name: | MeasureReportStatus
Title: | MeasureReportStatus
Definition: | The status of the measure report.
Committee: | Clinical Quality Information Work Group
OID: | 2.16.840.1.113883.4.642.4.777 (for OID based terminology systems)
Source Resource | XML / JSON

This Code system is used in the following value sets:

• ValueSet: MeasureReportStatus (The status of the measure report.)

• ValueSet: MeasureReportStatus (The status of the measure report.)

4.3.14.180.1 Content

4.3.14.180.2 MeasureReportStatus

The status of the measure report.

This code system http://hl7.org/fhir/measure-report-status defines the following codes:

Code | Display | Definition
complete | Complete | The report is complete and ready for use.
pending | Pending | The report is currently being generated.
error | Error | An error occurred attempting to generate the report.

See the full registry of code systems defined as part of FHIR.

Explanation of the columns that may appear on this page:

Level | A few code lists that FHIR defines are hierarchical - each code is assigned a level. See Code System for further information.
Source | The source of the definition of the code (when the value set draws in codes defined elsewhere)
Code | The code (used as the code in the resource instance). If the code is in italics, this indicates that the code is not selectable ('Abstract')
Display | The display (used in the display element of a Coding). If there is no display, implementers should not simply display the code, but map the concept into their application
Definition | An explanation of the meaning of the concept
Comments | Additional notes about how to use the code

4.3.14.181 Code System http://hl7.org/fhir/namingsystem-type

URL: https://hl7.org/fhir/R4/codesystem-namingsystem-type.html
FHIR Infrastructure Work Group | Maturity Level: 1 | Trial Use | Use Context: Any

This is a code system defined by the FHIR project.

Summary

Defining URL: | http://hl7.org/fhir/namingsystem-type
Version: | 4.0.1
Name: | NamingSystemType
Title: | NamingSystemType
Definition: | Identifies the purpose of the naming system.
Committee: | FHIR Infrastructure Work Group
OID: | 2.16.840.1.113883.4.642.4.491 (for OID based terminology systems)
Source Resource | XML / JSON

This Code system is used in the following value sets:

• ValueSet: NamingSystemType (Identifies the purpose of the naming system.)

• ValueSet: NamingSystemType (Identifies the purpose of the naming system.)

4.3.14.181.1 Content

4.3.14.181.2 NamingSystemType

Identifies the purpose of the naming system.

This code system http://hl7.org/fhir/namingsystem-type defines the following codes:

Code | Display | Definition
codesystem | Code System | The naming system is used to define concepts and symbols to represent those concepts; e.g. UCUM, LOINC, NDC code, local lab codes, etc.
identifier | Identifier | The naming system is used to manage identifiers (e.g. license numbers, order numbers, etc.).
root | Root | The naming system is used as the root for other identifiers and naming systems.

See the full registry of code systems defined as part of FHIR.

Explanation of the columns that may appear on this page:

Level | A few code lists that FHIR defines are hierarchical - each code is assigned a level. See Code System for further information.
Source | The source of the definition of the code (when the value set draws in codes defined elsewhere)
Code | The code (used as the code in the resource instance). If the code is in italics, this indicates that the code is not selectable ('Abstract')
Display | The display (used in the display element of a Coding). If there is no display, implementers should not simply display the code, but map the concept into their application
Definition | An explanation of the meaning of the concept
Comments | Additional notes about how to use the code

4.3.14.182 Code System http://hl7.org/fhir/relation-type

URL: https://hl7.org/fhir/R4/codesystem-relation-type.html
Orders and Observations Work Group | Maturity Level: 0 | Trial Use | Use Context: Any

This is a code system defined by the FHIR project.

Summary

Defining URL: | http://hl7.org/fhir/relation-type
Version: | 4.0.1
Name: | CatalogEntryRelationType
Title: | CatalogEntryRelationType
Definition: | The type of relations between entries.
Committee: | Orders and Observations Work Group
OID: | 2.16.840.1.113883.4.642.4.1029 (for OID based terminology systems)
Source Resource | XML / JSON

This Code system is used in the following value sets:

• ValueSet: CatalogEntryRelationType (The type of relations between entries.)
• ValueSet: CatalogEntryRelationType (The type of relations between entries.)

4.3.14.182.1 Content

4.3.14.182.2 CatalogEntryRelationType

The type of relations between entries.

This code system http://hl7.org/fhir/relation-type defines the following codes:

Code | Display | Definition
triggers | Triggers | the related entry represents an activity that may be triggered by the current item.
is-replaced-by | Replaced By | the related entry represents an item that replaces the current retired item.

See the full registry of code systems defined as part of FHIR.

Explanation of the columns that may appear on this page:

Level | A few code lists that FHIR defines are hierarchical - each code is assigned a level. See Code System for further information.
Source | The source of the definition of the code (when the value set draws in codes defined elsewhere)
Code | The code (used as the code in the resource instance). If the code is in italics, this indicates that the code is not selectable ('Abstract')
Display | The display (used in the display element of a Coding). If there is no display, implementers should not simply display the code, but map the concept into their application
Definition | An explanation of the meaning of the concept
Comments | Additional notes about how to use the code

4.3.14.183 Code System http://hl7.org/fhir/asset-availability

URL: https://hl7.org/fhir/R4/codesystem-asset-availability.html
Financial Management Work Group | Maturity Level: 1 | Draft | Use Context: Any

This is a code system defined by the FHIR project.

Summary

Defining URL: | http://hl7.org/fhir/asset-availability
Version: | 4.0.1
Name: | ContractResourceAssetAvailiabilityCodes
Title: | Contract Resource Asset Availiability codes
Definition: | This value set has asset availability codes.
Committee: | Financial Management Work Group
OID: | 2.16.840.1.113883.4.642.4.1296 (for OID based terminology systems)
Copyright: | HL7 International.
Source Resource | XML / JSON

This Code system is used in the following value sets:

• ValueSet: Contract Resource Asset Availiability codes (This value set has asset availability codes.)
• ValueSet: Contract Resource Asset Availiability codes (This value set has asset availability codes.)

4.3.14.183.1 Content

Each definition includes usage notes explaining the precedence order in contract lifecycle - i.e., while only some stages are required, the order in which they may occur is deterministic; and a map to comparable FHIR and v.3 status codes. It follows guidance about use of status codes in FHIR at http://build.fhir.org/sc.html.

4.3.14.183.2 Contract Resource Asset Availiability codes

This value set has asset availability codes.

Copyright Statement:

HL7 International.

This code system http://hl7.org/fhir/asset-availability defines the following codes:

Code | Display | Definition
lease | Lease | To be completed

See the full registry of code systems defined as part of FHIR.

Explanation of the columns that may appear on this page:

Level | A few code lists that FHIR defines are hierarchical - each code is assigned a level. See Code System for further information.
Source | The source of the definition of the code (when the value set draws in codes defined elsewhere)
Code | The code (used as the code in the resource instance). If the code is in italics, this indicates that the code is not selectable ('Abstract')
Display | The display (used in the display element of a Coding). If there is no display, implementers should not simply display the code, but map the concept into their application
Definition | An explanation of the meaning of the concept
Comments | Additional notes about how to use the code

4.3.14.184 Code System http://terminology.hl7.org/CodeSystem/medicationrequest-course-of-therapy

URL: https://hl7.org/fhir/R4/codesystem-medicationrequest-course-of-therapy.html
Pharmacy Work Group | Maturity Level: 1 | Draft | Use Context: Any

This is a code system defined by the FHIR project.

Summary

Defining URL: | http://terminology.hl7.org/CodeSystem/medicationrequest-course-of-therapy
Version: | 4.0.1
Name: | medicationRequest Course of Therapy Codes
Title: | Medication request course of therapy codes
Definition: | MedicationRequest Course of Therapy Codes
Committee: | Pharmacy Work Group
OID: | 2.16.840.1.113883.4.642.4.1327 (for OID based terminology systems)
Source Resource | XML / JSON

This Code system is used in the following value sets:

• ValueSet: Medication request course of therapy codes (MedicationRequest Course of Therapy Codes)
• ValueSet: Medication request course of therapy codes (MedicationRequest Course of Therapy Codes)

4.3.14.184.1 Content

4.3.14.184.2 Medication request course of therapy codes

MedicationRequest Course of Therapy Codes

This code system http://terminology.hl7.org/CodeSystem/medicationrequest-course-of-therapy defines the following codes:

Code | Display | Definition
continuous | Continuous long term therapy | A medication which is expected to be continued beyond the present order and which the patient should be assumed to be taking unless explicitly stopped.
acute | Short course (acute) therapy | A medication which the patient is only expected to consume for the duration of the current order and which is not expected to be renewed.
seasonal | Seasonal | A medication which is expected to be used on a part time basis at certain times of the year

See the full registry of code systems defined as part of FHIR.

Explanation of the columns that may appear on this page:

Level | A few code lists that FHIR defines are hierarchical - each code is assigned a level. See Code System for further information.
Source | The source of the definition of the code (when the value set draws in codes defined elsewhere)
Code | The code (used as the code in the resource instance). If the code is in italics, this indicates that the code is not selectable ('Abstract')

Display | The display (used in the display element of a Coding). If there is no display, implementers should not simply display the code, but map the concept into their application
Definition | An explanation of the meaning of the concept
Comments | Additional notes about how to use the code

4.3.14.185 Code System http://hl7.org/fhir/orientation-type

URL: https://hl7.org/fhir/R4/codesystem-orientation-type.html
Clinical Genomics Work Group | Maturity Level: 1 | Trial Use | Use Context: Any

This is a code system defined by the FHIR project.

Summary

Defining URL: | http://hl7.org/fhir/orientation-type
Version: | 4.0.1
Name: | orientationType
Title: | orientationType
Definition: | Type for orientation.
Committee: | Clinical Genomics Work Group
OID: | 2.16.840.1.113883.4.642.4.988 (for OID based terminology systems)
Source Resource | XML / JSON

This Code system is used in the following value sets:

• ValueSet: orientationType (Type for orientation.)

• ValueSet: orientationType (Type for orientation.)

4.3.14.185.1 Content

4.3.14.185.2 orientationType

Type for orientation.

This code system http://hl7.org/fhir/orientation-type defines the following codes:

Code | Display | Definition
sense | Sense orientation of referenceSeq | Sense orientation of reference sequence.
antisense | Antisense orientation of referenceSeq | Antisense orientation of reference sequence.

See the full registry of code systems defined as part of FHIR.

Explanation of the columns that may appear on this page:

Level | A few code lists that FHIR defines are hierarchical - each code is assigned a level. See Code System for further information.
Source | The source of the definition of the code (when the value set draws in codes defined elsewhere)
Code | The code (used as the code in the resource instance). If the code is in italics, this indicates that the code is not selectable ('Abstract')
Display | The display (used in the display element of a Coding). If there is no display, implementers should not simply display the code, but map the concept into their application
Definition | An explanation of the meaning of the concept
Comments | Additional notes about how to use the code

4.3.14.186 Code System http://terminology.hl7.org/CodeSystem/referencerange-meaning

URL: https://hl7.org/fhir/R4/codesystem-referencerange-meaning.html
Orders and Observations Work Group | Maturity Level: 0 | Informative | Use Context: Any

This is a code system defined by the FHIR project.

Summary

Defining URL: | http://terminology.hl7.org/CodeSystem/referencerange-meaning
Version: | 4.0.1
Name: | ObservationReferenceRangeMeaningCodes
Title: | Observation Reference Range Meaning Codes
Definition: | This value set defines a set of codes that can be used to indicate the meaning/use of a reference range for a particular target population.
Committee: | Orders and Observations Work Group
OID: | 2.16.840.1.113883.4.642.4.1124 (for OID based terminology systems)
Source Resource | XML / JSON

This Code system is used in the following value sets:

• ValueSet: Observation Reference Range Meaning Codes (This value set defines a set of codes that can be used to indicate the meaning/use of a reference range for a particular target population.)

• ValueSet: Observation Reference Range Meaning Codes (This value set defines a set of codes that can be used to indicate the meaning/use of a reference range for a particular target population.)

4.3.14.186.1 Content

4.3.14.186.2 Observation Reference Range Meaning Codes

This value set defines a set of codes that can be used to indicate the meaning/use of a reference range for a particular target population.

Properties

Code | URL | Description | Type
abstract | | True if an element is considered 'abstract' - in otherwords, the code is not for use as a real concept | boolean

This code system http://terminology.hl7.org/CodeSystem/referencerange-meaning defines the following codes:

Lvl | Code | Display | Definition
1 | type | Type | General types of reference range.
2 | normal | Normal Range | Values expected for a normal member of the relevant control population being measured. Typically each results producer such as a laboratory has specific normal ranges and they are usually defined as within two standard deviations from the mean and account for 95.45% of this population.
2 | recommended | Recommended Range | The range that is recommended by a relevant professional body.
2 | treatment | Treatment Range | The range at which treatment would/should be considered.
2 | therapeutic | Therapeutic Desired Level | The optimal range for best therapeutic outcomes.
3 | pre | Pre Therapeutic Desired Level | The optimal range for best therapeutic outcomes for a specimen taken immediately before administration.
3 | post | Post Therapeutic Desired Level | The optimal range for best therapeutic outcomes for a specimen taken immediately after administration.
1 | endocrine | Endocrine | Endocrine related states that change the expected value.
2 | pre-puberty | Pre-Puberty | An expected range in an individual prior to puberty.
2 | follicular | Follicular Stage | An expected range in an individual during the follicular stage of the cycle.
2 | midcycle | MidCycle | An expected range in an individual during the midcycle stage of the cycle.
2 | luteal | Luteal | An expected range in an individual during the luteal stage of the cycle.
2 | postmenopausal | Post-Menopause | An expected range in an individual post-menopause.

See the full registry of code systems defined as part of FHIR.

Explanation of the columns that may appear on this page:

Level | A few code lists that FHIR defines are hierarchical - each code is assigned a level. See Code System for further information.
Source | The source of the definition of the code (when the value set draws in codes defined elsewhere)
Code | The code (used as the code in the resource instance). If the code is in italics, this indicates that the code is not selectable ('Abstract')
Display | The display (used in the display element of a Coding). If there is no display, implementers should not simply display the code, but map the concept into their application
Definition | An explanation of the meaning of the concept
Comments | Additional notes about how to use the code

4.3.14.187 Code System http://hl7.org/fhir/contract-security-classification

URL: https://hl7.org/fhir/R4/codesystem-contract-security-classification.html
Financial Management Work Group | Maturity Level: 1 | Draft | Use Context: Any

This is a code system defined by the FHIR project.

Summary

Defining URL: | http://hl7.org/fhir/contract-security-classification
Version: | 4.0.1
Name: | ContractResourceScopeCodes
Title: | Contract Resource Scope codes
Definition: | This value set contract specific codes for security classification.
Committee: | Financial Management Work Group
OID: | 2.16.840.1.113883.4.642.4.1219 (for OID based terminology systems)
Copyright: | HL7 International.
Source Resource | XML / JSON

This Code system is used in the following value sets:

• ValueSet: Contract Resource Scope codes (This value set contract specific codes for security classification.)

• ValueSet: Contract Resource Scope codes (This value set contract specific codes for security classification.)

4.3.14.187.1 Content

Each definition includes usage notes explaining the precedence order in contract lifecycle - i.e., while only some stages are required, the order in which they may occur is deterministic; and a map to comparable FHIR and v.3 status codes. It follows guidance about use of status codes in FHIR at http://build.fhir.org/sc.html.

4.3.14.187.2 Contract Resource Scope codes

This value set contract specific codes for security classification.

Copyright Statement:

HL7 International.

This code system http://hl7.org/fhir/contract-security-classification defines the following codes:

Code | Display | Definition
policy | Policy | To be completed

See the full registry of code systems defined as part of FHIR.

Explanation of the columns that may appear on this page:

Level | A few code lists that FHIR defines are hierarchical - each code is assigned a level. See Code System for further information.
Source | The source of the definition of the code (when the value set draws in codes defined elsewhere)
Code | The code (used as the code in the resource instance). If the code is in italics, this indicates that the code is not selectable ('Abstract')
Display | The display (used in the display element of a Coding). If there is no display, implementers should not simply display the code, but map the concept into their application
Definition | An explanation of the meaning of the concept
Comments | Additional notes about how to use the code

4.3.14.188 Code System http://terminology.hl7.org/CodeSystem/modifiers

URL: https://hl7.org/fhir/R4/codesystem-claim-modifiers.html
Financial Management Work Group | Maturity Level: 1 | Draft | Use Context: Any

This is a code system defined by the FHIR project.

Summary

Defining URL: | http://terminology.hl7.org/CodeSystem/modifiers
Version: | 4.0.1
Name: | ModifierTypeCodes
Title: | Modifier type Codes
Definition: | This value set includes sample Modifier type codes.
Committee: | Financial Management Work Group
OID: | 2.16.840.1.113883.4.642.4.1151 (for OID based terminology systems)
Copyright: | This is an example set.
Source Resource | XML / JSON

This Code system is used in the following value sets:

• ValueSet: Modifier type Codes (This value set includes sample Modifier type codes.)

• ValueSet: Modifier type Codes (This value set includes sample Modifier type codes.)

4.3.14.188.1 Content

4.3.14.188.2 Modifier type Codes

This value set includes sample Modifier type codes.

Copyright Statement:

This is an example set.

This code system http://terminology.hl7.org/CodeSystem/modifiers defines the following codes:

Code | Display | Definition
a | Repair of prior service or installation | Repair of prior service or installation.
b | Temporary service or installation | Temporary service or installation.
c | TMJ treatment | Treatment associated with TMJ.
e | Implant or associated with an implant | Implant or associated with an implant.
rooh | Rush or Outside of office hours | A Rush service or service performed outside of normal office hours.
x | None | None.

See the full registry of code systems defined as part of FHIR.

Explanation of the columns that may appear on this page:

Level | A few code lists that FHIR defines are hierarchical - each code is assigned a level. See Code System for further information.
Source | The source of the definition of the code (when the value set draws in codes defined elsewhere)
Code | The code (used as the code in the resource instance). If the code is in italics, this indicates that the code is not selectable ('Abstract')
Display | The display (used in the display element of a Coding). If there is no display, implementers should not simply display the code, but map the concept into their application
Definition | An explanation of the meaning of the concept
Comments | Additional notes about how to use the code

4.3.14.189 Code System http://hl7.org/fhir/metric-calibration-type

URL: https://hl7.org/fhir/R4/codesystem-metric-calibration-type.html
Health Care Devices Work Group | Maturity Level: 1 | Trial Use | Use Context: Any

This is a code system defined by the FHIR project.

Summary

Defining URL: | http://hl7.org/fhir/metric-calibration-type
Version: | 4.0.1
Name: | DeviceMetricCalibrationType
Title: | DeviceMetricCalibrationType
Definition: | Describes the type of a metric calibration.
Committee: | Health Care Devices Work Group
OID: | 2.16.840.1.113883.4.642.4.651 (for OID based terminology systems)
Source Resource | XML / JSON

This Code system is used in the following value sets:

• ValueSet: DeviceMetricCalibrationType (Describes the type of a metric calibration.)

• ValueSet: DeviceMetricCalibrationType (Describes the type of a metric calibration.)

4.3.14.189.1 Content

4.3.14.189.2 DeviceMetricCalibrationType

Describes the type of a metric calibration.

This code system http://hl7.org/fhir/metric-calibration-type defines the following codes:

Code | Display | Definition
unspecified | Unspecified | Metric calibration method has not been identified.
offset | Offset | Offset metric calibration method.
gain | Gain | Gain metric calibration method.
two-point | Two Point | Two-point metric calibration method.

See the full registry of code systems defined as part of FHIR.

Explanation of the columns that may appear on this page:

Level | A few code lists that FHIR defines are hierarchical - each code is assigned a level. See Code System for further information.
Source | The source of the definition of the code (when the value set draws in codes defined elsewhere)
Code | The code (used as the code in the resource instance). If the code is in italics, this indicates that the code is not selectable ('Abstract')
Display | The display (used in the display element of a Coding). If there is no display, implementers should not simply display the code, but map the concept into their application
Definition | An explanation of the meaning of the concept
Comments | Additional notes about how to use the code

4.3.14.190 Code System http://terminology.hl7.org/CodeSystem/evidence-variant-state

URL: https://hl7.org/fhir/R4/codesystem-evidence-variant-state.html
Clinical Decision Support Work Group | Maturity Level: 0 | Trial Use | Use Context: Any

This is a code system defined by the FHIR project.

Summary

Defining URL: | http://terminology.hl7.org/CodeSystem/evidence-variant-state
Version: | 4.0.1
Name: | EvidenceVariantState
Title: | EvidenceVariantState
Definition: | Used for results by exposure in variant states such as low-risk, medium-risk and high-risk states.
Committee: | Clinical Decision Support Work Group
OID: | 2.16.840.1.113883.4.642.4.1354 (for OID based terminology systems)
Source Resource | XML / JSON

This Code system is used in the following value sets:

• ValueSet: EvidenceVariantState (Used for results by exposure in variant states such as low-risk, medium-risk and high-risk states.)

• ValueSet: EvidenceVariantState (Used for results by exposure in variant states such as low-risk, medium-risk and high-risk states.)

4.3.14.190.1 Content

4.3.14.190.2 EvidenceVariantState

Used for results by exposure in variant states such as low-risk, medium-risk and high-risk states.

This code system http://terminology.hl7.org/CodeSystem/evidence-variant-state defines the following codes:

Code | Display | Definition
low-risk | low risk | low risk estimate.
medium-risk | medium risk | medium risk estimate.
high-risk | high risk | high risk estimate.

See the full registry of code systems defined as part of FHIR.

Explanation of the columns that may appear on this page:

Level | A few code lists that FHIR defines are hierarchical - each code is assigned a level. See Code System for further information.
Source | The source of the definition of the code (when the value set draws in codes defined elsewhere)
Code | The code (used as the code in the resource instance). If the code is in italics, this indicates that the code is not selectable ('Abstract')
Display | The display (used in the display element of a Coding). If there is no display, implementers should not simply display the code, but map the concept into their application
Definition | An explanation of the meaning of the concept
Comments | Additional notes about how to use the code

4.3.14.191 Code System http://terminology.hl7.org/CodeSystem/adjudication

URL: https://hl7.org/fhir/R4/codesystem-adjudication.html
Financial Management Work Group | Maturity Level: 1 | Draft | Use Context: Any

This is a code system defined by the FHIR project.

Summary

Defining URL: | http://terminology.hl7.org/CodeSystem/adjudication
Version: | 4.0.1
Name: | AdjudicationValueCodes
Title: | Adjudication Value Codes
Definition: | This value set includes a smattering of Adjudication Value codes which includes codes to indicate the amounts eligible under the plan, the amount of benefit, copays etc.
Committee: | Financial Management Work Group
OID: | 2.16.840.1.113883.4.642.4.1171 (for OID based terminology systems)
Copyright: | This is an example set.
Source Resource | XML / JSON

This Code system is used in the following value sets:

• ValueSet: Adjudication Value Codes (This value set includes a smattering of Adjudication Value codes which includes codes to indicate the amounts eligible under the plan, the amount of benefit, copays etc.)

• ValueSet: Adjudication Value Codes (This value set includes a smattering of Adjudication Value codes which includes codes to indicate the amounts eligible under the plan, the amount of benefit, copays etc.)

4.3.14.191.1 Content

4.3.14.191.2 Adjudication Value Codes

This value set includes a smattering of Adjudication Value codes which includes codes to indicate the amounts eligible under the plan, the amount of benefit, copays etc.

Copyright Statement:

This is an example set.

This code system http://terminology.hl7.org/CodeSystem/adjudication defines the following codes:

Code | Display | Definition
submitted | Submitted Amount | The total submitted amount for the claim or group or line item.
copay | CoPay | Patient Co-Payment
eligible | Eligible Amount | Amount of the change which is considered for adjudication.
deductible | Deductible | Amount deducted from the eligible amount prior to adjudication.
unallocdeduct | Unallocated Deductible | The amount of deductible which could not allocated to other line items.
eligpercent | Eligible % | Eligible Percentage.
tax | Tax | The amount of tax.
benefit | Benefit Amount | Amount payable under the coverage

See the full registry of code systems defined as part of FHIR.

Explanation of the columns that may appear on this page:

Level | A few code lists that FHIR defines are hierarchical - each code is assigned a level. See Code System for further information.
Source | The source of the definition of the code (when the value set draws in codes defined elsewhere)

Code | The code (used as the code in the resource instance). If the code is in italics, this indicates that the code is not selectable ('Abstract')
Display | The display (used in the display element of a Coding). If there is no display, implementers should not simply display the code, but map the concept into their application
Definition | An explanation of the meaning of the concept
Comments | Additional notes about how to use the code

4.3.14.192 Code System http://terminology.hl7.org/CodeSystem/risk-probability

URL: https://hl7.org/fhir/R4/codesystem-risk-probability.html
Clinical Decision Support Work Group | Maturity Level: 1 | Draft | Use Context: Any

This is a code system defined by the FHIR project.

Summary

Defining URL: | http://terminology.hl7.org/CodeSystem/risk-probability
Version: | 4.0.1
Name: | RiskProbability
Title: | Risk Probability
Definition: | Codes representing the likelihood of a particular outcome in a risk assessment.
Committee: | Clinical Decision Support Work Group
OID: | 2.16.840.1.113883.4.642.4.1133 (for OID based terminology systems)
Source Resource | XML / JSON

This Code system is used in the following value sets:

• ValueSet: Risk Probability (Codes representing the likelihood of a particular outcome in a risk assessment.)
• ValueSet: Risk Probability (Codes representing the likelihood of a particular outcome in a risk assessment.)

4.3.14.192.1 Content

4.3.14.192.2 Risk Probability

Codes representing the likelihood of a particular outcome in a risk assessment.

This code system http://terminology.hl7.org/CodeSystem/risk-probability defines the following codes:

Code | Display | Definition
negligible | Negligible likelihood | The specified outcome is exceptionally unlikely.
low | Low likelihood | The specified outcome is possible but unlikely.
moderate | Moderate likelihood | The specified outcome has a reasonable likelihood of occurrence.
high | High likelihood | The specified outcome is more likely to occur than not.
certain | Certain | The specified outcome is effectively guaranteed.

See the full registry of code systems defined as part of FHIR.

Explanation of the columns that may appear on this page:

Level | A few code lists that FHIR defines are hierarchical - each code is assigned a level. See Code System for further information.
Source | The source of the definition of the code (when the value set draws in codes defined elsewhere)
Code | The code (used as the code in the resource instance). If the code is in italics, this indicates that the code is not selectable ('Abstract')
Display | The display (used in the display element of a Coding). If there is no display, implementers should not simply display the code, but map the concept into their application
Definition | An explanation of the meaning of the concept
Comments | Additional notes about how to use the code

4.3.14.193 Code System http://terminology.hl7.org/CodeSystem/discharge-disposition

URL: https://hl7.org/fhir/R4/codesystem-encounter-discharge-disposition.html
Patient Administration Work Group | Maturity Level: 1 | Draft | Use Context: Any

This is a code system defined by the FHIR project.

Summary

Defining URL: | http://terminology.hl7.org/CodeSystem/discharge-disposition
Version: | 4.0.1
Name: | DischargeDisposition
Title: | Discharge disposition
Definition: | This value set defines a set of codes that can be used to where the patient left the hospital.
Committee: | Patient Administration Work Group
OID: | 2.16.840.1.113883.4.642.4.1093 (for OID based terminology systems)
Source Resource | XML / JSON

This Code system is used in the following value sets:

• ValueSet: Discharge disposition (This value set defines a set of codes that can be used to where the patient left the hospital.)

• ValueSet: Discharge disposition (This value set defines a set of codes that can be used to where the patient left the hospital.)

4.3.14.193.1 Content

4.3.14.193.2 Discharge disposition

This value set defines a set of codes that can be used to where the patient left the hospital.

This code system http://terminology.hl7.org/CodeSystem/discharge-disposition defines the following codes:

Code | Display | Definition
home | Home | The patient was dicharged and has indicated that they are going to return home afterwards.
alt-home | Alternative home | The patient was discharged and has indicated that they are going to return home afterwards, but not the patient's home - e.g. a family member's home.
other-hcf | Other healthcare facility | The patient was transferred to another healthcare facility.
hosp | Hospice | The patient has been discharged into palliative care.
long | Long-term care | The patient has been discharged into long-term care where is likely to be monitored through an ongoing episode-of-care.
aadvice | Left against advice | The patient self discharged against medical advice.
exp | Expired | The patient has deceased during this encounter.
psy | Psychiatric hospital | The patient has been transferred to a psychiatric facility.
rehab | Rehabilitation | The patient was discharged and is to receive post acute care rehabilitation services.
snf | Skilled nursing facility | The patient has been discharged to a skilled nursing facility for the patient to receive additional care.
oth | Other | The discharge disposition has not otherwise defined.

See the full registry of code systems defined as part of FHIR.

Explanation of the columns that may appear on this page:

Level | A few code lists that FHIR defines are hierarchical - each code is assigned a level. See Code System for further information.
Source | The source of the definition of the code (when the value set draws in codes defined elsewhere)
Code | The code (used as the code in the resource instance). If the code is in italics, this indicates that the code is not selectable ('Abstract')
Display | The display (used in the display element of a Coding). If there is no display, implementers should not simply display the code, but map the concept into their application
Definition | An explanation of the meaning of the concept
Comments | Additional notes about how to use the code

4.3.14.194 Code System http://hl7.org/fhir/location-status

URL: https://hl7.org/fhir/R4/codesystem-location-status.html
Patient Administration Work Group | Maturity Level: 3 | Trial Use | Use Context: Any

This is a code system defined by the FHIR project.

Summary

Defining URL: | http://hl7.org/fhir/location-status
Version: | 4.0.1
Name: | LocationStatus
Title: | LocationStatus
Definition: | Indicates whether the location is still in use.
Committee: | Patient Administration Work Group
OID: | 2.16.840.1.113883.4.642.4.333 (for OID based terminology systems)
Source Resource | XML / JSON

This Code system is used in the following value sets:

• ValueSet: LocationStatus (Indicates whether the location is still in use.)

• ValueSet: LocationStatus (Indicates whether the location is still in use.)

4.3.14.194.1 Content

4.3.14.194.2 LocationStatus

Indicates whether the location is still in use.

This code system http://hl7.org/fhir/location-status defines the following codes:

Code | Display | Definition
active | Active | The location is operational.
suspended | Suspended | The location is temporarily closed.
inactive | Inactive | The location is no longer used.

See the full registry of code systems defined as part of FHIR.

Explanation of the columns that may appear on this page:

Level | A few code lists that FHIR defines are hierarchical - each code is assigned a level. See Code System for further information.
Source | The source of the definition of the code (when the value set draws in codes defined elsewhere)
Code | The code (used as the code in the resource instance). If the code is in italics, this indicates that the code is not selectable ('Abstract')
Display | The display (used in the display element of a Coding). If there is no display, implementers should not simply display the code, but map the concept into their application
Definition | An explanation of the meaning of the concept
Comments | Additional notes about how to use the code

4.3.14.195 Code System http://hl7.org/fhir/device-definition-status

URL: https://hl7.org/fhir/R4/codesystem-device-definition-status.html
Vocabulary Work Group | Maturity Level: 0 | Informative | Use Context: Any

This is a code system defined by the FHIR project.

Summary

Defining URL: | http://hl7.org/fhir/device-definition-status
Version: | 4.0.1
Name: | FHIRDeviceStatus
Title: | FHIRDeviceStatus
Definition: | Codes representing the current status of the device - on, off, suspended, etc.
Committee: | ??
OID: | 2.16.840.1.113883.4.642.4.1308 (for OID based terminology systems)
Source Resource | XML / JSON

This Code system is used in the following value sets:

• ValueSet: FHIRDeviceStatus (Codes representing the current status of the device - on, off, suspended, etc.)
• ValueSet: FHIRDeviceStatus (Codes representing the current status of the device - on, off, suspended, etc.)

4.3.14.195.1 Content

4.3.14.195.2 FHIRDeviceStatus

Codes representing the current status of the device - on, off, suspended, etc.

This code system http://hl7.org/fhir/device-definition-status defines the following codes:

Code | Display | Definition
active | Active | The device is available for use. Note: For *implanted devices* this means that the device is implanted in the patient.
inactive | Inactive | The device is no longer available for use (e.g. lost, expired, damaged). Note: For *implanted devices* this means that the device has been removed from the patient.
entered-in-error | Entered in Error | The device was entered in error and voided.
unknown | Unknown | The status of the device has not been determined.

See the full registry of code systems defined as part of FHIR.

Explanation of the columns that may appear on this page:

Level | A few code lists that FHIR defines are hierarchical - each code is assigned a level. See Code System for further information.
Source | The source of the definition of the code (when the value set draws in codes defined elsewhere)
Code | The code (used as the code in the resource instance). If the code is in italics, this indicates that the code is not selectable ('Abstract')
Display | The display (used in the display element of a Coding). If there is no display, implementers should not simply display the code, but map the concept into their application
Definition | An explanation of the meaning of the concept
Comments | Additional notes about how to use the code

4.3.14.196 Code System http://terminology.hl7.org/CodeSystem/goal-acceptance-status

URL: https://hl7.org/fhir/R4/codesystem-goal-acceptance-status.html
Vocabulary Work Group | Maturity Level: 0 | Informative | Use Context: Any

This is a code system defined by the FHIR project.

Summary

Defining URL: | http://terminology.hl7.org/CodeSystem/goal-acceptance-status
Version: | 4.0.1
Name: | GoalAcceptanceStatus
Title: | GoalAcceptanceStatus
Definition: | Codes indicating whether the goal has been accepted by a stakeholder.
Committee: | ??
OID: | 2.16.840.1.113883.4.642.4.1270 (for OID based terminology systems)

Source Resource | XML / JSON

This Code system is used in the following value sets:

• ValueSet: GoalAcceptanceStatus (Codes indicating whether the goal has been accepted by a stakeholder.)

• ValueSet: GoalAcceptanceStatus (Codes indicating whether the goal has been accepted by a stakeholder.)

4.3.14.196.1 Content

4.3.14.196.2 GoalAcceptanceStatus

Codes indicating whether the goal has been accepted by a stakeholder.

This code system http://terminology.hl7.org/CodeSystem/goal-acceptance-status defines the following codes:

Code | Display | Definition
agree | Agree | Stakeholder supports pursuit of the goal.
disagree | Disagree | Stakeholder is not in support of the pursuit of the goal.
pending | Pending | Stakeholder has not yet made a decision on whether they support the goal.

See the full registry of code systems defined as part of FHIR.

Explanation of the columns that may appear on this page:

Level | A few code lists that FHIR defines are hierarchical - each code is assigned a level. See Code System for further information.
Source | The source of the definition of the code (when the value set draws in codes defined elsewhere)
Code | The code (used as the code in the resource instance). If the code is in italics, this indicates that the code is not selectable ('Abstract')
Display | The display (used in the display element of a Coding). If there is no display, implementers should not simply display the code, but map the concept into their application
Definition | An explanation of the meaning of the concept
Comments | Additional notes about how to use the code

4.3.14.197 Code System http://terminology.hl7.org/CodeSystem/composite-measure-scoring

URL: https://hl7.org/fhir/R4/codesystem-composite-measure-scoring.html
Clinical Quality Information Work Group | Maturity Level: 2 | Trial Use | Use Context: Any

This is a code system defined by the FHIR project.

Summary

Defining URL: | http://terminology.hl7.org/CodeSystem/composite-measure-scoring
Version: | 4.0.1
Name: | CompositeMeasureScoring
Title: | CompositeMeasureScoring
Definition: | The composite scoring method of the measure.
Committee: | Clinical Quality Information Work Group
OID: | 2.16.840.1.113883.4.642.4.1235 (for OID based terminology systems)
Source Resource | XML / JSON

This Code system is used in the following value sets:

• ValueSet: CompositeMeasureScoring (The composite scoring method of the measure.)

• ValueSet: CompositeMeasureScoring (The composite scoring method of the measure.)

4.3.14.197.1 Content

4.3.14.197.2 CompositeMeasureScoring

The composite scoring method of the measure.

This code system http://terminology.hl7.org/CodeSystem/composite-measure-scoring defines the following codes:

Code | Display | Definition
opportunity | Opportunity | Opportunity scoring combines the scores from component measures by combining the numerators and denominators for each component.
all-or-nothing | All-or-nothing | All-or-nothing scoring includes an individual in the numerator of the composite measure if they are in the numerators of all of the component measures in which they are in the denominator.
linear | Linear | Linear scoring gives an individual a score based on the number of numerators in which they appear.
weighted | Weighted | Weighted scoring gives an individual a score based on a weighted factor for each component numerator in which they appear.

See the full registry of code systems defined as part of FHIR.

Explanation of the columns that may appear on this page:

Level | A few code lists that FHIR defines are hierarchical - each code is assigned a level. See Code System for further information.
Source | The source of the definition of the code (when the value set draws in codes defined elsewhere)

Code | The code (used as the code in the resource instance). If the code is in italics, this indicates that the code is not selectable ('Abstract')
Display | The display (used in the display element of a Coding). If there is no display, implementers should not simply display the code, but map the concept into their application
Definition | An explanation of the meaning of the concept
Comments | Additional notes about how to use the code

4.3.14.198 Code System http://hl7.org/fhir/allergy-intolerance-type

URL: https://hl7.org/fhir/R4/codesystem-allergy-intolerance-type.html
Patient Care Work Group | Maturity Level: 3 | Trial Use | Use Context: Any

This is a code system defined by the FHIR project.

Summary

Defining URL: | http://hl7.org/fhir/allergy-intolerance-type
Version: | 4.0.1
Name: | AllergyIntoleranceType
Title: | AllergyIntoleranceType
Definition: | Identification of the underlying physiological mechanism for a Reaction Risk.
Committee: | Patient Care Work Group
OID: | 2.16.840.1.113883.4.642.4.132 (for OID based terminology systems)
Source Resource | XML / JSON

This Code system is used in the following value sets:

• ValueSet: AllergyIntoleranceType (Identification of the underlying physiological mechanism for a Reaction Risk.)

• ValueSet: AllergyIntoleranceType (Identification of the underlying physiological mechanism for a Reaction Risk.)

4.3.14.198.1 Content

4.3.14.198.2 AllergyIntoleranceType

Identification of the underlying physiological mechanism for a Reaction Risk.

This code system http://hl7.org/fhir/allergy-intolerance-type defines the following codes:

Code | Display | Definition
allergy | Allergy | A propensity for hypersensitive reaction(s) to a substance. These reactions are most typically type I hypersensitivity, plus other "allergy-like" reactions, including pseudoallergy.
intolerance | Intolerance | A propensity for adverse reactions to a substance that is not judged to be allergic or "allergy-like". These reactions are typically (but not necessarily) non-immune. They are to some degree idiosyncratic and/or patient-specific (i.e. are not a reaction that is expected to occur with most or all patients given similar circumstances).

See the full registry of code systems defined as part of FHIR.

Explanation of the columns that may appear on this page:

Level | A few code lists that FHIR defines are hierarchical - each code is assigned a level. See Code System for further information.
Source | The source of the definition of the code (when the value set draws in codes defined elsewhere)
Code | The code (used as the code in the resource instance). If the code is in italics, this indicates that the code is not selectable ('Abstract')
Display | The display (used in the display element of a Coding). If there is no display, implementers should not simply display the code, but map the concept into their application
Definition | An explanation of the meaning of the concept
Comments | Additional notes about how to use the code

4.3.14.199 Code System http://hl7.org/fhir/note-type

URL: https://hl7.org/fhir/R4/codesystem-note-type.html
Financial Management Work Group | Maturity Level: 2 | Trial Use | Use Context: Any

This is a code system defined by the FHIR project.

Summary

Defining URL: | http://hl7.org/fhir/note-type
Version: | 4.0.1
Name: | NoteType
Title: | NoteType
Definition: | The presentation types of notes.
Committee: | Financial Management Work Group
OID: | 2.16.840.1.113883.4.642.4.16 (for OID based terminology systems)
Source Resource | XML / JSON

This Code system is used in the following value sets:

• ValueSet: NoteType (The presentation types of notes.)

• ValueSet: NoteType (The presentation types of notes.)

4.3.14.199.1 Content

4.3.14.199.2 NoteType

The presentation types of notes.

This code system http://hl7.org/fhir/note-type defines the following codes:

Code | Display | Definition
display | Display | Display the note.
print | Print (Form) | Print the note on the form.
printoper | Print (Operator) | Print the note for the operator.

See the full registry of code systems defined as part of FHIR.

Explanation of the columns that may appear on this page:

Level | A few code lists that FHIR defines are hierarchical - each code is assigned a level. See Code System for further information.
Source | The source of the definition of the code (when the value set draws in codes defined elsewhere)
Code | The code (used as the code in the resource instance). If the code is in italics, this indicates that the code is not selectable ('Abstract')
Display | The display (used in the display element of a Coding). If there is no display, implementers should not simply display the code, but map the concept into their application
Definition | An explanation of the meaning of the concept
Comments | Additional notes about how to use the code

4.3.14.200 Code System http://hl7.org/fhir/consent-provision-type

URL: https://hl7.org/fhir/R4/codesystem-consent-provision-type.html
Community Based Collaborative Care Work Group | Maturity Level: 2 | Trial Use | Use Context: Any

This is a code system defined by the FHIR project.

Summary

Defining URL: | http://hl7.org/fhir/consent-provision-type
Version: | 4.0.1
Name: | ConsentProvisionType
Title: | ConsentProvisionType
Definition: | How a rule statement is applied, such as adding additional consent or removing consent.
Committee: | Community Based Collaborative Care Work Group
OID: | 2.16.840.1.113883.4.642.4.758 (for OID based terminology systems)
Source Resource | XML / JSON

This Code system is used in the following value sets:

• ValueSet: ConsentProvisionType (How a rule statement is applied, such as adding additional consent or removing consent.)

• ValueSet: ConsentProvisionType (How a rule statement is applied, such as adding additional consent or removing consent.)

4.3.14.200.1 Content

4.3.14.200.2 ConsentProvisionType

How a rule statement is applied, such as adding additional consent or removing consent.

This code system http://hl7.org/fhir/consent-provision-type defines the following codes:

Code | Display | Definition
deny | Opt Out | Consent is denied for actions meeting these rules.
permit | Opt In | Consent is provided for actions meeting these rules.

See the full registry of code systems defined as part of FHIR.

Explanation of the columns that may appear on this page:

Level | A few code lists that FHIR defines are hierarchical - each code is assigned a level. See Code System for further information.
Source | The source of the definition of the code (when the value set draws in codes defined elsewhere)
Code | The code (used as the code in the resource instance). If the code is in italics, this indicates that the code is not selectable ('Abstract')
Display | The display (used in the display element of a Coding). If there is no display, implementers should not simply display the code, but map the concept into their application
Definition | An explanation of the meaning of the concept
Comments | Additional notes about how to use the code

4.3.14.201 Code System http://hl7.org/fhir/constraint-severity

URL: https://hl7.org/fhir/R4/codesystem-constraint-severity.html
FHIR Infrastructure Work Group | Maturity Level: N | Normative (from v4.0.0) | Use Context: Any

This is a code system defined by the FHIR project.

Summary

Defining URL: | http://hl7.org/fhir/constraint-severity
Version: | 4.0.1
Name: | ConstraintSeverity
Title: | ConstraintSeverity
Definition: | SHALL applications comply with this constraint?
Committee: | FHIR Infrastructure Work Group
OID: | 2.16.840.1.113883.4.642.4.82 (for OID based terminology systems)
Source Resource | XML / JSON

This Code system is used in the following value sets:

• ValueSet: ConstraintSeverity (SHALL applications comply with this constraint?)

• ValueSet: ConstraintSeverity (SHALL applications comply with this constraint?)

4.3.14.201.1 Content

4.3.14.201.2 ConstraintSeverity

SHALL applications comply with this constraint?

This code system http://hl7.org/fhir/constraint-severity defines the following codes:

Code | Display | Definition
error | Error | If the constraint is violated, the resource is not conformant.
warning | Warning | If the constraint is violated, the resource is conformant, but it is not necessarily following best practice.

See the full registry of code systems defined as part of FHIR.

Explanation of the columns that may appear on this page:

Level | A few code lists that FHIR defines are hierarchical - each code is assigned a level. See Code System for further information.
Source | The source of the definition of the code (when the value set draws in codes defined elsewhere)
Code | The code (used as the code in the resource instance). If the code is in italics, this indicates that the code is not selectable ('Abstract')
Display | The display (used in the display element of a Coding). If there is no display, implementers should not simply display the code, but map the concept into their application
Definition | An explanation of the meaning of the concept
Comments | Additional notes about how to use the code

4.3.14.202 Code System http://terminology.hl7.org/CodeSystem/claiminformationcategory

URL: https://hl7.org/fhir/R4/codesystem-claim-informationcategory.html
Financial Management Work Group | Maturity Level: 1 | Draft | Use Context: Any

This is a code system defined by the FHIR project.

Summary

Defining URL: | http://terminology.hl7.org/CodeSystem/claiminformationcategory
Version: | 4.0.1
Name: | ClaimInformationCategoryCodes
Title: | Claim Information Category Codes
Definition: | This value set includes sample Information Category codes.
Committee: | Financial Management Work Group
OID: | 2.16.840.1.113883.4.642.4.1163 (for OID based terminology systems)
Copyright: | This is an example set.
Source Resource | XML / JSON

This Code system is used in the following value sets:

• ValueSet: Claim Information Category Codes (This value set includes sample Information Category codes.)

• ValueSet: Claim Information Category Codes (This value set includes sample Information Category codes.)

4.3.14.202.1 Content

4.3.14.202.2 Claim Information Category Codes

This value set includes sample Information Category codes.

Copyright Statement:

This is an example set.

This code system http://terminology.hl7.org/CodeSystem/claiminformationcategory defines the following codes:

Code | Display | Definition
info | Information | Codes conveying additional situation and condition information.
discharge | Discharge | Discharge status and discharge to locations.
onset | Onset | Period, start or end dates of aspects of the Condition.
related | Related Services | Nature and date of the related event e.g. Last exam, service, X-ray etc.
exception | Exception | Insurance policy exceptions.
material | Materials Forwarded | Materials being forwarded, e.g. Models, molds, images, documents.
attachment | Attachment | Materials attached such as images, documents and resources.
missingtooth | Missing Tooth | Teeth which are missing for any reason, for example: prior extraction, never developed.
prosthesis | Prosthesis | The type of prosthesis and date of supply if a previously supplied prosthesis.
other | Other | Other information identified by the type.system.
hospitalized | Hospitalized | An indication that the patient was hospitalized, the period if known otherwise a Yes/No (boolean).
employmentimpacted | EmploymentImpacted | An indication that the patient was unable to work, the period if known otherwise a Yes/No (boolean).
externalcause | External Caause | The external cause of an illness or injury.
patientreasonforvisit | Patient Reason for Visit | The reason for the patient visit.

See the full registry of code systems defined as part of FHIR.

Explanation of the columns that may appear on this page:

Level | A few code lists that FHIR defines are hierarchical - each code is assigned a level. See Code System for further information.
Source | The source of the definition of the code (when the value set draws in codes defined elsewhere)
Code | The code (used as the code in the resource instance). If the code is in italics, this indicates that the code is not selectable ('Abstract')
Display | The display (used in the display element of a Coding). If there is no display, implementers should not simply display the code, but map the concept into their application
Definition | An explanation of the meaning of the concept
Comments | Additional notes about how to use the code

4.3.14.203 Code System http://hl7.org/fhir/supplyrequest-status

URL: https://hl7.org/fhir/R4/codesystem-supplyrequest-status.html
Orders and Observations Work Group | Maturity Level: 1 | Trial Use | Use Context: Any

This is a code system defined by the FHIR project.

Summary

Defining URL: | http://hl7.org/fhir/supplyrequest-status
Version: | 4.0.1
Name: | SupplyRequestStatus
Title: | SupplyRequestStatus
Definition: | Status of the supply request.
Committee: | Orders and Observations Work Group
OID: | 2.16.840.1.113883.4.642.4.696 (for OID based terminology systems)
Source Resource | XML / JSON

This Code system is used in the following value sets:

• ValueSet: SupplyRequestStatus (Status of the supply request.)
• ValueSet: SupplyRequestStatus (Status of the supply request.)

4.3.14.203.1 Content

4.3.14.203.2 SupplyRequestStatus

Status of the supply request.

This code system http://hl7.org/fhir/supplyrequest-status defines the following codes:

Code | Display | Definition
draft | Draft | The request has been created but is not yet complete or ready for action.
active | Active | The request is ready to be acted upon.
suspended | Suspended | The authorization/request to act has been temporarily withdrawn but is expected to resume in the future.
cancelled | Cancelled | The authorization/request to act has been terminated prior to the full completion of the intended actions. No further activity should occur.
completed | Completed | Activity against the request has been sufficiently completed to the satisfaction of the requester.
entered-in-error | Entered in Error | This electronic record should never have existed, though it is possible that real-world decisions were based on it. (If real-world activity has occurred, the status should be "cancelled" rather than "entered-in-error".).
unknown | Unknown | The authoring/source system does not know which of the status values currently applies for this observation. Note: This concept is not to be used for "other" - one of the listed statuses is presumed to apply, but the authoring/source system does not know which.

See the full registry of code systems defined as part of FHIR.

Explanation of the columns that may appear on this page:

Level | A few code lists that FHIR defines are hierarchical - each code is assigned a level. See Code System for further information.
Source | The source of the definition of the code (when the value set draws in codes defined elsewhere)
Code | The code (used as the code in the resource instance). If the code is in italics, this indicates that the code is not selectable ('Abstract')
Display | The display (used in the display element of a Coding). If there is no display, implementers should not simply display the code, but map the concept into their application
Definition | An explanation of the meaning of the concept
Comments | Additional notes about how to use the code

4.3.14.204 Code System http://hl7.org/fhir/quality-type

URL: https://hl7.org/fhir/R4/codesystem-quality-type.html
Clinical Genomics Work Group | Maturity Level: 1 | Trial Use | Use Context: Any

This is a code system defined by the FHIR project.

Summary

Defining URL: | http://hl7.org/fhir/quality-type
Version: | 4.0.1
Name: | qualityType
Title: | qualityType
Definition: | Type for quality report.
Committee: | Clinical Genomics Work Group
OID: | 2.16.840.1.113883.4.642.4.229 (for OID based terminology systems)
Source Resource | XML / JSON

This Code system is used in the following value sets:

• ValueSet: qualityType (Type for quality report.)

• ValueSet: qualityType (Type for quality report.)

4.3.14.204.1 Content

4.3.14.204.2 qualityType

Type for quality report.

This code system http://hl7.org/fhir/quality-type defines the following codes:

Code | Display | Definition
indel | INDEL Comparison | INDEL Comparison.
snp | SNP Comparison | SNP Comparison.
unknown | UNKNOWN Comparison | UNKNOWN Comparison.

See the full registry of code systems defined as part of FHIR.

Explanation of the columns that may appear on this page:

Level | A few code lists that FHIR defines are hierarchical - each code is assigned a level. See Code System for further information.
Source | The source of the definition of the code (when the value set draws in codes defined elsewhere)
Code | The code (used as the code in the resource instance). If the code is in italics, this indicates that the code is not selectable ('Abstract')
Display | The display (used in the display element of a Coding). If there is no display, implementers should not simply display the code, but map the concept into their application
Definition | An explanation of the meaning of the concept
Comments | Additional notes about how to use the code

4.3.14.205 Code System http://terminology.hl7.org/CodeSystem/validation-type

URL: https://hl7.org/fhir/R4/codesystem-verificationresult-validation-type.html
Patient Administration Work Group | Maturity Level: 0 | Informative | Use Context: Any

This is a code system defined by the FHIR project.

Summary

Defining URL: | http://terminology.hl7.org/CodeSystem/validation-type
Version: | 4.0.1
Name: | validation-type
Title: | Validation-type
Definition: | What the target is validated against
Committee: | Patient Administration Work Group
OID: | 2.16.840.1.113883.4.642.1.887 (for OID based terminology systems)
Source Resource | XML / JSON

This Code system is used in the following value sets:

• ValueSet: Validation-type (What the target is validated against)

• ValueSet: Validation-type (What the target is validated against)

4.3.14.205.1 Content

4.3.14.205.2 Validation-type

What the target is validated against

This code system http://terminology.hl7.org/CodeSystem/validation-type defines the following codes:

Code | Display | Definition
nothing | Nothing
primary | Primary Source
multiple | Multiple Sources

See the full registry of code systems defined as part of FHIR.

Explanation of the columns that may appear on this page:

Level | A few code lists that FHIR defines are hierarchical - each code is assigned a level. See Code System for further information.
Source | The source of the definition of the code (when the value set draws in codes defined elsewhere)
Code | The code (used as the code in the resource instance). If the code is in italics, this indicates that the code is not selectable ('Abstract')
Display | The display (used in the display element of a Coding). If there is no display, implementers should not simply display the code, but map the concept into their application
Definition | An explanation of the meaning of the concept
Comments | Additional notes about how to use the code

4.3.14.206 Code System http://hl7.org/fhir/reaction-event-severity

URL: https://hl7.org/fhir/R4/codesystem-reaction-event-severity.html
Patient Care Work Group | Maturity Level: 3 | Trial Use | Use Context: Any

This is a code system defined by the FHIR project.

Summary

Defining URL: | http://hl7.org/fhir/reaction-event-severity
Version: | 4.0.1
Name: | AllergyIntoleranceSeverity
Title: | AllergyIntoleranceSeverity
Definition: | Clinical assessment of the severity of a reaction event as a whole, potentially considering multiple different manifestations.
Committee: | Patient Care Work Group
OID: | 2.16.840.1.113883.4.642.4.136 (for OID based terminology systems)
Source Resource | XML / JSON

This Code system is used in the following value sets:

• ValueSet: AllergyIntoleranceSeverity (Clinical assessment of the severity of a reaction event as a whole, potentially considering multiple different manifestations.)

• ValueSet: AllergyIntoleranceSeverity (Clinical assessment of the severity of a reaction event as a whole, potentially considering multiple different manifestations.)

4.3.14.206.1 Content

4.3.14.206.2 AllergyIntoleranceSeverity

Clinical assessment of the severity of a reaction event as a whole, potentially considering multiple different manifestations.

This code system http://hl7.org/fhir/reaction-event-severity defines the following codes:

Code | Display | Definition
mild | Mild | Causes mild physiological effects.
moderate | Moderate | Causes moderate physiological effects.
severe | Severe | Causes severe physiological effects.

See the full registry of code systems defined as part of FHIR.

Explanation of the columns that may appear on this page:

Level | A few code lists that FHIR defines are hierarchical - each code is assigned a level. See Code System for further information.
Source | The source of the definition of the code (when the value set draws in codes defined elsewhere)
Code | The code (used as the code in the resource instance). If the code is in italics, this indicates that the code is not selectable ('Abstract')

Display | The display (used in the display element of a Coding). If there is no display, implementers should not simply display the code, but map the concept into their application
Definition | An explanation of the meaning of the concept
Comments | Additional notes about how to use the code

4.3.14.207 Code System http://terminology.hl7.org/CodeSystem/basic-resource-type

URL: https://hl7.org/fhir/R4/codesystem-basic-resource-type.html
FHIR Infrastructure Work Group | Maturity Level: 1 | Draft | Use Context: Any

This is a code system defined by the FHIR project.

Summary

Defining URL: | http://terminology.hl7.org/CodeSystem/basic-resource-type
Version: | 4.0.1
Name: | BasicResourceTypes
Title: | Basic Resource Types
Definition: | This value set defines codes for resources not yet supported by (or which will never be supported by) FHIR. Many of the codes listed here will eventually be turned into official resources. However, there is no guarantee that any particular resource will be created nor that the scope will be exactly as defined by the codes presented here. Codes in this set will be deprecated if/when formal resources are defined that encompass these concepts.
Committee: | FHIR Infrastructure Work Group
OID: | 2.16.840.1.113883.4.642.4.1072 (for OID based terminology systems)
Source Resource | XML / JSON

This Code system is used in the following value sets:

• ValueSet: Basic Resource Types (This value set defines codes for resources not yet supported by (or which will never be supported by) FHIR. Many of the codes listed here will eventually be turned into official resources. However, there is no guarantee that any particular resource will be created nor that the scope will be exactly as defined by the codes presented here. Codes in this set will be deprecated if/when formal resources are defined that encompass these concepts.)

• ValueSet: Basic Resource Types (This value set defines codes for resources not yet supported by (or which will never be supported by) FHIR. Many of the codes listed here will eventually be turned into official resources. However, there is no guarantee that any particular resource will be created nor that the scope will be exactly as defined by the codes presented here. Codes in this set will be deprecated if/when formal resources are defined that encompass these concepts.)

4.3.14.207.1 Content

4.3.14.207.2 Basic Resource Types

This value set defines codes for resources not yet supported by (or which will never be supported by) FHIR. Many of the codes listed here will eventually be turned into official resources. However, there is no guarantee that any particular resource will be created nor that the scope will be exactly as defined by the codes presented here. Codes in this set will be deprecated if/when formal resources are defined that encompass these concepts.

This code system http://terminology.hl7.org/CodeSystem/basic-resource-type defines the following codes:

Code | Display | Definition
consent | Consent | An assertion of permission for an activity or set of activities to occur, possibly subject to particular limitations; e.g. surgical consent, information disclosure consent, etc.
referral | Referral | A request that care of a particular type be provided to a patient. Could involve the transfer of care, a consult, etc.
advevent | Adverse Event | An undesired reaction caused by exposure to some agent (e.g. a medication, immunization, food, or environmental agent).
aptmtreq | Appointment Request | A request that a time be scheduled for a type of service for a specified patient, potentially subject to other constraints
transfer | Transfer | The transition of a patient or set of material from one location to another
diet | Diet | The specification of a set of food and/or other nutritional material to be delivered to a patient.
adminact | Administrative Activity | An occurrence of a non-care-related event in the healthcare domain, such as approvals, reviews, etc.
exposure | Exposure | Record of a situation where a subject was exposed to a substance. Usually of interest to public health.
investigation | Investigation | A formalized inquiry into the circumstances surrounding a particular unplanned event or potential event for the purposes of identifying possible causes and contributing factors for the event
account | Account | A financial instrument used to track costs, charges or other amounts.
invoice | Invoice | A request for payment for goods and/or services. Includes the idea of a healthcare insurance claim.
adjudicat | Invoice Adjudication | The determination of what will be paid against a particular invoice based on coverage, plan rules, etc.
predetreq | Pre-determination Request | A request for a pre-determination of the cost that would be paid under an insurance plan for a hypothetical claim for goods or services
predetermine | Predetermination | An adjudication of what would be paid under an insurance plan for a hypothetical claim for goods or services

study | Study | An investigation to determine information about a particular therapy or product
protocol | Protocol | A set of (possibly conditional) steps to be taken to achieve some aim. Includes study protocols, treatment protocols, emergency protocols, etc.

See the full registry of code systems defined as part of FHIR.

Explanation of the columns that may appear on this page:

Level | A few code lists that FHIR defines are hierarchical - each code is assigned a level. See Code System for further information.
Source | The source of the definition of the code (when the value set draws in codes defined elsewhere)
Code | The code (used as the code in the resource instance). If the code is in italics, this indicates that the code is not selectable ('Abstract')
Display | The display (used in the display element of a Coding). If there is no display, implementers should not simply display the code, but map the concept into their application
Definition | An explanation of the meaning of the concept
Comments | Additional notes about how to use the code

4.3.14.208 Code System http://hl7.org/fhir/capability-statement-kind

URL: https://hl7.org/fhir/R4/codesystem-capability-statement-kind.html
FHIR Infrastructure Work Group | Maturity Level: N | Normative (from v4.0.0) | Use Context: Any

| This page has been approved as part of an ANSI standard. See the Conformance Package for further details.

This is a code system defined by the FHIR project.

Summary

Defining URL: | http://hl7.org/fhir/capability-statement-kind
Version: | 4.0.1
Name: | CapabilityStatementKind
Title: | CapabilityStatementKind
Definition: | How a capability statement is intended to be used.
Committee: | FHIR Infrastructure Work Group
OID: | 2.16.840.1.113883.4.642.4.199 (for OID based terminology systems)
Source Resource | XML / JSON

This Code system is used in the following value sets:

• ValueSet: CapabilityStatementKind (How a capability statement is intended to be used.)

• ValueSet: CapabilityStatementKind (How a capability statement is intended to be used.)

4.3.14.208.1 Content

4.3.14.208.2 CapabilityStatementKind

How a capability statement is intended to be used.

This code system http://hl7.org/fhir/capability-statement-kind defines the following codes:

Code | Display | Definition | Comments
instance | Instance | The CapabilityStatement instance represents the present capabilities of a specific system instance. This is the kind returned by /metadata for a FHIR server end-point.
capability | Capability | The CapabilityStatement instance represents the capabilities of a system or piece of software, independent of a particular installation. | Elements marked as 'optional' represent configurable capabilities
requirements | Requirements | The CapabilityStatement instance represents a set of requirements for other systems to meet; e.g. as part of an implementation guide or 'request for proposal'.

See the full registry of code systems defined as part of FHIR.

Explanation of the columns that may appear on this page:

Level | A few code lists that FHIR defines are hierarchical - each code is assigned a level. See Code System for further information.
Source | The source of the definition of the code (when the value set draws in codes defined elsewhere)
Code | The code (used as the code in the resource instance). If the code is in italics, this indicates that the code is not selectable ('Abstract')
Display | The display (used in the display element of a Coding). If there is no display, implementers should not simply display the code, but map the concept into their application
Definition | An explanation of the meaning of the concept
Comments | Additional notes about how to use the code

4.3.14.209 Code System http://terminology.hl7.org/CodeSystem/communication-not-done-reason

URL: https://hl7.org/fhir/R4/codesystem-communication-not-done-reason.html
Patient Care Work Group | Maturity Level: 1 | Draft | Use Context: Any

This is a code system defined by the FHIR project.

Summary

Defining URL: | http://terminology.hl7.org/CodeSystem/communication-not-done-reason
Version: | 4.0.1
Name: | CommunicationNotDoneReason
Title: | CommunicationNotDoneReason
Definition: | Codes for the reason why a communication did not happen.
Committee: | Patient Care Work Group
OID: | 2.16.840.1.113883.4.642.4.1077 (for OID based terminology systems)
Source Resource | XML / JSON

This Code system is used in the following value sets:

• ValueSet: CommunicationNotDoneReason (Codes for the reason why a communication did not happen.)

• ValueSet: CommunicationNotDoneReason (Codes for the reason why a communication did not happen.)

4.3.14.209.1 Content

4.3.14.209.2 CommunicationNotDoneReason

Codes for the reason why a communication did not happen.

This code system http://terminology.hl7.org/CodeSystem/communication-not-done-reason defines the following codes:

Code | Display | Definition
unknown | Unknown | The communication was not done due to an unknown reason.
system-error | System Error | The communication was not done due to a system error.
invalid-phone-number | Invalid Phone Number | The communication was not done due to an invalid phone number.
recipient-unavailable | Recipient Unavailable | The communication was not done due to the recipient being unavailable.
family-objection | Family Objection | The communication was not done due to a family objection.
patient-objection | Patient Objection | The communication was not done due to a patient objection.

See the full registry of code systems defined as part of FHIR.

Explanation of the columns that may appear on this page:

Level | A few code lists that FHIR defines are hierarchical - each code is assigned a level. See Code System for further information.
Source | The source of the definition of the code (when the value set draws in codes defined elsewhere)
Code | The code (used as the code in the resource instance). If the code is in italics, this indicates that the code is not selectable ('Abstract')
Display | The display (used in the display element of a Coding). If there is no display, implementers should not simply display the code, but map the concept into their application
Definition | An explanation of the meaning of the concept
Comments | Additional notes about how to use the code

4.3.14.210 Code System http://hl7.org/fhir/report-action-result-codes

URL: https://hl7.org/fhir/R4/codesystem-report-action-result-codes.html
FHIR Infrastructure Work Group | Maturity Level: 0 | Trial Use | Use Context: Any

This is a code system defined by the FHIR project.

Summary

Defining URL: | http://hl7.org/fhir/report-action-result-codes
Version: | 4.0.1
Name: | TestReportActionResult
Title: | TestReportActionResult
Definition: | The results of executing an action.
Committee: | FHIR Infrastructure Work Group
OID: | 2.16.840.1.113883.4.642.4.721 (for OID based terminology systems)
Source Resource | XML / JSON

This Code system is used in the following value sets:

• ValueSet: TestReportActionResult (The results of executing an action.)

• ValueSet: TestReportActionResult (The results of executing an action.)

4.3.14.210.1 Content

4.3.14.210.2 TestReportActionResult

The results of executing an action.

This code system http://hl7.org/fhir/report-action-result-codes defines the following codes:

Code | Display | Definition
pass | Pass | The action was successful.
skip | Skip | The action was skipped.
fail | Fail | The action failed.

warning | Warning | The action passed but with warnings.
error | Error | The action encountered a fatal error and the engine was unable to process.

See the full registry of code systems defined as part of FHIR.

Explanation of the columns that may appear on this page:

Level | A few code lists that FHIR defines are hierarchical - each code is assigned a level. See Code System for further information.
Source | The source of the definition of the code (when the value set draws in codes defined elsewhere)
Code | The code (used as the code in the resource instance). If the code is in italics, this indicates that the code is not selectable ('Abstract')
Display | The display (used in the display element of a Coding). If there is no display, implementers should not simply display the code, but map the concept into their application
Definition | An explanation of the meaning of the concept
Comments | Additional notes about how to use the code

4.3.14.211 Code System http://terminology.hl7.org/CodeSystem/goal-category

URL: https://hl7.org/fhir/R4/codesystem-goal-category.html
Patient Care Work Group | Maturity Level: 1 | Draft | Use Context: Any

This is a code system defined at http://www.hl7.org/Special/committees/patientcare/ .

Summary

Defining URL: | http://terminology.hl7.org/CodeSystem/goal-category
Version: | 4.0.1
Name: | GoalCategory
Title: | Goal category
Definition: | Example codes for grouping goals to use for filtering or presentation.
Committee: | Patient Care Work Group
OID: | 2.16.840.1.113883.4.642.4.1097 (for OID based terminology systems)
Source Resource | XML / JSON

This Code system is used in the following value sets:

• ValueSet: Goal category (Example codes for grouping goals to use for filtering or presentation.)

• ValueSet: Goal category (Example codes for grouping goals to use for filtering or presentation.)

4.3.14.211.1 Content

4.3.14.211.2 Goal category

Example codes for grouping goals to use for filtering or presentation.

This code system http://terminology.hl7.org/CodeSystem/goal-category defines the following codes:

Code | Display | Definition
dietary | Dietary | Goals related to the consumption of food and/or beverages.
safety | Safety | Goals related to the personal protection of the subject.
behavioral | Behavioral | Goals related to the manner in which the subject acts.
nursing | Nursing | Goals related to the practice of nursing or established by nurses.
physiotherapy | Physiotherapy | Goals related to the mobility and/or motor capability of the subject.

See the full registry of code systems defined as part of FHIR.

Explanation of the columns that may appear on this page:

Level | A few code lists that FHIR defines are hierarchical - each code is assigned a level. See Code System for further information.
Source | The source of the definition of the code (when the value set draws in codes defined elsewhere)
Code | The code (used as the code in the resource instance). If the code is in italics, this indicates that the code is not selectable ('Abstract')
Display | The display (used in the display element of a Coding). If there is no display, implementers should not simply display the code, but map the concept into their application
Definition | An explanation of the meaning of the concept
Comments | Additional notes about how to use the code

4.3.14.212 Code System http://hl7.org/fhir/questionnaire-enable-behavior

URL: https://hl7.org/fhir/R4/codesystem-questionnaire-enable-behavior.html
FHIR Infrastructure Work Group | Maturity Level: 3 | Trial Use | Use Context: Any

This is a code system defined by the FHIR project.

Summary

Defining URL: | http://hl7.org/fhir/questionnaire-enable-behavior
Version: | 4.0.1
Name: | EnableWhenBehavior

Title: | EnableWhenBehavior
Definition: | Controls how multiple enableWhen values are interpreted - whether all or any must be true.
Committee: | FHIR Infrastructure Work Group
OID: | 2.16.840.1.113883.4.642.4.1008 (for OID based terminology systems)
Source Resource | XML / JSON

This Code system is used in the following value sets:

• ValueSet: EnableWhenBehavior (Controls how multiple enableWhen values are interpreted - whether all or any must be true.)

• ValueSet: EnableWhenBehavior (Controls how multiple enableWhen values are interpreted - whether all or any must be true.)

4.3.14.212.1 Content

4.3.14.212.2 EnableWhenBehavior

Controls how multiple enableWhen values are interpreted - whether all or any must be true.

This code system http://hl7.org/fhir/questionnaire-enable-behavior defines the following codes:

Code | Display | Definition
all | All | Enable the question when all the enableWhen criteria are satisfied.
any | Any | Enable the question when any of the enableWhen criteria are satisfied.

See the full registry of code systems defined as part of FHIR.

Explanation of the columns that may appear on this page:

Level | A few code lists that FHIR defines are hierarchical - each code is assigned a level. See Code System for further information.
Source | The source of the definition of the code (when the value set draws in codes defined elsewhere)
Code | The code (used as the code in the resource instance). If the code is in italics, this indicates that the code is not selectable ('Abstract')
Display | The display (used in the display element of a Coding). If there is no display, implementers should not simply display the code, but map the concept into their application
Definition | An explanation of the meaning of the concept
Comments | Additional notes about how to use the code

4.3.14.213 Code System http://hl7.org/fhir/compartment-type

URL: https://hl7.org/fhir/R4/codesystem-compartment-type.html
FHIR Infrastructure Work Group | Maturity Level: 1 | Trial Use | Use Context: Any

This is a code system defined by the FHIR project.

Summary

Defining URL: | http://hl7.org/fhir/compartment-type
Version: | 4.0.1
Name: | CompartmentType
Title: | CompartmentType
Definition: | Which type a compartment definition describes.
Committee: | FHIR Infrastructure Work Group
OID: | 2.16.840.1.113883.4.642.4.787 (for OID based terminology systems)
Source Resource | XML / JSON

This Code system is used in the following value sets:

• ValueSet: CompartmentType (Which type a compartment definition describes.)

• ValueSet: CompartmentType (Which type a compartment definition describes.)

4.3.14.213.1 Content

4.3.14.213.2 CompartmentType

Which type a compartment definition describes.

This code system http://hl7.org/fhir/compartment-type defines the following codes:

Code | Display | Definition
Patient | Patient | The compartment definition is for the patient compartment.
Encounter | Encounter | The compartment definition is for the encounter compartment.
RelatedPerson | RelatedPerson | The compartment definition is for the related-person compartment.
Practitioner | Practitioner | The compartment definition is for the practitioner compartment.
Device | Device | The compartment definition is for the device compartment.

See the full registry of code systems defined as part of FHIR.

Explanation of the columns that may appear on this page:

Level | A few code lists that FHIR defines are hierarchical - each code is assigned a level. See Code System for further information.
Source | The source of the definition of the code (when the value set draws in codes defined elsewhere)

Code | The code (used as the code in the resource instance). If the code is in italics, this indicates that the code is not selectable ('Abstract')
Display | The display (used in the display element of a Coding). If there is no display, implementers should not simply display the code, but map the concept into their application
Definition | An explanation of the meaning of the concept
Comments | Additional notes about how to use the code

4.3.14.214 Code System http://terminology.hl7.org/CodeSystem/definition-topic

URL: https://hl7.org/fhir/R4/codesystem-definition-topic.html
Clinical Decision Support Work Group | Maturity Level: 1 | Draft | Use Context: Any

This is a code system defined by the FHIR project.

Summary

Defining URL: | http://terminology.hl7.org/CodeSystem/definition-topic
Version: | 4.0.1
Name: | DefinitionTopic
Title: | DefinitionTopic
Definition: | High-level categorization of the definition, used for searching, sorting, and filtering.
Committee: | Clinical Decision Support Work Group
OID: | 2.16.840.1.113883.4.642.4.1244 (for OID based terminology systems)
Source Resource | XML / JSON

This Code system is used in the following value sets:

• ValueSet: DefinitionTopic (High-level categorization of the definition, used for searching, sorting, and filtering.)

• ValueSet: DefinitionTopic (High-level categorization of the definition, used for searching, sorting, and filtering.)

4.3.14.214.1 Content

4.3.14.214.2 DefinitionTopic

High-level categorization of the definition, used for searching, sorting, and filtering.

This code system http://terminology.hl7.org/CodeSystem/definition-topic defines the following codes:

Code | Display | Definition
treatment | Treatment | The definition is related to treatment of the patient.
education | Education | The definition is related to education of the patient.
assessment | Assessment | The definition is related to assessment of the patient.

See the full registry of code systems defined as part of FHIR.

Explanation of the columns that may appear on this page:

Level | A few code lists that FHIR defines are hierarchical - each code is assigned a level. See Code System for further information.
Source | The source of the definition of the code (when the value set draws in codes defined elsewhere)
Code | The code (used as the code in the resource instance). If the code is in italics, this indicates that the code is not selectable ('Abstract')
Display | The display (used in the display element of a Coding). If there is no display, implementers should not simply display the code, but map the concept into their application
Definition | An explanation of the meaning of the concept
Comments | Additional notes about how to use the code

4.3.14.215 Code System http://terminology.hl7.org/CodeSystem/coverage-class

URL: https://hl7.org/fhir/R4/codesystem-coverage-class.html
Financial Management Work Group | Maturity Level: 2 | Trial Use | Use Context: Any

This is a code system defined by the FHIR project.

Summary

Defining URL: | http://terminology.hl7.org/CodeSystem/coverage-class
Version: | 4.0.1
Name: | CoverageClassCodes
Title: | Coverage Class Codes
Definition: | This value set includes Coverage Class codes.
Committee: | Financial Management Work Group
OID: | 2.16.840.1.113883.4.642.4.1147 (for OID based terminology systems)
Copyright: | HL7 Inc.
Source Resource | XML / JSON

This Code system is used in the following value sets:

• ValueSet: Coverage Class Codes (This value set includes Coverage Class codes.)

• ValueSet: Coverage Class Codes (This value set includes Coverage Class codes.)

4.3.14.215.1 Content

4.3.14.215.2 Coverage Class Codes

This value set includes Coverage Class codes.

Copyright Statement:

HL7 Inc.

This code system http://terminology.hl7.org/CodeSystem/coverage-class defines the following codes:

Code	Display	Definition
group	Group	An employee group
subgroup	SubGroup	A sub-group of an employee group
plan	Plan	A specific suite of benefits.
subplan	SubPlan	A subset of a specific suite of benefits.
class	Class	A class of benefits.
subclass	SubClass	A subset of a class of benefits.
sequence	Sequence	A sequence number associated with a short-term continuance of the coverage.
rxbin	RX BIN	Pharmacy benefit manager's Business Identification Number.
rxpcn	RX PCN	A Pharmacy Benefit Manager specified Processor Control Number.
rxid	RX Id	A Pharmacy Benefit Manager specified Member ID.
rxgroup	RX Group	A Pharmacy Benefit Manager specified Group number.

See the full registry of code systems defined as part of FHIR.

Explanation of the columns that may appear on this page:

Level	A few code lists that FHIR defines are hierarchical - each code is assigned a level. See Code System for further information.
Source	The source of the definition of the code (when the value set draws in codes defined elsewhere)
Code	The code (used as the code in the resource instance). If the code is in italics, this indicates that the code is not selectable ('Abstract')
Display	The display (used in the display element of a Coding). If there is no display, implementers should not simply display the code, but map the concept into their application
Definition	An explanation of the meaning of the concept
Comments	Additional notes about how to use the code

4.3.14.216 Code System http://hl7.org/fhir/allergy-intolerance-category

URL: https://hl7.org/fhir/R4/codesystem-allergy-intolerance-category.html
Patient Care Work Group | Maturity Level: 3 | Trial Use | Use Context: Any

This is a code system defined by the FHIR project.

Summary

Defining URL:	http://hl7.org/fhir/allergy-intolerance-category
Version:	4.0.1
Name:	AllergyIntoleranceCategory
Title:	AllergyIntoleranceCategory
Definition:	Category of an identified substance associated with allergies or intolerances.
Committee:	Patient Care Work Group
OID:	2.16.840.1.113883.4.642.4.134 (for OID based terminology systems)
Source Resource	XML / JSON

This Code system is used in the following value sets:

• ValueSet: AllergyIntoleranceCategory (Category of an identified substance associated with allergies or intolerances.)

• ValueSet: AllergyIntoleranceCategory (Category of an identified substance associated with allergies or intolerances.)

4.3.14.216.1 Content

4.3.14.216.2 AllergyIntoleranceCategory

Category of an identified substance associated with allergies or intolerances.

This code system http://hl7.org/fhir/allergy-intolerance-category defines the following codes:

Code	Display	Definition
food	Food	Any substance consumed to provide nutritional support for the body.
medication	Medication	Substances administered to achieve a physiological effect.

environment | Environment | Any substances that are encountered in the environment, including any substance not already classified as food, medication, or biologic.
biologic | Biologic | A preparation that is synthesized from living organisms or their products, especially a human or animal protein, such as a hormone or antitoxin, that is used as a diagnostic, preventive, or therapeutic agent. Examples of biologic medications include: vaccines; allergenic extracts, which are used for both diagnosis and treatment (for example, allergy shots); gene therapies; cellular therapies. There are other biologic products, such as tissues, which are not typically associated with allergies.

See the full registry of code systems defined as part of FHIR.

Explanation of the columns that may appear on this page:

Level | A few code lists that FHIR defines are hierarchical - each code is assigned a level. See Code System for further information.
Source | The source of the definition of the code (when the value set draws in codes defined elsewhere)
Code | The code (used as the code in the resource instance). If the code is in italics, this indicates that the code is not selectable ('Abstract')
Display | The display (used in the display element of a Coding). If there is no display, implementers should not simply display the code, but map the concept into their application
Definition | An explanation of the meaning of the concept
Comments | Additional notes about how to use the code

4.3.14.217 Code System http://terminology.hl7.org/CodeSystem/coverage-copay-type

URL: https://hl7.org/fhir/R4/codesystem-coverage-copay-type.html
Financial Management Work Group | Maturity Level: 2 | Trial Use | Use Context: Any

This is a code system defined by the FHIR project.

Summary

Defining URL: | http://terminology.hl7.org/CodeSystem/coverage-copay-type
Version: | 4.0.1
Name: | CoverageCopayTypeCodes
Title: | Coverage Copay Type Codes
Definition: | This value set includes sample Coverage Copayment Type codes.
Committee: | Financial Management Work Group
OID: | 2.16.840.1.113883.4.642.4.1149 (for OID based terminology systems)
Copyright: | This is an example set.
Source Resource | XML / JSON

This Code system is used in the following value sets:

• ValueSet: Coverage Copay Type Codes (This value set includes sample Coverage Copayment Type codes.)
• ValueSet: Coverage Copay Type Codes (This value set includes sample Coverage Copayment Type codes.)

4.3.14.217.1 Content

4.3.14.217.2 Coverage Copay Type Codes

This value set includes sample Coverage Copayment Type codes.

Copyright Statement:

This is an example set.

This code system http://terminology.hl7.org/CodeSystem/coverage-copay-type defines the following codes:

Code | Display | Definition
gpvisit | GP Office Visit | An office visit for a general practitioner of a discipline.
spvisit | Specialist Office Visit | An office visit for a specialist practitioner of a discipline
emergency | Emergency | An episode in an emergency department.
inpthosp | Inpatient Hospital | An episode of an Inpatient hospital stay.
televisit | Tele-visit | A visit held where the patient is remote relative to the practitioner, e.g. by phone, computer or video conference.
urgentcare | Urgent Care | A visit to an urgent care facility - typically a community care clinic.
copaypct | Copay Percentage | A standard percentage applied to all classes or service or product not otherwise specified.
copay | Copay Amount | A standard fixed currency amount applied to all classes or service or product not otherwise specified.
deductible | Deductible | The accumulated amount of patient payment before the coverage begins to pay for services.
maxoutofpocket | Maximum out of pocket | The maximum amout of payment for services which a patient, or family, is expected to incur - typically annually.

See the full registry of code systems defined as part of FHIR.

Explanation of the columns that may appear on this page:

Level | A few code lists that FHIR defines are hierarchical - each code is assigned a level. See Code System for further information.
Source | The source of the definition of the code (when the value set draws in codes defined elsewhere)
Code | The code (used as the code in the resource instance). If the code is in italics, this indicates that the code is not selectable ('Abstract')
Display | The display (used in the display element of a Coding). If there is no display, implementers should not simply display the code, but map the concept into their application
Definition | An explanation of the meaning of the concept

Comments | Additional notes about how to use the code

4.3.14.218 Code System http://hl7.org/fhir/adverse-event-actuality

URL: https://hl7.org/fhir/R4/codesystem-adverse-event-actuality.html
Patient Care Work Group | Maturity Level: 0 | Trial Use | Use Context: Any

This is a code system defined by the FHIR project.

Summary

Defining URL: | http://hl7.org/fhir/adverse-event-actuality
Version: | 4.0.1
Name: | AdverseEventActuality
Title: | AdverseEventActuality
Definition: | Overall nature of the adverse event, e.g. real or potential.
Committee: | Patient Care Work Group
OID: | 2.16.840.1.113883.4.642.4.832 (for OID based terminology systems)
Source Resource | XML / JSON

This Code system is used in the following value sets:

• ValueSet: AdverseEventActuality (Overall nature of the adverse event, e.g. real or potential.)

• ValueSet: AdverseEventActuality (Overall nature of the adverse event, e.g. real or potential.)

4.3.14.218.1 Content

4.3.14.218.2 AdverseEventActuality

Overall nature of the adverse event, e.g. real or potential.

This code system http://hl7.org/fhir/adverse-event-actuality defines the following codes:

Code | Display | Definition
actual | Adverse Event | The adverse event actually happened regardless of whether anyone was affected or harmed.
potential | Potential Adverse Event | A potential adverse event.

See the full registry of code systems defined as part of FHIR.

Explanation of the columns that may appear on this page:

Level | A few code lists that FHIR defines are hierarchical - each code is assigned a level. See Code System for further information.
Source | The source of the definition of the code (when the value set draws in codes defined elsewhere)
Code | The code (used as the code in the resource instance). If the code is in italics, this indicates that the code is not selectable ('Abstract')
Display | The display (used in the display element of a Coding). If there is no display, implementers should not simply display the code, but map the concept into their application
Definition | An explanation of the meaning of the concept
Comments | Additional notes about how to use the code

4.3.14.219 Code System http://hl7.org/fhir/observation-status

URL: https://hl7.org/fhir/R4/codesystem-observation-status.html
Clinical Decision Support Work Group | Maturity Level: N | Normative (from v4.0.0) | Use Context: Any

| This page has been approved as part of an ANSI standard. See the Observation Package for further details.

This is a code system defined by the FHIR project.

Summary

Defining URL: | http://hl7.org/fhir/observation-status
Version: | 4.0.1
Name: | ObservationStatus
Title: | ObservationStatus
Definition: | Codes providing the status of an observation.
Committee: | Clinical Decision Support Work Group
OID: | 2.16.840.1.113883.4.642.4.401 (for OID based terminology systems)
Source Resource | XML / JSON

This Code system is used in the following value sets:

• ValueSet: ObservationStatus (Codes providing the status of an observation.)

• ValueSet: ObservationStatus (Codes providing the status of an observation.)

4.3.14.219.1 Content

4.3.14.219.2 ObservationStatus

Codes providing the status of an observation.

This code system http://hl7.org/fhir/observation-status defines the following codes:

Lvl | Code | Display | Definition
1 | registered | Registered | The existence of the observation is registered, but there is no result yet available.
1 | preliminary | Preliminary | This is an initial or interim observation: data may be incomplete or unverified.
1 | final | Final | The observation is complete and there are no further actions needed. Additional information such "released", "signed", etc would be represented using [Provenance](provenance.html) which provides not only the act but also the actors and dates and other related data. These act states would be associated with an observation status of `preliminary` until they are all completed and then a status of `final` would be applied.
1 | amended | Amended | Subsequent to being Final, the observation has been modified subsequent. This includes updates/new information and corrections.
2 | corrected | Corrected | Subsequent to being Final, the observation has been modified to correct an error in the test result.
1 | cancelled | Cancelled | The observation is unavailable because the measurement was not started or not completed (also sometimes called "aborted").
1 | entered-in-error | Entered in Error | The observation has been withdrawn following previous final release. This electronic record should never have existed, though it is possible that real-world decisions were based on it. (If real-world activity has occurred, the status should be "cancelled" rather than "entered-in-error".).
1 | unknown | Unknown | The authoring/source system does not know which of the status values currently applies for this observation. Note: This concept is not to be used for "other" - one of the listed statuses is presumed to apply, but the authoring/source system does not know which.

See the full registry of code systems defined as part of FHIR.

Explanation of the columns that may appear on this page:

Level | A few code lists that FHIR defines are hierarchical - each code is assigned a level. See Code System for further information.
Source | The source of the definition of the code (when the value set draws in codes defined elsewhere)
Code | The code (used as the code in the resource instance). If the code is in italics, this indicates that the code is not selectable ('Abstract')
Display | The display (used in the display element of a Coding). If there is no display, implementers should not simply display the code, but map the concept into their application
Definition | An explanation of the meaning of the concept
Comments | Additional notes about how to use the code

4.3.14.220 Code System http://hl7.org/fhir/item-type

URL: https://hl7.org/fhir/R4/codesystem-item-type.html
FHIR Infrastructure Work Group | Maturity Level: 3 | Trial Use | Use Context: Any

This is a code system defined by the FHIR project.

Summary

Defining URL: | http://hl7.org/fhir/item-type
Version: | 4.0.1
Name: | QuestionnaireItemType
Title: | QuestionnaireItemType
Definition: | Distinguishes groups from questions and display text and indicates data type for questions.
Committee: | FHIR Infrastructure Work Group
OID: | 2.16.840.1.113883.4.642.4.445 (for OID based terminology systems)
Source Resource | XML / JSON

This Code system is used in the following value sets:

• ValueSet: QuestionnaireItemType (Distinguishes groups from questions and display text and indicates data type for questions.)

• ValueSet: QuestionnaireItemType (Distinguishes groups from questions and display text and indicates data type for questions.)

4.3.14.220.1 Content

4.3.14.220.2 QuestionnaireItemType

Distinguishes groups from questions and display text and indicates data type for questions.

Properties

Code | URL | Description | Type
notSelectable | http://hl7.org/fhir/concept-properties#notSelectable | Indicates that the code is abstract - only intended to be used as a selector for other concepts | boolean

This code system http://hl7.org/fhir/item-type defines the following codes:

Lvl | Code | Display | Definition
1 | group | Group | An item with no direct answer but should have at least one child item.
1 | display | Display | Text for display that will not capture an answer or have child items.
1 | question | Question | An item that defines a specific answer to be captured, and which may have child items. (the answer provided in the QuestionnaireResponse should be of the defined datatype).
2 | boolean | Boolean | Question with a yes/no answer (valueBoolean).
2 | decimal | Decimal | Question with is a real number answer (valueDecimal).
2 | integer | Integer | Question with an integer answer (valueInteger).

2 | date | Date | Question with a date answer (valueDate).
2 | dateTime | Date Time | Question with a date and time answer (valueDateTime).
2 | time | Time | Question with a time (hour:minute:second) answer independent of date. (valueTime).
2 | string | String | Question with a short (few words to short sentence) free-text entry answer (valueString).
2 | text | Text | Question with a long (potentially multi-paragraph) free-text entry answer (valueString).
2 | url | Url | Question with a URL (website, FTP site, etc.) answer (valueUri).
2 | choice | Choice | Question with a Coding drawn from a list of possible answers (specified in either the answerOption property, or via the valueset referenced in the answerValueSet property) as an answer (valueCoding).
2 | open-choice | Open Choice | Answer is a Coding drawn from a list of possible answers (as with the choice type) or a free-text entry in a string (valueCoding or valueString).
2 | attachment | Attachment | Question with binary content such as an image, PDF, etc. as an answer (valueAttachment).
2 | reference | Reference | Question with a reference to another resource (practitioner, organization, etc.) as an answer (valueReference).
2 | quantity | Quantity | Question with a combination of a numeric value and unit, potentially with a comparator (<, >, etc.) as an answer. (valueQuantity) There is an extension 'http://hl7.org/fhir/StructureDefinition/questionnaire-unit' that can be used to define what unit should be captured (or the unit that has a ucum conversion from the provided unit).

See the full registry of code systems defined as part of FHIR.

Explanation of the columns that may appear on this page:

Level | A few code lists that FHIR defines are hierarchical - each code is assigned a level. See Code System for further information.
Source | The source of the definition of the code (when the value set draws in codes defined elsewhere)
Code | The code (used as the code in the resource instance). If the code is in italics, this indicates that the code is not selectable ('Abstract')
Display | The display (used in the display element of a Coding). If there is no display, implementers should not simply display the code, but map the concept into their application
Definition | An explanation of the meaning of the concept
Comments | Additional notes about how to use the code

4.3.14.221 Code System http://hl7.org/fhir/sequence-type

URL: https://hl7.org/fhir/R4/codesystem-sequence-type.html
Clinical Genomics Work Group | Maturity Level: 1 | Trial Use | Use Context: Any

This is a code system defined by the FHIR project.

Summary

Defining URL: | http://hl7.org/fhir/sequence-type
Version: | 4.0.1
Name: | sequenceType
Title: | sequenceType
Definition: | Type if a sequence -- DNA, RNA, or amino acid sequence.
Committee: | Clinical Genomics Work Group
OID: | 2.16.840.1.113883.4.642.4.220 (for OID based terminology systems)
Source Resource | XML / JSON

This Code system is used in the following value sets:

• ValueSet: sequenceType (Type if a sequence -- DNA, RNA, or amino acid sequence.)
• ValueSet: sequenceType (Type if a sequence -- DNA, RNA, or amino acid sequence.)

4.3.14.221.1 Content

4.3.14.221.2 sequenceType

Type if a sequence -- DNA, RNA, or amino acid sequence.

This code system http://hl7.org/fhir/sequence-type defines the following codes:

Code | Display | Definition
aa | AA Sequence | Amino acid sequence.
dna | DNA Sequence | DNA Sequence.
rna | RNA Sequence | RNA Sequence.

See the full registry of code systems defined as part of FHIR.

Explanation of the columns that may appear on this page:

Level | A few code lists that FHIR defines are hierarchical - each code is assigned a level. See Code System for further information.
Source | The source of the definition of the code (when the value set draws in codes defined elsewhere)
Code | The code (used as the code in the resource instance). If the code is in italics, this indicates that the code is not selectable ('Abstract')
Display | The display (used in the display element of a Coding). If there is no display, implementers should not simply display the code, but map the concept into their application
Definition | An explanation of the meaning of the concept
Comments | Additional notes about how to use the code

4.3.14.222 Code System http://hl7.org/fhir/CodeSystem/status

URL: https://hl7.org/fhir/R4/codesystem-verificationresult-status.html
Patient Administration Work Group | Maturity Level: 0 | Trial Use | Use Context: Any

This is a code system defined by the FHIR project.

Summary

Defining URL: | http://hl7.org/fhir/CodeSystem/status
Version: | 4.0.1
Name: | status
Title: | Status
Definition: | The validation status of the target
Committee: | Patient Administration Work Group
OID: | 2.16.840.1.113883.4.642.1.885 (for OID based terminology systems)
Source Resource | XML / JSON

This Code system is used in the following value sets:

• ValueSet: Status (The validation status of the target)

• ValueSet: Status (The validation status of the target)

4.3.14.222.1 Content

4.3.14.222.2 Status

The validation status of the target

This code system http://hl7.org/fhir/CodeSystem/status defines the following codes:

Code | Display | Definition
attested | Attested | ***TODO***
validated | Validated | ***TODO***
in-process | In process | ***TODO***
req-revalid | Requires revalidation | ***TODO***
val-fail | Validation failed | ***TODO***
reval-fail | Re-Validation failed | ***TODO***

See the full registry of code systems defined as part of FHIR.

Explanation of the columns that may appear on this page:

Level | A few code lists that FHIR defines are hierarchical - each code is assigned a level. See Code System for further information.
Source | The source of the definition of the code (when the value set draws in codes defined elsewhere)
Code | The code (used as the code in the resource instance). If the code is in italics, this indicates that the code is not selectable ('Abstract')
Display | The display (used in the display element of a Coding). If there is no display, implementers should not simply display the code, but map the concept into their application
Definition | An explanation of the meaning of the concept
Comments | Additional notes about how to use the code

4.3.14.223 Code System http://hl7.org/fhir/map-transform

URL: https://hl7.org/fhir/R4/codesystem-map-transform.html
FHIR Infrastructure Work Group | Maturity Level: 2 | Trial Use | Use Context: Any

This is a code system defined by the FHIR project.

Summary

Defining URL: | http://hl7.org/fhir/map-transform
Version: | 4.0.1
Name: | StructureMapTransform
Title: | StructureMapTransform
Definition: | How data is copied/created.
Committee: | FHIR Infrastructure Work Group
OID: | 2.16.840.1.113883.4.642.4.682 (for OID based terminology systems)
Source Resource | XML / JSON

This Code system is used in the following value sets:

• ValueSet: StructureMapTransform (How data is copied/created.)

• ValueSet: StructureMapTransform (How data is copied/created.)

4.3.14.223.1 Content

4.3.14.223.2 StructureMapTransform

How data is copied/created.

This code system http://hl7.org/fhir/map-transform defines the following codes:

Code | Display | Definition
create | create | create(type : string) - type is passed through to the application on the standard API, and must be known by it.

copy | copy | copy(source).
truncate | truncate | truncate(source, length) - source must be stringy type.
escape | escape | escape(source, fmt1, fmt2) - change source from one kind of escaping to another (plain, java, xml, json). note that this is for when the string itself is escaped.
cast | cast | cast(source, type?) - case source from one type to another. target type can be left as implicit if there is one and only one target type known.
append | append | append(source...) - source is element or string.
translate | translate | translate(source, uri_of_map) - use the translate operation.
reference | reference | reference(source : object) - return a string that references the provided tree properly.
dateOp | dateOp | Perform a date operation. *Parameters to be documented*.
uuid | uuid | Generate a random UUID (in lowercase). No Parameters.
pointer | pointer | Return the appropriate string to put in a reference that refers to the resource provided as a parameter.
evaluate | evaluate | Execute the supplied FHIRPath expression and use the value returned by that.
cc | cc | Create a CodeableConcept. Parameters = (text) or (system. Code[, display]).
c | c | Create a Coding. Parameters = (system. Code[, display]).
qty | qty | Create a quantity. Parameters = (text) or (value, unit, [system, code]) where text is the natural representation e.g. [comparator]value[space]unit.
id | id | Create an identifier. Parameters = (system, value[, type]) where type is a code from the identifier type value set.
cp | cp | Create a contact details. Parameters = (value) or (system, value). If no system is provided, the system should be inferred from the content of the value.

See the full registry of code systems defined as part of FHIR.

Explanation of the columns that may appear on this page:

Level | A few code lists that FHIR defines are hierarchical - each code is assigned a level. See Code System for further information.
Source | The source of the definition of the code (when the value set draws in codes defined elsewhere)
Code | The code (used as the code in the resource instance). If the code is in italics, this indicates that the code is not selectable ('Abstract')
Display | The display (used in the display element of a Coding). If there is no display, implementers should not simply display the code, but map the concept into their application
Definition | An explanation of the meaning of the concept
Comments | Additional notes about how to use the code

4.3.14.224 Code System http://hl7.org/fhir/list-status

URL: https://hl7.org/fhir/R4/codesystem-list-status.html
FHIR Infrastructure Work Group | Maturity Level: 1 | Trial Use | Use Context: Any

This is a code system defined by the FHIR project.

Summary

Defining URL: | http://hl7.org/fhir/list-status
Version: | 4.0.1
Name: | ListStatus
Title: | ListStatus
Definition: | The current state of the list.
Committee: | FHIR Infrastructure Work Group
OID: | 2.16.840.1.113883.4.642.4.327 (for OID based terminology systems)
Source Resource | XML / JSON

This Code system is used in the following value sets:

• ValueSet: ListStatus (The current state of the list.)
• ValueSet: ListStatus (The current state of the list.)

4.3.14.224.1 Content

4.3.14.224.2 ListStatus

The current state of the list.

This code system http://hl7.org/fhir/list-status defines the following codes:

Code | Display | Definition
current | Current | The list is considered to be an active part of the patient's record.
retired | Retired | The list is "old" and should no longer be considered accurate or relevant.
entered-in-error | Entered In Error | The list was never accurate. It is retained for medico-legal purposes only.

See the full registry of code systems defined as part of FHIR.

Explanation of the columns that may appear on this page:

Level | A few code lists that FHIR defines are hierarchical - each code is assigned a level. See Code System for further information.
Source | The source of the definition of the code (when the value set draws in codes defined elsewhere)
Code | The code (used as the code in the resource instance). If the code is in italics, this indicates that the code is not selectable ('Abstract')
Display | The display (used in the display element of a Coding). If there is no display, implementers should not simply display the code, but map the concept into their application
Definition | An explanation of the meaning of the concept

Comments | Additional notes about how to use the code

4.3.14.225 Code System http://hl7.org/fhir/codesystem-content-mode

URL: https://hl7.org/fhir/R4/codesystem-codesystem-content-mode.html
Vocabulary Work Group | Maturity Level: N | Normative (from v4.0.0) | Use Context: Any

| This page has been approved as part of an ANSI standard. See the Conformance Package for further details.

This is a code system defined by the FHIR project.

Summary

Defining URL: | http://hl7.org/fhir/codesystem-content-mode
Version: | 4.0.1
Name: | CodeSystemContentMode
Title: | CodeSystemContentMode
Definition: | The extent of the content of the code system (the concepts and codes it defines) are represented in a code system resource.
Committee: | Vocabulary Work Group
OID: | 2.16.840.1.113883.4.642.4.783 (for OID based terminology systems)
Source Resource | XML / JSON

This Code system is used in the following value sets:

• ValueSet: CodeSystemContentMode (The extent of the content of the code system (the concepts and codes it defines) are represented in a code system resource.)

• ValueSet: CodeSystemContentMode (The extent of the content of the code system (the concepts and codes it defines) are represented in a code system resource.)

4.3.14.225.1 Content

4.3.14.225.2 CodeSystemContentMode

The extent of the content of the code system (the concepts and codes it defines) are represented in a code system resource.

This code system http://hl7.org/fhir/codesystem-content-mode defines the following codes:

Code | Display | Definition
not-present | Not Present | None of the concepts defined by the code system are included in the code system resource.
example | Example | A few representative concepts are included in the code system resource. There is no useful intent in the subset choice and there's no process to make it workable: it's not intended to be workable.
fragment | Fragment | A subset of the code system concepts are included in the code system resource. This is a curated subset released for a specific purpose under the governance of the code system steward, and that the intent, bounds and consequences of the fragmentation are clearly defined in the fragment or the code system documentation. Fragments are also known as partitions.
complete | Complete | All the concepts defined by the code system are included in the code system resource.
supplement | Supplement | The resource doesn't define any new concepts; it just provides additional designations and properties to another code system.

See the full registry of code systems defined as part of FHIR.

Explanation of the columns that may appear on this page:

Level | A few code lists that FHIR defines are hierarchical - each code is assigned a level. See Code System for further information.
Source | The source of the definition of the code (when the value set draws in codes defined elsewhere)
Code | The code (used as the code in the resource instance). If the code is in italics, this indicates that the code is not selectable ('Abstract')
Display | The display (used in the display element of a Coding). If there is no display, implementers should not simply display the code, but map the concept into their application
Definition | An explanation of the meaning of the concept
Comments | Additional notes about how to use the code

4.3.14.226 Code System http://hl7.org/fhir/request-intent

URL: https://hl7.org/fhir/R4/codesystem-request-intent.html
Clinical Decision Support Work Group | Maturity Level: 2 | Trial Use | Use Context: Any

This is a code system defined by the FHIR project.

Summary

Defining URL: | http://hl7.org/fhir/request-intent
Version: | 4.0.1
Name: | RequestIntent
Title: | RequestIntent
Definition: | Codes indicating the degree of authority/intentionality associated with a request.
Committee: | Clinical Decision Support Work Group

OID: | 2.16.840.1.113883.4.642.4.114 (for OID based terminology systems)
Source Resource | XML / JSON

This Code system is used in the following value sets:

• ValueSet: Care Plan Intent (Codes indicating the degree of authority/intentionality associated with a care plan.)

• ValueSet: RequestIntent (Codes indicating the degree of authority/intentionality associated with a request.)

• ValueSet: TaskIntent (Distinguishes whether the task is a proposal, plan or full order.)

• ValueSet: Care Plan Intent (Codes indicating the degree of authority/intentionality associated with a care plan.)

• ValueSet: TaskIntent (Distinguishes whether the task is a proposal, plan or full order.)

• ValueSet: RequestIntent (Codes indicating the degree of authority/intentionality associated with a request.)

4.3.14.226.1 Content

4.3.14.226.2 RequestIntent

Codes indicating the degree of authority/intentionality associated with a request.

This code system http://hl7.org/fhir/request-intent defines the following codes:

Lvl | Code | Display | Definition
1 | proposal | Proposal | The request is a suggestion made by someone/something that does not have an intention to ensure it occurs and without providing an authorization to act.
1 | plan | Plan | The request represents an intention to ensure something occurs without providing an authorization for others to act.
1 | directive | Directive | The request represents a legally binding instruction authored by a Patient or RelatedPerson.
1 | order | Order | The request represents a request/demand and authorization for action by a Practitioner.
2 | original-order | Original Order | The request represents an original authorization for action.
2 | reflex-order | Reflex Order | The request represents an automatically generated supplemental authorization for action based on a parent authorization together with initial results of the action taken against that parent authorization.
2 | filler-order | Filler Order | The request represents the view of an authorization instantiated by a fulfilling system representing the details of the fulfiller's intention to act upon a submitted order.
3 | instance-order | Instance Order | An order created in fulfillment of a broader order that represents the authorization for a single activity occurrence. E.g. The administration of a single dose of a drug.
1 | option | Option | The request represents a component or option for a RequestGroup that establishes timing, conditionality and/or other constraints among a set of requests. Refer to [[[RequestGroup]]] for additional information on how this status is used.

See the full registry of code systems defined as part of FHIR.

Explanation of the columns that may appear on this page:

Level | A few code lists that FHIR defines are hierarchical - each code is assigned a level. See Code System for further information.
Source | The source of the definition of the code (when the value set draws in codes defined elsewhere)
Code | The code (used as the code in the resource instance). If the code is in italics, this indicates that the code is not selectable ('Abstract')
Display | The display (used in the display element of a Coding). If there is no display, implementers should not simply display the code, but map the concept into their application
Definition | An explanation of the meaning of the concept
Comments | Additional notes about how to use the code

4.3.14.227 Code System http://hl7.org/fhir/encounter-location-status

URL: https://hl7.org/fhir/R4/codesystem-encounter-location-status.html
Patient Administration Work Group | Maturity Level: 2 | Trial Use | Use Context: Any

This is a code system defined by the FHIR project.

Summary

Defining URL: | http://hl7.org/fhir/encounter-location-status
Version: | 4.0.1
Name: | EncounterLocationStatus
Title: | EncounterLocationStatus
Definition: | The status of the location.
Committee: | Patient Administration Work Group
OID: | 2.16.840.1.113883.4.642.4.263 (for OID based terminology systems)
Source Resource | XML / JSON

This Code system is used in the following value sets:

• ValueSet: EncounterLocationStatus (The status of the location.)

• ValueSet: EncounterLocationStatus (The status of the location.)

4.3.14.227.1 Content

4.3.14.227.2 EncounterLocationStatus

The status of the location.

This code system http://hl7.org/fhir/encounter-location-status defines the following codes:

Code | Display | Definition
planned | Planned | The patient is planned to be moved to this location at some point in the future.
active | Active | The patient is currently at this location, or was between the period specified. A system may update these records when the patient leaves the location to either reserved, or completed.
reserved | Reserved | This location is held empty for this patient.
completed | Completed | The patient was at this location during the period specified. Not to be used when the patient is currently at the location.

See the full registry of code systems defined as part of FHIR.

Explanation of the columns that may appear on this page:

Level | A few code lists that FHIR defines are hierarchical - each code is assigned a level. See Code System for further information.
Source | The source of the definition of the code (when the value set draws in codes defined elsewhere)
Code | The code (used as the code in the resource instance). If the code is in italics, this indicates that the code is not selectable ('Abstract')
Display | The display (used in the display element of a Coding). If there is no display, implementers should not simply display the code, but map the concept into their application
Definition | An explanation of the meaning of the concept
Comments | Additional notes about how to use the code

4.3.14.228 Code System http://hl7.org/fhir/contact-point-system

URL: https://hl7.org/fhir/R4/codesystem-contact-point-system.html
FHIR Infrastructure Work Group | Maturity Level: N | Normative (from v4.0.0) | Use Context: Any

This is a code system defined by the FHIR project.

Summary

Defining URL: | http://hl7.org/fhir/contact-point-system
Version: | 4.0.1
Name: | ContactPointSystem
Title: | ContactPointSystem
Definition: | Telecommunications form for contact point.
Committee: | FHIR Infrastructure Work Group
OID: | 2.16.840.1.113883.4.642.4.72 (for OID based terminology systems)
Source Resource | XML / JSON

This Code system is used in the following value sets:

• ValueSet: ContactPointSystem (Telecommunications form for contact point.)
• ValueSet: ContactPointSystem (Telecommunications form for contact point.)

4.3.14.228.1 Content

4.3.14.228.2 ContactPointSystem

Telecommunications form for contact point.

This code system http://hl7.org/fhir/contact-point-system defines the following codes:

Code | Display | Definition
phone | Phone | The value is a telephone number used for voice calls. Use of full international numbers starting with + is recommended to enable automatic dialing support but not required.
fax | Fax | The value is a fax machine. Use of full international numbers starting with + is recommended to enable automatic dialing support but not required.
email | Email | The value is an email address.
pager | Pager | The value is a pager number. These may be local pager numbers that are only usable on a particular pager system.
url | URL | A contact that is not a phone, fax, pager or email address and is expressed as a URL. This is intended for various institutional or personal contacts including web sites, blogs, Skype, Twitter, Facebook, etc. Do not use for email addresses.
sms | SMS | A contact that can be used for sending an sms message (e.g. mobile phones, some landlines).
other | Other | A contact that is not a phone, fax, page or email address and is not expressible as a URL. E.g. Internal mail address. This SHOULD NOT be used for contacts that are expressible as a URL (e.g. Skype, Twitter, Facebook, etc.) Extensions may be used to distinguish "other" contact types.

See the full registry of code systems defined as part of FHIR.

Explanation of the columns that may appear on this page:

Level | A few code lists that FHIR defines are hierarchical - each code is assigned a level. See Code System for further information.
Source | The source of the definition of the code (when the value set draws in codes defined elsewhere)
Code | The code (used as the code in the resource instance). If the code is in italics, this indicates that the code is not selectable ('Abstract')

Display | The display (used in the display element of a Coding). If there is no display, implementers should not simply display the code, but map the concept into their application
Definition | An explanation of the meaning of the concept
Comments | Additional notes about how to use the code

4.3.14.229 Code System http://hl7.org/fhir/map-input-mode

URL: https://hl7.org/fhir/R4/codesystem-map-input-mode.html
FHIR Infrastructure Work Group | Maturity Level: 2 | Trial Use | Use Context: Any

This is a code system defined by the FHIR project.

Summary

Defining URL: | http://hl7.org/fhir/map-input-mode
Version: | 4.0.1
Name: | StructureMapInputMode
Title: | StructureMapInputMode
Definition: | Mode for this instance of data.
Committee: | FHIR Infrastructure Work Group
OID: | 2.16.840.1.113883.4.642.4.678 (for OID based terminology systems)
Source Resource | XML / JSON

This Code system is used in the following value sets:

• ValueSet: StructureMapInputMode (Mode for this instance of data.)

• ValueSet: StructureMapInputMode (Mode for this instance of data.)

4.3.14.229.1 Content

4.3.14.229.2 StructureMapInputMode

Mode for this instance of data.

This code system http://hl7.org/fhir/map-input-mode defines the following codes:

Code | Display | Definition
source | Source Instance | Names an input instance used a source for mapping.
target | Target Instance | Names an instance that is being populated.

See the full registry of code systems defined as part of FHIR.

Explanation of the columns that may appear on this page:

Level | A few code lists that FHIR defines are hierarchical - each code is assigned a level. See Code System for further information.
Source | The source of the definition of the code (when the value set draws in codes defined elsewhere)
Code | The code (used as the code in the resource instance). If the code is in italics, this indicates that the code is not selectable ('Abstract')
Display | The display (used in the display element of a Coding). If there is no display, implementers should not simply display the code, but map the concept into their application
Definition | An explanation of the meaning of the concept
Comments | Additional notes about how to use the code

4.3.14.230 Code System http://terminology.hl7.org/CodeSystem/catalogType

URL: https://hl7.org/fhir/R4/codesystem-catalogType.html
Vocabulary Work Group | Maturity Level: 0 | Informative | Use Context: Any

This is a code system defined by the FHIR project.

Summary

Defining URL: | http://terminology.hl7.org/CodeSystem/catalogType
Version: | 4.0.1
Name: | CatalogType
Title: | CatalogType
Definition: | The type of catalog.
Committee: | ??
OID: | 2.16.840.1.113883.4.642.4.1288 (for OID based terminology systems)
Source Resource | XML / JSON

This Code system is used in the following value sets:

• ValueSet: CatalogType (The type of catalog.)

• ValueSet: CatalogType (The type of catalog.)

4.3.14.230.1 Content

4.3.14.230.2 CatalogType

The type of catalog.

This code system http://terminology.hl7.org/CodeSystem/catalogType defines the following codes:

Code | Display | Definition
medication | Medication Catalog | Medication Catalog.
device | Device Catalog | Device Catalog.
protocol | Protocol List | Protocol List.

See the full registry of code systems defined as part of FHIR.

Explanation of the columns that may appear on this page:

Level | A few code lists that FHIR defines are hierarchical - each code is assigned a level. See Code System for further information.
Source | The source of the definition of the code (when the value set draws in codes defined elsewhere)
Code | The code (used as the code in the resource instance). If the code is in italics, this indicates that the code is not selectable ('Abstract')
Display | The display (used in the display element of a Coding). If there is no display, implementers should not simply display the code, but map the concept into their application
Definition | An explanation of the meaning of the concept
Comments | Additional notes about how to use the code

4.3.14.231 Code System http://hl7.org/fhir/audit-event-action

URL: https://hl7.org/fhir/R4/codesystem-audit-event-action.html
Security Work Group | Maturity Level: 3 | Trial Use | Use Context: Any

This is a code system defined by the FHIR project.

Summary

Defining URL: | http://hl7.org/fhir/audit-event-action
Version: | 4.0.1
Name: | AuditEventAction
Title: | AuditEventAction
Definition: | Indicator for type of action performed during the event that generated the event.
Committee: | Security Work Group
OID: | 2.16.840.1.113883.4.642.4.453 (for OID based terminology systems)
Source Resource | XML / JSON

This Code system is used in the following value sets:

• ValueSet: AuditEventAction (Indicator for type of action performed during the event that generated the event.)

• ValueSet: AuditEventAction (Indicator for type of action performed during the event that generated the event.)

4.3.14.231.1 Content

4.3.14.231.2 AuditEventAction

Indicator for type of action performed during the event that generated the event.

This code system http://hl7.org/fhir/audit-event-action defines the following codes:

Code | Display | Definition
C | Create | Create a new database object, such as placing an order.
R | Read/View/Print | Display or print data, such as a doctor census.
U | Update | Update data, such as revise patient information.
D | Delete | Delete items, such as a doctor master file record.
E | Execute | Perform a system or application function such as log-on, program execution or use of an object's method, or perform a query/search operation.

See the full registry of code systems defined as part of FHIR.

Explanation of the columns that may appear on this page:

Level | A few code lists that FHIR defines are hierarchical - each code is assigned a level. See Code System for further information.
Source | The source of the definition of the code (when the value set draws in codes defined elsewhere)
Code | The code (used as the code in the resource instance). If the code is in italics, this indicates that the code is not selectable ('Abstract')
Display | The display (used in the display element of a Coding). If there is no display, implementers should not simply display the code, but map the concept into their application
Definition | An explanation of the meaning of the concept
Comments | Additional notes about how to use the code

4.3.14.232 Code System http://terminology.hl7.org/CodeSystem/observation-category

URL: https://hl7.org/fhir/R4/codesystem-observation-category.html
Orders and Observations Work Group | Maturity Level: 0 | Informative | Use Context: Any

This is a code system defined by the FHIR project.

Summary

Defining URL: | http://terminology.hl7.org/CodeSystem/observation-category
Version: | 4.0.1
Name: | ObservationCategoryCodes
Title: | Observation Category Codes
Definition: | Observation Category codes.
Committee: | Orders and Observations Work Group
OID: | 2.16.840.1.113883.4.642.4.1125 (for OID based terminology systems)
Source Resource | XML / JSON

This Code system is used in the following value sets:

• ValueSet: Observation Category Codes (Observation Category codes.)

• ValueSet: Observation Category Codes (Observation Category codes.)

4.3.14.232.1 Content

4.3.14.232.2 Observation Category Codes

Observation Category codes.

This code system http://terminology.hl7.org/CodeSystem/observation-category defines the following codes:

Code | Display | Definition
social-history | Social History | Social History Observations define the patient's occupational, personal (e.g., lifestyle), social, familial, and environmental history and health risk factors that may impact the patient's health.
vital-signs | Vital Signs | Clinical observations measure the body's basic functions such as blood pressure, heart rate, respiratory rate, height, weight, body mass index, head circumference, pulse oximetry, temperature, and body surface area.
imaging | Imaging | Observations generated by imaging. The scope includes observations regarding plain x-ray, ultrasound, CT, MRI, angiography, echocardiography, and nuclear medicine.
laboratory | Laboratory | The results of observations generated by laboratories. Laboratory results are typically generated by laboratories providing analytic services in areas such as chemistry, hematology, serology, histology, cytology, anatomic pathology (including digital pathology), microbiology, and/or virology. These observations are based on analysis of specimens obtained from the patient and submitted to the laboratory.
procedure | Procedure | Observations generated by other procedures. This category includes observations resulting from interventional and non-interventional procedures excluding laboratory and imaging (e.g., cardiology catheterization, endoscopy, electrodiagnostics, etc.). Procedure results are typically generated by a clinician to provide more granular information about component observations made during a procedure. An example would be when a gastroenterologist reports the size of a polyp observed during a colonoscopy.
survey | Survey | Assessment tool/survey instrument observations (e.g., Apgar Scores, Montreal Cognitive Assessment (MoCA)).
exam | Exam | Observations generated by physical exam findings including direct observations made by a clinician and use of simple instruments and the result of simple maneuvers performed directly on the patient's body.
therapy | Therapy | Observations generated by non-interventional treatment protocols (e.g. occupational, physical, radiation, nutritional and medication therapy)
activity | Activity | Observations that measure or record any bodily activity that enhances or maintains physical fitness and overall health and wellness. Not under direct supervision of practitioner such as a physical therapist. (e.g., laps swum, steps, sleep data)

See the full registry of code systems defined as part of FHIR.

Explanation of the columns that may appear on this page:

Level | A few code lists that FHIR defines are hierarchical - each code is assigned a level. See Code System for further information.
Source | The source of the definition of the code (when the value set draws in codes defined elsewhere)
Code | The code (used as the code in the resource instance). If the code is in italics, this indicates that the code is not selectable ('Abstract')
Display | The display (used in the display element of a Coding). If there is no display, implementers should not simply display the code, but map the concept into their application
Definition | An explanation of the meaning of the concept
Comments | Additional notes about how to use the code

4.3.14.233 Code System http://terminology.hl7.org/CodeSystem/chargeitem-billingcodes

URL: https://hl7.org/fhir/R4/codesystem-chargeitem-billingcodes.html
Patient Administration Work Group | Maturity Level: 1 | Draft | Use Context: Any

This is a code system defined by the FHIR project.

Summary

Defining URL: | http://terminology.hl7.org/CodeSystem/chargeitem-billingcodes
Version: | 4.0.1
Name: | ChargeItemCode
Title: | ChargeItemCode
Definition: | Example set of codes that can be used for billing purposes.
Committee: | Patient Administration Work Group
OID: | 2.16.840.1.113883.4.642.4.1257 (for OID based terminology systems)

Source Resource | XML / JSON

This Code system is used in the following value sets:

• ValueSet: ChargeItemCode (Example set of codes that can be used for billing purposes.)

• ValueSet: ChargeItemCode (Example set of codes that can be used for billing purposes.)

4.3.14.233.1 Content

4.3.14.233.2 ChargeItemCode

Example set of codes that can be used for billing purposes.

This code system http://terminology.hl7.org/CodeSystem/chargeitem-billingcodes defines the following codes:

Code | Display | Definition
1100 | Unvorhergesehene Inanspruchnahme | From German EBM billing system: Unvorhergesehene Inanspruchnahme des Vertragsarztes durch einen Patienten;zwischen 19:00 und 22:00 Uhr;an Samstagen, Sonntagen und gesetzlichen Feiertagen, am 24.12. und 31.12. zwischen 07:00 und 19:00 Uhr.
1210 | Notfallpauschale | From German EBM billing system: Notfallpauschale im organisierten Not(-fall)dienst und für nicht an der vertragsärztlichen Versorgung teilnehmende Ärzte, Institute und Krankenhäuser bei Inanspruchnahme;zwischen 07:00 und 19:00 Uhr.
1320 | Grundpauschale | From German EBM billing system: Grundpauschale für Ärzte, Institute und Krankenhäuser, die zur Erbringung von Leistungen innerhalb mindestens eines der Fachgebiete Anästhesiologie, Frauenheilkunde und Geburtshilfe, Haut- und Geschlechtskrankheiten, Mund-, Kiefer- und Gesichtschirurgie und Humangenetik ermächtigt sind.

See the full registry of code systems defined as part of FHIR.

Explanation of the columns that may appear on this page:

Level | A few code lists that FHIR defines are hierarchical - each code is assigned a level. See Code System for further information.
Source | The source of the definition of the code (when the value set draws in codes defined elsewhere)
Code | The code (used as the code in the resource instance). If the code is in italics, this indicates that the code is not selectable ('Abstract')
Display | The display (used in the display element of a Coding). If there is no display, implementers should not simply display the code, but map the concept into their application
Definition | An explanation of the meaning of the concept
Comments | Additional notes about how to use the code

4.3.14.234 Code System http://terminology.hl7.org/CodeSystem/medicationknowledge-status

URL: https://hl7.org/fhir/R4/codesystem-medicationknowledge-status.html
Pharmacy Work Group | Maturity Level: 0 | Trial Use | Use Context: Any

This is a code system defined by the FHIR project.

Summary

Defining URL: | http://terminology.hl7.org/CodeSystem/medicationknowledge-status
Version: | 4.0.1
Name: | MedicationKnowledge Status Codes
Title: | Medication knowledge status codes
Definition: | MedicationKnowledge Status Codes
Committee: | Pharmacy Work Group
OID: | 2.16.840.1.113883.4.642.4.1336 (for OID based terminology systems)
Source Resource | XML / JSON

This Code system is used in the following value sets:

• ValueSet: Medication knowledge status codes (MedicationKnowledge Status Codes)

• ValueSet: Medication knowledge status codes (MedicationKnowledge Status Codes)

4.3.14.234.1 Content

4.3.14.234.2 Medication knowledge status codes

MedicationKnowledge Status Codes

This code system http://terminology.hl7.org/CodeSystem/medicationknowledge-status defines the following codes:

Code | Display | Definition
active | Active | The medication is available for use.
inactive | Inactive | The medication is not available for use.
entered-in-error | Entered in Error | The medication was entered in error.

See the full registry of code systems defined as part of FHIR.

Explanation of the columns that may appear on this page:

Level | A few code lists that FHIR defines are hierarchical - each code is assigned a level. See Code System for further information.
Source | The source of the definition of the code (when the value set draws in codes defined elsewhere)

Code | The code (used as the code in the resource instance). If the code is in italics, this indicates that the code is not selectable ('Abstract')
Display | The display (used in the display element of a Coding). If there is no display, implementers should not simply display the code, but map the concept into their application
Definition | An explanation of the meaning of the concept
Comments | Additional notes about how to use the code

4.3.14.235 Code System http://hl7.org/fhir/action-precheck-behavior

URL: https://hl7.org/fhir/R4/codesystem-action-precheck-behavior.html
Clinical Decision Support Work Group | Maturity Level: 2 | Trial Use | Use Context: Any

This is a code system defined by the FHIR project.

Summary

Defining URL: | http://hl7.org/fhir/action-precheck-behavior
Version: | 4.0.1
Name: | ActionPrecheckBehavior
Title: | ActionPrecheckBehavior
Definition: | Defines selection frequency behavior for an action or group.
Committee: | Clinical Decision Support Work Group
OID: | 2.16.840.1.113883.4.642.4.806 (for OID based terminology systems)
Source Resource | XML / JSON

This Code system is used in the following value sets:

• ValueSet: ActionPrecheckBehavior (Defines selection frequency behavior for an action or group.)
• ValueSet: ActionPrecheckBehavior (Defines selection frequency behavior for an action or group.)

4.3.14.235.1 Content

4.3.14.235.2 ActionPrecheckBehavior

Defines selection frequency behavior for an action or group.

This code system http://hl7.org/fhir/action-precheck-behavior defines the following codes:

Code | Display | Definition
yes | Yes | An action with this behavior is one of the most frequent action that is, or should be, included by an end user, for the particular context in which the action occurs. The system displaying the action to the end user should consider "pre-checking" such an action as a convenience for the user.
no | No | An action with this behavior is one of the less frequent actions included by the end user, for the particular context in which the action occurs. The system displaying the actions to the end user would typically not "pre-check" such an action.

See the full registry of code systems defined as part of FHIR.

Explanation of the columns that may appear on this page:

Level | A few code lists that FHIR defines are hierarchical - each code is assigned a level. See Code System for further information.
Source | The source of the definition of the code (when the value set draws in codes defined elsewhere)
Code | The code (used as the code in the resource instance). If the code is in italics, this indicates that the code is not selectable ('Abstract')
Display | The display (used in the display element of a Coding). If there is no display, implementers should not simply display the code, but map the concept into their application
Definition | An explanation of the meaning of the concept
Comments | Additional notes about how to use the code

4.3.14.236 Code System http://hl7.org/fhir/research-subject-status

URL: https://hl7.org/fhir/R4/codesystem-research-subject-status.html
Biomedical Research and Regulation Work Group | Maturity Level: 1 | Trial Use | Use Context: Any

This is a code system defined by the FHIR project.

Summary

Defining URL: | http://hl7.org/fhir/research-subject-status
Version: | 4.0.1
Name: | ResearchSubjectStatus
Title: | ResearchSubjectStatus
Definition: | Indicates the progression of a study subject through a study.
Committee: | Biomedical Research and Regulation Work Group
OID: | 2.16.840.1.113883.4.642.4.830 (for OID based terminology systems)
Source Resource | XML / JSON

This Code system is used in the following value sets:

• ValueSet: ResearchSubjectStatus (Indicates the progression of a study subject through a study.)
• ValueSet: ResearchSubjectStatus (Indicates the progression of a study subject through a study.)

4.3.14.236.1 Content

4.3.14.236.2 ResearchSubjectStatus

Indicates the progression of a study subject through a study.

This code system http://hl7.org/fhir/research-subject-status defines the following codes:

Code | Display | Definition
candidate | Candidate | An identified person that can be considered for inclusion in a study.
eligible | Eligible | A person that has met the eligibility criteria for inclusion in a study.
follow-up | Follow-up | A person is no longer receiving study intervention and/or being evaluated with tests and procedures according to the protocol, but they are being monitored on a protocol-prescribed schedule.
ineligible | Ineligible | A person who did not meet one or more criteria required for participation in a study is considered to have failed screening or is ineligible for the study.
not-registered | Not Registered | A person for whom registration was not completed.
off-study | Off-study | A person that has ended their participation on a study either because their treatment/observation is complete or through not responding, withdrawal, non-compliance and/or adverse event.
on-study | On-study | A person that is enrolled or registered on a study.
on-study-intervention | On-study-intervention | The person is receiving the treatment or participating in an activity (e.g. yoga, diet, etc.) that the study is evaluating.
on-study-observation | On-study-observation | The subject is being evaluated via tests and assessments according to the study calendar, but is not receiving any intervention. Note that this state is study-dependent and might not exist in all studies. A synonym for this is "short-term follow-up".
pending-on-study | Pending on-study | A person is pre-registered for a study.
potential-candidate | Potential Candidate | A person that is potentially eligible for participation in the study.
screening | Screening | A person who is being evaluated for eligibility for a study.
withdrawn | Withdrawn | The person has withdrawn their participation in the study before registration.

See the full registry of code systems defined as part of FHIR.

Explanation of the columns that may appear on this page:

Level | A few code lists that FHIR defines are hierarchical - each code is assigned a level. See Code System for further information.
Source | The source of the definition of the code (when the value set draws in codes defined elsewhere)
Code | The code (used as the code in the resource instance). If the code is in italics, this indicates that the code is not selectable ('Abstract')
Display | The display (used in the display element of a Coding). If there is no display, implementers should not simply display the code, but map the concept into their application
Definition | An explanation of the meaning of the concept
Comments | Additional notes about how to use the code

4.3.14.237 Code System http://hl7.org/fhir/participationstatus

URL: https://hl7.org/fhir/R4/codesystem-participationstatus.html
Patient Administration Work Group | Maturity Level: 3 | Trial Use | Use Context: Any

This is a code system defined by the FHIR project.

Summary

Defining URL: | http://hl7.org/fhir/participationstatus
Version: | 4.0.1
Name: | ParticipationStatus
Title: | ParticipationStatus
Definition: | The Participation status of an appointment.
Committee: | Patient Administration Work Group
OID: | 2.16.840.1.113883.4.642.4.487 (for OID based terminology systems)
Source Resource | XML / JSON

This Code system is used in the following value sets:

• ValueSet: ParticipationStatus (The Participation status of an appointment.)
• ValueSet: ParticipationStatus (The Participation status of an appointment.)

4.3.14.237.1 Content

4.3.14.237.2 ParticipationStatus

The Participation status of an appointment.

This code system http://hl7.org/fhir/participationstatus defines the following codes:

Code | Display | Definition
accepted | Accepted | The participant has accepted the appointment.
declined | Declined | The participant has declined the appointment and will not participate in the appointment.

tentative | Tentative | The participant has tentatively accepted the appointment. This could be automatically created by a system and requires further processing before it can be accepted. There is no commitment that attendance will occur.
needs-action | Needs Action | The participant needs to indicate if they accept the appointment by changing this status to one of the other statuses.

See the full registry of code systems defined as part of FHIR.

Explanation of the columns that may appear on this page:

Level | A few code lists that FHIR defines are hierarchical - each code is assigned a level. See Code System for further information.
Source | The source of the definition of the code (when the value set draws in codes defined elsewhere)
Code | The code (used as the code in the resource instance). If the code is in italics, this indicates that the code is not selectable ('Abstract')
Display | The display (used in the display element of a Coding). If there is no display, implementers should not simply display the code, but map the concept into their application
Definition | An explanation of the meaning of the concept
Comments | Additional notes about how to use the code

4.3.14.238 Code System http://terminology.hl7.org/CodeSystem/certainty-subcomponent-type

URL: https://hl7.org/fhir/R4/codesystem-certainty-subcomponent-type.html
Clinical Decision Support Work Group | Maturity Level: 0 | Trial Use | Use Context: Any

This is a code system defined by the FHIR project.

Summary

Defining URL: | http://terminology.hl7.org/CodeSystem/certainty-subcomponent-type
Version: | 4.0.1
Name: | CertaintySubcomponentType
Title: | CertaintySubcomponentType
Definition: | The subcomponent classification of quality of evidence rating systems.
Committee: | Clinical Decision Support Work Group
OID: | 2.16.840.1.113883.4.642.4.1360 (for OID based terminology systems)
Source Resource | XML / JSON

This Code system is used in the following value sets:

• ValueSet: CertaintySubcomponentType (The subcomponent classification of quality of evidence rating systems.)

• ValueSet: CertaintySubcomponentType (The subcomponent classification of quality of evidence rating systems.)

4.3.14.238.1 Content

4.3.14.238.2 CertaintySubcomponentType

The subcomponent classification of quality of evidence rating systems.

This code system http://terminology.hl7.org/CodeSystem/certainty-subcomponent-type defines the following codes:

Code | Display | Definition
RiskOfBias | Risk of bias | methodologic concerns reducing internal validity.
Inconsistency | Inconsistency | concerns that findings are not similar enough to support certainty.
Indirectness | Indirectness | concerns reducing external validity.
Imprecision | Imprecision | High quality evidence.
PublicationBias | Publication bias | likelihood that what is published misrepresents what is available to publish.
DoseResponseGradient | Dose response gradient | higher certainty due to dose response relationship.
PlausibleConfounding | Plausible confounding | higher certainty due to risk of bias in opposite direction.
LargeEffect | Large effect | higher certainty due to large effect size.

See the full registry of code systems defined as part of FHIR.

Explanation of the columns that may appear on this page:

Level | A few code lists that FHIR defines are hierarchical - each code is assigned a level. See Code System for further information.
Source | The source of the definition of the code (when the value set draws in codes defined elsewhere)
Code | The code (used as the code in the resource instance). If the code is in italics, this indicates that the code is not selectable ('Abstract')
Display | The display (used in the display element of a Coding). If there is no display, implementers should not simply display the code, but map the concept into their application
Definition | An explanation of the meaning of the concept
Comments | Additional notes about how to use the code

4.3.14.239 Code System http://terminology.hl7.org/CodeSystem/medicationrequest-category

URL: https://hl7.org/fhir/R4/codesystem-medicationrequest-category.html
Pharmacy Work Group | Maturity Level: 1 | Draft | Use Context: Any

This is a code system defined by the FHIR project.

Summary

Defining URL: | http://terminology.hl7.org/CodeSystem/medicationrequest-category
Version: | 4.0.1
Name: | medicationRequest Category Codes
Title: | Medication request category codes
Definition: | MedicationRequest Category Codes
Committee: | Pharmacy Work Group
OID: | 2.16.840.1.113883.4.642.4.1323 (for OID based terminology systems)
Source Resource | XML / JSON

This Code system is used in the following value sets:

• ValueSet: Medication request category codes (MedicationRequest Category Codes)

• ValueSet: Medication request category codes (MedicationRequest Category Codes)

4.3.14.239.1 Content

4.3.14.239.2 Medication request category codes

MedicationRequest Category Codes

This code system http://terminology.hl7.org/CodeSystem/medicationrequest-category defines the following codes:

Code | Display | Definition
inpatient | Inpatient | Includes requests for medications to be administered or consumed in an inpatient or acute care setting
outpatient | Outpatient | Includes requests for medications to be administered or consumed in an outpatient setting (for example, Emergency Department, Outpatient Clinic, Outpatient Surgery, Doctor's office)
community | Community | Includes requests for medications to be administered or consumed by the patient in their home (this would include long term care or nursing homes, hospices, etc.)
discharge | Discharge | Includes requests for medications created when the patient is being released from a facility

See the full registry of code systems defined as part of FHIR.

Explanation of the columns that may appear on this page:

Level | A few code lists that FHIR defines are hierarchical - each code is assigned a level. See Code System for further information.
Source | The source of the definition of the code (when the value set draws in codes defined elsewhere)
Code | The code (used as the code in the resource instance). If the code is in italics, this indicates that the code is not selectable ('Abstract')
Display | The display (used in the display element of a Coding). If there is no display, implementers should not simply display the code, but map the concept into their application
Definition | An explanation of the meaning of the concept
Comments | Additional notes about how to use the code

4.3.14.240 Code System http://hl7.org/fhir/message-events

URL: https://hl7.org/fhir/R4/codesystem-message-events.html
Infrastructure And Messaging Work Group | Maturity Level: 1 | Draft | Use Context: Any

This is a code system defined by the FHIR project.

Summary

Defining URL: | http://hl7.org/fhir/message-events
Version: | 4.0.1
Name: | MessageEvent
Title: | MessageEvent
Definition: | One of the message events defined as part of this version of FHIR.
Committee: | Infrastructure And Messaging Work Group
OID: | (for OID based terminology systems)
Source Resource | XML / JSON

This Code System is generated based on the information defined in this specification. The definition will remain fixed across versions, but the actual contents will change from version to version

This Code system is used in the following value sets:

• ValueSet: MessageEvent (One of the message events defined as part of this version of FHIR.)

• ValueSet: MessageEvent (One of the message events defined as part of this version of FHIR.)

4.3.14.240.1 Content

4.3.14.240.2 MessageEvent

One of the message events defined as part of this version of FHIR.

This code system http://hl7.org/fhir/message-events defines the following codes:

Code | Definition

See the full registry of code systems defined as part of FHIR.

Explanation of the columns that may appear on this page:

Level | A few code lists that FHIR defines are hierarchical - each code is assigned a level. See Code System for further information.
Source | The source of the definition of the code (when the value set draws in codes defined elsewhere)
Code | The code (used as the code in the resource instance). If the code is in italics, this indicates that the code is not selectable ('Abstract')
Display | The display (used in the display element of a Coding). If there is no display, implementers should not simply display the code, but map the concept into their application
Definition | An explanation of the meaning of the concept
Comments | Additional notes about how to use the code

4.3.14.241 Code System http://hl7.org/fhir/related-artifact-type

URL: https://hl7.org/fhir/R4/codesystem-related-artifact-type.html
FHIR Infrastructure Work Group | Maturity Level: 5 | Trial Use | Use Context: Any

This is a code system defined by the FHIR project.

Summary

Defining URL: | http://hl7.org/fhir/related-artifact-type
Version: | 4.0.1
Name: | RelatedArtifactType
Title: | RelatedArtifactType
Definition: | The type of relationship to the related artifact.
Committee: | FHIR Infrastructure Work Group
OID: | 2.16.840.1.113883.4.642.4.100 (for OID based terminology systems)
Source Resource | XML / JSON

This Code system is used in the following value sets:

• ValueSet: RelatedArtifactType (The type of relationship to the related artifact.)
• ValueSet: RelatedArtifactType (The type of relationship to the related artifact.)

4.3.14.241.1 Content

4.3.14.241.2 RelatedArtifactType

The type of relationship to the related artifact.

This code system http://hl7.org/fhir/related-artifact-type defines the following codes:

Code | Display | Definition
documentation | Documentation | Additional documentation for the knowledge resource. This would include additional instructions on usage as well as additional information on clinical context or appropriateness.
justification | Justification | A summary of the justification for the knowledge resource including supporting evidence, relevant guidelines, or other clinically important information. This information is intended to provide a way to make the justification for the knowledge resource available to the consumer of interventions or results produced by the knowledge resource.
citation | Citation | Bibliographic citation for papers, references, or other relevant material for the knowledge resource. This is intended to allow for citation of related material, but that was not necessarily specifically prepared in connection with this knowledge resource.
predecessor | Predecessor | The previous version of the knowledge resource.
successor | Successor | The next version of the knowledge resource.
derived-from | Derived From | The knowledge resource is derived from the related artifact. This is intended to capture the relationship in which a particular knowledge resource is based on the content of another artifact, but is modified to capture either a different set of overall requirements, or a more specific set of requirements such as those involved in a particular institution or clinical setting.
depends-on | Depends On | The knowledge resource depends on the given related artifact.
composed-of | Composed Of | The knowledge resource is composed of the given related artifact.

See the full registry of code systems defined as part of FHIR.

Explanation of the columns that may appear on this page:

Level | A few code lists that FHIR defines are hierarchical - each code is assigned a level. See Code System for further information.
Source | The source of the definition of the code (when the value set draws in codes defined elsewhere)
Code | The code (used as the code in the resource instance). If the code is in italics, this indicates that the code is not selectable ('Abstract')
Display | The display (used in the display element of a Coding). If there is no display, implementers should not simply display the code, but map the concept into their application
Definition | An explanation of the meaning of the concept
Comments | Additional notes about how to use the code

4.3.14.242 Code System http://hl7.org/fhir/gender-identity

URL: https://hl7.org/fhir/R4/codesystem-gender-identity.html
Vocabulary Work Group | Maturity Level: 0 | Informative | Use Context: Any

This is a code system defined by the FHIR project.

Summary

Defining URL: | http://hl7.org/fhir/gender-identity
Version: | 4.0.1
Name: | GenderIdentity
Title: | Gender identity
Definition: | This example value set defines a set of codes that can be used to indicate a patient's gender identity.
Committee: | ??
OID: | 2.16.840.1.113883.4.642.4.973 (for OID based terminology systems)
Copyright: | This resource includes content from SNOMED Clinical Terms® (SNOMED CT®) which is copyright of the International Health Terminology Standards Development Organisation (IHTSDO). Implementers of these specifications must have the appropriate SNOMED CT Affiliate license - for more information contact http://www.snomed.org/snomed-ct/get-snomed-ct or info@snomed.org
Source Resource | XML / JSON

This Code system is used in the following value sets:

• ValueSet: Gender identity (This example value set defines a set of codes that can be used to indicate a patient's gender identity.)

• ValueSet: Gender identity (This example value set defines a set of codes that can be used to indicate a patient's gender identity.)

4.3.14.242.1 Content

4.3.14.242.2 Gender identity

This example value set defines a set of codes that can be used to indicate a patient's gender identity.

Copyright Statement:

This resource includes content from SNOMED Clinical Terms® (SNOMED CT®) which is copyright of the International Health Terminology Standards Development Organisation (IHTSDO). Implementers of these specifications must have the appropriate SNOMED CT Affiliate license - for more information contact http://www.snomed.org/snomed-ct/get-snomed-ct or info@snomed.org

This code system http://hl7.org/fhir/gender-identity defines the following codes:

Code | Display | Definition
transgender-female | transgender female | the patient identifies as transgender male-to-female
transgender-male | transgender male | the patient identifies as transgender female-to-male
non-binary | non-binary | the patient identifies with neither/both female and male
male | male | the patient identifies as male
female | female | the patient identifies as female
other | other | other gender identity
non-disclose | does not wish to disclose | the patient does not wish to disclose his gender identity

See the full registry of code systems defined as part of FHIR.

Explanation of the columns that may appear on this page:

Level | A few code lists that FHIR defines are hierarchical - each code is assigned a level. See Code System for further information.
Source | The source of the definition of the code (when the value set draws in codes defined elsewhere)
Code | The code (used as the code in the resource instance). If the code is in italics, this indicates that the code is not selectable ('Abstract')
Display | The display (used in the display element of a Coding). If there is no display, implementers should not simply display the code, but map the concept into their application
Definition | An explanation of the meaning of the concept
Comments | Additional notes about how to use the code

4.3.14.243 Code System http://hl7.org/fhir/concept-properties

URL: https://hl7.org/fhir/R4/codesystem-concept-properties.html
Vocabulary Work Group | Maturity Level: N | Normative | Use Context: Any

This is a code system defined by the FHIR project.

Summary

Defining URL: | http://hl7.org/fhir/concept-properties
Version: | 4.0.1
Name: | FHIR Defined Concept Properties
Title:
Definition: | A set of common concept properties for use on coded systems throughout the FHIR eco-system.
Committee: | Vocabulary Work Group

OID: | (for OID based terminology systems)
Source Resource | XML / JSON

This Code system is not currently used

4.3.14.243.1 Content

4.3.14.243.2 FHIR Defined Concept Properties

A set of common concept properties for use on coded systems throughout the FHIR eco-system.

This code system http://hl7.org/fhir/concept-properties defines the following codes:

Code | Display | Definition
inactive | Inactive | True if the concept is not considered active - e.g. not a valid concept any more. Property type is boolean, default value is false
deprecated | Deprecated | The date at which a concept was deprecated. Concepts that are deprecated but not inactive can still be used, but their use is discouraged, and they should be expected to be made inactive in a future release. Property type is dateTime
notSelectable | Not Selectable | The concept is not intended to be chosen by the user - only intended to be used as a selector for other concepts. Note, though, that the interpretation of this is highly contextual; all concepts are selectable in some context. Property type is boolean
parent | Parent | The concept identified in this property is a parent of the concept on which it is a property. The property type will be 'code'. The meaning of 'parent' is defined by the hierarchyMeaning attribute
child | Child | The concept identified in this property is a child of the concept on which it is a property. The property type will be 'code'. The meaning of 'child' is defined by the hierarchyMeaning attribute

See the full registry of code systems defined as part of FHIR.

Explanation of the columns that may appear on this page:

Level | A few code lists that FHIR defines are hierarchical - each code is assigned a level. See Code System for further information.
Source | The source of the definition of the code (when the value set draws in codes defined elsewhere)
Code | The code (used as the code in the resource instance). If the code is in italics, this indicates that the code is not selectable ('Abstract')
Display | The display (used in the display element of a Coding). If there is no display, implementers should not simply display the code, but map the concept into their application
Definition | An explanation of the meaning of the concept
Comments | Additional notes about how to use the code

4.3.14.244 Code System http://hl7.org/fhir/goal-status

URL: https://hl7.org/fhir/R4/codesystem-goal-status.html
Patient Care Work Group | Maturity Level: 2 | Trial Use | Use Context: Any

This is a code system defined by the FHIR project.

Summary

Defining URL: | http://hl7.org/fhir/goal-status
Version: | 4.0.1
Name: | GoalLifecycleStatus
Title: | GoalLifecycleStatus
Definition: | Codes that reflect the current state of a goal and whether the goal is still being targeted.
Committee: | Patient Care Work Group
OID: | 2.16.840.1.113883.4.642.4.272 (for OID based terminology systems)
Source Resource | XML / JSON

This Code system is used in the following value sets:

• ValueSet: GoalLifecycleStatus (Codes that reflect the current state of a goal and whether the goal is still being targeted.)

• ValueSet: GoalLifecycleStatus (Codes that reflect the current state of a goal and whether the goal is still being targeted.)

4.3.14.244.1 Content

4.3.14.244.2 GoalLifecycleStatus

Codes that reflect the current state of a goal and whether the goal is still being targeted.

This code system http://hl7.org/fhir/goal-status defines the following codes:

Lvl | Code | Display | Definition
1 | proposed | Proposed | A goal is proposed for this patient.
1 | planned | Planned | A goal is planned for this patient.
1 | accepted | Accepted | A proposed goal was accepted or acknowledged.
2 | active | Active | The goal is being sought actively.
2 | on-hold | On Hold | The goal remains a long term objective but is no longer being actively pursued for a temporary period of time.
2 | completed | Completed | The goal is no longer being sought.
1 | cancelled | Cancelled | The goal has been abandoned.

1 | entered-in-error | Entered in Error | The goal was entered in error and voided.
1 | rejected | Rejected | A proposed goal was rejected.

See the full registry of code systems defined as part of FHIR.

Explanation of the columns that may appear on this page:

Level | A few code lists that FHIR defines are hierarchical - each code is assigned a level. See Code System for further information.
Source | The source of the definition of the code (when the value set draws in codes defined elsewhere)
Code | The code (used as the code in the resource instance). If the code is in italics, this indicates that the code is not selectable ('Abstract')
Display | The display (used in the display element of a Coding). If there is no display, implementers should not simply display the code, but map the concept into their application
Definition | An explanation of the meaning of the concept
Comments | Additional notes about how to use the code

4.3.14.245 Code System http://hl7.org/fhir/sid/ex-icd-10-procedures

URL: https://hl7.org/fhir/R4/codesystem-icd-10-procedures.html
Financial Management Work Group | Maturity Level: 1 | Draft | Use Context: Any

This is a code system defined by the FHIR project.

Summary

Defining URL: | http://hl7.org/fhir/sid/ex-icd-10-procedures
Version: | 4.0.1
Name: | ICD-10ProcedureCodes
Title: | ICD-10 Procedure Codes
Definition: | This value set includes sample ICD-10 Procedure codes.
Committee: | Financial Management Work Group
OID: | 2.16.840.1.113883.4.642.4.575 (for OID based terminology systems)
Copyright: | This is an example set.
Source Resource | XML / JSON

This Code system is used in the following value sets:

• ValueSet: ICD-10 Procedure Codes (This value set includes sample ICD-10 Procedure codes.)
• ValueSet: ICD-10 Procedure Codes (This value set includes sample ICD-10 Procedure codes.)

4.3.14.245.1 Content

4.3.14.245.2 ICD-10 Procedure Codes

This value set includes sample ICD-10 Procedure codes.

Copyright Statement:

This is an example set.

This code system http://hl7.org/fhir/sid/ex-icd-10-procedures defines the following codes:

Code | Display | Definition
123001 | PROC-1 | Procedure 1
123002 | PROC-2 | Procedure 2
123003 | PROC-3 | Procedure 3

See the full registry of code systems defined as part of FHIR.

Explanation of the columns that may appear on this page:

Level | A few code lists that FHIR defines are hierarchical - each code is assigned a level. See Code System for further information.
Source | The source of the definition of the code (when the value set draws in codes defined elsewhere)
Code | The code (used as the code in the resource instance). If the code is in italics, this indicates that the code is not selectable ('Abstract')
Display | The display (used in the display element of a Coding). If there is no display, implementers should not simply display the code, but map the concept into their application
Definition | An explanation of the meaning of the concept
Comments | Additional notes about how to use the code

4.3.14.246 Code System http://terminology.hl7.org/CodeSystem/recommendation-strength

URL: https://hl7.org/fhir/R4/codesystem-recommendation-strength.html
Vocabulary Work Group | Maturity Level: 0 | Informative | Use Context: Any

This is a code system defined by the FHIR project.

Summary

Defining URL: | http://terminology.hl7.org/CodeSystem/recommendation-strength

Version: | 4.0.1
Name: | StrengthOfRecommendationRating
Title: | StrengthOfRecommendationRating
Definition: | A rating system that describes the strength of the recommendation, such as the GRADE, DynaMed, or HGPS systems.
Committee: | ??
OID: | 2.16.840.1.113883.4.642.4.1268 (for OID based terminology systems)
Source Resource | XML / JSON

This Code system is used in the following value sets:

• ValueSet: StrengthOfRecommendationRating (A rating system that describes the strength of the recommendation, such as the GRADE, DynaMed, or HGPS systems.)

• ValueSet: StrengthOfRecommendationRating (A rating system that describes the strength of the recommendation, such as the GRADE, DynaMed, or HGPS systems.)

4.3.14.246.1 Content

4.3.14.246.2 StrengthOfRecommendationRating

A rating system that describes the strength of the recommendation, such as the GRADE, DynaMed, or HGPS systems.

This code system http://terminology.hl7.org/CodeSystem/recommendation-strength defines the following codes:

Code | Display | Definition
strong | Strong | Strong recommendation.
weak | Weak | Weak recommendation.

See the full registry of code systems defined as part of FHIR.

Explanation of the columns that may appear on this page:

Level | A few code lists that FHIR defines are hierarchical - each code is assigned a level. See Code System for further information.
Source | The source of the definition of the code (when the value set draws in codes defined elsewhere)
Code | The code (used as the code in the resource instance). If the code is in italics, this indicates that the code is not selectable ('Abstract')
Display | The display (used in the display element of a Coding). If there is no display, implementers should not simply display the code, but map the concept into their application
Definition | An explanation of the meaning of the concept
Comments | Additional notes about how to use the code

4.3.14.247 Code System http://hl7.org/fhir/graph-compartment-rule

URL: https://hl7.org/fhir/R4/codesystem-graph-compartment-rule.html
FHIR Infrastructure Work Group | Maturity Level: 1 | Trial Use | Use Context: Any

This is a code system defined by the FHIR project.

Summary

Defining URL: | http://hl7.org/fhir/graph-compartment-rule
Version: | 4.0.1
Name: | GraphCompartmentRule
Title: | GraphCompartmentRule
Definition: | How a compartment must be linked.
Committee: | FHIR Infrastructure Work Group
OID: | 2.16.840.1.113883.4.642.4.281 (for OID based terminology systems)
Source Resource | XML / JSON

This Code system is used in the following value sets:

• ValueSet: GraphCompartmentRule (How a compartment must be linked.)

• ValueSet: GraphCompartmentRule (How a compartment must be linked.)

4.3.14.247.1 Content

4.3.14.247.2 GraphCompartmentRule

How a compartment must be linked.

This code system http://hl7.org/fhir/graph-compartment-rule defines the following codes:

Code | Display | Definition
identical | Identical | The compartment must be identical (the same literal reference).
matching | Matching | The compartment must be the same - the record must be about the same patient, but the reference may be different.
different | Different | The compartment must be different.
custom | Custom | The compartment rule is defined in the accompanying FHIRPath expression.

See the full registry of code systems defined as part of FHIR.

Explanation of the columns that may appear on this page:

Level | A few code lists that FHIR defines are hierarchical - each code is assigned a level. See Code System for further information.
Source | The source of the definition of the code (when the value set draws in codes defined elsewhere)
Code | The code (used as the code in the resource instance). If the code is in italics, this indicates that the code is not selectable ('Abstract')
Display | The display (used in the display element of a Coding). If there is no display, implementers should not simply display the code, but map the concept into their application
Definition | An explanation of the meaning of the concept
Comments | Additional notes about how to use the code

4.3.14.248 Code System http://terminology.hl7.org/CodeSystem/allergyintolerance-verification

URL: https://hl7.org/fhir/R4/codesystem-allergyintolerance-verification.html
Patient Care Work Group | Maturity Level: 3 | Trial Use | Use Context: Any

This is a code system defined by the FHIR project.

Summary

Defining URL: | http://terminology.hl7.org/CodeSystem/allergyintolerance-verification
Version: | 4.0.1
Name: | AllergyIntoleranceVerificationStatusCodes
Title: | AllergyIntolerance Verification Status Codes
Definition: | Preferred value set for AllergyIntolerance Verification Status.
Committee: | Patient Care Work Group
OID: | 2.16.840.1.113883.4.642.4.1371 (for OID based terminology systems)
Source Resource | XML / JSON

This Code system is used in the following value sets:

• ValueSet: AllergyIntolerance Verification Status Codes (Preferred value set for AllergyIntolerance Verification Status.)

• ValueSet: AllergyIntolerance Verification Status Codes (Preferred value set for AllergyIntolerance Verification Status.)

4.3.14.248.1 Content

4.3.14.248.2 AllergyIntolerance Verification Status Codes

Preferred value set for AllergyIntolerance Verification Status.

This code system http://terminology.hl7.org/CodeSystem/allergyintolerance-verification defines the following codes:

Code | Display | Definition
unconfirmed | Unconfirmed | A low level of certainty about the propensity for a reaction to the identified substance.
confirmed | Confirmed | A high level of certainty about the propensity for a reaction to the identified substance, which may include clinical evidence by testing or rechallenge.
refuted | Refuted | A propensity for a reaction to the identified substance has been disputed or disproven with a sufficient level of clinical certainty to justify invalidating the assertion. This might or might not include testing or rechallenge.
entered-in-error | Entered in Error | The statement was entered in error and is not valid.

See the full registry of code systems defined as part of FHIR.

Explanation of the columns that may appear on this page:

Level | A few code lists that FHIR defines are hierarchical - each code is assigned a level. See Code System for further information.
Source | The source of the definition of the code (when the value set draws in codes defined elsewhere)
Code | The code (used as the code in the resource instance). If the code is in italics, this indicates that the code is not selectable ('Abstract')
Display | The display (used in the display element of a Coding). If there is no display, implementers should not simply display the code, but map the concept into their application
Definition | An explanation of the meaning of the concept
Comments | Additional notes about how to use the code

4.3.14.249 Code System http://terminology.hl7.org/CodeSystem/activity-definition-category

URL: https://hl7.org/fhir/R4/codesystem-activity-definition-category.html
Vocabulary Work Group | Maturity Level: 0 | Informative | Use Context: Any

This is a code system defined by the FHIR project.

Summary

Defining URL: | http://terminology.hl7.org/CodeSystem/activity-definition-category

Version: | 4.0.1
Name: | ActivityDefinitionCategory
Title: | ActivityDefinitionCategory
Definition: | High-level categorization of the type of activity.
Committee: | ??
OID: | 2.16.840.1.113883.4.642.4.1243 (for OID based terminology systems)
Source Resource | XML / JSON

This Code system is used in the following value sets:

• ValueSet: ActivityDefinitionCategory (High-level categorization of the type of activity.)

• ValueSet: ActivityDefinitionCategory (High-level categorization of the type of activity.)

4.3.14.249.1 Content

4.3.14.249.2 ActivityDefinitionCategory

High-level categorization of the type of activity.

This code system http://terminology.hl7.org/CodeSystem/activity-definition-category defines the following codes:

Code | Display | Definition
treatment | Treatment | The activity is intended to provide or is related to treatment of the patient.
education | Education | The activity is intended to provide or is related to education of the patient.
assessment | Assessment | The activity is intended to perform or is related to assessment of the patient.

See the full registry of code systems defined as part of FHIR.

Explanation of the columns that may appear on this page:

Level | A few code lists that FHIR defines are hierarchical - each code is assigned a level. See Code System for further information.
Source | The source of the definition of the code (when the value set draws in codes defined elsewhere)
Code | The code (used as the code in the resource instance). If the code is in italics, this indicates that the code is not selectable ('Abstract')
Display | The display (used in the display element of a Coding). If there is no display, implementers should not simply display the code, but map the concept into their application
Definition | An explanation of the meaning of the concept
Comments | Additional notes about how to use the code

4.3.14.250 Code System http://terminology.hl7.org/CodeSystem/list-order

URL: https://hl7.org/fhir/R4/codesystem-list-order.html
Structured Documents Work Group | Maturity Level: 0 | Informative | Use Context: Any

This is a code system defined by the FHIR project.

Summary

Defining URL: | http://terminology.hl7.org/CodeSystem/list-order
Version: | 4.0.1
Name: | ListOrderCodes
Title: | List Order Codes
Definition: | Base values for the order of the items in a list resource.
Committee: | Structured Documents Work Group
OID: | 2.16.840.1.113883.4.642.4.1107 (for OID based terminology systems)
Source Resource | XML / JSON

This Code system is used in the following value sets:

• ValueSet: List Order Codes (Base values for the order of the items in a list resource.)

• ValueSet: List Order Codes (Base values for the order of the items in a list resource.)

4.3.14.250.1 Content

4.3.14.250.2 List Order Codes

Base values for the order of the items in a list resource.

This code system http://terminology.hl7.org/CodeSystem/list-order defines the following codes:

Code | Display | Definition
user | Sorted by User | The list was sorted by a user. The criteria the user used are not specified.
system | Sorted by System | The list was sorted by the system. The criteria the user used are not specified; define additional codes to specify a particular order (or use other defined codes).
event-date | Sorted by Event Date | The list is sorted by the data of the event. This can be used when the list has items which are dates with past or future events.
entry-date | Sorted by Item Date | The list is sorted by the date the item was added to the list. Note that the date added to the list is not explicit in the list itself.

priority | Sorted by Priority | The list is sorted by priority. The exact method in which priority has been determined is not specified.
alphabetic | Sorted Alphabetically | The list is sorted alphabetically by an unspecified property of the items in the list.
category | Sorted by Category | The list is sorted categorically by an unspecified property of the items in the list.
patient | Sorted by Patient | The list is sorted by patient, with items for each patient grouped together.

See the full registry of code systems defined as part of FHIR.

Explanation of the columns that may appear on this page:

Level | A few code lists that FHIR defines are hierarchical - each code is assigned a level. See Code System for further information.
Source | The source of the definition of the code (when the value set draws in codes defined elsewhere)
Code | The code (used as the code in the resource instance). If the code is in italics, this indicates that the code is not selectable ('Abstract')
Display | The display (used in the display element of a Coding). If there is no display, implementers should not simply display the code, but map the concept into their application
Definition | An explanation of the meaning of the concept
Comments | Additional notes about how to use the code

4.3.14.251 Code System http://hl7.org/fhir/issue-severity

URL: https://hl7.org/fhir/R4/codesystem-issue-severity.html
FHIR Infrastructure Work Group | Maturity Level: N | Normative (from v4.0.0) | Use Context: Any

| This page has been approved as part of an ANSI standard. See the Infrastructure Package for further details.

This is a code system defined by the FHIR project.

Summary

Defining URL: | http://hl7.org/fhir/issue-severity
Version: | 4.0.1
Name: | IssueSeverity
Title: | IssueSeverity
Definition: | How the issue affects the success of the action.
Committee: | FHIR Infrastructure Work Group
OID: | 2.16.840.1.113883.4.642.4.409 (for OID based terminology systems)
Source Resource | XML / JSON

This Code system is used in the following value sets:

• ValueSet: IssueSeverity (How the issue affects the success of the action.)

• ValueSet: IssueSeverity (How the issue affects the success of the action.)

4.3.14.251.1 Content

4.3.14.251.2 IssueSeverity

How the issue affects the success of the action.

This code system http://hl7.org/fhir/issue-severity defines the following codes:

Code | Display | Definition
fatal | Fatal | The issue caused the action to fail and no further checking could be performed.
error | Error | The issue is sufficiently important to cause the action to fail.
warning | Warning | The issue is not important enough to cause the action to fail but may cause it to be performed suboptimally or in a way that is not as desired.
information | Information | The issue has no relation to the degree of success of the action.

See the full registry of code systems defined as part of FHIR.

Explanation of the columns that may appear on this page:

Level | A few code lists that FHIR defines are hierarchical - each code is assigned a level. See Code System for further information.
Source | The source of the definition of the code (when the value set draws in codes defined elsewhere)
Code | The code (used as the code in the resource instance). If the code is in italics, this indicates that the code is not selectable ('Abstract')
Display | The display (used in the display element of a Coding). If there is no display, implementers should not simply display the code, but map the concept into their application
Definition | An explanation of the meaning of the concept
Comments | Additional notes about how to use the code

4.3.14.252 Code System http://hl7.org/fhir/diagnostic-report-status

URL: https://hl7.org/fhir/R4/codesystem-diagnostic-report-status.html
Orders and Observations Work Group | Maturity Level: 3 | Trial Use | Use Context: Any

This is a code system defined by the FHIR project.

Summary

Defining URL: | http://hl7.org/fhir/diagnostic-report-status

Version: | 4.0.1
Name: | DiagnosticReportStatus
Title: | DiagnosticReportStatus
Definition: | The status of the diagnostic report.
Committee: | Orders and Observations Work Group
OID: | 2.16.840.1.113883.4.642.4.236 (for OID based terminology systems)
Source Resource | XML / JSON

This Code system is used in the following value sets:

• ValueSet: DiagnosticReportStatus (The status of the diagnostic report.)

• ValueSet: DiagnosticReportStatus (The status of the diagnostic report.)

4.3.14.252.1 Content

4.3.14.252.2 DiagnosticReportStatus

The status of the diagnostic report.

This code system http://hl7.org/fhir/diagnostic-report-status defines the following codes:

Lvl | Code | Display | Definition
1 | registered | Registered | The existence of the report is registered, but there is nothing yet available.
1 | partial | Partial | This is a partial (e.g. initial, interim or preliminary) report: data in the report may be incomplete or unverified.
2 | preliminary | Preliminary | Verified early results are available, but not all results are final.
1 | final | Final | The report is complete and verified by an authorized person.
1 | amended | Amended | Subsequent to being final, the report has been modified. This includes any change in the results, diagnosis, narrative text, or other content of a report that has been issued.
2 | corrected | Corrected | Subsequent to being final, the report has been modified to correct an error in the report or referenced results.
2 | appended | Appended | Subsequent to being final, the report has been modified by adding new content. The existing content is unchanged.
1 | cancelled | Cancelled | The report is unavailable because the measurement was not started or not completed (also sometimes called "aborted").
1 | entered-in-error | Entered in Error | The report has been withdrawn following a previous final release. This electronic record should never have existed, though it is possible that real-world decisions were based on it. (If real-world activity has occurred, the status should be "cancelled" rather than "entered-in-error".).
1 | unknown | Unknown | The authoring/source system does not know which of the status values currently applies for this observation. Note: This concept is not to be used for "other" - one of the listed statuses is presumed to apply, but the authoring/source system does not know which.

See the full registry of code systems defined as part of FHIR.

Explanation of the columns that may appear on this page:

Level | A few code lists that FHIR defines are hierarchical - each code is assigned a level. See Code System for further information.
Source | The source of the definition of the code (when the value set draws in codes defined elsewhere)
Code | The code (used as the code in the resource instance). If the code is in italics, this indicates that the code is not selectable ('Abstract')
Display | The display (used in the display element of a Coding). If there is no display, implementers should not simply display the code, but map the concept into their application
Definition | An explanation of the meaning of the concept
Comments | Additional notes about how to use the code

4.3.14.253 Code System http://terminology.hl7.org/fhir/CodeSystem/medicationdispense-category

URL: https://hl7.org/fhir/R4/codesystem-medicationdispense-category.html
Pharmacy Work Group | Maturity Level: 0 | Informative | Use Context: Any

This is a code system defined by the FHIR project.

Summary

Defining URL: | http://terminology.hl7.org/fhir/CodeSystem/medicationdispense-category
Version: | 4.0.1
Name: | MedicationDispense Category Codes
Title: | Medication dispense category codes
Definition: | MedicationDispense Category Codes
Committee: | Pharmacy Work Group
OID: | 2.16.840.1.113883.4.642.4.1315 (for OID based terminology systems)
Source Resource | XML / JSON

This Code system is used in the following value sets:

• ValueSet: Medication dispense category codes (MedicationDispense Category Codes)

• ValueSet: Medication dispense category codes (MedicationDispense Category Codes)

4.3.14.253.1 Content

4.3.14.253.2 Medication dispense category codes

MedicationDispense Category Codes

This code system http://terminology.hl7.org/fhir/CodeSystem/medicationdispense-category defines the following codes:

Code | Display | Definition
inpatient | Inpatient | Includes dispenses for medications to be administered or consumed in an inpatient or acute care setting.
outpatient | Outpatient | Includes dispenses for medications to be administered or consumed in an outpatient setting (for example, Emergency Department, Outpatient Clinic, Outpatient Surgery, Doctor's office).
community | Community | Includes dispenses for medications to be administered or consumed by the patient in their home (this would include long term care or nursing homes, hospices, etc.).
discharge | Discharge | Includes dispenses for medications created when the patient is being released from a facility.

See the full registry of code systems defined as part of FHIR.

Explanation of the columns that may appear on this page:

Level | A few code lists that FHIR defines are hierarchical - each code is assigned a level. See Code System for further information.
Source | The source of the definition of the code (when the value set draws in codes defined elsewhere)
Code | The code (used as the code in the resource instance). If the code is in italics, this indicates that the code is not selectable ('Abstract')
Display | The display (used in the display element of a Coding). If there is no display, implementers should not simply display the code, but map the concept into their application
Definition | An explanation of the meaning of the concept
Comments | Additional notes about how to use the code

4.3.14.254 Code System http://hl7.org/fhir/appointmentstatus

URL: https://hl7.org/fhir/R4/codesystem-appointmentstatus.html
Patient Administration Work Group | Maturity Level: 3 | Trial Use | Use Context: Any

This is a code system defined by the FHIR project.

Summary

Defining URL: | http://hl7.org/fhir/appointmentstatus
Version: | 4.0.1
Name: | AppointmentStatus
Title: | AppointmentStatus
Definition: | The free/busy status of an appointment.
Committee: | Patient Administration Work Group
OID: | 2.16.840.1.113883.4.642.4.485 (for OID based terminology systems)
Source Resource | XML / JSON

This Code system is used in the following value sets:

• ValueSet: AppointmentStatus (The free/busy status of an appointment.)

• ValueSet: AppointmentStatus (The free/busy status of an appointment.)

4.3.14.254.1 Content

4.3.14.254.2 AppointmentStatus

The free/busy status of an appointment.

This code system http://hl7.org/fhir/appointmentstatus defines the following codes:

Code | Display | Definition
proposed | Proposed | None of the participant(s) have finalized their acceptance of the appointment request, and the start/end time might not be set yet.
pending | Pending | Some or all of the participant(s) have not finalized their acceptance of the appointment request.
booked | Booked | All participant(s) have been considered and the appointment is confirmed to go ahead at the date/times specified.
arrived | Arrived | The patient/patients has/have arrived and is/are waiting to be seen.
fulfilled | Fulfilled | The planning stages of the appointment are now complete, the encounter resource will exist and will track further status changes. Note that an encounter may exist before the appointment status is fulfilled for many reasons.
cancelled | Cancelled | The appointment has been cancelled.
noshow | No Show | Some or all of the participant(s) have not/did not appear for the appointment (usually the patient).
entered-in-error | Entered in error | This instance should not have been part of this patient's medical record.
checked-in | Checked In | When checked in, all pre-encounter administrative work is complete, and the encounter may begin. (where multiple patients are involved, they are all present).
waitlist | Waitlisted | The appointment has been placed on a waitlist, to be scheduled/confirmed in the future when a slot/service is available. A specific time might or might not be pre-allocated.

See the full registry of code systems defined as part of FHIR.

Explanation of the columns that may appear on this page:

Level | A few code lists that FHIR defines are hierarchical - each code is assigned a level. See Code System for further information.
Source | The source of the definition of the code (when the value set draws in codes defined elsewhere)

Code | The code (used as the code in the resource instance). If the code is in italics, this indicates that the code is not selectable ('Abstract')
Display | The display (used in the display element of a Coding). If there is no display, implementers should not simply display the code, but map the concept into their application
Definition | An explanation of the meaning of the concept
Comments | Additional notes about how to use the code

4.3.14.255 Code System http://hl7.org/fhir/product-status

URL: https://hl7.org/fhir/R4/codesystem-product-status.html
Orders and Observations Work Group | Maturity Level: 0 | Trial Use | Use Context: Any

This is a code system defined by the FHIR project.

Summary

Defining URL: | http://hl7.org/fhir/product-status
Version: | 4.0.1
Name: | BiologicallyDerivedProductStatus
Title: | BiologicallyDerivedProductStatus
Definition: | Biologically Derived Product Status.
Committee: | Orders and Observations Work Group
OID: | 2.16.840.1.113883.4.642.4.903 (for OID based terminology systems)
Source Resource | XML / JSON

This Code system is used in the following value sets:

• ValueSet: BiologicallyDerivedProductStatus (Biologically Derived Product Status.)

• ValueSet: BiologicallyDerivedProductStatus (Biologically Derived Product Status.)

4.3.14.255.1 Content

4.3.14.255.2 BiologicallyDerivedProductStatus

Biologically Derived Product Status.

This code system http://hl7.org/fhir/product-status defines the following codes:

Code | Display | Definition
available | Available | Product is currently available for use.
unavailable | Unavailable | Product is not currently available for use.

See the full registry of code systems defined as part of FHIR.

Explanation of the columns that may appear on this page:

Level | A few code lists that FHIR defines are hierarchical - each code is assigned a level. See Code System for further information.
Source | The source of the definition of the code (when the value set draws in codes defined elsewhere)
Code | The code (used as the code in the resource instance). If the code is in italics, this indicates that the code is not selectable ('Abstract')
Display | The display (used in the display element of a Coding). If there is no display, implementers should not simply display the code, but map the concept into their application
Definition | An explanation of the meaning of the concept
Comments | Additional notes about how to use the code

4.3.14.256 Code System http://terminology.hl7.org/CodeSystem/communication-category

URL: https://hl7.org/fhir/R4/codesystem-communication-category.html
Patient Care Work Group | Maturity Level: 1 | Draft | Use Context: Any

This is a code system defined by the FHIR project.

Summary

Defining URL: | http://terminology.hl7.org/CodeSystem/communication-category
Version: | 4.0.1
Name: | CommunicationCategory
Title: | CommunicationCategory
Definition: | Codes for general categories of communications such as alerts, instructions, etc.
Committee: | Patient Care Work Group
OID: | 2.16.840.1.113883.4.642.4.1076 (for OID based terminology systems)
Source Resource | XML / JSON

This Code system is used in the following value sets:

• ValueSet: CommunicationCategory (Codes for general categories of communications such as alerts, instructions, etc.)

• ValueSet: CommunicationCategory (Codes for general categories of communications such as alerts, instructions, etc.)

4.3.14.256.1 Content

4.3.14.256.2 CommunicationCategory

Codes for general categories of communications such as alerts, instructions, etc.

This code system http://terminology.hl7.org/CodeSystem/communication-category defines the following codes:

Code | Display | Definition
alert | Alert | The communication conveys an alert.
notification | Notification | The communication conveys a notification.
reminder | Reminder | The communication conveys a reminder.
instruction | Instruction | The communication conveys an instruction.

See the full registry of code systems defined as part of FHIR.

Explanation of the columns that may appear on this page:

Level | A few code lists that FHIR defines are hierarchical - each code is assigned a level. See Code System for further information.
Source | The source of the definition of the code (when the value set draws in codes defined elsewhere)
Code | The code (used as the code in the resource instance). If the code is in italics, this indicates that the code is not selectable ('Abstract')
Display | The display (used in the display element of a Coding). If there is no display, implementers should not simply display the code, but map the concept into their application
Definition | An explanation of the meaning of the concept
Comments | Additional notes about how to use the code

4.3.14.257 Code System http://terminology.hl7.org/CodeSystem/contract-content-derivative

URL: https://hl7.org/fhir/R4/codesystem-contract-content-derivative.html
Financial Management Work Group | Maturity Level: 1 | Draft | Use Context: Any

This is a code system defined by the FHIR project.

Summary

Defining URL: | http://terminology.hl7.org/CodeSystem/contract-content-derivative
Version: | 4.0.1
Name: | ContractContentDerivationCodes
Title: | Contract Content Derivation Codes
Definition: | This is an example set of Content Derivative type codes, which represent the minimal content derived from the basal information source at a specific stage in its lifecycle, which is sufficient to manage that source information, for example, in a repository, registry, processes and workflows, for making access control decisions, and providing query responses.
Committee: | Financial Management Work Group
OID: | 2.16.840.1.113883.4.642.4.1204 (for OID based terminology systems)
Copyright: | This is an example set.
Source Resource | XML / JSON

This Code system is used in the following value sets:

• ValueSet: Contract Content Derivation Codes (This is an example set of Content Derivative type codes, which represent the minimal content derived from the basal information source at a specific stage in its lifecycle, which is sufficient to manage that source information, for example, in a repository, registry, processes and workflows, for making access control decisions, and providing query responses.)

• ValueSet: Contract Content Derivation Codes (This is an example set of Content Derivative type codes, which represent the minimal content derived from the basal information source at a specific stage in its lifecycle, which is sufficient to manage that source information, for example, in a repository, registry, processes and workflows, for making access control decisions, and providing query responses.)

4.3.14.257.1 Content

This is an example set of Content Derivative type codes, which represent the minimal content derived from the basal information source at a specific stage in its lifecycle, which is sufficient to manage that source information, for example, in a repository, registry, processes and workflows, for making access control decisions, and providing query responses.

4.3.14.257.2 Contract Content Derivation Codes

This is an example set of Content Derivative type codes, which represent the minimal content derived from the basal information source at a specific stage in its lifecycle, which is sufficient to manage that source information, for example, in a repository, registry, processes and workflows, for making access control decisions, and providing query responses.

Copyright Statement:

This is an example set.

This code system http://terminology.hl7.org/CodeSystem/contract-content-derivative defines the following codes:

Code | Display | Definition
registration | Content Registration | Content derivative that conveys sufficient information needed to register the source basal content from which it is derived. This derivative content may be used to register the basal content as it changes status in its lifecycle. For example, content registration may occur when the basal content is created, updated, inactive, or deleted.
retrieval | Content Retrieval | A content derivative that conveys sufficient information to locate and retrieve the content.
statement | Content Statement | Content derivative that has less than full fidelity to the basal information source from which it was 'transcribed'. It provides recipients with the full content representation they may require for compliance purposes, and typically include a reference to or an attached unstructured representation for recipients needing an exact copy of the legal agreement.
shareable | Shareable Content | A Content Derivative that conveys sufficient information to determine the authorized entities with which the content may be shared.

See the full registry of code systems defined as part of FHIR.

Explanation of the columns that may appear on this page:

Level | A few code lists that FHIR defines are hierarchical - each code is assigned a level. See Code System for further information.
Source | The source of the definition of the code (when the value set draws in codes defined elsewhere)
Code | The code (used as the code in the resource instance). If the code is in italics, this indicates that the code is not selectable ('Abstract')
Display | The display (used in the display element of a Coding). If there is no display, implementers should not simply display the code, but map the concept into their application
Definition | An explanation of the meaning of the concept
Comments | Additional notes about how to use the code

4.3.14.258 Code System http://terminology.hl7.org/CodeSystem/ex-serviceplace

URL: https://hl7.org/fhir/R4/codesystem-service-place.html
Financial Management Work Group | Maturity Level: 1 | Draft | Use Context: Any

This is a code system defined by the FHIR project.

Summary

Defining URL: | http://terminology.hl7.org/CodeSystem/ex-serviceplace
Version: | 4.0.1
Name: | ExampleServicePlaceCodes
Title: | Example Service Place Codes
Definition: | This value set includes a smattering of Service Place codes.
Committee: | Financial Management Work Group
OID: | 2.16.840.1.113883.4.642.4.1157 (for OID based terminology systems)
Copyright: | This is an example set.
Source Resource | XML / JSON

This Code system is used in the following value sets:

• ValueSet: Example Service Place Codes (This value set includes a smattering of Service Place codes.)
• ValueSet: Example Service Place Codes (This value set includes a smattering of Service Place codes.)

4.3.14.258.1 Content

4.3.14.258.2 Example Service Place Codes

This value set includes a smattering of Service Place codes.

Copyright Statement:

This is an example set.

This code system http://terminology.hl7.org/CodeSystem/ex-serviceplace defines the following codes:

Code | Display | Definition
01 | Pharmacy | A facility or location where drugs and other medically related items and services are sold, dispensed, or otherwise provided directly to patients.
03 | School | A facility whose primary purpose is education.
04 | Homeless Shelter | A facility or location whose primary purpose is to provide temporary housing to homeless individuals (e.g., emergency shelters, individual or family shelters).
05 | Indian Health Service Free-standing Facility | A facility or location, owned and operated by the Indian Health Service, which provides diagnostic, therapeutic (surgical and nonsurgical), and rehabilitation services to American Indians and Alaska Natives who do not require hospitalization.
06 | Indian Health Service Provider-based Facility | A facility or location, owned and operated by the Indian Health Service, which provides diagnostic, therapeutic (surgical and nonsurgical), and rehabilitation services rendered by, or under the supervision of, physicians to American Indians and Alaska Natives admitted as inpatients or outpatients.
07 | Tribal 638 Free-Standing Facility | A facility or location owned and operated by a federally recognized American Indian or Alaska Native tribe or tribal organization under a 638 agreement, which provides diagnostic, therapeutic (surgical and nonsurgical), and rehabilitation services to tribal members who do not require hospitalization.

08 | Tribal 638 Provider-Based Facility | A facility or location owned and operated by a federally recognized American Indian or Alaska Native tribe or tribal organization under a 638 agreement, which provides diagnostic, therapeutic (surgical and nonsurgical), and rehabilitation services to tribal members admitted as inpatients or outpatients.
09 | Prison/Correctional Facility | A prison, jail, reformatory, work farm, detention center, or any other similar facility maintained by either Federal, State or local authorities for the purpose of confinement or rehabilitation of adult or juvenile criminal offenders.
11 | Office | Location, other than a hospital, skilled nursing facility (SNF), military treatment facility, community health center, State or local public health clinic, or intermediate care facility (ICF), where the health professional routinely provides health examinations, diagnosis, and treatment of illness or injury on an ambulatory basis.
12 | Home | Location, other than a hospital or other facility, where the patient receives care in a private residence.
13 | Assisted Living Fa | Congregate residential facility with self-contained living units providing assessment of each resident's needs and on-site support 24 hours a day, 7 days a week, with the capacity to deliver or arrange for services including some health care and other services.
14 | Group Home | A residence, with shared living areas, where clients receive supervision and other services such as social and/or behavioral services, custodial service, and minimal services (e.g., medication administration).
15 | Mobile Unit | A facility/unit that moves from place-to-place equipped to provide preventive, screening, diagnostic, and/or treatment services.
19 | Off Campus-Outpatient Hospital | portion of an off-campus hospital provider-based department which provides diagnostic, therapeutic (both surgical and nonsurgical), and rehabilitation services to sick or injured persons who do not require hospitalization or institutionalization.
20 | Urgent Care Facility | Location, distinct from a hospital emergency room, an office, or a clinic, whose purpose is to diagnose and treat illness or injury for unscheduled, ambulatory patients seeking immediate medical attention.
21 | Inpatient Hospital | A facility, other than psychiatric, which primarily provides diagnostic, therapeutic (both surgical and nonsurgical), and rehabilitation services by, or under, the supervision of physicians to patients admitted for a variety of medical conditions.
41 | Ambulance—Land | A land vehicle specifically designed, equipped and staffed for lifesaving and transporting the sick or injured.

See the full registry of code systems defined as part of FHIR.

Explanation of the columns that may appear on this page:

Level | A few code lists that FHIR defines are hierarchical - each code is assigned a level. See Code System for further information.
Source | The source of the definition of the code (when the value set draws in codes defined elsewhere)
Code | The code (used as the code in the resource instance). If the code is in italics, this indicates that the code is not selectable ('Abstract')
Display | The display (used in the display element of a Coding). If there is no display, implementers should not simply display the code, but map the concept into their application
Definition | An explanation of the meaning of the concept
Comments | Additional notes about how to use the code

4.3.14.259 Code System http://terminology.hl7.org/CodeSystem/audit-entity-type

URL: https://hl7.org/fhir/R4/codesystem-audit-entity-type.html
Security Work Group | Maturity Level: 3 | Trial Use | Use Context: Any

This is a code system defined by the FHIR project.

Summary

Defining URL: | http://terminology.hl7.org/CodeSystem/audit-entity-type
Version: | 4.0.1
Name: | AuditEventEntityType
Title: | Audit event entity type
Definition: | Code for the entity type involved in the audit event.
Committee: | Security Work Group
OID: | 2.16.840.1.113883.4.642.4.1134 (for OID based terminology systems)
Source Resource | XML / JSON

This Code system is used in the following value sets:

• ValueSet: Audit event entity type (Code for the entity type involved in the audit event.)
• ValueSet: Audit event entity type (Code for the entity type involved in the audit event.)

4.3.14.259.1 Content

4.3.14.259.2 Audit event entity type

Code for the entity type involved in the audit event.

This code system http://terminology.hl7.org/CodeSystem/audit-entity-type defines the following codes:

Code | Display | Definition
1 | Person | Person
2 | System Object | System Object
3 | Organization | Organization
4 | Other | Other

See the full registry of code systems defined as part of FHIR.

Explanation of the columns that may appear on this page:

Level | A few code lists that FHIR defines are hierarchical - each code is assigned a level. See Code System for further information.
Source | The source of the definition of the code (when the value set draws in codes defined elsewhere)
Code | The code (used as the code in the resource instance). If the code is in italics, this indicates that the code is not selectable ('Abstract')
Display | The display (used in the display element of a Coding). If there is no display, implementers should not simply display the code, but map the concept into their application
Definition | An explanation of the meaning of the concept
Comments | Additional notes about how to use the code

4.3.14.260 Code System http://hl7.org/fhir/map-source-list-mode

URL: https://hl7.org/fhir/R4/codesystem-map-source-list-mode.html
FHIR Infrastructure Work Group | Maturity Level: 2 | Trial Use | Use Context: Any

This is a code system defined by the FHIR project.

Summary

Defining URL: | http://hl7.org/fhir/map-source-list-mode
Version: | 4.0.1
Name: | StructureMapSourceListMode
Title: | StructureMapSourceListMode
Definition: | If field is a list, how to manage the source.
Committee: | FHIR Infrastructure Work Group
OID: | 2.16.840.1.113883.4.642.4.684 (for OID based terminology systems)
Source Resource | XML / JSON

This Code system is used in the following value sets:

• ValueSet: StructureMapSourceListMode (If field is a list, how to manage the source.)
• ValueSet: StructureMapSourceListMode (If field is a list, how to manage the source.)

4.3.14.260.1 Content

4.3.14.260.2 StructureMapSourceListMode

If field is a list, how to manage the source.

This code system http://hl7.org/fhir/map-source-list-mode defines the following codes:

Code | Display | Definition
first | First | Only process this rule for the first in the list.
not_first | All but the first | Process this rule for all but the first.
last | Last | Only process this rule for the last in the list.
not_last | All but the last | Process this rule for all but the last.
only_one | Enforce only one | Only process this rule is there is only item.

See the full registry of code systems defined as part of FHIR.

Explanation of the columns that may appear on this page:

Level | A few code lists that FHIR defines are hierarchical - each code is assigned a level. See Code System for further information.
Source | The source of the definition of the code (when the value set draws in codes defined elsewhere)
Code | The code (used as the code in the resource instance). If the code is in italics, this indicates that the code is not selectable ('Abstract')
Display | The display (used in the display element of a Coding). If there is no display, implementers should not simply display the code, but map the concept into their application
Definition | An explanation of the meaning of the concept
Comments | Additional notes about how to use the code

4.3.14.261 Code System http://terminology.hl7.org/CodeSystem/goal-relationship-type

URL: https://hl7.org/fhir/R4/codesystem-goal-relationship-type.html
Vocabulary Work Group | Maturity Level: 0 | Informative | Use Context: Any

This is a code system defined by the FHIR project.

Summary

Defining URL: | http://terminology.hl7.org/CodeSystem/goal-relationship-type
Version: | 4.0.1
Name: | GoalRelationshipType
Title: | GoalRelationshipType
Definition: | Types of relationships between two goals.
Committee: | ??

OID: | 2.16.840.1.113883.4.642.4.1269 (for OID based terminology systems)
Source Resource | XML / JSON

This Code system is used in the following value sets:

• ValueSet: GoalRelationshipType (Types of relationships between two goals.)

• ValueSet: GoalRelationshipType (Types of relationships between two goals.)

4.3.14.261.1 Content

4.3.14.261.2 GoalRelationshipType

Types of relationships between two goals.

This code system http://terminology.hl7.org/CodeSystem/goal-relationship-type defines the following codes:

Code | Display | Definition
predecessor | Predecessor | Indicates that the target goal is one which must be met before striving for the current goal.
successor | Successor | Indicates that the target goal is a desired objective once the current goal is met.
replacement | Replacement | Indicates that this goal has been replaced by the target goal.
milestone | Milestone | Indicates that the target goal is considered to be a "piece" of attaining this goal.
other | Other | Indicates that the relationship is not covered by one of the pre-defined codes. (An extension may convey more information about the meaning of the relationship.).

See the full registry of code systems defined as part of FHIR.

Explanation of the columns that may appear on this page:

Level | A few code lists that FHIR defines are hierarchical - each code is assigned a level. See Code System for further information.
Source | The source of the definition of the code (when the value set draws in codes defined elsewhere)
Code | The code (used as the code in the resource instance). If the code is in italics, this indicates that the code is not selectable ('Abstract')
Display | The display (used in the display element of a Coding). If there is no display, implementers should not simply display the code, but map the concept into their application
Definition | An explanation of the meaning of the concept
Comments | Additional notes about how to use the code

4.3.14.262 Code System http://terminology.hl7.org/CodeSystem/contracttermsubtypecodes

URL: https://hl7.org/fhir/R4/codesystem-contract-term-subtype.html
Financial Management Work Group | Maturity Level: 1 | Draft | Use Context: Any

This is a code system defined by the FHIR project.

Summary

Defining URL: | http://terminology.hl7.org/CodeSystem/contracttermsubtypecodes
Version: | 4.0.1
Name: | ContractTermSubtypeCodes
Title: | Contract Term Subtype Codes
Definition: | This value set includes sample Contract Term SubType codes.
Committee: | Financial Management Work Group
OID: | 2.16.840.1.113883.4.642.4.1200 (for OID based terminology systems)
Copyright: | This is an example set.
Source Resource | XML / JSON

This Code system is used in the following value sets:

• ValueSet: Contract Term Subtype Codes (This value set includes sample Contract Term SubType codes.)

• ValueSet: Contract Term Subtype Codes (This value set includes sample Contract Term SubType codes.)

4.3.14.262.1 Content

4.3.14.262.2 Contract Term Subtype Codes

This value set includes sample Contract Term SubType codes.

Copyright Statement:

This is an example set.

This code system http://terminology.hl7.org/CodeSystem/contracttermsubtypecodes defines the following codes:

Code | Display | Definition
condition | Condition | Terms that go to the very root of a contract.
warranty | Warranty | Less imperative than a condition, so the contract will survive a breach
innominate | Innominate | Breach of which might or might not go to the root of the contract depending upon the nature of the breach

See the full registry of code systems defined as part of FHIR.

Explanation of the columns that may appear on this page:

Level | A few code lists that FHIR defines are hierarchical - each code is assigned a level. See Code System for further information.
Source | The source of the definition of the code (when the value set draws in codes defined elsewhere)
Code | The code (used as the code in the resource instance). If the code is in italics, this indicates that the code is not selectable ('Abstract')
Display | The display (used in the display element of a Coding). If there is no display, implementers should not simply display the code, but map the concept into their application
Definition | An explanation of the meaning of the concept
Comments | Additional notes about how to use the code

4.3.14.263 Code System http://hl7.org/fhir/contract-action-status

URL: https://hl7.org/fhir/R4/codesystem-contract-actionstatus.html
Financial Management Work Group | Maturity Level: 1 | Draft | Use Context: Any

This is a code system defined by the FHIR project.

Summary

Defining URL: | http://hl7.org/fhir/contract-action-status
Version: | 4.0.1
Name: | ContractResourceActionStatusCodes
Title: | Contract Resource Action Status codes
Definition: | This value set contract specific codes for action status.
Committee: | Financial Management Work Group
OID: | 2.16.840.1.113883.4.642.4.1304 (for OID based terminology systems)
Copyright: | HL7 International.
Source Resource | XML / JSON

This Code system is used in the following value sets:

• ValueSet: Contract Resource Action Status codes (This value set contract specific codes for action status.)
• ValueSet: Contract Resource Action Status codes (This value set contract specific codes for action status.)

4.3.14.263.1 Content

Each definition includes usage notes explaining the precedence order in contract lifecycle - i.e., while only some stages are required, the order in which they may occur is deterministic; and a map to comparable FHIR and v.3 status codes. It follows guidance about use of status codes in FHIR at http://build.fhir.org/sc.html.

4.3.14.263.2 Contract Resource Action Status codes

This value set contract specific codes for action status.

Copyright Statement:

HL7 International.

This code system http://hl7.org/fhir/contract-action-status defines the following codes:

Code | Display | Definition
complete | Complete | To be completed

See the full registry of code systems defined as part of FHIR.

Explanation of the columns that may appear on this page:

Level | A few code lists that FHIR defines are hierarchical - each code is assigned a level. See Code System for further information.
Source | The source of the definition of the code (when the value set draws in codes defined elsewhere)
Code | The code (used as the code in the resource instance). If the code is in italics, this indicates that the code is not selectable ('Abstract')
Display | The display (used in the display element of a Coding). If there is no display, implementers should not simply display the code, but map the concept into their application
Definition | An explanation of the meaning of the concept
Comments | Additional notes about how to use the code

4.3.14.264 Code System http://terminology.hl7.org/CodeSystem/immunization-program-eligibility

URL: https://hl7.org/fhir/R4/codesystem-immunization-program-eligibility.html
Public Health and Emergency Response Work Group | Maturity Level: 1 | Draft | Use Context: Any

This is a code system defined at http://www.hl7.org/Special/committees/pher/index.cfm .

Summary

Defining URL: | http://terminology.hl7.org/CodeSystem/immunization-program-eligibility
Version: | 4.0.1
Name: | ImmunizationProgramEligibility

Title: | Immunization Program Eligibility
Definition: | The value set to instantiate this attribute should be drawn from a terminologically robust code system that consists of or contains concepts to support describing the patient's eligibility for a vaccination program. This value set is provided as a suggestive example.
Committee: | Public Health and Emergency Response Work Group
OID: | 2.16.840.1.113883.4.642.4.1099 (for OID based terminology systems)
Source Resource | XML / JSON

This Code system is used in the following value sets:

• ValueSet: Immunization Program Eligibility (The value set to instantiate this attribute should be drawn from a terminologically robust code system that consists of or contains concepts to support describing the patient's eligibility for a vaccination program. This value set is provided as a suggestive example.)

• ValueSet: Immunization Program Eligibility (The value set to instantiate this attribute should be drawn from a terminologically robust code system that consists of or contains concepts to support describing the patient's eligibility for a vaccination program. This value set is provided as a suggestive example.)

4.3.14.264.1 Content

4.3.14.264.2 Immunization Program Eligibility

The value set to instantiate this attribute should be drawn from a terminologically robust code system that consists of or contains concepts to support describing the patient's eligibility for a vaccination program. This value set is provided as a suggestive example.

This code system http://terminology.hl7.org/CodeSystem/immunization-program-eligibility defines the following codes:

Code | Display | Definition
ineligible | Not Eligible | The patient is not eligible for the funding program.
uninsured | Uninsured | The patient is eligible for the funding program because they are uninsured.

See the full registry of code systems defined as part of FHIR.

Explanation of the columns that may appear on this page:

Level | A few code lists that FHIR defines are hierarchical - each code is assigned a level. See Code System for further information.
Source | The source of the definition of the code (when the value set draws in codes defined elsewhere)
Code | The code (used as the code in the resource instance). If the code is in italics, this indicates that the code is not selectable ('Abstract')
Display | The display (used in the display element of a Coding). If there is no display, implementers should not simply display the code, but map the concept into their application
Definition | An explanation of the meaning of the concept
Comments | Additional notes about how to use the code

4.3.14.265 Code System http://hl7.org/fhir/udi-entry-type

URL: https://hl7.org/fhir/R4/codesystem-udi-entry-type.html
Orders and Observations Work Group | Maturity Level: 2 | Trial Use | Use Context: Any

This is a code system defined by the FHIR project.

Summary

Defining URL: | http://hl7.org/fhir/udi-entry-type
Version: | 4.0.1
Name: | UDIEntryType
Title: | UDIEntryType
Definition: | Codes to identify how UDI data was entered.
Committee: | Orders and Observations Work Group
OID: | 2.16.840.1.113883.4.642.4.212 (for OID based terminology systems)
Source Resource | XML / JSON

This Code system is used in the following value sets:

• ValueSet: UDIEntryType (Codes to identify how UDI data was entered.)

• ValueSet: UDIEntryType (Codes to identify how UDI data was entered.)

4.3.14.265.1 Content

4.3.14.265.2 UDIEntryType

Codes to identify how UDI data was entered.

This code system http://hl7.org/fhir/udi-entry-type defines the following codes:

Code | Display | Definition
barcode | Barcode | a barcodescanner captured the data from the device label.
rfid | RFID | An RFID chip reader captured the data from the device label.
manual | Manual | The data was read from the label by a person and manually entered. (e.g. via a keyboard).

card | Card | The data originated from a patient's implant card and was read by an operator.
self-reported | Self Reported | The data originated from a patient source and was not directly scanned or read from a label or card.
unknown | Unknown | The method of data capture has not been determined.

See the full registry of code systems defined as part of FHIR.

Explanation of the columns that may appear on this page:

Level | A few code lists that FHIR defines are hierarchical - each code is assigned a level. See Code System for further information.
Source | The source of the definition of the code (when the value set draws in codes defined elsewhere)
Code | The code (used as the code in the resource instance). If the code is in italics, this indicates that the code is not selectable ('Abstract')
Display | The display (used in the display element of a Coding). If there is no display, implementers should not simply display the code, but map the concept into their application
Definition | An explanation of the meaning of the concept
Comments | Additional notes about how to use the code

4.3.14.266 Code System http://hl7.org/fhir/ex-claimitemtype

URL: https://hl7.org/fhir/R4/codesystem-fm-itemtype.html
Vocabulary Work Group | Maturity Level: 0 | Informative | Use Context: Any

This is a code system defined by the FHIR project.

Summary

Defining URL: | http://hl7.org/fhir/ex-claimitemtype
Version: | 4.0.1
Name: | ClaimItemTypeCodes
Title: | Claim Item Type Codes
Definition: | This value set includes sample Item Type codes.
Committee: | ??
OID: | 2.16.840.1.113883.4.642.4.549 (for OID based terminology systems)
Copyright: | This is an example set.
Source Resource | XML / JSON

This Code system is used in the following value sets:

• ValueSet: Claim Item Type Codes (This value set includes sample Item Type codes.)
• ValueSet: Claim Item Type Codes (This value set includes sample Item Type codes.)

4.3.14.266.1 Content

4.3.14.266.2 Claim Item Type Codes

This value set includes sample Item Type codes.

Copyright Statement:

This is an example set.

This code system http://hl7.org/fhir/ex-claimitemtype defines the following codes:

Code | Display | Definition
group | Group | A group of products and/or Services, amount ar the summary or detail level products and services.
product | Product | A billed product line item.
service | Service | A billed service line item.

See the full registry of code systems defined as part of FHIR.

Explanation of the columns that may appear on this page:

Level | A few code lists that FHIR defines are hierarchical - each code is assigned a level. See Code System for further information.
Source | The source of the definition of the code (when the value set draws in codes defined elsewhere)
Code | The code (used as the code in the resource instance). If the code is in italics, this indicates that the code is not selectable ('Abstract')
Display | The display (used in the display element of a Coding). If there is no display, implementers should not simply display the code, but map the concept into their application
Definition | An explanation of the meaning of the concept
Comments | Additional notes about how to use the code

4.3.14.267 Code System http://hl7.org/fhir/consent-state-codes

URL: https://hl7.org/fhir/R4/codesystem-consent-state-codes.html
Community Based Collaborative Care Work Group | Maturity Level: 2 | Trial Use | Use Context: Any

This is a code system defined by the FHIR project.

Summary

Defining URL: | http://hl7.org/fhir/consent-state-codes
Version: | 4.0.1

Name: | ConsentState
Title: | ConsentState
Definition: | Indicates the state of the consent.
Committee: | Community Based Collaborative Care Work Group
OID: | 2.16.840.1.113883.4.642.4.756 (for OID based terminology systems)
Source Resource | XML / JSON

This Code system is used in the following value sets:

• ValueSet: ConsentState (Indicates the state of the consent.)

• ValueSet: ConsentState (Indicates the state of the consent.)

4.3.14.267.1 Content

4.3.14.267.2 ConsentState

Indicates the state of the consent.

This code system http://hl7.org/fhir/consent-state-codes defines the following codes:

Code | Display | Definition
draft | Pending | The consent is in development or awaiting use but is not yet intended to be acted upon.
proposed | Proposed | The consent has been proposed but not yet agreed to by all parties. The negotiation stage.
active | Active | The consent is to be followed and enforced.
rejected | Rejected | The consent has been rejected by one or more of the parties.
inactive | Inactive | The consent is terminated or replaced.
entered-in-error | Entered in Error | The consent was created wrongly (e.g. wrong patient) and should be ignored.

See the full registry of code systems defined as part of FHIR.

Explanation of the columns that may appear on this page:

Level | A few code lists that FHIR defines are hierarchical - each code is assigned a level. See Code System for further information.
Source | The source of the definition of the code (when the value set draws in codes defined elsewhere)
Code | The code (used as the code in the resource instance). If the code is in italics, this indicates that the code is not selectable ('Abstract')
Display | The display (used in the display element of a Coding). If there is no display, implementers should not simply display the code, but map the concept into their application
Definition | An explanation of the meaning of the concept
Comments | Additional notes about how to use the code

4.3.14.268 Code System http://hl7.org/fhir/address-type

URL: https://hl7.org/fhir/R4/codesystem-address-type.html
FHIR Infrastructure Work Group | Maturity Level: N | Normative (from v4.0.0) | Use Context: Any

This is a code system defined by the FHIR project.

Summary

Defining URL: | http://hl7.org/fhir/address-type
Version: | 4.0.1
Name: | AddressType
Title: | AddressType
Definition: | The type of an address (physical / postal).
Committee: | FHIR Infrastructure Work Group
OID: | 2.16.840.1.113883.4.642.4.70 (for OID based terminology systems)
Source Resource | XML / JSON

This Code system is used in the following value sets:

• ValueSet: AddressType (The type of an address (physical / postal).)

• ValueSet: AddressType (The type of an address (physical / postal).)

4.3.14.268.1 Content

4.3.14.268.2 AddressType

The type of an address (physical / postal).

This code system http://hl7.org/fhir/address-type defines the following codes:

Code | Display | Definition
postal | Postal | Mailing addresses - PO Boxes and care-of addresses.
physical | Physical | A physical address that can be visited.
both | Postal & Physical | An address that is both physical and postal.

See the full registry of code systems defined as part of FHIR.

Explanation of the columns that may appear on this page:

Level | A few code lists that FHIR defines are hierarchical - each code is assigned a level. See Code System for further information.
Source | The source of the definition of the code (when the value set draws in codes defined elsewhere)

Code | The code (used as the code in the resource instance). If the code is in italics, this indicates that the code is not selectable ('Abstract')
Display | The display (used in the display element of a Coding). If there is no display, implementers should not simply display the code, but map the concept into their application
Definition | An explanation of the meaning of the concept
Comments | Additional notes about how to use the code

4.3.14.269 Code System http://hl7.org/fhir/document-reference-status

URL: https://hl7.org/fhir/R4/codesystem-document-reference-status.html
Structured Documents Work Group | Maturity Level: 3 | Trial Use | Use Context: Any

This is a code system defined by the FHIR project.

Summary

Defining URL: | http://hl7.org/fhir/document-reference-status
Version: | 4.0.1
Name: | DocumentReferenceStatus
Title: | DocumentReferenceStatus
Definition: | The status of the document reference.
Committee: | Structured Documents Work Group
OID: | 2.16.840.1.113883.4.642.4.8 (for OID based terminology systems)
Source Resource | XML / JSON

This Code system is used in the following value sets:

• ValueSet: DocumentReferenceStatus (The status of the document reference.)
• ValueSet: DocumentReferenceStatus (The status of the document reference.)

4.3.14.269.1 Content

4.3.14.269.2 DocumentReferenceStatus

The status of the document reference.

This code system http://hl7.org/fhir/document-reference-status defines the following codes:

Code | Display | Definition
current | Current | This is the current reference for this document.
superseded | Superseded | This reference has been superseded by another reference.
entered-in-error | Entered in Error | This reference was created in error.

See the full registry of code systems defined as part of FHIR.

Explanation of the columns that may appear on this page:

Level | A few code lists that FHIR defines are hierarchical - each code is assigned a level. See Code System for further information.
Source | The source of the definition of the code (when the value set draws in codes defined elsewhere)
Code | The code (used as the code in the resource instance). If the code is in italics, this indicates that the code is not selectable ('Abstract')
Display | The display (used in the display element of a Coding). If there is no display, implementers should not simply display the code, but map the concept into their application
Definition | An explanation of the meaning of the concept
Comments | Additional notes about how to use the code

4.3.14.270 Code System http://hl7.org/fhir/eligibilityrequest-purpose

URL: https://hl7.org/fhir/R4/codesystem-eligibilityrequest-purpose.html
Financial Management Work Group | Maturity Level: 2 | Trial Use | Use Context: Any

This is a code system defined by the FHIR project.

Summary

Defining URL: | http://hl7.org/fhir/eligibilityrequest-purpose
Version: | 4.0.1
Name: | EligibilityRequestPurpose
Title: | EligibilityRequestPurpose
Definition: | A code specifying the types of information being requested.
Committee: | Financial Management Work Group
OID: | 2.16.840.1.113883.4.642.4.1183 (for OID based terminology systems)
Source Resource | XML / JSON

This Code system is used in the following value sets:

• ValueSet: EligibilityRequestPurpose (A code specifying the types of information being requested.)
• ValueSet: EligibilityRequestPurpose (A code specifying the types of information being requested.)

4.3.14.270.1 Content

4.3.14.270.2 EligibilityRequestPurpose

A code specifying the types of information being requested.

This code system http://hl7.org/fhir/eligibilityrequest-purpose defines the following codes:

Code | Display | Definition
auth-requirements | Coverage auth-requirements | The prior authorization requirements for the listed, or discovered if specified, converages for the categories of service and/or specifed biling codes are requested.
benefits | Coverage benefits | The plan benefits and optionally benefits consumed for the listed, or discovered if specified, converages are requested.
discovery | Coverage Discovery | The insurer is requested to report on any coverages which they are aware of in addition to any specifed.
validation | Coverage Validation | A check that the specified coverages are in-force is requested.

See the full registry of code systems defined as part of FHIR.

Explanation of the columns that may appear on this page:

Level | A few code lists that FHIR defines are hierarchical - each code is assigned a level. See Code System for further information.
Source | The source of the definition of the code (when the value set draws in codes defined elsewhere)
Code | The code (used as the code in the resource instance). If the code is in italics, this indicates that the code is not selectable ('Abstract')
Display | The display (used in the display element of a Coding). If there is no display, implementers should not simply display the code, but map the concept into their application
Definition | An explanation of the meaning of the concept
Comments | Additional notes about how to use the code

4.3.14.271 Code System http://hl7.org/fhir/type-derivation-rule

URL: https://hl7.org/fhir/R4/codesystem-type-derivation-rule.html
FHIR Infrastructure Work Group | Maturity Level: N | Normative (from v4.0.0) | Use Context: Any

| This page has been approved as part of an ANSI standard. See the Conformance Package for further details.

This is a code system defined by the FHIR project.

Summary

Defining URL: | http://hl7.org/fhir/type-derivation-rule
Version: | 4.0.1
Name: | TypeDerivationRule
Title: | TypeDerivationRule
Definition: | How a type relates to its baseDefinition.
Committee: | FHIR Infrastructure Work Group
OID: | 2.16.840.1.113883.4.642.4.674 (for OID based terminology systems)
Source Resource | XML / JSON

This Code system is used in the following value sets:

• ValueSet: TypeDerivationRule (How a type relates to its baseDefinition.)
• ValueSet: TypeDerivationRule (How a type relates to its baseDefinition.)

4.3.14.271.1 Content

4.3.14.271.2 TypeDerivationRule

How a type relates to its baseDefinition.

This code system http://hl7.org/fhir/type-derivation-rule defines the following codes:

Code | Display | Definition
specialization | Specialization | This definition defines a new type that adds additional elements to the base type.
constraint | Constraint | This definition adds additional rules to an existing concrete type.

See the full registry of code systems defined as part of FHIR.

Explanation of the columns that may appear on this page:

Level | A few code lists that FHIR defines are hierarchical - each code is assigned a level. See Code System for further information.
Source | The source of the definition of the code (when the value set draws in codes defined elsewhere)
Code | The code (used as the code in the resource instance). If the code is in italics, this indicates that the code is not selectable ('Abstract')
Display | The display (used in the display element of a Coding). If there is no display, implementers should not simply display the code, but map the concept into their application
Definition | An explanation of the meaning of the concept
Comments | Additional notes about how to use the code

4.3.14.272 Code System http://terminology.hl7.org/CodeSystem/ex-revenue-center

URL: https://hl7.org/fhir/R4/codesystem-ex-revenue-center.html
Financial Management Work Group | Maturity Level: 1 | Draft | Use Context: Any

This is a code system defined by the FHIR project.

Summary

Defining URL: | http://terminology.hl7.org/CodeSystem/ex-revenue-center
Version: | 4.0.1
Name: | ExampleRevenueCenterCodes
Title: | Example Revenue Center Codes
Definition: | This value set includes sample Revenue Center codes.
Committee: | Financial Management Work Group
OID: | 2.16.840.1.113883.4.642.4.1168 (for OID based terminology systems)
Copyright: | These codes have been appropriated from the UB04 code set owned and managed by the AHA . Users require a license from the AHA in order to use these codes. Note: the codes have been withdrawn in a later version
Source Resource | XML / JSON

This Code system is used in the following value sets:

• ValueSet: Example Revenue Center Codes (This value set includes sample Revenue Center codes.)
• ValueSet: Example Revenue Center Codes (This value set includes sample Revenue Center codes.)

4.3.14.272.1 Content

4.3.14.272.2 Example Revenue Center Codes

This value set includes sample Revenue Center codes.

Copyright Statement:

These codes have been appropriated from the UB04 code set owned and managed by the AHA . Users require a license from the AHA in order to use these codes. Note: the codes have been withdrawn in a later version

This code system http://terminology.hl7.org/CodeSystem/ex-revenue-center defines the following codes:

Code | Display | Definition
0370 | Anaesthesia | Anaesthesia.
0420 | Physical Therapy | Physical Therapy.
0421 | Physical Therapy - | Physical Therapy - visit charge.
0440 | Speech-Language Pathology | Speech-Language Pathology.
0441 | Speech-Language Pathology - Visit | Speech-Language Pathology- visit charge
0450 | Emergency Room | Emergency Room
0451 | Emergency Room - EM/EMTALA | Emergency Room - EM/EMTALA
0452 | Emergency Room - beyond EMTALA | Emergency Room - beyond EMTALA
0010 | Vision Clinic | Vision Clinic

See the full registry of code systems defined as part of FHIR.

Explanation of the columns that may appear on this page:

Level | A few code lists that FHIR defines are hierarchical - each code is assigned a level. See Code System for further information.
Source | The source of the definition of the code (when the value set draws in codes defined elsewhere)
Code | The code (used as the code in the resource instance). If the code is in italics, this indicates that the code is not selectable ('Abstract')
Display | The display (used in the display element of a Coding). If there is no display, implementers should not simply display the code, but map the concept into their application
Definition | An explanation of the meaning of the concept
Comments | Additional notes about how to use the code

4.3.14.273 Code System http://terminology.hl7.org/CodeSystem/device-status-reason

URL: https://hl7.org/fhir/R4/codesystem-device-status-reason.html
Orders and Observations Work Group | Maturity Level: 2 | Trial Use | Use Context: Any

This is a code system defined by the FHIR project.

Summary

Defining URL: | http://terminology.hl7.org/CodeSystem/device-status-reason
Version: | 4.0.1
Name: | FHIRDeviceStatusReason
Title: | FHIRDeviceStatusReason
Definition: | The availability status reason of the device.
Committee: | Orders and Observations Work Group
OID: | 2.16.840.1.113883.4.642.4.1082 (for OID based terminology systems)

Source Resource | XML / JSON

This Code system is used in the following value sets:

• ValueSet: FHIRDeviceStatusReason (The availability status reason of the device.)

• ValueSet: FHIRDeviceStatusReason (The availability status reason of the device.)

4.3.14.273.1 Content

4.3.14.273.2 FHIRDeviceStatusReason

The availability status reason of the device.

This code system http://terminology.hl7.org/CodeSystem/device-status-reason defines the following codes:

Code | Display | Definition
online | Online | The device is off.
paused | Paused | The device is paused.
standby | Standby | The device is ready but not actively operating.
offline | Offline | The device is offline.
not-ready | Not Ready | The device is not ready.
transduc-discon | Transducer Disconnected | The device transducer is disconnected.
hw-discon | Hardware Disconnected | The device hardware is disconnected.
off | Off | The device is off.

See the full registry of code systems defined as part of FHIR.

Explanation of the columns that may appear on this page:

Level | A few code lists that FHIR defines are hierarchical - each code is assigned a level. See Code System for further information.
Source | The source of the definition of the code (when the value set draws in codes defined elsewhere)
Code | The code (used as the code in the resource instance). If the code is in italics, this indicates that the code is not selectable ('Abstract')
Display | The display (used in the display element of a Coding). If there is no display, implementers should not simply display the code, but map the concept into their application
Definition | An explanation of the meaning of the concept
Comments | Additional notes about how to use the code

4.3.14.274 Code System http://hl7.org/fhir/assert-response-code-types

URL: https://hl7.org/fhir/R4/codesystem-assert-response-code-types.html
FHIR Infrastructure Work Group | Maturity Level: 2 | Trial Use | Use Context: Any

This is a code system defined by the FHIR project.

Summary

Defining URL: | http://hl7.org/fhir/assert-response-code-types
Version: | 4.0.1
Name: | AssertionResponseTypes
Title: | AssertionResponseTypes
Definition: | The type of response code to use for assertion.
Committee: | FHIR Infrastructure Work Group
OID: | 2.16.840.1.113883.4.642.4.711 (for OID based terminology systems)
Source Resource | XML / JSON

This Code system is used in the following value sets:

• ValueSet: AssertionResponseTypes (The type of response code to use for assertion.)

• ValueSet: AssertionResponseTypes (The type of response code to use for assertion.)

4.3.14.274.1 Content

4.3.14.274.2 AssertionResponseTypes

The type of response code to use for assertion.

This code system http://hl7.org/fhir/assert-response-code-types defines the following codes:

Code | Display | Definition
okay | okay | Response code is 200.
created | created | Response code is 201.
noContent | noContent | Response code is 204.
notModified | notModified | Response code is 304.
bad | bad | Response code is 400.
forbidden | forbidden | Response code is 403.
notFound | notFound | Response code is 404.
methodNotAllowed | methodNotAllowed | Response code is 405.
conflict | conflict | Response code is 409.

gone | gone | Response code is 410.
preconditionFailed | preconditionFailed | Response code is 412.
unprocessable | unprocessable | Response code is 422.

See the full registry of code systems defined as part of FHIR.

Explanation of the columns that may appear on this page:

Level | A few code lists that FHIR defines are hierarchical - each code is assigned a level. See Code System for further information.
Source | The source of the definition of the code (when the value set draws in codes defined elsewhere)
Code | The code (used as the code in the resource instance). If the code is in italics, this indicates that the code is not selectable ('Abstract')
Display | The display (used in the display element of a Coding). If there is no display, implementers should not simply display the code, but map the concept into their application
Definition | An explanation of the meaning of the concept
Comments | Additional notes about how to use the code

4.3.14.275 Code System http://terminology.hl7.org/CodeSystem/allerg-intol-substance-exp-risk

URL: https://hl7.org/fhir/R4/codesystem-allerg-intol-substance-exp-risk.html
Vocabulary Work Group | Maturity Level: 0 | Informative | Use Context: Any

This is a code system defined by the FHIR project.

Summary

Defining URL: | http://terminology.hl7.org/CodeSystem/allerg-intol-substance-exp-risk
Version: | 4.0.1
Name: | AllergyIntoleranceSubstanceExposureRisk
Title: | AllergyIntoleranceSubstanceExposureRisk
Definition: | The risk of an adverse reaction (allergy or intolerance) for this patient upon exposure to the substance (including pharmaceutical products).
Committee: | ??
OID: | 2.16.840.1.113883.4.642.4.1275 (for OID based terminology systems)
Source Resource | XML / JSON

This Code system is used in the following value sets:

• ValueSet: AllergyIntoleranceSubstanceExposureRisk (The risk of an adverse reaction (allergy or intolerance) for this patient upon exposure to the substance (including pharmaceutical products).)

• ValueSet: AllergyIntoleranceSubstanceExposureRisk (The risk of an adverse reaction (allergy or intolerance) for this patient upon exposure to the substance (including pharmaceutical products).)

4.3.14.275.1 Content

4.3.14.275.2 AllergyIntoleranceSubstanceExposureRisk

The risk of an adverse reaction (allergy or intolerance) for this patient upon exposure to the substance (including pharmaceutical products).

This code system http://terminology.hl7.org/CodeSystem/allerg-intol-substance-exp-risk defines the following codes:

Code | Display | Definition
known-reaction-risk | Known Reaction Risk | Known risk of allergy or intolerance reaction upon exposure to the specified substance.
no-known-reaction-risk | No Known Reaction Risk | No known risk of allergy or intolerance reaction upon exposure to the specified substance.

See the full registry of code systems defined as part of FHIR.

Explanation of the columns that may appear on this page:

Level | A few code lists that FHIR defines are hierarchical - each code is assigned a level. See Code System for further information.
Source | The source of the definition of the code (when the value set draws in codes defined elsewhere)
Code | The code (used as the code in the resource instance). If the code is in italics, this indicates that the code is not selectable ('Abstract')
Display | The display (used in the display element of a Coding). If there is no display, implementers should not simply display the code, but map the concept into their application
Definition | An explanation of the meaning of the concept
Comments | Additional notes about how to use the code

4.3.14.276 Code System http://hl7.org/fhir/contract-expiration-type

URL: https://hl7.org/fhir/R4/codesystem-contract-expiration-type.html
Financial Management Work Group | Maturity Level: 1 | Draft | Use Context: Any

This is a code system defined by the FHIR project.

Summary

Defining URL: | http://hl7.org/fhir/contract-expiration-type
Version: | 4.0.1
Name: | ContractResourceExpirationTypeCodes
Title: | Contract Resource Expiration Type codes
Definition: | This value set contract specific codes for status.
Committee: | Financial Management Work Group
OID: | 2.16.840.1.113883.4.642.4.1215 (for OID based terminology systems)
Copyright: | HL7 International.
Source Resource | XML / JSON

This Code system is used in the following value sets:

• ValueSet: Contract Resource Expiration Type codes (This value set contract specific codes for status.)

• ValueSet: Contract Resource Expiration Type codes (This value set contract specific codes for status.)

4.3.14.276.1 Content

Each definition includes usage notes explaining the precedence order in contract lifecycle - i.e., while only some stages are required, the order in which they may occur is deterministic; and a map to comparable FHIR and v.3 status codes. It follows guidance about use of status codes in FHIR at http://build.fhir.org/sc.html.

4.3.14.276.2 Contract Resource Expiration Type codes

This value set contract specific codes for status.

Copyright Statement:

HL7 International.

This code system http://hl7.org/fhir/contract-expiration-type defines the following codes:

Code | Display | Definition
breach | Breach | To be completed

See the full registry of code systems defined as part of FHIR.

Explanation of the columns that may appear on this page:

Level | A few code lists that FHIR defines are hierarchical - each code is assigned a level. See Code System for further information.
Source | The source of the definition of the code (when the value set draws in codes defined elsewhere)
Code | The code (used as the code in the resource instance). If the code is in italics, this indicates that the code is not selectable ('Abstract')
Display | The display (used in the display element of a Coding). If there is no display, implementers should not simply display the code, but map the concept into their application
Definition | An explanation of the meaning of the concept
Comments | Additional notes about how to use the code

4.3.14.277 Code System http://hl7.org/fhir/report-participant-type

URL: https://hl7.org/fhir/R4/codesystem-report-participant-type.html
FHIR Infrastructure Work Group | Maturity Level: 0 | Trial Use | Use Context: Any

This is a code system defined by the FHIR project.

Summary

Defining URL: | http://hl7.org/fhir/report-participant-type
Version: | 4.0.1
Name: | TestReportParticipantType
Title: | TestReportParticipantType
Definition: | The type of participant.
Committee: | FHIR Infrastructure Work Group
OID: | 2.16.840.1.113883.4.642.4.723 (for OID based terminology systems)
Source Resource | XML / JSON

This Code system is used in the following value sets:

• ValueSet: TestReportParticipantType (The type of participant.)

• ValueSet: TestReportParticipantType (The type of participant.)

4.3.14.277.1 Content

4.3.14.277.2 TestReportParticipantType

The type of participant.

This code system http://hl7.org/fhir/report-participant-type defines the following codes:

Code | Display | Definition
test-engine | Test Engine | The test execution engine.
client | Client | A FHIR Client.
server | Server | A FHIR Server.

See the full registry of code systems defined as part of FHIR.

Explanation of the columns that may appear on this page:

Level | A few code lists that FHIR defines are hierarchical - each code is assigned a level. See Code System for further information.
Source | The source of the definition of the code (when the value set draws in codes defined elsewhere)
Code | The code (used as the code in the resource instance). If the code is in italics, this indicates that the code is not selectable ('Abstract')
Display | The display (used in the display element of a Coding). If there is no display, implementers should not simply display the code, but map the concept into their application
Definition | An explanation of the meaning of the concept
Comments | Additional notes about how to use the code

4.3.14.278 Code System http://hl7.org/fhir/identifier-use

URL: https://hl7.org/fhir/R4/codesystem-identifier-use.html
FHIR Infrastructure Work Group | Maturity Level: N | Normative (from v4.0.0) | Use Context: Any

This is a code system defined by the FHIR project.

Summary

Defining URL: | http://hl7.org/fhir/identifier-use
Version: | 4.0.1
Name: | IdentifierUse
Title: | IdentifierUse
Definition: | Identifies the purpose for this identifier, if known .
Committee: | FHIR Infrastructure Work Group
OID: | 2.16.840.1.113883.4.642.4.58 (for OID based terminology systems)
Source Resource | XML / JSON

This Code system is used in the following value sets:

• ValueSet: IdentifierUse (Identifies the purpose for this identifier, if known .)
• ValueSet: IdentifierUse (Identifies the purpose for this identifier, if known .)

4.3.14.278.1 Content

4.3.14.278.2 IdentifierUse

Identifies the purpose for this identifier, if known .

This code system http://hl7.org/fhir/identifier-use defines the following codes:

Code | Display | Definition
usual | Usual | The identifier recommended for display and use in real-world interactions.
official | Official | The identifier considered to be most trusted for the identification of this item. Sometimes also known as "primary" and "main". The determination of "official" is subjective and implementation guides often provide additional guidelines for use.
temp | Temp | A temporary identifier.
secondary | Secondary | An identifier that was assigned in secondary use - it serves to identify the object in a relative context, but cannot be consistently assigned to the same object again in a different context.
old | Old | The identifier id no longer considered valid, but may be relevant for search purposes. E.g. Changes to identifier schemes, account merges, etc.

See the full registry of code systems defined as part of FHIR.

Explanation of the columns that may appear on this page:

Level | A few code lists that FHIR defines are hierarchical - each code is assigned a level. See Code System for further information.
Source | The source of the definition of the code (when the value set draws in codes defined elsewhere)
Code | The code (used as the code in the resource instance). If the code is in italics, this indicates that the code is not selectable ('Abstract')
Display | The display (used in the display element of a Coding). If there is no display, implementers should not simply display the code, but map the concept into their application
Definition | An explanation of the meaning of the concept
Comments | Additional notes about how to use the code

4.3.14.279 Code System http://terminology.hl7.org/CodeSystem/benefit-type

URL: https://hl7.org/fhir/R4/codesystem-benefit-type.html
Financial Management Work Group | Maturity Level: 1 | Draft | Use Context: Any

This is a code system defined by the FHIR project.

Summary

Defining URL: | http://terminology.hl7.org/CodeSystem/benefit-type
Version: | 4.0.1
Name: | BenefitTypeCodes
Title: | Benefit Type Codes
Definition: | This value set includes a smattering of Benefit type codes.
Committee: | Financial Management Work Group
OID: | 2.16.840.1.113883.4.642.4.1176 (for OID based terminology systems)
Copyright: | This is an example set.
Source Resource | XML / JSON

This Code system is used in the following value sets:

• ValueSet: Benefit Type Codes (This value set includes a smattering of Benefit type codes.)

• ValueSet: Benefit Type Codes (This value set includes a smattering of Benefit type codes.)

4.3.14.279.1 Content

4.3.14.279.2 Benefit Type Codes

This value set includes a smattering of Benefit type codes.

Copyright Statement:

This is an example set.

This code system http://terminology.hl7.org/CodeSystem/benefit-type defines the following codes:

Code | Display | Definition
benefit | Benefit | Maximum benefit allowable.
deductible | Deductible | Cost to be incurred before benefits are applied
visit | Visit | Service visit
room | Room | Type of room
copay | Copayment per service | Copayment per service
copay-percent | Copayment Percent per service | Copayment percentage per service
copay-maximum | Copayment maximum per service | Copayment maximum per service
vision-exam | Vision Exam | Vision Exam
vision-glasses | Vision Glasses | Frames and lenses
vision-contacts | Vision Contacts Coverage | Contact Lenses
medical-primarycare | Medical Primary Health Coverage | Medical Primary Health Coverage
pharmacy-dispense | Pharmacy Dispense Coverage | Pharmacy Dispense Coverage

See the full registry of code systems defined as part of FHIR.

Explanation of the columns that may appear on this page:

Level | A few code lists that FHIR defines are hierarchical - each code is assigned a level. See Code System for further information.
Source | The source of the definition of the code (when the value set draws in codes defined elsewhere)
Code | The code (used as the code in the resource instance). If the code is in italics, this indicates that the code is not selectable ('Abstract')
Display | The display (used in the display element of a Coding). If there is no display, implementers should not simply display the code, but map the concept into their application
Definition | An explanation of the meaning of the concept
Comments | Additional notes about how to use the code

4.3.14.280 Code System http://hl7.org/fhir/search-comparator

URL: https://hl7.org/fhir/R4/codesystem-search-comparator.html
FHIR Infrastructure Work Group | Maturity Level: 3 | Trial Use | Use Context: Any

This is a code system defined by the FHIR project.

Summary

Defining URL: | http://hl7.org/fhir/search-comparator
Version: | 4.0.1
Name: | SearchComparator
Title: | SearchComparator
Definition: | What Search Comparator Codes are supported in search.
Committee: | FHIR Infrastructure Work Group
OID: | 2.16.840.1.113883.4.642.4.638 (for OID based terminology systems)
Source Resource | XML / JSON

This Code system is used in the following value sets:

• ValueSet: SearchComparator (What Search Comparator Codes are supported in search.)

• ValueSet: SearchComparator (What Search Comparator Codes are supported in search.)

4.3.14.280.1 Content

4.3.14.280.2 SearchComparator

What Search Comparator Codes are supported in search.

This code system http://hl7.org/fhir/search-comparator defines the following codes:

Code | Display | Definition
eq | Equals | the value for the parameter in the resource is equal to the provided value.
ne | Not Equals | the value for the parameter in the resource is not equal to the provided value.
gt | Greater Than | the value for the parameter in the resource is greater than the provided value.
lt | Less Than | the value for the parameter in the resource is less than the provided value.
ge | Greater or Equals | the value for the parameter in the resource is greater or equal to the provided value.
le | Less of Equal | the value for the parameter in the resource is less or equal to the provided value.
sa | Starts After | the value for the parameter in the resource starts after the provided value.
eb | Ends Before | the value for the parameter in the resource ends before the provided value.
ap | Approximately | the value for the parameter in the resource is approximately the same to the provided value.

See the full registry of code systems defined as part of FHIR.

Explanation of the columns that may appear on this page:

Level | A few code lists that FHIR defines are hierarchical - each code is assigned a level. See Code System for further information.
Source | The source of the definition of the code (when the value set draws in codes defined elsewhere)
Code | The code (used as the code in the resource instance). If the code is in italics, this indicates that the code is not selectable ('Abstract')
Display | The display (used in the display element of a Coding). If there is no display, implementers should not simply display the code, but map the concept into their application
Definition | An explanation of the meaning of the concept
Comments | Additional notes about how to use the code

4.3.14.281 Code System http://hl7.org/fhir/strand-type

URL: https://hl7.org/fhir/R4/codesystem-strand-type.html
Clinical Genomics Work Group | Maturity Level: 1 | Trial Use | Use Context: Any

This is a code system defined by the FHIR project.

Summary

Defining URL: | http://hl7.org/fhir/strand-type
Version: | 4.0.1
Name: | strandType
Title: | strandType
Definition: | Type for strand.
Committee: | Clinical Genomics Work Group
OID: | 2.16.840.1.113883.4.642.4.986 (for OID based terminology systems)
Source Resource | XML / JSON

This Code system is used in the following value sets:

• ValueSet: strandType (Type for strand.)

• ValueSet: strandType (Type for strand.)

4.3.14.281.1 Content

4.3.14.281.2 strandType

Type for strand.

This code system http://hl7.org/fhir/strand-type defines the following codes:

Code | Display | Definition
watson | Watson strand of referenceSeq | Watson strand of reference sequence.
crick | Crick strand of referenceSeq | Crick strand of reference sequence.

See the full registry of code systems defined as part of FHIR.

Explanation of the columns that may appear on this page:

Level | A few code lists that FHIR defines are hierarchical - each code is assigned a level. See Code System for further information.
Source | The source of the definition of the code (when the value set draws in codes defined elsewhere)
Code | The code (used as the code in the resource instance). If the code is in italics, this indicates that the code is not selectable ('Abstract')
Display | The display (used in the display element of a Coding). If there is no display, implementers should not simply display the code, but map the concept into their application
Definition | An explanation of the meaning of the concept
Comments | Additional notes about how to use the code

4.3.14.282 Code System http://terminology.hl7.org/CodeSystem/rejection-criteria

URL: https://hl7.org/fhir/R4/codesystem-rejection-criteria.html
Orders and Observations Work Group | Maturity Level: 1 | Draft | Use Context: Any

This is a code system defined by the FHIR project.

Summary

Defining URL: | http://terminology.hl7.org/CodeSystem/rejection-criteria
Version: | 4.0.1
Name: | RejectionCriterion
Title: | RejectionCriterion
Definition: | Criterion for rejection of the specimen by laboratory.
Committee: | Orders and Observations Work Group
OID: | 2.16.840.1.113883.4.642.4.1260 (for OID based terminology systems)
Source Resource | XML / JSON

This Code system is used in the following value sets:

• ValueSet: RejectionCriterion (Criterion for rejection of the specimen by laboratory.)

• ValueSet: RejectionCriterion (Criterion for rejection of the specimen by laboratory.)

4.3.14.282.1 Content

4.3.14.282.2 RejectionCriterion

Criterion for rejection of the specimen by laboratory.

This code system http://terminology.hl7.org/CodeSystem/rejection-criteria defines the following codes:

Code | Display | Definition
hemolized | hemolized specimen | blood specimen hemolized.
insufficient | insufficient specimen volume | insufficient quantity of specimen.
broken | broken specimen container | specimen container broken.
clotted | specimen clotted | specimen clotted.
wrong-temperature | specimen temperature inappropriate | specimen temperature inappropriate.

See the full registry of code systems defined as part of FHIR.

Explanation of the columns that may appear on this page:

Level | A few code lists that FHIR defines are hierarchical - each code is assigned a level. See Code System for further information.
Source | The source of the definition of the code (when the value set draws in codes defined elsewhere)
Code | The code (used as the code in the resource instance). If the code is in italics, this indicates that the code is not selectable ('Abstract')
Display | The display (used in the display element of a Coding). If there is no display, implementers should not simply display the code, but map the concept into their application
Definition | An explanation of the meaning of the concept
Comments | Additional notes about how to use the code

4.3.14.283 Code System http://hl7.org/fhir/detectedissue-severity

URL: https://hl7.org/fhir/R4/codesystem-detectedissue-severity.html
Clinical Decision Support Work Group | Maturity Level: 1 | Trial Use | Use Context: Any

This is a code system defined by the FHIR project.

Summary

Defining URL: | http://hl7.org/fhir/detectedissue-severity
Version: | 4.0.1
Name: | DetectedIssueSeverity
Title: | DetectedIssueSeverity
Definition: | Indicates the potential degree of impact of the identified issue on the patient.
Committee: | Clinical Decision Support Work Group
OID: | 2.16.840.1.113883.4.642.4.207 (for OID based terminology systems)
Source Resource | XML / JSON

This Code system is used in the following value sets:

• ValueSet: DetectedIssueSeverity (Indicates the potential degree of impact of the identified issue on the patient.)

• ValueSet: DetectedIssueSeverity (Indicates the potential degree of impact of the identified issue on the patient.)

4.3.14.283.1 Content

4.3.14.283.2 DetectedIssueSeverity

Indicates the potential degree of impact of the identified issue on the patient.

This code system http://hl7.org/fhir/detectedissue-severity defines the following codes:

Code | Display | Definition
high | High | Indicates the issue may be life-threatening or has the potential to cause permanent injury.
moderate | Moderate | Indicates the issue may result in noticeable adverse consequences but is unlikely to be life-threatening or cause permanent injury.
low | Low | Indicates the issue may result in some adverse consequences but is unlikely to substantially affect the situation of the subject.

See the full registry of code systems defined as part of FHIR.

Explanation of the columns that may appear on this page:

Level | A few code lists that FHIR defines are hierarchical - each code is assigned a level. See Code System for further information.
Source | The source of the definition of the code (when the value set draws in codes defined elsewhere)
Code | The code (used as the code in the resource instance). If the code is in italics, this indicates that the code is not selectable ('Abstract')
Display | The display (used in the display element of a Coding). If there is no display, implementers should not simply display the code, but map the concept into their application
Definition | An explanation of the meaning of the concept
Comments | Additional notes about how to use the code

4.3.14.284 Code System http://terminology.hl7.org/CodeSystem/hl7-work-group

URL: https://hl7.org/fhir/R4/codesystem-hl7-work-group.html
Vocabulary Work Group | Maturity Level: 0 | Informative | Use Context: Any

This is a code system defined by the FHIR project.

Summary

Defining URL: | http://terminology.hl7.org/CodeSystem/hl7-work-group
Version: | 4.0.1
Name: | HL7Workgroup
Title: | HL7Workgroup
Definition: | An HL7 administrative unit that owns artifacts in the FHIR specification.
Committee: | ??
OID: | 2.16.840.1.113883.4.642.4.1277 (for OID based terminology systems)
Source Resource | XML / JSON

This Code system is used in the following value sets:

• ValueSet: HL7Workgroup (An HL7 administrative unit that owns artifacts in the FHIR specification.)

• ValueSet: HL7Workgroup (An HL7 administrative unit that owns artifacts in the FHIR specification.)

4.3.14.284.1 Content

4.3.14.284.2 HL7Workgroup

An HL7 administrative unit that owns artifacts in the FHIR specification.

This code system http://terminology.hl7.org/CodeSystem/hl7-work-group defines the following codes:

Code | Display | Definition
cbcc | Community Based Collaborative Care | Community Based Collaborative Care (http://www.hl7.org/Special/committees/cbcc/index.cfm).
cds | Clinical Decision Support | Clinical Decision Support (http://www.hl7.org/Special/committees/dss/index.cfm).
cqi | Clinical Quality Information | Clinical Quality Information (http://www.hl7.org/Special/committees/cqi/index.cfm).
cg | Clinical Genomics | Clinical Genomics (http://www.hl7.org/Special/committees/clingenomics/index.cfm).
dev | Health Care Devices | Health Care Devices (http://www.hl7.org/Special/committees/healthcaredevices/index.cfm).
ehr | Electronic Health Records | Electronic Health Records (http://www.hl7.org/special/committees/ehr/index.cfm).
fhir | FHIR Infrastructure | FHIR Infrastructure (http://www.hl7.org/Special/committees/fiwg/index.cfm).
fm | Financial Management | Financial Management (http://www.hl7.org/Special/committees/fm/index.cfm).
hsi | Health Standards Integration | Health Standards Integration (http://www.hl7.org/Special/committees/hsi/index.cfm).
ii | Imaging Integration | Imaging Integration (http://www.hl7.org/Special/committees/imagemgt/index.cfm).
inm | Infrastructure And Messaging | Infrastructure And Messaging (http://www.hl7.org/special/committees/inm/index.cfm).
its | Implementable Technology Specifications | Implementable Technology Specifications (http://www.hl7.org/special/committees/xml/index.cfm).
mnm | Modeling and Methodology | Modeling and Methodology (http://www.hl7.org/Special/committees/mnm/index.cfm).
oo | Orders and Observations | Orders and Observations (http://www.hl7.org/Special/committees/orders/index.cfm).
pa | Patient Administration | Patient Administration (http://www.hl7.org/Special/committees/pafm/index.cfm).
pc | Patient Care | Patient Care (http://www.hl7.org/Special/committees/patientcare/index.cfm).
pher | Public Health and Emergency Response | Public Health and Emergency Response (http://www.hl7.org/Special/committees/pher/index.cfm).
phx | Pharmacy | Pharmacy (http://www.hl7.org/Special/committees/medication/index.cfm).
brr | Biomedical Research and Regulation | Biomedical Research and Regulation (http://www.hl7.org/Special/committees/rcrim/index.cfm).
sd | Structured Documents | Structured Documents (http://www.hl7.org/Special/committees/structure/index.cfm).

sec | Security | Security (http://www.hl7.org/Special/committees/secure/index.cfm).
us | US Realm Taskforce | US Realm Taskforce (http://www.hl7.org/Special/committees/usrealm/index.cfm).
vocab | Vocabulary | Vocabulary (http://www.hl7.org/Special/committees/Vocab/index.cfm).
aid | Application Implementation and Design | Application Implementation and Design (http://www.hl7.org/Special/committees/java/index.cfm).

See the full registry of code systems defined as part of FHIR.

Explanation of the columns that may appear on this page:

Level | A few code lists that FHIR defines are hierarchical - each code is assigned a level. See Code System for further information.
Source | The source of the definition of the code (when the value set draws in codes defined elsewhere)
Code | The code (used as the code in the resource instance). If the code is in italics, this indicates that the code is not selectable ('Abstract')
Display | The display (used in the display element of a Coding). If there is no display, implementers should not simply display the code, but map the concept into their application
Definition | An explanation of the meaning of the concept
Comments | Additional notes about how to use the code

4.3.14.285 Code System http://terminology.hl7.org/CodeSystem/endpoint-connection-type

URL: https://hl7.org/fhir/R4/codesystem-endpoint-connection-type.html
Patient Administration Work Group | Maturity Level: 2 | Trial Use | Use Context: Any

This is a code system defined by the FHIR project.

Summary

Defining URL: | http://terminology.hl7.org/CodeSystem/endpoint-connection-type
Version: | 4.0.1
Name: | EndpointConnectionType
Title: | Endpoint Connection Type
Definition: | This is an example value set defined by the FHIR project, that could be used to represent possible connection type profile values.
Committee: | Patient Administration Work Group
OID: | 2.16.840.1.113883.4.642.4.1140 (for OID based terminology systems)
Copyright: | Some content from IHE® Copyright © 2015 IHE International, Inc. This content is from the IHE Technical Frameworks and Supplements, available for free download and use at http://www.ihe.net/Technical_Frameworks/
Source Resource | XML / JSON

This Code system is used in the following value sets:

• ValueSet: Endpoint Connection Type (This is an example value set defined by the FHIR project, that could be used to represent possible connection type profile values.)

• ValueSet: Endpoint Connection Type (This is an example value set defined by the FHIR project, that could be used to represent possible connection type profile values.)

4.3.14.285.1 Content

4.3.14.285.2 Endpoint Connection Type

This is an example value set defined by the FHIR project, that could be used to represent possible connection type profile values.

Copyright Statement:

Some content from IHE® Copyright © 2015 IHE International, Inc. This content is from the IHE Technical Frameworks and Supplements, available for free download and use at http://www.ihe.net/Technical_Frameworks/

This code system http://terminology.hl7.org/CodeSystem/endpoint-connection-type defines the following codes:

Code | Display | Definition
ihe-xcpd | IHE XCPD | IHE Cross Community Patient Discovery Profile (XCPD) - http://wiki.ihe.net/index.php/Cross-Community_Patient_Discovery
ihe-xca | IHE XCA | IHE Cross Community Access Profile (XCA) - http://wiki.ihe.net/index.php/Cross-Community_Access
ihe-xdr | IHE XDR | IHE Cross-Enterprise Document Reliable Exchange (XDR) - http://wiki.ihe.net/index.php/Cross-enterprise_Document_Reliable_Interchange
ihe-xds | IHE XDS | IHE Cross-Enterprise Document Sharing (XDS) - http://wiki.ihe.net/index.php/Cross-Enterprise_Document_Sharing
ihe-iid | IHE IID | IHE Invoke Image Display (IID) - http://wiki.ihe.net/index.php/Invoke_Image_Display
dicom-wado-rs | DICOM WADO-RS | DICOMweb RESTful Image Retrieve - http://dicom.nema.org/medical/dicom/current/output/chtml/part18/sect_6.5.html
dicom-qido-rs | DICOM QIDO-RS | DICOMweb RESTful Image query - http://dicom.nema.org/medical/dicom/current/output/chtml/part18/sect_6.7.html
dicom-stow-rs | DICOM STOW-RS | DICOMweb RESTful image sending and storage - http://dicom.nema.org/medical/dicom/current/output/chtml/part18/sect_6.6.html

dicom-wado-uri | DICOM WADO-URI | DICOMweb Image Retrieve - http://dicom.nema.org/dicom/2013/output/chtml/part18/sect_6.3.html
hl7-fhir-rest | HL7 FHIR | Interact with the server interface using FHIR's RESTful interface. For details on its version/capabilities you should connect the value in Endpoint.address and retrieve the FHIR CapabilityStatement.
hl7-fhir-msg | HL7 FHIR Messaging | Use the servers FHIR Messaging interface. Details can be found on the messaging.html page in the FHIR Specification. The FHIR server's base address is specified in the Endpoint.address property.
hl7v2-mllp | HL7 v2 MLLP | HL7v2 messages over an LLP TCP connection
secure-email | Secure email | Email delivery using a digital certificate to encrypt the content using the public key, receiver must have the private key to decrypt the content
direct-project | Direct Project | Direct Project information - http://wiki.directproject.org/

See the full registry of code systems defined as part of FHIR.

Explanation of the columns that may appear on this page:

Level | A few code lists that FHIR defines are hierarchical - each code is assigned a level. See Code System for further information.
Source | The source of the definition of the code (when the value set draws in codes defined elsewhere)
Code | The code (used as the code in the resource instance). If the code is in italics, this indicates that the code is not selectable ('Abstract')
Display | The display (used in the display element of a Coding). If there is no display, implementers should not simply display the code, but map the concept into their application
Definition | An explanation of the meaning of the concept
Comments | Additional notes about how to use the code

4.3.14.286 Code System http://hl7.org/fhir/chargeitem-status

URL: https://hl7.org/fhir/R4/codesystem-chargeitem-status.html
Patient Administration Work Group | Maturity Level: 0 | Trial Use | Use Context: Any

This is a code system defined by the FHIR project.

Summary

Defining URL: | http://hl7.org/fhir/chargeitem-status
Version: | 4.0.1
Name: | ChargeItemStatus
Title: | ChargeItemStatus
Definition: | Codes identifying the lifecycle stage of a ChargeItem.
Committee: | Patient Administration Work Group
OID: | 2.16.840.1.113883.4.642.4.847 (for OID based terminology systems)
Source Resource | XML / JSON

This Code system is used in the following value sets:

• ValueSet: ChargeItemStatus (Codes identifying the lifecycle stage of a ChargeItem.)
• ValueSet: ChargeItemStatus (Codes identifying the lifecycle stage of a ChargeItem.)

4.3.14.286.1 Content

4.3.14.286.2 ChargeItemStatus

Codes identifying the lifecycle stage of a ChargeItem.

This code system http://hl7.org/fhir/chargeitem-status defines the following codes:

Code | Display | Definition
planned | Planned | The charge item has been entered, but the charged service is not yet complete, so it shall not be billed yet but might be used in the context of pre-authorization.
billable | Billable | The charge item is ready for billing.
not-billable | Not billable | The charge item has been determined to be not billable (e.g. due to rules associated with the billing code).
aborted | Aborted | The processing of the charge was aborted.
billed | Billed | The charge item has been billed (e.g. a billing engine has generated financial transactions by applying the associated ruled for the charge item to the context of the Encounter, and placed them into Claims/Invoices.
entered-in-error | Entered in Error | The charge item has been entered in error and should not be processed for billing.
unknown | Unknown | The authoring system does not know which of the status values currently applies for this charge item Note: This concept is not to be used for "other" - one of the listed statuses is presumed to apply, it's just not known which one.

See the full registry of code systems defined as part of FHIR.

Explanation of the columns that may appear on this page:

Level | A few code lists that FHIR defines are hierarchical - each code is assigned a level. See Code System for further information.
Source | The source of the definition of the code (when the value set draws in codes defined elsewhere)
Code | The code (used as the code in the resource instance). If the code is in italics, this indicates that the code is not selectable ('Abstract')
Display | The display (used in the display element of a Coding). If there is no display, implementers should not simply display the code, but map the concept into their application
Definition | An explanation of the meaning of the concept
Comments | Additional notes about how to use the code

4.3.14.287 Code System http://terminology.hl7.org/CodeSystem/research-study-prim-purp-type

URL: https://hl7.org/fhir/R4/codesystem-research-study-prim-purp-type.html
Biomedical Research and Regulation Work Group | Maturity Level: 1 | Trial Use | Use Context: Any

This is a code system defined by the FHIR project.

Summary

Defining URL: | http://terminology.hl7.org/CodeSystem/research-study-prim-purp-type
Version: | 4.0.1
Name: | ResearchStudyPrimaryPurposeType
Title: | ResearchStudyPrimaryPurposeType
Definition: | Codes for the main intent of the study.
Committee: | Biomedical Research and Regulation Work Group
OID: | 2.16.840.1.113883.4.642.4.1250 (for OID based terminology systems)
Source Resource | XML / JSON

This Code system is used in the following value sets:

• ValueSet: ResearchStudyPrimaryPurposeType (Codes for the main intent of the study.)
• ValueSet: ResearchStudyPrimaryPurposeType (Codes for the main intent of the study.)

4.3.14.287.1 Content

4.3.14.287.2 ResearchStudyPrimaryPurposeType

Codes for the main intent of the study.

This code system http://terminology.hl7.org/CodeSystem/research-study-prim-purp-type defines the following codes:

Code | Display | Definition
treatment | Treatment | One or more interventions are being evaluated for treating a disease, syndrome, or condition.
prevention | Prevention | One or more interventions are being assessed for preventing the development of a specific disease or health condition.
diagnostic | Diagnostic | One or more interventions are being evaluated for identifying a disease or health condition.
supportive-care | Supportive Care | One or more interventions are evaluated for maximizing comfort, minimizing side effects, or mitigating against a decline in the participant's health or function.
screening | Screening | One or more interventions are assessed or examined for identifying a condition, or risk factors for a condition, in people who are not yet known to have the condition or risk factor.
health-services-research | Health Services Research | One or more interventions for evaluating the delivery, processes, management, organization, or financing of healthcare.
basic-science | Basic Science | One or more interventions for examining the basic mechanism of action (for example, physiology or biomechanics of an intervention).
device-feasibility | Device Feasibility | An intervention of a device product is being evaluated to determine the feasibility of the product or to test a prototype device and not health outcomes. Such studies are conducted to confirm the design and operating specifications of a device before beginning a full clinical trial.

See the full registry of code systems defined as part of FHIR.

Explanation of the columns that may appear on this page:

Level | A few code lists that FHIR defines are hierarchical - each code is assigned a level. See Code System for further information.
Source | The source of the definition of the code (when the value set draws in codes defined elsewhere)
Code | The code (used as the code in the resource instance). If the code is in italics, this indicates that the code is not selectable ('Abstract')
Display | The display (used in the display element of a Coding). If there is no display, implementers should not simply display the code, but map the concept into their application
Definition | An explanation of the meaning of the concept
Comments | Additional notes about how to use the code

4.3.14.288 Code System http://terminology.hl7.org/CodeSystem/flag-category

URL: https://hl7.org/fhir/R4/codesystem-flag-category.html
Patient Care Work Group | Maturity Level: 1 | Draft | Use Context: Any

This is a code system defined at http://www.hl7.org/Special/committees/patientcare .

Summary

Defining URL: | http://terminology.hl7.org/CodeSystem/flag-category
Version: | 4.0.1
Name: | FlagCategory
Title: | Flag Category
Definition: | Example list of general categories for flagged issues. (Not complete or necessarily appropriate.)
Committee: | Patient Care Work Group

OID: | 2.16.840.1.113883.4.642.4.1071 (for OID based terminology systems)
Source Resource | XML / JSON

This Code system is used in the following value sets:

• ValueSet: Flag Category (Example list of general categories for flagged issues. (Not complete or necessarily appropriate.))

• ValueSet: Flag Category (Example list of general categories for flagged issues. (Not complete or necessarily appropriate.))

4.3.14.288.1 Content

4.3.14.288.2 Flag Category

Example list of general categories for flagged issues. (Not complete or necessarily appropriate.)

This code system http://terminology.hl7.org/CodeSystem/flag-category defines the following codes:

Code | Display | Definition
diet | Diet | Flags related to the subject's dietary needs.
drug | Drug | Flags related to the subject's medications.
lab | Lab | Flags related to performing laboratory tests and related processes (e.g. phlebotomy).
admin | Administrative | Flags related to administrative and financial processes.
contact | Subject Contact | Flags related to coming into contact with the patient.
clinical | Clinical | Flags related to the subject's clinical data.
behavioral | Behavioral | Flags related to behavior.
research | Research | Flags related to research.
advance-directive | Advance Directive | Flags related to subject's advance directives.
safety | Safety | Flags related to safety precautions.

See the full registry of code systems defined as part of FHIR.

Explanation of the columns that may appear on this page:

Level | A few code lists that FHIR defines are hierarchical - each code is assigned a level. See Code System for further information.
Source | The source of the definition of the code (when the value set draws in codes defined elsewhere)
Code | The code (used as the code in the resource instance). If the code is in italics, this indicates that the code is not selectable ('Abstract')
Display | The display (used in the display element of a Coding). If there is no display, implementers should not simply display the code, but map the concept into their application
Definition | An explanation of the meaning of the concept
Comments | Additional notes about how to use the code

4.3.14.289 Code System http://hl7.org/fhir/device-status

URL: https://hl7.org/fhir/R4/codesystem-device-status.html
Orders and Observations Work Group | Maturity Level: 2 | Trial Use | Use Context: Any

This is a code system defined by the FHIR project.

Summary

Defining URL: | http://hl7.org/fhir/device-status
Version: | 4.0.1
Name: | FHIRDeviceStatus
Title: | FHIRDeviceStatus
Definition: | The availability status of the device.
Committee: | Orders and Observations Work Group
OID: | 2.16.840.1.113883.4.642.4.210 (for OID based terminology systems)
Source Resource | XML / JSON

This Code system is used in the following value sets:

• ValueSet: FHIRDeviceStatus (The availability status of the device.)

• ValueSet: FHIRDeviceStatus (The availability status of the device.)

4.3.14.289.1 Content

4.3.14.289.2 FHIRDeviceStatus

The availability status of the device.

This code system http://hl7.org/fhir/device-status defines the following codes:

Code | Display | Definition
active | Active | The device is available for use. Note: For *implanted devices* this means that the device is implanted in the patient.
inactive | Inactive | The device is no longer available for use (e.g. lost, expired, damaged). Note: For *implanted devices* this means that the device has been removed from the patient.
entered-in-error | Entered in Error | The device was entered in error and voided.
unknown | Unknown | The status of the device has not been determined.

See the full registry of code systems defined as part of FHIR.

Explanation of the columns that may appear on this page:

Level | A few code lists that FHIR defines are hierarchical - each code is assigned a level. See Code System for further information.
Source | The source of the definition of the code (when the value set draws in codes defined elsewhere)
Code | The code (used as the code in the resource instance). If the code is in italics, this indicates that the code is not selectable ('Abstract')
Display | The display (used in the display element of a Coding). If there is no display, implementers should not simply display the code, but map the concept into their application
Definition | An explanation of the meaning of the concept
Comments | Additional notes about how to use the code

4.3.14.290 Code System http://terminology.hl7.org/CodeSystem/claimcareteamrole

URL: https://hl7.org/fhir/R4/codesystem-claim-careteamrole.html
Financial Management Work Group | Maturity Level: 1 | Draft | Use Context: Any

This is a code system defined by the FHIR project.

Summary

Defining URL: | http://terminology.hl7.org/CodeSystem/claimcareteamrole
Version: | 4.0.1
Name: | ClaimCareTeamRoleCodes
Title: | Claim Care Team Role Codes
Definition: | This value set includes sample Claim Care Team Role codes.
Committee: | Financial Management Work Group
OID: | 2.16.840.1.113883.4.642.4.1165 (for OID based terminology systems)
Copyright: | This is an example set.
Source Resource | XML / JSON

This Code system is used in the following value sets:

• ValueSet: Claim Care Team Role Codes (This value set includes sample Claim Care Team Role codes.)

• ValueSet: Claim Care Team Role Codes (This value set includes sample Claim Care Team Role codes.)

4.3.14.290.1 Content

4.3.14.290.2 Claim Care Team Role Codes

This value set includes sample Claim Care Team Role codes.

Copyright Statement:

This is an example set.

This code system http://terminology.hl7.org/CodeSystem/claimcareteamrole defines the following codes:

Code | Display | Definition
primary | Primary provider | The primary care provider.
assist | Assisting Provider | Assisting care provider.
supervisor | Supervising Provider | Supervising care provider.
other | Other | Other role on the care team.

See the full registry of code systems defined as part of FHIR.

Explanation of the columns that may appear on this page:

Level | A few code lists that FHIR defines are hierarchical - each code is assigned a level. See Code System for further information.
Source | The source of the definition of the code (when the value set draws in codes defined elsewhere)
Code | The code (used as the code in the resource instance). If the code is in italics, this indicates that the code is not selectable ('Abstract')
Display | The display (used in the display element of a Coding). If there is no display, implementers should not simply display the code, but map the concept into their application
Definition | An explanation of the meaning of the concept
Comments | Additional notes about how to use the code

4.3.14.291 Code System http://terminology.hl7.org/CodeSystem/expansion-parameter-source

URL: https://hl7.org/fhir/R4/codesystem-expansion-parameter-source.html
Vocabulary Work Group | Maturity Level: 0 | Informative | Use Context: Any

This is a code system defined by the FHIR project.

Summary

Defining URL: | http://terminology.hl7.org/CodeSystem/expansion-parameter-source
Version: | 4.0.1

Name: | ExpansionParameterSource
Title: | ExpansionParameterSource
Definition: | Declares what the source of a parameter is.
Committee: | ??
OID: | 2.16.840.1.113883.4.642.4.1279 (for OID based terminology systems)
Source Resource | XML / JSON

This Code system is used in the following value sets:

• ValueSet: ExpansionParameterSource (Declares what the source of a parameter is.)

• ValueSet: ExpansionParameterSource (Declares what the source of a parameter is.)

4.3.14.291.1 Content

4.3.14.291.2 ExpansionParameterSource

Declares what the source of a parameter is.

This code system http://terminology.hl7.org/CodeSystem/expansion-parameter-source defines the following codes:

Code | Display | Definition
input | Client Input | The parameter was supplied by the client in the $expand request.
server | Server Engine | The parameter was added by the expansion engine on the server.
codesystem | Code System | The parameter was added from one the code systems used in the $expand operation.

See the full registry of code systems defined as part of FHIR.

Explanation of the columns that may appear on this page:

Level | A few code lists that FHIR defines are hierarchical - each code is assigned a level. See Code System for further information.
Source | The source of the definition of the code (when the value set draws in codes defined elsewhere)
Code | The code (used as the code in the resource instance). If the code is in italics, this indicates that the code is not selectable ('Abstract')
Display | The display (used in the display element of a Coding). If there is no display, implementers should not simply display the code, but map the concept into their application
Definition | An explanation of the meaning of the concept
Comments | Additional notes about how to use the code

4.3.14.292 Code System http://terminology.hl7.org/CodeSystem/action-type

URL: https://hl7.org/fhir/R4/codesystem-action-type.html
Clinical Decision Support Work Group | Maturity Level: 2 | Trial Use | Use Context: Any

This is a code system defined by the FHIR project.

Summary

Defining URL: | http://terminology.hl7.org/CodeSystem/action-type
Version: | 4.0.1
Name: | ActionType
Title: | ActionType
Definition: | The type of action to be performed.
Committee: | Clinical Decision Support Work Group
OID: | 2.16.840.1.113883.4.642.4.1246 (for OID based terminology systems)
Source Resource | XML / JSON

This Code system is used in the following value sets:

• ValueSet: ActionType (The type of action to be performed.)

• ValueSet: ActionType (The type of action to be performed.)

4.3.14.292.1 Content

4.3.14.292.2 ActionType

The type of action to be performed.

This code system http://terminology.hl7.org/CodeSystem/action-type defines the following codes:

Code | Display | Definition
create | Create | The action is to create a new resource.
update | Update | The action is to update an existing resource.
remove | Remove | The action is to remove an existing resource.
fire-event | Fire Event | The action is to fire a specific event.

See the full registry of code systems defined as part of FHIR.

Explanation of the columns that may appear on this page:

Level | A few code lists that FHIR defines are hierarchical - each code is assigned a level. See Code System for further information.

Source | The source of the definition of the code (when the value set draws in codes defined elsewhere)
Code | The code (used as the code in the resource instance). If the code is in italics, this indicates that the code is not selectable ('Abstract')
Display | The display (used in the display element of a Coding). If there is no display, implementers should not simply display the code, but map the concept into their application
Definition | An explanation of the meaning of the concept
Comments | Additional notes about how to use the code

4.3.14.293 Code System http://terminology.hl7.org/CodeSystem/diet

URL: https://hl7.org/fhir/R4/codesystem-encounter-diet.html
Patient Administration Work Group | Maturity Level: 1 | Draft | Use Context: Any

This is a code system defined by the FHIR project.

Summary

Defining URL: | http://terminology.hl7.org/CodeSystem/diet
Version: | 4.0.1
Name: | Diet
Title: | Diet
Definition: | This value set defines a set of codes that can be used to indicate dietary preferences or restrictions a patient may have.
Committee: | Patient Administration Work Group
OID: | 2.16.840.1.113883.4.642.4.1091 (for OID based terminology systems)
Source Resource | XML / JSON

This Code system is used in the following value sets:

• ValueSet: Diet (This value set defines a set of codes that can be used to indicate dietary preferences or restrictions a patient may have.)

• ValueSet: Diet (This value set defines a set of codes that can be used to indicate dietary preferences or restrictions a patient may have.)

4.3.14.293.1 Content

4.3.14.293.2 Diet

This value set defines a set of codes that can be used to indicate dietary preferences or restrictions a patient may have.

This code system http://terminology.hl7.org/CodeSystem/diet defines the following codes:

Code | Display | Definition
vegetarian | Vegetarian | Food without meat, poultry or seafood.
dairy-free | Dairy Free | Excludes dairy products.
nut-free | Nut Free | Excludes ingredients containing nuts.
gluten-free | Gluten Free | Excludes ingredients containing gluten.
vegan | Vegan | Food without meat, poultry, seafood, eggs, dairy products and other animal-derived substances.
halal | Halal | Foods that conform to Islamic law.
kosher | Kosher | Foods that conform to Jewish dietary law.

See the full registry of code systems defined as part of FHIR.

Explanation of the columns that may appear on this page:

Level | A few code lists that FHIR defines are hierarchical - each code is assigned a level. See Code System for further information.
Source | The source of the definition of the code (when the value set draws in codes defined elsewhere)
Code | The code (used as the code in the resource instance). If the code is in italics, this indicates that the code is not selectable ('Abstract')
Display | The display (used in the display element of a Coding). If there is no display, implementers should not simply display the code, but map the concept into their application
Definition | An explanation of the meaning of the concept
Comments | Additional notes about how to use the code

4.3.14.294 Code System http://hl7.org/fhir/linkage-type

URL: https://hl7.org/fhir/R4/codesystem-linkage-type.html
Patient Care Work Group | Maturity Level: 0 | Trial Use | Use Context: Any

This is a code system defined by the FHIR project.

Summary

Defining URL: | http://hl7.org/fhir/linkage-type
Version: | 4.0.1
Name: | LinkageType
Title: | LinkageType

Definition: | Used to distinguish different roles a resource can play within a set of linked resources.
Committee: | Patient Care Work Group
OID: | 2.16.840.1.113883.4.642.4.315 (for OID based terminology systems)
Source Resource | XML / JSON

This Code system is used in the following value sets:

• ValueSet: LinkageType (Used to distinguish different roles a resource can play within a set of linked resources.)

• ValueSet: LinkageType (Used to distinguish different roles a resource can play within a set of linked resources.)

4.3.14.294.1 Content

4.3.14.294.2 LinkageType

Used to distinguish different roles a resource can play within a set of linked resources.

This code system http://hl7.org/fhir/linkage-type defines the following codes:

Code | Display | Definition
source | Source of Truth | The resource represents the "source of truth" (from the perspective of this Linkage resource) for the underlying event/condition/etc.
alternate | Alternate Record | The resource represents an alternative view of the underlying event/condition/etc. The resource may still be actively maintained, even though it is not considered to be the source of truth.
historical | Historical/Obsolete Record | The resource represents an obsolete record of the underlying event/condition/etc. It is not expected to be actively maintained.

See the full registry of code systems defined as part of FHIR.

Explanation of the columns that may appear on this page:

Level | A few code lists that FHIR defines are hierarchical - each code is assigned a level. See Code System for further information.
Source | The source of the definition of the code (when the value set draws in codes defined elsewhere)
Code | The code (used as the code in the resource instance). If the code is in italics, this indicates that the code is not selectable ('Abstract')
Display | The display (used in the display element of a Coding). If there is no display, implementers should not simply display the code, but map the concept into their application
Definition | An explanation of the meaning of the concept
Comments | Additional notes about how to use the code

4.3.14.295 Code System http://terminology.hl7.org/CodeSystem/measure-population

URL: https://hl7.org/fhir/R4/codesystem-measure-population.html
Clinical Quality Information Work Group | Maturity Level: 2 | Trial Use | Use Context: Any

This is a code system defined by the FHIR project.

Summary

Defining URL: | http://terminology.hl7.org/CodeSystem/measure-population
Version: | 4.0.1
Name: | MeasurePopulationType
Title: | MeasurePopulationType
Definition: | The type of population.
Committee: | Clinical Quality Information Work Group
OID: | 2.16.840.1.113883.4.642.4.1231 (for OID based terminology systems)
Source Resource | XML / JSON

This Code system is used in the following value sets:

• ValueSet: MeasurePopulationType (The type of population.)

• ValueSet: MeasurePopulationType (The type of population.)

4.3.14.295.1 Content

4.3.14.295.2 MeasurePopulationType

The type of population.

This code system http://terminology.hl7.org/CodeSystem/measure-population defines the following codes:

Code | Display | Definition
initial-population | Initial Population | The initial population refers to all patients or events to be evaluated by a quality measure involving patients who share a common set of specified characterstics. All patients or events counted (for example, as numerator, as denominator) are drawn from the initial population.
numerator | Numerator | The upper portion of a fraction used to calculate a rate, proportion, or ratio. Also called the measure focus, it is the target process, condition, event, or outcome. Numerator criteria are the processes or outcomes expected for each patient, or event defined in the denominator. A numerator statement describes the clinical action that satisfies the conditions of the measure.

numerator-exclusion | Numerator Exclusion | Numerator exclusion criteria define patients or events to be removed from the numerator. Numerator exclusions are used in proportion and ratio measures to help narrow the numerator (for inverted measures).
denominator | Denominator | The lower portion of a fraction used to calculate a rate, proportion, or ratio. The denominator can be the same as the initial population, or a subset of the initial population to further constrain the population for the purpose of the measure.
denominator-exclusion | Denominator Exclusion | Denominator exclusion criteria define patients or events that should be removed from the denominator before determining if numerator criteria are met. Denominator exclusions are used in proportion and ratio measures to help narrow the denominator. For example, patients with bilateral lower extremity amputations would be listed as a denominator exclusion for a measure requiring foot exams.
denominator-exception | Denominator Exception | Denominator exceptions are conditions that should remove a patient or event from the denominator of a measure only if the numerator criteria are not met. Denominator exception allows for adjustment of the calculated score for those providers with higher risk populations. Denominator exception criteria are only used in proportion measures.
measure-population | Measure Population | Measure population criteria define the patients or events for which the individual observation for the measure should be taken. Measure populations are used for continuous variable measures rather than numerator and denominator criteria.
measure-population-exclusion | Measure Population Exclusion | Measure population criteria define the patients or events that should be removed from the measure population before determining the outcome of one or more continuous variables defined for the measure observation. Measure population exclusion criteria are used within continuous variable measures to help narrow the measure population.
measure-observation | Measure Observation | Defines the individual observation to be performed for each patient or event in the measure population. Measure observations for each case in the population are aggregated to determine the overall measure score for the population.

See the full registry of code systems defined as part of FHIR.

Explanation of the columns that may appear on this page:

Level | A few code lists that FHIR defines are hierarchical - each code is assigned a level. See Code System for further information.
Source | The source of the definition of the code (when the value set draws in codes defined elsewhere)
Code | The code (used as the code in the resource instance). If the code is in italics, this indicates that the code is not selectable ('Abstract')
Display | The display (used in the display element of a Coding). If there is no display, implementers should not simply display the code, but map the concept into their application
Definition | An explanation of the meaning of the concept
Comments | Additional notes about how to use the code

4.3.14.296 Code System http://hl7.org/fhir/guide-parameter-code

URL: https://hl7.org/fhir/R4/codesystem-guide-parameter-code.html
FHIR Infrastructure Work Group | Maturity Level: 1 | Trial Use | Use Context: Any

This is a code system defined by the FHIR project.

Summary

Defining URL: | http://hl7.org/fhir/guide-parameter-code
Version: | 4.0.1
Name: | GuideParameterCode
Title: | GuideParameterCode
Definition: | Code of parameter that is input to the guide.
Committee: | FHIR Infrastructure Work Group
OID: | 2.16.840.1.113883.4.642.4.997 (for OID based terminology systems)
Source Resource | XML / JSON

This Code system is used in the following value sets:

• ValueSet: GuideParameterCode (Code of parameter that is input to the guide.)
• ValueSet: GuideParameterCode (Code of parameter that is input to the guide.)

4.3.14.296.1 Content

4.3.14.296.2 GuideParameterCode

Code of parameter that is input to the guide.

This code system http://hl7.org/fhir/guide-parameter-code defines the following codes:

Code | Display | Definition
apply | Apply Metadata Value | If the value of this string 0..* parameter is one of the metadata fields then all conformance resources will have any specified [Resource].[field] overwritten with the ImplementationGuide.[field], where field is one of: version, date, status, publisher, contact, copyright, experimental, jurisdiction, useContext.
path-resource | Resource Path | The value of this string 0..* parameter is a subfolder of the build context's location that is to be scanned to load resources. Scope is (if present) a particular resource type.
path-pages | Pages Path | The value of this string 0..1 parameter is a subfolder of the build context's location that contains files that are part of the html content processed by the builder.
path-tx-cache | Terminology Cache Path | The value of this string 0..1 parameter is a subfolder of the build context's location that is used as the terminology cache. If this is not present, the terminology cache is on the local system, not under version control.

expansion-parameter | Expansion Profile | The value of this string 0..* parameter is a parameter (name=value) when expanding value sets for this implementation guide. This is particularly used to specify the versions of published terminologies such as SNOMED CT.
rule-broken-links | Broken Links Rule | The value of this string 0..1 parameter is either "warning" or "error" (default = "error"). If the value is "warning" then IG build tools allow the IG to be considered successfully build even when there is no internal broken links.
generate-xml | Generate XML | The value of this boolean 0..1 parameter specifies whether the IG publisher creates examples in XML format. If not present, the Publication Tool decides whether to generate XML.
generate-json | Generate JSON | The value of this boolean 0..1 parameter specifies whether the IG publisher creates examples in JSON format. If not present, the Publication Tool decides whether to generate JSON.
generate-turtle | Generate Turtle | The value of this boolean 0..1 parameter specifies whether the IG publisher creates examples in Turtle format. If not present, the Publication Tool decides whether to generate Turtle.
html-template | HTML Template | The value of this string singleton parameter is the name of the file to use as the builder template for each generated page (see templating).

See the full registry of code systems defined as part of FHIR.

Explanation of the columns that may appear on this page:

Level | A few code lists that FHIR defines are hierarchical - each code is assigned a level. See Code System for further information.
Source | The source of the definition of the code (when the value set draws in codes defined elsewhere)
Code | The code (used as the code in the resource instance). If the code is in italics, this indicates that the code is not selectable ('Abstract')
Display | The display (used in the display element of a Coding). If there is no display, implementers should not simply display the code, but map the concept into their application
Definition | An explanation of the meaning of the concept
Comments | Additional notes about how to use the code

4.3.14.297 Code System http://terminology.hl7.org/CodeSystem/handling-condition

URL: https://hl7.org/fhir/R4/codesystem-handling-condition.html
Orders and Observations Work Group | Maturity Level: 1 | Draft | Use Context: Any

This is a code system defined by the FHIR project.

Summary

Defining URL: | http://terminology.hl7.org/CodeSystem/handling-condition
Version: | 4.0.1
Name: | HandlingConditionSet
Title: | HandlingConditionSet
Definition: | Set of handling instructions prior testing of the specimen.
Committee: | Orders and Observations Work Group
OID: | 2.16.840.1.113883.4.642.4.1259 (for OID based terminology systems)
Source Resource | XML / JSON

This Code system is used in the following value sets:

• ValueSet: HandlingConditionSet (Set of handling instructions prior testing of the specimen.)
• ValueSet: HandlingConditionSet (Set of handling instructions prior testing of the specimen.)

4.3.14.297.1 Content

4.3.14.297.2 HandlingConditionSet

Set of handling instructions prior testing of the specimen.

This code system http://terminology.hl7.org/CodeSystem/handling-condition defines the following codes:

Code | Display | Definition
room | room temperature | room temperature.
refrigerated | refrigerated | refrigerated temperature.
frozen | frozen | frozen temperature.

See the full registry of code systems defined as part of FHIR.

Explanation of the columns that may appear on this page:

Level | A few code lists that FHIR defines are hierarchical - each code is assigned a level. See Code System for further information.
Source | The source of the definition of the code (when the value set draws in codes defined elsewhere)
Code | The code (used as the code in the resource instance). If the code is in italics, this indicates that the code is not selectable ('Abstract')
Display | The display (used in the display element of a Coding). If there is no display, implementers should not simply display the code, but map the concept into their application
Definition | An explanation of the meaning of the concept
Comments | Additional notes about how to use the code

4.3.14.298 Code System http://terminology.hl7.org/CodeSystem/plan-definition-type

URL: https://hl7.org/fhir/R4/codesystem-plan-definition-type.html
Clinical Decision Support Work Group | Maturity Level: 2 | Trial Use | Use Context: Any

This is a code system defined by the FHIR project.

Summary

Defining URL: | http://terminology.hl7.org/CodeSystem/plan-definition-type
Version: | 4.0.1
Name: | PlanDefinitionType
Title: | PlanDefinitionType
Definition: | The type of PlanDefinition.
Committee: | Clinical Decision Support Work Group
OID: | 2.16.840.1.113883.4.642.4.1245 (for OID based terminology systems)
Source Resource | XML / JSON

This Code system is used in the following value sets:

• ValueSet: PlanDefinitionType (The type of PlanDefinition.)
• ValueSet: PlanDefinitionType (The type of PlanDefinition.)

4.3.14.298.1 Content

4.3.14.298.2 PlanDefinitionType

The type of PlanDefinition.

This code system http://terminology.hl7.org/CodeSystem/plan-definition-type defines the following codes:

Code | Display | Definition
order-set | Order Set | A pre-defined and approved group of orders related to a particular clinical condition (e.g. hypertension treatment and monitoring) or stage of care (e.g. hospital admission to Coronary Care Unit). An order set is used as a checklist for the clinician when managing a patient with a specific condition. It is a structured collection of orders relevant to that condition and presented to the clinician in a computerized provider order entry (CPOE) system.
clinical-protocol | Clinical Protocol | Defines a desired/typical sequence of clinical activities including preconditions, triggers and temporal relationships.
eca-rule | ECA Rule | A decision support rule of the form [on Event] if Condition then Action. It is intended to be a shareable, computable definition of actions that should be taken whenever some condition is met in response to a particular event or events.
workflow-definition | Workflow Definition | Defines the steps for a group of one or more systems in an event flow process along with the step constraints, sequence, pre-conditions and decision points to complete a particular objective.

See the full registry of code systems defined as part of FHIR.

Explanation of the columns that may appear on this page:

Level | A few code lists that FHIR defines are hierarchical - each code is assigned a level. See Code System for further information.
Source | The source of the definition of the code (when the value set draws in codes defined elsewhere)
Code | The code (used as the code in the resource instance). If the code is in italics, this indicates that the code is not selectable ('Abstract')
Display | The display (used in the display element of a Coding). If there is no display, implementers should not simply display the code, but map the concept into their application
Definition | An explanation of the meaning of the concept
Comments | Additional notes about how to use the code

4.3.14.299 Code System http://terminology.hl7.org/CodeSystem/missingtoothreason

URL: https://hl7.org/fhir/R4/codesystem-missing-tooth-reason.html
Financial Management Work Group | Maturity Level: 1 | Draft | Use Context: Any

This is a code system defined by the FHIR project.

Summary

Defining URL: | http://terminology.hl7.org/CodeSystem/missingtoothreason
Version: | 4.0.1
Name: | MissingToothReasonCodes
Title: | Missing Tooth Reason Codes
Definition: | This value set includes sample Missing Tooth Reason codes.
Committee: | Financial Management Work Group
OID: | 2.16.840.1.113883.4.642.4.1150 (for OID based terminology systems)
Copyright: | This is an example set.
Source Resource | XML / JSON

This Code system is used in the following value sets:

• ValueSet: Missing Tooth Reason Codes (This value set includes sample Missing Tooth Reason codes.)

• ValueSet: Missing Tooth Reason Codes (This value set includes sample Missing Tooth Reason codes.)

4.3.14.299.1 Content

4.3.14.299.2 Missing Tooth Reason Codes

This value set includes sample Missing Tooth Reason codes.

Copyright Statement:

This is an example set.

This code system http://terminology.hl7.org/CodeSystem/missingtoothreason defines the following codes:

Code | Display | Definition
e | E | Extraction
c | C | Congenital
u | U | Unknown
o | O | Other

See the full registry of code systems defined as part of FHIR.

Explanation of the columns that may appear on this page:

Level | A few code lists that FHIR defines are hierarchical - each code is assigned a level. See Code System for further information.
Source | The source of the definition of the code (when the value set draws in codes defined elsewhere)
Code | The code (used as the code in the resource instance). If the code is in italics, this indicates that the code is not selectable ('Abstract')
Display | The display (used in the display element of a Coding). If there is no display, implementers should not simply display the code, but map the concept into their application
Definition | An explanation of the meaning of the concept
Comments | Additional notes about how to use the code

4.3.14.300 Code System http://hl7.org/fhir/search-xpath-usage

URL: https://hl7.org/fhir/R4/codesystem-search-xpath-usage.html
FHIR Infrastructure Work Group | Maturity Level: 3 | Trial Use | Use Context: Any

This is a code system defined by the FHIR project.

Summary

Defining URL: | http://hl7.org/fhir/search-xpath-usage
Version: | 4.0.1
Name: | XPathUsageType
Title: | XPathUsageType
Definition: | How a search parameter relates to the set of elements returned by evaluating its xpath query.
Committee: | FHIR Infrastructure Work Group
OID: | 2.16.840.1.113883.4.642.4.636 (for OID based terminology systems)
Source Resource | XML / JSON

This Code system is used in the following value sets:

• ValueSet: XPathUsageType (How a search parameter relates to the set of elements returned by evaluating its xpath query.)

• ValueSet: XPathUsageType (How a search parameter relates to the set of elements returned by evaluating its xpath query.)

4.3.14.300.1 Content

4.3.14.300.2 XPathUsageType

How a search parameter relates to the set of elements returned by evaluating its xpath query.

This code system http://hl7.org/fhir/search-xpath-usage defines the following codes:

Code | Display | Definition
normal | Normal | The search parameter is derived directly from the selected nodes based on the type definitions.
phonetic | Phonetic | The search parameter is derived by a phonetic transform from the selected nodes.
nearby | Nearby | The search parameter is based on a spatial transform of the selected nodes.
distance | Distance | The search parameter is based on a spatial transform of the selected nodes, using physical distance from the middle.
other | Other | The interpretation of the xpath statement is unknown (and can't be automated).

See the full registry of code systems defined as part of FHIR.

Explanation of the columns that may appear on this page:

Level | A few code lists that FHIR defines are hierarchical - each code is assigned a level. See Code System for further information.
Source | The source of the definition of the code (when the value set draws in codes defined elsewhere)
Code | The code (used as the code in the resource instance). If the code is in italics, this indicates that the code is not selectable ('Abstract')

Display | The display (used in the display element of a Coding). If there is no display, implementers should not simply display the code, but map the concept into their application
Definition | An explanation of the meaning of the concept
Comments | Additional notes about how to use the code

4.3.14.301 Code System http://terminology.hl7.org/CodeSystem/ex-diagnosisrelatedgroup

URL: https://hl7.org/fhir/R4/codesystem-ex-diagnosisrelatedgroup.html
Financial Management Work Group | Maturity Level: 1 | Draft | Use Context: Any

This is a code system defined by the FHIR project.

Summary

Defining URL: | http://terminology.hl7.org/CodeSystem/ex-diagnosisrelatedgroup
Version: | 4.0.1
Name: | ExampleDiagnosisRelatedGroupCodes
Title: | Example Diagnosis Related Group Codes
Definition: | This value set includes example Diagnosis Related Group codes.
Committee: | Financial Management Work Group
OID: | 2.16.840.1.113883.4.642.4.1166 (for OID based terminology systems)
Copyright: | This is an example set.
Source Resource | XML / JSON

This Code system is used in the following value sets:

• ValueSet: Example Diagnosis Related Group Codes (This value set includes example Diagnosis Related Group codes.)

• ValueSet: Example Diagnosis Related Group Codes (This value set includes example Diagnosis Related Group codes.)

4.3.14.301.1 Content

4.3.14.301.2 Example Diagnosis Related Group Codes

This value set includes example Diagnosis Related Group codes.

Copyright Statement:

This is an example set.

This code system http://terminology.hl7.org/CodeSystem/ex-diagnosisrelatedgroup defines the following codes:

Code | Display | Definition
100 | Normal Vaginal Delivery | Normal Vaginal Delivery.
101 | Appendectomy - uncomplicated | Appendectomy without rupture or other complications.
300 | Tooth abscess | Emergency department treatment of a tooth abscess.
400 | Head trauma - concussion | Head trauma - concussion.

See the full registry of code systems defined as part of FHIR.

Explanation of the columns that may appear on this page:

Level | A few code lists that FHIR defines are hierarchical - each code is assigned a level. See Code System for further information.
Source | The source of the definition of the code (when the value set draws in codes defined elsewhere)
Code | The code (used as the code in the resource instance). If the code is in italics, this indicates that the code is not selectable ('Abstract')
Display | The display (used in the display element of a Coding). If there is no display, implementers should not simply display the code, but map the concept into their application
Definition | An explanation of the meaning of the concept
Comments | Additional notes about how to use the code

4.3.14.302 Code System http://hl7.org/fhir/ex-pharmaservice

URL: https://hl7.org/fhir/R4/codesystem-service-pharmacy.html
Vocabulary Work Group | Maturity Level: 0 | Informative | Use Context: Any

This is a code system defined by the FHIR project.

Summary

Defining URL: | http://hl7.org/fhir/ex-pharmaservice
Version: | 4.0.1
Name: | ExamplePharmacyServiceCodes
Title: | Example Pharmacy Service Codes
Definition: | This value set includes a smattering of Pharmacy Service codes.
Committee: | ??
OID: | 2.16.840.1.113883.4.642.4.563 (for OID based terminology systems)

Copyright: | This is an example set.
Source Resource | XML / JSON

This Code system is used in the following value sets:

• ValueSet: Example Pharmacy Service Codes (This value set includes a smattering of Pharmacy Service codes.)

• ValueSet: Example Pharmacy Service Codes (This value set includes a smattering of Pharmacy Service codes.)

4.3.14.302.1 Content

4.3.14.302.2 Example Pharmacy Service Codes

This value set includes a smattering of Pharmacy Service codes.

Copyright Statement:

This is an example set.

This code system http://hl7.org/fhir/ex-pharmaservice defines the following codes:

Code | Display | Definition
smokecess | Smoking cessation | Smoking cessation
flushot | Flu Shot | Flu Shot
drugcost | Drug Cost | The wholesale price of the medication.
markup | Markup | The additional cost assessed on the drug.
dispensefee | Dispense Fee | The professional fee charged for dispensing the product or service.
compoundfee | Compounding Fee | The professional fee charged for compounding the medication.

See the full registry of code systems defined as part of FHIR.

Explanation of the columns that may appear on this page:

Level | A few code lists that FHIR defines are hierarchical - each code is assigned a level. See Code System for further information.
Source | The source of the definition of the code (when the value set draws in codes defined elsewhere)
Code | The code (used as the code in the resource instance). If the code is in italics, this indicates that the code is not selectable ('Abstract')
Display | The display (used in the display element of a Coding). If there is no display, implementers should not simply display the code, but map the concept into their application
Definition | An explanation of the meaning of the concept
Comments | Additional notes about how to use the code

4.3.14.303 Code System http://hl7.org/fhir/bundle-type

URL: https://hl7.org/fhir/R4/codesystem-bundle-type.html
FHIR Infrastructure Work Group | Maturity Level: N | Normative (from v4.0.0) | Use Context: Any

| This page has been approved as part of an ANSI standard. See the Infrastructure Package for further details.

This is a code system defined by the FHIR project.

Summary

Defining URL: | http://hl7.org/fhir/bundle-type
Version: | 4.0.1
Name: | BundleType
Title: | BundleType
Definition: | Indicates the purpose of a bundle - how it is intended to be used.
Committee: | FHIR Infrastructure Work Group
OID: | 2.16.840.1.113883.4.642.4.621 (for OID based terminology systems)
Source Resource | XML / JSON

This Code system is used in the following value sets:

• ValueSet: BundleType (Indicates the purpose of a bundle - how it is intended to be used.)

• ValueSet: BundleType (Indicates the purpose of a bundle - how it is intended to be used.)

4.3.14.303.1 Content

4.3.14.303.2 BundleType

Indicates the purpose of a bundle - how it is intended to be used.

This code system http://hl7.org/fhir/bundle-type defines the following codes:

Code | Display | Definition
document | Document | The bundle is a document. The first resource is a Composition.
message | Message | The bundle is a message. The first resource is a MessageHeader.
transaction | Transaction | The bundle is a transaction - intended to be processed by a server as an atomic commit.
transaction-response | Transaction Response | The bundle is a transaction response. Because the response is a transaction response, the transaction has succeeded, and all responses are error free.
batch | Batch | The bundle is a set of actions - intended to be processed by a server as a group of independent actions.

batch-response | Batch Response | The bundle is a batch response. Note that as a batch, some responses may indicate failure and others success.
history | History List | The bundle is a list of resources from a history interaction on a server.
searchset | Search Results | The bundle is a list of resources returned as a result of a search/query interaction, operation, or message.
collection | Collection | The bundle is a set of resources collected into a single package for ease of distribution that imposes no processing obligations or behavioral rules beyond persistence.

See the full registry of code systems defined as part of FHIR.

Explanation of the columns that may appear on this page:

Level | A few code lists that FHIR defines are hierarchical - each code is assigned a level. See Code System for further information.
Source | The source of the definition of the code (when the value set draws in codes defined elsewhere)
Code | The code (used as the code in the resource instance). If the code is in italics, this indicates that the code is not selectable ('Abstract')
Display | The display (used in the display element of a Coding). If there is no display, implementers should not simply display the code, but map the concept into their application
Definition | An explanation of the meaning of the concept
Comments | Additional notes about how to use the code

4.3.14.304 Code System http://terminology.hl7.org/CodeSystem/contractactorrole

URL: https://hl7.org/fhir/R4/codesystem-contract-actorrole.html
Financial Management Work Group | Maturity Level: 1 | Draft | Use Context: Any

This is a code system defined by the FHIR project.

Summary

Defining URL: | http://terminology.hl7.org/CodeSystem/contractactorrole
Version: | 4.0.1
Name: | ContractActorRoleCodes
Title: | Contract Actor Role Codes
Definition: | This value set includes sample Contract Actor Role codes.
Committee: | Financial Management Work Group
OID: | 2.16.840.1.113883.4.642.4.1203 (for OID based terminology systems)
Copyright: | This is an example set.
Source Resource | XML / JSON

This Code system is used in the following value sets:

• ValueSet: Contract Actor Role Codes (This value set includes sample Contract Actor Role codes.)
• ValueSet: Contract Actor Role Codes (This value set includes sample Contract Actor Role codes.)

4.3.14.304.1 Content

4.3.14.304.2 Contract Actor Role Codes

This value set includes sample Contract Actor Role codes.

Copyright Statement:

This is an example set.

This code system http://terminology.hl7.org/CodeSystem/contractactorrole defines the following codes:

Code | Display | Definition
practitioner | Practitioner | Someone who provides health care related services to people or animals including both clinical and support services.
patient | Patient | A receiver, human or animal, of health care related goods and services.

See the full registry of code systems defined as part of FHIR.

Explanation of the columns that may appear on this page:

Level | A few code lists that FHIR defines are hierarchical - each code is assigned a level. See Code System for further information.
Source | The source of the definition of the code (when the value set draws in codes defined elsewhere)
Code | The code (used as the code in the resource instance). If the code is in italics, this indicates that the code is not selectable ('Abstract')
Display | The display (used in the display element of a Coding). If there is no display, implementers should not simply display the code, but map the concept into their application
Definition | An explanation of the meaning of the concept
Comments | Additional notes about how to use the code

4.3.14.305 Code System http://terminology.hl7.org/CodeSystem/consentaction

URL: https://hl7.org/fhir/R4/codesystem-consent-action.html

Community Based Collaborative Care Work Group | Maturity Level: 1 | Draft | Use Context: Any

This is a code system defined by the FHIR project.

Summary

Defining URL: | http://terminology.hl7.org/CodeSystem/consentaction
Version: | 4.0.1
Name: | ConsentActionCodes
Title: | Consent Action Codes
Definition: | This value set includes sample Consent Action codes.
Committee: | Community Based Collaborative Care Work Group
OID: | 2.16.840.1.113883.4.642.4.1227 (for OID based terminology systems)
Copyright: | This is an example set.
Source Resource | XML / JSON

This Code system is used in the following value sets:

• ValueSet: Consent Action Codes (This value set includes sample Consent Action codes.)

• ValueSet: Consent Action Codes (This value set includes sample Consent Action codes.)

4.3.14.305.1 Content

4.3.14.305.2 Consent Action Codes

This value set includes sample Consent Action codes.

Copyright Statement:

This is an example set.

This code system http://terminology.hl7.org/CodeSystem/consentaction defines the following codes:

Code | Display | Definition
collect | Collect | Gather retrieved information for storage
access | Access | Retrieval without permitting collection, use or disclosure. e.g., no screen-scraping for collection, use or disclosure (view-only access)
use | Use | Utilize the retrieved information
disclose | Disclose | Transfer retrieved information
correct | Access and Correct | Allow retrieval of a patient's information for the purpose of update or rectify

See the full registry of code systems defined as part of FHIR.

Explanation of the columns that may appear on this page:

Level | A few code lists that FHIR defines are hierarchical - each code is assigned a level. See Code System for further information.
Source | The source of the definition of the code (when the value set draws in codes defined elsewhere)
Code | The code (used as the code in the resource instance). If the code is in italics, this indicates that the code is not selectable ('Abstract')
Display | The display (used in the display element of a Coding). If there is no display, implementers should not simply display the code, but map the concept into their application
Definition | An explanation of the meaning of the concept
Comments | Additional notes about how to use the code

4.3.14.306 Code System http://terminology.hl7.org/CodeSystem/medication-admin-category

URL: https://hl7.org/fhir/R4/codesystem-medication-admin-category.html
Pharmacy Work Group | Maturity Level: 0 | Informative | Use Context: Any

This is a code system defined by the FHIR project.

Summary

Defining URL: | http://terminology.hl7.org/CodeSystem/medication-admin-category
Version: | 4.0.1
Name: | MedicationAdministration Category Codes
Title: | Medication administration category codes
Definition: | MedicationAdministration Category Codes
Committee: | Pharmacy Work Group
OID: | 2.16.840.1.113883.4.642.4.1111 (for OID based terminology systems)
Source Resource | XML / JSON

This Code system is used in the following value sets:

• ValueSet: Medication administration category codes (MedicationAdministration Category Codes)

• ValueSet: Medication administration category codes (MedicationAdministration Category Codes)

4.3.14.306.1 Content

4.3.14.306.2 Medication administration category codes

MedicationAdministration Category Codes

This code system http://terminology.hl7.org/CodeSystem/medication-admin-category defines the following codes:

Code | Display | Definition
inpatient | Inpatient | Includes administrations in an inpatient or acute care setting
outpatient | Outpatient | Includes administrations in an outpatient setting (for example, Emergency Department, Outpatient Clinic, Outpatient Surgery, Doctor's office)
community | Community | Includes administrations by the patient in their home (this would include long term care or nursing homes, hospices, etc.)

See the full registry of code systems defined as part of FHIR.

Explanation of the columns that may appear on this page:

Level | A few code lists that FHIR defines are hierarchical - each code is assigned a level. See Code System for further information.
Source | The source of the definition of the code (when the value set draws in codes defined elsewhere)
Code | The code (used as the code in the resource instance). If the code is in italics, this indicates that the code is not selectable ('Abstract')
Display | The display (used in the display element of a Coding). If there is no display, implementers should not simply display the code, but map the concept into their application
Definition | An explanation of the meaning of the concept
Comments | Additional notes about how to use the code

4.3.14.307 Code System http://hl7.org/fhir/action-grouping-behavior

URL: https://hl7.org/fhir/R4/codesystem-action-grouping-behavior.html
Clinical Decision Support Work Group | Maturity Level: 2 | Trial Use | Use Context: Any

This is a code system defined by the FHIR project.

Summary

Defining URL: | http://hl7.org/fhir/action-grouping-behavior
Version: | 4.0.1
Name: | ActionGroupingBehavior
Title: | ActionGroupingBehavior
Definition: | Defines organization behavior of a group.
Committee: | Clinical Decision Support Work Group
OID: | 2.16.840.1.113883.4.642.4.800 (for OID based terminology systems)
Source Resource | XML / JSON

This Code system is used in the following value sets:

• ValueSet: ActionGroupingBehavior (Defines organization behavior of a group.)

• ValueSet: ActionGroupingBehavior (Defines organization behavior of a group.)

4.3.14.307.1 Content

4.3.14.307.2 ActionGroupingBehavior

Defines organization behavior of a group.

This code system http://hl7.org/fhir/action-grouping-behavior defines the following codes:

Code | Display | Definition
visual-group | Visual Group | Any group marked with this behavior should be displayed as a visual group to the end user.
logical-group | Logical Group | A group with this behavior logically groups its sub-elements, and may be shown as a visual group to the end user, but it is not required to do so.
sentence-group | Sentence Group | A group of related alternative actions is a sentence group if the target referenced by the action is the same in all the actions and each action simply constitutes a different variation on how to specify the details for the target. For example, two actions that could be in a SentenceGroup are "aspirin, 500 mg, 2 times per day" and "aspirin, 300 mg, 3 times per day". In both cases, aspirin is the target referenced by the action, and the two actions represent different options for how aspirin might be ordered for the patient. Note that a SentenceGroup would almost always have an associated selection behavior of "AtMostOne", unless it's a required action, in which case, it would be "ExactlyOne".

See the full registry of code systems defined as part of FHIR.

Explanation of the columns that may appear on this page:

Level | A few code lists that FHIR defines are hierarchical - each code is assigned a level. See Code System for further information.
Source | The source of the definition of the code (when the value set draws in codes defined elsewhere)
Code | The code (used as the code in the resource instance). If the code is in italics, this indicates that the code is not selectable ('Abstract')
Display | The display (used in the display element of a Coding). If there is no display, implementers should not simply display the code, but map the concept into their application
Definition | An explanation of the meaning of the concept
Comments | Additional notes about how to use the code

4.3.14.308 Code System http://terminology.hl7.org/CodeSystem/claim-exception

URL: https://hl7.org/fhir/R4/codesystem-claim-exception.html
Financial Management Work Group | Maturity Level: 1 | Draft | Use Context: Any

This is a code system defined by the FHIR project.

Summary

Defining URL: | http://terminology.hl7.org/CodeSystem/claim-exception
Version: | 4.0.1
Name: | ExceptionCodes
Title: | Exception Codes
Definition: | This value set includes sample Exception codes.
Committee: | Financial Management Work Group
OID: | 2.16.840.1.113883.4.642.4.1162 (for OID based terminology systems)
Copyright: | This is an example set.
Source Resource | XML / JSON

This Code system is used in the following value sets:

• ValueSet: Exception Codes (This value set includes sample Exception codes.)

• ValueSet: Exception Codes (This value set includes sample Exception codes.)

4.3.14.308.1 Content

4.3.14.308.2 Exception Codes

This value set includes sample Exception codes.

Copyright Statement:

This is an example set.

This code system http://terminology.hl7.org/CodeSystem/claim-exception defines the following codes:

Code | Display | Definition
student | Student (Fulltime) | Fulltime Student
disabled | Disabled | Disabled

See the full registry of code systems defined as part of FHIR.

Explanation of the columns that may appear on this page:

Level | A few code lists that FHIR defines are hierarchical - each code is assigned a level. See Code System for further information.
Source | The source of the definition of the code (when the value set draws in codes defined elsewhere)
Code | The code (used as the code in the resource instance). If the code is in italics, this indicates that the code is not selectable ('Abstract')
Display | The display (used in the display element of a Coding). If there is no display, implementers should not simply display the code, but map the concept into their application
Definition | An explanation of the meaning of the concept
Comments | Additional notes about how to use the code

4.3.14.309 Code System http://hl7.org/fhir/map-model-mode

URL: https://hl7.org/fhir/R4/codesystem-map-model-mode.html
FHIR Infrastructure Work Group | Maturity Level: 2 | Trial Use | Use Context: Any

This is a code system defined by the FHIR project.

Summary

Defining URL: | http://hl7.org/fhir/map-model-mode
Version: | 4.0.1
Name: | StructureMapModelMode
Title: | StructureMapModelMode
Definition: | How the referenced structure is used in this mapping.
Committee: | FHIR Infrastructure Work Group
OID: | 2.16.840.1.113883.4.642.4.676 (for OID based terminology systems)
Source Resource | XML / JSON

This Code system is used in the following value sets:

• ValueSet: StructureMapModelMode (How the referenced structure is used in this mapping.)

• ValueSet: StructureMapModelMode (How the referenced structure is used in this mapping.)

4.3.14.309.1 Content

4.3.14.309.2 StructureMapModelMode

How the referenced structure is used in this mapping.

This code system http://hl7.org/fhir/map-model-mode defines the following codes:

Code | Display | Definition
source | Source Structure Definition | This structure describes an instance passed to the mapping engine that is used a source of data.
queried | Queried Structure Definition | This structure describes an instance that the mapping engine may ask for that is used a source of data.
target | Target Structure Definition | This structure describes an instance passed to the mapping engine that is used a target of data.
produced | Produced Structure Definition | This structure describes an instance that the mapping engine may ask to create that is used a target of data.

See the full registry of code systems defined as part of FHIR.

Explanation of the columns that may appear on this page:

Level | A few code lists that FHIR defines are hierarchical - each code is assigned a level. See Code System for further information.
Source | The source of the definition of the code (when the value set draws in codes defined elsewhere)
Code | The code (used as the code in the resource instance). If the code is in italics, this indicates that the code is not selectable ('Abstract')
Display | The display (used in the display element of a Coding). If there is no display, implementers should not simply display the code, but map the concept into their application
Definition | An explanation of the meaning of the concept
Comments | Additional notes about how to use the code

4.3.14.310 Code System http://terminology.hl7.org/CodeSystem/immunization-funding-source

URL: https://hl7.org/fhir/R4/codesystem-immunization-funding-source.html
Public Health and Emergency Response Work Group | Maturity Level: 1 | Draft | Use Context: Any

This is a code system defined at http://www.hl7.org/Special/committees/pher/index.cfm .

Summary

Defining URL: | http://terminology.hl7.org/CodeSystem/immunization-funding-source
Version: | 4.0.1
Name: | ImmunizationFundingSource
Title: | Immunization Funding Source
Definition: | The value set to instantiate this attribute should be drawn from a terminologically robust code system that consists of or contains concepts to support describing the source of the vaccine administered. This value set is provided as a suggestive example.
Committee: | Public Health and Emergency Response Work Group
OID: | 2.16.840.1.113883.4.642.4.1100 (for OID based terminology systems)
Source Resource | XML / JSON

This Code system is used in the following value sets:

• ValueSet: Immunization Funding Source (The value set to instantiate this attribute should be drawn from a terminologically robust code system that consists of or contains concepts to support describing the source of the vaccine administered. This value set is provided as a suggestive example.)

• ValueSet: Immunization Funding Source (The value set to instantiate this attribute should be drawn from a terminologically robust code system that consists of or contains concepts to support describing the source of the vaccine administered. This value set is provided as a suggestive example.)

4.3.14.310.1 Content

4.3.14.310.2 Immunization Funding Source

The value set to instantiate this attribute should be drawn from a terminologically robust code system that consists of or contains concepts to support describing the source of the vaccine administered. This value set is provided as a suggestive example.

This code system http://terminology.hl7.org/CodeSystem/immunization-funding-source defines the following codes:

Code | Display | Definition
private | Private | The vaccine was purchased with private funds.
public | Public | The vaccine was purchased with public funds.

See the full registry of code systems defined as part of FHIR.

Explanation of the columns that may appear on this page:

Level | A few code lists that FHIR defines are hierarchical - each code is assigned a level. See Code System for further information.
Source | The source of the definition of the code (when the value set draws in codes defined elsewhere)
Code | The code (used as the code in the resource instance). If the code is in italics, this indicates that the code is not selectable ('Abstract')
Display | The display (used in the display element of a Coding). If there is no display, implementers should not simply display the code, but map the concept into their application

Definition | An explanation of the meaning of the concept
Comments | Additional notes about how to use the code

4.3.14.311 Code System http://hl7.org/fhir/imagingstudy-status

URL: https://hl7.org/fhir/R4/codesystem-imagingstudy-status.html
Imaging Integration Work Group | Maturity Level: 3 | Trial Use | Use Context: Any

This is a code system defined by the FHIR project.

Summary

Defining URL: | http://hl7.org/fhir/imagingstudy-status
Version: | 4.0.1
Name: | ImagingStudyStatus
Title: | ImagingStudyStatus
Definition: | The status of the ImagingStudy.
Committee: | Imaging Integration Work Group
OID: | 2.16.840.1.113883.4.642.4.991 (for OID based terminology systems)
Source Resource | XML / JSON

This Code system is used in the following value sets:

• ValueSet: ImagingStudyStatus (The status of the ImagingStudy.)

• ValueSet: ImagingStudyStatus (The status of the ImagingStudy.)

4.3.14.311.1 Content

4.3.14.311.2 ImagingStudyStatus

The status of the ImagingStudy.

This code system http://hl7.org/fhir/imagingstudy-status defines the following codes:

Code | Display | Definition
registered | Registered | The existence of the imaging study is registered, but there is nothing yet available.
available | Available | At least one instance has been associated with this imaging study.
cancelled | Cancelled | The imaging study is unavailable because the imaging study was not started or not completed (also sometimes called "aborted").
entered-in-error | Entered in Error | The imaging study has been withdrawn following a previous final release. This electronic record should never have existed, though it is possible that real-world decisions were based on it. (If real-world activity has occurred, the status should be "cancelled" rather than "entered-in-error".).
unknown | Unknown | The system does not know which of the status values currently applies for this request. Note: This concept is not to be used for "other" - one of the listed statuses is presumed to apply, it's just not known which one.

See the full registry of code systems defined as part of FHIR.

Explanation of the columns that may appear on this page:

Level | A few code lists that FHIR defines are hierarchical - each code is assigned a level. See Code System for further information.
Source | The source of the definition of the code (when the value set draws in codes defined elsewhere)
Code | The code (used as the code in the resource instance). If the code is in italics, this indicates that the code is not selectable ('Abstract')
Display | The display (used in the display element of a Coding). If there is no display, implementers should not simply display the code, but map the concept into their application
Definition | An explanation of the meaning of the concept
Comments | Additional notes about how to use the code

4.3.14.312 Code System http://terminology.hl7.org/CodeSystem/observation-statistics

URL: https://hl7.org/fhir/R4/codesystem-observation-statistics.html
Vocabulary Work Group | Maturity Level: 0 | Informative | Use Context: Any

This is a code system defined by the FHIR project.

Summary

Defining URL: | http://terminology.hl7.org/CodeSystem/observation-statistics
Version: | 4.0.1
Name: | StatisticsCode
Title: | StatisticsCode
Definition: | The statistical operation parameter -"statistic" codes.
Committee: | ??
OID: | 2.16.840.1.113883.4.642.4.1126 (for OID based terminology systems)
Source Resource | XML / JSON

This Code system is used in the following value sets:

• ValueSet: StatisticsCode (The statistical operation parameter -"statistic" codes.)
• ValueSet: StatisticsCode (The statistical operation parameter -"statistic" codes.)

4.3.14.312.1 Content

4.3.14.312.2 StatisticsCode

The statistical operation parameter -"statistic" codes.

This code system http://terminology.hl7.org/CodeSystem/observation-statistics defines the following codes:

Code | Display | Definition
average | Average | The [mean](https://en.wikipedia.org/wiki/Arithmetic_mean) of N measurements over the stated period.
maximum | Maximum | The [maximum](https://en.wikipedia.org/wiki/Maximal_element) value of N measurements over the stated period.
minimum | Minimum | The [minimum](https://en.wikipedia.org/wiki/Minimal_element) value of N measurements over the stated period.
count | Count | The [number] of valid measurements over the stated period that contributed to the other statistical outputs.
total-count | Total Count | The total [number] of valid measurements over the stated period, including observations that were ignored because they did not contain valid result values.
median | Median | The [median](https://en.wikipedia.org/wiki/Median) of N measurements over the stated period.
std-dev | Standard Deviation | The [standard deviation](https://en.wikipedia.org/wiki/Standard_deviation) of N measurements over the stated period.
sum | Sum | The [sum](https://en.wikipedia.org/wiki/Summation) of N measurements over the stated period.
variance | Variance | The [variance](https://en.wikipedia.org/wiki/Variance) of N measurements over the stated period.
20-percent | 20th Percentile | The 20th [Percentile](https://en.wikipedia.org/wiki/Percentile) of N measurements over the stated period.
80-percent | 80th Percentile | The 80th [Percentile](https://en.wikipedia.org/wiki/Percentile) of N measurements over the stated period.
4-lower | Lower Quartile | The lower [Quartile](https://en.wikipedia.org/wiki/Quartile) Boundary of N measurements over the stated period.
4-upper | Upper Quartile | The upper [Quartile](https://en.wikipedia.org/wiki/Quartile) Boundary of N measurements over the stated period.
4-dev | Quartile Deviation | The difference between the upper and lower [Quartiles](https://en.wikipedia.org/wiki/Quartile) is called the Interquartile range. (IQR = Q3-Q1) Quartile deviation or Semi-interquartile range is one-half the difference between the first and the third quartiles.
5-1 | 1st Quintile | The lowest of four values that divide the N measurements into a frequency distribution of five classes with each containing one fifth of the total population.
5-2 | 2nd Quintile | The second of four values that divide the N measurements into a frequency distribution of five classes with each containing one fifth of the total population.
5-3 | 3rd Quintile | The third of four values that divide the N measurements into a frequency distribution of five classes with each containing one fifth of the total population.
5-4 | 4th Quintile | The fourth of four values that divide the N measurements into a frequency distribution of five classes with each containing one fifth of the total population.
skew | Skew | Skewness is a measure of the asymmetry of the probability distribution of a real-valued random variable about its mean. The skewness value can be positive or negative, or even undefined. Source: [Wikipedia](https://en.wikipedia.org/wiki/Skewness).
kurtosis | Kurtosis | Kurtosis is a measure of the "tailedness" of the probability distribution of a real-valued random variable. Source: [Wikipedia](https://en.wikipedia.org/wiki/Kurtosis).
regression | Regression | Linear regression is an approach for modeling two-dimensional sample points with one independent variable and one dependent variable (conventionally, the x and y coordinates in a Cartesian coordinate system) and finds a linear function (a non-vertical straight line) that, as accurately as possible, predicts the dependent variable values as a function of the independent variables. Source: [Wikipedia](https://en.wikipedia.org/wiki/Simple_linear_regression) This Statistic code will return both a gradient and an intercept value.

See the full registry of code systems defined as part of FHIR.

Explanation of the columns that may appear on this page:

Level | A few code lists that FHIR defines are hierarchical - each code is assigned a level. See Code System for further information.
Source | The source of the definition of the code (when the value set draws in codes defined elsewhere)
Code | The code (used as the code in the resource instance). If the code is in italics, this indicates that the code is not selectable ('Abstract')
Display | The display (used in the display element of a Coding). If there is no display, implementers should not simply display the code, but map the concept into their application
Definition | An explanation of the meaning of the concept
Comments | Additional notes about how to use the code

4.3.14.313 Code System http://terminology.hl7.org/CodeSystem/condition-category

URL: https://hl7.org/fhir/R4/codesystem-condition-category.html
Patient Care Work Group | Maturity Level: 3 | Trial Use | Use Context: Any

This is a code system defined by the FHIR project.

Summary

Defining URL: | http://terminology.hl7.org/CodeSystem/condition-category
Version: | 4.0.1
Name: | ConditionCategoryCodes
Title: | Condition Category Codes
Definition: | Preferred value set for Condition Categories.
Committee: | Patient Care Work Group
OID: | 2.16.840.1.113883.4.642.4.1073 (for OID based terminology systems)
Source Resource | XML / JSON

This Code system is used in the following value sets:

• ValueSet: Condition Category Codes (Preferred value set for Condition Categories.)

• ValueSet: Condition Category Codes (Preferred value set for Condition Categories.)

4.3.14.313.1 Content

4.3.14.313.2 Condition Category Codes

Preferred value set for Condition Categories.

This code system http://terminology.hl7.org/CodeSystem/condition-category defines the following codes:

Code | Display | Definition
problem-list-item | Problem List Item | An item on a problem list that can be managed over time and can be expressed by a practitioner (e.g. physician, nurse), patient, or related person.
encounter-diagnosis | Encounter Diagnosis | A point in time diagnosis (e.g. from a physician or nurse) in context of an encounter.

See the full registry of code systems defined as part of FHIR.

Explanation of the columns that may appear on this page:

Level | A few code lists that FHIR defines are hierarchical - each code is assigned a level. See Code System for further information.
Source | The source of the definition of the code (when the value set draws in codes defined elsewhere)
Code | The code (used as the code in the resource instance). If the code is in italics, this indicates that the code is not selectable ('Abstract')
Display | The display (used in the display element of a Coding). If there is no display, implementers should not simply display the code, but map the concept into their application
Definition | An explanation of the meaning of the concept
Comments | Additional notes about how to use the code

4.3.14.314 Code System http://terminology.hl7.org/CodeSystem/admit-source

URL: https://hl7.org/fhir/R4/codesystem-encounter-admit-source.html
Patient Administration Work Group | Maturity Level: 0 | Informative | Use Context: Any

This is a code system defined by the FHIR project.

Summary

Defining URL: | http://terminology.hl7.org/CodeSystem/admit-source
Version: | 4.0.1
Name: | AdmitSource
Title: | Admit source
Definition: | This value set defines a set of codes that can be used to indicate from where the patient came in.
Committee: | Patient Administration Work Group
OID: | 2.16.840.1.113883.4.642.4.1092 (for OID based terminology systems)
Source Resource | XML / JSON

This Code system is used in the following value sets:

• ValueSet: Admit source (This value set defines a set of codes that can be used to indicate from where the patient came in.)

• ValueSet: Admit source (This value set defines a set of codes that can be used to indicate from where the patient came in.)

4.3.14.314.1 Content

4.3.14.314.2 Admit source

This value set defines a set of codes that can be used to indicate from where the patient came in.

This code system http://terminology.hl7.org/CodeSystem/admit-source defines the following codes:

Code | Display | Definition
hosp-trans | Transferred from other hospital | The Patient has been transferred from another hospital for this encounter.
emd | From accident/emergency department | The patient has been transferred from the emergency department within the hospital. This is typically used in the transition to an inpatient encounter
outp | From outpatient department | The patient has been transferred from an outpatient department within the hospital.

born | Born in hospital | The patient is a newborn and the encounter will track the baby related activities (as opposed to the Mothers encounter - that may be associated using the newborn encounters partof property)
gp | General Practitioner referral | The patient has been admitted due to a referred from a General Practitioner.
mp | Medical Practitioner/physician referral | The patient has been admitted due to a referred from a Specialist (as opposed to a General Practitioner).
nursing | From nursing home | The patient has been transferred from a nursing home.
psych | From psychiatric hospital | The patient has been transferred from a psychiatric facility.
rehab | From rehabilitation facility | The patient has been transferred from a rehabilitation facility or clinic.
other | Other | The patient has been admitted from a source otherwise not specified here.

See the full registry of code systems defined as part of FHIR.

Explanation of the columns that may appear on this page:

Level | A few code lists that FHIR defines are hierarchical - each code is assigned a level. See Code System for further information.
Source | The source of the definition of the code (when the value set draws in codes defined elsewhere)
Code | The code (used as the code in the resource instance). If the code is in italics, this indicates that the code is not selectable ('Abstract')
Display | The display (used in the display element of a Coding). If there is no display, implementers should not simply display the code, but map the concept into their application
Definition | An explanation of the meaning of the concept
Comments | Additional notes about how to use the code

4.3.14.315 Code System http://terminology.hl7.org/CodeSystem/effect-estimate-type

URL: https://hl7.org/fhir/R4/codesystem-effect-estimate-type.html
Clinical Decision Support Work Group | Maturity Level: 0 | Trial Use | Use Context: Any

This is a code system defined by the FHIR project.

Summary

Defining URL: | http://terminology.hl7.org/CodeSystem/effect-estimate-type
Version: | 4.0.1
Name: | EffectEstimateType
Title: | EffectEstimateType
Definition: | Whether the effect estimate is an absolute effect estimate (absolute difference) or a relative effect estimate (relative difference), and the specific type of effect estimate (eg relative risk or median difference).
Committee: | Clinical Decision Support Work Group
OID: | 2.16.840.1.113883.4.642.4.1356 (for OID based terminology systems)
Source Resource | XML / JSON

This Code system is used in the following value sets:

• ValueSet: EffectEstimateType (Whether the effect estimate is an absolute effect estimate (absolute difference) or a relative effect estimate (relative difference), and the specific type of effect estimate (eg relative risk or median difference).)

• ValueSet: EffectEstimateType (Whether the effect estimate is an absolute effect estimate (absolute difference) or a relative effect estimate (relative difference), and the specific type of effect estimate (eg relative risk or median difference).)

4.3.14.315.1 Content

4.3.14.315.2 EffectEstimateType

Whether the effect estimate is an absolute effect estimate (absolute difference) or a relative effect estimate (relative difference), and the specific type of effect estimate (eg relative risk or median difference).

This code system http://terminology.hl7.org/CodeSystem/effect-estimate-type defines the following codes:

Code | Display | Definition
relative-RR | relative risk | relative risk (a type of relative effect estimate).
relative-OR | odds ratio | odds ratio (a type of relative effect estimate).
relative-HR | hazard ratio | hazard ratio (a type of relative effect estimate).
absolute-ARD | absolute risk difference | absolute risk difference (a type of absolute effect estimate).
absolute-MeanDiff | mean difference | mean difference (a type of absolute effect estimate).
absolute-SMD | standardized mean difference | standardized mean difference (a type of absolute effect estimate).
absolute-MedianDiff | median difference | median difference (a type of absolute effect estimate).

See the full registry of code systems defined as part of FHIR.

Explanation of the columns that may appear on this page:

Level | A few code lists that FHIR defines are hierarchical - each code is assigned a level. See Code System for further information.
Source | The source of the definition of the code (when the value set draws in codes defined elsewhere)
Code | The code (used as the code in the resource instance). If the code is in italics, this indicates that the code is not selectable ('Abstract')
Display | The display (used in the display element of a Coding). If there is no display, implementers should not simply display the code, but map the concept into their application

Definition | An explanation of the meaning of the concept
Comments | Additional notes about how to use the code

4.3.14.316 Code System http://hl7.org/fhir/composition-status

URL: https://hl7.org/fhir/R4/codesystem-composition-status.html
Structured Documents Work Group | Maturity Level: 3 | Trial Use | Use Context: Any

This is a code system defined by the FHIR project.

Summary

Defining URL: | http://hl7.org/fhir/composition-status
Version: | 4.0.1
Name: | CompositionStatus
Title: | CompositionStatus
Definition: | The workflow/clinical status of the composition.
Committee: | Structured Documents Work Group
OID: | 2.16.840.1.113883.4.642.4.242 (for OID based terminology systems)
Source Resource | XML / JSON

This Code system is used in the following value sets:

• ValueSet: CompositionStatus (The workflow/clinical status of the composition.)

• ValueSet: CompositionStatus (The workflow/clinical status of the composition.)

4.3.14.316.1 Content

4.3.14.316.2 CompositionStatus

The workflow/clinical status of the composition.

This code system http://hl7.org/fhir/composition-status defines the following codes:

Code | Display | Definition
preliminary | Preliminary | This is a preliminary composition or document (also known as initial or interim). The content may be incomplete or unverified.
final | Final | This version of the composition is complete and verified by an appropriate person and no further work is planned. Any subsequent updates would be on a new version of the composition.
amended | Amended | The composition content or the referenced resources have been modified (edited or added to) subsequent to being released as "final" and the composition is complete and verified by an authorized person.
entered-in-error | Entered in Error | The composition or document was originally created/issued in error, and this is an amendment that marks that the entire series should not be considered as valid.

See the full registry of code systems defined as part of FHIR.

Explanation of the columns that may appear on this page:

Level | A few code lists that FHIR defines are hierarchical - each code is assigned a level. See Code System for further information.
Source | The source of the definition of the code (when the value set draws in codes defined elsewhere)
Code | The code (used as the code in the resource instance). If the code is in italics, this indicates that the code is not selectable ('Abstract')
Display | The display (used in the display element of a Coding). If there is no display, implementers should not simply display the code, but map the concept into their application
Definition | An explanation of the meaning of the concept
Comments | Additional notes about how to use the code

4.3.14.317 Code System http://hl7.org/fhir/procedure-progress-status-code

URL: https://hl7.org/fhir/R4/codesystem-procedure-progress-status-codes.html
Vocabulary Work Group | Maturity Level: 0 | Informative | Use Context: Any

This is a code system defined by the FHIR project.

Summary

Defining URL: | http://hl7.org/fhir/procedure-progress-status-code
Version: | 4.0.1
Name: | ProcedureProgressStatusCodes
Title: | Procedure Progress Status Codes
Definition: | This value set is provided as an example. The value set to instantiate this attribute should be drawn from a robust terminology code system that consists of or contains concepts to support the procedure performance process.
Committee: | ??
OID: | 2.16.840.1.113883.4.642.4.947 (for OID based terminology systems)
Source Resource | XML / JSON

This Code system is used in the following value sets:

• ValueSet: Procedure Progress Status Codes (This value set is provided as an example. The value set to instantiate this attribute should be drawn from a robust terminology code system that consists of or contains

concepts to support the procedure performance process.)

• ValueSet: Procedure Progress Status Codes (This value set is provided as an example. The value set to instantiate this attribute should be drawn from a robust terminology code system that consists of or contains concepts to support the procedure performance process.)

4.3.14.317.1 Content

4.3.14.317.2 Procedure Progress Status Codes

This value set is provided as an example. The value set to instantiate this attribute should be drawn from a robust terminology code system that consists of or contains concepts to support the procedure performance process.

This code system http://hl7.org/fhir/procedure-progress-status-code defines the following codes:

Code | Display | Definition
in-operating-room | In Operating Room | A patient is in the Operating Room.
prepared | Prepared | The patient is prepared for a procedure.
anesthesia-induced | Anesthesia Induced | The patient is under anesthesia.
open-incision | Open Incision | The patient has open incision(s).
closed-incision | Closed Incision | The patient has incision(s) closed.
in-recovery-room | In Recovery Room | The patient is in the recovery room.

See the full registry of code systems defined as part of FHIR.

Explanation of the columns that may appear on this page:

Level | A few code lists that FHIR defines are hierarchical - each code is assigned a level. See Code System for further information.
Source | The source of the definition of the code (when the value set draws in codes defined elsewhere)
Code | The code (used as the code in the resource instance). If the code is in italics, this indicates that the code is not selectable ('Abstract')
Display | The display (used in the display element of a Coding). If there is no display, implementers should not simply display the code, but map the concept into their application
Definition | An explanation of the meaning of the concept
Comments | Additional notes about how to use the code

4.3.14.318 Code System http://terminology.hl7.org/CodeSystem/implantStatus

URL: https://hl7.org/fhir/R4/codesystem-implantStatus.html
Vocabulary Work Group | Maturity Level: 0 | Informative | Use Context: Any

This is a code system defined by the FHIR project.

Summary

Defining URL: | http://terminology.hl7.org/CodeSystem/implantStatus
Version: | 4.0.1
Name: | Implant Status
Title: | Implant Status
Definition: | A set codes that define the functional status of an implanted device.
Committee: | ??
OID: | 2.16.840.1.113883.4.642.4.1283 (for OID based terminology systems)
Source Resource | XML / JSON

This Code system is used in the following value sets:

• ValueSet: Implant Status (A set codes that define the functional status of an implanted device.)

• ValueSet: Implant Status (A set codes that define the functional status of an implanted device.)

4.3.14.318.1 Content

4.3.14.318.2 Implant Status

A set codes that define the functional status of an implanted device.

This code system http://terminology.hl7.org/CodeSystem/implantStatus defines the following codes:

Code | Display | Definition
functional | Functional | The implanted device is working normally.
non-functional | Non-Functional | The implanted device is not working.
disabled | Disabled | The implanted device has been turned off.
unknown | Unknown | the functional status of the implant has not been determined.

See the full registry of code systems defined as part of FHIR.

Explanation of the columns that may appear on this page:

Level | A few code lists that FHIR defines are hierarchical - each code is assigned a level. See Code System for further information.
Source | The source of the definition of the code (when the value set draws in codes defined elsewhere)

Code | The code (used as the code in the resource instance). If the code is in italics, this indicates that the code is not selectable ('Abstract')
Display | The display (used in the display element of a Coding). If there is no display, implementers should not simply display the code, but map the concept into their application
Definition | An explanation of the meaning of the concept
Comments | Additional notes about how to use the code

4.3.14.319 Code System http://terminology.hl7.org/CodeSystem/study-type

URL: https://hl7.org/fhir/R4/codesystem-study-type.html
Clinical Decision Support Work Group | Maturity Level: 0 | Trial Use | Use Context: Any

This is a code system defined by the FHIR project.

Summary

Defining URL: | http://terminology.hl7.org/CodeSystem/study-type
Version: | 4.0.1
Name: | StudyType
Title: | StudyType
Definition: | Types of research studies (types of research methods).
Committee: | Clinical Decision Support Work Group
OID: | 2.16.840.1.113883.4.642.4.1350 (for OID based terminology systems)
Source Resource | XML / JSON

This Code system is used in the following value sets:

• ValueSet: StudyType (Types of research studies (types of research methods).)
• ValueSet: StudyType (Types of research studies (types of research methods).)

4.3.14.319.1 Content

4.3.14.319.2 StudyType

Types of research studies (types of research methods).

This code system http://terminology.hl7.org/CodeSystem/study-type defines the following codes:

Code | Display | Definition
RCT | randomized trial | randomized controlled trial.
CCT | controlled trial (non-randomized) | controlled (but not randomized) trial.
cohort | comparative cohort study | observational study comparing cohorts.
case-control | case-control study | case-control study.
series | uncontrolled cohort or case series | uncontrolled cohort or case series.
case-report | case report | a single case report.
mixed | mixed methods | a combination of 1 or more types of studies.

See the full registry of code systems defined as part of FHIR.

Explanation of the columns that may appear on this page:

Level | A few code lists that FHIR defines are hierarchical - each code is assigned a level. See Code System for further information.
Source | The source of the definition of the code (when the value set draws in codes defined elsewhere)
Code | The code (used as the code in the resource instance). If the code is in italics, this indicates that the code is not selectable ('Abstract')
Display | The display (used in the display element of a Coding). If there is no display, implementers should not simply display the code, but map the concept into their application
Definition | An explanation of the meaning of the concept
Comments | Additional notes about how to use the code

4.3.14.320 Code System http://hl7.org/fhir/concept-map-equivalence

URL: https://hl7.org/fhir/R4/codesystem-concept-map-equivalence.html
FHIR Infrastructure Work Group | Maturity Level: 3 | Trial Use | Use Context: Any

This is a code system defined by the FHIR project.

Summary

Defining URL: | http://hl7.org/fhir/concept-map-equivalence
Version: | 4.0.1
Name: | ConceptMapEquivalence
Title: | ConceptMapEquivalence
Definition: | The degree of equivalence between concepts.
Committee: | FHIR Infrastructure Work Group
OID: | 2.16.840.1.113883.4.642.4.18 (for OID based terminology systems)
Source Resource | XML / JSON

This Code system is used in the following value sets:

• ValueSet: ConceptMapEquivalence (The degree of equivalence between concepts.)

• ValueSet: ConceptMapEquivalence (The degree of equivalence between concepts.)

4.3.14.320.1 Content

4.3.14.320.2 ConceptMapEquivalence

The degree of equivalence between concepts.

This code system http://hl7.org/fhir/concept-map-equivalence defines the following codes:

Lvl | Code | Display | Definition
1 | relatedto | Related To | The concepts are related to each other, and have at least some overlap in meaning, but the exact relationship is not known.
2 | equivalent | Equivalent | The definitions of the concepts mean the same thing (including when structural implications of meaning are considered) (i.e. extensionally identical).
3 | equal | Equal | The definitions of the concepts are exactly the same (i.e. only grammatical differences) and structural implications of meaning are identical or irrelevant (i.e. intentionally identical).
2 | wider | Wider | The target mapping is wider in meaning than the source concept.
2 | subsumes | Subsumes | The target mapping subsumes the meaning of the source concept (e.g. the source is-a target).
2 | narrower | Narrower | The target mapping is narrower in meaning than the source concept. The sense in which the mapping is narrower SHALL be described in the comments in this case, and applications should be careful when attempting to use these mappings operationally.
2 | specializes | Specializes | The target mapping specializes the meaning of the source concept (e.g. the target is-a source).
2 | inexact | Inexact | The target mapping overlaps with the source concept, but both source and target cover additional meaning, or the definitions are imprecise and it is uncertain whether they have the same boundaries to their meaning. The sense in which the mapping is inexact SHALL be described in the comments in this case, and applications should be careful when attempting to use these mappings operationally.
1 | unmatched | Unmatched | There is no match for this concept in the target code system.
2 | disjoint | Disjoint | This is an explicit assertion that there is no mapping between the source and target concept.

See the full registry of code systems defined as part of FHIR.

Explanation of the columns that may appear on this page:

Level | A few code lists that FHIR defines are hierarchical - each code is assigned a level. See Code System for further information.
Source | The source of the definition of the code (when the value set draws in codes defined elsewhere)
Code | The code (used as the code in the resource instance). If the code is in italics, this indicates that the code is not selectable ('Abstract')
Display | The display (used in the display element of a Coding). If there is no display, implementers should not simply display the code, but map the concept into their application
Definition | An explanation of the meaning of the concept
Comments | Additional notes about how to use the code

4.3.14.321 Code System http://terminology.hl7.org/CodeSystem/medicationrequest-status-reason

URL: https://hl7.org/fhir/R4/codesystem-medicationrequest-status-reason.html
Pharmacy Work Group | Maturity Level: 1 | Draft | Use Context: Any

This is a code system defined by the FHIR project.

Summary

Defining URL: | http://terminology.hl7.org/CodeSystem/medicationrequest-status-reason
Version: | 4.0.1
Name: | medicationRequest Status Reason Codes
Title: | Medication request status reason codes
Definition: | MedicationRequest Status Reason Codes
Committee: | Pharmacy Work Group
OID: | 2.16.840.1.113883.4.642.4.1325 (for OID based terminology systems)
Source Resource | XML / JSON

This Code system is used in the following value sets:

• ValueSet: Medication request status reason codes (MedicationRequest Status Reason Codes)

• ValueSet: Medication request status reason codes (MedicationRequest Status Reason Codes)

4.3.14.321.1 Content

4.3.14.321.2 Medication request status reason codes

MedicationRequest Status Reason Codes

This code system http://terminology.hl7.org/CodeSystem/medicationrequest-status-reason defines the following codes:

Code | Display | Definition

altchoice | Try another treatment first | This therapy has been ordered as a backup to a preferred therapy. This order will be released when and if the preferred therapy is unsuccessful.
clarif | Prescription requires clarification | Clarification is required before the order can be acted upon.
drughigh | Drug level too high | The current level of the medication in the patient's system is too high. The medication is suspended to allow the level to subside to a safer level.
hospadm | Admission to hospital | The patient has been admitted to a care facility and their community medications are suspended until hospital discharge.
labint | Lab interference issues | The therapy would interfere with a planned lab test and the therapy is being withdrawn until the test is completed.
non-avail | Patient not available | Patient not available for a period of time due to a scheduled therapy, leave of absence or other reason.
preg | Parent is pregnant/breast feeding | The patient is pregnant or breast feeding. The therapy will be resumed when the pregnancy is complete and the patient is no longer breastfeeding.
salg | Allergy | The patient is believed to be allergic to a substance that is part of the therapy and the therapy is being temporarily withdrawn to confirm.
sddi | Drug interacts with another drug | The drug interacts with a short-term treatment that is more urgently required. This order will be resumed when the short-term treatment is complete.
sdupther | Duplicate therapy | The drug interacts with a short-term treatment that is more urgently required. This order will be resumed when the short-term treatment is complete.
sintol | Suspected intolerance | The drug interacts with a short-term treatment that is more urgently required. This order will be resumed when the short-term treatment is complete.
surg | Patient scheduled for surgery. | The drug is contraindicated for patients receiving surgery and the patient is scheduled to be admitted for surgery in the near future. The drug will be resumed when the patient has sufficiently recovered from the surgery.
washout | Waiting for old drug to wash out | The patient was previously receiving a medication contraindicated with the current medication. The current medication will remain on hold until the prior medication has been cleansed from their system.

See the full registry of code systems defined as part of FHIR.

Explanation of the columns that may appear on this page:

Level | A few code lists that FHIR defines are hierarchical - each code is assigned a level. See Code System for further information.
Source | The source of the definition of the code (when the value set draws in codes defined elsewhere)
Code | The code (used as the code in the resource instance). If the code is in italics, this indicates that the code is not selectable ('Abstract')
Display | The display (used in the display element of a Coding). If there is no display, implementers should not simply display the code, but map the concept into their application
Definition | An explanation of the meaning of the concept
Comments | Additional notes about how to use the code

4.3.14.322 Code System http://terminology.hl7.org/CodeSystem/entformula-additive

URL: https://hl7.org/fhir/R4/codesystem-entformula-additive.html
Orders and Observations Work Group | Maturity Level: 1 | Draft | Use Context: Any

This is a code system defined by the FHIR project.

Summary

Defining URL: | http://terminology.hl7.org/CodeSystem/entformula-additive
Version: | 4.0.1
Name: | EnteralFormulaAdditiveTypeCode
Title: | Enteral Formula Additive Type Code
Definition: | EnteralFormulaAdditiveType: Codes for the type of modular component such as protein, carbohydrate or fiber to be provided in addition to or mixed with the base formula. This value set is provided as a suggestive example.
Committee: | Orders and Observations Work Group
OID: | 2.16.840.1.113883.4.642.4.1123 (for OID based terminology systems)
Source Resource | XML / JSON

This Code system is used in the following value sets:

• ValueSet: Enteral Formula Additive Type Code (EnteralFormulaAdditiveType: Codes for the type of modular component such as protein, carbohydrate or fiber to be provided in addition to or mixed with the base formula. This value set is provided as a suggestive example.)

• ValueSet: Enteral Formula Additive Type Code (EnteralFormulaAdditiveType: Codes for the type of modular component such as protein, carbohydrate or fiber to be provided in addition to or mixed with the base formula. This value set is provided as a suggestive example.)

4.3.14.322.1 Content

4.3.14.322.2 Enteral Formula Additive Type Code

EnteralFormulaAdditiveType: Codes for the type of modular component such as protein, carbohydrate or fiber to be provided in addition to or mixed with the base formula. This value set is provided as a suggestive example.

This code system http://terminology.hl7.org/CodeSystem/entformula-additive defines the following codes:

Code | Display | Definition
lipid | Lipid | Modular lipid enteral formula component
protein | Protein | Modular protein enteral formula component
carbohydrate | Carbohydrate | Modular carbohydrate enteral formula component
fiber | Fiber | Modular fiber enteral formula component
water | Water | Added water

See the full registry of code systems defined as part of FHIR.

Explanation of the columns that may appear on this page:

Level | A few code lists that FHIR defines are hierarchical - each code is assigned a level. See Code System for further information.
Source | The source of the definition of the code (when the value set draws in codes defined elsewhere)
Code | The code (used as the code in the resource instance). If the code is in italics, this indicates that the code is not selectable ('Abstract')
Display | The display (used in the display element of a Coding). If there is no display, implementers should not simply display the code, but map the concept into their application
Definition | An explanation of the meaning of the concept
Comments | Additional notes about how to use the code

4.3.14.323 Code System http://terminology.hl7.org/CodeSystem/dicom-audit-lifecycle

URL: https://hl7.org/fhir/R4/codesystem-dicom-audit-lifecycle.html
Vocabulary Work Group | Maturity Level: 0 | Informative | Use Context: Any

This is a code system defined by the FHIR project.

Summary

Defining URL: | http://terminology.hl7.org/CodeSystem/dicom-audit-lifecycle
Version: | 20100826
Name: | DICOM Audit Message Record Lifecycle Events
Title:
Definition: | Attached is vocabulary for the record lifecycle events, as per DICOM Audit Message,
Committee: | ??
OID: | (for OID based terminology systems)
Copyright: | These codes are excerpted from Digital Imaging and Communications in Medicine (DICOM) Standard, Part 16: Content Mapping Resource, Copyright © 2011 by the National Electrical Manufacturers Association.
Source Resource | XML / JSON

This Code system is not currently used

4.3.14.323.1 Content

4.3.14.323.2 DICOM Audit Message Record Lifecycle Events

Attached is vocabulary for the record lifecycle events, as per DICOM Audit Message,

Copyright Statement:

These codes are excerpted from Digital Imaging and Communications in Medicine (DICOM) Standard, Part 16: Content Mapping Resource, Copyright © 2011 by the National Electrical Manufacturers Association.

This code system http://terminology.hl7.org/CodeSystem/dicom-audit-lifecycle defines the following codes:

Code | Display | Definition
1 | Origination / Creation
2 | Import / Copy
3 | Amendment
4 | Verification
5 | Translation
6 | Access / Use
7 | De-identification
8 | Aggregation / summarization / derivation
9 | Report
10 | Export
11 | Disclosure
12 | Receipt of disclosure
13 | Archiving
14 | Logical deletion
15 | Permanent erasure / Physical destruction

See the full registry of code systems defined as part of FHIR.

Explanation of the columns that may appear on this page:

Level | A few code lists that FHIR defines are hierarchical - each code is assigned a level. See Code System for further information.
Source | The source of the definition of the code (when the value set draws in codes defined elsewhere)
Code | The code (used as the code in the resource instance). If the code is in italics, this indicates that the code is not selectable ('Abstract')

Display | The display (used in the display element of a Coding). If there is no display, implementers should not simply display the code, but map the concept into their application
Definition | An explanation of the meaning of the concept
Comments | Additional notes about how to use the code

4.3.14.324 Code System http://hl7.org/fhir/identity-assuranceLevel

URL: https://hl7.org/fhir/R4/codesystem-identity-assuranceLevel.html
Patient Administration Work Group | Maturity Level: 2 | Trial Use | Use Context: Any

This is a code system defined by the FHIR project.

Summary

Defining URL: | http://hl7.org/fhir/identity-assuranceLevel
Version: | 4.0.1
Name: | IdentityAssuranceLevel
Title: | IdentityAssuranceLevel
Definition: | The level of confidence that this link represents the same actual person, based on NIST Authentication Levels.
Committee: | Patient Administration Work Group
OID: | 2.16.840.1.113883.4.642.4.657 (for OID based terminology systems)
Source Resource | XML / JSON

This Code system is used in the following value sets:

• ValueSet: IdentityAssuranceLevel (The level of confidence that this link represents the same actual person, based on NIST Authentication Levels.)

• ValueSet: IdentityAssuranceLevel (The level of confidence that this link represents the same actual person, based on NIST Authentication Levels.)

4.3.14.324.1 Content

4.3.14.324.2 IdentityAssuranceLevel

The level of confidence that this link represents the same actual person, based on NIST Authentication Levels.

This code system http://hl7.org/fhir/identity-assuranceLevel defines the following codes:

Code | Display | Definition
level1 | Level 1 | Little or no confidence in the asserted identity's accuracy.
level2 | Level 2 | Some confidence in the asserted identity's accuracy.
level3 | Level 3 | High confidence in the asserted identity's accuracy.
level4 | Level 4 | Very high confidence in the asserted identity's accuracy.

See the full registry of code systems defined as part of FHIR.

Explanation of the columns that may appear on this page:

Level | A few code lists that FHIR defines are hierarchical - each code is assigned a level. See Code System for further information.
Source | The source of the definition of the code (when the value set draws in codes defined elsewhere)
Code | The code (used as the code in the resource instance). If the code is in italics, this indicates that the code is not selectable ('Abstract')
Display | The display (used in the display element of a Coding). If there is no display, implementers should not simply display the code, but map the concept into their application
Definition | An explanation of the meaning of the concept
Comments | Additional notes about how to use the code

4.3.14.325 Code System http://hl7.org/fhir/flag-priority-code

URL: https://hl7.org/fhir/R4/codesystem-flag-priority.html
Vocabulary Work Group | Maturity Level: 0 | Informative | Use Context: Any

This is a code system defined by the FHIR project.

Summary

Defining URL: | http://hl7.org/fhir/flag-priority-code
Version: | 4.0.1
Name: | FlagPriorityCodes
Title: | Flag Priority Codes
Definition: | This value set is provided as an exemplar. The value set is driven by IHE Table B.8-4: Abnormal Flags, Alert Priority.
Committee: | ??
OID: | 2.16.840.1.113883.4.642.4.951 (for OID based terminology systems)
Source Resource | XML / JSON

This Code system is used in the following value sets:

• ValueSet: Flag Priority Codes (This value set is provided as an exemplar. The value set is driven by IHE Table B.8-4: Abnormal Flags, Alert Priority.)

• ValueSet: Flag Priority Codes (This value set is provided as an exemplar. The value set is driven by IHE Table B.8-4: Abnormal Flags, Alert Priority.)

4.3.14.325.1 Content

4.3.14.325.2 Flag Priority Codes

This value set is provided as an exemplar. The value set is driven by IHE Table B.8-4: Abnormal Flags, Alert Priority.

This code system http://hl7.org/fhir/flag-priority-code defines the following codes:

Code | Display | Definition
PN | No alarm | No alarm.
PL | Low priority | Low priority.
PM | Medium priority | Medium priority.
PH | High priority | High priority.

See the full registry of code systems defined as part of FHIR.

Explanation of the columns that may appear on this page:

Level | A few code lists that FHIR defines are hierarchical - each code is assigned a level. See Code System for further information.
Source | The source of the definition of the code (when the value set draws in codes defined elsewhere)
Code | The code (used as the code in the resource instance). If the code is in italics, this indicates that the code is not selectable ('Abstract')
Display | The display (used in the display element of a Coding). If there is no display, implementers should not simply display the code, but map the concept into their application
Definition | An explanation of the meaning of the concept
Comments | Additional notes about how to use the code

4.3.14.326 Code System http://hl7.org/fhir/request-resource-types

URL: https://hl7.org/fhir/R4/codesystem-request-resource-types.html
Clinical Decision Support Work Group | Maturity Level: 2 | Trial Use | Use Context: Any

This is a code system defined by the FHIR project.

Summary

Defining URL: | http://hl7.org/fhir/request-resource-types
Version: | 4.0.1
Name: | RequestResourceType
Title: | RequestResourceType
Definition: | A list of all the request resource types defined in this version of the FHIR specification.
Committee: | Clinical Decision Support Work Group
OID: | 2.16.840.1.113883.4.642.4.1059 (for OID based terminology systems)
Source Resource | XML / JSON

This Code system is used in the following value sets:

• ValueSet: RequestResourceType (A list of all the request resource types defined in this version of the FHIR specification.)

• ValueSet: RequestResourceType (A list of all the request resource types defined in this version of the FHIR specification.)

4.3.14.326.1 Content

4.3.14.326.2 RequestResourceType

A list of all the request resource types defined in this version of the FHIR specification.

This code system http://hl7.org/fhir/request-resource-types defines the following codes:

Code | Display | Definition
Appointment | Appointment | A booking of a healthcare event among patient(s), practitioner(s), related person(s) and/or device(s) for a specific date/time. This may result in one or more Encounter(s).
AppointmentResponse | AppointmentResponse | A reply to an appointment request for a patient and/or practitioner(s), such as a confirmation or rejection.
CarePlan | CarePlan | Healthcare plan for patient or group.
Claim | Claim | Claim, Pre-determination or Pre-authorization.
CommunicationRequest | CommunicationRequest | A request for information to be sent to a receiver.
Contract | Contract | Legal Agreement.
DeviceRequest | DeviceRequest | Medical device request.
EnrollmentRequest | EnrollmentRequest | Enrollment request.
ImmunizationRecommendation | ImmunizationRecommendation | Guidance or advice relating to an immunization.
MedicationRequest | MedicationRequest | Ordering of medication for patient or group.
NutritionOrder | NutritionOrder | Diet, formula or nutritional supplement request.

ServiceRequest | ServiceRequest | A record of a request for service such as diagnostic investigations, treatments, or operations to be performed.
SupplyRequest | SupplyRequest | Request for a medication, substance or device.
Task | Task | A task to be performed.
VisionPrescription | VisionPrescription | Prescription for vision correction products for a patient.

See the full registry of code systems defined as part of FHIR.

Explanation of the columns that may appear on this page:

Level | A few code lists that FHIR defines are hierarchical - each code is assigned a level. See Code System for further information.
Source | The source of the definition of the code (when the value set draws in codes defined elsewhere)
Code | The code (used as the code in the resource instance). If the code is in italics, this indicates that the code is not selectable ('Abstract')
Display | The display (used in the display element of a Coding). If there is no display, implementers should not simply display the code, but map the concept into their application
Definition | An explanation of the meaning of the concept
Comments | Additional notes about how to use the code

4.3.14.327 Code System http://terminology.hl7.org/CodeSystem/choice-list-orientation

URL: https://hl7.org/fhir/R4/codesystem-choice-list-orientation.html
Vocabulary Work Group | Maturity Level: 0 | Informative | Use Context: Any

This is a code system defined by the FHIR project.

Summary

Defining URL: | http://terminology.hl7.org/CodeSystem/choice-list-orientation
Version: | 4.0.1
Name: | ChoiceListOrientation
Title: | ChoiceListOrientation
Definition: | Direction in which lists of possible answers should be displayed.
Committee: | ??
OID: | 2.16.840.1.113883.4.642.4.1273 (for OID based terminology systems)
Source Resource | XML / JSON

This Code system is used in the following value sets:

• ValueSet: ChoiceListOrientation (Direction in which lists of possible answers should be displayed.)

• ValueSet: ChoiceListOrientation (Direction in which lists of possible answers should be displayed.)

4.3.14.327.1 Content

4.3.14.327.2 ChoiceListOrientation

Direction in which lists of possible answers should be displayed.

This code system http://terminology.hl7.org/CodeSystem/choice-list-orientation defines the following codes:

Code | Display | Definition
horizontal | Horizontal | List choices along the horizontal axis.
vertical | Vertical | List choices down the vertical axis.

See the full registry of code systems defined as part of FHIR.

Explanation of the columns that may appear on this page:

Level | A few code lists that FHIR defines are hierarchical - each code is assigned a level. See Code System for further information.
Source | The source of the definition of the code (when the value set draws in codes defined elsewhere)
Code | The code (used as the code in the resource instance). If the code is in italics, this indicates that the code is not selectable ('Abstract')
Display | The display (used in the display element of a Coding). If there is no display, implementers should not simply display the code, but map the concept into their application
Definition | An explanation of the meaning of the concept
Comments | Additional notes about how to use the code

4.3.14.328 Code System http://terminology.hl7.org/CodeSystem/restful-security-service

URL: https://hl7.org/fhir/R4/codesystem-restful-security-service.html
FHIR Infrastructure Work Group | Maturity Level: N | Normative (from v4.0.0) | Use Context: Any

| This page has been approved as part of an ANSI standard. See the Conformance Package for further details.

This is a code system defined by the FHIR project.

Summary

Defining URL: | http://terminology.hl7.org/CodeSystem/restful-security-service
Version: | 4.0.1

Name: | RestfulSecurityService
Title: | RestfulSecurityService
Definition: | Types of security services used with FHIR.
Committee: | FHIR Infrastructure Work Group
OID: | 2.16.840.1.113883.4.642.4.1079 (for OID based terminology systems)
Source Resource | XML / JSON

This Code system is used in the following value sets:

• ValueSet: RestfulSecurityService (Types of security services used with FHIR.)

• ValueSet: RestfulSecurityService (Types of security services used with FHIR.)

4.3.14.328.1 Content

4.3.14.328.2 RestfulSecurityService

Types of security services used with FHIR.

This code system http://terminology.hl7.org/CodeSystem/restful-security-service defines the following codes:

Code | Display | Definition
OAuth | OAuth | OAuth (unspecified version see oauth.net).
SMART-on-FHIR | SMART-on-FHIR | OAuth2 using SMART-on-FHIR profile (see http://docs.smarthealthit.org/).
NTLM | NTLM | Microsoft NTLM Authentication.
Basic | Basic | Basic authentication defined in HTTP specification.
Kerberos | Kerberos | see http://www.ietf.org/rfc/rfc4120.txt.
Certificates | Certificates | SSL where client must have a certificate registered with the server.

See the full registry of code systems defined as part of FHIR.

Explanation of the columns that may appear on this page:

Level | A few code lists that FHIR defines are hierarchical - each code is assigned a level. See Code System for further information.
Source | The source of the definition of the code (when the value set draws in codes defined elsewhere)
Code | The code (used as the code in the resource instance). If the code is in italics, this indicates that the code is not selectable ('Abstract')
Display | The display (used in the display element of a Coding). If there is no display, implementers should not simply display the code, but map the concept into their application
Definition | An explanation of the meaning of the concept
Comments | Additional notes about how to use the code

4.3.14.329 Code System http://cds-hooks.hl7.org/CodeSystem/indicator

URL: https://hl7.org/fhir/R4/codesystem-cdshooks-indicator.html
Vocabulary Work Group | Maturity Level: 0 | Informative | Use Context: Any

This is a code system defined by the FHIR project.

Summary

Defining URL: | http://cds-hooks.hl7.org/CodeSystem/indicator
Version: | 4.0.1
Name: | Indicator
Title:
Definition: | This value set captures the set of indicator codes defined by the CDS Hooks specification.
Committee: | Vocabulary Work Group
OID: | 2.16.840.1.113883.4.642.4.1066 (for OID based terminology systems)
Source Resource | XML / JSON

This Code system is used in the following value sets:

• ValueSet: CDSHooksIndicator (This value set captures the set of indicator codes defined by the CDS Hooks specification.)

• ValueSet: CDSHooksIndicator (This value set captures the set of indicator codes defined by the CDS Hooks specification.)

4.3.14.329.1 Content

4.3.14.329.2 Indicator

This value set captures the set of indicator codes defined by the CDS Hooks specification.

This code system http://cds-hooks.hl7.org/CodeSystem/indicator defines the following codes:

Code | Display | Definition
info | The response is informational
warning | The response is a warning
critical | The response is critical and indicates the workflow should not be allowed to proceed

See the full registry of code systems defined as part of FHIR.

Explanation of the columns that may appear on this page:

Level | A few code lists that FHIR defines are hierarchical - each code is assigned a level. See Code System for further information.
Source | The source of the definition of the code (when the value set draws in codes defined elsewhere)
Code | The code (used as the code in the resource instance). If the code is in italics, this indicates that the code is not selectable ('Abstract')
Display | The display (used in the display element of a Coding). If there is no display, implementers should not simply display the code, but map the concept into their application
Definition | An explanation of the meaning of the concept
Comments | Additional notes about how to use the code

4.3.14.330 Code System http://terminology.hl7.org/CodeSystem/processpriority

URL: https://hl7.org/fhir/R4/codesystem-process-priority.html
Financial Management Work Group | Maturity Level: 1 | Draft | Use Context: Any

This is a code system defined by the FHIR project.

Summary

Defining URL: | http://terminology.hl7.org/CodeSystem/processpriority
Version: | 4.0.1
Name: | ProcessPriorityCodes
Title: | Process Priority Codes
Definition: | This value set includes the financial processing priority codes.
Committee: | Financial Management Work Group
OID: | 2.16.840.1.113883.4.642.4.1155 (for OID based terminology systems)
Copyright: | This is an example set.
Source Resource | XML / JSON

This Code system is used in the following value sets:

• ValueSet: Process Priority Codes (This value set includes the financial processing priority codes.)
• ValueSet: Process Priority Codes (This value set includes the financial processing priority codes.)

4.3.14.330.1 Content

4.3.14.330.2 Process Priority Codes

This value set includes the financial processing priority codes.

Copyright Statement:

This is an example set.

This code system http://terminology.hl7.org/CodeSystem/processpriority defines the following codes:

Code | Display | Definition
stat | Immediate | Immediately in real time.
normal | Normal | With best effort.
deferred | Deferred | Later, when possible.

See the full registry of code systems defined as part of FHIR.

Explanation of the columns that may appear on this page:

Level | A few code lists that FHIR defines are hierarchical - each code is assigned a level. See Code System for further information.
Source | The source of the definition of the code (when the value set draws in codes defined elsewhere)
Code | The code (used as the code in the resource instance). If the code is in italics, this indicates that the code is not selectable ('Abstract')
Display | The display (used in the display element of a Coding). If there is no display, implementers should not simply display the code, but map the concept into their application
Definition | An explanation of the meaning of the concept
Comments | Additional notes about how to use the code

4.3.14.331 Code System http://hl7.org/fhir/allergy-intolerance-criticality

URL: https://hl7.org/fhir/R4/codesystem-allergy-intolerance-criticality.html
Patient Care Work Group | Maturity Level: 3 | Trial Use | Use Context: Any

This is a code system defined by the FHIR project.

Summary

Defining URL: | http://hl7.org/fhir/allergy-intolerance-criticality
Version: | 4.0.1
Name: | AllergyIntoleranceCriticality
Title: | AllergyIntoleranceCriticality
Definition: | Estimate of the potential clinical harm, or seriousness, of a reaction to an identified substance.

Committee: | Patient Care Work Group
OID: | 2.16.840.1.113883.4.642.4.130 (for OID based terminology systems)
Source Resource | XML / JSON

This Code system is used in the following value sets:

• ValueSet: AllergyIntoleranceCriticality (Estimate of the potential clinical harm, or seriousness, of a reaction to an identified substance.)

• ValueSet: AllergyIntoleranceCriticality (Estimate of the potential clinical harm, or seriousness, of a reaction to an identified substance.)

4.3.14.331.1 Content

4.3.14.331.2 AllergyIntoleranceCriticality

Estimate of the potential clinical harm, or seriousness, of a reaction to an identified substance.

This code system http://hl7.org/fhir/allergy-intolerance-criticality defines the following codes:

Code | Display | Definition
low | Low Risk | Worst case result of a future exposure is not assessed to be life-threatening or having high potential for organ system failure.
high | High Risk | Worst case result of a future exposure is assessed to be life-threatening or having high potential for organ system failure.
unable-to-assess | Unable to Assess Risk | Unable to assess the worst case result of a future exposure.

See the full registry of code systems defined as part of FHIR.

Explanation of the columns that may appear on this page:

Level | A few code lists that FHIR defines are hierarchical - each code is assigned a level. See Code System for further information.
Source | The source of the definition of the code (when the value set draws in codes defined elsewhere)
Code | The code (used as the code in the resource instance). If the code is in italics, this indicates that the code is not selectable ('Abstract')
Display | The display (used in the display element of a Coding). If there is no display, implementers should not simply display the code, but map the concept into their application
Definition | An explanation of the meaning of the concept
Comments | Additional notes about how to use the code

4.3.14.332 Code System http://hl7.org/fhir/contract-scope

URL: https://hl7.org/fhir/R4/codesystem-contract-scope.html
Financial Management Work Group | Maturity Level: 1 | Draft | Use Context: Any

This is a code system defined by the FHIR project.

Summary

Defining URL: | http://hl7.org/fhir/contract-scope
Version: | 4.0.1
Name: | ContractResourceScopeCodes
Title: | Contract Resource Scope codes
Definition: | This value set contract specific codes for scope.
Committee: | Financial Management Work Group
OID: | 2.16.840.1.113883.4.642.4.1217 (for OID based terminology systems)
Copyright: | HL7 International.
Source Resource | XML / JSON

This Code system is used in the following value sets:

• ValueSet: Contract Resource Scope codes (This value set contract specific codes for scope.)

• ValueSet: Contract Resource Scope codes (This value set contract specific codes for scope.)

4.3.14.332.1 Content

Each definition includes usage notes explaining the precedence order in contract lifecycle - i.e., while only some stages are required, the order in which they may occur is deterministic; and a map to comparable FHIR and v.3 status codes. It follows guidance about use of status codes in FHIR at http://build.fhir.org/sc.html.

4.3.14.332.2 Contract Resource Scope codes

This value set contract specific codes for scope.

Copyright Statement:

HL7 International.

This code system http://hl7.org/fhir/contract-scope defines the following codes:

Code | Display | Definition
policy | Policy | To be completed

See the full registry of code systems defined as part of FHIR.

Explanation of the columns that may appear on this page:

Level | A few code lists that FHIR defines are hierarchical - each code is assigned a level. See Code System for further information.
Source | The source of the definition of the code (when the value set draws in codes defined elsewhere)
Code | The code (used as the code in the resource instance). If the code is in italics, this indicates that the code is not selectable ('Abstract')
Display | The display (used in the display element of a Coding). If there is no display, implementers should not simply display the code, but map the concept into their application
Definition | An explanation of the meaning of the concept
Comments | Additional notes about how to use the code

4.3.14.333 Code System http://terminology.hl7.org/CodeSystem/expansion-processing-rule

URL: https://hl7.org/fhir/R4/codesystem-expansion-processing-rule.html
Vocabulary Work Group | Maturity Level: 0 | Informative | Use Context: Any

This is a code system defined by the FHIR project.

Summary

Defining URL: | http://terminology.hl7.org/CodeSystem/expansion-processing-rule
Version: | 4.0.1
Name: | ExpansionProcessingRule
Title: | ExpansionProcessingRule
Definition: | Defines how concepts are processed into the expansion when it's for UI presentation.
Committee: | ??
OID: | 2.16.840.1.113883.4.642.4.1281 (for OID based terminology systems)
Source Resource | XML / JSON

This Code system is used in the following value sets:

• ValueSet: ExpansionProcessingRule (Defines how concepts are processed into the expansion when it's for UI presentation.)

• ValueSet: ExpansionProcessingRule (Defines how concepts are processed into the expansion when it's for UI presentation.)

4.3.14.333.1 Content

4.3.14.333.2 ExpansionProcessingRule

Defines how concepts are processed into the expansion when it's for UI presentation.

This code system http://terminology.hl7.org/CodeSystem/expansion-processing-rule defines the following codes:

Code | Display | Definition
all-codes | All Codes | The expansion (when in UI mode) includes all codes *and* any defined groups (in extensions).
ungrouped | Groups + Ungrouped codes | The expanion (when in UI mode) lists the groups, and then any codes that have not been included in a group.
groups-only | Groups Only | The expansion (when in UI mode) only includes the defined groups.

See the full registry of code systems defined as part of FHIR.

Explanation of the columns that may appear on this page:

Level | A few code lists that FHIR defines are hierarchical - each code is assigned a level. See Code System for further information.
Source | The source of the definition of the code (when the value set draws in codes defined elsewhere)
Code | The code (used as the code in the resource instance). If the code is in italics, this indicates that the code is not selectable ('Abstract')
Display | The display (used in the display element of a Coding). If there is no display, implementers should not simply display the code, but map the concept into their application
Definition | An explanation of the meaning of the concept
Comments | Additional notes about how to use the code

4.3.14.334 Code System http://terminology.hl7.org/CodeSystem/contract-type

URL: https://hl7.org/fhir/R4/codesystem-contract-type.html
Financial Management Work Group | Maturity Level: 1 | Draft | Use Context: Any

This is a code system defined by the FHIR project.

Summary

Defining URL: | http://terminology.hl7.org/CodeSystem/contract-type
Version: | 4.0.1
Name: | ContractTypeCodes
Title: | Contract Type Codes

Definition: | This value set includes sample Contract Type codes.
Committee: | Financial Management Work Group
OID: | 2.16.840.1.113883.4.642.4.1330 (for OID based terminology systems)
Copyright: | This is an example set.
Source Resource | XML / JSON

This Code system is used in the following value sets:

• ValueSet: Contract Type Codes (This value set includes sample Contract Type codes.)

• ValueSet: Contract Type Codes (This value set includes sample Contract Type codes.)

4.3.14.334.1 Content

4.3.14.334.2 Contract Type Codes

This value set includes sample Contract Type codes.

Copyright Statement:

This is an example set.

This code system http://terminology.hl7.org/CodeSystem/contract-type defines the following codes:

Code | Display | Definition
privacy | Privacy | Privacy policy.
disclosure | Disclosure | Information disclosure policy.
healthinsurance | Health Insurance | Health Insurance policy.
supply | Supply Contract | Contract to supply goods or services.
consent | Consent | Consent Directive.

See the full registry of code systems defined as part of FHIR.

Explanation of the columns that may appear on this page:

Level | A few code lists that FHIR defines are hierarchical - each code is assigned a level. See Code System for further information.
Source | The source of the definition of the code (when the value set draws in codes defined elsewhere)
Code | The code (used as the code in the resource instance). If the code is in italics, this indicates that the code is not selectable ('Abstract')
Display | The display (used in the display element of a Coding). If there is no display, implementers should not simply display the code, but map the concept into their application
Definition | An explanation of the meaning of the concept
Comments | Additional notes about how to use the code

4.3.14.335 Code System http://terminology.hl7.org/CodeSystem/provenance-participant-type

URL: https://hl7.org/fhir/R4/codesystem-provenance-agent-type.html
Financial Management Work Group | Maturity Level: 1 | Draft | Use Context: Any

This is a code system defined by the FHIR project.

Summary

Defining URL: | http://terminology.hl7.org/CodeSystem/provenance-participant-type
Version: | 4.0.1
Name: | ProvenanceParticipantType
Title: | Provenance participant type
Definition: | The type of participation a provenance participant.
Committee: | Financial Management Work Group
OID: | 2.16.840.1.113883.4.642.4.1131 (for OID based terminology systems)
Source Resource | XML / JSON

This Code system is used in the following value sets:

• ValueSet: Provenance participant type (The type of participation a provenance participant.)

• ValueSet: Provenance participant type (The type of participation a provenance participant.)

4.3.14.335.1 Content

4.3.14.335.2 Provenance participant type

The type of participation a provenance participant.

This code system http://terminology.hl7.org/CodeSystem/provenance-participant-type defines the following codes:

Lvl | Code | Display | Definition
1 | enterer | Enterer | A person entering the data into the originating system
1 | performer | Performer | A person, animal, organization or device that who actually and principally carries out the activity
1 | author | Author | A party that originates the resource and therefore has responsibility for the information given in the resource and ownership of this resource

1 | verifier | Verifier | A person who verifies the correctness and appropriateness of activity
2 | legal | Legal Authenticator | The person authenticated the content and accepted legal responsibility for its content
1 | attester | Attester | A verifier who attests to the accuracy of the resource
1 | informant | Informant | A person who reported information that contributed to the resource
1 | custodian | Custodian | The entity that is accountable for maintaining a true an accurate copy of the original record
1 | assembler | Assembler | A device that operates independently of an author on custodian's algorithms for data extraction of existing information for purpose of generating a new artifact.
1 | composer | Composer | A device used by an author to record new information, which may also be used by the author to select existing information for aggregation with newly recorded information for the purpose of generating a new artifact.

See the full registry of code systems defined as part of FHIR.

Explanation of the columns that may appear on this page:

Level | A few code lists that FHIR defines are hierarchical - each code is assigned a level. See Code System for further information.
Source | The source of the definition of the code (when the value set draws in codes defined elsewhere)
Code | The code (used as the code in the resource instance). If the code is in italics, this indicates that the code is not selectable ('Abstract')
Display | The display (used in the display element of a Coding). If there is no display, implementers should not simply display the code, but map the concept into their application
Definition | An explanation of the meaning of the concept
Comments | Additional notes about how to use the code

4.3.14.336 Code System http://terminology.hl7.org/CodeSystem/ex-claimsubtype

URL: https://hl7.org/fhir/R4/codesystem-claim-subtype.html
Financial Management Work Group | Maturity Level: 1 | Draft | Use Context: Any

This is a code system defined by the FHIR project.

Summary

Defining URL: | http://terminology.hl7.org/CodeSystem/ex-claimsubtype
Version: | 4.0.1
Name: | ExampleClaimSubTypeCodes
Title: | Example Claim SubType Codes
Definition: | This value set includes sample Claim SubType codes which are used to distinguish the claim types for example within type institutional there may be subtypes for emergency services, bed stay and transportation.
Committee: | Financial Management Work Group
OID: | 2.16.840.1.113883.4.642.4.1158 (for OID based terminology systems)
Copyright: | This is an example set.
Source Resource | XML / JSON

This Code system is used in the following value sets:

• ValueSet: Example Claim SubType Codes (This value set includes sample Claim SubType codes which are used to distinguish the claim types for example within type institutional there may be subtypes for emergency services, bed stay and transportation.)

• ValueSet: Example Claim SubType Codes (This value set includes sample Claim SubType codes which are used to distinguish the claim types for example within type institutional there may be subtypes for emergency services, bed stay and transportation.)

4.3.14.336.1 Content

4.3.14.336.2 Example Claim SubType Codes

This value set includes sample Claim SubType codes which are used to distinguish the claim types for example within type institutional there may be subtypes for emergency services, bed stay and transportation.

Copyright Statement:

This is an example set.

This code system http://terminology.hl7.org/CodeSystem/ex-claimsubtype defines the following codes:

Code | Display | Definition
ortho | Orthodontic Claim | A claim for Orthodontic Services.
emergency | Emergency Claim | A claim for emergency services.

See the full registry of code systems defined as part of FHIR.

Explanation of the columns that may appear on this page:

Level | A few code lists that FHIR defines are hierarchical - each code is assigned a level. See Code System for further information.
Source | The source of the definition of the code (when the value set draws in codes defined elsewhere)
Code | The code (used as the code in the resource instance). If the code is in italics, this indicates that the code is not selectable ('Abstract')
Display | The display (used in the display element of a Coding). If there is no display, implementers should not simply display the code, but map the concept into their application
Definition | An explanation of the meaning of the concept

Comments | Additional notes about how to use the code

4.3.14.337 Code System http://terminology.hl7.org/CodeSystem/precision-estimate-type

URL: https://hl7.org/fhir/R4/codesystem-precision-estimate-type.html
Clinical Decision Support Work Group | Maturity Level: 0 | Trial Use | Use Context: Any

This is a code system defined by the FHIR project.

Summary

Defining URL: | http://terminology.hl7.org/CodeSystem/precision-estimate-type
Version: | 4.0.1
Name: | PrecisionEstimateType
Title: | PrecisionEstimateType
Definition: | Method of reporting variability of estimates, such as confidence intervals, interquartile range or standard deviation.
Committee: | Clinical Decision Support Work Group
OID: | 2.16.840.1.113883.4.642.4.1358 (for OID based terminology systems)
Source Resource | XML / JSON

This Code system is used in the following value sets:

• ValueSet: PrecisionEstimateType (Method of reporting variability of estimates, such as confidence intervals, interquartile range or standard deviation.)

• ValueSet: PrecisionEstimateType (Method of reporting variability of estimates, such as confidence intervals, interquartile range or standard deviation.)

4.3.14.337.1 Content

4.3.14.337.2 PrecisionEstimateType

Method of reporting variability of estimates, such as confidence intervals, interquartile range or standard deviation.

This code system http://terminology.hl7.org/CodeSystem/precision-estimate-type defines the following codes:

Code | Display | Definition
CI | confidence interval | confidence interval.
IQR | interquartile range | interquartile range.
SD | standard deviation | standard deviation.
SE | standard error | standard error.

See the full registry of code systems defined as part of FHIR.

Explanation of the columns that may appear on this page:

Level | A few code lists that FHIR defines are hierarchical - each code is assigned a level. See Code System for further information.
Source | The source of the definition of the code (when the value set draws in codes defined elsewhere)
Code | The code (used as the code in the resource instance). If the code is in italics, this indicates that the code is not selectable ('Abstract')
Display | The display (used in the display element of a Coding). If there is no display, implementers should not simply display the code, but map the concept into their application
Definition | An explanation of the meaning of the concept
Comments | Additional notes about how to use the code

4.3.14.338 Code System http://terminology.hl7.org/CodeSystem/endpoint-payload-type

URL: https://hl7.org/fhir/R4/codesystem-endpoint-payload-type.html
Patient Administration Work Group | Maturity Level: 1 | Draft | Use Context: Any

This is a code system defined by the FHIR project.

Summary

Defining URL: | http://terminology.hl7.org/CodeSystem/endpoint-payload-type
Version: | 4.0.1
Name: | EndpointPayloadType
Title: | Endpoint Payload Type
Definition: | This is an example value set defined by the FHIR project, that could be used to represent possible payload document types.
Committee: | Patient Administration Work Group
OID: | 2.16.840.1.113883.4.642.4.1139 (for OID based terminology systems)
Copyright: | Some content from IHE® Copyright © 2015 IHE International, Inc. This content is from the IHE Technical Frameworks and Supplements, available for free download and use at http://www.ihe.net/Technical_Frameworks/
Source Resource | XML / JSON

This Code system is used in the following value sets:

• ValueSet: Endpoint Payload Type (This is an example value set defined by the FHIR project, that could be used to represent possible payload document types.)

• ValueSet: Endpoint Payload Type (This is an example value set defined by the FHIR project, that could be used to represent possible payload document types.)

4.3.14.338.1 Content

4.3.14.338.2 Endpoint Payload Type

This is an example value set defined by the FHIR project, that could be used to represent possible payload document types.

Copyright Statement:

Some content from IHE® Copyright © 2015 IHE International, Inc. This content is from the IHE Technical Frameworks and Supplements, available for free download and use at http://www.ihe.net/Technical_Frameworks/

This code system http://terminology.hl7.org/CodeSystem/endpoint-payload-type defines the following codes:

Code	Display	Definition
any	Any	Any payload type can be used with this endpoint, it is either a payload agnostic infrastructure (such as a storage repository), or some other type of endpoint where payload considerations are internally handled, and not available
none	None	This endpoint does not require any content to be sent; simply connecting to the endpoint is enough notification. This can be used as a 'ping' to wakeup a service to retrieve content, which could be to ensure security considerations are correctly handled

See the full registry of code systems defined as part of FHIR.

Explanation of the columns that may appear on this page:

Level	A few code lists that FHIR defines are hierarchical - each code is assigned a level. See Code System for further information.
Source	The source of the definition of the code (when the value set draws in codes defined elsewhere)
Code	The code (used as the code in the resource instance). If the code is in italics, this indicates that the code is not selectable ('Abstract')
Display	The display (used in the display element of a Coding). If there is no display, implementers should not simply display the code, but map the concept into their application
Definition	An explanation of the meaning of the concept
Comments	Additional notes about how to use the code

4.3.14.339 Code System http://terminology.hl7.org/CodeSystem/codesystem-altcode-kind

URL: https://hl7.org/fhir/R4/codesystem-codesystem-altcode-kind.html	
Vocabulary Work Group	Maturity Level: 0 | Informative | Use Context: Any

This is a code system defined by the FHIR project.

Summary

Defining URL:	http://terminology.hl7.org/CodeSystem/codesystem-altcode-kind
Version:	4.0.1
Name:	AlternativeCodeKind
Title:	AlternativeCodeKind
Definition:	Indicates the type of use for which the code is defined.
Committee:	??
OID:	2.16.840.1.113883.4.642.4.1284 (for OID based terminology systems)
Source Resource	XML / JSON

This Code system is used in the following value sets:

• ValueSet: AlternativeCodeKind (Indicates the type of use for which the code is defined.)

• ValueSet: AlternativeCodeKind (Indicates the type of use for which the code is defined.)

4.3.14.339.1 Content

4.3.14.339.2 AlternativeCodeKind

Indicates the type of use for which the code is defined.

This code system http://terminology.hl7.org/CodeSystem/codesystem-altcode-kind defines the following codes:

Code	Display	Definition
alternate	Alternate Code	The code is an alternative code that can be used in any of the circumstances that the primary code can be used.
deprecated	Deprecated	The code should no longer be used, but was used in the past.
case-insensitive	Case Insensitive	The code is an alternative to be used when a case insensitive code is required (when the primary codes are case sensitive).

case-sensitive | Case Sensitive | The code is an alternative to be used when a case sensitive code is required (when the primary codes are case insensitive).
expression | Expression | The code is an alternative for the primary code that is built using the expression grammar defined by the code system.

See the full registry of code systems defined as part of FHIR.

Explanation of the columns that may appear on this page:

Level | A few code lists that FHIR defines are hierarchical - each code is assigned a level. See Code System for further information.
Source | The source of the definition of the code (when the value set draws in codes defined elsewhere)
Code | The code (used as the code in the resource instance). If the code is in italics, this indicates that the code is not selectable ('Abstract')
Display | The display (used in the display element of a Coding). If there is no display, implementers should not simply display the code, but map the concept into their application
Definition | An explanation of the meaning of the concept
Comments | Additional notes about how to use the code

4.3.14.340 Code System http://hl7.org/fhir/discriminator-type

URL: https://hl7.org/fhir/R4/codesystem-discriminator-type.html
FHIR Infrastructure Work Group | Maturity Level: N | Normative (from v4.0.0) | Use Context: Any

This is a code system defined by the FHIR project.

Summary

Defining URL: | http://hl7.org/fhir/discriminator-type
Version: | 4.0.1
Name: | DiscriminatorType
Title: | DiscriminatorType
Definition: | How an element value is interpreted when discrimination is evaluated.
Committee: | FHIR Infrastructure Work Group
OID: | 2.16.840.1.113883.4.642.4.92 (for OID based terminology systems)
Source Resource | XML / JSON

This Code system is used in the following value sets:

• ValueSet: DiscriminatorType (How an element value is interpreted when discrimination is evaluated.)
• ValueSet: DiscriminatorType (How an element value is interpreted when discrimination is evaluated.)

4.3.14.340.1 Content

4.3.14.340.2 DiscriminatorType

How an element value is interpreted when discrimination is evaluated.

This code system http://hl7.org/fhir/discriminator-type defines the following codes:

Code | Display | Definition
value | Value | The slices have different values in the nominated element.
exists | Exists | The slices are differentiated by the presence or absence of the nominated element.
pattern | Pattern | The slices have different values in the nominated element, as determined by testing them against the applicable ElementDefinition.pattern[x].
type | Type | The slices are differentiated by type of the nominated element.
profile | Profile | The slices are differentiated by conformance of the nominated element to a specified profile. Note that if the path specifies .resolve() then the profile is the target profile on the reference. In this case, validation by the possible profiles is required to differentiate the slices.

See the full registry of code systems defined as part of FHIR.

Explanation of the columns that may appear on this page:

Level | A few code lists that FHIR defines are hierarchical - each code is assigned a level. See Code System for further information.
Source | The source of the definition of the code (when the value set draws in codes defined elsewhere)
Code | The code (used as the code in the resource instance). If the code is in italics, this indicates that the code is not selectable ('Abstract')
Display | The display (used in the display element of a Coding). If there is no display, implementers should not simply display the code, but map the concept into their application
Definition | An explanation of the meaning of the concept
Comments | Additional notes about how to use the code

4.3.14.341 Code System http://hl7.org/fhir/provenance-entity-role

URL: https://hl7.org/fhir/R4/codesystem-provenance-entity-role.html
Security Work Group | Maturity Level: 3 | Trial Use | Use Context: Any

This is a code system defined by the FHIR project.

Summary

Defining URL: | http://hl7.org/fhir/provenance-entity-role
Version: | 4.0.1
Name: | ProvenanceEntityRole
Title: | ProvenanceEntityRole
Definition: | How an entity was used in an activity.
Committee: | Security Work Group
OID: | 2.16.840.1.113883.4.642.4.437 (for OID based terminology systems)
Source Resource | XML / JSON

This Code system is used in the following value sets:

• ValueSet: ProvenanceEntityRole (How an entity was used in an activity.)

• ValueSet: ProvenanceEntityRole (How an entity was used in an activity.)

4.3.14.341.1 Content

4.3.14.341.2 ProvenanceEntityRole

How an entity was used in an activity.

This code system http://hl7.org/fhir/provenance-entity-role defines the following codes:

Lvl | Code | Display | Definition
1 | derivation | Derivation | A transformation of an entity into another, an update of an entity resulting in a new one, or the construction of a new entity based on a pre-existing entity.
2 | revision | Revision | A derivation for which the resulting entity is a revised version of some original.
2 | quotation | Quotation | The repeat of (some or all of) an entity, such as text or image, by someone who might or might not be its original author.
2 | source | Source | A primary source for a topic refers to something produced by some agent with direct experience and knowledge about the topic, at the time of the topic's study, without benefit from hindsight.
2 | removal | Removal | A derivation for which the entity is removed from accessibility usually through the use of the Delete operation.

See the full registry of code systems defined as part of FHIR.

Explanation of the columns that may appear on this page:

Level | A few code lists that FHIR defines are hierarchical - each code is assigned a level. See Code System for further information.
Source | The source of the definition of the code (when the value set draws in codes defined elsewhere)
Code | The code (used as the code in the resource instance). If the code is in italics, this indicates that the code is not selectable ('Abstract')
Display | The display (used in the display element of a Coding). If there is no display, implementers should not simply display the code, but map the concept into their application
Definition | An explanation of the meaning of the concept
Comments | Additional notes about how to use the code

4.3.14.342 Code System http://terminology.hl7.org/CodeSystem/container-cap

URL: https://hl7.org/fhir/R4/codesystem-container-cap.html
Orders and Observations Work Group | Maturity Level: 1 | Draft | Use Context: Any

This is a code system defined by the FHIR project.

Summary

Defining URL: | http://terminology.hl7.org/CodeSystem/container-cap
Version: | 4.0.1
Name: | ContainerCap
Title: | ContainerCap
Definition: | Color of the container cap.
Committee: | Orders and Observations Work Group
OID: | 2.16.840.1.113883.4.642.4.1258 (for OID based terminology systems)
Source Resource | XML / JSON

This Code system is used in the following value sets:

• ValueSet: ContainerCap (Color of the container cap.)

• ValueSet: ContainerCap (Color of the container cap.)

4.3.14.342.1 Content

4.3.14.342.2 ContainerCap

Color of the container cap.

This code system http://terminology.hl7.org/CodeSystem/container-cap defines the following codes:

Code | Display | Definition
red | red cap | red cap.
yellow | yellow cap | yellow cap.

dark-yellow | dark yellow cap | dark yellow cap.
grey | grey cap | grey cap.
light-blue | light blue cap | light blue cap.
black | black cap | black cap.
green | green cap | green cap.
light-green | light green cap | light green cap.
lavender | lavender cap | lavender cap.
brown | brown cap | brown cap.
white | white cap | white cap.
pink | pink cap | pink cap.

See the full registry of code systems defined as part of FHIR.

Explanation of the columns that may appear on this page:

Level | A few code lists that FHIR defines are hierarchical - each code is assigned a level. See Code System for further information.
Source | The source of the definition of the code (when the value set draws in codes defined elsewhere)
Code | The code (used as the code in the resource instance). If the code is in italics, this indicates that the code is not selectable ('Abstract')
Display | The display (used in the display element of a Coding). If there is no display, implementers should not simply display the code, but map the concept into their application
Definition | An explanation of the meaning of the concept
Comments | Additional notes about how to use the code

4.3.14.343 Code System http://terminology.hl7.org/CodeSystem/medicationdispense-performer-function

URL: https://hl7.org/fhir/R4/codesystem-medicationdispense-performer-function.html
Pharmacy Work Group | Maturity Level: 1 | Draft | Use Context: Any

This is a code system defined by the FHIR project.

Summary

Defining URL: | http://terminology.hl7.org/CodeSystem/medicationdispense-performer-function
Version: | 4.0.1
Name: | MedicationDispense Performer Function Codes
Title: | Medication dispense performer function codes
Definition: | MedicationDispense Performer Function Codes
Committee: | Pharmacy Work Group
OID: | 2.16.840.1.113883.4.642.4.1319 (for OID based terminology systems)
Source Resource | XML / JSON

This Code system is used in the following value sets:

• ValueSet: Medication dispense performer function codes (MedicationDispense Performer Function Codes)
• ValueSet: Medication dispense performer function codes (MedicationDispense Performer Function Codes)

4.3.14.343.1 Content

4.3.14.343.2 Medication dispense performer function codes

MedicationDispense Performer Function Codes

This code system http://terminology.hl7.org/CodeSystem/medicationdispense-performer-function defines the following codes:

Code | Display | Definition
dataenterer | Data Enterer | Recorded the details of the request
packager | Packager | Prepared the medication.
checker | Checker | Performed initial quality assurance on the prepared medication
finalchecker | Final Checker | Performed the final quality assurance on the prepared medication against the request. Typically, this is a pharmacist function.

See the full registry of code systems defined as part of FHIR.

Explanation of the columns that may appear on this page:

Level | A few code lists that FHIR defines are hierarchical - each code is assigned a level. See Code System for further information.
Source | The source of the definition of the code (when the value set draws in codes defined elsewhere)
Code | The code (used as the code in the resource instance). If the code is in italics, this indicates that the code is not selectable ('Abstract')
Display | The display (used in the display element of a Coding). If there is no display, implementers should not simply display the code, but map the concept into their application
Definition | An explanation of the meaning of the concept
Comments | Additional notes about how to use the code

4.3.14.344 Code System http://hl7.org/fhir/feeding-device

URL: https://hl7.org/fhir/R4/codesystem-feeding-device.html
Vocabulary Work Group | Maturity Level: 0 | Informative | Use Context: Any

This is a code system defined by the FHIR project.

Summary

Defining URL: | http://hl7.org/fhir/feeding-device
Version: | 4.0.1
Name: | FeedingDeviceCodes
Title: | Feeding Device Codes
Definition: | Materials used or needed to feed the patient.
Committee: | ??
OID: | 2.16.840.1.113883.4.642.4.962 (for OID based terminology systems)
Copyright: | This resource includes content from SNOMED Clinical Terms® (SNOMED CT®) which is copyright of the International Health Terminology Standards Development Organisation (IHTSDO). Implementers of these specifications must have the appropriate SNOMED CT Affiliate license - for more information contact http://www.snomed.org/snomed-ct/get-snomed-ct or info@snomed.org
Source Resource | XML / JSON

This Code system is used in the following value sets:

• ValueSet: Feeding Device Codes (Materials used or needed to feed the patient.)

• ValueSet: Feeding Device Codes (Materials used or needed to feed the patient.)

4.3.14.344.1 Content

4.3.14.344.2 Feeding Device Codes

Materials used or needed to feed the patient.

Copyright Statement:

This resource includes content from SNOMED Clinical Terms® (SNOMED CT®) which is copyright of the International Health Terminology Standards Development Organisation (IHTSDO). Implementers of these specifications must have the appropriate SNOMED CT Affiliate license - for more information contact http://www.snomed.org/snomed-ct/get-snomed-ct or info@snomed.org

This code system http://hl7.org/fhir/feeding-device defines the following codes:

Code | Display | Definition
standard-nipple | Standard nipple | Standard nipple definition:
preemie-nipple | Preemie nipple | Preemie nipple definition:
ortho-nipple | Orthodontic nipple | Orthodontic nipple definition:
sloflo-nipple | Slow flow nipple | Slow flow nipple definition:
midflo-nipple | Middle flow nipple | Middle flow nipple definition:
bigcut-nipple | Enlarged, cross-cut nipple | Enlarged, cross-cut nipple definition:
haberman-bottle | Haberman bottle | Haberman bottle definition:
sippy-valve | Sippy cup with valve | Sippy cup with valve definition:
sippy-no-valve | Sippy cup without valve | Sippy cup without valve definition:
provale-cup | Provale Cup | Provale Cup definition:
glass-lid | Glass with lid/sippy cup | Glass with lid/sippy cup definition:
handhold-cup | Double handhold on glass/cup | Double handhold on glass/cup definition:
rubber-mat | Rubber matting under tray | Rubber matting under tray definition:
straw | Straw | Straw definition:
nose-cup | Nose cup | Nose cup definition:
scoop-plate | Scoop plate | Scoop plate definition:
utensil-holder | Hand wrap utensil holder | Hand wrap utensil holder definition:
foam-handle | Foam handle utensils | Foam handle utensils definition:
angled-utensil | Angled utensils | Angled utensils definition:
spout-cup | Spout cup | Spout cup definition:
autofeeding-device | Automated feeding devices | Automated feeding devices definition:
rocker-knife | Rocker knife | Rocker knife definition:

See the full registry of code systems defined as part of FHIR.

Explanation of the columns that may appear on this page:

Level | A few code lists that FHIR defines are hierarchical - each code is assigned a level. See Code System for further information.
Source | The source of the definition of the code (when the value set draws in codes defined elsewhere)
Code | The code (used as the code in the resource instance). If the code is in italics, this indicates that the code is not selectable ('Abstract')
Display | The display (used in the display element of a Coding). If there is no display, implementers should not simply display the code, but map the concept into their application
Definition | An explanation of the meaning of the concept
Comments | Additional notes about how to use the code

4.3.14.345 Code System http://terminology.hl7.org/CodeSystem/iso-21089-lifecycle

URL: https://hl7.org/fhir/R4/codesystem-iso-21089-lifecycle.html
Vocabulary Work Group | Maturity Level: 0 | Informative | Use Context: Any

This is a code system defined by the FHIR project.

Summary

Defining URL: | http://terminology.hl7.org/CodeSystem/iso-21089-lifecycle
Version: | null
Name: | ISO 21089-2017 Health Record Lifecycle Events
Title:
Definition: | Attached is vocabulary for the 27 record lifecycle events, as per ISO TS 21089-2017, Health Informatics - Trusted End-to-End Information Flows, Section 3, Terms and Definitions (2017, at ISO Central Secretariat, passed ballot and ready for publication). This will also be included in the FHIR EHR Record Lifecycle Event Implementation Guide, balloted and (to be) published with FHIR STU-3.
Committee: | ??
OID: | (for OID based terminology systems)
Copyright: | These codes are excerpted from ISO Standard, TS 21089-2017 - Health Informatics - Trusted End-to-End Information Flows, Copyright by ISO International. Copies of this standard are available through the ISO Web Site at www.iso.org.
Source Resource | XML / JSON

This Code system is used in the following value sets:

• ValueSet: Audit Event ID (Event Types for Audit Events - defined by DICOM with some FHIR specific additions.)

• ValueSet: Audit Event ID (Event Types for Audit Events - defined by DICOM with some FHIR specific additions.)

4.3.14.345.1 Content

4.3.14.345.2 ISO 21089-2017 Health Record Lifecycle Events

Attached is vocabulary for the 27 record lifecycle events, as per ISO TS 21089-2017, Health Informatics - Trusted End-to-End Information Flows, Section 3, Terms and Definitions (2017, at ISO Central Secretariat, passed ballot and ready for publication). This will also be included in the FHIR EHR Record Lifecycle Event Implementation Guide, balloted and (to be) published with FHIR STU-3.

Copyright Statement:

These codes are excerpted from ISO Standard, TS 21089-2017 - Health Informatics - Trusted End-to-End Information Flows, Copyright by ISO International. Copies of this standard are available through the ISO Web Site at www.iso.org.

This code system http://terminology.hl7.org/CodeSystem/iso-21089-lifecycle defines the following codes:

Code | Display | Definition
access | Access/View Record Lifecycle Event | Occurs when an agent causes the system to obtain and open a record entry for inspection or review.
hold | Add Legal Hold Record Lifecycle Event | Occurs when an agent causes the system to tag or otherwise indicate special access management and suspension of record entry deletion/destruction, if deemed relevant to a lawsuit or which are reasonably anticipated to be relevant or to fulfill organizational policy under the legal doctrine of “duty to preserve”.
amend | Amend (Update) Record Lifecycle Event | Occurs when an agent makes any change to record entry content currently residing in storage considered permanent (persistent).
archive | Archive Record Lifecycle Event | Occurs when an agent causes the system to create and move archive artifacts containing record entry content, typically to long-term offline storage.
attest | Attest Record Lifecycle Event | Occurs when an agent causes the system to capture the agent’s digital signature (or equivalent indication) during formal validation of record entry content.
decrypt | Decrypt Record Lifecycle Event | Occurs when an agent causes the system to decode record entry content from a cipher.
deidentify | De-Identify (Anononymize) Record Lifecycle Event | Occurs when an agent causes the system to scrub record entry content to reduce the association between a set of identifying data and the data subject in a way that might or might not be reversible.
deprecate | Deprecate Record Lifecycle Event | Occurs when an agent causes the system to tag record entry(ies) as obsolete, erroneous or untrustworthy, to warn against its future use.
destroy | Destroy/Delete Record Lifecycle Event | Occurs when an agent causes the system to permanently erase record entry content from the system.
disclose | Disclose Record Lifecycle Event | Occurs when an agent causes the system to release, transfer, provision access to, or otherwise divulge record entry content.
encrypt | Encrypt Record Lifecycle Event | Occurs when an agent causes the system to encode record entry content in a cipher.
extract | Extract Record Lifecycle Event | Occurs when an agent causes the system to selectively pull out a subset of record entry content, based on explicit criteria.
link | Link Record Lifecycle Event | Occurs when an agent causes the system to connect related record entries.
merge | Merge Record Lifecycle Event | Occurs when an agent causes the system to combine or join content from two or more record entries, resulting in a single logical record entry.
originate | Originate/Retain Record Lifecycle Event | Occurs when an agent causes the system to: a) initiate capture of potential record content, and b) incorporate that content into the storage considered a permanent part of the health record.

pseudonymize | Pseudonymize Record Lifecycle Event | Occurs when an agent causes the system to remove record entry content to reduce the association between a set of identifying data and the data subject in a way that may be reversible.
reactivate | Re-activate Record Lifecycle Event | Occurs when an agent causes the system to recreate or restore full status to record entries previously deleted or deprecated.
receive | Receive/Retain Record Lifecycle Event | Occurs when an agent causes the system to a) initiate capture of data content from elsewhere, and b) incorporate that content into the storage considered a permanent part of the health record.
reidentify | Re-identify Record Lifecycle Event | Occurs when an agent causes the system to restore information to data that allows identification of information source and/or information subject.
unhold | Remove Legal Hold Record Lifecycle Event | Occurs when an agent causes the system to remove a tag or other cues for special access management had required to fulfill organizational policy under the legal doctrine of “duty to preserve”.
report | Report (Output) Record Lifecycle Event | Occurs when an agent causes the system to produce and deliver record entry content in a particular form and manner.
restore | Restore Record Lifecycle Event | Occurs when an agent causes the system to recreate record entries and their content from a previous created archive artefact.
transform | Transform/Translate Record Lifecycle Event | Occurs when an agent causes the system to change the form, language or code system used to represent record entry content.
transmit | Transmit Record Lifecycle Event | Occurs when an agent causes the system to send record entry content from one (EHR/PHR/other) system to another.
unlink | Unlink Record Lifecycle Event | Occurs when an agent causes the system to disconnect two or more record entries previously connected, rendering them separate (disconnected) again.
unmerge | Unmerge Record Lifecycle Event | Occurs when an agent causes the system to reverse a previous record entry merge operation, rendering them separate again.
verify | Verify Record Lifecycle Event | Occurs when an agent causes the system to confirm compliance of data or data objects with regulations, requirements, specifications, or other imposed conditions based on organizational policy.

See the full registry of code systems defined as part of FHIR.

Explanation of the columns that may appear on this page:

Level | A few code lists that FHIR defines are hierarchical - each code is assigned a level. See Code System for further information.
Source | The source of the definition of the code (when the value set draws in codes defined elsewhere)
Code | The code (used as the code in the resource instance). If the code is in italics, this indicates that the code is not selectable ('Abstract')
Display | The display (used in the display element of a Coding). If there is no display, implementers should not simply display the code, but map the concept into their application
Definition | An explanation of the meaning of the concept
Comments | Additional notes about how to use the code

4.3.14.346 Code System http://hl7.org/fhir/group-measure

URL: https://hl7.org/fhir/R4/codesystem-group-measure.html
Clinical Decision Support Work Group | Maturity Level: 0 | Trial Use | Use Context: Any

This is a code system defined by the FHIR project.

Summary

Defining URL: | http://hl7.org/fhir/group-measure
Version: | 4.0.1
Name: | GroupMeasure
Title: | GroupMeasure
Definition: | Possible group measure aggregates (E.g. Mean, Median).
Committee: | Clinical Decision Support Work Group
OID: | 2.16.840.1.113883.4.642.4.1346 (for OID based terminology systems)
Source Resource | XML / JSON

This Code system is used in the following value sets:

• ValueSet: GroupMeasure (Possible group measure aggregates (E.g. Mean, Median).)

• ValueSet: GroupMeasure (Possible group measure aggregates (E.g. Mean, Median).)

4.3.14.346.1 Content

4.3.14.346.2 GroupMeasure

Possible group measure aggregates (E.g. Mean, Median).

This code system http://hl7.org/fhir/group-measure defines the following codes:

Code | Display | Definition
mean | Mean | Aggregated using Mean of participant values.
median | Median | Aggregated using Median of participant values.
mean-of-mean | Mean of Study Means | Aggregated using Mean of study mean values.
mean-of-median | Mean of Study Medins | Aggregated using Mean of study median values.
median-of-mean | Median of Study Means | Aggregated using Median of study mean values.
median-of-median | Median of Study Medians | Aggregated using Median of study median values.

See the full registry of code systems defined as part of FHIR.

Explanation of the columns that may appear on this page:

Level | A few code lists that FHIR defines are hierarchical - each code is assigned a level. See Code System for further information.
Source | The source of the definition of the code (when the value set draws in codes defined elsewhere)
Code | The code (used as the code in the resource instance). If the code is in italics, this indicates that the code is not selectable ('Abstract')
Display | The display (used in the display element of a Coding). If there is no display, implementers should not simply display the code, but map the concept into their application
Definition | An explanation of the meaning of the concept
Comments | Additional notes about how to use the code

4.3.14.347 Code System http://terminology.hl7.org/CodeSystem/adverse-event-causality-method

URL: https://hl7.org/fhir/R4/codesystem-adverse-event-causality-method.html
Patient Care Work Group | Maturity Level: 1 | Draft | Use Context: Any

This is a code system defined by the FHIR project.

Summary

Defining URL: | http://terminology.hl7.org/CodeSystem/adverse-event-causality-method
Version: | 4.0.1
Name: | AdverseEventCausalityMethod
Title: | AdverseEventCausalityMethod
Definition: | TODO.
Committee: | Patient Care Work Group
OID: | 2.16.840.1.113883.4.642.4.1255 (for OID based terminology systems)
Source Resource | XML / JSON

This Code system is used in the following value sets:

• ValueSet: AdverseEventCausalityMethod (TODO.)

• ValueSet: AdverseEventCausalityMethod (TODO.)

4.3.14.347.1 Content

4.3.14.347.2 AdverseEventCausalityMethod

TODO.

This code system http://terminology.hl7.org/CodeSystem/adverse-event-causality-method defines the following codes:

Code | Display | Definition
ProbabilityScale | Probability Scale
Bayesian | Bayesian
Checklist | Checklist

See the full registry of code systems defined as part of FHIR.

Explanation of the columns that may appear on this page:

Level | A few code lists that FHIR defines are hierarchical - each code is assigned a level. See Code System for further information.
Source | The source of the definition of the code (when the value set draws in codes defined elsewhere)
Code | The code (used as the code in the resource instance). If the code is in italics, this indicates that the code is not selectable ('Abstract')
Display | The display (used in the display element of a Coding). If there is no display, implementers should not simply display the code, but map the concept into their application
Definition | An explanation of the meaning of the concept
Comments | Additional notes about how to use the code

4.3.14.348 Code System http://terminology.hl7.org/CodeSystem/list-example-use-codes

URL: https://hl7.org/fhir/R4/codesystem-list-example-codes.html
FHIR Infrastructure Work Group | Maturity Level: 1 | Draft | Use Context: Any

This is a code system defined by the FHIR project.

Summary

Defining URL: | http://terminology.hl7.org/CodeSystem/list-example-use-codes
Version: | 4.0.1
Name: | ExampleUseCodesForList
Title: | Example Use Codes for List
Definition: | Example use codes for the List resource - typical kinds of use.
Committee: | FHIR Infrastructure Work Group
OID: | 2.16.840.1.113883.4.642.4.1105 (for OID based terminology systems)
Source Resource | XML / JSON

This Code system is used in the following value sets:

• ValueSet: Example Use Codes for List (Example use codes for the List resource - typical kinds of use.)

• ValueSet: Example Use Codes for List (Example use codes for the List resource - typical kinds of use.)

4.3.14.348.1 Content

4.3.14.348.2 Example Use Codes for List

Example use codes for the List resource - typical kinds of use.

This code system http://terminology.hl7.org/CodeSystem/list-example-use-codes defines the following codes:

Code	Display	Definition
alerts	Alerts	A list of alerts for the patient.
adverserxns	Adverse Reactions	A list of part adverse reactions.
allergies	Allergies	A list of Allergies for the patient.
medications	Medication List	A list of medication statements for the patient.
problems	Problem List	A list of problems that the patient is known of have (or have had in the past).
worklist	Worklist	A list of items that constitute a set of work to be performed (typically this code would be specialized for more specific uses, such as a ward round list).
waiting	Waiting List	A list of items waiting for an event (perhaps a surgical patient waiting list).
protocols	Protocols	A set of protocols to be followed.
plans	Care Plans	A set of care plans that apply in a particular context of care.

See the full registry of code systems defined as part of FHIR.

Explanation of the columns that may appear on this page:

Level	A few code lists that FHIR defines are hierarchical - each code is assigned a level. See Code System for further information.
Source	The source of the definition of the code (when the value set draws in codes defined elsewhere)
Code	The code (used as the code in the resource instance). If the code is in italics, this indicates that the code is not selectable ('Abstract')
Display	The display (used in the display element of a Coding). If there is no display, implementers should not simply display the code, but map the concept into their application
Definition	An explanation of the meaning of the concept
Comments	Additional notes about how to use the code

4.3.14.349 Code System http://terminology.hl7.org/CodeSystem/research-study-phase

URL: https://hl7.org/fhir/R4/codesystem-research-study-phase.html
Biomedical Research and Regulation Work Group | Maturity Level: 1 | Draft | Use Context: Any

This is a code system defined by the FHIR project.

Summary

Defining URL:	http://terminology.hl7.org/CodeSystem/research-study-phase
Version:	4.0.1
Name:	ResearchStudyPhase
Title:	ResearchStudyPhase
Definition:	Codes for the stage in the progression of a therapy from initial experimental use in humans in clinical trials to post-market evaluation.
Committee:	Biomedical Research and Regulation Work Group
OID:	2.16.840.1.113883.4.642.4.1247 (for OID based terminology systems)
Source Resource	XML / JSON

This Code system is used in the following value sets:

• ValueSet: ResearchStudyPhase (Codes for the stage in the progression of a therapy from initial experimental use in humans in clinical trials to post-market evaluation.)

• ValueSet: ResearchStudyPhase (Codes for the stage in the progression of a therapy from initial experimental use in humans in clinical trials to post-market evaluation.)

4.3.14.349.1 Content

4.3.14.349.2 ResearchStudyPhase

Codes for the stage in the progression of a therapy from initial experimental use in humans in clinical trials to post-market evaluation.

This code system http://terminology.hl7.org/CodeSystem/research-study-phase defines the following codes:

Code	Display	Definition
n-a	N/A	Trials without phases (for example, studies of devices or behavioral interventions).
early-phase-1	Early Phase 1	Designation for optional exploratory trials conducted in accordance with the United States Food and Drug Administration's (FDA) 2006 Guidance on Exploratory Investigational New Drug (IND) Studies. Formerly called Phase 0.
phase-1	Phase 1	Includes initial studies to determine the metabolism and pharmacologic actions of drugs in humans, the side effects associated with increasing doses, and to gain early evidence of effectiveness; may include healthy participants and/or

patients.
phase-1-phase-2 | Phase 1/Phase 2 | Trials that are a combination of phases 1 and 2.
phase-2 | Phase 2 | Includes controlled clinical studies conducted to evaluate the effectiveness of the drug for a particular indication or indications in participants with the disease or condition under study and to determine the common short-term side effects and risks.
phase-2-phase-3 | Phase 2/Phase 3 | Trials that are a combination of phases 2 and 3.
phase-3 | Phase 3 | Includes trials conducted after preliminary evidence suggesting effectiveness of the drug has been obtained, and are intended to gather additional information to evaluate the overall benefit-risk relationship of the drug.
phase-4 | Phase 4 | Studies of FDA-approved drugs to delineate additional information including the drug's risks, benefits, and optimal use.

See the full registry of code systems defined as part of FHIR.

Explanation of the columns that may appear on this page:

Level | A few code lists that FHIR defines are hierarchical - each code is assigned a level. See Code System for further information.
Source | The source of the definition of the code (when the value set draws in codes defined elsewhere)
Code | The code (used as the code in the resource instance). If the code is in italics, this indicates that the code is not selectable ('Abstract')
Display | The display (used in the display element of a Coding). If there is no display, implementers should not simply display the code, but map the concept into their application
Definition | An explanation of the meaning of the concept
Comments | Additional notes about how to use the code

4.3.14.350 Code System http://terminology.hl7.org/CodeSystem/media-modality

URL: https://hl7.org/fhir/R4/codesystem-media-modality.html
Orders and Observations Work Group | Maturity Level: 1 | Draft | Use Context: Any

This is a code system defined by the FHIR project.

Summary

Defining URL: | http://terminology.hl7.org/CodeSystem/media-modality
Version: | 4.0.1
Name: | MediaModality
Title: | Media Modality
Definition: | Detailed information about the type of the image - its kind, purpose, or the kind of equipment used to generate it.
Committee: | Orders and Observations Work Group
OID: | 2.16.840.1.113883.4.642.4.1109 (for OID based terminology systems)
Copyright: | This resource includes content from the Digital Imaging and Communications in Medicine (DICOM) Standard, Copyright 2011 by the National Electrical Manufacturers Association
Source Resource | XML / JSON

This Code system is used in the following value sets:

• ValueSet: Media Modality (Detailed information about the type of the image - its kind, purpose, or the kind of equipment used to generate it.)

• ValueSet: Media Modality (Detailed information about the type of the image - its kind, purpose, or the kind of equipment used to generate it.)

4.3.14.350.1 Content

4.3.14.350.2 Media Modality

Detailed information about the type of the image - its kind, purpose, or the kind of equipment used to generate it.

Copyright Statement:

This resource includes content from the Digital Imaging and Communications in Medicine (DICOM) Standard, Copyright 2011 by the National Electrical Manufacturers Association

This code system http://terminology.hl7.org/CodeSystem/media-modality defines the following codes:

Code | Display | Definition
diagram | Diagram | A diagram. Often used in diagnostic reports
fax | Fax | A digital record of a fax document
scan | Scanned Document | A digital scan of a document. This is reserved for when there is not enough metadata to create a document reference
retina | Retina Scan | A retinal image used for identification purposes
fingerprint | Fingerprint | A finger print scan used for identification purposes
iris | Iris Scan | An iris scan used for identification purposes
palm | Palm Scan | A palm scan used for identification purposes
face | Face Scan | A face scan used for identification purposes

See the full registry of code systems defined as part of FHIR.

Explanation of the columns that may appear on this page:

Level | A few code lists that FHIR defines are hierarchical - each code is assigned a level. See Code System for further information.
Source | The source of the definition of the code (when the value set draws in codes defined elsewhere)
Code | The code (used as the code in the resource instance). If the code is in italics, this indicates that the code is not selectable ('Abstract')
Display | The display (used in the display element of a Coding). If there is no display, implementers should not simply display the code, but map the concept into their application
Definition | An explanation of the meaning of the concept
Comments | Additional notes about how to use the code

4.3.14.351 Code System http://terminology.hl7.org/CodeSystem/measure-data-usage

URL: https://hl7.org/fhir/R4/codesystem-measure-data-usage.html
Clinical Quality Information Work Group | Maturity Level: 2 | Trial Use | Use Context: Any

This is a code system defined by the FHIR project.

Summary

Defining URL: | http://terminology.hl7.org/CodeSystem/measure-data-usage
Version: | 4.0.1
Name: | MeasureDataUsage
Title: | MeasureDataUsage
Definition: | The intended usage for supplemental data elements in the measure.
Committee: | Clinical Quality Information Work Group
OID: | 2.16.840.1.113883.4.642.4.1234 (for OID based terminology systems)
Source Resource | XML / JSON

This Code system is used in the following value sets:

• ValueSet: MeasureDataUsage (The intended usage for supplemental data elements in the measure.)
• ValueSet: MeasureDataUsage (The intended usage for supplemental data elements in the measure.)

4.3.14.351.1 Content

4.3.14.351.2 MeasureDataUsage

The intended usage for supplemental data elements in the measure.

This code system http://terminology.hl7.org/CodeSystem/measure-data-usage defines the following codes:

Code | Display | Definition
supplemental-data | Supplemental Data | The data is intended to be provided as additional information alongside the measure results.
risk-adjustment-factor | Risk Adjustment Factor | The data is intended to be used to calculate and apply a risk adjustment model for the measure.

See the full registry of code systems defined as part of FHIR.

Explanation of the columns that may appear on this page:

Level | A few code lists that FHIR defines are hierarchical - each code is assigned a level. See Code System for further information.
Source | The source of the definition of the code (when the value set draws in codes defined elsewhere)
Code | The code (used as the code in the resource instance). If the code is in italics, this indicates that the code is not selectable ('Abstract')
Display | The display (used in the display element of a Coding). If there is no display, implementers should not simply display the code, but map the concept into their application
Definition | An explanation of the meaning of the concept
Comments | Additional notes about how to use the code

4.3.14.352 Code System http://hl7.org/fhir/conditional-delete-status

URL: https://hl7.org/fhir/R4/codesystem-conditional-delete-status.html
FHIR Infrastructure Work Group | Maturity Level: N | Normative (from v4.0.0) | Use Context: Any

| This page has been approved as part of an ANSI standard. See the Conformance Package for further details.

This is a code system defined by the FHIR project.

Summary

Defining URL: | http://hl7.org/fhir/conditional-delete-status
Version: | 4.0.1
Name: | ConditionalDeleteStatus
Title: | ConditionalDeleteStatus
Definition: | A code that indicates how the server supports conditional delete.
Committee: | FHIR Infrastructure Work Group
OID: | 2.16.840.1.113883.4.642.4.195 (for OID based terminology systems)
Source Resource | XML / JSON

This Code system is used in the following value sets:

• ValueSet: ConditionalDeleteStatus (A code that indicates how the server supports conditional delete.)

• ValueSet: ConditionalDeleteStatus (A code that indicates how the server supports conditional delete.)

4.3.14.352.1 Content

4.3.14.352.2 ConditionalDeleteStatus

A code that indicates how the server supports conditional delete.

This code system http://hl7.org/fhir/conditional-delete-status defines the following codes:

Code | Display | Definition
not-supported | Not Supported | No support for conditional deletes.
single | Single Deletes Supported | Conditional deletes are supported, but only single resources at a time.
multiple | Multiple Deletes Supported | Conditional deletes are supported, and multiple resources can be deleted in a single interaction.

See the full registry of code systems defined as part of FHIR.

Explanation of the columns that may appear on this page:

Level | A few code lists that FHIR defines are hierarchical - each code is assigned a level. See Code System for further information.
Source | The source of the definition of the code (when the value set draws in codes defined elsewhere)
Code | The code (used as the code in the resource instance). If the code is in italics, this indicates that the code is not selectable ('Abstract')
Display | The display (used in the display element of a Coding). If there is no display, implementers should not simply display the code, but map the concept into their application
Definition | An explanation of the meaning of the concept
Comments | Additional notes about how to use the code

4.3.14.353 Code System http://hl7.org/fhir/sort-direction

URL: https://hl7.org/fhir/R4/codesystem-sort-direction.html
FHIR Infrastructure Work Group | Maturity Level: 5 | Trial Use | Use Context: Any

This is a code system defined by the FHIR project.

Summary

Defining URL: | http://hl7.org/fhir/sort-direction
Version: | 4.0.1
Name: | SortDirection
Title: | SortDirection
Definition: | The possible sort directions, ascending or descending.
Committee: | FHIR Infrastructure Work Group
OID: | 2.16.840.1.113883.4.642.4.980 (for OID based terminology systems)
Source Resource | XML / JSON

This Code system is used in the following value sets:

• ValueSet: SortDirection (The possible sort directions, ascending or descending.)

• ValueSet: SortDirection (The possible sort directions, ascending or descending.)

4.3.14.353.1 Content

4.3.14.353.2 SortDirection

The possible sort directions, ascending or descending.

This code system http://hl7.org/fhir/sort-direction defines the following codes:

Code | Display | Definition
ascending | Ascending | Sort by the value ascending, so that lower values appear first.
descending | Descending | Sort by the value descending, so that lower values appear last.

See the full registry of code systems defined as part of FHIR.

Explanation of the columns that may appear on this page:

Level | A few code lists that FHIR defines are hierarchical - each code is assigned a level. See Code System for further information.
Source | The source of the definition of the code (when the value set draws in codes defined elsewhere)
Code | The code (used as the code in the resource instance). If the code is in italics, this indicates that the code is not selectable ('Abstract')
Display | The display (used in the display element of a Coding). If there is no display, implementers should not simply display the code, but map the concept into their application
Definition | An explanation of the meaning of the concept
Comments | Additional notes about how to use the code

4.3.14.354 Code System http://hl7.org/fhir/CodeSystem/medication-status

URL: https://hl7.org/fhir/R4/codesystem-medication-status.html
Pharmacy Work Group | Maturity Level: 3 | Trial Use | Use Context: Any

This is a code system defined by the FHIR project.

Summary

Defining URL: | http://hl7.org/fhir/CodeSystem/medication-status
Version: | 4.0.1
Name: | Medication Status Codes
Title: | Medication status codes
Definition: | Medication Status Codes
Committee: | Pharmacy Work Group
OID: | 2.16.840.1.113883.4.642.4.1380 (for OID based terminology systems)
Source Resource | XML / JSON

This Code system is used in the following value sets:

• ValueSet: Medication status codes (Medication Status Codes)

• ValueSet: Medication status codes (Medication Status Codes)

4.3.14.354.1 Content

4.3.14.354.2 Medication status codes

Medication Status Codes

This code system http://hl7.org/fhir/CodeSystem/medication-status defines the following codes:

Code | Display | Definition
active | Active | The medication is available for use.
inactive | Inactive | The medication is not available for use.
entered-in-error | Entered in Error | The medication was entered in error.

See the full registry of code systems defined as part of FHIR.

Explanation of the columns that may appear on this page:

Level | A few code lists that FHIR defines are hierarchical - each code is assigned a level. See Code System for further information.
Source | The source of the definition of the code (when the value set draws in codes defined elsewhere)
Code | The code (used as the code in the resource instance). If the code is in italics, this indicates that the code is not selectable ('Abstract')
Display | The display (used in the display element of a Coding). If there is no display, implementers should not simply display the code, but map the concept into their application
Definition | An explanation of the meaning of the concept
Comments | Additional notes about how to use the code

4.3.14.355 Code System http://terminology.hl7.org/CodeSystem/episodeofcare-type

URL: https://hl7.org/fhir/R4/codesystem-episodeofcare-type.html
Patient Administration Work Group | Maturity Level: 1 | Draft | Use Context: Any

This is a code system defined by the FHIR project.

Summary

Defining URL: | http://terminology.hl7.org/CodeSystem/episodeofcare-type
Version: | 4.0.1
Name: | EpisodeOfCareType
Title: | Episode of care type
Definition: | This example value set defines a set of codes that can be used to express the usage type of an EpisodeOfCare record.
Committee: | Patient Administration Work Group
OID: | 2.16.840.1.113883.4.642.4.1189 (for OID based terminology systems)
Source Resource | XML / JSON

This Code system is used in the following value sets:

• ValueSet: Episode of care type (This example value set defines a set of codes that can be used to express the usage type of an EpisodeOfCare record.)

• ValueSet: Episode of care type (This example value set defines a set of codes that can be used to express the usage type of an EpisodeOfCare record.)

4.3.14.355.1 Content

4.3.14.355.2 Episode of care type

This example value set defines a set of codes that can be used to express the usage type of an EpisodeOfCare record.

This code system http://terminology.hl7.org/CodeSystem/episodeofcare-type defines the following codes:

Code | Display | Definition
hacc | Home and Community Care
pac | Post Acute Care
diab | Post coordinated diabetes program
da | Drug and alcohol rehabilitation
cacp | Community-based aged care

See the full registry of code systems defined as part of FHIR.

Explanation of the columns that may appear on this page:

Level | A few code lists that FHIR defines are hierarchical - each code is assigned a level. See Code System for further information.
Source | The source of the definition of the code (when the value set draws in codes defined elsewhere)
Code | The code (used as the code in the resource instance). If the code is in italics, this indicates that the code is not selectable ('Abstract')
Display | The display (used in the display element of a Coding). If there is no display, implementers should not simply display the code, but map the concept into their application
Definition | An explanation of the meaning of the concept
Comments | Additional notes about how to use the code

4.3.14.356 Code System http://hl7.org/fhir/metric-category

URL: https://hl7.org/fhir/R4/codesystem-metric-category.html
Health Care Devices Work Group | Maturity Level: 1 | Trial Use | Use Context: Any

This is a code system defined by the FHIR project.

Summary

Defining URL: | http://hl7.org/fhir/metric-category
Version: | 4.0.1
Name: | DeviceMetricCategory
Title: | DeviceMetricCategory
Definition: | Describes the category of the metric.
Committee: | Health Care Devices Work Group
OID: | 2.16.840.1.113883.4.642.4.649 (for OID based terminology systems)
Source Resource | XML / JSON

This Code system is used in the following value sets:

• ValueSet: DeviceMetricCategory (Describes the category of the metric.)

• ValueSet: DeviceMetricCategory (Describes the category of the metric.)

4.3.14.356.1 Content

4.3.14.356.2 DeviceMetricCategory

Describes the category of the metric.

This code system http://hl7.org/fhir/metric-category defines the following codes:

Code | Display | Definition
measurement | Measurement | DeviceObservations generated for this DeviceMetric are measured.
setting | Setting | DeviceObservations generated for this DeviceMetric is a setting that will influence the behavior of the Device.
calculation | Calculation | DeviceObservations generated for this DeviceMetric are calculated.
unspecified | Unspecified | The category of this DeviceMetric is unspecified.

See the full registry of code systems defined as part of FHIR.

Explanation of the columns that may appear on this page:

Level | A few code lists that FHIR defines are hierarchical - each code is assigned a level. See Code System for further information.
Source | The source of the definition of the code (when the value set draws in codes defined elsewhere)
Code | The code (used as the code in the resource instance). If the code is in italics, this indicates that the code is not selectable ('Abstract')
Display | The display (used in the display element of a Coding). If there is no display, implementers should not simply display the code, but map the concept into their application
Definition | An explanation of the meaning of the concept
Comments | Additional notes about how to use the code

4.3.14.357 Code System http://terminology.hl7.org/CodeSystem/media-type

URL: https://hl7.org/fhir/R4/codesystem-media-type.html
Orders and Observations Work Group | Maturity Level: 1 | Trial Use | Use Context: Any

This is a code system defined by the FHIR project.

Summary

Defining URL: | http://terminology.hl7.org/CodeSystem/media-type
Version: | 4.0.1
Name: | MediaType
Title: | Media Type
Definition: | Codes for high level media categories.
Committee: | Orders and Observations Work Group
OID: | 2.16.840.1.113883.4.642.1.326 (for OID based terminology systems)
Source Resource | XML / JSON

This Code system is used in the following value sets:

• ValueSet: Media Type (Codes for high level media categories.)

• ValueSet: Media Type (Codes for high level media categories.)

4.3.14.357.1 Content

4.3.14.357.2 Media Type

Codes for high level media categories.

This code system http://terminology.hl7.org/CodeSystem/media-type defines the following codes:

Code | Display | Definition
image | Image | The media consists of one or more unmoving images, including photographs, computer-generated graphs and charts, and scanned documents
video | Video | The media consists of a series of frames that capture a moving image
audio | Audio | The media consists of a sound recording

See the full registry of code systems defined as part of FHIR.

Explanation of the columns that may appear on this page:

Level | A few code lists that FHIR defines are hierarchical - each code is assigned a level. See Code System for further information.
Source | The source of the definition of the code (when the value set draws in codes defined elsewhere)
Code | The code (used as the code in the resource instance). If the code is in italics, this indicates that the code is not selectable ('Abstract')
Display | The display (used in the display element of a Coding). If there is no display, implementers should not simply display the code, but map the concept into their application
Definition | An explanation of the meaning of the concept
Comments | Additional notes about how to use the code

4.3.14.358 Code System http://hl7.org/fhir/assert-operator-codes

URL: https://hl7.org/fhir/R4/codesystem-assert-operator-codes.html
FHIR Infrastructure Work Group | Maturity Level: 2 | Trial Use | Use Context: Any

This is a code system defined by the FHIR project.

Summary

Defining URL: | http://hl7.org/fhir/assert-operator-codes
Version: | 4.0.1
Name: | AssertionOperatorType
Title: | AssertionOperatorType
Definition: | The type of operator to use for assertion.
Committee: | FHIR Infrastructure Work Group
OID: | 2.16.840.1.113883.4.642.4.709 (for OID based terminology systems)
Source Resource | XML / JSON

This Code system is used in the following value sets:

• ValueSet: AssertionOperatorType (The type of operator to use for assertion.)

• ValueSet: AssertionOperatorType (The type of operator to use for assertion.)

4.3.14.358.1 Content

4.3.14.358.2 AssertionOperatorType

The type of operator to use for assertion.

This code system http://hl7.org/fhir/assert-operator-codes defines the following codes:

Code | Display | Definition
equals | equals | Default value. Equals comparison.
notEquals | notEquals | Not equals comparison.
in | in | Compare value within a known set of values.
notIn | notIn | Compare value not within a known set of values.

greaterThan | greaterThan | Compare value to be greater than a known value.
lessThan | lessThan | Compare value to be less than a known value.
empty | empty | Compare value is empty.
notEmpty | notEmpty | Compare value is not empty.
contains | contains | Compare value string contains a known value.
notContains | notContains | Compare value string does not contain a known value.
eval | evaluate | Evaluate the FHIRPath expression as a boolean condition.

See the full registry of code systems defined as part of FHIR.

Explanation of the columns that may appear on this page:

Level | A few code lists that FHIR defines are hierarchical - each code is assigned a level. See Code System for further information.
Source | The source of the definition of the code (when the value set draws in codes defined elsewhere)
Code | The code (used as the code in the resource instance). If the code is in italics, this indicates that the code is not selectable ('Abstract')
Display | The display (used in the display element of a Coding). If there is no display, implementers should not simply display the code, but map the concept into their application
Definition | An explanation of the meaning of the concept
Comments | Additional notes about how to use the code

4.3.14.359 Code System http://hl7.org/fhir/guide-page-generation

URL: https://hl7.org/fhir/R4/codesystem-guide-page-generation.html
FHIR Infrastructure Work Group | Maturity Level: 1 | Trial Use | Use Context: Any

This is a code system defined by the FHIR project.

Summary

Defining URL: | http://hl7.org/fhir/guide-page-generation
Version: | 4.0.1
Name: | GuidePageGeneration
Title: | GuidePageGeneration
Definition: | A code that indicates how the page is generated.
Committee: | FHIR Infrastructure Work Group
OID: | 2.16.840.1.113883.4.642.4.999 (for OID based terminology systems)
Source Resource | XML / JSON

This Code system is used in the following value sets:

• ValueSet: GuidePageGeneration (A code that indicates how the page is generated.)
• ValueSet: GuidePageGeneration (A code that indicates how the page is generated.)

4.3.14.359.1 Content

4.3.14.359.2 GuidePageGeneration

A code that indicates how the page is generated.

This code system http://hl7.org/fhir/guide-page-generation defines the following codes:

Code | Display | Definition
html | HTML | Page is proper xhtml with no templating. Will be brought across unchanged for standard post-processing.
markdown | Markdown | Page is markdown with templating. Will use the template to create a file that imports the markdown file prior to post-processing.
xml | XML | Page is xml with templating. Will use the template to create a file that imports the source file and run the nominated XSLT transform (see parameters) if present prior to post-processing.
generated | Generated | Page will be generated by the publication process - no source to bring across.

See the full registry of code systems defined as part of FHIR.

Explanation of the columns that may appear on this page:

Level | A few code lists that FHIR defines are hierarchical - each code is assigned a level. See Code System for further information.
Source | The source of the definition of the code (when the value set draws in codes defined elsewhere)
Code | The code (used as the code in the resource instance). If the code is in italics, this indicates that the code is not selectable ('Abstract')
Display | The display (used in the display element of a Coding). If there is no display, implementers should not simply display the code, but map the concept into their application
Definition | An explanation of the meaning of the concept
Comments | Additional notes about how to use the code

4.3.14.360 Code System http://terminology.hl7.org/CodeSystem/contractsubtypecodes

URL: https://hl7.org/fhir/R4/codesystem-contract-subtype.html
Financial Management Work Group | Maturity Level: 1 | Draft | Use Context: Any

This is a code system defined by the FHIR project.

Summary

Defining URL: | http://terminology.hl7.org/CodeSystem/contractsubtypecodes
Version: | 4.0.1
Name: | ContractSubtypeCodes
Title: | Contract Subtype Codes
Definition: | This value set includes sample Contract Subtype codes.
Committee: | Financial Management Work Group
OID: | 2.16.840.1.113883.4.642.4.1198 (for OID based terminology systems)
Copyright: | This is an example set.
Source Resource | XML / JSON

This Code system is used in the following value sets:

• ValueSet: Contract Subtype Codes (This value set includes sample Contract Subtype codes.)

• ValueSet: Contract Subtype Codes (This value set includes sample Contract Subtype codes.)

4.3.14.360.1 Content

4.3.14.360.2 Contract Subtype Codes

This value set includes sample Contract Subtype codes.

Copyright Statement:

This is an example set.

This code system http://terminology.hl7.org/CodeSystem/contractsubtypecodes defines the following codes:

Code | Display | Definition
disclosure-ca | Disclosure-CA | Canadian health information disclosure policy.
disclosure-us | Disclosure-US | United States health information disclosure policy.

See the full registry of code systems defined as part of FHIR.

Explanation of the columns that may appear on this page:

Level | A few code lists that FHIR defines are hierarchical - each code is assigned a level. See Code System for further information.
Source | The source of the definition of the code (when the value set draws in codes defined elsewhere)
Code | The code (used as the code in the resource instance). If the code is in italics, this indicates that the code is not selectable ('Abstract')
Display | The display (used in the display element of a Coding). If there is no display, implementers should not simply display the code, but map the concept into their application
Definition | An explanation of the meaning of the concept
Comments | Additional notes about how to use the code

4.3.14.361 Code System http://hl7.org/fhir/messageheader-response-request

URL: https://hl7.org/fhir/R4/codesystem-messageheader-response-request.html
Infrastructure And Messaging Work Group | Maturity Level: 1 | Trial Use | Use Context: Any

This is a code system defined by the FHIR project.

Summary

Defining URL: | http://hl7.org/fhir/messageheader-response-request
Version: | 4.0.1
Name: | messageheader-response-request
Title: | messageheader-response-request
Definition: | HL7-defined table of codes which identify conditions under which acknowledgments are required to be returned in response to a message.
Committee: | Infrastructure And Messaging Work Group
OID: | 2.16.840.1.113883.4.642.4.925 (for OID based terminology systems)
Source Resource | XML / JSON

This Code system is used in the following value sets:

• ValueSet: messageheader-response-request (HL7-defined table of codes which identify conditions under which acknowledgments are required to be returned in response to a message.)

• ValueSet: messageheader-response-request (HL7-defined table of codes which identify conditions under which acknowledgments are required to be returned in response to a message.)

4.3.14.361.1 Content

4.3.14.361.2 messageheader-response-request

HL7-defined table of codes which identify conditions under which acknowledgments are required to be returned in response to a message.

This code system http://hl7.org/fhir/messageheader-response-request defines the following codes:

Code | Display | Definition
always | Always | initiator expects a response for this message.
on-error | Error/reject conditions only | initiator expects a response only if in error.
never | Never | initiator does not expect a response.
on-success | Successful completion only | initiator expects a response only if successful.

See the full registry of code systems defined as part of FHIR.

Explanation of the columns that may appear on this page:

Level | A few code lists that FHIR defines are hierarchical - each code is assigned a level. See Code System for further information.
Source | The source of the definition of the code (when the value set draws in codes defined elsewhere)
Code | The code (used as the code in the resource instance). If the code is in italics, this indicates that the code is not selectable ('Abstract')
Display | The display (used in the display element of a Coding). If there is no display, implementers should not simply display the code, but map the concept into their application
Definition | An explanation of the meaning of the concept
Comments | Additional notes about how to use the code

4.3.14.362 Code System http://hl7.org/fhir/device-nametype

URL: https://hl7.org/fhir/R4/codesystem-device-nametype.html
Orders and Observations Work Group | Maturity Level: 0 | Trial Use | Use Context: Any

This is a code system defined by the FHIR project.

Summary

Defining URL: | http://hl7.org/fhir/device-nametype
Version: | 4.0.1
Name: | DeviceNameType
Title: | DeviceNameType
Definition: | The type of name the device is referred by.
Committee: | Orders and Observations Work Group
OID: | 2.16.840.1.113883.4.642.4.1084 (for OID based terminology systems)
Source Resource | XML / JSON

This Code system is used in the following value sets:

• ValueSet: DeviceNameType (The type of name the device is referred by.)

• ValueSet: DeviceNameType (The type of name the device is referred by.)

4.3.14.362.1 Content

4.3.14.362.2 DeviceNameType

The type of name the device is referred by.

This code system http://hl7.org/fhir/device-nametype defines the following codes:

Code | Display | Definition
udi-label-name | UDI Label name | UDI Label name.
user-friendly-name | User Friendly name | User Friendly name.
patient-reported-name | Patient Reported name | Patient Reported name.
manufacturer-name | Manufacturer name | Manufacturer name.
model-name | Model name | Model name.
other | other | other.

See the full registry of code systems defined as part of FHIR.

Explanation of the columns that may appear on this page:

Level | A few code lists that FHIR defines are hierarchical - each code is assigned a level. See Code System for further information.
Source | The source of the definition of the code (when the value set draws in codes defined elsewhere)
Code | The code (used as the code in the resource instance). If the code is in italics, this indicates that the code is not selectable ('Abstract')
Display | The display (used in the display element of a Coding). If there is no display, implementers should not simply display the code, but map the concept into their application
Definition | An explanation of the meaning of the concept
Comments | Additional notes about how to use the code

4.3.14.363 Code System http://terminology.hl7.org/CodeSystem/adverse-event-outcome

URL: https://hl7.org/fhir/R4/codesystem-adverse-event-outcome.html
Patient Care Work Group | Maturity Level: 0 | Trial Use | Use Context: Any

This is a code system defined by the FHIR project.

Summary

Defining URL: | http://terminology.hl7.org/CodeSystem/adverse-event-outcome
Version: | 4.0.1
Name: | AdverseEventOutcome
Title: | AdverseEventOutcome
Definition: | TODO (and should this be required?).
Committee: | Patient Care Work Group
OID: | 2.16.840.1.113883.4.642.4.1252 (for OID based terminology systems)
Source Resource | XML / JSON

This Code system is used in the following value sets:

• ValueSet: AdverseEventOutcome (TODO (and should this be required?).)

• ValueSet: AdverseEventOutcome (TODO (and should this be required?).)

4.3.14.363.1 Content

4.3.14.363.2 AdverseEventOutcome

TODO (and should this be required?).

This code system http://terminology.hl7.org/CodeSystem/adverse-event-outcome defines the following codes:

Code | Display | Definition
resolved | Resolved
recovering | Recovering
ongoing | Ongoing
resolvedWithSequelae | Resolved with Sequelae
fatal | Fatal
unknown | Unknown

See the full registry of code systems defined as part of FHIR.

Explanation of the columns that may appear on this page:

Level | A few code lists that FHIR defines are hierarchical - each code is assigned a level. See Code System for further information.
Source | The source of the definition of the code (when the value set draws in codes defined elsewhere)
Code | The code (used as the code in the resource instance). If the code is in italics, this indicates that the code is not selectable ('Abstract')
Display | The display (used in the display element of a Coding). If there is no display, implementers should not simply display the code, but map the concept into their application
Definition | An explanation of the meaning of the concept
Comments | Additional notes about how to use the code

4.3.14.364 Code System http://terminology.hl7.org/CodeSystem/payment-type

URL: https://hl7.org/fhir/R4/codesystem-payment-type.html
Financial Management Work Group | Maturity Level: 1 | Draft | Use Context: Any

This is a code system defined by the FHIR project.

Summary

Defining URL: | http://terminology.hl7.org/CodeSystem/payment-type
Version: | 4.0.1
Name: | PaymentTypeCodes
Title: | Payment Type Codes
Definition: | This value set includes sample Payment Type codes.
Committee: | Financial Management Work Group
OID: | 2.16.840.1.113883.4.642.4.1186 (for OID based terminology systems)
Copyright: | This is an example set.
Source Resource | XML / JSON

This Code system is used in the following value sets:

• ValueSet: Payment Type Codes (This value set includes sample Payment Type codes.)

• ValueSet: Payment Type Codes (This value set includes sample Payment Type codes.)

4.3.14.364.1 Content

4.3.14.364.2 Payment Type Codes

This value set includes sample Payment Type codes.

Copyright Statement:

This is an example set.

This code system http://terminology.hl7.org/CodeSystem/payment-type defines the following codes:

Code | Display | Definition
payment | Payment | The amount is partial or complete settlement of the amounts due.
adjustment | Adjustment | The amount is an adjustment regarding claims already paid.
advance | Advance | The amount is an advance against future claims.

See the full registry of code systems defined as part of FHIR.

Explanation of the columns that may appear on this page:

Level | A few code lists that FHIR defines are hierarchical - each code is assigned a level. See Code System for further information.
Source | The source of the definition of the code (when the value set draws in codes defined elsewhere)
Code | The code (used as the code in the resource instance). If the code is in italics, this indicates that the code is not selectable ('Abstract')
Display | The display (used in the display element of a Coding). If there is no display, implementers should not simply display the code, but map the concept into their application
Definition | An explanation of the meaning of the concept
Comments | Additional notes about how to use the code

4.3.14.365 Code System http://terminology.hl7.org/CodeSystem/consentcategorycodes

URL: https://hl7.org/fhir/R4/codesystem-consent-category.html
Community Based Collaborative Care Work Group | Maturity Level: 2 | Trial Use | Use Context: Any

This is a code system defined by the FHIR project.

Summary

Defining URL: | http://terminology.hl7.org/CodeSystem/consentcategorycodes
Version: | 4.0.1
Name: | ConsentCategoryCodes
Title: | Consent Category Codes
Definition: | This value set includes sample Consent Directive Type codes, including several consent directive related LOINC codes; HL7 VALUE SET: ActConsentType(2.16.840.1.113883.1.11.19897); examples of US realm consent directive legal descriptions and references to online and/or downloadable forms such as the SSA-827 Authorization to Disclose Information to the Social Security Administration; and other anticipated consent directives related to participation in a clinical trial, medical procedures, reproductive procedures; health care directive (Living Will); advance directive, do not resuscitate (DNR); Physician Orders for Life-Sustaining Treatment (POLST)
Committee: | Community Based Collaborative Care Work Group
OID: | 2.16.840.1.113883.4.642.4.1226 (for OID based terminology systems)
Copyright: | This value set includes content from LOINC® which is copyright © 1995 Regenstrief Institute, Inc. and the LOINC Committee, and available at no cost under the license at http://loinc.org/terms-of-use
Source Resource | XML / JSON

This Code system is used in the following value sets:

• ValueSet: Consent Category Codes (This value set includes sample Consent Directive Type codes, including several consent directive related LOINC codes; HL7 VALUE SET: ActConsentType(2.16.840.1.113883.1.11.19897); examples of US realm consent directive legal descriptions and references to online and/or downloadable forms such as the SSA-827 Authorization to Disclose Information to the Social Security Administration; and other anticipated consent directives related to participation in a clinical trial, medical procedures, reproductive procedures; health care directive (Living Will); advance directive, do not resuscitate (DNR); Physician Orders for Life-Sustaining Treatment (POLST))

• ValueSet: Consent Category Codes (This value set includes sample Consent Directive Type codes, including several consent directive related LOINC codes; HL7 VALUE SET: ActConsentType(2.16.840.1.113883.1.11.19897); examples of US realm consent directive legal descriptions and references to online and/or downloadable forms such as the SSA-827 Authorization to Disclose Information to the Social Security Administration; and other anticipated consent directives related to participation in a clinical trial, medical procedures, reproductive procedures; health care directive (Living Will); advance directive, do not resuscitate (DNR); Physician Orders for Life-Sustaining Treatment (POLST))

4.3.14.365.1 Content

4.3.14.365.2 Consent Category Codes

This value set includes sample Consent Directive Type codes, including several consent directive related LOINC codes; HL7 VALUE SET: ActConsentType(2.16.840.1.113883.1.11.19897); examples of US realm consent directive legal descriptions and references to online and/or downloadable forms such as the SSA-827 Authorization to Disclose Information to the Social Security Administration; and other anticipated consent directives related to participation in a clinical trial, medical procedures, reproductive procedures; health care directive (Living Will); advance directive, do not resuscitate (DNR); Physician Orders for Life-Sustaining Treatment (POLST)

Copyright Statement:

This value set includes content from LOINC® which is copyright © 1995 Regenstrief Institute, Inc. and the LOINC Committee, and available at no cost under the license at http://loinc.org/terms-of-use

This code system http://terminology.hl7.org/CodeSystem/consentcategorycodes defines the following codes:

Code | Display | Definition
acd | Advance Directive | Any instructions, written or given verbally by a patient to a health care provider in anticipation of potential need for medical treatment. [2005 Honor My Wishes]
dnr | Do Not Resuscitate | A legal document, signed by both the patient and their provider, stating a desire not to have CPR initiated in case of a cardiac event. Note: This form was replaced in 2003 with the Physician Orders for Life-Sustaining Treatment [POLST].
emrgonly | Emergency Only | Opt-in to disclosure of health information for emergency only consent directive. Comment: This general consent directive specifically limits disclosure of health information for purpose of emergency treatment. Additional parameters may further limit the disclosure to specific users, roles, duration, types of information, and impose uses obligations. [ActConsentDirective (2.16.840.1.113883.1.11.20425)]
hcd | Health Care Directive | Patient's document telling patient's health care provider what the patient wants or does not want if the patient is diagnosed as being terminally ill and in a persistent vegetative state or in a permanently unconscious condition.[2005 Honor My Wishes]
npp | Notice of Privacy Practices | Acknowledgement of custodian notice of privacy practices. Usage Notes: This type of consent directive acknowledges a custodian's notice of privacy practices including its permitted collection, access, use and disclosure of health information to users and for purposes of use specified. [ActConsentDirective (2.16.840.1.113883.1.11.20425)]
polst | POLST | The Physician Order for Life-Sustaining Treatment form records a person's health care wishes for end of life emergency treatment and translates them into an order by the physician. It must be reviewed and signed by both the patient and the physician, Advanced Registered Nurse Practitioner or Physician Assistant. [2005 Honor My Wishes] Comment: Opt-in Consent Directive with restrictions.
research | Research Information Access | Consent to have healthcare information in an electronic health record accessed for research purposes. [VALUE SET: ActConsentType (2.16.840.1.113883.1.11.19897)]
rsdid | De-identified Information Access | Consent to have de-identified healthcare information in an electronic health record that is accessed for research purposes, but without consent to re-identify the information under any circumstance. [VALUE SET: ActConsentType (2.16.840.1.113883.1.11.19897)
rsreid | Re-identifiable Information Access | Consent to have de-identified healthcare information in an electronic health record that is accessed for research purposes re-identified under specific circumstances outlined in the consent. [VALUE SET: ActConsentType (2.16.840.1.113883.1.11.19897)]

See the full registry of code systems defined as part of FHIR.

Explanation of the columns that may appear on this page:

Level | A few code lists that FHIR defines are hierarchical - each code is assigned a level. See Code System for further information.
Source | The source of the definition of the code (when the value set draws in codes defined elsewhere)
Code | The code (used as the code in the resource instance). If the code is in italics, this indicates that the code is not selectable ('Abstract')
Display | The display (used in the display element of a Coding). If there is no display, implementers should not simply display the code, but map the concept into their application
Definition | An explanation of the meaning of the concept
Comments | Additional notes about how to use the code

4.3.14.366 Code System http://hl7.org/fhir/subscription-channel-type

URL: https://hl7.org/fhir/R4/codesystem-subscription-channel-type.html
FHIR Infrastructure Work Group | Maturity Level: 3 | Trial Use | Use Context: Any

This is a code system defined by the FHIR project.

Summary

Defining URL: | http://hl7.org/fhir/subscription-channel-type
Version: | 4.0.1
Name: | SubscriptionChannelType
Title: | SubscriptionChannelType
Definition: | The type of method used to execute a subscription.
Committee: | FHIR Infrastructure Work Group
OID: | 2.16.840.1.113883.4.642.4.501 (for OID based terminology systems)
Source Resource | XML / JSON

This Code system is used in the following value sets:

• ValueSet: SubscriptionChannelType (The type of method used to execute a subscription.)
• ValueSet: SubscriptionChannelType (The type of method used to execute a subscription.)

4.3.14.366.1 Content

4.3.14.366.2 SubscriptionChannelType

The type of method used to execute a subscription.

This code system http://hl7.org/fhir/subscription-channel-type defines the following codes:

Code | Display | Definition

rest-hook | Rest Hook | The channel is executed by making a post to the URI. If a payload is included, the URL is interpreted as the service base, and an update (PUT) is made.
websocket | Websocket | The channel is executed by sending a packet across a web socket connection maintained by the client. The URL identifies the websocket, and the client binds to this URL.
email | Email | The channel is executed by sending an email to the email addressed in the URI (which must be a mailto:).
sms | SMS | The channel is executed by sending an SMS message to the phone number identified in the URL (tel:).
message | Message | The channel is executed by sending a message (e.g. a Bundle with a MessageHeader resource etc.) to the application identified in the URI.

See the full registry of code systems defined as part of FHIR.

Explanation of the columns that may appear on this page:

Level | A few code lists that FHIR defines are hierarchical - each code is assigned a level. See Code System for further information.
Source | The source of the definition of the code (when the value set draws in codes defined elsewhere)
Code | The code (used as the code in the resource instance). If the code is in italics, this indicates that the code is not selectable ('Abstract')
Display | The display (used in the display element of a Coding). If there is no display, implementers should not simply display the code, but map the concept into their application
Definition | An explanation of the meaning of the concept
Comments | Additional notes about how to use the code

4.3.14.367 Code System http://terminology.hl7.org/CodeSystem/service-referral-method

URL: https://hl7.org/fhir/R4/codesystem-service-referral-method.html
Patient Administration Work Group | Maturity Level: 1 | Draft | Use Context: Any

This is a code system defined by the FHIR project.

Summary

Defining URL: | http://terminology.hl7.org/CodeSystem/service-referral-method
Version: | 4.0.1
Name: | ReferralMethod
Title: | ReferralMethod
Definition: | The methods of referral can be used when referring to a specific HealthCareService resource.
Committee: | Patient Administration Work Group
OID: | 2.16.840.1.113883.4.642.4.1142 (for OID based terminology systems)
Source Resource | XML / JSON

This Code system is used in the following value sets:

• ValueSet: ReferralMethod (The methods of referral can be used when referring to a specific HealthCareService resource.)

• ValueSet: ReferralMethod (The methods of referral can be used when referring to a specific HealthCareService resource.)

4.3.14.367.1 Content

4.3.14.367.2 ReferralMethod

The methods of referral can be used when referring to a specific HealthCareService resource.

This code system http://terminology.hl7.org/CodeSystem/service-referral-method defines the following codes:

Code | Display | Definition
fax | Fax | Referrals may be accepted by fax.
phone | Phone | Referrals may be accepted over the phone from a practitioner.
elec | Secure Messaging | Referrals may be accepted via a secure messaging system. To determine the types of secure messaging systems supported, refer to the identifiers collection. Callers will need to understand the specific identifier system used to know that they are able to transmit messages.
semail | Secure Email | Referrals may be accepted via a secure email. To send please encrypt with the services public key.
mail | Mail | Referrals may be accepted via regular postage (or hand delivered).

See the full registry of code systems defined as part of FHIR.

Explanation of the columns that may appear on this page:

Level | A few code lists that FHIR defines are hierarchical - each code is assigned a level. See Code System for further information.
Source | The source of the definition of the code (when the value set draws in codes defined elsewhere)
Code | The code (used as the code in the resource instance). If the code is in italics, this indicates that the code is not selectable ('Abstract')
Display | The display (used in the display element of a Coding). If there is no display, implementers should not simply display the code, but map the concept into their application
Definition | An explanation of the meaning of the concept
Comments | Additional notes about how to use the code

4.3.14.368 Code System http://terminology.hl7.org/CodeSystem/allergyintolerance-clinical

URL: https://hl7.org/fhir/R4/codesystem-allergyintolerance-clinical.html
Patient Care Work Group | Maturity Level: 3 | Trial Use | Use Context: Any

This is a code system defined by the FHIR project.

Summary

Defining URL: | http://terminology.hl7.org/CodeSystem/allergyintolerance-clinical
Version: | 4.0.1
Name: | AllergyIntoleranceClinicalStatusCodes
Title: | AllergyIntolerance Clinical Status Codes
Definition: | Preferred value set for AllergyIntolerance Clinical Status.
Committee: | Patient Care Work Group
OID: | 2.16.840.1.113883.4.642.4.1373 (for OID based terminology systems)
Source Resource | XML / JSON

This Code system is used in the following value sets:

• ValueSet: AllergyIntolerance Clinical Status Codes (Preferred value set for AllergyIntolerance Clinical Status.)

• ValueSet: AllergyIntolerance Clinical Status Codes (Preferred value set for AllergyIntolerance Clinical Status.)

4.3.14.368.1 Content

4.3.14.368.2 AllergyIntolerance Clinical Status Codes

Preferred value set for AllergyIntolerance Clinical Status.

This code system http://terminology.hl7.org/CodeSystem/allergyintolerance-clinical defines the following codes:

Lvl | Code | Display | Definition
1 | active | Active | The subject is currently experiencing, or is at risk of, a reaction to the identified substance.
1 | inactive | Inactive | The subject is no longer at risk of a reaction to the identified substance.
2 | resolved | Resolved | A reaction to the identified substance has been clinically reassessed by testing or re-exposure and is considered no longer to be present. Re-exposure could be accidental, unplanned, or outside of any clinical setting.

See the full registry of code systems defined as part of FHIR.

Explanation of the columns that may appear on this page:

Level | A few code lists that FHIR defines are hierarchical - each code is assigned a level. See Code System for further information.
Source | The source of the definition of the code (when the value set draws in codes defined elsewhere)
Code | The code (used as the code in the resource instance). If the code is in italics, this indicates that the code is not selectable ('Abstract')
Display | The display (used in the display element of a Coding). If there is no display, implementers should not simply display the code, but map the concept into their application
Definition | An explanation of the meaning of the concept
Comments | Additional notes about how to use the code

4.3.14.369 Code System http://hl7.org/fhir/reference-handling-policy

URL: https://hl7.org/fhir/R4/codesystem-reference-handling-policy.html
FHIR Infrastructure Work Group | Maturity Level: N | Normative (from v4.0.0) | Use Context: Any

| This page has been approved as part of an ANSI standard. See the Conformance Package for further details.

This is a code system defined by the FHIR project.

Summary

Defining URL: | http://hl7.org/fhir/reference-handling-policy
Version: | 4.0.1
Name: | ReferenceHandlingPolicy
Title: | ReferenceHandlingPolicy
Definition: | A set of flags that defines how references are supported.
Committee: | FHIR Infrastructure Work Group
OID: | 2.16.840.1.113883.4.642.4.203 (for OID based terminology systems)
Source Resource | XML / JSON

This Code system is used in the following value sets:

• ValueSet: ReferenceHandlingPolicy (A set of flags that defines how references are supported.)

• ValueSet: ReferenceHandlingPolicy (A set of flags that defines how references are supported.)

4.3.14.369.1 Content

4.3.14.369.2 ReferenceHandlingPolicy

A set of flags that defines how references are supported.

This code system http://hl7.org/fhir/reference-handling-policy defines the following codes:

Code | Display | Definition
literal | Literal References | The server supports and populates Literal references (i.e. using Reference.reference) where they are known (this code does not guarantee that all references are literal; see 'enforced').
logical | Logical References | The server allows logical references (i.e. using Reference.identifier).
resolves | Resolves References | The server will attempt to resolve logical references to literal references - i.e. converting Reference.identifier to Reference.reference (if resolution fails, the server may still accept resources; see logical).
enforced | Reference Integrity Enforced | The server enforces that references have integrity - e.g. it ensures that references can always be resolved. This is typically the case for clinical record systems, but often not the case for middleware/proxy systems.
local | Local References Only | The server does not support references that point to other servers.

See the full registry of code systems defined as part of FHIR.

Explanation of the columns that may appear on this page:

Level | A few code lists that FHIR defines are hierarchical - each code is assigned a level. See Code System for further information.
Source | The source of the definition of the code (when the value set draws in codes defined elsewhere)
Code | The code (used as the code in the resource instance). If the code is in italics, this indicates that the code is not selectable ('Abstract')
Display | The display (used in the display element of a Coding). If there is no display, implementers should not simply display the code, but map the concept into their application
Definition | An explanation of the meaning of the concept
Comments | Additional notes about how to use the code

4.3.14.370 Code System http://hl7.org/fhir/language-preference-type

URL: https://hl7.org/fhir/R4/codesystem-language-preference-type.html
Vocabulary Work Group | Maturity Level: 0 | Informative | Use Context: Any

This is a code system defined by the FHIR project.

Summary

Defining URL: | http://hl7.org/fhir/language-preference-type
Version: | 4.0.1
Name: | LanguagePreferenceType
Title: | Language preference type
Definition: | This value set defines the set of codes for describing the type or mode of the patient's preferred language.
Committee: | ??
OID: | 2.16.840.1.113883.4.642.4.1023 (for OID based terminology systems)
Source Resource | XML / JSON

This Code system is used in the following value sets:

• ValueSet: Language preference type (This value set defines the set of codes for describing the type or mode of the patient's preferred language.)

• ValueSet: Language preference type (This value set defines the set of codes for describing the type or mode of the patient's preferred language.)

4.3.14.370.1 Content

4.3.14.370.2 Language preference type

This value set defines the set of codes for describing the type or mode of the patient's preferred language.

This code system http://hl7.org/fhir/language-preference-type defines the following codes:

Code | Display | Definition
verbal | verbal | The patient prefers to verbally communicate with the associated language.
written | written | The patient prefers to communicate in writing with the associated language.

See the full registry of code systems defined as part of FHIR.

Explanation of the columns that may appear on this page:

Level | A few code lists that FHIR defines are hierarchical - each code is assigned a level. See Code System for further information.
Source | The source of the definition of the code (when the value set draws in codes defined elsewhere)
Code | The code (used as the code in the resource instance). If the code is in italics, this indicates that the code is not selectable ('Abstract')
Display | The display (used in the display element of a Coding). If there is no display, implementers should not simply display the code, but map the concept into their application
Definition | An explanation of the meaning of the concept
Comments | Additional notes about how to use the code

4.3.14.371 Code System http://terminology.hl7.org/CodeSystem/extra-security-role-type

URL: https://hl7.org/fhir/R4/codesystem-extra-security-role-type.html
Vocabulary Work Group | Maturity Level: 0 | Informative | Use Context: Not Intended for Production use

This is a code system defined by the FHIR project.

Summary

Defining URL: | http://terminology.hl7.org/CodeSystem/extra-security-role-type
Version: | 4.0.1
Name: | SecurityRoleType
Title:
Definition: | This CodeSystem contains Additional FHIR-defined Security Role types not defined elsewhere
Committee: | ??
OID: | (for OID based terminology systems)
Source Resource | XML / JSON

This Code system is used in the following value sets:

• ValueSet: ParticipationRoleType (This FHIR value set is comprised of Actor participation Type codes, which can be used to value FHIR agents, actors, and other role elements. The FHIR Actor participation type value set is based on DICOM Audit Message, C402; ASTM Standard, E1762-95 [2013]; selected codes and derived actor roles from HL7 RoleClass OID 2.16.840.1.113883.5.110; HL7 Role Code 2.16.840.1.113883.5.111, including AgentRoleType; HL7 ParticipationType OID: 2.16.840.1.113883.5.90; and HL7 ParticipationFunction codes OID: 2.16.840.1.113883.5.88. This value set includes, by reference, role codes from external code systems: NUCC Health Care Provider Taxonomy OID: 2.16.840.1.113883.6.101; North American Industry Classification System [NAICS]OID: 2.16.840.1.113883.6.85; IndustryClassificationSystem 2.16.840.1.113883.1.11.16039; and US Census Occupation Code OID: 2.16.840.1.113883.6.243 for relevant recipient or custodian codes not included in this value set. If no source is indicated in the definition comments, then these are example FHIR codes.)

• ValueSet: ParticipationRoleType (This FHIR value set is comprised of Actor participation Type codes, which can be used to value FHIR agents, actors, and other role elements. The FHIR Actor participation type value set is based on DICOM Audit Message, C402; ASTM Standard, E1762-95 [2013]; selected codes and derived actor roles from HL7 RoleClass OID 2.16.840.1.113883.5.110; HL7 Role Code 2.16.840.1.113883.5.111, including AgentRoleType; HL7 ParticipationType OID: 2.16.840.1.113883.5.90; and HL7 ParticipationFunction codes OID: 2.16.840.1.113883.5.88. This value set includes, by reference, role codes from external code systems: NUCC Health Care Provider Taxonomy OID: 2.16.840.1.113883.6.101; North American Industry Classification System [NAICS]OID: 2.16.840.1.113883.6.85; IndustryClassificationSystem 2.16.840.1.113883.1.11.16039; and US Census Occupation Code OID: 2.16.840.1.113883.6.243 for relevant recipient or custodian codes not included in this value set. If no source is indicated in the definition comments, then these are example FHIR codes.)

• ValueSet: SecurityRoleType (This example FHIR value set is comprised of example Actor Type codes, which can be used to value FHIR agents, actors, and other role elements such as those specified in financial transactions. The FHIR Actor value set is based on DICOM Audit Message, C402; ASTM Standard, E1762-95 [2013]; selected codes and derived actor roles from HL7 RoleClass OID 2.16.840.1.113883.5.110; HL7 Role Code 2.16.840.1.113883.5.111, including AgentRoleType; HL7 ParticipationType OID: 2.16.840.1.113883.5.90; and HL7 ParticipationFunction codes OID: 2.16.840.1.113883.5.88. This value set includes, by reference, role codes from external code systems: NUCC Health Care Provider Taxonomy OID: 2.16.840.1.113883.6.101; North American Industry Classification System [NAICS]OID: 2.16.840.1.113883.6.85; IndustryClassificationSystem 2.16.840.1.113883.1.11.16039; and US Census Occupation Code OID: 2.16.840.1.113883.6.243 for relevant recipient or custodian codes not included in this value set. If no source is indicated in the definition comments, then these are example FHIR codes. It can be extended with appropriate roles described by SNOMED as well as those described in the HL7 Role Based Access Control Catalog and the HL7 Healthcare (Security and Privacy) Access Control Catalog. In Role-Based Access Control (RBAC), permissions are operations on an object that a user wishes to access. Permissions are grouped into roles. A role characterizes the functions a user is allowed to perform. Roles are assigned to users. If the user's role has the appropriate permissions to access an object, then that user is granted access to the object. FHIR readily enables RBAC, as FHIR Resources are object types and the CRUDE events (the FHIR equivalent to permissions in the RBAC scheme) are operations on those objects. In Attribute-Based Access Control (ABAC), a user requests to perform operations on objects. That user's access request is granted or denied based on a set of access control policies that are specified in terms of attributes and conditions. FHIR readily enables ABAC, as instances of a Resource in FHIR (again, Resources are object types) can have attributes associated with them. These attributes include security tags, environment conditions, and a host of user and object characteristics, which are the same attributes as those used in ABAC. Attributes help define the access control policies that determine the operations a user may perform on a Resource (in FHIR) or object (in ABAC). For example, a tag (or attribute) may specify that the identified Resource (object) is not to be further disclosed without explicit consent from the patient.)

• ValueSet: SecurityRoleType (This example FHIR value set is comprised of example Actor Type codes, which can be used to value FHIR agents, actors, and other role elements such as those specified in financial transactions. The FHIR Actor value set is based on DICOM Audit Message, C402; ASTM Standard, E1762-95 [2013]; selected codes and derived actor roles from HL7 RoleClass OID 2.16.840.1.113883.5.110; HL7 Role Code 2.16.840.1.113883.5.111, including AgentRoleType; HL7 ParticipationType OID: 2.16.840.1.113883.5.90; and HL7 ParticipationFunction codes OID: 2.16.840.1.113883.5.88. This value set includes, by reference, role codes from external code systems: NUCC Health Care Provider Taxonomy OID: 2.16.840.1.113883.6.101; North American Industry Classification System [NAICS]OID: 2.16.840.1.113883.6.85; IndustryClassificationSystem 2.16.840.1.113883.1.11.16039; and US Census Occupation Code OID: 2.16.840.1.113883.6.243 for relevant recipient or custodian codes not included in this value set. If no source is indicated in the definition comments, then these are example FHIR codes. It can be extended with appropriate roles described by SNOMED as well as those described in the HL7 Role Based Access Control Catalog and the HL7 Healthcare (Security and Privacy) Access Control Catalog. In Role-Based Access Control (RBAC), permissions are operations on an object that a user wishes to access. Permissions are grouped into roles. A role characterizes the functions a user is allowed to perform. Roles are assigned to users. If the user's role has the appropriate permissions to access an object, then that user is granted access to the object. FHIR readily enables RBAC, as FHIR Resources are object types and the CRUDE events (the FHIR equivalent to permissions in the RBAC scheme) are operations on those objects. In Attribute-Based Access Control (ABAC), a user requests to perform operations on objects. That user's access request is granted or denied based on a set of access control policies that are specified in terms of attributes and conditions. FHIR readily enables ABAC, as instances of a Resource in FHIR (again, Resources are object types) can have attributes associated with them. These attributes include security tags, environment conditions, and a host of user and object characteristics, which are the same attributes as those used in ABAC. Attributes help define the access control policies that determine the operations a user may perform on a Resource (in FHIR) or object (in ABAC). For example, a tag (or attribute) may specify that the identified Resource (object) is not to be further disclosed without explicit consent from the patient.)

4.3.14.371.1 Content

4.3.14.371.2 SecurityRoleType

This CodeSystem contains Additional FHIR-defined Security Role types not defined elsewhere

This code system http://terminology.hl7.org/CodeSystem/extra-security-role-type defines the following codes:

Code | Display | Definition
authserver | authorization server | An entity providing authorization services to enable the electronic sharing of health-related information based on resource owner's preapproved permissions. For example, an UMA Authorization Server[UMA]
datacollector | data collector | An entity that collects information over which the data subject may have certain rights under policy or law to control that information's management and distribution by data collectors, including the right to access, retrieve, distribute, or delete that information.
dataprocessor | data processor | An entity that processes collected information over which the data subject may have certain rights under policy or law to control that information's management and distribution by data processors, including the right to access, retrieve, distribute, or delete that information.
datasubject | data subject | A person whose personal information is collected or processed, and who may have certain rights under policy or law to control that information's management and distribution by data collectors or processors, including the right to access, retrieve, distribute, or delete that information.
humanuser | human user | The human user that has participated.

See the full registry of code systems defined as part of FHIR.

Explanation of the columns that may appear on this page:

Level | A few code lists that FHIR defines are hierarchical - each code is assigned a level. See Code System for further information.
Source | The source of the definition of the code (when the value set draws in codes defined elsewhere)
Code | The code (used as the code in the resource instance). If the code is in italics, this indicates that the code is not selectable ('Abstract')
Display | The display (used in the display element of a Coding). If there is no display, implementers should not simply display the code, but map the concept into their application
Definition | An explanation of the meaning of the concept
Comments | Additional notes about how to use the code

4.3.14.372 Code System http://hl7.org/fhir/contract-status

URL: https://hl7.org/fhir/R4/codesystem-contract-status.html
Financial Management Work Group | Maturity Level: 1 | Trial Use | Use Context: Any

This is a code system defined by the FHIR project.

Summary

Defining URL: | http://hl7.org/fhir/contract-status
Version: | 4.0.1
Name: | ContractResourceStatusCodes
Title: | Contract Resource Status Codes
Definition: | This value set contract specific codes for status.

Committee: | Financial Management Work Group
OID: | 2.16.840.1.113883.4.642.4.744 (for OID based terminology systems)
Copyright: | HL7 International.
Source Resource | XML / JSON

This Code system is used in the following value sets:

• ValueSet: Contract Resource Status Codes (This value set contract specific codes for status.)

• ValueSet: Contract Resource Status Codes (This value set contract specific codes for status.)

4.3.14.372.1 Content

Each definition includes usage notes explaining the precedence order in contract lifecycle - i.e., while only some stages are required, the order in which they may occur is deterministic; and a map to comparable FHIR and v.3 status codes. It follows guidance about use of status codes in FHIR at http://build.fhir.org/sc.html.

4.3.14.372.2 Contract Resource Status Codes

This value set contract specific codes for status.

Copyright Statement:

HL7 International.

This code system http://hl7.org/fhir/contract-status defines the following codes:

Code | Display | Definition
amended | Amended | Contract is augmented with additional information to correct errors in a predecessor or to updated values in a predecessor. Usage: Contract altered within effective time. Precedence Order = 9. Comparable FHIR and v.3 status codes: revised; replaced.
appended | Appended | Contract is augmented with additional information that was missing from a predecessor Contract. Usage: Contract altered within effective time. Precedence Order = 9. Comparable FHIR and v.3 status codes: updated, replaced.
cancelled | Cancelled | Contract is terminated due to failure of the Grantor and/or the Grantee to fulfil one or more contract provisions. Usage: Abnormal contract termination. Precedence Order = 10. Comparable FHIR and v.3 status codes: stopped; failed; aborted.
disputed | Disputed | Contract is pended to rectify failure of the Grantor or the Grantee to fulfil contract provision(s). E.g., Grantee complaint about Grantor's failure to comply with contract provisions. Usage: Contract pended. Precedence Order = 7. Comparable FHIR and v.3 status codes: on hold; pended; suspended.
entered-in-error | Entered in Error | Contract was created in error. No Precedence Order. Status may be applied to a Contract with any status.
executable | Executable | Contract execution pending; may be executed when either the Grantor or the Grantee accepts the contract provisions by signing. I.e., where either the Grantor or the Grantee has signed, but not both. E.g., when an insurance applicant signs the insurers application, which references the policy. Usage: Optional first step of contract execution activity. May be skipped and contracting activity moves directly to executed state. Precedence Order = 3. Comparable FHIR and v.3 status codes: draft; preliminary; planned; intended; active.
executed | Executed | Contract is activated for period stipulated when both the Grantor and Grantee have signed it. Usage: Required state for normal completion of contracting activity. Precedence Order = 6. Comparable FHIR and v.3 status codes: accepted; completed.
negotiable | Negotiable | Contract execution is suspended while either or both the Grantor and Grantee propose and consider new or revised contract provisions. I.e., where the party which has not signed proposes changes to the terms. E .g., a life insurer declines to agree to the signed application because the life insurer has evidence that the applicant, who asserted to being younger or a non-smoker to get a lower premium rate - but offers instead to agree to a higher premium based on the applicants actual age or smoking status. Usage: Optional contract activity between executable and executed state. Precedence Order = 4. Comparable FHIR and v.3 status codes: in progress; review; held.
offered | Offered | Contract is a proposal by either the Grantor or the Grantee. Aka - A Contract hard copy or electronic 'template', 'form' or 'application'. E.g., health insurance application; consent directive form. Usage: Beginning of contract negotiation, which may have been completed as a precondition because used for 0..* contracts. Precedence Order = 2. Comparable FHIR and v.3 status codes: requested; new.
policy | Policy | Contract template is available as the basis for an application or offer by the Grantor or Grantee. E.g., health insurance policy; consent directive policy. Usage: Required initial contract activity, which may have been completed as a precondition because used for 0..* contracts. Precedence Order = 1. Comparable FHIR and v.3 status codes: proposed; intended.
rejected | Rejected | Execution of the Contract is not completed because either or both the Grantor and Grantee decline to accept some or all of the contract provisions. Usage: Optional contract activity between executable and abnormal termination. Precedence Order = 5. Comparable FHIR and v.3 status codes: stopped; cancelled.
renewed | Renewed | Beginning of a successor Contract at the termination of predecessor Contract lifecycle. Usage: Follows termination of a preceding Contract that has reached its expiry date. Precedence Order = 13. Comparable FHIR and v.3 status codes: superseded.
revoked | Revoked | A Contract that is rescinded. May be required prior to replacing with an updated Contract. Comparable FHIR and v.3 status codes: nullified.
resolved | Resolved | Contract is reactivated after being pended because of faulty execution. *E.g., competency of the signer(s), or where the policy is substantially different from and did not accompany the application/form so that the applicant could not compare them. Aka - ''reactivated''. Usage: Optional stage where a pended contract is reactivated. Precedence Order = 8. Comparable FHIR and v.3 status codes: reactivated.
terminated | Terminated | Contract reaches its expiry date. It might or might not be renewed or renegotiated. Usage: Normal end of contract period. Precedence Order = 12. Comparable FHIR and v.3 status codes: Obsoleted.

See the full registry of code systems defined as part of FHIR.

Explanation of the columns that may appear on this page:

Level | A few code lists that FHIR defines are hierarchical - each code is assigned a level. See Code System for further information.

Source | The source of the definition of the code (when the value set draws in codes defined elsewhere)
Code | The code (used as the code in the resource instance). If the code is in italics, this indicates that the code is not selectable ('Abstract')
Display | The display (used in the display element of a Coding). If there is no display, implementers should not simply display the code, but map the concept into their application
Definition | An explanation of the meaning of the concept
Comments | Additional notes about how to use the code

4.3.14.373 Code System http://terminology.hl7.org/CodeSystem/ex-paymenttype

URL: https://hl7.org/fhir/R4/codesystem-ex-paymenttype.html
Financial Management Work Group | Maturity Level: 1 | Draft | Use Context: Any

This is a code system defined by the FHIR project.

Summary

Defining URL: | http://terminology.hl7.org/CodeSystem/ex-paymenttype
Version: | 4.0.1
Name: | ExamplePaymentTypeCodes
Title: | Example Payment Type Codes
Definition: | This value set includes example Payment Type codes.
Committee: | Financial Management Work Group
OID: | 2.16.840.1.113883.4.642.4.1181 (for OID based terminology systems)
Copyright: | This is an example set.
Source Resource | XML / JSON

This Code system is used in the following value sets:

• ValueSet: Example Payment Type Codes (This value set includes example Payment Type codes.)
• ValueSet: Example Payment Type Codes (This value set includes example Payment Type codes.)

4.3.14.373.1 Content

4.3.14.373.2 Example Payment Type Codes

This value set includes example Payment Type codes.

Copyright Statement:

This is an example set.

This code system http://terminology.hl7.org/CodeSystem/ex-paymenttype defines the following codes:

Code | Display | Definition
complete | Complete | Complete (final) payment of the benefit under the Claim less any adjustments.
partial | Partial | Partial payment of the benefit under the Claim less any adjustments.

See the full registry of code systems defined as part of FHIR.

Explanation of the columns that may appear on this page:

Level | A few code lists that FHIR defines are hierarchical - each code is assigned a level. See Code System for further information.
Source | The source of the definition of the code (when the value set draws in codes defined elsewhere)
Code | The code (used as the code in the resource instance). If the code is in italics, this indicates that the code is not selectable ('Abstract')
Display | The display (used in the display element of a Coding). If there is no display, implementers should not simply display the code, but map the concept into their application
Definition | An explanation of the meaning of the concept
Comments | Additional notes about how to use the code

4.3.14.374 Code System http://hl7.org/fhir/secondary-finding

URL: https://hl7.org/fhir/R4/codesystem-secondary-finding.html
Vocabulary Work Group | Maturity Level: 0 | Informative | Use Context: Any

This is a code system defined by the FHIR project.

Summary

Defining URL: | http://hl7.org/fhir/secondary-finding
Version: | 4.0.1
Name: | ObservationCategoryCodes
Title: | Observation Category Codes
Definition: | Codes to denote a guideline or policy statement.when a genetic test result is being shared as a secondary finding.
Committee: | ??
OID: | 2.16.840.1.113883.4.642.4.1286 (for OID based terminology systems)
Source Resource | XML / JSON

This Code system is used in the following value sets:

• ValueSet: Observation Category Codes (Codes to denote a guideline or policy statement.when a genetic test result is being shared as a secondary finding.)

• ValueSet: Observation Category Codes (Codes to denote a guideline or policy statement.when a genetic test result is being shared as a secondary finding.)

4.3.14.374.1 Content

4.3.14.374.2 Observation Category Codes

Codes to denote a guideline or policy statement.when a genetic test result is being shared as a secondary finding.

This code system http://hl7.org/fhir/secondary-finding defines the following codes:

Code | Display | Definition
acmg-version1 | ACMG Version 1 | First release (2013): ACMG Recommendations for Reporting of Incidental Findings in Clinical Exome and Genome Sequencing. https://www.ncbi.nlm.nih.gov/pmc/articles/PMC3727274/
acmg-version2 | ACMG Version 2 | Second release (2016): Recommendations for reporting of secondary findings in clinical exome and genome sequencing, 2016 update (ACMG SF v2.0): a policy statement of the American College of Medical Genetics and Genomics. https://www.ncbi.nlm.nih.gov/pubmed/27854360

See the full registry of code systems defined as part of FHIR.

Explanation of the columns that may appear on this page:

Level | A few code lists that FHIR defines are hierarchical - each code is assigned a level. See Code System for further information.
Source | The source of the definition of the code (when the value set draws in codes defined elsewhere)
Code | The code (used as the code in the resource instance). If the code is in italics, this indicates that the code is not selectable ('Abstract')
Display | The display (used in the display element of a Coding). If there is no display, implementers should not simply display the code, but map the concept into their application
Definition | An explanation of the meaning of the concept
Comments | Additional notes about how to use the code

4.3.14.375 Code System http://terminology.hl7.org/CodeSystem/certainty-subcomponent-rating

URL: https://hl7.org/fhir/R4/codesystem-certainty-subcomponent-rating.html
Clinical Decision Support Work Group | Maturity Level: 0 | Trial Use | Use Context: Any

This is a code system defined by the FHIR project.

Summary

Defining URL: | http://terminology.hl7.org/CodeSystem/certainty-subcomponent-rating
Version: | 4.0.1
Name: | CertaintySubcomponentRating
Title: | CertaintySubcomponentRating
Definition: | The quality rating of the subcomponent of a quality of evidence rating.
Committee: | Clinical Decision Support Work Group
OID: | 2.16.840.1.113883.4.642.4.1362 (for OID based terminology systems)
Source Resource | XML / JSON

This Code system is used in the following value sets:

• ValueSet: CertaintySubcomponentRating (The quality rating of the subcomponent of a quality of evidence rating.)

• ValueSet: CertaintySubcomponentRating (The quality rating of the subcomponent of a quality of evidence rating.)

4.3.14.375.1 Content

4.3.14.375.2 CertaintySubcomponentRating

The quality rating of the subcomponent of a quality of evidence rating.

This code system http://terminology.hl7.org/CodeSystem/certainty-subcomponent-rating defines the following codes:

Code | Display | Definition
no-change | no change to rating | no change to quality rating.
downcode1 | reduce rating: -1 | reduce quality rating by 1.
downcode2 | reduce rating: -2 | reduce quality rating by 2.
downcode3 | reduce rating: -3 | reduce quality rating by 3.
upcode1 | increase rating: +1 | increase quality rating by 1.
upcode2 | increase rating: +2 | increase quality rating by 2.
no-concern | no serious concern | no serious concern.
serious-concern | serious concern | serious concern.
critical-concern | critical concern | critical concern.

present | present | possible reason for increasing quality rating was checked and found to bepresent.
absent | absent | possible reason for increasing quality rating was checked and found to be absent.

See the full registry of code systems defined as part of FHIR.

Explanation of the columns that may appear on this page:

Level | A few code lists that FHIR defines are hierarchical - each code is assigned a level. See Code System for further information.
Source | The source of the definition of the code (when the value set draws in codes defined elsewhere)
Code | The code (used as the code in the resource instance). If the code is in italics, this indicates that the code is not selectable ('Abstract')
Display | The display (used in the display element of a Coding). If there is no display, implementers should not simply display the code, but map the concept into their application
Definition | An explanation of the meaning of the concept
Comments | Additional notes about how to use the code

4.3.14.376 Code System http://terminology.hl7.org/CodeSystem/organization-type

URL: https://hl7.org/fhir/R4/codesystem-organization-type.html
Patient Administration Work Group | Maturity Level: 1 | Draft | Use Context: Any

This is a code system defined by the FHIR project.

Summary

Defining URL: | http://terminology.hl7.org/CodeSystem/organization-type
Version: | 4.0.1
Name: | OrganizationType
Title: | Organization type
Definition: | This example value set defines a set of codes that can be used to indicate a type of organization.
Committee: | Patient Administration Work Group
OID: | 2.16.840.1.113883.4.642.4.1128 (for OID based terminology systems)
Source Resource | XML / JSON

This Code system is used in the following value sets:

• ValueSet: Organization type (This example value set defines a set of codes that can be used to indicate a type of organization.)

• ValueSet: Organization type (This example value set defines a set of codes that can be used to indicate a type of organization.)

4.3.14.376.1 Content

4.3.14.376.2 Organization type

This example value set defines a set of codes that can be used to indicate a type of organization.

This code system http://terminology.hl7.org/CodeSystem/organization-type defines the following codes:

Code | Display | Definition
prov | Healthcare Provider | An organization that provides healthcare services.
dept | Hospital Department | A department or ward within a hospital (Generally is not applicable to top level organizations)
team | Organizational team | An organizational team is usually a grouping of practitioners that perform a specific function within an organization (which could be a top level organization, or a department).
govt | Government | A political body, often used when including organization records for government bodies such as a Federal Government, State or Local Government.
ins | Insurance Company | A company that provides insurance to its subscribers that may include healthcare related policies.
pay | Payer | A company, charity, or governmental organization, which processes claims and/or issues payments to providers on behalf of patients or groups of patients.
edu | Educational Institute | An educational institution that provides education or research facilities.
reli | Religious Institution | An organization that is identified as a part of a religious institution.
crs | Clinical Research Sponsor | An organization that is identified as a Pharmaceutical/Clinical Research Sponsor.
cg | Community Group | An un-incorporated community group.
bus | Non-Healthcare Business or Corporation | An organization that is a registered business or corporation but not identified by other types.
other | Other | Other type of organization not already specified.

See the full registry of code systems defined as part of FHIR.

Explanation of the columns that may appear on this page:

Level | A few code lists that FHIR defines are hierarchical - each code is assigned a level. See Code System for further information.
Source | The source of the definition of the code (when the value set draws in codes defined elsewhere)
Code | The code (used as the code in the resource instance). If the code is in italics, this indicates that the code is not selectable ('Abstract')
Display | The display (used in the display element of a Coding). If there is no display, implementers should not simply display the code, but map the concept into their application
Definition | An explanation of the meaning of the concept
Comments | Additional notes about how to use the code

4.3.14.377 Code System http://hl7.org/fhir/search-modifier-code

URL: https://hl7.org/fhir/R4/codesystem-search-modifier-code.html
FHIR Infrastructure Work Group | Maturity Level: 3 | Trial Use | Use Context: Any

This is a code system defined by the FHIR project.

Summary

Defining URL: | http://hl7.org/fhir/search-modifier-code
Version: | 4.0.1
Name: | SearchModifierCode
Title: | SearchModifierCode
Definition: | A supported modifier for a search parameter.
Committee: | FHIR Infrastructure Work Group
OID: | 2.16.840.1.113883.4.642.4.640 (for OID based terminology systems)
Source Resource | XML / JSON

This Code system is used in the following value sets:

• ValueSet: SearchModifierCode (A supported modifier for a search parameter.)

• ValueSet: SearchModifierCode (A supported modifier for a search parameter.)

4.3.14.377.1 Content

4.3.14.377.2 SearchModifierCode

A supported modifier for a search parameter.

This code system http://hl7.org/fhir/search-modifier-code defines the following codes:

Code | Display | Definition
missing | Missing | The search parameter returns resources that have a value or not.
exact | Exact | The search parameter returns resources that have a value that exactly matches the supplied parameter (the whole string, including casing and accents).
contains | Contains | The search parameter returns resources that include the supplied parameter value anywhere within the field being searched.
not | Not | The search parameter returns resources that do not contain a match.
text | Text | The search parameter is processed as a string that searches text associated with the code/value - either CodeableConcept.text, Coding.display, or Identifier.type.text.
in | In | The search parameter is a URI (relative or absolute) that identifies a value set, and the search parameter tests whether the coding is in the specified value set.
not-in | Not In | The search parameter is a URI (relative or absolute) that identifies a value set, and the search parameter tests whether the coding is not in the specified value set.
below | Below | The search parameter tests whether the value in a resource is subsumed by the specified value (is-a, or hierarchical relationships).
above | Above | The search parameter tests whether the value in a resource subsumes the specified value (is-a, or hierarchical relationships).
type | Type | The search parameter only applies to the Resource Type specified as a modifier (e.g. the modifier is not actually :type, but :Patient etc.).
identifier | Identifier | The search parameter applies to the identifier on the resource, not the reference.
ofType | Of Type | The search parameter has the format system|code|value, where the system and code refer to an Identifier.type.coding.system and .code, and match if any of the type codes match. All 3 parts must be present.

See the full registry of code systems defined as part of FHIR.

Explanation of the columns that may appear on this page:

Level | A few code lists that FHIR defines are hierarchical - each code is assigned a level. See Code System for further information.
Source | The source of the definition of the code (when the value set draws in codes defined elsewhere)
Code | The code (used as the code in the resource instance). If the code is in italics, this indicates that the code is not selectable ('Abstract')
Display | The display (used in the display element of a Coding). If there is no display, implementers should not simply display the code, but map the concept into their application
Definition | An explanation of the meaning of the concept
Comments | Additional notes about how to use the code

4.3.14.378 Code System http://hl7.org/fhir/contract-decision-mode

URL: https://hl7.org/fhir/R4/codesystem-contract-decision-mode.html
Financial Management Work Group | Maturity Level: 1 | Draft | Use Context: Any

This is a code system defined by the FHIR project.

Summary

Defining URL: | http://hl7.org/fhir/contract-decision-mode
Version: | 4.0.1

Name: | ContractResourceDecisionModeCodes
Title: | Contract Resource Decision Mode codes
Definition: | This value set contract specific codes for decision modes.
Committee: | Financial Management Work Group
OID: | 2.16.840.1.113883.4.642.4.1292 (for OID based terminology systems)
Copyright: | HL7 International.
Source Resource | XML / JSON

This Code system is used in the following value sets:

• ValueSet: Contract Resource Decision Mode codes (This value set contract specific codes for decision modes.)

• ValueSet: Contract Resource Decision Mode codes (This value set contract specific codes for decision modes.)

4.3.14.378.1 Content

Each definition includes usage notes explaining the precedence order in contract lifecycle - i.e., while only some stages are required, the order in which they may occur is deterministic; and a map to comparable FHIR and v.3 status codes. It follows guidance about use of status codes in FHIR at http://build.fhir.org/sc.html.

4.3.14.378.2 Contract Resource Decision Mode codes

This value set contract specific codes for decision modes.

Copyright Statement:

HL7 International.

This code system http://hl7.org/fhir/contract-decision-mode defines the following codes:

Code | Display | Definition
policy | Policy | To be completed

See the full registry of code systems defined as part of FHIR.

Explanation of the columns that may appear on this page:

Level | A few code lists that FHIR defines are hierarchical - each code is assigned a level. See Code System for further information.
Source | The source of the definition of the code (when the value set draws in codes defined elsewhere)
Code | The code (used as the code in the resource instance). If the code is in italics, this indicates that the code is not selectable ('Abstract')
Display | The display (used in the display element of a Coding). If there is no display, implementers should not simply display the code, but map the concept into their application
Definition | An explanation of the meaning of the concept
Comments | Additional notes about how to use the code

4.3.14.379 Code System http://terminology.hl7.org/CodeSystem/communication-topic

URL: https://hl7.org/fhir/R4/codesystem-communication-topic.html
Patient Care Work Group | Maturity Level: 1 | Draft | Use Context: Any

This is a code system defined by the FHIR project.

Summary

Defining URL: | http://terminology.hl7.org/CodeSystem/communication-topic
Version: | 4.0.1
Name: | CommunicationTopic
Title: | CommunicationTopic
Definition: | Codes describing the purpose or content of the communication.
Committee: | Patient Care Work Group
OID: | 2.16.840.1.113883.4.642.4.1078 (for OID based terminology systems)
Source Resource | XML / JSON

This Code system is used in the following value sets:

• ValueSet: CommunicationTopic (Codes describing the purpose or content of the communication.)

• ValueSet: CommunicationTopic (Codes describing the purpose or content of the communication.)

4.3.14.379.1 Content

4.3.14.379.2 CommunicationTopic

Codes describing the purpose or content of the communication.

This code system http://terminology.hl7.org/CodeSystem/communication-topic defines the following codes:

Code | Display | Definition
prescription-refill-request | Prescription Refill Request | The purpose or content of the communication is a prescription refill request.

progress-update | Progress Update | The purpose or content of the communication is a progress update.
report-labs | Report Labs | The purpose or content of the communication is to report labs.
appointment-reminder | Appointment Reminder | The purpose or content of the communication is an appointment reminder.
phone-consult | Phone Consult | The purpose or content of the communication is a phone consult.
summary-report | Summary Report | The purpose or content of the communication is a summary report.

See the full registry of code systems defined as part of FHIR.

Explanation of the columns that may appear on this page:

Level | A few code lists that FHIR defines are hierarchical - each code is assigned a level. See Code System for further information.
Source | The source of the definition of the code (when the value set draws in codes defined elsewhere)
Code | The code (used as the code in the resource instance). If the code is in italics, this indicates that the code is not selectable ('Abstract')
Display | The display (used in the display element of a Coding). If there is no display, implementers should not simply display the code, but map the concept into their application
Definition | An explanation of the meaning of the concept
Comments | Additional notes about how to use the code

4.3.14.380 Code System http://hl7.org/fhir/location-mode

URL: https://hl7.org/fhir/R4/codesystem-location-mode.html
Patient Administration Work Group | Maturity Level: 3 | Trial Use | Use Context: Any

This is a code system defined by the FHIR project.

Summary

Defining URL: | http://hl7.org/fhir/location-mode
Version: | 4.0.1
Name: | LocationMode
Title: | LocationMode
Definition: | Indicates whether a resource instance represents a specific location or a class of locations.
Committee: | Patient Administration Work Group
OID: | 2.16.840.1.113883.4.642.4.331 (for OID based terminology systems)
Source Resource | XML / JSON

This Code system is used in the following value sets:

• ValueSet: LocationMode (Indicates whether a resource instance represents a specific location or a class of locations.)

• ValueSet: LocationMode (Indicates whether a resource instance represents a specific location or a class of locations.)

4.3.14.380.1 Content

4.3.14.380.2 LocationMode

Indicates whether a resource instance represents a specific location or a class of locations.

This code system http://hl7.org/fhir/location-mode defines the following codes:

Code | Display | Definition
instance | Instance | The Location resource represents a specific instance of a location (e.g. Operating Theatre 1A).
kind | Kind | The Location represents a class of locations (e.g. Any Operating Theatre) although this class of locations could be constrained within a specific boundary (such as organization, or parent location, address etc.).

See the full registry of code systems defined as part of FHIR.

Explanation of the columns that may appear on this page:

Level | A few code lists that FHIR defines are hierarchical - each code is assigned a level. See Code System for further information.
Source | The source of the definition of the code (when the value set draws in codes defined elsewhere)
Code | The code (used as the code in the resource instance). If the code is in italics, this indicates that the code is not selectable ('Abstract')
Display | The display (used in the display element of a Coding). If there is no display, implementers should not simply display the code, but map the concept into their application
Definition | An explanation of the meaning of the concept
Comments | Additional notes about how to use the code

4.3.14.381 Code System urn:iso-astm:E1762-95:2013

URL: https://hl7.org/fhir/R4/codesystem-signature-type.html
FHIR Infrastructure Work Group | Maturity Level: 0 | Informative | Use Context: Any

This is a code system defined at http://www.astm.org/ .

Summary

Defining URL: | urn:iso-astm:E1762-95:2013
Version: | 4.0.1
Name: | SignatureTypeCodes

Title: | Signature Type Codes
Definition: | The Digital Signature Purposes, an indication of the reason an entity signs a document. This is included in the signed information and can be used when determining accountability for various actions concerning the document. Examples include: author, transcriptionist/recorder, and witness.
Committee: | FHIR Infrastructure Work Group
OID: | 2.16.840.1.113883.4.642.4.64 (for OID based terminology systems)
Copyright: | These codes are excerpted from ASTM Standard, E1762-95(2013) - Standard Guide for Electronic Authentication of Health Care Information, Copyright by ASTM International, 100 Barr Harbor Drive, West Conshohocken, PA 19428. Copies of this standard are available through the ASTM Web Site at www.astm.org.
Source Resource | XML / JSON

This Code system is used in the following value sets:

• ValueSet: Signature Type Codes (The Digital Signature Purposes, an indication of the reason an entity signs a document. This is included in the signed information and can be used when determining accountability for various actions concerning the document. Examples include: author, transcriptionist/recorder, and witness.)

• ValueSet: Signature Type Codes (The Digital Signature Purposes, an indication of the reason an entity signs a document. This is included in the signed information and can be used when determining accountability for various actions concerning the document. Examples include: author, transcriptionist/recorder, and witness.)

4.3.14.381.1 Content

4.3.14.381.2 Signature Type Codes

The Digital Signature Purposes, an indication of the reason an entity signs a document. This is included in the signed information and can be used when determining accountability for various actions concerning the document. Examples include: author, transcriptionist/recorder, and witness.

Copyright Statement:

These codes are excerpted from ASTM Standard, E1762-95(2013) - Standard Guide for Electronic Authentication of Health Care Information, Copyright by ASTM International, 100 Barr Harbor Drive, West Conshohocken, PA 19428. Copies of this standard are available through the ASTM Web Site at www.astm.org.

This code system urn:iso-astm:E1762-95:2013 defines the following codes:

Code | Display | Definition
1.2.840.10065.1.12.1.1 | Author's Signature | the signature of the primary or sole author of a health information document. There can be only one primary author of a health information document.
1.2.840.10065.1.12.1.2 | Coauthor's Signature | the signature of a health information document coauthor. There can be multiple coauthors of a health information document.
1.2.840.10065.1.12.1.3 | Co-participant's Signature | the signature of an individual who is a participant in the health information document but is not an author or coauthor. (Example a surgeon who is required by institutional, regulatory, or legal rules to sign an operative report, but who was not involved in the authorship of that report.)
1.2.840.10065.1.12.1.4 | Transcriptionist/Recorder Signature | the signature of an individual who has transcribed a dictated document or recorded written text into a digital machine readable format.
1.2.840.10065.1.12.1.5 | Verification Signature | a signature verifying the information contained in a document. (Example a physician is required to countersign a verbal order that has previously been recorded in the medical record by a registered nurse who has carried out the verbal order.)
1.2.840.10065.1.12.1.6 | Validation Signature | a signature validating a health information document for inclusion in the patient record. (Example a medical student or resident is credentialed to perform history or physical examinations and to write progress notes. The attending physician signs the history and physical examination to validate the entry for inclusion in the patient's medical record.)
1.2.840.10065.1.12.1.7 | Consent Signature | the signature of an individual consenting to what is described in a health information document.
1.2.840.10065.1.12.1.8 | Signature Witness Signature | the signature of a witness to any other signature.
1.2.840.10065.1.12.1.9 | Event Witness Signature | the signature of a witness to an event. (Example the witness has observed a procedure and is attesting to this fact.)
1.2.840.10065.1.12.1.10 | Identity Witness Signature | the signature of an individual who has witnessed another individual who is known to them signing a document. (Example the identity witness is a notary public.)
1.2.840.10065.1.12.1.11 | Consent Witness Signature | the signature of an individual who has witnessed the health care provider counselling a patient.
1.2.840.10065.1.12.1.12 | Interpreter Signature | the signature of an individual who has translated health care information during an event or the obtaining of consent to a treatment.
1.2.840.10065.1.12.1.13 | Review Signature | the signature of a person, device, or algorithm that has reviewed or filtered data for inclusion into the patient record. (Examples: (1) a medical records clerk who scans a document for inclusion in the medical record, enters header information, or catalogues and classifies the data, or a combination thereof; (2) a gateway that receives data from another computer system and interprets that data or changes its format, or both, before entering it into the patient record.)
1.2.840.10065.1.12.1.14 | Source Signature | the signature of an automated data source. (Examples: (1) the signature for an image that is generated by a device for inclusion in the patient record; (2) the signature for an ECG derived by an ECG system for inclusion in the patient record; (3) the data from a biomedical monitoring device or system that is for inclusion in the patient record.)
1.2.840.10065.1.12.1.15 | Addendum Signature | the signature on a new amended document of an individual who has corrected, edited, or amended an original health information document. An addendum signature can either be a signature type or a signature sub-type (see 8.1). Any document with an addendum signature shall have a companion document that is the original document with its original, unaltered content, and original signatures. The original document shall be referenced via an attribute in the new document, which contains, for example, the digest of the old document. Whether the original, unaltered, document is always displayed with the addended document is a local matter, but the original, unaltered, document must remain as part of the

patient record and be retrievable on demand.
1.2.840.10065.1.12.1.16 | Modification Signature | the signature on an original document of an individual who has generated a new amended document. This (original) document shall reference the new document via an additional signature purpose. This is the inverse of an addendum signature and provides a pointer from the original to the amended document.
1.2.840.10065.1.12.1.17 | Administrative (Error/Edit) Signature | the signature of an individual who is certifying that the document is invalidated by an error(s), or is placed in the wrong chart. An administrative (error/edit) signature must include an addendum to the document and therefore shall have an addendum signature sub-type (see 8.1). This signature is reserved for the highest health information system administrative classification, since it is a statement that the entire document is invalidated by the error and that the document should no longer be used for patient care, although for legal reasons the document must remain part of the permanent patient record.
1.2.840.10065.1.12.1.18 | Timestamp Signature | the signature by an entity or device trusted to provide accurate timestamps. This timestamp might be provided, for example, in the signature time attribute.

See the full registry of code systems defined as part of FHIR.

Explanation of the columns that may appear on this page:

Level | A few code lists that FHIR defines are hierarchical - each code is assigned a level. See Code System for further information.
Source | The source of the definition of the code (when the value set draws in codes defined elsewhere)
Code | The code (used as the code in the resource instance). If the code is in italics, this indicates that the code is not selectable ('Abstract')
Display | The display (used in the display element of a Coding). If there is no display, implementers should not simply display the code, but map the concept into their application
Definition | An explanation of the meaning of the concept
Comments | Additional notes about how to use the code

4.3.14.382 Code System http://terminology.hl7.org/CodeSystem/list-empty-reason

URL: https://hl7.org/fhir/R4/codesystem-list-empty-reason.html
Structured Documents Work Group | Maturity Level: 0 | Informative | Use Context: Any

This is a code system defined by the FHIR project.

Summary

Defining URL: | http://terminology.hl7.org/CodeSystem/list-empty-reason
Version: | 4.0.1
Name: | ListEmptyReasons
Title: | List Empty Reasons
Definition: | General reasons for a list to be empty. Reasons are either related to a summary list (i.e. problem or medication list) or to a workflow related list (i.e. consultation list).
Committee: | Structured Documents Work Group
OID: | 2.16.840.1.113883.4.642.4.1106 (for OID based terminology systems)
Source Resource | XML / JSON

This Code system is used in the following value sets:

• ValueSet: List Empty Reasons (General reasons for a list to be empty. Reasons are either related to a summary list (i.e. problem or medication list) or to a workflow related list (i.e. consultation list).)

• ValueSet: List Empty Reasons (General reasons for a list to be empty. Reasons are either related to a summary list (i.e. problem or medication list) or to a workflow related list (i.e. consultation list).)

4.3.14.382.1 Content

4.3.14.382.2 List Empty Reasons

General reasons for a list to be empty. Reasons are either related to a summary list (i.e. problem or medication list) or to a workflow related list (i.e. consultation list).

This code system http://terminology.hl7.org/CodeSystem/list-empty-reason defines the following codes:

Code | Display | Definition
nilknown | Nil Known | Clinical judgment that there are no known items for this list after reasonable investigation. Note that this a positive statement by a clinical user, and not a default position asserted by a computer system in the lack of other information. Example uses: * For allergies: the patient or patient's agent/guardian has asserted that he/she is not aware of any allergies (NKA - nil known allergies) * For medications: the patient or patient's agent/guardian has asserted that the patient is known to be taking no medications * For diagnoses, problems and procedures: the patient or patient's agent/guardian has asserted that there is no known event to record.
notasked | Not Asked | The investigation to find out whether there are items for this list has not occurred.
withheld | Information Withheld | The content of the list was not provided due to privacy or confidentiality concerns. Note that it should not be assumed that this means that the particular information in question was withheld due to its contents - it can also be a policy decision.
unavailable | Unavailable | Information to populate this list cannot be obtained; e.g. unconscious patient.
notstarted | Not Started | The work to populate this list has not yet begun.
closed | Closed | This list has now closed or has ceased to be relevant or useful.

See the full registry of code systems defined as part of FHIR.

Explanation of the columns that may appear on this page:

Level | A few code lists that FHIR defines are hierarchical - each code is assigned a level. See Code System for further information.
Source | The source of the definition of the code (when the value set draws in codes defined elsewhere)
Code | The code (used as the code in the resource instance). If the code is in italics, this indicates that the code is not selectable ('Abstract')
Display | The display (used in the display element of a Coding). If there is no display, implementers should not simply display the code, but map the concept into their application
Definition | An explanation of the meaning of the concept
Comments | Additional notes about how to use the code

4.3.14.383 Code System http://terminology.hl7.org/CodeSystem/adverse-event-seriousness

URL: https://hl7.org/fhir/R4/codesystem-adverse-event-seriousness.html
Patient Care Work Group | Maturity Level: 1 | Draft | Use Context: Any

This is a code system defined by the FHIR project.

Summary

Defining URL: | http://terminology.hl7.org/CodeSystem/adverse-event-seriousness
Version: | 4.0.1
Name: | AdverseEventSeriousness
Title: | AdverseEventSeriousness
Definition: | Overall seriousness of this event for the patient.
Committee: | Patient Care Work Group
OID: | 2.16.840.1.113883.4.642.4.1253 (for OID based terminology systems)
Source Resource | XML / JSON

This Code system is used in the following value sets:

• ValueSet: AdverseEventSeriousness (Overall seriousness of this event for the patient.)
• ValueSet: AdverseEventSeriousness (Overall seriousness of this event for the patient.)

4.3.14.383.1 Content

4.3.14.383.2 AdverseEventSeriousness

Overall seriousness of this event for the patient.

This code system http://terminology.hl7.org/CodeSystem/adverse-event-seriousness defines the following codes:

Lvl | Code | Display | Definition
1 | Non-serious | Non-serious | Non-serious.
1 | Serious | Serious | Serious.
2 | SeriousResultsInDeath | Results in death | Results in death.
2 | SeriousIsLifeThreatening | Is Life-threatening | Is Life-threatening.
2 | SeriousResultsInHospitalization | Requires or prolongs inpatient hospitalization | Requires inpatient hospitalization or causes prolongation of existing hospitalization.
2 | SeriousResultsInDisability | Results in persistent or significant disability/incapacity | Results in persistent or significant disability/incapacity.
2 | SeriousIsBirthDefect | Is a congenital anomaly/birth defect | Is a congenital anomaly/birth defect.
2 | SeriousRequiresPreventImpairment | Requires intervention to prevent permanent impairment | Requires intervention to prevent permanent impairment or damage (i.e., an important medical event that requires medical judgement).

See the full registry of code systems defined as part of FHIR.

Explanation of the columns that may appear on this page:

Level | A few code lists that FHIR defines are hierarchical - each code is assigned a level. See Code System for further information.
Source | The source of the definition of the code (when the value set draws in codes defined elsewhere)
Code | The code (used as the code in the resource instance). If the code is in italics, this indicates that the code is not selectable ('Abstract')
Display | The display (used in the display element of a Coding). If there is no display, implementers should not simply display the code, but map the concept into their application
Definition | An explanation of the meaning of the concept
Comments | Additional notes about how to use the code

4.3.14.384 Code System http://terminology.hl7.org/CodeSystem/contractsignertypecodes

URL: https://hl7.org/fhir/R4/codesystem-contract-signer-type.html
Financial Management Work Group | Maturity Level: 0 | Informative | Use Context: Any

This is a code system defined by the FHIR project.

Summary

Defining URL: | http://terminology.hl7.org/CodeSystem/contractsignertypecodes

Version: | 4.0.1
Name: | ContractSignerTypeCodes
Title: | Contract Signer Type Codes
Definition: | This value set includes sample Contract Signer Type codes.
Committee: | Financial Management Work Group
OID: | 2.16.840.1.113883.4.642.4.1201 (for OID based terminology systems)
Copyright: | This is an example set based on ASTM Standard, E1762-95 (2013) HL7 RoleClass OID 2.16.840.1.113883.5.110, HL7 Role Code 2.16.840.1.113883.5.111, HL7 ParticipationType OID: 2.16.840.1.113883.5.90, HL7 ParticipationFunction codes at OID: 2.16.840.1.113883.5.88, and HL7 Security and Privacy Domain Analysis Model roles classes.
Source Resource | XML / JSON

This Code system is used in the following value sets:

• ValueSet: Contract Signer Type Codes (This value set includes sample Contract Signer Type codes.)

• ValueSet: ParticipationRoleType (This FHIR value set is comprised of Actor participation Type codes, which can be used to value FHIR agents, actors, and other role elements. The FHIR Actor participation type value set is based on DICOM Audit Message, C402; ASTM Standard, E1762-95 [2013]; selected codes and derived actor roles from HL7 RoleClass OID 2.16.840.1.113883.5.110; HL7 Role Code 2.16.840.1.113883.5.111, including AgentRoleType; HL7 ParticipationType OID: 2.16.840.1.113883.5.90; and HL7 ParticipationFunction codes OID: 2.16.840.1.113883.5.88. This value set includes, by reference, role codes from external code systems: NUCC Health Care Provider Taxonomy OID: 2.16.840.1.113883.6.101; North American Industry Classification System [NAICS]OID: 2.16.840.1.113883.6.85; IndustryClassificationSystem 2.16.840.1.113883.1.11.16039; and US Census Occupation Code OID: 2.16.840.1.113883.6.243 for relevant recipient or custodian codes not included in this value set. If no source is indicated in the definition comments, then these are example FHIR codes.)

• ValueSet: ParticipationRoleType (This FHIR value set is comprised of Actor participation Type codes, which can be used to value FHIR agents, actors, and other role elements. The FHIR Actor participation type value set is based on DICOM Audit Message, C402; ASTM Standard, E1762-95 [2013]; selected codes and derived actor roles from HL7 RoleClass OID 2.16.840.1.113883.5.110; HL7 Role Code 2.16.840.1.113883.5.111, including AgentRoleType; HL7 ParticipationType OID: 2.16.840.1.113883.5.90; and HL7 ParticipationFunction codes OID: 2.16.840.1.113883.5.88. This value set includes, by reference, role codes from external code systems: NUCC Health Care Provider Taxonomy OID: 2.16.840.1.113883.6.101; North American Industry Classification System [NAICS]OID: 2.16.840.1.113883.6.85; IndustryClassificationSystem 2.16.840.1.113883.1.11.16039; and US Census Occupation Code OID: 2.16.840.1.113883.6.243 for relevant recipient or custodian codes not included in this value set. If no source is indicated in the definition comments, then these are example FHIR codes.)

• ValueSet: SecurityRoleType (This example FHIR value set is comprised of example Actor Type codes, which can be used to value FHIR agents, actors, and other role elements such as those specified in financial transactions. The FHIR Actor value set is based on DICOM Audit Message, C402; ASTM Standard, E1762-95 [2013]; selected codes and derived actor roles from HL7 RoleClass OID 2.16.840.1.113883.5.110; HL7 Role Code 2.16.840.1.113883.5.111, including AgentRoleType; HL7 ParticipationType OID: 2.16.840.1.113883.5.90; and HL7 ParticipationFunction codes OID: 2.16.840.1.113883.5.88. This value set includes, by reference, role codes from external code systems: NUCC Health Care Provider Taxonomy OID: 2.16.840.1.113883.6.101; North American Industry Classification System [NAICS]OID: 2.16.840.1.113883.6.85; IndustryClassificationSystem 2.16.840.1.113883.1.11.16039; and US Census Occupation Code OID: 2.16.840.1.113883.6.243 for relevant recipient or custodian codes not included in this value set. If no source is indicated in the definition comments, then these are example FHIR codes. It can be extended with appropriate roles described by SNOMED as well as those described in the HL7 Role Based Access Control Catalog and the HL7 Healthcare (Security and Privacy) Access Control Catalog. In Role-Based Access Control (RBAC), permissions are operations on an object that a user wishes to access. Permissions are grouped into roles. A role characterizes the functions a user is allowed to perform. Roles are assigned to users. If the user's role has the appropriate permissions to access an object, then that user is granted access to the object. FHIR readily enables RBAC, as FHIR Resources are object types and the CRUDE events (the FHIR equivalent to permissions in the RBAC scheme) are operations on those objects. In Attribute-Based Access Control (ABAC), a user requests to perform operations on objects. That user's access request is granted or denied based on a set of access control policies that are specified in terms of attributes and conditions. FHIR readily enables ABAC, as instances of a Resource in FHIR (again, Resources are object types) can have attributes associated with them. These attributes include security tags, environment conditions, and a host of user and object characteristics, which are the same attributes as those used in ABAC. Attributes help define the access control policies that determine the operations a user may perform on a Resource (in FHIR) or object (in ABAC). For example, a tag (or attribute) may specify that the identified Resource (object) is not to be further disclosed without explicit consent from the patient.)

• ValueSet: SecurityRoleType (This example FHIR value set is comprised of example Actor Type codes, which can be used to value FHIR agents, actors, and other role elements such as those specified in financial transactions. The FHIR Actor value set is based on DICOM Audit Message, C402; ASTM Standard, E1762-95 [2013]; selected codes and derived actor roles from HL7 RoleClass OID 2.16.840.1.113883.5.110; HL7 Role Code 2.16.840.1.113883.5.111, including AgentRoleType; HL7 ParticipationType OID:

2.16.840.1.113883.5.90; and HL7 ParticipationFunction codes OID: 2.16.840.1.113883.5.88. This value set includes, by reference, role codes from external code systems: NUCC Health Care Provider Taxonomy OID: 2.16.840.1.113883.6.101; North American Industry Classification System [NAICS]OID: 2.16.840.1.113883.6.85; IndustryClassificationSystem 2.16.840.1.113883.1.11.16039; and US Census Occupation Code OID: 2.16.840.1.113883.6.243 for relevant recipient or custodian codes not included in this value set. If no source is indicated in the definition comments, then these are example FHIR codes. It can be extended with appropriate roles described by SNOMED as well as those described in the HL7 Role Based Access Control Catalog and the HL7 Healthcare (Security and Privacy) Access Control Catalog. In Role-Based Access Control (RBAC), permissions are operations on an object that a user wishes to access. Permissions are grouped into roles. A role characterizes the functions a user is allowed to perform. Roles are assigned to users. If the user's role has the appropriate permissions to access an object, then that user is granted access to the object. FHIR readily enables RBAC, as FHIR Resources are object types and the CRUDE events (the FHIR equivalent to permissions in the RBAC scheme) are operations on those objects. In Attribute-Based Access Control (ABAC), a user requests to perform operations on objects. That user's access request is granted or denied based on a set of access control policies that are specified in terms of attributes and conditions. FHIR readily enables ABAC, as instances of a Resource in FHIR (again, Resources are object types) can have attributes associated with them. These attributes include security tags, environment conditions, and a host of user and object characteristics, which are the same attributes as those used in ABAC. Attributes help define the access control policies that determine the operations a user may perform on a Resource (in FHIR) or object (in ABAC). For example, a tag (or attribute) may specify that the identified Resource (object) is not to be further disclosed without explicit consent from the patient.)

• ValueSet: Contract Signer Type Codes (This value set includes sample Contract Signer Type codes.)

4.3.14.384.1 Content

4.3.14.384.2 Contract Signer Type Codes

This value set includes sample Contract Signer Type codes.

Copyright Statement:

This is an example set based on ASTM Standard, E1762-95 (2013) HL7 RoleClass OID 2.16.840.1.113883.5.110, HL7 Role Code 2.16.840.1.113883.5.111, HL7 ParticipationType OID: 2.16.840.1.113883.5.90, HL7 ParticipationFunction codes at OID: 2.16.840.1.113883.5.88, and HL7 Security and Privacy Domain Analysis Model roles classes.

This code system http://terminology.hl7.org/CodeSystem/contractsignertypecodes defines the following codes:

Code | Display | Definition

AMENDER | Amender | A person who has corrected, edited, or amended pre-existing information.

AUTHN | Authenticator | A person in the role of verifier who attests to the accuracy of an act, but who does not have privileges to legally authenticate information content. An example would be a resident physician who sees a patient and dictates a note, then later signs it. The resident's signature constitutes an authentication.

AUT | Author | An entity that authored specific content. There can be multiple authors of content, which may take such forms as a contract, a healthcare record entry or document, a policy, or a consent directive.

AFFL | Affiliate | An entity that has a business or professional relationship with another entity in accordance with an agreement.

AGNT | Agent | An entity that acts or is authorized to act on behalf of another entity in accordance with an agreement.

ASSIGNED | Assigned Entity | An agent role in which the agent is an Entity acting in the employ of an organization. The focus is on functional role on behalf of the organization, unlike the Employee role where the focus is on the 'Human Resources' relationship between the employee and the organization.

CIT | Citizen | The member of a jurisdiction afforded certain rights and encumbered with certain obligation in accordance with jurisdictional policy.

CLAIMANT | Claimant | A party that makes a claim for coverage under a policy.

COAUTH | Co-Author | The entity that co-authored content. There can be multiple co-authors of content, which may take such forms as a contract, a healthcare record entry or document, a policy, or a consent directive.

CONSENTER | Consenter | A patient or patient representative who is the grantee in a healthcare related agreement such as a consent for healthcare services, advanced directive, or a privacy consent directive in accordance with jurisdictional, organizational, or patient policy.

CONSWIT | Consent Witness | A person who has witnessed and attests to observing a patient being counseled about a healthcare related agreement such as a consent for healthcare services, advanced directive, or a privacy consent directive.

CONT | Contact | A person or an organization that provides or receives information regarding another entity. Examples; patient NOK and emergency contacts; guarantor contact; employer contact.

COPART | Co-Participant | A person who participates in the generation of and attest to veracity of content but is not an author or co-author. For example, a surgeon who is required by institutional, regulatory, or legal rules to sign an operative report, but who was not involved in the authorship of that report.

COVPTY | Covered Party | An entity, which is the insured, that receives benefits such as healthcare services, reimbursement for out-of-pocket expenses, or compensation for losses through coverage under the terms of an insurance policy. The underwriter of that policy is the scoping entity. The covered party receives coverage because of some contractual or other relationship with the holder of that policy. Note that a particular policy may cover several individuals one of whom may be, but need not be, the policy holder. Thus the notion of covered party is a role that is distinct from that of the policy holder.

DELEGATEE | Delegatee | A party to whom some right or authority is delegated by a delegator.

delegator | Delegator | A party that delegates a right or authority to another party.

DEPEND | Dependent | A person covered under an insurance policy or program based on an association with a subscriber, which is recognized by the policy holder. The dependent has an association with the subscriber such as a financial dependency or personal relationship such as that of a spouse, or a natural or adopted child. The policy holder may be required by law to recognize certain associations or may have discretion about the associations. For example, a policy holder may dictate the criteria for the dependent status of adult children who are students, such as requiring full time enrollment, or may recognize domestic partners as dependents. Under certain circumstances, the dependent may be under the indirect authority of a responsible party acting as a surrogate for the subscriber, for example, if the subscriber is differently-abled or deceased, a guardian ad lidem or estate executor may be appointed to assume the subscriber's legal standing in the relationship with the dependent.

DPOWATT | Durable Power of Attorney | A person who has been granted the authority to represent or act on another's behalf generally in a manner which is a legally binding upon the person giving such authority as if he or she personally were to do the acts. Unlike ordinary powers of attorney, durable powers can survive for long periods of time, and again, unlike standard powers of attorney, durable powers can continue after incompetency.

EMGCON | Emergency Contact | An entity to be contacted in the event of an emergency

EVTWIT | Event Witness | A person who attests to observing an occurrence. For example, the witness has observed a procedure and is attesting to this fact.

EXCEST | Executor of Estate | A person who has been granted the authority to act as an estate executor for a deceased person who was the responsible party.

GRANTEE | Grantee | A person who grants to another person the authority to represent or act on that person's behalf. Examples include (1) exercising specific rights belonging to the grantee; (2) performing specific duties on behalf of a grantee; and (3) making specific decisions concerning a grantee.

GRANTOR | Grantor | A person who has been granted the authority to represent or act on another's behalf. Examples include (1) exercising specific rights belonging to the grantee; (2) performing specific duties on behalf of a grantee; and (3) making specific decisions concerning a grantee.

GUAR | Guarantor | A person or organization contractually recognized by the issuer as an entity that has assumed fiscal responsibility (e.g., by making or giving a promise, assurance, or pledge) for another entity's financial obligations by guaranteeing to pay for amounts owed to a particular account. In a healthcare context, the account may be a patient's billing account for services rendered by a provider or a health plan premium account.

GUARD | Guardian | A person or organization legally empowered with responsibility for the care of a ward.

GUADLTM | Guardian ad lidem | A person appointed by the court to look out for the best interests of a minor child during the course of legal proceedings.

INF | Informant | An entity that is the source of reported information (e.g., a next of kin who answers questions about the patient's history). For history questions, the patient is logically an informant, yet the informant of history questions is implicitly the subject.

INTPRT | Interpreter | A person who converts spoken or written language into the language of key participants in an event such as when a provider is obtaining a patient's consent to treatment or permission to disclose information.

INSBJ | Investigation Subject | An entity that is the subject of an investigation. This role is scoped by the party responsible for the investigation.

HPOWATT | Healthcare Power of Attorney | A person who has been granted the authority to represent or act on another's behalf for healthcare related matters in a manner which is a legally binding upon the person giving such authority as if he or she personally were to do the acts. Examples include (1) exercising specific healthcare legal rights belonging to the grantee such as signing a consent directive; (2) performing specific healthcare related legal duties on behalf of a grantee such as claims payment; and (3) making specific healthcare legal decisions concerning a grantee such as consenting to healthcare services.

HPROV | Healthcare Provider | An entity that is authorized to provide health care services by an authorizing organization or jurisdiction.

LEGAUTHN | Legal Authenticator | A person in the role of verifier who attests to the accuracy of information content, and who has privileges to certify the legal authenticity of that content with a signature that constitutes a legal authentication. For example, a licensed physician who signs a consult authored by a resident physician who authenticated it.

NMDINS | Named Insured | A party to an insurance policy under which the insurer agrees to indemnify for losses, provides benefits for, or renders services. A named insured may be either a person, non-person living subject, or an organization, or a group of persons, non-person living subject that is the named insured under a comprehensive automobile, disability, or property and casualty policy. The named insured and might or might not be the policy holder.

NOK | Next of Kin | A person, who is a type of contact, designated to receive notifications on behalf of another person who is a relative.

NOTARY | Notary | The party credentialed to legally attest to the contract binding by verifying the identity and capacity of the grantor and grantee, and witnessing their signing of the contract or agreement such as a real estate transaction, pre-nuptial agreement, or a will.

PAT | Patient | A person, animal, or other living subject that is the actual or potential recipient of health care services.

POWATT | Power of Attorney | A person who has been granted the authority to represent or act on another's behalf generally in a manner which is a legally binding upon the person giving such authority as if he or she personally were to do the acts. Examples include (1) exercising specific legal rights belonging to the grantee such as signing a contract; (2) performing specific legal duties on behalf of a grantee such as making loan payments; and (3) making specific legal decisions concerning a grantee such as financial investment decisions.

PRIMAUTH | Primary Author | An entity that is the primary or sole author of information content. In the healthcare context, there can be only one primary author of health information content in a record entry or document.

PRIRECIP | Primary Responsible Party | An entity that may, should receive, or has received information or an object to which it was primarily addressed.

RECIP | Recipient | An entity that may, should receive, or has received information or an object, which might not have been primarily addressed to it. For example, the staff of a provider, a clearinghouse, or other intermediary.

RESPRSN | Responsible Party | An entity that has legal responsibility for another party.

REVIEWER | Reviewer | A person, device, or algorithm that has used approved criteria for filtered data for inclusion into the patient record. Examples: (1) a medical records clerk who scans a document for inclusion in the medical record, enters header information, or catalogues and classifies the data, or a combination thereof; (2) a gateway that receives data from another computer system and interprets that data or changes its format, or both, before entering it into the patient record.

TRANS | Transcriber | An entity entering the data into the originating system. This includes the transcriptionist for dictated text transcribed into electronic form.

SOURCE | Source | An automated data source that generates a signature along with content. Examples: (1) the signature for an image that is generated by a device for inclusion in the patient record; (2) the signature for an ECG derived by an ECG system for inclusion in the patient record; (3) the data from a biomedical monitoring device or system that is for inclusion in the patient

record.
SPOWATT | Special Power of Attorney | A person who has been granted the authority to represent or act on another's behalf for a limited set of specific matters in a manner which is a legally binding upon the person giving such authority as if he or she personally were to do the acts. Examples include (1) exercising specific legal rights belonging to the grantee such as drafting a will; (2) performing specific legal duties on behalf of a grantee such as making a reversible mortgage to pay for end of life expenses; and (3) making specific legal decisions concerning a grantee such as managing a trust.
VALID | Validator | A person who validates a health information document for inclusion in the patient record. For example, a medical student or resident is credentialed to perform history or physical examinations and to write progress notes. The attending physician signs the history and physical examination to validate the entry for inclusion in the patient's medical record.
VERF | Verifier | A person who asserts the correctness and appropriateness of an act or the recording of the act, and is accountable for the assertion that the act or the recording of the act complies with jurisdictional or organizational policy. For example, a physician is required to countersign a verbal order that has previously been recorded in the medical record by a registered nurse who has carried out the verbal order.
WIT | Witness | A person witnessing the signature of another party. A witness is not knowledgeable about the content being signed, much less approves of anything stated in the content. For example, an advanced directive witness or a witness that a party to a contract signed that certain demographic or financial information is truthful.

See the full registry of code systems defined as part of FHIR.

Explanation of the columns that may appear on this page:

Level | A few code lists that FHIR defines are hierarchical - each code is assigned a level. See Code System for further information.
Source | The source of the definition of the code (when the value set draws in codes defined elsewhere)
Code | The code (used as the code in the resource instance). If the code is in italics, this indicates that the code is not selectable ('Abstract')
Display | The display (used in the display element of a Coding). If there is no display, implementers should not simply display the code, but map the concept into their application
Definition | An explanation of the meaning of the concept
Comments | Additional notes about how to use the code

4.3.14.385 Code System http://hl7.org/fhir/extension-context-type

URL: https://hl7.org/fhir/R4/codesystem-extension-context-type.html
FHIR Infrastructure Work Group | Maturity Level: N | Normative (from v4.0.0) | Use Context: Any

| This page has been approved as part of an ANSI standard. See the Conformance Package for further details.

This is a code system defined by the FHIR project.

Summary

Defining URL: | http://hl7.org/fhir/extension-context-type
Version: | 4.0.1
Name: | ExtensionContextType
Title: | ExtensionContextType
Definition: | How an extension context is interpreted.
Committee: | FHIR Infrastructure Work Group
OID: | 2.16.840.1.113883.4.642.4.1013 (for OID based terminology systems)
Source Resource | XML / JSON

This Code system is used in the following value sets:

• ValueSet: ExtensionContextType (How an extension context is interpreted.)

• ValueSet: ExtensionContextType (How an extension context is interpreted.)

4.3.14.385.1 Content

4.3.14.385.2 ExtensionContextType

How an extension context is interpreted.

This code system http://hl7.org/fhir/extension-context-type defines the following codes:

Code | Display | Definition
fhirpath | FHIRPath | The context is all elements that match the FHIRPath query found in the expression.
element | Element ID | The context is any element that has an ElementDefinition.id that matches that found in the expression. This includes ElementDefinition Ids that have slicing identifiers. The full path for the element is [url]#[elementid]. If there is no #, the Element id is one defined in the base specification.
extension | Extension URL | The context is a particular extension from a particular StructureDefinition, and the expression is just a uri that identifies the extension.

See the full registry of code systems defined as part of FHIR.

Explanation of the columns that may appear on this page:

Level | A few code lists that FHIR defines are hierarchical - each code is assigned a level. See Code System for further information.
Source | The source of the definition of the code (when the value set draws in codes defined elsewhere)
Code | The code (used as the code in the resource instance). If the code is in italics, this indicates that the code is not selectable ('Abstract')
Display | The display (used in the display element of a Coding). If there is no display, implementers should not simply display the code, but map the concept into their application

Definition | An explanation of the meaning of the concept
Comments | Additional notes about how to use the code

4.3.14.386 Code System http://hl7.org/fhir/episode-of-care-status

URL: https://hl7.org/fhir/R4/codesystem-episode-of-care-status.html
Patient Administration Work Group | Maturity Level: 2 | Trial Use | Use Context: Any

This is a code system defined by the FHIR project.

Summary

Defining URL: | http://hl7.org/fhir/episode-of-care-status
Version: | 4.0.1
Name: | EpisodeOfCareStatus
Title: | EpisodeOfCareStatus
Definition: | The status of the episode of care.
Committee: | Patient Administration Work Group
OID: | 2.16.840.1.113883.4.642.4.665 (for OID based terminology systems)
Source Resource | XML / JSON

This Code system is used in the following value sets:

• ValueSet: EpisodeOfCareStatus (The status of the episode of care.)

• ValueSet: EpisodeOfCareStatus (The status of the episode of care.)

4.3.14.386.1 Content

4.3.14.386.2 EpisodeOfCareStatus

The status of the episode of care.

This code system http://hl7.org/fhir/episode-of-care-status defines the following codes:

Code | Display | Definition
planned | Planned | This episode of care is planned to start at the date specified in the period.start. During this status, an organization may perform assessments to determine if the patient is eligible to receive services, or be organizing to make resources available to provide care services.
waitlist | Waitlist | This episode has been placed on a waitlist, pending the episode being made active (or cancelled).
active | Active | This episode of care is current.
onhold | On Hold | This episode of care is on hold; the organization has limited responsibility for the patient (such as while on respite).
finished | Finished | This episode of care is finished and the organization is not expecting to be providing further care to the patient. Can also be known as "closed", "completed" or other similar terms.
cancelled | Cancelled | The episode of care was cancelled, or withdrawn from service, often selected during the planned stage as the patient may have gone elsewhere, or the circumstances have changed and the organization is unable to provide the care. It indicates that services terminated outside the planned/expected workflow.
entered-in-error | Entered in Error | This instance should not have been part of this patient's medical record.

See the full registry of code systems defined as part of FHIR.

Explanation of the columns that may appear on this page:

Level | A few code lists that FHIR defines are hierarchical - each code is assigned a level. See Code System for further information.
Source | The source of the definition of the code (when the value set draws in codes defined elsewhere)
Code | The code (used as the code in the resource instance). If the code is in italics, this indicates that the code is not selectable ('Abstract')
Display | The display (used in the display element of a Coding). If there is no display, implementers should not simply display the code, but map the concept into their application
Definition | An explanation of the meaning of the concept
Comments | Additional notes about how to use the code

4.3.14.387 Code System http://terminology.hl7.org/CodeSystem/medicationknowledge-characteristic

URL: https://hl7.org/fhir/R4/codesystem-medicationknowledge-characteristic.html
Pharmacy Work Group | Maturity Level: 1 | Draft | Use Context: Any

This is a code system defined by the FHIR project.

Summary

Defining URL: | http://terminology.hl7.org/CodeSystem/medicationknowledge-characteristic
Version: | 4.0.1
Name: | medicationKnowledge Characteristic Codes
Title: | Medication knowledge characteristic codes
Definition: | MedicationKnowledge Characteristic Codes
Committee: | Pharmacy Work Group

OID: | 2.16.840.1.113883.4.642.4.1338 (for OID based terminology systems)
Source Resource | XML / JSON

This Code system is used in the following value sets:

• ValueSet: Medication knowledge characteristic codes (MedicationKnowledge Characteristic Codes)

• ValueSet: Medication knowledge characteristic codes (MedicationKnowledge Characteristic Codes)

4.3.14.387.1 Content

4.3.14.387.2 Medication knowledge characteristic codes

MedicationKnowledge Characteristic Codes

This code system http://terminology.hl7.org/CodeSystem/medicationknowledge-characteristic defines the following codes:

Code	Display	Definition
imprintcd	Imprint Code	Identyifying marks on product
size	Size	Description of size of the product
shape	Shape	Description of the shape of the product
color	Color	Description of the color of the product
coating	Coating	Description of the coating of the product
scoring	Scoring	Description of the scoring of the product
logo	Logo	Description of the Logo of the product

See the full registry of code systems defined as part of FHIR.

Explanation of the columns that may appear on this page:

Level | A few code lists that FHIR defines are hierarchical - each code is assigned a level. See Code System for further information.
Source | The source of the definition of the code (when the value set draws in codes defined elsewhere)
Code | The code (used as the code in the resource instance). If the code is in italics, this indicates that the code is not selectable ('Abstract')
Display | The display (used in the display element of a Coding). If there is no display, implementers should not simply display the code, but map the concept into their application
Definition | An explanation of the meaning of the concept
Comments | Additional notes about how to use the code

4.3.14.388 Code System http://terminology.hl7.org/CodeSystem/adjudication-error

URL: https://hl7.org/fhir/R4/codesystem-adjudication-error.html
Financial Management Work Group | Maturity Level: 1 | Draft | Use Context: Not Intended for Production use

This is a code system defined by the FHIR project.

Summary

Defining URL: | http://terminology.hl7.org/CodeSystem/adjudication-error
Version: | 4.0.1
Name: | Adjudication Error Codes
Title:
Definition: | This value set includes a smattering of adjudication codes.
Committee: | Financial Management Work Group
OID: | 2.16.840.1.113883.4.642.4.1053 (for OID based terminology systems)
Copyright: | This is an example set.
Source Resource | XML / JSON

This Code system is used in the following value sets:

• ValueSet: AdjudicationError (This value set includes a smattering of adjudication codes.)

• ValueSet: AdjudicationError (This value set includes a smattering of adjudication codes.)

4.3.14.388.1 Content

4.3.14.388.2 Adjudication Error Codes

This value set includes a smattering of adjudication codes.

Copyright Statement:

This is an example set.

This code system http://terminology.hl7.org/CodeSystem/adjudication-error defines the following codes:

Code	Display	Definition
a001	Missing Identifier	Missing Identifier
a002	Missing Creation Date	Missing Creation Date

See the full registry of code systems defined as part of FHIR.

Explanation of the columns that may appear on this page:

Level | A few code lists that FHIR defines are hierarchical - each code is assigned a level. See Code System for further information.
Source | The source of the definition of the code (when the value set draws in codes defined elsewhere)
Code | The code (used as the code in the resource instance). If the code is in italics, this indicates that the code is not selectable ('Abstract')
Display | The display (used in the display element of a Coding). If there is no display, implementers should not simply display the code, but map the concept into their application
Definition | An explanation of the meaning of the concept
Comments | Additional notes about how to use the code

4.3.14.389 Code System http://hl7.org/fhir/metric-operational-status

URL: https://hl7.org/fhir/R4/codesystem-metric-operational-status.html
Health Care Devices Work Group | Maturity Level: 1 | Trial Use | Use Context: Any

This is a code system defined by the FHIR project.

Summary

Defining URL: | http://hl7.org/fhir/metric-operational-status
Version: | 4.0.1
Name: | DeviceMetricOperationalStatus
Title: | DeviceMetricOperationalStatus
Definition: | Describes the operational status of the DeviceMetric.
Committee: | Health Care Devices Work Group
OID: | 2.16.840.1.113883.4.642.4.647 (for OID based terminology systems)
Source Resource | XML / JSON

This Code system is used in the following value sets:

• ValueSet: DeviceMetricOperationalStatus (Describes the operational status of the DeviceMetric.)
• ValueSet: DeviceMetricOperationalStatus (Describes the operational status of the DeviceMetric.)

4.3.14.389.1 Content

4.3.14.389.2 DeviceMetricOperationalStatus

Describes the operational status of the DeviceMetric.

This code system http://hl7.org/fhir/metric-operational-status defines the following codes:

Code | Display | Definition
on | On | The DeviceMetric is operating and will generate DeviceObservations.
off | Off | The DeviceMetric is not operating.
standby | Standby | The DeviceMetric is operating, but will not generate any DeviceObservations.
entered-in-error | Entered In Error | The DeviceMetric was entered in error.

See the full registry of code systems defined as part of FHIR.

Explanation of the columns that may appear on this page:

Level | A few code lists that FHIR defines are hierarchical - each code is assigned a level. See Code System for further information.
Source | The source of the definition of the code (when the value set draws in codes defined elsewhere)
Code | The code (used as the code in the resource instance). If the code is in italics, this indicates that the code is not selectable ('Abstract')
Display | The display (used in the display element of a Coding). If there is no display, implementers should not simply display the code, but map the concept into their application
Definition | An explanation of the meaning of the concept
Comments | Additional notes about how to use the code

4.3.14.390 Code System http://terminology.hl7.org/CodeSystem/conformance-expectation

URL: https://hl7.org/fhir/R4/codesystem-conformance-expectation.html
Vocabulary Work Group | Maturity Level: 0 | Informative | Use Context: Any

This is a code system defined by the FHIR project.

Summary

Defining URL: | http://terminology.hl7.org/CodeSystem/conformance-expectation
Version: | 4.0.1
Name: | ConformanceExpectation
Title: | ConformanceExpectation
Definition: | Indicates the degree of adherence to a specified behavior or capability expected for a system to be deemed conformant with a specification.
Committee: | ??
OID: | 2.16.840.1.113883.4.642.4.1271 (for OID based terminology systems)
Source Resource | XML / JSON

This Code system is used in the following value sets:

• ValueSet: ConformanceExpectation (Indicates the degree of adherence to a specified behavior or capability expected for a system to be deemed conformant with a specification.)

• ValueSet: ConformanceExpectation (Indicates the degree of adherence to a specified behavior or capability expected for a system to be deemed conformant with a specification.)

4.3.14.390.1 Content

4.3.14.390.2 ConformanceExpectation

Indicates the degree of adherence to a specified behavior or capability expected for a system to be deemed conformant with a specification.

This code system http://terminology.hl7.org/CodeSystem/conformance-expectation defines the following codes:

Code | Display | Definition
SHALL | SHALL | Support for the specified capability is required to be considered conformant.
SHOULD | SHOULD | Support for the specified capability is strongly encouraged, and failure to support it should only occur after careful consideration.
MAY | MAY | Support for the specified capability is not necessary to be considered conformant, and the requirement should be considered strictly optional.
SHOULD-NOT | SHOULD-NOT | Support for the specified capability is strongly discouraged and should occur only after careful consideration.

See the full registry of code systems defined as part of FHIR.

Explanation of the columns that may appear on this page:

Level | A few code lists that FHIR defines are hierarchical - each code is assigned a level. See Code System for further information.
Source | The source of the definition of the code (when the value set draws in codes defined elsewhere)
Code | The code (used as the code in the resource instance). If the code is in italics, this indicates that the code is not selectable ('Abstract')
Display | The display (used in the display element of a Coding). If there is no display, implementers should not simply display the code, but map the concept into their application
Definition | An explanation of the meaning of the concept
Comments | Additional notes about how to use the code

4.3.14.391 Code System http://terminology.hl7.org/CodeSystem/resource-security-category

URL: https://hl7.org/fhir/R4/codesystem-resource-security-category.html
Vocabulary Work Group | Maturity Level: 0 | Informative | Use Context: Any

This is a code system defined by the FHIR project.

Summary

Defining URL: | http://terminology.hl7.org/CodeSystem/resource-security-category
Version: | 4.0.1
Name: | ResourceSecurityCategory
Title: | ResourceSecurityCategory
Definition: | Provides general guidance around the kind of access Control to Read, Search, Create, Update, or Delete a resource.
Committee: | ??
OID: | 2.16.840.1.113883.4.642.4.1404 (for OID based terminology systems)
Source Resource | XML / JSON

This Code system is used in the following value sets:

• ValueSet: ResourceSecurityCategory (Provides general guidance around the kind of access Control to Read, Search, Create, Update, or Delete a resource.)

• ValueSet: ResourceSecurityCategory (Provides general guidance around the kind of access Control to Read, Search, Create, Update, or Delete a resource.)

4.3.14.391.1 Content

4.3.14.391.2 ResourceSecurityCategory

Provides general guidance around the kind of access Control to Read, Search, Create, Update, or Delete a resource.

This code system http://terminology.hl7.org/CodeSystem/resource-security-category defines the following codes:

Code | Display | Definition
anonymous | Anonymous READ Access Resource | These resources tend to not contain any individual data, or business sensitive data. Most often these Resources will be available for anonymous access, meaning there is no access control based on the user or system requesting. However these Resources do tend to contain important information that must be authenticated back to the

source publishing them, and protected from integrity failures in communication. For this reason server authenticated https (TLS) is recommended to provide authentication of the server and integrity protection in transit. This is normal web-server use of https.
business | Business Sensitive Resource | These Resources tend to not contain any individual data, but do have data that describe business or service sensitive data. The use of the term Business is not intended to only mean an incorporated business, but rather the more broad concept of an organization, location, or other group that is not identifable as individuals. Often these resources will require some for of client authentication to assure that only authorized access is given. The client access control may be to individuals, or may be to system identity. For this purpose possible client authentication methods such as: mutual-authenticated-TLS, APIKey, App signed JWT, or App OAuth client-id JWT For example: a App that uses a Business protected Provider Directory to determine other business endpoint details.
individual | Individual Sensitive Resource | These Resources do NOT contain Patient data, but do contain individual information about other participants. These other individuals are Practitioners, PractionerRole, CareTeam, or other users. These identities are needed to enable the practice of healthcare. These identities are identities under general privacy regulations, and thus must consider Privacy risk. Often access to these other identities are covered by business relationships. For this purpose access to these Resources will tend to be Role specific using methods such as RBAC or ABAC.
patient | Patient Sensitive | These Resources make up the bulk of FHIR and therefore are the most commonly understood. These Resources contain highly sesitive health information, or are closely linked to highly sensitive health information. These Resources will often use the security labels to differentiate various confidentiality levels within this broad group of Patient Sensitive data. Access to these Resources often requires a declared Purpose Of Use. Access to these Resources is often controlled by a Privacy Consent.
not-classified | Not classified | Some Resources can be used for a wide scope of use-cases that span very sensitive to very non-sensitive. These Resources do not fall into any of the above classifications, as their sensitivity is highly variable. These Resources will need special handling. These Resources often contain metadata that describes the content in a way that can be used for Access Control decisions.

See the full registry of code systems defined as part of FHIR.

Explanation of the columns that may appear on this page:

Level | A few code lists that FHIR defines are hierarchical - each code is assigned a level. See Code System for further information.
Source | The source of the definition of the code (when the value set draws in codes defined elsewhere)
Code | The code (used as the code in the resource instance). If the code is in italics, this indicates that the code is not selectable ('Abstract')
Display | The display (used in the display element of a Coding). If there is no display, implementers should not simply display the code, but map the concept into their application
Definition | An explanation of the meaning of the concept
Comments | Additional notes about how to use the code

4.3.14.392 Code System http://hl7.org/fhir/quantity-comparator

URL: https://hl7.org/fhir/R4/codesystem-quantity-comparator.html
FHIR Infrastructure Work Group | Maturity Level: N | Normative (from v4.0.0) | Use Context: Any

This is a code system defined by the FHIR project.

Summary

Defining URL: | http://hl7.org/fhir/quantity-comparator
Version: | 4.0.1
Name: | QuantityComparator
Title: | QuantityComparator
Definition: | How the Quantity should be understood and represented.
Committee: | FHIR Infrastructure Work Group
OID: | 2.16.840.1.113883.4.642.4.60 (for OID based terminology systems)
Source Resource | XML / JSON

This Code system is used in the following value sets:

• ValueSet: QuantityComparator (How the Quantity should be understood and represented.)
• ValueSet: QuantityComparator (How the Quantity should be understood and represented.)

4.3.14.392.1 Content

4.3.14.392.2 QuantityComparator

How the Quantity should be understood and represented.

This code system http://hl7.org/fhir/quantity-comparator defines the following codes:

Code | Display | Definition
< | Less than | The actual value is less than the given value.
<= | Less or Equal to | The actual value is less than or equal to the given value.
>= | Greater or Equal to | The actual value is greater than or equal to the given value.
> | Greater than | The actual value is greater than the given value.

See the full registry of code systems defined as part of FHIR.

Explanation of the columns that may appear on this page:

Level | A few code lists that FHIR defines are hierarchical - each code is assigned a level. See Code System for further information.
Source | The source of the definition of the code (when the value set draws in codes defined elsewhere)

Code | The code (used as the code in the resource instance). If the code is in italics, this indicates that the code is not selectable ('Abstract')
Display | The display (used in the display element of a Coding). If there is no display, implementers should not simply display the code, but map the concept into their application
Definition | An explanation of the meaning of the concept
Comments | Additional notes about how to use the code

4.3.14.393 Code System http://hl7.org/fhir/message-significance-category

URL: https://hl7.org/fhir/R4/codesystem-message-significance-category.html
Infrastructure And Messaging Work Group | Maturity Level: 1 | Trial Use | Use Context: Any

This is a code system defined by the FHIR project.

Summary

Defining URL: | http://hl7.org/fhir/message-significance-category
Version: | 4.0.1
Name: | MessageSignificanceCategory
Title: | MessageSignificanceCategory
Definition: | The impact of the content of a message.
Committee: | Infrastructure And Messaging Work Group
OID: | 2.16.840.1.113883.4.642.4.189 (for OID based terminology systems)
Source Resource | XML / JSON

This Code system is used in the following value sets:

• ValueSet: MessageSignificanceCategory (The impact of the content of a message.)
• ValueSet: MessageSignificanceCategory (The impact of the content of a message.)

4.3.14.393.1 Content

4.3.14.393.2 MessageSignificanceCategory

The impact of the content of a message.

This code system http://hl7.org/fhir/message-significance-category defines the following codes:

Code | Display | Definition
consequence | Consequence | The message represents/requests a change that should not be processed more than once; e.g., making a booking for an appointment.
currency | Currency | The message represents a response to query for current information. Retrospective processing is wrong and/or wasteful.
notification | Notification | The content is not necessarily intended to be current, and it can be reprocessed, though there may be version issues created by processing old notifications.

See the full registry of code systems defined as part of FHIR.

Explanation of the columns that may appear on this page:

Level | A few code lists that FHIR defines are hierarchical - each code is assigned a level. See Code System for further information.
Source | The source of the definition of the code (when the value set draws in codes defined elsewhere)
Code | The code (used as the code in the resource instance). If the code is in italics, this indicates that the code is not selectable ('Abstract')
Display | The display (used in the display element of a Coding). If there is no display, implementers should not simply display the code, but map the concept into their application
Definition | An explanation of the meaning of the concept
Comments | Additional notes about how to use the code

4.3.14.394 Code System http://hl7.org/fhir/provenance-participant-role

URL: https://hl7.org/fhir/R4/codesystem-provenance-agent-role.html
Financial Management Work Group | Maturity Level: 1 | Draft | Use Context: Any

This is a code system defined by the FHIR project.

Summary

Defining URL: | http://hl7.org/fhir/provenance-participant-role
Version: | 4.0.1
Name: | ProvenanceParticipantRole
Title: | Provenance participant role
Definition: | The role that a provenance participant played
Committee: | Financial Management Work Group
OID: | 2.16.840.1.113883.4.642.4.1306 (for OID based terminology systems)
Source Resource | XML / JSON

This Code system is used in the following value sets:

• ValueSet: Provenance participant role (The role that a provenance participant played)
• ValueSet: Provenance participant role (The role that a provenance participant played)

4.3.14.394.1 Content

4.3.14.394.2 Provenance participant role

The role that a provenance participant played

This code system http://hl7.org/fhir/provenance-participant-role defines the following codes:

Lvl | Code | Display | Definition
1 | enterer | Enterer | A person entering the data into the originating system
1 | performer | Performer | A person, animal, organization or device that who actually and principally carries out the activity
1 | author | Author | A party that originates the resource and therefore has responsibility for the information given in the resource and ownership of this resource
1 | verifier | Verifier | A person who verifies the correctness and appropriateness of activity
2 | legal | Legal Authenticator | The person authenticated the content and accepted legal responsibility for its content
1 | attester | Attester | A verifier who attests to the accuracy of the resource
1 | informant | Informant | A person who reported information that contributed to the resource
1 | custodian | Custodian | The entity that is accountable for maintaining a true an accurate copy of the original record
1 | assembler | Assembler | A device that operates independently of an author on custodian's algorithms for data extraction of existing information for purpose of generating a new artifact.
1 | composer | Composer | A device used by an author to record new information, which may also be used by the author to select existing information for aggregation with newly recorded information for the purpose of generating a new artifact.

See the full registry of code systems defined as part of FHIR.

Explanation of the columns that may appear on this page:

Level | A few code lists that FHIR defines are hierarchical - each code is assigned a level. See Code System for further information.
Source | The source of the definition of the code (when the value set draws in codes defined elsewhere)
Code | The code (used as the code in the resource instance). If the code is in italics, this indicates that the code is not selectable ('Abstract')
Display | The display (used in the display element of a Coding). If there is no display, implementers should not simply display the code, but map the concept into their application
Definition | An explanation of the meaning of the concept
Comments | Additional notes about how to use the code

4.3.14.395 Code System http://hl7.org/fhir/document-mode

URL: https://hl7.org/fhir/R4/codesystem-document-mode.html
FHIR Infrastructure Work Group | Maturity Level: N | Normative (from v4.0.0) | Use Context: Any

| This page has been approved as part of an ANSI standard. See the Conformance Package for further details.

This is a code system defined by the FHIR project.

Summary

Defining URL: | http://hl7.org/fhir/document-mode
Version: | 4.0.1
Name: | DocumentMode
Title: | DocumentMode
Definition: | Whether the application produces or consumes documents.
Committee: | FHIR Infrastructure Work Group
OID: | 2.16.840.1.113883.4.642.4.187 (for OID based terminology systems)
Source Resource | XML / JSON

This Code system is used in the following value sets:

• ValueSet: DocumentMode (Whether the application produces or consumes documents.)
• ValueSet: DocumentMode (Whether the application produces or consumes documents.)

4.3.14.395.1 Content

4.3.14.395.2 DocumentMode

Whether the application produces or consumes documents.

This code system http://hl7.org/fhir/document-mode defines the following codes:

Code | Display | Definition
producer | Producer | The application produces documents of the specified type.
consumer | Consumer | The application consumes documents of the specified type.

See the full registry of code systems defined as part of FHIR.

Explanation of the columns that may appear on this page:

Level | A few code lists that FHIR defines are hierarchical - each code is assigned a level. See Code System for further information.
Source | The source of the definition of the code (when the value set draws in codes defined elsewhere)

Code | The code (used as the code in the resource instance). If the code is in italics, this indicates that the code is not selectable ('Abstract')
Display | The display (used in the display element of a Coding). If there is no display, implementers should not simply display the code, but map the concept into their application
Definition | An explanation of the meaning of the concept
Comments | Additional notes about how to use the code

4.3.14.396 Code System http://terminology.hl7.org/CodeSystem/ex-USCLS

URL: https://hl7.org/fhir/R4/codesystem-service-uscls.html
Financial Management Work Group | Maturity Level: 1 | Draft | Use Context: Any

This is a code system defined by the FHIR project.

Summary

Defining URL: | http://terminology.hl7.org/CodeSystem/ex-USCLS
Version: | 4.0.1
Name: | USCLSCodes
Title: | USCLS Codes
Definition: | This value set includes a smattering of USCLS codes.
Committee: | Financial Management Work Group
OID: | 2.16.840.1.113883.4.642.4.1153 (for OID based terminology systems)
Copyright: | This is an example set.
Source Resource | XML / JSON

This Code system is used in the following value sets:

• ValueSet: USCLS Codes (This value set includes a smattering of USCLS codes.)

• ValueSet: USCLS Codes (This value set includes a smattering of USCLS codes.)

4.3.14.396.1 Content

4.3.14.396.2 USCLS Codes

This value set includes a smattering of USCLS codes.

Copyright Statement:

This is an example set.

This code system http://terminology.hl7.org/CodeSystem/ex-USCLS defines the following codes:

Code | Display | Definition
1101 | Exam, comp, primary | Exam, comp, primary
1102 | Exam, comp, mixed | Exam, comp, mixed
1103 | Exam, comp, permanent | Exam, comp, permanent
1201 | Exam, recall | Exam, recall
1205 | Exam, emergency | Exam, emergency
2101 | Radiograph, series (12) | Radiograph, series (12)
2102 | Radiograph, series (16) | Radiograph, series (16)
2141 | Radiograph, bitewing | Radiograph, bitewing
2601 | Radiograph, panoramic | Radiograph, panoramic
11101 | Polishing, 1 unit | Polishing, 1 unit
11102 | Polishing, 2 unit | Polishing, 2 unit
11103 | Polishing, 3 unit | Polishing, 3 unit
11104 | Polishing, 4 unit | Polishing, 4 unit
21211 | Amalgam, 1 surface | Amalgam, 1 surface
21212 | Amalgam, 2 surface | Amalgam, 2 surface
27211 | Crown, PFM | Crown, PFM
67211 | Maryland Bridge | Maryland Bridge
99111 | Lab, commercial | Lab, commercial
99333 | Lab, in office | Lab, in office
99555 | Expense | Expense

See the full registry of code systems defined as part of FHIR.

Explanation of the columns that may appear on this page:

Level | A few code lists that FHIR defines are hierarchical - each code is assigned a level. See Code System for further information.
Source | The source of the definition of the code (when the value set draws in codes defined elsewhere)
Code | The code (used as the code in the resource instance). If the code is in italics, this indicates that the code is not selectable ('Abstract')
Display | The display (used in the display element of a Coding). If there is no display, implementers should not simply display the code, but map the concept into their application
Definition | An explanation of the meaning of the concept
Comments | Additional notes about how to use the code

4.3.14.397 Code System http://hl7.org/fhir/abstract-types

URL: https://hl7.org/fhir/R4/codesystem-abstract-types.html
FHIR Infrastructure Work Group | Maturity Level: N | Normative (from v4.0.0) | Use Context: Any

| This page has been approved as part of an ANSI standard. See the Conformance Package for further details.

This is a code system defined by the FHIR project.

Summary

Defining URL: | http://hl7.org/fhir/abstract-types
Version: | 4.0.1
Name: | AbstractType
Title: | AbstractType
Definition: | A list of the base types defined by this version of the FHIR specification - types that are defined, but for which only specializations actually are created.
Committee: | FHIR Infrastructure Work Group
OID: | (for OID based terminology systems)
Source Resource | XML / JSON

This Code System is normative - it is generated based on the information defined in this specification. The definition will remain fixed across versions, but the actual contents will change from version to version

This Code system is used in the following value sets:

• ValueSet: AbstractType (A list of the base types defined by this version of the FHIR specification - types that are defined, but for which only specializations actually are created.)

• ValueSet: AbstractType (A list of the base types defined by this version of the FHIR specification - types that are defined, but for which only specializations actually are created.)

• ValueSet: FHIRAllTypes (A list of all the concrete types defined in this version of the FHIR specification - Abstract Types, Data Types and Resource Types.)

• ValueSet: FHIRAllTypes (A list of all the concrete types defined in this version of the FHIR specification - Abstract Types, Data Types and Resource Types.)

4.3.14.397.1 Content

4.3.14.397.2 AbstractType

A list of the base types defined by this version of the FHIR specification - types that are defined, but for which only specializations actually are created.

This code system http://hl7.org/fhir/abstract-types defines the following codes:

Code | Display | Definition
Type | Type | A place holder that means any kind of data type
Any | Any | A place holder that means any kind of resource

See the full registry of code systems defined as part of FHIR.

Explanation of the columns that may appear on this page:

Level | A few code lists that FHIR defines are hierarchical - each code is assigned a level. See Code System for further information.
Source | The source of the definition of the code (when the value set draws in codes defined elsewhere)
Code | The code (used as the code in the resource instance). If the code is in italics, this indicates that the code is not selectable ('Abstract')
Display | The display (used in the display element of a Coding). If there is no display, implementers should not simply display the code, but map the concept into their application
Definition | An explanation of the meaning of the concept
Comments | Additional notes about how to use the code

4.3.14.398 Code System http://terminology.hl7.org/CodeSystem/diagnosis-role

URL: https://hl7.org/fhir/R4/codesystem-diagnosis-role.html
Patient Administration Work Group | Maturity Level: 0 | Informative | Use Context: Any

This is a code system defined by the FHIR project.

Summary

Defining URL: | http://terminology.hl7.org/CodeSystem/diagnosis-role
Version: | 4.0.1
Name: | DiagnosisRole
Title:
Definition: | This value set defines a set of codes that can be used to express the role of a diagnosis on the Encounter or EpisodeOfCare record.
Committee: | Patient Administration Work Group
OID: | 2.16.840.1.113883.4.642.4.1054 (for OID based terminology systems)
Source Resource | XML / JSON

This Code system is used in the following value sets:

• ValueSet: DiagnosisRole (This value set defines a set of codes that can be used to express the role of a diagnosis on the Encounter or EpisodeOfCare record.)

• ValueSet: DiagnosisRole (This value set defines a set of codes that can be used to express the role of a diagnosis on the Encounter or EpisodeOfCare record.)

4.3.14.398.1 Content

4.3.14.398.2 DiagnosisRole

This value set defines a set of codes that can be used to express the role of a diagnosis on the Encounter or EpisodeOfCare record.

This code system http://terminology.hl7.org/CodeSystem/diagnosis-role defines the following codes:

Code | Display | Definition
AD | Admission diagnosis
DD | Discharge diagnosis
CC | Chief complaint
CM | Comorbidity diagnosis
pre-op | pre-op diagnosis
post-op | post-op diagnosis
billing | Billing

See the full registry of code systems defined as part of FHIR.

Explanation of the columns that may appear on this page:

Level | A few code lists that FHIR defines are hierarchical - each code is assigned a level. See Code System for further information.
Source | The source of the definition of the code (when the value set draws in codes defined elsewhere)
Code | The code (used as the code in the resource instance). If the code is in italics, this indicates that the code is not selectable ('Abstract')
Display | The display (used in the display element of a Coding). If there is no display, implementers should not simply display the code, but map the concept into their application
Definition | An explanation of the meaning of the concept
Comments | Additional notes about how to use the code

4.3.14.399 Code System http://hl7.org/fhir/questionnaire-item-control

URL: https://hl7.org/fhir/R4/codesystem-questionnaire-item-control.html
Vocabulary Work Group | Maturity Level: 0 | Informative | Use Context: Any

This is a code system defined at http://www.hl7.org/Special/committees/patientcare .

Summary

Defining URL: | http://hl7.org/fhir/questionnaire-item-control
Version: | 4.0.1
Name: | QuestionnaireItemUIControlCodes
Title: | Questionnaire Item UI Control Codes
Definition: | Starter set of user interface control/display mechanisms that might be used when rendering an item in a questionnaire.
Committee: | ??
OID: | 2.16.840.1.113883.4.642.4.932 (for OID based terminology systems)
Source Resource | XML / JSON

This Code system is used in the following value sets:

• ValueSet: Questionnaire Item UI Control Codes (Starter set of user interface control/display mechanisms that might be used when rendering an item in a questionnaire.)

• ValueSet: Questionnaire Item UI Control Codes (Starter set of user interface control/display mechanisms that might be used when rendering an item in a questionnaire.)

4.3.14.399.1 Content

4.3.14.399.2 Questionnaire Item UI Control Codes

Starter set of user interface control/display mechanisms that might be used when rendering an item in a questionnaire.

Properties

Code | URL | Description | Type
abstract | | True if an element is considered 'abstract' - that is the code is not for use as a real concept | boolean

This code system http://hl7.org/fhir/questionnaire-item-control defines the following codes:

Lvl | Code | Display | Definition

1 | group | | UI controls relevant to organizing groups of questions
2 | list | List | Questions within the group should be listed sequentially
2 | table | Vertical Answer Table | Questions within the group are rows in the table with possible answers as columns. Used for 'choice' questions.
2 | htable | Horizontal Answer Table | Questions within the group are columns in the table with possible answers as rows. Used for 'choice' questions.
2 | gtable | Group Table | Questions within the group are columns in the table with each group repetition as a row. Used for single-answer questions.
2 | atable | Answer Table | This table has one row - for the question. Permitted answers are columns. Used for choice questions.
2 | header | Header | The group is to be continuously visible at the top of the questionnaire
2 | footer | Footer | The group is to be continuously visible at the bottom of the questionnaire
1 | text | | UI controls relevant to rendering questionnaire text items
2 | inline | In-line | Text is displayed as a paragraph in a sequential position between sibling items (default behavior)
2 | prompt | Prompt | Text is displayed immediately below or within the answer-entry area of the containing question item (typically as a guide for what to enter)
2 | unit | Unit | Text is displayed adjacent (horizontally or vertically) to the answer space for the parent question, typically to indicate a unit of measure
2 | lower | Lower-bound | Text is displayed to the left of the set of answer choices or a scaling control for the parent question item to indicate the meaning of the 'lower' bound. E.g. 'Strongly disagree'
2 | upper | Upper-bound | Text is displayed to the right of the set of answer choices or a scaling control for the parent question item to indicate the meaning of the 'upper' bound. E.g. 'Strongly agree'
2 | flyover | Fly-over | Text is temporarily visible over top of an item if the mouse is positioned over top of the text for the containing item
2 | help | Help-Button | Text is displayed in a dialog box or similar control if invoked by pushing a button or some other UI-appropriate action to request 'help' for a question, group or the questionnaire as a whole (depending what the text is nested within)
1 | question | | UI controls relevant to capturing question data
2 | autocomplete | Auto-complete | A control which provides a list of potential matches based on text entered into a control. Used for large choice sets where text-matching is an appropriate discovery mechanism.
2 | drop-down | Drop down | A control where an item (or multiple items) can be selected from a list that is only displayed when the user is editing the field.
2 | check-box | Check-box | A control where choices are listed with a box beside them. The box can be toggled to select or de-select a given choice. Multiple selections may be possible.
2 | lookup | Lookup | A control where editing an item spawns a separate dialog box or screen permitting a user to navigate, filter or otherwise discover an appropriate match. Useful for large choice sets where text matching is not an appropriate discovery mechanism. Such screens must generally be tuned for the specific choice list structure.
2 | radio-button | Radio Button | A control where choices are listed with a button beside them. The button can be toggled to select or de-select a given choice. Selecting one item deselects all others.
2 | slider | Slider | A control where an axis is displayed between the high and low values and the control can be visually manipulated to select a value anywhere on the axis.
2 | spinner | Spinner | A control where a list of numeric or other ordered values can be scrolled through via arrows.
2 | text-box | Text Box | A control where a user can type in their answer freely.

See the full registry of code systems defined as part of FHIR.

Explanation of the columns that may appear on this page:

Level | A few code lists that FHIR defines are hierarchical - each code is assigned a level. See Code System for further information.
Source | The source of the definition of the code (when the value set draws in codes defined elsewhere)
Code | The code (used as the code in the resource instance). If the code is in italics, this indicates that the code is not selectable ('Abstract')
Display | The display (used in the display element of a Coding). If there is no display, implementers should not simply display the code, but map the concept into their application
Definition | An explanation of the meaning of the concept
Comments | Additional notes about how to use the code

4.3.14.400 Code System http://terminology.hl7.org/CodeSystem/benefit-network

URL: https://hl7.org/fhir/R4/codesystem-benefit-network.html
Financial Management Work Group | Maturity Level: 1 | Draft | Use Context: Any

This is a code system defined by the FHIR project.

Summary

Defining URL: | http://terminology.hl7.org/CodeSystem/benefit-network
Version: | 4.0.1
Name: | NetworkTypeCodes
Title: | Network Type Codes
Definition: | This value set includes a smattering of Network type codes.
Committee: | Financial Management Work Group
OID: | 2.16.840.1.113883.4.642.4.1177 (for OID based terminology systems)
Copyright: | This is an example set.
Source Resource | XML / JSON

This Code system is used in the following value sets:

• ValueSet: Network Type Codes (This value set includes a smattering of Network type codes.)
• ValueSet: Network Type Codes (This value set includes a smattering of Network type codes.)

4.3.14.400.1 Content

4.3.14.400.2 Network Type Codes

This value set includes a smattering of Network type codes.

Copyright Statement:

This is an example set.

This code system http://terminology.hl7.org/CodeSystem/benefit-network defines the following codes:

Code | Display | Definition
in | In Network | Services rendered by a Network provider
out | Out of Network | Services rendered by a provider who is not in the Network

See the full registry of code systems defined as part of FHIR.

Explanation of the columns that may appear on this page:

Level | A few code lists that FHIR defines are hierarchical - each code is assigned a level. See Code System for further information.
Source | The source of the definition of the code (when the value set draws in codes defined elsewhere)
Code | The code (used as the code in the resource instance). If the code is in italics, this indicates that the code is not selectable ('Abstract')
Display | The display (used in the display element of a Coding). If there is no display, implementers should not simply display the code, but map the concept into their application
Definition | An explanation of the meaning of the concept
Comments | Additional notes about how to use the code

4.3.14.401 Code System http://hl7.org/fhir/CodeSystem/task-code

URL: https://hl7.org/fhir/R4/codesystem-task-code.html
Orders and Observations Work Group | Maturity Level: 1 | Draft | Use Context: Any

This is a code system defined by the FHIR project.

Summary

Defining URL: | http://hl7.org/fhir/CodeSystem/task-code
Version: | 4.0.1
Name: | TaskCode
Title: | Task Codes
Definition: | Codes indicating the type of action that is expected to be performed
Committee: | Orders and Observations Work Group
OID: | 2.16.840.1.113883.4.642.4.1397 (for OID based terminology systems)
Source Resource | XML / JSON

This Code system is used in the following value sets:

• ValueSet: Task Codes (Codes indicating the type of action that is expected to be performed)
• ValueSet: Task Codes (Codes indicating the type of action that is expected to be performed)

4.3.14.401.1 Content

4.3.14.401.2 Task Codes

Codes indicating the type of action that is expected to be performed

This code system http://hl7.org/fhir/CodeSystem/task-code defines the following codes:

Code | Display | Definition
approve | Activate/approve the focal resource | Take what actions are needed to transition the focus resource from 'draft' to 'active' or 'in-progress', as appropriate for the resource type. This may involve additing additional content, approval, validation, etc.
fulfill | Fulfill the focal request | Act to perform the actions defined in the focus request. This might result in a 'more assertive' request (order for a plan or proposal, filler order for a placer order), but is intend to eventually result in events. The degree of fulfillment requested might be limited by Task.restriction.
abort | Mark the focal resource as no longer active | Abort, cancel or withdraw the focal resource, as appropriate for the type of resource.
replace | Replace the focal resource with the input resource | Replace the focal resource with the specified input resource
change | Change the focal resource | Update the focal resource of the owning system to reflect the content specified as the Task.focus
suspend | Suspend the focal resource | Transition the focal resource from 'active' or 'in-progress' to 'suspended'
resume | Re-activate the focal resource | Transition the focal resource from 'suspended' to 'active' or 'in-progress' as appropriate for the resource type.

See the full registry of code systems defined as part of FHIR.

Explanation of the columns that may appear on this page:

Level | A few code lists that FHIR defines are hierarchical - each code is assigned a level. See Code System for further information.
Source | The source of the definition of the code (when the value set draws in codes defined elsewhere)
Code | The code (used as the code in the resource instance). If the code is in italics, this indicates that the code is not selectable ('Abstract')
Display | The display (used in the display element of a Coding). If there is no display, implementers should not simply display the code, but map the concept into their application
Definition | An explanation of the meaning of the concept
Comments | Additional notes about how to use the code

4.3.14.402 Code System http://hl7.org/fhir/variable-type

URL: https://hl7.org/fhir/R4/codesystem-variable-type.html
Clinical Decision Support Work Group | Maturity Level: 0 | Trial Use | Use Context: Any

This is a code system defined by the FHIR project.

Summary

Defining URL: | http://hl7.org/fhir/variable-type
Version: | 4.0.1
Name: | EvidenceVariableType
Title: | EvidenceVariableType
Definition: | The possible types of variables for exposures or outcomes (E.g. Dichotomous, Continuous, Descriptive).
Committee: | Clinical Decision Support Work Group
OID: | 2.16.840.1.113883.4.642.4.1344 (for OID based terminology systems)
Source Resource | XML / JSON

This Code system is used in the following value sets:

• ValueSet: EvidenceVariableType (The possible types of variables for exposures or outcomes (E.g. Dichotomous, Continuous, Descriptive).)

• ValueSet: EvidenceVariableType (The possible types of variables for exposures or outcomes (E.g. Dichotomous, Continuous, Descriptive).)

4.3.14.402.1 Content

4.3.14.402.2 EvidenceVariableType

The possible types of variables for exposures or outcomes (E.g. Dichotomous, Continuous, Descriptive).

This code system http://hl7.org/fhir/variable-type defines the following codes:

Code | Display | Definition
dichotomous | Dichotomous | The variable is dichotomous, such as present or absent.
continuous | Continuous | The variable is a continuous result such as a quantity.
descriptive | Descriptive | The variable is described narratively rather than quantitatively.

See the full registry of code systems defined as part of FHIR.

Explanation of the columns that may appear on this page:

Level | A few code lists that FHIR defines are hierarchical - each code is assigned a level. See Code System for further information.
Source | The source of the definition of the code (when the value set draws in codes defined elsewhere)
Code | The code (used as the code in the resource instance). If the code is in italics, this indicates that the code is not selectable ('Abstract')
Display | The display (used in the display element of a Coding). If there is no display, implementers should not simply display the code, but map the concept into their application
Definition | An explanation of the meaning of the concept
Comments | Additional notes about how to use the code

4.3.14.403 Code System http://terminology.hl7.org/CodeSystem/financialtaskinputtype

URL: https://hl7.org/fhir/R4/codesystem-financial-taskinputtype.html
Vocabulary Work Group | Maturity Level: 0 | Informative | Use Context: Any

This is a code system defined by the FHIR project.

Summary

Defining URL: | http://terminology.hl7.org/CodeSystem/financialtaskinputtype
Version: | 4.0.1
Name: | FinancialTaskInputTypeCodes
Title: | Financial Task Input Type Codes
Definition: | This value set includes Financial Task Input Type codes.
Committee: | ??
OID: | 2.16.840.1.113883.4.642.4.1392 (for OID based terminology systems)
Copyright: | This is an example set.

Source Resource | XML / JSON

This Code system is used in the following value sets:

• ValueSet: Financial Task Input Type Codes (This value set includes Financial Task Input Type codes.)

• ValueSet: Financial Task Input Type Codes (This value set includes Financial Task Input Type codes.)

4.3.14.403.1 Content

4.3.14.403.2 Financial Task Input Type Codes

This value set includes Financial Task Input Type codes.

Copyright Statement:

This is an example set.

This code system http://terminology.hl7.org/CodeSystem/financialtaskinputtype defines the following codes:

Code	Display	Definition
include	Include	The name of a resource to include in a selection.
exclude	Exclude	The name of a resource to not include in a selection.
origresponse	Original Response	A reference to the response resource to the original processing of a resource.
reference	Reference Number	A reference value which must be quoted to authorize an action.
item	Item Number	The sequence number associated with an item for reprocessing.
period	Period	The reference period for the action being requested.
status	Status code	The processing status from a check on the processing status of a resource such as the adjudication of a claim.

See the full registry of code systems defined as part of FHIR.

Explanation of the columns that may appear on this page:

Level | A few code lists that FHIR defines are hierarchical - each code is assigned a level. See Code System for further information.
Source | The source of the definition of the code (when the value set draws in codes defined elsewhere)
Code | The code (used as the code in the resource instance). If the code is in italics, this indicates that the code is not selectable ('Abstract')
Display | The display (used in the display element of a Coding). If there is no display, implementers should not simply display the code, but map the concept into their application
Definition | An explanation of the meaning of the concept
Comments | Additional notes about how to use the code

4.3.14.404 Code System http://hl7.org/fhir/audit-event-outcome

URL: https://hl7.org/fhir/R4/codesystem-audit-event-outcome.html
Security Work Group | Maturity Level: 3 | Trial Use | Use Context: Any

This is a code system defined by the FHIR project.

Summary

Defining URL: | http://hl7.org/fhir/audit-event-outcome
Version: | 4.0.1
Name: | AuditEventOutcome
Title: | AuditEventOutcome
Definition: | Indicates whether the event succeeded or failed.
Committee: | Security Work Group
OID: | 2.16.840.1.113883.4.642.4.455 (for OID based terminology systems)
Source Resource | XML / JSON

This Code system is used in the following value sets:

• ValueSet: AuditEventOutcome (Indicates whether the event succeeded or failed.)

• ValueSet: AuditEventOutcome (Indicates whether the event succeeded or failed.)

4.3.14.404.1 Content

4.3.14.404.2 AuditEventOutcome

Indicates whether the event succeeded or failed.

This code system http://hl7.org/fhir/audit-event-outcome defines the following codes:

Code	Display	Definition
0	Success	The operation completed successfully (whether with warnings or not).
4	Minor failure	The action was not successful due to some kind of minor failure (often equivalent to an HTTP 400 response).
8	Serious failure	The action was not successful due to some kind of unexpected error (often equivalent to an HTTP 500 response).
12	Major failure	An error of such magnitude occurred that the system is no longer available for use (i.e. the system died).

See the full registry of code systems defined as part of FHIR.

Explanation of the columns that may appear on this page:

Level | A few code lists that FHIR defines are hierarchical - each code is assigned a level. See Code System for further information.
Source | The source of the definition of the code (when the value set draws in codes defined elsewhere)
Code | The code (used as the code in the resource instance). If the code is in italics, this indicates that the code is not selectable ('Abstract')
Display | The display (used in the display element of a Coding). If there is no display, implementers should not simply display the code, but map the concept into their application
Definition | An explanation of the meaning of the concept
Comments | Additional notes about how to use the code

4.3.14.405 Code System http://hl7.org/fhir/vision-base-codes

URL: https://hl7.org/fhir/R4/codesystem-vision-base-codes.html
Financial Management Work Group | Maturity Level: 2 | Trial Use | Use Context: Any

This is a code system defined by the FHIR project.

Summary

Defining URL: | http://hl7.org/fhir/vision-base-codes
Version: | 4.0.1
Name: | VisionBase
Title: | VisionBase
Definition: | A coded concept listing the base codes.
Committee: | Financial Management Work Group
OID: | 2.16.840.1.113883.4.642.4.663 (for OID based terminology systems)
Source Resource | XML / JSON

This Code system is used in the following value sets:

• ValueSet: VisionBase (A coded concept listing the base codes.)

• ValueSet: VisionBase (A coded concept listing the base codes.)

4.3.14.405.1 Content

4.3.14.405.2 VisionBase

A coded concept listing the base codes.

This code system http://hl7.org/fhir/vision-base-codes defines the following codes:

Code | Display | Definition
up | Up | top.
down | Down | bottom.
in | In | inner edge.
out | Out | outer edge.

See the full registry of code systems defined as part of FHIR.

Explanation of the columns that may appear on this page:

Level | A few code lists that FHIR defines are hierarchical - each code is assigned a level. See Code System for further information.
Source | The source of the definition of the code (when the value set draws in codes defined elsewhere)
Code | The code (used as the code in the resource instance). If the code is in italics, this indicates that the code is not selectable ('Abstract')
Display | The display (used in the display element of a Coding). If there is no display, implementers should not simply display the code, but map the concept into their application
Definition | An explanation of the meaning of the concept
Comments | Additional notes about how to use the code

4.3.14.406 Code System http://hl7.org/fhir/search-param-type

URL: https://hl7.org/fhir/R4/codesystem-search-param-type.html
FHIR Infrastructure Work Group | Maturity Level: N | Normative (from v4.0.0) | Use Context: Any

| This page has been approved as part of an ANSI standard. See the Conformance Package for further details.

This is a code system defined by the FHIR project.

Summary

Defining URL: | http://hl7.org/fhir/search-param-type
Version: | 4.0.1
Name: | SearchParamType
Title: | SearchParamType
Definition: | Data types allowed to be used for search parameters.
Committee: | FHIR Infrastructure Work Group
OID: | 2.16.840.1.113883.4.642.4.12 (for OID based terminology systems)
Source Resource | XML / JSON

This Code system is used in the following value sets:

• ValueSet: SearchParamType (Data types allowed to be used for search parameters.)
• ValueSet: SearchParamType (Data types allowed to be used for search parameters.)

4.3.14.406.1 Content

4.3.14.406.2 SearchParamType

Data types allowed to be used for search parameters.

This code system http://hl7.org/fhir/search-param-type defines the following codes:

Code | Display | Definition
number | Number | Search parameter SHALL be a number (a whole number, or a decimal).
date | Date/DateTime | Search parameter is on a date/time. The date format is the standard XML format, though other formats may be supported.
string | String | Search parameter is a simple string, like a name part. Search is case-insensitive and accent-insensitive. May match just the start of a string. String parameters may contain spaces.
token | Token | Search parameter on a coded element or identifier. May be used to search through the text, display, code and code/codesystem (for codes) and label, system and key (for identifier). Its value is either a string or a pair of namespace and value, separated by a "|", depending on the modifier used.
reference | Reference | A reference to another resource (Reference or canonical).
composite | Composite | A composite search parameter that combines a search on two values together.
quantity | Quantity | A search parameter that searches on a quantity.
uri | URI | A search parameter that searches on a URI (RFC 3986).
special | Special | Special logic applies to this parameter per the description of the search parameter.

See the full registry of code systems defined as part of FHIR.

Explanation of the columns that may appear on this page:

Level | A few code lists that FHIR defines are hierarchical - each code is assigned a level. See Code System for further information.
Source | The source of the definition of the code (when the value set draws in codes defined elsewhere)
Code | The code (used as the code in the resource instance). If the code is in italics, this indicates that the code is not selectable ('Abstract')
Display | The display (used in the display element of a Coding). If there is no display, implementers should not simply display the code, but map the concept into their application
Definition | An explanation of the meaning of the concept
Comments | Additional notes about how to use the code

4.3.14.407 Code System http://terminology.hl7.org/CodeSystem/supply-item-type

URL: https://hl7.org/fhir/R4/codesystem-supplydelivery-type.html
Orders and Observations Work Group | Maturity Level: 1 | Trial Use | Use Context: Any

This is a code system defined by the FHIR project.

Summary

Defining URL: | http://terminology.hl7.org/CodeSystem/supply-item-type
Version: | 4.0.1
Name: | SupplyItemType
Title: | Supply Item Type
Definition: | This value sets refers to a specific supply item.
Committee: | Orders and Observations Work Group
OID: | 2.16.840.1.113883.4.642.4.1194 (for OID based terminology systems)
Source Resource | XML / JSON

This Code system is used in the following value sets:

• ValueSet: Supply Item Type (This value sets refers to a specific supply item.)
• ValueSet: Supply Item Type (This value sets refers to a specific supply item.)

4.3.14.407.1 Content

4.3.14.407.2 Supply Item Type

This value sets refers to a specific supply item.

This code system http://terminology.hl7.org/CodeSystem/supply-item-type defines the following codes:

Code | Display | Definition
medication | Medication | Supply is a kind of medication.
device | Device | What is supplied (or requested) is a device.

See the full registry of code systems defined as part of FHIR.

Explanation of the columns that may appear on this page:

Level | A few code lists that FHIR defines are hierarchical - each code is assigned a level. See Code System for further information.
Source | The source of the definition of the code (when the value set draws in codes defined elsewhere)

Code | The code (used as the code in the resource instance). If the code is in italics, this indicates that the code is not selectable ('Abstract')
Display | The display (used in the display element of a Coding). If there is no display, implementers should not simply display the code, but map the concept into their application
Definition | An explanation of the meaning of the concept
Comments | Additional notes about how to use the code

4.3.14.408 Code System http://hl7.org/fhir/action-cardinality-behavior

URL: https://hl7.org/fhir/R4/codesystem-action-cardinality-behavior.html
Clinical Decision Support Work Group | Maturity Level: 2 | Trial Use | Use Context: Any

This is a code system defined by the FHIR project.

Summary

Defining URL: | http://hl7.org/fhir/action-cardinality-behavior
Version: | 4.0.1
Name: | ActionCardinalityBehavior
Title: | ActionCardinalityBehavior
Definition: | Defines behavior for an action or a group for how many times that item may be repeated.
Committee: | Clinical Decision Support Work Group
OID: | 2.16.840.1.113883.4.642.4.808 (for OID based terminology systems)
Source Resource | XML / JSON

This Code system is used in the following value sets:

• ValueSet: ActionCardinalityBehavior (Defines behavior for an action or a group for how many times that item may be repeated.)

• ValueSet: ActionCardinalityBehavior (Defines behavior for an action or a group for how many times that item may be repeated.)

4.3.14.408.1 Content

4.3.14.408.2 ActionCardinalityBehavior

Defines behavior for an action or a group for how many times that item may be repeated.

This code system http://hl7.org/fhir/action-cardinality-behavior defines the following codes:

Code | Display | Definition
single | Single | The action may only be selected one time.
multiple | Multiple | The action may be selected multiple times.

See the full registry of code systems defined as part of FHIR.

Explanation of the columns that may appear on this page:

Level | A few code lists that FHIR defines are hierarchical - each code is assigned a level. See Code System for further information.
Source | The source of the definition of the code (when the value set draws in codes defined elsewhere)
Code | The code (used as the code in the resource instance). If the code is in italics, this indicates that the code is not selectable ('Abstract')
Display | The display (used in the display element of a Coding). If there is no display, implementers should not simply display the code, but map the concept into their application
Definition | An explanation of the meaning of the concept
Comments | Additional notes about how to use the code

4.3.14.409 Code System http://terminology.hl7.org/CodeSystem/coverageeligibilityresponse-ex-auth-support

URL: https://hl7.org/fhir/R4/codesystem-coverageeligibilityresponse-ex-auth-support.html
Financial Management Work Group | Maturity Level: 1 | Draft | Use Context: Any

This is a code system defined by the FHIR project.

Summary

Defining URL: | http://terminology.hl7.org/CodeSystem/coverageeligibilityresponse-ex-auth-support
Version: | 4.0.1
Name: | CoverageEligibilityResponseAuthSupportCodes
Title: | CoverageEligibilityResponse Auth Support Codes
Definition: | This value set includes CoverageEligibilityResponse Auth Support codes.
Committee: | Financial Management Work Group
OID: | 2.16.840.1.113883.4.642.4.1394 (for OID based terminology systems)
Copyright: | HL7 Inc.
Source Resource | XML / JSON

This Code system is used in the following value sets:

• ValueSet: CoverageEligibilityResponse Auth Support Codes (This value set includes CoverageEligibilityResponse Auth Support codes.)

• ValueSet: CoverageEligibilityResponse Auth Support Codes (This value set includes CoverageEligibilityResponse Auth Support codes.)

4.3.14.409.1 Content

4.3.14.409.2 CoverageEligibilityResponse Auth Support Codes

This value set includes CoverageEligibilityResponse Auth Support codes.

Copyright Statement:

HL7 Inc.

This code system http://terminology.hl7.org/CodeSystem/coverageeligibilityresponse-ex-auth-support defines the following codes:

Code | Display | Definition
laborder | Lab Order | A request or authorization for laboratory diagnostic tests.
labreport | Lab Report | A report on laboratory diagnostic test(s).
diagnosticimageorder | Diagnostic Image Order | A request or authorization for diagnostic imaging.
diagnosticimagereport | Diagnostic Image Report | A report on diagnostic image(s).
professionalreport | Professional Report | A report from a licensed professional regarding the siutation, condition or proposed treatment.
accidentreport | Accident Report | A formal accident report as would be filed with police or a simlar official body.
model | Model | A physical model of the affected area.
picture | Picture | A photograph of the affected area.

See the full registry of code systems defined as part of FHIR.

Explanation of the columns that may appear on this page:

Level | A few code lists that FHIR defines are hierarchical - each code is assigned a level. See Code System for further information.
Source | The source of the definition of the code (when the value set draws in codes defined elsewhere)
Code | The code (used as the code in the resource instance). If the code is in italics, this indicates that the code is not selectable ('Abstract')
Display | The display (used in the display element of a Coding). If there is no display, implementers should not simply display the code, but map the concept into their application
Definition | An explanation of the meaning of the concept
Comments | Additional notes about how to use the code

4.3.14.410 Code System http://hl7.org/fhir/ex-serviceproduct

URL: https://hl7.org/fhir/R4/codesystem-service-product.html
Vocabulary Work Group | Maturity Level: 0 | Informative | Use Context: Any

This is a code system defined by the FHIR project.

Summary

Defining URL: | http://hl7.org/fhir/ex-serviceproduct
Version: | 4.0.1
Name: | ExampleService/ProductCodes
Title: | Example Service/Product Codes
Definition: | This value set includes a smattering of Service/Product codes.
Committee: | ??
OID: | 2.16.840.1.113883.4.642.4.561 (for OID based terminology systems)
Copyright: | This is an example set.
Source Resource | XML / JSON

This Code system is used in the following value sets:

• ValueSet: Example Service/Product Codes (This value set includes a smattering of Service/Product codes.)

• ValueSet: Example Service/Product Codes (This value set includes a smattering of Service/Product codes.)

4.3.14.410.1 Content

4.3.14.410.2 Example Service/Product Codes

This value set includes a smattering of Service/Product codes.

Copyright Statement:

This is an example set.

This code system http://hl7.org/fhir/ex-serviceproduct defines the following codes:

Code | Display | Definition
exam | Exam | Exam
flushot | Flu shot | Flu shot

See the full registry of code systems defined as part of FHIR.

Explanation of the columns that may appear on this page:

Level | A few code lists that FHIR defines are hierarchical - each code is assigned a level. See Code System for further information.
Source | The source of the definition of the code (when the value set draws in codes defined elsewhere)
Code | The code (used as the code in the resource instance). If the code is in italics, this indicates that the code is not selectable ('Abstract')
Display | The display (used in the display element of a Coding). If there is no display, implementers should not simply display the code, but map the concept into their application
Definition | An explanation of the meaning of the concept
Comments | Additional notes about how to use the code

4.3.14.411 Code System http://hl7.org/fhir/name-use

URL: https://hl7.org/fhir/R4/codesystem-name-use.html
FHIR Infrastructure Work Group | Maturity Level: N | Normative (from v4.0.0) | Use Context: Any

This is a code system defined by the FHIR project.

Summary

Defining URL: | http://hl7.org/fhir/name-use
Version: | 4.0.1
Name: | NameUse
Title: | NameUse
Definition: | The use of a human name.
Committee: | FHIR Infrastructure Work Group
OID: | 2.16.840.1.113883.4.642.4.66 (for OID based terminology systems)
Source Resource | XML / JSON

This Code system is used in the following value sets:

• ValueSet: NameUse (The use of a human name.)

• ValueSet: NameUse (The use of a human name.)

4.3.14.411.1 Content

4.3.14.411.2 NameUse

The use of a human name.

This code system http://hl7.org/fhir/name-use defines the following codes:

Lvl | Code | Display | Definition
1 | usual | Usual | Known as/conventional/the one you normally use.
1 | official | Official | The formal name as registered in an official (government) registry, but which name might not be commonly used. May be called "legal name".
1 | temp | Temp | A temporary name. Name.period can provide more detailed information. This may also be used for temporary names assigned at birth or in emergency situations.
1 | nickname | Nickname | A name that is used to address the person in an informal manner, but is not part of their formal or usual name.
1 | anonymous | Anonymous | Anonymous assigned name, alias, or pseudonym (used to protect a person's identity for privacy reasons).
1 | old | Old | This name is no longer in use (or was never correct, but retained for records).
2 | maiden | Name changed for Marriage | A name used prior to changing name because of marriage. This name use is for use by applications that collect and store names that were used prior to a marriage. Marriage naming customs vary greatly around the world, and are constantly changing. This term is not gender specific. The use of this term does not imply any particular history for a person's name.

See the full registry of code systems defined as part of FHIR.

Explanation of the columns that may appear on this page:

Level | A few code lists that FHIR defines are hierarchical - each code is assigned a level. See Code System for further information.
Source | The source of the definition of the code (when the value set draws in codes defined elsewhere)
Code | The code (used as the code in the resource instance). If the code is in italics, this indicates that the code is not selectable ('Abstract')
Display | The display (used in the display element of a Coding). If there is no display, implementers should not simply display the code, but map the concept into their application
Definition | An explanation of the meaning of the concept
Comments | Additional notes about how to use the code

4.3.14.412 Code System http://hl7.org/fhir/substance-status

URL: https://hl7.org/fhir/R4/codesystem-substance-status.html
Orders and Observations Work Group | Maturity Level: 2 | Trial Use | Use Context: Any

This is a code system defined by the FHIR project.

Summary

Defining URL: | http://hl7.org/fhir/substance-status
Version: | 4.0.1
Name: | FHIRSubstanceStatus
Title: | FHIRSubstanceStatus
Definition: | A code to indicate if the substance is actively used.
Committee: | Orders and Observations Work Group
OID: | 2.16.840.1.113883.4.642.4.475 (for OID based terminology systems)
Source Resource | XML / JSON

This Code system is used in the following value sets:

• ValueSet: FHIRSubstanceStatus (A code to indicate if the substance is actively used.)

• ValueSet: FHIRSubstanceStatus (A code to indicate if the substance is actively used.)

4.3.14.412.1 Content

4.3.14.412.2 FHIRSubstanceStatus

A code to indicate if the substance is actively used.

This code system http://hl7.org/fhir/substance-status defines the following codes:

Code | Display | Definition
active | Active | The substance is considered for use or reference.
inactive | Inactive | The substance is considered for reference, but not for use.
entered-in-error | Entered in Error | The substance was entered in error.

See the full registry of code systems defined as part of FHIR.

Explanation of the columns that may appear on this page:

Level | A few code lists that FHIR defines are hierarchical - each code is assigned a level. See Code System for further information.
Source | The source of the definition of the code (when the value set draws in codes defined elsewhere)
Code | The code (used as the code in the resource instance). If the code is in italics, this indicates that the code is not selectable ('Abstract')
Display | The display (used in the display element of a Coding). If there is no display, implementers should not simply display the code, but map the concept into their application
Definition | An explanation of the meaning of the concept
Comments | Additional notes about how to use the code

4.3.14.413 Code System http://hl7.org/fhir/codesystem-hierarchy-meaning

URL: https://hl7.org/fhir/R4/codesystem-codesystem-hierarchy-meaning.html
Vocabulary Work Group | Maturity Level: N | Normative (from v4.0.0) | Use Context: Any

| This page has been approved as part of an ANSI standard. See the Conformance Package for further details.

This is a code system defined by the FHIR project.

Summary

Defining URL: | http://hl7.org/fhir/codesystem-hierarchy-meaning
Version: | 4.0.1
Name: | CodeSystemHierarchyMeaning
Title: | CodeSystemHierarchyMeaning
Definition: | The meaning of the hierarchy of concepts in a code system.
Committee: | Vocabulary Work Group
OID: | 2.16.840.1.113883.4.642.4.785 (for OID based terminology systems)
Source Resource | XML / JSON

This Code system is used in the following value sets:

• ValueSet: CodeSystemHierarchyMeaning (The meaning of the hierarchy of concepts in a code system.)

• ValueSet: CodeSystemHierarchyMeaning (The meaning of the hierarchy of concepts in a code system.)

4.3.14.413.1 Content

4.3.14.413.2 CodeSystemHierarchyMeaning

The meaning of the hierarchy of concepts in a code system.

This code system http://hl7.org/fhir/codesystem-hierarchy-meaning defines the following codes:

Code | Display | Definition
grouped-by | Grouped By | No particular relationship between the concepts can be assumed, except what can be determined by inspection of the definitions of the elements (possible reasons to use this: importing from a source where this is not defined, or where various parts of the hierarchy have different meanings).
is-a | Is-A | A hierarchy where the child concepts have an IS-A relationship with the parents - that is, all the properties of the parent are also true for its child concepts. Not that is-a is a property of the concepts, so additional subsumption relationships may be defined using properties or the [subsumes](extension-codesystem-subsumes.html) extension.

part-of | Part Of | Child elements list the individual parts of a composite whole (e.g. body site).
classified-with | Classified With | Child concepts in the hierarchy may have only one parent, and there is a presumption that the code system is a "closed world" meaning all things must be in the hierarchy. This results in concepts such as "not otherwise classified.".

See the full registry of code systems defined as part of FHIR.

Explanation of the columns that may appear on this page:

Level | A few code lists that FHIR defines are hierarchical - each code is assigned a level. See Code System for further information.
Source | The source of the definition of the code (when the value set draws in codes defined elsewhere)
Code | The code (used as the code in the resource instance). If the code is in italics, this indicates that the code is not selectable ('Abstract')
Display | The display (used in the display element of a Coding). If there is no display, implementers should not simply display the code, but map the concept into their application
Definition | An explanation of the meaning of the concept
Comments | Additional notes about how to use the code

4.3.14.414 Code System http://hl7.org/fhir/encounter-status

URL: https://hl7.org/fhir/R4/codesystem-encounter-status.html
Patient Administration Work Group | Maturity Level: 2 | Trial Use | Use Context: Any

This is a code system defined by the FHIR project.

Summary

Defining URL: | http://hl7.org/fhir/encounter-status
Version: | 4.0.1
Name: | EncounterStatus
Title: | EncounterStatus
Definition: | Current state of the encounter.
Committee: | Patient Administration Work Group
OID: | 2.16.840.1.113883.4.642.4.247 (for OID based terminology systems)
Source Resource | XML / JSON

This Code system is used in the following value sets:

• ValueSet: EncounterStatus (Current state of the encounter.)

• ValueSet: EncounterStatus (Current state of the encounter.)

4.3.14.414.1 Content

4.3.14.414.2 EncounterStatus

Current state of the encounter.

This code system http://hl7.org/fhir/encounter-status defines the following codes:

Code | Display | Definition
planned | Planned | The Encounter has not yet started.
arrived | Arrived | The Patient is present for the encounter, however is not currently meeting with a practitioner.
triaged | Triaged | The patient has been assessed for the priority of their treatment based on the severity of their condition.
in-progress | In Progress | The Encounter has begun and the patient is present / the practitioner and the patient are meeting.
onleave | On Leave | The Encounter has begun, but the patient is temporarily on leave.
finished | Finished | The Encounter has ended.
cancelled | Cancelled | The Encounter has ended before it has begun.
entered-in-error | Entered in Error | This instance should not have been part of this patient's medical record.
unknown | Unknown | The encounter status is unknown. Note that "unknown" is a value of last resort and every attempt should be made to provide a meaningful value other than "unknown".

See the full registry of code systems defined as part of FHIR.

Explanation of the columns that may appear on this page:

Level | A few code lists that FHIR defines are hierarchical - each code is assigned a level. See Code System for further information.
Source | The source of the definition of the code (when the value set draws in codes defined elsewhere)
Code | The code (used as the code in the resource instance). If the code is in italics, this indicates that the code is not selectable ('Abstract')
Display | The display (used in the display element of a Coding). If there is no display, implementers should not simply display the code, but map the concept into their application
Definition | An explanation of the meaning of the concept
Comments | Additional notes about how to use the code

4.3.14.415 Code System http://terminology.hl7.org/CodeSystem/dose-rate-type

URL: https://hl7.org/fhir/R4/codesystem-dose-rate-type.html
FHIR Infrastructure Work Group | Maturity Level: 1 | Draft | Use Context: Any

This is a code system defined by the FHIR project.

Summary

Defining URL: | http://terminology.hl7.org/CodeSystem/dose-rate-type
Version: | 4.0.1
Name: | DoseAndRateType
Title: | DoseAndRateType
Definition: | The kind of dose or rate specified.
Committee: | FHIR Infrastructure Work Group
OID: | 2.16.840.1.113883.4.642.4.1069 (for OID based terminology systems)
Source Resource | XML / JSON

This Code system is used in the following value sets:

• ValueSet: DoseAndRateType (The kind of dose or rate specified.)

• ValueSet: DoseAndRateType (The kind of dose or rate specified.)

4.3.14.415.1 Content

4.3.14.415.2 DoseAndRateType

The kind of dose or rate specified.

This code system http://terminology.hl7.org/CodeSystem/dose-rate-type defines the following codes:

Code | Display | Definition
calculated | Calculated | The dose specified is calculated by the prescriber or the system.
ordered | Ordered | The dose specified is as ordered by the prescriber.

See the full registry of code systems defined as part of FHIR.

Explanation of the columns that may appear on this page:

Level | A few code lists that FHIR defines are hierarchical - each code is assigned a level. See Code System for further information.
Source | The source of the definition of the code (when the value set draws in codes defined elsewhere)
Code | The code (used as the code in the resource instance). If the code is in italics, this indicates that the code is not selectable ('Abstract')
Display | The display (used in the display element of a Coding). If there is no display, implementers should not simply display the code, but map the concept into their application
Definition | An explanation of the meaning of the concept
Comments | Additional notes about how to use the code

4.3.14.416 Code System http://hl7.org/fhir/filter-operator

URL: https://hl7.org/fhir/R4/codesystem-filter-operator.html
Vocabulary Work Group | Maturity Level: N | Normative (from v4.0.0) | Use Context: Any

| This page has been approved as part of an ANSI standard. See the Conformance Package for further details.

This is a code system defined by the FHIR project.

Summary

Defining URL: | http://hl7.org/fhir/filter-operator
Version: | 4.0.1
Name: | FilterOperator
Title: | FilterOperator
Definition: | The kind of operation to perform as a part of a property based filter.
Committee: | Vocabulary Work Group
OID: | 2.16.840.1.113883.4.642.4.479 (for OID based terminology systems)
Source Resource | XML / JSON

This Code system is used in the following value sets:

• ValueSet: FilterOperator (The kind of operation to perform as a part of a property based filter.)

• ValueSet: FilterOperator (The kind of operation to perform as a part of a property based filter.)

4.3.14.416.1 Content

4.3.14.416.2 FilterOperator

The kind of operation to perform as a part of a property based filter.

This code system http://hl7.org/fhir/filter-operator defines the following codes:

Code | Display | Definition | Comments
= | Equals | The specified property of the code equals the provided value.
is-a | Is A (by subsumption) | Includes all concept ids that have a transitive is-a relationship with the concept Id provided as the value, including the provided concept itself (include descendant codes and self). | The definition of is-a is that all the properties of the value are true for the specified property of the code, which means that a code has an is-a relationship with itself. To exclude the root code, use descendent-of

descendent-of | Descendent Of (by subsumption) | Includes all concept ids that have a transitive is-a relationship with the concept Id provided as the value, excluding the provided concept itself i.e. include descendant codes only). | The definition of is-a is that all the properties of the value are true for the specified property of the code. Spelling note: "descendant" is a more correct spelling, but the spelling "descendent" is maintained in the code for backwards compatibility reasons
is-not-a | Not (Is A) (by subsumption) | The specified property of the code does not have an is-a relationship with the provided value.
regex | Regular Expression | The specified property of the code matches the regex specified in the provided value.
in | In Set | The specified property of the code is in the set of codes or concepts specified in the provided value (comma separated list).
not-in | Not in Set | The specified property of the code is not in the set of codes or concepts specified in the provided value (comma separated list).
generalizes | Generalizes (by Subsumption) | Includes all concept ids that have a transitive is-a relationship from the concept Id provided as the value, including the provided concept itself (i.e. include ancestor codes and self). | The definition of is-a is that all the properties of the value are true for the specified property of the code, which means that a code has an is-a relationship with itself. To exclude the root code, add it explicitly to as an exclude
exists | Exists | The specified property of the code has at least one value (if the specified value is true; if the specified value is false, then matches when the specified property of the code has no values).

See the full registry of code systems defined as part of FHIR.

Explanation of the columns that may appear on this page:

Level | A few code lists that FHIR defines are hierarchical - each code is assigned a level. See Code System for further information.
Source | The source of the definition of the code (when the value set draws in codes defined elsewhere)
Code | The code (used as the code in the resource instance). If the code is in italics, this indicates that the code is not selectable ('Abstract')
Display | The display (used in the display element of a Coding). If there is no display, implementers should not simply display the code, but map the concept into their application
Definition | An explanation of the meaning of the concept
Comments | Additional notes about how to use the code

4.3.14.417 Code System http://hl7.org/fhir/practitioner-specialty

URL: https://hl7.org/fhir/R4/codesystem-practitioner-specialty.html
Vocabulary Work Group | Maturity Level: 0 | Informative | Use Context: Any

This is a code system defined by the FHIR project.

Summary

Defining URL: | http://hl7.org/fhir/practitioner-specialty
Version: | 4.0.1
Name: | PractitionerSpecialty
Title: | Practitioner specialty
Definition: | This example value set defines a set of codes that can be used to indicate the specialty of a Practitioner.
Committee: | ??
OID: | 2.16.840.1.113883.4.642.4.442 (for OID based terminology systems)
Source Resource | XML / JSON

This Code system is used in the following value sets:

• ValueSet: Practitioner specialty (This example value set defines a set of codes that can be used to indicate the specialty of a Practitioner.)

• ValueSet: Practitioner specialty (This example value set defines a set of codes that can be used to indicate the specialty of a Practitioner.)

4.3.14.417.1 Content

4.3.14.417.2 Practitioner specialty

This example value set defines a set of codes that can be used to indicate the specialty of a Practitioner.

This code system http://hl7.org/fhir/practitioner-specialty defines the following codes:

Code | Display | Definition
cardio | Cardiologist
dent | Dentist
dietary | Dietary consultant
midw | Midwife
sysarch | Systems architect

See the full registry of code systems defined as part of FHIR.

Explanation of the columns that may appear on this page:

Level | A few code lists that FHIR defines are hierarchical - each code is assigned a level. See Code System for further information.
Source | The source of the definition of the code (when the value set draws in codes defined elsewhere)
Code | The code (used as the code in the resource instance). If the code is in italics, this indicates that the code is not selectable ('Abstract')

Display | The display (used in the display element of a Coding). If there is no display, implementers should not simply display the code, but map the concept into their application
Definition | An explanation of the meaning of the concept
Comments | Additional notes about how to use the code

4.3.14.418 Code System http://hl7.org/fhir/days-of-week

URL: https://hl7.org/fhir/R4/codesystem-days-of-week.html
Patient Administration Work Group | Maturity Level: N | Normative (from v4.0.0) | Use Context: Any

This is a code system defined by the FHIR project.

Summary

Defining URL: | http://hl7.org/fhir/days-of-week
Version: | 4.0.1
Name: | DaysOfWeek
Title: | DaysOfWeek
Definition: | The days of the week.
Committee: | Patient Administration Work Group
OID: | 2.16.840.1.113883.4.642.4.513 (for OID based terminology systems)
Source Resource | XML / JSON

This Code system is used in the following value sets:

• ValueSet: DaysOfWeek (The days of the week.)

• ValueSet: DaysOfWeek (The days of the week.)

4.3.14.418.1 Content

4.3.14.418.2 DaysOfWeek

The days of the week.

This code system http://hl7.org/fhir/days-of-week defines the following codes:

Code | Display | Definition
mon | Monday | Monday.
tue | Tuesday | Tuesday.
wed | Wednesday | Wednesday.
thu | Thursday | Thursday.
fri | Friday | Friday.
sat | Saturday | Saturday.
sun | Sunday | Sunday.

See the full registry of code systems defined as part of FHIR.

Explanation of the columns that may appear on this page:

Level | A few code lists that FHIR defines are hierarchical - each code is assigned a level. See Code System for further information.
Source | The source of the definition of the code (when the value set draws in codes defined elsewhere)
Code | The code (used as the code in the resource instance). If the code is in italics, this indicates that the code is not selectable ('Abstract')
Display | The display (used in the display element of a Coding). If there is no display, implementers should not simply display the code, but map the concept into their application
Definition | An explanation of the meaning of the concept
Comments | Additional notes about how to use the code

4.3.14.419 Code System http://hl7.org/fhir/claim-use

URL: https://hl7.org/fhir/R4/codesystem-claim-use.html
Financial Management Work Group | Maturity Level: 2 | Trial Use | Use Context: Any

This is a code system defined by the FHIR project.

Summary

Defining URL: | http://hl7.org/fhir/claim-use
Version: | 4.0.1
Name: | Use
Title: | Use
Definition: | The purpose of the Claim: predetermination, preauthorization, claim.
Committee: | Financial Management Work Group
OID: | 2.16.840.1.113883.4.642.4.545 (for OID based terminology systems)
Source Resource | XML / JSON

This Code system is used in the following value sets:

• ValueSet: Use (The purpose of the Claim: predetermination, preauthorization, claim.)

• ValueSet: Use (The purpose of the Claim: predetermination, preauthorization, claim.)

4.3.14.419.1 Content

4.3.14.419.2 Use

The purpose of the Claim: predetermination, preauthorization, claim.

This code system http://hl7.org/fhir/claim-use defines the following codes:

Code | Display | Definition
claim | Claim | The treatment is complete and this represents a Claim for the services.
preauthorization | Preauthorization | The treatment is proposed and this represents a Pre-authorization for the services.
predetermination | Predetermination | The treatment is proposed and this represents a Pre-determination for the services.

See the full registry of code systems defined as part of FHIR.

Explanation of the columns that may appear on this page:

Level | A few code lists that FHIR defines are hierarchical - each code is assigned a level. See Code System for further information.
Source | The source of the definition of the code (when the value set draws in codes defined elsewhere)
Code | The code (used as the code in the resource instance). If the code is in italics, this indicates that the code is not selectable ('Abstract')
Display | The display (used in the display element of a Coding). If there is no display, implementers should not simply display the code, but map the concept into their application
Definition | An explanation of the meaning of the concept
Comments | Additional notes about how to use the code

4.3.14.420 Code System http://hl7.org/fhir/explanationofbenefit-status

URL: https://hl7.org/fhir/R4/codesystem-explanationofbenefit-status.html
Financial Management Work Group | Maturity Level: 2 | Trial Use | Use Context: Any

This is a code system defined by the FHIR project.

Summary

Defining URL: | http://hl7.org/fhir/explanationofbenefit-status
Version: | 4.0.1
Name: | ExplanationOfBenefitStatus
Title: | ExplanationOfBenefitStatus
Definition: | A code specifying the state of the resource instance.
Committee: | Financial Management Work Group
OID: | 2.16.840.1.113883.4.642.4.619 (for OID based terminology systems)
Source Resource | XML / JSON

This Code system is used in the following value sets:

• ValueSet: ExplanationOfBenefitStatus (A code specifying the state of the resource instance.)

• ValueSet: ExplanationOfBenefitStatus (A code specifying the state of the resource instance.)

4.3.14.420.1 Content

4.3.14.420.2 ExplanationOfBenefitStatus

A code specifying the state of the resource instance.

This code system http://hl7.org/fhir/explanationofbenefit-status defines the following codes:

Code | Display | Definition
active | Active | The resource instance is currently in-force.
cancelled | Cancelled | The resource instance is withdrawn, rescinded or reversed.
draft | Draft | A new resource instance the contents of which is not complete.
entered-in-error | Entered In Error | The resource instance was entered in error.

See the full registry of code systems defined as part of FHIR.

Explanation of the columns that may appear on this page:

Level | A few code lists that FHIR defines are hierarchical - each code is assigned a level. See Code System for further information.
Source | The source of the definition of the code (when the value set draws in codes defined elsewhere)
Code | The code (used as the code in the resource instance). If the code is in italics, this indicates that the code is not selectable ('Abstract')
Display | The display (used in the display element of a Coding). If there is no display, implementers should not simply display the code, but map the concept into their application
Definition | An explanation of the meaning of the concept
Comments | Additional notes about how to use the code

4.3.14.421 Code System http://hl7.org/fhir/fm-conditions

URL: https://hl7.org/fhir/R4/codesystem-fm-conditions.html
Vocabulary Work Group | Maturity Level: 0 | Informative | Use Context: Any

This is a code system defined by the FHIR project.

Summary

Defining URL: | http://hl7.org/fhir/fm-conditions
Version: | 4.0.1
Name: | FMConditionCodes
Title: | FM Condition Codes
Definition: | This value set includes sample Conditions codes.
Committee: | ??
OID: | 2.16.840.1.113883.4.642.4.557 (for OID based terminology systems)
Copyright: | This is an example set.
Source Resource | XML / JSON

This Code system is used in the following value sets:

• ValueSet: FM Condition Codes (This value set includes sample Conditions codes.)

• ValueSet: FM Condition Codes (This value set includes sample Conditions codes.)

4.3.14.421.1 Content

4.3.14.421.2 FM Condition Codes

This value set includes sample Conditions codes.

Copyright Statement:

This is an example set.

This code system http://hl7.org/fhir/fm-conditions defines the following codes:

Code | Display | Definition
123987 | Headache | Headache

See the full registry of code systems defined as part of FHIR.

Explanation of the columns that may appear on this page:

Level | A few code lists that FHIR defines are hierarchical - each code is assigned a level. See Code System for further information.
Source | The source of the definition of the code (when the value set draws in codes defined elsewhere)
Code | The code (used as the code in the resource instance). If the code is in italics, this indicates that the code is not selectable ('Abstract')
Display | The display (used in the display element of a Coding). If there is no display, implementers should not simply display the code, but map the concept into their application
Definition | An explanation of the meaning of the concept
Comments | Additional notes about how to use the code

4.3.14.422 Code System http://terminology.hl7.org/CodeSystem/claim-type

URL: https://hl7.org/fhir/R4/codesystem-claim-type.html
Financial Management Work Group | Maturity Level: 2 | Trial Use | Use Context: Any

This is a code system defined by the FHIR project.

Summary

Defining URL: | http://terminology.hl7.org/CodeSystem/claim-type
Version: | 4.0.1
Name: | ClaimTypeCodes
Title: | Claim Type Codes
Definition: | This value set includes Claim Type codes.
Committee: | Financial Management Work Group
OID: | 2.16.840.1.113883.4.642.4.1156 (for OID based terminology systems)
Copyright: | HL7 Inc.
Source Resource | XML / JSON

This Code system is used in the following value sets:

• ValueSet: Claim Type Codes (This value set includes Claim Type codes.)

• ValueSet: Claim Type Codes (This value set includes Claim Type codes.)

4.3.14.422.1 Content

4.3.14.422.2 Claim Type Codes

This value set includes Claim Type codes.

Copyright Statement:

HL7 Inc.

This code system http://terminology.hl7.org/CodeSystem/claim-type defines the following codes:

Code | Display | Definition
institutional | Institutional | Hospital, clinic and typically inpatient claims.
oral | Oral | Dental, Denture and Hygiene claims.
pharmacy | Pharmacy | Pharmacy claims for goods and services.
professional | Professional | Typically, outpatient claims from Physician, Psychological, Chiropractor, Physiotherapy, Speech Pathology, rehabilitative, consulting.
vision | Vision | Vision claims for professional services and products such as glasses and contact lenses.

See the full registry of code systems defined as part of FHIR.

Explanation of the columns that may appear on this page:

Level | A few code lists that FHIR defines are hierarchical - each code is assigned a level. See Code System for further information.
Source | The source of the definition of the code (when the value set draws in codes defined elsewhere)
Code | The code (used as the code in the resource instance). If the code is in italics, this indicates that the code is not selectable ('Abstract')
Display | The display (used in the display element of a Coding). If there is no display, implementers should not simply display the code, but map the concept into their application
Definition | An explanation of the meaning of the concept
Comments | Additional notes about how to use the code

4.3.14.423 Code System http://terminology.hl7.org/CodeSystem/encounter-special-arrangements

URL: https://hl7.org/fhir/R4/codesystem-encounter-special-arrangements.html
Patient Administration Work Group | Maturity Level: 0 | Informative | Use Context: Any

This is a code system defined by the FHIR project.

Summary

Defining URL: | http://terminology.hl7.org/CodeSystem/encounter-special-arrangements
Version: | 4.0.1
Name: | SpecialArrangements
Title: | Special arrangements
Definition: | This value set defines a set of codes that can be used to indicate the kinds of special arrangements in place for a patients visit.
Committee: | Patient Administration Work Group
OID: | 2.16.840.1.113883.4.642.4.1090 (for OID based terminology systems)
Source Resource | XML / JSON

This Code system is used in the following value sets:

• ValueSet: Special arrangements (This value set defines a set of codes that can be used to indicate the kinds of special arrangements in place for a patients visit.)

• ValueSet: Special arrangements (This value set defines a set of codes that can be used to indicate the kinds of special arrangements in place for a patients visit.)

4.3.14.423.1 Content

4.3.14.423.2 Special arrangements

This value set defines a set of codes that can be used to indicate the kinds of special arrangements in place for a patients visit.

This code system http://terminology.hl7.org/CodeSystem/encounter-special-arrangements defines the following codes:

Code | Display | Definition
wheel | Wheelchair | The patient requires a wheelchair to be made available for the encounter.
add-bed | Additional bedding | An additional bed made available for a person accompanying the patient, for example a parent accompanying a child.
int | Interpreter | The patient is not fluent in the local language and requires an interpreter to be available. Refer to the Patient.Language property for the type of interpreter required.
att | Attendant | A person who accompanies a patient to provide assistive services necessary for the patient's care during the encounter.
dog | Guide dog | The patient has a guide dog and the location used for the encounter should be able to support the presence of the service animal.

See the full registry of code systems defined as part of FHIR.

Explanation of the columns that may appear on this page:

Level | A few code lists that FHIR defines are hierarchical - each code is assigned a level. See Code System for further information.
Source | The source of the definition of the code (when the value set draws in codes defined elsewhere)
Code | The code (used as the code in the resource instance). If the code is in italics, this indicates that the code is not selectable ('Abstract')
Display | The display (used in the display element of a Coding). If there is no display, implementers should not simply display the code, but map the concept into their application
Definition | An explanation of the meaning of the concept

Comments | Additional notes about how to use the code

4.3.14.424 Code System http://hl7.org/fhir/narrative-status

URL: https://hl7.org/fhir/R4/codesystem-narrative-status.html
Vocabulary Work Group | Maturity Level: 0 | Informative | Use Context: Any

This is a code system defined by the FHIR project.

Summary

Defining URL: | http://hl7.org/fhir/narrative-status
Version: | 4.0.1
Name: | NarrativeStatus
Title: | NarrativeStatus
Definition: | The status of a resource narrative.
Committee: | ??
OID: | 2.16.840.1.113883.4.642.4.56 (for OID based terminology systems)
Source Resource | XML / JSON

This Code system is used in the following value sets:

• ValueSet: NarrativeStatus (The status of a resource narrative.)

• ValueSet: NarrativeStatus (The status of a resource narrative.)

4.3.14.424.1 Content

4.3.14.424.2 NarrativeStatus

The status of a resource narrative.

This code system http://hl7.org/fhir/narrative-status defines the following codes:

Code | Display | Definition
generated | Generated | The contents of the narrative are entirely generated from the core elements in the content.
extensions | Extensions | The contents of the narrative are entirely generated from the core elements in the content and some of the content is generated from extensions. The narrative SHALL reflect the impact of all modifier extensions.
additional | Additional | The contents of the narrative may contain additional information not found in the structured data. Note that there is no computable way to determine what the extra information is, other than by human inspection.
empty | Empty | The contents of the narrative are some equivalent of "No human-readable text provided in this case".

See the full registry of code systems defined as part of FHIR.

Explanation of the columns that may appear on this page:

Level | A few code lists that FHIR defines are hierarchical - each code is assigned a level. See Code System for further information.
Source | The source of the definition of the code (when the value set draws in codes defined elsewhere)
Code | The code (used as the code in the resource instance). If the code is in italics, this indicates that the code is not selectable ('Abstract')
Display | The display (used in the display element of a Coding). If there is no display, implementers should not simply display the code, but map the concept into their application
Definition | An explanation of the meaning of the concept
Comments | Additional notes about how to use the code

4.3.14.425 Code System http://terminology.hl7.org/CodeSystem/encounter-type

URL: https://hl7.org/fhir/R4/codesystem-encounter-type.html
Patient Administration Work Group | Maturity Level: 1 | Draft | Use Context: Any

This is a code system defined by the FHIR project.

Summary

Defining URL: | http://terminology.hl7.org/CodeSystem/encounter-type
Version: | 4.0.1
Name: | EncounterType
Title: | Encounter type
Definition: | This example value set defines a set of codes that can be used to indicate the type of encounter: a specific code indicating type of service provided.
Committee: | Patient Administration Work Group
OID: | 2.16.840.1.113883.4.642.4.1088 (for OID based terminology systems)
Source Resource | XML / JSON

This Code system is used in the following value sets:

• ValueSet: Encounter type (This example value set defines a set of codes that can be used to indicate the type of encounter: a specific code indicating type of service provided.)

• ValueSet: Encounter type (This example value set defines a set of codes that can be used to indicate the type of encounter: a specific code indicating type of service provided.)

4.3.14.425.1 Content

4.3.14.425.2 Encounter type

This example value set defines a set of codes that can be used to indicate the type of encounter: a specific code indicating type of service provided.

This code system http://terminology.hl7.org/CodeSystem/encounter-type defines the following codes:

Code | Display | Definition
ADMS | Annual diabetes mellitus screening
BD/BM-clin | Bone drilling/bone marrow punction in clinic
CCS60 | Infant colon screening - 60 minutes
OKI | Outpatient Kenacort injection

See the full registry of code systems defined as part of FHIR.

Explanation of the columns that may appear on this page:

Level | A few code lists that FHIR defines are hierarchical - each code is assigned a level. See Code System for further information.
Source | The source of the definition of the code (when the value set draws in codes defined elsewhere)
Code | The code (used as the code in the resource instance). If the code is in italics, this indicates that the code is not selectable ('Abstract')
Display | The display (used in the display element of a Coding). If there is no display, implementers should not simply display the code, but map the concept into their application
Definition | An explanation of the meaning of the concept
Comments | Additional notes about how to use the code

4.3.14.426 Code System http://terminology.hl7.org/CodeSystem/subscriber-relationship

URL: https://hl7.org/fhir/R4/codesystem-subscriber-relationship.html
Financial Management Work Group | Maturity Level: 2 | Trial Use | Use Context: Any

This is a code system defined by the FHIR project.

Summary

Defining URL: | http://terminology.hl7.org/CodeSystem/subscriber-relationship
Version: | 4.0.1
Name: | SubscriberRelationshipCodes
Title: | SubscriberPolicyholder Relationship Codes
Definition: | This value set includes codes for the relationship between the Subscriber and the Beneficiary (insured/covered party/patient).
Committee: | Financial Management Work Group
OID: | 2.16.840.1.113883.4.642.4.1386 (for OID based terminology systems)
Copyright: | This is an extensible set.
Source Resource | XML / JSON

This Code system is used in the following value sets:

• ValueSet: SubscriberPolicyholder Relationship Codes (This value set includes codes for the relationship between the Subscriber and the Beneficiary (insured/covered party/patient).)

• ValueSet: SubscriberPolicyholder Relationship Codes (This value set includes codes for the relationship between the Subscriber and the Beneficiary (insured/covered party/patient).)

4.3.14.426.1 Content

4.3.14.426.2 SubscriberPolicyholder Relationship Codes

This value set includes codes for the relationship between the Subscriber and the Beneficiary (insured/covered party/patient).

Copyright Statement:

This is an extensible set.

This code system http://terminology.hl7.org/CodeSystem/subscriber-relationship defines the following codes:

Code | Display | Definition
child | Child | The Beneficiary is a child of the Subscriber
parent | Parent | The Beneficiary is a parent of the Subscriber
spouse | Spouse | The Beneficiary is a spouse or equivalent of the Subscriber
common | Common Law Spouse | The Beneficiary is a common law spouse or equivalent of the Subscriber
other | Other | The Beneficiary has some other relationship the Subscriber
self | Self | The Beneficiary is the Subscriber
injured | Injured Party | The Beneficiary is covered under insurance of the subscriber due to an injury.

See the full registry of code systems defined as part of FHIR.

Explanation of the columns that may appear on this page:

Level | A few code lists that FHIR defines are hierarchical - each code is assigned a level. See Code System for further information.
Source | The source of the definition of the code (when the value set draws in codes defined elsewhere)
Code | The code (used as the code in the resource instance). If the code is in italics, this indicates that the code is not selectable ('Abstract')
Display | The display (used in the display element of a Coding). If there is no display, implementers should not simply display the code, but map the concept into their application
Definition | An explanation of the meaning of the concept
Comments | Additional notes about how to use the code

4.3.14.427 Code System http://terminology.hl7.org/CodeSystem/validation-status

URL: https://hl7.org/fhir/R4/codesystem-verificationresult-validation-status.html
Patient Administration Work Group | Maturity Level: 0 | Informative | Use Context: Any

This is a code system defined by the FHIR project.

Summary

Defining URL: | http://terminology.hl7.org/CodeSystem/validation-status
Version: | 4.0.1
Name: | validation-status
Title: | Validation-status
Definition: | Status of the validation of the target against the primary source
Committee: | Patient Administration Work Group
OID: | 2.16.840.1.113883.4.642.1.895 (for OID based terminology systems)
Source Resource | XML / JSON

This Code system is used in the following value sets:

• ValueSet: Validation-status (Status of the validation of the target against the primary source)
• ValueSet: Validation-status (Status of the validation of the target against the primary source)

4.3.14.427.1 Content

4.3.14.427.2 Validation-status

Status of the validation of the target against the primary source

This code system http://terminology.hl7.org/CodeSystem/validation-status defines the following codes:

Code | Display | Definition
successful | Successful
failed | Failed
unknown | Unknown | The validations status has not been determined yet

See the full registry of code systems defined as part of FHIR.

Explanation of the columns that may appear on this page:

Level | A few code lists that FHIR defines are hierarchical - each code is assigned a level. See Code System for further information.
Source | The source of the definition of the code (when the value set draws in codes defined elsewhere)
Code | The code (used as the code in the resource instance). If the code is in italics, this indicates that the code is not selectable ('Abstract')
Display | The display (used in the display element of a Coding). If there is no display, implementers should not simply display the code, but map the concept into their application
Definition | An explanation of the meaning of the concept
Comments | Additional notes about how to use the code

4.3.14.428 Code System http://hl7.org/fhir/slotstatus

URL: https://hl7.org/fhir/R4/codesystem-slotstatus.html
Patient Administration Work Group | Maturity Level: 3 | Trial Use | Use Context: Any

This is a code system defined by the FHIR project.

Summary

Defining URL: | http://hl7.org/fhir/slotstatus
Version: | 4.0.1
Name: | SlotStatus
Title: | SlotStatus
Definition: | The free/busy status of the slot.
Committee: | Patient Administration Work Group
OID: | 2.16.840.1.113883.4.642.4.483 (for OID based terminology systems)
Source Resource | XML / JSON

This Code system is used in the following value sets:

• ValueSet: SlotStatus (The free/busy status of the slot.)

• ValueSet: SlotStatus (The free/busy status of the slot.)

4.3.14.428.1 Content

4.3.14.428.2 SlotStatus

The free/busy status of the slot.

This code system http://hl7.org/fhir/slotstatus defines the following codes:

Code | Display | Definition
busy | Busy | Indicates that the time interval is busy because one or more events have been scheduled for that interval.
free | Free | Indicates that the time interval is free for scheduling.
busy-unavailable | Busy (Unavailable) | Indicates that the time interval is busy and that the interval cannot be scheduled.
busy-tentative | Busy (Tentative) | Indicates that the time interval is busy because one or more events have been tentatively scheduled for that interval.
entered-in-error | Entered in error | This instance should not have been part of this patient's medical record.

See the full registry of code systems defined as part of FHIR.

Explanation of the columns that may appear on this page:

Level | A few code lists that FHIR defines are hierarchical - each code is assigned a level. See Code System for further information.
Source | The source of the definition of the code (when the value set draws in codes defined elsewhere)
Code | The code (used as the code in the resource instance). If the code is in italics, this indicates that the code is not selectable ('Abstract')
Display | The display (used in the display element of a Coding). If there is no display, implementers should not simply display the code, but map the concept into their application
Definition | An explanation of the meaning of the concept
Comments | Additional notes about how to use the code

4.3.14.429 Code System http://hl7.org/fhir/examplescenario-actor-type

URL: https://hl7.org/fhir/R4/codesystem-examplescenario-actor-type.html
FHIR Infrastructure Work Group | Maturity Level: 0 | Trial Use | Use Context: Any

This is a code system defined by the FHIR project.

Summary

Defining URL: | http://hl7.org/fhir/examplescenario-actor-type
Version: | 4.0.1
Name: | ExampleScenarioActorType
Title: | ExampleScenarioActorType
Definition: | The type of actor - system or human.
Committee: | FHIR Infrastructure Work Group
OID: | 2.16.840.1.113883.4.642.4.859 (for OID based terminology systems)
Source Resource | XML / JSON

This Code system is used in the following value sets:

• ValueSet: ExampleScenarioActorType (The type of actor - system or human.)
• ValueSet: ExampleScenarioActorType (The type of actor - system or human.)

4.3.14.429.1 Content

4.3.14.429.2 ExampleScenarioActorType

The type of actor - system or human.

This code system http://hl7.org/fhir/examplescenario-actor-type defines the following codes:

Code | Display | Definition
person | Person | A person.
entity | System | A system.

See the full registry of code systems defined as part of FHIR.

Explanation of the columns that may appear on this page:

Level | A few code lists that FHIR defines are hierarchical - each code is assigned a level. See Code System for further information.
Source | The source of the definition of the code (when the value set draws in codes defined elsewhere)
Code | The code (used as the code in the resource instance). If the code is in italics, this indicates that the code is not selectable ('Abstract')
Display | The display (used in the display element of a Coding). If there is no display, implementers should not simply display the code, but map the concept into their application
Definition | An explanation of the meaning of the concept
Comments | Additional notes about how to use the code

4.3.14.430 Code System http://hl7.org/fhir/contributor-type

URL: https://hl7.org/fhir/R4/codesystem-contributor-type.html
FHIR Infrastructure Work Group | Maturity Level: 5 | Trial Use | Use Context: Any

This is a code system defined by the FHIR project.

Summary

Defining URL: | http://hl7.org/fhir/contributor-type
Version: | 4.0.1
Name: | ContributorType
Title: | ContributorType
Definition: | The type of contributor.
Committee: | FHIR Infrastructure Work Group
OID: | 2.16.840.1.113883.4.642.4.94 (for OID based terminology systems)
Source Resource | XML / JSON

This Code system is used in the following value sets:

• ValueSet: ContributorType (The type of contributor.)

• ValueSet: ContributorType (The type of contributor.)

4.3.14.430.1 Content

4.3.14.430.2 ContributorType

The type of contributor.

This code system http://hl7.org/fhir/contributor-type defines the following codes:

Code | Display | Definition
author | Author | An author of the content of the module.
editor | Editor | An editor of the content of the module.
reviewer | Reviewer | A reviewer of the content of the module.
endorser | Endorser | An endorser of the content of the module.

See the full registry of code systems defined as part of FHIR.

Explanation of the columns that may appear on this page:

Level | A few code lists that FHIR defines are hierarchical - each code is assigned a level. See Code System for further information.
Source | The source of the definition of the code (when the value set draws in codes defined elsewhere)
Code | The code (used as the code in the resource instance). If the code is in italics, this indicates that the code is not selectable ('Abstract')
Display | The display (used in the display element of a Coding). If there is no display, implementers should not simply display the code, but map the concept into their application
Definition | An explanation of the meaning of the concept
Comments | Additional notes about how to use the code