Epic-FHIR — API category: CMS Incoming (sections 14 – 14.2.2)

Source: Epic on FHIR (fhir.epic.com) documentation, mirrored 2026-11. Text-only edition for AI ingestion (NotebookLM); pages follow the source order (its table of contents when one exists).

14 API category: CMS Incoming

File: site/apis/14-CMS-Incoming/index.html

R4 (91)

API | Method | URL template | Type

$submit-attachment (Prior Auth) (R4) | POST | /api/FHIR/R4/$submit-attachment | Industry-Standard

AllergyIntolerance.Read (Outside Record) (R4) | GET | /api/FHIR/R4/AllergyIntolerance/{ID} | USCDI

AllergyIntolerance.Search (Outside Record) (R4) | GET | /api/FHIR/R4/AllergyIntolerance?clinical-status={clinical-status}&patient={patient}&_count={_count}&_id={_id}&_include={_include}&_revinclude={_revinclude} | USCDI

Appointment.Read (Prior Auth) (R4) | GET | /api/FHIR/R4/Appointment/{ID} | Industry-Standard

Appointment.Search (Prior Auth) (R4) | GET | /api/FHIR/R4/Appointment?date={date}&identifier={identifier}&onlyscannable={onlyscannable}&patient={patient}&service-category={service-category}&status={status}&_count={_count}&_id={_id}&_include={_include}&_revinclude={_revinclude} | Industry-Standard

Binary.Read (Outside Record - Clinical Notes) (R4) (described under Infrastructure Documents & Lists) | GET | /api/FHIR/R4/Binary/{ID} | USCDI

Binary.Read (Prior Auth Supporting Info) (R4) | GET | /api/FHIR/R4/Binary/{ID} | Industry-Standard

Binary.Search (Outside Record - Clinical Notes) (R4) (described under Infrastructure Documents & Lists) | GET | /api/FHIR/R4/Binary?_id={_id} | USCDI

CarePlan.Read (Outside Record) (R4) | GET | /api/FHIR/R4/CarePlan/{ID} | USCDI

CarePlan.Search (Outside Record) (R4) | GET | /api/FHIR/R4/CarePlan?activity-date={activity-date}&category={category}&encounter={encounter}&part-of={part-of}&patient={patient}&status={status}&subject={subject}&_count={_count}&_id={_id}&_include={_include}&_revinclude={_revinclude} | USCDI

CareTeam.Read (Outside Record) (R4) | GET | /api/FHIR/R4/CareTeam/{ID} | USCDI

CareTeam.Search (Outside Record) (R4) | GET | /api/FHIR/R4/CareTeam?patient={patient}&status={status}&subject={subject}&_count={_count}&_id={_id}&_include={_include}&_revinclude={_revinclude} | USCDI

Claim.$inquire (Prior Auth) (R4) | POST | /api/FHIR/R4/Claim/$inquire`Parameters*** | Industry-Standard

Claim.$submit (Prior Auth) (R4) | POST | /api/FHIR/R4/Claim/$submit | Industry-Standard

Condition.Read (Outside Record Encounter Diagnosis) (R4) | GET | /api/FHIR/R4/Condition/{ID} | USCDI

Condition.Read (Outside Record Health Concern) (R4) | GET | /api/FHIR/R4/Condition/{ID} | USCDI

Condition.Read (Outside Record Problems) (R4) | GET | /api/FHIR/R4/Condition/{ID} | USCDI

Condition.Search (Outside Record Encounter Diagnosis) (R4) | GET | /api/FHIR/R4/Condition?abatement-date={abatement-date}&category={category}&clinical-status={clinical-status}&code={code}&encounter={encounter}&onset-date={onset-date}&patient={patient}&recorded-date={recorded-date}&subject={subject}&_count={_count}&_id={_id}&_include={_include}&_revinclude={_revinclude} | USCDI

Condition.Search (Outside Record Health Concern) (R4) | GET | /api/FHIR/R4/Condition?abatement-date={abatement-date}&category={category}&clinical-status={clinical-status}&code={code}&encounter={encounter}&onset-date={onset-date}&patient={patient}&recorded-date={recorded-date}&subject={subject}&_count={_count}&_id={_id}&_include={_include}&_revinclude={_revinclude} | USCDI

Condition.Search (Outside Record Problems) (R4) | GET | /api/FHIR/R4/Condition?abatement-date={abatement-date}&category={category}&clinical-status={clinical-status}&code={code}&encounter={encounter}&onset-date={onset-date}&patient={patient}&recorded-date={recorded-date}&subject={subject}&_count={_count}&_id={_id}&_include={_include}&_revinclude={_revinclude} | USCDI

Coverage Requirements Discovery (R4) | | /api/FHIR | Industry-Standard

Coverage Requirements Discovery Endpoint Discovery (R4) | | | Industry-Standard

Coverage.Read (Outside Record) (R4) | GET | /api/FHIR/R4/Coverage/{ID} | USCDI

Coverage.Search (Outside Record) (R4) | GET | /api/FHIR/R4/Coverage?beneficiary={beneficiary}&patient={patient}&_count={_count}&_id={_id}&_include={_include}&_revinclude={_revinclude} | USCDI

Device.Read (Outside Record) (R4) | GET | /api/FHIR/R4/Device/{ID} | USCDI

Device.Search (Outside Record) (R4) | GET | /api/FHIR/R4/Device?device-name={device-name}&manufacturer={manufacturer}&model={model}&patient={patient}&udi-carrier={udi-carrier}&udi-di={udi-di}&_count={_count}&_id={_id}&_include={_include}&_revinclude={_revinclude} | USCDI

DiagnosticReport.Read (Outside Record Results) (R4) | GET | /api/FHIR/R4/DiagnosticReport/{ID} | USCDI

DiagnosticReport.Search (Outside Record Results) (R4) | GET | /api/FHIR/R4/DiagnosticReport?category={category}&code={code}&date={date}&identifier={identifier}&patient={patient}&subject={subject}&_count={_count}&_id={_id}&_include={_include}&_revinclude={_revinclude} | USCDI

DocumentReference.Read (Outside Record - Clinical Notes) (R4) (described under Infrastructure Documents & Lists) | GET | /api/FHIR/R4/DocumentReference/{ID} | USCDI

DocumentReference.Read (Prior Auth Supporting Info) (R4) | GET | /api/FHIR/R4/DocumentReference/{ID} | Industry-Standard

DocumentReference.Search (Outside Record - Clinical Notes) (R4) (described under Infrastructure Documents & Lists) | GET | /api/FHIR/R4/DocumentReference?author={author}&category={category}&date={date}&docstatus={docstatus}&encounter={encounter}&patient={patient}&period={period}&status={status}&subject={subject}&type={type}&_id={_id}&_include={_include}&_lastupdated={_lastupdated} | USCDI

Encounter.Read (Outside Record) (R4) (described under Workflow Patient Management) | GET | /api/FHIR/R4/Encounter/{ID} | USCDI

Encounter.Search (Outside Record) (R4) (described under Workflow Patient Management) | GET | /api/FHIR/R4/Encounter?class={class}&date={date}&identifier={identifier}&onlyscannable={onlyscannable}&patient={patient}&subject={subject}&_count={_count}&_id={_id} | USCDI

Goal.Read (Outside Record) (R4) | GET | /api/FHIR/R4/Goal/{ID} | USCDI

Goal.Search (Outside Record) (R4) | GET | /api/FHIR/R4/Goal?category={category}&lifecycle-status={lifecycle-status}&patient={patient}&start-date={start-date}&subject={subject}&_count={_count}&_id={_id}&_include={_include}&_revinclude={_revinclude} | USCDI

Group.$bulk-member-match Kickoff | POST | /api/FHIR/R4/Group/$bulk-member-match`Parameters*** | Industry-Standard

Immunization.Read (Outside Record) (R4) | GET | /api/FHIR/R4/Immunization/{ID} | USCDI

Immunization.Search (Outside Record) (R4) | GET | /api/FHIR/R4/Immunization?date={date}&patient={patient}&status={status}&_count={_count}&_id={_id}&_include={_include}&_revinclude={_revinclude} | USCDI

Location.Read (Outside Record) (R4) | GET | /api/FHIR/R4/Location/{ID} | USCDI

Location.Search (Outside Record) (R4) | GET | /api/FHIR/R4/Location?type={type}&_count={_count}&_id={_id}&_include={_include}&_revinclude={_revinclude} | USCDI

Medication.Read (Outside Record) (R4) | GET | /api/FHIR/R4/Medication/{ID} | USCDI

Medication.Search (Outside Record) (R4) | GET | /api/FHIR/R4/Medication?_count={_count}&_id={_id}&_include={_include}&_revinclude={_revinclude} | USCDI

MedicationDispense.Read (Outside Record) (R4) | GET | /api/FHIR/R4/MedicationDispense/{ID} | USCDI

MedicationDispense.Search (Outside Record) (R4) | GET | /api/FHIR/R4/MedicationDispense?category={category}&patient={patient}&subject={subject}&_count={_count}&_id={_id}&_include={_include}&_revinclude={_revinclude} | USCDI

MedicationRequest.Read (Outside Record) (R4) | GET | /api/FHIR/R4/MedicationRequest/{ID} | USCDI

MedicationRequest.Read (Prior Auth) (R4) | GET | /api/FHIR/R4/MedicationRequest/{ID} | Industry-Standard

MedicationRequest.Search (Outside Record) (R4) | GET | /api/FHIR/R4/MedicationRequest?category={category}&date={date}&intent={intent}&patient={patient}&status={status}&subject={subject}&_count={_count}&_id={_id}&_include={_include}&_revinclude={_revinclude} | USCDI

MedicationRequest.Search (Prior Auth) (R4) | GET | /api/FHIR/R4/MedicationRequest?category={category}&date={date}&intent={intent}&patient={patient}&status={status}&subject={subject}&_count={_count}&_id={_id}&_include={_include}&_revinclude={_revinclude} | Industry-Standard

MedicationRequest.Update (Prior Auth) (R4) | | | Industry-Standard

Observation.Read (Outside Record Activities of Daily Living) (R4) | GET | /api/FHIR/R4/Observation/{ID} | USCDI

Observation.Read (Outside Record Occupation) (R4) | GET | /api/FHIR/R4/Observation/{ID} | USCDI

Observation.Read (Outside Record Pregnancy Status) (R4) | GET | /api/FHIR/R4/Observation/{ID} | USCDI

Observation.Read (Outside Record Results) (R4) | GET | /api/FHIR/R4/Observation/{ID} | USCDI

Observation.Read (Outside Record Screening Assessment) (R4) | GET | /api/FHIR/R4/Observation/{ID} | USCDI

Observation.Read (Outside Record SDOH Assessment) (R4) | GET | /api/FHIR/R4/Observation/{ID} | USCDI

Observation.Read (Outside Record Sexual Orientation) (R4) | GET | /api/FHIR/R4/Observation/{ID} | USCDI

Observation.Read (Outside Record Smoking Status) (R4) | GET | /api/FHIR/R4/Observation/{ID} | USCDI

Observation.Read (Outside Record Vital Signs) (R4) | GET | /api/FHIR/R4/Observation/{ID} | USCDI

Observation.Search (Outside Record Activities of Daily Living) (R4) | GET | /api/FHIR/R4/Observation?based-on={based-on}&category={category}&code={code}&date={date}&focus={focus}&issued={issued}&patient={patient}&subject={subject}&_count={_count}&_id={_id}&_include={_include}&_revinclude={_revinclude} | USCDI

Observation.Search (Outside Record Occupation) (R4) | GET | /api/FHIR/R4/Observation?based-on={based-on}&category={category}&code={code}&date={date}&focus={focus}&issued={issued}&patient={patient}&subject={subject}&_count={_count}&_id={_id}&_include={_include}&_revinclude={_revinclude} | USCDI

Observation.Search (Outside Record Pregnancy Status) (R4) | GET | /api/FHIR/R4/Observation?based-on={based-on}&category={category}&code={code}&date={date}&focus={focus}&issued={issued}&patient={patient}&subject={subject}&_count={_count}&_id={_id}&_include={_include}&_revinclude={_revinclude} | USCDI

Observation.Search (Outside Record Results) (R4) | GET | /api/FHIR/R4/Observation?based-on={based-on}&category={category}&code={code}&date={date}&focus={focus}&issued={issued}&patient={patient}&subject={subject}&_count={_count}&_id={_id}&_include={_include}&_revinclude={_revinclude} | USCDI

Observation.Search (Outside Record Screening Assessment) (R4) | GET | /api/FHIR/R4/Observation?based-on={based-on}&category={category}&code={code}&date={date}&focus={focus}&issued={issued}&patient={patient}&subject={subject}&_count={_count}&_id={_id}&_include={_include}&_revinclude={_revinclude} | USCDI

Observation.Search (Outside Record SDOH Assessment) (R4) | GET | /api/FHIR/R4/Observation?based-on={based-on}&category={category}&code={code}&date={date}&focus={focus}&issued={issued}&patient={patient}&subject={subject}&_count={_count}&_id={_id}&_include={_include}&_revinclude={_revinclude} | USCDI

Observation.Search (Outside Record Sexual Orientation) (R4) | GET | /api/FHIR/R4/Observation?based-on={based-on}&category={category}&code={code}&date={date}&focus={focus}&issued={issued}&patient={patient}&subject={subject}&_count={_count}&_id={_id}&_include={_include}&_revinclude={_revinclude} | USCDI

Observation.Search (Outside Record Smoking Status) (R4) | GET | /api/FHIR/R4/Observation?based-on={based-on}&category={category}&code={code}&date={date}&focus={focus}&issued={issued}&patient={patient}&subject={subject}&_count={_count}&_id={_id}&_include={_include}&_revinclude={_revinclude} | USCDI

Observation.Search (Outside Record Vital Signs) (R4) | GET | /api/FHIR/R4/Observation?based-on={based-on}&category={category}&code={code}&date={date}&focus={focus}&issued={issued}&patient={patient}&subject={subject}&_count={_count}&_id={_id}&_include={_include}&_revinclude={_revinclude} | USCDI

Organization.Read (Outside Record) (R4) | GET | /api/FHIR/R4/Organization/{ID} | USCDI

Organization.Search (Outside Record) (R4) | GET | /api/FHIR/R4/Organization?_count={_count}&_id={_id}&_include={_include}&_revinclude={_revinclude} | USCDI

PAS Incoming Claim Response Notification | POST | /api/FHIR/R4/ClaimResponse/$notify | Industry-Standard

Practitioner.Read (Outside Record) (R4) | GET | /api/FHIR/R4/Practitioner/{ID} | USCDI

Practitioner.Search (Outside Record) (R4) | GET | /api/FHIR/R4/Practitioner?address={address}&address-city={address-city}&address-postalcode={address-postalcode}&address-state={address-state}&family={family}&given={given}&identifier={identifier}&name={name}&_count={_count}&_id={_id}&_include={_include}&_revinclude={_revinclude} | USCDI

PractitionerRole.Read (Outside Record) (R4) | GET | /api/FHIR/R4/PractitionerRole/{ID} | USCDI

PractitionerRole.Search (Outside Record) (R4) | GET | /api/FHIR/R4/PractitionerRole?email={email}&identifier={identifier}&location={location}&organization={organization}&phone={phone}&practitioner={practitioner}&role={role}&specialty={specialty}&telecom={telecom}&_count={_count}&_id={_id}&_include={_include}&_revinclude={_revinclude} | USCDI

Procedure.Read (Outside Record) (R4) | GET | /api/FHIR/R4/Procedure/{ID} | USCDI

Procedure.Search (Outside Record) (R4) | GET | /api/FHIR/R4/Procedure?category={category}&code={code}&date={date}&identifier={identifier}&patient={patient}&subject={subject}&_count={_count}&_id={_id}&_include={_include}&_revinclude={_revinclude} | USCDI

Questionnaire.$log-questionnaire-errors (R4) | | | Industry-Standard

Questionnaire.$next-question (R4) | POST | | Industry-Standard

Questionnaire.$questionnaire-package (R4) | | | Industry-Standard

QuestionnaireResponse.Read (Outside Record) (R4) | GET | /api/FHIR/R4/QuestionnaireResponse/{ID} | USCDI

QuestionnaireResponse.Search (Outside Record) (R4) | GET | /api/FHIR/R4/QuestionnaireResponse?encounter={encounter}&patient={patient}&subject={subject}&_count={_count}&_id={_id}&_include={_include}&_revinclude={_revinclude} | USCDI

RelatedPerson.Read (Outside Record) (R4) | GET | /api/FHIR/R4/RelatedPerson/{ID} | USCDI

RelatedPerson.Search (Outside Record) (R4) | GET | /api/FHIR/R4/RelatedPerson?patient={patient}&_count={_count}&_id={_id}&_include={_include}&_revinclude={_revinclude} | USCDI

ServiceRequest.Read (Outside Record) (R4) | GET | /api/FHIR/R4/ServiceRequest/{ID} | USCDI
ServiceRequest.Read (Prior Auth) (R4) | GET | /api/FHIR/R4/ServiceRequest/{ID} | Industry-Standard
ServiceRequest.Search (Outside Record) (R4) | GET | /api/FHIR/R4/ServiceRequest?authored={authored}&category={category}&code={code}&encounter={encounter}&identifier={identifier}&onlyscannable={onlyscannable}&patient={patient}&requester={requester}&status={status}&subject={subject}&_count={_count}&_id={_id}&_include={_include}&_revinclude={_revinclude} | USCDI
ServiceRequest.Search (Prior Auth) (R4) | GET | /api/FHIR/R4/ServiceRequest?authored={authored}&category={category}&code={code}&encounter={encounter}&identifier={identifier}&onlyscannable={onlyscannable}&patient={patient}&requester={requester}&status={status}&subject={subject}&_count={_count}&_id={_id}&_include={_include}&_revinclude={_revinclude} | Industry-Standard
ServiceRequest.Update (Prior Auth) (R4) | PUT | /api/FHIR/R4/ServiceRequest/{ID}`ServiceRequest*** | Industry-Standard
Specimen.Read (Outside Record) (R4) | GET | /api/FHIR/R4/Specimen/{ID} | USCDI
Specimen.Search (Outside Record) (R4) | GET |
/api/FHIR/R4/Specimen?_count={_count}&_id={_id}&_include={_include}&_revinclude={_revinclude} | USCDI
ValueSet.$expand (DTR Payer Guidelines) (R4) | | /api/FHIR | Industry-Standard

Non-FHIR (2)

API | Method | URL template | Type
Group.$bulk-member-match File Request | | | Industry-Standard
Group.$bulk-member-match Status Request | | | Industry-Standard

14.1 CMS Incoming: R4

File: site/apis/14-CMS-Incoming/1-R4/index.html

* $submit-attachment (Prior Auth) (R4)
* AllergyIntolerance.Read (Outside Record) (R4)
* AllergyIntolerance.Search (Outside Record) (R4)
* Appointment.Read (Prior Auth) (R4)
* Appointment.Search (Prior Auth) (R4)
* Binary.Read (Prior Auth Supporting Info) (R4)
* CarePlan.Read (Outside Record) (R4)
* CarePlan.Search (Outside Record) (R4)
* CareTeam.Read (Outside Record) (R4)
* CareTeam.Search (Outside Record) (R4)
* Claim.$inquire (Prior Auth) (R4)
* Claim.$submit (Prior Auth) (R4)
* Condition.Read (Outside Record Encounter Diagnosis) (R4)
* Condition.Read (Outside Record Health Concern) (R4)
* Condition.Read (Outside Record Problems) (R4)
* Condition.Search (Outside Record Encounter Diagnosis) (R4)
* Condition.Search (Outside Record Health Concern) (R4)
* Condition.Search (Outside Record Problems) (R4)
* Coverage Requirements Discovery (R4)
* Coverage Requirements Discovery Endpoint Discovery (R4)
* Coverage.Read (Outside Record) (R4)
* Coverage.Search (Outside Record) (R4)
* Device.Read (Outside Record) (R4)
* Device.Search (Outside Record) (R4)
* DiagnosticReport.Read (Outside Record Results) (R4)
* DiagnosticReport.Search (Outside Record Results) (R4)
* DocumentReference.Read (Prior Auth Supporting Info) (R4)
* Goal.Read (Outside Record) (R4)
* Goal.Search (Outside Record) (R4)
* Group.$bulk-member-match Kickoff
* Immunization.Read (Outside Record) (R4)
* Immunization.Search (Outside Record) (R4)
* Location.Read (Outside Record) (R4)
* Location.Search (Outside Record) (R4)
* Medication.Read (Outside Record) (R4)
* Medication.Search (Outside Record) (R4)

* MedicationDispense.Read (Outside Record) (R4)
* MedicationDispense.Search (Outside Record) (R4)
* MedicationRequest.Read (Outside Record) (R4)
* MedicationRequest.Read (Prior Auth) (R4)
* MedicationRequest.Search (Outside Record) (R4)
* MedicationRequest.Search (Prior Auth) (R4)
* MedicationRequest.Update (Prior Auth) (R4)
* Observation.Read (Outside Record Activities of Daily Living) (R4)
* Observation.Read (Outside Record Occupation) (R4)
* Observation.Read (Outside Record Pregnancy Status) (R4)
* Observation.Read (Outside Record Results) (R4)
* Observation.Read (Outside Record Screening Assessment) (R4)
* Observation.Read (Outside Record SDOH Assessment) (R4)
* Observation.Read (Outside Record Sexual Orientation) (R4)
* Observation.Read (Outside Record Smoking Status) (R4)
* Observation.Read (Outside Record Vital Signs) (R4)
* Observation.Search (Outside Record Activities of Daily Living) (R4)
* Observation.Search (Outside Record Occupation) (R4)
* Observation.Search (Outside Record Pregnancy Status) (R4)
* Observation.Search (Outside Record Results) (R4)
* Observation.Search (Outside Record Screening Assessment) (R4)
* Observation.Search (Outside Record SDOH Assessment) (R4)
* Observation.Search (Outside Record Sexual Orientation) (R4)
* Observation.Search (Outside Record Smoking Status) (R4)
* Observation.Search (Outside Record Vital Signs) (R4)
* Organization.Read (Outside Record) (R4)
* Organization.Search (Outside Record) (R4)
* PAS Incoming Claim Response Notification
* Practitioner.Read (Outside Record) (R4)
* Practitioner.Search (Outside Record) (R4)
* PractitionerRole.Read (Outside Record) (R4)
* PractitionerRole.Search (Outside Record) (R4)
* Procedure.Read (Outside Record) (R4)
* Procedure.Search (Outside Record) (R4)
* Questionnaire.$log-questionnaire-errors (R4)
* Questionnaire.$next-question (R4)
* Questionnaire.$questionnaire-package (R4)
* QuestionnaireResponse.Read (Outside Record) (R4)
* QuestionnaireResponse.Search (Outside Record) (R4)
* RelatedPerson.Read (Outside Record) (R4)
* RelatedPerson.Search (Outside Record) (R4)
* ServiceRequest.Read (Outside Record) (R4)
* ServiceRequest.Read (Prior Auth) (R4)
* ServiceRequest.Search (Outside Record) (R4)
* ServiceRequest.Search (Prior Auth) (R4)
* ServiceRequest.Update (Prior Auth) (R4)
* Specimen.Read (Outside Record) (R4)
* Specimen.Search (Outside Record) (R4)
* ValueSet.$expand (DTR Payer Guidelines) (R4)

14.1.1 $submit-attachment (Prior Auth) (R4)

File: site/apis/14-CMS-Incoming/1-R4/11276-submit-attachment-Prior-Auth-R4.html
Epic API ID | 11276

FHIR version | R4
Categories | CMS Incoming
API type | Industry-Standard
USCDI | No
HTTP method | POST
URL template | /api/FHIR/R4/$submit-attachment
Supports OAuth 2.0 | True
Supported user types | Backend Systems and Non-OAuth 2.0, Clinicians or Administrative Users
Performs scope validation | False
Source | https://fhir.epic.com/Specifications?api=11276

Description

This web service is used by providers to submit additional information to facilitate the payer's prior authorization review process.

The current types of additional information that are supported include QuestionnaireResponse Bundles and DocumentReference in the form of PDFs.

This is generally used in conjunction with

Claim.$submit (Prior Auth) (R4)

as a way to add details to a specific submission.

This incoming web service enables submission of additional information to the payer's UM system using FHIR. Refer to

Operation Definition of $submit-attachment v2.1.0

and

CDex Parameters Submit Attachment Profile v2.1.0

for more information.

Request parameters

Name | Type | Optional | Array | Cardinality | Description
Parameters (R4) | Parameters | Required | | 1..1 | Container for the $submit-attachment input parameters. This operation accepts attachments and the information required to associate them with a prior authorization.
Parameters (R4).parameter (Attachment) (also: parameter (Attachment)) | BackboneElement | Required | Yes | 1..* | Represents a single attachment submission. Each Attachment parameter contains exactly one payload, either a DocumentReference (PDF) or a DTR Bundle. Exactly one of DocumentReference or Bundle must be present in a single Attachment parameter, but there can be multiple Attachment parameter elements.
Parameters (R4).parameter (Attachment).name | string | Required | | 1..1 | Parameter name. Fixed to "Attachment".
Parameters (R4).parameter (Attachment).part (Content) (also: part (Content)) | BackboneElement | Required | Yes | 1..1 | Attachment payload wrapper. Contains the submitted attachment as a FHIR resource.
Parameters (R4).parameter (Attachment).part (Content).name | string | Required | | 1..1 | Part name. Fixed to "Content".
Parameters (R4).parameter (Attachment).part (Content).resource | ResourceContainer | Required | | 1..1 | Attachment payload resource. Supported types include: DocumentReference (PDF), DTR Bundle (must include QuestionnaireResponse package). Must be represented as whole resources not just references.
Parameters (R4).parameter (Attachment).part (Content).resource.Bundle | Bundle | Conditional | | 0..1 | Bundle used to submit a QuestionnaireResponse. Can contain other referenced resources. Must contain a QuestionnaireResponse resource, and that must be listed first. Exactly one of DocumentReference or Bundle must be present in a single Attachment parameter. For externally processed bundles, not all fields are documented here. The specifications of the entities that the specific customer contracts with should be consulted to verify all required fields are present. Refer to Structure Definition of DTR QRBundle v2.1.0 for more information.
Parameters (R4).parameter (Attachment).part (Content).resource.Bundle.entry | BackboneElement | Required | Yes | 1..* | A container for a resource included in the Bundle. Each entry represents one resource that is part of the structured attachment payload.
Parameters (R4).parameter (Attachment).part (Content).resource.Bundle.entry.fullUrl | uri | Conditional | | 0..1 | The absolute URL identifying the resource in this bundle entry. Can be used to support reference resolution within the bundle.
Parameters (R4).parameter (Attachment).part (Content).resource.Bundle.entry.resource | ResourceContainer | Required | | 1..1 | The resource included in this bundle entry. For DTR submissions, this includes the QuestionnaireResponse and any supporting resources referenced by it.
Parameters (R4).parameter (Attachment).part (Content).resource.Bundle.entry.resource.QuestionnaireResponse | Resource | Required | | 1..1 | Completed responses to the Questionnaire which might be included in this Bundle. Contains answers submitted as structured attachment data. Must be listed as the first element and Bundles must not contain more than one QuestionnaireResponse resource. Refer to Structure Definition of DTR Questionnaire Response v2.1.0 for more information.
Parameters (R4).parameter (Attachment).part (Content).resource.Bundle.entry.resource.QuestionnaireResponse.authored | dateTime | Required | | 1..1 | Date the answers were most recently gathered.
Parameters (R4).parameter (Attachment).part (Content).resource.Bundle.entry.resource.QuestionnaireResponse.extension (intendedUse) (also: extension (intendedUse)) | Extension | Optional | Yes | 0..1 | Indicates how the EHR is to use the information with respect to the associated orders/records.
Parameters (R4).parameter (Attachment).part (Content).resource.Bundle.entry.resource.QuestionnaireResponse.extension (intendedUse).url | uri | Required | | 1..1 | The canonical URL identifying the intendedUse extension. URL: http://hl7.org/fhir/us/davinci-dtr/StructureDefinition/intendedUse
Parameters (R4).parameter (Attachment).part (Content).resource.Bundle.entry.resource.QuestionnaireResponse.extension (intendedUse).valueCodeableConcept | CodeableConcept | Required | | 1..1 | The coded value indicating how the QuestionnaireResponse is intended to be used.
Parameters (R4).parameter (Attachment).part (Content).resource.Bundle.entry.resource.QuestionnaireResponse.extension (intendedUse).valueCodeableConcept.coding | Coding | Required | Yes | 1..1 | A coding that represents the intended use value.
Parameters (R4).parameter (Attachment).part (Content).resource.Bundle.entry.resource.QuestionnaireResponse.extension (intendedUse).valueCodeableConcept.coding.code | String | Required | | 1..1 | The code identifying the intended use value within the code system.
Parameters (R4).parameter (Attachment).part (Content).resource.Bundle.entry.resource.QuestionnaireResponse.extension (intendedUse).valueCodeableConcept.coding.system | String | Required | | 1..1 | The code system for the intended use value. URL:

http://hl7.org/fhir/us/davinci-crd/ValueSet/DocReason

Parameters (R4).parameter (Attachment).part (Content).resource.Bundle.entry.resource.QuestionnaireResponse.extension (qr-context) (also: extension (qr-context)) | Extension | Optional | Yes | 2..* | Identifies the orders and coverages associated with the specified QuestionnaireResponse. The QuestionnaireResponse must have at least one context that refers to a patient Coverage and at least one context that refers to a ServiceRequest resource.

Parameters (R4).parameter (Attachment).part (Content).resource.Bundle.entry.resource.QuestionnaireResponse.extension (qr-context).url | uri | | | | The canonical URL identifying the qr-context extension. URL: http://hl7.org/fhir/us/davinci-dtr/StructureDefinition/qr-context

Parameters (R4).parameter (Attachment).part (Content).resource.Bundle.entry.resource.QuestionnaireResponse.extension (qr-context).valueReference | Reference | Required | | 1..1 | Reference to a resource providing context for the QuestionnaireResponse, such as a Coverage or a ServiceRequest resource.

Parameters (R4).parameter (Attachment).part (Content).resource.Bundle.entry.resource.QuestionnaireResponse.id | id | Required | | 1..1 | The identifier of this QuestionnaireResponse. It is required to be submitted with the same ID from when the QuestionnaireResponse resource was retrieved during a previous part of the workflow.

Parameters (R4).parameter (Attachment).part (Content).resource.Bundle.entry.resource.QuestionnaireResponse.item | BackboneElement | Required | Yes | 1..* | A response item corresponding to a question or group in the Questionnaire. Items can be nested several levels deep.

Parameters (R4).parameter (Attachment).part (Content).resource.Bundle.entry.resource.QuestionnaireResponse.item.answer | BackboneElement | Required | Yes | 1..1 | The answer provided for this item. Answer types should be passed back as originally sent. A change in value type could lead to errors. Only one answer is supported per question. Exactly one value[x] element must be present in each answer.

Parameters (R4).parameter (Attachment).part (Content).resource.Bundle.entry.resource.QuestionnaireResponse.item.answer.extension (@url='http://hl7.org/fhir/us/davinci-dtr/StructureDefinition/information-origin') | Extension | Required | Yes | 1..1 | Identifies the origin of the information in the answer and how it came to exist. URL: http://hl7.org/fhir/us/davinci-dtr/StructureDefinition/information-origin

Parameters (R4).parameter (Attachment).part (Content).resource.Bundle.entry.resource.QuestionnaireResponse.item.answer.extension (@url='http://hl7.org/fhir/us/davinci-dtr/StructureDefinition/information-origin').extension (@url='author') | Extension | Conditional | Yes | 0..1 | Nested extension identifying the author of the information. If source is 'override' or 'manual' then an author must be supplied.

Parameters (R4).parameter (Attachment).part (Content).resource.Bundle.entry.resource.QuestionnaireResponse.item.answer.extension (@url='http://hl7.org/fhir/us/davinci-dtr/StructureDefinition/information-origin').extension (@url='author').extension (@url='practitioner') | Extension | Required | Yes | 1..1 | Reference to the practitioner who authored or modified the information.

Parameters (R4).parameter (Attachment).part (Content).resource.Bundle.entry.resource.QuestionnaireResponse.item.answer.extension (@url='http://hl7.org/fhir/us/davinci-dtr/StructureDefinition/information-origin').extension (@url='author').extension (@url='practitioner').url | uri | Required | | 1..1 | Fixed to "practitioner".

Parameters (R4).parameter (Attachment).part (Content).resource.Bundle.entry.resource.QuestionnaireResponse.item.answer.extension (@url='http://hl7.org/fhir/us/davinci-dtr/StructureDefinition/information-origin').extension (@url='author').extension (@url='practitioner').valueReference | Reference | Required | | 1..1 | Reference to the Practitioner resource representing the author.

Parameters (R4).parameter (Attachment).part (Content).resource.Bundle.entry.resource.QuestionnaireResponse.item.answer.extension (@url='http://hl7.org/fhir/us/davinci-dtr/StructureDefinition/information-origin').extension (@url='author').extension (@url='role') | Extension | Optional | Yes | 0..1 | The role of the individual who provided or modified the information.

Parameters (R4).parameter (Attachment).part (Content).resource.Bundle.entry.resource.QuestionnaireResponse.item.answer.extension (@url='http://hl7.org/fhir/us/davinci-dtr/StructureDefinition/information-origin').extension (@url='author').extension (@url='role').url | uri | Required | | 1..1 | Fixed to "role".

Parameters (R4).parameter (Attachment).part (Content).resource.Bundle.entry.resource.QuestionnaireResponse.item.answer.extension (@url='http://hl7.org/fhir/us/davinci-dtr/StructureDefinition/information-origin').extension (@url='author').extension (@url='role').valueCodeableConcept | CodeableConcept | Required | | 1..1 | The coded role of the author, such as the practitioner role.

Parameters (R4).parameter (Attachment).part (Content).resource.Bundle.entry.resource.QuestionnaireResponse.item.answer.extension (@url='http://hl7.org/fhir/us/davinci-dtr/StructureDefinition/information-origin').extension (@url='author').extension (@url='role').valueCodeableConcept.coding | Coding | Required | Yes | 1..1 | Coding representation of the author role.

Parameters (R4).parameter (Attachment).part (Content).resource.Bundle.entry.resource.QuestionnaireResponse.item.answer.extension (@url='http://hl7.org/fhir/us/davinci-dtr/StructureDefinition/information-origin').extension (@url='author').extension (@url='role').valueCodeableConcept.coding.code | String | Required | | 1..1 | The code identifying the role within the system.

Parameters (R4).parameter (Attachment).part (Content).resource.Bundle.entry.resource.QuestionnaireResponse.item.answer.extension (@url='http://hl7.org/fhir/us/davinci-dtr/StructureDefinition/information-origin').extension (@url='author').extension (@url='role').valueCodeableConcept.coding.system | String | Required | | 1..1 | The code system defining the role. URL: http://hl7.org/fhir/us/core/ValueSet/us-core-provider-role

Parameters (R4).parameter (Attachment).part (Content).resource.Bundle.entry.resource.QuestionnaireResponse.item.answer.extension (@url='http://hl7.org/fhir/us/davinci-dtr/StructureDefinition/information-origin').extension (@url='author').url | uri | Required | | 1..1 | Fixed to "author".

Parameters (R4).parameter (Attachment).part (Content).resource.Bundle.entry.resource.QuestionnaireResponse.item.answer.extension (@url='http://hl7.org/fhir/us/davinci-dtr/StructureDefinition/information-origin').extension (@url='source') | Extension | Required | Yes | 1..1 | Nested extension indicating the source of the information.

Parameters (R4).parameter (Attachment).part (Content).resource.Bundle.entry.resource.QuestionnaireResponse.item.answer.extension (@url='http://hl7.org/fhir/us/davinci-dtr/StructureDefinition/information-origin').extension (@url='source').url | uri | Required | | 1..1 | Fixed to "source".

Parameters (R4).parameter (Attachment).part (Content).resource.Bundle.entry.resource.QuestionnaireResponse.item.answer.extension (@url='http://hl7.org/fhir/us/davinci-dtr/StructureDefinition/information-origin').extension (@url='source').valueCode | code | Required | | 1..1 | The codes describing the possible origination of information. Must be from the Information Origins Value Set. URL: http://hl7.org/fhir/us/davinci-dtr/ValueSet/informationOrigins

Parameters (R4).parameter (Attachment).part (Content).resource.Bundle.entry.resource.QuestionnaireResponse.item.answer.extension (@url='http://hl7.org/fhir/us/davinci-dtr/StructureDefinition/information-origin').url | uri | Required | | 1..1 | Canonical URL identifying the information-origin extension. URL: http://hl7.org/fhir/us/davinci-dtr/StructureDefinition/information-origin

Parameters (R4).parameter (Attachment).part (Content).resource.Bundle.entry.resource.QuestionnaireResponse.item.answer.valueAttachment | Attachment | Conditional | | 0..1 | File attachment answer. The valueAttachment.contentType must be "application/pdf" for a PDF attachment. Other attachment types are ignored.

Parameters (R4).parameter (Attachment).part (Content).resource.Bundle.entry.resource.QuestionnaireResponse.item.answer.valueBoolean | boolean | Conditional | | 0..1 | Boolean true/false answer.

Parameters (R4).parameter (Attachment).part (Content).resource.Bundle.entry.resource.QuestionnaireResponse.item.answer.valueCoding | Coding | Conditional | | 0..1 | Coded answer.

Parameters (R4).parameter (Attachment).part (Content).resource.Bundle.entry.resource.QuestionnaireResponse.item.answer.valueDate | date | Conditional | | 0..1 | Date answer.

Parameters (R4).parameter (Attachment).part (Content).resource.Bundle.entry.resource.QuestionnaireResponse.item.answer.valueDateTime | dateTime | Conditional | | 0..1 | Date and time answer.

Parameters (R4).parameter (Attachment).part (Content).resource.Bundle.entry.resource.QuestionnaireResponse.item.answer.valueDecimal | decimal | Conditional | | 0..1 | Decimal number answer.

Parameters (R4).parameter (Attachment).part (Content).resource.Bundle.entry.resource.QuestionnaireResponse.item.answer.valueQuantity | Quantity | Conditional | | 0..1 | Quantity with unit.

Parameters (R4).parameter (Attachment).part (Content).resource.Bundle.entry.resource.QuestionnaireResponse.item.answer.valueString | string | Conditional | | 0..1 | Free-text string answer.

Parameters (R4).parameter (Attachment).part (Content).resource.Bundle.entry.resource.QuestionnaireResponse.item.answer.valueTime | time | Conditional | | 0..1 | Time answer.

Parameters (R4).parameter (Attachment).part (Content).resource.Bundle.entry.resource.QuestionnaireResponse.item.item | BackboneElement | Required | Yes | 1..* | A response item corresponding to a question or group in the Questionnaire. Items can be nested several levels deep.

Parameters (R4).parameter (Attachment).part (Content).resource.Bundle.entry.resource.QuestionnaireResponse.item.linkId | string | Required | | 1..1 | The ID connecting this item to its question definition in the system. Must be preserved from previous parts of the workflow.

Parameters (R4).parameter (Attachment).part (Content).resource.Bundle.entry.resource.QuestionnaireResponse.item.text | string | Optional | | 0..1 | The display text for the question or group.

Parameters (R4).parameter (Attachment).part (Content).resource.Bundle.entry.resource.QuestionnaireResponse.meta | Meta | Optional | | 0..1 | Metadata about the response resource.

Parameters (R4).parameter (Attachment).part (Content).resource.Bundle.entry.resource.QuestionnaireResponse.meta.profile | String | Optional | Yes | 0..1 | Declares the profile to which the QuestionnaireResponse resource conforms. URL: http://hl7.org/fhir/us/davinci-dtr/StructureDefinition/dtr-questionnaireresponse

Parameters (R4).parameter (Attachment).part (Content).resource.Bundle.entry.resource.QuestionnaireResponse.questionnaire | canonical | Required | | 1..1 | Canonical reference to the Questionnaire definition which might be included in the same Bundle, might be a contained reference, or might just be a reference. Must match the Questionnaire.url value of the included Questionnaire (if included).

Parameters (R4).parameter (Attachment).part (Content).resource.Bundle.entry.resource.QuestionnaireResponse.status | code | Required | | 1..1 | The associated QuestionnaireResponseStatus of the questionnaire response. Expected to be "completed" for submission. URL: http://hl7.org/fhir/ValueSet/questionnaire-answers-status

Parameters (R4).parameter (Attachment).part (Content).resource.Bundle.entry.resource.QuestionnaireResponse.subject | Reference | Required | | 1..1 | Reference to the Patient that this response is about.

Parameters (R4).parameter (Attachment).part (Content).resource.Bundle.entry.resource.QuestionnaireResponse.subject.reference | String | Required | | 1..1 | Reference to the Patient that this response is about.

Parameters (R4).parameter (Attachment).part (Content).resource.Bundle.entry.resource.QuestionnaireResponse.text | Narrative | Optional | | 0..1 | Human-readable narrative summary of the QuestionnaireResponse.

Parameters (R4).parameter (Attachment).part (Content).resource.Bundle.type | code | Required | | 1..1 | Must be "collection".

Parameters (R4).parameter (Attachment).part (Content).resource.DocumentReference | DocumentReference | Conditional | | 0..1 | Represents a document attachment submitted as part of the $submit-attachment operation. Epic supports DocumentReference for submission of PDF attachments. Exactly one of DocumentReference or Bundle must be present in a single Attachment parameter. Refer to Structure Definition of DocumentReference v7.0.0 and Structure Definition of PAS DocumentReference v2.2.0 for more information.

Parameters (R4).parameter (Attachment).part (Content).resource.DocumentReference.content | BackboneElement | Required | Yes | 1..* | The document content. At least one content element must be present and must include a PDF representation of the document. If there are multiple content element repetitions, these must all represent the same document in different format or attachment metadata.

Parameters (R4).parameter (Attachment).part (Content).resource.DocumentReference.content.attachment | Attachment | Required | | 1..1 | The attached content and format. Epic supports DocumentReference for submission of PDF attachments.

Parameters (R4).parameter (Attachment).part (Content).resource.DocumentReference.content.attachment.contentType | String | Required | | 1..1 | Must be "application/pdf" for a pdf attachment. Only PDF is supported. Other attachment types are ignored.

Parameters (R4).parameter (Attachment).part (Content).resource.DocumentReference.content.attachment.data | String | Conditional | | 0..1 | Inline base64 PDF. Either data or url must be populated.

Parameters (R4).parameter (Attachment).part (Content).resource.DocumentReference.content.attachment.size | Int64 | Optional | | 0..1 | Size in bytes.

Parameters (R4).parameter (Attachment).part (Content).resource.DocumentReference.content.attachment.url | String | Conditional | | 0..1 | Url to retrieve the PDF binary. Either data or url must be populated.

Parameters (R4).parameter (Attachment).part (Content).resource.DocumentReference.date | instant | Optional | | 0..1 | Creation timestamp for the DocumentReference.

Parameters (R4).parameter (Attachment).part (Content).resource.DocumentReference.status | code | Required | | 1..1 | The associated DocumentReferenceStatus of DocumentReference. Must be in a status of "current" to be accepted. URL: http://hl7.org/fhir/ValueSet/document-reference-status

Parameters (R4).parameter (Attachment).part (Content).resource.DocumentReference.type | CodeableConcept | Required | | 1..1 | Type of document being submitted. Must include either: a coding with system URL: http://loinc.org, or a coding with system URL: http://terminology.hl7.org/CodeSystem/v3-NullFlavor and code "UNK" if the document type is unknown. LOINC is preferred when known. Use v3-NullFlavor "UNK" only when a specific document type is not available.

Parameters (R4).parameter (AttachTo) (also: parameter (AttachTo)) | BackboneElement | Required | Yes | 1..1 | Indicates the purpose of the submitted attachment. For this operation, the value must be "preauthorization".

Parameters (R4).parameter (AttachTo).name | string | Required | | 1..1 | Parameter name. Fixed to "AttachTo".

Parameters (R4).parameter (AttachTo).valueCode | code | Required | | 1..1 | Required to be "preauthorization" for this endpoint. URL: https://hl7.org/fhir/us/davinci-cdex/STU2.1/ValueSet-cdex-claim-use.html

Parameters (R4).parameter (MemberId) (also: parameter (MemberId)) | BackboneElement | Required | Yes | 1..1 | Patient/member identifier used by the payer to associate the attachment to the correct member record.

Parameters (R4).parameter (MemberId).name | string | Required | | 1..1 | Parameter name. Fixed to "MemberId".

Parameters (R4).parameter (MemberId).valueIdentifier | Identifier | Required | | 1..1 | Member identifier.

Parameters (R4).parameter (MemberId).valueIdentifier.system | String | Required | | 1..1 | Payer's member ID system. Must use Epic member-id namespace. URL: http://open.epic.com/FHIR/StructureDefinition/member-id

Parameters (R4).parameter (MemberId).valueIdentifier.type | CodeableConcept | Required | | 1..1 | Identifier type. Must include coding from system URL: http://terminology.hl7.org/CodeSystem/v2-0203 with code "MB". Must look like this: "type": { "coding": [{ "system": "http://terminology.hl7.org/CodeSystem/v2-0203", "code": "MB" }] }

Parameters (R4).parameter (MemberId).valueIdentifier.value | String | Required | | 1..1 | The member's ID found on their coverage.

Parameters (R4).parameter (OrganizationId) (also: parameter (OrganizationId)) | BackboneElement | Conditional | Yes | 0..1 | Sending organization/location identifier (such as Type 2 NPI). Epic expects either OrganizationId or ProviderId (if both are received, only the first is used). At least one of OrganizationId or ProviderId is required for most configurations.

Parameters (R4).parameter (OrganizationId).name | string | Required | | 1..1 | Parameter name. Fixed to "OrganizationId".

Parameters (R4).parameter (OrganizationId).valueIdentifier | Identifier | Required | | 1..1 | Organization identifier (such as NPI or TIN).

Parameters (R4).parameter (OrganizationId).valueIdentifier.system | String | Required | | 1..1 | Identifier system. Supported: URL: http://terminology.hl7.org/NamingSystem/USEIN (TIN) URL: http://hl7.org/fhir/sid/us-npi (NPI)

Parameters (R4).parameter (OrganizationId).valueIdentifier.value | String | Required | | 1..1 | Organization identifier value.

Parameters (R4).parameter (ProviderId) (also: parameter (ProviderId)) | BackboneElement | Conditional | Yes | 0..1 | Sending provider identifier (such as Type 1 NPI). Epic expects either OrganizationId or ProviderId (if both are received, only the first is used). At least one of OrganizationId or ProviderId is required for most configurations.

Parameters (R4).parameter (ProviderId).name | string | Required | | 1..1 | Parameter name. Fixed to "ProviderId".

Parameters (R4).parameter (ProviderId).valueIdentifier | Identifier | Required | | 1..1 | Provider identifier (such as NPI or TIN).

Parameters (R4).parameter (ProviderId).valueIdentifier.system | String | Required | | 1..1 | Identifier system. Supported: URL: http://terminology.hl7.org/NamingSystem/USEIN (TIN) URL: http://hl7.org/fhir/sid/us-npi (NPI)

Parameters (R4).parameter (ProviderId).valueIdentifier.value | String | Required | | 1..1 | Provider identifier value.

Parameters (R4).parameter (TrackingId) (also: parameter (TrackingId)) | BackboneElement | Required | Yes | 1..1 | Identifier used to associate the submitted attachments with an existing prior authorization request.

Parameters (R4).parameter (TrackingId).name | string | Required | | 1..1 | Parameter name. Fixed to "TrackingId".

Parameters (R4).parameter (TrackingId).valueIdentifier | Identifier | Required | | 1..1 | Identifier containing the tracking control number.

Parameters (R4).parameter (TrackingId).valueIdentifier.system | String | Optional | | 0..1 | Namespace for the tracking identifier (implementation-defined).

Parameters (R4).parameter (TrackingId).valueIdentifier.value | String | Required | | 1..1 | Tracking identifier value.

Sample request

```
POST https://hostname/instance/api/FHIR/R4/$submit-attachment
{
  "resourceType": "Parameters",
  "parameter": [
    {
      "name": "TrackingId",
      "valueIdentifier": {
        "system": "http://example.org/payer",
        "value": "EPICRTXCSN 1051423"
      }
    },
    {
      "name": "AttachTo",
      "valueCode": "preauthorization"
    },
    {
      "name": "OrganizationId",
      "valueIdentifier": {
        "system": "http://hl7.org/fhir/sid/us-npi",
        "value": "1407071236"
      }
    },
    {
      "name": "ProviderId",
      "valueIdentifier": {
        "system": "http://hl7.org/fhir/sid/us-npi",
        "value": "9941339108"
      }
    },
    {
      "name": "MemberId",
      "valueIdentifier": {
        "type": {
          "coding": [
            {
              "system": "http://terminology.hl7.org/CodeSystem/v2-0203",
              "code": "MB"
            }
          ]
        },
        "system": "http://open.epic.com/FHIR/StructureDefinition/member-id",
        "value": "23435436546"
      }
    },
    {
      "name": "Attachment",
      "part": [
        {
          "name": "Content",
          "resource": {
            "resourceType": "DocumentReference",
            "id": "cdex-example-doc1",
            "status": "current",
            "type": {
              "coding": [
                {
                  "system": "http://loinc.org",
                  "code": "11506-3",
                  "display": "Progress note"
                }
              ],
              "text": "Progress note"
```

```
            },
            "category": [
              {
                "coding": [
                  {
                    "system": "http://hl7.org/fhir/us/core/CodeSystem/us-core-documentreference-category",
                    "code": "clinical-note",
                    "display": "Clinical Note"
                  }
                ],
                "text": "Clinical Note 1"
              }
            ],
            "date": "2025-07-03T18:30:56-08:00",
            "content": [
              {
                "attachment": {
                  "contentType": "application/pdf",
                  "data": "<base64 encoded document>"
                }
              }
            ]
          }
        }
      ]
    }
  ]
}
```

Sample response

```
{
  "resourceType": "OperationOutcome",
  "issue": [
    {
      "severity": "fatal",
      "code": "processing",
      "diagnostics": "Binary data extraction failed. Invalid base64 data."
    }
  ]
}
```

14.1.2 AllergyIntolerance.Read (Outside Record) (R4)

File: site/apis/14-CMS-Incoming/1-R4/11363-AllergyIntolerance-Read-Outside-Record-R4.html
Epic API ID | 11363
FHIR version | R4
Categories | CMS Incoming
API type | USCDI
A la carte | Industry-Standard Level 1 API
USCDI | Yes
Available in inpatient and other contexts | Yes
HTTP method | GET
URL template | /api/FHIR/R4/AllergyIntolerance/{ID}
Supports OAuth 2.0 | True
Supported user types | Backend Systems and Non-OAuth 2.0, Clinicians or Administrative Users, Patients
Performs scope validation | False
Source | https://fhir.epic.com/Specifications?api=11363

Description

Use this API to retrieve a specific instance of the AllergyIntolerance (Outside Record) resource. This FHIR resource represents data about an allergy or intolerance associated with a patient.

This API differs from

AllergyIntolerance.Read (Patient Chart) (R4)

because it returns data that was obtained as part of payer data exchange workflows rather than directly recorded during patient care. This data can come from payers, providers, or loaded from other FHIR servers. Because this data doesn't originate from the organization being queried, users of this API should be aware that the data might be unverified, incomplete, or duplicative.

Data from outside payer and provider systems is saved to an organization's database and returned in a standard format, documented below. Data loaded from other FHIR servers is returned in the format the organization received it. Because of this, the documentation below does not apply to these loaded resources. These resources can include any elements from the FHIR specification and can be distinguished from other resources by the presence of meta.tag set to "external-bulk-data".

Request parameters

Name | Type | Optional | Array | Cardinality | Description
ID | token | Required | | | The AllergyIntolerance FHIR ID

Response elements

Name | Type | Optional | Array | Cardinality | Description

AllergyIntolerance (R4) | AllergyIntolerance

AllergyIntolerance (R4).clinicalStatus | CodeableConcept | Required | | 1..1 | The current calculated status of the allergy. This can be active or inactive. All codes are from the system: http://terminology.hl7.org/CodeSystem/allergyintolerance-clinical

AllergyIntolerance (R4).code | CodeableConcept | Required | | 1..1 | The allergen name and codes.

AllergyIntolerance (R4).id | id | | | 1..1 | Unique FHIR ID for the AllergyIntolerance.

AllergyIntolerance (R4).meta | Meta | | | | Metadata about the resource, including information about the origin or source of the data.

AllergyIntolerance (R4).meta.tag | Coding | | Yes | | Set to external-bulk-data for resources originally loaded from another FHIR server. If this element is set to external-bulk-data, all other element-level documentation does not apply to the resource. The resource content might vary and can include any elements allowed by the FHIR specification.

AllergyIntolerance (R4).patient | Reference | Required | | 1..1 | Reference to a Patient resource for whom the allergy is relevant.

AllergyIntolerance (R4).reaction | BackboneElement | Required | Yes | 0..* | List of known reactions the Patient had to the substance.

AllergyIntolerance (R4).reaction.manifestation | CodeableConcept | Required | Yes | 1..* | A single reaction the Patient had to the substance.

Sample request

```
GET https://hostname/instance/api/FHIR/R4/AllergyIntolerance/f6OinER9yIEiN8G5gk-c2.mYoNwcrrbxHjnPnMO4T0ls4
```

Sample response


```
{
  "resourceType": "AllergyIntolerance",
  "id": "f6OinER9yIEiN8G5gk-c2.mYoNwcrrbxHjnPnMO4T0ls4",
  "clinicalStatus": {
    "coding": [
      {
        "system": "http://terminology.hl7.org/CodeSystem/allergyintolerance-clinical",
        "code": "active",
        "display": "Active"
      }
    ],
    "text": "Active"
  },
  "code": {
    "coding": [
      {
        "system": "http://www.nlm.nih.gov/research/umls/rxnorm",
        "code": "190521"
      },
      {
        "system": "http://www.nlm.nih.gov/research/umls/rxnorm",
        "code": "221052"
      },
      {
        "system": "urn:oid:2.16.840.1.113883.4.9",
        "code": "1PPL256S5A"
      },
      {
        "system": "urn:oid:2.16.840.1.113883.4.9",
        "code": "GZP7A66C3C"
      },
      {
        "system": "urn:oid:2.16.840.1.113883.4.9",
        "code": "J220T4J9Q2"
      },
      {
        "system": "urn:oid:2.16.840.1.113883.4.9",
        "code": "PMA9EH08PM"
      },
      {
        "system": "urn:oid:2.16.840.1.113883.4.9",
        "code": "RP0T719KX7"
      },
      {
        "system": "urn:oid:2.16.840.1.113883.4.9",
        "code": "WR2TIP26VS"
      }
    ],
    "text": "Aspirin"
  },
  "patient": {
    "reference": "Patient/eabcdecd1hijklmnop88883",
    "display": "FHIR, Test Patient"
  },
  "reaction": [
    {
      "manifestation": [
        {
          "coding": [
            {
              "system": "urn:oid:2.16.840.1.113883.4.9",
              "code": "TR2SIP26VS"
            }
          ],
```

```
          "text": "Itching"
        }
      ]
    }
  ]
}
```

Change log

Epic Version | Description | Type
February 2026 | The Outside Record FHIR APIs now validate member coverage and return only resources relevant to the member's coverage enrollment. Previously they returned resources unrelated to the member's coverage. | Breaking Change
November 2025 | The Outside Record FHIR APIs are no longer enabled in the November 2025 version. Requests to these APIs do not return data. | Breaking Change

14.1.3 AllergyIntolerance.Search (Outside Record) (R4)

File: site/apis/14-CMS-Incoming/1-R4/11365-AllergyIntolerance-Search-Outside-Record-R4.html
Epic API ID | 11365
FHIR version | R4
Categories | CMS Incoming
API type | USCDI
A la carte | Industry-Standard Level 1 API
USCDI | Yes
Available in inpatient and other contexts | Yes
HTTP method | GET
URL template | /api/FHIR/R4/AllergyIntolerance?clinical-status={clinical-status}&patient={patient}&_count={_count}&_id={_id}&_include={_include}&_revinclude={_revinclude}
Supports OAuth 2.0 | True
Supported user types | Backend Systems and Non-OAuth 2.0, Clinicians or Administrative Users, Patients
Performs scope validation | False
Source | https://fhir.epic.com/Specifications?api=11365

Description

Use this API to search for a patient's AllergyIntolerance resources. This FHIR resource represents data about an allergy or intolerance associated with a patient.

This API differs from

AllergyIntolerance.Search (Patient Chart) (R4)

because it returns data that was obtained as part of payer data exchange workflows rather than directly recorded during patient care. This data can come from payers, providers, or loaded from other FHIR servers. Because this data doesn't originate from the organization being queried, users of this API should be aware that the data might be unverified, incomplete, or duplicative.

Data from outside payer and provider systems is saved to an organization's database and returned in a standard format, documented below. Data loaded from other FHIR servers is returned in the format the organization received it. Because of this, the documentation below does not apply to these loaded resources. These resources can include any elements from the FHIR specification and can be distinguished from other resources by the presence of meta.tag set to "external-bulk-data".

Request parameters

Name | Type | Optional | Array | Cardinality | Description
_count | number | Optional | Yes | | Number of results per page.
_id | token | Optional | Yes | | FHIR resource IDs for the desired resources. Can be used in combination with _count, _include, and _revInclude. All others will be ignored.
_include | string | Optional | Yes | | Used to indicate which referenced resources to include in the search bundle.
_revinclude | string | Optional | Yes | | Used to include Provenance or AuditEvent resources that refer to search results, when available.
patient | reference | Required | Yes | | Reference to a Patient resource.

Request parameters (post-filtered search parameters)

Name | Type | Optional | Array | Cardinality | Description
clinical-status | token | Optional | Yes | | The current status of the allergy. Only active is accepted.
code | token | Optional | Yes | | Code that identifies the allergy or intolerance.
manifestation | token | Optional | Yes | | A single reaction the patient had to the substance.

Response elements

Name | Type | Optional | Array | Cardinality | Description
AllergyIntolerance (R4) | AllergyIntolerance
AllergyIntolerance (R4).clinicalStatus | CodeableConcept | Required | | 1..1 | The current calculated status of the allergy. This can be active or inactive. All codes are from the system: http://terminology.hl7.org/CodeSystem/allergyintolerance-clinical
AllergyIntolerance (R4).code | CodeableConcept | Required | | 1..1 | The allergen name and codes.
AllergyIntolerance (R4).id | id | | | 1..1 | Unique FHIR ID for the AllergyIntolerance.

AllergyIntolerance (R4).meta | Meta | | | Metadata about the resource, including information about the origin or source of the data.

AllergyIntolerance (R4).meta.tag | Coding | | Yes | | Set to external-bulk-data for resources originally loaded from another FHIR server. If this element is set to external-bulk-data, all other element-level documentation does not apply to the resource. The resource content might vary and can include any elements allowed by the FHIR specification.

AllergyIntolerance (R4).patient | Reference | Required | | 1..1 | Reference to a Patient resource for whom the allergy is relevant.

AllergyIntolerance (R4).reaction | BackboneElement | Required | Yes | 0..* | List of known reactions the Patient had to the substance.

AllergyIntolerance (R4).reaction.manifestation | CodeableConcept | Required | Yes | 1..* | A single reaction the Patient had to the substance.

Sample request

```
GET https://hostname/instance/api/FHIR/R4/AllergyIntolerance?patient=eabcdecd1hijklmnop88883
```

Sample response


```
{
  "resourceType": "Bundle",
  "type": "searchset",
  "total": 1,
  "link": [
    {
      "relation": "self",
      "url": "https://hostname/instance/api/FHIR/R4/AllergyIntolerance?patient=eabcdecd1hijklmnop88883"
    }
  ],
  "entry": [
    {
      "link": [
        {
          "relation": "self",
          "url":
    "https://hostname/instance/api/FHIR/R4/AllergyIntolerance/f6OinER9yIEiN8G5gk-c2.mYoNwcrrbxHjnPnMO4T0ls4"
        }
      ],
      "fullUrl":
    "https://hostname/instance/api/FHIR/R4/AllergyIntolerance/f6OinER9yIEiN8G5gk-c2.mYoNwcrrbxHjnPnMO4T0ls4",
      "resource": {
        "resourceType": "AllergyIntolerance",
        "id": "f6OinER9yIEiN8G5gk-c2.mYoNwcrrbxHjnPnMO4T0ls4",
        "clinicalStatus": {
          "coding": [
            {
              "system": "http://terminology.hl7.org/CodeSystem/allergyintolerance-clinical",
              "code": "active",
              "display": "Active"
            }
          ],
          "text": "Active"
        },
        "code": {
          "coding": [
            {
              "system": "http://www.nlm.nih.gov/research/umls/rxnorm",
              "code": "190521"
            },
            {
              "system": "http://www.nlm.nih.gov/research/umls/rxnorm",
              "code": "221052"
            },
            {
              "system": "urn:oid:2.16.840.1.113883.4.9",
              "code": "1PPL256S5A"
            },
            {
              "system": "urn:oid:2.16.840.1.113883.4.9",
              "code": "GZP7A66C3C"
            },
            {
              "system": "urn:oid:2.16.840.1.113883.4.9",
              "code": "J220T4J9Q2"
            },
            {
              "system": "urn:oid:2.16.840.1.113883.4.9",
              "code": "PMA9EH08PM"
            },
            {
              "system": "urn:oid:2.16.840.1.113883.4.9",
              "code": "RP0T719KX7"
            },
            {
              "system": "urn:oid:2.16.840.1.113883.4.9",
              "code": "WR2TIP26VS"
            }
          ],
          "text": "Aspirin"
        },
        "patient": {
          "reference": "Patient/eabcdecd1hijklmnop88883",
```

```
          "display": "FHIR, Test Patient"
        },
        "reaction": [
          {
            "manifestation": [
              {
                "coding": [
                  {
                    "system": "urn:oid:2.16.840.1.113883.4.9",
                    "code": "TR2SIP26VS"
                  }
                ],
                "text": "Itching"
              }
            ]
          }
        ]
      },
      "search": {
        "mode": "match"
      }
    }
  ]
}
```


Change log

Epic Version | Description | Type
February 2026 | The Outside Record FHIR APIs now validate member coverage and return only resources relevant to the member's coverage enrollment. Previously they returned resources unrelated to the member's coverage. | Breaking Change
November 2025 | The Outside Record FHIR APIs are no longer enabled in the November 2025 version. Requests to these APIs do not return data. | Breaking Change

14.1.4 Appointment.Read (Prior Auth) (R4)

File: site/apis/14-CMS-Incoming/1-R4/11269-Appointment-Read-Prior-Auth-R4.html
Epic API ID | 11269
FHIR version | R4
Categories | CMS Incoming
API type | Industry-Standard
USCDI | No
Available in inpatient and other contexts | Yes
HTTP method | GET
URL template | /api/FHIR/R4/Appointment/{ID}
Supports OAuth 2.0 | True
Supported user types | Backend Systems and Non-OAuth 2.0, Clinicians or Administrative Users, Patients
Performs scope validation | False
Source | https://fhir.epic.com/Specifications?api=11269

Description

Appointment (Prior Auth) is used during CDS Hooks workflows which trigger Clinical Requirements Discovery (CRD). The Appointment (Prior Auth) resource can only be sent as a prefetched resource in the CDS Hooks request.

14.1.5 Appointment.Search (Prior Auth) (R4)

File: site/apis/14-CMS-Incoming/1-R4/11270-Appointment-Search-Prior-Auth-R4.html
Epic API ID | 11270
FHIR version | R4
Categories | CMS Incoming
API type | Industry-Standard
USCDI | No
Available in inpatient and other contexts | Yes
HTTP method | GET
URL template | /api/FHIR/R4/Appointment?date={date}&identifier={identifier}&onlyscannable={onlyscannable}&patient={patient}&service-category={service-category}&status={status}&_count={_count}&_id={_id}&_include={_include}&_revinclude={_revinclude}
Supports OAuth 2.0 | True
Supported user types | Backend Systems and Non-OAuth 2.0, Clinicians or Administrative Users, Patients
Performs scope validation | False
Source | https://fhir.epic.com/Specifications?api=11270

Description

Appointment (Prior Auth) is used during CDS Hooks workflows which trigger Clinical Requirements Discovery (CRD). The Appointment (Prior Auth) resource can only be sent as a prefetched resource in the CDS Hooks request.

14.1.6 Binary.Read (Prior Auth Supporting Info) (R4)

File: site/apis/14-CMS-Incoming/1-R4/11398-Binary-Read-Prior-Auth-Supporting-Info-R4.html
Epic API ID | 11398
FHIR version | R4
Categories | CMS Incoming
API type | Industry-Standard
API group | Prior Auth Supporting Info Document Group
USCDI | No
Available in inpatient and other contexts | Yes
HTTP method | GET
URL template | /api/FHIR/R4/Binary/{ID}
Supports OAuth 2.0 | True
Supported user types | Backend Systems and Non-OAuth 2.0, Clinicians or Administrative Users, Patients
Performs scope validation | False
Source | https://fhir.epic.com/Specifications?api=11398

Description

Use this API to retrieve a Binary (Prior Auth Supporting Info) resource. This resource represents the raw binary payload of unstructured clinical content submitted in support of a prior authorization request.

This API is available for provider-facing and backend applications and is not exposed to patient-facing applications.

The API can retrieve supporting information for prior authorizations processed directly by the organization as well as supporting information for prior authorizations received from external payers through payer data exchange workflows.

Data loaded from other FHIR servers is returned in the format the organization received it. Because of this, the documentation below does not apply to these loaded resources.

When used as part of the CMS Payer-to-Payer API, only supporting information for approved prior authorizations is returned. In other interoperability scenarios, supporting information for both approved and denied prior authorizations can be returned.

Request parameters

Name | Type | Optional | Array | Cardinality | Description
ID | token | Required | | | The FHIR ID for the Binary Resource.

Response elements

Name | Type | Optional | Array | Cardinality | Description
Binary (R4) | Binary | | | | A single instance of a FHIR Binary resource.
Binary (R4).contentType | String | | | 1..1 | Mime content type string. This is always "text/html" or "text/rtf".
Binary (R4).data | String | | | 1..1 | Base64 encoded note or document content.

Sample request

```
GET https://hostname/instance/api/FHIR/R4/Binary/fbSaJYwtiyiGEGIsurzCN3g4
```

Sample response


```
{
  "resourceType": "Binary",
  "id": "fbSaJYwtiyiGEGIsurzCN3g4",
  "contentType": "text/html",
  "data": "e1xydGYxXGVwaWNWMTE3MDBcYW5zaVxzcGx0cGdwYXJcamV4cGFuZFxub3hsYXR0b3llbiANClxkZWZmMVxwYXBlcncxMjI0MFxwYXBlcmgxN
    Tg0MFxtYXJnbDE4MDBcbWFyZ3IxODAwXG1hcmd0MTQ0MFxtYXJnYjE0NDAgDQp7XGZvbnR0Ymx7XGYxXGZjaGFyc2V0MFxmc3dpc3MgQXJpYWw7fX0NC
    lxzZWN0ZFxoZWFkZXJ5NzIwXGZvb3Rlcnk3MjBccGFyZFxsdHJwYXIgDQpccGxhaW5cbHRyY2hcbGFuZzBcZnMyMiBteSBITk8gY29tbWVudHMgLCB0a
    GlzIGlzIHRoZSBSRkkgc2lkZVxwYXJ9"
}
```


Change log

Epic Version | Description | Type
Nov 2026 | The “content-disposition” header is returned on Binary.Read requests when the document is requested rather than the FHIR resource representation. | Breaking change

14.1.7 CarePlan.Read (Outside Record) (R4)

File: site/apis/14-CMS-Incoming/1-R4/11458-CarePlan-Read-Outside-Record-R4.html
Epic API ID | 11458
FHIR version | R4
Categories | CMS Incoming
API type | USCDI
A la carte | Industry-Standard Level 1 API
USCDI | Yes
Available in inpatient and other contexts | Yes
HTTP method | GET

URL template | /api/FHIR/R4/CarePlan/{ID}
Supports OAuth 2.0 | True
Supported user types | Backend Systems and Non-OAuth 2.0, Clinicians or Administrative Users, Patients
Performs scope validation | False
Source | https://fhir.epic.com/Specifications?api=11458

Description

Use this API to retrieve details about a care plan for a patient. A single CarePlan (Outside Record) resource represents an individual's assessment and plan of care.

This API differs from other CarePlan APIs because it returns data obtained as part of payer data exchange workflows rather than directly recorded during patient care. This data can come from payers or loaded from other FHIR servers. Because this data doesn't originate from the organization being queried, users of this API should be aware that the data might be unverified, incomplete, or duplicative.

This data is loaded from other FHIR servers and returned in the format the organization received it. Because of this, the documentation below is minimal. These resources can include any elements from the FHIR specification and can be distinguished from other resources by the presence of meta.tag set to

external-bulk-data

Sample request

```
GET https://hostname/instance/api/FHIR/R4/CarePlan/f3-bIiKii7EAbO2puaSH.XrMwLhLvOma5yRUDsnzU08U4
```

Sample response

```
{
    "resourceType": "CarePlan",
    "id": "fLpmCluaIaxXZWoy9Wq933bRL7afy53t-SfVxfj.FmLg4",
    "meta": {
        "tag": [
            {
                "system": "https://open.epic.com/FHIR/bulk-data-source",
                "code": "external-bulk-data",
                "display": "External Bulk Data"
            }
        ]
    },
    ... <R4 CarePlan Compliant Elements> ...
}
```

14.1.8 CarePlan.Search (Outside Record) (R4)

File: site/apis/14-CMS-Incoming/1-R4/11457-CarePlan-Search-Outside-Record-R4.html
Epic API ID | 11457
FHIR version | R4
Categories | CMS Incoming
API type | USCDI
A la carte | Industry-Standard Level 1 API
USCDI | Yes
Available in inpatient and other contexts | Yes
HTTP method | GET
URL template | /api/FHIR/R4/CarePlan?activity-date={activity-date}&category={category}&encounter={encounter}&part-of={part-of}&patient={patient}&status={status}&subject={subject}&_count={_count}&_id={_id}&_include={_include}&_revinclude={_revinclude}
Supports OAuth 2.0 | True
Supported user types | Backend Systems and Non-OAuth 2.0, Clinicians or Administrative Users, Patients
Performs scope validation | False
Source | https://fhir.epic.com/Specifications?api=11457

Description

Use this API to search for care plans for a patient. A single CarePlan (Outside Record) resource represents an individual's assessment and plan of care.

This API differs from other CarePlan APIs because it returns data obtained as part of payer data exchange workflows rather than directly recorded during patient care. This data can come from payers or loaded from other FHIR servers. Because this data doesn't originate from the organization being queried, users of this API should be aware that the data might be unverified, incomplete, or duplicative.

This data is loaded from other FHIR servers and returned in the format the organization received it. Because of this, the documentation below is minimal. These resources can include any elements from the FHIR specification and can be distinguished from other resources by the presence of meta.tag set to

external-bulk-data

Request parameters

Name | Type | Optional | Array | Cardinality | Description
_count | String | Optional | Yes | | Number of results per page.
_id | String | Optional | Yes | | FHIR resource IDs for the desired resources. Can be used in combination with _count, _include, and _revInclude. All others will be ignored.
_include | String | Optional | Yes | | Used to indicate which referenced resources to include in the search bundle.
_revinclude | String | Optional | Yes | | Used to include Provenance or AuditEvent resources that refer to search results, when available.
category | String | Optional | Yes | | The category of the care plan.
patient | String | Optional | Yes | | Reference to a Patient resource whose care plan was documented. Either patient or subject must be populated. If patient and subject are both populated, they must be identical.

Request parameters (post-filtered search parameters)

Name | Type | Optional | Array | Cardinality | Description
activity-date | String | Optional | Yes | | Date in which the activity is to occur or has occurred.
status | String | Optional | Yes | | The status of the care plan.
subject | String | Optional | Yes | | Reference to a Patient resource whose care plan was documented. Either patient or subject must be populated. If patient and subject are both populated, they must be identical.

Response elements

Name | Type | Optional | Array | Cardinality | Description
CarePlan (R4) | CarePlan | | | | An instance of the R4 CarePlan resource.
CarePlan (R4).id | String | | | 1..1 | The unique FHIR ID representing the CarePlan (Outside Record) resource.
CarePlan (R4).meta | Meta | | | 1..1 | Metadata about the resource, including information about the origin or source of the data.
CarePlan (R4).meta.tag | Coding | | Yes | 1..* | Set to external-bulk-data for resources originally loaded from another FHIR server. If this element is set to external-bulk-data, the resource content might vary and can include any elements allowed by the FHIR specification.
CarePlan (R4).subject | Reference | | | 1..1 | Reference to a Patient resource for whom the care plan is relevant.

Sample request

```
GET https://hostname/instance/api/FHIR/R4/CarePlan?patient=ewkziDgGIYcHews463gzKyQ3&category=assess-plan
```

Sample response


```
{
    "resourceType": "Bundle",
    "type": "searchset",
    "total": 1,
    "link": [
        {
            "relation": "self",
            "url": "https://hostname/instance/api/FHIR/R4/CarePlan?patient=ewkziDgGIYcHews463gzKyQ3&category=assess-
    plan"
        }
    ],
    "entry": [
        {
            "link": [
                {
                    "relation": "self",
                    "url": "https://hostname/instance/api/FHIR/R4/CarePlan/egRzL.QI2v-
    y35mh3e0CKSyyJe8k6bAUPW58YbJkpb9AfdMRRph6aI2aZ07Ha2DeS31-Z7sMw3sjptZF8-sCqYg3"
                }
            ],
            "fullUrl": "https://hostname/instance/api/FHIR/R4/CarePlan/egRzL.QI2v-
    y35mh3e0CKSyyJe8k6bAUPW58YbJkpb9AfdMRRph6aI2aZ07Ha2DeS31-Z7sMw3sjptZF8-sCqYg3",
            "resource": {
                "resourceType": "CarePlan",
                "id": "egRzL.QI2v-y35mh3e0CKSyyJe8k6bAUPW58YbJkpb9AfdMRRph6aI2aZ07Ha2DeS31-Z7sMw3sjptZF8-sCqYg3",
                "meta": {
                    "tag": [
                        {
                            "system": "https://open.epic.com/FHIR/bulk-data-source",
                            "code": "external-bulk-data",
                            "display": "External Bulk Data"
                        }
                    ]
                },
                ... <r4 careplan="" compliant="" elements=""> ...
            }
        }
    ]
}</r4>
```


14.1.9 CareTeam.Read (Outside Record) (R4)

File: site/apis/14-CMS-Incoming/1-R4/11367-CareTeam-Read-Outside-Record-R4.html
Epic API ID | 11367
FHIR version | R4
Categories | CMS Incoming
API type | USCDI

A la carte | Industry-Standard Level 1 API
USCDI | Yes
Available in inpatient and other contexts | Yes
HTTP method | GET
URL template | /api/FHIR/R4/CareTeam/{ID}
Supports OAuth 2.0 | True
Supported user types | Backend Systems and Non-OAuth 2.0, Clinicians or Administrative Users, Patients
Performs scope validation | False
Source | https://fhir.epic.com/Specifications?api=11367

Description

Use this API to retrieve a specific instance of a CareTeam. This FHIR resource represents information about a patient's care team and care team members.

This API differs from other CareTeam APIs because it returns data that was obtained as part of payer data exchange workflows rather than directly recorded during patient care. This data can come from payers, providers, or loaded from other FHIR servers. Because this data doesn't originate from the organization being queried, users of this API should be aware that the data might be unverified, incomplete, or duplicative.

Data from outside payer and provider systems is saved to an organization's database and returned in a standard format, documented below. Data loaded from other FHIR servers is returned in the format the organization received it. Because of this, the documentation below does not apply to these loaded resources. These resources can include any elements from the FHIR specification and can be distinguished from other resources by the presence of meta.tag set to "external-bulk-data".

Request parameters

Name | Type | Optional | Array | Cardinality | Description
ID | token | Required | | | A CareTeam's FHIR ID.

Response elements

Name | Type | Optional | Array | Cardinality | Description
CareTeam (R4) | CareTeam
CareTeam (R4).id | id | | | 1..1 | Unique FHIR ID for the CareTeam resource.
CareTeam (R4).meta | Meta | | | | Metadata about the resource, including information about the origin or source of the data.
CareTeam (R4).meta.tag | Coding | | Yes | | Set to external-bulk-data for resources originally loaded from another FHIR server. If this element is set to external-bulk-data, all other element-level documentation does not apply to the resource. The resource content might vary and can include any elements allowed by the FHIR specification.
CareTeam (R4).participant | BackboneElement | Required | Yes | 1..* | A participant in the care team.
CareTeam (R4).participant.member | Reference | Required | | 1..1 | Reference to a care team member. All CareTeam members referenced are a PractitionerRole resource.
CareTeam (R4).participant.period | Period | | | 0..1 | The time period during which the participant was on the CareTeam.
CareTeam (R4).participant.role | CodeableConcept | Required | Yes | 1..1 | Provider type or specialty.
CareTeam (R4).status | code | Required | | 1..1 | This field always return "active". This CareTeam resource only returns known active members on the CareTeam.
CareTeam (R4).subject | Reference | Required | | 1..1 | A reference to the patient FHIR resource.

Sample request

```
GET https://hostname/instance/api/FHIR/R4/CareTeam/eLBjKFCDCE-jKkMAS4JxZ3pAST.wl3
```

Sample response


```
{
  "resourceType": "CareTeam",
  "id": "eLBjKFCDCE-jKkMAS4JxZ3pAST.wl3",
  "status": "active",
  "subject": {
    "reference": "Patient/eabcdecd1hijklmnop88883",
    "display": "FHIR, Test Patient"
  },
  "participant": [
    {
      "role": [
        {
          "coding": [
            {
              "system": "urn:oid:1.2.840.114350.1.13.5325.1.7.4.836982.1050",
              "code": "9",
              "display": "Family Practice"
            },
            {
              "system": "urn:oid:1.2.840.114350.1.13.5325.1.7.4.698084.5655",
              "code": "1",
              "display": "General"
            }
          ],
          "text": "Family Practice"
        }
```

```
      ],
      "member": {
          "reference": "Practitioner/eF6GO8p1qW-YKCvYtvJ3P5w3",
          "display": "Test Provider FHIR A, MD"
      },
      "period": {
          "start": "2018-11-15"
    }
  ]
}
```

Change log

Epic Version | Description | Type
February 2026 | The Outside Record FHIR APIs now validate member coverage and return only resources relevant to the member's coverage enrollment. Previously they returned resources unrelated to the member's coverage. | Breaking Change
November 2025 | The Outside Record FHIR APIs are no longer enabled in the November 2025 version. Requests to these APIs do not return data. | Breaking Change

14.1.10 CareTeam.Search (Outside Record) (R4)

File: site/apis/14-CMS-Incoming/1-R4/11369-CareTeam-Search-Outside-Record-R4.html
Epic API ID | 11369
FHIR version | R4
Categories | CMS Incoming
API type | USCDI
A la carte | Industry-Standard Level 1 API
USCDI | Yes
Available in inpatient and other contexts | Yes
HTTP method | GET
URL template | /api/FHIR/R4/CareTeam?patient={patient}&status={status}&subject={subject}&_count={_count}&_id={_id}&_include={_include}&_revinclude={_revinclude}
Supports OAuth 2.0 | True
Supported user types | Backend Systems and Non-OAuth 2.0, Clinicians or Administrative Users, Patients
Performs scope validation | False
Source | https://fhir.epic.com/Specifications?api=11369

Description

Use this API to

search for a patient's CareTeams

. This FHIR resource represents information about a patient's care team and care team members.

This API differs from other CareTeam APIs because it returns data that was obtained as part of payer data exchange workflows rather than directly recorded during patient care. This data can come from payers, providers, or loaded from other FHIR servers. Because this data doesn't originate from the organization being queried, users of this API should be aware that the data might be unverified, incomplete, or duplicative.

Data from outside payer and provider systems is saved to an organization's database and returned in a standard format, documented below. Data loaded from other FHIR servers is returned in the format the organization received it. Because of this, the documentation below does not apply to these loaded resources. These resources can include any elements from the FHIR specification and can be distinguished from other resources by the presence of meta.tag set to "external-bulk-data".

Request parameters

Name | Type | Optional | Array | Cardinality | Description
_count | number | Optional | Yes | | Number of results per page.
_id | token | Optional | Yes | | FHIR resource IDs for the desired resources. Can be used in combination with _count, _include, and _revInclude. All others will be ignored.
_include | string | Optional | Yes | | Used to indicate which referenced resources to include in the search bundle.
_revinclude | string | Optional | Yes | | Used to include Provenance or AuditEvent resources that refer to search results, when available.
patient | reference | Conditional | Yes | | Patient FHIR resource ID. Either a patient or subject parameter must be provided. If both are provided, they must match exactly.
status | token | Optional | Yes | | CareTeam status.
subject | reference | Conditional | Yes | | Patient FHIR resource ID. Either a patient or subject parameter must be provided. If both are provided, they must match exactly.

Request parameters (post-filtered search parameters)

Name | Type | Optional | Array | Cardinality | Description
participant | reference | Optional | Yes | | A member of the team

Response elements

Name | Type | Optional | Array | Cardinality | Description
CareTeam (R4) | CareTeam

CareTeam (R4).id | id | | | 1..1 | Unique FHIR ID for the CareTeam resource.

CareTeam (R4).meta | Meta | | | | Metadata about the resource, including information about the origin or source of the data.

CareTeam (R4).meta.tag | Coding | | Yes | | Set to external-bulk-data for resources originally loaded from another FHIR server. If this element is set to external-bulk-data, all other element-level documentation does not apply to the resource. The resource content might vary and can include any elements allowed by the FHIR specification.

CareTeam (R4).participant | BackboneElement | Required | Yes | 1..* | A participant in the care team.

CareTeam (R4).participant.member | Reference | Required | | 1..1 | Reference to a care team member. All CareTeam members referenced are a PractitionerRole resource.

CareTeam (R4).participant.period | Period | | | 0..1 | The time period during which the participant was on the CareTeam.

CareTeam (R4).participant.role | CodeableConcept | Required | Yes | 1..1 | Provider type or specialty.

CareTeam (R4).status | code | Required | | 1..1 | This field always return "active". This CareTeam resource only returns known active members on the CareTeam.

CareTeam (R4).subject | Reference | Required | | 1..1 | A reference to the patient FHIR resource.

Sample request

```
GET https://hostname/instance/api/FHIR/R4/CareTeam?patient=eabcdecd1hijklmnop88883
```

Sample response


```
{
  "resourceType": "Bundle",
  "type": "searchset",
  "total": 1,
  "link": [
    {
      "relation": "self",
      "url": "https://hostname/instance/api/FHIR/R4/CareTeam?patient=eabcdecd1hijklmnop88883"
    }
  ],
  "entry": [
    {
      "link": [
        {
          "relation": "self",
          "url": "https://hostname/instance/api/FHIR/R4/CareTeam/eKDCE-jKkMA4JxZ3pJbu.ww3"
        }
      ],
      "fullUrl": "https://hostname/instance/api/FHIR/R4/CareTeam/eKDCE-jKkMA4JxZ3pJbu.ww3",
      "resource": {
        "resourceType": "CareTeam",
        "id": "eKDCE-jKkMA4JxZ3pJbu.ww3",
        "status": "active",
        "subject": {
          "reference": "Patient/eabcdecd1hijklmnop88883",
          "display": "FHIR, Test Patient"
        },
        "participant": [
          {
            "role": [
              {
                "coding": [
                  {
                    "system": "urn:oid:1.2.840.114350.1.13.5325.1.7.4.836982.1050",
                    "code": "9",
                    "display": "Family Practice"
                  },
                  {
                    "system": "urn:oid:1.2.840.114350.1.13.5325.1.7.4.698084.5655",
                    "code": "1",
                    "display": "General"
                  }
                ],
                "text": "Family Practice"
              }
            ],
            "member": {
              "reference": "Practitioner/eF6GO8p1qW-YKCvYtvJ3P5w3",
              "display": "Test Provider FHIR A, MD"
            },
            "period": {
              "start": "2018-11-15"
            }
          },
          {
            "role": [
              {
                "coding": [
                  {
                    "system": "urn:oid:1.2.840.114350.1.13.5325.1.7.4.836982.1050",
                    "code": "3",
                    "display": "Audiology"
                  },
                  {
                    "system": "http://nucc.org",
                    "code": "231H00000X",
```

```
                  "display": "Audiology"
                }
              ],
              "text": "Audiology"
            }
          ],
          "member": {
            "reference": "Practitioner/ezWCnkVxIP.UJG8lklPITMw3",
            "display": "Test Provider FHIR B, MD"
          }
        }
      ]
    },
    "search": {
      "mode": "match"
    }
  }
 ]
}
```


Change log

Epic Version | Description | Type
February 2026 | The Outside Record FHIR APIs now validate member coverage and return only resources relevant to the member's coverage enrollment. Previously they returned resources unrelated to the member's coverage. | Breaking Change
November 2025 | The Outside Record FHIR APIs are no longer enabled in the November 2025 version. Requests to these APIs do not return data. | Breaking Change

14.1.11 Claim.$inquire (Prior Auth) (R4)

File: site/apis/14-CMS-Incoming/1-R4/11275-Claim-inquire-Prior-Auth-R4.html
Epic API ID | 11275
FHIR version | R4
Categories | CMS Incoming
API type | Industry-Standard
USCDI | No
HTTP method | POST
URL template | /api/FHIR/R4/Claim/$inquire`Parameters***
Supports OAuth 2.0 | True
Supported user types | Backend Systems and Non-OAuth 2.0, Clinicians or Administrative Users
Performs scope validation | False
Source | https://fhir.epic.com/Specifications?api=11275

Description

This web service enables providers to inquire about the status of existing prior authorization requests in the utilization management system using FHIR technology. It is an alternative to the traditional ANSI X12 278 transaction, which is the EDI standard historically used by payers and providers to exchange prior authorization requests and inquiries electronically.

Providers can use this service to check the current review status, retrieve pended authorization details, or confirm approved/denied outcomes for previously submitted prior authorization requests. This API functions similarly to the incoming 278 inquiry API but, instead, uses the FHIR specification defined in

the Da Vinci Prior Authorization Support implementation guide

Request parameters

Name | Type | Optional | Array | Cardinality | Description
Bundle (R4) | Bundle | Required | | 1..1 | A collection of resources.
Bundle (R4).entry | BackboneElement | Required | Yes | 1..* | Entries in the bundle – each entry contains a resource. Supported resources: Claim, Coverage, Patient, Practitioner, PractitionerRole, Organization, Location. Must include only one Claim resource. All referenced resources need to be included as well.
Bundle (R4).entry.resource | ResourceContainer | Required | | 1..1 | A resource in the bundle.
Bundle (R4).entry.resource.Claim | Resource | Required | | 1..1 | The prior authorization Claim resource contains details about the requested services, along with references to supporting clinical and administrative resources such as Patient, Coverage, Practitioner, Organization, and relevant clinical documentation.
Bundle (R4).entry.resource.Claim.accident | BackboneElement | Optional | | 0..1 | Accident information.
Bundle (R4).entry.resource.Claim.accident.date | date | Required | | 1..1 | Accident date.
Bundle (R4).entry.resource.Claim.billablePeriod | Period | Optional | | 0..1 | Relevant timeframe for the claim, use as fallback dates for supportingInfo:admissionDate/dischargeDate and supportingInfo:patientEvent.
Bundle (R4).entry.resource.Claim.billablePeriod.end | String | Required | | 1..1 | End dateTime.
Bundle (R4).entry.resource.Claim.billablePeriod.start | String | Required | | 1..1 | Start dateTime.
Bundle (R4).entry.resource.Claim.careTeam | BackboneElement | Optional | Yes | 0..* | It can be either: Care team providers that are applicable to all services being requested. Care team providers that are applicable to a specific item (as referenced by that item).
Bundle (R4).entry.resource.Claim.careTeam.extension (careTeamClaimScope) (also: extension (careTeamClaimScope)) | Extension | Required | Yes | 1..1 | Whether this care team element applies to the whole claim. URL: http://hl7.org/fhir/us/davinci-pas/StructureDefinition/extension-careTeamClaimScope

Bundle (R4).entry.resource.Claim.careTeam.extension (careTeamClaimScope).url | uri | Required | | 1..1 | URL of the extension: http://hl7.org/fhir/us/davinci-pas/StructureDefinition/extension-careTeamClaimScope

Bundle (R4).entry.resource.Claim.careTeam.extension (careTeamClaimScope).valueBoolean | boolean | Required | | 1..1 | True if the careTeam element applies to the entire claim. False if the careTeam element applies a specific item.

Bundle (R4).entry.resource.Claim.careTeam.provider | Reference | Required | | 1..1 | Member of the care team who renders the service(s). A reference to a Practitioner, PractitionerRole, or Organization resource.

Bundle (R4).entry.resource.Claim.careTeam.qualification | CodeableConcept | Optional | | 0..1 | The qualification of practitioner. Must include a coding system of https://codesystem.x12.org/005010/127.

Bundle (R4).entry.resource.Claim.careTeam.role | CodeableConcept | Optional | | 0..1 | Function within the care team. Must include a coding system of https://codesystem.x12.org/005010/98.

Bundle (R4).entry.resource.Claim.careTeam.sequence | positiveInt | Required | | 1..1 | Sequence number of careTeam member.

Bundle (R4).entry.resource.Claim.created | dateTime | Optional | | 0..1 | Resource creation date.

Bundle (R4).entry.resource.Claim.diagnosis | BackboneElement | Optional | Yes | 0..* | Diagnosis information.

Bundle (R4).entry.resource.Claim.enterer | Reference | Optional | | 0..1 | Author of the claim. A reference to a Practitioner or PractitionerRole resource.

Bundle (R4).entry.resource.Claim.extension (administrationReferenceNumber) (also: extension (administrationReferenceNumber)) | Extension | Optional | Yes | 0..1 | Administrative Reference Number and Authorization number must be the same for inquiry. The value must be taken from the preAuthRef element of a ClaimResponse to the previous Claim being updated. URL: http://hl7.org/fhir/us/davinci-pas/StructureDefinition/extension-administrationReferenceNumber

Bundle (R4).entry.resource.Claim.extension (administrationReferenceNumber).url | uri | Required | | 1..1 | URL of the extension: http://hl7.org/fhir/us/davinci-pas/StructureDefinition/extension-administrationReferenceNumber

Bundle (R4).entry.resource.Claim.extension (administrationReferenceNumber).valueString | string | Required | | 1..1 | Administration reference number. The value must be taken from the preAuthRef element of a ClaimResponse to the previous Claim being updated.

Bundle (R4).entry.resource.Claim.extension (authorizationNumber) (also: extension (authorizationNumber)) | Extension | Optional | Yes | 0..1 | A string assigned by the UMO to an authorized review outcome associated with this service item. Administrative Reference Number and Authorization number must be the same for inquiry. The value must be taken from the preAuthRef element of a ClaimResponse to the previous Claim being updated. URL: http://hl7.org/fhir/us/davinci-pas/StructureDefinition/extension-authorizationNumber

Bundle (R4).entry.resource.Claim.extension (authorizationNumber).url | uri | Required | | 1..1 | URL of the extension: http://hl7.org/fhir/us/davinci-pas/StructureDefinition/extension-authorizationNumber

Bundle (R4).entry.resource.Claim.extension (authorizationNumber).valueString | string | Required | | 1..1 | Authorization number.

Bundle (R4).entry.resource.Claim.extension (homeHealthCareInformation) (also: extension (homeHealthCareInformation)) | Extension | Optional | Yes | 0..1 | Extensions for homeHealthCareInformation, equivalent to CR6 (ANSI X12 value). URL: http://hl7.org/fhir/us/davinci-pas/StructureDefinition/extension-homeHealthCareInformation

Bundle (R4).entry.resource.Claim.extension (homeHealthCareInformation).extension (date) (also: extension (date)) | Extension | Required | Yes | 1..1 | Home health start date, equivalent to CR602 (ANSI X12 value). If prognosis is populated, date must be populated as well. URL: “date”

Bundle (R4).entry.resource.Claim.extension (homeHealthCareInformation).extension (date).url | uri | Required | | 1..1 | URL of the extension: “date”

Bundle (R4).entry.resource.Claim.extension (homeHealthCareInformation).extension (date).valueDate | date | Required | | 1..1 | Home health start date, equivalent to CR602 (ANSI X12 value). If prognosis is populated, date is required to be populated as well.

Bundle (R4).entry.resource.Claim.extension (homeHealthCareInformation).extension (prognosis) (also: extension (prognosis)) | Extension | Required | Yes | 1..1 | Prognosis code, equivalent to CR601 (ANSI X12 value). URL: “prognosis”

Bundle (R4).entry.resource.Claim.extension (homeHealthCareInformation).extension (prognosis).url | uri | Required | | 1..1 | URL of the extension: “prognosis”

Bundle (R4).entry.resource.Claim.extension (homeHealthCareInformation).extension (prognosis).valueCodeableConcept | CodeableConcept | Required | | 1..1 | Prognosis code. Must include a coding system of https://codesystem.x12.org/005010/923.

Bundle (R4).entry.resource.Claim.extension (homeHealthCareInformation).url | uri | Required | | 1..1 | URL of the extension: http://hl7.org/fhir/us/davinci-pas/StructureDefinition/extension-homeHealthCareInformation

Bundle (R4).entry.resource.Claim.extension (levelOfServiceCode) (also: extension (levelOfServiceCode)) | Extension | Optional | Yes | 0..1 | Extension for levelOfServiceCode. URL: http://hl7.org/fhir/us/davinci-pas/StructureDefinition/extension-levelOfServiceCode

Bundle (R4).entry.resource.Claim.extension (levelOfServiceCode).url | uri | Required | | 1..1 | URL of the extension: http://hl7.org/fhir/us/davinci-pas/StructureDefinition/extension-levelOfServiceCode

Bundle (R4).entry.resource.Claim.extension (levelOfServiceCode).valueCodeableConcept | CodeableConcept | Required | | 1..1 | Level of service type code. Must include a coding system of https://codesystem.x12.org/005010/1338.

Bundle (R4).entry.resource.Claim.facility | Reference | Optional | | 0..1 | Facility where the services were provided. A reference to a Location resource.

Bundle (R4).entry.resource.Claim.id | id | Optional | | 0..1 | Claim ID.

Bundle (R4).entry.resource.Claim.identifier | Identifier | Required | Yes | 1..* | Business identifier for the claim, equivalent to TRN (ANSI X12 value).

Bundle (R4).entry.resource.Claim.identifier.extension (subDepartment) (also: extension (subDepartment)) | Extension | Optional | Yes | 0..1 | Extension for subDepartment. An additional element that provides a further subdivision within the organization granting the identifier, equivalent to TRN04 (ANSI X12 value). URL: http://hl7.org/fhir/us/davinci-pas/StructureDefinition/extension-identifierSubDepartment

Bundle (R4).entry.resource.Claim.identifier.extension (subDepartment).url | uri | Required | | 1..1 | URL of the extension: http://hl7.org/fhir/us/davinci-pas/StructureDefinition/extension-identifierSubDepartment

Bundle (R4).entry.resource.Claim.identifier.extension (subDepartment).valueString | string | Required | | 1..1 | Additional reference number.

Bundle (R4).entry.resource.Claim.identifier.system | String | Required | | 1..1 | This System of the identifier, equivalent to TRN03 (ANSI X12 value). Should use a scheme of 'urn:trnorg:<TRN03>' (ANSI X12 value).

Bundle (R4).entry.resource.Claim.identifier.value | String | Required | | 1..1 | System of the identifier, equivalent to TRN03 (ANSI X12 value).

Bundle (R4).entry.resource.Claim.insurance | BackboneElement | Required | Yes | 1..* | Patient insurance information.

Bundle (R4).entry.resource.Claim.insurance.coverage | Reference | Required | | 1..1 | A reference to a Coverage resource.

Bundle (R4).entry.resource.Claim.insurance.focal | boolean | Required | | 1..1 | A flag to indicate if the coverage is used for the prior authorization. The first coverage with a focal value of true is used.

Bundle (R4).entry.resource.Claim.insurer | Reference | Required | | 1..1 | Target of the request, equivalent to UMO loop (2000A). A reference to an Organization resource.

Bundle (R4).entry.resource.Claim.item | BackboneElement | Optional | Yes | 0..* | Product or service provided.

Bundle (R4).entry.resource.Claim.item.careTeamSequence | positiveInt | Optional | Yes | 0..* | Sequence number of the related care team.

Bundle (R4).entry.resource.Claim.item.category | CodeableConcept | Required | | 1..1 | Code to identify the general type of benefits under which products and services are provided, equivalent to 2000F UM03 (ANSI X12 value). Must include one of the allowed coding systems:

https://x12.org/codes/service-type-codes http://codesystem.x12.org/005010/1365.

Bundle (R4).entry.resource.Claim.item.diagnosisSequence | positiveInt | Optional | Yes | 0..* | Sequence number of the related diagnosis.

Bundle (R4).entry.resource.Claim.item.extension (administrationReferenceNumber) (also: extension (administrationReferenceNumber)) | Extension | Optional | Yes | 0..1 | Identifier assigned by the UMO to the original disallowed review outcome for this service item. URL: http://hl7.org/fhir/us/davinci-pas/StructureDefinition/extension-administrationReferenceNumber

Bundle (R4).entry.resource.Claim.item.extension (administrationReferenceNumber).url | uri | Required | | 1..1 | URL of the extension: http://hl7.org/fhir/us/davinci-pas/StructureDefinition/extension-administrationReferenceNumber

Bundle (R4).entry.resource.Claim.item.extension (administrationReferenceNumber).valueString | string | Required | | 1..1 | Administrative reference number.

Bundle (R4).entry.resource.Claim.item.extension (authorizationNumber) (also: extension (authorizationNumber)) | Extension | Optional | Yes | 0..1 | A string assigned by the UMO to an authorized review outcome associated with this service item. Administrative Reference Number and Authorization number must be the same for inquiry. The value must be taken from the preAuthRef element of a ClaimResponse to the previous Claim being updated. URL: http://hl7.org/fhir/us/davinci-pas/StructureDefinition/extension-authorizationNumber

Bundle (R4).entry.resource.Claim.item.extension (authorizationNumber).url | uri | Required | | 1..1 | URL of the extension: http://hl7.org/fhir/us/davinci-pas/StructureDefinition/extension-authorizationNumber

Bundle (R4).entry.resource.Claim.item.extension (authorizationNumber).valueString | string | Required | | 1..1 | Authorization number.

Bundle (R4).entry.resource.Claim.item.extension (certEffectiveDate) (also: extension (certEffectiveDate)) | Extension | Optional | Yes | 0..1 | The specific date or period within which this item's preauthorization became effective. URL: http://hl7.org/fhir/us/davinci-pas/StructureDefinition/extension-itemCertificationEffectiveDate

Bundle (R4).entry.resource.Claim.item.extension (certEffectiveDate).url | uri | Required | | 1..1 | URL of the extension: http://hl7.org/fhir/us/davinci-pas/StructureDefinition/extension-itemCertificationEffectiveDate.

Bundle (R4).entry.resource.Claim.item.extension (certEffectiveDate).valueDate | date | Required | | 1..1 | Date value.

Bundle (R4).entry.resource.Claim.item.extension (certExpirationDate) (also: extension (certExpirationDate)) | Extension | Optional | Yes | 0..1 | The specific date or period within which this item's preauthorization expires. URL: http://hl7.org/fhir/us/davinci-pas/StructureDefinition/extension-itemCertificationExpirationDate

Bundle (R4).entry.resource.Claim.item.extension (certExpirationDate).url | uri | Required | | 1..1 | URL of the extension: http://hl7.org/fhir/us/davinci-pas/StructureDefinition/extension-itemCertificationExpirationDate.

Bundle (R4).entry.resource.Claim.item.extension (certExpirationDate).valueDate | date | Required | | 1..1 | Date value.

Bundle (R4).entry.resource.Claim.item.extension (certificationType) (also: extension (certificationType)) | Extension | Required | Yes | 0..1 | A code representing the type of certification being requested, equivalent to 2000F UM02 (ANSI X12 value). URL: http://hl7.org/fhir/us/davinci-pas/StructureDefinition/extension-certificationType

Bundle (R4).entry.resource.Claim.item.extension (certificationType).url | uri | Required | | 1..1 | URL of the extension: http://hl7.org/fhir/us/davinci-pas/StructureDefinition/extension-certificationType

Bundle (R4).entry.resource.Claim.item.extension (certificationType).valueCodeableConcept | CodeableConcept | Required | | 1..1 | Certification type. Must include a coding system of https://codesystem.x12.org/005010/1322.

Bundle (R4).entry.resource.Claim.item.extension (certIssueDate) (also: extension (certIssueDate)) | Extension | Optional | Yes | 0..1 | The specific date or period within when which item's preauthorization was issued. URL: http://hl7.org/fhir/us/davinci-pas/StructureDefinition/extension-itemCertificationIssueDate.

Bundle (R4).entry.resource.Claim.item.extension (certIssueDate).url | uri | Required | | 1..1 | URL of the extension: http://hl7.org/fhir/us/davinci-pas/StructureDefinition/extension-itemCertificationIssueDate.

Bundle (R4).entry.resource.Claim.item.extension (certIssueDate).valueDate | date | Required | | 1..1 | Date value.

Bundle (R4).entry.resource.Claim.item.extension (infoChanged) (also: extension (infoChanged)) | Extension | Optional | Yes | 0..1 | Only used for update message, indicates how the piece of information has changed. If the certification type is I-Initial, the code cannot be “changed”. If the certification type is S-Revision, the code cannot be “added”. If the certification type is 3-Cancel, the code cannot be “added”. URL: http://hl7.org/fhir/us/davinci-pas/StructureDefinition/extension-infoChanged

Bundle (R4).entry.resource.Claim.item.extension (infoChanged).url | uri | Required | | 1..1 | URL of the extension: http://hl7.org/fhir/us/davinci-pas/StructureDefinition/extension-infoChanged

Bundle (R4).entry.resource.Claim.item.extension (infoChanged).valueCode | code | Required | | 1..1 | Value of “changed” indicates previously sent information has been changed. Value of “added” indicates new information that was not sent previously.

Bundle (R4).entry.resource.Claim.item.extension (itemTraceNumber) (also: extension (itemTraceNumber)) | Extension | Optional | Yes | 0..* | Uniquely identifies this claim item, equivalent to 2000F TRN (ANSI X12 value). URL: http://hl7.org/fhir/us/davinci-pas/StructureDefinition/extension-itemTraceNumber

Bundle (R4).entry.resource.Claim.item.extension (itemTraceNumber).url | uri | Required | | 1..1 | URL of the extension: http://hl7.org/fhir/us/davinci-pas/StructureDefinition/extension-itemTraceNumber

Bundle (R4).entry.resource.Claim.item.extension (itemTraceNumber).valueIdentifier | Identifier | Required | | 1..1 | Trace number.

Bundle (R4).entry.resource.Claim.item.extension (itemTraceNumber).valueIdentifier.extension (subDepartment) (also: extension (subDepartment)) | Extension | Optional | Yes | 0..1 | An additional element that provides a further subdivision within the organization granting the identifier, equivalent to TRN04 (ANSI X12 value). URL: http://hl7.org/fhir/us/davinci-pas/StructureDefinition/extension-identifierSubDepartment

Bundle (R4).entry.resource.Claim.item.extension (itemTraceNumber).valueIdentifier.extension (subDepartment).url | uri | Required | | 1..1 | URL of the extension: http://hl7.org/fhir/us/davinci-pas/StructureDefinition/extension-identifierSubDepartment

Bundle (R4).entry.resource.Claim.item.extension (itemTraceNumber).valueIdentifier.extension (subDepartment).valueString | string | Required | | 1..1 | Additional reference number.

Bundle (R4).entry.resource.Claim.item.extension (itemTraceNumber).valueIdentifier.system | String | Required | | 1..1 | System of the identifier, equivalent to TRN03 (ANSI X12 value). Should use a scheme of 'urn:trnorg:<TRN03>'.

Bundle (R4).entry.resource.Claim.item.extension (itemTraceNumber).valueIdentifier.value | String | Required | | 1..1 | Value of the identifier, equivalent to TRN02 (ANSI X12 value).

Bundle (R4).entry.resource.Claim.item.extension (requestType) (also: extension (requestType)) | Extension | Optional | Yes | 0..1 | A code that identifies the type of service being requested, equivalent to 2000F UM01 (ANSI X12 value). URL: http://hl7.org/fhir/us/davinci-pas/StructureDefinition/extension-serviceItemRequestType

Bundle (R4).entry.resource.Claim.item.extension (requestType).url | uri | Required | | 1..1 | URL of the extension: http://hl7.org/fhir/us/davinci-pas/StructureDefinition/extension-serviceItemRequestType

Bundle (R4).entry.resource.Claim.item.extension (requestType).valueCodeableConcept | CodeableConcept | Required | | 1..1 | Request type. Must include a coding system of https://codesystem.x12.org/005010/1525.

Bundle (R4).entry.resource.Claim.item.extension (reviewActionCode) (also: extension (reviewActionCode)) | Extension | Optional | Yes | 0..1 | The code describing the result of the review. URL: http://hl7.org/fhir/us/davinci-pas/StructureDefinition/extension-reviewActionCode.

Bundle (R4).entry.resource.Claim.item.extension (reviewActionCode).url | uri | Required | | 1..1 | URL of the extension: http://hl7.org/fhir/us/davinci-pas/StructureDefinition/extension-reviewActionCode.

Bundle (R4).entry.resource.Claim.item.extension (reviewActionCode).valueCodeableConcept | CodeableConcept | Required | | 1..1 | Codes indicating type of action. Must include a coding system of https://codesystem.x12.org/005010/306.

Bundle (R4).entry.resource.Claim.item.informationSequence | positiveInt | Optional | Yes | 0..* | Sequence number of the related supporting information. Only sequence number of supportingInfo additionalInformation or messageText is considered.

Bundle (R4).entry.resource.Claim.item.locationCodeableConcept | CodeableConcept | Optional | | 0..1 | Place of service, equivalent to 2000F UM04. Must include one of the allowed coding systems: https://www.cms.gov/Medicare/Coding/place-of-service-codes/Place_of_Service_Code_Set. https://www.nubc.org/CodeSystem/TypeOfBill.

Bundle (R4).entry.resource.Claim.item.modifier | CodeableConcept | Optional | Yes | 0..* | Service modifiers. Must include one of the allowed coding systems: http://www.cms.gov/Medicare/Coding/HCPCSReleaseCodeSets. http://www.ama-assn.org/go/cpt. https://open.epic.com/FHIR/(custom_OID)/custom-procedure-modifier.

Bundle (R4).entry.resource.Claim.item.quantity | Quantity | Optional | | 0..1 | Requested quantity.

Bundle (R4).entry.resource.Claim.item.quantity.code | String | Required | | 1..1 | Code from the system.

Bundle (R4).entry.resource.Claim.item.quantity.system | String | Required | | 1..1 | System of the code, required to be https://codesystem.x12.org/005010/673.

Bundle (R4).entry.resource.Claim.item.quantity.value | Decimal | Required | | 1..1 | Numeric value.

Bundle (R4).entry.resource.Claim.item.revenue | CodeableConcept | Optional | | 0..1 | Revenue code. Must include a coding system of https://www.nubc.org/CodeSystem/RevenueCodes.

Bundle (R4).entry.resource.Claim.item.sequence | positiveInt | Required | | 1..1 | Sequence number of the item element.

Bundle (R4).entry.resource.Claim.item.servicedDate | date | Optional | | 0..1 | Service date.

Bundle (R4).entry.resource.Claim.item.servicedPeriod | Period | Optional | | 0..1 | Service period.

Bundle (R4).entry.resource.Claim.item.servicedPeriod.end | String | Required | | 1..1 | End dateTime.

Bundle (R4).entry.resource.Claim.item.servicedPeriod.start | String | Required | | 1..1 | Start dateTime.

Bundle (R4).entry.resource.Claim.patient | Reference | Required | | 1..1 | A reference to the beneficiary patient. Expected to match coverage.beneficiary.

Bundle (R4).entry.resource.Claim.provider | Reference | Required | | 1..1 | The provider who is responsible for the prior authorization, equivalent to Requester loop (2000B). A reference to either Organization or PractitionerRole.

Bundle (R4).entry.resource.Claim.status | code | Required | | 1..1 | Status of the Claim resource, required to be “active”.

Bundle (R4).entry.resource.Claim.supportingInfo (admissionDates) (also: supportingInfo (admissionDates)) | BackboneElement | Optional | Yes | 0..1 | Admission dates of a hospital admission being requested.

Bundle (R4).entry.resource.Claim.supportingInfo (admissionDates).category | CodeableConcept | Required | | 1..1 | Must include a coding system of http://hl7.org/fhir/us/davinci-pas/CodeSystem/PASTempCodes. The code must be "admissionDates".

Bundle (R4).entry.resource.Claim.supportingInfo (admissionDates).timingDate | date | Optional | | 0..1 | Admission date.

Bundle (R4).entry.resource.Claim.supportingInfo (admissionDates).timingPeriod | Period | Conditional | | 0..1 | The admission period. This is required if timingDate is absent and is not used if timingDate is present.

Bundle (R4).entry.resource.Claim.supportingInfo (admissionDates).timingPeriod.end | String | Required | | 1..1 | End dateTime.

Bundle (R4).entry.resource.Claim.supportingInfo (admissionDates).timingPeriod.start | String | Required | | 1..1 | Start dateTime.

Bundle (R4).entry.resource.Claim.supportingInfo (dischargeDates) (also: supportingInfo (dischargeDates)) | BackboneElement | Optional | Yes | 0..1 | Discharge dates of a hospital admission being requested.

Bundle (R4).entry.resource.Claim.supportingInfo (dischargeDates).category | CodeableConcept | Required | | 1..1 | Must include a coding system of http://hl7.org/fhir/us/davinci-pas/CodeSystem/PASTempCodes. The code must be "dischargeDates"

Bundle (R4).entry.resource.Claim.supportingInfo (dischargeDates).timingDate | date | Required | | 1..1 | Discharge date.

Bundle (R4).entry.resource.Claim.supportingInfo (patientEvent) (also: supportingInfo (patientEvent)) | BackboneElement | Optional | Yes | 0..1 | Event dates being requested.

Bundle (R4).entry.resource.Claim.supportingInfo (patientEvent).category | CodeableConcept | Required | | 1..1 | Must include a coding system of http://hl7.org/fhir/us/davinci-pas/CodeSystem/PASTempCodes. The code must be "patientEvent".

Bundle (R4).entry.resource.Claim.supportingInfo (patientEvent).timingDate | date | Optional | | 0..1 | Patient Event Date.

Bundle (R4).entry.resource.Claim.supportingInfo (patientEvent).timingPeriod | Period | Conditional | | 0..1 | The patient event period. This is required if timingDate is absent and is not used if timingDate is present.

Bundle (R4).entry.resource.Claim.supportingInfo (patientEvent).timingPeriod.end | String | Required | | 1..1 | End dateTime.

Bundle (R4).entry.resource.Claim.supportingInfo (patientEvent).timingPeriod.start | String | Required | | 1..1 | Start dateTime.

Bundle (R4).entry.resource.Claim.type | CodeableConcept | Required | | 1..1 | The type of claim. Must include a coding system of http://terminology.hl7.org/CodeSystem/claim-type.

Bundle (R4).entry.resource.Claim.use | code | Required | | 1..1 | The purpose of the claim, required to be “preauthorization”.

Bundle (R4).entry.resource.Coverage | Resource | Required | | 1..* | Coverage resource.

Bundle (R4).entry.resource.Coverage.beneficiary | Reference | Required | | 1..1 | Reference to beneficiary, a Patient resource.

Bundle (R4).entry.resource.Coverage.class (group) (also: class (group)) | BackboneElement | Optional | Yes | 0..1 | Group class.

Bundle (R4).entry.resource.Coverage.class (group).type | CodeableConcept | Required | | 1..1 | Code must be "group". System must be http://terminology.hl7.org/CodeSystem/coverage-class.

Bundle (R4).entry.resource.Coverage.class (group).value | string | Required | | 1..1 | Group ID.

Bundle (R4).entry.resource.Coverage.class (plan) (also: class (plan)) | BackboneElement | Optional | Yes | 0..1 | Plan Class.

Bundle (R4).entry.resource.Coverage.class (plan).type | CodeableConcept | Required | | 1..1 | Code must be "plan". System must be http://terminology.hl7.org/CodeSystem/coverage-class.

Bundle (R4).entry.resource.Coverage.class (plan).value | string | Required | | 1..1 | Plan ID.

Bundle (R4).entry.resource.Coverage.dependent | string | Optional | | 0..1 | A unique member number for the dependent on the coverage.

Bundle (R4).entry.resource.Coverage.identifier (memberId) (also: identifier (memberId)) | Identifier | Optional | Yes | 0..* | Member ID.

Bundle (R4).entry.resource.Coverage.identifier (memberId).type | CodeableConcept | Required | | 1..1 | Identifier type. Must include a coding system of http://terminology.hl7.org/CodeSystem/v2-0203, and the code must be “MB”.

Bundle (R4).entry.resource.Coverage.identifier (memberId).value | String | Optional | | 0..1 | Identifier value.

Bundle (R4).entry.resource.Coverage.payor | Reference | Required | Yes | 1..1 | Reference to insurer Organization resource. Payor reference must be the same as Claim.insurer.

Bundle (R4).entry.resource.Coverage.relationship | CodeableConcept | Required | | 1..1 | Beneficiary relationship to the subscriber. Must include one of the allowed coding systems: https://codesystem.x12.org/005010/1069. http://terminology.hl7.org/CodeSystem/subscriber-relationship.

Bundle (R4).entry.resource.Coverage.subscriber | Reference | Optional | | 0..1 | Reference to subscriber.

Bundle (R4).entry.resource.Coverage.subscriberId | string | Optional | | 0..1 | Subscriber ID.

Bundle (R4).entry.resource.Location | Resource | Optional | | 0..* | Location resource.

Bundle (R4).entry.resource.Location.address | Address | Optional | | 0..* | Address.

Bundle (R4).entry.resource.Location.address.city | string | Optional | | 0..1 | Name of city, town, and so on.

Bundle (R4).entry.resource.Location.address.line | string | Optional | Yes | 0..2 | Street name, number, direction, P.O. Box, and so on.

Bundle (R4).entry.resource.Location.address.postalCode | string | Optional | | 0..1 | US ZIP codes.

Bundle (R4).entry.resource.Location.address.use | code | Optional | | 0..1 | The purpose of this address. This is used to determine the priority of the identifier. Values of “billing” and “work” have higher priority than the rest of the values. The highest priority of the address gets used.

Bundle (R4).entry.resource.Location.identifier | Identifier | Optional | Yes | 0..* | Identifier.

Bundle (R4).entry.resource.Location.identifier.system | String | Required | | 1..1 | The system for the identifier value. Supported systems: http://terminology.hl7.org/NamingSystem/USEIN (TIN). http://hl7.org/fhir/sid/us-npi (NPI).

Bundle (R4).entry.resource.Location.identifier.use | String | Optional | | 0..1 | The purpose of this identifier. This is used to determine the priority of the identifier. Values of “official” and “usual” have higher priority than the rest of the values. The highest priority of the same identity type gets used.

Bundle (R4).entry.resource.Location.identifier.value | String | Required | | 1..1 | Identifier value that is unique within the system.

Bundle (R4).entry.resource.Location.name | string | Required | | 1..1 | Name.

Bundle (R4).entry.resource.Location.status | code | Required | | 1..1 | Location status. Required to be active.

Bundle (R4).entry.resource.Location.telecom | ContactPoint | Optional | Yes | 0..* | Contact details.

Bundle (R4).entry.resource.Location.telecom.rank | positiveInt | Optional | | 0..1 | Specifies a preferred order in which to use the set of contacts. Higher rank of the same contact system gets used. If the rank is the same, then the higher use priority gets used.

Bundle (R4).entry.resource.Location.telecom.system | code | Optional | | 0..1 | Form of communication. Supported values: phone, fax, email.

Bundle (R4).entry.resource.Location.telecom.use | code | Optional | | 0..1 | The purpose of this contact point. This is used to determine the priority of the identifier. Values of “work” and “mobile” have higher priority than the rest of the values. The highest priority of the same contact system gets used.

Bundle (R4).entry.resource.Location.telecom.value | string | Optional | | 0..1 | The actual contact point details, in a form that is meaningful to the designated communication system (for example, phone number or email address).

Bundle (R4).entry.resource.Organization | Resource | Optional | | 0..* | Organization resource.

Bundle (R4).entry.resource.Organization.address | Address | Optional | Yes | 0..* | Address.

Bundle (R4).entry.resource.Organization.address.city | string | Optional | | 0..1 | Name of city, town, and so on.

Bundle (R4).entry.resource.Organization.address.line | string | Optional | Yes | 0..2 | Street name, number, direction, P.O. Box, and so on.

Bundle (R4).entry.resource.Organization.address.postalCode | string | Optional | | 0..1 | US ZIP codes.

Bundle (R4).entry.resource.Organization.address.state | string | Optional | | 0..1 | US state 2 letter abbreviation. Value set: http://hl7.org/fhir/us/core/STU7/ValueSet-us-core-usps-state.html.

Bundle (R4).entry.resource.Organization.address.use | code | Optional | | 0..1 | The purpose of this address. This is used to determine the priority of the identifier. Values of “billing” and “work” have higher priority than the rest of the values. The highest priority of the address gets used.

Bundle (R4).entry.resource.Organization.contact | BackboneElement | Optional | Yes | 0..* | Contact information. For Organization, only the contact name information is used.

Bundle (R4).entry.resource.Organization.identifier | Identifier | Optional | Yes | 0..* | All identifiers. Payer identifier is only used for Claim.Insurer/ClaimResponse.insurer.

Bundle (R4).entry.resource.Organization.identifier.system | String | Required | | 1..1 | The namespace for the identifier value. Supported systems: http://terminology.hl7.org/NamingSystem/USEIN (TIN). http://hl7.org/fhir/sid/us-npi (NPI).

Bundle (R4).entry.resource.Organization.identifier.type | CodeableConcept | Required | | 1..1 | Identifier type. Only required for payer identifier slice. Must include a coding system of http://hl7.org/fhir/us/carin-bb/CodeSystem/C4BBIdentifierType, and code is “payerid”.

Bundle (R4).entry.resource.Organization.identifier.use | String | Optional | | 0..1 | The purpose of this identifier. This is used to determine the priority of the identifier. Values of “official” and “usual” have higher priority than the rest of the values. The highest priority of the same identity type gets used.

Bundle (R4).entry.resource.Organization.identifier.value | String | Optional | | 0..1 | Identifier value that is unique within the system.

Bundle (R4).entry.resource.Organization.name | string | Required | | 1..1 | Name.

Bundle (R4).entry.resource.Organization.telecom | ContactPoint | Optional | Yes | 0..* | Contact details.

Bundle (R4).entry.resource.Organization.telecom.rank | positiveInt | Optional | | 0..1 | Specifies a preferred order in which to use the set of contacts. Higher rank of the same contact system gets used. If the rank is the same, then the higher use priority gets used.

Bundle (R4).entry.resource.Organization.telecom.system | code | Optional | | 0..1 | Form of communication. Supported values: phone, fax, email.

Bundle (R4).entry.resource.Organization.telecom.use | code | Optional | | 0..1 | The purpose of this contact point. This is used to determine the priority of the identifier. Values of “work” and “mobile” have higher priority than the rest of the values. The highest priority of the same contact system gets used.

Bundle (R4).entry.resource.Organization.telecom.value | string | Optional | | 0..1 | The actual contact point details, in a form that is meaningful to the designated communication system (for example, phone number or email address).

Bundle (R4).entry.resource.Organization.type | CodeableConcept | Optional | Yes | 0..* | It is only supported for insurer and requestor. Must include a coding system of https://codesystem.x12.org/005010/98. For Claim.Insurer, the code must be one of the following: 2B, 36, PR, X3.

Bundle (R4).entry.resource.Patient | Resource | Optional | | 0..* | Patient resource.

Bundle (R4).entry.resource.Patient.address | Address | Optional | Yes | 0..* | Address.

Bundle (R4).entry.resource.Patient.address.city | string | Optional | | 0..1 | Name of city, town, and so on.

Bundle (R4).entry.resource.Patient.address.line | string | Optional | Yes | 0..2 | Street name, number, direction, P.O. Box, and so on.

Bundle (R4).entry.resource.Patient.address.postalCode | string | Optional | | 0..1 | US ZIP codes.

Bundle (R4).entry.resource.Patient.address.state | string | Optional | | 0..1 | US state 2 letter abbreviation. Value set: http://hl7.org/fhir/us/core/STU7/ValueSet-us-core-usps-state.html.

Bundle (R4).entry.resource.Patient.address.use | code | Optional | | 0..1 | The purpose of this address. This is used to determine the priority of the identifier. Values of “home”, “billing”, and “work” have higher priority than the rest of the values. The highest priority of the address gets used.

Bundle (R4).entry.resource.Patient.birthDate | date | Optional | | 0..1 | Birth date.

Bundle (R4).entry.resource.Patient.gender | code | Required | | 1..1 | Gender. Code: male | female | other | unknown.

Bundle (R4).entry.resource.Patient.identifier | Identifier | Optional | Yes | 0..* | All Identifiers.

Bundle (R4).entry.resource.Patient.identifier.system | String | Required | | 1..1 | The system for the identifier value. Supported systems: urn:oid:2.16.840.1.113883.4.1 (SSN) http://open.epic.com/FHIR/StructureDefinition/member-id (Member ID) Other OID or URN that are mapped in internal system. (Identity ID).

Bundle (R4).entry.resource.Patient.identifier.type | CodeableConcept | Required | | 1..1 | Identifier type. Only required for the member ID slice. Must include a coding system of http://terminology.hl7.org/CodeSystem/v2-0203, and code must be “MB”.

Bundle (R4).entry.resource.Patient.identifier.use | String | Optional | | 0..1 | The purpose of this identifier. This is used to determine the priority of the identifier. Values of “official” and “usual” have higher priority than the rest of the values. The highest priority of the same identity type gets used.

Bundle (R4).entry.resource.Patient.identifier.value | String | Required | | 1..1 | Identifier value that is unique within the system.

Bundle (R4).entry.resource.Patient.name | HumanName | Required | Yes | 1..* | Human name.

Bundle (R4).entry.resource.Patient.name.family | string | Optional | | 0..1 | Family name (surname).

Bundle (R4).entry.resource.Patient.name.given | string | Optional | Yes | 0..* | Given name (includes middle name).

Bundle (R4).entry.resource.Patient.name.suffix | string | Optional | Yes | 0..* | Suffix.

Bundle (R4).entry.resource.Patient.name.use | code | Optional | | 0..1 | The purpose of this name. This is used to determine the priority of the identifier. Values of “official” and “usual” have higher priority than the rest of the values. The highest priority of the name gets used.

Bundle (R4).entry.resource.Patient.telecom | ContactPoint | Optional | Yes | 0..* | Contact details.

Bundle (R4).entry.resource.Patient.telecom.rank | positiveInt | Optional | | 0..1 | Specifies a preferred order in which to use the set of contacts. Higher rank of the same contact system gets used. If the rank is the same, then the higher use priority gets used.

Bundle (R4).entry.resource.Patient.telecom.system | code | Optional | | 0..1 | Form of communication. Supported values: phone, fax, email.

Bundle (R4).entry.resource.Patient.telecom.use | code | Optional | | 0..1 | The purpose of this contact point. This is used to determine the priority of the identifier. Values of “home,” “work” and “mobile” have higher priority than the rest of the values. The highest priority of the same contact system gets used.

Bundle (R4).entry.resource.Patient.telecom.value | string | Optional | | 0..1 | The actual contact point details, in a form that is meaningful to the designated communication system (for example, phone number or email address).

Bundle (R4).entry.resource.Practitioner | Resource | Optional | | 0..* | Practitioner resource.

Bundle (R4).entry.resource.Practitioner.address | Address | Required | Yes | 0..* | Address.

Bundle (R4).entry.resource.Practitioner.address.city | string | Optional | | 0..1 | Name of city, town, and so on.

Bundle (R4).entry.resource.Practitioner.address.line | string | Optional | Yes | 0..2 | Street name, number, direction & P.O. Box, and so on.

Bundle (R4).entry.resource.Practitioner.address.postalCode | string | Optional | | 0..1 | US ZIP codes.

Bundle (R4).entry.resource.Practitioner.address.state | string | Optional | | 0..1 | US state 2 letter abbreviation. Value set: http://hl7.org/fhir/us/core/STU7/ValueSet-us-core-usps-state.html.

Bundle (R4).entry.resource.Practitioner.address.use | code | Optional | | 0..1 | The purpose of this address. This is used to determine the priority of the identifier. Values of “billing” and “work” have higher priority than the rest of the values. The highest priority of the address gets used.

Bundle (R4).entry.resource.Practitioner.identifier | Identifier | Optional | Yes | 0..* | Identifier.

Bundle (R4).entry.resource.Practitioner.identifier.system | String | Required | | 1..1 | The system for the identifier value. Supported systems: http://terminology.hl7.org/NamingSystem/USEIN (TIN). http://hl7.org/fhir/sid/us-npi (NPI).

Bundle (R4).entry.resource.Practitioner.identifier.use | String | Optional | | 0..1 | The purpose of this identifier. This is used to determine the priority of the identifier. Values of “official” and “usual” have higher priority than the rest of the values. The highest priority of the same identity type gets used.

Bundle (R4).entry.resource.Practitioner.identifier.value | String | Required | | 1..1 | Identifier value.

Bundle (R4).entry.resource.Practitioner.name | HumanName | Required | Yes | 1..* | Name.

Bundle (R4).entry.resource.Practitioner.name.family | string | Optional | | 0..1 | Family name (surname).

Bundle (R4).entry.resource.Practitioner.name.given | string | Optional | Yes | 0..* | Given name (includes middle name).

Bundle (R4).entry.resource.Practitioner.name.suffix | string | Optional | Yes | 0..* | Suffix.

Bundle (R4).entry.resource.Practitioner.name.use | code | Optional | | 0..1 | The purpose of this name. This is used to determine the priority of the identifier. Values of “official” and “usual” have higher priority than the rest of the values. The highest priority of the name gets used.

Bundle (R4).entry.resource.Practitioner.telecom | ContactPoint | Optional | Yes | 0..* | Contact details.

Bundle (R4).entry.resource.Practitioner.telecom.rank | positiveInt | Optional | | 0..1 | Specifies a preferred order in which to use the set of contacts. Higher rank of the same contact system gets used. If the rank is the same, then the higher use priority gets used.

Bundle (R4).entry.resource.Practitioner.telecom.system | code | Optional | | 0..1 | Form of communication. Supported values: phone, fax, email.

Bundle (R4).entry.resource.Practitioner.telecom.use | code | Optional | | 0..1 | The purpose of this contact point. This is used to determine the priority of the identifier. Values of “work” and “mobile” have higher priority than the rest of the values. The highest priority of the same contact system gets used.

Bundle (R4).entry.resource.Practitioner.telecom.value | string | Optional | | 0..1 | The actual contact point details, in a form that is meaningful to the designated communication system (for example, phone number or email address).

Bundle (R4).entry.resource.PractitionerRole | Resource | Optional | | 0..* | PractitionerRole resource.

Bundle (R4).entry.resource.PractitionerRole.location | Reference | Optional | Yes | 0..1 | A reference to a Location resource. The location where the practitioner performs the roles associated.

Bundle (R4).entry.resource.PractitionerRole.organization | Reference | Optional | | 0..1 | A reference to an Organization resource. The organization where the practitioner performs the roles associated.

Bundle (R4).entry.resource.PractitionerRole.practitioner | Reference | Required | | 1..1 | A reference to a Practitioner resource. Practitioner that can provide the defined services for the organization.

Bundle (R4).entry.resource.PractitionerRole.telecom | ContactPoint | Optional | Yes | 0..* | Contact details.

Bundle (R4).entry.resource.PractitionerRole.telecom.rank | positiveInt | Optional | | 0..1 | Specifies a preferred order in which to use the set of contacts. Higher rank of the same contact system gets used. If the rank is the same, then the higher use priority gets used.

Bundle (R4).entry.resource.PractitionerRole.telecom.system | code | Optional | | 0..1 | Form of communication. Supported values: phone, fax, email

Bundle (R4).entry.resource.PractitionerRole.telecom.use | code | Optional | | 0..1 | The purpose of this contact point. This is used to determine the priority of the identifier. Values of “work” and “mobile” have higher priority than the rest of the values. The highest priority of the same contact system gets used.

Bundle (R4).entry.resource.PractitionerRole.telecom.value | string | Optional | | 0..1 | The actual contact point details, in a form that is meaningful to the designated communication system (for example, phone number or email address).

Bundle (R4).id | id | Optional | | 0..1 | Logical ID of the bundle.

Bundle (R4).identifier | Identifier | Optional | | 0..1 | Submitted Transaction Identifier - this number is assigned by the originator or sender to identify the transaction within the sender's business application system.

Bundle (R4).meta | Meta | Optional | | 0..* | Metadata about the resource.

Bundle (R4).meta.security | Coding | Optional | Yes | 0..1 | When received code is SUBSETTED, the system stops processing the submitted claim and returns an error.

Bundle (R4).timestamp | instant | Optional | | 0..1 | When the Bundle was assembled.

Bundle (R4).type | code | Required | | 1..1 | Purpose of the Bundle. Required to be “collection”.

Response elements

Name | Type | Optional | Array | Cardinality | Description

Bundle (R4) | Bundle | Required | | 1..1 | Bundle resource.

Bundle (R4).entry | BackboneElement | Required | Yes | 1..* | Entries in the bundle – each entry contains a resource. Each authorization is represented as one ClaimResponse resource. Resources referenced by the ClaimResponse resource are included in the bundle. Resources that can be sent: ClaimResponse, Patient, Practitioner, PractitionerRole, Organization, and ServiceRequest.

Bundle (R4).entry.fullUrl | uri | Required | | 1..1 | URI for the resource (Absolute URL server address or URI for UUID/OID).

Bundle (R4).entry.link | BackboneElement | Optional | Yes | 0..* | Provides additional context or references related to the entry.

Bundle (R4).entry.link.relation | string | Required | | 1..1 | Purpose of the link. Sent as self.

Bundle (R4).entry.link.url | uri | Required | | 1..1 | Reference details for the link. Contains the same value as entry.fullUrl.

Bundle (R4).entry.resource | ResourceContainer | Required | | 1..1 | A resource in the bundle.

Bundle (R4).entry.resource.ClaimResponse | Resource | Required | | 1..* | ClaimResponse resource.

Bundle (R4).entry.resource.ClaimResponse.addItem | BackboneElement | Optional | Yes | 0..* | Insurer added line items.

Bundle (R4).entry.resource.ClaimResponse.addItem.adjudication | BackboneElement | Required | Yes | 1..1 | Adjudication for insurer added items.

Bundle (R4).entry.resource.ClaimResponse.addItem.adjudication.category | CodeableConcept | Required | | 1..1 | Adjudication category. The coding system is http://terminology.hl7.org/CodeSystem/adjudication. The returned code is always “submitted”.

Bundle (R4).entry.resource.ClaimResponse.addItem.adjudication.extension (reviewAction) (also: extension (reviewAction)) | Extension | Optional | Yes | 0..1 | The details of the review action that are necessary for the authorization, equivalent to 2000F HCR (ANSI X12 value). URL: http://hl7.org/fhir/us/davinci-pas/StructureDefinition/extension-reviewAction

Bundle (R4).entry.resource.ClaimResponse.addItem.adjudication.extension (reviewAction).extension (number) (also: extension (number)) | Extension | Optional | Yes | 0..1 | Review number, equivalent to 2000F HCR02 (ANSI X12 value). URL: number

Bundle (R4).entry.resource.ClaimResponse.addItem.adjudication.extension (reviewAction).extension (number).url | uri | Required | | 1..1 | URL of the extension: number

Bundle (R4).entry.resource.ClaimResponse.addItem.adjudication.extension (reviewAction).extension (number).valueString | string | Required | | 1..1 | Review number value.

Bundle (R4).entry.resource.ClaimResponse.addItem.adjudication.extension (reviewAction).extension (reasonCode) (also: extension (reasonCode)) | Extension | Optional | Yes | 0..1 | Certification action code: indicates the reason for the approved, denied, pended, or other services, equivalent to 2000F HCR03 (ANSI X12 value). URL: reasonCode

Bundle (R4).entry.resource.ClaimResponse.addItem.adjudication.extension (reviewAction).extension (reasonCode).url | uri | Required | | 1..1 | URL for the extension: reasonCode

Bundle (R4).entry.resource.ClaimResponse.addItem.adjudication.extension (reviewAction).extension (reasonCode).valueCodeableConcept | CodeableConcept | Required | | 1..1 | Reason code value. It has a code system of https://codesystem.x12.org/external/886.

Bundle (R4).entry.resource.ClaimResponse.addItem.adjudication.extension (reviewAction).extension (reviewActionCode) (also: extension (reviewActionCode)) | Extension | Optional | Yes | 0..1 | Code for the review action, equivalent to 2000F HCR01 (ANSI X12 value). URL: http://hl7.org/fhir/us/davinci-pas/StructureDefinition/extension-reviewActionCode

Bundle (R4).entry.resource.ClaimResponse.addItem.adjudication.extension (reviewAction).extension (reviewActionCode).url | uri | Required | | 1..1 | URL of the extension: http://hl7.org/fhir/us/davinci-pas/StructureDefinition/extension-reviewActionCode

Bundle (R4).entry.resource.ClaimResponse.addItem.adjudication.extension (reviewAction).extension (reviewActionCode).valueCodeableConcept | CodeableConcept | Required | | 1..1 | Review action code for the adjudication. It has a code system of https://codesystem.x12.org/005010/306.

Bundle (R4).entry.resource.ClaimResponse.addItem.adjudication.extension (reviewAction).url | uri | Required | | 1..1 | URL of the extension: http://hl7.org/fhir/us/davinci-pas/StructureDefinition/extension-reviewAction

Bundle (R4).entry.resource.ClaimResponse.addItem.extension (administrationReferenceNumber) (also: extension (administrationReferenceNumber)) | Extension | Optional | Yes | 0..1 | A string assigned by the payer to the original disallowed review outcome associated with this service item, equivalent to 2000F REF*NT (ANSI X12 value). URL: http://hl7.org/fhir/us/davinci-pas/StructureDefinition/extension-administrationReferenceNumber

Bundle (R4).entry.resource.ClaimResponse.addItem.extension (administrationReferenceNumber).url | uri | Required | | 1..1 | URL of the extension: http://hl7.org/fhir/us/davinci-pas/StructureDefinition/extension-administrationReferenceNumber

Bundle (R4).entry.resource.ClaimResponse.addItem.extension (administrationReferenceNumber).valueString | string | Required | | 1..1 | Administrative reference number.

Bundle (R4).entry.resource.ClaimResponse.addItem.extension (itemTraceNumber) (also: extension (itemTraceNumber)) | Extension | Optional | Yes | 0..* | Uniquely identifies this claim item, equivalent to 2000F TRN (ANSI X12 value). URL: http://hl7.org/fhir/us/davinci-pas/StructureDefinition/extension-itemTraceNumber

Bundle (R4).entry.resource.ClaimResponse.addItem.extension (itemTraceNumber).url | uri | Required | | 1..1 | URL of the extension: http://hl7.org/fhir/us/davinci-pas/StructureDefinition/extension-itemTraceNumber

Bundle (R4).entry.resource.ClaimResponse.addItem.extension (itemTraceNumber).valueIdentifier | Identifier | Optional | | 0..1 | Trace number.

Bundle (R4).entry.resource.ClaimResponse.addItem.extension (itemTraceNumber).valueIdentifier.extension (subDepartment) (also: extension (subDepartment)) | Extension | Optional | Yes | 0..1 | An additional element that provides a further subdivision within the organization granting the identifier, equivalent to TRN04 (ANSI X12 value). URL: http://hl7.org/fhir/us/davinci-pas/StructureDefinition/extension-identifierSubDepartment

Bundle (R4).entry.resource.ClaimResponse.addItem.extension (itemTraceNumber).valueIdentifier.extension (subDepartment).url | uri | Required | | 1..1 | URL of the extension: http://hl7.org/fhir/us/davinci-pas/StructureDefinition/extension-identifierSubDepartment

Bundle (R4).entry.resource.ClaimResponse.addItem.extension (itemTraceNumber).valueIdentifier.extension (subDepartment).valueString | string | Required | | 1..1 | Additional reference number.

Bundle (R4).entry.resource.ClaimResponse.addItem.extension (itemTraceNumber).valueIdentifier.system | String | Required | | 1..1 | System of the identifier, equivalent to TRN03 (ANSI X12 value). Uses a scheme of 'urn:trnorg:<TRN03>'.

Bundle (R4).entry.resource.ClaimResponse.addItem.extension (itemTraceNumber).valueIdentifier.value | String | Required | | 1..1 | Value of the identifier, equivalent to TRN02 (ANSI X12 value).

Bundle (R4).entry.resource.ClaimResponse.addItem.extension (preAuthIssueDate) (also: extension (preAuthIssueDate)) | Extension | Optional | Yes | 0..1 | The date when this item's preauthorization was issued. URL: http://hl7.org/fhir/us/davinci-pas/StructureDefinition/extension-itemPreAuthIssueDate

Bundle (R4).entry.resource.ClaimResponse.addItem.extension (preAuthIssueDate).url | uri | Required | | 1..1 | URL of the extension: http://hl7.org/fhir/us/davinci-pas/StructureDefinition/extension-itemPreAuthIssueDate

Bundle (R4).entry.resource.ClaimResponse.addItem.extension (preAuthIssueDate).valueDate | date | Required | | 1..1 | The date when this item's preauthorization was issued.

Bundle (R4).entry.resource.ClaimResponse.addItem.extension (preAuthPeriod) (also: extension (preAuthPeriod)) | Extension | Optional | Yes | 0..1 | The date/period when this item's preauthorization is valid. URL: http://hl7.org/fhir/us/davinci-pas/StructureDefinition/extension-itemPreAuthPeriod

Bundle (R4).entry.resource.ClaimResponse.addItem.extension (preAuthPeriod).url | uri | Required | | 1..1 | URL of the extension: http://hl7.org/fhir/us/davinci-pas/StructureDefinition/extension-itemPreAuthPeriod

Bundle (R4).entry.resource.ClaimResponse.addItem.extension (preAuthPeriod).valuePeriod | Period | Required | | 1..1 | The period when this item's preauthorization is valid.

Bundle (R4).entry.resource.ClaimResponse.addItem.extension (preAuthPeriod).valuePeriod.end | String | Required | | 1..1 | Preauthorization end date.

Bundle (R4).entry.resource.ClaimResponse.addItem.extension (preAuthPeriod).valuePeriod.start | String | Required | | 1..1 | Preauthorization start date.

Bundle (R4).entry.resource.ClaimResponse.addItem.extension (previousAuthorizationNumber) (also: extension (previousAuthorizationNumber)) | Extension | Optional | Yes | 0..1 | A string assigned by the payer to an authorized review outcome associated with this service item, equivalent to 2000F REF*BB (ANSI X12 value). URL: http://hl7.org/fhir/us/davinci-pas/StructureDefinition/extension-authorizationNumber

Bundle (R4).entry.resource.ClaimResponse.addItem.extension (previousAuthorizationNumber).url | uri | Required | | 1..1 | URL of the extension: http://hl7.org/fhir/us/davinci-pas/StructureDefinition/extension-authorizationNumber

Bundle (R4).entry.resource.ClaimResponse.addItem.extension (previousAuthorizationNumber).valueString | string | Required | | 1..1 | A string assigned by the payer to an authorized review outcome associated with this service item.

Bundle (R4).entry.resource.ClaimResponse.addItem.extension (requestedService) (also: extension (requestedService)) | Extension | Optional | Yes | 0..1 | The ServiceRequest that contains the recurring quantity details of what has been requested for this addItem. If not recurring, addItem.quantity is sent instead. URL: http://hl7.org/fhir/us/davinci-pas/StructureDefinition/extension-requestedService

Bundle (R4).entry.resource.ClaimResponse.addItem.extension (requestedService).url | uri | Required | | 1..1 | URL of the extension: http://hl7.org/fhir/us/davinci-pas/StructureDefinition/extension-requestedService

Bundle (R4).entry.resource.ClaimResponse.addItem.extension (requestedService).valueReference | Reference | Required | | 1..1 | Reference to authorized service. A reference to ServiceRequest resource.

Bundle (R4).entry.resource.ClaimResponse.addItem.extension (revenue) (also: extension (revenue)) | Extension | Optional | Yes | 0..1 | Revenue code of the added service. URL: http://hl7.org/fhir/us/davinci-pas/StructureDefinition/extension-revenueCode

Bundle (R4).entry.resource.ClaimResponse.addItem.extension (revenue).url | uri | Required | | 1..1 | URL of the extension: http://hl7.org/fhir/us/davinci-pas/StructureDefinition/extension-revenueCode

Bundle (R4).entry.resource.ClaimResponse.addItem.extension (revenue).valueCodeableConcept | CodeableConcept | Required | | 1..1 | Revenue code of the added service. It has a coding system of https://www.nubc.org/CodeSystem/RevenueCodes.

Bundle (R4).entry.resource.ClaimResponse.addItem.itemSequence | positiveInt | Required | Yes | 1..1 | Item sequence number.

Bundle (R4).entry.resource.ClaimResponse.addItem.modifier | CodeableConcept | Optional | Yes | 0..* | Service modifier. Coding system (depending on the type of modifier): http://www.ama-assn.org/go/cpt http://www.cms.gov/Medicare/Coding/HCPCSReleaseCodeSets https://open.epic.com/FHIR/(custom_OID)/custom-procedure-modifier

Bundle (R4).entry.resource.ClaimResponse.addItem.noteNumber | positiveInt | Optional | Yes | 0..* | Applicable note numbers.

Bundle (R4).entry.resource.ClaimResponse.addItem.productOrService | CodeableConcept | Required | | 1..1 | Service code. Coding system (depending on the type of service): http://www.ama-assn.org/go/cpt http://www.cms.gov/Medicare/Coding/HCPCSReleaseCodeSets

Bundle (R4).entry.resource.ClaimResponse.addItem.provider | Reference | Optional | Yes | 0..* | Authorized provider. A reference to Practitioner or Organization resource.

Bundle (R4).entry.resource.ClaimResponse.addItem.provider.extension (providerType) (also: extension (providerType)) | Extension | Optional | Yes | 0..1 | Authorized Provider Type. URL: http://hl7.org/fhir/us/davinci-pas/StructureDefinition/extension-authorizedProviderType

Bundle (R4).entry.resource.ClaimResponse.addItem.provider.extension (providerType).url | uri | Required | | 1..1 | URL of the extension: http://hl7.org/fhir/us/davinci-pas/StructureDefinition/extension-authorizedProviderType

Bundle (R4).entry.resource.ClaimResponse.addItem.provider.extension (providerType).valueCodeableConcept | CodeableConcept | Required | | 1..1 | Provider type value. It has a coding system of https://codesystem.x12.org/005010/98.

Bundle (R4).entry.resource.ClaimResponse.addItem.quantity | Quantity | Optional | | 0..1 | The non-recurring quantity details of what has been requested for this addItem. If recurring, addItem.extension:requestedService is sent instead.

Bundle (R4).entry.resource.ClaimResponse.addItem.quantity.code | String | Required | | 1..1 | Coded form of the unit.

Bundle (R4).entry.resource.ClaimResponse.addItem.quantity.system | String | Required | | 1..1 | System that defines coded unit form. It has a system of https://codesystem.x12.org/005010/673.

Bundle (R4).entry.resource.ClaimResponse.addItem.quantity.value | Decimal | Required | | 1..1 | Quantity value.

Bundle (R4).entry.resource.ClaimResponse.addItem.servicedDate | date | Optional | | 0..1 | For date of service or product delivery. If it has a range of date, it uses servicedPeriod instead.

Bundle (R4).entry.resource.ClaimResponse.addItem.servicedPeriod | Period | Optional | | 0..1 | For range of dates of service or product delivery. If it only has a single date, it uses serviceDate instead.

Bundle (R4).entry.resource.ClaimResponse.created | dateTime | Required | | 1..1 | Response creation date.

Bundle (R4).entry.resource.ClaimResponse.error | BackboneElement | Optional | Yes | 0..* | Errors with the authorization request.

Bundle (R4).entry.resource.ClaimResponse.error.code | CodeableConcept | Required | | 1..1 | Error code detailing processing issues with, equivalent to AAA03 (ANSI X12 value). It has a coding system of https://codesystem.x12.org/005010/901.

Bundle (R4).entry.resource.ClaimResponse.error.extension (errorElement) (also: extension (errorElement)) | Extension | Required | Yes | 1..1 | The specific X12 loop, segment, or element that this error information is about. URL: http://hl7.org/fhir/us/davinci-pas/StructureDefinition/extension-errorElement

Bundle (R4).entry.resource.ClaimResponse.error.extension (errorElement).url | uri | Required | | 1..1 | URL of the extension: http://hl7.org/fhir/us/davinci-pas/StructureDefinition/extension-errorElement

Bundle (R4).entry.resource.ClaimResponse.error.extension (errorElement).valueString | string | Required | | 1..1 | The specific X12 loop, segment, or element that this error information is about.

Bundle (R4).entry.resource.ClaimResponse.error.extension (errorPath) (also: extension (errorPath)) | Extension | Optional | Yes | 0..1 | The FHIR path expression that indicates which FHIR element that this error information is about. URL: http://hl7.org/fhir/us/davinci-pas/StructureDefinition/extension-errorPath

Bundle (R4).entry.resource.ClaimResponse.error.extension (errorPath).url | uri | Required | | 1..1 | URL of the extension: http://hl7.org/fhir/us/davinci-pas/StructureDefinition/extension-errorPath

Bundle (R4).entry.resource.ClaimResponse.error.extension (errorPath).valueString | string | Required | | 1..1 | The FHIR path expression that indicates which FHIR element that this error information is about. For example: "Bundle.entry[1].Claim.type.coding[1].code"

Bundle (R4).entry.resource.ClaimResponse.error.extension (followupAction) (also: extension (followupAction)) | Extension | Required | Yes | 1..1 | A code representing what action must occur to resolve this error, equivalent to AAA04 (ANSI X12 value). URL: http://hl7.org/fhir/us/davinci-pas/StructureDefinition/extension-errorFollowupAction

Bundle (R4).entry.resource.ClaimResponse.error.extension (followupAction).url | uri | Required | | 1..1 | URL of the extension: http://hl7.org/fhir/us/davinci-pas/StructureDefinition/extension-errorFollowupAction

Bundle (R4).entry.resource.ClaimResponse.error.extension (followupAction).valueCodeableConcept | CodeableConcept | Required | | 1..1 | A code representing what action must occur to resolve this error. It has a coding system of https://codesystem.x12.org/005010/889.

Bundle (R4).entry.resource.ClaimResponse.id | id | Optional | | 0..1 | ClaimResponse ID.

Bundle (R4).entry.resource.ClaimResponse.identifier | Identifier | Optional | Yes | 0..* | Identifies the ClaimResponse. This contains the identifier included in the original Claim request.

Bundle (R4).entry.resource.ClaimResponse.identifier.extension (subDepartment) (also: extension (subDepartment)) | Extension | Optional | Yes | 0..1 | An additional element that provides a further subdivision within the organization granting the identifier, equivalent to TRN04 (ANSI X12 value). URL: http://hl7.org/fhir/us/davinci-pas/StructureDefinition/extension-identifierSubDepartment

Bundle (R4).entry.resource.ClaimResponse.identifier.extension (subDepartment).url | uri | Required | | 1..1 | URL of the extension: http://hl7.org/fhir/us/davinci-pas/StructureDefinition/extension-identifierSubDepartment

Bundle (R4).entry.resource.ClaimResponse.identifier.extension (subDepartment).valueString | string | Required | | 1..1 | Additional reference number.

Bundle (R4).entry.resource.ClaimResponse.identifier.system | String | Required | | 1..1 | System of the identifier, equivalent to TRN03 (ANSI X12 value). Uses a scheme of 'urn:trnorg:<TRN03>'.

Bundle (R4).entry.resource.ClaimResponse.identifier.value | String | Required | | 1..1 | Value of the identifier, equivalent to TRN02 (ANSI X12 value).

Bundle (R4).entry.resource.ClaimResponse.insurer | Reference | Required | | 1..1 | Party responsible for reimbursement. A reference to the Organization resource.

Bundle (R4).entry.resource.ClaimResponse.item | BackboneElement | Optional | Yes | 0..* | Requested items.

Bundle (R4).entry.resource.ClaimResponse.item.adjudication | BackboneElement | Required | Yes | 1..1 | Item adjudication.

Bundle (R4).entry.resource.ClaimResponse.item.adjudication.category | CodeableConcept | Required | | 1..1 | Adjudication category. The coding system is http://terminology.hl7.org/CodeSystem/adjudication. The returned code is always “submitted”.

Bundle (R4).entry.resource.ClaimResponse.item.adjudication.extension (reviewAction) (also: extension (reviewAction)) | Extension | Optional | Yes | 0..1 | The details of the review action that are necessary for the authorization, equivalent to 2000F HCR (ANSI X12 value). URL: http://hl7.org/fhir/us/davinci-pas/StructureDefinition/extension-reviewAction

Bundle (R4).entry.resource.ClaimResponse.item.adjudication.extension (reviewAction).extension (number) (also: extension (number)) | Extension | Optional | Yes | 0..1 | Review number, equivalent to 2000F HCR02 (ANSI X12 value). URL: number

Bundle (R4).entry.resource.ClaimResponse.item.adjudication.extension (reviewAction).extension (number).url | uri | Required | | 1..1 | URL of the extension: number

Bundle (R4).entry.resource.ClaimResponse.item.adjudication.extension (reviewAction).extension (number).valueString | string | Required | | 1..1 | Review number value.

Bundle (R4).entry.resource.ClaimResponse.item.adjudication.extension (reviewAction).extension (reasonCode) (also: extension (reasonCode)) | Extension | Optional | Yes | 0..1 | Certification action code: indicates the reason for the approved, denied, pended, or other services, equivalent to 2000F HCR03 (ANSI X12 value). URL: reasonCode

Bundle (R4).entry.resource.ClaimResponse.item.adjudication.extension (reviewAction).extension (reasonCode).url | uri | Required | | 1..1 | URL for the extension: reasonCode

Bundle (R4).entry.resource.ClaimResponse.item.adjudication.extension (reviewAction).extension (reasonCode).valueCodeableConcept | CodeableConcept | Required | | 1..1 | Reason code value. It has a code system of https://codesystem.x12.org/external/886.

Bundle (R4).entry.resource.ClaimResponse.item.adjudication.extension (reviewAction).extension (reviewActionCode) (also: extension (reviewActionCode)) | Extension | Optional | Yes | 0..1 | Code for the review action, equivalent to 2000F HCR01 (ANSI X12 value). URL: http://hl7.org/fhir/us/davinci-pas/StructureDefinition/extension-reviewActionCode

Bundle (R4).entry.resource.ClaimResponse.item.adjudication.extension (reviewAction).extension (reviewActionCode).url | uri | Required | | 1..1 | URL of the extension: http://hl7.org/fhir/us/davinci-pas/StructureDefinition/extension-reviewActionCode

Bundle (R4).entry.resource.ClaimResponse.item.adjudication.extension (reviewAction).extension (reviewActionCode).valueCodeableConcept | CodeableConcept | Required | | 1..1 | Review action code for the adjudication. It has a code system of https://codesystem.x12.org/005010/306.

Bundle (R4).entry.resource.ClaimResponse.item.adjudication.extension (reviewAction).url | uri | Required | | 1..1 | URL of the extension: http://hl7.org/fhir/us/davinci-pas/StructureDefinition/extension-reviewAction

Bundle (R4).entry.resource.ClaimResponse.item.extension (administrationReferenceNumber) (also: extension (administrationReferenceNumber)) | Extension | Optional | Yes | 0..1 | A string assigned by the payer to the original disallowed review outcome associated with this service item, equivalent to 2000F REF*NT (ANSI X12 value). URL: http://hl7.org/fhir/us/davinci-pas/StructureDefinition/extension-administrationReferenceNumber

Bundle (R4).entry.resource.ClaimResponse.item.extension (administrationReferenceNumber).url | uri | Required | | 1..1 | URL of the extension: http://hl7.org/fhir/us/davinci-pas/StructureDefinition/extension-administrationReferenceNumber

Bundle (R4).entry.resource.ClaimResponse.item.extension (administrationReferenceNumber).valueString | string | Required | | 1..1 | Administrative reference number.

Bundle (R4).entry.resource.ClaimResponse.item.extension (authorizedItemDetail) (also: extension (authorizedItemDetail)) | Extension | Optional | Yes | 0..1 | The details of the requested item. URL: http://hl7.org/fhir/us/davinci-pas/StructureDefinition/extension-itemAuthorizedDetail

Bundle (R4).entry.resource.ClaimResponse.item.extension (authorizedItemDetail).extension (authorizedService) (also: extension (authorizedService)) | Extension | Optional | Yes | 0..1 | The ServiceRequest that contains the recurring quantity details of what has been requested for this item. If not recurring, item.extension:quantity is sent instead. URL: http://hl7.org/fhir/us/davinci-pas/StructureDefinition/extension-requestedService

Bundle (R4).entry.resource.ClaimResponse.item.extension (authorizedItemDetail).extension (authorizedService).url | uri | Required | | 1..1 | URL of the extension: http://hl7.org/fhir/us/davinci-pas/StructureDefinition/extension-requestedService

Bundle (R4).entry.resource.ClaimResponse.item.extension (authorizedItemDetail).extension (authorizedService).valueReference | Reference | Required | | 1..1 | Reference to authorized service. A reference to ServiceRequest resource.

Bundle (R4).entry.resource.ClaimResponse.item.extension (authorizedItemDetail).extension (modifier) (also: extension (modifier)) | Extension | Optional | Yes | 0..* | The modifier details of what has been requested for this item. URL: modifier

Bundle (R4).entry.resource.ClaimResponse.item.extension (authorizedItemDetail).extension (modifier).url | uri | Required | | 1..1 | URL of the extension: modifier

Bundle (R4).entry.resource.ClaimResponse.item.extension (authorizedItemDetail).extension (modifier).valueCodeableConcept | CodeableConcept | Required | | 1..1 | Service modifier. Coding system (depending on the type of modifier): http://www.ama-assn.org/go/cpt http://www.cms.gov/Medicare/Coding/HCPCSReleaseCodeSets https://open.epic.com/FHIR/(custom_OID)/custom-procedure-modifier

Bundle (R4).entry.resource.ClaimResponse.item.extension (authorizedItemDetail).extension (productOrServiceCode) (also: extension (productOrServiceCode)) | Extension | Optional | Yes | 0..1 | The productOrServiceCode details of what has been requested for this item. URL: productOrServiceCode

Bundle (R4).entry.resource.ClaimResponse.item.extension (authorizedItemDetail).extension (productOrServiceCode).url | uri | Required | | 1..1 | URL of the extension: productOrServiceCode

Bundle (R4).entry.resource.ClaimResponse.item.extension (authorizedItemDetail).extension (productOrServiceCode).valueCodeableConcept | CodeableConcept | Required | | 1..1 | Service code. Coding system (depending on the type of service): http://www.ama-assn.org/go/cpt http://www.cms.gov/Medicare/Coding/HCPCSReleaseCodeSets Code is set to the procedure code. Text is set to the procedure description.

Bundle (R4).entry.resource.ClaimResponse.item.extension (authorizedItemDetail).extension (quantity) (also: extension (quantity)) | Extension | Optional | Yes | 0..1 | The non-recurring quantity details of what has been requested for this item. If recurring, item.extension:authorizedService is sent instead. URL: quantity

Bundle (R4).entry.resource.ClaimResponse.item.extension (authorizedItemDetail).extension (quantity).url | uri | Required | | 1..1 | URL of the extension: quantity

Bundle (R4).entry.resource.ClaimResponse.item.extension (authorizedItemDetail).extension (quantity).valueQuantity | Quantity | Required | | 1..1 | Quantity amount.

Bundle (R4).entry.resource.ClaimResponse.item.extension (authorizedItemDetail).extension (revenue) (also: extension (revenue)) | Extension | Optional | Yes | 0..1 | The revenue details of what has been requested for this item. URL: http://hl7.org/fhir/us/davinci-pas/StructureDefinition/extension-revenueCode

Bundle (R4).entry.resource.ClaimResponse.item.extension (authorizedItemDetail).extension (revenue).url | uri | Required | | 1..1 | URL of the extension: http://hl7.org/fhir/us/davinci-pas/StructureDefinition/extension-revenueCode

Bundle (R4).entry.resource.ClaimResponse.item.extension (authorizedItemDetail).extension (revenue).valueCodeableConcept | CodeableConcept | Required | | 1..1 | Revenue code of the added service. It has a coding system of https://www.nubc.org/CodeSystem/RevenueCodes.

Bundle (R4).entry.resource.ClaimResponse.item.extension (authorizedItemDetail).url | uri | Required | | 1..1 | URL of the extension: http://hl7.org/fhir/us/davinci-pas/StructureDefinition/extension-itemAuthorizedDetail

Bundle (R4).entry.resource.ClaimResponse.item.extension (authorizedProvider) (also: extension (authorizedProvider)) | Extension | Optional | Yes | 0..* | The specific provider who has been authorized to provide this item. URL: http://hl7.org/fhir/us/davinci-pas/StructureDefinition/extension-itemAuthorizedProvider

Bundle (R4).entry.resource.ClaimResponse.item.extension (authorizedProvider).extension (provider) (also: extension (provider)) | Extension | Optional | Yes | 0..1 | The provider who is authorized to provider this item. URL: provider

Bundle (R4).entry.resource.ClaimResponse.item.extension (authorizedProvider).extension (provider).url | uri | Required | | 1..1 | URL of the extension: provider

Bundle (R4).entry.resource.ClaimResponse.item.extension (authorizedProvider).extension (provider).valueReference | Reference | Required | | 1..1 | Reference to the provider. A reference to Practitioner or Organization resource.

Bundle (R4).entry.resource.ClaimResponse.item.extension (authorizedProvider).extension (providerType) (also: extension (providerType)) | Extension | Optional | Yes | 0..1 | The provider types. URL: providerType

Bundle (R4).entry.resource.ClaimResponse.item.extension (authorizedProvider).extension (providerType).url | uri | Required | | 1..1 | URL of the extension: providerType

Bundle (R4).entry.resource.ClaimResponse.item.extension (authorizedProvider).extension (providerType).valueCodeableConcept | CodeableConcept | Required | | 1..1 | Provider type. Code system is set to “https://codesystem.x12.org/005010/98”.

Bundle (R4).entry.resource.ClaimResponse.item.extension (authorizedProvider).url | uri | Required | | 1..1 | URL of the extension: http://hl7.org/fhir/us/davinci-pas/StructureDefinition/extension-itemAuthorizedProvider

Bundle (R4).entry.resource.ClaimResponse.item.extension (itemTraceNumber) (also: extension (itemTraceNumber)) | Extension | Optional | Yes | 0..* | Uniquely identifies this claim item, equivalent to 2000F TRN (ANSI X12 value). URL: http://hl7.org/fhir/us/davinci-pas/StructureDefinition/extension-itemTraceNumber

Bundle (R4).entry.resource.ClaimResponse.item.extension (itemTraceNumber).url | uri | Required | | 1..1 | URL of the extension: http://hl7.org/fhir/us/davinci-pas/StructureDefinition/extension-itemTraceNumber

Bundle (R4).entry.resource.ClaimResponse.item.extension (itemTraceNumber).valueIdentifier | Identifier | Optional | | 0..1 | Trace number.

Bundle (R4).entry.resource.ClaimResponse.item.extension (itemTraceNumber).valueIdentifier.extension (subDepartment) (also: extension (subDepartment)) | Extension | Optional | Yes | 0..1 | An additional element that provides a further subdivision within the organization granting the identifier, equivalent to TRN04 (ANSI X12 value). URL: http://hl7.org/fhir/us/davinci-pas/StructureDefinition/extension-identifierSubDepartment

Bundle (R4).entry.resource.ClaimResponse.item.extension (itemTraceNumber).valueIdentifier.extension (subDepartment).url | uri | Required | | 1..1 | URL of the extension: http://hl7.org/fhir/us/davinci-pas/StructureDefinition/extension-identifierSubDepartment

Bundle (R4).entry.resource.ClaimResponse.item.extension (itemTraceNumber).valueIdentifier.extension (subDepartment).valueString | string | Required | | 1..1 | Additional reference number.

Bundle (R4).entry.resource.ClaimResponse.item.extension (itemTraceNumber).valueIdentifier.system | String | Required | | 1..1 | System of the identifier, equivalent to TRN03 (ANSI X12 value). Uses a scheme of 'urn:trnorg:<TRN03>'.

Bundle (R4).entry.resource.ClaimResponse.item.extension (itemTraceNumber).valueIdentifier.value | String | Required | | 1..1 | Value of the identifier, equivalent to TRN02 (ANSI X12 value).

Bundle (R4).entry.resource.ClaimResponse.item.extension (preAuthIssueDate) (also: extension (preAuthIssueDate)) | Extension | Optional | Yes | 0..1 | The date when this item's preauthorization was issued. URL: http://hl7.org/fhir/us/davinci-pas/StructureDefinition/extension-itemPreAuthIssueDate

Bundle (R4).entry.resource.ClaimResponse.item.extension (preAuthIssueDate).url | uri | Required | | 1..1 | URL of the extension: http://hl7.org/fhir/us/davinci-pas/StructureDefinition/extension-itemPreAuthIssueDate

Bundle (R4).entry.resource.ClaimResponse.item.extension (preAuthIssueDate).valueDate | date | Required | | 1..1 | The date when this item's preauthorization was issued.

Bundle (R4).entry.resource.ClaimResponse.item.extension (preAuthPeriod) (also: extension (preAuthPeriod)) | Extension | Optional | Yes | 0..1 | The date/period when this item's preauthorization is valid. URL: http://hl7.org/fhir/us/davinci-pas/StructureDefinition/extension-itemPreAuthPeriod

Bundle (R4).entry.resource.ClaimResponse.item.extension (preAuthPeriod).url | uri | Required | | 1..1 | URL of the extension: http://hl7.org/fhir/us/davinci-pas/StructureDefinition/extension-itemPreAuthPeriod

Bundle (R4).entry.resource.ClaimResponse.item.extension (preAuthPeriod).valuePeriod | Period | Required | | 1..1 | The period when this item's preauthorization is valid.

Bundle (R4).entry.resource.ClaimResponse.item.extension (preAuthPeriod).valuePeriod.end | String | Optional | | 0..1 | Preauthorization end date.

Bundle (R4).entry.resource.ClaimResponse.item.extension (preAuthPeriod).valuePeriod.start | String | Optional | | 0..1 | Preauthorization start date.

Bundle (R4).entry.resource.ClaimResponse.item.extension (previousAuthorizationNumber) (also: extension (previousAuthorizationNumber)) | Extension | Optional | Yes | 0..1 | A string assigned by the payer to an authorized review outcome associated with this service item, equivalent to 2000F REF*BB (ANSI X12 value). URL: http://hl7.org/fhir/us/davinci-pas/StructureDefinition/extension-authorizationNumber

Bundle (R4).entry.resource.ClaimResponse.item.extension (previousAuthorizationNumber).url | uri | Required | | 1..1 | URL of the extension: http://hl7.org/fhir/us/davinci-pas/StructureDefinition/extension-authorizationNumber

Bundle (R4).entry.resource.ClaimResponse.item.extension (previousAuthorizationNumber).valueString | string | Required | | 1..1 | A string assigned by the payer to an authorized review outcome associated with this service item.

Bundle (R4).entry.resource.ClaimResponse.item.extension (requestedServiceDate) (also: extension (requestedServiceDate)) | Extension | Optional | Yes | 0..1 | The original date/period that was requested by the submitter for this item. URL: http://hl7.org/fhir/us/davinci-pas/StructureDefinition/extension-itemRequestedServiceDate

Bundle (R4).entry.resource.ClaimResponse.item.extension (requestedServiceDate).url | uri | Required | | 1..1 | URL of the extension: http://hl7.org/fhir/us/davinci-pas/StructureDefinition/extension-itemRequestedServiceDate

Bundle (R4).entry.resource.ClaimResponse.item.extension (requestedServiceDate).valueDateTime (also: valueDateTime) | dateTime | Conditional | | 0..1 | The original date time that was requested by the submitter for this item. If it is a range of dates, valuePeriod is used.

Bundle (R4).entry.resource.ClaimResponse.item.extension (requestedServiceDate).valuePeriod | Period | Conditional | | 0..1 | The original period that was requested by the submitter for this item. If it is a single date, valueDateTime is used.

Bundle (R4).entry.resource.ClaimResponse.item.extension (requestedServiceDate).valuePeriod.end | String | Optional | | 0..1 | Requested end date.

Bundle (R4).entry.resource.ClaimResponse.item.extension (requestedServiceDate).valuePeriod.start | String | Optional | | 0..1 | Requested start date.

Bundle (R4).entry.resource.ClaimResponse.item.itemSequence | positiveInt | Required | | 1..1 | Claim item instance identifier.

Bundle (R4).entry.resource.ClaimResponse.item.noteNumber | positiveInt | Optional | Yes | 0..* | Applicable note numbers.

Bundle (R4).entry.resource.ClaimResponse.outcome | code | Required | | 1..1 | Code: complete | error | partial. An outcome for the overall prior auth status. Returns complete if a decision has been made on the authorization. Returns error if there are any non-operationOutcome errors. Returns partial if some services are still under review.

Bundle (R4).entry.resource.ClaimResponse.patient | Reference | Required | | 1..1 | A reference to the beneficiary patient. A reference to Patient resource.

Bundle (R4).entry.resource.ClaimResponse.preAuthPeriod | Period | Optional | | 0..1 | Preauthorization reference effective period.

Bundle (R4).entry.resource.ClaimResponse.preAuthPeriod.end | String | Optional | | 0..1 | Preauthorization reference effective end date.

Bundle (R4).entry.resource.ClaimResponse.preAuthPeriod.start | String | Optional | | 0..1 | Preauthorization reference effective start date.

Bundle (R4).entry.resource.ClaimResponse.preAuthRef | string | Optional | | 0..1 | Preauthorization reference. For inquiry, this is the authorization number from the matched authorization, falling back to the administrative reference number.

Bundle (R4).entry.resource.ClaimResponse.processNote | BackboneElement | Optional | Yes | 0..* | Note concerning adjudication.

Bundle (R4).entry.resource.ClaimResponse.processNote.number | positiveInt | Required | | 1..1 | Note instance identifier.

Bundle (R4).entry.resource.ClaimResponse.processNote.text | string | Required | | 1..1 | Note text.

Bundle (R4).entry.resource.ClaimResponse.request | Reference | Required | | 1..1 | The associated request for this response. This contains the claim reference sent by the submitter. This response bundle does not contain the claim resource itself. A reference to Claim resource.

Bundle (R4).entry.resource.ClaimResponse.requestor | Reference | Optional | | 0..1 | Party responsible for the claim. A reference to Organization or PractitionerRole resource.

Bundle (R4).entry.resource.ClaimResponse.status | code | Required | | 1..1 | A code specifying the state of the resource instance. Sent as active.

Bundle (R4).entry.resource.ClaimResponse.type | CodeableConcept | Required | | 1..1 | The type of claim. The code system is set to http://terminology.hl7.org/CodeSystem/claim-type.

Bundle (R4).entry.resource.ClaimResponse.use | code | Required | | 1..1 | A code determines the use of the response body. Sent as preauthorization.

Bundle (R4).entry.resource.Organization | Resource | Optional | | 0..* | Organization resource.

Bundle (R4).entry.resource.Organization.active | boolean | Required | | 1..1 | Whether the organization's record is still in active use. Sent as 1.

Bundle (R4).entry.resource.Organization.address | Address | Optional | Yes | 0..* | Address.

Bundle (R4).entry.resource.Organization.address.city | string | Optional | | 0..1 | Name of city or town.

Bundle (R4).entry.resource.Organization.address.line | string | Optional | Yes | 0..4 | Street name, number, direction, and P.O. Box.

Bundle (R4).entry.resource.Organization.address.postalCode | string | Optional | | 0..1 | US ZIP Codes.

Bundle (R4).entry.resource.Organization.address.state | string | Optional | | 0..1 | US state two-letter abbreviation. Value set: http://hl7.org/fhir/us/core/STU7/ValueSet-us-core-usps-state.html.

Bundle (R4).entry.resource.Organization.contact | BackboneElement | Optional | Yes | 0..* | Contact information.

Bundle (R4).entry.resource.Organization.contact.name | HumanName | Optional | | 0..1 | Contact name.

Bundle (R4).entry.resource.Organization.contact.telecom | ContactPoint | Optional | Yes | 0..* | Contact detail.

Bundle (R4).entry.resource.Organization.contact.telecom.system | code | Required | | 1..1 | Telecommunication form of contact point. Depending on what information was received, it can contain: phone, fax, email.

Bundle (R4).entry.resource.Organization.contact.telecom.value | string | Required | | 1..1 | The actual contact point details, in a form that is meaningful to the designated communication system (such as phone number or email address).

Bundle (R4).entry.resource.Organization.identifier | Identifier | Optional | Yes | 0..* | All identifiers.

Bundle (R4).entry.resource.Organization.identifier.system | String | Required | | 1..1 | The system for the identifier value which is copied from the request. Supported systems: http://terminology.hl7.org/NamingSystem/USEIN (TIN) http://hl7.org/fhir/sid/us-npi (NPI)

Bundle (R4).entry.resource.Organization.identifier.type | CodeableConcept | Optional | | 0..1 | Identifier type. This is only used for when Organization is ClaimResponse.insurer. Coding system is set to http://hl7.org/fhir/us/carin-bb/CodeSystem/C4BBIdentifierType, and code is set to “payerid”.

Bundle (R4).entry.resource.Organization.identifier.value | String | Required | | 1..1 | Identifier value that is copied from the request.

Bundle (R4).entry.resource.Organization.name | string | Required | | 1..1 | Name.

Bundle (R4).entry.resource.Organization.telecom | ContactPoint | Optional | Yes | 0..* | Contact detail.

Bundle (R4).entry.resource.Organization.telecom.system | code | Required | | 1..1 | Telecommunication form of contact point. Depending on what information was received, it can contain: phone, fax, email.

Bundle (R4).entry.resource.Organization.telecom.value | string | Required | | 1..1 | The actual contact point details in a form that is meaningful to the designated communication system (such as phone number or email address).

Bundle (R4).entry.resource.Organization.type | CodeableConcept | Optional | Yes | 0..* | Coding system is set to https://codesystem.x12.org/005010/98. For ClaimResponse.Insurer, the code is one of the following: 2B, 36, PR, X3.

Bundle (R4).entry.resource.Patient | Resource | Optional | | 0..* | Patient resource.

Bundle (R4).entry.resource.Patient.address | Address | Optional | Yes | 0..* | Address.

Bundle (R4).entry.resource.Patient.address.city | string | Optional | | 0..1 | Name of city or town.

Bundle (R4).entry.resource.Patient.address.line | string | Optional | Yes | 0..4 | Street name, number, direction, and P.O. Box.

Bundle (R4).entry.resource.Patient.address.postalCode | string | Optional | | 0..1 | US ZIP Codes.

Bundle (R4).entry.resource.Patient.address.state | string | Optional | | 0..1 | US state two-letter abbreviation. Value set: http://hl7.org/fhir/us/core/STU7/ValueSet-us-core-usps-state.html.

Bundle (R4).entry.resource.Patient.birthDate | date | Optional | | 0..1 | Birth date.

Bundle (R4).entry.resource.Patient.gender | code | Required | | 1..1 | Gender. Code: male | female | other | unknown

Bundle (R4).entry.resource.Patient.identifier | Identifier | Required | Yes | 1..* | All Identifiers

Bundle (R4).entry.resource.Patient.identifier.system | String | Required | | 1..1 | The system for the identifier value which is copied from the request. Supported systems from request: urn:oid:2.16.840.1.113883.4.1 (SSN) http://open.epic.com/FHIR/StructureDefinition/member-id (Member ID) Other

OID or URN that are mapped in internal system

Bundle (R4).entry.resource.Patient.identifier.type | CodeableConcept | Optional | | 0..1 | Identifier type. This is only used for Member ID. Coding system is set to http://terminology.hl7.org/CodeSystem/v2-0203, and code is set to “MB”.

Bundle (R4).entry.resource.Patient.identifier.value | String | Required | | 1..1 | Identifier value that is copied from the request. Member ID value is coming from the sytem.

Bundle (R4).entry.resource.Patient.name | HumanName | Required | Yes | 1..* | Name.

Bundle (R4).entry.resource.Patient.name.family | string | Optional | | 0..1 | Family name (surname).

Bundle (R4).entry.resource.Patient.name.given | string | Optional | Yes | 0..* | Given name (includes middle name).

Bundle (R4).entry.resource.Patient.name.suffix | string | Optional | Yes | 0..* | Suffix.

Bundle (R4).entry.resource.Patient.telecom | ContactPoint | Optional | Yes | 0..* | Contact details.

Bundle (R4).entry.resource.Patient.telecom.system | code | Required | | 1..1 | Telecommunication form of contact point. Depending on what information was received, it can contain: phone, fax, email.

Bundle (R4).entry.resource.Patient.telecom.value | string | Required | | 1..1 | The actual contact point details in a form that is meaningful to the designated communication system (such as phone number or email address).

Bundle (R4).entry.resource.Practitioner | Resource | Optional | | 0..* | Practitioner resource.

Bundle (R4).entry.resource.Practitioner.address | Address | Optional | Yes | 0..* | Address.

Bundle (R4).entry.resource.Practitioner.address.city | string | Optional | | 0..1 | Name of city or town.

Bundle (R4).entry.resource.Practitioner.address.line | string | Optional | Yes | 0..4 | Street name, number, direction, and P.O. Box.

Bundle (R4).entry.resource.Practitioner.address.postalCode | string | Optional | | 0..1 | US ZIP Codes.

Bundle (R4).entry.resource.Practitioner.address.state | string | Optional | | 0..1 | US state two-letter abbreviation. Value set: http://hl7.org/fhir/us/core/STU7/ValueSet-us-core-usps-state.html.

Bundle (R4).entry.resource.Practitioner.identifier | Identifier | Required | Yes | 1..* | All identifiers.

Bundle (R4).entry.resource.Practitioner.identifier.system | String | Required | | 1..1 | The system for the identifier value which is copied from request. Supported systems for request: http://terminology.hl7.org/NamingSystem/USEIN (TIN) http://hl7.org/fhir/sid/us-npi (NPI)

Bundle (R4).entry.resource.Practitioner.identifier.value | String | Required | | 1..1 | Identifier value that is copied from the request.

Bundle (R4).entry.resource.Practitioner.name | HumanName | Required | Yes | 1..* | Name.

Bundle (R4).entry.resource.Practitioner.name.family | string | Required | | 1..1 | Family name (surname).

Bundle (R4).entry.resource.Practitioner.name.given | string | Optional | Yes | 0..* | Given name (includes middle name).

Bundle (R4).entry.resource.Practitioner.name.suffix | string | Optional | Yes | 0..* | Suffix.

Bundle (R4).entry.resource.Practitioner.telecom | ContactPoint | Optional | Yes | 0..* | Contact details.

Bundle (R4).entry.resource.Practitioner.telecom.system | code | Required | | 1..1 | Telecommunication form of contact point. Depending on what information was received, it can contain: phone, fax, email.

Bundle (R4).entry.resource.Practitioner.telecom.value | string | Required | | 1..1 | The actual contact point details in a form that is meaningful to the designated communication system (such as phone number or email address).

Bundle (R4).entry.resource.PractitionerRole | Resource | Optional | | 0..* | PractitionerRole resource.

Bundle (R4).entry.resource.PractitionerRole.practitioner | Reference | Required | | 1..1 | Practitioner that can provide the defined services for the organization. A reference to Practitioner resource.

Bundle (R4).entry.resource.ServiceRequest | Resource | Optional | | 0..* | ServiceRequest resource.

Bundle (R4).entry.resource.ServiceRequest.intent | code | Required | | 1..1 | The kind of service request. Sent as order.

Bundle (R4).entry.resource.ServiceRequest.occurrenceTiming | Timing | Optional | | 0..1 | A timing schedule that specifies an event that can occur multiple times.

Bundle (R4).entry.resource.ServiceRequest.occurrenceTiming.repeat | BackboneElement | Required | | 1..1 | When the event is to occur.

Bundle (R4).entry.resource.ServiceRequest.occurrenceTiming.repeat.boundsDuration | Duration | Optional | | 0..1 | The number of periods over which the service is delivered.

Bundle (R4).entry.resource.ServiceRequest.occurrenceTiming.repeat.boundsDuration.code | code | Required | | 1..1 | Units (h | d | wk | mo | a).

Bundle (R4).entry.resource.ServiceRequest.occurrenceTiming.repeat.boundsDuration.system | uri | Required | | 1..1 | URL of the system: http://unitsofmeasure.org.

Bundle (R4).entry.resource.ServiceRequest.occurrenceTiming.repeat.boundsDuration.unit | string | Required | | 1..1 | Unit representation.

Bundle (R4).entry.resource.ServiceRequest.occurrenceTiming.repeat.boundsDuration.value | decimal | Required | | 1..1 | Value of the duration.

Bundle (R4).entry.resource.ServiceRequest.occurrenceTiming.repeat.period | decimal | Required | | 1..1 | The number of times the event occurs within the specified time period. Sent as 1.

Bundle (R4).entry.resource.ServiceRequest.occurrenceTiming.repeat.periodUnit | code | Required | | 1..1 | Units (h | d | wk | mo | a). BoundsDuration.code and periodUnit are the same.

Bundle (R4).entry.resource.ServiceRequest.quantityQuantity | Quantity | Optional | | 0..1 | A fixed quantity.

Bundle (R4).entry.resource.ServiceRequest.quantityQuantity.system | String | Required | | 1..1 | System that defines coded unit form. It has a system of https://codesystem.x12.org/005010/673.

Bundle (R4).entry.resource.ServiceRequest.quantityQuantity.unit | String | Required | | 1..1 | Unit representation.

Bundle (R4).entry.resource.ServiceRequest.quantityQuantity.value | Decimal | Required | | 1..1 | Quantity value.

Bundle (R4).entry.resource.ServiceRequest.status | code | Required | | 1..1 | Status of the service. Sent as active.

Bundle (R4).entry.resource.ServiceRequest.subject | Reference | Required | | 1..1 | Individual or Entity the service is ordered for. UUID of the patient of the beneficiary patient is sent. A reference to Patient resource.

Bundle (R4).timestamp | instant | Required | | 1..1 | The time of Bundle creation.

Bundle (R4).type | code | Required | | 1..1 | Purpose of the Bundle. Sent as collection.

Sample request


```
{
  "resourceType": "Bundle",
  "id": "ReferralAuthorizationBundleExample",
  "meta": {
    "profile": [
      "http://hl7.org/fhir/us/davinci-pas/StructureDefinition/profile-pas-request-bundle"
    ]
  },
  "identifier": {
    "system": "urn:oid:2.16.840.1.113883.3.12345.4.2",
```

```
  "value": "A12345"
},
"type": "collection",
"timestamp": "2024-04-15T11:01:00+05:00",
"entry": [
  {
    "fullUrl": "https://hostname/instance/api/FHIR/R4/Claim/eClm-9YQ4wP8",
    "resource": {
      "resourceType": "Claim",
      "id": "eClm-9YQ4wP8",
      "meta": {
        "profile": [
          "http://hl7.org/fhir/us/davinci-pas/StructureDefinition/profile-claim"
        ]
      },
      "extension": [
        {
          "valueCodeableConcept": {
            "coding": [
              {
                "system": "https://codesystem.x12.org/005010/1338",
                "code": "U",
                "display": "Urgent"
              }
            ],
            "text": "Urgent"
          },
          "url": "http://hl7.org/fhir/us/davinci-pas/StructureDefinition/extension-levelOfServiceCode"
        }
      ],
      "identifier": [
        {
          "system": "urn:oid:2.16.840.1.113883.3.12345.4.1",
          "value": "1461746",
          "assigner": {
            "identifier": {
              "system": "http://hl7.org/fhir/sid/us-npi",
              "value": "9012345678"
            }
          }
        }
      ],
      "status": "active",
      "type": {
        "coding": [
          {
            "system": "http://terminology.hl7.org/CodeSystem/claim-type",
            "code": "oral"
          }
        ]
      },
      "use": "preauthorization",
      "created": "2005-05-02T01:01:00-05:00",
      "insurer": {
        "reference": "Organization/e.Ins-7KC4gB2"
      },
      "patient": {
        "reference": "Patient/e.Pat-6HV3nK5"
      },
      "enterer": {
        "reference": "Practitioner/e.Prov-8WN2kF4"
      },
      "provider": {
        "reference": "Organization/e.Org-3QA9hD7"
      },
      "facility": {
        "reference": "Location/e.Loc-2XT8mS9"
      },
      "supportingInfo": [
        {
          "sequence": 1,
          "category": {
            "coding": [
              {
                "system": "http://hl7.org/fhir/us/davinci-pas/CodeSystem/PASTempCodes",
                "code": "patientEvent"
              }
            ]
          },
          "timingPeriod": {
            "start": "2025-01-01",
            "end": "2025-01-31"
          }
        }
      ],
      "diagnosis": [
        {
          "sequence": 1,
          "diagnosisCodeableConcept": {
```

```
      "coding": [
        {
          "system": "http://hl7.org/fhir/sid/icd-10-cm",
          "code": "G89.4"
        }
      ]
    }
  },
  {
    "sequence": 2,
    "diagnosisCodeableConcept": {
      "coding": [
        {
          "system": "http://hl7.org/fhir/sid/icd-10-cm",
          "code": "E56.1"
        }
      ]
    }
  }
],
"insurance": [
  {
    "sequence": 1,
    "focal": true,
    "coverage": {
      "reference": "Coverage/e.Cov-5PL6jR1"
    }
  }
],
"item": [
  {
    "extension": [
      {
        "url": "http://hl7.org/fhir/us/davinci-pas/StructureDefinition/extension-itemCertificationIssueDate",
        "valueCodeableConcept": {
          "coding": [
            {
              "system": "https://codesystem.x12.org/005010/1525",
              "code": "HS",
              "display": "Health service review"
            }
          ]
        }
      },
      {
        "url": "http://hl7.org/fhir/us/davinci-pas/StructureDefinition/extension-certificationType",
        "valueCodeableConcept": {
          "coding": [
            {
              "system": "https://codesystem.x12.org/005010/1322",
              "code": "I",
              "display": "INITIAL"
            }
          ]
        }
      }
    ],
    "sequence": 1,
    "revenue": {
      "coding": [
        {
          "system": "https://www.nubc.org/CodeSystem/RevenueCodes",
          "code": "0372",
          "display": "Administrative Days"
        }
      ]
    },
    "productOrService": {
      "coding": [
        {
          "system": "http://www.ama-assn.org/go/cpt",
          "code": "97039",
          "display": "PHYSICAL THERAPY TREATMENT"
        }
      ]
    },
    "modifier": [
      {
        "coding": [
          {
            "system": "http://www.cms.gov/Medicare/Coding/HCPCSReleaseCodeSets",
            "code": "D",
            "display": "Diagnostic Or Theraputic Site"
          }
        ]
      },
      {
        "coding": [
          {
```

```
                "system": "http://www.cms.gov/Medicare/Coding/HCPCSReleaseCodeSets",
                "code": "G",
                "display": "Hospital-Based Dialysis Facility"
              }
            ]
          }
        ],
        "quantity": {
          "value": 13,
          "system": "https://codesystem.x12.org/005010/673",
          "code": "FL"
        }
      }
    ]
  }
},
{
  "fullUrl": "https://hostname/instance/api/FHIR/R4/Organization/e.Org-3QA9hD7",
  "resource": {
    "resourceType": "Organization",
    "id": "e.Org-3QA9hD7",
    "meta": {
      "profile": [
        "http://hl7.org/fhir/us/davinci-pas/StructureDefinition/profile-requestor"
      ]
    },
    "identifier": [
      {
        "system": "http://hl7.org/fhir/sid/us-npi",
        "value": "1000000764"
      }
    ],
    "active": true,
    "type": [
      {
        "coding": [
          {
            "system": "https://codesystem.x12.org/005010/98",
            "code": "X3"
          }
        ]
      }
    ],
    "name": "Test Hospital",
    "address": [
      {
        "line": [
          "1 Milky Way"
        ],
        "city": "VERONA",
        "state": "WI",
        "postalCode": "53593",
        "country": "US"
      }
    ]
  }
},
{
  "fullUrl": "https://hostname/instance/api/FHIR/R4/Practitioner/e.Prov-8WN2kF4",
  "resource": {
    "resourceType": "Practitioner",
    "id": "e.Prov-8WN2kF4",
    "meta": {
      "versionId": "1",
      "lastUpdated": "2019-06-13T09:55:47.101-04:00"
    },
    "identifier": [
      {
        "system": "http://hl7.org/fhir/sid/us-npi",
        "value": "1000003370"
      }
    ],
    "name": [
      {
        "use": "official",
        "family": "Practitioner",
        "given": [
          "Test"
        ]
      }
    ]
  }
},
{
  "fullUrl": "https://hostname/instance/api/FHIR/R4/Coverage/e.Cov-5PL6jR1",
  "resource": {
    "resourceType": "Coverage",
    "id": "e.Cov-5PL6jR1",
    "meta": {
```

```
      "profile": [
        "http://hl7.org/fhir/us/davinci-pas/StructureDefinition/profile-coverage"
      ]
    },
    "status": "active",
    "subscriber": {
      "reference": "Patient/e.Pat-6HV3nK5"
    },
    "subscriberId": "39060001",
    "beneficiary": {
      "reference": "Patient/e.Pat-6HV3nK5"
    },
    "relationship": {
      "coding": [
        {
          "system": "https://codesystem.x12.org/005010/1069",
          "code": "18"
        }
      ]
    },
    "payor": [
      {
        "reference": "Organization/e.Ins-7KC4gB2"
      }
    ]
  }
},
{
  "fullUrl": "https://hostname/instance/api/FHIR/R4/Organization/e.Ins-7KC4gB2",
  "resource": {
    "resourceType": "Organization",
    "id": "e.Ins-7KC4gB2",
    "meta": {
      "profile": [
        "http://hl7.org/fhir/us/davinci-pas/StructureDefinition/profile-insurer"
      ]
    },
    "identifier": [
      {
        "type": {
          "coding": [
            {
              "system": "http://hl7.org/fhir/us/carin-bb/CodeSystem/C4BBIdentifierType",
              "code": "payerid"
            }
          ]
        },
        "system": "payer id system",
        "value": "Example PAS PAYERID"
      },
      {
        "system": "http://terminology.hl7.org/NamingSystem/USEIN",
        "value": "3906001"
      }
    ],
    "active": true,
    "type": [
      {
        "coding": [
          {
            "system": "https://codesystem.x12.org/005010/98",
            "code": "PR"
          }
        ]
      }
    ],
    "name": "Test Insurer",
    "telecom": [
      {
        "system": "phone",
        "value": "555-555-1234"
      },
      {
        "system": "email",
        "value": "PasInsComp@sample.com"
      },
      {
        "system": "fax",
        "value": "555-555-4321"
      }
    ],
    "contact": [
      {
        "purpose": {
          "coding": [
            {
              "code": "PAYOR"
            }
          ]
```

```
        },
        "name": {
          "family": "Contact",
          "given": [
            "Insurer",
            "T"
          ]
        },
        "telecom": [
          {
            "system": "phone",
            "value": "555-555-5678"
          },
          {
            "system": "email",
            "value": "PasInsPer@sample.com"
          },
          {
            "system": "fax",
            "value": "555-555-8765"
          }
        ]
      },
      {
        "purpose": {
          "coding": [
            {
              "code": "BILL"
            }
          ]
        },
        "name": {
          "family": "Patient",
          "given": [
            "Test",
            "T"
          ]
        },
        "telecom": [
          {
            "system": "phone",
            "value": "555-555-1111"
          },
          {
            "system": "email",
            "value": "testpatient@example.com"
          },
          {
            "system": "fax",
            "value": "555-555-2222"
          }
        ]
      }
    ]
  }
},
{
  "fullUrl": "https://hostname/instance/api/FHIR/R4/Location/e.Loc-2XT8mS9",
  "resource": {
    "resourceType": "Location",
    "id": "e.Loc-2XT8mS9",
    "meta": {
      "versionId": "1",
      "lastUpdated": "2019-06-13T09:55:47.101-04:00"
    },
    "identifier": [
      {
        "system": "http://hl7.org/fhir/sid/us-npi",
        "value": "1000000756"
      }
    ],
    "name": "Test Hospital"
  }
},
{
  "fullUrl": "https://hostname/instance/api/FHIR/R4/Patient/e.Pat-6HV3nK5",
  "resource": {
    "resourceType": "Patient",
    "id": "e.Pat-6HV3nK5",
    "meta": {
      "profile": [
        "http://hl7.org/fhir/us/davinci-pas/StructureDefinition/profile-subscriber"
      ]
    },
    "identifier": [
      {
        "type": {
          "coding": [
            {
```

```
                "system": "http://terminology.hl7.org/CodeSystem/v2-0203",
                "code": "MB"
              }
            ]
          },
          "system": "http://open.epic.com/FHIR/StructureDefinition/member-id",
          "value": "39060001"
        },
        {
          "system": "urn:oid:2.16.840.1.113883.4.1",
          "value": "1236549987"
        }
      ],
      "name": [
        {
          "family": "Patient",
          "given": [
            "Test"
          ]
        }
      ],
      "address": [
        {
          "line": [
            "1 MILKY WAY"
          ],
          "city": "VERONA",
          "state": "WI",
          "postalCode": "53593",
          "country": "US"
        }
      ],
      "gender": "female",
      "birthDate": "2000-01-01"
    }
  }
 ]
}
```


Sample response


```
{
  "resourceType": "Bundle",
  "type": "collection",
  "timestamp": "2026-01-23T18:33:51Z",
  "entry": [
    {
      "fullUrl": "https://hostname/instance/api/FHIR/R4/ClaimResponse/e4qschBhU34Rl9xca0l9id2fJY-BJ9SwX9MtNIR-t2RE3",
      "resource": {
        "resourceType": "ClaimResponse",
        "id": "e4qschBhU34Rl9xca0l9id2fJY-BJ9SwX9MtNIR-t2RE3",
        "identifier": [
          {
            "system": "urn:oid:2.16.840.1.113883.3.12345.4.1",
            "value": "1461746"
          }
        ],
        "status": "active",
        "type": {
          "coding": [
            {
              "system": "http://terminology.hl7.org/CodeSystem/claim-type",
              "code": "oral",
              "display": "Oral"
            }
          ]
        },
        "use": "preauthorization",
        "patient": {
          "reference": "Patient/e.Pat-6HV3nK5"
        },
        "created": "2026-01-23T18:33:51Z",
        "insurer": {
          "reference": "Organization/e.Ins-7KC4gB2"
        },
        "requestor": {
          "reference": "Organization/e.Org-3QA9hD7"
        },
        "request": {
          "reference": "Claim/eClm-9YQ4wP8"
        },
        "outcome": "partial",
        "preAuthRef": "1000221466-1",
        "addItem": [
          {
            "extension": [
              {
                "valueCodeableConcept": {
                  "coding": [
```

```
                {
                  "system": "https://www.nubc.org/CodeSystem/RevenueCodes",
                  "code": "0372",
                  "display": "ANESTHESIA - ANESTHESIA INCIDENT TO OTHER DIAGNOSTIC SERVICES"
                }
              ]
            },
            "url": "http://hl7.org/fhir/us/davinci-pas/StructureDefinition/extension-revenueCode"
          }
        ],
        "itemSequence": [
          1
        ],
        "productOrService": {
          "coding": [
            {
              "system": "http://www.ama-assn.org/go/cpt",
              "code": "97039",
              "display": "PHYSICAL THERAPY TREATMENT"
            }
          ]
        },
        "quantity": {
          "value": 1,
          "system": "https://codesystem.x12.org/005010/673",
          "code": "FL"
        },
        "adjudication": [
          {
            "extension": [
              {
                "extension": [
                  {
                    "valueCodeableConcept": {
                      "coding": [
                        {
                          "system": "https://codesystem.x12.org/005010/306",
                          "code": "A4",
                          "display": "Pended"
                        }
                      ]
                    },
                    "url": "http://hl7.org/fhir/us/davinci-pas/StructureDefinition/extension-reviewActionCode"
                  },
                  {
                    "valueCodeableConcept": {
                      "coding": [
                        {
                          "system": "https://codesystem.x12.org/external/886",
                          "code": "0V",
                          "display": "Requires Medical Review"
                        }
                      ]
                    },
                    "url": "reasonCode"
                  }
                ],
                "url": "http://hl7.org/fhir/us/davinci-pas/StructureDefinition/extension-reviewAction"
              }
            ],
            "category": {
              "coding": [
                {
                  "system": "http://terminology.hl7.org/CodeSystem/adjudication",
                  "code": "submitted"
                }
              ]
            }
          }
        ]
      }
    ]
  }
},
{
  "fullUrl": "https://hostname/instance/api/FHIR/R4/Organization/e.Ins-7KC4gB2",
  "resource": {
    "resourceType": "Organization",
    "id": "e.Ins-7KC4gB2",
    "identifier": [
      {
        "system": "http://terminology.hl7.org/NamingSystem/USEIN",
        "value": "3906001"
      },
      {
        "type": {
          "coding": [
            {
              "system": "http://hl7.org/fhir/us/carin-bb/CodeSystem/C4BBIdentifierType",
```

```
              "code": "payerid"
            }
          ]
        },
        "value": "Example PAS PAYERID"
      }
    ],
    "active": true,
    "name": "Test Insurer",
    "telecom": [
      {
        "system": "phone",
        "value": "555-555-1234"
      },
      {
        "system": "fax",
        "value": "555-555-4321"
      },
      {
        "system": "email",
        "value": "PasInsComp@sample.com"
      }
    ]
  }
},
{
  "fullUrl": "https://hostname/instance/api/FHIR/R4/Organization/e.Org-3QA9hD7",
  "resource": {
    "resourceType": "Organization",
    "id": "e.Org-3QA9hD7",
    "identifier": [
      {
        "system": "http://hl7.org/fhir/sid/us-npi",
        "value": "1000000764"
      }
    ],
    "active": true,
    "type": [
      {
        "coding": [
          {
            "system": "https://codesystem.x12.org/005010/98",
            "code": "X3"
          }
        ]
      }
    ],
    "name": "Test Hospital",
    "address": [
      {
        "line": [
          "1 Milky Way"
        ],
        "city": "VERONA",
        "state": "WI",
        "postalCode": "53593"
      }
    ]
  }
},
{
  "fullUrl": "https://hostname/instance/api/FHIR/R4/Patient/e.Pat-6HV3nK5",
  "resource": {
    "resourceType": "Patient",
    "id": "e.Pat-6HV3nK5",
    "identifier": [
      {
        "type": {
          "coding": [
            {
              "system": "http://terminology.hl7.org/CodeSystem/v2-0203",
              "code": "MB"
            }
          ]
        },
        "system": "http://open.epic.com/FHIR/StructureDefinition/member-id",
        "value": "39060001"
      }
    ],
    "name": [
      {
        "family": "Patient",
        "given": [
          "Test"
        ]
      }
    ],
    "gender": "female",
    "birthDate": "2000-01-01",
```

```
        "address": [
          {
            "line": [
              "1 MILKY WAY"
            ],
            "city": "VERONA",
            "state": "WI",
            "postalCode": "53593"
          }
        ]
      }
    }
  ]
}
```

14.1.12 Claim.$submit (Prior Auth) (R4)

File: site/apis/14-CMS-Incoming/1-R4/11274-Claim-submit-Prior-Auth-R4.html
Epic API ID | 11274
FHIR version | R4
Categories | CMS Incoming
API type | Industry-Standard
USCDI | No
HTTP method | POST
URL template | /api/FHIR/R4/Claim/$submit
Supports OAuth 2.0 | True
Supported user types | Backend Systems and Non-OAuth 2.0, Clinicians or Administrative Users
Performs scope validation | False
Source | https://fhir.epic.com/Specifications?api=11274

Description

This web service enables providers to submit prior authorization requests to the utilization management system using FHIR technology. It is an alternative to an ANSI X12 278 Health Care Services Request For Review message, which is the EDI standard historically used by payers and providers to exchange prior authorization requests electronically.

Providers can use this service as standalone, following Coverage Requirements Discovery (CRD) when prior authorization is determined necessary, or after Documentation Templates and Rules (DTR) interactions to submit QuestionnaireResponse resources alongside the initial authorization request. This API functions similarly to the incoming 278 request API but, instead, uses the FHIR specification defined in

Da Vinci Prior Authorization Support (PAS) implementation guide v2.1.0 for PAS Claim

Request parameters

Name | Type | Optional | Array | Cardinality | Description
Bundle (R4) | Bundle | Required | | 1..1 | A collection of resources.
Bundle (R4).entry | BackboneElement | Required | Yes | 1..* | Entries in the bundle – each entry contains a resource. Supported resources: Claim, Coverage, Patient, Practitioner, PractitionerRole, Organization, Location, ServiceRequest, DeviceRequest, DocumentReference, and QuestionnaireResponse Bundle. Must include only one Claim resource. All referenced resources need to be included as well.
Bundle (R4).entry.fullUrl | uri | Required | | 1..1 | URI for the resource (Absolute URL server address or URI for UUID/OID).
Bundle (R4).entry.resource | ResourceContainer | Required | | 1..1 | A resource in the bundle.
Bundle (R4).entry.resource.Bundle | Bundle | Conditional | | 0..1 | Bundle used to submit a QuestionnaireResponse. Can contain other referenced resources. Must contain a QuestionnaireResponse resource, and that must be listed first. Exactly one of DocumentReference or Bundle must be present in a single Attachment parameter. For externally processed bundles, not all fields are documented here. The specifications of the entities that the specific customer contracts with should be consulted to verify all required fields are present. Refer to Structure Definition of DTR QRBundle v2.1.0 for more information.
Bundle (R4).entry.resource.Bundle.entry | BackboneElement | Required | Yes | 1..* | A container for a resource included in the Bundle. Each entry represents one resource that is part of the structured attachment payload.
Bundle (R4).entry.resource.Bundle.entry.resource | ResourceContainer | Required | | 1..1 | The resource included in this bundle entry. For DTR submissions, this includes the QuestionnaireResponse and any supporting resources referenced by it.
Bundle (R4).entry.resource.Bundle.entry.resource.QuestionnaireResponse | Resource | Required | | 1..1 | Completed responses to the Questionnaire which might be included in this Bundle. Contains answers submitted as structured attachment data. Must be listed as the first element and Bundles must not contain more than one QuestionnaireResponse resource. Refer to Structure Definition of DTR Questionnaire Response v2.1.0 for more information.
Bundle (R4).entry.resource.Bundle.entry.resource.QuestionnaireResponse.authored | dateTime | Required | | 1..1 | Date the answers were most recently gathered.
Bundle (R4).entry.resource.Bundle.entry.resource.QuestionnaireResponse.extension (intendedUse) (also: extension (intendedUse)) | Extension | Optional | Yes | 0..1 | Indicates how the EHR is to use the information with respect to the associated orders/records.
Bundle (R4).entry.resource.Bundle.entry.resource.QuestionnaireResponse.extension (qr-context) (also: extension (qr-context)) | Extension | Optional | Yes | 2..* | Identifies the orders and coverages associated with the specified QuestionnaireResponse. The QuestionnaireResponse must have at least one context that refers to a patient Coverage and at least one context that refers to a ServiceRequest resource.
Bundle (R4).entry.resource.Bundle.entry.resource.QuestionnaireResponse.id | id | Required | | 1..1 | The identifier of this QuestionnaireResponse. It is required to be submitted with the same ID from when the QuestionnaireResponse resource was retrieved during a previous part of the workflow.
Bundle (R4).entry.resource.Bundle.entry.resource.QuestionnaireResponse.item | BackboneElement | Required | Yes | 1..* | A response item corresponding to a question or group in the Questionnaire. Items can be nested several levels deep.
Bundle (R4).entry.resource.Bundle.entry.resource.QuestionnaireResponse.item.answer | BackboneElement | Required | Yes | 1..1 | The answer provided for this item. Answer types should be passed back as originally sent. A change in value type could lead to errors. Only one answer is

supported per question. Exactly one value[x] element must be present in each answer.
Bundle (R4).entry.resource.Bundle.entry.resource.QuestionnaireResponse.item.answer.valueAttachment | Attachment | Conditional | | 0..1 | File attachment answer. The valueAttachment.contentType must be "application/pdf" for a PDF attachment. Other attachment types are ignored.
Bundle (R4).entry.resource.Bundle.entry.resource.QuestionnaireResponse.item.answer.valueBoolean | boolean | Conditional | | 0..1 | Boolean true/false answer.
Bundle (R4).entry.resource.Bundle.entry.resource.QuestionnaireResponse.item.answer.valueCoding | Coding | Conditional | | 0..1 | Coded answer.
Bundle (R4).entry.resource.Bundle.entry.resource.QuestionnaireResponse.item.answer.valueDate | date | Conditional | | 0..1 | Date answer.
Bundle (R4).entry.resource.Bundle.entry.resource.QuestionnaireResponse.item.answer.valueDateTime | dateTime | Conditional | | 0..1 | Date and time answer.
Bundle (R4).entry.resource.Bundle.entry.resource.QuestionnaireResponse.item.answer.valueDecimal | decimal | Conditional | | 0..1 | Decimal number answer.
Bundle (R4).entry.resource.Bundle.entry.resource.QuestionnaireResponse.item.answer.valueQuantity | Quantity | Conditional | | 0..1 | Quantity with unit.
Bundle (R4).entry.resource.Bundle.entry.resource.QuestionnaireResponse.item.answer.valueString | string | Conditional | | 0..1 | Free-text string answer.
Bundle (R4).entry.resource.Bundle.entry.resource.QuestionnaireResponse.item.answer.valueTime | time | Conditional | | 0..1 | Time answer.
Bundle (R4).entry.resource.Bundle.entry.resource.QuestionnaireResponse.item.item | BackboneElement | Required | Yes | 1..* | A response item corresponding to a question or group in the Questionnaire. Items can be nested several levels deep.
Bundle (R4).entry.resource.Bundle.entry.resource.QuestionnaireResponse.item.linkId | string | Required | | 1..1 | The ID connecting this item to its question definition in the system. Must be preserved from previous parts of the workflow.
Bundle (R4).entry.resource.Bundle.entry.resource.QuestionnaireResponse.item.text | string | Optional | | 0..1 | The display text for the question or group.
Bundle (R4).entry.resource.Bundle.entry.resource.QuestionnaireResponse.meta | Meta | Optional | | 0..1 | Metadata about the response resource.
Bundle (R4).entry.resource.Bundle.entry.resource.QuestionnaireResponse.meta.profile | String | Optional | Yes | 0..1 | Declares the profile to which the QuestionnaireResponse resource conforms. URL: http://hl7.org/fhir/us/davinci-dtr/StructureDefinition/dtr-questionnaireresponse
Bundle (R4).entry.resource.Bundle.entry.resource.QuestionnaireResponse.questionnaire | canonical | Required | | 1..1 | Canonical reference to the Questionnaire definition which might be included in the same Bundle, might be a contained reference, or might just be a reference. Must match the Questionnaire.url value of the included Questionnaire (if included).
Bundle (R4).entry.resource.Bundle.entry.resource.QuestionnaireResponse.status | code | Required | | 1..1 | The associated QuestionnaireResponseStatus of the questionnaire response. Expected to be "completed" for submission. URL: http://hl7.org/fhir/ValueSet/questionnaire-answers-status
Bundle (R4).entry.resource.Bundle.entry.resource.QuestionnaireResponse.subject | Reference | Required | | 1..1 | Reference to the Patient that this response is about.
Bundle (R4).entry.resource.Bundle.entry.resource.QuestionnaireResponse.subject.reference | String | Required | | 1..1 | Reference to the Patient that this response is about.
Bundle (R4).entry.resource.Bundle.entry.resource.QuestionnaireResponse.text | Narrative | Optional | | 0..1 | Human-readable narrative summary of the QuestionnaireResponse.
Bundle (R4).entry.resource.Claim | Resource | Required | | 1..1 | The prior authorization Claim resource contains details about the requested services, along with references to supporting clinical and administrative resources such as Patient, Coverage, Practitioner, Organization, and relevant clinical documentation.
Bundle (R4).entry.resource.Claim.accident | BackboneElement | Optional | | 0..1 | Accident information.
Bundle (R4).entry.resource.Claim.accident.date | date | Required | | 1..1 | Accident date.
Bundle (R4).entry.resource.Claim.billablePeriod | Period | Optional | | 0..1 | Relevant timeframe for the claim, use as fallback dates for supportingInfo:admissionDate/dischargeDate and supportingInfo:patientEvent.
Bundle (R4).entry.resource.Claim.billablePeriod.end | String | Required | | 1..1 | End dateTime.
Bundle (R4).entry.resource.Claim.billablePeriod.start | String | Required | | 1..1 | Start dateTime.
Bundle (R4).entry.resource.Claim.careTeam | BackboneElement | Optional | Yes | 0..* | It can be either: Care team providers that are applicable to all services being requested. Care team providers that are applicable to a specific item (as referenced by that item).
Bundle (R4).entry.resource.Claim.careTeam.extension (careTeamClaimScope) (also: extension (careTeamClaimScope)) | Extension | Required | Yes | 1..1 | Whether this care team element applies to the whole claim. URL: http://hl7.org/fhir/us/davinci-pas/StructureDefinition/extension-careTeamClaimScope
Bundle (R4).entry.resource.Claim.careTeam.extension (careTeamClaimScope).url | uri | Required | | 1..1 | URL of the extension: http://hl7.org/fhir/us/davinci-pas/StructureDefinition/extension-careTeamClaimScope
Bundle (R4).entry.resource.Claim.careTeam.extension (careTeamClaimScope).valueBoolean | boolean | Required | | 1..1 | True if the careTeam element applies to the entire claim. False if the careTeam element applies a specific item.
Bundle (R4).entry.resource.Claim.careTeam.provider | Reference | Required | | 1..1 | Member of the care team who renders the service(s). A reference to a Practitioner, PractitionerRole, or Organization resource.
Bundle (R4).entry.resource.Claim.careTeam.qualification | CodeableConcept | Optional | | 0..1 | The qualification of practitioner. Must include a coding system of https://codesystem.x12.org/005010/127.
Bundle (R4).entry.resource.Claim.careTeam.role | CodeableConcept | Optional | | 0..1 | Function within the care team. Must include a coding system of https://codesystem.x12.org/005010/98.
Bundle (R4).entry.resource.Claim.careTeam.sequence | positiveInt | Required | | 1..1 | Sequence number of careTeam member.
Bundle (R4).entry.resource.Claim.created | dateTime | Optional | | 0..1 | Resource creation date.
Bundle (R4).entry.resource.Claim.diagnosis | BackboneElement | Optional | Yes | 0..* | Diagnosis information.
Bundle (R4).entry.resource.Claim.diagnosis.diagnosisCodeableConcept | CodeableConcept | Required | | 1..1 | Diagnosis code. Must include one of the allowed coding systems: http://hl7.org/fhir/sid/icd-9-cm http://hl7.org/fhir/sid/icd-10-cm
Bundle (R4).entry.resource.Claim.diagnosis.sequence | positiveInt | Required | | 1..1 | Sequence number for diagnosis element.
Bundle (R4).entry.resource.Claim.enterer | Reference | Optional | | 0..1 | Author of the claim. A reference to a Practitioner or PractitionerRole resource.
Bundle (R4).entry.resource.Claim.extension (administrationReferenceNumber) (also: extension (administrationReferenceNumber)) | Extension | Conditional | Yes | 0..* | Extension for administrationReferenceNumber. Either Previous Review Administrative Reference number or Previous Review Authorization number is needed for updates to match to previous request. The value must be taken from the preAuthRef element of a ClaimResponse to the previous Claim being updated. URL: http://hl7.org/fhir/us/davinci-pas/StructureDefinition/extension-administrationReferenceNumber

Bundle (R4).entry.resource.Claim.extension (administrationReferenceNumber).url | uri | Required | | 1..1 | URL of the extension: http://hl7.org/fhir/us/davinci-pas/StructureDefinition/extension-administrationReferenceNumber

Bundle (R4).entry.resource.Claim.extension (administrationReferenceNumber).valueString | string | Required | | 1..1 | Administration reference number. The value must be taken from the preAuthRef element of a ClaimResponse to the previous Claim being updated.

Bundle (R4).entry.resource.Claim.extension (authorizationNumber) (also: extension (authorizationNumber)) | Extension | Optional | Yes | 0..1 | A string assigned by the utilization management organization to an authorized review outcome associated with this service item. Either Previous Review Administrative Reference number or Previous Review Authorization number is needed for updates to match to previous request. The value must be taken from the preAuthRef element of a ClaimResponse to the previous Claim being updated. URL: http://hl7.org/fhir/us/davinci-pas/StructureDefinition/extension-authorizationNumber

Bundle (R4).entry.resource.Claim.extension (authorizationNumber).url | uri | Required | | 1..1 | URL of the extension: http://hl7.org/fhir/us/davinci-pas/StructureDefinition/extension-authorizationNumber

Bundle (R4).entry.resource.Claim.extension (authorizationNumber).valueString | string | Required | | 1..1 | Authorization number.

Bundle (R4).entry.resource.Claim.extension (encounter) (also: extension (encounter)) | Extension | Optional | Yes | 0..1 | Information about a hospital claim being requested. URL: http://hl7.org/fhir/5.0/StructureDefinition/extension-Claim.encounter

Bundle (R4).entry.resource.Claim.extension (encounter).url | uri | Required | | 1..1 | URL of the extension: http://hl7.org/fhir/5.0/StructureDefinition/extension-Claim.encounter

Bundle (R4).entry.resource.Claim.extension (encounter).valueReference | Reference | Required | | 1..1 | A reference to an Encounter resource.

Bundle (R4).entry.resource.Claim.extension (homeHealthCareInformation) (also: extension (homeHealthCareInformation)) | Extension | Optional | Yes | 0..1 | Extensions for homeHealthCareInformation, equivalent to CR6 (ANSI X12 value). URL: http://hl7.org/fhir/us/davinci-pas/StructureDefinition/extension-homeHealthCareInformation

Bundle (R4).entry.resource.Claim.extension (homeHealthCareInformation).extension (date) (also: extension (date)) | Extension | Required | Yes | 1..1 | Home health start date, equivalent to CR602 (ANSI X12 value). If prognosis is populated, date must be populated as well. URL: “date”

Bundle (R4).entry.resource.Claim.extension (homeHealthCareInformation).extension (date).url | uri | Required | | 1..1 | URL of the extension: “date”

Bundle (R4).entry.resource.Claim.extension (homeHealthCareInformation).extension (date).valueDate | date | Required | | 1..1 | Home health start date, equivalent to CR602 (ANSI X12 value). If prognosis is populated, date is required to be populated as well.

Bundle (R4).entry.resource.Claim.extension (homeHealthCareInformation).extension (prognosis) (also: extension (prognosis)) | Extension | Required | Yes | 1..1 | Prognosis code, equivalent to CR601 (ANSI X12 value). URL: “prognosis”

Bundle (R4).entry.resource.Claim.extension (homeHealthCareInformation).extension (prognosis).url | uri | Required | | 1..1 | URL of the extension: “prognosis”

Bundle (R4).entry.resource.Claim.extension (homeHealthCareInformation).extension (prognosis).valueCodeableConcept | CodeableConcept | Required | | 1..1 | Prognosis code. Must include a coding system of https://codesystem.x12.org/005010/923.

Bundle (R4).entry.resource.Claim.extension (homeHealthCareInformation).url | uri | Required | | 1..1 | URL of the extension: http://hl7.org/fhir/us/davinci-pas/StructureDefinition/extension-homeHealthCareInformation

Bundle (R4).entry.resource.Claim.extension (levelOfServiceCode) (also: extension (levelOfServiceCode)) | Extension | Optional | Yes | 0..1 | Extension for levelOfServiceCode. URL: http://hl7.org/fhir/us/davinci-pas/StructureDefinition/extension-levelOfServiceCode

Bundle (R4).entry.resource.Claim.extension (levelOfServiceCode).url | uri | Required | | 1..1 | URL of the extension: http://hl7.org/fhir/us/davinci-pas/StructureDefinition/extension-levelOfServiceCode

Bundle (R4).entry.resource.Claim.extension (levelOfServiceCode).valueCodeableConcept | CodeableConcept | Required | | 1..1 | Level of service type code. Must include a coding system of https://codesystem.x12.org/005010/1338.

Bundle (R4).entry.resource.Claim.facility | Reference | Optional | | 0..1 | Facility where the services were provided. A reference to a Location resource.

Bundle (R4).entry.resource.Claim.id | id | Optional | | 0..1 | Claim ID.

Bundle (R4).entry.resource.Claim.identifier | Identifier | Required | Yes | 1..* | Business identifier for the claim, equivalent to TRN (ANSI X12 value).

Bundle (R4).entry.resource.Claim.identifier.extension (subDepartment) (also: extension (subDepartment)) | Extension | Optional | Yes | 0..1 | Extension for subDepartment. An additional element that provides a further subdivision within the organization granting the identifier, equivalent to TRN04 (ANSI X12 value). URL: http://hl7.org/fhir/us/davinci-pas/StructureDefinition/extension-identifierSubDepartment

Bundle (R4).entry.resource.Claim.identifier.extension (subDepartment).url | uri | Required | | 1..1 | URL of the extension: http://hl7.org/fhir/us/davinci-pas/StructureDefinition/extension-identifierSubDepartment

Bundle (R4).entry.resource.Claim.identifier.extension (subDepartment).valueString | string | Required | | 1..1 | Additional reference number.

Bundle (R4).entry.resource.Claim.identifier.system | String | Required | | 1..1 | This System of the identifier, equivalent to TRN03 (ANSI X12 value). Should use a scheme of 'urn:trnorg:<TRN03>' (ANSI X12 value).

Bundle (R4).entry.resource.Claim.identifier.value | String | Required | | 1..1 | System of the identifier, equivalent to TRN03 (ANSI X12 value).

Bundle (R4).entry.resource.Claim.insurance | BackboneElement | Required | Yes | 1..* | Patient insurance information.

Bundle (R4).entry.resource.Claim.insurance.coverage | Reference | Required | | 1..1 | A reference to a Coverage resource.

Bundle (R4).entry.resource.Claim.insurance.focal | boolean | Required | | 1..1 | A flag to indicate if the coverage is used for the prior authorization. The first coverage with a focal value of true is used.

Bundle (R4).entry.resource.Claim.insurer | Reference | Required | | 1..1 | Target of the request, equivalent to UMO loop (2000A). A reference to an Organization resource.

Bundle (R4).entry.resource.Claim.item | BackboneElement | Required | Yes | 1..* | Product or service provided.

Bundle (R4).entry.resource.Claim.item.careTeamSequence | positiveInt | Optional | Yes | 0..* | Sequence number of the related care team.

Bundle (R4).entry.resource.Claim.item.category | CodeableConcept | Required | | 1..1 | Code to identify the general type of benefits under which products and services are provided, equivalent to 2000F UM03 (ANSI X12 value). Must include one of the allowed coding systems: https://x12.org/codes/service-type-codes https://codesystem.x12.org/005010/1365.

Bundle (R4).entry.resource.Claim.item.diagnosisSequence | positiveInt | Optional | Yes | 0..* | Sequence number of the related diagnosis.

Bundle (R4).entry.resource.Claim.item.extension (administrationReferenceNumber) (also: extension (administrationReferenceNumber)) | Extension | Optional | Yes | 0..1 | Identifier assigned by the UMO to the original disallowed review outcome for this service item. URL: http://hl7.org/fhir/us/davinci-pas/StructureDefinition/extension-administrationReferenceNumber

Bundle (R4).entry.resource.Claim.item.extension (administrationReferenceNumber).url | uri | Required | | 1..1 | URL of the extension: http://hl7.org/fhir/us/davinci-pas/StructureDefinition/extension-administrationReferenceNumber

Bundle (R4).entry.resource.Claim.item.extension (administrationReferenceNumber).valueString | string | Required | | 1..1 | Administrative reference number.

Bundle (R4).entry.resource.Claim.item.extension (authorizationNumber) (also: extension (authorizationNumber)) | Extension | Optional | Yes | 0..1 | A string assigned by the utilization management organization to an authorized review outcome associated with this service item. Either Previous Review Administrative Reference number or Previous Review Authorization number is needed for updates to match to previous request. The value must be taken from the preAuthRef element of a ClaimResponse to the previous Claim being updated. URL: http://hl7.org/fhir/us/davinci-pas/StructureDefinition/extension-authorizationNumber

Bundle (R4).entry.resource.Claim.item.extension (authorizationNumber).url | uri | Required | | 1..1 | URL of the extension: http://hl7.org/fhir/us/davinci-pas/StructureDefinition/extension-authorizationNumber

Bundle (R4).entry.resource.Claim.item.extension (authorizationNumber).valueString | string | Required | | 1..1 | Authorization number.

Bundle (R4).entry.resource.Claim.item.extension (certificationType) (also: extension (certificationType)) | Extension | Required | Yes | 0..1 | A code representing the type of certification being requested, equivalent to 2000F UM02 (ANSI X12 value). URL: http://hl7.org/fhir/us/davinci-pas/StructureDefinition/extension-certificationType

Bundle (R4).entry.resource.Claim.item.extension (certificationType).url | uri | Required | | 1..1 | URL of the extension: http://hl7.org/fhir/us/davinci-pas/StructureDefinition/extension-certificationType

Bundle (R4).entry.resource.Claim.item.extension (certificationType).valueCodeableConcept | CodeableConcept | Required | | 1..1 | Certification type. Must include a coding system of https://codesystem.x12.org/005010/1322.

Bundle (R4).entry.resource.Claim.item.extension (infoChanged) (also: extension (infoChanged)) | Extension | Optional | Yes | 0..1 | Only used for update message, indicates how the piece of information has changed. If the certification type is I-Initial, the code cannot be “changed”. If the certification type is S-Revision, the code cannot be “added”. If the certification type is 3-Cancel, the code cannot be “added”. URL: http://hl7.org/fhir/us/davinci-pas/StructureDefinition/extension-infoChanged

Bundle (R4).entry.resource.Claim.item.extension (infoChanged).url | uri | Required | | 1..1 | URL of the extension: http://hl7.org/fhir/us/davinci-pas/StructureDefinition/extension-infoChanged

Bundle (R4).entry.resource.Claim.item.extension (infoChanged).valueCode | code | Required | | 1..1 | Value of “changed” indicates previously sent information has been changed. Value of “added” indicates new information that was not sent previously.

Bundle (R4).entry.resource.Claim.item.extension (itemTraceNumber) (also: extension (itemTraceNumber)) | Extension | Optional | Yes | 0..* | Uniquely identifies this claim item, equivalent to 2000F TRN (ANSI X12 value). URL: http://hl7.org/fhir/us/davinci-pas/StructureDefinition/extension-itemTraceNumber

Bundle (R4).entry.resource.Claim.item.extension (itemTraceNumber).url | uri | Required | | 1..1 | URL of the extension: http://hl7.org/fhir/us/davinci-pas/StructureDefinition/extension-itemTraceNumber

Bundle (R4).entry.resource.Claim.item.extension (itemTraceNumber).valueIdentifier | Identifier | Required | | 1..1 | Trace number.

Bundle (R4).entry.resource.Claim.item.extension (itemTraceNumber).valueIdentifier.extension (subDepartment) (also: extension (subDepartment)) | Extension | Optional | Yes | 0..1 | An additional element that provides a further subdivision within the organization granting the identifier, equivalent to TRN04 (ANSI X12 value). URL: http://hl7.org/fhir/us/davinci-pas/StructureDefinition/extension-identifierSubDepartment

Bundle (R4).entry.resource.Claim.item.extension (itemTraceNumber).valueIdentifier.extension (subDepartment).url | uri | Required | | 1..1 | URL of the extension: http://hl7.org/fhir/us/davinci-pas/StructureDefinition/extension-identifierSubDepartment

Bundle (R4).entry.resource.Claim.item.extension (itemTraceNumber).valueIdentifier.extension (subDepartment).valueString | string | Required | | 1..1 | Additional reference number.

Bundle (R4).entry.resource.Claim.item.extension (itemTraceNumber).valueIdentifier.system | String | Required | | 1..1 | System of the identifier, equivalent to TRN03 (ANSI X12 value). Should use a scheme of 'urn:trnorg:<TRN03>'.

Bundle (R4).entry.resource.Claim.item.extension (itemTraceNumber).valueIdentifier.value | String | Required | | 1..1 | Value of the identifier, equivalent to TRN02 (ANSI X12 value).

Bundle (R4).entry.resource.Claim.item.extension (requestedService) (also: extension (requestedService)) | Extension | Optional | Yes | 0..1 | The details of the service being requested. Only used for requested quantity. URL: http://hl7.org/fhir/us/davinci-pas/StructureDefinition/extension-requestedService

Bundle (R4).entry.resource.Claim.item.extension (requestedService).url | uri | Required | | 1..1 | URL of the extension: http://hl7.org/fhir/us/davinci-pas/StructureDefinition/extension-requestedService

Bundle (R4).entry.resource.Claim.item.extension (requestedService).valueReference | Reference | Required | | 1..1 | Reference to requested service. It can be a reference to: ServiceRequest DeviceRequest

Bundle (R4).entry.resource.Claim.item.extension (requestType) (also: extension (requestType)) | Extension | Optional | Yes | 0..1 | A code that identifies the type of service being requested, equivalent to 2000F UM01 (ANSI X12 value). URL: http://hl7.org/fhir/us/davinci-pas/StructureDefinition/extension-serviceItemRequestType

Bundle (R4).entry.resource.Claim.item.extension (requestType).url | uri | Required | | 1..1 | URL of the extension: http://hl7.org/fhir/us/davinci-pas/StructureDefinition/extension-serviceItemRequestType

Bundle (R4).entry.resource.Claim.item.extension (requestType).valueCodeableConcept | CodeableConcept | Required | | 1..1 | Request type. Must include a coding system of https://codesystem.x12.org/005010/1525.

Bundle (R4).entry.resource.Claim.item.informationSequence | positiveInt | Optional | Yes | 0..* | Sequence number of the related supporting information. Only sequence number of supportingInfo additionalInformation or messageText is considered.

Bundle (R4).entry.resource.Claim.item.locationCodeableConcept | CodeableConcept | Optional | | 0..1 | Place of service, equivalent to 2000F UM04. Must include one of the allowed coding systems: https://www.cms.gov/Medicare/Coding/place-of-service-codes/Place_of_Service_Code_Set. https://www.nubc.org/CodeSystem/TypeOfBill.

Bundle (R4).entry.resource.Claim.item.modifier | CodeableConcept | Optional | Yes | 0..* | Service modifiers. Must include one of the allowed coding systems: http://www.cms.gov/Medicare/Coding/HCPCSReleaseCodeSets. http://www.ama-assn.org/go/cpt. https://open.epic.com/FHIR/(custom_OID)/custom-procedure-modifier.

Bundle (R4).entry.resource.Claim.item.modifierExtension (infoCanceledFlag) (also: modifierExtension (infoCanceledFlag)) | Extension | Optional | Yes | 0..* | Used only for update message, indicates that this piece of information is not to be used. If the certification type is I-Initial or S-Revision, this modifier extension cannot be included. If the certification type is 3-Cancel, this modifier extension must be included. URL: http://hl7.org/fhir/us/davinci-pas/StructureDefinition/modifierextension-infoCancelled

Bundle (R4).entry.resource.Claim.item.modifierExtension (infoCanceledFlag).url | uri | Required | | 1..1 | URL of the extension: http://hl7.org/fhir/us/davinci-pas/StructureDefinition/modifierextension-infoCancelled

Bundle (R4).entry.resource.Claim.item.modifierExtension (infoCanceledFlag).valueBoolean | boolean | Required | | 1..1 | It is for whether this information is not being used. Required to be true.

Bundle (R4).entry.resource.Claim.item.productOrService | CodeableConcept | Required | | 1..1 | Service code. Must include one of the allowed coding systems: http://terminology.hl7.org/CodeSystem/data-absent-reason. https://codesystem.x12.org/005010/1365. http://www.cms.gov/Medicare/Coding/HCPCSReleaseCodeSets. http://www.ama-assn.org/go/cpt. For coding system http://terminology.hl7.org/CodeSystem/data-absent-reason, the code must be "not-applicable".

Bundle (R4).entry.resource.Claim.item.quantity | Quantity | Optional | | 0..1 | Requested quantity.

Bundle (R4).entry.resource.Claim.item.quantity.code | String | Required | | 1..1 | Code from the system.

Bundle (R4).entry.resource.Claim.item.quantity.system | String | Required | | 1..1 | System of the code, required to be https://codesystem.x12.org/005010/673.

Bundle (R4).entry.resource.Claim.item.quantity.value | Decimal | Required | | 1..1 | Numeric value.

Bundle (R4).entry.resource.Claim.item.revenue | CodeableConcept | Optional | | 0..1 | Revenue code. Must include a coding system of https://www.nubc.org/CodeSystem/RevenueCodes.

Bundle (R4).entry.resource.Claim.item.sequence | positiveInt | Required | | 1..1 | Sequence number of the item element.

Bundle (R4).entry.resource.Claim.item.servicedDate | date | Optional | | 0..1 | Service date.

Bundle (R4).entry.resource.Claim.item.servicedPeriod | Period | Optional | | 0..1 | Service period.

Bundle (R4).entry.resource.Claim.item.servicedPeriod.end | String | Required | | 1..1 | End dateTime.

Bundle (R4).entry.resource.Claim.item.servicedPeriod.start | String | Required | | 1..1 | Start dateTime.

Bundle (R4).entry.resource.Claim.patient | Reference | Required | | 1..1 | A reference to the beneficiary patient. Expected to match coverage.beneficiary.

Bundle (R4).entry.resource.Claim.provider | Reference | Required | | 1..1 | The provider who is responsible for the prior authorization, equivalent to Requester loop (2000B). A reference to either Organization or PractitionerRole.

Bundle (R4).entry.resource.Claim.related | BackboneElement | Conditional | Yes | 0..1 | It is used only for update messages: references to prior Claim.

Bundle (R4).entry.resource.Claim.related.claim | Reference | Required | | 1..1 | Reference to the related Claim. Must not include the referenced Claim resource in the request bundle.

Bundle (R4).entry.resource.Claim.related.relationship | CodeableConcept | Required | | 1..1 | How the reference Claim is related. Must include a coding system of http://terminology.hl7.org/CodeSystem/ex-relatedclaimrelationship, and code must be “prior”.

Bundle (R4).entry.resource.Claim.status | code | Required | | 1..1 | Status of the Claim resource, required to be “active”.

Bundle (R4).entry.resource.Claim.supportingInfo (additionalInformation) (also: supportingInfo (additionalInformation)) | BackboneElement | Optional | Yes | 0..* | Additional supporting information for the request.

Bundle (R4).entry.resource.Claim.supportingInfo (additionalInformation).category | CodeableConcept | Required | | 1..1 | Must include a coding system of http://hl7.org/fhir/us/davinci-pas/CodeSystem/PASTempCodes. The code must be "additionalInformation"

Bundle (R4).entry.resource.Claim.supportingInfo (additionalInformation).sequence | positiveInt | Required | | 1..1 | Sequence number of the supportingInfo element.

Bundle (R4).entry.resource.Claim.supportingInfo (additionalInformation).valueReference | Reference | Required | | 1..1 | Used in AdditionalInformation, reference to additional information resource. A reference to DocumentReference or QuestionnaireResponseBundle.

Bundle (R4).entry.resource.Claim.supportingInfo (admissionDates) (also: supportingInfo (admissionDates)) | BackboneElement | Optional | Yes | 0..1 | Admission dates of a hospital admission being requested.

Bundle (R4).entry.resource.Claim.supportingInfo (admissionDates).category | CodeableConcept | Required | | 1..1 | Must include a coding system of http://hl7.org/fhir/us/davinci-pas/CodeSystem/PASTempCodes. The code must be "admissionDates".

Bundle (R4).entry.resource.Claim.supportingInfo (admissionDates).sequence | positiveInt | Required | | 1..1 | Sequence number of the supportingInfo element.

Bundle (R4).entry.resource.Claim.supportingInfo (admissionDates).timingDate | date | Optional | | 0..1 | Admission date.

Bundle (R4).entry.resource.Claim.supportingInfo (admissionDates).timingPeriod | Period | Conditional | | 0..1 | The admission period. This is required if timingDate is absent and is not used if timingDate is present.

Bundle (R4).entry.resource.Claim.supportingInfo (admissionDates).timingPeriod.end | String | Required | | 1..1 | End dateTime.

Bundle (R4).entry.resource.Claim.supportingInfo (admissionDates).timingPeriod.start | String | Required | | 1..1 | Start dateTime.

Bundle (R4).entry.resource.Claim.supportingInfo (dischargeDates) (also: supportingInfo (dischargeDates)) | BackboneElement | Optional | Yes | 0..1 | Discharge dates of a hospital admission being requested.

Bundle (R4).entry.resource.Claim.supportingInfo (dischargeDates).category | CodeableConcept | Required | | 1..1 | Must include a coding system of http://hl7.org/fhir/us/davinci-pas/CodeSystem/PASTempCodes. The code must be "dischargeDates"

Bundle (R4).entry.resource.Claim.supportingInfo (dischargeDates).sequence | positiveInt | Required | | 1..1 | Sequence number of the supportingInfo element.

Bundle (R4).entry.resource.Claim.supportingInfo (dischargeDates).timingDate | date | Required | | 1..1 | Discharge date.

Bundle (R4).entry.resource.Claim.supportingInfo (messageText) (also: supportingInfo (messageText)) | BackboneElement | Optional | Yes | 0..* | Free text message to the UMO.

Bundle (R4).entry.resource.Claim.supportingInfo (messageText).category | CodeableConcept | Required | | 1..1 | Must include a coding system of http://hl7.org/fhir/us/davinci-pas/CodeSystem/PASTempCodes. The code must be "freeFormMessage"

Bundle (R4).entry.resource.Claim.supportingInfo (messageText).sequence | positiveInt | Required | | 1..1 | Sequence number of the supportingInfo element.

Bundle (R4).entry.resource.Claim.supportingInfo (messageText).valueString | string | Required | | 1..1 | Free text message, equivalent to MSG01.

Bundle (R4).entry.resource.Claim.supportingInfo (patientEvent) (also: supportingInfo (patientEvent)) | BackboneElement | Optional | Yes | 0..1 | Event dates being requested.

Bundle (R4).entry.resource.Claim.supportingInfo (patientEvent).category | CodeableConcept | Required | | 1..1 | Must include a coding system of http://hl7.org/fhir/us/davinci-pas/CodeSystem/PASTempCodes. The code must be "patientEvent".

Bundle (R4).entry.resource.Claim.supportingInfo (patientEvent).sequence | positiveInt | Required | | 1..1 | Sequence number of the supportingInfo element.

Bundle (R4).entry.resource.Claim.supportingInfo (patientEvent).timingDate | date | Optional | | 0..1 | Patient Event Date.

Bundle (R4).entry.resource.Claim.supportingInfo (patientEvent).timingPeriod | Period | Conditional | | 0..1 | The patient event period. This is required if timingDate is absent and is not used if timingDate is present.

Bundle (R4).entry.resource.Claim.supportingInfo (patientEvent).timingPeriod.end | String | Required | | 1..1 | End dateTime.

Bundle (R4).entry.resource.Claim.supportingInfo (patientEvent).timingPeriod.start | String | Required | | 1..1 | Start dateTime.

Bundle (R4).entry.resource.Claim.type | CodeableConcept | Required | | 1..1 | The type of claim. Must include a coding system of http://terminology.hl7.org/CodeSystem/claim-type.

Bundle (R4).entry.resource.Claim.use | code | Required | | 1..1 | The purpose of the claim, required to be “preauthorization”.

Bundle (R4).entry.resource.Coverage | Resource | Required | | 1..* | Coverage resource.

Bundle (R4).entry.resource.Coverage.beneficiary | Reference | Required | | 1..1 | Reference to beneficiary, a Patient resource.

Bundle (R4).entry.resource.Coverage.class (group) (also: class (group)) | BackboneElement | Optional | Yes | 0..1 | Group class.

Bundle (R4).entry.resource.Coverage.class (group).type | CodeableConcept | Required | | 1..1 | Code must be "group". System must be http://terminology.hl7.org/CodeSystem/coverage-class.

Bundle (R4).entry.resource.Coverage.class (group).value | string | Required | | 1..1 | Group ID.

Bundle (R4).entry.resource.Coverage.class (plan) (also: class (plan)) | BackboneElement | Optional | Yes | 0..1 | Plan Class.

Bundle (R4).entry.resource.Coverage.class (plan).name | string | Optional | | 0..1 | Plan name.

Bundle (R4).entry.resource.Coverage.class (plan).type | CodeableConcept | Required | | 1..1 | Code must be "plan". System must be http://terminology.hl7.org/CodeSystem/coverage-class.

Bundle (R4).entry.resource.Coverage.class (plan).value | string | Required | | 1..1 | Plan ID.

Bundle (R4).entry.resource.Coverage.dependent | string | Optional | | 0..1 | A unique member number for the dependent on the coverage.

Bundle (R4).entry.resource.Coverage.identifier (memberId) (also: identifier (memberId)) | Identifier | Optional | Yes | 0..* | Member ID.

Bundle (R4).entry.resource.Coverage.identifier (memberId).type | CodeableConcept | Required | | 1..1 | Identifier type. Must include a coding system of http://terminology.hl7.org/CodeSystem/v2-0203, and the code must be “MB”.

Bundle (R4).entry.resource.Coverage.identifier (memberId).value | String | Optional | | 0..1 | Identifier value.

Bundle (R4).entry.resource.Coverage.payor | Reference | Required | Yes | 1..1 | Reference to insurer Organization resource. Payor reference must be the same as Claim.insurer.

Bundle (R4).entry.resource.Coverage.relationship | CodeableConcept | Required | | 1..1 | Beneficiary relationship to the subscriber. Must include one of the allowed coding systems: https://codesystem.x12.org/005010/1069. http://terminology.hl7.org/CodeSystem/subscriber-relationship.

Bundle (R4).entry.resource.Coverage.subscriber | Reference | Optional | | 0..1 | Reference to subscriber.

Bundle (R4).entry.resource.Coverage.subscriberId | string | Optional | | 0..1 | Subscriber ID.

Bundle (R4).entry.resource.DeviceRequest | Resource | Optional | | 0..* | DeviceRequest Resource.

Bundle (R4).entry.resource.DeviceRequest.occurrenceTiming | Timing | Optional | | 0..1 | A timing schedule that specifies an event that can occur multiple times.

Bundle (R4).entry.resource.DeviceRequest.occurrenceTiming.repeat | BackboneElement | Optional | | 0..1 | Numeric value. When the event is to occur.

Bundle (R4).entry.resource.DeviceRequest.occurrenceTiming.repeat.boundsDuration | Duration | Optional | | 0..1 | The number of periods over which the service is delivered.

Bundle (R4).entry.resource.DeviceRequest.occurrenceTiming.repeat.boundsDuration.code | code | Required | | 1..1 | Duration unit code (UCUM).

Bundle (R4).entry.resource.DeviceRequest.occurrenceTiming.repeat.boundsDuration.system | uri | Required | | 1..1 | URL of the system: http://unitsofmeasure.org.

Bundle (R4).entry.resource.DeviceRequest.occurrenceTiming.repeat.boundsDuration.value | decimal | Required | | 1..1 | Duration quantity.

Bundle (R4).entry.resource.DeviceRequest.occurrenceTiming.repeat.period | decimal | Required | | 1..1 | Only period=1 is supported.

Bundle (R4).entry.resource.DeviceRequest.occurrenceTiming.repeat.periodUnit | code | Required | | 1..1 | Units from UCUM (h | d | wk | mo | a). BoundsDuration.code and periodUnit are expected to be the same.

Bundle (R4).entry.resource.DeviceRequest.subject | Reference | Required | | 1..1 | Individual or entity the service is ordered for. A reference to the beneficiary Patient resource. Expected to match coverage.beneficiary.

Bundle (R4).entry.resource.DocumentReference | DocumentReference | Optional | | 0..* | DocumentReference resource.

Bundle (R4).entry.resource.DocumentReference.content | BackboneElement | Required | Yes | 1..* | The document content. At least one content element must be present and must include a PDF representation of the document. If there are multiple content element repetitions, these must all represent the same document in different format or attachment metadata.

Bundle (R4).entry.resource.DocumentReference.content.attachment | Attachment | Required | | 1..1 | The document and format referenced.

Bundle (R4).entry.resource.DocumentReference.content.attachment.contentType | String | Required | | 1..1 | MIME type of content. Must be "application/pdf" for a PDF attachment. Only PDF is supported. Other attachment types are ignored.

Bundle (R4).entry.resource.DocumentReference.content.attachment.data | String | Conditional | | 0..1 | The actual data of attachment, base64 encoded. Either data or url need to be specified.

Bundle (R4).entry.resource.DocumentReference.content.attachment.size | Int64 | Optional | | 0..1 | The number of bytes of data.

Bundle (R4).entry.resource.DocumentReference.content.attachment.url | String | Conditional | | 0..1 | The URL where the data can be retrieved from. The data returned by the url is expected to be the binary of the document. The URL can either be a partial URL of format Binary/<FhirID> or a full url with the agreed upon base url and domain. Either data or url need to be specified.

Bundle (R4).entry.resource.DocumentReference.date | instant | Optional | | 0..1 | When this document reference was created.

Bundle (R4).entry.resource.DocumentReference.masterIdentifier | Identifier | Optional | | 0..1 | Document identifier as assigned by the source of the document. This identifier is specific to this version of the document. This unique identifier might be used elsewhere to identify this version of the document.

Bundle (R4).entry.resource.DocumentReference.status | code | Required | | 1..1 | Status of the document, required to be “current”.

Bundle (R4).entry.resource.DocumentReference.subject | Reference | Required | | 1..1 | The subject of the document. A reference to the beneficiary patient. Expected to match coverage.beneficiary.

Bundle (R4).entry.resource.DocumentReference.type | CodeableConcept | Required | | 1..1 | The type of the document. Must contain a coding system of http://loinc.org. http://terminology.hl7.org/CodeSystem/v3-NullFlavor and the value must be "UNK".

Bundle (R4).entry.resource.Encounter | Resource | Optional | | 0..* | An interaction during which services are provided to the patient.

Bundle (R4).entry.resource.Encounter.class | Coding | Required | | 1..1 | Classification of patient encounter.

Bundle (R4).entry.resource.Encounter.extension (patientStatus) (also: extension (patientStatus)) | Extension | Optional | Yes | 0..1 | A code representing the status of the patient when being admitted. URL: http://hl7.org/fhir/us/davinci-pas/StructureDefinition/extension-patientStatus

Bundle (R4).entry.resource.Encounter.extension (patientStatus).url | uri | Required | | 1..1 | URL of the extension: http://hl7.org/fhir/us/davinci-pas/StructureDefinition/extension-patientStatus

Bundle (R4).entry.resource.Encounter.extension (patientStatus).valueCodeableConcept (also: valueCodeableConcept) | CodeableConcept | Required | | 1..1 | Patient Status. Must have a system of https://codesystem.x12.org/005010/1352.

Bundle (R4).entry.resource.Encounter.hospitalization | BackboneElement | Required | | 1..1 | Details about the admission to a healthcare service.

Bundle (R4).entry.resource.Encounter.hospitalization.admitSource | CodeableConcept | Required | | 1..1 | From where patient was admitted. Must have a system of https://codesystem.x12.org/005010/1314.

Bundle (R4).entry.resource.Encounter.hospitalization.dischargeDisposition | CodeableConcept | Optional | | 0..1 | Category or kind of location after discharge. Must have a system of https://www.nubc.org/CodeSystem/PatDischargeStatus.

Bundle (R4).entry.resource.Encounter.status | code | Required | | 1..1 | Status of the encounter. Required to be "planned".

Bundle (R4).entry.resource.Encounter.subject | Reference | Required | | 1..1 | Reference to a Patient resource, representing the patient present at the encounter. This is expected to match coverage.beneficiary.

Bundle (R4).entry.resource.Encounter.type | CodeableConcept | Required | Yes | 1..* | Admission Type. Must include coding system of https://codesystem.x12.org/005010/1315.

Bundle (R4).entry.resource.Location | Resource | Optional | | 0..* | Location resource.

Bundle (R4).entry.resource.Location.address | Address | Optional | | 0..* | Address.

Bundle (R4).entry.resource.Location.address.city | string | Optional | | 0..1 | Name of city, town, and so on.

Bundle (R4).entry.resource.Location.address.line | string | Optional | Yes | 0..2 | Street name, number, direction, P.O. Box, and so on.

Bundle (R4).entry.resource.Location.address.postalCode | string | Optional | | 0..1 | US ZIP codes.

Bundle (R4).entry.resource.Location.address.state | string | Optional | | 0..1 | US state 2 letter abbreviation. Value set: http://hl7.org/fhir/us/core/STU7/ValueSet-us-core-usps-state.html.

Bundle (R4).entry.resource.Location.address.use | code | Optional | | 0..1 | The purpose of this address. This is used to determine the priority of the identifier. Values of “billing” and “work” have higher priority than the rest of the values. The highest priority of the address gets used.

Bundle (R4).entry.resource.Location.identifier | Identifier | Optional | Yes | 0..* | Identifier.

Bundle (R4).entry.resource.Location.identifier.system | String | Required | | 1..1 | The system for the identifier value. Supported systems: http://terminology.hl7.org/NamingSystem/USEIN (TIN). http://hl7.org/fhir/sid/us-npi (NPI).

Bundle (R4).entry.resource.Location.identifier.use | String | Optional | | 0..1 | The purpose of this identifier. This is used to determine the priority of the identifier. Values of “official” and “usual” have higher priority than the rest of the values. The highest priority of the same identity type gets used.

Bundle (R4).entry.resource.Location.identifier.value | String | Required | | 1..1 | Identifier value that is unique within the system.

Bundle (R4).entry.resource.Location.name | string | Required | | 1..1 | Name.

Bundle (R4).entry.resource.Location.status | code | Required | | 1..1 | Location status. Required to be active.

Bundle (R4).entry.resource.Location.telecom | ContactPoint | Optional | Yes | 0..* | Contact details.

Bundle (R4).entry.resource.Location.telecom.rank | positiveInt | Optional | | 0..1 | Specifies a preferred order in which to use the set of contacts. Higher rank of the same contact system gets used. If the rank is the same, then the higher use priority gets used.

Bundle (R4).entry.resource.Location.telecom.system | code | Optional | | 0..1 | Form of communication. Supported values: phone, fax, email.

Bundle (R4).entry.resource.Location.telecom.use | code | Optional | | 0..1 | The purpose of this contact point. This is used to determine the priority of the identifier. Values of “work” and “mobile” have higher priority than the rest of the values. The highest priority of the same contact system gets used.

Bundle (R4).entry.resource.Location.telecom.value | string | Optional | | 0..1 | The actual contact point details, in a form that is meaningful to the designated communication system (for example, phone number or email address).

Bundle (R4).entry.resource.Location.type | CodeableConcept | Optional | Yes | 0..* | Must include a coding system of https://codesystem.x12.org/005010/98.

Bundle (R4).entry.resource.Organization | Resource | Optional | | 0..* | Organization resource.

Bundle (R4).entry.resource.Organization.address | Address | Optional | Yes | 0..* | Address.

Bundle (R4).entry.resource.Organization.address.city | string | Optional | | 0..1 | Name of city, town, and so on.

Bundle (R4).entry.resource.Organization.address.line | string | Optional | Yes | 0..2 | Street name, number, direction, P.O. Box, and so on.

Bundle (R4).entry.resource.Organization.address.postalCode | string | Optional | | 0..1 | US ZIP codes.

Bundle (R4).entry.resource.Organization.address.state | string | Optional | | 0..1 | US state 2 letter abbreviation. Value set: http://hl7.org/fhir/us/core/STU7/ValueSet-us-core-usps-state.html.

Bundle (R4).entry.resource.Organization.address.use | code | Optional | | 0..1 | The purpose of this address. This is used to determine the priority of the identifier. Values of “billing” and “work” have higher priority than the rest of the values. The highest priority of the address gets used.

Bundle (R4).entry.resource.Organization.contact | BackboneElement | Optional | Yes | 0..* | Contact information. For Organization, only the contact name information is used.

Bundle (R4).entry.resource.Organization.contact.name | HumanName | Optional | | 0..1 | Contact name.

Bundle (R4).entry.resource.Organization.contact.purpose | CodeableConcept | Optional | | 0..1 | Purpose of the contact. It is only considered when coding system is http://terminology.hl7.org/CodeSystem/contactentity-type. This is used to determine the priority of the contact name. The contact name with the highest priority gets used. The hierarchy for the purpose priority is as follows: PAYOR BILL ADMIN <Unspecified> or blank <Other purpose> (for example, none of the above)

Bundle (R4).entry.resource.Organization.identifier | Identifier | Optional | Yes | 0..* | All identifiers. Payer identifier is only used for Claim.Insurer/ClaimResponse.insurer.

Bundle (R4).entry.resource.Organization.identifier.system | String | Required | | 1..1 | The namespace for the identifier value. Supported systems: http://terminology.hl7.org/NamingSystem/USEIN (TIN). http://hl7.org/fhir/sid/us-npi (NPI).

Bundle (R4).entry.resource.Organization.identifier.type | CodeableConcept | Required | | 1..1 | Identifier type. Only required for payer identifier slice. Must include a coding system of http://hl7.org/fhir/us/carin-bb/CodeSystem/C4BBIdentifierType, and code is “payerid”.

Bundle (R4).entry.resource.Organization.identifier.use | String | Optional | | 0..1 | The purpose of this identifier. This is used to determine the priority of the identifier. Values of “official” and “usual” have higher priority than the rest of the values. The highest priority of the same identity type gets used.

Bundle (R4).entry.resource.Organization.identifier.value | String | Optional | | 0..1 | Identifier value that is unique within the system.

Bundle (R4).entry.resource.Organization.name | string | Required | | 1..1 | Name.

Bundle (R4).entry.resource.Organization.telecom | ContactPoint | Optional | Yes | 0..* | Contact details.

Bundle (R4).entry.resource.Organization.telecom.rank | positiveInt | Optional | | 0..1 | Specifies a preferred order in which to use the set of contacts. Higher rank of the same contact system gets used. If the rank is the same, then the higher use priority gets used.

Bundle (R4).entry.resource.Organization.telecom.system | code | Optional | | 0..1 | Form of communication. Supported values: phone, fax, email.

Bundle (R4).entry.resource.Organization.telecom.use | code | Optional | | 0..1 | The purpose of this contact point. This is used to determine the priority of the identifier. Values of “work” and “mobile” have higher priority than the rest of the values. The highest priority of the same contact system gets used.

Bundle (R4).entry.resource.Organization.telecom.value | string | Optional | | 0..1 | The actual contact point details, in a form that is meaningful to the designated communication system (for example, phone number or email address).

Bundle (R4).entry.resource.Organization.type | CodeableConcept | Optional | Yes | 0..* | It is only supported for insurer and requestor. Must include a coding system of https://codesystem.x12.org/005010/98. For Claim.Insurer, the code must be one of the following: 2B, 36, PR, X3.

Bundle (R4).entry.resource.Patient | Resource | Optional | | 0..* | Patient resource.

Bundle (R4).entry.resource.Patient.address | Address | Optional | Yes | 0..* | Address.

Bundle (R4).entry.resource.Patient.address.city | string | Optional | | 0..1 | Name of city, town, and so on.

Bundle (R4).entry.resource.Patient.address.line | string | Optional | Yes | 0..2 | Street name, number, direction, P.O. Box, and so on.

Bundle (R4).entry.resource.Patient.address.postalCode | string | Optional | | 0..1 | US ZIP codes.

Bundle (R4).entry.resource.Patient.address.state | string | Optional | | 0..1 | US state 2 letter abbreviation. Value set: http://hl7.org/fhir/us/core/STU7/ValueSet-us-core-usps-state.html.

Bundle (R4).entry.resource.Patient.address.use | code | Optional | | 0..1 | The purpose of this address. This is used to determine the priority of the identifier. Values of “home”, “billing”, and “work” have higher priority than the rest of the values. The highest priority of the address gets used.

Bundle (R4).entry.resource.Patient.birthDate | date | Optional | | 0..1 | Birth date.

Bundle (R4).entry.resource.Patient.gender | code | Required | | 1..1 | Gender. Code: male | female | other | unknown.

Bundle (R4).entry.resource.Patient.identifier | Identifier | Optional | Yes | 0..* | All Identifiers.

Bundle (R4).entry.resource.Patient.identifier.system | String | Required | | 1..1 | The system for the identifier value. Supported systems: urn:oid:2.16.840.1.113883.4.1 (SSN) http://open.epic.com/FHIR/StructureDefinition/member-id (Member ID) Other OID or URN that are mapped in internal system. (Identity ID).

Bundle (R4).entry.resource.Patient.identifier.type | CodeableConcept | Required | | 1..1 | Identifier type. Only required for the member ID slice. Must include a coding system of http://terminology.hl7.org/CodeSystem/v2-0203, and code must be “MB”.

Bundle (R4).entry.resource.Patient.identifier.use | String | Optional | | 0..1 | The purpose of this identifier. This is used to determine the priority of the identifier. Values of “official” and “usual” have higher priority than the rest of the values. The highest priority of the same identity type gets used.

Bundle (R4).entry.resource.Patient.identifier.value | String | Required | | 1..1 | Identifier value that is unique within the system.

Bundle (R4).entry.resource.Patient.name | HumanName | Required | Yes | 1..* | Human name.

Bundle (R4).entry.resource.Patient.name.family | string | Optional | | 0..1 | Family name (surname).

Bundle (R4).entry.resource.Patient.name.given | string | Optional | Yes | 0..* | Given name (includes middle name).

Bundle (R4).entry.resource.Patient.name.suffix | string | Optional | Yes | 0..* | Suffix.

Bundle (R4).entry.resource.Patient.name.use | code | Optional | | 0..1 | The purpose of this name. This is used to determine the priority of the identifier. Values of “official” and “usual” have higher priority than the rest of the values. The highest priority of the name gets used.

Bundle (R4).entry.resource.Patient.telecom | ContactPoint | Optional | Yes | 0..* | Contact details.

Bundle (R4).entry.resource.Patient.telecom.rank | positiveInt | Optional | | 0..1 | Specifies a preferred order in which to use the set of contacts. Higher rank of the same contact system gets used. If the rank is the same, then the higher use priority gets used.

Bundle (R4).entry.resource.Patient.telecom.system | code | Optional | | 0..1 | Form of communication. Supported values: phone, fax, email.

Bundle (R4).entry.resource.Patient.telecom.use | code | Optional | | 0..1 | The purpose of this contact point. This is used to determine the priority of the identifier. Values of “home,” “work” and “mobile” have higher priority than the rest of the values. The highest priority of the same contact system gets used.

Bundle (R4).entry.resource.Patient.telecom.value | string | Optional | | 0..1 | The actual contact point details, in a form that is meaningful to the designated communication system (for example, phone number or email address).

Bundle (R4).entry.resource.Practitioner | Resource | Optional | | 0..* | Practitioner resource.

Bundle (R4).entry.resource.Practitioner.address | Address | Required | Yes | 0..* | Address.

Bundle (R4).entry.resource.Practitioner.address.city | string | Optional | | 0..1 | Name of city, town, and so on.

Bundle (R4).entry.resource.Practitioner.address.line | string | Optional | Yes | 0..2 | Street name, number, direction & P.O. Box, and so on.

Bundle (R4).entry.resource.Practitioner.address.postalCode | string | Optional | | 0..1 | US ZIP codes.

Bundle (R4).entry.resource.Practitioner.address.state | string | Optional | | 0..1 | US state 2 letter abbreviation. Value set: http://hl7.org/fhir/us/core/STU7/ValueSet-us-core-usps-state.html.

Bundle (R4).entry.resource.Practitioner.address.use | code | Optional | | 0..1 | The purpose of this address. This is used to determine the priority of the identifier. Values of “billing” and “work” have higher priority than the rest of the values. The highest priority of the address gets used.

Bundle (R4).entry.resource.Practitioner.identifier | Identifier | Optional | Yes | 0..* | Identifier.

Bundle (R4).entry.resource.Practitioner.identifier.system | String | Required | | 1..1 | The system for the identifier value. Supported systems: http://terminology.hl7.org/NamingSystem/USEIN (TIN). http://hl7.org/fhir/sid/us-npi (NPI).

Bundle (R4).entry.resource.Practitioner.identifier.use | String | Optional | | 0..1 | The purpose of this identifier. This is used to determine the priority of the identifier. Values of “official” and “usual” have higher priority than the rest of the values. The highest priority of the same identity type gets used.

Bundle (R4).entry.resource.Practitioner.identifier.value | String | Required | | 1..1 | Identifier value.

Bundle (R4).entry.resource.Practitioner.name | HumanName | Required | Yes | 1..* | Name.

Bundle (R4).entry.resource.Practitioner.name.family | string | Optional | | 0..1 | Family name (surname).

Bundle (R4).entry.resource.Practitioner.name.given | string | Optional | Yes | 0..* | Given name (includes middle name).

Bundle (R4).entry.resource.Practitioner.name.suffix | string | Optional | Yes | 0..* | Suffix.

Bundle (R4).entry.resource.Practitioner.name.use | code | Optional | | 0..1 | The purpose of this name. This is used to determine the priority of the identifier. Values of “official” and “usual” have higher priority than the rest of the values. The highest priority of the name gets used.

Bundle (R4).entry.resource.Practitioner.telecom | ContactPoint | Optional | Yes | 0..* | Contact details.

Bundle (R4).entry.resource.Practitioner.telecom.rank | positiveInt | Optional | | 0..1 | Specifies a preferred order in which to use the set of contacts. Higher rank of the same contact system gets used. If the rank is the same, then the higher use priority gets used.

Bundle (R4).entry.resource.Practitioner.telecom.system | code | Optional | | 0..1 | Form of communication. Supported values: phone, fax, email.

Bundle (R4).entry.resource.Practitioner.telecom.use | code | Optional | | 0..1 | The purpose of this contact point. This is used to determine the priority of the identifier. Values of “work” and “mobile” have higher priority than the rest of the values. The highest priority of the same contact system gets used.

Bundle (R4).entry.resource.Practitioner.telecom.value | string | Optional | | 0..1 | The actual contact point details, in a form that is meaningful to the designated communication system (for example, phone number or email address).

Bundle (R4).entry.resource.PractitionerRole | Resource | Optional | | 0..* | PractitionerRole resource.

Bundle (R4).entry.resource.PractitionerRole.location | Reference | Optional | Yes | 0..1 | A reference to a Location resource. The location where the practitioner performs the roles associated.

Bundle (R4).entry.resource.PractitionerRole.organization | Reference | Optional | | 0..1 | A reference to an Organization resource. The organization where the practitioner performs the roles associated.

Bundle (R4).entry.resource.PractitionerRole.practitioner | Reference | Required | | 1..1 | A reference to a Practitioner resource. Practitioner that can provide the defined services for the organization.

Bundle (R4).entry.resource.PractitionerRole.telecom | ContactPoint | Optional | Yes | 0..* | Contact details.

Bundle (R4).entry.resource.PractitionerRole.telecom.rank | positiveInt | Optional | | 0..1 | Specifies a preferred order in which to use the set of contacts. Higher rank of the same contact system gets used. If the rank is the same, then the higher use priority gets used.

Bundle (R4).entry.resource.PractitionerRole.telecom.system | code | Optional | | 0..1 | Form of communication. Supported values: phone, fax, email

Bundle (R4).entry.resource.PractitionerRole.telecom.use | code | Optional | | 0..1 | The purpose of this contact point. This is used to determine the priority of the identifier. Values of “work” and “mobile” have higher priority than the rest of the values. The highest priority of the same contact system gets used.

Bundle (R4).entry.resource.PractitionerRole.telecom.value | string | Optional | | 0..1 | The actual contact point details, in a form that is meaningful to the designated communication system (for example, phone number or email address).

Bundle (R4).entry.resource.ServiceRequest | Resource | Optional | | 0..* | ServiceRequest resource.

Bundle (R4).entry.resource.ServiceRequest.occurrenceTiming | Timing | Optional | | 0..1 | A timing schedule that specifies an event that can occur multiple times.

Bundle (R4).entry.resource.ServiceRequest.occurrenceTiming.repeat | BackboneElement | Optional | | 0..1 | Numeric value. When the event is to occur.

Bundle (R4).entry.resource.ServiceRequest.occurrenceTiming.repeat.boundsDuration | Duration | Optional | | 0..1 | The number of periods over which the service is delivered.

Bundle (R4).entry.resource.ServiceRequest.occurrenceTiming.repeat.boundsDuration.code | code | Required | | 1..1 | Duration unit code (UCUM).

Bundle (R4).entry.resource.ServiceRequest.occurrenceTiming.repeat.boundsDuration.system | uri | Required | | 1..1 | URL of the system: http://unitsofmeasure.org.

Bundle (R4).entry.resource.ServiceRequest.occurrenceTiming.repeat.boundsDuration.value | decimal | Required | | 1..1 | Duration quantity.

Bundle (R4).entry.resource.ServiceRequest.occurrenceTiming.repeat.period | decimal | Required | | 1..1 | Only period=1 is supported.

Bundle (R4).entry.resource.ServiceRequest.occurrenceTiming.repeat.periodUnit | code | Required | | 1..1 | Units from UCUM (h | d | wk | mo | a). BoundsDuration.code and periodUnit are expected to be the same.

Bundle (R4).entry.resource.ServiceRequest.quantityQuantity | Quantity | Optional | | 0..1 | A fixed quantity.

Bundle (R4).entry.resource.ServiceRequest.quantityQuantity.code | String | Required | | 1..1 | Coded form of the unit.

Bundle (R4).entry.resource.ServiceRequest.quantityQuantity.system | String | Required | | 1..1 | System that defines coded unit form. Required system to be https://codesystem.x12.org/005010/673.

Bundle (R4).entry.resource.ServiceRequest.quantityQuantity.value | Decimal | Required | | 1..1 | Numerical value.

Bundle (R4).entry.resource.ServiceRequest.subject | Reference | Required | | 1..1 | Individual or Entity the service is ordered for. A reference to the beneficiary patient. Expected to match coverage.beneficiary.

Bundle (R4).id | id | Optional | | 0..1 | Logical ID of the bundle.

Bundle (R4).identifier | Identifier | Optional | | 0..1 | Submitted Transaction Identifier - this number is assigned by the originator or sender to identify the transaction within the sender's business application system.

Bundle (R4).meta | Meta | Optional | | 0..* | Metadata about the resource.

Bundle (R4).meta.security | Coding | Optional | Yes | 0..1 | When received code is SUBSETTED, the system stops processing the submitted claim and returns an error.

Bundle (R4).timestamp | instant | Optional | | 0..1 | When the Bundle was assembled.

Bundle (R4).type | code | Required | | 1..1 | Purpose of the Bundle. Required to be “collection”.

Response elements

Name | Type | Optional | Array | Cardinality | Description

Bundle (R4) | Bundle | Required | | 1..1 | Bundle resource.

Bundle (R4).entry | BackboneElement | Required | Yes | 1..* | Entries in the bundle – each entry contains a resource. Always include only one ClaimResponse resource. The other resources in the bundle are referenced by ClaimResponse by their fullUrl. Resources that can be sent: ClaimResponse, Patient, Practitioner, PractitionerRole, Organization, and ServiceRequest.

Bundle (R4).entry.fullUrl | uri | Required | | 1..1 | URI for the resource (Absolute URL server address or URI for UUID/OID).

Bundle (R4).entry.link | BackboneElement | Optional | Yes | 0..* | Provides additional context or references related to the entry.

Bundle (R4).entry.link.relation | string | Required | | 1..1 | Purpose of the link. Sent as self.

Bundle (R4).entry.link.url | uri | Required | | 1..1 | Reference details for the link. Contains the same value as entry.fullUrl.

Bundle (R4).entry.resource | ResourceContainer | Required | | 1..1 | A resource in the bundle.

Bundle (R4).entry.resource.ClaimResponse | Resource | Required | | 1..1 | ClaimResponse resource.

Bundle (R4).entry.resource.ClaimResponse.addItem | BackboneElement | Optional | Yes | 0..* | Insurer added line items.

Bundle (R4).entry.resource.ClaimResponse.addItem.adjudication | BackboneElement | Optional | Yes | 0..1 | Adjudication for insurer added items.

Bundle (R4).entry.resource.ClaimResponse.addItem.adjudication.category | CodeableConcept | Required | | 1..1 | Adjudication category. The coding system is http://terminology.hl7.org/CodeSystem/adjudication. The returned code is always “submitted”.

Bundle (R4).entry.resource.ClaimResponse.addItem.adjudication.extension (reviewAction) (also: extension (reviewAction)) | Extension | Optional | Yes | 0..1 | The details of the review action that are necessary for the authorization, equivalent to 2000F HCR (ANSI X12 value). URL: http://hl7.org/fhir/us/davinci-pas/StructureDefinition/extension-reviewAction

Bundle (R4).entry.resource.ClaimResponse.addItem.adjudication.extension (reviewAction).extension (number) (also: extension (number)) | Extension | Optional | Yes | 0..1 | Review number, equivalent to 2000F HCR02 (ANSI X12 value). URL: number

Bundle (R4).entry.resource.ClaimResponse.addItem.adjudication.extension (reviewAction).extension (number).url | uri | Required | | 1..1 | URL of the extension: number

Bundle (R4).entry.resource.ClaimResponse.addItem.adjudication.extension (reviewAction).extension (number).valueString | string | Required | | 1..1 | Review number value.

Bundle (R4).entry.resource.ClaimResponse.addItem.adjudication.extension (reviewAction).extension (reasonCode) (also: extension (reasonCode)) | Extension | Optional | Yes | 0..1 | Certification action code: indicates the reason for the approved, denied, pended, or other services, equivalent to 2000F HCR03 (ANSI X12 value). URL: reasonCode

Bundle (R4).entry.resource.ClaimResponse.addItem.adjudication.extension (reviewAction).extension (reasonCode).url | uri | Required | | 1..1 | URL for the extension: reasonCode

Bundle (R4).entry.resource.ClaimResponse.addItem.adjudication.extension (reviewAction).extension (reasonCode).valueCodeableConcept | CodeableConcept | Required | | 1..1 | Reason code value. It has a code system of https://codesystem.x12.org/external/886.

Bundle (R4).entry.resource.ClaimResponse.addItem.adjudication.extension (reviewAction).extension (reviewActionCode) (also: extension (reviewActionCode)) | Extension | Optional | Yes | 0..1 | Code for the review action, equivalent to 2000F HCR01 (ANSI X12 value). URL: http://hl7.org/fhir/us/davinci-pas/StructureDefinition/extension-reviewActionCode

Bundle (R4).entry.resource.ClaimResponse.addItem.adjudication.extension (reviewAction).extension (reviewActionCode).url | uri | Required | | 1..1 | URL of the extension: http://hl7.org/fhir/us/davinci-pas/StructureDefinition/extension-reviewActionCode

Bundle (R4).entry.resource.ClaimResponse.addItem.adjudication.extension (reviewAction).extension (reviewActionCode).valueCodeableConcept | CodeableConcept | Required | | 1..1 | Review action code for the adjudication. It has a code system of https://codesystem.x12.org/005010/306.

Bundle (R4).entry.resource.ClaimResponse.addItem.adjudication.extension (reviewAction).url | uri | Required | | 1..1 | URL of the extension: http://hl7.org/fhir/us/davinci-pas/StructureDefinition/extension-reviewAction

Bundle (R4).entry.resource.ClaimResponse.addItem.extension (administrationReferenceNumber) (also: extension (administrationReferenceNumber)) | Extension | Optional | Yes | 0..1 | A string assigned by the payer to the original disallowed review outcome associated with this service item, equivalent to 2000F REF*NT (ANSI X12 value). URL: http://hl7.org/fhir/us/davinci-pas/StructureDefinition/extension-administrationReferenceNumber

Bundle (R4).entry.resource.ClaimResponse.addItem.extension (administrationReferenceNumber).url | uri | Required | | 1..1 | URL of the extension: http://hl7.org/fhir/us/davinci-pas/StructureDefinition/extension-administrationReferenceNumber

Bundle (R4).entry.resource.ClaimResponse.addItem.extension (administrationReferenceNumber).valueString | string | Required | | 1..1 | Administrative reference number.

Bundle (R4).entry.resource.ClaimResponse.addItem.extension (itemTraceNumber) (also: extension (itemTraceNumber)) | Extension | Optional | Yes | 0..* | Uniquely identifies this claim item, equivalent to 2000F TRN (ANSI X12 value). URL: http://hl7.org/fhir/us/davinci-pas/StructureDefinition/extension-itemTraceNumber

Bundle (R4).entry.resource.ClaimResponse.addItem.extension (itemTraceNumber).url | uri | Required | | 1..1 | URL of the extension: http://hl7.org/fhir/us/davinci-pas/StructureDefinition/extension-itemTraceNumber

Bundle (R4).entry.resource.ClaimResponse.addItem.extension (itemTraceNumber).valueIdentifier | Identifier | Optional | | 0..1 | Trace number.

Bundle (R4).entry.resource.ClaimResponse.addItem.extension (itemTraceNumber).valueIdentifier.extension (subDepartment) (also: extension (subDepartment)) | Extension | Optional | Yes | 0..1 | An additional element that provides a further subdivision within the organization granting the identifier, equivalent to TRN04 (ANSI X12 value). URL: http://hl7.org/fhir/us/davinci-pas/StructureDefinition/extension-identifierSubDepartment

Bundle (R4).entry.resource.ClaimResponse.addItem.extension (itemTraceNumber).valueIdentifier.extension (subDepartment).url | uri | Required | | 1..1 | URL of the extension: http://hl7.org/fhir/us/davinci-pas/StructureDefinition/extension-identifierSubDepartment

Bundle (R4).entry.resource.ClaimResponse.addItem.extension (itemTraceNumber).valueIdentifier.extension (subDepartment).valueString | string | Required | | 1..1 | Additional reference number.

Bundle (R4).entry.resource.ClaimResponse.addItem.extension (itemTraceNumber).valueIdentifier.system | String | Required | | 1..1 | System of the identifier, equivalent to TRN03 (ANSI X12 value). Uses a scheme of 'urn:trnorg:<TRN03>'.

Bundle (R4).entry.resource.ClaimResponse.addItem.extension (itemTraceNumber).valueIdentifier.value | String | Required | | 1..1 | Value of the identifier, equivalent to TRN02 (ANSI X12 value).

Bundle (R4).entry.resource.ClaimResponse.addItem.extension (preAuthIssueDate) (also: extension (preAuthIssueDate)) | Extension | Optional | Yes | 0..1 | The date when this item's preauthorization was issued. URL: http://hl7.org/fhir/us/davinci-pas/StructureDefinition/extension-itemPreAuthIssueDate

Bundle (R4).entry.resource.ClaimResponse.addItem.extension (preAuthIssueDate).url | uri | Required | | 1..1 | URL of the extension: http://hl7.org/fhir/us/davinci-pas/StructureDefinition/extension-itemPreAuthIssueDate

Bundle (R4).entry.resource.ClaimResponse.addItem.extension (preAuthIssueDate).valueDate | date | Required | | 1..1 | The date when this item's preauthorization was issued.

Bundle (R4).entry.resource.ClaimResponse.addItem.extension (preAuthPeriod) (also: extension (preAuthPeriod)) | Extension | Optional | Yes | 0..1 | The date/period when this item's preauthorization is valid. URL: http://hl7.org/fhir/us/davinci-pas/StructureDefinition/extension-itemPreAuthPeriod

Bundle (R4).entry.resource.ClaimResponse.addItem.extension (preAuthPeriod).url | uri | Required | | 1..1 | URL of the extension: http://hl7.org/fhir/us/davinci-pas/StructureDefinition/extension-itemPreAuthPeriod

Bundle (R4).entry.resource.ClaimResponse.addItem.extension (preAuthPeriod).valuePeriod | Period | Required | | 1..1 | The period when this item's preauthorization is valid.

Bundle (R4).entry.resource.ClaimResponse.addItem.extension (preAuthPeriod).valuePeriod.end | String | Required | | 1..1 | Preauthorization end date.

Bundle (R4).entry.resource.ClaimResponse.addItem.extension (preAuthPeriod).valuePeriod.start | String | Required | | 1..1 | Preauthorization start date.

Bundle (R4).entry.resource.ClaimResponse.addItem.extension (previousAuthorizationNumber) (also: extension (previousAuthorizationNumber)) | Extension | Optional | Yes | 0..1 | A string assigned by the payer to an authorized review outcome associated with this service item, equivalent to 2000F REF*BB (ANSI X12 value). URL: http://hl7.org/fhir/us/davinci-pas/StructureDefinition/extension-authorizationNumber

Bundle (R4).entry.resource.ClaimResponse.addItem.extension (previousAuthorizationNumber).url | uri | Required | | 1..1 | URL of the extension: http://hl7.org/fhir/us/davinci-pas/StructureDefinition/extension-authorizationNumber

Bundle (R4).entry.resource.ClaimResponse.addItem.extension (previousAuthorizationNumber).valueString | string | Required | | 1..1 | A string assigned by the payer to an authorized review outcome associated with this service item.

Bundle (R4).entry.resource.ClaimResponse.addItem.extension (requestedService) (also: extension (requestedService)) | Extension | Optional | Yes | 0..1 | The ServiceRequest that contains the recurring quantity details of what has been requested for this addItem. If not recurring, addItem.quantity is sent instead. URL: http://hl7.org/fhir/us/davinci-pas/StructureDefinition/extension-requestedService

Bundle (R4).entry.resource.ClaimResponse.addItem.extension (requestedService).url | uri | Required | | 1..1 | URL of the extension: http://hl7.org/fhir/us/davinci-pas/StructureDefinition/extension-requestedService

Bundle (R4).entry.resource.ClaimResponse.addItem.extension (requestedService).valueReference | Reference | Required | | 1..1 | Reference to authorized service. A reference to ServiceRequest resource.

Bundle (R4).entry.resource.ClaimResponse.addItem.extension (revenue) (also: extension (revenue)) | Extension | Optional | Yes | 0..1 | Revenue code of the added service. URL: http://hl7.org/fhir/us/davinci-pas/StructureDefinition/extension-revenueCode

Bundle (R4).entry.resource.ClaimResponse.addItem.extension (revenue).url | uri | Required | | 1..1 | URL of the extension: http://hl7.org/fhir/us/davinci-pas/StructureDefinition/extension-revenueCode

Bundle (R4).entry.resource.ClaimResponse.addItem.extension (revenue).valueCodeableConcept | CodeableConcept | Required | | 1..1 | Revenue code of the added service. It has a coding system of https://www.nubc.org/CodeSystem/RevenueCodes.

Bundle (R4).entry.resource.ClaimResponse.addItem.itemSequence | positiveInt | Required | Yes | 1..1 | Item sequence number.

Bundle (R4).entry.resource.ClaimResponse.addItem.modifier | CodeableConcept | Optional | Yes | 0..* | Service modifier. Coding system (depending on the type of modifier): http://www.ama-assn.org/go/cpt http://www.cms.gov/Medicare/Coding/HCPCSReleaseCodeSets https://open.epic.com/FHIR/(custom_OID)/custom-procedure-modifier

Bundle (R4).entry.resource.ClaimResponse.addItem.noteNumber | positiveInt | Optional | Yes | 0..* | Applicable note numbers.

Bundle (R4).entry.resource.ClaimResponse.addItem.productOrService | CodeableConcept | Required | | 1..1 | Service code. Coding system (depending on the type of service): http://www.ama-assn.org/go/cpt http://www.cms.gov/Medicare/Coding/HCPCSReleaseCodeSets

Bundle (R4).entry.resource.ClaimResponse.addItem.provider | Reference | Optional | Yes | 0..* | Authorized provider. A reference to Practitioner or Organization resource.

Bundle (R4).entry.resource.ClaimResponse.addItem.provider.extension (providerType) (also: extension (providerType)) | Extension | Optional | Yes | 0..1 | Authorized Provider Type. URL: http://hl7.org/fhir/us/davinci-pas/StructureDefinition/extension-authorizedProviderType

Bundle (R4).entry.resource.ClaimResponse.addItem.provider.extension (providerType).url | uri | Required | | 1..1 | URL of the extension: http://hl7.org/fhir/us/davinci-pas/StructureDefinition/extension-authorizedProviderType

Bundle (R4).entry.resource.ClaimResponse.addItem.provider.extension (providerType).valueCodeableConcept | CodeableConcept | Required | | 1..1 | Provider type value. It has a coding system of https://codesystem.x12.org/005010/98.

Bundle (R4).entry.resource.ClaimResponse.addItem.quantity | Quantity | Optional | | 0..1 | The non-recurring quantity details of what has been requested for this addItem. If recurring, addItem.extension:requestedService is sent instead.

Bundle (R4).entry.resource.ClaimResponse.addItem.quantity.code | String | Required | | 1..1 | Coded form of the unit.

Bundle (R4).entry.resource.ClaimResponse.addItem.quantity.system | String | Required | | 1..1 | System that defines coded unit form. It has a system of https://codesystem.x12.org/005010/673.

Bundle (R4).entry.resource.ClaimResponse.addItem.quantity.value | Decimal | Required | | 1..1 | Quantity value.

Bundle (R4).entry.resource.ClaimResponse.addItem.servicedDate | date | Optional | | 0..1 | For date of service or product delivery. If it has a range of date, it uses servicedPeriod instead.

Bundle (R4).entry.resource.ClaimResponse.addItem.servicedPeriod | Period | Optional | | 0..1 | For range of dates of service or product delivery. If it only has a single date, it uses serviceDate instead.

Bundle (R4).entry.resource.ClaimResponse.addItem.servicedPeriod.end | String | Required | | 1..1 | Service end date.

Bundle (R4).entry.resource.ClaimResponse.addItem.servicedPeriod.start | String | Required | | 1..1 | Service start date.

Bundle (R4).entry.resource.ClaimResponse.adjudication | BackboneElement | Optional | Yes | 0..1 | Adjudication for the entire claim.

Bundle (R4).entry.resource.ClaimResponse.adjudication.category | CodeableConcept | Required | | 1..1 | Adjudication category. The coding system is http://terminology.hl7.org/CodeSystem/adjudication. The returned code is always “submitted”.

Bundle (R4).entry.resource.ClaimResponse.adjudication.extension (reviewAction) (also: extension (reviewAction)) | Extension | Optional | Yes | 0..1 | The details of the review action that are necessary for the authorization, equivalent to 2000E HCR (ANSI X12 value). URL: http://hl7.org/fhir/us/davinci-pas/StructureDefinition/extension-reviewAction

Bundle (R4).entry.resource.ClaimResponse.adjudication.extension (reviewAction).extension (number) (also: extension (number)) | Extension | Optional | Yes | 0..1 | Review number, equivalent to 2000E HCR02 (ANSI X12 value). URL: number

Bundle (R4).entry.resource.ClaimResponse.adjudication.extension (reviewAction).extension (number).url | uri | Required | | 1..1 | URL of the extension: number

Bundle (R4).entry.resource.ClaimResponse.adjudication.extension (reviewAction).extension (number).valueString | string | Required | | 1..1 | Review number value.

Bundle (R4).entry.resource.ClaimResponse.adjudication.extension (reviewAction).extension (reasonCode) (also: extension (reasonCode)) | Extension | Optional | Yes | 0..1 | Certification action code: indicates the reason for the approved, denied, pended, or other services, equivalent to 2000E HCR03 (ANSI X12 value). URL: reasonCode

Bundle (R4).entry.resource.ClaimResponse.adjudication.extension (reviewAction).extension (reasonCode).url | uri | Required | | 1..1 | URL for the extension: reasonCode

Bundle (R4).entry.resource.ClaimResponse.adjudication.extension (reviewAction).extension (reasonCode).valueCodeableConcept | CodeableConcept | Required | | 1..1 | Reason code value. It has a code system of https://codesystem.x12.org/external/886.

Bundle (R4).entry.resource.ClaimResponse.adjudication.extension (reviewAction).extension (reviewActionCode) (also: extension (reviewActionCode)) | Extension | Optional | Yes | 0..1 | Code for the review action, equivalent to 2000E HCR01 (ANSI X12 value). URL: http://hl7.org/fhir/us/davinci-pas/StructureDefinition/extension-reviewActionCode

Bundle (R4).entry.resource.ClaimResponse.adjudication.extension (reviewAction).extension (reviewActionCode).url | uri | Required | | 1..1 | URL of the extension: http://hl7.org/fhir/us/davinci-pas/StructureDefinition/extension-reviewActionCode

Bundle (R4).entry.resource.ClaimResponse.adjudication.extension (reviewAction).extension (reviewActionCode).valueCodeableConcept | CodeableConcept | Required | | 1..1 | Review action code for the adjudication. It has a code system of https://codesystem.x12.org/005010/306.

Bundle (R4).entry.resource.ClaimResponse.adjudication.extension (reviewAction).url | uri | Required | | 1..1 | URL of the extension: http://hl7.org/fhir/us/davinci-pas/StructureDefinition/extension-reviewAction

Bundle (R4).entry.resource.ClaimResponse.communicationRequest | Reference | Optional | Yes | 0..* | Request for additional information. Reference to CommunicationRequest resource.

Bundle (R4).entry.resource.ClaimResponse.created | dateTime | Required | | 1..1 | Response creation date.

Bundle (R4).entry.resource.ClaimResponse.error | BackboneElement | Optional | Yes | 0..* | Errors with the authorization request.

Bundle (R4).entry.resource.ClaimResponse.error.code | CodeableConcept | Required | | 1..1 | Error code detailing processing issues with, equivalent to AAA03 (ANSI X12 value). It has a coding system of https://codesystem.x12.org/005010/901.

Bundle (R4).entry.resource.ClaimResponse.error.extension (errorElement) (also: extension (errorElement)) | Extension | Required | Yes | 1..1 | The specific X12 loop, segment, or element that this error information is about. URL: http://hl7.org/fhir/us/davinci-pas/StructureDefinition/extension-errorElement

Bundle (R4).entry.resource.ClaimResponse.error.extension (errorElement).url | uri | Required | | 1..1 | URL of the extension: http://hl7.org/fhir/us/davinci-pas/StructureDefinition/extension-errorElement

Bundle (R4).entry.resource.ClaimResponse.error.extension (errorElement).valueString | string | Required | | 1..1 | The specific X12 loop, segment, or element that this error information is about.

Bundle (R4).entry.resource.ClaimResponse.error.extension (errorPath) (also: extension (errorPath)) | Extension | Optional | Yes | 0..1 | The FHIR path expression that indicates which FHIR element that this error information is about. URL: http://hl7.org/fhir/us/davinci-pas/StructureDefinition/extension-errorPath

Bundle (R4).entry.resource.ClaimResponse.error.extension (errorPath).url | uri | Required | | 1..1 | URL of the extension: http://hl7.org/fhir/us/davinci-pas/StructureDefinition/extension-errorPath

Bundle (R4).entry.resource.ClaimResponse.error.extension (errorPath).valueString | string | Required | | 1..1 | The FHIR path expression that indicates which FHIR element that this error information is about. For example: "Bundle.entry[1].Claim.type.coding[1].code"

Bundle (R4).entry.resource.ClaimResponse.error.extension (followupAction) (also: extension (followupAction)) | Extension | Required | Yes | 1..1 | A code representing what action must occur to resolve this error, equivalent to AAA04 (ANSI X12 value). URL: http://hl7.org/fhir/us/davinci-pas/StructureDefinition/extension-errorFollowupAction

Bundle (R4).entry.resource.ClaimResponse.error.extension (followupAction).url | uri | Required | | 1..1 | URL of the extension: http://hl7.org/fhir/us/davinci-pas/StructureDefinition/extension-errorFollowupAction

Bundle (R4).entry.resource.ClaimResponse.error.extension (followupAction).valueCodeableConcept | CodeableConcept | Required | | 1..1 | A code representing what action must occur to resolve this error. It has a coding system of https://codesystem.x12.org/005010/889.

Bundle (R4).entry.resource.ClaimResponse.id | id | Optional | | 0..1 | ClaimResponse ID.

Bundle (R4).entry.resource.ClaimResponse.identifier | Identifier | Optional | Yes | 0..* | Identifies the ClaimResponse. This includes the identifier included in the original Claim request and a new identifier for the response.

Bundle (R4).entry.resource.ClaimResponse.identifier.extension (subDepartment) (also: extension (subDepartment)) | Extension | Optional | Yes | 0..1 | An additional element that provides a further subdivision within the organization granting the identifier, equivalent to TRN04 (ANSI X12 value). URL: http://hl7.org/fhir/us/davinci-pas/StructureDefinition/extension-identifierSubDepartment

Bundle (R4).entry.resource.ClaimResponse.identifier.extension (subDepartment).url | uri | Required | | 1..1 | URL of the extension: http://hl7.org/fhir/us/davinci-pas/StructureDefinition/extension-identifierSubDepartment

Bundle (R4).entry.resource.ClaimResponse.identifier.extension (subDepartment).valueString | string | Required | | 1..1 | Additional reference number.

Bundle (R4).entry.resource.ClaimResponse.identifier.system | String | Required | | 1..1 | System of the identifier, equivalent to TRN03 (ANSI X12 value). Uses a scheme of 'urn:trnorg:<TRN03>'.

Bundle (R4).entry.resource.ClaimResponse.identifier.value | String | Required | | 1..1 | Value of the identifier, equivalent to TRN02 (ANSI X12 value).

Bundle (R4).entry.resource.ClaimResponse.insurer | Reference | Required | | 1..1 | Party responsible for reimbursement. A reference to the Organization resource.

Bundle (R4).entry.resource.ClaimResponse.item | BackboneElement | Optional | Yes | 0..* | The items requested for prior authorization.

Bundle (R4).entry.resource.ClaimResponse.item.adjudication | BackboneElement | Optional | Yes | 0..1 | Item adjudication.

Bundle (R4).entry.resource.ClaimResponse.item.adjudication.category | CodeableConcept | Required | | 1..1 | Adjudication category. The coding system is http://terminology.hl7.org/CodeSystem/adjudication. The returned code is always “submitted”.

Bundle (R4).entry.resource.ClaimResponse.item.adjudication.extension (reviewAction) (also: extension (reviewAction)) | Extension | Optional | Yes | 0..1 | The details of the review action that are necessary for the authorization, equivalent to 2000F HCR (ANSI X12 value). URL: http://hl7.org/fhir/us/davinci-pas/StructureDefinition/extension-reviewAction

Bundle (R4).entry.resource.ClaimResponse.item.adjudication.extension (reviewAction).extension (number) (also: extension (number)) | Extension | Optional | Yes | 0..1 | Review number, equivalent to 2000F HCR02 (ANSI X12 value). URL: number

Bundle (R4).entry.resource.ClaimResponse.item.adjudication.extension (reviewAction).extension (number).url | uri | Required | | 1..1 | URL of the extension: number

Bundle (R4).entry.resource.ClaimResponse.item.adjudication.extension (reviewAction).extension (number).valueString | string | Required | | 1..1 | Review number value.

Bundle (R4).entry.resource.ClaimResponse.item.adjudication.extension (reviewAction).extension (reasonCode) (also: extension (reasonCode)) | Extension | Optional | Yes | 0..1 | Certification action code: indicates the reason for the approved, denied, pended, or other services, equivalent to 2000F HCR03 (ANSI X12 value). URL: reasonCode

Bundle (R4).entry.resource.ClaimResponse.item.adjudication.extension (reviewAction).extension (reasonCode).url | uri | Required | | 1..1 | URL for the extension: reasonCode

Bundle (R4).entry.resource.ClaimResponse.item.adjudication.extension (reviewAction).extension (reasonCode).valueCodeableConcept | CodeableConcept | Required | | 1..1 | Reason code value. It has a code system of https://codesystem.x12.org/external/886.

Bundle (R4).entry.resource.ClaimResponse.item.adjudication.extension (reviewAction).extension (reviewActionCode) (also: extension (reviewActionCode)) | Extension | Optional | Yes | 0..1 | Code for the review action, equivalent to 2000F HCR01 (ANSI X12 value). URL: http://hl7.org/fhir/us/davinci-pas/StructureDefinition/extension-reviewActionCode

Bundle (R4).entry.resource.ClaimResponse.item.adjudication.extension (reviewAction).extension (reviewActionCode).url | uri | Required | | 1..1 | URL of the extension: http://hl7.org/fhir/us/davinci-pas/StructureDefinition/extension-reviewActionCode

Bundle (R4).entry.resource.ClaimResponse.item.adjudication.extension (reviewAction).extension (reviewActionCode).valueCodeableConcept | CodeableConcept | Required | | 1..1 | Review action code for the adjudication. It has a code system of https://codesystem.x12.org/005010/306.

Bundle (R4).entry.resource.ClaimResponse.item.adjudication.extension (reviewAction).url | uri | Required | | 1..1 | URL of the extension: http://hl7.org/fhir/us/davinci-pas/StructureDefinition/extension-reviewAction

Bundle (R4).entry.resource.ClaimResponse.item.extension (administrationReferenceNumber) (also: extension (administrationReferenceNumber)) | Extension | Optional | Yes | 0..1 | A string assigned by the payer to the original disallowed review outcome associated with this service item, equivalent to 2000F REF*NT (ANSI X12 value). URL: http://hl7.org/fhir/us/davinci-pas/StructureDefinition/extension-administrationReferenceNumber

Bundle (R4).entry.resource.ClaimResponse.item.extension (administrationReferenceNumber).url | uri | Required | | 1..1 | URL of the extension: http://hl7.org/fhir/us/davinci-pas/StructureDefinition/extension-administrationReferenceNumber

Bundle (R4).entry.resource.ClaimResponse.item.extension (administrationReferenceNumber).valueString | string | Required | | 1..1 | Administrative reference number.

Bundle (R4).entry.resource.ClaimResponse.item.extension (authorizedItemDetail) (also: extension (authorizedItemDetail)) | Extension | Optional | Yes | 0..1 | The details of the requested item. URL: http://hl7.org/fhir/us/davinci-pas/StructureDefinition/extension-itemAuthorizedDetail

Bundle (R4).entry.resource.ClaimResponse.item.extension (authorizedItemDetail).extension (authorizedService) (also: extension (authorizedService)) | Extension | Optional | Yes | 0..1 | The ServiceRequest that contains the recurring quantity details of what has been requested for this item. If not recurring, item.extension:quantity is sent instead. URL: http://hl7.org/fhir/us/davinci-pas/StructureDefinition/extension-requestedService

Bundle (R4).entry.resource.ClaimResponse.item.extension (authorizedItemDetail).extension (authorizedService).url | uri | Required | | 1..1 | URL of the extension: http://hl7.org/fhir/us/davinci-pas/StructureDefinition/extension-requestedService

Bundle (R4).entry.resource.ClaimResponse.item.extension (authorizedItemDetail).extension (authorizedService).valueReference | Reference | Required | | 1..1 | Reference to authorized service. A reference to ServiceRequest resource.

Bundle (R4).entry.resource.ClaimResponse.item.extension (authorizedItemDetail).extension (modifier) (also: extension (modifier)) | Extension | Optional | Yes | 0..* | The modifier details of what has been requested for this item. URL: modifier

Bundle (R4).entry.resource.ClaimResponse.item.extension (authorizedItemDetail).extension (modifier).url | uri | Required | | 1..1 | URL of the extension: modifier

Bundle (R4).entry.resource.ClaimResponse.item.extension (authorizedItemDetail).extension (modifier).valueCodeableConcept | CodeableConcept | Required | | 1..1 | Service modifier. Coding system (depending on the type of modifier): http://www.ama-assn.org/go/cpt http://www.cms.gov/Medicare/Coding/HCPCSReleaseCodeSets https://open.epic.com/FHIR/(custom_OID)/custom-procedure-modifier

Bundle (R4).entry.resource.ClaimResponse.item.extension (authorizedItemDetail).extension (productOrServiceCode) (also: extension (productOrServiceCode)) | Extension | Optional | Yes | 0..1 | The productOrServiceCode details of what has been requested for this item. URL: productOrServiceCode

Bundle (R4).entry.resource.ClaimResponse.item.extension (authorizedItemDetail).extension (productOrServiceCode).url | uri | Required | | 1..1 | URL of the extension: productOrServiceCode

Bundle (R4).entry.resource.ClaimResponse.item.extension (authorizedItemDetail).extension (productOrServiceCode).valueCodeableConcept | CodeableConcept | Required | | 1..1 | Service code. Coding system (depending on the type of service): http://www.ama-assn.org/go/cpt http://www.cms.gov/Medicare/Coding/HCPCSReleaseCodeSets Code is set to the procedure code. Text is set to the procedure description.

Bundle (R4).entry.resource.ClaimResponse.item.extension (authorizedItemDetail).extension (quantity) (also: extension (quantity)) | Extension | Optional | Yes | 0..1 | The non-recurring quantity details of what has been requested for this item. If recurring, item.extension:authorizedService is sent instead. URL: quantity

Bundle (R4).entry.resource.ClaimResponse.item.extension (authorizedItemDetail).extension (quantity).url | uri | Required | | 1..1 | URL of the extension: quantity

Bundle (R4).entry.resource.ClaimResponse.item.extension (authorizedItemDetail).extension (quantity).valueQuantity | Quantity | Required | | 1..1 | Quantity amount.

Bundle (R4).entry.resource.ClaimResponse.item.extension (authorizedItemDetail).extension (revenue) (also: extension (revenue)) | Extension | Optional | Yes | 0..1 | The revenue details of what has been requested for this item. URL: http://hl7.org/fhir/us/davinci-pas/StructureDefinition/extension-revenueCode

Bundle (R4).entry.resource.ClaimResponse.item.extension (authorizedItemDetail).extension (revenue).url | uri | Required | | 1..1 | URL of the extension: http://hl7.org/fhir/us/davinci-pas/StructureDefinition/extension-revenueCode

Bundle (R4).entry.resource.ClaimResponse.item.extension (authorizedItemDetail).extension (revenue).valueCodeableConcept | CodeableConcept | Required | | 1..1 | Revenue code of the added service. It has a coding system of https://www.nubc.org/CodeSystem/RevenueCodes.

Bundle (R4).entry.resource.ClaimResponse.item.extension (authorizedItemDetail).url | uri | Required | | 1..1 | URL of the extension: http://hl7.org/fhir/us/davinci-pas/StructureDefinition/extension-itemAuthorizedDetail

Bundle (R4).entry.resource.ClaimResponse.item.extension (authorizedProvider) (also: extension (authorizedProvider)) | Extension | Optional | Yes | 0..* | The specific provider who has been authorized to provide this item. URL: http://hl7.org/fhir/us/davinci-pas/StructureDefinition/extension-itemAuthorizedProvider

Bundle (R4).entry.resource.ClaimResponse.item.extension (authorizedProvider).extension (provider) (also: extension (provider)) | Extension | Optional | Yes | 0..1 | The provider who is authorized to provider this item. URL: provider

Bundle (R4).entry.resource.ClaimResponse.item.extension (authorizedProvider).extension (provider).url | uri | Required | | 1..1 | URL of the extension: provider

Bundle (R4).entry.resource.ClaimResponse.item.extension (authorizedProvider).extension (provider).valueReference | Reference | Required | | 1..1 | Reference to the provider. A reference to Practitioner or Organization resource.

Bundle (R4).entry.resource.ClaimResponse.item.extension (authorizedProvider).extension (providerType) (also: extension (providerType)) | Extension | Optional | Yes | 0..1 | The provider types. URL: providerType

Bundle (R4).entry.resource.ClaimResponse.item.extension (authorizedProvider).extension (providerType).url | uri | Required | | 1..1 | URL of the extension: providerType

Bundle (R4).entry.resource.ClaimResponse.item.extension (authorizedProvider).extension (providerType).valueCodeableConcept | CodeableConcept | Required | | 1..1 | Provider type. Code system is set to “https://codesystem.x12.org/005010/98”.

Bundle (R4).entry.resource.ClaimResponse.item.extension (authorizedProvider).url | uri | Required | | 1..1 | URL of the extension: http://hl7.org/fhir/us/davinci-pas/StructureDefinition/extension-itemAuthorizedProvider

Bundle (R4).entry.resource.ClaimResponse.item.extension (itemTraceNumber) (also: extension (itemTraceNumber)) | Extension | Optional | Yes | 0..* | Uniquely identifies this claim item, equivalent to 2000F TRN (ANSI X12 value). URL: http://hl7.org/fhir/us/davinci-pas/StructureDefinition/extension-itemTraceNumber

Bundle (R4).entry.resource.ClaimResponse.item.extension (itemTraceNumber).url | uri | Required | | 1..1 | URL of the extension: http://hl7.org/fhir/us/davinci-pas/StructureDefinition/extension-itemTraceNumber

Bundle (R4).entry.resource.ClaimResponse.item.extension (itemTraceNumber).valueIdentifier | Identifier | Optional | | 0..1 | Trace number.

Bundle (R4).entry.resource.ClaimResponse.item.extension (itemTraceNumber).valueIdentifier.extension (subDepartment) (also: extension (subDepartment)) | Extension | Optional | Yes | 0..1 | An additional element that provides a further subdivision within the organization granting the identifier, equivalent to TRN04 (ANSI X12 value). URL: http://hl7.org/fhir/us/davinci-pas/StructureDefinition/extension-identifierSubDepartment

Bundle (R4).entry.resource.ClaimResponse.item.extension (itemTraceNumber).valueIdentifier.extension (subDepartment).url | uri | Required | | 1..1 | URL of the extension: http://hl7.org/fhir/us/davinci-pas/StructureDefinition/extension-identifierSubDepartment

Bundle (R4).entry.resource.ClaimResponse.item.extension (itemTraceNumber).valueIdentifier.extension (subDepartment).valueString | string | Required | | 1..1 | Additional reference number.

Bundle (R4).entry.resource.ClaimResponse.item.extension (itemTraceNumber).valueIdentifier.system | String | Required | | 1..1 | System of the identifier, equivalent to TRN03 (ANSI X12 value). Uses a scheme of 'urn:trnorg:<TRN03>'.

Bundle (R4).entry.resource.ClaimResponse.item.extension (itemTraceNumber).valueIdentifier.value | String | Required | | 1..1 | Value of the identifier, equivalent to TRN02 (ANSI X12 value).

Bundle (R4).entry.resource.ClaimResponse.item.extension (preAuthIssueDate) (also: extension (preAuthIssueDate)) | Extension | Optional | Yes | 0..1 | The date when this item's preauthorization was issued. URL: http://hl7.org/fhir/us/davinci-pas/StructureDefinition/extension-itemPreAuthIssueDate

Bundle (R4).entry.resource.ClaimResponse.item.extension (preAuthIssueDate).url | uri | Required | | 1..1 | URL of the extension: http://hl7.org/fhir/us/davinci-pas/StructureDefinition/extension-itemPreAuthIssueDate

Bundle (R4).entry.resource.ClaimResponse.item.extension (preAuthIssueDate).valueDate | date | Required | | 1..1 | The date when this item's preauthorization was issued.

Bundle (R4).entry.resource.ClaimResponse.item.extension (preAuthPeriod) (also: extension (preAuthPeriod)) | Extension | Optional | Yes | 0..1 | The date/period when this item's preauthorization is valid. URL: http://hl7.org/fhir/us/davinci-pas/StructureDefinition/extension-itemPreAuthPeriod

Bundle (R4).entry.resource.ClaimResponse.item.extension (preAuthPeriod).url | uri | Required | | 1..1 | URL of the extension: http://hl7.org/fhir/us/davinci-pas/StructureDefinition/extension-itemPreAuthPeriod

Bundle (R4).entry.resource.ClaimResponse.item.extension (preAuthPeriod).valuePeriod | Period | Required | | 1..1 | The period when this item's preauthorization is valid.

Bundle (R4).entry.resource.ClaimResponse.item.extension (preAuthPeriod).valuePeriod.end | String | Optional | | 0..1 | Preauthorization end date.

Bundle (R4).entry.resource.ClaimResponse.item.extension (preAuthPeriod).valuePeriod.start | String | Optional | | 0..1 | Preauthorization start date.

Bundle (R4).entry.resource.ClaimResponse.item.extension (previousAuthorizationNumber) (also: extension (previousAuthorizationNumber)) | Extension | Optional | Yes | 0..1 | A string assigned by the payer to an authorized review outcome associated with this service item, equivalent to 2000F REF*BB (ANSI X12 value). URL: http://hl7.org/fhir/us/davinci-pas/StructureDefinition/extension-authorizationNumber

Bundle (R4).entry.resource.ClaimResponse.item.extension (previousAuthorizationNumber).url | uri | Required | | 1..1 | URL of the extension: http://hl7.org/fhir/us/davinci-pas/StructureDefinition/extension-authorizationNumber

Bundle (R4).entry.resource.ClaimResponse.item.extension (previousAuthorizationNumber).valueString | string | Required | | 1..1 | A string assigned by the payer to an authorized review outcome associated with this service item.

Bundle (R4).entry.resource.ClaimResponse.item.extension (requestedServiceDate) (also: extension (requestedServiceDate)) | Extension | Optional | Yes | 0..1 | The original date/period that was requested by the submitter for this item. URL: http://hl7.org/fhir/us/davinci-pas/StructureDefinition/extension-itemRequestedServiceDate

Bundle (R4).entry.resource.ClaimResponse.item.extension (requestedServiceDate).url | uri | Required | | 1..1 | URL of the extension: http://hl7.org/fhir/us/davinci-pas/StructureDefinition/extension-itemRequestedServiceDate

Bundle (R4).entry.resource.ClaimResponse.item.extension (requestedServiceDate).valueDateTime (also: valueDateTime) | dateTime | Conditional | | 0..1 | The original date time that was requested by the submitter for this item. If it is a range of dates, valuePeriod is used.

Bundle (R4).entry.resource.ClaimResponse.item.extension (requestedServiceDate).valuePeriod | Period | Conditional | | 0..1 | The original period that was requested by the submitter for this item. If it is a single date, valueDateTime is used.

Bundle (R4).entry.resource.ClaimResponse.item.extension (requestedServiceDate).valuePeriod.end | String | Optional | | 0..1 | Requested end date.

Bundle (R4).entry.resource.ClaimResponse.item.extension (requestedServiceDate).valuePeriod.start | String | Optional | | 0..1 | Requested start date.

Bundle (R4).entry.resource.ClaimResponse.item.itemSequence | positiveInt | Required | | 1..1 | Claim item instance identifier.

Bundle (R4).entry.resource.ClaimResponse.item.noteNumber | positiveInt | Optional | Yes | 0..* | Applicable note numbers.

Bundle (R4).entry.resource.ClaimResponse.outcome | code | Required | | 1..1 | Code: complete | error | partial. An outcome for the overall prior auth status. Returns complete if a decision has been made on the authorization. Returns error if there are any non-operationOutcome errors. Returns partial if some services are still under review.

Bundle (R4).entry.resource.ClaimResponse.patient | Reference | Required | | 1..1 | A reference to the beneficiary patient. A reference to Patient resource.

Bundle (R4).entry.resource.ClaimResponse.preAuthPeriod | Period | Optional | | 0..1 | Preauthorization reference effective period.

Bundle (R4).entry.resource.ClaimResponse.preAuthPeriod.end | String | Optional | | 0..1 | Preauthorization reference effective end date.

Bundle (R4).entry.resource.ClaimResponse.preAuthPeriod.start | String | Optional | | 0..1 | Preauthorization reference effective start date.

Bundle (R4).entry.resource.ClaimResponse.preAuthRef | string | Optional | | 0..1 | Preauthorization reference.

Bundle (R4).entry.resource.ClaimResponse.processNote | BackboneElement | Optional | Yes | 0..* | Note concerning adjudication.

Bundle (R4).entry.resource.ClaimResponse.processNote.number | positiveInt | Required | | 1..1 | Note instance identifier.

Bundle (R4).entry.resource.ClaimResponse.processNote.text | string | Required | | 1..1 | Note text.

Bundle (R4).entry.resource.ClaimResponse.request | Reference | Required | | 1..1 | The associated request for this response. This contains the claim reference sent by the submitter. This response bundle does not contain the claim resource itself. A reference to Claim resource.

Bundle (R4).entry.resource.ClaimResponse.requestor | Reference | Optional | | 0..1 | Party responsible for the claim. A reference to Organization or PractitionerRole resource.

Bundle (R4).entry.resource.ClaimResponse.status | code | Required | | 1..1 | A code specifying the state of the resource instance. Sent as active.

Bundle (R4).entry.resource.ClaimResponse.type | CodeableConcept | Required | | 1..1 | The type of claim. The code system is set to http://terminology.hl7.org/CodeSystem/claim-type.

Bundle (R4).entry.resource.ClaimResponse.use | code | Required | | 1..1 | A code determines the use of the response body. Sent as preauthorization.

Bundle (R4).entry.resource.CommunicationRequest | Resource | Optional | | 0..* | CommunicationRequest resource.

Bundle (R4).entry.resource.CommunicationRequest.category | CodeableConcept | Optional | Yes | 0..1 | Message category. Code system is set to https://codesystem.x12.org/005010/755. Code value is set to X12 value of report type (PWK01). Code display is set to the name of the report type.

Bundle (R4).entry.resource.CommunicationRequest.extension (serviceLineNumber) (also: extension (serviceLineNumber)) | Extension | Optional | Yes | 0..1 | Service Line Number. URL: http://hl7.org/fhir/us/davinci-pas/StructureDefinition/extension-serviceLineNumber

Bundle (R4).entry.resource.CommunicationRequest.extension (serviceLineNumber).url | uri | Required | | 1..1 | URL of the extension: http://hl7.org/fhir/us/davinci-pas/StructureDefinition/extension-serviceLineNumber

Bundle (R4).entry.resource.CommunicationRequest.extension (serviceLineNumber).valuePositiveInt | positiveInt | Required | | 1..1 | Item sequence number.

Bundle (R4).entry.resource.CommunicationRequest.identifier | Identifier | Required | Yes | 1..1 | Unique Identifier used in linking the CommunicationRequest to the response (X12's Attachment Control Number). Value is set to the attachment control number.

Bundle (R4).entry.resource.CommunicationRequest.medium | CodeableConcept | Optional | Yes | 0..1 | A channel of communication. Code system is set to https://codesystem.x12.org/005010/756. Code value is set to “EL”. Code display is set to “Electronically Only”.

Bundle (R4).entry.resource.CommunicationRequest.payload | BackboneElement | Optional | Yes | 0..1 | Message payload.

Bundle (R4).entry.resource.CommunicationRequest.payload.contentString | string | Optional | | 0..1 | LOINC code.

Bundle (R4).entry.resource.CommunicationRequest.payload.extension (serviceLineNumber) (also: extension (serviceLineNumber)) | Extension | Optional | Yes | 0..1 | Service Line Number. URL: http://hl7.org/fhir/us/davinci-pas/StructureDefinition/extension-serviceLineNumber

Bundle (R4).entry.resource.CommunicationRequest.payload.extension (serviceLineNumber).url | uri | Required | | 1..1 | URL of the extension: http://hl7.org/fhir/us/davinci-pas/StructureDefinition/extension-serviceLineNumber

Bundle (R4).entry.resource.CommunicationRequest.payload.extension (serviceLineNumber).valuePositiveInt | positiveInt | Required | | 1..1 | Item sequence number.

Bundle (R4).entry.resource.CommunicationRequest.requester | Reference | Optional | | 0..1 | The entity requesting the service. Copies the reference of ClaimResponse.requestor if the type is Organization. A reference to Organization resource.

Bundle (R4).entry.resource.CommunicationRequest.sender | Reference | Optional | | 0..1 | Message sender. Copies the reference of ClaimResponse.insurer. A reference to Organization resource.

Bundle (R4).entry.resource.CommunicationRequest.status | code | Required | | 1..1 | The status of the communication request. Sent as active.

Bundle (R4).entry.resource.CommunicationRequest.subject | Reference | Optional | | 0..1 | Subject of the communication request. Copies the reference of ClaimResponse.patient. A reference to Patient resource.

Bundle (R4).entry.resource.Organization | Resource | Optional | | 0..* | Organization resource.

Bundle (R4).entry.resource.Organization.active | boolean | Required | | 1..1 | Whether the organization's record is still in active use. Sent as 1.

Bundle (R4).entry.resource.Organization.address | Address | Optional | Yes | 0..* | Address.

Bundle (R4).entry.resource.Organization.address.city | string | Optional | | 0..1 | Name of city or town.

Bundle (R4).entry.resource.Organization.address.line | string | Optional | Yes | 0..4 | Street name, number, direction, and P.O. Box.

Bundle (R4).entry.resource.Organization.address.postalCode | string | Optional | | 0..1 | US ZIP Codes.

Bundle (R4).entry.resource.Organization.address.state | string | Optional | | 0..1 | US state two-letter abbreviation. Value set: http://hl7.org/fhir/us/core/STU7/ValueSet-us-core-usps-state.html.

Bundle (R4).entry.resource.Organization.contact | BackboneElement | Optional | Yes | 0..* | Contact information.

Bundle (R4).entry.resource.Organization.contact.name | HumanName | Optional | | 0..1 | Contact name.

Bundle (R4).entry.resource.Organization.contact.telecom | ContactPoint | Optional | Yes | 0..* | Contact detail.

Bundle (R4).entry.resource.Organization.contact.telecom.system | code | Required | | 1..1 | Telecommunication form of contact point. Depending on what information was received, it can contain: phone, fax, email.

Bundle (R4).entry.resource.Organization.contact.telecom.value | string | Required | | 1..1 | The actual contact point details, in a form that is meaningful to the designated communication system (such as phone number or email address).

Bundle (R4).entry.resource.Organization.identifier | Identifier | Optional | Yes | 0..* | All identifiers.

Bundle (R4).entry.resource.Organization.identifier.system | String | Required | | 1..1 | The system for the identifier value which is copied from the request. Supported systems: http://terminology.hl7.org/NamingSystem/USEIN (TIN) http://hl7.org/fhir/sid/us-npi (NPI)

Bundle (R4).entry.resource.Organization.identifier.type | CodeableConcept | Optional | | 0..1 | Identifier type. This is only used for when Organization is ClaimResponse.insurer. Coding system is set to http://hl7.org/fhir/us/carin-bb/CodeSystem/C4BBIdentifierType, and code is set to “payerid”.

Bundle (R4).entry.resource.Organization.identifier.value | String | Required | | 1..1 | Identifier value that is copied from the request.

Bundle (R4).entry.resource.Organization.name | string | Required | | 1..1 | Name.

Bundle (R4).entry.resource.Organization.telecom | ContactPoint | Optional | Yes | 0..* | Contact detail.

Bundle (R4).entry.resource.Organization.telecom.system | code | Required | | 1..1 | Telecommunication form of contact point. Depending on what information was received, it can contain: phone, fax, email.

Bundle (R4).entry.resource.Organization.telecom.value | string | Required | | 1..1 | The actual contact point details in a form that is meaningful to the designated communication system (such as phone number or email address).

Bundle (R4).entry.resource.Organization.type | CodeableConcept | Optional | Yes | 0..* | Coding system is set to https://codesystem.x12.org/005010/98. For ClaimResponse.Insurer, the code is one of the following: 2B, 36, PR, X3.

Bundle (R4).entry.resource.Patient | Resource | Optional | | 0..* | Patient resource.

Bundle (R4).entry.resource.Patient.address | Address | Optional | Yes | 0..* | Address.

Bundle (R4).entry.resource.Patient.address.city | string | Optional | | 0..1 | Name of city or town.

Bundle (R4).entry.resource.Patient.address.line | string | Optional | Yes | 0..4 | Street name, number, direction, and P.O. Box.

Bundle (R4).entry.resource.Patient.address.postalCode | string | Optional | | 0..1 | US ZIP Codes.

Bundle (R4).entry.resource.Patient.address.state | string | Optional | | 0..1 | US state two-letter abbreviation. Value set: http://hl7.org/fhir/us/core/STU7/ValueSet-us-core-usps-state.html.

Bundle (R4).entry.resource.Patient.birthDate | date | Optional | | 0..1 | Birth date.

Bundle (R4).entry.resource.Patient.gender | code | Required | | 1..1 | Gender. Code: male | female | other | unknown

Bundle (R4).entry.resource.Patient.identifier | Identifier | Required | Yes | 1..* | All Identifiers

Bundle (R4).entry.resource.Patient.identifier.system | String | Required | | 1..1 | The system for the identifier value which is copied from the request. Supported systems from request: urn:oid:2.16.840.1.113883.4.1 (SSN) http://open.epic.com/FHIR/StructureDefinition/member-id (Member ID) Other OID or URN that are mapped in internal system

Bundle (R4).entry.resource.Patient.identifier.type | CodeableConcept | Optional | | 0..1 | Identifier type. This is only used for Member ID. Coding system is set to http://terminology.hl7.org/CodeSystem/v2-0203, and code is set to “MB”.

Bundle (R4).entry.resource.Patient.identifier.value | String | Required | | 1..1 | Identifier value that is copied from the request. Member ID value is coming from the sytem.

Bundle (R4).entry.resource.Patient.name | HumanName | Required | Yes | 1..* | Name.

Bundle (R4).entry.resource.Patient.name.family | string | Optional | | 0..1 | Family name (surname).

Bundle (R4).entry.resource.Patient.name.given | string | Optional | Yes | 0..* | Given name (includes middle name).

Bundle (R4).entry.resource.Patient.name.suffix | string | Optional | Yes | 0..* | Suffix.

Bundle (R4).entry.resource.Patient.telecom | ContactPoint | Optional | Yes | 0..* | Contact details.

Bundle (R4).entry.resource.Patient.telecom.system | code | Required | | 1..1 | Telecommunication form of contact point. Depending on what information was received, it can contain: phone, fax, email.

Bundle (R4).entry.resource.Patient.telecom.value | string | Required | | 1..1 | The actual contact point details in a form that is meaningful to the designated communication system (such as phone number or email address).

Bundle (R4).entry.resource.Practitioner | Resource | Optional | | 0..* | Practitioner resource.

Bundle (R4).entry.resource.Practitioner.address | Address | Optional | Yes | 0..* | Address.

Bundle (R4).entry.resource.Practitioner.address.city | string | Optional | | 0..1 | Name of city or town.

Bundle (R4).entry.resource.Practitioner.address.line | string | Optional | Yes | 0..4 | Street name, number, direction, and P.O. Box.

Bundle (R4).entry.resource.Practitioner.address.postalCode | string | Optional | | 0..1 | US ZIP Codes.

Bundle (R4).entry.resource.Practitioner.address.state | string | Optional | | 0..1 | US state two-letter abbreviation. Value set: http://hl7.org/fhir/us/core/STU7/ValueSet-us-core-usps-state.html.

Bundle (R4).entry.resource.Practitioner.identifier | Identifier | Required | Yes | 1..* | All identifiers.

Bundle (R4).entry.resource.Practitioner.identifier.system | String | Required | | 1..1 | The system for the identifier value which is copied from request. Supported systems for request: http://terminology.hl7.org/NamingSystem/USEIN (TIN) http://hl7.org/fhir/sid/us-npi (NPI)

Bundle (R4).entry.resource.Practitioner.identifier.value | String | Required | | 1..1 | Identifier value that is copied from the request.

Bundle (R4).entry.resource.Practitioner.name | HumanName | Required | Yes | 1..* | Name.

Bundle (R4).entry.resource.Practitioner.name.family | string | Required | | 1..1 | Family name (surname).

Bundle (R4).entry.resource.Practitioner.name.given | string | Optional | Yes | 0..* | Given name (includes middle name).

Bundle (R4).entry.resource.Practitioner.name.suffix | string | Optional | Yes | 0..* | Suffix.

Bundle (R4).entry.resource.Practitioner.telecom | ContactPoint | Optional | Yes | 0..* | Contact details.

Bundle (R4).entry.resource.Practitioner.telecom.system | code | Required | | 1..1 | Telecommunication form of contact point. Depending on what information was received, it can contain: phone, fax, email.

Bundle (R4).entry.resource.Practitioner.telecom.value | string | Required | | 1..1 | The actual contact point details in a form that is meaningful to the designated communication system (such as phone number or email address).

Bundle (R4).entry.resource.PractitionerRole | Resource | Optional | | 0..* | PractitionerRole resource.

Bundle (R4).entry.resource.PractitionerRole.practitioner | Reference | Required | | 1..1 | Practitioner that can provide the defined services for the organization. A reference to Practitioner resource.

Bundle (R4).entry.resource.ServiceRequest | Resource | Optional | | 0..* | ServiceRequest resource.

Bundle (R4).entry.resource.ServiceRequest.intent | code | Required | | 1..1 | The kind of service request. Sent as order.

Bundle (R4).entry.resource.ServiceRequest.occurrenceTiming | Timing | Optional | | 0..1 | A timing schedule that specifies an event that can occur multiple times.

Bundle (R4).entry.resource.ServiceRequest.occurrenceTiming.repeat | BackboneElement | Required | | 1..1 | When the event is to occur.

Bundle (R4).entry.resource.ServiceRequest.occurrenceTiming.repeat.boundsDuration | Duration | Optional | | 0..1 | The number of periods over which the service is delivered.

Bundle (R4).entry.resource.ServiceRequest.occurrenceTiming.repeat.boundsDuration.code | code | Required | | 1..1 | Units (h | d | wk | mo | a).

Bundle (R4).entry.resource.ServiceRequest.occurrenceTiming.repeat.boundsDuration.system | uri | Required | | 1..1 | URL of the system: http://unitsofmeasure.org.

Bundle (R4).entry.resource.ServiceRequest.occurrenceTiming.repeat.boundsDuration.unit | string | Required | | 1..1 | Unit representation.

Bundle (R4).entry.resource.ServiceRequest.occurrenceTiming.repeat.boundsDuration.value | decimal | Required | | 1..1 | Value of the duration.

Bundle (R4).entry.resource.ServiceRequest.occurrenceTiming.repeat.period | decimal | Required | | 1..1 | The number of times the event occurs within the specified time period. Sent as 1.

Bundle (R4).entry.resource.ServiceRequest.occurrenceTiming.repeat.periodUnit | code | Required | | 1..1 | Units (h | d | wk | mo | a). BoundsDuration.code and periodUnit are the same.

Bundle (R4).entry.resource.ServiceRequest.quantityQuantity | Quantity | Optional | | 0..1 | A fixed quantity.

Bundle (R4).entry.resource.ServiceRequest.quantityQuantity.system | String | Required | | 1..1 | System that defines coded unit form. It has a system of https://codesystem.x12.org/005010/673.

Bundle (R4).entry.resource.ServiceRequest.quantityQuantity.unit | String | Required | | 1..1 | Unit representation.

Bundle (R4).entry.resource.ServiceRequest.quantityQuantity.value | Decimal | Required | | 1..1 | Quantity value.

Bundle (R4).entry.resource.ServiceRequest.status | code | Required | | 1..1 | Status of the service. Sent as active.

Bundle (R4).entry.resource.ServiceRequest.subject | Reference | Required | | 1..1 | Individual or Entity the service is ordered for. UUID of the patient of the beneficiary patient is sent. A reference to Patient resource.

Bundle (R4).timestamp | instant | Required | | 1..1 | The time of Bundle creation.

Bundle (R4).type | code | Required | | 1..1 | Purpose of the Bundle. Sent as collection.

Sample request


```
{
  "resourceType": "Bundle",
  "id": "ePASReq-1BN5hL9",
  "meta": {
```

```
  "profile": [
    "http://hl7.org/fhir/us/davinci-pas/StructureDefinition/profile-pas-request-bundle"
  ]
},
"identifier": {
  "value": "AUTH-REQ-12345"
},
"type": "collection",
"timestamp": "2026-01-22T22:37:07Z",
"entry": [
  {
    "fullUrl": "https://hostname/instance/api/FHIR/R4/Claim/eClm-4RW7xM2",
    "resource": {
      "resourceType": "Claim",
      "id": "eClm-4RW7xM2",
      "identifier": [
        {
          "system": "urn:oid:2.16.840.1.113883.3.12345.4.1",
          "value": "AUTH-REQ-12345"
        }
      ],
      "status": "active",
      "type": {
        "coding": [
          {
            "system": "http://terminology.hl7.org/CodeSystem/claim-type",
            "code": "professional",
            "display": "Professional"
          }
        ]
      },
      "use": "preauthorization",
      "patient": {
        "reference": "Patient/ePat-9XC4wD1"
      },
      "billablePeriod": {
        "start": "2026-01-22",
        "end": "2026-04-22"
      },
      "created": "2026-01-22T22:37:07Z",
      "insurer": {
        "reference": "Organization/eIns-5YH1bR8"
      },
      "provider": {
        "reference": "PractitionerRole/eProvRole-6VA2mE7"
      },
      "priority": {
        "coding": [
          {
            "system": "http://terminology.hl7.org/CodeSystem/processpriority",
            "code": "normal"
          }
        ]
      },
      "careTeam": [
        {
          "extension": [
            {
              "valueBoolean": true,
              "url": "http://hl7.org/fhir/us/davinci-pas/StructureDefinition/extension-careTeamClaimScope"
            }
          ],
          "sequence": 1,
          "provider": {
            "reference": "PractitionerRole/eProvRole-6VA2mE7"
          },
          "role": {
            "coding": [
              {
                "system": "https://codesystem.x12.org/005010/98",
                "code": "SJ",
                "display": "Service Provider"
              },
              {
                "system": "https://codesystem.x12.org/005010/1221",
                "code": "PE",
                "display": "Performing"
              }
            ]
          }
        },
        {
          "extension": [
            {
              "valueBoolean": true,
              "url": "http://hl7.org/fhir/us/davinci-pas/StructureDefinition/extension-careTeamClaimScope"
            }
          ],
          "sequence": 2,
```

```
    "provider": {
      "reference": "Organization/eOrg-7FM6nS3"
    },
    "role": {
      "coding": [
        {
          "system": "https://codesystem.x12.org/005010/98",
          "code": "77",
          "display": "Service Location"
        },
        {
          "system": "https://codesystem.x12.org/005010/1221",
          "code": "PE",
          "display": "Performing"
        }
      ]
    }
  }
],
"supportingInfo": [
  {
    "sequence": 1,
    "category": {
      "coding": [
        {
          "system": "http://hl7.org/fhir/us/davinci-pas/CodeSystem/PASTempCodes",
          "code": "patientEvent"

        }
      ]
    },
    "timingPeriod": {
      "start": "2026-01-22",
      "end": "2026-04-22"
    }
  }
],
"diagnosis": [
  {
    "sequence": 1,
    "diagnosisCodeableConcept": {
      "coding": [
        {
          "system": "http://hl7.org/fhir/sid/icd-10-cm",
          "code": "M25.571",
          "display": "Pain in right ankle and joints of right foot"
        }
      ]
    }
  }
],
"insurance": [
  {
    "sequence": 1,
    "focal": true,
    "coverage": {
      "reference": "Coverage/eCov-2JL9pQ4"
    }
  }
],
"item": [
  {
    "extension": [
      {
        "valueIdentifier": {
          "system": "urn:oid:2.16.840.1.113883.3.12345.4.1",
          "value": "LINE-ITEM-001"
        },
        "url": "http://hl7.org/fhir/us/davinci-pas/StructureDefinition/extension-itemTraceNumber"
      },
      {
        "valueCodeableConcept": {
          "coding": [
            {
              "system": "https://codesystem.x12.org/005010/1525",
              "code": "HS",
              "display": "HealthServices Review"
            }
          ]
        },
        "url": "http://hl7.org/fhir/us/davinci-pas/StructureDefinition/extension-serviceItemRequestType"
      },
      {
        "valueCodeableConcept": {
          "coding": [
            {
              "system": "https://codesystem.x12.org/005010/1322",
              "code": "I",
              "display": "Initial"
            }
```

```
            ]
          },
          "url": "http://hl7.org/fhir/us/davinci-pas/StructureDefinition/extension-certificationType"
        }
      ],
      "sequence": 1,
      "diagnosisSequence": [
        1
      ],
      "informationSequence": [
        1
      ],
      "revenue": {
        "coding": [
          {
            "system": "https://www.nubc.org/CodeSystem/RevenueCodes",
            "code": "0510",
            "display": "Clinic - General Classification"
          }
        ]
      },
      "category": {
        "coding": [
          {
            "system": "https://codesystem.x12.org/005010/1365",
            "code": "3",
            "display": "Consultation"
          }
        ]
      },
      "productOrService": {
        "coding": [
          {
            "system": "http://www.ama-assn.org/go/cpt",
            "code": "99213",
            "display": "Office or other outpatient visit, established patient"
          }
        ]
      },
      "locationCodeableConcept": {
        "coding": [
          {
            "system": "https://www.cms.gov/Medicare/Coding/place-of-service-codes/Place_of_Service_Code_Set",
            "code": "11",
            "display": "Office"
          }
        ]
      },
      "quantity": {
        "value": 1,
        "unit": "Units",
        "system": "https://codesystem.x12.org/005010/673",
        "code": "FL"
      }
    }
  ]
 }
},
{
  "fullUrl": "https://hostname/instance/api/FHIR/R4/Coverage/eCov-2JL9pQ4",
  "resource": {
    "resourceType": "Coverage",
    "id": "eCov-2JL9pQ4",
    "identifier": [
      {
        "type": {
          "coding": [
            {
              "system": "http://terminology.hl7.org/CodeSystem/v2-0203",
              "code": "MB",
              "display": "Member Number"
            }
          ]
        },
        "system": "urn:oid:2.16.840.1.113883.3.67890.1.2",
        "value": "MEMBER-123456"
      }
    ],
    "status": "active",
    "beneficiary": {
      "reference": "Patient/ePat-9XC4wD1"
    },
    "relationship": {
      "coding": [
        {
          "system": "https://codesystem.x12.org/005010/1069",
          "code": "18",
          "display": "Self"
        }
```

```
      ]
    },
    "payor": [
      {
        "reference": "Organization/eIns-5YH1bR8"
      }
    ],
    "class": [
      {
        "type": {
          "coding": [
            {
              "system": "http://terminology.hl7.org/CodeSystem/coverage-class",
              "code": "group",
              "display": "Group"
            }
          ]
        },
        "value": "GROUP-001",
        "name": "Example Health Plan Group"
      }
    ]
  }
},
{
  "fullUrl": "https://hostname/instance/api/FHIR/R4/Organization/eIns-5YH1bR8",
  "resource": {
    "resourceType": "Organization",
    "id": "eIns-5YH1bR8",
    "identifier": [
      {
        "type": {
          "coding": [
            {
              "system": "https://codesystem.x12.org/005010/66",
              "code": "PI",
              "display": "PayerIdentification"
            },
            {
              "system": "http://hl7.org/fhir/us/carin-bb/CodeSystem/C4BBIdentifierType",
              "code": "payerid"
            }
          ]
        },
        "value": "PAYER-12345"
      }
    ],
    "active": true,
    "type": [
      {
        "coding": [
          {
            "system": "https://codesystem.x12.org/005010/98",
            "code": "X3",
            "display": "Third Party Administrator"
          }
        ]
      }
    ],
    "name": "Test Insurer"
  }
},
{
  "fullUrl": "https://hostname/instance/api/FHIR/R4/Organization/eOrg-7FM6nS3",
  "resource": {
    "resourceType": "Organization",
    "id": "eOrg-7FM6nS3",
    "identifier": [
      {
        "system": "http://hl7.org/fhir/sid/us-npi",
        "value": "1234567890"
      }
    ],
    "active": true,
    "name": "Test Medical Center"
  }
},
{
  "fullUrl": "https://hostname/instance/api/FHIR/R4/Patient/ePat-9XC4wD1",
  "resource": {
    "resourceType": "Patient",
    "id": "ePat-9XC4wD1",
    "identifier": [
      {
        "type": {
          "coding": [
            {
              "system": "http://terminology.hl7.org/CodeSystem/v2-0203",
              "code": "MB",
```

```
                "display": "MemberNumber"
              }
            ]
          },
          "system": "urn:oid:2.16.840.1.113883.3.67890.1.2",
          "value": "MEMBER-123456"
        }
      ],
      "name": [
        {
          "family": "Patient",
          "given": [
            "Test"
          ]
        }
      ],
      "gender": "male",
      "birthDate": "1980-01-15",
      "address": [
        {
          "line": [
            "123 Main Street"
          ],
          "city": "Madison",
          "state": "WI",
          "postalCode": "53703"
        }
      ]
    }
  },
  {
    "fullUrl": "https://hostname/instance/api/FHIR/R4/Practitioner/eProv-3KG8jT5",
    "resource": {
      "resourceType": "Practitioner",
      "id": "eProv-3KG8jT5",
      "identifier": [
        {
          "type": {
            "coding": [
              {
                "system": "https://codesystem.x12.org/005010/66",
                "code": "XX",
                "display": "Health Care Financing AdministrationNational Provider Identifier"
              }
            ]
          },
          "system": "http://hl7.org/fhir/sid/us-npi",
          "value": "9876543210"
        }
      ],
      "name": [
        {
          "family": "Practitioner",
          "given": [
            "Test",
            "T"
          ]
        }
      ],
      "telecom": [
        {
          "system": "phone",
          "value": "608-555-1234"
        }
      ],
      "address": [
        {
          "line": [
            "456 Medical Plaza"
          ],
          "city": "Madison",
          "state": "WI",
          "postalCode": "53715"
        }
      ]
    }
  },
  {
    "fullUrl": "https://hostname/instance/api/FHIR/R4/PractitionerRole/eProvRole-6VA2mE7",
    "resource": {
      "resourceType": "PractitionerRole",
      "id": "eProvRole-6VA2mE7",
      "practitioner": {
        "reference": "Practitioner/eProv-3KG8jT5"
      }
    }
  }
]
}
```

Sample response


```
{
  "resourceType": "Bundle",
  "id": "ePASResp-4QR8kW2",
  "meta": {
    "profile": [
      "http://hl7.org/fhir/us/davinci-pas/StructureDefinition/profile-pas-response-bundle"
    ]
  },
  "identifier": {
    "value": "AUTH-REQ-12345"
  },
  "type": "collection",
  "timestamp": "2026-01-22T22:37:10Z",
  "entry": [
    {
      "fullUrl": "https://hostname/instance/api/FHIR/R4/ClaimResponse/eClmR-8TN3vK6",
      "resource": {
        "resourceType": "ClaimResponse",
        "id": "eClmR-8TN3vK6",
        "identifier": [
          {
            "system": "urn:oid:2.16.840.1.113883.3.67890.1.1",
            "value": "AUTH-RESP-67890"
          },
          {
            "system": "urn:oid:2.16.840.1.113883.3.12345.4.1",
            "value": "AUTH-REQ-12345"
          }
        ],
        "status": "active",
        "type": {
          "coding": [
            {
              "system": "http://terminology.hl7.org/CodeSystem/claim-type",
              "code": "professional",
              "display": "Professional"
            }
          ]
        },
        "use": "preauthorization",
        "patient": {
          "reference": "Patient/ePat-9XC4wD1"
        },
        "created": "2026-01-22T22:37:10Z",
        "insurer": {
          "reference": "Organization/eIns-5YH1bR8"
        },
        "requestor": {
          "reference": "PractitionerRole/eProvRole-6VA2mE7"
        },
        "request": {
          "reference": "Claim/eClm-4RW7xM2"
        },
        "outcome": "complete",
        "preAuthRef": "AUTH-NUM-987654",
        "item": [
          {
            "extension": [
              {
                "valueIdentifier": {
                  "system": "urn:oid:2.16.840.1.113883.3.67890.1.1",
                  "value": "LINE-AUTH-001"
                },
                "url": "http://hl7.org/fhir/us/davinci-pas/StructureDefinition/extension-itemTraceNumber"
              },
              {
                "valueIdentifier": {
                  "system": "urn:oid:2.16.840.1.113883.3.12345.4.1",
                  "value": "LINE-ITEM-001"
                },
                "url": "http://hl7.org/fhir/us/davinci-pas/StructureDefinition/extension-itemTraceNumber"
              },
              {
                "valueString": "AUTH-NUM-987654",
                "url": "http://hl7.org/fhir/us/davinci-pas/StructureDefinition/extension-administrationReferenceNumber"
              },
              {
                "extension": [
                  {
                    "valueCodeableConcept": {
                      "coding": [
                        {
                          "system": "https://www.nubc.org/CodeSystem/RevenueCodes",
                          "code": "0510",
                          "display": "Clinic - General Classification"
                        }
                      ]
```

```
                },
                "url": "http://hl7.org/fhir/us/davinci-pas/StructureDefinition/extension-revenueCode"
              },
              {
                "valueCodeableConcept": {
                  "coding": [
                    {
                      "system": "http://www.ama-assn.org/go/cpt",
                      "code": "99213",
                      "display": "Office or other outpatient visit, established patient"
                    }
                  ]
                },
                "url": "productOrServiceCode"
              }
            ],
            "url": "http://hl7.org/fhir/us/davinci-pas/StructureDefinition/extension-itemAuthorizedDetail"
          }
        ],
        "itemSequence": 1,
        "adjudication": [
          {
            "extension": [
              {
                "extension": [
                  {
                    "valueCodeableConcept": {
                      "coding": [
                        {
                          "system": "https://codesystem.x12.org/005010/306",
                          "code": "A1",
                          "display": "Certified in Total"
                        }
                      ]
                    },
                    "url": "http://hl7.org/fhir/us/davinci-pas/StructureDefinition/extension-reviewActionCode"
                  }
                ],
                "url": "http://hl7.org/fhir/us/davinci-pas/StructureDefinition/extension-reviewAction"
              }
            ],
            "category": {
              "coding": [
                {
                  "system": "http://terminology.hl7.org/CodeSystem/adjudication",
                  "code": "submitted"
                }
              ]
            }
          }
        ]
      }
    ],
    "adjudication": [
      {
        "extension": [
          {
            "extension": [
              {
                "valueCodeableConcept": {
                  "coding": [
                    {
                      "system": "https://codesystem.x12.org/005010/306",
                      "code": "A1",
                      "display": "Certified in Total"
                    }
                  ]
                },
                "url": "http://hl7.org/fhir/us/davinci-pas/StructureDefinition/extension-reviewActionCode"
              }
            ],
            "url": "http://hl7.org/fhir/us/davinci-pas/StructureDefinition/extension-reviewAction"
          }
        ],
        "category": {
          "coding": [
            {
              "system": "http://terminology.hl7.org/CodeSystem/adjudication",
              "code": "submitted"
            }
          ]
        }
      }
    ]
  }
},
{
  "fullUrl": "https://hostname/instance/api/FHIR/R4/Organization/eIns-5YH1bR8",
  "resource": {
```

```
    "resourceType": "Organization",
    "id": "eIns-5YH1bR8",
    "identifier": [
      {
        "type": {
          "coding": [
            {
              "system": "https://codesystem.x12.org/005010/66",
              "code": "PI",
              "display": "PayerIdentification"
            },
            {
              "system": "http://hl7.org/fhir/us/carin-bb/CodeSystem/C4BBIdentifierType",
              "code": "payerid"
            }
          ]
        },
        "value": "PAYER-12345"
      }
    ],
    "active": true,
    "type": [
      {
        "coding": [
          {
            "system": "https://codesystem.x12.org/005010/98",
            "code": "X3",
            "display": "Third Party Administrator"
          }
        ]
      }
    ],
    "name": "Test Insurer"
  }
},
{
  "fullUrl": "https://hostname/instance/api/FHIR/R4/Patient/ePat-9XC4wD1",
  "resource": {
    "resourceType": "Patient",
    "id": "ePat-9XC4wD1",
    "identifier": [
      {
        "type": {
          "coding": [
            {
              "system": "http://terminology.hl7.org/CodeSystem/v2-0203",
              "code": "MB",
              "display": "MemberNumber"
            }
          ]
        },
        "system": "urn:oid:2.16.840.1.113883.3.67890.1.2",
        "value": "MEMBER-123456"
      }
    ],
    "name": [
      {
        "family": "Patient",
        "given": [
          "Test"
        ]
      }
    ],
    "gender": "male",
    "birthDate": "1980-01-15",
    "address": [
      {
        "line": [
          "123 Main Street"
        ],
        "city": "Madison",
        "state": "WI",
        "postalCode": "53703"
      }
    ]
  }
},
{
  "fullUrl": "https://hostname/instance/api/FHIR/R4/Practitioner/eProv-3KG8jT5",
  "resource": {
    "resourceType": "Practitioner",
    "id": "eProv-3KG8jT5",
    "identifier": [
      {
        "type": {
          "coding": [
            {
              "system": "https://codesystem.x12.org/005010/66",
              "code": "XX",
```

```
                  "display": "Health Care Financing AdministrationNational Provider Identifier"
                }
              ]
            },
            "system": "http://hl7.org/fhir/sid/us-npi",
            "value": "9876543210"
          }
        ],
        "name": [
          {
            "family": "Practitioner",
            "given": [
              "Test",
              "T"
            ]
          }
        ],
        "telecom": [
          {
            "system": "phone",
            "value": "608-555-1234"
          }
        ],
        "address": [
          {
            "line": [
              "456 Medical Plaza"
            ],
            "city": "Madison",
            "state": "WI",
            "postalCode": "53715"
          }
        ]
      }
    },
    {
      "fullUrl": "https://hostname/instance/api/FHIR/R4/PractitionerRole/eProvRole-6VA2mE7",
      "resource": {
        "resourceType": "PractitionerRole",
        "id": "eProvRole-6VA2mE7",
        "practitioner": {
          "reference": "Practitioner/eProv-3KG8jT5"
        }
      }
    }
  ]
}
```


14.1.13 Condition.Read (Outside Record Encounter Diagnosis) (R4)

File: site/apis/14-CMS-Incoming/1-R4/11387-Condition-Read-Outside-Record-Encounter-Diagnosis-R4.html
Epic API ID | 11387
FHIR version | R4
Categories | CMS Incoming
API type | USCDI
A la carte | Industry-Standard Level 1 API
USCDI | Yes
Available in inpatient and other contexts | Yes
HTTP method | GET
URL template | /api/FHIR/R4/Condition/{ID}
Supports OAuth 2.0 | True
Supported user types | Backend Systems and Non-OAuth 2.0, Clinicians or Administrative Users, Patients
Performs scope validation | False
Source | https://fhir.epic.com/Specifications?api=11387

Description

Use this API to look up a specific instance of a patient's encounter diagnosis. This web service returns a point in time diagnosis (for example from a physician or nurse) in context of an encounter.

The data returned by this API includes the minimal set of data to record, search, and fetch information about an encounter diagnosis. This API does not return Problems and Health Concerns.

This API differs from other

Condition.Read (Encounter Diagnosis) (R4)

APIs because it returns data obtained as part of payer data exchange workflows rather than directly recorded during patient care. This data can come from payers, providers, or loaded from other FHIR servers. Because this data doesn't originate from the organization being queried, users of this API should be aware that the data might be unverified, incomplete, or duplicative.

Data from outside payer and provider systems is saved to an organization's database and returned in a standard format, documented below. Data loaded from other FHIR servers is returned in the format the organization received it. Because of this, the documentation below does not apply to these loaded resources. These resources can include any elements from the

FHIR specification and can be distinguished from other resources by the presence of meta.tag set to “external-bulk-data".

Request parameters

Name | Type | Optional | Array | Cardinality | Description
ID | token | Required | | 1..1 | A Condition FHIR ID.

Response elements

Name | Type | Optional | Array | Cardinality | Description
Condition (R4) | Condition | | | | An instance of the R4 Condition resource.
Condition (R4).abatementDateTime | dateTime | Required | | 0..1 | If a Condition has a resolved date, it appears here.
Condition (R4).category | CodeableConcept | Required | Yes | 1..* | Always includes category codes "encounter-diagnosis" and "external-encounter-diagnosis" .
Condition (R4).clinicalStatus | CodeableConcept | Required | | 0..1 | The clinical status, which can be active, resolved, or inactive.
Condition (R4).code | CodeableConcept | Required | | 1..1 | Sends a list of external codes for the Condition. If there are no available Condition codes, then the name of the Condition is used instead.
Condition (R4).encounter | Reference | Required | | 0..1 | Reference to the Encounter associated with this Condition.
Condition (R4).id | id | Required | | 1..1 | The condition FHIR ID.
Condition (R4).meta | Meta | | | | Metadata about the resource, including information about the origin or source of the data.
Condition (R4).meta.tag | Coding | | Yes | | Set to external-bulk-data for resources originally loaded from another FHIR server. If this element is set to external-bulk-data, all other element-level documentation does not apply to the resource. The resource content might vary and can include any elements allowed by the FHIR specification.
Condition (R4).onsetDateTime | dateTime | Required | | 0..1 | If a Condition has a noted date, it appears here.
Condition (R4).recordedDate (also: recordedDate) | dateTime | Required | | 0..1 | The date that the encounter diagnosis was first recorded.
Condition (R4).subject | Reference | Required | | 1..1 | The patient associated with the Condition.
Condition (R4).verificationStatus | CodeableConcept | Required | | 0..1 | This value is "confirmed".

Sample request

```
GET https://hostname/instance/api/FHIR/R4/Condition/fiBlR0m-dBY4.0Nt22-h6tKYxDBU.cTXxMav4LO7MO4I4
```

Sample response


```
{
  "resourceType": "Condition",
  "id": "fiBlR0m-dBY4.0Nt22-h6tKYxDBU.cTXxMav4LO7MO4I4",
  "extension": [
    {
      "valueDateTime": "02/28/2020 12:00 AM",
      "url": "http://hl7.org/fhir/StructureDefinition/condition-assertedDate"
    }
  ],
  "verificationStatus": {
    "coding": [
      {
        "system": "http://terminology.hl7.org/CodeSystem/condition-ver-status",
        "version": "4.0.0",
        "code": "confirmed",
        "display": "Confirmed"
      }
    ],
    "text": "Confirmed"
  },
  "category": [
    {
      "coding": [
        {
          "system": "http://terminology.hl7.org/CodeSystem/condition-category",
          "code": "encounter-diagnosis",
          "display": "Encounter Diagnosis"
        }
      ],
      "text": "Encounter Diagnosis"
    },
    {
      "coding": [
        {
          "system": "http://open.epic.com/FHIR/StructureDefinition/condition-category",
          "code": "external-encounter-diagnosis",
          "display": "External Encounter Diagnosis"
        }
      ],
      "text": "External Encounter Diagnosis"
    }
  ],
  "code": {
    "coding": [
      {
        "system": "http://hl7.org/fhir/sid/icd-10-cm",
        "code": "E10.9",
        "display": "Type 1 diabetes mellitus without complications."
      }
    ],
```

```
    "text": "Type 1 diabetes mellitus without complications."
  },
  "subject": {
    "reference": "Patient/eJQmQ1wDd.IYXOq-L5gxQ0g3",
    "display": "Patient, Test"
  },
  "onsetDateTime": "2020-02-28T06:00:00Z",
  "abatementDateTime": "2020-03-30T05:00:00Z",
  "recordedDate": "2020-02-28T06:00:00Z"
}
```


14.1.14 Condition.Read (Outside Record Health Concern) (R4)

File: site/apis/14-CMS-Incoming/1-R4/11371-Condition-Read-Outside-Record-Health-Concern-R4.html
Epic API ID | 11371
FHIR version | R4
Categories | CMS Incoming
API type | USCDI
A la carte | Industry-Standard Level 1 API
USCDI | Yes
Available in inpatient and other contexts | Yes
HTTP method | GET
URL template | /api/FHIR/R4/Condition/{ID}
Supports OAuth 2.0 | True
Supported user types | Backend Systems and Non-OAuth 2.0, Clinicians or Administrative Users, Patients
Performs scope validation | False
Source | https://fhir.epic.com/Specifications?api=11371

Description

Use this API to retrieve a specific instance of a Social Drivers of Health (SDOH) concern derived from a screening assessment. The Condition (Outside Record Health Concern) resources do not represent a patient's diagnoses or problem list items over time and might not represent a condition officially diagnosed by a physician. These resources represent a high or medium concern determined at the time an SDOH assessment was performed. They do not have onset or abatement dates, and they are always documented as active. They should not be used without the assessments they are associated with.

For the associated SDOH assessments, see

Observation.Read (Outside Record Screening Assessment) (R4)

and

Observation.Search (Outside Record Screening Assessment) (R4)

The data returned by this API includes SDOH concerns automatically derived from screening assessments. This API does not return health concerns reviewed or directly documented by a provider.

This API differs from

Condition.Read (Health Concerns) (R4)

because it returns data that was obtained as part of payer data exchange workflows rather than directly recorded during patient care. This data can come from payers, providers, or loaded from other FHIR servers. Because this data doesn't originate from the organization being queried, users of this API should be aware that the data might be unverified, incomplete, or duplicative.

Data from outside payer and provider systems is saved to an organization's database and returned in a standard format, documented below. Data loaded from other FHIR servers is returned in the format the organization received it. Because of this, the documentation below does not apply to these loaded resources. These resources can include any elements from the FHIR specification and can be distinguished from other resources by the presence of meta.tag set to "external-bulk-data".

Request parameters

Name | Type | Optional | Array | Cardinality | Description
ID | token | Required | | | The FHIR ID for a Condition (Outside Record Health Concern) resource.

Response elements

Name | Type | Optional | Array | Cardinality | Description
Condition (R4) | Condition | | | | An instance of the R4 Condition resource.
Condition (R4).category | CodeableConcept | | Yes | 3..3 | Categories identifying the type of Condition documented. Always contains the category codes "health-concern", "external-health-concern", and "sdoh".
Condition (R4).clinicalStatus | CodeableConcept | | | 1..1 | The Condition's clinical status. For Condition (Outside Record Health Concern) resources, this is always "active", because the resource represents the condition at the time of an SDOH assessment, and the resource is only created if a concern is present.
Condition (R4).code | CodeableConcept | | | 1..1 | ICD-10 Z-Codes representing the health concern associated with a particular SDOH assessment. If an SDOH domain does not correspond to a particular generalized Z-Code, but a concern is still present, this has a dataAbsentReason instead of a code.

Condition (R4).evidence | BackboneElement | | Yes | 1..1 | The Observation (Outside Record Screening Assessment) resource the health concern was derived from. This is always present and always references an SDOH assessment.

Condition (R4).evidence.detail | Reference | | Yes | 1..1 | Reference to the Observation (Outside Record Screening Assessment) resource the health concern was derived from. This is always present and always references an SDOH assessment.

Condition (R4).extension (condition-asserted-date) (also: extension (condition-asserted-date)) | Extension | | Yes | 0..1 | Date the health concern was first asserted. URL: http://hl7.org/fhir/StructureDefinition/condition-assertedDate

Condition (R4).id | id | | | 1..1 | Unique FHIR ID for the Condition resource.

Condition (R4).meta | Meta | | | | Metadata about the resource, including information about the origin or source of the data.

Condition (R4).meta.tag | Coding | | Yes | | Set to external-bulk-data for resources originally loaded from another FHIR server. If this element is set to external-bulk-data, all other element-level documentation does not apply to the resource. The resource content might vary and can include any elements allowed by the FHIR specification.

Condition (R4).recordedDate | dateTime | | | 1..1 | The date on which the source assessment that the health concern is derived from took place.

Condition (R4).severity | CodeableConcept | | | 1..1 | The severity of the concern. This is the SNOMEDCT code "24484000" (severe) for a high concern level and "6736007" (moderate) for a medium concern level. A low concern does not produce a Condition (Outside Record Health Concern) resource.

Condition (R4).subject | Reference | | | 1..1 | A reference to the Patient FHIR resource associated with the Health Concern.

Condition (R4).verificationStatus | CodeableConcept | | | 1..1 | The verification status of the condition. This is always a status of "confirmed".

Sample request

```
GET https://hostname/instance/api/FHIR/R4/Condition/f3ahRZt3g-QTdb0S9ITGAsz3aMYBF44U25FFAQlTdvJo4
```

Sample response


```
{
  "resourceType": "Condition",
  "id": "f3ahRZt3g-QTdb0S9ITGAsz3aMYBF44U25FFAQlTdvJo4",
  "clinicalStatus": {
    "coding": [
      {
        "system": "http://terminology.hl7.org/CodeSystem/condition-clinical",
        "version": "4.0.0",
        "code": "active",
        "display": "Active"
      }
    ],
    "text": "Active"
  },
  "verificationStatus": {
    "coding": [
      {
        "system": "http://terminology.hl7.org/CodeSystem/condition-ver-status",
        "version": "4.0.0",
        "code": "confirmed",
        "display": "Confirmed"
      }
    ],
    "text": "Confirmed"
  },
  "category": [
    {
      "coding": [
        {
          "system": "http://hl7.org/fhir/us/core/CodeSystem/condition-category",
          "code": "health-concern",
          "display": "Health Concern"
        }
      ],
      "text": "Health Concern"
    },
    {
      "coding": [
        {
          "system": "http://open.epic.com/FHIR/StructureDefinition/condition-category",
          "code": "external-health-concern",
          "display": "External Health Concern"
        }
      ],
      "text": "External Health Concern"
    },
    {
      "coding": [
        {
          "system": "http://hl7.org/fhir/us/core/CodeSystem/us-core-category",
          "code": "sdoh",
          "display": "sdoh"
        }
      ],
      "text": "sdoh"
    }
  ],
  "severity": {
    "coding": [
      {
        "system": "http://snomed.info/sct",
```

```
        "code": "24484000",
        "display": "Severe"
      }
    ],
    "text": "Severe"
  },
  "code": {
    "coding": [
      {
        "system": "http://hl7.org/fhir/sid/icd-10-cm",
        "code": "Z91.89",
        "display": "At risk for postpartum depression"
      }
    ],
    "text": "At risk for postpartum depression"
  },
  "subject": {
    "reference": "Patient/eHbAXIMc5gSWa6JczktbLLQ3",
    "display": "Fhir, Test Patient"
  },
  "recordedDate": "2025-08-13",
  "evidence": [
    {
      "detail": [
        {
          "reference": "Observation/fIFuCN0sujsCEjxJW6kngvn8uAhKKqVvMhqcs33oWG4w4",
          "display": "Edinburgh Postnatal Depression Scale"
        }
      ]
    }
  ]
}
```


14.1.15 Condition.Read (Outside Record Problems) (R4)

File: site/apis/14-CMS-Incoming/1-R4/11374-Condition-Read-Outside-Record-Problems-R4.html
Epic API ID | 11374
FHIR version | R4
Categories | CMS Incoming
API type | USCDI
A la carte | Industry-Standard Level 1 API
USCDI | Yes
Available in inpatient and other contexts | Yes
HTTP method | GET
URL template | /api/FHIR/R4/Condition/{ID}
Supports OAuth 2.0 | True
Supported user types | Backend Systems and Non-OAuth 2.0, Clinicians or Administrative Users, Patients
Performs scope validation | False
Source | https://fhir.epic.com/Specifications?api=11374

Description

Use this API to retrieve a specific instance of a patient's problems.

A problem is an item on the problem list that can be managed over time.

Problems are distinct from health concerns, which are additional concerns from other stakeholders. For Conditions that pertain to health concerns, see

Condition.Read (Outside Record Health Concern) (R4)

This API differs from other Condition Problems APIs because it returns data obtained as part of payer data exchange workflows rather than directly recorded during patient care. This data can come from payers, providers, or loaded from other FHIR servers. Because this data doesn't originate from the organization being queried, users of this API should be aware that the data might be unverified, incomplete, or duplicative.

Data from outside payer and provider systems is saved to an organization's database and returned in a standard format, documented below. Data loaded from other FHIR servers is returned in the format the organization received it. Because of this, the documentation below does not apply to these loaded resources. These resources can include any elements from the FHIR specification and can be distinguished from other resources by the presence of meta.tag set to “external-bulk-data".

Request parameters

Name | Type | Optional | Array | Cardinality | Description
ID | token | Required | | | A Condition FHIR ID.

Response elements

Name | Type | Optional | Array | Cardinality | Description
Condition (R4) | Condition | | | | An instance of the R4 Condition resource.
Condition (R4).abatementDateTime | dateTime | | | 0..1 | If a Condition has a resolved date, it appears here.

Condition (R4).category | CodeableConcept | | Yes | 2..2 | Always includes category codes "problem-list-item" and "external-problem-list-item".

Condition (R4).clinicalStatus | CodeableConcept | | | 1..1 | The current calculated status of the problem. This can be active or inactive.

Condition (R4).code | CodeableConcept | | | 1..1 | External codings for the Condition. If a list of codes is sent, they're listed in this element. Otherwise, this element uses the problem name from the name element.

Condition (R4).extension (assertedDateTime) (also: extension (assertedDateTime)) | Extension | | Yes | 0..1 | Date the Condition was first asserted URL: http://hl7.org/fhir/StructureDefinition/condition-assertedDate

Condition (R4).id | id | Required | | 1..1 | The Condition FHIR ID.

Condition (R4).meta | Meta | | | 0..1 | Metadata about the resource, including information about the origin or source of the data.

Condition (R4).meta.tag | Coding | | Yes | 0..* | Set to external-bulk-data for resources originally loaded from another FHIR server. If this element is set to external-bulk-data, all other element-level documentation does not apply to the resource. The resource content might vary and can include any elements allowed by the FHIR specification.

Condition (R4).note | Annotation | | Yes | 0..* | Additional free text information about the problem.

Condition (R4).note.text | String | | | 1..1 | A single free text comment about the problem.

Condition (R4).onsetDateTime | dateTime | | | 0..1 | If a Condition has a noted date, it appears here.

Condition (R4).recordedDate | dateTime | | | 0..1 | The date the Condition was recorded.

Condition (R4).subject | Reference | | | 1..1 | The Patient associated with the Condition.

Condition (R4).verificationStatus | CodeableConcept | | | 1..1 | Always includes verification status "confirmed".

Sample request

```
GET https://hostname/instance/api/FHIR/R4/Condition/fQ1PjSrOd85UZL81pV8szP3pZe4oc9BzRtT7tMXkO0R441
```

Sample response


```
{
  "resourceType": "Condition",
  "id": "fQ1PjSrOd85UZL81pV8szP3pZe4oc9BzRtT7tMXkO0R441",
  "clinicalStatus": {
    "coding": [
      {
        "system": "http://terminology.hl7.org/CodeSystem/condition-clinical",
        "version": "4.0.0",
        "code": "active",
        "display": "Active"
      }
    ],
    "text": "Active"
  },
  "verificationStatus": {
    "coding": [
      {
        "system": "http://terminology.hl7.org/CodeSystem/condition-ver-status",
        "version": "4.0.0",
        "code": "confirmed",
        "display": "Confirmed"
      }
    ],
    "text": "Confirmed"
  },
  "category": [
    {
      "coding": [
        {
          "system": "http://terminology.hl7.org/CodeSystem/condition-category",
          "code": "problem-list-item",
          "display": "Problem List Item"
        }
      ],
      "text": "Problem List Item"
    },
    {
      "coding": [
        {
          "system": "http://open.epic.com/FHIR/StructureDefinition/condition-category",
          "code": "external-problem-list-item",
          "display": "External Problem List Item"
        }
      ],
      "text": "External Problem List Item"
    }
  ],
  "code": {
    "coding": [
      {
        "system": "http://snomed.info/sct",
        "code": "305058001",
        "display": "Health examination of defined subpopulation"
      },
      {
        "system": "http://hl7.org/fhir/sid/icd-10-cm",
        "code": "Z02.89",
        "display": "Health examination of defined subpopulation"
      },
      {
        "system": "http://hl7.org/fhir/sid/icd-9-cm",
```

```
        "code": "V70.5",
        "display": "Health examination of defined subpopulation"
      },
      {
        "system": "urn:oid:2.16.840.1.113883.3.247.1.1",
        "code": "80810",
        "display": "Health examination of defined subpopulation"
      }
    ],
    "text": "Health examination of defined subpopulation"
  },
  "subject": {
    "reference": "Patient/eabcdecd1hijklmnop88883",
    "display": "FHIR, Test Patient"
  },
  "onsetDateTime": "2025-07-01",
  "abatementDateTime": "2025-07-16",
  "recordedDate": "2025-07-01",
  "note": [
    {
      "text": "Routine health exam ordered per employer requirement. Patient reports no acute complaints. Vitals within
    normal limits. Screening labs ordered."
    },
    {
      "text": "Lab results reviewed. All values within normal range. Exam findings unremarkable. Patient counseled on
    preventive care. Cleared for occupational clearance."
    }
  ]
}
```


14.1.16 Condition.Search (Outside Record Encounter Diagnosis) (R4)

File: site/apis/14-CMS-Incoming/1-R4/11389-Condition-Search-Outside-Record-Encounter-Diagnosis-R4.html
Epic API ID | 11389
FHIR version | R4
Categories | CMS Incoming
API type | USCDI
A la carte | Industry-Standard Level 1 API
USCDI | Yes
Available in inpatient and other contexts | Yes
HTTP method | GET
URL template | /api/FHIR/R4/Condition?abatement-date={abatement-date}&category={category}&clinical-status={clinical-status}&code={code}&encounter={encounter}&onset-date={onset-date}&patient={patient}&recorded-date={recorded-date}&subject={subject}&_count={_count}&_id={_id}&_include={_include}&_revinclude={_revinclude}
Supports OAuth 2.0 | True
Supported user types | Backend Systems and Non-OAuth 2.0, Clinicians or Administrative Users, Patients
Performs scope validation | False
Source | https://fhir.epic.com/Specifications?api=11389

Description

Use this API to search for a patient's encounter diagnoses. This resource returns a

point in time diagnosis (for example from a physician or nurse) in context of an encounter.

The data returned by this API includes the minimal set of data to record, search, and fetch information about an encounter diagnosis. This API does not return Problems and Health Concerns.

This API differs from other

Condition.Search (Encounter Diagnosis) (R4)

APIs because it returns data obtained as part of payer data exchange workflows rather than directly recorded during patient care. This data can come from payers, providers, or loaded from other FHIR servers. Because this data doesn't originate from the organization being queried, users of this API should be aware that the data might be unverified, incomplete, or duplicative.

Data from outside payer and provider systems is saved to an organization's database and returned in a standard format, documented below. Data loaded from other FHIR servers is returned in the format the organization received it. Because of this, the documentation below does not apply to these loaded resources. These resources can include any elements from the FHIR specification and can be distinguished from other resources by the presence of meta.tag set to “external-bulk-data".

Request parameters

Name | Type | Optional | Array | Cardinality | Description
_count | number | Optional | Yes | | Number of results per page.
_id | token | Optional | Yes | | FHIR resource IDs for the desired resources. Can be used in combination with _count, _include, and _revInclude. All others are ignored.
_include | string | Optional | Yes | | Used to indicate which referenced resources to include in the search bundle.
_revinclude | string | Optional | Yes | | Used to include Provenance or AuditEvent resources that refer to search results, when available.
category | token | Optional | Yes | 0..* | Either "encounter-diagnosis" or "external-encounter-diagnosis" for this API.
onset-date | date | Optional | Yes | 0..* | The Condition's noted date.

patient | reference | Conditional | Yes | 1..* | Reference to a patient resource the Condition is for. Either a patient or subject parameter must be provided. If both are provided, they must match exactly.
subject | reference | Conditional | Yes | 0..* | Reference to a patient resource the Condition is for. Either a patient or subject parameter must be provided. If both are provided, they must match exactly.

Request parameters (post-filtered search parameters)

Name | Type | Optional | Array | Cardinality | Description
abatement-date | date | Optional | Yes | | A Condition's resolved date.
clinical-status | token | Optional | Yes | | The clinical status, which can be active, resolved, or inactive.
code | token | Optional | Yes | | External coding for the Condition.
recorded-date | date | Optional | Yes | | The date that the encounter diagnosis was first recorded.
verification-status | token | Optional | Yes | | This value is "confirmed".

Response elements

Name | Type | Optional | Array | Cardinality | Description
Condition (R4) | Condition | | | | An instance of the R4 Condition resource.
Condition (R4).abatementDateTime | dateTime | Required | | 0..1 | If a Condition has a resolved date, it appears here.
Condition (R4).category | CodeableConcept | Required | Yes | 1..* | Always includes category codes "encounter-diagnosis" and "external-encounter-diagnosis" .
Condition (R4).clinicalStatus | CodeableConcept | Required | | 0..1 | The clinical status, which can be active, resolved, or inactive.
Condition (R4).code | CodeableConcept | Required | | 1..1 | Sends a list of external codes for the Condition. If there are no available Condition codes, then the name of the Condition is used instead.
Condition (R4).encounter | Reference | Required | | 0..1 | Reference to the Encounter associated with this Condition.
Condition (R4).id | id | Required | | 1..1 | The condition FHIR ID.
Condition (R4).meta | Meta | | | | Metadata about the resource, including information about the origin or source of the data.
Condition (R4).meta.tag | Coding | | Yes | | Set to external-bulk-data for resources originally loaded from another FHIR server. If this element is set to external-bulk-data, all other element-level documentation does not apply to the resource. The resource content might vary and can include any elements allowed by the FHIR specification.
Condition (R4).onsetDateTime | dateTime | Required | | 0..1 | If a Condition has a noted date, it appears here.
Condition (R4).recordedDate (also: recordedDate) | dateTime | Required | | 0..1 | The date that the encounter diagnosis was first recorded.
Condition (R4).subject | Reference | Required | | 1..1 | The patient associated with the Condition.
Condition (R4).verificationStatus | CodeableConcept | Required | | 0..1 | This value is "confirmed".

Sample request

```
GET https://hostname/instance/api/FHIR/R4/Condition?patient=eJQmQ1wDd.IYXOq-L5gxQ0g3&category=external-encounter-
    diagnosis
```

Sample response


```
{
  "resourceType": "Bundle",
  "type": "searchset",
  "total": 1,
  "link": [
    {
      "relation": "self",
      "url": "https://hostname/instance/api/FHIR/R4/Condition?category=external-encounter-
    diagnosis&patient=eJQmQ1wDd.IYXOq-L5gxQ0g3"
    }
  ],
  "entry": [
    {
      "link": [
        {
          "relation": "self",
          "url": "https://hostname/instance/api/FHIR/R4/Condition/fe88ccso9-GMUtNcY1.b0Nnp6BVrDTeGe58Sh.XjWk8w4"
        }
      ],
      "fullUrl": "https://hostname/instance/api/FHIR/R4/Condition/fe88ccso9-GMUtNcY1.b0Nnp6BVrDTeGe58Sh.XjWk8w4",
      "resource": {
        "resourceType": "Condition",
        "id": "fe88ccso9-GMUtNcY1.b0Nnp6BVrDTeGe58Sh.XjWk8w4",
        "extension": [
          {
            "valueDateTime": "02/28/2020 12:00 AM",
            "url": "http://hl7.org/fhir/StructureDefinition/condition-assertedDate"
          }
        ],
        "verificationStatus": {
          "coding": [
            {
              "system": "http://terminology.hl7.org/CodeSystem/condition-ver-status",
              "version": "4.0.0",
              "code": "confirmed",
              "display": "Confirmed"
            }
          ],
          "text": "Confirmed"
        },
```

```
        "category": [
          {
            "coding": [
              {
                "system": "http://terminology.hl7.org/CodeSystem/condition-category",
                "code": "encounter-diagnosis",
                "display": "Encounter Diagnosis"
              }
            ],
            "text": "Encounter Diagnosis"
          },
          {
            "coding": [
              {
                "system": "http://open.epic.com/FHIR/StructureDefinition/condition-category",
                "code": "external-encounter-diagnosis",
                "display": "External Encounter Diagnosis"
              }
            ],
            "text": "External Encounter Diagnosis"
          }
        ],
        "code": {
          "coding": [
            {
              "system": "http://hl7.org/fhir/sid/icd-10-cm",
              "code": "E10.9",
              "display": "Type 1 diabetes mellitus without complications."
            }
          ],
          "text": "Type 1 diabetes mellitus without complications."
        },
        "subject": {
          "reference": "Patient/eJQmQ1wDd.IYXOq-L5gxQ0g3",
          "display": "FHIR, Test Patient"
        },
        "onsetDateTime": "2020-02-28T06:00:00Z",
        "abatementDateTime": "2020-03-30T05:00:00Z",
        "recordedDate": "2020-02-28T06:00:00Z"
      },
      "search": {
        "mode": "match"
      }
    }
  ]
}
```


14.1.17 Condition.Search (Outside Record Health Concern) (R4)

File: site/apis/14-CMS-Incoming/1-R4/11376-Condition-Search-Outside-Record-Health-Concern-R4.html
Epic API ID | 11376
FHIR version | R4
Categories | CMS Incoming
API type | USCDI
A la carte | Industry-Standard Level 1 API
USCDI | Yes
Available in inpatient and other contexts | Yes
HTTP method | GET
URL template | /api/FHIR/R4/Condition?abatement-date={abatement-date}&category={category}&clinical-status={clinical-status}&code={code}&encounter={encounter}&onset-date={onset-date}&patient={patient}&recorded-date={recorded-date}&subject={subject}&_count={_count}&_id={_id}&_include={_include}&_revinclude={_revinclude}
Supports OAuth 2.0 | True
Supported user types | Backend Systems and Non-OAuth 2.0, Clinicians or Administrative Users, Patients
Performs scope validation | False
Source | https://fhir.epic.com/Specifications?api=11376

Description

Use this API to search for Social Drivers of Health (SDOH) concerns derived from screening assessments. The Condition (Outside Record Health Concern) resources do not represent a patient's diagnoses or problem list items over time and might not represent a condition officially diagnosed by a physician. These resources represent a high or medium concern determined at the time an SDOH assessment was performed. They do not have onset or abatement dates, and they are always documented as active. They should not be used without the assessments they are associated with.

For the associated SDOH assessments, see

Observation.Read (Outside Record Screening Assessment) (R4)

and

Observation.Search (Outside Record Screening Assessment) (R4)

The data returned by this API includes SDOH concerns automatically derived from screening assessments. This API does not return health concerns reviewed or directly documented by a provider.

This API differs from

Condition.Search (Health Concerns) (R4)

because it returns data that was obtained as part of payer data exchange workflows rather than directly recorded during patient care. This data can come from payers, providers, or loaded from other FHIR servers. Because this data doesn't originate from the organization being queried, users of this API should be aware that the data might be unverified, incomplete, or duplicative.

Data from outside payer and provider systems is saved to an organization's database and returned in a standard format, documented below. Data loaded from other FHIR servers is returned in the format the organization received it. Because of this, the documentation below does not apply to these loaded resources. These resources can include any elements from the FHIR specification and can be distinguished from other resources by the presence of meta.tag set to "external-bulk-data".

Request parameters

Name | Type | Optional | Array | Cardinality | Description

_count | number | Optional | Yes | | Number of results per page.

_id | token | Optional | Yes | | FHIR resource IDs for the desired resources. Can be used in combination with _count, _include, and _revInclude. All others are ignored.

_include | string | Optional | Yes | | Used to indicate which referenced resources to include in the search bundle.

_revinclude | string | Optional | Yes | | Used to include Provenance or AuditEvent resources that refer to search results, when available.

category | token | Optional | Yes | | All of the health-concern, external-health-concern, and sdoh category codes are present on all available Condition (Outside Record Health Concern) resources.

patient | reference | Conditional | Yes | | Reference to a Patient resource the Condition is for. Either a patient or subject parameter must be provided. If both are provided, they must match exactly.

recorded-date | date | Optional | Yes | | The date the associated SDOH screening assessment took place.

subject | reference | Conditional | Yes | | Reference to a Patient resource the Condition is for. Either a patient or subject parameter must be provided. If both are provided, they must match exactly.

Request parameters (post-filtered search parameters)

Name | Type | Optional | Array | Cardinality | Description

clinical-status | token | Optional | Yes | | The clinical status of the health concern. This is always "active" for Condition (Outside Record Health Concern) resources.

code | token | Optional | Yes | | The code that identifies the specific type of health concern. Only ICD-10 Z-codes are supported. These codes are calculated based on the SDOH domains and concern level from the Health Concern's associated Screening Assessment.

evidence | token | Optional | Yes | | The Observation (Outside Record Screening Assessment) resource a Health Concern was derived from.

evidence-detail | reference | Optional | Yes | | The Observation (Outside Record Screening Assessment) resource a health concern was derived from.

verification-status | token | Optional | Yes | | The verification status of the health concern. For this API, all Conditions have a verificationStatus of "confirmed"

Response elements

Name | Type | Optional | Array | Cardinality | Description

Condition (R4) | Condition | | | | An instance of the R4 Condition resource.

Condition (R4).category | CodeableConcept | | Yes | 3..3 | Categories identifying the type of Condition documented. Always contains the category codes "health-concern", "external-health-concern", and "sdoh".

Condition (R4).clinicalStatus | CodeableConcept | | | 1..1 | The Condition's clinical status. For Condition (Outside Record Health Concern) resources, this is always "active", because the resource represents the condition at the time of an SDOH assessment, and the resource is only created if a concern is present.

Condition (R4).code | CodeableConcept | | | 1..1 | ICD-10 Z-Codes representing the health concern associated with a particular SDOH assessment. If an SDOH domain does not correspond to a particular generalized Z-Code, but a concern is still present, this has a dataAbsentReason instead of a code.

Condition (R4).evidence | BackboneElement | | Yes | 1..1 | The Observation (Outside Record Screening Assessment) resource the health concern was derived from. This is always present and always references an SDOH assessment.

Condition (R4).evidence.detail | Reference | | Yes | 1..1 | Reference to the Observation (Outside Record Screening Assessment) resource the health concern was derived from. This is always present and always references an SDOH assessment.

Condition (R4).extension (condition-asserted-date) (also: extension (condition-asserted-date)) | Extension | | Yes | 0..1 | Date the health concern was first asserted. URL: http://hl7.org/fhir/StructureDefinition/condition-assertedDate

Condition (R4).id | id | | | 1..1 | Unique FHIR ID for the Condition resource.

Condition (R4).meta | Meta | | | | Metadata about the resource, including information about the origin or source of the data.

Condition (R4).meta.tag | Coding | | Yes | | Set to external-bulk-data for resources originally loaded from another FHIR server. If this element is set to external-bulk-data, all other element-level documentation does not apply to the resource. The resource content might vary and can include any elements allowed by the FHIR specification.

Condition (R4).recordedDate | dateTime | | | 1..1 | The date on which the source assessment that the health concern is derived from took place.

Condition (R4).severity | CodeableConcept | | | 1..1 | The severity of the concern. This is the SNOMEDCT code "24484000" (severe) for a high concern level and "6736007" (moderate) for a medium concern level. A low concern does not produce a Condition (Outside Record Health Concern) resource.

Condition (R4).subject | Reference | | | 1..1 | A reference to the Patient FHIR resource associated with the Health Concern.

Condition (R4).verificationStatus | CodeableConcept | | | 1..1 | The verification status of the condition. This is always a status of "confirmed".

Sample request

```
GET https://hostname/instance/api/FHIR/R4/Condition?patient=eHbAXIMc5gSWa6JczktbLLQ3&category=health-concern
```

Sample response


```
{
    "resourceType": "Bundle",
    "type": "searchset",
    "total": 1,
    "link": [
        {
            "relation": "self",
            "url": "https://hostname/instance/api/FHIR/R4/Condition?category=health-
    concern&patient=eHbAXIMc5gSWa6JczktbLLQ3"
        }
    ],
    "entry": [
        {
            "link": [
                {
                    "relation": "self",
                    "url":
    "https://hostname/instance/api/FHIR/R4/Condition/fRU9EX1jXpPfJ1zYSzrlkC.XEmH3gO7Um5hkgS6gN.a84"
                }
            ],
            "fullUrl": "https://hostname/instance/api/FHIR/R4/Condition/fRU9EX1jXpPfJ1zYSzrlkC.XEmH3gO7Um5hkgS6gN.a84",
            "resource": {
            "resourceType": "Condition",
            "id": "f3ahRZt3g-QTdb0S9ITGAsz3aMYBF44U25FFAQlTdvJo4",
            "clinicalStatus": {
                "coding": [
                    {
                        "system": "http://terminology.hl7.org/CodeSystem/condition-clinical",
                        "version": "4.0.0",
                        "code": "active",
                        "display": "Active"
                    }
                ],
                "text": "Active"
            },
            "verificationStatus": {
                "coding": [
                    {
                        "system": "http://terminology.hl7.org/CodeSystem/condition-ver-status",
                        "version": "4.0.0",
                        "code": "confirmed",
                        "display": "Confirmed"
                    }
                ],
                "text": "Confirmed"
            },
            "category": [
                {
                    "coding": [
                        {
                            "system": "http://hl7.org/fhir/us/core/CodeSystem/condition-category",
                            "code": "health-concern",
                            "display": "Health Concern"
                        }
                    ],
                    "text": "Health Concern"
                },
                {
                    "coding": [
                        {
                            "system": "http://open.epic.com/FHIR/StructureDefinition/condition-category",
                            "code": "external-health-concern",
                            "display": "External Health Concern"
                        }
                    ],
                    "text": "External Health Concern"
                },
                {
                    "coding": [
                        {
                            "system": "http://hl7.org/fhir/us/core/CodeSystem/us-core-category",
                            "code": "sdoh",
                            "display": "sdoh"
                        }
                    ],
                    "text": "sdoh"
                }
            ],
            "severity": {
                "coding": [
                    {
                        "system": "http://snomed.info/sct",
                        "code": "24484000",
                        "display": "Severe"
                    }
                ],
                "text": "Severe"
```

```
        },
        "code": {
            "coding": [
                {
                    "system": "http://hl7.org/fhir/sid/icd-10-cm",
                    "code": "Z91.89",
                    "display": "At risk for postpartum depression"
                }
            ],
            "text": "At risk for postpartum depression"
        },
        "subject": {
            "reference": "Patient/eHbAXIMc5gSWa6JczktbLLQ3",
            "display": "Fhir, Test Patient"
        },
        "recordedDate": "2025-08-13",
        "evidence": [
            {
                "detail": [
                    {
                        "reference": "Observation/fIFuCN0sujsCEjxJW6kngvn8uAhKKqVvMhqcs33oWG4w4",
                        "display": "Edinburgh Postnatal Depression Scale"
                    }
                ]
            }
        ]
        },
        "search": {
            "mode": "match"
        }
    },
```


14.1.18 Condition.Search (Outside Record Problems) (R4)

File: site/apis/14-CMS-Incoming/1-R4/11377-Condition-Search-Outside-Record-Problems-R4.html
Epic API ID | 11377
FHIR version | R4
Categories | CMS Incoming
API type | USCDI
A la carte | Industry-Standard Level 1 API
USCDI | Yes
Available in inpatient and other contexts | Yes
HTTP method | GET
URL template | /api/FHIR/R4/Condition?abatement-date={abatement-date}&category={category}&clinical-status={clinical-status}&code={code}&encounter={encounter}&onset-date={onset-date}&patient={patient}&recorded-date={recorded-date}&subject={subject}&_count={_count}&_id={_id}&_include={_include}&_revinclude={_revinclude}
Supports OAuth 2.0 | True
Supported user types | Backend Systems and Non-OAuth 2.0, Clinicians or Administrative Users, Patients
Performs scope validation | False
Source | https://fhir.epic.com/Specifications?api=11377

Description

Use this API to search for a patient's problems. A problem is an item on the problem list that can be managed over time.

Problems are distinct from health concerns, which are additional concerns from other stakeholders. For Conditions that pertain to health concerns, see

Condition.Search (Outside Record Health Concern) (R4)

This API differs from other <resource type> APIs because it returns data obtained as part of payer data exchange workflows rather than directly recorded during patient care. This data can come from payers, providers, or loaded from other FHIR servers. Because this data doesn't originate from the organization being queried, users of this API should be aware that the data might be unverified, incomplete, or duplicative.

Data from outside payer and provider systems is saved to an organization's database and returned in a standard format, documented below. Data loaded from other FHIR servers is returned in the format the organization received it. Because of this, the documentation below does not apply to these loaded resources. These resources can include any elements from the FHIR specification and can be distinguished from other resources by the presence of meta.tag set to “external-bulk-data".

Request parameters

Name | Type | Optional | Array | Cardinality | Description
_count | number | Optional | Yes | | Number of results per page.
_id | token | Optional | Yes | | FHIR resource IDs for the desired resources. Can be used in combination with _count, _include, and _revInclude. All others are ignored.
_include | string | Optional | Yes | | Used to indicate which referenced resources to include in the search bundle.
_revinclude | string | Optional | Yes | | Used to include Provenance or AuditEvent resources that refer to search results, when available.
category | token | Optional | Yes | | The category associated with the Condition. Use "problem-list-item" or "external-problem-list-item" for this API.
patient | reference | Conditional | Yes | 1..* | The FHIR ID of the Patient. Either a patient or subject parameter must be provided. If both are provided, they must match exactly.

subject | reference | Conditional | Yes | 1..* | The FHIR ID of the Patient. Either a patient or subject parameter must be provided. If both are provided, they must match exactly.

Request parameters (post-filtered search parameters)

Name | Type | Optional | Array | Cardinality | Description
abatement-date | date | Optional | Yes | | The date the problem went into resolution or remission.
clinical-status | token | Optional | Yes | | The current status of the problem.
code | token | Optional | Yes | | Code that identifies the problem.
onset-date | date | Optional | Yes | | Estimated or actual date or date-time of problem.
recorded-date | date | Optional | Yes | | Date the problem was first recorded.

Response elements

Name | Type | Optional | Array | Cardinality | Description
Condition (R4) | Condition | | | | An instance of the R4 Condition resource.
Condition (R4).abatementDateTime | dateTime | | | 0..1 | If a Condition has a resolved date, it appears here.
Condition (R4).category | CodeableConcept | | Yes | 2..2 | Always includes category codes "problem-list-item" and "external-problem-list-item".
Condition (R4).clinicalStatus | CodeableConcept | | | 1..1 | The current calculated status of the problem. This can be active or inactive.
Condition (R4).code | CodeableConcept | | | 1..1 | External codings for the Condition. If a list of codes is sent, they're listed in this element. Otherwise, this element uses the problem name from the name element.
Condition (R4).extension (assertedDateTime) (also: extension (assertedDateTime)) | Extension | | Yes | 0..1 | Date the Condition was first asserted
URL: http://hl7.org/fhir/StructureDefinition/condition-assertedDate
Condition (R4).id | id | Required | | 1..1 | The Condition FHIR ID.
Condition (R4).meta | Meta | | | 0..1 | Metadata about the resource, including information about the origin or source of the data.
Condition (R4).meta.tag | Coding | | Yes | 0..* | Set to external-bulk-data for resources originally loaded from another FHIR server. If this element is set to external-bulk-data, all other element-level documentation does not apply to the resource. The resource content might vary and can include any elements allowed by the FHIR specification.
Condition (R4).note | Annotation | | Yes | 0..* | Additional free text information about the problem.
Condition (R4).note.text | String | | | 1..1 | A single free text comment about the problem.
Condition (R4).onsetDateTime | dateTime | | | 0..1 | If a Condition has a noted date, it appears here.
Condition (R4).recordedDate | dateTime | | | 0..1 | The date the Condition was recorded.
Condition (R4).subject | Reference | | | 1..1 | The Patient associated with the Condition.
Condition (R4).verificationStatus | CodeableConcept | | | 1..1 | Always includes verification status "confirmed".

Sample request

```
GET https://hostname/instance/api/FHIR/R4/Condition?patient=eabcdecd1hijklmnop88883&category=external-problem-list-item
```

Sample response


```
{
  "resourceType": "Bundle",
  "type": "searchset",
  "total": 1,
  "link": [
    {
      "relation": "self",
      "url": "https://hostname/instance/api/FHIR/R4/Condition?subject=eabcdecd1hijklmnop88883"
    }
  ],
  "entry": [
    {
      "link": [
        {
          "relation": "self",
          "url": "https://hostname/instance/api/FHIR/R4/Condition/fQ1PjSrOd85UZL81pV8szP3pZe4oc9BzRtT7tMXkO0R44"
        }
      ],
      "fullUrl": "https://hostname/instance/api/FHIR/R4/Condition/fQ1PjSrOd85UZL81pV8szP3pZe4oc9BzRtT7tMXkO0R44",
      "resource": {
        "resourceType": "Condition",
        "id": "fQ1PjSrOd85UZL81pV8szP3pZe4oc9BzRtT7tMXkO0R44",
        "extension": [
          {
            "valueDateTime": "2023-01-31",
            "url": "http://hl7.org/fhir/StructureDefinition/condition-assertedDate"
          }
        ],
        "clinicalStatus": {
          "coding": [
            {
              "system": "http://terminology.hl7.org/CodeSystem/condition-clinical",
              "version": "4.0.0",
              "code": "active",
              "display": "Active"
            }
          ],
          "text": "Active"
        },
        "verificationStatus": {
          "coding": [
```

```
            {
              "system": "http://terminology.hl7.org/CodeSystem/condition-ver-status",
              "version": "4.0.0",
              "code": "confirmed",
              "display": "Confirmed"
            }
          ],
          "text": "Confirmed"
        },
        "category": [
          {
            "coding": [
              {
                "system": "http://terminology.hl7.org/CodeSystem/condition-category",
                "code": "problem-list-item",
                "display": "Problem List Item"
              }
            ],
            "text": "Problem List Item"
          },
          {
            "coding": [
              {
                "system": "http://terminology.hl7.org/CodeSystem/condition-category",
                "code": "external-problem-list-item",
                "display": "External Problem List Item"
              }
            ],
            "text": "External Problem List Item"
          }
        ],
        "code": {
          "coding": [
            {
              "system": "http://snomed.info/sct",
              "code": "79974007",
              "display": "Cat scratch fever"
            },
            {
              "system": "http://hl7.org/fhir/sid/icd-10-cm",
              "code": "A28.1",
              "display": "Cat scratch fever"
            }
          ],
          "text": "Cat Scratch Fever"
        },
        "subject": {
          "reference": "Patient/eabcdecd1hijklmnop88883",
          "display": "FHIR, Test Patient"
        },
        "onsetDateTime": "2024-05-27",
        "abatementDateTime": "2025-07-16",
        "recordedDate": "2025-07-01",
        "note": [
          {
            "text": "Patient presents with lymphadenopathy and low-grade fever following a cat scratch 10 days ago.
    Bartonella infection suspected. Starting doxycycline 100mg BID x 14 days."
          },
          {
            "text": "Follow-up: lymph node swelling notably reduced. Patient tolerated antibiotic course well. No new
    symptoms. Condition improving; will continue to monitor at next scheduled visit."
          }
        ]
      },
      "search": {
        "mode": "match"
      }
    }
  ]
}
```


14.1.19 Coverage Requirements Discovery (R4)

File: site/apis/14-CMS-Incoming/1-R4/11288-Coverage-Requirements-Discovery-R4.html
Epic API ID | 11288
FHIR version | R4
Categories | CMS Incoming
API type | Industry-Standard
USCDI | No
URL template | /api/FHIR
Supports OAuth 2.0 | True
Supported user types | Backend Systems and Non-OAuth 2.0
Performs scope validation | False
Source | https://fhir.epic.com/Specifications?api=11288

Description

This web service is available as part of Epic's utilization management module for clients to integrate with Epic health plans and payers.

This web service is based on the

implementation guide published by the HL7® FHIR® Da Vinci Project for Coverage Requirements Discovery (STU 2.1)

, acting as a payer-side CRD server. The purpose of CRD is to communicate coverage information about a requested service for a covered member, including whether the service is a covered benefit, whether the service requires a prior authorization, and whether additional documentation is needed through the Documentation Templates and Rules web service (DTR).

Epic's CRD payer web service supports responding to requests by two mechanisms: directly by using authorization requirements created inside Epic's utilization management module; and by forwarding the CRD request to another system. This guide describes the requirements and invariants of Epic's implementation of CRD for its utilization management module. Coordinate with each payer you integrate with to understand any additional features or limitations of other CRD systems that might be involved in final responses over this web service.

At the time of writing, CRD is a constantly evolving specification and is still receiving corrections and enhancements, as is our server implementation, so this content will change over time.

Request parameters

Name | Type | Optional | Array | Cardinality | Description

Coverage Requirements Discovery - Request (R4) | $coveragerequirementsdiscovery - Request | Required | | 1..1 | A Coverage Requirements Discovery request.

Coverage Requirements Discovery - Request (R4).context | $context

Coverage Requirements Discovery - Request (R4).context.appointments | Bundle | Conditional | | 0..1 | A Bundle of Appointments being scheduled with the patient. This is required when the hook is "appointment-book", and ignored when the hook is "order-sign".

Coverage Requirements Discovery - Request (R4).context.appointments.entry | BackboneElement | | Yes | | An array of entries included in this bundle.

Coverage Requirements Discovery - Request (R4).context.appointments.entry.resource | ResourceContainer | | | | A container for a single FHIR resource.

Coverage Requirements Discovery - Request (R4).context.appointments.entry.resource.Appointment | Resource | | | | An appointment being scheduled with the patient.

Coverage Requirements Discovery - Request (R4).context.appointments.entry.resource.Appointment.basedOn | Reference | Required | Yes | 1..* | The services planned to be performed in this Appointment. As a deviation from the Da Vinci CRD implementation guide, this can be a reference to either a ServiceRequest or a MedicationRequest.

Coverage Requirements Discovery - Request (R4).context.appointments.entry.resource.Appointment.end | instant | | | 0..1 | The end instant of the appointment. Either the start and end elements should be populated, or the requestedPeriod.start and requestedPeriod.end elements should be populated.

Coverage Requirements Discovery - Request (R4).context.appointments.entry.resource.Appointment.participant | BackboneElement | | Yes | | Planned participants in the appointment.

Coverage Requirements Discovery - Request (R4).context.appointments.entry.resource.Appointment.participant.actor | Reference | | | | A reference to the actor participating in this appointment. Performing provider and location information can be conveyed using Practitioner, PractitionerRole, and Location references. A reference to a Patient indicates the patient that the appointment is being scheduled for. Other reference types are not supported. Requesting providers that are not also performing providers should not be included.

Coverage Requirements Discovery - Request (R4).context.appointments.entry.resource.Appointment.participant.status | code | Required | | 1..1 | The status of the appointment participant. When the status is "declined", the participant is skipped.

Coverage Requirements Discovery - Request (R4).context.appointments.entry.resource.Appointment.participant.type | CodeableConcept | | Yes | | The type of the appointment participant. If the type is "PPRF", "SPRF", or not specified, the taxonomy code that is specified in the PractitionerRole.specialty of the appointment.actor is used to determine the specialty used for network check.

Coverage Requirements Discovery - Request (R4).context.appointments.entry.resource.Appointment.requestedPeriod | Period | | Yes | 0..1 | The period the appointment is requested to take place within. Either the start and end elements should be populated, or the requestedPeriod.start and requestedPeriod.end elements should be populated.

Coverage Requirements Discovery - Request (R4).context.appointments.entry.resource.Appointment.start | instant | | | 0..1 | The start instant of the appointment. Either the start and end elements should be populated, or the requestedPeriod.start and requestedPeriod.end elements should be populated.

Coverage Requirements Discovery - Request (R4).context.appointments.entry.resource.Appointment.status | code | Required | | 1..1 | The status of the appointment. When the status is "cancelled" or "entered-in-error", the Appointment is skipped, and coverage guidance is not provided.

Coverage Requirements Discovery - Request (R4).context.draftOrders | Bundle | Conditional | | 0..1 | A Bundle of orders being signed for the patient. This is required when the hook is "order-sign", and ignored when the hook is "appointment-book".

Coverage Requirements Discovery - Request (R4).context.draftOrders.entry | BackboneElement | | Yes | | An array of entries included in this bundle.

Coverage Requirements Discovery - Request (R4).context.draftOrders.entry.resource | ResourceContainer | | | | A container for a single FHIR resource.

Coverage Requirements Discovery - Request (R4).context.draftOrders.entry.resource.MedicationRequest | MedicationRequest | | | | A medication being ordered for a patient. This is intended to be used for clinically administered medications and not prescriptions administered at home.

Coverage Requirements Discovery - Request (R4).context.draftOrders.entry.resource.MedicationRequest.authoredOn | dateTime | Required | | 1..1 | The date and time the order was authored.

Coverage Requirements Discovery - Request (R4).context.draftOrders.entry.resource.MedicationRequest.extension (crd-delegate-evaluate) (also: extension (crd-delegate-evaluate)) | Extension | Optional | Yes | 0..1 | This custom extension is sent when Epic forwards the CRD request to a delegated entity. The extension informs the delegate that only a portion of their CRD response will be used in the overall response to the provider. This extension is not sent if the delegate is responsible for the entire request. The valueString is "covered" when the delegate is responsible for determining if the service is a covered benefit. The valueString is "pa-needed" when the delegate is responsible for determining if the service requires authorization.

Coverage Requirements Discovery - Request (R4).context.draftOrders.entry.resource.MedicationRequest.extension (crd-delegate-evaluate).crd-delegate-evaluate:url (also: crd-delegate-evaluate:url) | uri | Required | | 1..1 | The URL

"https://open.epic.com/fhir/extensions/crd-delegate-evaluate".

Coverage Requirements Discovery - Request (R4).context.draftOrders.entry.resource.MedicationRequest.extension (crd-delegate-evaluate).crd-delegate-evaluate:valueString (also: crd-delegate-evaluate:valueString) | string | Required | | 1..1 | The valueString indicates the portion of the CRD request for which the delegate is responsible.

Coverage Requirements Discovery - Request (R4).context.draftOrders.entry.resource.MedicationRequest.id | id | Required | | 1..1 | The FHIR ID of the request. FHIR IDs are required for referencing.

Coverage Requirements Discovery - Request (R4).context.draftOrders.entry.resource.MedicationRequest.identifier | Identifier | Optional | Yes | 0..* | Identifiers for the order to echo in responses.

Coverage Requirements Discovery - Request (R4).context.draftOrders.entry.resource.MedicationRequest.insurance | Reference | Optional | Yes | 0..1 | A reference to the Coverage resource to use for guidance on this order.

Coverage Requirements Discovery - Request (R4).context.draftOrders.entry.resource.MedicationRequest.intent | code | Required | | 1..1 | The intent of the order.

Coverage Requirements Discovery - Request (R4).context.draftOrders.entry.resource.MedicationRequest.medicationCodeableConcept | CodeableConcept | Conditional | | 0..1 | Coded representation of the medication being ordered. Either medicationCodeableConcept or medicationReference must be present. Supported code systems: System URI CPT http://www.ama-assn.org/go/cpt CPT urn:oid:2.16.840.1.113883.6.12 SNOMED CT http://snomed.info/sct SNOMED CT urn:oid:2.16.840.1.113883.6.96 HCPCS https://www.cms.gov/Medicare/Coding/HCPCSReleaseCodeSets HCPCS urn:oid:2.16.840.1.113883.6.285 LOINC http://loinc.org LOINC urn:oid:2.16.840.1.113883.6.1 Work with payers you integrate with to understand the code systems for which they provide guidance. As an example, they might only define requirements for procedure codes in terms of CPT or HCPCS.

System | URI

CPT | http://www.ama-assn.org/go/cpt

CPT | urn:oid:2.16.840.1.113883.6.12

SNOMED CT | http://snomed.info/sct

SNOMED CT | urn:oid:2.16.840.1.113883.6.96

HCPCS | https://www.cms.gov/Medicare/Coding/HCPCSReleaseCodeSets

HCPCS | urn:oid:2.16.840.1.113883.6.285

LOINC | http://loinc.org

LOINC | urn:oid:2.16.840.1.113883.6.1

Coverage Requirements Discovery - Request (R4).context.draftOrders.entry.resource.MedicationRequest.medicationReference | Reference | Conditional | | 0..1 | A reference to the medication being requested. Either medicationCodeableConcept or medicationReference must be present.

Coverage Requirements Discovery - Request (R4).context.draftOrders.entry.resource.MedicationRequest.performer | Reference | Optional | | 0..1 | The provider who is planned to perform the service. Multiple performing providers are not supported.

Coverage Requirements Discovery - Request (R4).context.draftOrders.entry.resource.MedicationRequest.reasonCode | CodeableConcept | Optional | Yes | 0..1 | The diagnosis code associated with the order, and the reason for this service. Multiple diagnosis codes are not supported. Supported code systems: System URI SNOMED CT http://snomed.info/sct ICD-10 http://hl7.org/fhir/sid/icd-10-cm ICD-10 urn:oid:2.16.840.1.113883.6.90 ICD-9 http://hl7.org/fhir/sid/icd-9-cm/diagnosis ICD-9 http://hl7.org/fhir/sid/icd-9-cm ICD-9 urn:oid:2.16.840.1.113883.6.2 Work with payers you integrate with to understand the code systems for which they provide guidance. As an example, they might only define requirements for diagnosis codes in terms of ICD-10.

System | URI

SNOMED CT | http://snomed.info/sct

ICD-10 | http://hl7.org/fhir/sid/icd-10-cm

ICD-10 | urn:oid:2.16.840.1.113883.6.90

ICD-9 | http://hl7.org/fhir/sid/icd-9-cm/diagnosis

ICD-9 | http://hl7.org/fhir/sid/icd-9-cm

ICD-9 | urn:oid:2.16.840.1.113883.6.2

Coverage Requirements Discovery - Request (R4).context.draftOrders.entry.resource.MedicationRequest.reasonReference | Reference | Optional | Yes | 0..* | The diagnosis code associated with the order, and the reason for this service, as a reference to a Condition resource. Observation resources are not supported.

Coverage Requirements Discovery - Request (R4).context.draftOrders.entry.resource.MedicationRequest.reportedBoolean | boolean | Optional | | 0..1 | Whether this medication order is reported, rather than a primary record. Reported MedicationRequests are ignored and coverage guidance is not provided.

Coverage Requirements Discovery - Request (R4).context.draftOrders.entry.resource.MedicationRequest.reportedReference | Reference | Optional | | 0..1 | The actor that reported this medication order, indicating that this medication order is reported, rather than a primary record. Reported MedicationRequests are ignored and coverage guidance is not provided.

Coverage Requirements Discovery - Request (R4).context.draftOrders.entry.resource.MedicationRequest.requester | Reference | Required | | 1..1 | The provider that requested this service.

Coverage Requirements Discovery - Request (R4).context.draftOrders.entry.resource.MedicationRequest.status | code | Required | | 1..1 | The status of this order.

Coverage Requirements Discovery - Request (R4).context.draftOrders.entry.resource.MedicationRequest.subject | Reference | Required | | 1..1 | The patient for whom this service is being ordered. This must match the FHIR ID present in the context.patientId element.

Coverage Requirements Discovery - Request (R4).context.draftOrders.entry.resource.ServiceRequest | Resource | | | | A service being ordered for a patient.

Coverage Requirements Discovery - Request (R4).context.draftOrders.entry.resource.ServiceRequest.authoredOn | dateTime | Required | | 1..1 | The date and time the order was authored.

Coverage Requirements Discovery - Request (R4).context.draftOrders.entry.resource.ServiceRequest.code | CodeableConcept | Required | | 1..1 | Coded representation of the service being ordered. Supported code systems: System URI CPT http://www.ama-assn.org/go/cpt CPT urn:oid:2.16.840.1.113883.6.12 SNOMED CT http://snomed.info/sct SNOMED CT urn:oid:2.16.840.1.113883.6.96 HCPCS https://www.cms.gov/Medicare/Coding/HCPCSReleaseCodeSets HCPCS urn:oid:2.16.840.1.113883.6.285 LOINC http://loinc.org LOINC urn:oid:2.16.840.1.113883.6.1 Work with payers you integrate with to understand the code systems for which they provide guidance. As an example, they might only define requirements for procedure codes in terms of CPT or HCPCS.

System | URI

CPT | http://www.ama-assn.org/go/cpt

CPT | urn:oid:2.16.840.1.113883.6.12

SNOMED CT | http://snomed.info/sct

SNOMED CT | urn:oid:2.16.840.1.113883.6.96

HCPCS | https://www.cms.gov/Medicare/Coding/HCPCSReleaseCodeSets

HCPCS | urn:oid:2.16.840.1.113883.6.285

LOINC | http://loinc.org

LOINC | urn:oid:2.16.840.1.113883.6.1

Coverage Requirements Discovery - Request (R4).context.draftOrders.entry.resource.ServiceRequest.doNotPerform | boolean | Optional | | 0..1 | Whether the service should be performed. When doNotPerform is true, the service is skipped, and coverage guidance is not provided.

Coverage Requirements Discovery - Request (R4).context.draftOrders.entry.resource.ServiceRequest.extension (crd-delegate-evaluate) (also: extension (crd-delegate-evaluate)) | Extension | Optional | Yes | 0..1 | This custom extension is sent when Epic forwards the CRD request to a delegated entity. The extension informs the delegate that only a portion of their CRD response will be used in the overall response to the provider. This extension is not sent if the delegate is responsible for the entire request. The valueString is "covered" when the delegate is responsible for determining if the service is a covered benefit. The valueString is "pa-needed" when the delegate is responsible for determining if the service requires authorization.

Coverage Requirements Discovery - Request (R4).context.draftOrders.entry.resource.ServiceRequest.extension (crd-delegate-evaluate).crd-delegate-evaluate:url (also: crd-delegate-evaluate:url) | uri | Required | | 1..1 | The URL "https://open.epic.com/fhir/extensions/crd-delegate-evaluate".

Coverage Requirements Discovery - Request (R4).context.draftOrders.entry.resource.ServiceRequest.extension (crd-delegate-evaluate).crd-delegate-evaluate:valueString (also: crd-delegate-evaluate:valueString) | string | Required | | 1..1 | The valueString indicates the portion of the CRD request for which the delegate is responsible.

Coverage Requirements Discovery - Request (R4).context.draftOrders.entry.resource.ServiceRequest.id | id | Required | | 1..1 | The FHIR ID of the request. FHIR IDs are required for referencing.

Coverage Requirements Discovery - Request (R4).context.draftOrders.entry.resource.ServiceRequest.identifier | Identifier | Optional | Yes | 0..* | Identifiers for the order to echo in responses.

Coverage Requirements Discovery - Request (R4).context.draftOrders.entry.resource.ServiceRequest.insurance | Reference | Optional | Yes | 0..1 | A reference to the Coverage resource to use for guidance on this order.

Coverage Requirements Discovery - Request (R4).context.draftOrders.entry.resource.ServiceRequest.intent | code | Required | | 1..1 | The intent of the order.

Coverage Requirements Discovery - Request (R4).context.draftOrders.entry.resource.ServiceRequest.locationCode | CodeableConcept | | Yes | | The location taxonomy code for this service.

Coverage Requirements Discovery - Request (R4).context.draftOrders.entry.resource.ServiceRequest.locationReference | Reference | Optional | Yes | 0..1 | A reference to the Location where the service is planned to be performed.

Coverage Requirements Discovery - Request (R4).context.draftOrders.entry.resource.ServiceRequest.occurrencePeriod | Period | Optional | | 0..1 | The period of time over which the service is planned to be performed.

Coverage Requirements Discovery - Request (R4).context.draftOrders.entry.resource.ServiceRequest.occurrenceTiming | Timing | Optional | | 0..1 | The timing information of when this service is planned to be performed.

Coverage Requirements Discovery - Request (R4).context.draftOrders.entry.resource.ServiceRequest.occurrenceTiming.event | String | Optional | Yes | 0..* | The discrete times at which this service is planned to be performed.

Coverage Requirements Discovery - Request (R4).context.draftOrders.entry.resource.ServiceRequest.occurrenceTiming.repeat | BackboneElement | Optional | | 0..1 | The repeating details of this order. The service will be performed repeating within the boundsPeriod. Within the bounds, the service will be repeated in windows defined by the period and periodUnit. Within each window, the service will be repeated a number of times defined by the frequency.

Coverage Requirements Discovery - Request (R4).context.draftOrders.entry.resource.ServiceRequest.occurrenceTiming.repeat.boundsPeriod | Period | Optional | | 0..1 | The period within which the service is planned to be performed.

Coverage Requirements Discovery - Request (R4).context.draftOrders.entry.resource.ServiceRequest.occurrenceTiming.repeat.frequency | Int64 | Optional | | 0..1 | The frequency at which the service is planned to be performed.

Coverage Requirements Discovery - Request (R4).context.draftOrders.entry.resource.ServiceRequest.occurrenceTiming.repeat.period | decimal | Optional | | 0..1 | The period of repetition for performing the service.

Coverage Requirements Discovery - Request (R4).context.draftOrders.entry.resource.ServiceRequest.occurrenceTiming.repeat.periodUnit | code | Optional | | 0..1 | The units of the repeat period.

Coverage Requirements Discovery - Request (R4).context.draftOrders.entry.resource.ServiceRequest.performer | Reference | Optional | Yes | 0..1 | The provider who is planned to perform the service. Multiple performing providers are not supported.

Coverage Requirements Discovery - Request (R4).context.draftOrders.entry.resource.ServiceRequest.performerType | CodeableConcept | | | | The performer taxonomy code for this service.

Coverage Requirements Discovery - Request (R4).context.draftOrders.entry.resource.ServiceRequest.quantityQuantity | Quantity | Optional | | 0..1 | The quantity of the service being ordered.

Coverage Requirements Discovery - Request (R4).context.draftOrders.entry.resource.ServiceRequest.quantityRange | Range | Optional | | 0..1 | The range of quantities that might be performed for this order.

Coverage Requirements Discovery - Request (R4).context.draftOrders.entry.resource.ServiceRequest.reasonCode | CodeableConcept | Optional | Yes | 0..1 | The diagnosis code associated with the order, and the reason for this service. Multiple diagnosis codes are not supported. Supported code systems: System URI SNOMED CT http://snomed.info/sct ICD-10 http://hl7.org/fhir/sid/icd-10-cm ICD-10 urn:oid:2.16.840.1.113883.6.90 ICD-9 http://hl7.org/fhir/sid/icd-9-cm/diagnosis ICD-9 http://hl7.org/fhir/sid/icd-9-cm ICD-9 urn:oid:2.16.840.1.113883.6.2 Work with payers you integrate with to understand the code systems for which they provide guidance. As an example, they might only define requirements for diagnosis codes in terms of ICD-10.

System | URI

SNOMED CT | http://snomed.info/sct

ICD-10 | http://hl7.org/fhir/sid/icd-10-cm

ICD-10 | urn:oid:2.16.840.1.113883.6.90

ICD-9 | http://hl7.org/fhir/sid/icd-9-cm/diagnosis

ICD-9 | http://hl7.org/fhir/sid/icd-9-cm

ICD-9 | urn:oid:2.16.840.1.113883.6.2

Coverage Requirements Discovery - Request (R4).context.draftOrders.entry.resource.ServiceRequest.reasonReference | Reference | Optional | Yes | 0..* | The diagnosis code associated with the order, and the reason for this service, as a reference to a Condition resource. Observation resources are not supported.

Coverage Requirements Discovery - Request (R4).context.draftOrders.entry.resource.ServiceRequest.requester | Reference | Required | | 1..1 | The provider that requested this service.

Coverage Requirements Discovery - Request (R4).context.draftOrders.entry.resource.ServiceRequest.status | code | Required | | 1..1 | The status of this order.

Coverage Requirements Discovery - Request (R4).context.draftOrders.entry.resource.ServiceRequest.subject | Reference | Required | | 1..1 | The patient for whom this service is being ordered. This must match the FHIR ID present in the context.patientId element.

Coverage Requirements Discovery - Request (R4).context.patientId | String | Required | | 1..1 | The FHIR ID of the patient for whom this transaction is initiated.

Coverage Requirements Discovery - Request (R4).hook (also: hook) | String | Required | | 1..1 | The type of CDS Hook, either "order-sign" or "appointment-book".

Coverage Requirements Discovery - Request (R4).hookInstance (also: hookInstance) | String | Required | | 1..1 | A unique transaction identifier.

Coverage Requirements Discovery - Request (R4).prefetch | $prefetch | Required | | | FHIR resources retrieved by the prefetch queries from Coverage Requirements Discovery Endpoint Discovery. The prefetch field is an object with keys defined by configuration within Epic and values containing FHIR query results. The configurationDefinedKey field is a placeholder for these keys that are defined at runtime. For example, the prefetch object might contain keys "patient" and "coverage", each containing FHIR resources from the result of the associated prefetch queries. There should not be a key literally called "configurationDefinedKey". Prefetch is required to provide coverage guidance. Resources are not fetched from a FHIR server during request processing.

Coverage Requirements Discovery - Request (R4).prefetch.configurationDefinedKey | ResourceContainer | | | | FHIR resources from the results of the defined prefetch queries.

Coverage Requirements Discovery - Request (R4).prefetch.configurationDefinedKey.Bundle | Bundle | | | | A bundle of prefetched resources as the result of a FHIR search. Resources contained within bundles are supported equivalently to resources found at the top level of prefetch.

Coverage Requirements Discovery - Request (R4).prefetch.configurationDefinedKey.Condition | Condition | | | | A Condition used to report a diagnosis.

Coverage Requirements Discovery - Request (R4).prefetch.configurationDefinedKey.Condition.code | CodeableConcept | Required | | 1..1 | The diagnosis code for this condition. Supported code systems: System URI SNOMED CT http://snomed.info/sct ICD-10 http://hl7.org/fhir/sid/icd-10-cm ICD-10 urn:oid:2.16.840.1.113883.6.90 ICD-9 http://hl7.org/fhir/sid/icd-9-cm/diagnosis ICD-9 http://hl7.org/fhir/sid/icd-9-cm ICD-9 urn:oid:2.16.840.1.113883.6.2 Work with payers you integrate with to understand the code systems for which they provide guidance. As an example, they might only define requirements for diagnosis codes in terms of ICD-10.

System | URI

SNOMED CT | http://snomed.info/sct

ICD-10 | http://hl7.org/fhir/sid/icd-10-cm

ICD-10 | urn:oid:2.16.840.1.113883.6.90

ICD-9 | http://hl7.org/fhir/sid/icd-9-cm/diagnosis

ICD-9 | http://hl7.org/fhir/sid/icd-9-cm

ICD-9 | urn:oid:2.16.840.1.113883.6.2

Coverage Requirements Discovery - Request (R4).prefetch.configurationDefinedKey.Condition.subject | Reference | Required | | 1..1 | The subject of the condition. This must be a Patient reference with the same FHIR ID as the request's context.patientId.

Coverage Requirements Discovery - Request (R4).prefetch.configurationDefinedKey.Condition.verificationStatus | CodeableConcept | Optional | | 0..1 | The verification status of the diagnosis. When the status is "refuted" or "entered-in-error", the Condition is skipped, and the diagnosis is not used in determining coverage guidance.

Coverage Requirements Discovery - Request (R4).prefetch.configurationDefinedKey.Coverage | Resource | | | | The details of the patient's health insurance coverage.

Coverage Requirements Discovery - Request (R4).prefetch.configurationDefinedKey.Coverage.beneficiary | Reference | Required | | 1..1 | The beneficiary of the coverage. This must be a Patient reference with the same FHIR ID as the request's context.patientId.

Coverage Requirements Discovery - Request (R4).prefetch.configurationDefinedKey.Coverage.dependent | string | Conditional | | 0..1 | The dependent's member ID, if applicable. This is required if the beneficiary's relationship to the subscriber is not self. This should be the full member ID for the dependent's coverage.

Coverage Requirements Discovery - Request (R4).prefetch.configurationDefinedKey.Coverage.identifier | Identifier | Optional | Yes | 0..1 | Identifiers for the coverage, including the member ID for the coverage.

Coverage Requirements Discovery - Request (R4).prefetch.configurationDefinedKey.Coverage.identifier.type | CodeableConcept | Conditional | | 0..1 | For a member ID, the type must have a system of http://terminology.hl7.org/CodeSystem/v2-0203 and a value of "MB". Other types of identifiers are ignored.

Coverage Requirements Discovery - Request (R4).prefetch.configurationDefinedKey.Coverage.identifier.value | String | Required | | 1..1 | The beneficiary's member ID for the coverage.

Coverage Requirements Discovery - Request (R4).prefetch.configurationDefinedKey.Coverage.relationship | CodeableConcept | Required | | 1..1 | The relationship of the beneficiary of the coverage to the subscriber. The code system must be http://terminology.hl7.org/CodeSystem/subscriber-relationship or urn:oid:2.16.840.1.113883.4.642.1.1386.

Coverage Requirements Discovery - Request (R4).prefetch.configurationDefinedKey.Coverage.subscriberId | string | Required | | 1..1 | The subscriber ID of the coverage.

Coverage Requirements Discovery - Request (R4).prefetch.configurationDefinedKey.Location | Resource | | | | A performing or requesting facility.

Coverage Requirements Discovery - Request (R4).prefetch.configurationDefinedKey.Location.address | Address | Required | | 1..1 | The address of the facility.

Coverage Requirements Discovery - Request (R4).prefetch.configurationDefinedKey.Location.identifier | Identifier | Optional | Yes | 0..* | The identifiers of the facility. Supported code systems: System URI NPI http://hl7.org/fhir/sid/us-npi EIN http://terminology.hl7.org/NamingSystem/USEIN

System | URI

NPI | http://hl7.org/fhir/sid/us-npi

EIN | http://terminology.hl7.org/NamingSystem/USEIN

Coverage Requirements Discovery - Request (R4).prefetch.configurationDefinedKey.Location.name | string | Required | | 1..1 | The name of the facility.

Coverage Requirements Discovery - Request (R4).prefetch.configurationDefinedKey.Location.status | code | Optional | | 0..1 | The status of the facility. When the status is "inactive", the facility is skipped, and it is not used to determine coverage guidance.

Coverage Requirements Discovery - Request (R4).prefetch.configurationDefinedKey.Location.telecom | ContactPoint | Optional | Yes | 0..* | The contact information for the facility.

Coverage Requirements Discovery - Request (R4).prefetch.configurationDefinedKey.Location.type | CodeableConcept | Optional | Yes | 0..1 | The place of service type code for the facility. The CMS Mappable Location Codes value set defined in the Da Vinci CRD implementation guide is supported, as well as direct CMS place of service codes using the system https://www.cms.gov/Medicare/Coding/place-of-service-codes/Place_of_Service_Code_Set.

Coverage Requirements Discovery - Request (R4).prefetch.configurationDefinedKey.Medication | Resource | | | | A medication being requested.

Coverage Requirements Discovery - Request (R4).prefetch.configurationDefinedKey.Medication.code | CodeableConcept | Required | | 1..1 | The coded representation of a medication. Supported code systems: System URI CPT http://www.ama-assn.org/go/cpt CPT

urn:oid:2.16.840.1.113883.6.12 SNOMED CT http://snomed.info/sct SNOMED CT urn:oid:2.16.840.1.113883.6.96 HCPCS https://www.cms.gov/Medicare/Coding/HCPCSReleaseCodeSets HCPCS urn:oid:2.16.840.1.113883.6.285 LOINC http://loinc.org LOINC urn:oid:2.16.840.1.113883.6.1 Work with payers you integrate with to understand the code systems for which they provide guidance. As an example, they might only define requirements for procedure codes in terms of CPT or HCPCS.

System | URI

CPT | http://www.ama-assn.org/go/cpt

CPT | urn:oid:2.16.840.1.113883.6.12

SNOMED CT | http://snomed.info/sct

SNOMED CT | urn:oid:2.16.840.1.113883.6.96

HCPCS | https://www.cms.gov/Medicare/Coding/HCPCSReleaseCodeSets

HCPCS | urn:oid:2.16.840.1.113883.6.285

LOINC | http://loinc.org

LOINC | urn:oid:2.16.840.1.113883.6.1

Coverage Requirements Discovery - Request (R4).prefetch.configurationDefinedKey.Organization | Resource | | | | A performing or requesting facility.

Coverage Requirements Discovery - Request (R4).prefetch.configurationDefinedKey.Organization.active | boolean | Required | | 1..1 | An indication of whether the facility is active. When the value of active is false, the facility is skipped, and it is not used to determine coverage guidance.

Coverage Requirements Discovery - Request (R4).prefetch.configurationDefinedKey.Organization.address | Address | Required | Yes | 1..1 | The address of the facility.

Coverage Requirements Discovery - Request (R4).prefetch.configurationDefinedKey.Organization.identifier | Identifier | Optional | Yes | 0..* | The identifiers of the facility. Supported code systems: System URI NPI http://hl7.org/fhir/sid/us-npi EIN http://terminology.hl7.org/NamingSystem/USEIN

System | URI

NPI | http://hl7.org/fhir/sid/us-npi

EIN | http://terminology.hl7.org/NamingSystem/USEIN

Coverage Requirements Discovery - Request (R4).prefetch.configurationDefinedKey.Organization.name | string | Required | | 1..1 | The name of the facility.

Coverage Requirements Discovery - Request (R4).prefetch.configurationDefinedKey.Organization.telecom | ContactPoint | Optional | Yes | 0..* | The contact information for the facility.

Coverage Requirements Discovery - Request (R4).prefetch.configurationDefinedKey.Patient | Resource | | | | A patient record.

Coverage Requirements Discovery - Request (R4).prefetch.configurationDefinedKey.Patient.address | Address | Optional | Yes | 0..1 | The home address of the patient.

Coverage Requirements Discovery - Request (R4).prefetch.configurationDefinedKey.Patient.birthDate | date | Optional | | 0..1 | The birth date of the patient.

Coverage Requirements Discovery - Request (R4).prefetch.configurationDefinedKey.Patient.gender | code | Required | | 1..1 | The legal sex of the patient.

Coverage Requirements Discovery - Request (R4).prefetch.configurationDefinedKey.Patient.identifier | Identifier | Optional | Yes | 0..* | Identifiers for the patient. The supported code system is urn:oid:2.16.840.1.113883.4.1 for Social Security Number.

Coverage Requirements Discovery - Request (R4).prefetch.configurationDefinedKey.Patient.name | HumanName | Required | Yes | 1..1 | The name of the patient.

Coverage Requirements Discovery - Request (R4).prefetch.configurationDefinedKey.Patient.telecom | ContactPoint | Optional | Yes | 0..* | The contact points for the patient.

Coverage Requirements Discovery - Request (R4).prefetch.configurationDefinedKey.Practitioner | Resource | | | | A healthcare practitioner.

Coverage Requirements Discovery - Request (R4).prefetch.configurationDefinedKey.Practitioner.address | Address | Optional | Yes | 0..* | The address of the practitioner.

Coverage Requirements Discovery - Request (R4).prefetch.configurationDefinedKey.Practitioner.identifier | Identifier | Required | Yes | 1..* | The identifiers of the practitioner. This code system is supported for communicating NPIs: http://hl7.org/fhir/sid/us-npi.

Coverage Requirements Discovery - Request (R4).prefetch.configurationDefinedKey.Practitioner.name | HumanName | Required | Yes | 1..1 | The name of the practitioner.

Coverage Requirements Discovery - Request (R4).prefetch.configurationDefinedKey.Practitioner.telecom | ContactPoint | Optional | Yes | 0..* | The contact details for the practitioner.

Coverage Requirements Discovery - Request (R4).prefetch.configurationDefinedKey.PractitionerRole | Resource | | | | A practitioner performing at a specific organization.

Coverage Requirements Discovery - Request (R4).prefetch.configurationDefinedKey.PractitionerRole.organization | Reference | Optional | | 0..1 | The organization at which the practitioner is working.

Coverage Requirements Discovery - Request (R4).prefetch.configurationDefinedKey.PractitionerRole.practitioner | Reference | Required | | 1..1 | A reference to the Practitioner resource representing the practitioner's information.

Coverage Requirements Discovery - Request (R4).prefetch.configurationDefinedKey.PractitionerRole.specialty | CodeableConcept | | Yes | | The taxonomy code for appointment participant.actor or ServiceRequest.performer that is referenced using the PractitionerRole resource.

Response elements

Name | Type | Optional | Array | Cardinality | Description

Coverage Requirements Discovery - Response (R4) | $coveragerequirementsdiscovery - Response | Required | | 1..1 | A Coverage Requirements Discovery response. In case of an error, an OperationOutcome is returned instead of this structure.

Coverage Requirements Discovery - Response (R4).cards | String | Required | Yes | 0..0 | The list of cards to display to the user. This is currently always an empty array.

Coverage Requirements Discovery - Response (R4).systemActions | | Optional | Yes | 0..* | The list of actions to apply to the system, updating request resources with coverage information.

Coverage Requirements Discovery - Response (R4).systemActions.resource | ResourceContainer | | | | The resource being updated. This is copied from the resource present in the request, with coverage information added.

Coverage Requirements Discovery - Response (R4).systemActions.resource.MedicationRequest | MedicationRequest | | | | A medication request being updated.

Coverage Requirements Discovery - Response (R4).systemActions.resource.MedicationRequest.extension (coverage-information) (also: extension (coverage-information)) | Extension | | Yes | | The coverage information being provided about this service.

Coverage Requirements Discovery - Response (R4).systemActions.resource.MedicationRequest.extension (coverage-information).coverage (also: coverage) | Extension | Conditional | Yes | 0..1 | The coverage resource used for this guidance. This uses the FHIR ID of the Coverage resource retrieved from the request. The value is always present unless there is an error retrieving/matching the coverage.

Coverage Requirements Discovery - Response (R4).systemActions.resource.MedicationRequest.extension (coverage-information).coverage.url | uri | Required | | 1..1 | The URL "coverage".

Coverage Requirements Discovery - Response (R4).systemActions.resource.MedicationRequest.extension (coverage-information).coverage.valueReference | Reference | Required | | 1..1 | The value reference to the Coverage.

Coverage Requirements Discovery - Response (R4).systemActions.resource.MedicationRequest.extension (coverage-information).coverage-assertion-id (also: coverage-assertion-id) | Extension | Required | Yes | 1..1 | A unique identifier for this coverage information. Coverage assertion IDs can be used to coordinate with payer staff as coverage guidance reference numbers.

Coverage Requirements Discovery - Response (R4).systemActions.resource.MedicationRequest.extension (coverage-information).coverage-assertion-id.url | uri | Required | | 1..1 | The URL "coverage-assertion-id".

Coverage Requirements Discovery - Response (R4).systemActions.resource.MedicationRequest.extension (coverage-information).coverage-assertion-id.valueString | string | Required | | 1..1 | The value of the unique identifier.

Coverage Requirements Discovery - Response (R4).systemActions.resource.MedicationRequest.extension (coverage-information).covered (also: covered) | Extension | Required | Yes | 1..1 | The covered benefit status of the service. The value is "covered" when the service is a covered benefit and might be paid for by the patient's coverage. This response does not guarantee payment, which might depend on more details determined at the time of claim submission and review. The value is "not-covered" when the service is not a covered benefit and is not paid for by the patient's coverage, or there was a problem matching the patient or coverage record. The value is "conditional" when the service might be covered depending on certain constraints.

Coverage Requirements Discovery - Response (R4).systemActions.resource.MedicationRequest.extension (coverage-information).covered.url | uri | Required | | 1..1 | The URL "covered".

Coverage Requirements Discovery - Response (R4).systemActions.resource.MedicationRequest.extension (coverage-information).covered.valueCode | code | Required | | 1..1 | The covered benefit status code.

Coverage Requirements Discovery - Response (R4).systemActions.resource.MedicationRequest.extension (coverage-information).date (also: date) | Extension | Required | Yes | 1..1 | The date the guidance was produced. The value is always the current date when the response is sent.

Coverage Requirements Discovery - Response (R4).systemActions.resource.MedicationRequest.extension (coverage-information).date.url | uri | Required | | 1..1 | The URL "date".

Coverage Requirements Discovery - Response (R4).systemActions.resource.MedicationRequest.extension (coverage-information).date.valueDate | date | Required | | 1..1 | The date the coverage guidance was provided.

Coverage Requirements Discovery - Response (R4).systemActions.resource.MedicationRequest.extension (coverage-information).detail (also: detail) | Extension | Optional | Yes | 0..* | Detailed information about the coverage guidance.

Coverage Requirements Discovery - Response (R4).systemActions.resource.MedicationRequest.extension (coverage-information).detail.detail code (also: detail code) | Extension | Required | Yes | 1..1 | The type of this detail. The following codes are currently supported from the code system http://hl7.org/fhir/us/davinci-crd/CodeSystem/temp: instructions instructions-admin auth-out-network-only

Coverage Requirements Discovery - Response (R4).systemActions.resource.MedicationRequest.extension (coverage-information).detail.detail code.url | uri | Required | | 1..1 | The URL "code".

Coverage Requirements Discovery - Response (R4).systemActions.resource.MedicationRequest.extension (coverage-information).detail.detail code.valueCodeableConcept | CodeableConcept | Required | | 1..1 | The coded type of detail in this detail extension.

Coverage Requirements Discovery - Response (R4).systemActions.resource.MedicationRequest.extension (coverage-information).detail.detail value (also: detail value) | Extension | Required | Yes | 1..1 | The value of the detail. Only string values are supported.

Coverage Requirements Discovery - Response (R4).systemActions.resource.MedicationRequest.extension (coverage-information).detail.detail value.url | uri | Required | | 1..1 | The URL "value".

Coverage Requirements Discovery - Response (R4).systemActions.resource.MedicationRequest.extension (coverage-information).detail.detail value.valueString | string | Required | | 1..1 | The string value of the detail.

Coverage Requirements Discovery - Response (R4).systemActions.resource.MedicationRequest.extension (coverage-information).detail.url | uri | Required | | 1..1 | The URL "detail".

Coverage Requirements Discovery - Response (R4).systemActions.resource.MedicationRequest.extension (coverage-information).doc-needed (also: doc-needed) | Extension | Optional | Yes | 0..1 | The documentation requirement for this service. The value is "clinical" when Documentation Templates and Rules should be used to submit documentation with a prior authorization request. This extension is not present otherwise.

Coverage Requirements Discovery - Response (R4).systemActions.resource.MedicationRequest.extension (coverage-information).doc-needed.url | uri | Required | | 1..1 | The URL "doc-needed".

Coverage Requirements Discovery - Response (R4).systemActions.resource.MedicationRequest.extension (coverage-information).doc-needed.valueCode | code | Required | | 1..1 | The code for documentation requirements.

Coverage Requirements Discovery - Response (R4).systemActions.resource.MedicationRequest.extension (coverage-information).doc-purpose (also: doc-purpose) | Extension | Optional | Yes | 0..1 | The purpose of the documentation requirement. The value is "withpa" when Documentation Templates and Rules should be used to submit documentation with a prior authorization request. This extension is not present otherwise.

Coverage Requirements Discovery - Response (R4).systemActions.resource.MedicationRequest.extension (coverage-information).doc-purpose.url | uri | Required | | 1..1 | The URL "doc-purpose".

Coverage Requirements Discovery - Response (R4).systemActions.resource.MedicationRequest.extension (coverage-information).doc-purpose.valueCode | code | Required | | 1..1 | The code for documentation purpose.

Coverage Requirements Discovery - Response (R4).systemActions.resource.MedicationRequest.extension (coverage-information).expiry-date (also: expiry-date) | Extension | Conditional | Yes | 0..1 | The expiration date of the coverage guidance provided. When the date of service is after the expiry date provided, the guidance should not be relied on without repeating the request to get up-to-date guidance. This is always present unless there is a failure matching the patient or coverage record.

Coverage Requirements Discovery - Response (R4).systemActions.resource.MedicationRequest.extension (coverage-information).expiry-date.url | uri | Required | | 1..1 | The URL "expiry-date".

Coverage Requirements Discovery - Response (R4).systemActions.resource.MedicationRequest.extension (coverage-information).expiry-date.valueDate | date | Required | | 1..1 | The expiration date value.

Coverage Requirements Discovery - Response (R4).systemActions.resource.MedicationRequest.extension (coverage-information).info-needed (also: info-needed) | Extension | Optional | Yes | 0..1 | The requirement for additional information to provide full guidance. The code "performer" from the system http://hl7.org/fhir/us/davinci-crd/CodeSystem/temp is supported.

Coverage Requirements Discovery - Response (R4).systemActions.resource.MedicationRequest.extension (coverage-information).info-needed.url | uri | Required | | 1..1 | The URL "info-needed".

Coverage Requirements Discovery - Response (R4).systemActions.resource.MedicationRequest.extension (coverage-information).info-needed.valueCode | code | Required | | 1..1 | The code for the information requirement.

Coverage Requirements Discovery - Response (R4).systemActions.resource.MedicationRequest.extension (coverage-information).pa-needed (also: pa-needed) | Extension | Optional | Yes | 0..1 | The requirement for a prior authorization for this service. The following codes are supported from the system http://hl7.org/fhir/us/davinci-crd/CodeSystem/temp: no-auth auth-needed conditional

Coverage Requirements Discovery - Response (R4).systemActions.resource.MedicationRequest.extension (coverage-information).pa-needed.url | uri | Required | | 1..1 | The URL "pa-needed".

Coverage Requirements Discovery - Response (R4).systemActions.resource.MedicationRequest.extension (coverage-information).pa-needed.valueCode | code | Required | | 1..1 | The code value for the prior authorization requirement.

Coverage Requirements Discovery - Response (R4).systemActions.resource.MedicationRequest.extension (coverage-information).reason (also: reason) | Extension | Optional | Yes | 0..1 | The reason for the guidance provided. The supported codes are from the value set http://hl7.org/fhir/us/davinci-crd/ValueSet/coverageAssertionReasons. The value is "member-not-found" when there was a failure to match the patient information to a record in the system. The value is "no-active-coverage" when there was a failure to match the coverage information to a record in the system.

Coverage Requirements Discovery - Response (R4).systemActions.resource.MedicationRequest.extension (coverage-information).reason.url | uri | Required | | 1..1 | The URL "reason".

Coverage Requirements Discovery - Response (R4).systemActions.resource.MedicationRequest.extension (coverage-information).reason.valueCodeableConcept | CodeableConcept | Required | | 1..1 | The coded reason for the coverage guidance.

Coverage Requirements Discovery - Response (R4).systemActions.resource.ServiceRequest | Resource | | | | A request for a service being updated.

Coverage Requirements Discovery - Response (R4).systemActions.resource.ServiceRequest.extension (coverage-information) (also: extension (coverage-information)) | Extension | | Yes | | The coverage information being provided about this service.

Coverage Requirements Discovery - Response (R4).systemActions.resource.ServiceRequest.extension (coverage-information).coverage (also: coverage) | Extension | Conditional | Yes | 0..1 | The coverage resource used for this guidance. This uses the FHIR ID of the Coverage resource retrieved from the request. The value is always present unless there is an error retrieving/matching the coverage.

Coverage Requirements Discovery - Response (R4).systemActions.resource.ServiceRequest.extension (coverage-information).coverage.url | uri | Required | | 1..1 | The URL "coverage".

Coverage Requirements Discovery - Response (R4).systemActions.resource.ServiceRequest.extension (coverage-information).coverage.valueReference | Reference | Required | | 1..1 | The value reference to the Coverage.

Coverage Requirements Discovery - Response (R4).systemActions.resource.ServiceRequest.extension (coverage-information).coverage-assertion-id (also: coverage-assertion-id) | Extension | Required | Yes | 1..1 | A unique identifier for this coverage information. Coverage assertion IDs can be used to coordinate with payer staff as coverage guidance reference numbers.

Coverage Requirements Discovery - Response (R4).systemActions.resource.ServiceRequest.extension (coverage-information).coverage-assertion-id.url | uri | Required | | 1..1 | The URL "coverage-assertion-id".

Coverage Requirements Discovery - Response (R4).systemActions.resource.ServiceRequest.extension (coverage-information).coverage-assertion-id.valueString | string | Required | | 1..1 | The value of the unique identifier.

Coverage Requirements Discovery - Response (R4).systemActions.resource.ServiceRequest.extension (coverage-information).covered (also: covered) | Extension | Required | Yes | 1..1 | The covered benefit status of the service. The value is "covered" when the service is a covered benefit and might be paid for by the patient's coverage. This response does not guarantee payment, which might depend on more details determined at the time of claim submission and review. The value is "not-covered" when the service is not a covered benefit and is not paid for by the patient's coverage, or there was a problem matching the patient or coverage record. The value is "conditional" when the service might be covered depending on certain constraints.

Coverage Requirements Discovery - Response (R4).systemActions.resource.ServiceRequest.extension (coverage-information).covered.url | uri | Required | | 1..1 | The URL "covered".

Coverage Requirements Discovery - Response (R4).systemActions.resource.ServiceRequest.extension (coverage-information).covered.valueCode | code | Required | | 1..1 | The covered benefit status code.

Coverage Requirements Discovery - Response (R4).systemActions.resource.ServiceRequest.extension (coverage-information).date (also: date) | Extension | Required | Yes | 1..1 | The date the guidance was produced. The value is always the current date when the response is sent.

Coverage Requirements Discovery - Response (R4).systemActions.resource.ServiceRequest.extension (coverage-information).date.url | uri | Required | | 1..1 | The URL "date".

Coverage Requirements Discovery - Response (R4).systemActions.resource.ServiceRequest.extension (coverage-information).date.valueDate | date | Required | | 1..1 | The date the coverage guidance was provided.

Coverage Requirements Discovery - Response (R4).systemActions.resource.ServiceRequest.extension (coverage-information).detail (also: detail) | Extension | Optional | Yes | 0..* | Detailed information about the coverage guidance.

Coverage Requirements Discovery - Response (R4).systemActions.resource.ServiceRequest.extension (coverage-information).detail.detail code (also: detail code) | Extension | Required | Yes | 1..1 | The type of this detail. The following codes are currently supported from the code system http://hl7.org/fhir/us/davinci-crd/CodeSystem/temp: instructions instructions-admin auth-out-network-only

Coverage Requirements Discovery - Response (R4).systemActions.resource.ServiceRequest.extension (coverage-information).detail.detail code.url | uri | Required | | 1..1 | The URL "code".

Coverage Requirements Discovery - Response (R4).systemActions.resource.ServiceRequest.extension (coverage-information).detail.detail code.valueCodeableConcept | CodeableConcept | Required | | 1..1 | The coded type of detail in this detail extension.

Coverage Requirements Discovery - Response (R4).systemActions.resource.ServiceRequest.extension (coverage-information).detail.detail value (also: detail value) | Extension | Required | Yes | 1..1 | The value of the detail. Only string values are supported.

Coverage Requirements Discovery - Response (R4).systemActions.resource.ServiceRequest.extension (coverage-information).detail.detail value.url | uri | Required | | 1..1 | The URL "value".

Coverage Requirements Discovery - Response (R4).systemActions.resource.ServiceRequest.extension (coverage-information).detail.detail value.valueString | string | Required | | 1..1 | The string value of the detail.

Coverage Requirements Discovery - Response (R4).systemActions.resource.ServiceRequest.extension (coverage-information).detail.url | uri | Required | | 1..1 | The URL "detail".

Coverage Requirements Discovery - Response (R4).systemActions.resource.ServiceRequest.extension (coverage-information).doc-needed (also: doc-needed) | Extension | Optional | Yes | 0..1 | The documentation requirement for this service. The value is "clinical" when Documentation Templates and Rules should be used to submit documentation with a prior authorization request. This extension is not present otherwise.

Coverage Requirements Discovery - Response (R4).systemActions.resource.ServiceRequest.extension (coverage-information).doc-needed.url | uri | Required | | 1..1 | The URL "doc-needed".

Coverage Requirements Discovery - Response (R4).systemActions.resource.ServiceRequest.extension (coverage-information).doc-needed.valueCode | code | Required | | 1..1 | The code for documentation requirements.

Coverage Requirements Discovery - Response (R4).systemActions.resource.ServiceRequest.extension (coverage-information).doc-purpose (also: doc-purpose) | Extension | Optional | Yes | 0..1 | The purpose of the documentation requirement. The value is "withpa" when Documentation Templates and Rules should be used to submit documentation with a prior authorization request. This extension is not present otherwise.

Coverage Requirements Discovery - Response (R4).systemActions.resource.ServiceRequest.extension (coverage-information).doc-purpose.url | uri | Required | | 1..1 | The URL "doc-purpose".

Coverage Requirements Discovery - Response (R4).systemActions.resource.ServiceRequest.extension (coverage-information).doc-purpose.valueCode | code | Required | | 1..1 | The code for documentation purpose.

Coverage Requirements Discovery - Response (R4).systemActions.resource.ServiceRequest.extension (coverage-information).expiry-date (also: expiry-date) | Extension | Conditional | Yes | 0..1 | The expiration date of the coverage guidance provided. When the date of service is after the expiry date provided, the guidance should not be relied on without repeating the request to get up-to-date guidance. This is always present unless there is a failure matching the patient or coverage record.

Coverage Requirements Discovery - Response (R4).systemActions.resource.ServiceRequest.extension (coverage-information).expiry-date.url | uri | Required | | 1..1 | The URL "expiry-date".

Coverage Requirements Discovery - Response (R4).systemActions.resource.ServiceRequest.extension (coverage-information).expiry-date.valueDate | date | Required | | 1..1 | The expiration date value.

Coverage Requirements Discovery - Response (R4).systemActions.resource.ServiceRequest.extension (coverage-information).info-needed (also: info-needed) | Extension | Optional | Yes | 0..1 | The requirement for additional information to provide full guidance. The code "performer" from the system http://hl7.org/fhir/us/davinci-crd/CodeSystem/temp is supported.

Coverage Requirements Discovery - Response (R4).systemActions.resource.ServiceRequest.extension (coverage-information).info-needed.url | uri | Required | | 1..1 | The URL "info-needed".

Coverage Requirements Discovery - Response (R4).systemActions.resource.ServiceRequest.extension (coverage-information).info-needed.valueCode | code | Required | | 1..1 | The code for the information requirement.

Coverage Requirements Discovery - Response (R4).systemActions.resource.ServiceRequest.extension (coverage-information).pa-needed (also: pa-needed) | Extension | Optional | Yes | 0..1 | The requirement for a prior authorization for this service. The following codes are supported from the system http://hl7.org/fhir/us/davinci-crd/CodeSystem/temp: no-auth auth-needed conditional

Coverage Requirements Discovery - Response (R4).systemActions.resource.ServiceRequest.extension (coverage-information).pa-needed.url | uri | Required | | 1..1 | The URL "pa-needed".

Coverage Requirements Discovery - Response (R4).systemActions.resource.ServiceRequest.extension (coverage-information).pa-needed.valueCode | code | Required | | 1..1 | The code value for the prior authorization requirement.

Coverage Requirements Discovery - Response (R4).systemActions.resource.ServiceRequest.extension (coverage-information).reason (also: reason) | Extension | Optional | Yes | 0..1 | The reason for the guidance provided. The supported codes are from the value set http://hl7.org/fhir/us/davinci-crd/ValueSet/coverageAssertionReasons. The value is "member-not-found" when there was a failure to match the patient information to a record in the system. The value is "no-active-coverage" when there was a failure to match the coverage information to a record in the system.

Coverage Requirements Discovery - Response (R4).systemActions.resource.ServiceRequest.extension (coverage-information).reason.url | uri | Required | | 1..1 | The URL "reason".

Coverage Requirements Discovery - Response (R4).systemActions.resource.ServiceRequest.extension (coverage-information).reason.valueCodeableConcept | CodeableConcept | Required | | 1..1 | The coded reason for the coverage guidance.

Coverage Requirements Discovery - Response (R4).systemActions.type | String | Required | | 1..1 | The type of the system action. Always "update".

Sample request

```
POST https://hostname/instance/api/epic/2024/HL7DaVinciCRD/CoverageRequirementsDiscovery/cds-
    services/CoverageRequirementsDiscovery
{
  "hookInstance": "<unique instance identifier>",
  "hook": "appointment-book",
  "context": {
    "patientId": "example-crd-patient",
    "appointments": {
      "resourceType": "Bundle",
      "entry": [
        {
          "resource": {
            "resourceType": "Appointment",
            "id": "example-appointment",
            "status": "booked",
            "start": "2026-02-10T11:00:00Z",
            "end": "2026-02-10T11:30:00Z",
            "requestedPeriod": [
              {
                "start": "2026-02-01T11:00:00Z",
                "end": "2026-02-28T11:00:00Z"
              }
            ],
            "participant": [
              {
                "actor": {
                  "reference": "PractitionerRole/example-practitioner-role"
                },
                "status": "accepted"
              },
              {
                "actor": {
                  "reference": "Location/example-location"
                },
                "status": "accepted"
              }
            ],
            "basedOn": [
              {
                "reference": "ServiceRequest/example-service-request"
              },
              {
                "reference": "MedicationRequest/example-medication-request"
              }
```

```
          ]
        }
      }
    ]
  }
},
"prefetch": {
  "patient": {
    "resourceType": "Patient",
    "id": "example-crd-patient",
    "identifier": [
      {
        "use": "usual",
        "system": "urn:oid:2.16.840.1.113883.4.1",
        "value": "406911001"
      }
    ],
    "name": [
      {
        "use": "usual",
        "family": "Patient",
        "given": [
          "Example"
        ],
        "suffix": [
          "Jr."
        ]
      }
    ],
    "telecom": [
      {
        "system": "phone",
        "value": "800-900-1000",
        "use": "home",
        "rank": 1
      },
      {
        "system": "phone",
        "value": "801-901-1001",
        "use": "home",
        "rank": 2
      },
      {
        "system": "email",
        "value": "member@example.com",
        "use": "home",
        "rank": 1
      }
    ],
    "gender": "female",
    "birthDate": "2000-01-01",
    "address": [
      {
        "line": [
          "123 Anywhere St"
        ],
        "city": "Madison",
        "state": "WI",
        "postalCode": "53593"
      }
    ]
  },
  "coverage": {
    "resourceType": "Bundle",
    "type": "searchset",
    "total": 1,
    "entry": [
      {
        "resource": {
          "resourceType": "Coverage",
          "id": "coverage-resource",
          "identifier": [
            {
              "type": {
                "coding": [
                  {
                    "system": "http://terminology.hl7.org/CodeSystem/v2-0203",
                    "code": "MB"
                  }
                ]
              },
              "value": "PSDNVRJ79HVNZGT01"
            }
          ],
          "beneficiary": {
            "reference": "Patient/example-crd-patient"
          },
          "relationship": {
            "coding": [
```

```
            {
              "system": "http://terminology.hl7.org/CodeSystem/subscriber-relationship",
              "code": "self"
            }
          ]
        },
        "subscriberId": "PSDNVRJ79HVNZGT01"
      },
      "search": {
        "mode": "match"
      }
    }
  ]
},
"serviceRequest": {
  "resourceType": "Bundle",
  "type": "searchset",
  "total": 1,
  "entry": [
    {
      "resource": {
        "resourceType": "ServiceRequest",
        "id": "example-service-request",
        "identifier": [
          {
            "system": "https://example.com/system",
            "value": "example-service-request"
          }
        ],
        "status": "draft",
        "intent": "order",
        "doNotPerform": false,
        "subject": {
          "reference": "Patient/example-crd-patient"
        },
        "insurance": [
          {
            "reference": "Coverage/coverage-resource"
          }
        ],
        "authoredOn": "2026-01-01",
        "requester": {
          "reference": "Practitioner/example-requester",
          "display": "Example Requester"
        },
        "performer": [
          {
            "reference": "PractitionerRole/example-performer-role",
            "display": "Example Performer"
          }
        ],
        "reasonReference": [
          {
            "reference": "Condition/example-condition"
          }
        ],
        "code": {
          "coding": [
            {
              "system": "http://www.ama-assn.org/go/cpt",
              "code": "73722",
              "display": "MRI scan of leg joint with contrast"
            }
          ],
          "text": "MRI scan of leg joint with contrast"
        },
        "quantityRange": {
          "low": {
            "value": 1
          },
          "high": {
            "value": 2
          }
        },
        "occurrencePeriod": {
          "start": "2026-02-01T16:00:00-00:00",
          "end": "2026-02-08T16:30:00-00:00"
        },
        "locationReference": [
          {
            "reference": "Location/example-location",
            "display": "Example Location"
          }
        ]
      },
      "search": {
        "mode": "match"
      }
    }
```

```
  ]
},
"medicationRequest": {
  "resourceType": "Bundle",
  "type": "searchset",
  "total": 1,
  "entry": [
    {
      "resource": {
        "resourceType": "MedicationRequest",
        "id": "example-medication-request",
        "identifier": [
          {
            "use": "official",
            "system": "http://www.bmc.nl/portal/prescriptions",
            "value": "12345689"
          }
        ],
        "status": "draft",
        "intent": "order",
        "reportedBoolean": false,
        "subject": {
          "reference": "Patient/example-crd-patient"
        },
        "insurance": [
          {
            "reference": "Coverage/coverage-resource"
          }
        ],
        "authoredOn": "2026-01-01",
        "requester": {
          "reference": "Practitioner/example-requester",
          "display": "Example Requester"
        },
        "performer": {
          "reference": "Practitioner/example-performer",
          "display": "Example Performer"
        },
        "medicationReference": {
          "reference": "Medication/example-medication"
        },
        "reasonCode": [
          {
            "coding": [
              {
                "system": "http://snomed.info/sct",
                "code": "418589001",
                "display": "Accidental physical contact with animal (event)"
              },
              {
                "system": "http://hl7.org/fhir/sid/icd-10-cm",
                "code": "W61.62XA",
                "display": "Struck by duck, initial encounter"
              }
            ],
            "text": "Struck by duck, initial encounter"
          }
        ],
        "dosageInstruction": [
          {
            "timing": {
              "event": [
                "2026-02-01T1600:0000:00"
              ],
              "repeat": {
                "boundsPeriod": {
                  "start": "2026-02-01T1600:0000:00",
                  "end": "2026-02-08T16:30:00-00:00"
                }
              }
            }
          }
        ]
      },
      "search": {
        "mode": "match"
      }
    }
  ]
},
"medication": {
  "resourceType": "Bundle",
  "type": "searchset",
  "total": 1,
  "entry": [
    {
      "resource": {
        "resourceType": "Medication",
        "id": "medication-example",
```

```
        "code": {
          "coding": [
            {
              "system": "urn:oid:2.16.840.1.113883.6.285",
              "code": "64612",
              "display": "PR CHEMODNRVTJ MUSC MUSC INNERVATED FACIAL NRV UNIL"
            }
          ],
          "text": "PR CHEMODNRVTJ MUSC MUSC INNERVATED FACIAL NRV UNIL"
        }
      },
      "search": {
        "mode": "match"
      }
    }
  ]
},
"practitionerRole": {
  "resourceType": "Bundle",
  "type": "searchset",
  "total": 1,
  "entry": [
    {
      "resource": {
        "resourceType": "PractitionerRole",
        "id": "example-performer-role",
        "practitioner": {
          "reference": "Practitioner/example-performer"
        },
        "organization": {
          "reference": "Organization/example-organization"
        },
        "location": [
          {
            "reference": "Location/example-location"
          }
        ]
      },
      "search": {
        "mode": "match"
      }
    }
  ]
},
"practitioner": {
  "resourceType": "Bundle",
  "type": "searchset",
  "total": 2,
  "entry": [
    {
      "resource": {
        "resourceType": "Practitioner",
        "id": "example-performer",
        "identifier": [
          {
            "system": "http://hl7.org/fhir/sid/us-npi",
            "value": "4069100004"
          }
        ],
        "name": [
          {
            "use": "usual",
            "family": "Performer",
            "given": [
              "Example"
            ]
          }
        ],
        "telecom": [
          {
            "system": "phone",
            "value": "804-904-1004",
            "use": "work"
          }
        ],
        "address": [
          {
            "line": [
              "456 Anywhere St"
            ],
            "city": "Madison",
            "state": "WI",
            "postalCode": "53593"
          }
        ]
      },
      "search": {
        "mode": "match"
      }
```

```
    },
    {
      "resource": {
        "resourceType": "Practitioner",
        "id": "example-requester",
        "identifier": [
          {
            "system": "http://hl7.org/fhir/sid/us-npi",
            "value": "4069100012"
          }
        ],
        "name": [
          {
            "use": "usual",
            "family": "Requester",
            "given": [
              "Example"
            ]
          }
        ],
        "telecom": [
          {
            "system": "phone",
            "value": "803-903-1003",
            "use": "work"
          }
        ],
        "address": [
          {
            "line": [
              "456 Anywhere St"
            ],
            "city": "Madison",
            "state": "WI",
            "postalCode": "53593"
          }
        ]
      },
      "search": {
        "mode": "match"
      }
    }
  ]
},
"location": {
  "resourceType": "Bundle",
  "type": "searchset",
  "total": 1,
  "entry": [
    {
      "resource": {
        "resourceType": "Location",
        "id": "example-location",
        "status": "active",
        "type": [
          {
            "coding": [
              {
                "system": "https://www.cms.gov/Medicare/Coding/place-of-service-codes/Place_of_Service_Code_Set",
                "code": "49"
              },
              {
                "system": "http://hl7.org/fhir/us/davinci-crd/CodeSystem/temp",
                "code": "49"
              }
            ]
          }
        ],
        "identifier": [
          {
            "system": "http://hl7.org/fhir/sid/us-npi",
            "value": "4069110003"
          }
        ],
        "name": "Example Location",
        "managingOrganization": {
          "reference": "Organization/example-organization"
        },
        "telecom": [
          {
            "system": "phone",
            "value": "802-902-1002",
            "use": "work",
            "rank": 1
          },
          {
            "system": "phone",
            "value": "803-904-1004",
            "use": "work",
```

```
              "rank": 2
            }
          ],
          "address": {
            "line": [
              "456 Anywhere St"
            ],
            "city": "Madison",
            "state": "WI",
            "postalCode": "53593"
          }
        },
        "search": {
          "mode": "match"
        }
      }
    ]
  },
  "organization": {
    "resourceType": "Bundle",
    "type": "searchset",
    "total": 1,
    "entry": [
      {
        "resource": {
          "resourceType": "Organization",
          "id": "example-organization",
          "active": true,
          "identifier": [
            {
              "system": "http://hl7.org/fhir/sid/us-npi",
              "value": "4069110003"
            }
          ],
          "name": "Example Organization",
          "telecom": [
            {
              "system": "phone",
              "value": "802-902-1002",
              "use": "work",
              "rank": 1
            },
            {
              "system": "phone",
              "value": "803-904-1004",
              "use": "work",
              "rank": 2
            }
          ],
          "address": [
            {
              "line": [
                "456 Anywhere St"
              ],
              "city": "Madison",
              "state": "WI",
              "postalCode": "53593"
            }
          ]
        },
        "search": {
          "mode": "match"
        }
      }
    ]
  }
}
```


Sample response


```
{
  "cards": [],
  "systemActions": [
    {
      "type": "update",
      "resource": {
        "resourceType": "ServiceRequest",
        "id": "example-service-request",
        "extension": [
          {
            "extension": [
              {
                "valueCode": "covered",
                "url": "covered"
              },
              {
                "valueCode": "auth-needed",
                "url": "pa-needed"
```

```
          },
          {
            "valueReference": {
              "reference": "Coverage/coverage-resource"
            },
            "url": "coverage"
          },
          {
            "valueDate": "2026-02-01",
            "url": "date"
          },
          {
            "valueString": "CRDREF 31649",
            "url": "coverage-assertion-id"
          },
          {
            "valueCode": "clinical",
            "url": "doc-needed"
          },
          {
            "valueCode": "withpa",
            "url": "doc-purpose"
          },
          {
            "extension": [
              {
                "valueCodeableConcept": {
                  "coding": [
                    {
                      "system": "http://hl7.org/fhir/us/davinci-crd/CodeSystem/temp",
                      "code": "instructions-admin"
                    }
                  ]
                },
                "url": "code"
              },
              {
                "valueString": "This guidance assumes the billed performing provider will be Example Performer. This
 guidance assumes the billed date of service will be 2026-02-10, not 2026-02-01.",
                "url": "value"
              }
            ],
            "url": "detail"
          },
          {
            "extension": [
              {
                "valueCodeableConcept": {
                  "coding": [
                    {
                      "system": "http://hl7.org/fhir/us/davinci-crd/CodeSystem/temp",
                      "code": "instructions"
                    }
                  ]
                },
                "url": "code"
              },
              {
                "valueString": "You entered referred to details that are out-of-network. Services should be
performed in network whenever possible.",
                "url": "value"
              }
            ],
            "url": "detail"
          },
          {
            "valueDate": "2026-02-26",
            "url": "expiry-date"
          }
        ],
        "url": "http://hl7.org/fhir/us/davinci-crd/StructureDefinition/ext-coverage-information"
      }
    ],
    "status": "draft",
    "intent": "order",
    "code": {
      "coding": [
        {
          "system": "http://www.ama-assn.org/go/cpt",
          "code": "73722"
        }
      ]
    },
    "subject": {
      "reference": "Patient/example-crd-patient"
    },
    "authoredOn": "2026-01-01",
    "requester": {
      "reference": "Practitioner/example-requester",
```

```
          "display": "Example Requester"
        },
        "performer": [
          {
            "reference": "Practitioner/example-performer",
            "display": "Example Performer"
          }
        ],
        "locationReference": [
          {
            "reference": "Location/example-organization"
          }
        ]
      }
    }
  ]
}
```

14.1.20 Coverage Requirements Discovery Endpoint Discovery (R4)

File: site/apis/14-CMS-Incoming/1-R4/11279-Coverage-Requirements-Discovery-Endpoint-Discovery-R4.html
Epic API ID | 11279
FHIR version | R4
Categories | CMS Incoming
API type | Industry-Standard
USCDI | No
Supports OAuth 2.0 | True
Supported user types | Backend Systems and Non-OAuth 2.0
Performs scope validation | False
Source | https://fhir.epic.com/Specifications?api=11279

Description

This web service is only for use alongside the

Coverage Requirements Discovery

(CRD) service available with Epic's utilization management module for health plans and payers.

The Coverage Requirements Discovery Endpoint Discovery API allows a client to discover endpoints and prefetch queries to be used for the CRD service with a health plan or payer using Epic's utilization management module.

CRD is based on

the CDS Hooks standard

. Refer to the documentation for that standard for more information about the

CDS Hooks Discovery

endpoint this web service implements. For more information about CRD, refer to the

implementation guide published by the HL7® FHIR® Da Vinci Project for Coverage Requirements Discovery (STU 2.1)

Response elements

Name | Type | Optional | Array | Cardinality | Description
Coverage Requirements Discovery Endpoint Discovery - Response (R4) | Response | Required | | 1..1 | Information about available CRD services. See the CDS Hooks Discovery Response documentation for more information about this format.
Coverage Requirements Discovery Endpoint Discovery - Response (R4).services | $service | Required | Yes | 2..2 | List of CRD services.
Coverage Requirements Discovery Endpoint Discovery - Response (R4).services.description | String | Required | | 1..1 | The description of the CRD service.
Coverage Requirements Discovery Endpoint Discovery - Response (R4).services.hook | String | Required | | 1..1 | The CDS Hook that this service expects. The supported values are "order-sign" and "appointment-book".
Coverage Requirements Discovery Endpoint Discovery - Response (R4).services.id | String | Required | | 1..1 | The ID of the CRD service. This is appended to the cds-services path to form the endpoint URL for making CRD requests.
Coverage Requirements Discovery Endpoint Discovery - Response (R4).services.prefetch | $prefetch | Required | | | FHIR query templates used to prefetch FHIR resources for inclusion in CRD requests. The prefetch field is an object with keys defined by configuration within Epic and values containing FHIR query templates. The configurationDefinedKey field is a placeholder for these keys that are defined at runtime. For example, the prefetch object might contain keys "patient" and "coverage", each with string values holding FHIR query templates. There is not a key literally called "configurationDefinedKey".
Coverage Requirements Discovery Endpoint Discovery - Response (R4).services.prefetch.configurationDefinedKey | String | | | | FHIR query templates used to prefetch FHIR resources for inclusion in CRD requests.
Coverage Requirements Discovery Endpoint Discovery - Response (R4).services.title | String | Required | | 1..1 | The title of the CRD service.

Sample request

```
GET https://hostname/instance/api/epic/2024/HL7DaVinciCRD/CoverageRequirementsDiscovery/cds-services
```

Sample response

```
{
  "services": [
```

```
    {
      "hook": "order-sign",
      "title": "Coverage Requirement Discovery",
      "description": "This service allows payers to provide information about coverage requirement to providers at the
    time treatment decisions are being made.",
      "id": "CoverageRequirementsDiscovery",
      "prefetch": {
        "coverage": "Coverage?patient={{%context.patientId}}&status=active",
        "patient": "Patient/{{%context.patientId}}",
        "condition":
    "Condition?_id={{%context.draftOrders.entry.resource.reasonReference.resolve().ofType(Condition).id}}",
        "location":
    "Location?_id={{%context.appointments.entry.resource.participant.actor.resolve().ofType(Location).id}}",
        "medication": "Medication?_id={{%context.draftOrders.entry.resource.ofType(MedicationRequest).medicationReferenc
    e.resolve().ofType(Medication).id}}",
        "practitionerRole": "PractitionerRole?_id={{%context.draftOrders.entry.resource.requester.resolve().ofType(Pract
    itionerRole).id|%context.draftOrders.entry.resource.performer.resolve().ofType(PractitionerRole).id}}",
        "practitioner": "Practitioner?_id={{%context.draftOrders.entry.resource.requester.resolve().ofType(Practitioner)
    .id|%context.draftOrders.entry.resource.performer.resolve().ofType(Practitioner).id|%practitionerRole.entry.resource
    .practitioner.resolve().ofType(Practitioner).id}}",
        "organization": "Organization?_id={{%practitionerRole.entry.resource.organization.resolve().ofType(Organization)
    .id|%location.entry.resource.managingOrganization.resolve().ofType(Organization).id}}"
      }
    },
    {
      "hook": "appointment-book",
      "title": "Coverage Requirement Discovery",
      "description": "This service allows payers to provide information about coverage requirement to providers at the
    time treatment decisions are being made.",
      "id": "CoverageRequirementsDiscovery",
      "prefetch": {
        "patient": "Patient/{{%context.patientId}}",
        "coverage": "Coverage?patient={{%context.patientId}}&status=active",
        "condition": "Condition?_id={{%serviceRequest.entry.resource.reasonReference.resolve().ofType(Condition).id|%med
    icationRequest.entry.resource.reasonReference.resolve().ofType(Condition).id}}",
        "serviceRequest":
    "ServiceRequest?_id={{%context.appointments.entry.resource.basedOn.resolve().ofType(ServiceRequest).id}}",
        "medicationRequest":
    "MedicationRequest?_id={{%context.appointments.entry.resource.basedOn.resolve().ofType(MedicationRequest).id}}",
        "location": "Location?_id={{%context.appointments.entry.resource.participant.actor.resolve().ofType(Location).id
    |%serviceRequest.entry.resource.locationReference.resolve().ofType(Location).id}}",
        "medication":
    "Medication?_id={{%medicationRequest.entry.resource.medicationReference.resolve().ofType(Medication).id}}",
        "practitionerRole": "PractitionerRole?_id={{%context.appointments.entry.resource.participant.actor.resolve().ofT
    ype(PractitionerRole).id|%serviceRequest.entry.resource.requester.resolve().ofType(PractitionerRole).id|%medicationR
    equest.entry.resource.requester.resolve().ofType(PractitionerRole).id}}",
        "practitioner": "Practitioner?_id={{%context.appointments.entry.resource.participant.actor.resolve().ofType(Prac
    titioner).id|%serviceRequest.entry.resource.requester.resolve().ofType(Practitioner).id|%medicationRequest.entry.res
    ource.requester.resolve().ofType(Practitioner).id|%practitionerRole.entry.resource.practitioner.resolve().ofType(Pra
    ctitioner).id}}",
        "organization": "Organization?_id={{%practitionerRole.entry.resource.organization.resolve().ofType(Organization)
    .id|%location.entry.resource.managingOrganization.resolve().ofType(Organization).id}}"
      }
    }
  ]
}
```

14.1.21 Coverage.Read (Outside Record) (R4)

File: site/apis/14-CMS-Incoming/1-R4/11455-Coverage-Read-Outside-Record-R4.html
Epic API ID | 11455
FHIR version | R4
Categories | CMS Incoming
API type | USCDI
A la carte | Industry-Standard Level 1 API
USCDI | Yes
Available in inpatient and other contexts | Yes
HTTP method | GET
URL template | /api/FHIR/R4/Coverage/{ID}
Supports OAuth 2.0 | True
Supported user types | Backend Systems and Non-OAuth 2.0, Clinicians or Administrative Users, Patients
Performs scope validation | False
Source | https://fhir.epic.com/Specifications?api=11455

Description

Use this API to retrieve a specific instance of a patient's coverage. A single overall Coverage (Outside Record)

resource represent

s a patient's insurance or other payment coverage (policy/member-level coverage information) that systems use to determine who pays for care. It holds administrative details needed for matching and billing: identifiers, status, coverage type, subscriber/policyHolder/beneficiary relationships, coverage period, and payer information.

This API differs from other Coverage APIs because it returns data obtained as part of payer data exchange workflows rather than directly recorded during patient care. This data can come from payers or loaded from other FHIR servers. Because this data doesn't originate from the organization being queried, users of this API should be aware that the data might be unverified, incomplete, or duplicative.

This data is loaded from other FHIR servers and returned in the format the organization received it. Because of this, the documentation below is minimal. These resources can include any elements from the FHIR specification and can be distinguished from other resources by the presence of meta.tag set to

external-bulk-data

Request parameters

Name | Type | Optional | Array | Cardinality | Description
ID | token | Required | | | The Coverage FHIR ID.

Response elements

Name | Type | Optional | Array | Cardinality | Description
Coverage (R4) | Resource
Coverage (R4).beneficiary | Reference | | | 1..1 | Reference to a Patient resource for whom the coverage is relevant.
Coverage (R4).id | id | | | 1..1 | The unique FHIR ID representing the Coverage (Outside Record) resource.
Coverage (R4).meta | Meta | | | 1..1 | Metadata about the resource, including information about the origin or source of the data.
Coverage (R4).meta.tag | Coding | | Yes | 1..* | Set to external-bulk-data for resources originally loaded from another FHIR server. If this element is set to external-bulk-data, the resource content might vary and can include any elements allowed by the FHIR specification.

Sample request

```
GET https://hostname/instance/api/FHIR/R4/Coverage/fmQHQdu4tCYQdCF1kksc9-4D5ekQ6MJS7yKiry5GfHN84
```

Sample response

```
{
  "resourceType": "Coverage",
  "id": "fmQHQdu4tCYQdCF1kksc9-4D5ekQ6MJS7yKiry5GfHN84",
  "meta": {
    "tag": [
      {
        "system": "https://open.epic.com/FHIR/bulk-data-source",
        "code": "external-bulk-data",
        "display": "External Bulk Data"
      }
    ]
  },
  ... <r4 coverage="" compliant="" elements=""> ...
}</r4>
```

14.1.22 Coverage.Search (Outside Record) (R4)

File: site/apis/14-CMS-Incoming/1-R4/11456-Coverage-Search-Outside-Record-R4.html
Epic API ID | 11456
FHIR version | R4
Categories | CMS Incoming
API type | USCDI
A la carte | Industry-Standard Level 1 API
USCDI | Yes
Available in inpatient and other contexts | Yes
HTTP method | GET
URL template |
/api/FHIR/R4/Coverage?beneficiary={beneficiary}&patient={patient}&_count={_count}&_id={_id}&_include={_include}&_revinclude={_revinclude}
Supports OAuth 2.0 | True
Supported user types | Backend Systems and Non-OAuth 2.0, Clinicians or Administrative Users, Patients
Performs scope validation | False
Source | https://fhir.epic.com/Specifications?api=11456

Description

Use this API to search for coverage resources. A single overall Coverage (Outside Record)

resource represent

s a patient's insurance or other payment coverage (policy/member-level coverage information) that systems use to determine who pays for care. It holds administrative details needed for matching and billing: identifiers, status, coverage type, subscriber/policyHolder/beneficiary relationships, coverage period, and payer information.

This API differs from other Coverage APIs because it returns data obtained as part of payer data exchange workflows rather than directly recorded during patient care. This data can come from payers or loaded from other FHIR servers. Because this data doesn't originate from the organization being queried, users of this API should be aware that the data might be unverified, incomplete, or duplicative.

This data is loaded from other FHIR servers and returned in the format the organization received it. Because of this, the documentation below is minimal. These resources can include any elements from the FHIR specification and can be distinguished from other resources by the presence of meta.tag set to

external-bulk-data

Request parameters

Name | Type | Optional | Array | Cardinality | Description
_count | number | Optional | Yes | | Number of results per page.
_id | token | Optional | Yes | | FHIR resource IDs for the desired resources. Can be used in combination with _count, _include, and _revInclude. All others will be ignored.
_include | string | Optional | Yes | | Used to indicate which referenced resources to include in the search bundle.
_revinclude | string | Optional | Yes | | Used to include Provenance or AuditEvent resources that refer to search results, when available.
beneficiary | reference | Conditional | Yes | | Reference to a Patient resource whose coverage was documented. Either patient or beneficiary must be populated. If patient and beneficiary are both populated, they must be identical.
patient | reference | Conditional | Yes | | Reference to a Patient resource whose coverage was documented. Either patient or beneficiary must be populated. If patient and beneficiary are both populated, they must be identical.

Response elements

Name | Type | Optional | Array | Cardinality | Description
Coverage (R4) | Resource
Coverage (R4).beneficiary | Reference | | | 1..1 | Reference to a Patient resource for whom the coverage is relevant.
Coverage (R4).id | id | | | 1..1 | The unique FHIR ID representing the Coverage (Outside Record) resource.
Coverage (R4).meta | Meta | | | 1..1 | Metadata about the resource, including information about the origin or source of the data.
Coverage (R4).meta.tag | Coding | | Yes | 1..* | Set to external-bulk-data for resources originally loaded from another FHIR server. If this element is set to external-bulk-data, the resource content might vary and can include any elements allowed by the FHIR specification.

Sample request

```
GET https://hostname/instance/api/FHIR/R4/Coverage?patient=fmQHQdu4tCYQdCF1kksc9S7yKiry5GfHN65
```

Sample response

```
{
  "resourceType": "Bundle",
  "type": "searchset",
  "total": 1,
  "link": [
    {
      "relation": "self",
      "url": "https://hostname/instance/api/FHIR/R4/Coverage?patient=fmQHQdu4tCYQdCF1kksc9S7yKiry5GfHN65"
    }
  ],
  "entry": [
    {
      "link": [
        {
          "relation": "self",
          "url": "https://hostname/instance/api/FHIR/R4/Coverage/fmQHQdu4tCYQdCF1kksc9-4D5ekQ6MJS7yKiry5GfHN84"
        }
      ],
      "fullUrl": "https://hostname/instance/api/FHIR/R4/Coverage/fmQHQdu4tCYQdCF1kksc9-4D5ekQ6MJS7yKiry5GfHN84",
      "resource": {
        "resourceType": "Coverage",
        "id": "fmQHQdu4tCYQdCF1kksc9-4D5ekQ6MJS7yKiry5GfHN84",
        "meta": {
          "tag": [
            {
              "system": "https://open.epic.com/FHIR/bulk-data-source",
              "code": "external-bulk-data",
              "display": "External Bulk Data"
            }
          ]
        },
        ... <r4 coverage="" compliant="" elements=""> ...
    }
  ]
}</r4>
```

14.1.23 Device.Read (Outside Record) (R4)

File: site/apis/14-CMS-Incoming/1-R4/11459-Device-Read-Outside-Record-R4.html
Epic API ID | 11459
FHIR version | R4
Categories | CMS Incoming
API type | USCDI
A la carte | Industry-Standard Level 1 API
USCDI | Yes
Available in inpatient and other contexts | Yes

HTTP method | GET
URL template | /api/FHIR/R4/Device/{ID}
Supports OAuth 2.0 | True
Supported user types | Backend Systems and Non-OAuth 2.0, Clinicians or Administrative Users, Patients
Performs scope validation | False
Source | https://fhir.epic.com/Specifications?api=11459

Description

Use this API to retrieve details about a device for a patient. A single Device (Outside Record) resource represents an individual's implantable device (such as a defibrillator) or non-implantable device (such as a motorized wheelchair).

This API differs from other Device APIs because it returns data obtained as part of payer data exchange workflows rather than directly recorded during patient care. This data can come from payers or loaded from other FHIR servers. Because this data doesn't originate from the organization being queried, users of this API should be aware that the data might be unverified, incomplete, or duplicative.

This data is loaded from other FHIR servers and returned in the format the organization received it. Because of this, the documentation below is minimal. These resources can include any elements from the FHIR specification and can be distinguished from other resources by the presence of meta.tag set to

external-bulk-data

Request parameters

Name | Type | Optional | Array | Cardinality | Description
ID | token | Required | | | The Device FHIR ID.

Response elements

Name | Type | Optional | Array | Cardinality | Description
Device (R4) | Resource
Device (R4).id | id | | | 1..1 | The unique FHIR ID representing the Device (Outside Record) resource.
Device (R4).meta | Meta | | | 1..1 | Metadata about the resource, including information about the origin or source of the data.
Device (R4).meta.tag | Coding | | Yes | 1..* | Set to external-bulk-data for resources originally loaded from another FHIR server. If this element is set to external-bulk-data, the resource content might vary and can include any elements allowed by the FHIR specification.
Device (R4).patient | Reference | | | 1..1 | Reference to a Patient resource for whom the device is relevant.

Sample request

```
GET https://hostname/instance/api/FHIR/R4/Device/fFjg6-hXbajcw3cSBY5kW1hc-
    rtU3RMBIrgAYMwRDbDT6Y6c07avWCIQ2-8VJKbdxGmLmRpWP7Fwpy3jcd8UqMw4
```

Sample response

```
{
  "resourceType": "Device",
  "id": "fFjg6-hXbajcw3cSBY5kW1hc-rtU3RMBIrgAYMwRDbDT6Y6c07avWCIQ2-8VJKbdxGmLmRpWP7Fwpy3jcd8UqMw4",
  "meta": {
    "profile": [
      "http://hl7.org/fhir/us/core/StructureDefinition/us-core-implantable-device"
    ],
    "tag": [
      {
        "system": "https://open.epic.com/FHIR/bulk-data-source",
        "code": "external-bulk-data",
        "display": "External Bulk Data"
      }
    ]
  },
    ... <r4 device="" compliant="" elements=""> ...
}</r4>
```

14.1.24 Device.Search (Outside Record) (R4)

File: site/apis/14-CMS-Incoming/1-R4/11460-Device-Search-Outside-Record-R4.html
Epic API ID | 11460
FHIR version | R4
Categories | CMS Incoming
API type | USCDI
A la carte | Industry-Standard Level 1 API
USCDI | Yes
Available in inpatient and other contexts | Yes
HTTP method | GET
URL template | /api/FHIR/R4/Device?device-name={device-name}&manufacturer={manufacturer}&model={model}&patient={patient}&udi-carrier={udi-carrier}&udi-di={udi-di}&_count={_count}&_id={_id}&_include={_include}&_revinclude={_revinclude}
Supports OAuth 2.0 | True
Supported user types | Backend Systems and Non-OAuth 2.0, Clinicians or Administrative Users, Patients
Performs scope validation | False

Source | https://fhir.epic.com/Specifications?api=11460

Description

Use this API to search for Device resources. A single Device (Outside Record) resource represents an individual's implantable device (such as a defibrillator) or non-implantable device (such as a motorized wheelchair).

This API differs from other Device APIs because it returns data obtained as part of payer data exchange workflows rather than directly recorded during patient care. This data can come from payers or loaded from other FHIR servers. Because this data doesn't originate from the organization being queried, users of this API should be aware that the data might be unverified, incomplete, or duplicative.

This data is loaded from other FHIR servers and returned in the format the organization received it. Because of this, the documentation below is minimal. These resources can include any elements from the FHIR specification and can be distinguished from other resources by the presence of meta.tag set to

external-bulk-data

Request parameters

Name | Type | Optional | Array | Cardinality | Description
_count | number | Optional | Yes | | Number of results per page.
_id | token | Optional | Yes | | FHIR resource IDs for the desired resources. Can be used in combination with _count, _include, and _revInclude. All others will be ignored.
_include | string | Optional | Yes | | Used to indicate which referenced resources to include in the search bundle.
_revinclude | string | Optional | Yes | | Used to include Provenance or AuditEvent resources that refer to search results, when available.
patient | reference | Required | Yes | | A FHIR ID representing the Patient who has the Device.

Response elements

Name | Type | Optional | Array | Cardinality | Description
Device (R4) | Resource
Device (R4).id | id | | | 1..1 | The unique FHIR ID representing the Device (Outside Record) resource.
Device (R4).meta | Meta | | | 1..1 | Metadata about the resource, including information about the origin or source of the data.
Device (R4).meta.tag | Coding | | Yes | 1..* | Set to external-bulk-data for resources originally loaded from another FHIR server. If this element is set to external-bulk-data, the resource content might vary and can include any elements allowed by the FHIR specification.
Device (R4).patient | Reference | | | 1..1 | Reference to a Patient resource for whom the device is relevant.

Sample request

```
GET https://hostname/instance/api/FHIR/R4/Device?patient=eKpwAQhoV6s9woTj1Y8Gziw3
```

Sample response

```
{
  "resourceType": "Bundle",
  "type": "searchset",
  "total": 1,
  "link": [
    {
      "relation": "self",
      "url": "https://hostname/instance/api/FHIR/R4/Device?patient=eKpwAQhoV6s9woTj1Y8Gziw3"
    }
  ],
  "entry": [
    {
      "link": [
        {
          "relation": "self",
          "url": "https://hostname/instance/api/FHIR/R4/Device/fFjg6-hXbajcw3cSBY5kW1hc-
    rtU3RMBIrgAYMwRDbDT6Y6c07avWCIQ2-8VJKbdxGmLmRpWP7Fwpy3jcd8UqMw4"
        }
      ],
      "fullUrl": "https://hostname/instance/api/FHIR/R4/Device/fFjg6-hXbajcw3cSBY5kW1hc-
    rtU3RMBIrgAYMwRDbDT6Y6c07avWCIQ2-8VJKbdxGmLmRpWP7Fwpy3jcd8UqMw4",
      "resource": {
        "resourceType": "Device",
        "id": "fFjg6-hXbajcw3cSBY5kW1hc-rtU3RMBIrgAYMwRDbDT6Y6c07avWCIQ2-8VJKbdxGmLmRpWP7Fwpy3jcd8UqMw4",
        "meta": {
          "tag": [
            {
              "system": "https://open.epic.com/FHIR/bulk-data-source",
              "code": "external-bulk-data",
              "display": "External Bulk Data"
            }
          ]
        },
      ... <r4 device="" compliant="" elements=""> ...
      },
      "search": {
        "mode": "match"
      }
    }
```

```
  ]
}</r4>
```

14.1.25 DiagnosticReport.Read (Outside Record Results) (R4)

File: site/apis/14-CMS-Incoming/1-R4/11372-DiagnosticReport-Read-Outside-Record-Results-R4.html
Epic API ID | 11372
FHIR version | R4
Categories | CMS Incoming
API type | USCDI
A la carte | Industry-Standard Level 1 API
USCDI | Yes
Available in inpatient and other contexts | Yes
HTTP method | GET
URL template | /api/FHIR/R4/DiagnosticReport/{ID}
Supports OAuth 2.0 | True
Supported user types | Backend Systems and Non-OAuth 2.0, Clinicians or Administrative Users, Patients
Performs scope validation | False
Source | https://fhir.epic.com/Specifications?api=11372

Description

Use this API to retrieve a specific instance of a patient's

laboratory test results, diagnostic reports, and notes

. A diagnostic report is defined by the findings and interpretation of diagnostic tests performed on patients.

This API differs from other DiagnosticReport APIs because it returns data obtained as part of payer data exchange workflows rather than directly recorded during patient care. This data can come from payers, providers, or loaded from other FHIR servers. Because this data doesn't originate from the organization being queried, users of this API should be aware that the data might be unverified, incomplete, or duplicative.

Data from outside payer and provider systems is saved to an organization's database and returned in a standard format, documented below. Data loaded from other FHIR servers is returned in the format the organization received it. Because of this, the documentation below does not apply to these loaded resources. These resources can include any elements from the FHIR specification and can be distinguished from other resources by the presence of meta.tag set to “external-bulk-data".

Request parameters

Name | Type | Optional | Array | Cardinality | Description
ID | token | Required | | | The DiagnosticReport FHIR ID.

Response elements

Name | Type | Optional | Array | Cardinality | Description
DiagnosticReport (R4) | DiagnosticReport
DiagnosticReport (R4).category | CodeableConcept | | Yes | 1..* | The Epic result type is always returned, and US Core Category Code is also returned if the order matches one of the categories. All results include a custom category of "external-diagnosticreport" code: external-diagnosticreport system: http://open.epic.com/FHIR/StructureDefinition/DiagnosticReport-category Additionally, results include a custom category based on the Epic Result Type if present: code: category abbreviation system: oid:1.2.840.114350.1.72.1.7.7.10.688882.5007 The US Core Category and LOINC Codes are based on: Epic Result Type Epic Lab Result Type Epic Result Image Type US Core Laboratory code: LAB system: http://terminology.hl7.org/CodeSystem/v2-0074 Epic Result Type Abbreviation: Lab Epic Lab Result Type Abbreviation: Gen Path CytoPath LOINC Pathology: code: LP7839-6 system: http://loinc.org Epic Lab Result Type Abbreviation: Anatomic Pathology - General Anatomic Pathology - Cytology LOINC Cardiology: code: LP29708-2 system: http://loinc.org Epic Result Type Abbreviation: ECG Epic Result Type Abbreviation: Image AND Epic Result Image Type: Cupid LOINC Radiology: code: LP29684-5 system: http://loinc.org Epic Result Type Abbreviation: Image AND Epic Result Image Type Abbreviation: Lumens
DiagnosticReport (R4).code | CodeableConcept | | | 1..1 | The LOINC code pertaining to the Diagnostic Report.
DiagnosticReport (R4).effectiveDateTime | dateTime | | | 0..1 | Clinically relevant date and, if available, the time associated with the report.
DiagnosticReport (R4).encounter | Reference | | | 0..1 | Encounter when the test was ordered.
DiagnosticReport (R4).id | id | | | | The unique FHIR ID for a DiagnosticReport (Outside Record Results) resource.
DiagnosticReport (R4).issued | instant | | | 0..1 | Date and time the Diagnostic Report was released. This element is populated only when both the date and time are available.
DiagnosticReport (R4).meta | Meta | | | | Metadata about the resource, including information about the origin or source of the data.
DiagnosticReport (R4).meta.tag | Coding | | Yes | | Set to external-bulk-data for resources originally loaded from another FHIR server. If this element is set to external-bulk-data, all other element-level documentation does not apply to the resource. The resource content might vary and can include any elements allowed by the FHIR specification.
DiagnosticReport (R4).performer | Reference | | Yes | 0..* | Participants in producing the report. This can include one or more references to the Practitioner resource. This element can also include a reference to an Organization resource. These would be display only references.
DiagnosticReport (R4).result | Reference | | Yes | 0..* | References to the Observation resources representing the result components for the DiagnosticReport.
DiagnosticReport (R4).specimen | Reference | | Yes | 0..* | Reference to the specimens this report is based on.
DiagnosticReport (R4).status | code | | | 1..1 | The status of the report. These values can be returned: registered preliminary final amended unknown If a test was performed but ended in an unsuccessful attempt, the status is cancelled. Cancelled results are not returned.
DiagnosticReport (R4).subject | Reference | | | 1..1 | A reference to the Patient resource representing the subject of the report.

Sample request

```
GET https://hostname/instance/api/FHIR/R4/DiagnosticReport/fKP.tRDTVjMBv5s41y-0L9Nux4H..qnznLtVdG99fE2I4
```

Sample response


```
{
  "resourceType": "DiagnosticReport",
  "id": "fKP.tRDTVjMBv5s41y-0L9Nux4H..qnznLtVdG99fE2I4",
  "status": "final",
  "category": [
    {
      "coding": [
        {
          "system": "http://open.epic.com/FHIR/StructureDefinition/DiagnosticReport-category",
          "code": "external-diagnosticreport",
          "display": "External DiagnosticReport"
        }
      ],
      "text": "External DiagnosticReport"
    },
    {
      "coding": [
        {
          "system": "urn:oid:1.2.840.114350.1.72.1.7.7.10.688882.5007",
          "code": "Lab",
          "display": "Lab"
        }
      ],
      "text": "Lab"
    },
    {
      "coding": [
        {
          "system": "http://terminology.hl7.org/CodeSystem/v2-0074",
          "code": "LAB",
          "display": "Laboratory"
        }
      ],
      "text": "Laboratory"
    }
  ],
  "code": {
    "coding": [
      {
        "system": "http://loinc.org",
        "code": "58410-2",
        "display": "CBC panel - Blood by Automated count"
      }
    ],
    "text": "CBC panel - Blood by Automated count"
  },
  "subject": {
    "reference": "Patient/evRwJC6.5LnESOKh7C776cg3",
    "display": "FHIR, Test Patient"
  },
  "effectiveDateTime": "2025-07-17T16:55:00Z",
  "issued": "2025-07-17T16:55:00Z",
  "encounter": {
    "reference": "Encounter/e7XpQk-9RLMtvy24js8GbHdWknoZCFURhVx1bTG.qkdm3",
    "display": "Office Visit"
  },
  "performer": [
    {
      "type": "Practitioner",
      "display": "FHIR, Test Provider MD"
    }
  ],
  "specimen": [
    {
      "reference": "Specimen/f3VdBd-1NEXlzm53zw5qogfFqhpAIKYMqNa5aCH.awlw4",
      "display": "Whole blood"
    }
  ],
  "result": [
    {
      "reference": "Observation/fKP.tRDTVjMBv5s41y-0L9NaecsPsXuU7vz1rGQ-apfY4",
      "display": "Glucose"
    },
    {
      "reference": "Observation/fKP.tRDd2114531453-0L9NaecsPsXuU7vz1rGQ-apfZ4",
      "display": "Blood Urea Nitrogen"
    }
  ]
}
```


14.1.26 DiagnosticReport.Search (Outside Record Results) (R4)

File: site/apis/14-CMS-Incoming/1-R4/11378-DiagnosticReport-Search-Outside-Record-Results-R4.html
Epic API ID | 11378
FHIR version | R4
Categories | CMS Incoming
API type | USCDI
A la carte | Industry-Standard Level 1 API
USCDI | Yes
Available in inpatient and other contexts | Yes
HTTP method | GET
URL template | /api/FHIR/R4/DiagnosticReport?category={category}&code={code}&date={date}&identifier={identifier}&patient={patient}&subject={subject}&_count={_count}&_id={_id}&_include={_include}&_revinclude={_revinclude}
Supports OAuth 2.0 | True
Supported user types | Backend Systems and Non-OAuth 2.0, Clinicians or Administrative Users, Patients
Performs scope validation | False
Source | https://fhir.epic.com/Specifications?api=11378

Description

Use this API to search for a patient's laboratory test results, diagnostic reports, and notes. A diagnostic report is defined by the findings and interpretation of diagnostic tests performed on patients.

This API differs from other DiagnosticReport APIs because it returns data obtained as part of payer data exchange workflows rather than directly recorded during patient care. This data can come from payers, providers, or loaded from other FHIR servers. Because this data doesn't originate from the organization being queried, users of this API should be aware that the data might be unverified, incomplete, or duplicative.

Data from outside payer and provider systems is saved to an organization's database and returned in a standard format, documented below. Data loaded from other FHIR servers is returned in the format the organization received it. Because of this, the documentation below does not apply to these loaded resources. These resources can include any elements from the FHIR specification and can be distinguished from other resources by the presence of meta.tag set to “external-bulk-data".

Request parameters

Name | Type | Optional | Array | Cardinality | Description
_count | number | Optional | Yes | | Number of results per page.
_id | token | Optional | Yes | | FHIR resource IDs for the desired resources. Can be used in combination with _count, _include, and _revInclude. All other search parameters are ignored.
_include | string | Optional | Yes | | Used to indicate which referenced resources to include in the search bundle.
_revinclude | string | Optional | Yes | | Used to include Provenance or AuditEvent resources that refer to search results, when available.
category | token | Optional | Yes | | The service category. This can be either an Epic result type or a value from the US Core valueset for DiagnosticReport. For the category system of "http://loinc.org", supported codes are: Cardiology: LP29708-2 Pathology: LP7839-6 Radiology: LP29684-5 For the category system of "http://terminology.hl7.org/CodeSystem/v2-0074", a code of LAB is supported. This parameter is formatted with or without a system specified (code=[code] or code=[system]|[code]). If specifying a system, the corresponding code must be provided.
code | token | Optional | Yes | | The code for the DiagnosticReport. This can only be LOINC codes. This parameter is formatted with a system specified (code=[system]|[code]). The system can only be "http://loinc.org".
date | date | Optional | Yes | | Clinically relevant time/time period for report. Matches to the effectiveDateTime response element.
patient | reference | Required | Yes | | The FHIR ID of the Patient for the DiagnosticReport.

Request parameters (post-filtered search parameters)

Name | Type | Optional | Array | Cardinality | Description
issued | date | Optional | Yes | | DateTime the version of this result was released.
result | reference | Optional | Yes | | The Observation resource FHIR ID within a DiagnosticReport.
specimen | reference | Optional | Yes | | The Specimen resource FHIR ID within a DiagnosticReport.
status | token | Optional | Yes | | The status of the report. The following statuses are supported: registered preliminary final amended unknown

Response elements

Name | Type | Optional | Array | Cardinality | Description
DiagnosticReport (R4) | DiagnosticReport
DiagnosticReport (R4).category | CodeableConcept | | Yes | 1..* | The Epic result type is always returned, and US Core Category Code is also returned if the order matches one of the categories. All results include a custom category of "external-diagnosticreport" code: external-diagnosticreport system: http://open.epic.com/FHIR/StructureDefinition/DiagnosticReport-category Additionally, results include a custom category based on the Epic Result Type if present: code: category abbreviation system: oid:1.2.840.114350.1.72.1.7.7.10.688882.5007 The US Core Category and LOINC Codes are based on: Epic Result Type Epic Lab Result Type Epic Result Image Type US Core Laboratory code: LAB system: http://terminology.hl7.org/CodeSystem/v2-0074 Epic Result Type Abbreviation: Lab Epic Lab Result Type Abbreviation: Gen Path CytoPath LOINC Pathology: code: LP7839-6 system: http://loinc.org Epic Lab Result Type Abbreviation: Anatomic Pathology - General Anatomic Pathology - Cytology LOINC Cardiology: code: LP29708-2 system: http://loinc.org Epic Result Type Abbreviation: ECG Epic Result Type Abbreviation: Image AND Epic Result Image Type: Cupid LOINC Radiology: code: LP29684-5 system: http://loinc.org Epic Result Type Abbreviation: Image AND Epic Result Image Type Abbreviation: Lumens
DiagnosticReport (R4).code | CodeableConcept | | | 1..1 | The LOINC code pertaining to the Diagnostic Report.
DiagnosticReport (R4).effectiveDateTime | dateTime | | | 0..1 | Clinically relevant date and, if available, the time associated with the report.
DiagnosticReport (R4).encounter | Reference | | | 0..1 | Encounter when the test was ordered.
DiagnosticReport (R4).id | id | | | 1..1 | The unique FHIR ID for a DiagnosticReport (Outside Record Results) resource.

DiagnosticReport (R4).issued | instant | | | 0..1 | Date and time the Diagnostic Report was released. This element is populated only when both the date and time are available.

DiagnosticReport (R4).meta | Meta | | | | Metadata about the resource, including information about the origin or source of the data.

DiagnosticReport (R4).meta.tag | Coding | | Yes | | Set to external-bulk-data for resources originally loaded from another FHIR server. If this element is set to external-bulk-data, all other element-level documentation does not apply to the resource. The resource content might vary and can include any elements allowed by the FHIR specification.

DiagnosticReport (R4).performer | Reference | | Yes | 0..* | Participants in producing the report. This can include one or more references to the Practitioner resource. This element can also include a reference to an Organization resource. These would be display only references.

DiagnosticReport (R4).result | Reference | | Yes | 0..* | References to the Observation resources representing the result components for the DiagnosticReport.

DiagnosticReport (R4).specimen | Reference | | Yes | 0..* | Reference to the specimens this report is based on.

DiagnosticReport (R4).status | code | | | 1..1 | The status of the report. These values can be returned: registered preliminary final amended unknown If a test was performed but ended in an unsuccessful attempt, the status is cancelled. Cancelled results are not returned.

DiagnosticReport (R4).subject | Reference | | | 1..1 | A reference to the Patient resource representing the subject of the report.

Sample request

```
GET https://hostname/instance/api/FHIR/R4/DiagnosticReport?patient=eOnL4Yt6VrgqISeMmWRqghA3&category=external-
    diagnosticreport
```

Sample response


```
{
  "resourceType": "Bundle",
  "type": "searchset",
  "total": 2,
  "link": [
    {
      "relation": "self",
      "url": "https://hostname/instance/api/FHIR/R4/DiagnosticReport?category=external-
    diagnosticreport&patient=eOnL4Yt6VrgqISeMmWRqghA3"
    }
  ],
  "entry": [
    {
      "link": [
        {
          "relation": "self",
          "url": "https://hostname/instance/api/FHIR/R4/DiagnosticReport/fmrDecIGNJuYS30tOxIFpvJbwaBu7FsVhPRxzQrwVxLo4"
        }
      ],
      "fullUrl": "
    https://hostname/instance/api/FHIR/R4/DiagnosticReport/fmrDecIGNJuYS30tOxIFpvJbwaBu7FsVhPRxzQrwVxLo4",
      "resource": {
        "resourceType": "DiagnosticReport",
        "id": "fmrDecIGNJuYS30tOxIFpvJbwaBu7FsVhPRxzQrwVxLo4",
        "status": "final",
        "category": [
          {
            "coding": [
              {
                "system": "http://open.epic.com/FHIR/StructureDefinition/DiagnosticReport-category",
                "code": "external-diagnosticreport",
                "display": "External DiagnosticReport"
              }
            ],
            "text": "External DiagnosticReport"
          },
          {
            "coding": [
              {
                "system": "urn:oid:1.2.840.114350.1.72.1.7.7.10.688882.5007",
                "code": "Image",
                "display": "Image"
              }
            ],
            "text": "Image"
          },
          {
            "coding": [
              {
                "system": "http://loinc.org",
                "code": "LP29684-5",
                "display": "Radiology"
              }
            ],
            "text": "Radiology"
          }
        ],
        "code": {
          "coding": [
            {
              "system": "http://loinc.org",
              "code": "24605-8",
              "display": "Lume Colonoscopy"
            }
```

```
      ],
      "text": "Lume Colonoscopy"
    },
    "subject": {
      "reference": "Patient/eOnL4Yt6VrgqISeMmWRqghA3",
      "display": "FHIR, Test Patient"
    },
    "encounter": {
      "reference": "Encounter/fODy91O9P--YCWpVymDy4UYEpALun.VB.BxEAVZxfgGQ4"
    },
    "effectiveDateTime": "2024-05-30T23:52:00Z",
    "issued": "2024-05-30T23:52:00Z",
    "performer": [
      {
        "type": "Practitioner",
        "display": "FHIR, Test Provider MD"
      }
    ],
    "specimen": [
      {
        "reference": "Specimen/f5GmSdk83Q5-SOlt9gloRtXnDQHoyHqkXh1lUcLLI7Xk4"
      }
    ]
  },
  "search": {
    "mode": "match"
  }
},
{
  "link": [
    {
      "relation": "self",
      "url": " https://hostname/instance/api/FHIR/R4/DiagnosticReport/f6M5jmLlzKHbxJh74JG14hLaTezKZ92Nmn48QOFdXC0A4"
    }
  ],
  "fullUrl": "
https://hostname/instance/api/FHIR/R4/DiagnosticReport/f6M5jmLlzKHbxJh74JG14hLaTezKZ92Nmn48QOFdXC0A4",
  "resource": {
    "resourceType": "DiagnosticReport",
    "id": "f6M5jmLlzKHbxJh74JG14hLaTezKZ92Nmn48QOFdXC0A4",
    "status": "final",
    "category": [
      {
        "coding": [
          {
            "system": "http://open.epic.com/FHIR/StructureDefinition/DiagnosticReport-category",
            "code": "external-diagnosticreport",
            "display": "External DiagnosticReport"
          }
        ],
        "text": "External DiagnosticReport"
      },
      {
        "coding": [
          {
            "system": "urn:oid:1.2.840.114350.1.72.1.7.7.10.688882.5007",
            "code": "Lab",
            "display": "Lab"
          }
        ],
        "text": "Lab"
      },
      {
        "coding": [
          {
            "system": "http://terminology.hl7.org/CodeSystem/v2-0074",
            "code": "LAB",
            "display": "Laboratory"
          }
        ],
        "text": "Laboratory"
      }
    ],
    "code": {
      "coding": [
        {
          "system": "http://loinc.org",
          "code": "58410-2",
          "display": "CBC panel - Blood by Automated count"
        }
      ],
      "text": "CBC panel - Blood by Automated count"
    },
    "subject": {
      "reference": "Patient/eOnL4Yt6VrgqISeMmWRqghA3",
      "display": "FHIR, Test Patient"
    },
    "encounter": {
      "reference": "Encounter/fODy91O9P--YCWpVymDy4UVW5d9TcjKpPrleLY6Uq9MA4"
```

```
        },
        "effectiveDateTime": "2024-01-05",
        "performer": [
          {
            "type": "Practitioner",
            "display": "FHIR, Test Provider MD"
          }
        ],
        "specimen": [
          {
            "reference": "Specimen/fPa3aLhi7I-jshaWYPx99ZOfDhFC4De7YxhzmLcYjTRc4",
            "display": "Blood - EDTA"
          }
        ],
        "result": [
          {
            "reference": "Observation/fKP.tRDTVjMBv5s41y-0L9NaecsPsXuU7vz1rGQ-apfY4",
            "display": "Glucose"
          },
          {
            "reference": "Observation/fKP.tRDd2114531453-0L9NaecsPsXuU7vz1rGQ-apfZ4",
            "display": "Blood Urea Nitrogen"
          }
        ]
      },
      "search": {
        "mode": "match"
      }
    }
  ]
}
```


14.1.27 DocumentReference.Read (Prior Auth Supporting Info) (R4)

File: site/apis/14-CMS-Incoming/1-R4/11399-DocumentReference-Read-Prior-Auth-Supporting-Info-R4.html
Epic API ID | 11399
FHIR version | R4
Categories | CMS Incoming
API type | Industry-Standard
API group | Prior Auth Supporting Info Document Group
USCDI | No
Available in inpatient and other contexts | Yes
HTTP method | GET
URL template | /api/FHIR/R4/DocumentReference/{ID}
Supports OAuth 2.0 | True
Supported user types | Backend Systems and Non-OAuth 2.0, Clinicians or Administrative Users, Patients
Performs scope validation | False
Source | https://fhir.epic.com/Specifications?api=11399

Description

Use this API to retrieve a specific DocumentReference (Prior Auth Supporting Info) resource. This resource represents unstructured clinical documents submitted by providers in support of a prior authorization request. This API is available for provider-facing and backend applications and is not exposed to patient-facing applications.

The API can retrieve documents for prior authorizations processed directly by the organization as well as documents for prior authorizations received from external payers through payer data exchange workflows.

Data loaded from other FHIR servers is returned in the format the organization received it. Because of this, the documentation below does not apply to these loaded resources. These resources can include any elements from the FHIR specification and can be distinguished from other resources by the presence of meta.tag set to

external-bulk-data

When used as part of the CMS Payer-to-Payer API, only supporting information for approved prior authorizations is returned. In other interoperability scenarios, supporting information for both approved and denied prior authorizations can be returned.

Request parameters

Name | Type | Optional | Array | Cardinality | Description
ID | token | Required | | | DocumentReference FHIR ID.

Response elements

Name | Type | Optional | Array | Cardinality | Description
DocumentReference (R4) | DocumentReference | | | | An instance of the R4 DocumentReference resource.
DocumentReference (R4).category | CodeableConcept | | Yes | 1..1 | Categorization of the document. For DocumentReference (Prior Auth Supporting Info) resources, this is always "clinical-note".
DocumentReference (R4).content | BackboneElement | | Yes | 1..* | Given a Binary FHIR ID for prior authorization supporting information, this web service returns an HTML or RTF version of the note.

DocumentReference (R4).content.attachment | Attachment | | | 1..1 | A reference to a Binary FHIR resource that contains the note's content or the content of the scanned document.
DocumentReference (R4).content.attachment.contentType | String | | | 1..1 | MIME content type for this version of the note. This is either text/html for HTML or text/rtf for Rich Text Format for text.
DocumentReference (R4).content.attachment.url | String | | | 1..1 | Reference to Binary FHIR resource that contains the note's content.
DocumentReference (R4).content.format | Coding | | | 1..1 | Always "mimetype Sufficient" system: "http://ihe.net/fhir/ValueSet/IHE.FormatCode.codesystem" code: "urn:ihe:iti:xds:2017:mimeTypeSufficient"
DocumentReference (R4).context | BackboneElement | | | 0..1 | Pointer to the document information record associated with this note.
DocumentReference (R4).context.related | Reference | | Yes | 1..1 | Related information associated with this note.
DocumentReference (R4).context.related.reference | String | | | 1..1 | DocumentReference for the document related to this note.
DocumentReference (R4).date | instant | | | 0..1 | Date and time when this note was created.
DocumentReference (R4).id | id | | | 1..1 | The DocumentReference FHIR ID.
DocumentReference (R4).meta | Meta | | | | Metadata about the resource, including information about the origin or source of the data.
DocumentReference (R4).meta.tag | Coding | | Yes | | Set to external-bulk-data for resources originally loaded from another FHIR server. If this element is set to external-bulk-data, all other element-level documentation does not apply to the resource. The resource content might vary and can include any elements allowed by the FHIR specification.
DocumentReference (R4).status | code | | | 1..1 | The status of this DocumentReference. This is always "current".
DocumentReference (R4).subject | Reference | | | 1..1 | The patient or member that is the subject of the document.

Sample request

```
GET https://hostname/instance/api/FHIR/R4/DocumentReference/ftuGV6WiAOINAuDnKEgeKDg4
```

Sample response


```
{
  "resourceType": "DocumentReference",
  "id": "ftuGV6WiAOINAuDnKEgeKDg4",
  "status": "current",
  "category": [
    {
      "coding": [
        {
          "system": "http://hl7.org/fhir/us/core/CodeSystem/us-core-documentreference-category",
          "code": "clinical-note"
        }
      ]
    }
  ],
  "subject": {
    "reference": "Patient/eMyQoQ6-E-PRP3Fkge4K0mA3",
    "display": "Patient, Test"
  },
  "content": [
    {
      "attachment": {
        "contentType": "text/html",
        "url": "Binary/fbSaJYwtiyiGEGIsurzCN3g4"
      },
      "format": {
        "system": "http://ihe.net/fhir/ValueSet/IHE.FormatCode.codesystem",
        "code": "urn:ihe:iti:xds:2017:mimeTypeSufficient",
        "display": "mimeType Sufficient"
      }
    }
  ]
}
```


14.1.28 Goal.Read (Outside Record) (R4)

File: site/apis/14-CMS-Incoming/1-R4/11411-Goal-Read-Outside-Record-R4.html
Epic API ID | 11411
FHIR version | R4
Categories | CMS Incoming
API type | USCDI
A la carte | Industry-Standard Level 1 API
USCDI | Yes
Available in inpatient and other contexts | Yes
HTTP method | GET
URL template | /api/FHIR/R4/Goal/{ID}
Supports OAuth 2.0 | True
Supported user types | Backend Systems and Non-OAuth 2.0, Clinicians or Administrative Users, Patients
Performs scope validation | False
Source | https://fhir.epic.com/Specifications?api=11411

Description

Use this API to retrieve a specific instance of a patient goal. This FHIR resource represents outcomes or conditions to be achieved in the process of patient care.

The data returned by this API includes outpatient care goals. This API does not return care plan goals, clinical pathways, or inpatient care goals.

This API differs from other Goal APIs because it returns data that was obtained as part of payer data exchange workflows rather than directly recorded during patient care. This data can come from payers, providers, or loaded from other FHIR servers. Because this data doesn't originate from the organization being queried, users of this API should be aware that the data might be unverified, incomplete, or duplicative.

Data from outside payer and provider systems is saved to an organization's database and returned in a standard format, documented below. Data loaded from other FHIR servers is returned in the format the organization received it. Because of this, the documentation below does not apply to these loaded resources. These resources can include any elements from the FHIR specification and can be distinguished from other resources by the presence of meta.tag set to "external-bulk-data".

Request parameters

Name | Type | Optional | Array | Cardinality | Description
ID | token | Required | | | FHIR ID of the Goal resource.

Response elements

Name | Type | Optional | Array | Cardinality | Description
Goal (R4) | Goal | | | | A single Goal resource.
Goal (R4).description | CodeableConcept | | | 1..1 | The Goal description. This is often represented by a SNOMED code, but it might be a code from a different code system. System (SNOMED): http://snomed.info/sct
Goal (R4).id | id | | | 1..1 | The unique FHIR ID for the Goal resource.
Goal (R4).lifecycleStatus | code | | | 1..1 | The state of the Goal throughout its lifecycle. This is always active
Goal (R4).meta | Meta | | | | Metadata about the resource, including information about the origin or source of the data.
Goal (R4).meta.tag | Coding | | Yes | | Set to external-bulk-data for resources originally loaded from another FHIR server. If this element is set to external-bulk-data, all other element-level documentation does not apply to the resource. The resource content might vary and can include any elements allowed by the FHIR specification.
Goal (R4).startDate | date | | | 0..1 | When Goal pursuit begins.
Goal (R4).subject | Reference | | | 1..1 | A reference to the Patient resource representing the subject for whom this Goal is intended.

Sample request

```
GET https://hostname/instance/api/FHIR/R4/Goal/fdhGDoKZTXQaY9NQl3JcQqU7kGnL6UmrUibgDE2dQBSA4
```

Sample response

```
{
  "resourceType": "Goal",
  "id": "fdhGDoKZTXQaY9NQl3JcQqU7kGnL6UmrUibgDE2dQBSA4",
  "lifecycleStatus": "active",
  "description": {
    "coding": [
      {
        "system": "http://snomed.info/sct",
        "code": "406156006",
        "display": "In paid employment"
      }
    ],
    "text": "In paid employment"
  },
  "subject": {
    "reference": "Patient/eUDxC7UG8-ZHRTFAKx89NYg3",
    "display": "FHIR, Test"
  },
  "startDate": "2023-11-28"
}
```

Change log

Epic Version | Description | Type
February 2026 | The Outside Record FHIR APIs now validate member coverage and return only resources relevant to the member's coverage enrollment. Previously they returned resources unrelated to the member's coverage. | Breaking Change
November 2025 | The Outside Record FHIR APIs are no longer enabled in the November 2025 version. Requests to these APIs do not return data. | Breaking Change

14.1.29 Goal.Search (Outside Record) (R4)

File: site/apis/14-CMS-Incoming/1-R4/11413-Goal-Search-Outside-Record-R4.html
Epic API ID | 11413
FHIR version | R4
Categories | CMS Incoming
API type | USCDI
A la carte | Industry-Standard Level 1 API
USCDI | Yes
Available in inpatient and other contexts | Yes
HTTP method | GET

URL template | /api/FHIR/R4/Goal?category={category}&lifecycle-status={lifecycle-status}&patient={patient}&start-date={start-date}&subject={subject}&_count={_count}&_id={_id}&_include={_include}&_revinclude={_revinclude}
Supports OAuth 2.0 | True
Supported user types | Backend Systems and Non-OAuth 2.0, Clinicians or Administrative Users, Patients
Performs scope validation | False
Source | https://fhir.epic.com/Specifications?api=11413

Description

Use this API to search for a patient's goals. This FHIR resource represents outcomes or conditions to be achieved in the process of patient care.

The data returned by this API includes outpatient care goals. This API does not return care plan goals, clinical pathways, or inpatient care goals.

This API differs from other Goal APIs because it returns data that was obtained as part of payer data exchange workflows rather than directly recorded during patient care. This data can come from payers, providers, or loaded from other FHIR servers. Because this data doesn't originate from the organization being queried, users of this API should be aware that the data might be unverified, incomplete, or duplicative.

Data from outside payer and provider systems is saved to an organization's database and returned in a standard format, documented below. Data loaded from other FHIR servers is returned in the format the organization received it. Because of this, the documentation below does not apply to these loaded resources. These resources can include any elements from the FHIR specification and can be distinguished from other resources by the presence of meta.tag set to "external-bulk-data".

Request parameters

Name | Type | Optional | Array | Cardinality | Description
_count | number | Optional | Yes | | Number of results per page.
_id | token | Optional | Yes | | FHIR resource IDs for the desired resources. Can be used in combination with _count, _include, and _revInclude. All others will be ignored.
_include | string | Optional | Yes | | Used to indicate which referenced resources to include in the search bundle.
_revinclude | string | Optional | Yes | | Used to include Provenance or AuditEvent resources that refer to search results, when available.
patient | reference | Conditional | Yes | | Patient FHIR ID for whom the goal is intended. One of either patient or subject is required.
start-date | date | Optional | Yes | | When goal pursuit begins.
subject | reference | Conditional | Yes | | Patient FHIR ID for whom the goal is intended. One of either patient or subject is required.

Request parameters (post-filtered search parameters)

Name | Type | Optional | Array | Cardinality | Description
lifecycle-status | token | Optional | Yes | | The state of the goal throughout its lifecycle. This is always "Active".

Response elements

Name | Type | Optional | Array | Cardinality | Description
Goal (R4) | Goal | | | | A single Goal resource.
Goal (R4).description | CodeableConcept | | | 1..1 | The Goal description. This is often represented by a SNOMED code, but it might be a code from a different code system. System (SNOMED): http://snomed.info/sct
Goal (R4).id | id | | | 1..1 | The unique FHIR ID for the Goal resource.
Goal (R4).lifecycleStatus | code | | | 1..1 | The state of the Goal throughout its lifecycle. This is always active
Goal (R4).meta | Meta | | | | Metadata about the resource, including information about the origin or source of the data.
Goal (R4).meta.tag | Coding | | Yes | | Set to external-bulk-data for resources originally loaded from another FHIR server. If this element is set to external-bulk-data, all other element-level documentation does not apply to the resource. The resource content might vary and can include any elements allowed by the FHIR specification.
Goal (R4).startDate | date | | | 0..1 | When Goal pursuit begins.
Goal (R4).subject | Reference | | | 1..1 | A reference to the Patient resource representing the subject for whom this Goal is intended.

Sample request

```
GET https://hostname/instance/api/FHIR/R4/Goal?patient=eH7uldpmBBnp2yJkfHPkyHA3
```

Sample response


```
{
  "resourceType": "Bundle",
  "type": "searchset",
  "total": 1,
  "link": [
    {
      "relation": "self",
      "url": "https://hostname/instance/api/FHIR/R4/Goal?patient=eH7uldpmBBnp2yJkfHPkyHA3"
    }
  ],
  "entry": [
    {
      "link": [
        {
          "relation": "self",
          "url": "https://hostname/instance/api/FHIR/R4/Goal/fdhGDoKZTXQaY9NQl3JcQqU7kGnL6UmrUibgDE2dQBSA4"
```

```
        }
      ],
      "fullUrl": "https://hostname/instance/api/FHIR/R4/Goal/fdhGDoKZTXQaY9NQl3JcQqU7kGnL6UmrUibgDE2dQBSA4",
      "resource": {
        "resourceType": "Goal",
        "id": "fdhGDoKZTXQaY9NQl3JcQqU7kGnL6UmrUibgDE2dQBSA4",
        "lifecycleStatus": "active",
        "description": {
          "coding": [
            {
              "system": "http://snomed.info/sct",
              "code": "406156006",
              "display": "In paid employment"
            }
          ],
          "text": "In paid employment"
        },
        "subject": {
          "reference": "Patient/eH7uldpmBBnp2yJkfHPkyHA3",
          "display": "FHIR, Test"
        },
        "startDate": "2025-07-07"
      },
      "search": {
        "mode": "match"
      }
    }
  ]
}
```


Change log

Epic Version | Description | Type
February 2026 | The Outside Record FHIR APIs now validate member coverage and return only resources relevant to the member's coverage enrollment. Previously they returned resources unrelated to the member's coverage. | Breaking Change
November 2025 | The Outside Record FHIR APIs are no longer enabled in the November 2025 version. Requests to these APIs do not return data. | Breaking Change

14.1.30 Group.$bulk-member-match Kickoff

File: site/apis/14-CMS-Incoming/1-R4/11424-Group-bulk-member-match-Kickoff.html
Epic API ID | 11424
FHIR version | R4
Categories | CMS Incoming
API type | Industry-Standard
API group | Bulk Member Data Group
USCDI | No
HTTP method | POST
URL template | /api/FHIR/R4/Group/$bulk-member-match`Parameters***
Supports OAuth 2.0 | True
Supported user types | Backend Systems and Non-OAuth 2.0, Clinicians or Administrative Users
Performs scope validation | False
Source | https://fhir.epic.com/Specifications?api=11424

Request parameters

Name | Type | Optional | Array | Cardinality | Description
Parameters | Parameters | False | | | Parameters resource comprising the request data.
Parameters._id | primitiveExtension | False
Parameters._implicitRules | primitiveExtension | False
Parameters._language | primitiveExtension | False
Parameters.id | String | False
Parameters.implicitRules | String | False
Parameters.language | String | False
Parameters.meta | Meta | False
Parameters.parameter | BackboneElement | False | Yes | | Parameter array.

Response elements

Name | Type | Optional | Array | Cardinality | Description
OperationOutcome | OperationOutcome | False
OperationOutcome._id | primitiveExtension | False
OperationOutcome._implicitRules | primitiveExtension | False
OperationOutcome._language | primitiveExtension | False
OperationOutcome.contained | ResourceContainer | False | Yes | | A container for a single FHIR resource.
OperationOutcome.extension | Extension | False | Yes
OperationOutcome.id | String | False
OperationOutcome.implicitRules | String | False

OperationOutcome.issue | Issue | False | Yes
OperationOutcome.language | String | False
OperationOutcome.meta | Meta | False
OperationOutcome.modifierExtension | Extension | False | Yes
OperationOutcome.text | Narrative | False

14.1.31 Immunization.Read (Outside Record) (R4)

File: site/apis/14-CMS-Incoming/1-R4/11415-Immunization-Read-Outside-Record-R4.html
Epic API ID | 11415
FHIR version | R4
Categories | CMS Incoming
API type | USCDI
A la carte | Industry-Standard Level 1 API
USCDI | Yes
Available in inpatient and other contexts | Yes
HTTP method | GET
URL template | /api/FHIR/R4/Immunization/{ID}
Supports OAuth 2.0 | True
Supported user types | Backend Systems and Non-OAuth 2.0, Clinicians or Administrative Users, Patients
Performs scope validation | False
Source | https://fhir.epic.com/Specifications?api=11415

Description

Use this API to retrieve a specific instance of a patient's historical immunization record. This FHIR resource represents events of a patient being administered a vaccine or a record of an immunization.

This API differs from

Immunization.Read (Patient Chart) (R4)

because it returns data obtained as part of payer data exchange workflows rather than directly recorded during patient care. This data can come from payers, providers, or loaded from other FHIR servers. Because this data doesn't originate from the organization being queried, users of this API should be aware that the data might be unverified, incomplete, or duplicative.

Data from outside payer and provider systems is saved to an organization's database and returned in a standard format, documented below. Data loaded from other FHIR servers is returned in the format the organization received it. Because of this, the documentation below does not apply to these loaded resources. These resources can include any elements from the FHIR specification and can be distinguished from other resources by the presence of meta.tag set to “external-bulk-data".

Request parameters

Name | Type | Optional | Array | Cardinality | Description
ID | token | Required | | | The Immunization FHIR ID.

Response elements

Name | Type | Optional | Array | Cardinality | Description
Immunization (R4) | Immunization | | | | A single Immunization resource.
Immunization (R4).doseQuantity | Quantity | | | 0..1 | The amount of vaccine product administered.
Immunization (R4).doseQuantity.code | String | | | 0..1 | Unit of amount of vaccine administered as a Unified Code for Units of Measure (UCUM) code.
Immunization (R4).doseQuantity.system | String | | | 0..1 | If a UCUM code is present in the code element, this is "http://unitsofmeasure.org".
Immunization (R4).doseQuantity.unit | String | | | 0..1 | Free text representation of the unit of measure for the vaccine administered.
Immunization (R4).doseQuantity.value | Decimal | | | 0..1 | Amount of vaccine administered as a decimal.
Immunization (R4).encounter | Reference | | | 0..1 | Reference to the Encounter resource in which this immunization took place.
Immunization (R4).expirationDate | date | | | 0..1 | The expiration date of the immunization administered as a string in format "YYYY-MM-DD".
Immunization (R4).id | id | | | 1..1 | Unique FHIR ID for the Immunization resource.
Immunization (R4).isSubpotent | boolean | | | 0..1 | Indicates that the dose wasn’t full strength.
Immunization (R4).location | Reference | | | 0..1 | The location where the immunization was administered. Only the display element of this reference is populated.
Immunization (R4).lotNumber | string | | | 0..1 | The lot number identifying the source of an immunization or injection.
Immunization (R4).manufacturer | Reference | | | 0..1 | The manufacturer of the immunization. Only the display element of this reference is populated.
Immunization (R4).meta | Meta | | | 0..1 | Metadata about the resource, including information about the origin or source of the data.
Immunization (R4).meta.tag | Coding | | Yes | 0..* | Set to external-bulk-data for resources originally loaded from another FHIR server. If this element is set to external-bulk-data, the resource content might vary and can include any elements allowed by the FHIR specification.
Immunization (R4).occurrenceDateTime | dateTime | | | 1..1 | Vaccination administration date (if available).
Immunization (R4).patient | Reference | | | 1..1 | A reference to the Patient resource representing the recipient of the Immunization.
Immunization (R4).route | CodeableConcept | | | 0..1 | The route that the immunization entered the body, such as intramuscular injection or swallowed.
Immunization (R4).site | CodeableConcept | | | 0..1 | The body site where the immunization was administered. Only the text element of this CodeableConcept is populated.
Immunization (R4).status | code | Required | | 1..1 | Status of the Immunization. Possible values are: completed entered-in-error not-done Incomplete Immunizations are not returned.

Immunization (R4).statusReason | CodeableConcept | | | 0..1 | Reason for why an Immunization was deferred. Code system: urn:oid:1.2.840.114350.1.13.51865.1.7.10.768076.4086

Immunization (R4).vaccineCode | CodeableConcept | Required | | 1..1 | Vaccine product administered with code and name information. Vaccines are mapped to CVX and NDC codes. CVX codes are a standard set of codes used to indicate the product used in a vaccination. Multiple vaccines in the system can be mapped to the same CVX code. Other code systems can be returned if they were received in the original data exchange workflow. CVX system: http://hl7.org/fhir/sid/cvx NDC system: http://hl7.org/fhir/sid/ndc

Sample request

```
GET https://hostname/instance/api/FHIR/R4/Immunization/fge8HSO32UR-BAlMUHMtmymvLCnA6oeQFlb5cm9H9cqc4
```

Sample response


```
{
  "resourceType": "Immunization",
  "id": "fge8HSO32UR-BAlMUHMtmymvLCnA6oeQFlb5cm9H9cqc4",
  "status": "completed",
  "vaccineCode": {
    "coding": [
      {
        "system": "http://hl7.org/fhir/sid/cvx",
        "code": "28"
      }
    ],
    "text": "Tetanus"
  },
  "patient": {
    "reference": "Patient/ehkwz5AmaWMzCNfXDXtRLKg3",
    "display": "FHIR, Test"
  },
  "encounter": {
    "reference": "Encounter/fdHzu2DGI4G8GXESQ1Xmw3PHlqFhjkh3g0tcisBGbKgk4",
    "display": "Immunization Clinic Visit"
  },
  "occurrenceDateTime": "2025-06-27",
  "location": {
    "display": "FHIR Test Clinic"
  },
  "manufacturer": {
    "display": "FHIR Test, Inc."
  },
  "lotNumber": "TEST-2024-M98765",
  "expirationDate": "2026-03-03",
  "site": {
    "text": "Right Deltoid"
  },
  "route": {
    "text": "Injection, intramuscular"
  },
  "doseQuantity": {
    "value": 0.5,
    "unit": "mL",
    "system": "http://unitsofmeasure.org",
    "code": "mL"
  }
}{
  "resourceType": "Immunization",
  "id": "fge8HSO32UR-BAlMUHMtmymvLCnA6oeQFlb5cm9H9cqc4",
  "status": "completed",
  "vaccineCode": {
    "coding": [
      {
        "system": "http://hl7.org/fhir/sid/cvx",
        "code": "28"
      }
    ],
    "text": "Tetanus"
  },
  "patient": {
    "reference": "Patient/ehkwz5AmaWMzCNfXDXtRLKg3",
    "display": "FHIR, Test"
  },
  "encounter": {
    "reference": "Encounter/fdHzu2DGI4G8GXESQ1Xmw3PHlqFhjkh3g0tcisBGbKgk4",
    "display": "Immunization Clinic Visit"
  },
  "occurrenceDateTime": "2025-06-27",
  "location": {
    "display": "FHIR Test Clinic"
  },
  "manufacturer": {
    "display": "FHIR Test, Inc."
  },
  "lotNumber": "TEST-2024-M98765",
  "expirationDate": "2026-03-03",
  "site": {
    "text": "Right Deltoid"
  },
```

```
  "route": {
    "text": "Injection, intramuscular"
  },
  "doseQuantity": {
    "value": 0.5,
    "unit": "mL",
    "system": "http://unitsofmeasure.org",
    "code": "mL"
  }
}
```

Change log

Epic Version | Description | Type
February 2026 | The Outside Record FHIR APIs now validate member coverage and return only resources relevant to the member's coverage enrollment. Previously they returned resources unrelated to the member's coverage. | Breaking Change
November 2025 | The Outside Record FHIR APIs are no longer enabled in the November 2025 version. Requests to these APIs do not return data. | Breaking Change

14.1.32 Immunization.Search (Outside Record) (R4)

File: site/apis/14-CMS-Incoming/1-R4/11416-Immunization-Search-Outside-Record-R4.html
Epic API ID | 11416
FHIR version | R4
Categories | CMS Incoming
API type | USCDI
A la carte | Industry-Standard Level 1 API
USCDI | Yes
Available in inpatient and other contexts | Yes
HTTP method | GET
URL template | /api/FHIR/R4/Immunization?date={date}&patient={patient}&status={status}&_count={_count}&_id={_id}&_include={_include}&_revinclude={_revinclude}
Supports OAuth 2.0 | True
Supported user types | Backend Systems and Non-OAuth 2.0, Clinicians or Administrative Users, Patients
Performs scope validation | False
Source | https://fhir.epic.com/Specifications?api=11416

Description

Use this API to search for

a patient's historical immunization records. This FHIR resource represents events of a patient being administered vaccines or records of immunizations.

This API differs from

Immunization.Search (Patient Chart) (R4)

because it returns data that was obtained as part of payer data exchange workflows rather than directly recorded during patient care. This data can come from payers, providers, or loaded from other FHIR servers. Because this data doesn't originate from the organization being queried, users of this API should be aware that the data might be unverified, incomplete, or duplicative.

Data from outside payer and provider systems is saved to an organization's database and returned in a standard format, documented below. Data loaded from other FHIR servers is returned in the format the organization received it. Because of this, the documentation below does not apply to these loaded resources. These resources can include any elements from the FHIR specification and can be distinguished from other resources by the presence of meta.tag set to "external-bulk-data".

Request parameters

Name | Type | Optional | Array | Cardinality | Description
_count | number | Optional | Yes | | Number of results per page.
_id | token | Optional | Yes | | FHIR resource IDs for the desired resources. Can be used in combination with _count, _include, and _revInclude. All other search parameters are ignored.
_include | string | Optional | Yes | | Used to indicate which referenced resources to include in the search bundle.
_revinclude | string | Optional | Yes | | Used to include Provenance or AuditEvent resources that refer to search results, when available.
date | date | Optional | Yes | | Date the vaccine was administered.
patient | reference | Required | Yes | | A FHIR ID representing the Patient who received the Immunization.

Request parameters (post-filtered search parameters)

Name | Type | Optional | Array | Cardinality | Description
lot-number | string | Optional | Yes | | Vaccine lot number.
status | token | Optional | Yes | | Immunization event status. Possible values are: completed entered-in-error not-done
status-reason | token | Optional | Yes | | The reason why the vaccine was not administered.
vaccine-code | token | Optional | Yes | | The vaccine product administered.

Response elements

Name | Type | Optional | Array | Cardinality | Description
Immunization (R4) | Immunization | | | | A single Immunization resource.
Immunization (R4).doseQuantity | Quantity | | | 0..1 | The amount of vaccine product administered.
Immunization (R4).doseQuantity.code | String | | | 0..1 | Unit of amount of vaccine administered as a Unified Code for Units of Measure (UCUM) code.
Immunization (R4).doseQuantity.system | String | | | 0..1 | If a UCUM code is present in the code element, this is "http://unitsofmeasure.org".
Immunization (R4).doseQuantity.unit | String | | | 0..1 | Free text representation of the unit of measure for the vaccine administered.
Immunization (R4).doseQuantity.value | Decimal | | | 0..1 | Amount of vaccine administered as a decimal.
Immunization (R4).encounter | Reference | | | 0..1 | Reference to the Encounter resource in which this immunization took place.
Immunization (R4).expirationDate | date | | | 0..1 | The expiration date of the immunization administered as a string in format "YYYY-MM-DD".
Immunization (R4).id | id | | | 1..1 | Unique FHIR ID for the Immunization resource.
Immunization (R4).isSubpotent | boolean | | | 0..1 | Indicates that the dose wasn't full strength.
Immunization (R4).location | Reference | | | 0..1 | The location where the immunization was administered. Only the display element of this reference is populated.
Immunization (R4).lotNumber | string | | | 0..1 | The lot number identifying the source of an immunization or injection.
Immunization (R4).manufacturer | Reference | | | 0..1 | The manufacturer of the immunization. Only the display element of this reference is populated.
Immunization (R4).meta | Meta | | | 0..1 | Metadata about the resource, including information about the origin or source of the data.
Immunization (R4).meta.tag | Coding | | Yes | 0..* | Set to external-bulk-data for resources originally loaded from another FHIR server. If this element is set to external-bulk-data, the resource content might vary and can include any elements allowed by the FHIR specification.
Immunization (R4).occurrenceDateTime | dateTime | | | 1..1 | Vaccination administration date (if available).
Immunization (R4).patient | Reference | | | 1..1 | A reference to the Patient resource representing the recipient of the Immunization.
Immunization (R4).route | CodeableConcept | | | 0..1 | The route that the immunization entered the body, such as intramuscular injection or swallowed.
Immunization (R4).site | CodeableConcept | | | 0..1 | The body site where the immunization was administered. Only the text element of this CodeableConcept is populated.
Immunization (R4).status | code | Required | | 1..1 | Status of the Immunization. Possible values are: completed entered-in-error not-done Incomplete Immunizations are not returned.
Immunization (R4).statusReason | CodeableConcept | | | 0..1 | Reason for why an Immunization was deferred. Code system: urn:oid:1.2.840.114350.1.13.51865.1.7.10.768076.4086
Immunization (R4).vaccineCode | CodeableConcept | Required | | 1..1 | Vaccine product administered with code and name information. Vaccines are mapped to CVX and NDC codes. CVX codes are a standard set of codes used to indicate the product used in a vaccination. Multiple vaccines in the system can be mapped to the same CVX code. Other code systems can be returned if they were received in the original data exchange workflow. CVX system: http://hl7.org/fhir/sid/cvx NDC system: http://hl7.org/fhir/sid/ndc

Sample request

```
GET https://hostname/instance/api/FHIR/R4/Immunization?patient=ehkwz5AmaWMzCNfXDXtRLKg3
```

Sample response


```
{
  "resourceType": "Bundle",
  "type": "searchset",
  "total": 1,
  "link": [
    {
      "relation": "self",
      "url": "https://hostname/instance/api/FHIR/R4/Immunization?patient=ehkwz5AmaWMzCNfXDXtRLKg3"
    }
  ],
  "entry": [
    {
      "link": [
        {
          "relation": "self",
          "url": "https://hostname/instance/api/FHIR/R4/Immunization/fge8HSO32UR-BAlMUHMtmymvLCnA6oeQFlb5cm9H9cqc4"
        }
      ],
      "fullUrl": "https: //hostname/instance/api/FHIR/R4/Immunization/fge8HSO32UR-BAlMUHMtmymvLCnA6oeQFlb5cm9H9cqc4",
      "resource": {
        "resourceType": "Immunization",
        "id": "fge8HSO32UR-BAlMUHMtmymvLCnA6oeQFlb5cm9H9cqc4",
        "status": "completed",
        "vaccineCode": {
          "coding": [
            {
              "system": "http://hl7.org/fhir/sid/cvx",
              "code": "28"
            }
          ],
          "text": "Tetanus"
        },
        "patient": {
          "reference": "Patient/ehkwz5AmaWMzCNfXDXtRLKg3",
          "display": "FHIR, Test"
        },
        "encounter": {
          "reference": "Encounter/fdHzu2DGI4G8GXESQ1Xmw3PHlqFhjkh3g0tcisBGbKgk4",
          "display": "Immunization Clinic Visit"
        },
```

```
        "occurrenceDateTime": "2025-06-27",
        "location": {
          "display": "FHIR Test Clinic"
        },
        "manufacturer": {
          "display": "FHIR Test, Inc."
        },
        "lotNumber": "TEST-2024-M98765",
        "expirationDate": "2026-03-03",
        "site": {
          "text": "Right Deltoid"
        },
        "route": {
          "text": "Injection, intramuscular"
        },
        "doseQuantity": {
          "value": 0.5,
          "unit": "mL",
          "system": "http://unitsofmeasure.org",
          "code": "mL"
        }
      },
      "search": {
        "mode": "match"
      }
    }
  ]
}{
  "resourceType": "Bundle",
  "type": "searchset",
  "total": 1,
  "link": [
    {
      "relation": "self",
      "url": "https://hostname/instance/api/FHIR/R4/Immunization?patient=ehkwz5AmaWMzCNfXDXtRLKg3"
    }
  ],
  "entry": [
    {
      "link": [
        {
          "relation": "self",
          "url": "https://hostname/instance/api/FHIR/R4/Immunization/fge8HSO32UR-BAlMUHMtmymvLCnA6oeQFlb5cm9H9cqc4"
        }
      ],
      "fullUrl": "https: //hostname/instance/api/FHIR/R4/Immunization/fge8HSO32UR-BAlMUHMtmymvLCnA6oeQFlb5cm9H9cqc4",
      "resource": {
        "resourceType": "Immunization",
        "id": "fge8HSO32UR-BAlMUHMtmymvLCnA6oeQFlb5cm9H9cqc4",
        "status": "completed",
        "vaccineCode": {
          "coding": [
            {
              "system": "http://hl7.org/fhir/sid/cvx",
              "code": "28"
            }
          ],
          "text": "Tetanus"
        },
        "patient": {
          "reference": "Patient/ehkwz5AmaWMzCNfXDXtRLKg3",
          "display": "FHIR, Test"
        },
        "encounter": {
          "reference": "Encounter/fdHzu2DGI4G8GXESQ1Xmw3PHlqFhjkh3g0tcisBGbKgk4",
          "display": "Immunization Clinic Visit"
        },
        "occurrenceDateTime": "2025-06-27",
        "location": {
          "display": "FHIR Test Clinic"
        },
        "manufacturer": {
          "display": "FHIR Test, Inc."
        },
        "lotNumber": "TEST-2024-M98765",
        "expirationDate": "2026-03-03",
        "site": {
          "text": "Right Deltoid"
        },
        "route": {
          "text": "Injection, intramuscular"
        },
        "doseQuantity": {
          "value": 0.5,
          "unit": "mL",
          "system": "http://unitsofmeasure.org",
          "code": "mL"
        }
      },
```

```
      "search": {
        "mode": "match"
      }
    }
  ]
}
```

Change log

Epic Version | Description | Type
February 2026 | The Outside Record FHIR APIs now validate member coverage and return only resources relevant to the member's coverage enrollment. Previously they returned resources unrelated to the member's coverage. | Breaking Change
November 2025 | The Outside Record FHIR APIs are no longer enabled in the November 2025 version. Requests to these APIs do not return data. | Breaking Change

14.1.33 Location.Read (Outside Record) (R4)

File: site/apis/14-CMS-Incoming/1-R4/11461-Location-Read-Outside-Record-R4.html
Epic API ID | 11461
FHIR version | R4
Categories | CMS Incoming
API type | USCDI
A la carte | Industry-Standard Level 1 API
USCDI | Yes
Available in inpatient and other contexts | Yes
HTTP method | GET
URL template | /api/FHIR/R4/Location/{ID}
Supports OAuth 2.0 | True
Supported user types | Backend Systems and Non-OAuth 2.0, Clinicians or Administrative Users, Patients
Performs scope validation | False
Source | https://fhir.epic.com/Specifications?api=11461

Description

Use this API to retrieve a specific instance of a location. A single overall Location (Outside Record)

resource repre

sents a physical place where healthcare is provided (for example a facility, clinic, department, ward, room, or bed) and is used any time other resources need to reference where care or a service occurred.

This API differs from other Location APIs because it returns data obtained as part of payer data exchange workflows rather than directly recorded during patient care. This data can come from payers or loaded from other FHIR servers. Because this data doesn't originate from the organization being queried, users of this API should be aware that the data might be unverified, incomplete, or duplicative.

This data is loaded from other FHIR servers and returned in the format the organization received it. Because of this, the documentation below is minimal. These resources can include any elements from the FHIR specification and can be distinguished from other resources by the presence of meta.tag set to

external-bulk-data

Request parameters

Name | Type | Optional | Array | Cardinality | Description
ID | token | Required | | | The Location FHIR ID.

Response elements

Name | Type | Optional | Array | Cardinality | Description
Location (R4) | Resource | | | | An instance of the R4 Location FHIR resource.
Location (R4).id | id | | | 1..1 | The unique FHIR ID representing the Location (Outside Record) resource.
Location (R4).meta | Meta | | | 1..1 | Metadata about the resource, including information about the origin or source of the data.
Location (R4).meta.tag | Coding | | Yes | 1..* | Set to external-bulk-data for resources originally loaded from another FHIR server. If this element is set to external-bulk-data, the resource content might vary and can include any elements allowed by the FHIR specification.

Sample request

```
GET https://hostname/instance/api/FHIR/R4/Location/fQbSZZeRjpcB9hVnuT5hbTQNn3bfTgAk83wPPOSApu9PXxvsA6o5yCWJIuaLv6svzQOH-
    tK8lsZOF7qyPT9iJ9A4
```

Sample response

```
{
  "resourceType": "Location",
  "id": "fQbSZZeRjpcB9hVnuT5hbTQNn3bfTgAk83wPPOSApu9PXxvsA6o5yCWJIuaLv6svzQOH-tK8lsZOF7qyPT9iJ9A4",
  "meta": {
    "tag": [
      {
```

```
        "system": "https://open.epic.com/FHIR/bulk-data-source",
        "code": "external-bulk-data",
        "display": "External Bulk Data"
      }
    ]
  },
  ... <r4 location="" compliant="" elements=""> ...
}</r4>
```

14.1.34 Location.Search (Outside Record) (R4)

File: site/apis/14-CMS-Incoming/1-R4/11462-Location-Search-Outside-Record-R4.html
Epic API ID | 11462
FHIR version | R4
Categories | CMS Incoming
API type | USCDI
A la carte | Industry-Standard Level 1 API
USCDI | Yes
Available in inpatient and other contexts | Yes
HTTP method | GET
URL template | /api/FHIR/R4/Location?type={type}&_count={_count}&_id={_id}&_include={_include}&_revinclude={_revinclude}
Supports OAuth 2.0 | True
Supported user types | Backend Systems and Non-OAuth 2.0, Clinicians or Administrative Users, Patients
Performs scope validation | False
Source | https://fhir.epic.com/Specifications?api=11462

Description

Use this API to search for location resources. A single overall Location (Outside Record)

resource repre

sents a physical place where healthcare is provided (for example a facility, clinic, department, ward, room, or bed) and is used any time other resources need to reference where care or a service occurred.

This API differs from other Location APIs because it returns data obtained as part of payer data exchange workflows rather than directly recorded during patient care. This data can come from payers or loaded from other FHIR servers. Because this data doesn't originate from the organization being queried, users of this API should be aware that the data might be unverified, incomplete, or duplicative.

This data is loaded from other FHIR servers and returned in the format the organization received it. Because of this, the documentation below is minimal. These resources can include any elements from the FHIR specification and can be distinguished from other resources by the presence of meta.tag set to

external-bulk-data

Request parameters

Name | Type | Optional | Array | Cardinality | Description
_count | number | Optional | Yes | | Number of results per page.
_id | token | Required | Yes | | FHIR resource IDs for the desired resources. Can be used in combination with _count, _include, and _revInclude. All others will be ignored.
_include | string | Optional | Yes | | Used to indicate which referenced resources to include in the search bundle.
_revinclude | string | Optional | Yes | | Used to include Provenance or AuditEvent resources that refer to search results, when available.

Response elements

Name | Type | Optional | Array | Cardinality | Description
Location (R4) | Resource | | | | An instance of the R4 Location FHIR resource.
Location (R4).id | id | | | 1..1 | The unique FHIR ID representing the Location (Outside Record) resource.
Location (R4).meta | Meta | | | 1..1 | Metadata about the resource, including information about the origin or source of the data.
Location (R4).meta.tag | Coding | | Yes | 1..* | Set to external-bulk-data for resources originally loaded from another FHIR server. If this element is set to external-bulk-data, the resource content might vary and can include any elements allowed by the FHIR specification.

Sample request

```
GET
    https://hostname/instance/api/FHIR/R4/Location?_ID=fQbSZZeRjpcB9hVnuT5hbTQNn3bfTgAk83wPPOSApu9PXxvsA6o5yCWJIuaLv6svz
    QOH-tK8lsZOF7qyPT9iJ9A4
```

Sample response

```
{
  "resourceType": "Bundle",
  "type": "searchset",
  "total": 1,
  "link": [
    {
      "relation": "self",
      "url": "https://hostname/instance/api/FHIR/R4/Location?_id=fQbSZZeRjpcB9hVnuT5hbTQNn3bfTgAk83wPPOSApu9PXxvsA6o5yCW
```

```
    JIuaLv6svzQOH-tK8lsZOF7qyPT9iJ9A4"
    }
  ],
  "entry": [
    {
      "link": [
        {
          "relation": "self",
          "url":
    "https://hostname/instance/api/FHIR/R4/Location/fQbSZZeRjpcB9hVnuT5hbTQNn3bfTgAk83wPPOSApu9PXxvsA6o5yCWJIuaLv6svzQOH
    -tK8lsZOF7qyPT9iJ9A4"
        }
      ],
      "fullUrl":
    "https://hostname/instance/api/FHIR/R4/Location/fQbSZZeRjpcB9hVnuT5hbTQNn3bfTgAk83wPPOSApu9PXxvsA6o5yCWJIuaLv6svzQOH
    -tK8lsZOF7qyPT9iJ9A4",
      "resource": {
        "resourceType": "Location",
        "id": "fQbSZZeRjpcB9hVnuT5hbTQNn3bfTgAk83wPPOSApu9PXxvsA6o5yCWJIuaLv6svzQOH-tK8lsZOF7qyPT9iJ9A4",
        "meta": {
          "tag": [
            {
              "system": "https://open.epic.com/FHIR/bulk-data-source",
              "code": "external-bulk-data",
              "display": "External Bulk Data"
            }
          ]
        },
        ... <r4 location="" compliant="" elements=""> ...
      }
    }
  ]
}
</r4>
```


14.1.35 Medication.Read (Outside Record) (R4)

File: site/apis/14-CMS-Incoming/1-R4/11463-Medication-Read-Outside-Record-R4.html
Epic API ID | 11463
FHIR version | R4
Categories | CMS Incoming
API type | USCDI
A la carte | Industry-Standard Level 1 API
USCDI | Yes
Available in inpatient and other contexts | Yes
HTTP method | GET
URL template | /api/FHIR/R4/Medication/{ID}
Supports OAuth 2.0 | True
Supported user types | Backend Systems and Non-OAuth 2.0, Clinicians or Administrative Users, Patients
Performs scope validation | False
Source | https://fhir.epic.com/Specifications?api=11463

Description

Use this API to retrieve a specific instance of a medication. A single overall Medication (Outside Record)

resource repr

esents a medication (drug) and exposes canonical details about it - most importantly a coded identity and optionally the medication ingredients and form (such as tablet or solution) - so other resources can unambiguously reference the drug.

This API differs from other Medication APIs because it returns data obtained as part of payer data exchange workflows rather than directly recorded during patient care. This data can come from payers or loaded from other FHIR servers. Because this data doesn't originate from the organization being queried, users of this API should be aware that the data might be unverified, incomplete, or duplicative.

This data is loaded from other FHIR servers and returned in the format the organization received it. Because of this, the documentation below is minimal. These resources can include any elements from the FHIR specification and can be distinguished from other resources by the presence of meta.tag set to

external-bulk-data

Request parameters

Name | Type | Optional | Array | Cardinality | Description
ID | token | Required | | | The Medication FHIR ID.

Response elements

Name | Type | Optional | Array | Cardinality | Description
Medication (R4) | Resource | | | | An instance of the R4 Medication FHIR resource.
Medication (R4).id | id | | | 1..1 | The unique FHIR ID representing the Medication (Outside Record) resource.

Medication (R4).meta | Meta | | | 1..1 | Metadata about the resource, including information about the origin or source of the data.
Medication (R4).meta.tag | Coding | | Yes | 1..* | Set to external-bulk-data for resources originally loaded from another FHIR server. If this element is set to external-bulk-data, the resource content might vary and can include any elements allowed by the FHIR specification.

Sample request

```
GET https://hostname/instance/api/FHIR/R4/Medication/fxWzms2BI5A.a2iG8289THKT1F2pG9rIS-0H8M-Qc1b5wxs758vofDBivuNWrgW1-
    yHIzRLHmovOXekSgVAYJuA4
```

Sample response

```
{
  "resourceType": "Medication",
  "id": "fxWzms2BI5A.a2iG8289THKT1F2pG9rIS-0H8M-Qc1b5wxs758vofDBivuNWrgW1-yHIzRLHmovOXekSgVAYJuA4",
  "meta": {
    "tag": [
      {
        "system": "https://open.epic.com/FHIR/bulk-data-source",
        "code": "external-bulk-data",
        "display": "External Bulk Data"
      }
    ]
  },
  ... <r4 medication="" compliant="" elements=""> ...
}
</r4>
```

14.1.36 Medication.Search (Outside Record) (R4)

File: site/apis/14-CMS-Incoming/1-R4/11464-Medication-Search-Outside-Record-R4.html
Epic API ID | 11464
FHIR version | R4
Categories | CMS Incoming
API type | USCDI
A la carte | Industry-Standard Level 1 API
USCDI | Yes
Available in inpatient and other contexts | Yes
HTTP method | GET
URL template | /api/FHIR/R4/Medication?_count={_count}&_id={_id}&_include={_include}&_revinclude={_revinclude}
Supports OAuth 2.0 | True
Supported user types | Backend Systems and Non-OAuth 2.0, Clinicians or Administrative Users, Patients
Performs scope validation | False
Source | https://fhir.epic.com/Specifications?api=11464

Description

Use this API to search for medication resources. A single overall Medication (Outside Record)

resource repr

esents a medication (drug) and exposes canonical details about it - most importantly a coded identity and optionally the medication ingredients and form (such as tablet or solution) - so other resources can unambiguously reference the drug.

This API differs from other Medication APIs because it returns data obtained as part of payer data exchange workflows rather than directly recorded during patient care. This data can come from payers or loaded from other FHIR servers. Because this data doesn't originate from the organization being queried, users of this API should be aware that the data might be unverified, incomplete, or duplicative.

This data is loaded from other FHIR servers and returned in the format the organization received it. Because of this, the documentation below is minimal. These resources can include any elements from the FHIR specification and can be distinguished from other resources by the presence of meta.tag set to

external-bulk-data

Request parameters

Name | Type | Optional | Array | Cardinality | Description
_count | number | Optional | Yes | | Number of results per page.
_id | token | Required | Yes | | FHIR resource IDs for the desired resources. Can be used in combination with _count, _include, and _revInclude. All others will be ignored.
_include | string | Optional | Yes | | Used to indicate which referenced resources to include in the search bundle.
_revinclude | string | Optional | Yes | | Used to include Provenance or AuditEvent resources that refer to search results, when available.

Response elements

Name | Type | Optional | Array | Cardinality | Description
Medication (R4) | Resource | | | | An instance of the R4 Medication FHIR resource.
Medication (R4).id | id | | | 1..1 | The unique FHIR ID representing the Medication (Outside Record) resource.
Medication (R4).meta | Meta | | | 1..1 | Metadata about the resource, including information about the origin or source of the data.

Medication (R4).meta.tag | Coding | | Yes | 1..* | Set to external-bulk-data for resources originally loaded from another FHIR server. If this element is set to external-bulk-data, the resource content might vary and can include any elements allowed by the FHIR specification.

Sample request

```
GET https://hostname/instance/api/FHIR/R4/Medication?_ID=fxWzms2BI5A.a2iG8289THKT1F2pG9rIS-0H8M-
    Qc1b5wxs758vofDBivuNWrgW1-yHIzRLHmovOXekSgVAYJuA4
```

Sample response

```
{
  "resourceType": "Bundle",
  "type": "searchset",
  "total": 1,
  "link": [
    {
      "relation": "self",
      "url": "https://hostname/instance/api/FHIR/R4/Medication?_id=fxWzms2BI5A.a2iG8289THKT1F2pG9rIS-0H8M-
    Qc1b5wxs758vofDBivuNWrgW1-yHIzRLHmovOXekSgVAYJuA4"
    }
  ],
  "entry": [
    {
      "link": [
        {
          "relation": "self",
          "url": "https://hostname/instance/api/FHIR/R4/Medication/fxWzms2BI5A.a2iG8289THKT1F2pG9rIS-0H8M-
    Qc1b5wxs758vofDBivuNWrgW1-yHIzRLHmovOXekSgVAYJuA4"
        }
      ],
      "fullUrl": "https://hostname/instance/api/FHIR/R4/Medication/fxWzms2BI5A.a2iG8289THKT1F2pG9rIS-0H8M-
    Qc1b5wxs758vofDBivuNWrgW1-yHIzRLHmovOXekSgVAYJuA4",
      "resource": {
        "resourceType": "Medication",
        "id": "fxWzms2BI5A.a2iG8289THKT1F2pG9rIS-0H8M-Qc1b5wxs758vofDBivuNWrgW1-yHIzRLHmovOXekSgVAYJuA4",
        "meta": {
          "tag": [
            {
              "system": "https://open.epic.com/FHIR/bulk-data-source",
              "code": "external-bulk-data",
              "display": "External Bulk Data"
            }
          ]
        },
      ... <r4 medication="" compliant="" elements=""> ...
      }
    }
  ]
}</r4>
```

14.1.37 MedicationDispense.Read (Outside Record) (R4)

File: site/apis/14-CMS-Incoming/1-R4/11417-MedicationDispense-Read-Outside-Record-R4.html
Epic API ID | 11417
FHIR version | R4
Categories | CMS Incoming
API type | USCDI
A la carte | Industry-Standard Level 1 API
USCDI | Yes
Available in inpatient and other contexts | Yes
HTTP method | GET
URL template | /api/FHIR/R4/MedicationDispense/{ID}
Supports OAuth 2.0 | True
Supported user types | Backend Systems and Non-OAuth 2.0, Clinicians or Administrative Users, Patients
Performs scope validation | False
Source | https://fhir.epic.com/Specifications?api=11417

Description

Use this API to retrieve a specific instance of a patient's dispensed medications. This FHIR resource represents a medication product that has been dispensed for a named patient.

For medication requests that might not have yet been dispensed, see

MedicationRequest.Read (Outside Record) (R4)

The data returned by this API include various types of medication dispenses, such as inpatient-dispensed medications, clinic-administered medications (CAMS), patient-reported medications, and claims imported medications. This API does not return reconciled medications.

This API differs from other MedicationDispense APIs because it returns data that was obtained as part of payer data exchange workflows rather than directly recorded during patient care. This data can come from payers, providers, or loaded from other FHIR servers. Because this data doesn't originate from the organization being queried, users of this API should be

aware that the data might be unverified, incomplete, or duplicative. This API can be used to exchange data between both providers and payers but is generally not recommended for use in patient treatment scenarios.

Data from outside payer and provider systems is saved to an organization's database and returned in a standard format, documented below. Data loaded from other FHIR servers is returned in the format the organization received it. Because of this, the documentation below does not apply to these loaded resources. These resources can include any elements from the FHIR specification and can be distinguished from other resources by the presence of meta.tag set to "external-bulk-data".

Request parameters

Name | Type | Optional | Array | Cardinality | Description
ID | token | Required | | | A MedicationDispense FHIR ID.

Response elements

Name | Type | Optional | Array | Cardinality | Description
MedicationDispense (R4) | MedicationDispense | | | | A single instance of a MedicationDispense resource.
MedicationDispense (R4).authorizingPrescription | Reference | | Yes | | The medication order that authorizes the dispense. This references the contained resource.
MedicationDispense (R4).contained | ResourceContainer | | Yes | 0..* | The resources referenced by the medication dispense.
MedicationDispense (R4).contained.MedicationRequest | MedicationRequest | | | 0..* | The request for the medication dispense.
MedicationDispense (R4).contained.MedicationRequest.intent | code | | | 1..1 | The kind of medication order. This is always "Plan".
MedicationDispense (R4).contained.MedicationRequest.medicationCodeableConcept | CodeableConcept | | | 1..1 | Codes defining the medication to be taken.
MedicationDispense (R4).contained.MedicationRequest.requester | Reference | | | 0..1 | The provider who created the request.
MedicationDispense (R4).contained.MedicationRequest.status | code | | | 1..1 | A code specifying the state of the prescribing event. This is always "Unknown".
MedicationDispense (R4).contained.MedicationRequest.subject | Reference | | | 1..1 | Who the medication request is for.
MedicationDispense (R4).dosageInstruction | Dosage | | Yes | 0..* | How the medication is to be used by the patient or administered by the caregiver.
MedicationDispense (R4).dosageInstruction.doseAndRate | BackboneElement | | Yes | 0..* | Amount of medication administered.
MedicationDispense (R4).dosageInstruction.doseAndRate.doseQuantity | Quantity | | | 0..1 | Amount of medication per dose.
MedicationDispense (R4).dosageInstruction.text | string | | | 0..1 | Free text dosage instructions.
MedicationDispense (R4).dosageInstruction.timing | Timing | | | 0..1 | When medication should be administered.
MedicationDispense (R4).id | id | | | 1..1 | The unique FHIR ID for the MedicationDispense.
MedicationDispense (R4).medicationCodeableConcept | CodeableConcept | | | 1..1 | What medication was supplied.
MedicationDispense (R4).meta | Meta | | | | Metadata about the resource, including information about the origin or source of the data.
MedicationDispense (R4).meta.tag | Coding | | Yes | | Set to external-bulk-data for resources originally loaded from another FHIR server. If this element is set to external-bulk-data, all other element-level documentation does not apply to the resource. The resource content might vary and can include any elements allowed by the FHIR specification.
MedicationDispense (R4).performer | BackboneElement | | Yes | 0..* | Who performed the medication dispense.
MedicationDispense (R4).performer.actor | Reference | | | 1..1 | Organization where the medication dispense is performed.
MedicationDispense (R4).quantity | Quantity | | | 0..1 | Amount dispensed.
MedicationDispense (R4).status | code | | | 1..1 | Medication dispense status. Statuses: in-progress on-hold completed entered-in-error stopped unknown Dispenses which have been auto-discarded or have a historical status of discontinued have a medication dispense status of "entered-in-error". Dispenses which have a historical status of discontinued will have a medication dispense status of "stopped". Dispenses which have refills included but all refills are remaining will have a status of "in-progress" Dispenses which have no handed over date that do not meet the criteria for the above statuses will have a status of "unknown". All other dispenses will have a status of "completed".
MedicationDispense (R4).subject | Reference | | | 1..1 | Who the dispense is for.
MedicationDispense (R4).type | CodeableConcept | | | 0..1 | The type of dispense. This is always "Refill".
MedicationDispense (R4).whenHandedOver | dateTime | | | 0..1 | When the product was given out or mailed.

Sample request

```
GET https://hostname/instance/api/FHIR/R4/MedicationDispense/fAHwfRdnYLU9kAp0EOmkY4lGx5XkFfk52jezpQN8v1eE4
```

Sample response


```
{
    "resourceType": "MedicationDispense",
    "id": "fAHwfRdnYLU9kAp0EOmkY4lGx5XkFfk52jezpQN8v1eE4",
    "contained": [
        {
            "resourceType": "MedicationRequest",
            "id": "authorizingPrescription1",
            "status": "unknown",
            "intent": "plan",
            "subject": {
                "reference": "Patient/eH7uldpmBBnp2yJkfHPkyHA3",
                "display": "FHIR, Test Patient"
            },
            "requester": {
                "reference": "Practitioner/eZjjXH-OF4y0aphI9Y8T6Y4Sm85SdUFCl44RziejZK4hsWdUdQaj70-sGmQdqCMf-3"
            }
        }
    ],
    "status": "completed",
    "medicationCodeableConcept": {
        "text": "Acetaminophen (ACETAMIN PO)"
    },
```

```
    "subject": {
        "reference": "Patient/eH7uldpmBBnp2yJkfHPkyHA3",
        "display": "FHIR, Test Patient"
    },
    "performer": [
        {
            "actor": {
                "reference": "Organization/eygDhxMZNno.H6kBQ0S39mg3",
                "type": "Organization",
                "display": "External Pharmacy"
            }
        }
    ],
    "authorizingPrescription": [
        {
            "reference": "#authorizingPrescription1"
        }
    ],
    "type": {
        "coding": [
            {
                "system": "http://terminology.hl7.org/CodeSystem/v3-ActCode",
                "code": "RF",
                "display": "Refill"
            }
        ],
        "text": "1 of 3 refills remaining"
    },
    "quantity": {
        "value": 90
    },
    "whenHandedOver": "2025-06-09T17:20:39Z",
    "dosageInstruction": [
        {
            "text": "Take 1 tablet daily"
            "timing": {
                "code": {
                    "text": "1 time daily"
                }
            },
            "doseAndRate": [
                {
                    "doseQuantity": {
                        "value": 1,
                        "unit": "tablet",
                        "system": "http://unitsofmeasure.org",
                        "code": "{tbl}"
                    }
                }
            ]
        }
    ]
}
```


Change log

Epic Version	Description	Type
February 2026	The Outside Record FHIR APIs now validate member coverage and return only resources relevant to the member's coverage enrollment. Previously they returned resources unrelated to the member's coverage.	Breaking Change
November 2025	The Outside Record FHIR APIs are no longer enabled in the November 2025 version. Requests to these APIs do not return data.	Breaking Change

14.1.38 MedicationDispense.Search (Outside Record) (R4)

File: site/apis/14-CMS-Incoming/1-R4/11418-MedicationDispense-Search-Outside-Record-R4.html	
Epic API ID	11418
FHIR version	R4
Categories	CMS Incoming
API type	USCDI
A la carte	Industry-Standard Level 2 API
USCDI	Yes
Available in inpatient and other contexts	Yes
HTTP method	GET
URL template	/api/FHIR/R4/MedicationDispense?category={category}&patient={patient}&subject={subject}&_count={_count}&_id={_id}&_include={_include}&_revinclude={_revinclude}
Supports OAuth 2.0	True
Supported user types	Backend Systems and Non-OAuth 2.0, Clinicians or Administrative Users, Patients
Performs scope validation	False
Source	https://fhir.epic.com/Specifications?api=11418

Description

Use this API to search for a patient’s dispensed medications. This FHIR resource represents a medication products that have been dispensed for a named patient.

For medication requests that might not have yet been dispensed, see

MedicationRequest.Search (Outside Record) (R4)

The data returned by this API include various types of medication dispenses, such as inpatient-dispensed medications, clinic-administered medications (CAMS), patient-reported medications, and claims imported medications. This API does not return reconciled medications.

This API differs from other MedicationDispense APIs because it returns data that was obtained as part of payer data exchange workflows rather than directly recorded during patient care. This data can come from payers, providers, or loaded from other FHIR servers. Because this data doesn't originate from the organization being queried, users of this API should be aware that the data might be unverified, incomplete, or duplicative. This API can be used to exchange data between both providers and payers but is generally not recommended for use in patient treatment scenarios.

Data from outside payer and provider systems is saved to an organization's database and returned in a standard format, documented below. Data loaded from other FHIR servers is returned in the format the organization received it. Because of this, the documentation below does not apply to these loaded resources. These resources can include any elements from the FHIR specification and can be distinguished from other resources by the presence of meta.tag set to "external-bulk-data".

Request parameters

Name | Type | Optional | Array | Cardinality | Description
_count | number | Optional | Yes | | Number of results per page.
_id | token | Optional | Yes | | FHIR resource IDs for the desired resources. Can be used in combination with _count, _include, and _revInclude. All other search parameters are ignored.
_include | string | Optional | Yes | | Used to indicate which referenced resources to include in the search bundle.
_revinclude | string | Optional | Yes | | Used to include Provenance or AuditEvent resources that refer to search results, when available.
patient | reference | Conditional | Yes | | Reference to a patient resource the dispense is for. Either a patient or subject parameter must be provided. If both are provided, they must match exactly.
subject | reference | Conditional | Yes | | Reference to a Patient resource the dispense is for. Either a patient or subject parameter must be provided. If both are provided, they must match exactly.

Request parameters (post-filtered search parameters)

Name | Type | Optional | Array | Cardinality | Description
code | token | Optional | Yes | | Code of the medication dispensed.
status | token | Optional | Yes | | Medication dispense status.
whenhandedover | date | Optional | Yes | | When product was given out or mailed.

Response elements

Name | Type | Optional | Array | Cardinality | Description
MedicationDispense (R4) | MedicationDispense | | | | A single instance of a MedicationDispense resource.
MedicationDispense (R4).authorizingPrescription | Reference | | Yes | | The medication order that authorizes the dispense. This references the contained resource.
MedicationDispense (R4).contained | ResourceContainer | | Yes | 0..* | The resources referenced by the medication dispense.
MedicationDispense (R4).contained.MedicationRequest | MedicationRequest | | | 0..* | The request for the medication dispense.
MedicationDispense (R4).contained.MedicationRequest.intent | code | | | 1..1 | The kind of medication order. This is always "Plan".
MedicationDispense (R4).contained.MedicationRequest.medicationCodeableConcept | CodeableConcept | | | 1..1 | Codes defining the medication to be taken.
MedicationDispense (R4).contained.MedicationRequest.requester | Reference | | | 0..1 | The provider who created the request.
MedicationDispense (R4).contained.MedicationRequest.status | code | | | 1..1 | A code specifying the state of the prescribing event. This is always "Unknown".
MedicationDispense (R4).contained.MedicationRequest.subject | Reference | | | 1..1 | Who the medication request is for.
MedicationDispense (R4).dosageInstruction | Dosage | | Yes | 0..* | How the medication is to be used by the patient or administered by the caregiver.
MedicationDispense (R4).dosageInstruction.doseAndRate | BackboneElement | | Yes | 0..* | Amount of medication administered.
MedicationDispense (R4).dosageInstruction.doseAndRate.doseQuantity | Quantity | | | 0..1 | Amount of medication per dose.
MedicationDispense (R4).dosageInstruction.text | string | | | 0..1 | Free text dosage instructions.
MedicationDispense (R4).dosageInstruction.timing | Timing | | | 0..1 | When medication should be administered.
MedicationDispense (R4).id | id | | | | The unique FHIR ID for the MedicationDispense.
MedicationDispense (R4).medicationCodeableConcept | CodeableConcept | | | 1..1 | What medication was supplied.
MedicationDispense (R4).meta | Meta | | | | Metadata about the resource, including information about the origin or source of the data.
MedicationDispense (R4).meta.tag | Coding | | Yes | | Set to external-bulk-data for resources originally loaded from another FHIR server. If this element is set to external-bulk-data, all other element-level documentation does not apply to the resource. The resource content might vary and can include any elements allowed by the FHIR specification.
MedicationDispense (R4).performer | BackboneElement | | Yes | 0..* | Who performed the medication dispense.
MedicationDispense (R4).performer.actor | Reference | | | 1..1 | Organization where the medication dispense is performed.
MedicationDispense (R4).quantity | Quantity | | | 0..1 | Amount dispensed.
MedicationDispense (R4).status | code | | | 1..1 | Medication dispense status. Statuses: in-progress on-hold completed entered-in-error stopped unknown Dispenses which have been auto-discarded or have a historical status of discontinued have a medication dispense status of "entered-in-error". Dispenses which have a historical status of discontinued will have a medication dispense status of "stopped". Dispenses which have refills included but all refills are remaining will have a status of "in-progress" Dispenses which have no handed over date that do not meet the criteria for the above statuses will have a status of "unknown". All other dispenses will have a status of "completed".

MedicationDispense (R4).subject | Reference | | | 1..1 | Who the dispense is for.
MedicationDispense (R4).type | CodeableConcept | | | 0..1 | The type of dispense. This is always "Refill".
MedicationDispense (R4).whenHandedOver | dateTime | | | 0..1 | When the product was given out or mailed.

Sample request

```
GET https://hostname/instance/api/FHIR/R4/MedicationDispense?patient=eH7uldpmBBnp2yJkfHPkyHA3
```

Sample response


```
{
  "resourceType": "Bundle",
  "type": "searchset",
  "total": 2,
  "link": [
    {
      "relation": "self",
      "url": "https://hostname/instance/api/FHIR/R4/MedicationDispense?patient=eH7uldpmBBnp2yJkfHPkyHA3"
    }
  ],
  "entry": [
    {
      "link": [
        {
          "relation": "self",
          "url":
    "https://hostname/instance/api/FHIR/R4/MedicationDispense/fAHwfRdnYLU9kAp0EOmkY4lGx5XkFfk52jezpQN8v1eE4"
        }
      ],
      "fullUrl":
    "https://hostname/instance/api/FHIR/R4/MedicationDispense/fAHwfRdnYLU9kAp0EOmkY4lGx5XkFfk52jezpQN8v1eE4",
      "resource": {
        "resourceType": "MedicationDispense",
        "id": "fAHwfRdnYLU9kAp0EOmkY4lGx5XkFfk52jezpQN8v1eE4",
        "status": "completed",
        "medicationCodeableConcept": {
          "text": "Acetaminophen (ACETAMIN PO)"
        },
        "subject": {
          "reference": "Patient/eH7uldpmBBnp2yJkfHPkyHA3",
          "display": "FHIR, Test Patient"
        },
        "performer": [
          {
            "actor": {
              "reference": "Organization/eygDhxMZNno.H6kBQ0S39mg3",
              "type": "Organization",
              "display": "External Pharmacy"
            }
          }
        ],
        "type": {
          "coding": [
            {
              "system": "http://terminology.hl7.org/CodeSystem/v3-ActCode",
              "code": "RF",
              "display": "Refill"
            }
          ],
          "text": "1 of 3 refills remaining"
        },
        "quantity": {
          "value": 90,
          "unit": "mg",
          "system": "http://unitsofmeasure.org",
          "code": "mg"
        },
        "whenHandedOver": "2025-06-09T17:20:39Z",
        "dosageInstruction": [
          {
            "text": "Take 1 tablet daily"
          }
        ]
      },
      "search": {
        "mode": "match"
      }
    },
    {
      "link": [
        {
          "relation": "self",
          "url": "https://hostname/instance/api/FHIR/R4/MedicationRequest/ezOIUpaTqesgNMZeRgIj0fuSdd5MHaIn6l98zviT0W7o3"
        }
      ],
      "fullUrl":
    "https://hostname/instance/api/FHIR/R4/MedicationRequest/ezOIUpaTqesgNMZeRgIj0fuSdd5MHaIn6l98zviT0W7o3",
      "resourceType": "MedicationDispense",
```

```
      "id": "ezOIUpaTqesgNMZeRgIj0fuSdd5MHaIn6l98zviT0W7o3",
      "contained": [
        {
          "resourceType": "MedicationRequest",
          "id": "authorizingPrescription1",
          "status": "unknown",
          "intent": "plan",
          "subject": {
            "reference": "Patient/eH7uldpmBBnp2yJkfHPkyHA3",
            "display": "FHIR, Test Patient"
          },
          "requester": {
            "reference": "Practitioner/eZjjXH-OF4y0aphI9Y8T6Y4Sm85SdUFCl44RziejZK4hsWdUdQaj70-sGmQdqCMf-3",
            "display": "FHIR, Requester"
          }
        }
      ],
      "status": "completed",
      "medicationCodeableConcept": {
        "text": "Acetaminophen (ACETAMIN PO)"
      },
      "subject": {
        "reference": "Patient/eH7uldpmBBnp2yJkfHPkyHA3",
        "display": "FHIR, Test Patient"
      },
      "performer": [
        {
          "actor": {
            "reference": "Organization/eygDhxMZNno.H6kBQ0S39mg3",
            "type": "Organization",
            "display": "External Pharmacy"
          }
        }
      ],
      "authorizingPrescription": [
        {
          "reference": "#authorizingPrescription1"
        }
      ],
      "type": {
        "coding": [
          {
            "system": "http://terminology.hl7.org/CodeSystem/v3-ActCode",
            "code": "RF",
            "display": "Refill"
          }
        ],
        "text": "1 of 3 refills remaining"
      },
      "quantity": {
        "value": 90,
        "unit": "mg",
        "system": "http://unitsofmeasure.org",
        "code": "mg"
      },
      "whenHandedOver": "2025-06-09T17:20:39Z",
      "dosageInstruction": [
        {
          "text": "Take 1 tablet daily",
          "timing": {
            "code": {
              "text": "1 time daily"
            }
          },
          "doseAndRate": [
            {
              "doseQuantity": {
                "value": 1,
                "unit": "tablet",
                "system": "http://unitsofmeasure.org",
                "code": "{tbl}"
              }
            }
          ]
        }
      ],
      "search": {
        "mode": "match"
      }
    }
  ]
}
```


Change log

Epic Version	Description	Type
February 2026	The Outside Record FHIR APIs now validate member coverage and return only resources relevant to the member's coverage enrollment. Previously they returned resources unrelated to the member's coverage.	Breaking Change

November 2025 | The Outside Record FHIR APIs are no longer enabled in the November 2025 version. Requests to these APIs do not return data. | Breaking Change

14.1.39 MedicationRequest.Read (Outside Record) (R4)

File: site/apis/14-CMS-Incoming/1-R4/11419-MedicationRequest-Read-Outside-Record-R4.html
Epic API ID | 11419
FHIR version | R4
Categories | CMS Incoming
API type | USCDI
A la carte | Industry-Standard Level 1 API
USCDI | Yes
Available in inpatient and other contexts | Yes
HTTP method | GET
URL template | /api/FHIR/R4/MedicationRequest/{ID}
Supports OAuth 2.0 | True
Supported user types | Backend Systems and Non-OAuth 2.0, Clinicians or Administrative Users, Patients
Performs scope validation | False
Source | https://fhir.epic.com/Specifications?api=11419

Description

Use this API to retrieve a specific instance of a patient's medication request. This FHIR resource represents an order or request for both supply of the medication and the instructions for administration of the medication to a patient.

For medications that have been dispensed, see

MedicationDispense.Read (Outside Record) (R4)

This resource can return various types of medications, including inpatient-ordered medications, clinic-administered medications (CAMS), and patient-reported medications. This API does not return reconciled medications.

This API differs from other MedicationRequest APIs because it returns data that was obtained as part of payer data exchange workflows rather than directly recorded during patient care. This data can come from payers, providers, or loaded from other FHIR servers. Because this data doesn't originate from the organization being queried, users of this API should be aware that the data might be unverified, incomplete, or duplicative. This API can be used to exchange data between both providers and payers but is generally not recommended for use in patient treatment scenarios.

Data from outside payer and provider systems is saved to an organization's database and returned in a standard format, documented below. Data loaded from other FHIR servers is returned in the format the organization received it. Because of this, the documentation below does not apply to these loaded resources. These resources can include any elements from the FHIR specification and can be distinguished from other resources by the presence of meta.tag set to "external-bulk-data".

Request parameters

Name | Type | Optional | Array | Cardinality | Description
ID | token | Required | | | A MedicationRequest FHIR ID.

Response elements

Name | Type | Optional | Array | Cardinality | Description
MedicationRequest (R4) | MedicationRequest | | | 1..1 | An instance of the R4 MedicationRequest FHIR resource.
MedicationRequest (R4).authoredOn | dateTime | | | 0..1 | When the request was initially authored.
MedicationRequest (R4).category | CodeableConcept | | Yes | 1..* | The context in which the medication was requested. The following code and system are always returned: Code: external-medication-request Terminology system: http://open.epic.com/FHIR/StructureDefinition/MedicationRequest-category In addition, the following codes are also supported: inpatient outpatient community discharge Terminology system: https://hl7.org/fhir/R4/codesystem-medicationrequest-category.html
MedicationRequest (R4).dispenseRequest | BackboneElement | | | 0..1 | The number of refills permitted to be dispensed and the quantity of medication per dispense.
MedicationRequest (R4).dispenseRequest.numberOfRepeatsAllowed | unsignedInt | | | 0..1 | Number of refills authorized.
MedicationRequest (R4).dispenseRequest.quantity | Quantity | | | 0..1 | Amount of medication to supply per dispense.
MedicationRequest (R4).dosageInstruction | Dosage | | Yes | 0..1 | How the medication should be taken.
MedicationRequest (R4).dosageInstruction.doseAndRate | BackboneElement | | Yes | 0..* | Amount of medication administered.
MedicationRequest (R4).dosageInstruction.doseAndRate.doseQuantity | Quantity | | | 0..1 | Amount of medication per dose.
MedicationRequest (R4).dosageInstruction.text | string | | | 0..1 | Free text dosage instructions such as SIG.
MedicationRequest (R4).dosageInstruction.timing | Timing | | | 0..1 | When medication should be administered.
MedicationRequest (R4).id | id | | | 1..1 | The unique FHIR ID for the MedicationRequest.
MedicationRequest (R4).intent | code | | | 1..1 | The kind of medication order. This is always plan.
MedicationRequest (R4).medicationCodeableConcept | CodeableConcept | | | 1..1 | Codes associated with the medication to be taken.
MedicationRequest (R4).meta | Meta | | | | Metadata about the resource, including information about the origin or source of the data.
MedicationRequest (R4).meta.tag | Coding | | Yes | | Set to external-bulk-data for resources originally loaded from another FHIR server. If this element is set to external-bulk-data, all other element-level documentation does not apply to the resource. The resource content might vary and can include any elements allowed by the FHIR specification.
MedicationRequest (R4).reportedBoolean | boolean | | | 0..1 | True means that the organization you request this record from is not the primary source of information, and it was received from another organization. This will always return true.
MedicationRequest (R4).requester | Reference | | | 0..1 | Who or what created the request. This would be a display only reference.

MedicationRequest (R4).status | code | | | 1..1 | A code specifying the state of the prescribing event. Describes the lifecycle of the prescription. Can be any of the following: active on-hold completed stopped
MedicationRequest (R4).subject | Reference | | | 1..1 | Reference to the Patient resource the medication request is for.

Sample request

```
GET https://hostname/instance/api/FHIR/R4/MedicationRequest/fKeXQgfN5SlPQMXDw4sbXUR9XsNvMjRncLK-QPfP1U8w4
```

Sample response


```
{
  "resourceType": "MedicationRequest",
  "id": "fKeXQgfN5SlPQMXDw4sbXUR9XsNvMjRncLK-QPfP1U8w4",
  "status": "active",
  "intent": "plan",
  "category": [
    {
      "coding": [
        {
          "system": "http://open.epic.com/FHIR/StructureDefinition/MedicationRequest-category",
          "code": "external-medication-request",
          "display": "External Medication Request"
        }
      ],
      "text": "External Medication Request"
    }
  ],
  "reportedBoolean": true,
  "medicationCodeableConcept": {
    "coding": [
      {
        "system": "http://www.nlm.nih.gov/research/umls/rxnorm",
        "code": "199119",
        "display": "omeprazole (PRILOSEC) 10 MG capsule"
      },
      {
        "system": "http://hl7.org/fhir/sid/ndc",
        "code": "62175011432"
      },
      {
        "system": "urn:oid:2.16.840.1.113883.6.253",
        "code": "64691"
      },
      {
        "system": "urn:oid:2.16.840.1.113883.6.68",
        "code": "49270060006510"
      },
      {
        "system": "urn:oid:2.16.840.1.113883.6.162",
        "code": "64691"
      },
      {
        "system": "urn:oid:2.16.840.1.113883.6.73",
        "code": "A02BC01"
      }
    ],
    "text": "omeprazole (PRILOSEC) 10 MG capsule"
  },
  "subject": {
    "reference": "Patient/ecZx27wD2MCL3sEiZ7A2.rg3",
    "display": "FHIR, Test Patient"
  },
  "authoredOn": "2025-08-08",
  "requester": {
    "display": "Test Provider"
  },
  "dosageInstruction": [
    {
      "text": "Take 10 mg by mouth in the morning.",
      "timing": {
        "repeat": {
          "boundsPeriod": {
            "start": "2025-08-09"
          },
          "frequency": 1,
          "period": 1,
          "periodUnit": "d"
        },
        "code": {
          "text": "1 TIME DAILY PRN"
        }
      },
      "doseAndRate": [
        {
          "doseQuantity": {
            "value": 10,
            "unit": "mg",
            "system": "http://unitsofmeasure.org",
```

```
            "code": "mg"
          }
        }
      ]
    }
  ],
  "dispenseRequest": {
    "numberOfRepeatsAllowed": 3,
    "quantity": {
      "unit": "mg",
      "system": "http://unitsofmeasure.org",
      "code": "mg"
    }
  }
}
```

Change log

Epic Version | Description | Type
February 2026 | The Outside Record FHIR APIs now validate member coverage and return only resources relevant to the member's coverage enrollment. Previously they returned resources unrelated to the member's coverage. | Breaking Change
November 2025 | The Outside Record FHIR APIs are no longer enabled in the November 2025 version. Requests to these APIs do not return data. | Breaking Change

14.1.40 MedicationRequest.Read (Prior Auth) (R4)

File: site/apis/14-CMS-Incoming/1-R4/11271-MedicationRequest-Read-Prior-Auth-R4.html
Epic API ID | 11271
FHIR version | R4
Categories | CMS Incoming
API type | Industry-Standard
USCDI | No
Available in inpatient and other contexts | Yes
HTTP method | GET
URL template | /api/FHIR/R4/MedicationRequest/{ID}
Supports OAuth 2.0 | True
Supported user types | Backend Systems and Non-OAuth 2.0, Clinicians or Administrative Users, Patients
Performs scope validation | False
Source | https://fhir.epic.com/Specifications?api=11271

Description

MedicationRequest (Prior Auth) is used during CDS hooks workflows which trigger Coverage Requirements Discovery (CRD). The MedicationRequest (Prior Auth) resource can only be sent as a prefetched resource in the CDS Hooks request.

14.1.41 MedicationRequest.Search (Outside Record) (R4)

File: site/apis/14-CMS-Incoming/1-R4/11420-MedicationRequest-Search-Outside-Record-R4.html
Epic API ID | 11420
FHIR version | R4
Categories | CMS Incoming
API type | USCDI
A la carte | Industry-Standard Level 1 API
USCDI | Yes
Available in inpatient and other contexts | Yes
HTTP method | GET
URL template | /api/FHIR/R4/MedicationRequest?category={category}&date={date}&intent={intent}&patient={patient}&status={status}&subject={subject}&_count={_count}&_id={_id}&_include={_include}&_revinclude={_revinclude}
Supports OAuth 2.0 | True
Supported user types | Backend Systems and Non-OAuth 2.0, Clinicians or Administrative Users, Patients
Performs scope validation | False
Source | https://fhir.epic.com/Specifications?api=11420

Description

Use this API to search for a patient's medication requests. This FHIR resource represents orders or requests for both supply of the medications and the instructions for administration of the medications to a patient.

For medications that have been dispensed, see

MedicationDispense.Search (Outside Record) (R4)

This resource can return various types of medications, including inpatient-ordered medications, clinic-administered medications (CAMS), and patient-reported medications. This API does not return reconciled medications.

This API differs from other MedicationRequest APIs because it returns data that was obtained as part of payer data exchange workflows rather than directly recorded during patient care. This data can come from payers, providers, or loaded from other

FHIR servers. Because this data doesn't originate from the organization being queried, users of this API should be aware that the data might be unverified, incomplete, or duplicative. This API can be used to exchange data between both providers and payers but is generally not recommended for use in patient treatment scenarios.

Data from outside payer and provider systems is saved to an organization's database and returned in a standard format, documented below. Data loaded from other FHIR servers is returned in the format the organization received it. Because of this, the documentation below does not apply to these loaded resources. These resources can include any elements from the FHIR specification and can be distinguished from other resources by the presence of meta.tag set to "external-bulk-data".

Request parameters

Name | Type | Optional | Array | Cardinality | Description

_count | number | Optional | Yes | | Number of results per page.

_id | token | Optional | Yes | | FHIR resource IDs for the desired resources. Can be used in combination with _count, _include, and _revInclude. All others will be ignored.

_include | string | Optional | Yes | | Used to indicate which referenced resources to include in the search bundle.

_revinclude | string | Optional | Yes | | Used to include Provenance or AuditEvent resources that refer to search results, when available.

category | token | Optional | Yes | | Type of medication usage. Can be any of the following: inpatient outpatient community discharge external-medication-request

intent | token | Optional | Yes | | The kind of medication order. Supported type: Plan

patient | reference | Conditional | Yes | | The Patient the medication request is for. Either patient or subject must be populated.

status | token | Optional | Yes | | A code specifying the state of the prescribing event. Describes the lifecycle of the prescription. Supported codes: active on-hold completed stopped

subject | reference | Conditional | Yes | | The Patient the medication request is for. Either patient or subject must be populated.

Response elements

Name | Type | Optional | Array | Cardinality | Description

MedicationRequest (R4) | MedicationRequest | | | 1..1 | An instance of the R4 MedicationRequest FHIR resource.

MedicationRequest (R4).authoredOn | dateTime | | | 0..1 | When the request was initially authored.

MedicationRequest (R4).category | CodeableConcept | | Yes | 1..* | The context in which the medication was requested. The following code and system are always returned: Code: external-medication-request Terminology system: http://open.epic.com/FHIR/StructureDefinition/MedicationRequest-category In addition, the following codes are also supported: inpatient outpatient community discharge Terminology system: https://hl7.org/fhir/R4/codesystem-medicationrequest-category.html

MedicationRequest (R4).dispenseRequest | BackboneElement | | | 0..1 | The number of refills permitted to be dispensed and the quantity of medication per dispense.

MedicationRequest (R4).dispenseRequest.numberOfRepeatsAllowed | unsignedInt | | | 0..1 | Number of refills authorized.

MedicationRequest (R4).dispenseRequest.quantity | Quantity | | | 0..1 | Amount of medication to supply per dispense.

MedicationRequest (R4).dosageInstruction | Dosage | | Yes | 0..1 | How the medication should be taken.

MedicationRequest (R4).dosageInstruction.doseAndRate | BackboneElement | | Yes | 0..* | Amount of medication administered.

MedicationRequest (R4).dosageInstruction.doseAndRate.doseQuantity | Quantity | | | 0..1 | Amount of medication per dose.

MedicationRequest (R4).dosageInstruction.text | string | | | 0..1 | Free text dosage instructions such as SIG.

MedicationRequest (R4).dosageInstruction.timing | Timing | | | 0..1 | When medication should be administered.

MedicationRequest (R4).id | id | | | 1..1 | The unique FHIR ID for the MedicationRequest.

MedicationRequest (R4).intent | code | | | 1..1 | The kind of medication order. This is always plan.

MedicationRequest (R4).medicationCodeableConcept | CodeableConcept | | | 1..1 | Codes associated with the medication to be taken.

MedicationRequest (R4).meta | Meta | | | | Metadata about the resource, including information about the origin or source of the data.

MedicationRequest (R4).meta.tag | Coding | | Yes | | Set to external-bulk-data for resources originally loaded from another FHIR server. If this element is set to external-bulk-data, all other element-level documentation does not apply to the resource. The resource content might vary and can include any elements allowed by the FHIR specification.

MedicationRequest (R4).reportedBoolean | boolean | | | 0..1 | True means that the organization you request this record from is not the primary source of information, and it was received from another organization. This will always return true.

MedicationRequest (R4).requester | Reference | | | 0..1 | Who or what created the request. This would be a display only reference.

MedicationRequest (R4).status | code | | | 1..1 | A code specifying the state of the prescribing event. Describes the lifecycle of the prescription. Can be any of the following: active on-hold completed stopped

MedicationRequest (R4).subject | Reference | | | 1..1 | Reference to the Patient resource the medication request is for.

Sample request

```
GET https://hostname/instance/api/FHIR/R4/MedicationRequest?patient=eH7uldpmBBnp2yJkfHPkyHA3
```

Sample response


```
{
  "resourceType": "Bundle",
  "type": "searchset",
  "total": 1,
  "link": [
    {
      "relation": "self",
      "url": "https://hostname/instance/api/FHIR/R4/MedicationRequest?patient=eH7uldpmBBnp2yJkfHPkyHA3"
    }
  ],
  "entry": [
    {
      "link": [
        {
          "relation": "self",
```

```
      "url": "https://hostname/instance/api/FHIR/R4/MedicationRequest/ezOIUpaTqesgNMZeRgIj0fuSdd5MHaIn6l98zviT0W7o3"
    }
  ],
  "fullUrl":
"https://hostname/instance/api/FHIR/R4/MedicationRequest/ezOIUpaTqesgNMZeRgIj0fuSdd5MHaIn6l98zviT0W7o3",
  "resource": {
    "resourceType": "MedicationRequest",
    "id": "ezOIUpaTqesgNMZeRgIj0fuSdd5MHaIn6l98zviT0W7o3",
    "status": "active",
    "intent": "plan",
    "category": [
      {
        "coding": [
          {
            "system": "http://open.epic.com/FHIR/StructureDefinition/MedicationRequest-category",
            "code": "external-medication-request",
            "display": "External Medication Request"
          }
        ],
        "text": "External Medication Request"
      },
      {
        "coding": [
          {
            "system": "http://terminology.hl7.org/CodeSystem/medicationrequest-category",
            "code": "community",
            "display": "Community"
          }
        ],
        "text": "Community"
      }
    ],
    "reportedBoolean": true,
    "medicationCodeableConcept": {
      "coding": [
        {
          "system": "http://hl7.org/fhir/sid/ndc",
          "code": "21695-420-12",
          "display": "IBUPROFEN"
        }
      ],
      "text": "IBUPROFEN"
    },
    "subject": {
      "reference": "Patient/eH7uldpmBBnp2yJkfHPkyHA3",
      "display": "Test, Patient"
    },
    "authoredOn": "2025-08-08",
    "requester": {
      "display": "Test Provider"
    },
    "dosageInstruction": [
      {
        "text": "take this 2 times a day",
        "timing": {
          "repeat": {
            "boundsPeriod": {
              "start": "2025-08-09"
            },
            "frequency": 2,
            "period": 2,
            "periodUnit": "d"
          },
          "code": {
            "text": "2 TIME DAILY PRN"
          }
        },
        "doseAndRate": [
          {
            "doseQuantity": {
              "value": 100,
              "unit": "mg",
              "system": "http://unitsofmeasure.org",
              "code": "mg"
            }
          }
        ]
      }
    ],
    "dispenseRequest": {
      "numberOfRepeatsAllowed": 3,
      "quantity": {
        "value": 100,
        "unit": "mg",
        "system": "http://unitsofmeasure.org",
        "code": "mg"
      }
    }
  },
```

```
      "search": {
        "mode": "match"
      }
    }
  ]
}
```

Change log

Epic Version | Description | Type
February 2026 | The Outside Record FHIR APIs now validate member coverage and return only resources relevant to the member's coverage enrollment. Previously they returned resources unrelated to the member's coverage. | Breaking Change
November 2025 | The Outside Record FHIR APIs are no longer enabled in the November 2025 version. Requests to these APIs do not return data. | Breaking Change

14.1.42 MedicationRequest.Search (Prior Auth) (R4)

File: site/apis/14-CMS-Incoming/1-R4/11272-MedicationRequest-Search-Prior-Auth-R4.html
Epic API ID | 11272
FHIR version | R4
Categories | CMS Incoming
API type | Industry-Standard
USCDI | No
Available in inpatient and other contexts | Yes
HTTP method | GET
URL template | /api/FHIR/R4/MedicationRequest?category={category}&date={date}&intent={intent}&patient={patient}&status={status}&subject={subject}&_count={_count}&_id={_id}&_include={_include}&_revinclude={_revinclude}
Supports OAuth 2.0 | True
Supported user types | Backend Systems and Non-OAuth 2.0, Clinicians or Administrative Users, Patients
Performs scope validation | False
Source | https://fhir.epic.com/Specifications?api=11272

Description

MedicationRequest (Prior Auth) is used during CDS hooks workflows which trigger Coverage Requirements Discovery (CRD). The MedicationRequest (Prior Auth) resource can only be sent as a prefetched resource in the CDS Hooks request.

14.1.43 MedicationRequest.Update (Prior Auth) (R4)

File: site/apis/14-CMS-Incoming/1-R4/11268-MedicationRequest-Update-Prior-Auth-R4.html
Epic API ID | 11268
FHIR version | R4
Categories | CMS Incoming
API type | Industry-Standard
USCDI | No
Supports OAuth 2.0 | True
Supported user types | Backend Systems and Non-OAuth 2.0, Clinicians or Administrative Users
Performs scope validation | False
Source | https://fhir.epic.com/Specifications?api=11268

Description

Request

The HL7 FHIR Da Vinci Coverage Requirements Discovery (CRD) STU 2.1 (https://hl7.org/fhir/us/davinci-crd/STU2.1/) functionality is intended to allow health systems to query a health plan to determine whether services or medications require prior authorizations and if so, whether there are any additional documentation requirements or specific guidance regarding coverage.

CRD requests can only be initiated using the CDS Hooks framework (see https://fhir.epic.com/Documentation?docId=cds-hooks for details on Epic's support).

Epic supports two hooks for the purposes of triggering CRD:

* The "order-sign" CDS Hook (https://cds-hooks.hl7.org/hooks/order-sign/STU1/order-sign/) that occurs when an order is signed. CRD requests triggered by this hook contain a "draftOrders" bundle of ServiceRequest or MedicationRequest resources.

* The "appointment-book" CDS Hook (https://cds-hooks.hl7.org/hooks/appointment-book/STU1/appointment-book/) that occurs when an appointment is scheduled. CRD Requests triggered by this hook contain an "appointments" bundle of Appointment resources.

To improve performance, resources are be bundled directly into each CRD request instead of being retrieved through additional FHIR calls. This is done by configuring CDS Hooks prefetch templates for each type of hook. (See https://cds-hooks.hl7.org/STU2/#providing-fhir-resources-to-a-cds-service). Each prefetch template adds a resource to the request message under the "prefetch" element.

The extension element of a CRD request message includes at least one metadata field. "Extension:davinci-crd.configuration.coverage-info", when set to true, indicates that the receiver should respond to the request with a response type of "coverage-info" and should indicate whether the requested service is a covered benefit and whether prior authorization is required.

Response

Epic Health Systems expect CRD response messages to contain an empty "cards" array and a "systemActions" array within which the payer shall share whether the requested services and medications are covered and whether they require prior authorization.

For each service or medication for which a decision has been made, the systemActions element shall contain a slice with a type of "update" and a corresponding ServiceRequest or MedicationRequest resource, which should contain a coverage-information extension (https://hl7.org/fhir/us/davinci-crd/STU2.1/StructureDefinition-ext-coverage-information.html).

Please note that modifications to the ServiceRequest or MedicationRequest outside of the coverage-information extension will be ignored or could cause the message to be discarded.

14.1.44 Observation.Read (Outside Record Activities of Daily Living) (R4)

File: site/apis/14-CMS-Incoming/1-R4/11465-Observation-Read-Outside-Record-Activities-of-Daily-Living-R.html
Epic API ID | 11465
FHIR version | R4
Categories | CMS Incoming
API type | USCDI
A la carte | Industry-Standard Level 1 API
USCDI | Yes
Available in inpatient and other contexts | Yes
HTTP method | GET
URL template | /api/FHIR/R4/Observation/{ID}
Supports OAuth 2.0 | True
Supported user types | Backend Systems and Non-OAuth 2.0, Clinicians or Administrative Users, Patients
Performs scope validation | False
Source | https://fhir.epic.com/Specifications?api=11465

Description

Use this API to retrieve a specific instance of a patient's activities of daily living. A single overall Observation (Outside Record Activities of Daily Living)

resource represents an individual's ability to

perform

daily activities. These Observations describe aspects of functional status, cognitive status, and disability status, and might include additional elements that identify the functional domains assessed—such as mobility, self-care, communication, or cognition—as well as structured interpretations that summarize overall functional ability or impairment.

This API differs from other Observation APIs because it returns data obtained as part of payer data exchange workflows rather than directly recorded during patient care. This data can come from payers or loaded from other FHIR servers. Because this data doesn't originate from the organization being queried, users of this API should be aware that the data might be unverified, incomplete, or duplicative.

This data is loaded from other FHIR servers and returned in the format the organization received it. Because of this, the documentation below is minimal. These resources can include any elements from the FHIR specification and can be distinguished from other resources by the presence of meta.tag set to

external-bulk-data

Request parameters

Name | Type | Optional | Array | Cardinality | Description
ID | token | Required | | | The Observation FHIR ID.

Response elements

Name | Type | Optional | Array | Cardinality | Description
Observation (R4) | Observation
Observation (R4).id | id | | | 1..1 | The unique FHIR ID representing the Observation (Outside Record Activities of Daily Living) resource.
Observation (R4).meta | Meta | | | 1..1 | Metadata about the resource, including information about the origin or source of the data.
Observation (R4).meta.tag | Coding | | Yes | 1..* | Set to external-bulk-data for resources originally loaded from another FHIR server. If this element is set to external-bulk-data, the resource content might vary and can include any elements allowed by the FHIR specification.
Observation (R4).subject | Reference | | | 1..1 | Reference to a Patient resource for whom the Observation is relevant.

Sample request

```
GET https://hostname/instance/api/FHIR/R4/Observation/fLpmCluaIaxXZWoy9Wq933bRL7afy53t-SfVxfj.FmLg4
```

Sample response


```
{
    "resourceType": "Observation",
    "id": "fLpmCluaIaxXZWoy9Wq933bRL7afy53t-SfVxfj.FmLg4",
    "meta": {
        "tag": [
            {
                "system": "https://open.epic.com/FHIR/bulk-data-source",
                "code": "external-bulk-data",
                "display": "External Bulk Data"
            }
        ]
    },
    ... <r4 observation="" compliant="" elements=""> ...
}</r4>
```


14.1.45 Observation.Read (Outside Record Occupation) (R4)

File: site/apis/14-CMS-Incoming/1-R4/11467-Observation-Read-Outside-Record-Occupation-R4.html
Epic API ID | 11467
FHIR version | R4
Categories | CMS Incoming
API type | USCDI
A la carte | Industry-Standard Level 1 API
USCDI | Yes
Available in inpatient and other contexts | Yes
HTTP method | GET
URL template | /api/FHIR/R4/Observation/{ID}
Supports OAuth 2.0 | True
Supported user types | Backend Systems and Non-OAuth 2.0, Clinicians or Administrative Users, Patients
Performs scope validation | False
Source | https://fhir.epic.com/Specifications?api=11467

Description

Use this API to retrieve details about a patient's occupation. A single overall Observation (Outside Record Occupation) resource represents an individual's current or past occupation.

This API differs from other Observation APIs because it returns data obtained as part of payer data exchange workflows rather than directly recorded during patient care. This data can come from payers or loaded from other FHIR servers. Because this data doesn't originate from the organization being queried, users of this API should be aware that the data might be unverified, incomplete, or duplicative.

This data is loaded from other FHIR servers and returned in the format the organization received it. Because of this, the documentation below is minimal. These resources can include any elements from the FHIR specification and can be distinguished from other resources by the presence of meta.tag set to

external-bulk-data

Request parameters

Name | Type | Optional | Array | Cardinality | Description
ID | token | Required | | | The Observation FHIR ID.

Response elements

Name | Type | Optional | Array | Cardinality | Description
Observation (R4) | Observation
Observation (R4).id | id | | | 1..1 | The unique FHIR ID representing the Observation (Outside Record Occupation) resource.
Observation (R4).meta | Meta | | | 1..1 | Metadata about the resource, including information about the origin or source of the data.
Observation (R4).meta.tag | Coding | | Yes | 1..* | Set to external-bulk-data for resources originally loaded from another FHIR server. If this element is set to external-bulk-data, the resource content might vary and can include any elements allowed by the FHIR specification.
Observation (R4).subject | Reference | | | 1..1 | Reference to a Patient resource for whom the Observation is relevant.

Sample request

```
GET https://hostname/instance/api/FHIR/R4/Observation/f3-bIiKii7EAbO2puaSH.XrMwLhLvOma5yRUDsnzU08U4
```

Sample response


```
{
    "resourceType": "Observation",
    "id": "f3-bIiKii7EAbO2puaSH.XrMwLhLvOma5yRUDsnzU08U4",
    "meta": {
        "tag": [
            {
                "system": "https://open.epic.com/FHIR/bulk-data-source",
                "code": "external-bulk-data",
                "display": "External Bulk Data"
```

```
            }
        ]
    },
    ... <R4 Observation Compliant Elements> ...
}
```

14.1.46 Observation.Read (Outside Record Pregnancy Status) (R4)

File: site/apis/14-CMS-Incoming/1-R4/11391-Observation-Read-Outside-Record-Pregnancy-Status-R4.html
Epic API ID | 11391
FHIR version | R4
Categories | CMS Incoming
API type | USCDI
A la carte | Industry-Standard Level 1 API
USCDI | Yes
Available in inpatient and other contexts | Yes
HTTP method | GET
URL template | /api/FHIR/R4/Observation/{ID}
Supports OAuth 2.0 | True
Supported user types | Backend Systems and Non-OAuth 2.0, Clinicians or Administrative Users, Patients
Performs scope validation | False
Source | https://fhir.epic.com/Specifications?api=11391

Description

Use this API to retrieve a specific instance of a patient's pregnancy status. This represents the status of whether a patient is pregnant at a given point in time, or if they intend to become pregnant in the future.

For Observation social history resources that contain sexual orientation or smoking status information, see

Observation.Read (Outside Record Sexual Orientation) (R4)

Observation.Read (Outside Record Smoking Status) (R4)

The data returned by this API includes pregnancy statuses. This API does not return other social history data.

This API differs from other Observation APIs because it returns data that was obtained as part of payer data exchange workflows rather than directly recorded during patient care. This data can come from payers, providers, or loaded from other FHIR servers. Because this data doesn't originate from the organization being queried, users of this API should be aware that the data might be unverified, incomplete, or duplicative.

Data from outside payer and provider systems is saved to an organization's database and returned in a standard format, documented below. Data loaded from other FHIR servers is returned in the format the organization received it. Because of this, the documentation below does not apply to these loaded resources. These resources can include any elements from the FHIR specification and can be distinguished from other resources by the presence of meta.tag set to "external-bulk-data".

Request parameters

Name | Type | Optional | Array | Cardinality | Description
ID | token | Required | | | The Observation FHIR ID.

Response elements

Name | Type | Optional | Array | Cardinality | Description
Observation (R4) | Observation
Observation (R4).category | CodeableConcept | | Yes | 2..2 | This is always "social-history" and "external-social-history" to identify the resource as coming from external data. There is one category element with two category codes.
Observation (R4).code | CodeableConcept | | | 1..1 | The code representing the type of data returned. For this resource, this is always LOINC code "82810-3" for pregnancy status or LOINC code "86645-9" for pregnancy intent.
Observation (R4).effectiveDateTime | dateTime | | | 0..1 | The date on which a pregnancy status was documented or was last known to be accurate.
Observation (R4).id | id | | | 1..1 | The unique FHIR ID representing the Observation (Outside Record Pregnancy Status) resource.
Observation (R4).meta | Meta | | | | Metadata about the resource, including information about the origin or source of the data.
Observation (R4).meta.tag | Coding | | Yes | | Set to external-bulk-data for resources originally loaded from another FHIR server. If this element is set to external-bulk-data, the resource content might vary and can include any elements allowed by the FHIR specification.
Observation (R4).status | code | | | 1..1 | This is always "final".
Observation (R4).subject | Reference | | | 1..1 | The FHIR ID for the Patient whose Pregnancy Status was documented.
Observation (R4).valueCodeableConcept | CodeableConcept | | | 1..1 | The code pertaining to a Patient's Pregnancy Status as documented in an external record.

Sample request

```
GET https://hostname/instance/api/FHIR/R4/Observation/fLpmCluaIaxXZWoy9Wq933bRL7afy53t-SfVxfj.FmLg4
```

Sample response

```
{
  "resourceType": "Observation",
  "id": "fLpmCluaIaxXZWoy9Wq933bRL7afy53t-SfVxfj.FmLg4",
  "status": "final",
```

```
  "category": [
    {
      "coding": [
        {
          "system": "http://terminology.hl7.org/CodeSystem/observation-category",
          "code": "social-history",
          "display": "Social History"
        }
      ],
      "text": "Social History"
    },
    {
      "coding": [
        {
          "system": "http://open.epic.com/FHIR/StructureDefinition/observation-category",
          "code": "external-social-history",
          "display": "External Social History"
        }
      ],
      "text": "External Social History"
    }
  ],
  "code": {
    "coding": [
      {
        "system": "http://loinc.org",
        "code": "82810-3"
      }
    ],
    "text": "Pregnancy Status"
  },
  "subject": {
    "reference": "Patient/eabcdecd1hijklmnop88883",
    "display": "FHIR, Test Patient"
  },
  "effectiveDateTime": "2025-07-22",
  "valueCodeableConcept": {
    "coding": [
      {
        "system": "http://snomed.info/sct",
        "code": "77386006",
        "display": "Pregnancy"
      }
    ],
    "text": "Pregnancy"
  }
}
```


14.1.47 Observation.Read (Outside Record Results) (R4)

File: site/apis/14-CMS-Incoming/1-R4/11380-Observation-Read-Outside-Record-Results-R4.html
Epic API ID | 11380
FHIR version | R4
Categories | CMS Incoming
API type | USCDI
A la carte | Industry-Standard Level 1 API
USCDI | Yes
Available in inpatient and other contexts | Yes
HTTP method | GET
URL template | /api/FHIR/R4/Observation/{ID}
Supports OAuth 2.0 | True
Supported user types | Backend Systems and Non-OAuth 2.0, Clinicians or Administrative Users, Patients
Performs scope validation | False
Source | https://fhir.epic.com/Specifications?api=11380

Description

Use this API to retrieve a specific instance of a patient's test results.

This FHIR resource represents laboratory and non-laboratory (clinical) test results for a patient as maintained by a payer organization.

This API differs from other Observation APIs because it returns data that was obtained as part of payer data exchange workflows rather than directly recorded during patient care.

This data can come from payers, providers, or loaded from other FHIR servers. Because this data doesn't originate from the organization being queried, users of this API should be aware that the data might be unverified, incomplete, or duplicative.

Data from outside payer and provider systems is saved to an organization's database and returned in a standard format, documented below. Data loaded from other FHIR servers is returned in the format the organization received it. Because of this, the documentation below does not apply to these loaded resources. These resources can include any elements from the FHIR specification and can be distinguished from other resources by the presence of meta.tag set to "external-bulk-data".

Request parameters

Name | Type | Optional | Array | Cardinality | Description
ID | token | Required | | | The Observation (Result) FHIR ID.

Response elements

Name | Type | Optional | Array | Cardinality | Description
Observation (R4) | Observation
Observation (R4).category | CodeableConcept | | Yes | 1..* | The type of result. All Laboratory results have a category of "laboratory" System: http://terminology.hl7.org/CodeSystem/observation-category Code: laboratory All Imaging results have a category of "imaging" System: http://terminology.hl7.org/CodeSystem/observation-category Code: imaging All Procedure results have a category of "procedure" System: http://terminology.hl7.org/CodeSystem/observation-category Code: procedure Additionally, all results include a custom category of "external-results" System: http://open.epic.com/FHIR/StructureDefinition/observation-category Code: external-results
Observation (R4).code | CodeableConcept | | | 0..1 | The LOINC code pertaining to the Observation.
Observation (R4).effectiveDateTime | dateTime | | | 0..1 | This represents the date and time this order was resulted.
Observation (R4).id | id | | | 1..1 | The unique FHIR ID for an Observation (Outside Record Results) resource.
Observation (R4).interpretation | CodeableConcept | | Yes | 0..1 | Codes that identify the interpretations of observations. The interpretation code corresponds to the following value set: Valueset-observation-interpretation - FHIR v4.0.1.
Observation (R4).meta | Meta | | | | Metadata about the resource, including information about the origin or source of the data.
Observation (R4).meta.tag | Coding | | Yes | | Set to external-bulk-data for resources originally loaded from another FHIR server. If this element is set to external-bulk-data, the resource content might vary and can include any elements allowed by the FHIR specification.
Observation (R4).referenceRange | BackboneElement | | Yes | 0..* | The reference range for the result, if present.
Observation (R4).referenceRange.high | Quantity | | | 1..1 | The value of the high bound of the reference range. The high bound of the reference range endpoint is inclusive of the value.
Observation (R4).referenceRange.low | Quantity | | | 1..1 | The value of the low bound of the reference range. The low bound of the reference range endpoint is inclusive of the value.
Observation (R4).referenceRange.text | String | | | 1..1 | Plain text representation of the high and low values.
Observation (R4).status | code | | | 1..1 | The status of the result. Can be any of the following: unknown preliminary final amended
Observation (R4).subject | Reference | | | 1..1 | A reference to the Patient resource representing the subject of the result.
Observation (R4).valueQuantity | Quantity | | | 0..1 | The numeric value and unit associated with a test result. Only one of valueQuantity, valueRange, valueRatio, or valueString is present on any given resource.
Observation (R4).valueRange | Range | | | 0..1 | The value returned as a low and a high limit associated with a test result. Only one of valueQuantity, valueRange, valueRatio, or valueString is present on any given resource.
Observation (R4).valueRatio | Ratio | | | 0..1 | The value returned as a structured numeric with an operator of ":" which is associated with a test result. Only one of valueQuantity, valueRange, valueRatio, or valueString is present on any given resource.
Observation (R4).valueString | string | | | 0..1 | The value returned as a string associated with a test result. Only one of valueQuantity, valueRange, valueRatio, or valueString is present on any given resource.

Sample request

```
GET https://hostname/instance/api/FHIR/R4/Observation/f03xttJO4OUYMbn-IoMboMJeRSX11qmLV-rPbjvLd2GA4
```

Sample response


```
{
  "resourceType": "Observation",
  "id": "f03xttJO4OUYMbn-IoMboMJeRSX11qmLV-rPbjvLd2GA4",
  "status": "final",
  "category": [
    {
      "coding": [
        {
          "system": "http://open.epic.com/FHIR/StructureDefinition/observation-category",
          "code": "external-results",
          "display": "External Results"
        }
      ],
      "text": "External Results"
    },
    {
      "coding": [
        {
          "system": "http://terminology.hl7.org/CodeSystem/observation-category",
          "code": "laboratory",
          "display": "Laboratory"
        }
      ],
      "text": "Laboratory"
    }
  ],
  "code": {
    "coding": [
      {
        "system": "http://loinc.org",
        "code": "6298-4"
      }
    ],
    "text": "CBC"
  },
  "subject": {
    "reference": "Patient/ehkwz5AmaWMzCNfXDXtRLKg3",
```

```
    "display": "FHIR, Test Patient"
  },
  "effectiveDateTime": "2025-07-01T16:49:00Z",
  "interpretation": [
    {
      "coding": [
        {
          "system": "http://terminology.hl7.org/CodeSystem/v3-ObservationInterpretation",
          "code": "EXP",
          "display": "Expected"
        }
      ],
      "text": "Better"
    }
  ],
  "valueRatio": {
    "numerator": {
      "value": 1,
      "unit": "K/uL",
      "system": "http://unitsofmeasure.org",
      "code": "K/uL"
    },
    "denominator": {
      "value": 11,
      "unit": "K/uL",
      "system": "http://unitsofmeasure.org",
      "code": "K/uL"
    }
  }
}
```


14.1.48 Observation.Read (Outside Record Screening Assessment) (R4)

File: site/apis/14-CMS-Incoming/1-R4/11386-Observation-Read-Outside-Record-Screening-Assessment-R4.html
Epic API ID | 11386
FHIR version | R4
Categories | CMS Incoming
API type | USCDI
A la carte | Industry-Standard Level 1 API
USCDI | Yes
Available in inpatient and other contexts | Yes
HTTP method | GET
URL template | /api/FHIR/R4/Observation/{ID}
Supports OAuth 2.0 | True
Supported user types | Backend Systems and Non-OAuth 2.0, Clinicians or Administrative Users, Patients
Performs scope validation | False
Source | https://fhir.epic.com/Specifications?api=11386

Description

Use this API to retrieve a specific instance of a patient's assessment or question contained within an assessment. A single overall Observation (Outside Record Screening Assessment) resource representing an overall assessment can contain references to other Observation resources representing individual questions within the assessment panel. These assessments can optionally represent an assessment of risk or concern levels for a Social Drivers of Health (SDOH) domain; in those cases, there are additional elements present on the resource, like category codes for the domains assessed and an interpretation of the results.

For SDOH assessments, there can be an associated Condition (Outside Record Health Concern) resource representing a concern level assessed for the patient. These associated condition resources are only present for high or medium level concerns and are not intended to communicate a patient's diagnosis over time.

This API differs from

Observation.Read (Assessments) (R4)

and

Observation.Read (SDOH Assessments) (R4)

because it returns data that was obtained as part of payer data exchange workflows rather than directly recorded during patient care. This data can come from payers, providers, or loaded from other FHIR servers. Because this data doesn't originate from the organization being queried, users of this API should be aware that the data might be unverified, incomplete, or duplicative.

Data from outside payer and provider systems is saved to an organization's database and returned in a standard format, documented below. Data loaded from other FHIR servers is returned in the format the organization received it. Because of this, the documentation below does not apply to these loaded resources. These resources can include any elements from the FHIR specification and can be distinguished from other resources by the presence of meta.tag set to "external-bulk-data".

Request parameters

Name | Type | Optional | Array | Cardinality | Description
ID | token | Required | | | The Observation (Outside Record Screening Assessment) FHIR resource ID.

Response elements

Name | Type | Optional | Array | Cardinality | Description
Observation (R4) | Observation
Observation (R4).category | CodeableConcept | | Yes | 2..* | Always returns "survey" and "external-survey". Also returns an additional assessment-specific category for "sdoh" if relevant Also returns categories for SDOH Domains, if present. Released Epic Domains have a category of the form "X-SDOH-DOMAIN-[domain category code]", like "X-SDOH-DOMAIN-101" for postpartum depression. Domain categories can also include values from SDOHCC CodeSystem Temporary Codes - SDOH Clinical Care v2.3.0.
Observation (R4).code | CodeableConcept | | | 1..1 | The code that corresponds to the measured assessment or a particular question in a panel. These are typically LOINC codes but can be from any code system. If not present, this contains a dataAbsentReason code of "unknown" instead.
Observation (R4).dataAbsentReason | CodeableConcept | | | 0..1 | Indicates that an assessment question's answer value is missing, or the patient refused to answer a question. This will always contain a code of "unknown" or "patient-refused".
Observation (R4).effectiveDateTime | dateTime | | | 1..1 | The date and time the assessment was filled out.
Observation (R4).extension (multiple-answer-coding) (also: extension (multiple-answer-coding)) | Extension | | Yes | 0..1 | Only present in the event that a multiple-response question was asked and responded to with multiple coded answers. Each answer's code is added to a valueCoding element within the extension. The answer text is still present in valueCodeableConcept's text element when this happens. URL: http://open.epic.com/FHIR/StructureDefinition/extension/multiple-answer-coding
Observation (R4).extension (multiple-answer-coding).valueCoding | Coding | | | 0..* | Individual codes for a multi-response question's answers. These are typically LOINC codes but can be any standard code system.
Observation (R4).hasMember | Reference | | Yes | 0..* | References to Observation (Outside Record Screening Assessment) resources representing individual question-answer pairs within a panel.
Observation (R4).id | id | | | 1..1 | The unique FHIR ID for an Observation (Outside Record Screening Assessment) resource.
Observation (R4).interpretation | CodeableConcept | | Yes | 0..1 | Interpretation of an SDOH Assessment's concern level, for example "Insufficiently Active" for a high concern assessment of physical activity. This does not have a related code or code system. It is always a "text" element only.
Observation (R4).meta | Meta | | | | Metadata about the resource, including information about the origin or source of the data.
Observation (R4).meta.tag | Coding | | Yes | | Set to external-bulk-data for resources originally loaded from another FHIR server. If this element is set to external-bulk-data, the resource content might vary and can include any elements allowed by the FHIR specification.
Observation (R4).status | code | | | 1..1 | The status of the overall observation. Always hardcoded to "final".
Observation (R4).subject | Reference | | | 1..1 | The FHIR ID of the patient associated with the observation.
Observation (R4).valueCodeableConcept | CodeableConcept | | | 0..1 | The codes and text associated with an answer to a question in a panel. Only one of valueCodeableConcept, valueQuantity, or valueString is present on any given resource.
Observation (R4).valueQuantity | Quantity | | | 0..1 | The numeric value and unit associated with an overall assessment, rather than a particular question. Only one of valueCodeableConcept, valueQuantity, or valueString is present on any given resource.
Observation (R4).valueString | string | | | 0..1 | If no answer codes are present, the answer text for a question in an assessment panel. Only one of valueCodeableConcept, valueQuantity, or valueString is present on any given resource.

Sample request

```
GET https://hostname/instance/api/FHIR/R4/Observation/fIFuCN0sujsCEjxJW6kngvn8uAhKKqVvMhqcs33oWG4w4
```

Sample response


```
{
  "resourceType": "Observation",
  "id": "fIFuCN0sujsCEjxJW6kngvn8uAhKKqVvMhqcs33oWG4w4",
  "status": "final",
  "category": [
    {
      "coding": [
        {
          "system": "http://terminology.hl7.org/CodeSystem/observation-category",
          "code": "survey",
          "display": "Survey"
        }
      ],
      "text": "Survey"
    },
    {
      "coding": [
        {
          "system": "http://open.epic.com/FHIR/StructureDefinition/observation-category",
          "code": "external-survey",
          "display": "External Survey"
        }
      ],
      "text": "External Survey"
    },
    {
      "coding": [
        {
          "system": "http://hl7.org/fhir/us/core/CodeSystem/us-core-category",
          "code": "sdoh",
          "display": "sdoh"
        }
      ],
      "text": "sdoh"
    },
    {
      "coding": [
```

```
        {
          "system": "urn:oid:1.2.840.114350.1.72.1.8.1",
          "code": "X-SDOH-DOMAIN-101",
          "display": "Postpartum Depression"
        }
      ]
    }
  ],
  "code": {
    "coding": [
      {
        "system": "http://loinc.org",
        "code": "71354-5",
        "display": "Edinburgh Postnatal Depression Scale [EPDS]"
      }
    ],
    "text": "Edinburgh Postnatal Depression Scale"
  },
  "subject": {
    "reference": "Patient/eHbAXIMc5gSWa6JczktbLLQ3",
    "display": "FHIR, Test Patient"
  },
  "effectiveDateTime": "2025-08-13T05:00:00Z",
  "interpretation": [
    {
      "text": "High Risk"
    }
  ],
  "hasMember": [
    {
      "reference": "Observation/fVmjf4bSEy0nzAeZC0ltn972xG2Ab8p2xUFif8QZOrdk4",
      "display": "Edinburgh Postnatal Depression Scale Total"
    },
    {
      "reference": "Observation/fBbndoMhT61cQ.4UA4VKo-P-9g9ilrmAXiD9nXMXAQwM4",
      "display": "The thought of harming myself has occurred to me."
    }
  ]
}
```


14.1.49 Observation.Read (Outside Record SDOH Assessment) (R4)

File: site/apis/14-CMS-Incoming/1-R4/11469-Observation-Read-Outside-Record-SDOH-Assessment-R4.html
Epic API ID | 11469
FHIR version | R4
Categories | CMS Incoming
API type | USCDI
A la carte | Industry-Standard Level 1 API
USCDI | Yes
Available in inpatient and other contexts | Yes
HTTP method | GET
URL template | /api/FHIR/R4/Observation/{ID}
Supports OAuth 2.0 | True
Supported user types | Backend Systems and Non-OAuth 2.0, Clinicians or Administrative Users, Patients
Performs scope validation | False
Source | https://fhir.epic.com/Specifications?api=11469

Description

Use this API to retrieve details about a patient's social determinants of health (SDOH) assessment. A single overall Observation (Outside Record SDOH Assessment) resource represents an individual SDOH assessment answer.

This API differs from other Observation APIs because it returns data obtained as part of payer data exchange workflows rather than directly recorded during patient care. This data can come from payers or loaded from other FHIR servers. Because this data doesn't originate from the organization being queried, users of this API should be aware that the data might be unverified, incomplete, or duplicative.

This data is loaded from other FHIR servers and returned in the format the organization received it. Because of this, the documentation below is minimal. These resources can include any elements from the FHIR specification and can be distinguished from other resources by the presence of meta.tag set to

external-bulk-data

Request parameters

Name | Type | Optional | Array | Cardinality | Description
ID | token | Required | | | The Observation FHIR ID.

Response elements

Name | Type | Optional | Array | Cardinality | Description
Observation (R4) | Observation

Observation (R4).id | id | | | 1..1 | The unique FHIR ID representing the Observation (Outside Record SDOH Assessment) resource.
Observation (R4).meta | Meta | | | 1..1 | Metadata about the resource, including information about the origin or source of the data.
Observation (R4).meta.tag | Coding | | Yes | 1..* | Set to external-bulk-data for resources originally loaded from another FHIR server. If this element is set to external-bulk-data, the resource content might vary and can include any elements allowed by the FHIR specification.
Observation (R4).subject | Reference | | | 1..1 | Reference to a Patient resource for whom the Observation is relevant.

Sample request

```
GET https://hostname/instance/api/FHIR/R4/Observation/f3-bIiKii7EAbO2puaSH.XrMwLhLvOma5yRUDsnzU08U5
```

Sample response

```
{
    "resourceType": "Observation",
    "id": "f3-bIiKii7EAbO2puaSH.XrMwLhLvOma5yRUDsnzU08U5",
    "meta": {
        "tag": [
            {
                "system": "https://open.epic.com/FHIR/bulk-data-source",
                "code": "external-bulk-data",
                "display": "External Bulk Data"
            }
        ]
    },
    ... <R4 Observation Compliant Elements> ...
}
```

14.1.50 Observation.Read (Outside Record Sexual Orientation) (R4)

File: site/apis/14-CMS-Incoming/1-R4/11375-Observation-Read-Outside-Record-Sexual-Orientation-R4.html
Epic API ID | 11375
FHIR version | R4
Categories | CMS Incoming
API type | USCDI
A la carte | Industry-Standard Level 1 API
USCDI | Yes
Available in inpatient and other contexts | Yes
HTTP method | GET
URL template | /api/FHIR/R4/Observation/{ID}
Supports OAuth 2.0 | True
Supported user types | Backend Systems and Non-OAuth 2.0, Clinicians or Administrative Users, Patients
Performs scope validation | False
Source | https://fhir.epic.com/Specifications?api=11375

Description

Use this API to retrieve a specific instance of a patient's sexual orientation. This represents the status of a patient's sexual orientation at a given point in time.

For Observation social history resources that contain smoking status or pregnancy status information, see

Observation.Read (Outside Record Smoking Status) (R4)

Observation.Read (Outside Record Pregnancy Status) (R4)

The data returned by this API includes sexual orientation data. This API does not return other social history data.

This API differs from other Observation APIs because it returns data that was obtained as part of payer data exchange workflows rather than directly recorded during patient care. This data can come from payers, providers, or loaded from other FHIR servers. Because this data doesn't originate from the organization being queried, users of this API should be aware that the data might be unverified, incomplete, or duplicative.

Data from outside payer and provider systems is saved to an organization's database and returned in a standard format, documented below. Data loaded from other FHIR servers is returned in the format the organization received it. Because of this, the documentation below does not apply to these loaded resources. These resources can include any elements from the FHIR specification and can be distinguished from other resources by the presence of meta.tag set to "external-bulk-data".

Request parameters

Name | Type | Optional | Array | Cardinality | Description
ID | token | Required | | | The Observation (Outside Record Sexual Orientation) FHIR ID.

Response elements

Name | Type | Optional | Array | Cardinality | Description
Observation (R4) | Observation
Observation (R4).category | CodeableConcept | | Yes | 2..2 | This is always "social-history" and "external-social-history" to identify the resource as coming from external data. There is one category element with two category codes.
Observation (R4).code | CodeableConcept | | | 1..1 | The code representing the type of data returned. This is always LOINC code "76690-7" for sexual orientation.

Observation (R4).effectiveDateTime | dateTime | | | 0..1 | The date on which a sexual orientation was documented or was last known to be accurate.
Observation (R4).id | id | | | 1..1 | The unique Observation (Outside Record Sexual Orientation) FHIR ID.
Observation (R4).meta | Meta | | | | Metadata about the resource, including information about the origin or source of the data.
Observation (R4).meta.tag | Coding | | Yes | | Set to external-bulk-data for resources originally loaded from another FHIR server. If this element is set to external-bulk-data, the resource content might vary and can include any elements allowed by the FHIR specification.
Observation (R4).status | code | | | 1..1 | This is always "final".
Observation (R4).subject | Reference | | | 1..1 | The FHIR ID for the Patient whose sexual orientation was documented.
Observation (R4).valueCodeableConcept | CodeableConcept | | | 1..1 | A code pertaining to a patient's sexual orientation as documented in an external record.

Sample request

```
GET https://hostname/instance/api/FHIR/R4/Observation/fjrQwDUAkMyP98rxjFgMT8BUMPsO9yc0o11PwuJnObVQ4
```

Sample response


```
{
  "resourceType": "Observation",
  "id": "fjrQwDUAkMyP98rxjFgMT8BUMPsO9yc0o11PwuJnObVQ4",
  "status": "final",
  "category": [
    {
      "coding": [
        {
          "system": "http://terminology.hl7.org/CodeSystem/observation-category",
          "code": "social-history",
          "display": "Social History"
        }
      ],
      "text": "Social History"
    },
    {
      "coding": [
        {
          "system": "http://open.epic.com/FHIR/StructureDefinition/observation-category",
          "code": "external-social-history",
          "display": "External Social History"
        }
      ],
      "text": "External Social History"
    }
  ],
  "code": {
    "coding": [
      {
        "system": "http://loinc.org",
        "code": "76690-7"
      }
    ],
    "text": "Sexual Orientation"
  },
  "subject": {
    "reference": "Patient/e4HLVJKlDwzIO1rWv0JtNYg3",
    "display": "Fhir, Testpatient"
  },
  "effectiveDateTime": "2025-07-22",
  "valueCodeableConcept": {
    "coding": [
      {
        "system": "http://snomed.info/sct",
        "code": "42035005",
        "display": "Bisexual (finding)"
      }
    ],
    "text": "Bisexual"
  }
}
```


14.1.51 Observation.Read (Outside Record Smoking Status) (R4)

File: site/apis/14-CMS-Incoming/1-R4/11379-Observation-Read-Outside-Record-Smoking-Status-R4.html
Epic API ID | 11379
FHIR version | R4
Categories | CMS Incoming
API type | USCDI
A la carte | Industry-Standard Level 1 API
USCDI | Yes
Available in inpatient and other contexts | Yes
HTTP method | GET
URL template | /api/FHIR/R4/Observation/{ID}
Supports OAuth 2.0 | True
Supported user types | Backend Systems and Non-OAuth 2.0, Clinicians or Administrative Users, Patients
Performs scope validation | False

Source | https://fhir.epic.com/Specifications?api=11379

Description

Use this API to retrieve a specific instance of a patient's smoking status. This represents the status of a patient's smoking habits at a given point in time.

For Observation social history resources that contain sexual orientation or pregnancy status information, see

Observation.Read (Outside Record Sexual Orientation) (R4)

Observation.Read (Outside Record Pregnancy Status) (R4)

The data returned by this API includes smoking statuses. This API does not return other social history data.

This API differs from other Observation APIs because it returns data that was obtained as part of payer data exchange workflows rather than directly recorded during patient care. This data can come from payers, providers, or loaded from other FHIR servers. Because this data doesn't originate from the organization being queried, users of this API should be aware that the data might be unverified, incomplete, or duplicative.

Data from outside payer and provider systems is saved to an organization's database and returned in a standard format, documented below. Data loaded from other FHIR servers is returned in the format the organization received it. Because of this, the documentation below does not apply to these loaded resources. These resources can include any elements from the FHIR specification and can be distinguished from other resources by the presence of meta.tag set to "external-bulk-data".

Request parameters

Name | Type | Optional | Array | Cardinality | Description
ID | token | Required | | | The Observation (Outside Record Smoking Status) FHIR ID

Response elements

Name | Type | Optional | Array | Cardinality | Description
Observation (R4) | Observation
Observation (R4).category | CodeableConcept | | Yes | 2..2 | This is always "social-history" and "external-social-history" to identify the resource as coming from external data.
Observation (R4).code | CodeableConcept | | | 1..1 | The code representing the type of data returned. For this resource, this is always LOINC code "72166-2" for smoking status.
Observation (R4).effectiveDateTime | dateTime | | | 1..1 | The date on which a smoking status was documented or was last known to be accurate. This might have a dataAbsentReason if no actual date is present.
Observation (R4).id | id | | | 1..1 | The unique FHIR ID representing the Observation (Outside Record Smoking Status) resource.
Observation (R4).meta | Meta | | | | Metadata about the resource, including information about the origin or source of the data.
Observation (R4).meta.tag | Coding | | Yes | | Set to external-bulk-data for resources originally loaded from another FHIR server. If this element is set to external-bulk-data, the resource content might vary and can include any elements allowed by the FHIR specification.
Observation (R4).status | code | | | 1..1 | This is always "final".
Observation (R4).subject | Reference | | | 1..1 | The FHIR ID for the patient whose smoking status was documented.
Observation (R4).valueCodeableConcept | CodeableConcept | | | 1..1 | The SNOMED code pertaining to a patient's smoking status as documented in an external record.

Sample request

```
GET https://hostname/instance/api/FHIR/R4/Observation/fLpmCluaIaxXZWoy9Wq933bRL7afy53t-SfVxfj.FmLg4
```

Sample response


```
{
  "resourceType": "Observation",
  "id": "fLpmCluaIaxXZWoy9Wq933bRL7afy53t-SfVxfj.FmLg4",
  "status": "final",
  "category": [
    {
      "coding": [
        {
          "system": "http://terminology.hl7.org/CodeSystem/observation-category",
          "code": "social-history",
          "display": "Social History"
        }
      ],
      "text": "Social History"
    },
    {
      "coding": [
        {
          "system": "http://open.epic.com/FHIR/StructureDefinition/observation-category",
          "code": "external-social-history",
          "display": "External Social History"
        }
      ],
      "text": "External Social History"
    }
  ],
  "code": {
    "coding": [
```

```
      {
        "system": "http://loinc.org",
        "code": "72166-2"
      }
    ],
    "text": "Smoking Status"
  },
  "subject": {
    "reference": "Patient/eabcdecd1hijklmnop88883",
    "display": "FHIR, Test Patient"
  },
  "effectiveDateTime": "2025-07-22",
  "valueCodeableConcept": {
    "coding": [
      {
        "system": "http://snomed.info/sct",
        "code": "449868002",
        "display": "Smokes tobacco daily"
      }
    ],
    "text": "Smokes tobacco daily"
  }
}
```


14.1.52 Observation.Read (Outside Record Vital Signs) (R4)

File: site/apis/14-CMS-Incoming/1-R4/11421-Observation-Read-Outside-Record-Vital-Signs-R4.html
Epic API ID | 11421
FHIR version | R4
Categories | CMS Incoming
API type | USCDI
A la carte | Industry-Standard Level 1 API
USCDI | Yes
Available in inpatient and other contexts | Yes
HTTP method | GET
URL template | /api/FHIR/R4/Observation/{ID}
Supports OAuth 2.0 | True
Supported user types | Backend Systems and Non-OAuth 2.0, Clinicians or Administrative Users, Patients
Performs scope validation | False
Source | https://fhir.epic.com/Specifications?api=11421

Description

Use this API to retrieve a specific instance of a vital sign for a patient. The following types of vital sign information and corresponding LOINC codes are supported:

* 2708-6 Oxygen saturation in arterial blood

* 29463-7 Body weight

* 39156-5 Body Mass Index

* 59408-5 Oxygen saturation in arterial blood by pulse oximetry (SpO2)

* 59576-9 Body Mass Index Percentile

* 8302-2 Body height

* 8310-5 Body temperature

* 85354-9 Blood pressure systolic and diastolic

* 8867-4 Heart rate

* 9279-1 Respiratory rate

* 9843-4 Head occipital-frontal circumference by tape measure

The data returned by this API includes vital sign measurements. This API does not return growth chart information or percentile values outside of BMI percentile.

This API differs from other Observation APIs because it returns data that was obtained as part of payer data exchange workflows rather than directly recorded during patient care. This data can come from payers, providers, or loaded from other FHIR servers. Because this data doesn't originate from the organization being queried, users of this API should be aware that the data might be unverified, incomplete, or duplicative.

Data from outside payer and provider systems is saved to an organization's database and returned in a standard format, documented below. Data loaded from other FHIR servers is returned in the format the organization received it. Because of this, the documentation below does not apply to these loaded resources. These resources can include any elements from the FHIR specification and can be distinguished from other resources by the presence of meta.tag set to "external-bulk-data".

Request parameters

Name | Type | Optional | Array | Cardinality | Description
ID | token | Required | | | Observation (Outside Record Vital Sign) FHIR resource ID

Response elements

Name | Type | Optional | Array | Cardinality | Description

Observation (R4) | Observation

Observation (R4).category | CodeableConcept | | Yes | 2..2 | This element always returns "vital-signs" and "external-vital-signs". There is one category element with two category codes.

Observation (R4).code | CodeableConcept | | | 1..1 | Coded value for what is being measured. This is always a LOINC code. The following types of vital information and corresponding LOINC codes are supported: 2708-6 Oxygen saturation in arterial blood 29463-7 Body weight 39156-5 Body Mass Index 59408-5 Oxygen saturation in arterial blood by pulse oximetry (SpO2) 59576-9 Body Mass Index Percentile 8302-2 Body height 8310-5 Body temperature 85354-9 Blood pressure systolic and diastolic 8867-4 Heart rate 9279-1 Respiratory rate 9843-4 Head occipital-frontal circumference by tape measure

Observation (R4).component | BackboneElement | | Yes | 0..2 | Includes extra information about the Observation. Populated only for blood pressure.

Observation (R4).component.code | CodeableConcept | | | 1..1 | Code for the type of blood pressure represented in a component. This is always one of the following: 8480-6: Systolic pressure 8462-4: Diastolic pressure

Observation (R4).component.dataAbsentReason | CodeableConcept | | | 0..1 | Indicates that an Observation value is missing. This is always "unknown" for systolic blood pressure values in Observations for diastolic-only blood pressure flowsheets, or for diastolic blood pressure values in Observations for systolic-only blood pressure flowsheets.

Observation (R4).component.valueQuantity | Quantity | | | 0..1 | The value of the systolic or diastolic blood pressure measurement, with appropriate units. Units for blood pressure are always mm[Hg]

Observation (R4).effectiveDateTime | dateTime | | | 1..1 | The date and time the Observation was taken.

Observation (R4).id | id | | | 1..1 | Unique FHIR ID for the vital sign resource.

Observation (R4).meta | Meta | | | | Metadata about the resource, including information about the origin or source of the data.

Observation (R4).meta.tag | Coding | | Yes | | Set to external-bulk-data for resources originally loaded from another FHIR server. If this element is set to external-bulk-data, the resource content might vary and can include any elements allowed by the FHIR specification.

Observation (R4).status | code | | | 1..1 | The status of the Observation. This element always returns "final".

Observation (R4).subject | Reference | | | 1..1 | The FHIR ID for the Patient a vital sign was measured for.

Observation (R4).valueQuantity | Quantity | | | 0..1 | The value of the vital sign measurement, with appropriate units.

Sample request

```
GET https://hostname/instance/api/FHIR/R4/Observation/fl465hCyfIRcTrn7h8YG-bfPz0nAFvckVIMmOvvcRQPw4
```

Sample response


```
{
  "resourceType": "Observation",
  "id": "fl465hCyfIRcTrn7h8YG-bfPz0nAFvckVIMmOvvcRQPw4",
  "status": "final",
  "category": [
    {
      "coding": [
        {
          "system": "http://terminology.hl7.org/CodeSystem/observation-category",
          "code": "vital-signs",
          "display": "Vital Signs"
        }
      ],
      "text": "Vital Signs"
    },
    {
      "coding": [
        {
          "system": "http://open.epic.com/FHIR/StructureDefinition/observation-category",
          "code": "external-vital-signs",
          "display": "External Vital Signs"
        }
      ],
      "text": "External Vital Signs"
    }
  ],
  "code": {
    "coding": [
      {
        "system": "http://loinc.org",
        "code": "85354-9",
        "display": "Blood pressure panel with all children optional"
      }
    ],
    "text": "Blood pressure panel with all children optional"
  },
  "subject": {
    "reference": "Patient/eabcdecd1hijklmnop88883",
    "display": "FHIR, Test Patient"
  },
  "effectiveDateTime": "2025-07-02T15:24:00Z",
  "component": [
    {
      "code": {
        "coding": [
          {
            "system": "http://loinc.org",
            "code": "8480-6",
            "display": "Systolic Blood Pressure"
          }
```

```
        ],
        "text": "Systolic Blood Pressure"
      },
      "valueQuantity": {
        "value": 120,
        "unit": "millimeter of mercury",
        "system": "http://unitsofmeasure.org",
        "code": "mm[Hg]"
      }
    },
    {
      "code": {
        "coding": [
          {
            "system": "http://loinc.org",
            "code": "8462-4",
            "display": "Diastolic Blood Pressure"
          }
        ],
        "text": "Diastolic Blood Pressure"
      },
      "valueQuantity": {
        "value": 80,
        "unit": "millimeter of mercury",
        "system": "http://unitsofmeasure.org",
        "code": "mm[Hg]"
      }
    }
  ]
}
```


14.1.53 Observation.Search (Outside Record Activities of Daily Living) (R4)

File: site/apis/14-CMS-Incoming/1-R4/11466-Observation-Search-Outside-Record-Activities-of-Daily-Living.html
Epic API ID | 11466
FHIR version | R4
Categories | CMS Incoming
API type | USCDI
A la carte | Industry-Standard Level 1 API
USCDI | Yes
Available in inpatient and other contexts | Yes
HTTP method | GET
URL template | /api/FHIR/R4/Observation?based-on={based-on}&category={category}&code={code}&date={date}&focus={focus}&issued={issued}&patient={patient}&subject={subject}&_count={_count}&_id={_id}&_include={_include}&_revinclude={_revinclude}
Supports OAuth 2.0 | True
Supported user types | Backend Systems and Non-OAuth 2.0, Clinicians or Administrative Users, Patients
Performs scope validation | False
Source | https://fhir.epic.com/Specifications?api=11466

Description

Use this API to search for patient's activities of daily living resources. A single overall Observation (Outside Record Activities of Daily Living) resource represents an individual's ability to perform daily activities. These Observations describe aspects of functional status, cognitive status, and disability status, and might include additional elements that identify the functional domains assessed—such as mobility, self-care, communication, or cognition—as well as structured interpretations that summarize overall functional ability or impairment.

This API differs from other Observation APIs because it returns data obtained as part of payer data exchange workflows rather than directly recorded during patient care. This data can come from payers or loaded from other FHIR servers. Because this data doesn't originate from the organization being queried, users of this API should be aware that the data might be unverified, incomplete, or duplicative.

This data is loaded from other FHIR servers and returned in the format the organization received it. Because of this, the documentation below is minimal. These resources can include any elements from the FHIR specification and can be distinguished from other resources by the presence of meta.tag set to

external-bulk-data

Request parameters

Name | Type | Optional | Array | Cardinality | Description
_count | number | Optional | Yes | | Number of results per page.
_id | token | Optional | Yes | | FHIR resource IDs for the desired resources. Can be used in combination with _count, _include, and _revInclude. All others will be ignored.
_include | string | Optional | Yes | | Used to indicate which referenced resources to include in the search bundle.
_revinclude | string | Optional | Yes | | Used to include Provenance or AuditEvent resources that refer to search results, when available.
category | token | Conditional | Yes | | This is always either functional-status, cognitive-status, or disability-status. Either a category or a code must be provided.
code | token | Conditional | Yes | | A code on the Observation. Either a category or a code must be provided.
date | date | Optional | Yes | | Date when the Observation occurred.

patient | reference | Conditional | Yes | | Reference to a Patient resource whose activities of daily living Observation was documented. Either patient or subject must be populated. If patient and subject are both populated, they must be identical.
subject | reference | Conditional | Yes | | Reference to a Patient resource whose activities of daily living Observation was documented. Either patient or subject must be populated. If patient and subject are both populated, they must be identical.

Request parameters (post-filtered search parameters)

Name | Type | Optional | Array | Cardinality | Description
status | token | Optional | Yes | | The status of the Observation.

Response elements

Name | Type | Optional | Array | Cardinality | Description
Observation (R4) | Observation
Observation (R4).id | id | | | 1..1 | The unique FHIR ID representing the Observation (Outside Record Activities of Daily Living) resource.
Observation (R4).meta | Meta | | | 1..1 | Metadata about the resource, including information about the origin or source of the data.
Observation (R4).meta.tag | Coding | | Yes | 1..* | Set to external-bulk-data for resources originally loaded from another FHIR server. If this element is set to external-bulk-data, the resource content might vary and can include any elements allowed by the FHIR specification.
Observation (R4).subject | Reference | | | 1..1 | Reference to a Patient resource for whom the Observation is relevant.

Sample request

```
GET https://hostname/instance/api/FHIR/R4/Observation?patient=ewkziDgGIYcHews463gzKyQ3&category=functional-
    status,cognitive-status,disability-status
```

Sample response


```
{
    "resourceType": "Bundle",
    "type": "searchset",
    "total": 1,
    "link": [
        {
            "relation": "self",
            "url":
    "https://hostname/instance/api/FHIR/R4/Observation/?patient=ewkziDgGIYcHews463gzKyQ3&category=functional-
    status,cognitive-status,disability-status"
        }
    ],
    "entry": [
        {
            "link": [
                {
                    "relation": "self",
                    "url": "https://hostname/instance/api/FHIR/R4/Observation/egRzL.QI2v-
    y35mh3e0CKSyyJe8k6bAUPW58YbJkpb9AfdMRRph6aI2aZ07Ha2DeS31-Z7sMw3sjptZF8-sCqYg3"
                }
            ],
            "fullUrl": "https://hostname/instance/api/FHIR/R4/Observation/egRzL.QI2v-
    y35mh3e0CKSyyJe8k6bAUPW58YbJkpb9AfdMRRph6aI2aZ07Ha2DeS31-Z7sMw3sjptZF8-sCqYg3",
            "resource": {
                "resourceType": "Observation",
                "id": "egRzL.QI2v-y35mh3e0CKSyyJe8k6bAUPW58YbJkpb9AfdMRRph6aI2aZ07Ha2DeS31-Z7sMw3sjptZF8-sCqYg3",
                "meta": {
                    "tag": [
                        {
                            "system": "https://open.epic.com/FHIR/bulk-data-source",
                            "code": "external-bulk-data",
                            "display": "External Bulk Data"
                        }
                    ]
                },
                ... <R4 Observation Compliant Elements> ...
            }
        }
    ]
}
```


14.1.54 Observation.Search (Outside Record Occupation) (R4)

File: site/apis/14-CMS-Incoming/1-R4/11468-Observation-Search-Outside-Record-Occupation-R4.html
Epic API ID | 11468
FHIR version | R4
Categories | CMS Incoming
API type | USCDI
A la carte | Industry-Standard Level 1 API
USCDI | Yes
Available in inpatient and other contexts | Yes
HTTP method | GET
URL template | /api/FHIR/R4/Observation?based-on={based-on}&category={category}&code={code}&date={date}&focus={focus}&issued={issued}&patient={patient}&subject={subject}&_count={_count}&_id={_id}&_include={_include}&_revinclude={_revinclude}
Supports OAuth 2.0 | True

Supported user types | Backend Systems and Non-OAuth 2.0, Clinicians or Administrative Users, Patients
Performs scope validation | False
Source | https://fhir.epic.com/Specifications?api=11468

Description

Use this API to search for details about a patient's occupation. A single overall Observation (Outside Record Occupation) resource represents an individual's current or past occupation.

This API differs from other Observation APIs because it returns data obtained as part of payer data exchange workflows rather than directly recorded during patient care. This data can come from payers or loaded from other FHIR servers. Because this data doesn't originate from the organization being queried, users of this API should be aware that the data might be unverified, incomplete, or duplicative.

This data is loaded from other FHIR servers and returned in the format the organization received it. Because of this, the documentation below is minimal. These resources can include any elements from the FHIR specification and can be distinguished from other resources by the presence of meta.tag set to

external-bulk-data

Request parameters

Name | Type | Optional | Array | Cardinality | Description
_count | number | Optional | Yes | | Number of results per page.
_id | token | Optional | Yes | | FHIR resource IDs for the desired resources. Can be used in combination with _count, _include, and _revInclude. All others will be ignored.
_include | string | Optional | Yes | | Used to indicate which referenced resources to include in the search bundle.
_revinclude | string | Optional | Yes | | Used to include Provenance or AuditEvent resources that refer to search results, when available.
category | token | Conditional | Yes | | This is always social-history. Either a category or a code must be provided.
code | token | Conditional | Yes | | This is always LOINC code "11341-5". Either a category or a code must be provided.
date | date | Optional | Yes | | Date when the Observation occurred.
patient | reference | Conditional | Yes | | Reference to a Patient resource whose occupation Observation was documented. Either patient or subject must be populated. If patient and subject are both populated, they must be identical.
subject | reference | Conditional | Yes | | Reference to a Patient resource whose occupation Observation was documented. Either patient or subject must be populated. If patient and subject are both populated, they must be identical.

Request parameters (post-filtered search parameters)

Name | Type | Optional | Array | Cardinality | Description
status | token | Optional | Yes | | The status of the Observation.

Response elements

Name | Type | Optional | Array | Cardinality | Description
Observation (R4) | Observation
Observation (R4).id | id | | | 1..1 | The unique FHIR ID representing the Observation (Outside Record Occupation) resource.
Observation (R4).meta | Meta | | | 1..1 | Metadata about the resource, including information about the origin or source of the data.
Observation (R4).meta.tag | Coding | | Yes | 1..* | Set to external-bulk-data for resources originally loaded from another FHIR server. If this element is set to external-bulk-data, the resource content might vary and can include any elements allowed by the FHIR specification.
Observation (R4).subject | Reference | | | 1..1 | Reference to a Patient resource for whom the Observation is relevant.

Sample request

```
GET https://hostname/instance/api/FHIR/R4/Observation?patient=ewkziDgGIYcHews463gzKyQ3&category=social-
    history&code=11341-5
```

Sample response

```
{
    "resourceType": "Bundle",
    "type": "searchset",
    "total": 1,
    "link": [
        {
            "relation": "self",
            "url": "https://hostname/instance/api/FHIR/R4/Observation/?patient=ewkziDgGIYcHews463gzKyQ3&category=social-
    history&code=11341-5"
        }
    ],
    "entry": [
        {
            "link": [
                {
                    "relation": "self",
                    "url": "https://hostname/instance/api/FHIR/R4/Observation/egRzL.QI2v-
    y35mh3e0CKSyyJe8k6bAUPW58YbJkpb9AfdMRRph6aI2aZ07Ha2DeS31-Z7sMw3sjptZF8-sCqYg3"
                }
            ],
            "fullUrl": "https://hostname/instance/api/FHIR/R4/Observation/egRzL.QI2v-
    y35mh3e0CKSyyJe8k6bAUPW58YbJkpb9AfdMRRph6aI2aZ07Ha2DeS31-Z7sMw3sjptZF8-sCqYg3",
```

```
            "resource": {
                "resourceType": "Observation",
                "id": "egRzL.QI2v-y35mh3e0CKSyyJe8k6bAUPW58YbJkpb9AfdMRRph6aI2aZ07Ha2DeS31-Z7sMw3sjptZF8-sCqYg3",
                "meta": {
                    "tag": [
                        {
                            "system": "https://open.epic.com/FHIR/bulk-data-source",
                            "code": "external-bulk-data",
                            "display": "External Bulk Data"
                        }
                    ]
                },
                ... <R4 Observation Compliant Elements> ...
            }
        }
    ]
}
```

14.1.55 Observation.Search (Outside Record Pregnancy Status) (R4)

File: site/apis/14-CMS-Incoming/1-R4/11392-Observation-Search-Outside-Record-Pregnancy-Status-R4.html
Epic API ID | 11392
FHIR version | R4
Categories | CMS Incoming
API type | USCDI
A la carte | Industry-Standard Level 1 API
USCDI | Yes
Available in inpatient and other contexts | Yes
HTTP method | GET
URL template | /api/FHIR/R4/Observation?based-on={based-on}&category={category}&code={code}&date={date}&focus={focus}&issued={issued}&patient={patient}&subject={subject}&_count={_count}&_id={_id}&_include={_include}&_revinclude={_revinclude}
Supports OAuth 2.0 | True
Supported user types | Backend Systems and Non-OAuth 2.0, Clinicians or Administrative Users, Patients
Performs scope validation | False
Source | https://fhir.epic.com/Specifications?api=11392

Description

Use this API to search for a patient's pregnancy status. This represents the status of whether a patient is pregnant at a given point in time, or if they intend to become pregnant in the future.

For Observation social history resources that contain sexual orientation or smoking status information, see

Observation.Search (Outside Record Sexual Orientation) (R4)

Observation.Search (Outside Record Smoking Status) (R4)

The data returned by this API includes pregnancy statuses. This API does not return other social history data.

This API differs from other Observation APIs because it returns data that was obtained as part of payer data exchange workflows rather than directly recorded during patient care. This data can come from payers, providers, or loaded from other FHIR servers. Because this data doesn't originate from the organization being queried, users of this API should be aware that the data might be unverified, incomplete, or duplicative.

Data from outside payer and provider systems is saved to an organization's database and returned in a standard format, documented below. Data loaded from other FHIR servers is returned in the format the organization received it. Because of this, the documentation below does not apply to these loaded resources. These resources can include any elements from the FHIR specification and can be distinguished from other resources by the presence of meta.tag set to "external-bulk-data".

Request parameters

Name | Type | Optional | Array | Cardinality | Description
_count | number | Optional | Yes | | Number of results per page.
_id | token | Optional | Yes | | FHIR resource IDs for the desired resources. Can be used in combination with _count, _include, and _revInclude. All others are ignored.
_include | string | Optional | Yes | | Used to indicate which referenced resources to include in the search bundle.
_revinclude | string | Optional | Yes | | Used to include Provenance or AuditEvent resources that refer to search results, when available.
category | token | Conditional | Yes | | This is always either "social-history" or "external-social-history". Either a category or a code must be provided.
code | token | Conditional | Yes | | This is always LOINC code "82810-3" or LOINC code "86645-9". Either a category or a code must be provided.
date | date | Optional | Yes | | Date when the Observation occurred.
patient | reference | Conditional | Yes | | Reference to a Patient resource whose pregnancy status was documented. Either patient or subject must be present. If both patient and subject are present, they must be the same value.
subject | reference | Conditional | Yes | | Reference to a Patient resource whose pregnancy status was documented. Either patient or subject must be present. If both patient and subject are present, they must be the same value.

Request parameters (post-filtered search parameters)

Name | Type | Optional | Array | Cardinality | Description
status | token | Optional | Yes | | The status of the observation. This is always "final" for Observation (Outside Record Pregnancy Status) resources.
value-concept | token | Optional | Yes | | CodeableConcept value representing a Patient's pregnancy status.

Response elements

Name | Type | Optional | Array | Cardinality | Description

Observation (R4) | Observation

Observation (R4).category | CodeableConcept | | Yes | 2..2 | This is always "social-history" and "external-social-history" to identify the resource as coming from external data. There is one category element with two category codes.

Observation (R4).code | CodeableConcept | | | 1..1 | The code representing the type of data returned. For this resource, this is always LOINC code "82810-3" for pregnancy status or LOINC code "86645-9" for pregnancy intent.

Observation (R4).effectiveDateTime | dateTime | | | 0..1 | The date on which a pregnancy status was documented or was last known to be accurate.

Observation (R4).id | id | | | 1..1 | The unique FHIR ID representing the Observation (Outside Record Pregnancy Status) resource.

Observation (R4).meta | Meta | | | | Metadata about the resource, including information about the origin or source of the data.

Observation (R4).meta.tag | Coding | | Yes | | Set to external-bulk-data for resources originally loaded from another FHIR server. If this element is set to external-bulk-data, the resource content might vary and can include any elements allowed by the FHIR specification.

Observation (R4).status | code | | | 1..1 | This is always "final".

Observation (R4).subject | Reference | | | 1..1 | The FHIR ID for the Patient whose Pregnancy Status was documented.

Observation (R4).valueCodeableConcept | CodeableConcept | | | 1..1 | The code pertaining to a Patient's Pregnancy Status as documented in an external record.

Sample request

```
GET https://hostname/instance/api/FHIR/R4/Observation?patient=eabcdecd1hijklmnop88883&category=social-history
```

Sample response


```
{
    "resourceType": "Bundle",
    "type": "searchset",
    "total": 1,
    "link": [
        {
            "relation": "self",
            "url": "https://hostname/instance/api/FHIR/R4/Observation?patient=eabcdecd1hijklmnop88883&category=social-
    history "
        }
    ],
    "entry": [
        {
            "link": [
                {
                    "relation": "self",
                    "url":
    "https://hostname/instance/api/FHIR/R4/Observation/fLpmCluaIaxXZWoy9Wq933bRL7afy53t-SfVxfj.FmLg4"
                }
            ],
            "fullUrl":
    "https://hostname/instance/api/FHIR/R4/Observation/fLpmCluaIaxXZWoy9Wq933bRL7afy53t-SfVxfj.FmLg4",
            "resource": {
                "resourceType": "Observation",
                "id": "fLpmCluaIaxXZWoy9Wq933bRL7afy53t-SfVxfj.FmLg4",
                "status": "final",
                "category": [
                    {
                        "coding": [
                            {
                                "system": "http://terminology.hl7.org/CodeSystem/observation-category",
                                "code": "social-history",
                                "display": "Social History"
                            }
                        ],
                        "text": "Social History"
                    },
                    {
                        "coding": [
                            {
                                "system": "http://open.epic.com/FHIR/StructureDefinition/observation-category",
                                "code": "external-social-history",
                                "display": "External Social History"
                            }
                        ],
                        "text": "External Social History"
                    }
                ],
                "code": {
                    "coding": [
                        {
                            "system": "http://loinc.org",
                            "code": "82810-3"
                        }
                    ],
                    "text": "Pregnancy Status"
                },
                "subject": {
                    "reference": "Patient/eabcdecd1hijklmnop88883",
                    "display": "FHIR, Test Patient"
```

```
                },
                "effectiveDateTime": "2025-07-22",
                "valueCodeableConcept": {
                    "coding": [
                        {
                            "system": "http://snomed.info/sct",
                            "code": "77386006",
                            "display": "Pregnancy"
                        }
                    ],
                    "text": "Pregnancy"
                 },
            "search": {
                "mode": "match"
            }
        }
    ]
}
}
```


14.1.56 Observation.Search (Outside Record Results) (R4)

File: site/apis/14-CMS-Incoming/1-R4/11381-Observation-Search-Outside-Record-Results-R4.html
Epic API ID | 11381
FHIR version | R4
Categories | CMS Incoming
API type | USCDI
A la carte | Industry-Standard Level 1 API
USCDI | Yes
Available in inpatient and other contexts | Yes
HTTP method | GET
URL template | /api/FHIR/R4/Observation?based-on={based-on}&category={category}&code={code}&date={date}&focus={focus}&issued={issued}&patient={patient}&subject={subject}&_count={_count}&_id={_id}&_include={_include}&_revinclude={_revinclude}
Supports OAuth 2.0 | True
Supported user types | Backend Systems and Non-OAuth 2.0, Clinicians or Administrative Users, Patients
Performs scope validation | False
Source | https://fhir.epic.com/Specifications?api=11381

Description

Use this API to search for

a patient's test results. This FHIR resource represents laboratory and non-laboratory (clinical) test results for a patient as maintained by a payer organization.

This API differs from other Observation APIs because it returns data obtained as part of payer data exchange workflows rather than directly recorded during patient care. This data can come from payers, providers, or loaded from other FHIR servers. Because this data doesn't originate from the organization being queried, users of this API should be aware that the data might be unverified, incomplete, or duplicative.

Data from outside payer and provider systems is saved to an organization's database and returned in a standard format, documented below. Data loaded from other FHIR servers is returned in the format the organization received it. Because of this, the documentation below does not apply to these loaded resources. These resources can include any elements from the FHIR specification and can be distinguished from other resources by the presence of meta.tag set to "external-bulk-data".

Request parameters

Name | Type | Optional | Array | Cardinality | Description
_count | number | Optional | Yes | | Number of results per page.
_id | token | Optional | Yes | | FHIR resource IDs for the desired resources. Can be used in combination with _count, _include, and _revInclude. All other search parameters are ignored.
_include | string | Optional | Yes | | Used to indicate which referenced resources to include in the search bundle.
_revinclude | string | Optional | Yes | | Used to include Provenance or AuditEvent resources that refer to search results, when available.
category | token | Conditional | Yes | | The category of Observations to search for. Either category or code must be provided. For lab results: System: http://terminology.hl7.org/CodeSystem/observation-category Category.code: laboratory For imaging results: System: http://terminology.hl7.org/CodeSystem/observation-category Category.code: imaging For procedure results: System: http://terminology.hl7.org/CodeSystem/observation-category Category.code: procedure For all outside record results: System: http://open.epic.com/FHIR/StructureDefinition/observation-category Category.code: external-results
code | token | Conditional | Yes | | Search for results by LOINC code Either category or code must be provided. The format for the code parameter is <system>|<code>. Note: The <system> value is optional, but providing it can improve performance. System: http://loinc.org Code: <LOINC code>
date | date | Optional | Yes | | Clinically relevant date/time period for the result. Matches to the effectiveDateTime response element.
patient | reference | Conditional | Yes | | FHIR ID of the Patient associated with the result. Either the patient or subject parameter must be provided. If both are provided, they must match exactly.
subject | reference | Conditional | Yes | | FHIR ID of the Patient associated with the result. Either the patient or subject parameter must be provided. If both are provided, they must match exactly.

Request parameters (post-filtered search parameters)

Name | Type | Optional | Array | Cardinality | Description

status | token | Optional | Yes | | The Observation status.

Response elements

Name | Type | Optional | Array | Cardinality | Description

Observation (R4) | Observation

Observation (R4).category | CodeableConcept | | Yes | 1..* | The type of result. All Laboratory results have a category of "laboratory" System: http://terminology.hl7.org/CodeSystem/observation-category Code: laboratory All Imaging results have a category of "imaging" System: http://terminology.hl7.org/CodeSystem/observation-category Code: imaging All Procedure results have a category of "procedure" System: http://terminology.hl7.org/CodeSystem/observation-category Code: procedure Additionally, all results include a custom category of "external-results" System: http://open.epic.com/FHIR/StructureDefinition/observation-category Code: external-results

Observation (R4).code | CodeableConcept | | | 0..1 | The LOINC code pertaining to the Observation.

Observation (R4).effectiveDateTime | dateTime | | | 0..1 | This represents the date and time this order was resulted.

Observation (R4).interpretation | CodeableConcept | | Yes | 0..1 | Codes that identify the interpretations of observations. The interpretation code corresponds to the following value set: Valueset-observation-interpretation - FHIR v4.0.1.

Observation (R4).meta | Meta | | | | Metadata about the resource, including information about the origin or source of the data.

Observation (R4).meta.tag | Coding | | Yes | | Set to external-bulk-data for resources originally loaded from another FHIR server. If this element is set to external-bulk-data, the resource content might vary and can include any elements allowed by the FHIR specification.

Observation (R4).referenceRange | BackboneElement | | Yes | 0..* | The reference range for the result, if present.

Observation (R4).referenceRange.high | Quantity | | | 1..1 | The value of the high bound of the reference range. The high bound of the reference range endpoint is inclusive of the value.

Observation (R4).referenceRange.low | Quantity | | | 1..1 | The value of the low bound of the reference range. The low bound of the reference range endpoint is inclusive of the value.

Observation (R4).referenceRange.text | String | | | 1..1 | Plain text representation of the high and low values.

Observation (R4).status | code | | | 1..1 | The status of the result. Can be any of the following: unknown preliminary final amended

Observation (R4).subject | Reference | | | 1..1 | A reference to the Patient resource representing the subject of the result.

Observation (R4).valueQuantity | Quantity | | | 0..1 | The numeric value and unit associated with a test result. Only one of valueQuantity, valueRange, valueRatio, or valueString is present on any given resource.

Observation (R4).valueRange | Range | | | 0..1 | The value returned as a low and a high limit associated with a test result. Only one of valueQuantity, valueRange, valueRatio, or valueString is present on any given resource.

Observation (R4).valueRatio | Ratio | | | 0..1 | The value returned as a structured numeric with an operator of ":" which is associated with a test result. Only one of valueQuantity, valueRange, valueRatio, or valueString is present on any given resource.

Observation (R4).valueString | string | | | 0..1 | The value returned as a string associated with a test result. Only one of valueQuantity, valueRange, valueRatio, or valueString is present on any given resource.

Sample request

```
GET https://hostname/instance/api/FHIR/R4/Observation?patient=ehkwz5AmaWMzCNfXDXtRLKg3&category=external-results
```

Sample response


```
{
  "resourceType": "Bundle",
  "type": "searchset",
  "total": 2,
  "link": [
    {
      "relation": "self",
      "url": "https://hostname/instance/api/FHIR/R4/Observation?patient=ehkwz5AmaWMzCNfXDXtRLKg3&category=external-
    results"
    }
  ],
  "entry": [
    {
      "link": [
        {
          "relation": "self",
          "url": "https://hostname/instance/api/FHIR/R4/Observation/fOLOXzbfHEdeASK0j.YY6OixuXMYJODkqjXiUnvDzBrw4"
        }
      ],
      "fullUrl": "https://hostname/instance/api/FHIR/R4/Observation/fOLOXzbfHEdeASK0j.YY6OixuXMYJODkqjXiUnvDzBrw4",
      "resource": {
        "resourceType": "Observation",
        "id": "fOLOXzbfHEdeASK0j.YY6OixuXMYJODkqjXiUnvDzBrw4",
        "status": "final",
        "category": [
          {
            "coding": [
              {
                "system": "http://open.epic.com/FHIR/StructureDefinition/observation-category",
                "code": "external-results",
                "display": "External Results"
              }
            ],
            "text": "External Results"
          },
          {
            "coding": [
              {
                "system": "http://terminology.hl7.org/CodeSystem/observation-category",
                "code": "laboratory",
                "display": "Laboratory"
```

```
          }
        ],
        "text": "Laboratory"
      }
    ],
    "code": {
      "coding": [
        {
          "system": "http://loinc.org",
          "code": "54486-6"
        }
      ],
      "text": "GLUCOSE"
    },
    "subject": {
      "reference": "Patient/ehkwz5AmaWMzCNfXDXtRLKg3",
      "display": "FHIR, Test Patient"
    },
    "effectiveDateTime": "2025-07-16T18:31:00Z",
    "valueQuantity": {
      "value": 80,
      "unit": "mg/dL",
      "system": "http://unitsofmeasure.org",
      "code": "mg/dL"
    }
  },
  "search": {
    "mode": "match"
  }
},
{
  "link": [
    {
      "relation": "self",
      "url": "https://hostname/instance/api/FHIR/R4/Observation/f03xttJO4OUYMbn-IoMboMJeRSX11qmLV-rPbjvLd2GA4"
    }
  ],
  "fullUrl": "https://hostname/instance/api/FHIR/R4/Observation/f03xttJO4OUYMbn-IoMboMJeRSX11qmLV-rPbjvLd2GA4",
  "resource": {
    "resourceType": "Observation",
    "id": "f03xttJO4OUYMbn-IoMboMJeRSX11qmLV-rPbjvLd2GA4",
    "status": "final",
    "category": [
      {
        "coding": [
          {
            "system": "http://open.epic.com/FHIR/StructureDefinition/observation-category",
            "code": "external-results",
            "display": "External Results"
          }
        ],
        "text": "External Results"
      },
      {
        "coding": [
          {
            "system": "http://terminology.hl7.org/CodeSystem/observation-category",
            "code": "laboratory",
            "display": "Laboratory"
          }
        ],
        "text": "Laboratory"
      }
    ],
    "code": {
      "coding": [
        {
          "system": "http://loinc.org",
          "code": "2951-2"
        }
      ],
      "text": "Sodium [Moles/volume] in Serum/Plasma"
    },
    "subject": {
      "reference": "Patient/ehkwz5AmaWMzCNfXDXtRLKg3",
      "display": "FHIR, Test Patient"
    },
    "effectiveDateTime": "2025-07-16T18:31:00Z",
    "valueRatio": {
      "numerator": {
        "value": 1,
        "unit": "K/uL",
        "system": "http://unitsofmeasure.org",
        "code": "K/uL"
      },
      "denominator": {
        "value": 11,
        "unit": "K/uL",
        "system": "http://unitsofmeasure.org",
```

```
            "code": "K/uL"
          }
        }
      },
      "search": {
        "mode": "match"
      }
    }
  ]
}
```

14.1.57 Observation.Search (Outside Record Screening Assessment) (R4)

File: site/apis/14-CMS-Incoming/1-R4/11388-Observation-Search-Outside-Record-Screening-Assessment-R4.html
Epic API ID | 11388
FHIR version | R4
Categories | CMS Incoming
API type | USCDI
A la carte | Industry-Standard Level 1 API
USCDI | Yes
Available in inpatient and other contexts | Yes
HTTP method | GET
URL template | /api/FHIR/R4/Observation?based-on={based-on}&category={category}&code={code}&date={date}&focus={focus}&issued={issued}&patient={patient}&subject={subject}&_count={_count}&_id={_id}&_include={_include}&_revinclude={_revinclude}
Supports OAuth 2.0 | True
Supported user types | Backend Systems and Non-OAuth 2.0, Clinicians or Administrative Users, Patients
Performs scope validation | False
Source | https://fhir.epic.com/Specifications?api=11388

Description

Use this API to search for a patient's assessments and/or questions contained within overall assessments. A single overall Observation (Outside Record Screening Assessment) resource representing an overall assessment can contain references to other Observation resources representing individual questions within the assessment panel. These assessments can optionally represent an assessment of risk or concern levels for a Social Drivers of Health (SDOH) domain; in those cases, there are additional elements present on the resource, like category codes for the domains assessed and an interpretation of the results.

For SDOH assessments, there can be an associated Condition (Outside Record Health Concern) resource representing a concern level assessed for the patient. These associated condition resources are only present for high or medium level concerns and are not intended to communicate a patient's diagnosis over time.

This API differs from

Observation.Search (Assessments) (R4)

and

Observation.Search (SDOH Assessments) (R4)

because it returns data that was obtained as part of payer data exchange workflows rather than directly recorded during patient care. This data can come from payers, providers, or loaded from other FHIR servers. Because this data doesn't originate from the organization being queried, users of this API should be aware that the data might be unverified, incomplete, or duplicative.

Data from outside payer and provider systems is saved to an organization's database and returned in a standard format, documented below. Data loaded from other FHIR servers is returned in the format the organization received it. Because of this, the documentation below does not apply to these loaded resources. These resources can include any elements from the FHIR specification and can be distinguished from other resources by the presence of meta.tag set to "external-bulk-data".

Request parameters

Name | Type | Optional | Array | Cardinality | Description
_count | number | Optional | Yes | | Number of results per page.
_id | token | Optional | Yes | | FHIR resource IDs for the desired resources. Can be used in combination with _count, _include, and _revInclude. All others are ignored.
_include | string | Optional | Yes | | Used to indicate which referenced resources to include in the search bundle.
_revinclude | string | Optional | Yes | | Used to include Provenance or AuditEvent resources that refer to search results, when available.
category | token | Conditional | Yes | | Use "survey" or "external-survey" to search for all assessments. Otherwise, use "sdoh" to search for only assessments with SDOH data, or a code for a particular domain to search for assessments associated with a specific SDOH domain. SDOH domain categories can be from the SDOHCC ValueSet SDOH Category - SDOH Clinical Care v2.3.0 or be custom to Epic's released SDOH domain category values. Searches with a patient must contain either a category or code as well.
code | token | Conditional | Yes | | Coded value for the overall assessment or a particular question being asked. Searches with a patient must contain either a category or code as well.
date | date | Optional | Yes | | The date when the observation was taken.
patient | reference | Conditional | Yes | | Reference to a Patient resource the observation is about. Either this or subject must be provided. If both this and subject are provided, they must match.

subject | reference | Conditional | Yes | | Reference to a Patient resource the observation is about. Either this or patient must be provided. If both this and patient are provided, they must match.

Request parameters (post-filtered search parameters)

Name | Type | Optional | Array | Cardinality | Description

data-absent-reason | token | Optional | Yes | | The reason an observation value is missing.

has-member | reference | Optional | Yes | | Panel members the observation contains.

status | token | Optional | Yes | | The status of the observation. This is always "final" for Observation (Outside Record Screening Assessment) resources.

value-concept | token | Optional | Yes | | CodeableConcept value representing the answer to a question in an assessment.

value-string | string | Optional | Yes | | String value representing the answer to a question in an assessment.

Response elements

Name | Type | Optional | Array | Cardinality | Description

Observation (R4) | Observation

Observation (R4).category | CodeableConcept | | Yes | 2..* | Always returns "survey" and "external-survey". Also returns an additional assessment-specific category for "sdoh" if relevant Also returns categories for SDOH Domains, if present. Released Epic Domains have a category of the form "X-SDOH-DOMAIN-[domain category code]", like "X-SDOH-DOMAIN-101" for postpartum depression. Domain categories can also include values from SDOHCC CodeSystem Temporary Codes - SDOH Clinical Care v2.3.0.

Observation (R4).code | CodeableConcept | | | 1..1 | The code that corresponds to the measured assessment or a particular question in a panel. These are typically LOINC codes but can be from any code system. If not present, this contains a dataAbsentReason code of "unknown" instead.

Observation (R4).dataAbsentReason | CodeableConcept | | | 0..1 | Indicates that an assessment question's answer value is missing, or the patient refused to answer a question. This will always contain a code of "unknown" or "patient-refused".

Observation (R4).effectiveDateTime | dateTime | | | 1..1 | The date and time the assessment was filled out.

Observation (R4).extension (multiple-answer-coding) (also: extension (multiple-answer-coding)) | Extension | | Yes | 0..1 | Only present in the event that a multiple-response question was asked and responded to with multiple coded answers. Each answer's code is added to a valueCoding element within the extension. The answer text is still present in valueCodeableConcept's text element when this happens. URL: http://open.epic.com/FHIR/StructureDefinition/extension/multiple-answer-coding

Observation (R4).extension (multiple-answer-coding).valueCoding | Coding | | | 0..* | Individual codes for a multi-response question's answers. These are typically LOINC codes but can be any standard code system.

Observation (R4).hasMember | Reference | | Yes | 0..* | References to Observation (Outside Record Screening Assessment) resources representing individual question-answer pairs within a panel.

Observation (R4).id | id | | | 1..1 | The unique FHIR ID for an Observation (Outside Record Screening Assessment) resource.

Observation (R4).interpretation | CodeableConcept | | Yes | 0..1 | Interpretation of an SDOH Assessment's concern level, for example "Insufficiently Active" for a high concern assessment of physical activity. This does not have a related code or code system. It is always a "text" element only.

Observation (R4).meta | Meta | | | | Metadata about the resource, including information about the origin or source of the data.

Observation (R4).meta.tag | Coding | | Yes | | Set to external-bulk-data for resources originally loaded from another FHIR server. If this element is set to external-bulk-data, the resource content might vary and can include any elements allowed by the FHIR specification.

Observation (R4).status | code | | | 1..1 | The status of the overall observation. Always hardcoded to "final".

Observation (R4).subject | Reference | | | 1..1 | The FHIR ID of the patient associated with the observation.

Observation (R4).valueCodeableConcept | CodeableConcept | | | 0..1 | The codes and text associated with an answer to a question in a panel. Only one of valueCodeableConcept, valueQuantity, or valueString is present on any given resource.

Observation (R4).valueQuantity | Quantity | | | 0..1 | The numeric value and unit associated with an overall assessment, rather than a particular question. Only one of valueCodeableConcept, valueQuantity, or valueString is present on any given resource.

Observation (R4).valueString | string | | | 0..1 | If no answer codes are present, the answer text for a question in an assessment panel. Only one of valueCodeableConcept, valueQuantity, or valueString is present on any given resource.

Sample request

```
GET https://hostname/instance/api/FHIR/R4/Observation?patient=eHbAXIMc5gSWa6JczktbLLQ3&category=external-survey
```

Sample response


```
{
  "resourceType": "Bundle",
  "type": "searchset",
  "total": 3,
  "link": [
    {
      "relation": "self",
      "url": "https://hostname/instance/api/FHIR/R4/Observation?category=external-
    survey&patient=eHbAXIMc5gSWa6JczktbLLQ3"
    }
  ],
  "entry": [
    {
      "link": [
        {
          "relation": "self",
          "url": "https://hostname/instance/api/FHIR/R4/Observation/fkyQDiRov.VLRO0IAR32qMGlxitP5axuCkHLT.E0zBxo4"
        }
      ],
      "fullUrl": "https://hostname/instance/api/FHIR/R4/Observation/fkyQDiRov.VLRO0IAR32qMGlxitP5axuCkHLT.E0zBxo4",
      "resource": {
        "resourceType": "Observation",
        "id": "fkyQDiRov.VLRO0IAR32qMGlxitP5axuCkHLT.E0zBxo4",
        "status": "final",
        "category": [
```

```
      {
        "coding": [
          {
            "system": "http://terminology.hl7.org/CodeSystem/observation-category",
            "code": "survey",
            "display": "Survey"
          }
        ],
        "text": "Survey"
      },
      {
        "coding": [
          {
            "system": "http://open.epic.com/FHIR/StructureDefinition/observation-category",
            "code": "external-survey",
            "display": "External Survey"
          }
        ],
        "text": "External Survey"
      },
      {
        "coding": [
          {
            "system": "http://hl7.org/fhir/us/core/CodeSystem/us-core-category",
            "code": "sdoh",
            "display": "sdoh"
          }
        ],
        "text": "sdoh"
      },
      {
        "coding": [
          {
            "system": "urn:oid:1.2.840.114350.1.72.1.8.1",
            "code": "X-SDOH-DOMAIN-101",
            "display": "Postpartum Depression"
          }
        ]
      }
    ],
    "code": {
      "coding": [
        {
          "system": "http://loinc.org",
          "code": "71354-5",
          "display": "Edinburgh Postnatal Depression Scale [EPDS]"
        }
      ],
      "text": "Edinburgh Postnatal Depression Scale"
    },
    "subject": {
      "reference": "Patient/eHbAXIMc5gSWa6JczktbLLQ3",
      "display": "Fhir, Test Patient"
    },
    "effectiveDateTime": "2025-08-13T05:00:00Z",
    "valueQuantity": {
      "value": 23
    },
    "interpretation": [
      {
        "text": "High Risk"
      }
    ],
    "hasMember": [
      {
        "reference": "Observation/fffg0WV8dM22j0TKrR5kmASdpFgU3BdMuDsQDaVayDDM4",
        "display": "Edinburgh Postnatal Depression Scale Total"
      },
      {
        "reference": "Observation/fCxbwiXtxlANyFlZlAKp9vRj57Ap98giIKASEImceaU44",
        "display": "The thought of harming myself has occurred to me."
      }
    ]
  },
  "search": {
    "mode": "match"
  }
},
{
  "link": [
    {
      "relation": "self",
      "url": "https://hostname/instance/api/FHIR/R4/Observation/fCxbwiXtxlANyFlZlAKp9vRj57Ap98giIKASEImceaU44"
    }
  ],
  "fullUrl": "https://hostname/instance/api/FHIR/R4/Observation/fCxbwiXtxlANyFlZlAKp9vRj57Ap98giIKASEImceaU44",
  "resource": {
    "resourceType": "Observation",
    "id": "fCxbwiXtxlANyFlZlAKp9vRj57Ap98giIKASEImceaU44",
```

```
    "status": "final",
    "category": [
      {
        "coding": [
          {
            "system": "http://terminology.hl7.org/CodeSystem/observation-category",
            "code": "survey",
            "display": "Survey"
          }
        ],
        "text": "Survey"
      },
      {
        "coding": [
          {
            "system": "http://open.epic.com/FHIR/StructureDefinition/observation-category",
            "code": "external-survey",
            "display": "External Survey"
          }
        ],
        "text": "External Survey"
      },
      {
        "coding": [
          {
            "system": "http://hl7.org/fhir/us/core/CodeSystem/us-core-category",
            "code": "sdoh",
            "display": "sdoh"
          }
        ],
        "text": "sdoh"
      },
      {
        "coding": [
          {
            "system": "urn:oid:1.2.840.114350.1.72.1.8.1",
            "code": "X-SDOH-DOMAIN-101",
            "display": "Postpartum Depression"
          }
        ]
      }
    ],
    "code": {
      "coding": [
        {
          "system": "http://loinc.org",
          "code": "71353-7",
          "display": "The thought of harming myself has occurred to me"
        }
      ],
      "text": "The thought of harming myself has occurred to me."
    },
    "subject": {
      "reference": "Patient/eHbAXIMc5gSWa6JczktbLLQ3",
      "display": "Fhir, Test Patient"
    },
    "effectiveDateTime": "2025-08-13T05:00:00Z",
    "valueCodeableConcept": {
      "coding": [
        {
          "system": "http://loinc.org",
          "code": "LA18396-4",
          "display": "Yes, quite often"
        }
      ],
      "text": "Yes, quite often"
    }
  },
  "search": {
    "mode": "match"
  }
},
{
  "link": [
    {
      "relation": "self",
      "url": "https://hostname/instance/api/FHIR/R4/Observation/fffg0WV8dM22j0TKrR5kmASdpFgU3BdMuDsQDaVayDDM4"
    }
  ],
  "fullUrl": "https://hostname/instance/api/FHIR/R4/Observation/fffg0WV8dM22j0TKrR5kmASdpFgU3BdMuDsQDaVayDDM4",
  "resource": {
    "resourceType": "Observation",
    "id": "fffg0WV8dM22j0TKrR5kmASdpFgU3BdMuDsQDaVayDDM4",
    "status": "final",
    "category": [
      {
        "coding": [
          {
            "system": "http://terminology.hl7.org/CodeSystem/observation-category",
```

```
              "code": "survey",
              "display": "Survey"
            }
          ],
          "text": "Survey"
        },
        {
          "coding": [
            {
              "system": "http://open.epic.com/FHIR/StructureDefinition/observation-category",
              "code": "external-survey",
              "display": "External Survey"
            }
          ],
          "text": "External Survey"
        },
        {
          "coding": [
            {
              "system": "http://hl7.org/fhir/us/core/CodeSystem/us-core-category",
              "code": "sdoh",
              "display": "sdoh"
            }
          ],
          "text": "sdoh"
        },
        {
          "coding": [
            {
              "system": "urn:oid:1.2.840.114350.1.72.1.8.1",
              "code": "X-SDOH-DOMAIN-101",
              "display": "Postpartum Depression"
            }
          ]
        }
      ],
      "code": {
        "coding": [
          {
            "system": "http://loinc.org",
            "code": "99046-5",
            "display": "Total score [EPDS]"
          }
        ],
        "text": "Edinburgh Postnatal Depression Scale Total"
      },
      "subject": {
        "reference": "Patient/eHbAXIMc5gSWa6JczktbLLQ3",
        "display": "Fhir, Test Patient"
      },
      "effectiveDateTime": "2025-08-13T05:00:00Z",
      "valueString": "23"
    },
    "search": {
      "mode": "match"
    }
  }
 ]
}
```


14.1.58 Observation.Search (Outside Record SDOH Assessment) (R4)

File: site/apis/14-CMS-Incoming/1-R4/11470-Observation-Search-Outside-Record-SDOH-Assessment-R4.html
Epic API ID | 11470
FHIR version | R4
Categories | CMS Incoming
API type | USCDI
A la carte | Industry-Standard Level 1 API
USCDI | Yes
Available in inpatient and other contexts | Yes
HTTP method | GET
URL template | /api/FHIR/R4/Observation?based-on={based-on}&category={category}&code={code}&date={date}&focus={focus}&issued={issued}&patient={patient}&subject={subject}&_count={_count}&_id={_id}&_include={_include}&_revinclude={_revinclude}
Supports OAuth 2.0 | True
Supported user types | Backend Systems and Non-OAuth 2.0, Clinicians or Administrative Users, Patients
Performs scope validation | False
Source | https://fhir.epic.com/Specifications?api=11470

Description

Use this API to retrieve details about a patient's social determinants of health (SDOH) assessment. A single overall Observation (Outside Record SDOH Assessment) resource represents an individual SDOH assessment answer.

This API differs from other Observation APIs because it returns data obtained as part of payer data exchange workflows rather than directly recorded during patient care. This data can come from payers or loaded from other FHIR servers. Because this data doesn't originate from the organization being queried, users of this API should be aware that the data might be unverified, incomplete, or duplicative.

This data is loaded from other FHIR servers and returned in the format the organization received it. Because of this, the documentation below is minimal. These resources can include any elements from the FHIR specification and can be distinguished from other resources by the presence of meta.tag set to

external-bulk-data

Request parameters

Name | Type | Optional | Array | Cardinality | Description
_count | number | Optional | Yes | | Number of results per page.
_id | token | Optional | Yes | | FHIR resource IDs for the desired resources. Can be used in combination with _count, _include, and _revInclude. All others will be ignored.
_include | string | Optional | Yes | | Used to indicate which referenced resources to include in the search bundle.
_revinclude | string | Optional | Yes | | Used to include Provenance or AuditEvent resources that refer to search results, when available.
category | token | Conditional | Yes | | This is always "sdoh". Either a category or a code must be provided.
code | token | Conditional | Yes | | A code on the Observation. Either a category or a code must be provided.
date | date | Optional | Yes | | Date when the Observation occurred.
patient | reference | Conditional | Yes | | Reference to a Patient resource whose SDOH assessment Observation was documented. Either patient or subject must be populated. If patient and subject are both populated, they must be identical.
subject | reference | Conditional | Yes | | Reference to a Patient resource whose SDOH assessment Observation was documented. Either patient or subject must be populated. If patient and subject are both populated, they must be identical.

Request parameters (post-filtered search parameters)

Name | Type | Optional | Array | Cardinality | Description
status | token | Optional | Yes | | The status of the Observation.

Response elements

Name | Type | Optional | Array | Cardinality | Description
Observation (R4) | Observation
Observation (R4).id | id | | | 1..1 | The unique FHIR ID representing the Observation (Outside Record SDOH Assessment) resource.
Observation (R4).meta | Meta | | | 1..1 | Metadata about the resource, including information about the origin or source of the data.
Observation (R4).meta.tag | Coding | | Yes | 1..* | Set to external-bulk-data for resources originally loaded from another FHIR server. If this element is set to external-bulk-data, the resource content might vary and can include any elements allowed by the FHIR specification.
Observation (R4).subject | Reference | | | 1..1 | Reference to a Patient resource for whom the Observation is relevant.

Sample request

```
GET https://hostname/instance/api/FHIR/R4/Observation?patient=ewkziDgGIYcHews463gzKyQ3&category=sdoh
```

Sample response

```
{
    "resourceType": "Bundle",
    "type": "searchset",
    "total": 1,
    "link": [
        {
            "relation": "self",
            "url": "https://hostname/instance/api/FHIR/R4/Observation/?patient=ewkziDgGIYcHews463gzKyQ3&category=sdoh"
        }
    ],
    "entry": [
        {
            "link": [
                {
                    "relation": "self",
                    "url": "https://hostname/instance/api/FHIR/R4/Observation/egRzL.QI2v-
    y35mh3e0CKSyyJe8k6bAUPW58YbJkpb9AfdMRRph6aI2aZ07Ha2DeS31-Z7sMw3sjptZF8-sCqYg3"
                }
            ],
            "fullUrl": "https://hostname/instance/api/FHIR/R4/Observation/egRzL.QI2v-
    y35mh3e0CKSyyJe8k6bAUPW58YbJkpb9AfdMRRph6aI2aZ07Ha2DeS31-Z7sMw3sjptZF8-sCqYg3",
            "resource": {
                "resourceType": "Observation",
                "id": "egRzL.QI2v-y35mh3e0CKSyyJe8k6bAUPW58YbJkpb9AfdMRRph6aI2aZ07Ha2DeS31-Z7sMw3sjptZF8-sCqYg3",
                "meta": {
                    "tag": [
                        {
                            "system": "https://open.epic.com/FHIR/bulk-data-source",
                            "code": "external-bulk-data",
                            "display": "External Bulk Data"
                        }
                    ]
                },
                ... <R4 Observation Compliant Elements> ...
```

```
            }
        }
    ]
}
```

14.1.59 Observation.Search (Outside Record Sexual Orientation) (R4)

File: site/apis/14-CMS-Incoming/1-R4/11384-Observation-Search-Outside-Record-Sexual-Orientation-R4.html
Epic API ID | 11384
FHIR version | R4
Categories | CMS Incoming
API type | USCDI
A la carte | Industry-Standard Level 1 API
USCDI | Yes
Available in inpatient and other contexts | Yes
HTTP method | GET
URL template | /api/FHIR/R4/Observation?based-on={based-on}&category={category}&code={code}&date={date}&focus={focus}&issued={issued}&patient={patient}&subject={subject}&_count={_count}&_id={_id}&_include={_include}&_revinclude={_revinclude}
Supports OAuth 2.0 | True
Supported user types | Backend Systems and Non-OAuth 2.0, Clinicians or Administrative Users, Patients
Performs scope validation | False
Source | https://fhir.epic.com/Specifications?api=11384

Description

Use this API to search for a patient's sexual orientation. This represents the status of a patient's sexual orientation at a given point in time.

For Observation social history resources that contain smoking status or pregnancy status information, see

Observation.Search (Outside Record Smoking Status) (R4)

Observation.Search (Outside Record Pregnancy Status) (R4)

The data returned by this API includes sexual orientation data. This API does not return other social history data.

This API differs from other Observation APIs because it returns data that was obtained as part of payer data exchange workflows rather than directly recorded during patient care. This data can come from payers, providers, or loaded from other FHIR servers. Because this data doesn't originate from the organization being queried, users of this API should be aware that the data might be unverified, incomplete, or duplicative.

Data from outside payer and provider systems is saved to an organization's database and returned in a standard format, documented below. Data loaded from other FHIR servers is returned in the format the organization received it. Because of this, the documentation below does not apply to these loaded resources. These resources can include any elements from the FHIR specification and can be distinguished from other resources by the presence of meta.tag set to "external-bulk-data".

Request parameters

Name | Type | Optional | Array | Cardinality | Description
_count | number | Optional | Yes | | Number of results per page.
_id | token | Optional | Yes | | FHIR resource IDs for the desired resources. Can be used in combination with _count, _include, and _revInclude. All others are ignored.
_include | string | Optional | Yes | | Used to indicate which referenced resources to include in the search bundle.
_revinclude | string | Optional | Yes | | Used to include Provenance or AuditEvent resources that refer to search results, when available.
category | token | Conditional | Yes | | This is always either "social-history" or "external-social-history". Either a category or a code must be provided.
code | token | Conditional | Yes | | This is always LOINC code "76690-7". Either a category or a code must be provided.
date | date | Optional | Yes | | Date when the observation occurred.
patient | reference | Conditional | Yes | | Reference to a Patient resource whose sexual orientation was documented. Either patient or subject must be populated. If patient and subject are both populated, they must be identical.
subject | reference | Conditional | Yes | | Reference to a Patient resource whose sexual orientation was documented. Either patient or subject must be populated. If patient and subject are both populated, they must be identical.

Request parameters (post-filtered search parameters)

Name | Type | Optional | Array | Cardinality | Description
status | token | Optional | Yes | | The status of the observation. This is always "final" for Observation (Outside Record Sexual Orientation) resources.
value-concept | token | Optional | Yes | | CodeableConcept value representing a patient's sexual orientation.

Response elements

Name | Type | Optional | Array | Cardinality | Description
Observation (R4) | Observation
Observation (R4).category | CodeableConcept | | Yes | 2..2 | This is always "social-history" and "external-social-history" to identify the resource as coming from external data. There is one category element with two category codes.
Observation (R4).code | CodeableConcept | | | 1..1 | The code representing the type of data returned. This is always LOINC code "76690-7" for sexual orientation.
Observation (R4).effectiveDateTime | dateTime | | | 0..1 | The date on which a sexual orientation was documented or was last known to be accurate.
Observation (R4).id | id | | | 1..1 | The unique Observation (Outside Record Sexual Orientation) FHIR ID.

Observation (R4).meta | Meta | | | Metadata about the resource, including information about the origin or source of the data.

Observation (R4).meta.tag | Coding | | Yes | | Set to external-bulk-data for resources originally loaded from another FHIR server. If this element is set to external-bulk-data, the resource content might vary and can include any elements allowed by the FHIR specification.

Observation (R4).status | code | | | 1..1 | This is always "final".

Observation (R4).subject | Reference | | | 1..1 | The FHIR ID for the Patient whose sexual orientation was documented.

Observation (R4).valueCodeableConcept | CodeableConcept | | | 1..1 | A code pertaining to a patient's sexual orientation as documented in an external record.

Sample request

```
GET https://hostname/instance/api/FHIR/R4/Observation?patient=e4HLVJKlDwzIO1rWv0JtNYg3&category=social-history
```

Sample response


```
{
  "resourceType": "Bundle",
  "type": "searchset",
  "total": 1,
  "link": [
    {
      "relation": "self",
      "url": "https://hostname/instance/api/FHIR/R4/Observation?patient=e4HLVJKlDwzIO1rWv0JtNYg3&category=social-history
     "
    }
  ],
  "entry": [
    {
      "link": [
        {
          "relation": "self",
          "url": "https://hostname/instance/api/FHIR/R4/Observation/fjrQwDUAkMyP98rxjFgMT8BUMPsO9yc0o11PwuJnObVQ4"
        }
      ],
      "fullUrl": "https://hostname/instance/api/FHIR/R4/Observation/fjrQwDUAkMyP98rxjFgMT8BUMPsO9yc0o11PwuJnObVQ4",
      "resource": {
        "resourceType": "Observation",
        "id": "fjrQwDUAkMyP98rxjFgMT8BUMPsO9yc0o11PwuJnObVQ4",
        "status": "final",
        "category": [
          {
            "coding": [
              {
                "system": "http://terminology.hl7.org/CodeSystem/observation-category",
                "code": "social-history",
                "display": "Social History"
              }
            ],
            "text": "Social History"
          },
          {
            "coding": [
              {
                "system": "http://open.epic.com/FHIR/StructureDefinition/observation-category",
                "code": "external-social-history",
                "display": "External Social History"
              }
            ],
            "text": "External Social History"
          }
        ],
        "code": {
          "coding": [
            {
              "system": "http://loinc.org",
              "code": "76690-7"
            }
          ],
          "text": "Sexual Orientation"
        },
        "subject": {
          "reference": "Patient/e4HLVJKlDwzIO1rWv0JtNYg3",
          "display": "Fhir, Testpatient"
        },
        "effectiveDateTime": "2025-07-22",
        "valueCodeableConcept": {
          "coding": [
            {
              "system": "http://snomed.info/sct",
              "code": "42035005",
              "display": "Bisexual (finding)"
            }
          ],
          "text": "Bisexual"
        }
      },
      "search": {
        "mode": "match"
```

```
      }
    }
  ]
}
```

14.1.60 Observation.Search (Outside Record Smoking Status) (R4)

File: site/apis/14-CMS-Incoming/1-R4/11383-Observation-Search-Outside-Record-Smoking-Status-R4.html
Epic API ID | 11383
FHIR version | R4
Categories | CMS Incoming
API type | USCDI
A la carte | Industry-Standard Level 1 API
USCDI | Yes
Available in inpatient and other contexts | Yes
HTTP method | GET
URL template | /api/FHIR/R4/Observation?based-on={based-on}&category={category}&code={code}&date={date}&focus={focus}&issued={issued}&patient={patient}&subject={subject}&_count={_count}&_id={_id}&_include={_include}&_revinclude={_revinclude}
Supports OAuth 2.0 | True
Supported user types | Backend Systems and Non-OAuth 2.0, Clinicians or Administrative Users, Patients
Performs scope validation | False
Source | https://fhir.epic.com/Specifications?api=11383

Description

Use this API to search for a patient's smoking status. This represents the status of a patient's smoking habits at a given point in time.

For Observation social history resources that contain sexual orientation or pregnancy status information, see

Observation.Search (Outside Record Sexual Orientation) (R4)

Observation.Search (Outside Record Pregnancy Status) (R4)

The data returned by this API includes smoking statuses. This API does not return other social history data.

This API differs from other Observation APIs because it returns data that was obtained as part of payer data exchange workflows rather than directly recorded during patient care. This data can come from payers, providers, or loaded from other FHIR servers. Because this data doesn't originate from the organization being queried, users of this API should be aware that the data might be unverified, incomplete, or duplicative.

Data from outside payer and provider systems is saved to an organization's database and returned in a standard format, documented below. Data loaded from other FHIR servers is returned in the format the organization received it. Because of this, the documentation below does not apply to these loaded resources. These resources can include any elements from the FHIR specification and can be distinguished from other resources by the presence of meta.tag set to "external-bulk-data".

Request parameters

Name | Type | Optional | Array | Cardinality | Description
_count | number | Optional | Yes | | Number of results per page.
_id | token | Optional | Yes | | FHIR resource IDs for the desired resources. Can be used in combination with _count, _include, and _revInclude. All others are ignored.
_include | string | Optional | Yes | | Used to indicate which referenced resources to include in the search bundle.
_revinclude | string | Optional | Yes | | Used to include Provenance or AuditEvent resources that refer to search results, when available.
category | token | Conditional | Yes | | This is always either "social-history" or "external-social-history". Either a category or a code must be provided.
code | token | Conditional | Yes | | This is always LOINC code "72166-2". Either a category or a code must be provided.
date | date | Optional | Yes | | Date when the observation occurred.
patient | reference | Conditional | Yes | | Reference to a Patient resource whose smoking status was documented. Either patient or subject must be populated. If patient and subject are both populated, they must be identical.
subject | reference | Conditional | Yes | | Reference to a Patient resource whose smoking status was documented. Either patient or subject must be populated. If patient and subject are both populated, they must be identical.

Request parameters (post-filtered search parameters)

Name | Type | Optional | Array | Cardinality | Description
status | token | Optional | Yes | | The status of the observation. This is always "final" for Observation (Outside Record Smoking Status) resources.
value-concept | token | Optional | Yes | | CodeableConcept value representing a patient's smoking status.

Response elements

Name | Type | Optional | Array | Cardinality | Description
Observation (R4) | Observation
Observation (R4).category | CodeableConcept | | Yes | 2..2 | This is always "social-history" and "external-social-history" to identify the resource as coming from external data.
Observation (R4).code | CodeableConcept | | | 1..1 | The code representing the type of data returned. For this resource, this is always LOINC code "72166-2" for smoking status.
Observation (R4).effectiveDateTime | dateTime | | | 1..1 | The date on which a smoking status was documented or was last known to be accurate. This might have a dataAbsentReason if no actual date is present.

Observation (R4).id | id | | | 1..1 | The unique FHIR ID representing the Observation (Outside Record Smoking Status) resource.
Observation (R4).meta | Meta | | | | Metadata about the resource, including information about the origin or source of the data.
Observation (R4).meta.tag | Coding | | Yes | | Set to external-bulk-data for resources originally loaded from another FHIR server. If this element is set to external-bulk-data, the resource content might vary and can include any elements allowed by the FHIR specification.
Observation (R4).status | code | | | 1..1 | This is always "final".
Observation (R4).subject | Reference | | | 1..1 | The FHIR ID for the patient whose smoking status was documented.
Observation (R4).valueCodeableConcept | CodeableConcept | | | 1..1 | The SNOMED code pertaining to a patient's smoking status as documented in an external record.

Sample request

```
GET https://hostname/instance/api/FHIR/R4/Observation?patient=eabcdecd1hijklmnop88883&category=social-history
```

Sample response


```
{
  "resourceType": "Bundle",
  "type": "searchset",
  "total": 1,
  "link": [
    {
      "relation": "self",
      "url": "https://hostname/instance/api/FHIR/R4/Observation?patient=eabcdecd1hijklmnop88883&category=social-history"
    }
  ],
  "entry": [
    {
      "link": [
        {
          "relation": "self",
          "url": "https://hostname/instance/api/FHIR/R4/Observation/fLpmCluaIaxXZWoy9Wq933bRL7afy53t-SfVxfj.FmLg4"
        }
      ],
      "fullUrl": "https://hostname/instance/api/FHIR/R4/Observation/fLpmCluaIaxXZWoy9Wq933bRL7afy53t-SfVxfj.FmLg4",
      "resource": {
        "resourceType": "Observation",
        "id": "fLpmCluaIaxXZWoy9Wq933bRL7afy53t-SfVxfj.FmLg4",
        "status": "final",
        "category": [
          {
            "coding": [
              {
                "system": "http://terminology.hl7.org/CodeSystem/observation-category",
                "code": "social-history",
                "display": "Social History"
              }
            ],
            "text": "Social History"
          },
          {
            "coding": [
              {
                "system": "http://open.epic.com/FHIR/StructureDefinition/observation-category",
                "code": "external-social-history",
                "display": "External Social History"
              }
            ],
            "text": "External Social History"
          }
        ],
        "code": {
          "coding": [
            {
              "system": "http://loinc.org",
              "code": "72166-2"
            }
          ],
          "text": "Smoking Status"
        },
        "subject": {
          "reference": "Patient/eabcdecd1hijklmnop88883",
          "display": "FHIR, Test Patient"
        },
        "effectiveDateTime": "2025-07-22",
        "valueCodeableConcept": {
          "coding": [
            {
              "system": "http://snomed.info/sct",
              "code": "449868002",
              "display": "Smokes tobacco daily"
            }
          ],
          "text": "Smokes tobacco daily"
        }
      },
      "search": {
        "mode": "match"
```

```
      }
    }
  ]
}
```

14.1.61 Observation.Search (Outside Record Vital Signs) (R4)

File: site/apis/14-CMS-Incoming/1-R4/11422-Observation-Search-Outside-Record-Vital-Signs-R4.html
Epic API ID | 11422
FHIR version | R4
Categories | CMS Incoming
API type | USCDI
A la carte | Industry-Standard Level 1 API
USCDI | Yes
Available in inpatient and other contexts | Yes
HTTP method | GET
URL template | /api/FHIR/R4/Observation?based-on={based-on}&category={category}&code={code}&date={date}&focus={focus}&issued={issued}&patient={patient}&subject={subject}&_count={_count}&_id={_id}&_include={_include}&_revinclude={_revinclude}
Supports OAuth 2.0 | True
Supported user types | Backend Systems and Non-OAuth 2.0, Clinicians or Administrative Users, Patients
Performs scope validation | False
Source | https://fhir.epic.com/Specifications?api=11422

Description

Use this API to search for a patient's vital signs. The following types of vital sign information and corresponding LOINC codes are supported:

* 2708-6 Oxygen saturation in arterial blood

* 29463-7 Body weight

* 39156-5 Body Mass Index

* 59408-5 Oxygen saturation in arterial blood by pulse oximetry (SpO2)

* 59576-9 Body Mass Index Percentile

* 8302-2 Body height

* 8310-5 Body temperature

* 85354-9 Blood pressure systolic and diastolic

* 8867-4 Heart rate

* 9279-1 Respiratory rate

* 9843-4 Head occipital-frontal circumference by tape measure

The data returned by this API includes vital sign measurements. This API does not return growth chart information or percentile values outside of BMI percentile.

This API differs from other Observation APIs because it returns data that was obtained as part of payer data exchange workflows rather than directly recorded during patient care. This data can come from payers, providers, or loaded from other FHIR servers. Because this data doesn't originate from the organization being queried, users of this API should be aware that the data might be unverified, incomplete, or duplicative.

Data from outside payer and provider systems is saved to an organization's database and returned in a standard format, documented below. Data loaded from other FHIR servers is returned in the format the organization received it. Because of this, the documentation below does not apply to these loaded resources. These resources can include any elements from the FHIR specification and can be distinguished from other resources by the presence of meta.tag set to "external-bulk-data".

Request parameters

Name | Type | Optional | Array | Cardinality | Description
_count | number | Optional | Yes | | Number of results per page.
_id | token | Optional | Yes | | FHIR resource IDs for the desired resources. Can be used in combination with _count, _include, and _revInclude. All others are ignored.
_include | string | Optional | Yes | | Used to indicate which referenced resources to include in the search bundle.
_revinclude | string | Optional | Yes | | Used to include Provenance or AuditEvent resources that refer to search results, when available.
category | token | Conditional | Yes | | Use "vital-signs" or "external-vital-signs" to search for vitals Observations. Either category or code must be provided.
code | token | Conditional | Yes | | Formatted as <system>|<code>. If a system is not provided, the code is assumed to be a LOINC code. Only LOINC codes are supported for search. Either code or category must be provided.
date | date | Optional | Yes | | The date range for when the Observation was taken.
patient | reference | Conditional | Yes | | The FHIR ID for the Patient whose vital signs were documented. Either patient or subject must be provided. If both patient and subject are provided, they must match.
subject | reference | Conditional | Yes | | The FHIR ID for the Patient whose vital signs were documented. Either patient or subject must be provided. If both patient and subject are provided, they must match.

Request parameters (post-filtered search parameters)

Name | Type | Optional | Array | Cardinality | Description

component-code | token | Optional | Yes | | The code for a blood pressure component element.

component-data-absent-reason | token | Optional | Yes | | The reason why the expected value for a diastolic or systolic blood pressure in the element Observation.component.value* is missing.

status | token | Optional | Yes | | The status of the Observation. This is always "final" for Observation (Outside Record Vital Signs) resources.

Response elements

Name | Type | Optional | Array | Cardinality | Description

Observation (R4) | Observation

Observation (R4).category | CodeableConcept | | Yes | 2..2 | This element always returns "vital-signs" and "external-vital-signs". There is one category element with two category codes.

Observation (R4).code | CodeableConcept | | | 1..1 | Coded value for what is being measured. This is always a LOINC code. The following types of vital information and corresponding LOINC codes are supported: 2708-6 Oxygen saturation in arterial blood 29463-7 Body weight 39156-5 Body Mass Index 59408-5 Oxygen saturation in arterial blood by pulse oximetry (SpO2) 59576-9 Body Mass Index Percentile 8302-2 Body height 8310-5 Body temperature 85354-9 Blood pressure systolic and diastolic 8867-4 Heart rate 9279-1 Respiratory rate 9843-4 Head occipital-frontal circumference by tape measure

Observation (R4).component | BackboneElement | | Yes | 0..2 | Includes extra information about the Observation. Populated only for blood pressure.

Observation (R4).component.code | CodeableConcept | | | 1..1 | Code for the type of blood pressure represented in a component. This is always one of the following: 8480-6: Systolic pressure 8462-4: Diastolic pressure

Observation (R4).component.dataAbsentReason | CodeableConcept | | | 0..1 | Indicates that an Observation value is missing. This is always "unknown" for systolic blood pressure values in Observations for diastolic-only blood pressure flowsheets, or for diastolic blood pressure values in Observations for systolic-only blood pressure flowsheets.

Observation (R4).component.valueQuantity | Quantity | | | 0..1 | The value of the systolic or diastolic blood pressure measurement, with appropriate units. Units for blood pressure are always mm[Hg]

Observation (R4).effectiveDateTime | dateTime | | | 1..1 | The date and time the Observation was taken.

Observation (R4).id | id | | | 1..1 | Unique FHIR ID for the vital sign resource.

Observation (R4).meta | Meta | | | | Metadata about the resource, including information about the origin or source of the data.

Observation (R4).meta.tag | Coding | | Yes | | Set to external-bulk-data for resources originally loaded from another FHIR server. If this element is set to external-bulk-data, the resource content might vary and can include any elements allowed by the FHIR specification.

Observation (R4).status | code | | | 1..1 | The status of the Observation. This element always returns "final".

Observation (R4).subject | Reference | | | 1..1 | The FHIR ID for the Patient a vital sign was measured for.

Observation (R4).valueQuantity | Quantity | | | 0..1 | The value of the vital sign measurement, with appropriate units.

Sample request

```
GET https://hostname/instance/api/FHIR/R4/Observation?patient=eabcdecd1hijklmnop88883&category=vital-signs
```

Sample response


```
{
  "resourceType": "Bundle",
  "type": "searchset",
  "total": 2,
  "link": [
    {
      "relation": "self",
      "url": "https://hostname/instance/api/FHIR/R4/Observation?patient=eabcdecd1hijklmnop88883&category=vital-signs"
    }
  ],
  "entry": [
    {
      "link": [
        {
          "relation": "self",
          "url": "https://hostname/instance/api/FHIR/R4/Observation/fl465hCyfIRcTrn7h8YG-bfPz0nAFvckVIMmOvvcRQPw4"
        }
      ],
      "fullUrl": "https://hostname/instance/api/FHIR/R4/Observation/fl465hCyfIRcTrn7h8YG-bfPz0nAFvckVIMmOvvcRQPw4",
      "resource": {
        "resourceType": "Observation",
        "id": "fl465hCyfIRcTrn7h8YG-bfPz0nAFvckVIMmOvvcRQPw4",
        "status": "final",
        "category": [
          {
            "coding": [
              {
                "system": "http://terminology.hl7.org/CodeSystem/observation-category",
                "code": "vital-signs",
                "display": "Vital Signs"
              }
            ],
            "text": "Vital Signs"
          },
          {
            "coding": [
              {
                "system": "http://open.epic.com/FHIR/StructureDefinition/observation-category",
                "code": "external-vital-signs",
                "display": "External Vital Signs"
```

```
          }
        ],
        "text": "External Vital Signs"
      }
    ],
    "code": {
      "coding": [
        {
          "system": "http://loinc.org",
          "code": "85354-9",
          "display": "Blood pressure panel with all children optional"
        }
      ],
      "text": "Blood pressure panel with all children optional"
    },
    "subject": {
      "reference": "Patient/eabcdecd1hijklmnop88883",
      "display": "FHIR, Test Patient"
    },
    "effectiveDateTime": "2025-07-02T15:24:00Z",
    "component": [
      {
        "code": {
          "coding": [
            {
              "system": "http://loinc.org",
              "code": "8480-6",
              "display": "Systolic Blood Pressure"
            }
          ],
          "text": "Systolic Blood Pressure"
        },
        "valueQuantity": {
          "value": 120,
          "unit": "millimeter of mercury",
          "system": "http://unitsofmeasure.org",
          "code": "mm[Hg]"
        }
      },
      {
        "code": {
          "coding": [
            {
              "system": "http://loinc.org",
              "code": "8462-4",
              "display": "Diastolic Blood Pressure"
            }
          ],
          "text": "Diastolic Blood Pressure"
        },
        "valueQuantity": {
          "value": 80,
          "unit": "millimeter of mercury",
          "system": "http://unitsofmeasure.org",
          "code": "mm[Hg]"
        }
      }
    ]
  },
  "search": {
    "mode": "match"
  }
},
{
  "link": [
    {
      "relation": "self",
      "url": "https://hostname/instance/api/FHIR/R4/Observation/fDI.C-9pxx9i.pOzKCI3axb-u7W6GEsMlWN8Z.7BZhHI4"
    }
  ],
  "fullUrl": "https://hostname/instance/api/FHIR/R4/Observation/fDI.C-9pxx9i.pOzKCI3axb-u7W6GEsMlWN8Z.7BZhHI4",
  "resource": {
    "resourceType": "Observation",
    "id": "fDI.C-9pxx9i.pOzKCI3axb-u7W6GEsMlWN8Z.7BZhHI4",
    "status": "final",
    "category": [
      {
        "coding": [
          {
            "system": "http://terminology.hl7.org/CodeSystem/observation-category",
            "code": "vital-signs",
            "display": "Vital Signs"
          }
        ],
        "text": "Vital Signs"
      },
      {
        "coding": [
          {
```

```
                "system": "http://open.epic.com/FHIR/StructureDefinition/observation-category",
                "code": "external-vital-signs",
                "display": "External Vital Signs"
              }
            ],
            "text": "External Vital Signs"
          }
        ],
        "code": {
          "coding": [
            {
              "system": "http://loinc.org",
              "code": "8867-4",
              "display": "Heart rate"
            }
          ],
          "text": "Heart rate"
        },
        "subject": {
          "reference": "Patient/eabcdecd1hijklmnop88883",
          "display": "FHIR, Test Patient"
        },
        "effectiveDateTime": "2025-09-11T20:07:00Z",
        "valueQuantity": {
          "value": 156,
          "unit": "per minute",
          "system": "http://unitsofmeasure.org",
          "code": "/min"
        }
      },
      "search": {
        "mode": "match"
      }
    }
  ]
}
```


14.1.62 Organization.Read (Outside Record) (R4)

File: site/apis/14-CMS-Incoming/1-R4/11439-Organization-Read-Outside-Record-R4.html
Epic API ID | 11439
FHIR version | R4
Categories | CMS Incoming
API type | USCDI
A la carte | Industry-Standard Level 1 API
USCDI | Yes
Available in inpatient and other contexts | Yes
HTTP method | GET
URL template | /api/FHIR/R4/Organization/{ID}
Supports OAuth 2.0 | True
Supported user types | Backend Systems and Non-OAuth 2.0, Clinicians or Administrative Users, Patients
Performs scope validation | False
Source | https://fhir.epic.com/Specifications?api=11439

Description

Use this API to retrieve a specific instance of an organization. A single overall Organization (Outside Record)

resource repre

sents an organization involved in care (for example a hospital, clinic, payer, or other healthcare-related entity) and is used when other FHIR resources need to reference that organization.

This API differs from other Organization APIs because it returns data obtained as part of payer data exchange workflows rather than directly recorded during patient care. This data can come from payers or loaded from other FHIR servers. Because this data doesn't originate from the organization being queried, users of this API should be aware that the data might be unverified, incomplete, or duplicative.

This data is loaded from other FHIR servers and returned in the format the organization received it. Because of this, the documentation below is minimal. These resources can include any elements from the FHIR specification and can be distinguished from other resources by the presence of meta.tag set to

external-bulk-data

Request parameters

Name | Type | Optional | Array | Cardinality | Description
ID | token | Required | | | The Organization FHIR ID.

Response elements

Name | Type | Optional | Array | Cardinality | Description

Organization (R4) | Resource | | | An instance of the R4 Organization FHIR resource.
Organization (R4).id | id | | | 1..1 | The unique FHIR ID representing the Organization (Outside Record) resource.
Organization (R4).meta | Meta | | | 1..1 | Metadata about the resource, including information about the origin or source of the data.
Organization (R4).meta.tag | Coding | | Yes | 1..* | Set to external-bulk-data for resources originally loaded from another FHIR server. If this element is set to external-bulk-data, the resource content might vary and can include any elements allowed by the FHIR specification.

Sample request

```
GET https://hostname/instance/api/FHIR/R4/Organization/fmZh3bBxz8qrNKW2dLRG0-QCJlrbB8b1SR1h1PJVYGK.ip-
    8fjNdib1i4mEslr3mvthjsu0G0LCHI0uAgx7Jsug4
```

Sample response

```
{
    "resourceType": "Organization",
    "id": "fmZh3bBxz8qrNKW2dLRG0-QCJlrbB8b1SR1h1PJVYGK.ip-8fjNdib1i4mEslr3mvthjsu0G0LCHI0uAgx7Jsug4",
    "meta": {
        "tag": [
            {
                "system": "https://open.epic.com/FHIR/bulk-data-source",
                "code": "external-bulk-data",
                "display": "External Bulk Data"
            }
        ]
    },
    ... <r4 organization="" compliant="" elements=""> ...
}</r4>
```

14.1.63 Organization.Search (Outside Record) (R4)

File: site/apis/14-CMS-Incoming/1-R4/11441-Organization-Search-Outside-Record-R4.html
Epic API ID | 11441
FHIR version | R4
Categories | CMS Incoming
API type | USCDI
A la carte | Industry-Standard Level 1 API
USCDI | Yes
Available in inpatient and other contexts | Yes
HTTP method | GET
URL template | /api/FHIR/R4/Organization?_count={_count}&_id={_id}&_include={_include}&_revinclude={_revinclude}
Supports OAuth 2.0 | True
Supported user types | Backend Systems and Non-OAuth 2.0, Clinicians or Administrative Users, Patients
Performs scope validation | False
Source | https://fhir.epic.com/Specifications?api=11441

Description

Use this API to search for organization resources. A single overall Organization (Outside Record)

resource repre

sents an organization involved in care (for example a hospital, clinic, payer, or other healthcare-related entity) and is used when other FHIR resources need to reference that organization.

This API differs from other Organization APIs because it returns data obtained as part of payer data exchange workflows rather than directly recorded during patient care. This data can come from payers or loaded from other FHIR servers. Because this data doesn't originate from the organization being queried, users of this API should be aware that the data might be unverified, incomplete, or duplicative.

This data is loaded from other FHIR servers and returned in the format the organization received it. Because of this, the documentation below is minimal. These resources can include any elements from the FHIR specification and can be distinguished from other resources by the presence of meta.tag set to

external-bulk-data

Request parameters

Name | Type | Optional | Array | Cardinality | Description
_count | number | Optional | Yes | | Number of results per page.
_id | token | Required | Yes | | FHIR resource IDs for the desired resources. Can be used in combination with _count, _include, and _revInclude. All others will be ignored.
_include | string | Optional | Yes | | Used to indicate which referenced resources to include in the search bundle.
_revinclude | string | Optional | Yes | | Used to include Provenance or AuditEvent resources that refer to search results, when available.

Response elements

Name | Type | Optional | Array | Cardinality | Description
Organization (R4) | Resource | | | An instance of the R4 Organization FHIR resource.
Organization (R4).id | id | | | 1..1 | The unique FHIR ID representing the Organization (Outside Record) resource.

Organization (R4).meta | Meta | | | 1..1 | Metadata about the resource, including information about the origin or source of the data.
Organization (R4).meta.tag | Coding | | Yes | 1..* | Set to external-bulk-data for resources originally loaded from another FHIR server. If this element is set to external-bulk-data, the resource content might vary and can include any elements allowed by the FHIR specification.

Sample request

```
GET https://hostname/instance/api/FHIR/R4/Organization?_id=fmZh3bBxz8qrNKW2dLRG0-QCJlrbB8b1SR1h1PJVYGK.ip-
    8fjNdib1i4mEslr3mvthjsu0G0LCHI0uAgx7Jsug4
```

Sample response

```
{
  "resourceType": "Bundle",
  "type": "searchset",
  "total": 1,
  "link": [
    {
      "relation": "self",
      "url": "https://hostname/instance/api/FHIR/R4/Organization?_id=fmZh3bBxz8qrNKW2dLRG0-QCJlrbB8b1SR1h1PJVYGK.ip-
    8fjNdib1i4mEslr3mvthjsu0G0LCHI0uAgx7Jsug4"
    }
  ],
  "entry": [
    {
      "link": [
        {
          "relation": "self",
          "url": "https://hostname/instance/api/FHIR/R4/Organization/fmZh3bBxz8qrNKW2dLRG0-QCJlrbB8b1SR1h1PJVYGK.ip-
    8fjNdib1i4mEslr3mvthjsu0G0LCHI0uAgx7Jsug4"
        }
      ],
      "fullUrl": "https://hostname/instance/api/FHIR/R4/Organization/fmZh3bBxz8qrNKW2dLRG0-QCJlrbB8b1SR1h1PJVYGK.ip-
    8fjNdib1i4mEslr3mvthjsu0G0LCHI0uAgx7Jsug4",
      "resource": {
        "resourceType": "Organization",
        "id": "fmZh3bBxz8qrNKW2dLRG0-QCJlrbB8b1SR1h1PJVYGK.ip-8fjNdib1i4mEslr3mvthjsu0G0LCHI0uAgx7Jsug4",
        "meta": {
          "tag": [
            {
              "system": "https://open.epic.com/FHIR/bulk-data-source",
              "code": "external-bulk-data",
              "display": "External Bulk Data"
            }
          ]
        }
        ... <r4 organization="" compliant="" elements=""> ...
      }
    }
  ]
}</r4>
```

14.1.64 PAS Incoming Claim Response Notification

File: site/apis/14-CMS-Incoming/1-R4/11277-PAS-Incoming-Claim-Response-Notification.html
Epic API ID | 11277
FHIR version | R4
Categories | CMS Incoming
API type | Industry-Standard
USCDI | No
HTTP method | POST
URL template | /api/FHIR/R4/ClaimResponse/$notify
Supports OAuth 2.0 | True
Supported user types | Backend Systems and Non-OAuth 2.0, Clinicians or Administrative Users
Performs scope validation | False
Source | https://fhir.epic.com/Specifications?api=11277

Description

The HL7 FHIR Da Vinci Prior Authorization Support (PAS) STU 2.1 (https://hl7.org/fhir/us/davinci-pas/STU2.1/) functionality is intended to streamline the prior authorization process using a FHIR-based data exchange rather than the previous ANSI X12-based electronic messaging specification as well as to encourage automation throughout the process.

Complex prior authorization requests can take some time to adjudicate. When a health plan finishes their adjudication or modifies the request, they shall use the $notify operation to inform the health system. This operation is essentially an asynchronous response to an authorization request using a bundled ClaimResponse resource (https://hl7.org/fhir/us/davinci-pas/STU2.1/StructureDefinition-profile-pas-response-bundle.html).

While the HL7 specification suggests that a subscription (https://hl7.org/fhir/us/davinci-pas/STU2.1/specification.html#subscription) request should first be submitted to initiate this notification process, Epic recommends that health plans should always assume that a subscription is desired when an authorization request has been submitted to improve automation.

14.1.65 Practitioner.Read (Outside Record) (R4)

File: site/apis/14-CMS-Incoming/1-R4/11471-Practitioner-Read-Outside-Record-R4.html
Epic API ID | 11471
FHIR version | R4
Categories | CMS Incoming
API type | USCDI
A la carte | Industry-Standard Level 1 API
USCDI | Yes
Available in inpatient and other contexts | Yes
HTTP method | GET
URL template | /api/FHIR/R4/Practitioner/{ID}
Supports OAuth 2.0 | True
Supported user types | Backend Systems and Non-OAuth 2.0, Clinicians or Administrative Users, Patients
Performs scope validation | False
Source | https://fhir.epic.com/Specifications?api=11471

Description

Use this API to retrieve a specific instance of a practitioner. A single overall Practitioner (Outside Record) resource represents a healthcare provider (for example a doctor, nurse, or pharmacist) and is used when other FHIR resources need to reference that practitioner.

This API differs from other Practitioner APIs because it returns data obtained as part of payer data exchange workflows rather than directly recorded during patient care. This data can come from payers or loaded from other FHIR servers. Because this data doesn't originate from the organization being queried, users of this API should be aware that the data might be unverified, incomplete, or duplicative.

This data is loaded from other FHIR servers and returned in the format the organization received it. Because of this, the documentation below is minimal. These resources can include any elements from the FHIR specification and can be distinguished from other resources by the presence of meta.tag set to

external-bulk-data

Request parameters

Name | Type | Optional | Array | Cardinality | Description
ID | token | Required | | | The Practitioner FHIR ID.

Response elements

Name | Type | Optional | Array | Cardinality | Description
Practitioner (R4) | Resource
Practitioner (R4).id | id | | | 1..1 | The unique FHIR ID representing the Practitioner (Outside Record) resource.
Practitioner (R4).meta | Meta | | | 1..1 | Metadata about the resource, including information about the origin or source of the data.
Practitioner (R4).meta.tag | Coding | | Yes | 1..* | Set to external-bulk-data for resources originally loaded from another FHIR server. If this element is set to external-bulk-data, all other element-level documentation does not apply to the resource. The resource content might vary and can include any elements allowed by the FHIR specification.

Sample request

```
GET https://hostname/instance/api/FHIR/R4/Practitioner/f-zd0ZX0ZZXKjmPUtxbJxY6o-VuMyBcVpO.GT4aHef1M4
```

Sample response

```
{
  "resourceType": "Practitioner",
  "id": "f-zd0ZX0ZZXKjmPUtxbJxY6o-VuMyBcVpO.GT4aHef1M4",
  "meta": {
    "tag": [
      {
        "system": "https://open.epic.com/FHIR/bulk-data-source",
        "code": "external-bulk-data",
        "display": "External Bulk Data"
      }
    ]
  },
    ... <R4 Practitioner Compliant Elements> ...
}
```

14.1.66 Practitioner.Search (Outside Record) (R4)

File: site/apis/14-CMS-Incoming/1-R4/11472-Practitioner-Search-Outside-Record-R4.html
Epic API ID | 11472
FHIR version | R4
Categories | CMS Incoming
API type | USCDI
A la carte | Industry-Standard Level 1 API

USCDI | Yes
Available in inpatient and other contexts | Yes
HTTP method | GET
URL template | /api/FHIR/R4/Practitioner?address={address}&address-city={address-city}&address-postalcode={address-postalcode}&address-state={address-state}&family={family}&given={given}&identifier={identifier}&name={name}&_count={_count}&_id={_id}&_include={_include}&_revinclude={_revinclude}
Supports OAuth 2.0 | True
Supported user types | Backend Systems and Non-OAuth 2.0, Clinicians or Administrative Users, Patients
Performs scope validation | False
Source | https://fhir.epic.com/Specifications?api=11472

Description

Use this API to search for Practitioner resources. A single overall Practitioner (Outside Record) resource represents a healthcare provider (for example a doctor, nurse, or pharmacist) and is used when other FHIR resources need to reference that practitioner.

This API differs from other Practitioner APIs because it returns data obtained as part of payer data exchange workflows rather than directly recorded during patient care. This data can come from payers or loaded from other FHIR servers. Because this data doesn't originate from the organization being queried, users of this API should be aware that the data might be unverified, incomplete, or duplicative.

This data is loaded from other FHIR servers and returned in the format the organization received it. Because of this, the documentation below is minimal. These resources can include any elements from the FHIR specification and can be distinguished from other resources by the presence of meta.tag set to

external-bulk-data

Request parameters

Name | Type | Optional | Array | Cardinality | Description
_count | number | Optional | Yes | | Number of results per page.
_id | token | Optional | Yes | | FHIR resource IDs for the desired resources. Can be used in combination with _count, _include, and _revInclude. All others will be ignored.
_include | string | Optional | Yes | | Used to indicate which referenced resources to include in the search bundle.
_revinclude | string | Optional | Yes | | Used to include Provenance or AuditEvent resources that refer to search results, when available.

Response elements

Name | Type | Optional | Array | Cardinality | Description
Practitioner (R4) | Resource
Practitioner (R4).id | id | | | 1..1 | The unique FHIR ID representing the Practitioner (Outside Record) resource.
Practitioner (R4).meta | Meta | | | 1..1 | Metadata about the resource, including information about the origin or source of the data.
Practitioner (R4).meta.tag | Coding | | Yes | 1..* | Set to external-bulk-data for resources originally loaded from another FHIR server. If this element is set to external-bulk-data, all other element-level documentation does not apply to the resource. The resource content might vary and can include any elements allowed by the FHIR specification.

Sample request

```
GET https://hostname/instance/api/FHIR/R4/Practitioner?_id=f-zd0ZX0ZZXKjmPUtxbJxY6o-VuMyBcVpO.GT4aHef1M4
```

Sample response


```
{
  "resourceType": "Bundle",
  "type": "searchset",
  "total": 1,
  "link": [
    {
      "relation": "self",
      "url": "https://hostname/instance/api/FHIR/R4/Practitioner?_id=f-zd0ZX0ZZXKjmPUtxbJxY6o-VuMyBcVpO.GT4aHef1M4"
    }
  ],
  "entry": [
    {
      "link": [
        {
          "relation": "self",
          "url": "https://hostname/instance/api/FHIR/R4/Practitioner/f-zd0ZX0ZZXKjmPUtxbJxY6o-VuMyBcVpO.GT4aHef1M4"
        }
      ],
      "fullUrl": "https://hostname/instance/api/FHIR/R4/Practitioner/f-zd0ZX0ZZXKjmPUtxbJxY6o-VuMyBcVpO.GT4aHef1M4",
      "resource": {
        "resourceType": "Practitioner",
        "id": "f-zd0ZX0ZZXKjmPUtxbJxY6o-VuMyBcVpO.GT4aHef1M4",
        "meta": {
          "tag": [
            {
              "system": "https://open.epic.com/FHIR/bulk-data-source",
              "code": "external-bulk-data",
              "display": "External Bulk Data"
```

```
            }
          ]
        },
              ... <R4 Practitioner Compliant Elements> ...
      },
      "search": {
        "mode": "match"
      }
    }
  ]
}
```

14.1.67 PractitionerRole.Read (Outside Record) (R4)

File: site/apis/14-CMS-Incoming/1-R4/11373-PractitionerRole-Read-Outside-Record-R4.html
Epic API ID | 11373
FHIR version | R4
Categories | CMS Incoming
API type | USCDI
A la carte | Industry-Standard Level 1 API
USCDI | Yes
Available in inpatient and other contexts | Yes
HTTP method | GET
URL template | /api/FHIR/R4/PractitionerRole/{ID}
Supports OAuth 2.0 | True
Supported user types | Backend Systems and Non-OAuth 2.0, Clinicians or Administrative Users, Patients
Performs scope validation | False
Source | https://fhir.epic.com/Specifications?api=11373

Description

Use this API to retrieve a specific instance of PractitionerRole. The PractitionerRole resource defines the types of services (roles) that a practitioner provides for an organization. It references the Practitioner resource, and there can be multiple PractitionerRoles per practitioner.

This API differs from the

PractitionerRole.Read (Organizational Directory) (R4)

API because it returns data that was obtained as part of payer data exchange workflows rather than directly recorded during patient care. This data can come from payers, providers, or loaded from other FHIR servers. Because this data doesn't originate from the organization being queried, users of this API should be aware that the data might be unverified, incomplete, or duplicative.

Data from outside payer and provider systems is saved to an organization's database and returned in a standard format, documented below. Data loaded from other FHIR servers is returned in the format the organization received it. Because of this, the documentation below does not apply to these loaded resources. These resources can include any elements from the FHIR specification and can be distinguished from other resources by the presence of meta.tag set to “external-bulk-data".

Request parameters

Name | Type | Optional | Array | Cardinality | Description
ID | token | Required | | | The PractitionerRole FHIR ID.

Response elements

Name | Type | Optional | Array | Cardinality | Description
PractitionerRole (R4) | Resource
PractitionerRole (R4).code | CodeableConcept | | Yes | | Roles which the practitioner performs.
PractitionerRole (R4).id | id | | | 1..1 | The unique FHIR ID for a PractitionerRole (Outside Record) resource.
PractitionerRole (R4).meta | Meta | | | | Metadata about the resource, including information about the origin or source of the data.
PractitionerRole (R4).meta.tag | Coding | | Yes | | Set to external-bulk-data for resources originally loaded from another FHIR server. If this element is set to external-bulk-data, all other element-level documentation does not apply to the resource. The resource content might vary and can include any elements allowed by the FHIR specification.
PractitionerRole (R4).practitioner | Reference | | | 0..1 | Reference to the Practitioner resource.
PractitionerRole (R4).specialty | CodeableConcept | | Yes | | The specialties that are associated with the practitioner.
PractitionerRole (R4).telecom | ContactPoint | | Yes | | Contact information (phone, fax, email) specific to the unique address.

Sample request

```
GET https://hostname/instance/api/FHIR/R4/PractitionerRole/eKXIu2L1.u3.DjMFsl.DcYFyJ3YM5dTtXBjZIYXdkVZs3
```

Sample response

```
{
  "resourceType": "PractitionerRole",
  "id": "eKXIu2L1.u3.DjMFsl.DcYFyJ3YM5dTtXBjZIYXdkVZs3",
  "practitioner": {
    "reference": "eS6KRsn5kL.pkis6ZW8zk9izxlXM1YahlUFSI2mLuAcUCrmDkwYKoYGZ9Og3A1V-33",
```

```
    "type": "Practitioner",
    "display": "FHIR Practitioner"
  },
  "code": [
    {
      "coding": [
        {
          "system": "urn:oid:1.2.840.114350.1.13.51879.1.7.10.836982.1040",
          "code": "1",
          "display": "Physician"
        }
      ],
      "text": "Physician"
    }
  ],
  "specialty": [
    {
      "coding": [
        {
          "system": "urn:oid:1.2.840.114350.1.72.1.7.7.10.688867.4160",
          "code": "19",
          "display": "Radiology"
        },
        {
          "system": "http://nucc.org",
          "code": "2085R0202X"
        },
        {
          "system": "http://nucc.org/provider-taxonomy",
          "code": "2085R0202X"
        }
      ],
      "text": "Radiology"
    },
    {
      "coding": [
        {
          "system": "urn:oid:1.2.840.114350.1.72.1.7.7.10.688867.4160",
          "code": "95",
          "display": "Radiation Therapy"
        },
        {
          "system": "urn:oid:1.2.840.114350.1.13.861.1.7.10.836982.1050",
          "code": "40",
          "display": "Radiology"
        }
      ]
    }
  ],
  "telecom": [
    {
      "system": "phone",
      "value": "+1 608-454-3124"
    }
  ]
}
```


14.1.68 PractitionerRole.Search (Outside Record) (R4)

File: site/apis/14-CMS-Incoming/1-R4/11385-PractitionerRole-Search-Outside-Record-R4.html
Epic API ID | 11385
FHIR version | R4
Categories | CMS Incoming
API type | USCDI
A la carte | Industry-Standard Level 1 API
USCDI | Yes
Available in inpatient and other contexts | Yes
HTTP method | GET
URL template | /api/FHIR/R4/PractitionerRole?email={email}&identifier={identifier}&location={location}&organization={organization}&phone={phone}&practitioner={practitioner}&role={role}&specialty={specialty}&telecom={telecom}&_count={_count}&_id={_id}&_include={_include}&_revinclude={_revinclude}
Supports OAuth 2.0 | True
Supported user types | Backend Systems and Non-OAuth 2.0, Clinicians or Administrative Users, Patients
Performs scope validation | False
Source | https://fhir.epic.com/Specifications?api=11385

Description

Use this API to search for instances of PractitionerRole resources. The PractitionerRole resource defines the types of services (roles) that a practitioner provides for an organization. It references the Practitioner resource, and there can be multiple PractitionerRoles per practitioner.

This API differs from the

PractitionerRole.Search (Organizational Directory) (R4)

API because it returns data that was obtained as part of payer data exchange workflows rather than directly recorded during patient care. This data can come from payers, providers, or loaded from other FHIR servers. Because this data doesn't originate from the organization being queried, users of this API should be aware that the data might be unverified, incomplete, or duplicative.

Data from outside payer and provider systems is saved to an organization's database and returned in a standard format, documented below. Data loaded from other FHIR servers is returned in the format the organization received it. Because of this, the documentation below does not apply to these loaded resources. These resources can include any elements from the FHIR specification and can be distinguished from other resources by the presence of meta.tag set to “external-bulk-data".

Request parameters

Name | Type | Optional | Array | Cardinality | Description
_count | number | Optional | Yes | | Number of results per page.
_id | token | Required | Yes | | FHIR resource IDs for the desired resources. Can be used in combination with _count, _include, and _revInclude. All others are ignored.
_include | string | Optional | Yes | | Used to indicate which referenced resources to include in the search bundle.
_revinclude | string | Optional | Yes | | Used to include Provenance or AuditEvent resources that refer to search results, when available.

Response elements

Name | Type | Optional | Array | Cardinality | Description
PractitionerRole (R4) | Resource
PractitionerRole (R4).code | CodeableConcept | | Yes | | Roles which the practitioner performs.
PractitionerRole (R4).id | id | | | 1..1 | The unique FHIR ID for a PractitionerRole (Outside Record) resource.
PractitionerRole (R4).meta | Meta | | | | Metadata about the resource, including information about the origin or source of the data.
PractitionerRole (R4).meta.tag | Coding | | Yes | | Set to external-bulk-data for resources originally loaded from another FHIR server. If this element is set to external-bulk-data, all other element-level documentation does not apply to the resource. The resource content might vary and can include any elements allowed by the FHIR specification.
PractitionerRole (R4).practitioner | Reference | | | 0..1 | Reference to the Practitioner resource.
PractitionerRole (R4).specialty | CodeableConcept | | Yes | | The specialties that are associated with the practitioner.
PractitionerRole (R4).telecom | ContactPoint | | Yes | | Contact information (phone, fax, email) specific to the unique address.

Sample request

```
GET https://hostname/instance/api/FHIR/R4/PractitionerRole?_id=eKXIu2L1.u3.DjMFsl.DcYFyJ3YM5dTtXBjZIYXdkVZs3
```

Sample response


```
{
  "resourceType": "Bundle",
  "type": "searchset",
  "total": 1,
  "link": [
    {
      "relation": "self",
      "url": "https://hostname/instance/api/FHIR/R4/PractitionerRole?id=eKXIu2L1.u3.DjMFsl.DcYFyJ3YM5dTtXBjZIYXdkVZs3"
    }
  ],
  "entry": [
    {
      "link": [
        {
          "relation": "self",
          "url": "https://hostname/instance/api/FHIR/R4/PractitionerRole/eKXIu2L1.u3.DjMFsl.DcYFyJ3YM5dTtXBjZIYXdkVZs3"
        }
      ],
      "fullUrl": "https://hostname/instance/api/FHIR/R4/PractitionerRole/eKXIu2L1.u3.DjMFsl.DcYFyJ3YM5dTtXBjZIYXdkVZs3",
      "resource": {
        "resourceType": "PractitionerRole",
        "id": "eKXIu2L1.u3.DjMFsl.DcYFyJ3YM5dTtXBjZIYXdkVZs3",
        "practitioner": {
          "reference": "eS6KRsn5kL.pkis6ZW8zk9izxlXM1YahlUFSI2mLuAcUCrmDkwYKoYGZ9Og3A1V-33",
          "type": "Practitioner",
          "display": "Mwz Admin Md, Otto Rioja"
        },
        "code": [
          {
            "coding": [
              {
                "system": "urn:oid:1.2.840.114350.1.13.51879.1.7.10.836982.1040",
                "code": "1",
                "display": "Physician"
              }
            ],
            "text": "Physician"
          }
        ],
        "specialty": [
          {
            "coding": [
```

```
              {
                "system": "urn:oid:1.2.840.114350.1.72.1.7.7.10.688867.4160",
                "code": "19",
                "display": "Radiology"
              },
              {
                "system": "http://nucc.org",
                "code": "2085R0202X"
              },
              {
                "system": "http://nucc.org/provider-taxonomy",
                "code": "2085R0202X"
              }
            ],
            "text": "Radiology"
          },
          {
            "coding": [
              {
                "system": "urn:oid:1.2.840.114350.1.72.1.7.7.10.688867.4160",
                "code": "95",
                "display": "Radiation Therapy"
              },
              {
                "system": "urn:oid:1.2.840.114350.1.13.861.1.7.10.836982.1050",
                "code": "40",
                "display": "Radiology"
              }
            ]
          }
        ],
        "telecom": [
          {
            "system": "phone",
            "value": "+1 608-454-3124"
          }
        ]
      },
      "search": {
        "mode": "match"
      }
    }
  ]
}
```


14.1.69 Procedure.Read (Outside Record) (R4)

File: site/apis/14-CMS-Incoming/1-R4/11368-Procedure-Read-Outside-Record-R4.html
Epic API ID | 11368
FHIR version | R4
Categories | CMS Incoming
API type | USCDI
A la carte | Industry-Standard Level 1 API
USCDI | Yes
Available in inpatient and other contexts | Yes
HTTP method | GET
URL template | /api/FHIR/R4/Procedure/{ID}
Supports OAuth 2.0 | True
Supported user types | Backend Systems and Non-OAuth 2.0, Clinicians or Administrative Users, Patients
Performs scope validation | False
Source | https://fhir.epic.com/Specifications?api=11368

Description

Use this API to retrieve a specific instance of a patient's historical procedure record. This FHIR resource represents activities performed on or with a patient as part of the provision of care and is designed to summarize any performed procedures for a patient for which an order has been created.

This API differs from other Procedure APIs because it returns data that was obtained as part of payer data exchange workflows rather than directly recorded during patient care. This data can come from payers, providers, or loaded from other FHIR servers. Because this data doesn't originate from the organization being queried, users of this API should be aware that the data might be unverified, incomplete, or duplicative.

Data from outside payer and provider systems is saved to an organization's database and returned in a standard format, documented below. Data loaded from other FHIR servers is returned in the format the organization received it. Because of this, the documentation below does not apply to these loaded resources. These resources can include any elements from the FHIR specification and can be distinguished from other resources by the presence of meta.tag set to "external-bulk-data".

Request parameters

Name | Type | Optional | Array | Cardinality | Description
ID | token | Required | | | The Procedure FHIR ID.

Response elements

Name | Type | Optional | Array | Cardinality | Description
Procedure (R4) | Procedure
Procedure (R4).category | CodeableConcept | | | 1..1 | This is always returned as the Epic custom category representing the Procedure (Outside Record) sub-resource. System: http://open.epic.com/FHIR/StructureDefinition/Procedure-category Category.code: external-procedure
Procedure (R4).code | CodeableConcept | | | 1..1 | External codes that are associated with the Procedure.
Procedure (R4).id | id | | | 1..1 | The unique FHIR ID for a Procedure (Outside Record) resource.
Procedure (R4).meta | Meta | | | | Metadata about the resource, including information about the origin or source of the data.
Procedure (R4).meta.tag | Coding | | Yes | | Set to external-bulk-data for resources originally loaded from another FHIR server. If this element is set to external-bulk-data, the resource content might vary and can include any elements allowed by the FHIR specification.
Procedure (R4).outcome | CodeableConcept | | | 0..1 | The outcome of the Procedure if it was not resolved. This would only be set when we make an unsuccessful attempt. System: http://snomed.info/sct Outcome.code: 385671000
Procedure (R4).performedDateTime | dateTime | | | 0..1 | The date the Procedure was performed. This is only populated if we have either the start date or end date. If both are populated, performedPeriod is used.
Procedure (R4).performedPeriod | Period | | | 0..1 | The period of time in which the Procedure was performed. This is only populated if we have both the start and the end date. If we have either the start or the end date but not both, performedDateTime is used.
Procedure (R4).status | code | | | 1..1 | The status of the Procedure. This can hold the following values: unknown stopped in-progress not-done completed on-hold preparation entered-in-error
Procedure (R4).subject | Reference | | | 1..1 | A reference to the Patient resource representing the subject of the report.

Sample request

```
GET https://hostname/instance/api/FHIR/R4/Procedure/fPAjoXZ4tSSiJpp.xIoJQU9NR.r7nIMYQ4wr-EJQz8Xs4
```

Sample response


```
{
  "resourceType": "Procedure",
  "id": "fPAjoXZ4tSSiJpp.xIoJQU9NR.r7nIMYQ4wr-EJQz8Xs4",
  "status": "completed",
  "category": {
    "coding": [
      {
        "system": "http://open.epic.com/FHIR/StructureDefinition/Procedure-category",
        "code": "external-procedure",
        "display": "External Procedure"
      }
    ],
    "text": "External Procedure"
  },
  "code": {
    "coding": [
      {
        "system": "http://snomed.info/sct",
        "code": "108252007",
        "display": "Laboratory procedure"
      }
    ],
    "text": "Laboratory procedure"
  },
  "subject": {
    "reference": "Patient/eyu4vpKUjflTtDmuOljEFxg3",
    "display": "FHIR, Test Patient"
  },
  "performedPeriod": {
    "start": "2024-06-18",
    "end": "2024-06-18"
  }
}
```


Change log

Epic Version | Description | Type
February 2026 | The Outside Record FHIR APIs now validate member coverage and return only resources relevant to the member's coverage enrollment. Previously they returned resources unrelated to the member's coverage. | Breaking Change
November 2025 | The Outside Record FHIR APIs are no longer enabled in the November 2025 version. Requests to these APIs do not return data. | Breaking Change

14.1.70 Procedure.Search (Outside Record) (R4)

File: site/apis/14-CMS-Incoming/1-R4/11370-Procedure-Search-Outside-Record-R4.html
Epic API ID | 11370
FHIR version | R4
Categories | CMS Incoming
API type | USCDI
A la carte | Industry-Standard Level 1 API
USCDI | Yes
Available in inpatient and other contexts | Yes

HTTP method | GET
URL template | /api/FHIR/R4/Procedure?category={category}&code={code}&date={date}&identifier={identifier}&patient={patient}&subject={subject}&_count={_count}&_id={_id}&_include={_include}&_revinclude={_revinclude}
Supports OAuth 2.0 | True
Supported user types | Backend Systems and Non-OAuth 2.0, Clinicians or Administrative Users, Patients
Performs scope validation | False
Source | https://fhir.epic.com/Specifications?api=11370

Description

Use this API to search for a patient's historical procedure records. This FHIR resource represents activities performed on or with a patient as part of the provision of care and is designed to summarize any performed procedures for a patient for which an order has been created.

This API differs from other Procedure APIs because it returns data that was obtained as part of payer data exchange workflows rather than directly recorded during patient care. This data can come from payers, providers, or loaded from other FHIR servers. Because this data doesn't originate from the organization being queried, users of this API should be aware that the data might be unverified, incomplete, or duplicative.

Data from outside payer and provider systems is saved to an organization's database and returned in a standard format, documented below. Data loaded from other FHIR servers is returned in the format the organization received it. Because of this, the documentation below does not apply to these loaded resources. These resources can include any elements from the FHIR specification and can be distinguished from other resources by the presence of meta.tag set to "external-bulk-data".

Request parameters

Name | Type | Optional | Array | Cardinality | Description
_count | number | Optional | Yes | | Number of results per page.
_id | token | Optional | Yes | | FHIR resource IDs for the desired resources. Can be used in combination with _count, _include, and _revInclude. All others are ignored.
_include | string | Optional | Yes | | Used to indicate which referenced resources to include in the search bundle.
_revinclude | string | Optional | Yes | | Used to include Provenance or AuditEvent resources that refer to search results, when available.
category | token | Optional | Yes | | An Epic code that classifies the type of Procedure data being returned. To limit search results to only the Outside Record sub-resource, add the category parameter with a value of "external-procedure" to your query.
date | date | Optional | Yes | | Date or period that the Procedure was performed, using the FHIR date parameter format.
patient | reference | Conditional | Yes | | The Patient FHIR resource ID. Either a patient or subject parameter must be provided. If both are provided, they must match exactly.
subject | reference | Conditional | Yes | | The subject FHIR resource ID. Either a patient or subject parameter must be provided. If both are provided, they must match exactly.

Response elements

Name | Type | Optional | Array | Cardinality | Description
Procedure (R4) | Procedure
Procedure (R4).category | CodeableConcept | | | 1..1 | This is always returned as the Epic custom category representing the Procedure (Outside Record) sub-resource. System: http://open.epic.com/FHIR/StructureDefinition/Procedure-category Category.code: external-procedure
Procedure (R4).code | CodeableConcept | | | 1..1 | External codes that are associated with the Procedure.
Procedure (R4).id | id | | | 1..1 | The unique FHIR ID for a Procedure (Outside Record) resource.
Procedure (R4).meta | Meta | | | | Metadata about the resource, including information about the origin or source of the data.
Procedure (R4).meta.tag | Coding | | Yes | | Set to external-bulk-data for resources originally loaded from another FHIR server. If this element is set to external-bulk-data, the resource content might vary and can include any elements allowed by the FHIR specification.
Procedure (R4).outcome | CodeableConcept | | | 0..1 | The outcome of the Procedure if it was not resolved. This would only be set when we make an unsuccessful attempt. System: http://snomed.info/sct Outcome.code: 385671000
Procedure (R4).performedDateTime | dateTime | | | 0..1 | The date the Procedure was performed. This is only populated if we have either the start date or end date. If both are populated, performedPeriod is used.
Procedure (R4).performedPeriod | Period | | | 0..1 | The period of time in which the Procedure was performed. This is only populated if we have both the start and the end date. If we have either the start or the end date but not both, performedDateTime is used.
Procedure (R4).status | code | | | 1..1 | The status of the Procedure. This can hold the following values: unknown stopped in-progress not-done completed on-hold preparation entered-in-error
Procedure (R4).subject | Reference | | | 1..1 | A reference to the Patient resource representing the subject of the report.

Sample request

```
GET https://hostname/instance/api/FHIR/R4/Procedure?patient=eyu4vpKUjflTtDmuOljEFxg3
```

Sample response


```
{
  "resourceType": "Bundle",
  "type": "searchset",
  "total": 2,
  "link": [
    {
      "relation": "self",
      "url": "https://hostname/instance/api/FHIR/R4/Procedure?patient=eyu4vpKUjflTtDmuOljEFxg3"
    }
  ],
  "entry": [
```

```
{
  "link": [
    {
      "relation": "self",
      "url": "https://hostname/instance/api/FHIR/R4/Procedure/fPAjoXZ4tSSiJpp.xIoJQU9NR.r7nIMYQ4wr-EJQz8Xs4"
    }
  ],
  "fullUrl": "https://hostname/instance/api/FHIR/R4/Procedure/fPAjoXZ4tSSiJpp.xIoJQU9NR.r7nIMYQ4wr-EJQz8Xs4",
  "resource": {
    "resourceType": "Procedure",
    "id": "fPAjoXZ4tSSiJpp.xIoJQU9NR.r7nIMYQ4wr-EJQz8Xs4",
    "status": "completed",
    "category": {
      "coding": [
        {
          "system": "http://open.epic.com/FHIR/StructureDefinition/Procedure-category",
          "code": "external-procedure",
          "display": "External Procedure"
        }
      ],
      "text": "External Procedure"
    },
    "code": {
      "coding": [
        {
          "system": "http://snomed.info/sct",
          "code": "108252007",
          "display": "Laboratory procedure"
        }
      ],
      "text": "Laboratory procedure"
    },
    "subject": {
      "reference": "Patient/eyu4vpKUjflTtDmuOljEFxg3",
      "display": "FHIR, Test Patient"
    },
    "performedPeriod": {
      "start": "2024-06-18",
      "end": "2024-06-18"
    }
  },
  "search": {
    "mode": "match"
  }
},
{
  "link": [
    {
      "relation": "self",
      "url": "https://hostname/instance/api/FHIR/R4/Procedure/fq.S6qausiOoBBi2Xl6goW8h5SAArFN7GzjzZe7Xh16E4"
    }
  ],
  "fullUrl": "https://hostname/instance/api/FHIR/R4/Procedure/fq.S6qausiOoBBi2Xl6goW8h5SAArFN7GzjzZe7Xh16E4",
  "resource": {
    "resourceType": "Procedure",
    "id": "fq.S6qausiOoBBi2Xl6goW8h5SAArFN7GzjzZe7Xh16E4",
    "status": "completed",
    "category": {
      "coding": [
        {
          "system": "http://open.epic.com/FHIR/StructureDefinition/Procedure-category",
          "code": "external-procedure",
          "display": "External Procedure"
        }
      ],
      "text": "External Procedure"
    },
    "code": {
      "coding": [
        {
          "system": "http://snomed.info/sct",
          "code": "396428000",
          "display": "Measurement of serum calcium level"
        }
      ],
      "text": "Measurement of serum calcium level"
    },
    "subject": {
      "reference": "Patient/eyu4vpKUjflTtDmuOljEFxg3",
      "display": "FHIR, Test Patient"
    },
    "performedPeriod": {
      "start": "2024-07-21",
      "end": "2024-07-28"
    }
  },
  "search": {
    "mode": "match"
  }
```

```
    }
  ]
}
```

Change log

Epic Version | Description | Type
February 2026 | The Outside Record FHIR APIs now validate member coverage and return only resources relevant to the member's coverage enrollment. Previously they returned resources unrelated to the member's coverage. | Breaking Change
November 2025 | The Outside Record FHIR APIs are no longer enabled in the November 2025 version. Requests to these APIs do not return data. | Breaking Change

14.1.71 Questionnaire.$log-questionnaire-errors (R4)

File: site/apis/14-CMS-Incoming/1-R4/11414-Questionnaire-log-questionnaire-errors-R4.html
Epic API ID | 11414
FHIR version | R4
Categories | CMS Incoming
API type | Industry-Standard
USCDI | No
Supports OAuth 2.0 | True
Supported user types | Backend Systems and Non-OAuth 2.0
Performs scope validation | False
Source | https://fhir.epic.com/Specifications?api=11414

Description

The Questionnaire.$log-questionnaire-errors operation allows a client to report errors encountered while rendering or processing a DTR questionnaire.The request identifies the questionnaire using its canonical URL. The server validates the canonical, resolves the appropriate downstream endpoint based on that canonical, and forwards the request to that endpoint for processing.This implementation does not interpret or process the reported error details locally. Any additional parameters (such as an operationOutcome describing the errors) are forwarded to the resolved downstream endpoint without modification.If the questionnaire canonical cannot be validated or resolved to a downstream endpoint, the operation returns an OperationOutcome describing the failure.On successful resolution, the downstream endpoint’s response is returned unchanged.

Refer to

Operation Definition of $log-questionnaire-errors v2.1.0

and

Structure Definition of dtr-log-errors-input-parameters v2.1.0

for more information.

Request parameters

Name | Type | Optional | Array | Cardinality | Description
Parameters (R4) | Parameters | Required | | 1..1 | Request wrapper for the Da Vinci DTR $log-questionnaire-errors operation.
Parameters (R4).parameter (operationOutcome) (also: parameter (operationOutcome)) | BackboneElement | Conditional | Yes | 0..1 | Parameter used to log an OperationOutcome containing errors associated with a Questionnaire or QuestionnaireResponse. This parameter usage may vary based on implementation.
Parameters (R4).parameter (operationOutcome).name | string | Required | | 1..1 | Parameter name. Fixed to "operationOutcome".
Parameters (R4).parameter (operationOutcome).resource | ResourceContainer | Required | | 1..1 | The OperationOutcome resource containing error details to be logged.
Parameters (R4).parameter (operationOutcome).resource.OperationOutcome | OperationOutcome | Required | | 1..1 | A resource that contains details about errors, warnings, or informational messages generated during processing. Specific error details may be ignored depending on implementation.
Parameters (R4).parameter (questionnaire) (also: parameter (questionnaire)) | BackboneElement | Required | Yes | 1..1 | Parameter identifying the Questionnaire associated with the logged error.
Parameters (R4).parameter (questionnaire).name | string | Required | | 1..1 | Parameter name. Fixed to "questionnaire".
Parameters (R4).parameter (questionnaire).valueCanonical | String | Required | | 1..1 | Canonical reference to the Questionnaire resource that the error is associated with.

Sample request

```
POST https://hostname/instance/api/epic/2024/HL7DaVinciDTR/DTROperations/Questionnaire/$log-questionnaire-errors
{
  "resourceType": "Parameters",
  "parameter": [
    {
      "name": "questionnaire",
      "valueCanonical": "http://hl7.org/fhir/us/davinci-dtr/Questionnaire/home-o2-std-questionnaire|2.1.0"
    },
    {
      "name": "operationOutcome",
      "resource": {
        "resourceType": "OperationOutcome",
```

```
        "issue": [
          {
            "severity": "error",
            "code": "not-found"
          }
        ]
      }
    }
  ]
}
```

Sample response

```
{
  "resourceType": "OperationOutcome",
  "issue": [
    {
      "severity": "error",
      "code": "invalid",
      "diagnostics": "Unable to resolve upstream URL to downstream canonical URL - Canonical URL does not meet format
    expectations (prefix)"
    }
  ]
}
```

14.1.72 Questionnaire.$next-question (R4)

File: site/apis/14-CMS-Incoming/1-R4/11400-Questionnaire-next-question-R4.html
Epic API ID | 11400
FHIR version | R4
Categories | CMS Incoming
API type | Industry-Standard
USCDI | No
HTTP method | POST
Supports OAuth 2.0 | True
Supported user types | Backend Systems and Non-OAuth 2.0
Performs scope validation | False
Source | https://fhir.epic.com/Specifications?api=11400

Description

The Questionnaire.$next-question operation supports adaptive (dynamic) questionnaires by enabling a client to request the next set of questions based on the answers collected so far.

The client sends a FHIR Parameters resource containing a single input parameter named "in", whose value is a QuestionnaireResponse representing the current questionnaire state. The QuestionnaireResponse includes the Questionnaire definition as a contained resource and any answers gathered up to that point.

The server evaluates the adaptive logic and returns a FHIR Parameters resource containing a single output parameter named "out", whose value is an updated QuestionnaireResponse. The returned QuestionnaireResponse preserves previously provided answers and updates the contained Questionnaire to include the next question(s) the client should present.

This operation is typically called repeatedly in a loop:

* The client submits the current QuestionnaireResponse.

* The server returns the next question(s).

* The client collects answers and resubmits.

This cycle repeats until the server returns a QuestionnaireResponse with status = complete.

If the input is invalid or incomplete, the server returns an OperationOutcome describing the issue.

Refer to

Operation Definition of DTR Questionnaire $next-question v2.1.0

Structure Definition of dtr-next-question-input-parameters v2.1.0

, and

Structure Definition of dtr-next-question-output-parameters v2.1.0

for more information.

Request parameters

Name | Type | Optional | Array | Cardinality | Description
Parameters (R4) | Parameters | Required | | 1..1 | Request wrapper for the DTR $next-question operation.
Parameters (R4).meta | Meta | Optional | | 0..1 | Metadata about the resource.
Parameters (R4).meta.profile | String | Optional | Yes | 0..1 | Declares the profile that this Parameters resource conforms to. URL: http://hl7.org/fhir/us/davinci-dtr/StructureDefinition/dtr-next-question-input-parameters
Parameters (R4).parameter | BackboneElement | Required | Yes | 1..1 | Parameter containing the QuestionnaireResponse used as input to determine the next question.
Parameters (R4).parameter.name | string | Required | | 1..1 | Parameter name. Fixed to "in".

Parameters (R4).parameter.resource | ResourceContainer | Required | | 1..1 | QuestionnaireResponse resource.

Parameters (R4).parameter.resource.QuestionnaireResponse | Resource | Required | | 1..1 | Completed responses to the Questionnaire which might be included in this Bundle. Contains answers submitted as structured attachment data. Must be listed as the first element and Bundles must not contain more than one QuestionnaireResponse resource. Refer to Structure Definition of DTR Questionnaire Response v2.1.0 for more information.

Parameters (R4).parameter.resource.QuestionnaireResponse.authored | dateTime | Required | | 1..1 | Date the answers were most recently gathered.

Parameters (R4).parameter.resource.QuestionnaireResponse.contained | ResourceContainer | Required | Yes | 1..* | Contained resources required to support the QuestionnaireResponse. Must include the associated Questionnaire resource.

Parameters (R4).parameter.resource.QuestionnaireResponse.contained.Questionnaire | Resource | Required | | 1..1 | The Questionnaire resource defining the structure and content of the form.

Parameters (R4).parameter.resource.QuestionnaireResponse.contained.Questionnaire.id | id | Required | | 1..1 | The logical identifier of the Questionnaire resource.

Parameters (R4).parameter.resource.QuestionnaireResponse.contained.Questionnaire.status | code | Required | | 1..1 | The publication status of the Questionnaire. URL: http://hl7.org/fhir/ValueSet/publication-status

Parameters (R4).parameter.resource.QuestionnaireResponse.extension (intendedUse) (also: extension (intendedUse)) | Extension | Required | Yes | 1..1 | Indicates how the EHR is to use the information with respect to the associated orders/records. URL: http://hl7.org/fhir/us/davinci-dtr/StructureDefinition/intendedUse

Parameters (R4).parameter.resource.QuestionnaireResponse.extension (intendedUse).url | uri | Required | | 1..1 | The canonical URL identifying the intendedUse extension. URL: http://hl7.org/fhir/us/davinci-dtr/StructureDefinition/intendedUse

Parameters (R4).parameter.resource.QuestionnaireResponse.extension (intendedUse).valueCodeableConcept | CodeableConcept | Required | | 1..1 | The coded value indicating how the QuestionnaireResponse is intended to be used.

Parameters (R4).parameter.resource.QuestionnaireResponse.extension (intendedUse).valueCodeableConcept.coding | Coding | Required | Yes | 1..1 | A coding that represents the intended use value.

Parameters (R4).parameter.resource.QuestionnaireResponse.extension (intendedUse).valueCodeableConcept.coding.code | String | Required | | 1..1 | The code identifying the intended use value within the code system.

Parameters (R4).parameter.resource.QuestionnaireResponse.extension (intendedUse).valueCodeableConcept.coding.system | String | Required | | 1..1 | The code system for the intended use value. URL: http://hl7.org/fhir/us/davinci-crd/ValueSet/DocReason

Parameters (R4).parameter.resource.QuestionnaireResponse.extension (qr-context) (also: extension (qr-context)) | Extension | Required | Yes | 2..* | Identifies the orders and coverages associated with the specified QuestionnaireResponse. The QuestionnaireResponse must have at least one context that refers to a patient Coverage and at least one context that refers to a ServiceRequest resource. URL: http://hl7.org/fhir/us/davinci-dtr/StructureDefinition/qr-context

Parameters (R4).parameter.resource.QuestionnaireResponse.extension (qr-context).url | uri | Required | | 1..1 | The canonical URL identifying the qr-context extension. URL: http://hl7.org/fhir/us/davinci-dtr/StructureDefinition/qr-context

Parameters (R4).parameter.resource.QuestionnaireResponse.extension (qr-context).valueReference | Reference | Required | | 1..1 | Reference to a resource providing context for the QuestionnaireResponse, such as a Coverage or a ServiceRequest resource.

Parameters (R4).parameter.resource.QuestionnaireResponse.id | id | Required | | 1..1 | The identifier of this QuestionnaireResponse. It is required to be submitted with the same ID from when the QuestionnaireResponse resource was retrieved during a previous part of the workflow.

Parameters (R4).parameter.resource.QuestionnaireResponse.item | BackboneElement | Required | Yes | 1..* | A response item corresponding to a question or group in the Questionnaire. Items can be nested several levels deep.

Parameters (R4).parameter.resource.QuestionnaireResponse.item.answer | BackboneElement | Required | Yes | 1..1 | The answer provided for this item. Answer types should be passed back as originally sent. A change in value type could lead to errors. Only one answer is supported per question. Exactly one value[x] element must be present in each answer.

Parameters (R4).parameter.resource.QuestionnaireResponse.item.answer.extension (information-origin) (also: extension (information-origin)) | Extension | Required | Yes | 1..1 | Identifies the origin of the information in the answer and how it came to exist. URL: http://hl7.org/fhir/us/davinci-dtr/StructureDefinition/information-origin

Parameters (R4).parameter.resource.QuestionnaireResponse.item.answer.extension (information-origin).extension (also: extension) | Extension | Required | Yes | 1..1 | Nested extension indicating the source of the information.

Parameters (R4).parameter.resource.QuestionnaireResponse.item.answer.extension (information-origin).extension.url | uri | Required | | 1..1 | Fixed to "source".

Parameters (R4).parameter.resource.QuestionnaireResponse.item.answer.extension (information-origin).extension.valueCode | code | Required | | 1..1 | The codes describing the possible origination of information. Must be from the Information Origins Value Set. URL: http://hl7.org/fhir/us/davinci-dtr/ValueSet/informationOrigins

Parameters (R4).parameter.resource.QuestionnaireResponse.item.answer.extension (information-origin).extension (author) (also: extension (author)) | Extension | Conditional | Yes | 0..1 | Nested extension identifying the author of the information. If source is 'override' or 'manual' then an author must be supplied.

Parameters (R4).parameter.resource.QuestionnaireResponse.item.answer.extension (information-origin).extension (author).extension (@url='practitioner') | Extension | Required | Yes | 1..1 | Reference to the practitioner who authored or modified the information.

Parameters (R4).parameter.resource.QuestionnaireResponse.item.answer.extension (information-origin).extension (author).extension (@url='practitioner').url | uri | Required | | 1..1 | Fixed to "practitioner".

Parameters (R4).parameter.resource.QuestionnaireResponse.item.answer.extension (information-origin).extension (author).extension (@url='practitioner').valueReference | Reference | Required | | 1..1 | Reference to the Practitioner resource representing the author.

Parameters (R4).parameter.resource.QuestionnaireResponse.item.answer.extension (information-origin).extension (author).extension (@url='role') | Extension | Optional | Yes | 0..1 | The role of the individual who provided or modified the information.

Parameters (R4).parameter.resource.QuestionnaireResponse.item.answer.extension (information-origin).extension (author).extension (@url='role').url | uri | Required | | 1..1 | Fixed to "role".

Parameters (R4).parameter.resource.QuestionnaireResponse.item.answer.extension (information-origin).extension (author).extension (@url='role').valueCodeableConcept | CodeableConcept | Required | | 1..1 | The coded role of the author, such as the practitioner role.

Parameters (R4).parameter.resource.QuestionnaireResponse.item.answer.extension (information-origin).extension (author).extension (@url='role').valueCodeableConcept.coding | Coding | Required | Yes | 1..1 | Coding representation of the author role.

Parameters (R4).parameter.resource.QuestionnaireResponse.item.answer.extension (information-origin).extension (author).extension (@url='role').valueCodeableConcept.coding.code | String | Required | | 1..1 | The code identifying the role within the system.

Parameters (R4).parameter.resource.QuestionnaireResponse.item.answer.extension (information-origin).extension (author).extension (@url='role').valueCodeableConcept.coding.system | String | Required | | 1..1 | The code system defining the role. URL: http://hl7.org/fhir/us/core/ValueSet/us-core-provider-role

Parameters (R4).parameter.resource.QuestionnaireResponse.item.answer.extension (information-origin).extension (author).url | uri | Required | | 1..1 | Fixed to "author".

Parameters (R4).parameter.resource.QuestionnaireResponse.item.answer.extension (information-origin).url | uri | Required | | 1..1 | Canonical URL identifying the information-origin extension. URL: http://hl7.org/fhir/us/davinci-dtr/StructureDefinition/information-origin

Parameters (R4).parameter.resource.QuestionnaireResponse.item.answer.valueAttachment | Attachment | Conditional | | 0..1 | File attachment answer.

Parameters (R4).parameter.resource.QuestionnaireResponse.item.answer.valueBoolean | boolean | Conditional | | 0..1 | Boolean true/false answer.

Parameters (R4).parameter.resource.QuestionnaireResponse.item.answer.valueCoding | Coding | Conditional | | 0..1 | Coded answer. System and code are deconstructed.

Parameters (R4).parameter.resource.QuestionnaireResponse.item.answer.valueDate | date | Conditional | | 0..1 | Date answer.

Parameters (R4).parameter.resource.QuestionnaireResponse.item.answer.valueDateTime | dateTime | Conditional | | 0..1 | Date and time answer.

Parameters (R4).parameter.resource.QuestionnaireResponse.item.answer.valueDecimal | decimal | Conditional | | 0..1 | Decimal number answer.

Parameters (R4).parameter.resource.QuestionnaireResponse.item.answer.valueQuantity | Quantity | Conditional | | 0..1 | Quantity with unit.

Parameters (R4).parameter.resource.QuestionnaireResponse.item.answer.valueString | string | Conditional | | 0..1 | Free-text string answer.

Parameters (R4).parameter.resource.QuestionnaireResponse.item.answer.valueTime | time | Conditional | | 0..1 | Time answer.

Parameters (R4).parameter.resource.QuestionnaireResponse.item.item | BackboneElement | Required | Yes | 1..* | A response item corresponding to a question or group in the Questionnaire. Items can be nested several levels deep.

Parameters (R4).parameter.resource.QuestionnaireResponse.item.linkId | string | Required | | 1..1 | The ID connecting this item to its question definition in the system. Must be preserved from previous parts of the workflow.

Parameters (R4).parameter.resource.QuestionnaireResponse.item.text | string | Optional | | 0..1 | The display text for the question or group.

Parameters (R4).parameter.resource.QuestionnaireResponse.meta | Meta | Optional | | 0..1 | Metadata about the QuestionnaireResponse resource.

Parameters (R4).parameter.resource.QuestionnaireResponse.meta.profile | String | Optional | Yes | 0..1 | Declares the profile that this QuestionnaireResponse conforms to. URL: http://hl7.org/fhir/us/davinci-dtr/StructureDefinition/dtr-questionnaireresponse

Parameters (R4).parameter.resource.QuestionnaireResponse.questionnaire | canonical | Required | | 1..1 | Canonical reference to the Questionnaire definition which should be included in the contained resources. Must match the Questionnaire.url value of the included Questionnaire.

Parameters (R4).parameter.resource.QuestionnaireResponse.status | code | Required | | 1..1 | The associated QuestionnaireResponseStatus of the questionnaire response. URL: http://hl7.org/fhir/ValueSet/questionnaire-answers-status

Parameters (R4).parameter.resource.QuestionnaireResponse.subject | Reference | Required | | 1..1 | Reference to the Patient that this response is about.

Parameters (R4).parameter.resource.QuestionnaireResponse.text | Narrative | Optional | | 0..1 | A human-readable narrative representation of the QuestionnaireResponse.

Response elements

Name | Type | Optional | Array | Cardinality | Description

Parameters (R4) | Parameters | Required | | 1..1 | Response wrapper for the DTR $next-question operation.

Parameters (R4).meta | Meta | Optional | | 0..1 | Metadata about the resource.

Parameters (R4).meta.profile | String | Optional | Yes | 0..1 | Declares the profile that this Parameters resource conforms to. URL: http://hl7.org/fhir/us/davinci-dtr/StructureDefinition/dtr-next-question-output-parameters

Parameters (R4).parameter | BackboneElement | Required | Yes | 1..1 | Parameter containing the updated QuestionnaireResponse after processing the next question.

Parameters (R4).parameter.name | string | Required | | 1..1 | Parameter name. Fixed to "out".

Parameters (R4).parameter.resource | ResourceContainer | Required | | 1..1 | QuestionnaireResponse resource.

Parameters (R4).parameter.resource.QuestionnaireResponse | Resource | Required | | 1..1 | Completed responses to the Questionnaire which might be included in this Bundle. Contains answers submitted as structured attachment data. Must be listed as the first element and Bundles must not contain more than one QuestionnaireResponse resource. Refer to Structure Definition of DTR Questionnaire Response v2.1.0 for more information.

Parameters (R4).parameter.resource.QuestionnaireResponse.authored | dateTime | Required | | 1..1 | Date the answers were most recently gathered.

Parameters (R4).parameter.resource.QuestionnaireResponse.contained | ResourceContainer | Required | Yes | 1..* | Container for Questionnaire Resource and other resources as necessary. Must contain at least the Questionnaire Resource.

Parameters (R4).parameter.resource.QuestionnaireResponse.contained.Questionnaire | Resource | Required | | 1..1 | The form definition representing documentation requirements.

Parameters (R4).parameter.resource.QuestionnaireResponse.contained.Questionnaire.id | id | Required | | 1..1 | ID of the Questionnaire resource.

Parameters (R4).parameter.resource.QuestionnaireResponse.contained.Questionnaire.status | code | Required | | 1..1 | The associated PublicationStatus of the questionnaire. URL: http://hl7.org/fhir/ValueSet/publication-status

Parameters (R4).parameter.resource.QuestionnaireResponse.extension (intendedUse) (also: extension (intendedUse)) | Extension | Required | Yes | 1..1 | Indicates how the EHR is to use the information with respect to the associated orders/records. URL: http://hl7.org/fhir/us/davinci-dtr/StructureDefinition/intendedUse

Parameters (R4).parameter.resource.QuestionnaireResponse.extension (intendedUse).url | uri | Required | | 1..1 | The canonical URL identifying the intendedUse extension. URL: http://hl7.org/fhir/us/davinci-dtr/StructureDefinition/intendedUse

Parameters (R4).parameter.resource.QuestionnaireResponse.extension (intendedUse).valueCodeableConcept | CodeableConcept | Required | | 1..1 | The coded value indicating how the QuestionnaireResponse is intended to be used.

Parameters (R4).parameter.resource.QuestionnaireResponse.extension (intendedUse).valueCodeableConcept.coding | Coding | Required | Yes | 1..1 | A coding that represents the intended use value.

Parameters (R4).parameter.resource.QuestionnaireResponse.extension (intendedUse).valueCodeableConcept.coding.code | String | Required | | 1..1 | The code identifying the intended use value within the code system.

Parameters (R4).parameter.resource.QuestionnaireResponse.extension (intendedUse).valueCodeableConcept.coding.system | String | Required | | 1..1 | The code system defining the role. URL: http://hl7.org/fhir/us/core/ValueSet/us-core-provider-role

Parameters (R4).parameter.resource.QuestionnaireResponse.extension (qr-context) (also: extension (qr-context)) | Extension | Required | Yes | 2..* | Identifies the orders and coverages associated with the specified QuestionnaireResponse. The QuestionnaireResponse must have at least one context that refers to a patient Coverage and at least one context that refers to a ServiceRequest resource. URL: http://hl7.org/fhir/us/davinci-dtr/StructureDefinition/qr-context/fhir/us/davinci-dtr/StructureDefinition/qr-context

Parameters (R4).parameter.resource.QuestionnaireResponse.extension (qr-context).url | uri | Required | | 1..1 | The canonical URL identifying the qr-context extension. URL: http://hl7.org/fhir/us/davinci-dtr/StructureDefinition/qr-context

Parameters (R4).parameter.resource.QuestionnaireResponse.extension (qr-context).valueReference | Reference | Required | | 1..1 | Reference to a resource providing context for the QuestionnaireResponse, such as a Coverage or a ServiceRequest resource.

Parameters (R4).parameter.resource.QuestionnaireResponse.id | id | Required | | 1..1 | The identifier of this QuestionnaireResponse. It is required to be submitted with the same ID from when the QuestionnaireResponse resource was retrieved during a previous part of the workflow.

Parameters (R4).parameter.resource.QuestionnaireResponse.item | BackboneElement | Required | Yes | 1..* | A response item corresponding to a question or group in the Questionnaire. Items can be nested several levels deep.

Parameters (R4).parameter.resource.QuestionnaireResponse.item.answer | BackboneElement | Required | Yes | 1..1 | The answer provided for this item. Answer types should be passed back as originally sent. A change in value type could lead to errors. Only one answer is supported per question. Exactly one value[x] element must be present in each answer.

Parameters (R4).parameter.resource.QuestionnaireResponse.item.answer.extension (@url='http://hl7.org/fhir/us/davinci-dtr/StructureDefinition/information-origin') | Extension | Required | Yes | 1..1 | Identifies the origin of the information in the answer and how it came to exist. URL: http://hl7.org/fhir/us/davinci-dtr/StructureDefinition/information-origin

Parameters (R4).parameter.resource.QuestionnaireResponse.item.answer.extension (@url='http://hl7.org/fhir/us/davinci-dtr/StructureDefinition/information-origin').extension (author) (also: extension (author)) | Extension | Conditional | Yes | 0..1 | Nested extension identifying the author of the information. If source is 'override' or 'manual' then an author must be supplied.

Parameters (R4).parameter.resource.QuestionnaireResponse.item.answer.extension (@url='http://hl7.org/fhir/us/davinci-dtr/StructureDefinition/information-origin').extension (author).extension (@url='practitioner') | Extension | Required | Yes | 1..1 | Reference to the practitioner who authored or modified the information.

Parameters (R4).parameter.resource.QuestionnaireResponse.item.answer.extension (@url='http://hl7.org/fhir/us/davinci-dtr/StructureDefinition/information-origin').extension (author).extension (@url='practitioner').url | uri | Required | | 1..1 | Fixed to "practitioner".

Parameters (R4).parameter.resource.QuestionnaireResponse.item.answer.extension (@url='http://hl7.org/fhir/us/davinci-dtr/StructureDefinition/information-origin').extension (author).extension (@url='practitioner').valueReference | Reference | Required | | 1..1 | Reference to the Practitioner resource representing the author.

Parameters (R4).parameter.resource.QuestionnaireResponse.item.answer.extension (@url='http://hl7.org/fhir/us/davinci-dtr/StructureDefinition/information-origin').extension (author).extension (@url='role') | Extension | Optional | Yes | 0..1 | The role of the individual who provided or modified the information.

Parameters (R4).parameter.resource.QuestionnaireResponse.item.answer.extension (@url='http://hl7.org/fhir/us/davinci-dtr/StructureDefinition/information-origin').extension (author).extension (@url='role').url | uri | Required | | 1..1 | Fixed to "role".

Parameters (R4).parameter.resource.QuestionnaireResponse.item.answer.extension (@url='http://hl7.org/fhir/us/davinci-dtr/StructureDefinition/information-origin').extension (author).extension (@url='role').valueCodeableConcept | CodeableConcept | Required | | 1..1 | The coded role of the author, such as the practitioner role.

Parameters (R4).parameter.resource.QuestionnaireResponse.item.answer.extension (@url='http://hl7.org/fhir/us/davinci-dtr/StructureDefinition/information-origin').extension (author).extension (@url='role').valueCodeableConcept.coding | Coding | Required | Yes | 1..1 | Coding representation of the author role.

Parameters (R4).parameter.resource.QuestionnaireResponse.item.answer.extension (@url='http://hl7.org/fhir/us/davinci-dtr/StructureDefinition/information-origin').extension (author).extension (@url='role').valueCodeableConcept.coding.code | String | Required | | 1..1 | The code identifying the role within the system.

Parameters (R4).parameter.resource.QuestionnaireResponse.item.answer.extension (@url='http://hl7.org/fhir/us/davinci-dtr/StructureDefinition/information-origin').extension (author).extension (@url='role').valueCodeableConcept.coding.system | String | Required | | 1..1 | The code system defining the role. URL: http://hl7.org/fhir/us/core/ValueSet/us-core-provider-role

Parameters (R4).parameter.resource.QuestionnaireResponse.item.answer.extension (@url='http://hl7.org/fhir/us/davinci-dtr/StructureDefinition/information-origin').extension (author).url | uri | Required | | 1..1 | Fixed to "author".

Parameters (R4).parameter.resource.QuestionnaireResponse.item.answer.extension (@url='http://hl7.org/fhir/us/davinci-dtr/StructureDefinition/information-origin').extension (source) (also: extension (source)) | Extension | Required | Yes | 1..1 | Nested extension indicating the source of the information.

Parameters (R4).parameter.resource.QuestionnaireResponse.item.answer.extension (@url='http://hl7.org/fhir/us/davinci-dtr/StructureDefinition/information-origin').extension (source).url | uri | Required | | 1..1 | Fixed to "source".

Parameters (R4).parameter.resource.QuestionnaireResponse.item.answer.extension (@url='http://hl7.org/fhir/us/davinci-dtr/StructureDefinition/information-origin').extension (source).valueCode | code | Required | | 1..1 | The codes describing the possible origination of information. Must be from the Information Origins Value Set. URL: http://hl7.org/fhir/us/davinci-dtr/ValueSet/informationOrigins

Parameters (R4).parameter.resource.QuestionnaireResponse.item.answer.extension (@url='http://hl7.org/fhir/us/davinci-dtr/StructureDefinition/information-origin').url | uri | Required | | 1..1 | Canonical URL identifying the information-origin extension. URL: http://hl7.org/fhir/us/davinci-dtr/StructureDefinition/information-origin

Parameters (R4).parameter.resource.QuestionnaireResponse.item.answer.valueAttachment | Attachment | Conditional | | 0..1 | File attachment answer.

Parameters (R4).parameter.resource.QuestionnaireResponse.item.answer.valueBoolean | boolean | Conditional | | 0..1 | Boolean true/false answer.

Parameters (R4).parameter.resource.QuestionnaireResponse.item.answer.valueCoding | Coding | Conditional | | 0..1 | Coded answer. System and code are deconstructed.

Parameters (R4).parameter.resource.QuestionnaireResponse.item.answer.valueDate | date | Conditional | | 0..1 | Date answer.

Parameters (R4).parameter.resource.QuestionnaireResponse.item.answer.valueDateTime | dateTime | Conditional | | 0..1 | Date and time answer.

Parameters (R4).parameter.resource.QuestionnaireResponse.item.answer.valueDecimal | decimal | Conditional | | 0..1 | Decimal number answer.

Parameters (R4).parameter.resource.QuestionnaireResponse.item.answer.valueQuantity | Quantity | Conditional | | 0..1 | Quantity with unit.

Parameters (R4).parameter.resource.QuestionnaireResponse.item.answer.valueString | string | Optional | | 0..1 | Free-text string answer.

Parameters (R4).parameter.resource.QuestionnaireResponse.item.answer.valueTime | time | Optional | | 0..1 | Time answer.

Parameters (R4).parameter.resource.QuestionnaireResponse.item.item | BackboneElement | Required | Yes | 1..* | A response item corresponding to a question or group in the Questionnaire. Items can be nested several levels deep.

Parameters (R4).parameter.resource.QuestionnaireResponse.item.linkId | string | Required | | 1..1 | The ID connecting this item to its question definition in the system. Must be preserved from previous parts of the workflow.

Parameters (R4).parameter.resource.QuestionnaireResponse.item.text | string | Optional | | 0..1 | The display text for the question or group.

Parameters (R4).parameter.resource.QuestionnaireResponse.meta | Meta | Optional | | 0..1 | Metadata about the resource.

Parameters (R4).parameter.resource.QuestionnaireResponse.meta.profile | String | Optional | Yes | 0..1 | Declares the profile the QuestionnaireResponse resource conforms to. URL: http://hl7.org/fhir/us/davinci-dtr/StructureDefinition/dtr-questionnaireresponse

Parameters (R4).parameter.resource.QuestionnaireResponse.questionnaire | canonical | Required | | 1..1 | Canonical reference to the Questionnaire definition which should be included in the contained resources. Must match the Questionnaire.url value of the included Questionnaire.

Parameters (R4).parameter.resource.QuestionnaireResponse.status | code | Required | | 1..1 | The associated QuestionnaireResponseStatus of the questionnaire response. URL: http://hl7.org/fhir/ValueSet/questionnaire-answers-status

Parameters (R4).parameter.resource.QuestionnaireResponse.subject | Reference | Required | | 1..1 | Reference to the Patient that this response is about.

Parameters (R4).parameter.resource.QuestionnaireResponse.text | Narrative | Optional | | 0..1 | The display text for the question or group.

Sample request

```
POST https://hostname/instance/api/epic/2024/HL7DaVinciDTR/DTROperations/Questionnaire/$next-question
{
  "resourceType": "Parameters",
  "meta": {
    "profile": [
      "http://hl7.org/fhir/us/davinci-dtr/StructureDefinition/dtr-next-question-input-parameters"
    ]
  },
  "parameter": [
    {
      "name": "in",
      "resource": {
        "resourceType": "QuestionnaireResponse",
        "meta": {
          "profile": [
            "http://hl7.org/fhir/us/davinci-dtr/StructureDefinition/dtr-questionnaireresponse"
          ]
        },
        "extension": [
          {
            "url": "http://hl7.org/fhir/us/davinci-dtr/StructureDefinition/qr-context",
            "valueReference": {
              "reference": "Coverage/123"
            }
          },
          {
            "url": "http://hl7.org/fhir/us/davinci-dtr/StructureDefinition/qr-context",
            "valueReference": {
              "reference": "ServiceRequest/abc"
            }
          },
          {
            "url": "http://hl7.org/fhir/us/davinci-dtr/StructureDefinition/intendedUse",
            "valueCodeableConcept": {
              "coding": [
                {
                  "system": "http://hl7.org/fhir/us/davinci-crd/CodeSystem/temp",
                  "code": "withorder",
                  "display": "Include with order"
                }
              ]
            }
          }
        ],
        "questionnaire": "http://example.org/fhir/Questionnaire/my-adaptive-questionnaire|1.0.0",
        "status": "in-progress",
        "subject": {
          "reference": "Patient/789"
        },
        "authored": "2026-03-09T14:12:00-05:00",
        "item": [
          {
            "linkId": "1",
            "text": "Patient information",
            "item": [
              {
                "linkId": "1.1",
                "text": "Last name",
                "answer": [
                  {
                    "extension": [
                      {
                        "url": "http://hl7.org/fhir/us/davinci-dtr/StructureDefinition/information-origin",
                        "extension": [
                          {
                            "url": "source",
                            "valueCode": "auto"
                          }
                        ]
                      }
                    ],
                    "valueString": "Quinton"
                  }
                ]
              },
              {
                "linkId": "1.2",
                "text": "Date of birth",
                "answer": [
                  {
```

```
          "extension": [
            {
              "url": "http://hl7.org/fhir/us/davinci-dtr/StructureDefinition/information-origin",
              "extension": [
                {
                  "url": "source",
                  "valueCode": "auto"
                }
              ]
            }
          ],
          "valueDate": "1956-12-01"
        }
      ]
    }
  ]
},
{
  "linkId": "2",
  "text": "Coverage requirements",
  "item": [
    {
      "linkId": "2.1",
      "text": "Is the patient currently on oxygen?",
      "answer": [
        {
          "extension": [
            {
              "url": "http://hl7.org/fhir/us/davinci-dtr/StructureDefinition/information-origin",
              "extension": [
                {
                  "url": "source",
                  "valueCode": "override"
                },
                {
                  "url": "author",
                  "extension": [
                    {
                      "url": "role",
                      "valueCodeableConcept": {
                        "coding": [
                          {
                            "system": "http://terminology.hl7.org/CodeSystem/practitioner-role",
                            "code": "doctor",
                            "display": "Doctor"
                          }
                        ]
                      }
                    },
                    {
                      "url": "practitioner",
                      "valueReference": {
                        "reference": "Practitioner/456",
                        "display": "Dr. Jane Doe"
                      }
                    }
                  ]
                }
              ]
            }
          ],
          "valueBoolean": true
        }
      ]
    },
    {
      "linkId": "2.2",
      "text": "Resting PO2 (mm[Hg])",
      "answer": [
        {
          "extension": [
            {
              "url": "http://hl7.org/fhir/us/davinci-dtr/StructureDefinition/information-origin",
              "extension": [
                {
                  "url": "source",
                  "valueCode": "auto"
                }
              ]
            }
          ],
          "valueQuantity": {
            "value": 83,
            "system": "http://unitsofmeasure.org",
            "code": "mm[Hg]"
          }
        }
      ]
    },
```

```
            {
              "linkId": "2.3",
              "text": "Primary diagnosis",
              "answer": [
                {
                  "extension": [
                    {
                      "url": "http://hl7.org/fhir/us/davinci-dtr/StructureDefinition/information-origin",
                      "extension": [
                        {
                          "url": "source",
                          "valueCode": "auto"
                        }
                      ]
                    }
                  ],
                  "valueCoding": {
                    "system": "http://snomed.info/sct",
                    "code": "313296004",
                    "display": "Mild chronic obstructive pulmonary disease"
                  }
                }
              ]
            }
          ]
        }
      ]
    }
  ]
}
```

Sample response

```
{
  "resourceType": "Parameters",
  "meta": {
    "profile": [
      "http://hl7.org/fhir/us/davinci-dtr/StructureDefinition/dtr-next-question-output-parameters"
    ]
  },
  "parameter": [
    {
      "name": "out",
      "resource": {
        "resourceType": "QuestionnaireResponse",
        "meta": {
          "profile": [
            "http://hl7.org/fhir/us/davinci-dtr/StructureDefinition/dtr-questionnaireresponse"
          ]
        },
        "extension": [
          {
            "url": "http://hl7.org/fhir/us/davinci-dtr/StructureDefinition/qr-context",
            "valueReference": {
              "reference": "Coverage/123"
            }
          },
          {
            "url": "http://hl7.org/fhir/us/davinci-dtr/StructureDefinition/qr-context",
            "valueReference": {
              "reference": "ServiceRequest/abc"
            }
          },
          {
            "url": "http://hl7.org/fhir/us/davinci-dtr/StructureDefinition/intendedUse",
            "valueCodeableConcept": {
              "coding": [
                {
                  "system": "http://hl7.org/fhir/us/davinci-crd/CodeSystem/temp",
                  "code": "withorder",
                  "display": "Include with order"
                }
              ]
            }
          }
        ],
        "questionnaire": "http://example.org/fhir/Questionnaire/my-adaptive-questionnaire|1.0.0",
        "status": "in-progress",
        "subject": {
          "reference": "Patient/789"
        },
        "authored": "2026-03-09T14:12:00-05:00",
        "item": [
          {
            "linkId": "1",
            "text": "Patient information",
            "item": [
              {
```

```
      "linkId": "1.1",
      "text": "Last name",
      "answer": [
        {
          "extension": [
            {
              "url": "http://hl7.org/fhir/us/davinci-dtr/StructureDefinition/information-origin",
              "extension": [
                {
                  "url": "source",
                  "valueCode": "auto"
                }
              ]
            }
          ],
          "valueString": "Quinton"
        }
      ]
    }
  ]
},
{
  "linkId": "3",
  "text": "Prescribed use",
  "item": [
    {
      "linkId": "3.1",
      "text": "Start date",
      "answer": [
        {
          "extension": [
            {
              "url": "http://hl7.org/fhir/us/davinci-dtr/StructureDefinition/information-origin",
              "extension": [
                {
                  "url": "source",
                  "valueCode": "auto"
                }
              ]
            }
          ],
          "valueDate": "2026-03-01"
        }
      ]
    },
    {
      "linkId": "3.2",
      "text": "Length of need (months)",
      "answer": [
        {
          "extension": [
            {
              "url": "http://hl7.org/fhir/us/davinci-dtr/StructureDefinition/information-origin",
              "extension": [
                {
                  "url": "source",
                  "valueCode": "auto"
                }
              ]
            }
          ],
          "valueInteger": 99
        }
      ]
    },
    {
      "linkId": "3.3",
      "text": "Peak flow rate",
      "item": [
        {
          "linkId": "3.3.1",
          "text": "Liters per minute",
          "answer": [
            {
              "extension": [
                {
                  "url": "http://hl7.org/fhir/us/davinci-dtr/StructureDefinition/information-origin",
                  "extension": [
                    {
                      "url": "source",
                      "valueCode": "auto"
                    }
                  ]
                }
              ],
              "valueQuantity": {
                "value": 2,
                "system": "http://unitsofmeasure.org",
                "code": "L/min"
```

```
                    }
                  }
                ]
              },
              {
                "linkId": "3.3.2",
                "text": "Oxygen percent",
                "answer": [
                  {
                    "extension": [
                      {
                        "url": "http://hl7.org/fhir/us/davinci-dtr/StructureDefinition/information-origin",
                        "extension": [
                          {
                            "url": "source",
                            "valueCode": "auto"
                          }
                        ]
                      }
                    ],
                    "valueInteger": 98
                  }
                ]
              }
            ]
          },
          {
            "linkId": "3.4",
            "text": "NEXT QUESTION: Frequency of use (choose one)",
            "answer": [
              {
                "extension": [
                  {
                    "url": "http://hl7.org/fhir/us/davinci-dtr/StructureDefinition/information-origin",
                    "extension": [
                      {
                        "url": "source",
                        "valueCode": "auto"
                      }
                    ]
                  }
                ],
                "valueCoding": {
                  "system": "http://example.org/fhir/CodeSystem/frequency",
                  "code": "rest-awake",
                  "display": "At rest and awake"
                }
              }
            ]
          }
        ]
      }
    ]
  }
}
```


14.1.73 Questionnaire.$questionnaire-package (R4)

File: site/apis/14-CMS-Incoming/1-R4/11287-Questionnaire-questionnaire-package-R4.html
Epic API ID | 11287
FHIR version | R4
Categories | CMS Incoming
API type | Industry-Standard
USCDI | No
Supports OAuth 2.0 | True
Supported user types | Backend Systems and Non-OAuth 2.0
Performs scope validation | False
Source | https://fhir.epic.com/Specifications?api=11287

Description

The HL7 FHIR Da Vinci Documentation Templates and Rules (DTR) STU 2.1 (

https://hl7.org/fhir/us/davinci-dtr/STU2.1/

) enables health plans to express their documentation requirements for prior authorizations and to allow health systems to gather and submit that information in a streamlined manner.

When a health plan responds to a CRD (

https://hl7.org/fhir/us/davinci-crd/STU2.1/

) or PAS (

https://hl7.org/fhir/us/davinci-pas/STU2.1/

) message indicating that clinical or administrative data is required, and optionally includes a canonical questionnaire, the health system performs a $questionnaire-package operation (

https://hl7.org/fhir/us/davinci-dtr/STU2.1/OperationDefinition-questionnaire-package.html

Health systems use the $questionnaire-package operation (

https://hl7.org/fhir/us/davinci-dtr/STU2.1/StructureDefinition-dtr-qpackage-input-parameters.html

) to retrieve a DTR Standard Questionnaire resource (

https://hl7.org/fhir/us/davinci-dtr/STU2.1/StructureDefinition-dtr-std-questionnaire.html

) from the output (

https://hl7.org/fhir/us/davinci-dtr/STU2.1/StructureDefinition-dtr-qpackage-output-parameters.html

), which is shown to an appropriate user.

The health system then builds a QuestionnaireResponse resource from the answered questionnaire and sends it to the health plan as part of the PAS request process.

Request parameters

Name | Type | Optional | Array | Cardinality | Description

Parameters (R4) | Parameters | Required | | 1..1 | Parameters for $questionnaire-package include at least 1 coverage and either at least 1 order or a context string provided prior. Attempts to request a questionnaire directly without an order or context provided are ignored. A Patient resource is always required to be included as a "referenced" Parameter.

Parameters (R4).parameter (context) (also: parameter (context)) | BackboneElement | Conditional | Yes | 0..1 | Context string provided prior to calling this API. Either "context" or "order" is required.

Parameters (R4).parameter (context).name | string | Required | | 1..1 | Parameter name. Fixed to "context".

Parameters (R4).parameter (context).valueString | String | Required | | 1..1 | Context string provided prior to calling this API. Either "context" or "order" is required.

Parameters (R4).parameter (coverage) (also: parameter (coverage)) | BackboneElement | Required | Yes | 1..* | The coverage/payer context used for member coverage matching and payer-specific documentation requirements. At least one Coverage is required in all supported flows.

Parameters (R4).parameter (coverage).name | string | Required | | 1..1 | Parameter name. Fixed to "coverage".

Parameters (R4).parameter (coverage).resource | ResourceContainer | Required | | 1..1 | Coverage resource.

Parameters (R4).parameter (coverage).resource.Coverage | Resource | Required | | 1..1 | Coverage resource. Refer to Structure Definition of Coverage v2.1.0 for more information.

Parameters (R4).parameter (coverage).resource.Coverage.beneficiary | Reference | Required | | 1..1 | Patient that is covered by the coverage sent. Must match patient in referenced resources.

Parameters (R4).parameter (coverage).resource.Coverage.contained | ResourceContainer | Optional | Yes | 0..1 | Can use "contained" in place of "reference" if the resource is only referenced within the Coverage resource.

Parameters (R4).parameter (coverage).resource.Coverage.id | id | Required | | 1..1 | The ID of the coverage.

Parameters (R4).parameter (coverage).resource.Coverage.identifier | Identifier | Required | Yes | 1..* | Can include multiple identifiers, however, one identifier should be a Member ID identifier to find the patient in the receiving system. This specific type is documented below.

Parameters (R4).parameter (coverage).resource.Coverage.identifier.type | CodeableConcept | Required | | 1..1 | Identifier type. Must include coding from system "http://terminology.hl7.org/CodeSystem/v2-0203" with code "MB".

Parameters (R4).parameter (coverage).resource.Coverage.identifier.value | String | Required | | 1..1 | Member ID value.

Parameters (R4).parameter (coverage).resource.Coverage.payor | Reference | Required | Yes | 1..1 | Reference to insurer organization.

Parameters (R4).parameter (coverage).resource.Coverage.relationship | CodeableConcept | Required | | 1..1 | Beneficiary relationship to the subscriber. Must include a coding system with either: https://codesystem.x12.org/005010/1069
http://terminology.hl7.org/CodeSystem/subscriber-relationship

Parameters (R4).parameter (coverage).resource.Coverage.status | code | Required | | 1..1 | A code specifying the state of the resource instance. URL: http://hl7.org/fhir/ValueSet/fm-status

Parameters (R4).parameter (coverage).resource.Coverage.subscriber | Reference | Conditional | | 0..1 | Reference to subscriber.

Parameters (R4).parameter (coverage).resource.Coverage.subscriberId | string | Optional | | 0..1 | Subscriber or Member ID. Must match the member ID value in the identifier.

Parameters (R4).parameter (order) (also: parameter (order)) | BackboneElement | Conditional | Yes | 0..* | The order being requested. Only ServiceRequest type supported currently. Either "context" or "order" is required.

Parameters (R4).parameter (order).name | string | Required | | 1..1 | Parameter name. Fixed to "order".

Parameters (R4).parameter (order).resource | ResourceContainer | Required | | 1..1 | ServiceRequest resource being requested.

Parameters (R4).parameter (order).resource.ServiceRequest | Resource | Required | | 1..1 | ServiceRequest resource being requested. Refer to Structure Definition of ServiceRequest v2.1.0 for more information.

Parameters (R4).parameter (order).resource.ServiceRequest.authoredOn | dateTime | Conditional | | 0..1 | Timestamp of the request. Defaults to date received in some implementations.

Parameters (R4).parameter (order).resource.ServiceRequest.code | CodeableConcept | Required | | 1..1 | Required code identifying the service request. Must resolve in receiver's system to a known code. Can use a system such as "http://www.ama-assn.org/go/cpt".

Parameters (R4).parameter (order).resource.ServiceRequest.id | id | Required | | 1..1 | The ID of the ServiceRequest.

Parameters (R4).parameter (order).resource.ServiceRequest.insurance | Reference | Optional | Yes | 0..1 | Insurance preference if multiple coverages are provided. Does not guarantee that only that coverage is used in cases where other coverage is more appropriate.

Parameters (R4).parameter (order).resource.ServiceRequest.intent | code | Optional | | 0..1 | The kind of service request. Must use a value from value set: http://hl7.org/fhir/ValueSet/request-intent

Parameters (R4).parameter (order).resource.ServiceRequest.occurrenceDateTime | String | Conditional | | 0..1 | Timing of requested service. The "occurrence" elements priority order are: occurrencePeriod.start, occurrenceDateTime, occurrenceTiming.event[0], then occurrenceTiming.repeat.boundsPeriod.start. If multiple values provided, the element that comes first in the priority order is used first. If not given, defaults to date received in some implementations.

Parameters (R4).parameter (order).resource.ServiceRequest.occurrencePeriod | Period | Conditional | | 0..1 | Timing of requested service. The "occurrence" elements priority order are: occurrencePeriod.start, occurrenceDateTime, occurrenceTiming.event[0], then occurrenceTiming.repeat.boundsPeriod.start. If multiple values provided, the element that comes first in the priority order is used first. If not given,

defaults to date received in some implementations.

Parameters (R4).parameter (order).resource.ServiceRequest.occurrenceTiming | Timing | Conditional | | 0..1 | Timing of requested service. The "occurrence" elements priority order are: occurrencePeriod.start, occurrenceDateTime, occurrenceTiming.event[0], then occurrenceTiming.repeat.boundsPeriod.start. If multiple values provided, the element that comes first in the priority order is used first. If not given, defaults to date received in some implementations.

Parameters (R4).parameter (order).resource.ServiceRequest.performer | Reference | Conditional | Yes | 0..1 | Reference to PractitionerRole that is the expected performer of the request, which should be found in a "referenced" Parameter. Should be included for best results. Might be required based on system settings.

Parameters (R4).parameter (order).resource.ServiceRequest.reasonCode | CodeableConcept | Conditional | Yes | 0..1 | Diagnosis associated with request. Should be from coding systems recognizable in the system. Examples include: "http://snomed.info/sct" "http://hl7.org/fhir/sid/icd-10-cm" Should be included for best results. Might be required based on system settings.

Parameters (R4).parameter (order).resource.ServiceRequest.requester | Reference | Conditional | | 0..1 | Reference to PractitionerRole to be found in a "referenced" Parameter. Should be included for best results. Might be required based on system settings.

Parameters (R4).parameter (order).resource.ServiceRequest.status | code | Optional | | 0..1 | The RequestStatus of a service order. URL: http://hl7.org/fhir/ValueSet/request-status

Parameters (R4).parameter (order).resource.ServiceRequest.subject | Reference | Required | | 1..1 | Must be a reference to the patient in referenced resources.

Parameters (R4).parameter (questionnaire) | BackboneElement | | Yes | | Parameter array.

Parameters (R4).parameter (referenced) (also: parameter (referenced)) | BackboneElement | Required | Yes | 1..* | Referenced resources in the bundle. Must include references to all mentioned references in the bundle for proper processing and the most accurate response. Not all references are validated, and if not included, the references default to being "unknown" where possible. Must at least include a single Patient resource.

Parameters (R4).parameter (referenced).name | string | Required | | 1..1 | Parameter name. Fixed to "referenced".

Parameters (R4).parameter (referenced).resource | ResourceContainer | Required | | 1..1 | Resource container for individual referenced parameters. Does not have to contain a patient resource.

Parameters (R4).parameter (referenced).resource.Patient | Resource | Required | | 1..1 | The Patient resource to include in the referenced parameters. There must be exactly one of these provided within the request.

Parameters (R4).parameter (referenced).resource.Patient.id | id | Required | | 1..1 | The ID of the patient must match references made in the Coverage resource and when applicable, also the ServiceRequest resource.

Response elements

Name | Type | Optional | Array | Cardinality | Description

Parameters (R4) | Parameters | Required | | 1..1 | Response wrapper for the DTR $questionnaire-package operation.

Parameters (R4).meta | Meta | Optional | | 0..1 | Metadata about the response resource.

Parameters (R4).meta.profile | String | Optional | Yes | 0..1 | Declares the profile the Parameters resource conforms to. URL: http://hl7.org/fhir/us/davinci-dtr/StructureDefinition/dtr-qpackage-output-parameters

Parameters (R4).parameter (PackageBundle) (also: parameter (PackageBundle)) | BackboneElement | Required | Yes | 1..* | PackageBundle parameter.

Parameters (R4).parameter (PackageBundle).name | string | Required | | 1..1 | Parameter name. Fixed to "PackageBundle".

Parameters (R4).parameter (PackageBundle).resource | ResourceContainer | Required | | 1..1 | The Bundle resource for this parameter entry.

Parameters (R4).parameter (PackageBundle).resource.Bundle | Bundle | Required | | 1..* | A package containing the Questionnaire and a corresponding QuestionnaireResponse skeleton. Based on: Structure Definition of DTR QRBundle v2.1.0

Parameters (R4).parameter (PackageBundle).resource.Bundle.entry | BackboneElement | Required | Yes | 2..* | Entries included in the package bundle. Includes a Questionnaire and QuestionnaireResponse, might include more depending on additional system setup.

Parameters (R4).parameter (PackageBundle).resource.Bundle.entry.fullUrl | uri | Required | | 1..1 | URL for the resource.

Parameters (R4).parameter (PackageBundle).resource.Bundle.entry.resource | ResourceContainer | Required | | 1..1 | Resources within the bundle.

Parameters (R4).parameter (PackageBundle).resource.Bundle.entry.resource.Library | Resource

Parameters (R4).parameter (PackageBundle).resource.Bundle.entry.resource.Questionnaire (also: Questionnaire) | Resource | Required | | 1..1 | The form definition representing documentation requirements.

Parameters (R4).parameter (PackageBundle).resource.Bundle.entry.resource.Questionnaire.id | id | Optional | | 0..1 | ID of the Questionnaire resource.

Parameters (R4).parameter (PackageBundle).resource.Bundle.entry.resource.Questionnaire.item | BackboneElement | Required | Yes | 1..* | A response item corresponding to a question or group in the Questionnaire. Items can be nested several levels deep.

Parameters (R4).parameter (PackageBundle).resource.Bundle.entry.resource.Questionnaire.item.answerValueSet | canonical | Required | | 0..1 | Canonical URL of a ValueSet containing permitted answers for choice/open-choice questions. ValueSet can be in the bundle itself or it might not be. This depends on system settings. Clients might need to resolve it externally by calling $valueset-expand.

Parameters (R4).parameter (PackageBundle).resource.Bundle.entry.resource.Questionnaire.item.item | BackboneElement | Required | Yes | 1..* | A response item corresponding to a question or group in the Questionnaire. Items can be nested several levels deep.

Parameters (R4).parameter (PackageBundle).resource.Bundle.entry.resource.Questionnaire.item.linkId | string | Required | | 1..1 | Unique identifier within the questionnaire used to correlate with QuestionnaireResponse items.

Parameters (R4).parameter (PackageBundle).resource.Bundle.entry.resource.Questionnaire.item.text | string | Required | | 1..1 | The display text for the question or group.

Parameters (R4).parameter (PackageBundle).resource.Bundle.entry.resource.Questionnaire.item.type | code | Required | | 1..1 | Questionnaire Item Type. Type from http://hl7.org/fhir/ValueSet/item-type is expected.

Parameters (R4).parameter (PackageBundle).resource.Bundle.entry.resource.Questionnaire.status | code | Required | | 1..1 | Publication status of the questionnaire. Status should be from: http://hl7.org/fhir/ValueSet/publication-status

Parameters (R4).parameter (PackageBundle).resource.Bundle.entry.resource.Questionnaire.title | string | Optional | | 0..1 | Human-readable title for display.

Parameters (R4).parameter (PackageBundle).resource.Bundle.entry.resource.QuestionnaireResponse | Resource | Required | | 1..1 | A response template/skeleton corresponding to the Questionnaire. Responses are not pre-populated by default. They might be if additional configuration and setup is done. It is important that the structure is kept when being sent back completed.

Parameters (R4).parameter (PackageBundle).resource.Bundle.entry.resource.QuestionnaireResponse.authored | dateTime | Required | | 1..1 | Date the Questionnaire was sent or filled out.

Parameters (R4).parameter (PackageBundle).resource.Bundle.entry.resource.QuestionnaireResponse.extension (intendedUse) (also: extension (intendedUse)) | Extension | Required | Yes | 1..* | Indicates how the EHR is to use the information with respect to the associated orders/records. URL: http://hl7.org/fhir/us/davinci-dtr/StructureDefinition/intendedUse

Parameters (R4).parameter (PackageBundle).resource.Bundle.entry.resource.QuestionnaireResponse.extension (intendedUse).url | uri | Required | | 1..1 | The canonical URL identifying the intendedUse extension. URL: http://hl7.org/fhir/us/davinci-dtr/StructureDefinition/intendedUse

Parameters (R4).parameter (PackageBundle).resource.Bundle.entry.resource.QuestionnaireResponse.extension (intendedUse).valueCodeableConcept | CodeableConcept | Required | | 1..1 | The coded value indicating how the QuestionnaireResponse is intended to be used.

Parameters (R4).parameter (PackageBundle).resource.Bundle.entry.resource.QuestionnaireResponse.extension (intendedUse).valueCodeableConcept.coding | Coding | Required | Yes | 1..1 | A coding that represents the intended use value.

Parameters (R4).parameter (PackageBundle).resource.Bundle.entry.resource.QuestionnaireResponse.extension (intendedUse).valueCodeableConcept.coding.code | String | Required | | 1..1 | The code identifying the intended use value within the code system.

Parameters (R4).parameter (PackageBundle).resource.Bundle.entry.resource.QuestionnaireResponse.extension (intendedUse).valueCodeableConcept.coding.system | String | Required | | 1..1 | The code system for the intended use value. URL: http://hl7.org/fhir/us/davinci-crd/ValueSet/DocReason

Parameters (R4).parameter (PackageBundle).resource.Bundle.entry.resource.QuestionnaireResponse.extension (qr-context) (also: extension (qr-context)) | Extension | Required | Yes | 2..* | Identifies the orders and coverages associated with the specified QuestionnaireResponse. The QuestionnaireResponse must have at least one context that refers to a patient Coverage and at least one context that refers to a Request resource. It is important these references to the services be preserved when doing later workflows. URL: http://hl7.org/fhir/us/davinci-dtr/StructureDefinition/qr-context

Parameters (R4).parameter (PackageBundle).resource.Bundle.entry.resource.QuestionnaireResponse.extension (qr-context).url | uri | Required | | 1..1 | The canonical URL identifying the qr-context extension. URL: http://hl7.org/fhir/us/davinci-dtr/StructureDefinition/qr-context

Parameters (R4).parameter (PackageBundle).resource.Bundle.entry.resource.QuestionnaireResponse.extension (qr-context).valueReference | Reference | Required | | 1..1 | Reference to a resource providing context for the QuestionnaireResponse, such as a Coverage or a ServiceRequest resource.

Parameters (R4).parameter (PackageBundle).resource.Bundle.entry.resource.QuestionnaireResponse.id | id | Required | | 1..1 | The ID of this QuestionnaireResponse. It is required to be submitted with the same ID when being used in a later workflow.

Parameters (R4).parameter (PackageBundle).resource.Bundle.entry.resource.QuestionnaireResponse.item | BackboneElement | Required | Yes | 1..* | A response item corresponding to a question or group in the Questionnaire. Items can be nested several levels deep.

Parameters (R4).parameter (PackageBundle).resource.Bundle.entry.resource.QuestionnaireResponse.item.item | BackboneElement | Required | Yes | 1..* | A response item corresponding to a question or group in the Questionnaire. Items can be nested several levels deep.

Parameters (R4).parameter (PackageBundle).resource.Bundle.entry.resource.QuestionnaireResponse.item.linkId | string | Required | | 1..1 | Unique identifier within the questionnaire used to correlate with QuestionnaireResponse items.

Parameters (R4).parameter (PackageBundle).resource.Bundle.entry.resource.QuestionnaireResponse.questionnaire | canonical | Required | | 1..1 | Canonical reference to the Questionnaire this response answers. Must correspond to the questionnaire in this Bundle.

Parameters (R4).parameter (PackageBundle).resource.Bundle.entry.resource.QuestionnaireResponse.status | code | Required | | 1..1 | The associated QuestionnaireResponseStatus of the questionnaire response. URL: http://hl7.org/fhir/ValueSet/questionnaire-answers-status

Parameters (R4).parameter (PackageBundle).resource.Bundle.entry.resource.QuestionnaireResponse.subject | Reference | Required | | 1..1 | Reference to the Patient that this response is about.

Parameters (R4).parameter (PackageBundle).resource.Bundle.entry.resource.ValueSet | ValueSet | Conditional | | 0..* | Optional terminology artifacts used by Questionnaire items for answer lists. Might be included depending on additional system setup.

Parameters (R4).parameter (PackageBundle).resource.Bundle.entry.resource.ValueSet.expansion | BackboneElement | | | 0..1 | ValueSet expansion details.

Parameters (R4).parameter (PackageBundle).resource.Bundle.entry.resource.ValueSet.expansion.contains | BackboneElement | | Yes | 0..* | Array of codes in the ValueSet.

Parameters (R4).parameter (PackageBundle).resource.Bundle.entry.resource.ValueSet.expansion.contains.code | code | | | 1..1 | Code value.

Parameters (R4).parameter (PackageBundle).resource.Bundle.entry.resource.ValueSet.expansion.contains.display | string | | | 1..1 | Display value associated with the code.

Parameters (R4).parameter (PackageBundle).resource.Bundle.entry.resource.ValueSet.expansion.contains.system | uri | | | 1..1 | System value for the code.

Parameters (R4).parameter (PackageBundle).resource.Bundle.entry.resource.ValueSet.expansion.parameter | BackboneElement | | Yes | 1..* | Parameter that controlled the expansion process.

Parameters (R4).parameter (PackageBundle).resource.Bundle.entry.resource.ValueSet.expansion.parameter.name | string | | | 1..1 | Parameter name as assigned by the client or server.

Parameters (R4).parameter (PackageBundle).resource.Bundle.entry.resource.ValueSet.expansion.parameter.valueUri | uri | | | 0..1 | Parameter value. Used with the context parameter.

Parameters (R4).parameter (PackageBundle).resource.Bundle.entry.resource.ValueSet.expansion.timestamp | dateTime | | | 1..1 | Time when the ValueSet expansion occurred.

Parameters (R4).parameter (PackageBundle).resource.Bundle.entry.resource.ValueSet.expansion.total | integer | | | 1..1 | Total number of codes in the expansion.

Parameters (R4).parameter (PackageBundle).resource.Bundle.entry.resource.ValueSet.status | code | | | 1..1 | Status of the ValueSet. Always active.

Parameters (R4).parameter (PackageBundle).resource.Bundle.entry.resource.ValueSet.url | uri | | | 1..1 | A canonical reference to this ValueSet.

Parameters (R4).parameter (PackageBundle).resource.Bundle.id | id | Conditional | | 0..1 | Identification for the Bundle. This is conditionally required based on system settings.

Parameters (R4).parameter (PackageBundle).resource.Bundle.meta | Meta | Optional | | 0..1 | Metadata about the bundle.

Parameters (R4).parameter (PackageBundle).resource.Bundle.meta.profile | String | Conditional | Yes | 0..1 | Declares the profile the Bundle conforms to. URL: https://hl7.org/fhir/us/davinci-dtr/STU2.1/StructureDefinition-DTR-QPackageBundle.html

Parameters (R4).parameter (PackageBundle).resource.Bundle.type | code | Required | | 1..1 | The bundle type. Must be "collection".

Sample request

```
POST https://hostname/instance/api/epic/2024/HL7DaVinciDTR/DTROperations/Questionnaire/$questionnaire-package
{
    "resourceType": "Parameters",
    "parameter": [
        {
            "name": "coverage",
            "resource": {
                "resourceType": "Coverage",
```

```
        "id": "eOC6c0z2Ies1te1ZW4ktIZwto-ymEqA6jqTGzgupccEpmp9F5VVHw1xclgcbl5yBU3",
        "identifier": [
            {
                "system": "urn:oid:1.2.840.114350.1.13.5325.1.7.2.678671",
                "value": "1026274"
            },
            {
                "type": {
                    "coding": [
                        {
                            "system": "http://terminology.hl7.org/CodeSystem/v2-0203",
                            "code": "MB",
                            "display": "Member Number"
                        }
                    ]
                },
                "value": "46796"
            }
        ],
        "status": "active",
        "subscriber": {
            "reference": "Patient/eLpjtce.j.HQohqaWuElZYg3",
            "display": "Mkk, Allen"
        },
        "subscriberId": "46796",
        "beneficiary": {
            "reference": "Patient/eLpjtce.j.HQohqaWuElZYg3",
            "display": "Mkk, Allen"
        },
        "relationship": {
            "coding": [
                {
                    "system": "urn:oid:1.2.840.114350.1.13.5325.1.7.10.678671.305",
                    "code": "01",
                    "display": "Self"
                },
                {
                    "system": "http://terminology.hl7.org/CodeSystem/subscriber-relationship",
                    "code": "self",
                    "display": "Self"
                }
            ],
            "text": "Self"
        },
        "period": {
            "start": "2026-01-24"
        },
        "payor": [
            {
                "reference": "Organization/eoWo8uqDKzZKeOGyT3arR4Q3",
                "identifier": {
                    "use": "official",
                    "system": "http://open.epic.com/FHIR/StructureDefinition/payer-id",
                    "value": "467961"
                },
                "display": "MKK PAS WW PAYER"
            }
        ],
        "class": [
            {
                "extension": [
                    {
                        "valueIdentifier": {
                            "use": "secondary",
                            "system": "urn:oid:1.2.840.114350.1.13.5325.1.7.2.698080",
                            "value": "467961"
                        },
                        "url": "http://open.epic.com/FHIR/StructureDefinition/extension/epic-id"
                    }
                ],
                "type": {
                    "coding": [
                        {
                            "system": "http://terminology.hl7.org/CodeSystem/coverage-class",
                            "code": "plan",
                            "display": "Plan"
                        }
                    ]
                },
                "value": "467961",
                "name": "MKK PAS WW PLAN"
            }
        ],
        "order": 1
    }
},
{
    "name": "referenced",
    "resource": {
```

```
            "resourceType": "Patient",
            "id": "eLpjtce.j.HQohqaWuElZYg3",
            "extension": [
                {
                    "valueCodeableConcept": {
                        "coding": [
                            {
                                "system": "urn:oid:1.2.840.114350.1.13.5325.1.7.10.698084.130.768080.39128",
                                "code": "male",
                                "display": "male"
                            }
                        ],
                        "text": "Male"
                    },
                    "url": "http://open.epic.com/FHIR/StructureDefinition/extension/legal-sex"
                },
                {
                    "valueCodeableConcept": {
                        "coding": [
                            {
                                "system": "urn:oid:1.2.840.114350.1.13.5325.1.7.10.698084.130.768080.35144",
                                "code": "male",
                                "display": "male"

                            }
                        ]
                    },
                    "url": "http://open.epic.com/FHIR/StructureDefinition/extension/sex-for-clinical-use"
                },
                {
                    "extension": [
                        {
                            "valueCoding": {
                                "system": "http://terminology.hl7.org/CodeSystem/v3-NullFlavor",
                                "code": "UNK",
                                "display": "Unknown"
                            },
                            "url": "ombCategory"
                        },
                        {
                            "valueString":******,
                            "url": "text"
                        }
                    ],
                    "url": "http://hl7.org/fhir/us/core/StructureDefinition/us-core-race"
                },
                {
                    "extension": [
                        {
                            "valueString":******,
                            "url": "text"
                        }
                    ],
                    "url": "http://hl7.org/fhir/us/core/StructureDefinition/us-core-ethnicity"
                },
                {
                    "valueCode": "248153007",
                    "url": "http://hl7.org/fhir/us/core/StructureDefinition/us-core-sex"
                },
                {
                    "valueCodeableConcept": {
                        "coding": [
                            {
                                "system": "http://loinc.org",
                                "code": "LA29518-0",
                                "display": "he/him/his/his/himself"
                            }
                        ]
                    },
                    "url": "http://open.epic.com/FHIR/StructureDefinition/extension/calculated-pronouns-to-use-for-
text"
                }
            ],
            "identifier": [
                {
                    "use": "usual",
                    "type": {
                        "text": "CEID"
                    },
                    "system": "urn:oid:1.2.840.114350.1.13.5325.1.7.3.688884.100",
                    "value": "YB0DRQX1DWTDLRQ"
                },
                {
                    "use": "usual",
                    "type": {
                        "text": "EPI"
                    },
                    "system": "urn:oid:1.2.840.114350.1.1",
                    "value": "887235"
                },
```

```
        {
            "use": "usual",
            "type": {
                "coding": [
                    {
                        "system": "http://hl7.org/fhir/us/carin-bb/CodeSystem/C4BBIdentifierType",
                        "code": "um"
                    }
                ],
                "text": "EXTERNAL"
            },
            "system": "urn:oid:1.2.840.114350.1.13.5325.1.7.2.698084",
            "value": "Z379105"
        },
        {
            "use": "usual",
            "type": {
                "text": "FHIR"
            },
            "system": "http://open.epic.com/FHIR/StructureDefinition/patient-dstu2-fhir-id",
            "value": "TJcMgvfNuJcR5gMTjOnTqm7E74c6w.Fl--TPbMs9LppsB"
        },
        {
            "use": "usual",
            "type": {
                "text": "FHIR STU3"
            },
            "system": "http://open.epic.com/FHIR/StructureDefinition/patient-fhir-id",
            "value": "eLpjtce.j.HQohqaWuElZYg3"
        },
        {
            "use": "usual",
            "type": {
                "text": "INTERNAL"
            },
            "system": "urn:oid:1.2.840.114350.1.13.5325.1.7.2.698084",
            "value": "   Z379105"
        },
        {
            "use": "usual",
            "type": {
                "text": "WPRINTERNAL"
            },
            "system": "urn:oid:1.2.840.114350.1.13.5325.1.7.2.878082",
            "value": "154261"
        },
        {
            "use": "usual",
            "type": {
                "coding": [
                    {
                        "system": "http://terminology.hl7.org/CodeSystem/v2-0203",
                        "code": "MB"
                    }
                ]
            },
            "system": "https://open.epic.com/FHIR/StructureDefinition/PayerMemberId",
            "value": "46796"
        },
        {
            "use": "usual",
            "system": "urn:oid:2.16.840.1.113883.4.1",
            "value": "120-12-0250"
        }
    ],
    "active": true,
    "name": [
        {
            "use": "official",
            "text": "Allen Mkk",
            "family": "Mkk",
            "given": [
                "Allen"
            ]
        },
        {
            "use": "usual",
            "text": "Allen Mkk",
            "family": "Mkk",
            "given": [
                "Allen"
            ]
        }
    ],
    "telecom": [
        {
            "system": "phone",
            "value": "+1 608-844-5476",
            "use": "home"
```

```
            }
        ],
        "gender": "male",
        "birthDate": "2019-12-01",
        "deceasedBoolean": false,
        "address": [
            {
                "use": "home",
                "text": "123 Main St\r\nMADISON WI 53719\r\nUnited States of America",
                "line": [
                    "123 Main St"
                ],
                "city": "MADISON",
                "district": "DANE",
                "state": "WI",
                "postalCode": "53719",
                "country": "USA",
                "period": {
                    "start": "2026-02-24"
                }
            }
        ],
        "generalPractitioner": [
            {
                "reference": "Practitioner/e0lRIY.4N3KwJun04yQ0TNg3",
                "type": "Practitioner",
                "display": "Mkk Doc"
            }
        ],
        "managingOrganization": {
            "reference": "Organization/e3.Mm8f5VDySoXn7Yd2M79A3",
            "display": "MC Shared Business"
        }
    }
},
{
    "name": "order",
    "resource": {
        "resourceType": "ServiceRequest",
        "id": "fXX3P3bEzsEoH2Yaa8Bm4RXnf2LjAqKz5CSFh6UBBs4Y4",
        "status": "active",
        "intent": "order",
        "code": {
            "coding": [
                {
                    "system": "http://www.ama-assn.org/go/cpt",
                    "code": "50540",
                    "display": "REVISION OF HORSESHOE KIDNEY"
                }
            ],
            "text": "REVISION OF HORSESHOE KIDNEY"
        },
        "quantityQuantity": {
            "value": 1
        },
        "subject": {
            "reference": "Patient/eLpjtce.j.HQohqaWuElZYg3",
            "display": "Mkk, Allen"
        },
        "encounter": {
            "identifier": {
                "use": "usual",
                "system": "urn:oid:1.2.840.114350.1.13.5325.1.7.3.698084.8",
                "value": "10006897395"
            },
            "display": "Appointment"
        },
        "occurrenceTiming": {
            "repeat": {
                "boundsPeriod": {
                    "start": "2026-03-24T05:00:00Z"
                }
            }
        },
        "requester": {
            "reference": "PractitionerRole/eZ2oBLU158WNEv-GYD0n4Kj0Z2GkTlpWaav88piefaHI3"
        },
        "performer": [
            {
                "reference": "PractitionerRole/eZ2oBLU158WNEv-GYD0n4Kj0Z2GkTlpWaav88piefaHI3"
            }
        ],
        "reasonCode": [
            {
                "coding": [
                    {
                        "system": "http://snomed.info/sct",
                        "code": "1255670000",
                        "display": "Finding of increased risk level (finding)"
```

```
                            },
                            {
                                "system": "http://hl7.org/fhir/sid/icd-10-cm",
                                "code": "Z91.89",
                                "display": "Other specified personal risk factors, not elsewhere classified"
                            }
                        ],
                        "text": "Other specified personal risk factors, not elsewhere classified"
                    }
                ],
                "insurance": [
                    {
                        "reference": "Coverage/eOC6c0z2Ies1te1ZW4ktIZwto-ymEqA6jqTGzgupccEpmp9F5VVHw1xclgcbl5yBU3",
                        "display": "MKK PAS WW PAYER/MKK PAS WW PLAN"
                    }
                ]
            }
        },
        {
            "name": "context",
            "valueString":******
        },
        {
            "name": "internal.epic.epic-emp-id",
            "valueString":******
        }
    ]
}
```

Sample response


```
{
  "resourceType": "Parameters",
  "parameter": [
    {
      "name": "PackageBundle",
      "resource": {
        "resourceType": "Bundle",
        "meta": {
          "profile": [
            "http://hl7.org/fhir/us/davinci-dtr/StructureDefinition/DTR-QPackageBundle"
          ]
        },
        "type": "collection",
        "entry": [
          {
            "fullUrl": "urn:uuid:d9ba6144-e744-4899-8cf1-3908d7c07dc7",
            "resource": {
              "resourceType": "Questionnaire",
              "id": "fnWm-NGpC.SjKn2BlCgME7Q4",
              "extension": [
                {
                  "valueCode": "random",
                  "url": "http://hl7.org/fhir/uv/sdc/StructureDefinition/sdc-questionnaire-entryMode"
                }
              ],
              "url": "https://epicdtrproxy.canonical/21e97f1f003848c9aecb0d11d3b5375e-1",
              "version": "5844791673",
              "title": "MKK Guideline",
              "status": "active",
              "subjectType": [
                "Patient"
              ],
              "effectivePeriod": {
                "start": "2026-03-05"
              },
              "item": [
                {
                  "extension": [
                    {
                      "valueBoolean": false,
                      "url": "http://hl7.org/fhir/StructureDefinition/questionnaire-hidden"
                    }
                  ],
                  "linkId": "urn:uuid:3bca2f64-2331-11f1-b0a4-0050568bf2db",
                  "prefix": "1",
                  "text": "Delegate DTR",
                  "type": "boolean",
                  "required": false,
                  "item": [
                    {
                      "extension": [
                        {
                          "valueBoolean": false,
                          "url": "http://hl7.org/fhir/StructureDefinition/questionnaire-hidden"
                        }
                      ],
                      "linkId": "urn:uuid:3bcaf5b8-2331-11f1-b0a4-0050568bf2db",
                      "prefix": "1.1",
```

```
                "text": "question 1",
                "type": "boolean",
                "required": false,
                "item": [
                  {
                    "extension": [
                      {
                        "valueBoolean": false,
                        "url": "http://hl7.org/fhir/StructureDefinition/questionnaire-hidden"
                      }
                    ],
                    "linkId": "urn:uuid:3bcb56b6-2331-11f1-b0a4-0050568bf2db",
                    "prefix": "1.1.1",
                    "text": "child question 1",
                    "type": "boolean",
                    "required": false
                  }
                ]
              },
              {
                "extension": [
                  {
                    "valueBoolean": false,
                    "url": "http://hl7.org/fhir/StructureDefinition/questionnaire-hidden"
                  }
                ],
                "linkId": "urn:uuid:3bcbae01-2331-11f1-b0a4-0050568bf2db",
                "prefix": "1.2",
                "text": "question 2",
                "type": "boolean",
                "required": false
              }
            ]
          }
        ]
      }
    },
    {
      "fullUrl": "urn:uuid:82a85c41-e39d-43ed-8b37-79271bb74e1e",
      "resource": {
        "resourceType": "QuestionnaireResponse",
        "id": "fLWMkfVYIyWsQRjpP7RpRlA4",
        "extension": [
          {
            "valueReference": {
              "reference": "ServiceRequest/fXX3P3bEzsEoH2Yaa8Bm4RXnf2LjAqKz5CSFh6UBBs4Y4"
            },
            "url": "http://hl7.org/fhir/us/davinci-dtr/StructureDefinition/qr-context"
          },
          {
            "valueReference": {
              "reference": "Coverage/eOC6c0z2Ies1te1ZW4ktIZwto-ymEqA6jqTGzgupccEpmp9F5VVHw1xclgcbl5yBU3"
            },
            "url": "http://hl7.org/fhir/us/davinci-dtr/StructureDefinition/qr-context"
          },
          {
            "valueCodeableConcept": {
              "coding": [
                {
                  "system": "http://hl7.org/fhir/us/davinci-crd/CodeSystem/temp",
                  "code": "withpa",
                  "display": "Include in prior authorization"
                }
              ]
            },
            "url": "http://hl7.org/fhir/us/davinci-dtr/StructureDefinition/intendedUse"
          }
        ],
        "questionnaire": "https://epicdtrproxy.canonical/21e97f1f003848c9aecb0d11d3b5375e-1|5844791673",
        "status": "in-progress",
        "subject": {
          "reference": "Patient/eLpjtce.j.HQohqaWuElZYg3"
        },
        "authored": "2026-03-24T16:21:41Z"
      }
    }
  ]
 }
},
{
  "name": "PackageBundle",
  "resource": {
    "resourceType": "Bundle",
    "meta": {
      "profile": [
        "http://hl7.org/fhir/us/davinci-dtr/StructureDefinition/DTR-QPackageBundle"
      ]
    },
    "type": "collection",
```

```
        "entry": [
          {
            "fullUrl": "urn:uuid:bfdafa50-1885-453f-b9af-4b87be035f86",
            "resource": {
              "resourceType": "Questionnaire",
              "id": "f4FB5rTytZt7v1SFPyHyf2g4",
              "extension": [
                {
                  "valueCode": "random",
                  "url": "http://hl7.org/fhir/uv/sdc/StructureDefinition/sdc-questionnaire-entryMode"
                }
              ],
              "url": "https://epicdtrproxy.canonical/bbf349be7f1a4764be77c929020379f9-1",
              "version": "5842869092",
              "title": "JZF Admin All",
              "status": "active",
              "subjectType": [
                "Patient"
              ],
              "effectivePeriod": {
                "start": "2016-02-24"
              },
              "item": [
                {
                  "extension": [
                    {
                      "valueBoolean": false,
                      "url": "http://hl7.org/fhir/StructureDefinition/questionnaire-hidden"
                    }
                  ],
                  "linkId": "urn:uuid:0d5126a9-11b5-11f1-b0a4-0050568bf2db",
                  "prefix": "1",
                  "text": "Question?",
                  "type": "boolean",
                  "required": false
                }
              ]
            }
          },
          {
            "fullUrl": "urn:uuid:78545e51-610d-4b64-b811-db6f9cb5ba53",
            "resource": {
              "resourceType": "QuestionnaireResponse",
              "id": "f8PDLFQ7IR4x9ZDqMPUoL4A4",
              "extension": [
                {
                  "valueReference": {
                    "reference": "ServiceRequest/fXX3P3bEzsEoH2Yaa8Bm4RXnf2LjAqKz5CSFh6UBBs4Y4"
                  },
                  "url": "http://hl7.org/fhir/us/davinci-dtr/StructureDefinition/qr-context"
                },
                {
                  "valueReference": {
                    "reference": "Coverage/eOC6c0z2Ies1te1ZW4ktIZwto-ymEqA6jqTGzgupccEpmp9F5VVHw1xclgcbl5yBU3"
                  },
                  "url": "http://hl7.org/fhir/us/davinci-dtr/StructureDefinition/qr-context"
                },
                {
                  "valueCodeableConcept": {
                    "coding": [
                      {
                        "system": "http://hl7.org/fhir/us/davinci-crd/CodeSystem/temp",
                        "code": "withpa",
                        "display": "Include in prior authorization"
                      }
                    ]
                  },
                  "url": "http://hl7.org/fhir/us/davinci-dtr/StructureDefinition/intendedUse"
                }
              ],
              "questionnaire": "https://epicdtrproxy.canonical/bbf349be7f1a4764be77c929020379f9-1|5842869092",
              "status": "in-progress",
              "subject": {
                "reference": "Patient/eLpjtce.j.HQohqaWuElZYg3"
              },
              "authored": "2026-03-24T16:21:42Z"
            }
          }
        ]
      }
    }
  ]
}
```


14.1.74 QuestionnaireResponse.Read (Outside Record) (R4)

File: site/apis/14-CMS-Incoming/1-R4/11473-QuestionnaireResponse-Read-Outside-Record-R4.html
Epic API ID | 11473

FHIR version | R4
Categories | CMS Incoming
API type | USCDI
A la carte | Industry-Standard Level 1 API
USCDI | Yes
Available in inpatient and other contexts | Yes
HTTP method | GET
URL template | /api/FHIR/R4/QuestionnaireResponse/{ID}
Supports OAuth 2.0 | True
Supported user types | Backend Systems and Non-OAuth 2.0, Clinicians or Administrative Users, Patients
Performs scope validation | False
Source | https://fhir.epic.com/Specifications?api=11473

Description

Use this API to retrieve an instance of a questionnaire response for a patient. A single QuestionnaireResponse (Outside Record) resource represents a filled-in instance of a questionnaire, that is, the collected answers to a structured form or assessment. It stores metadata (for example status, authored, subject, author, and a reference to the questionnaire) and a hierarchical item / answer structure that mirrors the questionnaire definition and supports nested groups and multiple answer types.

This API differs from other QuestionnaireResponse APIs because it returns data obtained as part of payer data exchange workflows rather than directly recorded during patient care. This data can come from payers or loaded from other FHIR servers. Because this data doesn't originate from the organization being queried, users of this API should be aware that the data might be unverified, incomplete, or duplicative.

This data is loaded from other FHIR servers and returned in the format the organization received it. Because of this, the documentation below is minimal. These resources can include any elements from the FHIR specification and can be distinguished from other resources by the presence of meta.tag set to

external-bulk-data

Request parameters

Name | Type | Optional | Array | Cardinality | Description
ID | token | Required | | | The QuestionnaireResponse FHIR ID.

Response elements

Name | Type | Optional | Array | Cardinality | Description
QuestionnaireResponse (R4) | Resource | | | | An instance of the R4 QuestionnaireResponse FHIR resource.
QuestionnaireResponse (R4).id | id | | | 1..1 | The unique FHIR ID representing the QuestionnaireResponse (Outside Record) resource.
QuestionnaireResponse (R4).meta | Meta | | | 1..1 | Metadata about the resource, including information about the origin or source of the data.
QuestionnaireResponse (R4).meta.tag | Coding | | Yes | 1..* | Set to external-bulk-data for resources originally loaded from another FHIR server. If this element is set to external-bulk-data, the resource content might vary and can include any elements allowed by the FHIR specification.
QuestionnaireResponse (R4).subject | Reference | | | 1..1 | Reference to a Patient resource for whom the questionnaire response is relevant.

Sample request

```
GET https://hostname/instance/api/FHIR/R4/QuestionnaireResponse/fX1IHiYB94Rv6qj3xWJOIX0gtU60pOzBFtoxs8ospHbY4
```

Sample response

```
{
  "resourceType": "QuestionnaireResponse",
  "id": "fX1IHiYB94Rv6qj3xWJOIX0gtU60pOzBFtoxs8ospHbY4",
  "meta": {
    "tag": [
      {
        "system": "https://open.epic.com/FHIR/bulk-data-source",
        "code": "external-bulk-data",
        "display": "External Bulk Data"
      }
    ]
  },
  ... <R4 QuestionnaireResponse Compliant Elements> ...
}
```

14.1.75 QuestionnaireResponse.Search (Outside Record) (R4)

File: site/apis/14-CMS-Incoming/1-R4/11474-QuestionnaireResponse-Search-Outside-Record-R4.html
Epic API ID | 11474
FHIR version | R4
Categories | CMS Incoming
API type | USCDI
A la carte | Industry-Standard Level 1 API
USCDI | Yes
Available in inpatient and other contexts | Yes

HTTP method | GET
URL template | /api/FHIR/R4/QuestionnaireResponse?encounter={encounter}&patient={patient}&subject={subject}&_count={_count}&_id={_id}&_include={_include}&_revinclude={_revinclude}
Supports OAuth 2.0 | True
Supported user types | Backend Systems and Non-OAuth 2.0, Clinicians or Administrative Users, Patients
Performs scope validation | False
Source | https://fhir.epic.com/Specifications?api=11474

Description

Use this API to search for questionnaire responses for a patient. A single QuestionnaireResponse (Outside Record) resource represents a filled-in instance of a questionnaire, that is, the collected answers to a structured form or assessment. It stores metadata (for example status, authored, subject, author, and a reference to the questionnaire) and a hierarchical item / answer structure that mirrors the questionnaire definition and supports nested groups and multiple answer types.

This API differs from other QuestionnaireResponse APIs because it returns data obtained as part of payer data exchange workflows rather than directly recorded during patient care. This data can come from payers or loaded from other FHIR servers. Because this data doesn't originate from the organization being queried, users of this API should be aware that the data might be unverified, incomplete, or duplicative.

This data is loaded from other FHIR servers and returned in the format the organization received it. Because of this, the documentation below is minimal. These resources can include any elements from the FHIR specification and can be distinguished from other resources by the presence of meta.tag set to

external-bulk-data

Request parameters

Name | Type | Optional | Array | Cardinality | Description
_count | number | Optional | Yes | | Number of results per page.
_id | token | Optional | Yes | | FHIR resource IDs for the desired resources. Can be used in combination with _count, _include, and _revInclude. All others will be ignored.
_include | string | Optional | Yes | | Used to indicate which referenced resources to include in the search bundle.
_revinclude | string | Optional | Yes | | Used to include Provenance or AuditEvent resources that refer to search results, when available.
patient | reference | Conditional | Yes | | Reference to a Patient resource whose questionnaire response was documented. Either patient or subject must be populated. If patient and subject are both populated, they must be identical.
subject | reference | Conditional | Yes | | Reference to a Patient resource whose questionnaire response was documented. Either patient or subject must be populated. If patient and subject are both populated, they must be identical.

Response elements

Name | Type | Optional | Array | Cardinality | Description
QuestionnaireResponse (R4) | Resource | | | | An instance of the R4 QuestionnaireResponse FHIR resource.
QuestionnaireResponse (R4).id | id | | | 1..1 | The unique FHIR ID representing the QuestionnaireResponse (Outside Record) resource.
QuestionnaireResponse (R4).meta | Meta | | | 1..1 | Metadata about the resource, including information about the origin or source of the data.
QuestionnaireResponse (R4).meta.tag | Coding | | Yes | 1..* | Set to external-bulk-data for resources originally loaded from another FHIR server. If this element is set to external-bulk-data, the resource content might vary and can include any elements allowed by the FHIR specification.
QuestionnaireResponse (R4).subject | Reference | | | 1..1 | Reference to a Patient resource for whom the questionnaire response is relevant.

Sample request

```
GET https://hostname/instance/api/FHIR/R4/QuestionnaireResponse?patient=eKpwAQhoV6s9woTj1Y8Gziw3
```

Sample response


```
{
  "resourceType": "Bundle",
  "type": "searchset",
  "total": 1,
  "link": [
    {
      "relation": "self",
      "url": "https://hostname/instance/api/FHIR/R4/QuestionnaireResponse?patient=eKpwAQhoV6s9woTj1Y8Gziw3"
    }
  ],
  "entry": [
    {
      "link": [
        {
          "relation": "self",
          "url":
    "https://hostname/instance/api/FHIR/R4/QuestionnaireResponse/fX1IHiYB94Rv6qj3xWJOIX0gtU60pOzBFtoxs8ospHbY4"
        }
      ],
      "fullUrl":
    "https://hostname/instance/api/FHIR/R4/QuestionnaireResponse/fX1IHiYB94Rv6qj3xWJOIX0gtU60pOzBFtoxs8ospHbY4",
      "resource": {
        "resourceType": "QuestionnaireResponse",
        "id": "fX1IHiYB94Rv6qj3xWJOIX0gtU60pOzBFtoxs8ospHbY4",
        "meta": {
```

```
          "tag": [
            {
              "system": "https://open.epic.com/FHIR/bulk-data-source",
              "code": "external-bulk-data",
              "display": "External Bulk Data"
            }
          ]
        },
        ... <R4 QuestionnaireResponse Compliant Elements> ...
      }
    }
  ]
}
```

14.1.76 RelatedPerson.Read (Outside Record) (R4)

File: site/apis/14-CMS-Incoming/1-R4/11438-RelatedPerson-Read-Outside-Record-R4.html
Epic API ID | 11438
FHIR version | R4
Categories | CMS Incoming
API type | USCDI
A la carte | Industry-Standard Level 1 API
USCDI | Yes
Available in inpatient and other contexts | Yes
HTTP method | GET
URL template | /api/FHIR/R4/RelatedPerson/{ID}
Supports OAuth 2.0 | True
Supported user types | Backend Systems and Non-OAuth 2.0, Clinicians or Administrative Users, Patients
Performs scope validation | False
Source | https://fhir.epic.com/Specifications?api=11438

Description

Use this API to retrieve details about persons with a relationship to a patient. A single RelatedPerson (Outside Record) resource represents a single individual with a relationship to the patient, such as an emergency contact or parent.

This API differs from other RelatedPerson APIs because it returns data obtained as part of payer data exchange workflows rather than directly recorded during patient care. This data can come from payers or loaded from other FHIR servers. Because this data doesn't originate from the organization being queried, users of this API should be aware that the data might be unverified, incomplete, or duplicative.

This data is loaded from other FHIR servers and returned in the format the organization received it. Because of this, the documentation below is minimal. These resources can include any elements from the FHIR specification and can be distinguished from other resources by the presence of meta.tag set to

external-bulk-data

Request parameters

Name | Type | Optional | Array | Cardinality | Description
ID | token | Required | | | The RelatedPerson FHIR ID.

Response elements

Name | Type | Optional | Array | Cardinality | Description
RelatedPerson (R4) | RelatedPerson
RelatedPerson (R4).id | id | | | 1..1 | The unique FHIR ID representing the RelatedPerson (Outside Record) resource.
RelatedPerson (R4).meta | Meta | | | 1..1 | Metadata about the resource, including information about the origin or source of the data.
RelatedPerson (R4).meta.tag | Coding | | Yes | 1..* | Set to external-bulk-data for resources originally loaded from another FHIR server. If this element is set to external-bulk-data, the resource content might vary and can include any elements allowed by the FHIR specification.
RelatedPerson (R4).patient | Reference | | | 1..1 | Reference to a Patient resource for whom the related person is relevant.

Sample request

```
GET https://hostname/instance/api/FHIR/R4/RelatedPerson/fQ74PSwBEurp4iHNp-6BCAJ23J9A.cAr4QRifp3ENvr72X5XBbVYYxuuxY23VRA-
    AH0R9OkKOpdioQV7XDnfk9Q4
```

Sample response

```
{
  "resourceType": "RelatedPerson",
  "id": "fQ74PSwBEurp4iHNp-6BCAJ23J9A.cAr4QRifp3ENvr72X5XBbVYYxuuxY23VRA-AH0R9OkKOpdioQV7XDnfk9Q4",
  "meta": {
    "tag": [
      {
        "system": "https://open.epic.com/FHIR/bulk-data-source",
        "code": "external-bulk-data",
        "display": "External Bulk Data"
      }
    ]
```

```
  },
    ... <r4 relatedperson="" compliant="" elements=""> ...
}</r4>
```

14.1.77 RelatedPerson.Search (Outside Record) (R4)

File: site/apis/14-CMS-Incoming/1-R4/11440-RelatedPerson-Search-Outside-Record-R4.html
Epic API ID | 11440
FHIR version | R4
Categories | CMS Incoming
API type | USCDI
A la carte | Industry-Standard Level 1 API
USCDI | Yes
Available in inpatient and other contexts | Yes
HTTP method | GET
URL template | /api/FHIR/R4/RelatedPerson?patient={patient}&_count={_count}&_id={_id}&_include={_include}&_revinclude={_revinclude}
Supports OAuth 2.0 | True
Supported user types | Backend Systems and Non-OAuth 2.0, Clinicians or Administrative Users, Patients
Performs scope validation | False
Source | https://fhir.epic.com/Specifications?api=11440

Description

Use this API to search for RelatedPerson resources. A single RelatedPerson (Outside Record) resource represents a single individual with a relationship to the patient, such as an emergency contact or parent.

This API differs from other RelatedPerson APIs because it returns data obtained as part of payer data exchange workflows rather than directly recorded during patient care. This data can come from payers or loaded from other FHIR servers. Because this data doesn't originate from the organization being queried, users of this API should be aware that the data might be unverified, incomplete, or duplicative.

This data is loaded from other FHIR servers and returned in the format the organization received it. Because of this, the documentation below is minimal. These resources can include any elements from the FHIR specification and can be distinguished from other resources by the presence of meta.tag set to

external-bulk-data

Request parameters

Name | Type | Optional | Array | Cardinality | Description
_count | number | Optional | Yes | | Number of results per page.
_id | token | Optional | Yes | | FHIR resource IDs for the desired resources. Can be used in combination with _count, _include, and _revInclude. All others will be ignored.
_include | string | Optional | Yes | | Used to indicate which referenced resources to include in the search bundle.
_revinclude | string | Optional | Yes | | Used to include Provenance or AuditEvent resources that refer to search results, when available.
patient | reference | Optional | Yes | | Reference to a Patient resource.

Response elements

Name | Type | Optional | Array | Cardinality | Description
RelatedPerson (R4) | RelatedPerson
RelatedPerson (R4).id | id | | | 1..1 | The unique FHIR ID representing the RelatedPerson (Outside Record) resource.
RelatedPerson (R4).meta | Meta | | | 1..1 | Metadata about the resource, including information about the origin or source of the data.
RelatedPerson (R4).meta.tag | Coding | | Yes | 1..* | Set to external-bulk-data for resources originally loaded from another FHIR server. If this element is set to external-bulk-data, the resource content might vary and can include any elements allowed by the FHIR specification.
RelatedPerson (R4).patient | Reference | | | 1..1 | Reference to a Patient resource for whom the related person is relevant.

Sample request

```
GET https://hostname/instance/api/FHIR/R4/RelatedPerson?patient=eKpwAQhoV6s9woTj1Y8Gziw3
```

Sample response

```
{
  "resourceType": "Bundle",
  "type": "searchset",
  "total": 1,
  "link": [
    {
      "relation": "self",
      "url": "https://hostname/instance/api/FHIR/R4/RelatedPerson?patient=eKpwAQhoV6s9woTj1Y8Gziw3"
    }
  ],
  "entry": [
    {
      "link": [
        {
          "relation": "self",
          "url":
```

```
    "https://hostname/instance/api/FHIR/R4/RelatedPerson/fQ74PSwBEurp4iHNp-
    6BCAJ23J9A.cAr4QRifp3ENvr72X5XBbVYYxuuxY23VRA-AH0R9OkKOpdioQV7XDnfk9Q4"
        }
      ],
      "fullUrl":
    "https://hostname/instance/api/FHIR/R4/RelatedPerson/fQ74PSwBEurp4iHNp-
    6BCAJ23J9A.cAr4QRifp3ENvr72X5XBbVYYxuuxY23VRA-AH0R9OkKOpdioQV7XDnfk9Q4",
      "resource": {
        "resourceType": "RelatedPerson",
        "id": "fQ74PSwBEurp4iHNp-6BCAJ23J9A.cAr4QRifp3ENvr72X5XBbVYYxuuxY23VRA-AH0R9OkKOpdioQV7XDnfk9Q4",
        "meta": {
          "tag": [
            {
              "system": "https://open.epic.com/FHIR/bulk-data-source",
              "code": "external-bulk-data",
              "display": "External Bulk Data"
            }
          ]
        },
      ... <r4 relatedperson="" compliant="" elements=""> ...
      "search": {
        "mode": "match"
      }
    }
  ]
}</r4>
```


14.1.78 ServiceRequest.Read (Outside Record) (R4)

File: site/apis/14-CMS-Incoming/1-R4/11475-ServiceRequest-Read-Outside-Record-R4.html
Epic API ID | 11475
FHIR version | R4
Categories | CMS Incoming
API type | USCDI
A la carte | Industry-Standard Level 1 API
USCDI | Yes
Available in inpatient and other contexts | Yes
HTTP method | GET
URL template | /api/FHIR/R4/ServiceRequest/{ID}
Supports OAuth 2.0 | True
Supported user types | Backend Systems and Non-OAuth 2.0, Clinicians or Administrative Users, Patients
Performs scope validation | False
Source | https://fhir.epic.com/Specifications?api=11475

Description

Use this API to retrieve details about service requests or referrals for a patient. A single ServiceRequest (Outside Record) resource represents a single request for a service, or a service available to a patient.

This API differs from other ServiceRequest APIs because it returns data obtained as part of payer data exchange workflows rather than directly recorded during patient care. This data can come from payers or loaded from other FHIR servers. Because this data doesn't originate from the organization being queried, users of this API should be aware that the data might be unverified, incomplete, or duplicative.

This data is loaded from other FHIR servers and returned in the format the organization received it. Because of this, the documentation below is minimal. These resources can include any elements from the FHIR specification and can be distinguished from other resources by the presence of meta.tag set to

external-bulk-data

Request parameters

Name | Type | Optional | Array | Cardinality | Description
ID | String | Required | | | The unique FHIR ID representing the ServiceRequest (Outside Record) resource.

Response elements

Name | Type | Optional | Array | Cardinality | Description
ServiceRequest (R4) | Resource | | | | An instance of the R4 ServiceRequest resource.
ServiceRequest (R4).id | id | | | 1..1 | The unique FHIR ID representing the ServiceRequest (Outside Record) resource.
ServiceRequest (R4).meta | Meta | | | 1..1 | Metadata about the resource, including information about the origin or source of the data.
ServiceRequest (R4).meta.tag | Coding | | Yes | 1..* | Set to external-bulk-data for resources originally loaded from another FHIR server. If this element is set to external-bulk-data, the resource content might vary and can include any elements allowed by the FHIR specification.
ServiceRequest (R4).subject | Reference | | | 1..1 | Reference to a Patient resource for whom the service request is relevant.

Sample request

```
GET https://hostname/instance/api/FHIR/R4/ServiceRequest/foF.bZF9r7MoQo5YsuQRyD68a7CFPlyD936iwtXqPaPU4
```

Sample response

```
{
  "resourceType": "ServiceRequest",
  "id": "foF.bZF9r7MoQo5YsuQRyD68a7CFPlyD936iwtXqPaPU4",
  "meta": {
    "tag": [
      {
        "system": "https://open.epic.com/FHIR/bulk-data-source",
        "code": "external-bulk-data",
        "display": "External Bulk Data"
      }
    ]
  },
  ... <R4 ServiceRequest Compliant Elements> ...
}
```

14.1.79 ServiceRequest.Read (Prior Auth) (R4)

File: site/apis/14-CMS-Incoming/1-R4/11265-ServiceRequest-Read-Prior-Auth-R4.html
Epic API ID | 11265
FHIR version | R4
Categories | CMS Incoming
API type | Industry-Standard
USCDI | No
Available in inpatient and other contexts | Yes
HTTP method | GET
URL template | /api/FHIR/R4/ServiceRequest/{ID}
Supports OAuth 2.0 | True
Supported user types | Backend Systems and Non-OAuth 2.0, Clinicians or Administrative Users, Patients
Performs scope validation | False
Source | https://fhir.epic.com/Specifications?api=11265

Description

ServiceRequest (Prior Auth) is used during CDS hooks workflows which trigger Coverage Requirements Discovery (CRD). The ServiceRequest (Prior Auth) resource can only be used as a prefetched resource in the CDS Hooks request.

14.1.80 ServiceRequest.Search (Outside Record) (R4)

File: site/apis/14-CMS-Incoming/1-R4/11476-ServiceRequest-Search-Outside-Record-R4.html
Epic API ID | 11476
FHIR version | R4
Categories | CMS Incoming
API type | USCDI
A la carte | Industry-Standard Level 1 API
USCDI | Yes
Available in inpatient and other contexts | Yes
HTTP method | GET
URL template | /api/FHIR/R4/ServiceRequest?authored={authored}&category={category}&code={code}&encounter={encounter}&identifier={identifier}&onlyscannable={onlyscannable}&patient={patient}&requester={requester}&status={status}&subject={subject}&_count={_count}&_id={_id}&_include={_include}&_revinclude={_revinclude}
Supports OAuth 2.0 | True
Supported user types | Backend Systems and Non-OAuth 2.0, Clinicians or Administrative Users, Patients
Performs scope validation | False
Source | https://fhir.epic.com/Specifications?api=11476

Description

Use this API to search for ServiceRequest resources. A single ServiceRequest (Outside Record) resource represents a single request for a service, or a service available to a patient.

This API differs from other ServiceRequest APIs because it returns data obtained as part of payer data exchange workflows rather than directly recorded during patient care. This data can come from payers or loaded from other FHIR servers. Because this data doesn't originate from the organization being queried, users of this API should be aware that the data might be unverified, incomplete, or duplicative.

This data is loaded from other FHIR servers and returned in the format the organization received it. Because of this, the documentation below is minimal. These resources can include any elements from the FHIR specification and can be distinguished from other resources by the presence of meta.tag set to

external-bulk-data

Request parameters

Name | Type | Optional | Array | Cardinality | Description
_count | String | Optional | Yes | | Number of results per page.

_id | String | Optional | Yes | | FHIR resource IDs for the desired resources. Can be used in combination with _count, _include, and _revInclude. All others will be ignored.
_include | String | Optional | Yes | | Used to indicate which referenced resources to include in the search bundle.
_revinclude | String | Optional | Yes | | Used to include Provenance or AuditEvent resources that refer to search results, when available.
patient | String | Required | Yes | | Reference to a Patient resource.

Response elements

Name | Type | Optional | Array | Cardinality | Description
ServiceRequest (R4) | Resource | | | | An instance of the R4 ServiceRequest resource.
ServiceRequest (R4).id | id | | | 1..1 | The unique FHIR ID representing the ServiceRequest (Outside Record) resource.
ServiceRequest (R4).meta | Meta | | | 1..1 | Metadata about the resource, including information about the origin or source of the data.
ServiceRequest (R4).meta.tag | Coding | | Yes | 1..* | Set to external-bulk-data for resources originally loaded from another FHIR server. If this element is set to external-bulk-data, the resource content might vary and can include any elements allowed by the FHIR specification.
ServiceRequest (R4).subject | Reference | | | 1..1 | Reference to a Patient resource for whom the service request is relevant.

Sample request

```
GET https://hostname/instance/api/FHIR/R4/ServiceRequest?patient=eKpwAQhoV6s9woTj1Y8Gziw3
```

Sample response

```
{
  "resourceType": "Bundle",
  "type": "searchset",
  "total": 1,
  "link": [
    {
      "relation": "self",
      "url": "https://hostname/instance/api/FHIR/R4/ServiceRequest?patient=eKpwAQhoV6s9woTj1Y8Gziw3"
    }
  ],
  "entry": [
    {
      "link": [
        {
          "relation": "self",
          "url": "https://hostname/instance/api/FHIR/R4/ServiceRequest/foF.bZF9r7MoQo5YsuQRyD68a7CFPlyD936iwtXqPaPU4"
        }
      ],
      "fullUrl": "https://hostname/instance/api/FHIR/R4/ServiceRequest/foF.bZF9r7MoQo5YsuQRyD68a7CFPlyD936iwtXqPaPU4",
      "resource": {
        "resourceType": "ServiceRequest",
        "id": "foF.bZF9r7MoQo5YsuQRyD68a7CFPlyD936iwtXqPaPU4",
        "meta": {
          "tag": [
            {
              "system": "https://open.epic.com/FHIR/bulk-data-source",
              "code": "external-bulk-data",
              "display": "External Bulk Data"
            }
          ]
        },
      ... <R4 ServiceRequest Compliant Elements> ...
      },
      "search": {
        "mode": "match"
      }
    }
  ]
}
```

14.1.81 ServiceRequest.Search (Prior Auth) (R4)

File: site/apis/14-CMS-Incoming/1-R4/11266-ServiceRequest-Search-Prior-Auth-R4.html
Epic API ID | 11266
FHIR version | R4
Categories | CMS Incoming
API type | Industry-Standard
USCDI | No
Available in inpatient and other contexts | Yes
HTTP method | GET
URL template | /api/FHIR/R4/ServiceRequest?authored={authored}&category={category}&code={code}&encounter={encounter}&identifier={identifier}&onlyscannable={onlyscannable}&patient={patient}&requester={requester}&status={status}&subject={subject}&_count={_count}&_id={_id}&_include={_include}&_revinclude={_revinclude}
Supports OAuth 2.0 | True
Supported user types | Backend Systems and Non-OAuth 2.0, Clinicians or Administrative Users, Patients
Performs scope validation | False
Source | https://fhir.epic.com/Specifications?api=11266

Description

ServiceRequest (Prior Auth) is used during CDS hooks workflows which trigger Coverage Requirements Discovery (CRD). The ServiceRequest (Prior Auth) resource can only be used as a prefetched resource in the CDS Hooks request.

14.1.82 ServiceRequest.Update (Prior Auth) (R4)

File: site/apis/14-CMS-Incoming/1-R4/11267-ServiceRequest-Update-Prior-Auth-R4.html
Epic API ID | 11267
FHIR version | R4
Categories | CMS Incoming
API type | Industry-Standard
USCDI | No
Available in inpatient and other contexts | Yes
HTTP method | PUT
URL template | /api/FHIR/R4/ServiceRequest/{ID}`ServiceRequest***
Supports OAuth 2.0 | True
Supported user types | Backend Systems and Non-OAuth 2.0, Clinicians or Administrative Users, Patients
Performs scope validation | False
Source | https://fhir.epic.com/Specifications?api=11267

Description

Request

The HL7 FHIR Da Vinci Coverage Requirements Discovery (CRD) STU 2.1 (https://hl7.org/fhir/us/davinci-crd/STU2.1/) functionality is intended to allow health systems to query a health plan to determine whether services or medications require prior authorizations and if so, whether there are any additional documentation requirements or specific guidance regarding coverage.

CRD requests can only be initiated using the CDS Hooks framework (see https://fhir.epic.com/Documentation?docId=cds-hooks for details on Epic's support).

Epic supports two hooks for the purposes of triggering CRD:

* The "order-sign" CDS Hook (https://cds-hooks.hl7.org/hooks/order-sign/STU1/order-sign/) that occurs when an order is signed. CRD requests triggered by this hook contain a "draftOrders" bundle of ServiceRequest or MedicationRequest resources.

* The "appointment-book" CDS Hook (https://cds-hooks.hl7.org/hooks/appointment-book/STU1/appointment-book/) that occurs when an appointment is scheduled. CRD Requests triggered by this hook contain an "appointments" bundle of Appointment resources.

To improve performance, resources are be bundled directly into each CRD request instead of being retrieved through additional FHIR calls. This is done by configuring CDS Hooks prefetch templates for each type of hook. (See https://cds-hooks.hl7.org/STU2/#providing-fhir-resources-to-a-cds-service). Each prefetch template adds a resource to the request message under the "prefetch" element.

The extension element of a CRD request message includes at least one metadata field. "Extension:davinci-crd.configuration.coverage-info", when set to true, indicates that the receiver should respond to the request with a response type of "coverage-info" and should indicate whether the requested service is a covered benefit and whether prior authorization is required.

Response

Epic Health Systems expect CRD response messages to contain an empty "cards" array and a "systemActions" array within which the payer shall share whether the requested services and medications are covered and whether they require prior authorization.

For each service or medication for which a decision has been made, the systemActions element shall contain a slice with a type of "update" and a corresponding ServiceRequest or MedicationRequest resource, which should contain a coverage-information extension (https://hl7.org/fhir/us/davinci-crd/STU2.1/StructureDefinition-ext-coverage-information.html).

Please note that modifications to the ServiceRequest or MedicationRequest outside of the coverage-information extension will be ignored or could cause the message to be discarded.

14.1.83 Specimen.Read (Outside Record) (R4)

File: site/apis/14-CMS-Incoming/1-R4/11364-Specimen-Read-Outside-Record-R4.html
Epic API ID | 11364
FHIR version | R4
Categories | CMS Incoming
API type | USCDI
A la carte | Industry-Standard Level 1 API
USCDI | Yes
Available in inpatient and other contexts | Yes
HTTP method | GET

URL template | /api/FHIR/R4/Specimen/{ID}
Supports OAuth 2.0 | True
Supported user types | Backend Systems and Non-OAuth 2.0, Clinicians or Administrative Users, Patients
Performs scope validation | False
Source | https://fhir.epic.com/Specifications?api=11364

Description

Use this API to retrieve a specific instance of a specimen associated with a patient.

This FHIR resource represents substances being sampled or tested (for example, nasopharyngeal swab, whole blood, serum, urine, or wound swab) associated with a patient.

The data returned by this API includes information about specimens used in diagnostic testing. Specimens can be defined in Epic or on orders from outside Epic directly, as is the case for specimens recorded in a third-party lab system.

This API differs from

Specimen.Read (Patient Chart) (R4)

because it returns data that was obtained as part of payer data exchange workflows rather than directly recorded during patient care. This data can come from payers, providers, or loaded from other FHIR servers. Because this data doesn't originate from the organization being queried, users of this API should be aware that the data might be unverified, incomplete, or duplicative.

Data from outside payer and provider systems is saved to an organization's database and returned in a standard format, documented below. Data loaded from other FHIR servers is returned in the format the organization received it. Because of this, the documentation below does not apply to these loaded resources. These resources can include any elements from the FHIR specification and can be distinguished from other resources by the presence of meta.tag set to "external-bulk-data".

Request parameters

Name | Type | Optional | Array | Cardinality | Description
ID | token | Required | | | The Specimen FHIR ID

Response elements

Name | Type | Optional | Array | Cardinality | Description
Specimen (R4) | Specimen | | | | A single Specimen resource.
Specimen (R4).id | id | | | 1..1 | The Specimen FHIR ID.
Specimen (R4).meta | Meta | | | | Metadata about the resource, including information about the origin or source of the data.
Specimen (R4).meta.tag | Coding | | Yes | | Set to external-bulk-data for resources originally loaded from another FHIR server. If this element is set to external-bulk-data, all other element-level documentation does not apply to the resource. The resource content might vary and can include any elements allowed by the FHIR specification.
Specimen (R4).subject | Reference | | | 1..1 | The patient the specimen was collected from. This returns a reference to the Patient resource.
Specimen (R4).type | CodeableConcept | | | 1..1 | Kind of material that forms the specimen.

Sample request

```
GET https://hostname/instance/api/FHIR/R4/Specimen/ftZtos0x-nu3-uaXGcHEZCZ2N6yp6sa6m3.k5VbeH9sQ4
```

Sample response


```
{
  "resourceType": "Specimen",
  "id": "ftZtos0x-nu3-uaXGcHEZCZ2N6yp6sa6m3.k5VbeH9sQ4 ",
  "type": {
    "coding": [
      {
        "system": "http://snomed.info/sct",
        "code": "420135007",
        "display": "Whole blood"
      },
      {
        "system": "urn:oid:1.2.840.114350.1.13.51893.1.7.4.798268.300",
        "code": "70",
        "display": "Whole blood"
      }
    ],
    "text": "Whole blood"
  },
  "subject": {
    "reference": "Patient/eabcdecd1hijklmnop88883",
    "display": "FHIR, Test Patient"
  }
}
```


Change log

Epic Version | Description | Type
February 2026 | The Outside Record FHIR APIs now validate member coverage and return only resources relevant to the member's coverage enrollment. Previously they returned resources unrelated to the member's coverage. | Breaking Change

November 2025 | The Outside Record FHIR APIs are no longer enabled in the November 2025 version. Requests to these APIs do not return data. | Breaking Change

14.1.84 Specimen.Search (Outside Record) (R4)

File: site/apis/14-CMS-Incoming/1-R4/11366-Specimen-Search-Outside-Record-R4.html
Epic API ID | 11366
FHIR version | R4
Categories | CMS Incoming
API type | USCDI
A la carte | Industry-Standard Level 1 API
USCDI | Yes
Available in inpatient and other contexts | Yes
HTTP method | GET
URL template | /api/FHIR/R4/Specimen?_count={_count}&_id={_id}&_include={_include}&_revinclude={_revinclude}
Supports OAuth 2.0 | True
Supported user types | Backend Systems and Non-OAuth 2.0, Clinicians or Administrative Users, Patients
Performs scope validation | False
Source | https://fhir.epic.com/Specifications?api=11366

Description

Use this API to search for specific instances of specimens associated with patients.

This FHIR resource represents substances being sampled or tested (for example, nasopharyngeal swab, whole blood, serum, urine, or wound swab) associated with a patient.

The data returned by this API includes information about specimens used in diagnostic testing. Specimens can be defined in Epic or on orders from outside Epic directly, as is the case for specimens recorded in a third-party lab system.

This API differs from

Specimen.Search (Patient Chart) (R4)

because it returns data that was obtained as part of payer data exchange workflows rather than directly recorded during patient care. This data can come from payers, providers, or loaded from other FHIR servers. Because this data doesn't originate from the organization being queried, users of this API should be aware that the data might be unverified, incomplete, or duplicative.

Data from outside payer and provider systems is saved to an organization's database and returned in a standard format, documented below. Data loaded from other FHIR servers is returned in the format the organization received it. Because of this, the documentation below does not apply to these loaded resources. These resources can include any elements from the FHIR specification and can be distinguished from other resources by the presence of meta.tag set to "external-bulk-data".

Request parameters

Name | Type | Optional | Array | Cardinality | Description
_count | number | Optional | Yes | | Number of results per page.
_id | token | Optional | Yes | | FHIR resource IDs for the desired resources. Can be used in combination with _count, _include, and _revInclude. All other search parameters are ignored.
_include | string | Optional | Yes | | Used to indicate which referenced resources to include in the search bundle.
_revinclude | string | Optional | Yes | | Used to include Provenance or AuditEvent resources that refer to search results, when available.

Response elements

Name | Type | Optional | Array | Cardinality | Description
Specimen (R4) | Specimen | | | | A single Specimen resource.
Specimen (R4).id | id | | | 1..1 | The Specimen FHIR ID.
Specimen (R4).meta | Meta | | | | Metadata about the resource, including information about the origin or source of the data.
Specimen (R4).meta.tag | Coding | | Yes | | Set to external-bulk-data for resources originally loaded from another FHIR server. If this element is set to external-bulk-data, all other element-level documentation does not apply to the resource. The resource content might vary and can include any elements allowed by the FHIR specification.
Specimen (R4).subject | Reference | | | 1..1 | The patient the specimen was collected from. This returns a reference to the Patient resource.
Specimen (R4).type | CodeableConcept | | | 1..1 | Kind of material that forms the specimen.

Sample request

```
GET https://hostname/instance/api/FHIR/R4/Specimen?id=ftZtos0x-nu3-uaXGcHEZCZ2N6yp6sa6m3.k5VbeH9sQ4
```

Sample response


```
{
  "resourceType": "Bundle",
  "type": "searchset",
  "total": 1,
  "link": [
    {
      "relation": "self",
```

```
      "url": "https://hostname/instance/api/FHIR/R4/Specimen?id=ftZtos0x-nu3-uaXGcHEZCZ2N6yp6sa6m3.k5VbeH9sQ4"
    }
  ],
  "entry": [
    {
      "link": [
        {
          "relation": "self",
          "url": "https://hostname/instance/api/FHIR/R4/Specimen/ftZtos0x-nu3-uaXGcHEZCZ2N6yp6sa6m3.k5VbeH9sQ4"
        }
      ],
      "fullUrl": "https://hostname/instance/api/FHIR/R4/Specimen/ftZtos0x-nu3-uaXGcHEZCZ2N6yp6sa6m3.k5VbeH9sQ4",
      "resource": {
        "resourceType": "Specimen",
        "id": "ftZtos0x-nu3-uaXGcHEZCZ2N6yp6sa6m3.k5VbeH9sQ4 ",
        "type": {
          "coding": [
            {
              "system": "http://snomed.info/sct",
              "code": "420135007",
              "display": "Whole blood"
            },
            {
              "system": "urn:oid:1.2.840.114350.1.13.51893.1.7.4.798268.300",
              "code": "70",
              "display": "Whole blood"
            }
          ],
          "text": "Whole blood"
        },
        "subject": {
          "reference": "Patient/eabcdecd1hijklmnop88883",
          "display": "FHIR, Test Patient"
        }
      },
      "search": {
        "mode": "match"
      }
    }
  ]
}
```


Change log

Epic Version	Description	Type
February 2026	The Outside Record FHIR APIs now validate member coverage and return only resources relevant to the member's coverage enrollment. Previously they returned resources unrelated to the member's coverage.	Breaking Change
November 2025	The Outside Record FHIR APIs are no longer enabled in the November 2025 version. Requests to these APIs do not return data.	Breaking Change

14.1.85 ValueSet.$expand (DTR Payer Guidelines) (R4)

File: site/apis/14-CMS-Incoming/1-R4/11412-ValueSet-expand-DTR-Payer-Guidelines-R4.html	
Epic API ID	11412
FHIR version	R4
Categories	CMS Incoming
API type	Industry-Standard
USCDI	No
URL template	/api/FHIR
Supports OAuth 2.0	True
Supported user types	Backend Systems and Non-OAuth 2.0
Performs scope validation	False
Source	https://fhir.epic.com/Specifications?api=11412

Description

The ValueSet resource represents a subset of the codes in a code system that is supported by a given server. The DTR (Documentation Templates and Rules) $expand operation of the ValueSet resource can be used to dynamically expand value sets referenced in DTR questionnaires, providing a simple collection of codes suitable for use for data entry or validation within documentation requirement workflows. It is important that this is the endpoint used to fetch ValueSets from references that come through during CRD/DTR/PAS related workflows.

The DTR $expand operation response represents a single ValueSet resource, or an OperationOutcome with an error message.

DTR value set expansion only supports querying the ValueSet.$expand operation at the resource type level.

Request parameters

Name	Type	Optional	Array	Cardinality	Description
url	uri	Required	Yes		The canonical identifier for a value set, represented as a URI (globally unique).

Response elements

Name | Type | Optional | Array | Cardinality | Description
ValueSet (R4) | ValueSet | Conditional | | 0..* | Optional terminology artifacts used by Questionnaire items for answer lists. Might be included depending on additional system setup.
ValueSet (R4).expansion | BackboneElement | | | 0..1 | ValueSet expansion details.
ValueSet (R4).expansion.contains | BackboneElement | | Yes | 0..* | Array of codes in the ValueSet.
ValueSet (R4).expansion.contains.code | code | | | 1..1 | Code value.
ValueSet (R4).expansion.contains.display | string | | | 1..1 | Display value associated with the code.
ValueSet (R4).expansion.contains.system | uri | | | 1..1 | System value for the code.
ValueSet (R4).expansion.parameter | BackboneElement | | Yes | 1..* | Parameter that controlled the expansion process.
ValueSet (R4).expansion.parameter.name | string | | | 1..1 | Parameter name as assigned by the client or server.
ValueSet (R4).expansion.parameter.valueUri | uri | | | 0..1 | Parameter value. Used with the context parameter.
ValueSet (R4).expansion.timestamp | dateTime | | | 1..1 | Time when the ValueSet expansion occurred.
ValueSet (R4).expansion.total | integer | | | 1..1 | Total number of codes in the expansion.
ValueSet (R4).status | code | | | 1..1 | Status of the ValueSet. Always active.
ValueSet (R4).url | uri | | | 1..1 | A canonical reference to this ValueSet.

Sample request

```
GET https://hostname/instance/api/epic/2024/HL7DaVinciDTR/DTROperations/ValueSet/$expand?url=urn%3Auuid%3A35f009f1-a3b3-
    11f0-9c67-0050568b0c08
```

Sample response


```
{
  "resourceType": "ValueSet",
  "id": "fjXxAT5j8Os1KI7IyObhT6w4",
  "url": "urn:uuid:35f009f1-a3b3-11f0-9c67-0050568b0c08",
  "status": "active",
  "expansion": {
    "timestamp": "2025-10-07T19:27:43Z",
    "total": 6,
    "parameter": [
      {
        "name": "url",
        "valueUri": "urn:uuid:35f009f1-a3b3-11f0-9c67-0050568b0c08"
      }
    ],
    "contains": [
      {
        "system": "urn:oid:1.2.840.114350.1.13.861.1.7.2.688169",
        "code": "1",
        "display": "Routine"
      },
      {
        "system": "urn:oid:1.2.840.114350.1.13.861.1.7.2.688169",
        "code": "2",
        "display": "Urgent"
      },
      {
        "system": "urn:oid:1.2.840.114350.1.13.861.1.7.2.688169",
        "code": "5",
        "display": "Two Week Wait"
      },
      {
        "system": "urn:oid:1.2.840.114350.1.13.861.1.7.2.688169",
        "code": "6",
        "display": "See Details"
      },
      {
        "system": "urn:oid:1.2.840.114350.1.13.861.1.7.2.688169",
        "code": "3",
        "display": "Emergency"
      },
      {
        "system": "urn:oid:1.2.840.114350.1.13.861.1.7.2.688169",
        "code": "4",
        "display": "Elective"
      }
    ]
  }
}
```


14.2 CMS Incoming: Non-FHIR

File: site/apis/14-CMS-Incoming/2-Non-FHIR/index.html

* Group.$bulk-member-match File Request

* Group.$bulk-member-match Status Request

14.2.1 Group.$bulk-member-match File Request

File: site/apis/14-CMS-Incoming/2-Non-FHIR/11426-Group-bulk-member-match-File-Request.html
Epic API ID | 11426
FHIR version | Non-FHIR
Categories | CMS Incoming
API type | Industry-Standard
API group | Bulk Member Data Group
USCDI | No
Supports OAuth 2.0 | True
Supported user types | Backend Systems and Non-OAuth 2.0, Clinicians or Administrative Users
Performs scope validation | False
Source | https://fhir.epic.com/Specifications?api=11426

14.2.2 Group.$bulk-member-match Status Request

File: site/apis/14-CMS-Incoming/2-Non-FHIR/11425-Group-bulk-member-match-Status-Request.html
Epic API ID | 11425
FHIR version | Non-FHIR
Categories | CMS Incoming
API type | Industry-Standard
API group | Bulk Member Data Group
USCDI | No
Supports OAuth 2.0 | True
Supported user types | Backend Systems and Non-OAuth 2.0, Clinicians or Administrative Users
Performs scope validation | False
Source | https://fhir.epic.com/Specifications?api=11425