Epic-FHIR — API category: CRM (sections 18 – 18.2.1)

Source: Epic on FHIR (fhir.epic.com) documentation, mirrored 2026-11. Text-only edition for AI ingestion (NotebookLM); pages follow the source order (its table of contents when one exists).

18 API category: CRM

File: site/apis/18-CRM/index.html

R4 (4)

API | Method | URL template | Type
Communication.Read (Customer Relationship Management) (R4) | GET | /api/FHIR/R4/Communication/{ID} | Epic Public
Communication.Read (Non-Patient Customer Relationship Management) (R4) | GET | /api/FHIR/R4/Communication/{ID} | Epic Public
Communication.Search (Customer Relationship Management) (R4) | GET | /api/FHIR/R4/Communication?_id={_id} | Epic Public
Communication.Search (Non-Patient Customer Relationship Management) (R4) | GET | /api/FHIR/R4/Communication?_id={_id} | Epic Public

Non-FHIR (1)

API | Method | URL template | Type
ReceiveCommunication4 | POST | /api/epic/2023/Common/Utility/RECEIVECOMMUNICATION4/ReceiveCommunication4 | Epic Public

18.1 CRM: R4

File: site/apis/18-CRM/1-R4/index.html

* Communication.Read (Customer Relationship Management) (R4)
* Communication.Read (Non-Patient Customer Relationship Management) (R4)
* Communication.Search (Customer Relationship Management) (R4)
* Communication.Search (Non-Patient Customer Relationship Management) (R4)

18.1.1 Communication.Read (Customer Relationship Management) (R4)

File: site/apis/18-CRM/1-R4/10408-Communication-Read-Customer-Relationship-Management-R4.html
Epic API ID | 10408
FHIR version | R4
Categories | CRM
API type | Epic Public
API group | Document and Image Management Group
USCDI | No
Keywords | CRM;communication
Available in inpatient and other contexts | Yes
HTTP method | GET
URL template | /api/FHIR/R4/Communication/{ID}
Supports OAuth 2.0 | True
Supported user types | Backend Systems and Non-OAuth 2.0, Clinicians or Administrative Users, Patients
Performs scope validation | False
Source | https://fhir.epic.com/Specifications?api=10408

Description

The Communication (Customer Relationship Management) resource returns a record of communication between one entity, a sender, to another entity, a receiver. The sender and receivers may be patients, providers, insurers, or customer support analysts. Workflows include managing customer/patient calls and customer service requests as well as providing provider recommendations. Customer Relationship Management (CRM) records are saved in the Customer Service (NCS) master file.

This web service is designed to be used for scanning integrations. The Hyperdrive Client allows end users to acquire scanned documents through a Document Management System (DMS). Hyperdrive can be configured to launch the external scan acquisition application to perform a workflow. Contextual information, like a FHIR Communication ID representing a CRM, can be passed as a context variable as part of the launch workflow. The scanning software can then use the Communication.Read (Customer Relationship Management) API to access information about the CRM. When the scanning workflow is completed within the scanning system, the scanning application stores the scanned document’s binary data to its server and files metadata about the scan to Epic using the DocumentReference.Create (Non-Patient Document Information) API. For CRM scanning workflows that do not have an associated patient, the FHIR Communication ID provided as a launch context variable should be included in the DocumentReference.context.related property in the DocumentReference.Create (Non-Patient Document Information) API to link the scan to the CRM.

Response elements

Name | Type | Optional | Array | Cardinality | Description
Communication | Communication | False | | | An instance of the R4 Communication FHIR resource.

Communication.identifier | Identifier | False | Yes | | The Epic CRM ID
Communication.sender | Reference | True | | | Reference to a patient FHIR resource, representing the source patient (if any) associated with the CRM.
Communication.status | String | False | | | Status from http://hl7.org/fhir/codesystem-request-status.html. Returns “in-progress” when referring to a CRM that has not been resolved, and “completed” when the CRM is resolved.
Communication.subject | Reference | True | | | Reference to a patient FHIR resource, representing the subject (if any) associated with the CRM.

Sample request

```
https://hostname/instance/api/FHIR/R4/Communication/fLEbnJmVAjxBWpjENjrSXAf.2TSJEb1QJKIOb6jiJ4904
```

Sample response

```
<Communication xmlns="http://hl7.org/fhir">
  <id value="fLEbnJmVAjxBWpjENjrSXAf.2TSJEb1QJKIOb6jiJ4904"/>
  <identifier>
    <use value="usual"/>
    <system value="urn:oid:1.2.840.114350.1.13.5325.1.7.2.786783"/>
    <value value="12586"/>
  </identifier>
  <status value="in-progress"/>
  <subject>
    <reference value="Patient/eekLYOfNyfPWT1JTmHCGtrQ3"/>
    <display value="Meissner, Camp"/>
  </subject>
  <sender>
    <reference value="Patient/eekLYOfNyfPWT1JTmHCGtrQ3"/>
    <display value="Meissner, Camp"/>
  </sender>
</Communication>
```

18.1.2 Communication.Read (Non-Patient Customer Relationship Management) (R4)

File: site/apis/18-CRM/1-R4/10535-Communication-Read-Non-Patient-Customer-Relationship-Managem.html
Epic API ID | 10535
FHIR version | R4
Categories | CRM
API type | Epic Public
API group | Document and Image Management Group
USCDI | No
Available in inpatient and other contexts | Yes
HTTP method | GET
URL template | /api/FHIR/R4/Communication/{ID}
Supports OAuth 2.0 | True
Supported user types | Backend Systems and Non-OAuth 2.0, Clinicians or Administrative Users, Patients
Performs scope validation | False
Source | https://fhir.epic.com/Specifications?api=10535

Description

The Communication (Non-Patient Customer Relationship Management) resource returns a record of communication between one entity, a sender, to another entity, a receiver. The sender and receivers may be patients, providers, insurers, or customer support analysts. Workflows include managing customer/patient calls and customer service requests as well as providing provider recommendations. Customer Relationship Management (CRM) records are saved in the Customer Service (NCS) master file. This non-patient CRM resource is created when a sender and receiver communicate regarding a non-patient record. An example could be an employer calling a Health Plan to inquire about a group Premium Billing Account (PBA) being billed for an inaccurate amount.

This web service is designed to be used for scanning integrations. The Hyperdrive Client allows end users to acquire scanned documents through a Document Management System (DMS). Hyperdrive can be configured to launch the external scan acquisition application to perform a workflow. Contextual information, like a FHIR Communication ID representing a CRM, can be passed as a context variable as part of the launch workflow. The scanning software can then use the Communication.Read (Non-Patient Customer Relationship Management) API to access information about the CRM. When the scanning workflow is completed within the scanning system, the scanning application stores the scanned document’s binary data to its server and files metadata about the scan to Epic using the DocumentReference.Create (Non-Patient Document Information) API. For CRM scanning workflows that do not have an associated patient, the FHIR Communication ID provided as a launch context variable should be included in the DocumentReference.context.related property in the DocumentReference.Create (Non-Patient Document Information) API to link the scan to the CRM.

Response elements

Name | Type | Optional | Array | Cardinality | Description
Communication | Communication | False | | | An instance of the R4 Communication FHIR resource.
Communication.identifier | Identifier | False | Yes | | The Epic CRM ID

Communication.status | String | False | | | Status from http://hl7.org/fhir/codesystem-request-status.html. Returns “in-progress” when referring to a CRM that has not been resolved, and “completed” when the CRM is resolved.

Sample request

```
https://hostname/instance/api/FHIR/R4/Communication/N7QjkHD0gaLx21l.JJ5lQA4
```

Sample response

```
<Communication xmlns="http://hl7.org/fhir">
  <id value="fN7QjkHD0gaLx21l.JJ5lQA4"/>
  <identifier>
    <use value="usual"/>
    <system value="urn:oid:1.2.840.114350.1.13.5325.1.7.2.786783"/>
    <value value="12238"/>
  </identifier>
  <status value="in-progress"/>
</Communication>
```

18.1.3 Communication.Search (Customer Relationship Management) (R4)

File: site/apis/18-CRM/1-R4/10537-Communication-Search-Customer-Relationship-Management-R4.html
Epic API ID | 10537
FHIR version | R4
Categories | CRM
API type | Epic Public
API group | Document and Image Management Group
USCDI | No
Available in inpatient and other contexts | Yes
HTTP method | GET
URL template | /api/FHIR/R4/Communication?_id={_id}
Supports OAuth 2.0 | True
Supported user types | Backend Systems and Non-OAuth 2.0, Clinicians or Administrative Users, Patients
Performs scope validation | False
Source | https://fhir.epic.com/Specifications?api=10537

Description

The Communication (Customer Relationship Management) resource returns a record of communication between one entity, a sender, to another entity, a receiver. The sender and receivers may be patients, providers, insurers, or customer support analysts. Workflows include managing customer/patient calls and customer service requests as well as providing provider recommendations. Customer Relationship Management (CRM) records are saved in the Customer Service (NCS) master file.
.

This web service is designed to be used for scanning integrations. The Hyperdrive Client allows end users to acquire scanned documents through a Document Management System (DMS). Hyperdrive can be configured to launch the external scan acquisition application to perform a workflow. Contextual information, like a FHIR Communication ID representing a CRM, can be passed as a context variable as part of the launch workflow. The scanning software can then use the Communication.Read (Non-Patient Customer Relationship Management) API to access information about the CRM. When the scanning workflow is completed within the scanning system, the scanning application stores the scanned document’s binary data to its server and files metadata about the scan to Epic using the DocumentReference.Create (Non-Patient Document Information) API. For CRM scanning workflows that do not have an associated patient, the FHIR Communication ID provided as a launch context variable should be included in the DocumentReference.context.related property in the DocumentReference.Create (Non-Patient Document Information) API to link the scan to the CRM.

The Search interaction currently supports only the _id search parameter, making it similar to a Communication.Read (Customer Relationship Management) request.

Response elements

Name | Type | Optional | Array | Cardinality | Description
Bundle | Bundle | False | | | Resource bundle. For more information, refer to the FHIR specification.
Bundle.entry | BackboneElement | False | Yes | | An array of entries included in this bundle.
Bundle.entry.resource | ResourceContainer | False | | | A container for a single FHIR resource.
Bundle.entry.resource.Communication | Communication | False | | | An instance of the R4 Communication FHIR resource.
Bundle.entry.resource.Communication.identifier | Identifier | False | Yes | | The Epic CRM ID
Bundle.entry.resource.Communication.sender | Reference | True | | | Reference to a patient FHIR resource, representing the source patient (if any) associated with the CRM.
Bundle.entry.resource.Communication.status | String | False | | | Status from http://hl7.org/fhir/codesystem-request-status.html. Returns “in-progress” when referring to a CRM that has not been resolved, and “completed” when the CRM is resolved.
Bundle.entry.resource.Communication.subject | Reference | True | | | Reference to a patient FHIR resource, representing the subject (if any) associated with the CRM.

Sample request

```
https://hostname/instance/api/FHIR/R4/Communication?_id=fLEbnJmVAjxBWpjENjrSXAf.2TSJEb1QJKIOb6jiJ4904
```

Sample response

```
<Bundle xmlns="http://hl7.org/fhir">
  <type value="searchset"/>
  <total value="1"/>
  <link>
    <relation value="self"/>
    <url value="https://hostname/instance/api/FHIR/R4/Communication?_id=fLEbnJmVAjxBWpjENjrSXAf.2TSJEb1QJKIOb6jiJ4904"/>
  </link>
  <entry>
    <link>
      <relation value="self"/>
      <url value=" https://hostname/instance/api/FHIR/R4/Communication/fLEbnJmVAjxBWpjENjrSXAf.2TSJEb1QJKIOb6jiJ4904"/>
    </link>
    <fullUrl value="
    https://hostname/instance/api/FHIR/R4/Communication/fLEbnJmVAjxBWpjENjrSXAf.2TSJEb1QJKIOb6jiJ4904"/>
    <resource>
      <Communication>
        <id value="fLEbnJmVAjxBWpjENjrSXAf.2TSJEb1QJKIOb6jiJ4904"/>
        <identifier>
          <use value="usual"/>
          <system value="urn:oid:1.2.840.114350.1.13.5325.1.7.2.786783"/>
          <value value="12586"/>
        </identifier>
        <status value="in-progress"/>
        <subject>
          <reference value="Patient/eekLYOfNyfPWT1JTmHCGtrQ3"/>
          <display value="Meissner, Camp"/>
        </subject>
        <sender>
          <reference value="Patient/eekLYOfNyfPWT1JTmHCGtrQ3"/>
          <display value="Meissner, Camp"/>
        </sender>
      </Communication>
    </resource>
    <search>
      <mode value="match"/>
    </search>
  </entry>
</Bundle>
```

18.1.4 Communication.Search (Non-Patient Customer Relationship Management) (R4)

File: site/apis/18-CRM/1-R4/10536-Communication-Search-Non-Patient-Customer-Relationship-Manag.html
Epic API ID | 10536
FHIR version | R4
Categories | CRM
API type | Epic Public
API group | Document and Image Management Group
USCDI | No
Keywords | CRM;communication
Available in inpatient and other contexts | Yes
HTTP method | GET
URL template | /api/FHIR/R4/Communication?_id={_id}
Supports OAuth 2.0 | True
Supported user types | Backend Systems and Non-OAuth 2.0, Clinicians or Administrative Users, Patients
Performs scope validation | False
Source | https://fhir.epic.com/Specifications?api=10536

Description

The Communication (Non-Patient Customer Relationship Management) resource returns a record of communication between one entity, a sender, to another entity, a receiver. The sender and receivers may be patients, providers, insurers, or customer support analysts. Workflows include managing customer/patient calls and customer service requests as well as providing provider recommendations. Customer Relationship Management (CRM) records are saved in the Customer Service (NCS) master file. This non-patient CRM resource is created when a sender and receiver communicate regarding a non-patient record. An example could be an employer calling a Health Plan to inquire about a group Premium Billing Account (PBA) being billed for an inaccurate amount.

This web service is designed to be used for scanning integrations. The Hyperdrive Client allows end users to acquire scanned documents through a Document Management System (DMS). Hyperdrive can be configured to launch the external scan acquisition application to perform a workflow. Contextual information, like a FHIR Communication ID representing a CRM, can be passed as a context variable as part of the launch workflow. The scanning software can then use the Communication.Read (Non-Patient Customer Relationship Management) API to access information about the CRM. When the scanning workflow is completed within the scanning system, the scanning application stores the scanned document’s binary data to its server and files metadata about the scan to Epic using the DocumentReference.Create (Non-Patient Document Information) API. For CRM scanning workflows that do not have an associated patient, the FHIR Communication

ID provided as a launch context variable should be included in the DocumentReference.context.related property in the DocumentReference.Create (Non-Patient Document Information) API to link the scan to the CRM.

The Search interaction currently supports only the _id search parameter, making it similar to a Communication.Read (Non-Patient Customer Relationship Management) request.

Response elements

Name | Type | Optional | Array | Cardinality | Description
Bundle | Bundle | False | | | Resource bundle. For more information, refer to the FHIR specification.
Bundle.entry | BackboneElement | False | Yes | | An array of entries included in this bundle.
Bundle.entry.resource | ResourceContainer | False | | | A container for a single FHIR resource.
Bundle.entry.resource.Communication | Communication | False | | | An instance of the R4 Communication FHIR resource.
Bundle.entry.resource.Communication.identifier | Identifier | False | Yes | | The Epic CRM ID
Bundle.entry.resource.Communication.status | String | False | | | Status from http://hl7.org/fhir/codesystem-request-status.html. Returns “in-progress” when referring to a CRM that has not been resolved, and “completed” when the CRM is resolved.

Sample request

```
https://hostname/instance/api/FHIR/R4/Communication?_id=fN7QjkHD0gaLx21l.JJ5lQA4
```

Sample response

```
<Bundle xmlns="http://hl7.org/fhir">
  <type value="searchset"/>
  <total value="1"/>
  <link>
    <relation value="self"/>
    <url value="https://hostname/instance/api/FHIR/R4/Communication?_id=fN7QjkHD0gaLx21l.JJ5lQA4"/>
  </link>
  <entry>
    <link>
      <relation value="self"/>
      <url value="https://hostname/instance/api/FHIR/R4/Communication/fN7QjkHD0gaLx21l.JJ5lQA4"/>
    </link>
    <fullUrl value="https://hostname/instance/api/FHIR/R4/Communication/fN7QjkHD0gaLx21l.JJ5lQA4"/>
    <resource>
      <Communication>
        <id value="fN7QjkHD0gaLx21l.JJ5lQA4"/>
        <identifier>
          <use value="usual"/>
          <system value="urn:oid:1.2.840.114350.1.13.5325.1.7.2.786783"/>
          <value value="12238"/>
        </identifier>
        <status value="in-progress"/>
      </Communication>
    </resource>
    <search>
      <mode value="match"/>
    </search>
  </entry>
</Bundle>
```

18.2 CRM: Non-FHIR

File: site/apis/18-CRM/2-Non-FHIR/index.html

* ReceiveCommunication4

18.2.1 ReceiveCommunication4

File: site/apis/18-CRM/2-Non-FHIR/11301-ReceiveCommunication4.html
Epic API ID | 11301
FHIR version | Non-FHIR
Categories | CRM
API type | Epic Public
API group | Computer-Telephony Integration (CTI) Group
USCDI | No
HTTP method | POST
URL template | /api/epic/2023/Common/Utility/RECEIVECOMMUNICATION4/ReceiveCommunication4
Supports OAuth 2.0 | True
Supported user types | Backend Systems and Non-OAuth 2.0, Clinicians or Administrative Users
Performs scope validation | False
Source | https://fhir.epic.com/Specifications?api=11301

Remarks

This API creates communication tracking records.

If LookupType is set to Patient or Provider, and if:

* LookupID is used, the screen pop is linked directly to the patient, provider, or vendor record.

* LookupInformation, LookupInformationType, or CallerPhoneNumber is used, the user is shown a list of matching patients, providers, or vendors to select from before the desired screen is popped.

* No match is found, the user is notified and taken to the patient, provider, or vendor lookup screen.

If LookupType is set to None, the activity is launched without automatically selecting a patient. If a patient is required for the activity, use the Patient lookup type.

For Auto Dial workflows,

* Leave Context blank, as the system determines the correct activity to launch.

* ContactType should be set to Outgoing.

* CommunicationType should be set to Phone.

* LookupType must be set to AutoDial and the LookupID must be populated with a valid Auto Dial Reply Context.

* The patient associated with the Auto Dial Reply Context listed in LookupID appears in the Identity Validation screen, so the user can confirm their identity. If the external phone system supports patient validation (IVR, for example), the validated patient's ID can be passed in the AdditionalLookupID field. If the lookup is successful and the patient ID matches that from the Auto Dial Reply Context, the Identity Validation screen is bypassed.

Request parameters

Name | Type | Optional | Array | Cardinality | Description
AdditionalLookupID | IDType | True | | | A generic identifier.
AdditionalLookupType | String | True
CallerName | String | True
CallerPhoneNumber | String | True
CallerRelationshipToPatient | String | True
CallID | String | True
CommunicationType | String | True
ContactType | String | True
Context | String | True
DialedPhoneNumber | String | True
IntentID | IDType | True | | | A generic identifier.
LookupID | IDType | True | | | A generic identifier.
LookupID.ID | String | False | | | The identifier for this resource.
LookupID.Type | String | False | | | The type of identifier.
LookupInformation | String | True
LookupInformationType | String | True
LookupType | String | True
PhoneSystemID | IDType | True | | | A generic identifier.
RecipientID | String | False
RecipientIDType | String | True

Response elements

Name | Type | Optional | Array | Cardinality | Description
EpicCallID | String | False

Errors

Code | Severity | Description | Example
NOT-LICENSED | None | | Required license is not activated.
INVALID-AUTHORIZATION-CONTEXT | None | | This service does not allow this type of authorizing user.
INVALID-CONTEXT | None | | The context given was not valid.
NO-USER-ID | None | | User ID not provided.
INVALID-USER-ID | None | | The user ID does not match the user provided with the OAuth token.
INVALID-USER-ID-TYPE | None | | Invalid ID type entered.
NO-USER-FOUND | None | | Either the user is not logged in or the user is not found.
INVALID-LOOKUP-TYPE | None | | Lookup type is invalid.
INVALID-LOOKUP-ID-TYPE | None | | Lookup ID type is invalid.
NO-RECORD-FOUND | None | | Record not found.
NO-LOOKUP-INFORMATION | None | | The required lookup information was not given.
INVALID-CONTACT-TYPE | None | | Contact type is invalid.
INVALID-COMMUNICATION-TYPE | None | | Communication type is invalid.
ACTIVITY-NOT-SUPPORTED-READ-ONLY | None | | The specified activity is not supported in read-only environments.
EVENT-PUBLISH-FAILED | None | | The event failed to publish to Hyperspace.
NO-EXTENSION-FOUND | None | | Phone extension is not mapped.
INVALID-PHONE-NUMBER | None | | The provided phone number is not a valid phone number
INVALID-LOOKUP-INFORMATION-TYPE | None | | Lookup information type is not valid.
INVALID-PHONE-SYSTEM-ID-TYPE | None | | The phone system ID type is invalid.
NO-PHONE-SYSTEM-FOUND | None | | The phone system ID is invalid.
INVALID-PHONE-SYSTEM-FOUND | None | | The phone system ID is an actual record ID, but the corresponding record isn't built correctly.

INVALID-ADDITIONAL-LOOKUPID-TYPE | None | | Additional Lookup ID Type is invalid.
UNSUPPORTED-ADDITIONAL-LOOKUP-TYPE | None | | Patient is the only value supported for AdditionalLookupType.
INVALID-ADDITIONAL-LOOKUP-ID | None | | Invalid patient ID or Type provided for AdditionalLookupId. This field is required if AdditionalLookupType is populated.
CRM-AUTODIALER-NOT-ENABLED | None | | This environment is not licensed for the auto dial web service.
MCK-AUTODIAL-LOOKUP-ID | None | | A valid Auto Dial Reply Context CSN value in the LookupID field is required for communications with a LookupType of AutoDial, but one wasn't provided. Mock outreach RCH CSN values, created through Campaign Test Outreach, are not supported
INVALID-AUTODIAL-LOOKUP-ID | None | | A valid Auto Dial Reply Context CSN value in the LookupID field is required for communcations with a LookupType of AutoDial, but one wasn't provided.
NO-AUTODIAL-LOOKUP-ID | None | | An Auto Dial Reply Context CSN value in the LookupID field is required for communications with a LookupType of AutoDial, but one wasn't provided.
OUTREACH-RECORD-INVALID-FOR-AUTODIAL | None | | The Auto Dial Reply Context CSN value provided in the LookupID field does not have a valid patient, order, or CRM re]cord associated with it.
OUTREACH-CONTEXT-INVALID-FOR-AUTODIAL | None | | An Auto Dial Reply Context CSN value in the LookupID field is required for communications with a LookupType of AutoDial, but a valid one wasn't provided.
INVALID-INTENT-ID | None | | A valid Customer Service Workflow or Customer Service Grouper value was not provided in the IntentID field.

Sample request


```
{
  "Context": "",
  "RecipientID": "29900",
  "RecipientIDType": "External",
  "LookupType": "AutoDial",
  "LookupInformationType": "",
  "LookupInformation": "",
  "CallID": "AD1234",
  "ContactType": "Outgoing",
  "CommunicationType": "Phone",
  "CallerPhoneNumber": "6085551234",
  "DialedPhoneNumber": "",
  "AdditionalLookupType": "Patient",
  "CallerName": "",
  "CallerRelationshipToPatient": "",
  "LookupID": {
    "ID": "12345678",
    "Type": "CSN"
  },
  "PhoneSystemID": {
    "ID": "",
    "Type": ""
  },
  "AdditionalLookupID": {
    "ID": "123456",
    "Type": "MRN"
  },
  "IntentID": {
    "ID": "",
    "Type": ""
  }
}
```


Sample response


```
{
  "EpicCallID": "2990000"
}
```