Epic-FHIR — API category: Identification Individuals (sections 22 – 22.4.5)

Source: Epic on FHIR (fhir.epic.com) documentation, mirrored 2026-11. Text-only edition for AI ingestion (NotebookLM); pages follow the source order (its table of contents when one exists).

22 API category: Identification Individuals

File: site/apis/22-Identification-Individuals/index.html

R4 (12)

API | Method | URL template | Type
Patient.$match (Patient Match) (R4) | POST | /api/FHIR/R4/Patient/$match | Industry-Standard
Patient.Create (Demographics) (R4) | POST | api/FHIR/R4/Patient | Industry-Standard
Patient.Read (Demographics) (R4) | GET | api/FHIR/R4/Patient/{ID} | USCDI
Patient.Search (Demographics) (R4) | GET | api/FHIR/R4/Patient?address={address}&address-city={address-city}&address-postalcode={address-postalcode}&address-state={address-state}&birthdate={birthdate}&family={family}&gender={gender}&given={given}&identifier={identifier}&name={name}&own-name={own-name}&own-prefix={own-prefix}&partner-name={partner-name}&partner-prefix={partner-prefix}&telecom={telecom}&legal-sex={legal-sex} | USCDI
Practitioner.Read (Organizational Directory) (R4) | GET | api/FHIR/R4/Practitioner/{ID} | USCDI
Practitioner.Search (Organizational Directory) (R4) | GET | api/FHIR/R4/Practitioner?address={address}&address-city={address-city}&address-postalcode={address-postalcode}&address-state={address-state}&family={family}&given={given}&identifier={identifier}&name={name} | USCDI
PractitionerRole.Read (Organizational Directory) (R4) | GET | api/FHIR/R4/PractitionerRole/{ID} | USCDI
PractitionerRole.Search (Organizational Directory) (R4) | GET | api/FHIR/R4/PractitionerRole?email={email}&identifier={identifier}&location={location}&phone={phone}&practitioner={practitioner}&specialty={specialty}&organization={organization}&role={role}&telecom={telecom} | USCDI
RelatedPerson.Read (Friends and Family) (R4) | GET | /api/FHIR/R4/RelatedPerson/{ID} | USCDI
RelatedPerson.Read (Proxy) (R4) | GET | api/FHIR/R4/RelatedPerson/{ID} | USCDI
RelatedPerson.Search (Friends and Family) (R4) | GET | /api/FHIR/R4/RelatedPerson?_id={_id} | USCDI
RelatedPerson.Search (Proxy) (R4) | GET | /api/FHIR/R4/RelatedPerson?_id={ID} | USCDI

STU3 (7)

API | Method | URL template | Type
Patient.Create (STU3) | POST | api/FHIR/STU3/Patient | Industry-Standard
Patient.Read (STU3) | GET | api/FHIR/STU3/Patient/{ID} | USCDI
Patient.Search (STU3) | GET | api/FHIR/STU3/Patient?address={address}&address-city={address-city}&address-postalcode={address-postalcode}&address-state={address-state}&birthdate={birthdate}&family={family}&gender={gender}&given={given}&identifier={identifier}&own-name={own-name}&own-prefix={own-prefix}&partner-name={partner-name}&partner-prefix={partner-prefix}&telecom={telecom}&legal-sex={legal-sex} | USCDI
Practitioner.Read (STU3) | GET | api/FHIR/STU3/Practitioner/{ID} | USCDI
Practitioner.Search (STU3) | GET | api/FHIR/STU3/Practitioner?address={address}&address-city={address-city}&address-postalcode={address-postalcode}&address-state={address-state}&family={family}&given={given}&identifier={identifier}&name={name} | USCDI
PractitionerRole.Read (STU3) | GET | api/FHIR/STU3/PractitionerRole/{ID} | USCDI
PractitionerRole.Search (STU3) | GET | /api/FHIR/STU3/PractitionerRole?email={email}&identifier={identifier}&location={location}&organization={organization}&phone={phone}&practitioner={practitioner}&role={role}&specialty={specialty}&telecom={telecom} | USCDI

DSTU2 (4)

API | Method | URL template | Type
Patient.Read (DSTU2) | GET | api/FHIR/DSTU2/Patient/{ID} | USCDI
Patient.Search (DSTU2) | GET | api/FHIR/DSTU2/Patient?_id={_id}&identifier={identifier}&family={family}&given={given}&birthdate={birthdate}&address={address}&gender={gender}&telecom={telecom} | USCDI
Practitioner.Read (DSTU2) | GET | api/FHIR/DSTU2/Practitioner/{ID} | USCDI
Practitioner.Search (DSTU2) | GET | api/FHIR/DSTU2/Practitioner?_id={_id}&address={address}&family={family}&gender={gender}&given={given}&specialty={specialty}&address_city={address_city}&address_state={address_state}&address_postalcode={address_postalcode} | USCDI

Non-FHIR (5)

API | Method | URL template | Type
PatientCreate (2009) | | | Epic Public
PatientLookup (2005) | | | Epic Public
PatientLookup (2009) | | | Epic Public
PatientLookup (2012) | POST | api/epic/2012/EMPI/Patient/PATIENTLOOKUP/Lookup | Epic Public
UpdateUserDemographics | POST | api/epic/2011/Common/User/UPDATEUSERDEMOGRAPHICS/User/Demographics?UserID={UserID}&UserIDType={UserIDType}&EmailAddress={EmailAddress}&PhoneNumber={PhoneNumber}&FaxNumber={FaxNumber}&UpdateLinkedProviderRecord={UpdateLinkedProviderRecord} | Epic Public

22.1 Identification Individuals: R4

File: site/apis/22-Identification-Individuals/1-R4/index.html

* Patient.$match (Patient Match) (R4)
* Patient.Create (Demographics) (R4)

* Patient.Read (Demographics) (R4)
* Patient.Search (Demographics) (R4)
* Practitioner.Read (Organizational Directory) (R4)
* Practitioner.Search (Organizational Directory) (R4)
* PractitionerRole.Read (Organizational Directory) (R4)
* PractitionerRole.Search (Organizational Directory) (R4)
* RelatedPerson.Read (Friends and Family) (R4)
* RelatedPerson.Read (Proxy) (R4)
* RelatedPerson.Search (Friends and Family) (R4)
* RelatedPerson.Search (Proxy) (R4)

22.1.1 Patient.$match (Patient Match) (R4)

File: site/apis/22-Identification-Individuals/1-R4/10423-Patient-match-Patient-Match-R4.html
Epic API ID | 10423
FHIR version | R4
Categories | Identification Individuals
API type | Industry-Standard
USCDI | No
Keywords | patient;match;search
Available in inpatient and other contexts | Yes
HTTP method | POST
URL template | /api/FHIR/R4/Patient/$match
Supports OAuth 2.0 | True
Supported user types | Backend Systems and Non-OAuth 2.0, Clinicians or Administrative Users, Patients
Performs scope validation | False
Source | https://fhir.epic.com/Specifications?api=10423

Description

The $match operation accepts a set of patient demographic information and attempts to find a single high-confidence match for a patient record in the target organization's system.

The Patient.$match operation is similar to

Patient.Search (Demographics) (R4)

. For systems that need a single high confidence match, Epic recommends using Patient.$match instead of Patient.Search. An example would be a back-end system without an end user. If a system has an end user who can evaluate a list of patients returned by Patient.Search, then Patient.Search is potentially a better option. Epic's implementation of this operation requires that the onlyCertainMatches parameter be set to “true”. This means that the operation returns a matching Patient resource only if one high-confidence match is found. When more than one patient record in the target system is matched with high confidence, or when no patient can be matched with high confidence to the provided demographics, this operation returns no results and a corresponding error:

* Multiple high-confidence matches: OperationOutcome code 59011 (“The matching operation found multiple potential matches, but requires only one match.”)
* No high-confidence matches, but one or more low-confidence matches: OperationOutcome code 59013 (“The matching operation found one or more possible matches, but did not find a certain match.”)
* No high-confidence or low-confidence matches: OperationOutcome 4101 (“Resource request returns no results.”)

When a non-national ID identifier is provided (e.g. the patient's MRN), the identifier will first be used to perform patient lookup. Provided demographics are still required and will be used to validate the found patient. A patient is considered valid if the provided demographics is a low confidence match with the found patient. If identifier lookup without providing demographics information is desired, please refer to Patient.Search (R4) as an alternative.

The demographics requirements to produce a high-confidence match on a patient can be configured differently at each organization. By default, the following information will influence whether a patient is considered a high confidence match:

Information that is required:

* Exact patient name
* Exact patient birthdate

A combination of the following optional information:

* Patient address
* National identifier (e.g. SSN)
* Patient phone number
* Patient email address
* Patient gender

A user accessing this FHIR resource must have appropriate security to have search details, demographic details, and/or PCP details included in the Patient resource. Additionally, if an Epic organization has configured service area restrictions, the user accessing this FHIR resource must be authorized to view patients in the target service area.

This operation is not supported for MyChart users.

Patient.$match is not currently supported for organizations in the Netherlands. This is because Epic doesn't currently support given name initials in the request body.

Request parameters

Name | Type | Optional | Array | Cardinality | Description

Parameters (R4) | Parameters | | | | Parameters resource comprising the request data.

Parameters (R4).parameter (onlyCertainMatches) (also: parameter (onlyCertainMatches)) | BackboneElement | | Yes | 1..1 | An instance of the Parameters resource containing the onlyCertainMatches parameter. Specify resourceType = Parameters

Parameters (R4).parameter (onlyCertainMatches).name | string | | | 1..1 | Set to onlyCertainMatches.

Parameters (R4).parameter (onlyCertainMatches).valueBoolean | Boolean | | | 1..1 | Epic only supports the use case where onlyCertainMatches is set to true.

Parameters (R4).parameter (resource) (also: parameter (resource)) | BackboneElement | | Yes | 1..1 | An instance of the Parameters resource containing the resource parameter which represents a Patient resource. Specify resourceType = Parameters

Parameters (R4).parameter (resource).name | string | | | 1..1 | Set to resource.

Parameters (R4).parameter (resource).resource | ResourceContainer | | | 1..1 | Contains the Patient FHIR resource. Specify resource.resourceType = Patient

Parameters (R4).parameter (resource).resource.Patient | Resource | | | 1..1 | The Patient FHIR resource with the demographics used to match to a patient record.

Parameters (R4).parameter (resource).resource.Patient.address | Address | | Yes | 0..1 | The patient's address information.

Parameters (R4).parameter (resource).resource.Patient.address.city | string | | | 0..1 | The city that the patient lives in.

Parameters (R4).parameter (resource).resource.Patient.address.country | String | | | 0..1 | The country that the patient lives in.

Parameters (R4).parameter (resource).resource.Patient.address.district | String | | | 0..1 | The patient's county of residence.

Parameters (R4).parameter (resource).resource.Patient.address.line | string | | Yes | 0..* | The patient’s street address. You can enter multiple lines of address.

Parameters (R4).parameter (resource).resource.Patient.address.postalCode | string | | | 0..1 | The patient's ZIP Code in one of the following formats: nnnnn nnnnn-nnnn

Parameters (R4).parameter (resource).resource.Patient.address.state | string | | | 0..1 | The state where the patient lives. Either enter the two-letter postal abbreviation for the state or the state's numeric value. The numeric value is assigned alphabetically where District of Columbia is 9 and Wyoming is 51.

Parameters (R4).parameter (resource).resource.Patient.birthDate | date | | | 0..1 | The patient's date of birth in the format YYYY-MM-DD.

Parameters (R4).parameter (resource).resource.Patient.gender | code | | | 0..1 | The patient's legal sex.

Parameters (R4).parameter (resource).resource.Patient.identifier | Identifier | | Yes | 0..* | The patient's identifier. To look up a patient using only the identifier without any demographics information, refer to Patient.Search (R4). Epic MPI IDs (e.g. the patient's MRN) and national IDs (e.g. SSN) are supported in this field. Historical MPI IDs are supported with no special formatting requirements. If an MPI ID is provided, Epic will use the identifier to find the patient instead of the provided demographics. The matching patient will then be verified using the provided demographics. If a national ID is provided, Epic will perform a match on overall demographics, including the national ID, instead of a lookup on only the identifier. If multiple identifiers are provided, they must all be on the same patient.

Parameters (R4).parameter (resource).resource.Patient.identifier.system | String | | | 1..1 | The identifier's system value. Valid system values include: MPI ID OID. This system value is highly configurable at each Epic organization. National identifier OIDs including: US Social Security Number: 2.16.840.1.113883.4.1 UK NHS ID: 2.16.840.1.113883.2.1.4.1 Dutch BSN: 2.16.840.1.113883.2.4.6.3 or http://fhir.nl/fhir/NamingSystem/bsn Finnish National ID: 1.2.246.21

Parameters (R4).parameter (resource).resource.Patient.identifier.value | String | | | 1..1 | The identifier.

Parameters (R4).parameter (resource).resource.Patient.name | HumanName | | Yes | 0..1 | The patient name.

Parameters (R4).parameter (resource).resource.Patient.name.family | string | | | 0..1 | The patient's family name.

Parameters (R4).parameter (resource).resource.Patient.name.given | string | | Yes | 0..1 | The patient's given name. May include first and middle names.

Parameters (R4).parameter (resource).resource.Patient.telecom | ContactPoint | | Yes | 0..* | Telephone numbers and email addresses for the patient, along with their use (home or work for example).

Parameters (R4).parameter (resource).resource.Patient.telecom.system | code | | | 1..1 | The type of telecom. Potential values are: email phone

Parameters (R4).parameter (resource).resource.Patient.telecom.use | code | | | 0..1 | If the telecom entry is a phone number, possible values are: home mobile work

Parameters (R4).parameter (resource).resource.Patient.telecom.value | string | | | 1..1 | Value of the telecom method. May be an email address or phone number.

Response elements

Name | Type | Optional | Array | Cardinality | Description

Patient (R4) | Resource

Patient (R4).active | boolean | | | 1..1 | Whether the patient record is active.

Patient (R4).address | Address | | Yes | 0..* | The patient's current address, as well as any previous or temporary addresses, if applicable. The patient's current address has a use code of "home". If the patient also has one or more previous addresses, each previous address has a use code of "old". The patient's temporary address has a use code of "temp".

Patient (R4).address.city | string | | | 0..1 | The city that the patient lives in.

Patient (R4).address.country | String | | | 0..1 | The country that the patient lives in.

Patient (R4).address.district | String | | | 0..1 | The county that the patient lives in.

Patient (R4).address.line | string | | Yes | 0..* | The patient’s street address.

Patient (R4).address.line.extension (additionalLocator) (also: extension (additionalLocator)) | Extension | | Yes | 0..1 | This extension is returned only for organizations in Singapore. The patient’s floor. URL: http://hl7.org/fhir/StructureDefinition/iso21090-ADXP-additionalLocator

Patient (R4).address.line.extension (buildingName) (also: extension (buildingName)) | Extension | | Yes | 0..1 | This extension is returned only for organizations in Singapore. The patient's building name. URL: http://open.epic.com/FHIR/StructureDefinition/extension/buildingName

Patient (R4).address.line.extension (houseNumber) (also: extension (houseNumber)) | Extension | | Yes | 0..1 | For organizations in the Netherlands and Singapore, this element represents the portion of a patient or contact's address that is their house number. URL: http://hl7.org/fhir/StructureDefinition/iso21090-ADXP-houseNumber

Patient (R4).address.line.extension (streetName) (also: extension (streetName)) | Extension | | Yes | 0..* | For organizations in the Netherlands and Singapore, this element represents the portion of a patient or contact's address that includes the name of their street. URL: http://hl7.org/fhir/StructureDefinition/iso21090-ADXP-streetName

Patient (R4).address.line.extension (unitID) (also: extension (unitID)) | Extension | | Yes | 0..1 | This extension is returned only for organizations in Singapore. The patient's unit number. URL: http://hl7.org/fhir/StructureDefinition/iso21090-ADXP-unitID

Patient (R4).address.period | Period | | | 0..1 | The start date – and optionally, end date – for when the address is valid. Returned for the current address if the information is available. Starting in the May 2025 version of Epic, also returned for previous and temporary addresses if the information is available.

Patient (R4).address.postalCode | string | | | 0..1 | The patient's postal code.

Patient (R4).address.state | string | | | 0..1 | The state where the patient lives.

Patient (R4).address.text | String | | | 0..1 | The patient's full address as a string. This is formatted based on the country the address is in. For U.S. addresses, to meet the standards laid out in the Project US@ Technical Specifications, patient addresses format automatically for patient matching purposes.

Patient (R4).address.use | code | | | 1..1 | Specifies the type of address: home – A permanent address old – A previous permanent address temp – A temporary address Temporary addresses behavior varies by Epic version: May 2025 or later – Returned only if the Epic organization has configured temporary addresses to be visible in FHIR responses (applies to all locales). Prior to May 2025 – Singapore – Always returned. Norway – Always returned if using: August 2024 version, or May 2024 version with special updates.

Patient (R4).birthDate | date | | | 1..1 | The patient's date of birth in the format YYYY-MM-DD

Patient (R4).birthDate.extension (birthTime) (also: extension (birthTime)) | Extension | | | 0..1 | The patient's time of birth. This extension follows the HL7 birthTime specification. Prior to the November 2023 verison of Epic, this extension was returned at the Patient resource level. Beginning in the November 2023 version of Epic, this is now returned underneath the BirthDate element. URL: http://hl7.org/fhir/StructureDefinition/patient-birthTime

Patient (R4).birthDate.extension (dataAbsentReason) (also: extension (dataAbsentReason)) | Extension | | | 0..1 | Available starting with the November 2024 version of Epic. If the patient's birth date is not recorded, this extension is returned with a value of "unknown". URL: http://hl7.org/fhir/StructureDefinition/data-absent-reason

Patient (R4).communication | BackboneElement | | Yes | 0..* | Languages used to communicate with the patient, along with an indicator of which is preferred.

Patient (R4).communication.extension (comment) (also: extension (comment)) | Extension | | Yes | 0..1 | A comment about the patient's language proficiency. This extension is returned only for organizations in the Netherlands. URL: http://nictiz.nl/fhir/StructureDefinition/Comment

Patient (R4).communication.extension (patient-proficiency) (also: extension (patient-proficiency)) | Extension | | Yes | 0..3 | Container extension that holds details about the patient's language proficiency. Contains two child extensions which indicate the type of language proficiency and the level of that proficiency. This extension is returned only for organizations in the Netherlands. URL: http://nictiz.nl/fhir/StructureDefinition/patient-proficiency

Patient (R4).communication.extension (patient-proficiency).extension (v3-LanguageAbilityMode) (also: extension (v3-LanguageAbilityMode)) | Extension | | Yes | 0..1 | Patient's language proficiency type. This is a valueCoding wherein the following code and display values are supported: RSP - Received spoken ESP - Expressed spoken RWR - Received written System value of http://terminology.hl7.org/CodeSystem/v3-LanguageAbilityMode URL: type

Patient (R4).communication.extension (patient-proficiency).extension (v3-LanguageAbilityProficiency) (also: extension (v3-LanguageAbilityProficiency)) | Extension | | Yes | 0..1 | Patient's language proficiency level. This is a valueCoding wherein the following code and display values are supported: E - Excellent G - Good F - Fair P - Poor System value of http://terminology.hl7.org/CodeSystem/v3-LanguageAbilityProficiency URL: level

Patient (R4).communication.language | CodeableConcept | | | 1..1 | The patient's general language, onsite care language, and spoken language.

Patient (R4).communication.preferred | boolean | | | 0..1 | Whether the language is the patient's preferred language.

Patient (R4).communication.preferred.extension (patient-preferenceType) (also: extension (patient-preferenceType)) | Extension | | Yes | 0..1 | The preferred mode of communication for the patient's preferred language. This can be either verbal or written. Returned starting in the May 2025 version of Epic. Returned with system http://hl7.org/fhir/language-preference-type. URL: http://hl7.org/fhir/StructureDefinition/patient-preferenceType

Patient (R4).contact | BackboneElement | | Yes | 0..* | Details for the patient's contacts. Patient contacts include any documented family members, emergency contacts, care givers, acquaintances, and employers.

Patient (R4).contact.address | Address | | | 0..1 | The contact address. For responses to a patient-facing application, this element is not returned for contacts linked to a patient record. For organizations in the Netherlands, this element represents an nl-core-address value.

Patient (R4).contact.name | HumanName | | | 1..1 | The contact's preferred name. The system determines this from the contact's linked patient record if available. For contacts linked to a patient record, only the patient's official first name is returned in patient context. For organizations in the Netherlands, this element represents an nl-core-humanname value.

Patient (R4).contact.name.extension (humanname-assembly-order) (also: extension (humanname-assembly-order)) | Extension | | Yes | 0..1 | This extension is populated only for organizations in the Netherlands. Name order for the contact. One of the following values: NL1 - Own Name NL2 - Partner Name NL3 - Partner Name followed by Maiden Name NL4 - Own Name followed by Partner Name URL: http://hl7.org/fhir/StructureDefinition/humanname-assembly-order

Patient (R4).contact.organization | Reference | | | 0..1 | An Organization reference that represents the patient's employer. Returned when contact.relationship.code is E.

Patient (R4).contact.period | Period | | | 0..1 | The start and end dates for the patient contact.

Patient (R4).contact.relationship | CodeableConcept | | Yes | 0..* | The contact's relationship to the patient. This element can return multiple values. It will always return one or more Epic category values for the contact's relationship to the patient. In addition, it can return one or more of the following: For organizations in the Netherlands, either a Relationship (RelatieCodelijst) code system value or a role (RolCodelijst) code system value. For all other organizations, can return either a code system value – such as "C" (emergency contact) or "E" (employer) – or a RoleClass code system value – such as "GUARD" or "AGNT".

Patient (R4).contact.telecom | ContactPoint | | Yes | 0..* | Telephone numbers and email address for the contact. For responses to a patient-facing application, this element is not returned for contacts linked to a patient record. For organizations in the Netherlands, this element represents an nl-core-contactpoint value.

Patient (R4).contact.telecom.rank | positiveInt | | | 0..1 | The priority for permanent phone numbers or emails. 1 indicates the highest priority phone number, 2 indicates the second priority, and so on. Starting in the May 2025 version of Epic, rank is returned for the phone numbers of patient contacts.

Patient (R4).contact.telecom.system | code | | | 0..1 | The type of telecom. Potential values are: email phone

Patient (R4).contact.telecom.use | code | | | 0..1 | If the telecom entry is a phone number, possible values are: home mobile work

Patient (R4).contact.telecom.value | string | | | 1..1 | Value of the telecom method. Can be an email address or phone number.

Patient (R4).deceasedBoolean | boolean | | | 0..1 | Whether the patient is deceased.

Patient (R4).deceasedDateTime | dateTime | | | 0..1 | The date and time of death.

Patient (R4).extension (birth-location) (also: extension (birth-location)) | Extension | | Yes | 0..1 | A reference to a newborn's birth facility. URL: http://open.epic.com/FHIR/StructureDefinition/extension/birth-location

Patient (R4).extension (birth-sex) (also: extension (birth-sex)) | Extension | | Yes | 0..1 | The patient's sex assigned at birth. This element is not returned for organizations in the Netherlands. URL: http://hl7.org/fhir/us/core/StructureDefinition/us-core-birthsex

Patient (R4).extension (calculated-pronouns-to-use-for-text) (also: extension (calculated-pronouns-to-use-for-text)) | Extension | | Yes | 0..* | The patient's pronouns to use when generating text. Available starting in the November 2023 version of Epic. This is an Epic-calculated value based on specified pronouns, the patient's gender identity, or the patient's legal sex. Consider using extension (individual-pronouns) instead of this one. One of the following: A value from LOINC Answer List LL5144-2 Personal pronouns EP-PS-DO-NOT-USE-PRONOUNS, from the Epic-defined pronoun set https://open.epic.com/FHIR/Epic/pronoun-set URL: http://open.epic.com/FHIR/StructureDefinition/extension/calculated-pronouns-to-use-for-text

Patient (R4).extension (gender-identity) (also: extension (gender-identity)) | Extension | | Yes | 0..1 | The patient's gender identity. URL: http://hl7.org/fhir/StructureDefinition/patient-genderIdentity

Patient (R4).extension (individual-pronouns) (also: extension (individual-pronouns)) | Extension | | Yes | 0..* | The pronouns to use when communicating about an individual. Available starting in the November 2024 version of Epic. URL: http://hl7.org/fhir/StructureDefinition/individual-pronouns

Patient (R4).extension (legal-sex) (also: extension (legal-sex)) | Extension | | Yes | 0..1 | The patient's legal sex. URL: http://open.epic.com/FHIR/StructureDefinition/extension/legal-sex

Patient (R4).extension (nationality) (also: extension (nationality)) | Extension | | Yes | 0..1 | The patient's nationality. This extension is returned only for organizations in the Singapore. URL: http://hl7.org/fhir/StructureDefinition/patient-nationality

Patient (R4).extension (patient-preferred-provider-language) (also: extension (patient-preferred-provider-language)) | Extension | | Yes | 0..1 | The patient's preferred provider language, used for scheduling. URL: http://open.epic.com/FHIR/STU3/StructureDefinition/patient-preferred-provider-language

Patient (R4).extension (patient-preferred-provider-sex) (also: extension (patient-preferred-provider-sex)) | Extension | | Yes | 0..1 | The patient's preferred provider sex, used for scheduling. URL: http://open.epic.com/FHIR/STU3/StructureDefinition/patient-preferred-provider-sex

Patient (R4).extension (patient-type) (also: extension (patient-type)) | Extension | | Yes | 0..* | The type of patient, such as Confidential or Employee. URL: http://open.epic.com/FHIR/StructureDefinition/extension/patient-type

Patient (R4).extension (patient-unmerge-source) (also: extension (patient-unmerge-source)) | Extension | | Yes | 0..* | This extension contains a collection of extensions that represent the metadata for a patient record unmerge from the perspective of the source patient. If the patient is involved as the source patient in multiple unmerges, this set of extensions is returned for each unmerge event. URL: https://open.epic.com/FHIR/StructureDefinition/patient-unmerge-source

Patient (R4).extension (patient-unmerge-source).extension (patient-merge-unmerge-instant) (also: extension (patient-merge-unmerge-instant)) | Extension | | Yes | 0..1 | The instant the patient merge event occurred. URL: https://open.epic.com/FHIR/StructureDefinition/patient-merge-unmerge-instant

Patient (R4).extension (patient-unmerge-source).extension (patient-unmerge-current-target-reference) (also: extension (patient-unmerge-current-target-reference)) | Extension | | Yes | 0..1 | A reference to the current FHIR ID of the unmerge event's target patient. URL: https://open.epic.com/FHIR/StructureDefinition/patient-unmerge-current-target-reference

Patient (R4).extension (patient-unmerge-source).extension (patient-unmerge-old-target-reference) (also: extension (patient-unmerge-old-target-reference)) | Extension | | Yes | 0..1 | A reference to the FHIR ID of the unmerge event's target patient at the time of the merge. URL: https://open.epic.com/FHIR/StructureDefinition/patient-unmerge-old-target-reference

Patient (R4).extension (patient-unmerge-source).extension (patient-unmerge-original-source-reference) (also: extension (patient-unmerge-original-source-reference)) | Extension | | Yes | 0..1 | A reference to the current FHIR ID of the unmerge event's source patient. URL: https://open.epic.com/FHIR/StructureDefinition/patient-unmerge-original-source-reference

Patient (R4).extension (patient-unmerge-source).extension (patient-unmerge-reference-old) (also: extension (patient-unmerge-reference-old)) | Extension | | Yes | 0..1 | A reference to the FHIR ID of the unmerge event's source patient at the time of the merge. URL: https://open.epic.com/FHIR/StructureDefinition/patient-unmerge-reference-old

Patient (R4).extension (patient-unmerge-target) (also: extension (patient-unmerge-target)) | Extension | | Yes | 0..* | This extension contains a collection of extensions that represent the metadata for a patient record unmerge from the perspective of the target patient. If the patient is involved as the target patient in multiple unmerges, this set of extensions is returned for each unmerge event. URL: https://open.epic.com/FHIR/StructureDefinition/patient-unmerge-target

Patient (R4).extension (patient-unmerge-target).extension (patient-merge-unmerge-instant) (also: extension (patient-merge-unmerge-instant)) | Extension | | Yes | 0..1 | The instant the patient merge event occurred. URL: https://open.epic.com/FHIR/StructureDefinition/patient-merge-unmerge-instant

Patient (R4).extension (patient-unmerge-target).extension (patient-unmerge-old-target-reference) (also: extension (patient-unmerge-old-target-reference)) | Extension | | Yes | 0..1 | A reference to the FHIR ID of the unmerge event's target patient at the time of the merge. URL: https://open.epic.com/FHIR/StructureDefinition/patient-unmerge-old-target-reference

Patient (R4).extension (patient-unmerge-target).extension (patient-unmerge-original-source-reference) (also: extension (patient-unmerge-original-source-reference)) | Extension | | Yes | 0..1 | A reference to the current FHIR ID of the unmerge event's source patient. URL: https://open.epic.com/FHIR/StructureDefinition/patient-unmerge-original-source-reference

Patient (R4).extension (patient-unmerge-target).extension (patient-unmerge-reference-new) (also: extension (patient-unmerge-reference-new)) | Extension | | Yes | 0..1 | A reference to the FHIR ID of the unmerge event's source patient after the unmerge. URL: https://open.epic.com/FHIR/StructureDefinition/patient-unmerge-reference-new

Patient (R4).extension (patient-unmerge-target).extension (patient-unmerge-reference-old) (also: extension (patient-unmerge-reference-old)) | Extension | | Yes | 0..1 | A reference to the FHIR ID of the unmerge event's source patient at the time of the merge. URL: https://open.epic.com/FHIR/StructureDefinition/patient-unmerge-reference-old

Patient (R4).extension (sex-for-clinical-use) (also: extension (sex-for-clinical-use)) | Extension | | Yes | 0..1 | The patient's sex for clinical decision making. This is an Epic-calculated value. If the patient's sex, gender, and clinical information indicate the patient is not unambiguously a cisgender male or female, the extension is not included. URL: http://open.epic.com/FHIR/StructureDefinition/extension/sex-for-clinical-use

Patient (R4).extension (us-core-ethnicity) (also: extension (us-core-ethnicity)) | Extension | | Yes | 0..1 | The patient's ethnicity parent extension. This element is not returned for organizations in the Netherlands or Singapore. For other organizations, the value returned depends on the mapping owned by the Epic organization. For organizations in the US, this mapping is typically based on regulatory standards set by the CDC. URL: http://hl7.org/fhir/us/core/StructureDefinition/us-core-ethnicity

Patient (R4).extension (us-core-ethnicity).extension (ombCategory) (also: extension (ombCategory)) | Extension | | Yes | 0..1 | The patient's ethnicity. URL: ombCategory

Patient (R4).extension (us-core-ethnicity).extension (text) (also: extension (text)) | Extension | | Yes | 0..1 | Textual display value for the OMB ethnicity code. The following mapping is used: OMB Ethnicity Code Text 2135-2 Hispanic or Latino 2186-5 Not Hispanic or Latino Default Value

Unknown URL: text

OMB Ethnicity Code | Text

2135-2 | Hispanic or Latino

2186-5 | Not Hispanic or Latino

Default Value | Unknown

Patient (R4).extension (us-core-genderIdentity) (also: extension (us-core-genderIdentity)) | Extension | | Yes | 0..1 | The patient’s gender identity URL: http://hl7.org/fhir/us/core/StructureDefinition/us-core-genderIdentity

Patient (R4).extension (us-core-race) (also: extension (us-core-race)) | Extension | | Yes | 0..1 | The patient's race. This element is not returned for organizations in the Netherlands or Singapore. For other organizations, the value returned depends on the mapping owned by the Epic organization. For organizations in the US, this mapping is typically based on regulatory standards set by the CDC. URL: http://hl7.org/fhir/us/core/StructureDefinition/us-core-race

Patient (R4).extension (us-core-race).extension (detailed) (also: extension (detailed)) | Extension | | Yes | 0..* | Detailed CDC race code. URL: detailed

Patient (R4).extension (us-core-race).extension (ombCategory) (also: extension (ombCategory)) | Extension | | Yes | 0..* | Race code according to the OMB race category valueset. URL: ombCategory

Patient (R4).extension (us-core-race).extension (text) (also: extension (text)) | Extension | | Yes | 0..* | Textual display value for the OMB race code. The following mapping is used: OMB Race Code Text 1002-5 American Indian or Alaska Native 2028-9 Asian 2054-5 Black or African American 2076-8 Native Hawaiian or Other Pacific Islander 2106-3 White 2131-1 Other Race Default Value Unknown URL: text

OMB Race Code | Text

1002-5 | American Indian or Alaska Native

2028-9 | Asian

2054-5 | Black or African American

2076-8 | Native Hawaiian or Other Pacific Islander

2106-3 | White

2131-1 | Other Race

Default Value | Unknown

Patient (R4).extension (us-core-sex) (also: extension (us-core-sex)) | Extension | | Yes | 0..1 | The patient’s most reliable sex for clinical decision making. If the patient's sex cannot be reliably determined, nothing is returned. URL: http://hl7.org/fhir/us/core/StructureDefinition/us-core-sex

Patient (R4).extension (us-core-tribal-affiliation) (also: extension (us-core-tribal-affiliation)) | Extension | | Yes | 0..1 | The patient’s tribal affiliation. URL: http://hl7.org/fhir/us/core/StructureDefinition/us-core-tribal-affiliation

Patient (R4).extension (us-core-tribal-affiliation).extension (tribalAffiliation) (also: extension (tribalAffiliation)) | Extension | | Yes | 0..1 | The patient's tribal affiliation code.

Patient (R4).gender | code | | | 1..1 | The patient's legal sex.

Patient (R4).generalPractitioner | Reference | | Yes | 0..* | The patient's Primary Care Provider (PCP). Reference to a Practitioner resource. For organizations in UK with EPS enabled at the system level, also contains an identifier-based reference to the patient's care organization.

Patient (R4).id | id | | | 1..1 | The Patient FHIR ID.

Patient (R4).identifier | Identifier | | Yes | 1..* | The patient's identifiers. Includes the following: MPI IDs (such as MRNs) Epic MyChart login IDs Epic database IDs Payer Member IDs National IDs FHIR ID Care Everywhere ID For organizations in Singapore, the patient’s document ID, type, and expiry date.

Patient (R4).identifier.period | Period | | | 0..1 | The expiration date of the patient's identification document in Singapore.

Patient (R4).identifier.system | String | | | 1..1 | Epic Identity IDs (such as Patient MRN) Identity ID OID Identity ID HL7 Assigning Authority as the "Text" value. Epic MyChart IDs MyChart login OID Epic Care Everywhere ID CEID Epic internal ID Generated OID for the Epic internal patient ID Epic external ID Generated OID for the Epic external patient ID Payer Member ID https://open.epic.com/FHIR/StructureDefinition/PayerMemberId National Identifier US Social Security Number: 2.16.840.1.113883.4.1 UK NHS ID: 2.16.840.1.113883.2.1.4.1 or https://fhir.nhs.uk/Id/nhs-number Dutch BSN: 2.16.840.1.113883.2.4.6.3 or http://fhir.nl/fhir/NamingSystem/bsn Finnish National ID: 1.2.246.21 United Arab Emirates: 2.16.840.1.113883.3.7326.10.1 Australian Medicare Number: http://ns.electronichealth.net.au/id/medicare-number Singapore Document ID https://open.epic.com/singapore/doc-id FHIR ID STU3 and up: http://open.epic.com/FHIR/StructureDefinition/patient-fhir-id DSTU2: http://open.epic.com/FHIR/StructureDefinition/patient-dstu2-fhir-id

Patient (R4).identifier.type | CodeableConcept | | | 0..1 | The patient's identifier type. In Singapore, this is the patient's identification document type.

Patient (R4).identifier.value | String | | | 1..1 | The patient's ID. For organizations in Singapore, this can also be the patient's identification document ID.

Patient (R4).identifier.value.extension (rendered-value) (also: extension (rendered-value)) | Extension | | Yes | | Contains the patient's masked national ID if the organization masks national identifiers. URL: http://hl7.org/fhir/StructureDefinition/rendered-value

Patient (R4).link | BackboneElement | | Yes | 0..* | Contains links to other patient records if the patient record was involved in a merge. Each link element represents a single merge event. If the patient was involved in multiple merges, multiple Link elements are returned. Starting in the February 2024 version of Epic, the 30 most recent merge events are returned instead of all merge events.

Patient (R4).link.extension (patient-merge-target-reference) (also: extension (patient-merge-target-reference)) | Extension | | Yes | 0..1 | The FHIR ID reference to the target patient. In a merge, the target patient refers to the surviving patient. URL: https://open.epic.com/FHIR/StructureDefinition/patient-merge-target-reference

Patient (R4).link.extension (patient-merge-unmerge-instant) (also: extension (patient-merge-unmerge-instant)) | Extension | | Yes | 0..1 | The instant the patient merge event occurred. URL: https://open.epic.com/FHIR/StructureDefinition/patient-merge-unmerge-instant

Patient (R4).link.other | Reference | | | 0..1 | A Patient reference to the source patient. In a merge, the source patient is the patient that goes away.

Patient (R4).link.type | code | | | 1..1 | The type of link between Patient resources. This is always set to "replaces". The Patient FHIR ID in the link.extension (patient-merge-target-reference) element replaces the Patient FHIR ID referenced in the link.other element.

Patient (R4).managingOrganization | Reference | | | 0..1 | The patient’s primary service area. Reference to an Organization resource.

Patient (R4).maritalStatus | CodeableConcept | | | 0..1 | The patient's marital status.

Patient (R4).meta | Meta | | | | Metadata about the resource.

Patient (R4).meta.security | Coding | | Yes | 0..2 | The patient’s unverified status. Available starting in the May 2024 version of Epic, and in February 2024 and November 2023 with special updates. This is used to track new patient records that might need to be reconciled against existing records in the system. The element is not returned for verified patients. Unverified patients always return the value PATRPT (Patient Reported) along with one of the following values: UNCERTAIN (Uncertain Reliability) UNRELIABLE (Unreliable)

Patient (R4).multipleBirthInteger | integer | | | 0..1 | The patient's birth order.

Patient (R4).name | HumanName | | Yes | 1..* | The patient's name.

Patient (R4).name.extension (humanNameAssemblyOrder) (also: extension (humanNameAssemblyOrder)) | Extension | | Yes | 0..* | This extension is populated only for organizations in the Netherlands. Name order for the contact. One of the following values: * NL1-Own Name * NL2-Partner

Name * NL3-Partner Name followed by Maiden Name * NL4-Own Name followed by Partner Name URL: http://hl7.org/fhir/StructureDefinition/humanname-assembly-order

Patient (R4).name.family | string | | | 1..1 | The patient's family (last) name. Can contain a data-absent-reason extension with a value of "unknown" if the patient has an alias that cannot be returned as discrete elements or if the patient's preferred name replaces their full name.

Patient (R4).name.family.extension (data-absent-reason) (also: extension (data-absent-reason)) | Extension | | Yes | 0..1 | Returned as "unknown" for patients without family names.

Patient (R4).name.family.extension (humanNameOwnName) (also: extension (humanNameOwnName)) | Extension | | Yes | 0..1 | The portion of a patient's family name derived from the patient's own name.

Patient (R4).name.family.extension (humanNameOwnPrefix) (also: extension (humanNameOwnPrefix)) | Extension | | Yes | 0..1 | The prefix portion of a patient's family name derived from the patient's own surname.

Patient (R4).name.family.extension (humanNamePartnerName) (also: extension (humanNamePartnerName)) | Extension | | Yes | 0..1 | The portion of a patient's family name derived from the patient's partner's name.

Patient (R4).name.family.extension (humanNamePartnerPrefix) (also: extension (humanNamePartnerPrefix)) | Extension | | Yes | 0..1 | The prefix portion of a patient's family name derived from the patient's partner's surname.

Patient (R4).name.given | string | | Yes | 1..* | The patient's given name. Can include first and middle names.

Patient (R4).name.given.extension (namePartQualifier) (also: extension (namePartQualifier)) | Extension | | Yes | 0..2 | This extension is returned if initials or a preferred name are present. The entity qualifier extension code is IN for initials and is CL for preferred name. URL: http://hl7.org/fhir/StructureDefinition/iso21090-EN-qualifier

Patient (R4).name.prefix | string | | Yes | 0..1 | The patient's name prefix.

Patient (R4).name.suffix | string | | Yes | 0..* | The patient's name suffix. Acquired as a title due to academic, legal, employment or nobility status, etc.

Patient (R4).name.text | string | | | 1..1 | The patient's full name as a string.

Patient (R4).name.use | code | | | 1..1 | The purpose of the name. Can be "official", "usual", or "old".

Patient (R4).telecom | ContactPoint | | Yes | 0..* | Telephone numbers and email addresses for the patient, along with their use (home or work for example) and their preferred rank (which to contact first, second, third, etc).

Patient (R4).telecom.rank | positiveInt | | | 0..1 | The priority for permanent phone numbers or emails. 1 indicates the highest priority phone number, 2 indicates the second priority, etc . The preferred has a rank of 1. Additional emails have a null rank.

Patient (R4).telecom.system | code | | | 1..1 | The type of telecom. Potential values are: email phone fax url pager sms other

Patient (R4).telecom.use | code | | | 0..1 | If the telecom entry is a phone number, possible values are: home mobile work temp old Use is not returned for emails.

Patient (R4).telecom.value | string | | | 1..1 | Value of the telecom method. Can be an email address or phone number.

Sample request

```
POST https://hostname/instance/api/FHIR/R4/Patient/$match
{
  "resourceType": "Parameters",
  "parameter": [
    {
      "name": "resource",
      "resource": {
        "resourceType": "Patient",
        "name": [
          {
            "family": "Doe",
            "given": [
              "John"
            ]
          }
        ],
        "birthDate": "2001-01-01",
        "telecom": [
          {
            "system": "phone",
            "value": "111-444-5555",
            "use": "home"
          },
          {
            "system": "phone",
            "value": "111-666-7777",
            "use": "work"
          }
        ],
        "address": [
          {
            "line": [
              "123 Snowy Street"
            ],
            "city": "Buffalo",
            "district": "ERIE",
            "state": "NY",
            "postalCode": "14217",
            "country": "USA"
          }
        ]
      }
    },
    {
      "name": "onlyCertainMatches",
      "valueBoolean": "true"
    }
  ]
}
```

Sample response


```
Status code: OK (200)
Status description: OK
Content-Type: application/json; charset=utf-8
{
    "resourceType": "Bundle",
    "type": "searchset",
    "total": 1,
    "link": [
        {
            "relation": "self",
            "url": "https://hostname/instance/api/FHIR/R4/Patient/$match"
        }
    ],
    "entry": [
        {
            "link": [
                {
                    "relation": "self",
                    "url": "https://hostname/instance/api/FHIR/R4/Patient/e0dkfe0Q2inYOZe3gAt.ltw3"
                }
            ],
            "fullUrl": "https://hostname/instance/api/FHIR/R4/Patient/e0dkfe0Q2inYOZe3gAt.ltw3",
            "resource": {
                "resourceType": "Patient",
                "id": "e0dkfe0Q2inYOZe3gAt.ltw3",
                "extension": [
                    {
                        "extension": [
                            {
                                "valueCoding": {
                                    "system": "http://terminology.hl7.org/CodeSystem/v3-NullFlavor",
                                    "code": "UNK",
                                    "display": "Unknown"
                                },
                                "url": "ombCategory"
                            },
                            {
                                "valueString": "Unknown",
                                "url": "text"
                            }
                        ],
                        "url": "http://hl7.org/fhir/us/core/StructureDefinition/us-core-race"
                    },
                    {
                        "extension": [
                            {
                                "valueString": "Unknown",
                                "url": "text"
                            }
                        ],
                        "url": "http://hl7.org/fhir/us/core/StructureDefinition/us-core-ethnicity"
                    },
                    {
                        "valueCodeableConcept": {
                            "coding": [
                                {
                                    "system": "urn:oid:1.2.840.114350.1.13.5325.1.7.10.698084.130.768080.39128",
                                    "code": "nonbinary",
                                    "display": "nonbinary"
                                }
                            ]
                        },
                        "url": "http://open.epic.com/FHIR/StructureDefinition/extension/legal-sex"
                    },
                    {
                        "valueCodeableConcept": {
                            "coding": [
                                {
                                    "system": "http://hl7.org/fhir/gender-identity",
                                    "code": "other",
                                    "display": "other"
                                }
                            ]
                        },
                        "url": "http://hl7.org/fhir/StructureDefinition/patient-genderIdentity"
                    },
                    {
                        "valueCode": "M",
                        "url": "http://hl7.org/fhir/us/core/StructureDefinition/us-core-birthsex"
                    }
                ],
                "identifier": [
                    {
                        "use": "usual",
                        "system": "urn:oid:2.16.840.1.113883.4.1",
                        "value": "999-99-9999"
                    },
```

```
        {
            "use": "usual",
            "type": {
                "text": "CEID"
            },
            "system": "urn:oid:1.2.840.114350.1.13.5325.1.7.3.688884.100",
            "value": "YE17SGM0XNVJFSV"
        },
        {
            "use": "usual",
            "type": {
                "text": "EPI"
            },
            "system": "urn:oid:1.2.840.114350.1.1",
            "value": "111068"
        },
        {
            "use": "usual",
            "type": {
                "text": "EXTERNAL"
            },
            "system": "urn:oid:1.2.840.114350.1.13.5325.1.7.2.698084",
            "value": "Z13369"
        },
        {
            "use": "usual",
            "type": {
                "text": "FHIR"
            },
            "system": "http://open.epic.com/FHIR/StructureDefinition/patient-dstu2-fhir-id",
            "value": "TlW7mv5GwjlSpZuvIbExVec-QRIghh6zEq8Q2nYt89boB"
        },
        {
            "use": "usual",
            "type": {
                "text": "FHIR STU3"
            },
            "system": "http://open.epic.com/FHIR/StructureDefinition/patient-fhir-id",
            "value": "e0dkfe0Q2inYOZe3gAt.ltw3"
        },
        {
            "use": "usual",
            "type": {
                "text": "INTERNAL"
            },
            "system": "urn:oid:1.2.840.114350.1.13.5325.1.7.2.698084",
            "value": "    Z13369"
        },
        {
            "use": "usual",
            "type": {
                "text": "Custom Identifier Type"
            },
            "system": "urn:oid:1.2.840.114350.1.13.5325.1.7.5.737384.1398",
            "value": "3006340"
        },
        {
            "use": "usual",
            "type": {
                "text": "WPRINTERNAL"
            },
            "system": "urn:oid:1.2.840.114350.1.13.5325.1.7.2.878082",
            "value": "16888"
        }
    ],
    "active": true,
    "name": [
        {
            "use": "official",
            "text": "John Middlename Doe",
            "family": "Doe",
            "given": [
                "John",
                "Middlename"
            ]
        },
        {
            "use": "usual",
            "text": "John Middlename Doe",
            "family": "Doe",
            "given": [
                "John",
                "Middlename"
            ]
        }
    ],
    "telecom": [
        {
            "system": "phone",
```

```
                    "value": "111-444-5555",
                    "use": "home"
                },
                {
                    "system": "phone",
                    "value": "111-666-7777",
                    "use": "work"
                }
            ],
            "gender": "other",
            "birthDate": "2001-01-01",
            "deceasedBoolean": false,
            "address": [
                {
                    "use": "old",
                    "line": [
                        "123 Sesame Street"
                    ],
                    "city": "Buffalo",
                    "district": "ERIE",
                    "state": "NY",
                    "postalCode": "14217",
                    "country": "USA"
                },
                {
                    "use": "home",
                    "line": [
                        "123 Snowy Street"
                    ],
                    "city": "Buffalo",
                    "district": "ERIE",
                    "state": "NY",
                    "postalCode": "14217",
                    "country": "USA"
                }
            ],
            "communication": [
                {
                    "language": {
                        "coding": [
                            {
                                "system": "urn:ietf:bcp:47",
                                "code": "en",
                                "display": "English"
                            }
                        ],
                        "text": "English"
                    },
                    "preferred": true
                },
                {
                    "language": {
                        "coding": [
                            {
                                "system": "urn:ietf:bcp:47",
                                "code": "es",
                                "display": "Spanish"
                            }
                        ],
                        "text": "Spanish"
                    }
                }
            ],
            "generalPractitioner": [
                {
                    "reference": "Practitioner/ekk17eu0BAPwHQ6s2NDWYEQ3",
                    "type": "Practitioner",
                    "display": "Dotty Doctor"
                }
            ],
            "managingOrganization": {
                "reference": "Organization/ePioZEeqCYv.F5W96swOaXA3",
                "display": "Happy Healthcare Management"
            }
        },
        "search": {
            "extension": [
                {
                    "valueCode": "certain",
                    "url": "http://hl7.org/fhir/StructureDefinition/match-grade"
                }
            ],
            "mode": "match",
            "score": 1
        }
    }
  ]
}
```

Change log

Epic Version | Description | Type
May 2023 | Allow searching for patient records using only demographics the associated user has security to access in the response. | Breaking change

22.1.2 Patient.Create (Demographics) (R4)

File: site/apis/22-Identification-Individuals/1-R4/930-Patient-Create-Demographics-R4.html
Epic API ID | 930
FHIR version | R4
Categories | Identification Individuals, Workflow Patient Management
API type | Industry-Standard
USCDI | No
ONC certification products | EpicCare Ambulatory Base, EpicCare Inpatient Base
ONC certification versions | August 2019
HTTP method | POST
URL template | api/FHIR/R4/Patient
Supports OAuth 2.0 | True
Supported user types | Backend Systems and Non-OAuth 2.0, Clinicians or Administrative Users
Performs scope validation | False
Source | https://fhir.epic.com/Specifications?api=930

Description

The FHIR Patient resource defines demographics, care providers, and other administrative information about a person receiving care at a healthcare organization. The Patient.Create web service uses the following logic to determine whether a new patient should be created or an existing one should be returned:

* If a patient is found using a provided identifier, and that patient passes demographic validation based on provided demographics, the matching patient is returned.

* If no identifier is provided, and a single high confidence match is found based on provided demographics, the matching patient is returned.

* If the Epic environment uses an external EMPI, and a match is found using an external EMPI query, then a shell patient is created in the environment and returned.

* If no matches are found, a single low-threshold match is found, or multiple high-threshold or low-threshold matches are found, a net new patient is created and returned.

Organizations in the Netherlands:

Patient.Create is not currently supported for organizations in the Netherlands, because Epic doesn't support submitting given name initials in the request body.

The response of a Create depends on the Prefer header:

Prefer: return=minimal

returns the full URL to the resource in the Location header.

Prefer: return=representation

returns both the full URL to the resource in the Location header, as well as the full FHIR resource in the response body.

Request parameters

Name | Type | Optional | Array | Cardinality | Description
Patient (R4) | Resource | | | | A single instance of a Patient FHIR resource.
Patient (R4).active | boolean | | | 0..1 | Whether the patient record is active. This is always True. Creating inactive patients is not supported.
Patient (R4).address | Address | | Yes | 0..1 | Addresses for the patient. Only supports filing the home address.
Patient (R4).address.city | string | | | 1..1 | The city that the patient lives in.
Patient (R4).address.country | String | | | 0..1 | The country that the patient lives in.
Patient (R4).address.line | string | | Yes | 1..* | The patient’s street address, in array format.
Patient (R4).address.line.extension (additionalLocator) (also: extension (additionalLocator)) | Extension | | Yes | 0..1 | The patient’s floor. For organizations in Singapore only.
Patient (R4).address.line.extension (additionalLocator).url | uri | | | 1..1 | Must be: http://hl7.org/fhir/StructureDefinition/iso21090-ADXP-additionalLocator
Patient (R4).address.line.extension (additionalLocator).valueString | string | | | 1..1 | Element containing the value for the additionalLocator extension.
Patient (R4).address.line.extension (buildingName) (also: extension (buildingName)) | Extension | | Yes | 0..1 | The patient’s building name. For organizations in Singapore only.
Patient (R4).address.line.extension (buildingName).url | uri | | | 1..1 | Must be: http://open.epic.com/FHIR/StructureDefinition/extension/buildingName
Patient (R4).address.line.extension (buildingName).valueString | string | | | 1..1 | Element containing the value of the buildingName extension.
Patient (R4).address.line.extension (houseNumber) (also: extension (houseNumber)) | Extension | | Yes | 0..1 | This element represents the portion of a patient's address that is their house number. For organizations in Singapore only.
Patient (R4).address.line.extension (houseNumber).url | uri | | | 1..1 | Must be: http://hl7.org/fhir/StructureDefinition/iso21090-ADXP-houseNumber
Patient (R4).address.line.extension (houseNumber).valueString | string | | | 1..1 | Element containing the value for the houseNumber extension.

Patient (R4).address.line.extension (streetName) (also: extension (streetName)) | Extension | | Yes | 0..* | This element represents the portion of a patient's address that includes the name of their street. For organizations in Singapore only.

Patient (R4).address.line.extension (streetName).url | uri | | | 1..1 | Must be: http://hl7.org/fhir/StructureDefinition/iso21090-ADXP-streetName

Patient (R4).address.line.extension (streetName).valueString | string | | | 1..1 | Element containing the value of the streetName extension.

Patient (R4).address.line.extension (unitID) (also: extension (unitID)) | Extension | | Yes | 0..1 | The patient's unit number. For organizations in Singapore only.

Patient (R4).address.line.extension (unitID).url | uri | | | 1..1 | Must be: http://hl7.org/fhir/StructureDefinition/iso21090-ADXP-unitID

Patient (R4).address.line.extension (unitID).valueString | string | | | 1..1 | Element containing the value for the unitID extension.

Patient (R4).address.period | Period | | | 0..1 | The effective date for the address.

Patient (R4).address.period.start | String | | | 0..1 | The start date for the address. If not set, today's date is used.

Patient (R4).address.postalCode | string | | | 0..1 | The patient's ZIP Code. Format depends on locale. For US addresses either of the following formats are supported: * nnnnn * nnnnn-nnnn

Patient (R4).address.state | string | | | 0..1 | The state where the patient lives. Either enter the two-letter postal abbreviation for the state or the state's numeric value. The numeric value is assigned alphabetically where District of Columbia is 9 and Wyoming is 51.

Patient (R4).address.use | code | | | 0..1 | A use of "home" is supported. Addresses with other uses are ignored.

Patient (R4).birthDate | date | | | 0..1 | The patient's date of birth in the format YYYY-MM-DD.

Patient (R4).deceasedBoolean | boolean | | | 0..1 | Whether the patient is deceased. Only a value of "False" is supported.

Patient (R4).extension (legal-sex) (also: extension (legal-sex)) | Extension | | Yes | 0..1 | The patient's legal sex. Represented by a valueCodeableConcept object.

Patient (R4).extension (legal-sex).url | uri | | | 1..1 | Must be: http://open.epic.com/FHIR/StructureDefinition/extension/legal-sex

Patient (R4).extension (legal-sex).valueCodeableConcept | CodeableConcept | | | 1..1 | The valueCodeableConcept object container for the legal-sex extension.

Patient (R4).extension (legal-sex).valueCodeableConcept.coding | Coding | | Yes | 1..1 | The coding object container for the legal-sex extension. All children of the coding object aside from code is ignored.

Patient (R4).extension (legal-sex).valueCodeableConcept.coding.code | String | | | 1..1 | The coded value of the legal-sex extension.

Patient (R4).extension (patient-genderIdentity) (also: extension (patient-genderIdentity)) | Extension | | Yes | 0..1 | The patient's gender identity. Defined by a valueCodeableConcept object.

Patient (R4).extension (patient-genderIdentity).url | uri | | | 1..1 | Must be: http://hl7.org/fhir/StructureDefinition/patient-genderIdentity

Patient (R4).extension (patient-genderIdentity).valueCodeableConcept | CodeableConcept | | | 1..1 | The valueCodeableConcept object container for the patient-genderIdentity extension.

Patient (R4).extension (patient-genderIdentity).valueCodeableConcept.coding | Coding | | Yes | 1..1 | The coding object container for the patient-genderIdentity extension. All children of the coding object aside from code is ignored.

Patient (R4).extension (patient-genderIdentity).valueCodeableConcept.coding.code | String | | | 1..1 | The coded value of the patient-genderidentity extension.

Patient (R4).extension (patient-nationality) (also: extension (patient-nationality)) | Extension | | Yes | 0..1 | The patient's nationality, represented by a valueCodeableConcept object. For organizations in Singapore only.

Patient (R4).extension (patient-nationality).url | uri | | | 1..1 | Must be: http://hl7.org/fhir/StructureDefinition/patient-nationality

Patient (R4).extension (patient-nationality).valueCodeableConcept | CodeableConcept | | | 1..1 | The valueCodeableConcept object container for the patient-nationality extension.

Patient (R4).extension (patient-nationality).valueCodeableConcept.coding | Coding | | Yes | 1..1 | The coding object container for the patient-nationality extension. All children of the coding object aside from code is ignored.

Patient (R4).extension (patient-nationality).valueCodeableConcept.coding.code | String | | | | The coded value of the patient-nationality extension.

Patient (R4).extension (patient-preferred-provider-language) (also: extension (patient-preferred-provider-language)) | Extension | | Yes | 0..1 | The patient's preferred provider language, used for scheduling.

Patient (R4).extension (patient-preferred-provider-language).url | uri | | | | Must be: http://open.epic.com/FHIR/STU3/StructureDefinition/patient-preferred-provider-language

Patient (R4).extension (patient-preferred-provider-language).valueCodeableConcept | CodeableConcept | | | 1..1 | The valueCodeableConcept object container for the patient-preferred-provider-language.

Patient (R4).extension (patient-preferred-provider-language).valueCodeableConcept.text | String | | | 1..1 | The textual value for the patient-preferred-provider-language extension.

Patient (R4).extension (patient-preferred-provider-sex) (also: extension (patient-preferred-provider-sex)) | Extension | | Yes | 0..1 | The patient's preferred provider sex, used for scheduling.

Patient (R4).extension (patient-preferred-provider-sex).url | uri | | | 1..1 | Must be: http://open.epic.com/FHIR/STU3/StructureDefinition/patient-preferred-provider-sex

Patient (R4).extension (patient-preferred-provider-sex).valueCode | code | | | 0..1 | The value for the patient's preferred provider sex.

Patient (R4).extension (patient-race) (also: extension (patient-race)) | Extension | | Yes | 0..* | The patient's race, represented by a valueCodeableConcept object. For organizations in Singapore only.

Patient (R4).extension (patient-race).url | uri | | | 1..1 | Must be: http://open.epic.com/FHIR/StructureDefinition/extension/patient-race

Patient (R4).extension (patient-race).valueCodeableConcept | CodeableConcept | | | 1..1 | The valueCodeableConcept object container for the patient-race extension.

Patient (R4).extension (patient-race).valueCodeableConcept.coding | Coding | | Yes | 1..1 | The coding object container for the patient-race extension. All children of the coding object aside from code is ignored.

Patient (R4).extension (patient-race).valueCodeableConcept.coding.code | String | | | 1..1 | The coded value for the patient-race extension.

Patient (R4).gender | code | | | 0..1 | The patient's legal sex.

Patient (R4).generalPractitioner | Reference | | Yes | 0..* | The patient's primary care provider (PCP). Reference to a Practitioner resource with a FHIR ID.

Patient (R4).identifier | Identifier | | Yes | 0..* | Unique IDs assigned to the patient. Can include MPI IDs, Care Everywhere ID, National Identifiers, and Singapore Document ID. For Finland, Denmark, and UK customers additional configuration is required by each Epic organization to file these identifiers.

Patient (R4).identifier.period | Period | | | 0..1 | In Singapore, this is the expiration date of the patient's identification document.

Patient (R4).identifier.system | String | | | 1..1 | Epic MPI IDs (e.g. Patient MRN) MPI ID Type OID Epic Care Everywhere ID CEID National Identifier US Social Security Number: 2.16.840.1.113883.4.1 UK NHS ID: 2.16.840.1.113883.2.1.4.1 Dutch BSN: 2.16.840.1.113883.2.4.6.3 or http://fhir.nl/fhir/NamingSystem/bsn Finnish National ID: 1.2.246.21 Australian Medicare Number: http://ns.electronichealth.net.au/id/medicare-number Singapore Document ID https://open.epic.com/singapore/doc-id

Patient (R4).identifier.type | CodeableConcept | | | 0..1 | The patient's identifier type. In Singapore, this is the patient's identification document type.

Patient (R4).identifier.value | String | | | 1..1 | The patient's ID. In Singapore, this is the patient's identification document ID.

Patient (R4).maritalStatus | CodeableConcept | | | 0..1 | The patient’s marital status. Accepted codes depend on build at the organization and typically follow the FHIR MaritalStatus value set.

Patient (R4).name | HumanName | | Yes | 1..1 | The patient's name. When submitting a create request, all names are treated as official names. Preferred names are not supported for create.

Patient (R4).name.family | string | | | 1..1 | The patient's family (last) name.

Patient (R4).name.given | string | | Yes | 1..2 | The patient's given name, in array format. May include first and middle names. When submitting a create request, only a single given and middle name are supported. Additional entries beyond the first two entries in the name.given array are ignored.

Patient (R4).name.prefix | string | | Yes | 0..1 | The patient's name prefix, in array format. When submitting a create request, last name prefixes and academic titles are not supported. Only the first value in the name.prefix array is used.

Patient (R4).name.suffix | string | | Yes | 0..1 | The patient's name suffix, in array format. Only the first value in the name.suffix array is used.

Patient (R4).name.use | code | | | 0..1 | The purpose of the name. Accepted values are "official" and "usual". When submitting a create request, all names are treated as official names. Preferred names are not supported for create.

Patient (R4).telecom | ContactPoint | Optional | Yes | 0..* | Telephone numbers and email addresses for the patient.

Patient (R4).telecom.system | code | | | 0..1 | The type of telecom. Supported values are: * email * phone This value may be null for email addresses.

Patient (R4).telecom.use | code | | | 0..1 | If the telecom entry is a phone number, supported values are: * home * mobile * work This value may be null for email addresses.

Patient (R4).telecom.value | string | | | 1..1 | Value of the telecom method. May be an email address or phone number. If the value is a valid email address, it is filed as an email regardless of the telecom.system value.

Response elements

Name | Type | Optional | Array | Cardinality | Description

Patient (R4) | Resource

Patient (R4).active | boolean | | | 1..1 | Whether the patient record is active.

Patient (R4).address | Address | | Yes | 0..* | The patient's current address, as well as any previous or temporary addresses, if applicable. The patient's current address has a use code of "home". If the patient also has one or more previous addresses, each previous address has a use code of "old". The patient's temporary address has a use code of "temp".

Patient (R4).address.city | string | | | 0..1 | The city that the patient lives in.

Patient (R4).address.country | String | | | 0..1 | The country that the patient lives in.

Patient (R4).address.district | String | | | 0..1 | The county that the patient lives in.

Patient (R4).address.line | string | | Yes | 0..* | The patient’s street address.

Patient (R4).address.line.extension (additionalLocator) (also: extension (additionalLocator)) | Extension | | Yes | 0..1 | This extension is returned only for organizations in Singapore. The patient’s floor. URL: http://hl7.org/fhir/StructureDefinition/iso21090-ADXP-additionalLocator

Patient (R4).address.line.extension (buildingName) (also: extension (buildingName)) | Extension | | Yes | 0..1 | This extension is returned only for organizations in Singapore. The patient’s building name. URL: http://open.epic.com/FHIR/StructureDefinition/extension/buildingName

Patient (R4).address.line.extension (houseNumber) (also: extension (houseNumber)) | Extension | | Yes | 0..1 | For organizations in the Netherlands and Singapore, this element represents the portion of a patient or contact’s address that is their house number. URL: http://hl7.org/fhir/StructureDefinition/iso21090-ADXP-houseNumber

Patient (R4).address.line.extension (streetName) (also: extension (streetName)) | Extension | | Yes | 0..* | For organizations in the Netherlands and Singapore, this element represents the portion of a patient or contact’s address that includes the name of their street. URL: http://hl7.org/fhir/StructureDefinition/iso21090-ADXP-streetName

Patient (R4).address.line.extension (unitID) (also: extension (unitID)) | Extension | | Yes | 0..1 | This extension is returned only for organizations in Singapore. The patient’s unit number. URL: http://hl7.org/fhir/StructureDefinition/iso21090-ADXP-unitID

Patient (R4).address.period | Period | | | 0..1 | The start date – and optionally, end date – for when the address is valid. Returned for the current address if the information is available. Starting in the May 2025 version of Epic, also returned for previous and temporary addresses if the information is available.

Patient (R4).address.postalCode | string | | | 0..1 | The patient’s postal code.

Patient (R4).address.state | string | | | 0..1 | The state where the patient lives.

Patient (R4).address.text | String | | | 0..1 | The patient’s full address as a string. This is formatted based on the country the address is in. For U.S. addresses, to meet the standards laid out in the Project US@ Technical Specifications, patient addresses format automatically for patient matching purposes.

Patient (R4).address.use | code | | | 1..1 | Specifies the type of address: home – A permanent address old – A previous permanent address temp – A temporary address Temporary addresses behavior varies by Epic version: May 2025 or later – Returned only if the Epic organization has configured temporary addresses to be visible in FHIR responses (applies to all locales). Prior to May 2025 – Singapore – Always returned. Norway – Always returned if using: August 2024 version, or May 2024 version with special updates.

Patient (R4).birthDate | date | | | 1..1 | The patient's date of birth in the format YYYY-MM-DD

Patient (R4).birthDate.extension (birthTime) (also: extension (birthTime)) | Extension | | | 0..1 | The patient's time of birth. This extension follows the HL7 birthTime specification. Prior to the November 2023 verison of Epic, this extension was returned at the Patient resource level. Beginning in the November 2023 version of Epic, this is now returned underneath the BirthDate element. URL: http://hl7.org/fhir/StructureDefinition/patient-birthTime

Patient (R4).birthDate.extension (dataAbsentReason) (also: extension (dataAbsentReason)) | Extension | | | 0..1 | Available starting with the November 2024 version of Epic. If the patient’s birth date is not recorded, this extension is returned with a value of "unknown". URL: http://hl7.org/fhir/StructureDefinition/data-absent-reason

Patient (R4).communication | BackboneElement | | Yes | 0..* | Languages used to communicate with the patient, along with an indicator of which is preferred.

Patient (R4).communication.extension (comment) (also: extension (comment)) | Extension | | Yes | 0..1 | A comment about the patient's language proficiency. This extension is returned only for organizations in the Netherlands. URL: http://nictiz.nl/fhir/StructureDefinition/Comment

Patient (R4).communication.extension (patient-proficiency) (also: extension (patient-proficiency)) | Extension | | Yes | 0..3 | Container extension that holds details about the patient's language proficiency. Contains two child extensions which indicate the type of language proficiency and the level of that proficiency. This extension is returned only for organizations in the Netherlands. URL: http://nictiz.nl/fhir/StructureDefinition/patient-proficiency

Patient (R4).communication.extension (patient-proficiency).extension (v3-LanguageAbilityMode) (also: extension (v3-LanguageAbilityMode)) | Extension | | Yes | 0..1 | Patient's language proficiency type. This is a valueCoding wherein the following code and display values are supported: RSP - Received spoken ESP - Expressed spoken RWR - Received written System value of http://terminology.hl7.org/CodeSystem/v3-LanguageAbilityMode URL: type

Patient (R4).communication.extension (patient-proficiency).extension (v3-LanguageAbilityProficiency) (also: extension (v3-LanguageAbilityProficiency)) | Extension | | Yes | 0..1 | Patient's language proficiency level. This is a valueCoding wherein the following code and display values are supported: E - Excellent G - Good F - Fair P - Poor System value of http://terminology.hl7.org/CodeSystem/v3-LanguageAbilityProficiency URL: level

Patient (R4).communication.language | CodeableConcept | | | 1..1 | The patient's general language, onsite care language, and spoken language.

Patient (R4).communication.preferred | boolean | | | 0..1 | Whether the language is the patient's preferred language.

Patient (R4).communication.preferred.extension (patient-preferenceType) (also: extension (patient-preferenceType)) | Extension | | Yes | 0..1 | The preferred mode of communication for the patient's preferred language. This can be either verbal or written. Returned starting in the May 2025 version of Epic. Returned with system http://hl7.org/fhir/language-preference-type. URL: http://hl7.org/fhir/StructureDefinition/patient-preferenceType

Patient (R4).contact | BackboneElement | | Yes | 0..* | Details for the patient's contacts. Patient contacts include any documented family members, emergency contacts, care givers, acquaintances, and employers.

Patient (R4).contact.address | Address | | | 0..1 | The contact address. For responses to a patient-facing application, this element is not returned for contacts linked to a patient record. For organizations in the Netherlands, this element represents an nl-core-address value.

Patient (R4).contact.name | HumanName | | | 1..1 | The contact's preferred name. The system determines this from the contact's linked patient record if available. For contacts linked to a patient record, only the patient's official first name is returned in patient context. For organizations in the Netherlands, this element represents an nl-core-humanname value.

Patient (R4).contact.name.extension (humanname-assembly-order) (also: extension (humanname-assembly-order)) | Extension | | Yes | 0..1 | This extension is populated only for organizations in the Netherlands. Name order for the contact. One of the following values: NL1 - Own Name NL2 - Partner Name NL3 - Partner Name followed by Maiden Name NL4 - Own Name followed by Partner Name URL: http://hl7.org/fhir/StructureDefinition/humanname-assembly-order

Patient (R4).contact.organization | Reference | | | 0..1 | An Organization reference that represents the patient's employer. Returned when contact.relationship.code is E.

Patient (R4).contact.period | Period | | | 0..1 | The start and end dates for the patient contact.

Patient (R4).contact.relationship | CodeableConcept | | Yes | 0..* | The contact's relationship to the patient. This element can return multiple values. It will always return one or more Epic category values for the contact's relationship to the patient. In addition, it can return one or more of the following: For organizations in the Netherlands, either a Relationship (RelatieCodelijst) code system value or a role (RolCodelijst) code system value. For all other organizations, can return either a code system value – such as "C" (emergency contact) or "E" (employer) – or a RoleClass code system value – such as "GUARD" or "AGNT".

Patient (R4).contact.telecom | ContactPoint | | Yes | 0..* | Telephone numbers and email address for the contact. For responses to a patient-facing application, this element is not returned for contacts linked to a patient record. For organizations in the Netherlands, this element represents an nl-core-contactpoint value.

Patient (R4).contact.telecom.rank | positiveInt | | | 0..1 | The priority for permanent phone numbers or emails. 1 indicates the highest priority phone number, 2 indicates the second priority, and so on. Starting in the May 2025 version of Epic, rank is returned for the phone numbers of patient contacts.

Patient (R4).contact.telecom.system | code | | | 0..1 | The type of telecom. Potential values are: email phone

Patient (R4).contact.telecom.use | code | | | 0..1 | If the telecom entry is a phone number, possible values are: home mobile work

Patient (R4).contact.telecom.value | string | | | 1..1 | Value of the telecom method. Can be an email address or phone number.

Patient (R4).deceasedBoolean | boolean | | | 0..1 | Whether the patient is deceased.

Patient (R4).deceasedDateTime | dateTime | | | 0..1 | The date and time of death.

Patient (R4).extension (birth-location) (also: extension (birth-location)) | Extension | | Yes | 0..1 | A reference to a newborn's birth facility. URL: http://open.epic.com/FHIR/StructureDefinition/extension/birth-location

Patient (R4).extension (birth-sex) (also: extension (birth-sex)) | Extension | | Yes | 0..1 | The patient's sex assigned at birth. This element is not returned for organizations in the Netherlands. URL: http://hl7.org/fhir/us/core/StructureDefinition/us-core-birthsex

Patient (R4).extension (calculated-pronouns-to-use-for-text) (also: extension (calculated-pronouns-to-use-for-text)) | Extension | | Yes | 0..* | The patient's pronouns to use when generating text. Available starting in the November 2023 version of Epic. This is an Epic-calculated value based on specified pronouns, the patient's gender identity, or the patient's legal sex. Consider using extension (individual-pronouns) instead of this one. One of the following: A value from LOINC Answer List LL5144-2 Personal pronouns EP-PS-DO-NOT-USE-PRONOUNS, from the Epic-defined pronoun set https://open.epic.com/FHIR/Epic/pronoun-set URL: http://open.epic.com/FHIR/StructureDefinition/extension/calculated-pronouns-to-use-for-text

Patient (R4).extension (gender-identity) (also: extension (gender-identity)) | Extension | | Yes | 0..1 | The patient's gender identity. URL: http://hl7.org/fhir/StructureDefinition/patient-genderIdentity

Patient (R4).extension (individual-pronouns) (also: extension (individual-pronouns)) | Extension | | Yes | 0..* | The pronouns to use when communicating about an individual. Available starting in the November 2024 version of Epic. URL: http://hl7.org/fhir/StructureDefinition/individual-pronouns

Patient (R4).extension (legal-sex) (also: extension (legal-sex)) | Extension | | Yes | 0..1 | The patient's legal sex. URL: http://open.epic.com/FHIR/StructureDefinition/extension/legal-sex

Patient (R4).extension (nationality) (also: extension (nationality)) | Extension | | Yes | 0..1 | The patient's nationality. This extension is returned only for organizations in the Singapore. URL: http://hl7.org/fhir/StructureDefinition/patient-nationality

Patient (R4).extension (patient-preferred-provider-language) (also: extension (patient-preferred-provider-language)) | Extension | | Yes | 0..1 | The patient's preferred provider language, used for scheduling. URL: http://open.epic.com/FHIR/STU3/StructureDefinition/patient-preferred-provider-language

Patient (R4).extension (patient-preferred-provider-sex) (also: extension (patient-preferred-provider-sex)) | Extension | | Yes | 0..1 | The patient's preferred provider sex, used for scheduling. URL: http://open.epic.com/FHIR/STU3/StructureDefinition/patient-preferred-provider-sex

Patient (R4).extension (patient-type) (also: extension (patient-type)) | Extension | | Yes | 0..* | The type of patient, such as Confidential or Employee. URL: http://open.epic.com/FHIR/StructureDefinition/extension/patient-type

Patient (R4).extension (patient-unmerge-source) (also: extension (patient-unmerge-source)) | Extension | | Yes | 0..* | This extension contains a collection of extensions that represent the metadata for a patient record unmerge from the perspective of the source patient. If the patient is involved as the source patient in multiple unmerges, this set of extensions is returned for each unmerge event. URL: https://open.epic.com/FHIR/StructureDefinition/patient-unmerge-source

Patient (R4).extension (patient-unmerge-source).extension (patient-merge-unmerge-instant) (also: extension (patient-merge-unmerge-instant)) | Extension | | Yes | 0..1 | The instant the patient merge event occurred. URL: https://open.epic.com/FHIR/StructureDefinition/patient-merge-unmerge-instant

Patient (R4).extension (patient-unmerge-source).extension (patient-unmerge-current-target-reference) (also: extension (patient-unmerge-current-target-reference)) | Extension | | Yes | 0..1 | A reference to the current FHIR ID of the unmerge event's target patient. URL: https://open.epic.com/FHIR/StructureDefinition/patient-unmerge-current-target-reference

Patient (R4).extension (patient-unmerge-source).extension (patient-unmerge-old-target-reference) (also: extension (patient-unmerge-old-target-reference)) | Extension | | Yes | 0..1 | A reference to the FHIR ID of the unmerge event's target patient at the time of the

merge. URL: https://open.epic.com/FHIR/StructureDefinition/patient-unmerge-old-target-reference

Patient (R4).extension (patient-unmerge-source).extension (patient-unmerge-original-source-reference) (also: extension (patient-unmerge-original-source-reference)) | Extension | | Yes | 0..1 | A reference to the current FHIR ID of the unmerge event's source patient. URL: https://open.epic.com/FHIR/StructureDefinition/patient-unmerge-original-source-reference

Patient (R4).extension (patient-unmerge-source).extension (patient-unmerge-reference-old) (also: extension (patient-unmerge-reference-old)) | Extension | | Yes | 0..1 | A reference to the FHIR ID of the unmerge event's source patient at the time of the merge. URL: https://open.epic.com/FHIR/StructureDefinition/patient-unmerge-reference-old

Patient (R4).extension (patient-unmerge-target) (also: extension (patient-unmerge-target)) | Extension | | Yes | 0..* | This extension contains a collection of extensions that represent the metadata for a patient record unmerge from the perspective of the target patient. If the patient is involved as the target patient in multiple unmerges, this set of extensions is returned for each unmerge event. URL: https://open.epic.com/FHIR/StructureDefinition/patient-unmerge-target

Patient (R4).extension (patient-unmerge-target).extension (patient-merge-unmerge-instant) (also: extension (patient-merge-unmerge-instant)) | Extension | | Yes | 0..1 | The instant the patient merge event occurred. URL: https://open.epic.com/FHIR/StructureDefinition/patient-merge-unmerge-instant

Patient (R4).extension (patient-unmerge-target).extension (patient-unmerge-old-target-reference) (also: extension (patient-unmerge-old-target-reference)) | Extension | | Yes | 0..1 | A reference to the FHIR ID of the unmerge event's target patient at the time of the merge. URL: https://open.epic.com/FHIR/StructureDefinition/patient-unmerge-old-target-reference

Patient (R4).extension (patient-unmerge-target).extension (patient-unmerge-original-source-reference) (also: extension (patient-unmerge-original-source-reference)) | Extension | | Yes | 0..1 | A reference to the current FHIR ID of the unmerge event's source patient. URL: https://open.epic.com/FHIR/StructureDefinition/patient-unmerge-original-source-reference

Patient (R4).extension (patient-unmerge-target).extension (patient-unmerge-reference-new) (also: extension (patient-unmerge-reference-new)) | Extension | | Yes | 0..1 | A reference to the FHIR ID of the unmerge event's source patient after the unmerge. URL: https://open.epic.com/FHIR/StructureDefinition/patient-unmerge-reference-new

Patient (R4).extension (patient-unmerge-target).extension (patient-unmerge-reference-old) (also: extension (patient-unmerge-reference-old)) | Extension | | Yes | 0..1 | A reference to the FHIR ID of the unmerge event's source patient at the time of the merge. URL: https://open.epic.com/FHIR/StructureDefinition/patient-unmerge-reference-old

Patient (R4).extension (sex-for-clinical-use) (also: extension (sex-for-clinical-use)) | Extension | | Yes | 0..1 | The patient's sex for clinical decision making. This is an Epic-calculated value. If the patient's sex, gender, and clinical information indicate the patient is not unambiguously a cisgender male or female, the extension is not included. URL: http://open.epic.com/FHIR/StructureDefinition/extension/sex-for-clinical-use

Patient (R4).extension (us-core-ethnicity) (also: extension (us-core-ethnicity)) | Extension | | Yes | 0..1 | The patient's ethnicity parent extension. This element is not returned for organizations in the Netherlands or Singapore. For other organizations, the value returned depends on the mapping owned by the Epic organization. For organizations in the US, this mapping is typically based on regulatory standards set by the CDC. URL: http://hl7.org/fhir/us/core/StructureDefinition/us-core-ethnicity

Patient (R4).extension (us-core-ethnicity).extension (ombCategory) (also: extension (ombCategory)) | Extension | | Yes | 0..1 | The patient's ethnicity. URL: ombCategory

Patient (R4).extension (us-core-ethnicity).extension (text) (also: extension (text)) | Extension | | Yes | 0..1 | Textual display value for the OMB ethnicity code. The following mapping is used: OMB Ethnicity Code Text 2135-2 Hispanic or Latino 2186-5 Not Hispanic or Latino Default Value Unknown URL: text

OMB Ethnicity Code | Text

2135-2 | Hispanic or Latino

2186-5 | Not Hispanic or Latino

Default Value | Unknown

Patient (R4).extension (us-core-genderIdentity) (also: extension (us-core-genderIdentity)) | Extension | | Yes | 0..1 | The patient’s gender identity URL: http://hl7.org/fhir/us/core/StructureDefinition/us-core-genderIdentity

Patient (R4).extension (us-core-race) (also: extension (us-core-race)) | Extension | | Yes | 0..1 | The patient's race. This element is not returned for organizations in the Netherlands or Singapore. For other organizations, the value returned depends on the mapping owned by the Epic organization. For organizations in the US, this mapping is typically based on regulatory standards set by the CDC. URL: http://hl7.org/fhir/us/core/StructureDefinition/us-core-race

Patient (R4).extension (us-core-race).extension (detailed) (also: extension (detailed)) | Extension | | Yes | 0..* | Detailed CDC race code. URL: detailed

Patient (R4).extension (us-core-race).extension (ombCategory) (also: extension (ombCategory)) | Extension | | Yes | 0..* | Race code according to the OMB race category valueset. URL: ombCategory

Patient (R4).extension (us-core-race).extension (text) (also: extension (text)) | Extension | | Yes | 0..* | Textual display value for the OMB race code. The following mapping is used: OMB Race Code Text 1002-5 American Indian or Alaska Native 2028-9 Asian 2054-5 Black or African American 2076-8 Native Hawaiian or Other Pacific Islander 2106-3 White 2131-1 Other Race Default Value Unknown URL: text

OMB Race Code | Text

1002-5 | American Indian or Alaska Native

2028-9 | Asian

2054-5 | Black or African American

2076-8 | Native Hawaiian or Other Pacific Islander

2106-3 | White

2131-1 | Other Race

Default Value | Unknown

Patient (R4).extension (us-core-sex) (also: extension (us-core-sex)) | Extension | | Yes | 0..1 | The patient’s most reliable sex for clinical decision making. If the patient's sex cannot be reliably determined, nothing is returned. URL: http://hl7.org/fhir/us/core/StructureDefinition/us-core-sex

Patient (R4).extension (us-core-tribal-affiliation) (also: extension (us-core-tribal-affiliation)) | Extension | | Yes | 0..1 | The patient’s tribal affiliation. URL: http://hl7.org/fhir/us/core/StructureDefinition/us-core-tribal-affiliation

Patient (R4).extension (us-core-tribal-affiliation).extension (tribalAffiliation) (also: extension (tribalAffiliation)) | Extension | | Yes | 0..1 | The patient's tribal affiliation code.

Patient (R4).gender | code | | | 1..1 | The patient's legal sex.

Patient (R4).generalPractitioner | Reference | | Yes | 0..* | The patient's Primary Care Provider (PCP). Reference to a Practitioner resource. For organizations in UK with EPS enabled at the system level, also contains an identifier-based reference to the patient's care organization.

Patient (R4).id | id | | | 1..1 | The Patient FHIR ID.

Patient (R4).identifier | Identifier | | Yes | 1..* | The patient's identifiers. Includes the following: MPI IDs (such as MRNs) Epic MyChart login IDs Epic database IDs Payer Member IDs National IDs FHIR ID Care Everywhere ID For organizations in Singapore, the patient’s document ID, type, and expiry date.

Patient (R4).identifier.period | Period | | | 0..1 | The expiration date of the patient's identification document in Singapore.

Patient (R4).identifier.system | String | | | 1..1 | Epic Identity IDs (such as Patient MRN) Identity ID OID Identity ID HL7 Assigning Authority as the "Text" value. Epic MyChart IDs MyChart login OID Epic Care Everywhere ID CEID Epic internal ID Generated OID for the Epic internal patient ID Epic external ID Generated OID for the Epic external patient ID Payer Member ID https://open.epic.com/FHIR/StructureDefinition/PayerMemberId National Identifier US Social Security Number: 2.16.840.1.113883.4.1 UK NHS ID: 2.16.840.1.113883.2.1.4.1 or https://fhir.nhs.uk/Id/nhs-number Dutch BSN: 2.16.840.1.113883.2.4.6.3 or http://fhir.nl/fhir/NamingSystem/bsn Finnish National ID: 1.2.246.21 United Arab Emirates: 2.16.840.1.113883.3.7326.10.1 Australian Medicare Number: http://ns.electronichealth.net.au/id/medicare-number Singapore Document ID https://open.epic.com/singapore/doc-id FHIR ID STU3 and up: http://open.epic.com/FHIR/StructureDefinition/patient-fhir-id DSTU2: http://open.epic.com/FHIR/StructureDefinition/patient-dstu2-fhir-id

Patient (R4).identifier.type | CodeableConcept | | | 0..1 | The patient's identifier type. In Singapore, this is the patient's identification document type.

Patient (R4).identifier.value | String | | | 1..1 | The patient's ID. For organizations in Singapore, this can also be the patient's identification document ID.

Patient (R4).identifier.value.extension (rendered-value) (also: extension (rendered-value)) | Extension | | Yes | | Contains the patient's masked national ID if the organization masks national identifiers. URL: http://hl7.org/fhir/StructureDefinition/rendered-value

Patient (R4).link | BackboneElement | | Yes | 0..* | Contains links to other patient records if the patient record was involved in a merge. Each link element represents a single merge event. If the patient was involved in multiple merges, multiple Link elements are returned. Starting in the February 2024 version of Epic, the 30 most recent merge events are returned instead of all merge events.

Patient (R4).link.extension (patient-merge-target-reference) (also: extension (patient-merge-target-reference)) | Extension | | Yes | 0..1 | The FHIR ID reference to the target patient. In a merge, the target patient refers to the surviving patient. URL: https://open.epic.com/FHIR/StructureDefinition/patient-merge-target-reference

Patient (R4).link.extension (patient-merge-unmerge-instant) (also: extension (patient-merge-unmerge-instant)) | Extension | | Yes | 0..1 | The instant the patient merge event occurred. URL: https://open.epic.com/FHIR/StructureDefinition/patient-merge-unmerge-instant

Patient (R4).link.other | Reference | | | 0..1 | A Patient reference to the source patient. In a merge, the source patient is the patient that goes away.

Patient (R4).link.type | code | | | 1..1 | The type of link between Patient resources. This is always set to "replaces". The Patient FHIR ID in the link.extension (patient-merge-target-reference) element replaces the Patient FHIR ID referenced in the link.other element.

Patient (R4).managingOrganization | Reference | | | 0..1 | The patient’s primary service area. Reference to an Organization resource.

Patient (R4).maritalStatus | CodeableConcept | | | 0..1 | The patient's marital status.

Patient (R4).meta | Meta | | | | Metadata about the resource.

Patient (R4).meta.security | Coding | | Yes | 0..2 | The patient’s unverified status. Available starting in the May 2024 version of Epic, and in February 2024 and November 2023 with special updates. This is used to track new patient records that might need to be reconciled against existing records in the system. The element is not returned for verified patients. Unverified patients always return the value PATRPT (Patient Reported) along with one of the following values: UNCERTAIN (Uncertain Reliability) UNRELIABLE (Unreliable)

Patient (R4).multipleBirthInteger | integer | | | 0..1 | The patient's birth order.

Patient (R4).name | HumanName | | Yes | 1..* | The patient's name.

Patient (R4).name.extension (humanNameAssemblyOrder) (also: extension (humanNameAssemblyOrder)) | Extension | | Yes | 0..* | This extension is populated only for organizations in the Netherlands. Name order for the contact. One of the following values: * NL1-Own Name * NL2-Partner Name * NL3-Partner Name followed by Maiden Name * NL4-Own Name followed by Partner Name URL: http://hl7.org/fhir/StructureDefinition/humanname-assembly-order

Patient (R4).name.family | string | | | 1..1 | The patient's family (last) name. Can contain a data-absent-reason extension with a value of "unknown" if the patient has an alias that cannot be returned as discrete elements or if the patient's preferred name replaces their full name.

Patient (R4).name.family.extension (data-absent-reason) (also: extension (data-absent-reason)) | Extension | | Yes | 0..1 | Returned as "unknown" for patients without family names.

Patient (R4).name.family.extension (humanNameOwnName) (also: extension (humanNameOwnName)) | Extension | | Yes | 0..1 | The portion of a patient's family name derived from the patient's own name.

Patient (R4).name.family.extension (humanNameOwnPrefix) (also: extension (humanNameOwnPrefix)) | Extension | | Yes | 0..1 | The prefix portion of a patient's family name derived from the patient's own surname.

Patient (R4).name.family.extension (humanNamePartnerName) (also: extension (humanNamePartnerName)) | Extension | | Yes | 0..1 | The portion of a patient's family name derived from the patient's partner's name.

Patient (R4).name.family.extension (humanNamePartnerPrefix) (also: extension (humanNamePartnerPrefix)) | Extension | | Yes | 0..1 | The prefix portion of a patient's family name derived from the patient's partner's surname.

Patient (R4).name.given | string | | Yes | 1..* | The patient's given name. Can include first and middle names.

Patient (R4).name.given.extension (namePartQualifier) (also: extension (namePartQualifier)) | Extension | | Yes | 0..2 | This extension is returned if initials or a preferred name are present. The entity qualifier extension code is IN for initials and is CL for preferred name. URL: http://hl7.org/fhir/StructureDefinition/iso21090-EN-qualifier

Patient (R4).name.prefix | string | | Yes | 0..1 | The patient's name prefix.

Patient (R4).name.suffix | string | | Yes | 0..* | The patient's name suffix. Acquired as a title due to academic, legal, employment or nobility status, etc.

Patient (R4).name.text | string | | | 1..1 | The patient's full name as a string.

Patient (R4).name.use | code | | | 1..1 | The purpose of the name. Can be "official", "usual", or "old".

Patient (R4).telecom | ContactPoint | | Yes | 0..* | Telephone numbers and email addresses for the patient, along with their use (home or work for example) and their preferred rank (which to contact first, second, third, etc).

Patient (R4).telecom.rank | positiveInt | | | 0..1 | The priority for permanent phone numbers or emails. 1 indicates the highest priority phone number, 2 indicates the second priority, etc . The preferred has a rank of 1. Additional emails have a null rank.

Patient (R4).telecom.system | code | | | 1..1 | The type of telecom. Potential values are: email phone fax url pager sms other

Patient (R4).telecom.use | code | | | 0..1 | If the telecom entry is a phone number, possible values are: home mobile work temp old Use is not returned for emails.

Patient (R4).telecom.value | string | | | 1..1 | Value of the telecom method. Can be an email address or phone number.

Sample request

```
POST https://hostname/instance/api/FHIR/R4/Patient
{
  "resourceType": "Patient",
  "identifier": [
    {
      "use": "usual",
      "system": "urn:oid:1.2.840.114350.1.13.861.1.7.5.737384.27000",
      "value": "8512"
```

```
    },
    {
      "use": "usual",
      "system": "urn:oid:2.16.840.1.113883.4.1",
      "value": "999-99-9999"
    }
  ],
  "name": [
    {
      "use": "official",
      "family": "Patient",
      "given": [
        "Test"
      ],
      "suffix": [
        "JR."
      ]
    }
  ],
  "telecom": [
    {
      "system": "phone",
      "value": "336-544-1111",
      "use": "home"
    },
    {
      "system": "email",
      "value": "test.patient@epic.com"
    }
  ],
  "gender": "female",
  "birthDate": "1994-07-20",
  "address": [
    {
      "use": "home",
      "line": [
        "100 Milky Way",
        "Learning Campus"
      ],
      "city": "Verona",
      "state": "WI",
      "postalCode": "53593",
      "country": "USA"
    }
  ],
  "maritalStatus": {
    "text": "Single"
  },
  "generalPractitioner": [
    {
      "display": "Sample Provider, MD",
      "reference": "https://hostname/instance/api/FHIR/R4/Practitioner/e4ZKPXZ0ux4Z80UHywzHyHg3"
    }
  ],
  "extension": [
    {
      "url": "http://open.epic.com/FHIR/R4/StructureDefinition/patient-preferred-provider-language",
      "valueCodeableConcept": {
        "coding": [
          {
            "system": "urn:oid:2.16.840.1.113883.6.99",
            "code": "ja"
          }
        ],
        "text": "Japanese"
      }
    },
    {
      "url": "http://open.epic.com/FHIR/R4/StructureDefinition/patient-preferred-provider-sex",
      "valueCode": "female"
    },
    {
      "url": "http://hl7.org/fhir/StructureDefinition/patient-genderIdentity",
      "valueCodeableConcept": {
        "coding": [
          {
            "system": "urn:oid:1.2.840.114350.1.13.5325.1.7.10.698084.131.657370.1194",
            "code": "female"
          }
        ]
      }
    }
  ]
}
```


Sample response

```
Status code: Created (201)
Content-Type: application/json; charset=utf-8
```

```
Location: Patient/ei4u9SQ4uH7sl61.VEhXgng3
```

Change log

Epic Version | Description | Type
November 2022 | Epic has updated the behavior of certain modifier elements in FHIR write APIs to ensure the data in the incoming request body matches the data filed to the database and to comply with the HL7 FHIR specification. Previously, the modifier element was ignored in certain situations, and an undocumented default value was saved in its place. Now, if the modifier element is included and is set to an unaccepted value, a fatal error logs, preventing the request from filing to the database. The FHIR request returns an OperationOutcome with the invalid element and what value is accepted for that element. Element Accepted Incoming Value Default Value active true true deceasedBoolean false false deceasedDateTime None - will always trigger fatal error None - not supported on incoming requests link None - will always trigger fatal error None - not supported on incoming requests | Substantive change
Element | Accepted Incoming Value | Default Value
active | true | true
deceasedBoolean | false | false
deceasedDateTime | None - will always trigger fatal error | None - not supported on incoming requests
link | None - will always trigger fatal error | None - not supported on incoming requests

22.1.3 Patient.Read (Demographics) (R4)

File: site/apis/22-Identification-Individuals/1-R4/931-Patient-Read-Demographics-R4.html
Epic API ID | 931
FHIR version | R4
Categories | Identification Individuals
API type | USCDI
A la carte | Industry-Standard Level 1 API
USCDI | Yes
Keywords | Care Team Members;Patient Demographics;First name;Last name;Middle name;initial;Suffix;Birth sex;Date of birth;Race;Ethnicity;Preferred language;Address;Phone number;Previous name
Available in inpatient and other contexts | Yes
ONC certification products | EpicCare Ambulatory Base, EpicCare Inpatient Base
ONC certification versions | August 2019
HTTP method | GET
URL template | api/FHIR/R4/Patient/{ID}
Supports OAuth 2.0 | True
Supported user types | Backend Systems and Non-OAuth 2.0, Clinicians or Administrative Users, Patients
Performs scope validation | False
Source | https://fhir.epic.com/Specifications?api=931

Description

The FHIR Patient resource defines demographics, care providers, and other administrative information about a person receiving care at a health organization.

A non-patient user must have appropriate security to have search details, demographic details, and/or PCP details included in the Patient resource.

This web service respects all patient-facing security for demographic information when used in the context of a patient as the user.

If an Epic organization has configured service area restrictions, the user accessing this FHIR resource must be authorized to view patients in the target service area.

When two patients are merged, a Patient.Read on the target (surviving) patient will work normally. The source patient will return a 404 error, as we consider the source patient FHIR ID to be invalid.

Remarks

You can configure this FHIR resource using the following profile variables:

* COMM_EQUIP_TYPE_TBL
* FHIR_SEX_AT_BIRTH_TBL
* GENDER_TBL
* GENDER_IDENTITY_CORE_V3_TBL
* GENDER_IDENTITY_TBL
* MARITAL_TABLE
* PCP_TYPES
* TRIBAL_AFFILIATION_CORE_V3_TBL

Request parameters

Name | Type | Optional | Array | Cardinality | Description
ID | token | Required | | | The Patient FHIR ID.

Response elements

Name | Type | Optional | Array | Cardinality | Description

Patient (R4) | Resource

Patient (R4).active | boolean | | | 1..1 | Whether the patient record is active.

Patient (R4).address | Address | | Yes | 0..* | The patient's current address, as well as any previous or temporary addresses, if applicable. The patient's current address has a use code of "home". If the patient also has one or more previous addresses, each previous address has a use code of "old". The patient's temporary address has a use code of "temp".

Patient (R4).address.city | string | | | 0..1 | The city that the patient lives in.

Patient (R4).address.country | String | | | 0..1 | The country that the patient lives in.

Patient (R4).address.district | String | | | 0..1 | The county that the patient lives in.

Patient (R4).address.line | string | | Yes | 0..* | The patient’s street address.

Patient (R4).address.line.extension (additionalLocator) (also: extension (additionalLocator)) | Extension | | Yes | 0..1 | This extension is returned only for organizations in Singapore. The patient’s floor. URL: http://hl7.org/fhir/StructureDefinition/iso21090-ADXP-additionalLocator

Patient (R4).address.line.extension (buildingName) (also: extension (buildingName)) | Extension | | Yes | 0..1 | This extension is returned only for organizations in Singapore. The patient’s building name. URL: http://open.epic.com/FHIR/StructureDefinition/extension/buildingName

Patient (R4).address.line.extension (houseNumber) (also: extension (houseNumber)) | Extension | | Yes | 0..1 | For organizations in the Netherlands and Singapore, this element represents the portion of a patient or contact’s address that is their house number. URL: http://hl7.org/fhir/StructureDefinition/iso21090-ADXP-houseNumber

Patient (R4).address.line.extension (streetName) (also: extension (streetName)) | Extension | | Yes | 0..* | For organizations in the Netherlands and Singapore, this element represents the portion of a patient or contact’s address that includes the name of their street. URL: http://hl7.org/fhir/StructureDefinition/iso21090-ADXP-streetName

Patient (R4).address.line.extension (unitID) (also: extension (unitID)) | Extension | | Yes | 0..1 | This extension is returned only for organizations in Singapore. The patient’s unit number. URL: http://hl7.org/fhir/StructureDefinition/iso21090-ADXP-unitID

Patient (R4).address.period | Period | | | 0..1 | The start date – and optionally, end date – for when the address is valid. Returned for the current address if the information is available. Starting in the May 2025 version of Epic, also returned for previous and temporary addresses if the information is available.

Patient (R4).address.postalCode | string | | | 0..1 | The patient’s postal code.

Patient (R4).address.state | string | | | 0..1 | The state where the patient lives.

Patient (R4).address.text | String | | | 0..1 | The patient’s full address as a string. This is formatted based on the country the address is in. For U.S. addresses, to meet the standards laid out in the Project US@ Technical Specifications, patient addresses format automatically for patient matching purposes.

Patient (R4).address.use | code | | | 1..1 | Specifies the type of address: home – A permanent address old – A previous permanent address temp – A temporary address Temporary addresses behavior varies by Epic version: May 2025 or later – Returned only if the Epic organization has configured temporary addresses to be visible in FHIR responses (applies to all locales). Prior to May 2025 – Singapore – Always returned. Norway – Always returned if using: August 2024 version, or May 2024 version with special updates.

Patient (R4).birthDate | date | | | 1..1 | The patient's date of birth in the format YYYY-MM-DD

Patient (R4).birthDate.extension (birthTime) (also: extension (birthTime)) | Extension | | | 0..1 | The patient's time of birth. This extension follows the HL7 birthTime specification. Prior to the November 2023 verison of Epic, this extension was returned at the Patient resource level. Beginning in the November 2023 version of Epic, this is now returned underneath the BirthDate element. URL: http://hl7.org/fhir/StructureDefinition/patient-birthTime

Patient (R4).birthDate.extension (dataAbsentReason) (also: extension (dataAbsentReason)) | Extension | | | 0..1 | Available starting with the November 2024 version of Epic. If the patient’s birth date is not recorded, this extension is returned with a value of "unknown". URL: http://hl7.org/fhir/StructureDefinition/data-absent-reason

Patient (R4).communication | BackboneElement | | Yes | 0..* | Languages used to communicate with the patient, along with an indicator of which is preferred.

Patient (R4).communication.extension (comment) (also: extension (comment)) | Extension | | Yes | 0..1 | A comment about the patient's language proficiency. This extension is returned only for organizations in the Netherlands. URL: http://nictiz.nl/fhir/StructureDefinition/Comment

Patient (R4).communication.extension (patient-proficiency) (also: extension (patient-proficiency)) | Extension | | Yes | 0..3 | Container extension that holds details about the patient's language proficiency. Contains two child extensions which indicate the type of language proficiency and the level of that proficiency. This extension is returned only for organizations in the Netherlands. URL: http://nictiz.nl/fhir/StructureDefinition/patient-proficiency

Patient (R4).communication.extension (patient-proficiency).extension (v3-LanguageAbilityMode) (also: extension (v3-LanguageAbilityMode)) | Extension | | Yes | 0..1 | Patient's language proficiency type. This is a valueCoding wherein the following code and display values are supported: RSP - Received spoken ESP - Expressed spoken RWR - Received written System value of http://terminology.hl7.org/CodeSystem/v3-LanguageAbilityMode URL: type

Patient (R4).communication.extension (patient-proficiency).extension (v3-LanguageAbilityProficiency) (also: extension (v3-LanguageAbilityProficiency)) | Extension | | Yes | 0..1 | Patient's language proficiency level. This is a valueCoding wherein the following code and display values are supported: E - Excellent G - Good F - Fair P - Poor System value of http://terminology.hl7.org/CodeSystem/v3-LanguageAbilityProficiency URL: level

Patient (R4).communication.language | CodeableConcept | | | 1..1 | The patient's general language, onsite care language, and spoken language.

Patient (R4).communication.preferred | boolean | | | 0..1 | Whether the language is the patient's preferred language.

Patient (R4).communication.preferred.extension (patient-preferenceType) (also: extension (patient-preferenceType)) | Extension | | Yes | 0..1 | The preferred mode of communication for the patient’s preferred language. This can be either verbal or written. Returned starting in the May 2025 version of Epic. Returned with system http://hl7.org/fhir/language-preference-type. URL: http://hl7.org/fhir/StructureDefinition/patient-preferenceType

Patient (R4).contact | BackboneElement | | Yes | 0..* | Details for the patient's contacts. Patient contacts include any documented family members, emergency contacts, care givers, acquaintances, and employers.

Patient (R4).contact.address | Address | | | 0..1 | The contact address. For responses to a patient-facing application, this element is not returned for contacts linked to a patient record. For organizations in the Netherlands, this element represents an nl-core-address value.

Patient (R4).contact.name | HumanName | | | 1..1 | The contact's preferred name. The system determines this from the contact's linked patient record if available. For contacts linked to a patient record, only the patient's official first name is returned in patient context. For organizations in the Netherlands, this element represents an nl-core-humanname value.

Patient (R4).contact.name.extension (humanname-assembly-order) (also: extension (humanname-assembly-order)) | Extension | | Yes | 0..1 | This extension is populated only for organizations in the Netherlands. Name order for the contact. One of the following values: NL1 - Own Name NL2 - Partner Name NL3 - Partner Name followed by Maiden Name NL4 - Own Name followed by Partner Name URL: http://hl7.org/fhir/StructureDefinition/humanname-assembly-order

Patient (R4).contact.organization | Reference | | | 0..1 | An Organization reference that represents the patient's employer. Returned when contact.relationship.code is E.

Patient (R4).contact.period | Period | | | 0..1 | The start and end dates for the patient contact.

Patient (R4).contact.relationship | CodeableConcept | | Yes | 0..* | The contact's relationship to the patient. This element can return multiple values. It will always return one or more Epic category values for the contact's relationship to the patient. In addition, it can return one or more of the following: For organizations in the Netherlands, either a Relationship (RelatieCodelijst) code system value or a role (RolCodelijst) code system value. For all other organizations, can return either a code system value – such as "C" (emergency contact) or "E" (employer) – or a RoleClass code system value – such as "GUARD" or "AGNT".

Patient (R4).contact.telecom | ContactPoint | | Yes | 0..* | Telephone numbers and email address for the contact. For responses to a patient-facing application, this element is not returned for contacts linked to a patient record. For organizations in the Netherlands, this element represents an nl-core-contactpoint value.

Patient (R4).contact.telecom.rank | positiveInt | | | 0..1 | The priority for permanent phone numbers or emails. 1 indicates the highest priority phone number, 2 indicates the second priority, and so on. Starting in the May 2025 version of Epic, rank is returned for the phone numbers of patient contacts.

Patient (R4).contact.telecom.system | code | | | 0..1 | The type of telecom. Potential values are: email phone

Patient (R4).contact.telecom.use | code | | | 0..1 | If the telecom entry is a phone number, possible values are: home mobile work

Patient (R4).contact.telecom.value | string | | | 1..1 | Value of the telecom method. Can be an email address or phone number.

Patient (R4).deceasedBoolean | boolean | | | 0..1 | Whether the patient is deceased.

Patient (R4).deceasedDateTime | dateTime | | | 0..1 | The date and time of death.

Patient (R4).extension (birth-location) (also: extension (birth-location)) | Extension | | Yes | 0..1 | A reference to a newborn's birth facility. URL: http://open.epic.com/FHIR/StructureDefinition/extension/birth-location

Patient (R4).extension (birth-sex) (also: extension (birth-sex)) | Extension | | Yes | 0..1 | The patient's sex assigned at birth. This element is not returned for organizations in the Netherlands. URL: http://hl7.org/fhir/us/core/StructureDefinition/us-core-birthsex

Patient (R4).extension (calculated-pronouns-to-use-for-text) (also: extension (calculated-pronouns-to-use-for-text)) | Extension | | Yes | 0..* | The patient's pronouns to use when generating text. Available starting in the November 2023 version of Epic. This is an Epic-calculated value based on specified pronouns, the patient's gender identity, or the patient's legal sex. Consider using extension (individual-pronouns) instead of this one. One of the following: A value from LOINC Answer List LL5144-2 Personal pronouns EP-PS-DO-NOT-USE-PRONOUNS, from the Epic-defined pronoun set https://open.epic.com/FHIR/Epic/pronoun-set URL: http://open.epic.com/FHIR/StructureDefinition/extension/calculated-pronouns-to-use-for-text

Patient (R4).extension (gender-identity) (also: extension (gender-identity)) | Extension | | Yes | 0..1 | The patient's gender identity. URL: http://hl7.org/fhir/StructureDefinition/patient-genderIdentity

Patient (R4).extension (individual-pronouns) (also: extension (individual-pronouns)) | Extension | | Yes | 0..* | The pronouns to use when communicating about an individual. Available starting in the November 2024 version of Epic. URL: http://hl7.org/fhir/StructureDefinition/individual-pronouns

Patient (R4).extension (interpreter-needed) (also: extension (interpreter-needed)) | Extension | Optional | Yes | 0..1 | Whether the patient needs an interpreter. URL: http://hl7.org/fhir/us/core/StructureDefinition/us-core-interpreter-needed

Patient (R4).extension (legal-sex) (also: extension (legal-sex)) | Extension | | Yes | 0..1 | The patient's legal sex. URL: http://open.epic.com/FHIR/StructureDefinition/extension/legal-sex

Patient (R4).extension (nationality) (also: extension (nationality)) | Extension | | Yes | 0..1 | The patient's nationality. This extension is returned only for organizations in the Singapore. URL: http://hl7.org/fhir/StructureDefinition/patient-nationality

Patient (R4).extension (patient-preferred-provider-language) (also: extension (patient-preferred-provider-language)) | Extension | | Yes | 0..1 | The patient's preferred provider language, used for scheduling. URL: http://open.epic.com/FHIR/STU3/StructureDefinition/patient-preferred-provider-language

Patient (R4).extension (patient-preferred-provider-sex) (also: extension (patient-preferred-provider-sex)) | Extension | | Yes | 0..1 | The patient's preferred provider sex, used for scheduling. URL: http://open.epic.com/FHIR/STU3/StructureDefinition/patient-preferred-provider-sex

Patient (R4).extension (patient-type) (also: extension (patient-type)) | Extension | | Yes | 0..* | The type of patient, such as Confidential or Employee. URL: http://open.epic.com/FHIR/StructureDefinition/extension/patient-type

Patient (R4).extension (patient-unmerge-source) (also: extension (patient-unmerge-source)) | Extension | | Yes | 0..* | This extension contains a collection of extensions that represent the metadata for a patient record unmerge from the perspective of the source patient. If the patient is involved as the source patient in multiple unmerges, this set of extensions is returned for each unmerge event. URL: https://open.epic.com/FHIR/StructureDefinition/patient-unmerge-source

Patient (R4).extension (patient-unmerge-source).extension (patient-merge-unmerge-instant) (also: extension (patient-merge-unmerge-instant)) | Extension | | Yes | 0..1 | The instant the patient merge event occurred. URL: https://open.epic.com/FHIR/StructureDefinition/patient-merge-unmerge-instant

Patient (R4).extension (patient-unmerge-source).extension (patient-unmerge-current-target-reference) (also: extension (patient-unmerge-current-target-reference)) | Extension | | Yes | 0..1 | A reference to the current FHIR ID of the unmerge event's target patient. URL: https://open.epic.com/FHIR/StructureDefinition/patient-unmerge-current-target-reference

Patient (R4).extension (patient-unmerge-source).extension (patient-unmerge-old-target-reference) (also: extension (patient-unmerge-old-target-reference)) | Extension | | Yes | 0..1 | A reference to the FHIR ID of the unmerge event's target patient at the time of the merge. URL: https://open.epic.com/FHIR/StructureDefinition/patient-unmerge-old-target-reference

Patient (R4).extension (patient-unmerge-source).extension (patient-unmerge-original-source-reference) (also: extension (patient-unmerge-original-source-reference)) | Extension | | Yes | 0..1 | A reference to the current FHIR ID of the unmerge event's source patient. URL: https://open.epic.com/FHIR/StructureDefinition/patient-unmerge-original-source-reference

Patient (R4).extension (patient-unmerge-source).extension (patient-unmerge-reference-old) (also: extension (patient-unmerge-reference-old)) | Extension | | Yes | 0..1 | A reference to the FHIR ID of the unmerge event's source patient at the time of the merge. URL: https://open.epic.com/FHIR/StructureDefinition/patient-unmerge-reference-old

Patient (R4).extension (patient-unmerge-target) (also: extension (patient-unmerge-target)) | Extension | | Yes | 0..* | This extension contains a collection of extensions that represent the metadata for a patient record unmerge from the perspective of the target patient. If the patient is involved as the target patient in multiple unmerges, this set of extensions is returned for each unmerge event. URL: https://open.epic.com/FHIR/StructureDefinition/patient-unmerge-target

Patient (R4).extension (patient-unmerge-target).extension (patient-merge-unmerge-instant) (also: extension (patient-merge-unmerge-instant)) | Extension | | Yes | 0..1 | The instant the patient merge event occurred. URL: https://open.epic.com/FHIR/StructureDefinition/patient-merge-unmerge-instant

Patient (R4).extension (patient-unmerge-target).extension (patient-unmerge-old-target-reference) (also: extension (patient-unmerge-old-target-reference)) | Extension | | Yes | 0..1 | A reference to the FHIR ID of the unmerge event's target patient at the time of the merge. URL: https://open.epic.com/FHIR/StructureDefinition/patient-unmerge-old-target-reference

Patient (R4).extension (patient-unmerge-target).extension (patient-unmerge-original-source-reference) (also: extension (patient-unmerge-original-source-reference)) | Extension | | Yes | 0..1 | A reference to the current FHIR ID of the unmerge event's source patient. URL: https://open.epic.com/FHIR/StructureDefinition/patient-unmerge-original-source-reference

Patient (R4).extension (patient-unmerge-target).extension (patient-unmerge-reference-new) (also: extension (patient-unmerge-reference-new)) | Extension | | Yes | 0..1 | A reference to the FHIR ID of the unmerge event's source patient after the unmerge. URL: https://open.epic.com/FHIR/StructureDefinition/patient-unmerge-reference-new

Patient (R4).extension (patient-unmerge-target).extension (patient-unmerge-reference-old) (also: extension (patient-unmerge-reference-old)) | Extension | | Yes | 0..1 | A reference to the FHIR ID of the unmerge event's source patient at the time of the merge. URL: https://open.epic.com/FHIR/StructureDefinition/patient-unmerge-reference-old

Patient (R4).extension (sex-for-clinical-use) (also: extension (sex-for-clinical-use)) | Extension | | Yes | 0..1 | The patient's sex for clinical decision making. This is an Epic-calculated value. If the patient's sex, gender, and clinical information indicate the patient is not unambiguously a cisgender male or female, the extension is not included. URL: http://open.epic.com/FHIR/StructureDefinition/extension/sex-for-clinical-use

Patient (R4).extension (us-core-ethnicity) (also: extension (us-core-ethnicity)) | Extension | | Yes | 0..1 | The patient's ethnicity parent extension. This element is not returned for organizations in the Netherlands or Singapore. For other organizations, the value returned depends on the mapping owned by the Epic organization. For organizations in the US, this mapping is typically based on regulatory standards set by the CDC. URL: http://hl7.org/fhir/us/core/StructureDefinition/us-core-ethnicity

Patient (R4).extension (us-core-ethnicity).extension (ombCategory) (also: extension (ombCategory)) | Extension | | Yes | 0..1 | The patient's ethnicity. URL: ombCategory

Patient (R4).extension (us-core-ethnicity).extension (text) (also: extension (text)) | Extension | | Yes | 0..1 | Textual display value for the OMB ethnicity code. The following mapping is used: OMB Ethnicity Code Text 2135-2 Hispanic or Latino 2186-5 Not Hispanic or Latino Default Value Unknown URL: text

OMB Ethnicity Code | Text

2135-2 | Hispanic or Latino

2186-5 | Not Hispanic or Latino

Default Value | Unknown

Patient (R4).extension (us-core-genderIdentity) (also: extension (us-core-genderIdentity)) | Extension | | Yes | 0..1 | The patient’s gender identity URL: http://hl7.org/fhir/us/core/StructureDefinition/us-core-genderIdentity

Patient (R4).extension (us-core-race) (also: extension (us-core-race)) | Extension | | Yes | 0..1 | The patient's race. This element is not returned for organizations in the Netherlands or Singapore. For other organizations, the value returned depends on the mapping owned by the Epic organization. For organizations in the US, this mapping is typically based on regulatory standards set by the CDC. URL: http://hl7.org/fhir/us/core/StructureDefinition/us-core-race

Patient (R4).extension (us-core-race).extension (detailed) (also: extension (detailed)) | Extension | | Yes | 0..* | Detailed CDC race code. URL: detailed

Patient (R4).extension (us-core-race).extension (ombCategory) (also: extension (ombCategory)) | Extension | | Yes | 0..* | Race code according to the OMB race category valueset. URL: ombCategory

Patient (R4).extension (us-core-race).extension (text) (also: extension (text)) | Extension | | Yes | 0..* | Textual display value for the OMB race code. The following mapping is used: OMB Race Code Text 1002-5 American Indian or Alaska Native 2028-9 Asian 2054-5 Black or African American 2076-8 Native Hawaiian or Other Pacific Islander 2106-3 White 2131-1 Other Race Default Value Unknown URL: text

OMB Race Code | Text

1002-5 | American Indian or Alaska Native

2028-9 | Asian

2054-5 | Black or African American

2076-8 | Native Hawaiian or Other Pacific Islander

2106-3 | White

2131-1 | Other Race

Default Value | Unknown

Patient (R4).extension (us-core-sex) (also: extension (us-core-sex)) | Extension | | Yes | 0..1 | The patient’s most reliable sex for clinical decision making. If the patient's sex cannot be reliably determined, nothing is returned. URL: http://hl7.org/fhir/us/core/StructureDefinition/us-core-sex

Patient (R4).extension (us-core-tribal-affiliation) (also: extension (us-core-tribal-affiliation)) | Extension | | Yes | 0..1 | The patient’s tribal affiliation. URL: http://hl7.org/fhir/us/core/StructureDefinition/us-core-tribal-affiliation

Patient (R4).extension (us-core-tribal-affiliation).extension (tribalAffiliation) (also: extension (tribalAffiliation)) | Extension | | Yes | 0..1 | The patient's tribal affiliation code.

Patient (R4).gender | code | | | 1..1 | The patient's legal sex.

Patient (R4).generalPractitioner | Reference | | Yes | 0..* | The patient's Primary Care Provider (PCP). Reference to a Practitioner resource. For organizations in UK with EPS enabled at the system level, also contains an identifier-based reference to the patient's care organization.

Patient (R4).id | id | | | 1..1 | The Patient FHIR ID.

Patient (R4).identifier | Identifier | | Yes | 1..* | The patient's identifiers. Includes the following: MPI IDs (such as MRNs) Epic MyChart login IDs Epic database IDs Payer Member IDs National IDs FHIR ID Care Everywhere ID For organizations in Singapore, the patient’s document ID, type, and expiry date.

Patient (R4).identifier.period | Period | | | 0..1 | The expiration date of the patient's identification document in Singapore.

Patient (R4).identifier.system | String | | | 1..1 | Epic Identity IDs (such as Patient MRN) Identity ID OID Identity ID HL7 Assigning Authority as the "Text" value. Epic MyChart IDs MyChart login OID Epic Care Everywhere ID CEID Epic internal ID Generated OID for the Epic internal patient ID Epic external ID Generated OID for the Epic external patient ID Payer Member ID https://open.epic.com/FHIR/StructureDefinition/PayerMemberId National Identifier US Social Security Number: 2.16.840.1.113883.4.1 UK NHS ID: 2.16.840.1.113883.2.1.4.1 or https://fhir.nhs.uk/Id/nhs-number Dutch BSN: 2.16.840.1.113883.2.4.6.3 or http://fhir.nl/fhir/NamingSystem/bsn Finnish National ID: 1.2.246.21 United Arab Emirates: 2.16.840.1.113883.3.7326.10.1 Australian Medicare Number: http://ns.electronichealth.net.au/id/medicare-number Singapore Document ID https://open.epic.com/singapore/doc-id FHIR ID STU3 and up: http://open.epic.com/FHIR/StructureDefinition/patient-fhir-id DSTU2: http://open.epic.com/FHIR/StructureDefinition/patient-dstu2-fhir-id

Patient (R4).identifier.type | CodeableConcept | | | 0..1 | The patient's identifier type. In Singapore, this is the patient's identification document type.

Patient (R4).identifier.type.coding | Coding | | Yes | 0..* | The type coding.

Patient (R4).identifier.type.coding.code | String | | | | The type code. Epic external ID "um" Payer Member ID "MB" Australian Medicare Number "MC"

Patient (R4).identifier.type.coding.system | String | | | | The code system. Epic external ID http://hl7.org/fhir/us/carin-bb/CodeSystem/C4BBIdentifierType Payer Member ID http://terminology.hl7.org/CodeSystem/v2-0203 Australian Medicare Number http://terminology.hl7.org/CodeSystem/v2-0203

Patient (R4).identifier.value | String | | | 1..1 | The patient's ID. For organizations in Singapore, this can also be the patient's identification document ID.

Patient (R4).identifier.value.extension (rendered-value) (also: extension (rendered-value)) | Extension | | Yes | | Contains the patient's masked national ID if the organization masks national identifiers. URL: http://hl7.org/fhir/StructureDefinition/rendered-value

Patient (R4).link | BackboneElement | | Yes | 0..* | Contains links to other patient records if the patient record was involved in a merge. Each link element represents a single merge event. If the patient was involved in multiple merges, multiple Link elements are returned. Starting in the February 2024 version of Epic, the 30 most recent merge events are returned instead of all merge events.

Patient (R4).link.extension (patient-merge-target-reference) (also: extension (patient-merge-target-reference)) | Extension | | Yes | 0..1 | The FHIR ID reference to the target patient. In a merge, the target patient refers to the surviving patient. URL: https://open.epic.com/FHIR/StructureDefinition/patient-merge-target-reference

Patient (R4).link.extension (patient-merge-unmerge-instant) (also: extension (patient-merge-unmerge-instant)) | Extension | | Yes | 0..1 | The instant the patient merge event occurred. URL: https://open.epic.com/FHIR/StructureDefinition/patient-merge-unmerge-instant

Patient (R4).link.other | Reference | | | 0..1 | A Patient reference to the source patient. In a merge, the source patient is the patient that goes away.

Patient (R4).link.type | code | | | 1..1 | The type of link between Patient resources. This is always set to "replaces". The Patient FHIR ID in the link.extension (patient-merge-target-reference) element replaces the Patient FHIR ID referenced in the link.other element.

Patient (R4).managingOrganization | Reference | | | 0..1 | The patient's primary service area. Reference to an Organization resource.

Patient (R4).maritalStatus | CodeableConcept | | | 0..1 | The patient's marital status.

Patient (R4).meta | Meta | | | | Metadata about the resource.

Patient (R4).meta.security | Coding | | Yes | 0..2 | The patient's unverified status. Available starting in the May 2024 version of Epic, and in February 2024 and November 2023 with special updates. This is used to track new patient records that might need to be reconciled against existing records in the system. The element is not returned for verified patients. Unverified patients always return the value PATRPT (Patient Reported) along with one of the following values: UNCERTAIN (Uncertain Reliability) UNRELIABLE (Unreliable)

Patient (R4).multipleBirthInteger | integer | | | 0..1 | The patient's birth order.

Patient (R4).name | HumanName | | Yes | 1..* | The patient's name.

Patient (R4).name.extension (humanNameAssemblyOrder) (also: extension (humanNameAssemblyOrder)) | Extension | | Yes | 0..* | This extension is populated only for organizations in the Netherlands. Name order for the contact. One of the following values: * NL1-Own Name * NL2-Partner Name * NL3-Partner Name followed by Maiden Name * NL4-Own Name followed by Partner Name URL: http://hl7.org/fhir/StructureDefinition/humanname-assembly-order

Patient (R4).name.family | string | | | 1..1 | The patient's family (last) name. Can contain a data-absent-reason extension with a value of "unknown" if the patient has an alias that cannot be returned as discrete elements or if the patient's preferred name replaces their full name.

Patient (R4).name.family.extension (data-absent-reason) (also: extension (data-absent-reason)) | Extension | | Yes | 0..1 | Returned as "unknown" for patients without family names.

Patient (R4).name.family.extension (humanNameOwnName) (also: extension (humanNameOwnName)) | Extension | | Yes | 0..1 | The portion of a patient's family name derived from the patient's own name.

Patient (R4).name.family.extension (humanNameOwnPrefix) (also: extension (humanNameOwnPrefix)) | Extension | | Yes | 0..1 | The prefix portion of a patient's family name derived from the patient's own surname.

Patient (R4).name.family.extension (humanNamePartnerName) (also: extension (humanNamePartnerName)) | Extension | | Yes | 0..1 | The portion of a patient's family name derived from the patient's partner's name.

Patient (R4).name.family.extension (humanNamePartnerPrefix) (also: extension (humanNamePartnerPrefix)) | Extension | | Yes | 0..1 | The prefix portion of a patient's family name derived from the patient's partner's surname.

Patient (R4).name.given | string | | Yes | 1..* | The patient's given name. Can include first and middle names.

Patient (R4).name.given.extension (namePartQualifier) (also: extension (namePartQualifier)) | Extension | | Yes | 0..2 | This extension is returned if initials or a preferred name are present. The entity qualifier extension code is IN for initials and is CL for preferred name. URL: http://hl7.org/fhir/StructureDefinition/iso21090-EN-qualifier

Patient (R4).name.prefix | string | | Yes | 0..1 | The patient's name prefix.

Patient (R4).name.suffix | string | | Yes | 0..* | The patient's name suffix. Acquired as a title due to academic, legal, employment or nobility status, etc.

Patient (R4).name.text | string | | | 1..1 | The patient's full name as a string.

Patient (R4).name.use | code | | | 1..1 | The purpose of the name. Can be "official", "usual", or "old".

Patient (R4).telecom | ContactPoint | | Yes | 0..* | Telephone numbers and email addresses for the patient, along with their use (home or work for example) and their preferred rank (which to contact first, second, third, etc).

Patient (R4).telecom.rank | positiveInt | | | 0..1 | The priority for permanent phone numbers or emails. 1 indicates the highest priority phone number, 2 indicates the second priority, etc . The preferred has a rank of 1. Additional emails have a null rank.

Patient (R4).telecom.system | code | | | 1..1 | The type of telecom. Potential values are: email phone fax url pager sms other

Patient (R4).telecom.use | code | | | 0..1 | If the telecom entry is a phone number, possible values are: home mobile work temp old Use is not returned for emails.

Patient (R4).telecom.value | string | | | 1..1 | Value of the telecom method. Can be an email address or phone number.

Sample request

```
GET https://hostname/instance/api/FHIR/R4/Patient/emtoVdevKvB6npMPDw0gAlQ3
```

Sample response


```
{
  "resourceType": "Patient",
  "id": "emtoVdevKvB6npMPDw0gAlQ3",
  "extension": [
    {
      "valueCodeableConcept": {
        "coding": [
          {
            "system": "urn:oid:1.2.840.114350.1.13.4304.2.7.10.698084.130.657370.334219900",
            "code": "female",
            "display": "female"
          }
        ]
      },
      "url": "http://open.epic.com/FHIR/StructureDefinition/extension/legal-sex"
    },
    {
      "valueCodeableConcept": {
        "coding": [
          {
```

```
          "system": "http://hl7.org/fhir/gender-identity",
          "code": "female",
          "display": "female"
        }
      ]
    },
    "url": "http://hl7.org/fhir/StructureDefinition/patient-genderIdentity"
  },
  {
    "valueCode": "F",
    "url": "http://hl7.org/fhir/us/core/StructureDefinition/us-core-birthsex"
  },
  {
    "extension": [
      {
        "valueCoding": {
          "system": "urn:oid:2.16.840.1.113883.6.238",
          "code": "2106-3",
          "display": "White"
        },
        "url": "ombCategory"
      },
      {
        "valueString": "White",
        "url": "text"
      }
    ],
    "url": "http://hl7.org/fhir/us/core/StructureDefinition/us-core-race"
  },
  {
    "extension": [
      {
        "valueCoding": {
          "system": "urn:oid:2.16.840.1.113883.6.238",
          "code": "2186-5",
          "display": "Not Hispanic or Latino"
        },
        "url": "ombCategory"
      },
      {
        "valueString": "Not Hispanic or Latino",
        "url": "text"
      }
    ],
    "url": "http://hl7.org/fhir/us/core/StructureDefinition/us-core-ethnicity"
  },
  {
    "valueCode": "184115007",
    "url": "http://hl7.org/fhir/us/core/StructureDefinition/us-core-sex"
  },
  {
    "valueCodeableConcept": {
      "coding": [
        {
          "system": "urn:oid:2.16.840.1.113883.6.96",
          "code": "446141000124107",
          "display": "Identifies as female gender (finding)"
        }
      ],
      "text": "Identifies as female gender (finding)"
    },
    "url": "http://hl7.org/fhir/us/core/StructureDefinition/us-core-genderIdentity"
  },
  {
    "extension": [
      {
        "valueCodeableConcept": {
          "coding": [
            {
              "system": "http://terminology.hl7.org/CodeSystem/v3-TribalEntityUS",
              "code": "65",
              "display": "Coquille Indian Tribe"
            }
          ],
          "text": "Coquille Indian Tribe"
        },
        "url": "tribalAffiliation"
      }
    ],
    "url": "http://hl7.org/fhir/us/core/StructureDefinition/us-core-tribal-affiliation"
  }
],
"identifier": [
  {
    "use": "usual",
    "type": {
      "text": "CEID"
    },
    "system": "urn:oid:1.2.840.114350.1.13.4977.1.7.3.688884.100",
```

```
      "value": "YYYJHGF3XBPV9JV"
    },
    {
      "use": "usual",
      "type": {
        "text": "EPIC"
      },
      "system": "urn:oid:1.2.840.114350.1.13.4304.2.7.5.737384.0",
      "value": "E4200"
    },
    {
      "use": "usual",
      "type": {
        "text": "EXTERNAL"
      },
      "system": "urn:oid:1.2.840.114350.1.13.4304.2.7.2.698084",
      "value": "Z6306"
    },
    {
      "use": "usual",
      "type": {
        "text": "FHIR"
      },
      "system": "http://open.epic.com/FHIR/StructureDefinition/patient-dstu2-fhir-id",
      "value": "ThZDEf8GAOd4vyLe4Ew5cKUh5Mv4TrbhFI7goJyWCxFYB"
    },
    {
      "use": "usual",
      "type": {
        "text": "FHIR STU3"
      },
      "system": "http://open.epic.com/FHIR/StructureDefinition/patient-fhir-id",
      "value": "emtoVdevKvB6npMPDw0gAlQ3"
    },
    {
      "use": "usual",
      "type": {
        "text": "INTERNAL"
      },
      "system": "urn:oid:1.2.840.114350.1.13.4304.2.7.2.698084",
      "value": "     Z6306"
    },
    {
      "use": "usual",
      "type": {
        "text": "MYCHARTLOGIN"
      },
      "system": "urn:oid:1.2.840.114350.1.13.4304.2.7.3.878082.110",
      "value": "FRANCESCA.FHIR"
    },
    {
      "use": "usual",
      "type": {
        "text": "WPRINTERNAL"
      },
      "system": "urn:oid:1.2.840.114350.1.13.4304.2.7.2.878082",
      "value": "703"
    },
    {
      "use": "usual",
      "system": "https://open.epic.com/FHIR/StructureDefinition/PayerMemberId",
      "value": "123456789"
    }
  ],
  "active": true,
  "name": [
    {
      "use": "official",
      "text": "Francesca Fhir Jr.",
      "family": "Fhir",
      "given": [
        "Francesca"
      ],
      "suffix": [
        "JR."
      ]
    },
    {
      "use": "usual",
      "text": "Francesca Fhir Jr.",
      "family": "Fhir",
      "given": [
        "Francesca"
      ],
      "suffix": [
        "JR."
      ]
    },
    {
```

```
    "use": "old",
    "text": "FHIR,FRANCINE",
    "family": "Fhir",
    "given": [
      "Francine"
    ]
  }
],
"telecom": [
  {
    "system": "phone",
    "value": "555-777-4321",
    "use": "home",
    "rank": 1
  },
  {
    "system": "phone",
    "value": "555-777-1234",
    "use": "mobile",
    "rank": 2
  },
  {
    "system": "email",
    "value": "example@example.com",
    "rank": 1
  }
],
"gender": "female",
"birthDate": "2019-01-24",
"deceasedBoolean": false,
"address": [
  {
    "use": "home",
    "line": [
      "1357 Amber Dr"
    ],
    "city": "BEAVERTON",
    "district": "WASHINGTON",
    "state": "OR",
    "postalCode": "97006",
    "country": "US",
    "period": {
      "start": "2022-01-18"
    }
  },
  {
    "use": "old",
    "line": [
      "3579 Ampersand Circle"
    ],
    "city": "BEAVERTON",
    "district": "WASHINGTON",
    "state": "OR",
    "postalCode": "97006",
    "country": "US"
  }
],
"maritalStatus": {
  "coding": [
    {
      "system": "http://terminology.hl7.org/CodeSystem/v3-NullFlavor",
      "code": "OTH",
      "display": "Other"
    }
  ],
  "text": "Single"
},
"contact": [
  {
    "relationship": [
      {
        "coding": [
          {
            "system": "http://snomed.info/sct",
            "code": "66839005",
            "display": "Father (person)"
          },
          {
            "system": "urn:oid:1.2.840.114350.1.13.4304.2.7.4.827665.1000",
            "code": "3",
            "display": "Father"
          }
        ],
        "text": "Father"
      }
    ],
    "name": {
      "use": "usual",
      "text": "Fhir,Matthew"
```

```
    },
    "telecom": [
      {
        "system": "phone",
        "value": "555-777-2345",
        "use": "home"
      }
    ],
    "address": {
      "use": "home",
      "line": [
        "1357 Amber Dr"
      ],
      "city": "BEAVERTON",
      "district": "WASHINGTON",
      "state": "OR",
      "postalCode": "97006",
      "country": "US"
    }
  },
  {
    "relationship": [
      {
        "coding": [
          {
            "system": "urn:oid:1.2.840.114350.1.13.4304.2.7.4.827665.1000",
            "code": "7",
            "display": "Grandparent"
          }
        ],
        "text": "Grandparent"
      }
    ],
    "name": {
      "use": "usual",
      "text": "Fhir,Rick"
    },
    "telecom": [
      {
        "system": "phone",
        "value": "555-777-5432",
        "use": "home"
      }
    ],
    "address": {
      "use": "home",
      "line": [
        "1357 Amber Dr"
      ],
      "city": "BEAVERTON",
      "district": "WASHINGTON",
      "state": "OR",
      "postalCode": "97006",
      "country": "US"
    }
  },
  {
    "relationship": [
      {
        "coding": [
          {
            "system": "http://snomed.info/sct",
            "code": "133932002",
            "display": "Caregiver (person)"
          },
          {
            "system": "urn:oid:1.2.840.114350.1.13.4304.2.7.4.827665.1000",
            "code": "22",
            "display": "Care Giver"
          }
        ],
        "text": "Care Giver"
      }
    ],
    "name": {
      "use": "official",
      "text": "Elena",
      "given": [
        "Elena"
      ]
    }
  }
],
"communication": [
  {
    "language": {
      "coding": [
        {
          "system": "urn:ietf:bcp:47",
```

```
            "code": "es",
            "display": "Spanish"
          }
        ],
        "text": "Spanish"
      },
      "preferred": true
    }
  ],
  "generalPractitioner": [
    {
      "reference": "Practitioner/eNGYW36Nj8CK.JrLKbizkUQ3",
      "type": "Practitioner",
      "display": "H. L. Seven"
    }
  ],
  "managingOrganization": {
    "reference": "Organization/e.pDiuIbjczxCdZQuupGLmg3",
    "display": "Community Health Hospitals"
  }
}
```


Change log

Epic Version | Description | Type

August 2024 and May 2024 with SU | Patient.Read requests now return temporary addresses for organizations in Norway. Previously, temporary addresses were returned only for organizations in Singapore.

November 2023 | The patient-birthTime extension now appears as a child extension on the birthDate element when present, to conform with the FHIR specification. Previously, patient-birthTime was returned as a root-level extension on the Patient resource. | Breaking Change

November 2022 | Patient.contact.relationship previously only returned "C" for emergency contact or "E" for employer. When this element is "C" for emergency contact, additional elements about that contact's relationship to the patient are returned. | Non-substantive change

22.1.4 Patient.Search (Demographics) (R4)

File: site/apis/22-Identification-Individuals/1-R4/932-Patient-Search-Demographics-R4.html

Epic API ID | 932

FHIR version | R4

Categories | Identification Individuals

API type | USCDI

A la carte | Industry-Standard Level 1 API

USCDI | Yes

Keywords | Care Team Members;Patient Demographics;First name;Last name;Middle name;initial;Suffix;Birth sex;Date of birth;Race;Ethnicity;Preferred language;Address;Phone number;Previous name

Available in inpatient and other contexts | Yes

ONC certification products | EpicCare Ambulatory Base, EpicCare Inpatient Base

ONC certification versions | August 2019

HTTP method | GET

URL template | api/FHIR/R4/Patient?address={address}&address-city={address-city}&address-postalcode={address-postalcode}&address-state={address-state}&birthdate={birthdate}&family={family}&gender={gender}&given={given}&identifier={identifier}&name={name}&own-name={own-name}&own-prefix={own-prefix}&partner-name={partner-name}&partner-prefix={partner-prefix}&telecom={telecom}&legal-sex={legal-sex}

Supports OAuth 2.0 | True

Supported user types | Backend Systems and Non-OAuth 2.0, Clinicians or Administrative Users, Patients

Performs scope validation | False

Source | https://fhir.epic.com/Specifications?api=932

Description

Patient.$match (Patient Match) (R4)

Alternative: If you need to identify a single patient record, it's strongly recommended to use Patient.$match (Demographics) (R4) instead. This is especially useful for backend integrations whenever sufficient patient demographics are available. Patient.Search should be used to get a list of patients matching a set of parameters rather than matching a single patient record. Improper use of Patient.Search could lead to patient safety concerns such as reading and writing data using the wrong patient record.

This web service allows filtering or searching for patients and retrieves patient demographic information from a patient's chart for each matching patient record. See the

best practices document

for our recommended patient matching criteria.

The minimum data set requirement for a patient to be returned is configurable at each Epic organization. By default, one of the following minimum data sets is required:

* Identifier such as FHIR ID, National ID, or Identity ID (such as MRN)

* Given Name + Family Name + Birthdate

* Given Name + Family Name + Legal Sex + Phone Number/Email

A non-patient user must have appropriate security to consume search details, demographic details, and/or PCP details included in the Patient resource.

This web service respects all patient-facing security for demographic information when used in the context of a patient as the user.

If an Epic organization has configured service area restrictions, the user accessing this FHIR resource must also be authorized to view patients in the target service area.

When two patients are merged, a Patient.Search on the target (surviving) patient works normally. The source patient returns a 404 error, as we consider the source patient FHIR ID to be invalid.

Request parameters

Name | Type | Optional | Array | Cardinality | Description
_count | number | Optional | Yes | | Number of results per page.
_id | token | Optional | Yes | | FHIR resource IDs for the desired resources. Can be used in combination with _count, _include, and _revInclude. All others will be ignored.
_include | string | Optional | Yes | | Used to indicate which referenced resources to include in the search bundle.
_revinclude | string | Optional | Yes | | Used to include Provenance or AuditEvent resources that refer to search results, when available.
address | string | Conditional | Yes | | The patient's street address, in the format address=<address line 1>&address=<address line 2>...
address-city | string | Conditional | Yes | | The city for the patient's home address.
address-postalcode | string | Conditional | Yes | | The postal code for the patient's home address.
address-state | string | Conditional | Yes | | The state for the patient's home address.
birthdate | date | Conditional | Yes | | The patient's date of birth in the format YYYY-MM-DD
doc-type | token | Optional | Yes | | Document Type. Applies only to organizations in Singapore.
family | string | Conditional | Yes | | The patient's family (last) name. If own-name is provided as a search parameter, it is used instead of the family parameter.
gender | token | Conditional | Yes | | The patient's gender. If the legal-sex parameter is also included, the gender parameter is ignored.
given | string | Conditional | Yes | | The patient's given name. First and middle names are supported.
identifier | token | Conditional | Yes | 0..* | The patient's identifier. Can be formatted as either <system>|<id> or just <id>. When specifying a <system> value as an OID, including the urn:oid: prefix is optional and is not case sensitive. When searching without a <system> value, Epic attemps lookups on all common identifier systems. Valid <systems>: MPI IDs (e.g. Patient MRN). Epic first searches active MPI IDs, and falls back to a historical MPI ID search if unsuccessful. MPI ID Type system values are highly configurable by the organization. MPI ID Type Descriptor MPI ID Type OID MPI ID Type HL7 ID Type Epic MyChart login ID Epic OID for MyChart login Epic Care Everywhere ID CEID National Identifier US Social Security Number: 2.16.840.1.113883.4.1 UK NHS ID: 2.16.840.1.113883.2.1.4.1 Dutch BSN: 2.16.840.1.113883.2.4.6.3 or http://fhir.nl/fhir/NamingSystem/bsn Finnish National ID: 1.2.246.21 Australian Medicare Number: http://ns.electronichealth.net.au/id/medicare-number Singapore Document ID https://open.epic.com/singapore/doc-id FHIR ID http://open.epic.com/FHIR/StructureDefinition/patient-fhir-id
legal-sex | token | Conditional | Yes | | The patient's legal sex. Takes precedence over the gender parameter.
name | string | Conditional | Yes | | Any part of the patient's name. Example formats: name=<given name> name=<family name> name=<given name>%20<family name> This parameter is ignored when any of the following discrete name parameters are also provided: family given own-name
own-name | string | Conditional | Yes | | The patient's own last name. Usage is more prevalent in locales outside of the US. If provided, this value as well as own-prefix, partner-name, and partner-prefix are used instead of the family parameter.
own-prefix | string | Conditional | Yes | | The patient's own prefix. Usage is more prevalent in locales outside of the US.
partner-name | string | Conditional | Yes | | The patient's spouse's last name. Usage is more prevalent in locales outside of the US.
partner-prefix | string | Conditional | Yes | | The patient's spouse's prefix. Usage is more prevalent in locales outside of the US.
telecom | token | Conditional | Yes | | The patient's phone number or email. Phone number validation is skipped if the first character is #. If the first character is + then the number is treated as an international number. Only one email address is supported. If multiple are supplied, only the first instance is used.

Request parameters (post-filtered search parameters)

Name | Type | Optional | Array | Cardinality | Description
active | token | Optional | Yes | 0..1 | Whether the patient record is active.
address-use | token | Optional | Yes | | Specifies the type of address: home – A permanent address old – A previous permanent address temp – A temporary address Temporary addresses behavior varies by Epic version: May 2025 or later – Returned only if the Epic organization has configured temporary addresses to be visible in FHIR responses (applies to all locales). Prior to May 2025 – Singapore – Always returned. Norway – Always returned if using: August 2024 version, or May 2024 version with special updates.
death-date | date | Optional | Yes | | The date or date/time of death in the format yyyy-mm-dd or yyyy-mm-ddThh:mm:ss[Z|(+|-)hh:mm]
email | token | Optional | Yes | | Email address for the patient.
general-practitioner | reference | Optional | Yes | | The patient's primary care provider (PCP) FHIR ID. Whether and which generalPractictioner references are searched depends on setup at each organization.
language | token | Optional | Yes | | The code for the patient's language. For organizations outside of Singapore, this is the IETF BCP 47 language code.
link | reference | Optional | Yes | | The FHIR ID for other Patient resources linked to the patient as a result of a merge.
organization | reference | Optional | Yes | | FHIR Location resource for the patient's primary service area.
phone | token | Optional | Yes | | Telephone number for the patient.

Response elements

Name | Type | Optional | Array | Cardinality | Description
Patient (R4) | Resource
Patient (R4).active | boolean | | | 1..1 | Whether the patient record is active.
Patient (R4).address | Address | | Yes | 0..* | The patient's current address, as well as any previous or temporary addresses, if applicable. The patient's current address has a use code of "home". If the patient also has one or more previous addresses, each previous address has a use code of "old". The patient's temporary address has a use code of "temp".

Patient (R4).address.city | string | | | 0..1 | The city that the patient lives in.

Patient (R4).address.country | String | | | 0..1 | The country that the patient lives in.

Patient (R4).address.district | String | | | 0..1 | The county that the patient lives in.

Patient (R4).address.line | string | | Yes | 0..* | The patient's street address.

Patient (R4).address.line.extension (additionalLocator) (also: extension (additionalLocator)) | Extension | | Yes | 0..1 | This extension is returned only for organizations in Singapore. The patient's floor. URL: http://hl7.org/fhir/StructureDefinition/iso21090-ADXP-additionalLocator

Patient (R4).address.line.extension (buildingName) (also: extension (buildingName)) | Extension | | Yes | 0..1 | This extension is returned only for organizations in Singapore. The patient's building name. URL: http://open.epic.com/FHIR/StructureDefinition/extension/buildingName

Patient (R4).address.line.extension (houseNumber) (also: extension (houseNumber)) | Extension | | Yes | 0..1 | For organizations in the Netherlands and Singapore, this element represents the portion of a patient or contact's address that is their house number. URL: http://hl7.org/fhir/StructureDefinition/iso21090-ADXP-houseNumber

Patient (R4).address.line.extension (streetName) (also: extension (streetName)) | Extension | | Yes | 0..* | For organizations in the Netherlands and Singapore, this element represents the portion of a patient or contact's address that includes the name of their street. URL: http://hl7.org/fhir/StructureDefinition/iso21090-ADXP-streetName

Patient (R4).address.line.extension (unitID) (also: extension (unitID)) | Extension | | Yes | 0..1 | This extension is returned only for organizations in Singapore. The patient's unit number. URL: http://hl7.org/fhir/StructureDefinition/iso21090-ADXP-unitID

Patient (R4).address.period | Period | | | 0..1 | The start date – and optionally, end date – for when the address is valid. Returned for the current address if the information is available. Starting in the May 2025 version of Epic, also returned for previous and temporary addresses if the information is available.

Patient (R4).address.postalCode | string | | | 0..1 | The patient's postal code.

Patient (R4).address.state | string | | | 0..1 | The state where the patient lives.

Patient (R4).address.text | String | | | 0..1 | The patient's full address as a string. This is formatted based on the country the address is in. For U.S. addresses, to meet the standards laid out in the Project US@ Technical Specifications, patient addresses format automatically for patient matching purposes.

Patient (R4).address.use | code | | | 1..1 | Specifies the type of address: home – A permanent address old – A previous permanent address temp – A temporary address Temporary addresses behavior varies by Epic version: May 2025 or later – Returned only if the Epic organization has configured temporary addresses to be visible in FHIR responses (applies to all locales). Prior to May 2025 – Singapore – Always returned. Norway – Always returned if using: August 2024 version, or May 2024 version with special updates.

Patient (R4).birthDate | date | | | 1..1 | The patient's date of birth in the format YYYY-MM-DD

Patient (R4).birthDate.extension (birthTime) (also: extension (birthTime)) | Extension | | | 0..1 | The patient's time of birth. This extension follows the HL7 birthTime specification. Prior to the November 2023 verison of Epic, this extension was returned at the Patient resource level. Beginning in the November 2023 version of Epic, this is now returned underneath the BirthDate element. URL: http://hl7.org/fhir/StructureDefinition/patient-birthTime

Patient (R4).birthDate.extension (dataAbsentReason) (also: extension (dataAbsentReason)) | Extension | | | 0..1 | Available starting with the November 2024 version of Epic. If the patient's birth date is not recorded, this extension is returned with a value of "unknown". URL: http://hl7.org/fhir/StructureDefinition/data-absent-reason

Patient (R4).communication | BackboneElement | | Yes | 0..* | Languages used to communicate with the patient, along with an indicator of which is preferred.

Patient (R4).communication.extension (comment) (also: extension (comment)) | Extension | | Yes | 0..1 | A comment about the patient's language proficiency. This extension is returned only for organizations in the Netherlands. URL: http://nictiz.nl/fhir/StructureDefinition/Comment

Patient (R4).communication.extension (patient-proficiency) (also: extension (patient-proficiency)) | Extension | | Yes | 0..3 | Container extension that holds details about the patient's language proficiency. Contains two child extensions which indicate the type of language proficiency and the level of that proficiency. This extension is returned only for organizations in the Netherlands. URL: http://nictiz.nl/fhir/StructureDefinition/patient-proficiency

Patient (R4).communication.extension (patient-proficiency).extension (v3-LanguageAbilityMode) (also: extension (v3-LanguageAbilityMode)) | Extension | | Yes | 0..1 | Patient's language proficiency type. This is a valueCoding wherein the following code and display values are supported: RSP - Received spoken ESP - Expressed spoken RWR - Received written System value of http://terminology.hl7.org/CodeSystem/v3-LanguageAbilityMode URL: type

Patient (R4).communication.extension (patient-proficiency).extension (v3-LanguageAbilityProficiency) (also: extension (v3-LanguageAbilityProficiency)) | Extension | | Yes | 0..1 | Patient's language proficiency level. This is a valueCoding wherein the following code and display values are supported: E - Excellent G - Good F - Fair P - Poor System value of http://terminology.hl7.org/CodeSystem/v3-LanguageAbilityProficiency URL: level

Patient (R4).communication.language | CodeableConcept | | | 1..1 | The patient's general language, onsite care language, and spoken language.

Patient (R4).communication.preferred | boolean | | | 0..1 | Whether the language is the patient's preferred language.

Patient (R4).communication.preferred.extension (patient-preferenceType) (also: extension (patient-preferenceType)) | Extension | | Yes | 0..1 | The preferred mode of communication for the patient's preferred language. This can be either verbal or written. Returned starting in the May 2025 version of Epic. Returned with system http://hl7.org/fhir/language-preference-type. URL: http://hl7.org/fhir/StructureDefinition/patient-preferenceType

Patient (R4).contact | BackboneElement | | Yes | 0..* | Details for the patient's contacts. Patient contacts include any documented family members, emergency contacts, care givers, acquaintances, and employers.

Patient (R4).contact.address | Address | | | 0..1 | The contact address. For responses to a patient-facing application, this element is not returned for contacts linked to a patient record. For organizations in the Netherlands, this element represents an nl-core-address value.

Patient (R4).contact.name | HumanName | | | 1..1 | The contact's preferred name. The system determines this from the contact's linked patient record if available. For contacts linked to a patient record, only the patient's official first name is returned in patient context. For organizations in the Netherlands, this element represents an nl-core-humanname value.

Patient (R4).contact.name.extension (humanname-assembly-order) (also: extension (humanname-assembly-order)) | Extension | | Yes | 0..1 | This extension is populated only for organizations in the Netherlands. Name order for the contact. One of the following values: NL1 - Own Name NL2 - Partner Name NL3 - Partner Name followed by Maiden Name NL4 - Own Name followed by Partner Name URL: http://hl7.org/fhir/StructureDefinition/humanname-assembly-order

Patient (R4).contact.organization | Reference | | | 0..1 | An Organization reference that represents the patient's employer. Returned when contact.relationship.code is E.

Patient (R4).contact.period | Period | | | 0..1 | The start and end dates for the patient contact.

Patient (R4).contact.relationship | CodeableConcept | | Yes | 0..* | The contact's relationship to the patient. This element can return multiple values. It will always return one or more Epic category values for the contact's relationship to the patient. In addition, it can return one or more of the following: For organizations in the Netherlands, either a Relationship (RelatieCodelijst) code system value or a role (RolCodelijst) code system value. For all other organizations, can return either a code system value – such as "C" (emergency contact) or "E" (employer) – or a RoleClass code system value – such as "GUARD" or "AGNT".

Patient (R4).contact.telecom | ContactPoint | | Yes | 0..* | Telephone numbers and email address for the contact. For responses to a patient-facing application, this element is not returned for contacts linked to a patient record. For organizations in the Netherlands, this element represents an

nl-core-contactpoint value.

Patient (R4).contact.telecom.rank | positiveInt | | | 0..1 | The priority for permanent phone numbers or emails. 1 indicates the highest priority phone number, 2 indicates the second priority, and so on. Starting in the May 2025 version of Epic, rank is returned for the phone numbers of patient contacts.

Patient (R4).contact.telecom.system | code | | | 0..1 | The type of telecom. Potential values are: email phone

Patient (R4).contact.telecom.use | code | | | 0..1 | If the telecom entry is a phone number, possible values are: home mobile work

Patient (R4).contact.telecom.value | string | | | 1..1 | Value of the telecom method. Can be an email address or phone number.

Patient (R4).deceasedBoolean | boolean | | | 0..1 | Whether the patient is deceased.

Patient (R4).deceasedDateTime | dateTime | | | 0..1 | The date and time of death.

Patient (R4).extension (birth-location) (also: extension (birth-location)) | Extension | | Yes | 0..1 | A reference to a newborn's birth facility. URL: http://open.epic.com/FHIR/StructureDefinition/extension/birth-location

Patient (R4).extension (birth-sex) (also: extension (birth-sex)) | Extension | | Yes | 0..1 | The patient's sex assigned at birth. This element is not returned for organizations in the Netherlands. URL: http://hl7.org/fhir/us/core/StructureDefinition/us-core-birthsex

Patient (R4).extension (calculated-pronouns-to-use-for-text) (also: extension (calculated-pronouns-to-use-for-text)) | Extension | | Yes | 0..* | The patient's pronouns to use when generating text. Available starting in the November 2023 version of Epic. This is an Epic-calculated value based on specified pronouns, the patient's gender identity, or the patient's legal sex. Consider using extension (individual-pronouns) instead of this one. One of the following: A value from LOINC Answer List LL5144-2 Personal pronouns EP-PS-DO-NOT-USE-PRONOUNS, from the Epic-defined pronoun set https://open.epic.com/FHIR/Epic/pronoun-set URL: http://open.epic.com/FHIR/StructureDefinition/extension/calculated-pronouns-to-use-for-text

Patient (R4).extension (gender-identity) (also: extension (gender-identity)) | Extension | | Yes | 0..1 | The patient's gender identity. URL: http://hl7.org/fhir/StructureDefinition/patient-genderIdentity

Patient (R4).extension (individual-pronouns) (also: extension (individual-pronouns)) | Extension | | Yes | 0..* | The pronouns to use when communicating about an individual. Available starting in the November 2024 version of Epic. URL: http://hl7.org/fhir/StructureDefinition/individual-pronouns

Patient (R4).extension (legal-sex) (also: extension (legal-sex)) | Extension | | Yes | 0..1 | The patient's legal sex. URL: http://open.epic.com/FHIR/StructureDefinition/extension/legal-sex

Patient (R4).extension (nationality) (also: extension (nationality)) | Extension | | Yes | 0..1 | The patient's nationality. This extension is returned only for organizations in the Singapore. URL: http://hl7.org/fhir/StructureDefinition/patient-nationality

Patient (R4).extension (patient-preferred-provider-language) (also: extension (patient-preferred-provider-language)) | Extension | | Yes | 0..1 | The patient's preferred provider language, used for scheduling. URL: http://open.epic.com/FHIR/STU3/StructureDefinition/patient-preferred-provider-language

Patient (R4).extension (patient-preferred-provider-sex) (also: extension (patient-preferred-provider-sex)) | Extension | | Yes | 0..1 | The patient's preferred provider sex, used for scheduling. URL: http://open.epic.com/FHIR/STU3/StructureDefinition/patient-preferred-provider-sex

Patient (R4).extension (patient-type) (also: extension (patient-type)) | Extension | | Yes | 0..* | The type of patient, such as Confidential or Employee. URL: http://open.epic.com/FHIR/StructureDefinition/extension/patient-type

Patient (R4).extension (patient-unmerge-source) (also: extension (patient-unmerge-source)) | Extension | | Yes | 0..* | This extension contains a collection of extensions that represent the metadata for a patient record unmerge from the perspective of the source patient. If the patient is involved as the source patient in multiple unmerges, this set of extensions is returned for each unmerge event. URL: https://open.epic.com/FHIR/StructureDefinition/patient-unmerge-source

Patient (R4).extension (patient-unmerge-source).extension (patient-merge-unmerge-instant) (also: extension (patient-merge-unmerge-instant)) | Extension | | Yes | 0..1 | The instant the patient merge event occurred. URL: https://open.epic.com/FHIR/StructureDefinition/patient-merge-unmerge-instant

Patient (R4).extension (patient-unmerge-source).extension (patient-unmerge-current-target-reference) (also: extension (patient-unmerge-current-target-reference)) | Extension | | Yes | 0..1 | A reference to the current FHIR ID of the unmerge event's target patient. URL: https://open.epic.com/FHIR/StructureDefinition/patient-unmerge-current-target-reference

Patient (R4).extension (patient-unmerge-source).extension (patient-unmerge-old-target-reference) (also: extension (patient-unmerge-old-target-reference)) | Extension | | Yes | 0..1 | A reference to the FHIR ID of the unmerge event's target patient at the time of the merge. URL: https://open.epic.com/FHIR/StructureDefinition/patient-unmerge-old-target-reference

Patient (R4).extension (patient-unmerge-source).extension (patient-unmerge-original-source-reference) (also: extension (patient-unmerge-original-source-reference)) | Extension | | Yes | 0..1 | A reference to the current FHIR ID of the unmerge event's source patient. URL: https://open.epic.com/FHIR/StructureDefinition/patient-unmerge-original-source-reference

Patient (R4).extension (patient-unmerge-source).extension (patient-unmerge-reference-old) (also: extension (patient-unmerge-reference-old)) | Extension | | Yes | 0..1 | A reference to the FHIR ID of the unmerge event's source patient at the time of the merge. URL: https://open.epic.com/FHIR/StructureDefinition/patient-unmerge-reference-old

Patient (R4).extension (patient-unmerge-target) (also: extension (patient-unmerge-target)) | Extension | | Yes | 0..* | This extension contains a collection of extensions that represent the metadata for a patient record unmerge from the perspective of the target patient. If the patient is involved as the target patient in multiple unmerges, this set of extensions is returned for each unmerge event. URL: https://open.epic.com/FHIR/StructureDefinition/patient-unmerge-target

Patient (R4).extension (patient-unmerge-target).extension (patient-merge-unmerge-instant) (also: extension (patient-merge-unmerge-instant)) | Extension | | Yes | 0..1 | The instant the patient merge event occurred. URL: https://open.epic.com/FHIR/StructureDefinition/patient-merge-unmerge-instant

Patient (R4).extension (patient-unmerge-target).extension (patient-unmerge-old-target-reference) (also: extension (patient-unmerge-old-target-reference)) | Extension | | Yes | 0..1 | A reference to the FHIR ID of the unmerge event's target patient at the time of the merge. URL: https://open.epic.com/FHIR/StructureDefinition/patient-unmerge-old-target-reference

Patient (R4).extension (patient-unmerge-target).extension (patient-unmerge-original-source-reference) (also: extension (patient-unmerge-original-source-reference)) | Extension | | Yes | 0..1 | A reference to the current FHIR ID of the unmerge event's source patient. URL: https://open.epic.com/FHIR/StructureDefinition/patient-unmerge-original-source-reference

Patient (R4).extension (patient-unmerge-target).extension (patient-unmerge-reference-new) (also: extension (patient-unmerge-reference-new)) | Extension | | Yes | 0..1 | A reference to the FHIR ID of the unmerge event's source patient after the unmerge. URL: https://open.epic.com/FHIR/StructureDefinition/patient-unmerge-reference-new

Patient (R4).extension (patient-unmerge-target).extension (patient-unmerge-reference-old) (also: extension (patient-unmerge-reference-old)) | Extension | | Yes | 0..1 | A reference to the FHIR ID of the unmerge event's source patient at the time of the merge. URL: https://open.epic.com/FHIR/StructureDefinition/patient-unmerge-reference-old

Patient (R4).extension (sex-for-clinical-use) (also: extension (sex-for-clinical-use)) | Extension | | Yes | 0..1 | The patient's sex for clinical decision making. This is an Epic-calculated value. If the patient's sex, gender, and clinical information indicate the patient is not unambiguously a cisgender male or female, the extension is not included. URL: http://open.epic.com/FHIR/StructureDefinition/extension/sex-for-clinical-use

Patient (R4).extension (us-core-ethnicity) (also: extension (us-core-ethnicity)) | Extension | | Yes | 0..1 | The patient's ethnicity parent extension. This element is not returned for organizations in the Netherlands or Singapore. For other organizations, the value returned depends on the mapping

owned by the Epic organization. For organizations in the US, this mapping is typically based on regulatory standards set by the CDC. URL: http://hl7.org/fhir/us/core/StructureDefinition/us-core-ethnicity

Patient (R4).extension (us-core-ethnicity).extension (ombCategory) (also: extension (ombCategory)) | Extension | | Yes | 0..1 | The patient's ethnicity. URL: ombCategory

Patient (R4).extension (us-core-ethnicity).extension (text) (also: extension (text)) | Extension | | Yes | 0..1 | Textual display value for the OMB ethnicity code. The following mapping is used: OMB Ethnicity Code Text 2135-2 Hispanic or Latino 2186-5 Not Hispanic or Latino Default Value Unknown URL: text

OMB Ethnicity Code | Text

2135-2 | Hispanic or Latino

2186-5 | Not Hispanic or Latino

Default Value | Unknown

Patient (R4).extension (us-core-genderIdentity) (also: extension (us-core-genderIdentity)) | Extension | | Yes | 0..1 | The patient’s gender identity URL: http://hl7.org/fhir/us/core/StructureDefinition/us-core-genderIdentity

Patient (R4).extension (us-core-race) (also: extension (us-core-race)) | Extension | | Yes | 0..1 | The patient's race. This element is not returned for organizations in the Netherlands or Singapore. For other organizations, the value returned depends on the mapping owned by the Epic organization. For organizations in the US, this mapping is typically based on regulatory standards set by the CDC. URL: http://hl7.org/fhir/us/core/StructureDefinition/us-core-race

Patient (R4).extension (us-core-race).extension (detailed) (also: extension (detailed)) | Extension | | Yes | 0..* | Detailed CDC race code. URL: detailed

Patient (R4).extension (us-core-race).extension (ombCategory) (also: extension (ombCategory)) | Extension | | Yes | 0..* | Race code according to the OMB race category valueset. URL: ombCategory

Patient (R4).extension (us-core-race).extension (text) (also: extension (text)) | Extension | | Yes | 0..* | Textual display value for the OMB race code. The following mapping is used: OMB Race Code Text 1002-5 American Indian or Alaska Native 2028-9 Asian 2054-5 Black or African American 2076-8 Native Hawaiian or Other Pacific Islander 2106-3 White 2131-1 Other Race Default Value Unknown URL: text

OMB Race Code | Text

1002-5 | American Indian or Alaska Native

2028-9 | Asian

2054-5 | Black or African American

2076-8 | Native Hawaiian or Other Pacific Islander

2106-3 | White

2131-1 | Other Race

Default Value | Unknown

Patient (R4).extension (us-core-sex) (also: extension (us-core-sex)) | Extension | | Yes | 0..1 | The patient’s most reliable sex for clinical decision making. If the patient's sex cannot be reliably determined, nothing is returned. URL: http://hl7.org/fhir/us/core/StructureDefinition/us-core-sex

Patient (R4).extension (us-core-tribal-affiliation) (also: extension (us-core-tribal-affiliation)) | Extension | | Yes | 0..1 | The patient’s tribal affiliation. URL: http://hl7.org/fhir/us/core/StructureDefinition/us-core-tribal-affiliation

Patient (R4).extension (us-core-tribal-affiliation).extension (tribalAffiliation) (also: extension (tribalAffiliation)) | Extension | | Yes | 0..1 | The patient's tribal affiliation code.

Patient (R4).gender | code | | | 1..1 | The patient's legal sex.

Patient (R4).generalPractitioner | Reference | | Yes | 0..* | The patient's Primary Care Provider (PCP). Reference to a Practitioner resource. For organizations in UK with EPS enabled at the system level, also contains an identifier-based reference to the patient's care organization.

Patient (R4).id | id | | | 1..1 | The Patient FHIR ID.

Patient (R4).identifier | Identifier | | Yes | 1..* | The patient's identifiers. Includes the following: MPI IDs (such as MRNs) Epic MyChart login IDs Epic database IDs Payer Member IDs National IDs FHIR ID Care Everywhere ID For organizations in Singapore, the patient’s document ID, type, and expiry date.

Patient (R4).identifier.period | Period | | | 0..1 | The expiration date of the patient's identification document in Singapore.

Patient (R4).identifier.system | String | | | 1..1 | Epic Identity IDs (such as Patient MRN) Identity ID OID Identity ID HL7 Assigning Authority as the "Text" value. Epic MyChart IDs MyChart login OID Epic Care Everywhere ID CEID Epic internal ID Generated OID for the Epic internal patient ID Epic external ID Generated OID for the Epic external patient ID Payer Member ID https://open.epic.com/FHIR/StructureDefinition/PayerMemberId National Identifier US Social Security Number: 2.16.840.1.113883.4.1 UK NHS ID: 2.16.840.1.113883.2.1.4.1 or https://fhir.nhs.uk/Id/nhs-number Dutch BSN: 2.16.840.1.113883.2.4.6.3 or http://fhir.nl/fhir/NamingSystem/bsn Finnish National ID: 1.2.246.21 United Arab Emirates: 2.16.840.1.113883.3.7326.10.1 Australian Medicare Number: http://ns.electronichealth.net.au/id/medicare-number Singapore Document ID https://open.epic.com/singapore/doc-id FHIR ID STU3 and up: http://open.epic.com/FHIR/StructureDefinition/patient-fhir-id DSTU2: http://open.epic.com/FHIR/StructureDefinition/patient-dstu2-fhir-id

Patient (R4).identifier.type | CodeableConcept | | | 0..1 | The patient's identifier type. In Singapore, this is the patient's identification document type.

Patient (R4).identifier.type.coding | Coding | | Yes | 0..* | The type coding.

Patient (R4).identifier.type.coding.code | String | | | | The type code. Epic external ID "um" Payer Member ID "MB" Australian Medicare Number "MC"

Patient (R4).identifier.type.coding.system | String | | | | The code system. Epic external ID http://hl7.org/fhir/us/carin-bb/CodeSystem/C4BBIdentifierType Payer Member ID http://terminology.hl7.org/CodeSystem/v2-0203 Australian Medicare Number http://terminology.hl7.org/CodeSystem/v2-0203

Patient (R4).identifier.value | String | | | 1..1 | The patient's ID. For organizations in Singapore, this can also be the patient's identification document ID.

Patient (R4).identifier.value.extension (rendered-value) (also: extension (rendered-value)) | Extension | | Yes | | Contains the patient's masked national ID if the organization masks national identifiers. URL: http://hl7.org/fhir/StructureDefinition/rendered-value

Patient (R4).link | BackboneElement | | Yes | 0..* | Contains links to other patient records if the patient record was involved in a merge. Each link element represents a single merge event. If the patient was involved in multiple merges, multiple Link elements are returned. Starting in the February 2024 version of Epic, the 30 most recent merge events are returned instead of all merge events.

Patient (R4).link.extension (patient-merge-target-reference) (also: extension (patient-merge-target-reference)) | Extension | | Yes | 0..1 | The FHIR ID reference to the target patient. In a merge, the target patient refers to the surviving patient. URL: https://open.epic.com/FHIR/StructureDefinition/patient-merge-target-reference

Patient (R4).link.extension (patient-merge-unmerge-instant) (also: extension (patient-merge-unmerge-instant)) | Extension | | Yes | 0..1 | The instant the patient merge event occurred. URL: https://open.epic.com/FHIR/StructureDefinition/patient-merge-unmerge-instant

Patient (R4).link.other | Reference | | | 0..1 | A Patient reference to the source patient. In a merge, the source patient is the patient that goes away.

Patient (R4).link.type | code | | | 1..1 | The type of link between Patient resources. This is always set to "replaces". The Patient FHIR ID in the link.extension (patient-merge-target-reference) element replaces the Patient FHIR ID referenced in the link.other element.

Patient (R4).managingOrganization | Reference | | | 0..1 | The patient’s primary service area. Reference to an Organization resource.

Patient (R4).maritalStatus | CodeableConcept | | | 0..1 | The patient's marital status.

Patient (R4).meta | Meta | | | | Metadata about the resource.

Patient (R4).meta.security | Coding | | Yes | 0..2 | The patient’s unverified status. Available starting in the May 2024 version of Epic, and in February 2024 and November 2023 with special updates. This is used to track new patient records that might need to be reconciled against existing records in the system. The element is not returned for verified patients. Unverified patients always return the value PATRPT (Patient Reported) along with one of the following values: UNCERTAIN (Uncertain Reliability) UNRELIABLE (Unreliable)

Patient (R4).multipleBirthInteger | integer | | | 0..1 | The patient's birth order.

Patient (R4).name | HumanName | | Yes | 1..* | The patient's name.

Patient (R4).name.extension (humanNameAssemblyOrder) (also: extension (humanNameAssemblyOrder)) | Extension | | Yes | 0..* | This extension is populated only for organizations in the Netherlands. Name order for the contact. One of the following values: * NL1-Own Name * NL2-Partner Name * NL3-Partner Name followed by Maiden Name * NL4-Own Name followed by Partner Name URL: http://hl7.org/fhir/StructureDefinition/humanname-assembly-order

Patient (R4).name.family | string | | | 1..1 | The patient's family (last) name. Can contain a data-absent-reason extension with a value of "unknown" if the patient has an alias that cannot be returned as discrete elements or if the patient's preferred name replaces their full name.

Patient (R4).name.family.extension (data-absent-reason) (also: extension (data-absent-reason)) | Extension | | Yes | 0..1 | Returned as "unknown" for patients without family names.

Patient (R4).name.family.extension (humanNameOwnName) (also: extension (humanNameOwnName)) | Extension | | Yes | 0..1 | The portion of a patient's family name derived from the patient's own name.

Patient (R4).name.family.extension (humanNameOwnPrefix) (also: extension (humanNameOwnPrefix)) | Extension | | Yes | 0..1 | The prefix portion of a patient's family name derived from the patient's own surname.

Patient (R4).name.family.extension (humanNamePartnerName) (also: extension (humanNamePartnerName)) | Extension | | Yes | 0..1 | The portion of a patient's family name derived from the patient's partner's name.

Patient (R4).name.family.extension (humanNamePartnerPrefix) (also: extension (humanNamePartnerPrefix)) | Extension | | Yes | 0..1 | The prefix portion of a patient's family name derived from the patient's partner's surname.

Patient (R4).name.given | string | | Yes | 1..* | The patient's given name. Can include first and middle names.

Patient (R4).name.given.extension (namePartQualifier) (also: extension (namePartQualifier)) | Extension | | Yes | 0..2 | This extension is returned if initials or a preferred name are present. The entity qualifier extension code is IN for initials and is CL for preferred name. URL: http://hl7.org/fhir/StructureDefinition/iso21090-EN-qualifier

Patient (R4).name.prefix | string | | Yes | 0..1 | The patient's name prefix.

Patient (R4).name.suffix | string | | Yes | 0..* | The patient's name suffix. Acquired as a title due to academic, legal, employment or nobility status, etc.

Patient (R4).name.text | string | | | 1..1 | The patient's full name as a string.

Patient (R4).name.use | code | | | 1..1 | The purpose of the name. Can be "official", "usual", or "old".

Patient (R4).telecom | ContactPoint | | Yes | 0..* | Telephone numbers and email addresses for the patient, along with their use (home or work for example) and their preferred rank (which to contact first, second, third, etc).

Patient (R4).telecom.rank | positiveInt | | | 0..1 | The priority for permanent phone numbers or emails. 1 indicates the highest priority phone number, 2 indicates the second priority, etc . The preferred has a rank of 1. Additional emails have a null rank.

Patient (R4).telecom.system | code | | | 1..1 | The type of telecom. Potential values are: email phone fax url pager sms other

Patient (R4).telecom.use | code | | | 0..1 | If the telecom entry is a phone number, possible values are: home mobile work temp old Use is not returned for emails.

Patient (R4).telecom.value | string | | | 1..1 | Value of the telecom method. Can be an email address or phone number.

Sample request

```
GET
    https://hostname/instance/api/FHIR/R4/Patient?family=fhir&given=freddy&birthdate=1991-07-
    16&identifier=EXTERNAL|Z8446
```

Sample response


```
{
  "resourceType": "Bundle",
  "type": "searchset",
  "total": 1,
  "link": [
    {
      "relation": "self",
      "url":
    "https://hostname/instance/api/FHIR/R4/Patient?family=fhir&given=freddy&birthdate=1991-07-
    16&identifier=EXTERNAL|Z8446"
    }
  ],
  "entry": [
    {
      "link": [
        {
          "relation": "self",
          "url": "https://hostname/instance/api/FHIR/R4/Patient/eP-BmFG0190obAH1wt4wjUw3"
        }
      ],
      "fullUrl": "https://hostname/instance/api/FHIR/R4/Patient/eP-BmFG0190obAH1wt4wjUw3",
      "resource": {
        "resourceType": "Patient",
        "id": "eP-BmFG0190obAH1wt4wjUw3",
        "extension": [
          {
            "valueCodeableConcept": {
              "coding": [
                {
                  "system": "urn:oid:1.2.840.114350.1.13.1545.1.7.10.698084.130.657370.74",
                  "code": "female",
```

```
        "display": "female"
      }
    ]
  },
  "url": "http://open.epic.com/FHIR/StructureDefinition/extension/legal-sex"
},
{
  "valueCodeableConcept": {
    "coding": [
      {
        "system": "http://hl7.org/fhir/gender-identity",
        "code": "female",
        "display": "female"
      }
    ]
  },
  "url": "http://hl7.org/fhir/StructureDefinition/patient-genderIdentity"
},
{
  "valueCodeableConcept": {
    "coding": [
      {
        "system": "urn:oid:1.2.840.114350.1.13.1545.1.7.10.698084.130.657370.74",
        "code": "female",
        "display": "female"
      }
    ]
  },
  "url": "http://open.epic.com/FHIR/StructureDefinition/extension/sex-for-clinical-use"
},
{
  "extension": [
    {
      "valueCoding": {
        "system": "urn:oid:2.16.840.1.113883.6.238",
        "code": "1002-5",
        "display": "American Indian or Alaska Native"
      },
      "url": "ombCategory"
    },
    {
      "valueString": "American Indian or Alaska Native",
      "url": "text"
    }
  ],
  "url": "http://hl7.org/fhir/us/core/StructureDefinition/us-core-race"
},
{
  "extension": [
    {
      "valueString": "Unknown",
      "url": "text"
    }
  ],
  "url": "http://hl7.org/fhir/us/core/StructureDefinition/us-core-ethnicity"
},
{
  "valueCode": "248152002",
  "url": "http://hl7.org/fhir/us/core/StructureDefinition/us-core-sex"
},
{
  "valueCodeableConcept": {
    "coding": [
      {
        "system": "urn:oid:2.16.840.1.113883.6.96",
        "code": "446141000124107",
        "display": "Identifies as female gender (finding)"
      }
    ],
    "text": "Identifies as female gender (finding)"
  },
  "url": "http://hl7.org/fhir/us/core/StructureDefinition/us-core-genderIdentity"
},
{
  "extension": [
    {
      "valueCodeableConcept": {
        "coding": [
          {
            "system": "http://terminology.hl7.org/CodeSystem/v3-TribalEntityUS",
            "code": "101"
          }
        ]
      },
      "url": "tribalAffiliation"
    }
  ],
  "url": "http://hl7.org/fhir/us/core/StructureDefinition/us-core-tribal-affiliation"
},
```

```
    {
      "valueCodeableConcept": {
        "coding": [
          {
            "system": "http://loinc.org",
            "code": "LA29519-8",
            "display": "she/her/her/hers/herself"
          }
        ]
      },
      "url": "http://open.epic.com/FHIR/StructureDefinition/extension/calculated-pronouns-to-use-for-text"
    }
  ],
  "identifier": [
    {
      "use": "usual",
      "type": {
        "text": "CEID"
      },
      "system": "urn:oid:1.2.840.114350.1.13.1545.1.7.3.688884.100",
      "value": "CADGPNJ6SD3B5TN"
    },
    {
      "use": "usual",
      "type": {
        "text": "EPIC"
      },
      "system": "urn:oid:1.2.840.114350.1.13.1545.1.7.5.737384.0",
      "value": "E6393"
    },
    {
      "use": "usual",
      "type": {
        "text": "EXTERNAL"
      },
      "system": "urn:oid:1.2.840.114350.1.13.1545.1.7.2.698084",
      "value": "Z8446"
    },
    {
      "use": "usual",
      "type": {
        "text": "FHIR"
      },
      "system": "http://open.epic.com/FHIR/StructureDefinition/patient-dstu2-fhir-id",
      "value": "TzIrWN90OE2ddVDqpQe7al9trRYDL0ZwPw7-jQHypmZoB"
    },
    {
      "use": "usual",
      "type": {
        "text": "FHIR STU3"
      },
      "system": "http://open.epic.com/FHIR/StructureDefinition/patient-fhir-id",
      "value": "eP-BmFG0190obAH1wt4wjUw3"
    },
    {
      "use": "usual",
      "type": {
        "text": "INTERNAL"
      },
      "system": "urn:oid:1.2.840.114350.1.13.1545.1.7.2.698084",
      "value": "     Z8446"
    },
    {
      "use": "usual",
      "type": {
        "text": "WPRINTERNAL"
      },
      "system": "urn:oid:1.2.840.114350.1.13.1545.1.7.2.878082",
      "value": "1368"
    },
    {
      "use": "usual",
      "system": "https://open.epic.com/FHIR/StructureDefinition/PayerMemberId",
      "value": "E639301"
    },
    {
      "use": "usual",
      "system": "urn:oid:2.16.840.1.113883.4.1",
      "_value": {
        "extension": [
          {
            "valueString": "xxx-xx-5813",
            "url": "http://hl7.org/fhir/StructureDefinition/rendered-value"
          }
        ]
      }
    }
  ],
  "active": true,
```

```
"name": [
  {
    "use": "official",
    "text": "Frederick Fhir",
    "family": "Fhir",
    "given": [
      "Frederick"
    ]
  },
  {
    "use": "usual",
    "text": "Freddy Fhir",
    "family": "Tests",
    "given": [
      "Freddy"
    ],
    "_given": [
      {
        "extension": [
          {
            "valueCode": "CL",
            "url": "http://hl7.org/fhir/StructureDefinition/iso21090-EN-qualifier"
          }
        ]
      }
    ]
  },
  {
    "use": "old",
    "text": "FHIR,FRANCIS",
    "family": "Fhir",
    "given": [
      "Francis"
    ]
  }
],
"telecom": [
  {
    "system": "phone",
    "value": "000-123-4567",
    "use": "home",
    "rank": 2
  },
  {
    "system": "phone",
    "value": "000-555-5555",
    "use": "mobile",
    "rank": 1
  },
  {
    "system": "email",
    "value": "freddy_fhir@email.com",
    "rank": 1
  }
],
"gender": "female",
"birthDate": "1991-07-16",
"deceasedBoolean": false,
"address": [
  {
    "use": "home",
    "line": [
      "1979 Milky Way",
      "Apt 123"
    ],
    "city": "VERONA",
    "district": "DANE",
    "state": "WI",
    "postalCode": "53593",
    "country": "US"
  },
  {
    "use": "old",
    "line": [
      "1979 Milky Way",
      "Apt 123"
    ],
    "city": "VERONA",
    "district": "DANE",
    "state": "WI",
    "postalCode": "53593",
    "country": "US"
  }
],
"maritalStatus": {
  "text": "Married"
},
"contact": [
  {
```

```
    "name": {
      "use": "usual",
      "text": "Contact,Sample"
    },
    "telecom": [
      {
        "system": "phone",
        "value": "123-456-7890",
        "use": "home"
      }
    ]
  },
  {
    "relationship": [
      {
        "coding": [
          {
            "system": "http://terminology.hl7.org/CodeSystem/v3-RoleCode",
            "code": "MTH"
          },
          {
            "system": "urn:oid:1.2.840.114350.1.13.1545.1.7.4.827665.1000",
            "code": "8",
            "display": "Mother"
          }
        ],
        "text": "Mother"
      }
    ],
    "name": {
      "use": "usual",
      "text": "Related,Person"
    },
    "telecom": [
      {
        "system": "phone",
        "value": "614-222-9999",
        "use": "home"
      },
      {
        "system": "phone",
        "value": "614-999-2222",
        "use": "mobile"
      },
      {
        "system": "email",
        "value": "relatedperson@email.com"
      }
    ],
    "address": {
      "use": "home",
      "line": [
        "123 Main St"
      ],
      "city": "MADISON",
      "district": "DANE",
      "state": "WI",
      "postalCode": "53719",
      "country": "US"
    }
  }
],
"communication": [
  {
    "language": {
      "coding": [
        {
          "system": "urn:ietf:bcp:47",
          "code": "es",
          "display": "Spanish"
        }
      ],
      "text": "Spanish"
    },
    "preferred": true
  }
],
"generalPractitioner": [
  {
    "reference": "Practitioner/eCuj-8RSML9azgNbvriN9zQ3",
    "type": "Practitioner",
    "display": "Cardiologist Cupid, MD"
  },
  {
    "reference": "Practitioner/eStpl8RIDCXUeqWgdoSou8A3",
    "type": "Practitioner",
    "display": "Administrator Homehealth"
  }
],
```

```
        "managingOrganization": {
          "reference": "Organization/ew-tiMJ-I2HvVOV1E0GKCoQ3",
          "display": "Epic Service Area"
        }
      },
      "search": {
        "mode": "match"
      }
    }
  ]
}
```

Change log

Epic Version | Description | Type
August 2024 and May 2024 with SU | Patient.Read requests now return temporary addresses for organizations in Norway. Previously, temporary addresses were returned only for organizations in Singapore.
November 2023 | The patient-birthTime extension now appears as a child extension on the birthDate element when present, to conform with the FHIR specification. Previously, patient-birthTime was returned as a root-level extension on the Patient resource. | Breaking Change
November 2022 | Patient.contact.relationship previously only returned "C" for emergency contact or "E" for employer. When this element is "C" for emergency contact, additional elements about that contact's relationship to the patient are returned. | Non-substantive change

22.1.5 Practitioner.Read (Organizational Directory) (R4)

File: site/apis/22-Identification-Individuals/1-R4/935-Practitioner-Read-Organizational-Directory-R4.html
Epic API ID | 935
FHIR version | R4
Categories | Identification Individuals
API type | USCDI
A la carte | Industry-Standard Level 1 API
USCDI | Yes
Available in inpatient and other contexts | Yes
ONC certification products | EpicCare Ambulatory Base, EpicCare Inpatient Base
ONC certification versions | August 2019
HTTP method | GET
URL template | api/FHIR/R4/Practitioner/{ID}
Supports OAuth 2.0 | True
Supported user types | Backend Systems and Non-OAuth 2.0, Clinicians or Administrative Users, Patients
Performs scope validation | False
Source | https://fhir.epic.com/Specifications?api=935

Description

The FHIR Practitioner resource defines a person who is directly or indirectly involved in the provisioning of healthcare. The Practitioner resource can provide information about a healthcare provider, such as activities, responsibilities, demographics, and other administrative information.

Remarks

This Practitioner API can return basic provider details, but does not include the provider's location and contact details. If your application needs to access location and contact details for this provider, you can make a subsequent request to the PractitionerRole.Search API. In that request, set the practitioner search parameter equal to the Practitioner FHIR ID and use _include to include the related Location reference. For example:

https://hostname/instance/api/FHIR/R4/PractitionerRole?practitioner={Practitioner_FHIR_ID}&_include=PractitionerRole:location

Request parameters

Name | Type | Optional | Array | Cardinality | Description
ID | token | Required | | 1..1 | The Practitioner FHIR ID. Must be a user, an internal provider of type person, or an external provider.

Response elements

Name | Type | Optional | Array | Cardinality | Description
Practitioner (R4) | Resource
Practitioner (R4).active | boolean | | | 0..1 | Whether the practitioner's record is active. This element isn't supported for external providers.
Practitioner (R4).birthDate | date | | | 0..1 | The Practitioner's date of birth in the format: YYYY-MM-DD. Not supported in patient context.
Practitioner (R4).communication | CodeableConcept | | Yes | 0..* | A language which may be used to communicate with the Practitioner.
Practitioner (R4).gender | code | | | 0..1 | The Practitioner's gender.
Practitioner (R4).identifier | Identifier | | Yes | 0..* | The provider or user identifiers defined in the system. The Epic provider ID is returned with identifier system urn:oid:1.2.840.114350.1.13.xxx.y.7.2.836982. The Epic user ID is returned with the identifier system of urn:oid:1.2.840.114350.1.13.xxx.y.7.2.697780. The xxx value is replaced with an organization-specific sub-identifier and the y value changes depending on whether the environment is Epic-owned, a non-production environment, or a production environment. For Epic provider-based or user-based Practitioners, this service returns both the Epic provider ID and the Epic user ID associated with the Practitioner when there is a link between the provider and user records. Starting in November 2024, for Practitioners with a Tax Identification Number (TIN), this service returns an identifier type of TIN and the ID of the TIN. For provider-based Practitioners with a National Provider Identifier (NPI), this service returns an identifier

type of NPI and the ID of the NPI. Starting in the November 2026 version of Epic, for organizations using EPS in the United Kingdom, identifiers are loaded from the Epic user record linked to the Epic provider record. If the identifier is set to one of the following ID types and system OIDs, the corresponding system URL is returned in Identifier.system: ID Type System OID System URL returned in Identifier.system UZI 2.16.528.1.1007.3.1 http://fhir.nl/fhir/NamingSystem/uzi-nr-pers AGB 2.16.840.1.113883.2.4.6.1 http://fhir.nl/fhir/NamingSystem/agb-z BIG 2.16.528.1.1007.5.1 http://fhir.nl/fhir/NamingSystem/big NPI 1.2.840.114350.1.13.xxx.y.7.5.737384 http://hl7.org/fhir/sid/us-npi Tax ID Number 2.16.840.1.113883.4.4
ID Type | System OID | System URL returned in Identifier.system
UZI | 2.16.528.1.1007.3.1 | http://fhir.nl/fhir/NamingSystem/uzi-nr-pers
AGB | 2.16.840.1.113883.2.4.6.1 | http://fhir.nl/fhir/NamingSystem/agb-z
BIG | 2.16.528.1.1007.5.1 | http://fhir.nl/fhir/NamingSystem/big
NPI | 1.2.840.114350.1.13.xxx.y.7.5.737384 | http://hl7.org/fhir/sid/us-npi
Tax ID Number | 2.16.840.1.113883.4.4
Practitioner (R4).identifier.type | CodeableConcept | | | 1..1 | The identifier type.
Practitioner (R4).identifier.type.coding | Coding | | Yes | 0..* | The identifier type coding. A type coding is only included for Tax ID identifiers.
Practitioner (R4).identifier.type.coding.code | String | | | 1..1 | The identifier type code. ID Type Code Tax ID Number TAX
ID Type | Code
Tax ID Number | TAX
Practitioner (R4).identifier.type.coding.system | String | | | 1..1 | The defining code system for the corresponding code. ID Type System URL Tax ID Number http://terminology.hl7.org/CodeSystem/v2-0203
ID Type | System URL
Tax ID Number | http://terminology.hl7.org/CodeSystem/v2-0203
Practitioner (R4).name | HumanName | | Yes | 0..* | The name associated with the Practitioner.
Practitioner (R4).name.family | string | | | 1..1 | The Practitioner's last name.
Practitioner (R4).name.given | string | | Yes | 1..1 | The Practitioner's first and middle name. If more than one given name is present, each name is returned in a separate line.
Practitioner (R4).name.prefix | string | | Yes | 0..1 | The Practitioner's prefix.
Practitioner (R4).name.suffix | string | | Yes | 0..1 | The Practitioner's suffix. This can include academic titles.
Practitioner (R4).name.text | string | | | 1..1 | The Practitioner's full concatenated name.
Practitioner (R4).photo | Attachment | | Yes | 0..* | A link or reference to the provider's photo.
Practitioner (R4).photo.url | String | | | 1..1 | The URI or URL where the photo can be found. If the photo is stored on the BLOB server, a URL to a Binary (Provider Photo) resource is returned.
Practitioner (R4).qualification | BackboneElement | | Yes | 0..* | The Practitioner's qualifications, including their current license and board certifications. Not supported in patient-facing context or if the Practitioner does not have a user record in Epic.
Practitioner (R4).qualification.issuer | Reference | | | 0..1 | The medical board that issued the board certification.
Practitioner (R4).qualification.period | Period | | | 0..1 | The period through which the qualification is effective.
Practitioner (R4).telecom | ContactPoint | | Yes | 0..* | Email address of the Practitioner. Not supported in patient-facing context or if the Practitioner does not have a user record in Epic.
Practitioner (R4).telecom.system | code | | | 1..1 | Always set to "email".
Practitioner (R4).telecom.value | string | | | 1..1 | Email address of the Practitioner.

Sample request

```
GET https://hostname/instance/api/FHIR/R4/Practitioner/eXzZgWndjVuKaore80K8bLA3
```

Sample response


```
{
  "resourceType": "Practitioner",
  "id": "eXzZgWndjVuKaore80K8bLA3",
  "identifier": [
    {
      "use": "usual",
      "type": {
        "text": "INTERNAL"
      },
      "system": "urn:oid:1.2.840.114350.1.13.861.1.7.2.836982",
      "value": "  841860"
    },
    {
      "use": "usual",
      "type": {
        "text": "EXTERNAL"
      },
      "system": "urn:oid:1.2.840.114350.1.13.861.1.7.2.836982",
      "value": "841860"
    }
  ],
  "active": true,
  "name": [
    {
      "use": "usual",
      "text": "Practitioner Fhir, MD",
      "family": "Fhir",
      "given": [
        "Practitioner"
      ]
    }
  ],
  "telecom": [
    {
      "system": "email",
      "value": "provider@fhir.com"
```

```
    }
  ],
  "gender": "male",
  "birthDate": "2000-04-01",
  "photo": [
    {
      "url": "Binary/ep5jITTLopSbAiPb27Q3gEw3"
    }
  ],
  "qualification": [
    {
      "code": {
        "coding": [
          {
            "system": "urn:oid:1.2.840.114350.1.13.861.1.7.4.836982.6000",
            "code": "1",
            "display": "MD"
          }
        ],
        "text": "MD"
      }
    }
  ],
  "communication": [
    {
      "coding": [
        {
          "system": "urn:oid:2.16.840.1.113883.6.99",
          "code": "en",
          "display": "English"
        },
        {
          "system": "urn:ietf:bcp:47",
          "code": "en",
          "display": "English"
        }
      ],
      "text": "English"
    },
    {
      "coding": [
        {
          "system": "urn:oid:2.16.840.1.113883.6.99",
          "code": "es",
          "display": "Spanish"
        },
        {
          "system": "urn:ietf:bcp:47",
          "code": "es",
          "display": "Spanish"
        }
      ],
      "text": "Spanish"
    }
  ]
}
```


22.1.6 Practitioner.Search (Organizational Directory) (R4)

File: site/apis/22-Identification-Individuals/1-R4/936-Practitioner-Search-Organizational-Directory-R4.html
Epic API ID | 936
FHIR version | R4
Categories | Identification Individuals
API type | USCDI
A la carte | Industry-Standard Level 1 API
USCDI | Yes
Available in inpatient and other contexts | Yes
ONC certification products | EpicCare Ambulatory Base, EpicCare Inpatient Base
ONC certification versions | August 2019
HTTP method | GET
URL template | api/FHIR/R4/Practitioner?address={address}&address-city={address-city}&address-postalcode={address-postalcode}&address-state={address-state}&family={family}&given={given}&identifier={identifier}&name={name}
Supports OAuth 2.0 | True
Supported user types | Backend Systems and Non-OAuth 2.0, Clinicians or Administrative Users, Patients
Performs scope validation | False
Source | https://fhir.epic.com/Specifications?api=936

Description

The FHIR Practitioner resource defines a person who is directly or indirectly involved in the provisioning of healthcare. This web service allows searching for practitioners and retrieves information about a practitioner, such as activities, responsibilities, demographics, and other administrative information.

One of the following minimum data sets is required for a practitioner to be returned:

* Identifier such as FHIR ID, or Identity ID (such as NPI)

* Family Name + Given Name

* Family Name

* Name

This web service only returns practitioners in the system who represent a healthcare provider and are active.

Remarks

This Practitioner API can return basic provider details, but does not include the provider's location and contact details. If your application needs to access location and contact details for this provider, you can make a subsequent request to the PractitionerRole.Search API. In that request, set the practitioner search parameter equal to the Practitioner FHIR ID and use _include to include the related Location reference. For example:

https://hostname/instance/api/FHIR/R4/PractitionerRole?practitioner={Practitioner_FHIR_ID}&_include=PractitionerRole:location

Request parameters

Name | Type | Optional | Array | Cardinality | Description
_count | number | Optional | Yes | | Number of results per page.
_id | token | Optional | Yes | | FHIR resource IDs for the desired resources. Can be used in combination with _count, _include, and _revInclude. All others are ignored.
_include | string | Optional | Yes | | Used to indicate which referenced resources to include in the search bundle.
_revinclude | string | Optional | Yes | | Used to include Provenance or AuditEvent resources that refer to search results, when available.
address | string | Optional | Yes | | The free-text address. This parameter is ignored if the identifier parameter is provided.
address-city | string | Optional | Yes | | The city specified in the Practitioner's address. City cannot be specified without state. This parameter is ignored if the identifier parameter is provided.
address-postalcode | string | Optional | Yes | | A ZIP code specified in the Practitioner's address. Should be a valid zip code for the country. This parameter is ignored if the identifier parameter is provided.
address-state | string | Optional | Yes | | A state specified in the Practitioner's address. This parameter is ignored if the identifier parameter is provided.
family | string | Conditional | Yes | | A portion of the Practitioner's family name. This parameter is ignored if the identifier parameter is provided.
given | string | Conditional | Yes | | A portion of the Practitioner's given name. Family name is also required if this parameter is specified. This parameter is ignored if the identifier parameter is provided.
identifier | token | Conditional | Yes | | A Practitioner's identifier, such as NPI. This web service supports using ID and ID type combinations, such as identifier=External|608999 or identifier=http://hl7.org/fhir/sid/us-npi|608999. If this parameter is provided, all other parameters are ignored.
name | string | Conditional | Yes | | Free text that can match a portion of Practitioner's family name, given name, or both. This parameter is ignored if the identifier parameter is provided. If this parameter is provided, family and given are ignored.

Request parameters (post-filtered search parameters)

Name | Type | Optional | Array | Cardinality | Description
active | token | Optional | Yes | | Whether the Practitioner's record is active.
communication | token | Optional | Yes | | A language which may be used to communicate with the Practitioner.
email | token | Optional | Yes | | The Practitioner's email.
gender | token | Optional | Yes | | The Practitioner's gender.
telecom | token | Optional | Yes | | The Practitioner's email. Should be in [system]|[value] format. System should be email and the value should be a valid email address.

Response elements

Name | Type | Optional | Array | Cardinality | Description
Practitioner (R4) | Resource
Practitioner (R4).active | boolean | | | 0..1 | Whether the practitioner's record is active. This element isn't supported for external providers.
Practitioner (R4).birthDate | date | | | 0..1 | The Practitioner's date of birth in the format: YYYY-MM-DD. Not supported in patient context.
Practitioner (R4).communication | CodeableConcept | | Yes | 0..* | A language which may be used to communicate with the Practitioner.
Practitioner (R4).gender | code | | | 0..1 | The Practitioner's gender.
Practitioner (R4).identifier | Identifier | | Yes | 0..* | The provider or user identifiers defined in the system. The Epic provider ID is returned with identifier system urn:oid:1.2.840.114350.1.13.xxx.y.7.2.836982. The Epic user ID is returned with the identifier system of urn:oid:1.2.840.114350.1.13.xxx.y.7.2.697780. The xxx value is replaced with an organization-specific sub-identifier and the y value changes depending on whether the environment is Epic-owned, a non-production environment, or a production environment. For Epic provider-based or user-based Practitioners, this service returns both the Epic provider ID and the Epic user ID associated with the Practitioner when there is a link between the provider and user records. Starting in November 2024, for Practitioners with a Tax Identification Number (TIN), this service returns an identifier type of TIN and the ID of the TIN. For provider-based Practitioners with a National Provider Identifier (NPI), this service returns an identifier type of NPI and the ID of the NPI. Starting in the November 2026 version of Epic, for organizations using EPS in the United Kingdom, identifiers are loaded from the Epic user record linked to the Epic provider record. If the identifier is set to one of the following ID types and system OIDs, the corresponding system URL is returned in Identifier.system: ID Type System OID System URL returned in Identifier.system UZI 2.16.528.1.1007.3.1 http://fhir.nl/fhir/NamingSystem/uzi-nr-pers AGB 2.16.840.1.113883.2.4.6.1 http://fhir.nl/fhir/NamingSystem/agb-z BIG 2.16.528.1.1007.5.1 http://fhir.nl/fhir/NamingSystem/big NPI 1.2.840.114350.1.13.xxx.y.7.5.737384 http://hl7.org/fhir/sid/us-npi Tax ID Number 2.16.840.1.113883.4.4
ID Type | System OID | System URL returned in Identifier.system
UZI | 2.16.528.1.1007.3.1 | http://fhir.nl/fhir/NamingSystem/uzi-nr-pers
AGB | 2.16.840.1.113883.2.4.6.1 | http://fhir.nl/fhir/NamingSystem/agb-z
BIG | 2.16.528.1.1007.5.1 | http://fhir.nl/fhir/NamingSystem/big

NPI | 1.2.840.114350.1.13.xxx.y.7.5.737384 | http://hl7.org/fhir/sid/us-npi
Tax ID Number | 2.16.840.1.113883.4.4
Practitioner (R4).name | HumanName | | Yes | 0..* | The name associated with the Practitioner.
Practitioner (R4).name.family | string | | | 1..1 | The Practitioner's last name.
Practitioner (R4).name.given | string | | Yes | 1..1 | The Practitioner's first and middle name. If more than one given name is present, each name is returned in a separate line.
Practitioner (R4).name.prefix | string | | Yes | 0..1 | The Practitioner's prefix.
Practitioner (R4).name.suffix | string | | Yes | 0..1 | The Practitioner's suffix. This can include academic titles.
Practitioner (R4).name.text | string | | | 1..1 | The Practitioner's full concatenated name.
Practitioner (R4).photo | Attachment | | Yes | 0..* | A link or reference to the provider's photo.
Practitioner (R4).photo.url | String | | | 1..1 | The URI or URL where the photo can be found. If the photo is stored on the BLOB server, a URL to a Binary (Provider Photo) resource is returned.
Practitioner (R4).qualification | BackboneElement | | Yes | 0..* | The Practitioner's qualifications, including their current license and board certifications. Not supported in patient-facing context or if the Practitioner does not have a user record in Epic.
Practitioner (R4).qualification.issuer | Reference | | | 0..1 | The medical board that issued the board certification.
Practitioner (R4).qualification.period | Period | | | 0..1 | The period through which the qualification is effective.
Practitioner (R4).telecom | ContactPoint | | Yes | 0..* | Email address of the Practitioner. Not supported in patient-facing context or if the Practitioner does not have a user record in Epic.
Practitioner (R4).telecom.system | code | | | 1..1 | Always set to "email".
Practitioner (R4).telecom.value | string | | | 1..1 | Email address of the Practitioner.

Sample request

```
GET https://hostname/instance/api/FHIR/R4/Practitioner?family=Fhir&given=practitioner
```

Sample response


```
{
  "resourceType": "Bundle",
  "type": "searchset",
  "total": 1,
  "link": [
    {
      "relation": "self",
      "url": "https://hostname/instance/api/FHIR/R4/Practitioner?family=Fhir&given=practitioner"
    }
  ],
  "entry": [
    {
      "link": [
        {
          "relation": "self",
          "url": "https://hostname/instance/api/FHIR/R4/Practitioner/eXzZgWndjVuKaore80K8bLA3"
        }
      ],
      "fullUrl": "https://hostname/instance/api/FHIR/R4/Practitioner/eXzZgWndjVuKaore80K8bLA3",
      "resource": {
        "resourceType": "Practitioner",
        "id": "eXzZgWndjVuKaore80K8bLA3",
        "identifier": [
          {
            "use": "usual",
            "type": {
              "text": "INTERNAL"
            },
            "system": "urn:oid:1.2.840.114350.1.13.861.1.7.2.836982",
            "value": "  841860"
          },
          {
            "use": "usual",
            "type": {
              "text": "EXTERNAL"
            },
            "system": "urn:oid:1.2.840.114350.1.13.861.1.7.2.836982",
            "value": "841860"
          }
        ],
        "active": true,
        "name": [
          {
            "use": "usual",
            "text": "Practitioner Fhir, MD",
            "family": "Fhir",
            "given": [
              "Practitioner"
            ]
          }
        ],
        "telecom": [
          {
            "system": "email",
            "value": "provider@fhir.com"
          }
        ],
```

```
        "gender": "male",
        "birthDate": "2000-04-01",
        "photo": [
          {
            "url": "Binary/ep5jITTLopSbAiPb27Q3gEw3"
          }
        ],
        "qualification": [
          {
            "code": {
              "coding": [
                {
                  "system": "urn:oid:1.2.840.114350.1.13.861.1.7.4.836982.6000",
                  "code": "1",
                  "display": "MD"
                }
              ],
              "text": "MD"
            }
          }
        ],
        "communication": [
          {
            "coding": [
              {
                "system": "urn:oid:2.16.840.1.113883.6.99",
                "code": "en",
                "display": "English"
              },
              {
                "system": "urn:ietf:bcp:47",
                "code": "en",
                "display": "English"
              }
            ],
            "text": "English"
          },
          {
            "coding": [
              {
                "system": "urn:oid:2.16.840.1.113883.6.99",
                "code": "es",
                "display": "Spanish"
              },
              {
                "system": "urn:ietf:bcp:47",
                "code": "es",
                "display": "Spanish"
              }
            ],
            "text": "Spanish"
          }
        ]
      },
      "search": {
        "mode": "match"
      }
    }
  ]
}
```


Change log

Version	Description	Type
May 2022	Hidden or soft-deleted records are no longer returned in Search results	Breaking change

22.1.7 PractitionerRole.Read (Organizational Directory) (R4)

File: site/apis/22-Identification-Individuals/1-R4/937-PractitionerRole-Read-Organizational-Directory-R4.html

Epic API ID	937
FHIR version	R4
Categories	Identification Individuals
API type	USCDI
A la carte	Industry-Standard Level 1 API
USCDI	Yes
Available in inpatient and other contexts	Yes
ONC certification products	EpicCare Ambulatory Base, EpicCare Inpatient Base
ONC certification versions	August 2019
HTTP method	GET
URL template	api/FHIR/R4/PractitionerRole/{ID}
Supports OAuth 2.0	True
Supported user types	Backend Systems and Non-OAuth 2.0, Clinicians or Administrative Users, Patients
Performs scope validation	False
Source	https://fhir.epic.com/Specifications?api=937

Description

The PractitionerRole resource defines location and types of services (roles) that a practitioner provides for an organization. It references the Practitioner resource, and there can be multiple PractitionerRoles per practitioner.

Request parameters

Name | Type | Optional | Array | Cardinality | Description
ID | token | Required | | 1..1 | The PractitionerRole FHIR ID. Must be a provider (SER) record of type 'Person' with valid address in Epic.

Response elements

Name | Type | Optional | Array | Cardinality | Description
PractitionerRole (R4) | Resource
PractitionerRole (R4).active | Boolean | | | 0..1 | Whether the PractitionerRole is active.
PractitionerRole (R4).code | CodeableConcept | | Yes | 0..* | Roles which the practitioner may perform. Starting in the May 2024 version of Epic, this also includes the SNOMED practitioner code.
PractitionerRole (R4).endpoint | Reference | | Yes | 0..1 | Reference to the Endpoint for the PractitionerRole. This element is not returned in a patient-facing context or if the corresponding practitioner is inactive.
PractitionerRole (R4).location | Reference | | Yes | 0..* | Reference to a Location containing information about the unique address of the practitioner. In the August 2025 version of Epic and earlier, this element is not returned in a patient-facing context. Starting in the November 2025 version of Epic (August 2025, May 2025, February 2025, and November 2024 with special updates), this element is conditionally returned in a patient-facing context, depending on system configuration.
PractitionerRole (R4).organization | Reference | | | 0..1 | Reference to the practitioner's place of service. This element is only supported for organizations in the Netherlands.
PractitionerRole (R4).practitioner | Reference | | | 0..1 | Reference to the Practitioner resource.
PractitionerRole (R4).specialty | CodeableConcept | | Yes | 0..* | The specialties associated with the practitioner.
PractitionerRole (R4).telecom | ContactPoint | | Yes | 0..* | Contact information (phone, fax, email) specific to the unique address. In the August 2025 version of Epic and earlier, this element is not returned in a patient-facing context. Starting in the November 2025 version of Epic (August 2025, May 2025, February 2025, and November 2024 with special updates), this element is conditionally returned in a patient-facing context, depending on system configuration.

Sample request

```
GET https://hostname/instance/api/FHIR/R4/PractitionerRole/fIidEgs9aUIFFBCsj1TnOXmmbOuEnhxY8XHSG-tyNFpo4
```

Sample response


```
{
  "resourceType": "PractitionerRole",
  "id": "fIidEgs9aUIFFBCsj1TnOXmmbOuEnhxY8XHSG-tyNFpo4",
  "active": true,
  "practitioner": {
    "reference": "Practitioner/eXzZgWndjVuKaore80K8bLA3",
    "display": "Practitioner Fhir, MD"
  },
  "code": [
    {
      "coding": [
        {
          "system": "urn:oid:1.2.840.114350.1.13.861.1.7.10.836982.1040",
          "code": "14",
          "display": "Cardiologist"
        },
        {
          "system": "http://snomed.info/sct",
          "code": "106289002",
          "display": "Dentist (occupation)"
        }
      ],
      "text": "Cardiologist"
    }
  ],
  "specialty": [
    {
      "coding": [
        {
          "system": "urn:oid:1.2.840.114350.1.72.1.7.7.10.688867.4160",
          "code": "10",
          "display": "Cardiology"
        }
      ],
      "text": "Cardiology"
    },
    {
      "coding": [
        {
          "system": "urn:oid:1.2.840.114350.1.72.1.7.7.10.688867.4160",
          "code": "11",
          "display": "Cardiac Surgery"
        }
      ],
```

```
      "text": "Cardiac Surgery"
    }
  ],
  "location": [
    {
      "reference": "Location/fN5r5RGGtyvRDgqZZ7ITj37N9MHsZtZrT.t1rBlZpiyI4"
    }
  ],
  "telecom": [
    {
      "system": "phone",
      "value": "+91 8974 512365",
      "use": "work"
    },
    {
      "system": "fax",
      "value": "+91 9394 939494",
      "use": "work"
    },
    {
      "system": "email",
      "value": "fhir.practitioner@fhir.com",
      "use": "work"
    }
  ],
  "endpoint": [
    {
      "reference": "Endpoint/fkOK1jRjSpaKYqwl4ayJZPu6TEOgqFzahaUECIsZbyVA4",
      "display": "Practitioner Fhir, MD"
    }
  ]
}
```


22.1.8 PractitionerRole.Search (Organizational Directory) (R4)

File: site/apis/22-Identification-Individuals/1-R4/938-PractitionerRole-Search-Organizational-Directory-R4.html
Epic API ID | 938
FHIR version | R4
Categories | Identification Individuals
API type | USCDI
A la carte | Industry-Standard Level 1 API
USCDI | Yes
Available in inpatient and other contexts | Yes
ONC certification products | EpicCare Ambulatory Base, EpicCare Inpatient Base
ONC certification versions | August 2019
HTTP method | GET
URL template | api/FHIR/R4/PractitionerRole?email={email}&identifier={identifier}&location={location}&phone={phone}&practitioner={practitioner}&specialty={specialty}&organization={organization}&role={role}&telecom={telecom}
Supports OAuth 2.0 | True
Supported user types | Backend Systems and Non-OAuth 2.0, Clinicians or Administrative Users, Patients
Performs scope validation | False
Source | https://fhir.epic.com/Specifications?api=938

Description

The PractitionerRole resource defines location and types of services (roles) that a practitioner provides for an organization. It references the Practitioner resource, and there can be multiple PractitionerRoles per practitioner.

Request parameters

Name | Type | Optional | Array | Cardinality | Description
_count | number | Optional | Yes | | Number of results per page.
_id | token | Optional | Yes | | FHIR resource IDs for the desired resources. Can be used in combination with _count, _include, and _revInclude. All others will be ignored.
_include | string | Optional | Yes | | Used to indicate which referenced resources to include in the search bundle.
_revinclude | string | Optional | Yes | | Used to include Provenance or AuditEvent resources that refer to search results, when available.
email | String | Optional | Yes | | Email on the PractitionerRole. This parameter is not supported in a patient-facing context.
identifier | String | Conditional | Yes | | A practitioner's identifier such as NPI. When this parameter is provided, native parameters other than practitioner, role, phone, and email are ignored. An identifier, practitioner, organization, location, or specialty parameter is required.
location | String | Conditional | Yes | | Reference (FHIR ID) to one of the Locations at which this practitioner provides care. An identifier, practitioner, organization, location, or specialty parameter is required.
organization | String | Conditional | Yes | | Reference (FHIR ID) to the Organization that the practitioner represents or acts on behalf of. Provider-based Organization resources are only supported in the Netherlands. An identifier, practitioner, organization, location, or specialty parameter is required.
phone | String | Optional | Yes | | Phone on the PractitionerRole. This parameter is not supported in a patient-facing context.
practitioner | String | Conditional | Yes | | Reference (FHIR ID) to a Practitioner that can provide the defined services for the organization. When this parameter is provided, native parameters other than identifier, role, phone, and email are ignored. An identifier, practitioner, organization, location, or specialty parameter is required.
role | String | Optional | Yes | | The role a practitioner can perform at an organization.

specialty | String | Conditional | Yes | | The practitioner's specialty at an organization. Must be in the format: <system>|<value> where valid <system> values include: NUCC Coding System: http://nucc.org Provider Taxonomy Codes: http://nucc.org/provider-taxonomy An identifier, practitioner, organization, location, or specialty parameter is required.
telecom | String | Optional | Yes | | The phone or email on the PractitionerRole. This parameter is not supported in the patient-facing context.

Request parameters (post-filtered search parameters)

Name | Type | Optional | Array | Cardinality | Description
active | String | Optional | Yes | | Whether the PractitionerRole is active.
endpoint | String | Optional | Yes | | Reference to the Endpoint for the PractitionerRole.

Response elements

Name | Type | Optional | Array | Cardinality | Description
PractitionerRole (R4) | Resource
PractitionerRole (R4).active | Boolean | | | 0..1 | Whether the PractitionerRole is active.
PractitionerRole (R4).code | CodeableConcept | | Yes | 0..* | Roles which the practitioner may perform. Starting in the May 2024 version of Epic, this also includes the SNOMED practitioner code.
PractitionerRole (R4).endpoint | Reference | | Yes | 0..1 | Reference to the Endpoint for the PractitionerRole. This element is not returned in a patient-facing context or if the corresponding practitioner is inactive.
PractitionerRole (R4).location | Reference | | Yes | 0..* | Reference to a Location containing information about the unique address of the practitioner. In the August 2025 version of Epic and earlier, this element is not returned in a patient-facing context. Starting in the November 2025 version of Epic (August 2025, May 2025, February 2025, and November 2024 with special updates), this element is conditionally returned in a patient-facing context, depending on system configuration.
PractitionerRole (R4).organization | Reference | | | 0..1 | Reference to the practitioner's place of service. This element is only supported for organizations in the Netherlands.
PractitionerRole (R4).practitioner | Reference | | | 0..1 | Reference to the Practitioner resource.
PractitionerRole (R4).specialty | CodeableConcept | | Yes | 0..* | The specialties associated with the practitioner.
PractitionerRole (R4).telecom | ContactPoint | | Yes | 0..* | Contact information (phone, fax, email) specific to the unique address. In the August 2025 version of Epic and earlier, this element is not returned in a patient-facing context. Starting in the November 2025 version of Epic (August 2025, May 2025, February 2025, and November 2024 with special updates), this element is conditionally returned in a patient-facing context, depending on system configuration.

Sample request

```
GET https://hostname/instance/api/FHIR/R4/PractitionerRole?practitioner=eXzZgWndjVuKaore80K8bLA3
```

Sample response


```
{
  "resourceType": "Bundle",
  "type": "searchset",
  "total": 1,
  "link": [
    {
      "relation": "self",
      "url": "https://hostname/instance/api/FHIR/R4/PractitionerRole?practitioner=eXzZgWndjVuKaore80K8bLA3"
    }
  ],
  "entry": [
    {
      "link": [
        {
          "relation": "self",
          "url": "https://hostname/instance/api/FHIR/R4/PractitionerRole/fIidEgs9aUIFFBCsj1TnOXmmbOuEnhxY8XHSG-tyNFpo4"
        }
      ],
      "fullUrl": "https://hostname/instance/api/FHIR/R4/PractitionerRole/fIidEgs9aUIFFBCsj1TnOXmmbOuEnhxY8XHSG-tyNFpo4",
      "resource": {
        "resourceType": "PractitionerRole",
        "id": "fIidEgs9aUIFFBCsj1TnOXmmbOuEnhxY8XHSG-tyNFpo4",
        "active": true,
        "practitioner": {
          "reference": "Practitioner/eXzZgWndjVuKaore80K8bLA3",
          "display": "Practitioner Fhir, MD"
        },
        "code": [
          {
            "coding": [
              {
                "system": "urn:oid:1.2.840.114350.1.13.861.1.7.10.836982.1040",
                "code": "14",
                "display": "Cardiologist"
              },
              {
                "system": "http://snomed.info/sct",
                "code": "106289002",
                "display": "Dentist (occupation)"
              }
            ],
            "text": "Cardiologist"
          }
        ],
```

```
        "specialty": [
          {
            "coding": [
              {
                "system": "urn:oid:1.2.840.114350.1.72.1.7.7.10.688867.4160",
                "code": "10",
                "display": "Cardiology"
              }
            ],
            "text": "Cardiology"
          },
          {
            "coding": [
              {
                "system": "urn:oid:1.2.840.114350.1.72.1.7.7.10.688867.4160",
                "code": "11",
                "display": "Cardiac Surgery"
              }
            ],
            "text": "Cardiac Surgery"
          }
        ],
        "location": [
          {
            "reference": "Location/fN5r5RGGtyvRDgqZZ7ITj37N9MHsZtZrT.t1rBlZpiyI4"
          }
        ],
        "telecom": [
          {
            "system": "phone",
            "value": "+91 8974 512365",
            "use": "work"
          },
          {
            "system": "fax",
            "value": "+91 9394 939494",
            "use": "work"
          },
          {
            "system": "email",
            "value": "fhir.practitioner@fhir.com",
            "use": "work"
          }
        ],
        "endpoint": [
          {
            "reference": "Endpoint/fkOK1jRjSpaKYqwl4ayJZPu6TEOgqFzahaUECIsZbyVA4",
            "display": "Practitioner Fhir, MD"
          }
        ]
      },
      "search": {
        "mode": "match"
      }
    }
  ]
}
```


22.1.9 RelatedPerson.Read (Friends and Family) (R4)

File: site/apis/22-Identification-Individuals/1-R4/11003-RelatedPerson-Read-Friends-and-Family-R4.html
Epic API ID | 11003
FHIR version | R4
Categories | Identification Individuals
API type | USCDI
A la carte | Industry-Standard Level 1 API
USCDI | Yes
Available in inpatient and other contexts | Yes
HTTP method | GET
URL template | /api/FHIR/R4/RelatedPerson/{ID}
Supports OAuth 2.0 | True
Supported user types | Backend Systems and Non-OAuth 2.0, Clinicians or Administrative Users, Patients
Performs scope validation | False
Source | https://fhir.epic.com/Specifications?api=11003

Description

The FHIR RelatedPerson (Friends and Family) resource includes friends or relatives the patient chooses to list on their file. RelatedPersons are often a source of information about the patient. A RelatedPerson can also be a patient's caregiver for a home health or hospice episode. These caregivers provide care during the patient’s home health or hospice episode and are also included in the RelatedPerson.Read (Friends and Family) (R4) API Response.

The read interaction enables the lookup of a RelatedPerson resource by a constant server ID. The read interaction allows clients to store only the server ID, and with a single request, retrieve the most up-to-date information about the resource. Read interactions begin by receiving a RelatedPerson FHIR ID from the CareTeam (R4) resource.

Response elements

Name | Type | Optional | Array | Cardinality | Description
RelatedPerson | RelatedPerson | False
RelatedPerson.active | Boolean | True | | | Whether or not the RelatedPerson record is active.
RelatedPerson.address | Address | False | Yes | | Address of the RelatedPerson.
RelatedPerson.id | id | False | | | FHIR ID
RelatedPerson.relationship | CodeableConcept | False | Yes | | Relationship of the RelatedPerson to patient.
RelatedPerson.telecom | ContactPoint | False | Yes | | Telephone numbers and email addresses for the RelatedPerson, along with their use (home or work for example) and their preferred rank (which to contact first, second, third, and so on).

Sample request

```
https://hostname/instance/api/FHIR/R4/RelatedPerson/e40ZMje.0zWx-ujxfsSunua79c5JesiTb.vP7Wq41U8o3
```

Sample response


```
{
    "resourceType": "RelatedPerson",
    "id": "fQ9M6q7STwTTOGKHJDEhh7A4",
    "active": true,
    "patient": {
        "reference": "Patient/eFUP71YeMGjzx1EDSpkMftA3",
        "display": "Patient,Test"
    },
    "relationship": [
        {
            "coding": [
                {
                    "system": "http://terminology.hl7.org/CodeSystem/v3-RoleCode",
                    "code": "MTH"
                    "display": "mother"
                },
                {
                    "system": "urn:oid:1.2.840.114350.1.13.5325.1.7.4.827665.1000",
                    "code": "8",
                    "display": "Mother"
                }
            ],
            "text": "mother"
        }
    ],
    "name": [
        {
            "use": "usual",
            "text": "Care,Sally"
        }
    ],
    "telecom": [
        {
            "system": "phone",
            "value": "555-555-5555",
            "use": "home",
            "rank": 1
        },
        {
            "system": "phone",
            "value": "555-555-5555",
            "use": "work"
        },
        {
            "system": "phone",
            "value": "555-555-5555",
            "use": "mobile"
        },
        {
            "system": "email",
            "value": "DoNotUse@DoNotUse.DoNotUse"
        }
    ],
    "address": [
        {
            "line": [
                "123 Anywhere St."
            ],
            "city": "VERONA",
            "state": "Wisconsin",
            "postalCode": "53593",
            "country": "United States of America"
        }
    ]
}
```

22.1.10 RelatedPerson.Read (Proxy) (R4)

File: site/apis/22-Identification-Individuals/1-R4/977-RelatedPerson-Read-Proxy-R4.html
Epic API ID | 977
FHIR version | R4
Categories | Identification Individuals
API type | USCDI
A la carte | Industry-Standard Level 1 API
USCDI | Yes
Available in inpatient and other contexts | Yes
ONC certification products | EpicCare Ambulatory Base, EpicCare Inpatient Base
ONC certification versions | November 2019
HTTP method | GET
URL template | api/FHIR/R4/RelatedPerson/{ID}
Supports OAuth 2.0 | True
Supported user types | Backend Systems and Non-OAuth 2.0, Clinicians or Administrative Users, Patients
Performs scope validation | False
Source | https://fhir.epic.com/Specifications?api=977

Description

The FHIR RelatedPerson (Proxy) resource is typically an entity with a personal or professional relationship to the patient. RelatedPersons are often a source of information about the patient. For integrations with Epic, the RelatedPerson is represented by a MyChart account record ID and their link to a Patient record ID. Typically the RelatedPerson represents a MyChart proxy for the patient.

The read interaction enables the lookup of a RelatedPerson resource by a constant server ID. The read interaction allows clients to store only the server ID, and with a single request, retrieve the most up-to-date information about the resource. Read interactions typically begin with a client having previously established a relationship. In this case, clients will get the FHIR ID from an OpenID Connect (OIDC) workflow.

Response elements

Name | Type | Optional | Array | Cardinality | Description
RelatedPerson | RelatedPerson | False
RelatedPerson.address | Address | True | Yes | | Address details for this related person.
RelatedPerson.birthDate | String | True | | | The birth date of this related person.
RelatedPerson.gender | String | True | | | This related person’s legal sex. Possible values are: Male Female Other Unknown
RelatedPerson.extension (also: legal-sex) | Extension | True | Yes | | The related person’s legal sex.
RelatedPerson.name | HumanName | True | Yes | | The name of this related person.
RelatedPerson.patient | Reference | False | | | A Patient FHIR ID, representing the patient whom this related person has MyChart proxy access to.
RelatedPerson.telecom | ContactPoint | True | Yes | | Contact details for this related person. Possible values are: Phone Email If the entry is a phone number, possible values for “use” are: Home Work Mobile

Sample request

```
https://hostname/instance/api/FHIR/R4/RelatedPerson/e40ZMje.0zWx-ujxfsSunua79c5JesiTb.vP7Wq41U8o3
```

Sample response


```
{
  "resourceType": "RelatedPerson",
  "id": "e40ZMje.0zWx-ujxfsSunua79c5JesiTb.vP7Wq41U8o3",
  "extension": [
    {
      "valueCodeableConcept": {
        "coding": [
          {
            "system": "urn:oid:1.2.840.114350.1.13.861.1.7.10.698084.130.657370.2253",
            "code": "male",
            "display": "male"
          }
        ]
      },
      "url": "http://open.epic.com/FHIR/StructureDefinition/extension/legal-sex"
    }
  ],
  "patient": {
    "reference": "Patient/e7XZi7JJ6AZSxlmZBc9-Rdw3",
    "display": "CDS, Fhir Patient"
  },
  "name": [
    {
      "use": "usual",
      "text": "CDS, Fhir Proxy",
      "family": "CDS",
      "given": [
        "Fhir Proxy"
      ]
```

```
    }
  ],
  "telecom": [
    {
      "system": "phone",
      "value": "555-555-5555",
      "use": "home"
    },
    {
      "system": "phone",
      "value": "608-555-5555",
      "use": "mobile"
    },
    {
      "system": "phone",
      "value": "666-555-6666",
      "use": "work"
    }
  ],
  "gender": "male",
  "birthDate": "2000-01-01",
  "address": [
    {
      "line": [
        "1976 Milky Way"
      ],
      "city": "VERONA",
      "state": "WI",
      "postalCode": "53593",
      "country": "USA"
    }
  ]
}
```


22.1.11 RelatedPerson.Search (Friends and Family) (R4)

File: site/apis/22-Identification-Individuals/1-R4/11008-RelatedPerson-Search-Friends-and-Family-R4.html
Epic API ID | 11008
FHIR version | R4
Categories | Identification Individuals
API type | USCDI
A la carte | Industry-Standard Level 1 API
USCDI | Yes
Available in inpatient and other contexts | Yes
HTTP method | GET
URL template | /api/FHIR/R4/RelatedPerson?_id={_id}
Supports OAuth 2.0 | True
Supported user types | Backend Systems and Non-OAuth 2.0, Clinicians or Administrative Users, Patients
Performs scope validation | False
Source | https://fhir.epic.com/Specifications?api=11008

Description

Response elements

Name | Type | Optional | Array | Cardinality | Description
Bundle | Bundle | False | | | Resource bundle. For more information, refer to the FHIR specification.
Bundle.entry | BackboneElement | False | Yes | | An array of entries included in this bundle.
Bundle.entry.resource | ResourceContainer | False | | | A container for a single FHIR resource.
Bundle.entry.resource.RelatedPerson | RelatedPerson | False
Bundle.entry.resource.RelatedPerson.active | Boolean | True | | | Whether or not the RelatedPerson record is active.
Bundle.entry.resource.RelatedPerson.address | Address | False | Yes | | Address of the RelatedPerson.
Bundle.entry.resource.RelatedPerson.id | id | False | | | FHIR ID
Bundle.entry.resource.RelatedPerson.relationship | CodeableConcept | False | Yes | | Relationship of the RelatedPerson to patient.
Bundle.entry.resource.RelatedPerson.telecom | ContactPoint | False | Yes | | Telephone numbers and email addresses for the RelatedPerson, along with their use (home or work for example) and their preferred rank (which to contact first, second, third, and so on).

Sample request

```
https://hostname/instance/api/FHIR/R4/RelatedPerson?_id=e40ZMje.0zWx-ujxfsSunua79c5JesiTb.vP7Wq41U8o3
```

Sample response


```
{
    "resourceType": "RelatedPerson",
    "id": "fQ9M6q7STwTTOGKHJDEhh7A4",
    "active": true,
    "patient": {
        "reference": "Patient/eFUP71YeMGjzx1EDSpkMftA3",
        "display": "Patient,Test"
    },
```

```
    "relationship": [
        {
            "coding": [
                {
                    "system": "http://terminology.hl7.org/CodeSystem/v3-RoleCode",
                    "code": "MTH"
                    "display": "mother"
                },
                {
                    "system": "urn:oid:1.2.840.114350.1.13.5325.1.7.4.827665.1000",
                    "code": "8",
                    "display": "Mother"
                }
            ],
            "text": "mother"
        }
    ],
    "name": [
        {
            "use": "usual",
            "text": "Care,Sally"
        }
    ],
    "telecom": [
        {
            "system": "phone",
            "value": "555-555-5555",
            "use": "home",
            "rank": 1
        },
        {
            "system": "phone",
            "value": "555-555-5555",
            "use": "work"
        },
        {
            "system": "phone",
            "value": "555-555-5555",
            "use": "mobile"
        },
        {
            "system": "email",
            "value": "DoNotUse@DoNotUse.DoNotUse"
        }
    ],
    "address": [
        {
            "line": [
                "123 Anywhere St."
            ],
            "city": "VERONA",
            "state": "Wisconsin",
            "postalCode": "53593",
            "country": "United States of America"
        }
    ]
}
```


22.1.12 RelatedPerson.Search (Proxy) (R4)

File: site/apis/22-Identification-Individuals/1-R4/11007-RelatedPerson-Search-Proxy-R4.html
Epic API ID | 11007
FHIR version | R4
Categories | Identification Individuals
API type | USCDI
A la carte | Industry-Standard Level 1 API
USCDI | Yes
Available in inpatient and other contexts | Yes
HTTP method | GET
URL template | /api/FHIR/R4/RelatedPerson?_id={ID}
Supports OAuth 2.0 | True
Supported user types | Backend Systems and Non-OAuth 2.0, Clinicians or Administrative Users, Patients
Performs scope validation | False
Source | https://fhir.epic.com/Specifications?api=11007

Description

Response elements

Name | Type | Optional | Array | Cardinality | Description
Bundle | Bundle | False | | | Resource bundle. For more information, refer to the FHIR specification.
Bundle.entry | BackboneElement | False | Yes | | An array of entries included in this bundle.
Bundle.entry.resource | ResourceContainer | False | | | A container for a single FHIR resource.

Bundle.entry.resource.RelatedPerson | RelatedPerson | False
Bundle.entry.resource.RelatedPerson.address | Address | True | Yes | | Address details for this related person.
Bundle.entry.resource.RelatedPerson.birthDate | String | True | | | The birth date of this related person.
Bundle.entry.resource.RelatedPerson.gender | String | True | | | This related person's legal sex. Possible values are: Male Female Other Unknown
Bundle.entry.resource.RelatedPerson.extension (also: legal-sex) | Extension | True | Yes | | The related person's legal sex.
Bundle.entry.resource.RelatedPerson.name | HumanName | True | Yes | | The name of this related person.
Bundle.entry.resource.RelatedPerson.patient | Reference | False | | | A Patient FHIR ID, representing the patient whom this related person has MyChart proxy access to.
Bundle.entry.resource.RelatedPerson.telecom | ContactPoint | True | Yes | | Contact details for this related person. Possible values are: Phone Email If the entry is a phone number, possible values for "use" are: Home Work Mobile

Sample request

```
https://hostname/instance/api/FHIR/R4/RelatedPerson?_id=e40ZMje.0zWx-ujxfsSunua79c5JesiTb.vP7Wq41U8o3
```

Sample response


```
{
  "resourceType": "RelatedPerson",
  "id": "e40ZMje.0zWx-ujxfsSunua79c5JesiTb.vP7Wq41U8o3",
  "extension": [
    {
      "valueCodeableConcept": {
        "coding": [
          {
            "system": "urn:oid:1.2.840.114350.1.13.861.1.7.10.698084.130.657370.2253",
            "code": "male",
            "display": "male"
          }
        ]
      },
      "url": "http://open.epic.com/FHIR/StructureDefinition/extension/legal-sex"
    }
  ],
  "patient": {
    "reference": "Patient/e7XZi7JJ6AZSxlmZBc9-Rdw3",
    "display": "CDS, Fhir Patient"
  },
  "name": [
    {
      "use": "usual",
      "text": "CDS, Fhir Proxy",
      "family": "CDS",
      "given": [
        "Fhir Proxy"
      ]
    }
  ],
  "telecom": [
    {
      "system": "phone",
      "value": "555-555-5555",
      "use": "home"
    },
    {
      "system": "phone",
      "value": "608-555-5555",
      "use": "mobile"
    },
    {
      "system": "phone",
      "value": "666-555-6666",
      "use": "work"
    }
  ],
  "gender": "male",
  "birthDate": "2000-01-01",
  "address": [
    {
      "line": [
        "1976 Milky Way"
      ],
      "city": "VERONA",
      "state": "WI",
      "postalCode": "53593",
      "country": "USA"
    }
  ]
}
```


22.2 Identification Individuals: STU3

File: site/apis/22-Identification-Individuals/2-STU3/index.html

* Patient.Create (STU3)

* Patient.Read (STU3)
* Patient.Search (STU3)
* Practitioner.Read (STU3)
* Practitioner.Search (STU3)
* PractitionerRole.Read (STU3)
* PractitionerRole.Search (STU3)

22.2.1 Patient.Create (STU3)

File: site/apis/22-Identification-Individuals/2-STU3/824-Patient-Create-STU3.html
Epic API ID | 824
FHIR version | STU3
Categories | Identification Individuals, Workflow Patient Management
API type | Industry-Standard
USCDI | No
ONC certification products | EpicCare Ambulatory Base, EpicCare Inpatient Base
ONC certification versions | Epic 2018
HTTP method | POST
URL template | api/FHIR/STU3/Patient
Supports OAuth 2.0 | True
Supported user types | Backend Systems and Non-OAuth 2.0, Clinicians or Administrative Users
Performs scope validation | False
Source | https://fhir.epic.com/Specifications?api=824

Description

The FHIR Patient resource defines demographics, care providers, and other administrative information about a person receiving care at a healthcare organization. The Patient.Create web service creates a new patient record or returns an existing one uses the following logic to determine whether a new patient should be created or an existing one should be returned:

* If a patient is found using a provided identifier, and that patient passes demographic validation based on provided demographics, the matching patient is returned.

* If no identifier is provided, and a single high confidence match is found based on provided demographics, the matching patient is returned.

* If the Epic environment uses an external EMPI, and a match is found using an external EMPI query, then a shell patient is created in the environment and returned.

* If no matches are found, a single low-threshold match is found, or multiple high-threshold or low-threshold matches are found, a net new patient is created and returned.

Organizations in the Netherlands:

Patient.Create is not currently supported for organizations in the Netherlands, because Epic doesn't support submitting given name initials in the request body.

The response of a create depends on the Prefer header:

Prefer: return=minimal

returns the full URL to the resource in the Location header.

Prefer: return=representation

returns both the full URL to the resource in the Location header, as well as the full FHIR resource in the response body.

Request parameters

Name | Type | Optional | Array | Cardinality | Description
Patient (STU3) | Resource | | | | A single instance of a Patient FHIR resource.
Patient (STU3).active | boolean | Optional | | 0..1 | Whether the patient record is active. This is always True. Creating inactive patients is not supported.
Patient (STU3).address | Address | Optional | Yes | 0..1 | Addresses for the patient. Only supports filing the home address.
Patient (STU3).address.city | String | Optional | | 0..1 | The city that the patient lives in.
Patient (STU3).address.country | String | Optional | | 0..1 | The country that the patient lives in.
Patient (STU3).address.line | String | Optional | Yes | 1..* | The patient’s street address, in array format.
Patient (STU3).address.period | Period | | | 0..1 | The effective dates for the address.
Patient (STU3).address.period.start | String | | | 0..1 | The start date for the address. If not set, today's date is used.
Patient (STU3).address.postalCode | String | Optional | | 0..1 | The patient's ZIP Code. Format depends on locale. For US addresses either of the following formats are supported: * nnnnn * nnnnn-nnnn
Patient (STU3).address.state | String | Optional | | 0..1 | The state where the patient lives. Either enter the two-letter postal abbreviation for the state or the state's numeric value. The numeric value is assigned alphabetically where District of Columbia is 9 and Wyoming is 51.
Patient (STU3).address.use | String | Optional | | 0..1 | A use of "home" is supported. Addresses with other uses are ignored.
Patient (STU3).birthDate | date | Conditional | | 0..1 | The patient's date of birth in the format YYYY-MM-DD
Patient (STU3).deceasedBoolean | boolean | | | 0..1 | Whether the patient is deceased. Only a value of "False" is supported.

Patient (STU3).extension (patient-preferred-provider-sex) (also: extension (patient-preferred-provider-sex)) | Extension | Optional | Yes | 0..1 | The patient's preferred provider sex, used for scheduling.

Patient (STU3).extension (patient-preferred-provider-sex).url | uri | | | 1..1 | Must be: http://open.epic.com/FHIR/STU3/StructureDefinition/patient-preferred-provider-sex

Patient (STU3).extension (patient-preferred-provider-sex).valueCode | code | | | 0..1 | The value for the patient's preferred provider sex.

Patient (STU3).gender | code | Conditional | | 0..1 | The patient's legal sex.

Patient (STU3).generalPractitioner | Reference | Optional | Yes | 0..* | The patient's primary care provider (PCP). Reference to a Practitioner resource with a FHIR ID.

Patient (STU3).identifier | Identifier | Required | Yes | | Unique IDs assigned to the patient. Can include MPI IDs, Care Everywhere ID, National Identifiers, and Singapore Document ID. For Finland, Denmark, and UK customers additional configuration is required by each Epic organization to file these identifiers.

Patient (STU3).identifier.period | Period | | | 0..1 | In Singapore, this is the expiration date of the patient's identification document.

Patient (STU3).identifier.system | String | | | 1..1 | Epic MPI IDs (e.g. Patient MRN) MPI ID Type OID Epic Care Everywhere ID CEID National Identifier US Social Security Number: 2.16.840.1.113883.4.1 UK NHS ID: 2.16.840.1.113883.2.1.4.1 Dutch BSN: 2.16.840.1.113883.2.4.6.3 or http://fhir.nl/fhir/NamingSystem/bsn Finnish National ID: 1.2.246.21 Australian Medicare Number: http://ns.electronichealth.net.au/id/medicare-number Singapore Document ID https://open.epic.com/singapore/doc-id

Patient (STU3).identifier.type | CodeableConcept | | | 0..1 | The patient's identifier type. In Singapore, this is the patient's identification document type.

Patient (STU3).identifier.value | String | | | | The patient's ID. In Singapore, this is the patient's identification document ID.

Patient (STU3).maritalStatus | CodeableConcept | Optional | | 0..1 | The patient's marital status.

Patient (STU3).name | HumanName | Required | Yes | 1..1 | The patient's name. When submitting a create request, all names are treated as official names. Preferred names are not supported for create.

Patient (STU3).name.family | String | Required | | 1..1 | The patient's family (last) name.

Patient (STU3).name.given | String | Required | Yes | 1..2 | The patient's given name, in array format. May include first and middle names. When submitting a create request, only a single given and middle name are supported. Additional entries beyond the first two entries in the name.given array are ignored.

Patient (STU3).name.prefix | String | Optional | Yes | 0..1 | The patient's name prefix, in array format. When submitting a create request, last name prefixes and academic titles are not supported. Only the first value in the name.prefix array is used.

Patient (STU3).name.suffix | String | Optional | Yes | 0..1 | The patient's name suffix, in array format. Only the first value in the name.suffix array is used.

Patient (STU3).name.use | String | Required | | 0..1 | The purpose of the name. Accepted values are "official" and "usual". When submitting a create request, all names are treated as official names. Preferred names are not supported for create.

Patient (STU3).telecom | ContactPoint | Optional | Yes | 0..* | Telephone numbers and email addresses for the patient.

Patient (STU3).telecom.system | String | Required | | 1..1 | The type of telecom. Supported values are: * email * phone

Patient (STU3).telecom.use | String | Optional | | 0..1 | If the telecom entry is a phone number, supported values are: * home * mobile * work This value may be null for email addresses.

Patient (STU3).telecom.value | String | Required | | 1..1 | Value of the telecom method. May be an email address or phone number. If the value is a valid email address, it is filed as an email regardless of the telecom.system value.

Response elements

Name | Type | Optional | Array | Cardinality | Description

Patient (STU3) | Resource

Patient (STU3).active | boolean | | | 1..1 | Whether the patient record is active.

Patient (STU3).address | Address | | Yes | 0..* | The patient's current address, as well as any previous or temporary addresses, if applicable. The patient's current address has a use code of "home". If the patient also has one or more previous addresses, each previous address has a use code of "old". The patient's temporary address has a use code of "temp".

Patient (STU3).address.city | String | | | 0..1 | The city that the patient lives in.

Patient (STU3).address.country | String | | | 0..1 | The country that the patient lives in.

Patient (STU3).address.district | String | | | 0..1 | The county that the patient lives in.

Patient (STU3).address.line | String | | Yes | 0..* | The patient’s street address.

Patient (STU3).address.line.extension (houseNumber) (also: extension (houseNumber)) | Extension | | Yes | 1..* | For organizations in the Netherlands, this item represents the portion of a patient or contact's address that is their house number. URL: http://hl7.org/fhir/StructureDefinition/iso21090-ADXP-houseNumber

Patient (STU3).address.line.extension (streetName) (also: extension (streetName)) | Extension | | Yes | 0..* | For organizations in the Netherlands, this item represents the portion of a patient or contact's address that includes the name of their street. URL: http://hl7.org/fhir/StructureDefinition/iso21090-ADXP-streetName

Patient (STU3).address.period | Period | | | 0..1 | The effective dates for the address.

Patient (STU3).address.postalCode | String | | | 0..1 | The patient’s postal code.

Patient (STU3).address.state | String | | | 0..1 | The state where the patient lives.

Patient (STU3).address.text | String | | | 0..1 | The patient's full address as a string. This is formatted based on the country the address is in.

Patient (STU3).address.use | String | | | 1..1 | The type of address. The value is "home" for a permanent address, "old" for a previous permanent address, or "temp" for a temporary address. Addresses with a type of “temp” are returned as noted depending on Epic version: In the May 2025 version of Epic or later: Returned only if the Epic organization has configured temporary addresses to be visible in FHIR responses, regardless of locale. In versions prior to the May 2025 version of Epic: Always returned for organizations in Singapore. Starting in the August 2024 version of Epic, or the May 2024 version with special updates, and prior to the May 2025 version: Always returned for organizations in Norway.

Patient (STU3).birthDate | date | | | 1..1 | The patient's date of birth in the format YYYY-MM-DD

Patient (STU3).birthDate.extension (birthTime) (also: extension (birthTime)) | Extension | | | 0..* | The patient's time of birth. This extension follows the HL7 birthTime specification. Returned in August 2023 versions of Epic and earlier. URL: http://hl7.org/fhir/StructureDefinition/patient-birthTime

Patient (STU3).birthDate.extension (dataAbsentReason) (also: extension (dataAbsentReason)) | Extension | | | 0..* | Available starting with the November 2024 version of Epic. If the patient's birth date is not recorded, this extension is returned with a value of "unknown". URL: http://hl7.org/fhir/StructureDefinition/data-absent-reason

Patient (STU3).communication | BackboneElement | | Yes | 0..* | Languages used to communicate with the patient, along with an indicator of which is preferred.

Patient (STU3).communication.extension (comment) (also: extension (comment)) | Extension | | Yes | 0..1 | A comment about the patient's language proficiency. This extension is returned only for organizations in the Netherlands. URL: http://nictiz.nl/fhir/StructureDefinition/Comment

Patient (STU3).communication.extension (patient-proficiency) (also: extension (patient-proficiency)) | Extension | | Yes | 0..* | Container extension that holds details about the patient's language proficiency. Contains two child extensions which indicate the type of language proficiency and the level of that proficiency. This extension is returned only for organizations in the Netherlands. URL: http://nictiz.nl/fhir/StructureDefinition/patient-proficiency

Patient (STU3).communication.extension (patient-proficiency).extension (v3-LanguageAbilityMode) (also: extension (v3-LanguageAbilityMode)) | Extension | | Yes | 0..1 | Patient's language proficiency type. This is a valueCoding wherein the following code and display values are supported: RSP - Received spoken ESP - Expressed spoken RWR - Received written System value of http://terminology.hl7.org/CodeSystem/v3-LanguageAbilityMode URL: type

Patient (STU3).communication.extension (patient-proficiency).extension (v3-LanguageAbilityProficiency) (also: extension (v3-LanguageAbilityProficiency)) | Extension | | Yes | 0..1 | Patient's language proficiency level. This is a valueCoding wherein the following code and display values are supported: E - Excellent G - Good F - Fair P - Poor System value of http://terminology.hl7.org/CodeSystem/v3-LanguageAbilityProficiency URL: level

Patient (STU3).communication.language | CodeableConcept | | | 1..1 | The patient's general language, onsite care language, and spoken language.

Patient (STU3).communication.preferred | boolean | | | 0..1 | Whether the language is the patient's preferred language.

Patient (STU3).communication.preferred.extension (patient-preferenceType) (also: extension (patient-preferenceType)) | Extension | | Yes | 0..1 | The preferred mode of communication for the patient’s preferred language. This can be either verbal or written. Returned starting in the May 2025 version of Epic. Returned with system http://hl7.org/fhir/language-preference-type. URL: http://hl7.org/fhir/StructureDefinition/patient-preferenceType

Patient (STU3).contact | BackboneElement | | Yes | 0..* | Details for the patient's contacts. Patient contacts include any documented family members, emergency contacts, care givers, acquaintances, and employers.

Patient (STU3).contact.address | Address | | | 1..1 | The contact address. For responses to a patient-facing application, this element is not returned for contacts linked to a patient record. For organizations in the Netherlands, this element represents an nl-core-address value.

Patient (STU3).contact.name | HumanName | | | 1..1 | The contact's name. The system determines this from the contact's linked patient record if available. For contacts linked to a patient record, only the patient's first name is returned in patient context. For organizations in the Netherlands, this element represents an nl-core-humanname value.

Patient (STU3).contact.name.extension (humannameAssemblyOrder) (also: extension (humannameAssemblyOrder)) | Extension | | Yes | 0..* | This extension is populated only for organizations in the Netherlands. Name order for the contact. One of the following values: * NL1-Own Name * NL2-Partner Name * NL3-Partner Name followed by Maiden Name * NL4-Own Name followed by Partner Name URL: http://hl7.org/fhir/StructureDefinition/humanname-assembly-order

Patient (STU3).contact.organization | Reference | | | 0..1 | An Organization reference that represents the patient's employer. Returned when contact.relationship.code is E.

Patient (STU3).contact.period | Period | | | 1..1 | The contact period.

Patient (STU3).contact.relationship | CodeableConcept | | Yes | 1..* | The contact’s relationship to the patient. This element can return multiple values. It will always return one or more Epic category values for the contact’s relationship to the patient. In addition, it can return one or more of the following: For organizations in the Netherlands, either a Relationship (RelatieCodelijst) code system value or a role (RolCodelijst) code system value. For all other organizations, can return either a code system value – such as “C” (emergency contact) or “E” (employer) – or a RoleClass code system value – such as “GUARD” or “AGNT”.

Patient (STU3).contact.telecom | ContactPoint | | Yes | 0..* | Telephone numbers and email address for the contact. For responses to a patient-facing application, this element is not returned for contacts linked to a patient record. For organizations in the Netherlands, this element represents an nl-core-contactpoint value.

Patient (STU3).contact.telecom.rank | Int64 | | | 0..1 | The priority for permanent phone numbers or emails. 1 indicates the highest priority phone number, 2 indicates the second priority, and so on. Starting in the May 2025 version of Epic, rank is returned for the phone numbers of patient contacts.

Patient (STU3).contact.telecom.system | String | | | 0..1 | The type of telecom. Potential values are: email phone

Patient (STU3).contact.telecom.use | String | | | 0..1 | If the telecom entry is a phone number, possible values are: home mobile work

Patient (STU3).contact.telecom.value | String | | | 1..1 | Value of the telecom method. Can be an email address or phone number.

Patient (STU3).deceasedBoolean | boolean | | | 0..1 | Whether the patient is deceased.

Patient (STU3).deceasedDateTime | dateTime | | | 0..1 | The date and time of death.

Patient (STU3).extension (birth sex) (also: extension (birth sex)) | Extension | | Yes | 0..* | The patient's sex assigned at birth. This element is not returned for organizations in the Netherlands. URL: http://hl7.org/fhir/us/core/StructureDefinition/us-core-birthsex

Patient (STU3).extension (birth-location) (also: extension (birth-location)) | Extension | | Yes | 0..1 | A reference to a newborn’s birth facility. URL: http://open.epic.com/FHIR/StructureDefinition/extension/birth-location

Patient (STU3).extension (gender-identity) (also: extension (gender-identity)) | Extension | | Yes | 0..1 | The patient's gender identity. URL: http://hl7.org/fhir/StructureDefinition/patient-genderIdentity

Patient (STU3).extension (legal-sex) (also: extension (legal-sex)) | Extension | | Yes | 0..1 | The patient's legal sex. URL: http://open.epic.com/FHIR/StructureDefinition/extension/legal-sex

Patient (STU3).extension (patient-preferred-provider-language) (also: extension (patient-preferred-provider-language)) | Extension | | Yes | 1..1 | The patient's preferred provider language, used for scheduling. URL: http://open.epic.com/FHIR/STU3/StructureDefinition/patient-preferred-provider-language

Patient (STU3).extension (patient-preferred-provider-sex) (also: extension (patient-preferred-provider-sex)) | Extension | | Yes | 0..1 | The patient's preferred provider sex, used for scheduling. URL: http://open.epic.com/FHIR/STU3/StructureDefinition/patient-preferred-provider-sex

Patient (STU3).extension (patient-race) (also: extension (patient-race)) | Extension | | Yes | 0..1 | The patient's race. This is returned for organizations in Singapore URL: http://open.epic.com/FHIR/StructureDefinition/extension/patient-race

Patient (STU3).extension (patient-type) (also: extension (patient-type)) | Extension | | Yes | 0..* | The type of patient, such as Confidential or Employee. URL: http://open.epic.com/FHIR/StructureDefinition/extension/patient-type

Patient (STU3).extension (patient-unmerge-source) (also: extension (patient-unmerge-source)) | Extension | | Yes | 0..* | This extension contains a collection of extensions that represent the metadata for a patient record unmerge from the perspective of the source patient. If the patient is involved as the source patient in multiple unmerges, this set of extensions is returned for each unmerge event. URL: https://open.epic.com/FHIR/StructureDefinition/patient-unmerge-source

Patient (STU3).extension (patient-unmerge-source).extension (patient-merge-unmerge-instant) (also: extension (patient-merge-unmerge-instant)) | Extension | | Yes | 0..1 | The instant the patient merge or unmerge event occurred. URL: https://open.epic.com/FHIR/StructureDefinition/patient-merge-unmerge-instant

Patient (STU3).extension (patient-unmerge-source).extension (patient-unmerge-current-target-reference) (also: extension (patient-unmerge-current-target-reference)) | Extension | | Yes | 0..1 | A reference to the current FHIR ID of the unmerge event's target patient. URL: https://open.epic.com/FHIR/StructureDefinition/patient-unmerge-current-target-reference

Patient (STU3).extension (patient-unmerge-source).extension (patient-unmerge-old-target-reference) (also: extension (patient-unmerge-old-target-reference)) | Extension | | Yes | 0..1 | A reference to the FHIR ID of the unmerge event's target patient at the time of the

merge. URL: https://open.epic.com/FHIR/StructureDefinition/patient-unmerge-old-target-reference

Patient (STU3).extension (patient-unmerge-source).extension (patient-unmerge-original-source-reference) (also: extension (patient-unmerge-original-source-reference)) | Extension | | Yes | 0..1 | A reference to the current FHIR ID of the unmerge event's source patient. URL: https://open.epic.com/FHIR/StructureDefinition/patient-unmerge-original-source-reference

Patient (STU3).extension (patient-unmerge-source).extension (patient-unmerge-reference-old) (also: extension (patient-unmerge-reference-old)) | Extension | | Yes | 0..1 | A reference to the FHIR ID of the unmerge event's source patient at the time of the merge. URL: https://open.epic.com/FHIR/StructureDefinition/patient-unmerge-reference-old

Patient (STU3).extension (patient-unmerge-target) (also: extension (patient-unmerge-target)) | Extension | | Yes | 0..* | This extension contains a collection of extensions that represent the metadata for a patient record unmerge from the perspective of the target patient. If the patient is involved as the target patient in multiple unmerges, this set of extensions is returned for each unmerge event. URL: https://open.epic.com/FHIR/StructureDefinition/patient-unmerge-target

Patient (STU3).extension (patient-unmerge-target).extension (patient-merge-unmerge-instant) (also: extension (patient-merge-unmerge-instant)) | Extension | | Yes | 0..1 | The instant the patient merge or unmerge event occurred. URL: https://open.epic.com/FHIR/StructureDefinition/patient-merge-unmerge-instant

Patient (STU3).extension (patient-unmerge-target).extension (patient-unmerge-old-target-reference) (also: extension (patient-unmerge-old-target-reference)) | Extension | | Yes | 0..1 | A reference to the FHIR ID of the unmerge event's target patient at the time of the merge. URL: https://open.epic.com/FHIR/StructureDefinition/patient-unmerge-old-target-reference

Patient (STU3).extension (patient-unmerge-target).extension (patient-unmerge-original-source-reference) (also: extension (patient-unmerge-original-source-reference)) | Extension | | Yes | 0..1 | A reference to the current FHIR ID of the unmerge event's source patient. URL: https://open.epic.com/FHIR/StructureDefinition/patient-unmerge-original-source-reference

Patient (STU3).extension (patient-unmerge-target).extension (patient-unmerge-reference-old) (also: extension (patient-unmerge-reference-old)) | Extension | | Yes | 0..1 | A reference to the FHIR ID of the unmerge event's source patient at the time of the merge. URL: https://open.epic.com/FHIR/StructureDefinition/patient-unmerge-reference-old

Patient (STU3).extension (sex-for-clinical-use) (also: extension (sex-for-clinical-use)) | Extension | | Yes | 0..1 | The patient's sex for clinical decision making. This is an Epic-calculated value. If the patient's sex, gender, and clinical information indicate the patient is not unambiguously a cisgender male or female, the extension is not included. URL: http://open.epic.com/FHIR/StructureDefinition/extension/sex-for-clinical-use

Patient (STU3).extension (us-core-ethnicity) (also: extension (us-core-ethnicity)) | Extension | | Yes | 0..1 | The patient's ethnicity. This element is not returned for organizations in the Netherlands. URL: http://hl7.org/fhir/us/core/StructureDefinition/us-core-ethnicity

Patient (STU3).extension (us-core-race) (also: extension (us-core-race)) | Extension | | Yes | 0..1 | The patient's race. This element is not returned for organizations in the Netherlands. URL: http://hl7.org/fhir/us/core/StructureDefinition/us-core-race

Patient (STU3).gender | code | | | 1..1 | The patient's legal sex.

Patient (STU3).generalPractitioner | Reference | | Yes | 0..* | The patient's primary care provider (PCP). Reference to a Practitioner resource.

Patient (STU3).id | id | | | 1..1 | The Patient FHIR ID.

Patient (STU3).identifier | Identifier | | Yes | 0..* | The patient's identifiers. Includes the following: Epic MPI IDs (e.g. MRNs) Epic database IDs National IDs FHIR ID Care Everywhere ID For organizations in Singapore, the patient’s document ID, type, and expiry date.

Patient (STU3).identifier.system | String | | | 1..1 | Epic Identity IDs (e.g. Patient MRN) Identity ID OID Identity ID HL7 Assigning Authority as the "Text" value. Epic MyChart IDs MyChart login OID Epic Care Everywhere ID CEID Epic internal ID OID generated for Epic patient records National Identifier US Social Security Number: 2.16.840.1.113883.4.1 UK NHS ID: 2.16.840.1.113883.2.1.4.1 Dutch BSN: 2.16.840.1.113883.2.4.6.3 or http://fhir.nl/fhir/NamingSystem/bsn Finnish National ID: 1.2.246.21 Australian Medicare Number: http://ns.electronichealth.net.au/id/medicare-number FHIR ID STU3 and up: http://open.epic.com/FHIR/StructureDefinition/patient-fhir-id DSTU2: http://open.epic.com/FHIR/StructureDefinition/patient-dstu2-fhir-id

Patient (STU3).identifier.type | CodeableConcept | | | 0..1 | The patient's identifier type.

Patient (STU3).identifier.value | String | | | 1..1 | The patient's ID.

Patient (STU3).identifier.value.extension (rendered-value) (also: extension (rendered-value)) | Extension | | Yes | 0..1 | Contains the patient's masked national ID if the organization masks national identifiers. URL: http://hl7.org/fhir/StructureDefinition/rendered-value

Patient (STU3).link | BackboneElement | | Yes | 0..* | Contains links to other patient records if the patient record was merged. Starting in February 2024, the 30 most recent merge events are returned instead of all merge events.

Patient (STU3).link.extension (patient-merge-unmerge-instant) (also: extension (patient-merge-unmerge-instant)) | Extension | | Yes | 0..1 | The instant the patient merge or unmerge event occurred. URL: https://open.epic.com/FHIR/StructureDefinition/patient-merge-unmerge-instant

Patient (STU3).link.other | Reference | | | 0..1 | A reference to the Patient resource that was merged into the Patient resource currently being viewed.

Patient (STU3).link.other.reference | String | | | 0..1 | A reference to the Patient resource that this Patient replaces.

Patient (STU3).link.type | code | | | 1..1 | The type of link between Patient resources. This is always set to "replaces".

Patient (STU3).managingOrganization | Reference | | | 0..1 | The patient's primary service area. Reference to an Organization resource.

Patient (STU3).maritalStatus | CodeableConcept | | | 0..1 | The patient's marital status.

Patient (STU3).meta | Meta | | | 1..1 | Metadata about the resource.

Patient (STU3).meta.profile | String | | Yes | 0..1 | Only returned for organizations in the Netherlands. This element shows that this API conforms to the profile connected to the following canonical url: http://fhir.nl/fhir/StructureDefinition/nl-core-patient

Patient (STU3).meta.security | Coding | | Yes | 0..* | The patient’s unverified status. Available starting in the May 2024 version of Epic, as well as the February 2024 and November 2023 with special updates. This is used to track new patient records that might need to be reconciled against existing records in the system. The element is not returned for verified patients. Unverified patients always return the value PATRPT (Patient Reported) along with one of the following values: UNCERTAIN (Uncertain Reliability) UNRELIABLE (Unreliable)

Patient (STU3).multipleBirthInteger | integer | | | 0..1 | The patient's birth order.

Patient (STU3).name | HumanName | | Yes | 1..* | The patient's name. This element includes both the patient's "official" name, which returns the patient's full name, and the patient's "usual" name, which returns the patient's preferred name. If the patient does not have a preferred name defined, the "usual" name also returns the patient's full name.

Patient (STU3).name.extension (humanNameAssemblyOrder) (also: extension (humanNameAssemblyOrder)) | Extension | | Yes | 0..* | This extension is populated only for organizations in the Netherlands. Name order for the contact. One of the following values: * NL1-Own Name * NL2-Partner Name * NL3-Partner Name followed by Maiden Name * NL4-Own Name followed by Partner Name URL: http://hl7.org/fhir/StructureDefinition/humanname-assembly-order

Patient (STU3).name.family | String | | | 1..1 | The patient's family (last) name. Can contain a data-absent-reason extension with a value of "unknown" if the patient has an alias that cannot be returned as discrete elements or if the patient's preferred name replaces their full name.

Patient (STU3).name.family.extension (data-absent-reason) (also: extension (data-absent-reason)) | Extension | | Yes | 0..1 | Returned as "unknown" for patients without family names.

Patient (STU3).name.family.extension (humanNameOwnName) (also: extension (humanNameOwnName)) | Extension | | Yes | 0..1 | The portion of a patient's family name derived from the patient's own name.

Patient (STU3).name.family.extension (humanNameOwnPrefix) (also: extension (humanNameOwnPrefix)) | Extension | | Yes | 0..1 | The prefix portion of a patient's family name derived from the patient's own surname.

Patient (STU3).name.family.extension (humanNamePartnerName) (also: extension (humanNamePartnerName)) | Extension | | Yes | 0..1 | The portion of a patient's family name derived from the patient's partner's name.

Patient (STU3).name.family.extension (humanNamePartnerPrefix) (also: extension (humanNamePartnerPrefix)) | Extension | | Yes | 0..1 | The prefix portion of a patient's family name derived from the patient's partner's surname.

Patient (STU3).name.given | String | | Yes | 1..* | The patient's given name. Can include first and middle names.

Patient (STU3).name.given.extension (namePartQualifier) (also: extension (namePartQualifier)) | Extension | | Yes | 1..* | This extension is returned if initials or a preferred name are present. The entity qualifier extension code is IN for initials and CL for preferred name.

Patient (STU3).name.prefix | String | | Yes | 0..1 | The patient's name prefix.

Patient (STU3).name.suffix | String | | Yes | 0..* | The patient's name suffix. Acquired as a title due to academic, legal, employment or nobility status, etc.

Patient (STU3).name.text | String | | | 1..1 | The patient's full name as a string.

Patient (STU3).name.use | String | | | 1..1 | The purpose of the name. Can be "official", "usual", or "old".

Patient (STU3).telecom | ContactPoint | | Yes | 0..* | Telephone numbers and email addresses for the patient, along with their use (home or work for example) and their preferred rank (which to contact first, second, third, etc).

Patient (STU3).telecom.rank | Int64 | | | 0..1 | The priority for permanent phone numbers or emails. 1 indicates the highest priority phone number, 2 indicates the second priority, and so on. The preferred has a rank of 1. Additional emails have a null rank.

Patient (STU3).telecom.system | String | | | 1..1 | The type of telecom. Potential values are: email phone fax url pager sms other

Patient (STU3).telecom.use | String | | | 0..1 | If the telecom entry is a phone number, possible values are: home mobile work temp old Use is not returned for emails.

Patient (STU3).telecom.value | String | | | 1..1 | Value of the telecom method. Can be an email address or phone number.

Sample request

```
POST https://hostname/instance/api/FHIR/STU3/Patient
{
  "resourceType": "Patient",
  "identifier": [
    {
      "use": "usual",
      "system": "urn:oid:1.2.840.114350.1.13.861.1.7.5.737384.27000",
      "value": "8512"
    },
    {
      "use": "usual",
      "system": "urn:oid:2.16.840.1.113883.4.1",
      "value": "999-99-9999"
    }
  ],
  "name": [
    {
      "use": "official",
      "family": "Patient",
      "given": [
        "Test"
      ],
      "suffix": [
        "JR."
      ]
    }
  ],
  "telecom": [
    {
      "system": "phone",
      "value": "336-544-1111",
      "use": "home"
    },
    {
      "system": "email",
      "value": "test.patient@epic.com"
    }
  ],
  "gender": "female",
  "birthDate": "1994-07-20",
  "address": [
    {
      "use": "home",
      "line": [
        "100 Milky Way",
        "Learning Campus"
      ],
      "city": "Verona",
      "state": "WI",
      "postalCode": "53593",
      "country": "USA"
    }
  ],
  "maritalStatus": {
    "text": "Single"
  },
  "generalPractitioner": [
    {
      "display": "Sample Provider, MD",
```

```
      "reference": "https://hostname/instance/api/FHIR/STU3/Practitioner/e4ZKPXZ0ux4Z80UHywzHyHg3"
    }
  ],
  "extension": [
    {
      "url": "http://open.epic.com/FHIR/STU3/StructureDefinition/patient-preferred-provider-language",
      "valueCodeableConcept": {
        "coding": [
          {
            "system": "urn:oid:2.16.840.1.113883.6.99",
            "code": "ja"
          }
        ],
        "text": "Japanese"
      }
    },
    {
      "url": "http://open.epic.com/FHIR/STU3/StructureDefinition/patient-preferred-provider-sex",
      "valueCode": "female"
    },
    {
      "url": "http://hl7.org/fhir/StructureDefinition/patient-genderIdentity",
      "valueCodeableConcept": {
        "coding": [
          {
            "system": "urn:oid:1.2.840.114350.1.13.5325.1.7.10.698084.131.657370.1194",
            "code": "female"
          }
        ]
      }
    }
  ]
}
```

Sample response

```
Status code: Created (201)
Content-Type: application/json; charset=utf-8
Location: Patient/ei4u9SQ4uH7sl61.VEhXgng3
```

Change log

Epic Version | Description | Type

November 2022 | Epic has updated the behavior of certain modifier elements in FHIR write APIs to ensure the data in the incoming request body matches the data filed to the database and to comply with the HL7 FHIR specification. Previously, the modifier element was ignored in certain situations, and an undocumented default value was saved in its place. Now, if the modifier element is included and is set to an unaccepted value, a fatal error logs, preventing the request from filing to the database. The FHIR request returns an OperationOutcome with the invalid element and what value is accepted for that element. Element Accepted Incoming Value Default Value active true true deceasedBoolean false false deceasedDateTime None - will always trigger fatal error None - not supported on incoming requests link None - will always trigger fatal error None - not supported on incoming requests | Substantive change

Element | Accepted Incoming Value | Default Value

active | true | true

deceasedBoolean | false | false

deceasedDateTime | None - will always trigger fatal error | None - not supported on incoming requests

link | None - will always trigger fatal error | None - not supported on incoming requests

22.2.2 Patient.Read (STU3)

File: site/apis/22-Identification-Individuals/2-STU3/825-Patient-Read-STU3.html

Epic API ID | 825

FHIR version | STU3

Categories | Identification Individuals

API type | USCDI

A la carte | Industry-Standard Level 1 API

USCDI | Yes

Keywords | Care Team Members;Patient Demographics;First name;Last name;Middle name;initial;Suffix;Birth sex;Date of birth;Race;Ethnicity;Preferred language;Address;Phone number;Previous name

Available in inpatient and other contexts | Yes

ONC certification products | EpicCare Ambulatory Base, EpicCare Inpatient Base

ONC certification versions | Epic 2018

HTTP method | GET

URL template | api/FHIR/STU3/Patient/{ID}

Supports OAuth 2.0 | True

Supported user types | Backend Systems and Non-OAuth 2.0, Clinicians or Administrative Users, Patients

Performs scope validation | False

Source | https://fhir.epic.com/Specifications?api=825

Description

The FHIR Patient resource defines demographics, care providers, and other administrative information about a person receiving care at a health organization.

A non-patient user must have appropriate security to have search details, demographic details, and/or PCP details included in the Patient resource.

This web service respects all patient-facing security for demographic information when used in the context of a patient as the user.

If an Epic organization has configured service area restrictions, the user accessing this FHIR resource must be authorized to view patients in the target service area.

When two patients are merged, a Patient.Read on the target (surviving) patient will work normally. The source patient will return a 404 error, as we consider the source patient FHIR ID to be invalid.

Note:

If you plan to use this API on a patient-facing app, and you plan to integrate with MyChart Bedside, you should use the R4 version of this resource or later. Older versions of the Patient resource will fail in this context if the patient does not have a standard MyChart account outside of MyChart Beside.

Remarks

You can configure this FHIR resource using the following profile variables:

* COMM_EQUIP_TYPE_TBL
* FHIR_SEX_AT_BIRTH_TBL
* GENDER_TBL
* GENDER_IDENTITY_TBL
* MARITAL_TABLE
* PCP_TYPES

Request parameters

Name | Type | Optional | Array | Cardinality | Description
ID | token | Required | | | The Patient FHIR ID.

Response elements

Name | Type | Optional | Array | Cardinality | Description
Patient (STU3) | Resource
Patient (STU3).active | boolean | | | 1..1 | Whether the patient record is active.
Patient (STU3).address | Address | | Yes | 0..* | The patient's current address, as well as any previous or temporary addresses, if applicable. The patient's current address has a use code of "home". If the patient also has one or more previous addresses, each previous address has a use code of "old". The patient's temporary address has a use code of "temp".
Patient (STU3).address.city | String | | | 0..1 | The city that the patient lives in.
Patient (STU3).address.country | String | | | 0..1 | The country that the patient lives in.
Patient (STU3).address.district | String | | | 0..1 | The county that the patient lives in.
Patient (STU3).address.line | String | | Yes | 0..* | The patient’s street address.
Patient (STU3).address.line.extension (houseNumber) (also: extension (houseNumber)) | Extension | | Yes | 1..* | For organizations in the Netherlands, this item represents the portion of a patient or contact's address that is their house number. URL: http://hl7.org/fhir/StructureDefinition/iso21090-ADXP-houseNumber
Patient (STU3).address.line.extension (streetName) (also: extension (streetName)) | Extension | | Yes | 0..* | For organizations in the Netherlands, this item represents the portion of a patient or contact's address that includes the name of their street. URL: http://hl7.org/fhir/StructureDefinition/iso21090-ADXP-streetName
Patient (STU3).address.period | Period | | | 0..1 | The effective dates for the address.
Patient (STU3).address.postalCode | String | | | 0..1 | The patient’s postal code.
Patient (STU3).address.state | String | | | 0..1 | The state where the patient lives.
Patient (STU3).address.text | String | | | 0..1 | The patient's full address as a string. This is formatted based on the country the address is in.
Patient (STU3).address.use | String | | | 1..1 | The type of address. The value is "home" for a permanent address, "old" for a previous permanent address, or "temp" for a temporary address. Addresses with a type of “temp” are returned as noted depending on Epic version: In the May 2025 version of Epic or later: Returned only if the Epic organization has configured temporary addresses to be visible in FHIR responses, regardless of locale. In versions prior to the May 2025 version of Epic: Always returned for organizations in Singapore. Starting in the August 2024 version of Epic, or the May 2024 version with special updates, and prior to the May 2025 version: Always returned for organizations in Norway.
Patient (STU3).birthDate | date | | | 1..1 | The patient's date of birth in the format YYYY-MM-DD
Patient (STU3).birthDate.extension (birthTime) (also: extension (birthTime)) | Extension | | | 0..* | The patient's time of birth. This extension follows the HL7 birthTime specification. Returned in August 2023 versions of Epic and earlier. URL: http://hl7.org/fhir/StructureDefinition/patient-birthTime
Patient (STU3).birthDate.extension (dataAbsentReason) (also: extension (dataAbsentReason)) | Extension | | | 0..* | Available starting with the November 2024 version of Epic. If the patient's birth date is not recorded, this extension is returned with a value of "unknown". URL: http://hl7.org/fhir/StructureDefinition/data-absent-reason
Patient (STU3).communication | BackboneElement | | Yes | 0..* | Languages used to communicate with the patient, along with an indicator of which is preferred.
Patient (STU3).communication.extension (comment) (also: extension (comment)) | Extension | | Yes | 0..1 | A comment about the patient's language proficiency. This extension is returned only for organizations in the Netherlands. URL: http://nictiz.nl/fhir/StructureDefinition/Comment
Patient (STU3).communication.extension (patient-proficiency) (also: extension (patient-proficiency)) | Extension | | Yes | 0..* | Container extension that holds details about the patient's language proficiency. Contains two child extensions which indicate the type of language proficiency and the level of that proficiency. This extension is returned only for organizations in the Netherlands. URL:

http://nictiz.nl/fhir/StructureDefinition/patient-proficiency

Patient (STU3).communication.extension (patient-proficiency).extension (v3-LanguageAbilityMode) (also: extension (v3-LanguageAbilityMode)) | Extension | | Yes | 0..1 | Patient's language proficiency type. This is a valueCoding wherein the following code and display values are supported: RSP - Received spoken ESP - Expressed spoken RWR - Received written System value of http://terminology.hl7.org/CodeSystem/v3-LanguageAbilityMode URL: type

Patient (STU3).communication.extension (patient-proficiency).extension (v3-LanguageAbilityProficiency) (also: extension (v3-LanguageAbilityProficiency)) | Extension | | Yes | 0..1 | Patient's language proficiency level. This is a valueCoding wherein the following code and display values are supported: E - Excellent G - Good F - Fair P - Poor System value of http://terminology.hl7.org/CodeSystem/v3-LanguageAbilityProficiency URL: level

Patient (STU3).communication.language | CodeableConcept | | | 1..1 | The patient's general language, onsite care language, and spoken language.

Patient (STU3).communication.preferred | boolean | | | 0..1 | Whether the language is the patient's preferred language.

Patient (STU3).communication.preferred.extension (patient-preferenceType) (also: extension (patient-preferenceType)) | Extension | | Yes | 0..1 | The preferred mode of communication for the patient’s preferred language. This can be either verbal or written. Returned starting in the May 2025 version of Epic. Returned with system http://hl7.org/fhir/language-preference-type. URL: http://hl7.org/fhir/StructureDefinition/patient-preferenceType

Patient (STU3).contact | BackboneElement | | Yes | 0..* | Details for the patient's contacts. Patient contacts include any documented family members, emergency contacts, care givers, acquaintances, and employers.

Patient (STU3).contact.address | Address | | | 1..1 | The contact address. For responses to a patient-facing application, this element is not returned for contacts linked to a patient record. For organizations in the Netherlands, this element represents an nl-core-address value.

Patient (STU3).contact.name | HumanName | | | 1..1 | The contact's name. The system determines this from the contact's linked patient record if available. For contacts linked to a patient record, only the patient's first name is returned in patient context. For organizations in the Netherlands, this element represents an nl-core-humanname value.

Patient (STU3).contact.name.extension (humannameAssemblyOrder) (also: extension (humannameAssemblyOrder)) | Extension | | Yes | 0..* | This extension is populated only for organizations in the Netherlands. Name order for the contact. One of the following values: * NL1-Own Name * NL2-Partner Name * NL3-Partner Name followed by Maiden Name * NL4-Own Name followed by Partner Name URL: http://hl7.org/fhir/StructureDefinition/humanname-assembly-order

Patient (STU3).contact.organization | Reference | | | 0..1 | An Organization reference that represents the patient's employer. Returned when contact.relationship.code is E.

Patient (STU3).contact.period | Period | | | 1..1 | The contact period.

Patient (STU3).contact.relationship | CodeableConcept | | Yes | 1..* | The contact’s relationship to the patient. This element can return multiple values. It will always return one or more Epic category values for the contact’s relationship to the patient. In addition, it can return one or more of the following: For organizations in the Netherlands, either a Relationship (RelatieCodelijst) code system value or a role (RolCodelijst) code system value. For all other organizations, can return either a code system value – such as “C” (emergency contact) or “E” (employer) – or a RoleClass code system value – such as “GUARD” or “AGNT”.

Patient (STU3).contact.telecom | ContactPoint | | Yes | 0..* | Telephone numbers and email address for the contact. For responses to a patient-facing application, this element is not returned for contacts linked to a patient record. For organizations in the Netherlands, this element represents an nl-core-contactpoint value.

Patient (STU3).contact.telecom.rank | Int64 | | | 0..1 | The priority for permanent phone numbers or emails. 1 indicates the highest priority phone number, 2 indicates the second priority, and so on. Starting in the May 2025 version of Epic, rank is returned for the phone numbers of patient contacts.

Patient (STU3).contact.telecom.system | String | | | 0..1 | The type of telecom. Potential values are: email phone

Patient (STU3).contact.telecom.use | String | | | 0..1 | If the telecom entry is a phone number, possible values are: home mobile work

Patient (STU3).contact.telecom.value | String | | | 1..1 | Value of the telecom method. Can be an email address or phone number.

Patient (STU3).deceasedBoolean | boolean | | | 0..1 | Whether the patient is deceased.

Patient (STU3).deceasedDateTime | dateTime | | | 0..1 | The date and time of death.

Patient (STU3).extension (birth sex) (also: extension (birth sex)) | Extension | | Yes | 0..* | The patient's sex assigned at birth. This element is not returned for organizations in the Netherlands. URL: http://hl7.org/fhir/us/core/StructureDefinition/us-core-birthsex

Patient (STU3).extension (birth-location) (also: extension (birth-location)) | Extension | | Yes | 0..1 | A reference to a newborn’s birth facility. URL: http://open.epic.com/FHIR/StructureDefinition/extension/birth-location

Patient (STU3).extension (gender-identity) (also: extension (gender-identity)) | Extension | | Yes | 0..1 | The patient's gender identity. URL: http://hl7.org/fhir/StructureDefinition/patient-genderIdentity

Patient (STU3).extension (legal-sex) (also: extension (legal-sex)) | Extension | | Yes | 0..1 | The patient's legal sex. URL: http://open.epic.com/FHIR/StructureDefinition/extension/legal-sex

Patient (STU3).extension (patient-preferred-provider-language) (also: extension (patient-preferred-provider-language)) | Extension | | Yes | 1..1 | The patient's preferred provider language, used for scheduling. URL: http://open.epic.com/FHIR/STU3/StructureDefinition/patient-preferred-provider-language

Patient (STU3).extension (patient-preferred-provider-sex) (also: extension (patient-preferred-provider-sex)) | Extension | | Yes | 0..1 | The patient's preferred provider sex, used for scheduling. URL: http://open.epic.com/FHIR/STU3/StructureDefinition/patient-preferred-provider-sex

Patient (STU3).extension (patient-race) (also: extension (patient-race)) | Extension | | Yes | 0..1 | The patient's race. This is returned for organizations in Singapore URL: http://open.epic.com/FHIR/StructureDefinition/extension/patient-race

Patient (STU3).extension (patient-type) (also: extension (patient-type)) | Extension | | Yes | 0..* | The type of patient, such as Confidential or Employee. URL: http://open.epic.com/FHIR/StructureDefinition/extension/patient-type

Patient (STU3).extension (patient-unmerge-source) (also: extension (patient-unmerge-source)) | Extension | | Yes | 0..* | This extension contains a collection of extensions that represent the metadata for a patient record unmerge from the perspective of the source patient. If the patient is involved as the source patient in multiple unmerges, this set of extensions is returned for each unmerge event. URL: https://open.epic.com/FHIR/StructureDefinition/patient-unmerge-source

Patient (STU3).extension (patient-unmerge-source).extension (patient-merge-unmerge-instant) (also: extension (patient-merge-unmerge-instant)) | Extension | | Yes | 0..1 | The instant the patient merge or unmerge event occurred. URL: https://open.epic.com/FHIR/StructureDefinition/patient-merge-unmerge-instant

Patient (STU3).extension (patient-unmerge-source).extension (patient-unmerge-current-target-reference) (also: extension (patient-unmerge-current-target-reference)) | Extension | | Yes | 0..1 | A reference to the current FHIR ID of the unmerge event's target patient. URL: https://open.epic.com/FHIR/StructureDefinition/patient-unmerge-current-target-reference

Patient (STU3).extension (patient-unmerge-source).extension (patient-unmerge-old-target-reference) (also: extension (patient-unmerge-old-target-reference)) | Extension | | Yes | 0..1 | A reference to the FHIR ID of the unmerge event's target patient at the time of the merge. URL: https://open.epic.com/FHIR/StructureDefinition/patient-unmerge-old-target-reference

Patient (STU3).extension (patient-unmerge-source).extension (patient-unmerge-original-source-reference) (also: extension (patient-unmerge-original-source-reference)) | Extension | | Yes | 0..1 | A reference to the current FHIR ID of the unmerge event's source patient.

URL: https://open.epic.com/FHIR/StructureDefinition/patient-unmerge-original-source-reference

Patient (STU3).extension (patient-unmerge-source).extension (patient-unmerge-reference-old) (also: extension (patient-unmerge-reference-old)) | Extension | | Yes | 0..1 | A reference to the FHIR ID of the unmerge event's source patient at the time of the merge. URL: https://open.epic.com/FHIR/StructureDefinition/patient-unmerge-reference-old

Patient (STU3).extension (patient-unmerge-target) (also: extension (patient-unmerge-target)) | Extension | | Yes | 0..* | This extension contains a collection of extensions that represent the metadata for a patient record unmerge from the perspective of the target patient. If the patient is involved as the target patient in multiple unmerges, this set of extensions is returned for each unmerge event. URL: https://open.epic.com/FHIR/StructureDefinition/patient-unmerge-target

Patient (STU3).extension (patient-unmerge-target).extension (patient-merge-unmerge-instant) (also: extension (patient-merge-unmerge-instant)) | Extension | | Yes | 0..1 | The instant the patient merge or unmerge event occurred. URL: https://open.epic.com/FHIR/StructureDefinition/patient-merge-unmerge-instant

Patient (STU3).extension (patient-unmerge-target).extension (patient-unmerge-old-target-reference) (also: extension (patient-unmerge-old-target-reference)) | Extension | | Yes | 0..1 | A reference to the FHIR ID of the unmerge event's target patient at the time of the merge. URL: https://open.epic.com/FHIR/StructureDefinition/patient-unmerge-old-target-reference

Patient (STU3).extension (patient-unmerge-target).extension (patient-unmerge-original-source-reference) (also: extension (patient-unmerge-original-source-reference)) | Extension | | Yes | 0..1 | A reference to the current FHIR ID of the unmerge event's source patient. URL: https://open.epic.com/FHIR/StructureDefinition/patient-unmerge-original-source-reference

Patient (STU3).extension (patient-unmerge-target).extension (patient-unmerge-reference-old) (also: extension (patient-unmerge-reference-old)) | Extension | | Yes | 0..1 | A reference to the FHIR ID of the unmerge event's source patient at the time of the merge. URL: https://open.epic.com/FHIR/StructureDefinition/patient-unmerge-reference-old

Patient (STU3).extension (sex-for-clinical-use) (also: extension (sex-for-clinical-use)) | Extension | | Yes | 0..1 | The patient's sex for clinical decision making. This is an Epic-calculated value. If the patient's sex, gender, and clinical information indicate the patient is not unambiguously a cisgender male or female, the extension is not included. URL: http://open.epic.com/FHIR/StructureDefinition/extension/sex-for-clinical-use

Patient (STU3).extension (us-core-ethnicity) (also: extension (us-core-ethnicity)) | Extension | | Yes | 0..1 | The patient's ethnicity. This element is not returned for organizations in the Netherlands. URL: http://hl7.org/fhir/us/core/StructureDefinition/us-core-ethnicity

Patient (STU3).extension (us-core-race) (also: extension (us-core-race)) | Extension | | Yes | 0..1 | The patient's race. This element is not returned for organizations in the Netherlands. URL: http://hl7.org/fhir/us/core/StructureDefinition/us-core-race

Patient (STU3).gender | code | | | 1..1 | The patient's legal sex.

Patient (STU3).generalPractitioner | Reference | | Yes | 0..* | The patient's primary care provider (PCP). Reference to a Practitioner resource.

Patient (STU3).id | id | | | 1..1 | The Patient FHIR ID.

Patient (STU3).identifier | Identifier | | Yes | 0..* | The patient's identifiers. Includes the following: Epic MPI IDs (e.g. MRNs) Epic database IDs National IDs FHIR ID Care Everywhere ID For organizations in Singapore, the patient’s document ID, type, and expiry date.

Patient (STU3).identifier.system | String | | | 1..1 | Epic Identity IDs (e.g. Patient MRN) Identity ID OID Identity ID HL7 Assigning Authority as the "Text" value. Epic MyChart IDs MyChart login OID Epic Care Everywhere ID CEID Epic internal ID OID generated for Epic patient records National Identifier US Social Security Number: 2.16.840.1.113883.4.1 UK NHS ID: 2.16.840.1.113883.2.1.4.1 Dutch BSN: 2.16.840.1.113883.2.4.6.3 or http://fhir.nl/fhir/NamingSystem/bsn Finnish National ID: 1.2.246.21 Australian Medicare Number: http://ns.electronichealth.net.au/id/medicare-number FHIR ID STU3 and up: http://open.epic.com/FHIR/StructureDefinition/patient-fhir-id DSTU2: http://open.epic.com/FHIR/StructureDefinition/patient-dstu2-fhir-id

Patient (STU3).identifier.type | CodeableConcept | | | 0..1 | The patient's identifier type.

Patient (STU3).identifier.value | String | | | 1..1 | The patient's ID.

Patient (STU3).identifier.value.extension (rendered-value) (also: extension (rendered-value)) | Extension | | Yes | 0..1 | Contains the patient's masked national ID if the organization masks national identifiers. URL: http://hl7.org/fhir/StructureDefinition/rendered-value

Patient (STU3).link | BackboneElement | | Yes | 0..* | Contains links to other patient records if the patient record was merged. Starting in February 2024, the 30 most recent merge events are returned instead of all merge events.

Patient (STU3).link.extension (patient-merge-unmerge-instant) (also: extension (patient-merge-unmerge-instant)) | Extension | | Yes | 0..1 | The instant the patient merge or unmerge event occurred. URL: https://open.epic.com/FHIR/StructureDefinition/patient-merge-unmerge-instant

Patient (STU3).link.other | Reference | | | 0..1 | A reference to the Patient resource that was merged into the Patient resource currently being viewed.

Patient (STU3).link.other.reference | String | | | 0..1 | A reference to the Patient resource that this Patient replaces.

Patient (STU3).link.type | code | | | 1..1 | The type of link between Patient resources. This is always set to "replaces".

Patient (STU3).managingOrganization | Reference | | | 0..1 | The patient's primary service area. Reference to an Organization resource.

Patient (STU3).maritalStatus | CodeableConcept | | | 0..1 | The patient's marital status.

Patient (STU3).meta | Meta | | | 1..1 | Metadata about the resource.

Patient (STU3).meta.profile | String | | Yes | 0..1 | Only returned for organizations in the Netherlands. This element shows that this API conforms to the profile connected to the following canonical url: http://fhir.nl/fhir/StructureDefinition/nl-core-patient

Patient (STU3).meta.security | Coding | | Yes | 0..* | The patient’s unverified status. Available starting in the May 2024 version of Epic, as well as the February 2024 and November 2023 with special updates. This is used to track new patient records that might need to be reconciled against existing records in the system. The element is not returned for verified patients. Unverified patients always return the value PATRPT (Patient Reported) along with one of the following values: UNCERTAIN (Uncertain Reliability) UNRELIABLE (Unreliable)

Patient (STU3).multipleBirthInteger | integer | | | 0..1 | The patient's birth order.

Patient (STU3).name | HumanName | | Yes | 1..* | The patient's name. This element includes both the patient's "official" name, which returns the patient's full name, and the patient's "usual" name, which returns the patient's preferred name. If the patient does not have a preferred name defined, the "usual" name also returns the patient's full name.

Patient (STU3).name.extension (humanNameAssemblyOrder) (also: extension (humanNameAssemblyOrder)) | Extension | | Yes | 0..* | This extension is populated only for organizations in the Netherlands. Name order for the contact. One of the following values: * NL1-Own Name * NL2-Partner Name * NL3-Partner Name followed by Maiden Name * NL4-Own Name followed by Partner Name URL: http://hl7.org/fhir/StructureDefinition/humanname-assembly-order

Patient (STU3).name.family | String | | | 1..1 | The patient's family (last) name. Can contain a data-absent-reason extension with a value of "unknown" if the patient has an alias that cannot be returned as discrete elements or if the patient's preferred name replaces their full name.

Patient (STU3).name.family.extension (data-absent-reason) (also: extension (data-absent-reason)) | Extension | | Yes | 0..1 | Returned as "unknown" for patients without family names.

Patient (STU3).name.family.extension (humanNameOwnName) (also: extension (humanNameOwnName)) | Extension | | Yes | 0..1 | The portion of a patient's family name derived from the patient's own name.

Patient (STU3).name.family.extension (humanNameOwnPrefix) (also: extension (humanNameOwnPrefix)) | Extension | | Yes | 0..1 | The prefix portion of a patient's family name derived from the patient's own surname.

Patient (STU3).name.family.extension (humanNamePartnerName) (also: extension (humanNamePartnerName)) | Extension | | Yes | 0..1 | The portion of a patient's family name derived from the patient's partner's name.

Patient (STU3).name.family.extension (humanNamePartnerPrefix) (also: extension (humanNamePartnerPrefix)) | Extension | | Yes | 0..1 | The prefix portion of a patient's family name derived from the patient's partner's surname.

Patient (STU3).name.given | String | | Yes | 1..* | The patient's given name. Can include first and middle names.

Patient (STU3).name.given.extension (namePartQualifier) (also: extension (namePartQualifier)) | Extension | | Yes | 1..* | This extension is returned if initials or a preferred name are present. The entity qualifier extension code is IN for initials and CL for preferred name.

Patient (STU3).name.prefix | String | | Yes | 0..1 | The patient's name prefix.

Patient (STU3).name.suffix | String | | Yes | 0..* | The patient's name suffix. Acquired as a title due to academic, legal, employment or nobility status, etc.

Patient (STU3).name.text | String | | | 1..1 | The patient's full name as a string.

Patient (STU3).name.use | String | | | 1..1 | The purpose of the name. Can be "official", "usual", or "old".

Patient (STU3).telecom | ContactPoint | | Yes | 0..* | Telephone numbers and email addresses for the patient, along with their use (home or work for example) and their preferred rank (which to contact first, second, third, etc).

Patient (STU3).telecom.rank | Int64 | | | 0..1 | The priority for permanent phone numbers or emails. 1 indicates the highest priority phone number, 2 indicates the second priority, and so on. The preferred has a rank of 1. Additional emails have a null rank.

Patient (STU3).telecom.system | String | | | 1..1 | The type of telecom. Potential values are: email phone fax url pager sms other

Patient (STU3).telecom.use | String | | | 0..1 | If the telecom entry is a phone number, possible values are: home mobile work temp old Use is not returned for emails.

Patient (STU3).telecom.value | String | | | 1..1 | Value of the telecom method. Can be an email address or phone number.

Sample request

```
GET https://hostname/instance/api/FHIR/STU3/Patient/ezHbeFCm6Ih8kgxuHUAdvJQ3
```

Sample response


```
{
  "resourceType": "Patient",
  "id": "eNO3wqOfAltfnWMfWBQ1WmQ3",
  "extension": [
    {
      "valueCodeableConcept": {
        "coding": [
          {
            "system": "urn:oid:1.2.840.114350.1.13.5325.1.7.10.698084.130.768080.39128",
            "code": "female",
            "display": "female"
          }
        ],
        "text": "Female"
      },
      "url": "http://open.epic.com/FHIR/StructureDefinition/extension/legal-sex"
    },
    {
      "valueCodeableConcept": {
        "coding": [
          {
            "system": "http://hl7.org/fhir/gender-identity",
            "code": "other",
            "display": "other"
          }
        ]
      },
      "url": "http://hl7.org/fhir/StructureDefinition/patient-genderIdentity"
    },
    {
      "valueCode": "F",
      "url": "http://hl7.org/fhir/us/core/StructureDefinition/us-core-birthsex"
    },
    {
      "extension": [
        {
          "valueCoding": {
            "system": "http://hl7.org/fhir/us/core/ValueSet/omb-race-category",
            "code": "UNK",
            "display": "Unknown"
          },
          "url": "ombCategory"
        },
        {
          "valueString": "Unknown",
          "url": "text"
        }
      ],
      "url": "http://hl7.org/fhir/us/core/StructureDefinition/us-core-race"
    },
    {
      "extension": [
        {
          "valueCoding": {
            "system": "http://hl7.org/fhir/us/core/ValueSet/omb-ethnicity-category",
            "code": "2186-5",
            "display": "Not Hispanic or Latino"
          },
          "url": "ombCategory"
        },
```

```
      {
        "valueString": "Not Hispanic or Latino",
        "url": "text"
      }
    ],
    "url": "http://hl7.org/fhir/us/core/StructureDefinition/us-core-ethnicity"
  }
],
"identifier": [
  {
    "use": "usual",
    "type": {
      "text": "CEID"
    },
    "system": "urn:oid:1.2.840.114350.1.13.5325.1.7.3.688884.100",
    "value": "YB0LDR46VQQNGCX"
  },
  {
    "use": "usual",
    "type": {
      "text": "EDI"
    },
    "system": "urn:oid:1.2.840.114350.1.13.5325.1.7.5.737384.421",
    "value": "33400003"
  },
  {
    "use": "usual",
    "type": {
      "text": "EPI"
    },
    "system": "urn:oid:1.2.840.114350.1.1",
    "value": "107393"
  },
  {
    "use": "usual",
    "type": {
      "text": "EXTERNAL"
    },
    "system": "urn:oid:1.2.840.114350.1.13.5325.1.7.2.698084",
    "value": "Z9668"
  },
  {
    "use": "usual",
    "type": {
      "text": "FHIR"
    },
    "system": "http://open.epic.com/FHIR/StructureDefinition/patient-dstu2-fhir-id",
    "value": "TjK9XmsROjvY5OtpAOfF9aVnhgNSOVh3AzZHjvyQOKPcB"
  },
  {
    "use": "usual",
    "type": {
      "text": "FHIR STU3"
    },
    "system": "http://open.epic.com/FHIR/StructureDefinition/patient-fhir-id",
    "value": "eNO3wqOfAltfnWMfWBQ1WmQ3"
  },
  {
    "use": "usual",
    "type": {
      "text": "IDQAVClinic"
    },
    "system": "urn:oid:1.2.840.114350.1.13.5325.1.7.5.737384.123401",
    "value": "15794"
  },
  {
    "use": "usual",
    "type": {
      "text": "INTERNAL"
    },
    "system": "urn:oid:1.2.840.114350.1.13.5325.1.7.2.698084",
    "value": "     Z9668"
  },
  {
    "use": "usual",
    "type": {
      "text": "MYCHARTLOGIN"
    },
    "system": "urn:oid:1.2.840.114350.1.13.5325.1.7.3.878082.110",
    "value": "EFWFHIR"
  },
  {
    "use": "usual",
    "type": {
      "text": "WPRINTERNAL"
    },
    "system": "urn:oid:1.2.840.114350.1.13.5325.1.7.2.878082",
    "value": "14190"
  },
```

```
  {
    "extension": [
      {
        "valueString": "011-23-5813",
        "url": "http://hl7.org/fhir/StructureDefinition/rendered-value"
      }
    ],
    "use": "usual",
    "system": "urn:oid:2.16.840.1.113883.4.1",
    "value": "011-23-5813"
  }
],
"active": true,
"name": [
  {
    "use": "official",
    "text": "Test FHIR zzTest",
    "family": "zzTest",
    "given": [
      "Test",
      "FHIR"
    ]
  },
  {
    "use": "usual",
    "text": "Test FHIR zzTest",
    "family": "zzTest",
    "given": [
      "Test",
      "FHIR"
    ]
  }
],
"telecom": [
  {
    "system": "phone",
    "value": "+1 608-777-7777",
    "use": "work"
  },
  {
    "system": "email",
    "value": "fhir@email.com",
    "rank": 1
  }
],
"gender": "female",
"birthDate": "1991-08-23",
"deceasedBoolean": false,
"address": [
  {
    "use": "home",
    "text": "1979 Milky Way\r\nVERONA WI 53593\r\nUnited States of America",
    "line": [
      "1979 Milky Way"
    ],
    "city": "VERONA",
    "district": "DANE",
    "state": "WI",
    "postalCode": "53593",
    "country": "USA",
    "period": {
      "start": "2019-08-23"
    }
  }
],
"maritalStatus": {
  "text": "Married"
},
"contact": [
  {
    "relationship": [
      {
        "coding": [
          {
            "system": "urn:oid:1.2.840.114350.1.13.5325.1.7.4.827665.1000",
            "code": "17",
            "display": "Spouse"
          }
        ],
        "text": "Spouse"
      }
    ],
    "name": {
      "use": "usual",
      "text": "Zztest,Fhirgirl"
    },
    "telecom": [
      {
        "system": "phone",
```

```
          "value": "+1 608-222-2392",
          "use": "mobile",
          "rank": 1
        }
      ]
    }
  ],
  "communication": [
    {
      "language": {
        "coding": [
          {
            "system": "urn:ietf:bcp:47",
            "code": "en",
            "display": "English"
          }
        ],
        "text": "English"
      },
      "preferred": true
    }
  ],
  "generalPractitioner": [
    {
      "reference": "https://hostname/instance/api/FHIR/STU3/Practitioner/eb3d.4apzwRM33Q91Nm7wJA3",
      "display": "Doctor Doctorson, MD"
    }
  ],
  "managingOrganization": {
    "reference": "https://hostname/instance/api/FHIR/STU3/Organization/ePioZEeqCYv.F5W96swOaXA3",
    "display": "Test Healthcare Management"
  }
}
```


Change log

Epic Version | Description | Type
November 2023 | The patient-birthTime extension now appears as a child extension on the birthDate element when present, to conform with the FHIR specification. Previously, patient-birthTime was returned as a root-level extension on the Patient resource. | Breaking Change
November 2022 | Patient.contact.relationship previously only returned "C" for emergency contact or "E" for employer. When this element is "C" for emergency contact, additional elements about that contact's relationship to the patient are returned. | Non-substantive change

22.2.3 Patient.Search (STU3)

File: site/apis/22-Identification-Individuals/2-STU3/883-Patient-Search-STU3.html
Epic API ID | 883
FHIR version | STU3
Categories | Identification Individuals
API type | USCDI
A la carte | Industry-Standard Level 1 API
USCDI | Yes
Keywords | Care Team Members;Patient Demographics;First name;Last name;Middle name;initial;Suffix;Birth sex;Date of birth;Race;Ethnicity;Preferred language;Address;Phone number;Previous name
Available in inpatient and other contexts | Yes
ONC certification products | EpicCare Ambulatory Base, EpicCare Inpatient Base
ONC certification versions | November 2018
HTTP method | GET
URL template | api/FHIR/STU3/Patient?address={address}&address-city={address-city}&address-postalcode={address-postalcode}&address-state={address-state}&birthdate={birthdate}&family={family}&gender={gender}&given={given}&identifier={identifier}&own-name={own-name}&own-prefix={own-prefix}&partner-name={partner-name}&partner-prefix={partner-prefix}&telecom={telecom}&legal-sex={legal-sex}
Supports OAuth 2.0 | True
Supported user types | Backend Systems and Non-OAuth 2.0, Clinicians or Administrative Users, Patients
Performs scope validation | False
Source | https://fhir.epic.com/Specifications?api=883

Description

Patient.$match (Patient Match) (R4)

Alternative: If you need to identify a single patient record, strongly consider using Patient.$match instead. This is especially useful for backend integrations whenever sufficient patient demographics are available. Patient.Search should be used to get a list of patients matching a subset of parameters rather than matching a single patient record. Improper use of Patient.Search could lead to patient safety concerns such as reading and writing data using the wrong patient record.

This web service allows filtering or searching for patients and retrieves patient demographic information from a patient's chart for each matching patient record. See the

best practices document

for our recommended patient matching criteria.

The minimum data set requirement for a patient to be returned is configurable at each Epic organization. By default, one of the following minimum data sets is required:

* Identifier such as FHIR ID, National ID, or Identity ID (such as MRN)

* Given Name + Family Name + Birthdate

* Given Name + Family Name + Legal Sex + Phone Number/Email

A non-patient user must have appropriate security to consume search details, demographic details, and/or PCP details included in the Patient resource.

This web service respects all patient-facing security for demographic information when used in the context of a patient as the user.

If an Epic organization has configured service area restrictions, the user accessing this FHIR resource must be authorized to view patients in the target service area.

When two patients are merged, a Patient.Search on the target (surviving) patient will work normally. The source patient will return a 404 error, as we consider the source patient FHIR ID to be invalid.

Note:

If you plan to use this API on a patient-facing app, and you plan to integrate with MyChart Bedside, you should use the R4 version of this resource or later. Older versions of the Patient resource will fail in this context if the patient does not have a standard MyChart account outside of MyChart Beside.

Request parameters

Name | Type | Optional | Array | Cardinality | Description
_count | number | Optional | Yes | | Number of results per page.
_id | token | Optional | Yes | | FHIR resource IDs for the desired resources. Can be used in combination with _count and _include. All others will be ignored.
_include | string | Optional | Yes | | Used to indicate which referenced resources to include in the search bundle.
address | string | Conditional | Yes | | The patient's street address, in the format address=<address line 1>&address=<address line 2>...
address-city | string | Conditional | Yes | | The city for the patient's home address.
address-postalcode | string | Conditional | Yes | | The postal code for the patient's home address.
address-state | string | Conditional | Yes | | The state for the patient's home address.
birthdate | date | Conditional | Yes | | The patient's date of birth in the format YYYY-MM-DD
family | string | Conditional | Yes | | The patient's family (last) name. If own-name is provided as a search parameter, it is used instead of the family parameter.
gender | token | Conditional | Yes | | The patient's legal sex. If the legal-sex parameter is also included, the gender parameter is ignored.
given | string | Conditional | Yes | | The patient's given name. First and middle names ares supported.
identifier | token | Conditional | Yes | | The patient's identifier. Can be formatted as either <system>|<id> or just <id>. When specifying a <system> value as an OID, including the urn:oid: prefix is optional and is not case sensitive. When searching without a <system> value, Epic attempts lookups on all common identifier systems. Valid <systems>: MPI IDs (e.g. patient MRN). Epic first searches active MPI IDs, and falls back to a historical MPI ID search if unsuccessful. MPI ID type system values are highly configurable by the organization. MPI ID Type Descriptor MPI ID Type OID MPI ID Type HL7 ID Type Epic Care Everywhere ID CEID National Identifier US Social Security Number: 2.16.840.1.113883.4.1 UK NHS ID: 2.16.840.1.113883.2.1.4.1 Dutch BSN: 2.16.840.1.113883.2.4.6.3 or http://fhir.nl/fhir/NamingSystem/bsn Finnish National ID: 1.2.246.21 Australian Medicare Number: http://ns.electronichealth.net.au/id/medicare-number Singapore Document ID https://open.epic.com/singapore/doc-id FHIR ID http://open.epic.com/FHIR/StructureDefinition/patient-fhir-id
legal-sex | token | Conditional | Yes | | The patient's legal sex. Takes precedence over the gender search parameter.
name | string | Conditional | Yes | | Any part of the patient's name. Example formats: name=<given name> name=<family name> name=<given name>%20<family name> This parameter is ignored when any of the following discrete name parameters are also provided: family given own-name
own-name | string | Conditional | Yes | | The patient's own last name. Usage is more prevalent in locales outside of the US. If provided, this value as well as own-prefix, partner-name, and partner-prefix are used instead of the family parameter.
own-prefix | string | Conditional | Yes | | The patient's own prefix. Usage is more prevalent in locales outside of the US.
partner-name | string | Conditional | Yes | | The patient's spouse's last name. Usage is more prevalent in locales outside of the US.
partner-prefix | string | Conditional | Yes | | The patient's spouse's prefix. Usage is more prevalent in locales outside of the US.
telecom | token | Conditional | Yes | | The patient's phone number or email. Phone number validation is skipped if the first character is #. If the first character is + then the number is treated as an international number. Only one email address is supported. If multiple are supplied, only the first instance is used.

Response elements

Name | Type | Optional | Array | Cardinality | Description
Patient (STU3) | Resource
Patient (STU3).active | boolean | | | 1..1 | Whether the patient record is active.
Patient (STU3).address | Address | | Yes | 0..* | The patient's current address, as well as any previous or temporary addresses, if applicable. The patient's current address has a use code of "home". If the patient also has one or more previous addresses, each previous address has a use code of "old". The patient's temporary address has a use code of "temp".
Patient (STU3).address.city | String | | | 0..1 | The city that the patient lives in.
Patient (STU3).address.country | String | | | 0..1 | The country that the patient lives in.
Patient (STU3).address.district | String | | | 0..1 | The county that the patient lives in.
Patient (STU3).address.line | String | | Yes | 0..* | The patient's street address.
Patient (STU3).address.line.extension (houseNumber) (also: extension (houseNumber)) | Extension | | Yes | 1..* | For organizations in the Netherlands, this item represents the portion of a patient or contact's address that is their house number. URL: http://hl7.org/fhir/StructureDefinition/iso21090-ADXP-houseNumber

Patient (STU3).address.line.extension (streetName) (also: extension (streetName)) | Extension | | Yes | 0..* | For organizations in the Netherlands, this item represents the portion of a patient or contact's address that includes the name of their street. URL: http://hl7.org/fhir/StructureDefinition/iso21090-ADXP-streetName

Patient (STU3).address.period | Period | | | 0..1 | The effective dates for the address.

Patient (STU3).address.postalCode | String | | | 0..1 | The patient’s postal code.

Patient (STU3).address.state | String | | | 0..1 | The state where the patient lives.

Patient (STU3).address.text | String | | | 0..1 | The patient's full address as a string. This is formatted based on the country the address is in.

Patient (STU3).address.use | String | | | 1..1 | The type of address. The value is "home" for a permanent address, "old" for a previous permanent address, or "temp" for a temporary address. Addresses with a type of “temp” are returned as noted depending on Epic version: In the May 2025 version of Epic or later: Returned only if the Epic organization has configured temporary addresses to be visible in FHIR responses, regardless of locale. In versions prior to the May 2025 version of Epic: Always returned for organizations in Singapore. Starting in the August 2024 version of Epic, or the May 2024 version with special updates, and prior to the May 2025 version: Always returned for organizations in Norway.

Patient (STU3).birthDate | date | | | 1..1 | The patient's date of birth in the format YYYY-MM-DD

Patient (STU3).birthDate.extension (birthTime) (also: extension (birthTime)) | Extension | | | 0..* | The patient's time of birth. This extension follows the HL7 birthTime specification. Returned in August 2023 versions of Epic and earlier. URL: http://hl7.org/fhir/StructureDefinition/patient-birthTime

Patient (STU3).birthDate.extension (dataAbsentReason) (also: extension (dataAbsentReason)) | Extension | | | 0..* | Available starting with the November 2024 version of Epic. If the patient's birth date is not recorded, this extension is returned with a value of "unknown". URL: http://hl7.org/fhir/StructureDefinition/data-absent-reason

Patient (STU3).communication | BackboneElement | | Yes | 0..* | Languages used to communicate with the patient, along with an indicator of which is preferred.

Patient (STU3).communication.extension (comment) (also: extension (comment)) | Extension | | Yes | 0..1 | A comment about the patient's language proficiency. This extension is returned only for organizations in the Netherlands. URL: http://nictiz.nl/fhir/StructureDefinition/Comment

Patient (STU3).communication.extension (patient-proficiency) (also: extension (patient-proficiency)) | Extension | | Yes | 0..* | Container extension that holds details about the patient's language proficiency. Contains two child extensions which indicate the type of language proficiency and the level of that proficiency. This extension is returned only for organizations in the Netherlands. URL: http://nictiz.nl/fhir/StructureDefinition/patient-proficiency

Patient (STU3).communication.extension (patient-proficiency).extension (v3-LanguageAbilityMode) (also: extension (v3-LanguageAbilityMode)) | Extension | | Yes | 0..1 | Patient's language proficiency type. This is a valueCoding wherein the following code and display values are supported: RSP - Received spoken ESP - Expressed spoken RWR - Received written System value of http://terminology.hl7.org/CodeSystem/v3-LanguageAbilityMode URL: type

Patient (STU3).communication.extension (patient-proficiency).extension (v3-LanguageAbilityProficiency) (also: extension (v3-LanguageAbilityProficiency)) | Extension | | Yes | 0..1 | Patient's language proficiency level. This is a valueCoding wherein the following code and display values are supported: E - Excellent G - Good F - Fair P - Poor System value of http://terminology.hl7.org/CodeSystem/v3-LanguageAbilityProficiency URL: level

Patient (STU3).communication.language | CodeableConcept | | | 1..1 | The patient's general language, onsite care language, and spoken language.

Patient (STU3).communication.preferred | boolean | | | 0..1 | Whether the language is the patient's preferred language.

Patient (STU3).communication.preferred.extension (patient-preferenceType) (also: extension (patient-preferenceType)) | Extension | | Yes | 0..1 | The preferred mode of communication for the patient’s preferred language. This can be either verbal or written. Returned starting in the May 2025 version of Epic. Returned with system http://hl7.org/fhir/language-preference-type. URL: http://hl7.org/fhir/StructureDefinition/patient-preferenceType

Patient (STU3).contact | BackboneElement | | Yes | 0..* | Details for the patient's contacts. Patient contacts include any documented family members, emergency contacts, care givers, acquaintances, and employers.

Patient (STU3).contact.address | Address | | | 1..1 | The contact address. For responses to a patient-facing application, this element is not returned for contacts linked to a patient record. For organizations in the Netherlands, this element represents an nl-core-address value.

Patient (STU3).contact.name | HumanName | | | 1..1 | The contact's name. The system determines this from the contact's linked patient record if available. For contacts linked to a patient record, only the patient's first name is returned in patient context. For organizations in the Netherlands, this element represents an nl-core-humanname value.

Patient (STU3).contact.name.extension (humannameAssemblyOrder) (also: extension (humannameAssemblyOrder)) | Extension | | Yes | 0..* | This extension is populated only for organizations in the Netherlands. Name order for the contact. One of the following values: * NL1-Own Name * NL2-Partner Name * NL3-Partner Name followed by Maiden Name * NL4-Own Name followed by Partner Name URL: http://hl7.org/fhir/StructureDefinition/humanname-assembly-order

Patient (STU3).contact.organization | Reference | | | 0..1 | An Organization reference that represents the patient's employer. Returned when contact.relationship.code is E.

Patient (STU3).contact.period | Period | | | 1..1 | The contact period.

Patient (STU3).contact.relationship | CodeableConcept | | Yes | 1..* | The contact’s relationship to the patient. This element can return multiple values. It will always return one or more Epic category values for the contact’s relationship to the patient. In addition, it can return one or more of the following: For organizations in the Netherlands, either a Relationship (RelatieCodelijst) code system value or a role (RolCodelijst) code system value. For all other organizations, can return either a code system value – such as “C” (emergency contact) or “E” (employer) – or a RoleClass code system value – such as “GUARD” or “AGNT”.

Patient (STU3).contact.telecom | ContactPoint | | Yes | 0..* | Telephone numbers and email address for the contact. For responses to a patient-facing application, this element is not returned for contacts linked to a patient record. For organizations in the Netherlands, this element represents an nl-core-contactpoint value.

Patient (STU3).contact.telecom.rank | Int64 | | | 0..1 | The priority for permanent phone numbers or emails. 1 indicates the highest priority phone number, 2 indicates the second priority, and so on. Starting in the May 2025 version of Epic, rank is returned for the phone numbers of patient contacts.

Patient (STU3).contact.telecom.system | String | | | 0..1 | The type of telecom. Potential values are: email phone

Patient (STU3).contact.telecom.use | String | | | 0..1 | If the telecom entry is a phone number, possible values are: home mobile work

Patient (STU3).contact.telecom.value | String | | | 1..1 | Value of the telecom method. Can be an email address or phone number.

Patient (STU3).deceasedBoolean | boolean | | | 0..1 | Whether the patient is deceased.

Patient (STU3).deceasedDateTime | dateTime | | | 0..1 | The date and time of death.

Patient (STU3).extension (birth sex) (also: extension (birth sex)) | Extension | | Yes | 0..* | The patient's sex assigned at birth. This element is not returned for organizations in the Netherlands. URL: http://hl7.org/fhir/us/core/StructureDefinition/us-core-birthsex

Patient (STU3).extension (birth-location) (also: extension (birth-location)) | Extension | | Yes | 0..1 | A reference to a newborn’s birth facility. URL: http://open.epic.com/FHIR/StructureDefinition/extension/birth-location

Patient (STU3).extension (gender-identity) (also: extension (gender-identity)) | Extension | | Yes | 0..1 | The patient's gender identity. URL: http://hl7.org/fhir/StructureDefinition/patient-genderIdentity

Patient (STU3).extension (legal-sex) (also: extension (legal-sex)) | Extension | | Yes | 0..1 | The patient's legal sex. URL: http://open.epic.com/FHIR/StructureDefinition/extension/legal-sex

Patient (STU3).extension (patient-preferred-provider-language) (also: extension (patient-preferred-provider-language)) | Extension | | Yes | 1..1 | The patient's preferred provider language, used for scheduling. URL: http://open.epic.com/FHIR/STU3/StructureDefinition/patient-preferred-provider-language

Patient (STU3).extension (patient-preferred-provider-sex) (also: extension (patient-preferred-provider-sex)) | Extension | | Yes | 0..1 | The patient's preferred provider sex, used for scheduling. URL: http://open.epic.com/FHIR/STU3/StructureDefinition/patient-preferred-provider-sex

Patient (STU3).extension (patient-race) (also: extension (patient-race)) | Extension | | Yes | 0..1 | The patient's race. This is returned for organizations in Singapore URL: http://open.epic.com/FHIR/StructureDefinition/extension/patient-race

Patient (STU3).extension (patient-type) (also: extension (patient-type)) | Extension | | Yes | 0..* | The type of patient, such as Confidential or Employee. URL: http://open.epic.com/FHIR/StructureDefinition/extension/patient-type

Patient (STU3).extension (patient-unmerge-source) (also: extension (patient-unmerge-source)) | Extension | | Yes | 0..* | This extension contains a collection of extensions that represent the metadata for a patient record unmerge from the perspective of the source patient. If the patient is involved as the source patient in multiple unmerges, this set of extensions is returned for each unmerge event. URL: https://open.epic.com/FHIR/StructureDefinition/patient-unmerge-source

Patient (STU3).extension (patient-unmerge-source).extension (patient-merge-unmerge-instant) (also: extension (patient-merge-unmerge-instant)) | Extension | | Yes | 0..1 | The instant the patient merge or unmerge event occurred. URL: https://open.epic.com/FHIR/StructureDefinition/patient-merge-unmerge-instant

Patient (STU3).extension (patient-unmerge-source).extension (patient-unmerge-current-target-reference) (also: extension (patient-unmerge-current-target-reference)) | Extension | | Yes | 0..1 | A reference to the current FHIR ID of the unmerge event's target patient. URL: https://open.epic.com/FHIR/StructureDefinition/patient-unmerge-current-target-reference

Patient (STU3).extension (patient-unmerge-source).extension (patient-unmerge-old-target-reference) (also: extension (patient-unmerge-old-target-reference)) | Extension | | Yes | 0..1 | A reference to the FHIR ID of the unmerge event's target patient at the time of the merge. URL: https://open.epic.com/FHIR/StructureDefinition/patient-unmerge-old-target-reference

Patient (STU3).extension (patient-unmerge-source).extension (patient-unmerge-original-source-reference) (also: extension (patient-unmerge-original-source-reference)) | Extension | | Yes | 0..1 | A reference to the current FHIR ID of the unmerge event's source patient. URL: https://open.epic.com/FHIR/StructureDefinition/patient-unmerge-original-source-reference

Patient (STU3).extension (patient-unmerge-source).extension (patient-unmerge-reference-old) (also: extension (patient-unmerge-reference-old)) | Extension | | Yes | 0..1 | A reference to the FHIR ID of the unmerge event's source patient at the time of the merge. URL: https://open.epic.com/FHIR/StructureDefinition/patient-unmerge-reference-old

Patient (STU3).extension (patient-unmerge-target) (also: extension (patient-unmerge-target)) | Extension | | Yes | 0..* | This extension contains a collection of extensions that represent the metadata for a patient record unmerge from the perspective of the target patient. If the patient is involved as the target patient in multiple unmerges, this set of extensions is returned for each unmerge event. URL: https://open.epic.com/FHIR/StructureDefinition/patient-unmerge-target

Patient (STU3).extension (patient-unmerge-target).extension (patient-merge-unmerge-instant) (also: extension (patient-merge-unmerge-instant)) | Extension | | Yes | 0..1 | The instant the patient merge or unmerge event occurred. URL: https://open.epic.com/FHIR/StructureDefinition/patient-merge-unmerge-instant

Patient (STU3).extension (patient-unmerge-target).extension (patient-unmerge-old-target-reference) (also: extension (patient-unmerge-old-target-reference)) | Extension | | Yes | 0..1 | A reference to the FHIR ID of the unmerge event's target patient at the time of the merge. URL: https://open.epic.com/FHIR/StructureDefinition/patient-unmerge-old-target-reference

Patient (STU3).extension (patient-unmerge-target).extension (patient-unmerge-original-source-reference) (also: extension (patient-unmerge-original-source-reference)) | Extension | | Yes | 0..1 | A reference to the current FHIR ID of the unmerge event's source patient. URL: https://open.epic.com/FHIR/StructureDefinition/patient-unmerge-original-source-reference

Patient (STU3).extension (patient-unmerge-target).extension (patient-unmerge-reference-old) (also: extension (patient-unmerge-reference-old)) | Extension | | Yes | 0..1 | A reference to the FHIR ID of the unmerge event's source patient at the time of the merge. URL: https://open.epic.com/FHIR/StructureDefinition/patient-unmerge-reference-old

Patient (STU3).extension (sex-for-clinical-use) (also: extension (sex-for-clinical-use)) | Extension | | Yes | 0..1 | The patient's sex for clinical decision making. This is an Epic-calculated value. If the patient's sex, gender, and clinical information indicate the patient is not unambiguously a cisgender male or female, the extension is not included. URL: http://open.epic.com/FHIR/StructureDefinition/extension/sex-for-clinical-use

Patient (STU3).extension (us-core-ethnicity) (also: extension (us-core-ethnicity)) | Extension | | Yes | 0..1 | The patient's ethnicity. This element is not returned for organizations in the Netherlands. URL: http://hl7.org/fhir/us/core/StructureDefinition/us-core-ethnicity

Patient (STU3).extension (us-core-race) (also: extension (us-core-race)) | Extension | | Yes | 0..1 | The patient's race. This element is not returned for organizations in the Netherlands. URL: http://hl7.org/fhir/us/core/StructureDefinition/us-core-race

Patient (STU3).gender | code | | | 1..1 | The patient's legal sex.

Patient (STU3).generalPractitioner | Reference | | Yes | 0..* | The patient's primary care provider (PCP). Reference to a Practitioner resource.

Patient (STU3).id | id | | | 1..1 | The Patient FHIR ID.

Patient (STU3).identifier | Identifier | | Yes | 0..* | The patient's identifiers. Includes the following: Epic MPI IDs (e.g. MRNs) Epic database IDs National IDs FHIR ID Care Everywhere ID For organizations in Singapore, the patient’s document ID, type, and expiry date.

Patient (STU3).identifier.system | String | | | 1..1 | Epic Identity IDs (e.g. Patient MRN) Identity ID OID Identity ID HL7 Assigning Authority as the "Text" value. Epic MyChart IDs MyChart login OID Epic Care Everywhere ID CEID Epic internal ID OID generated for Epic patient records National Identifier US Social Security Number: 2.16.840.1.113883.4.1 UK NHS ID: 2.16.840.1.113883.2.1.4.1 Dutch BSN: 2.16.840.1.113883.2.4.6.3 or http://fhir.nl/fhir/NamingSystem/bsn Finnish National ID: 1.2.246.21 Australian Medicare Number: http://ns.electronichealth.net.au/id/medicare-number FHIR ID STU3 and up: http://open.epic.com/FHIR/StructureDefinition/patient-fhir-id DSTU2: http://open.epic.com/FHIR/StructureDefinition/patient-dstu2-fhir-id

Patient (STU3).identifier.type | CodeableConcept | | | 0..1 | The patient's identifier type.

Patient (STU3).identifier.value | String | | | 1..1 | The patient's ID.

Patient (STU3).identifier.value.extension (rendered-value) (also: extension (rendered-value)) | Extension | | Yes | 0..1 | Contains the patient's masked national ID if the organization masks national identifiers. URL: http://hl7.org/fhir/StructureDefinition/rendered-value

Patient (STU3).link | BackboneElement | | Yes | 0..* | Contains links to other patient records if the patient record was merged. Starting in February 2024, the 30 most recent merge events are returned instead of all merge events.

Patient (STU3).link.extension (patient-merge-unmerge-instant) (also: extension (patient-merge-unmerge-instant)) | Extension | | Yes | 0..1 | The instant the patient merge or unmerge event occurred. URL: https://open.epic.com/FHIR/StructureDefinition/patient-merge-unmerge-instant

Patient (STU3).link.other | Reference | | | 0..1 | A reference to the Patient resource that was merged into the Patient resource currently being viewed.

Patient (STU3).link.other.reference | String | | | 0..1 | A reference to the Patient resource that this Patient replaces.

Patient (STU3).link.type | code | | | 1..1 | The type of link between Patient resources. This is always set to "replaces".

Patient (STU3).managingOrganization | Reference | | | 0..1 | The patient's primary service area. Reference to an Organization resource.

Patient (STU3).maritalStatus | CodeableConcept | | | 0..1 | The patient's marital status.

Patient (STU3).meta | Meta | | | 1..1 | Metadata about the resource.

Patient (STU3).meta.profile | String | | Yes | 0..1 | Only returned for organizations in the Netherlands. This element shows that this API conforms to the profile connected to the following canonical url: http://fhir.nl/fhir/StructureDefinition/nl-core-patient

Patient (STU3).meta.security | Coding | | Yes | 0..* | The patient's unverified status. Available starting in the May 2024 version of Epic, as well as the February 2024 and November 2023 with special updates. This is used to track new patient records that might need to be reconciled against existing records in the system. The element is not returned for verified patients. Unverified patients always return the value PATRPT (Patient Reported) along with one of the following values: UNCERTAIN (Uncertain Reliability) UNRELIABLE (Unreliable)

Patient (STU3).multipleBirthInteger | integer | | | 0..1 | The patient's birth order.

Patient (STU3).name | HumanName | | Yes | 1..* | The patient's name. This element includes both the patient's "official" name, which returns the patient's full name, and the patient's "usual" name, which returns the patient's preferred name. If the patient does not have a preferred name defined, the "usual" name also returns the patient's full name.

Patient (STU3).name.extension (humanNameAssemblyOrder) (also: extension (humanNameAssemblyOrder)) | Extension | | Yes | 0..* | This extension is populated only for organizations in the Netherlands. Name order for the contact. One of the following values: * NL1-Own Name * NL2-Partner Name * NL3-Partner Name followed by Maiden Name * NL4-Own Name followed by Partner Name URL: http://hl7.org/fhir/StructureDefinition/humanname-assembly-order

Patient (STU3).name.family | String | | | 1..1 | The patient's family (last) name. Can contain a data-absent-reason extension with a value of "unknown" if the patient has an alias that cannot be returned as discrete elements or if the patient's preferred name replaces their full name.

Patient (STU3).name.family.extension (data-absent-reason) (also: extension (data-absent-reason)) | Extension | | Yes | 0..1 | Returned as "unknown" for patients without family names.

Patient (STU3).name.family.extension (humanNameOwnName) (also: extension (humanNameOwnName)) | Extension | | Yes | 0..1 | The portion of a patient's family name derived from the patient's own name.

Patient (STU3).name.family.extension (humanNameOwnPrefix) (also: extension (humanNameOwnPrefix)) | Extension | | Yes | 0..1 | The prefix portion of a patient's family name derived from the patient's own surname.

Patient (STU3).name.family.extension (humanNamePartnerName) (also: extension (humanNamePartnerName)) | Extension | | Yes | 0..1 | The portion of a patient's family name derived from the patient's partner's name.

Patient (STU3).name.family.extension (humanNamePartnerPrefix) (also: extension (humanNamePartnerPrefix)) | Extension | | Yes | 0..1 | The prefix portion of a patient's family name derived from the patient's partner's surname.

Patient (STU3).name.given | String | | Yes | 1..* | The patient's given name. Can include first and middle names.

Patient (STU3).name.given.extension (namePartQualifier) (also: extension (namePartQualifier)) | Extension | | Yes | 1..* | This extension is returned if initials or a preferred name are present. The entity qualifier extension code is IN for initials and CL for preferred name.

Patient (STU3).name.prefix | String | | Yes | 0..1 | The patient's name prefix.

Patient (STU3).name.suffix | String | | Yes | 0..* | The patient's name suffix. Acquired as a title due to academic, legal, employment or nobility status, etc.

Patient (STU3).name.text | String | | | 1..1 | The patient's full name as a string.

Patient (STU3).name.use | String | | | 1..1 | The purpose of the name. Can be "official", "usual", or "old".

Patient (STU3).telecom | ContactPoint | | Yes | 0..* | Telephone numbers and email addresses for the patient, along with their use (home or work for example) and their preferred rank (which to contact first, second, third, etc).

Patient (STU3).telecom.rank | Int64 | | | 0..1 | The priority for permanent phone numbers or emails. 1 indicates the highest priority phone number, 2 indicates the second priority, and so on. The preferred has a rank of 1. Additional emails have a null rank.

Patient (STU3).telecom.system | String | | | 1..1 | The type of telecom. Potential values are: email phone fax url pager sms other

Patient (STU3).telecom.use | String | | | 0..1 | If the telecom entry is a phone number, possible values are: home mobile work temp old Use is not returned for emails.

Patient (STU3).telecom.value | String | | | 1..1 | Value of the telecom method. Can be an email address or phone number.

Sample request

```
GET https://hostname/instance/api/FHIR/STU3/Patient?address=123 Main St.&address-city=Madison&address-
    postalcode=53703&address-state=Wisconsin&family=Patient&gender=Female&given=Test&telecom=608-123-4567
```

Sample response


```
{
  "resourceType": "Bundle",
  "type": "searchset",
  "total": 1,
  "link": [
    {
      "relation": "self",
      "url": "https://hostname/instance/api/FHIR/STU3/Patient?address=123%20Main%20St.&address-city=Madison&address-
    postalcode=53703&address-state=Wisconsin&family=Patient&gender=Female&given=Test&telecom=608-123-4567"
    }
  ],
  "entry": [
    {
      "link": [
        {
          "relation": "self",
          "url": "https://hostname/instance/api/FHIR/STU3/Patient/eJzlzKe3KPzAV5TtkxmNivQ3"
        }
      ],
      "fullUrl": "https://hostname/instance/api/FHIR/STU3/Patient/eJzlzKe3KPzAV5TtkxmNivQ3",
      "resource": {
        "resourceType": "Patient",
        "id": "eJzlzKe3KPzAV5TtkxmNivQ3",
        "extension": [
          {
            "valueCodeableConcept": {
              "coding": [
                {
                  "system": "urn:oid:1.2.840.114350.1.13.0.1.7.10.698084.130.657370.19999000",
```

```
            "code": "female",
            "display": "female"
          }
        ],
        "text": "Female"
      },
      "url": "http://open.epic.com/FHIR/StructureDefinition/extension/legal-sex"
    },
    {
      "valueCodeableConcept": {
        "coding": [
          {
            "system": "http://hl7.org/fhir/gender-identity",
            "code": "transgender-female",
            "display": "transgender-female"
          }
        ],
        "text": "Transgender Female"
      },
      "url": "http://hl7.org/fhir/StructureDefinition/patient-genderIdentity"
    },
    {
      "valueCode": "M",
      "url": "http://hl7.org/fhir/us/core/StructureDefinition/us-core-birthsex"
    },
    {
      "extension": [
        {
          "valueCoding": {
            "system": "http://hl7.org/fhir/us/core/ValueSet/omb-race-category",
            "code": "UNK",
            "display": "Unknown"
          },
          "url": "ombCategory"
        },
        {
          "valueString": "Unknown",
          "url": "text"
        }
      ],
      "url": "http://hl7.org/fhir/us/core/StructureDefinition/us-core-race"
    },
    {
      "extension": [
        {
          "valueCoding": {
            "system": "http://hl7.org/fhir/us/core/ValueSet/omb-ethnicity-category",
            "code": "2186-5",
            "display": "Not Hispanic or Latino"
          },
          "url": "ombCategory"
        },
        {
          "valueString": "Not Hispanic or Latino",
          "url": "text"
        }
      ],
      "url": "http://hl7.org/fhir/us/core/StructureDefinition/us-core-ethnicity"
    }
  ],
  "identifier": [
    {
      "use": "usual",
      "type": {
        "text": "CEID"
      },
      "system": "urn:epic:apporchard.curprod",
      "value": "AO17CLS4HWQQDHN"
    },
    {
      "use": "usual",
      "type": {
        "text": "EPIC"
      },
      "system": "urn:oid:1.2.840.114350.1.13.0.1.7.5.737384.0",
      "value": "E2731"
    },
    {
      "use": "usual",
      "type": {
        "text": "EXTERNAL"
      },
      "system": "urn:oid:1.2.840.114350.1.13.0.1.7.2.698084",
      "value": "Z4572"
    },
    {
      "use": "usual",
      "type": {
        "text": "FHIR"
```

```
    },
    "system": "http://open.epic.com/FHIR/StructureDefinition/patient-dstu2-fhir-id",
    "value": "TJgJ7wgwgI32QvHx3YBhDm4egjwdyhmAhfdtE7bQsPYYB"
  },
  {
    "use": "usual",
    "type": {
      "text": "FHIR STU3"
    },
    "system": "http://open.epic.com/FHIR/StructureDefinition/patient-fhir-id",
    "value": "eJzlzKe3KPzAV5TtkxmNivQ3"
  },
  {
    "use": "usual",
    "type": {
      "text": "INTERNAL"
    },
    "system": "urn:oid:1.2.840.114350.1.13.0.1.7.2.698084",
    "value": "     Z4572"
  },
  {
    "use": "usual",
    "type": {
      "text": "MRN"
    },
    "system": "urn:oid:1.2.840.114350.1.13.0.1.7.5.737384.14",
    "value": "202497"
  },
  {
    "use": "usual",
    "type": {
      "text": "PATIENTLOGIN"
    },
    "system": "urn:oid:1.2.840.114350.1.13.0.1.7.3.878082.110",
    "value": "PATIENTTEST"
  },
  {
    "use": "usual",
    "type": {
      "text": "WPRINTERNAL"
    },
    "system": "urn:oid:1.2.840.114350.1.13.0.1.7.2.878082",
    "value": "16"
  },
  {
    "use": "usual",
    "system": "https://open.epic.com/FHIR/StructureDefinition/PayerMemberId",
    "value": "230030346"
  },
  {
    "use": "usual",
    "system": "https://open.epic.com/FHIR/StructureDefinition/PayerMemberId",
    "value": "987654321A"
  },
  {
    "extension": [
      {
        "valueString": "999-99-9999",
        "url": "http://hl7.org/fhir/StructureDefinition/rendered-value"
      }
    ],
    "use": "usual",
    "system": "urn:oid:2.16.840.1.113883.4.1",
    "value": "999-99-9999"
  }
],
"active": true,
"name": [
  {
    "use": "official",
    "text": "Test Patient",
    "family": "Patient",
    "given": [
      "Test"
    ]
  },
  {
    "use": "usual",
    "text": "Ali Hackett",
    "family": "Hackett",
    "given": [
      "Ali"
    ],
    "_given": [
      {
        "extension": [
          {
            "valueCode": "CL",
            "url": "http://hl7.org/fhir/StructureDefinition/iso21090-EN-qualifier"
```

```
                }
              ]
            }
          ]
        }
      ],
      "telecom": [
        {
          "system": "phone",
          "value": "+1 608-123-4567",
          "use": "home",
          "rank": 1
        }
      ],
      "gender": "female",
      "birthDate": "1987-01-15",
      "deceasedBoolean": false,
      "address": [
        {
          "use": "home",
          "text": "1325 Main St.\r\nMadison WI 53703\r\nUnited States of America",
          "line": [
            "1325 Main St."
          ],
          "city": "Madison",
          "district": "DANE",
          "state": "WI",
          "postalCode": "53703",
          "country": "US",
          "period": {
            "start": "2023-10-06"
          }
        }
      ],
      "maritalStatus": {
        "text": "Significant Other"
      },
      "communication": [
        {
          "language": {
            "coding": [
              {
                "system": "urn:ietf:bcp:47",
                "code": "en",
                "display": "English"
              }
            ],
            "text": "English"
          },
          "preferred": true
        }
      ],
      "generalPractitioner": [
        {
          "reference": "https://hostname/instance/api/FHIR/STU3/Practitioner/eM5CWtq15N0WJeuCet5bJlQ3",
          "display": "Physician Family Medicine, MD"
        },
        {
          "reference": "https://hostname/instance/api/FHIR/STU3/Practitioner/ef9TegF2nfECi-0Skirbvpg3",
          "display": "Physician One Cardiology, MD"
        }
      ],
      "managingOrganization": {
        "reference": "https://hostname/instance/api/FHIR/STU3/Organization/enRyWnSP963FYDpoks4NHOA3",
        "display": "Epic Hospital System"
      }
    },
    "search": {
      "mode": "match"
    }
  }
 ]
}
```


Change log

Epic Version	Description	Type
November 2023	The patient-birthTime extension now appears as a child extension on the birthDate element when present, to conform with the FHIR specification. Previously, patient-birthTime was returned as a root-level extension on the Patient resource.	Breaking Change
May 2023	Allow searching for patient records using only demographics the associated user has security to access in the response.	Breaking change
November 2022	Patient.contact.relationship previously only returned "C" for emergency contact or "E" for employer. When this element is "C" for emergency contact, additional elements about that contact's relationship to the patient are returned.	Non-substantive change
May 2022	Hidden or soft-deleted records are no longer returned in Search results	Breaking change

22.2.4 Practitioner.Read (STU3)

File: site/apis/22-Identification-Individuals/2-STU3/499-Practitioner-Read-STU3.html
Epic API ID | 499
FHIR version | STU3
Categories | Identification Individuals
API type | USCDI
A la carte | Industry-Standard Level 1 API
USCDI | Yes
Available in inpatient and other contexts | Yes
ONC certification products | EpicCare Ambulatory Base, EpicCare Inpatient Base
ONC certification versions | Epic 2018
HTTP method | GET
URL template | api/FHIR/STU3/Practitioner/{ID}
Supports OAuth 2.0 | True
Supported user types | Backend Systems and Non-OAuth 2.0, Clinicians or Administrative Users, Patients
Performs scope validation | False
Source | https://fhir.epic.com/Specifications?api=499

Description

You can use the read interaction to look up a Practitioner resource by a constant server ID. The read interaction allows you to store only the server ID, and with a single request, retrieve the most up-to-date role information on a Practitioner. Read interactions typically begin with a client having previously established a relationship.

Request parameters

Name | Type | Optional | Array | Cardinality | Description
ID | String | False | | | The ID of a practitioner.

Response elements

Name | Type | Optional | Array | Cardinality | Description
Practitioner | Practitioner | True | | | An instance of the STU3 Practitioner resource.
Practitioner.active | Boolean | True | | | Whether the practitioner's record is in active use.
Practitioner.communication | CodeableConcept | True | Yes | | A language the practitioner is able to use in patient communication.
Practitioner.gender | String | True | | | The gender of the practitioner.
Practitioner.identifier | Identifier | True | Yes | | The practitioner or user ID. The Epic provider ID will be returned with identifier system urn:oid:1.2.840.114350.1.13.xxx.y.7.2.836982. The Epic user ID will be returned with the identifier system of urn:oid:1.2.840.114350.1.13.xxx.y.7.2.697780. The xxx value will be replaced with an organization-specific sub-identifier and the y value will change depending on whether the environment is Epic-owned, a non-production environment, or a production environment. For Epic provider-based or user-based practitioners, this service returns both the Epic provider ID and the Epic user ID associated with the practitioner when there is a link between the provider and user records. Starting in November 2024, for practitioners with a Tax Identification Number (TIN), this service returns an identifier type of TIN and the ID of the TIN. For external practitioners with a National Provider Identifier (NPI), this service returns an identifier type of NPI and the ID of the NPI. If the identifier is set to one of the following ID types and system OIDs, the corresponding system URL is returned in Identifier.system: ID Type System OID System URL returned in Identifier.system UZI 2.16.528.1.1007.3.1 http://fhir.nl/fhir/NamingSystem/uzi-nr-pers AGB 2.16.840.1.113883.2.4.6.1 http://fhir.nl/fhir/NamingSystem/agb-z BIG 2.16.528.1.1007.5.1 http://fhir.nl/fhir/NamingSystem/big NPI SER 1.2.840.114350.1.13.xxx.y.7.5.737384 http://hl7.org/fhir/sid/us-npi TIN 2.16.840.1.113883.4.4
ID Type | System OID | System URL returned in Identifier.system
UZI | 2.16.528.1.1007.3.1 | http://fhir.nl/fhir/NamingSystem/uzi-nr-pers
AGB | 2.16.840.1.113883.2.4.6.1 | http://fhir.nl/fhir/NamingSystem/agb-z
BIG | 2.16.528.1.1007.5.1 | http://fhir.nl/fhir/NamingSystem/big
NPI SER | 1.2.840.114350.1.13.xxx.y.7.5.737384 | http://hl7.org/fhir/sid/us-npi
TIN | 2.16.840.1.113883.4.4
Practitioner.meta | Meta | True | | | The document metadata.
Practitioner.meta.profile | String | True | | | Available in Netherlands environments only. This environment shows that this API conforms to the profile connected to the following canonical url: http://fhir.nl/fhir/StructureDefinition/nl-core-practitioner
Practitioner.name | HumanName | True | Yes | | The name of the practitioner, including all prefixes and suffixes available.
Practitioner.photo | Attachment | True | Yes | | Contains parameters related to the practitioner photo.
Practitioner.photo.url | String | True | | | The URI or URL where the photo can be found. If this is a BLOB key, we will return a URL to a binary resource.
Practitioner.qualification | Qualification | True | Yes | | The practitioner's qualifications.
Practitioner.telecom | ContactPoint | True | Yes | | Returned only for Epic user-based practitioners. Not returned in a MyChart context.
Practitioner.telecom.system | String | False | | | Always set to "email"
Practitioner.telecom.value | String | True | | | The email for the Epic user-based practitioner. Obtained from the user record.

Sample request

```
https://hostname/instance/api/FHIR/STU3/Practitioner/eBaNzWMT6Meuve0uFYmxLSA3
```

Sample response

```
<Practitioner xmlns="http://hl7.org/fhir">
  <id value="eBaNzWMT6Meuve0uFYmxLSA3"/>
  <identifier>
    <use value="usual"/>
    <system value="urn:oid:1.2.840.114350.1.13.861.1.7.5.737384.650"/>
    <value value="DAEFJ39F"/>
```

```
  </identifier>
  <identifier>
    <use value="usual"/>
    <type>
      <text value="Zorgmail"/>
    </type>
    <system value="urn:oid:1.2.840.114350.1.13.861.1.7.5.737384.864"/>
    <value value="8DRLGIJRG"/>
  </identifier>
  <identifier>
    <use value="usual"/>
    <type>
      <text value="GPSER"/>
    </type>
    <system value="urn:oid:1.2.840.114350.1.13.861.1.7.5.737384.917"/>
    <value value="HOLIDAY, DOC"/>
  </identifier>
  <identifier>
    <use value="usual"/>
    <type>
      <text value="AJHPROV"/>
    </type>
    <system value="AJHPROV"/>
    <value value="3456"/>
  </identifier>
  <Active value="true"/>
  <name>
    <use value="usual"/>
    <text value="Holiday, Doc"/>
    <family value="Holiday"/>
    <given value="Doc"/>
  </name>
  <communication>
    <coding>
      <system value="urn:oid:2.16.840.1.113883.6.99"/>
      <code value="en"/>
      <display value="English"/>
    </coding>
    <text value="English"/>
  </communication>
  <communication>
    <coding>
      <system value="urn:oid:2.16.840.1.113883.6.99"/>
      <code value="fr"/>
      <display value="French"/>
    </coding>
    <text value="French"/>
  </communication>
  <communication>
    <coding>
      <system value="urn:oid:2.16.840.1.113883.6.99"/>
      <code value="km"/>
      <display value="Central Khmer"/>
    </coding>
    <text value="Central Khmer"/>
  </communication>
</Practitioner>
```

22.2.5 Practitioner.Search (STU3)

File: site/apis/22-Identification-Individuals/2-STU3/858-Practitioner-Search-STU3.html
Epic API ID | 858
FHIR version | STU3
Categories | Identification Individuals
API type | USCDI
A la carte | Industry-Standard Level 1 API
USCDI | Yes
Available in inpatient and other contexts | Yes
ONC certification products | EpicCare Ambulatory Base, EpicCare Inpatient Base
ONC certification versions | August 2018
HTTP method | GET
URL template | api/FHIR/STU3/Practitioner?address={address}&address-city={address-city}&address-postalcode={address-postalcode}&address-state={address-state}&family={family}&given={given}&identifier={identifier}&name={name}
Supports OAuth 2.0 | True
Supported user types | Backend Systems and Non-OAuth 2.0, Clinicians or Administrative Users, Patients
Performs scope validation | False
Source | https://fhir.epic.com/Specifications?api=858

Description

The FHIR Practitioner resource is defined as a person who is directly or indirectly involved in the provisioning of healthcare. The Practitioner resource can provide information about a healthcare provider, such as activities, responsibilities, demographics, and other administrative information.

Request parameters

Name | Type | Optional | Array | Cardinality | Description
address | String | True | | | The free-text address.
address-city | String | True | | | The city specified in the address. City cannot be specified without state or ZIP code.
address-postalcode | String | True | | | A ZIP code specified in the address.
address-state | String | True | | | A state specified in the address.
family | String | False | | | A portion of the family name. If name or identifier is provided, this is not required.
given | String | True | | | A portion of the given name. If Given is provided, Family must also be provided.
identifier | String | False | | | A Practitioner's identifier, such as NPI. Should be formatted as <system>|<id>. For example, identifier=SERID|608999. MPI IDs are a valid system and any of the following can be used: MPI ID Type Descriptor MPI ID Type OID MPI ID Type HL7 ID Type This parameter is ignored if the _id parameter is provided.
name | String | False | | | Free text that can match either Family or Given (or both). If Family or Identifier is provided, this is not required.

Response elements

Name | Type | Optional | Array | Cardinality | Description
Bundle | Bundle | False | | | Resource bundle. For more information, refer to the FHIR specification.
Bundle.entry | Entry | False | Yes | | A single entry in the resource bundle.
Bundle.entry.resource | ResourceContainer | False | | | A single resource returned as part of this bundle.
Bundle.entry.resource.Practitioner | Practitioner | False | | | An instance of the STU3 Practitioner resource.
Bundle.entry.resource.Practitioner.active | Boolean | True | | | Whether the practitioner's record is active.
Bundle.entry.resource.Practitioner.communication | CodeableConcept | True | Yes | | A language that the practitioner can use in patient communication.
Bundle.entry.resource.Practitioner.gender | String | True | | | The practitioner's gender.
Bundle.entry.resource.Practitioner.meta | Meta | True | | | The document metadata.
Bundle.entry.resource.Practitioner.meta.profile | String | True | | | Available in Netherlands environments only. This environment shows that this API conforms to the profile connected to the following canonical url: http://fhir.nl/fhir/StructureDefinition/nl-core-practitioner
Bundle.entry.resource.Practitioner.name | HumanName | True | Yes | | The name associated with the practitioner.
Bundle.entry.resource.Practitioner.photo | Attachment | True | Yes | | Contains parameters related to the practitioner photo.
Bundle.entry.resource.Practitioner.photo.url | String | False | | | The URI or URL where the photo can be found. If this is a BLOB key, we will return a URL to a binary resource.
Bundle.entry.resource.Practitioner.qualification | Qualification | True | Yes | | The practitioner's qualifications.
Bundle.entry.resource.Practitioner.telecom | ContactPoint | True | Yes | | Returned only for Epic user-based practitioners. Not returned in a MyChart context.
Bundle.entry.resource.Practitioner.telecom.system | String | False | | | Always set to "email"
Bundle.entry.resource.Practitioner.telecom.value | String | True | | | The email for the Epic user-based practitioner. Obtained from the user record.
Bundle.identifier | Identifier | True | | | here's what the old version looked like for reference: The practitioner or user ID. The Epic provider ID will be returned with identifier system urn:oid:1.2.840.114350.1.13.xxx.y.7.2.836982. The Epic user ID will be returned with the identifier system of urn:oid:1.2.840.114350.1.13.xxx.y.7.2.697780. The xxx value will be replaced with an organization-specific sub-identifier and the y value will change depending on whether the environment is Epic-owned, a non-production environment, or a production environment. For Epic provider-based or user-based practitioners, this service returns both the Epic provider ID and the Epic user ID associated with the practitioner when there is a link between the provider and user records. Starting in November 2024, for practitioners with a Tax Identification Number (TIN), this service returns an identifier type of TIN and the ID of the TIN. For external practitioners with a National Provider Identifier (NPI), this service returns an identifier type of NPI and the ID of the NPI. If the identifier is set to one of the following ID types and system OIDs, the corresponding system URL is returned in Identifier.system: ID Type System OID System URL returned in Identifier.system UZI 2.16.528.1.1007.3.1 http://fhir.nl/fhir/NamingSystem/uzi-nr-pers AGB 2.16.840.1.113883.2.4.6.1 http://fhir.nl/fhir/NamingSystem/agb-z BIG 2.16.528.1.1007.5.1 http://fhir.nl/fhir/NamingSystem/big NPI SER 1.2.840.114350.1.13.xxx.y.7.5.737384 http://hl7.org/fhir/sid/us-npi TIN 2.16.840.1.113883.4.4
ID Type | System OID | System URL returned in Identifier.system
UZI | 2.16.528.1.1007.3.1 | http://fhir.nl/fhir/NamingSystem/uzi-nr-pers
AGB | 2.16.840.1.113883.2.4.6.1 | http://fhir.nl/fhir/NamingSystem/agb-z
BIG | 2.16.528.1.1007.5.1 | http://fhir.nl/fhir/NamingSystem/big
NPI SER | 1.2.840.114350.1.13.xxx.y.7.5.737384 | http://hl7.org/fhir/sid/us-npi
TIN | 2.16.840.1.113883.4.4

Sample request

```
https://hostname/instance/api/FHIR/STU3/Practitioner?family=hornick&address-postalcode=53715
```

Sample response

```
<Bundle xmlns="http://hl7.org/fhir">
  <type value="searchset"/>
  <total value="3"/>
  <link>
    <relation value="self"/>
    <url value="https://hostname/instance/api/FHIR/STU3/Practitioner?family=williams&amp;given=e"/>
  </link>
  <entry>
    <link>
      <relation value="self"/>
      <url value="https://hostname/instance/api/FHIR/STU3/Practitioner/eikKqRciSdRl9-4axpkvW4g3"/>
    </link>
    <fullUrl value="https://hostname/instance/api/FHIR/STU3/Practitioner/eikKqRciSdRl9-4axpkvW4g3"/>
    <resource>
      <Practitioner>
        <id value="eikKqRciSdRl9-4axpkvW4g3"/>
        <identifier>
```

```
        <use value="usual"/>
        <type>
          <text value="GPSER"/>
        </type>
        <system value="urn:oid:1.2.840.114350.1.13.861.1.7.5.737384.917"/>
        <value value="WILLIAMS, EM"/>
      </identifier>
      <active value="true"/>
      <name>
        <use value="usual"/>
        <text value="Emily Williams"/>
        <family value="Williams"/>
        <given value="Emily"/>
      </name>
    </Practitioner>
  </resource>
  <search>
    <mode value="match"/>
  </search>
</entry>
<entry>
  <link>
    <relation value="self"/>
    <url value="https://hostname/instance/api/FHIR/STU3/Practitioner/edw0sycOoJ7dTNbQ1Mx3jIw3"/>
  </link>
  <fullUrl value="https://hostname/instance/api/FHIR/STU3/Practitioner/edw0sycOoJ7dTNbQ1Mx3jIw3"/>
  <resource>
    <Practitioner>
      <id value="edw0sycOoJ7dTNbQ1Mx3jIw3"/>
      <active value="true"/>
      <name>
        <use value="usual"/>
        <text value="Epic User, MD"/>
        <family value="Williams"/>
        <given value="Everett"/>
        <given value="L"/>
      </name>
    </Practitioner>
  </resource>
  <search>
    <mode value="match"/>
  </search>
</entry>
<entry>
  <link>
    <relation value="self"/>
    <url value="https://hostname/instance/api/FHIR/STU3/Practitioner/eyXRBabyOnbdV1-ZrNtn5iA3"/>
  </link>
  <fullUrl value="https://hostname/instance/api/FHIR/STU3/Practitioner/eyXRBabyOnbdV1-ZrNtn5iA3"/>
  <resource>
    <Practitioner>
      <id value="eyXRBabyOnbdV1-ZrNtn5iA3"/>
      <identifier>
        <use value="usual"/>
        <type>
          <text value="NPI"/>
        </type>
        <system value="urn:oid:1.2.840.114350.1.13.861.1.7.5.737384.136"/>
        <value value="1528322153"/>
      </identifier>
      <active value="true"/>
      <name>
        <use value="usual"/>
        <text value="CRETARO WILLIAMS, ELAINE"/>
        <family value="Cretaro Williams"/>
        <given value="Elaine"/>
      </name>
    </Practitioner>
  </resource>
  <search>
    <mode value="match"/>
  </search>
</entry>
</Bundle>
```


Change log

Version | Description | Type
May 2022 | Hidden or soft-deleted records are no longer returned in Search results | Breaking change

22.2.6 PractitionerRole.Read (STU3)

File: site/apis/22-Identification-Individuals/2-STU3/859-PractitionerRole-Read-STU3.html
Epic API ID | 859
FHIR version | STU3
Categories | Identification Individuals

API type | USCDI
A la carte | Industry-Standard Level 1 API
USCDI | Yes
Available in inpatient and other contexts | Yes
ONC certification products | EpicCare Ambulatory Base, EpicCare Inpatient Base
ONC certification versions | August 2018
HTTP method | GET
URL template | api/FHIR/STU3/PractitionerRole/{ID}
Supports OAuth 2.0 | True
Supported user types | Backend Systems and Non-OAuth 2.0, Clinicians or Administrative Users, Patients
Performs scope validation | False
Source | https://fhir.epic.com/Specifications?api=859

Description

The PractitionerRole resource defines location and types of services (roles) that a practitioner provides for an organization. It references the Practitioner resource, and there can be multiple PractitionerRoles per practitioner.

Request parameters

Name | Type | Optional | Array | Cardinality | Description
ID | String | False | | | The read interaction enables the look up of a PractitionerRole resource by a constant server ID.

Response elements

Name | Type | Optional | Array | Cardinality | Description
PractitionerRole | PractitionerRole | True | | | An instance of the STU3 PractitionerRole resource.
PractitionerRole.active | Boolean | True | | | Whether the unique address is active.
PractitionerRole.code | CodeableConcept | True | Yes | | The Epic provider role. Starting in the May 2024 version of Epic, also includes and the SNOMED practitioner code.
PractitionerRole.location | Reference | True | Yes | | Reference to the Location resource.
PractitionerRole.meta | Meta | True | | | The document metadata.
PractitionerRole.meta.profile | String | True | | | Available in Netherlands environments only. This environment shows that this API conforms to the profile connected to the following canonical url: http://fhir.nl/fhir/StructureDefinition/nl-core-practitionerrole
PractitionerRole.organization | Reference | True | | | The provider's place of service. This element is only supported for organizations in the Netherlands.
PractitionerRole.practitioner | Reference | True | | | Reference to the Practitioner resource.
PractitionerRole.specialty | CodeableConcept | True | Yes | | The provider specialty.
PractitionerRole.telecom | ContactPoint | True | Yes | | Contact information specific to the unique address.

Sample request

```
https://hostname/instance/api/FHIR/STU3/PractitionerRole/e1mDtDYSVrqp5V9CkMEgDlg3
```

Sample response


```
{
  "resourceType": "PractitionerRole",
  "id": "ecJemvYsDotATCnQwlwkAHroAms-SqS3MkpZWzrzpofs3",
  "active": true,
  "practitioner": {
    "reference": " https://hostname/instance/api/FHIR/STU3/Practitioner/epxGqVzHww9Mm9gfQ7DE-KA3",
    "display": "Seeger, Marty"
  },
  "code": [
    {
      "coding": [
        {
          "system": "urn:oid:1.2.840.114350.1.13.5325.1.7.10.836982.1040",
          "code": "1",
          "display": "Physician"
        },
        {
          "system": "http://snomed.info/sct",
          "code": "309343006",
          "display": "Physician (occupation)"
        }
      ],
      "text": "Physician"
    }
  ],
  "specialty": [
    {
      "coding": [
        {
          "system": "urn:oid:1.2.840.114350.1.72.1.7.7.10.688867.4160",
          "code": "82",
          "display": "Pediatrics"
        }
      ],
      "text": "Pediatrics"
```

```
    }
  ],
  "location": [
    {
      "reference": " https://hostname/instance/api/FHIR/STU3/Location/ecNk5JqJK8lFxayMfbkvTFNQNg.9VRZeJM0psLFWaNbc3"
    }
  ],
  "telecom": [
    {
      "system": "phone",
      "value": "608-444-5566",
      "use": "work"
    }
  ]
}
```


22.2.7 PractitionerRole.Search (STU3)

File: site/apis/22-Identification-Individuals/2-STU3/885-PractitionerRole-Search-STU3.html
Epic API ID | 885
FHIR version | STU3
Categories | Identification Individuals
API type | USCDI
A la carte | Industry-Standard Level 1 API
USCDI | Yes
Available in inpatient and other contexts | Yes
ONC certification products | EpicCare Ambulatory Base, EpicCare Inpatient Base
ONC certification versions | November 2018
HTTP method | GET
URL template | /api/FHIR/STU3/PractitionerRole?email={email}&identifier={identifier}&location={location}&organization={organization}&phone={phone}&practitioner={practitioner}&role={role}&specialty={specialty}&telecom={telecom}
Supports OAuth 2.0 | True
Supported user types | Backend Systems and Non-OAuth 2.0, Clinicians or Administrative Users, Patients
Performs scope validation | False
Source | https://fhir.epic.com/Specifications?api=885

Description

The FHIR PractitionerRole resource consists of a location and types of services that practitioners can provide for an organization. When using the Search operation, an identifier, practitioner, organization, location, or specialty parameter is required.

Starting in the August 2019 version of Epic, this resource accepts multiple comma-delimited values for practitioner, location, or organization.

Request parameters

Name | Type | Optional | Array | Cardinality | Description
email | String | True | | | Value in an email contact.
identifier | String | An identifier, practitioner, organization, location, or specialty parameter is required. | | | A practitioner's identifier. A successful identifier search comprises of a token that is a URN:OID: + the code system, and a code in the format identifier=code system|code.
location | String | An identifier, practitioner, organization, location, or specialty parameter is required. | | | One of the locations at which this practitioner provides care.
organization | String | An identifier, practitioner, organization, location, or specialty parameter is required. | | | The organization that the practitioner represents or acts on behalf of.
phone | String | True | | | A value in a phone contact.
practitioner | String | An identifier, practitioner, organization, location, or specialty parameter is required. | | | A practitioner that can provide the defined services for the organization.
role | String | True | | | The role a practitioner can perform at an organization.
specialty | String | An identifier, practitioner, organization, location, or specialty parameter is required. | | | The practitioner's specialty at an organization.
telecom | String | True | | | The value in any kind of contact.

Response elements

Name | Type | Optional | Array | Cardinality | Description
Bundle | Bundle | True | | | Resource bundle. For more information, refer to the FHIR specification.
Bundle.entry | Entry | True | Yes | | A single entry in the resource bundle.
Bundle.entry.resource | ResourceContainer | True | | | A single resource returned as part of this bundle.
Bundle.entry.resource.PractitionerRole | PractitionerRole | True | | | An instance of the STU3 PractitionerRole resource.
Bundle.entry.resource.PractitionerRole.active | Boolean | True | | | Whether the unique address is active.
Bundle.entry.resource.PractitionerRole.code | CodeableConcept | True | Yes | | The Epic provider role. Starting in the May 2024 version of Epic, also includes and the SNOMED practitioner code.
Bundle.entry.resource.PractitionerRole.endpoint | Reference | True | Yes | | Reference to the endpoint.
Bundle.entry.resource.PractitionerRole.location | Reference | True | Yes | | A location containing address information for the provider. This element isn't returned in a patient-facing context.
Bundle.entry.resource.PractitionerRole.meta | Meta | True | | | The document metadata.

Bundle.entry.resource.PractitionerRole.meta.profile | String | True | | | Available in Netherlands environments only. This environment shows that this API conforms to the profile connected to the following canonical url: http://fhir.nl/fhir/StructureDefinition/nl-core-practitionerrole

Bundle.entry.resource.PractitionerRole.organization | Reference | True | | | The provider's place of service. This element is only supported for organizations in the Netherlands.

Bundle.entry.resource.PractitionerRole.practitioner | Reference | True | | | Reference to the Practitioner resource.

Bundle.entry.resource.PractitionerRole.specialty | CodeableConcept | True | Yes | | The provider specialty.

Bundle.entry.resource.PractitionerRole.telecom | ContactPoint | True | Yes | | Contact information specific to the unique address.

Sample request

```
https://hostname/instance/api/FHIR/STU3/PractitionerRole?location=ey.Zm.yki8dw5uM1UNVX9.g3&role=urn:oid:1.2.840.114350.1
    .13.861.1.7.10.836982.1040|6
```

Sample response


```
{
 "resourceType": "Bundle",
 "type": "searchset",
 "total": 1,
 "link": [
 {
 "relation": "self",
 "url": " https://hostname/instance/api/FHIR/STU3/PractitionerRole?practitioner=epxGqVzHww9Mm9gfQ7DE-KA3"
 }
 ],
 "entry": [
 {
 "link": [
 {
 "relation": "self",
 "url": " https://hostname/instance/api/FHIR/STU3/PractitionerRole/ecJemvYsDotATCnQwlwkAHroAms-SqS3MkpZWzrzpofs3"
 }
 ],
 "fullUrl": " https://hostname/instance/api/FHIR/STU3/PractitionerRole/ecJemvYsDotATCnQwlwkAHroAms-SqS3MkpZWzrzpofs3",
 "resource": {
 "resourceType": "PractitionerRole",
 "id": "ecJemvYsDotATCnQwlwkAHroAms-SqS3MkpZWzrzpofs3",
 "active": true,
 "practitioner": {
 "reference": https://hostname/instance/api/FHIR/STU3/Practitioner/epxGqVzHww9Mm9gfQ7DE-KA3",
 "display": "Seeger, Marty"
 },
 "code": [
 {
 "coding": [
 {
 "system": "urn:oid:1.2.840.114350.1.13.5325.1.7.10.836982.1040",
 "code": "1",
 "display": "Physician"
 },
 {
 "system": "http://snomed.info/sct",
 "code": "309343006",
 "display": "Physician (occupation)"
 }
 ],
 "text": "Physician"
 }
 ],
 "specialty": [
 {
 "coding": [
 {
 "system": "urn:oid:1.2.840.114350.1.72.1.7.7.10.688867.4160",
 "code": "82",
 "display": "Pediatrics"
 }
 ],
 "text": "Pediatrics"
 }
 ],
 "location": [
 {
 "reference": " https://hostname/instance/api/FHIR/STU3/Location/ecNk5JqJK8lFxayMfbkvTFNQNg.9VRZeJM0psLFWaNbc3"
 }
 ],
 "telecom": [
 {
 "system": "phone",
 "value": "608-444-5566",
 "use": "work"
 }
 ]
 },
 "search": {
 "mode": "match"
 }
```

```
 }
 ]
}
```

22.3 Identification Individuals: DSTU2

File: site/apis/22-Identification-Individuals/3-DSTU2/index.html

* Patient.Read (DSTU2)
* Patient.Search (DSTU2)
* Practitioner.Read (DSTU2)
* Practitioner.Search (DSTU2)

22.3.1 Patient.Read (DSTU2)

File: site/apis/22-Identification-Individuals/3-DSTU2/29-Patient-Read-DSTU2.html
Epic API ID | 29
FHIR version | DSTU2
Categories | Identification Individuals
API type | USCDI
A la carte | Industry-Standard Level 1 API
USCDI | Yes
Keywords | Care Team Members;Patient Demographics;First name;Last name;Middle name;initial;Suffix;Birth sex;Date of birth;Race;Ethnicity;Preferred language;Address;Phone number;Previous name
Available in inpatient and other contexts | Yes
ONC certification products | EpicCare Ambulatory Base, EpicCare Inpatient Base
ONC certification versions | Epic 2015
HTTP method | GET
URL template | api/FHIR/DSTU2/Patient/{ID}
Supports OAuth 2.0 | True
Supported user types | Backend Systems and Non-OAuth 2.0, Clinicians or Administrative Users, Patients
Performs scope validation | False
Source | https://fhir.epic.com/Specifications?api=29

Description

The FHIR Patient resource defines demographics, care providers, and other administrative information about a person receiving care at a health organization. The Patient resource can be thought of as the starting point for many different client application workflows; often, a workflow will begin with a patient query and selection, and the server ID will be used to drive additional queries for diagnostic and care-related information.

The Patient resource corresponds to the following Common Clinical Data Set (CCDS) Elements: Patient Name, DOB, Race, Ethnicity, Preferred Language, and Care Team.

The read interaction enables the look up of a Patient resource by a constant server ID. The read interaction allows clients to store only the server ID, and with a single request, retrieve the most up-to-date demographics on a patient. Read interactions typically begin with a client having previously established a relationship, often through querying for patients through the search interaction.

When two patients are merged, doing a Patient.Read on the target patient will work normally. The source patient will return a 301 redirect to the target patient.

Note: If you plan to use this API on a patient-facing app, and you plan to integrate with MyChart Bedside, you should use the R4 version of this resource or later. Older versions of the Patient resource will fail in this context if the patient does not have a standard MyChart account outside of MyChart Beside.”.

Supported Patient Extensions

In addition to the Standard FHIR Patient resource, Epic supports the following patient-level extensions:

US Core Race Coded value of the Patient's documented race using the HL7 Version 3 Race Code System.

```
{"url": "http://hl7.org/fhir/StructureDefinition/us-core-race", "valueCodeableConcept": {"text": "Asian", "coding":
[{"system": "2.16.840.1.113883.5.104", "code": "2028-9", "display": "Asian"}] }}
```

US Core Ethnicity Coded value of the Patient's documented ethnicity using the HL7 Version 3 Ethnicity Code System.

```
{"url": "http://hl7.org/fhir/StructureDefinition/us-core-ethnicity", "valueCodeableConcept": {"text": "Not Hispanic
 or Latino", "coding": [{"system": "2.16.840.1.113883.5.50", "code": "2186-5", "display": "Not Hispanic or Latino"}]
 }}
```

US Core Birth Sex Coded value of the Patient's documented birth sex using the HL7 Version 3 Administrative Gender Code System, as required by ONC regulation. Note: if no birth sex is documented, a value will not be returned.

```
{"url": "http://hl7.org/fhir/StructureDefinition/us-core-birth-sex", "valueCodeableConcept": { "text": "Male",
 "coding": [{"system": "http://hl7.org/fhir/v3/AdministrativeGender", "code": "M", "display": "Male"}] }}
```

Remarks

FHIR Patient resources can be retrieved via a Read or Search interaction and can be consumed as either XML or JSON. Searches most often utilize the Identity Duplicate Checking infrastructure. A released IDC record will allow this web service to perform searches. A search may return as many as 100 potential matches.

Request parameters

Name | Type | Optional | Array | Cardinality | Description
ID | String | False | | | The Patient's FHIR ID.

Response elements

Name | Type | Optional | Array | Cardinality | Description
Patient | Patient | False | | | A single Patient FHIR resource.
Patient.active | Boolean | False | | | Whether the patient record is active.
Patient.address | Address | False | Yes | | Addresses for the patient.
Patient.birthDate | DateTime | True | | | The patient's date of birth in the format YYYY-MM-DD.
Patient.careProvider | ReferencedResource | True | Yes | | PCP of type general for the patient. Reference to a Practitioner resource.
Patient.communication | Communication | False | Yes | | A list of languages used to communicate with the patient, along with an indicator of which is preferred.
Patient.communication.language | CodeableConcept | False | | | The patient's general language, onsite care language, and spoken language. The codes come from the two character ISO 639-1 code list.
Patient.communication.preferred | Boolean | True | | | Whether the language is the patient's preferred language.
Patient.deceasedBoolean | Boolean | deceasedDateTime is returned whenever available. If not available, deceasedBoolean will be returned. | | | Whether the patient is deceased.
Patient.deceasedDateTime | DateTime | deceasedDateTime is returned whenever available. If not available, deceasedBoolean will be returned. | | | The date and time at which the patient was deceased.
Patient.gender | String | False | | | The patient's legal sex.
Patient.id | String | False | | | The Patient's FHIR ID.
Patient.identifier | Identifier | False | Yes | | Identifiers and assigning authorities associated with a patient. These are of the format <OID>|<value>.
Patient.maritalStatus | CodeableConcept | False | | | The patient’s marital status.
Patient.name | HumanName | False | Yes | | The patient's name. Starting in the May 2020 version of Epic, this element includes both the patient's "official" name, which is the patient's legal name, and the patient's "usual" name, which is the patient's preferred name. If the patient does not have a preferred name defined in your system, the "usual" name also holds the patient's legal name. In a patient-facing context, this web service always shows the patient's preferred name, unless a user has the security point 'Only Show Legal Name'. In February 2020 and earlier, this element returns only the patient's legal name with a use code of "usual".
Patient.name.family | String | False | | | The patient's family (last) name.
Patient.name.given | String | False | | | The patient's given name. May include first and middle names.
Patient.name.prefix | String | True | | | The patient's name prefix.
Patient.name.suffix | String | True | | | The patient's name suffix. Acquired as a title due to academic, legal, employment or nobility status, etc.
Patient.name.text | String | False | | | The patient's full name as a string.
Patient.name.use | String | False | | | The purpose of the name. May be "legal" or "usual". See the name parameter for full details on use.
Patient.telecom | ContactPoint | True | Yes | | Telephone numbers and email addresses for the patient, along with their use (i.e. home, work, etc.)
Patient.telecom.system | String | False | | | The type of telecom. Potential values are: email phone
Patient.telecom.use | String | True | | | If the telecom entry is a phone number, possible values are: home mobile work
Patient.telecom.value | String | False | | | Value of the telecom method. May be an email address or phone number.
Patient.extension (also: us-core-birth-sex) | ExtensionElement | True | Yes | | The patient's sex assigned at birth.
Patient.extension (also: us-core-ethnicity) | ExtensionElement | True | Yes | | The patient's ethnicity. This element is not returned for organizations in the Netherlands.
Patient.extension (also: us-core-race) | ExtensionElement | False | Yes | | The patient's race. This element is not returned for organizations in the Netherlands.

Sample request

```
http://hostname/instance/api/FHIR/DSTU2/Patient/T0hY1cLFnO.TSydQJmt.mnZlFY0oi78v5x9iaxuyWOmUB
```

Sample response

```
<Patient xmlns="http://hl7.org/fhir">
  <birthDate value="1991-01-13T00:00:00"/>
  <active value="true"/>
  <gender value="female"/>
  <deceasedBoolean value="false"/>
  <id value="T0hY1cLFnO.TSydQJmt.mneK9ATxa9uysPCZFPmn2KygB"/>
  <careProvider>
    <display value="John Doe, MD"/>
    <reference value="https://hostname/instance/api/FHIR/DSTU2/Practitioner/TiOmkdUgh7pJl0-mpSeeFtQB"/>
  </careProvider>
  <name>
    <use value="usual"/>
    <family value="Doe"/>
    <given value="John"/>
    <given value="Condition"/>
  </name>
  <identifier>
    <use value="usual"/>
    <system value="urn:oid:1.2.840.114350.1.1"/>
    <value value="104897"/>
  </identifier>
  <address>
```

```
    <use value="home"/>
    <line value="1979 Milky Way"/>
    <city value="VERONA"/>
    <state value="WI"/>
    <postalCode value="53593"/>
    <country value="USA"/>
  </address>
  <telecom>
    <system value="phone"/>
    <value value="608-555-5555"/>
    <use value="home"/>
  </telecom>
  <telecom>
    <system value="phone"/>
    <value value="608-222-2222"/>
    <use value="work"/>
  </telecom>
  <telecom>
    <system value="email"/>
    <value value="condition@fhir.com"/>
  </telecom>
  <maritalStatus>
    <text value="Single"/>
    <coding>
      <system value="http://hl7.org/fhir/vs/marital-status"/>
      <code value="S"/>
      <display value="Never Married"/>
    </coding>
  </maritalStatus>
  <communication>
    <preferred value="true"/>
    <language>
      <text value="English"/>
      <coding>
        <system value="urn:oid:2.16.840.1.113883.6.99"/>
        <code value="en"/>
        <display value="English"/>
      </coding>
    </language>
  </communication>
  <extension>
    <url value="http://hl7.org/fhir/StructureDefinition/us-core-race"/>
    <valueCodeableConcept>
      <text value="Other Race"/>
      <coding>
        <system value="2.16.840.1.113883.5.104"/>
        <code value="2131-1"/>
        <display value="Other Race"/>
      </coding>
    </valueCodeableConcept>
  </extension>
  <extension>
    <url value="http://hl7.org/fhir/StructureDefinition/us-core-ethnicity"/>
    <valueCodeableConcept>
      <text value="Unknown"/>
      <coding>
        <system value="2.16.840.1.113883.5.50"/>
        <code value="UNK"/>
        <display value="Unknown"/>
      </coding>
    </valueCodeableConcept>
  </extension>
</Patient>
```

22.3.2 Patient.Search (DSTU2)

File: site/apis/22-Identification-Individuals/3-DSTU2/30-Patient-Search-DSTU2.html
Epic API ID | 30
FHIR version | DSTU2
Categories | Identification Individuals
API type | USCDI
A la carte | Industry-Standard Level 1 API
USCDI | Yes
Keywords | Care Team Members;Patient Demographics;First name;Last name;Middle name;initial;Suffix;Birth sex;Date of birth;Race;Ethnicity;Preferred language;Address;Phone number;Previous name
Available in inpatient and other contexts | Yes
ONC certification products | EpicCare Ambulatory Base, EpicCare Inpatient Base
ONC certification versions | Epic 2015
HTTP method | GET
URL template | api/FHIR/DSTU2/Patient?_id={_id}&identifier={identifier}&family={family}&given={given}&birthdate={birthdate}&address={address}&gender={gender}&telecom={telecom}
Supports OAuth 2.0 | True
Supported user types | Backend Systems and Non-OAuth 2.0, Clinicians or Administrative Users, Patients
Performs scope validation | False

Source | https://fhir.epic.com/Specifications?api=30

Description

The FHIR Patient resource defines demographics, care providers, and other administrative information about a person receiving care at a health organization. The Patient resource can be thought of as the starting point for many different client application workflows; often, a workflow will begin with a patient query and selection, and the server ID will be used to drive additional queries for diagnostic and care-related information.

The Patient resource corresponds to the following Common Clinical Data Set (CCDS) Elements: Patient Name, DOB, Race, Ethnicity, Preferred Language, and Care Team.

The search interaction enables the client to query for patients based on a specified set of demographics information. The Patient Search endpoint allows clients to establish an identifier for a patient without previously receiving unique identification from the server for the patient.

Epic's support of the Patient resource only allows retrieving the most up-to-date demographics information. Previous demographic information cannot be queried.

When two patients are merged, you can provide either the source or target patient FHIR ID, and the search with return whatever data is on the merged patient. This includes searching Patient using _id.

Note: If you plan to use this API on a patient-facing app, and you plan to integrate with MyChart Bedside, you should use the R4 version of this resource or later. Older versions of the Patient resource will fail in this context if the patient does not have a standard MyChart account outside of MyChart Beside.”.

Epic's patient search implementation only returns patients with strong demographics matches. Most query parameters will return no results unless used in concert with more specific demographic information. Health systems have the flexibility to define which demographic property combinations are used when searching for patients in their system. The allowed search parameter combinations available in the sandbox may differ from those allowed by health systems.

Supported Patient Extensions

In addition to the Standard FHIR Patient resource, Epic supports the following patient-level extensions:

US Core Race Coded value of the Patient's documented race using the HL7 Version 3 Race Code System.

```
{"url": "http://hl7.org/fhir/StructureDefinition/us-core-race", "valueCodeableConcept": {"text": "Asian", "coding":
[{"system": "2.16.840.1.113883.5.104", "code": "2028-9", "display": "Asian"}] }}
```

US Core Ethnicity Coded value of the Patient's documented ethnicity using the HL7 Version 3 Ethnicity Code System.

```
{"url": "http://hl7.org/fhir/StructureDefinition/us-core-ethnicity", "valueCodeableConcept": {"text": "Not Hispanic
 or Latino", "coding": [{"system": "2.16.840.1.113883.5.50", "code": "2186-5", "display": "Not Hispanic or Latino"}]
 }}
```

US Core Birth Sex Coded value of the Patient's documented birth sex using the HL7 Version 3 Administrative Gender Code System, as required by ONC regulation. If no birth sex is documented, a value will not be returned.

```
{"url": "http://hl7.org/fhir/StructureDefinition/us-core-birth-sex", "valueCodeableConcept": { "text": "Male",
 "coding": [{"system": "http://hl7.org/fhir/v3/AdministrativeGender", "code": "M", "display": "Male"}] }}
```

Remarks

FHIR Patient resources can be retrieved via a Read or Search interaction and can be consumed as either XML or JSON. Searches most often utilize the Identity Duplicate Checking infrastructure. A released IDC record will allow this web service to perform searches. A search may return as many as 100 potential matches.

Request parameters

Name | Type | Optional | Array | Cardinality | Description

_id | String | If provided, all other input parameters will be ignored. One of the following input combinations must be provided at minimum: _id (aka FHIR ID) identifier in the form {IDType}|{ID}, which includes SSN Given name, family name, and birthdate Given name, family name, gender, and communication (phone number/email) | | | The Patient's FHIR ID.

address | String | One of the following input combinations must be provided at minimum: _id (aka FHIR ID) identifier in the form {IDType}|{ID}, which includes SSN Given name, family name, and birthdate Given name, family name, gender, and communication (phone number/email) | | | Addresses for the patient.

birthdate | String | One of the following input combinations must be provided at minimum: _id (aka FHIR ID) identifier in the form {IDType}|{ID}, which includes SSN Given name, family name, and birthdate Given name, family name, gender, and communication (phone number/email) | | | The patient's date of birth in the format YYYY-MM-DD.

family | String | One of the following input combinations must be provided at minimum: _id (aka FHIR ID) identifier in the form {IDType}|{ID}, which includes SSN Given name, family name, and birthdate Given name, family name, gender, and communication (phone number/email) | | | The patient's family (last) name.

gender | String | One of the following input combinations must be provided at minimum: _id (aka FHIR ID) identifier in the form {IDType}|{ID}, which includes SSN Given name, family name, and birthdate Given name, family name, gender, and communication (phone number/email) | | | The patient's legal sex.

given | String | One of the following input combinations must be provided at minimum: _id (aka FHIR ID) identifier in the form {IDType}|{ID}, which includes SSN Given name, family name, and birthdate Given name, family name, gender, and communication (phone number/email) | | | The patient's given name. May include first and middle names.

identifier | String | One of the following input combinations must be provided at minimum: id (aka FHIR ID) identifier in the form {IDType}|{ID}, which includes SSN Given name, family name, and birthdate Given name, family name, gender, and communication (phone number/email) | | | Identifiers and assigning authorities associated with a patient. These are of the format <OID>|<value>.

telecom | String | One of the following input combinations must be provided at minimum: _id (aka FHIR ID) identifier in the form {IDType}|{ID}, which includes SSN Given name, family name, and birthdate Given name, family name, gender, and communication (phone number/email) | | | Telephone numbers and email addresses for the patient, along with their use (i.e. home, work, etc.)

Response elements

Name | Type | Optional | Array | Cardinality | Description

Bundle | Bundle | False | | | Resource bundle. For more information, refer to the FHIR specification.

Bundle.entry | Entry | False | Yes | | A single entry in the resource bundle.

Bundle.entry.resource | Resource | False | | | A single resource returned as part of this bundle.

Bundle.entry.resource.Patient | Patient | False | | | A single Patient FHIR resource.

Bundle.entry.resource.Patient.active | Boolean | False | | | Whether the patient record is active.

Bundle.entry.resource.Patient.address | Address | False | Yes | | Addresses for the patient.

Bundle.entry.resource.Patient.birthDate | DateTime | False | | | The patient's date of birth in the format YYYY-MM-DD.

Bundle.entry.resource.Patient.careProvider | ReferencedResource | True | Yes | | PCP of type general for the patient. Reference to a Practitioner resource.

Bundle.entry.resource.Patient.communication | Communication | False | Yes | | A list of languages used to communicate with the patient, along with an indicator of which is preferred.

Bundle.entry.resource.Patient.communication.language | CodeableConcept | False | | | The patient's general language, onsite care language, and spoken language.

Bundle.entry.resource.Patient.communication.preferred | Boolean | True | | | Whether the language is the patient's preferred language.

Bundle.entry.resource.Patient.deceasedBoolean | Boolean | deceasedDateTime is returned whenever available. If not available, deceasedBoolean will be returned. | | | Whether the patient is deceased.

Bundle.entry.resource.Patient.deceasedDateTime | DateTime | deceasedDateTime is returned whenever available. If not available, deceasedBoolean will be returned. | | | The date and time at which the patient was deceased.

Bundle.entry.resource.Patient.gender | String | False | | | The patient's legal sex.

Bundle.entry.resource.Patient.id | String | False | | | The Patient's FHIR ID.

Bundle.entry.resource.Patient.identifier | Identifier | False | Yes | | Identifiers and assigning authorities associated with a patient. These are of the format <OID>|<value>.

Bundle.entry.resource.Patient.maritalStatus | CodeableConcept | False | | | The patient’s marital status.

Bundle.entry.resource.Patient.name | HumanName | False | Yes | | The patient's name. Starting in the May 2020 version of Epic, this element includes both the patient's "official" name, which is the patient's legal name, and the patient's "usual" name, which is the patient's preferred name. If the patient does not have a preferred name defined in your system, the "usual" name also holds the patient's legal name. In a patient-facing context, this web service always shows the patient's preferred name, unless a user has the security point 'Only Show Legal Name'. In February 2020 and earlier, this element returns only the patient's legal name with a use code of "usual".

Bundle.entry.resource.Patient.name.family | String | False | | | The patient's family (last) name.

Bundle.entry.resource.Patient.name.given | String | False | | | The patient's given name. May include first and middle names.

Bundle.entry.resource.Patient.name.prefix | String | True | | | The patient's name prefix.

Bundle.entry.resource.Patient.name.suffix | String | True | | | The patient's name suffix.

Bundle.entry.resource.Patient.name.text | String | False | | | The patient's full name as a string.

Bundle.entry.resource.Patient.name.use | String | False | | | The purpose of the name. May be "legal" or "usual". See the name parameter for full details on use.

Bundle.entry.resource.Patient.telecom | ContactPoint | True | Yes | | Telephone numbers and email addresses for the patient, along with their use (i.e. home, work, etc.)

Bundle.entry.resource.Patient.telecom.system | String | False | | | The type of telecom. Potential values are: email phone

Bundle.entry.resource.Patient.telecom.use | String | True | | | If the telecom entry is a phone number, possible values are: home mobile work

Bundle.entry.resource.Patient.telecom.value | String | False | | | Value of the telecom method. May be an email address or phone number.

Bundle.entry.resource.Patient.extension (also: us-core-birth-sex) | ExtensionElement | True | Yes | | The patient's sex assigned at birth.

Bundle.entry.resource.Patient.extension (also: us-core-ethnicity) | ExtensionElement | True | Yes | | The patient's ethnicity. This element is not returned for organizations in the Netherlands.

Bundle.entry.resource.Patient.extension (also: us-core-race) | ExtensionElement | True | Yes | | The patient's race. This element is not returned for organizations in the Netherlands.

Sample request

```
http://hostname/instance/api/FHIR/DSTU2/Patient?Family=Doe&Given=John
```

Sample response

```
<Bundle xmlns="http://hl7.org/fhir">
  <type value="searchset"/>
  <total value="17"/>
  <link>
    <relation value="self"/>
    <url value="https://hostname/instance/api/FHIR/DSTU2/Patient?Family=Doe&amp;Given=John"/>
  </link>
  <entry>
    <fullUrl value="https://hostname/instance/api/FHIR/DSTU2/Patient/TB2fiHITxwOAD8ZYflxSqWbko892TkWkXFaCTS-1nKBQB"/>
    <link>
      <relation value="self"/>
      <url value="https://hostname/instance/api/FHIR/DSTU2/Patient/TB2fiHITxwOAD8ZYflxSqWbko892TkWkXFaCTS-1nKBQB"/>
    </link>
    <resource>
      <Patient>
        <birthDate value="1991-12-31T00:00:00"/>
        <active value="true"/>
        <gender value="female"/>
        <deceasedBoolean value="false"/>
        <id value="TB2fiHITxwOAD8ZYflxSqWbko892TkWkXFaCTS-1nKBQB"/>
```

```
    <careProvider>
      <display value="John Doe, MD"/>
      <reference value="https://hostname/instance/api/FHIR/DSTU2/Practitioner/TiOmkdUgh7pJl0-mpSeeFtQB"/>
    </careProvider>
    <name>
      <use value="usual"/>
      <family value="Doe"/>
      <given value="John"/>
      <given value="FHIR"/>
      <prefix value="MS."/>
    </name>
    <identifier>
      <use value="usual"/>
      <system value="urn:oid:1.2.840.114350.1.1"/>
      <value value="104800"/>
    </identifier>
    <address>
      <use value="home"/>
      <line value="101 Main St"/>
      <line value="Apt 320"/>
      <city value="VERONA"/>
      <state value="WI"/>
      <postalCode value="53593"/>
      <country value="USA"/>
    </address>
    <telecom>
      <system value="phone"/>
      <value value="608-777-7777"/>
      <use value="home"/>
    </telecom>
    <telecom>
      <system value="phone"/>
      <value value="608-888-8888"/>
      <use value="work"/>
    </telecom>
    <telecom>
      <system value="phone"/>
      <value value="608-444-4444"/>
      <use value="mobile"/>
    </telecom>
    <telecom>
      <system value="email"/>
      <value value="fhirDoe@email.com"/>
    </telecom>
    <maritalStatus>
      <text value="Married"/>
      <coding>
        <system value="http://hl7.org/fhir/vs/marital-status"/>
        <code value="M"/>
        <display value="Married"/>
      </coding>
    </maritalStatus>
    <communication>
      <preferred value="true"/>
      <language>
        <text value="English"/>
        <coding>
          <system value="urn:oid:2.16.840.1.113883.6.99"/>
          <code value="en"/>
          <display value="English"/>
        </coding>
      </language>
    </communication>
    <extension>
      <url value="http://hl7.org/fhir/StructureDefinition/us-core-race"/>
      <valueCodeableConcept>
        <text value="White"/>
        <coding>
          <system value="2.16.840.1.113883.5.104"/>
          <code value="2106-3"/>
          <display value="White"/>
        </coding>
      </valueCodeableConcept>
    </extension>
    <extension>
      <url value="http://hl7.org/fhir/StructureDefinition/us-core-ethnicity"/>
      <valueCodeableConcept>
        <text value="Unknown"/>
        <coding>
          <system value="2.16.840.1.113883.5.50"/>
          <code value="UNK"/>
          <display value="Unknown"/>
        </coding>
      </valueCodeableConcept>
    </extension>
  </Patient>
</resource>
<search>
  <mode value="match"/>
```

```
  </search>
</entry>
<entry>
  <fullUrl value="https://hostname/instance/api/FHIR/DSTU2/Patient/Te6i4i91kgVIfTthLY63dU2ssXNHwXk097.6wCp29ryYB"/>
  <link>
    <relation value="self"/>
    <url value="https://hostname/instance/api/FHIR/DSTU2/Patient/Te6i4i91kgVIfTthLY63dU2ssXNHwXk097.6wCp29ryYB"/>
  </link>
  <resource>
    <Patient>
      <birthDate value="1991-12-31T00:00:00"/>
      <active value="true"/>
      <gender value="female"/>
      <deceasedBoolean value="false"/>
      <id value="Te6i4i91kgVIfTthLY63dU2ssXNHwXk097.6wCp29ryYB"/>
      <name>
        <use value="usual"/>
        <family value="Doe"/>
        <given value="John"/>
        <given value="C"/>
      </name>
      <identifier>
        <use value="usual"/>
        <system value="urn:oid:1.2.840.114350.1.1"/>
        <value value="104803"/>
      </identifier>
      <extension>
        <url value="http://hl7.org/fhir/StructureDefinition/us-core-race"/>
        <valueCodeableConcept>
          <text value="Unknown"/>
          <coding>
            <system value="2.16.840.1.113883.5.104"/>
            <code value="UNK"/>
            <display value="Unknown"/>
          </coding>
        </valueCodeableConcept>
      </extension>
      <extension>
        <url value="http://hl7.org/fhir/StructureDefinition/us-core-ethnicity"/>
        <valueCodeableConcept>
          <text value="Unknown"/>
          <coding>
            <system value="2.16.840.1.113883.5.50"/>
            <code value="UNK"/>
            <display value="Unknown"/>
          </coding>
        </valueCodeableConcept>
      </extension>
    </Patient>
  </resource>
  <search>
    <mode value="match"/>
  </search>
</entry>
<entry>
  <fullUrl value="https://hostname/instance/api/FHIR/DSTU2/Patient/TOBqFFKh8.TSTgOHfozJMTPWvphHOos55Vi-1lfQKvEMB"/>
  <link>
    <relation value="self"/>
    <url value="https://hostname/instance/api/FHIR/DSTU2/Patient/TOBqFFKh8.TSTgOHfozJMTPWvphHOos55Vi-1lfQKvEMB"/>
  </link>
  <resource>
    <Patient>
      <birthDate value="1991-12-31T00:00:00"/>
      <active value="true"/>
      <gender value="female"/>
      <deceasedBoolean value="false"/>
      <id value="TOBqFFKh8.TSTgOHfozJMTPWvphHOos55Vi-1lfQKvEMB"/>
      <name>
        <use value="usual"/>
        <family value="Doe"/>
        <given value="John"/>
        <given value="B"/>
      </name>
      <identifier>
        <use value="usual"/>
        <system value="urn:oid:1.2.840.114350.1.1"/>
        <value value="104802"/>
      </identifier>
      <extension>
        <url value="http://hl7.org/fhir/StructureDefinition/us-core-race"/>
        <valueCodeableConcept>
          <text value="Unknown"/>
          <coding>
            <system value="2.16.840.1.113883.5.104"/>
            <code value="UNK"/>
            <display value="Unknown"/>
          </coding>
        </valueCodeableConcept>
      </extension>
```

```
      <extension>
        <url value="http://hl7.org/fhir/StructureDefinition/us-core-ethnicity"/>
        <valueCodeableConcept>
          <text value="Unknown"/>
          <coding>
            <system value="2.16.840.1.113883.5.50"/>
            <code value="UNK"/>
            <display value="Unknown"/>
          </coding>
        </valueCodeableConcept>
      </extension>
    </Patient>
  </resource>
  <search>
    <mode value="match"/>
  </search>
</entry>
<entry>
  <fullUrl value="https://hostname/instance/api/FHIR/DSTU2/Patient/TVvHM06czXsYBOZYtJiz9BsSuvzmIbZGbIRzim-CwknYB"/>
  <link>
    <relation value="self"/>
    <url value="https://hostname/instance/api/FHIR/DSTU2/Patient/TVvHM06czXsYBOZYtJiz9BsSuvzmIbZGbIRzim-CwknYB"/>
  </link>
  <resource>
    <Patient>
      <birthDate value="1991-12-31T00:00:00"/>
      <active value="true"/>
      <gender value="female"/>
      <deceasedBoolean value="false"/>
      <id value="TVvHM06czXsYBOZYtJiz9BsSuvzmIbZGbIRzim-CwknYB"/>
      <name>
        <use value="usual"/>
        <family value="Doe"/>
        <given value="John"/>
        <given value="A"/>
      </name>
      <identifier>
        <use value="usual"/>
        <system value="urn:oid:1.2.840.114350.1.1"/>
        <value value="104801"/>
      </identifier>
      <extension>
        <url value="http://hl7.org/fhir/StructureDefinition/us-core-race"/>
        <valueCodeableConcept>
          <text value="Unknown"/>
          <coding>
            <system value="2.16.840.1.113883.5.104"/>
            <code value="UNK"/>
            <display value="Unknown"/>
          </coding>
        </valueCodeableConcept>
      </extension>
      <extension>
        <url value="http://hl7.org/fhir/StructureDefinition/us-core-ethnicity"/>
        <valueCodeableConcept>
          <text value="Unknown"/>
          <coding>
            <system value="2.16.840.1.113883.5.50"/>
            <code value="UNK"/>
            <display value="Unknown"/>
          </coding>
        </valueCodeableConcept>
      </extension>
    </Patient>
  </resource>
  <search>
    <mode value="match"/>
  </search>
</entry>
<entry>
  <fullUrl value="https://hostname/instance/api/FHIR/DSTU2/Patient/ToueZw1.F0ZmssWl-YvEOkzXHFyPqpsv.7zUXEqQjQ2QB"/>
  <link>
    <relation value="self"/>
    <url value="https://hostname/instance/api/FHIR/DSTU2/Patient/ToueZw1.F0ZmssWl-YvEOkzXHFyPqpsv.7zUXEqQjQ2QB"/>
  </link>
  <resource>
    <Patient>
      <birthDate value="1991-01-13T00:00:00"/>
      <active value="true"/>
      <gender value="female"/>
      <deceasedBoolean value="false"/>
      <id value="ToueZw1.F0ZmssWl-YvEOkzXHFyPqpsv.7zUXEqQjQ2QB"/>
      <name>
        <use value="usual"/>
        <family value="Doe"/>
        <given value="John"/>
        <given value="Observation"/>
      </name>
      <identifier>
```

```
        <use value="usual"/>
        <system value="urn:oid:1.2.840.114350.1.1"/>
        <value value="104893"/>
      </identifier>
      <extension>
        <url value="http://hl7.org/fhir/StructureDefinition/us-core-race"/>
        <valueCodeableConcept>
          <text value="Unknown"/>
          <coding>
            <system value="2.16.840.1.113883.5.104"/>
            <code value="UNK"/>
            <display value="Unknown"/>
          </coding>
        </valueCodeableConcept>
      </extension>
      <extension>
        <url value="http://hl7.org/fhir/StructureDefinition/us-core-ethnicity"/>
        <valueCodeableConcept>
          <text value="Unknown"/>
          <coding>
            <system value="2.16.840.1.113883.5.50"/>
            <code value="UNK"/>
            <display value="Unknown"/>
          </coding>
        </valueCodeableConcept>
      </extension>
    </Patient>
  </resource>
  <search>
    <mode value="match"/>
  </search>
</entry>
<entry>
  <fullUrl value="https://hostname/instance/api/FHIR/DSTU2/Patient/T0hY1cLFnO.TSydQJmt.mneK9ATxa9uysPCZFPmn2KygB"/>
  <link>
    <relation value="self"/>
    <url value="https://hostname/instance/api/FHIR/DSTU2/Patient/T0hY1cLFnO.TSydQJmt.mneK9ATxa9uysPCZFPmn2KygB"/>
  </link>
  <resource>
    <Patient>
      <birthDate value="1991-01-13T00:00:00"/>
      <active value="true"/>
      <gender value="female"/>
      <deceasedBoolean value="false"/>
      <id value="T0hY1cLFnO.TSydQJmt.mneK9ATxa9uysPCZFPmn2KygB"/>
      <careProvider>
        <display value="John Doe, MD"/>
        <reference value="https://hostname/instance/api/FHIR/DSTU2/Practitioner/TiOmkdUgh7pJl0-mpSeeFtQB"/>
      </careProvider>
      <name>
        <use value="usual"/>
        <family value="Doe"/>
        <given value="John"/>
        <given value="Condition"/>
      </name>
      <identifier>
        <use value="usual"/>
        <system value="urn:oid:1.2.840.114350.1.1"/>
        <value value="104897"/>
      </identifier>
      <address>
        <use value="home"/>
        <line value="1979 Milky Way"/>
        <city value="VERONA"/>
        <state value="WI"/>
        <postalCode value="53593"/>
        <country value="USA"/>
      </address>
      <telecom>
        <system value="phone"/>
        <value value="608-555-5555"/>
        <use value="home"/>
      </telecom>
      <telecom>
        <system value="phone"/>
        <value value="608-222-2222"/>
        <use value="work"/>
      </telecom>
      <telecom>
        <system value="email"/>
        <value value="condition@fhir.com"/>
      </telecom>
      <maritalStatus>
        <text value="Single"/>
        <coding>
          <system value="http://hl7.org/fhir/vs/marital-status"/>
          <code value="S"/>
          <display value="Never Married"/>
        </coding>
```

```
      </maritalStatus>
      <communication>
        <preferred value="true"/>
        <language>
          <text value="English"/>
          <coding>
            <system value="urn:oid:2.16.840.1.113883.6.99"/>
            <code value="en"/>
            <display value="English"/>
          </coding>
        </language>
      </communication>
      <extension>
        <url value="http://hl7.org/fhir/StructureDefinition/us-core-race"/>
        <valueCodeableConcept>
          <text value="Other Race"/>
          <coding>
            <system value="2.16.840.1.113883.5.104"/>
            <code value="2131-1"/>
            <display value="Other Race"/>
          </coding>
        </valueCodeableConcept>
      </extension>
      <extension>
        <url value="http://hl7.org/fhir/StructureDefinition/us-core-ethnicity"/>
        <valueCodeableConcept>
          <text value="Unknown"/>
          <coding>
            <system value="2.16.840.1.113883.5.50"/>
            <code value="UNK"/>
            <display value="Unknown"/>
          </coding>
        </valueCodeableConcept>
      </extension>
    </Patient>
  </resource>
  <search>
    <mode value="match"/>
  </search>
</entry>
<entry>
  <fullUrl value="https://hostname/instance/api/FHIR/DSTU2/Patient/To.tzuYi7iqTWlgCJE3ESXNZdsySqanPeMiImsJ5kCQwB"/>
  <link>
    <relation value="self"/>
    <url value="https://hostname/instance/api/FHIR/DSTU2/Patient/To.tzuYi7iqTWlgCJE3ESXNZdsySqanPeMiImsJ5kCQwB"/>
  </link>
  <resource>
    <Patient>
      <birthDate value="1991-01-19T00:00:00"/>
      <active value="true"/>
      <gender value="female"/>
      <deceasedBoolean value="false"/>
      <id value="To.tzuYi7iqTWlgCJE3ESXNZdsySqanPeMiImsJ5kCQwB"/>
      <name>
        <use value="usual"/>
        <family value="Doe"/>
        <given value="John"/>
        <given value="DD"/>
      </name>
      <identifier>
        <use value="usual"/>
        <system value="urn:oid:1.2.840.114350.1.1"/>
        <value value="105012"/>
      </identifier>
      <extension>
        <url value="http://hl7.org/fhir/StructureDefinition/us-core-race"/>
        <valueCodeableConcept>
          <text value="Unknown"/>
          <coding>
            <system value="2.16.840.1.113883.5.104"/>
            <code value="UNK"/>
            <display value="Unknown"/>
          </coding>
        </valueCodeableConcept>
      </extension>
      <extension>
        <url value="http://hl7.org/fhir/StructureDefinition/us-core-ethnicity"/>
        <valueCodeableConcept>
          <text value="Unknown"/>
          <coding>
            <system value="2.16.840.1.113883.5.50"/>
            <code value="UNK"/>
            <display value="Unknown"/>
          </coding>
        </valueCodeableConcept>
      </extension>
    </Patient>
  </resource>
  <search>
```

```
    <mode value="match"/>
  </search>
</entry>
<entry>
  <fullUrl value="https://hostname/instance/api/FHIR/DSTU2/Patient/TaBMXyh9psHdly7olirysOC1vFrFEWt9Peot0Vjyt9wQB"/>
  <link>
    <relation value="self"/>
    <url value="https://hostname/instance/api/FHIR/DSTU2/Patient/TaBMXyh9psHdly7olirysOC1vFrFEWt9Peot0Vjyt9wQB"/>
  </link>
  <resource>
    <Patient>
      <birthDate value="1991-01-19T00:00:00"/>
      <active value="true"/>
      <gender value="female"/>
      <deceasedBoolean value="false"/>
      <id value="TaBMXyh9psHdly7olirysOC1vFrFEWt9Peot0Vjyt9wQB"/>
      <name>
        <use value="usual"/>
        <family value="Doe"/>
        <given value="John"/>
        <given value="D"/>
      </name>
      <identifier>
        <use value="usual"/>
        <system value="urn:oid:1.2.840.114350.1.1"/>
        <value value="105011"/>
      </identifier>
      <identifier>
        <use value="usual"/>
        <system value="urn:oid:1.2.840.114350.1.13.5552.1.7.5.737384.225"/>
        <value value="54654"/>
      </identifier>
      <maritalStatus>
        <text value="Married"/>
        <coding>
          <system value="http://hl7.org/fhir/vs/marital-status"/>
          <code value="M"/>
          <display value="Married"/>
        </coding>
      </maritalStatus>
      <communication>
        <preferred value="true"/>
        <language>
          <text value="Dutch"/>
          <coding>
            <system value="urn:oid:2.16.840.1.113883.6.99"/>
            <code value="nl"/>
            <display value="Dutch"/>
          </coding>
        </language>
      </communication>
      <extension>
        <url value="http://hl7.org/fhir/StructureDefinition/us-core-race"/>
        <valueCodeableConcept>
          <text value="Unknown"/>
          <coding>
            <system value="2.16.840.1.113883.5.104"/>
            <code value="UNK"/>
            <display value="Unknown"/>
          </coding>
        </valueCodeableConcept>
      </extension>
      <extension>
        <url value="http://hl7.org/fhir/StructureDefinition/us-core-ethnicity"/>
        <valueCodeableConcept>
          <text value="Unknown"/>
          <coding>
            <system value="2.16.840.1.113883.5.50"/>
            <code value="UNK"/>
            <display value="Unknown"/>
          </coding>
        </valueCodeableConcept>
      </extension>
    </Patient>
  </resource>
  <search>
    <mode value="match"/>
  </search>
</entry>
<entry>
  <fullUrl value="https://hostname/instance/api/FHIR/DSTU2/Patient/Tgv7cZXHhDotXlKpEZLbT1A11ZuVyfk-D5zPphjQr5IMB"/>
  <link>
    <relation value="self"/>
    <url value="https://hostname/instance/api/FHIR/DSTU2/Patient/Tgv7cZXHhDotXlKpEZLbT1A11ZuVyfk-D5zPphjQr5IMB"/>
  </link>
  <resource>
    <Patient>
      <birthDate value="1991-01-24T00:00:00"/>
      <active value="true"/>
```

```
      <gender value="female"/>
      <deceasedBoolean value="false"/>
      <id value="Tgv7cZXHhDotXlKpEZLbT1A11ZuVyfk-D5zPphjQr5IMB"/>
      <careProvider>
        <display value="John Doe, MD"/>
        <reference value="https://hostname/instance/api/FHIR/DSTU2/Practitioner/TiOmkdUgh7pJl0-mpSeeFtQB"/>
      </careProvider>
      <name>
        <use value="usual"/>
        <family value="Doe"/>
        <given value="John"/>
        <given value="E"/>
      </name>
      <identifier>
        <use value="usual"/>
        <system value="urn:oid:1.2.840.114350.1.1"/>
        <value value="105228"/>
      </identifier>
      <extension>
        <url value="http://hl7.org/fhir/StructureDefinition/us-core-race"/>
        <valueCodeableConcept>
          <text value="Unknown"/>
          <coding>
            <system value="2.16.840.1.113883.5.104"/>
            <code value="UNK"/>
            <display value="Unknown"/>
          </coding>
        </valueCodeableConcept>
      </extension>
      <extension>
        <url value="http://hl7.org/fhir/StructureDefinition/us-core-ethnicity"/>
        <valueCodeableConcept>
          <text value="Unknown"/>
          <coding>
            <system value="2.16.840.1.113883.5.50"/>
            <code value="UNK"/>
            <display value="Unknown"/>
          </coding>
        </valueCodeableConcept>
      </extension>
    </Patient>
  </resource>
  <search>
    <mode value="match"/>
  </search>
</entry>
<entry>
  <fullUrl value="https://hostname/instance/api/FHIR/DSTU2/Patient/TWwDy4mdtNEaxOoQNLzfatY6C01B5cXM0opoEhrprDq8B"/>
  <link>
    <relation value="self"/>
    <url value="https://hostname/instance/api/FHIR/DSTU2/Patient/TWwDy4mdtNEaxOoQNLzfatY6C01B5cXM0opoEhrprDq8B"/>
  </link>
  <resource>
    <Patient>
      <birthDate value="1991-01-24T00:00:00"/>
      <active value="true"/>
      <gender value="female"/>
      <deceasedBoolean value="false"/>
      <id value="TWwDy4mdtNEaxOoQNLzfatY6C01B5cXM0opoEhrprDq8B"/>
      <careProvider>
        <display value="John Doe, MD"/>
        <reference value="https://hostname/instance/api/FHIR/DSTU2/Practitioner/TiOmkdUgh7pJl0-mpSeeFtQB"/>
      </careProvider>
      <name>
        <use value="usual"/>
        <family value="Doe"/>
        <given value="John"/>
        <given value="F"/>
      </name>
      <identifier>
        <use value="usual"/>
        <system value="urn:oid:1.2.840.114350.1.1"/>
        <value value="105229"/>
      </identifier>
      <extension>
        <url value="http://hl7.org/fhir/StructureDefinition/us-core-race"/>
        <valueCodeableConcept>
          <text value="Unknown"/>
          <coding>
            <system value="2.16.840.1.113883.5.104"/>
            <code value="UNK"/>
            <display value="Unknown"/>
          </coding>
        </valueCodeableConcept>
      </extension>
      <extension>
        <url value="http://hl7.org/fhir/StructureDefinition/us-core-ethnicity"/>
        <valueCodeableConcept>
          <text value="Unknown"/>
```

```
          <coding>
            <system value="2.16.840.1.113883.5.50"/>
            <code value="UNK"/>
            <display value="Unknown"/>
          </coding>
        </valueCodeableConcept>
      </extension>
    </Patient>
  </resource>
  <search>
    <mode value="match"/>
  </search>
</entry>
<entry>
  <fullUrl value="https://hostname/instance/api/FHIR/DSTU2/Patient/T46lhChTnLnBf-ZBR7qN4gtw.XYXt7u1tzla4ZyD9t7cB"/>
  <link>
    <relation value="self"/>
    <url value="https://hostname/instance/api/FHIR/DSTU2/Patient/T46lhChTnLnBf-ZBR7qN4gtw.XYXt7u1tzla4ZyD9t7cB"/>
  </link>
  <resource>
    <Patient>
      <birthDate value="1991-01-24T00:00:00"/>
      <active value="true"/>
      <gender value="female"/>
      <deceasedBoolean value="false"/>
      <id value="T46lhChTnLnBf-ZBR7qN4gtw.XYXt7u1tzla4ZyD9t7cB"/>
      <careProvider>
        <display value="John Doe, MD"/>
        <reference value="https://hostname/instance/api/FHIR/DSTU2/Practitioner/TiOmkdUgh7pJl0-mpSeeFtQB"/>
      </careProvider>
      <name>
        <use value="usual"/>
        <family value="Doe"/>
        <given value="John"/>
        <given value="G"/>
      </name>
      <identifier>
        <use value="usual"/>
        <system value="urn:oid:1.2.840.114350.1.1"/>
        <value value="105230"/>
      </identifier>
      <extension>
        <url value="http://hl7.org/fhir/StructureDefinition/us-core-race"/>
        <valueCodeableConcept>
          <text value="Unknown"/>
          <coding>
            <system value="2.16.840.1.113883.5.104"/>
            <code value="UNK"/>
            <display value="Unknown"/>
          </coding>
        </valueCodeableConcept>
      </extension>
      <extension>
        <url value="http://hl7.org/fhir/StructureDefinition/us-core-ethnicity"/>
        <valueCodeableConcept>
          <text value="Unknown"/>
          <coding>
            <system value="2.16.840.1.113883.5.50"/>
            <code value="UNK"/>
            <display value="Unknown"/>
          </coding>
        </valueCodeableConcept>
      </extension>
    </Patient>
  </resource>
  <search>
    <mode value="match"/>
  </search>
</entry>
<entry>
  <fullUrl value="https://hostname/instance/api/FHIR/DSTU2/Patient/TVtd7x5wMBMpqt6hanM6NlqEXrPIRlc6yZUrGmXddKX8B"/>
  <link>
    <relation value="self"/>
    <url value="https://hostname/instance/api/FHIR/DSTU2/Patient/TVtd7x5wMBMpqt6hanM6NlqEXrPIRlc6yZUrGmXddKX8B"/>
  </link>
  <resource>
    <Patient>
      <birthDate value="1991-01-25T00:00:00"/>
      <active value="true"/>
      <gender value="female"/>
      <deceasedBoolean value="false"/>
      <id value="TVtd7x5wMBMpqt6hanM6NlqEXrPIRlc6yZUrGmXddKX8B"/>
      <careProvider>
        <display value="John Doe, MD"/>
        <reference value="https://hostname/instance/api/FHIR/DSTU2/Practitioner/TiOmkdUgh7pJl0-mpSeeFtQB"/>
      </careProvider>
      <name>
        <use value="usual"/>
        <family value="Doe"/>
```

```
        <given value="John"/>
        <given value="H"/>
      </name>
      <identifier>
        <use value="usual"/>
        <system value="urn:oid:1.2.840.114350.1.1"/>
        <value value="105399"/>
      </identifier>
      <address>
        <use value="home"/>
        <line value="1979 Milky Way"/>
        <line value="Apt 310"/>
        <city value="VERONA"/>
        <state value="WI"/>
        <postalCode value="53593"/>
        <country value="USA"/>
      </address>
      <telecom>
        <system value="phone"/>
        <value value="608-555-5555"/>
        <use value="home"/>
      </telecom>
      <telecom>
        <system value="phone"/>
        <value value="608-444-4444"/>
        <use value="work"/>
      </telecom>
      <maritalStatus>
        <text value="Single"/>
        <coding>
          <system value="http://hl7.org/fhir/vs/marital-status"/>
          <code value="S"/>
          <display value="Never Married"/>
        </coding>
      </maritalStatus>
      <communication>
        <preferred value="true"/>
        <language>
          <text value="English"/>
          <coding>
            <system value="urn:oid:2.16.840.1.113883.6.99"/>
            <code value="en"/>
            <display value="English"/>
          </coding>
        </language>
      </communication>
      <extension>
        <url value="http://hl7.org/fhir/StructureDefinition/us-core-race"/>
        <valueCodeableConcept>
          <text value="White"/>
          <coding>
            <system value="2.16.840.1.113883.5.104"/>
            <code value="2106-3"/>
            <display value="White"/>
          </coding>
        </valueCodeableConcept>
      </extension>
      <extension>
        <url value="http://hl7.org/fhir/StructureDefinition/us-core-ethnicity"/>
        <valueCodeableConcept>
          <text value="Unknown"/>
          <coding>
            <system value="2.16.840.1.113883.5.50"/>
            <code value="UNK"/>
            <display value="Unknown"/>
          </coding>
        </valueCodeableConcept>
      </extension>
    </Patient>
  </resource>
  <search>
    <mode value="match"/>
  </search>
</entry>
<entry>
  <fullUrl value="https://hostname/instance/api/FHIR/DSTU2/Patient/TG7cJWa-If.KeTo74UIBQhhbTdO7s5GnyjkLCzU7kx54B"/>
  <link>
    <relation value="self"/>
    <url value="https://hostname/instance/api/FHIR/DSTU2/Patient/TG7cJWa-If.KeTo74UIBQhhbTdO7s5GnyjkLCzU7kx54B"/>
  </link>
  <resource>
    <Patient>
      <birthDate value="1991-02-02T00:00:00"/>
      <active value="true"/>
      <gender value="female"/>
      <deceasedBoolean value="false"/>
      <id value="TG7cJWa-If.KeTo74UIBQhhbTdO7s5GnyjkLCzU7kx54B"/>
      <name>
        <use value="usual"/>
```

```
        <family value="Doe"/>
        <given value="John"/>
        <given value="Device"/>
      </name>
      <identifier>
        <use value="usual"/>
        <system value="urn:oid:1.2.840.114350.1.1"/>
        <value value="106127"/>
      </identifier>
      <telecom>
        <system value="email"/>
        <value value="devicefhir@email.com"/>
      </telecom>
      <extension>
        <url value="http://hl7.org/fhir/StructureDefinition/us-core-race"/>
        <valueCodeableConcept>
          <text value="Unknown"/>
          <coding>
            <system value="2.16.840.1.113883.5.104"/>
            <code value="UNK"/>
            <display value="Unknown"/>
          </coding>
        </valueCodeableConcept>
      </extension>
      <extension>
        <url value="http://hl7.org/fhir/StructureDefinition/us-core-ethnicity"/>
        <valueCodeableConcept>
          <text value="Unknown"/>
          <coding>
            <system value="2.16.840.1.113883.5.50"/>
            <code value="UNK"/>
            <display value="Unknown"/>
          </coding>
        </valueCodeableConcept>
      </extension>
    </Patient>
  </resource>
  <search>
    <mode value="match"/>
  </search>
</entry>
<entry>
  <fullUrl value="https://hostname/instance/api/FHIR/DSTU2/Patient/T9X1pLrPrD6802KBILrnAFln5jV7TXVKw3-p5XCqQPkMB"/>
  <link>
    <relation value="self"/>
    <url value="https://hostname/instance/api/FHIR/DSTU2/Patient/T9X1pLrPrD6802KBILrnAFln5jV7TXVKw3-p5XCqQPkMB"/>
  </link>
  <resource>
    <Patient>
      <birthDate value="1991-02-09T00:00:00"/>
      <active value="true"/>
      <gender value="female"/>
      <deceasedBoolean value="false"/>
      <id value="T9X1pLrPrD6802KBILrnAFln5jV7TXVKw3-p5XCqQPkMB"/>
      <name>
        <use value="usual"/>
        <family value="Doe"/>
        <given value="John"/>
        <given value="Immunization"/>
      </name>
      <identifier>
        <use value="usual"/>
        <system value="urn:oid:1.2.840.114350.1.1"/>
        <value value="107173"/>
      </identifier>
      <extension>
        <url value="http://hl7.org/fhir/StructureDefinition/us-core-race"/>
        <valueCodeableConcept>
          <text value="Unknown"/>
          <coding>
            <system value="2.16.840.1.113883.5.104"/>
            <code value="UNK"/>
            <display value="Unknown"/>
          </coding>
        </valueCodeableConcept>
      </extension>
      <extension>
        <url value="http://hl7.org/fhir/StructureDefinition/us-core-ethnicity"/>
        <valueCodeableConcept>
          <text value="Unknown"/>
          <coding>
            <system value="2.16.840.1.113883.5.50"/>
            <code value="UNK"/>
            <display value="Unknown"/>
          </coding>
        </valueCodeableConcept>
      </extension>
    </Patient>
  </resource>
```

```
  <search>
    <mode value="match"/>
  </search>
</entry>
<entry>
  <fullUrl value="https://hostname/instance/api/FHIR/DSTU2/Patient/TK0ALKsNCLTt1zsJOsvcOxUmYN0SxaZiehN52lnU8FgMB"/>
  <link>
    <relation value="self"/>
    <url value="https://hostname/instance/api/FHIR/DSTU2/Patient/TK0ALKsNCLTt1zsJOsvcOxUmYN0SxaZiehN52lnU8FgMB"/>
  </link>
  <resource>
    <Patient>
      <birthDate value="1991-02-11T00:00:00"/>
      <active value="true"/>
      <gender value="female"/>
      <deceasedBoolean value="false"/>
      <id value="TK0ALKsNCLTt1zsJOsvcOxUmYN0SxaZiehN52lnU8FgMB"/>
      <name>
        <use value="usual"/>
        <family value="Doe"/>
        <given value="John"/>
        <given value="Never Assessed"/>
      </name>
      <identifier>
        <use value="usual"/>
        <system value="urn:oid:1.2.840.114350.1.1"/>
        <value value="107243"/>
      </identifier>
      <extension>
        <url value="http://hl7.org/fhir/StructureDefinition/us-core-race"/>
        <valueCodeableConcept>
          <text value="Unknown"/>
          <coding>
            <system value="2.16.840.1.113883.5.104"/>
            <code value="UNK"/>
            <display value="Unknown"/>
          </coding>
        </valueCodeableConcept>
      </extension>
      <extension>
        <url value="http://hl7.org/fhir/StructureDefinition/us-core-ethnicity"/>
        <valueCodeableConcept>
          <text value="Unknown"/>
          <coding>
            <system value="2.16.840.1.113883.5.50"/>
            <code value="UNK"/>
            <display value="Unknown"/>
          </coding>
        </valueCodeableConcept>
      </extension>
    </Patient>
  </resource>
  <search>
    <mode value="match"/>
  </search>
</entry>
<entry>
  <fullUrl value="https://hostname/instance/api/FHIR/DSTU2/Patient/TA5E13.E32DEDmMHKT.MbqX-Nc9W6hFsM5.TCbUfJvF0B"/>
  <link>
    <relation value="self"/>
    <url value="https://hostname/instance/api/FHIR/DSTU2/Patient/TA5E13.E32DEDmMHKT.MbqX-Nc9W6hFsM5.TCbUfJvF0B"/>
  </link>
  <resource>
    <Patient>
      <birthDate value="1991-02-11T00:00:00"/>
      <active value="true"/>
      <gender value="female"/>
      <deceasedBoolean value="false"/>
      <id value="TA5E13.E32DEDmMHKT.MbqX-Nc9W6hFsM5.TCbUfJvF0B"/>
      <name>
        <use value="usual"/>
        <family value="Doe"/>
        <given value="John"/>
        <given value="Unknown"/>
      </name>
      <identifier>
        <use value="usual"/>
        <system value="urn:oid:1.2.840.114350.1.1"/>
        <value value="107244"/>
      </identifier>
      <extension>
        <url value="http://hl7.org/fhir/StructureDefinition/us-core-race"/>
        <valueCodeableConcept>
          <text value="Unknown"/>
          <coding>
            <system value="2.16.840.1.113883.5.104"/>
            <code value="UNK"/>
            <display value="Unknown"/>
          </coding>
```

```
        </valueCodeableConcept>
      </extension>
      <extension>
        <url value="http://hl7.org/fhir/StructureDefinition/us-core-ethnicity"/>
        <valueCodeableConcept>
          <text value="Unknown"/>
          <coding>
            <system value="2.16.840.1.113883.5.50"/>
            <code value="UNK"/>
            <display value="Unknown"/>
          </coding>
        </valueCodeableConcept>
      </extension>
    </Patient>
  </resource>
  <search>
    <mode value="match"/>
  </search>
 </entry>
 <entry>
  <fullUrl value="https://hostname/instance/api/FHIR/DSTU2/Patient/TE8W3rK2.OY-eAQIFbovGOw3YxmqXp-GmS6WnZ0Q.ZwEB"/>
  <link>
    <relation value="self"/>
    <url value="https://hostname/instance/api/FHIR/DSTU2/Patient/TE8W3rK2.OY-eAQIFbovGOw3YxmqXp-GmS6WnZ0Q.ZwEB"/>
  </link>
  <resource>
    <Patient>
      <birthDate value="1991-02-11T00:00:00"/>
      <active value="true"/>
      <gender value="female"/>
      <deceasedBoolean value="false"/>
      <id value="TE8W3rK2.OY-eAQIFbovGOw3YxmqXp-GmS6WnZ0Q.ZwEB"/>
      <name>
        <use value="usual"/>
        <family value="Doe"/>
        <given value="John"/>
        <given value="Smoker"/>
      </name>
      <identifier>
        <use value="usual"/>
        <system value="urn:oid:1.2.840.114350.1.1"/>
        <value value="107245"/>
      </identifier>
      <extension>
        <url value="http://hl7.org/fhir/StructureDefinition/us-core-race"/>
        <valueCodeableConcept>
          <text value="Unknown"/>
          <coding>
            <system value="2.16.840.1.113883.5.104"/>
            <code value="UNK"/>
            <display value="Unknown"/>
          </coding>
        </valueCodeableConcept>
      </extension>
      <extension>
        <url value="http://hl7.org/fhir/StructureDefinition/us-core-ethnicity"/>
        <valueCodeableConcept>
          <text value="Unknown"/>
          <coding>
            <system value="2.16.840.1.113883.5.50"/>
            <code value="UNK"/>
            <display value="Unknown"/>
          </coding>
        </valueCodeableConcept>
      </extension>
    </Patient>
  </resource>
  <search>
    <mode value="match"/>
  </search>
 </entry>
</Bundle>
```


Change log

Epic Version | Description | Type

May 2023 | Allow searching for patient records using only demographics the associated user has security to access in the response. | Breaking change

22.3.3 Practitioner.Read (DSTU2)

File: site/apis/22-Identification-Individuals/3-DSTU2/31-Practitioner-Read-DSTU2.html

Epic API ID | 31

FHIR version | DSTU2

Categories | Identification Individuals

API type | USCDI

A la carte | Industry-Standard Level 1 API
USCDI | Yes
Available in inpatient and other contexts | Yes
ONC certification products | EpicCare Ambulatory Base, EpicCare Inpatient Base
ONC certification versions | Epic 2015
HTTP method | GET
URL template | api/FHIR/DSTU2/Practitioner/{ID}
Supports OAuth 2.0 | True
Supported user types | Backend Systems and Non-OAuth 2.0, Clinicians or Administrative Users, Patients
Performs scope validation | False
Source | https://fhir.epic.com/Specifications?api=31

Description

The FHIR Practitioner resource defines demographics and identifiers for care providers at a health care organization. The Practitioner resource supplements many of the resources within FHIR by providing information about a primary care provider, prescriber, or the clinician involved in ordering a diagnostic test for a patient.

The Practitioner resource corresponds to the following Common Clinical Data Set (CCDS) Elements: Care Team.

The read interaction enables the look up of a Practitioner resource by a constant server ID. The read interaction allows clients to store only the server ID, and with a single request, retrieve the most up-to-date demographics on a practitioner. Read interactions typically begin with a client having previously established a relationship, often through receiving the provider reference as a part of the Patient resource.

Request parameters

Name | Type | Optional | Array | Cardinality | Description
ID | String | False | | | The FHIR ID of a practitioner.

Response elements

Name | Type | Optional | Array | Cardinality | Description
Practitioner | Practitioner | False | | | A single Practitioner FHIR resource.
Practitioner.communication | CodeableConcept | True | Yes | | Spoken language of the provider.
Practitioner.gender | String | True | | | The sex of the provider.
Practitioner.identifier | Identifier | True | Yes | | Additional practitioner identifiers.
Practitioner.name | HumanName | True | | | The name of the provider, including all prefixes and suffixes available.
Practitioner.practitionerRole | PractionerRole | True | Yes | | The practitioner's role at the organization.
Practitioner.practitionerRole.role | CodeableConcept | True | | | Roles which this practitioner may perform.
Practitioner.practitionerRole.specialty | CodeableConcept | True | Yes | | Specific specialty of the practitioner.

Sample request

```
https://hostname/instance/api/FHIR/DSTU2/Practitioner/TrTk7Zaw96VJM5sIX95IYHAB
```

Sample response

```
<Practitioner xmlns="http://hl7.org/fhir">
  <gender value="female"/>
  <active value="true"/>
  <id value="TrTk7Zaw96VJM5sIX95IYHAB"/>
  <identifier>
    <use value="usual"/>
    <system value="PROVID"/>
    <value value="97"/>
  </identifier>
  <name>
    <text value="Wilson, Helen, MD"/>
    <family value="Wilson"/>
    <given value="Helen"/>
    <given value="Claire"/>
  </name>
  <communication>
    <text value="English"/>
    <coding>
      <system value="urn:oid:2.16.840.1.113883.6.99"/>
      <code value="en"/>
      <display value="English"/>
    </coding>
  </communication>
  <communication>
    <text value="Spanish"/>
    <coding>
      <system value="urn:oid:2.16.840.1.113883.6.99"/>
      <code value="es"/>
      <display value="Spanish"/>
    </coding>
  </communication>
</Practitioner>
```

22.3.4 Practitioner.Search (DSTU2)

File: site/apis/22-Identification-Individuals/3-DSTU2/826-Practitioner-Search-DSTU2.html
Epic API ID | 826
FHIR version | DSTU2
Categories | Identification Individuals
API type | USCDI
A la carte | Industry-Standard Level 1 API
USCDI | Yes
Available in inpatient and other contexts | Yes
ONC certification products | EpicCare Ambulatory Base, EpicCare Inpatient Base
ONC certification versions | Epic 2017
HTTP method | GET
URL template | api/FHIR/DSTU2/Practitioner?_id={_id}&address={address}&family={family}&gender={gender}&given={given}&specialty={specialty}&address_city={address_city}&address_state={address_state}&address_postalcode={address_postalcode}
Supports OAuth 2.0 | True
Supported user types | Backend Systems and Non-OAuth 2.0, Clinicians or Administrative Users, Patients
Performs scope validation | False
Source | https://fhir.epic.com/Specifications?api=826

Description

The search interaction enables the client to query for Practitioner resources based on a specified set of demographics information. To activate a Practitioner resource search, you must include either the family or specialty parameter.

Request parameters

Name | Type | Optional | Array | Cardinality | Description
address | String | True | | | Search for Practitioner resources by any part of an address, such as street or city, where a practitioner can be found.
address_city | String | True | | | Search for Practitioner resources using the city portion of the address at which the practitioner can be found. This parameter must be used with the address_postalcode parameter.
address_postalcode | String | True | | | Search for Practitioner resources using the postal code portion of the address at which the practitioner can be found.
address_state | String | True | | | Search for Practitioner resources using the state portion of the address at which the practitioner can be found.
family | String | True | | | Search for Practitioner resources by family (last) name. Family name searching supports both exact and "sounds like" matches. Either Family or Specialty is required for a search to succeed.
gender | String | True | | | Search for Practitioner resources using the following gender codes: "female", "male", or "unknown".
given | String | True | | | Search for Practitioner resources by given (first) name. Given name searching supports both exact and "sounds like" matches.
specialty | String | True | | | Search for Practitioner resources by specialty in the format [code system]|[code]. Either Family or Specialty is required for a search to succeed.

Response elements

Name | Type | Optional | Array | Cardinality | Description
Bundle | Bundle | True | | | Resource bundle. For more information, refer to the FHIR specification.
Bundle.entry | Entry | True | Yes | | A single entry returned as part of this bundle.
Bundle.entry.resource | resource | True | | | A single resource returned as part of this bundle.
Bundle.entry.resource.Practitioner | Practitioner | True | | | An instance of the DSTU2 Practitioner resource.
Bundle.entry.resource.Practitioner.communication | CodeableConcept | True | Yes | | Spoken language of the provider.
Bundle.entry.resource.Practitioner.gender | String | True | | | The sex of the provider.
Bundle.entry.resource.Practitioner.identifier | Identifier | True | Yes | | Additional practitioner identifiers.
Bundle.entry.resource.Practitioner.name | HumanName | True | | | The name of the provider, including all prefixes and suffixes available.
Bundle.entry.resource.Practitioner.practitionerRole | PractionerRole | True | Yes | | The practitioner's role at the organization.
Bundle.entry.resource.Practitioner.practitionerRole.role | CodeableConcept | True | | | Roles which this practitioner may perform.
Bundle.entry.resource.Practitioner.practitionerRole.specialty | CodeableConcept | True | Yes | | Specific specialty of the practitioner.

Sample request

```
https://hostname/instance/api/FHIR/DSTU2/Practitioner?given=physician&family=oncology
```

Sample response

```
<?xml version="1.0" encoding="UTF-8"?>
<Bundle xmlns="http://hl7.org/fhir">
  <type value="searchset"/>
  <total value="4"/>
  <entry>
    <fullUrl value="https://hostname/instance/api/FHIR/DSTU2/Practitioner/TB68968z8PiutauHlCAZtmwB"/>
    <resource>
      <Practitioner>
        <active value="true"/>
        <id value="TB68968z8PiutauHlCAZtmwB"/>
        <identifier>
          <use value="usual"/>
          <system value="PROVID"/>
          <value value="1017"/>
```

```
      </identifier>
      <identifier>
        <use value="usual"/>
        <value value="207RX0202X"/>
      </identifier>
      <identifier>
        <use value="usual"/>
        <value value="1101799991"/>
      </identifier>
      <identifier>
        <use value="usual"/>
        <value value="TEMP1017"/>
      </identifier>
      <name>
        <use value="usual"/>
        <text value="Beacon, Physician, MD"/>
        <family value="Beacon"/>
        <given value="Physician"/>
      </name>
      <practitionerRole>
        <specialty>
          <text value="Oncology"/>
          <coding>
            <system value="urn:oid:1.2.840.114350.1.13.0.1.7.10.836982.1050"/>
            <code value="24"/>
            <display value="Oncology"/>
          </coding>
        </specialty>
      </practitionerRole>
      <practitionerRole>
        <role>
          <text value="Physician"/>
          <coding>
            <system value="urn:oid:1.2.840.114350.1.13.0.1.7.10.836982.1040"/>
            <code value="1"/>
            <display value="Physician"/>
          </coding>
        </role>
      </practitionerRole>
    </Practitioner>
  </resource>
  <link>
    <relation value="self"/>
    <url value="https://hostname/instance/api/FHIR/DSTU2/Practitioner/TB68968z8PiutauHlCAZtmwB"/>
  </link>
</entry>
<entry>
  <fullUrl value="https://hostname/instance/api/FHIR/DSTU2/Practitioner/ThJP8JGx1lvjqK0A6yCmckgB"/>
  <resource>
    <Practitioner>
      <active value="true"/>
      <id value="ThJP8JGx1lvjqK0A6yCmckgB"/>
      <identifier>
        <use value="usual"/>
        <system value="PROVID"/>
        <value value="1033"/>
      </identifier>
      <identifier>
        <use value="usual"/>
        <value value="2085R0001X"/>
      </identifier>
      <identifier>
        <use value="usual"/>
        <value value="1103399998"/>
      </identifier>
      <identifier>
        <use value="usual"/>
        <value value="TEMP1033"/>
      </identifier>
      <name>
        <use value="usual"/>
        <text value="Radiaton Oncology, Physician, MD"/>
        <family value="Radiation Oncology"/>
        <given value="Physician"/>
      </name>
      <practitionerRole>
        <specialty>
          <text value="Radiation Oncology"/>
          <coding>
            <system value="urn:oid:1.2.840.114350.1.13.0.1.7.10.836982.1050"/>
            <code value="39"/>
            <display value="Radiation Oncology"/>
          </coding>
        </specialty>
      </practitionerRole>
      <practitionerRole>
        <role>
          <text value="Physician"/>
          <coding>
```

```
            <system value="urn:oid:1.2.840.114350.1.13.0.1.7.10.836982.1040"/>
            <code value="1"/>
            <display value="Physician"/>
          </coding>
        </role>
      </practitionerRole>
    </Practitioner>
  </resource>
  <link>
    <relation value="self"/>
    <url value="https://hostname/instance/api/FHIR/DSTU2/Practitioner/ThJP8JGx1lvjqK0A6yCmckgB"/>
  </link>
</entry>
<entry>
  <fullUrl value="https://hostname/instance/api/FHIR/DSTU2/Practitioner/TUqLIzXr6eW1IQ1y4r.-oHwB"/>
  <resource>
    <Practitioner>
      <active value="true"/>
      <id value="TUqLIzXr6eW1IQ1y4r.-oHwB"/>
      <identifier>
        <use value="usual"/>
        <value value="207RX0202X"/>
      </identifier>
      <identifier>
        <use value="usual"/>
        <value value="1103999995"/>
      </identifier>
      <identifier>
        <use value="usual"/>
        <value value="794"/>
      </identifier>
      <name>
        <use value="usual"/>
        <text value="Physician Oncology, MD"/>
        <family value="Oncology"/>
        <given value="Physician"/>
      </name>
      <practitionerRole>
        <specialty>
          <text value="Oncology"/>
          <coding>
            <system value="urn:oid:1.2.840.114350.1.13.0.1.7.10.836982.1050"/>
            <code value="24"/>
            <display value="Oncology"/>
          </coding>
        </specialty>
      </practitionerRole>
      <practitionerRole>
        <role>
          <text value="Physician"/>
          <coding>
            <system value="urn:oid:1.2.840.114350.1.13.0.1.7.10.836982.1040"/>
            <code value="1"/>
            <display value="Physician"/>
          </coding>
        </role>
      </practitionerRole>
    </Practitioner>
  </resource>
  <link>
    <relation value="self"/>
    <url value="https://hostname/instance/api/FHIR/DSTU2/Practitioner/TUqLIzXr6eW1IQ1y4r.-oHwB"/>
  </link>
</entry>
<entry>
  <fullUrl
  value="https://hostname/instance/api/FHIR/DSTU2/Practitioner/TX00bAc8I9BeygK7mirvynKP9lu715yJBLF1JbRBAXEIB"/>
  <resource>
    <Practitioner>
      <active value="true"/>
      <id value="TX00bAc8I9BeygK7mirvynKP9lu715yJBLF1JbRBAXEIB"/>
      <identifier>
        <use value="usual"/>
        <system value="PROVID"/>
        <value value="4000062"/>
      </identifier>
      <name>
        <use value="usual"/>
        <text value="Physician Oncology Ip, MD"/>
        <family value="Oncology Ip"/>
        <given value="Physician"/>
      </name>
      <practitionerRole>
        <specialty>
          <text value="Oncology"/>
          <coding>
            <system value="urn:oid:1.2.840.114350.1.13.0.1.7.10.836982.1050"/>
            <code value="24"/>
            <display value="Oncology"/>
```

```
          </coding>
        </specialty>
      </practitionerRole>
      <practitionerRole>
        <role>
          <text value="Physician"/>
          <coding>
            <system value="urn:oid:1.2.840.114350.1.13.0.1.7.10.836982.1040"/>
            <code value="1"/>
            <display value="Physician"/>
          </coding>
        </role>
      </practitionerRole>
    </Practitioner>
  </resource>
  <link>
    <relation value="self"/>
    <url value="https://hostname/instance/api/FHIR/DSTU2/Practitioner/TX00bAc8I9BeygK7mirvynKP9lu715yJBLF1JbRBAXEIB"/>
  </link>
 </entry>
 <link>
  <relation value="self"/>
  <url value="https://hostname/instance/api/FHIR/DSTU2/Practitioner?given=physician&amp;family=oncology"/>
 </link>
</Bundle>
```


22.4 Identification Individuals: Non-FHIR

File: site/apis/22-Identification-Individuals/4-Non-FHIR/index.html

* PatientCreate (2009)
* PatientLookup (2005)
* PatientLookup (2009)
* PatientLookup (2012)
* UpdateUserDemographics

22.4.1 PatientCreate (2009)

File: site/apis/22-Identification-Individuals/4-Non-FHIR/250-PatientCreate-2009.html
Epic API ID | 250
FHIR version | Non-FHIR
Categories | Identification Individuals, Workflow Patient Management
API type | Epic Public
API group | EMPI Group
USCDI | No
Supports OAuth 2.0 | True
Supported user types | Backend Systems and Non-OAuth 2.0
Performs scope validation | False
SOAP namespace | urn:epicsystems-com:EMPI.2009.Services
WSDL | EMPI.wsdl
Source | https://fhir.epic.com/Specifications?api=250

Remarks

Epic recommends that you use the PatientLookup service to search for existing patient records before creating a new patient record.

Request

Name | Type | Optional | Array | Description
Name | NameType | True | | The patient's name.
DepartmentID | xsd:string | False | | The identifier of the Department (DEP) record to use for system settings when creating the patient. Example: 100
UserID | xsd:string | False | | The identifier of an Employee (EMP) record to use for who created the patient. This user must have patient creation security.
UserIDType | xsd:string | False | | The type of identifier of the Employee (EMP) record used for who created the patient. Valid values are: Internal, External, CID, Name, or an ID Type (IIT) record identifier.
NationalIdentifier | xsd:string | False | | The patient's national identification number. In the US, this is the patient's Social Security number.
DateOfBirth | xsd:date | False | | The patient's date of birth. This has to be in ISO format (yyyy-mm-dd).
Gender | xsd:string | False | | The patient's gender. Titles of EPT item 130 categories are valid values.
MaritalStatus | xsd:string | True | | The patient's marital status. Titles of EPT item 140 categories are valid values.
Race | xsd:string | True | | The patient's race. Titles of EPT item 145 categories are valid values.
Religion | xsd:string | True | | The patient's religion. Titles of EPT item 150 categories are valid values.
Address | AddressType | True | | The patient's address.
DepartmentIDType | xsd:string | False | | The type of identifier of the Department (DEP) record used when creating the patient. Valid values are: Internal, External, CID, Name, or an ID Type (IIT) record identifier.

Response

Name | Type | Optional | Array | Description
PatientIDs | PatientIDsType | True
Name | NameType | True | | The name of the patient.
NationalIdentifier | xsd:string | False | | The patient's national identification number. In the US, this is the patient's Social Security number.
DateOfBirth | xsd:date | False | | The patient's date of birth in ISO format (yyyy-mm-dd).
Gender | xsd:string | False | | The patient's gender. Titles of EPT item 130 categories are valid values.
MaritalStatus | xsd:string | True | | The patient's marital status. Titles of EPT item 140 categories are valid values.
Race | xsd:string | True | | The patient's race. Titles of EPT item 145 categories are valid values.
Religion | xsd:string | True | | The patient's religion. Titles of EPT item 150 categories are valid values.
Address | AddressType | True | | The patient's address.

Type: NameType

Name | Type | Optional | Array | Description
LastName | xsd:string | True | | The last name of the patient. Example: Jones
LastNameFromSpouse | xsd:string | True | | The last name of the patient's spouse.
LastNamePrefix | xsd:string | True | | The prefix for the patient's last name.
SpouseLastNameFirst | xsd:boolean | True | | This indicates if the patient spouse's last name should appear first in the hyphenated last name. Titles of ECT item 101 categories are valid values. No, Yes
GivenNameInitials | xsd:string | True | | Only used for Dutch locale name. These are the patient's initials used in place of the first name when address formally. Example: HJL.
First | xsd:string | True | | The patient's first name.
Middle | xsd:string | True | | The patient's middle name.
Title | xsd:string | True | | The patient's title. Titles of EPT item 121 categories are valid values.
Suffix | xsd:string | True | | The suffix for the patient's name. Titles of EPT item 122 categories are valid values.
Academic | xsd:string | True | | The academic suffix for the patient's name. Titles of EPT item 124 categories are valid values.
PreferredName | xsd:string | True | | The name the patient prefers to use. Example: Bob Jones
PreferredNameType | xsd:string | True | | The type of the preferred name. Titles of EPT item 127 categories are valid values. Nickname, Pseudonym
SpouseLastNamePrefix | xsd:string | True | | The prefix for the patient spouse's last name.

Type: AddressType

Name | Type | Optional | Array | Description
Street | xsd:string | True | | The patient's street address.
StreetLine2 | xsd:string | True | | Line two of the patient's street address.
HouseNumber | xsd:string | True | | Only used for Dutch locale address. The patient's house number.
City | xsd:string | True | | The city where the patient lives.
County | xsd:string | True | | The county where the patient lives. Titles of EPT item 75 categories are valid values.
State | xsd:string | True | | The state where the patient lives. Titles of EPT item 70 categories are valid values.
ZipCode | xsd:string | True | | The patient's ZIP code.
Country | xsd:string | True | | The country where the patient lives. Titles of EPT item 78 categories are valid values.
Phones | PhonesType | True
Email | xsd:string | True | | The patient's email address.

Type: PhonesType

Name | Type | Optional | Array | Description
Type | xsd:string | True | | The type of phone. Titles of EPT item 94 categories are valid values.
Number | xsd:string | True | | The patient's phone number in the format that match its type.

Type: PatientIDsType

Name | Type | Optional | Array | Description
Type | xsd:string | True | | The identifier of the ID Type (IIT) record which defines the ID type. From EPT item 2060 of Patient (EPT) record.
ID | xsd:string | True | | The actual identifier assigned of given ID type. From EPT item 2061 of Patient (EPT) record.

Errors

Code | Severity | Description | Example
PatientCreateDateOfBirthRequired | None | | Date Of Birth is a required field in the environment.
PatientCreateInvalidDateOfBirth | None | | DateOfBirth is in an incorrect format (format = yyyy-mm-dd).
PatientCreateInvalidUser | None | | UserID and UserIDType do not resolved to a valid user record.
PatientCreateUserSecurityCheckFailed | None | | User does not have security to create a patient record.
PatientCreateInvalidPatientName | None | | Patient name could not be formatted correctly with the name fields in the request.
PatientCreateUnableToAssignEnterpriseID | None | | The enterprise ID created could not be assigned to the patient record.
PatientCreateUnableToGenerateEnterpriseID | None | | An enterprise ID could not be generated for the patient record. A patient record has been created.
PatientCreateUnableToCreateRecord | None | | A patient record could not be created due to an unknown problem.
PatientCreateUnableToReserveRecordID | None | | A record ID for the patient could not be reserved.
PatientCreateLastNameRequired | None | | Last Name is a required field.
PatientCreateInvalidGender | None | | Gender cannot be resolved.
PatientCreateGenderRequired | None | | Gender is a required field in this environment.

PatientCreateNationalIdentifierRequired | None | | NationalIdenifier (SSN) is a required field in this environment.
PatientCreateInvalidDepartment | None | | DepartmentID and DepartmentIDType do not resolve to a valid department.
PatientCreateFutureDateOfBirthNotAllowed | None | | DOB provided is in the future.

Sample request

```
<PatientCreate>
  <Name>
    <LastName>Kenealy</LastName>
    <LastNameFromSpouse>Regent</LastNameFromSpouse>
    <LastNamePrefix/>
    <SpouseLastNamePrefix/>
    <SpouseLastNameFirst/>
    <GivenNameInitials/>
    <First>Jessica</First>
    <Middle/>
    <Title/>
    <Suffix/>
    <Academic/>
    <PreferredName>Jessica Kenealy</PreferredName>
    <PreferredNameType>?</PreferredNameType>
  </Name>
  <DepartmentID>1</DepartmentID>
  <DepartmentIDType>Internal</DepartmentIDType>
  <UserID>1</UserID>
  <UserIDType>Internal</UserIDType>
  <NationalIdentifier>938734634</NationalIdentifier>
  <DateOfBirth>1977-04-15</DateOfBirth>
  <Gender>Female</Gender>
  <MaritalStatus>Married</MaritalStatus>
  <Race/>
  <Religion/>
  <Address>
    <Street>1979 Milky Way</Street>
    <StreetLine2/>
    <HouseNumber/>
    <City>Verona</City>
    <County>Dane</County>
    <State>WI</State>
    <ZipCode>53539</ZipCode>
    <Country/>
    <Phones>
      <Phone>
        <Type>Home</Type>
        <Number>608-271-9000</Number>
      </Phone>
    </Phones>
    <Email>jess.kenealy@site.com</Email>
  </Address>
</PatientCreate>
```

Sample response

```
<PatientCreateResponse>
  <PatientIDs>
    <PatientID>
      <Type>EPIC</Type>
      <ID>4816</ID>
    </PatientID>
    <PatientID>
      <Type/>
      <ID>3810</ID>
    </PatientID>
  </PatientIDs>
  <Name>
    <LastName>Kenealy</LastName>
    <LastNameFromSpouse>Regent</LastNameFromSpouse>
    <First>Jessica</First>
    <PreferredName>Jessica Kenealy</PreferredName>
  </Name>
  <Address>
    <Street>1979 Milky Way</Street>
    <City>Verona</City>
    <County>Dane</County>
    <State>WI</State>
    <ZipCode>53539</ZipCode>
    <Country/>
    <Phones>
      <Phone>
        <Type>Home</Type>
        <Number>608-271-9000</Number>
      </Phone>
    </Phones>
    <Email>jess.kenealy@site.com</Email>
  </Address>
</PatientCreateResponse>
```

22.4.2 PatientLookup (2005)

File: site/apis/22-Identification-Individuals/4-Non-FHIR/376-PatientLookup-2005.html
Epic API ID | 376
FHIR version | Non-FHIR
Categories | Identification Individuals
API type | Epic Public
API group | EMPI Group
USCDI | No
Supports OAuth 2.0 | True
Supported user types | Backend Systems and Non-OAuth 2.0
Performs scope validation | False
SOAP namespace | urn:epicsystems-com:EMPI.2005-01.Services
WSDL | EMPI.wsdl
Source | https://fhir.epic.com/Specifications?api=376

Remarks

The patient search is performed using one of two matching algorithms as defined in the searchType attribute described above. The default mechanism is to use the Identity duplicate search mechanism. This mechanism employs an algorithm to weigh each of the fields passed in, where the relative weight of data can be set on the EMPI deployment. If the total weight of all the fields reaches a pre-defined threshold, the patient is selected. The Foundations search mechanism identifies patients by name, partial name, or ID. The other fields passed in are used as filters to further refine the search.

The result returned is a list of zero or more patients that match the search along with a large array of demographics fields.

Request

Name | Type | Optional | Array | Description
query | QueryType | False

Response

Name | Type | Optional | Array | Description
Result | ResultType | False

Type: PatientIDType

Name | Type | Optional | Array | Description
idType | xsd:string | True | | Type for the provided ID (Internal, External, CID, Identity ID Type Descriptor (I IIT 600), NationalID, CSN, MyChart login name (WPR 110), or FHIR). If the ID type is not provided, the default is Internal.

Type: PatientIDsType

Name | Type | Optional | Array | Description
PatientID | PatientIDType | False | | The patient MRN and ID Type.

Type: AddressType

Name | Type | Optional | Array | Description
type | xsd:string | True | | The type of address: Permanent Temporary
Street | xsd:string | False | | The number and name of the street where the patient resides.
City | xsd:string | False | | The city where the patient resides.
County | xsd:string | False | | The county where the patient resides.
State | xsd:string | False | | The state where the patient resides.
ZipCode | xsd:string | False | | The ZIP code in which the patient resides.
Country | xsd:string | False | | The country where the patient resides.
Email | xsd:string | False | | The e-mail address of the patient.
Phones | PhonesType | False | | The phone number(s) of the patient.

Type: PhonesType

Name | Type | Optional | Array | Description
Phone | xsd:string | False | | The phone number of the patient. Extensions are shown after the phone number with an "x" followed by the extension. For example, 608-555-4352x1234.

Type: Phone

Name | Type | Optional | Array | Description
type | xsd:string | True | | Indicates the type of phone number: HOME - the home phone number of the patient WORK - the work phone number of the patient

Type: EmploymentInformationType

Name | Type | Optional | Array | Description

Name | xsd:string | False | | The name of the patient's employer.
Occupation | xsd:string | False | | The occupation of the patient.
Phone | xsd:string | False | | The phone number of the patient's employer.

Type: EmergencyContactType

Name | Type | Optional | Array | Description
legalGuardian | xsd:string | False | | Indicates whether the emergency contact is the legal guardian of the patient: 1 - indicates "yes" 2 - indicates "no"
Name | xsd:string | False | | The name of the emergency contact.
Relation | xsd:string | False | | The relationship of the emergency contact to the patient.
Phones | PhonesType | False

Type: PCPsType

Name | Type | Optional | Array | Description
PrimaryCarePhysician | PCPType | True | Yes | The primary care physician(s) information.

Type: PCPType

Name | Type | Optional | Array | Description
type | xsd:string | True | | The type of primary care provider (for example, General, Obstetrics/Gynecology).
ID | xsd:string | False | | The primary care provider's ID.
Name | xsd:string | False | | The name of the primary care provider.

Type: ResultType

Name | Type | Optional | Array | Description
Patient | PatientType | True | Yes

Type: PatientType

Name | Type | Optional | Array | Description
Name | xsd:string | False | | The name of the patient.
PatientIDs | PatientIDsType | False | | The list of patient MRNs and ID Types.
SocialSecurityNumber | xsd:string | False | | The Social Security number of the patient.
DateOfBirth | xsd:string | False | | The date of birth of the patient.
Gender | xsd:string | False | | The gender of the patient.
PatientStatus | xsd:string | False | | The status of the patient: Alive Deceased
MaritalStatus | xsd:string | False | | The current marital status of the patient.
Address | AddressType | False | | The address(es) of the patient.
EmploymentInformation | EmploymentInformationType | False | | The employment information of the patient.
EmploymentInformationType | xsd.complex | False
EmergencyContact | EmergencyContactType | False | | The emergency contact information for the patient.
HomeDeployment | xsd:string | False | | The home deployment of the patient record.
PrimaryCarePhysicians | PCPsType | False | | Indicates the patient's PCP.
PCPsType | | False

Type: QueryType

Name | Type | Optional | Array | Description
searchType | xsd:string | True | | Description: Indicates the type of search to perform. The following options can be used: 0 - Uses Identity's duplicate patient selection algorithm 1 - Uses the Foundations search mechanism where the name field is a partial match and other fields are exact matches The Identity duplicate patient search is the default.
regionRestriction | xsd:string | True | | Limits search for patients to a region indicated here.
IDTypeMnemonic | xsd:string | True | | Specifies the mnemonic of the ID type to return for a patient
Name | xsd:string | False | | The name of the patient to be looked up.
PatientID | PatientIDType | False | | The MRN of the patient to be looked up.
SocialSecurityNumber | xsd:string | False | | The Social Security number of the patient to be looked up.
DateOfBirth | xsd:string | False | | The date of birth of the patient to be looked up.
Gender | xsd:string | False | | The gender of the patient to be looked up.

Sample request

```
<PatientLookup xmlns="urn:epicsystems-com:EMPI.2005-01.Services">
  <query IDTypeMnemonic="NORTH">
    <Name>THUSOR,REBECCA J</Name>
    <PatientID idType="NORTH">3031641</PatientID>
    <SocialSecurityNumber>297-56-4856</SocialSecurityNumber>
    <DateOfBirth>1961-09-21T05:00:00ZZ</DateOfBirth>
    <Gender>Female</Gender>
  </query>
</PatientLookup>
```

Sample response

```
<PatientLookupResponse xmlns="urn:epicsystems-com:EMPI.2005-01.Services">
  <Result>
```

```
    <Patient>
      <Name>Rebecca J Thusor</Name>
      <PatientIDs>
        <PatientID idType="CID">303Z10012472</PatientID>
        <PatientID idType="EPI">130980</PatientID>
        <PatientID idType="NORTH">3031641</PatientID>
      </PatientIDs>
      <SocialSecurityNumber>297-56-4856</SocialSecurityNumber>
      <DateOfBirth>1961-09-21T05:00:00Z</DateOfBirth>
      <Gender>Female</Gender>
      <PatientStatus>Alive</PatientStatus>
      <MaritalStatus>Married</MaritalStatus>
      <Address type="Permanent">
        <Street>1442 Elm St</Street>
        <City>ARLINGTON</City>
        <County>ARLINGTON</County>
        <State>Virginia</State>
        <ZipCode>22222</ZipCode>
        <Country>United States of America</Country>
        <Email>rthusor@forta.com</Email>
        <Phones>
          <Phone type="HOME">608-555-0547</Phone>
          <Phone type="WORK">608-555-0564</Phone>
        </Phones>
      </Address>
      <Address type="Temporary">
        <Street>1405 Washington St</Street>
        <City>CAMDEN</City>
        <County/>
        <State>Ohio</State>
        <ZipCode>45311</ZipCode>
        <Country>United States of America</Country>
        <Email/>
        <Phones>
          <Phone>608-234-3737</Phone>
        </Phones>
      </Address>
      <EmploymentInformation>
        <Name>Charcoal Inn</Name>
        <Occupation>Cook</Occupation>
        <Phone>920-555-1147</Phone>
      </EmploymentInformation>
      <EmergencyContact legalGuardian="2">
        <Name>THUSOR,MICHAEL</Name>
        <Relation>Spouse</Relation>
        <Phones>
          <Phone type="HOME">608-555-0547</Phone>
          <Phone type="WORK">608-555-3477</Phone>
        </Phones>
      </EmergencyContact>
      <HomeDeployment>urn:epicsystems-com:deployment.cedev.north</HomeDeployment>
      <PrimaryCarePhysicians>
        <PCPType type="1">
          <ID>6061965</ID>
          <Name>Sally Speasesw</Name>
        </PCPType>
      </PrimaryCarePhysicians>
    </Patient>
  </Result>
</PatientLookupResponse>
```

22.4.3 PatientLookup (2009)

File: site/apis/22-Identification-Individuals/4-Non-FHIR/377-PatientLookup-2009.html
Epic API ID | 377
FHIR version | Non-FHIR
Categories | Identification Individuals
API type | Epic Public
API group | EMPI Group
USCDI | No
Supports OAuth 2.0 | True
Supported user types | Backend Systems and Non-OAuth 2.0
Performs scope validation | False
SOAP namespace | urn:epicsystems-com:EMPI.2009.Services
WSDL | Epic.Community.EMPI/Patient.svc?wsdl
Source | https://fhir.epic.com/Specifications?api=377

Request

Name | Type | Optional | Array | Description
PatientID | PatientID | True | | Patient's identifier.
Name | string | True | | Patient's name.
DateOfBirth | dateTime | True | | Patient's date of birth.
SocialSecurityNumber | string | True | | Patient's SSN.

Gender | string | True | | Patient's gender.
SearchType | string | True | | Indicates the method of searching the patient. Default is DuplicateSearch. These are the options: DuplicateSearch. Uses Identity's duplicate patient selection algorithm. PartialNameLookup. Uses the Foundations search mechanism where the name field is a partial match and other fields are exact matches.
RegionRestriction | string | True | | Limits the search for patients to a region indicated here.
IDTypeMnemonic | string | True | | Indicates the type of MRN to return.

Response

Name | Type | Optional | Array | Description
PatientLookupResult | PatientLookupResult | False | | Result returned by the web service.

Type: PatientID

Name | Type | Optional | Array | Description
ID | string | False | | Patient's ID (EPT ID).
Type | string | False | | Type for the provided ID (Internal, External, CID, Identity ID Type Descriptor (I IIT 600), NationalID, CSN, MyChart login name (WPR 110), or FHIR). If the ID type is not provided, the default is Internal.

Type: PatientLookupResult

Name | Type | Optional | Array | Description
Patients | Patient | False | Yes | A list of matching patients returned by the web service.

Type: Patient

Name | Type | Optional | Array | Description
Addresses | Address | False | Yes | Patient's address.
DateOfBirth | string | False | | Patient's date of birth.
EmergencyContact | EmergencyContact | False | | Emergency contact for the patient.
EmploymentInformation | EmploymentInformation | False | | Information about the patient's employer.
Gender | string | False | | Patient's gender.
HomeDeployment | string | False | | The home deployment of the patient record.
IDs | PatientID | False | Yes | Patient's IDs and ID types.
MaritalStatus | string | False | | Patient's current marital status.
Name | string | False | | Patient's name.
NameComponents | NameComponents | False | | Various information related to patient's name.
PersonalCareProviders | PersonalCareProvider | False | Yes | Indicates patient's PCP.
SocialSecurityNumber | string | False | | The patient's SSN.
Status | string | False | | The patient's status (Alive or Deceased).

Type: Address

Name | Type | Optional | Array | Description
City | string | False | | City.
Country | string | False | | Country.
County | string | False | | County.
Email | string | False | | E-mail address.
PhoneNumbers | PhoenInfo | False | Yes | Patient's phone numbers.
State | string | False | | State.
Street | string | False | | Street address.
Type | string | False | | Type of address (e.g. permanent or temporary).
ZipCode | string | False | | Zip code.

Type: EmergencyContact

Name | Type | Optional | Array | Description
LegalGuardian | string | False | | Indicates whether the emergency contact is the legal guardian of the patient: 1 - Yes 2 - No
Name | string | False | | Name of the emergency contact.
PhoneNumbers | PhoneInfo | False | Yes | Phone numbers of the emergency contact.
Relation | string | False | | The relationship of the emergency contact to the patient.

Type: EmploymentInformation

Name | Type | Optional | Array | Description
EmployerName | string | False | | Name of the patient's employer.
Occupation | string | False | | Patient's occupation.
PhonesNumbers | PhoneInfo | False | Yes | Patient's business phone numbers.

Type: PhoneInfo

Name | Type | Optional | Array | Description
PhoneNumber | string | False | | Phone number.
PhoneType | string | False | | Phone number type (e.g. work phone or home phone).

Type: PatientID

Name | Type | Optional | Array | Description
ID | string | False | | Patient's ID (EPT ID).
Type | string | False | | Patient's ID type (Internal, External, CID or IIT identifiers).

Type: NameComponents

Name | Type | Optional | Array | Description
Academic | string | False | | Academic title to display with the person's name, such as "PhD".
FirstName | string | False | | Person's first name.
FullLastName | string | False | | Person's full, formatted last name.
GivenNameInitials | string | False | | Initials for the person's given names.
History | string | False | | The history of the record name.
LastName | string | False | | Person's last name.
LastNameFromSpouse | string | False | | Part of the person's last name from their spouse.
LastNamePrefix | string | False | | Person's last name prefix.
MiddleName | string | False | | Person's middle name.
PreferredName | string | False | | Name the person prefers to be called.
PreferredNameType | string | False | | Type of the preferred name, which can indicate whether the preferred name is a nickname or a full alias.
SpouceLastNameFirst | string | False | | Indicates whether the person's last name and spouse's last name items should be swapped when formatting the name for display.
SpouceLastNamePrefix | string | False | | Part of the person's last name that is the prefix for the spouse's last name.
Suffix | string | False | | Suffix to display with the person's last name, such as "Jr." or "II".
Title | string | False | | Title to show with the person's last name, such as "Mr." or "Mrs.".

Type: PersonalCareProvider

Name | Type | Optional | Array | Description
ID | string | False | | PCP's ID.
Name | string | False | | PCP's name.
Type | string | False | | Type of primary care provider (e.g. General, Obstetrics).

Sample request

```
<PatientLookup xmlns="urn:epicsystems-com:EMPI.2009.Services">
  <PatientID>
    <ID>AZ3094900</ID>
    <Type>CID</Type>
  </PatientID>
  <Name>Smith, Rebecca</Name>
  <DateOfBirth>1978-03-29</DateOfBirth>
  <SocialSecurityNumber>000-12-1313</SocialSecurityNumber>
  <Gender>Female</Gender>
  <SearchType>1</SearchType>
  <RegionRestriction/>
  <IDTypeMnemonic>INTERNAL</IDTypeMnemonic>
</PatientLookup>
```

Sample response

```
<PatientLookupResponse xmlns="urn:epicsystems-com:EMPI.2009.Services">
  <PatientLookupResult xmlns:i="http://www.w3.org/2001/XMLSchema-instance">
    <Patients>
      <Patient>
        <Addresses>
          <Address>
            <City>VERONA</City>
            <Country>United States of America</Country>
            <County>DANE</County>
            <Email>rsmith@fake.com</Email>
            <PhoneNumbers>
              <PhoneInfo>
                <PhoneNumber>608-271-9000</PhoneNumber>
                <PhoneType>HOME</PhoneType>
              </PhoneInfo>
            </PhoneNumbers>
            <State>Wisconsin</State>
            <Street>1979 Milky Way</Street>
            <Type>Permanent</Type>
            <ZipCode>53593</ZipCode>
          </Address>
        </Addresses>
        <DateOfBirth>1980-03-29</DateOfBirth>
        <EmergencyContact>
          <LegalGuardian>2</LegalGuardian>
          <Name>Bobby Smith</Name>
          <PhoneNumbers>
            <PhoneInfo>
              <PhoneNumber>608-555-9595</PhoneNumber>
              <PhoneType>HOME</PhoneType>
            </PhoneInfo>
```

```
            <PhoneInfo>
              <PhoneNumber>608-555-1212</PhoneNumber>
              <PhoneType>WORK</PhoneType>
            </PhoneInfo>
          </PhoneNumbers>
          <Relation>Spouse</Relation>
        </EmergencyContact>
        <EmploymentInformation>
          <EmployerName>Starbucks</EmployerName>
          <Occupation>Server</Occupation>
          <PhonesNumbers>
            <PhoneInfo>
              <PhoneNumber>888-785-9000</PhoneNumber>
              <PhoneType/>
            </PhoneInfo>
          </PhonesNumbers>
        </EmploymentInformation>
        <Gender>Female</Gender>
        <HomeDeployment/>
        <IDs>
          <PatientID>
            <ID/>
            <Type>CID</Type>
          </PatientID>
          <PatientID>
            <ID>760584</ID>
            <Type>EPI</Type>
          </PatientID>
        </IDs>
        <MaritalStatus/>
        <Name>Rebecca K Smith</Name>
        <NameComponents>
          <Academic/>
          <FirstName>Rebecca</FirstName>
          <FullLastName/>
          <GivenNameInitials/>
          <History>SMITH,REBECCA K[03/29/2012</History>
          <LastName>Smith</LastName>
          <LastNameFromSpouse/>
          <LastNamePrefix/>
          <MiddleName>K</MiddleName>
          <PreferredName i:nil="true"/>
          <PreferredNameType/>
          <SpouceLastNameFirst>No</SpouceLastNameFirst>
          <SpouceLastNamePrefix/>
          <Suffix/>
          <Title>Miss</Title>
        </NameComponents>
        <PersonalCareProviders>
          <PersonalCareProvider>
            <ID/>
            <Name>Brandon Smith</Name>
            <Type>2</Type>
          </PersonalCareProvider>
          <PersonalCareProvider>
            <ID/>
            <Name>Marty Seeger, RPH</Name>
            <Type>1</Type>
          </PersonalCareProvider>
        </PersonalCareProviders>
        <SocialSecurityNumber>000-12-1313</SocialSecurityNumber>
        <Status>Alive</Status>
      </Patient>
    </Patients>
  </PatientLookupResult>
</PatientLookupResponse>
```

22.4.4 PatientLookup (2012)

File: site/apis/22-Identification-Individuals/4-Non-FHIR/150-PatientLookup-2012.html
Epic API ID | 150
FHIR version | Non-FHIR
Categories | Identification Individuals
API type | Epic Public
API group | EMPI Group
USCDI | No
HTTP method | POST
URL template | api/epic/2012/EMPI/Patient/PATIENTLOOKUP/Lookup
Supports OAuth 2.0 | True
Supported user types | Backend Systems and Non-OAuth 2.0, Clinicians or Administrative Users
Performs scope validation | False
SOAP namespace | urn:Epic-com:EMPI.2012.Services.Patient
WSDL | Epic.EMPI.GeneratedServices/Patient.svc?wsdl
Source | https://fhir.epic.com/Specifications?api=150

Remarks

The search is performed using the algorithm specified in the SearchType field. The StandardSearch search type identifies patients by name, partial name, ID, or some other primary key, and uses other fields as filters. The DuplicateSearch search type assigns weights for criteria that match a patient we are considering in the search. If the total weight is above a pre-defined threshold, that patient is included in the search results.

For a StandardSearch, at least one of these fields is required:

* PatientID

* Name

* DateOfBirth

* NationalIdentifier

* AddressRequest.Email

* AddressRequest.PhoneNumbers

All other items are optional and can be used as filters to further narrow down the results. For a DuplicateSearch, the required items depend on the configuration of the Duplicate Configuration record listed in the HDF item IDC Record for Patient Searches. Contact your Identity Technical Services representative for more information.

Request parameters

Name | Type | Optional | Array | Cardinality | Description
Address | AddressRequest | True
Address.City | String | True
Address.Country | String | True
Address.County | String | True
Address.District | String | True
Address.Email | String | True
Address.HouseNumber | String | True
Address.PhoneNumbers | String | True
Address.PostalCode | String | True
Address.State | String | True
Address.Street | String | True
Address.Type | String | True
DateOfBirth | String | True
FallBackToHistoricalMRN | Boolean | True
Name | String | True
NationalIdentifier | String | True
PatientID | String | True
PatientIDType | String | True
SearchType | String | True
ServiceAreaID | String | True
ServiceAreaIDType | String | True
Sex | String | True
UserID | String | False
UserIDType | String | True

Response elements

Name | Type | Optional | Array | Cardinality | Description
Patients | Patient | False | Yes
Patients.Addresses | Address | False | Yes
Patients.Addresses.City | String | True
Patients.Addresses.Country | String | True
Patients.Addresses.County | String | True
Patients.Addresses.District | String | True
Patients.Addresses.Email | String | True
Patients.Addresses.HouseNumber | String | True
Patients.Addresses.PhoneNumbers | PhoneInfo | True | Yes
Patients.Addresses.PhoneNumbers.Number | String | False
Patients.Addresses.PhoneNumbers.Type | String | False
Patients.Addresses.PostalCode | String | True
Patients.Addresses.State | String | True
Patients.Addresses.Street | String | True
Patients.Addresses.Type | String | True
Patients.Aliases | String | False
Patients.CareTeam | CareTeamMember | False | Yes
Patients.ConfidentialName | String | False
Patients.DateOfBirth | String | False
Patients.EmergencyContacts | EmergencyContact | False | Yes
Patients.EmploymentInformation | EmploymentInformation | False
Patients.EthnicGroup | String | False

Patients.HistoricalIDs | IDType | False | Yes
Patients.HomeDeployment | String | False
Patients.IDs | IDType | False | Yes
Patients.IDs.ID | String | False
Patients.IDs.Type | String | False
Patients.MaritalStatus | String | False
Patients.Name | String | False
Patients.NameComponents | NameComponents | False
Patients.NameComponents.Academic | String | False
Patients.NameComponents.FirstName | String | False
Patients.NameComponents.GivenNameInitials | String | False
Patients.NameComponents.LastName | String | False
Patients.NameComponents.LastNameFromSpouse | String | False
Patients.NameComponents.LastNamePrefix | String | False
Patients.NameComponents.MiddleName | String | False
Patients.NameComponents.PreferredName | String | False
Patients.NameComponents.PreferredNameType | String | False
Patients.NameComponents.SpouseLastNameFirst | String | False
Patients.NameComponents.Suffix | String | False
Patients.NameComponents.Title | String | False
Patients.NationalIdentifier | String | False
Patients.Race | String | False
Patients.Rank | String | False
Patients.Sex | String | False
Patients.Status | String | False

Errors

Code | Severity | Description | Example
NOT-LICENSED | None | | This feature is not licensed.
INVALID-PATIENT-ID-TYPE | None | | Patient ID type is invalid.
INVALID-DATE-OF-BIRTH | None | | Date of birth is invalid.
INVALID-SEX | None | | Sex is invalid, or could not be resolved to a unique value.
INVALID-SEARCH-TYPE | None | | Search type is invalid.
INVALID-SERVICE-AREA | None | | Service area is invalid.
INVALID-STATE | None | | State is invalid, or could not be resolved to a unique value.
INVALID-COUNTY | None | | County is invalid, or could not be resolved to a unique value.
INVALID-COUNTRY | None | | Country is invalid, or could not be resolved to a unique value.
INVALID-NATIONAL-IDENTIFIER | None | | National identifier is invalid.
INVALID-PHONE-NUMBER | None | | Phone number is invalid.
INSUFFICIENT-CRITERIA | None | | Insufficient criteria were provided to perform the search.
INVALID-USER | None | | User is invalid, or was not provided.
INVALID-DISTRICT | None | | District is invalid, or could not be resolved to a unique value.
INVALID-POSTAL-CODE | None | | Postal code is invalid.
INVALID-EMAIL-ADDRESS | None | | E-mail address is invalid.

Sample request

```
<PatientLookup xmlns="urn:Epic-com:EMPI.2012.Services.Patient">
  <PatientID>E1135745</PatientID>
  <PatientIDType>EPI</PatientIDType>
  <Name>Smith, John</Name>
  <DateOfBirth>1978-09-05</DateOfBirth>
  <NationalIdentifier>778-84-4123</NationalIdentifier>
  <Sex>M</Sex>
  <SearchType>StandardSearch</SearchType>
  <ServiceAreaID>20000</ServiceAreaID>
  <ServiceAreaIDType>SAID</ServiceAreaIDType>
  <FallBackToHistoricalMRN>false</FallBackToHistoricalMRN>
  <UserID>54687</UserID>
  <UserIDType>EXTERNAL</UserIDType>
  <Address>
    <City>Madison</City>
    <Country>USA</Country>
    <County>Dane</County>
    <District/>
    <Email>john.smith@jsenterprises.com</Email>
    <HouseNumber/>
    <PhoneNumbers>
      <string xmlns="http://schemas.microsoft.com/2003/10/Serialization/Arrays">608-841-6541</string>
    </PhoneNumbers>
    <PostalCode>53717</PostalCode>
    <State>WI</State>
    <Street>
      <string xmlns="http://schemas.microsoft.com/2003/10/Serialization/Arrays">7155 Wisconsin Lane</string>
    </Street>
    <Type>PERMANENT</Type>
  </Address>
```

```
</PatientLookup>
```

Sample response

```
<PatientLookupResult xmlns="urn:Epic-com:EMPI.2012.Services.Patient">
  <Patients>
    <Patient>
      <Addresses>
        <Address>
          <City>Madison</City>
          <Country>United States of America</Country>
          <County>DANE</County>
          <District/>
          <Email>
            <string
    xmlns="http://schemas.microsoft.com/2003/10/Serialization/Arrays">john.smith@jsenterprises.com</string>
          </Email>
          <HouseNumber/>
          <PhoneNumbers>
            <PhoneInfo>
              <Number>608-841-6541</Number>
              <Type>Home</Type>
            </PhoneInfo>
            <PhoneInfo>
              <Number>608-443-1121</Number>
              <Type>Work</Type>
            </PhoneInfo>
          </PhoneNumbers>
          <PostalCode>53717</PostalCode>
          <State>WI</State>
          <Street>
            <string xmlns="http://schemas.microsoft.com/2003/10/Serialization/Arrays">7155 Wisconsin Lane</string>
          </Street>
          <Type>PERMANENT</Type>
        </Address>
      </Addresses>
      <Aliases>
        <string xmlns="http://schemas.microsoft.com/2003/10/Serialization/Arrays">Smith, Johnny</string>
      </Aliases>
      <CareTeam>
        <CareTeamMember>
          <IDs>
            <IDType>
              <ID>55674</ID>
              <Type>SERID</Type>
            </IDType>
            <IDType>
              <ID>5143499748</ID>
              <Type>NPIID</Type>
            </IDType>
          </IDs>
          <Name>Johnson, Steve</Name>
          <Type>General</Type>
        </CareTeamMember>
      </CareTeam>
      <DateOfBirth>1978-09-05</DateOfBirth>
      <EmergencyContacts>
        <EmergencyContact>
          <LegalGuardian>No</LegalGuardian>
          <Name>Smith, Jane</Name>
          <PhoneNumbers>
            <PhoneInfo>
              <Number>608-945-6654</Number>
              <Type>Home</Type>
            </PhoneInfo>
          </PhoneNumbers>
          <Relation>Sister</Relation>
        </EmergencyContact>
      </EmergencyContacts>
      <EmploymentInformation>
        <EmployerName>John Smith Enterprises</EmployerName>
        <Occupation>Engineer</Occupation>
        <PhoneNumbers>
          <PhoneInfo>
            <Number>608-656-7189</Number>
            <Type>Main</Type>
          </PhoneInfo>
        </PhoneNumbers>
      </EmploymentInformation>
      <EthnicGroup>Caucasian</EthnicGroup>
      <HistoricalIDs>
        <IDType>
          <ID>9135462</ID>
          <Type>DEPID</Type>
        </IDType>
      </HistoricalIDs>
      <IDs>
        <IDType>
          <ID>E32657484</ID>
```

```
          <Type>EPI</Type>
        </IDType>
        <IDType>
          <ID>9135463</ID>
          <Type>DEPID</Type>
        </IDType>
      </IDs>
      <MaritalStatus>Single</MaritalStatus>
      <Name>Smith, John</Name>
      <NameComponents>
        <Academic/>
        <FirstName>John</FirstName>
        <GivenNameInitials/>
        <LastName>Smith</LastName>
        <LastNameFromSpouse/>
        <LastNamePrefix/>
        <MiddleName/>
        <PreferredName/>
        <PreferredNameType/>
        <SpouseLastNameFirst/>
        <SpouseLastNamePrefix/>
        <Suffix/>
        <Title/>
      </NameComponents>
      <NationalIdentifier>xxx-xx-4123</NationalIdentifier>
      <Race>
        <string xmlns="http://schemas.microsoft.com/2003/10/Serialization/Arrays">White</string>
      </Race>
      <Rank>99.9</Rank>
      <Sex>Male</Sex>
      <Status>Alive</Status>
    </Patient>
  </Patients>
</PatientLookupResult>
```

22.4.5 UpdateUserDemographics

File: site/apis/22-Identification-Individuals/4-Non-FHIR/126-UpdateUserDemographics.html
Epic API ID | 126
FHIR version | Non-FHIR
Categories | Identification Individuals
API type | Epic Public
API group | Personnel Management Group
USCDI | No
HTTP method | POST
URL template | api/epic/2011/Common/User/UPDATEUSERDEMOGRAPHICS/User/Demographics?UserID={UserID}&UserIDType={UserIDType}&EmailAddress={EmailAddress}&PhoneNumber={PhoneNumber}&FaxNumber={FaxNumber}&UpdateLinkedProviderRecord={UpdateLinkedProviderRecord}
Supports OAuth 2.0 | True
Supported user types | Backend Systems and Non-OAuth 2.0
Performs scope validation | False
SOAP namespace | urn:Epic-com:Common.2011.Services.User
WSDL | Epic.Common.GeneratedServices/User.svc?wsdl
Source | https://fhir.epic.com/Specifications?api=126

Remarks

You can't use this service to update a Provider (SER) record.

This service will update the user record only if the Type of EMP Record is User or null. Also, the EMP record will be updated only if the service is executed on the deployment that owns the EMP record.

This service will not update any demographic information if any of the demographic properties (in the request) are controlled by a template or a sub-template.

Request parameters

Name | Type | Optional | Array | Cardinality | Description
Address | Address | True | | | User's address.
Address.City | String | False | | | City in the address.
Address.Country | String | True | | | Country in the address.
Address.County | String | True | | | County in the address
Address.District | String | True | | | District in the address.
Address.HouseNumber | String | True | | | House number in the address.
Address.Lines | String | True | | | An array that contains street address.
Address.State | String | True | | | State in the address.
Address.ZipCode | String | True | | | Zip code in the address.
EmailAddress | String | True | | | User's new e-mail address.
FaxNumber | String | True | | | Do not use this element. The fax number refers to a provider's fax number, but you can't use this web service to update a Provider record.

PhoneNumber | String | True | | | User's new phone number.
UpdateLinkedProviderRecord | Boolean | True | | | Do not use this element. You can't update Provider records using this web service.
UserID | String | False | | | Identifier for the user whose record is being updated.
UserIDType | String | False | | | Type of identifier provided in UserID. You can specify Internal, External, CID or SystemLogin.

Response elements

Name | Type | Optional | Array | Cardinality | Description
Success | Boolean | False | | | A boolean indicating whether the User record was updated successfully.

Errors

Code | Severity | Description | Example
NO-USER-FOUND | None | | When no EMP record is found for the provided user ID and ID type
NO-USER-ID | None | | When no user ID is provided
NO-USER-ID-TYPE | None | | When no user ID type is provided
INVALID-COUNTY | None | | When an invalid value is provided for the input parameter 'County'
INVALID-STATE | None | | When an invalid value is provided for the input parameter 'State'
INVALID-DISTRICT | None | | When an invalid value is provided for the input parameter 'District'
INVALID-COUNTRY | None | | When an invalid value is provided for the input parameter 'Country'
INVALID-RECORD-TYPE | None | | When the EMP record (updated by the service) is not of type 'User' (I EMP 75)
INVALID-SER-ID | None | | When no EMP record is found for the provided user ID and ID type
SER-LOCK-FAILED | None | | Cannot obtain lock on the linked provider's record. You shouldn't receive this warning because you can't update a Provider (SER) record using this web service.
EMP-LOCK-FAILED | None | | When no EMP record is found for the provided user ID and ID type
INVALID-USER-DEPLOYMENT | None | | The selected user cannot be updated because the record is owned by a different deployment.
SUBTEMPLATE-ITEM:Property_Name | None | | A property can be modified through sub-template (I EMP 9201) only. 'Property_Name' is the name of the request property. E.g., SUBTEMPLATE-ITEM:CITY, SUBTEMPLATE-ITEM:STATE, SUBTEMPLATE-ITEM:COUNTRY
TEMPLATE-ITEM:Property_Name | None | | When no EMP record is found for the provided user ID and ID type

Sample request

```
<UpdateUserDemographics xmlns="urn:Epic-com:Common.2011.Services.Utility">
  <UserID>9054</UserID>
  <UserIDType>External</UserIDType>
  <EmailAddress>mjones@mail.com</EmailAddress>
  <PhoneNumber>608-555-3434</PhoneNumber>
  <Address>
    <City>Madison</City>
    <Country>USA</Country>
    <County>Dane</County>
    <District/>
    <Lines>
      <string>1979 Milky Way</string>
    </Lines>
    <State>WI</State>
    <ZipCode>53719</ZipCode>
  </Address>
</UpdateUserDemographics>
```

Sample response

```
<UpdateUserDemographicsResult xmlns="urn:Epic-com:Common.2011.Services.User">
  <Success>true</Success>
</UpdateUserDemographicsResult>
```