Epic-FHIR — API category: Infrastructure Printers (sections 25 – 25.1.3)

Source: Epic on FHIR (fhir.epic.com) documentation, mirrored 2026-11. Text-only edition for AI ingestion (NotebookLM); pages follow the source order (its table of contents when one exists).

25 API category: Infrastructure Printers

File: site/apis/25-Infrastructure-Printers/index.html

Non-FHIR (3)

API | Method | URL template | Type
PrintTestPage | POST | api/epic/2015/Core/Utility/PrintTestPage/PrintTestPage?ID={ID}&PrinterIDType={PrinterIDType}&PrintoutType={PrintoutType} | Epic Public
PrintTestPageToTray | POST | /api/epic/2021/Core/Utility/PrintTestPageToTray/PrintTestPageToTray?ID={ID}&PrinterIDType={PrinterIDType}&TrayName={TrayName} | Epic Public
UpdatePrintJobStatus | POST | api/epic/2017/Printing/EPS/UpdatePrintJobStatus | Epic Public

25.1 Infrastructure Printers: Non-FHIR

File: site/apis/25-Infrastructure-Printers/1-Non-FHIR/index.html

* PrintTestPage
* PrintTestPageToTray
* UpdatePrintJobStatus

25.1.1 PrintTestPage

File: site/apis/25-Infrastructure-Printers/1-Non-FHIR/380-PrintTestPage.html
Epic API ID | 380
FHIR version | Non-FHIR
Categories | Infrastructure Printers
API type | Epic Public
API group | Printing/Faxing Group
USCDI | No
HTTP method | POST
URL template | api/epic/2015/Core/Utility/PrintTestPage/PrintTestPage?ID={ID}&PrinterIDType={PrinterIDType}&PrintoutType={PrintoutType}
Supports OAuth 2.0 | True
Supported user types | Backend Systems and Non-OAuth 2.0
Performs scope validation | False
SOAP namespace | urn:Epic-com:Core.2015.Services.Utility
WSDL | Epic.Core.GeneratedServices/Utility.svc?wsdl
Source | https://fhir.epic.com/Specifications?api=380

Request parameters

Name | Type | Optional | Array | Cardinality | Description
Copies | Int32 | True
ID | String | False
PrinterIDType | String | True
PrintoutType | String | True

Errors

Code | Severity | Description | Example
NO-PRINTER-ID | None | NO-PRINTER-ID | Printer ID is required but not provided.
INVALID-ID-TYPE | None | INVALID-ID-TYPE | Printer ID type is invalid.
NO-PRINTER-FOUND | None | NO-PRINTER-FOUND | No printer is found with the provided ID and ID type.
INVALID-PRINTOUT-TYPE | None | INVALID-PRINTOUT-TYPE | PrintoutType is invalid.
undefined | None | FAX-DEVICE-NOT-ALLOWED | Fax devices are not allowed.
undefined | None | DOWNTIME-DEVICE-NOT-ALLOWED | Downtime devices are not allowed

Sample request

```
<PrintTestPage xmlns="urn:Epic-com:Core.2015.Services.Utility">
  <ID>148</ID>
  <PrinterIDType>Internal</PrinterIDType>
  <PrintoutType>Rich</PrintoutType>
  <Copies>2</Copies>
</PrintTestPage>
```

Sample response

```
<PrintTestPageResult/>
```

25.1.2 PrintTestPageToTray

File: site/apis/25-Infrastructure-Printers/1-Non-FHIR/10040-PrintTestPageToTray.html
Epic API ID | 10040
FHIR version | Non-FHIR
Categories | Infrastructure Printers
API type | Epic Public
API group | Printing/Faxing Group
USCDI | No
HTTP method | POST
URL template | /api/epic/2021/Core/Utility/PrintTestPageToTray/PrintTestPageToTray?ID={ID}&PrinterIDType={PrinterIDType}&TrayName={TrayName}
Supports OAuth 2.0 | True
Supported user types | Backend Systems and Non-OAuth 2.0
Performs scope validation | False
SOAP namespace | urn:Epic-com:Core.2021.Services.Utility
WSDL | /wcf/Epic.Core.GeneratedServices/Utility.svc?wsdl
Source | https://fhir.epic.com/Specifications?api=10040

Request parameters

Name | Type | Optional | Array | Cardinality | Description
ID | String | False
PrinterIDType | String | False
TrayName | String | False

Response elements

Name | Type | Optional | Array | Cardinality | Description
JobID | String | False

Errors

Code | Severity | Description | Example
NO-PRINTER-ID | None | | Printer ID is required but not provided.
INVALID-ID-TYPE | None | | Printer ID type is invalid.
NO-PRINTER-FOUND | None | | No printer is found with the provided ID and ID type.
INVALID-TRAY-NAME | None | | TrayName is invalid.
FAX-DEVICE-NOT-ALLOWED | None | | Test page print jobs cannot be submitted to fax devices.
DOWNTIME-DEVICE-NOT-ALLOWED | None | | Test page print jobs cannot be submitted to downtime devices.

Sample request

```
<PrintTestPageToTray xmlns="urn:Epic-com:Core.2021.Services.Utility">
  <ID>148</ID>
  <PrinterIDType>Internal</PrinterIDType>
  <TrayName>Tray 2</TrayName>
</PrintTestPageToTray>
```

Sample response

```
<PrintTestPageToTrayResult>
  <JobID>63AAEBAD07EF413BB4349BC77189B4A9</JobID>
</PrintTestPageToTrayResult>
```

25.1.3 UpdatePrintJobStatus

File: site/apis/25-Infrastructure-Printers/1-Non-FHIR/506-UpdatePrintJobStatus.html
Epic API ID | 506
FHIR version | Non-FHIR
Categories | Infrastructure Printers
API type | Epic Public
API group | Printing/Faxing Group
USCDI | No
HTTP method | POST
URL template | api/epic/2017/Printing/EPS/UpdatePrintJobStatus
Supports OAuth 2.0 | True
Supported user types | Backend Systems and Non-OAuth 2.0
Performs scope validation | False
SOAP namespace | urn:Epic-com:Printing.2017.Services.EPS
WSDL | Epic.Printing.GeneratedServices/EPS.svc/basic

Source | https://fhir.epic.com/Specifications?api=506

Request parameters

Name | Type | Optional | Array | Cardinality | Description
ErrorMessage | String | True | | | Error message as a string of up to 254 characters.
PrintJobID | String | False | | | ID of the print job.
Status | String | False | | | Status of the print job. This should be a category ID: 1-Completed 19-Failed - Fax transmission failure 22-Failed - Printer failure 45-Failed - Third party error
WarningMessage | String | True | | | Warning message as a string of up to 1000 characters.

Response elements

Name | Type | Optional | Array | Cardinality | Description
StatusUpdateSuccessful | Boolean | False | | | True if the status was updated successfully, else False.
Warning | String | True | | | Warning message.

Errors

Code | Severity | Description | Example
NO-PRINT-JOB-ID-PROVIDED | None | | No value was provided for PrintJobID. PrintJobID is a required parameter.
INVALID-PRINT-JOB-ID | None | | No print job found with given ID <Print Job ID>.
NO-STATUS-PROVIDED | None | | No value was provided for the Status parameter. Status is a required parameter.
INVALID-STATUS | None | | Status <status value> is invalid.
PRINT-JOB-LOCKED | None | | Unable to acquire lock on print job: <Print Job ID>
CHARACTER-LENGTH-EXCEEDED | None | | <Property name> entered is <number of extra characters> characters too long. The maximum length is <number of characters allowed> characters. Example: ErrorMessage entered is 684 characters too long. The maximum length is 254 characters.
JOB-STATUS-UPDATE-NOT-ALLOWED | None | | Status update is not allowed as the print job <print job ID> was not processed on node <name of node where request was received>.

Sample request

```
<UpdatePrintJobStatus xmlns="urn:Epic-com:Printing.2017.Services.EPS" xmlns:xsi="http://www.w3.org/2001/XMLSchema-
    instance">
  <!--string occurs:0,1-->
  <PrintJobID xsi:nil="false">000024F41BDA487ABFBB97BB10D6C573</PrintJobID>
  <!--string occurs:0,1-->
  <Status xsi:nil="false">45</Status>
  <!--string occurs:0,1-->
  <ErrorMessage xsi:nil="false">Universal print driver error.</ErrorMessage>
  <!--string occurs:0,1-->
  <WarningMessage xsi:nil="false">Print job re-directed to (alternate printer name)</WarningMessage>
</UpdatePrintJobStatus>
```

Sample response

```
<?xml version="1.0" encoding="utf-16"?>
<s:Envelope xmlns:s="http://schemas.xmlsoap.org/soap/envelope/">
<s:Body>
<UpdatePrintJobStatusResponse xmlns="urn:Epic-com:Printing.2017.Services.EPS">
<UpdatePrintJobStatusResult xmlns:i="http://www.w3.org/2001/XMLSchema-instance">
<StatusUpdateSuccessful>true</StatusUpdateSuccessful>
<Warning />
</UpdatePrintJobStatusResult>
</UpdatePrintJobStatusResponse>
</s:Body>
</s:Envelope>
```