Epic-FHIR — API category: Security (sections 32 – 32.3.33)

Source: Epic on FHIR (fhir.epic.com) documentation, mirrored 2026-11. Text-only edition for AI ingestion (NotebookLM); pages follow the source order (its table of contents when one exists).

32 API category: Security

File: site/apis/32-Security/index.html

R4 (4)

API | Method | URL template | Type
Consent.Read (Code Status) (R4) | GET | /api/FHIR/R4/Consent/{ID} | Industry-Standard
Consent.Read (Document) (R4) | GET | api/FHIR/R4/Consent/{ID} | Industry-Standard
Consent.Search (Code Status) (R4) | GET | /api/FHIR/R4/Consent?category={category}&patient={patient}&status={status}&subject={subject} | Industry-Standard
Consent.Search (Document) (R4) | GET;POST | api/FHIR/R4/Consent?patient={patient}&status={status}&category={category} | Industry-Standard

STU3 (4)

API | Method | URL template | Type
Consent.Read (Code Status) (STU3) | GET | /api/FHIR/STU3/Consent/{ID} | Industry-Standard
Consent.Read (Document) (STU3) | GET | /api/FHIR/STU3/Consent/{ID} | Industry-Standard
Consent.Search (Code Status) (STU3) | GET | /api/FHIR/STU3/Consent?category={category}&patient={patient}&status={status}&subject={subject} | Industry-Standard
Consent.Search (Document) (STU3) | GET | /api/FHIR/STU3/Consent?category={category}&patient={patient}&status={status}&subject={subject} | Industry-Standard

Non-FHIR (33)

API | Method | URL template | Type
ActivateUser | POST | api/epic/2012/Security/PersonnelManagement/ActivateUser/Personnel/User/Activate?UserID={UserID} | Epic Public
CreateUser (2014) | PUT | api/epic/2014/Security/PersonnelManagement/CreateUser?UserInternalID={UserInternalID}&Name={Name}&ContactDate={ContactDate}&ContactComment={ContactComment}&SystemLoginID={SystemLoginID}&LDAPOverrideID={LDAPOverrideID}&IsActive={IsActive}&StartDate={StartDate}&EndDate={EndDate}&UserAlias={UserAlias}&UserPhotoPath={UserPhotoPath}&Sex={Sex}&ReportGrouper1={ReportGrouper1}&ReportGrouper2={ReportGrouper2}&ReportGrouper3={ReportGrouper3}&Notes={Notes}&UserDictionaryPath={UserDictionaryPath}&ProviderAtLoginOption={ProviderAtLoginOption}&AuditUserID={AuditUserID}&AuditUserIDType={AuditUserIDType}&AuditUserPassword={AuditUserPassword} | Epic Public
CreateUser (2026) | PUT | /api/epic/2026/Security/PersonnelManagement/CreateUser/?UserInternalID={UserInternalID} | Epic Public
DeleteAll2FATokens | POST | api/epic/2018/Security/PersonnelManagement/DeleteAll2FATokens/DeleteAll2FATokens | Epic Public
DeleteUser | POST | api/epic/2012/Security/PersonnelManagement/DeleteUser/Personnel/User/Delete?UserID={UserID} | Epic Public
ForcePasswordChange | POST | api/epic/2012/Security/PersonnelManagement/ForcePasswordChange/Personnel/User/ForcePasswordChange?UserID={UserID} | Epic Public
GetUserPagerID | POST | api/epic/2017/Security/PersonnelManagement/GetUserPagerID/GetUserPagerID | Epic Public
InactivateUser | POST | api/epic/2012/Security/PersonnelManagement/InactivateUser/Personnel/User/Inactivate?UserID={UserID} | Epic Public
Introspect | POST | oauth2/Introspect | USCDI
Set2FATempPasscode | POST | /api/epic/2018/Security/PersonnelManagement/Set2FATempPasscode/Set2FATempPasscode?Passcode={Passcode}&ExpirationInstant={ExpirationInstant} | Epic Public
Set2FAToken | POST | /api/epic/2018/Security/PersonnelManagement/Set2FAToken/Set2FAToken?Token={Token} | Epic Public
SetDutchName | | api/epic/2013/Security/PersonnelManagement/SetDutchName/Users/DutchName?UserID={UserID}&GivenNameInitials={GivenNameInitials}&LastName={LastName} | Epic Public
SetReportSelectionCriteria | POST | api/epic/2015/Security/PersonnelManagement/SetReportSelectionCriteria?UserID={UserID}&UserIDType={UserIDType}&AuditUserID={AuditUserID}&AuditUserIDType={AuditUserIDType}&AuditUserPassword={AuditUserPassword} | Epic Public
SetUserExternalPasswords | POST | api/epic/2012/Security/PersonnelManagement/SetUserExternalPasswords/Personnel/User/ExternalPasswords?UserID={UserID} | Epic Public
SetUserPagerID | POST | api/epic/2017/Security/PersonnelManagement/SetUserPagerID/SetUserPagerID?PagerID={PagerID} | Epic Public
SetUserPassword | PUT | api/epic/2012/Security/PersonnelManagement/SetUserPassword/Personnel/User/EpicPassword?UserID={UserID} | Epic Public
UpdateAuthorizedServiceAreas | | api/epic/2017/Security/PersonnelManagement/UpdateAuthorizedServiceAreas/Personnel/User/AuthorizedServiceAreas/Update?Append={Append} | Epic Public
UpdateBIDefaultUser | POST | api/epic/2017/Security/PersonnelManagement/UpdateBIDefaultUser/User/UpdateBIDefaultUser | Epic Public
UpdateCommunityUser | POST | api/epic/2016/Security/PersonnelManagement/UpdateCommunityUser/User/UpdateCommunityUser?WebExternalIdentifier={WebExternalIdentifier}&ReceiveExternalEmail={ReceiveExternalEmail}&ReceiveGroupNotifications={ReceiveGroupNotifications}&Deactivated={Deactivated} | Epic Public
UpdateFacilityDepartmentList | | api/epic/2017/Security/PersonnelManagement/UpdateFacilityDepartmentList/Personnel/User/FacilityDepartmentList/Update?Append={Append} | Epic Public
UpdateLoginDepartments | | api/epic/2016/Security/PersonnelManagement/UpdateLoginDepartments/Personnel/User/LoginDepartments/Update | Epic Public
UpdateUser (2014) | POST | api/epic/2014/Security/PersonnelManagement/UpdateUser/Personnel/User | Epic Public
UpdateUser (2026) | POST | /api/epic/2026/Security/PersonnelManagement/UpdateUser/Personnel/User/Update`Name`ContactDate`ContactComment`SystemLoginID`LDAPOverrideID`IsActive`StartDate`EndDate`UserAlias`UserPhotoPath`Sex`ReportGrouper1`ReportGrouper2`ReportGrouper3`CategoryReportGrouper1*`CategoryReportGrouper2*`CategoryReportGrouper3*`CategoryReportGrouper4*`CategoryReportGrouper5*`CategoryReportGrouper6*`Notes`InBasketClassifications*`UserDictionaryPath`ProviderAtLoginOption`ForceContactCreation`UserComplexName***`Authentica

tionConfigurationID***`BlockStatus***`LinkedTemplatesConfig***`UserSubtemplateIDs***`EmployeeDemographics***`PrimaryManager***`UsersManagers***`UserRoleIDs***`DefaultLoginDepartmentID***`CustomUserDictionaries***`LinkedProviderID***`IdentityIDs***`ExternalIdentifiers***`Items***`UserID***`AuditUserID*** | Epic Public
UpdateUserGroups | POST | api/epic/2016/Security/PersonnelManagement/UpdateUserGroups/Personnel/User/Groups/Update | Epic Public
ViewAuthorizedServiceAreas | |
api/epic/2017/Security/PersonnelManagement/ViewAuthorizedServiceAreas/Personnel/User/AuthorizedServiceAreas/View | Epic Public
ViewBIDefaultUser | POST | api/epic/2017/Security/PersonnelManagement/ViewBIDefaultUser/User/ViewBIDefaultUser | Epic Public
ViewCommunityUser | POST | api/epic/2016/Security/PersonnelManagement/ViewCommunityUser/User/ViewCommunityUser | Epic Public
ViewCurrentReportSelectionCriteria | POST |
api/epic/2015/Security/PersonnelManagement/ViewCurrentReportSelectionCriteria/User/ViewCurrentReportSelectionCriteria?UserID={UserID} |
Epic Public
ViewFacilityDepartmentList | POST |
api/epic/2017/Security/PersonnelManagement/ViewFacilityDepartmentList/Personnel/User/FacilityDepartmentList/View | Epic Public
ViewLoginDepartments | POST | api/epic/2016/Security/PersonnelManagement/ViewLoginDepartments/Personnel/User/LoginDepartments/View |
Epic Public
ViewUser (2014) | GET | api/epic/2014/Security/PersonnelManagement/ViewUser?UserID={UserID}&UserIDType={UserIDType}&ContactDate={ContactDate}&AuditUserID={AuditUserID}&AuditUserIDType={AuditUserIDType}&AuditUserPassword={AuditUserPassword} | Epic Public
ViewUser (2026) | POST |
/api/epic/2026/Security/PersonnelManagement/ViewUser/Personnel/User/View?ContactDate={ContactDate}`UserID***`AuditUserID*** | Epic Public
ViewUserGroups | POST | api/epic/2016/Security/PersonnelManagement/ViewUserGroups/Personnel/User/Groups/View | Epic Public

32.1 Security: R4

File: site/apis/32-Security/1-R4/index.html

* Consent.Read (Code Status) (R4)
* Consent.Read (Document) (R4)
* Consent.Search (Code Status) (R4)
* Consent.Search (Document) (R4)

32.1.1 Consent.Read (Code Status) (R4)

File: site/apis/32-Security/1-R4/10258-Consent-Read-Code-Status-R4.html
Epic API ID | 10258
FHIR version | R4
Categories | Security
API type | Industry-Standard
USCDI | No
Available in inpatient and other contexts | Yes
HTTP method | GET
URL template | /api/FHIR/R4/Consent/{ID}
Supports OAuth 2.0 | True
Supported user types | Backend Systems and Non-OAuth 2.0, Clinicians or Administrative Users, Patients
Performs scope validation | False
Source | https://fhir.epic.com/Specifications?api=10258

Description

The FHIR Code Status sub-resource defines a concept around collected consent for a patient code status. A code status documents the level of medical interventions a patient consents to receiving if their heart or breathing stops. The Consent.Read interaction returns data about a specific code status for a patient.

This resource respects patient-level Break-the-Glass checks and advanced directive security checks as configured in Epic. Audit events are logged to the patient audit trail when a code status is accessed by this resource.

Request parameters

Name | Type | Optional | Array | Cardinality | Description
ID | String | False | | | The Consent FHIR ID.

Response elements

Name | Type | Optional | Array | Cardinality | Description
Consent | Resource | False
Consent.category | CodeableConcept | False | Yes | | The type of code status. Hard-coded to SNOMED code 11291000146105.
Consent.extension (also: comments) | Extension | True | Yes | | Comments entered for the code status.
Consent.extension (also: context) | Extension | False | Yes | | The context that the code status was recorded in. For example, “Outpatient, “Inpatient”, “HOV”, etc.
Consent.dateTime | String | False | | | Date and time that the code status was created.
Consent.id | String | False | | | The Consent FHIR ID.
Consent.identifier | Identifier | False | Yes | | ID of the order that recorded the code status.
Consent.patient | Reference | False | | | FHIR reference for the Patient the code status applies to.
Consent.performer | Reference | True | Yes | | ID and name of the ordering provider.
Consent.policy | BackboneElement | True | Yes | | The policy of the code status.

Consent.policy.extension (also: data-absent-reason) | Extension | False | Yes | | Always set to "http://hl7.org/fhir/StructureDefinition/data-absent-reason".

Consent.scope | CodeableConcept | False | | | The scope of the code status.

Consent.sourceReference | Reference | True | | | A FHIR reference.

Consent.status | code | False | | | The state of the code status for a patient. This value follows the specification of the FHIR ConsentState value set and will always be either ‘active’ or ‘inactive’.

Consent.verification | Verification | False | Yes | | Shows whether this consent has been verified by the patient or their family.

Consent.verification.verificationDate | String | True | | | The date that a patient verified their consent.

Consent.verification.verified | Boolean | True | | | Whether or not this consent has been verified. Returns true if either VerifiedWith or VerificationDate elements are answered.

Sample request

```
https://hostname/instance/api/FHIR/R4/Consent/e4.SVLsY78WgkKb7v7e4ygA3
```

Sample response


```
{
  "resourceType": "Consent",
  "id": "e4.SVLsY78WgkKb7v7e4ygA3",
  "extension": [
    {
      "valueString": "If Partial Code, do not resuscitate exept for the following interventions: Defibrillation and
    External Chest Compression",
      "url": "http://nictiz.nl/fhir/StructureDefinition/Comment"
    }
  ],
  "identifier": [
    {
      "use": "usual",
      "system": "urn:oid:1.2.840.114350.1.13.5325.1.7.2.798268",
      "value": "6001461292"
    }
  ],
  "status": "active",
  "scope": {
    "coding": [
      {
        "system": "http://terminology.hl7.org/CodeSystem/consentscope",
        "code": "adr",
        "display": "Advanced Care Directive"
      }
    ]
  },
  "category": [
    {
      "coding": [
        {
          "system": "http://terminology.hl7.org/CodeSystem/consentcategorycodes",
          "code": "acd",
          "display": "Advance Directive"
        },
        {
          "system": "urn:oid:1.2.840.114350.1.13.5325.1.7.4.796783.100",
          "code": "3",
          "display": "Partial Code"
        },
        {
          "system": "http://snomed.info/sct",
          "code": "11291000146105"
        }
      ]
    }
  ],
  "patient": {
    "reference": "Patient/ejhJ5AcIkLeU2HYq1TuE9RP8BKaTy54Jlyrxvg.KTUuc3",
    "display": "Zzz, Fhirconsent"
  },
  "dateTime": "2021-10-07T14:02:51Z",
  "performer": [
    {
      "reference": "Practitioner/eK1CnAH.5qjxHmSwhyzsI2A3",
      "identifier": {
        "use": "usual",
        "system": "urn:oid:1.2.840.114350.1.13.5325.1.7.2.697780",
        "value": "29518"
      },
      "display": "Serreyn, Superuser, MD"
    }
  ],
  "sourceReference": {
    "reference": "QuestionnaireResponse/e1YCrNQzuB9H5gtKDHjkXnQ3"
  },
  "policy": [
    {
      "extension": [
        {
```

```
          "valueCode": "unknown",
          "url": "http://hl7.org/fhir/StructureDefinition/data-absent-reason"
        }
      ]
    }
  ],
  "verification": [
    {
      "verified": false
    }
  ]
}
```


32.1.2 Consent.Read (Document) (R4)

File: site/apis/32-Security/1-R4/986-Consent-Read-Document-R4.html
Epic API ID | 986
FHIR version | R4
Categories | Security
API type | Industry-Standard
USCDI | No
Available in inpatient and other contexts | Yes
ONC certification products | EpicCare Ambulatory Base, EpicCare Inpatient Base
ONC certification versions | February 2020
HTTP method | GET
URL template | api/FHIR/R4/Consent/{ID}
Supports OAuth 2.0 | True
Supported user types | Backend Systems and Non-OAuth 2.0, Clinicians or Administrative Users, Patients
Performs scope validation | False
Source | https://fhir.epic.com/Specifications?api=986

Description

The FHIR Consent resource defines a concept around collected consent for some action. A Consent resource corresponds to Document record in Epic. The Consent.Read interaction returns only metadata about the patient consent document on file, such as the type of consent and the effective period. This resource does not return the consent document itself. This API can return data about a single, specific Consent document.

In the August 2021 version of Epic and earlier, the Consent (Document) API is intended only for provider-facing applications. Providers can use this API to access all types of consent documents. Starting in the November 2021 version of Epic, patients can also use the the Consent (Document) API to look up information on their consent regarding Advance Directives and Living Will, or Power of Attorney.

This resource respects patient-level break-the-glass checks and document type security checks as configured in Epic. Audit events are logged to the patient audit trail when a consent document is accessed by this resource.

Request parameters

Name | Type | Optional | Array | Cardinality | Description
ID | String | False | | | The FHIR ID for a Consent resource.

Response elements

Name | Type | Optional | Array | Cardinality | Description
Consent | Resource | False | | | An instance of the R4 Consent resource.
Consent.category | CodeableConcept | False | Yes | | The type of consent document. This value follows the specification of the FHIR ConsentCategoryCodes (consent-category) value set, which includes LOINC codes and other identifiers. Additional values can be mapped by Epic organizations if desired. Supported consent categories include: 59284-0 (Consent Document) 64292-6 (Release of information Consent Document) 84095-9 (Do not resuscitate) 59284-0 (Clinical Consent) 64293-4 (Procedure Consent Document) 61359-6 (Anesthesia Consent Document) 61358-8 (Surgical operation Consent Document) 52027-0 (Abortion Consent Document) 52029-6 (Sterilization Consent Document) 64300-7 (Organ donation Consent Document) 83930-8 (Research Consent Document) Starting in the November 2021 version of Epic, this API also supports SNOMED code 11341000146107-Advance Directive as a category. For organizations located in the Netherlands, this API also supports category mapping based on the WilsverklaringTypeCodelijst.
Consent.extension (also: comment) | Extension | True | Yes | | Description of the document.
Consent.dateTime | String | False | | | Date and time that the consent document was created.
Consent.identifier | Identifier | False | Yes | | Document ID (ID value + ID Type).
Consent.patient | Reference | False | | | FHIR reference for the Patient the consent applies to.
Consent.policy | BackboneElement | True | Yes | | The policy of the consent document.
Consent.policy.extension (also: data-absent-reason) | Extension | False | Yes | | Always set to "http://hl7.org/fhir/StructureDefinition/data-absent-reason".
Consent.provision | BackboneElement | False | | | The time period that this document is valid for.
Consent.provision.period | Period | True | | | Time period that this document is valid for. Open-ended periods are represented by the absence of an EndDate and EndTime.
Consent.scope | CodeableConcept | False | | | The scope of the consent.
Consent.status | code | False | | | The state of the consent. This value follows the specification of the FHIR ConsentState value set. The following values have default out-of-the-box support in Epic. Additional statuses can be mapped by Epic organizations if desired. draft Corresponds to Epic value 11-Not Received active Corresponds to Epic values 10-Received and 20-Accepted rejected Corresponds to Epic value 1-Unknown

entered-in-error Corresponds to Epic value 35-Error inactive Does not correspond to any Epic value by default proposed Does not correspond to any Epic value by default The Consent resource returns data for those consent documents that have a document status that corresponds to one of the values above or an additional value that was mapped by the Epic organization. In the August 2021 version of Epic and earlier, Consent documents with no status specified in Epic cannot be retrieved by this web service. Starting in the November 2021 version of Epic, Consent documents with a status not mapped in Epic, or no status specified in Epic, return unknown.

Sample request

```
https://hostname/instance/api/FHIR/R4/Consent/eGKK2eVEbT-bevsE.hB9v3w3
```

Sample response

```
<Consent xmlns="http://hl7.org/fhir">
  <id value="eGKK2eVEbT-bevsE.hB9v3w3"/>
  <identifier>
    <use value="usual"/>
    <system value="urn:oid:1.2.840.114350.1.13.861.1.7.2.686783"/>
    <value value="851260"/>
  </identifier>
  <status value="active"/>
  <scope>
    <coding>
      <system value="urn:oid:1.2.840.114350.1.13.861.1.7.4.686783.100"/>
      <code value="12"/>
      <display value="HIPAA Notice of Privacy"/>
    </coding>
    <text value="HIPAA Notice of Privacy"/>
  </scope>
  <category>
    <coding>
      <system value="urn:oid:1.2.840.114350.1.13.861.1.7.4.686783.100"/>
      <code value="12"/>
      <display value="HIPAA Notice of Privacy"/>
    </coding>
    <coding>
      <system value="http://loinc.org"/>
      <code value="59284-0"/>
      <display value="Consent Document"/>
    </coding>
    <text value="Consent Document"/>
  </category>
  <patient>
    <reference value="Patient/elZHAwEsWkPTsmAOGAUehHg3"/>
    <display value="Zzz, Fhirconsent"/>
  </patient>
  <dateTime value="2019-09-23T21:04:41Z"/>
  <policy>
    <extension url="http://hl7.org/fhir/StructureDefinition/data-absent-reason">
      <valueCode value="unknown"/>
    </extension>
  </policy>
  <provision>
    <period>
      <start value="2019-09-23T21:04:00Z"/>
    </period>
  </provision>
</Consent>
```

32.1.3 Consent.Search (Code Status) (R4)

File: site/apis/32-Security/1-R4/10259-Consent-Search-Code-Status-R4.html
Epic API ID | 10259
FHIR version | R4
Categories | Security
API type | Industry-Standard
USCDI | No
Available in inpatient and other contexts | Yes
HTTP method | GET
URL template | /api/FHIR/R4/Consent?category={category}&patient={patient}&status={status}&subject={subject}
Supports OAuth 2.0 | True
Supported user types | Backend Systems and Non-OAuth 2.0, Clinicians or Administrative Users, Patients
Performs scope validation | False
Source | https://fhir.epic.com/Specifications?api=10259

Description

The FHIR Code Status sub-resource defines a concept around collected consent for a patient code status. A code status documents the level of medical interventions a patient consents to receiving if his heart or breathing stops. The Consent.Search interaction returns data about the patient code statuses. This resource can be used to check whether a code status is on file for a particular patient.

The Code Status sub-resource can return data about one or more code statuses that match the search parameters.

This resource respects patient-level Break-the-Glass checks and advanced directive security checks as configured in Epic. Audit events are logged to the patient audit trail when a code status is accessed by this resource.

Request parameters

Name | Type | Optional | Array | Cardinality | Description
category | String | True | | | Use a value of http://snomed.info/sct|11291000146105 for Code Status
patient | String | Either patient or subject must be provided. | | | FHIR ID for the Patient the consent applies to.
status | String | True | | | The state of the code status for a patient. This value follows the specification of the FHIR ConsentState value set.
subject | String | Either patient or subject must be provided. | | | FHIR ID for the Patient the consent applies to.

Request parameters (post-filtered search parameters)

Name | Type | Optional | Array | Cardinality | Description
action | String | True | | | Unsupported
actor | String | True | | | Unsupported
consentor | String | True | | | Unsupported
data | String | True | | | Unsupported
date | String | True | | | Date/Time this code status was created.
identifier | String | True | | | ID of the order that recorded the code status.
organization | String | True | | | Unsupported
period | String | True | | | Unsupported
purpose | String | True | | | Unsupported
scope | String | True | | | The scope of the code status.
security-label | String | True | | | Unsupported
source-reference | String | True | | | FHIR reference for the questions answered on the code status order.

Response elements

Name | Type | Optional | Array | Cardinality | Description
Bundle | Bundle | False | | | Resource bundle. For more information, refer to the FHIR specification.
Bundle.entry | BackboneElement | False | Yes | | An array of entries included in this bundle.
Bundle.entry.resource | ResourceContainer | False | | | A container for a single FHIR resource.
Bundle.entry.resource.Consent | Resource | False
Bundle.entry.resource.Consent.category | CodeableConcept | False | Yes | | The type of code status. Hard-coded to SNOMED code 11291000146105.
Bundle.entry.resource.Consent.extension (also: comments) | Extension | True | Yes | | Comments entered for the code status.
Bundle.entry.resource.Consent.extension (also: context) | Extension | True | Yes | | The context that the code status was recorded in. For example, “Outpatient, “Inpatient”, “HOV”, etc.
Bundle.entry.resource.Consent.dateTime | String | False | | | Date/Time this code status was created.
Bundle.entry.resource.Consent.id | String | False | | | The Consent FHIR ID.
Bundle.entry.resource.Consent.identifier | Identifier | False | Yes | | ID of the order that recorded the code status.
Bundle.entry.resource.Consent.patient | Reference | False | | | FHIR reference for the Patient the code status applies to.
Bundle.entry.resource.Consent.policy | BackboneElement | True | Yes | | The time period that this code status is valid for.
Bundle.entry.resource.Consent.policy.extension (also: data-absent-reason) | Extension | False | Yes | | Always set to "http://hl7.org/fhir/StructureDefinition/data-absent-reason".
Bundle.entry.resource.Consent.scope | CodeableConcept | False | | | The scope of the code status.
Bundle.entry.resource.Consent.sourceReference | Reference | True | | | FHIR reference for the questions answered on the code status order.
Bundle.entry.resource.Consent.status | code | False | | | The state of the code status for a patient. This value follows the specification of the FHIR ConsentState value set and will always be either ‘active’ or ‘inactive’.
Bundle.entry.resource.Consent.verification | Verification | True | Yes | | Shows whether this consent has been verified by the patient or their family.
Bundle.entry.resource.Consent.verification.verificationDate | String | True | | | The date that a patient verified their consent.
Bundle.entry.resource.Consent.verification.verified | Boolean | False | | | Whether or not this consent has been verified.
Bundle.total | Int64 | True | | | Total number of resources that matched the search criteria.

Sample request

```
https://hostname/instance/api/FHIR/R4/Consent?patient=ejhJ5AcIkLeU2HYq1TuE9RP8BKaTy54Jlyrxvg.KTUuc3&status=active
```

Sample response


```
{
  "resourceType": "Bundle",
  "type": "searchset",
  "total": 1,
  "link": [
    {
      "relation": "self",
      "url": "https://hostname/instance/api/FHIR/R4/Consent?patient=ejhJ5AcIkLeU2HYq1TuE9RP8BKaTy54Jlyrxvg.KTUuc3"
    }
  ],
  "entry": [
    {
      "link": [
        {
          "relation": "self",
          "url": "https://hostname/instance/api/FHIR/R4/Consent/e4.SVLsY78WgkKb7v7e4ygA3"
```

```
    }
  ],
  "fullUrl": "https://hostname/instance/api/FHIR/R4/Consent/e4.SVLsY78WgkKb7v7e4ygA3",
  "resource": {
    "resourceType": "Consent",
    "id": "e4.SVLsY78WgkKb7v7e4ygA3",
    "extension": [
      {
        "valueString": "If Partial Code, do not resuscitate exept for the following interventions: Defibrillation
and External Chest Compression",
        "url": "http://nictiz.nl/fhir/StructureDefinition/Comment"
      }
    ],
    "identifier": [
      {
        "use": "usual",
        "system": "urn:oid:1.2.840.114350.1.13.5325.1.7.2.798268",
        "value": "6001461292"
      }
    ],
    "status": "active",
    "scope": {
      "coding": [
        {
          "system": "http://terminology.hl7.org/CodeSystem/consentscope",
          "code": "adr",
          "display": "Advanced Care Directive"
        }
      ]
    },
    "category": [
      {
        "coding": [
          {
            "system": "http://terminology.hl7.org/CodeSystem/consentcategorycodes",
            "code": "acd",
            "display": "Advance Directive"
          },
          {
            "system": "urn:oid:1.2.840.114350.1.13.5325.1.7.4.796783.100",
            "code": "3",
            "display": "Partial Code"
          },
          {
            "system": "http://snomed.info/sct",
            "code": "11291000146105"
          }
        ]
      }
    ],
    "patient": {
      "reference": "Patient/ejhJ5AcIkLeU2HYq1TuE9RP8BKaTy54Jlyrxvg.KTUuc3",
      "display": "Zzz, Fhirconsent"
    },
    "dateTime": "2021-10-07T14:02:51Z",
    "performer": [
      {
        "reference": "Practitioner/eK1CnAH.5qjxHmSwhyzsI2A3",
        "identifier": {
          "use": "usual",
          "system": "urn:oid:1.2.840.114350.1.13.5325.1.7.2.697780",
          "value": "29518"
        },
        "display": "Serreyn, Superuser, MD"
      }
    ],
    "sourceReference": {
      "reference": "QuestionnaireResponse/e1YCrNQzuB9H5gtKDHjkXnQ3"
    },
    "policy": [
      {
        "extension": [
          {
            "valueCode": "unknown",
            "url": "http://hl7.org/fhir/StructureDefinition/data-absent-reason"
          }
        ]
      }
    ],
    "verification": [
      {
        "verified": false
      }
    ]
  },
  "search": {
    "mode": "match"
  }
}
```

```
  ]
}
```

32.1.4 Consent.Search (Document) (R4)

File: site/apis/32-Security/1-R4/987-Consent-Search-Document-R4.html
Epic API ID | 987
FHIR version | R4
Categories | Security
API type | Industry-Standard
USCDI | No
Available in inpatient and other contexts | Yes
ONC certification products | EpicCare Ambulatory Base, EpicCare Inpatient Base
ONC certification versions | February 2020
HTTP method | GET;POST
URL template | api/FHIR/R4/Consent?patient={patient}&status={status}&category={category}
Supports OAuth 2.0 | True
Supported user types | Backend Systems and Non-OAuth 2.0, Clinicians or Administrative Users, Patients
Performs scope validation | False
Source | https://fhir.epic.com/Specifications?api=987

Description

The FHIR Consent resource defines a concept around collected consent for some action. Consent resources correspond to Document records in Epic. The Consent.Search interaction returns only metadata about the patient consent document(s) on file, such as the type of consent and the effective period. This resource does not return the consent document itself. Typically this resource is used to check whether a consent document is on file for a particular patient.

This API can return data about one or more Consent documents that match the search parameters.

In the August 2021 version of Epic and earlier, the Consent (Document) API is intended only for provider-facing applications. Providers can use this API to access all types of consent documents. Starting in the November 2021 version of Epic, patients can also use the the Consent (Document) API to look up information on their consent regarding Advance Directives and Living Will, or Power of Attorney.

This resource respects patient-level break-the-glass checks and document type security checks as configured in Epic. Audit events are logged to the patient audit trail when a consent document is accessed by this resource.

Request parameters

Name | Type | Optional | Array | Cardinality | Description
category | String | True | | | The type of consent document. This value follows the specification of the FHIR ConsentCategoryCodes (consent-category) value set, which includes LOINC codes and other identifiers. Additional values can be mapped by Epic organizations if desired. Supported consent categories include: 59284-0 (Consent Document) 64292-6 (Release of information Consent Document) 84095-9 (Do not resuscitate) 59284-0 (Clinical Consent) 64293-4 (Procedure Consent Document) 61359-6 (Anesthesia Consent Document) 61358-8 (Surgical operation Consent Document) 52027-0 (Abortion Consent Document) 52029-6 (Sterilization Consent Document) 64300-7 (Organ donation Consent Document) 83930-8 (Research Consent Document)
patient | String | Either patient or subject must be provided. If both are provided, they must match. | | | FHIR ID for the Patient the consent applies to.
status | String | True | | | The state of the consent. This value follows the specification of the FHIR ConsentState value set. The following values have default out-of-the-box support in Epic. Additional statuses can be mapped by Epic organizations if desired. draft Corresponds to Epic value 11-Not Received active Corresponds to Epic values 10-Received and 20-Accepted rejected Corresponds to Epic value 1-Unknown entered-in-error Corresponds to Epic value 35-Error inactive Does not correspond to any Epic value by default proposed Does not correspond to any Epic value by default The Consent resource returns data only for those consent documents that have a document status that corresponds to one of the values above (or an additional value that was mapped by the Epic organization). For this reason, Consent documents with no status specified in Epic cannot be retrieved by this web service.
subject | String | Either patient or subject must be provided. If both are provided, they must match. | | | FHIR ID for the Patient the consent applies to.

Request parameters (post-filtered search parameters)

Name | Type | Optional | Array | Cardinality | Description
action | String | True | | | Unsupported
actor | String | True | | | Unsupported
consentor | String | True | | | Unsupported
data | String | True | | | Unsupported
date | String | True | | | Date/Time this document was created
identifier | String | True | | | Document ID
organization | String | True | | | Unsupported
period | String | True | | | Time period that this document is valid for.
purpose | String | False | | | Unsupported
scope | String | True | | | The scope of the consent.
security-label | String | True | | | Unsupported
source-reference | String | True | | | Unsupported

Response elements

Name | Type | Optional | Array | Cardinality | Description

Bundle | Bundle | False | | | Resource bundle. For more information, refer to the FHIR specification.

Bundle.entry | BackboneElement | False | Yes | | An array of entries included in this bundle.

Bundle.entry.resource | ResourceContainer | False | | | A container for a single FHIR resource.

Bundle.entry.resource.Consent | Resource | False | | | An instance of the R4 Consent resource.

Bundle.entry.resource.Consent.category | CodeableConcept | False | Yes | | The type of consent document. This value follows the specification of the FHIR ConsentCategoryCodes (consent-category) value set, which includes LOINC codes and other identifiers. Additional values can be mapped by Epic organizations if desired. Supported consent categories include: 59284-0 (Consent Document) 64292-6 (Release of information Consent Document) 84095-9 (Do not resuscitate) 59284-0 (Clinical Consent) 64293-4 (Procedure Consent Document) 61359-6 (Anesthesia Consent Document) 61358-8 (Surgical operation Consent Document) 52027-0 (Abortion Consent Document) 52029-6 (Sterilization Consent Document) 64300-7 (Organ donation Consent Document) 83930-8 (Research Consent Document) Starting in the November 2021 version of Epic, this API also supports SNOMED code 11341000146107-Advance Directive as a category. For organizations located in the Netherlands, this API also supports category mapping based on the WilsverklaringTypeCodelijst.

Bundle.entry.resource.Consent.extension (also: comment) | Extension | False | Yes | | Description of the document.

Bundle.entry.resource.Consent.dateTime | String | False | | | Date/Time this document was created

Bundle.entry.resource.Consent.identifier | Identifier | False | Yes | | Document ID (ID value + ID Type).

Bundle.entry.resource.Consent.patient | Reference | False | | | FHIR reference for the Patient the consent applies to.

Bundle.entry.resource.Consent.policy | BackboneElement | False | Yes | | The policy of the consent document.

Bundle.entry.resource.Consent.policy.extension (also: data-absent-reason) | Extension | False | Yes | | Always set to "http://hl7.org/fhir/StructureDefinition/data-absent-reason".

Bundle.entry.resource.Consent.provision | BackboneElement | False | | | The time period that this document is valid for.

Bundle.entry.resource.Consent.provision.period | Period | True | | | Time period that this document is valid for. Open-ended periods are represented by the absence of an EndDate and EndTime.

Bundle.entry.resource.Consent.scope | CodeableConcept | False | | | The scope of the consent.

Bundle.entry.resource.Consent.status | code | False | | | The state of the consent. This value follows the specification of the FHIR ConsentState value set. The following values have default out-of-the-box support in Epic. Additional statuses can be mapped by Epic organizations if desired. draft Corresponds to Epic value 11-Not Received active Corresponds to Epic values 10-Received and 20-Accepted rejected Corresponds to Epic value 1-Unknown entered-in-error Corresponds to Epic value 35-Error inactive Does not correspond to any Epic value by default proposed Does not correspond to any Epic value by default The Consent resource returns data for those consent documents that have a document status that corresponds to one of the values above or an additional value that was mapped by the Epic organization. In the August 2021 version of Epic and earlier, Consent documents with no status specified in Epic cannot be retrieved by this web service. Starting in the November 2021 version of Epic, Consent documents with a status not mapped in Epic, or no status specified in Epic, return unknown.

Bundle.total | Int64 | True | | | Total number of resources that matched the search criteria.

Sample request

```
https://hostname/instance/api/FHIR/R4/Consent?patient=elZHAwEsWkPTsmAOGAUehHg3&status=active,rejected,draft&category=htt
    p://loinc.org|59284-0
```

Sample response

```
<Bundle xmlns="http://hl7.org/fhir">
  <type value="searchset"/>
  <total value="1"/>
  <link>
    <relation value="self"/>
    <url value="https://hostname/instance/api/FHIR/R4/Consent?patient=elZHAwEsWkPTsmAOGAUehHg3&amp;status=active,rejecte
    d,draft&amp;category=,http://loinc.org%7C59284-0"/>
  </link>
  <entry>
    <link>
      <relation value="self"/>
      <url value="https://hostname/instance/api/FHIR/R4/Consent/eGKK2eVEbT-bevsE.hB9v3w3"/>
    </link>
    <fullUrl value="https://hostname/instance/api/FHIR/R4/Consent/eGKK2eVEbT-bevsE.hB9v3w3"/>
    <resource>
      <Consent>
        <id value="eGKK2eVEbT-bevsE.hB9v3w3"/>
        <identifier>
          <use value="usual"/>
          <system value="urn:oid:1.2.840.114350.1.13.861.1.7.2.686783"/>
          <value value="851260"/>
        </identifier>
        <status value="active"/>
        <scope>
          <coding>
            <system value="urn:oid:1.2.840.114350.1.13.861.1.7.4.686783.100"/>
            <code value="12"/>
            <display value="HIPAA Notice of Privacy"/>
          </coding>
          <text value="HIPAA Notice of Privacy"/>
        </scope>
        <category>
          <coding>
            <system value="urn:oid:1.2.840.114350.1.13.861.1.7.4.686783.100"/>
            <code value="12"/>
            <display value="HIPAA Notice of Privacy"/>
          </coding>
          <coding>
            <system value="http://loinc.org"/>
            <code value="59284-0"/>
            <display value="Consent Document"/>
          </coding>
          <text value="Consent Document"/>
```

```
        </category>
        <patient>
          <reference value="Patient/elZHAwEsWkPTsmAOGAUehHg3"/>
          <display value="Zzz, Fhirconsent"/>
        </patient>
        <dateTime value="2019-09-23T21:04:41Z"/>
        <policy>
          <extension url="http://hl7.org/fhir/StructureDefinition/data-absent-reason">
            <valueCode value="unknown"/>
          </extension>
        </policy>
        <provision>
          <period>
            <start value="2019-09-23T21:04:00Z"/>
          </period>
        </provision>
      </Consent>
    </resource>
    <search>
      <mode value="match"/>
    </search>
  </entry>
</Bundle>
```

32.2 Security: STU3

File: site/apis/32-Security/2-STU3/index.html

* Consent.Read (Code Status) (STU3)
* Consent.Read (Document) (STU3)
* Consent.Search (Code Status) (STU3)
* Consent.Search (Document) (STU3)

32.2.1 Consent.Read (Code Status) (STU3)

File: site/apis/32-Security/2-STU3/10255-Consent-Read-Code-Status-STU3.html
Epic API ID | 10255
FHIR version | STU3
Categories | Security
API type | Industry-Standard
USCDI | No
Available in inpatient and other contexts | Yes
HTTP method | GET
URL template | /api/FHIR/STU3/Consent/{ID}
Supports OAuth 2.0 | True
Supported user types | Backend Systems and Non-OAuth 2.0, Clinicians or Administrative Users, Patients
Performs scope validation | False
Source | https://fhir.epic.com/Specifications?api=10255

Description

The FHIR Code Status sub-resource defines a concept around collected consent for a patient code status. A Code Status sub-resource corresponds to a Code Status (OCS) record in Epic. The Consent.Read returns data about a specific patient code status.

This resource respects patient-level Break-the-Glass checks and advanced directive security checks as configured in Epic. Audit events are logged to the patient audit trail when a code status is accessed by this resource.

Request parameters

Name | Type | Optional | Array | Cardinality | Description
ID | String | False | | | The Consent FHIR ID.

Response elements

Name | Type | Optional | Array | Cardinality | Description
Consent | Consent | False | | | An instance of the R4 Consent resource.
Consent.category | CodeableConcept | False | Yes | | The type of code status. Hard-coded to SNOMED code 11291000146105.
Consent.extension (also: comments) | Extension | True | Yes | | Comments entered for the code status.
Consent.dateTime | String | False | | | Date and time that the consent document was created.
Consent.except | Except | True | Yes | | This element holds additional rules that can add or remove permissions when returning results. An exception to the base policy of this consent. This element applies to the Netherlands only.
Consent.except.extension (also: restrictions) | Extension | True | Yes | | A free text description of what your restrictions are. This element is only used in Netherlands environments.
Consent.except.type | String | Always returned in the Netherlands only.
Consent.id | String | False | | | The Consent FHIR ID.
Consent.identifier | Identifier | False | | | ID of the order that recorded the code status.

Consent.meta | Meta | True | | | The document metadata.

Consent.meta.profile | String | True | | | Available in Netherlands environments only. This element shows that this API conforms to the profile connected to the following canonical url: http://nictiz.nl/fhir/StructureDefinition/zib-TreatmentDirective

Consent.patient | Reference | False | | | FHIR reference for the Patient the consent applies to.

Consent.period | Period | True | | | Time period that this document is valid for. At a minimum, the Consent resource always returns a StartDate and StartTime, which default to the time of the consent document creation. Open-ended periods are represented by the absence of an EndDate and EndTime.

Consent.policy | Policy | True | Yes | | The policy of the consent document.

Consent.policy.extension (also: data-absent-reason) | Extension | False | Yes | | Always set to "http://hl7.org/fhir/StructureDefinition/data-absent-reason".

Consent.status | String | False | | | The state of the code status for a patient. This value follows the specification of the FHIR ConsentState value set.

Consent.extension (also: treatment) | Extension | True | Yes | | The treatment being consented to, if this is a treatment consent directive. Note that treatment consent directives are specific to organizations in the Netherlands.

Consent.modifierExtension (also: TreatmentPermitted) | Extension | Always returned in the Netherlands only. | Yes | | Whether a treatment has been consented to, as part of a treatment consent directive. Note that treatment consent directives are specific to organizations in the Netherlands.

Consent.extension (also: verification) | Extension | True | Yes | | Shows whether this consent has been verified by the patient or their family. Note that treatment consent directives are specific to organizations in the Netherlands.

Consent.extension.extension (also: verificationDate) | Extension | True | Yes | | The date that a patient verified their consent.

Consent.extension.extension (also: verified) | Extension | False | Yes | | Whether or not this consent has been verified. Returns true if either VerifiedWith or VerificationDate elements are answered.

Consent.extension.extension (also: verifiedWith) | Extension | True | Yes | | A question that verifies a patient's consent.

Sample request

```
https://hostname/instance/api/FHIR/STU3/Consent/eP7KPXxro.hd3w5ZB7AKoIWeB.-PT6NgolqYO9YhEr9o3
```

Sample response

```
<Consent xmlns="http://hl7.org/fhir">
  <id value="eP7KPXxro.hd3w5ZB7AKoIWeB.-PT6NgolqYO9YhEr9o3"/>
  <extension url="http://nictiz.nl/fhir/StructureDefinition/Comment">
    <valueString value="test"/>
  </extension>
  <extension url="http://nictiz.nl/fhir/StructureDefinition/zib-TreatmentDirective-Verification">
    <extension url="Verified">
      <valueBoolean value="true"/>
    </extension>
    <extension url="VerifiedWith">
      <valueCodeableConcept>
        <coding>
          <system value="http://snomed.info/sct"/>
          <code value="116154003"/>
          <display value="PATIENT (PERSON)"/>
        </coding>
        <coding>
          <system value="urn:oid:1.2.840.114350.1.13.260.1.7.4.696784.72007"/>
          <code value="1"/>
          <display value="Patient"/>
        </coding>
        <text value="PATIENT (PERSON)"/>
      </valueCodeableConcept>
    </extension>
    <extension url="VerificationDate">
      <valueDateTime value="2021-09-24"/>
    </extension>
  </extension>
  <extension url="http://nictiz.nl/fhir/StructureDefinition/zib-TreatmentDirective-Treatment">
    <valueCodeableConcept>
      <coding>
        <system value="http://snomed.info/sct"/>
        <code value="305352006"/>
        <display value="ADMISSION TO ADULT INTENSIVE CARE UNIT (PROCEDURE)"/>
      </coding>
      <coding>
        <system value="http://snomed.info/sct"/>
        <code value="305351004"/>
        <display value="ADMISSION TO INTENSIVE CARE UNIT (PROCEDURE)"/>
      </coding>
      <coding>
        <system value="urn:oid:1.2.840.114350.1.13.260.1.7.4.696784.72009"/>
        <code value="1"/>
        <display value="Admission to intensive care unit"/>
      </coding>
      <text value="ADMISSION TO ADULT INTENSIVE CARE UNIT (PROCEDURE)"/>
    </valueCodeableConcept>
  </extension>
  <modifierExtension>
    <valueCodeableConcept>
      <coding>
        <system value="urn:oid:2.16.840.1.113883.2.4.3.11.60.40.4"/>
        <code value="JA"/>
        <display value="Ja"/>
      </coding>
    </valueCodeableConcept>
    <url value="http://nictiz.nl/fhir/StructureDefinition/zib-TreatmentDirective-TreatmentPermitted"/>
```

```
  </modifierExtension>
  <identifier>
    <use value="usual"/>
    <system value="urn:oid:1.2.840.114350.1.13.260.1.7.2.798268"/>
    <value value="313885"/>
  </identifier>
  <status value="active"/>
  <category>
    <coding>
      <system value="http://terminology.hl7.org/CodeSystem/consentcategorycodes"/>
      <code value="acd"/>
      <display value="Advance Directive"/>
    </coding>
    <coding>
      <system value="urn:oid:1.2.840.114350.1.13.260.1.7.4.796783.100"/>
      <code value="1"/>
      <display value="Full Code"/>
    </coding>
    <coding>
      <system value="http://snomed.info/sct"/>
      <code value="11291000146105"/>
    </coding>
  </category>
  <patient>
    <reference value=" https://hostname/instance/api/FHIR/STU3/Consent/eP7KPXxro.hd3w5ZB7AKoIWeB.-PT6NgolqYO9YhEr9o3"/>
    <display value="Giles, F.C."/>
  </patient>
  <period>
    <start value="2021-09-24T19:28:28Z"/>
  </period>
  <dateTime value="2021-09-24T19:28:28Z"/>
  <policy>
    <extension url="http://hl7.org/fhir/StructureDefinition/data-absent-reason">
      <valueCode value="unknown"/>
    </extension>
  </policy>
</Consent>
```

Change log

Epic Version | Description | Type
November 2022 | Code systems for the following code sets now return a URL in place of an OID: ActCode, ICD-10-CM, ICD-10-CA, ICD-10-NL, SNOMED System URL OID ActCode STU3: http://hl7.org/fhir/v3/ActCode R4: http://terminology.hl7.org/CodeSystem/v3-ActCode 2.16.840.1.113883.5.4 ICD-10-CM http://hl7.org/fhir/sid/icd-10-cm 2.16.840.1.113883.6.90 ICD-10-CA http://hl7.org/fhir/sid/icd-10-ca 2.16.840.1.113883.6.94 ICD-10-NL http://hl7.org/fhir/sid/icd-10-nl 2.16.840.1.113883.6.3.2 SNOMED http://snomed.info/sct 2.16.840.1.113883.6.96 | Breaking change
System | URL | OID
ActCode | STU3: http://hl7.org/fhir/v3/ActCode R4: http://terminology.hl7.org/CodeSystem/v3-ActCode | 2.16.840.1.113883.5.4
ICD-10-CM | http://hl7.org/fhir/sid/icd-10-cm | 2.16.840.1.113883.6.90
ICD-10-CA | http://hl7.org/fhir/sid/icd-10-ca | 2.16.840.1.113883.6.94
ICD-10-NL | http://hl7.org/fhir/sid/icd-10-nl | 2.16.840.1.113883.6.3.2
SNOMED | http://snomed.info/sct | 2.16.840.1.113883.6.96

32.2.2 Consent.Read (Document) (STU3)

File: site/apis/32-Security/2-STU3/10260-Consent-Read-Document-STU3.html
Epic API ID | 10260
FHIR version | STU3
Categories | Security
API type | Industry-Standard
USCDI | No
Available in inpatient and other contexts | Yes
HTTP method | GET
URL template | /api/FHIR/STU3/Consent/{ID}
Supports OAuth 2.0 | True
Supported user types | Backend Systems and Non-OAuth 2.0, Clinicians or Administrative Users, Patients
Performs scope validation | False
Source | https://fhir.epic.com/Specifications?api=10260

Description

The FHIR Consent resource defines a concept around collected consent for some action. A Consent resource corresponds to Document record in Epic. The Consent.Read interaction returns only metadata about the patient consent document on file, such as the type of consent and the effective period. This resource does not return the consent document itself. This API can return data about a single, specific Consent document.

In the August 2021 version of Epic and earlier, the Consent (Document) API is intended only for provider-facing applications. Providers can use this API to access all types of consent documents. Starting in the November 2021 version of Epic, patients can also use the the Consent (Document) API to look up information on their consent regarding Advance Directives and Living Will, or Power of Attorney.

This resource respects patient-level break-the-glass checks and document type security checks as configured in Epic. Audit events are logged to the patient audit trail when a consent document is accessed by this resource.

Request parameters

Name | Type | Optional | Array | Cardinality | Description
ID | String | False | | | The Consent FHIR ID.

Response elements

Name | Type | Optional | Array | Cardinality | Description
Consent | Consent | False | | | An instance of the R4 Consent resource.
Consent.category | CodeableConcept | False | Yes | | The type of consent document. This value follows the specification of the FHIR ConsentCategoryCodes (consent-category) value set, which includes LOINC codes and other identifiers. Additional values can be mapped by Epic organizations if desired. Supported consent categories include: 59284-0 (Consent Document) 64292-6 (Release of information Consent Document) 84095-9 (Do not resuscitate) 59284-0 (Clinical Consent) 64293-4 (Procedure Consent Document) 61359-6 (Anesthesia Consent Document) 61358-8 (Surgical operation Consent Document) 52027-0 (Abortion Consent Document) 52029-6 (Sterilization Consent Document) 64300-7 (Organ donation Consent Document) 83930-8 (Research Consent Document) This API also supports SNOMED code 11341000146107-Advance Directive as a category. For organizations located in the Netherlands, this API also supports category mapping based on the WilsverklaringTypeCodelijst.
Consent.extension (also: comment) | Extension | True | Yes | | Description of a document.
Consent.consentingParty | Reference | True | Yes | | This element applies only to organizations in the Netherlands. The person who is the legal representative or is appointed as the authorized representative in the signed consent. In Epic, this is represented by the patient's active Health Care Agent. If a patient has no active Health Care Agent, this returns the patient's own name.
Consent.dateTime | String | False | | | Date and time that the consent document was created.
Consent.id | String | False | | | The Consent FHIR ID.
Consent.identifier | Identifier | False | | | Document ID (ID value + ID Type).
Consent.meta | Meta | True | | | The document metadata.
Consent.meta.profile | String | True | | | Available in Netherlands environments only. This element shows that this API conforms to the profile connected to the following canonical url: http://nictiz.nl/fhir/StructureDefinition/zib-AdvanceDirective
Consent.patient | Reference | False | | | FHIR reference for the Patient the consent applies to.
Consent.period | Period | True | | | Time period that this document is valid for. Open-ended periods are represented by the absence of an EndDate and EndTime.
Consent.policy | Policy | True | Yes | | The policy of the consent document.
Consent.policy.extension (also: data-absent-reason) | Extension | False | Yes | | Always set to "http://hl7.org/fhir/StructureDefinition/data-absent-reason".
Consent.status | String | False | | | The state of the consent. This value follows the specification of the FHIR ConsentState value set. The following values have default out-of-the-box support in Epic. Additional statuses can be mapped by Epic organizations if desired. draft Corresponds to Epic value 11-Not Received active Corresponds to Epic values 10-Received and 20-Accepted rejected Corresponds to Epic value 1-Unknown entered-in-error Corresponds to Epic value 35-Error inactive Does not correspond to any Epic value by default proposed Does not correspond to any Epic value by default

Sample request

```
https://hostname/instance/api/FHIR/STU3/Consent/eGKK2eVEbT-bevsE.hB9v3w3
```

Sample response


```
{
  "resourceType": "Consent",
  "id": "eohl7R2Vlqb6G28xH4sYyK8zPeTjGBGbTDV3rHgSHZCk3",
  "extension": [
    {
      "valueString": "living will.pdf",
      "url": "http://nictiz.nl/fhir/StructureDefinition/Comment"
    }
  ],
  "identifier": {
    "use": "usual",
    "system": "urn:oid:1.2.840.114350.1.13.5325.1.7.2.686783",
    "value": "1040113"
  },
  "status": "active",
  "category": [
    {
      "coding": [
        {
          "system": "urn:oid:1.2.840.114350.1.13.5325.1.7.4.686783.100",
          "code": "10",
          "display": "Advance Directives and Living Will"
        },
        {
          "system": "http://snomed.info/sct",
          "code": "11341000146107"
        }
      ],
      "text": "Advance Directives and Living Will"
    }
  ],
  "patient": {
    "reference": "https://vs-icx18-25/Interconnect-FHIR-Current-Stage1-Primary-Unsecured/api/FHIR/STU3/Patient/eivR2DL-
    WAG8Nxx3xBYUu7A3",
    "display": "Patient, Sample"
```

```
  },
  "period": {
    "start": "2023-03-13T19:54:19Z",
    "end": "2023-04-12T04:59:59Z"
  },
  "dateTime": "2023-03-13T19:54:19Z",
  "policy": [
    {
      "extension": [
        {
          "valueCode": "unknown",
          "url": "http://hl7.org/fhir/StructureDefinition/data-absent-reason"
        }
      ]
    }
  ]
}
```


32.2.3 Consent.Search (Code Status) (STU3)

File: site/apis/32-Security/2-STU3/10256-Consent-Search-Code-Status-STU3.html
Epic API ID | 10256
FHIR version | STU3
Categories | Security
API type | Industry-Standard
USCDI | No
Available in inpatient and other contexts | Yes
HTTP method | GET
URL template | /api/FHIR/STU3/Consent?category={category}&patient={patient}&status={status}&subject={subject}
Supports OAuth 2.0 | True
Supported user types | Backend Systems and Non-OAuth 2.0, Clinicians or Administrative Users, Patients
Performs scope validation | False
Source | https://fhir.epic.com/Specifications?api=10256

Description

The FHIR Code Status sub-resource defines a concept around collected consent for a patient code status. A Code Status sub-resource corresponds to a Code Status (OCS) record in Epic. The Consent.Search interaction returns data about the patient code statuses. Typically this resource is used to check whether a code status is on file for a particular patient.

The Code Status sub-resource can return data about one or more code statuses that match the search parameters.

This resource respects patient-level Break-the-glass checks and advanced directive security checks as configured in Epic. Audit events are logged to the patient audit trail when a code status is accessed by this resource.

Request parameters

Name | Type | Optional | Array | Cardinality | Description
category | String | True | | | The type of code status. Code statuses always include the Advanced Directive (acd) category from the specification of the FHIR ConsentCategoryCodes (consent-category) value set, and additional information about what type of code status.
patient | String | Either patient or subject must be provided. If both are provided, they must match. | | | FHIR ID for the Patient the consent applies to.
status | String | True | | | The state of the code status for a patient. This value follows the specification of the FHIR ConsentState value set.
subject | String | Either patient or subject must be provided. If both are provided, they must match. | | | FHIR ID for the Patient the consent applies to.

Response elements

Name | Type | Optional | Array | Cardinality | Description
Bundle | Bundle | False | | | Resource bundle. For more information, refer to the FHIR specification.
Bundle.entry | Entry | False | Yes | | A single entry in the resource bundle.
Bundle.entry.resource | ResourceContainer | False | | | A single resource returned as part of this bundle.
Bundle.entry.resource.Consent | Consent | False | | | An instance of the R4 Consent resource.
Bundle.entry.resource.Consent.category | CodeableConcept | False | Yes | | The type of code status. Hard-coded to SNOMED code 11291000146105.
Bundle.entry.resource.Consent.extension (also: comments) | Extension | True | Yes | | Comments entered for the code status.
Bundle.entry.resource.Consent.dateTime | String | False | | | Date/Time this document was created
Bundle.entry.resource.Consent.except | Except | True | Yes | | This element holds additional rules that can add or remove permissions when returning results. An exception to the base policy of this consent. This element applies to the Netherlands only.
Bundle.entry.resource.Consent.except.extension (also: restrictions) | Extension | True | Yes | | A free text description of what your restrictions are. This element is only used in Netherlands environments.
Bundle.entry.resource.Consent.except.type | String | Always returned in the Netherlands only. | | | The action to take when the exception is met- whether to accept or deny this consent. This is hardcoded to DENY if Extension(TreatmentPermitted) = JA_MAAR. This element is only used in Netherlands environments.
Bundle.entry.resource.Consent.id | String | False | | | The Consent FHIR ID.
Bundle.entry.resource.Consent.identifier | Identifier | False | | | ID of the order that recorded the code status.
Bundle.entry.resource.Consent.meta | Meta | True | | | The document metadata.
Bundle.entry.resource.Consent.meta.profile | String | True | | | Available in Netherlands environments only. This element shows that this API conforms to the profile connected to the following canonical url: http://nictiz.nl/fhir/StructureDefinition/zib-TreatmentDirective
Bundle.entry.resource.Consent.patient | Reference | False | | | FHIR reference for the Patient the consent applies to.

Bundle.entry.resource.Consent.period | Period | True | | | Time period that this document is valid for. At a minimum, the Consent resource always returns a StartDate and StartTime, which default to the time of the consent document creation. Open-ended periods are represented by the absence of an EndDate and EndTime.

Bundle.entry.resource.Consent.policy | Policy | False | Yes | | The policy of the consent document.

Bundle.entry.resource.Consent.policy.extension (also: data-absent-reason) | Extension | False | Yes | | Always set to "http://hl7.org/fhir/StructureDefinition/data-absent-reason".

Bundle.entry.resource.Consent.status | String | False | | | The state of the code status for a patient. This value follows the specification of the FHIR ConsentState value set.

Bundle.entry.resource.Consent.extension (also: treatment) | Extension | True | Yes | | The treatment being consented to, if this is a treatment consent directive. Note that treatment consent directives are specific to organizations in the Netherlands.

Bundle.entry.resource.Consent.modifierExtension (also: TreatmentPermitted) | Extension | Always returned in the Netherlands only. | Yes | | Whether a treatment has been consented to, as part of a treatment consent directive. Note that treatment consent directives are specific to organizations in the Netherlands.

Bundle.entry.resource.Consent.extension (also: verification) | Extension | True | Yes | | Shows whether this consent has been verified by the patient or their family. Note that treatment consent directives are specific to organizations in the Netherlands.

Bundle.entry.resource.Consent.extension.extension (also: VerificationDate) | Extension | False | Yes | | The date that a patient verified their consent.

Bundle.entry.resource.Consent.extension.extension (also: verified) | Extension | False | Yes | | Whether or not this consent has been verified. Returns true if either VerifiedWith or VerificationDate elements are answered.

Bundle.entry.resource.Consent.extension.extension (also: VerifiedWith) | Extension | True | Yes | | A question that verifies a patient's consent.

Sample request

```
https://hostname/instance/api/FHIR/STU3/Consent?patient=ed7aXNgz9-
    VaUIk2e.6Bgjg3&category=http://snomed.info/sct|11291000146105
```

Sample response

```
<Bundle xmlns="http://hl7.org/fhir">
    <type value="searchset" />
    <total value="5" />
    <link>
        <relation value="self" />
        <url value=" https://hostname/instance/api/FHIR/STU3/Consent?patient=ed7aXNgz9-
    VaUIk2e.6Bgjg3&category=http://snomed.info/sct|11291000146105" />
    </link>
    <entry>
        <link>
            <relation value="self" />
            <url value="https://hostname/instance/api/FHIR/STU3/Consent?patient=ed7aXNgz9-
    VaUIk2e.6Bgjg3&category=http://snomed.info/sct|11291000146105" />
        </link>
        <fullUrl value="https://hostname/instance/api/FHIR/STU3/Consent?patient=ed7aXNgz9-
    VaUIk2e.6Bgjg3&category=http://snomed.info/sct|11291000146105" />
        <resource>
            <Consent>
                <id value="eP7KPXxro.hd3w5ZB7AKoIWeB.-PT6NgolqYO9YhEr9o3" />
                <extension url="http://nictiz.nl/fhir/StructureDefinition/Comment">
                    <valueString value="test" />
                </extension>
                <extension url="http://nictiz.nl/fhir/StructureDefinition/zib-TreatmentDirective-Verification">
                    <extension url="Verified">
                        <valueBoolean value="true" />
                    </extension>
                    <extension url="VerifiedWith">
                        <valueCodeableConcept>
                            <coding>
                                <system value="http://snomed.info/sct" />
                                <code value="116154003" />
                                <display value="PATIENT (PERSON)" />
                            </coding>
                            <coding>
                                <system value="urn:oid:1.2.840.114350.1.13.260.1.7.4.696784.72007" />
                                <code value="1" />
                                <display value="Patient" />
                            </coding>
                            <text value="PATIENT (PERSON)" />
                        </valueCodeableConcept>
                    </extension>
                    <extension url="VerificationDate">
                        <valueDateTime value="2021-09-24" />
                    </extension>
                </extension>
                <extension url="http://nictiz.nl/fhir/StructureDefinition/zib-TreatmentDirective-Treatment">
                    <valueCodeableConcept>
                        <coding>
                            <system value="http://snomed.info/sct" />
                            <code value="305352006" />
                            <display value="ADMISSION TO ADULT INTENSIVE CARE UNIT (PROCEDURE)" />
                        </coding>
                        <coding>
                            <system value="http://snomed.info/sct" />
                            <code value="305351004" />
                            <display value="ADMISSION TO INTENSIVE CARE UNIT (PROCEDURE)" />
                        </coding>
                        <coding>
```

```
                        <system value="urn:oid:1.2.840.114350.1.13.260.1.7.4.696784.72009" />
                        <code value="1" />
                        <display value="Admission to intensive care unit" />
                    </coding>
                    <text value="ADMISSION TO ADULT INTENSIVE CARE UNIT (PROCEDURE)" />
                </valueCodeableConcept>
            </extension>
            <modifierExtension>
                <valueCodeableConcept>
                    <coding>
                        <system value="urn:oid:2.16.840.1.113883.2.4.3.11.60.40.4" />
                        <code value="JA" />
                        <display value="Ja" />
                    </coding>
                </valueCodeableConcept>
                <url value="http://nictiz.nl/fhir/StructureDefinition/zib-TreatmentDirective-TreatmentPermitted" />
            </modifierExtension>
            <identifier>
                <use value="usual" />
                <system value="urn:oid:1.2.840.114350.1.13.260.1.7.2.798268" />
                <value value="313885" />
            </identifier>
            <status value="active" />
            <category>
                <coding>
                    <system value="http://terminology.hl7.org/CodeSystem/consentcategorycodes" />
                    <code value="acd" />
                    <display value="Advance Directive" />
                </coding>
                <coding>
                    <system value="urn:oid:1.2.840.114350.1.13.260.1.7.4.796783.100" />
                    <code value="1" />
                    <display value="Full Code" />
                </coding>
                <coding>
                    <system value="http://snomed.info/sct" />
                    <code value="11291000146105" />
                </coding>
            </category>
            <patient>
                <reference value="https://hostname/instance/api/FHIR/STU3/Consent?patient=ed7aXNgz9-
VaUIk2e.6Bgjg3&category=http://snomed.info/sct|11291000146105" />
                <display value="Giles, F.C." />
            </patient>
            <period>
                <start value="2021-09-24T19:28:28Z" />
            </period>
            <dateTime value="2021-09-24T19:28:28Z" />
            <policy>
                <extension url="http://hl7.org/fhir/StructureDefinition/data-absent-reason">
                    <valueCode value="unknown" />
                </extension>
            </policy>
        </Consent>
    </resource>
    <search>
        <mode value="match" />
    </search>
</entry>
<entry>
    <link>
        <relation value="self" />
        <url value="https://hostname/instance/api/FHIR/STU3/Consent/extAlpT.eA0vXZeagl9dTmrJX-1bEp7AWr2ZunlLn.ec3"
/>
    </link>
    <fullUrl value="https://hostname/instance/api/FHIR/STU3/Consent/extAlpT.eA0vXZeagl9dTmrJX-1bEp7AWr2ZunlLn.ec3"
/>
    <resource>
        <Consent>
            <id value="extAlpT.eA0vXZeagl9dTmrJX-1bEp7AWr2ZunlLn.ec3" />
            <extension url="http://nictiz.nl/fhir/StructureDefinition/Comment">
                <valueString value="test" />
            </extension>
            <extension url="http://nictiz.nl/fhir/StructureDefinition/zib-TreatmentDirective-Verification">
                <extension url="Verified">
                    <valueBoolean value="true" />
                </extension>
                <extension url="VerifiedWith">
                    <valueCodeableConcept>
                        <coding>
                            <system value="http://snomed.info/sct" />
                            <code value="116154003" />
                            <display value="PATIENT (PERSON)" />
                        </coding>
                        <coding>
                            <system value="urn:oid:1.2.840.114350.1.13.260.1.7.4.696784.72007" />
                            <code value="1" />
                            <display value="Patient" />
                        </coding>
```

```
                        <text value="PATIENT (PERSON)" />
                    </valueCodeableConcept>
                </extension>
                <extension url="VerificationDate">
                    <valueDateTime value="2021-09-24" />
                </extension>
            </extension>
            <extension url="http://nictiz.nl/fhir/StructureDefinition/zib-TreatmentDirective-Treatment">
                <valueCodeableConcept>
                    <coding>
                        <system value="http://snomed.info/sct" />
                        <code value="89666000" />
                        <display value="CARDIOPULMONARY RESUSCITATION (PROCEDURE)" />
                    </coding>
                    <coding>
                        <system value="http://snomed.info/sct" />
                        <code value="439569004" />
                        <display value="Resuscitation (procedure)" />
                    </coding>
                    <coding>
                        <system value="http://snomed.info/sct" />
                        <code value="69779005" />
                        <display value="CARDIAC RESUSCITATION (PROCEDURE)" />
                    </coding>
                    <coding>
                        <system value="urn:oid:1.2.840.114350.1.13.260.1.7.4.696784.72009" />
                        <code value="2" />
                        <display value="Cardiopulmonary resuscitation " />
                    </coding>
                    <text value="CARDIOPULMONARY RESUSCITATION (PROCEDURE)" />
                </valueCodeableConcept>
            </extension>
            <modifierExtension>
                <valueCodeableConcept>
                    <coding>
                        <system value="urn:oid:2.16.840.1.113883.2.4.3.11.60.40.4" />
                        <code value="JA" />
                        <display value="Ja" />
                    </coding>
                </valueCodeableConcept>
                <url value="http://nictiz.nl/fhir/StructureDefinition/zib-TreatmentDirective-TreatmentPermitted" />
            </modifierExtension>
            <identifier>
                <use value="usual" />
                <system value="urn:oid:1.2.840.114350.1.13.260.1.7.2.798268" />
                <value value="313885" />
            </identifier>
            <status value="active" />
            <category>
                <coding>
                    <system value="http://terminology.hl7.org/CodeSystem/consentcategorycodes" />
                    <code value="acd" />
                    <display value="Advance Directive" />
                </coding>
                <coding>
                    <system value="urn:oid:1.2.840.114350.1.13.260.1.7.4.796783.100" />
                    <code value="1" />
                    <display value="Full Code" />
                </coding>
                <coding>
                    <system value="http://snomed.info/sct" />
                    <code value="11291000146105" />
                </coding>
            </category>
            <patient>
                <reference value="https://hostname/instance/api/FHIR/STU3/Consent?patient=ed7aXNgz9-
VaUIk2e.6Bgjg3&category=http://snomed.info/sct|11291000146105" />
                <display value="Giles, F.C." />
            </patient>
            <period>
                <start value="2021-09-24T19:28:28Z" />
            </period>
            <dateTime value="2021-09-24T19:28:28Z" />
            <policy>
                <extension url="http://hl7.org/fhir/StructureDefinition/data-absent-reason">
                    <valueCode value="unknown" />
                </extension>
            </policy>
        </Consent>
    </resource>
    <search>
        <mode value="match" />
    </search>
</entry>
<entry>
    <link>
        <relation value="self" />
        <url value="https://hostname/instance/api/FHIR/STU3/Consent/ehP.PkSjthv5gfEEuO0Mk5Py6XfR5vtY5Mllc-LChUG03"
/>
```

```
    </link>
    <fullUrl value="https://hostname/instance/api/FHIR/STU3/Consent/ehP.PkSjthv5gfEEuO0Mk5Py6XfR5vtY5Mllc-LChUG03"
/>
    <resource>
        <Consent>
            <id value="ehP.PkSjthv5gfEEuO0Mk5Py6XfR5vtY5Mllc-LChUG03" />
            <extension url="http://nictiz.nl/fhir/StructureDefinition/Comment">
                <valueString value="test" />
            </extension>
            <extension url="http://nictiz.nl/fhir/StructureDefinition/zib-TreatmentDirective-Verification">
                <extension url="Verified">
                    <valueBoolean value="true" />
                </extension>
                <extension url="VerifiedWith">
                    <valueCodeableConcept>
                        <coding>
                            <system value="http://snomed.info/sct" />
                            <code value="116154003" />
                            <display value="PATIENT (PERSON)" />
                        </coding>
                        <coding>
                            <system value="urn:oid:1.2.840.114350.1.13.260.1.7.4.696784.72007" />
                            <code value="1" />
                            <display value="Patient" />
                        </coding>
                        <text value="PATIENT (PERSON)" />
                    </valueCodeableConcept>
                </extension>
                <extension url="VerificationDate">
                    <valueDateTime value="2021-09-24" />
                </extension>
            </extension>
            <extension url="http://nictiz.nl/fhir/StructureDefinition/zib-TreatmentDirective-Treatment">
                <valueCodeableConcept>
                    <coding>
                        <system value="http://snomed.info/sct" />
                        <code value="40617009" />
                        <display value="ARTIFICIAL RESPIRATION (PROCEDURE)" />
                    </coding>
                    <coding>
                        <system value="urn:oid:1.2.840.114350.1.13.260.1.7.4.696784.72009" />
                        <code value="3" />
                        <display value="Artificial respiration" />
                    </coding>
                    <text value="ARTIFICIAL RESPIRATION (PROCEDURE)" />
                </valueCodeableConcept>
            </extension>
            <modifierExtension>
                <valueCodeableConcept>
                    <coding>
                        <system value="urn:oid:2.16.840.1.113883.2.4.3.11.60.40.4" />
                        <code value="JA" />
                        <display value="Ja" />
                    </coding>
                </valueCodeableConcept>
                <url value="http://nictiz.nl/fhir/StructureDefinition/zib-TreatmentDirective-TreatmentPermitted" />
            </modifierExtension>
            <identifier>
                <use value="usual" />
                <system value="urn:oid:1.2.840.114350.1.13.260.1.7.2.798268" />
                <value value="313885" />
            </identifier>
            <status value="active" />
            <category>
                <coding>
                    <system value="http://terminology.hl7.org/CodeSystem/consentcategorycodes" />
                    <code value="acd" />
                    <display value="Advance Directive" />
                </coding>
                <coding>
                    <system value="urn:oid:1.2.840.114350.1.13.260.1.7.4.796783.100" />
                    <code value="1" />
                    <display value="Full Code" />
                </coding>
                <coding>
                    <system value="http://snomed.info/sct" />
                    <code value="11291000146105" />
                </coding>
            </category>
            <patient>
                <reference value="https://hostname/instance/api/FHIR/STU3/Consent?patient=ed7aXNgz9-
VaUIk2e.6Bgjg3&category=http://snomed.info/sct|11291000146105" />
                <display value="Giles, F.C." />
            </patient>
            <period>
                <start value="2021-09-24T19:28:28Z" />
            </period>
            <dateTime value="2021-09-24T19:28:28Z" />
            <policy>
```

```
                <extension url="http://hl7.org/fhir/StructureDefinition/data-absent-reason">
                    <valueCode value="unknown" />
                </extension>
            </policy>
        </Consent>
    </resource>
    <search>
        <mode value="match" />
    </search>
</entry>
<entry>
    <link>
        <relation value="self" />
        <url value="https://hostname/instance/api/FHIR/STU3/Consent/eZQ2Ewm-Cteoe86h.2IpKlRvvha8crlFDAc1LiUhUo8Q3"
/>
    </link>
    <fullUrl value="https://hostname/instance/api/FHIR/STU3/Consent/eZQ2Ewm-Cteoe86h.2IpKlRvvha8crlFDAc1LiUhUo8Q3"
/>
    <resource>
        <Consent>
            <id value="eZQ2Ewm-Cteoe86h.2IpKlRvvha8crlFDAc1LiUhUo8Q3" />
            <extension url="http://nictiz.nl/fhir/StructureDefinition/Comment">
                <valueString value="test" />
            </extension>
            <extension url="http://nictiz.nl/fhir/StructureDefinition/zib-TreatmentDirective-Verification">
                <extension url="Verified">
                    <valueBoolean value="true" />
                </extension>
                <extension url="VerifiedWith">
                    <valueCodeableConcept>
                        <coding>
                            <system value="http://snomed.info/sct" />
                            <code value="116154003" />
                            <display value="PATIENT (PERSON)" />
                        </coding>
                        <coding>
                            <system value="urn:oid:1.2.840.114350.1.13.260.1.7.4.696784.72007" />
                            <code value="1" />
                            <display value="Patient" />
                        </coding>
                        <text value="PATIENT (PERSON)" />
                    </valueCodeableConcept>
                </extension>
                <extension url="VerificationDate">
                    <valueDateTime value="2021-09-24" />
                </extension>
            </extension>
            <extension url="http://nictiz.nl/fhir/StructureDefinition/zib-TreatmentDirective-Treatment">
                <valueCodeableConcept>
                    <coding>
                        <system value="http://snomed.info/sct" />
                        <code value="116762002" />
                        <display value="ADMINISTRATION OF BLOOD PRODUCT (PROCEDURE)" />
                    </coding>
                    <coding>
                        <system value="http://snomed.info/sct" />
                        <code value="246483004" />
                        <display value="BLOOD PRODUCT USED (ATTRIBUTE)" />
                    </coding>
                    <coding>
                        <system value="urn:oid:1.2.840.114350.1.13.260.1.7.4.696784.72009" />
                        <code value="4" />
                        <display value="Administration of blood product " />
                    </coding>
                    <text value="ADMINISTRATION OF BLOOD PRODUCT (PROCEDURE)" />
                </valueCodeableConcept>
            </extension>
            <modifierExtension>
                <valueCodeableConcept>
                    <coding>
                        <system value="urn:oid:2.16.840.1.113883.2.4.3.11.60.40.4" />
                        <code value="JA" />
                        <display value="Ja" />
                    </coding>
                </valueCodeableConcept>
                <url value="http://nictiz.nl/fhir/StructureDefinition/zib-TreatmentDirective-TreatmentPermitted" />
            </modifierExtension>
            <identifier>
                <use value="usual" />
                <system value="urn:oid:1.2.840.114350.1.13.260.1.7.2.798268" />
                <value value="313885" />
            </identifier>
            <status value="active" />
            <category>
                <coding>
                    <system value="http://terminology.hl7.org/CodeSystem/consentcategorycodes" />
                    <code value="acd" />
                    <display value="Advance Directive" />
                </coding>
```

```
                <coding>
                    <system value="urn:oid:1.2.840.114350.1.13.260.1.7.4.796783.100" />
                    <code value="1" />
                    <display value="Full Code" />
                </coding>
                <coding>
                    <system value="http://snomed.info/sct" />
                    <code value="11291000146105" />
                </coding>
            </category>
            <patient>
                <reference value="https://hostname/instance/api/FHIR/STU3/Consent?patient=ed7aXNgz9-
VaUIk2e.6Bgjg3&category=http://snomed.info/sct|11291000146105" />
                <display value="Giles, F.C." />
            </patient>
            <period>
                <start value="2021-09-24T19:28:28Z" />
            </period>
            <dateTime value="2021-09-24T19:28:28Z" />
            <policy>
                <extension url="http://hl7.org/fhir/StructureDefinition/data-absent-reason">
                    <valueCode value="unknown" />
                </extension>
            </policy>
        </Consent>
    </resource>
    <search>
        <mode value="match" />
    </search>
</entry>
<entry>
    <link>
        <relation value="self" />
        <url value="https://hostname/instance/api/FHIR/STU3/Consent/eP7KPXxro.hd3w5ZB7AKoIcaiVG79TuhNvVL2fTq.iys3"
/>
    </link>
    <fullUrl value="https://hostname/instance/api/FHIR/STU3/Consent/eP7KPXxro.hd3w5ZB7AKoIcaiVG79TuhNvVL2fTq.iys3"
/>
    <resource>
        <Consent>
            <id value="eP7KPXxro.hd3w5ZB7AKoIcaiVG79TuhNvVL2fTq.iys3" />
            <extension url="http://nictiz.nl/fhir/StructureDefinition/Comment">
                <valueString value="test" />
            </extension>
            <extension url="http://nictiz.nl/fhir/StructureDefinition/zib-TreatmentDirective-Verification">
                <extension url="Verified">
                    <valueBoolean value="true" />
                </extension>
                <extension url="VerifiedWith">
                    <valueCodeableConcept>
                        <coding>
                            <system value="http://snomed.info/sct" />
                            <code value="116154003" />
                            <display value="PATIENT (PERSON)" />
                        </coding>
                        <coding>
                            <system value="urn:oid:1.2.840.114350.1.13.260.1.7.4.696784.72007" />
                            <code value="1" />
                            <display value="Patient" />
                        </coding>
                        <text value="PATIENT (PERSON)" />
                    </valueCodeableConcept>
                </extension>
                <extension url="VerificationDate">
                    <valueDateTime value="2021-09-24" />
                </extension>
            </extension>
            <extension url="http://nictiz.nl/fhir/StructureDefinition/zib-TreatmentDirective-Treatment">
                <valueCodeableConcept>
                    <coding>
                        <system value="http://snomed.info/sct" />
                        <code value="902003" />
                        <display value="EXPERIMENTAL DRUG (PRODUCT)" />
                    </coding>
                    <coding>
                        <system value="urn:oid:1.2.840.114350.1.13.260.1.7.4.696784.72009" />
                        <code value="101" />
                        <display value="Other" />
                    </coding>
                    <text value="EXPERIMENTAL DRUG (PRODUCT)" />
                </valueCodeableConcept>
            </extension>
            <modifierExtension>
                <valueCodeableConcept>
                    <coding>
                        <system value="urn:oid:2.16.840.1.113883.2.4.3.11.60.40.4" />
                        <code value="JA" />
                        <display value="Ja" />
                    </coding>
```

```
                    </valueCodeableConcept>
                    <url value="http://nictiz.nl/fhir/StructureDefinition/zib-TreatmentDirective-TreatmentPermitted" />
                </modifierExtension>
                <identifier>
                    <use value="usual" />
                    <system value="urn:oid:1.2.840.114350.1.13.260.1.7.2.798268" />
                    <value value="313885" />
                </identifier>
                <status value="active" />
                <category>
                    <coding>
                        <system value="http://terminology.hl7.org/CodeSystem/consentcategorycodes" />
                        <code value="acd" />
                        <display value="Advance Directive" />
                    </coding>
                    <coding>
                        <system value="urn:oid:1.2.840.114350.1.13.260.1.7.4.796783.100" />
                        <code value="1" />
                        <display value="Full Code" />
                    </coding>
                    <coding>
                        <system value="http://snomed.info/sct" />
                        <code value="11291000146105" />
                    </coding>
                </category>
                <patient>
                    <reference value="https://hostname/instance/api/FHIR/STU3/Consent?patient=ed7aXNgz9-
    VaUIk2e.6Bgjg3&category=http://snomed.info/sct|11291000146105" />
                    <display value="Giles, F.C." />
                </patient>
                <period>
                    <start value="2021-09-24T19:28:28Z" />
                </period>
                <dateTime value="2021-09-24T19:28:28Z" />
                <policy>
                    <extension url="http://hl7.org/fhir/StructureDefinition/data-absent-reason">
                        <valueCode value="unknown" />
                    </extension>
                </policy>
            </Consent>
        </resource>
        <search>
            <mode value="match" />
        </search>
    </entry>
</Bundle>
```


Change log

Epic Version | Description | Type
November 2022 | Code systems for the following code sets now return a URL in place of an OID: ActCode, ICD-10-CM, ICD-10-CA, ICD-10-NL, SNOMED System URL OID ActCode STU3: http://hl7.org/fhir/v3/ActCode R4: http://terminology.hl7.org/CodeSystem/v3-ActCode 2.16.840.1.113883.5.4 ICD-10-CM http://hl7.org/fhir/sid/icd-10-cm 2.16.840.1.113883.6.90 ICD-10-CA http://hl7.org/fhir/sid/icd-10-ca 2.16.840.1.113883.6.94 ICD-10-NL http://hl7.org/fhir/sid/icd-10-nl 2.16.840.1.113883.6.3.2 SNOMED http://snomed.info/sct 2.16.840.1.113883.6.96 | Breaking change
System | URL | OID
ActCode | STU3: http://hl7.org/fhir/v3/ActCode R4: http://terminology.hl7.org/CodeSystem/v3-ActCode | 2.16.840.1.113883.5.4
ICD-10-CM | http://hl7.org/fhir/sid/icd-10-cm | 2.16.840.1.113883.6.90
ICD-10-CA | http://hl7.org/fhir/sid/icd-10-ca | 2.16.840.1.113883.6.94
ICD-10-NL | http://hl7.org/fhir/sid/icd-10-nl | 2.16.840.1.113883.6.3.2
SNOMED | http://snomed.info/sct | 2.16.840.1.113883.6.96

32.2.4 Consent.Search (Document) (STU3)

File: site/apis/32-Security/2-STU3/10261-Consent-Search-Document-STU3.html
Epic API ID | 10261
FHIR version | STU3
Categories | Security
API type | Industry-Standard
USCDI | No
Available in inpatient and other contexts | Yes
HTTP method | GET
URL template | /api/FHIR/STU3/Consent?category={category}&patient={patient}&status={status}&subject={subject}
Supports OAuth 2.0 | True
Supported user types | Backend Systems and Non-OAuth 2.0, Clinicians or Administrative Users, Patients
Performs scope validation | False
Source | https://fhir.epic.com/Specifications?api=10261

Description

The FHIR Consent resource defines a concept around collected consent for some action. Consent resources correspond to Document records in Epic. The Consent.Search interaction returns only metadata about the patient consent document(s) on file, such as the type of consent and the effective period. This resource does not return the consent document itself. Typically this resource is used to check whether a consent document is on file for a particular patient.

This API can return data about one or more Consent documents that match the search parameters.

In the August 2021 version of Epic and earlier, the Consent (Document) API is intended only for provider-facing applications. Providers can use this API to access all types of consent documents. Starting in the November 2021 version of Epic, patients can also use the the Consent (Document) API to look up information on their consent regarding Advance Directives and Living Will, or Power of Attorney.

This resource respects patient-level break-the-glass checks and document type security checks as configured in Epic. Audit events are logged to the patient audit trail when a consent document is accessed by this resource.

Request parameters

Name | Type | Optional | Array | Cardinality | Description

category | String | True | | | The type of consent document. This value follows the specification of the FHIR ConsentCategoryCodes (consent-category) value set, which includes LOINC codes and other identifiers. Additional values can be mapped by Epic organizations if desired. Supported consent categories include: 59284-0 (Consent Document) 64292-6 (Release of information Consent Document) 84095-9 (Do not resuscitate) 59284-0 (Clinical Consent) 64293-4 (Procedure Consent Document) 61359-6 (Anesthesia Consent Document) 61358-8 (Surgical operation Consent Document) 52027-0 (Abortion Consent Document) 52029-6 (Sterilization Consent Document) 64300-7 (Organ donation Consent Document) 83930-8 (Research Consent Document) This API also supports SNOMED code 11341000146107-Advance Directive as a category.

patient | String | Either patient or subject must be provided. If both are provided, they must match. | | | FHIR ID for the Patient the consent applies to.

status | String | True | | | The state of the consent. This value follows the specification of the FHIR ConsentState value set. The following values have default out-of-the-box support in Epic. Additional statuses can be mapped by Epic organizations if desired. draft Corresponds to Epic value 11-Not Received active Corresponds to Epic values 10-Received and 20-Accepted rejected Corresponds to Epic value 1-Unknown entered-in-error Corresponds to Epic value 35-Error inactive Does not correspond to any Epic value by default proposed Does not correspond to any Epic value by default Consent documents with no status specified in Epic are returned when searching without a status parameter

subject | String | Either patient or subject must be provided. If both are provided, they must match. | | | FHIR ID for the Patient the consent applies to.

Response elements

Name | Type | Optional | Array | Cardinality | Description

Bundle | Bundle | False | | | Resource bundle. For more information, refer to the FHIR specification.

Bundle.entry | Entry | False | Yes | | A single entry in the resource bundle.

Bundle.entry.resource | ResourceContainer | False | | | A single resource returned as part of this bundle.

Bundle.entry.resource.Consent | Consent | False | | | An instance of the R4 Consent resource.

Bundle.entry.resource.Consent.category | CodeableConcept | False | Yes | | The type of consent document. This value follows the specification of the FHIR ConsentCategoryCodes (consent-category) value set, which includes LOINC codes and other identifiers. Additional values can be mapped by Epic organizations if desired. Supported consent categories include: 59284-0 (Consent Document) 64292-6 (Release of information Consent Document) 84095-9 (Do not resuscitate) 59284-0 (Clinical Consent) 64293-4 (Procedure Consent Document) 61359-6 (Anesthesia Consent Document) 61358-8 (Surgical operation Consent Document) 52027-0 (Abortion Consent Document) 52029-6 (Sterilization Consent Document) 64300-7 (Organ donation Consent Document) 83930-8 (Research Consent Document) This API also supports SNOMED code 11341000146107-Advance Directive as a . For organizations located in the Netherlands, this API also supports category mapping based on the WilsverklaringTypeCodelijst.

Bundle.entry.resource.Consent.extension (also: comment) | Extension | True | Yes | | Description of a document.

Bundle.entry.resource.Consent.consentingParty | Reference | True | Yes | | This element applies only to organizations in the Netherlands. The person who is the legal representative or is appointed as the authorized representative in the signed consent. In Epic, this is represented by the patient's active Health Care Agent. If a patient has no active Health Care Agent, this returns the patient's own name.

Bundle.entry.resource.Consent.dateTime | String | False

Bundle.entry.resource.Consent.id | String | False | | | The Consent FHIR ID.

Bundle.entry.resource.Consent.identifier | Identifier | False | | | Document ID (ID value + ID Type).

Bundle.entry.resource.Consent.meta | Meta | True | | | The document metadata.

Bundle.entry.resource.Consent.meta.profile | String | True | | | Available in Netherlands environments only. This element shows that this API conforms to the profile connected to the following canonical url: http://nictiz.nl/fhir/StructureDefinition/zib-AdvanceDirective

Bundle.entry.resource.Consent.patient | Reference | False | | | FHIR reference for the Patient the consent applies to.

Bundle.entry.resource.Consent.period | Period | True | | | Time period that this document is valid for. Open-ended periods are represented by the absence of an EndDate and EndTime.

Bundle.entry.resource.Consent.policy | Policy | False | Yes | | The policy of the consent document.

Bundle.entry.resource.Consent.policy.extension (also: data-absent-reason) | Extension | False | Yes | | Always set to "http://hl7.org/fhir/StructureDefinition/data-absent-reason".

Bundle.entry.resource.Consent.status | String | False | | | The state of the consent. This value follows the specification of the FHIR ConsentState value set. The following values have default out-of-the-box support in Epic. Additional statuses can be mapped by Epic organizations if desired. draft Corresponds to Epic value 11-Not Received active Corresponds to Epic values 10-Received and 20-Accepted rejected Corresponds to Epic value 1-Unknown entered-in-error Corresponds to Epic value 35-Error inactive Does not correspond to any Epic value by default proposed Does not correspond to any Epic value by default Consent documents with no status specified in Epic return all statuses.

Sample request

```
https://hostname/instance/api/FHIR/STU3/Consent?patient=eafUq-Rq7rj37QX5fTQxg9Q3
```

Sample response


```
{
  "resourceType": "Bundle",
  "type": "searchset",
```

```
"total": 3,
"link": [
  {
    "relation": "self",
    "url": "https://vs-icx18-25/Interconnect-FHIR-Current-Stage1-Primary-
  Unsecured/api/FHIR/STU3/Consent?patient=eivR2DL-WAG8Nxx3xBYUu7A3"
  }
],
"entry": [
  {
    "link": [
      {
        "relation": "self",
        "url": "https://vs-icx18-25/Interconnect-FHIR-Current-Stage1-Primary-
  Unsecured/api/FHIR/STU3/Consent/eohl7R2Vlqb6G28xH4sYyK8zPeTjGBGbTDV3rHgSHZCk3"
      }
    ],
    "fullUrl": "https://vs-icx18-25/Interconnect-FHIR-Current-Stage1-Primary-
  Unsecured/api/FHIR/STU3/Consent/eohl7R2Vlqb6G28xH4sYyK8zPeTjGBGbTDV3rHgSHZCk3",
    "resource": {
      "resourceType": "Consent",
      "id": "eohl7R2Vlqb6G28xH4sYyK8zPeTjGBGbTDV3rHgSHZCk3",
      "extension": [
        {
          "valueString": "Will.pdf",
          "url": "http://nictiz.nl/fhir/StructureDefinition/Comment"
        }
      ],
      "identifier": {
        "use": "usual",
        "system": "urn:oid:1.2.840.114350.1.13.5325.1.7.2.686783",
        "value": "1040113"
      },
      "status": "active",
      "category": [
        {
          "coding": [
            {
              "system": "urn:oid:1.2.840.114350.1.13.5325.1.7.4.686783.100",
              "code": "10",
              "display": "Advance Directives and Living Will"
            },
            {
              "system": "http://snomed.info/sct",
              "code": "11341000146107"
            }
          ],
          "text": "Advance Directives and Living Will"
        }
      ],
      "patient": {
        "reference": "https://vs-icx18-25/Interconnect-FHIR-Current-Stage1-Primary-
  Unsecured/api/FHIR/STU3/Patient/eivR2DL-WAG8Nxx3xBYUu7A3",
        "display": "Patient, Sample"
      },
      "period": {
        "start": "2023-03-13T19:54:19Z",
        "end": "2023-04-12T04:59:59Z"
      },
      "dateTime": "2023-03-13T19:54:19Z",
      "policy": [
        {
          "extension": [
            {
              "valueCode": "unknown",
              "url": "http://hl7.org/fhir/StructureDefinition/data-absent-reason"
            }
          ]
        }
      ]
    },
    "search": {
      "mode": "match"
    }
  },
  {
    "link": [
      {
        "relation": "self",
        "url": "https://vs-icx18-25/Interconnect-FHIR-Current-Stage1-Primary-
  Unsecured/api/FHIR/STU3/Consent/e1RjA4Uo63HhX4q6uvGF4kPiyNT66AiuBWWpJXFgntl83"
      }
    ],
    "fullUrl": "https://vs-icx18-25/Interconnect-FHIR-Current-Stage1-Primary-
  Unsecured/api/FHIR/STU3/Consent/e1RjA4Uo63HhX4q6uvGF4kPiyNT66AiuBWWpJXFgntl83",
    "resource": {
      "resourceType": "Consent",
      "id": "e1RjA4Uo63HhX4q6uvGF4kPiyNT66AiuBWWpJXFgntl83",
      "identifier": {
```

```
      "use": "usual",
      "system": "urn:oid:1.2.840.114350.1.13.5325.1.7.2.686783",
      "value": "1040135"
    },
    "status": "active",
    "category": [
      {
        "coding": [
          {
            "system": "urn:oid:1.2.840.114350.1.13.5325.1.7.4.686783.100",
            "code": "10",
            "display": "Advance Directives and Living Will"
          },
          {
            "system": "http://snomed.info/sct",
            "code": "11341000146107"
          }
        ],
        "text": "Advance Directives and Living Will"
      }
    ],
    "patient": {
      "reference": "https://vs-icx18-25/Interconnect-FHIR-Current-Stage1-Primary-
Unsecured/api/FHIR/STU3/Patient/eivR2DL-WAG8Nxx3xBYUu7A3",
      "display": "Patient, Sample"
    },
    "period": {
      "start": "2023-03-13",
      "end": "2023-03-13"
    },
    "dateTime": "2023-03-13T20:08:13Z",
    "policy": [
      {
        "extension": [
          {
            "valueCode": "unknown",
            "url": "http://hl7.org/fhir/StructureDefinition/data-absent-reason"
          }
        ]
      }
    ]
  },
  "search": {
    "mode": "match"
  }
},
{
  "link": [
    {
      "relation": "self",
      "url": "https://vs-icx18-25/Interconnect-FHIR-Current-Stage1-Primary-Unsecured/api/FHIR/STU3/Consent/eWN0LfIzt
--GyrAQB-YSBzk6XI1pL97vIwPVdBWx16jI3"
    }
  ],
  "fullUrl": "https://vs-icx18-25/Interconnect-FHIR-Current-Stage1-Primary-Unsecured/api/FHIR/STU3/Consent/eWN0LfIzt
--GyrAQB-YSBzk6XI1pL97vIwPVdBWx16jI3",
  "resource": {
    "resourceType": "Consent",
    "id": "eWN0LfIzt--GyrAQB-YSBzk6XI1pL97vIwPVdBWx16jI3",
    "extension": [
      {
        "valueString": "Attorney.pdf",
        "url": "http://nictiz.nl/fhir/StructureDefinition/Comment"
      }
    ],
    "identifier": {
      "use": "usual",
      "system": "urn:oid:1.2.840.114350.1.13.5325.1.7.2.686783",
      "value": "1040973"
    },
    "status": "active",
    "category": [
      {
        "coding": [
          {
            "system": "urn:oid:1.2.840.114350.1.13.5325.1.7.4.686783.100",
            "code": "11",
            "display": "Power of Attorney"
          },
          {
            "system": "http://snomed.info/sct",
            "code": "11341000146107"
          }
        ],
        "text": "Power of Attorney"
      }
    ],
    "patient": {
      "reference": "https://vs-icx18-25/Interconnect-FHIR-Current-Stage1-Primary-
```

```
    Unsecured/api/FHIR/STU3/Patient/eivR2DL-WAG8Nxx3xBYUu7A3",
          "display": "Patient, Sample"
        },
        "period": {
          "start": "2023-03-14T17:53:39Z",
          "end": "2023-03-17"
        },
        "dateTime": "2023-03-14T17:53:39Z",
        "policy": [
          {
            "extension": [
              {
                "valueCode": "unknown",
                "url": "http://hl7.org/fhir/StructureDefinition/data-absent-reason"
              }
            ]
          }
        ]
      },
      "search": {
        "mode": "match"
      }
    }
  ]
}
```


32.3 Security: Non-FHIR

File: site/apis/32-Security/3-Non-FHIR/index.html

* ActivateUser
* CreateUser (2014)
* CreateUser (2026)
* DeleteAll2FATokens
* DeleteUser
* ForcePasswordChange
* GetUserPagerID
* InactivateUser
* Introspect
* Set2FATempPasscode
* Set2FAToken
* SetDutchName
* SetReportSelectionCriteria
* SetUserExternalPasswords
* SetUserPagerID
* SetUserPassword
* UpdateAuthorizedServiceAreas
* UpdateBIDefaultUser
* UpdateCommunityUser
* UpdateFacilityDepartmentList
* UpdateLoginDepartments
* UpdateUser (2014)
* UpdateUser (2026)
* UpdateUserGroups
* ViewAuthorizedServiceAreas
* ViewBIDefaultUser
* ViewCommunityUser
* ViewCurrentReportSelectionCriteria
* ViewFacilityDepartmentList
* ViewLoginDepartments
* ViewUser (2014)
* ViewUser (2026)
* ViewUserGroups

32.3.1 ActivateUser

File: site/apis/32-Security/3-Non-FHIR/205-ActivateUser.html
Epic API ID | 205
FHIR version | Non-FHIR
Categories | Security
API type | Epic Public
API group | Personnel Management Group
USCDI | No
HTTP method | POST
URL template | api/epic/2012/Security/PersonnelManagement/ActivateUser/Personnel/User/Activate?UserID={UserID}
Supports OAuth 2.0 | True
Supported user types | Backend Systems and Non-OAuth 2.0
Performs scope validation | False
SOAP namespace | urn:Epic-com:Security.2012.Services.PersonnelManagement
WSDL | Epic.Security.GeneratedServices/PersonnelManagement.svc?wsdl
Source | https://fhir.epic.com/Specifications?api=205

Request parameters

Name | Type | Optional | Array | Cardinality | Description
AuditUserID | String | True | | | Identifier for the user performing the activation.
AuditUserIDType | String | True | | | Audit User Identifier type. You can specify Internal, External, CID, SystemLogin, Alias, or an Identity ID. Defaults to Internal if not provided.
AuditUserPassword | String | True | | | This parameter is no longer used. The Epic password of the Audit User.
UserID | String | False | | | Identifier for the user to be activated.
UserIDType | String | True | | | User Identifier type. You can specify Internal, External, CID, SystemLogin, Alias, or an Identity ID. Defaults to Internal if not provided.

Response elements

Name | Type | Optional | Array | Cardinality | Description
Messages | String | False | | | A list of human-readable warning messages.

Errors

Code | Severity | Description | Example
LICENSE-NOT-FOUND | None | | Organization is not licensed for this feature.
NO-USER-ID | None | | Missing required parameter UserID.
NO-USER-FOUND | None | | Unable to resolve UserID and UserIDType combination to a unique user record.
INVALID-RECORD-TYPE | None | | UserID and UserIDType identify a background user or template record, which is not a valid target for this service.
EMP-LOCK-FAILED | None | | The user record is currently locked by another user.
ITEMS-PROTECTED | None | | Cannot fulfill the request because an item is EMFI or Data Courier protected and this is not the owning deployment.

Sample request

```
<ActivateUser xmlns="urn:Epic-com:Security.2012.Services.PersonnelManagement">
  <UserID>13423</UserID>
  <UserIDType>External</UserIDType>
  <AuditUserID>MSMITH</AuditUserID>
  <AuditUserIDType>SystemLogin</AuditUserIDType>
  <AuditUserPassword>P3ars Plz</AuditUserPassword>
</ActivateUser>
```

Sample response

```
<ActivateUserResponse xmlns="urn:Epic-com:Security.2011.Services.PersonnelManagement">
  <ActivateUserResult xmlns:i="http://www.w3.org/2001/XMLSchema-instance">
    <Messages xmlns:b="http://schemas.microsoft.com/2003/10/Serialization/Arrays">
      <b:string>User block status cleared</b:string>
    </Messages>
  </ActivateUserResult>
</ActivateUserResponse>
```

32.3.2 CreateUser (2014)

File: site/apis/32-Security/3-Non-FHIR/345-CreateUser-2014.html
Epic API ID | 345
FHIR version | Non-FHIR
Categories | Security
API type | Epic Public
API group | Personnel Management Group
USCDI | No
HTTP method | PUT
URL template | api/epic/2014/Security/PersonnelManagement/CreateUser?UserInternalID={UserInternalID}&Name={Name}&ContactDate={ContactDate}&ContactComment={ContactComment}&SystemLoginID={SystemLoginID}&LDAPOverrideID={LDAPOverrideID}&IsActive={IsActive}&StartDate={StartDate}&EndDate={EndDate}&UserAlias={UserAlias}&UserPhotoPath={UserPhotoPath}&Sex={Sex}&ReportGrouper1={ReportGrouper1}&ReportGrouper2={ReportGrouper2}&ReportGrouper3={ReportGrouper3}&Notes={Notes}&UserDictionaryPath={UserDictionaryPath}&ProviderAtLoginOption={ProviderAtLoginOption}&AuditUserID={AuditUserID}&AuditUserIDType={AuditUserIDType}&AuditUserPassword={AuditUserPassword}

Supports OAuth 2.0 | True
Supported user types | Backend Systems and Non-OAuth 2.0
Performs scope validation | False
SOAP namespace | urn:Epic-com:Security.2014.Services.PersonnelManagement
WSDL | Epic.Security.GeneratedServices/PersonnelManagement.svc?wsdl
Source | https://fhir.epic.com/Specifications?api=345

Remarks

If any error is encountered, the record will not be created. If input is unambigious and valid, but poorly formatted, it may be corrected automatically. If so, the response will contain descriptions of what was changed in the messages element.

Request parameters

Name | Type | Optional | Array | Cardinality | Description
AuditUserID | String | True
AuditUserIDType | String | True
AuditUserPassword | String | True | | | This parameter is no longer used. The Epic password of the Audit User.
AuthenticationConfigurationID | IDType | True | | | A generic identifier.
AuthenticationConfigurationID.ID | String | False | | | The identifier for this resource.
AuthenticationConfigurationID.Type | String | True | | | The type of identifier.
BlockStatus | BlockStatus | True | | | A user's block status.
BlockStatus.Comment | String | True | | | Free text comment about why the user is blocked.
BlockStatus.IsBlocked | Boolean | False | | | Should the user be blocked?
BlockStatus.Reason | String | False | | | Category value for block reason if we are blocking the user.
CategoryReportGrouper1 | String | True | | | A list of values for the user's first category report grouper item, which does not have an Epic-defined meaning.
CategoryReportGrouper2 | String | True | | | A list of values for the user's second category report grouper item, which does not have an Epic-defined meaning.
CategoryReportGrouper3 | String | True | | | A list of values for the user's third category report grouper item, which does not have an Epic-defined meaning.
CategoryReportGrouper4 | String | True | | | A list of values for the user's fourth category report grouper item, which does not have an Epic-defined meaning.
CategoryReportGrouper5 | String | True | | | A list of values for the user's fifth category report grouper item, which does not have an Epic-defined meaning.
CategoryReportGrouper6 | String | True | | | A list of values for the user's sixth category report grouper item, which does not have an Epic-defined meaning.
ContactComment | String | True | | | Contact comment that will appear for the initial contact.
ContactDate | String | True | | | Date to use for the newly created contact. Defaults to current date if not set.
CustomUserDictionaries | IndexedString | True | Yes | | Starting in Epic May 2020, this element is no longer supported. List of values for custom user dictionary files.
CustomUserDictionaries.Index | String | False | | | Number indicating priority of the value - smaller numbers override larger ones.
CustomUserDictionaries.Value | String | False | | | Value of this string.
DefaultLoginDepartmentID | IDType | True | | | A generic identifier.
EmployeeDemographics | EmployeeDemographics | True | Yes | | Customizable items used for demographic information about a user specific to a contact.
EmployeeDemographics.EmployeeDemographic1 | String | True | | | Value of the first employee demographic item. Typically job code.
EmployeeDemographics.EmployeeDemographic2 | String | True | | | Value of the second employee demographic item. Typically payroll department.
EmployeeDemographics.EmployeeDemographic3 | String | True | | | Value of the third employee demographic item. Typically location.
EmployeeDemographics.Index | String | False | | | Number indicating the ordering of the values. Should be a sequence of consecutive numbers starting from 1.
EndDate | String | True | | | The date at which the user becomes inactive.
ExternalIdentifiers | ExternalIdentifier | True | Yes | | List of external ID items set for this user.
ExternalIdentifiers.Identifier | String | False | | | External identifier for the user.
ExternalIdentifiers.IdentifierType | String | False | | | External identifier type.
ExternalIdentifiers.IsActive | Boolean | False | | | True if the identifier is active.
IdentityIDs | IDType | True | Yes | | A generic identifier.
InBasketClassifications | String | True | | | List of values for user In Basket classifications.
IsActive | Boolean | True
LDAPOverrideID | String | True | | | A string that can be provided to identify the user to the LDAP server in place of the SystemLogin. Need not be unique. Maximum length 254 characters.
LinkedProviderID | IDType | True | | | A generic identifier.
LinkedTemplatesConfig | LinkedTemplatesConfig | True | | | The linked template setup for the user.
LinkedTemplatesConfig.AppliedTemplateID | IDType | False | | | A generic identifier.
LinkedTemplatesConfig.AvailableLinkableTemplates | AvailableTemplateSetup | False | Yes
LinkedTemplatesConfig.AvailableLinkableTemplates.EndDate | String | True | | | The date after which the user should no longer have access to this template.
LinkedTemplatesConfig.AvailableLinkableTemplates.LinkedTemplateID | IDType | False | | | A generic identifier.
LinkedTemplatesConfig.AvailableLinkableTemplates.LoginTypes | String | True | | | The applications for which this template should be applied automatically.
LinkedTemplatesConfig.AvailableLinkableTemplates.StartDate | String | True | | | The date the user should begin to have access to this template.
LinkedTemplatesConfig.DefaultTemplateID | IDType | False | | | A generic identifier.
Name | String | True | | | User's name in LAST, FIRST MI format. If a UserComplexName is provided this is ignored. If one is not, this is required.
Notes | String | True

PrimaryManager | IDType | True | | | A generic identifier.
ProviderAtLoginOption | String | True
ReportGrouper1 | String | True | | | New value for the user's first free-text report grouper item, which does not have an Epic-defined meaning.
ReportGrouper2 | String | True | | | New value for the user's second free-text report grouper item, which does not have an Epic-defined meaning.
ReportGrouper3 | String | True | | | New value for the user's third free-text report grouper item, which does not have an Epic-defined meaning.
Sex | String | True
StartDate | String | True | | | The date on which the user becomes active. Defaults to the current date if not set.
SystemLoginID | String | True | | | New value for the user's system login. Must be unique. Maximum length 254 characters.
UserAlias | String | True | | | New value for the user's alias.
UserComplexName | PersonName | True | | | Individual pieces of a user's name. If UserName is not provided, this is required. If this is given, it will be used instead of UserName.
UserComplexName.FirstName | String | False | | | Person’s first name
UserComplexName.GivenNameInitials | String | False | | | Person’s given name initials
UserComplexName.LastName | String | False | | | Person’s last name
UserComplexName.MiddleName | String | True | | | Person’s middle name
UserDictionaryPath | String | True
UserInternalID | String | False | | | An internal ID to assign for the new user, or * to automatically generate one.
UserPhotoPath | String | True | | | A URL or file path identifying the location of a picture to show for this user. Maximum length 260 characters.
UserRoleIDs | IndexedRecordIn | True | Yes
UserRoleIDs.Identifier | IDType | False | | | A generic identifier.
UserRoleIDs.Index | String | False | | | Number indicating the ordering of the record. Should be a sequence of consecutive numbers starting from 1.
UsersManagers | IDType | True | Yes | | A generic identifier.
UserSubtemplateIDs | IndexedRecordIn | True | Yes
UserSubtemplateIDs.Identifier | IDType | False | | | A generic identifier.
UserSubtemplateIDs.Index | String | False | | | Number indicating the ordering of the record. Should be a sequence of consecutive numbers starting from 1.

Response elements

Name | Type | Optional | Array | Cardinality | Description
Messages | String | True
UserIDs | IDType | False | Yes | | A generic identifier.

Errors

Code | Severity | Description | Example
LICENSE-NOT-FOUND | None | | Organization is not licensed for this feature.
NO-INTERNAL-ID | None | | Missing required parameter InternalID.
NO-NAME | None | | Missing both UserName and UserComplexName.
NO-INDEX | None | | Missing index value for an ordered multiple response item.
EMP-NO-CREATE | None | | Cannot create new EMP records in this deployment.
EMP-LOCK-FAILED | None | | The user record is currently locked by another user.
ID-IN-USE | None | | InternalID was specified but it is already in use.
CREATE-USER-FAILED | None | | User creation failed.
CREATE-CONTACT-FAILED | None | | Error creating initial contact for user.
ASSIGN-USER-ID-FAILED | None | | Automatic internal ID assignment failed.
INVALID-NAME | None | | Invalid value provided for Name.
NO-LAST-NAME | None | | A last name is required.
INVALID-LAST-NAME | None | | Last name can contain only alphabetic and punctuation characters.
INVALID-GIVEN-NAME-INITIALS | None | | Given name initials must end in a period.
TEMPLATE-ITEM | None | | Attempted to set an item that is defined by a template.
SUBTEMPLATE-ITEM | None | | Attempted to set an item that is defined by a subtemplate.
ITEMS-PROTECTED | None | | Cannot fulfill the request because an item is EMFI/DC protected and this is not the owning deployment.
INVALID-CONTACT-DATE | None | | Contact date provided is invalid or out of range.
INVALID-SYSTEM-LOGIN-ID | None | | System login value provided is invalid or already in use.
INVALID-SYSTEM-LOGIN-ID-LENGTH | None | | System login cannot exceed 192 characters.
INVALID-USER-ALIAS-LENGTH | None | | User alias cannot exceed 192 characters.
INVALID-REPORT-GROUPER1-LENGTH | None | | Report grouper 1 cannot exceed 254 characters.
INVALID-REPORT-GROUPER2-LENGTH | None | | Report grouper 2 cannot exceed 254 characters.
INVALID-REPORT-GROUPER3-LENGTH | None | | Report grouper 3 cannot exceed 254 characters.
INVALID-START-DATE | None | | Invalid value provided for start date.
INVALID-END-DATE | None | | Invalid value provided for end date.
INVALID-ACTIVE-DATES | None | | Start date is after end date.
INVALID-USER-ROLE-ID | None | | Invalid value provided for a user role.
INVALID-CUSTOM-DICT | None | | Invalid value provided for CustomUserDictionaries.
INVALID-DICT-PATH | None | | Invalid value provided for UserDictionaryPath.
INVALID-SUBTEMPLATES | None | | Attempted to set a total of more than 7 subtemplates.
INVALID-SUBTEMPLATE-ID | None | | Linked subtemplate ID and ID type did not match an active linked template record.
INVALID-AUTH-CONFIG-ID | None | | Authentication configuration ID and ID type did not match a record.
INVALID-BLOCK-STATUS-REASON | None | | Invalid value provided for block status reason.
INVALID-LINKED-PROVIDER-ID | None | | Invalid ID/Type combination for Linked Provider.
INVALID-LOGIN-DEPT-ID | None | | Invalid ID/Type combination for DefaultLoginDepartment.
INVALID-EXTERNAL-ID | None | | Invalid value provided for an external identifier.

NO-EXTERNAL-ID-TYPE | None | | Missing external identifier type.
DUP-EXTERNAL-ID-TYPE | None | | External ID types list cannot contain duplicate values.
INVALID-IDENTITY-ID-TYPE | None | | Identity ID type provided did not match descriptor of a valid ID type.
INVALID-IDENTITY-ID | None | | Identity ID provided already in use or does not meet requirements for that ID type.
SET-NAME-FAILED | None | | Error setting name for user.
TEMPLATE-FAILED | None | | Error setting template for user.
SUBTEMPLATE-FAILED | None | | Error setting subtemplate for user.
IDENTITY-ID-ERROR | None | | Error setting Identity IDs for user.
INVALID-LDAP-OVERRIDE-ID-LENGTH | None | | LDAPOverrideID cannot exceed 192 characters.
INVALID-USER-PHOTO-PATH | None | | Invalid value provided for UserPhotoPath
INVALID-USER-PHOTO-PATH-LENGTH | None | | UserPhotoPath cannot exceed 260 characters.
INVALID-LINKED-TEMPLATES-CONFIG | None | | The linked template setup provided was invalid
INVALID-DEFAULT-TEMPLATE-ID | None | | Default template ID did not match a record.
INVALID-APPLIED-TEMPLATE-ID | None | | Applied template ID did not match a record.
INVALID-LOGIN-TYPE | None | | Login type does not match a category value.
INVALID-SEX | None | | Invalid value provided for Sex.
INVALID-EMPLOYEE-DEMOGRAPHICS1 | None | | Invalid value provided for first employee demographic item.
INVALID-EMPLOYEE-DEMOGRAPHICS2 | None | | Invalid value provided for second employee demographic item.
INVALID-EMPLOYEE-DEMOGRAPHICS3 | None | | Invalid value provided for third employee demographic item.
INVALID-CATEGORY-REPORT-GROUPER1 | None | | Invalid value provided for first category report grouper item.
INVALID-CATEGORY-REPORT-GROUPER2 | None | | Invalid value provided for second category report grouper item.
INVALID-CATEGORY-REPORT-GROUPER3 | None | | Invalid value provided for third category report grouper item.
INVALID-CATEGORY-REPORT-GROUPER4 | None | | Invalid value provided for fourth category report grouper item.
INVALID-CATEGORY-REPORT-GROUPER5 | None | | Invalid value provided for fifth category report grouper item.
INVALID-CATEGORY-REPORT-GROUPER6 | None | | Invalid value provided for sixth category report grouper item.
INVALID-NOTES | None | | Invalid value provided for Notes.
INVALID-NOTES-LENGTH | None | | Notes cannot exceed 2000 characters.
INVALID-PRIMARY-MANAGER-ID | None | | Invalid ID/Type combination for PrimaryManager.
INVALID-USER-MANAGER | None | | Invalid ID/Type combination for a user's manager.
INVALID-PROVIDER-AT-LOGIN-OPTION | None | | Invalid value provided for ProviderAtLoginOption.
INVALID-INDEX | None | | The index value contains non-numeric characters, is less than 1, or is greater than the maximum value.
INVALID-CONTACT-COMMENT-LENGTH | None | | Contact comments cannot exceed 100 characters.
INVALID-IB-CLASS | None | | In Basket classification did not match a category value or has duplicate values.

Sample request

```
<CreateUser xmlns="urn:Epic-com:Security.2014.Services.PersonnelManagement" xmlns:xsi="http://www.w3.org/2001/XMLSchema-
    instance">
  <UserInternalID xsi:nil="false">*</UserInternalID>
  <ContactComment xsi:nil="false">Created</ContactComment>
  <SystemLoginID xsi:nil="false">MSEEGER2</SystemLoginID>
  <LDAPOverrideID xsi:nil="false">MSEEGER</LDAPOverrideID>
  <IsActive>false</IsActive>
  <StartDate xsi:nil="false">t+5</StartDate>
  <Sex xsi:nil="false">Male</Sex>
  <ReportGrouper1 xsi:nil="false">AMB</ReportGrouper1>
  <ReportGrouper3 xsi:nil="false">324613</ReportGrouper3>
  <CategoryReportGrouper4 xsi:nil="false">
    <string xmlns="http://schemas.microsoft.com/2003/10/Serialization/Arrays" xsi:nil="false">4</string>
    <string xmlns="http://schemas.microsoft.com/2003/10/Serialization/Arrays" xsi:nil="false">101</string>
    <string xmlns="http://schemas.microsoft.com/2003/10/Serialization/Arrays" xsi:nil="false">102</string>
    <string xmlns="http://schemas.microsoft.com/2003/10/Serialization/Arrays" xsi:nil="false">103</string>
  </CategoryReportGrouper4>
  <Notes xsi:nil="false">New amb physician starting next week</Notes>
  <UserComplexName xsi:nil="false">
    <FirstName xsi:nil="false">Marty</FirstName>
    <LastName xsi:nil="false">Seeger</LastName>
    <MiddleName xsi:nil="false">Test</MiddleName>
    <PrimaryTitle xsi:nil="false">Dr.</PrimaryTitle>
  </UserComplexName>
  <LinkedTemplatesConfig xsi:nil="false">
    <AppliedTemplateID xsi:nil="false">
      <ID xmlns="urn:Epic-com:Security.2012.Services.PersonnelManagement" xsi:nil="false">T00272</ID>
      <Type xmlns="urn:Epic-com:Security.2012.Services.PersonnelManagement" xsi:nil="false">External</Type>
    </AppliedTemplateID>
    <AvailableLinkableTemplates xsi:nil="false">
      <AvailableTemplateSetup xsi:nil="false">
        <LinkedTemplateID xsi:nil="false">
          <ID xmlns="urn:Epic-com:Security.2012.Services.PersonnelManagement" xsi:nil="false">T00271</ID>
          <Type xmlns="urn:Epic-com:Security.2012.Services.PersonnelManagement" xsi:nil="false">External</Type>
        </LinkedTemplateID>
        <LoginTypes xsi:nil="false">
          <string xmlns="http://schemas.microsoft.com/2003/10/Serialization/Arrays" xsi:nil="false">6</string>
          <string xmlns="http://schemas.microsoft.com/2003/10/Serialization/Arrays" xsi:nil="false">3</string>
        </LoginTypes>
        <StartDate xsi:nil="false">w+2</StartDate>
      </AvailableTemplateSetup>
      <AvailableTemplateSetup xsi:nil="false">
        <LinkedTemplateID xsi:nil="false">
          <ID xmlns="urn:Epic-com:Security.2012.Services.PersonnelManagement" xsi:nil="false">T00272</ID>
          <Type xmlns="urn:Epic-com:Security.2012.Services.PersonnelManagement" xsi:nil="false">External</Type>
```

```
        </LinkedTemplateID>
      </AvailableTemplateSetup>
    </AvailableLinkableTemplates>
    <DefaultTemplateID xsi:nil="false">
      <ID xmlns="urn:Epic-com:Security.2012.Services.PersonnelManagement" xsi:nil="false">T00272</ID>
      <Type xmlns="urn:Epic-com:Security.2012.Services.PersonnelManagement" xsi:nil="false">External</Type>
    </DefaultTemplateID>
  </LinkedTemplatesConfig>
  <UserSubtemplateIDs xsi:nil="false">
    <IndexedRecordIn xmlns="urn:Epic-com:Security.2012.Services.PersonnelManagement" xsi:nil="false">
      <Identifier xsi:nil="false">
        <ID xsi:nil="false">T00031</ID>
        <Type xsi:nil="false">External</Type>
      </Identifier>
      <Index xsi:nil="false">1</Index>
    </IndexedRecordIn>
    <IndexedRecordIn xmlns="urn:Epic-com:Security.2012.Services.PersonnelManagement" xsi:nil="false">
      <Identifier xsi:nil="false">
        <ID xsi:nil="false">T00113</ID>
        <Type xsi:nil="false">External</Type>
      </Identifier>
      <Index xsi:nil="false">2</Index>
    </IndexedRecordIn>
  </UserSubtemplateIDs>
  <EmployeeDemographics xsi:nil="false">
    <EmployeeDemographics xsi:nil="false">
      <EmployeeDemographic1 xsi:nil="false">1</EmployeeDemographic1>
      <EmployeeDemographic2 xsi:nil="false">3</EmployeeDemographic2>
      <Index xsi:nil="false">1</Index>
    </EmployeeDemographics>
    <EmployeeDemographics xsi:nil="false">
      <EmployeeDemographic2 xsi:nil="false">3</EmployeeDemographic2>
      <Index xsi:nil="false">2</Index>
    </EmployeeDemographics>
    <EmployeeDemographics xsi:nil="false">
      <EmployeeDemographic2 xsi:nil="false">77</EmployeeDemographic2>
      <Index xsi:nil="false">3</Index>
    </EmployeeDemographics>
  </EmployeeDemographics>
  <LinkedProviderID xsi:nil="false">
    <ID xmlns="urn:Epic-com:Security.2012.Services.PersonnelManagement" xsi:nil="false">13144114</ID>
    <Type xmlns="urn:Epic-com:Security.2012.Services.PersonnelManagement" xsi:nil="false">External</Type>
  </LinkedProviderID>
</CreateUser>
```

Sample response

```
<CreateUserResponse xmlns="urn:Epic-com:Security.2014.Services.PersonnelManagement">
  <CreateUserResult xmlns:i="http://www.w3.org/2001/XMLSchema-instance">
    <Messages xmlns:a="http://schemas.microsoft.com/2003/10/Serialization/Arrays">
      <a:string/>
    </Messages>
    <UserIDs xmlns:a="urn:Epic-com:Security.2012.Services.PersonnelManagement">
      <a:IDType>
        <a:ID>130298547</a:ID>
        <a:Type>CID</a:Type>
      </a:IDType>
      <a:IDType>
        <a:ID>20743</a:ID>
        <a:Type>External</a:Type>
      </a:IDType>
      <a:IDType>
        <a:ID> 20743</a:ID>
        <a:Type>Internal</a:Type>
      </a:IDType>
      <a:IDType>
        <a:ID>SEEGER, MARTY TEST</a:ID>
        <a:Type>Name</a:Type>
      </a:IDType>
      <a:IDType>
        <a:ID>MSEEGER2</a:ID>
        <a:Type>SystemLogin</a:Type>
      </a:IDType>
    </UserIDs>
  </CreateUserResult>
</CreateUserResponse>
```

32.3.3 CreateUser (2026)

File: site/apis/32-Security/3-Non-FHIR/40303-CreateUser-2026.html
Epic API ID | 40303
FHIR version | Non-FHIR
Categories | Security
API type | Epic Public
API group | Personnel Management Group
USCDI | No

HTTP method | PUT
URL template | /api/epic/2026/Security/PersonnelManagement/CreateUser/?UserInternalID={UserInternalID}
Supports OAuth 2.0 | True
Supported user types | Backend Systems and Non-OAuth 2.0
Performs scope validation | False
Source | https://fhir.epic.com/Specifications?api=40303

Request parameters

Name | Type | Optional | Array | Cardinality | Description
AuditUserID | IDType | False | | | A generic identifier.
AuthenticationConfigurationID | IDType | False | | | A generic identifier.
BlockStatus | BlockStatus | False | | | A user's block status.
BlockStatus.Comment | String | False | | | Free text comment about why the user is blocked.
BlockStatus.IsBlocked | Boolean | False | | | Should the user be blocked?
BlockStatus.Reason | String | False | | | Category value for block reason if we are blocking the user.
CategoryReportGrouper1 | String | True | Yes
CategoryReportGrouper2 | String | True | Yes
CategoryReportGrouper3 | String | True | Yes
CategoryReportGrouper4 | String | False | Yes
CategoryReportGrouper5 | String | True | Yes
CategoryReportGrouper6 | String | False | Yes
ContactComment | String | False
ContactDate | String | False
DefaultLoginDepartmentID | IDType | True | | | A generic identifier.
EmployeeDemographics | EmployeeDemographics | False | Yes | | Customizable items used for demographic information about a user specific to a contact.
EmployeeDemographics.EmployeeDemographic1 | String | False | | | Value of the first employee demographic item. Typically job code.
EmployeeDemographics.EmployeeDemographic2 | String | False | | | Value of the second employee demographic item. Typically payroll department.
EmployeeDemographics.EmployeeDemographic3 | String | False | | | Value of the third employee demographic item. Typically location.
EmployeeDemographics.Index | String | False | | | Number indicating the ordering of the values. Should be a sequence of consecutive numbers starting from 1.
EndDate | String | False
ExternalIdentifiers | ExternalIdentifier | False | Yes | | List of external ID items set for this user.
ExternalIdentifiers.Identifier | String | False | | | External identifier for the user.
ExternalIdentifiers.IdentifierType | String | False | | | External identifier type.
ExternalIdentifiers.IsActive | Boolean | False | | | True if the identifier is active.
IdentityIDs | IDType | False | Yes | | A generic identifier.
InBasketClassifications | String | False | Yes
IsActive | Boolean | True
LDAPOverrideID | String | False
LinkedProviderID | IDType | True | | | A generic identifier.
LinkedTemplatesConfig | LinkedTemplatesConfig2026 | True
LinkedTemplatesConfig.AppliedTemplateID | IDType | False | | | A generic identifier.
LinkedTemplatesConfig.AvailableLinkableTemplates | AvailableTemplateSetup2026 | False | Yes
LinkedTemplatesConfig.DefaultTemplateID | IDType | False | | | A generic identifier.
Name | String | False
Notes | String | False
PrimaryManager | IDType | False | | | A generic identifier.
ProviderAtLoginOption | String | False
ReportGrouper1 | String | True
ReportGrouper2 | String | True
ReportGrouper3 | String | True
Sex | String | True
StartDate | String | True
SystemLoginID | String | True
UserAlias | String | True
UserComplexName | PersonName | False | | | Individual pieces of a user's name. If UserName is not provided, this is required. If this is given, it will be used instead of UserName.
UserComplexName.AcademicTitle | String | False | | | Person’s academic title for name
UserComplexName.FatherName | String | False | | | Name of person’s father
UserComplexName.FirstName | String | False | | | Person’s first name
UserComplexName.GivenNameInitials | String | False | | | Person’s given name initials
UserComplexName.GrandfatherName | String | False | | | Name of person’s grandfather
UserComplexName.LastName | String | False | | | Person’s last name
UserComplexName.LastNamePrefix | String | False | | | Person’s last name prefix
UserComplexName.MiddleName | String | False | | | Person’s middle name
UserComplexName.PrimaryTitle | String | False | | | Person’s primary title
UserComplexName.SpouseLastName | String | False | | | Last name of person’s spouse
UserComplexName.SpouseLastNameFirst | Boolean | False | | | Whether the last name of the person’s spouse is listed first
UserComplexName.SpousePrefix | String | False | | | The prefix of the spouse’s name
UserComplexName.Suffix | String | False | | | Person name suffix
UserInternalID | String | False

UserPhotoPath | String | False
UserRoleIDs | IndexedRecordIn | True | Yes
UserRoleIDs.Identifier | IDType | False | | | A generic identifier.
UserRoleIDs.Index | String | False | | | Number indicating the ordering of the record. Should be a sequence of consecutive numbers starting from 1.
UsersManagers | IDType | True | Yes | | A generic identifier.
UserSubtemplateIDs | IndexedRecordIn | True | Yes
UserSubtemplateIDs.Identifier | IDType | False | | | A generic identifier.
UserSubtemplateIDs.Index | String | False | | | Number indicating the ordering of the record. Should be a sequence of consecutive numbers starting from 1.

Response elements

Name | Type | Optional | Array | Cardinality | Description
Messages | String | True | Yes
UserIDs | IDType | False | Yes | | A generic identifier.
UserIDs.ID | String | False | | | The identifier for this resource.
UserIDs.Type | String | False | | | The type of identifier.

Errors

Code | Severity | Description | Example
LICENSE-NOT-FOUND | None | | Organization is not licensed for this feature.
NO-INTERNAL-ID | None | | Missing required parameter InternalID.
NO-NAME | None | | Missing both UserName and UserComplexName.
NO-INDEX | None | | Missing index value for an ordered multiple response item.
EMP-NO-CREATE | None | | Cannot create new EMP records in this deployment.
EMP-LOCK-FAILED | None | | The user record is currently locked by another user.
ID-IN-USE | None | | InternalID was specified but it is already in use.
CREATE-USER-FAILED | None | | User creation failed.
CREATE-CONTACT-FAILED | None | | Error creating initial contact for user.
ASSIGN-USER-ID-FAILED | None | | Automatic internal ID assignment failed.
INVALID-NAME | None | | Invalid value provided for Name.
NO-LAST-NAME | None | | A last name is required.
INVALID-LAST-NAME | None | | Last name can contain only alphabetic and punctuation characters.
INVALID-GIVEN-NAME-INITIALS | None | | Given name initials must end in a period.
TEMPLATE-ITEM | None | | Attempted to set an item that is defined by a template.
SUBTEMPLATE-ITEM | None | | Attempted to set an item that is defined by a subtemplate.
ITEMS-PROTECTED | None | | Cannot fulfill the request because an item is EMFI/DC protected and this is not the owning deployment.
INVALID-CONTACT-DATE | None | | Contact date provided is invalid or out of range.
INVALID-SYSTEM-LOGIN-ID | None | | System login value provided is invalid or already in use.
INVALID-SYSTEM-LOGIN-ID-LENGTH | None | | System login cannot exceed 192 characters.
INVALID-USER-ALIAS-LENGTH | None | | User alias cannot exceed 192 characters.
INVALID-REPORT-GROUPER1-LENGTH | None | | Report grouper 1 cannot exceed 254 characters.
INVALID-REPORT-GROUPER2-LENGTH | None | | Report grouper 2 cannot exceed 254 characters.
INVALID-REPORT-GROUPER3-LENGTH | None | | Report grouper 3 cannot exceed 254 characters.
INVALID-START-DATE | None | | Invalid value provided for start date.
INVALID-END-DATE | None | | Invalid value provided for end date.
INVALID-ACTIVE-DATES | None | | Start date is after end date.
INVALID-USER-ROLE-ID | None | | Invalid value provided for a user role.
INVALID-CUSTOM-DICT | None | | Invalid value provided for CustomUserDictionaries.
INVALID-DICT-PATH | None | | Invalid value provided for UserDictionaryPath.
INVALID-SUBTEMPLATES | None | | Attempted to set a total of more than 7 subtemplates.
INVALID-SUBTEMPLATE-ID | None | | Linked subtemplate ID and ID type did not match an active linked template record.
INVALID-AUTH-CONFIG-ID | None | | Authentication configuration ID and ID type did not match a record.
INVALID-BLOCK-STATUS-REASON | None | | Invalid value provided for block status reason.
INVALID-LINKED-PROVIDER-ID | None | | Invalid ID/Type combination for Linked Provider.
INVALID-LOGIN-DEPT-ID | None | | Invalid ID/Type combination for DefaultLoginDepartment.
INVALID-EXTERNAL-ID | None | | Invalid value provided for an external identifier.
NO-EXTERNAL-ID-TYPE | None | | Missing external identifier type.
DUP-EXTERNAL-ID-TYPE | None | | External ID types list cannot contain duplicate values.
INVALID-IDENTITY-ID-TYPE | None | | Identity ID type provided did not match descriptor of a valid ID type.
INVALID-IDENTITY-ID | None | | Identity ID provided already in use or does not meet requirements for that ID type.
SET-NAME-FAILED | None | | Error setting name for user.
TEMPLATE-FAILED | None | | Error setting template for user.
SUBTEMPLATE-FAILED | None | | Error setting subtemplate for user.
IDENTITY-ID-ERROR | None | | Error setting Identity IDs for user.
INVALID-AUDIT-USER-PASS | None | | An incorrect password was provided for the audit user, or the user account is blocked or inactive.
INVALID-LDAP-OVERRIDE-ID-LENGTH | None | | LDAPOverrideID cannot exceed 192 characters.
INVALID-USER-PHOTO-PATH | None | | Invalid value provided for UserPhotoPath
INVALID-USER-PHOTO-PATH-LENGTH | None | | UserPhotoPath cannot exceed 260 characters.
INVALID-LINKED-TEMPLATES-CONFIG | None | | The linked template setup provided was invalid.
INVALID-DEFAULT-TEMPLATE-ID | None | | Default template ID did not match a record.
INVALID-APPLIED-TEMPLATE-ID | None | | Applied template ID did not match a record.

INVALID-LOGIN-TYPE | None | | Login type does not match a category value.
INVALID-SEX | None | | Invalid value provided for Sex.
INVALID-EMPLOYEE-DEMOGRAPHICS1 | None | | Invalid value provided for first employee demographic item.
INVALID-EMPLOYEE-DEMOGRAPHICS2 | None | | Invalid value provided for second employee demographic item.
INVALID-EMPLOYEE-DEMOGRAPHICS3 | None | | Invalid value provided for third employee demographic item.
INVALID-CATEGORY-REPORT-GROUPER1 | None | | Invalid value provided for first category report grouper item.
INVALID-CATEGORY-REPORT-GROUPER2 | None | | Invalid value provided for second category report grouper item.
INVALID-CATEGORY-REPORT-GROUPER3 | None | | Invalid value provided for third category report grouper item.
INVALID-CATEGORY-REPORT-GROUPER4 | None | | Invalid value provided for fourth category report grouper item.
INVALID-CATEGORY-REPORT-GROUPER5 | None | | Invalid value provided for fifth category report grouper item.
INVALID-CATEGORY-REPORT-GROUPER6 | None | | Invalid value provided for sixth category report grouper item.
INVALID-NOTES | None | | Invalid value provided for Notes.
INVALID-NOTES-LENGTH | None | | Notes cannot exceed 2000 characters.
INVALID-PRIMARY-MANAGER-ID | None | | Invalid ID/Type combination for PrimaryManager.
INVALID-USER-MANAGER | None | | Invalid ID/Type combination for a user's manager.
INVALID-PROVIDER-AT-LOGIN-OPTION | None | | Invalid value provided for ProviderAtLoginOption.
INVALID-INDEX | None | | The index value contains non-numeric characters, is less than 1, or is greater than the maximum value.
INVALID-CONTACT-COMMENT-LENGTH | None | | Contact comments cannot exceed 100 characters.
INVALID-IB-CLASS | None | | In Basket classification did not match a category value or has duplicate values.
INVALID-LOGIN-BLUEPRINT-ID | None | | Login Blueprint ID did not match a record.
INVALID-LOGIN-BLUEPRINT | None | | Login Blueprint is not of valid type.

Sample request


```
{
  "CreateUser": {
    "UserInternalID": "*",
    "ContactComment": "Created",
    "SystemLoginID": "MSEEGER2",
    "LDAPOverrideID": "MSEEGER",
    "IsActive": false,
    "StartDate": "t+5",
    "Sex": "Male",
    "ReportGrouper1": "AMB",
    "ReportGrouper3": "324613",
    "CategoryReportGrouper4": [
      "4",
      "101",
      "102",
      "103"
    ],
    "Notes": "New amb physician starting next week",
    "UserComplexName": {
      "FirstName": "Marty",
      "LastName": "Seeger",
      "MiddleName": "Test",
      "PrimaryTitle": "Dr."
    },
    "LinkedTemplatesConfig": {
      "AppliedTemplateID": {
        "ID": "T00272",
        "Type": "External"
      },
      "AvailableLinkableTemplates": {
        "AvailableTemplateSetup2026": {
          "LinkedTemplateID": {
            "ID": "T00271",
            "Type": "External"
          },
          "LoginBlueprintID": {
            "ID": "L001",
            "Type": "External"
          },
          "LoginTypes": [
            "6",
            "3"
          ],
          "StartDate": "w+2"
        }
      },
      "DefaultTemplateID": {
        "ID": "T00272",
        "Type": "External"
      }
    },
    "UserSubtemplateIDs": [
      {
        "Identifier": {
          "ID": "T00031",
          "Type": "External"
        },
        "Index": 1
      },
      {
```

```
        "Identifier": {
          "ID": "T00113",
          "Type": "External"
        },
        "Index": 2
      }
    ],
    "EmployeeDemographics": {
      "EmployeeDemographics": [
        {
          "EmployeeDemographic1": "1",
          "EmployeeDemographic2": "3",
          "Index": 1
        },
        {
          "EmployeeDemographic2": "3",
          "Index": 2
        },
        {
          "EmployeeDemographic2": "77",
          "Index": 3
        }
      ]
    },
    "LinkedProviderID": {
      "ID": "13144114",
      "Type": "External"
    },
    "AuditUserID": {
      "ID": "234898",
      "Type": "External"
    }
  }
}
```


Sample response


```
{
  "CreateUserResponse": {
    "CreateUserResult": {
      "Messages": [],
      "UserIDs": [
        {
          "ID": "130298547",
          "Type": "CID"
        },
        {
          "ID": "20743",
          "Type": "External"
        },
        {
          "ID": " 20743",
          "Type": "Internal"
        },
        {
          "ID": "SEEGER, MARTY TEST",
          "Type": "Name"
        },
        {
          "ID": "MSEEGER2",
          "Type": "SystemLogin"
        }
      ]
    }
  }
}
```


32.3.4 DeleteAll2FATokens

File: site/apis/32-Security/3-Non-FHIR/11668-DeleteAll2FATokens.html
Epic API ID | 11668
FHIR version | Non-FHIR
Categories | Security
API type | Epic Public
API group | Personnel Management Group
USCDI | No
HTTP method | POST
URL template | api/epic/2018/Security/PersonnelManagement/DeleteAll2FATokens/DeleteAll2FATokens
Supports OAuth 2.0 | True
Supported user types | Backend Systems and Non-OAuth 2.0
Performs scope validation | False
Source | https://fhir.epic.com/Specifications?api=11668

Remarks

Request parameters

Name | Type | Optional | Array | Cardinality | Description
AuditUserID | IDType | True | | | A generic identifier.
AuditUserID.ID | String | False | | | The identifier for this resource.
AuditUserID.Type | String | True | | | The type of identifier.
UserID | IDType | False | | | A generic identifier.
UserID.ID | String | False | | | The identifier for this resource.
UserID.Type | String | True | | | The type of identifier.

Errors

Code | Severity | Description | Example
ITEMS-PROTECTED | None | | Can't be edited on this deployment.
TEMPLATE-IEM | None | | This item is defined by the template and cannot be set directly.
INVALID-RECORD-TYPE | None | | A user record was identified, but the record is a background user or (sub)template record, which is not a valid target for this service.
NO-USER-FOUND | None | | A user ID was received, but a corresponding record could not be found, or the identifier did not produce a unique user record.
LICENSE-NOT-FOUND | None | | Organization is not licensed for this feature.
NO-USER-ID | None | | Web service request did not specify the required UserID field.
INVALID-AUDIT-USER | None | | The audit user passed in could not be found.

32.3.5 DeleteUser

File: site/apis/32-Security/3-Non-FHIR/207-DeleteUser.html
Epic API ID | 207
FHIR version | Non-FHIR
Categories | Security
API type | Epic Public
API group | Personnel Management Group
USCDI | No
HTTP method | POST
URL template | api/epic/2012/Security/PersonnelManagement/DeleteUser/Personnel/User/Delete?UserID={UserID}
Supports OAuth 2.0 | True
Supported user types | Backend Systems and Non-OAuth 2.0
Performs scope validation | False
SOAP namespace | urn:Epic-com:Security.2012.Services.PersonnelManagement
WSDL | Epic.Security.GeneratedServices/PersonnelManagement.svc?wsdl
Source | https://fhir.epic.com/Specifications?api=207

Request parameters

Name | Type | Optional | Array | Cardinality | Description
AuditUserID | String | True
AuditUserIDType | String | True
AuditUserPassword | String | True | | | This parameter is no longer used. The Epic password of the Audit User.
UserID | String | False
UserIDType | String | True

Response elements

Name | Type | Optional | Array | Cardinality | Description
Messages | String | False

Errors

Code | Severity | Description | Example
LICENSE-NOT-FOUND | None | | Organization is not licensed for this feature.
NO-USER-ID | None | | Missing required parameter UserID.
NO-USER-FOUND | None | | Unable to resolve UserID and UserIDType combination to a unique user record.
INVALID-RECORD-TYPE | None | | UserID and UserIDType identify a background user or template record, which is not a valid target for this service.
EMP-LOCK-FAILED | None | | The user record is currently locked by another user.
INVALID-USER-DEPLOYMENT | None | | Attempted to delete record on non-owning deployment.
EMP-DELETE-FAILED | None | | Unable to delete requested record.

Sample request

```
<DeleteUser xmlns="urn:Epic-com:Security.2012.Services.PersonnelManagement">
  <UserID>RHAMMOND</UserID>
  <UserIDType>SystemLogin</UserIDType>
  <AuditUserID>555</AuditUserID>
  <AuditUserIDType>External</AuditUserIDType>
  <AuditUserPassword>P3ars Plz</AuditUserPassword>
</DeleteUser>
```

Sample response

```
<DeleteUserResponse xmlns="urn:Epic-com:Security.2012.Services.PersonnelManagement">
  <DeleteUserResult xmlns:i="http://www.w3.org/2001/XMLSchema-instance">
    <Messages xmlns:b="http://schemas.microsoft.com/2003/10/Serialization/Arrays"/>
  </DeleteUserResult>
</DeleteUserResponse>
```

32.3.6 ForcePasswordChange

File: site/apis/32-Security/3-Non-FHIR/208-ForcePasswordChange.html
Epic API ID | 208
FHIR version | Non-FHIR
Categories | Security
API type | Epic Public
API group | Personnel Management Group
USCDI | No
HTTP method | POST
URL template | api/epic/2012/Security/PersonnelManagement/ForcePasswordChange/Personnel/User/ForcePasswordChange?UserID={UserID}
Supports OAuth 2.0 | True
Supported user types | Backend Systems and Non-OAuth 2.0
Performs scope validation | False
SOAP namespace | urn:Epic-com:Security.2012.Services.PersonnelManagement
WSDL | Epic.Security.GeneratedServices/PersonnelManagement.svc?wsdl
Source | https://fhir.epic.com/Specifications?api=208

Request parameters

Name | Type | Optional | Array | Cardinality | Description
AuditUserID | String | True
AuditUserIDType | String | True
AuditUserPassword | String | True | | | This parameter is no longer used. The Epic password of the Audit User.
UserID | String | False
UserIDType | String | True

Response elements

Name | Type | Optional | Array | Cardinality | Description
Messages | String | False

Errors

Code | Severity | Description | Example
LICENSE-NOT-FOUND | None | | Organization is not licensed for this feature.
NO-USER-ID | None | | Missing required parameter UserID.
NO-USER-FOUND | None | | Unable to resolve UserID and UserIDType combination to a unique user record.
INVALID-RECORD-TYPE | None | | UserID and UserIDType identify a background user or template record, which is not a valid target for this service.
EMP-LOCK-FAILED | None | | The user record is currently locked by another user.
ITEMS-PROTECTED | None | | Cannot fulfill the request because an item is EMFI/DC protected and this is not the owning deployment.
NON-NATIVE-AUTH | None | | The user record selected uses an authentication method other than an Epic password.

Sample request

```
<ForcePasswordChange xmlns="urn:Epic-com:Security.2012.Services.PersonnelManagement">
  <UserID>MSEEGER</UserID>
  <UserIDType>SystemLogin</UserIDType>
  <AuditUserID> 1355452</AuditUserID>
  <AuditUserIDType>CID</AuditUserIDType>
  <AuditUserPassword>P3ars Plz</AuditUserPassword>
</ForcePasswordChange>
```

Sample response

```
<ForcePasswordChangeResponse xmlns="urn:Epic-com:Security.2012.Services.PersonnelManagement">
  <ForcePasswordChangeResult xmlns:i="http://www.w3.org/2001/XMLSchema-instance">
    <Messages xmlns:b="http://schemas.microsoft.com/2003/10/Serialization/Arrays" i:nil="true"/>
  </ForcePasswordChangeResult>
</ForcePasswordChangeResponse>
```

32.3.7 GetUserPagerID

File: site/apis/32-Security/3-Non-FHIR/487-GetUserPagerID.html
Epic API ID | 487
FHIR version | Non-FHIR
Categories | Security
API type | Epic Public
API group | Personnel Management Group

USCDI | No
HTTP method | POST
URL template | api/epic/2017/Security/PersonnelManagement/GetUserPagerID/GetUserPagerID
Supports OAuth 2.0 | True
Supported user types | Backend Systems and Non-OAuth 2.0
Performs scope validation | False
SOAP namespace | urn:Epic-com:Security.2017.Services.PersonnelManagement
WSDL | {baseURL}/wcf/Epic.Security.GeneratedServices/PersonnelManagement.svc?wsdl
Source | https://fhir.epic.com/Specifications?api=487

Request parameters

Name | Type | Optional | Array | Cardinality | Description
AuditUserID | IDType | True | | | A generic identifier.
AuditUserID.ID | String | False | | | The identifier for this resource.
AuditUserID.Type | String | True | | | The type of identifier.
UserID | IDType | False | | | A generic identifier.
UserID.ID | String | False | | | The identifier for this resource.
UserID.Type | String | True | | | The type of identifier.

Response elements

Name | Type | Optional | Array | Cardinality | Description
PagerID | String | True

Errors

Code | Severity | Description | Example
LICENSE-NOT-FOUND | None | | The organization is not licensed for this feature.
NO-USER-ID | None | | Missing required parameter UserID.
NO-USER-FOUND | None | | Unable to resolve UserID and UserIDType combination to a unique user record.
INVALID-AUDIT-USER-ID | None | | Unable to resolve UserID and UserIDType combination to a unique user record.
INVALID-RECORD-TYPE | None | | UserID and UserIDType identify a background user or template record, which is not a valid target for this service.

Sample request

```
<GetUserPagerID xmlns="urn:Epic-com:Security.2017.Services.PersonnelManagement"
    xmlns:xsi="http://www.w3.org/2001/XMLSchema-instance">
  <!--idtype occurs:0,1-->
  <UserID xsi:nil="false">
    <!--string occurs:0,1-->
    <ID xmlns="urn:Epic-com:Security.2012.Services.PersonnelManagement" xsi:nil="false">20524</ID>
    <!--string occurs:0,1-->
    <Type xmlns="urn:Epic-com:Security.2012.Services.PersonnelManagement" xsi:nil="false">External</Type>
  </UserID>
  <!--idtype occurs:0,1-->
  <AuditUserID xsi:nil="false">
    <!--string occurs:0,1-->
    <ID xmlns="urn:Epic-com:Security.2012.Services.PersonnelManagement" xsi:nil="false">20524</ID>
    <!--string occurs:0,1-->
    <Type xmlns="urn:Epic-com:Security.2012.Services.PersonnelManagement" xsi:nil="false">External</Type>
  </AuditUserID>
</GetUserPagerID>
```

Sample response

```
<?xml version="1.0" encoding="utf-16"?>
<s:Envelope xmlns:s="http://schemas.xmlsoap.org/soap/envelope/">
<s:Body>
<GetUserPagerIDResponse xmlns="urn:Epic-com:Security.2017.Services.PersonnelManagement">
<GetUserPagerIDResult xmlns:i="http://www.w3.org/2001/XMLSchema-instance">
<PagerID>user@email.com</PagerID>
</GetUserPagerIDResult>
</GetUserPagerIDResponse>
</s:Body>
</s:Envelope>
```

32.3.8 InactivateUser

File: site/apis/32-Security/3-Non-FHIR/209-InactivateUser.html
Epic API ID | 209
FHIR version | Non-FHIR
Categories | Security
API type | Epic Public
API group | Personnel Management Group
USCDI | No
HTTP method | POST
URL template | api/epic/2012/Security/PersonnelManagement/InactivateUser/Personnel/User/Inactivate?UserID={UserID}
Supports OAuth 2.0 | True

Supported user types | Backend Systems and Non-OAuth 2.0
Performs scope validation | False
SOAP namespace | urn:Epic-com:Security.2012.Services.PersonnelManagement
WSDL | Epic.Security.GeneratedServices/PersonnelManagement.svc?wsdl
Source | https://fhir.epic.com/Specifications?api=209

Request parameters

Name | Type | Optional | Array | Cardinality | Description
AuditUserID | String | True
AuditUserIDType | String | True
AuditUserPassword | String | True | | | This parameter is no longer used. The Epic password of the Audit User.
UserID | String | False
UserIDType | String | True

Response elements

Name | Type | Optional | Array | Cardinality | Description
Messages | String | False

Errors

Code | Severity | Description | Example
LICENSE-NOT-FOUND | None | | Organization is not licensed for this feature.
NO-USER-ID | None | | Missing required parameter UserID.
NO-USER-FOUND | None | | Unable to resolve UserID and UserIDType combination to a unique user record.
INVALID-RECORD-TYPE | None | | UserID and UserIDType identify a background user or template record, which is not a valid target for this service.
EMP-LOCK-FAILED | None | | The user record is currently locked by another user.
ITEMS-PROTECTED | None | | Cannot fulfill the request because an item is EMFI/DC protected and this is not the owning deployment.

Sample request

```
<InactivateUser xmlns="urn:Epic-com:Security.2012.Services.PersonnelManagement">
  <UserID>13423</UserID>
  <UserIDType>External</UserIDType>
  <AuditUserID>MSMITH</AuditUserID>
  <AuditUserIDType>SystemLogin</AuditUserIDType>
  <AuditUserPassword>P3ars Plz</AuditUserPassword>
</InactivateUser>
```

Sample response

```
<InactivateUserResponse xmlns="urn:Epic-com:Security.2011.Services.PersonnelManagement">
  <InactivateUserResult xmlns:i="http://www.w3.org/2001/XMLSchema-instance">
    <Messages xmlns:b="http://schemas.microsoft.com/2003/10/Serialization/Arrays">
      <b:string>User active status was already set to requested value</b:string>
    </Messages>
  </InactivateUserResult>
</InactivateUserResponse>
```

32.3.9 Introspect

File: site/apis/32-Security/3-Non-FHIR/488-Introspect.html
Epic API ID | 488
FHIR version | Non-FHIR
Categories | Security
API type | USCDI
API group | OAuth 2.0, including Introspect
A la carte | Epic Public Level 0 API
USCDI | Yes
Available in inpatient and other contexts | Yes
ONC certification products | EpicCare Ambulatory Base, EpicCare Inpatient Base
ONC certification versions | Epic 2018
HTTP method | POST
URL template | oauth2/Introspect
Supports OAuth 2.0 | True
Supported user types | Backend Systems and Non-OAuth 2.0, Clinicians or Administrative Users, Patients
Performs scope validation | False
WSDL | None
Source | https://fhir.epic.com/Specifications?api=488

Description

This web service implements the OAuth2 token introspection endpoint defined by RFC 7662. It allows an application using OAuth2 secured services to get data associated with an OAuth2 token. One particularly useful function of this service is to allow the client application to determine the user associated with the OAuth2 token. You can also use an API manager to

validate a token when choosing to allow a request through.

Requests can be formatted as application/x-www-form-urlencoded in accordance with RFC 7662, but Epic also supports a JSON request body.

Request

Name | Type | Optional | Array | Description
token | String | False | | The OAuth2 token to perform introspection on.
epic_user_id_type | String | True | | The desired format to have the user id returned in. Options include Internal, External, and any valid IIT descriptor. If omitted, the service uses FHIR by default, which is the practitioner resource for users (EMP) and patient resource for patient access accounts (WPR).

Response

Name | Type | Optional | Array | Description
active | Boolean | False | | Boolean indicator of whether or not the token is active.
scope | String | True | | A space separated list of the scopes associated with the token.
client_id | String | True | | The identifier of the OAuth2 client that requested the token.
username | String | True | | A human-readable identifier for the user who authorized this token. This is System Login (I EMP 45) for users (EMP) and MyChart Login (I WPR 110) for patient access accounts (WPR).
exp | Long | True | | The token's expiration time formatted as Unix Epoch time.
sub | String | True | | The identifier of the subject of the token. (User ID)
iss | String | True | | The identifier of the issuer of the token.
jti | String | True | | Unique string identifier for the token.
epic_user_type | String | True | | The master file associated with the user ID returned in the "sub" response property. (EMP or WPR)

Errors

Code | Severity | Description | Example
INVALID-ID-TYPE-REQUESTED | None | | The value provided in the epic_user_type parameter is not a valid ID type. Valid options include "internal", "external", and valid IIT descriptors.

Sample request

```
{
  "token": "-iIFMi62E3oYtXOH3ffjeoRnRywNMC0pb5e2E_pOLqUszQNCM46w6QWaXYEpPY9uEQBi7x_WkL4Wxunodn5aoBbfi8TIE3aEWWo-
    csLR42Ho0YahqjvrcCYY81N_t2Jl",
  "epic_user_id_type": "internal"
}
```

Sample response

```
{
  "active": true,
  "scope": "ADVERSEEVENT.READ ADVERSEEVENT.SEARCH ADVERSEREACTION.READ ADVERSEREACTION.SEARCH ALLERGYINTOLERANCE.READ
    ALLERGYINTOLERANCE.SEARCH APPOINTMENT.READ APPOINTMENT.SEARCH APPOINTMENTRESPONSE.READ APPOINTMENTRESPONSE.SEARCH
    AUDITEVENT.READ BINARY.READ BINARY.SEARCH CAREPLAN.READ CAREPLAN.SEARCH CARETEAM.READ CARETEAM.SEARCH
    CODESYSTEM.READ CODESYSTEM.SEARCH CONDITION.READ CONDITION.SEARCH CONFORMANCE.READ DARYL.READ DEVICE.READ
    DEVICE.SEARCH DIAGNOSTICORDER.READ DIAGNOSTICORDER.SEARCH DIAGNOSTICREPORT.READ DIAGNOSTICREPORT.SEARCH
    DIRECTORY.SEARCH DOCUMENTREFERENCE.READ DOCUMENTREFERENCE.SEARCH ENCOUNTER.READ ENCOUNTER.SEARCH ENDPOINT.READ
    FAMILYHISTORY.READ FAMILYHISTORY.SEARCH FAMILYMEMBERHISTORY.SEARCH FAMILYMEMBERHISTORY.WRITE FHIRSERVICE.READ
    GOAL.READ GOAL.SEARCH IMMUNIZATION.READ IMMUNIZATION.SEARCH LIST.READ LOCATION.READ LOCATION.SEARCH MEDICATION.READ
    MEDICATION.SEARCH MEDICATIONORDER.READ MEDICATIONORDER.SEARCH MEDICATIONPRESCRIPTION.READ
    MEDICATIONPRESCRIPTION.SEARCH MEDICATIONREQUEST.READ MEDICATIONREQUEST.SEARCH MEDICATIONSTATEMENT.READ
    MEDICATIONSTATEMENT.SEARCH OBSERVATION.READ OBSERVATION.SEARCH ORGANIZATION.READ ORGANIZATION.SEARCH PARAMETERS.READ
     PARSEREQUEST.SEARCH PATIENT.READ PATIENT.SEARCH PERSON.READ PRACTITIONER.READ PRACTITIONER.SEARCH
    PRACTITIONERROLE.READ PRACTITIONERROLE.SEARCH PROCEDURE.READ PROCEDURE.SEARCH PROCEDUREREQUEST.READ
    PROCEDUREREQUEST.SEARCH SLOT.READ SUBSCRIPTION.READ SUBSTANCE.READ SUBSTANCE.SEARCH VALUESET.READ VALUESET.SEARCH",
  "client_id": "3330fa1443fe11e4b959520281306b0a",
  "username": "EPICUSER",
  "exp": 1507168257,
  "sub": " 1",
  "iss": "https://hostname/instance/oauth2",
  "jti": "B8AFFD4D680C4FF6A859FD91DE56CDF5",
  "epic_user_type": "EMP"
}
```

32.3.10 Set2FATempPasscode

File: site/apis/32-Security/3-Non-FHIR/11667-Set2FATempPasscode.html
Epic API ID | 11667
FHIR version | Non-FHIR
Categories | Security
API type | Epic Public
API group | Personnel Management Group
USCDI | No
HTTP method | POST
URL template | /api/epic/2018/Security/PersonnelManagement/Set2FATempPasscode/Set2FATempPasscode?Passcode={Passcode}&ExpirationInstant={ExpirationInstant}

Supports OAuth 2.0 | True
Supported user types | Backend Systems and Non-OAuth 2.0
Performs scope validation | False
Source | https://fhir.epic.com/Specifications?api=11667

Remarks

This web service can also be used to remove a temporary passcode if blanks are sent in for all parameters and it also mirrors Epic's import spec functionality.

Request parameters

Name | Type | Optional | Array | Cardinality | Description
AuditUserID | IDType | False | | | A generic identifier.
AuditUserID.ID | String | False | | | The identifier for this resource.
AuditUserID.Type | String | False | | | The type of identifier.
ExpirationInstant | String | True
ExpireAfterHours | Int32 | True
Passcode | String | False
UserID | IDType | False | | | A generic identifier.
UserID.ID | String | False | | | The identifier for this resource.
UserID.Type | String | False | | | The type of identifier.

Response elements

Name | Type | Optional | Array | Cardinality | Description
Passcode | String | False

Errors

Code | Severity | Description | Example
ITEMS-PROTECTED | None | | Can't be edited on this deployment.
EMP-LOCK-FAILED | None | | Unable to obtain lock on specified user record.
INVALID-RECORD-TYPE | None | | A user record was identified, but the record is a background user or (sub)template record, which is not a valid target for this service.
NO-USER-FOUND | None | | A user ID was received, but a corresponding record could not be found, or the identifier did not produce a unique user record.
LICENSE-NOT-FOUND | None | | Organization is not licensed for this feature.
NO-USER-ID | None | | Web service request did not specify the required UserID field.
INVALID-AUDIT-USER | None | | The audit user passed in could not be found.
NO-PASSCODE | None | | No passcode was sent.
NO-EXPIRATION | None | | No expiration time was sent.
CONFLICTING-EXPIRATION | None | | Both expiration fields were filled in, and we don't know which to use.

Sample request

```
{
<Set2FATempPasscode xmlns="urn:Epic-com:Security.2018.Services.PersonnelManagement"
                    xmlns:xsi="http://www.w3.org/2001/XMLSchema-instance">
  <Passcode xsi:nil="false">*</Passcode>
  <ExpireAfterHours xsi:nil="false">4</ExpireAfterHours>
  <UserID xsi:nil="false">
    <ID xmlns="urn:Epic-com:Security.2012.Services.PersonnelManagement" xsi:nil="false">11605</ID>
    <Type xmlns="urn:Epic-com:Security.2012.Services.PersonnelManagement" xsi:nil="false">external</Type>
  </UserID>
  <AuditUserID xsi:nil="false">
    <ID xmlns="urn:Epic-com:Security.2012.Services.PersonnelManagement" xsi:nil="false">1</ID>
    <Type xmlns="urn:Epic-com:Security.2012.Services.PersonnelManagement" xsi:nil="false">external</Type>
  </AuditUserID>
</Set2FATempPasscode>
}
```

32.3.11 Set2FAToken

File: site/apis/32-Security/3-Non-FHIR/11669-Set2FAToken.html
Epic API ID | 11669
FHIR version | Non-FHIR
Categories | Security
API type | Epic Public
API group | Personnel Management Group
USCDI | No
HTTP method | POST
URL template | /api/epic/2018/Security/PersonnelManagement/Set2FAToken/Set2FAToken?Token={Token}
Supports OAuth 2.0 | True
Supported user types | Backend Systems and Non-OAuth 2.0
Performs scope validation | False

Source | https://fhir.epic.com/Specifications?api=11669

Remarks

Running this service will reset the user's token completely. The IsUserEnrolled field is optional, and if it is not sent then the user's enrolled state will not be changed.

Request parameters

Name | Type | Optional | Array | Cardinality | Description
AuditUserID | IDType | True | | | A generic identifier.
AuditUserID.ID | String | False | | | The identifier for this resource.
AuditUserID.Type | String | True | | | The type of identifier.
AuthenticatorID | IDType | False | | | A generic identifier.
AuthenticatorID.ID | String | False | | | The identifier for this resource.
AuthenticatorID.Type | String | True | | | The type of identifier.
IsUserEnrolled | Boolean | True
Token | String | False
UserID | IDType | False | | | A generic identifier.
UserID.ID | String | False | | | The identifier for this resource.
UserID.Type | String | True | | | The type of identifier.

Errors

Code | Severity | Description | Example
NO-AUTHENTICATOR | None | | The authenticator ID could not be resolved.
INVALID-AUTHENTICATOR | None | | The specified authenticator can't be used for 2FA.
INVALID-TOKEN | None | | The token must be a base-32 encoded string and can't be empty.
ITEMS-PROTECTED | None | | Can't be edited on this deployment.
TEMPLATE-ITEM | None | | This item is defined by the template and cannot be set directly.
EMP-LOCK-FAILED | None | | Unable to obtain lock on specified user record.
INVALID-RECORD-TYPE | None | | A user record was identified, but the record is a background user or (sub)template record, which is not a valid target for this service.
NO-USER-FOUND | None | | A user ID was received, but a corresponding record could not be found, or the identifier did not produce a unique user record.
LICENSE-NOT-FOUND | None | | Organization is not licensed for this feature.
NO-USER-ID | None | | Web service request did not specify the required UserID field.
INVALID-AUDIT-USER | None | | The audit user passed in could not be found.

Sample request

```
{
    <Set2FAToken xmlns="urn:Epic-com:Security.2018.Services.PersonnelManagement"
    xmlns:xsi="http://www.w3.org/2001/XMLSchema-instance">
  <!--string occurs:0,1-->
  <Token xsi:nil="false">IFBEG===</Token>
  <!--idtype occurs:0,1-->
  <UserID xsi:nil="false">
    <!--string occurs:0,1-->
    <ID xmlns="urn:Epic-com:Security.2012.Services.PersonnelManagement" xsi:nil="false">32673</ID>
    <!--string occurs:0,1-->
    <Type xmlns="urn:Epic-com:Security.2012.Services.PersonnelManagement" xsi:nil="false">EXTERNAL</Type>
  </UserID>
  <!--idtype occurs:0,1-->
  <AuditUserID xsi:nil="false">
    <!--string occurs:0,1-->
    <ID xmlns="urn:Epic-com:Security.2012.Services.PersonnelManagement" xsi:nil="false">11450</ID>
    <!--string occurs:0,1-->
    <Type xmlns="urn:Epic-com:Security.2012.Services.PersonnelManagement" xsi:nil="false">EXTERNAL</Type>
  </AuditUserID>
  <!--idtype occurs:0,1-->
  <AuthenticatorID xsi:nil="false">
    <!--string occurs:0,1-->
    <ID xmlns="urn:Epic-com:Security.2012.Services.PersonnelManagement" xsi:nil="false">41</ID>
    <!--string occurs:0,1-->
    <Type xmlns="urn:Epic-com:Security.2012.Services.PersonnelManagement" xsi:nil="false">EXTERNAL</Type>
  </AuthenticatorID>
</Set2FAToken>
}
```

Sample response

```
{
   <?xml version="1.0" encoding="utf-16"?>
<s:Envelope xmlns:s="http://schemas.xmlsoap.org/soap/envelope/">
  <s:Body>
    <Set2FATokenResponse xmlns="urn:Epic-com:Security.2018.Services.PersonnelManagement">
      <Set2FATokenResult xmlns:i="http://www.w3.org/2001/XMLSchema-instance" />
    </Set2FATokenResponse>
  </s:Body>
</s:Envelope>
```

}

32.3.12 SetDutchName

File: site/apis/32-Security/3-Non-FHIR/18-SetDutchName.html
Epic API ID | 18
FHIR version | Non-FHIR
Categories | Security
API type | Epic Public
API group | Personnel Management Group
USCDI | No
URL template | api/epic/2013/Security/PersonnelManagement/SetDutchName/Users/DutchName?UserID={UserID}&GivenNameInitials={GivenNameInitials}&LastName={LastName}
Supports OAuth 2.0 | True
Supported user types | Backend Systems and Non-OAuth 2.0
Performs scope validation | False
SOAP namespace | Epic.Security.GeneratedServices
WSDL | /wcf/Epic.Security.GeneratedServices/PersonnelManagement.svc?wsdl
Source | https://fhir.epic.com/Specifications?api=18

Request parameters

Name | Type | Optional | Array | Cardinality | Description
AcademicTitle | String | True | | | The user's academic title.
AuditUserID | String | True | | | ID of the user requesting this change. The default value is the Interconnect user.
AuditUserIDType | String | True | | | ID type used in AuditUserID. The default value is Internal.
AuditUserPassword | String | True | | | This parameter is no longer used. The Epic password of the Audit User.
ContactComment | String | True | | | Contact comment to use for the new contact. The default value is blank.
ContactDate | DateTime | True | | | Date associated with the name change.
FirstName | String | True | | | The user's first name.
GivenNameInitials | String | False | | | The user's initials. Must end in a period.
LastName | String | False | | | The user's last name. Can only contain alphabetic and punctuation characters.
LastNamePrefix | String | True | | | The last name prefix.
PrimaryTitle | String | True | | | The user's primary title.
SpouseLastName | String | True | | | The last name of the user's spouse.
SpouseLastNameFirst | Boolean | True | | | Indicates whether the last name of the user's spouse is first.
SpousePrefix | String | True | | | The prefix of the user's spouse’s last name.
Suffix | String | True | | | The suffix of the user's name.
UserID | String | False | | | ID of the user to change name for.
UserIDType | String | True | | | ID type used in UserID. Defaults to Internal.

Response elements

Name | Type | Optional | Array | Cardinality | Description
Messages | String | False | Yes

Errors

Code | Severity | Description | Example
LICENSE-NOT-FOUND | None | | Organization is not licensed for this feature.
NO-USER-ID | None | | Missing required parameter UserID.
NO-USER-FOUND | None | | Unable to resolve UserID and UserIDType combination to a unique user record.
INVALID-RECORD-TYPE | None | | UserID and UserIDType identify a background user or template record, which is not a valid target for this service.
EMP-LOCK-FAILED | None | | The user record is currently locked by another user.
CONTACT-PROTECTED | None | | Cannot fulfill the request because new contacts cannot be created on user records in this deployment.
ITEMS-PROTECTED | None | | Cannot fulfill the request because EMP .2 is EMFI/Data Courier protected and this is not the owning deployment.
INVALID-PRIMARY-TITLE | None | | The value provided for the user's primary title did not match a category value.
INVALID-ACADEMIC-TITLE | None | | The value provided for the user's academic title did not match a category value.
INVALID-SUFFIX | None | | The value provided for the user's suffix did not match a category value.
INVALID-NAME | None | | The combined user's name is not valid.
NO-LAST-NAME | None | | A blank value was provided for the user's last name.
INVALID-LAST-NAME | None | | The value provided for the user's last name contains illegal characters.

Sample request


```
{
  "UserIDType": "External",
  "ContactDate": "01/01/2026",
  "FirstName": "Ellen",
  "LastNamePrefix": "de",
  "SpouseLastName": "Witte",
  "SpousePrefix": "de",
  "Suffix": "Sr.",
  "PrimaryTitle": "Ms.",
  "AcademicTitle": "",
```

```
  "SpouseLastNameFirst": "",
  "AuditUserID": "   3434",
  "AuditUserIDType": "internal",
  "ContactComment": "Update Ellen Witte"
}
```

Sample response

```
{
  "Messages": [
    ""
  ]
}
```

32.3.13 SetReportSelectionCriteria

File: site/apis/32-Security/3-Non-FHIR/389-SetReportSelectionCriteria.html
Epic API ID | 389
FHIR version | Non-FHIR
Categories | Security
API type | Epic Public
API group | Personnel Management Group
USCDI | No
HTTP method | POST
URL template | api/epic/2015/Security/PersonnelManagement/SetReportSelectionCriteria?UserID={UserID}&UserIDType={UserIDType}&AuditUserID={AuditUserID}&AuditUserIDType={AuditUserIDType}&AuditUserPassword={AuditUserPassword}
Supports OAuth 2.0 | True
Supported user types | Backend Systems and Non-OAuth 2.0
Performs scope validation | False
SOAP namespace | urn:Epic-com:Security.2015.Services.PersonnelManagement
WSDL | Epic.Security.GeneratedServices/PersonnelManagement.svc?wsdl
Source | https://fhir.epic.com/Specifications?api=389

Request parameters

Name | Type | Optional | Array | Cardinality | Description
AuditUserID | String | True
AuditUserIDType | String | True
AuditUserPassword | String | True
Items | Item | False | Yes | | Array of items to update in this request. A tag that appears as the Name of an item here will be updated, even if it is empty.
Items.Mode | String | False | | | Default is "Replace." Can be set to "Append" for UserRoleIDs, CustomUserDictionaries, InBasketClassifications, LinkedSubtemplateIDs, UserSubtemplateIDs and CategoryReportGroupers.
Items.Name | String | False | | | Name of the item to update. EMP items will not be updated unless the parameter name (SystemLoginID, StartDate, etc) is given as a Name in the items list.
ReportAuthorizedDepartmentGroups | IndexedRecordIn | True | Yes
ReportAuthorizedDepartments | IndexedRecordIn | True | Yes
ReportAuthorizedLocations | IndexedRecordIn | True | Yes
ReportAuthorizedProviders | IndexedRecordIn | True | Yes
ReportAuthorizedServiceAreas | IndexedRecordIn | True | Yes
ReportAuthorizedServiceAreas.Identifier | IDType | False | | | A generic identifier.
ReportAuthorizedServiceAreas.Index | String | False | | | Number indicating the ordering of the record. Should be a sequence of consecutive numbers starting from 1.
ReportAuthorizedUsers | IndexedRecordIn | True | Yes
UserID | String | False
UserIDType | String | True

Response elements

Name | Type | Optional | Array | Cardinality | Description
Messages | String | False

Errors

Code | Severity | Description | Example
LICENSE-NOT-FOUND | None | | Organization is not licensed for this feature.
NO-USER-ID | None | | Missing required parameter UserID.
NO-USER-FOUND | None | | Unable to resolve UserID and UserIDType combination to a unique user record.
INVALID-RECORD-TYPE | None | | UserID and UserIDType identify a background user or template record, which is not a valid target for this service.
EMP-LOCK-FAILED | None | | The user record is currently locked by another user.
ITEMS-PROTECTED | None | | Cannot fulfill the request because an item being updated is EMFI/DC protected and this is not the owning deployment.
TEMPLATE-ITEM | None | | Attempted to set an item that is defined by a template.
SUBTEMPLATE-ITEM | None | | Attempted to set an item that is defined by a subtemplate.
NO-ITEMS-SELECTED | None | | Missing required parameter Items or it contains only invalid entries.
INVALID-ITEM-MODE | None | | Invalid value provided for Mode of an item - should be Append, Replace, or empty.

BAD-ITEM-LIST | None | | Same item is listed more than once with different modes.
INVALID-REPORT-AUTH-SERVICE-AREA | None | | A value provided for the report authorized service area is not eligible to be selected.
INVALID-REPORT-AUTH-SERVICE-AREA-ID | None | | A value provided for the report authorized service area did not match a valid record.
DUPLICATE-REPORT-AUTH-SERVICE-AREA | None | | A value provided for the report authorized service area appeared more than once in report authorized service areas.
INVALID-REPORT-AUTH-DEPARTMENT-ID | None | | A value provided for the report authorized department did not match a valid record.
DUPLICATE-REPORT-AUTH-DEPARTMENT | None | | A value provided for the report authorized department appeared more than once in report authorized departments.
INVALID-REPORT-AUTH-DEPARTMENT-GROUP | None | | A value provided for the report authorized department group is not eligible to be selected.
INVALID-REPORT-AUTH-DEPARTMENT-GROUP-ID | None | | A value provided for the report authorized department group did not match a valid record.
DUPLICATE-REPORT-AUTH-DEPARTMENT-GROUP | None | | A value provided for the report authorized department group appeared more than once in report authorized department groups.
INVALID-REPORT-AUTH-PROVIDER-ID | None | | A value provided for the report authorized provider did not match a valid record.
DUPLICATE-REPORT-AUTH-PROVIDER | None | | A value provided for the report authorized provider appeared more than once in report authorized providers.
INVALID-REPORT-AUTH-USER | None | | A value provided for the report authorized user is not eligible to be selected.
INVALID-REPORT-AUTH-USER-ID | None | | A value provided for the report authorized user did not match a valid record.
DUPLICATE-REPORT-AUTH-USER | None | | A value provided for the report authorized user appeared more than once in report authorized users.
INVALID-REPORT-AUTH-LOCATION | None | | A value provided for the report authorized location is not eligible to be selected.
INVALID-REPORT-AUTH-LOCATION-ID | None | | A value provided for the report authorized location did not match a valid record.
DUPLICATE-REPORT-AUTH-LOCATION | None | | A value provided for the report authorized location appeared more than once in report authorized locations.
NON-INTEGER-INDEX | None | | Indices must be a positive integer value.

Sample request

```
<SetReportSelectionCriteria xmlns="urn:Epic-com:Security.2015.Services.PersonnelManagement"
    xmlns:xsi="http://www.w3.org/2001/XMLSchema-instance">
  <UserID xsi:nil="false">24445</UserID>
  <UserIDType xsi:nil="false">external</UserIDType>
  <AuditUserID xsi:nil="false">11605</AuditUserID>
  <AuditUserIDType xsi:nil="false">external</AuditUserIDType>
  <AuditUserPassword xsi:nil="false">aa</AuditUserPassword>
  <ReportAuthorizedServiceAreas xsi:nil="false">
    <IndexedRecordIn xmlns="urn:Epic-com:Security.2012.Services.PersonnelManagement" xsi:nil="false">
      <Identifier xsi:nil="false">
        <ID xsi:nil="false">372</ID>
        <Type xsi:nil="false">external</Type>
      </Identifier>
      <Index xsi:nil="false">1</Index>
    </IndexedRecordIn>
    <IndexedRecordIn xmlns="urn:Epic-com:Security.2012.Services.PersonnelManagement" xsi:nil="false">
      <Identifier xsi:nil="false">
        <ID xsi:nil="false">307</ID>
        <Type xsi:nil="false">external</Type>
      </Identifier>
      <Index xsi:nil="false">2</Index>
    </IndexedRecordIn>
  </ReportAuthorizedServiceAreas>
  <ReportAuthorizedLocations xsi:nil="false">
    <IndexedRecordIn xmlns="urn:Epic-com:Security.2012.Services.PersonnelManagement" xsi:nil="false">
      <Identifier xsi:nil="false">
        <ID xsi:nil="false">8989</ID>
        <Type xsi:nil="false">external</Type>
      </Identifier>
      <Index xsi:nil="false">1</Index>
    </IndexedRecordIn>
    <IndexedRecordIn xmlns="urn:Epic-com:Security.2012.Services.PersonnelManagement" xsi:nil="false">
      <Identifier xsi:nil="false">
        <ID xsi:nil="false">307</ID>
        <Type xsi:nil="false">external</Type>
      </Identifier>
      <Index xsi:nil="false">2</Index>
    </IndexedRecordIn>
  </ReportAuthorizedLocations>
  <ReportAuthorizedDepartments xsi:nil="false">
    <IndexedRecordIn xmlns="urn:Epic-com:Security.2012.Services.PersonnelManagement" xsi:nil="false">
      <Identifier xsi:nil="false">
        <ID xsi:nil="false">440</ID>
        <Type xsi:nil="false">external</Type>
      </Identifier>
      <Index xsi:nil="false">1</Index>
    </IndexedRecordIn>
    <IndexedRecordIn xmlns="urn:Epic-com:Security.2012.Services.PersonnelManagement" xsi:nil="false">
      <Identifier xsi:nil="false">
        <ID xsi:nil="false">442</ID>
        <Type xsi:nil="false">external</Type>
      </Identifier>
      <Index xsi:nil="false">2</Index>
    </IndexedRecordIn>
  </ReportAuthorizedDepartments>
  <ReportAuthorizedDepartmentGroups xsi:nil="false">
```

```
    <IndexedRecordIn xmlns="urn:Epic-com:Security.2012.Services.PersonnelManagement" xsi:nil="false">
      <Identifier xsi:nil="false">
        <ID xsi:nil="false">315116</ID>
        <Type xsi:nil="false">external</Type>
      </Identifier>
      <Index xsi:nil="false">1</Index>
    </IndexedRecordIn>
    <IndexedRecordIn xmlns="urn:Epic-com:Security.2012.Services.PersonnelManagement" xsi:nil="false">
      <Identifier xsi:nil="false">
        <ID xsi:nil="false">315117</ID>
        <Type xsi:nil="false">external</Type>
      </Identifier>
      <Index xsi:nil="false">1</Index>
    </IndexedRecordIn>
  </ReportAuthorizedDepartmentGroups>
  <ReportAuthorizedProviders xsi:nil="false">
    <IndexedRecordIn xmlns="urn:Epic-com:Security.2012.Services.PersonnelManagement" xsi:nil="false">
      <Identifier xsi:nil="false">
        <ID xsi:nil="false">547</ID>
        <Type xsi:nil="false">Internal</Type>
      </Identifier>
      <Index xsi:nil="false">1</Index>
    </IndexedRecordIn>
    <IndexedRecordIn xmlns="urn:Epic-com:Security.2012.Services.PersonnelManagement" xsi:nil="false">
      <Identifier xsi:nil="false">
        <ID xsi:nil="false">544</ID>
        <Type xsi:nil="false">Internal</Type>
      </Identifier>
      <Index xsi:nil="false">2</Index>
    </IndexedRecordIn>
  </ReportAuthorizedProviders>
  <ReportAuthorizedUsers xsi:nil="false">
    <Identifier xmlns="urn:Epic-com:Security.2012.Services.PersonnelManagement" xsi:nil="false">
      <ID xsi:nil="false">11605</ID>
      <Type xsi:nil="false">external</Type>
    </Identifier>
    <Index xmlns="urn:Epic-com:Security.2012.Services.PersonnelManagement" xsi:nil="false"/>
  </ReportAuthorizedUsers>
  <Items xsi:nil="false">
    <Item xmlns="urn:Epic-com:Security.2012.Services.PersonnelManagement" xsi:nil="false">
      <Mode xsi:nil="false">replace</Mode>
      <Name xsi:nil="false">ReportAuthorizedProviders</Name>
    </Item>
    <Item xmlns="urn:Epic-com:Security.2012.Services.PersonnelManagement" xsi:nil="false">
      <Mode xsi:nil="false">replace</Mode>
      <Name xsi:nil="false">ReportAuthorizedUsers</Name>
    </Item>
    <Item xmlns="urn:Epic-com:Security.2012.Services.PersonnelManagement" xsi:nil="false">
      <Mode xsi:nil="false">replace</Mode>
      <Name xsi:nil="false">ReportAuthorizedDepartmentGroups</Name>
    </Item>
    <Item xmlns="urn:Epic-com:Security.2012.Services.PersonnelManagement" xsi:nil="false">
      <Mode xsi:nil="false">replace</Mode>
      <Name xsi:nil="false">ReportAuthorizedDepartments</Name>
    </Item>
    <Item xmlns="urn:Epic-com:Security.2012.Services.PersonnelManagement" xsi:nil="false">
      <Mode xsi:nil="false">replace</Mode>
      <Name xsi:nil="false">ReportAuthorizedLocations</Name>
    </Item>
    <Item xmlns="urn:Epic-com:Security.2012.Services.PersonnelManagement" xsi:nil="false">
      <Mode xsi:nil="false">replace</Mode>
      <Name xsi:nil="false">ReportAuthorizedServiceAreas</Name>
    </Item>
  </Items>
</SetReportSelectionCriteria>
```

Sample response

```
<?xml version="1.0" encoding="utf-16"?>
<s:Envelope xmlns:s="http://schemas.xmlsoap.org/soap/envelope/">
<s:Body>
<SetReportSelectionCriteriaResponse xmlns="urn:Epic-com:Security.2015.Services.PersonnelManagement">
<SetReportSelectionCriteriaResult xmlns:i="http://www.w3.org/2001/XMLSchema-instance">
<Messages xmlns:a="http://schemas.microsoft.com/2003/10/Serialization/Arrays">
<a:string />
</Messages>
</SetReportSelectionCriteriaResult>
</SetReportSelectionCriteriaResponse>
</s:Body>
</s:Envelope>
```

32.3.14 SetUserExternalPasswords

File: site/apis/32-Security/3-Non-FHIR/210-SetUserExternalPasswords.html
Epic API ID | 210
FHIR version | Non-FHIR
Categories | Security

API type | Epic Public
API group | Personnel Management Group
USCDI | No
HTTP method | POST
URL template | api/epic/2012/Security/PersonnelManagement/SetUserExternalPasswords/Personnel/User/ExternalPasswords?UserID={UserID}
Supports OAuth 2.0 | True
Supported user types | Backend Systems and Non-OAuth 2.0
Performs scope validation | False
SOAP namespace | urn:Epic-com:Security.2012.Services.PersonnelManagement
WSDL | Epic.Security.GeneratedServices/PersonnelManagement.svc?wsdl
Source | https://fhir.epic.com/Specifications?api=210

Request parameters

Name | Type | Optional | Array | Cardinality | Description
AuditUserID | String | True
AuditUserIDType | String | True
AuditUserPassword | String | True
ExternalPasswords | ExternalPassword | False | Yes
ExternalPasswords.IDType | String | False
ExternalPasswords.Password | String | False
UserID | String | False
UserIDType | String | True

Response elements

Name | Type | Optional | Array | Cardinality | Description
Messages | String | False

Errors

Code | Severity | Description | Example
LICENSE-NOT-FOUND | None | | Organization is not licensed for this feature.
NO-USER-ID | None | | Missing required parameter UserID.
NO-USER-FOUND | None | | Unable to resolve UserID and UserIDType combination to a unique user record.
NO-EXTERNAL-PASSWORDS | None | | External password array missing or empty.
INVALID-RECORD-TYPE | None | | UserID and UserIDType identify a background user or template record, which is not a valid target for this service.
EMP-LOCK-FAILED | None | | The user record is currently locked by another user.
ITEMS-PROTECTED | None | | Cannot fulfill the request because an item is EMFI/DC protected and this is not the owning deployment.
INVALID-EXTERNAL-ID-TYPE | None | | Invalid value provided for External ID type.
NO-EXTERNAL-ID | None | | Attempted to set password for an external ID type that did not have an ID assigned.
DUP-EXTERNAL-ID-TYPE | None | | Attempted to set password for the same external ID type more than once.
INVALID-EXTERNAL-PASSWORD | None | | External password is longer than 254 characters or contains illegal characters.

Sample request

```
<SetUserExternalPasswords xmlns="urn:Epic-com:Security.2012.Services.PersonnelManagement">
  <UserID>MSEEGER</UserID>
  <UserIDType>SystemLogin</UserIDType>
  <AuditUserID> 1355452</AuditUserID>
  <AuditUserIDType>CID</AuditUserIDType>
  <AuditUserPassword>P3ars Plz</AuditUserPassword>
  <ExternalPasswords>
    <ExternalPassword>
      <IDType>7</IDType>
      <Password>kaW!R7cet</Password>
    </ExternalPassword>
  </ExternalPasswords>
</SetUserExternalPasswords>
```

Sample response

```
<SetUserExternalPasswordsResponse xmlns="urn:Epic-com:Security.2012.Services.PersonnelManagement">
  <SetUserExternalPasswordsResult xmlns:i="http://www.w3.org/2001/XMLSchema-instance">
    <Messages xmlns:b="http://schemas.microsoft.com/2003/10/Serialization/Arrays" i:nil="true"/>
  </SetUserExternalPasswordsResult>
</SetUserExternalPasswordsResponse>
```

32.3.15 SetUserPagerID

File: site/apis/32-Security/3-Non-FHIR/503-SetUserPagerID.html
Epic API ID | 503
FHIR version | Non-FHIR
Categories | Security
API type | Epic Public
API group | Personnel Management Group
USCDI | No

HTTP method | POST
URL template | api/epic/2017/Security/PersonnelManagement/SetUserPagerID/SetUserPagerID?PagerID={PagerID}
Supports OAuth 2.0 | True
Supported user types | Backend Systems and Non-OAuth 2.0
Performs scope validation | False
SOAP namespace | urn:Epic-com:Security.2017.Services.PersonnelManagement
WSDL | {baseURL}/wcf/Epic.Security.GeneratedServices/PersonnelManagement.svc?wsdl
Source | https://fhir.epic.com/Specifications?api=503

Request parameters

Name | Type | Optional | Array | Cardinality | Description
AuditUserID | IDType | True | | | A generic identifier.
AuditUserID.ID | String | False | | | The identifier for this resource.
AuditUserID.Type | String | False | | | The type of identifier.
PagerID | String | True
UserID | IDType | False | | | A generic identifier.
UserID.ID | String | False | | | The identifier for this resource.
UserID.Type | String | False | | | The type of identifier.

Response elements

Name | Type | Optional | Array | Cardinality | Description
NonFatalErrorMessages | String | False

Errors

Code | Severity | Description | Example
LICENSE-NOT-FOUND | None | | The organization is not licensed for this feature.
NO-USER-ID | None | | Missing required parameter UserID.
NO-USER-FOUND | None | | Unable to resolve UserID and UserIDType combination to a unique user record.
INVALID-AUDIT-USER-ID | None | | Unable to resolve UserID and UserIDType combination to a unique user record.
INVALID-RECORD-TYPE | None | | UserID and UserIDType identify a background user or template record, which is not a valid target for this service.
EMP-LOCK-FAILED | None | | The user record is currently locked by another user.
ITEMS-PROTECTED | None | | Cannot fulfill the request because an item being updated is EMFI/Data Courier protected and this is not the owning deployment.
INVALID-PAGER-ID | None | | Cannot use the provided pager ID. It might contain invalid characters or exceed the maximum length.

Sample request

```
<SetUserPagerID xmlns="urn:Epic-com:Security.2017.Services.PersonnelManagement"
    xmlns:xsi="http://www.w3.org/2001/XMLSchema-instance">
  <!--string occurs:0,1-->
  <PagerID xsi:nil="false">user@epic.com</PagerID>
  <!--idtype occurs:0,1-->
  <UserID xsi:nil="false">
    <!--string occurs:0,1-->
    <ID xmlns="urn:Epic-com:Security.2012.Services.PersonnelManagement" xsi:nil="false">20524</ID>
    <!--string occurs:0,1-->
    <Type xmlns="urn:Epic-com:Security.2012.Services.PersonnelManagement" xsi:nil="false">External</Type>
  </UserID>
  <!--idtype occurs:0,1-->
  <AuditUserID xsi:nil="false">
    <!--string occurs:0,1-->
    <ID xmlns="urn:Epic-com:Security.2012.Services.PersonnelManagement" xsi:nil="false">20524</ID>
    <!--string occurs:0,1-->
    <Type xmlns="urn:Epic-com:Security.2012.Services.PersonnelManagement" xsi:nil="false">External</Type>
  </AuditUserID>
</SetUserPagerID>
```

Sample response

```
<?xml version="1.0" encoding="utf-16"?>
<s:Envelope xmlns:s="http://schemas.xmlsoap.org/soap/envelope/">
<s:Body>
<SetUserPagerIDResponse xmlns="urn:Epic-com:Security.2017.Services.PersonnelManagement">
<SetUserPagerIDResult xmlns:i="http://www.w3.org/2001/XMLSchema-instance">
<NonFatalErrorMessages i:nil="true" xmlns:a="http://schemas.microsoft.com/2003/10/Serialization/Arrays" />
</SetUserPagerIDResult>
</SetUserPagerIDResponse>
</s:Body>
</s:Envelope>
```

32.3.16 SetUserPassword

File: site/apis/32-Security/3-Non-FHIR/211-SetUserPassword.html
Epic API ID | 211
FHIR version | Non-FHIR
Categories | Security

API type | Epic Public
API group | Personnel Management Group
USCDI | No
HTTP method | PUT
URL template | api/epic/2012/Security/PersonnelManagement/SetUserPassword/Personnel/User/EpicPassword?UserID={UserID}
Supports OAuth 2.0 | True
Supported user types | Backend Systems and Non-OAuth 2.0
Performs scope validation | False
SOAP namespace | urn:Epic-com:Security.2012.Services.PersonnelManagement
WSDL | Epic.Security.GeneratedServices/PersonnelManagement.svc?wsdl
Source | https://fhir.epic.com/Specifications?api=211

Request parameters

Name | Type | Optional | Array | Cardinality | Description
AuditUserID | String | True | | | Identifier for the user changing the password.
AuditUserIDType | String | True | | | Audit User Identifier type. You can specify Internal, External, CID, SystemLogin, Alias, or an Identity ID. Defaults to Internal if not provided.
AuditUserPassword | String | True | | | Epic password of the Audit User. Must be provided (and correct) if an audit user is specified.
NewPassword | String | False | | | The new password to set.
UserID | String | False | | | Identifier for the user whose password is being updated.
UserIDType | String | True | | | User Identifier type. You can specify Internal, External, CID, SystemLogin, Alias, or an Identity ID. Defaults to Internal if not provided.

Response elements

Name | Type | Optional | Array | Cardinality | Description
Messages | String | False | | | A list of human-readable warning messages.

Errors

Code | Severity | Description | Example
LICENSE-NOT-FOUND | None | | Organization is not licensed for this feature.
NO-USER-ID | None | | Missing required parameter UserID.
NO-USER-FOUND | None | | Unable to resolve UserID and UserIDType combination to a unique user record.
INVALID-RECORD-TYPE | None | | UserID and UserIDType identify a background user or template record, which is not a valid target for this service.
EMP-LOCK-FAILED | None | | The user record is currently locked by another user.
NO-NEW-PASSWORD | None | | Missing required parameter NewPassword.
PW-PROTECTED | None | | Item 40 is DC/EMFI protected or password changes are not allowed in this environment.
ITEMS-PROTECTED | None | | Cannot fulfill the request because an item is EMFI/DC protected and this is not the owning deployment.
NON-NATIVE-AUTH | None | | The user record selected uses an authentication method other than an Epic password.
INVALID-NEW-PASSWORD | None | | New password contains illegal characters or does not meet environment history or complexity requiremenTS.

Sample request

```
<SetUserPassword xmlns="urn:Epic-com:Security.2012.Services.PersonnelManagement">
  <NewPassword>IL0V3ep1c!</NewPassword>
  <UserID>MSEEGER</UserID>
  <UserIDType>SystemLogin</UserIDType>
  <AuditUserID>278931</AuditUserID>
  <AuditUserIDType>CID</AuditUserIDType>
  <AuditUserPassword>P3ars Plz</AuditUserPassword>
</SetUserPassword>
```

Sample response

```
<SetUserPasswordResponse xmlns="urn:Epic-com:Security.2012.Services.PersonnelManagement">
  <SetUserPasswordResult xmlns:i="http://www.w3.org/2001/XMLSchema-instance">
    <Messages xmlns:b="http://schemas.microsoft.com/2003/10/Serialization/Arrays" i:nil="true"/>
  </SetUserPasswordResult>
</SetUserPasswordResponse>
```

32.3.17 UpdateAuthorizedServiceAreas

File: site/apis/32-Security/3-Non-FHIR/456-UpdateAuthorizedServiceAreas.html
Epic API ID | 456
FHIR version | Non-FHIR
Categories | Security
API type | Epic Public
API group | Personnel Management Group
USCDI | No
URL template | api/epic/2017/Security/PersonnelManagement/UpdateAuthorizedServiceAreas/Personnel/User/AuthorizedServiceAreas/Update?Append={Append}
Supports OAuth 2.0 | True
Supported user types | Backend Systems and Non-OAuth 2.0
Performs scope validation | False

SOAP namespace | urn:Epic-com:Security.2017.Services.PersonnelManagement
WSDL | http://vs-icx.epic.com/Interconnect-CDE/wcf/Epic.Security.GeneratedServices/PersonnelManagement.svc?wsdl
Source | https://fhir.epic.com/Specifications?api=456

Request parameters

Name | Type | Optional | Array | Cardinality | Description
Append | Boolean | True
AuditUserID | IDType | True | | | A generic identifier.
AuditUserID.ID | String | False | | | The identifier for this resource.
AuditUserID.Type | String | True | | | The type of identifier.
AuthorizedServiceAreas | IndexedRecordIn | True | Yes
AuthorizedServiceAreas.Identifier | IDType | False | | | A generic identifier.
AuthorizedServiceAreas.Identifier.ID | String | False | | | The identifier for this resource.
AuthorizedServiceAreas.Identifier.Type | String | True | | | The type of identifier.
AuthorizedServiceAreas.Index | String | False | | | Number indicating the ordering of the record. Should be a sequence of consecutive numbers starting from 1.
UserID | IDType | False | | | A generic identifier.
UserID.ID | String | False | | | The identifier for this resource.
UserID.Type | String | True | | | The type of identifier.

Response elements

Name | Type | Optional | Array | Cardinality | Description
Messages | String | True

Errors

Code | Severity | Description | Example
ITEMS-PROTECTED | None | | This item can't be edited on this deployment.
TEMPLATE-ITEM | None | | This item is defined by the template and cannot be set directly.
EMP-LOCK-FAILED | None | | Unable to obtain lock on specified user record.
INVALID-RECORD-TYPE | None | | A user record was identified, but the record is a background user, template, or subtemplate record, which is not a valid target for this service.
NO-USER-FOUND | None | | A user ID was received, but a corresponding record could not be found, or the identifier did not produce a unique user record.
LICENSE-NOT-FOUND | None | | The organization is not licensed for this feature.
NO-USER-ID | None | | The web service request did not specify the required UserID field.
INVALID-AUDIT-USER | None | | The audit user passed in could not be found.
INVALID-AUTH-SERVICE-AREA | None | | A value provided for the authorized service area is of an invalid type.
INVALID-AUTH-SERVICE-AREA-ID | None | | A value provided for the authorized service area did not match a valid record.
DUPLICATE-AUTH-SERVICE-AREA | None | | A value provided for the authorized service area appeared more than once in authorized services areas.
NON-INTEGER-INDEX | None | | Indices must be a positive integer value.

Sample request

```
<UpdateAuthorizedServiceAreas xmlns="urn:Epic-com:Security.2017.Services.PersonnelManagement"
    xmlns:xsi="http://www.w3.org/2001/XMLSchema-instance">
  <!--boolean occurs:0,1-->
  <Append>1</Append>
  <!--idtype occurs:0,1-->
  <UserID xsi:nil="false">
    <!--string occurs:0,1-->
    <ID xmlns="urn:Epic-com:Security.2012.Services.PersonnelManagement" xsi:nil="false">24714</ID>
    <!--string occurs:0,1-->
    <Type xmlns="urn:Epic-com:Security.2012.Services.PersonnelManagement" xsi:nil="false">external</Type>
  </UserID>
  <!--idtype occurs:0,1-->
  <AuditUserID xsi:nil="false">
    <!--string occurs:0,1-->
    <ID xmlns="urn:Epic-com:Security.2012.Services.PersonnelManagement" xsi:nil="false">24714</ID>
    <!--string occurs:0,1-->
    <Type xmlns="urn:Epic-com:Security.2012.Services.PersonnelManagement" xsi:nil="false">external</Type>
  </AuditUserID>
  <!--arrayofindexedrecordin occurs:0,1-->
  <AuthorizedServiceAreas xsi:nil="false">
    <!--indexedrecordin occurs:0,-->
    <IndexedRecordIn xmlns="urn:Epic-com:Security.2012.Services.PersonnelManagement" xsi:nil="false">
      <!--idtype occurs:0,1-->
      <Identifier xsi:nil="false">
        <!--string occurs:0,1-->
        <ID xsi:nil="false">1</ID>
        <!--string occurs:0,1-->
        <Type xsi:nil="false">external</Type>
      </Identifier>
      <!--string occurs:0,1-->
      <Index xsi:nil="false">1</Index>
    </IndexedRecordIn>
  </AuthorizedServiceAreas>
```

```
</UpdateAuthorizedServiceAreas>
```

Sample response

```
<?xml version="1.0" encoding="utf-16"?>
<s:Envelope xmlns:s="http://schemas.xmlsoap.org/soap/envelope/">
<s:Header>
<ServerMetrics xmlns="Epic.Core.Communication">[{"BlockReads":16,"BlockWrites":9,"BlocksAllocated":0,"DBTime":28,"ECFNet
    workTime":1,"ECFRequestCount":0,"ECFRequestTime":29,"GREF":971,"JournalEntries":20,"LocksFailed":0,"LocksGranted":6,
    "MCommands":4616,"MemoryDifference":51200,"WorkflowEventBlockReads":16,"WorkflowEventDBTime":28,"WorkflowEventECFNet
    workTime":0,"WorkflowEventECFRequestCount":0,"WorkflowEventGREF":971}]</ServerMetrics>
</s:Header>
<s:Body>
<UpdateAuthorizedServiceAreasResponse xmlns="urn:Epic-com:Security.2017.Services.PersonnelManagement">
<UpdateAuthorizedServiceAreasResult xmlns:i="http://www.w3.org/2001/XMLSchema-instance">
<Messages
i:nil="true" xmlns:a="http://schemas.microsoft.com/2003/10/Serialization/Arrays" />
</UpdateAuthorizedServiceAreasResult>
</UpdateAuthorizedServiceAreasResponse>
</s:Body>
</s:Envelope>
```

32.3.18 UpdateBIDefaultUser

File: site/apis/32-Security/3-Non-FHIR/505-UpdateBIDefaultUser.html
Epic API ID | 505
FHIR version | Non-FHIR
Categories | Security
API type | Epic Public
API group | Personnel Management Group
USCDI | No
HTTP method | POST
URL template | api/epic/2017/Security/PersonnelManagement/UpdateBIDefaultUser/User/UpdateBIDefaultUser
Supports OAuth 2.0 | True
Supported user types | Backend Systems and Non-OAuth 2.0
Performs scope validation | False
SOAP namespace | urn:Epic-com:Security.2017.Services.PersonnelManagement
WSDL | Epic.Security.GeneratedServices/PersonnelManagement.svc?wsdl
Source | https://fhir.epic.com/Specifications?api=505

Request parameters

Name | Type | Optional | Array | Cardinality | Description
AuditUserID | IDType | True | | | A generic identifier.
AuditUserID.ID | String | False | | | The identifier for this resource.
AuditUserID.Type | String | True | | | The type of identifier.
BIDefaultUser | String | False
UserID | IDType | False | | | A generic identifier.
UserID.ID | String | False | | | The identifier for this resource.
UserID.Type | String | True | | | The type of identifier.

Response elements

Name | Type | Optional | Array | Cardinality | Description
Messages | String | False

Errors

Code | Severity | Description | Example
LICENSE-NOT-FOUND | None | | The organization is not licensed for this feature.
NO-USER-ID | None | | Missing required parameter UserID.
NO-USER-FOUND | None | | Unable to resolve UserID and UserIDType combination to a unique user record.
INVALID-RECORD-TYPE | None | | UserID and UserIDType identify a background user or template record, which is not a valid target for this service.
INVALID-AUDIT-USER-ID | None | | AuditUserID identifies a user record that is not active.
EMP-LOCK-FAILED | None | | The user record is currently locked by another user.
ITEMS-PROTECTED | None | | Cannot fulfill the request because an item being updated is EMFI/DC protected and this is not the owning deployment.
DUPLICATE-BI-USER-NAME | None | | The BI user name is already assigned to another user.
INVALID-BI-USER-NAME | None | | The BI user name exceeds the 100 character limit or contains the "[" character.

Sample request

```
<UpdateBIDefaultUser xmlns="urn:Epic-com:Security.2017.Services.PersonnelManagement"
    xmlns:xsi="http://www.w3.org/2001/XMLSchema-instance">
  <!--string occurs:0,1-->
  <BIDefaultUser xsi:nil="false">Administrator</BIDefaultUser>
  <!--idtype occurs:0,1-->
  <UserID xsi:nil="false">
```

```
    <!--string occurs:0,1-->
    <ID xmlns="urn:Epic-com:Security.2012.Services.PersonnelManagement" xsi:nil="false">BIADMIN</ID>
    <!--string occurs:0,1-->
    <Type xmlns="urn:Epic-com:Security.2012.Services.PersonnelManagement" xsi:nil="false">External</Type>
  </UserID>
  <!--idtype occurs:0,1-->
  <AuditUserID xsi:nil="false">
    <!--string occurs:0,1-->
    <ID xmlns="urn:Epic-com:Security.2012.Services.PersonnelManagement" xsi:nil="false">1</ID>
    <!--string occurs:0,1-->
    <Type xmlns="urn:Epic-com:Security.2012.Services.PersonnelManagement" xsi:nil="false">External</Type>
  </AuditUserID>
</UpdateBIDefaultUser>
```

Sample response

```
<?xml version="1.0" encoding="utf-16"?>
<s:Envelope xmlns:s="http://schemas.xmlsoap.org/soap/envelope/">
<s:Body>
<UpdateBIDefaultUserResponse xmlns="urn:Epic-com:Security.2017.Services.PersonnelManagement">
<UpdateBIDefaultUserResult xmlns:i="http://www.w3.org/2001/XMLSchema-instance">
<Messages i:nil="true" xmlns:a="http://schemas.microsoft.com/2003/10/Serialization/Arrays" />
</UpdateBIDefaultUserResult>
</UpdateBIDefaultUserResponse>
</s:Body>
</s:Envelope>
```

32.3.19 UpdateCommunityUser

File: site/apis/32-Security/3-Non-FHIR/391-UpdateCommunityUser.html
Epic API ID | 391
FHIR version | Non-FHIR
Categories | Security
API type | Epic Public
API group | Personnel Management Group
USCDI | No
HTTP method | POST
URL template | api/epic/2016/Security/PersonnelManagement/UpdateCommunityUser/User/UpdateCommunityUser?WebExternalIdentifier={WebExternalIdentifier}&ReceiveExternalEmail={ReceiveExternalEmail}&ReceiveGroupNotifications={ReceiveGroupNotifications}&Deactivated={Deactivated}
Supports OAuth 2.0 | True
Supported user types | Backend Systems and Non-OAuth 2.0
Performs scope validation | False
SOAP namespace | urn:Epic-com:Security.2016.Services.PersonnelManagement
WSDL | Epic.Security.GeneratedServices/PersonnelManagement.svc?wsdl
Source | https://fhir.epic.com/Specifications?api=391

Request parameters

Name | Type | Optional | Array | Cardinality | Description
AuditUserID | IDType | True | | | A generic identifier.
AuditUserID.ID | String | False | | | The identifier for this resource.
AuditUserID.Type | String | True | | | The type of identifier.
Deactivated | Boolean | True
ReceiveExternalEmail | Boolean | True
ReceiveGroupNotifications | Boolean | True
SiteManagerContexts | MultiStringIn | True
SiteManagerContexts.Append | Boolean | False
SiteManagerContexts.Values | String | True
UserContexts | MultiStringIn | True
UserContexts.Append | Boolean | False
UserContexts.Values | String | True
UserID | IDType | False | | | A generic identifier.
UserID.ID | String | False | | | The identifier for this resource.
UserID.Type | String | True | | | The type of identifier.
WebExternalIdentifier | String | True

Response elements

Name | Type | Optional | Array | Cardinality | Description
Messages | String | True

Errors

Code | Severity | Description | Example
LICENSE-NOT-FOUND | None | | Organization is not licensed for this feature.
NO-USER-ID | None | | Web service request did not specify the required UserID field.
INVALID-AUDIT-USER | None | | The audit user passed in could not be found.

EMP-LOCK-FAILED | None | | Unable to obtain lock on specified user record.
NO-USER-FOUND | None | | A user ID was received, but a corresponding record could not be found, or the identifier did not produce a unique user record.
INVALID-RECORD-TYPE | None | | A user record was identified, but the record is a background user or (sub)template record, which is not a valid target for this service.
INVALID-USER-CONTEXT | None | | Invalid value provided for user context.
INVALID-SITE-MANAGER-CONTEXT | None | | Invalid value provided for site manager context.
INVALID-WEB-EXTERNAL-ID | None | | Invalid value provided for web external identifier.

Sample request

```
<UpdateCommunityUser xmlns="urn:Epic-com:Security.2016.Services.PersonnelManagement"
    xmlns:xsi="http://www.w3.org/2001/XMLSchema-instance">
  <!--string occurs:0,1-->
  <WebExternalIdentifier xsi:nil="false">bcarlyon</WebExternalIdentifier>
  <!--boolean occurs:0,1-->
  <ReceiveExternalEmail>false</ReceiveExternalEmail>
  <!--boolean occurs:0,1-->
  <ReceiveGroupNotifications>false</ReceiveGroupNotifications>
  <!--boolean occurs:0,1-->
  <Deactivated>false</Deactivated>
  <!--idtype occurs:0,1-->
  <UserID xsi:nil="false">
    <!--string occurs:0,1-->
    <ID xmlns="urn:Epic-com:Security.2012.Services.PersonnelManagement" xsi:nil="false">6495</ID>
    <!--string occurs:0,1-->
    <Type xmlns="urn:Epic-com:Security.2012.Services.PersonnelManagement" xsi:nil="false">EXTERNAL</Type>
  </UserID>
  <!--idtype occurs:0,1-->
  <AuditUserID xsi:nil="false">
    <!--string occurs:0,1-->
    <ID xmlns="urn:Epic-com:Security.2012.Services.PersonnelManagement" xsi:nil="false">6495</ID>
    <!--string occurs:0,1-->
    <Type xmlns="urn:Epic-com:Security.2012.Services.PersonnelManagement" xsi:nil="false">EXTERNAL</Type>
  </AuditUserID>
  <!--multistringin occurs:0,1-->
  <UserContexts xsi:nil="false">
    <!--boolean occurs:0,1-->
    <Append>false</Append>
    <!--arrayofstring occurs:0,1-->
    <Values xsi:nil="false">
      <!--string occurs:0,-->
      <string xmlns="http://schemas.microsoft.com/2003/10/Serialization/Arrays" xsi:nil="false">6495</string>
    </Values>
  </UserContexts>
  <!--multistringin occurs:0,1-->
  <SiteManagerContexts xsi:nil="false">
    <!--boolean occurs:0,1-->
    <Append>false</Append>
    <!--arrayofstring occurs:0,1-->
    <Values xsi:nil="false">
      <!--string occurs:0,-->
      <string xmlns="http://schemas.microsoft.com/2003/10/Serialization/Arrays" xsi:nil="false">6495</string>
    </Values>
  </SiteManagerContexts>
</UpdateCommunityUser>
```

Sample response

```
<?xml version="1.0" encoding="utf-16"?>
<s:Envelope xmlns:s="http://www.w3.org/2003/05/soap-envelope" xmlns:a="http://www.w3.org/2005/08/addressing">
<s:Header>
<a:Action s:mustUnderstand="1">urn:Epic-
    com:Security.2016.Services.PersonnelManagement.UpdateCommunityUserResponse</a:Action>
<a:RelatesTo>urn:uuid:bd444432-b0e7-4c3f-bcc3-8fd0a516cd2d</a:RelatesTo>
</s:Header>
<s:Body>
<UpdateCommunityUserResponse xmlns="urn:Epic-com:Security.2016.Services.PersonnelManagement">
<UpdateCommunityUserResult xmlns:i="http://www.w3.org/2001/XMLSchema-instance">
<Messages xmlns:b="http://schemas.microsoft.com/2003/10/Serialization/Arrays" />
</UpdateCommunityUserResult>
</UpdateCommunityUserResponse>
</s:Body>
</s:Envelope>
```

32.3.20 UpdateFacilityDepartmentList

File: site/apis/32-Security/3-Non-FHIR/457-UpdateFacilityDepartmentList.html
Epic API ID | 457
FHIR version | Non-FHIR
Categories | Security
API type | Epic Public
API group | Personnel Management Group
USCDI | No

URL template | api/epic/2017/Security/PersonnelManagement/UpdateFacilityDepartmentList/Personnel/User/FacilityDepartmentList/Update?Append={Append}
Supports OAuth 2.0 | True
Supported user types | Backend Systems and Non-OAuth 2.0
Performs scope validation | False
SOAP namespace | urn:Epic-com:Security.2017.Services.PersonnelManagement
WSDL | http://vs-icx.epic.com/Interconnect-CDE/wcf/Epic.Security.GeneratedServices/PersonnelManagement.svc?wsdl
Source | https://fhir.epic.com/Specifications?api=457

Request parameters

Name | Type | Optional | Array | Cardinality | Description
Append | Boolean | True
AuditUserID | IDType | False | | | A generic identifier.
AuditUserID.ID | String | False | | | The identifier for this resource.
AuditUserID.Type | String | False | | | The type of identifier.
FacilityDepartmentList | IndexedRecordIn | True | Yes
FacilityDepartmentList.Identifier | IDType | True | | | A generic identifier.
FacilityDepartmentList.Index | String | False | | | Number indicating the ordering of the record. Should be a sequence of consecutive numbers starting from 1.
UserID | IDType | False | | | A generic identifier.
UserID.ID | String | False | | | The identifier for this resource.
UserID.Type | String | False | | | The type of identifier.

Errors

Code | Severity | Description | Example
ITEMS-PROTECTED | None | | This item can't be edited on this deployment.
TEMPLATE-ITEM | None | | This item is defined by the template and cannot be set directly.
FOUND-PROVIDER-RECORD | None | | The user has a linked provider record that should be used to define these items.
NO-FACILITY-DEFINED | None | | The user does not have a facility record defined. The facility department item would not be used.
EMP-LOCK-FAILED | None | | Unable to obtain lock on the specified user record.
INVALID-RECORD-TYPE | None | | A user record was identified, but the record is a background user, template or subtemplate record, which is not a valid target for this service.
NO-USER-FOUND | None | | A user ID was received, but a corresponding record could not be found, or the identifier did not produce a unique user record.
LICENSE-NOT-FOUND | None | | The organization is not licensed for this feature.
NO-USER-ID | None | | The web service request did not specify the required UserID field.
INVALID-AUDIT-USER | None | | The audit user passed in could not be found.
INVALID-FAC-DEPT-ID | None | | A value provided for the facility department list did not match a valid record.
DUPLICATE-FAC-DEPT | None | | A value provided for the facility department list appeared more than once in facility department list.
NON-INTEGER-INDEX | None | | Indices must be a positive integer value.

Sample request

```
<UpdateFacilityDepartmentList xmlns="urn:Epic-com:Security.2017.Services.PersonnelManagement"
    xmlns:xsi="http://www.w3.org/2001/XMLSchema-instance">
  <!--boolean occurs:0,1-->
  <Append>0</Append>
  <!--idtype occurs:0,1-->
  <UserID xsi:nil="false">
    <!--string occurs:0,1-->
    <ID xmlns="urn:Epic-com:Security.2012.Services.PersonnelManagement" xsi:nil="false">24714</ID>
    <!--string occurs:0,1-->
    <Type xmlns="urn:Epic-com:Security.2012.Services.PersonnelManagement" xsi:nil="false">external</Type>
  </UserID>
  <!--idtype occurs:0,1-->
  <AuditUserID xsi:nil="false">
    <!--string occurs:0,1-->
    <ID xmlns="urn:Epic-com:Security.2012.Services.PersonnelManagement" xsi:nil="false">24714</ID>
    <!--string occurs:0,1-->
    <Type xmlns="urn:Epic-com:Security.2012.Services.PersonnelManagement" xsi:nil="false">external</Type>
  </AuditUserID>
  <!--arrayofindexedrecordin occurs:0,1-->
  <FacilityDepartmentList xsi:nil="false">
    <!--indexedrecordin occurs:0,-->
    <IndexedRecordIn xmlns="urn:Epic-com:Security.2012.Services.PersonnelManagement" xsi:nil="false">
      <!--idtype occurs:0,1-->
      <Identifier xsi:nil="false">
        <!--string occurs:0,1-->
        <ID xsi:nil="false">2</ID>
        <!--string occurs:0,1-->
        <Type xsi:nil="false">external</Type>
      </Identifier>
      <!--string occurs:0,1-->
      <Index xsi:nil="false">1</Index>
    </IndexedRecordIn>
  </FacilityDepartmentList>
</UpdateFacilityDepartmentList>
```

Sample response

```
<?xml version="1.0" encoding="utf-16"?>
<s:Envelope xmlns:s="http://schemas.xmlsoap.org/soap/envelope/">
<s:Header>
<ServerMetrics xmlns="Epic.Core.Communication">[{"BlockReads":9,"BlockWrites":1,"BlocksAllocated":0,"DBTime":12,"ECFNetw
    orkTime":1,"ECFRequestCount":0,"ECFRequestTime":13,"GREF":848,"JournalEntries":6,"LocksFailed":0,"LocksGranted":4,"M
    Commands":3758,"MemoryDifference":12288,"WorkflowEventBlockReads":9,"WorkflowEventDBTime":12,"WorkflowEventECFNetwor
    kTime":0,"WorkflowEventECFRequestCount":0,"WorkflowEventGREF":848}]</ServerMetrics>
</s:Header>
<s:Body>
<UpdateFacilityDepartmentListResponse xmlns="urn:Epic-com:Security.2017.Services.PersonnelManagement">
<UpdateFacilityDepartmentListResult xmlns:i="http://www.w3.org/2001/XMLSchema-instance">
<Messages
i:nil="true" xmlns:a="http://schemas.microsoft.com/2003/10/Serialization/Arrays" />
</UpdateFacilityDepartmentListResult>
</UpdateFacilityDepartmentListResponse>
</s:Body>
</s:Envelope>
```

32.3.21 UpdateLoginDepartments

File: site/apis/32-Security/3-Non-FHIR/458-UpdateLoginDepartments.html
Epic API ID | 458
FHIR version | Non-FHIR
Categories | Security
API type | Epic Public
API group | Personnel Management Group
USCDI | No
URL template | api/epic/2016/Security/PersonnelManagement/UpdateLoginDepartments/Personnel/User/LoginDepartments/Update
Supports OAuth 2.0 | True
Supported user types | Backend Systems and Non-OAuth 2.0
Performs scope validation | False
SOAP namespace | urn:Epic-com:Security.2016.Services.PersonnelManagement
WSDL | http://vs-icx.epic.com/Interconnect-CDE/wcf/Epic.Security.GeneratedServices/PersonnelManagement.svc?wsdl
Source | https://fhir.epic.com/Specifications?api=458

Request parameters

Name | Type | Optional | Array | Cardinality | Description
AuditUserID | IDType | True | | | A generic identifier.
DefaultLoginDepartmentID | IDType | False | | | A generic identifier.
DepartmentFilterSetting | String | True
Items | Item | True | Yes | | Array of items to update in this request. A tag that appears as the Name of an item here will be updated, even if it is empty.
Items.Mode | String | True | | | Default is "Replace." Can be set to "Append" for UserRoleIDs, CustomUserDictionaries, InBasketClassifications, LinkedSubtemplateIDs, UserSubtemplateIDs and CategoryReportGroupers.
Items.Name | String | False | | | Name of the item to update. EMP items will not be updated unless the parameter name (SystemLoginID, StartDate, etc) is given as a Name in the items list.
LoginDepartmentFilterList | IndexedRecordIn | True | Yes
LoginDepartmentFilterList.Identifier | IDType | True | | | A generic identifier.
LoginDepartmentFilterList.Index | String | False | | | Number indicating the ordering of the record. Should be a sequence of consecutive numbers starting from 1.
PreferredLoginDepartments | IndexedRecordIn | True | Yes
PreferredLoginDepartments.Identifier | IDType | True | | | A generic identifier.
PreferredLoginDepartments.Index | String | False | | | Number indicating the ordering of the record. Should be a sequence of consecutive numbers starting from 1.
UserID | IDType | False | | | A generic identifier.

Response elements

Name | Type | Optional | Array | Cardinality | Description
Messages | String | True

Errors

Code | Severity | Description | Example
LICENSE-NOT-FOUND | None | | The organization is not licensed for this feature
NO-USER-ID | None | | The web service request did not specify the required UserID field.
INVALID-AUDIT-USER-ID | None | | The audit user passed in could not be found.
EMP-LOCK-FAILED | None | | Unable to obtain a lock on the specified user record.
NO-USER-FOUND | None | | A user ID was received, but a corresponding record could not be found, or the identifier did not produce a unique user record.
INVALID-RECORD-TYPE | None | | A user record was identified, but the record is a background user or (sub)template record, which is not a valid target for this service.
TEMPLATE-ITEM | None | | Attempted to set an item that is defined by a template.
SUBTEMPLATE-ITEM | None | | Attempted to set an item that is defined by a subtemplate.

ITEMS-PROTECTED | None | | Cannot fulfill the request because an item being updated is EMFI/DC protected and this is not the owning deployment.
NO-INDEX | None | | Missing an index value for an ordered multiple response item.
INVALID-DEFAULT-LOGIN-DEPT | None | | Invalid value provided for default login department.
INVALID-DEPT-FILTER-SETTING | None | | Invalid value provided for department filter setting.
NO-ITEMS-SELECTED | None | | Missing required parameter Items or it contains only invalid entries.
INVALID-ITEM-MODE | None | | Invalid value provided for the mode of an item. It should be Append, Replace, or empty.
BAD-ITEM-LIST | None | | The same item is listed more than once with different modes.
INVALID-PREF-LOGIN-DEPT-ID | None | | A value provided for the preferred login departments did not match a valid record.
DUPLICATE-PREF-LOGIN-DEPT | None | | A value provided for the preferred login departments appeared more than once in preferred login departments.
INVALID-LOGIN-DEPT-FILTER-ID | None | | A value provided for the preferred login department filter did not match a valid record.
DUPLICATE-LOGIN-DEPT-FILTER | None | | A value provided for the preferred login department filter appeared more than once in login department filter list.
NON-INTEGER-INDEX | None | | Indices must be a positive integer value.

Sample request

```
<UpdateLoginDepartments xmlns="urn:Epic-com:Security.2016.Services.PersonnelManagement"
    xmlns:xsi="http://www.w3.org/2001/XMLSchema-instance">
  <DepartmentFilterSetting xsi:nil="false">Exclusive</DepartmentFilterSetting>
  <UserID xsi:nil="false">
    <ID xmlns="urn:Epic-com:Security.2012.Services.PersonnelManagement" xsi:nil="false">2093</ID>
    <Type xmlns="urn:Epic-com:Security.2012.Services.PersonnelManagement" xsi:nil="false">external</Type>
  </UserID>
  <AuditUserID xsi:nil="false">
    <ID xmlns="urn:Epic-com:Security.2012.Services.PersonnelManagement" xsi:nil="false"/>
    <Type xmlns="urn:Epic-com:Security.2012.Services.PersonnelManagement" xsi:nil="false"/>
  </AuditUserID>
  <DefaultLoginDepartmentID xsi:nil="false">
    <ID xmlns="urn:Epic-com:Security.2012.Services.PersonnelManagement" xsi:nil="false">3499</ID>
    <Type xmlns="urn:Epic-com:Security.2012.Services.PersonnelManagement" xsi:nil="false">Internal</Type>
  </DefaultLoginDepartmentID>
  <PreferredLoginDepartments xsi:nil="false">
    <IndexedRecordIn xmlns="urn:Epic-com:Security.2012.Services.PersonnelManagement" xsi:nil="false">
      <Identifier xsi:nil="false">
        <ID xsi:nil="false">3499</ID>
        <Type xsi:nil="false">Internal</Type>
      </Identifier>
      <Index xsi:nil="false">1</Index>
    </IndexedRecordIn>
    <IndexedRecordIn xmlns="urn:Epic-com:Security.2012.Services.PersonnelManagement" xsi:nil="false">
      <Identifier xsi:nil="false">
        <ID xsi:nil="false">552016</ID>
        <Type xsi:nil="false">External</Type>
      </Identifier>
      <Index xsi:nil="false">2</Index>
    </IndexedRecordIn>
  </PreferredLoginDepartments>
  <LoginDepartmentFilterList xsi:nil="false">
    <IndexedRecordIn xmlns="urn:Epic-com:Security.2012.Services.PersonnelManagement" xsi:nil="false">
      <Identifier xsi:nil="false">
        <ID xsi:nil="false">3499</ID>
        <Type xsi:nil="false">External</Type>
      </Identifier>
      <Index xsi:nil="false">1</Index>
    </IndexedRecordIn>
    <IndexedRecordIn xmlns="urn:Epic-com:Security.2012.Services.PersonnelManagement" xsi:nil="false">
      <Identifier xsi:nil="false">
        <ID xsi:nil="false">208701</ID>
        <Type xsi:nil="false">External</Type>
      </Identifier>
      <Index xsi:nil="false">2</Index>
    </IndexedRecordIn>
  </LoginDepartmentFilterList>
  <Items xsi:nil="false">
    <Item xmlns="urn:Epic-com:Security.2012.Services.PersonnelManagement" xsi:nil="false">
      <Mode xsi:nil="false">Replace</Mode>
      <Name xsi:nil="false">PreferredLoginDepartments</Name>
    </Item>
    <Item xmlns="urn:Epic-com:Security.2012.Services.PersonnelManagement" xsi:nil="false">
      <Mode xsi:nil="false">Replace</Mode>
      <Name xsi:nil="false">LoginDepartmentFilterList</Name>
    </Item>
    <Item xmlns="urn:Epic-com:Security.2012.Services.PersonnelManagement" xsi:nil="false">
      <Mode xsi:nil="false">Replace</Mode>
      <Name xsi:nil="false">DepartmentFilterSetting</Name>
    </Item>
    <Item xmlns="urn:Epic-com:Security.2012.Services.PersonnelManagement" xsi:nil="false">
      <Mode xsi:nil="false">Replace</Mode>
      <Name xsi:nil="false">DefaultLoginDepartmentID</Name>
    </Item>
  </Items>
</UpdateLoginDepartments>
```

Sample response

```
<?xml version="1.0" encoding="utf-16"?>
<s:Envelope xmlns:s="http://schemas.xmlsoap.org/soap/envelope/">
<s:Body>
<UpdateLoginDepartmentsResponse xmlns="urn:Epic-com:Security.2016.Services.PersonnelManagement">
<UpdateLoginDepartmentsResult xmlns:i="http://www.w3.org/2001/XMLSchema-instance">
<Messages xmlns:a="http://schemas.microsoft.com/2003/10/Serialization/Arrays">
<a:string />
</Messages>
</UpdateLoginDepartmentsResult>
</UpdateLoginDepartmentsResponse>
</s:Body>
</s:Envelope>
```

32.3.22 UpdateUser (2014)

File: site/apis/32-Security/3-Non-FHIR/393-UpdateUser-2014.html
Epic API ID | 393
FHIR version | Non-FHIR
Categories | Security
API type | Epic Public
API group | Personnel Management Group
USCDI | No
HTTP method | POST
URL template | api/epic/2014/Security/PersonnelManagement/UpdateUser/Personnel/User
Supports OAuth 2.0 | True
Supported user types | Backend Systems and Non-OAuth 2.0
Performs scope validation | False
SOAP namespace | urn:Epic-com:Security.2014.Services.PersonnelManagement
WSDL | Epic.Security.GeneratedServices/PersonnelManagement.svc?wsdl
Source | https://fhir.epic.com/Specifications?api=393

Remarks

If any error is encountered, the record is not modified. If input is unambigious and valid, but poorly formatted, it may be corrected automatically. If so, the response contains descriptions of what was changed in the messages element.

To modify an item, that item must be listed in the Items array. For most items, the old value will be cleared and replaced with the new value, but for some multiple response items, you can choose to append new values to the end of the list.

To clear an item, do not include the element corresponding to the item in the request, but instead list the item by name in the Items array.

To leave an item unchanged, do not include the item in the Items array.

Request parameters

Name | Type | Optional | Array | Cardinality | Description
AuditUserID | String | True | | | ID of user creating the record.
AuditUserIDType | String | False | | | Type of ID for user creating the record. You can specify Internal, External, CID, SystemLogin, or an Identity ID type.
AuditUserPassword | String | True | | | This parameter is no longer used. The Epic password of the Audit User.
AuthenticationConfigurationID | IDType | False | | | A generic identifier.
BlockStatus | BlockStatus | True | | | A user's block status.
BlockStatus.Comment | String | True | | | Free text comment about why the user is blocked.
BlockStatus.IsBlocked | Boolean | False | | | Should the user be blocked?
BlockStatus.Reason | String | False | | | Category value for block reason if we are blocking the user.
CategoryReportGrouper1 | String | True | | | A list of values for the user's first category report grouper item, which does not have an Epic-defined meaning.
CategoryReportGrouper2 | String | True | | | A list of values for the user's second category report grouper item, which does not have an Epic-defined meaning.
CategoryReportGrouper3 | String | True | | | A list of values for the user's third category report grouper item, which does not have an Epic-defined meaning.
CategoryReportGrouper4 | String | True | | | A list of values for the user's fourth category report grouper item, which does not have an Epic-defined meaning.
CategoryReportGrouper5 | String | True | | | A list of values for the user's fifth category report grouper item, which does not have an Epic-defined meaning.
CategoryReportGrouper6 | String | True | | | A list of values for the user's sixth category report grouper item, which does not have an Epic-defined meaning.
ContactComment | String | True | | | Contact comment that appears for the initial contact.
ContactDate | String | True | | | Date to use for the newly created contact. Defaults to current date if not set.
CustomUserDictionaries | IndexedString | True | Yes | | List of new values for custom user dictionary files. Starting in Epic May 2020, this element is no longer supported.
DefaultLoginDepartmentID | IDType | True | | | A generic identifier.
EmployeeDemographics | EmployeeDemographics | True | Yes | | Customizable items used for demographic information about a user specific to a contact.
EmployeeDemographics.EmployeeDemographic1 | String | True | | | Value of the first employee demographic item. Typically job code.

EmployeeDemographics.EmployeeDemographic2 | String | True | | | Value of the second employee demographic item. Typically payroll department.
EmployeeDemographics.EmployeeDemographic3 | String | True | | | Value of the third employee demographic item. Typically location.
EmployeeDemographics.Index | String | False | | | Number indicating the ordering of the values. Should be a sequence of consecutive numbers starting from 1.
EndDate | String | True | | | The date at which the user becomes inactive.
ExternalIdentifiers | ExternalIdentifier | True | Yes | | List of external ID items set for this user.
ExternalIdentifiers.Identifier | String | True | | | External identifier for the user.
ExternalIdentifiers.IdentifierType | String | False | | | External identifier type.
ExternalIdentifiers.IsActive | Boolean | True | | | True if the identifier is active.
ForceContactCreation | Boolean | False | | | Pass in a true value to force a new contact to be created for this change.
IdentityIDs | IDType | True | Yes | | A generic identifier.
IdentityIDs.ID | String | False | | | The identifier for this resource.
IdentityIDs.Type | String | False | | | You can specify Internal, External, CID, or an MPI ID. The default value is Internal.
InBasketClassifications | String | True | | | List of new values for user In Basket classifications.
IsActive | Boolean | True | | | Whether the user record should be set to active or inactive. The default value is False.
Items | Item | False | Yes | | Array of items to update in this request. A tag that appears as the Name of an item here will be updated, even if it is empty.
Items.Mode | String | True | | | Default is "Replace." Can be set to "Append" for UserRoleIDs, CustomUserDictionaries, InBasketClassifications, LinkedSubtemplateIDs, UserSubtemplateIDs and CategoryReportGroupers.
Items.Name | String | False | | | Name of the item to update. EMP items will not be updated unless the parameter name (SystemLoginID, StartDate, etc) is given as a Name in the items list.
LDAPOverrideID | String | True | | | A string that can be provided to identify the user to the LDAP server in place of the SystemLogin. Does not need to be unique. Maximum length 254 characters.
LinkedProviderID | IDType | True | | | A generic identifier.
LinkedTemplatesConfig | LinkedTemplatesConfig | True | | | The linked template setup for the user.
LinkedTemplatesConfig.AppliedTemplateID | IDType | False | | | The template to apply to the user. If the user is currently logged in, the template is not applied and an INVALID-LINKED-TEMPLATES-CONFIG fault is returned.
LinkedTemplatesConfig.AvailableLinkableTemplates | AvailableTemplateSetup | False | Yes | | The list of template the user should be allowed to select from. Should include both the default linkable template and applied linkable template.
LinkedTemplatesConfig.AvailableLinkableTemplates.EndDate | String | True | | | The date after which the user should no longer have access to this template.
LinkedTemplatesConfig.AvailableLinkableTemplates.LinkedTemplateID | IDType | False | | | A generic identifier.
LinkedTemplatesConfig.AvailableLinkableTemplates.LoginTypes | String | True | | | The applications for which this template should be applied automatically.
LinkedTemplatesConfig.AvailableLinkableTemplates.StartDate | String | True | | | The date the user should begin to have access to this template.
LinkedTemplatesConfig.DefaultTemplateID | IDType | False | | | The default linkable template for this user. Certain authentication items and lower-version environments always pull from this template.
Name | String | True | | | User's name in LAST, FIRST MI format. If a UserComplexName is provided, this is ignored. If one is not, this is required.
Notes | String | True | | | Up to 2000 characters of fee text notes about the user.
PrimaryManager | IDType | True | | | The primary manager of this user.
ProviderAtLoginOption | String | False | | | How the user should be prompted for a provider when logging in.
ReportGrouper1 | String | True | | | New value for the user's first free-text report grouper item, which does not have an Epic-defined meaning.
ReportGrouper2 | String | True | | | New value for the user's second free-text report grouper item, which does not have an Epic-defined meaning.
ReportGrouper3 | String | True | | | New value for the user's third free-text report grouper item, which does not have an Epic-defined meaning.
Sex | String | True | | | The sex of the user.
StartDate | String | True | | | The date on which the user becomes active. The default value is the current date.
SystemLoginID | String | True | | | New value for the user's system login. Must be unique. Maximum length 254 characters.
UserAlias | String | True | | | New value for the user's alias.
UserComplexName | PersonName | True | | | Individual pieces of a user's name. If UserName is not provided, this is required. If this is given, it will be used instead of UserName.
UserComplexName.AcademicTitle | String | True | | | Person’s academic title for name
UserComplexName.FatherName | String | True | | | Name of person’s father
UserComplexName.FirstName | String | True | | | Person’s first name
UserComplexName.GivenNameInitials | String | True | | | Person’s given name initials
UserComplexName.GrandfatherName | String | True | | | Name of person’s grandfather
UserComplexName.LastName | String | True | | | Person’s last name
UserComplexName.LastNamePrefix | String | True | | | Person’s last name prefix
UserComplexName.MiddleName | String | True | | | Person’s middle name
UserComplexName.PrimaryTitle | String | True | | | Person’s primary title
UserComplexName.SpouseLastName | String | True | | | Last name of person’s spouse
UserComplexName.SpouseLastNameFirst | Boolean | True | | | Whether the last name of the person’s spouse is listed first
UserComplexName.SpousePrefix | String | True | | | The prefix of the spouse’s name
UserComplexName.Suffix | String | True | | | Person name suffix
UserDictionaryPath | String | True | | | Starting in Epic May 2020, this element is no longer supported. Value of the path to user dictionary file.
UserID | String | False | | | Identifier for the user whose record is being updated.
UserIDType | String | False | | | Type of identifier provided in UserID. You can specify Internal, External, CID, SystemLogin, or the descriptor of an Identity ID. Defaults to Internal if not provided.
UserPhotoPath | String | True | | | A URL or file path identifying the location of a picture to show for this user. Maximum length 260 characters.
UserRoleIDs | IndexedRecordIn | True | Yes
UserRoleIDs.Identifier | IDType | False | | | Identifier for the record.
UserRoleIDs.Index | String | False | | | Number indicating the ordering of the record. Should be a sequence of consecutive numbers starting from 1.
UsersManagers | IDType | True | Yes | | List of this user's managers. If provided, should include the PrimaryManager.
UserSubtemplateIDs | IndexedRecordIn | False | Yes

Response elements

Name | Type | Optional | Array | Cardinality | Description
Messages | String | True | | | A list of human-readable messages about the successful user update.

Errors

Code | Severity | Description | Example
LICENSE-NOT-FOUND | None | | Organization is not licensed for this feature.
NO-USER-ID | None | | Missing required parameter UserID.
NO-USER-FOUND | None | | Unable to resolve UserID and UserIDType combination to a unique user record.
INVALID-RECORD-TYPE | None | | UserID and UserIDType identify a background user or template record, which is not a valid target for this service.
EMP-LOCK-FAILED | None | | The user record is currently locked by another user.
NO-INDEX | None | | Missing index value for an ordered multiple response item.
NO-ITEMS-SELECTED | None | | Missing required parameter Items or it contains only invalid entries.
INVALID-ITEM-MODE | None | | Invalid value provided for Mode of an item - should be Append, Replace, or empty.
BAD-ITEM-LIST | None | | Same item is listed more than once with different modes.
TEMPLATE-ITEM | None | | Attempted to set an item that is defined by a template.
SUBTEMPLATE-ITEM | None | | Attempted to set an item that is defined by a subtemplate.
ITEMS-PROTECTED | None | | Cannot fulfill the request because an item is EMFI/DC protected and this is not the owning deployment.
CREATE-CONTACT-FAILED | None | | Error creating new contact for user.
INVALID-CONTACT-DATE | None | | Contact date provided is invalid or out of range.
INVALID-SYSTEM-LOGIN-ID | None | | System login value provided is invalid or already in use.
INVALID-SYSTEM-LOGIN-ID-LENGTH | None | | System login cannot exceed 192 characters.
INVALID-NAME | None | | Invalid value provided for Name.
NO-LAST-NAME | None | | A last name is required.
INVALID-LAST-NAME | None | | Last name can only contain alphabetic and punctuation characters.
INVALID-GIVEN-NAME-INITIALS | None | | Given name initials must end in a period.
INVALID-USER-ALIAS-LENGTH | None | | User alias cannot exceed 192 characters.
INVALID-REPORT-GROUPER1-LENGTH | None | | Report grouper 1 cannot exceed 254 characters.
INVALID-REPORT-GROUPER2-LENGTH | None | | Report grouper 2 cannot exceed 254 characters.
INVALID-REPORT-GROUPER3-LENGTH | None | | Report grouper 3 cannot exceed 254 characters.
INVALID-START-DATE | None | | Invalid value provided for start date.
INVALID-END-DATE | None | | Invalid value provided for end date.
INVALID-ACTIVE-DATES | None | | Start date is after end date.
INVALID-USER-ROLE-ID | None | | Invalid value provided for a user role.
INVALID-CUSTOM-DICT | None | | Invalid value provided for CustomUserDictionaries.
INVALID-DICT-PATH | None | | Invalid value provided for UserDictionaryPath.
INVALID-SUBTEMPLATES | None | | Attempted to set a total of more than 7 subtemplates.
INVALID-SUBTEMPLATE-ID | None | | Linked subtemplate ID and ID type did not match an active linked template record.
INVALID-AUTH-CONFIG-ID | None | | Authentication configuration ID and ID type did not match a record.
INVALID-BLOCK-STATUS-REASON | None | | Invalid value provided for block status reason.
INVALID-LINKED-PROVIDER-ID | None | | Invalid ID/Type combination for Linked Provider.
INVALID-LOGIN-DEPT-ID | None | | Invalid ID/Type combination for DefaultLoginDepartment.
INVALID-EXTERNAL-ID | None | | Invalid value provided for an external identifier.
NO-EXTERNAL-ID-TYPE | None | | Missing external identifier type.
DUP-EXTERNAL-ID-TYPE | None | | External ID types list cannot contain duplicate values.
INVALID-IDENTITY-ID-TYPE | None | | Identity ID type provided did not match descriptor of a valid ID type.
INVALID-IDENTITY-ID | None | | Identity ID provided already in use or does not meet requirements for that ID type.
SET-NAME-FAILED | None | | Error setting name for user.
TEMPLATE-FAILED | None | | Error setting template for user.
SUBTEMPLATE-FAILED | None | | Error setting subtemplate for user.
IDENTITY-ID-ERROR | None | | Error setting Identity IDs for user.
INVALID-LDAP-OVERRIDE-ID-LENGTH | None | | LDAPOverrideID cannot exceed 192 characters.
INVALID-USER-PHOTO-PATH | None | | Invalid value provided for UserPhotoPath
INVALID-USER-PHOTO-PATH-LENGTH | None | | UserPhotoPath cannot exceed 260 characters.
INVALID-LINKED-TEMPLATES-CONFIG | None | | The linked template setup provided was invalid
INVALID-DEFAULT-TEMPLATE-ID | None | | Default template ID did not match a record.
INVALID-APPLIED-TEMPLATE-ID | None | | Applied template ID did not match a record.
INVALID-LOGIN-TYPE | None | | Login type does not match a category value.
INVALID-SEX | None | | Invalid value provided for Sex
INVALID-EMPLOYEE-DEMOGRAPHICS1 | None | | Invalid value provided for first employee demographic item
INVALID-EMPLOYEE-DEMOGRAPHICS2 | None | | Invalid value provided for second employee demographic item
INVALID-EMPLOYEE-DEMOGRAPHICS3 | None | | Invalid value provided for third employee demographic item
INVALID-CATEGORY-REPORT-GROUPER1 | None | | Invalid value provided for first category report grouper item
INVALID-CATEGORY-REPORT-GROUPER2 | None | | Invalid value provided for second category report grouper item
INVALID-CATEGORY-REPORT-GROUPER3 | None | | Invalid value provided for third category report grouper item
INVALID-CATEGORY-REPORT-GROUPER4 | None | | Invalid value provided for fourth category report grouper item
INVALID-CATEGORY-REPORT-GROUPER5 | None | | Invalid value provided for fifth category report grouper item
INVALID-CATEGORY-REPORT-GROUPER6 | None | | Invalid value provided for sixth category report grouper item
INVALID-NOTES | None | | Invalid value provided for Notes
INVALID-NOTES-LENGTH | None | | Notes cannot exceed 2000 characters.
INVALID-PRIMARY-MANAGER-ID | None | | Invalid ID/Type combination for PrimaryManager

INVALID-USER-MANAGER | None | | Invalid ID/Type combination for a user's manager
INVALID-PROVIDER-AT-LOGIN-OPTION | None | | Invalid value provided for ProviderAtLoginOption
INVALID-INDEX | None | | The index value contains non-numeric characters, is less than 1, or is greater than the maximum value
INVALID-CONTACT-COMMENT-LENGTH | None | | Contact comments cannot exceed 100 characters.
INVALID-IB-CLASS | None | | In Basket classification did not match a category value or has duplicate values.

Sample request

```
<UpdateUser xmlns:xsi="http://www.w3.org/2001/XMLSchema-instance" xmlns="urn:Epic-
    com:Security.2014.Services.PersonnelManagement">
  <UserID xsi:nil="false">MSEEGER2</UserID>
  <UserIDType xsi:nil="false">Systemlogin</UserIDType>
  <ReportGrouper1 xsi:nil="false">B988</ReportGrouper1>
  <CategoryReportGrouper1 xsi:nil="false">
    <string xmlns="http://schemas.microsoft.com/2003/10/Serialization/Arrays" xsi:nil="false">1</string>
    <string xmlns="http://schemas.microsoft.com/2003/10/Serialization/Arrays" xsi:nil="false">3</string>
  </CategoryReportGrouper1>
  <AuthenticationConfigurationID xsi:nil="false">
    <ID xmlns="urn:Epic-com:Security.2012.Services.PersonnelManagement" xsi:nil="false">1</ID>
    <Type xmlns="urn:Epic-com:Security.2012.Services.PersonnelManagement" xsi:nil="false">External</Type>
  </AuthenticationConfigurationID>
  <UserRoleIDs xsi:nil="false">
    <IndexedRecordIn xmlns="urn:Epic-com:Security.2012.Services.PersonnelManagement" xsi:nil="false">
      <Identifier xsi:nil="false">
        <ID xsi:nil="false">AMB_QA_DOCTOR</ID>
        <Type xsi:nil="false">Alias</Type>
      </Identifier>
      <Index xsi:nil="false">1</Index>
    </IndexedRecordIn>
    <IndexedRecordIn xmlns="urn:Epic-com:Security.2012.Services.PersonnelManagement" xsi:nil="false">
      <Identifier xsi:nil="false">
        <ID xsi:nil="false">IP_ED_PHYSICIAN</ID>
        <Type xsi:nil="false">Alias</Type>
      </Identifier>
      <Index xsi:nil="false">2</Index>
    </IndexedRecordIn>
  </UserRoleIDs>
  <Items xsi:nil="false">
    <Item xmlns="urn:Epic-com:Security.2012.Services.PersonnelManagement" xsi:nil="false">
      <Mode xsi:nil="false">Replace</Mode>
      <Name xsi:nil="false">ReportGrouper1</Name>
    </Item>
    <Item xmlns="urn:Epic-com:Security.2012.Services.PersonnelManagement" xsi:nil="false">
      <Mode xsi:nil="false">Append</Mode>
      <Name xsi:nil="false">CategoryReportGrouper1</Name>
    </Item>
    <Item xmlns="urn:Epic-com:Security.2012.Services.PersonnelManagement" xsi:nil="false">
      <Mode xsi:nil="false">Replace</Mode>
      <Name xsi:nil="false">AuthenticationConfigurationID</Name>
    </Item>
    <Item xmlns="urn:Epic-com:Security.2012.Services.PersonnelManagement" xsi:nil="false">
      <Mode xsi:nil="false">Append</Mode>
      <Name xsi:nil="false">UserRoleIDs</Name>
    </Item>
  </Items>
</UpdateUser>
```

Sample response

```
<UpdateUserResponse xmlns="urn:Epic-com:Security.2014.Services.PersonnelManagement">
  <UpdateUserResult xmlns:i="http://www.w3.org/2001/XMLSchema-instance">
    <Messages xmlns:a="http://schemas.microsoft.com/2003/10/Serialization/Arrays">
      <a:string/>
    </Messages>
  </UpdateUserResult>
</UpdateUserResponse>
```

32.3.23 UpdateUser (2026)

File: site/apis/32-Security/3-Non-FHIR/40304-UpdateUser-2026.html
Epic API ID | 40304
FHIR version | Non-FHIR
Categories | Security
API type | Epic Public
API group | Personnel Management Group
USCDI | No
HTTP method | POST
URL template | /api/epic/2026/Security/PersonnelManagement/UpdateUser/Personnel/User/Update`Name`ContactDate`ContactComment`SystemLoginID`LDAPOverrideID`IsActive`StartDate`EndDate`UserAlias`UserPhotoPath`Sex`ReportGrouper1`ReportGrouper2`ReportGrouper3`CategoryReportGrouper1*`CategoryReportGrouper2*`CategoryReportGrouper3*`CategoryReportGrouper4*`CategoryReportGrouper5*`CategoryReportGrouper6*`Notes`InBasketClassifications*`UserDictionaryPath`ProviderAtLoginOption`ForceContactCreation`UserComplexName***`AuthenticationConfigurationID***`BlockStatus***`LinkedTemplatesConfig***`UserSubtemplateIDs***`EmployeeDemographics***`PrimaryManager***`UsersManagers***`UserRoleIDs***`DefaultLoginDepartmentID***`CustomUserDictionaries***`LinkedProviderID***`IdentityIDs***`ExternalIdentifiers***`Items***`UserID***`AuditUserID***

Supports OAuth 2.0 | True
Supported user types | Backend Systems and Non-OAuth 2.0
Performs scope validation | False
Source | https://fhir.epic.com/Specifications?api=40304

Remarks

If any error is encountered, the record is not modified. If input is unambiguous and valid, but poorly formatted, it may be corrected automatically. If so, the response contains descriptions of what was changed in the messages element.

To modify an item, that item must be listed in the Items array. For most items, the old value will be cleared and replaced with the new value, but for some multiple response items, you can choose to append new values to the end of the list.

To clear an item, do not include the element corresponding to the item in the request, but instead list the item by name in the Items array.

To leave an item unchanged, do not include the item in the Items array.

Request parameters

Name | Type | Optional | Array | Cardinality | Description
AuditUserID | IDType | True | | | A generic identifier.
AuditUserID.ID | String | False | | | The identifier for this resource.
AuditUserID.Type | String | False | | | The type of identifier.
AuthenticationConfigurationID | IDType | False | | | A generic identifier.
AuthenticationConfigurationID.ID | String | False | | | The identifier for this resource.
AuthenticationConfigurationID.Type | String | False | | | The type of identifier.
BlockStatus | BlockStatus | True | | | A user's block status.
BlockStatus.Comment | String | True | | | Free text comment about why the user is blocked.
BlockStatus.IsBlocked | Boolean | False | | | Should the user be blocked?
BlockStatus.Reason | String | False | | | Category value for block reason if we are blocking the user.
CategoryReportGrouper1 | String | True | Yes
CategoryReportGrouper2 | String | True | Yes
CategoryReportGrouper3 | String | True | Yes
CategoryReportGrouper4 | String | True | Yes
CategoryReportGrouper5 | String | True | Yes
CategoryReportGrouper6 | String | True | Yes
ContactComment | String | True
ContactDate | String | True
CustomUserDictionaries | IndexedString | True | Yes | | Starting in Epic May 2020, this element is no longer supported. List of values for custom user dictionary files.
CustomUserDictionaries.Index | String | False | | | Number indicating priority of the value - smaller numbers override larger ones.
CustomUserDictionaries.Value | String | False | | | Value of this string.
DefaultLoginDepartmentID | IDType | True | | | A generic identifier.
DefaultLoginDepartmentID.ID | String | False | | | The identifier for this resource.
DefaultLoginDepartmentID.Type | String | False | | | The type of identifier.
EmployeeDemographics | EmployeeDemographics | True | Yes | | Customizable items used for demographic information about a user specific to a contact.
EmployeeDemographics.EmployeeDemographic1 | String | At least one EmployeeDemographic must be provided per index provided. | | | Value of the first employee demographic item. Typically job code.
EmployeeDemographics.EmployeeDemographic2 | String | At least one EmployeeDemographic must be provided per index provided. | | | Value of the second employee demographic item. Typically payroll department.
EmployeeDemographics.EmployeeDemographic3 | String | At least one EmployeeDemographic must be provided per index provided. | | | Value of the third employee demographic item. Typically location.
EmployeeDemographics.Index | String | False | | | Number indicating the ordering of the values. Should be a sequence of consecutive numbers starting from 1.
EndDate | String | True
ExternalIdentifiers | ExternalIdentifier | False | Yes | | List of external ID items set for this user.
ExternalIdentifiers.Identifier | String | True | | | External identifier for the user.
ExternalIdentifiers.IdentifierType | String | False | | | External identifier type.
ExternalIdentifiers.IsActive | Boolean | True | | | True if the identifier is active.
ForceContactCreation | Boolean | False
IdentityIDs | IDType | True | Yes | | A generic identifier.
IdentityIDs.ID | String | False | | | The identifier for this resource.
IdentityIDs.Type | String | False | | | The type of identifier.
InBasketClassifications | String | True | Yes
IsActive | Boolean | True
Items | Item | False | Yes | | Array of items to update in this request. A tag that appears as the Name of an item here will be updated, even if it is empty.
Items.Mode | String | True | | | Default is "Replace." Can be set to "Append" for UserRoleIDs, CustomUserDictionaries, InBasketClassifications, LinkedSubtemplateIDs, UserSubtemplateIDs and CategoryReportGroupers.
Items.Name | String | False | | | Name of the item to update. EMP items will not be updated unless the parameter name (SystemLoginID, StartDate, etc) is given as a Name in the items list.
LDAPOverrideID | String | True
LinkedProviderID | IDType | True | | | A generic identifier.

LinkedProviderID.ID | String | False | | | The identifier for this resource.
LinkedProviderID.Type | String | False | | | The type of identifier.
LinkedTemplatesConfig | LinkedTemplatesConfig2026 | True
LinkedTemplatesConfig.AppliedTemplateID | IDType | False | | | A generic identifier.
LinkedTemplatesConfig.AppliedTemplateID.ID | String | False | | | The identifier for this resource.
LinkedTemplatesConfig.AppliedTemplateID.Type | String | False | | | The type of identifier.
LinkedTemplatesConfig.AvailableLinkableTemplates | AvailableTemplateSetup2026 | False | Yes
LinkedTemplatesConfig.AvailableLinkableTemplates.EndDate | String | True
LinkedTemplatesConfig.AvailableLinkableTemplates.LinkedTemplateID | IDType | False | | | A generic identifier.
LinkedTemplatesConfig.AvailableLinkableTemplates.LinkedTemplateID.ID | String | False | | | The identifier for this resource.
LinkedTemplatesConfig.AvailableLinkableTemplates.LinkedTemplateID.Type | String | False | | | The type of identifier.
LinkedTemplatesConfig.AvailableLinkableTemplates.LoginBlueprintID | IDType | True | | | A generic identifier.
LinkedTemplatesConfig.AvailableLinkableTemplates.LoginBlueprintID.ID | String | False | | | The identifier for this resource.
LinkedTemplatesConfig.AvailableLinkableTemplates.LoginBlueprintID.Type | String | False | | | The type of identifier.
LinkedTemplatesConfig.AvailableLinkableTemplates.LoginTypes | String | True | Yes
LinkedTemplatesConfig.AvailableLinkableTemplates.StartDate | String | True
LinkedTemplatesConfig.DefaultTemplateID | IDType | False | | | A generic identifier.
LinkedTemplatesConfig.DefaultTemplateID.ID | String | False | | | The identifier for this resource.
LinkedTemplatesConfig.DefaultTemplateID.Type | String | False | | | The type of identifier.
Name | String | If a UserComplexName is provided, name is ignored.
Notes | String | True
PrimaryManager | IDType | True | | | A generic identifier.
PrimaryManager.ID | String | False | | | The identifier for this resource.
PrimaryManager.Type | String | False | | | The type of identifier.
ProviderAtLoginOption | String | False
ReportGrouper1 | String | True
ReportGrouper2 | String | True
ReportGrouper3 | String | True
Sex | String | True
StartDate | String | True
SystemLoginID | String | True
UserAlias | String | True
UserComplexName | PersonName | If UserName is provided, UserComplexName is required. | | | Individual pieces of a user's name. If UserName is not provided, this is required. If this is given, it will be used instead of UserName.
UserComplexName.AcademicTitle | String | True | | | Person’s academic title for name
UserComplexName.FatherName | String | True | | | Name of person’s father
UserComplexName.FirstName | String | True | | | Person’s first name
UserComplexName.GivenNameInitials | String | True | | | Person’s given name initials
UserComplexName.GrandfatherName | String | True | | | Name of person’s grandfather
UserComplexName.LastName | String | True | | | Person’s last name
UserComplexName.LastNamePrefix | String | True | | | Person’s last name prefix
UserComplexName.MiddleName | String | True | | | Person’s middle name
UserComplexName.PrimaryTitle | String | True | | | Person’s primary title
UserComplexName.SpouseLastName | String | True | | | Last name of person’s spouse
UserComplexName.SpouseLastNameFirst | Boolean | True | | | Whether the last name of the person’s spouse is listed first
UserComplexName.SpousePrefix | String | True | | | The prefix of the spouse’s name
UserComplexName.Suffix | String | True | | | Person name suffix
UserDictionaryPath | String | True
UserID | IDType | False | | | A generic identifier.
UserID.ID | String | False | | | The identifier for this resource.
UserID.Type | String | False | | | The type of identifier.
UserPhotoPath | String | True
UserRoleIDs | IndexedRecordIn | True | Yes
UserRoleIDs.Identifier | IDType | False | | | A generic identifier.
UserRoleIDs.Identifier.ID | String | False | | | The identifier for this resource.
UserRoleIDs.Identifier.Type | String | False | | | The type of identifier.
UserRoleIDs.Index | String | False | | | Number indicating the ordering of the record. Should be a sequence of consecutive numbers starting from 1.
UsersManagers | IDType | True | Yes | | A generic identifier.
UsersManagers.ID | String | False | | | The identifier for this resource.
UsersManagers.Type | String | False | | | The type of identifier.
UserSubtemplateIDs | IndexedRecordIn | True | Yes
UserSubtemplateIDs.Identifier | IDType | False | | | A generic identifier.
UserSubtemplateIDs.Identifier.ID | String | False | | | The identifier for this resource.
UserSubtemplateIDs.Identifier.Type | String | False | | | The type of identifier.
UserSubtemplateIDs.Index | String | False | | | Number indicating the ordering of the record. Should be a sequence of consecutive numbers starting from 1.

Response elements

Name | Type | Optional | Array | Cardinality | Description
Messages | String | True | Yes

Errors

Code | Severity | Description | Example
LICENSE-NOT-FOUND | None | | Organization is not licensed for this feature.
NO-USER-ID | None | | Missing required parameter UserID.
NO-USER-FOUND | None | | Unable to resolve UserID and UserIDType combination to a unique user record.
INVALID-RECORD-TYPE | None | | UserID and UserIDType identify a background user or template record, which is not a valid target for this service.
EMP-LOCK-FAILED | None | | The user record is currently locked by another user.
NO-INDEX | None | | Missing index value for an ordered multiple response item.
NO-ITEMS-SELECTED | None | | Missing required parameter Items or it contains only invalid entries.
INVALID-ITEM-MODE | None | | Invalid value provided for Mode of an item - should be Append, Replace, or empty.
BAD-ITEM-LIST | None | | Same item is listed more than once with different modes.
TEMPLATE-ITEM | None | | Attempted to set an item that is defined by a template.
SUBTEMPLATE-ITEM | None | | Attempted to set an item that is defined by a subtemplate.
ITEMS-PROTECTED | None | | Cannot fulfill the request because an item is EMFI/DC protected and this is not the owning deployment.
CREATE-CONTACT-FAILED | None | | Error creating new contact for user.
INVALID-CONTACT-DATE | None | | Contact date provided is invalid or out of range.
INVALID-SYSTEM-LOGIN-ID | None | | System login value provided is invalid or already in use.
INVALID-SYSTEM-LOGIN-ID-LENGTH | None | | System login cannot exceed 192 characters.
INVALID-NAME | None | | Invalid value provided for Name.
NO-LAST-NAME | None | | A last name is required.
INVALID-LAST-NAME | None | | Last name can only contain alphabetic and punctuation characters.
INVALID-GIVEN-NAME-INITIALS | None | | Given name initials must end in a period.
INVALID-USER-ALIAS-LENGTH | None | | User alias cannot exceed 192 characters.
INVALID-REPORT-GROUPER1-LENGTH | None | | Report grouper 1 cannot exceed 254 characters.
INVALID-REPORT-GROUPER2-LENGTH | None | | Report grouper 2 cannot exceed 254 characters.
INVALID-REPORT-GROUPER3-LENGTH | None | | Report grouper 3 cannot exceed 254 characters.
INVALID-START-DATE | None | | Invalid value provided for start date.
INVALID-END-DATE | None | | Invalid value provided for end date.
INVALID-ACTIVE-DATES | None | | Start date is after end date.
INVALID-USER-ROLE-ID | None | | Invalid value provided for a user role.
INVALID-CUSTOM-DICT | None | | Invalid value provided for CustomUserDictionaries.
INVALID-DICT-PATH | None | | Invalid value provided for UserDictionaryPath.
INVALID-SUBTEMPLATES | None | | Attempted to set a total of more than 7 subtemplates.
INVALID-SUBTEMPLATE-ID | None | | Linked subtemplate ID and ID type did not match an active linked template record.
INVALID-AUTH-CONFIG-ID | None | | Authentication configuration ID and ID type did not match a record.
INVALID-BLOCK-STATUS-REASON | None | | Invalid value provided for block status reason.
INVALID-LINKED-PROVIDER-ID | None | | Invalid ID/Type combination for Linked Provider.
INVALID-LOGIN-DEPT-ID | None | | Invalid ID/Type combination for DefaultLoginDepartment.
INVALID-EXTERNAL-ID | None | | Invalid value provided for an external identifier.
NO-EXTERNAL-ID-TYPE | None | | Missing external identifier type.
DUP-EXTERNAL-ID-TYPE | None | | External ID types list cannot contain duplicate values.
INVALID-IDENTITY-ID-TYPE | None | | Identity ID type provided did not match descriptor of a valid ID type.
INVALID-IDENTITY-ID | None | | Identity ID provided already in use or does not meet requirements for that ID type.
SET-NAME-FAILED | None | | Error setting name for user.
TEMPLATE-FAILED | None | | Error setting template for user.
SUBTEMPLATE-FAILED | None | | Error setting subtemplate for user.
INVALID-AUDIT-USER-PASS | None | | An incorrect password was provided for the audit user, or the user account is blocked or inactive.
IDENTITY-ID-ERROR | None | | Error setting Identity IDs for user.
INVALID-LDAP-OVERRIDE-ID-LENGTH | None | | LDAPOverrideID cannot exceed 192 characters.
INVALID-USER-PHOTO-PATH | None | | Invalid value provided for UserPhotoPath
INVALID-USER-PHOTO-PATH-LENGTH | None | | UserPhotoPath cannot exceed 260 characters.
INVALID-LINKED-TEMPLATES-CONFIG | None | | The linked template setup provided was invalid
INVALID-DEFAULT-TEMPLATE-ID | None | | Default template ID did not match a record.
INVALID-APPLIED-TEMPLATE-ID | None | | Applied template ID did not match a record.
INVALID-LOGIN-TYPE | None | | Login type does not match a category value.
INVALID-SEX | None | | Invalid value provided for Sex
INVALID-EMPLOYEE-DEMOGRAPHICS1 | None | | Invalid value provided for first employee demographic item
INVALID-EMPLOYEE-DEMOGRAPHICS2 | None | | Invalid value provided for second employee demographic item
INVALID-EMPLOYEE-DEMOGRAPHICS3 | None | | Invalid value provided for third employee demographic item
INVALID-CATEGORY-REPORT-GROUPER1 | None | | Invalid value provided for first category report grouper item
INVALID-CATEGORY-REPORT-GROUPER2 | None | | Invalid value provided for second category report grouper item
INVALID-CATEGORY-REPORT-GROUPER3 | None | | Invalid value provided for third category report grouper item
INVALID-CATEGORY-REPORT-GROUPER4 | None | | Invalid value provided for fourth category report grouper item
INVALID-CATEGORY-REPORT-GROUPER5 | None | | Invalid value provided for fifth category report grouper item
INVALID-CATEGORY-REPORT-GROUPER6 | None | | Invalid value provided for sixth category report grouper item
INVALID-NOTES | None | | Invalid value provided for Notes
INVALID-NOTES-LENGTH | None | | Notes cannot exceed 2000 characters.
INVALID-PRIMARY-MANAGER-ID | None | | Invalid ID/Type combination for PrimaryManager
INVALID-USER-MANAGER | None | | Invalid ID/Type combination for a user's manager
INVALID-PROVIDER-AT-LOGIN-OPTION | None | | Invalid value provided for ProviderAtLoginOption
INVALID-INDEX | None | | The index value contains non-numeric characters, is less than 1, or is greater than the maximum value

INVALID-CONTACT-COMMENT-LENGTH | None | | Contact comments cannot exceed 100 characters.
INVALID-IB-CLASS | None | | In Basket classification did not match a category value or has duplicate values.
INVALID-LOGIN-BLUEPRINT-ID | None | | Login Blueprint ID did not match a record.
INVALID-LOGIN-BLUEPRINT | None | | Login Blueprint is not of valid type.

Sample request

```
<UpdateUser xmlns:xsi="http://www.w3.org/2001/XMLSchema-instance" xmlns="urn:Epic-
    com:Security.2026.Services.PersonnelManagement">
  <LinkedTemplatesConfig xsi:nil="false">
    <AppliedTemplateID xsi:nil="false">
      <ID xmlns="urn:Epic-com:Security.2012.Services.PersonnelManagement" xsi:nil="false">T00421</ID>
      <Type xmlns="urn:Epic-com:Security.2012.Services.PersonnelManagement" xsi:nil="false">External</Type>
    </AppliedTemplateID>
    <AvailableLinkableTemplates xsi:nil="false">
      <AvailableTemplateSetup2026 xsi:nil="false">
        <LinkedTemplateID xsi:nil="false">
          <ID xmlns="urn:Epic-com:Security.2012.Services.PersonnelManagement" xsi:nil="false">T00421</ID>
          <Type xmlns="urn:Epic-com:Security.2012.Services.PersonnelManagement" xsi:nil="false">External</Type>
        </LinkedTemplateID>
        <LoginBlueprintID xsi:nil="false">
          <ID xmlns="urn:Epic-com:Security.2012.Services.PersonnelManagement" xsi:nil="false">803275</ID>
          <Type xmlns="urn:Epic-com:Security.2012.Services.PersonnelManagement" xsi:nil="false">External</Type>
        </LoginBlueprintID>
        <StartDate xsi:nil="false">T+5</StartDate>
      </AvailableTemplateSetup2026>
    </AvailableLinkableTemplates>
  </LinkedTemplatesConfig>
  <ReportGrouper1 xsi:nil="false">B988</ReportGrouper1>
  <CategoryReportGrouper1 xsi:nil="false">
    <string xmlns="http://schemas.microsoft.com/2003/10/Serialization/Arrays" xsi:nil="false">1</string>
    <string xmlns="http://schemas.microsoft.com/2003/10/Serialization/Arrays" xsi:nil="false">3</string>
  </CategoryReportGrouper1>
  <AuthenticationConfigurationID xsi:nil="false">
    <ID xmlns="urn:Epic-com:Security.2012.Services.PersonnelManagement" xsi:nil="false">1</ID>
    <Type xmlns="urn:Epic-com:Security.2012.Services.PersonnelManagement" xsi:nil="false">External</Type>
  </AuthenticationConfigurationID>
  <UserRoleIDs xsi:nil="false">
    <IndexedRecordIn xmlns="urn:Epic-com:Security.2012.Services.PersonnelManagement" xsi:nil="false">
      <Identifier xsi:nil="false">
        <ID xsi:nil="false">AMB_QA_DOCTOR</ID>
        <Type xsi:nil="false">Alias</Type>
      </Identifier>
      <Index xsi:nil="false">1</Index>
    </IndexedRecordIn>
    <IndexedRecordIn xmlns="urn:Epic-com:Security.2012.Services.PersonnelManagement" xsi:nil="false">
      <Identifier xsi:nil="false">
        <ID xsi:nil="false">IP_ED_PHYSICIAN</ID>
        <Type xsi:nil="false">Alias</Type>
      </Identifier>
      <Index xsi:nil="false">2</Index>
    </IndexedRecordIn>
  </UserRoleIDs>
  <Items xsi:nil="false">
    <Item xmlns="urn:Epic-com:Security.2012.Services.PersonnelManagement" xsi:nil="false">
      <Mode xsi:nil="false">Replace</Mode>
      <Name xsi:nil="false">ReportGrouper1</Name>
    </Item>
    <Item xmlns="urn:Epic-com:Security.2012.Services.PersonnelManagement" xsi:nil="false">
      <Mode xsi:nil="false">Append</Mode>
      <Name xsi:nil="false">CategoryReportGrouper1</Name>
    </Item>
    <Item xmlns="urn:Epic-com:Security.2012.Services.PersonnelManagement" xsi:nil="false">
      <Mode xsi:nil="false">Replace</Mode>
      <Name xsi:nil="false">AuthenticationConfigurationID</Name>
    </Item>
    <Item xmlns="urn:Epic-com:Security.2012.Services.PersonnelManagement" xsi:nil="false">
      <Mode xsi:nil="false">Append</Mode>
      <Name xsi:nil="false">UserRoleIDs</Name>
    </Item>
    <Item xmlns="urn:Epic-com:Security.2012.Services.PersonnelManagement" xsi:nil="false">
      <Mode xsi:nil="false">Replace</Mode>
      <Name xsi:nil="false">LinkedTemplatesConfig</Name>
    </Item>
  </Items>
  <UserID xsi:nil="false">
    <ID xmlns="urn:Epic-com:Security.2012.Services.PersonnelManagement" xsi:nil="false">T023984</ID>
    <Type xmlns="urn:Epic-com:Security.2012.Services.PersonnelManagement" xsi:nil="false">External</Type>
  </UserID>
  <AuditUserID xsi:nil="false">
    <ID xmlns="urn:Epic-com:Security.2012.Services.PersonnelManagement" xsi:nil="false">22566</ID>
    <Type xmlns="urn:Epic-com:Security.2012.Services.PersonnelManagement" xsi:nil="false">External</Type>
  </AuditUserID>
</UpdateUser>
```

Sample response

```
<UpdateUserResponse xmlns="urn:Epic-com:Security.2026.Services.PersonnelManagement">
```

```
  <UpdateUserResult xmlns:i="http://www.w3.org/2001/XMLSchema-instance">
    <Messages xmlns:a="http://schemas.microsoft.com/2003/10/Serialization/Arrays">
      <a:string/>
    </Messages>
  </UpdateUserResult>
</UpdateUserResponse>
```

32.3.24 UpdateUserGroups

File: site/apis/32-Security/3-Non-FHIR/507-UpdateUserGroups.html
Epic API ID | 507
FHIR version | Non-FHIR
Categories | Security
API type | Epic Public
API group | Personnel Management Group
USCDI | No
HTTP method | POST
URL template | api/epic/2016/Security/PersonnelManagement/UpdateUserGroups/Personnel/User/Groups/Update
Supports OAuth 2.0 | True
Supported user types | Backend Systems and Non-OAuth 2.0
Performs scope validation | False
SOAP namespace | urn:Epic-com:Security.2016.Services.PersonnelManagement
WSDL | http://vs-icx.epic.com/Interconnect-CDE/wcf/Epic.Security.GeneratedServices/PersonnelManagement.svc?wsdl
Source | https://fhir.epic.com/Specifications?api=507

Request parameters

Name | Type | Optional | Array | Cardinality | Description
Append | Boolean | False | | | Set to True to append values if supported.
AuditUserID | IDType | False | | | A generic identifier.
AuditUserID.ID | String | False | | | The identifier for this resource.
AuditUserID.Type | String | False | | | The type of identifier.
UserGroups | String | True | Yes | | The new values for the User Groups item.
UserID | IDType | False | | | A generic identifier.
UserID.ID | String | False | | | The identifier for this resource.
UserID.Type | String | False | | | The type of identifier.

Response elements

Name | Type | Optional | Array | Cardinality | Description
Messages | String | False | Yes | | Reserved for future use to send back human readable messages from a successful update.

Errors

Code | Severity | Description | Example
LICENSE-NOT-FOUND | None | | The organization is not licensed for this feature.
NO-USER-ID | None | | The web service request did not specify the required UserID field.
INVALID-AUDIT-USER-ID | None | | The audit user passed in could not be found.
EMP-LOCK-FAILED | None | | Unable to obtain lock on specified user record.
NO-USER-FOUND | None | | A user ID was received, but a corresponding record could not be found, or the identifier did not produce a unique user record.
INVALID-RECORD-TYPE | None | | A user record was identified, but the record is a background user or (sub)template record, which is not a valid target for this service.
INVALID-USER-GROUP | None | | An invalid value was provided for the user group.
TEMPLATE-ITEM | None | | The web service attempted to set an item that is defined by a template.
SUBTEMPLATE-ITEM | None | | The web service attempted to set an item that is defined by a subtemplate.
ITEMS-PROTECTED | None | | Cannot fulfill the request because an item being updated is EMFI/Data Courier protected and this is not the owning deployment.

Sample request

```
<UpdateUserGroups xmlns="urn:Epic-com:Security.2016.Services.PersonnelManagement"
    xmlns:xsi="http://www.w3.org/2001/XMLSchema-instance">
  <UserGroups xsi:nil="false">
    <string xmlns="http://schemas.microsoft.com/2003/10/Serialization/Arrays" xsi:nil="false">1215</string>
    <string xmlns="http://schemas.microsoft.com/2003/10/Serialization/Arrays" xsi:nil="false">adg2</string>
    <string xmlns="http://schemas.microsoft.com/2003/10/Serialization/Arrays" xsi:nil="false">438201</string>
  </UserGroups>
  <Append>false</Append>
  <UserID xsi:nil="false">
    <ID xmlns="urn:Epic-com:Security.2012.Services.PersonnelManagement" xsi:nil="false">11605</ID>
    <Type xmlns="urn:Epic-com:Security.2012.Services.PersonnelManagement" xsi:nil="false">external</Type>
  </UserID>
  <AuditUserID xsi:nil="false">
    <ID xmlns="urn:Epic-com:Security.2012.Services.PersonnelManagement" xsi:nil="false">secadm</ID>
    <Type xmlns="urn:Epic-com:Security.2012.Services.PersonnelManagement" xsi:nil="false">systemlogin</Type>
  </AuditUserID>
</UpdateUserGroups>
```

Sample response

```
<?xml version="1.0" encoding="utf-16"?>
<s:Envelope xmlns:s="http://schemas.xmlsoap.org/soap/envelope/">
<s:Body>
<UpdateUserGroupsResponse xmlns="urn:Epic-com:Security.2016.Services.PersonnelManagement">
<UpdateUserGroupsResult xmlns:i="http://www.w3.org/2001/XMLSchema-instance">
<Messages i:nil="true" xmlns:a="http://schemas.microsoft.com/2003/10/Serialization/Arrays" />
</UpdateUserGroupsResult>
</UpdateUserGroupsResponse>
</s:Body>
</s:Envelope>
```

32.3.25 ViewAuthorizedServiceAreas

File: site/apis/32-Security/3-Non-FHIR/460-ViewAuthorizedServiceAreas.html
Epic API ID | 460
FHIR version | Non-FHIR
Categories | Security
API type | Epic Public
API group | Personnel Management Group
USCDI | No
URL template | api/epic/2017/Security/PersonnelManagement/ViewAuthorizedServiceAreas/Personnel/User/AuthorizedServiceAreas/View
Supports OAuth 2.0 | True
Supported user types | Backend Systems and Non-OAuth 2.0, Clinicians or Administrative Users
Performs scope validation | False
SOAP namespace | urn:Epic-com:Security.2017.Services.PersonnelManagement
WSDL | http://vs-icx.epic.com/Interconnect-CDE/wcf/Epic.Security.GeneratedServices/PersonnelManagement.svc?wsdl
Source | https://fhir.epic.com/Specifications?api=460

Request parameters

Name | Type | Optional | Array | Cardinality | Description
AuditUserID | IDType | True | | | A generic identifier.
AuditUserID.ID | String | False | | | The identifier for this resource.
AuditUserID.Type | String | False | | | The type of identifier.
UserID | IDType | False | | | A generic identifier.
UserID.ID | String | False | | | The identifier for this resource.
UserID.Type | String | False | | | The type of identifier.

Response elements

Name | Type | Optional | Array | Cardinality | Description
AuthorizedServiceAreas | IndexedRecordOut | False | Yes | | List of default roles for the user.
AuthorizedServiceAreas.Identifiers | IDType | True | Yes | | A generic identifier.
AuthorizedServiceAreas.Identifiers.ID | String | False | | | The identifier for this resource.
AuthorizedServiceAreas.Identifiers.Type | String | False | | | The type of identifier.
AuthorizedServiceAreas.Index | String | False | | | Number indicating priority of the record - smaller numbers override larger ones.

Errors

Code | Severity | Description | Example
INVALID-RECORD-TYPE | None | | A user record was identified, but the record is a background user, template, or subtemplate record, which is not a valid target for this service.
NO-USER-FOUND | None | | A user ID was received, but a corresponding record could not be found, or the identifier did not produce a unique user record.
LICENSE-NOT-FOUND | None | | The organization is not licensed for this feature.
NO-USER-ID | None | | The web service request did not specify the required UserID field.
INVALID-AUDIT-USER | None | | The audit user passed in could not be found.

Sample request

```
<ViewAuthorizedServiceAreas xmlns="urn:Epic-com:Security.2017.Services.PersonnelManagement"
    xmlns:xsi="http://www.w3.org/2001/XMLSchema-instance">
  <!--idtype occurs:0,1-->
  <UserID xsi:nil="false">
    <!--string occurs:0,1-->
    <ID xmlns="urn:Epic-com:Security.2012.Services.PersonnelManagement" xsi:nil="false">24714</ID>
    <!--string occurs:0,1-->
    <Type xmlns="urn:Epic-com:Security.2012.Services.PersonnelManagement" xsi:nil="false">external</Type>
  </UserID>
  <!--idtype occurs:0,1-->
  <AuditUserID xsi:nil="false">
    <!--string occurs:0,1-->
    <ID xmlns="urn:Epic-com:Security.2012.Services.PersonnelManagement" xsi:nil="false">24714</ID>
    <!--string occurs:0,1-->
    <Type xmlns="urn:Epic-com:Security.2012.Services.PersonnelManagement" xsi:nil="false">external</Type>
  </AuditUserID>
```

```
</ViewAuthorizedServiceAreas>
```

Sample response

```
<?xml version="1.0" encoding="utf-16"?>
<s:Envelope xmlns:s="http://schemas.xmlsoap.org/soap/envelope/">
<s:Header>
<ServerMetrics xmlns="Epic.Core.Communication">[{"BlockReads":10,"BlockWrites":0,"BlocksAllocated":0,"DBTime":13,"ECFNet
    workTime":2,"ECFRequestCount":0,"ECFRequestTime":15,"GREF":192,"JournalEntries":0,"LocksFailed":0,"LocksGranted":0,"
    MCommands":1805,"MemoryDifference":188416,"WorkflowEventBlockReads":10,"WorkflowEventDBTime":13,"WorkflowEventECFNet
    workTime":0,"WorkflowEventECFRequestCount":0,"WorkflowEventGREF":192}]</ServerMetrics>
</s:Header>
<s:Body>
<ViewAuthorizedServiceAreasResponse xmlns="urn:Epic-com:Security.2017.Services.PersonnelManagement">
<ViewAuthorizedServiceAreasResult xmlns:i="http://www.w3.org/2001/XMLSchema-instance">
<AuthorizedServiceAreas xmlns:a="urn:Epic-com:Security.2012.Services.PersonnelManagement">
<a:IndexedRecordOut>
<a:Identifiers>
<a:IDType>
<a:ID>1</a:ID>
<a:Type>External</a:Type>
</a:IDType>
<a:IDType>
<a:ID>1</a:ID>
<a:Type>Internal</a:Type>
</a:IDType>
<a:IDType>
<a:ID>EPIC FACILITY</a:ID>
<a:Type>Name</a:Type>
</a:IDType>
</a:Identifiers>
<a:Index>1</a:Index>
</a:IndexedRecordOut>
</AuthorizedServiceAreas>
</ViewAuthorizedServiceAreasResult>
</ViewAuthorizedServiceAreasResponse>
</s:Body>
</s:Envelope>
```

32.3.26 ViewBIDefaultUser

File: site/apis/32-Security/3-Non-FHIR/508-ViewBIDefaultUser.html
Epic API ID | 508
FHIR version | Non-FHIR
Categories | Security
API type | Epic Public
API group | Personnel Management Group
USCDI | No
HTTP method | POST
URL template | api/epic/2017/Security/PersonnelManagement/ViewBIDefaultUser/User/ViewBIDefaultUser
Supports OAuth 2.0 | True
Supported user types | Backend Systems and Non-OAuth 2.0
Performs scope validation | False
SOAP namespace | urn:Epic-com:Security.2017.Services.PersonnelManagement
WSDL | Epic.Security.GeneratedServices/PersonnelManagement.svc?wsdl
Source | https://fhir.epic.com/Specifications?api=508

Request parameters

Name | Type | Optional | Array | Cardinality | Description
AuditUserID | IDType | True | | | A generic identifier.
UserID | IDType | False | | | A generic identifier.

Response elements

Name | Type | Optional | Array | Cardinality | Description
BIDefaultUser | String | False
Messages | String | True

Errors

Code | Severity | Description | Example
LICENSE-NOT-FOUND | None | | Organization is not licensed for this feature.

Sample request

```
<ViewBIDefaultUser xmlns="urn:Epic-com:Security.2017.Services.PersonnelManagement"
    xmlns:xsi="http://www.w3.org/2001/XMLSchema-instance">
  <!--idtype occurs:0,1-->
  <UserID xsi:nil="false">
    <!--string occurs:0,1-->
```

```
    <ID xmlns="urn:Epic-com:Security.2012.Services.PersonnelManagement" xsi:nil="false">BIADMIN</ID>
    <!--string occurs:0,1-->
    <Type xmlns="urn:Epic-com:Security.2012.Services.PersonnelManagement" xsi:nil="false">EXTERNAL</Type>
  </UserID>
  <!--idtype occurs:0,1-->
  <AuditUserID xsi:nil="false">
    <!--string occurs:0,1-->
    <ID xmlns="urn:Epic-com:Security.2012.Services.PersonnelManagement" xsi:nil="false">1</ID>
    <!--string occurs:0,1-->
    <Type xmlns="urn:Epic-com:Security.2012.Services.PersonnelManagement" xsi:nil="false">EXTERNAL</Type>
  </AuditUserID>
</ViewBIDefaultUser>
```

Sample response

```
<?xml version="1.0" encoding="utf-16"?>
<s:Envelope xmlns:s="http://schemas.xmlsoap.org/soap/envelope/">
<s:Body>
<ViewBIDefaultUserResponse xmlns="urn:Epic-com:Security.2017.Services.PersonnelManagement">
<ViewBIDefaultUserResult xmlns:i="http://www.w3.org/2001/XMLSchema-instance">
<BIDefaultUser>Administrator</BIDefaultUser>
<Message i:nil="true" xmlns:a="http://schemas.microsoft.com/2003/10/Serialization/Arrays" />
</ViewBIDefaultUserResult>
</ViewBIDefaultUserResponse>
</s:Body>
</s:Envelope>
```

32.3.27 ViewCommunityUser

File: site/apis/32-Security/3-Non-FHIR/395-ViewCommunityUser.html
Epic API ID | 395
FHIR version | Non-FHIR
Categories | Security
API type | Epic Public
API group | Personnel Management Group
USCDI | No
HTTP method | POST
URL template | api/epic/2016/Security/PersonnelManagement/ViewCommunityUser/User/ViewCommunityUser
Supports OAuth 2.0 | True
Supported user types | Backend Systems and Non-OAuth 2.0
Performs scope validation | False
SOAP namespace | urn:Epic-com:Security.2016.Services.PersonnelManagement
WSDL | Epic.Security.GeneratedServices/PersonnelManagement.svc?wsdl
Source | https://fhir.epic.com/Specifications?api=395

Request parameters

Name | Type | Optional | Array | Cardinality | Description
AuditUserID | IDType | True | | | A generic identifier.
UserID | IDType | False | | | A generic identifier.

Response elements

Name | Type | Optional | Array | Cardinality | Description
Deactivated | Boolean | False
ReceiveExternalEmail | Boolean | False
ReceiveGroupNotifications | Boolean | False
SiteManagerContexts | String | True
UserContexts | String | True
WebExternalIdentifier | String | True

Errors

Code | Severity | Description | Example
LICENSE-NOT-FOUND | None | | Organization is not licensed for this feature.
NO-USER-ID | None | | Web service request did not specify the required UserID field.
INVALID-AUDIT-USER | None | | The audit user passed in could not be found.
NO-USER-FOUND | None | | A user ID was received, but a corresponding record could not be found, or the identifier did not produce a unique user record.
INVALID-RECORD-TYPE | None | | A user record was identified, but the record is a background user or (sub)template record, which is not a valid target for this service.

Sample request

```
<ViewCommunityUser xmlns="urn:Epic-com:Security.2016.Services.PersonnelManagement"
    xmlns:xsi="http://www.w3.org/2001/XMLSchema-instance">
  <!--idtype occurs:0,1-->
  <UserID xsi:nil="false">
    <!--string occurs:0,1-->
```

```
    <ID xmlns="urn:Epic-com:Security.2012.Services.PersonnelManagement" xsi:nil="false">6495</ID>
    <!--string occurs:0,1-->
    <Type xmlns="urn:Epic-com:Security.2012.Services.PersonnelManagement" xsi:nil="false">EXTERNAL</Type>
  </UserID>
  <!--idtype occurs:0,1-->
  <AuditUserID xsi:nil="false">
    <!--string occurs:0,1-->
    <ID xmlns="urn:Epic-com:Security.2012.Services.PersonnelManagement" xsi:nil="false">6495</ID>
    <!--string occurs:0,1-->
    <Type xmlns="urn:Epic-com:Security.2012.Services.PersonnelManagement" xsi:nil="false">EXTERNAL</Type>
  </AuditUserID>
</ViewCommunityUser>
```

Sample response

```
<?xml version="1.0" encoding="utf-16"?>
<s:Envelope xmlns:s="http://www.w3.org/2003/05/soap-envelope" xmlns:a="http://www.w3.org/2005/08/addressing">
<s:Header>
<a:Action s:mustUnderstand="1">urn:Epic-
    com:Security.2016.Services.PersonnelManagement.ViewCommunityUserResponse</a:Action>
<a:RelatesTo>urn:uuid:20953708-00e5-4c07-b40c-9e8f4e6e92da</a:RelatesTo>
</s:Header>
<s:Body>
<ViewCommunityUserResponse xmlns="urn:Epic-com:Security.2016.Services.PersonnelManagement">
<ViewCommunityUserResult xmlns:i="http://www.w3.org/2001/XMLSchema-instance">
<Deactivated>false</Deactivated>
<ReceiveExternalEmail>true</ReceiveExternalEmail>
<ReceiveGroupNotifications>true</ReceiveGroupNotifications>
<SiteManagerContexts xmlns:b="http://schemas.microsoft.com/2003/10/Serialization/Arrays">
<b:string>Dinj Context</b:string>
</SiteManagerContexts>
<UserContexts xmlns:b="http://schemas.microsoft.com/2003/10/Serialization/Arrays">
<b:string>Dinj Context</b:string>
</UserContexts>
<WebExternalIdentifier>bcarlyon</WebExternalIdentifier>
</ViewCommunityUserResult>
</ViewCommunityUserResponse>
</s:Body>
</s:Envelope>
```

32.3.28 ViewCurrentReportSelectionCriteria

File: site/apis/32-Security/3-Non-FHIR/396-ViewCurrentReportSelectionCriteria.html
Epic API ID | 396
FHIR version | Non-FHIR
Categories | Security
API type | Epic Public
API group | Personnel Management Group
USCDI | No
HTTP method | POST
URL template |
api/epic/2015/Security/PersonnelManagement/ViewCurrentReportSelectionCriteria/User/ViewCurrentReportSelectionCriteria?UserID={UserID}
Supports OAuth 2.0 | True
Supported user types | Backend Systems and Non-OAuth 2.0
Performs scope validation | False
SOAP namespace | urn:Epic-com:Security.2015.Services.PersonnelManagement
WSDL | Epic.Security.GeneratedServices/PersonnelManagement.svc?wsdl
Source | https://fhir.epic.com/Specifications?api=396

Remarks

Gets information about the various report selection criteria.

If the report selection criteria are defined by linkable templates, the values returned will be from the currently applied linkable template only.

Request parameters

Name | Type | Optional | Array | Cardinality | Description
AuditUserID | String | True
AuditUserIDType | String | True
AuditUserPassword | String | True
UserID | String | False
UserIDType | String | True

Response elements

Name | Type | Optional | Array | Cardinality | Description
ReportAuthorizedDepartmentGroups | IndexedRecordOut | True | Yes | | List of default roles for the user.
ReportAuthorizedDepartments | IndexedRecordOut | True | Yes | | List of default roles for the user.
ReportAuthorizedLocations | IndexedRecordOut | True | Yes | | List of default roles for the user.

ReportAuthorizedProviders | IndexedRecordOut | True | Yes | | List of default roles for the user.
ReportAuthorizedServiceAreas | IndexedRecordOut | True | Yes | | List of default roles for the user.
ReportAuthorizedUsers | IndexedRecordOut | True | Yes | | List of default roles for the user.

Errors

Code | Severity | Description | Example
LICENSE-NOT-FOUND | None | | Organization is not licensed for this feature.
NO-USER-ID | None | | Missing required parameter UserID.
NO-USER-FOUND | None | | Unable to resolve UserID and UserIDType combination to a unique user record.
INVALID-RECORD-TYPE | None | | UserID and UserIDType identify a background user or template record, which is not a valid target for this service.

Sample request

```
<ViewCurrentReportSelectionCriteria xmlns="urn:Epic-com:Security.2015.Services.PersonnelManagement"
    xmlns:xsi="http://www.w3.org/2001/XMLSchema-instance">
  <!--string occurs:0,1-->
  <UserID xsi:nil="false">24445</UserID>
  <!--string occurs:0,1-->
  <UserIDType xsi:nil="false">external</UserIDType>
</ViewCurrentReportSelectionCriteria>
```

Sample response

```
<?xml version="1.0" encoding="utf-16"?>
<s:Envelope xmlns:s="http://schemas.xmlsoap.org/soap/envelope/">
<s:Body>
<ViewCurrentReportSelectionCriteriaResponse xmlns="urn:Epic-com:Security.2015.Services.PersonnelManagement">
<ViewCurrentReportSelectionCriteriaResult xmlns:i="http://www.w3.org/2001/XMLSchema-instance">
<ReportAuthorizedDepartmentGroups xmlns:a="urn:Epic-com:Security.2012.Services.PersonnelManagement">
<a:IndexedRecordOut>
<a:Identifiers>
<a:IDType>
<a:ID>100020</a:ID>
<a:Type>External</a:Type>
</a:IDType>
<a:IDType>
<a:ID>100020</a:ID>
<a:Type>Internal</a:Type>
</a:IDType>
<a:IDType>
<a:ID>APLB DEP VCG</a:ID>
<a:Type>Name</a:Type>
</a:IDType>
</a:Identifiers>
<a:Index>1</a:Index>
</a:IndexedRecordOut>
</ReportAuthorizedDepartmentGroups>
<ReportAuthorizedDepartments xmlns:a="urn:Epic-com:Security.2012.Services.PersonnelManagement">
<a:IndexedRecordOut>
<a:Identifiers>
<a:IDType>
<a:ID>274</a:ID>
<a:Type>External</a:Type>
</a:IDType>
<a:IDType>
<a:ID>274</a:ID>
<a:Type>Internal</a:Type>
</a:IDType>
<a:IDType>
<a:ID>ADASDASA</a:ID>
<a:Type>Name</a:Type>
</a:IDType>
</a:Identifiers>
<a:Index>1</a:Index>
</a:IndexedRecordOut>
</ReportAuthorizedDepartments>
<ReportAuthorizedLocations xmlns:a="urn:Epic-com:Security.2012.Services.PersonnelManagement">
<a:IndexedRecordOut>
<a:Identifiers>
<a:IDType>
<a:ID>953301</a:ID>
<a:Type>External</a:Type>
</a:IDType>
<a:IDType>
<a:ID>953301</a:ID>
<a:Type>Internal</a:Type>
</a:IDType>
<a:IDType>
<a:ID>aetest2</a:ID>
<a:Type>Name</a:Type>
</a:IDType>
</a:Identifiers>
<a:Index>1</a:Index>
</a:IndexedRecordOut>
</ReportAuthorizedLocations>
```

```
<ReportAuthorizedProviders xmlns:a="urn:Epic-com:Security.2012.Services.PersonnelManagement">
<a:IndexedRecordOut>
<a:Identifiers>
<a:IDType>
<a:ID>66679</a:ID>
<a:Type>External</a:Type>
</a:IDType>
<a:IDType>
<a:ID> 66679</a:ID>
<a:Type>Internal</a:Type>
</a:IDType>
<a:IDType>
<a:ID>AARDVARK,ADAM</a:ID>
<a:Type>Name</a:Type>
</a:IDType>
</a:Identifiers>
<a:Index>1</a:Index>
</a:IndexedRecordOut>
</ReportAuthorizedProviders>
<ReportAuthorizedServiceAreas xmlns:a="urn:Epic-com:Security.2012.Services.PersonnelManagement">
<a:IndexedRecordOut>
<a:Identifiers>
<a:IDType>
<a:ID>1307600</a:ID>
<a:Type>External</a:Type>
</a:IDType>
<a:IDType>
<a:ID>1307600</a:ID>
<a:Type>Internal</a:Type>
</a:IDType>
<a:IDType>
<a:ID>AGW TEST FACILITY</a:ID>
<a:Type>Name</a:Type>
</a:IDType>
</a:Identifiers>
<a:Index>1</a:Index>
</a:IndexedRecordOut>
</ReportAuthorizedServiceAreas>
<ReportAuthorizedUsers xmlns:a="urn:Epic-com:Security.2012.Services.PersonnelManagement">
<a:IndexedRecordOut>
<a:Identifiers>
<a:IDType>
<a:ID>113414</a:ID>
<a:Type>External</a:Type>
</a:IDType>
<a:IDType>
<a:ID> 113414</a:ID>
<a:Type>Internal</a:Type>
</a:IDType>
<a:IDType>
<a:ID>TEST, TEST</a:ID>
<a:Type>Name</a:Type>
</a:IDType>
</a:Identifiers>
<a:Index>1</a:Index>
</a:IndexedRecordOut>
</ReportAuthorizedUsers>
</ViewCurrentReportSelectionCriteriaResult>
</ViewCurrentReportSelectionCriteriaResponse>
</s:Body>
</s:Envelope>
```


32.3.29 ViewFacilityDepartmentList

File: site/apis/32-Security/3-Non-FHIR/461-ViewFacilityDepartmentList.html
Epic API ID | 461
FHIR version | Non-FHIR
Categories | Security
API type | Epic Public
API group | Personnel Management Group
USCDI | No
HTTP method | POST
URL template | api/epic/2017/Security/PersonnelManagement/ViewFacilityDepartmentList/Personnel/User/FacilityDepartmentList/View
Supports OAuth 2.0 | True
Supported user types | Backend Systems and Non-OAuth 2.0
Performs scope validation | False
SOAP namespace | urn:Epic-com:Security.2017.Services.PersonnelManagement
WSDL | http://vs-icx.epic.com/Interconnect-CDE/wcf/Epic.Security.GeneratedServices/PersonnelManagement.svc?wsdl
Source | https://fhir.epic.com/Specifications?api=461

Request parameters

Name | Type | Optional | Array | Cardinality | Description

AuditUserID | IDType | True | | | A generic identifier.
UserID | IDType | False | | | A generic identifier.

Response elements

Name | Type | Optional | Array | Cardinality | Description
FacilityDepartmentList | IndexedRecordOut | False | Yes | | List of default roles for the user.
FacilityDepartmentList.Identifiers | IDType | True | Yes | | A generic identifier.
FacilityDepartmentList.Index | String | False | | | Number indicating priority of the record - smaller numbers override larger ones.

Errors

Code | Severity | Description | Example
FOUND-PROVIDER-RECORD | None | | The user has a linked provider record that should be used to define these items.
INVALID-RECORD-TYPE | None | | A user record was identified, but the record is a background user, template, or subtemplate record, which is not a valid target for this service.
NO-USER-FOUND | None | | A user ID was received, but a corresponding record could not be found, or the identifier did not produce a unique user record.
LICENSE-NOT-FOUND | None | | The organization is not licensed for this feature.
NO-USER-ID | None | | The web service request did not specify the required UserID field.
INVALID-AUDIT-USER | None | | The audit user passed in could not be found.

Sample request

```
<ViewFacilityDepartmentList xmlns="urn:Epic-com:Security.2017.Services.PersonnelManagement"
    xmlns:xsi="http://www.w3.org/2001/XMLSchema-instance">
  <!--idtype occurs:0,1-->
  <UserID xsi:nil="false">
    <!--string occurs:0,1-->
    <ID xmlns="urn:Epic-com:Security.2012.Services.PersonnelManagement" xsi:nil="false">24714</ID>
    <!--string occurs:0,1-->
    <Type xmlns="urn:Epic-com:Security.2012.Services.PersonnelManagement" xsi:nil="false">external</Type>
  </UserID>
  <!--idtype occurs:0,1-->
  <AuditUserID xsi:nil="false">
    <!--string occurs:0,1-->
    <ID xmlns="urn:Epic-com:Security.2012.Services.PersonnelManagement" xsi:nil="false">24714</ID>
    <!--string occurs:0,1-->
    <Type xmlns="urn:Epic-com:Security.2012.Services.PersonnelManagement" xsi:nil="false">external</Type>
  </AuditUserID>
</ViewFacilityDepartmentList>
```

Sample response

```
<?xml version="1.0" encoding="utf-16"?>
<s:Envelope xmlns:s="http://schemas.xmlsoap.org/soap/envelope/">
<s:Header>
<ServerMetrics xmlns="Epic.Core.Communication">[{"BlockReads":0,"BlockWrites":0,"BlocksAllocated":0,"DBTime":0,"ECFNetwo
    rkTime":2,"ECFRequestCount":0,"ECFRequestTime":2,"GREF":189,"JournalEntries":0,"LocksFailed":0,"LocksGranted":0,"MCo
    mmands":1806,"MemoryDifference":155648,"WorkflowEventBlockReads":0,"WorkflowEventDBTime":0,"WorkflowEventECFNetworkT
    ime":0,"WorkflowEventECFRequestCount":0,"WorkflowEventGREF":189}]</ServerMetrics>
</s:Header>
<s:Body>
<ViewFacilityDepartmentListResponse xmlns="urn:Epic-com:Security.2017.Services.PersonnelManagement">
<ViewFacilityDepartmentListResult xmlns:i="http://www.w3.org/2001/XMLSchema-instance">
<FacilityDepartmentList xmlns:a="urn:Epic-com:Security.2012.Services.PersonnelManagement">
<a:IndexedRecordOut>
<a:Identifiers>
<a:IDType>
<a:ID>2</a:ID>
<a:Type>External</a:Type>
</a:IDType>
<a:IDType>
<a:ID>2</a:ID>
<a:Type>Internal</a:Type>
</a:IDType>
<a:IDType>
<a:ID>INITIAL UNIT</a:ID>
<a:Type>Name</a:Type>
</a:IDType>
</a:Identifiers>
<a:Index>1</a:Index>
</a:IndexedRecordOut>
</FacilityDepartmentList>
</ViewFacilityDepartmentListResult>
</ViewFacilityDepartmentListResponse>
</s:Body>
</s:Envelope>
```

32.3.30 ViewLoginDepartments

File: site/apis/32-Security/3-Non-FHIR/462-ViewLoginDepartments.html
Epic API ID | 462

FHIR version | Non-FHIR
Categories | Security
API type | Epic Public
API group | Personnel Management Group
USCDI | No
HTTP method | POST
URL template | api/epic/2016/Security/PersonnelManagement/ViewLoginDepartments/Personnel/User/LoginDepartments/View
Supports OAuth 2.0 | True
Supported user types | Backend Systems and Non-OAuth 2.0, Clinicians or Administrative Users
Performs scope validation | False
SOAP namespace | urn:Epic-com:Security.2016.Services.PersonnelManagement
WSDL | http://vs-icx.epic.com/Interconnect-CDE/wcf/Epic.Security.GeneratedServices/PersonnelManagement.svc?wsdl
Source | https://fhir.epic.com/Specifications?api=462

Request parameters

Name | Type | Optional | Array | Cardinality | Description
AuditUserID | IDType | True | | | A generic identifier.
UserID | IDType | False | | | A generic identifier.

Response elements

Name | Type | Optional | Array | Cardinality | Description
DefaultLoginDepartmentID | IDType | True | Yes | | A generic identifier.
DepartmentFilterSetting | String | True
LoginDepartmentFilterList | IndexedRecordOut | False | Yes | | List of default roles for the user.
PreferredLoginDepartments | IndexedRecordOut | False | Yes | | List of default roles for the user.
PreferredLoginDepartments.Identifiers | IDType | True | Yes | | A generic identifier.
PreferredLoginDepartments.Index | String | False | | | Number indicating priority of the record - smaller numbers override larger ones.

Errors

Code | Severity | Description | Example
LICENSE-NOT-FOUND | None | | The organization is not licensed for this feature.
NO-USER-ID | None | | The web service request did not specify the required UserID field.
INVALID-AUDIT-USER-ID | None | | The audit user passed in could not be found.
NO-USER-FOUND | None | | A user ID was received, but a corresponding record could not be found, or the identifier did not produce a unique user record.
INVALID-RECORD-TYPE | None | | A user record was identified, but the record is a background user or (sub)template record, which is not a valid target for this service.

Sample request

```
<ViewLoginDepartments xmlns="urn:Epic-com:Security.2016.Services.PersonnelManagement"
    xmlns:xsi="http://www.w3.org/2001/XMLSchema-instance">
  <UserID xsi:nil="false">
    <ID xmlns="urn:Epic-com:Security.2012.Services.PersonnelManagement" xsi:nil="false">11605</ID>
    <Type xmlns="urn:Epic-com:Security.2012.Services.PersonnelManagement" xsi:nil="false">external</Type>
  </UserID>
  <AuditUserID xsi:nil="false">
    <ID xmlns="urn:Epic-com:Security.2012.Services.PersonnelManagement" xsi:nil="false">secadm</ID>
    <Type xmlns="urn:Epic-com:Security.2012.Services.PersonnelManagement" xsi:nil="false">systemlogin</Type>
  </AuditUserID>
</ViewLoginDepartments>
```

Sample response

```
<?xml version="1.0" encoding="utf-16"?>
<s:Envelope xmlns:s="http://schemas.xmlsoap.org/soap/envelope/">
<s:Body>
<ViewLoginDepartmentsResponse xmlns="urn:Epic-com:Security.2016.Services.PersonnelManagement">
<ViewLoginDepartmentsResult xmlns:i="http://www.w3.org/2001/XMLSchema-instance">
<DefaultLoginDepartmentID xmlns:a="urn:Epic-com:Security.2012.Services.PersonnelManagement" />
<DepartmentFilterSetting>Inclusive</DepartmentFilterSetting>
<LoginDepartmentFilterList xmlns:a="urn:Epic-com:Security.2012.Services.PersonnelManagement">
<a:IndexedRecordOut>
<a:Identifiers>
<a:IDType>
<a:ID>385</a:ID>
<a:Type>External</a:Type>
</a:IDType>
<a:IDType>
<a:ID>385</a:ID>
<a:Type>Internal</a:Type>
</a:IDType>
<a:IDType>
<a:ID>3 SW (ILION)</a:ID>
<a:Type>Name</a:Type>
</a:IDType>
</a:Identifiers>
```

<a:Index>1</a:Index>
</a:IndexedRecordOut>
<a:IndexedRecordOut>
<a:Identifiers>
<a:IDType>
<a:ID>451</a:ID>
<a:Type>External</a:Type>
</a:IDType>
<a:IDType>
<a:ID>451</a:ID>
<a:Type>Internal</a:Type>
</a:IDType>
<a:IDType>
<a:ID>3 NW (ILION)</a:ID>
<a:Type>Name</a:Type>
</a:IDType>
</a:Identifiers>
<a:Index>2</a:Index>
</a:IndexedRecordOut>
<a:IndexedRecordOut>
<a:Identifiers>
<a:IDType>
<a:ID>1</a:ID>
<a:Type>External</a:Type>
</a:IDType>
<a:IDType>
<a:ID>1</a:ID>
<a:Type>Internal</a:Type>
</a:IDType>
<a:IDType>
<a:ID>INITIAL DEPARTMENT</a:ID>
<a:Type>Name</a:Type>
</a:IDType>
</a:Identifiers>
<a:Index>3</a:Index>
</a:IndexedRecordOut>
<a:IndexedRecordOut>
<a:Identifiers>
<a:IDType>
<a:ID>3001</a:ID>
<a:Type>External</a:Type>
</a:IDType>
<a:IDType>
<a:ID>3001</a:ID>
<a:Type>Internal</a:Type>
</a:IDType>
<a:IDType>
<a:ID>2NT FH</a:ID>
<a:Type>Name</a:Type>
</a:IDType>
</a:Identifiers>
<a:Index>4</a:Index>
</a:IndexedRecordOut>
<a:IndexedRecordOut>
<a:Identifiers>
<a:IDType>
<a:ID>468</a:ID>
<a:Type>External</a:Type>
</a:IDType>
<a:IDType>
<a:ID>468</a:ID>
<a:Type>Internal</a:Type>
</a:IDType>
<a:IDType>
<a:ID>$1N (THEBES)</a:ID>
<a:Type>Name</a:Type>
</a:IDType>
</a:Identifiers>
<a:Index>5</a:Index>
</a:IndexedRecordOut>
</LoginDepartmentFilterList>
<PreferredLoginDepartments xmlns:a="urn:Epic-com:Security.2012.Services.PersonnelManagement">
<a:IndexedRecordOut>
<a:Identifiers>
<a:IDType>
<a:ID>1</a:ID>
<a:Type>External</a:Type>
</a:IDType>
<a:IDType>
<a:ID>1</a:ID>
<a:Type>Internal</a:Type>
</a:IDType>
<a:IDType>
<a:ID>INITIAL DEPARTMENT</a:ID>
<a:Type>Name</a:Type>
</a:IDType>
</a:Identifiers>
<a:Index>1</a:Index>
</a:IndexedRecordOut>

```
<a:IndexedRecordOut>
<a:Identifiers>
<a:IDType>
<a:ID>451</a:ID>
<a:Type>External</a:Type>
</a:IDType>
<a:IDType>
<a:ID>451</a:ID>
<a:Type>Internal</a:Type>
</a:IDType>
<a:IDType>
<a:ID>3 NW (ILION)</a:ID>
<a:Type>Name</a:Type>
</a:IDType>
</a:Identifiers>
<a:Index>2</a:Index>
</a:IndexedRecordOut>
<a:IndexedRecordOut>
<a:Identifiers>
<a:IDType>
<a:ID>385</a:ID>
<a:Type>External</a:Type>
</a:IDType>
<a:IDType>
<a:ID>385</a:ID>
<a:Type>Internal</a:Type>
</a:IDType>
<a:IDType>
<a:ID>3 SW (ILION)</a:ID>
<a:Type>Name</a:Type>
</a:IDType>
</a:Identifiers>
<a:Index>3</a:Index>
</a:IndexedRecordOut>
</PreferredLoginDepartments>
</ViewLoginDepartmentsResult>
</ViewLoginDepartmentsResponse>
</s:Body>
</s:Envelope>
```

32.3.31 ViewUser (2014)

File: site/apis/32-Security/3-Non-FHIR/398-ViewUser-2014.html
Epic API ID | 398
FHIR version | Non-FHIR
Categories | Security
API type | Epic Public
API group | Personnel Management Group
USCDI | No
HTTP method | GET
URL template | api/epic/2014/Security/PersonnelManagement/ViewUser?UserID={UserID}&UserIDType={UserIDType}&ContactDate={ContactDate}&AuditUserID={AuditUserID}&AuditUserIDType={AuditUserIDType}&AuditUserPassword={AuditUserPassword}
Supports OAuth 2.0 | True
Supported user types | Backend Systems and Non-OAuth 2.0, Clinicians or Administrative Users
Performs scope validation | False
SOAP namespace | urn:Epic-com:Security.2014.Services.PersonnelManagement
WSDL | Epic.Security.GeneratedServices/PersonnelManagement.svc?wsdl
Source | https://fhir.epic.com/Specifications?api=398

Request parameters

Name | Type | Optional | Array | Cardinality | Description
AuditUserID | String | True | | | The audit user's ID. Audit User information is not currently used by this web service.
AuditUserIDType | String | True | | | The audit user's ID type. Audit User information is not currently used by this web service.
AuditUserPassword | String | True | | | The audit user's password. Audit User information is not currently used by this web service.
ContactDate | String | True
UserID | String | False | | | Identifier for the user whose record is being viewed.
UserIDType | String | True

Response elements

Name | Type | Optional | Array | Cardinality | Description
AuthenticationConfigurationID | IDType | True | Yes | | A generic identifier.
BlockStatus | BlockStatus | True | | | A user's block status.
BlockStatus.Comment | String | True | | | Free text comment about why the user is blocked.
BlockStatus.IsBlocked | Boolean | False | | | Should the user be blocked?
BlockStatus.Reason | String | False | | | Category value for block reason if we are blocking the user.
CategoryReportGrouper1 | String | True | | | A list of values for the user's first category report grouper item, which does not have an Epic-defined meaning.

CategoryReportGrouper2 | String | True | | | A list of values for the user's second category report grouper item, which does not have an Epic-defined meaning.
CategoryReportGrouper3 | String | True | | | A list of values for the user's third category report grouper item, which does not have an Epic-defined meaning.
CategoryReportGrouper4 | String | True | | | A list of values for the user's fourth category report grouper item, which does not have an Epic-defined meaning.
CategoryReportGrouper5 | String | True | | | A list of values for the user's fifth category report grouper item, which does not have an Epic-defined meaning.
CategoryReportGrouper6 | String | True | | | A list of values for the user's sixth category report grouper item, which does not have an Epic-defined meaning.
ContactComment | String | True
CustomUserDictionaries | IndexedString | True | Yes | | Starting in Epic May 2020, this element is no longer supported. List of values for custom user dictionary files.
CustomUserDictionaries.Index | String | False | | | Number indicating priority of the value - smaller numbers override larger ones.
CustomUserDictionaries.Value | String | False | | | Value of this string.
DefaultLoginDepartmentID | IDType | True | Yes | | A generic identifier.
EmployeeDemographics | EmployeeDemographics | True | Yes | | Customizable items used for demographic information about a user specific to a contact.
EmployeeDemographics.EmployeeDemographic1 | String | True | | | Value of the first employee demographic item. Typically job code.
EmployeeDemographics.EmployeeDemographic2 | String | True | | | Value of the second employee demographic item. Typically payroll department.
EmployeeDemographics.EmployeeDemographic3 | String | True | | | Value of the third employee demographic item. Typically location.
EmployeeDemographics.Index | String | False | | | Number indicating the ordering of the values. Should be a sequence of consecutive numbers starting from 1.
EndDate | String | True
ExternalIdentifiers | ExternalIdentifier | True | Yes | | List of external ID items set for this user.
ExternalIdentifiers.Identifier | String | False | | | External identifier for the user.
ExternalIdentifiers.IdentifierType | String | False | | | External identifier type.
ExternalIdentifiers.IsActive | Boolean | False | | | True if the identifier is active.
InBasketClassifications | String | True | | | List of user's In Basket classifications.
IsActive | Boolean | True
IsPasswordChangeRequired | Boolean | True
LDAPOverrideID | String | True
LinkedProviderID | IDType | True | Yes | | A generic identifier.
LinkedTemplatesConfig | LinkedTemplatesConfigOut | True
LinkedTemplatesConfig.AppliedTemplateID | IDType | False | Yes | | A generic identifier.
LinkedTemplatesConfig.AvailableLinkableTemplates | AvailableTemplateSetupOut | False | Yes
LinkedTemplatesConfig.AvailableLinkableTemplates.EndDate | String | True
LinkedTemplatesConfig.AvailableLinkableTemplates.LinkedTemplateID | IDType | False | Yes | | A generic identifier.
LinkedTemplatesConfig.AvailableLinkableTemplates.LoginTypes | String | True
LinkedTemplatesConfig.AvailableLinkableTemplates.StartDate | String | True
LinkedTemplatesConfig.DefaultTemplateID | IDType | False | Yes | | A generic identifier.
Name | String | False
Notes | String | True
PrimaryManager | IDType | True | Yes | | A generic identifier.
PrimaryManager.ID | String | False | | | The identifier for this resource.
PrimaryManager.Type | String | False | | | The type of identifier.
ProviderAtLoginOption | String | True
ReportGrouper1 | String | True | | | Current value of the user's first free-text report grouper item, which does not have an Epic-defined meaning.
ReportGrouper2 | String | True | | | Current value of the user's second free-text report grouper item, which does not have an Epic-defined meaning.
ReportGrouper3 | String | True | | | Current value of the user's third free-text report grouper item, which does not have an Epic-defined meaning.
Sex | String | True
StartDate | String | True
UserAlias | String | True
UserComplexName | PersonName | False | | | Individual pieces of a user's name. If UserName is not provided, this is required. If this is given, it will be used instead of UserName.
UserComplexName.AcademicTitle | String | True | | | Person’s academic title for name
UserComplexName.FatherName | String | True | | | Name of person’s father
UserComplexName.FirstName | String | True | | | Person’s first name
UserComplexName.GivenNameInitials | String | True | | | Person’s given name initials
UserComplexName.GrandfatherName | String | True | | | Name of person’s grandfather
UserComplexName.LastName | String | True | | | Person’s last name
UserComplexName.LastNamePrefix | String | True | | | Person’s last name prefix
UserComplexName.MiddleName | String | True | | | Person’s middle name
UserComplexName.PrimaryTitle | String | True | | | Person’s primary title
UserComplexName.SpouseLastName | String | True | | | Last name of person’s spouse
UserComplexName.SpouseLastNameFirst | Boolean | True | | | Whether the last name of the person’s spouse is listed first
UserComplexName.SpousePrefix | String | True | | | The prefix of the spouse’s name
UserComplexName.Suffix | String | True | | | Person name suffix
UserDictionaryPath | String | True | | | Starting in Epic May 2020, this element is no longer supported. Value of the path to user dictionary file.
UserIDs | IDType | False | Yes | | A generic identifier.
UserIDs.ID | String | False | | | The identifier for this resource.
UserIDs.Type | String | True | | | The type of identifier.
UserPhotoPath | String | True

UserRoleIDs | IndexedRecordOut | True | Yes | | List of default roles for the user.
UsersManagers | IndexedRecordOut | True | Yes | | List of default roles for the user.
UsersManagers.Identifiers | IDType | False | Yes | | A generic identifier.
UsersManagers.Index | String | False | | | Number indicating priority of the record - smaller numbers override larger ones.
UserSubtemplateIDs | IndexedRecordOut | True | Yes | | List of default roles for the user.
UserSubtemplateIDs.Identifiers | IDType | False | Yes | | A generic identifier.
UserSubtemplateIDs.Index | String | False | | | Number indicating priority of the record - smaller numbers override larger ones.

Errors

Code | Severity | Description | Example
LICENSE-NOT-FOUND | None | Your organization is not licensed for this feature or your license has expired. | Organization is not currently licensed for this feature.
NO-USER-ID | None | No User ID provided. Enter an ID for user lookup. | Missing required parameter UserID.
NO-USER-FOUND | None | User/audit user records cannot be selected with ID type <detail>. | Unable to resolve UserID and UserIDType combination to a unique user record.
NO-USER-FOUND | None | No match was found for a user/an audit user with <DisplayIDType>: <detail> | Unable to resolve UserID and UserIDType combination to a unique user record.
NO-USER-FOUND | None | More than one match was found for user/audit user with <DisplayIDType>: <detail> | Unable to resolve UserID and UserIDType combination to a unique user record.
INVALID-RECORD-TYPE | None | Only records of type 'User' can be selected | UserID and UserIDType do not identify a record of type User and therefore it is not a valid target for this service.
INVALID-RECORD-TYPE | None | Only records of type 'User' or 'Background User' can be selected for the audit user | AuditUserID and AuditUserIDType do not identify a background or foreground user and therefore it is not a valid target for this service.

Sample request

```
<ViewUser xmlns="urn:Epic-com:Security.2014.Services.PersonnelManagement" xmlns:xsi="http://www.w3.org/2001/XMLSchema-
    instance">
  <UserID xsi:nil="false">18577</UserID>
  <UserIDType xsi:nil="false">external</UserIDType>
</ViewUser>
```

Sample response

```
<ViewUserResponse xmlns="urn:Epic-com:Security.2014.Services.PersonnelManagement">
<ViewUserResult xmlns:i="http://www.w3.org/2001/XMLSchema-instance">
<AuthenticationConfigurationID xmlns:a="urn:Epic-com:Security.2012.Services.PersonnelManagement">
<a:Type>
<a:ID>9001</a:ID>
<a:Type>CID</a:Type>
</a:IDType>
<a:IDType>
<a:ID>1</a:ID>
<a:Type>External</a:Type>
</a:IDType>
<a:IDType>
<a:ID>1</a:ID>
<a:Type>Internal</a:Type>
</a:IDType>
<a:IDType>
<a:ID>EPIC NATIVE AUTHENTICATION RECORD</a:ID>
<a:Type>Name</a:Type>
</a:IDType>
</AuthenticationConfigurationID>
<BlockStatus xmlns:a="urn:Epic-com:Security.2012.Services.PersonnelManagement">
<a:Comment />
<a:IsBlocked>false</a:IsBlocked>
<a:Reason />
</BlockStatus>
<CategoryReportGrouper1 xmlns:a="http://schemas.microsoft.com/2003/10/Serialization/Arrays">
<a:string>Building Lakeside</a:string>
<a:string>Building Metro</a:string>
</CategoryReportGrouper1>
<CategoryReportGrouper2 xmlns:a="http://schemas.microsoft.com/2003/10/Serialization/Arrays" />
<CategoryReportGrouper3 xmlns:a="http://schemas.microsoft.com/2003/10/Serialization/Arrays" />
<CategoryReportGrouper4 xmlns:a="http://schemas.microsoft.com/2003/10/Serialization/Arrays" />
<CategoryReportGrouper5 xmlns:a="http://schemas.microsoft.com/2003/10/Serialization/Arrays" />
<CategoryReportGrouper6 xmlns:a="http://schemas.microsoft.com/2003/10/Serialization/Arrays" />
<ContactComment>Initial Entry</ContactComment>
<DefaultLoginDepartmentID xmlns:a="urn:Epic-com:Security.2012.Services.PersonnelManagement">
<a:IDType>
<a:ID>2021</a:ID>
<a:Type>CID</a:Type>
</a:IDType>
<a:IDType>
<a:ID>1</a:ID>
<a:Type>External</a:Type>
</a:IDType>
<a:IDType>
<a:ID>1</a:ID>
<a:Type>Internal</a:Type>
</a:IDType>
<a:IDType>
```

<a:ID>WEST INTERNAL MEDICINE</a:ID>
<a:Type>Name</a:Type>
</a:IDType>
</DefaultLoginDepartmentID>
<EmployeeDemographics />
<EndDate i:nil="true" />
<ExternalIdentifiers xmlns:a="urn:Epic-com:Security.2012.Services.PersonnelManagement" />
<InBasketClassifications xmlns:a="http://schemas.microsoft.com/2003/10/Serialization/Arrays">
<a:string>All physicians</a:string>
<a:string>Scheduling tickler pool</a:string>
<a:string>Letter tickler pool</a:string>
<a:string>Staff</a:string>
<a:string>Utilization Review</a:string>
<a:string>Chart Synchronization Conflicts</a:string>
</InBasketClassifications>
<IsActive>true</IsActive>
<IsPasswordChangeRequired>false</IsPasswordChangeRequired>
<LDAPOverrideID />
<LinkedProviderID xmlns:a="urn:Epic-com:Security.2012.Services.PersonnelManagement">
<a:IDType>
<a:ID>2021</a:ID>
<a:Type>CID</a:Type>
</a:IDType>
<a:IDType>
<a:ID>66516</a:ID>
<a:Type>External</a:Type>
</a:IDType>
<a:IDType>
<a:ID> 66516</a:ID>
<a:Type>Internal</a:Type>
</a:IDType>
<a:IDType>
<a:ID>PROVIDER, STARTER</a:ID>
<a:Type>Name</a:Type>
</a:IDType>
</LinkedProviderID>
<LinkedTemplatesConfig>
<AppliedTemplateID xmlns:a="urn:Epic-com:Security.2012.Services.PersonnelManagement">
<a:IDType>
<a:ID>130298463</a:ID>
<a:Type>CID</a:Type>
</a:IDType>
<a:IDType>
<a:ID>T00271</a:ID>
<a:Type>External</a:Type>
</a:IDType>
<a:IDType>
<a:ID> T00271</a:ID>
<a:Type>Internal</a:Type>
</a:IDType>
<a:IDType>
<a:ID>IP ED PHYS</a:ID>
<a:Type>Name</a:Type>
</a:IDType>
</AppliedTemplateID>
<AvailableLinkableTemplates>
<AvailableTemplateSetupOut>
<EndDate />
<LinkedTemplateID xmlns:a="urn:Epic-com:Security.2012.Services.PersonnelManagement">
<a:IDType>
<a:ID>130298464</a:ID>
<a:Type>CID</a:Type>
</a:IDType>
<a:IDType>
<a:ID>T00272</a:ID>
<a:Type>External</a:Type>
</a:IDType>
<a:IDType>
<a:ID> T00272</a:ID>
<a:Type>Internal</a:Type>
</a:IDType>
<a:IDType>
<a:ID>AMB PHYS</a:ID>
<a:Type>Name</a:Type>
</a:IDType>
</LinkedTemplateID>
<LoginTypes xmlns:a="http://schemas.microsoft.com/2003/10/Serialization/Arrays">
<a:string>Web Suite</a:string>
<a:string>Haiku / Canto</a:string>
</LoginTypes>
<StartDate>7/18/15</StartDate>
</AvailableTemplateSetupOut>
<AvailableTemplateSetupOut>
<EndDate />
<LinkedTemplateID xmlns:a="urn:Epic-com:Security.2012.Services.PersonnelManagement">
<a:IDType>
<a:ID>130298463</a:ID>
<a:Type>CID</a:Type>
</a:IDType>

<a:IDType>
<a:ID>T00271</a:ID>
<a:Type>External</a:Type>
</a:IDType>
<a:IDType>
<a:ID> T00271</a:ID>
<a:Type>Internal</a:Type>
</a:IDType>
<a:IDType>
<a:ID>IP ED PHYS</a:ID>
<a:Type>Name</a:Type>
</a:IDType>
</LinkedTemplateID>
<LoginTypes xmlns:a="http://schemas.microsoft.com/2003/10/Serialization/Arrays" />
<StartDate />
</AvailableTemplateSetupOut>
</AvailableLinkableTemplates>
<DefaultTemplateID xmlns:a="urn:Epic-com:Security.2012.Services.PersonnelManagement">
<a:IDType>
<a:ID>130298463</a:ID>
<a:Type>CID</a:Type>
</a:IDType>
<a:IDType>
<a:ID>T00271</a:ID>
<a:Type>External</a:Type>
</a:IDType>
<a:IDType>
<a:ID> T00271</a:ID>
<a:Type>Internal</a:Type>
</a:IDType>
<a:IDType>
<a:ID>IP ED PHYS</a:ID>
<a:Type>Name</a:Type>
</a:IDType>
</DefaultTemplateID>
</LinkedTemplatesConfig>
<Name>Marty Seeger, MD</Name>
<Notes />
<PrimaryManager xmlns:a="urn:Epic-com:Security.2012.Services.PersonnelManagement" />
<ProviderAtLoginOption />
<ReportGrouper1 />
<ReportGrouper2 />
<ReportGrouper3 />
<Sex />
<StartDate i:nil="true" />
<UserAlias />
<UserComplexName>
<AcademicTitle>MD</AcademicTitle>
<FatherName />
<FirstName>Marty</FirstName>
<GivenNameInitials />
<GrandfatherName />
<LastName>Seeger</LastName>
<LastNamePrefix />
<MiddleName />
<PrimaryTitle>Dr.</PrimaryTitle>
<SpouseLastName />
<SpouseLastNameFirst>false</SpouseLastNameFirst>
<SpousePrefix />
<Suffix />
</UserComplexName>
<UserDictionaryPath />
<UserIDs xmlns:a="urn:Epic-com:Security.2012.Services.PersonnelManagement">
<a:IDType>
<a:ID>2021</a:ID>
<a:Type>CID</a:Type>
</a:IDType>
<a:IDType>
<a:ID>1</a:ID>
<a:Type>External</a:Type>
</a:IDType>
<a:IDType>
<a:ID> 1</a:ID>
<a:Type>Internal</a:Type>
</a:IDType>
<a:IDType>
<a:ID>EPIC, USER</a:ID>
<a:Type>Name</a:Type>
</a:IDType>
<a:IDType>
<a:ID>USEREPIC</a:ID>
<a:Type>SystemLogin</a:Type>
</a:IDType>
</UserIDs>
<UserPhotoPath />
<UserRoleIDs xmlns:a="urn:Epic-com:Security.2012.Services.PersonnelManagement">
<a:IndexedRecordOut>
<a:Identifiers>
<a:IDType>

<a:ID>MR_EPIC_STAFF</a:ID>
<a:Type>Alias</a:Type>
</a:IDType>
<a:IDType>
<a:ID>90017999</a:ID>
<a:Type>CID</a:Type>
</a:IDType>
<a:IDType>
<a:ID>17999</a:ID>
<a:Type>External</a:Type>
</a:IDType>
<a:IDType>
<a:ID>17999</a:ID>
<a:Type>Internal</a:Type>
</a:IDType>
<a:IDType>
<a:ID>MR_EPIC_STAFF</a:ID>
<a:Type>Name</a:Type>
</a:IDType>
</a:Identifiers>
<a:Index>1</a:Index>
</a:IndexedRecordOut>
<a:IndexedRecordOut>
<a:Identifiers>
<a:IDType>
<a:ID>ADMIN_ROLE</a:ID>
<a:Type>Alias</a:Type>
</a:IDType>
<a:IDType>
<a:ID>90014100</a:ID>
<a:Type>CID</a:Type>
</a:IDType>
<a:IDType>
<a:ID>14100</a:ID>
<a:Type>External</a:Type>
</a:IDType>
<a:IDType>
<a:ID>14100</a:ID>
<a:Type>Internal</a:Type>
</a:IDType>
<a:IDType>
<a:ID>ADMIN ROLE</a:ID>
<a:Type>Name</a:Type>
</a:IDType>
</a:Identifiers>
<a:Index>2</a:Index>
</a:IndexedRecordOut>
<a:IndexedRecordOut>
<a:Identifiers>
<a:IDType>
<a:ID>MR_ADM_ROLE</a:ID>
<a:Type>Alias</a:Type>
</a:IDType>
<a:IDType>
<a:ID>90017920</a:ID>
<a:Type>CID</a:Type>
</a:IDType>
<a:IDType>
<a:ID>17920</a:ID>
<a:Type>External</a:Type>
</a:IDType>
<a:IDType>
<a:ID>17920</a:ID>
<a:Type>Internal</a:Type>
</a:IDType>
<a:IDType>
<a:ID>MR_ADM_ROLE</a:ID>
<a:Type>Name</a:Type>
</a:IDType>
</a:Identifiers>
<a:Index>3</a:Index>
</a:IndexedRecordOut>
<a:IndexedRecordOut>
<a:Identifiers>
<a:IDType>
<a:ID>IP_ED_PROVIDER</a:ID>
<a:Type>Alias</a:Type>
</a:IDType>
<a:IDType>
<a:ID>90034750</a:ID>
<a:Type>CID</a:Type>
</a:IDType>
<a:IDType>
<a:ID>34750</a:ID>
<a:Type>External</a:Type>
</a:IDType>
<a:IDType>
<a:ID>34750</a:ID>
<a:Type>Internal</a:Type>

```
</a:IDType>
<a:IDType>
<a:ID>IP_ED_PROVIDER</a:ID>
<a:Type>Name</a:Type>
</a:IDType>
</a:Identifiers>
<a:Index>4</a:Index>
</a:IndexedRecordOut>
</UserRoleIDs>
<UserSubtemplateIDs xmlns:a="urn:Epic-com:Security.2012.Services.PersonnelManagement" />
<UsersManagers xmlns:a="urn:Epic-com:Security.2012.Services.PersonnelManagement" />
</ViewUserResult>
</ViewUserResponse>
```

Change log

32.3.32 ViewUser (2026)

File: site/apis/32-Security/3-Non-FHIR/40305-ViewUser-2026.html
Epic API ID | 40305
FHIR version | Non-FHIR
Categories | Security
API type | Epic Public
API group | Personnel Management Group
USCDI | No
HTTP method | POST
URL template |
/api/epic/2026/Security/PersonnelManagement/ViewUser/Personnel/User/View?ContactDate={ContactDate}`UserID***`AuditUserID***
Supports OAuth 2.0 | True
Supported user types | Backend Systems and Non-OAuth 2.0, Clinicians or Administrative Users
Performs scope validation | False
Source | https://fhir.epic.com/Specifications?api=40305

Request parameters

Name | Type | Optional | Array | Cardinality | Description
AuditUserID | IDType | True | | | A generic identifier.
AuditUserID.ID | String | False | | | The identifier for this resource.
AuditUserID.Type | String | False | | | The type of identifier.
ContactDate | String | True
UserID | IDType | False | | | A generic identifier.
UserID.ID | String | False | | | The identifier for this resource.
UserID.Type | String | False | | | The type of identifier.

Response elements

Name | Type | Optional | Array | Cardinality | Description
AuthenticationConfigurationID | IDType | True | Yes | | A generic identifier.
AuthenticationConfigurationID.ID | String | False | | | The identifier for this resource.
AuthenticationConfigurationID.Type | String | False | | | The type of identifier.
BlockStatus | BlockStatus | True | | | A user's block status.
BlockStatus.Comment | String | True | | | Free text comment about why the user is blocked.
BlockStatus.IsBlocked | Boolean | False if I EMP 55 is null. Otherwise, true. | | | Should the user be blocked?
BlockStatus.Reason | String | False | | | Category value for block reason if we are blocking the user.
CategoryReportGrouper1 | String | True | Yes
CategoryReportGrouper2 | String | True | Yes
CategoryReportGrouper3 | String | True | Yes
CategoryReportGrouper4 | String | True | Yes
CategoryReportGrouper5 | String | True | Yes
CategoryReportGrouper6 | String | True | Yes
ContactComment | String | True
CustomUserDictionaries | IndexedString | True | Yes | | Starting in Epic May 2020, this element is no longer supported. List of values for custom user dictionary files.
CustomUserDictionaries.Index | String | False | | | Number indicating priority of the value - smaller numbers override larger ones.
CustomUserDictionaries.Value | String | False | | | Value of this string.
DefaultLoginDepartmentID | IDType | True | Yes | | A generic identifier.
DefaultLoginDepartmentID.ID | String | False | | | The identifier for this resource.
DefaultLoginDepartmentID.Type | String | False | | | The type of identifier.
EmployeeDemographics | EmployeeDemographics | True | Yes | | Customizable items used for demographic information about a user specific to a contact.
EmployeeDemographics.EmployeeDemographic1 | String | At least one EmployeeDemographic must be provided per index provided. | | | Value of the first employee demographic item. Typically job code.
EmployeeDemographics.EmployeeDemographic2 | String | At least one EmployeeDemographic must be provided per index provided. | | | Value of the second employee demographic item. Typically payroll department.

EmployeeDemographics.EmployeeDemographic3 | String | At least one EmployeeDemographic must be provided per index provided. | | | Value of the third employee demographic item. Typically location.
EmployeeDemographics.Index | String | False | | | Number indicating the ordering of the values. Should be a sequence of consecutive numbers starting from 1.
EndDate | String | True
ExternalIdentifiers | ExternalIdentifier | True | Yes | | List of external ID items set for this user.
ExternalIdentifiers.Identifier | String | False | | | External identifier for the user.
ExternalIdentifiers.IdentifierType | String | False | | | External identifier type.
ExternalIdentifiers.IsActive | Boolean | False | | | True if the identifier is active.
InBasketClassifications | String | True | Yes
IsActive | Boolean | True
IsPasswordChangeRequired | Boolean | True
LDAPOverrideID | String | True
LinkedProviderID | IDType | True | Yes | | A generic identifier.
LinkedProviderID.ID | String | False | | | The identifier for this resource.
LinkedProviderID.Type | String | False | | | The type of identifier.
LinkedTemplatesConfig | LinkedTemplatesConfigOut2026 | False
LinkedTemplatesConfig.AppliedTemplateID | IDType | False | Yes | | A generic identifier.
LinkedTemplatesConfig.AppliedTemplateID.ID | String | False | | | The identifier for this resource.
LinkedTemplatesConfig.AppliedTemplateID.Type | String | False | | | The type of identifier.
LinkedTemplatesConfig.AvailableLinkableTemplates | AvailableTemplateSetupOut2026 | False | Yes
LinkedTemplatesConfig.AvailableLinkableTemplates.EndDate | String | True
LinkedTemplatesConfig.AvailableLinkableTemplates.LinkedTemplateID | IDType | False | Yes | | A generic identifier.
LinkedTemplatesConfig.AvailableLinkableTemplates.LinkedTemplateID.ID | String | False | | | The identifier for this resource.
LinkedTemplatesConfig.AvailableLinkableTemplates.LinkedTemplateID.Type | String | False | | | The type of identifier.
LinkedTemplatesConfig.AvailableLinkableTemplates.LoginBlueprintID | IDType | False | Yes | | A generic identifier.
LinkedTemplatesConfig.AvailableLinkableTemplates.LoginBlueprintID.ID | String | False | | | The identifier for this resource.
LinkedTemplatesConfig.AvailableLinkableTemplates.LoginBlueprintID.Type | String | False | | | The type of identifier.
LinkedTemplatesConfig.AvailableLinkableTemplates.LoginTypes | String | True | Yes
LinkedTemplatesConfig.AvailableLinkableTemplates.StartDate | String | True
LinkedTemplatesConfig.DefaultTemplateID | IDType | False | Yes | | A generic identifier.
LinkedTemplatesConfig.DefaultTemplateID.ID | String | False | | | The identifier for this resource.
LinkedTemplatesConfig.DefaultTemplateID.Type | String | False | | | The type of identifier.
Messages | String | False | Yes
Name | String | False
Notes | String | True
PrimaryManager | IDType | True | Yes | | A generic identifier.
PrimaryManager.ID | String | False | | | The identifier for this resource.
PrimaryManager.Type | String | False | | | The type of identifier.
ProviderAtLoginOption | String | True
ReportGrouper1 | String | True
ReportGrouper2 | String | True
ReportGrouper3 | String | True
Sex | String | True
StartDate | String | True
UserAlias | String | True
UserComplexName | PersonName | False | | | Individual pieces of a user's name. If UserName is not provided, this is required. If this is given, it will be used instead of UserName.
UserComplexName.AcademicTitle | String | True | | | Person’s academic title for name
UserComplexName.FatherName | String | True | | | Name of person’s father
UserComplexName.FirstName | String | True | | | Person’s first name
UserComplexName.GivenNameInitials | String | True | | | Person’s given name initials
UserComplexName.GrandfatherName | String | True | | | Name of person’s grandfather
UserComplexName.LastName | String | True | | | Person’s last name
UserComplexName.LastNamePrefix | String | True | | | Person’s last name prefix
UserComplexName.MiddleName | String | True | | | Person’s middle name
UserComplexName.PrimaryTitle | String | True | | | Person’s primary title
UserComplexName.SpouseLastName | String | True | | | Last name of person’s spouse
UserComplexName.SpouseLastNameFirst | Boolean | True | | | Whether the last name of the person’s spouse is listed first
UserComplexName.SpousePrefix | String | True | | | The prefix of the spouse’s name
UserComplexName.Suffix | String | True | | | Person name suffix
UserDictionaryPath | String | True
UserIDs | IDType | False | Yes | | A generic identifier.
UserIDs.ID | String | False | | | The identifier for this resource.
UserIDs.Type | String | False | | | The type of identifier.
UserPhotoPath | String | True
UserRoleIDs | IndexedRecordOut | True | Yes | | List of default roles for the user.
UserRoleIDs.Identifiers | IDType | False | Yes | | A generic identifier.
UserRoleIDs.Identifiers.ID | String | False | | | The identifier for this resource.
UserRoleIDs.Identifiers.Type | String | False | | | The type of identifier.
UserRoleIDs.Index | String | False | | | Number indicating priority of the record - smaller numbers override larger ones.
UsersManagers | IndexedRecordOut | True | Yes | | List of default roles for the user.

UsersManagers.Identifiers | IDType | False | Yes | | A generic identifier.
UsersManagers.Identifiers.ID | String | False | | | The identifier for this resource.
UsersManagers.Identifiers.Type | String | False | | | The type of identifier.
UsersManagers.Index | String | False | | | Number indicating priority of the record - smaller numbers override larger ones.
UserSubtemplateIDs | IndexedRecordOut | True | Yes | | List of default roles for the user.
UserSubtemplateIDs.Identifiers | IDType | False | Yes | | A generic identifier.
UserSubtemplateIDs.Identifiers.ID | String | False | | | The identifier for this resource.
UserSubtemplateIDs.Identifiers.Type | String | False | | | The type of identifier.
UserSubtemplateIDs.Index | String | False | | | Number indicating priority of the record - smaller numbers override larger ones.

Errors

Code | Severity | Description | Example
LICENSE-NOT-FOUND | None | Your organization is not licensed for this feature or your license has expired. | Organization is not currently licensed for this feature.
NO-USER-ID | None | No User ID provided. Enter an ID for user lookup. | Missing required parameter UserID.
NO-USER-FOUND | None | User/audit user records cannot be selected with ID type . | Unable to resolve ID and Type combination of UserID provided to a unique user record.
NO-USER-FOUND | None | No match was found for a user/an audit user with : | Unable to resolve ID and Type combination of UserID provided to a unique user record.
NO-USER-FOUND | None | More than one match was found for user/audit user with : | Unable to resolve ID and Type combination of UserID provided to a unique user record.
INVALID-RECORD-TYPE | None | Only records of type 'User' can be selected | UserID do not identify a record of type User and therefore it is not a valid target for this service.
INVALID-RECORD-TYPE | None | Only records of type 'User' or 'Background User' can be selected for the audit user | AuditUserID do not identify a background or foreground user and therefore it is not a valid target for this service.

Sample request

```
<ViewUser xmlns="urn:Epic-com:Security.2026.Services.PersonnelManagement" xmlns:xsi="http://www.w3.org/2001/XMLSchema-
    instance">
  <ContactDate xsi:nil="false"/>
  <UserID xsi:nil="false">
    <ID xmlns="urn:Epic-com:Security.2012.Services.PersonnelManagement" xsi:nil="false">31107</ID>
    <Type xmlns="urn:Epic-com:Security.2012.Services.PersonnelManagement" xsi:nil="false">External</Type>
  </UserID>
  <AuditUserID xsi:nil="false">
    <ID xmlns="urn:Epic-com:Security.2012.Services.PersonnelManagement" xsi:nil="false"/>
    <Type xmlns="urn:Epic-com:Security.2012.Services.PersonnelManagement" xsi:nil="false"/>
  </AuditUserID>
</ViewUser>
```

Sample response

```
<ViewUserResponse xmlns="urn:Epic-com:Security.2026.Services.PersonnelManagement">
<ViewUserResult xmlns:i="http://www.w3.org/2001/XMLSchema-instance">
<AuthenticationConfigurationID xmlns:a="urn:Epic-com:Security.2012.Services.PersonnelManagement">
<a:Type>
<a:ID>9001</a:ID>
<a:Type>CID</a:Type>
</a:IDType>
<a:IDType>
<a:ID>1</a:ID>
<a:Type>External</a:Type>
</a:IDType>
<a:IDType>
<a:ID>1</a:ID>
<a:Type>Internal</a:Type>
</a:IDType>
<a:IDType>
<a:ID>EPIC NATIVE AUTHENTICATION RECORD</a:ID>
<a:Type>Name</a:Type>
</a:IDType>
</AuthenticationConfigurationID>
<BlockStatus xmlns:a="urn:Epic-com:Security.2012.Services.PersonnelManagement">
<a:Comment />
<a:IsBlocked>false</a:IsBlocked>
<a:Reason />
</BlockStatus>
<CategoryReportGrouper1 xmlns:a="http://schemas.microsoft.com/2003/10/Serialization/Arrays">
<a:string>Building Lakeside</a:string>
<a:string>Building Metro</a:string>
</CategoryReportGrouper1>
<CategoryReportGrouper2 xmlns:a="http://schemas.microsoft.com/2003/10/Serialization/Arrays" />
<CategoryReportGrouper3 xmlns:a="http://schemas.microsoft.com/2003/10/Serialization/Arrays" />
<CategoryReportGrouper4 xmlns:a="http://schemas.microsoft.com/2003/10/Serialization/Arrays" />
<CategoryReportGrouper5 xmlns:a="http://schemas.microsoft.com/2003/10/Serialization/Arrays" />
<CategoryReportGrouper6 xmlns:a="http://schemas.microsoft.com/2003/10/Serialization/Arrays" />
<ContactComment>Initial Entry</ContactComment>
<DefaultLoginDepartmentID xmlns:a="urn:Epic-com:Security.2012.Services.PersonnelManagement">
<a:IDType>
<a:ID>2021</a:ID>
<a:Type>CID</a:Type>
</a:IDType>
```

<a:IDType>
<a:ID>1</a:ID>
<a:Type>External</a:Type>
</a:IDType>
<a:IDType>
<a:ID>1</a:ID>
<a:Type>Internal</a:Type>
</a:IDType>
<a:IDType>
<a:ID>WEST INTERNAL MEDICINE</a:ID>
<a:Type>Name</a:Type>
</a:IDType>
</DefaultLoginDepartmentID>
<EmployeeDemographics />
<EndDate i:nil="true" />
<ExternalIdentifiers xmlns:a="urn:Epic-com:Security.2012.Services.PersonnelManagement" />
<InBasketClassifications xmlns:a="http://schemas.microsoft.com/2003/10/Serialization/Arrays">
<a:string>All physicians</a:string>
<a:string>Scheduling tickler pool</a:string>
<a:string>Letter tickler pool</a:string>
<a:string>Staff</a:string>
<a:string>Utilization Review</a:string>
<a:string>Chart Synchronization Conflicts</a:string>
</InBasketClassifications>
<IsActive>true</IsActive>
<IsPasswordChangeRequired>false</IsPasswordChangeRequired>
<LDAPOverrideID />
<LinkedProviderID xmlns:a="urn:Epic-com:Security.2012.Services.PersonnelManagement">
<a:IDType>
<a:ID>2021</a:ID>
<a:Type>CID</a:Type>
</a:IDType>
<a:IDType>
<a:ID>66516</a:ID>
<a:Type>External</a:Type>
</a:IDType>
<a:IDType>
<a:ID> 66516</a:ID>
<a:Type>Internal</a:Type>
</a:IDType>
<a:IDType>
<a:ID>PROVIDER, STARTER</a:ID>
<a:Type>Name</a:Type>
</a:IDType>
</LinkedProviderID>
<LinkedTemplatesConfig>
<AppliedTemplateID xmlns:a="urn:Epic-com:Security.2012.Services.PersonnelManagement">
<a:IDType>
<a:ID>181216669</a:ID>
<a:Type>CID</a:Type>
</a:IDType>
<a:IDType>
<a:ID>T00421</a:ID>
<a:Type>External</a:Type>
</a:IDType>
<a:IDType>
<a:ID> T00421</a:ID>
<a:Type>Internal</a:Type>
</a:IDType>
<a:IDType>
<a:ID>MBR TEMPLATE</a:ID>
<a:Type>Name</a:Type>
</a:IDType>
</AppliedTemplateID>
<AvailableLinkableTemplates>
<AvailableTemplateSetupOut2026>
<EndDate />
<LinkedTemplateID xmlns:a="urn:Epic-com:Security.2012.Services.PersonnelManagement">
<a:IDType>
<a:ID>181216669</a:ID>
<a:Type>CID</a:Type>
</a:IDType>
<a:IDType>
<a:ID>T00421</a:ID>
<a:Type>External</a:Type>
</a:IDType>
<a:IDType>
<a:ID> T00421</a:ID>
<a:Type>Internal</a:Type>
</a:IDType>
<a:IDType>
<a:ID>MBR TEMPLATE</a:ID>
<a:Type>Name</a:Type>
</a:IDType>
</LinkedTemplateID>
<LoginBlueprintID xmlns:a="urn:Epic-com:Security.2012.Services.PersonnelManagement">
<a:IDType>
<a:ID>181285155</a:ID>
<a:Type>CID</a:Type>

```
</a:IDType>
<a:IDType>
<a:ID>807746</a:ID>
<a:Type>External</a:Type>
</a:IDType>
<a:IDType>
<a:ID>  807746</a:ID>
<a:Type>Internal</a:Type>
</a:IDType>
<a:IDType>
<a:ID>1000011050</a:ID>
<a:Type>NPI_SER</a:Type>
</a:IDType>
<a:IDType>
<a:ID>TSN LOGIN MD</a:ID>
<a:Type>Name</a:Type>
</a:IDType>
<a:IDType>
<a:ID>181285155</a:ID>
<a:Type>PROVID</a:Type>
</a:IDType>
<a:IDType>
<a:ID>55</a:ID>
<a:Type>SERID</a:Type>
</a:IDType>
</LoginBlueprintID>
<LoginTypes xmlns:a="http://schemas.microsoft.com/2003/10/Serialization/Arrays" />
<StartDate />
</AvailableTemplateSetupOut2026>
</AvailableLinkableTemplates>
<DefaultTemplateID xmlns:a="urn:Epic-com:Security.2012.Services.PersonnelManagement">
<a:IDType>
<a:ID>181216669</a:ID>
<a:Type>CID</a:Type>
</a:IDType>
<a:IDType>
<a:ID>T00421</a:ID>
<a:Type>External</a:Type>
</a:IDType>
<a:IDType>
<a:ID> T00421</a:ID>
<a:Type>Internal</a:Type>
</a:IDType>
<a:IDType>
<a:ID>MBR TEMPLATE</a:ID>
<a:Type>Name</a:Type>
</a:IDType>
</DefaultTemplateID>
</LinkedTemplatesConfig>
<Messages
i:nil="true" xmlns:a="http://schemas.microsoft.com/2003/10/Serialization/Arrays" />
<Name>Marty Seeger, MD</Name>
<Notes />
<PrimaryManager xmlns:a="urn:Epic-com:Security.2012.Services.PersonnelManagement" />
<ProviderAtLoginOption />
<ReportGrouper1 />
<ReportGrouper2 />
<ReportGrouper3 />
<Sex />
<StartDate i:nil="true" />
<UserAlias />
<UserComplexName>
<AcademicTitle>MD</AcademicTitle>
<FatherName />
<FirstName>Marty</FirstName>
<GivenNameInitials />
<GrandfatherName />
<LastName>Seeger</LastName>
<LastNamePrefix />
<MiddleName />
<PrimaryTitle>Dr.</PrimaryTitle>
<SpouseLastName />
<SpouseLastNameFirst>false</SpouseLastNameFirst>
<SpousePrefix />
<Suffix />
</UserComplexName>
<UserDictionaryPath />
<UserIDs xmlns:a="urn:Epic-com:Security.2012.Services.PersonnelManagement">
<a:IDType>
<a:ID>2021</a:ID>
<a:Type>CID</a:Type>
</a:IDType>
<a:IDType>
<a:ID>1</a:ID>
<a:Type>External</a:Type>
</a:IDType>
<a:IDType>
<a:ID> 1</a:ID>
<a:Type>Internal</a:Type>
```

```
</a:IDType>
<a:IDType>
<a:ID>EPIC, USER</a:ID>
<a:Type>Name</a:Type>
</a:IDType>
<a:IDType>
<a:ID>USEREPIC</a:ID>
<a:Type>SystemLogin</a:Type>
</a:IDType>
</UserIDs>
<UserPhotoPath />
<UserRoleIDs xmlns:a="urn:Epic-com:Security.2012.Services.PersonnelManagement">
<a:IndexedRecordOut>
<a:Identifiers>
<a:IDType>
<a:ID>MR_EPIC_STAFF</a:ID>
<a:Type>Alias</a:Type>
</a:IDType>
<a:IDType>
<a:ID>90017999</a:ID>
<a:Type>CID</a:Type>
</a:IDType>
<a:IDType>
<a:ID>17999</a:ID>
<a:Type>External</a:Type>
</a:IDType>
<a:IDType>
<a:ID>17999</a:ID>
<a:Type>Internal</a:Type>
</a:IDType>
<a:IDType>
<a:ID>MR_EPIC_STAFF</a:ID>
<a:Type>Name</a:Type>
</a:IDType>
</a:Identifiers>
<a:Index>1</a:Index>
</a:IndexedRecordOut>
<a:IndexedRecordOut>
<a:Identifiers>
<a:IDType>
<a:ID>ADMIN_ROLE</a:ID>
<a:Type>Alias</a:Type>
</a:IDType>
<a:IDType>
<a:ID>90014100</a:ID>
<a:Type>CID</a:Type>
</a:IDType>
<a:IDType>
<a:ID>14100</a:ID>
<a:Type>External</a:Type>
</a:IDType>
<a:IDType>
<a:ID>14100</a:ID>
<a:Type>Internal</a:Type>
</a:IDType>
<a:IDType>
<a:ID>ADMIN ROLE</a:ID>
<a:Type>Name</a:Type>
</a:IDType>
</a:Identifiers>
<a:Index>2</a:Index>
</a:IndexedRecordOut>
<a:IndexedRecordOut>
<a:Identifiers>
<a:IDType>
<a:ID>MR_ADM_ROLE</a:ID>
<a:Type>Alias</a:Type>
</a:IDType>
<a:IDType>
<a:ID>90017920</a:ID>
<a:Type>CID</a:Type>
</a:IDType>
<a:IDType>
<a:ID>17920</a:ID>
<a:Type>External</a:Type>
</a:IDType>
<a:IDType>
<a:ID>17920</a:ID>
<a:Type>Internal</a:Type>
</a:IDType>
<a:IDType>
<a:ID>MR_ADM_ROLE</a:ID>
<a:Type>Name</a:Type>
</a:IDType>
</a:Identifiers>
<a:Index>3</a:Index>
</a:IndexedRecordOut>
<a:IndexedRecordOut>
<a:Identifiers>
```

```
<a:IDType>
<a:ID>IP_ED_PROVIDER</a:ID>
<a:Type>Alias</a:Type>
</a:IDType>
<a:IDType>
<a:ID>90034750</a:ID>
<a:Type>CID</a:Type>
</a:IDType>
<a:IDType>
<a:ID>34750</a:ID>
<a:Type>External</a:Type>
</a:IDType>
<a:IDType>
<a:ID>34750</a:ID>
<a:Type>Internal</a:Type>
</a:IDType>
<a:IDType>
<a:ID>IP_ED_PROVIDER</a:ID>
<a:Type>Name</a:Type>
</a:IDType>
</a:Identifiers>
<a:Index>4</a:Index>
</a:IndexedRecordOut>
</UserRoleIDs>
<UserSubtemplateIDs xmlns:a="urn:Epic-com:Security.2012.Services.PersonnelManagement" />
<UsersManagers xmlns:a="urn:Epic-com:Security.2012.Services.PersonnelManagement" />
</ViewUserResult>
</ViewUserResponse>
```

32.3.33 ViewUserGroups

File: site/apis/32-Security/3-Non-FHIR/509-ViewUserGroups.html
Epic API ID | 509
FHIR version | Non-FHIR
Categories | Security
API type | Epic Public
API group | Personnel Management Group
USCDI | No
HTTP method | POST
URL template | api/epic/2016/Security/PersonnelManagement/ViewUserGroups/Personnel/User/Groups/View
Supports OAuth 2.0 | True
Supported user types | Backend Systems and Non-OAuth 2.0
Performs scope validation | False
SOAP namespace | urn:Epic-com:Security.2016.Services.PersonnelManagement
WSDL | /wcf/Epic.Security.GeneratedServices/PersonnelManagement.svc?wsdl
Source | https://fhir.epic.com/Specifications?api=509

Request parameters

Name | Type | Optional | Array | Cardinality | Description
AuditUserID | IDType | False | | | A generic identifier.
UserID | IDType | False | | | A generic identifier.

Response elements

Name | Type | Optional | Array | Cardinality | Description
UserGroups | String | True

Errors

Code | Severity | Description | Example
LICENSE-NOT-FOUND | None | | The organization is not licensed for this feature.
NO-USER-ID | None | | The web service request did not specify the required UserID field.
INVALID-AUDIT-USER-ID | None | | The audit user passed in could not be found.
NO-USER-FOUND | None | | A user ID was received, but a corresponding record could not be found, or the identifier did not produce a unique user record.
INVALID-RECORD-TYPE | None | | A user record was identified, but the record is a background user or (sub)template record, which is not a valid target for this service.

Sample request

```
<ViewUserGroups xmlns="urn:Epic-com:Security.2016.Services.PersonnelManagement"
    xmlns:xsi="http://www.w3.org/2001/XMLSchema-instance">
  <UserID xsi:nil="false">
    <ID xmlns="urn:Epic-com:Security.2012.Services.PersonnelManagement" xsi:nil="false">11605</ID>
    <Type xmlns="urn:Epic-com:Security.2012.Services.PersonnelManagement" xsi:nil="false">external</Type>
  </UserID>
  <AuditUserID xsi:nil="false">
    <ID xmlns="urn:Epic-com:Security.2012.Services.PersonnelManagement" xsi:nil="false">secadm</ID>
    <Type xmlns="urn:Epic-com:Security.2012.Services.PersonnelManagement" xsi:nil="false">systemlogin</Type>
```

```
  </AuditUserID>
</ViewUserGroups>
```

Sample response

```
<?xml version="1.0" encoding="utf-16"?>
<s:Envelope xmlns:s="http://schemas.xmlsoap.org/soap/envelope/">
<s:Body>
<ViewUserGroupsResponse xmlns="urn:Epic-com:Security.2016.Services.PersonnelManagement">
<ViewUserGroupsResult xmlns:i="http://www.w3.org/2001/XMLSchema-instance">
<UserGroups xmlns:a="http://schemas.microsoft.com/2003/10/Serialization/Arrays">
<a:string>LNIEDERS GROUP</a:string>
<a:string>adg2</a:string>
<a:string>TW TRANSCRIPTIONIST</a:string>
</UserGroups>
</ViewUserGroupsResult>
</ViewUserGroupsResponse>
</s:Body>
</s:Envelope>
```