Epic-FHIR — API category: Uncategorized (sections 33 – 33.1.1)

Source: Epic on FHIR (fhir.epic.com) documentation, mirrored 2026-11. Text-only edition for AI ingestion (NotebookLM); pages follow the source order (its table of contents when one exists).

33 API category: Uncategorized

File: site/apis/33-Uncategorized/index.html

R4 (1)

API | Method | URL template | Type
QuestionnaireResponse.Read (Prior Auth) (R4) | GET | /api/FHIR/R4/QuestionnaireResponse/{ID} | Industry-Standard

33.1 Uncategorized: R4

File: site/apis/33-Uncategorized/1-R4/index.html

* QuestionnaireResponse.Read (Prior Auth) (R4)

33.1.1 QuestionnaireResponse.Read (Prior Auth) (R4)

File: site/apis/33-Uncategorized/1-R4/11394-QuestionnaireResponse-Read-Prior-Auth-R4.html
Epic API ID | 11394
FHIR version | R4
Categories | Uncategorized
API type | Industry-Standard
USCDI | No
Available in inpatient and other contexts | Yes
HTTP method | GET
URL template | /api/FHIR/R4/QuestionnaireResponse/{ID}
Supports OAuth 2.0 | True
Supported user types | Backend Systems and Non-OAuth 2.0, Clinicians or Administrative Users, Patients
Performs scope validation | False
Source | https://fhir.epic.com/Specifications?api=11394

Description

Use this API to retrieve a specific QuestionnaireResponse (Prior Auth) resource. This resource represents structured clinical information submitted by a provider in support of a prior authorization request, typically generated through the Da Vinci DTR workflow. The QuestionnaireResponse contains structured answers, attachments, and context extensions linking it to the related authorization, encounter, order, and coverage.

When used as part of the CMS Payer-to-Payer API, only supporting information for approved prior authorizations is returned. In other interoperability scenarios, supporting information for both approved and denied prior authorizations can be returned.

Request parameters

Name | Type | Optional | Array | Cardinality | Description
ID | token | Required | | | QuestionnaireResponse FHIR ID.

Response elements

Name | Type | Optional | Array | Cardinality | Description
QuestionnaireResponse (R4) | Resource | | | | An instance of the R4 QuestionnaireResponse FHIR resource.
QuestionnaireResponse (R4).authored | dateTime | | | 1..1 | Identifies when this version of the answer set was created. Changes whenever the answers are updated.
QuestionnaireResponse (R4).extension | Extension | | Yes | 3..* | Extensions supported: extension:context - Associates the QuestionnaireResponse with its related clinical context (such as the specific encounter, visit, service line, or order and the relevant coverage). This allows consumers to locate DTR responses that belong to a particular Order/Encounter/Appointment for a given insurance coverage. extension:intendedUse - Indicates how the information is to be used with respect to the associated orders or records. This extension is always set to "withpa".
QuestionnaireResponse (R4).id | id | | | 1..1 | The QuestionnaireResponse FHIR ID.
QuestionnaireResponse (R4).item | BackboneElement | | Yes | 1..* | A group or question item from the original questionnaire for which answers are provided.
QuestionnaireResponse (R4).item.answer | BackboneElement | | Yes | 0..* | The answer (or one of the answers) provided by the respondent to the question. Supports the following value types: valueBoolean, valueDate, valueDateTime, valueTime, valueDecimal, valueInteger, valueString, valueCoding, valueUri, and valueQuantity.
QuestionnaireResponse (R4).item.answer.extension | Extension | | Yes | 1..* | Extensions supported: extension:origin - Identifies the origin of the information in the answer and how it came to exist.
QuestionnaireResponse (R4).item.item | BackboneElement | | Yes | 0..* | Questions or sub-groups nested beneath a question or group.
QuestionnaireResponse (R4).item.linkId | string | | | 1..1 | The item from the Questionnaire that corresponds to this item in the QuestionnaireResponse resource.
QuestionnaireResponse (R4).questionnaire | canonical | | | 1..1 | The Questionnaire that defines and organizes the questions for which answers are being provided.

QuestionnaireResponse (R4).status | code | | | 1..1 | The position of the questionnaire response within its overall lifecycle.
QuestionnaireResponse (R4).subject | Reference | | | 1..1 | The subject of the questionnaire response. This is the patient to whom the answers apply.

Sample request

```
GET https://hostname/instance/api/FHIR/R4/QuestionnaireResponse/f1XYzEpWgDYgg4zfkYGY4YQ4
```

Sample response


```
{
  "resourceType": "QuestionnaireResponse",
  "id": "f1XYzEpWgDYgg4zfkYGY4YQ4",
  "extension": [
    {
      "valueReference": {
        "reference": "Coverage/eI8-ieLKHpZPX0H6unDAPBpEnUHuQIb4SO6Dp4zWhszi9IRMaIp25ljQo5oaqchyV3",
        "type": "Coverage"
      },
      "url": "http://hl7.org/fhir/us/davinci-dtr/StructureDefinition/qr-coverage"
    },
    {
      "valueCodeableConcept": {
        "coding": [
          {
            "system": "http://hl7.org/fhir/us/davinci-crd/CodeSystem/temp",
            "code": "withpa",
            "display": "Include in prior authorization"
          }
        ]
      },
      "url": "http://hl7.org/fhir/us/davinci-dtr/StructureDefinition/intendedUse"
    }
  ],
  "questionnaire": "urn:uuid:ee341f56-a391-11f0-9c67-0050568b0c08|5830759513",
  "status": "stopped",
  "subject": {
    "reference": "Patient/eMyQoQ6-E-PRP3Fkge4K0mA3",
    "display": "Patient, Test"
  },
  "authored": "2025-11-04T23:33:56Z",
  "item": [
    {
      "linkId": "urn:uuid:ee34584a-a391-11f0-9c67-0050568b0c08",
      "item": [
        {
          "linkId": "urn:uuid:ee34f4ab-a391-11f0-9c67-0050568b0c08",
          "answer": [
            {
              "extension": [
                {
                  "extension": [
                    {
                      "extension": [
                        {
                          "valueReference": {
                            "reference": "Practitioner/elSn0CKm.qT02sNQFv6ysPQ3",
                            "type": "Practitioner",
                            "display": "Test Practitioner"
                          },
                          "url": "practitioner"
                        }
                      ],
                      "url": "author"
                    },
                    {
                      "valueCode": "manual",
                      "url": "source"
                    }
                  ],
                  "url": "http://hl7.org/fhir/us/davinci-dtr/StructureDefinition/information-origin"
                }
              ],
              "valueBoolean": true
            }
          ]
        },
        {
          "linkId": "urn:uuid:ee36574e-a391-11f0-9c67-0050568b0c08",
          "answer": [
            {
              "extension": [
                {
                  "extension": [
                    {
                      "extension": [
                        {
                          "valueReference": {
                            "reference": "Practitioner/elSn0CKm.qT02sNQFv6ysPQ3",
```

```
                        "type": "Practitioner",
                        "display": "Test Practitioner"
                      },
                      "url": "practitioner"
                    }
                  ],
                  "url": "author"
                },
                {
                  "valueCode": "manual",
                  "url": "source"
                }
              ],
              "url": "http://hl7.org/fhir/us/davinci-dtr/StructureDefinition/information-origin"
            }
          ],
          "valueBoolean": true
        }
      ]
    }
  ]
}
```