Epic-FHIR — API category: Utility (sections 35 – 35.2.5)

Source: Epic on FHIR (fhir.epic.com) documentation, mirrored 2026-11. Text-only edition for AI ingestion (NotebookLM); pages follow the source order (its table of contents when one exists).

35 API category: Utility

File: site/apis/35-Utility/index.html

R4 (4)

API | Method | URL template | Type
Device.$auxiliary-function (Auxiliary Function Notification) (R4) | POST | /api/FHIR/R4/Device/$auxiliary-function?timestamp={timestamp}`Parameters*** | Industry-Standard
Provenance.Read (R4) | GET | /api/FHIR/R4/Provenance/{ID} | USCDI
Task.Read (Auxiliary Function Notification) (R4) | GET | /api/FHIR/R4/Task/{ID} | Industry-Standard
Task.Search (Auxiliary Function Notification) (R4) | GET | /api/FHIR/R4/Task?code={code}&encounter={encounter}&focus={focus}&patient={patient}&status={status}&subject={subject}&_count={_count}&_id={_id}&_include={_include}&_revinclude={_revinclude} | Industry-Standard

Non-FHIR (5)

API | Method | URL template | Type
AssignPatientIdentifier | POST | api/epic/2012/EMPI/Patient/ASSIGNPATIENTIDENTIFIER/PatientIdentifier | Epic Public
ReceiveCommunication | POST | api/epic/2015/Common/Utility/RECEIVECOMMUNICATION/ReceiveCommunication | Epic Public
ReceiveCommunication2 | POST | /api/epic/2020/Common/Utility/RECEIVECOMMUNICATION2/ReceiveCommunication2 | Epic Public
ReceiveCommunication3 | POST | api/epic/2023/Common/Utility/RECEIVECOMMUNICATION3/ReceiveCommunication3 | Epic Public
StoreCallID | POST | /api/epic/2018/Common/Utility/STORECALLID/StoreCallID | Epic Public

35.1 Utility: R4

File: site/apis/35-Utility/1-R4/index.html

* Device.$auxiliary-function (Auxiliary Function Notification) (R4)
* Provenance.Read (R4)
* Task.Read (Auxiliary Function Notification) (R4)
* Task.Search (Auxiliary Function Notification) (R4)

35.1.1 Device.$auxiliary-function (Auxiliary Function Notification) (R4)

File: site/apis/35-Utility/1-R4/11352-Device-auxiliary-function-Auxiliary-Function-Notification-R4.html
Epic API ID | 11352
FHIR version | R4
Categories | Utility
API type | Industry-Standard
USCDI | No
Keywords | staff duress;device
HTTP method | POST
URL template | /api/FHIR/R4/Device/$auxiliary-function?timestamp={timestamp}`Parameters***
Supports OAuth 2.0 | True
Supported user types | Backend Systems and Non-OAuth 2.0, Clinicians or Administrative Users
Performs scope validation | False
Source | https://fhir.epic.com/Specifications?api=11352

Description

This web service generates a push notification that represents a task triggered from an auxiliary function.

This is currently exclusive to staff duress push notifications, which are created when a user presses a panic button on a Real-Time Location System (RTLS) device and are sent to configured groups of users. The notification tracks who has received or responded to the notification.

Staff duress push notifications require third-party RTLS Badges integration with Epic.

Request parameters

Name | Type | Optional | Array | Cardinality | Description
Parameters (R4) | Parameters | | | | Parameters resource comprising the request data.
Parameters (R4).parameter (device) (also: parameter (device)) | BackboneElement | | Yes | 1..1 | Represents the device parameter for Device.$auxiliary-function (R4) request.
Parameters (R4).parameter (device).name | string | | | 1..1 | Set to device
Parameters (R4).parameter (device).resource | ResourceContainer | | | 1..1 | Contains the Device FHIR resource. Specify resource.resourceType = Device

Parameters (R4).parameter (device).resource.Device | Resource | | | 1..1 | The Device FHIR resource which is used to identify an RTLS badge device.

Parameters (R4).parameter (device).resource.Device.identifier | Identifier | | Yes | 1..1 | The RTLS device's identifier.

Parameters (R4).parameter (device).resource.Device.identifier.system | String | | | 1..1 | The identifier's system value. Valid system values include: Identity ID OID. This system value is highly configurable at each Epic organization.

Parameters (R4).parameter (device).resource.Device.identifier.value | String | | | 1..1 | The RTLS device identifier.

Parameters (R4).parameter (event) (also: parameter (event)) | BackboneElement | | Yes | 1..1 | Represents the event parameter for Device.$auxiliary-function (R4) request.

Parameters (R4).parameter (event).name | string | | | 1..1 | Set to event

Parameters (R4).parameter (event).valueCoding | Coding | | | 1..1 | The event of the auxiliary function. This determines what type of auxiliary function should be performed.

Parameters (R4).parameter (event).valueCoding.code | String | | | 1..1 | The code associated with the event. Currently supports "staff-duress".

Parameters (R4).parameter (event).valueCoding.display | String | | | 0..1 | The display name of the event code. Currently supports "Staff Duress" for "staff-duress".

Parameters (R4).parameter (event).valueCoding.system | String | | | 1..1 | The coding's system value. Set to: https://hl7.org/FHIR/R4/rtls/CodeSystem/rtlsMessageEvents

Parameters (R4).parameter (location) (also: parameter (location)) | BackboneElement | | Yes | 1..1 | Represents the location parameter for Device.$auxiliary-function (R4) request.

Parameters (R4).parameter (location).name | string | | | 1..1 | Set to location

Parameters (R4).parameter (location).resource | ResourceContainer | | | 1..1 | Contains the Location FHIR resource. Specify resource.resourceType = Location

Parameters (R4).parameter (location).resource.Location | Resource | | | 1..1 | The Location FHIR resource which is used to identify an RTLS location.

Parameters (R4).parameter (location).resource.Location.identifier | Identifier | | Yes | 1..1 | The RTLS location's identifier.

Parameters (R4).parameter (location).resource.Location.identifier.system | String | | | 1..1 | The identifier's system value. This is an OID unique to each Epic organization.

Parameters (R4).parameter (location).resource.Location.identifier.value | String | | | 1..1 | The RTLS location's identifier.

Parameters (R4).parameter (timestamp) (also: parameter (timestamp)) | BackboneElement | | Yes | 1..1 | Represents the timestamp parameter for Device.$auxiliary-function (R4) request.

Parameters (R4).parameter (timestamp).name | string | | | 1..1 | Set to timestamp

Parameters (R4).parameter (timestamp).valueInstant | String | | | 1..1 | The time the auxiliary function on the RTLS device was performed.

Response elements

Name | Type | Optional | Array | Cardinality | Description

Parameters (R4) | Parameters | | | | Parameters resource comprising the request data.

Parameters (R4).parameter (outcome) (also: parameter (outcome)) | BackboneElement | | Yes | 0..1 | Represents the outcome parameter for Device.$auxiliary-function (R4) response.

Parameters (R4).parameter (outcome).name | string | | | 1..1 | Set to outcome

Parameters (R4).parameter (outcome).resource | ResourceContainer | | | 1..1 | Contains the OperationOutcome FHIR resource. Specify resource.resourceType = OperationOutcome

Parameters (R4).parameter (outcome).resource.OperationOutcome | OperationOutcome | | | 1..1 | The OperationOutcome FHIR resource which is used to send back any warnings associated with the operation.

Parameters (R4).parameter (outcome).resource.OperationOutcome.issue | Issue | | Yes | 1..* | Information about an error associated with the FHIR operation.

Parameters (R4).parameter (outcome).resource.OperationOutcome.issue.code | String | | | 1..1 | Error or warning code associated with the issue.

Parameters (R4).parameter (outcome).resource.OperationOutcome.issue.details | CodeableConcept | | | 1..1 | Additional details about the error

Parameters (R4).parameter (outcome).resource.OperationOutcome.issue.details.coding | Coding | | Yes | 1..* | The code of the OperationOutcome.

Parameters (R4).parameter (outcome).resource.OperationOutcome.issue.details.coding.code | String | | | 1..1 | The code of the OperationOutcome.

Parameters (R4).parameter (outcome).resource.OperationOutcome.issue.details.coding.display | String | | | 1..1 | The display name of the OperationOutcome code

Parameters (R4).parameter (outcome).resource.OperationOutcome.issue.details.coding.system | String | | | 1..1 | The coding's system value. Set to: http://terminology.hl7.org/CodeSystem/operation-outcome

Parameters (R4).parameter (outcome).resource.OperationOutcome.issue.details.text | String | | | 1..1 | Plain text representation of the error details.

Parameters (R4).parameter (outcome).resource.OperationOutcome.issue.diagnostics | String | | | 1..1 | Additional diagnostic information about the issue.

Parameters (R4).parameter (outcome).resource.OperationOutcome.issue.expression | String | | Yes | 1..* | FHIRPath of element(s) related to the issue

Parameters (R4).parameter (outcome).resource.OperationOutcome.issue.location | String | | Yes | 1..* | Path of element(s) related to issue.

Parameters (R4).parameter (outcome).resource.OperationOutcome.issue.severity | String | | | 1..1 | The severity of the issue.

Parameters (R4).parameter (task) (also: parameter (task)) | BackboneElement | | Yes | 0..1 | Represents the task parameter for Device.$auxiliary-function (R4) response.

Parameters (R4).parameter (task).name | string | | | 1..1 | Set to task

Parameters (R4).parameter (task).resource | ResourceContainer | | | 1..1 | Contains the Task FHIR resource. Specify resource.resourceType = Task

Parameters (R4).parameter (task).resource.Task | Resource | | | 1..1 | The Task FHIR resource which is used to identify a push notification.

Parameters (R4).parameter (task).resource.Task.code | CodeableConcept | | | 1..1 | The type of Task.

Parameters (R4).parameter (task).resource.Task.code.text | String | | | 1..1 | Plaintext representation of the code. Currently only "Staff Duress" is supported.

Parameters (R4).parameter (task).resource.Task.id | id | | | 1..1 | A unique identifier for this Task.

Parameters (R4).parameter (task).resource.Task.intent | code | | | 1..1 | The intent of the Task. Currently only "unknown" is used.

Parameters (R4).parameter (task).resource.Task.priority | code | | | 1..1 | The Task's priority. Currently supports: routine urgent asap stat

Parameters (R4).parameter (task).resource.Task.status | code | | | 1..1 | The status of the Task. The status is determined by considering both the delivery status and the actions taken on the Task. Currently supported: requested - The Task notification has been sent but not delivered to recipients. received - At least one user has been delivered the Task notification, and the notification has not been accepted or rejected yet. accepted - At least one user has marked an affirmative action on the Task notification to accept the request. rejected - All users have marked a negative action

on the Task notification to decline the request.

Sample request

```
POST https://hostname/instance/api/FHIR/R4/Device/$auxiliary-function
{
  "resourceType": "Parameters",
  "parameter": [
    {
      "name": "event",
      "valueCoding": {
        "system": "http://hl7.org/FHIR/R4/rtls/CodeSystem/rtlsMessageEvents",
        "code": "staff-duress",
        "display": "Staff Duress"
      }
    },
    {
      "name": "location",
      "resource": {
        "resourceType": "Location",
        "identifier": [
          {
            "value": "STH-3F-RM221",
            "system": "urn:oid:1.2.840.114350.1.13.861.1.7.3.657370.210"
          }
        ]
      }
    },
    {
      "name": "device",
      "resource": {
        "resourceType": "Device",
        "identifier": [
          {
            "value": "0005A1C7B3",
            "system": "urn:oid:1.2.840.114350.1.13.861.1.7.5.737384.1001"
          }
        ]
      }
    },
    {
      "name": "timestamp",
      "valueInstant": "2025-05-24T13:00:00-05:00"
    }
  ]
}
```

Sample response

```
{
  "resourceType": "Parameters",
  "parameter": [
    {
      "name": "task",
      "resource": {
        "resourceType": "Task",
        "id": "111222333",
        "intent": "unknown",
        "status": "received",
        "priority": "stat",
        "code": {
          "text": "Staff Duress"
        }
      }
    }
  ]
}
```

35.1.2 Provenance.Read (R4)

File: site/apis/35-Utility/1-R4/10180-Provenance-Read-R4.html
Epic API ID | 10180
FHIR version | R4
Categories | Utility
API type | USCDI
A la carte | Industry-Standard Level 1 API
USCDI | Yes
Available in inpatient and other contexts | Yes
ONC certification products | EpicCare Ambulatory Base, EpicCare Inpatient Base
ONC certification versions | August 2021
HTTP method | GET
URL template | /api/FHIR/R4/Provenance/{ID}
Supports OAuth 2.0 | True
Supported user types | Backend Systems and Non-OAuth 2.0, Clinicians or Administrative Users, Patients

Performs scope validation | False
Source | https://fhir.epic.com/Specifications?api=10180

Description

The Provenance resource returns contextual metadata about the origin of a different resource, such as who created or transmitted data about the target resource.

Typically, provenance data is requested as part of the search interaction for a different resource, as described in the FHIR Search Parameters documentation.

Request parameters

Name | Type | Optional | Array | Cardinality | Description
ID | String | False | | | Provenance FHIR ID.

Response elements

Name | Type | Optional | Array | Cardinality | Description
Provenance | Provenance | False
Provenance.agent | Agent | False | Yes | | Actors involved, such as the author and transmitter.
Provenance.agent.onBehalfOf | Reference | True | | | Who the actor is representing.
Provenance.agent.type | CodeableConcept | True | | | How the actor participated.
Provenance.agent.who | Reference | False | | | Who participated.
Provenance.id | String | False | | | Provenance FHIR ID.
Provenance.recorded | String | False | | | Timestamp that the activity was recorded or updated.
Provenance.target | Reference | False | Yes | | The resource that this provenance describes.

Sample request

```
https://hostname/instance/api/FHIR/R4/Provenance/evEEcicwDTY2yB6W1wcnUdRomP9lL.s5Mm8T.Z.NEY6c3
```

Sample response


```
{
  "resourceType": "Provenance",
  "id": "evEEcicwDTY2yB6W1wcnUdRomP9lL.s5Mm8T.Z.NEY6c3",
  "target": [
    {
      "reference": "CareTeam/ebGqfgpibCSwCNi5D0-A7Dg3"
    }
  ],
  "recorded": "2021-07-30T20:29:02Z",
  "agent": [
    {
      "type": {
        "coding": [
          {
            "system": "http://terminology.hl7.org/CodeSystem/provenance-participant-type",
            "code": "author",
            "display": "Author"
          }
        ],
        "text": "Author"
      },
      "who": {
        "reference": "Practitioner/eMqwQScPw6FOlWzs-BLtrZg3",
        "display": "John Johnson, MD"
      },
      "onBehalfOf": {
        "display": "Example Organization"
      }
    },
    {
      "type": {
        "coding": [
          {
            "system": "http://hl7.org/fhir/us/core/CodeSystem/us-core-provenance-participant-type",
            "code": "transmitter",
            "display": "Transmitter"
          }
        ],
        "text": "Transmitter"
      },
      "who": {
        "display": "Example Organization"
      }
    }
  ]
}
```


35.1.3 Task.Read (Auxiliary Function Notification) (R4)

File: site/apis/35-Utility/1-R4/11404-Task-Read-Auxiliary-Function-Notification-R4.html
Epic API ID | 11404
FHIR version | R4
Categories | Utility
API type | Industry-Standard
USCDI | No
HTTP method | GET
URL template | /api/FHIR/R4/Task/{ID}
Supports OAuth 2.0 | True
Supported user types | Backend Systems and Non-OAuth 2.0, Clinicians or Administrative Users
Performs scope validation | False
Source | https://fhir.epic.com/Specifications?api=11404

Description

This web service retrieves information relating to a push notification for a task generated from an auxiliary function.

For example, when a staff member presses a panic button on a real-time location system (RTLS) device, Epic automatically sends a staff duress push notification to designated groups of users, such as security teams or charge nurses. The notification tracks the status of who has received or responded to the notification.

The system can then communicate to the staff member that help is on the way.

This resource can be queried by a task ID.

There are no alternatives for this web service.

Request parameters

Name | Type | Optional | Array | Cardinality | Description
ID | token | Required | | | The Task FHIR ID.

Response elements

Name | Type | Optional | Array | Cardinality | Description
Task (R4) | Resource | | | | A single instance of an R4 Task FHIR resource.
Task (R4).code | CodeableConcept | | | 1..1 | The type of Task.
Task (R4).code.text | String | | | 1..1 | Plaintext representation of the code. Currently only "Staff Duress" is supported.
Task (R4).id | id | | | 1..1 | A unique identifier for this Task.
Task (R4).intent | code | | | 1..1 | The intent of the Task. Currently only "unknown" is used.
Task (R4).priority | code | | | 1..1 | The Task's priority. Currently supports: routine urgent asap stat
Task (R4).status | code | | | 1..1 | The status of the Task. The status is determined by considering both the delivery status and the actions taken on the Task. Currently supported: requested - The Task notification has been sent but not delivered to recipients. received - At least one user has been delivered the Task notification, and the notification has not been accepted or rejected yet. accepted - At least one user has marked an affirmative action on the Task notification to accept the request. rejected - All users have marked a negative action on the Task notification to decline the request.

Sample request

```
GET https://hostname/instance/api/FHIR/R4/Task/fhvDXvZ4r5W0lEZmAO8CDkA4
```

Sample response

```
{
  "resourceType": "Task",
  "id": "fhvDXvZ4r5W0lEZmAO8CDkA4",
  "status": "accepted",
  "intent": "unknown",
  "priority": "stat",
  "code": {
    "text": "Staff Duress"
  }
}
```

35.1.4 Task.Search (Auxiliary Function Notification) (R4)

File: site/apis/35-Utility/1-R4/11403-Task-Search-Auxiliary-Function-Notification-R4.html
Epic API ID | 11403
FHIR version | R4
Categories | Utility
API type | Industry-Standard
USCDI | No
HTTP method | GET
URL template | /api/FHIR/R4/Task?code={code}&encounter={encounter}&focus={focus}&patient={patient}&status={status}&subject={subject}&_count={_count}&_id={_id}&_include={_include}&_revinclude={_revinclude}
Supports OAuth 2.0 | True
Supported user types | Backend Systems and Non-OAuth 2.0, Clinicians or Administrative Users
Performs scope validation | False
Source | https://fhir.epic.com/Specifications?api=11403

Description

This web service retrieves information relating to a push notification for a task generated from an auxiliary function.

For example, when a staff member presses a panic button on a real-time location system (RTLS) device, Epic automatically sends a staff duress push notification to designated groups of users, such as security teams or charge nurses. The notification tracks the status of who has received or responded to the notification.

The system can then communicate to the staff member that help is on the way.

This API supports only the _id parameter, so it is similar to a Task.Read.

There are no alternatives for this web service.

Request parameters

Name | Type | Optional | Array | Cardinality | Description
_count | number | Optional | Yes | | Number of results per page.
_id | token | Optional | Yes | | FHIR resource IDs for the desired resources. Can be used in combination with _count, _include, and _revInclude. All others will be ignored.
_include | string | Optional | Yes | | Used to indicate which referenced resources to include in the search bundle.
_revinclude | string | Optional | Yes | | Used to include Provenance or AuditEvent resources that refer to search results, when available.

Response elements

Name | Type | Optional | Array | Cardinality | Description
Task (R4) | Resource | | | | A single instance of an R4 Task FHIR resource.
Task (R4).code | CodeableConcept | | | 1..1 | The type of Task.
Task (R4).code.text | String | | | 1..1 | Plaintext representation of the code. Currently only "Staff Duress" is supported.
Task (R4).id | id | | | 1..1 | A unique identifier for this Task.
Task (R4).intent | code | | | 1..1 | The intent of the Task. Currently only "unknown" is used.
Task (R4).priority | code | | | 1..1 | The Task's priority. Currently supports: routine urgent asap stat
Task (R4).status | code | | | 1..1 | The status of the Task. The status is determined by considering both the delivery status and the actions taken on the Task. Currently supported: requested - The Task notification has been sent but not delivered to recipients. received - At least one user has been delivered the Task notification, and the notification has not been accepted or rejected yet. accepted - At least one user has marked an affirmative action on the Task notification to accept the request. rejected - All users have marked a negative action on the Task notification to decline the request.

Sample request

```
GET https://hostname/instance/api/FHIR/R4/Task?_ID=fhvDXvZ4r5W0lEZmAO8CDkA4
```

Sample response

```
{
  "resourceType": "Bundle",
  "type": "searchset",
  "total": 1,
  "link": [
    {
      "relation": "self",
      "url": "https://hostname/instance/api/FHIR/R4/Task?_ID=fhvDXvZ4r5W0lEZmAO8CDkA4"
    }
  ],
  "entry": [
    {
      "link": [
        {
          "relation": "self",
          "url": "https://hostname/instance/api/FHIR/R4/Task/fhvDXvZ4r5W0lEZmAO8CDkA4"
        }
      ],
      "fullUrl": "https://hostname/instance/api/FHIR/R4/Task/fhvDXvZ4r5W0lEZmAO8CDkA4",
      "resource": {
        "resourceType": "Task",
        "id": "fhvDXvZ4r5W0lEZmAO8CDkA4",
        "status": "accepted",
        "intent": "unknown",
        "priority": "stat",
        "code": {
          "text": "Staff Duress"
        }
      },
      "search": {
        "mode": "match"
      }
    }
  ]
}
```

35.2 Utility: Non-FHIR

File: site/apis/35-Utility/2-Non-FHIR/index.html

* AssignPatientIdentifier
* ReceiveCommunication
* ReceiveCommunication2
* ReceiveCommunication3
* StoreCallID

35.2.1 AssignPatientIdentifier

File: site/apis/35-Utility/2-Non-FHIR/149-AssignPatientIdentifier.html
Epic API ID | 149
FHIR version | Non-FHIR
Categories | Utility
API type | Epic Public
API group | EMPI Group
USCDI | No
HTTP method | POST
URL template | api/epic/2012/EMPI/Patient/ASSIGNPATIENTIDENTIFIER/PatientIdentifier
Supports OAuth 2.0 | False
Supported user types | Backend Systems and Non-OAuth 2.0
Performs scope validation | False
SOAP namespace | urn:Epic-com:EMPI.2012.Services.Patient
WSDL | Epic.EMPI.GeneratedServices/Patient.svc?wsdl
Source | https://fhir.epic.com/Specifications?api=149

Request parameters

Name | Type | Optional | Array | Cardinality | Description
AssignMRN | String | If set, GenerateNewMRN should not be true.
AssignMRNType | String | False
GenerateNewMRN | Boolean | If not true, AssignMRN must be set.
PatientID | String | False
PatientIDType | String | True
UserID | String | False
UserIDType | String | True

Response elements

Name | Type | Optional | Array | Cardinality | Description
Identifiers | PatientIdentifier | False | Yes
Identifiers.ID | String | False
Identifiers.IDType | String | False
NewMRN | PatientIdentifier | False
NewMRN.ID | String | False
NewMRN.IDType | String | False

Errors

Code | Severity | Description | Example
INVALID-PATIENT-ID-TYPE | None | | Patient ID type is not supported.
NO-PATIENT-ID | None | | Patient ID is required but was not provided.
NO-PATIENT-FOUND | None | | No patient was found with the provided ID and ID type.
INVALID-USER-ID-TYPE | None | | User ID type is not supported.
NO-USER-ID | None | | User ID is required but was not provided.
NO-USER-FOUND | None | | No user was found with the provided ID and ID type.
NO-ASSIGN-ID-TYPE | None | | Assign ID type is required but was not provided.
INVALID-ASSIGN-ID-TYPE | None | | Assign ID type is not supported.
NO-ASSIGN-ID | None | | Assign ID is required when not generating an ID, but was not provided.
ID-ASSIGNMENT-FAILED | None | | The ID could not be assigned: <error code>
ID-GENERATION-FAILED | None | | The ID could not be generated or assigned: <error code>
ASSIGN-REQUEST-CONFLICT | None | | An assign ID was provided and the generate flag was set.
NOT-LICENSED | None | | Patient ID type is not supported.

Sample request

```
<AssignPatientIdentifier xmlns="urn:Epic-com:EMPI.2012.Services.Patient">
  <PatientIDType>EPI</PatientIDType>
  <PatientID>767662</PatientID>
  <UserIDType>INTERNAL</UserIDType>
  <UserID>10017</UserID>
  <AssignMRNType>HOP</AssignMRNType>
  <AssignMRN>HOP2035</AssignMRN>
  <GenerateNewMRN>false</GenerateNewMRN>
```

```
</AssignPatientIdentifier>
```

Sample response

```
<AssignPatientIdentifierResult xmlns="urn:Epic-com:EMPI.2012.Services.Patient">
  <Identifiers>
    <PatientIdentifier>
      <ID>767662</ID>
      <IDType>EPI</IDType>
    </PatientIdentifier>
    <PatientIdentifier>
      <ID>ENR343</ID>
      <IDType>ENR</IDType>
    </PatientIdentifier>
    <PatientIdentifier>
      <ID>HOP2035</ID>
      <IDType>HOP</IDType>
    </PatientIdentifier>
  </Identifiers>
  <NewMRN>
    <ID>HOP2035</ID>
    <IDType>HOP</IDType>
  </NewMRN>
</AssignPatientIdentifierResult>
```

35.2.2 ReceiveCommunication

File: site/apis/35-Utility/2-Non-FHIR/137-ReceiveCommunication.html
Epic API ID | 137
FHIR version | Non-FHIR
Categories | Utility
API type | Epic Public
API group | Computer-Telephony Integration (CTI) Group
USCDI | No
HTTP method | POST
URL template | api/epic/2015/Common/Utility/RECEIVECOMMUNICATION/ReceiveCommunication
Supports OAuth 2.0 | True
Supported user types | Backend Systems and Non-OAuth 2.0, Clinicians or Administrative Users
Performs scope validation | False
SOAP namespace | urn:Epic-com:Common.2015.Services.Utility
WSDL | Epic.Common.GeneratedServices/Utility.svc?wsdl
Source | https://fhir.epic.com/Specifications?api=137

Remarks

This API creates communication tracking (CAL) records.

If PatientID is used, the screen pop is directly to the patient record. If PatientInformation/PatientInformationType and/or PhoneNumber is used, the user is shown a list of matching patients to select from before the desired screen is popped. If no match is found, the user is notified and taken to the patient lookup screen.

Request parameters

Name | Type | Optional | Array | Cardinality | Description
CallID | String | True
CommunicationType | String | True
ContactType | String | True
Context | String | True
PatientID | IDType | One of PatientInformationType/PatientInformation, PhoneNumber, or PatientID is required. | | | A generic identifier.
PatientID.ID | String | False | | | The identifier for this resource.
PatientID.Type | String | False | | | The type of identifier.
PatientInformation | String | One of PatientInformationType/PatientInformation, PhoneNumber, or PatientID is required.
PatientInformationType | String | One of PatientInformationType/PatientInformation, PhoneNumber, or PatientID is required.
PhoneNumber | String | One of PatientInformationType/PatientInformation, PhoneNumber, or PatientID is required.
UserID | String | False
UserIDType | String | True

Errors

Code | Severity | Description | Example
NOT-LICENSED | None | | Required license is not activated.
AUTHENTICATION-FAILED | None | | Username token is not present in the request.
INVALID-CONTEXT | None | | The context given was not valid.
NO-USER-ID | None | | User ID is required but not provided.
NO-USER-ID-TYPE | None | | User ID type is required but not provided.
INVALID-USER-ID | None | | The user ID does not match the user provided with the OAuth token.
INVALID-USER-ID-TYPE | None | | User ID type is invalid.
NO-USER-FOUND | None | | No user found with the provided ID and ID type.

INVALID-PATIENT-ID-TYPE | None | | Patient ID type is invalid.
NO-PATIENT-FOUND | None | | No patient was found with the provided ID and ID type.
NO-PATIENT-INFORMATION | None | | Neither the patient info nor the patient ID was given. Since the patient info will be sent to the client for the nurse to find the correct patient, we can't tell if the info given will end up finding a patient, just that it exists.
INVALID-PATIENT-INFORMATION | None | | Patient information type is not valid.
INVALID-CONTACT-TYPE | None | | Contact type is invalid.
INVALID-COMMUNICATION-TYPE | None | | Communication type is invalid.
ACTIVITY-NOT-SUPPORTED-READ-ONLY | None | | The specified activity is not supported in read-only environments.
EVENT-PUBLISH-FAILED | None | | The event failed to publish to Hyperspace.
NO-EXTENSION-FOUND | None | | Phone extension is not mapped.
INVALID-PHONE-NUMBER | None | | Phone extension is not mapped. The provided phone number is not a valid phone number.

Sample request

```
{
  "Context": "CRM",
  "UserID": "CCSS",
  "UserIDType": "External",
  "PatientInformationType": "SS",
  "PatientInformation": "111111111",
  "CallID": "1234567890",
  "ContactType": "Incoming",
  "CommunicationType": "Phone",
  "PhoneNumber": "9876543210",
  "PatientID": {
    "ID": "",
    "Type": ""
  }
}
```

Sample response

```
{}
```

35.2.3 ReceiveCommunication2

File: site/apis/35-Utility/2-Non-FHIR/10481-ReceiveCommunication2.html
Epic API ID | 10481
FHIR version | Non-FHIR
Categories | Utility
API type | Epic Public
API group | Computer-Telephony Integration (CTI) Group
USCDI | No
HTTP method | POST
URL template | /api/epic/2020/Common/Utility/RECEIVECOMMUNICATION2/ReceiveCommunication2
Supports OAuth 2.0 | True
Supported user types | Backend Systems and Non-OAuth 2.0, Clinicians or Administrative Users
Performs scope validation | False
Source | https://fhir.epic.com/Specifications?api=10481

Remarks

This API creates communication tracking (CAL) records.

If LookupType is set to Patient or Provider and if:

* LookupID is used, the screen pop is linked directly to the patient record.

* LookupInformation, LookupInformationType, or PhoneNumber is used, the user is shown a list of matching patients to select from before the desired screen is popped.

* No match is found, the user is notified and taken to the patient, provider, or vendor lookup screen.

Request parameters

Name | Type | Optional | Array | Cardinality | Description
CallID | String | True | | | The call ID in the phone system, to be used to link Epic data to the phone system.
CommunicationType | String | True | | | Similar to ContactType, this stores if the contact was a phone call, text message, and so on. It uses Phone call if a contact type or phone number is entered but this is not. Some of the available values are: Phone Email Web Text Message Email SMS (Email and Text Message)
ContactType | String | True | | | What type of contact is being made, such as incoming or outgoing? It matches on the abbreviation in that category. If the contact type is missing but communication type or phone number is entered, it uses incoming. If neither is entered, a contact isn't recorded, but the activity still opens. Available values are: Incoming Outgoing
Context | String | True
LookupID | IDType | True | | | A generic identifier.
LookupID.ID | String | False | | | The Lookup ID.
LookupID.Type | String | False | | | Record identifier's type (examples: Internal, External, ExternalKey, Name, CID, System Login, Alias, or Identity IIT identifier).
LookupInformation | String | True

LookupInformationType | String | True
LookupType | String | True
PhoneNumber | String | True
RecipientID | String | False
RecipientIDType | String | True

Response elements

Name | Type | Optional | Array | Cardinality | Description
EpicCallID | String | False | | | The ID of the relevant call ID record.

Errors

Code | Severity | Description | Example
NOT-LICENSED | None | | Required license is not activated.
INVALID-AUTHORIZATION-CONTEXT | None | | This service does not allow this type of authorizing user.
INVALID-CONTEXT | None | | The context given was not valid.
NO-USER-ID | None | | User ID not provided.
INVALID-USER-ID | None | | The user ID does not match the user provided with the OAuth token.
INVALID-USER-ID-TYPE | None | | Invalid ID type entered.
NO-USER-FOUND | None | | Either: <ul> User is not logged in. User not found.
INVALID-LOOKUP-TYPE | None | | Lookup type is invalid.
INVALID-LOOKUP-ID-TYPE | None | | Lookup ID type is invalid.
NO-RECORD-FOUND | None | | Record not found.
NO-LOOKUP-INFORMATION | None | | The required lookup information was not given.
INVALID-CONTACT-TYPE | None | | Contact type is invalid.
INVALID-COMMUNICATION-TYPE | None | | Communication type is invalid.
ACTIVITY-NOT-SUPPORTED-READ-ONLY | None | | The specified activity is not supported in read-only environments.
EVENT-PUBLISH-FAILED | None | | The event failed to publish to Hyperspace.
NO-EXTENSION-FOUND | None | | Phone extension is not mapped.
INVALID-PHONE-NUMBER | None | | The provided phone number is not a valid phone number
INVALID-LOOKUP-INFORMATION-TYPE | None | | Lookup information type is not valid.

Sample request

```
{
    "Context": "Scheduling",
    "LookupType": "Patient",
    "RecipientID": "29900",
    "RecipientIDType": "External",
    "CallID": "2990000",
    "ContactType": "Incoming",
    "CommunicationType": "Phone",
    "PhoneNumber": "540-999-9999"
    "LookupInformationType": "SS",
    "LookupInformation": "000218293"
    "LookupID": {
         "ID": "",
         "Type": ""
     }
```

Sample response

```
{
  "EpicCallID": "2990000"
}
```

35.2.4 ReceiveCommunication3

File: site/apis/35-Utility/2-Non-FHIR/10538-ReceiveCommunication3.html
Epic API ID | 10538
FHIR version | Non-FHIR
Categories | Utility
API type | Epic Public
API group | Computer-Telephony Integration (CTI) Group
USCDI | No
HTTP method | POST
URL template | api/epic/2023/Common/Utility/RECEIVECOMMUNICATION3/ReceiveCommunication3
Supports OAuth 2.0 | True
Supported user types | Backend Systems and Non-OAuth 2.0, Clinicians or Administrative Users
Performs scope validation | False
Source | https://fhir.epic.com/Specifications?api=10538

Description

This web service is used to launch an activity in Hyperspace when a user receives a phone call so that the user can immediately start documenting the call in the most relevant activity. This web service can take information, such as the

caller's MRN, birthdate, or phone number, as well as a context, and the phone number that was dialed. When a user receives a phone call, the phone system alerts the operational database with the information it has, so that a new communication tracking record is created and the appropriate activity is launched. If appropriate, the communication tracking record is then linked to the record launched by the activity. This web service can work with multiple phone systems.

If caller information is not provided, this web service can still be used to launch any activity.

On success, the communication tracking record ID is returned. If it fails, an error code is returned.

We recommend that you use this API instead of the ReceiveCommunication2 API because this API provides the option to work with multiple phone systems. For more details, review the PhoneSystemID parameter description. Additionally, this API captures the phone number that the caller dialed. For more details, review the DialedPhoneNumber parameter description.

Remarks

This API creates communication tracking (CAL) records.

If LookupType is set to Patient or Provider and if:

* LookupID is used, the screen pop is linked directly to the patient record.

* LookupInformation, LookupInformationType, or CallerPhoneNumber is used, the user is shown a list of matching patients to select from before the desired screen is popped.

* No match is found, the user is notified and taken to the patient, provider, or vendor lookup screen.

Request parameters

Name | Type | Optional | Array | Cardinality | Description
CallerPhoneNumber | String | True
CallID | String | True | | | The call ID in the phone system, to be used to link Epic data to the phone system.
CommunicationType | String | True | | | Similar to ContactType, this stores if the contact was a phone call, text message, and so on. It uses Phone call if a contact type or phone number is entered but this is not. Some of the available values are: Phone Email Web Text Message Email SMS (Email and Text Message)
ContactType | String | True | | | What type of contact is being made, such as incoming or outgoing? It matches on the abbreviation in that category. If the contact type is missing but communication type or phone number is entered, it uses incoming. If neither is entered, a contact isn't recorded, but the activity still opens. Available values are: Incoming Outgoing
Context | String | True
DialedPhoneNumber | String | True | | | The phone number that the caller dialed.
LookupID | IDType | True | | | The ID and ID Type of the record to look up.
LookupID.ID | String | False | | | The identifier for this resource.
LookupID.Type | String | False | | | Record identifier's type (examples: Internal, External, ExternalKey, Name, CID, System Login, Alias, or Identity IIT identifier).
LookupInformation | String | True | | | The information that goes with LookupInformationType. See the LookupInformationType field for information about how to format the data you provide here. If LookupInformation is provided, LookupInformationType must be provided as well.
LookupInformationType | String | True
LookupType | String | True | | | The type of lookup performed by the system, either Patient, Provider, or None. If a lookup type isn't specified, the default value is Patient for all contexts except when the context is mapped to the Transfer Center New Call activity. In that case, the default value is None.
PhoneSystemID | IDType | True | | | The ID and ID Type of the phone system that sent the web service message. If this is not populated, it will fall back on the phone system defined in Shared Configuration.
RecipientID | String | False | | | This is the user or workstation ID external phone system ID, which must be of the type specified in RecipientIDType.
RecipientIDType | String | True | | | The type of the ID specified in RecipientID. This is Phone by default. It can be other values as well, like Internal or System Login.

Response elements

Name | Type | Optional | Array | Cardinality | Description
EpicCallID | String | False | | | The ID of the relevant call.

Errors

Code | Severity | Description | Example
NOT-LICENSED | None | | Required license is not activated.
INVALID-AUTHORIZATION-CONTEXT | None | | This service does not allow this type of authorizing user.
INVALID-CONTEXT | None | | The context given was not valid.
NO-USER-ID | None | | User ID not provided
INVALID-USER-ID | None | | The user ID does not match the user provided with the OAuth token.
INVALID-USER-ID-TYPE | None | | Invalid ID type entered.
NO-USER-FOUND | None | | Either: <ul> User is not logged in. User not found.
INVALID-LOOKUP-TYPE | None | | Lookup type is invalid.
INVALID-LOOKUP-ID-TYPE | None | | Lookup ID type is invalid.
NO-RECORD-FOUND | None | | Record not found.
NO-LOOKUP-INFORMATION | None | | The required lookup information was not given.
INVALID-CONTACT-TYPE | None | | Contact type is invalid.
INVALID-COMMUNICATION-TYPE | None | | Communication type is invalid.
ACTIVITY-NOT-SUPPORTED-READ-ONLY | None | | The specified activity is not supported in read-only environments.
EVENT-PUBLISH-FAILED | None | | The event failed to publish to Hyperspace.

NO-EXTENSION-FOUND | None | | Phone extension is not mapped.
INVALID-PHONE-NUMBER | None | | The provided phone number is not a valid phone number
INVALID-LOOKUP-INFORMATION-TYPE | None | | Lookup information type is not valid.
INVALID-PHONE-SYSTEM-ID-TYPE | None | | The phone system ID type is invalid.
NO-PHONE-SYSTEM-FOUND | None | | The phone system ID is invalid.
INVALID-PHONE-SYSTEM-FOUND | None | | The phone system ID is an actual record ID, but the corresponding record isn't built correctly.

Sample request

```
{
  "Context": "Scheduling",
  "RecipientID": "29900",
  "RecipientIDType": "External",
  "LookupType": "Patient",
  "LookupInformationType": "SS",
  "LookupInformation": "000218293",
  "CallID": "2990000",
  "ContactType": "Incoming",
  "CommunicationType": "Phone",
  "CallerPhoneNumber": "540-999-9999",
  "DialedPhoneNumber": "608-555-0123",
  "LookupID": {
    "ID": "",
    "Type": ""
  },
  "PhoneSystemID": {
    "ID": "12345",
    "Type": "External"
  }
}
```

Sample response

```
{
  "EpicCallID": "2990000"
}
```

35.2.5 StoreCallID

File: site/apis/35-Utility/2-Non-FHIR/890-StoreCallID.html
Epic API ID | 890
FHIR version | Non-FHIR
Categories | Utility
API type | Epic Public
API group | Computer-Telephony Integration (CTI) Group
USCDI | No
HTTP method | POST
URL template | /api/epic/2018/Common/Utility/STORECALLID/StoreCallID
Supports OAuth 2.0 | True
Supported user types | Backend Systems and Non-OAuth 2.0
Performs scope validation | False
SOAP namespace | Common.2018.Services.Utility
WSDL | Epic.Common.GeneratedServices/Utility.svc?wsdl
Source | https://fhir.epic.com/Specifications?api=890

Request

Name | Type | Optional | Array | Description
EpicCallID | String | False | | The identifier of the CAL record (.1).
PhoneSystemCallID | String | False | | The external identifier of the CAL record.

Errors

Code | Severity | Description | Example
NO-EPIC-CALL-ID | None | | CAL ID wasn't passed in
NO-PHONE-CALL-ID | None | | Phone system call ID wasn't passed in
NO-CALL-FOUND | None | | CAL ID wasn't an actual ID, CAL record already had ID stored, or other reason CAL wasn't valid to update
LOCK-FAILED | None | | CAL record was locked

Sample request

```
<StoreCallID xmlns="urn:Epic-com:Common.2018.Services.Utility" xmlns:xsi="http://www.w3.org/2001/XMLSchema-instance">
  <EpicCallID xsi:nil="false">123456</EpicCallID>
  <PhoneSystemCallID xsi:nil="false">abcd</PhoneSystemCallID>
</StoreCallID>
```

Sample response

```
<StoreCallIDResponse xmlns="urn:Epic-com:Common.2018.Services.Utility">
  <StoreCallIDResult xmlns:i="http://www.w3.org/2001/XMLSchema-instance"/>
```

```
</StoreCallIDResponse>
```