Epic-FHIR — API category: Workflow Patient Management (sections 36 – 36.2.2)

Source: Epic on FHIR (fhir.epic.com) documentation, mirrored 2026-11. Text-only edition for AI ingestion (NotebookLM); pages follow the source order (its table of contents when one exists).

36 API category: Workflow Patient Management

File: site/apis/36-Workflow-Patient-Management/index.html

R4 (11)

API | Method | URL template | Type
CriteriaReview.Create (R4) | POST | /api/FHIR/R4/CriteriaReview | Epic Public
CriteriaReview.Read (R4) | GET | /api/FHIR/R4/CriteriaReview/{ID} | Epic Public
CriteriaReview.Update (R4) | PUT | /api/FHIR/R4/CriteriaReview | Epic Public
Encounter.Read (Outside Record) (R4) | GET | /api/FHIR/R4/Encounter/{ID} | USCDI
Encounter.Read (Patient Chart) (R4) | GET | /api/FHIR/R4/Encounter/{ID} | USCDI
Encounter.Search (Outside Record) (R4) | GET | /api/FHIR/R4/Encounter?class={class}&date={date}&identifier={identifier}&onlyscannable={onlyscannable}&patient={patient}&subject={subject}&_count={_count}&_id={_id} | USCDI
Encounter.Search (Patient Chart) (R4) | GET | /api/FHIR/R4/Encounter?class={class}&date={date}&identifier={identifier}&onlyscannable={onlyscannable}&patient={patient}&subject={subject} | USCDI
Patient.Create (Demographics) (R4) (described under Identification Individuals) | POST | api/FHIR/R4/Patient | Industry-Standard
ReviewCollection.Create (R4) | POST | /api/FHIR/R4/ReviewCollection | Epic Public
ReviewCollection.Read (R4) | GET | /api/FHIR/R4/ReviewCollection/{ID} | Epic Public
ReviewCollection.Update (R4) | PUT | api/FHIR/R4/ReviewCollection | Epic Public

STU3 (3)

API | Method | URL template | Type
Encounter.Read (Patient Chart) (STU3) | GET | api/FHIR/STU3/Encounter/{ID} | USCDI
Encounter.Search (Patient Chart) (STU3) | GET | /api/FHIR/STU3/Encounter?class={class}&date={date}&identifier={identifier}&patient={patient}&subject={subject} | USCDI
Patient.Create (STU3) (described under Identification Individuals) | POST | api/FHIR/STU3/Patient | Industry-Standard

Non-FHIR (1)

API | Method | URL template | Type
PatientCreate (2009) (described under Identification Individuals) | | | Epic Public

36.1 Workflow Patient Management: R4

File: site/apis/36-Workflow-Patient-Management/1-R4/index.html

* CriteriaReview.Create (R4)
* CriteriaReview.Read (R4)
* CriteriaReview.Update (R4)
* Encounter.Read (Outside Record) (R4)
* Encounter.Read (Patient Chart) (R4)
* Encounter.Search (Outside Record) (R4)
* Encounter.Search (Patient Chart) (R4)
* ReviewCollection.Create (R4)
* ReviewCollection.Read (R4)
* ReviewCollection.Update (R4)

36.1.1 CriteriaReview.Create (R4)

File: site/apis/36-Workflow-Patient-Management/1-R4/1009-CriteriaReview-Create-R4.html
Epic API ID | 1009
FHIR version | R4
Categories | Workflow Patient Management
API type | Epic Public
API group | Utilization Management integration
USCDI | No
HTTP method | POST
URL template | /api/FHIR/R4/CriteriaReview
Supports OAuth 2.0 | True
Supported user types | Backend Systems and Non-OAuth 2.0, Clinicians or Administrative Users

Performs scope validation | False
Source | https://fhir.epic.com/Specifications?api=1009

Description

This web service creates new criteria review records that contain patient data.

Request parameters

Name | Type | Optional | Array | Cardinality | Description
CriteriaReview | CriteriaReview | False
CriteriaReview.associatedAuthorization | Reference | True | | | A FHIR Claim reference. Authorization this review is associated with, if any.
CriteriaReview.associatedDate | String | True | | | Date for which the review was performed
CriteriaReview.completedDateTime | String | True | | | Instant at which this review was marked completed. Required if the review has a status of completed. Cannot be a future time and cannot be earlier than creationDateTime.
CriteriaReview.completionReviewer | Reference | True | | | User who marked this review as completed. Should be sent as a FHIR Practitioner reference. Must be a valid active user.
CriteriaReview.copyright | String | True | | | Copyright text that should be included with this review. Will appear at the bottom of the review's summary note.
CriteriaReview.creationDateTime | String | False | | | Instant at which this review was first created. Cannot be in the future.
CriteriaReview.creationReviewer | Reference | True | | | User who created this review. Should be sent as a FHIR Practitioner reference. Must be a valid active user. Should be sent as a FHIR Practitioner reference.
CriteriaReview.criterion | Criterion | True | Yes | | Criteria to support the review's recommendation.
CriteriaReview.criterion.associatedCode | Coding | True | Yes | | Codes (e.g. SNOMED) associated with this criterion.
CriteriaReview.criterion.backingInfo | BackingInfo | True | Yes | | Information that supports this criterion.
CriteriaReview.criterion.backingInfo.attachmentDateTime | String | False | | | Instant that this backing information was attached to the criterion.
CriteriaReview.criterion.backingInfo.valueAnnotation | Annotation | False | | | Note or annotation details.
CriteriaReview.criterion.backingInfo.valueAnnotation.authorReference | Reference | False | | | A FHIR reference.
CriteriaReview.criterion.backingInfo.valueAnnotation.authorReference.reference | String | False
CriteriaReview.criterion.backingInfo.valueAnnotation.text | String | False
CriteriaReview.criterion.backingInfo.valueAnnotation.time | String | False
CriteriaReview.criterion.criterionEvidenceString | String | True | | | Evidence that this criterion is a valid measure to use for this criteria review. This field is an array.
CriteriaReview.criterion.criterionID | Identifier | True | | | Identifier of this criterion within the criteria review system that created the review.
CriteriaReview.criterion.isSatisfied | Boolean | False | | | Whether or not this criterion is satisfied.
CriteriaReview.criterion.subCriteriaCount | Int32 | True | | | If criterion.subCriteriaLogic is count, count-or-more, or count-or-fewer, what to use as count.
CriteriaReview.criterion.subCriteriaLogic | String | True | | | One of the following: all any none count count-or-more count-or-fewer How sub-criteria elements must be satisfied in order for criterion.isSatisfied to be true.
CriteriaReview.criterion.text | String | False | | | Textual representation of the criterion.
CriteriaReview.dayOfCare | Int32 | True | | | If this is a progression review, the day of the progression course expected given patient's admission date and associatedDate. Must be a positive integer.
CriteriaReview.dayOfProgressionPlan | Int32 | True | | | If this is a progression review, the day of the progression course this review represents. Must be a positive integer.
CriteriaReview.diagnosisCode | Coding | True | Yes | | Diagnoses on this patient for which this review was done.
CriteriaReview.encounter | Reference | True | | | Patient encounter for which the review was conducted. A reference to an encounter that already exists in the system in which this review is being created. Required in a provider context.
CriteriaReview.identifier | Identifier | False | | | Unique identifier for this review within the criteria review system that created it. Must be 254 characters or fewer.
CriteriaReview.isForReference | Boolean | True | | | Whether a review should not be applied to a patient and was done for comparison/reference.
CriteriaReview.levelOfAutomation | String | True | | | One of the following code values: fully-automated partially-automated manual A review is fully-automated if it has been done entirely without a reviewer making any modifications. A review is partially-automated if some parts of it have been done without a reviewer making any modifications, but other parts of it have been edited by a reviewer. A review is manual if no automation was used to generate it and it was created entirely by a reviewer. If nothing is populated, the default is manual.
CriteriaReview.note | Annotation | False | Yes | | Notes that apply to this review. Each annotation's text, along with author and time if specified, will be included in the review's summary note, but will not initially be stored discretely. Note.time cannot be in the future.
CriteriaReview.overallDetermination | String | False | | | The overall result from doing the review, represented in a human-readable format. Will be truncated to 50 characters everywhere except the review's summary note.
CriteriaReview.overallDeterminationValue | String | False | | | One of the following code values: positive negative neutral The meaning of the overallDetermination. Whether the criteria has been satisfied, has not been satisfied, or does not have either meaning.
CriteriaReview.patient | Reference | True | | | Patient for which the review was conducted. A reference to a patient that already exists in the system in which this review is being created.
CriteriaReview.procedureCode | Coding | True | Yes | | Procedures on this patient for which this review was done.
CriteriaReview.progressionExpectedLOS | Int32 | True | | | The patient's expected length of stay.
CriteriaReview.progressionExpectedLOSSource | String | True | | | Source used for calculating progressionExpectedLOS.
CriteriaReview.status | String | True | | | One of the following code values: in-progress completed entered-in-error A review is in-progress when the reviewer has saved it as a draft or there still exist required steps that have not been done. A review is completed when the review is no longer saved as a draft and all required steps for reviewing are done. A review is entered-in-error if it has been deleted after being mistakenly created. If nothing is populated, the default is in-progress.
CriteriaReview.templateID | Identifier | True | | | Identifier of template in criteria review software from which this review was created. templateID.value must be 50 or fewer characters.
CriteriaReview.templateName | String | True | | | Human-readable name of the template in the criteria review software from which this review was created.
CriteriaReview.templateVersion | String | True | | | Version of the template in criteria review software from which this review was created. Must be 50 or fewer characters.

CriteriaReview.title | String | False | | | Title of the review.

CriteriaReview.type | String | True | | | One of the following code values: planned-admission general-admission emergent-admission progression discharge outpatient-procedure Type of review. If the type is not specified, Unspecified is used.

CriteriaReview.unsolicitedUpdateCutoff | String | True | | | If unsolicited updates are allowed, instant after which no unsolicited updates will be allowed. Once this is specified, subsequent unsolicited calls to update after the cutoff will not be accepted. Only a solicited update will be able to reset the cutoff.

CriteriaReview.unsolicitedUpdatesAllowed | Boolean | True | | | Whether unsolicited updates should be allowed on this review (after current update). If not defined, assumed that unsolicited updates (updates done automatically without a reviewer involved) are allowed. If not specified and updatesAllowed is specified, defaults to value of updatesAllowed. This is to prevent a mismatch if updatesAllowed is set to false and unsolicitedUpdatesAllowed would normally default to true, causing an error.

CriteriaReview.updateDateTime | String | False | | | Instant at which this review was last updated. Cannot be in the future or earlier than creationDateTime.

CriteriaReview.updateReviewer | Reference | True | | | User who last updated this review. Must be a valid active user.

CriteriaReview.updatesAllowed | Boolean | True | | | Whether any updates should be allowed on this review (after current update). If not defined, assumed that updates are allowed. These updates can be either manual (done by a reviewer) or automated, depending upon the value of unsolicitedUpdatesAllowed.

CriteriaReview.userSessionToken | String | True | | | Identifier for the user session in which this review was created. Must match an existing token in the system in which this review is being created.

CriteriaReview.varianceNote | Annotation | False | | | If this is a progression review, variance in progression course plan. The annotation's text, along with author and time if specified, will be included in the review's summary note, but will not initially be stored discretely.

Response elements

Name | Type | Optional | Array | Cardinality | Description

CriteriaReview | CriteriaReview | False

CriteriaReview.associatedDate | String | True

CriteriaReview.dayOfCare | Int32 | True | | | If this is a progression review, the day of the progression course expected given patient's admission date and associatedDate. Must be a positive integer. This element is ignored if both firstDayOfCare and lastDayOfCare are populated.

CriteriaReview.dayOfProgressionPlan | Int32 | True | | | If this is a progression review, the day of the progression course this review represents. Must be a positive integer. This element is ignored if both firstDayOfProgressionPlan and lastDayOfProgressionPlan are populated.

OperationOutcome | OperationOutcome | False

OperationOutcome.contained | ResourceContainer | False | Yes | | A container for a single FHIR resource.

OperationOutcome.extension | Extension | False | Yes

OperationOutcome.id | String | False

OperationOutcome.implicitRules | String | False

OperationOutcome.issue | Issue | False | Yes

OperationOutcome.language | String | False

OperationOutcome.meta | Meta | False

OperationOutcome.modifierExtension | Extension | False | Yes

OperationOutcome.text | Narrative | False

Sample request

```
<CriteriaReview xmlns="http://hl7.org/fhir">
  <title value="Review Title"/>
  <userSessionToken value="i4wuerth894ahrs"/>
  <creationDateTime value="2019-12-11T19:14:50Z"/>
  <updateDateTime value="2019-12-11T19:14:50Z"/>
  <overallDetermination value="Not Met for Observation Admission"/>
  <associatedDates>
    <start value="2019-12-11"/>
    <end value="2019-12-14"/>
  </associatedDates>
  <templateName value="Superior Template Name"/>
  <templateVersion value="1.3"/>
  <updatesAllowed value="true"/>
  <unsolicitedUpdatesAllowed value="true"/>
  <overallDeterminationValue value="negative"/>
  <type value="planned-admission"/>
  <status value="completed"/>
  <firstDayOfCare value="4"/>
  <lastDayOfCare value="7"/>
  <firstDayOfProgressionPlan value="3"/>
  <lastDayOfProgressionPlan value="7"/>
  <unsolicitedUpdateCutoff value="2021-12-04T19:18:28Z"/>
  <progressionExpectedLOS value="4"/>
  <progressionExpectedLOSSource value="www.hackmevendor.com"/>
  <patient>
    <reference value="Patient/eb8ef41wb.a.b.LbkPQmI3A3"/>
    <display value="Example, Felicia"/>
  </patient>
  <encounter>
    <reference value="Encounter/eJvA2QM307qSWj6pIk.lOqxBmLXvAppIEdwNxX6crqkY3"/>
  </encounter>
  <identifier>
    <value value="300000000"/>
  </identifier>
  <creationReviewer>
    <reference value="Practitioner/eSNO5tMy06DcMPHcvMjFhsQ3"/>
    <display value="David Example, MD"/>
  </creationReviewer>
```

```
  <updateReviewer>
    <reference value="Practitioner/eSNO5tMy06DcMPHcvMjFhsQ3"/>
    <display value="David Example, MD"/>
  </updateReviewer>
  <completionReviewer>
    <reference value="Practitioner/eSNO5tMy06DcMPHcvMjFhsQ3"/>
    <display value="David Example, MD"/>
  </completionReviewer>
  <templateID>
    <system value="hackmevendor.com"/>
    <value value="123456720"/>
  </templateID>
  <criterion>
    <text value="Admission is indicated"/>
    <isSatisfied value="false"/>
    <subCriteriaLogic value="count-or-more"/>
    <subCriteriaCount value="2"/>
    <criterionEvidenceString value="Patient reported"/>
    <criterionEvidenceUri value="www.acmevendor.com/cite-it"/>
    <backingInfo>
      <attachmentDateTime value="2019-12-04T19:18:28Z"/>
      <valueAnnotation>
        <text value="Backing Info"/>
        <time value="2019-12-04T19:18:28Z"/>
        <authorReference>
          <reference value="Practitioner/eSNO5tMy06DcMPHcvMjFhsQ3"/>
        </authorReference>
      </valueAnnotation>
    </backingInfo>
    <subCriterion>
      <text value="Ventilatory support required"/>
      <isSatisfied value="true"/>
    </subCriterion>
    <subCriterion>
      <text value="Peak expiratory flow rate between 40% and 60% of predicted or personal best after treatment"/>
      <isSatisfied value="true"/>
      <subCriteriaLogic value="any"/>
      <subCriterion>
        <text value="History of asthma requiring intubation"/>
        <isSatisfied value="true"/>
      </subCriterion>
      <subCriterion>
        <text value="Hospitalization for asthma within the past year"/>
        <isSatisfied value="false"/>
      </subCriterion>
      <subCriterion>
        <text value="Exacerbation due to allergic reaction to food"/>
        <isSatisfied value="true"/>
      </subCriterion>
    </subCriterion>
    <subCriterion>
      <text value="Hypoxemia"/>
      <isSatisfied value="true"/>
    </subCriterion>
  </criterion>
  <note>
    <text value="New Clinical Note"/>
    <authorReference>
      <reference value="Practitioner/eSNO5tMy06DcMPHcvMjFhsQ3"/>
    </authorReference>
    <time value="2019-12-04T19:18:28Z"/>
  </note>
</CriteriaReview>
```

Sample response

N/A

36.1.2 CriteriaReview.Read (R4)

File: site/apis/36-Workflow-Patient-Management/1-R4/1010-CriteriaReview-Read-R4.html
Epic API ID | 1010
FHIR version | R4
Categories | Workflow Patient Management
API type | Epic Public
API group | Utilization Management integration
USCDI | No
HTTP method | GET
URL template | /api/FHIR/R4/CriteriaReview/{ID}
Supports OAuth 2.0 | True
Supported user types | Backend Systems and Non-OAuth 2.0, Clinicians or Administrative Users
Performs scope validation | False
Source | https://fhir.epic.com/Specifications?api=1010

Description

This web service retrieves data from a criteria review record.

Request parameters

Name | Type | Optional | Array | Cardinality | Description
ID | String | False

Response elements

Name | Type | Optional | Array | Cardinality | Description
CriteriaReview | CriteriaReview | False
CriteriaReview.associatedDate | String | True | | | Date for which the review was performed. This element is ignored if associatedDates is populated. (February 2026 and earlier)
CriteriaReview.authorizationRequest | Reference | True | | | A FHIR Claim reference. Authorization this resource is associated with, if any.
CriteriaReview.completedDateTime | String | True | | | Instant at which this review was marked completed. Required if the review has a status of completed. Cannot be a future time and cannot be earlier than creationDateTime.
CriteriaReview.completionReviewer | Reference | True | | | User who marked this review as completed. Must be a valid active user.
CriteriaReview.creationDateTime | String | False | | | Instant at which this review was first created.
CriteriaReview.creationReviewer | Reference | True | | | User who created this review. Must be a valid active user.
CriteriaReview.dayOfCare | Int32 | True | | | If this is a progression review, the day of the progression course expected given patient's admission date and associatedDate. Must be a positive integer. This element is ignored if both firstDayOfCare and lastDayOfCare are populated. (February 2026 and earlier)
CriteriaReview.dayOfProgressionPlan | Int32 | True | | | If this is a progression review, the day of the progression course this review represents. Must be a positive integer. This element is ignored if both firstDayOfProgressionPlan and lastDayOfProgressionPlan are populated. (February 2026 and earlier)
CriteriaReview.encounter | Reference | True | | | Patient encounter for which the review was conducted. A reference to an encounter that already exists in the system in which this review is being created.
CriteriaReview.id | String | False
CriteriaReview.identifier | Identifier | False | | | Unique identifier for this review within the criteria review system that created it. Must be 254 characters or fewer.
CriteriaReview.isForReference | Boolean | True | | | Whether a review should not be applied to a patient and was done for comparison/reference.
CriteriaReview.levelOfAutomation | String | True | | | One of the following code values: fully-automated partially-automated manual A review is fully-automated if it has been done entirely without a reviewer making any modifications. A review is partially-automated if some parts of it have been done without a reviewer making any modifications, but other parts of it have been edited by a reviewer. A review is manual if no automation was used to generate it and it was created entirely by a reviewer.. If nothing is populated, the default is manual.
CriteriaReview.note | Annotation | True | Yes | | Notes that apply to this review. Each annotation's text, along with author and time if specified, will be included in the review's summary note, but will not initially be stored discretely. Note.time cannot be in the future.
CriteriaReview.overallDetermination | String | False | | | The overall result from doing the review, represented in a human-readable format. Will be truncated to 50 characters everywhere except the review's summary note.
CriteriaReview.overallDeterminationValue | String | False | | | One of the following code values: positive negative neutral The meaning of the overallDetermination. Whether the criteria has been satisfied, has not been satisfied, or does not have either meaning.
CriteriaReview.patient | Reference | False | | | Patient for which the review was conducted. A reference to a patient that already exists in the system in which this review is being created.
CriteriaReview.serviceTraceNumber | String | True | Yes | | The service authorizations associated with the criteria review and their states.
CriteriaReview.status | String | True | | | One of the following code values: in-progress completed entered-in-error A review is in-progress when the reviewer has saved it as a draft or there still exist required steps that have not been done. A review is completed when the review is no longer saved as a draft and all required steps for reviewing are done. A review is entered-in-error if it has been deleted after being mistakenly created. If nothing is populated, the default is in-progress.
CriteriaReview.templateID | Identifier | True | | | Identifier of template in criteria review software from which this review was created. templateID.value must be 50 or fewer characters. templateID.system must be 260 or fewer characters.
CriteriaReview.templateName | String | True | | | Human-readable name of the template in the criteria review software from which this review was created.
CriteriaReview.templateVersion | String | True | | | Version of the template in criteria review software from which this review was created. Must be 50 or fewer characters.
CriteriaReview.title | String | False | | | Title of the review.
CriteriaReview.type | String | True | | | One of the following code values: planned-admission general-admission emergent-admission progression discharge outpatient-procedure Type of review. If the type is not specified, Unspecified is used.
CriteriaReview.unsolicitedUpdateCutoff | String | True | | | If unsolicited updates are allowed, instant after which no unsolicited updates will be allowed. Once this is specified, subsequent unsolicited calls to update after the cutoff will not be accepted. Only a solicited update will be able to reset the cutoff.
CriteriaReview.unsolicitedUpdatesAllowed | Boolean | True | | | Whether unsolicited updates should be allowed on this review (after current update). If not defined, assumed that unsolicited updates (updates done automatically without a reviewer involved) are allowed. If not specified and updatesAllowed is specified, defaults to value of updatesAllowed. This is to prevent a mismatch if updatesAllowed is set to false and unsolicitedUpdatesAllowed would normally default to true, causing an error.
CriteriaReview.updateDateTime | String | False | | | Instant at which this review was last updated.
CriteriaReview.updateReviewer | Reference | True | | | User who last updated this review. Must be a valid active user.
CriteriaReview.updatesAllowed | Boolean | True | | | Whether any updates should be allowed on this review (after current update). If not defined, assumed that updates are allowed. These updates can be either manual (done by a reviewer) or automated, depending upon the value of unsolicitedUpdatesAllowed.
OperationOutcome | OperationOutcome | False
OperationOutcome.contained | ResourceContainer | False | Yes | | A container for a single FHIR resource.
OperationOutcome.extension | Extension | False | Yes
OperationOutcome.id | String | False
OperationOutcome.implicitRules | String | False

OperationOutcome.issue | Issue | False | Yes
OperationOutcome.language | String | False
OperationOutcome.meta | Meta | False
OperationOutcome.modifierExtension | Extension | False | Yes
OperationOutcome.text | Narrative | False

Sample request

```
https://hostname/instance/api/FHIR/R4/CriteriaReview/123456789
```

Sample response

```
<CriteriaReview xmlns="http://hl7.org/fhir">
  <title value="Review Title"/>
  <creationDateTime value="2019-12-04T19:14:50Z"/>
  <updateDateTime value="2019-12-04T19:10:00Z"/>
  <completedDateTime value="2019-12-04T19:18:28Z"/>
  <overallDetermination value="Met for Inpatient Admission"/>
  <associatedDates>
    <start value="2019-12-11"/>
    <end value="2019-12-14"/>
  </associatedDates>
  <templateName value="Template Name"/>
  <templateVersion value="1.1"/>
  <updatesAllowed value="true"/>
  <unsolicitedUpdatesAllowed value="true"/>
  <overallDeterminationValue value="positive"/>
  <levelOfAutomation value="partially-automated"/>
  <type value="emergent-admission"/>
  <status value="completed"/>
  <firstDayOfCare value="4"/>
  <lastDayOfCare value="7"/>
  <firstDayOfProgressionPlan value="3"/>
  <lastDayOfProgressionPlan value="7"/>
  <unsolicitedUpdateCutoff value="2020-12-04T19:18:28Z"/>
  <patient>
    <reference value="Patient/eb8ef41wb.a.b.LbkPQmI3A3"/>
    <display value="Example, Felicia"/>
  </patient>
  <encounter>
    <reference value="Encounter/eJvA2QM307qSWj6pIk.lOqxBmLXvAppIEdwNxX6crqkY3"/>
  </encounter>
  <identifier>
    <value value="123456789"/>
  </identifier>
  <creationReviewer>
    <reference value="Practitioner/eSNO5tMy06DcMPHcvMjFhsQ3"/>
    <display value="David Example, MD"/>
  </creationReviewer>
  <updateReviewer>
    <reference value="Practitioner/eSNO5tMy06DcMPHcvMjFhsQ3"/>
    <display value="David Example, MD"/>
  </updateReviewer>
  <completionReviewer>
    <reference value="Practitioner/eSNO5tMy06DcMPHcvMjFhsQ3"/>
    <display value="David Example, MD"/>
  </completionReviewer>
  <templateID>
    <system value="acmevendor.com"/>
    <value value="123456789"/>
  </templateID>
  <varianceNote>
    <text value=" Primary Variance&#13;&#10; Category: Hospital system delay&#13;&#10; Reason: Delay in test
    initiation&#13;&#10; Context: A one day delay compared to the Optimal Recovery Course because of delay in test
    initiation, attributed to systems or staff (other than physician)&#13;&#10; Resolution: Assigned to Available
    Provider&#13;&#10; Variance Note:&#13;&#10; Variance Note&#13;&#10; Resolution Note:&#13;&#10; Resolution
    Note&#13;&#10;"/>
    <authorReference>
      <reference value="Practitioner/eSNO5tMy06DcMPHcvMjFhsQ3"/>
    </authorReference>
    <time value="2019-12-04T19:18:28Z"/>
  </varianceNote>
  <note>
    <text value="Clinical Note"/>
    <authorReference>
      <reference value="Practitioner/eSNO5tMy06DcMPHcvMjFhsQ3"/>
    </authorReference>
    <time value="2019-12-04T19:18:28Z"/>
  </note>
</CriteriaReview>
```

36.1.3 CriteriaReview.Update (R4)

File: site/apis/36-Workflow-Patient-Management/1-R4/1011-CriteriaReview-Update-R4.html
Epic API ID | 1011
FHIR version | R4

Categories | Workflow Patient Management
API type | Epic Public
API group | Utilization Management integration
USCDI | No
HTTP method | PUT
URL template | /api/FHIR/R4/CriteriaReview
Supports OAuth 2.0 | True
Supported user types | Backend Systems and Non-OAuth 2.0, Clinicians or Administrative Users
Performs scope validation | False
Source | https://fhir.epic.com/Specifications?api=1011

Description

This web service updates an existing criteria review record.

Request parameters

Name | Type | Optional | Array | Cardinality | Description
CriteriaReview | CriteriaReview | False
CriteriaReview.associatedAuthorization | Reference | True | | | A FHIR Claim reference. Authorization this review is associated with, if any.
CriteriaReview.associatedDate | String | True | | | Date for which the review was performed.
CriteriaReview.authorizationRequest | Reference | True | | | A FHIR Claim reference. Authorization this resource is associated with, if any.
CriteriaReview.completedDateTime | String | True | | | Instant at which this review was marked completed. Required if the review has a status of completed. Cannot be a future time and cannot be earlier than creationDateTime.
CriteriaReview.completionReviewer | Reference | True | | | User who marked this review as completed. Should be sent as a FHIR Practitioner reference. Must be a valid active user.
CriteriaReview.copyright | String | True | | | Copyright text that should be included with this review. Will appear at the bottom of the review's summary note.
CriteriaReview.creationDateTime | String | False | | | Instant at which this review was first created.
CriteriaReview.creationReviewer | Reference | True | | | User who created this review. Should be sent as a FHIR Practitioner reference. Must be a valid active user. Should be sent as a FHIR Practitioner reference.
CriteriaReview.criterion | Criterion | True | Yes | | Criteria to support the review's recommendation.
CriteriaReview.criterion.associatedCode | Coding | True | Yes | | Codes (e.g. SNOMED) associated with this criterion.
CriteriaReview.criterion.backingInfo | BackingInfo | True | Yes | | Information that supports this criterion.
CriteriaReview.criterion.backingInfo.attachmentDateTime | String | False | | | Instant that this backing information was attached to the criterion.
CriteriaReview.criterion.backingInfo.valueAnnotation | Annotation | False | | | Backing information that supports this criterion.
CriteriaReview.criterion.backingInfo.valueAnnotation.authorReference | Reference | False | | | A FHIR reference.
CriteriaReview.criterion.backingInfo.valueAnnotation.text | String | False
CriteriaReview.criterion.backingInfo.valueAnnotation.time | String | False
CriteriaReview.criterion.criterionEvidenceString | String | True | Yes | | Evidence that this criterion is a valid measure to use for this criteria review. This field is an array.
CriteriaReview.criterion.isSatisfied | Boolean | False | | | Whether or not this criterion is satisfied.
CriteriaReview.criterion.subCriteriaCount | Int32 | True | | | If criterion.subCriteriaLogic is count, count-or-more, or count-or-fewer, what to use as count.
CriteriaReview.criterion.subCriteriaLogic | String | True | | | One of the following: all any none count count-or-more count-or-fewer How sub-criteria elements must be satisfied in order for criterion.isSatisfied to be true.
CriteriaReview.criterion.text | String | False | | | Textual representation of the criterion.
CriteriaReview.dayOfCare | Int32 | True | | | If this is a progression review, the day of the progression course expected given patient's admission date and associatedDate. Must be a positive integer.
CriteriaReview.dayOfProgressionPlan | Int32 | True | | | If this is a progression review, the day of the progression course this review represents. Must be a positive integer.
CriteriaReview.diagnosisCode | Coding | True | Yes | | Diagnoses on this patient for which this review was done.
CriteriaReview.encounter | Reference | True | | | Patient encounter for which the review was conducted. A reference to an encounter that already exists in the system in which this review is being created.
CriteriaReview.identifier | Identifier | False | | | Unique identifier for this review within the criteria review system that created it. Must be 254 characters or fewer.
CriteriaReview.isForReference | Boolean | True | | | Whether a review should not be applied to a patient and was done for comparison/reference.
CriteriaReview.levelOfAutomation | String | True | | | One of the following code values: fully-automated partially-automated manual A review is fully-automated if it has been done entirely without a reviewer making any modifications. A review is partially-automated if some parts of it have been done without a reviewer making any modifications, but other parts of it have been edited by a reviewer. A review is manual if no automation was used to generate it and it was created entirely by a reviewer. If nothing is populated, the default is manual.
CriteriaReview.note | Annotation | True | Yes | | Notes that apply to this review. Each annotation's text, along with author and time if specified, will be included in the review's summary note, but will not initially be stored discretely. Note.time cannot be in the future.
CriteriaReview.overallDetermination | String | False | | | The overall result from doing the review, represented in a human-readable format. Will be truncated to 50 characters everywhere except the review's summary note.
CriteriaReview.overallDeterminationValue | String | False | | | One of the following code values: positive negative neutral The meaning of the overallDetermination. Whether the criteria has been satisfied, has not been satisfied, or does not have either meaning.
CriteriaReview.patient | Reference | True | | | Patient for which the review was conducted. A reference to a patient that already exists in the system in which this review is being created.
CriteriaReview.progressionExpectedLOS | Int32 | True | | | The patient's expected length of stay.
CriteriaReview.progressionExpectedLOSSource | String | True | | | Source used for calculating progressionExpectedLOS.
CriteriaReview.serviceTraceNumber | String | True | Yes | | The service authorizations associated with the criteria review and their states.
CriteriaReview.status | String | True | | | One of the following code values: in-progress completed entered-in-error A review is in-progress when the reviewer has saved it as a draft or there still exist required steps that have not been done. A review is completed when the review is no longer saved as a draft and all required steps for reviewing are done. A review is entered-in-error if it has been deleted after being mistakenly created. If nothing is

populated, the default is in-progress.

CriteriaReview.templateID | Identifier | True | | | Identifier of template in criteria review software from which this review was created. templateID.value must be 50 or fewer characters. templateID.system must be 260 or fewer characters.

CriteriaReview.templateName | String | True | | | Human-readable name of the template in the criteria review software from which this review was created.

CriteriaReview.templateVersion | String | True | | | Version of the template in criteria review software from which this review was created. Must be 50 or fewer characters.

CriteriaReview.title | String | False | | | Title of the review.

CriteriaReview.type | String | True | | | One of the following code values: planned-admission general-admission emergent-admission progression discharge outpatient-procedure Type of review. If the type is not specified, Unspecified is used.

CriteriaReview.unsolicitedUpdateCutoff | String | True | | | If unsolicited updates are allowed, instant after which no unsolicited updates will be allowed. Once this is specified, subsequent unsolicited calls to update after the cutoff will not be accepted. Only a solicited update will be able to reset the cutoff.

CriteriaReview.unsolicitedUpdatesAllowed | Boolean | True | | | Whether unsolicited updates should be allowed on this review (after current update). If not defined, assumed that unsolicited updates (updates done automatically without a reviewer involved) are allowed. If not specified and updatesAllowed is specified, defaults to value of updatesAllowed. This is to prevent a mismatch if updatesAllowed is set to false and unsolicitedUpdatesAllowed would normally default to true, causing an error.

CriteriaReview.updateDateTime | String | False | | | Instant at which this review was last updated.

CriteriaReview.updateReviewer | Reference | True | | | User who last updated this review. Must be a valid active user.

CriteriaReview.updatesAllowed | Boolean | True | | | Whether any updates should be allowed on this review (after current update). If not defined, assumed that updates are allowed. These updates can be either manual (done by a reviewer) or automated, depending upon the value of unsolicitedUpdatesAllowed.

CriteriaReview.userSessionToken | String | True | | | Identifier for the user session in which this review was created. Must match an existing token in the system in which this review is being created.

CriteriaReview.varianceNote | Annotation | True | | | If this is a progression review, variance in progression course plan. The annotation's text, along with author and time if specified, will be included in the review's summary note, but will not initially be stored discretely.

Response elements

Name | Type | Optional | Array | Cardinality | Description

OperationOutcome | OperationOutcome | False

Sample request

```
<CriteriaReview xmlns="http://hl7.org/fhir">
  <id value="ezz0C2AvdJLFz55guG4mm.Q3"/>
  <title value="Review Title"/>
  <userSessionToken value="i4wuerth894ahrs"/>
  <creationDateTime value="2019-12-11T19:14:50Z"/>
  <updateDateTime value="2019-12-11T19:10:00Z"/>
  <completedDateTime value="2019-12-11T19:18:28Z"/>
  <overallDetermination value="Not Met for Observation Admission"/>
  <associatedDates>
    <start value="2019-12-11"/>
    <end value="2019-12-14"/>
  </associatedDates>
  <templateName value="Superior Template Name"/>
  <templateVersion value="1.3"/>
  <updatesAllowed value="true"/>
  <unsolicitedUpdatesAllowed value="true"/>
  <overallDeterminationValue value="negative"/>
  <type value="planned-admission"/>
  <status value="completed"/>
  <firstDayOfCare value="4"/>
  <lastDayOfCare value="7"/>
  <firstDayOfProgressionPlan value="3"/>
  <lastDayOfProgressionPlan value="7"/>
  <unsolicitedUpdateCutoff value="2021-12-04T19:18:28Z"/>
  <progressionExpectedLOS value="4"/>
  <progressionExpectedLOSSource value="www.hackmevendor.com"/>
  <patient>
    <reference value="Patient/eb8ef41wb.a.b.LbkPQmI3A3"/>
    <display value="Example, Felicia"/>
  </patient>
  <encounter>
    <reference value="Encounter/eJvA2QM307qSWj6pIk.lOqxBmLXvAppIEdwNxX6crqkY3"/>
  </encounter>
  <identifier>
    <value value="300000000"/>
  </identifier>
  <creationReviewer>
    <reference value="Practitioner/eSNO5tMy06DcMPHcvMjFhsQ3"/>
    <display value="David Example, MD"/>
  </creationReviewer>
  <updateReviewer>
    <reference value="Practitioner/eSNO5tMy06DcMPHcvMjFhsQ3"/>
    <display value="David Example, MD"/>
  </updateReviewer>
  <completionReviewer>
    <reference value="Practitioner/eSNO5tMy06DcMPHcvMjFhsQ3"/>
    <display value="David Example, MD"/>
  </completionReviewer>
  <templateID>
```

```
    <system value="hackmevendor.com"/>
    <value value="123456720"/>
  </templateID>
  <criterion>
    <text value="Admission is indicated"/>
    <isSatisfied value="false"/>
    <subCriteriaLogic value="count-or-more"/>
    <subCriteriaCount value="2"/>
    <criterionEvidenceString value="Because I said so"/>
    <criterionEvidenceUri value="www.acmevendor.com/cite-it"/>
    <backingInfo>
      <attachmentDateTime value="2019-12-04T19:18:28Z"/>
      <valueAnnotation>
        <text value="Backing Info"/>
        <time value="2019-12-04T19:18:28Z"/>
        <authorReference>
          <reference value="Practitioner/eSNO5tMy06DcMPHcvMjFhsQ3"/>
        </authorReference>
      </valueAnnotation>
    </backingInfo>
    <subCriterion>
      <text value="Ventilatory support required"/>
      <isSatisfied value="true"/>
    </subCriterion>
    <subCriterion>
      <text value="Peak expiratory flow rate between 40% and 60% of predicted or personal best after treatment"/>
      <isSatisfied value="true"/>
      <subCriteriaLogic value="any"/>
      <subCriterion>
        <text value="History of asthma requiring intubation"/>
        <isSatisfied value="true"/>
      </subCriterion>
      <subCriterion>
        <text value="Hospitalization for asthma within the past year"/>
        <isSatisfied value="false"/>
      </subCriterion>
      <subCriterion>
        <text value="Exacerbation due to allergic reaction to food"/>
        <isSatisfied value="true"/>
      </subCriterion>
    </subCriterion>
    <subCriterion>
      <text value="Hypoxemia"/>
      <isSatisfied value="true"/>
    </subCriterion>
  </criterion>
  <note>
    <text value="New Clinical Note"/>
    <authorReference>
      <reference value="Practitioner/eSNO5tMy06DcMPHcvMjFhsQ3"/>
    </authorReference>
    <time value="2019-12-04T19:18:28Z"/>
  </note>
</CriteriaReview>
```

Sample response

```
N/A
```

36.1.4 Encounter.Read (Outside Record) (R4)

File: site/apis/36-Workflow-Patient-Management/1-R4/11006-Encounter-Read-Outside-Record-R4.html
Epic API ID | 11006
FHIR version | R4
Categories | Workflow Patient Management, CMS Incoming
API type | USCDI
A la carte | Industry-Standard Level 1 API
USCDI | Yes
Keywords | outside record
Available in inpatient and other contexts | Yes
HTTP method | GET
URL template | /api/FHIR/R4/Encounter/{ID}
Supports OAuth 2.0 | True
Supported user types | Backend Systems and Non-OAuth 2.0, Clinicians or Administrative Users, Patients
Performs scope validation | False
Source | https://fhir.epic.com/Specifications?api=11006

Description

Use this API to retrieve a specific instance of a patient's Encounters. The Encounter (Outside Record) resource defines the setting where patient care takes place.

The data returned by this API includes ambulatory, inpatient, emergency, home health, virtual, and externally loaded encounters. This API does not return upcoming encounters.

This API differs from other Encounter APIs because it returns data that was obtained as part of payer data exchange workflows rather than directly recorded during patient care. This data can come from payers, providers, or loaded from other FHIR servers. Because this data doesn't originate from the organization being queried, users of this API should be aware that the data might be unverified, incomplete, or duplicative.

Data from outside payer and provider systems is saved to an organization's database and returned in a standard format, documented below. Data loaded from other FHIR servers is returned in the format the organization received it. Because of this, the documentation below does not apply to these loaded resources. These resources can include any elements from the FHIR specification and can be distinguished from other resources by the presence of meta.tag set to "external-bulk-data".

Request parameters

Name | Type | Optional | Array | Cardinality | Description
ID | token | Required | | | The Encounter FHIR ID.

Response elements

Name | Type | Optional | Array | Cardinality | Description
Encounter (R4) | Resource | | | | A single Encounter resource.
Encounter (R4).class | Coding | | | 1..1 | Classification of patient encounter.
Encounter (R4).class.code | String | | | 0..1 | The abbreviation of the encounter type. This includes the following values: AMB IMP EMER OTHER
Encounter (R4).class.display | String | | | 0..1 | The display name of the encounter type. This includes the following values: Ambulatory Inpatient Encounter Emergency Other
Encounter (R4).hospitalization | BackboneElement | | | 0..1 | Details about the hospital admission.
Encounter (R4).hospitalization.dischargeDisposition | CodeableConcept | | | 0..1 | Category or kind of location after discharge.
Encounter (R4).id | id | | | 1..1 | The Encounter FHIR ID.
Encounter (R4).identifier | Identifier | | Yes | 0..* | Identifier(s) by which this encounter is known.
Encounter (R4).identifier.system | String | | | 1..1 | Establishes the namespace for the value - that is, a URL that describes a set of values that are unique.
Encounter (R4).identifier.value | String | | | 1..1 | The portion of the identifier typically relevant to the user and which is unique within the context of the system.
Encounter (R4).location | BackboneElement | | Yes | 0..* | List of locations where the patient has been during this encounter.
Encounter (R4).location.location | Reference | | | 1..1 | The location where the encounter takes place. This only contains the name of the location.
Encounter (R4).meta | Meta | | | 0..1 | Metadata about the resource, including information about the origin or source of the data.
Encounter (R4).meta.tag | Coding | | Yes | 0..* | Set to external-bulk-data for resources originally loaded from another FHIR server. If this element is set to external-bulk-data, all other element-level documentation does not apply to the resource. The resource content might vary and can include any elements allowed by the FHIR specification.
Encounter (R4).participant | BackboneElement | | Yes | 0..* | List of participants involved in the encounter. This can include but is not limited to: Attending Provider Referring Provider Interpreters Appointment Providers
Encounter (R4).participant.individual | Reference | | | 0..1 | Reference to the Practitioner or PractitionerRole resource representing the participant. A reference to a PractitionerRole resource is used when a provider taxonomy or provider type is available to send in PractitionerRole.specialty or PractitionerRole.code. Otherwise a Practitioner reference is used.
Encounter (R4).participant.period | Period | | | 0..1 | Period of time during the encounter that the participant participated. No period is populated for admitting and referring providers.
Encounter (R4).participant.type | CodeableConcept | | Yes | 0..* | Role of participant in encounter.
Encounter (R4).participant.type.coding | Coding | | Yes | 0..* | Code defined by a terminology system.
Encounter (R4).participant.type.coding.code | String | | | 0..1 | Symbol in syntax defined by the system. The values for this element include: ADM - admitter DIS - discharger ATND - attender REF - referrer PPRF - primary performer PART - participation
Encounter (R4).participant.type.coding.system | String | | | 0..1 | Returns http://terminology.hl7.org/CodeSystem/v3-ParticipationType.
Encounter (R4).period | Period | | | 0..1 | The start and end date/time of the encounter. The specific start and end times vary based on the type of encounter. Any encounters without a specific start or end time always start or end at midnight.
Encounter (R4).reasonReference | Reference | | Yes | 0..* | Reference to the Condition Encounter Diagnosis resource representing the reason for the visit.
Encounter (R4).status | code | | | 1..1 | The encounter status. A full list of statuses can be found here.
Encounter (R4).subject | Reference | | | 1..1 | Reference to the Patient resource who was the subject of the encounter.
Encounter (R4).type | CodeableConcept | | Yes | 1..* | The Epic encounter type and encounter type represented by a CPT code. If no CPT code applies, a SNOMED Code of "Unknown" is returned.

Sample request

```
GET https://hostname/instance/api/FHIR/R4/Encounter/fnSA0G7gB6LRd9RgYljSIlF5wsq2IsdiwVIvteQ3pAGI4
```

Sample response


```
{
  "resourceType": "Encounter",
  "id": "fnSA0G7gB6LRd9RgYljSIlF5wsq2IsdiwVIvteQ3pAGI4",
  "identifier": [
    {
      "use": "usual",
      "system": "urn:oid:1.2.840.114350.1.13.51879.1.7.3.698084.8",
      "value": "20745"
    }
  ],
  "status": "finished",
```

```
  "class": {
    "system": "http://terminology.hl7.org/CodeSystem/v3-ActCode",
    "code": "AMB",
    "display": "Ambulatory"
  },
  "type": [
    {
      "coding": [
        {
          "system": "http://snomed.info/sct",
          "code": "111",
          "display": "Orders Only"
        }
      ],
      "text": "Orders Only"
    },
    {
      "coding": [
        {
          "system": "urn:oid:1.2.840.114350.1.72.1.7.7.10.688882.8024",
          "code": "105",
          "display": "Letter (Out)"
        }
      ],
      "text": "Letter (Out)"
    }
  ],
  "subject": {
    "reference": "Patient/eH7uldpmBBnp2yJkfHPkyHA3",
    "display": "FHIR, Test"
  },
  "participant": [
    {
      "individual": {
        "reference": "Practitioner/eZjjXH-OF4y0aphI9Y8T6YwuOMpLEkeO495m2dJgrCQjUyYm574OL.1l8UcdW.YDZ3"
      },
      "type": [
        {
          "coding": [
            {
              "system": "http://terminology.hl7.org/CodeSystem/v3-ParticipationType",
              "code": "ATND"
            }
          ]
        }
      ],
      "period": {
        "start": "2024-08-09T05:00:00Z"
      }
    }
  ],
  "period": {
    "start": "2024-08-09",
    "end": "2024-08-09"
  },
  "location": [
    {
      "location": {
        "display": "FHIR Test Location"
      }
    }
  ]
}
```


Change log

Epic Version | Description | Type
November 2026 | Encounter.participant.individual can now contain a reference to a PractitionerRole resource. A PractitionerRole reference is sent when a provider specialty or provider type is available; otherwise, a Practitioner reference is sent as before. | Breaking change
February 2026 | FHIR IDs for Encounter (Outside Record) (R4) resources will no longer be valid if generated by previous versions, due to a change in format. | Breaking change

36.1.5 Encounter.Read (Patient Chart) (R4)

File: site/apis/36-Workflow-Patient-Management/1-R4/908-Encounter-Read-Patient-Chart-R4.html
Epic API ID | 908
FHIR version | R4
Categories | Workflow Patient Management
API type | USCDI
A la carte | Industry-Standard Level 1 API
USCDI | Yes
Available in inpatient and other contexts | Yes
ONC certification products | EpicCare Ambulatory Base, EpicCare Inpatient Base
ONC certification versions | August 2019

HTTP method | GET
URL template | /api/FHIR/R4/Encounter/{ID}
Supports OAuth 2.0 | True
Supported user types | Backend Systems and Non-OAuth 2.0, Clinicians or Administrative Users, Patients
Performs scope validation | False
Source | https://fhir.epic.com/Specifications?api=908

Description

The Encounter (Patient Chart) resource defines the setting where patient care takes place. This includes ambulatory, inpatient, emergency, home health, and virtual encounters.

Outpatient encounters are not valid until the patient has checked in. Upcoming appointments are not valid encounters.

Request parameters

Name | Type | Optional | Array | Cardinality | Description
ID | token | Required | | | The Encounter FHIR ID.

Response elements

Name | Type | Optional | Array | Cardinality | Description
Encounter (R4) | Resource | | | | A single Encounter resource.
Encounter (R4).account | Reference | | Yes | 0..* | The hospital account associated with an encounter. Includes an identifier for the hospital account, not a full reference to a FHIR Account resource.
Encounter (R4).class | Coding | | | 1..1 | Classification of the patient encounter. For organizations in the Netherlands, this field represents the ACT encounter code. For organizations in Denmark, this field represents the patient class.
Encounter (R4).diagnosis | BackboneElement | | Yes | 0..1 | Reference to a Condition (Problem) resource. Returns the principal problem for the hospital encounter. Used only for hospital encounters.
Encounter (R4).diagnosis.condition | Reference | | | 1..1 | FHIR Condition reference.
Encounter (R4).episodeOfCare | Reference | | Yes | 0..* | The episode associated with the encounter.
Encounter (R4).extension (accidentrelated) (also: extension (accidentrelated)) | Extension | | Yes | 0..1 | If true, this encounter is accident-related. URL: http://open.epic.com/FHIR/StructureDefinition/extension/accidentrelated
Encounter (R4).extension (interpreterRequired) (also: extension (interpreterRequired)) | Extension | | Yes | | Whether the patient needs an interpreter for the visit. URL: http://hl7.org/fhir/us/core/StructureDefinition/us-core-interpreter-needed
Encounter (R4).extension (is-scannable-encounter) (also: extension (is-scannable-encounter)) | Extension | | Yes | 0..1 | If true, this encounter is scannable. URL: http://open.epic.com/FHIR/StructureDefinition/extension/is-scannable-encounter
Encounter (R4).hospitalization | BackboneElement | | | 0..1 | Details about the hospital admission.
Encounter (R4).hospitalization.admitSource | CodeableConcept | | | 0..1 | The source of the patient’s admission, such as a physician referral.
Encounter (R4).hospitalization.destination | Reference | | | 0..1 | Location to which the patient is discharged. Reference to a Location resource.
Encounter (R4).hospitalization.dischargeDisposition | CodeableConcept | | | 0..1 | Category or kind of location after discharge.
Encounter (R4).hospitalization.extension (ip-admit-datetime) (also: extension (ip-admit-datetime)) | Extension | | Yes | 0..1 | The date and time the patient was admitted as inpatient. URL: http://open.epic.com/FHIR/StructureDefinition/extension/ip-admit-datetime
Encounter (R4).hospitalization.extension (observation-datetime) (also: extension (observation-datetime)) | Extension | | Yes | 0..1 | The date and time the patient was admitted for observation. URL: http://open.epic.com/FHIR/StructureDefinition/extension/observation-datetime
Encounter (R4).hospitalization.origin | Reference | | | 0..1 | The location from which the patient came before admission.
Encounter (R4).hospitalization.reAdmission | CodeableConcept | | | 0..1 | The type of hospital re-admission that has occurred (if any). If the value is absent, then this is not identified as a readmission.
Encounter (R4).id | id | | | 1..1 | The Encounter FHIR ID.
Encounter (R4).identifier | Identifier | | Yes | 1..* | The identifiers for the encounter. Including the Epic Contact Serial Number (CSN) and any other external identifiers.
Encounter (R4).location | BackboneElement | | Yes | 0..* | An array of locations representing the physical or virtual space the encounter occured in. This can include the following: bed, room, department, location, and/or service area.
Encounter (R4).location.location | Reference | | | 1..* | Location the encounter takes place. Can reference a Location resource if the location is a room, department, location, or service area. Beds are not represented by FHIR location resources.
Encounter (R4).location.location.display | String | | | 1..1 | The display name of the location.
Encounter (R4).location.location.identifier | Identifier | | | 0..1 | The identifiers associated with the location. Only returned for beds, as they are not Location references.
Encounter (R4).location.location.reference | String | | | 0..1 | Reference to a Location resource. Not returned for beds.
Encounter (R4).location.period | Period | | | 0..1 | Time period during which the patient was present at the location. This is only populated for departments.
Encounter (R4).location.physicalType | CodeableConcept | | | 0..1 | Returned for beds and rooms to describe the type of physical space represented by the Location object. Rooms are represented as ro Beds are represented as bd
Encounter (R4).meta | Meta | | | | Metadata about the Encounter
Encounter (R4).meta.lastUpdated | String | | | | Last time there was a change in the status of the encounter. In general this corresponds to the last time an event that can initiate HL7 V2 ADT message happened on the visit.
Encounter (R4).participant | BackboneElement | | Yes | 1..* | List of participants involved in the encounter. This can include but is not limited to: Attending Provider Referring Provider Interpreters Appointment Providers
Encounter (R4).participant.extension (specialty) (also: extension (specialty)) | Extension | | Yes | 0..1 | Specialty of the participant in the encounter. URL: http://open.epic.com/FHIR/StructureDefinition/extension/specialty
Encounter (R4).participant.extension (team-name) (also: extension (team-name)) | Extension | | Yes | 0..1 | Team name of the participant in the encounter. URL: http://open.epic.com/FHIR/StructureDefinition/extension/team-name
Encounter (R4).participant.individual | Reference | | | 1..1 | Reference to the Practitioner resource representing the participant.
Encounter (R4).participant.period | Period | | | 0..1 | Period of time during the encounter that the participant participated. This is populated for appointment providers. No period is populated for admitting and referring providers.

Encounter (R4).participant.type | CodeableConcept | | Yes | 0..1 | Role of participant in encounter.

Encounter (R4).participant.type.coding | Coding | | Yes | 0..1 | Coding for the participant type.

Encounter (R4).participant.type.coding.code | String | | | 1..1 | This element is returned as follows: ADM for admitting provider ATND for attending provider DIS for discharge provider REF for referring provider OTTM for other treatment team member PART for staff participant Translator for interpreter

Encounter (R4).participant.type.coding.display | String | | | 1..1 | The display name for the participant type. Returns the following: admitter for admitting providers discharger for discharge providers attender for attending providers referrer for referring providers losAuthorizingPhysician for LOS authorizing providers Participation for appointment staff Translator for interpreter Relationship to patient for treatment team members

Encounter (R4).participant.type.coding.system | String | | | 1..1 | Returns http://hl7.org/fhir/v3/ParticipationType except for interpreters, which returns http://terminology.hl7.org/CodeSystem/participant-type.

Encounter (R4).participant.type.text | String | | | 1..1 | The display name for the participant type. Returns the following: admitter for admitting providers discharger for discharge providers attender for attending providers referrer for referring providers losAuthorizingPhysician for LOS authorizing providers Participation for appointment staff Translator for interpreter Relationship to patient for treatment team members

Encounter (R4).partOf | Reference | | | 0..1 | Reference to another Encounter resource this Encounter is part of. This can be the hospital encounter that a surgical encounter is linked to, or the inpatient encounter that serves as the originating encounter for related hospital outpatient visits.

Encounter (R4).period | Period | | | 0..1 | The start and end date/time of the encounter. The specific start and end times vary based on the type of encounter. Encounters without a specific start or end time are returned with midnight as the start or end time.

Encounter (R4).period.end | String | | | 0..1 | The end date and time.

Encounter (R4).period.start | String | | | 0..1 | The start date and time.

Encounter (R4).priority | CodeableConcept | | | 0..1 | Indicates the urgency of the encounter.

Encounter (R4).reasonCode | CodeableConcept | | Yes | 0..* | The reason for visit. SNOMED codes are returned with a system of http://snomed.info/sct.

Encounter (R4).serviceProvider | Reference | | | 0..* | Reference to the Organization resource representing the service area for the encounter based on facility hierarchy. This element is returned starting in the February 2025 version of Epic, and back to the May 2024 version of Epic with special update.

Encounter (R4).serviceType | CodeableConcept | | | 0..1 | Type of service associated with this encounter. Examples include Surgery or Internal Medicine.

Encounter (R4).status | code | | | 1..1 | The encounter status. Full list of statuses can be found here.

Encounter (R4).subject | Reference | | | 1..1 | Reference to the Patient resource who was the subject of the encounter.

Encounter (R4).type | CodeableConcept | | Yes | 0..* | The encounter's types. Any values that are populated below are returned: Epic's Contact Type Patient Class Appointment Visit Type Hospital Admission Type Hospital Level of Service

Sample request

```
GET https://hostname/instance/api/FHIR/R4/Encounter/ej5R7X.4RdaFNR5vWdsTpVTtccmkRkWJcKixc5XVY4cQ3
```

Sample response


```
{
    "resourceType": "Encounter",
    "id": "eUjPAKMQNKw2lt1f9AQT-.IWL2ZUVHY4WsEwaZ2SxRbo3",
    "meta": {
"lastUpdated": "2023-11-05T19:28:00Z"
 },
    "extension": [
        {
            "valueBoolean": false,
            "url": "http://open.epic.com/FHIR/StructureDefinition/extension/accidentrelated"
        },
 {
"valueCoding": {
 "system": "http://snomed.info/sct",
 "code": "373067005",
 "display": "No"
},
             "url": "http://hl7.org/fhir/us/core/StructureDefinition/us-core-interpreter-needed"
  }
    ],
    "identifier": [
        {
            "use": "usual",
            "system": "urn:oid:1.2.840.114350.1.13.51879.1.7.3.698084.8",
            "value": "20745"
        }
    ],
    "identifier": [
        {
            "use": "usual",
            "system": "urn:oid:1.2.840.114350.1.13.5325.1.7.3.698084.8",
            "value": "10003033556"
        }
    ],
    "status": "in-progress",
    "class": {
        "system": "urn:oid:1.2.840.114350.1.72.1.7.7.10.696784.13260",
        "code": "3",
        "display": "Admission"
    },
    "type": [
        {
            "coding": [
                {
                    "system": "urn:oid:1.2.840.114350.1.13.5325.1.7.10.698084.10110",
```

```
                "code": "1",
                "display": "Inpatient"
            }
        ],
        "text": "Inpatient"
    },
    {
        "coding": [
            {
                "system": "urn:oid:1.2.840.114350.1.13.5325.1.7.10.698084.30",
                "code": "3",
                "display": "Hospital Encounter"
            }
        ],
        "text": "Hospital Encounter"
    },
    {
        "coding": [
            {
                "system": "http://snomed.info/sct",
                "code": "32485007",
                "display": "Hospital admission (procedure)"
            }
        ],
        "text": "Hospital admission (procedure)"
    },
    {
        "coding": [
            {
                "system": "urn:oid:1.2.840.114350.1.13.5325.1.7.10.698084.18875",
                "code": "1",
                "display": "Inpatient"
            }
        ],
        "text": "Inpatient"
    }
],
"serviceType": {
    "coding": [
        {
            "system": "urn:oid:1.2.840.114350.1.13.5325.1.7.10.698084.18886",
            "code": "9",
            "display": "Internal Medicine"
        }
    ],
    "text": "Internal Medicine"
},
"subject": {
    "reference": "Patient/eHOUAe.vs.Jf3E15dbsFQKg3",
    "display": "Park, Michael"
},
"participant": [
    {
        "type": [
            {
                "coding": [
                    {
                        "system": "http://terminology.hl7.org/CodeSystem/v3-ParticipationType",
                        "code": "ADM",
                        "display": "admitter"
                    }
                ],
                "text": "admitter"
            }
        ],
        "individual": {
            "reference": "Practitioner/eRs4ChjMr3UfbTGfUGoeUFg3",
            "type": "Practitioner",
            "display": "Daniel Park, MD"
        }
    },
    {
        "type": [
            {
                "coding": [
                    {
                        "system": "http://terminology.hl7.org/CodeSystem/v3-ParticipationType",
                        "code": "ATND",
                        "display": "attender"
                    }
                ],
                "text": "attender"
            }
        ],
        "individual": {
            "reference": "Practitioner/eRs4ChjMr3UfbTGfUGoeUFg3",
            "type": "Practitioner",
            "display": "Daniel Park, MD"
        }
```

```
    }
],
"period": {
    "start": "2023-11-04T13:00:00Z"
},
"account": [
    {
        "identifier": {
            "system": "urn:oid:1.2.840.114350.1.13.5325.1.7.2.726582",
            "value": "122010000197"
        },
        "display": "PARK,MICHAEL"
    }
],
"hospitalization": {
    "extension": [
        {
            "valueDateTime": "2023-11-04T13:00:00Z",
            "url": "http://open.epic.com/FHIR/StructureDefinition/extension/ip-admit-datetime"
        }
    ],
    "admitSource": {
        "coding": [
            {
                "system": "urn:oid:1.2.840.114350.1.13.5325.1.7.10.698084.10310",
                "code": "184201",
                "display": "Home"
            }
        ],
        "text": "Home"
    }
},
"location": [
    {
        "location": {
            "reference": "Location/eBKcWMNXDlvsyaTd2zNXEYw3",
            "display": "EMS Med Surg"
        },
        "period": {
            "start": "2023-11-04T13:00:00Z"
        }
    },
    {
        "location": {
            "reference": "Location/eBKcWMNXDlvsyaTd2zNXEYw3",
            "display": " EMS Med Surg"
        }
    },
    {
        "location": {
            "reference": "Location/elkw2Xo8.2fifAkV7cINKNQ3",
            "display": "EMS SERVICE AREA"
        }
    },
    {
        "location": {
            "reference": "Location/eyL8-LuO0GrGKQcBc4oB9iA3",
            "display": "115"
        },
        "physicalType": {
            "coding": [
                {
                    "system": "http://terminology.hl7.org/CodeSystem/location-physical-type",
                    "code": "ro",
                    "display": "Room"
                }
            ],
            "text": "Room"
        }
    },
    {
        "location": {
            "identifier": {
                "system": "urn:oid:1.2.840.114350.1.13.5325.1.7.2.666968",
                "value": "36392"
            },
            "display": "115 / 115-A"
        },
        "physicalType": {
            "coding": [
                {
                    "system": "http://terminology.hl7.org/CodeSystem/location-physical-type",
                    "code": "bd",
                    "display": "Bed"
                }
            ],
            "text": "Bed"
        }
    }
```

```
    ],
    "serviceProvider": {
        "reference": "Organization/eRljlo648hrqb3HPlPbCv1A3",
        "display": "EMS SERVICE AREA"
    }
}
```

Change log

Epic Version | Description | Type
February 2024 | Code system used in participant.type.coding.system has been changed: Old value Possible new values
http://hl7.org/fhir/v3/ParticipationType http://terminology.hl7.org/CodeSystem/v3-ParticipationType Or
http://terminology.hl7.org/CodeSystem/participant-type | Breaking change
Old value | Possible new values
http://hl7.org/fhir/v3/ParticipationType | http://terminology.hl7.org/CodeSystem/v3-ParticipationType Or
http://terminology.hl7.org/CodeSystem/participant-type
November 2022 | Code systems for the following code sets now return a URL in place of an OID: ActCode, ICD-10-CM, ICD-10-CA, ICD-10-NL, SNOMED System URL OID ActCode STU3: http://hl7.org/fhir/v3/ActCode R4: http://terminology.hl7.org/CodeSystem/v3-ActCode 2.16.840.1.113883.5.4 ICD-10-CM http://hl7.org/fhir/sid/icd-10-cm 2.16.840.1.113883.6.90 ICD-10-CA http://hl7.org/fhir/sid/icd-10-ca 2.16.840.1.113883.6.94 ICD-10-NL http://hl7.org/fhir/sid/icd-10-nl 2.16.840.1.113883.6.3.2 SNOMED http://snomed.info/sct 2.16.840.1.113883.6.96 | Breaking change
System | URL | OID
ActCode | STU3: http://hl7.org/fhir/v3/ActCode R4: http://terminology.hl7.org/CodeSystem/v3-ActCode | 2.16.840.1.113883.5.4
ICD-10-CM | http://hl7.org/fhir/sid/icd-10-cm | 2.16.840.1.113883.6.90
ICD-10-CA | http://hl7.org/fhir/sid/icd-10-ca | 2.16.840.1.113883.6.94
ICD-10-NL | http://hl7.org/fhir/sid/icd-10-nl | 2.16.840.1.113883.6.3.2
SNOMED | http://snomed.info/sct | 2.16.840.1.113883.6.96

36.1.6 Encounter.Search (Outside Record) (R4)

File: site/apis/36-Workflow-Patient-Management/1-R4/11000-Encounter-Search-Outside-Record-R4.html
Epic API ID | 11000
FHIR version | R4
Categories | Workflow Patient Management, CMS Incoming
API type | USCDI
A la carte | Industry-Standard Level 1 API
USCDI | Yes
Keywords | outside record
Available in inpatient and other contexts | Yes
HTTP method | GET
URL template | /api/FHIR/R4/Encounter?class={class}&date={date}&identifier={identifier}&onlyscannable={onlyscannable}&patient={patient}&subject={subject}&_count={_count}&_id={_id}
Supports OAuth 2.0 | True
Supported user types | Backend Systems and Non-OAuth 2.0, Clinicians or Administrative Users, Patients
Performs scope validation | False
Source | https://fhir.epic.com/Specifications?api=11000

Description

Use this API to search for a patient's Encounters. The Encounter (Outside Record) resource defines the setting where patient care takes place.

The data returned by this API includes ambulatory, inpatient, emergency, home health, virtual, and externally loaded encounters. This API does not return upcoming encounters.

This API differs from other Encounter APIs because it returns data that was obtained as part of payer data exchange workflows rather than directly recorded during patient care. This data can come from payers, providers, or loaded from other FHIR servers. Because this data doesn't originate from the organization being queried, users of this API should be aware that the data might be unverified, incomplete, or duplicative.

Data from outside payer and provider systems is saved to an organization's database and returned in a standard format, documented below. Data loaded from other FHIR servers is returned in the format the organization received it. Because of this, the documentation below does not apply to these loaded resources. These resources can include any elements from the FHIR specification and can be distinguished from other resources by the presence of meta.tag set to "external-bulk-data".

Request parameters

Name | Type | Optional | Array | Cardinality | Description
_count | number | Optional | Yes | | Number of results per page.
_id | token | Optional | Yes | | FHIR resource IDs for the desired resources. Can be used in combination with _count, _include, and _revInclude. All others are ignored.
_include | string | Optional | Yes | | Used to indicate which referenced resources to include in the search bundle.
_revinclude | string | Optional | Yes | | Used to include Provenance or AuditEvent resources that refer to search results, when available.
date | date | Optional | Yes | | A date parameter searches on a date/time or period. The date parameter format is yyyy-mm-ddThh:mm:ss[Z|(+|-)hh:mm]
patient | reference | Required | Yes | | Reference to a patient resource.

Request parameters (post-filtered search parameters)

Name | Type | Optional | Array | Cardinality | Description

class | token | Optional | Yes | | Classification of patient encounter.

participant | reference | Optional | Yes | | A participant that was involved in the target encounter. This can be used to search for Practitioner or PractitionerRole references.

participant-type | token | Optional | Yes | | Role of participant in encounter. The values for this element include: ADM - admitter DIS - discharger ATND - attender REF - referrer PPRF - primary performer PART - participation

practitioner | reference | Optional | Yes | | A participant that was involved in the target encounter. This can only be used to search for Practitioner references.

reason-reference | reference | Optional | Yes | | Reference to a condition encounter diagnosis resource.

status | token | Optional | Yes | | The encounter status. A full list of statuses can be found here.

type | token | Optional | Yes | | The encounter's types. The possible values are: Epic's encounter type Level of service CPT code

Response elements

Name | Type | Optional | Array | Cardinality | Description

Encounter (R4) | Resource | | | | A single Encounter resource.

Encounter (R4).class | Coding | | | 1..1 | Classification of patient encounter.

Encounter (R4).class.code | String | | | 0..1 | The abbreviation of the encounter type. This includes the following values: AMB IMP EMER OTHER

Encounter (R4).class.display | String | | | 0..1 | The display name of the encounter type. This includes the following values: Ambulatory Inpatient Encounter Emergency Other

Encounter (R4).hospitalization | BackboneElement | | | 0..1 | Details about the hospital admission.

Encounter (R4).hospitalization.dischargeDisposition | CodeableConcept | | | 0..1 | Category or kind of location after discharge.

Encounter (R4).id | id | | | 1..1 | The Encounter FHIR ID.

Encounter (R4).identifier | Identifier | | Yes | 0..* | Identifier(s) by which this encounter is known.

Encounter (R4).identifier.system | String | | | 1..1 | Establishes the namespace for the value - that is, a URL that describes a set of values that are unique.

Encounter (R4).identifier.value | String | | | 1..1 | The portion of the identifier typically relevant to the user and which is unique within the context of the system.

Encounter (R4).location | BackboneElement | | Yes | 0..* | List of locations where the patient has been during this encounter.

Encounter (R4).location.location | Reference | | | 1..1 | The location where the encounter takes place. This only contains the name of the location.

Encounter (R4).meta | Meta | | | 0..1 | Metadata about the resource, including information about the origin or source of the data.

Encounter (R4).meta.tag | Coding | | Yes | 0..* | Set to external-bulk-data for resources originally loaded from another FHIR server. If this element is set to external-bulk-data, all other element-level documentation does not apply to the resource. The resource content might vary and can include any elements allowed by the FHIR specification.

Encounter (R4).participant | BackboneElement | | Yes | 0..* | List of participants involved in the encounter. This can include but is not limited to: Attending Provider Referring Provider Interpreters Appointment Providers

Encounter (R4).participant.individual | Reference | | | 0..1 | Reference to the Practitioner or PractitionerRole resource representing the participant. A reference to a PractitionerRole resource is used when a provider taxonomy or provider type is available to send in PractitionerRole.specialty or PractitionerRole.code. Otherwise a Practitioner reference is used.

Encounter (R4).participant.period | Period | | | 0..1 | Period of time during the encounter that the participant participated. No period is populated for admitting and referring providers.

Encounter (R4).participant.type | CodeableConcept | | Yes | 0..* | Role of participant in encounter.

Encounter (R4).participant.type.coding | Coding | | Yes | 0..* | Code defined by a terminology system.

Encounter (R4).participant.type.coding.code | String | | | 0..1 | Symbol in syntax defined by the system. The values for this element include: ADM - admitter DIS - discharger ATND - attender REF - referrer PPRF - primary performer PART - participation

Encounter (R4).participant.type.coding.system | String | | | 0..1 | Returns http://terminology.hl7.org/CodeSystem/v3-ParticipationType.

Encounter (R4).period | Period | | | 0..1 | The start and end date/time of the encounter. The specific start and end times vary based on the type of encounter. Any encounters without a specific start or end time always start or end at midnight.

Encounter (R4).reasonReference | Reference | | Yes | 0..* | Reference to the Condition Encounter Diagnosis resource representing the reason for the visit.

Encounter (R4).status | code | | | 1..1 | The encounter status. A full list of statuses can be found here.

Encounter (R4).subject | Reference | | | 1..1 | Reference to the Patient resource who was the subject of the encounter.

Encounter (R4).type | CodeableConcept | | Yes | 1..* | The Epic encounter type and encounter type represented by a CPT code. If no CPT code applies, a SNOMED Code of "Unknown" is returned.

Sample request

```
GET https://hostname/instance/api/FHIR/R4/Encounter?patient=eH7uldpmBBnp2yJkfHPkyHA3
```

Sample response


```
{
  "resourceType": "Bundle",
  "type": "searchset",
  "total": 1,
  "link": [
    {
      "relation": "self",
      "url": "https://hostname/instance/api/FHIR/R4/Encounter?patient=eH7uldpmBBnp2yJkfHPkyHA3"
    }
  ],
  "entry": [
    {
      "link": [
        {
          "relation": "self",
```

```
          "url": "https://hostname/instance/api/FHIR/R4/Encounter/eL-JQN2uXwj1YnU56HyVf5Q3"
        }
      ],
      "fullUrl": "https://hostname/instance/api/FHIR/R4/Encounter/eL-JQN2uXwj1YnU56HyVf5Q3",
      "resource": {
        "resourceType": "Encounter",
        "id": "eL-JQN2uXwj1YnU56HyVf5Q3",
        "identifier": [
          {
            "use": "usual",
            "system": "urn:oid:1.2.840.114350.1.13.51879.1.7.3.698084.8",
            "value": "20745"
          }
        ],
        "status": "finished",
        "class": {
          "system": "urn:oid:1.2.840.114350.1.72.1.7.7.10.696784.13260",
          "code": "13",
          "display": "Support OP Encounter"
        },
        "type": [
          {
            "coding": [
              {
                "system": "urn:oid:1.2.840.114350.1.13.51879.1.7.10.698084.30",
                "code": "111",
                "display": "Orders Only"
              }
            ],
            "text": "Orders Only"
          }
        ],
        "subject": {
          "reference": "Patient/eH7uldpmBBnp2yJkfHPkyHA3",
          "display": "FHIR, Test"
        },
        "participant": [
          {
            "type": [
              {
                "coding": [
                  {
                    "system": "http://terminology.hl7.org/CodeSystem/v3-ParticipationType",
                    "code": "PART",
                    "display": "Participation"
                  }
                ],
                "text": "Participation"
              }
            ],
            "individual": {
              "reference": "Practitioner/e9KgLrOrvkHrZp6F3v8YzeMlwlAiV.GGsYs8XRUApcPc3",
              "display": "Test Practitioner"
            }
          }
        ],
        "period": {
          "start": "2025-06-26",
          "end": "2025-06-26"
        },
        "location": [
          {
            "location": {
              "display": "FHIR Test Location"
            }
          }
        ]
      },
      "search": {
        "mode": "match"
      }
    }
  ]
}
```


Change log

Epic Version | Description | Type
November 2026 | Encounter.participant.individual can now contain a reference to a PractitionerRole resource. A PractitionerRole reference is sent when a provider specialty or provider type is available; otherwise, a Practitioner reference is sent as before. | Breaking change

36.1.7 Encounter.Search (Patient Chart) (R4)

File: site/apis/36-Workflow-Patient-Management/1-R4/909-Encounter-Search-Patient-Chart-R4.html
Epic API ID | 909
FHIR version | R4

Categories | Workflow Patient Management
API type | USCDI
A la carte | Industry-Standard Level 1 API
USCDI | Yes
Available in inpatient and other contexts | Yes
ONC certification products | EpicCare Ambulatory Base, EpicCare Inpatient Base
ONC certification versions | August 2019
HTTP method | GET
URL template |
/api/FHIR/R4/Encounter?class={class}&date={date}&identifier={identifier}&onlyscannable={onlyscannable}&patient={patient}&subject={subject}
Supports OAuth 2.0 | True
Supported user types | Backend Systems and Non-OAuth 2.0, Clinicians or Administrative Users, Patients
Performs scope validation | False
Source | https://fhir.epic.com/Specifications?api=909

Description

The Encounter (Patient Chart) resource defines the setting where patient care takes place. This includes ambulatory, inpatient, emergency, home health, and virtual encounters.

This web service returns all inpatient encounters that meet the search criteria, but only returns outpatient encounters once they have been checked in. Upcoming appointments are not returned. You should instead use the Appointment resource to search for future appointments.

Remarks

You shouldn't use the Encounter resource to store upcoming appointment information. Use the Appointment resource instead. Encounter IDs are not valid until the encounter has started.

Starting in the November 2021 version of Epic, the _revInclude parameter can be used to include AuditEventinformation with this resource, which indicates the history of modifications to a patient’s encounter care team.

Request parameters

Name | Type | Optional | Array | Cardinality | Description
_count | number | Optional | Yes | | Number of results per page.
_id | token | Optional | Yes | | FHIR resource IDs for the desired resources. Can be used in combination with _count, _include, and _revInclude. All others are ignored.
_include | string | Optional | Yes | | Used to indicate which referenced resources to include in the search bundle.
_revinclude | string | Optional | Yes | | Used to include Provenance or AuditEvent resources that refer to search results, when available.
class | token | Optional | Yes | | Classification of the patient encounter. Formatted as <system>|<code>. For organizations not in the Netherlands, the <system> value must be urn:oid:1.2.840.114350.1.72.1.7.7.10.696784.13260 Coordinate with the Epic organization on which <code> values make the most sense to filter on based on your use case. For organizations in the Netherlands, this refers to the ACT encounter code. The <system> value must be http://hl7.org/fhir/v3/ActCode. Valid <code> values include: AMB IMP EMER OTHER
date | date | Optional | Yes | | A date range that the encounter takes place. Can be provided as either a date or a dateTime. A time zone can be specified using ISO 8601 formatting. Refer to this document on how to format a date or dateTime range. If no time zone is provided, UTC is assumed. When specifying a dateTime range, you can use different time zones for the lower and upper bound.
identifier | token | Optional | Yes | | Identifier by which this encounter is known in the format <system>|<identifier>. Valid <system> values are listed below, and vary at different Epic organizations: OID for Epic Contact Serial Number (CSN) item OID for Epic Billing Number Item OID for External Visit ID item OID for Visit Level Epic Identity ID record
onlyscannable | token | Optional | Yes | | If "true", only scannable encounters are returned in the response. This parameter may only be used as part of a user-facing SMART on FHIR EHR Launch workflow. It primarily facilitates front end scanning workflows that require a list of encounters to which a user is allowed to scan to in Epic scanning workflows.
patient | reference | Conditional | Yes | | Reference to a patient resource. Either patient or subject are required for the request to succeed. If both are provided, they must match exactly.
subject | reference | Conditional | Yes | | Reference to a patient resource. Either patient or subject are required for the request to succeed. if both are provided, they must match exactly.

Request parameters (post-filtered search parameters)

Name | Type | Optional | Array | Cardinality | Description
diagnosis | reference | Optional | Yes | | The principal problem for the hospital encounter, as a FHIR Condition reference. Used only for hospital encounters.
episode-of-care | reference | Optional | Yes | | The episode associated with the encounter.
location | reference | Optional | Yes | | Represents the physical or virtual space the encounter occured in. This can be a bed, room, department, location, and/or service area.
location-period | date | Optional | Yes | | Time period during which the patient was present at the location.
participant | reference | Optional | Yes | | A participant that was involved in the target encounter. This can include but is not limited to: attending provider, referring provider, interpreters, and appointment providers.
participant-type | token | Optional | Yes | | Role of participant in encounter. The values for this element include: ADM - admitting provider ATND - attending provider PART - ambulatory participants REF - referring provider translator - interpreters OTTM - other treatment team members.
part-of | reference | Optional | Yes | | Another encounter that the encounter being queried for is part of. Reference to an Encounter resource.
practitioner | reference | Optional | Yes | | A FHIR Practitioner ID for a practitioner that was part of the encounter. This can include but is not limited to: attending provider, referring provider, and appointment providers.
reason-code | token | Optional | Yes | | The reason for the visit.
status | token | Optional | Yes | | The encounter status. Full list of statuses can be found here.

type | token | Optional | Yes | | The Encounter's types. Any values that are populated below can be queried: Epic's Contact Type Patient Class Appointment Visit Type Hospital Admission Type Hospital Level of Service

Response elements

Name | Type | Optional | Array | Cardinality | Description

Encounter (R4) | Resource | | | | A single Encounter resource.

Encounter (R4).account | Reference | | Yes | 0..* | The hospital account associated with an encounter. Includes an identifier for the hospital account, not a full reference to a FHIR Account resource.

Encounter (R4).class | Coding | | | 1..1 | Classification of the patient encounter. For organizations in the Netherlands, this field represents the ACT encounter code. For organizations in Denmark, this field represents the patient class.

Encounter (R4).diagnosis | BackboneElement | | Yes | 0..1 | Reference to a Condition (Problem) resource. Returns the principal problem for the hospital encounter. Used only for hospital encounters.

Encounter (R4).diagnosis.condition | Reference | | | 1..1 | FHIR Condition reference.

Encounter (R4).episodeOfCare | Reference | | Yes | 0..* | The episode associated with the encounter.

Encounter (R4).extension (accidentrelated) (also: extension (accidentrelated)) | Extension | | Yes | 0..1 | If true, this encounter is accident-related. URL: http://open.epic.com/FHIR/StructureDefinition/extension/accidentrelated

Encounter (R4).extension (is-scannable-encounter) (also: extension (is-scannable-encounter)) | Extension | | Yes | 0..1 | If true, this encounter is scannable. URL: http://open.epic.com/FHIR/StructureDefinition/extension/is-scannable-encounter

Encounter (R4).hospitalization | BackboneElement | | | 0..1 | Details about the hospital admission.

Encounter (R4).hospitalization.admitSource | CodeableConcept | | | 0..1 | The source of the patient’s admission, such as a physician referral.

Encounter (R4).hospitalization.destination | Reference | | | 0..1 | Location to which the patient is discharged. Reference to a Location resource.

Encounter (R4).hospitalization.dischargeDisposition | CodeableConcept | | | 0..1 | Category or kind of location after discharge.

Encounter (R4).hospitalization.extension (ip-admit-datetime) (also: extension (ip-admit-datetime)) | Extension | | Yes | 0..1 | The date and time the patient was admitted as inpatient. URL: http://open.epic.com/FHIR/StructureDefinition/extension/ip-admit-datetime

Encounter (R4).hospitalization.extension (observation-datetime) (also: extension (observation-datetime)) | Extension | | Yes | 0..1 | The date and time the patient was admitted for observation. URL: http://open.epic.com/FHIR/StructureDefinition/extension/observation-datetime

Encounter (R4).hospitalization.origin | Reference | | | 0..1 | The location from which the patient came before admission.

Encounter (R4).hospitalization.reAdmission | CodeableConcept | | | 0..1 | The type of hospital re-admission that has occurred (if any). If the value is absent, then this is not identified as a readmission.

Encounter (R4).id | id | | | 1..1 | The Encounter FHIR ID.

Encounter (R4).identifier | Identifier | | Yes | 1..* | The identifiers for the encounter. Including the Epic Contact Serial Number (CSN) and any other external identifiers.

Encounter (R4).location | BackboneElement | | Yes | 0..* | An array of locations representing the physical or virtual space the encounter occured in. This can include the following: bed, room, department, location, and/or service area.

Encounter (R4).location.location | Reference | | | 1..* | Location the encounter takes place. Can reference a Location resource if the location is a room, department, location, or service area. Beds are not represented by FHIR location resources.

Encounter (R4).location.location.display | String | | | 1..1 | The display name of the location.

Encounter (R4).location.location.identifier | Identifier | | | 0..1 | The identifiers associated with the location. Only returned for beds, as they are not Location references.

Encounter (R4).location.location.reference | String | | | 0..1 | Reference to a Location resource. Not returned for beds.

Encounter (R4).location.period | Period | | | 0..1 | Time period during which the patient was present at the location. This is only populated for departments.

Encounter (R4).location.physicalType | CodeableConcept | | | 0..1 | Returned for beds and rooms to describe the type of physical space represented by the Location object. Rooms are represented as ro Beds are represented as bd

Encounter (R4).participant | BackboneElement | | Yes | 1..* | List of participants involved in the encounter. This can include but is not limited to: Attending Provider Referring Provider Interpreters Appointment Providers

Encounter (R4).participant.extension (specialty) (also: extension (specialty)) | Extension | | Yes | 0..1 | Specialty of the participant in the encounter. URL: http://open.epic.com/FHIR/StructureDefinition/extension/specialty

Encounter (R4).participant.extension (team-name) (also: extension (team-name)) | Extension | | Yes | 0..1 | Team name of the participant in the encounter. URL: http://open.epic.com/FHIR/StructureDefinition/extension/team-name

Encounter (R4).participant.individual | Reference | | | 1..1 | Reference to the Practitioner resource representing the participant.

Encounter (R4).participant.period | Period | | | 0..1 | Period of time during the encounter that the participant participated. This is populated for appointment providers. No period is populated for admitting and referring providers.

Encounter (R4).participant.type | CodeableConcept | | Yes | 0..1 | Role of participant in encounter.

Encounter (R4).participant.type.coding | Coding | | Yes | 0..1 | Coding for the participant type.

Encounter (R4).participant.type.coding.code | String | | | 1..1 | This element is returned as follows: ADM for admitting provider ATND for attending provider DIS for discharge provider REF for referring provider OTTM for other treatment team member PART for staff participant Translator for interpreter

Encounter (R4).participant.type.coding.display | String | | | 1..1 | The display name for the participant type. Returns the following: admitter for admitting providers discharger for discharge providers attender for attending providers referrer for referring providers losAuthorizingPhysician for LOS authorizing providers Participation for appointment staff Translator for interpreter Relationship to patient for treatment team members

Encounter (R4).participant.type.coding.system | String | | | 1..1 | Returns http://hl7.org/fhir/v3/ParticipationType except for interpreters, which returns http://terminology.hl7.org/CodeSystem/participant-type.

Encounter (R4).participant.type.text | String | | | 1..1 | The display name for the participant type. Returns the following: admitter for admitting providers discharger for discharge providers attender for attending providers referrer for referring providers losAuthorizingPhysician for LOS authorizing providers Participation for appointment staff Translator for interpreter Relationship to patient for treatment team members

Encounter (R4).partOf | Reference | | | 0..1 | Reference to another Encounter resource this Encounter is part of. This can be the hospital encounter that a surgical encounter is linked to, or the inpatient encounter that serves as the originating encounter for related hospital outpatient visits.

Encounter (R4).period | Period | | | 0..1 | The start and end date/time of the encounter. The specific start and end times vary based on the type of encounter. Encounters without a specific start or end time are returned with midnight as the start or end time.

Encounter (R4).period.end | String | | | 0..1 | The end date and time.

Encounter (R4).period.start | String | | | 0..1 | The start date and time.

Encounter (R4).priority | CodeableConcept | | | 0..1 | Indicates the urgency of the encounter.

Encounter (R4).reasonCode | CodeableConcept | | Yes | 0..* | The reason for visit. SNOMED codes are returned with a system of http://snomed.info/sct.

Encounter (R4).serviceProvider | Reference | | | 0..* | Reference to the Organization resource representing the service area for the encounter based on facility hierarchy. This element is returned starting in the February 2025 version of Epic, and back to the May 2024 version of Epic with special update.

Encounter (R4).serviceType | CodeableConcept | | | 0..1 | Type of service associated with this encounter. Examples include Surgery or Internal Medicine.

Encounter (R4).status | code | | | 1..1 | The encounter status. Full list of statuses can be found here.

Encounter (R4).subject | Reference | | | 1..1 | Reference to the Patient resource who was the subject of the encounter.

Encounter (R4).type | CodeableConcept | | Yes | 0..* | The encounter's types. Any values that are populated below are returned: Epic's Contact Type Patient Class Appointment Visit Type Hospital Admission Type Hospital Level of Service

Sample request

```
GET https://hostname/instance/api/FHIR/R4/Encounter?patient=eJcZl4T3ut30rE-k0LLiYyw3
```

Sample response


```
{
  "resourceType": "Bundle",
  "type": "searchset",
  "total": 1,
  "link": [
    {
      "relation": "self",
      "url": "https://hostname/instance/api/FHIR/R4/Encounter?patient=eJcZl4T3ut30rE-k0LLiYyw3"
    }
  ],
  "entry": [
    {
      "link": [
        {
          "relation": "self",
          "url": "https://hostname/instance/api/FHIR/R4/Encounter/eVIoWcsfIUyz3vHqv31zXyzf43WfSbVBBOXKsd87s3EU3"
        }
      ],
      "fullUrl": "https://hostname/instance/api/FHIR/R4/Encounter/eVIoWcsfIUyz3vHqv31zXyzf43WfSbVBBOXKsd87s3EU3",
      "resource": {
        "resourceType": "Encounter",
        "id": "eVIoWcsfIUyz3vHqv31zXyzf43WfSbVBBOXKsd87s3EU3",
        "identifier": [
          {
            "use": "usual",
            "system": "urn:oid:1.2.840.114350.1.13.861.1.7.3.698084.8",
            "value": "10000141675"
          }
        ],
        "status": "in-progress",
        "class": {
          "system": "urn:oid:1.2.840.114350.1.72.1.7.7.10.696784.13260",
          "code": "13",
          "display": "Support OP Encounter"
        },
        "type": [
          {
            "coding": [
              {
                "system": "urn:oid:1.2.840.114350.1.13.861.1.7.10.698084.30",
                "code": "101",
                "display": "Office Visit"
              }
            ],
            "text": "Office Visit"
          }
        ],
        "subject": {
          "reference": "Patient/eJcZl4T3ut30rE-k0LLiYyw3",
          "display": "Some One Jr."
        },
        "period": {
          "start value": "2021-08-20R15:15:00Z"
        },
        "diagnosis": [
          {
            "condition": {
              "reference": "Condition/e2kxGmpjr2c4S30KrixlhOW.WDPG0KtcL4PfK5NomBJM3",
              "display": "Acute hepatitis C with hepatic coma"
            }
          }
        ],
        "participant": [
          {
            "type": [
              {
                "coding": [
                  {
                    "system": "http://terminology.hl7.org/CodeSystem/v3-ParticipationType",
```

```
                    "code": "PART",
                    "display": "Participation"
                  }
                ],
                "text": "Participation"
              }
            ],
            "period": {
              "start": "2019-02-28T17:15:47Z"
            },
            "individual": {
              "reference": "Practitioner/e89p8GCwg7wvke-vxglQ0WA3",
              "display": "Firstname Lastname, MD"
            }
          }
        ],
        "location": [
          {
            "location": {
              "reference": "Location/eMRHhr1Ry-G-RV0fqAju6kA3",
              "display": "Initial Department"
            }
          }
        ],
        "serviceProvider": {
          "reference": "Organization/ePUQySFaW.ofXm2GhaXRMDA3",
          "display": "FACILITY"
        }
      },
      "search": {
        "mode": "match"
      }
    }
  ]
}
```


Change log

Epic Version | Description | Type
February 2024 | Code system used in participant.type.coding.system has been changed: Old value Possible new values
http://hl7.org/fhir/v3/ParticipationType http://terminology.hl7.org/CodeSystem/v3-ParticipationType Or
http://terminology.hl7.org/CodeSystem/participant-type | Breaking change
Old value | Possible new values
http://hl7.org/fhir/v3/ParticipationType | http://terminology.hl7.org/CodeSystem/v3-ParticipationType Or
http://terminology.hl7.org/CodeSystem/participant-type
November 2022 | Code systems for the following code sets now return a URL in place of an OID: ActCode, ICD-10-CM, ICD-10-CA, ICD-10-NL, SNOMED System URL OID ActCode STU3: http://hl7.org/fhir/v3/ActCode R4: http://terminology.hl7.org/CodeSystem/v3-ActCode 2.16.840.1.113883.5.4 ICD-10-CM http://hl7.org/fhir/sid/icd-10-cm 2.16.840.1.113883.6.90 ICD-10-CA http://hl7.org/fhir/sid/icd-10-ca 2.16.840.1.113883.6.94 ICD-10-NL http://hl7.org/fhir/sid/icd-10-nl 2.16.840.1.113883.6.3.2 SNOMED http://snomed.info/sct 2.16.840.1.113883.6.96 | Breaking change
System | URL | OID
ActCode | STU3: http://hl7.org/fhir/v3/ActCode R4: http://terminology.hl7.org/CodeSystem/v3-ActCode | 2.16.840.1.113883.5.4
ICD-10-CM | http://hl7.org/fhir/sid/icd-10-cm | 2.16.840.1.113883.6.90
ICD-10-CA | http://hl7.org/fhir/sid/icd-10-ca | 2.16.840.1.113883.6.94
ICD-10-NL | http://hl7.org/fhir/sid/icd-10-nl | 2.16.840.1.113883.6.3.2
SNOMED | http://snomed.info/sct | 2.16.840.1.113883.6.96

36.1.8 ReviewCollection.Create (R4)

File: site/apis/36-Workflow-Patient-Management/1-R4/1026-ReviewCollection-Create-R4.html
Epic API ID | 1026
FHIR version | R4
Categories | Workflow Patient Management
API type | Epic Public
API group | Utilization Management integration
USCDI | No
HTTP method | POST
URL template | /api/FHIR/R4/ReviewCollection
Supports OAuth 2.0 | True
Supported user types | Backend Systems and Non-OAuth 2.0, Clinicians or Administrative Users
Performs scope validation | False
Source | https://fhir.epic.com/Specifications?api=1026

Request parameters

Name | Type | Optional | Array | Cardinality | Description
ReviewCollection | ReviewCollection | False
ReviewCollection.associatedAuthorization | Reference | True | | | A FHIR Claim reference. Authorization this resource is associated with, if any.
ReviewCollection.copyright | String | True | | | Copyright text that should be included with this review collection.

ReviewCollection.encounter | Reference | Required in a provider context. | | | Patient encounter for which reviews in the review collection were conducted.
ReviewCollection.identifier | Identifier | False | | | Unique identifier of this review collection within the criteria review system that created it.
ReviewCollection.isDeleted | Boolean | True | | | Whether or not this review collection was deleted. By default, it is assumed that the review collection is not deleted.
ReviewCollection.note | Annotation | True | Yes | | Notes that apply to this review collection.
ReviewCollection.patient | Reference | False | | | Patient for which reviews in the review collection were conducted.
ReviewCollection.review | Reference | True | Yes | | Reviews that are part of this review collection.
ReviewCollection.reviewer | Reference | Required with a solicited call. | | | User who last updated this review collection. Must be a valid and active user.
ReviewCollection.templateID | Identifier | True | | | Identifier of template that review collection was created from.
ReviewCollection.templateName | String | True | | | Human-readable name of the template in the criteria review software from which this review collection was created.
ReviewCollection.templateVersion | String | True | | | Version of the template in criteria review software from which this review collection was created.
ReviewCollection.title | String | False | | | Title of this review collection.
ReviewCollection.userSessionToken | String | Required for all solicited calls. | | | Identifier for the user session in which this review collection was created.

Response elements

Name | Type | Optional | Array | Cardinality | Description
OperationOutcome | OperationOutcome | False
OperationOutcome.contained | ResourceContainer | False | Yes | | A container for a single FHIR resource.
OperationOutcome.extension | Extension | False | Yes
OperationOutcome.id | String | False
OperationOutcome.implicitRules | String | False
OperationOutcome.issue | Issue | False | Yes
OperationOutcome.language | String | False
OperationOutcome.meta | Meta | False
OperationOutcome.modifierExtension | Extension | False | Yes
OperationOutcome.text | Narrative | False
ReviewCollection | ReviewCollection | False

Sample request

```
<ReviewCollection xmlns="http://hl7.org/fhir">
  <title value="Collection Title"/>
  <userSessionToken value="843q9gjg4ha"/>
  <templateName value="Collection Template"/>
  <templateVersion value="1.1"/>
  <isDeleted value="false"/>
  <copyright value="© Copyright 1995"/>
  <patient>
    <reference value="Patient/eb8ef41wb.a.b.LbkPQmI3A3"/>
    <display value="Example, Felicia"/>
  </patient>
  <encounter>
    <reference value="Encounter/eJvA2QM307qSWj6pIk.lOqxBmLXvAppIEdwNxX6crqkY3"/>
  </encounter>
  <reviewer>
    <reference value="Practitioner/eSNO5tMy06DcMPHcvMjFhsQ3"/>
    <display value="David Example, MD"/>
  </reviewer>
  <identifier>
    <value value="123456789"/>
  </identifier>
  <templateID>
    <system value="acmevendor.com"/>
    <value value="123456789"/>
  </templateID>
  <note>
    <text value="Collection Note Text"/>
  </note>
  <review>
    <reference value="CriteriaReview/em.1ytr8NtbD3e8erevnehA3"/>
  </review>
</ReviewCollection>
```

Sample response

```
N/A
```

36.1.9 ReviewCollection.Read (R4)

File: site/apis/36-Workflow-Patient-Management/1-R4/1027-ReviewCollection-Read-R4.html
Epic API ID | 1027
FHIR version | R4
Categories | Workflow Patient Management
API type | Epic Public
API group | Utilization Management integration

USCDI | No
HTTP method | GET
URL template | /api/FHIR/R4/ReviewCollection/{ID}
Supports OAuth 2.0 | True
Supported user types | Backend Systems and Non-OAuth 2.0, Clinicians or Administrative Users
Performs scope validation | False
Source | https://fhir.epic.com/Specifications?api=1027

Request parameters

Name | Type | Optional | Array | Cardinality | Description
ID | String | False

Response elements

Name | Type | Optional | Array | Cardinality | Description
OperationOutcome | OperationOutcome | False
OperationOutcome.contained | ResourceContainer | False | Yes | | A container for a single FHIR resource.
OperationOutcome.extension | Extension | False | Yes
OperationOutcome.id | String | False
OperationOutcome.implicitRules | String | False
OperationOutcome.issue | Issue | False | Yes
OperationOutcome.language | String | False
OperationOutcome.meta | Meta | False
OperationOutcome.modifierExtension | Extension | False | Yes
OperationOutcome.text | Narrative | False
ReviewCollection | ReviewCollection | False
ReviewCollection.authorizationRequest | Reference | True | | | A FHIR Claim reference. Authorization this resource is associated with, if any.
ReviewCollection.encounter | Reference | Returned only for review collections in a provider context. | | | A FHIR reference.
ReviewCollection.id | String | False
ReviewCollection.identifier | Identifier | False | | | Generic identifier.
ReviewCollection.isDeleted | Boolean | True | | | Whether or not this review collection was deleted. By default, it is assumed that the review collection is not deleted.
ReviewCollection.note | Annotation | False | Yes | | Notes that apply to this review collection.
ReviewCollection.patient | Reference | False | | | A FHIR reference.
ReviewCollection.review | Reference | False | Yes | | Reviews that are part of this collection.
ReviewCollection.reviewer | Reference | False | | | User who last updated this review collection.
ReviewCollection.templateID | Identifier | False | | | Identifier of template that review collection was created from.
ReviewCollection.templateName | String | False | | | Human-readable name of the template in the criteria review software from which this review collection was created.
ReviewCollection.templateVersion | String | False | | | Version of the template in criteria review software from which this review collection was created.
ReviewCollection.title | String | False | | | Title of this review collection.

Sample request

```
https://hostname/instance/api/FHIR/R4/ReviewCollection/123456789
```

Sample response

```
<ReviewCollection xmlns="http://hl7.org/fhir">
  <title value="Collection Title"/>
  <templateName value="Collection Template"/>
  <templateVersion value="1.1"/>
  <isDeleted value="false"/>
  <copyright value="© Copyright 1995"/>
  <patient>
    <reference value="Patient/eb8ef41wb.a.b.LbkPQmI3A3"/>
    <display value="Example, Felicia"/>
  </patient>
  <encounter>
    <reference value="Encounter/eJvA2QM307qSWj6pIk.lOqxBmLXvAppIEdwNxX6crqkY3"/>
  </encounter>
  <reviewer>
    <reference value="Practitioner/eSNO5tMy06DcMPHcvMjFhsQ3"/>
    <display value="David Example, MD"/>
  </reviewer>
  <identifier>
    <value value="123456789"/>
  </identifier>
  <templateID>
    <system value="acmevendor.com"/>
    <value value="123456789"/>
  </templateID>
  <note>
    <text value="Collection Note Text"/>
  </note>
  <review>
    <reference value="CriteriaReview/em.1ytr8NtbD3e8erevnehA3"/>
```

```
  </review>
</ReviewCollection>
```

36.1.10 ReviewCollection.Update (R4)

File: site/apis/36-Workflow-Patient-Management/1-R4/1028-ReviewCollection-Update-R4.html
Epic API ID | 1028
FHIR version | R4
Categories | Workflow Patient Management
API type | Epic Public
API group | Utilization Management integration
USCDI | No
HTTP method | PUT
URL template | api/FHIR/R4/ReviewCollection
Supports OAuth 2.0 | True
Supported user types | Backend Systems and Non-OAuth 2.0, Clinicians or Administrative Users
Performs scope validation | False
Source | https://fhir.epic.com/Specifications?api=1028

Request parameters

Name | Type | Optional | Array | Cardinality | Description
ID | String | False
ReviewCollection | ReviewCollection | False
ReviewCollection.authorizationRequest | Reference | True | | | A FHIR Claim reference. Authorization this resource is associated with, if any.
ReviewCollection.copyright | String | True | | | Copyright text that should be included with this review collection.
ReviewCollection.encounter | Reference | Required in a provider context. | | | Patient encounter for which reviews in the review collection were conducted.
ReviewCollection.identifier | Identifier | False | | | Unique identifier of this review collection within the criteria review system that created it.
ReviewCollection.isDeleted | Boolean | True | | | Whether or not this review collection was deleted. By default, it is assumed that the review collection is not deleted.
ReviewCollection.note | Annotation | True | Yes | | Notes that apply to this review collection.
ReviewCollection.patient | Reference | False | | | Patient for which reviews in the review collection were conducted.
ReviewCollection.review | Reference | True | Yes | | Reviews that are part of this review collection.
ReviewCollection.reviewer | Reference | Required with a solicited call. | | | User who last updated this review collection.
ReviewCollection.templateID | Identifier | True | | | Identifier of template that review collection was created from.
ReviewCollection.templateName | String | True | | | Human-readable name of the template in the criteria review software from which this review collection was created.
ReviewCollection.templateVersion | String | True | | | Version of the template in criteria review software from which this review collection was created.
ReviewCollection.title | String | False | | | Title of this review collection.
ReviewCollection.userSessionToken | String | Required for all solicited calls. | | | Identifier for the user session in which this review collection was created.

Response elements

Name | Type | Optional | Array | Cardinality | Description
OperationOutcome | OperationOutcome | False
OperationOutcome.contained | ResourceContainer | False | Yes | | A container for a single FHIR resource.
OperationOutcome.extension | Extension | False | Yes
OperationOutcome.id | String | False
OperationOutcome.implicitRules | String | False
OperationOutcome.issue | Issue | False | Yes
OperationOutcome.language | String | False
OperationOutcome.meta | Meta | False
OperationOutcome.modifierExtension | Extension | False | Yes
OperationOutcome.text | Narrative | False

Sample request

```
<ReviewCollection xmlns="http://hl7.org/fhir">
  <title value="Collection Title"/>
  <userSessionToken value="843q9gjg4ha"/>
  <templateName value="Collection Template"/>
  <templateVersion value="1.1"/>
  <isDeleted value="false"/>
  <copyright value="© Copyright 1995"/>
  <patient>
    <reference value="Patient/eb8ef41wb.a.b.LbkPQmI3A3"/>
    <display value="Example, Felicia"/>
  </patient>
  <encounter>
    <reference value="Encounter/eJvA2QM307qSWj6pIk.lOqxBmLXvAppIEdwNxX6crqkY3"/>
  </encounter>
  <reviewer>
    <reference value="Practitioner/eSNO5tMy06DcMPHcvMjFhsQ3"/>
    <display value="David Example, MD"/>
  </reviewer>
```

```
  <identifier>
    <value value="123456789"/>
  </identifier>
  <templateID>
    <system value="acmevendor.com"/>
    <value value="123456789"/>
  </templateID>
  <note>
    <text value="Collection Note Text"/>
  </note>
  <review>
    <reference value="CriteriaReview/em.1ytr8NtbD3e8erevnehA3"/>
  </review>
</ReviewCollection>
```

Sample response

```
N/A
```

36.2 Workflow Patient Management: STU3

File: site/apis/36-Workflow-Patient-Management/2-STU3/index.html

* Encounter.Read (Patient Chart) (STU3)

* Encounter.Search (Patient Chart) (STU3)

36.2.1 Encounter.Read (Patient Chart) (STU3)

File: site/apis/36-Workflow-Patient-Management/2-STU3/471-Encounter-Read-Patient-Chart-STU3.html
Epic API ID | 471
FHIR version | STU3
Categories | Workflow Patient Management
API type | USCDI
A la carte | Industry-Standard Level 1 API
USCDI | Yes
Available in inpatient and other contexts | Yes
ONC certification products | EpicCare Ambulatory Base, EpicCare Inpatient Base
ONC certification versions | Epic 2018
HTTP method | GET
URL template | api/FHIR/STU3/Encounter/{ID}
Supports OAuth 2.0 | True
Supported user types | Backend Systems and Non-OAuth 2.0, Clinicians or Administrative Users, Patients
Performs scope validation | False
Source | https://fhir.epic.com/Specifications?api=471

Description

The Encounter (Patient Chart) resource defines the setting where patient care takes place. This includes ambulatory, inpatient, emergency, home health, and virtual encounters.

Outpatient encounters are not valid until the patient has checked in. Upcoming appointments are not valid encounters.

Remarks

You shouldn't use the Encounter resource to store upcoming appointment information. Use the Appointment resource instead. Encounter IDs are not valid until the encounter has started.

Request parameters

Name | Type | Optional | Array | Cardinality | Description
ID | token | Required | | | The Encounter FHIR ID.

Response elements

Name | Type | Optional | Array | Cardinality | Description
Encounter (STU3) | Encounter | | | | A single Encounter resource.
Encounter (STU3).appointment | Reference | | | 0..1 | Reference to an Appointment resource. This element is populated if this encounter is or was scheduled from an appointment.
Encounter (STU3).class | Coding | | | 1..1 | Classification of the patient encounter. For organizations in the Netherlands, this field represents the ACT encounter code. For organizations in Denmark, this field represents the patient class.
Encounter (STU3).diagnosis | BackboneElement | | Yes | 0..1 | Reference to a Condition (Problem) resource. Returns the principal problem for the hospital encounter. Used only for hospital encounters.
Encounter (STU3).diagnosis.condition | Reference | | | 1..1 | FHIR Condition reference.
Encounter (STU3).hospitalization | BackboneElement | | | 0..1 | Details about the hospital admission.
Encounter (STU3).hospitalization.admitSource | CodeableConcept | | | 0..1 | The source of the patient’s admission, such as a physician referral.
Encounter (STU3).hospitalization.destination | Reference | | | 0..1 | Location to which the patient is discharged. Reference to a Location resource.
Encounter (STU3).hospitalization.dischargeDisposition | CodeableConcept | | | 0..1 | Category or kind of location after discharge.

Encounter (STU3).hospitalization.extension (ip-admit-datetime) (also: extension (ip-admit-datetime)) | Extension | | Yes | 0..1 | The date and time the patient was admitted as inpatient. URL: http://open.epic.com/FHIR/StructureDefinition/extension/ip-admit-datetime

Encounter (STU3).hospitalization.extension (observation-datetime) (also: extension (observation-datetime)) | Extension | | Yes | 0..1 | The date and time the patient was admitted for observation. URL: http://open.epic.com/FHIR/StructureDefinition/extension/observation-datetime

Encounter (STU3).hospitalization.origin | Reference | | | 0..1 | The location from which the patient came before admission.

Encounter (STU3).hospitalization.reAdmission | CodeableConcept | | | 0..1 | The type of hospital re-admission that has occurred, if any. If the value is absent, then this is not identified as a readmission.

Encounter (STU3).id | id | | | 1..1 | The Encounter FHIR ID.

Encounter (STU3).identifier | Identifier | | Yes | 1..* | The identifiers for the encounter. Including the Epic Contact Serial Number (CSN) and any other external identifiers.

Encounter (STU3).location | BackboneElement | | Yes | 0..* | Can return a department, unit, or service area. Department and location are determined dynamically depending on a variety of factors.

Encounter (STU3).location.location | Reference | | | 1..1 | Location the encounter takes place. Reference to a Location resource.

Encounter (STU3).location.location.display | String | | | 1..1 | The display name of the location.

Encounter (STU3).location.location.reference | String | | | 1..1 | Reference to a Location resource.

Encounter (STU3).location.period | Period | | | 0..1 | Time period during which the patient was present at the location. This is only populated for departments.

Encounter (STU3).participant | BackboneElement | | Yes | 1..* | List of participants involved in the encounter. This can include but is not limited to: Attending Provider Referring Provider Interpreters Appointment Providers

Encounter (STU3).participant.extension (specialty) (also: extension (specialty)) | Extension | | Yes | 0..1 | Specialty of the participant in the encounter. URL: http://open.epic.com/FHIR/StructureDefinition/extension/specialty

Encounter (STU3).participant.extension (team-name) (also: extension (team-name)) | Extension | | Yes | 0..1 | Team name of the participant in the encounter. URL: http://open.epic.com/FHIR/StructureDefinition/extension/team-name

Encounter (STU3).participant.individual | Reference | | | 1..1 | Reference to the Practitioner resource representing the participant.

Encounter (STU3).participant.period | Period | | | 0..1 | Period of time during the encounter that the participant participated. Can be returned for attending providers, treatment team members, and appointment staff.

Encounter (STU3).participant.type | CodeableConcept | | Yes | 0..1 | Role of participant in encounter.

Encounter (STU3).participant.type.coding | Coding | | Yes | 0..1 | Coding for the participant type.

Encounter (STU3).participant.type.coding.code | String | | | 1..1 | This element is returned as follows: ADM for admitting provider ATND for attending provider DIS for discharge provider REF for referring provider OTTM for other treatment team member PART for staff participant translator for interpreter

Encounter (STU3).participant.type.coding.display | String | | | 1..1 | The display name for the participant type. Returns the following: admitter for admitting providers discharger for discharge providers attender for attending providers referrer for referring providers losAuthorizingPhysician for LOS authorizing providers Participation for appointment staff Translator for interpreter Relationship to patient for treatment team members

Encounter (STU3).participant.type.coding.system | String | Required | | 1..1 | Returns http://hl7.org/fhir/v3/ParticipationType except for interpreters, which returns http://terminology.hl7.org/CodeSystem/participant-type.

Encounter (STU3).participant.type.text | String | | | 1..1 | The display name for the participant type. Returns the following: admitter for admitting providers discharger for discharge providers attender for attending providers referrer for referring providers losAuthorizingPhysician for LOS authorizing providers Participation for appointment staff Translator for interpreter Relationship to patient for treatment team members

Encounter (STU3).partOf | Reference | | | 0..1 | Reference to another Encounter this Encounter is part of. This can be the hospital encounter that a surgical encounter is linked to, or the inpatient encounter that serves as the originating encounter for related hospital outpatient visits.

Encounter (STU3).period | Period | | | 0..1 | The start and end time of the encounter. The specific start and end times vary based on the type of encounter. Encounters without a specific start or end time are returned with midnight as the start or end time.

Encounter (STU3).period.end | String | | | 0..1 | The end date and time.

Encounter (STU3).period.start | String | | | 0..1 | The start date and time.

Encounter (STU3).priority | CodeableConcept | | | 0..1 | Indicates the urgency of the encounter.

Encounter (STU3).reason | CodeableConcept | | Yes | 0..* | The reason for visit. SNOMED codes are returned with a system of http://snomed.info/sct.

Encounter (STU3).serviceProvider | Reference | | | 0..1 | Reference to the Organization resource representing the service area for the encounter based on facility hierarchy. This element is returned starting in the February 2025 version of Epic, and back to the May 2024 version of Epic with special update.

Encounter (STU3).status | code | | | 1..1 | The encounter status. Full list of statuses can be found here.

Encounter (STU3).subject | Reference | | | 1..1 | Reference to the Patient resource who was the subject of the encounter.

Encounter (STU3).type | CodeableConcept | | Yes | 0..* | The encounter's types. Any values that are populated below are returned: Epic's Contact Type Patient Class Appointment Visit Type Hospital Admission Type Hospital Level of Service

Sample request

```
GET https://hostname/instance/api/FHIR/STU3/Encounter/eqmalKplzBwI7LnGrAcc9yKGAy.1ekJy25ierCAWx8bc3
```

Sample response


```
{
  "resourceType": "Encounter",
  "id": "eqmalKplzBwI7LnGrAcc9yKGAy.1ekJy25ierCAWx8bc3",
  "identifier": [
    {
      "use": "usual",
      "system": "urn:oid:1.2.840.114350.1.13.5325.1.7.3.698084.8",
      "value": "10004273531"
    }
  ],
  "status": "in-progress",
  "class": {
    "system": "urn:oid:1.2.840.114350.1.72.1.7.7.10.696784.13260",
    "code": "3",
    "display": "Admission"
  },
```

```
"type": [
  {
    "coding": [
      {
        "system": "urn:oid:1.2.840.114350.1.13.5325.1.7.10.698084.10110",
        "code": "1",
        "display": "Inpatient"
      }
    ],
    "text": "Inpatient"
  },
  {
    "coding": [
      {
        "system": "urn:oid:1.2.840.114350.1.13.5325.1.7.10.698084.30",
        "code": "3",
        "display": "Hospital Encounter"
      }
    ],
    "text": "Hospital Encounter"
  },
  {
    "coding": [
      {
        "system": "http://snomed.info/sct",
        "code": "32485007",
        "display": "Hospital admission"
      }
    ],
    "text": "Hospital admission"
  },
  {
    "coding": [
      {
        "system": "urn:oid:1.2.840.114350.1.13.5325.1.7.10.698084.18875",
        "code": "1",
        "display": "Inpatient"
      }
    ],
    "text": "Inpatient"
  }
],
"subject": {
  "reference": "https://hostname/instance/api/FHIR/STU3/Patient/erridPPePwvZcVdug9fsUvw3",
  "display": "Patient, Test"
},
"participant": [
  {
    "type": [
      {
        "coding": [
          {
            "system": "http://hl7.org/fhir/v3/ParticipationType",
            "code": "ADM",
            "display": "admitter"
          }
        ],
        "text": "admitter"
      }
    ],
    "individual": {
      "reference": "hostname/instance/api/FHIR/STU3/Practitioner/eTr5mlAR9svkW-JXbbYGUWQ3",
      "display": "Test Provider, MD"
    }
  },
  {
    "type": [
      {
        "coding": [
          {
            "system": "http://hl7.org/fhir/v3/ParticipationType",
            "code": "ATND",
            "display": "attender"
          }
        ],
        "text": "attender"
      }
    ],
    "period": {
      "start": "2024-10-15T21:33:39Z"
    },
    "individual": {
      "reference": "hostname/instance/api/FHIR/STU3/Practitioner/eRhB5No2Z8P6jEmZfgaqHvg3",
      "display": "Test Provider, MD"
    }
  }
],
"period": {
  "start": "2024-10-15T21:33:00Z"
```

```
  },
  "account": [
    {
      "identifier": {
        "system": "urn:oid:1.2.840.114350.1.13.5325.1.7.2.726582",
        "value": "4000020721"
      },
      "display": "Patient,Test"
    }
  ],
  "hospitalization": {
    "extension": [
      {
        "valueDateTime": "2024-10-15T21:33:00Z",
        "url": "http://open.epic.com/FHIR/StructureDefinition/extension/ip-admit-datetime"
      }
    ]
  },
  "location": [
    {
      "location": {
        "reference": "hostname/instance/api/FHIR/STU3/Location/eb4ovrrgI00SmjpUJirQPZg3",
        "display": "WI Test Psychology"
      },
      "period": {
        "start": "2024-10-15T21:33:00Z"
      }
    },
    {
      "location": {
        "reference": "hostname/instance/api/FHIR/STU3/Location/eb4ovrrgI00SmjpUJirQPZg3",
        "display": "WI Test Psychology"
      }
    },
    {
      "location": {
        "reference": "hostname/instance/api/FHIR/STU3/Location/eW-jIhJguqYkCAlGmqWa0aA3",
        "display": "WI TEST HOSPITALS"
      }
    }
  ],
  "serviceProvider": {
    "reference": "hostname/instance/api/FHIR/STU3/Organization/eRljlo648hrqb3HPlPbCv1A3",
    "display": "WI TEST HOSPITALS"
  }
}
```


Change log

Epic Version | Description | Type
November 2022 | Code systems for the following code sets now return a URL in place of an OID: ActCode, ICD-10-CM, ICD-10-CA, ICD-10-NL, SNOMED System URL OID ActCode STU3: http://hl7.org/fhir/v3/ActCode R4: http://terminology.hl7.org/CodeSystem/v3-ActCode 2.16.840.1.113883.5.4 ICD-10-CM http://hl7.org/fhir/sid/icd-10-cm 2.16.840.1.113883.6.90 ICD-10-CA http://hl7.org/fhir/sid/icd-10-ca 2.16.840.1.113883.6.94 ICD-10-NL http://hl7.org/fhir/sid/icd-10-nl 2.16.840.1.113883.6.3.2 SNOMED http://snomed.info/sct 2.16.840.1.113883.6.96 | Breaking change
System | URL | OID
ActCode | STU3: http://hl7.org/fhir/v3/ActCode R4: http://terminology.hl7.org/CodeSystem/v3-ActCode | 2.16.840.1.113883.5.4
ICD-10-CM | http://hl7.org/fhir/sid/icd-10-cm | 2.16.840.1.113883.6.90
ICD-10-CA | http://hl7.org/fhir/sid/icd-10-ca | 2.16.840.1.113883.6.94
ICD-10-NL | http://hl7.org/fhir/sid/icd-10-nl | 2.16.840.1.113883.6.3.2
SNOMED | http://snomed.info/sct | 2.16.840.1.113883.6.96

36.2.2 Encounter.Search (Patient Chart) (STU3)

File: site/apis/36-Workflow-Patient-Management/2-STU3/472-Encounter-Search-Patient-Chart-STU3.html
Epic API ID | 472
FHIR version | STU3
Categories | Workflow Patient Management
API type | USCDI
A la carte | Industry-Standard Level 1 API
USCDI | Yes
Available in inpatient and other contexts | Yes
ONC certification products | EpicCare Ambulatory Base, EpicCare Inpatient Base
ONC certification versions | Epic 2018
HTTP method | GET
URL template | /api/FHIR/STU3/Encounter?class={class}&date={date}&identifier={identifier}&patient={patient}&subject={subject}
Supports OAuth 2.0 | True
Supported user types | Backend Systems and Non-OAuth 2.0, Clinicians or Administrative Users, Patients
Performs scope validation | False
Source | https://fhir.epic.com/Specifications?api=472

Description

The Encounter (Patient Chart) resource defines the setting where patient care takes place. This includes ambulatory, inpatient, emergency, home health, and virtual encounters.

This web service returns all inpatient encounters that meet the search criteria, but only returns outpatient encounters once they have been checked in. Upcoming appointments are not returned. You should instead use the Appointment resource to search for future appointments.

Remarks

You shouldn't use the Encounter resource to store upcoming appointment information. Use the Appointment resource instead. Encounter IDs are not valid until the encounter has started.

Request parameters

Name | Type | Optional | Array | Cardinality | Description

_count | number | Optional | Yes | | Number of results per page.

_id | token | Optional | Yes | | FHIR resource IDs for the desired resources. Can be used in combination with _count and _include. All others are ignored.

_include | string | Optional | Yes | | Used to indicate which referenced resources to include in the search bundle.

class | token | Optional | Yes | | Classification of the patient encounter. Formatted as <system>|<code>. For organizations not in the Netherlands, the <system> value must be urn:oid:1.2.840.114350.1.72.1.7.7.10.696784.13260 Coordinate with the Epic organization on which <code> values make the most sense to filter on based on your use case. For organizations in the Netherlands, this refers to the ACT encounter code. The <system> value must be http://hl7.org/fhir/v3/ActCode. Valid <code> values include: AMB IMP EMER OTHER

date | date | Optional | Yes | | A date range that the encounter takes place. Can be provided as either a date or a dateTime. A time zone can be specified using ISO 8601 formatting. Refer to this document on how to format a date or dateTime range. If no time zone is provided, UTC is assumed. When specifying a dateTime range, you can use different different time zones for the lower and upper bound.

identifier | token | Optional | Yes | | Identifiers by which this encounter is known in the format <code system>|<code>. Valid <system> values are listed below, and vary at different Epic organizations: OID for Epic Contact Serial Number (CSN) item OID for Epic Billing Number Item OID for External Visit ID item OID for Visit Level Epic Identity ID record

patient | reference | Conditional | Yes | | Reference to a patient resource. Either patient or subject is required unless searching by _id.

subject | reference | Conditional | Yes | | Reference to a patient resource. Either patient or subject is required unless searching by _id.

Response elements

Name | Type | Optional | Array | Cardinality | Description

Encounter (STU3) | Encounter | | | | A single Encounter resource.

Encounter (STU3).appointment | Reference | | | 0..1 | Reference to an Appointment resource. This element is populated if this encounter is or was scheduled from an appointment.

Encounter (STU3).class | Coding | | | 1..1 | Classification of the patient encounter. For organizations in the Netherlands, this field represents the ACT encounter code. For organizations in Denmark, this field represents the patient class.

Encounter (STU3).diagnosis | BackboneElement | | Yes | 0..1 | Reference to a Condition (Problem) resource. Returns the principal problem for the hospital encounter. Used only for hospital encounters.

Encounter (STU3).diagnosis.condition | Reference | | | 1..1 | FHIR Condition reference.

Encounter (STU3).hospitalization | BackboneElement | | | 0..1 | Details about the hospital admission.

Encounter (STU3).hospitalization.admitSource | CodeableConcept | | | 0..1 | The source of the patient’s admission, such as a physician referral.

Encounter (STU3).hospitalization.destination | Reference | | | 0..1 | Location to which the patient is discharged. Reference to a Location resource.

Encounter (STU3).hospitalization.dischargeDisposition | CodeableConcept | | | 0..1 | Category or kind of location after discharge.

Encounter (STU3).hospitalization.extension (ip-admit-datetime) (also: extension (ip-admit-datetime)) | Extension | | Yes | 0..1 | The date and time the patient was admitted as inpatient. URL: http://open.epic.com/FHIR/StructureDefinition/extension/ip-admit-datetime

Encounter (STU3).hospitalization.extension (observation-datetime) (also: extension (observation-datetime)) | Extension | | Yes | 0..1 | The date and time the patient was admitted for observation. URL: http://open.epic.com/FHIR/StructureDefinition/extension/observation-datetime

Encounter (STU3).hospitalization.origin | Reference | | | 0..1 | The location from which the patient came before admission.

Encounter (STU3).hospitalization.reAdmission | CodeableConcept | | | 0..1 | The type of hospital re-admission that has occurred, if any. If the value is absent, then this is not identified as a readmission.

Encounter (STU3).id | id | | | 1..1 | The Encounter FHIR ID.

Encounter (STU3).identifier | Identifier | | Yes | 1..* | The identifiers for the encounter. Including the Epic Contact Serial Number (CSN) and any other external identifiers.

Encounter (STU3).location | BackboneElement | | Yes | 0..* | Can return a department, unit, or service area. Department and location are determined dynamically depending on a variety of factors.

Encounter (STU3).location.location | Reference | | | 1..1 | Location the encounter takes place. Reference to a Location resource.

Encounter (STU3).location.location.display | String | | | 1..1 | The display name of the location.

Encounter (STU3).location.location.reference | String | | | 1..1 | Reference to a Location resource.

Encounter (STU3).location.period | Period | | | 0..1 | Time period during which the patient was present at the location. This is only populated for departments.

Encounter (STU3).participant | BackboneElement | | Yes | 1..* | List of participants involved in the encounter. This can include but is not limited to: Attending Provider Referring Provider Interpreters Appointment Providers

Encounter (STU3).participant.extension (specialty) (also: extension (specialty)) | Extension | | Yes | 0..1 | Specialty of the participant in the encounter. URL: http://open.epic.com/FHIR/StructureDefinition/extension/specialty

Encounter (STU3).participant.extension (team-name) (also: extension (team-name)) | Extension | | Yes | 0..1 | Team name of the participant in the encounter. URL: http://open.epic.com/FHIR/StructureDefinition/extension/team-name

Encounter (STU3).participant.individual | Reference | | | 1..1 | Reference to the Practitioner resource representing the participant.

Encounter (STU3).participant.period | Period | | | 0..1 | Period of time during the encounter that the participant participated. Can be returned for attending providers, treatment team members, and appointment staff.

Encounter (STU3).participant.type | CodeableConcept | | Yes | 0..1 | Role of participant in encounter.

Encounter (STU3).participant.type.coding | Coding | | Yes | 0..1 | Coding for the participant type.

Encounter (STU3).participant.type.coding.code | String | | | 1..1 | This element is returned as follows: ADM for admitting provider ATND for attending provider DIS for discharge provider REF for referring provider OTTM for other treatment team member PART for staff participant translator for interpreter

Encounter (STU3).participant.type.coding.display | String | | | 1..1 | The display name for the participant type. Returns the following: admitter for admitting providers discharger for discharge providers attender for attending providers referrer for referring providers losAuthorizingPhysician for LOS authorizing providers Participation for appointment staff Translator for interpreter Relationship to patient for treatment team members

Encounter (STU3).participant.type.coding.system | String | Required | | 1..1 | Returns http://hl7.org/fhir/v3/ParticipationType except for interpreters, which returns http://terminology.hl7.org/CodeSystem/participant-type.

Encounter (STU3).participant.type.text | String | | | 1..1 | The display name for the participant type. Returns the following: admitter for admitting providers discharger for discharge providers attender for attending providers referrer for referring providers losAuthorizingPhysician for LOS authorizing providers Participation for appointment staff Translator for interpreter Relationship to patient for treatment team members

Encounter (STU3).partOf | Reference | | | 0..1 | Reference to another Encounter this Encounter is part of. This can be the hospital encounter that a surgical encounter is linked to, or the inpatient encounter that serves as the originating encounter for related hospital outpatient visits.

Encounter (STU3).period | Period | | | 0..1 | The start and end time of the encounter. The specific start and end times vary based on the type of encounter. Encounters without a specific start or end time are returned with midnight as the start or end time.

Encounter (STU3).period.end | String | | | 0..1 | The end date and time.

Encounter (STU3).period.start | String | | | 0..1 | The start date and time.

Encounter (STU3).priority | CodeableConcept | | | 0..1 | Indicates the urgency of the encounter.

Encounter (STU3).reason | CodeableConcept | | Yes | 0..* | The reason for visit. SNOMED codes are returned with a system of http://snomed.info/sct.

Encounter (STU3).serviceProvider | Reference | | | 0..1 | Reference to the Organization resource representing the service area for the encounter based on facility hierarchy. This element is returned starting in the February 2025 version of Epic, and back to the May 2024 version of Epic with special update.

Encounter (STU3).status | code | | | 1..1 | The encounter status. Full list of statuses can be found here.

Encounter (STU3).subject | Reference | | | 1..1 | Reference to the Patient resource who was the subject of the encounter.

Encounter (STU3).type | CodeableConcept | | Yes | 0..* | The encounter's types. Any values that are populated below are returned: Epic's Contact Type Patient Class Appointment Visit Type Hospital Admission Type Hospital Level of Service

Sample request

```
GET https://hostname/instance/api/FHIR/STU3/Encounter?patient=ehIpkoHmagKLnrzr.RBTUSw3
```

Sample response


```
{
  "resourceType": "Bundle",
  "type": "searchset",
  "total": 2,
  "link": [
    {
      "relation": "self",
      "url": "https://hostname/instance/api/FHIR/STU3/Encounter?Patient=ehIpkoHmagKLnrzr.RBTUSw3"
    }
  ],
  "entry": [
    {
      "link": [
        {
          "relation": "self",
          "url": "https://hostname/instance/api/FHIR/STU3/Encounter/ezV.wvzNZCgUW2HgOOcSlcKig.vjOn1Ein7DuiExXSw43"
        }
      ],
      "fullUrl": "https://hostname/instance/api/FHIR/STU3/Encounter/ezV.wvzNZCgUW2HgOOcSlcKig.vjOn1Ein7DuiExXSw43",
      "resource": {
        "resourceType": "Encounter",
        "id": "ezV.wvzNZCgUW2HgOOcSlcKig.vjOn1Ein7DuiExXSw43",
        "identifier": [
          {
            "use": "usual",
            "system": "urn:oid:1.2.840.114350.1.13.5325.1.7.3.698084.8",
            "value": "10004273091"
          }
        ],
        "status": "in-progress",
        "class": {
          "system": "urn:oid:1.2.840.114350.1.72.1.7.7.10.696784.13260",
          "code": "13",
          "display": "Support OP Encounter"
        },
        "type": [
          {
            "coding": [
              {
                "system": "urn:oid:1.2.840.114350.1.13.5325.1.7.10.698084.30",
                "code": "101",
                "display": "Office Visit"
              }
            ],
            "text": "Office Visit"
          },
          {
            "coding": [
              {
```

```
            "system": "http://snomed.info/sct",
            "code": "444971000124105",
            "display": "Annual wellness visit"
          }
        ],
        "text": "Annual wellness visit"
      }
    ],
    "subject": {
      "reference": "https://hostname/instance/api/FHIR/STU3/Patient/ehIpkoHmagKLnrzr.RBTUSw3",
      "display": "Patient, Test"
    },
    "participant": [
      {
        "type": [
          {
            "coding": [
              {
                "system": "http://hl7.org/fhir/v3/ParticipationType",
                "code": "PART",
                "display": "Participation"
              }
            ],
            "text": "Participation"
          }
        ],
        "individual": {
          "reference": "https://hostname/instance/api/FHIR/STU3/Practitioner/ePXvh8vspdDazyK46Y16elQ3",
          "display": "Test Provider, MD"
        }
      }
    ],
    "period": {
      "start": "2024-10-15",
      "end": "2024-10-15"
    },
    "location": [
      {
        "location": {
          "reference":
"https://hostname/instance/api/FHIR/STU3/Location/evpZXk5FxCfXvaTMaRQUgodcNEx1XjCKcKaXpS.-jrPw3",
          "display": "Test Department"
        }
      }
    ],
    "serviceProvider": {
      "reference":
"https://hostname/instance/api/FHIR/STU3/Organization/eQqNRyn-q2DZ3VE5vvqLTAILwevzTSRvYXr92te0wwWY3",
      "display": "Test Service Area"
    }
  },
  "search": {
    "mode": "match"
  }
},
{
  "link": [
    {
      "relation": "self",
      "url": "https://hostname/instance/api/FHIR/STU3/Encounter/eBg-hXZBXzn5aXF7qVIvuj5yzOd9t0b7wFlqTN41tmgM3"
    }
  ],
  "fullUrl": "https://hostname/instance/api/FHIR/STU3/Encounter/eBg-hXZBXzn5aXF7qVIvuj5yzOd9t0b7wFlqTN41tmgM3",
  "resource": {
    "resourceType": "Encounter",
    "id": "eBg-hXZBXzn5aXF7qVIvuj5yzOd9t0b7wFlqTN41tmgM3",
    "identifier": [
      {
        "use": "usual",
        "system": "urn:oid:1.2.840.114350.1.13.5325.1.7.3.698084.8",
        "value": "10004273084"

      }
    ],
    "status": "in-progress",
    "class": {
      "system": "urn:oid:1.2.840.114350.1.72.1.7.7.10.696784.13260",
      "code": "13",
      "display": "Support OP Encounter"
    },
    "type": [
      {
        "coding": [
          {
            "system": "urn:oid:1.2.840.114350.1.13.5325.1.7.10.698084.30",
            "code": "101",
            "display": "Office Visit"
          }
        ],
        "text": "Office Visit"
```

```
        },
        {
          "coding": [
            {
              "system": "http://snomed.info/sct",
              "code": "444971000124105",
              "display": "Annual wellness visit"
            }
          ],
          "text": "Annual wellness visit"
        }
      ],
      "subject": {
        "reference": "hostname/instance/api/FHIR/STU3/Patient/ehIpkoHmagKLnrzr.RBTUSw3",
        "display": "Patient, Test"
      },
      "participant": [
        {
          "type": [
            {
              "coding": [
                {
                  "system": "http://hl7.org/fhir/v3/ParticipationType",
                  "code": "PART",
                  "display": "Participation"
                }
              ],
              "text": "Participation"
            }
          ],
          "individual": {
            "reference": "hostname/instance/api/FHIR/STU3/Practitioner/ePXvh8vspdDazyK46Y16elQ3",
            "display": "Test Provider, MD"
          }
        }
      ],
      "period": {
        "start": "2024-10-15",
        "end": "2024-10-15"
      },
      "location": [
        {
          "location": {
            "reference": "hostname/instance/api/FHIR/STU3/Location/eHH8YTx7BUitno5IR6Os75Q3",
            "display": "Social Care Department"
          }
        }
      ],
      "serviceProvider": {
        "reference": "hostname/instance/api/FHIR/STU3/Organization/ePUQySFaW.ofXm2GhaXRMDA3",
        "display": "FACILITY"
      }
    },
    "search": {
      "mode": "match"
    }
  }
 ]
}
```


Change log

Epic Version | Description | Type

November 2022 | Code systems for the following code sets now return a URL in place of an OID: ActCode, ICD-10-CM, ICD-10-CA, ICD-10-NL, SNOMED System URL OID ActCode STU3: http://hl7.org/fhir/v3/ActCode R4: http://terminology.hl7.org/CodeSystem/v3-ActCode 2.16.840.1.113883.5.4 ICD-10-CM http://hl7.org/fhir/sid/icd-10-cm 2.16.840.1.113883.6.90 ICD-10-CA http://hl7.org/fhir/sid/icd-10-ca 2.16.840.1.113883.6.94 ICD-10-NL http://hl7.org/fhir/sid/icd-10-nl 2.16.840.1.113883.6.3.2 SNOMED http://snomed.info/sct 2.16.840.1.113883.6.96 | Breaking change

System | URL | OID

ActCode | STU3: http://hl7.org/fhir/v3/ActCode R4: http://terminology.hl7.org/CodeSystem/v3-ActCode | 2.16.840.1.113883.5.4

ICD-10-CM | http://hl7.org/fhir/sid/icd-10-cm | 2.16.840.1.113883.6.90

ICD-10-CA | http://hl7.org/fhir/sid/icd-10-ca | 2.16.840.1.113883.6.94

ICD-10-NL | http://hl7.org/fhir/sid/icd-10-nl | 2.16.840.1.113883.6.3.2

SNOMED | http://snomed.info/sct | 2.16.840.1.113883.6.96