FHIR-STU3 — Terminology Module — part 1 of 4 (sections 4 – 4.2.13.510)

Source: HL7 FHIR STU3 (v3.0.2). Text-only edition for AI ingestion (NotebookLM); pages follow the source order (its table of contents when one exists).

4 Terminology Module

URL: https://hl7.org/fhir/STU3/terminology-module.html

This page is part of the FHIR Specification (v3.0.2: STU 3). The current version which supercedes this version is 4.0.1. For a full list of available versions, see the Directory of published versions

Work Group Vocabulary | Ballot Status: Informative

4.0 Terminology Module

4.0.1 Introduction

The Terminology Module provides an overview and guide to the FHIR resources, operations, coded data types and externally-defined standard and FHIR-defined terminologies that are used for representing and communicating coded, structured data in the FHIR core specification and profiles. Collectively, these capabilities are used to provide the terminology service functionality required for supporting the use of coded data in FHIR resources throughout the specification as described in the other modules.

The terminology resources and their relationships are shown below:

The ElementDefinition type (shown with a dotted box) is described elsewhere in the specification in the Foundation and Conformance modules.

4.0.2 Index

The Terminology Module covers the following:

Resources

CodeSystem ValueSet | ConceptMap NamingSystem | ExpansionProfile

Terminology Service

Terminology Service Documentation

Operations

CodeSystem $lookup $subsumes $compose | ValueSet $expand $validate-code | ConceptMap $translate $closure

Coded Data Types

code | Coding | CodeableConcept

Documentation

Using Codes in Resources Code Systems Defined/Referenced in FHIR Value Sets Defined in FHIR | Mappings (FHIR-defined) Between Related Value Set Concepts Known Identifier Systems

4.0.3 Security and Privacy

For security considerations for terminology services, see the Terminology Service page Security section. For more general considerations, see the Security and Privacy module.

4.0.4 Common Use Cases

* Expand a value set

* Validate a code

* Look up a display term for a code

* Translate a code from one value set to another

* Maintain a client-side transitive closure table on subsumption relationships

* Test subsumption between concepts

* For a set of property/concept pairs, return the set of concepts for the requested properties

4.0.5 Developmental Roadmap

A subset of the terminology resources has been tested and are being used in production tooling, and as such have reached a maturity level where changes become less likely. These are:

* ValueSet 3

* ConceptMap 2

Other resources are still under development:

* NamingSystem 1

* CodeSystem 0

* ExpansionProfile 0

Over the next 18 months, we will continue to advance the resources through the Maturity Levels through further development and testing. We anticipate more widespread implementation of NamingSystem, CodeSystem and ExpansionProfile and testing in Connectathons and with implementation experience.

4.1 Using Codes in Resources

URL: https://hl7.org/fhir/STU3/terminologies.html

This page is part of the FHIR Specification (v3.0.2: STU 3). The current version which supercedes this version is 4.0.1. For a full list of available versions, see the Directory of published versions

FHIR Infrastructure Work Group | Maturity Level: 5 | Ballot Status: Trial Use

Many elements in the FHIR resources have a coded value: some fixed string (a sequence of characters) assigned elsewhere that identifies some defined "concept". The sequence of characters and its meaning may be defined in one of several places:

* As one of a set of fixed values defined in this specification

* In an internet RFC (e.g. mime type, language)

* An HL7 specification (HL7 v3 code system, or HL7 v2 table)

* Some external terminology or ontology such as LOINC , or SNOMED CT

* A locally maintained dictionary, look up table or enumeration in an application (for further discussion of locally defined value sets, see "Profiling FHIR"

These methods of defining codes are collectively called "code systems". This list is far from complete; there are many ways to define code systems, and they vary widely in sophistication and size.

Throughout this specification, coded values are always treated as a pair composed of "system" and "code", where the system is a URL that identifies the code system that defines the codes. Note that system values are always case sensitive. Different code systems make their own rules as to whether the codes they define are case sensitive or not. Note that all the codes defined by FHIR itself are case sensitive and SHALL be used in the provided case (usually, but not always, lowercase).

The FHIR framework for using coded values is based on the fundamental framework defined in section 5 of the HL7 v3 Core Principles document, including the separation between code systems and value sets.

When codes are carried in resources, one of 4 different data types is used:

code | The instance represents the code only. The system is implicit - it is defined as part of the definition of the element, and not carried in the instance.
Coding | A data type that has a code and a system element that identifies where the definition of the code comes from
CodeableConcept | A type that represents a concept by plain text and/or one or more Coding elements
Quantity | Special case: has system and code elements for carrying a code for the type of unit

Notes:

* Generally, the choice of data type is dictated by the resource itself. When choosing a data type for an extension, see the FHIR wiki for advice about data type choice .

* The types string and uri can also be bound - see below

4.1.1 Coded Values, Systems, and Value Sets

The set of coded values that is allowed in an element is known as a "value set". Anywhere these four data types are used, the specification "binds" a value set to the element.

The difference between a code system and a value set is an important distinction that is easily missed by implementers, since the difference is often overlooked in system design. For instance, it's not unusual to see an application table that is a mixed list of codes, containing some LOINC codes and also some additional in-house codes. Quite often, there is no explicit differentiation between them; only the fact that a code happens to look like a LOINC code betrays its origin.

For data exchange, on the other hand, explicitly tracking the source of the code is both important and necessary. In order to do this, each code system that defines codes is assigned a URL that identifies it, and all the codes it defines are actually a pair ("Code Pair": a name with a namespace). So in the case of this mixed list example from the previous paragraph, there are two code systems: LOINC (http://loinc.org) and a local one (let's say it has been given the URL: http://example.com/codesystems/additional-test-codes). The application table is a single value set (a set of Code Pairs) that includes codes from each of those two namespaces. The value set itself is given its own URL as an identifier (e.g. "http://example.com/fhir/ValueSet/test-codes"). This identifies the set of Code Pairs, but is never used as the namespace in a actual code pair, or in an instance. In FHIR, Code Pairs are always represented as "code" and "system", except for the simple data type code where the namespace (e.g. the system element/property) is fixed in the schema and not represented explicitly.

Note that for some code systems, there is a single correct mechanism by which to represent codes defined by the system as a single URL. These single URLs are used in the context of the RDF format to enable ontological reasoning. The URL is often a direct reference to a web source that can provide additional definitional material about the concept. Where the mechanism is known, and defined by the code system, it is described in this specification.

4.1.2 Choosing a system

The URL in a system is always a reference to a code system, not to a value set. The system ensures that codes can be unambiguously traced back to their original definition, and that logical comparisons, matching and inferences can be performed consistently by different systems. For this reason, choice of the correct URI for the system attribute is critical.

The correct value to use in the system for a given code system can be determined by working through the following list, in order:

* The specification Code System Registry - if a code system is listed here, it SHALL be used

* A system URI or OID defined as the correct value to use in FHIR by the publisher of the code system

* The FHIR community code system registry - if a code system is listed here with status = active, it SHALL be used

* An OID registered in the HL7 OID registry - if a code system is registered here, the OID SHOULD be used (using the syntax urn:oid:[oid])

If a code system is not resolved by this list, and there is no publisher to consult, implementers must choose a URI to use. The priority should be to choose a unique value that won't accidently be used by another implementer for a different purpose - or a very similar purpose with a different scope.

For publishers of code systems, the following considerations should be kept in mind when defining the correct URI to use:

* Once defined, the URI will require agreement from all implementers to change, and some may not be able to change (stored resources). If the set of users is not closed, it will usually not be possible to change the URI

* Implementers strongly prefer a human readable URI. http://acme.com/patients/mrn is a great deal easier to work with than urn:oid:1.2.3.4.5.6.7

* An http: address SHOULD resolve to some useful description of the code system. Ideally, if a user makes a request of the address with the media type set to a FHIR media type, the server will respond with a CodeSystem resource, but some other human or computable definition is allowed

* HTTP addresses should be permalinks which may re-direct to the current correct content

* A scope of the code system URI and the correct usage of codes and displays in its namespace SHOULD be clearly defined. See examples for SNOMED CT, RxNorm, LOINC, NDC

* Generally, allocation of URLs is hierarchical, and most care is required in choosing the Base URL. Once sub-URL policies are clearly defined, URIs can often be automatically assigned

Note: if the code system is made available packaged inside a ValueSet resource, the correct URL for the system value is ValueSet.codeSystem.system, not ValueSet.uri.

4.1.3 Controlling the use of Coded Values

When an element is bound to a value set, the binding has these properties:

Name | A descriptive name used when presenting information about the binding
Strength | How the binding should be understood - see below
Reference | A URL that defines the value set. Usually, this is a direct reference to a ValueSet resource, but can be a more indirect reference, where the value set is inferred
Description | A text description of the use of the codes. If there is no reference, this must be populated. When there is a reference, this can be used to make additional notes about the use and implementation of the value set

In the FHIR declarative datatypes, a binding is always represented using an ElementDefinition.binding.

4.1.3.1 Value Set References

There are a number of places in the specification where value sets are referenced in order to bind a coded value to a value set:

ElementDefinition.binding.valueSet[x] | Used to bind a defined element to a value set
ConceptMap.source[x] and .target[x] | used to indicate the scope of the mapping in the Concept Map - from one value set to another
Questionnaire.group.question.options | Indicates that answers to a set of questions come from a value set
ValueSet.compose.import | The content of a value set includes the content in the imported value set too
ValueSet Reference Extension | Indicates that a particular coded value was chosen from the specified value set

There are two types of value set references in this list, direct and logical.

4.1.3.1.1 Direct Value Set references

A direct value set reference has the type Reference, and refers directly to a ValueSet based on a URL, usually to a terminology server running a FHIR RESTful API. When accessing a value set based on this kind of reference, a system should access the URL directly (after converting a relative reference to an absolute reference according to the local context). If this process fails, the system is unable to resolve the value set and must handle the error appropriately.

Example:

```
GET fhir/Questionnaire/234

<Questionnaire>
  ...
  <question>
    <options>
      <reference value="ValueSet/234234"/>
```

```
    </options>
  </question>
  ....
</Questionnaire>
```

This specifies that the values for a particular questionnaire come from the ValueSet with id 234234 on the same FHIR end-point. To resolve this, the system would GET fhir/ValueSet/234234

Typically, a direct reference like this is good for in-process references, in closed or carefully managed eco-systems. In a more general context, these references tend to be fragile over time because web URLs - including RESTful API URLS - are easily reassigned. For this reason, systems are encouraged to use logical value set references.

4.1.3.1.2 Logical Value Set references

A logical value set reference has the type uri, where an absolute URI is provided that matches the one in ValueSet.url. The value set URL can - and is preferred to be - a web address that actually resolves directly to a fixed web address that serves as the authoritative source for that value set. Alternatively, the system can query its terminology server(s) to resolve a value set with that URL as its identity.

Example:

```
<StructureDefinition>
  ...
  <element>
    ...
    <binding>
      ...
      <valueSetUri value="http://hl7.org/fhir/ValueSet/clinical-findings"/>
    </binding>
    ...
  </element>
  ....
</StructureDefinition>
```

This specifies that the element is bound to the value set with a ValueSet.url of http://hl7.org/fhir/ValueSet/clinical-findings . One way to accees this value set is to try GET http://hl7.org/fhir/ValueSet/clinical-findings - which works, for this value set - http://hl7.org/fhir/ValueSet/clinical-findings returns the authoritative value set for this URL.

Alternatively, the value set could be resolved using a local terminology server. If that's running a FHIR Terminology Server, then this would work like this:

```
GET fhir/ValueSet?url=http://hl7.org/fhir/ValueSet/clinical-findings
```

if the terminology server knows the value set, then it will return the value set. If the URL doesn't resolve to an authoritative value set, and the terminology server(s) don't know the value set, the system is unable to resolve the value set and must handle the error appropriately.

The value set URL is allowed to be a URI such as a UUID (e.g. urn:uuid:c0e0d027-1250-4278-8f44-33a49dc67916). These value sets can never be accessed directly, and must come from a terminology server. Note that this specification defines many value sets that have a logical URL that is not resolvable (examples for SNOMED CT, RxNorm, LOINC)

Using a logical reference which is a direct reference to the authoritative value set is the easiest and most reliable approach. However, this requires suitable hosting arrangements, and cannot always be guaranteed, so it is not required.

Version specific Logical References

A value set has a two part identifier: a url, and a version. Some value sets only ever have a single 'version'; a revision of the value set contents will cause a new url to be assigned. Others, however, maintain the same URL, and change the version. A terminology server may have multiple value sets for the same ValueSet.url with different versions.

To be precise about which version of a value set is being referred to in a value set reference, append the version to the canonical url with a '|' like this:

```
<valueSetUri value="http://hl7.org/fhir/ValueSet/clinical-findings|0.8"/>
```

This is a version specific reference to a value set. Searching for this on a terminology server would look like this:

```
GET fhir/ValueSet?url=http://hl7.org/fhir/ValueSet/clinical-findings&version=0.8
```

Note that if a value set reference does not have a version, and the server finds multiple versions for the value set, the system using the value set should pick the latest version of the value set and use that. Note that this applies to all conformance resources.

4.1.3.1.3 Unbound

Note that as a matter of ongoing development, a few elements that have coded data types are not bound to any value set at all. Bindings are to be provided for these elements.

4.1.4 Binding Strengths

Almost all of the elements that have a coded data type are bound to a value set. The bindings are associated with various degrees of flexibility as to how closely the value set should be followed:

required | To be conformant, the concept in this element SHALL be from the specified value set

extensible | To be conformant, the concept in this element SHALL be from the specified value set if any of the codes within the value set can apply to the concept being communicated. If the value set does not cover the concept (based on human review), alternate codings (or, data type allowing, text) may be included instead.

preferred | Instances are encouraged to draw from the specified codes for interoperability purposes but are not required to do so to be considered conformant.
example | Instances are not expected or even encouraged to draw from the specified value set. The value set merely provides examples of the types of concepts intended to be included.

The precise conformance criteria for 'required' and 'extensible' binding strengths vary by the data type to which they are applied, as described in the paragraphs below.

Irrespective of the binding strength, when a StructureDefinition is used to describe local usage, it can bind the element to a different value set in order to be much more precise about exactly which coded values can be used for these elements, and/or increase the strength of the binding. There are different rules for this, depending on the binding strength, as discussed below. Generally it is expected that jurisdictions, projects and vendors will work together to choose actual working value sets.

4.1.4.1 Required

To be conformant, codes in this element SHALL be from the specified value set.

In the standard, this is generally used for elements where the value needs to be strictly controlled so that everyone can interpret it with confidence. Generally, this is used for elements with type code:

* the element is bound to a value set that contains a list of distinct codes with a specified system (and version, where required)

* the element is bound to some external standard that defines the set of valid codes that can be used (typical examples are Mime Types , Language Codes , UCUM , etc.)

The other place where this is used is when profiling resources, and there is agreement within a particular context of use that a particular set of codes are the only ones that can be used. In these cases, the data type SHALL contain one of the values in the value set.

The following rules apply when required bindings are used with the CodeableConcept data type:

* at least one Coding element SHALL be present

* one of the Coding values SHALL be from the specified value set

* text can be provided as well, and is always recommended, but is not an acceptable substitute for the required code

The following rules apply when required bindings are used with the code data type:

* Where the value set is defined by FHIR, the list of allowed codes will be fixed in the XML schema

* Comparison between codes is always case sensitive unless the codes are selected by reference (e.g. ValueSet.compose), and the referenced specification clearly states otherwise

* The list of codes that can be used can only be extended in subsequent releases of the FHIR specification

When an element is bound to a required value set, derived profiles may state rules on which codes can be used, but cannot select new or additional codes for these elements.

4.1.4.2 Extensible

To be conformant, codes in this element SHALL be from the specified value set if any of the codes within the value set can apply to the concept being communicated. If the value set does not cover the concept (based on human review), an alternate system.code may be used instead.

If the data type is CodeableConcept, then one of the coding values SHALL be from the specified value set if a code applies, but if no suitable code exists in the value set, alternate code(s) may be provided in its place. If no codes, including local codes, are available, then just text may be used.

If the data type is Coding, then the code/system SHALL be from the specified value set if a code applies, but if no suitable code exists in the value set, an alternate code may be provided in its place.

Identified gaps in value sets should be submitted to the organization administering the value set in order to improve interoperability in the future.

Extensible bindings are used when there is consensus at the specification or profiling level about the coded values that should be used, but it is impossible to create a bounded list of codes that are known to cover all use cases, including ones that are yet to arise.

When an element is extensibly bound to value set, derived profiles may state rules on which codes can be used, but cannot select new or additional codes for these elements unless no codes with appropriate meanings are found in the base value set.

4.1.4.3 Preferred

Instances are encouraged to draw from the specified codes for interoperability purposes but are not required to do so to be considered conformant.

If the data type is CodeableConcept, then one of the coding values SHOULD be from the specified value set, but another code and/or text can be used in its place.

Preferred bindings are used when there is consensus at the specification level about the coded values that are the best to be used, but there is recognition that some implementation contexts are unable to use the recommended codes for a variety of reasons. Applications should consider adopting the preferred value set wherever possible, as these preferred value sets are the most likely to server interoperability purposes in the future.

When an element is bound to a preferred value set, derived profiles may bind the element to any value set they choose.

4.1.4.3.1 Example Bindings

Instances are not expected or even encouraged to draw from the specified value set. The value set merely provides examples of the types of concepts intended to be included.

Example bindings are used when an element has a very broad meaning (such as List.code), or there is no consensus over the correct codes to be used. For these bindings:

* Coding: the system/code values MAY be one of the codes in the value set.

* CodeableConcept: one of the coding elements MAY contain a system/code that is in the value set.

Some other coded value MAY be used, or (for a CodeableConcept), a text alternative MAY be provided. Example value sets are provided to assist implementers to understand the correct use of an element. Value sets based on code systems such as SNOMED CT that have restrictive license terms will only be used as example bindings in the base FHIR specification, though implementation guides for particular jurisdictions may adopt value sets that require licenses.

When an element is bound to an example value set, derived profiles may bind the element to any value set they choose.

4.1.5 Other notes

* Subsequent versions of FHIR may replace example value sets with preferred bindings if enough consensus emerges in the relevant sphere.

* Bindings to value sets provided as part of the specification are always specific to the version of the value set published with the specification. The value set may be sealed by defining a simple list of enumerated codes, or it may include codes by their properties, along with a non-version specific reference to an underlying code system, in which case the list of valid concepts may change over time.

4.1.5.1 Binding String Values

In a few special cases, humans customarily use codes directly for elements that have type "string". A typical case is codes for states, and there are several places where a URI must come from a set of controlled values. An element of type string or uri can also be bound to a value set. When a string or URI is bound to a value set, the value property SHALL contain the code specified by the value set, and the system and display values are ignored.

4.1.5.2 Terminology Service

FHIR has defined a Terminology Service specification which sets requirements for systems that support the use of codes, value sets and code systems.

4.2 Code Systems

URL: https://hl7.org/fhir/STU3/terminologies-systems.html

This page is part of the FHIR Specification (v3.0.2: STU 3). The current version which supercedes this version is 4.0.1. For a full list of available versions, see the Directory of published versions

4.2.0 Code Systems

Vocabulary Work Group | Maturity Level: 3 | Ballot Status: Trial Use

The following names (URIs) may be used in the system element of the Coding data type. If a URI is defined here, it SHALL be used in preference to any other identifying mechanisms. If a code system is not listed here, the correct URI may be determined by working through the following list, in order:

* the HL7 OID Registry

* the documentation associated with the code system

* consulting the owner of the code system

* asking on the HL7 vocabulary mailing list

See also the list of known identifier systems that can be used in the system element of the Identifier data type. Additional identifier systems may be registered on the HL7 FHIR registry at http://hl7.org/fhir/registry .

Important Notes:

* This list of names is incomplete and subject to change. Some values may be dropped and others will likely be added in the coming months as HL7 institutes formal processes around URIs in vocabulary

* Note that some of the URNs in this list follow the URN specification in RFC 5141 for referring to standards published by ISO, such as urn:iso:std:iso:11073:10101. Where ISO standards define codes with meanings, and there is no entry in the list above, and they are not registered in the HL7 OID registry, the default URN for the code system is that defined by the RFC 5141.

* For several of the code systems in this list, multiple systems are given. This means that the variants identified are different code systems, not just variants of the same code system

* Any URL in http://example.org is reserved for testing and documentation purposes.

* External

* Internal (FHIR)
* HL7 V3
* HL7 v2

URI | Source | Comment | OID (for non-FHIR systems)
Externally Published code systems
http://snomed.info/sct | SNOMED CT (IHTSDO) | See Using SNOMED CT with FHIR | 2.16.840.1.113883.6.96
http://www.nlm.nih.gov/research/umls/rxnorm | RxNorm (US NLM) | See Using RxNorm with FHIR | 2.16.840.1.113883.6.88
http://loinc.org | LOINC (LOINC.org) | See Using LOINC with FHIR | 2.16.840.1.113883.6.1
http://unitsofmeasure.org | UCUM: (UnitsOfMeasure.org) Case Sensitive Codes | See Using UCUM with FHIR | 2.16.840.1.113883.6.8
http://ncimeta.nci.nih.gov | NCI Metathesaurus | See Using NCI Metathesaurus with FHIR | 2.16.840.1.113883.3.26.1.2
http://www.ama-assn.org/go/cpt | AMA CPT codes | See Using CPT with FHIR | 2.16.840.1.113883.6.12
http://hl7.org/fhir/ndfrt | NDF-RT (National Drug File – Reference Terminology) | See Using NDF-RT with FHIR | 2.16.840.1.113883.6.209
http://fdasis.nlm.nih.gov | Unique Ingredient Identifier (UNII) | See Using UNII with FHIR | 2.16.840.1.113883.4.9
http://hl7.org/fhir/sid/ndc | NDC/NHRIC Codes | See Using NDC with FHIR | 2.16.840.1.113883.6.69
http://hl7.org/fhir/sid/cvx | CVX (Vaccine Administered) | See Using CVX with FHIR | 2.16.840.1.113883.12.292
urn:iso:std:iso:3166 | ISO 2 letter Country Codes | A few country codes have been reused (e.g. CS). If a version is needed, simply use the year of publication e.g. 1998 | 1.0.3166.1.2.2
http://www.nubc.org/patient-discharge | NUBC code system for Patient Discharge Status | National Uniform Billing Committee, manual UB-04, UB form locator 17 | 2.16.840.1.113883.6.301.5
http://www.radlex.org | RadLex | (Includes play book codes) | 2.16.840.1.113883.6.256
ICD-9, ICD-10 | WHO) & National Variants | See Using ICD-[x] with FHIR | See ICD page for details
http://hl7.org/fhir/sid/icpc-1 http://hl7.org/fhir/sid/icpc-1-nl http://hl7.org/fhir/sid/icpc-2 | ICPC (International Classification of Primary Care) (PH3C) | | 2.16.840.1.113883.2.4.4.31.1 2.16.840.1.113883.6.139
http://hl7.org/fhir/sid/icf-nl | ICF (International Classification of Functioning, Disability and Health) (WHO) | | 2.16.840.1.113883.6.254
http://hl7.org/fhir/v2/[X](/v) | Version 2 tables | [X] is the 4 digit identifier for a table; e.g. http://hl7.org/fhir/v2/0203 Note: only some tables may be treated in this fashion. For some tables, the meaning of the code is version dependent, and so additional information must be included in the namespace, e.g. http://hl7.org/fhir/v2/0123/2.3+, as defined in the v2 table namespace list. Version 2 codes are case sensitive. | 2.16.840.1.113883.12.[X]
http://hl7.org/fhir/v3/[X] | A HL7 v3 code system | [X] is the code system name; e.g. http://hl7.org/fhir/v3/GenderStatus. HL7 v3 code systems are case sensitive. | see v3 list
http://www.whocc.no/atc | Anatomical Therapeutic Chemical Classification System (WHO) | | 2.16.840.1.113883.6.73
urn:ietf:bcp:47 | IETF language (see Tags for Identifying Languages - BCP 47) | This is used for identifying language throughout FHIR. Note that usually these codes are in a code and the system is assumed
urn:ietf:bcp:13 | Mime Types (see Multipurpose Internet Mail Extensions (MIME) Part Four - BCP 13) | This is used for identifying the mime type system throughout FHIR. Note that these codes are in a code (e.g. Attachment.contentType and in these elements the system is assumed). This system is defined for when constructing value sets of mime type codes
urn:iso:std:iso:11073:10101 | Medical Device Codes defined in ISO 11073-10101 (see RTM Management service) | The ISO/IEEE 11073-10201 Terminology Code is used in the code element, and the Terminology Reference ID is used in the display element (CODE10 and REFID in the reference) | 2.16.840.1.113883.6.24
http://dicom.nema.org/resources/ontology/DCM | DICOM Code Definitions | The meanings of codes defined in DICOM, either explicitly or by reference to another part of DICOM or an external reference document or standard | 1.2.840.10008.2.16.4
http://hl7.org/fhir/sid/ca-hc-din | Health Canada Drug Identification Number | A computer-generated eight digit number assigned by Health Canada to a drug product prior to being marketed in Canada. Canada Health Drug Product Database contains product specific information on drugs approved for use in Canada. | 2.16.840.1.113883.5.1105
http://nucc.org/provider-taxonomy | NUCC Provider Taxonomy | The Health Care Provider Taxonomy code is a unique alphanumeric code, ten characters in length. The code set is structured into three distinct "Levels" including Provider Type, Classification, and Area of Specialization. | 2.16.840.1.113883.6.101
Code Systems for Genetics
http://www.genenames.org | HGNC: Human Gene Nomenclature Committee | | 2.16.840.1.113883.6.281
http://www.ensembl.org | ENSEMBL reference sequence identifiers | Maintained jointly by the European Bioinformatics Institute and Welcome Trust Sanger Institute | not assigned yet
http://www.ncbi.nlm.nih.gov/nuccore | REFSEQ : National Center for Biotechnology Information (NCBI) Reference Sequences | | 2.16.840.1.113883.6.280
http://www.ncbi.nlm.nih.gov/clinvar | ClinVar | NCBI central repository for curating pathogenicity of potentially clinically relevant variants | not assigned yet
http://sequenceontology.org | Sequence Ontology | | not assigned yet
http://www.hgvs.org/mutnomen | HGVS : Human Genome Variation Society | | 2.16.840.1.113883.6.282
http://www.ncbi.nlm.nih.gov/projects/SNP | DBSNP : Single Nucleotide Polymorphism database | | 2.16.840.1.113883.6.284
http://cancer.sanger.ac.uk/ cancergenome/projects/cosmic | COSMIC : Catalogue Of Somatic Mutations In Cancer | | 2.16.840.1.113883.3.912
http://www.lrg-sequence.org | LRG : Locus Reference Genomic Sequences | | 2.16.840.1.113883.6.283
http://www.omim.org | OMIM : Online Mendelian Inheritance in Man | | 2.16.840.1.113883.6.174
http://www.ncbi.nlm.nih.gov/pubmed | PubMed | | 2.16.840.1.113883.13.191
http://www.pharmgkb.org | PHARMGKB : Pharmacogenomic Knowledge Base | | 2.16.840.1.113883.3.913
http://clinicaltrials.gov | ClinicalTrials.gov | | 2.16.840.1.113883.3.1077
http://www.ebi.ac.uk/ipd/imgt/hla/ | European Bioinformatics Institute | | 2.16.840.1.113883.13.252

URI (all prefixed with http://hl7.org/fhir/) | Description | OID
CodeSystem/example | ACME Codes for Cholesterol in Serum/Plasma: This is an example code system that includes all the ACME codes for serum/plasma cholesterol from v2.36.
CodeSystem/summary | Code system summary example for ACME body sites: This is an example code system summary for the ACME codes for body site.
FDI-surface | Surface Codes: This value set includes a smattering of FDI tooth surface codes. | 2.16.840.1.113883.4.642.1.539
abstract-types | AbstractType: A type defined by FHIR that is an abstract type
account-status | AccountStatus: Indicates whether the account is available to be used. | 2.16.840.1.113883.4.642.1.715

action-cardinality-behavior | ActionCardinalityBehavior: Defines behavior for an action or a group for how many times that item may be repeated | 2.16.840.1.113883.4.642.1.791
action-condition-kind | ActionConditionKind: Defines the kinds of conditions that can appear on actions | 2.16.840.1.113883.4.642.1.799
action-grouping-behavior | ActionGroupingBehavior: Defines organization behavior of a group | 2.16.840.1.113883.4.642.1.783
action-participant-type | ActionParticipantType: The type of participant for the action | 2.16.840.1.113883.4.642.1.795
action-precheck-behavior | ActionPrecheckBehavior: Defines selection frequency behavior for an action or group | 2.16.840.1.113883.4.642.1.789
action-relationship-type | ActionRelationshipType: Defines the types of relationships between actions | 2.16.840.1.113883.4.642.1.797
action-required-behavior | ActionRequiredBehavior: Defines requiredness behavior for selecting an action or an action group | 2.16.840.1.113883.4.642.1.787
action-selection-behavior | ActionSelectionBehavior: Defines selection behavior of a group | 2.16.840.1.113883.4.642.1.785
action-type | ActionType: The type of action to be performed | 2.16.840.1.113883.4.642.1.793
actionlist | ActionList: List of allowable action which this resource can request. | 2.16.840.1.113883.4.642.1.676
activity-definition-category | ActivityDefinitionCategory: High-level categorization of the type of activity | 2.16.840.1.113883.4.642.1.776
additionalmaterials | Additional Material Codes: This value set includes sample additional material type codes. | 2.16.840.1.113883.4.642.1.522
address-type | AddressType: The type of an address (physical / postal) | 2.16.840.1.113883.4.642.1.63
address-use | AddressUse: The use of an address | 2.16.840.1.113883.4.642.1.61
adjudication | Adjudication Value Codes: This value set includes a smattering of Adjudication Value codes which includes codes to indicate the amounts eligible under the plan, the amount of benefit, copays etc. | 2.16.840.1.113883.4.642.1.589
adjudication-error | Adjudication Error Codes: This value set includes a smattering of adjudication codes. | 2.16.840.1.113883.4.642.1.39
adjudication-reason | Adjudication Reason Codes: This value set includes smattering of Adjudication Reason codes. | 2.16.840.1.113883.4.642.1.591
administrative-gender | AdministrativeGender: The gender of a person used for administrative purposes. | 2.16.840.1.113883.4.642.1.2
admit-source | AdmitSource: This value set defines a set of codes that can be used to indicate from where the patient came in. | 2.16.840.1.113883.4.642.1.253
adverse-event-category | AdverseEventCategory: Overall categorization of the event, e.g. real or potential | 2.16.840.1.113883.4.642.1.807
adverse-event-causality | AdverseEventCausality: TODO | 2.16.840.1.113883.4.642.1.814
adverse-event-causality-assess | AdverseEventCausalityAssessment: TODO | 2.16.840.1.113883.4.642.1.816
adverse-event-causality-method | AdverseEventCausalityMethod: TODO | 2.16.840.1.113883.4.642.1.818
adverse-event-causality-result | AdverseEventCausalityResult: TODO | 2.16.840.1.113883.4.642.1.820
adverse-event-outcome | AdverseEventOutcome: TODO (and should this be required?) | 2.16.840.1.113883.4.642.1.810
adverse-event-seriousness | AdverseEventSeriousness: Overall seriousness of this event for the patient | 2.16.840.1.113883.4.642.1.812
allerg-intol-substance-exp-risk | AllergyIntoleranceSubstanceExposureRisk: The risk of an adverse reaction (allergy or intolerance) for this patient upon exposure to the substance (including pharmaceutical products). | 2.16.840.1.113883.4.642.1.858
allergy-clinical-status | AllergyIntoleranceClinicalStatus: The clinical status of the allergy or intolerance. | 2.16.840.1.113883.4.642.1.118
allergy-intolerance-category | AllergyIntoleranceCategory: Category of an identified substance. | 2.16.840.1.113883.4.642.1.124
allergy-intolerance-criticality | AllergyIntoleranceCriticality: Estimate of the potential clinical harm, or seriousness, of a reaction to an identified substance. | 2.16.840.1.113883.4.642.1.120
allergy-intolerance-type | AllergyIntoleranceType: Identification of the underlying physiological mechanism for a Reaction Risk. | 2.16.840.1.113883.4.642.1.122
allergy-verification-status | AllergyIntoleranceVerificationStatus: Assertion about certainty associated with a propensity, or potential risk, of a reaction to the identified substance. | 2.16.840.1.113883.4.642.1.116
animal-genderstatus | GenderStatus: This example value set defines a set of codes that can be used to indicate the current state of the animal's reproductive organs. | 2.16.840.1.113883.4.642.1.408
animal-species | AnimalSpecies: This example value set defines a set of codes that can be used to indicate species of animal patients. | 2.16.840.1.113883.4.642.1.410
appointmentstatus | AppointmentStatus: The free/busy status of an appointment. | 2.16.840.1.113883.4.642.1.478
assert-direction-codes | AssertionDirectionType: The type of direction to use for assertion. | 2.16.840.1.113883.4.642.1.695
assert-operator-codes | AssertionOperatorType: The type of operator to use for assertion. | 2.16.840.1.113883.4.642.1.697
assert-response-code-types | AssertionResponseTypes: The type of response code to use for assertion. | 2.16.840.1.113883.4.642.1.699
audit-entity-type | AuditEventEntityType: Code for the entity type involved in the audit event. | 2.16.840.1.113883.4.642.1.903
audit-event-action | AuditEventAction: Indicator for type of action performed during the event that generated the event | 2.16.840.1.113883.4.642.1.446
audit-event-outcome | AuditEventOutcome: Indicates whether the event succeeded or failed | 2.16.840.1.113883.4.642.1.448
audit-event-type | Audit Event ID: Event Types for Audit Events - defined by DICOM with some FHIR specific additions. | 2.16.840.1.113883.4.642.1.456
basic-resource-type | Basic Resource Types: This value set defines codes for resources not yet supported by (or which will never be supported by) FHIR. Many of the codes listed here will eventually be turned into official resources. However, there is no guarantee that any particular resource will be created nor that the scope will be exactly as defined by the codes presented here. Codes in this set will be deprecated if/when formal resources are defined that encompass these concepts. | 2.16.840.1.113883.4.642.1.129
benefit-category | Benefit Category Codes: This value set includes a smattering of Benefit Category codes. | 2.16.840.1.113883.4.642.1.595
benefit-network | Network Type Codes: This value set includes a smattering of Network type codes. | 2.16.840.1.113883.4.642.1.601
benefit-subcategory | Benefit SubCategory Codes: This value set includes a smattering of Benefit SubCategory codes. | 2.16.840.1.113883.4.642.1.597
benefit-term | Benefit Term Codes: This value set includes a smattering of Benefit Term codes. | 2.16.840.1.113883.4.642.1.605
benefit-type | Benefit Type Codes: This value set includes a smattering of Benefit type codes. | 2.16.840.1.113883.4.642.1.599
benefit-unit | Unit Type Codes: This value set includes a smattering of Unit type codes. | 2.16.840.1.113883.4.642.1.603
binding-strength | BindingStrength: Indication of the degree of conformance expectations associated with a binding. | 2.16.840.1.113883.4.642.1.43
bundle-type | BundleType: Indicates the purpose of a bundle - how it was intended to be used. | 2.16.840.1.113883.4.642.1.613
capability-statement-kind | CapabilityStatementKind: How a capability statement is intended to be used. | 2.16.840.1.113883.4.642.1.189
care-plan-activity-category | CarePlanActivityCategory: High-level categorization of the type of activity in a care plan. | 2.16.840.1.113883.4.642.1.132
care-plan-activity-status | CarePlanActivityStatus: Indicates where the activity is at in its overall life cycle. | 2.16.840.1.113883.4.642.1.135
care-plan-intent | CarePlanIntent: Codes indicating the degree of authority/intentionality associated with a care plan | 2.16.840.1.113883.4.642.1.142

care-plan-status | CarePlanStatus: Indicates whether the plan is currently being acted upon, represents future intentions or is now a historical record. | 2.16.840.1.113883.4.642.1.131
care-team-category | CareTeamCategory: Indicates the type of care team. | 2.16.840.1.113883.4.642.1.147
care-team-status | CareTeamStatus: Indicates the status of the care team. | 2.16.840.1.113883.4.642.1.145
chargeitem-billingcodes | ChargeItemCode: Example set of codes that can be used for billing purposes | 2.16.840.1.113883.4.642.1.824
chargeitem-status | ChargeItemStatus: Codes identifying the stage lifecycle stage of a ChargeItem | 2.16.840.1.113883.4.642.1.822
choice-list-orientation | ChoiceListOrientation: Direction in which lists of question options should be displayed | 2.16.840.1.113883.4.642.1.851
chromosome-human | chromosome-human: Chromosome number for human | 2.16.840.1.113883.4.642.1.220
claim-exception | Exception Codes: This value set includes sample Exception codes. | 2.16.840.1.113883.4.642.1.573
claim-use | Use: Complete, proposed, exploratory, other | 2.16.840.1.113883.4.642.1.537
claimcareteamrole | Claim Care Team Role Codes: This value set includes sample Claim Care Team Role codes. | 2.16.840.1.113883.4.642.1.579
claiminformationcategory | Claim Information Category Codes: This value set includes sample Information Category codes. | 2.16.840.1.113883.4.642.1.575
classification-or-context | ClassificationOrContext: Identifies whether a useContext represents a context or classification for the element | 2.16.840.1.113883.4.642.1.876
clinical-impression-status | ClinicalImpressionStatus: The workflow state of a clinical impression. | 2.16.840.1.113883.4.642.1.150
codesystem-content-mode | CodeSystemContentMode: How much of the content of the code system - the concepts and codes it defines - are represented in a code system resource | 2.16.840.1.113883.4.642.1.766
codesystem-hierarchy-meaning | CodeSystemHierarchyMeaning: The meaning of the hierarchy of concepts in a code system | 2.16.840.1.113883.4.642.1.768
common-tags | Common Tags: Common Tag Codes defined by FHIR project | 2.16.840.1.113883.4.642.1.73
communication-category | CommunicationCategory: Codes for general categories of communications such as alerts, instruction, etc. | 2.16.840.1.113883.4.642.1.163
communication-not-done-reason | CommunicationNotDoneReason: Codes for the reason why a communication was not done. | 2.16.840.1.113883.4.642.1.165
compartment-type | CompartmentType: Which compartment a compartment definition describes | 2.16.840.1.113883.4.642.1.770
composite-measure-scoring | CompositeMeasureScoring: The composite scoring method of the measure | 2.16.840.1.113883.4.642.1.758
composition-attestation-mode | CompositionAttestationMode: The way in which a person authenticated a composition. | 2.16.840.1.113883.4.642.1.234
composition-status | CompositionStatus: The workflow/clinical status of the composition. | 2.16.840.1.113883.4.642.1.237
concept-map-equivalence | ConceptMapEquivalence: The degree of equivalence between concepts. | 2.16.840.1.113883.4.642.1.18
concept-properties | FHIR Defined Concept Properties: A set of common concept properties for use on coded systems through out the FHIR eco-system.
concept-property-type | PropertyType: The type of a property value | 2.16.840.1.113883.4.642.1.764
conceptmap-unmapped-mode | ConceptMapGroupUnmappedMode: Defines which action to take if there is no match in the group. | 2.16.840.1.113883.4.642.1.474
condition-category | Condition Category Codes: Preferred value set for Condition Categories. | 2.16.840.1.113883.4.642.1.154
condition-clinical | Condition Clinical Status Codes: Preferred value set for Condition Clinical Status. | 2.16.840.1.113883.4.642.1.156
condition-state | ConditionState: Enumeration indicating whether the condition is currently active, inactive, or has been resolved. | 2.16.840.1.113883.4.642.1.878
condition-ver-status | ConditionVerificationStatus: The verification status to support or decline the clinical status of the condition or diagnosis. | 2.16.840.1.113883.4.642.1.158
conditional-delete-status | ConditionalDeleteStatus: A code that indicates how the server supports conditional delete. | 2.16.840.1.113883.4.642.1.185
conditional-read-status | ConditionalReadStatus: A code that indicates how the server supports conditional read. | 2.16.840.1.113883.4.642.1.191
conformance-expectation | ConformanceExpectation: Indicates the degree of adherence to a specified behavior or capability expected for a system to be deemed conformant with a specification. | 2.16.840.1.113883.4.642.1.839
consent-data-meaning | ConsentDataMeaning: How a resource reference is interpreted when testing consent restrictions | 2.16.840.1.113883.4.642.1.744
consent-except-type | ConsentExceptType: How an exception statement is applied, such as adding additional consent or removing consent | 2.16.840.1.113883.4.642.1.742
consent-state-codes | ConsentState: Indicates the state of the consent | 2.16.840.1.113883.4.642.1.740
consentaction | Consent Action Codes: This value set includes sample Consent Action codes. | 2.16.840.1.113883.4.642.1.738
consentcategorycodes | Consent Category Codes: This value set includes sample Consent Directive Type codes, including several consent directive related LOINC codes; HL7 VALUE SET: ActConsentType(2.16.840.1.113883.1.11.19897); examples of US realm consent directive legal descriptions and references to online and/or downloadable forms such as the SSA-827 Authorization to Disclose Information to the Social Security Administration; and other anticipated consent directives related to participation in a clinical trial, medical procedures, reproductive procedures; health care directive (Living Will); advance directive, do not resuscitate (DNR); Physician Orders for Life-Sustaining Treatment (POLST) | 2.16.840.1.113883.4.642.1.736
constraint-severity | ConstraintSeverity: SHALL applications comply with this constraint? | 2.16.840.1.113883.4.642.1.75
contact-point-system | ContactPointSystem: Telecommunications form for contact point | 2.16.840.1.113883.4.642.1.65
contact-point-use | ContactPointUse: Use of contact point | 2.16.840.1.113883.4.642.1.67
contactentity-type | ContactEntityType: This example value set defines a set of codes that can be used to indicate the purpose for which you would contact a contact party. | 2.16.840.1.113883.4.642.1.406
content-type | ContentType: The content or mime type. | 2.16.840.1.113883.4.642.1.693
contract-content-derivative | Contract Content Derivation Codes: This is an example set of Content Derivative type codes, which represent the minimal content derived from the basal information source at a specific stage in its lifecycle, which is sufficient to manage that source information, for example, in a repository, registry, processes and workflows, for making access control decisions, and providing query responses. | 2.16.840.1.113883.4.642.1.734
contract-status | Contract Resource Status Codes: This value set contract specific codes for status. | 2.16.840.1.113883.4.642.1.732
contractsubtypecodes | Contract Subtype Codes: This value set includes sample Contract Subtype codes. | 2.16.840.1.113883.4.642.1.720
contracttermsubtypecodes | Contract Term Subtype Codes: This value set includes sample Contract Term SubType codes. | 2.16.840.1.113883.4.642.1.724
contracttermtypecodes | Contract Term Type Codes: This value set includes sample Contract Term Type codes. | 2.16.840.1.113883.4.642.1.722
contracttypecodes | Contract Type Codes: This value set includes sample Contract Type codes. | 2.16.840.1.113883.4.642.1.718

contributor-type | ContributorType: The type of contributor | 2.16.840.1.113883.4.642.1.87
copy-number-event | CopyNumberEvent: Copy Number Event | 2.16.840.1.113883.4.642.1.222
coverage-level | Coverage Level Codes: This value set includes sample Coverage Level codes. | 2.16.840.1.113883.4.642.1.518
coverage-selfpay | Coverage SelfPay Codes: This value set includes Coverage SelfPay codes. | 2.16.840.1.113883.4.642.1.520
data-absent-reason | DataAbsentReason: Used to specify why the normally expected content of the data element is missing. | 2.16.840.1.113883.4.642.1.6
data-types | DataType: The type of an element - one of the FHIR data types.
dataelement-stringency | DataElementStringency: Indicates the degree of precision of the data element definition. | 2.16.840.1.113883.4.642.1.426
days-of-week | DaysOfWeek: The days of the week. | 2.16.840.1.113883.4.642.1.507
definition-status | DefinitionStatus: Codes identifying the lifecycle stage of a definition | 2.16.840.1.113883.4.642.1.99
definition-topic | DefinitionTopic: High-level categorization of the definition, used for searching, sorting, and filtering | 2.16.840.1.113883.4.642.1.778
detectedissue-severity | DetectedIssueSeverity: Indicates the potential degree of impact of the identified issue on the patient. | 2.16.840.1.113883.4.642.1.197
device-action | Procedure Device Action Codes: Example codes indicating the change that happened to the device during the procedure. Note that these are in no way complete and may not even be appropriate for some uses. | 2.16.840.1.113883.4.642.1.417
device-statement-status | DeviceUseStatementStatus: A coded concept indicating the current status of a the Device Usage | 2.16.840.1.113883.4.642.1.204
device-status | FHIRDeviceStatus: The availability status of the device. | 2.16.840.1.113883.4.642.1.200
diagnosis-role | DiagnosisRole: This value set defines a set of codes that can be used to express the role of a diagnosis on the Encounter or EpisodeOfCare record. | 2.16.840.1.113883.4.642.1.49
diagnostic-report-status | DiagnosticReportStatus: The status of the diagnostic report as a whole. | 2.16.840.1.113883.4.642.1.231
dicom-audit-lifecycle | DICOM Audit Message Record Lifecycle Events: Attached is vocabulary for the record lifecycle events, as per DICOM Audit Message,
diet | Diet: This value set defines a set of codes that can be used to indicate dietary preferences or restrictions a patient may have. | 2.16.840.1.113883.4.642.1.251
digital-media-type | DigitalMediaType: Whether the media is a photo, video, or audio | 2.16.840.1.113883.4.642.1.326
discharge-disposition | DischargeDisposition: This value set defines a set of codes that can be used to where the patient left the hospital. | 2.16.840.1.113883.4.642.1.255
discriminator-type | DiscriminatorType: How an element value is interpreted when discrimination is evaluated | 2.16.840.1.113883.4.642.1.85
document-mode | DocumentMode: Whether the application produces or consumes documents. | 2.16.840.1.113883.4.642.1.177
document-reference-status | DocumentReferenceStatus: The status of the document reference. | 2.16.840.1.113883.4.642.1.8
document-relationship-type | DocumentRelationshipType: The type of relationship between documents. | 2.16.840.1.113883.4.642.1.240
encounter-location-status | EncounterLocationStatus: The status of the location. | 2.16.840.1.113883.4.642.1.258
encounter-special-arrangements | SpecialArrangements: This value set defines a set of codes that can be used to indicate the kinds of special arrangements in place for a patients visit. | 2.16.840.1.113883.4.642.1.249
encounter-status | EncounterStatus: Current state of the encounter | 2.16.840.1.113883.4.642.1.242
encounter-type | EncounterType: This example value set defines a set of codes that can be used to indicate the type of encounter: a specific code indicating type of service provided. | 2.16.840.1.113883.4.642.1.244
endpoint-connection-type | Endpoint Connection Type: This is an example value set defined by the FHIR project, that could be used to represent possible connection type profile values. | 2.16.840.1.113883.4.642.1.492
endpoint-payload-type | Endpoint Payload Type: This is an example value set defined by the FHIR project, that could be used to represent possible payload document types. | 2.16.840.1.113883.4.642.1.490
endpoint-status | EndpointStatus: The status of the endpoint | 2.16.840.1.113883.4.642.1.488
entformula-additive | Enteral Formula Additive Type Code: EnteralFormulaAdditiveType: Codes for the type of modular component such as protein, carbohydrate or fiber to be provided in addition to or mixed with the base formula. This value set is provided as a suggestive example. | 2.16.840.1.113883.4.642.1.380
episode-of-care-status | EpisodeOfCareStatus: The status of the episode of care. | 2.16.840.1.113883.4.642.1.649
episodeofcare-type | EpisodeOfCareType: This example value set defines a set of codes that can be used to express the usage type of an EpisodeOfCare record. | 2.16.840.1.113883.4.642.1.651
event-capability-mode | EventCapabilityMode: The mode of a message capability statement. | 2.16.840.1.113883.4.642.1.173
event-status | EventStatus: Codes identifying the stage lifecycle stage of a event | 2.16.840.1.113883.4.642.1.101
event-timing | EventTiming: Real world event relating to the schedule. | 2.16.840.1.113883.4.642.1.69
evidence-quality | QualityOfEvidenceRating: A rating system that describes the quality of evidence such as the GRADE, DynaMed, or Oxford CEBM systems | 2.16.840.1.113883.4.642.1.887
ex-USCLS | USCLS Codes: This value set includes a smattering of USCLS codes. | 2.16.840.1.113883.4.642.1.535
ex-claimitemtype | Claim Item Type Codes: This value set includes sample Item Type codes. | 2.16.840.1.113883.4.642.1.541
ex-claimsubtype | Example Claim SubType Codes: This value set includes sample Claim SubType codes which are used to distinguish the claim types for example within type institutional there may be subtypes for emergency services, bedstay and transportation. | 2.16.840.1.113883.4.642.1.559
ex-claimtype | Example Claim Type Codes: This value set includes sample Claim Type codes. | 2.16.840.1.113883.4.642.1.551
ex-diagnosisrelatedgroup | Example Diagnosis Related Group Codes: This value set includes example Diagnosis Related Group codes. | 2.16.840.1.113883.4.642.1.581
ex-diagnosistype | Example Diagnosis Type Codes: This value set includes example Diagnosis Type codes. | 2.16.840.1.113883.4.642.1.583
ex-fdi | Teeth Codes: This value set includes the FDI Teeth codes. | 2.16.840.1.113883.4.642.1.543
ex-onsettype | Example Onset Type (Reason) Codes: This value set includes example Onset Type codes which are used to identify the event for which the onset, starting date, is required. | 2.16.840.1.113883.4.642.1.571
ex-oralprostho | Oral Prostho Material type Codes: This value set includes sample Oral Prosthodontic Material type codes. | 2.16.840.1.113883.4.642.1.531
ex-payee-resource-type | ClaimPayeeResourceType: The type of Claim payee Resource | 2.16.840.1.113883.4.642.1.577
ex-paymenttype | Example Payment Type Codes: This value set includes example Payment Type codes. | 2.16.840.1.113883.4.642.1.609
ex-pharmaservice | Example Pharmacy Service Codes: This value set includes a smattering of Pharmacy Service codes. | 2.16.840.1.113883.4.642.1.555
ex-programcode | Example Program Reason Codes: This value set includes sample Program Reason Span codes. | 2.16.840.1.113883.4.642.1.569

ex-providerqualification | Example Provider Qualification Codes: This value set includes sample Provider Qualification codes. | 2.16.840.1.113883.4.642.1.563
ex-relatedclaimrelationship | Example Related Claim Relationship Codes: This value set includes sample Related Claim Relationship codes. | 2.16.840.1.113883.4.642.1.561
ex-revenue-center | Example Revenue Center Codes: This value set includes sample Revenue Center codes. | 2.16.840.1.113883.4.642.1.587
ex-servicemodifier | Example Service Modifier Codes: This value set includes sample Service Modifier codes which may support differential payment. | 2.16.840.1.113883.4.642.1.565
ex-serviceplace | Example Service Place Codes: This value set includes a smattering of Service Place codes. | 2.16.840.1.113883.4.642.1.557
ex-serviceproduct | Example Service/Product Codes: This value set includes a smattering of Service/Product codes. | 2.16.840.1.113883.4.642.1.553
ex-tooth | Oral Site Codes: This value set includes a smattering of FDI oral site codes. | 2.16.840.1.113883.4.642.1.533
ex-udi | UDI Codes: This value set includes sample UDI codes. | 2.16.840.1.113883.4.642.1.547
ex-visionprescriptionproduct | Example Vision Prescription Product Codes: This value set includes a smattering of Prescription Product codes. | 2.16.840.1.113883.4.642.1.643
explanationofbenefit-status | ExplanationOfBenefitStatus: A code specifying the state of the resource instance. | 2.16.840.1.113883.4.642.1.611
extension-context | ExtensionContext: How an extension context is interpreted. | 2.16.840.1.113883.4.642.1.657
extra-activity-type | ExtraActivityType: This value set includes coded concepts not well covered in any of the included valuesets.
extra-security-role-type | SecurityRoleType: This CodeSystem contains Additional FHIR-defined Security Role types not defined elsewhere
filter-operator | FilterOperator: The kind of operation to perform as a part of a property based filter. | 2.16.840.1.113883.4.642.1.472
flag-category | Flag Category: Example list of general categories for flagged issues. (Not complete or necessarily appropriate.) | 2.16.840.1.113883.4.642.1.113
flag-priority-code | Flag Priority Codes: This value set is provided as an exemplar. The value set is driven by IHE Table B.8-4: Abnormal Flags, Alert Priority. | 2.16.840.1.113883.4.642.1.868
flag-status | FlagStatus: Indicates whether this flag is active and needs to be displayed to a user, or whether it is no longer needed or entered in error. | 2.16.840.1.113883.4.642.1.111
fm-conditions | FM Condition Codes: This value set includes sample Conditions codes. | 2.16.840.1.113883.4.642.1.549
fm-status | Financial Resource Status Codes: This value set includes Status codes. | 2.16.840.1.113883.4.642.1.585
forms-codes | Form Codes: This value set includes a sample set of Forms codes. | 2.16.840.1.113883.4.642.1.37
fundsreserve | Funds Reservation Codes: This value set includes sample funds reservation type codes. | 2.16.840.1.113883.4.642.1.33
goal-acceptance-status | GoalAcceptanceStatus: Codes indicating whether the goal has been accepted by a stakeholder | 2.16.840.1.113883.4.642.1.837
goal-category | GoalCategory: Example codes for grouping goals for filtering or presentation. | 2.16.840.1.113883.4.642.1.271
goal-priority | GoalPriority: Indicates the level of importance associated with reaching or sustaining a goal. | 2.16.840.1.113883.4.642.1.269
goal-relationship-type | GoalRelationshipType: Types of relationships between two goals | 2.16.840.1.113883.4.642.1.835
goal-status | GoalStatus: Indicates whether the goal has been met and is still being targeted | 2.16.840.1.113883.4.642.1.267
goal-status-reason | GoalStatusReason: Example codes indicating the reason for a current status. Note that these are in no way complete and may not even be appropriate for some uses. | 2.16.840.1.113883.4.642.1.273
graph-compartment-rule | GraphCompartmentRule: How a compartment must be linked | 2.16.840.1.113883.4.642.1.276
group-type | GroupType: Types of resources that are part of group | 2.16.840.1.113883.4.642.1.278
guidance-response-status | GuidanceResponseStatus: The status of a guidance response | 2.16.840.1.113883.4.642.1.801
guide-dependency-type | GuideDependencyType: How a dependency is represented when the guide is published. | 2.16.840.1.113883.4.642.1.302
guide-page-kind | GuidePageKind: The kind of an included page. | 2.16.840.1.113883.4.642.1.304
history-not-done-reason | FamilyHistoryNotDoneReason: Codes describing the reason why a family member history was not done. | 2.16.840.1.113883.4.642.1.265
history-status | FamilyHistoryStatus: A code that identifies the status of the family history record. | 2.16.840.1.113883.4.642.1.263
hl7-work-group | HL7Workgroup: An HL7 administrative unit that owns artifacts in the FHIR specification | 2.16.840.1.113883.4.642.1.862
http-operations | TestScriptRequestMethodCode: The allowable request method or HTTP operation codes. | 2.16.840.1.113883.4.642.1.705
http-verb | HTTPVerb: HTTP verbs (in the HTTP command line). | 2.16.840.1.113883.4.642.1.617
identifier-type | Identifier Type Codes: A coded type for an identifier that can be used to determine which identifier to use for a specific purpose. | 2.16.840.1.113883.4.642.1.45
identifier-use | IdentifierUse: Identifies the purpose for this identifier, if known . | 2.16.840.1.113883.4.642.1.53
identity-assuranceLevel | IdentityAssuranceLevel: The level of confidence that this link represents the same actual person, based on NIST Authentication Levels. | 2.16.840.1.113883.4.642.1.641
immunization-origin | Immunization Origin Codes: The value set to instantiate this attribute should be drawn from a terminologically robust code system that consists of or contains concepts to support describing the source of the data when the report of the immunization event is not based on information from the person, entity or organization who administered the vaccine. This value set is provided as a suggestive example. | 2.16.840.1.113883.4.642.1.294
immunization-recommendation-date-criterion | Immunization Recommendation Date Criterion Codes: The value set to instantiate this attribute should be drawn from a terminologically robust code system that consists of or contains concepts to support the definition of dates relevant to recommendations for future doses of vaccines. This value set is provided as a suggestive example. | 2.16.840.1.113883.4.642.1.299
immunization-recommendation-status | Immunization Recommendation Status Codes: The value set to instantiate this attribute should be drawn from a terminologically robust code system that consists of or contains concepts to support describing the status of the patient towards perceived immunity against a vaccine preventable disease. This value set is provided as a suggestive example. | 2.16.840.1.113883.4.642.1.297
implant-status | Implant Status: A set codes that define the functional status of an implanted device. | 2.16.840.1.113883.4.642.1.866
intervention | Intervention Codes: This value set includes sample Intervention codes. | 2.16.840.1.113883.4.642.1.525
iso-21089-lifecycle | ISO 21089-2017 Health Record Lifecycle Events: Attached is vocabulary for the 27 record lifecycle events, as per ISO TS 21089-2017, Health Informatics - Trusted End-to-End Information Flows, Section 3, Terms and Definitions (2017, at ISO Central Secretariat, passed ballot and ready for publication). This will also be included in the FHIR EHR Record Lifecycle Event Implementation Guide, balloted and (to be) published with FHIR STU-3.
issue-severity | IssueSeverity: How the issue affects the success of the action. | 2.16.840.1.113883.4.642.1.398
issue-type | IssueType: A code that describes the type of issue. | 2.16.840.1.113883.4.642.1.400
item-type | QuestionnaireItemType: Distinguishes groups from questions and display text and indicates data type for questions | 2.16.840.1.113883.4.642.1.438
library-type | LibraryType: The type of knowledge asset this library contains | 2.16.840.1.113883.4.642.1.748

link-type | LinkType: The type of link between this patient resource and another patient resource. | 2.16.840.1.113883.4.642.1.413
linkage-type | LinkageType: Used to distinguish different roles a resource can play within a set of linked resources | 2.16.840.1.113883.4.642.1.306
list-empty-reason | List Empty Reasons: General reasons for a list to be empty. Reasons are either related to a summary list (i.e. problem or medication list) or to a workflow related list (i.e. consultation list). | 2.16.840.1.113883.4.642.1.314
list-example-use-codes | Example Use Codes for List: Example use codes for the List resource - typical kinds of use. | 2.16.840.1.113883.4.642.1.308
list-mode | ListMode: The processing mode that applies to this list | 2.16.840.1.113883.4.642.1.310
list-order | List Order Codes: Base values for the order of the items in a list resource. | 2.16.840.1.113883.4.642.1.316
list-status | ListStatus: The current state of the list | 2.16.840.1.113883.4.642.1.318
location-mode | LocationMode: Indicates whether a resource instance represents a specific location or a class of locations. | 2.16.840.1.113883.4.642.1.322
location-physical-type | LocationType: This example value set defines a set of codes that can be used to indicate the physical form of the Location. | 2.16.840.1.113883.4.642.1.320
location-status | LocationStatus: Indicates whether the location is still in use. | 2.16.840.1.113883.4.642.1.324
map-context-type | StructureMapContextType: How to interpret the context | 2.16.840.1.113883.4.642.1.666
map-group-type-mode | StructureMapGroupTypeMode: If this is the default rule set to apply for the source type, or this combination of types | 2.16.840.1.113883.4.642.1.674
map-input-mode | StructureMapInputMode: Mode for this instance of data | 2.16.840.1.113883.4.642.1.664
map-model-mode | StructureMapModelMode: How the referenced structure is used in this mapping | 2.16.840.1.113883.4.642.1.662
map-source-list-mode | StructureMapSourceListMode: If field is a list, how to manage the source | 2.16.840.1.113883.4.642.1.670
map-target-list-mode | StructureMapTargetListMode: If field is a list, how to manage the production | 2.16.840.1.113883.4.642.1.672
map-transform | StructureMapTransform: How data is copied/created | 2.16.840.1.113883.4.642.1.668
marital-status | Marital Status Codes: This value set defines the set of codes that can be used to indicate the marital status of a person. | 2.16.840.1.113883.4.642.1.29
match-grade | MatchGrade: A Master Patient Index (MPI) assessment of whether a candidate patient record is a match or not. | 2.16.840.1.113883.4.642.1.883
measure-data-usage | MeasureDataUsage: The intended usage for supplemental data elements in the measure | 2.16.840.1.113883.4.642.1.756
measure-population | MeasurePopulationType: The type of population | 2.16.840.1.113883.4.642.1.750
measure-report-status | MeasureReportStatus: The status of the measure report | 2.16.840.1.113883.4.642.1.760
measure-report-type | MeasureReportType: The type of the measure report | 2.16.840.1.113883.4.642.1.762
measure-scoring | MeasureScoring: The scoring type of the measure | 2.16.840.1.113883.4.642.1.752
measure-type | MeasureType: The type of measure (includes codes from 2.16.840.1.113883.1.11.20368) | 2.16.840.1.113883.4.642.1.754
measurement-principle | MeasmntPrinciple: Different measurement principle supported by the device. | 2.16.840.1.113883.4.642.1.619
media-subtype | Media SubType: Detailed information about the type of the image - its kind, purpose, or the kind of equipment used to generate it. | 2.16.840.1.113883.4.642.1.328
medication-admin-category | MedicationAdministrationCategory: A coded concept describing where the medication administered is expected to occur | 2.16.840.1.113883.4.642.1.338
medication-admin-status | MedicationAdministrationStatus: A set of codes indicating the current status of a MedicationAdministration. | 2.16.840.1.113883.4.642.1.331
medication-dispense-category | MedicationDispenseCategory: A code describing where the dispensed medication is expected to be consumed or administered | 2.16.840.1.113883.4.642.1.342
medication-dispense-status | MedicationDispenseStatus: A coded concept specifying the state of the dispense event. | 2.16.840.1.113883.4.642.1.340
medication-package-form | MedicationContainer: A coded concept defining the kind of container a medication package is packaged in | 2.16.840.1.113883.4.642.1.362
medication-request-category | MedicationRequestCategory: A coded concept identifying where the medication ordered is expected to be consumed or administered | 2.16.840.1.113883.4.642.1.349
medication-request-intent | MedicationRequestIntent: The kind of medication order | 2.16.840.1.113883.4.642.1.346
medication-request-priority | MedicationRequestPriority: Identifies the level of importance to be assigned to actioning the request | 2.16.840.1.113883.4.642.1.351
medication-request-status | MedicationRequestStatus: A coded concept specifying the state of the prescribing event. Describes the lifecycle of the prescription | 2.16.840.1.113883.4.642.1.344
medication-statement-category | MedicationStatementCategory: A coded concept identifying where the medication included in the medicationstatement is expected to be consumed or administered | 2.16.840.1.113883.4.642.1.356
medication-statement-status | MedicationStatementStatus: A coded concept indicating the current status of a MedicationStatement. | 2.16.840.1.113883.4.642.1.353
medication-statement-taken | MedicationStatementTaken: A coded concept identifying level of certainty if patient has taken or has not taken the medication | 2.16.840.1.113883.4.642.1.358
medication-status | MedicationStatus: A coded concept defining if the medication is in active use | 2.16.840.1.113883.4.642.1.364
message-events | MessageEvent: One of the message events defined as part of FHIR.
message-reasons-encounter | Example Message Reason Codes: Example Message Reasons. These are the set of codes that might be used an updating an encounter using admin-update. | 2.16.840.1.113883.4.642.1.366
message-significance-category | MessageSignificanceCategory: The impact of the content of a message. | 2.16.840.1.113883.4.642.1.179
message-transport | MessageTransport: The protocol used for message transport. | 2.16.840.1.113883.4.642.1.175
messageheader-response-request | messageheader-response-request: HL7-defined table of codes which identify conditions under which acknowledgments are required to be returned in response to a message. | 2.16.840.1.113883.4.642.1.844
metric-calibration-state | DeviceMetricCalibrationState: Describes the state of a metric calibration. | 2.16.840.1.113883.4.642.1.637
metric-calibration-type | DeviceMetricCalibrationType: Describes the type of a metric calibration. | 2.16.840.1.113883.4.642.1.635
metric-category | DeviceMetricCategory: Describes the category of the metric. | 2.16.840.1.113883.4.642.1.633
metric-color | DeviceMetricColor: Describes the typical color of representation. | 2.16.840.1.113883.4.642.1.639
metric-operational-status | DeviceMetricOperationalStatus: Describes the operational status of the DeviceMetric. | 2.16.840.1.113883.4.642.1.631
missingtoothreason | Missing Tooth Reason Codes: This value set includes sample Missing Tooth Reason codes. | 2.16.840.1.113883.4.642.1.527
modifiers | Modifier type Codes: This value set includes sample Modifier type codes. | 2.16.840.1.113883.4.642.1.529

name-assembly-order | HumanNameAssemblyOrder: A code that represents the preferred display order of the components of a human name | 2.16.840.1.113883.4.642.1.833
name-use | NameUse: The use of a human name | 2.16.840.1.113883.4.642.1.59
namingsystem-identifier-type | NamingSystemIdentifierType: Identifies the style of unique identifier used to identify a namespace. | 2.16.840.1.113883.4.642.1.486
namingsystem-type | NamingSystemType: Identifies the purpose of the naming system. | 2.16.840.1.113883.4.642.1.484
narrative-status | NarrativeStatus: The status of a resource narrative | 2.16.840.1.113883.4.642.1.51
network-type | AuditEventAgentNetworkType: The type of network access point of this agent in the audit event | 2.16.840.1.113883.4.642.1.450
note-type | NoteType: The presentation types of notes. | 2.16.840.1.113883.4.642.1.16
nutrition-request-status | NutritionOrderStatus: Codes specifying the state of the request. Describes the lifecycle of the nutrition order. | 2.16.840.1.113883.4.642.1.370
object-role | AuditEventEntityRole: Code representing the role the entity played in the audit event | 2.16.840.1.113883.4.642.1.454
observation-category | Observation Category Codes: Observation Category codes. | 2.16.840.1.113883.4.642.1.393
observation-relationshiptypes | ObservationRelationshipType: Codes specifying how two observations are related. | 2.16.840.1.113883.4.642.1.390
observation-statistics | StatisticsCode: The statistical operation parameter -"statistic" - codes | 2.16.840.1.113883.4.642.1.395
observation-status | ObservationStatus: Codes providing the status of an observation. | 2.16.840.1.113883.4.642.1.388
operation-kind | OperationKind: Whether an operation is a normal operation or a query. | 2.16.840.1.113883.4.642.1.500
operation-outcome | Operation Outcome Codes: Operation Outcome codes used by FHIR test servers (see Implementation file translations.xml) | 2.16.840.1.113883.4.642.1.402
operation-parameter-use | OperationParameterUse: Whether an operation parameter is an input or an output parameter. | 2.16.840.1.113883.4.642.1.502
operational-status | DeviceComponentOperationalStatus: Codes representing the current status of the device - on, off, suspended, etc. | 2.16.840.1.113883.4.642.1.896
organization-type | OrganizationType: This example value set defines a set of codes that can be used to indicate a type of organization. | 2.16.840.1.113883.4.642.1.404
parameter-group | DeviceComponentParameterGroup: Codes identifying groupings of parameters; e.g. Cardiovascular. | 2.16.840.1.113883.4.642.1.900
participant-type | ParticipantType: This value set defines a set of codes that can be used to indicate how an individual participates in an encounter. | 2.16.840.1.113883.4.642.1.246
participantrequired | ParticipantRequired: Is the Participant required to attend the appointment. | 2.16.840.1.113883.4.642.1.482
participationstatus | ParticipationStatus: The Participation status of an appointment. | 2.16.840.1.113883.4.642.1.480
payeetype | Claim Payee Type Codes: This value set includes sample Payee Type codes. | 2.16.840.1.113883.4.642.1.31
payment-adjustment-reason | Payment Adjustment Reason Codes: This value set includes smattering of Payment Adjustment Reason codes. | 2.16.840.1.113883.4.642.1.593
payment-type | Payment Type Codes: This value set includes sample Payment Type codes. | 2.16.840.1.113883.4.642.1.627
paymentstatus | Payment Status Codes: This value set includes a sample set of Payment Status codes. | 2.16.840.1.113883.4.642.1.629
plan-definition-type | PlanDefinitionType: The type of PlanDefinition | 2.16.840.1.113883.4.642.1.781
policyholder-relationship | Policyholder Relationship Codes: This value set includes codes for the relationship between the Policyholder and the Beneficiary (insured/covered party/patient).. | 2.16.840.1.113883.4.642.1.516
practitioner-role | PractitionerRole: This example value set defines a set of codes that can be used to indicate the role of a Practitioner. | 2.16.840.1.113883.4.642.1.431
practitioner-specialty | PractitionerSpecialty: This example value set defines a set of codes that can be used to indicate the specialty of a Practitioner. | 2.16.840.1.113883.4.642.1.433
procedure-progress-status-code | Procedure Progress Status Codes: This value set is provided as an example. The value set to instantiate this attribute should be drawn from a robust terminology code system that consists of or contains concepts to support the procedure performance process. | 2.16.840.1.113883.4.642.1.864
processoutcomecodes | Process Outcome Codes: This value set includes sample Process Outcome codes. | 2.16.840.1.113883.4.642.1.678
processpriority | Process Priority Codes: This value set includes the financial processing priority codes. | 2.16.840.1.113883.4.642.1.545
property-representation | PropertyRepresentation: How a property is represented when serialized. | 2.16.840.1.113883.4.642.1.81
provenance-entity-role | ProvenanceEntityRole: How an entity was used in an activity. | 2.16.840.1.113883.4.642.1.428
publication-status | PublicationStatus: The lifecycle status of a Value Set or Concept Map. | 2.16.840.1.113883.4.642.1.4
quality-type | qualityType: Type for quality report | 2.16.840.1.113883.4.642.1.224
quantity-comparator | QuantityComparator: How the Quantity should be understood and represented. | 2.16.840.1.113883.4.642.1.55
question-max-occurs | MaxOccurs: Flags an element as having unlimited repetitions | 2.16.840.1.113883.4.642.1.847
questionnaire-answers-status | QuestionnaireResponseStatus: Lifecycle status of the questionnaire response. | 2.16.840.1.113883.4.642.1.441
questionnaire-display-category | Questionnaire Text Categories: Codes defining the purpose of a Questionnaire item of type 'text'. | 2.16.840.1.113883.4.642.1.853
questionnaire-item-control | Questionnaire Item UI Control Codes: Starter set of user interface control/display mechanisms that might be used when rendering an item in a questionnaire. | 2.16.840.1.113883.4.642.1.849
questionnaire-usage-mode | QuestionnaireItemUsageMode: Identifies the modes of usage of a questionnaire that should enable a particular questionnaire item | 2.16.840.1.113883.4.642.1.855
reaction-event-certainty | AllergyIntoleranceCertainty: Statement about the degree of clinical certainty that a specific substance was the cause of the manifestation in a reaction event. | 2.16.840.1.113883.4.642.1.860
reaction-event-severity | AllergyIntoleranceSeverity: Clinical assessment of the severity of a reaction event as a whole, potentially considering multiple different manifestations. | 2.16.840.1.113883.4.642.1.126
reason-medication-given | Reason Medication Given Codes: This value set is provided as an example. The value set to instantiate this attribute should be drawn from a robust terminology code system that consists of or contains concepts to support the medication process. | 2.16.840.1.113883.4.642.1.335
reason-medication-not-given | SNOMED CT Reason Medication Not Given Codes: This value set includes all medication refused, medication not administered, and non administration of necessary drug or medicine codes from SNOMED CT - provided as an exemplar value set. | 2.16.840.1.113883.4.642.1.333
recommendation-strength | StrengthOfRecommendationRating: A rating system that describes the strength of the recommendation, such as the GRADE, DynaMed, or HGPS systems | 2.16.840.1.113883.4.642.1.889
reference-handling-policy | ReferenceHandlingPolicy: A set of flags that defines how references are supported. | 2.16.840.1.113883.4.642.1.193

reference-version-rules | ReferenceVersionRules: Whether a reference needs to be version specific or version independent, or whether either can be used | 2.16.840.1.113883.4.642.1.83
referencerange-meaning | Observation Reference Range Meaning Codes: This value set defines a set of codes that can be used to indicate the meaning/use of a reference range for a particular target population. | 2.16.840.1.113883.4.642.1.385
related-artifact-type | RelatedArtifactType: The type of relationship to the related artifact | 2.16.840.1.113883.4.642.1.93
relationship | Beneficiary Relationship Codes: This value set includes the Patient to subscriber relationship codes. | 2.16.840.1.113883.4.642.1.35
remittance-outcome | Claim Processing Codes: This value set includes a Claim Processing Outcome codes. | 2.16.840.1.113883.4.642.1.14
report-action-result-codes | TestReportActionResult: The results of executing an action. | 2.16.840.1.113883.4.642.1.709
report-participant-type | TestReportParticipantType: The type of participant. | 2.16.840.1.113883.4.642.1.711
report-result-codes | TestReportResult: The reported execution result. | 2.16.840.1.113883.4.642.1.707
report-status-codes | TestReportStatus: The current status of the test report. | 2.16.840.1.113883.4.642.1.713
repository-type | repositoryType: Type for access of external URI | 2.16.840.1.113883.4.642.1.226
request-intent | RequestIntent: Codes indicating the degree of authority/intentionality associated with a request | 2.16.840.1.113883.4.642.1.105
request-priority | RequestPriority: Identifies the level of importance to be assigned to actioning the request | 2.16.840.1.113883.4.642.1.107
request-status | RequestStatus: Codes identifying the stage lifecycle stage of a request | 2.16.840.1.113883.4.642.1.103
research-study-status | ResearchStudyStatus: Codes that convey the current status of the research study | 2.16.840.1.113883.4.642.1.803
research-subject-status | ResearchSubjectStatus: Indicates the progression of a study subject through a study | 2.16.840.1.113883.4.642.1.805
resource-aggregation-mode | AggregationMode: How resource references can be aggregated. | 2.16.840.1.113883.4.642.1.79
resource-slicing-rules | SlicingRules: How slices are interpreted when evaluating an instance. | 2.16.840.1.113883.4.642.1.77
resource-type-link | PayeeResourceType: The type of payee Resource | 2.16.840.1.113883.4.642.1.607
resource-types | ResourceType: One of the resource types defined as part of FHIR.
resource-validation-mode | ResourceValidationMode: Codes indicating the type of validation to perform | 2.16.840.1.113883.4.642.1.109
response-code | ResponseType: The kind of response to a message | 2.16.840.1.113883.4.642.1.368
restful-capability-mode | RestfulCapabilityMode: The mode of a RESTful capability statement. | 2.16.840.1.113883.4.642.1.167
restful-interaction | FHIR Restful Interactions: The set of interactions defined by the RESTful part of the FHIR specification.
restful-security-service | RestfulSecurityService: Types of security services used with FHIR. | 2.16.840.1.113883.4.642.1.169
risk-probability | Risk Probability: Codes representing the likelihood of a particular outcome in a risk assessment. | 2.16.840.1.113883.4.642.1.444
search-comparator | SearchComparator: What Search Comparator Codes are supported in search | 2.16.840.1.113883.4.642.1.623
search-entry-mode | SearchEntryMode: Why an entry is in the result set - whether it's included as a match or because of an _include requirement. | 2.16.840.1.113883.4.642.1.615
search-modifier-code | SearchModifierCode: A supported modifier for a search parameter. | 2.16.840.1.113883.4.642.1.625
search-param-type | SearchParamType: Data types allowed to be used for search parameters. | 2.16.840.1.113883.4.642.1.12
search-xpath-usage | XPathUsageType: How a search parameter relates to the set of elements returned by evaluating its xpath query. | 2.16.840.1.113883.4.642.1.621
security-source-type | Audit Event Source Type: The type of process where the audit event originated from. | 2.16.840.1.113883.4.642.1.460
sequence-type | sequenceType: Type if a sequence -- DNA, RNA, or amino acid sequence | 2.16.840.1.113883.4.642.1.215
service-category | ServiceCategory: This value set defines an example set of codes that can be used to classify groupings of service-types/specialties. | 2.16.840.1.113883.4.642.1.511
service-provision-conditions | ServiceProvisionConditions: The code(s) that detail the conditions under which the healthcare service is available/offered. | 2.16.840.1.113883.4.642.1.509
service-referral-method | ReferralMethod: The methods of referral can be used when referring to a specific HealthCareService resource. | 2.16.840.1.113883.4.642.1.505
service-type | ServiceType: This value set defines an example set of codes of service-types. | 2.16.840.1.113883.4.642.1.513
sid/ex-icd-10-procedures | ICD-10 Procedure Codes: This value set includes sample ICD-10 Procedure codes. | 2.16.840.1.113883.4.642.1.567
slotstatus | SlotStatus: The free/busy status of the slot. | 2.16.840.1.113883.4.642.1.476
special-values | SpecialValues: A set of generally useful codes defined so they can be included in value sets. | 2.16.840.1.113883.4.642.1.10
specification-type | DeviceSpecificationSpecType: Codes for device specification types such as serial number, part number, hardware revision, software revision, etc. | 2.16.840.1.113883.4.642.1.898
specimen-status | SpecimenStatus: Codes providing the status/availability of a specimen. | 2.16.840.1.113883.4.642.1.465
structure-definition-kind | StructureDefinitionKind: Defines the type of structure that a definition is describing. | 2.16.840.1.113883.4.642.1.655
subscription-channel-type | SubscriptionChannelType: The type of method used to execute a subscription. | 2.16.840.1.113883.4.642.1.494
subscription-status | SubscriptionStatus: The status of a subscription. | 2.16.840.1.113883.4.642.1.496
subscription-tag | SubscriptionTag: Tags to put on a resource after subscriptions have been sent. | 2.16.840.1.113883.4.642.1.498
substance-category | Substance Category Codes: Substance category codes | 2.16.840.1.113883.4.642.1.470
substance-status | FHIRSubstanceStatus: A code to indicate if the substance is actively used | 2.16.840.1.113883.4.642.1.468
supply-item-type | Supply Item Type: This value sets refers to a specific supply item. | 2.16.840.1.113883.4.642.1.689
supply-kind | Supply Type: This value sets refers to a Category of supply. | 2.16.840.1.113883.4.642.1.680
supplydelivery-status | SupplyDeliveryStatus: Status of the supply delivery. | 2.16.840.1.113883.4.642.1.687
supplyrequest-reason | SupplyRequestReason: Why the supply item was requested | 2.16.840.1.113883.4.642.1.684
supplyrequest-status | SupplyRequestStatus: Status of the supply request | 2.16.840.1.113883.4.642.1.682
system-version-processing-mode | SystemVersionProcessingMode: How to manage the intersection between a fixed version in a value set, and a fixed version of the system in the expansion profile | 2.16.840.1.113883.4.642.1.261
task-performer-type | TaskPerformerType: The type(s) of task performers allowed | 2.16.840.1.113883.4.642.1.772
task-status | TaskStatus: The current status of the task. | 2.16.840.1.113883.4.642.1.774
testscript-operation-codes | TestScriptOperationCode: This value set defines a set of codes that are used to indicate the supported operations of a testing engine or tool. | 2.16.840.1.113883.4.642.1.691
testscript-profile-destination-types | TestScriptProfileDestinationType: This value set defines a set of codes that are used to indicate the profile type of a test system when acting as the destination within a TestScript. | 2.16.840.1.113883.4.642.1.703
testscript-profile-origin-types | TestScriptProfileOriginType: This value set defines a set of codes that are used to indicate the profile type of a test system when acting as the origin within a TestScript. | 2.16.840.1.113883.4.642.1.701
transaction-mode | TransactionMode: A code that indicates how transactions are supported. | 2.16.840.1.113883.4.642.1.183
trigger-type | TriggerType: The type of trigger | 2.16.840.1.113883.4.642.1.97
type-derivation-rule | TypeDerivationRule: How a type relates to its baseDefinition. | 2.16.840.1.113883.4.642.1.660

udi-entry-type | UDIEntryType: Codes to identify how UDI data was entered | 2.16.840.1.113883.4.642.1.202

unknown-content-code | UnknownContentCode: A code that indicates whether an application accepts unknown elements or extensions when reading resources. | 2.16.840.1.113883.4.642.1.187

usage-context-type | UsageContextType: A code that specifies a type of context being specified by a usage context | 2.16.840.1.113883.4.642.1.95

vaccination-protocol-dose-status | Vaccination Protocol Dose Status codes: The value set to instantiate this attribute should be drawn from a terminologically robust code system that consists of or contains concepts to support describing the validity of a dose relative to a particular recommended schedule. This value set is provided as a suggestive example. | 2.16.840.1.113883.4.642.1.289

vaccination-protocol-dose-status-reason | Vaccination Protocol Dose Status Reason codes: The value set to instantiate this attribute should be drawn from a terminologically robust code system that consists of or contains concepts to support describing the reason why an administered dose has been assigned a particular status. Often, this reason describes why a dose is considered invalid. This value set is provided as a suggestive example. | 2.16.840.1.113883.4.642.1.291

variant-state | sequenceStatus: Codes providing the status of the variant test result | 2.16.840.1.113883.4.642.1.211

versioning-policy | ResourceVersionPolicy: How the system supports versioning for a resource. | 2.16.840.1.113883.4.642.1.181

vision-base-codes | VisionBase: A coded concept listing the base codes. | 2.16.840.1.113883.4.642.1.647

vision-eye-codes | VisionEyes: A coded concept listing the eye codes. | 2.16.840.1.113883.4.642.1.645

w3c-provenance-activity-type | W3cProvenanceActivityType: This value set includes W3C PROV Data Model Activity concepts, which are treated as codes in this valueset. Some adaptations were made to make these concepts suitable values for the Provenance.activity element. Coded concepts are from PROV-DM and the display names are their counterparts in PROV-N (human readable notation syntax specification).[code system OID: http://www.w3.org/TR/2013/REC-prov-dm-20130430/ and http://www.w3.org/TR/2013/REC-prov-n-20130430/]

Name (URI = http://hl7.org/fhir/v3/...) | Description | OID

AcknowledgementCondition | The codes identify the conditions under which accept acknowledgements are required to be returned in response to this message. Note that accept acknowledgement address two different issues at the same time: reliable transport as well as syntactical correctness | .1.113883.5.1050

AcknowledgementDetailCode | OpenIssue: Missing description. | .1.113883.5.1100

AcknowledgementDetailType | A code identifying the specific message to be provided. Discussion: A textual value may be specified as the print name, or for non-coded messages, as the original text. Examples: 'Required attribute xxx is missing', 'System will be unavailable March 19 from 0100 to 0300' | .1.113883.5.1082

AcknowledgementType | This attribute contains an acknowledgement code as described in the HL7 message processing rules. OpenIssue: Description was copied from attribute and needs to be improved to be appropriate for a code system. | .1.113883.5.18

ActClass | **** MISSING DEFINITIONS **** | .1.113883.5.6

ActCode | A code specifying the particular kind of Act that the Act-instance represents within its class. Constraints: The kind of Act (e.g. physical examination, serum potassium, inpatient encounter, charge financial transaction, etc.) is specified with a code from one of several, typically external, coding systems. The coding system will depend on the class of Act, such as LOINC for observations, etc. Conceptually, the Act.code must be a specialization of the Act.classCode. This is why the structure of ActClass domain should be reflected in the superstructure of the ActCode domain and then individual codes or externally referenced vocabularies subordinated under these domains that reflect the ActClass structure. Act.classCode and Act.code are not modifiers of each other but the Act.code concept should really imply the Act.classCode concept. For a negative example, it is not appropriate to use an Act.code "potassium" together with and Act.classCode for "laboratory observation" to somehow mean "potassium laboratory observation" and then use the same Act.code for "potassium" together with Act.classCode for "medication" to mean "substitution of potassium". This mutually modifying use of Act.code and Act.classCode is not permitted. | .1.113883.5.4

ActExposureLevelCode | A qualitative measure of the degree of exposure to the causative agent. This includes concepts such as "low", "medium" and "high". This quantifies how the quantity that was available to be administered to the target differs from typical or background levels of the substance. | .1.113883.5.1114

ActInvoiceElementModifier | Processing consideration and clarification codes. | .1.113883.5.1051

ActMood | OpenIssue: In Ballot 2009May, a strong Negative vote was lodged against several of the concept definitions in the vocabulary used for Act.moodCode. The vote was found "Persuasive With Mod", with the understanding that M and M would undertake a detailed review of these concept definitions for a future release of the RIM. | .1.113883.5.1001

ActPriority | A set of codes (e.g., for routine, emergency), specifying the urgency under which the Act happened, can happen, is happening, is intended to happen, or is requested/demanded to happen. | .1.113883.5.7

ActReason | A set of codes specifying the motivation, cause, or rationale of an Act, when such rationale is not reasonably represented as an ActRelationship of type "has reason" linking to another Act. Examples: Example reasons that might qualify for being coded in this field might be: "routine requirement", "infectious disease reporting requirement", "on patient request", "required by law". | .1.113883.5.8

ActRelationshipCheckpoint | **** MISSING DEFINITIONS **** | .1.113883.5.10

ActRelationshipJoin | **** MISSING DEFINITIONS **** | .1.113883.5.12

ActRelationshipSplit | **** MISSING DEFINITIONS **** | .1.113883.5.13

ActRelationshipSubset | <ns1:p>Used to indicate that the target of the relationship will be a filtered subset of the total related set of targets.</ns1:p><ns1:p>Used when there is a need to limit the number of components to the first, the last, the next, the total, the average or some other filtered or calculated subset.</ns1:p> | .1.113883.5.1099

ActRelationshipType | The source is an excerpt from the target. | .1.113883.5.1002

ActSite | An anatomical location on an organism which can be the focus of an act. | .1.113883.5.1052

ActStatus | Codes representing the defined possible states of an Act, as defined by the Act class state machine. | .1.113883.5.14

ActUSPrivacyLaw | A jurisdictional mandate in the US relating to privacy. Deprecation Comment: Content moved to ActCode under _ActPrivacyLaw; use that instead. | .1.113883.5.1138

ActUncertainty | OpenIssue: Missing Description | .1.113883.5.1053

AddressPartType | Description: Code that specifies whether an address part names the street, city, country, postal code, post box, etc. Discussion: The hierarchical nature of these concepts shows composition. E.g. "Street Name" is part of "Street Address Line" | .1.113883.5.16

AddressUse | Codes that provide guidance around the circumstances in which a given address should be used. | .1.113883.5.1119

AdministrativeGender | The gender of a person used for adminstrative purposes (as opposed to clinical gender) | .1.113883.5.1

AmericanIndianAlaskaNativeLanguages | American Indian and Alaska Native languages currently being used in the United States. | .1.113883.5.1054

Calendar | **** MISSING DEFINITIONS **** | .1.113883.5.1055

CalendarCycle | Calendar cycle identifiers | .1.113883.5.9

CalendarType | **** MISSING DEFINITIONS **** | .1.113883.5.1017

Charset | Internet Assigned Numbers Authority (IANA) Charset Types | .1.113883.5.21

CodingRationale | Identifies how to interpret the instance of the code, codeSystem value in a set of translations. Since HL7 (or a government body) may mandate that codes from certain code systems be sent in conformant messages, other synonyms that are sent in the translation set need to be

distinguished among the originally captured source, the HL7 specified code, or some future role. When this code is NULL, it indicates that the translation is an undefined type. When valued, this property must contain one of the following values: SRC - Source (or original) code HL7 - HL7 Specified or Mandated SH - both HL7 mandated and the original code (precoordination) There may be additional values added to this value set as we work through the use of codes in messages and determine other Use Cases requiring special interpretation of the translations. | .1.113883.5.1074

CommunicationFunctionType | Describes the type of communication function that the associated entity plays in the associated transmission. | .1.113883.5.1056

CompressionAlgorithm | **** MISSING DEFINITIONS **** | .1.113883.5.1009

Confidentiality | A set of codes specifying the security classification of acts and roles in accordance with the definition for concept domain "Confidentiality". | .1.113883.5.25

ContainerCap | The type of cap associated with a container | .1.113883.5.26

ContainerSeparator | A material in a blood collection container that facilites the separation of of blood cells from serum or plasma | .1.113883.5.27

ContentProcessingMode | Description: Identifies the order in which content should be processed. | .1.113883.5.1110

ContextControl | A code that specifies how an ActRelationship or Participation contributes to the context of an Act, and whether it may be propagated to descendent Acts whose association allows such propagation (see also attributes Participation.contextControlCode, ActRelationship.contextControlCode, ActRelationship.contextConductionInd). | .1.113883.5.1057

DataOperation | **** MISSING DEFINITIONS **** | .1.113883.5.1123

DeviceAlertLevel | Domain values for the Device.Alert_levelCode | .1.113883.5.31

DocumentCompletion | Identifies the current completion state of a clinical document. | .1.113883.5.33

DocumentStorage | Identifies the storage status of a document. | .1.113883.5.34

EducationLevel | Years of education that a person has completed | .1.113883.5.1077

EmployeeJobClass | **** MISSING DEFINITIONS **** | .1.113883.5.1059

EncounterAdmissionSource | **** MISSING DEFINITIONS **** | .1.113883.5.37

EncounterSpecialCourtesy | **** MISSING DEFINITIONS **** | .1.113883.5.40

EntityClass | Classifies the Entity class and all of its subclasses. The terminology is hierarchical. At the top is this HL7-defined domain of high-level categories (such as represented by the Entity subclasses). Each of these terms must be harmonized and is specializable. The value sets beneath are drawn from multiple, frequently external, domains that reflect much more fine-grained typing. | .1.113883.5.41

EntityCode | OpenIssue: Missing description. | .1.113883.5.1060

EntityDeterminer | EntityDeterminer in natural language grammar is the class of words that comprises articles, demonstrative pronouns, and quantifiers. In the RIM, determiner is a structural code in the Entity class to distinguish whether any given Entity object stands for some, any one, or a specific thing. | .1.113883.5.30

EntityHandling | **** MISSING DEFINITIONS **** | .1.113883.5.42

EntityNamePartQualifier | OpenIssue: Needs description | .1.113883.5.43

EntityNamePartQualifierR2 | Description: The qualifier is a set of codes each of which specifies a certain subcategory of the name part in addition to the main name part type. For example, a given name may be flagged as a nickname, a family name may be a pseudonym or a name of public records. | .1.113883.5.1122

EntityNamePartType | **** MISSING DEFINITIONS **** | .1.113883.5.44

EntityNamePartTypeR2 | Description: Indicates whether the name part is a given name, family name, prefix, suffix, etc. | .1.113883.5.1121

EntityNameUse | **** MISSING DEFINITIONS **** | .1.113883.5.45

EntityNameUseR2 | Description: A set of codes advising a system or user which name in a set of names to select for a given purpose. | .1.113883.5.1120

EntityRisk | Kinds of risks associated with the handling of the material.. | .1.113883.5.46

EntityStatus | Codes representing the defined possible states of an Entity, as defined by the Entity class state machine. | .1.113883.5.1061

EquipmentAlertLevel | **** MISSING DEFINITIONS **** | .1.113883.5.49

Ethnicity | In the United States, federal standards for classifying data on ethnicity determine the categories used by federal agencies and exert a strong influence on categorization by state and local agencies and private sector organizations. The federal standards do not conceptually define ethnicity, and they recognize the absence of an anthropological or scientific basis for ethnicity classification. Instead, the federal standards acknowledge that ethnicity is a social-political construct in which an individual's own identification with a particular ethnicity is preferred to observer identification. The standards specify two minimum ethnicity categories: Hispanic or Latino, and Not Hispanic or Latino. The standards define a Hispanic or Latino as a person of "Mexican, Puerto Rican, Cuban, South or Central America, or other Spanish culture or origin, regardless of race." The standards stipulate that ethnicity data need not be limited to the two minimum categories, but any expansion must be collapsible to those categories. In addition, the standards stipulate that an individual can be Hispanic or Latino or can be Not Hispanic or Latino, but cannot be both. | .1.113883.5.50

ExposureMode | Code for the mechanism by which the exposure agent was exchanged or potentially exchanged by the participants involved in the exposure. | .1.113883.5.1113

GTSAbbreviation | **** MISSING DEFINITIONS **** | .1.113883.5.1022

GenderStatus | **** MISSING DEFINITIONS **** | .1.113883.5.51

HL7UpdateMode | The possible modes of updating that occur when an attribute is received by a system that already contains values for that attribute. | .1.113883.5.57

HtmlLinkType | HtmlLinkType values are drawn from HTML 4.0 and describe the relationship between the current document and the anchor that is the target of the link | .1.113883.5.58

IdentifierReliability | Specifies the reliability with which the identifier is known. This attribute MAY be used to assist with identifier matching algorithms. | .1.113883.5.1117

IdentifierScope | Description: Codes to specify the scope in which the identifier applies to the object with which it is associated, and used in the datatype property II. | .1.113883.5.1116

IntegrityCheckAlgorithm | **** MISSING DEFINITIONS **** | .1.113883.5.1010

LanguageAbilityMode | A value representing the method of expression of the language. Example: Expressed spoken, expressed written, expressed signed, received spoken, received written, received signed. OpenIssue: Description copied from Concept Domain of same name. Must be verified. | .1.113883.5.60

LanguageAbilityProficiency | A value representing the level of proficiency in a language. Example: Excellent, good, fair, poor. OpenIssue: Description copied from Concept Domain of same name. Must be verified. | .1.113883.5.61

LivingArrangement | A code depicting the living arrangements of a person | .1.113883.5.63

LocalMarkupIgnore | Tells a receiver to ignore just the local markup tags (local_markup, local_header, local_attr) when value="markup", or to ignore the local markup tags and all contained content when value="all" | .1.113883.5.65

LocalRemoteControlState | **** MISSING DEFINITIONS **** | .1.113883.5.66

ManagedParticipationStatus | Codes representing the defined possible states of a Managed Participation, as defined by the Managed Participation class state machine. | .1.113883.5.1062

MapRelationship | The closeness or quality of the mapping between the HL7 concept (as represented by the HL7 concept identifier) and the source coding system. The values are patterned after the similar relationships used in the UMLS Metathesaurus. Because the HL7 coding sy | .1.113883.5.67

MaritalStatus | * * * No description supplied * * * Open Issue: The specific meanings of these codes can vary somewhat by jurisdiction and implementation so caution should be used when determining equivalency. | .1.113883.5.2

MessageWaitingPriority | Indicates that the receiver has messages for the sender OpenIssue: Description does not make sense relative to name of coding system. Must be reviewed and improved. | .1.113883.5.1083

ModifyIndicator | **** MISSING DEFINITIONS **** | .1.113883.5.81

NullFlavor | A collection of codes specifying why a valid value is not present. | .1.113883.5.1008

ObservationInterpretation | One or more codes specifying a rough qualitative interpretation of the observation, such as "normal", "abnormal", "below normal", "change up", "resistant", "susceptible", etc. OpenIssue: Description copied from Concept Domain of same name. Must be verified. Note also that this might be identical to the V2 code system of interpretation codes (formerly Abnormal Flags in older versions). | .1.113883.5.83

ObservationMethod | A code that provides additional detail about the means or technique used to ascertain the observation. Examples: Blood pressure measurement method: arterial puncture vs. sphygmomanometer (Riva-Rocci), sitting vs. supine position, etc. OpenIssue: Description copied from Concept Domain of same name. Must be verified. Note that the Domain has a full discussion about use of the attribute and constraining that is not appropriate for the code system description. Needs to be improved. | .1.113883.5.84

ObservationValue | This domain is the root domain to which all HL7-recognized value sets for the Observation.value attribute will be linked when Observation.value has a coded data type. OpenIssue: Description copied from Concept Domain of same name. Must be corrected.. | .1.113883.5.1063

ParticipationFunction | This code is used to specify the exact function an actor had in a service in all necessary detail. This domain may include local extensions (CWE). | .1.113883.5.88

ParticipationMode | A set of codes specifying the modality by which the Entity playing the Role is participating in the Act. Examples: Physically present, over the telephone, written communication. Rationale: Particularly for author (originator) participants this is used to specify whether the information represented by the act was initially provided verbally, (hand-)written, or electronically. Open Issue: There needs to be a reexamination of the hierarchies as there seems to be some muddling between ELECTRONIC and other concepts that involve electronic communication that are in other hierarchies. | .1.113883.5.1064

ParticipationSignature | A set of codes specifying whether and how the participant has attested his participation through a signature and or whether such a signature is needed. Examples: A surgical Procedure act object (representing a procedure report) requires a signature of the performing and responsible surgeon, and possibly other participants. (See also: Participation.signatureText.) | .1.113883.5.89

ParticipationType | **** MISSING DEFINITIONS **** | .1.113883.5.90

PatientImportance | Patient VIP code | .1.113883.5.1075

PaymentTerms | Describes payment terms for a financial transaction, used in an invoice. This is typically expressed as a responsibility of the acceptor or payor of an invoice. | .1.113883.5.91

PersonDisabilityType | A code identifying a person's disability. | .1.113883.5.93

ProbabilityDistributionType | **** MISSING DEFINITIONS **** | .1.113883.5.1020

ProcessingID | Codes used to specify whether a message is part of a production, training, or debugging system. | .1.113883.5.100

ProcessingMode | **** MISSING DEFINITIONS **** | .1.113883.5.101

QueryParameterValue | The domain of coded values used as parameters within QueryByParameter queries. | .1.113883.5.1096

QueryPriority | **** MISSING DEFINITIONS **** | .1.113883.5.102

QueryRequestLimit | Definition: Defines the units associated with the magnitude of the maximum size limit of a query response that can be accepted by the requesting application. | .1.113883.5.1112

QueryResponse | A code classifying the general nature of the response to a given query. Includes whether or not data was found, or whether an error occurred. | .1.113883.5.1067

QueryStatusCode | A code specifying the state of the Query. | .1.113883.5.103

Race | In the United States, federal standards for classifying data on race determine the categories used by federal agencies and exert a strong influence on categorization by state and local agencies and private sector organizations. The federal standards do not conceptually define race, and they recognize the absence of an anthropological or scientific basis for racial classification. Instead, the federal standards acknowledge that race is a social-political construct in which an individual's own identification with one more race categories is preferred to observer identification. The standards use a variety of features to define five minimum race categories. Among these features are descent from "the original peoples" of a specified region or nation. The minimum race categories are American Indian or Alaska Native, Asian, Black or African American, Native Hawaiian or Other Pacific Islander, and White. The federal standards stipulate that race data need not be limited to the five minimum categories, but any expansion must be collapsible to those categories. | .1.113883.5.104

RelationalOperator | **** MISSING DEFINITIONS **** | .1.113883.5.105

RelationshipConjunction | **** MISSING DEFINITIONS **** | .1.113883.5.106

ReligiousAffiliation | Assigment of spiritual faith affiliation | .1.113883.5.1076

ResponseLevel | Specifies whether a response is expected from the addressee of this interaction and what level of detail that response should include | .1.113883.5.108

ResponseModality | Defines the timing and grouping of the response instances. OpenIssue: Description copied from Concept Domain of same name. Must be verified. | .1.113883.5.109

ResponseMode | Specifies the mode, immediate versus deferred or queued, by which a receiver should communicate its receiver responsibilities. | .1.113883.5.1126

RoleClass | Codes for the Role class hierarchy. The values in this hierarchy, represent a Role which is an association or relationship between two entities - the entity that plays the role and the entity that scopes the role. Roles names are derived from the name of the playing entity in that role. The role hierarchy stems from three core concepts, or abstract domains: RoleClassOntological is an abstract domain that collects roles in which the playing entity is defined or specified by the scoping entity. RoleClassPartitive collects roles in which the playing entity is in some sense a "part" of the scoping entity. RoleClassAssociative collects all of the remaining forms of association between the playing entity and the scoping entity. This set of roles is further partitioned between: RoleClassPassive which are roles in which the playing entity is used, known, treated, handled, built, or destroyed, etc. under the auspices of the scoping entity. The playing entity is passive in these roles in that the role exists without an agreement from the playing entity. RoleClassMutualRelationship which are relationships based on mutual behavior of the two entities. The basis of these relationship may be formal agreements or they may bede facto behavior. Thus, this sub-domain is further divided into: RoleClassRelationshipFormal in which the relationship is formally defined, frequently by a contract or agreement. Personal relationship which inks two people in a personal relationship. The hierarchy discussed above is represented In the current vocabulary tables as a set of abstract domains, with the exception of the "Personal relationship" which is a leaf concept. OpenIssue: Description copied from Concept Domain of same name. Must be verified. | .1.113883.5.110

RoleCode | A set of codes further specifying the kind of Role; specific classification codes for further qualifying RoleClass codes. | .1.113883.5.111

RoleLinkStatus | Description: Codes representing possible states of a RoleLink, as defined by the RoleLink class state machine. | .1.113883.5.1137
RoleLinkType | **** MISSING DEFINITIONS **** | .1.113883.5.107
RoleStatus | Codes representing the defined possible states of an Role, as defined by the Role class state machine. | .1.113883.5.1068
RouteOfAdministration | The path the administered medication takes to get into the body or into contact with the body. | .1.113883.5.112
Sequencing | Specifies sequence of sort order. | .1.113883.5.113
SetOperator | **** MISSING DEFINITIONS **** | .1.113883.5.1069
SpecimenType | **** MISSING DEFINITIONS **** | .1.113883.5.129
SubstitutionCondition | Identifies what sort of change is permitted or has occurred between the item that was ordered/requested and the one that was/will be provided. | .1.113883.5.1071
TableCellHorizontalAlign | These values are defined within the XHTML 4.0 Table Model | .1.113883.5.131
TableCellScope | These values are defined within the XHTML 4.0 Table Model | .1.113883.5.132
TableCellVerticalAlign | These values are defined within the XHTML 4.0 Table Model | .1.113883.5.133
TableFrame | These values are defined within the XHTML 4.0 Table Model | .1.113883.5.134
TableRules | These values are defined within the XHTML 4.0 Table Model | .1.113883.5.136
TargetAwareness | **** MISSING DEFINITIONS **** | .1.113883.5.137
TelecommunicationCapabilities | Description: Concepts that define the telecommunication capabilities of a particular device. Used to identify the expected capabilities to be found at a particular telecommunication address. | .1.113883.5.1118
TimingEvent | **** MISSING DEFINITIONS **** | .1.113883.5.139
TransmissionRelationshipTypeCode | Description: A code specifying the meaning and purpose of every TransmissionRelationship instance. Each of its values implies specific constraints to what kinds of Transmission objects can be related and in which way. | .1.113883.5.1111
TribalEntityUS | INDIAN ENTITIES RECOGNIZED AND ELIGIBLE TO RECEIVE SERVICES FROM THE UNITED STATES BUREAU OF INDIAN AFFAIRS | .1.113883.5.140
VaccineManufacturer | The manufacturer of a vaccine. | .1.113883.5.144
hl7Realm | Description: Coded concepts representing Binding Realms (used for Context Binding of terminology in HL7 models) and/or Namespace Realms (used to help ensure unique identification of HL7 artifacts). This code system is partitioned into three sections: Affiliate realms, Binding realms and Namespace realms. All affiliate realm codes may automatically be used as both binding realms and namespace realms. Furthermore, affiliate realms are the only realms that have authority over the creation of binding realms. (Note that 'affiliate' includes the idea of both international affiliates and the HL7 International organization.) All other codes must be associated with an owning affiliate realm and must appear as a specialization of _BindingRealm or _NamespaceRealm. For affiliates whose concepts align with nations, the country codes from ISO 3166-1 2-character alpha are used for the code when possible so these codes should not be used for other realm types. It is recommended that binding realm and namespace codes submitted by affiliates use the realm code as a prefix to avoid possible collisions with ISO codes. However, tooling does not currently support namepace realm codes greater than 2 characters. Open Issue: The name of the concept property "owningAffiliate" should be changed to better reflect that the property value is the human readable name of the organizational entity that manages the Realm identified by the Realm Code. Open Issue: In spite of the inability of tooling to process codes longer than 2 characters, there is at least one realm codes ('SOA') that was added that is 3 characters in length. | .1.113883.5.1124
hl7V3Conformance | Description: Identifies allowed codes for HL7aTMs v3 conformance property. | .1.113883.5.1125
orderableDrugForm | OpenIssue: Missing description. | .1.113883.5.85
substanceAdminSubstitution | Identifies what sort of change is permitted or has occurred between the therapy that was ordered and the therapy that was/will be provided. | .1.113883.5.1070

URI (all prefixed with http://hl7.org/fhir/v2/) | ID | OID
0001 | Administrative Sex
0002 | Marital Status
0003 | Event Type
0004 | Patient Class
0006 | ReligionVersion Dependent. Use one of: 2.1+ 2.4+
0007 | Admission Type
0008 | Acknowledgment code
0009 | Ambulatory Status
0012 | STOCK LOCATION
0017 | Transaction Type
0023 | Admit Source
0027 | Priority
0033 | ROUTE
0034 | SITE ADMINISTERED
0038 | Order status
0043 | Condition Code
0048 | What subject filter
0052 | Diagnosis Type
0061 | Check Digit Scheme
0062 | Event Reason
0063 | Relationship
0065 | Specimen Action Code
0066 | Employment Status
0069 | Hospital Service
0070 | Specimen Source Codes
0074 | Diagnostic Service Section ID
0076 | Message Type
0078 | Interpretation Codes
0080 | Nature of Abnormal Testing
0083 | Outlier Type
0085 | Observation Result Status Codes Interpretation
0091 | Query Priority
0092 | Re-Admission Indicator

0098 | Type of Agreement
0100 | Invocation event
0102 | Delayed acknowledgment type
0103 | Processing ID
0104 | Version ID
0105 | Source of Comment
0106 | Query/response format code
0107 | Deferred response type
0108 | Query results level
0109 | Report priority
0116 | Bed Status
0119 | Order Control Codes
0121 | Response Flag
0122 | Charge Type
0123 | Result Status
0124 | Transportation Mode
0126 | Quantity Limited Request
0127 | Allergen Type
0128 | Allergy Severity
0130 | Visit User Code
0131 | Contact Role
0133 | Procedure Practitioner Identifier Code Type
0135 | Assignment of Benefits
0136 | Yes/no Indicator
0137 | Mail Claim Party
0140 | Military Service
0141 | Military Rank/Grade
0142 | Military Status
0144 | Eligibility Source
0145 | Room Type
0146 | Amount Type
0147 | Policy Type
0148 | Money or Percentage Indicator
0149 | Day Type
0150 | Certification Patient Type
0153 | Value Code
0155 | Accept/Application Acknowledgment Conditions
0156 | Which date/time qualifier
0157 | Which date/time status qualifier
0158 | Date/time selection qualifier
0159 | Diet Code Specification Type
0160 | Tray Type
0161 | Allow Substitution
0162 | Route of Administration
0163 | Body Site
0164 | Administration Device
0165 | Administration Method
0166 | RX Component Type
0167 | Substitution Status
0168 | Processing Priority
0169 | Reporting Priority
0170 | Derived Specimen
0173 | Coordination of Benefits
0174 | Nature of Service/Test/Observation
0175 | Master File Identifier Code
0177 | Confidentiality Code
0178 | File Level Event Code
0179 | Response Level
0180 | Record-level Event Code
0181 | MFN Record-level Error Return
0183 | Active/Inactive
0185 | Preferred Method of Contact
0187 | Provider Billing
0189 | Ethnic Group
0190 | Address Type
0191 | Type of Referenced Data
0193 | Amount Class
0200 | Name Type
0201 | Telecommunication Use Code
0202 | Telecommunication Equipment Type
0203 | Identifier Type
0204 | Organizational Name Type

0205 | Price Type
0206 | Segment Action Code
0207 | Processing Mode
0208 | Query Response Status
0209 | Relational Operator
0210 | Relational Conjunction
0211 | Alternate Character Sets
0213 | Purge Status Code
0214 | Special Program Code
0215 | Publicity Code
0216 | Patient Status Code
0217 | Visit Priority Code
0220 | Living Arrangement
0223 | Living Dependency
0224 | Transport Arranged
0225 | Escort Required
0227 | Manufacturers of Vaccines (code=MVX)
0228 | Diagnosis Classification
0229 | DRG Payor
0230 | Procedure Functional Type
0231 | Student Status
0232 | - Insurance Company Contact Reason
0234 | Report Timing
0235 | Report Source
0236 | Event Reported To
0237 | Event Qualification
0238 | Event Seriousness
0239 | Event Expected
0240 | Event Consequence
0241 | Patient Outcome
0242 | Primary Observer's Qualification
0243 | Identity May Be Divulged
0247 | Status of Evaluation
0248 | Product Source
0250 | Relatedness Assessment
0251 | Action Taken in Response to the Event
0252 | Causality Observations
0253 | Indirect Exposure Mechanism
0254 | Kind of Quantity
0255 | Duration Categories
0256 | Time Delay Post Challenge
0257 | Nature of Challenge
0258 | Relationship Modifier
0259 | Modality
0260 | Patient Location Type
0261 | Location Equipment
0262 | Privacy Level
0263 | Level of Care
0265 | Specialty Type
0267 | Days of the Week
0268 | Override
0269 | Charge On Indicator
0270 | Document Type
0271 | Document Completion Status
0272 | Document Confidentiality Status
0273 | Document Availability Status
0275 | Document Storage Status
0276 | Appointment reason codes
0277 | Appointment Type Codes
0278 | Filler status codes
0279 | Allow Substitution Codes
0280 | Referral Priority
0281 | Referral Type
0282 | Referral Disposition
0283 | Referral Status
0284 | Referral Category
0286 | Provider Role
0287 | Problem/Goal Action Code
0290 | MIME base64 encoding characters
0291 | Subtype of Referenced Data
0292 | Vaccines Administered (code = CVX) (parenteral, un
0294 | Time Selection Criteria Parameter Class Codes

0298 | CP Range Type
0299 | Encoding
0301 | Universal ID Type
0305 | Person Location Type
0309 | Coverage Type
0311 | Job Status
0315 | Living Will Code
0316 | Organ Donor Code
0317 | Annotations
0321 | Dispense Method
0322 | Completion Status
0323 | Action Code
0324 | Location Characteristic ID
0325 | Location Relationship ID
0326 | Visit Indicator
0329 | Quantity Method
0330 | Marketing Basis
0331 | Facility Type
0332 | Source Type
0334 | Disabled Person Code
0335 | Repeat Pattern
0336 | Referral Reason
0337 | Certification Status
0338 | Practitioner ID Number Type
0339 | Advanced Beneficiary Notice Code
0344 | Patient's Relationship to Insured
0350 | Occurrence Code
0351 | Occurrence Span
0354 | Message Structure
0355 | Primary Key Value Type
0356 | Alternate Character Set Handling Scheme
0357 | Message Error Condition Codes
0359 | Diagnosis Priority
0360 | Degree/License/CertificateVersion Dependent. Use one of: 2.3.1+ 2.7+
0363 | Assigning Authority
0364 | Comment Type
0365 | Equipment State
0366 | Local/Remote Control State
0367 | Alert Level
0368 | Remote Control Command
0369 | Specimen Role
0370 | Container Status
0371 | Additive/Preservative
0372 | Specimen Component
0373 | Treatment
0374 | System Induced Contaminants
0375 | Artificial Blood
0376 | Special Handling Code
0377 | Other Environmental Factors
0383 | Substance Status
0384 | Substance Type
0387 | Command Response
0388 | Processing Type
0389 | Analyte Repeat Status
0391 | Segment GroupVersion Dependent. Use one of: 2.4+ 2.6+
0392 | Match Reason
0393 | Match Algorithms
0394 | Response Modality
0395 | Modify Indicator
0396 | Coding System
0397 | Sequencing
0398 | Continuation Style Code
0401 | Government Reimbursement Program
0402 | School Type
0403 | Language Ability
0404 | Language Proficiency
0406 | Organization Unit Type
0409 | Application Change Type
0411 | Supplemental Service Information Values
0415 | Transfer Type
0416 | Procedure DRG Type
0417 | Tissue Type Code

0418 | Procedure Priority
0421 | Severity of Illness Code
0422 | Triage Code
0423 | Case Category Code
0424 | Gestation Category Code
0425 | Newborn Code
0426 | Blood Product Code
0427 | Risk Management Incident Code
0428 | Incident Type Code
0429 | Production Class Code
0430 | Mode of Arrival Code
0431 | Recreational Drug Use Code
0432 | Admission Level of Care Code
0433 | Precaution Code
0434 | Patient Condition Code
0435 | Advance Directive Code
0436 | Sensitivity to Causative Agent Code
0437 | Alert Device Code
0438 | Allergy Clinical Status
0440 | Data Types
0441 | Immunization Registry Status
0442 | Location Service Code
0443 | Provider Role
0444 | Name Assembly Order
0445 | Identity Reliability Code
0450 | Event Type
0455 | Type of Bill Code
0456 | Revenue code
0457 | Overall Claim Disposition Code
0459 | Reimbursement Action Code
0460 | Denial or Rejection Code
0465 | Name/Address Representation
0466 | Ambulatory Payment Classification Code
0468 | Payment Adjustment Code
0469 | Packaging Status Code
0470 | - Reimbursement Type Code
0472 | TQ Conjunction ID
0473 | Formulary Status
0474 | Organization Unit Type
0475 | Charge Type Reason
0477 | Controlled Substance Schedule
0478 | Formulary Status
0480 | Pharmacy Order Types
0482 | Order Type
0483 | Authorization Mode
0484 | Dispense Type
0485 | Extended Priority Codes
0487 | Specimen Type
0488 | Specimen Collection Method
0489 | Risk Codes
0490 | Specimen Reject Reason
0491 | Specimen Quality
0492 | Specimen Appropriateness
0493 | Specimen Condition
0494 | Specimen Child Role
0495 | Body Site Modifier
0496 | Consent Type
0497 | Consent Mode
0498 | Consent Status
0499 | Consent Bypass Reason
0500 | Consent Disclosure Level
0501 | Consent Non-Disclosure Reason
0502 | Non-Subject Consenter Reason
0503 | Sequence/Results Flag
0504 | Sequence Condition Code
0505 | Cyclic Entry/Exit Indicator
0506 | Service Request Relationship
0507 | Observation Result Handling
0508 | Blood Product Processing Requirements
0510 | Blood Product Dispense Status
0511 | BP Observation Status Codes Interpretation
0513 | Blood Product Transfusion/Disposition Status

0514 | Transfusion Adverse Reaction
0516 | Error Severity
0517 | Inform Person Code
0518 | Override Type
0520 | Message Waiting Priority
0523 | Computation Type
0524 | Sequence condition
0527 | Calendar Alignment
0528 | Event Related Period
0529 | Precision
0530 | Organization, Agency, Department
0534 | Notify Clergy Code
0535 | Signature Code
0536 | Certificate Status
0538 | Institution Relationship Type
0540 | Inactive Reason Code
0544 | Container Condition
0547 | Jurisdictional Breadth
0548 | Signatory's Relationship to Subject
0550 | Body Parts
0553 | Invoice Control Code
0554 | Invoice Reason Codes
0555 | Invoice Type
0556 | Benefit Group
0557 | Payee Type
0558 | Payee Relationship to Invoice
0559 | Product/Service Status
0561 | Product/Services Clarification Codes
0562 | Processing Consideration Codes
0564 | Adjustment Category Code
0565 | Provider Adjustment Reason Code
0566 | Blood Unit Type
0569 | Adjustment Action
0570 | Payment Method Code
0571 | Invoice Processing Results Status
0572 | Tax status
0615 | User Authentication Credential Type Code
0616 | Address Expiration Reason
0617 | Address Usage
0618 | Protection Code
0625 | Item Status Codes
0634 | Item Importance Codes
0642 | Reorder Theory Codes
0651 | Labor Calculation Type
0653 | Date Format
0657 | Device Type
0659 | Lot Control
0667 | Device Data State
0669 | Load Status
0682 | Device Status
0702 | Cycle Type
0717 | Access Restriction Value
0719 | Access Restriction Reason Code
0725 | Mood Codes
0728 | CCL Value
0731 | DRG Diagnosis Determination Status
0734 | Grouper Status
0739 | DRG Status Patient
0742 | DRG Status Financial Calculation
0749 | DRG Grouping Status
0755 | Status Weight At Birth
0757 | DRG Status Respiration Minutes
0759 | Status Admission
0761 | DRG Procedure Determination Status
0763 | DRG Procedure Relevance
0776 | Item Status
0778 | Item Type
0790 | Approving Regulatory Agency
0793 | Ruling Act
0806 | Sterilization Type
0818 | Package
0834 | MIME Types

0868 | Telecommunication Expiration Reason
0871 | Supply Risk Codes
0881 | Role Executing Physician
0882 | Medical Role Executing Physician
0894 | Side of body
0895 | Present On Admission (POA) Indicator
0904 | Security Check Scheme
0905 | Shipment Status
0906 | ActPriority
0907 | Confidentiality
0909 | Patient Results Release Categorization Scheme
0912 | Participation
0914 | Root Cause
0916 | Relevant Clincial Information
0917 | Bolus Type
0918 | PCA Type
0919 | Exclusive Test
0920 | Preferred Specimen/Attribute Status
0921 | Certification Type Code
0922 | Certification Category Code
0923 | Process Interruption
0924 | Cumulative Dosage Limit UoM
0925 | Phlebotomy Issue
0926 | Phlebotomy Status
0927 | Arm Stick
0933 | Intended Procedure Type
0935 | Process Interruption Reason
4000 | Name/address representation

4.2.0.3 ICD-10

URL: https://hl7.org/fhir/STU3/sid/icd-10/index.html

This page is part of the FHIR Specification (v3.0.2: STU 3). The current version which supercedes this version is 4.0.1. For a full list of available versions, see the Directory of published versions

4.2.0.3.0 ICD-10

The URL "http://hl7.org/fhir/sid/icd-10" is the FHIR system identifier for codes defined in the ICD-10 International code system. The source of this code system is the WHO, at http://www.who.int/classifications/icd/en/ .

4.2.1 Using SNOMED CT with FHIR

URL: https://hl7.org/fhir/STU3/snomedct.html

This page is part of the FHIR Specification (v3.0.2: STU 3). The current version which supercedes this version is 4.0.1. For a full list of available versions, see the Directory of published versions

4.2.1.0 Using SNOMED CT with FHIR

Vocabulary Work Group | Maturity Level: 5 | Ballot Status: Trial Use

4.2.1.0.1 Summary

Source | SNOMED CT is owned, maintained and distributed by IHTSDO . IHTSDO is an international organization with countries as members. IHTSDO publishes the international release of SNOMED CT (which is used in FHIR international standards and resources). Each of the IHTSDO member countries may also distribute their own SNOMED CT edition, which contains the international release plus local extension content and derivatives.

System | The URI http://snomed.info/sct identifies the SNOMED CT code system.

Version | Where a version is used, it should be a full URI that represents the specific distribution (International Release, or National Release and version), following the SNOMED CT URI Specification (see note below)

Code | The following SNOMED CT artifacts are valid in the code element for the http://snomed.info/sct namespace: Concept IDs , Expressions (grammar) and SNOMED Legacy codes . SNOMED CT Terms (Description Ids) are not valid as codes in FHIR, nor are other alternate identifiers associated with SNOMED CT Concepts using the RF2 identifier infrastructure. Expressions SHOULD NOT contain terms, only concept IDs (note that when SNOMED CT terms must be exchanged, use the Description Id Extension)

Display | The correct display for a SNOMED CT concept is one of the synonyms for the concept. The best display is the preferred term in the relevant language reference set (if applicable). Preferred terms are case sensitive. The Fully Specified Name is not an appropriate choice. The source of preferred name comes from a Language Reference Set. SNOMED CT does not define displays for expressions; if no display has been associated with the expression through a value set or other mechanism, the full expression syntax with preferred terms embedded may be used

Inactive | Inactive codes are identified using the 'inactive' property (see below)

Subsumption | SNOMED CT Subsumption testing is based in the |is a| relationship defined by SNOMED CT

Filter Properties | Several properties are defined as described below

This specification publishes a canonical SNOMED CT code system resource. See also the SNOMED CT Usage Summary.

Note: The IHTSDO glossary explains some of these SNOMED CT specific terms.

4.2.1.0.2 Version Issues

There is no single distribution that contains all defined SNOMED CT codes in all contexts of use. Instead the international release contains all concepts shared and agreed to be internationally relevant and each national release centre distributes this international release plus additional national content (to extend that international set). In addition, other release authorities may be designated. The SNOMED CT URI Specification describes how to unambiguously reference a particular version of a distribution:

```
http://snomed.info/sct/[sctid]/version/[YYYYMMDD]
```

where [sctid] is the concept id of the SNOMED CT distribution (e.g. 32506021000036107 for Australia), and the tail is the date of release (by custom, this is usually the last day of the month). Note that many implementations are in the habit of simple using the date of release in the form YYYYMMDD (e.g. "20140531"), and assuming that the distribution is known. However this is not always safe, so implementations that populate the version element SHOULD use the full URI form.

4.2.1.0.3 Copyright/License Issues

The use of SNOMED CT codes, display names and value sets in this specification is subject to an MOU signed between HL7 International and IHTSDO. This does not convey the right to use SNOMED CT to any users of this specification; implementers must acquire a license to use SNOMED CT in their own right. See HL7 Policies and Guidance documents – Licensing .

4.2.1.0.4 RDF

The IHTSDO URI specifications uses the namespace http://snomed.info/sct for the code system, and the URI http://snomed.info/id for the individual concepts in the code system. This means that when a SNOMED CT concept is converted from the system::code pair, where the system is http://snomed.info/sct, to the RDF ontological form, the representation is http://snomed.info/id/[concept-id]. Expressions are represented the same way, except that for this use, expressions SHALL not contain whitespace, terms, or comments.

4.2.1.0.5 SNOMED CT Properties

In addition to the standard properties, the following properties are defined for SNOMED CT:

inactive | boolean | Whether the code is active or not (defaults to false). This is derived from the active column in the Concept file of the RF2 Distribution (by inverting the value)
sufficientlyDefined | boolean | True if the description logic definition of the concept includes sufficient conditions (i.e., if the concept is not primitive - found in the value of definitionStatusId in the concept file).
moduleId | code | The SNOMED CT concept id of the module that the concept belongs to.
normalForm | string | Generated Normal form expression for the provided code or expression, with terms
normalFormTerse | string | Generated Normal form expression for the provided code or expression, conceptIds only

In addition, any SNOMED CT relationships where the relationship type is subsumed by Attribute (246061005) automatically become properties. For example, laterality:

Laterality | code | In this case, the URI (See the code system definition) is http://snomed.info/id/272741003, which can be used to unambiguously map to the underlying concept

Note that when a $lookup operation is performed on a SNOMED CT concept, servers SHALL return the full URI for the edition and version being used (see above) in the version property. Other properties are at the discretion of the server and the client.

4.2.1.0.6 SNOMED CT Filters

This section documents the property filters that can be used with the SNOMED CT code system in value set composition statements.

For implementer convenience, some of the property filters are documented in terms of the SNOMED CT Query Language , but this does not imply that its use is required.

4.2.1.0.6.1 By Subsumption

Description | Select a set of concepts based on subsumption testing
Property Name | concept
Operations Allowed | is-a
Values Allowed | [concept id]
Comments | Includes all concept ids that have a transitive is-a relationship with the concept Id provided as the value (including the concept itself)
Example | Administration Methods
SCT ECL | << [concept] (or the long form: descendantOrSelfOf [concept])

4.2.1.0.6.2 By Reference Set

Description | Select a set of concepts based on their membership of a SNOMED CT reference set
Property Name | concept
Operations Allowed | in
Values Allowed | [concept id]
Comments | Includes all concept ids that are active members of the reference set identified by the concept Id provided as the value
SCT ECL | ^ [concept] (or the long form: memberOf [concept])

4.2.1.0.6.3 By SNOMED Query Expression

Description | Select a set of concepts based on a formal expression statement
Property Name | constraint

Operations Allowed | =

Values Allowed | [expression]

Comments | The result of the filter is the result of executing the given SNOMED CT Expression (Expression Constraint Language) . Example: "compose": { "include": [{ "system": "http://snomed.info/sct", "filter": [{ "property": "constraint", "op": "=", "value": "<< 30506011000036107 |Australian product|: 700000101000036108 |hasTP| = 17311000168105 |Panadol|" }] }] }

4.2.1.0.6.4 By whether post-coordination is allowed

Description | Specify whether post-coordination is allowed or not

Property Name | expressions

Operations Allowed | =

Values Allowed | true or false

Comments | Expressions, if allowed, are subject to the same rules as pre-coordinated concepts. Note: simple reference sets do not include expressions, but Query specification reference sets might).

Example | Administration Methods

SCT ECL | n/a

4.2.1.0.7 Implicit Value Sets

Implicit value sets are those whose specification can be predicted based on the grammar of the underlying code system, and the known structure of the URL that identifies them. SNOMED CT has two common sets of implicit value sets defined: By Subsumption, and By Reference Set. These implicit value sets do not use complex queries. This allows a single URL to serve as a value set definition that defines a value set, and can serve as the basis for the $expansion operation.

If any value set resources exist with an identifier that conforms to the URL patterns specified below, the content of the resource must conform to the template provided. Profiles and other value set references are allowed to reference these value sets directly (by reference as a URI, rather than by a value set reference, which is a literal reference).

A SNOMED CT implicit value set URL has two parts:

* the base URL is either "http://snomed.info/sct", or the URI for the edition version, in the format specified by the IHTSDO the SNOMED CT URI Specification

* a query portion that specifies the scope of the content

"http://snomed.info/sct" should be understood to mean an unspecified edition/version. This defines an incomplete value set whose actual membership will depend on the particular edition used when it is expanded. If no version or edition is specified, the terminology service SHALL use the latest version available for its default edition (or the international edition, if no other edition is the default).

For the second part of the URL (the query part), the 4 possible values are:

* ?fhir_vs - all Concept IDs in the edition/version. If the base URI is http://snomed.info/sct, this means all possible SNOMED CT concepts

* ?fhir_vs=isa/[sctid] - all concept IDs that are subsumed by the specified Concept.

* ?fhir_vs=refset - all concept ids that correspond to real references sets defined in the specified SNOMED CT edition

* ?fhir_vs=refset/[sctid] - all concept IDs in the specified reference set

A value set with a URL that follows the pattern "[edition/version]?fhir_vs=isa/[sctid]" follows this template:

```
<ValueSet xmlns="http://hl7.org/fhir">
  <text>
    <status value="generated"/>
    <div xmlns="http://www.w3.org/1999/xhtml">
     [Some HTML that describes this value set as all concepts subsumed by conceptid]
    </div>
  </text>
  <url value="[edition/version]?fhir_vs=isa/[sctid]"/>
  <version value="[edition/version]"/>
  <name value="SNOMED CT Concept [conceptid] and descendants"/>
  <description value="All SNOMED CT concepts for [concept id or preferred description]"/>
  <copyright value="This value set includes content from SNOMED CT, which is copyright © 2002+ International Health
    Terminology Standards Development Organisation (IHTSDO), and distributed by agreement between IHTSDO and HL7.
    Implementer use of SNOMED CT is not covered by this agreement"/>
  <status value="active"/>
  <compose>
    <include>
      <system value="http://snomed.info/sct"/>
      <filter>
        <property value="concept"/>
        <op value="is-a"/>
        <value value="[sctid]"/>
      </filter>
    </include>
  </compose>
</ValueSet>
```

The value set with a url that follows the pattern "[edition/version]?fhir_vs=refset" follows this template:

```
<ValueSet xmlns="http://hl7.org/fhir">
  <text>
    <status value="generated"/>
    <div xmlns="http://www.w3.org/1999/xhtml">
     [Some HTML that describes this value set as all concepts with associated reference sets]
```

```
    </div>
  </text>
  <url value="[edition/version]?fhir_vs=refset"/>
  <version value="[edition/version]"/>
  <name value="SNOMED CT Reference Sets"/>
  <description value="All SNOMED CT concepts associated with a reference set"/>
  <copyright value="This value set includes content from SNOMED CT, which is copyright © 2002+ International Health
    Terminology Standards Development Organisation (IHTSDO), and distributed by agreement between IHTSDO and HL7.
    Implementer use of SNOMED CT is not covered by this agreement"/>
  <status value="active"/>
  <compose>
    <include>
      <system value="http://snomed.info/sct"/>
      <!-- repeat: one concept element with a code for each concept that has an associated reference set -->
      <concept>
        <code value="[sctid]"/>
      </concept>
      <!-- end repeat -->
    </include>
  </compose>
</ValueSet>
```

For each concept that is associated with a reference set, there will be one concept element with a contained code that contains the concept id.

A value set with a url that follows the pattern "[edition/version]?fhir_vs=refset/[conceptid]" follows this template:

```
<ValueSet xmlns="http://hl7.org/fhir">
  <text>
    <status value="generated"/>
    <div xmlns="http://www.w3.org/1999/xhtml">
     [Some HTML that describes this value set as all concepts in the reference set identified by conceptid]
    </div>
  </text>
  <url value="[edition/version]?fhir_vs=refset/[sctid]"/>
  <version value="[edition/version]"/>
  <name value="SNOMED CT Reference Set [conceptid]"/>
  <description value="All SNOMED CT concepts in the reference set [concept id or preferred description]"/>
  <copyright value="This value set includes content from SNOMED CT, which is copyright © 2002+ International Health
    Terminology Standards Development Organisation (IHTSDO), and distributed by agreement between IHTSDO and HL7.
    Implementer use of SNOMED CT is not covered by this agreement"/>
  <status value="active"/>
  <compose>
    <include>
      <system value="http://snomed.info/sct"/>
      <filter>
        <property value="concept"/>
        <op value="in"/>
        <value value="[conceptid]"/>
      </filter>
    </include>
  </compose>
</ValueSet>
```

4.2.1.0.8 Implicit Concept Maps

Implicit concept maps are those whose specification can be predicted based on the grammar and/or content of the underlying code system, and the known structure of the URL that identifies them. This allows a single URL to serve as a concept map definition that defines a mapping between two sets of concepts, and which can serve as the basis for the $translate operation. SNOMED CT has two common sets of implicit concept maps defined:

* Association Reference Sets

* Simple Map Reference Sets

Association Reference Sets are part of the core SNOMED CT distribution. The following standard Association Reference sets are mapped to implicit Concept Maps:

Name	Concept Id	Relationship
POSSIBLY EQUIVALENT TO	900000000000523009	inexact
REPLACED BY	900000000000526001	equivalent
SAME AS	900000000000527005	equal
ALTERNATIVE	900000000000530003	inexact

If any concept map resources exist with an identifier that conforms to the URL pattern specified below, the content of the resource must conform to the template provided. Canonical references to concept maps are allowed to reference these concept maps directly by referring to their URI.

A SNOMED CT implicit concept map URL has two parts:

* the base URL is either "http://snomed.info/sct", or the URI for the edition version, in the format specified by the IHTSDO the SNOMED CT URI Specification

* a query portion that specifies the scope of the content

"http://snomed.info/sct" should be understood to mean an unspecified edition/version. This defines an incomplete concept map whose actual membership will depend on the particular edition used when it is expanded. If no version or edition is specified, the terminology service SHALL use the latest version available for its default edition (or the international edition, if

no other edition is the default).

For the second part of the URL (the query part), there is only one possible value:

* ?fhir_cm=[sctid] - where [sctid] is a value from the table above

A concept map with a URL that follows the pattern "[edition/version]?fhir_cm=[sctid]" follows this template, where [name], [sctid] and [relationship] are taken from the table above:

```
<ConceptMap xmlns="http://hl7.org/fhir">
  <text>
    <status value="generated"/>
    <div xmlns="http://www.w3.org/1999/xhtml">
     [Some HTML that describes this concept map]
    </div>
  </text>
  <url value="[edition/version]?fhir_cm=[sctid]"/>
  <version value="[edition/version]"/>
  <name value="SNOMED CT [name] Concept Map"/>
  <description value="The concept map implicitly defined by the [name] Association Reference Set"/>
  <copyright value="This value set includes content from SNOMED CT, which is copyright © 2002+ International Health
    Terminology Standards Development Organisation (IHTSDO), and distributed by agreement between IHTSDO and HL7.
    Implementer use of SNOMED CT is not covered by this agreement"/>
  <status value="active"/>

  <sourceUri value="[edition/version]?fhir_vs"/>
  <targetUri value="[edition/version]?fhir_vs"/>
  <group>  <!-- 0..* Same source and target systems -->
    <source value="http://snomed.info/sct"/>
    <sourceVersion value="[edition/version]"/>
    <target value="http://snomed.info/sct"/>
    <targetVersion value="[edition/version]"/>

    <!-- a mapping for each member of the reference set -->
    <element>
      <code value="[member]"/>
      <target>
        <code value="[reference set value]"/>
        <equivalence value="[relationship]"/>
      </target>
    </element>
  </group>
</ConceptMap>
```

Simple Map Reference Sets (reference sets which are descendants of 900000000000496009 "Simple map") also define an implicit concept map. However, at this time, these cannot be converted to Concept Maps because there is no source for the target code system. Another reference set has been proposed to IHTSDO, and this section will be revisited once it is adopted.

4.2.1.1 SNOMED CT in FHIR

URL: https://hl7.org/fhir/STU3/snomedct-usage.html

This page is part of the FHIR Specification (v3.0.2: STU 3). The current version which supercedes this version is 4.0.1. For a full list of available versions, see the Directory of published versions

4.2.1.1 SNOMED CT in FHIR

This page summarizes the use of SNOMED CT in the base FHIR Specification. It is used by HL7 and IHTSDO to help with SNOMED CT licensing management.

In principle, this base FHIR Specification only uses concepts defined in the International distribution of SNOMED CT, while FHIR implementation guides that use SNOMED CT are generally published by HL7 Affiliates under agreements with National distribution centers. However, there are some US specific codes on this page; HL7 is working with IHTSDO towards remove these from the specification (hopefully they will be elevated to the international SNOMED CT distribution).

4.2.1.1.1 Value Sets

The following value sets reference SNOMED CT. The table lists the value sets, and then the places they are used from, and includes the binding strengths

Name | Definition | CLD | Usage

Activity Reason | Example codes indicating the reason for a clinical activity being performed. | is-a Clinical finding | CarePlan.activity.detail.reasonCode (Example)

SNOMED CT Additional Dosage Instructions | This value set includes all SNOMED CT Additional Dosage Instructions. | is-a Additional dosage instructions | This value set is not currently used

SNOMED CT Administration Method Codes | This value set includes some method codes from SNOMED CT - provided as an exemplar | is-a Dosing instruction fragment | MedicationAdministration.dosage.method (Example)

SNOMED CT Clinical Findings | This value set includes all SNOMED CT Clinical Findings. | is-a Clinical finding | AdverseEvent.type (Example)

AllergyIntolerance Substance/Product, Condition and Negation Codes | This value set includes concept codes for specific substances/pharmaceutical products, allergy or intolerance conditions, and negation/exclusion codes to specify the absence of specific types of allergies or intolerances. | is-a Propensity to adverse reactions to substance is-a Lactose intolerance is-a Syndrome of carbohydrate intolerance is-a Lysine intolerance is-a Sucrose intolerance is-a Acquired fructose intolerance is-a No known allergy other code systems | AllergyIntolerance.code (Example)

AnimalBreeds | This example value set defines a set of codes that can be used to indicate breeds of species. | 2370 enumerated concepts | Patient.animal.breed (Example)

AnimalSpecies | This example value set defines a set of codes that can be used to indicate species of animal patients. | 10 enumerated concepts | This value set is the designated 'entire code system' value set for AnimalSpecies Patient.animal.species (Example) Extension http://hl7.org/fhir/StructureDefinition/practitioner-animalSpecies: animalSpecies ((Example))

SNOMED CT Anatomical Structure for Administration Site Codes | This value set includes Anatomical Structure codes from SNOMED CT - provided as an exemplar. | is-a Anatomical structure | MedicationAdministration.dosage.site (Example) Dosage.site (Example)

SNOMED CT Body Structures | This value set includes all codes from [SNOMED CT](http://snomed.info/sct) where concept is-a 442083009 (Anatomical or acquired body site (body structure)). | is-a Anatomical or acquired body structure | ImagingStudy.series.bodySite (Example) ChargeItem.bodysite (Example) ActivityDefinition.bodySite (Example) DeviceUseStatement.bodySite (Example) BodySite.code (Example) Specimen.collection.bodySite (Example) Procedure.bodySite (Example) Media.bodySite (Example) ProcedureRequest.bodySite (Example) StructureDefinition ProcedureRequest-Genetics: ProcedureRequest.bodySite ((Example)) Observation.bodySite (Example) StructureDefinition DeviceMetricObservation: Observation.bodySite ((Example)) StructureDefinition Observation-Genetics: Observation.bodySite ((Example)) StructureDefinition VitalSigns: Observation.bodySite ((Example)) StructureDefinition BodyWeight: Observation.bodySite ((Example)) StructureDefinition RespRate: Observation.bodySite ((Example)) StructureDefinition HeartRate: Observation.bodySite ((Example)) StructureDefinition BodyTemp: Observation.bodySite ((Example)) StructureDefinition BodyHeight: Observation.bodySite ((Example)) StructureDefinition BodyLength: Observation.bodySite ((Example)) StructureDefinition HeadCircum: Observation.bodySite ((Example)) StructureDefinition OxygenSat: Observation.bodySite ((Example)) StructureDefinition BMI: Observation.bodySite ((Example)) StructureDefinition BP: Observation.bodySite ((Example)) StructureDefinition VitalsPanel: Observation.bodySite ((Example)) StructureDefinition Cholesterol: Observation.bodySite ((Example)) StructureDefinition Triglyceride: Observation.bodySite ((Example)) StructureDefinition HDLCholesterol: Observation.bodySite ((Example)) StructureDefinition LDLCholesterol: Observation.bodySite ((Example)) Condition.bodySite (Example) Extension http://hl7.org/fhir/StructureDefinition/openEHR-location: location ((Extensible))

Laterality | Laterality: SNOMED-CT concepts for 'left', 'right', and 'bilateral' | 3 enumerated concepts | ImagingStudy.series.laterality (Example)

Bodysite Location Qualifier | SNOMED-CT concepts modifying the anatomic location | 12 enumerated concepts | BodySite.qualifier (Example)

Facility Type Code Value Set | This is the code representing the type of organizational setting where the clinical encounter, service, interaction, or treatment occurred. The value set used for Healthcare Facility Type has been defined by HITSP to be the value set reproduced from HITSP C80 Table 2-147. | 79 enumerated concepts | DocumentReference.context.facilityType (Example)

Practice Setting Code Value Set | This is the code representing the clinical specialty of the clinician or provider who interacted with, treated, or provided a service to/for the patient. The value set used for clinical specialty has been limited by HITSP to the value set reproduced from HITSP C80 Table 2-149 Clinical Specialty Value Set Definition. | 117 enumerated concepts | Appointment.specialty (Preferred) ReferralRequest.serviceRequested (Example) DocumentReference.context.practiceSetting (Example) PractitionerRole.specialty (Preferred) Slot.specialty (Preferred) HealthcareService.specialty (Preferred) Schedule.specialty (Preferred)

Care Plan Activity | Example Codes for types of activities that can appear in a care plan. | is-a Procedure | CarePlan.activity.detail.code (Example)

Care Plan Activity Outcome | Example codes indicating the outcome of a care plan activity. Note that these are in no way complete and may not even be appropriate for some uses. | is-a Healthcare knowledge finding | CarePlan.activity.outcomeCodeableConcept (Example)

Care Plan Category | Example codes indicating the category a care plan falls within. Note that these are in no way complete and may not even be appropriate for some uses. | is-a Care plan | CarePlan.category (Example)

SNOMED CT Clinical Findings | This value set includes all the "Clinical finding" [SNOMED CT](http://snomed.info/sct) codes - concepts where concept is-a 404684003 (Clinical finding (finding)). | is-a Clinical finding | ReferralRequest.reasonCode (Example) Goal.description (Example) Goal.outcomeCode (Example) CareTeam.reasonCode (Example) FamilyMemberHistory.reasonCode (Example) StructureDefinition FamilyMemberHistory-Genetic: FamilyMemberHistory.reasonCode ((Example)) Communication.reasonCode (Example) AllergyIntolerance.reaction.manifestation (Example) DiagnosticReport.codedDiagnosis (Example) StructureDefinition LipidProfile: DiagnosticReport.codedDiagnosis ((Example)) StructureDefinition DiagnosticReport-Genetics: DiagnosticReport.codedDiagnosis ((Example)) StructureDefinition HLAResult: DiagnosticReport.codedDiagnosis ((Example)) PlanDefinition.goal.description (Example)

Clinical Impression Prognosis | Example value set clinical impression prognosis | is-a Prognosis/outlook finding | ClinicalImpression.prognosisCodeableConcept (Example)

Condition Cause Codes | Example value set for Cause of Condition codes | any SCT concept | Extension http://hl7.org/fhir/StructureDefinition/event-reasonCode: reasonCode ((Example)) Extension http://hl7.org/fhir/StructureDefinition/condition-dueTo: dueTo ((Example))

Condition/Problem/Diagnosis Codes | Example value set for Condition/Problem/Diagnosis codes | is-a Clinical finding 1 enumerated concepts | FamilyMemberHistory.condition.code (Example) StructureDefinition FamilyMemberHistory-Genetic: FamilyMemberHistory.condition.code ((Example)) DeviceRequest.reasonCode (Example) Procedure.complication (Example) MedicationRequest.reasonCode (Example) MedicationStatement.reasonCode (Example) Condition.code (Example) ClinicalImpression.finding.item[x] (Example) PlanDefinition.goal.addresses (Example)

Condition Outcome Codes | Example value set for Condition Outcomes | is-a Clinical finding | FamilyMemberHistory.condition.outcome (Example) StructureDefinition FamilyMemberHistory-Genetic: FamilyMemberHistory.condition.outcome ((Example)) Extension http://hl7.org/fhir/StructureDefinition/condition-outcome: outcome ((Example))

Condition Predecessor Codes | Example value set for Condition Predecessor codes | any SCT concept | Extension http://hl7.org/fhir/StructureDefinition/condition-occurredFollowing: occurredFollowing ((Example))

Condition/Diagnosis Severity | Preferred value set for Condition/Diagnosis severity grading | 3 enumerated concepts | Condition.severity (Preferred) Extension http://hl7.org/fhir/StructureDefinition/familymemberhistory-severity: severity ((Example))

Condition Stage | Example value set for stages of cancer and other conditions | is-a Tumour stage finding | Condition.stage.summary (Example)

Fluid Consistency Type Codes | FluidConsistencyType : Codes used to represent the consistency of fluids and liquids provided to the patient. This value set includes all the [SNOMED CT](http://snomed.info/sct)(US Extension) where concept is a 435681000124103 (Dietary liquid consistency diet (regime/therapy)). It is provided as a suggestive example. | 4 enumerated concepts | NutritionOrder.oralDiet.fluidConsistencyType (Example)

DataElement SDC Object Class | The allowed codes for identifying the ISO 11179 ObjectClass for a particular data element if intended for registration/use within the U.S. Structured Data Capture (SDC) project. | any SCT concept other code systems | Extension http://hl7.org/fhir/StructureDefinition/11179-objectClass: objectClass ((Example))

DataElement SDC Object Class | The allowed codes for identifying the ISO 11179 ObjectClass Property for a particular data element if intended for registration/use within the U.S. Structured Data Capture (SDC) project. | any SCT concept other code systems | Extension http://hl7.org/fhir/StructureDefinition/11179-objectClassProperty: objectClassProperty ((Example))

Designation Use | Details of how a designation would be used | is-a Description type | ValueSet.compose.include.concept.designation.use (Extensible) StructureDefinition ShareableValueSet: ValueSet.compose.include.concept.designation.use ((Extensible)) CodeSystem.concept.designation.use (Extensible) StructureDefinition ShareableCodeSystem: CodeSystem.concept.designation.use ((Extensible))

Procedure Device Action Codes | Example codes indicating the change that happened to the device during the procedure. Note that these are in no way complete and may not even be appropriate for some uses. | is-a Action | This value set is the designated 'entire code system' value set for Procedure Device Action Codes Procedure.focalDevice.action (Preferred)

FHIR Device Types | Codes used to identify medical devices. Include codes from [SNOMED CT](http://snomed.info/sct) where concept is-a 49062001 (Device) and is provided as a suggestive example. | is-a Device | DeviceComponent.type (Preferred) DeviceRequest.code[x] (Example)

Procedure.usedCode (Example) Device.type (Example)

Diet Codes | Codes that can be used to indicate the type of food being ordered for a patient. This value set is provided as a suggestive example. It nclude codes from [SNOMED CT](http://snomed.info/sct) where concept is-a 182922004 (Dietary regime (regime/therapy)) | is-a Dietary regime | NutritionOrder.oralDiet.type (Example)

Media SubType | Detailed information about the type of the image - its kind, purpose, or the kind of equipment used to generate it. | is-a Imaging other code systems | This value set is the designated 'entire code system' value set for Media SubType Media.subtype (Example)

Encounter Reason Codes | This examples value set defines the set of codes that can be used to indicate reasons for an encounter. | is-a Clinical finding is-a Procedure | Appointment.reason (Preferred) Encounter.reason (Preferred)

Enteral Formula Type Codes | EnteralFormulaType : Codes for type of enteral formula to be administered to patient. This value set is is composed of SNOMED CT (US Extension) Concepts from SCTID 470581016 (Enteral+supplement feeds hierarchy (product)) and is provided as a suggestive example. | 36 enumerated concepts | NutritionOrder.enteralFormula.baseFormulaType (Example)

Flag Code | Example list of detail codes for flagged issues. (Not complete or necessarily appropriate.) | is-a Clinical finding | Flag.code (Example)

Focal Subject Codes | Example VS composed from SNOMED CT and HL7 v3 codes for observation targets: donor, fetus, spouse. As use cases are discovered more values may be added. | 1 enumerated concepts other code systems | Extension http://hl7.org/fhir/StructureDefinition/observation-focal-subject: focal-subject ((Example))

Food Type Codes | This value set represents codes for types of foods and is provided as a suggestive example. It include codes from [SNOMED CT](http://snomed.info/sct) where concept is-a 255620007 (Foods (substance)). | is-a Foods | NutritionOrder.excludeFoodModifier (Example)

GoalStartEvent | Identifies types of events that might trigger the start of a goal. | 4 enumerated concepts | Goal.start[x] (Example) PlanDefinition.goal.start (Example)

Immunization Reason Codes | The value set to instantiate this attribute should be drawn from a terminologically robust code system that consists of or contains concepts to support describing the reason why a dose of vaccine was administered. This value set is provided as a suggestive example. | 2 enumerated concepts | Immunization.explanation.reason (Example)

Immunization Recommendation Target Disease Codes | The value set to instantiate this attribute should be drawn from a terminologically robust code system that consists of or contains concepts to support describing the disease targeted by a vaccination recommendation. This value set is provided as a suggestive example and includes the SNOMED CT concepts from the 64572001 (Disease) hierarchy. | 9 enumerated concepts | ImmunizationRecommendation.recommendation.targetDisease (Example)

Investigation Type | Example value set for investigation type | 2 enumerated concepts | ClinicalImpression.investigation.code (Example)

Manifestation and Symptom Codes | Example value set for Manifestation and Symptom codes. | is-a Clinical finding | Condition.evidence.code (Example)

Media Collection View/Projection | Codes defined in SNOMED CT that can be used to record Media Recording views. | is-a Projection | Media.view (Example)

SNOMED CT Medication As Needed Reason Codes | This value set includes all clinical findings from SNOMED CT - provided as an exemplar value set. | is-a Clinical finding | ProcedureRequest.asNeeded[x] (Example) StructureDefinition ProcedureRequest-Genetics: ProcedureRequest.asNeeded[x] ((Example))

SNOMED CT Medication Codes | This value set includes all drug or medicament substance codes and all pharmaceutical/biologic products from SNOMED CT - provided as an exemplar value set. | is-a Drug or medicament is-a Pharmaceutical / biologic product is-a Immunologic substance | Medication.code (Example) ActivityDefinition.product[x] (Example) CarePlan.activity.detail.product[x] (Example) MedicationRequest.medication[x] (Example) MedicationAdministration.medication[x] (Example) MedicationStatement.medication[x] (Example) MedicationDispense.medication[x] (Example)

SNOMED CT Form Codes | This value set includes all dose form codes from SNOMED CT - provided as an exemplar. | is-a Drug dose form | Medication.form (Example)

Texture Modified Food Type Codes | TextureModifiedFoodType: Codes for types of foods that are texture modified. This value set is composed SNOMED CT Concepts from SCTID 255620007 Foods (substance) and is provided as a suggestive example. | 14 enumerated concepts | NutritionOrder.oralDiet.texture.foodType (Example)

Immunization Reasons for Not Immunizing Codes | The value set to instantiate this attribute should be drawn from a terminologically robust code system that consists of or contains concepts to support describing the reason why a dose of vaccine was not administered. This value set is provided as a suggestive example. | is-a Immunization consent not given other code systems | Immunization.explanation.reasonNotGiven (Example)

Nutrient Modifier Codes | NutrientModifier : Codes for types of nutrient that is being modified such as carbohydrate or sodium. This value set includes codes from [SNOMED CT](http://snomed.info/sct) where concept is-a 226355009 (Nutrients(substance)), and the concepts for Sodium, Potassium and Fluid. It is provided as a suggestive example. | 3 enumerated concepts is-a Nutrients | NutritionOrder.oralDiet.nutrient.modifier (Example)

Observation Methods | Observation Method codes from [SNOMED CT](http://snomed.info/sct) where concept is-a 272394005 (Technique (qualifier value)) or is-a 129264002 (Action (qualifier value)) or is-a 386053000 (Evaluation procedure(procedure)) | is-a Technique is-a Action is-a Patient evaluation procedure | Observation.method (Example) StructureDefinition DeviceMetricObservation: Observation.method ((Example)) StructureDefinition Observation-Genetics: Observation.method ((Example)) StructureDefinition VitalSigns: Observation.method ((Example)) StructureDefinition BodyWeight: Observation.method ((Example)) StructureDefinition RespRate: Observation.method ((Example)) StructureDefinition HeartRate: Observation.method ((Example)) StructureDefinition BodyTemp: Observation.method ((Example)) StructureDefinition BodyHeight: Observation.method ((Example)) StructureDefinition BodyLength: Observation.method ((Example)) StructureDefinition HeadCircum: Observation.method ((Example)) StructureDefinition OxygenSat: Observation.method ((Example)) StructureDefinition BMI: Observation.method ((Example)) StructureDefinition BP: Observation.method ((Example)) StructureDefinition VitalsPanel: Observation.method ((Example)) StructureDefinition Cholesterol: Observation.method ((Example)) StructureDefinition Triglyceride: Observation.method ((Example)) StructureDefinition HDLCholesterol: Observation.method ((Example)) StructureDefinition LDLCholesterol: Observation.method ((Example))

Participant Roles | Roles of Participants that may be included in a CarePlan.Participants, or in an EpisodeOfCare.CareTeam. Defined as: Is a Person, Healthcare professional (occupation) or Healthcare related organization (qualifier value). | is-a Person is-a Healthcare professional is-a Healthcare related organisation | CareTeam.participant.role (Example) DeviceRequest.performerType (Example) ProcedureRequest.performerType (Example) StructureDefinition ProcedureRequest-Genetics: ProcedureRequest.performerType ((Example))

Procedure Performer Role Codes | This examples value set defines the set of codes that can be used to indicate a role of procedure performer. | is-a Healthcare professional | ChargeItem.participant.role (Example) Procedure.performer.role (Example) DiagnosticReport.performer.role (Example) StructureDefinition LipidProfile: DiagnosticReport.performer.role ((Example)) StructureDefinition DiagnosticReport-Genetics: DiagnosticReport.performer.role ((Example)) StructureDefinition HLAResult: DiagnosticReport.performer.role ((Example)) Extension http://hl7.org/fhir/StructureDefinition/event-performerRole: performerRole ((Example))

Procedure Category Codes (SNOMED CT) | Procedure Category code: A selection of relevant SNOMED CT codes. | 6 enumerated concepts | Procedure.category (Example) ProcedureRequest.category (Example) StructureDefinition ProcedureRequest-Genetics: ProcedureRequest.category ((Example))

Procedure Codes (SNOMED CT) | Procedure Code: All SNOMED CT procedure codes. | is-a Procedure | ImagingStudy.procedureCode (Example) ActivityDefinition.code (Example) Procedure.code (Example) ProcedureRequest.code (Example) StructureDefinition ProcedureRequest-Genetics: ProcedureRequest.code ((Example))

Procedure Follow up Codes (SNOMED CT) | Procedure follow up codes: a selection of SNOMED CT codes relevant to procedure follow up. | 10 enumerated concepts | Procedure.followUp (Example)

Procedure Not Performed Reason (SNOMED-CT) | Situation codes describing the reason that a procedure, which might otherwise be expected, was not performed, or a procedure that was started and was not completed. Consists of SNOMED CT codes, children of procedure contraindicated (183932001), procedure discontinued (416406003), procedure not done (416237000), procedure not indicated (428119001), procedure not offered (416064006), procedure not wanted (416432009), procedure refused (183944003), and procedure stopped (394908001). | is-a Procedure contraindicated is-a Procedure discontinued is-a Procedure not done is-a Procedure not indicated is-a Procedure not offered is-a Procedure not wanted is-a Procedure refused is-a Procedure stopped | Procedure.notDoneReason (Example)

Procedure Outcome Codes (SNOMED CT) | Procedure Outcome code: A selection of relevant SNOMED CT codes. | 3 enumerated concepts | Procedure.outcome (Example)

Procedure Reason Codes | This examples value set defines the set of codes that can be used to indicate a reasons for a procedure. | is-a Clinical finding is-a Procedure | ImagingStudy.reason (Example) Procedure.reasonCode (Example) Media.reasonCode (Example) ProcedureRequest.reasonCode (Example) StructureDefinition ProcedureRequest-Genetics: ProcedureRequest.reasonCode ((Example))

Structure Definition Codes | Codes for the meaning of the defined structure. | any SCT concept other code systems | StructureDefinition.keyword (Example)

Questionnaire Answer Codes | Example list of codes for answers to questions. (Not complete or necessarily appropriate.) | any SCT concept | Questionnaire.item.enableWhen.answer[x] (Example) Questionnaire.item.initial[x] (Example) QuestionnaireResponse.item.answer.value[x] (Example)

Questionnaire Category Codes | Example list of potential categories for questionnaires. | 5 enumerated concepts | This value set is not currently used

SNOMED CT Reason Medication Not Given Codes | This value set includes all medication refused, medication not administered, and non administration of necessary drug or medicine codes from SNOMED CT - provided as an exemplar value set. | is-a Medication refused is-a Medication not administered is-a Drug not available for administration | This value set is the designated 'entire code system' value set for SNOMED CT Reason Medication Not Given Codes MedicationAdministration.reasonNotGiven (Example)

SNOMED CT Drugs not taken/completed Codes | This value set includes some not taken reason codes from SNOMED CT - provided as an exemplar | is-a Drugs not taken/completed | MedicationStatement.reasonNotTaken (Example)

Observation Reference Range Applies To Codes | This value set defines a set of codes that can be used to indicate the a particular target population the reference range applies to. | 3 enumerated concepts other code systems | Observation.referenceRange.appliesTo (Example) StructureDefinition DeviceMetricObservation: Observation.referenceRange.appliesTo ((Example)) StructureDefinition Observation-Genetics: Observation.referenceRange.appliesTo ((Example)) StructureDefinition VitalSigns: Observation.referenceRange.appliesTo ((Example)) StructureDefinition BodyWeight: Observation.referenceRange.appliesTo ((Example)) StructureDefinition RespRate: Observation.referenceRange.appliesTo ((Example)) StructureDefinition HeartRate: Observation.referenceRange.appliesTo ((Example)) StructureDefinition BodyTemp: Observation.referenceRange.appliesTo ((Example)) StructureDefinition BodyHeight: Observation.referenceRange.appliesTo ((Example)) StructureDefinition BodyLength: Observation.referenceRange.appliesTo ((Example)) StructureDefinition HeadCircum: Observation.referenceRange.appliesTo ((Example)) StructureDefinition OxygenSat: Observation.referenceRange.appliesTo ((Example)) StructureDefinition BMI: Observation.referenceRange.appliesTo ((Example)) StructureDefinition BP: Observation.referenceRange.appliesTo ((Example)) StructureDefinition VitalsPanel: Observation.referenceRange.appliesTo ((Example)) StructureDefinition Cholesterol: Observation.referenceRange.appliesTo ((Example)) StructureDefinition Triglyceride: Observation.referenceRange.appliesTo ((Example)) StructureDefinition HDLCholesterol: Observation.referenceRange.appliesTo ((Example)) StructureDefinition LDLCholesterol: Observation.referenceRange.appliesTo ((Example))

SNOMED CT Patient Referral | This value set includes all SNOMED CT Patient Referral. | is-a Patient referral | ReferralRequest.type (Example)

SNOMED CT Route Codes | This value set includes all Route codes from SNOMED CT - provided as an exemplar. | is-a Route of administration values | AllergyIntolerance.reaction.exposureRoute (Example) MedicationAdministration.dosage.route (Example)

SNOMED CT Codes for species | Codes identifying atomic results of observations when value is type codeableConcept. This value set includes all the children of SNOMED CT Concepts from SCTIDs 404684003 Clinical finding (finding), 410607006 Organism (organism),362981000 Qualifier value (qualifier value), 105590001 Substance (substance), and 123037004 Body structure (body structure). It is provided as a suggestive example | any SCT concept | This value set is not currently used

FHIR Specimen Collection Method | This example value set defines a set of codes that can be used to indicate the method of collection of a specimen. It includes values from HL7 v2 table 0048. | 13 enumerated concepts other code systems | Specimen.collection.method (Example)

SpecimenContainer | Containers which may hold specimens or specimen containers. Include codes SNOMED CT(http://snomed.info/sct) where concept is-a 434711009 (Specimen container (physical object)) | is-a Specimen container | Specimen.container.type (Example)

Substance Code | This value set contains concept codes for specific substances. It includes codes from [SNOMED](http://snomed.info/sct) where concept is-a 105590001 (Substance (substance)) adn where concept is-a 373873005 (Pharmaceutical / biologic product (product)) | is-a Substance is-a Pharmaceutical / biologic product | Substance.ingredient.substance[x] (Example) AllergyIntolerance.reaction.substance (Example) Extension http://hl7.org/fhir/StructureDefinition/allergyintolerance-substanceExposureRisk: substanceExposureRisk ((Example))

Supplement Type Codes | SupplementType : Codes for nutritional supplements to be provided to the patient. This value set is is composed of SNOMED CT (US Extension) Concepts from SCTID 470581016 (Enteral+supplement feeds hierarchy (product)) and is provided as a suggestive example. | 45 enumerated concepts | NutritionOrder.supplement.type (Example)

SNOMED CT Supply Item | This value set includes [SNOMED CT](http://snomed.info/sct) where concept is-a 105590001 (Substance (substance)) or concept is-a 260787004 (Physical object) and provided as an example value set. | is-a Substance is-a Physical object | SupplyRequest.orderedItem.item[x] (Example) SupplyDelivery.suppliedItem.item[x] (Example)

Texture Modifier Codes | TextureModifier: Codes for food consistency types or texture modifications to apply to foods. This value set is composed of SNOMED CT (US Extension and Core) Concepts from SCTID 229961002 Food consistency types (substance) hierarchy and is provided as a suggestive example. | 14 enumerated concepts | NutritionOrder.oralDiet.texture.modifier (Example)

Context of Use ValueSet | This value set defines a base set of codes that can be used to indicate that the content in a resource was developed with a focus and intent of supporting use within particular contexts. | is-a Medical specialties is-a Kingdom Animalia other code systems | UsageContext.value[x] (Example) Extension http://hl7.org/fhir/StructureDefinition/elementdefinition-bestpractice: bestpractice ((Extensible))

Vaccination Protocol Dose Target Codes | The value set to instantiate this attribute should be drawn from a terminologically robust code system that consists of or contains concepts to support describing the disease targeted by a vaccine. This value set is provided as a suggestive example and includes the SNOMED CT concepts from the 64572001 (Disease) hierarchy. | 9 enumerated concepts | Immunization.vaccinationProtocol.targetDisease (Example)

4.2.1.1.2 Concept References

The value sets that reference SNOMED CT explicitly reference the following SNOMED CT concepts. The table lists the concepts, and then the value sets and places they are used from, and includes the binding strengths. The table does not include codes published in the expansions.

Code | Display | ValueSets
1006005 | Percheron horse (organism) | AnimalBreeds
10206005 | Hospital outpatient dental clinic | Facility Type Code Value Set
102263004 | Eggs | Texture Modified Food Type Codes
10261003 | Belgium landrace pig (organism) | AnimalBreeds
103693007 | Diagnostic procedure | Procedure Category Codes (SNOMED CT)
10531005 | Free-standing ambulatory surgery facility | Facility Type Code Value Set
105590001 | Substance | Substance Code
106181007 | Immunologic substance | SNOMED CT Medication Codes
10643004 | Arucana chicken (organism) | AnimalBreeds
11161001 | Dekalb hybrid pig line 77 (organism) | AnimalBreeds
1118004 | Viking horse (organism) | AnimalBreeds
112485003 | Gujarati cattle breed (organism) | AnimalBreeds
112486002 | No-tail sheep (organism) | AnimalBreeds
112487006 | Romnelet sheep (organism) | AnimalBreeds
112488001 | Hackney horse (organism) | AnimalBreeds
112489009 | Berkshire pig (organism) | AnimalBreeds
112490000 | Dekalb hybrid pig line 63 (organism) | AnimalBreeds
112495005 | Rumpless chicken (organism) | AnimalBreeds
112496006 | Pilgrim goose (organism) | AnimalBreeds
11424001 | Ambulance-based care | Facility Type Code Value Set
11830008 | Delaware chicken (organism) | AnimalBreeds
119295008 | Specimen obtained by aspiration | FHIR Specimen Collection Method
11967001 | Kerry Hill sheep (organism) | AnimalBreeds
12360007 | Missouri fox trotting horse (organism) | AnimalBreeds
12407009 | Swedish landrace pig (organism) | AnimalBreeds
12419001 | Redcap chicken (organism) | AnimalBreeds
1247002 | Clydesdale horse (organism) | AnimalBreeds
125074003 | Hereford cattle superbreed (organism) | AnimalBreeds
125084002 | Equus caballus gmelini (organism) | AnimalBreeds
125086000 | Equus caballus gmelini X Equus caballus caballus (organism) | AnimalBreeds
125092006 | Bos frontalis (organism) | AnimalBreeds
125097000 | goat | AnimalSpecies
125099002 | sheep | AnimalSpecies
125101009 | Merino sheep superbreed (organism) | AnimalBreeds
125102002 | Anas platyrhynchos (organism) | AnimalBreeds
125104001 | Anser anser (organism) | AnimalBreeds
125676002 | Person | Participant Roles
12874007 | Crevecoeur chicken (organism) | AnimalBreeds
129264002 | Action | Procedure Device Action Codes
131426006 | Africander cattle breed (organism) | AnimalBreeds
131427002 | Ankole cattle breed (organism) | AnimalBreeds
131428007 | Ankole-Watusi cattle breed (organism) | AnimalBreeds
131429004 | Baladi cattle breed (organism) | AnimalBreeds
131430009 | Belmont Red cattle breed (organism) | AnimalBreeds
131431008 | Bonsmara cattle breed (organism) | AnimalBreeds
131432001 | Damietta cattle breed (organism) | AnimalBreeds
131433006 | Horro cattle breed (organism) | AnimalBreeds
131434000 | Kuri cattle breed (organism) | AnimalBreeds
131435004 | Nguni cattle breed (organism) | AnimalBreeds
131436003 | Philippine Native cattle breed (organism) | AnimalBreeds
131437007 | Romagnola cattle breed (organism) | AnimalBreeds
131438002 | Sanhe cattle breed (organism) | AnimalBreeds
131439005 | Tswana cattle breed (organism) | AnimalBreeds
131440007 | Tuli cattle breed (organism) | AnimalBreeds
131441006 | Aliab Dinka cattle breed (organism) | AnimalBreeds
131442004 | Alur cattle breed (organism) | AnimalBreeds
131443009 | Ankina cattle breed (organism) | AnimalBreeds
131444003 | Apulian Podolian cattle breed (organism) | AnimalBreeds
131445002 | Arado cattle breed (organism) | AnimalBreeds
131446001 | Aweil Dinka cattle breed (organism) | AnimalBreeds
131447005 | Bahima cattle breed (organism) | AnimalBreeds
131448000 | Bapedi cattle breed (organism) | AnimalBreeds
131449008 | Baria (Vietnam/Madagascar) cattle breed (organism) | AnimalBreeds
131450008 | Barotse cattle breed (organism) | AnimalBreeds
131451007 | Barra do Cuanzo cattle breed (organism) | AnimalBreeds
131452000 | Bashi cattle breed (organism) | AnimalBreeds
131453005 | Basuto cattle breed (organism) | AnimalBreeds
131454004 | Batangas cattle breed (organism) | AnimalBreeds
131455003 | Bavenda cattle breed (organism) | AnimalBreeds
131456002 | Beja cattle breed (organism) | AnimalBreeds
131457006 | Calabrian cattle breed (organism) | AnimalBreeds

131458001 | Blonde-du Cap Bon cattle breed (organism) | AnimalBreeds
131459009 | Chan-Doc cattle breed (organism) | AnimalBreeds
131460004 | Chernigov cattle breed (organism) | AnimalBreeds
131461000 | Chino Santandereano cattle breed (organism) | AnimalBreeds
131462007 | Cinisara cattle breed (organism) | AnimalBreeds
131463002 | Cuprem Hybrid cattle breed (organism) | AnimalBreeds
131464008 | Dabieshan cattle breed (organism) | AnimalBreeds
131465009 | Damara cattle breed (organism) | AnimalBreeds
131466005 | Danakil cattle breed (organism) | AnimalBreeds
131467001 | Dnieper cattle breed (organism) | AnimalBreeds
131468006 | Doayo cattle breed (organism) | AnimalBreeds
131469003 | Eastern Nuer cattle breed (organism) | AnimalBreeds
131470002 | Egyptian cattle breed (organism) | AnimalBreeds
131471003 | Fogera cattle breed (organism) | AnimalBreeds
131472005 | Garfagnina cattle breed (organism) | AnimalBreeds
131473000 | Grati cattle breed (organism) | AnimalBreeds
131474006 | Gaunling cattle breed (organism) | AnimalBreeds
131475007 | Halhin Gol cattle breed (organism) | AnimalBreeds
131476008 | Holmonger cattle breed (organism) | AnimalBreeds
131477004 | Ilocos cattle breed (organism) | AnimalBreeds
131478009 | Iloilo cattle breed (organism) | AnimalBreeds
131479001 | Inkuku cattle breed (organism) | AnimalBreeds
131480003 | Iskar cattle breed (organism) | AnimalBreeds
131481004 | Istrian cattle breed (organism) | AnimalBreeds
131482006 | Javanese Ongole cattle breed (organism) | AnimalBreeds
131483001 | Javanese Zebu cattle breed (organism) | AnimalBreeds
131484007 | Jinnan cattle breed (organism) | AnimalBreeds
131485008 | Kalmyk cattle breed (organism) | AnimalBreeds
131486009 | Kaokoveld cattle breed (organism) | AnimalBreeds
131487000 | Kazakh Whitehead cattle breed (organism) | AnimalBreeds
131488005 | Kedah-Kelantan cattle breed (organism) | AnimalBreeds
131489002 | Kigezi cattle breed (organism) | AnimalBreeds
131490006 | Kisantu cattle breed (organism) | AnimalBreeds
131491005 | Kolubara cattle breed (organism) | AnimalBreeds
131492003 | Kurgan cattle breed (organism) | AnimalBreeds
131493008 | Kyoga cattle breed (organism) | AnimalBreeds
131494002 | Lucanian cattle breed (organism) | AnimalBreeds
131495001 | Maremmana cattle breed (organism) | AnimalBreeds
131496000 | Marianas cattle breed (organism) | AnimalBreeds
131497009 | Maryuti cattle breed (organism) | AnimalBreeds
131498004 | Mauritius Créole cattle breed (organism) | AnimalBreeds
131499007 | Menufi cattle breed (organism) | AnimalBreeds
131500003 | Mezzalina cattle breed (organism) | AnimalBreeds
131501004 | Modicana cattle breed (organism) | AnimalBreeds
131502006 | Moi cattle breed (organism) | AnimalBreeds
131503001 | Nama cattle breed (organism) | AnimalBreeds
131504007 | Nanyang cattle breed (organism) | AnimalBreeds
131505008 | N'Dama Sanga cattle breed (organism) | AnimalBreeds
131506009 | Nganda cattle breed (organism) | AnimalBreeds
131507000 | Nilotic Sanga cattle breed (organism) | AnimalBreeds
131508005 | Nkone cattle breed (organism) | AnimalBreeds
131509002 | North Malawi Angoni cattle breed (organism) | AnimalBreeds
131510007 | Nuer cattle breed (organism) | AnimalBreeds
131511006 | Nuras cattle breed (organism) | AnimalBreeds
131512004 | Nyoro cattle breed (organism) | AnimalBreeds
131513009 | Ovambo cattle breed (organism) | AnimalBreeds
131514003 | Pantelleria cattle breed (organism) | AnimalBreeds
131515002 | Pinzhou cattle breed (organism) | AnimalBreeds
131516001 | Porto Amboim cattle breed (organism) | AnimalBreeds
131517005 | Posavina cattle breed (organism) | AnimalBreeds
131518000 | Romanian Steppe cattle breed (organism) | AnimalBreeds
131519008 | Saidi cattle breed (organism) | AnimalBreeds
131520002 | Sardo-Modicana cattle breed (organism) | AnimalBreeds
131521003 | Sengologa cattle breed (organism) | AnimalBreeds
131522005 | Serere cattle breed (organism) | AnimalBreeds
131523000 | Seshaga cattle breed (organism) | AnimalBreeds
131524006 | Siberian Black Pied cattle breed (organism) | AnimalBreeds
131525007 | Socotra cattle breed (organism) | AnimalBreeds
131526008 | Southern Tswana cattle breed (organism) | AnimalBreeds
131527004 | Spreca cattle breed (organism) | AnimalBreeds
131528009 | Sunkuma cattle breed (organism) | AnimalBreeds
131529001 | Taiwan Zebu cattle breed (organism) | AnimalBreeds

131530006 | Thai cattle breed (organism) | AnimalBreeds
131531005 | Thailand Fighting Zebu cattle breed (organism) | AnimalBreeds
131532003 | Thanh-Hoa cattle breed (organism) | AnimalBreeds
131533008 | Tibetan cattle breed (organism) | AnimalBreeds
131534002 | Tonga cattle breed (organism) | AnimalBreeds
131535001 | Toro cattle breed (organism) | AnimalBreeds
131536000 | Tuni cattle breed (organism) | AnimalBreeds
131537009 | Turkish Gray Steppe cattle breed (organism) | AnimalBreeds
131538004 | Tuy-Hoa cattle breed (organism) | AnimalBreeds
131539007 | Ujumqin cattle breed (organism) | AnimalBreeds
131540009 | Abigar cattle breed (organism) | AnimalBreeds
131541008 | Africangus cattle breed (organism) | AnimalBreeds
131542001 | Agerolese cattle breed (organism) | AnimalBreeds
131543006 | Albese cattle breed (organism) | AnimalBreeds
131544000 | Ukrainian Gray cattle breed (organism) | AnimalBreeds
131545004 | Vietnamese Yellow cattle breed (organism) | AnimalBreeds
131546003 | Watusi (United States of America) cattle breed (organism) | AnimalBreeds
131547007 | Wenshan cattle breed (organism) | AnimalBreeds
131548002 | Yakut cattle breed (organism) | AnimalBreeds
131549005 | Yunnan Zebu cattle breed (organism) | AnimalBreeds
131550005 | Zambia Angoni cattle breed (organism) | AnimalBreeds
131551009 | Drakensberger cattle breed (organism) | AnimalBreeds
131552002 | Modicana lowland cattle breed (organism) | AnimalBreeds
131553007 | Taiwan Yellow cattle breed (organism) | AnimalBreeds
131554001 | Menggu cattle breed (organism) | AnimalBreeds
131555000 | Albères cattle breed (organism) | AnimalBreeds
131556004 | Alentejana cattle breed (organism) | AnimalBreeds
131557008 | American White Park cattle breed (organism) | AnimalBreeds
131558003 | Amerifaxcattle breed (organism) | AnimalBreeds
131559006 | Anatolian Black cattle breed (organism) | AnimalBreeds
131560001 | Andalusian Black cattle breed (organism) | AnimalBreeds
13156006 | Spanish chicken (organism) | AnimalBreeds
131561002 | Andalusian Gray cattle breed (organism) | AnimalBreeds
131562009 | Angeln cattle breed (organism) | AnimalBreeds
131563004 | Asturian Mountain cattle breed (organism) | AnimalBreeds
131564005 | Asturian Valley cattle breed (organism) | AnimalBreeds
131565006 | Aubrac cattle breed (organism) | AnimalBreeds
131566007 | Aulie-Ata cattle breed (organism) | AnimalBreeds
131567003 | Australian Lowline cattle breed (organism) | AnimalBreeds
131568008 | Barzona cattle breed (organism) | AnimalBreeds
131569000 | Bazadais cattle breed (organism) | AnimalBreeds
131570004 | Beefmaker cattle breed (organism) | AnimalBreeds
131571000 | Belarus Red cattle breed (organism) | AnimalBreeds
131572007 | Belgian Blue cattle breed (organism) | AnimalBreeds
131573002 | Belgian Red cattle breed (organism) | AnimalBreeds
131574008 | Belmont Adaptaur cattle breed (organism) | AnimalBreeds
131575009 | Berrendas cattle breed (organism) | AnimalBreeds
131576005 | Blacksided Trondheim and Norland cattle breed (organism) | AnimalBreeds
131577001 | Blanco Orejinegro cattle breed (organism) | AnimalBreeds
131578006 | Braunvieh cattle breed (organism) | AnimalBreeds
131579003 | British White cattle breed (organism) | AnimalBreeds
131580000 | Cachena cattle breed (organism) | AnimalBreeds
131581001 | Canary Island cattle breed (organism) | AnimalBreeds
131582008 | Carinthian Blond cattle breed (organism) | AnimalBreeds
131583003 | Caucasian cattle breed (organism) | AnimalBreeds
131584009 | Charolais cattle breed (organism) | AnimalBreeds
131585005 | Chinese Black-and-White cattle breed (organism) | AnimalBreeds
131586006 | Corriente cattle breed (organism) | AnimalBreeds
131587002 | Costeño con Cuernos cattle breed (organism) | AnimalBreeds
131588007 | Damascus cattle breed (organism) | AnimalBreeds
131589004 | Danish Red cattle breed (organism) | AnimalBreeds
131590008 | Devon cattle breed (organism) | AnimalBreeds
131591007 | Dølafe cattle breed (organism) | AnimalBreeds
131592000 | Dutch Belted cattle breed (organism) | AnimalBreeds
131593005 | Dutch Friesian cattle breed (organism) | AnimalBreeds
131594004 | English Longhorn cattle breed (organism) | AnimalBreeds
131595003 | Estonian Red cattle breed (organism) | AnimalBreeds
131596002 | Evolène cattle breed (organism) | AnimalBreeds
131597006 | Fighting Bull cattle breed (organism) | AnimalBreeds
131598001 | Fjall cattle breed (organism) | AnimalBreeds
131599009 | Florida Cracker/Pineywoods cattle breed (organism) | AnimalBreeds
131600007 | Galician Blond cattle breed (organism) | AnimalBreeds

131601006 | Gascon cattle breed (organism) | AnimalBreeds
131602004 | German Red Pied cattle breed (organism) | AnimalBreeds
131603009 | Glan cattle breed (organism) | AnimalBreeds
131604003 | Gloucester cattle breed (organism) | AnimalBreeds
131605002 | Groningen Whiteheaded cattle breed (organism) | AnimalBreeds
131606001 | Hartón cattle breed (organism) | AnimalBreeds
131607005 | Mixed Breed Goat (organism) | AnimalBreeds
131608000 | Australian Goat breed (organism) | AnimalBreeds
131609008 | Arapawa Island goat breed (organism) | AnimalBreeds
131610003 | Maltese goat breed (organism) | AnimalBreeds
131611004 | Provençale goat breed (organism) | AnimalBreeds
131612006 | Negra Serrana goat breed (organism) | AnimalBreeds
131613001 | Orobica goat breed (organism) | AnimalBreeds
131614007 | Roya-Vesubie goat breed (organism) | AnimalBreeds
131615008 | Retinta Extremena goat breed (organism) | AnimalBreeds
131616009 | Appenzell goat breed (organism) | AnimalBreeds
131617000 | American Cashmere goat breed (organism) | AnimalBreeds
131618005 | Altai Mountain goat breed (organism) | AnimalBreeds
131619002 | Pyrenean goat breed (organism) | AnimalBreeds
131620008 | Bagot goat breed (organism) | AnimalBreeds
131621007 | Russian White goat breed (organism) | AnimalBreeds
131622000 | Moxotó goat breed (organism) | AnimalBreeds
131623005 | Myotonic goat breed (organism) | AnimalBreeds
131624004 | Nachi goat breed (organism) | AnimalBreeds
131625003 | Nigerian Dwarf goat breed (organism) | AnimalBreeds
131626002 | Sarda goat breed (organism) | AnimalBreeds
131627006 | Serpentina goat breed (organism) | AnimalBreeds
131628001 | Serrana goat breed (organism) | AnimalBreeds
131629009 | Verata goat breed (organism) | AnimalBreeds
131630004 | Verzasca black goat breed (organism) | AnimalBreeds
131631000 | Norwegian goat breed (organism) | AnimalBreeds
131632007 | Oberhasli goat breed (organism) | AnimalBreeds
131633002 | Peacock Goat breed (organism) | AnimalBreeds
131634008 | Philippine goat breed (organism) | AnimalBreeds
131635009 | Loashan goat breed (organism) | AnimalBreeds
131636005 | San Clemente goat breed (organism) | AnimalBreeds
131637001 | Somali goat breed (organism) | AnimalBreeds
131638006 | Spanish goat breed (organism) | AnimalBreeds
131639003 | Rove goat breed (organism) | AnimalBreeds
131640001 | SRD goat breed (organism) | AnimalBreeds
131641002 | Swedish Landrace goat breed (organism) | AnimalBreeds
131642009 | Thuringian goat breed (organism) | AnimalBreeds
131643004 | Uzbek Black goat breed (organism) | AnimalBreeds
131644005 | Zhongwei goat breed (organism) | AnimalBreeds
131645006 | Barbari goat breed (organism) | AnimalBreeds
131646007 | Poitou goat breed (organism) | AnimalBreeds
131647003 | Repartida goat breed (organism) | AnimalBreeds
131648008 | Booted Goat breed (organism) | AnimalBreeds
131649000 | Corsican goat breed (organism) | AnimalBreeds
131650000 | Chapar goat breed (organism) | AnimalBreeds
131651001 | Canindé goat breed (organism) | AnimalBreeds
131652008 | Canary Island goat breed (organism) | AnimalBreeds
131653003 | Daera Din Panah goat breed (organism) | AnimalBreeds
131654009 | British Alpine goat breed (organism) | AnimalBreeds
131655005 | Bhuj goat breed (organism) | AnimalBreeds
131656006 | Boer goat breed (organism) | AnimalBreeds
131657002 | Benadir goat breed (organism) | AnimalBreeds
131658007 | Créole Antilles goat breed (organism) | AnimalBreeds
131659004 | Beetal goat breed (organism) | AnimalBreeds
131660009 | Golden Guernsey goat breed (organism) | AnimalBreeds
131661008 | Danish Landrace goat breed (organism) | AnimalBreeds
131662001 | Kaghani goat breed (organism) | AnimalBreeds
131663006 | Irish Goat breed (organism) | AnimalBreeds
131664000 | Grisons Striped goat breed (organism) | AnimalBreeds
131665004 | Jining Gray goat breed (organism) | AnimalBreeds
131666003 | Finnish Landrace goat breed (organism) | AnimalBreeds
131667007 | Erzgebirg goat breed (organism) | AnimalBreeds
131668002 | Kamori goat breed (organism) | AnimalBreeds
131669005 | Don goat breed (organism) | AnimalBreeds
131670006 | Kiko goat breed (organism) | AnimalBreeds
131671005 | Kinder goat breed (organism) | AnimalBreeds
131672003 | Pygora goat breed (organism) | AnimalBreeds

131673008 | Wooden Leg goat breed (organism) | AnimalBreeds
131674002 | Alpine Chamoisee goat breed (organism) | AnimalBreeds
131675001 | Massif Central goat breed (organism) | AnimalBreeds
131676000 | Malagueña goat breed (organism) | AnimalBreeds
131677009 | Algarvia goat breed (organism) | AnimalBreeds
131678004 | British Saanen goat breed (organism) | AnimalBreeds
131679007 | British Toggenburg goat breed (organism) | AnimalBreeds
131680005 | Bündner goat breed (organism) | AnimalBreeds
131681009 | Blanca Andaluza goat breed (organism) | AnimalBreeds
131682002 | Blanca Celtiberica goat breed (organism) | AnimalBreeds
131683007 | Bravia goat breed (organism) | AnimalBreeds
131684001 | Black Grisonne goat breed (organism) | AnimalBreeds
131685000 | Chamois of the Alps goat breed (organism) | AnimalBreeds
131686004 | Charnequeria goat breed (organism) | AnimalBreeds
131687008 | Carpathe goat breed (organism) | AnimalBreeds
131688003 | Col Noir du Valais goat breed (organism) | AnimalBreeds
131689006 | Damani goat breed (organism) | AnimalBreeds
131690002 | Des Fosses (Communes de l'Ouest) goat breed (organism) | AnimalBreeds
131691003 | English goat breed (organism) | AnimalBreeds
131692005 | English Guernsey goat breed (organism) | AnimalBreeds
131693000 | German colored goat breed (organism) | AnimalBreeds
131694006 | Guadarrama goat breed (organism) | AnimalBreeds
131695007 | Garganica goat breed (organism) | AnimalBreeds
131696008 | Girgentana goat breed (organism) | AnimalBreeds
131697004 | Jonica goat breed (organism) | AnimalBreeds
131698009 | Murciana-Granadina goat breed (organism) | AnimalBreeds
131699001 | Bündner Oberland sheep breed (organism) | AnimalBreeds
131700000 | British Milk Sheep breed (organism) | AnimalBreeds
131701001 | Brillenschaf sheep breed (organism) | AnimalBreeds
131702008 | Brecknock Hill Cheviot sheep breed (organism) | AnimalBreeds
131703003 | Cholistani sheep breed (organism) | AnimalBreeds
131704009 | Bibrik sheep breed (organism) | AnimalBreeds
131705005 | Columbia sheep breed (organism) | AnimalBreeds
131706006 | Black Welsh Mountain Sheep breed (organism) | AnimalBreeds
131707002 | Blackhead Persian sheep breed (organism) | AnimalBreeds
131708007 | Bleu du Maine sheep breed (organism) | AnimalBreeds
131709004 | Bluefaced Leicester sheep breed (organism) | AnimalBreeds
131710009 | Bond sheep breed (organism) | AnimalBreeds
131711008 | Border Leicester sheep breed (organism) | AnimalBreeds
131712001 | Boreray sheep breed (organism) | AnimalBreeds
131713006 | Bovska sheep breed (organism) | AnimalBreeds
131714000 | Braunes Bergschaf sheep breed (organism) | AnimalBreeds
131715004 | Brazilian Somali sheep breed (organism) | AnimalBreeds
131716003 | Beulah Speckled-Face sheep breed (organism) | AnimalBreeds
131717007 | Dartmoor sheep breed (organism) | AnimalBreeds
131718002 | Fabrianese sheep breed (organism) | AnimalBreeds
131719005 | Exmoor Horn sheep breed (organism) | AnimalBreeds
131720004 | Elliottdale sheep breed (organism) | AnimalBreeds
131721000 | Drysdale sheep breed (organism) | AnimalBreeds
131722007 | Dorset Down sheep breed (organism) | AnimalBreeds
131723002 | German Blackheaded Mutton sheep breed (organism) | AnimalBreeds
131724008 | Kooka sheep breed (organism) | AnimalBreeds
131725009 | Friesian Milk Sheep breed (organism) | AnimalBreeds
131726005 | Gansu Alpine Fine-wool sheep breed (organism) | AnimalBreeds
131727001 | German Whiteheaded Mutton sheep breed (organism) | AnimalBreeds
131728006 | Graue Gehoernte Heidschnucke sheep breed (organism) | AnimalBreeds
131729003 | Han sheep breed (organism) | AnimalBreeds
131730008 | Gromark sheep breed (organism) | AnimalBreeds
131731007 | Gulf Coast Native sheep breed (organism) | AnimalBreeds
131732000 | Dorper sheep breed (organism) | AnimalBreeds
131733005 | Devon Closewool sheep breed (organism) | AnimalBreeds
131734004 | Deutsches Blaukoepfiges Fleischschaf sheep breed (organism) | AnimalBreeds
131735003 | Derbyshire Gritstone sheep breed (organism) | AnimalBreeds
131736002 | Coburger Fuchsschaf sheep breed (organism) | AnimalBreeds
131737006 | Danish Landrace sheep breed (organism) | AnimalBreeds
131738001 | Gute sheep breed (organism) | AnimalBreeds
131739009 | Hampshire sheep breed (organism) | AnimalBreeds
131740006 | Gentile di Puglia sheep breed (organism) | AnimalBreeds
131741005 | German Mountain sheep breed (organism) | AnimalBreeds
131742003 | Luzein sheep breed (organism) | AnimalBreeds
131743008 | Katahdin sheep breed (organism) | AnimalBreeds
131744002 | Leineschaf sheep breed (organism) | AnimalBreeds

131745001 | Lincoln Longwool sheep breed (organism) | AnimalBreeds
131746000 | Llanwenog sheep breed (organism) | AnimalBreeds
131747009 | Lleyn sheep breed (organism) | AnimalBreeds
131748004 | Damara sheep breed (organism) | AnimalBreeds
131749007 | Damani sheep breed (organism) | AnimalBreeds
131750007 | Dalesbred sheep breed (organism) | AnimalBreeds
131751006 | Dala sheep breed (organism) | AnimalBreeds
131752004 | Criollo sheep breed (organism) | AnimalBreeds
131753009 | Cormo sheep breed (organism) | AnimalBreeds
131754003 | Lati sheep breed (organism) | AnimalBreeds
131755002 | Lonk sheep breed (organism) | AnimalBreeds
131756001 | Langhe sheep breed (organism) | AnimalBreeds
131757005 | Manx Loaghtan sheep breed (organism) | AnimalBreeds
131758000 | Masai sheep breed (organism) | AnimalBreeds
131759008 | Merinolandschaf sheep breed (organism) | AnimalBreeds
131760003 | Lohi sheep breed (organism) | AnimalBreeds
131761004 | Ile-de-France sheep breed (organism) | AnimalBreeds
131762006 | Hasht Nagri sheep breed (organism) | AnimalBreeds
131763001 | Hazaragie sheep breed (organism) | AnimalBreeds
131764007 | Coopworth sheep breed (organism) | AnimalBreeds
131765008 | Comisana sheep breed (organism) | AnimalBreeds
131766009 | Comeback sheep breed (organism) | AnimalBreeds
131767000 | Sicilian Barbary sheep breed (organism) | AnimalBreeds
131768005 | Africana sheep breed (organism) | AnimalBreeds
131769002 | Welsh Mountain Badger Faced sheep breed (organism) | AnimalBreeds
131770001 | Hebridean sheep breed (organism) | AnimalBreeds
131771002 | Heidschnucke sheep breed (organism) | AnimalBreeds
131772009 | Herdwick sheep breed (organism) | AnimalBreeds
131773004 | Hill Radnor sheep breed (organism) | AnimalBreeds
131774005 | Icelandic sheep breed (organism) | AnimalBreeds
131775006 | Harnai sheep breed (organism) | AnimalBreeds
131776007 | Istrian Pramenka sheep breed (organism) | AnimalBreeds
131777003 | Jacob sheep breed (organism) | AnimalBreeds
131778008 | Jezerskosolcavska sheep breed (organism) | AnimalBreeds
131779000 | Kachhi sheep breed (organism) | AnimalBreeds
131780002 | Wensleydale sheep breed (organism) | AnimalBreeds
131781003 | West African Dwarf sheep breed (organism) | AnimalBreeds
131782005 | White Suffolk sheep breed (organism) | AnimalBreeds
131783000 | Whiteface Dartmoor sheep breed (organism) | AnimalBreeds
131784006 | Whiteface Woodland sheep breed (organism) | AnimalBreeds
131785007 | Xinjiang Finewool sheep breed (organism) | AnimalBreeds
131786008 | Kajli sheep breed (organism) | AnimalBreeds
131787004 | Hog Island Sheep breed (organism) | AnimalBreeds
131788009 | Biellese sheep breed (organism) | AnimalBreeds
131789001 | Chios sheep breed (organism) | AnimalBreeds
131790005 | Santa Cruz sheep breed (organism) | AnimalBreeds
131791009 | Charollais sheep breed (organism) | AnimalBreeds
131792002 | Castlemilk Moorit sheep breed (organism) | AnimalBreeds
131793007 | Campanian Barbary sheep breed (organism) | AnimalBreeds
131794001 | California Variegated Mutant sheep breed (organism) | AnimalBreeds
131795000 | California Red sheep breed (organism) | AnimalBreeds
131796004 | Sopravissana sheep breed (organism) | AnimalBreeds
131797008 | Somali sheep breed (organism) | AnimalBreeds
131798003 | Welsh Hill Speckled Face sheep breed (organism) | AnimalBreeds
131799006 | Skudde sheep breed (organism) | AnimalBreeds
131800005 | Waziri sheep breed (organism) | AnimalBreeds
131801009 | Shetland sheep breed (organism) | AnimalBreeds
131802002 | Cambridge sheep breed (organism) | AnimalBreeds
131803007 | Solognote sheep breed (organism) | AnimalBreeds
131804001 | Colombian Criollo horse breed (organism) | AnimalBreeds
131805000 | Comtois horse breed (organism) | AnimalBreeds
131806004 | Corsican horse breed (organism) | AnimalBreeds
131807008 | Costa Rican Saddle Horse horse breed (organism) | AnimalBreeds
131808003 | Costeno horse breed (organism) | AnimalBreeds
131809006 | Cuban Paso horse breed (organism) | AnimalBreeds
131810001 | Cayuga breed duck (organism) | AnimalBreeds
131811002 | Runner breed duck (organism) | AnimalBreeds
131812009 | Call breed duck (organism) | AnimalBreeds
131813004 | Orpington breed duck (organism) | AnimalBreeds
131814005 | Crested breed duck (organism) | AnimalBreeds
131815006 | Pommeranian breed duck (organism) | AnimalBreeds
131816007 | Rough Fell sheep breed (organism) | AnimalBreeds

131817003 | Blue Swedish breed duck (organism) | AnimalBreeds
131818008 | Golden 300 hybrid breed duck (organism) | AnimalBreeds
131819000 | Danish Warmblood horse breed (organism) | AnimalBreeds
131820006 | Ancona breed duck (organism) | AnimalBreeds
131821005 | Australian Spotted breed duck (organism) | AnimalBreeds
131822003 | Swaledale sheep breed (organism) | AnimalBreeds
131823008 | Polypay sheep breed (organism) | AnimalBreeds
131824002 | Aylesbury breed duck (organism) | AnimalBreeds
131825001 | Black East Indies breed duck (organism) | AnimalBreeds
131826000 | Coast breed duck (organism) | AnimalBreeds
131827009 | Kromsnaveleend breed duck (organism) | AnimalBreeds
131828004 | Magpie breed duck (organism) | AnimalBreeds
131829007 | Silver appleyard breed duck (organism) | AnimalBreeds
131830002 | Pagliarola sheep breed (organism) | AnimalBreeds
131831003 | Pomeranian Coarsewool sheep breed (organism) | AnimalBreeds
131832005 | Sheep, Breed Undetermined sheep breed (organism) | AnimalBreeds
131833000 | Orkney sheep breed (organism) | AnimalBreeds
131834006 | Old Norwegian sheep breed (organism) | AnimalBreeds
131835007 | Old Format Sheep breed (organism) | AnimalBreeds
131836008 | Norwegian Fur sheep breed (organism) | AnimalBreeds
131837004 | Norfolk Horn sheep breed (organism) | AnimalBreeds
131838009 | Navajo-Churro sheep breed (organism) | AnimalBreeds
131839001 | Swedish yellow breed duck (organism) | AnimalBreeds
131840004 | Diepholz goose breed (organism) | AnimalBreeds
131841000 | African goose breed (organism) | AnimalBreeds
131843002 | Embden goose breed (organism) | AnimalBreeds
131844008 | Chinese white goose breed (organism) | AnimalBreeds
131845009 | Chinese brown goose breed (organism) | AnimalBreeds
131846005 | Toulouse goose breed (organism) | AnimalBreeds
131847001 | American buff goose breed (organism) | AnimalBreeds
131848006 | Pomeranian goose breed (organism) | AnimalBreeds
131849003 | Roman goose breed (organism) | AnimalBreeds
131850003 | Scania goose breed (organism) | AnimalBreeds
131851004 | Racka sheep breed (organism) | AnimalBreeds
131852006 | Rasa Aragonesa sheep breed (organism) | AnimalBreeds
131853001 | Red Engadine sheep breed (organism) | AnimalBreeds
131854007 | Rhoenschaf sheep breed (organism) | AnimalBreeds
131855008 | Sebastopol goose breed (organism) | AnimalBreeds
131856009 | Swedish Island goose breed (organism) | AnimalBreeds
131857000 | Bronze turkey breed (organism) | AnimalBreeds
131858005 | Auburn turkey breed (organism) | AnimalBreeds
131859002 | Bourbon Red turkey breed (organism) | AnimalBreeds
131860007 | Buff turkey breed (organism) | AnimalBreeds
131861006 | Hucul horse breed (organism) | AnimalBreeds
131862004 | AraAppaloosa horse breed (organism) | AnimalBreeds
131863009 | Argentine Criollo horse breed (organism) | AnimalBreeds
131864003 | Argentine Polo Pony horse breed (organism) | AnimalBreeds
131865002 | Australian Pony horse breed (organism) | AnimalBreeds
131866001 | Auxois horse breed (organism) | AnimalBreeds
131867005 | Avelignese horse breed (organism) | AnimalBreeds
131868000 | Azerbaijan horse breed (organism) | AnimalBreeds
131869008 | Azores horse breed (organism) | AnimalBreeds
131870009 | Bali horse breed (organism) | AnimalBreeds
131871008 | Balikun horse breed (organism) | AnimalBreeds
131872001 | Waziri horse breed (organism) | AnimalBreeds
131873006 | Banker Horse horse breed (organism) | AnimalBreeds
131874000 | Bardigiano horse breed (organism) | AnimalBreeds
131875004 | Batak horse breed (organism) | AnimalBreeds
131876003 | Bavarian Warmblood horse breed (organism) | AnimalBreeds
131877007 | Belgian Ardennais horse breed (organism) | AnimalBreeds
131878002 | Belgian Halfblood horse breed (organism) | AnimalBreeds
131879005 | Belgian Warmblood horse breed (organism) | AnimalBreeds
131880008 | Bhutia horse breed (organism) | AnimalBreeds
131881007 | Black Sea Horse horse breed (organism) | AnimalBreeds
131882000 | Bosnian horse breed (organism) | AnimalBreeds
131883005 | Boulonnais horse breed (organism) | AnimalBreeds
131884004 | Brandenburg horse breed (organism) | AnimalBreeds
131885003 | Brazilian Sport Horse horse breed (organism) | AnimalBreeds
131886002 | British Appaloosa horse breed (organism) | AnimalBreeds
131887006 | British Riding Pony horse breed (organism) | AnimalBreeds
131888001 | British Spotted Pony horse breed (organism) | AnimalBreeds
131889009 | Buohai horse breed (organism) | AnimalBreeds

131890000 | Buryat horse breed (organism) | AnimalBreeds
131891001 | Calabrian horse breed (organism) | AnimalBreeds
131892008 | Camargue horse breed (organism) | AnimalBreeds
131893003 | Canadian Cutting Horse horse breed (organism) | AnimalBreeds
131894009 | Canadian Rustic Pony horse breed (organism) | AnimalBreeds
131895005 | Canadian Sport Horse horse breed (organism) | AnimalBreeds
131896006 | Canik horse breed (organism) | AnimalBreeds
131897002 | Cape Horse horse breed (organism) | AnimalBreeds
131898007 | Cerbat horse breed (organism) | AnimalBreeds
131899004 | Chakouyi horse breed (organism) | AnimalBreeds
131900009 | Chara Horse horse breed (organism) | AnimalBreeds
131901008 | Chickasaw horse breed (organism) | AnimalBreeds
131902001 | Chilote horse breed (organism) | AnimalBreeds
131903006 | Chinese Kazakh horse breed (organism) | AnimalBreeds
131904000 | Chinese Mongolian horse breed (organism) | AnimalBreeds
131905004 | Chumbivilcas horse breed (organism) | AnimalBreeds
131906003 | Chumysh horse breed (organism) | AnimalBreeds
131907007 | Cirit horse breed (organism) | AnimalBreeds
131908002 | Irish Draft horse breed (organism) | AnimalBreeds
131909005 | Irish Hunter horse breed (organism) | AnimalBreeds
131910000 | Cuban Trotter horse breed (organism) | AnimalBreeds
131911001 | Italian Heavy Draft horse breed (organism) | AnimalBreeds
131912008 | Jabe horse breed (organism) | AnimalBreeds
131913003 | Java horse breed (organism) | AnimalBreeds
131914009 | Vendéen sheep breed (organism) | AnimalBreeds
131915005 | Czech Warmblood horse breed (organism) | AnimalBreeds
131916006 | Jinhong horse breed (organism) | AnimalBreeds
131917002 | Jinzhou horse breed (organism) | AnimalBreeds
131918007 | Saxony breed duck (organism) | AnimalBreeds
131919004 | Danubian horse breed (organism) | AnimalBreeds
131920005 | Karachai horse breed (organism) | AnimalBreeds
131921009 | Karakacan horse breed (organism) | AnimalBreeds
131922002 | Kathiawari horse breed (organism) | AnimalBreeds
131923007 | Ke-Er-Qin horse breed (organism) | AnimalBreeds
131924001 | Kirgiz horse breed (organism) | AnimalBreeds
131925000 | Kuznet horse breed (organism) | AnimalBreeds
131926004 | Landais horse breed (organism) | AnimalBreeds
131927008 | Lewitzer horse breed (organism) | AnimalBreeds
131928003 | Lichuan horse breed (organism) | AnimalBreeds
131929006 | Lijiang horse breed (organism) | AnimalBreeds
131930001 | Llanero horse breed (organism) | AnimalBreeds
131931002 | Lombok horse breed (organism) | AnimalBreeds
131932009 | Lundy Pony horse breed (organism) | AnimalBreeds
131933004 | Malakan horse breed (organism) | AnimalBreeds
131934005 | Malopolski horse breed (organism) | AnimalBreeds
131935006 | Datong horse breed (organism) | AnimalBreeds
131936007 | Mangalarga Paulista horse breed (organism) | AnimalBreeds
131937003 | Dulmen Pony horse breed (organism) | AnimalBreeds
131938008 | Maremmana horse breed (organism) | AnimalBreeds
131939000 | Marwari horse breed (organism) | AnimalBreeds
131940003 | Megezh horse breed (organism) | AnimalBreeds
131941004 | Megrel horse breed (organism) | AnimalBreeds
131942006 | Merens horse breed (organism) | AnimalBreeds
131943001 | Messara horse breed (organism) | AnimalBreeds
131944007 | Sumba horse breed (organism) | AnimalBreeds
131945008 | Sumbawa horse breed (organism) | AnimalBreeds
131946009 | Swedish Ardennes horse breed (organism) | AnimalBreeds
131947000 | Dutch Tuigpaard horse breed (organism) | AnimalBreeds
131948005 | East and Southeast Anadolu horse breed (organism) | AnimalBreeds
131949002 | Thai Pony horse breed (organism) | AnimalBreeds
131950002 | Thessalonian horse breed (organism) | AnimalBreeds
131951003 | Tibetan horse breed (organism) | AnimalBreeds
131952005 | Tieling horse breed (organism) | AnimalBreeds
131953000 | Timor horse breed (organism) | AnimalBreeds
131954006 | Trakya horse breed (organism) | AnimalBreeds
131955007 | Trote en Gallope horse breed (organism) | AnimalBreeds
131956008 | Turkoman horse breed (organism) | AnimalBreeds
131957004 | Tushin horse breed (organism) | AnimalBreeds
131958009 | Tuva horse breed (organism) | AnimalBreeds
131959001 | Uzunyayla horse breed (organism) | AnimalBreeds
131960006 | Voronezh Coach Horse horse breed (organism) | AnimalBreeds
131961005 | Elegant Warmblood horse breed (organism) | AnimalBreeds

131962003 | Welsh Cob horse breed (organism) | AnimalBreeds
131963008 | Welsh Mountain Pony horse breed (organism) | AnimalBreeds
131964002 | English Hack horse breed (organism) | AnimalBreeds
131965001 | Wurttemberg horse breed (organism) | AnimalBreeds
131966000 | Xilingol horse breed (organism) | AnimalBreeds
131967009 | Yanqi horse breed (organism) | AnimalBreeds
131968004 | Yemeni Horses horse breed (organism) | AnimalBreeds
131969007 | Yili horse breed (organism) | AnimalBreeds
131970008 | Yiwu horse breed (organism) | AnimalBreeds
131971007 | Yunnan horse breed (organism) | AnimalBreeds
131972000 | German Riding Pony horse breed (organism) | AnimalBreeds
131973005 | Guanzhong horse breed (organism) | AnimalBreeds
131974004 | Guizhou horse breed (organism) | AnimalBreeds
131975003 | Guoxia horse breed (organism) | AnimalBreeds
131976002 | Erlunchun horse breed (organism) | AnimalBreeds
131977006 | Half Saddlebred horse breed (organism) | AnimalBreeds
131978001 | Flores horse breed (organism) | AnimalBreeds
131979009 | Freiberg horse breed (organism) | AnimalBreeds
131980007 | Hessen horse breed (organism) | AnimalBreeds
131981006 | Hinis horse breed (organism) | AnimalBreeds
131982004 | Hirzai horse breed (organism) | AnimalBreeds
131983009 | Hungarian Coldblood horse breed (organism) | AnimalBreeds
131984003 | Hungarian Dun horse breed (organism) | AnimalBreeds
131985002 | Hungarian Sport Horse horse breed (organism) | AnimalBreeds
131986001 | International Striped Horse horse breed (organism) | AnimalBreeds
131987005 | Irish Cob horse breed (organism) | AnimalBreeds
131988000 | Mezen horse breed (organism) | AnimalBreeds
131989008 | Mezohegyes Sport Horse horse breed (organism) | AnimalBreeds
131990004 | French Cob horse breed (organism) | AnimalBreeds
131991000 | French Saddle pony horse breed (organism) | AnimalBreeds
131992007 | Murakoz horse breed (organism) | AnimalBreeds
131993002 | Finnhorse Draft horse breed (organism) | AnimalBreeds
131994008 | Mecklenburg horse breed (organism) | AnimalBreeds
131995009 | Baheij chicken breed (organism) | AnimalBreeds
131996005 | Aseel chicken breed (organism) | AnimalBreeds
131997001 | Bandara chicken breed (organism) | AnimalBreeds
131998006 | Catalana chicken breed (organism) | AnimalBreeds
131999003 | Australian Gamefowl chicken breed (organism) | AnimalBreeds
132000009 | Ayam Cemani chicken breed (organism) | AnimalBreeds
132001008 | Swedish Spotted Hen chicken breed (organism) | AnimalBreeds
132002001 | Belgian Booted Bantam chicken breed (organism) | AnimalBreeds
132003006 | Brabanter chicken breed (organism) | AnimalBreeds
132004000 | Braekel chicken breed (organism) | AnimalBreeds
132005004 | Cochin, Standard chicken breed (organism) | AnimalBreeds
132006003 | Old English Bantam Game chicken breed (organism) | AnimalBreeds
132007007 | Gotland chicken breed (organism) | AnimalBreeds
132008002 | Groninger Meeuwen chicken breed (organism) | AnimalBreeds
132009005 | Haiti Créole pig breed (organism) | AnimalBreeds
132010000 | Manor Hybrid pig breed (organism) | AnimalBreeds
132011001 | Hamline pig breed (organism) | AnimalBreeds
132012008 | Manor Ranger pig breed (organism) | AnimalBreeds
132013003 | Manor Meishan pig breed (organism) | AnimalBreeds
132014009 | Cotswold Gold pig breed (organism) | AnimalBreeds
132015005 | Cotswold Platinum pig breed (organism) | AnimalBreeds
132016006 | Cotswold 16 pig breed (organism) | AnimalBreeds
132017002 | Cotswold 29 pig breed (organism) | AnimalBreeds
132018007 | Cotswold 90 pig breed (organism) | AnimalBreeds
132019004 | Hampen pig breed (organism) | AnimalBreeds
132020005 | SPM pig breed (organism) | AnimalBreeds
132021009 | High Conformation White pig breed (organism) | AnimalBreeds
132022002 | Line 32 pig breed (organism) | AnimalBreeds
132023007 | Line 21 pig breed (organism) | AnimalBreeds
132024001 | Meatline pig breed (organism) | AnimalBreeds
132025000 | Hampline pig breed (organism) | AnimalBreeds
132026004 | Euroline pig breed (organism) | AnimalBreeds
132027008 | Norline pig breed (organism) | AnimalBreeds
132028003 | Premier pig breed (organism) | AnimalBreeds
132029006 | Tribred pig breed (organism) | AnimalBreeds
132030001 | American Essex pig breed (organism) | AnimalBreeds
132031002 | Sino-Gascony pig breed (organism) | AnimalBreeds
132032009 | Guadeloupe Créole pig breed (organism) | AnimalBreeds
132033004 | Managra pig breed (organism) | AnimalBreeds

132034005 | Canadian Landrace pig breed (organism) | AnimalBreeds
132035006 | Canadian Yorkshire pig breed (organism) | AnimalBreeds
132037003 | Pineywoods pig breed (organism) | AnimalBreeds
132038008 | Catalina Island pig breed (organism) | AnimalBreeds
132039000 | Ras-n-Lansa pig breed (organism) | AnimalBreeds
132040003 | Pitman-Moore Miniature pig breed (organism) | AnimalBreeds
132041004 | Vita Vet Lab Minipig pig breed (organism) | AnimalBreeds
132042006 | Hanford Miniature pig breed (organism) | AnimalBreeds
132043001 | Black Hampshire pig breed (organism) | AnimalBreeds
132044007 | Red Hamprace pig breed (organism) | AnimalBreeds
132045008 | American Yorkshire pig breed (organism) | AnimalBreeds
132046009 | American Berkshire pig breed (organism) | AnimalBreeds
132047000 | Camborough Blue pig breed (organism) | AnimalBreeds
132048005 | Camborough 12 pig breed (organism) | AnimalBreeds
132049002 | Westrain pig breed (organism) | AnimalBreeds
132050002 | Dalland 030 pig breed (organism) | AnimalBreeds
132051003 | Razor-Back pig breed (organism) | AnimalBreeds
132052005 | Macau pig breed (organism) | AnimalBreeds
132053000 | Moura pig breed (organism) | AnimalBreeds
132054006 | Canastra pig breed (organism) | AnimalBreeds
132055007 | Pirapetinga pig breed (organism) | AnimalBreeds
132056008 | Piau pig breed (organism) | AnimalBreeds
132057004 | Nilo-Canastra pig breed (organism) | AnimalBreeds
132058009 | Canastrão pig breed (organism) | AnimalBreeds
132059001 | Canastrão, Junqueira pig breed (organism) | AnimalBreeds
132060006 | Canastrão, Capitão Chico pig breed (organism) | AnimalBreeds
132061005 | Canastrão, Zabumba pig breed (organism) | AnimalBreeds
132062003 | Canastrão, Cabano pig breed (organism) | AnimalBreeds
132063008 | Canastrão, Vermelho pig breed (organism) | AnimalBreeds
132064002 | Piau, Caruncho Piau pig breed (organism) | AnimalBreeds
132065001 | Canastrinho pig breed (organism) | AnimalBreeds
132066000 | Honduras Switch-Tail pig breed (organism) | AnimalBreeds
132067009 | Mastergilt pig breed (organism) | AnimalBreeds
132068004 | Sovereign pig breed (organism) | AnimalBreeds
132069007 | Poltava pig breed (organism) | AnimalBreeds
132070008 | Lipetsk pig breed (organism) | AnimalBreeds
132071007 | Soviet Meat pig breed (organism) | AnimalBreeds
132072000 | Central Russian pig breed (organism) | AnimalBreeds
132073005 | Steppe Meat pig breed (organism) | AnimalBreeds
132074004 | Kharkov pig breed (organism) | AnimalBreeds
132075003 | Dnepropetrovsk pig breed (organism) | AnimalBreeds
132076002 | Russian Large White pig breed (organism) | AnimalBreeds
132077006 | Forest Mountain pig breed (organism) | AnimalBreeds
132078001 | Dnieper pig breed (organism) | AnimalBreeds
132079009 | Iberian pig breed (organism) | AnimalBreeds
132080007 | Iberian, Extremadura Red pig breed (organism) | AnimalBreeds
132081006 | Iberian, Jabugo Spotted pig breed (organism) | AnimalBreeds
132082004 | Iberian, Black Iberian pig breed (organism) | AnimalBreeds
132083009 | Philippine Native, Ilocos pig breed (organism) | AnimalBreeds
132084003 | Philippine Native, Jalajala pig breed (organism) | AnimalBreeds
132085002 | Mangalizta pig breed (organism) | AnimalBreeds
132086001 | Alentejana pig breed (organism) | AnimalBreeds
132087005 | Belgian Landrace, BN pig breed (organism) | AnimalBreeds
132088000 | French Large White pig breed (organism) | AnimalBreeds
132089008 | Hyper Large White pig breed (organism) | AnimalBreeds
132090004 | Tia Meslan pig breed (organism) | AnimalBreeds
132091000 | Pen ar Lan 77 pig breed (organism) | AnimalBreeds
132092007 | Penshire pig breed (organism) | AnimalBreeds
132093002 | Laconie pig breed (organism) | AnimalBreeds
132094008 | Murcian pig breed (organism) | AnimalBreeds
132095009 | Cavallino pig breed (organism) | AnimalBreeds
132096005 | Calabrian pig breed (organism) | AnimalBreeds
132097001 | Apulian pig breed (organism) | AnimalBreeds
132098006 | Siena Belted pig breed (organism) | AnimalBreeds
132099003 | Calascibetta pig breed (organism) | AnimalBreeds
132100006 | Güssing Forest Pig pig breed (organism) | AnimalBreeds
132101005 | Swiss Edelschwein pig breed (organism) | AnimalBreeds
132102003 | North Caucasus pig breed (organism) | AnimalBreeds
132103008 | Don pig breed (organism) | AnimalBreeds
132104002 | Rostov pig breed (organism) | AnimalBreeds
132105001 | Russian Long-Eared White pig breed (organism) | AnimalBreeds
132106000 | Russian Short-Eared White pig breed (organism) | AnimalBreeds

132107009 | Prisheksninsk pig breed (organism) | AnimalBreeds
132108004 | Breitov pig breed (organism) | AnimalBreeds
132109007 | Livny pig breed (organism) | AnimalBreeds
132110002 | Tsivilsk pig breed (organism) | AnimalBreeds
132111003 | Urzhum pig breed (organism) | AnimalBreeds
132112005 | Minisib pig breed (organism) | AnimalBreeds
132113000 | Sakhalin White pig breed (organism) | AnimalBreeds
132114006 | North Siberian pig breed (organism) | AnimalBreeds
132115007 | Siberian Black Pied pig breed (organism) | AnimalBreeds
132116008 | Kemerovo pig breed (organism) | AnimalBreeds
132117004 | KM-1 pig breed (organism) | AnimalBreeds
132118009 | Aksaî Black Pied pig breed (organism) | AnimalBreeds
132119001 | Semirechensk pig breed (organism) | AnimalBreeds
132120007 | Min pig breed (organism) | AnimalBreeds
132121006 | Sanjiang White pig breed (organism) | AnimalBreeds
132122004 | Basque Black Pied pig breed (organism) | AnimalBreeds
132123009 | Corsican pig breed (organism) | AnimalBreeds
132124003 | Créole pig breed (organism) | AnimalBreeds
132125002 | Gascony pig breed (organism) | AnimalBreeds
132126001 | Limousin pig breed (organism) | AnimalBreeds
132127005 | Harbin White pig breed (organism) | AnimalBreeds
132128000 | Heilongjiang Spotted pig breed (organism) | AnimalBreeds
132129008 | Liaoning Black pig breed (organism) | AnimalBreeds
132130003 | Huang-Huai-Hai Black, Shenxian pig breed (organism) | AnimalBreeds
132131004 | Huang-Huai-Hai Black pig breed (organism) | AnimalBreeds
132132006 | Bamei pig breed (organism) | AnimalBreeds
132133001 | Hanjiang Black pig breed (organism) | AnimalBreeds
132134007 | Ding pig breed (organism) | AnimalBreeds
132135008 | Huai pig breed (organism) | AnimalBreeds
132136009 | New Huai pig breed (organism) | AnimalBreeds
132137000 | Mashen pig breed (organism) | AnimalBreeds
132138005 | Yimeng Black pig breed (organism) | AnimalBreeds
132139002 | Hetao Lop-Ear pig breed (organism) | AnimalBreeds
132140000 | Korean Native pig breed (organism) | AnimalBreeds
132141001 | Korean Improved pig breed (organism) | AnimalBreeds
132142008 | Penbuk pig breed (organism) | AnimalBreeds
132143003 | Beijing Black pig breed (organism) | AnimalBreeds
132144009 | Chenghua pig breed (organism) | AnimalBreeds
132145005 | Taoyuan pig breed (organism) | AnimalBreeds
132146006 | Taiwan Small Black pig breed (organism) | AnimalBreeds
132147002 | Taiwan Small Red pig breed (organism) | AnimalBreeds
132148007 | Guanling pig breed (organism) | AnimalBreeds
132149004 | Huchuan Mountain pig breed (organism) | AnimalBreeds
132150004 | Rongchang pig breed (organism) | AnimalBreeds
132151000 | Wujin pig breed (organism) | AnimalBreeds
132152007 | Dahe pig breed (organism) | AnimalBreeds
132153002 | Yanan pig breed (organism) | AnimalBreeds
132154008 | South Yunnan Short-Eared pig breed (organism) | AnimalBreeds
132155009 | Hainan, Lingao pig breed (organism) | AnimalBreeds
132156005 | Hainan, Tunchang pig breed (organism) | AnimalBreeds
132157001 | Hainan, Wenchang pig breed (organism) | AnimalBreeds
132158006 | Liang Guang Small Spotted pig breed (organism) | AnimalBreeds
132159003 | German Pasture pig breed (organism) | AnimalBreeds
132160008 | Piau, Sorocaba pig breed (organism) | AnimalBreeds
132161007 | Nilo pig breed (organism) | AnimalBreeds
132162000 | Bahia pig breed (organism) | AnimalBreeds
132163005 | Perna-Curta pig breed (organism) | AnimalBreeds
132164004 | Carunchinho pig breed (organism) | AnimalBreeds
132165003 | Mandi pig breed (organism) | AnimalBreeds
132166002 | Orehla de Colher pig breed (organism) | AnimalBreeds
132167006 | Venezuelan Black pig breed (organism) | AnimalBreeds
132168001 | Bolivian pig breed (organism) | AnimalBreeds
132169009 | Pelón pig breed (organism) | AnimalBreeds
132170005 | Mexican Wattled pig breed (organism) | AnimalBreeds
132171009 | Dalland 080 pig breed (organism) | AnimalBreeds
132173007 | Monarch pig breed (organism) | AnimalBreeds
132174001 | Bisaro pig breed (organism) | AnimalBreeds
132175000 | Black Hairless pig breed (organism) | AnimalBreeds
132176004 | Black Mangalitsa pig breed (organism) | AnimalBreeds
132178003 | Borghigiana pig breed (organism) | AnimalBreeds
132179006 | Chianina pig breed (organism) | AnimalBreeds
132180009 | Cosentina pig breed (organism) | AnimalBreeds

132181008 | Cuino pig breed (organism) | AnimalBreeds
132182001 | Friuli Black pig breed (organism) | AnimalBreeds
132183006 | Fumati pig breed (organism) | AnimalBreeds
132184000 | Galician pig breed (organism) | AnimalBreeds
132185004 | German Berkshire pig breed (organism) | AnimalBreeds
132186003 | Ghori pig breed (organism) | AnimalBreeds
132187007 | Jianli pig breed (organism) | AnimalBreeds
132188002 | Lucanian pig breed (organism) | AnimalBreeds
132189005 | Maremmana pig breed (organism) | AnimalBreeds
132190001 | Miami pig breed (organism) | AnimalBreeds
132191002 | Montmorillon pig breed (organism) | AnimalBreeds
132192009 | Old Swedish Spotted pig breed (organism) | AnimalBreeds
132193004 | Oliventina pig breed (organism) | AnimalBreeds
132194005 | Parmense pig breed (organism) | AnimalBreeds
132195006 | Romagnola pig breed (organism) | AnimalBreeds
132196007 | Siberian pig breed (organism) | AnimalBreeds
132197003 | Small White pig breed (organism) | AnimalBreeds
132198008 | Baltaret pig breed (organism) | AnimalBreeds
132199000 | Tunchang pig breed (organism) | AnimalBreeds
132200002 | Sterling pig breed (organism) | AnimalBreeds
132201003 | Vich pig breed (organism) | AnimalBreeds
132202005 | Vietnamese pig breed (organism) | AnimalBreeds
132203000 | Vitoria pig breed (organism) | AnimalBreeds
132204006 | Wai Chow pig breed (organism) | AnimalBreeds
132205007 | Yorkshire Blue and White pig breed (organism) | AnimalBreeds
132206008 | Dalland 020 pig breed (organism) | AnimalBreeds
132207004 | Wiltshire pig breed (organism) | AnimalBreeds
132208009 | Hamroc pig breed (organism) | AnimalBreeds
132209001 | DRU (TM) Terminals pig breed (organism) | AnimalBreeds
132210006 | Camborough 22 pig breed (organism) | AnimalBreeds
132211005 | Camborough 15 pig breed (organism) | AnimalBreeds
132212003 | PR 1050 pig breed (organism) | AnimalBreeds
132213008 | PR 1075 pig breed (organism) | AnimalBreeds
132214002 | Chryak PIC pig breed (organism) | AnimalBreeds
132215001 | Canadian Royal Blue pig breed (organism) | AnimalBreeds
132216000 | Line 500 Duroc pig breed (organism) | AnimalBreeds
132217009 | Bodmin 950 pig breed (organism) | AnimalBreeds
132218004 | Canadian Duroc pig breed (organism) | AnimalBreeds
132219007 | Canadian Hampshire pig breed (organism) | AnimalBreeds
132220001 | Ba Xuyen pig breed (organism) | AnimalBreeds
132221002 | Arapawa Island pig breed (organism) | AnimalBreeds
132222009 | Wuzhishan pig breed (organism) | AnimalBreeds
132223004 | Philippine Native pig breed (organism) | AnimalBreeds
132224005 | Sinclair Miniature pig breed (organism) | AnimalBreeds
132225006 | Saddleback pig breed (organism) | AnimalBreeds
132226007 | Yucatan Miniature pig breed (organism) | AnimalBreeds
132227003 | Bantu pig breed (organism) | AnimalBreeds
132228008 | Tibetan pig breed (organism) | AnimalBreeds
132229000 | Turopolje pig breed (organism) | AnimalBreeds
132230005 | Vietnamese Pot-Bellied Pig pig breed (organism) | AnimalBreeds
132231009 | American Landrace pig breed (organism) | AnimalBreeds
132232002 | Swallow Belied Mangalitza pig breed (organism) | AnimalBreeds
132233007 | Fengjing pig breed (organism) | AnimalBreeds
132234001 | Finnish Landrace pig breed (organism) | AnimalBreeds
132235000 | Guinea Hog pig breed (organism) | AnimalBreeds
132236004 | Hezuo pig breed (organism) | AnimalBreeds
132237008 | Ossabaw Island pig breed (organism) | AnimalBreeds
132238003 | Kele pig breed (organism) | AnimalBreeds
132239006 | Krskopolje pig breed (organism) | AnimalBreeds
132240008 | Kunekune pig breed (organism) | AnimalBreeds
132241007 | Large Black-White pig breed (organism) | AnimalBreeds
132242000 | Lithuanian Native pig breed (organism) | AnimalBreeds
132243005 | Meishan pig breed (organism) | AnimalBreeds
132244004 | Jinhua pig breed (organism) | AnimalBreeds
132245003 | Ningxiang pig breed (organism) | AnimalBreeds
132246002 | Mora Romagnola pig breed (organism) | AnimalBreeds
132247006 | Mukota pig breed (organism) | AnimalBreeds
132248001 | Minzhu pig breed (organism) | AnimalBreeds
132249009 | Neijiang pig breed (organism) | AnimalBreeds
132250009 | Mulefoot pig breed (organism) | AnimalBreeds
132251008 | Normand pig breed (organism) | AnimalBreeds
132252001 | Angeln Saddleback pig breed (organism) | AnimalBreeds

132253006 | Greek Local pig breed (organism) | AnimalBreeds
132254000 | Icelandic pig breed (organism) | AnimalBreeds
132255004 | Casertana pig breed (organism) | AnimalBreeds
132256003 | Madonie-Sicilian pig breed (organism) | AnimalBreeds
132257007 | Sardinian pig breed (organism) | AnimalBreeds
132258002 | Sicilian pig breed (organism) | AnimalBreeds
132259005 | Zlotniki Spotted pig breed (organism) | AnimalBreeds
132260000 | Zlotniki White pig breed (organism) | AnimalBreeds
132261001 | Siska pig breed (organism) | AnimalBreeds
132262008 | Sumadija pig breed (organism) | AnimalBreeds
132263003 | Froxfield Pygmy pig breed (organism) | AnimalBreeds
132264009 | Danish Large White pig breed (organism) | AnimalBreeds
132265005 | Danish Duroc pig breed (organism) | AnimalBreeds
132266006 | Danish Hampshire pig breed (organism) | AnimalBreeds
132267002 | Piggham pig breed (organism) | AnimalBreeds
132268007 | New York Red pig breed (organism) | AnimalBreeds
132269004 | Finnish Yorkshire pig breed (organism) | AnimalBreeds
132270003 | Dutch Yorkshire pig breed (organism) | AnimalBreeds
132271004 | Pulawy pig breed (organism) | AnimalBreeds
132272006 | Pomeranian pig breed (organism) | AnimalBreeds
132273001 | Polish Landrace pig breed (organism) | AnimalBreeds
132274007 | Estonian Bacon pig breed (organism) | AnimalBreeds
132275008 | Latvian White pig breed (organism) | AnimalBreeds
132276009 | Lithuanian White pig breed (organism) | AnimalBreeds
132277000 | BKB-1 pig breed (organism) | AnimalBreeds
132278005 | Belorus Black Pied pig breed (organism) | AnimalBreeds
132279002 | Mirgorod pig breed (organism) | AnimalBreeds
132280004 | Liang Guang Small Spotted, Luchuan pig breed (organism) | AnimalBreeds
132281000 | Fujian Small pig breed (organism) | AnimalBreeds
132282007 | North Fujian Black-and-White pig breed (organism) | AnimalBreeds
132283002 | Fuan Spotted pig breed (organism) | AnimalBreeds
132284008 | Putian pig breed (organism) | AnimalBreeds
132285009 | Fuzhou Black pig breed (organism) | AnimalBreeds
132286005 | Minbei Spotted pig breed (organism) | AnimalBreeds
132287001 | Lantang pig breed (organism) | AnimalBreeds
132288006 | Liang Guang Small Spotted, Guangdong Small Ear pig breed (organism) | AnimalBreeds
132289003 | Longlin pig breed (organism) | AnimalBreeds
132290007 | Yuedong Black pig breed (organism) | AnimalBreeds
132291006 | Xiang pig breed (organism) | AnimalBreeds
132292004 | Cantonese pig breed (organism) | AnimalBreeds
132293009 | Jinhua, Dongyang pig breed (organism) | AnimalBreeds
132294003 | Jinhua, Yongkang pig breed (organism) | AnimalBreeds
132295002 | Daweizi pig breed (organism) | AnimalBreeds
132296001 | Huazhong Two-End Black pig breed (organism) | AnimalBreeds
132297005 | Huazhong Two-End Black, Jianli pig breed (organism) | AnimalBreeds
132298000 | Huazhong Two-End Black, Tongcheng pig breed (organism) | AnimalBreeds
132299008 | Huazhong Two-End Black, Satzeling pig breed (organism) | AnimalBreeds
132300000 | Ganzhongnan Spotted pig breed (organism) | AnimalBreeds
132301001 | Hang pig breed (organism) | AnimalBreeds
132302008 | Leping pig breed (organism) | AnimalBreeds
132303003 | Longyou Black pig breed (organism) | AnimalBreeds
132304009 | Wuyi Black pig breed (organism) | AnimalBreeds
132305005 | Lee-Sung pig breed (organism) | AnimalBreeds
132306006 | Lan-Yu pig breed (organism) | AnimalBreeds
132307002 | Vietnamese Yorkshire pig breed (organism) | AnimalBreeds
132308007 | Yujiang pig breed (organism) | AnimalBreeds
132309004 | Wanzhe Spotted pig breed (organism) | AnimalBreeds
132310009 | Wanzhe Spotted, Chunan Spotted pig breed (organism) | AnimalBreeds
132311008 | Wanzhe Spotted, Wannan Spotted pig breed (organism) | AnimalBreeds
132312001 | Shengxian Spotted pig breed (organism) | AnimalBreeds
132313006 | Qingping pig breed (organism) | AnimalBreeds
132314000 | Xiangxi Black pig breed (organism) | AnimalBreeds
132315004 | Bamaxiang pig breed (organism) | AnimalBreeds
132316003 | Taihu pig breed (organism) | AnimalBreeds
132317007 | Erhulian pig breed (organism) | AnimalBreeds
132318002 | Jiaxing Black pig breed (organism) | AnimalBreeds
132319005 | Mi pig breed (organism) | AnimalBreeds
132320004 | Shahutou pig breed (organism) | AnimalBreeds
132321000 | Jiaoxi pig breed (organism) | AnimalBreeds
132322007 | Shanghai White pig breed (organism) | AnimalBreeds
132323002 | Hubei White pig breed (organism) | AnimalBreeds
132324008 | Xinjin pig breed (organism) | AnimalBreeds

132325009 | Xinjin, Jilin Black pig breed (organism) | AnimalBreeds
132326005 | Xinjin, Ning-an pig breed (organism) | AnimalBreeds
132327001 | Í pig breed (organism) | AnimalBreeds
132328006 | DBI pig breed (organism) | AnimalBreeds
132329003 | Xinjin, Xinjin pig breed (organism) | AnimalBreeds
132330008 | Meixin pig breed (organism) | AnimalBreeds
132331007 | North East China Spotted pig breed (organism) | AnimalBreeds
132332000 | Fannong Spotted pig breed (organism) | AnimalBreeds
132333005 | Laoshan pig breed (organism) | AnimalBreeds
132334004 | Nanjing Black pig breed (organism) | AnimalBreeds
132335003 | Shanxi Black pig breed (organism) | AnimalBreeds
132336002 | Ganzhou White pig breed (organism) | AnimalBreeds
132337006 | Guangxi White pig breed (organism) | AnimalBreeds
132338001 | Hanzhong White pig breed (organism) | AnimalBreeds
132339009 | Lutai White pig breed (organism) | AnimalBreeds
132340006 | Yili White pig breed (organism) | AnimalBreeds
132341005 | Xinjiang White pig breed (organism) | AnimalBreeds
132342003 | BSI pig breed (organism) | AnimalBreeds
132343008 | Mong Cai pig breed (organism) | AnimalBreeds
132344002 | Lang Hong pig breed (organism) | AnimalBreeds
132345001 | Muong Khuong pig breed (organism) | AnimalBreeds
132346000 | Meo pig breed (organism) | AnimalBreeds
132347009 | Tong Con pig breed (organism) | AnimalBreeds
132348004 | Ha Bac pig breed (organism) | AnimalBreeds
132349007 | Thai Binh pig breed (organism) | AnimalBreeds
132350007 | Co pig breed (organism) | AnimalBreeds
132351006 | Swiss Improved Landrace pig breed (organism) | AnimalBreeds
132352004 | German Landrace B pig breed (organism) | AnimalBreeds
132353009 | Edelschwein pig breed (organism) | AnimalBreeds
132354003 | Swabian-Hall pig breed (organism) | AnimalBreeds
132355002 | Bentheim Black Pied pig breed (organism) | AnimalBreeds
132356001 | Baldinger Spotted pig breed (organism) | AnimalBreeds
132357005 | German Red Pied pig breed (organism) | AnimalBreeds
132358000 | German Cornwall pig breed (organism) | AnimalBreeds
132359008 | Göttingen Miniature pig breed (organism) | AnimalBreeds
132360003 | Munich Miniature pig breed (organism) | AnimalBreeds
132361004 | Leicoma pig breed (organism) | AnimalBreeds
132362006 | Schwerfurt Meat pig breed (organism) | AnimalBreeds
132363001 | Hungarian White pig breed (organism) | AnimalBreeds
132364007 | Hungahyb pig breed (organism) | AnimalBreeds
132365008 | Bulgarian Native pig breed (organism) | AnimalBreeds
132366009 | East Balkan pig breed (organism) | AnimalBreeds
132367000 | Kula pig breed (organism) | AnimalBreeds
132368005 | Nghia Binh pig breed (organism) | AnimalBreeds
132681007 | Bergamasca sheep breed (organism) | AnimalBreeds
132682000 | Portland sheep breed (organism) | AnimalBreeds
132684004 | Weisse Hornlose Heidschnucke sheep breed (organism) | AnimalBreeds
132685003 | Drents Heideschaap sheep breed (organism) | AnimalBreeds
132686002 | Kameroen sheep breed (organism) | AnimalBreeds
132687006 | Mergelland sheep breed (organism) | AnimalBreeds
132688001 | Ouessant sheep breed (organism) | AnimalBreeds
132689009 | Canadian Arcott sheep breed (organism) | AnimalBreeds
132690000 | Noordhollander sheep breed (organism) | AnimalBreeds
132691001 | Chocolate turkey breed (organism) | AnimalBreeds
132692008 | Lilac turkey breed (organism) | AnimalBreeds
132693003 | Silver Auburn turkey breed (organism) | AnimalBreeds
132695005 | Wild cross turkey (organism) | AnimalBreeds
132696006 | Matrouh chicken breed (organism) | AnimalBreeds
132697002 | Rijnlam-A sheep breed (organism) | AnimalBreeds
132698007 | Schoonebeker sheep breed (organism) | AnimalBreeds
132699004 | Wallis Blacknosed Sheep breed (organism) | AnimalBreeds
132700003 | Khaki Campbell breed duck (organism) | AnimalBreeds
132701004 | Newfoundland sheep breed (organism) | AnimalBreeds
132702006 | Wallis Country Sheep breed (organism) | AnimalBreeds
132703001 | Rideau Arcott sheep breed (organism) | AnimalBreeds
132704007 | Tukidale sheep breed (organism) | AnimalBreeds
132705008 | Polwarth sheep breed (organism) | AnimalBreeds
132706009 | Ryeland sheep breed (organism) | AnimalBreeds
132707000 | Thalli sheep breed (organism) | AnimalBreeds
132708005 | Tong sheep breed (organism) | AnimalBreeds
132709002 | Touabire sheep breed (organism) | AnimalBreeds
132710007 | Tunis sheep breed (organism) | AnimalBreeds

132711006 | Tyrol Mountain sheep breed (organism) | AnimalBreeds
132712004 | Uda sheep breed (organism) | AnimalBreeds
132713009 | Gray chicken breed (organism) | AnimalBreeds
132714003 | Hamburgs chicken breed (organism) | AnimalBreeds
132715002 | Gimmizah chicken breed (organism) | AnimalBreeds
132716001 | German Mutton Merino sheep breed (organism) | AnimalBreeds
132717005 | Medium-Wool Merino sheep breed (organism) | AnimalBreeds
132718000 | Fonthill Merino sheep breed (organism) | AnimalBreeds
132719008 | South African Mutton Merino sheep breed (organism) | AnimalBreeds
132720002 | Strong Wool Merino sheep breed (organism) | AnimalBreeds
132721003 | Poll Merino sheep breed (organism) | AnimalBreeds
132722005 | Fine Merino sheep breed (organism) | AnimalBreeds
132723000 | South African Merino sheep breed (organism) | AnimalBreeds
132724006 | Superfine Merino sheep breed (organism) | AnimalBreeds
132725007 | Dutch Bantam chicken breed (organism) | AnimalBreeds
132726008 | Silver Montazah chicken breed (organism) | AnimalBreeds
132727004 | Swiss Hen chicken breed (organism) | AnimalBreeds
132728009 | Styrian chicken breed (organism) | AnimalBreeds
132729001 | Old English Game chicken breed (organism) | AnimalBreeds
132730006 | Appenzell Bearded Hen chicken breed (organism) | AnimalBreeds
132731005 | Baden Wurttemburg horse breed (organism) | AnimalBreeds
132732003 | British Warmblood horse breed (organism) | AnimalBreeds
132733008 | Israeli horse breed (organism) | AnimalBreeds
132734002 | French Ardennais horse breed (organism) | AnimalBreeds
132735001 | Booroola Merino sheep breed (organism) | AnimalBreeds
132736000 | Cukurova horse breed (organism) | AnimalBreeds
132737009 | Czech Coldblood horse breed (organism) | AnimalBreeds
132738004 | Czechoslovakian Small Riding Horse horse breed (organism) | AnimalBreeds
132739007 | Jianchang horse breed (organism) | AnimalBreeds
132740009 | Jielin horse breed (organism) | AnimalBreeds
132741008 | Wielkopolski horse breed (organism) | AnimalBreeds
132742001 | Eleia horse breed (organism) | AnimalBreeds
132743006 | English Cob horse breed (organism) | AnimalBreeds
132744000 | Welsh Pony horse breed (organism) | AnimalBreeds
132745004 | Welsh Pony of Cob Type horse breed (organism) | AnimalBreeds
132746003 | English Hunter horse breed (organism) | AnimalBreeds
132747007 | Eriskay Pony horse breed (organism) | AnimalBreeds
132748002 | Hackney Pony horse breed (organism) | AnimalBreeds
132749005 | Estonian Draft horse breed (organism) | AnimalBreeds
132750005 | Heihe horse breed (organism) | AnimalBreeds
132751009 | Heilongkaing horse breed (organism) | AnimalBreeds
132752002 | Sulmtaler chicken breed (organism) | AnimalBreeds
132753007 | Svart Höna chicken breed (organism) | AnimalBreeds
132754001 | Vorwerks chicken breed (organism) | AnimalBreeds
132755000 | Westfalische Totleger chicken breed (organism) | AnimalBreeds
132756004 | Yamato Gunkei chicken breed (organism) | AnimalBreeds
132757008 | Danish Sport Pony horse breed (organism) | AnimalBreeds
132758003 | Kabarda horse breed (organism) | AnimalBreeds
132759006 | Kalmyk horse breed (organism) | AnimalBreeds
132760001 | Mangalarga Marchador horse breed (organism) | AnimalBreeds
132761002 | Don horse breed (organism) | AnimalBreeds
132762009 | Manipuri horse breed (organism) | AnimalBreeds
132763004 | Swiss Warmblood horse breed (organism) | AnimalBreeds
132764005 | Tavda horse breed (organism) | AnimalBreeds
132765006 | East Bulgarian horse breed (organism) | AnimalBreeds
132766007 | East Friesian (Old Type) horse breed (organism) | AnimalBreeds
132767003 | East Friesian Warmblood (Modern Type) horse breed (organism) | AnimalBreeds
132768008 | Kakhetian pig breed (organism) | AnimalBreeds
132769000 | West French White pig breed (organism) | AnimalBreeds
132770004 | Miniature Hereford cattle breed (organism) | AnimalBreeds
132771000 | Jem-Jem Zebu cattle breed (organism) | AnimalBreeds
132772007 | Minusin horse breed (organism) | AnimalBreeds
132773002 | Morochuco horse breed (organism) | AnimalBreeds
132774008 | French Trotter horse breed (organism) | AnimalBreeds
132775009 | Furioso horse breed (organism) | AnimalBreeds
132776005 | Murghese horse breed (organism) | AnimalBreeds
132777001 | Mytilene horse breed (organism) | AnimalBreeds
132778006 | Namib Desert Horse horse breed (organism) | AnimalBreeds
132779003 | Danish Oldenborg horse breed (organism) | AnimalBreeds
132780000 | Volynsk cattle breed (organism) | AnimalBreeds
132781001 | Senepol cattle breed (organism) | AnimalBreeds
132782008 | Shilluk cattle breed (organism) | AnimalBreeds

132783003 | Sar Planina sheep breed (organism) | AnimalBreeds
132784009 | Santa Inês sheep breed (organism) | AnimalBreeds
132785005 | Sahel-type sheep breed (organism) | AnimalBreeds
132786006 | Rygja sheep breed (organism) | AnimalBreeds
132787002 | Rya sheep breed (organism) | AnimalBreeds
132788007 | Moghani sheep breed (organism) | AnimalBreeds
132789004 | Rouge de l'Quest sheep breed (organism) | AnimalBreeds
132790008 | Soay sheep breed (organism) | AnimalBreeds
132791007 | South Suffolk sheep breed (organism) | AnimalBreeds
132792000 | South Wales Mountain sheep breed (organism) | AnimalBreeds
132793005 | Spælsau sheep breed (organism) | AnimalBreeds
132794004 | Spiegel sheep breed (organism) | AnimalBreeds
132795003 | St. Croix sheep breed (organism) | AnimalBreeds
132796002 | Steigar sheep breed (organism) | AnimalBreeds
132797006 | Steinschaf sheep breed (organism) | AnimalBreeds
132798001 | Welsh Mountain sheep breed (organism) | AnimalBreeds
132799009 | Swedish Fur Sheep breed (organism) | AnimalBreeds
132800008 | Teeswater sheep breed (organism) | AnimalBreeds
132801007 | Texel sheep breed (organism) | AnimalBreeds
132802000 | Pelibüey sheep breed (organism) | AnimalBreeds
132803005 | Morada Nova sheep breed (organism) | AnimalBreeds
132804004 | Balkhi sheep breed (organism) | AnimalBreeds
132805003 | Bavarian Forest sheep breed (organism) | AnimalBreeds
132806002 | Barbados Blackbelly sheep breed (organism) | AnimalBreeds
132807006 | Romney sheep breed (organism) | AnimalBreeds
132808001 | Awassi sheep breed (organism) | AnimalBreeds
132809009 | Arapawa Island sheep breed (organism) | AnimalBreeds
132810004 | Arabi sheep breed (organism) | AnimalBreeds
132811000 | Apennine sheep breed (organism) | AnimalBreeds
132812007 | American Tunis sheep breed (organism) | AnimalBreeds
132813002 | Balwen Welsh Mountain sheep breed (organism) | AnimalBreeds
132814008 | Priangan sheep breed (organism) | AnimalBreeds
132815009 | Rabo Largo sheep breed (organism) | AnimalBreeds
132816005 | Frieslands chicken breed (organism) | AnimalBreeds
132817001 | Ameraucana chicken breed (organism) | AnimalBreeds
132818006 | Åsbos chicken breed (organism) | AnimalBreeds
132819003 | Augsburger chicken breed (organism) | AnimalBreeds
132820009 | Bielefelder chicken breed (organism) | AnimalBreeds
132821008 | Norfolk Gray chicken breed (organism) | AnimalBreeds
132822001 | Hedemora chicken breed (organism) | AnimalBreeds
132823006 | Hungarian Yellow chicken breed (organism) | AnimalBreeds
132824000 | Iowa blue chicken breed (organism) | AnimalBreeds
132825004 | Red jungle fowl type chicken (organism) | AnimalBreeds
132826003 | Ko Shamo chicken breed (organism) | AnimalBreeds
132827007 | Kraienkoppe chicken breed (organism) | AnimalBreeds
132828002 | Lincolnshire Buff chicken breed (organism) | AnimalBreeds
132829005 | Tomaru chicken breed (organism) | AnimalBreeds
132830000 | Onagadori chicken breed (organism) | AnimalBreeds
132831001 | Manx Rumpies chicken breed (organism) | AnimalBreeds
132832008 | Maline chicken breed (organism) | AnimalBreeds
132833003 | Nankin chicken breed (organism) | AnimalBreeds
132834009 | Øland chicken breed (organism) | AnimalBreeds
132835005 | Ölansk Bantam chicken breed (organism) | AnimalBreeds
132836006 | Orust chicken breed (organism) | AnimalBreeds
132837002 | Penedesenca chicken breed (organism) | AnimalBreeds
132838007 | Rhode Island White chicken breed (organism) | AnimalBreeds
132839004 | Rosecomb Bantam chicken breed (organism) | AnimalBreeds
132840002 | Sablepoot chicken breed (organism) | AnimalBreeds
132841003 | Saipan Jungle Fowl chicken breed (organism) | AnimalBreeds
132842005 | Scots Dumpy chicken breed (organism) | AnimalBreeds
132843000 | Muban pig breed (organism) | AnimalBreeds
132844006 | Iban pig breed (organism) | AnimalBreeds
132845007 | Altay sheep breed (organism) | AnimalBreeds
132846008 | Faeroes sheep breed (organism) | AnimalBreeds
132847004 | Green chicken breed (organism) | AnimalBreeds
132848009 | Gallus Inauris chicken breed (organism) | AnimalBreeds
132849001 | Pitt Island sheep breed (organism) | AnimalBreeds
132850001 | Golden Montazah chicken breed (organism) | AnimalBreeds
132851002 | Pinzirita sheep breed (organism) | AnimalBreeds
132852009 | Sardinian sheep breed (organism) | AnimalBreeds
132853004 | East Friesian sheep breed (organism) | AnimalBreeds
132854005 | Ujumqin sheep breed (organism) | AnimalBreeds

132855006 | DLS sheep breed (organism) | AnimalBreeds
132856007 | Walachenschaf sheep breed (organism) | AnimalBreeds
132857003 | Outaouais Arcott sheep breed (organism) | AnimalBreeds
132858008 | Ossimi sheep breed (organism) | AnimalBreeds
132859000 | Bentheimer Landschaf sheep breed (organism) | AnimalBreeds
132860005 | Barbado sheep breed (organism) | AnimalBreeds
132861009 | Baluchi sheep breed (organism) | AnimalBreeds
132862002 | Shamo chicken breed (organism) | AnimalBreeds
132950000 | mule | AnimalSpecies
132951001 | American Indian Horse horse breed (organism) | AnimalBreeds
132952008 | American Mustang horse breed (organism) | AnimalBreeds
132953003 | American Quarter Horse horse breed (organism) | AnimalBreeds
132954009 | American Shetland pony horse breed (organism) | AnimalBreeds
132955005 | Anadolu horse breed (organism) | AnimalBreeds
132956006 | Andean horse breed (organism) | AnimalBreeds
132957002 | Anglo-Kabarda horse breed (organism) | AnimalBreeds
132958007 | Poitou Donkey breed (organism) | AnimalBreeds
132959004 | Mammoth Jack Stock Donkey breed (organism) | AnimalBreeds
132960009 | Narym horse breed (organism) | AnimalBreeds
132961008 | National Spotted Saddle Horse horse breed (organism) | AnimalBreeds
132962001 | Nigerian horse breed (organism) | AnimalBreeds
132963006 | North Swedish Trotter horse breed (organism) | AnimalBreeds
132964000 | Oriental Horse horse breed (organism) | AnimalBreeds
132965004 | Rhineland Heavy Draft horse breed (organism) | AnimalBreeds
132966003 | Romanian Saddle Horse horse breed (organism) | AnimalBreeds
132967007 | Rottal horse breed (organism) | AnimalBreeds
132968002 | Royal Canadian Mounted Police Horse horse breed (organism) | AnimalBreeds
132969005 | Russian Saddle Horse horse breed (organism) | AnimalBreeds
132970006 | Sable Island Horse horse breed (organism) | AnimalBreeds
132971005 | Panje horse breed (organism) | AnimalBreeds
132972003 | Patibarcina horse breed (organism) | AnimalBreeds
132973008 | Pechora horse breed (organism) | AnimalBreeds
132974002 | Peneia horse breed (organism) | AnimalBreeds
132975001 | Periangan horse breed (organism) | AnimalBreeds
132976000 | Persian Arab horse breed (organism) | AnimalBreeds
132977009 | Petiso Argentino horse breed (organism) | AnimalBreeds
132978004 | Polish Draft horse breed (organism) | AnimalBreeds
132979007 | Priob horse breed (organism) | AnimalBreeds
132980005 | Rahvan horse breed (organism) | AnimalBreeds
132981009 | Salerno horse breed (organism) | AnimalBreeds
132982002 | Sandalwood horse breed (organism) | AnimalBreeds
132983007 | Sandan horse breed (organism) | AnimalBreeds
132984001 | Pindos horse breed (organism) | AnimalBreeds
132985000 | Piquira Pony horse breed (organism) | AnimalBreeds
132986004 | Pleven horse breed (organism) | AnimalBreeds
132987008 | Large standard donkey (organism) | AnimalBreeds
132988003 | Standard donkey (organism) | AnimalBreeds
132989006 | Miniature donkey (organism) | AnimalBreeds
132990002 | Garrano tarpan horse X domestic horse breed (organism) | AnimalBreeds
132991003 | Konink tarpan horse X domestic horse breed (organism) | AnimalBreeds
132992005 | Asturian tarpan horse X domestic horse breed (organism) | AnimalBreeds
132993000 | Pottok tarpan horse X domestic horse breed (organism) | AnimalBreeds
132994006 | Russian Trotter horse breed (organism) | AnimalBreeds
132995007 | West African Barb horse breed (organism) | AnimalBreeds
132996008 | Fell Pony horse breed (organism) | AnimalBreeds
132997004 | National Show Horse horse breed (organism) | AnimalBreeds
132998009 | Zhemaichu horse breed (organism) | AnimalBreeds
132999001 | Yonaguni horse breed (organism) | AnimalBreeds
133000000 | Yakut horse breed (organism) | AnimalBreeds
133001001 | Tawleed horse breed (organism) | AnimalBreeds
133002008 | Western Sudan Pony horse breed (organism) | AnimalBreeds
133003003 | Welera Pony horse breed (organism) | AnimalBreeds
133004009 | Vyatka horse breed (organism) | AnimalBreeds
133005005 | Vladimir Heavy Draft horse breed (organism) | AnimalBreeds
133006006 | Vlaamperd horse breed (organism) | AnimalBreeds
133007002 | Ukrainian Saddle Horse horse breed (organism) | AnimalBreeds
133008007 | Tori horse breed (organism) | AnimalBreeds
133009004 | Tokara horse breed (organism) | AnimalBreeds
133010009 | New Kirgiz horse breed (organism) | AnimalBreeds
133011008 | Oldenburg horse breed (organism) | AnimalBreeds
133012001 | Misaki horse breed (organism) | AnimalBreeds
133013006 | Miyako horse breed (organism) | AnimalBreeds

133014000 | Mongolian horse breed (organism) | AnimalBreeds
133015004 | Waler horse breed (organism) | AnimalBreeds
133016003 | Dutch Draft horse breed (organism) | AnimalBreeds
133017007 | Egyptian horse breed (organism) | AnimalBreeds
133018002 | Estonian Native horse breed (organism) | AnimalBreeds
133019005 | Exmoor Pony horse breed (organism) | AnimalBreeds
133020004 | Faeroes Island Horse horse breed (organism) | AnimalBreeds
133021000 | Falabella horse breed (organism) | AnimalBreeds
133022007 | Dutch Warmblood horse breed (organism) | AnimalBreeds
133023002 | Dongola horse breed (organism) | AnimalBreeds
133024008 | Døle horse breed (organism) | AnimalBreeds
133025009 | Djerma horse breed (organism) | AnimalBreeds
133026005 | Deliboz horse breed (organism) | AnimalBreeds
133027001 | Dartmoor Pony horse breed (organism) | AnimalBreeds
133028006 | Crioulo horse breed (organism) | AnimalBreeds
133029003 | Finnhorse horse breed (organism) | AnimalBreeds
133030008 | Sanfratello horse breed (organism) | AnimalBreeds
133031007 | Morab horse breed (organism) | AnimalBreeds
133032000 | Moyle horse breed (organism) | AnimalBreeds
133033005 | Mustang horse breed (organism) | AnimalBreeds
133034004 | M'Bayar horse breed (organism) | AnimalBreeds
133035003 | Lusitano horse breed (organism) | AnimalBreeds
133036002 | Newfoundland Pony horse breed (organism) | AnimalBreeds
133037006 | Noma horse breed (organism) | AnimalBreeds
133038001 | Nooitgedacht Pony horse breed (organism) | AnimalBreeds
133039009 | Nordland horse breed (organism) | AnimalBreeds
133040006 | Noric horse breed (organism) | AnimalBreeds
133041005 | North Swedish Horse horse breed (organism) | AnimalBreeds
133042003 | Northeastern horse breed (organism) | AnimalBreeds
133043008 | Kisber Felver horse breed (organism) | AnimalBreeds
133044002 | Anglo-Arab horse breed (organism) | AnimalBreeds
133045001 | Nonius horse breed (organism) | AnimalBreeds
133046000 | Nooitgedacht horse breed (organism) | AnimalBreeds
133047009 | Iomud horse breed (organism) | AnimalBreeds
133048004 | Jutland horse breed (organism) | AnimalBreeds
133049007 | Karabair horse breed (organism) | AnimalBreeds
133050007 | Karabakh horse breed (organism) | AnimalBreeds
133051006 | Kazakh horse breed (organism) | AnimalBreeds
133052004 | Mangalarga horse breed (organism) | AnimalBreeds
133053009 | Kirdi Pony horse breed (organism) | AnimalBreeds
133054003 | Kiso horse breed (organism) | AnimalBreeds
133055002 | Kladruby horse breed (organism) | AnimalBreeds
133056001 | Knabstrup horse breed (organism) | AnimalBreeds
133057005 | Kushum horse breed (organism) | AnimalBreeds
133058000 | Kustanai horse breed (organism) | AnimalBreeds
133059008 | Latvian horse breed (organism) | AnimalBreeds
133060003 | Lithuanian Heavy Draft horse breed (organism) | AnimalBreeds
133061004 | Lokai horse breed (organism) | AnimalBreeds
133062006 | Kiger Mustang horse breed (organism) | AnimalBreeds
133063001 | Pony of the Americas horse breed (organism) | AnimalBreeds
133064007 | Pintabian horse breed (organism) | AnimalBreeds
133065008 | Pantaneiro horse breed (organism) | AnimalBreeds
133066009 | Orlov Trotter horse breed (organism) | AnimalBreeds
133067000 | Northern Ardennais horse breed (organism) | AnimalBreeds
133068005 | Abtenauer horse breed (organism) | AnimalBreeds
133069002 | Adaev horse breed (organism) | AnimalBreeds
133070001 | Albanian horse breed (organism) | AnimalBreeds
133071002 | Alter Real horse breed (organism) | AnimalBreeds
133072009 | American Bashkir Curly horse breed (organism) | AnimalBreeds
133073004 | Poitou Mule Producer horse breed (organism) | AnimalBreeds
133074005 | Polesian horse breed (organism) | AnimalBreeds
133075006 | Sardinian Anglo-Arab horse breed (organism) | AnimalBreeds
133076007 | Sardinian Pony horse breed (organism) | AnimalBreeds
133077003 | Sarvar horse breed (organism) | AnimalBreeds
133078008 | Schleswig horse breed (organism) | AnimalBreeds
133079000 | Schwarzwalder Fuchse horse breed (organism) | AnimalBreeds
133080002 | Senne horse breed (organism) | AnimalBreeds
133081003 | Shan horse breed (organism) | AnimalBreeds
133082005 | Silesian horse breed (organism) | AnimalBreeds
133083000 | Sini horse breed (organism) | AnimalBreeds
133084006 | Skyros horse breed (organism) | AnimalBreeds
133085007 | Slovak Warmblood horse breed (organism) | AnimalBreeds

133086008 | Sokolka horse breed (organism) | AnimalBreeds
133087004 | South African Miniature horse breed (organism) | AnimalBreeds
133088009 | South German Coldblood horse breed (organism) | AnimalBreeds
133089001 | Southwest Spanish Mustang horse breed (organism) | AnimalBreeds
133090005 | Spanish-American Horse horse breed (organism) | AnimalBreeds
133091009 | Spanish Anglo-Arab horse breed (organism) | AnimalBreeds
133092002 | Spanish Colonial Horse horse breed (organism) | AnimalBreeds
133093007 | Spiti horse breed (organism) | AnimalBreeds
133094001 | Sulawesi horse breed (organism) | AnimalBreeds
133095000 | Criollo horse breed (organism) | AnimalBreeds
133096004 | Hequ horse breed (organism) | AnimalBreeds
133097008 | Connemara Pony horse breed (organism) | AnimalBreeds
133098003 | Colorado Ranger horse breed (organism) | AnimalBreeds
133099006 | Dales Pony horse breed (organism) | AnimalBreeds
133100003 | Gotland horse breed (organism) | AnimalBreeds
133101004 | Chincoteague Pony horse breed (organism) | AnimalBreeds
133102006 | Hokkaido horse breed (organism) | AnimalBreeds
133103001 | Highland Pony horse breed (organism) | AnimalBreeds
133104007 | Groningen horse breed (organism) | AnimalBreeds
133105008 | Cuban Pinto horse breed (organism) | AnimalBreeds
133106009 | Fleuve horse breed (organism) | AnimalBreeds
133107000 | Golden American Saddlebred horse breed (organism) | AnimalBreeds
133108005 | Gidran horse breed (organism) | AnimalBreeds
133109002 | Gelderland horse breed (organism) | AnimalBreeds
133110007 | Galician Pony horse breed (organism) | AnimalBreeds
133111006 | Friesian horse breed (organism) | AnimalBreeds
133112004 | Frederiksborg horse breed (organism) | AnimalBreeds
133113009 | Fouta horse breed (organism) | AnimalBreeds
133114003 | Florida Cracker horse breed (organism) | AnimalBreeds
133115002 | Guangxi horse breed (organism) | AnimalBreeds
133116001 | Ardennes horse breed (organism) | AnimalBreeds
133117005 | American Walking Pony horse breed (organism) | AnimalBreeds
133118000 | Azteca horse breed (organism) | AnimalBreeds
133119008 | American Cream Draft horse breed (organism) | AnimalBreeds
133120002 | Altai horse breed (organism) | AnimalBreeds
133121003 | Akhal-Teke horse breed (organism) | AnimalBreeds
133122005 | Abyssinian horse breed (organism) | AnimalBreeds
133123000 | Bhirum Pony horse breed (organism) | AnimalBreeds
133124006 | Cheju horse breed (organism) | AnimalBreeds
133125007 | Cayuse horse breed (organism) | AnimalBreeds
133126008 | Caspian horse breed (organism) | AnimalBreeds
133127004 | Carthusian horse breed (organism) | AnimalBreeds
133128009 | Campolina horse breed (organism) | AnimalBreeds
133129001 | Byelorussian Harness horse breed (organism) | AnimalBreeds
133130006 | Budyonny horse breed (organism) | AnimalBreeds
133131005 | Australian Brumby horse breed (organism) | AnimalBreeds
133132003 | Australian Stock Horse horse breed (organism) | AnimalBreeds
133133008 | Basuto Pony horse breed (organism) | AnimalBreeds
133134002 | Bashkir Curly horse breed (organism) | AnimalBreeds
133135001 | Bashkir horse breed (organism) | AnimalBreeds
133136000 | Barb horse breed (organism) | AnimalBreeds
133137009 | Ban-ei horse breed (organism) | AnimalBreeds
133138004 | Carpathian Pony horse breed (organism) | AnimalBreeds
133139007 | Baluchi horse breed (organism) | AnimalBreeds
133140009 | Balearic horse breed (organism) | AnimalBreeds
133141008 | Chilean Corralero horse breed (organism) | AnimalBreeds
133142001 | Breton horse breed (organism) | AnimalBreeds
133143006 | Taishuh horse breed (organism) | AnimalBreeds
133144000 | Swedish Warmblood horse breed (organism) | AnimalBreeds
133145004 | Sudan Country-Bred horse breed (organism) | AnimalBreeds
133146003 | Spanish-Norman horse breed (organism) | AnimalBreeds
133147007 | Spanish Barb horse breed (organism) | AnimalBreeds
133148002 | Soviet Heavy Draft horse breed (organism) | AnimalBreeds
133149005 | Sorraia horse breed (organism) | AnimalBreeds
133150005 | Somali Pony horse breed (organism) | AnimalBreeds
133151009 | Tersk horse breed (organism) | AnimalBreeds
133152002 | Shagya horse breed (organism) | AnimalBreeds
133153007 | Selle Francais horse breed (organism) | AnimalBreeds
133154001 | Sanhe horse breed (organism) | AnimalBreeds
133155000 | Russian Heavy Draft horse breed (organism) | AnimalBreeds
133156004 | Rocky Mountain Horse horse breed (organism) | AnimalBreeds
133157008 | Racking Horse horse breed (organism) | AnimalBreeds

133158003 | Quarter Pony horse breed (organism) | AnimalBreeds
133159006 | Quarab horse breed (organism) | AnimalBreeds
133160001 | Single-Footing Horse horse breed (organism) | AnimalBreeds
133161002 | Tuy Hoa Hairless pig breed (organism) | AnimalBreeds
133162009 | Hainan pig breed (organism) | AnimalBreeds
133163004 | Sino-Vietnamese pig breed (organism) | AnimalBreeds
133164005 | Bo Xu pig breed (organism) | AnimalBreeds
133165006 | Thuoc Nhieu pig breed (organism) | AnimalBreeds
133166007 | Burmese pig breed (organism) | AnimalBreeds
133167003 | Chin pig breed (organism) | AnimalBreeds
133168008 | Siamese pig breed (organism) | AnimalBreeds
133169000 | Hailum pig breed (organism) | AnimalBreeds
133170004 | Kwai pig breed (organism) | AnimalBreeds
133171000 | Raad pig breed (organism) | AnimalBreeds
133172007 | Akha pig breed (organism) | AnimalBreeds
133173002 | South China pig breed (organism) | AnimalBreeds
133174008 | South China Black pig breed (organism) | AnimalBreeds
133175009 | Balinese pig breed (organism) | AnimalBreeds
133176005 | Diani pig breed (organism) | AnimalBreeds
133177001 | Kaman pig breed (organism) | AnimalBreeds
133178006 | Ashanti Dwarf pig breed (organism) | AnimalBreeds
133179003 | Koronadal pig breed (organism) | AnimalBreeds
133180000 | Ohmini pig breed (organism) | AnimalBreeds
133181001 | Clawn pig breed (organism) | AnimalBreeds
133182008 | Sus scrofa domestic pig X Japanese wild boar intragenus hybrid (organism) | AnimalBreeds
133183003 | Kangaroo Island pig breed (organism) | AnimalBreeds
133184009 | Captain Cooker pig breed (organism) | AnimalBreeds
133185005 | West African pig breed (organism) | AnimalBreeds
133186006 | Nigerian pig breed (organism) | AnimalBreeds
133187002 | Bakosi pig breed (organism) | AnimalBreeds
133188007 | Windsnyer pig breed (organism) | AnimalBreeds
133189004 | Kolbroek pig breed (organism) | AnimalBreeds
133190008 | South African Landrace pig breed (organism) | AnimalBreeds
133191007 | Bulgarian White pig breed (organism) | AnimalBreeds
133192000 | Bulgarian Landrace pig breed (organism) | AnimalBreeds
133193005 | Danube White pig breed (organism) | AnimalBreeds
133194004 | Dermantsi Pied pig breed (organism) | AnimalBreeds
133195003 | Romanian Native, Stocli pig breed (organism) | AnimalBreeds
133196002 | Romanian Native, Baltaret pig breed (organism) | AnimalBreeds
133197006 | Banat White pig breed (organism) | AnimalBreeds
133198001 | Bazna pig breed (organism) | AnimalBreeds
133199009 | Dobrogea Black pig breed (organism) | AnimalBreeds
133200007 | Strei pig breed (organism) | AnimalBreeds
133201006 | Romanian Large White pig breed (organism) | AnimalBreeds
133202004 | Romanian Meat Pig pig breed (organism) | AnimalBreeds
133203009 | Gurktal pig breed (organism) | AnimalBreeds
133204003 | Black Slavonian pig breed (organism) | AnimalBreeds
133205002 | Resava pig breed (organism) | AnimalBreeds
133206001 | Morava pig breed (organism) | AnimalBreeds
133207005 | Dzumalia pig breed (organism) | AnimalBreeds
133208000 | Macedonian pig breed (organism) | AnimalBreeds
133209008 | Albanian Native pig breed (organism) | AnimalBreeds
133210003 | Shkodra pig breed (organism) | AnimalBreeds
133211004 | Slovenian White pig breed (organism) | AnimalBreeds
133212006 | Subotica White pig breed (organism) | AnimalBreeds
133213001 | Prestice pig breed (organism) | AnimalBreeds
133214007 | Slovakian Black Pied pig breed (organism) | AnimalBreeds
133215008 | Czech Improved White pig breed (organism) | AnimalBreeds
133216009 | Moravian Large Yorkshire pig breed (organism) | AnimalBreeds
133217000 | Slovakian White pig breed (organism) | AnimalBreeds
133218005 | Slovhyb-1 pig breed (organism) | AnimalBreeds
133219002 | Nitra Hybrid pig breed (organism) | AnimalBreeds
133220008 | Synthetic SL98 pig breed (organism) | AnimalBreeds
133221007 | SL96 pig breed (organism) | AnimalBreeds
133222000 | Czech Meat pig breed (organism) | AnimalBreeds
133223005 | Czech Miniature pig breed (organism) | AnimalBreeds
133224004 | Small Polish Prick-Eared pig breed (organism) | AnimalBreeds
133225003 | Polesian pig breed (organism) | AnimalBreeds
133226002 | Nadbuzanska pig breed (organism) | AnimalBreeds
133227006 | Sarny pig breed (organism) | AnimalBreeds
133228001 | Krolevets pig breed (organism) | AnimalBreeds
133229009 | Polish Marsh pig breed (organism) | AnimalBreeds

133230004 | Large Polish Long-Eared pig breed (organism) | AnimalBreeds
133231000 | Herens cattle breed (organism) | AnimalBreeds
133232007 | Hinterwald cattle breed (organism) | AnimalBreeds
133233002 | Hungarian Gray cattle breed (organism) | AnimalBreeds
133234008 | Icelandic cattle breed (organism) | AnimalBreeds
133235009 | Illawarra cattle breed (organism) | AnimalBreeds
133236005 | Irish Moiled cattle breed (organism) | AnimalBreeds
133237001 | Israeli Holstein cattle breed (organism) | AnimalBreeds
133238006 | Istoben cattle breed (organism) | AnimalBreeds
133239003 | Jaulan cattle breed (organism) | AnimalBreeds
133240001 | Kazakh cattle breed (organism) | AnimalBreeds
133241002 | Kerry cattle breed (organism) | AnimalBreeds
133242009 | Kholmogory cattle breed (organism) | AnimalBreeds
133243004 | Latvian Brown cattle breed (organism) | AnimalBreeds
133244005 | Lincoln Red Shorthorn cattle breed (organism) | AnimalBreeds
133245006 | Lithuanian Red cattle breed (organism) | AnimalBreeds
133246007 | Mashona cattle breed (organism) | AnimalBreeds
133247003 | Milking Devon cattle breed (organism) | AnimalBreeds
133248008 | Mirandesa cattle breed (organism) | AnimalBreeds
133249000 | Mixed dairy cattle breed (organism) | AnimalBreeds
133250000 | Mongolian cattle breed (organism) | AnimalBreeds
133251001 | Morucha cattle breed (organism) | AnimalBreeds
133252008 | Kurdi cattle breed (organism) | AnimalBreeds
133253003 | N'dama cattle breed (organism) | AnimalBreeds
133254009 | Norwegian Red cattle breed (organism) | AnimalBreeds
133255005 | Parthenais cattle breed (organism) | AnimalBreeds
133256006 | Polish Red cattle breed (organism) | AnimalBreeds
133257002 | Rätien Gray cattle breed (organism) | AnimalBreeds
133258007 | Red and White cattle breed (organism) | AnimalBreeds
133259004 | Red Angus cattle breed (organism) | AnimalBreeds
133260009 | Red Polled Østland cattle breed (organism) | AnimalBreeds
133261008 | Red Steppe cattle breed (organism) | AnimalBreeds
133262001 | Reggiana cattle breed (organism) | AnimalBreeds
133263006 | Retinta cattle breed (organism) | AnimalBreeds
133264000 | Romosinuano cattle breed (organism) | AnimalBreeds
133265004 | Russian Black Pied cattle breed (organism) | AnimalBreeds
133266003 | RX3 cattle breed (organism) | AnimalBreeds
133267007 | Salorn cattle breed (organism) | AnimalBreeds
133268002 | Murboden cattle breed (organism) | AnimalBreeds
133269005 | San Martinero cattle breed (organism) | AnimalBreeds
133270006 | Sarabi cattle breed (organism) | AnimalBreeds
133271005 | Sharabi cattle breed (organism) | AnimalBreeds
133272003 | Shetland cattle breed (organism) | AnimalBreeds
133273008 | Simbrah cattle breed (organism) | AnimalBreeds
133274002 | South Devon cattle breed (organism) | AnimalBreeds
133275001 | Suffolk cattle breed (organism) | AnimalBreeds
133276000 | Sussex cattle breed (organism) | AnimalBreeds
133277009 | Swedish Red Polled cattle breed (organism) | AnimalBreeds
133278004 | Telemark cattle breed (organism) | AnimalBreeds
133279007 | Texas Longhorn cattle breed (organism) | AnimalBreeds
133280005 | Texon cattle breed (organism) | AnimalBreeds
133281009 | Vestland Fjord cattle breed (organism) | AnimalBreeds
133282002 | Vestland Red Polled cattle breed (organism) | AnimalBreeds
133283007 | Wagyu cattle breed (organism) | AnimalBreeds
133284001 | White Cáceres cattle breed (organism) | AnimalBreeds
133285000 | Xinjiang Brown cattle breed (organism) | AnimalBreeds
133286004 | Yanbian cattle breed (organism) | AnimalBreeds
133287008 | Zaobei cattle breed (organism) | AnimalBreeds
133288003 | Zavot cattle breed (organism) | AnimalBreeds
133289006 | Znamensk cattle breed (organism) | AnimalBreeds
133290002 | Alistana-Sanabresa cattle breed (organism) | AnimalBreeds
133291003 | Andalusian Blond cattle breed (organism) | AnimalBreeds
133292005 | Aosta Black Pied cattle breed (organism) | AnimalBreeds
133293000 | Aosta Chestnut cattle breed (organism) | AnimalBreeds
133294006 | Aosta Red Pied cattle breed (organism) | AnimalBreeds
133295007 | Aracena cattle breed (organism) | AnimalBreeds
133296008 | Argentine Friesian cattle breed (organism) | AnimalBreeds
133297004 | Armorican cattle breed (organism) | AnimalBreeds
133298009 | Arouquesa cattle breed (organism) | AnimalBreeds
133299001 | Aure et Saint-Girons cattle breed (organism) | AnimalBreeds
133300009 | Australian White cattle breed (organism) | AnimalBreeds
133301008 | Austrian Simmental cattle breed (organism) | AnimalBreeds

133302001 | Austrian Yellow cattle breed (organism) | AnimalBreeds
133303006 | Avetonou cattle breed (organism) | AnimalBreeds
133304000 | Avilena cattle breed (organism) | AnimalBreeds
133305004 | Avilena-Black Iberian cattle breed (organism) | AnimalBreeds
133306003 | Bakosi cattle breed (organism) | AnimalBreeds
133307007 | Bakwiri cattle breed (organism) | AnimalBreeds
133308002 | Baltic Black Pied cattle breed (organism) | AnimalBreeds
133309005 | Baoule cattle breed (organism) | AnimalBreeds
133310000 | Barrosa cattle breed (organism) | AnimalBreeds
133311001 | Barroso cattle breed (organism) | AnimalBreeds
133312008 | Bearnais cattle breed (organism) | AnimalBreeds
133313003 | Beef shorthorn cattle breed (organism) | AnimalBreeds
133314009 | Beef synthetic cattle breed (organism) | AnimalBreeds
133315005 | Beijing Black Pied cattle breed (organism) | AnimalBreeds
133316006 | Beiroa cattle breed (organism) | AnimalBreeds
133317002 | Belgian Black Pied Holsteincattle breed (organism) | AnimalBreeds
133318007 | Belgian Red Pied cattle breed (organism) | AnimalBreeds
133319004 | Belgian White and Red cattle breed (organism) | AnimalBreeds
133320005 | Belted Welsh cattle breed (organism) | AnimalBreeds
133321009 | Bestuzhev cattle breed (organism) | AnimalBreeds
133322002 | Betizuak cattle breed (organism) | AnimalBreeds
133323007 | Black Baldy cattle breed (organism) | AnimalBreeds
133324001 | Black Forest cattle breed (organism) | AnimalBreeds
133325000 | Black Iberian cattle breed (organism) | AnimalBreeds
133326004 | Northern Blue cattle breed (organism) | AnimalBreeds
133327008 | Bragado do Sorraia cattle breed (organism) | AnimalBreeds
133328003 | Braganca cattle breed (organism) | AnimalBreeds
133329006 | Brandrood ljsselvee cattle breed (organism) | AnimalBreeds
133330001 | Brazilian Polled cattle breed (organism) | AnimalBreeds
133331002 | Breton Black Pied cattle breed (organism) | AnimalBreeds
133332009 | Brown Atlas cattle breed (organism) | AnimalBreeds
133333004 | Bulgarian Brown cattle breed (organism) | AnimalBreeds
133334005 | Bulgarian Red cattle breed (organism) | AnimalBreeds
133335006 | Burlina cattle breed (organism) | AnimalBreeds
133336007 | Burwash cattle breed (organism) | AnimalBreeds
133337003 | Byelorussian Red cattle breed (organism) | AnimalBreeds
133338008 | Byelorussian Synthetic cattle breed (organism) | AnimalBreeds
133339000 | Cabannina cattle breed (organism) | AnimalBreeds
133340003 | Caldeano cattle breed (organism) | AnimalBreeds
133341004 | Caldelana cattle breed (organism) | AnimalBreeds
133342006 | Calvana cattle breed (organism) | AnimalBreeds
133343001 | Camargue cattle breed (organism) | AnimalBreeds
133344007 | Cambodian cattle breed (organism) | AnimalBreeds
133345008 | Caracu cattle breed (organism) | AnimalBreeds
133346009 | Carpathian Brown cattle breed (organism) | AnimalBreeds
133347000 | Casanareno cattle breed (organism) | AnimalBreeds
133348005 | Central Russian Black Pied cattle breed (organism) | AnimalBreeds
133349002 | Chaouia cattle breed (organism) | AnimalBreeds
133350002 | Charollandais cattle breed (organism) | AnimalBreeds
133351003 | Char-swiss cattle breed (organism) | AnimalBreeds
133352005 | Korean Black cattle breed (organism) | AnimalBreeds
133353000 | Chesi cattle breed (organism) | AnimalBreeds
133354006 | Cheurfa cattle breed (organism) | AnimalBreeds
133355007 | Chiford cattle breed (organism) | AnimalBreeds
133356008 | Chimaine cattle breed (organism) | AnimalBreeds
133357004 | Chinampo cattle breed (organism) | AnimalBreeds
133358009 | Cildir cattle breed (organism) | AnimalBreeds
133359001 | COOPELSO 93 cattle breed (organism) | AnimalBreeds
133360006 | Thrace cattle breed (organism) | AnimalBreeds
133361005 | Corsican cattle breed (organism) | AnimalBreeds
133362003 | Cretan Lowland cattle breed (organism) | AnimalBreeds
133363008 | Cretan Mountain cattle breed (organism) | AnimalBreeds
133364002 | Croatian Red cattle breed (organism) | AnimalBreeds
133365001 | Cukurova cattle breed (organism) | AnimalBreeds
133366000 | Curraleiro cattle breed (organism) | AnimalBreeds
133367009 | Cyprus cattle breed (organism) | AnimalBreeds
133368004 | Czech Pied cattle breed (organism) | AnimalBreeds
133369007 | Dagestan Mountain cattle breed (organism) | AnimalBreeds
133370008 | Dairy Shorthorn cattle breed (organism) | AnimalBreeds
133371007 | Dairy Synthetic cattle breed (organism) | AnimalBreeds
133372000 | Danish Red Pied cattle breed (organism) | AnimalBreeds
133373005 | Dengchuan cattle breed (organism) | AnimalBreeds

133374004 | Dexter-Kerry cattle breed (organism) | AnimalBreeds
133375003 | Doran cattle breed (organism) | AnimalBreeds
133376002 | Dorna cattle breed (organism) | AnimalBreeds
133377006 | Dortyol cattle breed (organism) | AnimalBreeds
133378001 | East Anatolian Red cattle breed (organism) | AnimalBreeds
133379009 | East Finnish cattle breed (organism) | AnimalBreeds
133380007 | East Macedonian cattle breed (organism) | AnimalBreeds
133381006 | Epirus cattle breed (organism) | AnimalBreeds
133382004 | Estonian Black Pied cattle breed (organism) | AnimalBreeds
133383009 | Ferrandais cattle breed (organism) | AnimalBreeds
133384003 | Finnish Ayrshire cattle breed (organism) | AnimalBreeds
133385002 | Flemish cattle breed (organism) | AnimalBreeds
133386001 | Red Flemish cattle breed (organism) | AnimalBreeds
133387005 | Fort Cross cattle breed (organism) | AnimalBreeds
133388000 | Frati cattle breed (organism) | AnimalBreeds
133389008 | Estonian Native cattle breed (organism) | AnimalBreeds
133390004 | Faeroes cattle breed (organism) | AnimalBreeds
133391000 | French Brown cattle breed (organism) | AnimalBreeds
133392007 | Frijolillo cattle breed (organism) | AnimalBreeds
133393002 | FRS cattle breed (organism) | AnimalBreeds
133394008 | Gacko cattle breed (organism) | AnimalBreeds
133395009 | Gado da Terra cattle breed (organism) | AnimalBreeds
133396005 | Georgian Mountain cattle breed (organism) | AnimalBreeds
133397001 | German Black Pied cattle breed (organism) | AnimalBreeds
133398006 | German Black Pied Dairy cattle breed (organism) | AnimalBreeds
133399003 | Pechora cattle breed (organism) | AnimalBreeds
133400005 | Pee Wee cattle breed (organism) | AnimalBreeds
133401009 | Peloponnesus cattle breed (organism) | AnimalBreeds
133402002 | Pester cattle breed (organism) | AnimalBreeds
133403007 | Pie Rouge de l'Est cattle breed (organism) | AnimalBreeds
133404001 | Pisana cattle breed (organism) | AnimalBreeds
133405000 | German Brown cattle breed (organism) | AnimalBreeds
133406004 | German Shorthorn cattle breed (organism) | AnimalBreeds
133407008 | Ghana Shorthorn cattle breed (organism) | AnimalBreeds
133408003 | Glan-Donnersberg cattle breed (organism) | AnimalBreeds
133409006 | Gole cattle breed (organism) | AnimalBreeds
133410001 | Golpayegani cattle breed (organism) | AnimalBreeds
133411002 | Gorbatov Red cattle breed (organism) | AnimalBreeds
133412009 | Goryn cattle breed (organism) | AnimalBreeds
133413004 | Greater Caucasus cattle breed (organism) | AnimalBreeds
133414005 | Polish Black and White Lowland cattle breed (organism) | AnimalBreeds
133415006 | Polish Simmental cattle breed (organism) | AnimalBreeds
133416007 | Polled Jersey cattle breed (organism) | AnimalBreeds
133417003 | Polled Lincoln Red cattle breed (organism) | AnimalBreeds
133418008 | Polled Shorthorn (United States of America) cattle breed (organism) | AnimalBreeds
133419000 | Polled Simmental cattle breed (organism) | AnimalBreeds
133420006 | Greek Shorthorn cattle breed (organism) | AnimalBreeds
133421005 | Greek Steppe cattle breed (organism) | AnimalBreeds
133422003 | Gray Alpine cattle breed (organism) | AnimalBreeds
133423008 | Guadiana Spotted cattle breed (organism) | AnimalBreeds
133424002 | Guelma cattle breed (organism) | AnimalBreeds
133425001 | Harz Red cattle breed (organism) | AnimalBreeds
133426000 | Hawaiian wild cattle breed (organism) | AnimalBreeds
133427009 | Hereland cattle breed (organism) | AnimalBreeds
133428004 | Holgus cattle breed (organism) | AnimalBreeds
133429007 | Hrbinecky cattle breed (organism) | AnimalBreeds
133430002 | Polled Sussex cattle breed (organism) | AnimalBreeds
133431003 | Polled Welsh Black cattle breed (organism) | AnimalBreeds
133432005 | Pontremolese cattle breed (organism) | AnimalBreeds
133433000 | Preta cattle breed (organism) | AnimalBreeds
133434006 | Puerto Rican Criollo cattle breed (organism) | AnimalBreeds
133435007 | Pyrenean cattle breed (organism) | AnimalBreeds
133436008 | Huertana cattle breed (organism) | AnimalBreeds
133437004 | Hungarian Pied cattle breed (organism) | AnimalBreeds
133438009 | Hungarofries cattle breed (organism) | AnimalBreeds
133439001 | Improved Rodopi cattle breed (organism) | AnimalBreeds
133440004 | INRA 95 cattle breed (organism) | AnimalBreeds
133441000 | Italian Brown cattle breed (organism) | AnimalBreeds
133442007 | Italian Red Pied cattle breed (organism) | AnimalBreeds
133443002 | Japanese Black cattle breed (organism) | AnimalBreeds
133444008 | Japanese Brown cattle breed (organism) | AnimalBreeds
133445009 | Japanese Poll cattle breed (organism) | AnimalBreeds

133446005 | Qinchuan cattle breed (organism) | AnimalBreeds
133447001 | Ramo Grande cattle breed (organism) | AnimalBreeds
133448006 | Randall Lineback cattle breed (organism) | AnimalBreeds
133449003 | Red Galloway cattle breed (organism) | AnimalBreeds
133450003 | Regus cattle breed (organism) | AnimalBreeds
133451004 | Rendena cattle breed (organism) | AnimalBreeds
133452006 | Japanese Shorthorn cattle breed (organism) | AnimalBreeds
133453001 | Jarmelista cattle breed (organism) | AnimalBreeds
133454007 | Kabyle cattle breed (organism) | AnimalBreeds
133455008 | Kapsiki cattle breed (organism) | AnimalBreeds
133456009 | Katerini cattle breed (organism) | AnimalBreeds
133457000 | Kenran cattle breed (organism) | AnimalBreeds
133458005 | Khevsurian cattle breed (organism) | AnimalBreeds
133459002 | Kilis cattle breed (organism) | AnimalBreeds
133460007 | Kochi cattle breed (organism) | AnimalBreeds
133461006 | Korean Native cattle breed (organism) | AnimalBreeds
133462004 | Rhaetian Gray cattle breed (organism) | AnimalBreeds
133463009 | Rio Limon Dairy Criollo cattle breed (organism) | AnimalBreeds
133464003 | Rodopi cattle breed (organism) | AnimalBreeds
133465002 | Romanian Red cattle breed (organism) | AnimalBreeds
133466001 | Romanian Brown cattle breed (organism) | AnimalBreeds
133467005 | Russian Brown cattle breed (organism) | AnimalBreeds
133468000 | Kostroma cattle breed (organism) | AnimalBreeds
133469008 | Kravarsky cattle breed (organism) | AnimalBreeds
133470009 | Kuchinoshima cattle breed (organism) | AnimalBreeds
133471008 | Murray Gray cattle breed (organism) | AnimalBreeds
133472001 | Australian Shorthorn cattle breed (organism) | AnimalBreeds
133473006 | Kumamoto cattle breed (organism) | AnimalBreeds
133474000 | Lagune cattle breed (organism) | AnimalBreeds
133475004 | Lakenvelder cattle breed (organism) | AnimalBreeds
133476003 | Latvian Blue Roan cattle breed (organism) | AnimalBreeds
133477007 | La Velasquez cattle breed (organism) | AnimalBreeds
133478002 | Sardinian cattle breed (organism) | AnimalBreeds
133479005 | Sardinian brown cattle breed (organism) | AnimalBreeds
133480008 | Savinja Gray cattle breed (organism) | AnimalBreeds
133481007 | Sayaguesa cattle breed (organism) | AnimalBreeds
133482000 | Seferihisar cattle breed (organism) | AnimalBreeds
133483005 | Shkodra Red cattle breed (organism) | AnimalBreeds
133484004 | Lebanese cattle breed (organism) | AnimalBreeds
133485003 | Lebedin cattle breed (organism) | AnimalBreeds
133486002 | Lesser Caucasus cattle breed (organism) | AnimalBreeds
133487006 | Liberian Dwarf cattle breed (organism) | AnimalBreeds
133488001 | Libyan cattle breed (organism) | AnimalBreeds
133489009 | Lim cattle breed (organism) | AnimalBreeds
133490000 | Limiana cattle breed (organism) | AnimalBreeds
133491001 | Limpurger cattle breed (organism) | AnimalBreeds
133492008 | Lobi cattle breed (organism) | AnimalBreeds
133493003 | Lourdais cattle breed (organism) | AnimalBreeds
133494009 | Slovakian Pied cattle breed (organism) | AnimalBreeds
133495005 | Slovakian Pinzgau cattle breed (organism) | AnimalBreeds
133496006 | Slovenian Brown cattle breed (organism) | AnimalBreeds
133497002 | Somba cattle breed (organism) | AnimalBreeds
133498007 | South African Brown Swiss cattle breed (organism) | AnimalBreeds
133499004 | South Anatolian Red cattle breed (organism) | AnimalBreeds
133500008 | Lucerna cattle breed (organism) | AnimalBreeds
133501007 | Luxi cattle breed (organism) | AnimalBreeds
133502000 | Macedonian Busa cattle breed (organism) | AnimalBreeds
133503005 | Makaweli cattle breed (organism) | AnimalBreeds
133504004 | Marinhoa cattle breed (organism) | AnimalBreeds
133505003 | Maronesa cattle breed (organism) | AnimalBreeds
133506002 | Mazury cattle breed (organism) | AnimalBreeds
133507006 | Messaoria cattle breed (organism) | AnimalBreeds
133508001 | Metohija Red cattle breed (organism) | AnimalBreeds
133509009 | Mingrelian Red cattle breed (organism) | AnimalBreeds
133510004 | Southern Ukrainian cattle breed (organism) | AnimalBreeds
133511000 | Spanish Brown Alpine cattle breed (organism) | AnimalBreeds
133512007 | Suksun cattle breed (organism) | AnimalBreeds
133513002 | Swiss Black Pied cattle breed (organism) | AnimalBreeds
133514008 | Sychevka cattle breed (organism) | AnimalBreeds
133515009 | Sykia cattle breed (organism) | AnimalBreeds
133516005 | Minhota cattle breed (organism) | AnimalBreeds
133517001 | Minorcan cattle breed (organism) | AnimalBreeds

133518006 | Mishima cattle breed (organism) | AnimalBreeds
133519003 | Modenese cattle breed (organism) | AnimalBreeds
133520009 | Monchina cattle breed (organism) | AnimalBreeds
133521008 | Montafon cattle breed (organism) | AnimalBreeds
133522001 | Montbeliard cattle breed (organism) | AnimalBreeds
133523006 | Morenas del Noroeste cattle breed (organism) | AnimalBreeds
133524000 | Murcian cattle breed (organism) | AnimalBreeds
133525004 | Murnau-Werdenfels cattle breed (organism) | AnimalBreeds
133526003 | Tagil cattle breed (organism) | AnimalBreeds
133527007 | Tajma cattle breed (organism) | AnimalBreeds
133528002 | Tambov Red cattle breed (organism) | AnimalBreeds
133529005 | Tarina cattle breed (organism) | AnimalBreeds
133530000 | Thessaly cattle breed (organism) | AnimalBreeds
133531001 | Tinima cattle breed (organism) | AnimalBreeds
133532008 | Nantais cattle breed (organism) | AnimalBreeds
133533003 | Nejdi cattle breed (organism) | AnimalBreeds
133534009 | N'Gabou cattle breed (organism) | AnimalBreeds
133535005 | North Finncattle cattle breed (organism) | AnimalBreeds
133536006 | Oropa cattle breed (organism) | AnimalBreeds
133537002 | Oulmes Blond cattle breed (organism) | AnimalBreeds
133538007 | Pajuna cattle breed (organism) | AnimalBreeds
133539004 | Palmera cattle breed (organism) | AnimalBreeds
133540002 | Pankota Red cattle breed (organism) | AnimalBreeds
133541003 | Paphos cattle breed (organism) | AnimalBreeds
133542005 | Tinos cattle breed (organism) | AnimalBreeds
133543000 | Transylvanian Pinzgau cattle breed (organism) | AnimalBreeds
133544006 | Tropical Dairy Cattle cattle breed (organism) | AnimalBreeds
133545007 | Tropicana cattle breed (organism) | AnimalBreeds
133546008 | Tudanca cattle breed (organism) | AnimalBreeds
133547004 | Turino cattle breed (organism) | AnimalBreeds
133548009 | Turkish Brown cattle breed (organism) | AnimalBreeds
133549001 | Tux-Zillertal cattle breed (organism) | AnimalBreeds
133550001 | Tyrol Gray cattle breed (organism) | AnimalBreeds
133551002 | Abondance cattle breed (organism) | AnimalBreeds
133552009 | Ala-Tau cattle breed (organism) | AnimalBreeds
133553004 | Albanian Illyrian cattle breed (organism) | AnimalBreeds
133554005 | Albanian Dwarf cattle breed (organism) | AnimalBreeds
133555006 | Ukrainian Whiteheaded cattle breed (organism) | AnimalBreeds
133556007 | Ural Black Pied cattle breed (organism) | AnimalBreeds
133557003 | Valdres cattle breed (organism) | AnimalBreeds
133558008 | Vaynol cattle breed (organism) | AnimalBreeds
133559000 | Verinesa cattle breed (organism) | AnimalBreeds
133560005 | Vianesa cattle breed (organism) | AnimalBreeds
133561009 | Villard-de-Lans cattle breed (organism) | AnimalBreeds
133562002 | Vogelsberg cattle breed (organism) | AnimalBreeds
133563007 | Pie Rouge des Plaines cattle breed (organism) | AnimalBreeds
133564001 | Vorderwald cattle breed (organism) | AnimalBreeds
133565000 | West African Dwarf Shorthorn cattle breed (organism) | AnimalBreeds
133566004 | West Finnish cattle breed (organism) | AnimalBreeds
133567008 | West Macedonian cattle breed (organism) | AnimalBreeds
133568003 | Whitebred Shorthorn cattle breed (organism) | AnimalBreeds
133569006 | White Galloway cattle breed (organism) | AnimalBreeds
133570007 | White Welsh cattle breed (organism) | AnimalBreeds
133571006 | Witrik cattle breed (organism) | AnimalBreeds
133572004 | Yacumento cattle breed (organism) | AnimalBreeds
133573009 | Yaroslavl cattle breed (organism) | AnimalBreeds
133574003 | Yurino cattle breed (organism) | AnimalBreeds
133575002 | Aleppo cattle breed (organism) | AnimalBreeds
133576001 | Schwyz cattle breed (organism) | AnimalBreeds
133577005 | Busa cattle breed (organism) | AnimalBreeds
133578000 | Chiangus cattle breed (organism) | AnimalBreeds
133579008 | Hallingdal cattle breed (organism) | AnimalBreeds
133580006 | Danish Jersey cattle breed (organism) | AnimalBreeds
133581005 | Enderby Island cattle breed (organism) | AnimalBreeds
133582003 | German Angus cattle breed (organism) | AnimalBreeds
133583008 | Israeli Red cattle breed (organism) | AnimalBreeds
133584002 | Lineback cattle breed (organism) | AnimalBreeds
133585001 | Mertolenga cattle breed (organism) | AnimalBreeds
133586000 | Red Friesian cattle breed (organism) | AnimalBreeds
133587009 | Senegus cattle breed (organism) | AnimalBreeds
133588004 | Southern Crioulo cattle breed (organism) | AnimalBreeds
133589007 | Vosges cattle breed (organism) | AnimalBreeds

133590003 | Montanara cattle breed (organism) | AnimalBreeds
133591004 | Almanzorena cattle breed (organism) | AnimalBreeds
133592006 | Lorquina cattle breed (organism) | AnimalBreeds
133593001 | Calasparrena cattle breed (organism) | AnimalBreeds
133594007 | Amritmahal cattle breed (organism) | AnimalBreeds
133595008 | Bachaur cattle breed (organism) | AnimalBreeds
133596009 | Barka cattle breed (organism) | AnimalBreeds
133597000 | Bengali cattle breed (organism) | AnimalBreeds
133598005 | Bhagnari cattle breed (organism) | AnimalBreeds
133599002 | Boran cattle breed (organism) | AnimalBreeds
133600004 | Channi cattle breed (organism) | AnimalBreeds
133601000 | Cholistani cattle breed (organism) | AnimalBreeds
133602007 | Dajal cattle breed (organism) | AnimalBreeds
133603002 | Dangi cattle breed (organism) | AnimalBreeds
133604008 | Deoni cattle breed (organism) | AnimalBreeds
133605009 | Dhanni cattle breed (organism) | AnimalBreeds
133606005 | Gaolao cattle breed (organism) | AnimalBreeds
133607001 | Hallikar cattle breed (organism) | AnimalBreeds
133608006 | Hariana cattle breed (organism) | AnimalBreeds
133609003 | Indo-Brazilian cattle breed (organism) | AnimalBreeds
133610008 | Kangayam cattle breed (organism) | AnimalBreeds
133611007 | Kankrej cattle breed (organism) | AnimalBreeds
133612000 | Kenkatha cattle breed (organism) | AnimalBreeds
133613005 | Kherigarh cattle breed (organism) | AnimalBreeds
133614004 | Khillari cattle breed (organism) | AnimalBreeds
133615003 | Krishna Valley cattle breed (organism) | AnimalBreeds
133616002 | Lohani cattle breed (organism) | AnimalBreeds
133617006 | Malvi cattle breed (organism) | AnimalBreeds
133618001 | Mewati cattle breed (organism) | AnimalBreeds
133619009 | Nagori cattle breed (organism) | AnimalBreeds
133620003 | Nelore cattle breed (organism) | AnimalBreeds
133621004 | Nimari cattle breed (organism) | AnimalBreeds
133622006 | Ponwar cattle breed (organism) | AnimalBreeds
133623001 | Rath cattle breed (organism) | AnimalBreeds
133624007 | Rathi cattle breed (organism) | AnimalBreeds
133625008 | Red Sindhi cattle breed (organism) | AnimalBreeds
133626009 | Rojhan cattle breed (organism) | AnimalBreeds
133627000 | Sahiwal cattle breed (organism) | AnimalBreeds
133628005 | Siri zebu cattle breed (organism) | AnimalBreeds
133629002 | Tharparkar cattle breed (organism) | AnimalBreeds
133630007 | Zanzibar Zebu cattle breed (organism) | AnimalBreeds
133631006 | Arsi cattle breed (organism) | AnimalBreeds
133632004 | Atpadi Mahal cattle breed (organism) | AnimalBreeds
133633009 | Azaouak cattle breed (organism) | AnimalBreeds
133634003 | Azerbaijan Zebu cattle breed (organism) | AnimalBreeds
133635002 | Baggara cattle breed (organism) | AnimalBreeds
133636001 | Bambawa cattle breed (organism) | AnimalBreeds
133637005 | Bami cattle breed (organism) | AnimalBreeds
133638000 | Banyo cattle breed (organism) | AnimalBreeds
133639008 | Bargur cattle breed (organism) | AnimalBreeds
133640005 | Bari cattle breed (organism) | AnimalBreeds
133641009 | Bimal cattle breed (organism) | AnimalBreeds
133642002 | Borneo Zebu cattle breed (organism) | AnimalBreeds
133643007 | Butana cattle breed (organism) | AnimalBreeds
133644001 | Chittagong Red cattle breed (organism) | AnimalBreeds
133645000 | Cutchi cattle breed (organism) | AnimalBreeds
133646004 | Dairy Zebu of Uberaba cattle breed (organism) | AnimalBreeds
133647008 | Dashtiari cattle breed (organism) | AnimalBreeds
133648003 | Diali cattle breed (organism) | AnimalBreeds
133649006 | Didinga cattle breed (organism) | AnimalBreeds
133650006 | Dongola cattle breed (organism) | AnimalBreeds
133651005 | Fellata cattle breed (organism) | AnimalBreeds
133652003 | Turkmen zebu cattle breed (organism) | AnimalBreeds
133653008 | Abyssinian Highland Zebu cattle breed (organism) | AnimalBreeds
133654002 | Abyssinian Shorthorned Zebu cattle breed (organism) | AnimalBreeds
133655001 | Aceh cattle breed (organism) | AnimalBreeds
133656000 | Achham cattle breed (organism) | AnimalBreeds
133657009 | Garre cattle breed (organism) | AnimalBreeds
133658004 | Gasara cattle breed (organism) | AnimalBreeds
133659007 | Gobra cattle breed (organism) | AnimalBreeds
133660002 | Goomsur cattle breed (organism) | AnimalBreeds
133661003 | Gujamavu cattle breed (organism) | AnimalBreeds

133662005 | Leiqiong cattle breed (organism) | AnimalBreeds
133663000 | Hissar cattle breed (organism) | AnimalBreeds
133664006 | Ingessana cattle breed (organism) | AnimalBreeds
133665007 | Jamaica Brahman cattle breed (organism) | AnimalBreeds
133666008 | Jellicut cattle breed (organism) | AnimalBreeds
133667004 | Adamawa cattle breed (organism) | AnimalBreeds
133668009 | Aden Zebu cattle breed (organism) | AnimalBreeds
133669001 | Afghan cattle breed (organism) | AnimalBreeds
133670000 | Alambadi cattle breed (organism) | AnimalBreeds
133671001 | Umblachery cattle breed (organism) | AnimalBreeds
133672008 | Venezuelan Zebu cattle breed (organism) | AnimalBreeds
133673003 | Pantaneiro cattle breed (organism) | AnimalBreeds
133674009 | Jenubi cattle breed (organism) | AnimalBreeds
133675005 | Jiddu cattle breed (organism) | AnimalBreeds
133676006 | Jijjiga Zebu cattle breed (organism) | AnimalBreeds
133677002 | Kabota cattle breed (organism) | AnimalBreeds
133678007 | Kachcha Siri cattle breed (organism) | AnimalBreeds
133679004 | Kalakheri cattle breed (organism) | AnimalBreeds
133680001 | Kamdhino cattle breed (organism) | AnimalBreeds
133681002 | Kandahari cattle breed (organism) | AnimalBreeds
133682009 | Kaningan cattle breed (organism) | AnimalBreeds
133683004 | Wakwa cattle breed (organism) | AnimalBreeds
133684005 | White Fulani cattle breed (organism) | AnimalBreeds
133685006 | Yemeni Zebu cattle breed (organism) | AnimalBreeds
133686007 | Iranian Zebu cattle breed (organism) | AnimalBreeds
133687003 | Khorsan cattle breed (organism) | AnimalBreeds
133688008 | Polled Gir cattle breed (organism) | AnimalBreeds
133689000 | Kappiliyan cattle breed (organism) | AnimalBreeds
133690009 | Karamajong cattle breed (organism) | AnimalBreeds
133691008 | Kenana cattle breed (organism) | AnimalBreeds
133692001 | Kenya Boran cattle breed (organism) | AnimalBreeds
133693006 | Kenya Zebu cattle breed (organism) | AnimalBreeds
133694000 | Khamala cattle breed (organism) | AnimalBreeds
133695004 | Khurasani zebu cattle breed (organism) | AnimalBreeds
133696003 | Kilara cattle breed (organism) | AnimalBreeds
133697007 | Kinniya cattle breed (organism) | AnimalBreeds
133698002 | Konari cattle breed (organism) | AnimalBreeds
133699005 | Guzerat cattle breed (organism) | AnimalBreeds
133700006 | Tadzhik zebu cattle breed (organism) | AnimalBreeds
133701005 | Deogir cattle breed (organism) | AnimalBreeds
133702003 | Gayal cattle breed (organism) | AnimalBreeds
133703008 | American bison X cattle breed (organism) | AnimalBreeds
133704002 | Australian Braford cattle breed (organism) | AnimalBreeds
133705001 | Krishnagari cattle breed (organism) | AnimalBreeds
133706000 | Kumauni cattle breed (organism) | AnimalBreeds
133707009 | Ladakhi cattle breed (organism) | AnimalBreeds
133708004 | Latuka cattle breed (organism) | AnimalBreeds
133709007 | Lugware cattle breed (organism) | AnimalBreeds
133710002 | Madagascar Zebu cattle breed (organism) | AnimalBreeds
133711003 | Madaripur cattle breed (organism) | AnimalBreeds
133712005 | Magal cattle breed (organism) | AnimalBreeds
133713000 | Malawi Zebu cattle breed (organism) | AnimalBreeds
133714006 | Malnad Gidda cattle breed (organism) | AnimalBreeds
133715007 | Australian Friesian Sahiwal cattle breed (organism) | AnimalBreeds
133716008 | Braford cattle breed (organism) | AnimalBreeds
133717004 | Brahmousin cattle breed (organism) | AnimalBreeds
133718009 | Canchim cattle breed (organism) | AnimalBreeds
133719001 | Charbray cattle breed (organism) | AnimalBreeds
133720007 | Droughtmaster cattle breed (organism) | AnimalBreeds
133721006 | Mampati cattle breed (organism) | AnimalBreeds
133722004 | Manapari cattle breed (organism) | AnimalBreeds
133723009 | Maure cattle breed (organism) | AnimalBreeds
133724003 | Mazandarani cattle breed (organism) | AnimalBreeds
133725002 | Merauke cattle breed (organism) | AnimalBreeds
133727005 | Mhaswad cattle breed (organism) | AnimalBreeds
133728000 | Miniature Zebu cattle breed (organism) | AnimalBreeds
133729008 | Mongalla cattle breed (organism) | AnimalBreeds
133730003 | Morang cattle breed (organism) | AnimalBreeds
133731004 | Gelbray cattle breed (organism) | AnimalBreeds
133732006 | Jamaica Black cattle breed (organism) | AnimalBreeds
133733001 | Jamaica Hope cattle breed (organism) | AnimalBreeds
133734007 | Jamaica Red cattle breed (organism) | AnimalBreeds

133735008 | Karan Fries cattle breed (organism) | AnimalBreeds
133736009 | Karan Swiss cattle breed (organism) | AnimalBreeds
133737000 | Mozambique Angoni cattle breed (organism) | AnimalBreeds
133738005 | Mpwapwa cattle breed (organism) | AnimalBreeds
133739002 | Murle cattle breed (organism) | AnimalBreeds
133740000 | Nakali cattle breed (organism) | AnimalBreeds
133741001 | Nepalese Hill Zebu cattle breed (organism) | AnimalBreeds
133742008 | N'Gaoundere cattle breed (organism) | AnimalBreeds
133743003 | Nkedi cattle breed (organism) | AnimalBreeds
133744009 | North Bangladesh Gray cattle breed (organism) | AnimalBreeds
133745005 | North Somali Zebu cattle breed (organism) | AnimalBreeds
133746006 | Polled Guzerat cattle breed (organism) | AnimalBreeds
133747002 | Mandalong cattle breed (organism) | AnimalBreeds
133748007 | Australian Milking Zebu cattle breed (organism) | AnimalBreeds
133749004 | Red Brangus cattle breed (organism) | AnimalBreeds
133750004 | Santa Cruz cattle breed (organism) | AnimalBreeds
133751000 | Siboney cattle breed (organism) | AnimalBreeds
133752007 | Bambara cattle breed (organism) | AnimalBreeds
133753002 | Polled Nelore cattle breed (organism) | AnimalBreeds
133754008 | Prewakwa cattle breed (organism) | AnimalBreeds
133755009 | Pul-M'bor cattle breed (organism) | AnimalBreeds
133756005 | Punganur cattle breed (organism) | AnimalBreeds
133757001 | Ramgarhi cattle breed (organism) | AnimalBreeds
133758006 | Red Bororo cattle breed (organism) | AnimalBreeds
133759003 | Red Desert cattle breed (organism) | AnimalBreeds
133760008 | Red Kandhari cattle breed (organism) | AnimalBreeds
133761007 | Shakhansurri cattle breed (organism) | AnimalBreeds
133762000 | Sheko cattle breed (organism) | AnimalBreeds
133763005 | Bambey cattle breed (organism) | AnimalBreeds
133764004 | Batanes Black cattle breed (organism) | AnimalBreeds
133765003 | Borgou cattle breed (organism) | AnimalBreeds
133766002 | Brahorn cattle breed (organism) | AnimalBreeds
133767006 | Bralers cattle breed (organism) | AnimalBreeds
133768001 | Bra-Maine cattle breed (organism) | AnimalBreeds
133769009 | Shendi cattle breed (organism) | AnimalBreeds
133770005 | Shuwa cattle breed (organism) | AnimalBreeds
133771009 | Sinhala cattle breed (organism) | AnimalBreeds
133772002 | Sistani cattle breed (organism) | AnimalBreeds
133773007 | Small East African Zebu cattle breed (organism) | AnimalBreeds
133774001 | Sokoto Gudali cattle breed (organism) | AnimalBreeds
133775000 | Somali cattle breed (organism) | AnimalBreeds
133776004 | Sonkheri cattle breed (organism) | AnimalBreeds
133777008 | Son Valley cattle breed (organism) | AnimalBreeds
133778003 | South China Zebu cattle breed (organism) | AnimalBreeds
133779006 | Bra-Swiss cattle breed (organism) | AnimalBreeds
133780009 | Bravon cattle breed (organism) | AnimalBreeds
133781008 | Brazilian Dairy hybrid cattle (organism) | AnimalBreeds
133782001 | Burmese cattle breed (organism) | AnimalBreeds
133783006 | Bushuev cattle breed (organism) | AnimalBreeds
133784000 | Caiua cattle breed (organism) | AnimalBreeds
133785004 | South Malawi Zebu cattle breed (organism) | AnimalBreeds
133786003 | Sudanese Fulani cattle breed (organism) | AnimalBreeds
133787007 | Tabapua cattle breed (organism) | AnimalBreeds
133788002 | Tamankaduwa cattle breed (organism) | AnimalBreeds
133789005 | Tanzanian Zebu cattle breed (organism) | AnimalBreeds
133790001 | Tarai cattle breed (organism) | AnimalBreeds
133791002 | Thillari cattle breed (organism) | AnimalBreeds
133792009 | Toposa cattle breed (organism) | AnimalBreeds
133793004 | Toronke cattle breed (organism) | AnimalBreeds
133794005 | Toupouri cattle breed (organism) | AnimalBreeds
133795006 | Carazebu cattle breed (organism) | AnimalBreeds
133796007 | Central Asian Zebu cattle breed (organism) | AnimalBreeds
133797003 | Charford cattle breed (organism) | AnimalBreeds
133798008 | Cuban Criollo cattle breed (organism) | AnimalBreeds
133799000 | Cuban Zebu cattle breed (organism) | AnimalBreeds
133800001 | Dishty cattle breed (organism) | AnimalBreeds
133801002 | Djakore cattle breed (organism) | AnimalBreeds
133802009 | Gambian N'Dama cattle breed (organism) | AnimalBreeds
133803004 | Ghana Sanga cattle breed (organism) | AnimalBreeds
133804005 | Girolando cattle breed (organism) | AnimalBreeds
133805006 | Guzerando cattle breed (organism) | AnimalBreeds
133806007 | Hatton cattle breed (organism) | AnimalBreeds

133807003 | Ibage cattle breed (organism) | AnimalBreeds
133808008 | Iraqi cattle breed (organism) | AnimalBreeds
133809000 | Jerdi cattle breed (organism) | AnimalBreeds
133810005 | Jersind cattle breed (organism) | AnimalBreeds
133811009 | Jotko cattle breed (organism) | AnimalBreeds
133812002 | Kanem cattle breed (organism) | AnimalBreeds
133813007 | Keteku cattle breed (organism) | AnimalBreeds
133814001 | Lavinia cattle breed (organism) | AnimalBreeds
133815000 | Local Indian Dairy cattle breed (organism) | AnimalBreeds
133816004 | Mantiqueira cattle breed (organism) | AnimalBreeds
133817008 | Ndagu cattle breed (organism) | AnimalBreeds
133818003 | Normanzu cattle breed (organism) | AnimalBreeds
133819006 | Nuba Mountain cattle breed (organism) | AnimalBreeds
133820000 | Pabna cattle breed (organism) | AnimalBreeds
133821001 | Mixed Perijanero cattle breed (organism) | AnimalBreeds
133822008 | Pitangueiras cattle breed (organism) | AnimalBreeds
133823003 | Quasah cattle breed (organism) | AnimalBreeds
133824009 | Rana cattle (organism) | AnimalBreeds
133825005 | Ranger cattle (organism) | AnimalBreeds
133826006 | Renitelo cattle breed (organism) | AnimalBreeds
133827002 | Riopardenze cattle breed (organism) | AnimalBreeds
133828007 | Rustaqi cattle breed (organism) | AnimalBreeds
133829004 | Sabre cattle breed (organism) | AnimalBreeds
133830009 | Sahford cattle breed (organism) | AnimalBreeds
133831008 | Schwyz-Zeboid cattle breed (organism) | AnimalBreeds
133832001 | Suia cattle breed (organism) | AnimalBreeds
133833006 | Suisbu cattle breed (organism) | AnimalBreeds
133834000 | Sunandini cattle breed (organism) | AnimalBreeds
133835004 | Taino cattle breed (organism) | AnimalBreeds
133836003 | Thibar cattle breed (organism) | AnimalBreeds
133837007 | Toubou cattle breed (organism) | AnimalBreeds
133838002 | Tropical cattle breed (organism) | AnimalBreeds
133839005 | TSSH-1 cattle breed (organism) | AnimalBreeds
133840007 | Victoria cattle breed (organism) | AnimalBreeds
133841006 | Wokalup cattle breed (organism) | AnimalBreeds
133842004 | Madura cattle breed (organism) | AnimalBreeds
13487004 | Shire horse (organism) | AnimalBreeds
13544004 | Belted Galloway cattle breed (organism) | AnimalBreeds
13934009 | Panama sheep (organism) | AnimalBreeds
14063001 | FHC elite pig 9 (organism) | AnimalBreeds
14189004 | Measles | Vaccination Protocol Dose Target Codes
14866005 | Hospital outpatient mental health center | Facility Type Code Value Set
15443006 | Yuca pig (organism) | AnimalBreeds
15778005 | goose | AnimalSpecies
15961007 | British saddleback pig (organism) | AnimalBreeds
16015002 | Anglo nubian goat (organism) | AnimalBreeds
160237006 | History/symptoms | Investigation Type
160245001 | No current problems or disability | Condition/Problem/Diagnosis Codes
16042001 | Beefmaster cattle breed (organism) | AnimalBreeds
16404004 | Induced | FHIR Specimen Collection Method
17717005 | Pic Cambourgh pig (organism) | AnimalBreeds
1773006 | Free-standing radiology facility | Facility Type Code Value Set
1789009 | Trakehner horse (organism) | AnimalBreeds
1814000 | Hospital outpatient geriatric health center | Facility Type Code Value Set
18212001 | Boar power pig 72 (organism) | AnimalBreeds
182922004 | Dietary regime | Diet Codes
18299006 | Orpington chicken (organism) | AnimalBreeds
183932001 | Procedure contraindicated | Procedure Not Performed Reason (SNOMED-CT)
183944003 | Procedure refused | Procedure Not Performed Reason (SNOMED-CT)
1857005 | Gestational rubella syndrome | Vaccination Protocol Dose Target Codes
18949003 | Change of dressing | Procedure Follow up Codes (SNOMED CT)
190753003 | Sucrose intolerance | AllergyIntolerance Substance/Product, Condition and Negation Codes
19356005 | Hunter horse (organism) | AnimalBreeds
19602009 | Fee-for-service private physicians' group office | Facility Type Code Value Set
19770007 | Hereford pig (organism) | AnimalBreeds
20044005 | Pietrain pig (organism) | AnimalBreeds
20078004 | Substance abuse treatment center | Facility Type Code Value Set
20255002 | Blushing | FHIR Specimen Collection Method
20280002 | Hampshire pig (organism) | AnimalBreeds
2034000 | White turkey (organism) | AnimalBreeds
20657003 | Meleagris gallopavo (organism) | AnimalBreeds
2081004 | Hospital ship | Facility Type Code Value Set

21021000 | Large black pig (organism) | AnimalBreeds
21208000 | Saanen goat (organism) | AnimalBreeds
2124007 | Rambouillet sheep (organism) | AnimalBreeds
21295007 | Morgan horse (organism) | AnimalBreeds
21553004 | Luing cattle breed (organism) | AnimalBreeds
21921002 | Canadian cattle breed (organism) | AnimalBreeds
22330003 | Commercial white egg layer type chicken (organism) | AnimalBreeds
223366009 | Healthcare professional | Procedure Performer Role Codes
224687002 | Hospital-prison | Facility Type Code Value Set
22506004 | British lop pig (organism) | AnimalBreeds
225164002 | Removal of ligature | Procedure Follow up Codes (SNOMED CT)
2253004 | Marans chicken (organism) | AnimalBreeds
22549003 | Hospital outpatient gynecology clinic | Facility Type Code Value Set
225732001 | Hospital-community | Facility Type Code Value Set
226355009 | Nutrients | Nutrient Modifier Codes
226529007 | Starchy food | Texture Modified Food Type Codes
226760005 | Dairy foods | Texture Modified Food Type Codes
226887002 | Dietary Fats and Oils | Texture Modified Food Type Codes
22720009 | Belgian horse (organism) | AnimalBreeds
227210005 | Vegetables plus herbs and spices | Texture Modified Food Type Codes
227415002 | Fruit Nuts and Seeds | Texture Modified Food Type Codes
227518002 | Sauce seasonings and soups | Texture Modified Food Type Codes
228049004 | Chopped food | Texture Modifier Codes
228053002 | Cut-up food | Texture Modifier Codes
228055009 | Liquidized food | Texture Modifier Codes
228056005 | Lumpy food | Texture Modifier Codes
228057001 | Semi-solid food | Texture Modifier Codes
228058006 | Single texture food | Texture Modifier Codes
228059003 | Soft food | Texture Modifier Codes
228060008 | Solid food | Texture Modifier Codes
22836000 | Vegetables | Texture Modified Food Type Codes
229506003 | Scar tissue massage | Procedure Follow up Codes (SNOMED CT)
2333000 | Japanese chicken (organism) | AnimalBreeds
23392004 | Hospital outpatient otorhinolaryngology clinic | Facility Type Code Value Set
23469003 | Domestic goose (organism) | AnimalBreeds
23629009 | Hays converter cattle breed (organism) | AnimalBreeds
23992007 | Black-winged bronze turkey (organism) | AnimalBreeds
241031001 | Removal of drain | Procedure Follow up Codes (SNOMED CT)
24111007 | FHC elite pig 3 (organism) | AnimalBreeds
242990004 | Drug not available for administration | SNOMED CT Reason Medication Not Given Codes
24319000 | Boar power pig 414 (organism) | AnimalBreeds
24438005 | Pekin duck (organism) | AnimalBreeds
24484000 | Severe | Condition/Diagnosis Severity
24642003 | Psychiatry procedure or service | Procedure Category Codes (SNOMED CT)
248152002 | Female | Observation Reference Range Applies To Codes
248153007 | Male | Observation Reference Range Applies To Codes
24840008 | CPF pig (organism) | AnimalBreeds
24886005 | Penna palm turkey (organism) | AnimalBreeds
25327001 | Dorset sheep superbreed (organism) | AnimalBreeds
25369002 | Westphalian horse (organism) | AnimalBreeds
255551008 | Posterior | Bodysite Location Qualifier
255561001 | Medial | Bodysite Location Qualifier
255604002 | Mild | Condition/Diagnosis Severity
255620007 | Foods | Texture Modified Food Type Codes
25660007 | Barbados sheep (organism) | AnimalBreeds
25681007 | Sexually transmitted disease health center | Facility Type Code Value Set
25813002 | Holsteiner horse (organism) | AnimalBreeds
258431006 | Scrapings | FHIR Specimen Collection Method
25854005 | Small white turkey (organism) | AnimalBreeds
25856007 | Boar power pig 929 (organism) | AnimalBreeds
260419006 | Projection | Media Collection View/Projection
260787004 | Physical object | SNOMED CT Supply Item
26105007 | Holstein-Friesian cattle breed (organism) | AnimalBreeds
261089000 | Inferior | Bodysite Location Qualifier
261122009 | Lower | Bodysite Location Qualifier
261183002 | Upper | Bodysite Location Qualifier
264217000 | Superior | Bodysite Location Qualifier
264331002 | Grain | Texture Modified Food Type Codes
26525003 | White Park cattle breed (organism) | AnimalBreeds
266710000 | Drugs not taken/completed | SNOMED CT Drugs not taken/completed Codes
26699009 | New Forest pony (organism) | AnimalBreeds
267425008 | Lactose intolerance | AllergyIntolerance Substance/Product, Condition and Negation Codes

26837006 | American cream horse (organism) | AnimalBreeds
26973000 | American trotter horse (organism) | AnimalBreeds
271336007 | Examination / signs | Investigation Type
272394005 | Technique | Observation Methods
272501009 | Sports facility | Facility Type Code Value Set
273384008 | Consumer satisfaction questionnaire | Questionnaire Category Codes
273479001 | General health questionnaire | Questionnaire Category Codes
273601006 | Mental status questionnaire | Questionnaire Category Codes
273820006 | Social support questionnaire | Questionnaire Category Codes
274441001 | Suction drainage | Procedure Follow up Codes (SNOMED CT)
275576008 | Elderly assessment clinic | Facility Type Code Value Set
27836007 | Pertussis | Vaccination Protocol Dose Target Codes
278448002 | Care plan | Care Plan Category
278450005 | Finger stick | FHIR Specimen Collection Method
28138009 | Slate turkey (organism) | AnimalBreeds
281657000 | Travel vaccinations | Immunization Reason Codes
28336001 | Brangus cattle breed (organism) | AnimalBreeds
28360002 | Swiss alpine goat (organism) | AnimalBreeds
284009009 | Route of administration values | SNOMED CT Route Codes
284546000 | Hospice facility | Facility Type Code Value Set
28483003 | Simmental cattle breed (organism) | AnimalBreeds
2849009 | Hospital outpatient infectious disease clinic | Facility Type Code Value Set
28647000 | Meat | Texture Modified Food Type Codes
28744004 | Black Welsh cattle breed (organism) | AnimalBreeds
29223008 | Boar power pig 565 (organism) | AnimalBreeds
29235007 | Pic line pig 26 (organism) | AnimalBreeds
29240004 | Autopsy examination | FHIR Specimen Collection Method
29546006 | Faverolle chicken (organism) | AnimalBreeds
29615001 | La Fleche chicken (organism) | AnimalBreeds
29736007 | Syndrome of carbohydrate intolerance | AllergyIntolerance Substance/Product, Condition and Negation Codes
29881002 | Connor prairie pig (organism) | AnimalBreeds
30089001 | Toggenburg goat (organism) | AnimalBreeds
30221007 | Belgian bearded chicken (organism) | AnimalBreeds
30384003 | Brahma cattle breed (organism) | AnimalBreeds
30432005 | Broad breasted bronze turkey (organism) | AnimalBreeds
30448006 | Lacombe pig (organism) | AnimalBreeds
304784009 | Administrative form | Questionnaire Category Codes
30549001 | Removal of suture | Procedure Follow up Codes (SNOMED CT)
30634003 | Tamworth pig (organism) | AnimalBreeds
30720007 | Boar power pig 84 (organism) | AnimalBreeds
308283009 | Discharge from hospital | GoalStartEvent
309898008 | Psychogeriatric day hospital | Facility Type Code Value Set
309900005 | Care of the elderly day hospital | Facility Type Code Value Set
3099004 | Romney marsh sheep (organism) | AnimalBreeds
310205006 | Private residential home | Facility Type Code Value Set
310376006 | Immunization consent not given | Immunization Reasons for Not Immunizing Codes
31628002 | Hospital outpatient family medicine clinic | Facility Type Code Value Set
31633003 | Yorkshire coach horse (organism) | AnimalBreeds
32074000 | Hospital-long term care | Facility Type Code Value Set
32145006 | Romanov sheep (organism) | AnimalBreeds
3216001 | Lincoln red cattle breed (organism) | AnimalBreeds
32297006 | Boar power pig 48 (organism) | AnimalBreeds
32485007 | Admission to hospital | GoalStartEvent
32509001 | Black turkey (organism) | AnimalBreeds
32540008 | Commercial meat type chicken (organism) | AnimalBreeds
3260001 | Duroc pig (organism) | AnimalBreeds
32683006 | FHC elite pig 7 (organism) | AnimalBreeds
32938007 | Gir cattle breed (organism) | AnimalBreeds
33022008 | Hospital-based outpatient clinic or department--OTHER-NOT LISTED | Facility Type Code Value Set
331006 | Hospital outpatient rheumatology clinic | Facility Type Code Value Set
33212007 | Boar power pig 616 (organism) | AnimalBreeds
33224000 | Phoenix chicken (organism) | AnimalBreeds
33463005 | Fluid | Nutrient Modifier Codes
33551003 | Kentucky red berkshire pig (organism) | AnimalBreeds
33607002 | Buttercup chicken (organism) | AnimalBreeds
340519003 | Lysine intolerance | AllergyIntolerance Substance/Product, Condition and Negation Codes
34200004 | Standardbred horse (organism) | AnimalBreeds
3457005 | Patient referral | SNOMED CT Patient Referral
34595003 | Boar power pig 828 (organism) | AnimalBreeds
34618005 | cow | AnimalSpecies
351726001 | Below | Bodysite Location Qualifier
35229007 | Chianina cattle breed (organism) | AnimalBreeds

352730000 | Above | Bodysite Location Qualifier
35354009 | Equus caballus (organism) | AnimalBreeds
3566006 | Southdown sheep (organism) | AnimalBreeds
35839008 | Leghorn chicken (organism) | AnimalBreeds
35963001 | Removal of staples | Procedure Follow up Codes (SNOMED CT)
35971002 | Ambulatory care site--OTHER--NOT LISTED | Facility Type Code Value Set
359825008 | Cytopathology, review of bronchioalveolar lavage specimen | Procedure Follow up Codes (SNOMED CT)
359839008 | Domestic fowl (organism) | AnimalBreeds
360020006 | Extirpation - action | FHIR Specimen Collection Method
360957003 | Hospital outpatient allergy clinic | Facility Type Code Value Set
360966004 | Hospital outpatient immunology clinic | Facility Type Code Value Set
36111002 | Kleen leen black pig (organism) | AnimalBreeds
36125001 | Hospital-trauma center | Facility Type Code Value Set
36187006 | Spotted pig (organism) | AnimalBreeds
36293008 | Hospital outpatient pain clinic | Facility Type Code Value Set
363679005 | Imaging | Media SubType
36570001 | Dekalb hybrid pig line 31 (organism) | AnimalBreeds
365858006 | Prognosis/outlook finding | Clinical Impression Prognosis
36653000 | Rubella | Vaccination Protocol Dose Target Codes
36989005 | Mumps | Vaccination Protocol Dose Target Codes
371900001 | Medication not administered | SNOMED CT Reason Medication Not Given Codes
3729002 | Hospital outpatient pediatric clinic | Facility Type Code Value Set
373873005 | Pharmaceutical / biologic product | Substance Code
37546005 | Hospital outpatient rehabilitation clinic | Facility Type Code Value Set
37550003 | Hospital outpatient dermatology clinic | Facility Type Code Value Set
37812004 | Broad breasted white turkey (organism) | AnimalBreeds
38238005 | Hospital outpatient neurology clinic | Facility Type Code Value Set
385356007 | Tumour stage finding | Condition Stage
385669000 | Successful | Procedure Outcome Codes (SNOMED CT)
385670004 | Partially successful | Procedure Outcome Codes (SNOMED CT)
385671000 | Unsuccessful | Procedure Outcome Codes (SNOMED CT)
386053000 | Patient evaluation procedure | Observation Methods
386147002 | Smear procedure | FHIR Specimen Collection Method
386216000 | Childbirth | GoalStartEvent
3872000 | Beltsville white turkey (organism) | AnimalBreeds
387713003 | Surgical procedure | Procedure Category Codes (SNOMED CT)
387961004 | Kingdom Animalia | Context of Use ValueSet
388445009 | horse | AnimalSpecies
39350007 | Private physicians' group office | Facility Type Code Value Set
394539006 | Pediatric surgery | Practice Setting Code Value Set
394576009 | Surgical-Accident & emergency | Practice Setting Code Value Set
394577000 | Anesthetics | Practice Setting Code Value Set
394578005 | Audiological medicine | Practice Setting Code Value Set
394579002 | Cardiology | Practice Setting Code Value Set
394580004 | Clinical genetics | Practice Setting Code Value Set
394581000 | Community medicine | Practice Setting Code Value Set
394582007 | Dermatology | Practice Setting Code Value Set
394583002 | Endocrinology | Practice Setting Code Value Set
394584008 | Gastroenterology | Practice Setting Code Value Set
394585009 | Obstetrics and gynecology | Practice Setting Code Value Set
394586005 | Gynecology | Practice Setting Code Value Set
394587001 | Psychiatry | Practice Setting Code Value Set
394588006 | Pediatric (Child and adolescent) psychiatry | Practice Setting Code Value Set
394589003 | Nephrology | Practice Setting Code Value Set
394590007 | Thoracic medicine | Practice Setting Code Value Set
394591006 | Neurology | Practice Setting Code Value Set
394592004 | Clinical oncology | Practice Setting Code Value Set
394593009 | Medical oncology | Practice Setting Code Value Set
394594003 | Ophthalmology | Practice Setting Code Value Set
394597005 | Histopathology | Practice Setting Code Value Set
394598000 | Immunopathology | Practice Setting Code Value Set
394599008 | Neuropathology | Practice Setting Code Value Set
394600006 | Clinical pharmacology | Practice Setting Code Value Set
394601005 | Clinical physiology | Practice Setting Code Value Set
394602003 | Rehabilitation | Practice Setting Code Value Set
394604002 | Surgery-Ear, nose and throat surgery | Practice Setting Code Value Set
394605001 | Surgery-Dental-Oral surgery | Practice Setting Code Value Set
394606000 | Surgery-Dentistry-Restorative dentistry | Practice Setting Code Value Set
394607009 | Pediatric dentistry | Practice Setting Code Value Set
394608004 | Surgery-Dental-Orthodontics | Practice Setting Code Value Set Practice Setting Code Value Set
394609007 | Surgery-general | Practice Setting Code Value Set
394610002 | Surgery-Neurosurgery | Practice Setting Code Value Set

394611003 | Surgery-Plastic surgery | Practice Setting Code Value Set
394612005 | Urology | Practice Setting Code Value Set
394649004 | Nuclear medicine | Practice Setting Code Value Set
394725008 | Diabetes medication review | Procedure Follow up Codes (SNOMED CT)
394730007 | Healthcare related organisation | Participant Roles
394732004 | Surgical specialty--OTHER-NOT LISTED | Practice Setting Code Value Set
394733009 | Medical specialty--OTHER--NOT LISTED | Practice Setting Code Value Set
394759007 | Independent ambulatory care provider site--OTHER--NOT LISTED | Facility Type Code Value Set
394777002 | Health encounter site--NOT LISTED | Facility Type Code Value Set
394801008 | Surgery-Trauma and orthopedics | Practice Setting Code Value Set
394802001 | General medicine | Practice Setting Code Value Set
394803006 | Clinical hematology | Practice Setting Code Value Set
394804000 | Clinical cytogenetics and molecular genetics | Practice Setting Code Value Set
394806003 | Palliative medicine | Practice Setting Code Value Set
394807007 | Infectious diseases | Practice Setting Code Value Set
394808002 | Genito-urinary medicine | Practice Setting Code Value Set
394809005 | Clinical neuro-physiology | Practice Setting Code Value Set
394810000 | Rheumatology | Practice Setting Code Value Set
394811001 | Geriatric medicine | Practice Setting Code Value Set
394812008 | Dental medicine specialties | Practice Setting Code Value Set
394813003 | Medical ophthalmology | Practice Setting Code Value Set
394814009 | General practice | Practice Setting Code Value Set
394821009 | Occupational medicine | Practice Setting Code Value Set
394882004 | Pain management | Practice Setting Code Value Set
394908001 | Procedure stopped | Procedure Not Performed Reason (SNOMED-CT)
394913002 | Psychotherapy | Practice Setting Code Value Set
394914008 | Radiology | Practice Setting Code Value Set
394915009 | General pathology | Practice Setting Code Value Set
394916005 | Hematopathology | Practice Setting Code Value Set
39532001 | Norman coach horse (organism) | AnimalBreeds
39571003 | Buckeye chicken (organism) | AnimalBreeds
396488006 | Ariégeois pony breed (organism) | AnimalBreeds
396620009 | duck | AnimalSpecies
397430003 | Diphtheria due to Corynebacterium diphtheriae | Vaccination Protocol Dose Target Codes
397640006 | Healthcare knowledge finding | Care Plan Activity Outcome
398102009 | Acute poliomyelitis | Vaccination Protocol Dose Target Codes
39855006 | Wiltshire horn sheep (organism) | AnimalBreeds
39913001 | Residential school infirmary | Facility Type Code Value Set
3997000 | Pony (organism) | AnimalBreeds
39972003 | Sodium | Nutrient Modifier Codes
400003 | Pinzgauer cattle breed (organism) | AnimalBreeds
404684003 | Clinical finding | Encounter Reason Codes
405607001 | Ambulatory surgery center | Facility Type Code Value Set
406149000 | Medication refused | SNOMED CT Reason Medication Not Given Codes
406660008 | Galway sheep breed (organism) | AnimalBreeds
406663005 | Ukrainian steppe white pig (organism) | AnimalBreeds
406711007 | Brabant horse (organism) | AnimalBreeds
406714004 | Gypsy Vanner horse (organism) | AnimalBreeds
406715003 | Murgese horse (organism) | AnimalBreeds
406721004 | Mixed breed horse (organism) | AnimalBreeds
406722006 | Mixed breed sheep (organism) | AnimalBreeds
406723001 | Mixed breed chicken (organism) | AnimalBreeds
407402001 | Warmblood horse breed (organism) | AnimalBreeds
408440000 | Public health medicine | Practice Setting Code Value Set
408441001 | Surgery-Dental-Endodontics | Practice Setting Code Value Set
408443003 | General medical practice | Practice Setting Code Value Set
408444009 | Dental-General dental practice | Practice Setting Code Value Set
408446006 | Gynecological oncology | Practice Setting Code Value Set
408447002 | Respite care | Practice Setting Code Value Set
408448007 | Tropical medicine | Practice Setting Code Value Set
408449004 | Surgery-Dentistry--surgical | Practice Setting Code Value Set
408450004 | Sleep studies | Practice Setting Code Value Set
408454008 | Clinical microbiology | Practice Setting Code Value Set
408455009 | Radiology-Interventional radiology | Practice Setting Code Value Set
408459003 | Pediatric cardiology | Practice Setting Code Value Set
408460008 | Surgery-Dental-Prosthetic dentistry (Prosthodontics) | Practice Setting Code Value Set Practice Setting Code Value Set
408461007 | Surgery-Dental-Periodontal surgery | Practice Setting Code Value Set
408462000 | Burns care | Practice Setting Code Value Set
408463005 | Surgery-Vascular | Practice Setting Code Value Set
408464004 | Surgery-Colorectal surgery | Practice Setting Code Value Set
408465003 | Surgery-Dental-Oral and maxillofacial surgery | Practice Setting Code Value Set
408466002 | Surgery-Cardiac surgery | Practice Setting Code Value Set

408467006 | Adult mental illness | Practice Setting Code Value Set
408468001 | Learning disability | Practice Setting Code Value Set
408469009 | Surgery-Breast surgery | Practice Setting Code Value Set
408470005 | Obstetrics | Practice Setting Code Value Set
408471009 | Surgery-Cardiothoracic transplantation | Practice Setting Code Value Set
408472002 | Hepatology | Practice Setting Code Value Set
408474001 | Surgery-Hepatobiliary and pancreatic surgery | Practice Setting Code Value Set
408475000 | Diabetic medicine | Practice Setting Code Value Set
408476004 | Surgery-Bone and marrow transplantation | Practice Setting Code Value Set
408477008 | Surgery-Transplantation surgery | Practice Setting Code Value Set
408478003 | Critical care medicine | Practice Setting Code Value Set
408480009 | Clinical immunology | Practice Setting Code Value Set
409063005 | Counselling | Procedure Category Codes (SNOMED CT)
409073007 | Education | Procedure Category Codes (SNOMED CT)
409519008 | Contained casualty setting | Facility Type Code Value Set
409905004 | Black Angus cattle breed (organism) | AnimalBreeds
409906003 | Mixed breed cattle (organism) | AnimalBreeds
409908002 | Masai cattle breed (organism) | AnimalBreeds
409909005 | Antwerp bearded bantam (organism) | AnimalBreeds
409910000 | Bantam (organism) | AnimalBreeds
409911001 | Moulard duck breed (organism) | AnimalBreeds
409967009 | Toxicology | Practice Setting Code Value Set
409968004 | Preventive medicine | Practice Setting Code Value Set
410001006 | Military medicine | Practice Setting Code Value Set
410005002 | Dive medicine | Practice Setting Code Value Set
41092008 | Cleveland bay horse (organism) | AnimalBreeds
410942007 | Drug or medicament | SNOMED CT Medication Codes
41290008 | Plymouth Rock chicken (organism) | AnimalBreeds
413427002 | Acquired fructose intolerance | AllergyIntolerance Substance/Product, Condition and Negation Codes
413456002 | Adult day care center | Facility Type Code Value Set
413651001 | Bioptics | FHIR Specimen Collection Method
413817003 | Child day care center | Facility Type Code Value Set
41437006 | Jungle fowl chicken (organism) | AnimalBreeds
41561001 | Dekalb hybrid pig line 30 (organism) | AnimalBreeds
416064006 | Procedure not offered | Procedure Not Performed Reason (SNOMED-CT)
416237000 | Procedure not done | Procedure Not Performed Reason (SNOMED-CT)
416304004 | Osteopathic manipulative medicine | Practice Setting Code Value Set
416406003 | Procedure discontinued | Procedure Not Performed Reason (SNOMED-CT)
416432009 | Procedure not wanted | Procedure Not Performed Reason (SNOMED-CT)
417012009 | Mixed breed pig (organism) | AnimalBreeds
41706005 | Perendale sheep (organism) | AnimalBreeds
41738000 | Palomino horse (organism) | AnimalBreeds
41754002 | Lipizzaner horse (organism) | AnimalBreeds
418002000 | Pediatric oncology | Practice Setting Code Value Set
418018006 | Surgery-Dermatologic surgery | Practice Setting Code Value Set
418038007 | Propensity to adverse reactions to substance | AllergyIntolerance Substance/Product, Condition and Negation Codes
418058008 | Pediatric gastroenterology | Practice Setting Code Value Set
418112009 | Pulmonary medicine | Practice Setting Code Value Set
41844007 | Free-standing geriatric health center | Facility Type Code Value Set
418518002 | Dialysis unit--hospital | Facility Type Code Value Set
418535003 | Pediatric immunology | Practice Setting Code Value Set
418652005 | Pediatric hematology | Practice Setting Code Value Set
418862001 | Pediatric infectious diseases | Practice Setting Code Value Set
418960008 | Otolaryngology | Practice Setting Code Value Set
419043006 | Urological oncology | Practice Setting Code Value Set
419161000 | Unilateral left | Bodysite Location Qualifier
419170002 | Pediatric pulmonology | Practice Setting Code Value Set
419192003 | Internal medicine | Practice Setting Code Value Set
419321007 | Surgical oncology | Practice Setting Code Value Set
419365004 | Pediatric nephrology | Practice Setting Code Value Set
419465000 | Unilateral right | Bodysite Location Qualifier
419472004 | Pediatric rheumatology | Practice Setting Code Value Set
419492006 | Additional dosage instructions | SNOMED CT Additional Dosage Instructions
419610006 | Pediatric endocrinology | Practice Setting Code Value Set
419772000 | Family practice | Practice Setting Code Value Set
419815003 | Radiation oncology | Practice Setting Code Value Set
419955002 | Residential institution | Facility Type Code Value Set
419983000 | Pediatric ophthalmology | Practice Setting Code Value Set
420112009 | Pediatric surgery-bone marrow transplantation | Practice Setting Code Value Set
420208008 | Pediatric genetics | Practice Setting Code Value Set
421661004 | Blood banking and transfusion medicine | Practice Setting Code Value Set
421967003 | Drug dose form | SNOMED CT Form Codes

422096002 | Dosing instruction fragment | SNOMED CT Administration Method Codes
422191005 | Ophthalmic surgery | Practice Setting Code Value Set
424705003 | Bison bison X Simmental hybrid cattle breed (organism) | AnimalBreeds
425134008 | turkey | AnimalSpecies
425181009 | Bison bison X Bos taurus hybrid (organism) | AnimalBreeds
42602001 | Minorca chicken (organism) | AnimalBreeds
42665001 | Nursing home | Facility Type Code Value Set
427136006 | Saddlebred horse superbreed (organism) | AnimalBreeds
42724005 | American saddlebred horse (organism) | AnimalBreeds
428119001 | Procedure not indicated | Procedure Not Performed Reason (SNOMED-CT)
42840001 | Jersey giant chicken (organism) | AnimalBreeds
4288003 | Thoroughbred horse (organism) | AnimalBreeds
429060002 | Procedure to meet occupational requirement | Immunization Reason Codes
42948007 | Norwegian landrace pig (organism) | AnimalBreeds
430823004 | Examination of midstream urine specimen | FHIR Specimen Collection Method
4322002 | Hospital-military field | Facility Type Code Value Set
43223009 | Yokohama chicken (organism) | AnimalBreeds
434711009 | Specimen container | SpecimenContainer
43500007 | Boar power pig 454 (organism) | AnimalBreeds
43869002 | Rouen duck breed (organism) | AnimalBreeds
439021000124105 | nectar thick liquid | Fluid Consistency Type Codes
439031000124108 | honey thick liquid | Fluid Consistency Type Codes
439041000124103 | spoon thick liquid | Fluid Consistency Type Codes
439081000124109 | thin liquid | Fluid Consistency Type Codes
439091000124107 | Easy to chew food | Texture Modifier Codes
440034003 | Polled dorset sheep breed (organism) | AnimalBreeds
44027008 | Seafood | Texture Modified Food Type Codes
441531000124102 | Standard Enteral Formula | Supplement Type Codes
441561000124106 | Standard enteral formula with fiber | Supplement Type Codes
441571000124104 | High energy enteral formula with fiber | Supplement Type Codes
441591000124103 | Diabetic enteral formula with fiber | Supplement Type Codes
441601000124106 | Diabetic high calorie high protein enteral formula with fiber | Supplement Type Codes
441671000124100 | Hydrolyzed peptide-based high protein enteral formula | Supplement Type Codes
441714000 | Rhinelander horse breed (organism) | AnimalBreeds
441751000124100 | Mashed food | Texture Modifier Codes
441761000124103 | Minced food | Texture Modifier Codes
441771000124105 | Moist food | Texture Modifier Codes
441791000124106 | Strained food | Texture Modifier Codes
441881000124103 | Ground food | Texture Modifier Codes
442083009 | Anatomical or acquired body structure | SNOMED CT Body Structures
442137000 | Completion time of procedure | GoalStartEvent
44230005 | Brown Swiss cattle breed (organism) | AnimalBreeds
442651000124102 | Adult formula | Supplement Type Codes
442901000124106 | Adult clear liquid supplement | Supplement Type Codes
442911000124109 | Adult elemental formula | Supplement Type Codes
442921000124101 | Adult standard formula | Supplement Type Codes
442931000124103 | Adult soy protein isolate formula | Supplement Type Codes
442941000124108 | Adult renal specialty formula | Supplement Type Codes
442951000124105 | Adult pulmonary specialty formula | Supplement Type Codes
442961000124107 | Adult low carbohydrate formula | Supplement Type Codes
442971000124100 | Adult high energy formula | Supplement Type Codes
442981000124102 | Adult hydrolyzed protein formula | Supplement Type Codes
442991000124104 | Adult high protein formula | Supplement Type Codes
443011000124100 | Adult high protein high fiber formula | Supplement Type Codes
443021000124108 | Adult hepatic specialty formula | Supplement Type Codes
443031000124106 | Adult critical care formula | Supplement Type Codes
443051000124104 | Adult diabetes specialty formula | Supplement Type Codes
443111000124101 | High protein formula | Supplement Type Codes
443351000124102 | Increased fiber formula | Supplement Type Codes
443361000124100 | Pediatric Formula | Supplement Type Codes
443391000124108 | Pediatric clear liquid supplement | Supplement Type Codes
443401000124105 | Pediatric elemental formula | Supplement Type Codes
443411000124108 | Elemental Formula | Supplement Type Codes
443421000124100 | Pediatric hydrolyzed protein formula | Supplement Type Codes
443431000124102 | High Energy Formula | Supplement Type Codes
443441000124107 | Clear liquid supplement | Supplement Type Codes
443451000124109 | Pediatric standard formula | Supplement Type Codes
443461000124106 | Standard Formula | Supplement Type Codes
443471000124104 | Pediatric increased fiber formula | Supplement Type Codes
443481000124101 | Renal Formula | Supplement Type Codes
443491000124103 | Pediatric high energy formula | Supplement Type Codes
443501000124106 | Pediatric high energy formula with increased fiber | Supplement Type Codes

443561000124107 | Soy based formula | Supplement Type Codes
443771000124106 | Hydrolyzed protein formula | Supplement Type Codes
444321000124108 | Standard pudding oral supplement | Supplement Type Codes
444331000124106 | Diabetic meal replacement bar | Supplement Type Codes
444361000124102 | Electrolyte replacement supplement | Supplement Type Codes
444371000124109 | Powdered electrolyte replacement supplement | Supplement Type Codes
444381000124107 | Liquid electrolyte replacement supplement | Supplement Type Codes
444401000124107 | Frozen electrolyte replacement supplement | Supplement Type Codes
444431000124104 | Pediatric reduced energy formula | Supplement Type Codes
445729005 | Tarpan horse breed (organism) | AnimalBreeds
447346005 | Cardiopulmonary exercise test | Procedure Follow up Codes (SNOMED CT)
44835005 | Debouillet sheep (organism) | AnimalBreeds
45284002 | Maine Anjou cattle breed (organism) | AnimalBreeds
45618002 | Skilled nursing facility | Facility Type Code Value Set
45635003 | FHC elite pig 1 (organism) | AnimalBreeds
45690005 | Mouflon sheep (organism) | AnimalBreeds
45710003 | Sputum | FHIR Specimen Collection Method
4574003 | Shropshire sheep (organism) | AnimalBreeds
45790002 | American Albino horse (organism) | AnimalBreeds
45899008 | Free-standing laboratory facility | Facility Type Code Value Set
46224007 | Vaccination clinic | Facility Type Code Value Set
46392004 | Delaine merino sheep (organism) | AnimalBreeds
46408008 | American pony (organism) | AnimalBreeds
46830002 | Midget white turkey (organism) | AnimalBreeds
46947000 | Chiropractic manipulation | Procedure Category Codes (SNOMED CT)
47290002 | chicken | AnimalSpecies
47314009 | Dark brown turkey (organism) | AnimalBreeds
47745005 | Java chicken (organism) | AnimalBreeds
47795006 | FHC elite pig 4 (organism) | AnimalBreeds
47842004 | Canadian horse (organism) | AnimalBreeds
48255007 | Silkie chicken (organism) | AnimalBreeds
48311003 | Hospital-Veterans' Administration | Facility Type Code Value Set
48394005 | Beltsville pig (organism) | AnimalBreeds
48470006 | Boar power pig 656 (organism) | AnimalBreeds
48697009 | Clun Forest sheep (organism) | AnimalBreeds
48702000 | Limousin cattle breed (organism) | AnimalBreeds
4880003 | Piedmontese cattle breed (organism) | AnimalBreeds
49062001 | Device | FHIR Device Types
49240006 | Palouse pig (organism) | AnimalBreeds
49370004 | Lateral | Bodysite Location Qualifier
49407004 | Lankenvelder chicken (organism) | AnimalBreeds
49462008 | FHC elite pig 6 (organism) | AnimalBreeds
4960000 | Peruvian Paso horse (organism) | AnimalBreeds
50569004 | Hospital outpatient urology clinic | Facility Type Code Value Set
50710008 | Blue slate turkey (organism) | AnimalBreeds
50717006 | Cheviot sheep (organism) | AnimalBreeds
50959000 | Tarentaise cattle breed (organism) | AnimalBreeds
51023000 | Tennessee walking horse (organism) | AnimalBreeds
5114005 | Fayoumi chicken (organism) | AnimalBreeds
51440002 | Bilateral | Bodysite Location Qualifier
51563005 | Free-standing mental health center | Facility Type Code Value Set
5164003 | Montdale sheep (organism) | AnimalBreeds
51937006 | Jersey cattle breed (organism) | AnimalBreeds
5227002 | Oxford sandy block pig (organism) | AnimalBreeds
52668009 | Hospital birthing center | Facility Type Code Value Set
52882006 | Dominique chicken (organism) | AnimalBreeds
53031002 | Dexter cattle breed (organism) | AnimalBreeds
53360003 | Oxford Down sheep (organism) | AnimalBreeds
53431006 | Boar power pig 59 (organism) | AnimalBreeds
5345000 | Santa Gertrudis cattle breed (organism) | AnimalBreeds
5350006 | Rhode Island red chicken (organism) | AnimalBreeds
53567001 | Suffolk horse (organism) | AnimalBreeds
54098002 | Arabian horse (organism) | AnimalBreeds
54218009 | New Hampshire chicken (organism) | AnimalBreeds
54232006 | Welsh pig (organism) | AnimalBreeds
54251000 | Australorp chicken (organism) | AnimalBreeds
5438004 | French alpine goat (organism) | AnimalBreeds
54447000 | Haflinger horse (organism) | AnimalBreeds
54604007 | Gray turkey (organism) | AnimalBreeds
54699009 | American miniature horse (organism) | AnimalBreeds
55074002 | Jersey buff turkey (organism) | AnimalBreeds
55167009 | Appaloosa horse (organism) | AnimalBreeds

55530007 | La Mancha goat (organism) | AnimalBreeds
5584006 | Hospital outpatient peripheral vascular clinic | Facility Type Code Value Set
56084008 | Boar power pig 292 (organism) | AnimalBreeds
56086005 | Paso Fino horse (organism) | AnimalBreeds
56189001 | Hospital outpatient obstetrical clinic | Facility Type Code Value Set
56293002 | Hospital outpatient hematology clinic | Facility Type Code Value Set
56764001 | Holland chicken (organism) | AnimalBreeds
57159002 | Hospital outpatient respiratory disease clinic | Facility Type Code Value Set
57364006 | Brahma chicken (organism) | AnimalBreeds
57613003 | Kleen leen white pig (organism) | AnimalBreeds
57950004 | Spitzhauben chicken (organism) | AnimalBreeds
58264006 | Pinto (organism) | AnimalBreeds
58311005 | Dutch landrace pig (organism) | AnimalBreeds
58482006 | Hospital outpatient gastroenterology clinic | Facility Type Code Value Set
59210004 | Navajo sheep (organism) | AnimalBreeds
59374000 | Traveler's aid clinic | Facility Type Code Value Set
59667000 | FHC elite pig 2 (organism) | AnimalBreeds
6053007 | Dekalb hybrid pig line 33 (organism) | AnimalBreeds
60786005 | Lilac buff turkey (organism) | AnimalBreeds
60958006 | Maryland pig (organism) | AnimalBreeds
61036003 | Boar power pig 545 (organism) | AnimalBreeds
61083001 | Minnesota pig (organism) | AnimalBreeds
6112002 | Meusse-Rhine-Ijssel cattle breed (organism) | AnimalBreeds
61204004 | Dorking chicken (organism) | AnimalBreeds
61839006 | Cornish chicken (organism) | AnimalBreeds
61843005 | Polish chicken (organism) | AnimalBreeds
61973002 | Dekalb hybrid pig line 61 (organism) | AnimalBreeds
62124009 | Royal palm turkey (organism) | AnimalBreeds
62153005 | Blonde d'Aquitaine (organism) | AnimalBreeds
6220006 | Galiceno horse (organism) | AnimalBreeds
62480006 | Hospital-psychiatric | Facility Type Code Value Set
63257005 | Chantecler chicken (organism) | AnimalBreeds
64158000 | Angora goat (organism) | AnimalBreeds
6431001 | Leicester sheep (organism) | AnimalBreeds
64591001 | Karakul sheep (organism) | AnimalBreeds
65136005 | Light brown turkey (organism) | AnimalBreeds
65187008 | Black faced Highland sheep (organism) | AnimalBreeds
65344003 | Marchigiana cattle breed (organism) | AnimalBreeds
65492002 | Lincoln sheep (organism) | AnimalBreeds
65873005 | Barnevelder chicken (organism) | AnimalBreeds
66168008 | Hanoverian horse (organism) | AnimalBreeds
66314009 | Longhorn cattle breed (organism) | AnimalBreeds
66911005 | Galloway cattle breed (organism) | AnimalBreeds
67021006 | Sebright chicken (organism) | AnimalBreeds
67209003 | Turken chicken (organism) | AnimalBreeds
6736007 | Moderate | Condition/Diagnosis Severity
67414001 | Cotswold sheep (organism) | AnimalBreeds
67448000 | German Fleck-Vieh cattle breed (organism) | AnimalBreeds
67515002 | Corriedale sheep (organism) | AnimalBreeds
67720004 | FHC elite pig 5 (organism) | AnimalBreeds
67889009 | Irrigation | FHIR Specimen Collection Method
6827000 | Local community health center | Facility Type Code Value Set
684003 | Pygmy goat (organism) | AnimalBreeds
68412000 | Sultan chicken (organism) | AnimalBreeds
68512002 | Boar power pig 141 (organism) | AnimalBreeds
69067004 | Shetland pony (organism) | AnimalBreeds
69362002 | Hospital ambulatory surgery facility | Facility Type Code Value Set
69461005 | Chester white pig (organism) | AnimalBreeds
69575001 | Ancona chicken (organism) | AnimalBreeds
69602006 | Kleen leen pig (organism) | AnimalBreeds
70210006 | Orloff chicken (organism) | AnimalBreeds
70308007 | Langshan chicken (organism) | AnimalBreeds
70326005 | Cubalaya chicken (organism) | AnimalBreeds
70429002 | Game chicken (organism) | AnimalBreeds
70431006 | Alpine goat (organism) | AnimalBreeds
70457009 | Icelandic horse (organism) | AnimalBreeds
70881005 | Anser anser anser (organism) | AnimalBreeds
709410003 | Haemophilus influenzae type b infection | Vaccination Protocol Dose Target Codes
71238008 | Commercial brown egg layer type chicken (organism) | AnimalBreeds
71388002 | Procedure | Encounter Reason Codes
716186003 | No known allergy | AllergyIntolerance Substance/Product, Condition and Negation Codes
71923001 | Italian landrace pig (organism) | AnimalBreeds

72311000 | Health maintenance organization | Facility Type Code Value Set
72329005 | Finnish landrace sheep (organism) | AnimalBreeds
72394007 | American tunis horse (organism) | AnimalBreeds
72511004 | Fruit | Texture Modified Food Type Codes
72648002 | Suffolk sheep (organism) | AnimalBreeds
73005003 | FHC elite pig 8 (organism) | AnimalBreeds
73012007 | Penna white turkey (organism) | AnimalBreeds
73191001 | American merino sheep (organism) | AnimalBreeds
73644007 | Hospital outpatient endocrinology clinic | Facility Type Code Value Set
73648005 | Wessex saddleback pig (organism) | AnimalBreeds
73770003 | Emergency department--hospital | Facility Type Code Value Set
73944009 | Minnesota pig #1 (organism) | AnimalBreeds
74242007 | Food Starch | Texture Modified Food Type Codes
74517004 | Montana pig (organism) | AnimalBreeds
74568001 | Red wattle pig (organism) | AnimalBreeds
74745008 | Rock alpine goat (organism) | AnimalBreeds
74899005 | Boar power pig (organism) | AnimalBreeds
74921000 | Dekalb hybrid pig line (organism) | AnimalBreeds
74970001 | Boar power pig 161 (organism) | AnimalBreeds
75709004 | Pic pig (organism) | AnimalBreeds
7598004 | Wyandotte chicken (organism) | AnimalBreeds
7623008 | American paint horse (organism) | AnimalBreeds
76268003 | Campine chicken (organism) | AnimalBreeds
76302002 | Spanish mustang horse (organism) | AnimalBreeds
76364003 | Boar power pig 27 (organism) | AnimalBreeds
76467006 | Quarter horse (organism) | AnimalBreeds
76497003 | Gelbveih cattle breed (organism) | AnimalBreeds
76604009 | Nellore cattle breed (organism) | AnimalBreeds
76902006 | Tetanus | Vaccination Protocol Dose Target Codes
7700003 | Nebraskan spotted turkey (organism) | AnimalBreeds
77236002 | Large white pig (organism) | AnimalBreeds
77386006 | Pregnancy not delivered | Observation Reference Range Applies To Codes
7767003 | Lamona chicken (organism) | AnimalBreeds
77839002 | Thuringer chicken (organism) | AnimalBreeds
77931003 | Rural health center | Facility Type Code Value Set
7800008 | Punctate | FHIR Specimen Collection Method
78001009 | Hospital outpatient orthopedics clinic | Facility Type Code Value Set
78088001 | Hospital outpatient ophthalmology clinic | Facility Type Code Value Set
78154009 | Malay chicken (organism) | AnimalBreeds
78375007 | Andalusian chicken (organism) | AnimalBreeds
7843000 | Horned Hereford (organism) | AnimalBreeds
78541007 | Milking Shorthorn cattle breed (organism) | AnimalBreeds
78678003 | Sus scrofa (organism) | AnimalBreeds
78994007 | British landrace pig (organism) | AnimalBreeds
79491001 | Hospital radiology facility | Facility Type Code Value Set
79603002 | Romedale sheep (organism) | AnimalBreeds
79814001 | Poland China pig (organism) | AnimalBreeds
79993009 | Hospital-government | Facility Type Code Value Set
80084005 | Lucie pig (organism) | AnimalBreeds
80131009 | Landrace pig (organism) | AnimalBreeds
80204002 | Hungarian chicken (organism) | AnimalBreeds
80522000 | Hospital-rehabilitation | Facility Type Code Value Set
80610007 | Narragansett turkey (organism) | AnimalBreeds
80777007 | Andalusian horse (organism) | AnimalBreeds
80835003 | Shorthorn cattle breed (organism) | AnimalBreeds
80886008 | Rosecomb chicken (organism) | AnimalBreeds
8089006 | Welsh walking horse (organism) | AnimalBreeds
80979001 | San Pierre pig (organism) | AnimalBreeds
80993008 | Sussex chicken (organism) | AnimalBreeds
81234003 | Walk-in clinic | Facility Type Code Value Set
81267004 | Normandie cattle breed (organism) | AnimalBreeds
82242000 | Hospital-children's | Facility Type Code Value Set
82249009 | California chicken (organism) | AnimalBreeds
82440005 | Hampshire Down sheep (organism) | AnimalBreeds
82848009 | Houdan chicken (organism) | AnimalBreeds
82909008 | Middle white pig (organism) | AnimalBreeds
83173002 | Scottish Highland cattle breed (organism) | AnimalBreeds
83418008 | Fetus | Focal Subject Codes
83842004 | Hungarian goose (organism) | AnimalBreeds
83891005 | Solo practice private office | Facility Type Code Value Set
83996001 | Criollo cattle breed (organism) | AnimalBreeds
84081007 | Boar power pig 747 (organism) | AnimalBreeds

84232003 | Kleen leen red pig (organism) | AnimalBreeds
84315000 | Boar power pig 474 (organism) | AnimalBreeds
84528008 | Danish landrace pig (organism) | AnimalBreeds
84839000 | Guernsey cattle breed (organism) | AnimalBreeds
84923006 | Aberdeen Angus cattle breed (organism) | AnimalBreeds
8516002 | Dekalb hybrid pig line 51 (organism) | AnimalBreeds
85315007 | Yorkshire pig (organism) | AnimalBreeds
85626006 | donkey | AnimalSpecies
86440008 | Pic line pig 24 (organism) | AnimalBreeds
86694007 | Hormel miniature pig (organism) | AnimalBreeds
86920006 | Horned dorset sheep breed (organism) | AnimalBreeds
87061000 | Boar power pig 282 (organism) | AnimalBreeds
87530001 | Welsummer chicken (organism) | AnimalBreeds
8763002 | German landrace pig (organism) | AnimalBreeds
87833007 | Sumatra chicken (organism) | AnimalBreeds
87962009 | North County cheviot sheep (organism) | AnimalBreeds
88480006 | Potassium | Nutrient Modifier Codes
88807001 | Red Poll cattle breed (organism) | AnimalBreeds
89648005 | Fjord horse (organism) | AnimalBreeds
89665001 | Targhee sheep (organism) | AnimalBreeds
8970009 | French landrace pig (organism) | AnimalBreeds
89708009 | Chamoisee goat (organism) | AnimalBreeds
8989009 | Ayrshire cattle breed (organism) | AnimalBreeds
89928000 | FHC pig (organism) | AnimalBreeds
89972002 | Hospital outpatient oncology clinic | Facility Type Code Value Set
900000000000446008 | Description type | Designation Use
90050009 | American Buckskin horse (organism) | AnimalBreeds
901005 | Helicopter-based care | Facility Type Code Value Set
90484001 | Hospital outpatient general surgery clinic | Facility Type Code Value Set
90612002 | Salers cattle breed (organism) | AnimalBreeds
90885005 | Gloucester old spot pig (organism) | AnimalBreeds
91154008 | Free-standing birthing center | Facility Type Code Value Set
9135003 | OIC pig (organism) | AnimalBreeds
91401000 | Black Spanish turkey (organism) | AnimalBreeds
91427000 | Frizzle chicken (organism) | AnimalBreeds
91460002 | Chinese goose (organism) | AnimalBreeds
91723000 | Anatomical structure | SNOMED CT Anatomical Structure for Administration Site Codes
9230001 | Camarron goat (organism) | AnimalBreeds
9277006 | Polled Hereford (organism) | AnimalBreeds
944009 | Brown Welsh cattle breed (organism) | AnimalBreeds

4.2.2 Using RxNorm with FHIR

URL: https://hl7.org/fhir/STU3/rxnorm.html

This page is part of the FHIR Specification (v3.0.2: STU 3). The current version which supercedes this version is 4.0.1. For a full list of available versions, see the Directory of published versions

4.2.2 Using RxNorm with FHIR

Vocabulary Work Group | Maturity Level: 3 | Ballot Status: Trial Use

4.2.2.1 Summary

Source | RxNorm is made available by the US National Library of Medicine at http://www.nlm.nih.gov/research/umls/rxnorm
System | The URI http://www.nlm.nih.gov/research/umls/rxnorm identifies the RxNorm code system
Version | Where a version is used, it should be the date of release, encoded as in the download files, e.g. "07092014"
Code | The code value for an RxNorm code is a Concept Identifier (CUI), and only CUIs for which there is an SAB=RXNORM
Display | The correct display for a CUI is the string description for it associated with the source RXNORM. Display values are not case sensitive
Inactive | Todo: Describe how it is determined which concepts are inactive
Subsumption | No Subsumption relationships are defined by RxNorm
Filter Properties | Several properties are defined as described below

4.2.2.2 RxNorm MySQL Database

The RxNorm scripts are able to populate a MySQL database that contains the data from RxNorm. This page provides SQL statements that describe how to implement the features of the RxNorm terminology correctly against this database. These are provided for implementer convenience, and do not imply that any particular approach be used in implementations.

For example, the correct display name for a CUI is 'Select STR from rxnconso where RXCUI = :code and SAB = 'RXNORM' and TTY <> 'SY'.

4.2.2.3 Copyright/License Issues

Using RxNorm codes of type SAB=RXNORM as this specification describes does not require a UMLS license. Access to the full set of RxNorm definitions, and/or additional use of other RxNorm structures and information requires a UMLS license. The use of RxNorm in this specification is pursuant to HL7's status as a licensee of the NLM UMLS. HL7's license does not convey the right to use RxNorm to any users of this specification; implementers must acquire a license to use RxNorm in their own right.

4.2.2.4 RxNorm Filter Properties

This section documents the property filters that can be used with the RxNorm code system in value set composition statements.

The base SQL statement for returning a list of CUIs that conform to these filters is:

```
Select RXCUI from rxnconso where SAB = 'RXNORM' and TTY <> 'SY'
```

4.2.2.4.1 Semantic Type

Description | Allows for the selection of a set of CUIs based on their Semantic Type
Property Name | STY
Operations Allowed | = / in
Values Allowed | [column:]value
Comments | If not column is specified, the default column is TUI
SQL | and RXCUI in (select RXCUI from rxnsty where [:column] = :value)

4.2.2.4.2 Source

Description | Allows for the selection of a set of concepts that have mappings to a particular RxNorm concept
Property Name | SAB
Operations Allowed | = / in
Values Allowed | Values from RxNorm SAB table (e.g. select RSAB from rxnsab)
SQL | and RXCUI in (select RXCUI from rxnconso where SAB = :value)

4.2.2.4.3 Term Type

Description | Allows for the selection of a concept based on its designated type
Property Name | TTY
Operations Allowed | = / in
Values Allowed | TTY values from the RxNorm Concept table (e.g. select distinct TTY from rxnconso)
SQL | and TTY = :value

4.2.2.4.4 Relationship

Description | Allows for the selection of a concept based on its relationships
Property Name | [REL]
Operations Allowed | = / in
Values Allowed | CUI:[RXCUI] or AUI:[RXAUI] must be a valid CUI or AUI. Note that a CUI does not need to have an SAB=RXNORM entry to be used here
Comments | [REL] (:rel) is one of SY, SIB, RN, PAR, CHD, RB or RO
SQL | for CUI: and (RXCUI in (select RXCUI from rxnconso where RXCUI in (select RXCUI1 from rxnrel where REL = :rel and RXCUI2 = :value)) for AUI: and (RXCUI in (select RXCUI from rxnconso where RXAUI in (select RXAUI1 from rxnrel where REL = :rel and RXAUI2 = :value))

4.2.2.4.5 Relationship Type

Description | Allows for the selection of a concept based on the type of its relationships
Property Name | [RELA]
Operations Allowed | = / in
Values Allowed | CUI:[RXCUI] or AUI:[RXAUI] must be a valid CUI or AUI. Note that a CUI does not need to have an SAB=RXNORM entry to be used here
Comments | [RELA] (:rela) is one of the relationship types defined in RxNorm Appendix 1 (the "RELA" column)
SQL | for CUI: and (RXCUI in (select RXCUI from rxnconso where RXCUI in (select RXCUI1 from rxnrel where RELA = :rel and RXCUI2 = :value)) for AUI: and (RXCUI in (select RXCUI from rxnconso where RXAUI in (select RXAUI1 from rxnrel where RELA = :rel and RXAUI2 = :value))

4.2.2.5 RxNorm Properties

In addition to the standard properties, the following properties are defined for RxNorm:

(Yet to be done).

4.2.2.6 Implicit Value Sets

Implicit value sets are those whose specification can be predicted based on the grammar of the underlying code system, and the known structure of the URL that refers to them. At the time of this publication, RxNorm does not define implicit value sets.

The identifier http://www.nlm.nih.gov/research/umls/rxnorm/vs represents a value set that contains all RxNorm CUIs.

4.2.3 Using LOINC with FHIR

URL: https://hl7.org/fhir/STU3/loinc.html

This page is part of the FHIR Specification (v3.0.2: STU 3). The current version which supercedes this version is 4.0.1. For a full list of available versions, see the Directory of published versions

4.2.3 Using LOINC with FHIR

Vocabulary Work Group | Maturity Level: 5 | Ballot Status: Trial Use

4.2.3.1 Summary

Source | LOINC is made available by the Regenstrief Institute at http://loinc.org
System | The URI http://loinc.org identifies LOINC codes
Version | Where a version is used, it should be the standard LOINC version e.g. 2.48
Code | The LOINC Code Identifier e.g. 21176-3. LOINC codes are not case sensitive. In addition, LOINC part codes and LOINC answer string ids can be used where appropriate
Display | Use either the SHORTNAME or LONG_COMMON_NAME field for the display
Inactive | codes with Property ACTIVE=DEPRECATED are considered inactive
Subsumption | LOINC defines the Multi-Axial Hierarchy, which is the basis for subsumption logic in LOINC
Filter Properties | Several properties are defined as described below

Logically, LOINC codes and question codes correspond to Data Elements. See below for further information.

4.2.3.2 Copyright Issues

The terms of use for LOINC require that a notice be included with any use of LOINC codes. This notice must appear in the copyright element of any value set that includes LOINC codes (either in the code or filter elements, or in an expansion):

```
<copyright value="This content LOINC® is copyright © 1995 Regenstrief Institute, Inc. and the LOINC Committee, and
    available at no cost under the license at http://loinc.org/terms-of-use"/>
```

Additional copyright statements may also be found in the copyright element. Some LOINC codes have 3rd party copyright statements. When these codes are included in a value set, they must carry their own copyright statement as well.

4.2.3.3 Case Sensitivity

For comparison purposes, LOINC codes, displays, and property values are not case sensitive, though implementers SHOULD maintain the correct case when using LOINC codes and property values.

4.2.3.4 Use of LOINC PARTS

As described in the LOINC Manual section 10.2, LOINC Parts are a coded representation of a value for a dimension used to specify a LOINC Term which are assigned a non-semantic identifier with a "LP" prefix and a mod-10 check digit. Following the LOINC license, these part codes may be used in the following ways:

* In filter properties, as described below

* In Structure Definitions, where the structure describes the use of a set of LOINC codes

* In a ConceptMap resource, where mappings between LOINC codes and other codes are being defined

Part codes are the same LOINC system(http://loinc.org), and SHALL be represented in uppercase (e.g. LP31755-9).

4.2.3.5 Use of LOINC Answer Lists

LOINC also allocates Answer List and Answer String Ids for use in various forms and questionnaires. LOINC Answer String IDs are also valid LOINC codes:

```
<coding>
  <system value="http://loinc.org"/>
  <code value="LA11165-0"/>
  <display value="Platelet anisocytosis"/>
</coding>
```

LOINC Answer List Ids are actually value set identifiers. See below for how to use these.

4.2.3.6 RDF

LOINC uses the namespace http://loinc.org/owl# as the root for LOINC concepts in the RDF space. This means that when a LOINC code is converted from the system:code pair, where the system is http://loinc.org, to the RDF ontological form, the representation is http://loinc.org/owl#[code].

4.2.3.7 LOINC Properties

In addition to the standard properties, the following properties are defined for LOINC:

STATUS | boolean | Status of the term. For the purposes of LOINC, codes with Property ACTIVE=DEPRECATED are considered inactive
COMPONENT | code | First major axis-component or analyte: Analyte Name, Analyte sub-class, Challenge
PROPERTY | code | Second major axis-property observed: Kind of Property (also called kind of quantity)
TIME_ASPCT | code | Third major axis-timing of the measurement: Time Aspect (Point or moment in time vs. time interval)
SYSTEM | code | Fourth major axis-type of specimen or system: System (Sample) Type
SCALE_TYP | code | Fifth major axis-scale of measurement: Type of Scale
METHOD_TYP | code | Sixth major axis-method of measurement: Type of Method
CLASS | string | An arbitrary classification of the terms for grouping related observations together
CONSUMER_NAME | string | An experimental (beta) consumer friendly name for this item. The intent is to provide a test name that health care consumers will recognize; it will be similar to the names that might appear on a lab report
CLASSTYPE | string | 1=Laboratory class; 2=Clinical class; 3=Claims attachments; 4=Surveys
ORDER_OBS | string | ??
ORDER_OBS | string | Provides users with an idea of the intended use of the term by categorizing it as an order only, observation only, or both
DOCUMENT_SECTION | string | Classification of whether this LOINC code can be used a full document, a section of a document, or both

Note that when a $lookup operation is performed on a LOINC code, servers SHALL return the version being used (see above) in the version property. Other properties are at the discretion of the server and the client.

4.2.3.8 LOINC Filters

This section documents the property filters that can be used with the LOINC code system in value set composition statements.

4.2.3.8.1 LOINC Property filter

Description | Allows the selection of a set of LOINC codes with a common property value (see list above)
Property Name | One of the names listed in the "Field Name" column in LOINC Database Structure (Appendix A of the LOINC manual)
Operations Allowed | = / regex
Values Allowed | [string value]
Comments | The 6 properties COMPONENT, PROPERTY, TIME_ASPCT, SYSTEM, SCALE_TYP, and METHOD_TYP are most likely to be useful.

4.2.3.8.2 3rd Party Copyright

Description | Allows for the inclusion or exclusion of LOINC codes that include 3rd party copyright notices
Property Name | copyright
Operations Allowed | =
Values Allowed | LOINC | 3rdParty
Comments | LOINC = only codes with a sole copyright by Regenstrief. 3rdParty = only codes with a 3rd party copyright in addition to the one from Regenstrief.

4.2.3.8.3 Multi-Axial Hierarchy

Description | Allows for the selection of a set of codes base on their appearance in the LOINC multi-axial hierarchy
Property Name | parent | ancestor
Operations Allowed | = / in
Values Allowed | Part Code (or, for "in", multiple part codes separated by commas)
Comments | "parent" selects immediate parents only. For example, the code "44022-2" has the parent "LP52960-9". Ancestor includes parents transitively, e.g. "LP52960-9" eventually has a parent "LP31755-9", so the code "44022-2" is in the set of codes that have ancestor=LP31755-9

TODO: Document Ontology

4.2.3.9 Implicit Value Sets

Implicit value sets are those whose specification can be predicted based on the grammar of the underlying code system, and the known structure of the URL that refers to them. LOINC defines one set of implicit value sets: By Multi-Axial Hierarchy Entry.

If any value set resources exist with an identifier that conforms to the URL patterns specified below, the content of the resource must conform to the template provided. Profiles and other value set references are allowed to reference these value sets directly. todo: can LOINC actually host a service that returns these?

The value set identifier http://loinc.org/vs is a value set that contains all LOINC codes.

4.2.3.9.1 LOINC Answer List

LOINC defines a set of Answer lists, each of which contains a set of LOINC codes. LOINC answer lists are value sets. The value set identifier "http://loinc.org/vs/[id]" identifies a value set that contains a set of LOINC codes. For instance, the value set identifier http://loinc.org/vs/LL715-4 has the following definition for LOINC 2.52:

```
<ValueSet xmlns="http://hl7.org/fhir">
  <text>
    <status value="generated"/>
    <div xmlns="http://www.w3.org/1999/xhtml">
      [some html that identifies that this value set
      includes all LOINC codes in this answer list]
    </div>
  </text>
  <url value="http://loinc.org/vs/LL715-4"/>
  <version value="2.52"/>
  <name value="Platelet morph"/>
  <description value="LOINC Answer List for Platelet morph"/>
  <status value="active"/>
  <date value="[optional date of LOINC release]"/>
  <compose>
    <include>
      <system value="http://loinc.org"/>
      <concept>
        <code value="LA11165-0"/>
        <display value="Platelet anisocytosis"/>
      </concept>
      <concept>
        <code value="LA11168-4"/>
        <display value="Platelet clump"/>
      </concept>
      <concept>
        <code value="LA11167-6"/>
        <display value="Platelet large fragments"/>
      </concept>
      <concept>
        <code value="LA11166-8"/>
```

```
        <display value="Platelet satellitism"/>
      </concept>
      <concept>
        <code value="LA11169-2"/>
        <display value="Platelets.agranular"/>
      </concept>
      <concept>
        <code value="LA11170-0"/>
        <display value="Platelets.giant"/>
      </concept>
      <concept>
        <code value="LA11172-6"/>
        <display value="Platelets.large"/>
      </concept>
      <concept>
        <code value="LA11171-8"/>
        <display value="Platelets.small"/>
      </concept>
    </include>
  </compose>
</ValueSet>
```

Here is an example of a LOINC Answer list used in a Questionnaire question:

```
<question>
  <concept>
    <system value="http://loinc.org"/>
    <code value="11125-2"/>
    <display value="Plat morph Bld"/>
  </concept>
  <type value="choice"/>
  <options>
    <reference value="http://loinc.org/vs/LL715-4"/>
  </options>
</question>
```

4.2.3.9.2 Multi-Axial Hierarchy Entry

A value set with an identifier of "http://loinc.org/vs/[partcode]" must conform to this template, where [partcode] is a part code from the multi-axial hierarchy:

```
<ValueSet xmlns="http://hl7.org/fhir">
  <text>
    <status value="generated"/>
    <div xmlns="http://www.w3.org/1999/xhtml">
      [some html that identifies that this value set
      includes all LOINC codes subsumed by the identified
      Multi-Axial Hierarchy Part Code]
    </div>
  </text>
  <url value="http://loinc.org/vs/[partcode]"/>
  <version value="[optional - but strongly recommended - LOINC version]"/>
  <name value="LOINC Value Set from Multi-Axial Hierarchy code [partcode]"/>
  <description value="All LOINC codes for [partcode or name]"/>
  <status value="active"/>
  <date value="[optional date of LOINC release]"/>
  <compose>
    <include>
      <system value="http://loinc.org"/>
      <filter>
        <property value="ancestor"/>
        <op value="="/>
        <value value="[partcode]"/>
      </filter>
    </include>
  </compose>
</ValueSet>
```

4.2.3.9.3 LOINC and Data Elements

LOINC codes and their properties are describing a data element that can have a value. Functionally, this overlaps with the Data Element resource, and, in fact, a DataElement can be created for each LOINC code based on their properties:

```
<DataElement xmlns="http://hl7.org/fhir">
  <id value="[LOINC code]"/>
  <url value="http://loinc.org/fhir/DataElement/[LOINC code]"/>
  <version value="{LOINC version number]"/>  <!-- though this is not required -->
  <status value="[derived from STATUS]"/>
  <experimental value="false"/>
  <date value="[last changed date]"/>
  <publisher value="http://loinc.org"/>
  <title value="[display]"/>
  <copyright value="This content LOINC® is copyright © 1995 Regenstrief Institute, Inc.
      and the LOINC Committee, and available at no cost under the license at
      http://loinc.org/terms-of-use"/>
  <stringency value="comparable"/>
  <element>
    <!-- if type is Qn or OrdQn -->
    <extension url="http://hl7.org/fhir/StructureDefinition/elementdefinition-allowedUnits">
      <valueCodeableConcept>
        <coding>
```

```
        <system value="http://unitsofmeasure.org"/>
        <!-- ? just example?- need a canonical extension? -->
        <code value="[EXAMPLE_UCUM_UNITS]"/>
      </coding>
    </valueCodeableConcept>
  </extension>
  <path value="[LOINC code]"/>
  <short value="[display]"/>
  <definition value="[definition]"/>
  <min value="0"/>
  <max value="1"/>
  <type>
    <code value="[mapped type - see below]"/>
  </type>
  <!-- if this is a LOINC question with linked answers -->
  <binding>
    <strength value="required"/>
    <valueSetUri value="http://loinc.org/vs/[linked answer list code]"/>
  </binding>
 </element>
</DataElement>
```

The canonical URL http://loinc.org/fhir/DataElement/[LOINC code] can be used to refer to Data Elements defined by LOINC such as e.g. in Questionnaire.item.definition.

The appropriate type is determined by mapping from the LOINC specified SCALE_TYP for v3 to FHIR using this table:

SCALE_TYP | FHIR data type
Qn | Quantity
Ord | CodeableConcept
OrdQn | Quantity and CodeableConcept (e.g. both in the data element; either is allowed)
Nom | CodeableConcept (and string?)
Nar | markdown (?)
Multi | Attachment
Doc | Attachment

4.2.4 Using UCUM with FHIR

URL: https://hl7.org/fhir/STU3/ucum.html

This page is part of the FHIR Specification (v3.0.2: STU 3). The current version which supercedes this version is 4.0.1. For a full list of available versions, see the Directory of published versions

4.2.4 Using UCUM with FHIR

Vocabulary Work Group | Maturity Level: 5 | Ballot Status: Trial Use

The Units of Measure Coding System (UCUM) is recommended for use with the Quantity data type.

4.2.4.1 Summary

Source | UCUM is made available by the Regenstrief Institute, Inc and The UCUM Organization at http://unitsofmeasure.org
System | The URI http://unitsofmeasure.org identifies UCUM codes
Version | Where a version is used, it should be the standard UCUM version e.g. 1.9. There is no need to use version in the Coding data type, only in Value sets that use UCUM codes
Code | Valid expressions using the case sensitive symbols
Display | There is no defined display; the UCUM code is used directly for the display
Inactive | A few codes in UCUM are marked as deprecated (e.g. ppb, pptr)
Subsumption | No Subsumption relationships are defined by UCUM
Filter Properties | Two filter properties are defined as described below

4.2.4.2 Copyright

UCUM is Copyright © 1999-2013 Regenstrief Institute, Inc. and The UCUM Organization, Indianapolis, IN. All rights reserved. See TermsOfUse for details.

4.2.4.3 UCUM Filter Properties

This section documents the property filters that can be used with the UCUM code system in value set composition statements.

4.2.4.3.1 Property filter

Description | Restricts the expression to a describe a particular UCUM base property
Property Name | property
Operations Allowed | =
Values Allowed | [string name of property]
Comments | Restricts expressions to any expression that is comparable to a base unit with a matching property value. Note: this does not match the property on units, only base units

4.2.4.3.2 Canonical Filter

Description | Allows for any expression that is comparable to the named unit

Property Name | canonical
Operations Allowed | = / in
Values Allowed | UCUM expression
Comments | This allows any expression that is comparable to the given unit(s)

4.2.4.4 Implicit Value Sets

Implicit value sets are those whose specification can be predicted based on the grammar of the underlying code system, and the known structure of the URL that refers to them. There is one set of implicit value sets defined for UCUM: By Canonical Value.

If any value set resources exist with an identifier that conforms to the URL patterns specified below, the content of the resource must conform to the template provided. Profiles and other value set references are allowed to reference these value sets directly.

The value set identifier http://unitsofmeasure.org/vs is a value set that contains all UCUM codes.

4.2.4.4.1 UCUM Comparable Value Set

A value set with an identifier of "http://unitsofmeasure.org/vs/[expression]" must conform to this template, where [expression] is a valid UCUM expression:

```
<ValueSet xmlns="http://hl7.org/fhir">
  <text>
    <status value="generated"/>
    <div xmlns="http://www.w3.org/1999/xhtml">
      [some html that identifies that this value set
      includes all UCUM expressions that are comparable to the provided expression]
    </div>
  </text>
  <identifier value="http://unitsofmeasure.org/vs/[expression]"/>
  <version value="[optional - but recommended - UCUM version]"/>
  <name value="Ucum Expressions comparable to [expression]"/>
  <description value="Ucum Expressions comparable to [expression]"/>
  <status value="active"/>
  <date value="[optional date of UCUM release]"/>
  <compose>
    <include>
      <system value="http://unitsofmeasure.org"/>
      <filter>
        <property value="comparable"/>
        <op value="="/>
        <value value="[expression]"/>
      </filter>
    </include>
  </compose>
</ValueSet>
```

4.2.5 Using the NCI Metathesaurus with FHIR

URL: https://hl7.org/fhir/STU3/ncimeta.html

This page is part of the FHIR Specification (v3.0.2: STU 3). The current version which supercedes this version is 4.0.1. For a full list of available versions, see the Directory of published versions

4.2.5 Using the NCI Metathesaurus with FHIR

Vocabulary Work Group | Maturity Level: 2 | Ballot Status: Trial Use

4.2.5.1 Summary

Source | NCI Metathesaurus the NCI Center for Biomedical Informatics and Information Technology (CBIIT)
System | The URI http://ncimeta.nci.nih.gov identifies the NCI Metathesaurus
Version | There is no version or versioning associated with the NCI metathesaurus
Code | The Concept Unique Identifier (CUI) is used for the code value for a Metathesaurus concept
Display | The name should be used as the display for English usage (e.g. "Aerosol Dose Form" for CUI C1112870)
Inactive | Todo: Describe how it is determined which concepts are inactive
Subsumption | No Subsumption relationships are defined for the NCI Metathesaurus
Filter Properties | None are described yet

4.2.5.2 Version Issues

There are no staged releases of the NCI metathesaurus, so there is no versioning policy.

4.2.5.3 Copyright/License Issues

The NCI metathesaurus is in the public domain, so there are no copyright notices needed in value sets that refer to NCI metathesaurus concepts, and there are no licensing requirements limiting use of NCI metathesaurus concepts in instances or systems.

4.2.5.4 MCI Metathesaurus MySQL Database

Like RxNorm, the RRF files that are the distributed source of the NCI Metathesaurus can be used to populate a MySQL database that contains the data. This page provides SQL statements that describe how to implement the features of the NCI

Metathesaurus correctly against this database. They are provided only for implementer convenience, and do not imply that any particular approach must be used in implementations. (Note: for consistency, the RxNorm table and column names are used and the CUIs are 1 character longer, so the scripts must be updated).

For example, the correct display name for a CUI is

```
select STR from rxnconso where RXCUI = :code and SAB = 'RXNORM' and TTY <> 'SY'
```

4.2.5.5 NCI metathesaurus Filter Properties

This section documents the property filters that can be used with the RxNorm code system in value set composition statements.

The base SQL statement for returning a list of CUIs that conform to these filters is:

```
select RXCUI from RXNCONSO where SAB = 'RXNORM' and TTY <> 'SY'
```

4.2.5.5.1 Semantic Type

Description | Allows for selection of a set of CUIs based on their Semantic Type
Property Name | STY
Operations Allowed | = / in
Values Allowed | [column:]value
Comments | If a column is not specified, the default is TUI
SQL | and RXCUI in (select RXCUI from RXNSTY where [:column] = :value)

4.2.5.5.2 Source

Description | Allows for selection of the set of concepts that have mappings to a particular RxNorm source
Property Name | SAB
Operations Allowed | = / in
Values Allowed | Values from the SAB table (e.g. select RSAB from RXNsab)
SQL | and RXCUI in (select RXCUI from RXNconso where SAB = :value)

4.2.5.5.3 Term Type

Description | Allows for selection of a concept based on its designated type
Property Name | TTY
Operations Allowed | = / in
Values Allowed | TTY values from the RxNorm Concept table (e.g. select distinct TTY from rxnconso)
SQL | and TTY = :value

4.2.5.5.4 Relationship

Description | Allows for selection of a concept based on its relationships
Property Name | [REL]
Operations Allowed | = / in
Values Allowed | CUI:[RXCUI] or AUI:[RXAUI] must be a valid CUI or AUI. Note that a CUI does not need to have a SAB=RXNORM entry to be used here
Comments | [REL] (:rel) is one of AQ, CHD, PAR, QB, RB, RN, RO, RQ, SIB or SY
SQL | for CUI: and (RXCUI in (select RXCUI from rxnconso where RXCUI in (select RXCUI1 from rxnrel where REL = :rel and RXCUI2 = :value)) for AUI: and (RXCUI in (select RXCUI from rxnconso where RXAUI in (select RXAUI1 from rxnrel where REL = :rel and RXAUI2 = :value))

4.2.5.5.5 Relationship Type

Description | Allows for selection of a concept based on the type of its relationships
Property Name | [RELA]
Operations Allowed | = / in
Values Allowed | CUI:[RXCUI] or AUI:[RXAUI] must be a valid CUI or AUI. Note that a CUI does not need to have a SAB=RXNORM entry to be used here
Comments | [RELA] (:rela) is one of the relationship types listed in the NCI file "Relationships_Help_Page.txt" - the current list (nearly 1000 types) is at the end of the page
SQL | for CUI: and (RXCUI in (select RXCUI from rxnconso where RXCUI in (select RXCUI1 from rxnrel where RELA = :rel and RXCUI2 = :value)) for AUI: and (RXCUI in (select RXCUI from rxnconso where RXAUI in (select RXAUI1 from rxnrel where RELA = :rel and RXAUI2 = :value))

4.2.5.6 Implicit Value Sets

This section needs investigation

4.2.5.7 Current NCI Metathesaurus relationship types

* 3_UTR_of
* 5_UTR_of
* Abnormal_Cell_Affected_By_Chemical_Or_Drug
* Abnormality_Associated_With_Allele
* Abstract_of
* access_device_used_by
* access_of

* action_of
* active_ingredient_of
* active_metabolites_of
* Activity_Of_Allele
* adheres_to
* adjacent_to
* afferent_to
* agent_in
* alias_of
* Allele_Absent_From_Wild-type_Chromosomal_Location
* Allele_Has_Abnormality
* Allele_Has_Activity
* Allele_In_Chromosomal_Location
* Allele_of
* Allele_Plays_Altered_Role_In_Process
* Allele_Plays_Role_In_Metabolism_Of_Chemical_Or_Drug
* allelic_variant_of
* Amino_Acid_Variant_of
* analyzed_by
* analyzes
* Anatomic_Structure_Has_Location
* Anatomic_Structure_Is_Physical_Part_Of
* anatomical_site
* Anatomy_Originated_From_Biological_Process
* Aneuploidy_Addition_of
* Aneuploidy_Deletion_of
* anterior_to
* application_of
* Arm_Location_of
* Arm_of
* arterial_supply_of
* articulates_with
* associated_disease
* associated_finding_of
* associated_genetic_condition
* associated_morphology_of
* associated_procedure_of
* associated_with
* Associated_With_Malfunction_Of_Gene_Product
* attaches_to
* attributed_constitutional_part_of
* attributed_continuous_with
* attributed_part_of
* attributed_regional_part_of
* Author_of
* Band_Location_of
* Band_of
* bearer_of
* Biological_Process_Has_Associated_Location
* Biological_Process_Has_Initiator_Chemical_Or_Drug
* Biological_Process_Has_Initiator_Process
* Biological_Process_Has_Result_Anatomy

* Biological_Process_Has_Result_Biological_Process
* Biological_Process_Has_Result_Chemical_Or_Drug
* Biological_Process_Involves_Chemical_Or_Drug
* Biological_Process_Involves_Gene_Product
* Biological_Process_Is_Part_Of_Process
* Biological_Process_Results_From_Biological_Process
* Biomarker_Type_Includes_Gene
* Biomarker_Type_Includes_Gene_Product
* blood_supply_of
* bounded_by
* bounds
* branch_of
* branch_part_of
* causative_agent_of
* cause_of
* cell_connecting_part_of
* cell_shape_of
* cell_surface_specialization_of
* Cell_Type_Is_Associated_With_EO_Disease
* Cell_Type_Or_Tissue_Affected_By_Chemical_Or_Drug
* Centromere_of
* CH3_Status_of
* Chemical_Or_Drug_Affects_Abnormal_Cell
* Chemical_Or_Drug_Affects_Cell_Type_Or_Tissue
* Chemical_Or_Drug_Affects_Gene_Product
* Chemical_Or_Drug_Has_Mechanism_Of_Action
* Chemical_Or_Drug_Has_Physiologic_Effect
* Chemical_Or_Drug_Initiates_Biological_Process
* Chemical_Or_Drug_Is_Metabolized_By_Enzyme
* Chemical_Or_Drug_Is_Product_Of_Biological_Process
* Chemical_Or_Drug_Metabolism_Is_Associated_With_Allele
* Chemical_Or_Drug_Plays_Role_In_Biological_Process
* chemical_structure_of
* Chemotherapy_Regimen_Has_Component
* Chromosomal_Location_of
* Chromosomal_Location_Of_Allele
* Chromosomal_Location_of_Wild-type_Gene
* Chromosomal_Structural_Variant
* Chromosome_Involved_In_Cytogenetic_Abnormality
* Chromosome_Mapped_To_Disease
* class_code_classified_by
* classified_as
* classifies
* classifies_class_code
* clinical_course_of
* common_name_of
* Completely_Excised_Anatomy_Has_Procedure
* Completely_Excised_Anatomy_May_Have_Procedure
* Complex_Has_Physical_Part
* component_of
* Concept_In_Subset
* conceptual_part_of

* conjugate_component_of
* consider
* consider_from
* consists_of
* Constituent_Amino_Acid_of
* Constituent_Element_of
* Constituent_Protein_of
* Constituent_Variant_of
* constitutes
* constitutional_part_of
* contained_in
* contains
* context_binding_of
* continuation_branch_of
* continuous_with
* continuous_with_distally
* continuous_with_proximally
* contraindicated_with_disease
* contraindicating_class_of
* contraindicating_mechanism_of_action_of
* contraindicating_physiologic_effect_of
* Cytogenetic_Abnormality_Involves_Chromosome
* Data_Element_Of
* definitional_manifestation_of
* degree_of
* Deleted_Region_End_Band
* Deleted_Region_Start_Band
* denoted_by
* denotes
* dependent_of
* derivatized_to
* derives_from
* determines_parameter_for
* determines_property
* develops_from
* device_used_by
* diagnosed_by
* diagnoses
* direct_device_of
* direct_morphology_of
* direct_procedure_site_of
* direct_substance_of
* Disease_Excludes_Abnormal_Cell
* Disease_Excludes_Cytogenetic_Abnormality
* Disease_Excludes_Finding
* Disease_Excludes_Molecular_Abnormality
* Disease_Excludes_Normal_Cell_Origin
* Disease_Excludes_Normal_Tissue_Origin
* Disease_Excludes_Primary_Anatomic_Site
* Disease_Has_Abnormal_Cell
* Disease_Has_Accepted_Treatment_With_Regimen
* Disease_Has_Associated_Anatomic_Site

* Disease_Has_Associated_Disease
* Disease_Has_Associated_Gene
* Disease_Has_Cytogenetic_Abnormality
* Disease_Has_Finding
* Disease_Has_Metastatic_Anatomic_Site
* Disease_Has_Molecular_Abnormality
* Disease_Has_Normal_Cell_Origin
* Disease_Has_Normal_Tissue_Origin
* Disease_Has_Primary_Anatomic_Site
* Disease_Is_Grade
* Disease_Is_Marked_By_Gene
* Disease_Is_Stage
* Disease_Mapped_To_Chromosome
* Disease_Mapped_To_Gene
* Disease_May_Have_Abnormal_Cell
* Disease_May_Have_Associated_Disease
* Disease_May_Have_Cytogenetic_Abnormality
* Disease_May_Have_Finding
* Disease_May_Have_Molecular_Abnormality
* Disease_May_Have_Normal_Cell_Origin
* Disease_Pathogenesis_Involves_Gene
* disease_with_contraindication
* distal_to
* DOI_of
* dose_form_of
* doseformgroup_of
* drains_into
* drug_contraindicated_for
* due_to
* Duplicated_Region_End_Band
* Duplicated_Region_Start_Band
* effect_may_be_inhibited_by
* Effect_of
* efferent_to
* encapsulated_component_of
* Encoded_by
* Encodes
* Endogenous_Product_Related_To
* energy_used_by
* entrapment_site_of
* entrapped_component_of
* entry_version_of
* Enzyme_Metabolizes_Chemical_Or_Drug
* EO_Anatomy_Is_Associated_With_EO_Disease
* EO_Disease_Has_Associated_Cell_Type
* EO_Disease_Has_Associated_EO_Anatomy
* EO_Disease_Has_Property_Or_Attribute
* EO_Disease_Maps_To_Human_Disease
* epithelial_cell_shape_of
* evaluation_of
* Excised_Anatomy_Has_Procedure
* Excised_Anatomy_May_Have_Procedure

* exhibited_by
* exhibits
* Exon_of
* expanded_form_of
* external_to
* fascicular_architecture_of
* Feature_of
* finding_context_of
* finding_informer_of
* finding_method_of
* finding_site_of
* focus_of
* form_of
* function_of
* Gene_Associated_With_Disease
* Gene_Encodes_Gene_Product
* Gene_Found_In_Organism
* Gene_Has_Abnormality
* Gene_Has_Physical_Location
* Gene_In_Chromosomal_Location
* Gene_Involved_In_Molecular_Abnormality
* Gene_Involved_In_Pathogenesis_Of_Disease
* Gene_Is_Biomarker_Of
* Gene_Is_Biomarker_Type
* Gene_Is_Element_In_Pathway
* Gene_Location_of
* Gene_Mapped_To_Disease
* Gene_Mutant_Encodes_Gene_Product_Sequence_Variation
* Gene_of
* Gene_Plays_Role_In_Process
* Gene_Product_Affected_By_Chemical_Or_Drug
* Gene_Product_Encoded_By_Gene
* Gene_Product_Expressed_In_Tissue
* Gene_Product_Has_Abnormality
* Gene_Product_Has_Associated_Anatomy
* Gene_Product_Has_Biochemical_Function
* Gene_Product_Has_Chemical_Classification
* Gene_Product_Has_Organism_Source
* Gene_Product_Has_Structural_Domain_Or_Motif
* Gene_Product_Is_Biomarker_Of
* Gene_Product_Is_Biomarker_Type
* Gene_Product_Is_Element_In_Pathway
* Gene_Product_Is_Physical_Part_Of
* Gene_Product_Malfunction_Associated_With_Disease
* Gene_Product_Plays_Role_In_Biological_Process
* Gene_Product_Sequence_Variation_Encoded_By_Gene_Mutant
* Genomic_Mutation_Of
* germ_origin_of
* gives_rise_to
* Has_3_UTR
* Has_5_UTR
* has_Abstract

* has_access
* has_action
* has_active_ingredient
* has_active_metabolites
* has_additive
* has_adherent
* has_affiliation
* has_agent
* has_alias
* Has_Allele
* has_allelic_variant
* Has_Amino_Acid_Variant
* Has_Aneuploidy_Addition
* Has_Aneuploidy_Deletion
* has_application
* Has_Arm
* Has_Arm_Location
* has_arterial_supply
* has_associated_finding
* has_associated_morphology
* has_associated_procedure
* has_atmospheric_component
* has_attributed_constitutional_part
* has_attributed_part
* has_attributed_regional_part
* has_Author
* Has_Band
* Has_Band_Location
* has_been_treated
* has_bioassay_data
* has_bioassays
* has_biomaterial_characteristics
* has_blood_supply
* has_branch
* has_branch_part
* has_cancer_site
* has_category
* has_causative_agent
* Has_CDRH_Parent
* has_cell_connecting_part
* has_cell_shape
* has_cell_surface_specialization
* Has_Centromere
* Has_CH3_Status
* has_chemical_structure
* has_chromosomal_aberration_classification
* Has_Chromosomal_Location
* has_citation
* has_clinical_course
* has_clinical_finding
* has_clinical_record
* has_clinical_treatment

* has_common_name
* has_component
* has_component_part
* has_compound
* has_conceptual_part
* has_conjugated_component_part
* Has_Constituent_Amino_Acid
* Has_Constituent_Element
* Has_Constituent_Protein
* Has_Constituent_Variant
* has_constitutional_part
* has_context_binding
* has_continuation_branch
* has_contraindicated_drug
* has_contraindicating_class
* has_contraindicating_mechanism_of_action
* has_contraindicating_physiologic_effect
* has_cubic_volume
* Has_Data_Element
* has_database
* has_database_entry_type
* has_datum_value
* has_definitional_manifestation
* has_degree
* has_dependent
* has_diameter
* has_direct_device
* has_direct_morphology
* has_direct_procedure_site
* has_direct_substance
* has_disease_location
* has_disease_staging
* has_disease_state
* has_DOI
* has_donor
* has_dose_form
* has_doseformgroup
* Has_Effect
* has_encapsulated_component_part
* has_endpoint_of_measurement
* has_entrapment_site
* has_entrapped_component_part
* has_entry_version
* has_epithelial_cell_shape
* has_evaluation
* Has_Exon
* has_expanded_form
* has_experiment_design
* has_experiment_design_type
* has_experiment_factors
* has_factor_value
* has_factor_value_ontology_entry

* has_family_member
* has_family_relationship
* has_fascicular_architecture
* Has_Feature
* has_feature_shape
* has_fiducials
* has_finding_context
* has_finding_informer
* has_finding_method
* has_finding_site
* has_focus
* has_form
* Has_Free_Acid_Or_Base_Form
* has_function
* Has_Gene
* Has_Gene_Location
* Has_Gene_Product_Element
* Has_Genomic_Mutation
* has_germ_origin
* has_hardware
* has_height
* has_host
* has_host_part
* has_identification_type
* has_image_format
* has_indicator
* has_indirect_device
* has_indirect_morphology
* has_indirect_procedure_site
* has_individual
* has_individual_genetic_characteristics
* has_ingredient
* has_ingredients
* has_inherent_3d_shape
* has_inheritance_type
* has_initial_time_point
* has_innervation_source
* has_input_participant
* has_insertion
* has_integral_part
* has_intent
* has_interpretation
* Has_Intron
* has_Journal_Name
* has_laterality
* has_length
* has_location
* has_lymphatic_drainage
* has_MAGE_description
* has_manifestation
* has_manufacturer
* has_mapping_qualifier

* has_mass
* Has_Maternal_Uniparental_Disomy
* has_maximum_measurement
* has_measure
* has_measurement
* has_measurement_method
* has_measurement_type
* has_mechanism_of_action
* has_member
* has_method
* Has_Mode_of_Inheritance
* has_multi_level_category
* has_muscle_attachment
* has_muscle_insertion
* has_muscle_origin
* has_nerve_supply
* Has_NICHD_Parent
* has_node_value
* has_node_value_type
* has_nodes
* Has_Nucleotide_Repeat
* Has_Nucleotide_Variant
* has_nutrient_component
* has_occurrence
* has_organism_part
* has_orientation
* has_origin
* has_output_participant
* has_owner
* has_owning_affiliate
* has_owning_section
* has_owning_subsection
* has_parent_organization
* has_part
* has_part_modified
* has_participant
* Has_Paternal_Uniparental_Disomy
* has_pathological_process
* has_performer
* has_permuted_term
* has_pharmacokinetics
* Has_Physical_Part_Of_Anatomic_Structure
* has_physical_state
* has_physiologic_effect
* has_precise_ingredient
* has_primary_segmental_supply
* has_print_name
* has_prior_disease_state
* has_priority
* has_procedure_context
* has_procedure_device
* has_procedure_morphology

* has_procedure_site
* has_product_component
* has_property
* has_property_set
* has_protocol
* has_providers
* has_Publication_Year
* has_PubMedID
* has_quality
* has_quantified_form
* has_reason_for_deprecation
* has_recipient_category
* has_regional_part
* has_result
* has_revision_status
* has_role
* has_route_of_administration
* Has_RT_Product
* Has_Salt_Form
* has_scale
* has_scale_type
* has_secondary_segmental_supply
* has_segment
* has_segmental_composition
* has_segmental_supply
* has_severity
* has_shape
* has_single_level_category
* has_software
* has_sort_version
* has_species
* has_specimen
* has_specimen_procedure
* has_specimen_source_identity
* has_specimen_source_morphology
* has_specimen_source_topography
* has_specimen_substance
* has_subject_relationship_context
* Has_Subset
* has_supported_concept_property
* has_supported_concept_relationship
* has_surgical_approach
* has_systemic_part
* Has_Target
* Has_Telomere
* has_temperature_condition
* has_temporal_context
* has_test_result
* has_test_type
* has_therapeutic_class
* has_time_period
* has_tradename

* Has_Transcript
* has_treatment
* has_tributary
* has_type
* has_unit
* has_unit_of_measure
* has_units
* has_URI
* has_venous_drainage
* has_version
* Human_Disease_Maps_To_EO_Disease
* Human_Sex_Determinant
* icd_dagger
* identification_type_of
* Imaged_Anatomy_Has_Procedure
* included_in
* includes
* indicator_of
* indirect_device_of
* indirect_morphology_of
* indirect_procedure_site_of
* induced_by
* induces
* inferior_to
* ingredient_of
* ingredients_of
* inherence_for
* inherent_3d_shape_of
* inheres_in
* inheritance_type_of
* innervates
* insertion_of
* instrument_used_by
* intent_of
* internal_to
* interpretation_of
* interprets
* Intron_of
* INV_Chromosomal_Structural_Variant
* INV_Deleted_Region_End_Band
* INV_Deleted_Region_Start_Band
* INV_Duplicated_Region_End_Band
* INV_Duplicated_Region_Start_Band
* INV_Human_Sex_Determinant
* INV_Inverted_Region_End_Band
* INV_Inverted_Region_End_Exon
* INV_Inverted_Region_End_Gene
* INV_Inverted_Region_End_UTR
* INV_Inverted_Region_Start_Band
* INV_Inverted_Region_Start_Exon
* INV_Inverted_Region_Start_Gene
* INV_Inverted_Region_Start_Intron

* INV_Involves
* INV_Isochromosome_Origin
* INV_Karyotype_Class
* INV_Source_Band
* INV_Source_Exon
* INV_Source_Gene
* INV_Source_Intron
* INV_Target_Band
* INV_Target_Exon
* INV_Target_Gene
* INV_Target_Intron
* inverse_has_additive
* inverse_has_affiliation
* inverse_has_atmospheric_component
* inverse_has_been_treated
* inverse_has_bioassay_data
* inverse_has_bioassays
* inverse_has_biomaterial_characteristics
* inverse_has_cancer_site
* inverse_has_category
* inverse_has_chromosomal_aberration_classification
* inverse_has_citation
* inverse_has_clinical_finding
* inverse_has_clinical_record
* inverse_has_clinical_treatment
* inverse_has_compound
* inverse_has_cubic_volume
* inverse_has_database
* inverse_has_database_entry_type
* inverse_has_diameter
* inverse_has_disease_location
* inverse_has_disease_staging
* inverse_has_disease_state
* inverse_has_donor
* inverse_has_experiment_design
* inverse_has_experiment_design_type
* inverse_has_experiment_factors
* inverse_has_factor_value
* inverse_has_factor_value_ontology_entry
* inverse_has_family_member
* inverse_has_family_relationship
* inverse_has_feature_shape
* inverse_has_fiducials
* inverse_has_hardware
* inverse_has_height
* inverse_has_host
* inverse_has_host_part
* inverse_has_image_format
* inverse_has_individual
* inverse_has_individual_genetic_characteristics
* inverse_has_initial_time_point
* inverse_has_length

* inverse_has_MAGE_description
* inverse_has_manufacturer
* inverse_has_mass
* inverse_has_maximum_measurement
* inverse_has_measurement_type
* inverse_has_node_value
* inverse_has_node_value_type
* inverse_has_nodes
* inverse_has_nutrient_component
* inverse_has_organism_part
* inverse_has_owner
* inverse_has_parent_organization
* inverse_has_part_modified
* inverse_has_performer
* inverse_has_prior_disease_state
* inverse_has_property_set
* inverse_has_protocol
* inverse_has_providers
* inverse_has_reason_for_deprecation
* inverse_has_software
* inverse_has_species
* inverse_has_test_result
* inverse_has_test_type
* inverse_has_treatment
* inverse_has_type
* inverse_has_units
* inverse_has_URI
* inverse_isa
* inverse_was_tested_for
* Inverted_Region_End_Band
* Inverted_Region_End_Exon
* Inverted_Region_End_Gene
* Inverted_Region_End_UTR
* Inverted_Region_Start_Band
* Inverted_Region_Start_Exon
* Inverted_Region_Start_Gene
* Inverted_Region_Start_Intron
* Involves
* Is_Abnormal_Cell_Of_Disease
* Is_Abnormality_Of_Gene
* Is_Abnormality_Of_Gene_Product
* is_anatomical_site_of
* Is_Associated_Anatomic_Site_Of
* Is_Associated_Anatomy_Of_Gene_Product
* Is_Associated_Disease_Of
* Is_Biochemical_Function_Of_Gene_Product
* is_borne_by
* Is_Chemical_Classification_Of_Gene_Product
* Is_Chromosomal_Location_Of_Gene
* Is_Component_Of_Chemotherapy_Regimen
* Is_Cytogenetic_Abnormality_Of_Disease
* is_datum_of

* Is_Finding_Of_Disease
* Is_Grade_Of_Disease
* is_integral_part_of
* is_interpreted_by
* Is_Location_Of
* Is_Location_Of_Anatomic_Structure
* Is_Location_Of_Biological_Process
* Is_Marked_By_Gene_Product
* is_measurement_endpoint_of
* Is_Mechanism_Of_Action_Of_Chemical_Or_Drug
* Is_Metastatic_Anatomic_Site_Of_Disease
* Is_Molecular_Abnormality_Of_Disease
* Is_Normal_Cell_Origin_Of_Disease
* Is_Normal_Tissue_Origin_Of_Disease
* Is_Not_Abnormal_Cell_Of_Disease
* Is_Not_Cytogenetic_Abnormality_Of_Disease
* Is_Not_Finding_Of_Disease
* Is_Not_Molecular_Abnormality_Of_Disease
* Is_Not_Normal_Cell_Origin_Of_Disease
* Is_Not_Normal_Tissue_Origin_Of_Disease
* Is_Not_Primary_Anatomic_Site_Of_Disease
* Is_Organism_Source_Of_Gene_Product
* Is_Physical_Location_Of_Gene
* Is_Physiologic_Effect_Of_Chemical_Or_Drug
* Is_Primary_Anatomic_Site_Of_Disease
* Is_Property_Or_Attribute_Of_EO_Disease
* Is_Qualified_By
* is_realized_in
* Is_Related_To_Endogenous_Product
* Is_Stage_Of_Disease
* Is_Structural_Domain_Or_Motif_Of_Gene_Product
* Is_Target_Of_Agent
* is_temperature_of
* is_time_period_of
* isa
* Isochromosome_Origin
* Journal_Name_of
* Karyotype_Class
* Kind_Is_Domain_Of
* Kind_Is_Range_Of
* larger_than
* laterality_of
* location_of
* lymphatic_drainage_of
* manifestation_of
* mapped_from
* mapped_to
* mapping_qualifier_of
* Maternal_Uniparental_Disomy_of
* May_Be_Abnormal_Cell_Of_Disease
* May_Be_Associated_Disease_Of_Disease
* may_be_caused_by

* May_Be_Cytogenetic_Abnormality_Of_Disease
* may_be_diagnosed_by
* May_Be_Finding_Of_Disease
* May_Be_Molecular_Abnormality_Of_Disease
* May_Be_Normal_Cell_Origin_Of_Disease
* may_be_prevented_by
* may_be_qualified_by
* may_be_treated_by
* may_cause
* may_diagnose
* may_inhibit_effect_of
* may_prevent
* may_qualify
* may_treat
* measure_of
* measured_by
* measurement_method_of
* measurement_of
* measures
* mechanism_of_action_of
* member_of
* metabolic_site_of
* method_of
* modality_is_related_to
* Mode_of_Inheritance
* Molecular_Abnormality_Involves_Gene
* mth_british_form_of
* mth_expanded_form_of
* mth_has_british_form
* mth_has_expanded_form
* mth_has_plain_text_form
* mth_has_xml_form
* mth_plain_text_form_of
* mth_xml_form_of
* muscle_attachment_of
* muscle_insertion_of
* muscle_origin_of
* Negative_Protein_Expression
* Negatively_Expressed_By
* negatively_regulated_by
* negatively_regulates
* nerve_supply_of
* Nucleotide_Repeat_of
* Nucleotide_Variant_of
* occurs_after
* occurs_before
* occurs_in
* Organism_Has_Gene
* orientation_of
* origin_of
* owning_affiliate_of
* owning_section_of

* owning_subsection_of
* parameter_determined_from
* Parent_Is_CDRH
* Parent_Is_NICHD
* part_component_of
* part_of
* Partially_Excised_Anatomy_Has_Procedure
* Partially_Excised_Anatomy_May_Have_Procedure
* participates_in
* Paternal_Uniparental_Disomy_of
* pathological_process_of
* Pathway_Has_Gene_Element
* permuted_term_of
* pharmacokinetics_of
* physical_state_of
* physiologic_effect_of
* Positive_Protein_Expression
* Positively_Expressed_By
* positively_regulated_by
* positively_regulates
* posterior_to
* precise_ingredient_of
* primary_segmental_supply_of
* print_name_of
* priority_of
* procedure_context_of
* procedure_device_of
* Procedure_Has_Completely_Excised_Anatomy
* Procedure_Has_Excised_Anatomy
* Procedure_Has_Imaged_Anatomy
* Procedure_Has_Partially_Excised_Anatomy
* Procedure_Has_Target_Anatomy
* Procedure_May_Have_Completely_Excised_Anatomy
* Procedure_May_Have_Excised_Anatomy
* Procedure_May_Have_Partially_Excised_Anatomy
* procedure_morphology_of
* procedure_site_of
* Process_Altered_By_Allele
* Process_Includes_Biological_Process
* Process_Initiates_Biological_Process
* Process_Involves_Gene
* product_component_of
* projects_from
* projects_to
* projects_towards
* property_determined_from
* property_of
* proximal_to
* Publication_Year_of
* PubMedID_of
* Qualifier_Applies_To
* quality_of

* quantified_form_of
* reagent_used_in
* realizes
* receives_attachment
* receives_drainage_from
* receives_input_from
* receives_projection_from
* recipient_category_of
* reformulated_to
* reformulation_of
* Regimen_Has_Accepted_Use_For_Disease
* regional_part_of
* regulated_by
* regulates
* related_modality
* related_to
* replaced_by
* replaces
* responsive_to_stimulus
* result_of
* result_of_regulation
* results_in
* revision_status_of
* Role_Has_Domain
* Role_Has_Parent
* Role_Has_Range
* Role_Is_Parent_Of
* role_of
* route_of_administration_of
* RT_Product_of
* scale_of
* scale_type_of
* secondary_segmental_supply_of
* see
* see_from
* Segment_of
* segmental_composition_of
* segmental_supply_of
* sends_output_to
* severity_of
* shape_of
* sib_in_branch_of
* sib_in_isa
* sib_in_part_of
* sib_in_tributary_of
* site_of_metabolism
* smaller_than
* sort_version_of
* Source_Band
* Source_Exon
* Source_Gene
* Source_Intron

* specifies_value
* specimen_of
* specimen_procedure_of
* specimen_source_identity_of
* specimen_source_morphology_of
* specimen_source_topography_of
* specimen_substance_of
* stimulus_causes_response
* subject_relationship_context_of
* Subset_Includes_Concept
* Subset_of
* substance_used_by
* Subsumed_By
* Subsumes
* superior_to
* supported_concept_property_in
* supported_concept_relationship_in
* surgical_approach_of
* surrounded_by
* surrounds
* systemic_part_of
* Target_Anatomy_Has_Procedure
* Target_Band
* Target_Exon
* Target_Gene
* Target_Intron
* technique_used_for
* Telomere_of
* temporal_context_of
* therapeutic_class_of
* Tissue_Is_Expression_Site_Of_Gene_Product
* tradename_of
* Transcript_of
* treated_by
* treats
* tributary_of
* unit_of
* unit_of_measurement_of
* use
* used_by
* used_for
* uses
* uses_access_device
* uses_device
* uses_energy
* uses_instrument
* uses_reagent
* uses_substance
* uses_technique
* value_specified_at
* venous_drainage_of
* version_of

* was_tested_for

4.2.6 Using NDF-RT (the National Drug File - Reference Terminology) with FHIR

URL: https://hl7.org/fhir/STU3/ndfrt.html

This page is part of the FHIR Specification (v3.0.2: STU 3). The current version which supercedes this version is 4.0.1. For a full list of available versions, see the Directory of published versions

4.2.6 Using NDF-RT (the National Drug File - Reference Terminology) with FHIR

Vocabulary Work Group | Maturity Level: 2 | Ballot Status: Trial Use

4.2.6.1 Summary

Source | the National Drug File - Reference Terminology - prepared by Veterans Health Administration , and distributed as part of UMLS by the NLM (direct link)
System | The URI to identify NDF-RT is not resolved. As a temporary arrangement, the URL "http://hl7.org/fhir/ndfrt" is to be used
Version | A version is not needed. (Use the date of the UMLS release for the version of NDF-RT if a version is desired.)
Code | The NUI is used for the code value for an NDF-RT concept
Display | ??
Inactive | Todo: Describe how it is determined which concepts are inactive
Subsumption | Subsumption testing is based in the Is-a relationship defined by NDFRT
Filter Properties | None are described yet

This URL is temporary while the NDF-RT and FHIR teams discuss the long term arrangements. Further documentation can be found in evs .

4.2.6.2 Version Issues

NDF-RT is released as part of UMLS. Therefore, each successive release has the date of the UMLS release as its version.

4.2.6.3 Copyright/License Issues

NDF-RT has no copyright acknowledgement required. However, users must adhere to the UMLS license.

4.2.6.4 NDF-RT Filter Properties

This section documents the property filters that can be used with the SNOMED CT code system in value set composition statements.

4.2.6.4.1 By Subsumption

Description | Select a set of concepts based on subsumption testing
Property Name | concept
Operations Allowed | is-a
Values Allowed | NUI
Comments | Includes all concepts that have a transitive is-a relationship with the concept Id provided in the value as an NUI (including the concept itself)

Others yet to be done.

4.2.6.5 Implicit Value Sets

Yet to be done.

4.2.7 Using Unique Ingredient Identifier (UNII) with FHIR

URL: https://hl7.org/fhir/STU3/unii.html

This page is part of the FHIR Specification (v3.0.2: STU 3). The current version which supercedes this version is 4.0.1. For a full list of available versions, see the Directory of published versions

4.2.7 Using Unique Ingredient Identifier (UNII) with FHIR

Vocabulary Work Group | Maturity Level: 3 | Ballot Status: Trial Use

4.2.7.1 Summary

Source | FDA Substance Registration System
System | The URI to identify UNII codes is http://fdasis.nlm.nih.gov
Version | If it is desired to exchange the version, use the date of the file in the UNII list download in the format YYYYMMDD
Code | Use the value of the UNII column in the UNII List
Display | Use the value of the PT (Preferred Term) column in the UNII List
Inactive | Todo: Describe how it is determined which concepts are inactive
Subsumption | No Subsumption relationships are defined by UNII
Filter Properties | None are described yet

4.2.7.2 Version Issues

To be investigated

4.2.7.3 Copyright/License Issues

UNII has no copyright acknowledgement needed, nor are there any license terms to adhere to.

4.2.7.4 NDF-RT Filter Properties

No need for filters identified yet.

4.2.7.5 Implicit Value Sets

No need for implicit value sets identified yet.

4.2.8 Using CVX (Vaccine Administered) with FHIR

URL: https://hl7.org/fhir/STU3/cvx.html

This page is part of the FHIR Specification (v3.0.2: STU 3). The current version which supercedes this version is 4.0.1. For a full list of available versions, see the Directory of published versions

4.2.8 Using CVX (Vaccine Administered) with FHIR

Vocabulary Work Group | Maturity Level: 3 | Ballot Status: Trial Use

4.2.8.1 Summary

Source | Available at http://www2a.cdc.gov/vaccines/iis/iisstandards/vaccines.asp?rpt=cvx . Developed by The CDC's National Center of Immunization and Respiratory Diseases (NCIRD)
System | The URI to identify CVX codes is http://hl7.org/fhir/sid/cvx
Version | If it is desired to exchange the version, use the date of the last updated code in the format YYYYMMDD
Code | Use the value of "CVX Code" column in the web page
Display | Use the value of the "Short Description" column in the web page
Inactive | Todo: Describe how it is determined which concepts are inactive
Subsumption | No Subsumption relationships are defined by CVX
Filter Properties | None are described yet

4.2.8.2 Version Issues

If it is desired to exchange the version, use the date of the last updated code in the format YYYYMMDD.

4.2.8.3 Copyright/License Issues

CVX has no copyright acknowledgement needed, nor are there any license terms to adhere to.

4.2.8.4 CVX Filter Properties

No need for filters identified yet.

4.2.8.5 Implicit Value Sets

No need for implicit value sets identified yet.

4.2.9 Using CPT with FHIR

URL: https://hl7.org/fhir/STU3/cpt.html

This page is part of the FHIR Specification (v3.0.2: STU 3). The current version which supercedes this version is 4.0.1. For a full list of available versions, see the Directory of published versions

4.2.9 Using CPT with FHIR

Vocabulary Work Group | Maturity Level: 2 | Ballot Status: Trial Use

4.2.9.1 Summary

Source | CPT is made managed by the American Medical Association
System | The URI http://www.ama-assn.org/go/cpt identifies the CPT code system
Version | Where a version is appropriate, use the year of release e.g. 2014
Code | "Code" in the CPT tables (a 5-character code)
Display | "Description" in the CPT tables
Inactive | Todo: Describe how it is determined which concepts are inactive
Subsumption | No Subsumption relationships are defined by CPT
Filter Properties | None defined

4.2.9.2 Version Issues

CPT is released each October. CPT versions are identified simply by the year of their release.

4.2.9.3 Example Usage

```
<coding>
  <system value="http://www.ama-assn.org/go/cpt"/>
  <version value="2014"/>
```

```
    <code value="31502"/>
    <display value="Tracheotomy tube change prior to establishment of fistula tract"/>
  </coding>
```

4.2.9.4 Copyright/License Issues

CPT is a registered trademark of the American Medical Association. The AMA holds the copyright for the CPT coding system.

When Value Sets include CPT codes, the copyright element should include the text "CPT copyright 2014 American Medical Association. All rights reserved.".

4.2.9.5 CPT Filter Properties

No filter properties have been defined at this time.

4.2.9.6 Implicit Value Sets

The value set URL http://hl7.org/fhir/ValueSet/cpt-all is a value set that includes all CPT codes.

4.2.10 Using NDC and NHRIC Codes with FHIR

URL: https://hl7.org/fhir/STU3/ndc.html

This page is part of the FHIR Specification (v3.0.2: STU 3). The current version which supercedes this version is 4.0.1. For a full list of available versions, see the Directory of published versions

4.2.10 Using NDC and NHRIC Codes with FHIR

Vocabulary Work Group | Maturity Level: 2 | Ballot Status: Trial Use

The National Drug Codes (NDC) and National Health Related Items Code (NHRIC) codes are codes issued by the FDA for tracking drugs and devices. Note that the NHRIC codes are being replaced by the UDI system .

4.2.10.1 Summary

Source | National Drug Code Directory and the NHRIC Labeler Codes
System | The URI to identify NDC/NHRIC codes is http://hl7.org/fhir/sid/ndc
Version | Use YYYMMDD for the date of publication, but see note below
Code | The 10 digit NDC code, with "-" included. Note that different NDC codes have different positions for the "-": 1234-5678-90, 12345-6789-0, or 12345-678-90. The "-" must be correct for each NDC code
Display | Use the PACKAGEDESCRIPTION column value from the TSV or Excel distribution file
Inactive | Todo: Describe how it is determined which concepts are inactive
Subsumption | No Subsumption relationships are defined for the NDC codes
Filter Properties | None are described yet

4.2.10.2 Version Issues

The FDA published list of NDC codes for finished drug products is updated daily. Use the format YYYYMMDD to refer to a particular distribution. Note that while only valid NDC codes appear in the distribution file, there are other NDC codes that organizations have assigned but not yet reported to FDA. Therefore, the full set of NDCs that exists in the marketplace is unknown and cannot be versioned completely.

4.2.10.3 Copyright/License Issues

NDC codes have no copyright acknowledgment or license requirements.

4.2.10.4 NDF-RT Filter Properties

No need for filters identified yet.

4.2.10.5 Implicit Value Sets

No need for implicit value sets identified yet.

4.2.11 Using ICD-[X] Codes with FHIR

URL: https://hl7.org/fhir/STU3/icd.html

This page is part of the FHIR Specification (v3.0.2: STU 3). The current version which supercedes this version is 4.0.1. For a full list of available versions, see the Directory of published versions

4.2.11 Using ICD-[X] Codes with FHIR

Vocabulary Work Group | Maturity Level: 2 | Ballot Status: Trial Use

ICD is a family of code systems maintained by WHO , with many countries publishing their own variants.

The are two principal revisions of ICD in use - ICD-10 and ICD-9 (note that while US usage has recently updated to ICD-10, there is still a lot of legacy data coded in ICD-9). Though these can be referred to as different versions of ICD, they are entirely distinct sets of codes, with significant differences in organization and coding rules. Plus, if period ('.') characters are disregarded (as occurs in some systems), a few of the codes are overlapping between ICD-9 and ICD-10. Given these considerations, ICD-9 and ICD-10 are represented as entirely separate code systems. The next revision, ICD-11, is scheduled for release in 2017.

4.2.11.1 Summary

| ICD-10 | ICD-9
Source | WHO or see below | (CDC)
System | http://hl7.org/fhir/sid/icd-10 and http://hl7.org/fhir/sid/icd-10-[x] (see below) | http://hl7.org/fhir/sid/icd-9-cm
OID | 2.16.840.1.113883.6.3 | 2.16.840.1.113883.6.42
Version | The versioning convention and frequency may vary between the various ICD revisions and variants. WHO publishes a new version of ICD-10 annually in October (with minor updates annually, and major updates, if required, every 3 years - the versions are identified as 'YYYY', e.g. '2016'). The national variants (which in some cases are used multi-nationally) are also typically published on an annual basis (refer to the documentation for a particular variant for details).
Code | Either an ICD-10 or ICD-9 code, or a dual coding expression - see below
Display | There are no specific conventions required or described for obtaining the complete display string for use for each code.
Inactive | ICD-9 and ICD-10 do not have codes that are identified as inactive (although in some cases previously included codes may have been removed or changed in meaning in subsequent versions).
Hierarchy | The tabular representations are organized with headings and multiple levels of codes (typically based on the numbers of digits contained in each code), but an explicit hierarchy is not defined.
Filter Properties | None are described yet.

4.2.11.2 ICD-10 variants

Variants (other variants exist which are not listed here):

Germany | http://hl7.org/fhir/sid/icd-10-de | 2.16.840.1.113883.6.3.2
Netherlands | http://hl7.org/fhir/sid/icd-10-nl | 1.2.276.0.76.5.409
United States | http://hl7.org/fhir/sid/icd-10-cm | 2.16.840.1.113883.6.90

4.2.11.3 Dual Coding

Note that for dual coding (see volume 2 ICD-10 Manual), section 3.1.3 Two codes for certain conditions), simply use the two ICD-10 codes separated by a space, e.g. "J21.8 B95.6".

Dual coding in ICD-10 is used for the following (and potentially other) reasons:

* Coding for diagnostic statements containing information about both (1) an underlying generalized disease and (2) a manifestation in a particular organ or site which is a clinical problem in its own right. This is referred to as the "dagger and asterisk" system, as it marks the primary code for the underlying disease with a dagger (†) and an optional additional code for the manifestation with an asterisk (*).

* Other optional dual coding (noted in the tabular representation as “Use additional code, if desired ...”)

* For local infections, classifiable to the “body systems” chapters, codes from Chapter I may be added to identify the infecting organism, where this information does not appear in the title of the rubric.

* For neoplasms with functional activity. To the code from Chapter II may be added the appropriate code from Chapter IV to indicate the type of functional activity.

* For neoplasms, the morphology code from Volume 1, although not part of the main ICD, may be added to the Chapter II code to identify the morphological type of the tumour.

* For conditions classifiable to F00-F09 (Organic, including symptomatic, mental disorders) in Chapter V, where a code from another chapter may be added to indicate the cause, i.e. the underlying disease, injury or other insult to the brain.

* Where a condition is caused by a toxic agent, a code from Chapter XX may be added to identify that agent.

* Where two codes can be used to describe an injury, poisoning or other adverse effect: a code from Chapter XIX, which describes the nature of the injury, and a code from Chapter XX, which describes the cause.

For "dagger and asterisk" coding of an underlying generalized disease and a specific manifestation, it is recommended that the primary code for the underlying disease is listed first.

Dual Coding Example: "Staph aureus bronchiolitis" is coded using ICD-10 codes J21.8 "Acute bronchiolitis due to other specified organisms" and B95.6 "Staphylococcus aureus as the cause of diseases classified to other chapters" as

```
<coding>
  <system value="http://hl7.org/fhir/sid/icd-10"/>
  <code value="J21.8 B95.6"/>
</coding>
```

4.2.11.4 Copyright/License Issues

ICD-10 is ©Copyright World Health Organization (WHO). WHO licenses its published material widely, in order to encourage maximum use and dissemination. See Licensing WHO classifications for details. The ICD variants have their own separate copyright and licensing (refer to the documentation for the particular variant for details).

4.2.11.5 ICD-X Filter Properties

No need for filters identified yet.

4.2.11.6 Implicit Value Sets

No need for implicit value sets identified yet.

4.2.12.2 Code System http://hl7.org/fhir/administrative-gender

URL: https://hl7.org/fhir/STU3/codesystem-administrative-gender.html

This page is part of the FHIR Specification (v3.0.2: STU 3). The current version which supercedes this version is 4.0.1. For a full list of available versions, see the Directory of published versions

Vocabulary Work Group | Maturity Level: 5 | Informative | Use Context: Any

This is a code system defined by the FHIR project.

Summary

Defining URL: | http://hl7.org/fhir/administrative-gender
Name: | AdministrativeGender
Definition: | The gender of a person used for administrative purposes.
Committee: | Patient Administration Work Group
OID: | 2.16.840.1.113883.4.642.1.2 (for OID based terminology systems)
Source Resource | XML / JSON

This Code system is used in the following value sets:

* AdministrativeGender (The gender of a person used for administrative purposes.)

4.2.12.2.1 Content

4.2.12.2.2 AdministrativeGender

The gender of a person used for administrative purposes.

This code system http://hl7.org/fhir/administrative-gender defines the following codes:

Code | Display | Definition | Comments
male | Male | Male | Male
female | Female | Female | Female
other | Other | Other | The gender of a person could not be uniquely defined as male or female, such as hermaphrodite.
unknown | Unknown | Unknown | Description:A proper value is applicable, but not known. Usage Notes: This means the actual value is not known. If the only thing that is unknown is how to properly express the value in the necessary constraints (value set, datatype, etc.), then the OTH or UNC flavor should be used. No properties should be included for a datatype with this property unless: Those properties themselves directly translate to a semantic of "unknown". (E.g. a local code sent as a translation that conveys 'unknown') Those properties further qualify the nature of what is unknown. (E.g. specifying a use code of "H" and a URL prefix of "tel:" to convey that it is the home phone number that is unknown.)

See the full registry of value sets defined as part of FHIR.

Explanation of the columns that may appear on this page:

Level | A few code lists that FHIR defines are hierarchical - each code is assigned a level. In this scheme, some codes are under other codes, and imply that the code they are under also applies
Source | The source of the definition of the code (when the value set draws in codes defined elsewhere)
Code | The code (used as the code in the resource instance). If the code is in italics, this indicates that the code is not selectable ('Abstract')
Display | The display (used in the display element of a Coding). If there is no display, implementers should not simply display the code, but map the concept into their application
Definition | An explanation of the meaning of the concept
Comments | Additional notes about how to use the code

4.2.12.4 Code System http://hl7.org/fhir/publication-status

URL: https://hl7.org/fhir/STU3/codesystem-publication-status.html

This page is part of the FHIR Specification (v3.0.2: STU 3). The current version which supercedes this version is 4.0.1. For a full list of available versions, see the Directory of published versions

Vocabulary Work Group | Maturity Level: 5 | Informative | Use Context: Any

This is a code system defined by the FHIR project.

Summary

Defining URL: | http://hl7.org/fhir/publication-status
Name: | PublicationStatus
Definition: | The lifecycle status of a Value Set or Concept Map.
Committee: | FHIR Infrastructure Work Group
OID: | 2.16.840.1.113883.4.642.1.4 (for OID based terminology systems)
Source Resource | XML / JSON

This Code system is used in the following value sets:

* PublicationStatus (The lifecycle status of a Value Set or Concept Map.)

4.2.12.4.1 Content

4.2.12.4.2 PublicationStatus

The lifecycle status of a Value Set or Concept Map.

This code system http://hl7.org/fhir/publication-status defines the following codes:

Code | Display | Definition
draft | Draft | This resource is still under development and is not yet considered to be ready for normal use.

active | Active | This resource is ready for normal use.
retired | Retired | This resource has been withdrawn or superseded and should no longer be used.
unknown | Unknown | The authoring system does not know which of the status values currently applies for this resource. Note: This concept is not to be used for "other" - one of the listed statuses is presumed to apply, it's just not known which one.

Additional Language Displays

Code | Nederlands (Dutch, nl) | ??????? (Russian, ru)
draft | ontwerp | ????????
active | actief | ????????
retired | verouderd | ??????
unknown

See the full registry of value sets defined as part of FHIR.

Explanation of the columns that may appear on this page:

Level | A few code lists that FHIR defines are hierarchical - each code is assigned a level. In this scheme, some codes are under other codes, and imply that the code they are under also applies
Source | The source of the definition of the code (when the value set draws in codes defined elsewhere)
Code | The code (used as the code in the resource instance). If the code is in italics, this indicates that the code is not selectable ('Abstract')
Display | The display (used in the display element of a Coding). If there is no display, implementers should not simply display the code, but map the concept into their application
Definition | An explanation of the meaning of the concept
Comments | Additional notes about how to use the code

4.2.12.6 Code System http://hl7.org/fhir/data-absent-reason

URL: https://hl7.org/fhir/STU3/codesystem-data-absent-reason.html

This page is part of the FHIR Specification (v3.0.2: STU 3). The current version which supercedes this version is 4.0.1. For a full list of available versions, see the Directory of published versions

Vocabulary Work Group | Maturity Level: 0 | Informative | Use Context: Any

This is a code system defined by the FHIR project.

Summary

Defining URL: | http://hl7.org/fhir/data-absent-reason
Name: | DataAbsentReason
Definition: | Used to specify why the normally expected content of the data element is missing.
Committee: | FHIR Infrastructure Work Group
OID: | 2.16.840.1.113883.4.642.1.6 (for OID based terminology systems)
Source Resource | XML / JSON

This Code system is used in the following value sets:

* Observation Value Absent Reason (This value set defines the set of codes for identifying the reason why the expected result in Observation.value[x] is missing.)

* DataAbsentReason (Used to specify why the normally expected content of the data element is missing.)

4.2.12.6.1 Content

4.2.12.6.2 DataAbsentReason

Used to specify why the normally expected content of the data element is missing.

This code system http://hl7.org/fhir/data-absent-reason defines the following codes:

Lvl | Code | Display | Definition | Comments
1 | unknown | Unknown | The value is not known.
1 | asked | Asked | The source human does not know the value.
1 | temp | Temp | There is reason to expect (from the workflow) that the value may become known.
1 | not-asked | Not Asked | The workflow didn't lead to this value being known.
1 | masked | Masked | The information is not available due to security, privacy or related reasons. | Using "masked" may be breach of security or confidentiality, but there are times when its use is required to support alternate workflows for gaining access to denied information.
1 | unsupported | Unsupported | The source system wasn't capable of supporting this element.
1 | astext | As Text | The content of the data is represented in the resource narrative. | it may be linked by internal references (e.g. xml:id). This usually implies that the value could not be represented in the correct format - this may be due to system limitations, or this particular data value
1 | error | Error | Some system or workflow process error means that the information is not available.
2 | NaN | Not a Number | NaN, standing for not a number, is a numeric data type value representing an undefined or unrepresentable value. | This is sometimes an output value from measuring devices
1 | not-performed | Not Performed | The value is not available because the observation procedure (test, etc.) was not performed.

See the full registry of value sets defined as part of FHIR.

Explanation of the columns that may appear on this page:

Level | A few code lists that FHIR defines are hierarchical - each code is assigned a level. In this scheme, some codes are under other codes, and imply that the code they are under also applies
Source | The source of the definition of the code (when the value set draws in codes defined elsewhere)
Code | The code (used as the code in the resource instance). If the code is in italics, this indicates that the code is not selectable ('Abstract')

Display | The display (used in the display element of a Coding). If there is no display, implementers should not simply display the code, but map the concept into their application
Definition | An explanation of the meaning of the concept
Comments | Additional notes about how to use the code

4.2.12.8 Code System http://hl7.org/fhir/document-reference-status

URL: https://hl7.org/fhir/STU3/codesystem-document-reference-status.html

This page is part of the FHIR Specification (v3.0.2: STU 3). The current version which supercedes this version is 4.0.1. For a full list of available versions, see the Directory of published versions

Vocabulary Work Group | Maturity Level: 3 | Informative | Use Context: Any

This is a code system defined by the FHIR project.

Summary

Defining URL: | http://hl7.org/fhir/document-reference-status
Name: | DocumentReferenceStatus
Definition: | The status of the document reference.
Committee: | Structured Documents Work Group
OID: | 2.16.840.1.113883.4.642.1.8 (for OID based terminology systems)
Source Resource | XML / JSON

This Code system is used in the following value sets:

* DocumentReferenceStatus (The status of the document reference.)

4.2.12.8.1 Content

4.2.12.8.2 DocumentReferenceStatus

The status of the document reference.

This code system http://hl7.org/fhir/document-reference-status defines the following codes:

Code | Display | Definition
current | Current | This is the current reference for this document.
superseded | Superseded | This reference has been superseded by another reference.
entered-in-error | Entered in Error | This reference was created in error.

See the full registry of value sets defined as part of FHIR.

Explanation of the columns that may appear on this page:

Level | A few code lists that FHIR defines are hierarchical - each code is assigned a level. In this scheme, some codes are under other codes, and imply that the code they are under also applies
Source | The source of the definition of the code (when the value set draws in codes defined elsewhere)
Code | The code (used as the code in the resource instance). If the code is in italics, this indicates that the code is not selectable ('Abstract')
Display | The display (used in the display element of a Coding). If there is no display, implementers should not simply display the code, but map the concept into their application
Definition | An explanation of the meaning of the concept
Comments | Additional notes about how to use the code

4.2.12.10 Code System http://hl7.org/fhir/special-values

URL: https://hl7.org/fhir/STU3/codesystem-special-values.html

This page is part of the FHIR Specification (v3.0.2: STU 3). The current version which supercedes this version is 4.0.1. For a full list of available versions, see the Directory of published versions

Vocabulary Work Group | Maturity Level: 0 | Informative | Use Context: Any

This is a code system defined by the FHIR project.

Summary

Defining URL: | http://hl7.org/fhir/special-values
Name: | SpecialValues
Definition: | A set of generally useful codes defined so they can be included in value sets.
Committee: | FHIR Infrastructure Work Group
OID: | 2.16.840.1.113883.4.642.1.10 (for OID based terminology systems)
Source Resource | XML / JSON

This Code system is used in the following value sets:

* SpecialValues (A set of generally useful codes defined so they can be included in value sets.)

4.2.12.10.1 Content

4.2.12.10.2 SpecialValues

A set of generally useful codes defined so they can be included in value sets.

This code system http://hl7.org/fhir/special-values defines the following codes:

Code | Display | Definition | Comments
true | true | Boolean true.
false | false | Boolean false.
trace | Trace Amount Detected | The content is greater than zero, but too small to be quantified.
sufficient | Sufficient Quantity | The specific quantity is not known, but is known to be non-zero and is not specified because it makes up the bulk of the material. | used in formulations (e.g. 'Add 10mg of ingredient X, 50mg of ingredient Y, and sufficient quantity of water to 100mL.' This code would be used to express the quantity of water.)
withdrawn | Value Withdrawn | The value is no longer available.
nil-known | Nil Known | The are no known applicable values in this context. | The existence of this subject to review

See the full registry of value sets defined as part of FHIR.

Explanation of the columns that may appear on this page:

Level | A few code lists that FHIR defines are hierarchical - each code is assigned a level. In this scheme, some codes are under other codes, and imply that the code they are under also applies
Source | The source of the definition of the code (when the value set draws in codes defined elsewhere)
Code | The code (used as the code in the resource instance). If the code is in italics, this indicates that the code is not selectable ('Abstract')
Display | The display (used in the display element of a Coding). If there is no display, implementers should not simply display the code, but map the concept into their application
Definition | An explanation of the meaning of the concept
Comments | Additional notes about how to use the code

4.2.12.12 Code System http://hl7.org/fhir/search-param-type

URL: https://hl7.org/fhir/STU3/codesystem-search-param-type.html

This page is part of the FHIR Specification (v3.0.2: STU 3). The current version which supercedes this version is 4.0.1. For a full list of available versions, see the Directory of published versions

Vocabulary Work Group | Maturity Level: 4 | Informative | Use Context: Any

This is a code system defined by the FHIR project.

Summary

Defining URL: | http://hl7.org/fhir/search-param-type
Name: | SearchParamType
Definition: | Data types allowed to be used for search parameters.
Committee: | FHIR Infrastructure Work Group
OID: | 2.16.840.1.113883.4.642.1.12 (for OID based terminology systems)
Source Resource | XML / JSON

This Code system is used in the following value sets:

* SearchParamType (Data types allowed to be used for search parameters.)

4.2.12.12.1 Content

4.2.12.12.2 SearchParamType

Data types allowed to be used for search parameters.

This code system http://hl7.org/fhir/search-param-type defines the following codes:

Code | Display | Definition
number | Number | Search parameter SHALL be a number (a whole number, or a decimal).
date | Date/DateTime | Search parameter is on a date/time. The date format is the standard XML format, though other formats may be supported.
string | String | Search parameter is a simple string, like a name part. Search is case-insensitive and accent-insensitive. May match just the start of a string. String parameters may contain spaces.
token | Token | Search parameter on a coded element or identifier. May be used to search through the text, displayname, code and code/codesystem (for codes) and label, system and key (for identifier). Its value is either a string or a pair of namespace and value, separated by a "|", depending on the modifier used.
reference | Reference | A reference to another resource.
composite | Composite | A composite search parameter that combines a search on two values together.
quantity | Quantity | A search parameter that searches on a quantity.
uri | URI | A search parameter that searches on a URI (RFC 3986).

See the full registry of value sets defined as part of FHIR.

Explanation of the columns that may appear on this page:

Level | A few code lists that FHIR defines are hierarchical - each code is assigned a level. In this scheme, some codes are under other codes, and imply that the code they are under also applies
Source | The source of the definition of the code (when the value set draws in codes defined elsewhere)
Code | The code (used as the code in the resource instance). If the code is in italics, this indicates that the code is not selectable ('Abstract')
Display | The display (used in the display element of a Coding). If there is no display, implementers should not simply display the code, but map the concept into their application
Definition | An explanation of the meaning of the concept
Comments | Additional notes about how to use the code

4.2.12.14 Code System http://hl7.org/fhir/remittance-outcome

URL: https://hl7.org/fhir/STU3/codesystem-remittance-outcome.html

This page is part of the FHIR Specification (v3.0.2: STU 3). The current version which supercedes this version is 4.0.1. For a full list of available versions, see the Directory of published versions

Vocabulary Work Group | Maturity Level: 1 | Informative | Use Context: Not Intended for Production use

This is a code system defined by the FHIR project.

Summary

Defining URL: | http://hl7.org/fhir/remittance-outcome
Name: | Claim Processing Codes
Definition: | This value set includes a Claim Processing Outcome codes.
Committee: | Financial Management Work Group
OID: | 2.16.840.1.113883.4.642.1.14 (for OID based terminology systems)
Copyright: | This is an example set.
Source Resource | XML / JSON

This Code system is used in the following value sets:

* Claim Processing Codes (This value set includes a Claim Processing Outcome codes.)

4.2.12.14.1 Content

4.2.12.14.2 Claim Processing Codes

This value set includes a Claim Processing Outcome codes.

Copyright Statement: This is an example set.

This code system http://hl7.org/fhir/remittance-outcome defines the following codes:

Code | Display | Definition
complete | Processing Complete | The processing has completed without errors
error | Error | One or more errors have been detected in the Claim
partial | Partial Processing | No errors have been detected in the Claim and some of the adjudication has been performed.

See the full registry of value sets defined as part of FHIR.

Explanation of the columns that may appear on this page:

Level | A few code lists that FHIR defines are hierarchical - each code is assigned a level. In this scheme, some codes are under other codes, and imply that the code they are under also applies
Source | The source of the definition of the code (when the value set draws in codes defined elsewhere)
Code | The code (used as the code in the resource instance). If the code is in italics, this indicates that the code is not selectable ('Abstract')
Display | The display (used in the display element of a Coding). If there is no display, implementers should not simply display the code, but map the concept into their application
Definition | An explanation of the meaning of the concept
Comments | Additional notes about how to use the code

4.2.12.16 Code System http://hl7.org/fhir/note-type

URL: https://hl7.org/fhir/STU3/codesystem-note-type.html

This page is part of the FHIR Specification (v3.0.2: STU 3). The current version which supercedes this version is 4.0.1. For a full list of available versions, see the Directory of published versions

Vocabulary Work Group | Maturity Level: 2 | Informative | Use Context: Any

This is a code system defined by the FHIR project.

Summary

Defining URL: | http://hl7.org/fhir/note-type
Name: | NoteType
Definition: | The presentation types of notes.
Committee: | Financial Management Work Group
OID: | 2.16.840.1.113883.4.642.1.16 (for OID based terminology systems)
Source Resource | XML / JSON

This Code system is used in the following value sets:

* NoteType (The presentation types of notes.)

4.2.12.16.1 Content

4.2.12.16.2 NoteType

The presentation types of notes.

This code system http://hl7.org/fhir/note-type defines the following codes:

Code | Display | Definition
display | Display | Display the note.

print | Print (Form) | Print the note on the form.
printoper | Print (Operator) | Print the note for the operator.

See the full registry of value sets defined as part of FHIR.

Explanation of the columns that may appear on this page:

Level | A few code lists that FHIR defines are hierarchical - each code is assigned a level. In this scheme, some codes are under other codes, and imply that the code they are under also applies
Source | The source of the definition of the code (when the value set draws in codes defined elsewhere)
Code | The code (used as the code in the resource instance). If the code is in italics, this indicates that the code is not selectable ('Abstract')
Display | The display (used in the display element of a Coding). If there is no display, implementers should not simply display the code, but map the concept into their application
Definition | An explanation of the meaning of the concept
Comments | Additional notes about how to use the code

4.2.12.18 Code System http://hl7.org/fhir/concept-map-equivalence

URL: https://hl7.org/fhir/STU3/codesystem-concept-map-equivalence.html

This page is part of the FHIR Specification (v3.0.2: STU 3). The current version which supercedes this version is 4.0.1. For a full list of available versions, see the Directory of published versions

Vocabulary Work Group | Maturity Level: 3 | Informative | Use Context: Any

This is a code system defined by the FHIR project.

Summary

Defining URL: | http://hl7.org/fhir/concept-map-equivalence
Name: | ConceptMapEquivalence
Definition: | The degree of equivalence between concepts.
Committee: | FHIR Infrastructure Work Group
OID: | 2.16.840.1.113883.4.642.1.18 (for OID based terminology systems)
Source Resource | XML / JSON

This Code system is used in the following value sets:

* ConceptMapEquivalence (The degree of equivalence between concepts.)

4.2.12.18.1 Content

4.2.12.18.2 ConceptMapEquivalence

The degree of equivalence between concepts.

This code system http://hl7.org/fhir/concept-map-equivalence defines the following codes:

Lvl | Code | Display | Definition
1 | relatedto | Related To | The concepts are related to each other, and have at least some overlap in meaning, but the exact relationship is not known
2 | equivalent | Equivalent | The definitions of the concepts mean the same thing (including when structural implications of meaning are considered) (i.e. extensionally identical).
3 | equal | Equal | The definitions of the concepts are exactly the same (i.e. only grammatical differences) and structural implications of meaning are identical or irrelevant (i.e. intentionally identical).
2 | wider | Wider | The target mapping is wider in meaning than the source concept.
2 | subsumes | Subsumes | The target mapping subsumes the meaning of the source concept (e.g. the source is-a target).
2 | narrower | Narrower | The target mapping is narrower in meaning than the source concept. The sense in which the mapping is narrower SHALL be described in the comments in this case, and applications should be careful when attempting to use these mappings operationally.
2 | specializes | Specializes | The target mapping specializes the meaning of the source concept (e.g. the target is-a source).
2 | inexact | Inexact | The target mapping overlaps with the source concept, but both source and target cover additional meaning, or the definitions are imprecise and it is uncertain whether they have the same boundaries to their meaning. The sense in which the mapping is narrower SHALL be described in the comments in this case, and applications should be careful when attempting to use these mappings operationally.
1 | unmatched | Unmatched | There is no match for this concept in the destination concept system.
2 | disjoint | Disjoint | This is an explicit assertion that there is no mapping between the source and target concept.

See the full registry of value sets defined as part of FHIR.

Explanation of the columns that may appear on this page:

Level | A few code lists that FHIR defines are hierarchical - each code is assigned a level. In this scheme, some codes are under other codes, and imply that the code they are under also applies
Source | The source of the definition of the code (when the value set draws in codes defined elsewhere)
Code | The code (used as the code in the resource instance). If the code is in italics, this indicates that the code is not selectable ('Abstract')
Display | The display (used in the display element of a Coding). If there is no display, implementers should not simply display the code, but map the concept into their application
Definition | An explanation of the meaning of the concept
Comments | Additional notes about how to use the code

4.2.12.29 Code System http://hl7.org/fhir/marital-status

URL: https://hl7.org/fhir/STU3/codesystem-marital-status.html

This page is part of the FHIR Specification (v3.0.2: STU 3). The current version which supercedes this version is 4.0.1. For a full list of available versions, see the Directory of published versions

Vocabulary Work Group | Maturity Level: 5 | Informative | Use Context: Not Intended for Production use

This is a code system defined by the FHIR project.

Summary

Defining URL: | http://hl7.org/fhir/marital-status
Name: | Marital Status Codes
Definition: | This value set defines the set of codes that can be used to indicate the marital status of a person.
Committee: | Patient Administration Work Group
OID: | 2.16.840.1.113883.4.642.1.29 (for OID based terminology systems)
Source Resource | XML / JSON

This Code system is not currently used

4.2.12.29.1 Content

4.2.12.29.2 Marital Status Codes

This value set defines the set of codes that can be used to indicate the marital status of a person.

This code system http://hl7.org/fhir/marital-status defines the following codes:

Code | Display | Definition
U | Unmarried | The person is not presently married. The marital history is not known or stated.

See the full registry of value sets defined as part of FHIR.

Explanation of the columns that may appear on this page:

Level | A few code lists that FHIR defines are hierarchical - each code is assigned a level. In this scheme, some codes are under other codes, and imply that the code they are under also applies
Source | The source of the definition of the code (when the value set draws in codes defined elsewhere)
Code | The code (used as the code in the resource instance). If the code is in italics, this indicates that the code is not selectable ('Abstract')
Display | The display (used in the display element of a Coding). If there is no display, implementers should not simply display the code, but map the concept into their application
Definition | An explanation of the meaning of the concept
Comments | Additional notes about how to use the code

4.2.12.31 Code System http://hl7.org/fhir/payeetype

URL: https://hl7.org/fhir/STU3/codesystem-payeetype.html

This page is part of the FHIR Specification (v3.0.2: STU 3). The current version which supercedes this version is 4.0.1. For a full list of available versions, see the Directory of published versions

Vocabulary Work Group | Maturity Level: 1 | Informative | Use Context: Not Intended for Production use

This is a code system defined by the FHIR project.

Summary

Defining URL: | http://hl7.org/fhir/payeetype
Name: | Claim Payee Type Codes
Definition: | This value set includes sample Payee Type codes.
Committee: | Financial Management Work Group
OID: | 2.16.840.1.113883.4.642.1.31 (for OID based terminology systems)
Copyright: | This is an example set.
Source Resource | XML / JSON

This Code system is used in the following value sets:

* Claim Payee Type Codes (This value set includes sample Payee Type codes.)

4.2.12.31.1 Content

4.2.12.31.2 Claim Payee Type Codes

This value set includes sample Payee Type codes.

Copyright Statement: This is an example set.

This code system http://hl7.org/fhir/payeetype defines the following codes:

Code | Display | Definition
subscriber | Subscriber | The subscriber (policy holder) will be reimbursed.
provider | Provider | Any benefit payable will be paid to the provider (Assignment of Benefit).
other | Provider | Any benefit payable will be paid to a third party such as a guarrantor.

See the full registry of value sets defined as part of FHIR.

Explanation of the columns that may appear on this page:

Level | A few code lists that FHIR defines are hierarchical - each code is assigned a level. In this scheme, some codes are under other codes, and imply that the code they are under also applies

Source | The source of the definition of the code (when the value set draws in codes defined elsewhere)
Code | The code (used as the code in the resource instance). If the code is in italics, this indicates that the code is not selectable ('Abstract')
Display | The display (used in the display element of a Coding). If there is no display, implementers should not simply display the code, but map the concept into their application
Definition | An explanation of the meaning of the concept
Comments | Additional notes about how to use the code

4.2.12.33 Code System http://hl7.org/fhir/fundsreserve

URL: https://hl7.org/fhir/STU3/codesystem-fundsreserve.html

This page is part of the FHIR Specification (v3.0.2: STU 3). The current version which supercedes this version is 4.0.1. For a full list of available versions, see the Directory of published versions

Vocabulary Work Group | Maturity Level: 1 | Informative | Use Context: Not Intended for Production use

This is a code system defined by the FHIR project.

Summary

Defining URL: | http://hl7.org/fhir/fundsreserve
Name: | Funds Reservation Codes
Definition: | This value set includes sample funds reservation type codes.
Committee: | Financial Management Work Group
OID: | 2.16.840.1.113883.4.642.1.33 (for OID based terminology systems)
Copyright: | This is an example set.
Source Resource | XML / JSON

This Code system is used in the following value sets:

* Funds Reservation Codes (This value set includes sample funds reservation type codes.)

4.2.12.33.1 Content

4.2.12.33.2 Funds Reservation Codes

This value set includes sample funds reservation type codes.

Copyright Statement: This is an example set.

This code system http://hl7.org/fhir/fundsreserve defines the following codes:

Code | Display | Definition
patient | Patient | The payor is requested to reserve funds for the provision of the named services by any provider for settlement of future claims related to this request.
provider | Provider | The payor is requested to reserve funds solely for the named provider for settlement of future claims related to this request.
none | None | The payor is not being requested to reserve any funds for the settlement of future claims.

See the full registry of value sets defined as part of FHIR.

Explanation of the columns that may appear on this page:

Level | A few code lists that FHIR defines are hierarchical - each code is assigned a level. In this scheme, some codes are under other codes, and imply that the code they are under also applies
Source | The source of the definition of the code (when the value set draws in codes defined elsewhere)
Code | The code (used as the code in the resource instance). If the code is in italics, this indicates that the code is not selectable ('Abstract')
Display | The display (used in the display element of a Coding). If there is no display, implementers should not simply display the code, but map the concept into their application
Definition | An explanation of the meaning of the concept
Comments | Additional notes about how to use the code

4.2.12.35 Code System http://hl7.org/fhir/relationship

URL: https://hl7.org/fhir/STU3/codesystem-relationship.html

This page is part of the FHIR Specification (v3.0.2: STU 3). The current version which supercedes this version is 4.0.1. For a full list of available versions, see the Directory of published versions

Vocabulary Work Group | Maturity Level: 0 | Informative | Use Context: Not Intended for Production use

This is a code system defined by the FHIR project.

Summary

Defining URL: | http://hl7.org/fhir/relationship
Name: | Beneficiary Relationship Codes
Definition: | This value set includes the Patient to subscriber relationship codes.
Committee: | Financial Management Work Group
OID: | 2.16.840.1.113883.4.642.1.35 (for OID based terminology systems)
Copyright: | This is an example set.
Source Resource | XML / JSON

This Code system is used in the following value sets:

* Beneficiary Relationship Codes (This value set includes the Patient to subscriber relationship codes.)

4.2.12.35.1 Content

4.2.12.35.2 Beneficiary Relationship Codes

This value set includes the Patient to subscriber relationship codes.

Copyright Statement: This is an example set.

This code system http://hl7.org/fhir/relationship defines the following codes:

Code | Display | Definition
1 | Self | The patient is the subscriber (policy holder)
2 | Spouse | The patient is the spouse or equivalent of the subscriber (policy holder)
3 | Child | The patient is the child of the subscriber (policy holder)
4 | Common Law Spouse | The patient is the common law spouse of the subscriber (policy holder)
5 | Other | The patient has some other relationship, such as parent, to the subscriber (policy holder)

See the full registry of value sets defined as part of FHIR.

Explanation of the columns that may appear on this page:

Level | A few code lists that FHIR defines are hierarchical - each code is assigned a level. In this scheme, some codes are under other codes, and imply that the code they are under also applies
Source | The source of the definition of the code (when the value set draws in codes defined elsewhere)
Code | The code (used as the code in the resource instance). If the code is in italics, this indicates that the code is not selectable ('Abstract')
Display | The display (used in the display element of a Coding). If there is no display, implementers should not simply display the code, but map the concept into their application
Definition | An explanation of the meaning of the concept
Comments | Additional notes about how to use the code

4.2.12.37 Code System http://hl7.org/fhir/forms-codes

URL: https://hl7.org/fhir/STU3/codesystem-forms.html

This page is part of the FHIR Specification (v3.0.2: STU 3). The current version which supercedes this version is 4.0.1. For a full list of available versions, see the Directory of published versions

Vocabulary Work Group | Maturity Level: 1 | Informative | Use Context: Not Intended for Production use

This is a code system defined by the FHIR project.

Summary

Defining URL: | http://hl7.org/fhir/forms-codes
Name: | Form Codes
Definition: | This value set includes a sample set of Forms codes.
Committee: | Financial Management Work Group
OID: | 2.16.840.1.113883.4.642.1.37 (for OID based terminology systems)
Copyright: | This is an example set.
Source Resource | XML / JSON

This Code system is used in the following value sets:

* Form Codes (This value set includes a sample set of Forms codes.)

4.2.12.37.1 Content

4.2.12.37.2 Form Codes

This value set includes a sample set of Forms codes.

Copyright Statement: This is an example set.

This code system http://hl7.org/fhir/forms-codes defines the following codes:

Code | Display | Definition
1 | Form #1 | Example: The #1 form to be used when printing this information.
2 | Form #1 | Example: The #2 form to be used when printing this information.

See the full registry of value sets defined as part of FHIR.

Explanation of the columns that may appear on this page:

Level | A few code lists that FHIR defines are hierarchical - each code is assigned a level. In this scheme, some codes are under other codes, and imply that the code they are under also applies
Source | The source of the definition of the code (when the value set draws in codes defined elsewhere)
Code | The code (used as the code in the resource instance). If the code is in italics, this indicates that the code is not selectable ('Abstract')
Display | The display (used in the display element of a Coding). If there is no display, implementers should not simply display the code, but map the concept into their application
Definition | An explanation of the meaning of the concept
Comments | Additional notes about how to use the code

4.2.12.39 Code System http://hl7.org/fhir/adjudication-error

URL: https://hl7.org/fhir/STU3/codesystem-adjudication-error.html

This page is part of the FHIR Specification (v3.0.2: STU 3). The current version which supercedes this version is 4.0.1. For a full list of available versions, see the Directory of published versions

Vocabulary Work Group | Maturity Level: 1 | Informative | Use Context: Not Intended for Production use

This is a code system defined by the FHIR project.

Summary

Defining URL: | http://hl7.org/fhir/adjudication-error
Name: | Adjudication Error Codes
Definition: | This value set includes a smattering of adjudication codes.
Committee: | Financial Management Work Group
OID: | 2.16.840.1.113883.4.642.1.39 (for OID based terminology systems)
Copyright: | This is an example set.
Source Resource | XML / JSON

This Code system is used in the following value sets:

* Adjudication Error Codes (This value set includes a smattering of adjudication codes.)

4.2.12.39.1 Content

4.2.12.39.2 Adjudication Error Codes

This value set includes a smattering of adjudication codes.

Copyright Statement: This is an example set.

This code system http://hl7.org/fhir/adjudication-error defines the following codes:

Code | Display | Definition
a001 | Missing Identifier | Missing Identifier
a002 | Missing Creation Date | Missing Creation Date

See the full registry of value sets defined as part of FHIR.

Explanation of the columns that may appear on this page:

Level | A few code lists that FHIR defines are hierarchical - each code is assigned a level. In this scheme, some codes are under other codes, and imply that the code they are under also applies
Source | The source of the definition of the code (when the value set draws in codes defined elsewhere)
Code | The code (used as the code in the resource instance). If the code is in italics, this indicates that the code is not selectable ('Abstract')
Display | The display (used in the display element of a Coding). If there is no display, implementers should not simply display the code, but map the concept into their application
Definition | An explanation of the meaning of the concept
Comments | Additional notes about how to use the code

4.2.12.43 Code System http://hl7.org/fhir/binding-strength

URL: https://hl7.org/fhir/STU3/codesystem-binding-strength.html

This page is part of the FHIR Specification (v3.0.2: STU 3). The current version which supercedes this version is 4.0.1. For a full list of available versions, see the Directory of published versions

Vocabulary Work Group | Maturity Level: 4 | Informative | Use Context: Any

This is a code system defined by the FHIR project.

Summary

Defining URL: | http://hl7.org/fhir/binding-strength
Name: | BindingStrength
Definition: | Indication of the degree of conformance expectations associated with a binding.
Committee: | FHIR Infrastructure Work Group
OID: | 2.16.840.1.113883.4.642.1.43 (for OID based terminology systems)
Source Resource | XML / JSON

This Code system is used in the following value sets:

* BindingStrength (Indication of the degree of conformance expectations associated with a binding.)

4.2.12.43.1 Content

4.2.12.43.2 BindingStrength

Indication of the degree of conformance expectations associated with a binding.

This code system http://hl7.org/fhir/binding-strength defines the following codes:

Code | Display | Definition
required | Required | To be conformant, the concept in this element SHALL be from the specified value set
extensible | Extensible | To be conformant, the concept in this element SHALL be from the specified value set if any of the codes within the value set can apply to the concept being communicated. If the value set does not cover the concept (based on human review), alternate codings (or, data type allowing, text) may be included instead.
preferred | Preferred | Instances are encouraged to draw from the specified codes for interoperability purposes but are not required to do so to be considered conformant.

example | Example | Instances are not expected or even encouraged to draw from the specified value set. The value set merely provides examples of the types of concepts intended to be included.

See the full registry of value sets defined as part of FHIR.

Explanation of the columns that may appear on this page:

Level | A few code lists that FHIR defines are hierarchical - each code is assigned a level. In this scheme, some codes are under other codes, and imply that the code they are under also applies
Source | The source of the definition of the code (when the value set draws in codes defined elsewhere)
Code | The code (used as the code in the resource instance). If the code is in italics, this indicates that the code is not selectable ('Abstract')
Display | The display (used in the display element of a Coding). If there is no display, implementers should not simply display the code, but map the concept into their application
Definition | An explanation of the meaning of the concept
Comments | Additional notes about how to use the code

4.2.12.45 Code System http://hl7.org/fhir/identifier-type

URL: https://hl7.org/fhir/STU3/codesystem-identifier-type.html

This page is part of the FHIR Specification (v3.0.2: STU 3). The current version which supercedes this version is 4.0.1. For a full list of available versions, see the Directory of published versions

Vocabulary Work Group | Maturity Level: 1 | Informative | Use Context: Not Intended for Production use

This is a code system defined by the FHIR project.

Summary

Defining URL: | http://hl7.org/fhir/identifier-type
Name: | Identifier Type Codes
Definition: | A coded type for an identifier that can be used to determine which identifier to use for a specific purpose.
Committee: | ??
OID: | 2.16.840.1.113883.4.642.1.45 (for OID based terminology systems)
Source Resource | XML / JSON

This Code system is used in the following value sets:

* Identifier Type Codes (A coded type for an identifier that can be used to determine which identifier to use for a specific purpose.)

4.2.12.45.1 Content

4.2.12.45.2 Identifier Type Codes

A coded type for an identifier that can be used to determine which identifier to use for a specific purpose.

This code system http://hl7.org/fhir/identifier-type defines the following codes:

Code | Display | Definition
UDI | Universal Device Identifier | A identifier assigned to a device using the Universal Device Identifier framework as defined by FDA (http://www.fda.gov/MedicalDevices/DeviceRegulationandGuidance/UniqueDeviceIdentification/).
SNO | Serial Number | An identifier affixed to an item by the manufacturer when it is first made, where each item has a different identifier.
SB | Social Beneficiary Identifier | An identifier issued by a governmental organization to an individual for the purpose of the receipt of social services and benefits.
PLAC | Placer Identifier | The identifier associated with the person or service that requests or places an order.
FILL | Filler Identifier | The Identifier associated with the person, or service, who produces the observations or fulfills the order requested by the requestor.

See the full registry of value sets defined as part of FHIR.

Explanation of the columns that may appear on this page:

Level | A few code lists that FHIR defines are hierarchical - each code is assigned a level. In this scheme, some codes are under other codes, and imply that the code they are under also applies
Source | The source of the definition of the code (when the value set draws in codes defined elsewhere)
Code | The code (used as the code in the resource instance). If the code is in italics, this indicates that the code is not selectable ('Abstract')
Display | The display (used in the display element of a Coding). If there is no display, implementers should not simply display the code, but map the concept into their application
Definition | An explanation of the meaning of the concept
Comments | Additional notes about how to use the code

4.2.12.49 Code System http://hl7.org/fhir/diagnosis-role

URL: https://hl7.org/fhir/STU3/codesystem-diagnosis-role.html

This page is part of the FHIR Specification (v3.0.2: STU 3). The current version which supercedes this version is 4.0.1. For a full list of available versions, see the Directory of published versions

Vocabulary Work Group | Maturity Level: 2 | Informative | Use Context: Not Intended for Production use

This is a code system defined by the FHIR project.

Summary

Defining URL: | http://hl7.org/fhir/diagnosis-role

Name: | DiagnosisRole
Definition: | This value set defines a set of codes that can be used to express the role of a diagnosis on the Encounter or EpisodeOfCare record.
Committee: | ??
OID: | 2.16.840.1.113883.4.642.1.49 (for OID based terminology systems)
Source Resource | XML / JSON

This Code system is used in the following value sets:

* DiagnosisRole (This value set defines a set of codes that can be used to express the role of a diagnosis on the Encounter or EpisodeOfCare record.)

4.2.12.49.1 Content

4.2.12.49.2 DiagnosisRole

This value set defines a set of codes that can be used to express the role of a diagnosis on the Encounter or EpisodeOfCare record.

This code system http://hl7.org/fhir/diagnosis-role defines the following codes:

Code | Display | Definition
AD | Admission diagnosis
DD | Discharge diagnosis
CC | Chief complaint
CM | Comorbidity diagnosis
pre-op | pre-op diagnosis
post-op | post-op diagnosis
billing | Billing

See the full registry of value sets defined as part of FHIR.

Explanation of the columns that may appear on this page:

Level | A few code lists that FHIR defines are hierarchical - each code is assigned a level. In this scheme, some codes are under other codes, and imply that the code they are under also applies
Source | The source of the definition of the code (when the value set draws in codes defined elsewhere)
Code | The code (used as the code in the resource instance). If the code is in italics, this indicates that the code is not selectable ('Abstract')
Display | The display (used in the display element of a Coding). If there is no display, implementers should not simply display the code, but map the concept into their application
Definition | An explanation of the meaning of the concept
Comments | Additional notes about how to use the code

4.2.12.51 Code System http://hl7.org/fhir/narrative-status

URL: https://hl7.org/fhir/STU3/codesystem-narrative-status.html

This page is part of the FHIR Specification (v3.0.2: STU 3). The current version which supercedes this version is 4.0.1. For a full list of available versions, see the Directory of published versions

Vocabulary Work Group | Maturity Level: 0 | Informative | Use Context: Any

This is a code system defined by the FHIR project.

Summary

Defining URL: | http://hl7.org/fhir/narrative-status
Name: | NarrativeStatus
Definition: | The status of a resource narrative
Committee: | FHIR Infrastructure Work Group
OID: | 2.16.840.1.113883.4.642.1.51 (for OID based terminology systems)
Source Resource | XML / JSON

This Code system is used in the following value sets:

* NarrativeStatus (The status of a resource narrative)

4.2.12.51.1 Content

4.2.12.51.2 NarrativeStatus

The status of a resource narrative

This code system http://hl7.org/fhir/narrative-status defines the following codes:

Code | Display | Definition
generated | Generated | The contents of the narrative are entirely generated from the structured data in the content.
extensions | Extensions | The contents of the narrative are entirely generated from the structured data in the content and some of the content is generated from extensions
additional | Additional | The contents of the narrative may contain additional information not found in the structured data. Note that there is no computable way to determine what the extra information is, other than by human inspection
empty | Empty | The contents of the narrative are some equivalent of "No human-readable text provided in this case"

See the full registry of value sets defined as part of FHIR.

Explanation of the columns that may appear on this page:

Level | A few code lists that FHIR defines are hierarchical - each code is assigned a level. In this scheme, some codes are under other codes, and imply that the code they are under also applies
Source | The source of the definition of the code (when the value set draws in codes defined elsewhere)
Code | The code (used as the code in the resource instance). If the code is in italics, this indicates that the code is not selectable ('Abstract')
Display | The display (used in the display element of a Coding). If there is no display, implementers should not simply display the code, but map the concept into their application
Definition | An explanation of the meaning of the concept
Comments | Additional notes about how to use the code

4.2.12.53 Code System http://hl7.org/fhir/identifier-use

URL: https://hl7.org/fhir/STU3/codesystem-identifier-use.html

This page is part of the FHIR Specification (v3.0.2: STU 3). The current version which supercedes this version is 4.0.1. For a full list of available versions, see the Directory of published versions

Vocabulary Work Group | Maturity Level: 0 | Informative | Use Context: Any

This is a code system defined by the FHIR project.

Summary

Defining URL: | http://hl7.org/fhir/identifier-use
Name: | IdentifierUse
Definition: | Identifies the purpose for this identifier, if known .
Committee: | FHIR Infrastructure Work Group
OID: | 2.16.840.1.113883.4.642.1.53 (for OID based terminology systems)
Source Resource | XML / JSON

This Code system is used in the following value sets:

* IdentifierUse (Identifies the purpose for this identifier, if known .)

4.2.12.53.1 Content

4.2.12.53.2 IdentifierUse

Identifies the purpose for this identifier, if known .

This code system http://hl7.org/fhir/identifier-use defines the following codes:

Code | Display | Definition
usual | Usual | The identifier recommended for display and use in real-world interactions.
official | Official | The identifier considered to be most trusted for the identification of this item.
temp | Temp | A temporary identifier.
secondary | Secondary | An identifier that was assigned in secondary use - it serves to identify the object in a relative context, but cannot be consistently assigned to the same object again in a different context.

See the full registry of value sets defined as part of FHIR.

Explanation of the columns that may appear on this page:

Level | A few code lists that FHIR defines are hierarchical - each code is assigned a level. In this scheme, some codes are under other codes, and imply that the code they are under also applies
Source | The source of the definition of the code (when the value set draws in codes defined elsewhere)
Code | The code (used as the code in the resource instance). If the code is in italics, this indicates that the code is not selectable ('Abstract')
Display | The display (used in the display element of a Coding). If there is no display, implementers should not simply display the code, but map the concept into their application
Definition | An explanation of the meaning of the concept
Comments | Additional notes about how to use the code

4.2.12.55 Code System http://hl7.org/fhir/quantity-comparator

URL: https://hl7.org/fhir/STU3/codesystem-quantity-comparator.html

This page is part of the FHIR Specification (v3.0.2: STU 3). The current version which supercedes this version is 4.0.1. For a full list of available versions, see the Directory of published versions

Vocabulary Work Group | Maturity Level: 0 | Informative | Use Context: Any

This is a code system defined by the FHIR project.

Summary

Defining URL: | http://hl7.org/fhir/quantity-comparator
Name: | QuantityComparator
Definition: | How the Quantity should be understood and represented.
Committee: | FHIR Infrastructure Work Group
OID: | 2.16.840.1.113883.4.642.1.55 (for OID based terminology systems)
Source Resource | XML / JSON

This Code system is used in the following value sets:

* QuantityComparator (How the Quantity should be understood and represented.)

4.2.12.55.1 Content

4.2.12.55.2 QuantityComparator

How the Quantity should be understood and represented.

This code system http://hl7.org/fhir/quantity-comparator defines the following codes:

Code | Display | Definition
< | Less than | The actual value is less than the given value.
<= | Less or Equal to | The actual value is less than or equal to the given value.
>= | Greater or Equal to | The actual value is greater than or equal to the given value.
> | Greater than | The actual value is greater than the given value.

See the full registry of value sets defined as part of FHIR.

Explanation of the columns that may appear on this page:

Level | A few code lists that FHIR defines are hierarchical - each code is assigned a level. In this scheme, some codes are under other codes, and imply that the code they are under also applies
Source | The source of the definition of the code (when the value set draws in codes defined elsewhere)
Code | The code (used as the code in the resource instance). If the code is in italics, this indicates that the code is not selectable ('Abstract')
Display | The display (used in the display element of a Coding). If there is no display, implementers should not simply display the code, but map the concept into their application
Definition | An explanation of the meaning of the concept
Comments | Additional notes about how to use the code

4.2.12.57 Code System urn:iso-astm:E1762-95:2013

URL: https://hl7.org/fhir/STU3/codesystem-signature-type.html

This page is part of the FHIR Specification (v3.0.2: STU 3). The current version which supercedes this version is 4.0.1. For a full list of available versions, see the Directory of published versions

Vocabulary Work Group | Maturity Level: 0 | Informative | Use Context: Not Intended for Production use

This is a code system defined at http://www.astm.org/ .

Summary

Defining URL: | urn:iso-astm:E1762-95:2013
Name: | Signature Type Codes
Definition: | The Digital Signature Purposes, an indication of the reason an entity signs a document. This is included in the signed information and can be used when determining accountability for various actions concerning the document. Examples include: author, transcriptionist/recorder, and witness.
Committee: | FHIR Infrastructure Work Group
OID: | 2.16.840.1.113883.4.642.1.57 (for OID based terminology systems)
Copyright: | These codes are excerpted from ASTM Standard, E1762-95(2013) - Standard Guide for Electronic Authentication of Health Care Information, Copyright by ASTM International, 100 Barr Harbor Drive, West Conshohocken, PA 19428. Copies of this standard are available through the ASTM Web Site at www.astm.org.
Source Resource | XML / JSON

This Code system is used in the following value sets:

* Signature Type Codes (The Digital Signature Purposes, an indication of the reason an entity signs a document. This is included in the signed information and can be used when determining accountability for various actions concerning the document. Examples include: author, transcriptionist/recorder, and witness.)

4.2.12.57.1 Content

4.2.12.57.2 Signature Type Codes

The Digital Signature Purposes, an indication of the reason an entity signs a document. This is included in the signed information and can be used when determining accountability for various actions concerning the document. Examples include: author, transcriptionist/recorder, and witness.

Copyright Statement: These codes are excerpted from ASTM Standard, E1762-95(2013) - Standard Guide for Electronic Authentication of Health Care Information, Copyright by ASTM International, 100 Barr Harbor Drive, West Conshohocken, PA 19428. Copies of this standard are available through the ASTM Web Site at www.astm.org.

This code system urn:iso-astm:E1762-95:2013 defines the following codes:

Code | Display | Definition
1.2.840.10065.1.12.1.1 | Author's Signature | the signature of the primary or sole author of a health information document. There can be only one primary author of a health information document.
1.2.840.10065.1.12.1.2 | Coauthor's Signature | the signature of a health information document coauthor. There can be multiple coauthors of a health information document.
1.2.840.10065.1.12.1.3 | Co-participant's Signature | the signature of an individual who is a participant in the health information document but is not an author or coauthor. (Example a surgeon who is required by institutional, regulatory, or legal rules to sign an operative report, but who was not involved in the authorship of that report.)

1.2.840.10065.1.12.1.4 | Transcriptionist/Recorder Signature | the signature of an individual who has transcribed a dictated document or recorded written text into a digital machine readable format.
1.2.840.10065.1.12.1.5 | Verification Signature | a signature verifying the information contained in a document. (Example a physician is required to countersign a verbal order that has previously been recorded in the medical record by a registered nurse who has carried out the verbal order.)
1.2.840.10065.1.12.1.6 | Validation Signature | a signature validating a health information document for inclusion in the patient record. (Example a medical student or resident is credentialed to perform history or physical examinations and to write progress notes. The attending physician signs the history and physical examination to validate the entry for inclusion in the patient's medical record.)
1.2.840.10065.1.12.1.7 | Consent Signature | the signature of an individual consenting to what is described in a health information document.
1.2.840.10065.1.12.1.8 | Signature Witness Signature | the signature of a witness to any other signature.
1.2.840.10065.1.12.1.9 | Event Witness Signature | the signature of a witness to an event. (Example the witness has observed a procedure and is attesting to this fact.)
1.2.840.10065.1.12.1.10 | Identity Witness Signature | the signature of an individual who has witnessed another individual who is known to them signing a document. (Example the identity witness is a notary public.)
1.2.840.10065.1.12.1.11 | Consent Witness Signature | the signature of an individual who has witnessed the health care provider counselling a patient.
1.2.840.10065.1.12.1.12 | Interpreter Signature | the signature of an individual who has translated health care information during an event or the obtaining of consent to a treatment.
1.2.840.10065.1.12.1.13 | Review Signature | the signature of a person, device, or algorithm that has reviewed or filtered data for inclusion into the patient record. (Examples: (1) a medical records clerk who scans a document for inclusion in the medical record, enters header information, or catalogues and classifies the data, or a combination thereof; (2) a gateway that receives data from another computer system and interprets that data or changes its format, or both, before entering it into the patient record.)
1.2.840.10065.1.12.1.14 | Source Signature | the signature of an automated data source. (Examples: (1) the signature for an image that is generated by a device for inclusion in the patient record; (2) the signature for an ECG derived by an ECG system for inclusion in the patient record; (3) the data from a biomedical monitoring device or system that is for inclusion in the patient record.)
1.2.840.10065.1.12.1.15 | Addendum Signature | the signature on a new amended document of an individual who has corrected, edited, or amended an original health information document. An addendum signature can either be a signature type or a signature sub-type (see 8.1). Any document with an addendum signature shall have a companion document that is the original document with its original, unaltered content, and original signatures. The original document shall be referenced via an attribute in the new document, which contains, for example, the digest of the old document. Whether the original, unaltered, document is always displayed with the addended document is a local matter, but the original, unaltered, document must remain as part of the patient record and be retrievable on demand.
1.2.840.10065.1.12.1.16 | Modification Signature | the signature on an original document of an individual who has generated a new amended document. This (original) document shall reference the new document via an additional signature purpose. This is the inverse of an addendum signature and provides a pointer from the original to the amended document.
1.2.840.10065.1.12.1.17 | Administrative (Error/Edit) Signature | the signature of an individual who is certifying that the document is invalidated by an error(s), or is placed in the wrong chart. An administrative (error/edit) signature must include an addendum to the document and therefore shall have an addendum signature sub-type (see 8.1). This signature is reserved for the highest health information system administrative classification, since it is a statement that the entire document is invalidated by the error and that the document should no longer be used for patient care, although for legal reasons the document must remain part of the permanent patient record.
1.2.840.10065.1.12.1.18 | Timestamp Signature | the signature by an entity or device trusted to provide accurate timestamps. This timestamp might be provided, for example, in the signature time attribute.

See the full registry of value sets defined as part of FHIR.

Explanation of the columns that may appear on this page:

Level | A few code lists that FHIR defines are hierarchical - each code is assigned a level. In this scheme, some codes are under other codes, and imply that the code they are under also applies
Source | The source of the definition of the code (when the value set draws in codes defined elsewhere)
Code | The code (used as the code in the resource instance). If the code is in italics, this indicates that the code is not selectable ('Abstract')
Display | The display (used in the display element of a Coding). If there is no display, implementers should not simply display the code, but map the concept into their application
Definition | An explanation of the meaning of the concept
Comments | Additional notes about how to use the code

4.2.12.59 Code System http://hl7.org/fhir/name-use

URL: https://hl7.org/fhir/STU3/codesystem-name-use.html

This page is part of the FHIR Specification (v3.0.2: STU 3). The current version which supercedes this version is 4.0.1. For a full list of available versions, see the Directory of published versions

Vocabulary Work Group | Maturity Level: 0 | Informative | Use Context: Any

This is a code system defined by the FHIR project.

Summary

Defining URL: | http://hl7.org/fhir/name-use
Name: | NameUse
Definition: | The use of a human name
Committee: | FHIR Infrastructure Work Group
OID: | 2.16.840.1.113883.4.642.1.59 (for OID based terminology systems)
Source Resource | XML / JSON

This Code system is used in the following value sets:

* NameUse (The use of a human name)

4.2.12.59.1 Content

4.2.12.59.2 NameUse

The use of a human name

This code system http://hl7.org/fhir/name-use defines the following codes:

Lvl | Code | Display | Definition
1 | usual | Usual | Known as/conventional/the one you normally use
1 | official | Official | The formal name as registered in an official (government) registry, but which name might not be commonly used. May be called "legal name".
1 | temp | Temp | A temporary name. Name.period can provide more detailed information. This may also be used for temporary names assigned at birth or in emergency situations.
1 | nickname | Nickname | A name that is used to address the person in an informal manner, but is not part of their formal or usual name
1 | anonymous | Anonymous | Anonymous assigned name, alias, or pseudonym (used to protect a person's identity for privacy reasons)
1 | old | Old | This name is no longer in use (or was never correct, but retained for records)
2 | maiden | Name changed for Marriage | A name used prior to changing name because of marriage. This name use is for use by applications that collect and store names that were used prior to a marriage. Marriage naming customs vary greatly around the world, and are constantly changing. This term is not gender specific. The use of this term does not imply any particular history for a person's name

See the full registry of value sets defined as part of FHIR.

Explanation of the columns that may appear on this page:

Level | A few code lists that FHIR defines are hierarchical - each code is assigned a level. In this scheme, some codes are under other codes, and imply that the code they are under also applies
Source | The source of the definition of the code (when the value set draws in codes defined elsewhere)
Code | The code (used as the code in the resource instance). If the code is in italics, this indicates that the code is not selectable ('Abstract')
Display | The display (used in the display element of a Coding). If there is no display, implementers should not simply display the code, but map the concept into their application
Definition | An explanation of the meaning of the concept
Comments | Additional notes about how to use the code

4.2.12.61 Code System http://hl7.org/fhir/address-use

URL: https://hl7.org/fhir/STU3/codesystem-address-use.html

This page is part of the FHIR Specification (v3.0.2: STU 3). The current version which supercedes this version is 4.0.1. For a full list of available versions, see the Directory of published versions

Vocabulary Work Group | Maturity Level: 0 | Informative | Use Context: Any

This is a code system defined by the FHIR project.

Summary

Defining URL: | http://hl7.org/fhir/address-use
Name: | AddressUse
Definition: | The use of an address
Committee: | FHIR Infrastructure Work Group
OID: | 2.16.840.1.113883.4.642.1.61 (for OID based terminology systems)
Source Resource | XML / JSON

This Code system is used in the following value sets:

* AddressUse (The use of an address)

4.2.12.61.1 Content

4.2.12.61.2 AddressUse

The use of an address

This code system http://hl7.org/fhir/address-use defines the following codes:

Code | Display | Definition
home | Home | A communication address at a home.
work | Work | An office address. First choice for business related contacts during business hours.
temp | Temporary | A temporary address. The period can provide more detailed information.
old | Old / Incorrect | This address is no longer in use (or was never correct, but retained for records).

See the full registry of value sets defined as part of FHIR.

Explanation of the columns that may appear on this page:

Level | A few code lists that FHIR defines are hierarchical - each code is assigned a level. In this scheme, some codes are under other codes, and imply that the code they are under also applies
Source | The source of the definition of the code (when the value set draws in codes defined elsewhere)
Code | The code (used as the code in the resource instance). If the code is in italics, this indicates that the code is not selectable ('Abstract')
Display | The display (used in the display element of a Coding). If there is no display, implementers should not simply display the code, but map the concept into their application
Definition | An explanation of the meaning of the concept
Comments | Additional notes about how to use the code

4.2.12.63 Code System http://hl7.org/fhir/address-type

URL: https://hl7.org/fhir/STU3/codesystem-address-type.html

This page is part of the FHIR Specification (v3.0.2: STU 3). The current version which supercedes this version is 4.0.1. For a full list of available versions, see the Directory of published versions

Vocabulary Work Group | Maturity Level: 0 | Informative | Use Context: Any

This is a code system defined by the FHIR project.

Summary

Defining URL: | http://hl7.org/fhir/address-type
Name: | AddressType
Definition: | The type of an address (physical / postal)
Committee: | FHIR Infrastructure Work Group
OID: | 2.16.840.1.113883.4.642.1.63 (for OID based terminology systems)
Source Resource | XML / JSON

This Code system is used in the following value sets:

* AddressType (The type of an address (physical / postal))

4.2.12.63.1 Content

4.2.12.63.2 AddressType

The type of an address (physical / postal)

This code system http://hl7.org/fhir/address-type defines the following codes:

Code | Display | Definition
postal | Postal | Mailing addresses - PO Boxes and care-of addresses.
physical | Physical | A physical address that can be visited.
both | Postal & Physical | An address that is both physical and postal.

See the full registry of value sets defined as part of FHIR.

Explanation of the columns that may appear on this page:

Level | A few code lists that FHIR defines are hierarchical - each code is assigned a level. In this scheme, some codes are under other codes, and imply that the code they are under also applies
Source | The source of the definition of the code (when the value set draws in codes defined elsewhere)
Code | The code (used as the code in the resource instance). If the code is in italics, this indicates that the code is not selectable ('Abstract')
Display | The display (used in the display element of a Coding). If there is no display, implementers should not simply display the code, but map the concept into their application
Definition | An explanation of the meaning of the concept
Comments | Additional notes about how to use the code

4.2.12.65 Code System http://hl7.org/fhir/contact-point-system

URL: https://hl7.org/fhir/STU3/codesystem-contact-point-system.html

This page is part of the FHIR Specification (v3.0.2: STU 3). The current version which supercedes this version is 4.0.1. For a full list of available versions, see the Directory of published versions

Vocabulary Work Group | Maturity Level: 0 | Informative | Use Context: Any

This is a code system defined by the FHIR project.

Summary

Defining URL: | http://hl7.org/fhir/contact-point-system
Name: | ContactPointSystem
Definition: | Telecommunications form for contact point
Committee: | FHIR Infrastructure Work Group
OID: | 2.16.840.1.113883.4.642.1.65 (for OID based terminology systems)
Source Resource | XML / JSON

This Code system is used in the following value sets:

* ContactPointSystem (Telecommunications form for contact point)

4.2.12.65.1 Content

4.2.12.65.2 ContactPointSystem

Telecommunications form for contact point

This code system http://hl7.org/fhir/contact-point-system defines the following codes:

Code | Display | Definition
phone | Phone | The value is a telephone number used for voice calls. Use of full international numbers starting with + is recommended to enable automatic dialing support but not required.
fax | Fax | The value is a fax machine. Use of full international numbers starting with + is recommended to enable automatic dialing support but not required.
email | Email | The value is an email address.
pager | Pager | The value is a pager number. These may be local pager numbers that are only usable on a particular pager system.

url | URL | A contact that is not a phone, fax, pager or email address and is expressed as a URL. This is intended for various personal contacts including blogs, Skype, Twitter, Facebook, etc. Do not use for email addresses.

sms | SMS | A contact that can be used for sending an sms message (e.g. mobide phones, some landlines)

other | Other | A contact that is not a phone, fax, page or email address and is not expressible as a URL. E.g. Internal mail address. This SHOULD NOT be used for contacts that are expressible as a URL (e.g. Skype, Twitter, Facebook, etc.) Extensions may be used to distinguish "other" contact types.

See the full registry of value sets defined as part of FHIR.

Explanation of the columns that may appear on this page:

Level | A few code lists that FHIR defines are hierarchical - each code is assigned a level. In this scheme, some codes are under other codes, and imply that the code they are under also applies

Source | The source of the definition of the code (when the value set draws in codes defined elsewhere)

Code | The code (used as the code in the resource instance). If the code is in italics, this indicates that the code is not selectable ('Abstract')

Display | The display (used in the display element of a Coding). If there is no display, implementers should not simply display the code, but map the concept into their application

Definition | An explanation of the meaning of the concept

Comments | Additional notes about how to use the code

4.2.12.67 Code System http://hl7.org/fhir/contact-point-use

URL: https://hl7.org/fhir/STU3/codesystem-contact-point-use.html

This page is part of the FHIR Specification (v3.0.2: STU 3). The current version which supercedes this version is 4.0.1. For a full list of available versions, see the Directory of published versions

Vocabulary Work Group | Maturity Level: 0 | Informative | Use Context: Any

This is a code system defined by the FHIR project.

Summary

Defining URL: | http://hl7.org/fhir/contact-point-use

Name: | ContactPointUse

Definition: | Use of contact point

Committee: | FHIR Infrastructure Work Group

OID: | 2.16.840.1.113883.4.642.1.67 (for OID based terminology systems)

Source Resource | XML / JSON

This Code system is used in the following value sets:

* ContactPointUse (Use of contact point)

4.2.12.67.1 Content

4.2.12.67.2 ContactPointUse

Use of contact point

This code system http://hl7.org/fhir/contact-point-use defines the following codes:

Code | Display | Definition

home | Home | A communication contact point at a home; attempted contacts for business purposes might intrude privacy and chances are one will contact family or other household members instead of the person one wishes to call. Typically used with urgent cases, or if no other contacts are available.

work | Work | An office contact point. First choice for business related contacts during business hours.

temp | Temp | A temporary contact point. The period can provide more detailed information.

old | Old | This contact point is no longer in use (or was never correct, but retained for records).

mobile | Mobile | A telecommunication device that moves and stays with its owner. May have characteristics of all other use codes, suitable for urgent matters, not the first choice for routine business.

See the full registry of value sets defined as part of FHIR.

Explanation of the columns that may appear on this page:

Level | A few code lists that FHIR defines are hierarchical - each code is assigned a level. In this scheme, some codes are under other codes, and imply that the code they are under also applies

Source | The source of the definition of the code (when the value set draws in codes defined elsewhere)

Code | The code (used as the code in the resource instance). If the code is in italics, this indicates that the code is not selectable ('Abstract')

Display | The display (used in the display element of a Coding). If there is no display, implementers should not simply display the code, but map the concept into their application

Definition | An explanation of the meaning of the concept

Comments | Additional notes about how to use the code

4.2.12.69 Code System http://hl7.org/fhir/event-timing

URL: https://hl7.org/fhir/STU3/codesystem-event-timing.html

This page is part of the FHIR Specification (v3.0.2: STU 3). The current version which supercedes this version is 4.0.1. For a full list of available versions, see the Directory of published versions

Vocabulary Work Group | Maturity Level: 0 | Informative | Use Context: Any

This is a code system defined by the FHIR project.

Summary

Defining URL: | http://hl7.org/fhir/event-timing
Name: | EventTiming
Definition: | Real world event relating to the schedule.
Committee: | FHIR Infrastructure Work Group
OID: | 2.16.840.1.113883.4.642.1.69 (for OID based terminology systems)
Source Resource | XML / JSON

This Code system is used in the following value sets:

* EventTiming (Real world event relating to the schedule.)

4.2.12.69.1 Content

4.2.12.69.2 EventTiming

Real world event relating to the schedule.

This code system http://hl7.org/fhir/event-timing defines the following codes:

Code | Display | Definition
MORN | Morning | event occurs during the morning
AFT | Afternoon | event occurs during the afternoon
EVE | Evening | event occurs during the evening
NIGHT | Night | event occurs during the night
PHS | After Sleep | event occurs [offset] after subject goes to sleep

See the full registry of value sets defined as part of FHIR.

Explanation of the columns that may appear on this page:

Level | A few code lists that FHIR defines are hierarchical - each code is assigned a level. In this scheme, some codes are under other codes, and imply that the code they are under also applies
Source | The source of the definition of the code (when the value set draws in codes defined elsewhere)
Code | The code (used as the code in the resource instance). If the code is in italics, this indicates that the code is not selectable ('Abstract')
Display | The display (used in the display element of a Coding). If there is no display, implementers should not simply display the code, but map the concept into their application
Definition | An explanation of the meaning of the concept
Comments | Additional notes about how to use the code

4.2.12.73 Code System http://hl7.org/fhir/common-tags

URL: https://hl7.org/fhir/STU3/codesystem-common-tags.html

This page is part of the FHIR Specification (v3.0.2: STU 3). The current version which supercedes this version is 4.0.1. For a full list of available versions, see the Directory of published versions

Vocabulary Work Group | Maturity Level: 1 | Informative | Use Context: Not Intended for Production use

This is a code system defined by the FHIR project.

Summary

Defining URL: | http://hl7.org/fhir/common-tags
Name: | Common Tags
Definition: | Common Tag Codes defined by FHIR project
Committee: | FHIR Infrastructure Work Group
OID: | 2.16.840.1.113883.4.642.1.73 (for OID based terminology systems)
Source Resource | XML / JSON

This Code system is used in the following value sets:

* Common Tags (Common Tag Codes defined by FHIR project)

4.2.12.73.1 Content

4.2.12.73.2 Common Tags

Common Tag Codes defined by FHIR project

This code system http://hl7.org/fhir/common-tags defines the following codes:

Code | Display | Definition
actionable | Actionable | This request is intended to be acted upon, not merely stored

See the full registry of value sets defined as part of FHIR.

Explanation of the columns that may appear on this page:

Level | A few code lists that FHIR defines are hierarchical - each code is assigned a level. In this scheme, some codes are under other codes, and imply that the code they are under also applies
Source | The source of the definition of the code (when the value set draws in codes defined elsewhere)
Code | The code (used as the code in the resource instance). If the code is in italics, this indicates that the code is not selectable ('Abstract')
Display | The display (used in the display element of a Coding). If there is no display, implementers should not simply display the code, but map the concept into their application

Definition | An explanation of the meaning of the concept
Comments | Additional notes about how to use the code

4.2.12.75 Code System http://hl7.org/fhir/constraint-severity

URL: https://hl7.org/fhir/STU3/codesystem-constraint-severity.html

This page is part of the FHIR Specification (v3.0.2: STU 3). The current version which supercedes this version is 4.0.1. For a full list of available versions, see the Directory of published versions

Vocabulary Work Group | Maturity Level: 0 | Informative | Use Context: Any

This is a code system defined by the FHIR project.

Summary

Defining URL: | http://hl7.org/fhir/constraint-severity
Name: | ConstraintSeverity
Definition: | SHALL applications comply with this constraint?
Committee: | FHIR Infrastructure Work Group
OID: | 2.16.840.1.113883.4.642.1.75 (for OID based terminology systems)
Source Resource | XML / JSON

This Code system is used in the following value sets:

* ConstraintSeverity (SHALL applications comply with this constraint?)

4.2.12.75.1 Content

4.2.12.75.2 ConstraintSeverity

SHALL applications comply with this constraint?

This code system http://hl7.org/fhir/constraint-severity defines the following codes:

Code | Display | Definition
error | Error | If the constraint is violated, the resource is not conformant.
warning | Warning | If the constraint is violated, the resource is conformant, but it is not necessarily following best practice.

See the full registry of value sets defined as part of FHIR.

Explanation of the columns that may appear on this page:

Level | A few code lists that FHIR defines are hierarchical - each code is assigned a level. In this scheme, some codes are under other codes, and imply that the code they are under also applies
Source | The source of the definition of the code (when the value set draws in codes defined elsewhere)
Code | The code (used as the code in the resource instance). If the code is in italics, this indicates that the code is not selectable ('Abstract')
Display | The display (used in the display element of a Coding). If there is no display, implementers should not simply display the code, but map the concept into their application
Definition | An explanation of the meaning of the concept
Comments | Additional notes about how to use the code

4.2.12.77 Code System http://hl7.org/fhir/resource-slicing-rules

URL: https://hl7.org/fhir/STU3/codesystem-resource-slicing-rules.html

This page is part of the FHIR Specification (v3.0.2: STU 3). The current version which supercedes this version is 4.0.1. For a full list of available versions, see the Directory of published versions

Vocabulary Work Group | Maturity Level: 0 | Informative | Use Context: Any

This is a code system defined by the FHIR project.

Summary

Defining URL: | http://hl7.org/fhir/resource-slicing-rules
Name: | SlicingRules
Definition: | How slices are interpreted when evaluating an instance.
Committee: | FHIR Infrastructure Work Group
OID: | 2.16.840.1.113883.4.642.1.77 (for OID based terminology systems)
Source Resource | XML / JSON

This Code system is used in the following value sets:

* SlicingRules (How slices are interpreted when evaluating an instance.)

4.2.12.77.1 Content

4.2.12.77.2 SlicingRules

How slices are interpreted when evaluating an instance.

This code system http://hl7.org/fhir/resource-slicing-rules defines the following codes:

Code | Display | Definition
closed | Closed | No additional content is allowed other than that described by the slices in this profile.

open | Open | Additional content is allowed anywhere in the list.
openAtEnd | Open at End | Additional content is allowed, but only at the end of the list. Note that using this requires that the slices be ordered, which makes it hard to share uses. This should only be done where absolutely required.

See the full registry of value sets defined as part of FHIR.

Explanation of the columns that may appear on this page:

Level | A few code lists that FHIR defines are hierarchical - each code is assigned a level. In this scheme, some codes are under other codes, and imply that the code they are under also applies
Source | The source of the definition of the code (when the value set draws in codes defined elsewhere)
Code | The code (used as the code in the resource instance). If the code is in italics, this indicates that the code is not selectable ('Abstract')
Display | The display (used in the display element of a Coding). If there is no display, implementers should not simply display the code, but map the concept into their application
Definition | An explanation of the meaning of the concept
Comments | Additional notes about how to use the code

4.2.12.79 Code System http://hl7.org/fhir/resource-aggregation-mode

URL: https://hl7.org/fhir/STU3/codesystem-resource-aggregation-mode.html

This page is part of the FHIR Specification (v3.0.2: STU 3). The current version which supercedes this version is 4.0.1. For a full list of available versions, see the Directory of published versions

Vocabulary Work Group | Maturity Level: 0 | Informative | Use Context: Any

This is a code system defined by the FHIR project.

Summary

Defining URL: | http://hl7.org/fhir/resource-aggregation-mode
Name: | AggregationMode
Definition: | How resource references can be aggregated.
Committee: | FHIR Infrastructure Work Group
OID: | 2.16.840.1.113883.4.642.1.79 (for OID based terminology systems)
Source Resource | XML / JSON

This Code system is used in the following value sets:

* AggregationMode (How resource references can be aggregated.)

4.2.12.79.1 Content

4.2.12.79.2 AggregationMode

How resource references can be aggregated.

This code system http://hl7.org/fhir/resource-aggregation-mode defines the following codes:

Lvl | Code | Display | Definition
1 | contained | Contained | The reference is a local reference to a contained resource.
1 | referenced | Referenced | The reference to a resource that has to be resolved externally to the resource that includes the reference.
2 | bundled | Bundled | The resource the reference points to will be found in the same bundle as the resource that includes the reference.

See the full registry of value sets defined as part of FHIR.

Explanation of the columns that may appear on this page:

Level | A few code lists that FHIR defines are hierarchical - each code is assigned a level. In this scheme, some codes are under other codes, and imply that the code they are under also applies
Source | The source of the definition of the code (when the value set draws in codes defined elsewhere)
Code | The code (used as the code in the resource instance). If the code is in italics, this indicates that the code is not selectable ('Abstract')
Display | The display (used in the display element of a Coding). If there is no display, implementers should not simply display the code, but map the concept into their application
Definition | An explanation of the meaning of the concept
Comments | Additional notes about how to use the code

4.2.12.81 Code System http://hl7.org/fhir/property-representation

URL: https://hl7.org/fhir/STU3/codesystem-property-representation.html

This page is part of the FHIR Specification (v3.0.2: STU 3). The current version which supercedes this version is 4.0.1. For a full list of available versions, see the Directory of published versions

Vocabulary Work Group | Maturity Level: 0 | Informative | Use Context: Any

This is a code system defined by the FHIR project.

Summary

Defining URL: | http://hl7.org/fhir/property-representation
Name: | PropertyRepresentation
Definition: | How a property is represented when serialized.
Committee: | FHIR Infrastructure Work Group
OID: | 2.16.840.1.113883.4.642.1.81 (for OID based terminology systems)
Source Resource | XML / JSON

This Code system is used in the following value sets:

* PropertyRepresentation (How a property is represented when serialized.)

4.2.12.81.1 Content

4.2.12.81.2 PropertyRepresentation

How a property is represented when serialized.

This code system http://hl7.org/fhir/property-representation defines the following codes:

Code	Display	Definition
xmlAttr	XML Attribute	In XML, this property is represented as an attribute not an element.
xmlText	XML Text	This element is represented using the XML text attribute (primitives only)
typeAttr	Type Attribute	The type of this element is indicated using xsi:type
cdaText	CDA Text Format	Use CDA narrative instead of XHTML
xhtml	XHTML	The property is represented using XHTML

See the full registry of value sets defined as part of FHIR.

Explanation of the columns that may appear on this page:

Level	A few code lists that FHIR defines are hierarchical - each code is assigned a level. In this scheme, some codes are under other codes, and imply that the code they are under also applies
Source	The source of the definition of the code (when the value set draws in codes defined elsewhere)
Code	The code (used as the code in the resource instance). If the code is in italics, this indicates that the code is not selectable ('Abstract')
Display	The display (used in the display element of a Coding). If there is no display, implementers should not simply display the code, but map the concept into their application
Definition	An explanation of the meaning of the concept
Comments	Additional notes about how to use the code

4.2.12.83 Code System http://hl7.org/fhir/reference-version-rules

URL: https://hl7.org/fhir/STU3/codesystem-reference-version-rules.html

This page is part of the FHIR Specification (v3.0.2: STU 3). The current version which supercedes this version is 4.0.1. For a full list of available versions, see the Directory of published versions

Vocabulary Work Group | Maturity Level: 0 | Informative | Use Context: Any

This is a code system defined by the FHIR project.

Summary

Defining URL:	http://hl7.org/fhir/reference-version-rules
Name:	ReferenceVersionRules
Definition:	Whether a reference needs to be version specific or version independent, or whether either can be used
Committee:	FHIR Infrastructure Work Group
OID:	2.16.840.1.113883.4.642.1.83 (for OID based terminology systems)
Source Resource	XML / JSON

This Code system is used in the following value sets:

* ReferenceVersionRules (Whether a reference needs to be version specific or version independent, or whether either can be used)

4.2.12.83.1 Content

4.2.12.83.2 ReferenceVersionRules

Whether a reference needs to be version specific or version independent, or whether either can be used

This code system http://hl7.org/fhir/reference-version-rules defines the following codes:

Code	Display	Definition
either	Either Specific or independent	The reference may be either version independent or version specific
independent	Version independent	The reference must be version independent
specific	Version Specific	The reference must be version specific

See the full registry of value sets defined as part of FHIR.

Explanation of the columns that may appear on this page:

Level	A few code lists that FHIR defines are hierarchical - each code is assigned a level. In this scheme, some codes are under other codes, and imply that the code they are under also applies
Source	The source of the definition of the code (when the value set draws in codes defined elsewhere)
Code	The code (used as the code in the resource instance). If the code is in italics, this indicates that the code is not selectable ('Abstract')
Display	The display (used in the display element of a Coding). If there is no display, implementers should not simply display the code, but map the concept into their application
Definition	An explanation of the meaning of the concept
Comments	Additional notes about how to use the code

4.2.12.85 Code System http://hl7.org/fhir/discriminator-type

URL: https://hl7.org/fhir/STU3/codesystem-discriminator-type.html

This page is part of the FHIR Specification (v3.0.2: STU 3). The current version which supercedes this version is 4.0.1. For a full list of available versions, see the Directory of published versions

Vocabulary Work Group | Maturity Level: 0 | Informative | Use Context: Any

This is a code system defined by the FHIR project.

Summary

Defining URL: | http://hl7.org/fhir/discriminator-type
Name: | DiscriminatorType
Definition: | How an element value is interpreted when discrimination is evaluated
Committee: | FHIR Infrastructure Work Group
OID: | 2.16.840.1.113883.4.642.1.85 (for OID based terminology systems)
Source Resource | XML / JSON

This Code system is used in the following value sets:

* DiscriminatorType (How an element value is interpreted when discrimination is evaluated)

4.2.12.85.1 Content

4.2.12.85.2 DiscriminatorType

How an element value is interpreted when discrimination is evaluated

This code system http://hl7.org/fhir/discriminator-type defines the following codes:

Code | Display | Definition
value | Value | The slices have different values in the nominated element
exists | Exists | The slices are differentiated by the presence or absence of the nominated element
pattern | Pattern | The slices have different values in the nominated element, as determined by testing them against the applicable ElementDefinition.pattern[x]
type | Type | The slices are differentiated by type of the nominated element to a specifed profile
profile | Profile | The slices are differentiated by conformance of the nominated element to a specifed profile

See the full registry of value sets defined as part of FHIR.

Explanation of the columns that may appear on this page:

Level | A few code lists that FHIR defines are hierarchical - each code is assigned a level. In this scheme, some codes are under other codes, and imply that the code they are under also applies
Source | The source of the definition of the code (when the value set draws in codes defined elsewhere)
Code | The code (used as the code in the resource instance). If the code is in italics, this indicates that the code is not selectable ('Abstract')
Display | The display (used in the display element of a Coding). If there is no display, implementers should not simply display the code, but map the concept into their application
Definition | An explanation of the meaning of the concept
Comments | Additional notes about how to use the code

4.2.12.87 Code System http://hl7.org/fhir/contributor-type

URL: https://hl7.org/fhir/STU3/codesystem-contributor-type.html

This page is part of the FHIR Specification (v3.0.2: STU 3). The current version which supercedes this version is 4.0.1. For a full list of available versions, see the Directory of published versions

Vocabulary Work Group | Maturity Level: 0 | Informative | Use Context: Any

This is a code system defined by the FHIR project.

Summary

Defining URL: | http://hl7.org/fhir/contributor-type
Name: | ContributorType
Definition: | The type of contributor
Committee: | FHIR Infrastructure Work Group
OID: | 2.16.840.1.113883.4.642.1.87 (for OID based terminology systems)
Source Resource | XML / JSON

This Code system is used in the following value sets:

* ContributorType (The type of contributor)

4.2.12.87.1 Content

4.2.12.87.2 ContributorType

The type of contributor

This code system http://hl7.org/fhir/contributor-type defines the following codes:

Code | Display | Definition
author | Author | An author of the content of the module

editor | Editor | An editor of the content of the module
reviewer | Reviewer | A reviewer of the content of the module
endorser | Endorser | An endorser of the content of the module

See the full registry of value sets defined as part of FHIR.

Explanation of the columns that may appear on this page:

Level | A few code lists that FHIR defines are hierarchical - each code is assigned a level. In this scheme, some codes are under other codes, and imply that the code they are under also applies
Source | The source of the definition of the code (when the value set draws in codes defined elsewhere)
Code | The code (used as the code in the resource instance). If the code is in italics, this indicates that the code is not selectable ('Abstract')
Display | The display (used in the display element of a Coding). If there is no display, implementers should not simply display the code, but map the concept into their application
Definition | An explanation of the meaning of the concept
Comments | Additional notes about how to use the code

4.2.12.93 Code System http://hl7.org/fhir/related-artifact-type

URL: https://hl7.org/fhir/STU3/codesystem-related-artifact-type.html

This page is part of the FHIR Specification (v3.0.2: STU 3). The current version which supercedes this version is 4.0.1. For a full list of available versions, see the Directory of published versions

Vocabulary Work Group | Maturity Level: 0 | Informative | Use Context: Any

This is a code system defined by the FHIR project.

Summary

Defining URL: | http://hl7.org/fhir/related-artifact-type
Name: | RelatedArtifactType
Definition: | The type of relationship to the related artifact
Committee: | FHIR Infrastructure Work Group
OID: | 2.16.840.1.113883.4.642.1.93 (for OID based terminology systems)
Source Resource | XML / JSON

This Code system is used in the following value sets:

* RelatedArtifactType (The type of relationship to the related artifact)

4.2.12.93.1 Content

4.2.12.93.2 RelatedArtifactType

The type of relationship to the related artifact

This code system http://hl7.org/fhir/related-artifact-type defines the following codes:

Code | Display | Definition
documentation | Documentation | Additional documentation for the knowledge resource. This would include additional instructions on usage as well as additional information on clinical context or appropriateness
justification | Justification | A summary of the justification for the knowledge resource including supporting evidence, relevant guidelines, or other clinically important information. This information is intended to provide a way to make the justification for the knowledge resource available to the consumer of interventions or results produced by the knowledge resource
citation | Citation | Bibliographic citation for papers, references, or other relevant material for the knowledge resource. This is intended to allow for citation of related material, but that was not necessarily specifically prepared in connection with this knowledge resource
predecessor | Predecessor | The previous version of the knowledge resource
successor | Successor | The next version of the knowledge resource
derived-from | Derived From | The knowledge resource is derived from the related artifact. This is intended to capture the relationship in which a particular knowledge resource is based on the content of another artifact, but is modified to capture either a different set of overall requirements, or a more specific set of requirements such as those involved in a particular institution or clinical setting
depends-on | Depends On | The knowledge resource depends on the given related artifact
composed-of | Composed Of | The knowledge resource is composed of the given related artifact

See the full registry of value sets defined as part of FHIR.

Explanation of the columns that may appear on this page:

Level | A few code lists that FHIR defines are hierarchical - each code is assigned a level. In this scheme, some codes are under other codes, and imply that the code they are under also applies
Source | The source of the definition of the code (when the value set draws in codes defined elsewhere)
Code | The code (used as the code in the resource instance). If the code is in italics, this indicates that the code is not selectable ('Abstract')
Display | The display (used in the display element of a Coding). If there is no display, implementers should not simply display the code, but map the concept into their application
Definition | An explanation of the meaning of the concept
Comments | Additional notes about how to use the code

4.2.12.95 Code System http://hl7.org/fhir/usage-context-type

URL: https://hl7.org/fhir/STU3/codesystem-usage-context-type.html

This page is part of the FHIR Specification (v3.0.2: STU 3). The current version which supercedes this version is 4.0.1. For a full list of available versions, see the Directory of published versions

Vocabulary Work Group | Maturity Level: 0 | Informative | Use Context: Any

This is a code system defined by the FHIR project.

Summary

Defining URL: | http://hl7.org/fhir/usage-context-type
Name: | UsageContextType
Definition: | A code that specifies a type of context being specified by a usage context
Committee: | FHIR Infrastructure Work Group
OID: | 2.16.840.1.113883.4.642.1.95 (for OID based terminology systems)
Source Resource | XML / JSON

This Code system is used in the following value sets:

* UsageContextType (A code that specifies a type of context being specified by a usage context)

4.2.12.95.1 Content

4.2.12.95.2 UsageContextType

A code that specifies a type of context being specified by a usage context

This code system http://hl7.org/fhir/usage-context-type defines the following codes:

Code | Display | Definition
gender | Gender | The gender of the patient. For this context type, the value should be a code taken from the http://hl7.org/fhir/ValueSet/administrative-gender value set
age | Age Range | The age of the patient. For this context type, the value should be a range the specifies the applicable ages or a code from the MeSH value set http://hl7.org/fhir/ValueSet/v3-AgeGroupObservationValue
focus | Clinical Focus | The clinical concept(s) addressed by the artifact. For example, disease, diagnostic test interpretation, medication ordering as in http://hl7.org/fhir/ValueSet/condition-code.
user | User Type | The clinical specialty of the context in which the patient is being treated - For example, PCP, Patient, Cardiologist, Behavioral Professional, Oral Health Professional, Prescriber, etc... taken from the NUCC Health Care provider taxonomy value set http://hl7.org/fhir/ValueSet/provider-taxonomy.
workflow | Workflow Setting | The settings in which the artifact is intended for use. For example, admission, pre-op, etc. For example, the ActEncounterCode value set http://hl7.org/fhir/ValueSet/v3-ActEncounterCode
task | Workflow Task | The context for the clinical task(s) represented by this artifact. Can be any task context represented by the HL7 ActTaskCode value set http://hl7.org/fhir/ValueSet/v3-ActTaskCode. General categories include: order entry, patient documentation and patient information review.
venue | Clinical Venue | The venue in which an artifact could be used. For example, Outpatient, Inpatient, Home, Nursing home. The code value may originate from either the HL7 ActEncounterCode http://hl7.org/fhir/ValueSet/v3-ActEncounterCode or NUCC non-individual provider codes http://hl7.org/fhir/ValueSet/provider-taxonomy
species | Species | The species to which an artifact applies. For example, SNOMED - 387961004 | Kingdom Animalia (organism).

See the full registry of value sets defined as part of FHIR.

Explanation of the columns that may appear on this page:

Level | A few code lists that FHIR defines are hierarchical - each code is assigned a level. In this scheme, some codes are under other codes, and imply that the code they are under also applies
Source | The source of the definition of the code (when the value set draws in codes defined elsewhere)
Code | The code (used as the code in the resource instance). If the code is in italics, this indicates that the code is not selectable ('Abstract')
Display | The display (used in the display element of a Coding). If there is no display, implementers should not simply display the code, but map the concept into their application
Definition | An explanation of the meaning of the concept
Comments | Additional notes about how to use the code

4.2.12.97 Code System http://hl7.org/fhir/trigger-type

URL: https://hl7.org/fhir/STU3/codesystem-trigger-type.html

This page is part of the FHIR Specification (v3.0.2: STU 3). The current version which supercedes this version is 4.0.1. For a full list of available versions, see the Directory of published versions

Vocabulary Work Group | Maturity Level: 0 | Informative | Use Context: Any

This is a code system defined by the FHIR project.

Summary

Defining URL: | http://hl7.org/fhir/trigger-type
Name: | TriggerType
Definition: | The type of trigger
Committee: | FHIR Infrastructure Work Group
OID: | 2.16.840.1.113883.4.642.1.97 (for OID based terminology systems)
Source Resource | XML / JSON

This Code system is used in the following value sets:

* TriggerType (The type of trigger)

4.2.12.97.1 Content

4.2.12.97.2 TriggerType

The type of trigger

This code system http://hl7.org/fhir/trigger-type defines the following codes:

Code | Display | Definition
named-event | Named Event | The trigger occurs in response to a specific named event
periodic | Periodic | The trigger occurs at a specific time or periodically as described by a timing or schedule
data-added | Data Added | The trigger occurs whenever data of a particular type is added
data-modified | Data Modified | The trigger occurs whenever data of a particular type is modified
data-removed | Data Removed | The trigger occurs whenever data of a particular type is removed
data-accessed | Data Accessed | The trigger occurs whenever data of a particular type is accessed
data-access-ended | Data Access Ended | The trigger occurs whenever access to data of a particular type is completed

See the full registry of value sets defined as part of FHIR.

Explanation of the columns that may appear on this page:

Level | A few code lists that FHIR defines are hierarchical - each code is assigned a level. In this scheme, some codes are under other codes, and imply that the code they are under also applies
Source | The source of the definition of the code (when the value set draws in codes defined elsewhere)
Code | The code (used as the code in the resource instance). If the code is in italics, this indicates that the code is not selectable ('Abstract')
Display | The display (used in the display element of a Coding). If there is no display, implementers should not simply display the code, but map the concept into their application
Definition | An explanation of the meaning of the concept
Comments | Additional notes about how to use the code

4.2.12.99 Code System http://hl7.org/fhir/definition-status

URL: https://hl7.org/fhir/STU3/codesystem-definition-status.html

This page is part of the FHIR Specification (v3.0.2: STU 3). The current version which supercedes this version is 4.0.1. For a full list of available versions, see the Directory of published versions

Vocabulary Work Group | Maturity Level: 0 | Informative | Use Context: Any

This is a code system defined by the FHIR project.

Summary

Defining URL: | http://hl7.org/fhir/definition-status
Name: | DefinitionStatus
Definition: | Codes identifying the lifecycle stage of a definition
Committee: | FHIR Infrastructure Work Group
OID: | 2.16.840.1.113883.4.642.1.99 (for OID based terminology systems)
Source Resource | XML / JSON

This Code system is used in the following value sets:

* DefinitionStatus (Codes identifying the lifecycle stage of a definition)

4.2.12.99.1 Content

4.2.12.99.2 DefinitionStatus

Codes identifying the lifecycle stage of a definition

This code system http://hl7.org/fhir/definition-status defines the following codes:

Code | Display | Definition
draft | Draft | The definition is in the design stage and is not yet considered to be "ready for use"
active | Active | The definition is considered ready for use
withdrawn | Withdrawn | The definition should no longer be used
unknown | Unknown | The authoring system does not know which of the status values currently applies for this request. Note: This concept is not to be used for "other" - one of the listed statuses is presumed to apply, it's just not known which one.

See the full registry of value sets defined as part of FHIR.

Explanation of the columns that may appear on this page:

Level | A few code lists that FHIR defines are hierarchical - each code is assigned a level. In this scheme, some codes are under other codes, and imply that the code they are under also applies
Source | The source of the definition of the code (when the value set draws in codes defined elsewhere)
Code | The code (used as the code in the resource instance). If the code is in italics, this indicates that the code is not selectable ('Abstract')
Display | The display (used in the display element of a Coding). If there is no display, implementers should not simply display the code, but map the concept into their application
Definition | An explanation of the meaning of the concept
Comments | Additional notes about how to use the code

4.2.12.101 Code System http://hl7.org/fhir/event-status

URL: https://hl7.org/fhir/STU3/codesystem-event-status.html

This page is part of the FHIR Specification (v3.0.2: STU 3). The current version which supercedes this version is 4.0.1. For a full list of available versions, see the Directory of published versions

Vocabulary Work Group | Maturity Level: 3 | Informative | Use Context: Any

This is a code system defined by the FHIR project.

Summary

Defining URL: | http://hl7.org/fhir/event-status
Name: | EventStatus
Definition: | Codes identifying the stage lifecycle stage of a event
Committee: | FHIR Infrastructure Work Group
OID: | 2.16.840.1.113883.4.642.1.101 (for OID based terminology systems)
Source Resource | XML / JSON

This Code system is used in the following value sets:

* EventStatus (Codes identifying the stage lifecycle stage of a event)

4.2.12.101.1 Content

4.2.12.101.2 EventStatus

Codes identifying the stage lifecycle stage of a event

This code system http://hl7.org/fhir/event-status defines the following codes:

Code | Display | Definition
preparation | Preparation | The core event has not started yet, but some staging activities have begun (e.g. surgical suite preparation). Preparation stages may be tracked for billing purposes.
in-progress | In Progress | The event is currently occurring
suspended | Suspended | The event has been temporarily stopped but is expected to resume in the future
aborted | Aborted | The event was prior to the full completion of the intended actions
completed | Completed | The event has now concluded
entered-in-error | Entered in Error | This electronic record should never have existed, though it is possible that real-world decisions were based on it. (If real-world activity has occurred, the status should be "cancelled" rather than "entered-in-error".)
unknown | Unknown | The authoring system does not know which of the status values currently applies for this request. Note: This concept is not to be used for "other" - one of the listed statuses is presumed to apply, it's just not known which one.

See the full registry of value sets defined as part of FHIR.

Explanation of the columns that may appear on this page:

Level | A few code lists that FHIR defines are hierarchical - each code is assigned a level. In this scheme, some codes are under other codes, and imply that the code they are under also applies
Source | The source of the definition of the code (when the value set draws in codes defined elsewhere)
Code | The code (used as the code in the resource instance). If the code is in italics, this indicates that the code is not selectable ('Abstract')
Display | The display (used in the display element of a Coding). If there is no display, implementers should not simply display the code, but map the concept into their application
Definition | An explanation of the meaning of the concept
Comments | Additional notes about how to use the code

4.2.12.103 Code System http://hl7.org/fhir/request-status

URL: https://hl7.org/fhir/STU3/codesystem-request-status.html

This page is part of the FHIR Specification (v3.0.2: STU 3). The current version which supercedes this version is 4.0.1. For a full list of available versions, see the Directory of published versions

Vocabulary Work Group | Maturity Level: 3 | Informative | Use Context: Any

This is a code system defined by the FHIR project.

Summary

Defining URL: | http://hl7.org/fhir/request-status
Name: | RequestStatus
Definition: | Codes identifying the stage lifecycle stage of a request
Committee: | FHIR Infrastructure Work Group
OID: | 2.16.840.1.113883.4.642.1.103 (for OID based terminology systems)
Source Resource | XML / JSON

This Code system is used in the following value sets:

* RequestStatus (Codes identifying the stage lifecycle stage of a request)

4.2.12.103.1 Content

4.2.12.103.2 RequestStatus

Codes identifying the stage lifecycle stage of a request

This code system http://hl7.org/fhir/request-status defines the following codes:

Code | Display | Definition

draft | Draft | The request has been created but is not yet complete or ready for action
active | Active | The request is ready to be acted upon
suspended | Suspended | The authorization/request to act has been temporarily withdrawn but is expected to resume in the future
cancelled | Cancelled | The authorization/request to act has been terminated prior to the full completion of the intended actions. No further activity should occur.
completed | Completed | Activity against the request has been sufficiently completed to the satisfaction of the requester
entered-in-error | Entered in Error | This electronic record should never have existed, though it is possible that real-world decisions were based on it. (If real-world activity has occurred, the status should be "cancelled" rather than "entered-in-error".)
unknown | Unknown | The authoring system does not know which of the status values currently applies for this request. Note: This concept is not to be used for "other" . One of the listed statuses is presumed to apply, but the system creating the request doesn't know.

See the full registry of value sets defined as part of FHIR.

Explanation of the columns that may appear on this page:

Level | A few code lists that FHIR defines are hierarchical - each code is assigned a level. In this scheme, some codes are under other codes, and imply that the code they are under also applies
Source | The source of the definition of the code (when the value set draws in codes defined elsewhere)
Code | The code (used as the code in the resource instance). If the code is in italics, this indicates that the code is not selectable ('Abstract')
Display | The display (used in the display element of a Coding). If there is no display, implementers should not simply display the code, but map the concept into their application
Definition | An explanation of the meaning of the concept
Comments | Additional notes about how to use the code

4.2.12.105 Code System http://hl7.org/fhir/request-intent

URL: https://hl7.org/fhir/STU3/codesystem-request-intent.html

This page is part of the FHIR Specification (v3.0.2: STU 3). The current version which supercedes this version is 4.0.1. For a full list of available versions, see the Directory of published versions

Vocabulary Work Group | Maturity Level: 3 | Informative | Use Context: Any

This is a code system defined by the FHIR project.

Summary

Defining URL: | http://hl7.org/fhir/request-intent
Name: | RequestIntent
Definition: | Codes indicating the degree of authority/intentionality associated with a request
Committee: | FHIR Infrastructure Work Group
OID: | 2.16.840.1.113883.4.642.1.105 (for OID based terminology systems)
Source Resource | XML / JSON

This Code system is used in the following value sets:

* RequestIntent (Codes indicating the degree of authority/intentionality associated with a request)

4.2.12.105.1 Content

4.2.12.105.2 RequestIntent

Codes indicating the degree of authority/intentionality associated with a request

This code system http://hl7.org/fhir/request-intent defines the following codes:

Lvl | Code | Display | Definition
1 | proposal | Proposal | The request is a suggestion made by someone/something that doesn't have an intention to ensure it occurs and without providing an authorization to act
1 | plan | Plan | The request represents an intension to ensure something occurs without providing an authorization for others to act
1 | order | Order | The request represents a request/demand and authorization for action
2 | original-order | Original Order | The request represents an original authorization for action
2 | reflex-order | Reflex Order | The request represents an automatically generated supplemental authorization for action based on a parent authorization together with initial results of the action taken against that parent authorization
2 | filler-order | Filler Order | The request represents the view of an authorization instantiated by a fulfilling system representing the details of the fulfiller's intention to act upon a submitted order
3 | instance-order | Instance Order | An order created in fulfillment of a broader order that represents the authorization for a single activity occurrence. E.g. The administration of a single dose of a drug.
1 | option | Option | The request represents a component or option for a RequestGroup that establishes timing, conditionality and/or other constraints among a set of requests. Refer to [[[RequestGroup]]] for additional information on how this status is used

See the full registry of value sets defined as part of FHIR.

Explanation of the columns that may appear on this page:

Level | A few code lists that FHIR defines are hierarchical - each code is assigned a level. In this scheme, some codes are under other codes, and imply that the code they are under also applies
Source | The source of the definition of the code (when the value set draws in codes defined elsewhere)
Code | The code (used as the code in the resource instance). If the code is in italics, this indicates that the code is not selectable ('Abstract')
Display | The display (used in the display element of a Coding). If there is no display, implementers should not simply display the code, but map the concept into their application
Definition | An explanation of the meaning of the concept
Comments | Additional notes about how to use the code

4.2.12.107 Code System http://hl7.org/fhir/request-priority

URL: https://hl7.org/fhir/STU3/codesystem-request-priority.html

This page is part of the FHIR Specification (v3.0.2: STU 3). The current version which supercedes this version is 4.0.1. For a full list of available versions, see the Directory of published versions

Vocabulary Work Group | Maturity Level: 0 | Informative | Use Context: Any

This is a code system defined by the FHIR project.

Summary

Defining URL: | http://hl7.org/fhir/request-priority
Name: | RequestPriority
Definition: | Identifies the level of importance to be assigned to actioning the request
Committee: | FHIR Infrastructure Work Group
OID: | 2.16.840.1.113883.4.642.1.107 (for OID based terminology systems)
Source Resource | XML / JSON

This Code system is used in the following value sets:

* RequestPriority (The clinical priority of a diagnostic order.)

4.2.12.107.1 Content

4.2.12.107.2 RequestPriority

Identifies the level of importance to be assigned to actioning the request

This code system http://hl7.org/fhir/request-priority defines the following codes:

Code | Display | Definition
routine | Routine | The request has normal priority
urgent | Urgent | The request should be actioned promptly - higher priority than routine
asap | ASAP | The request should be actioned as soon as possible - higher priority than urgent
stat | STAT | The request should be actioned immediately - highest possible priority. E.g. an emergency

See the full registry of value sets defined as part of FHIR.

Explanation of the columns that may appear on this page:

Level | A few code lists that FHIR defines are hierarchical - each code is assigned a level. In this scheme, some codes are under other codes, and imply that the code they are under also applies
Source | The source of the definition of the code (when the value set draws in codes defined elsewhere)
Code | The code (used as the code in the resource instance). If the code is in italics, this indicates that the code is not selectable ('Abstract')
Display | The display (used in the display element of a Coding). If there is no display, implementers should not simply display the code, but map the concept into their application
Definition | An explanation of the meaning of the concept
Comments | Additional notes about how to use the code

4.2.12.109 Code System http://hl7.org/fhir/resource-validation-mode

URL: https://hl7.org/fhir/STU3/codesystem-resource-validation-mode.html

This page is part of the FHIR Specification (v3.0.2: STU 3). The current version which supercedes this version is 4.0.1. For a full list of available versions, see the Directory of published versions

Vocabulary Work Group | Maturity Level: 0 | Informative | Use Context: Any

This is a code system defined by the FHIR project.

Summary

Defining URL: | http://hl7.org/fhir/resource-validation-mode
Name: | ResourceValidationMode
Definition: | Codes indicating the type of validation to perform
Committee: | FHIR Infrastructure Work Group
OID: | 2.16.840.1.113883.4.642.1.109 (for OID based terminology systems)
Source Resource | XML / JSON

This Code system is used in the following value sets:

* ResourceValidationMode (Codes indicating the type of validation to perform)

4.2.12.109.1 Content

4.2.12.109.2 ResourceValidationMode

Codes indicating the type of validation to perform

This code system http://hl7.org/fhir/resource-validation-mode defines the following codes:

Code | Display | Definition
create | Validate for Create | The server checks the content, and then checks that the content would be acceptable as a create (e.g. that the content would not violate any uniqueness constraints).

update | Validate for Update | The server checks the content, and then checks that it would accept it as an update against the nominated specific resource (e.g. that there are no changes to immutable fields the server does not allow to change, and checking version integrity if appropriate).
delete | Validate for Delete | The server ignores the content, and checks that the nominated resource is allowed to be deleted (e.g. checking referential integrity rules).

See the full registry of value sets defined as part of FHIR.

Explanation of the columns that may appear on this page:

Level | A few code lists that FHIR defines are hierarchical - each code is assigned a level. In this scheme, some codes are under other codes, and imply that the code they are under also applies
Source | The source of the definition of the code (when the value set draws in codes defined elsewhere)
Code | The code (used as the code in the resource instance). If the code is in italics, this indicates that the code is not selectable ('Abstract')
Display | The display (used in the display element of a Coding). If there is no display, implementers should not simply display the code, but map the concept into their application
Definition | An explanation of the meaning of the concept
Comments | Additional notes about how to use the code

4.2.12.111 Code System http://hl7.org/fhir/flag-status

URL: https://hl7.org/fhir/STU3/codesystem-flag-status.html

This page is part of the FHIR Specification (v3.0.2: STU 3). The current version which supercedes this version is 4.0.1. For a full list of available versions, see the Directory of published versions

Vocabulary Work Group | Maturity Level: 1 | Informative | Use Context: Any

This is a code system defined by the FHIR project.

Summary

Defining URL: | http://hl7.org/fhir/flag-status
Name: | FlagStatus
Definition: | Indicates whether this flag is active and needs to be displayed to a user, or whether it is no longer needed or entered in error.
Committee: | Patient Care Work Group
OID: | 2.16.840.1.113883.4.642.1.111 (for OID based terminology systems)
Source Resource | XML / JSON

This Code system is used in the following value sets:

* FlagStatus (Indicates whether this flag is active and needs to be displayed to a user, or whether it is no longer needed or entered in error.)

4.2.12.111.1 Content

4.2.12.111.2 FlagStatus

Indicates whether this flag is active and needs to be displayed to a user, or whether it is no longer needed or entered in error.

This code system http://hl7.org/fhir/flag-status defines the following codes:

Code | Display | Definition
active | Active | A current flag that should be displayed to a user. A system may use the category to determine which roles should view the flag.
inactive | Inactive | The flag does not need to be displayed any more.
entered-in-error | Entered in Error | The flag was added in error, and should no longer be displayed.

See the full registry of value sets defined as part of FHIR.

Explanation of the columns that may appear on this page:

Level | A few code lists that FHIR defines are hierarchical - each code is assigned a level. In this scheme, some codes are under other codes, and imply that the code they are under also applies
Source | The source of the definition of the code (when the value set draws in codes defined elsewhere)
Code | The code (used as the code in the resource instance). If the code is in italics, this indicates that the code is not selectable ('Abstract')
Display | The display (used in the display element of a Coding). If there is no display, implementers should not simply display the code, but map the concept into their application
Definition | An explanation of the meaning of the concept
Comments | Additional notes about how to use the code

4.2.12.113 Code System http://hl7.org/fhir/flag-category

URL: https://hl7.org/fhir/STU3/codesystem-flag-category.html

This page is part of the FHIR Specification (v3.0.2: STU 3). The current version which supercedes this version is 4.0.1. For a full list of available versions, see the Directory of published versions

Vocabulary Work Group | Maturity Level: 1 | Informative | Use Context: Not Intended for Production use

This is a code system defined at http://www.hl7.org/Special/committees/patientcare .

Summary

Defining URL: | http://hl7.org/fhir/flag-category
Name: | Flag Category
Definition: | Example list of general categories for flagged issues. (Not complete or necessarily appropriate.)
Committee: | Patient Care Work Group

OID: | 2.16.840.1.113883.4.642.1.113 (for OID based terminology systems)
Source Resource | XML / JSON

This Code system is used in the following value sets:

* Flag Category (Example list of general categories for flagged issues. (Not complete or necessarily appropriate.))

4.2.12.113.1 Content

4.2.12.113.2 Flag Category

Example list of general categories for flagged issues. (Not complete or necessarily appropriate.)

This code system http://hl7.org/fhir/flag-category defines the following codes:

Code | Display | Definition
diet | Diet | Flags related to the subject's dietary needs.
drug | Drug | Flags related to the patient's medications.
lab | Lab | Flags related to performing laboratory tests and related processes (e.g. phlebotomy).
admin | Administrative | Flags related to administrative and financial processes.
contact | Subject contact | Flags related to coming into contact with the patient.

See the full registry of value sets defined as part of FHIR.

Explanation of the columns that may appear on this page:

Level | A few code lists that FHIR defines are hierarchical - each code is assigned a level. In this scheme, some codes are under other codes, and imply that the code they are under also applies
Source | The source of the definition of the code (when the value set draws in codes defined elsewhere)
Code | The code (used as the code in the resource instance). If the code is in italics, this indicates that the code is not selectable ('Abstract')
Display | The display (used in the display element of a Coding). If there is no display, implementers should not simply display the code, but map the concept into their application
Definition | An explanation of the meaning of the concept
Comments | Additional notes about how to use the code

4.2.12.116 Code System http://hl7.org/fhir/allergy-verification-status

URL: https://hl7.org/fhir/STU3/codesystem-allergy-verification-status.html

This page is part of the FHIR Specification (v3.0.2: STU 3). The current version which supercedes this version is 4.0.1. For a full list of available versions, see the Directory of published versions

Vocabulary Work Group | Maturity Level: 3 | Informative | Use Context: Any

This is a code system defined by the FHIR project.

Summary

Defining URL: | http://hl7.org/fhir/allergy-verification-status
Name: | AllergyIntoleranceVerificationStatus
Definition: | Assertion about certainty associated with a propensity, or potential risk, of a reaction to the identified substance.
Committee: | Patient Care Work Group
OID: | 2.16.840.1.113883.4.642.1.116 (for OID based terminology systems)
Source Resource | XML / JSON

This Code system is used in the following value sets:

* AllergyIntoleranceVerificationStatus (Assertion about certainty associated with a propensity, or potential risk, of a reaction to the identified substance.)

4.2.12.116.1 Content

4.2.12.116.2 AllergyIntoleranceVerificationStatus

Assertion about certainty associated with a propensity, or potential risk, of a reaction to the identified substance.

This code system http://hl7.org/fhir/allergy-verification-status defines the following codes:

Code | Display | Definition
unconfirmed | Unconfirmed | A low level of certainty about the propensity for a reaction to the identified substance.
confirmed | Confirmed | A high level of certainty about the propensity for a reaction to the identified substance, which may include clinical evidence by testing or rechallenge.
refuted | Refuted | A propensity for a reaction to the identified substance has been disproven with a high level of clinical certainty, which may include testing or rechallenge, and is refuted.
entered-in-error | Entered In Error | The statement was entered in error and is not valid.

See the full registry of value sets defined as part of FHIR.

Explanation of the columns that may appear on this page:

Level | A few code lists that FHIR defines are hierarchical - each code is assigned a level. In this scheme, some codes are under other codes, and imply that the code they are under also applies
Source | The source of the definition of the code (when the value set draws in codes defined elsewhere)
Code | The code (used as the code in the resource instance). If the code is in italics, this indicates that the code is not selectable ('Abstract')

Display | The display (used in the display element of a Coding). If there is no display, implementers should not simply display the code, but map the concept into their application
Definition | An explanation of the meaning of the concept
Comments | Additional notes about how to use the code

4.2.12.118 Code System http://hl7.org/fhir/allergy-clinical-status

URL: https://hl7.org/fhir/STU3/codesystem-allergy-clinical-status.html

This page is part of the FHIR Specification (v3.0.2: STU 3). The current version which supercedes this version is 4.0.1. For a full list of available versions, see the Directory of published versions

Vocabulary Work Group | Maturity Level: 3 | Informative | Use Context: Any

This is a code system defined by the FHIR project.

Summary

Defining URL: | http://hl7.org/fhir/allergy-clinical-status
Name: | AllergyIntoleranceClinicalStatus
Definition: | The clinical status of the allergy or intolerance.
Committee: | Patient Care Work Group
OID: | 2.16.840.1.113883.4.642.1.118 (for OID based terminology systems)
Source Resource | XML / JSON

This Code system is used in the following value sets:

* AllergyIntoleranceClinicalStatus (The clinical status of the allergy or intolerance.)

4.2.12.118.1 Content

4.2.12.118.2 AllergyIntoleranceClinicalStatus

The clinical status of the allergy or intolerance.

This code system http://hl7.org/fhir/allergy-clinical-status defines the following codes:

Lvl | Code | Display | Definition
1 | active | Active | An active record of a risk of a reaction to the identified substance.
1 | inactive | Inactive | An inactivated record of a risk of a reaction to the identified substance.
2 | resolved | Resolved | A reaction to the identified substance has been clinically reassessed by testing or re-exposure and considered to be resolved.

See the full registry of value sets defined as part of FHIR.

Explanation of the columns that may appear on this page:

Level | A few code lists that FHIR defines are hierarchical - each code is assigned a level. In this scheme, some codes are under other codes, and imply that the code they are under also applies
Source | The source of the definition of the code (when the value set draws in codes defined elsewhere)
Code | The code (used as the code in the resource instance). If the code is in italics, this indicates that the code is not selectable ('Abstract')
Display | The display (used in the display element of a Coding). If there is no display, implementers should not simply display the code, but map the concept into their application
Definition | An explanation of the meaning of the concept
Comments | Additional notes about how to use the code

4.2.12.120 Code System http://hl7.org/fhir/allergy-intolerance-criticality

URL: https://hl7.org/fhir/STU3/codesystem-allergy-intolerance-criticality.html

This page is part of the FHIR Specification (v3.0.2: STU 3). The current version which supercedes this version is 4.0.1. For a full list of available versions, see the Directory of published versions

Vocabulary Work Group | Maturity Level: 3 | Informative | Use Context: Any

This is a code system defined by the FHIR project.

Summary

Defining URL: | http://hl7.org/fhir/allergy-intolerance-criticality
Name: | AllergyIntoleranceCriticality
Definition: | Estimate of the potential clinical harm, or seriousness, of a reaction to an identified substance.
Committee: | Patient Care Work Group
OID: | 2.16.840.1.113883.4.642.1.120 (for OID based terminology systems)
Source Resource | XML / JSON

This Code system is used in the following value sets:

* AllergyIntoleranceCriticality (Estimate of the potential clinical harm, or seriousness, of a reaction to an identified substance.)

4.2.12.120.1 Content

4.2.12.120.2 AllergyIntoleranceCriticality

Estimate of the potential clinical harm, or seriousness, of a reaction to an identified substance.

This code system http://hl7.org/fhir/allergy-intolerance-criticality defines the following codes:

Code | Display | Definition
low | Low Risk | Worst case result of a future exposure is not assessed to be life-threatening or having high potential for organ system failure.
high | High Risk | Worst case result of a future exposure is assessed to be life-threatening or having high potential for organ system failure.
unable-to-assess | Unable to Assess Risk | Unable to assess the worst case result of a future exposure.

See the full registry of value sets defined as part of FHIR.

Explanation of the columns that may appear on this page:

Level | A few code lists that FHIR defines are hierarchical - each code is assigned a level. In this scheme, some codes are under other codes, and imply that the code they are under also applies
Source | The source of the definition of the code (when the value set draws in codes defined elsewhere)
Code | The code (used as the code in the resource instance). If the code is in italics, this indicates that the code is not selectable ('Abstract')
Display | The display (used in the display element of a Coding). If there is no display, implementers should not simply display the code, but map the concept into their application
Definition | An explanation of the meaning of the concept
Comments | Additional notes about how to use the code

4.2.12.122 Code System http://hl7.org/fhir/allergy-intolerance-type

URL: https://hl7.org/fhir/STU3/codesystem-allergy-intolerance-type.html

This page is part of the FHIR Specification (v3.0.2: STU 3). The current version which supercedes this version is 4.0.1. For a full list of available versions, see the Directory of published versions

Vocabulary Work Group | Maturity Level: 3 | Informative | Use Context: Any

This is a code system defined by the FHIR project.

Summary

Defining URL: | http://hl7.org/fhir/allergy-intolerance-type
Name: | AllergyIntoleranceType
Definition: | Identification of the underlying physiological mechanism for a Reaction Risk.
Committee: | Patient Care Work Group
OID: | 2.16.840.1.113883.4.642.1.122 (for OID based terminology systems)
Source Resource | XML / JSON

This Code system is used in the following value sets:

* AllergyIntoleranceType (Identification of the underlying physiological mechanism for a Reaction Risk.)

4.2.12.122.1 Content

4.2.12.122.2 AllergyIntoleranceType

Identification of the underlying physiological mechanism for a Reaction Risk.

This code system http://hl7.org/fhir/allergy-intolerance-type defines the following codes:

Code | Display | Definition
allergy | Allergy | A propensity for hypersensitivity reaction(s) to a substance. These reactions are most typically type I hypersensitivity, plus other "allergy-like" reactions, including pseudoallergy.
intolerance | Intolerance | A propensity for adverse reactions to a substance that is not judged to be allergic or "allergy-like". These reactions are typically (but not necessarily) non-immune. They are to some degree idiosyncratic and/or individually specific (i.e. are not a reaction that is expected to occur with most or all patients given similar circumstances).

See the full registry of value sets defined as part of FHIR.

Explanation of the columns that may appear on this page:

Level | A few code lists that FHIR defines are hierarchical - each code is assigned a level. In this scheme, some codes are under other codes, and imply that the code they are under also applies
Source | The source of the definition of the code (when the value set draws in codes defined elsewhere)
Code | The code (used as the code in the resource instance). If the code is in italics, this indicates that the code is not selectable ('Abstract')
Display | The display (used in the display element of a Coding). If there is no display, implementers should not simply display the code, but map the concept into their application
Definition | An explanation of the meaning of the concept
Comments | Additional notes about how to use the code

4.2.12.124 Code System http://hl7.org/fhir/allergy-intolerance-category

URL: https://hl7.org/fhir/STU3/codesystem-allergy-intolerance-category.html

This page is part of the FHIR Specification (v3.0.2: STU 3). The current version which supercedes this version is 4.0.1. For a full list of available versions, see the Directory of published versions

Vocabulary Work Group | Maturity Level: 3 | Informative | Use Context: Any

This is a code system defined by the FHIR project.

Summary

Defining URL: | http://hl7.org/fhir/allergy-intolerance-category

Name: | AllergyIntoleranceCategory
Definition: | Category of an identified substance.
Committee: | Patient Care Work Group
OID: | 2.16.840.1.113883.4.642.1.124 (for OID based terminology systems)
Source Resource | XML / JSON

This Code system is used in the following value sets:

* AllergyIntoleranceCategory (Category of an identified substance.)

4.2.12.124.1 Content

4.2.12.124.2 AllergyIntoleranceCategory

Category of an identified substance.

This code system http://hl7.org/fhir/allergy-intolerance-category defines the following codes:

Code | Display | Definition
food | Food | Any substance consumed to provide nutritional support for the body.
medication | Medication | Substances administered to achieve a physiological effect.
environment | Environment | Any substances that are encountered in the environment, including any substance not already classified as food, medication, or biologic.
biologic | Biologic | A preparation that is synthesized from living organisms or their products, especially a human or animal protein, such as a hormone or antitoxin, that is used as a diagnostic, preventive, or therapeutic agent. Examples of biologic medications include: vaccines; allergenic extracts, which are used for both diagnosis and treatment (for example, allergy shots); gene therapies; cellular therapies. There are other biologic products, such as tissues, that are not typically associated with allergies.

See the full registry of value sets defined as part of FHIR.

Explanation of the columns that may appear on this page:

Level | A few code lists that FHIR defines are hierarchical - each code is assigned a level. In this scheme, some codes are under other codes, and imply that the code they are under also applies
Source | The source of the definition of the code (when the value set draws in codes defined elsewhere)
Code | The code (used as the code in the resource instance). If the code is in italics, this indicates that the code is not selectable ('Abstract')
Display | The display (used in the display element of a Coding). If there is no display, implementers should not simply display the code, but map the concept into their application
Definition | An explanation of the meaning of the concept
Comments | Additional notes about how to use the code

4.2.12.126 Code System http://hl7.org/fhir/reaction-event-severity

URL: https://hl7.org/fhir/STU3/codesystem-reaction-event-severity.html

This page is part of the FHIR Specification (v3.0.2: STU 3). The current version which supercedes this version is 4.0.1. For a full list of available versions, see the Directory of published versions

Vocabulary Work Group | Maturity Level: 3 | Informative | Use Context: Any

This is a code system defined by the FHIR project.

Summary

Defining URL: | http://hl7.org/fhir/reaction-event-severity
Name: | AllergyIntoleranceSeverity
Definition: | Clinical assessment of the severity of a reaction event as a whole, potentially considering multiple different manifestations.
Committee: | Patient Care Work Group
OID: | 2.16.840.1.113883.4.642.1.126 (for OID based terminology systems)
Source Resource | XML / JSON

This Code system is used in the following value sets:

* AllergyIntoleranceSeverity (Clinical assessment of the severity of a reaction event as a whole, potentially considering multiple different manifestations.)

4.2.12.126.1 Content

4.2.12.126.2 AllergyIntoleranceSeverity

Clinical assessment of the severity of a reaction event as a whole, potentially considering multiple different manifestations.

This code system http://hl7.org/fhir/reaction-event-severity defines the following codes:

Code | Display | Definition
mild | Mild | Causes mild physiological effects.
moderate | Moderate | Causes moderate physiological effects.
severe | Severe | Causes severe physiological effects.

See the full registry of value sets defined as part of FHIR.

Explanation of the columns that may appear on this page:

Level | A few code lists that FHIR defines are hierarchical - each code is assigned a level. In this scheme, some codes are under other codes, and imply that the code they are under also applies

Source | The source of the definition of the code (when the value set draws in codes defined elsewhere)
Code | The code (used as the code in the resource instance). If the code is in italics, this indicates that the code is not selectable ('Abstract')
Display | The display (used in the display element of a Coding). If there is no display, implementers should not simply display the code, but map the concept into their application
Definition | An explanation of the meaning of the concept
Comments | Additional notes about how to use the code

4.2.12.129 Code System http://hl7.org/fhir/basic-resource-type

URL: https://hl7.org/fhir/STU3/codesystem-basic-resource-type.html

This page is part of the FHIR Specification (v3.0.2: STU 3). The current version which supercedes this version is 4.0.1. For a full list of available versions, see the Directory of published versions

Vocabulary Work Group | Maturity Level: 1 | Informative | Use Context: Not Intended for Production use

This is a code system defined by the FHIR project.

Summary

Defining URL: | http://hl7.org/fhir/basic-resource-type
Name: | Basic Resource Types
Definition: | This value set defines codes for resources not yet supported by (or which will never be supported by) FHIR. Many of the codes listed here will eventually be turned into official resources. However, there is no guarantee that any particular resource will be created nor that the scope will be exactly as defined by the codes presented here. Codes in this set will be deprecated if/when formal resources are defined that encompass these concepts.
Committee: | FHIR Infrastructure Work Group
OID: | 2.16.840.1.113883.4.642.1.129 (for OID based terminology systems)
Source Resource | XML / JSON

This Code system is used in the following value sets:

* Basic Resource Types (This value set defines codes for resources not yet supported by (or which will never be supported by) FHIR. Many of the codes listed here will eventually be turned into official resources. However, there is no guarantee that any particular resource will be created nor that the scope will be exactly as defined by the codes presented here. Codes in this set will be deprecated if/when formal resources are defined that encompass these concepts.)

4.2.12.129.1 Content

4.2.12.129.2 Basic Resource Types

This value set defines codes for resources not yet supported by (or which will never be supported by) FHIR. Many of the codes listed here will eventually be turned into official resources. However, there is no guarantee that any particular resource will be created nor that the scope will be exactly as defined by the codes presented here. Codes in this set will be deprecated if/when formal resources are defined that encompass these concepts.

This code system http://hl7.org/fhir/basic-resource-type defines the following codes:

Code | Display | Definition
consent | Consent | An assertion of permission for an activity or set of activities to occur, possibly subject to particular limitations; e.g. surgical consent, information disclosure consent, etc.
referral | Referral | A request that care of a particular type be provided to a patient. Could involve the transfer of care, a consult, etc.
advevent | Adverse Event | An undesired reaction caused by exposure to some agent (e.g. a medication, immunization, food, or environmental agent).
aptmtreq | Appointment Request | A request that a time be scheduled for a type of service for a specified patient, potentially subject to other constraints
transfer | Transfer | The transition of a patient or set of material from one location to another
diet | Diet | The specification of a set of food and/or other nutritional material to be delivered to a patient.
adminact | Administrative Activity | An occurrence of a non-care-related event in the healthcare domain, such as approvals, reviews, etc.
exposure | Exposure | Record of a situation where a subject was exposed to a substance. Usually of interest to public health.
investigation | Investigation | A formalized inquiry into the circumstances surrounding a particular unplanned event or potential event for the purposes of identifying possible causes and contributing factors for the event
account | Account | A financial instrument used to track costs, charges or other amounts.
invoice | Invoice | A request for payment for goods and/or services. Includes the idea of a healthcare insurance claim.
adjudicat | Invoice Adjudication | The determination of what will be paid against a particular invoice based on coverage, plan rules, etc.
predetreq | Pre-determination Request | A request for a pre-determination of the cost that would be paid under an insurance plan for a hypothetical claim for goods or services
predetermine | Predetermination | An adjudication of what would be paid under an insurance plan for a hypothetical claim for goods or services
study | Study | An investigation to determine information about a particular therapy or product
protocol | Protocol | A set of (possibly conditional) steps to be taken to achieve some aim. Includes study protocols, treatment protocols, emergency protocols, etc.

See the full registry of value sets defined as part of FHIR.

Explanation of the columns that may appear on this page:

Level | A few code lists that FHIR defines are hierarchical - each code is assigned a level. In this scheme, some codes are under other codes, and imply that the code they are under also applies
Source | The source of the definition of the code (when the value set draws in codes defined elsewhere)
Code | The code (used as the code in the resource instance). If the code is in italics, this indicates that the code is not selectable ('Abstract')

Display | The display (used in the display element of a Coding). If there is no display, implementers should not simply display the code, but map the concept into their application
Definition | An explanation of the meaning of the concept
Comments | Additional notes about how to use the code

4.2.12.131 Code System http://hl7.org/fhir/care-plan-status

URL: https://hl7.org/fhir/STU3/codesystem-care-plan-status.html

This page is part of the FHIR Specification (v3.0.2: STU 3). The current version which supercedes this version is 4.0.1. For a full list of available versions, see the Directory of published versions

Vocabulary Work Group | Maturity Level: 2 | Informative | Use Context: Any

This is a code system defined by the FHIR project.

Summary

Defining URL: | http://hl7.org/fhir/care-plan-status
Name: | CarePlanStatus
Definition: | Indicates whether the plan is currently being acted upon, represents future intentions or is now a historical record.
Committee: | Patient Care Work Group
OID: | 2.16.840.1.113883.4.642.1.131 (for OID based terminology systems)
Source Resource | XML / JSON

This Code system is used in the following value sets:

* CarePlanStatus (Indicates whether the plan is currently being acted upon, represents future intentions or is now a historical record.)

4.2.12.131.1 Content

4.2.12.131.2 CarePlanStatus

Indicates whether the plan is currently being acted upon, represents future intentions or is now a historical record.

This code system http://hl7.org/fhir/care-plan-status defines the following codes:

Code | Display | Definition
draft | Pending | The plan is in development or awaiting use but is not yet intended to be acted upon.
active | Active | The plan is intended to be followed and used as part of patient care.
suspended | Suspended | The plan has been temporarily stopped but is expected to resume in the future.
completed | Completed | The plan is no longer in use and is not expected to be followed or used in patient care.
entered-in-error | Entered In Error | The plan was entered in error and voided.
cancelled | Cancelled | The plan has been terminated prior to reaching completion (though it may have been replaced by a new plan).
unknown | Unknown | The authoring system doesn't know the current state of the care plan.

See the full registry of value sets defined as part of FHIR.

Explanation of the columns that may appear on this page:

Level | A few code lists that FHIR defines are hierarchical - each code is assigned a level. In this scheme, some codes are under other codes, and imply that the code they are under also applies
Source | The source of the definition of the code (when the value set draws in codes defined elsewhere)
Code | The code (used as the code in the resource instance). If the code is in italics, this indicates that the code is not selectable ('Abstract')
Display | The display (used in the display element of a Coding). If there is no display, implementers should not simply display the code, but map the concept into their application
Definition | An explanation of the meaning of the concept
Comments | Additional notes about how to use the code

4.2.12.132 Code System http://hl7.org/fhir/care-plan-activity-category

URL: https://hl7.org/fhir/STU3/codesystem-care-plan-activity-category.html

This page is part of the FHIR Specification (v3.0.2: STU 3). The current version which supercedes this version is 4.0.1. For a full list of available versions, see the Directory of published versions

Vocabulary Work Group | Maturity Level: 1 | Informative | Use Context: Not Intended for Production use

This is a code system defined by the FHIR project.

Summary

Defining URL: | http://hl7.org/fhir/care-plan-activity-category
Name: | CarePlanActivityCategory
Definition: | High-level categorization of the type of activity in a care plan.
Committee: | Patient Care Work Group
OID: | 2.16.840.1.113883.4.642.1.132 (for OID based terminology systems)
Source Resource | XML / JSON

This Code system is used in the following value sets:

* CarePlanActivityCategory (High-level categorization of the type of activity in a care plan.)

4.2.12.132.1 Content

4.2.12.132.2 CarePlanActivityCategory

High-level categorization of the type of activity in a care plan.

This code system http://hl7.org/fhir/care-plan-activity-category defines the following codes:

Code | Display | Definition
diet | Diet | Plan for the patient to consume food of a specified nature
drug | Drug | Plan for the patient to consume/receive a drug, vaccine or other product
encounter | Encounter | Plan to meet or communicate with the patient (in-patient, out-patient, phone call, etc.)
observation | Observation | Plan to capture information about a patient (vitals, labs, diagnostic images, etc.)
procedure | Procedure | Plan to modify the patient in some way (surgery, physiotherapy, education, counseling, etc.)
supply | Supply | Plan to provide something to the patient (medication, medical supply, etc.)
other | Other | Some other form of action

See the full registry of value sets defined as part of FHIR.

Explanation of the columns that may appear on this page:

Level | A few code lists that FHIR defines are hierarchical - each code is assigned a level. In this scheme, some codes are under other codes, and imply that the code they are under also applies
Source | The source of the definition of the code (when the value set draws in codes defined elsewhere)
Code | The code (used as the code in the resource instance). If the code is in italics, this indicates that the code is not selectable ('Abstract')
Display | The display (used in the display element of a Coding). If there is no display, implementers should not simply display the code, but map the concept into their application
Definition | An explanation of the meaning of the concept
Comments | Additional notes about how to use the code

4.2.12.135 Code System http://hl7.org/fhir/care-plan-activity-status

URL: https://hl7.org/fhir/STU3/codesystem-care-plan-activity-status.html

This page is part of the FHIR Specification (v3.0.2: STU 3). The current version which supercedes this version is 4.0.1. For a full list of available versions, see the Directory of published versions

Vocabulary Work Group | Maturity Level: 2 | Informative | Use Context: Any

This is a code system defined by the FHIR project.

Summary

Defining URL: | http://hl7.org/fhir/care-plan-activity-status
Name: | CarePlanActivityStatus
Definition: | Indicates where the activity is at in its overall life cycle.
Committee: | Patient Care Work Group
OID: | 2.16.840.1.113883.4.642.1.135 (for OID based terminology systems)
Source Resource | XML / JSON

This Code system is used in the following value sets:

* CarePlanActivityStatus (Indicates where the activity is at in its overall life cycle.)

4.2.12.135.1 Content

4.2.12.135.2 CarePlanActivityStatus

Indicates where the activity is at in its overall life cycle.

This code system http://hl7.org/fhir/care-plan-activity-status defines the following codes:

Code | Display | Definition
not-started | Not Started | Activity is planned but no action has yet been taken.
scheduled | Scheduled | Appointment or other booking has occurred but activity has not yet begun.
in-progress | In Progress | Activity has been started but is not yet complete.
on-hold | On Hold | Activity was started but has temporarily ceased with an expectation of resumption at a future time.
completed | Completed | The activities have been completed (more or less) as planned.
cancelled | Cancelled | The activities have been ended prior to completion (perhaps even before they were started).
unknown | Unknown | The authoring system doesn't know the current state of the activity.

See the full registry of value sets defined as part of FHIR.

Explanation of the columns that may appear on this page:

Level | A few code lists that FHIR defines are hierarchical - each code is assigned a level. In this scheme, some codes are under other codes, and imply that the code they are under also applies
Source | The source of the definition of the code (when the value set draws in codes defined elsewhere)
Code | The code (used as the code in the resource instance). If the code is in italics, this indicates that the code is not selectable ('Abstract')
Display | The display (used in the display element of a Coding). If there is no display, implementers should not simply display the code, but map the concept into their application
Definition | An explanation of the meaning of the concept
Comments | Additional notes about how to use the code

4.2.12.142 Code System http://hl7.org/fhir/care-plan-intent

URL: https://hl7.org/fhir/STU3/codesystem-care-plan-intent.html

This page is part of the FHIR Specification (v3.0.2: STU 3). The current version which supercedes this version is 4.0.1. For a full list of available versions, see the Directory of published versions

Vocabulary Work Group | Maturity Level: 2 | Informative | Use Context: Any

This is a code system defined by the FHIR project.

Summary

Defining URL: | http://hl7.org/fhir/care-plan-intent
Name: | CarePlanIntent
Definition: | Codes indicating the degree of authority/intentionality associated with a care plan
Committee: | Patient Care Work Group
OID: | 2.16.840.1.113883.4.642.1.142 (for OID based terminology systems)
Source Resource | XML / JSON

This Code system is used in the following value sets:

* CarePlanIntent (Codes indicating the degree of authority/intentionality associated with a care plan)

4.2.12.142.1 Content

4.2.12.142.2 CarePlanIntent

Codes indicating the degree of authority/intentionality associated with a care plan

This code system http://hl7.org/fhir/care-plan-intent defines the following codes:

Code | Display | Definition
proposal | Proposal | The care plan is a suggestion made by someone/something that doesn't have an intention to ensure it occurs and without providing an authorization to act
plan | Plan | The care plan represents an intention to ensure something occurs without providing an authorization for others to act
order | Order | The care plan represents a request/demand and authorization for action
option | Option | The care plan represents a component or option for a RequestGroup that establishes timing, conditionality and/or other constraints among a set of requests. Refer to [[[RequestGroup]]] for additional information on how this status is used

See the full registry of value sets defined as part of FHIR.

Explanation of the columns that may appear on this page:

Level | A few code lists that FHIR defines are hierarchical - each code is assigned a level. In this scheme, some codes are under other codes, and imply that the code they are under also applies
Source | The source of the definition of the code (when the value set draws in codes defined elsewhere)
Code | The code (used as the code in the resource instance). If the code is in italics, this indicates that the code is not selectable ('Abstract')
Display | The display (used in the display element of a Coding). If there is no display, implementers should not simply display the code, but map the concept into their application
Definition | An explanation of the meaning of the concept
Comments | Additional notes about how to use the code

4.2.12.145 Code System http://hl7.org/fhir/care-team-status

URL: https://hl7.org/fhir/STU3/codesystem-care-team-status.html

This page is part of the FHIR Specification (v3.0.2: STU 3). The current version which supercedes this version is 4.0.1. For a full list of available versions, see the Directory of published versions

Vocabulary Work Group | Maturity Level: 2 | Informative | Use Context: Any

This is a code system defined by the FHIR project.

Summary

Defining URL: | http://hl7.org/fhir/care-team-status
Name: | CareTeamStatus
Definition: | Indicates the status of the care team.
Committee: | Patient Care Work Group
OID: | 2.16.840.1.113883.4.642.1.145 (for OID based terminology systems)
Source Resource | XML / JSON

This Code system is used in the following value sets:

* CareTeamStatus (Indicates the status of the care team.)

4.2.12.145.1 Content

4.2.12.145.2 CareTeamStatus

Indicates the status of the care team.

This code system http://hl7.org/fhir/care-team-status defines the following codes:

Code | Display | Definition
proposed | Proposed | The care team has been drafted and proposed, but not yet participating in the coordination and delivery of care.

active | Active | The care team is currently participating in the coordination and delivery of care.
suspended | Suspended | The care team is temporarily on hold or suspended and not participating in the coordination and delivery of care.
inactive | Inactive | The care team was, but is no longer, participating in the coordination and delivery of care.
entered-in-error | Entered In Error | The care team should have never existed.

See the full registry of value sets defined as part of FHIR.

Explanation of the columns that may appear on this page:

Level | A few code lists that FHIR defines are hierarchical - each code is assigned a level. In this scheme, some codes are under other codes, and imply that the code they are under also applies
Source | The source of the definition of the code (when the value set draws in codes defined elsewhere)
Code | The code (used as the code in the resource instance). If the code is in italics, this indicates that the code is not selectable ('Abstract')
Display | The display (used in the display element of a Coding). If there is no display, implementers should not simply display the code, but map the concept into their application
Definition | An explanation of the meaning of the concept
Comments | Additional notes about how to use the code

4.2.12.147 Code System http://hl7.org/fhir/care-team-category

URL: https://hl7.org/fhir/STU3/codesystem-care-team-category.html

This page is part of the FHIR Specification (v3.0.2: STU 3). The current version which supercedes this version is 4.0.1. For a full list of available versions, see the Directory of published versions

Vocabulary Work Group | Maturity Level: 1 | Informative | Use Context: Any

This is a code system defined by the FHIR project.

Summary

Defining URL: | http://hl7.org/fhir/care-team-category
Name: | CareTeamCategory
Definition: | Indicates the type of care team.
Committee: | Patient Care Work Group
OID: | 2.16.840.1.113883.4.642.1.147 (for OID based terminology systems)
Source Resource | XML / JSON

This Code system is used in the following value sets:

* CareTeamCategory (Indicates the type of care team.)

4.2.12.147.1 Content

4.2.12.147.2 CareTeamCategory

Indicates the type of care team.

This code system http://hl7.org/fhir/care-team-category defines the following codes:

Code | Display | Definition
event | Event | This type of team focuses on one specific type of incident, which is non-patient specific. The incident is determined by the context of use. For example, code team (code red, code blue, medical emergency treatment) or the PICC line team.
encounter | Encounter | This type of team focuses on one specific encounter. The encounter is determined by the context of use. For example, during an inpatient encounter, the nutrition support care team
episode | Episode | This type of team focuses on one specific episode of care with a defined time period or self-limiting process (e.g. 10 visits). The episode of care is determined by the context of use. For example, a maternity care team over 9 months.
longitudinal | Longitudinal Care Coordination | This type of team focuses on overall care coordination managing one or more conditions across the continuum of care ensuring there are smooth transitions of care. The members of the team are determined or selected by an individual or organization. When determined by an organization, the team may be assigned or based on the person's enrollment in a particular program. For example, disease management team or patient centered medical home team.
condition | Condition | This type of team focuses on one specific condition. The condition is determined by the context of use. For example, a disease management team focused on one condition (e.g. diabetes).
clinical-research | Clinical Research | This type of team is responsible for establishing, conducting, coordinating and monitoring the outcomes of clinical trials. The team focuses on research, clinical care and education.

See the full registry of value sets defined as part of FHIR.

Explanation of the columns that may appear on this page:

Level | A few code lists that FHIR defines are hierarchical - each code is assigned a level. In this scheme, some codes are under other codes, and imply that the code they are under also applies
Source | The source of the definition of the code (when the value set draws in codes defined elsewhere)
Code | The code (used as the code in the resource instance). If the code is in italics, this indicates that the code is not selectable ('Abstract')
Display | The display (used in the display element of a Coding). If there is no display, implementers should not simply display the code, but map the concept into their application
Definition | An explanation of the meaning of the concept
Comments | Additional notes about how to use the code

4.2.12.150 Code System http://hl7.org/fhir/clinical-impression-status

URL: https://hl7.org/fhir/STU3/codesystem-clinical-impression-status.html

This page is part of the FHIR Specification (v3.0.2: STU 3). The current version which supercedes this version is 4.0.1. For a full list of available versions, see the Directory of published versions

Vocabulary Work Group | Maturity Level: 0 | Informative | Use Context: Any

This is a code system defined by the FHIR project.

Summary

Defining URL: | http://hl7.org/fhir/clinical-impression-status
Name: | ClinicalImpressionStatus
Definition: | The workflow state of a clinical impression.
Committee: | Patient Care Work Group
OID: | 2.16.840.1.113883.4.642.1.150 (for OID based terminology systems)
Source Resource | XML / JSON

This Code system is used in the following value sets:

* ClinicalImpressionStatus (The workflow state of a clinical impression.)

4.2.12.150.1 Content

4.2.12.150.2 ClinicalImpressionStatus

The workflow state of a clinical impression.

This code system http://hl7.org/fhir/clinical-impression-status defines the following codes:

Code | Display | Definition
draft | In progress | The assessment is still on-going and results are not yet final.
completed | Completed | The assessment is done and the results are final.
entered-in-error | Entered in Error | This assessment was never actually done and the record is erroneous (e.g. Wrong patient).

See the full registry of value sets defined as part of FHIR.

Explanation of the columns that may appear on this page:

Level | A few code lists that FHIR defines are hierarchical - each code is assigned a level. In this scheme, some codes are under other codes, and imply that the code they are under also applies
Source | The source of the definition of the code (when the value set draws in codes defined elsewhere)
Code | The code (used as the code in the resource instance). If the code is in italics, this indicates that the code is not selectable ('Abstract')
Display | The display (used in the display element of a Coding). If there is no display, implementers should not simply display the code, but map the concept into their application
Definition | An explanation of the meaning of the concept
Comments | Additional notes about how to use the code

4.2.12.154 Code System http://hl7.org/fhir/condition-category

URL: https://hl7.org/fhir/STU3/codesystem-condition-category.html

This page is part of the FHIR Specification (v3.0.2: STU 3). The current version which supercedes this version is 4.0.1. For a full list of available versions, see the Directory of published versions

Vocabulary Work Group | Maturity Level: 1 | Informative | Use Context: Not Intended for Production use

This is a code system defined by the FHIR project.

Summary

Defining URL: | http://hl7.org/fhir/condition-category
Name: | Condition Category Codes
Definition: | Preferred value set for Condition Categories.
Committee: | Patient Care Work Group
OID: | 2.16.840.1.113883.4.642.1.154 (for OID based terminology systems)
Source Resource | XML / JSON

This Code system is used in the following value sets:

* Condition Category Codes (Preferred value set for Condition Categories.)

4.2.12.154.1 Content

4.2.12.154.2 Condition Category Codes

Preferred value set for Condition Categories.

This code system http://hl7.org/fhir/condition-category defines the following codes:

Code | Display | Definition
problem-list-item | Problem List Item | An item on a problem list which can be managed over time and can be expressed by a practitioner (e.g. physician, nurse), patient, or related person.
encounter-diagnosis | Encounter Diagnosis | A point in time diagnosis (e.g. from a physician or nurse) in context of an encounter.

See the full registry of value sets defined as part of FHIR.

Explanation of the columns that may appear on this page:

Level | A few code lists that FHIR defines are hierarchical - each code is assigned a level. In this scheme, some codes are under other codes, and imply that the code they are under also applies
Source | The source of the definition of the code (when the value set draws in codes defined elsewhere)
Code | The code (used as the code in the resource instance). If the code is in italics, this indicates that the code is not selectable ('Abstract')
Display | The display (used in the display element of a Coding). If there is no display, implementers should not simply display the code, but map the concept into their application
Definition | An explanation of the meaning of the concept
Comments | Additional notes about how to use the code

4.2.12.156 Code System http://hl7.org/fhir/condition-clinical

URL: https://hl7.org/fhir/STU3/codesystem-condition-clinical.html

This page is part of the FHIR Specification (v3.0.2: STU 3). The current version which supercedes this version is 4.0.1. For a full list of available versions, see the Directory of published versions

Vocabulary Work Group | Maturity Level: 3 | Informative | Use Context: Not Intended for Production use

This is a code system defined by the FHIR project.

Summary

Defining URL: | http://hl7.org/fhir/condition-clinical
Name: | Condition Clinical Status Codes
Definition: | Preferred value set for Condition Clinical Status.
Committee: | Patient Care Work Group
OID: | 2.16.840.1.113883.4.642.1.156 (for OID based terminology systems)
Source Resource | XML / JSON

This Code system is used in the following value sets:

* Condition Clinical Status Codes (Preferred value set for Condition Clinical Status.)

4.2.12.156.1 Content

4.2.12.156.2 Condition Clinical Status Codes

Preferred value set for Condition Clinical Status.

This code system http://hl7.org/fhir/condition-clinical defines the following codes:

Lvl | Code | Display | Definition
1 | active | Active | The subject is currently experiencing the symptoms of the condition or there is evidence of the condition.
2 | recurrence | Recurrence | The subject is having a relapse or re-experiencing the condition after a period of remission or presumed resolution.
1 | inactive | Inactive | The subject is no longer experiencing the symptoms of the condition or there is no longer evidence of the condition.
2 | remission | Remission | The subject is no longer experiencing the symptoms of the condition, but there is a risk of the symptoms returning.
2 | resolved | Resolved | The subject is no longer experiencing the symptoms of the condition and there is a negligible perceived risk of the symptoms returning.

See the full registry of value sets defined as part of FHIR.

Explanation of the columns that may appear on this page:

Level | A few code lists that FHIR defines are hierarchical - each code is assigned a level. In this scheme, some codes are under other codes, and imply that the code they are under also applies
Source | The source of the definition of the code (when the value set draws in codes defined elsewhere)
Code | The code (used as the code in the resource instance). If the code is in italics, this indicates that the code is not selectable ('Abstract')
Display | The display (used in the display element of a Coding). If there is no display, implementers should not simply display the code, but map the concept into their application
Definition | An explanation of the meaning of the concept
Comments | Additional notes about how to use the code

4.2.12.158 Code System http://hl7.org/fhir/condition-ver-status

URL: https://hl7.org/fhir/STU3/codesystem-condition-ver-status.html

This page is part of the FHIR Specification (v3.0.2: STU 3). The current version which supercedes this version is 4.0.1. For a full list of available versions, see the Directory of published versions

Vocabulary Work Group | Maturity Level: 3 | Informative | Use Context: Any

This is a code system defined by the FHIR project.

Summary

Defining URL: | http://hl7.org/fhir/condition-ver-status
Name: | ConditionVerificationStatus
Definition: | The verification status to support or decline the clinical status of the condition or diagnosis.
Committee: | Patient Care Work Group
OID: | 2.16.840.1.113883.4.642.1.158 (for OID based terminology systems)
Source Resource | XML / JSON

This Code system is used in the following value sets:

* ConditionVerificationStatus (The verification status to support or decline the clinical status of the condition or diagnosis.)

4.2.12.158.1 Content

4.2.12.158.2 ConditionVerificationStatus

The verification status to support or decline the clinical status of the condition or diagnosis.

This code system http://hl7.org/fhir/condition-ver-status defines the following codes:

Code | Display | Definition
provisional | Provisional | This is a tentative diagnosis - still a candidate that is under consideration.
differential | Differential | One of a set of potential (and typically mutually exclusive) diagnoses asserted to further guide the diagnostic process and preliminary treatment.
confirmed | Confirmed | There is sufficient diagnostic and/or clinical evidence to treat this as a confirmed condition.
refuted | Refuted | This condition has been ruled out by diagnostic and clinical evidence.
entered-in-error | Entered In Error | The statement was entered in error and is not valid.
unknown | Unknown | The condition status is unknown. Note that "unknown" is a value of last resort and every attempt should be made to provide a meaningful value other than "unknown".

See the full registry of value sets defined as part of FHIR.

Explanation of the columns that may appear on this page:

Level | A few code lists that FHIR defines are hierarchical - each code is assigned a level. In this scheme, some codes are under other codes, and imply that the code they are under also applies
Source | The source of the definition of the code (when the value set draws in codes defined elsewhere)
Code | The code (used as the code in the resource instance). If the code is in italics, this indicates that the code is not selectable ('Abstract')
Display | The display (used in the display element of a Coding). If there is no display, implementers should not simply display the code, but map the concept into their application
Definition | An explanation of the meaning of the concept
Comments | Additional notes about how to use the code

4.2.12.163 Code System http://hl7.org/fhir/communication-category

URL: https://hl7.org/fhir/STU3/codesystem-communication-category.html

This page is part of the FHIR Specification (v3.0.2: STU 3). The current version which supercedes this version is 4.0.1. For a full list of available versions, see the Directory of published versions

Vocabulary Work Group | Maturity Level: 1 | Informative | Use Context: Any

This is a code system defined by the FHIR project.

Summary

Defining URL: | http://hl7.org/fhir/communication-category
Name: | CommunicationCategory
Definition: | Codes for general categories of communications such as alerts, instruction, etc.
Committee: | Patient Care Work Group
OID: | 2.16.840.1.113883.4.642.1.163 (for OID based terminology systems)
Source Resource | XML / JSON

This Code system is used in the following value sets:

* CommunicationCategory (Codes for general categories of communications such as alerts, instruction, etc.)

4.2.12.163.1 Content

4.2.12.163.2 CommunicationCategory

Codes for general categories of communications such as alerts, instruction, etc.

This code system http://hl7.org/fhir/communication-category defines the following codes:

Code | Display | Definition
alert | Alert | The communication conveys an alert.
notification | Notification | The communication conveys a notification.
reminder | Reminder | The communication conveys a reminder.
instruction | Instruction | The communication conveys instruction.

See the full registry of value sets defined as part of FHIR.

Explanation of the columns that may appear on this page:

Level | A few code lists that FHIR defines are hierarchical - each code is assigned a level. In this scheme, some codes are under other codes, and imply that the code they are under also applies
Source | The source of the definition of the code (when the value set draws in codes defined elsewhere)
Code | The code (used as the code in the resource instance). If the code is in italics, this indicates that the code is not selectable ('Abstract')
Display | The display (used in the display element of a Coding). If there is no display, implementers should not simply display the code, but map the concept into their application
Definition | An explanation of the meaning of the concept
Comments | Additional notes about how to use the code

4.2.12.165 Code System http://hl7.org/fhir/communication-not-done-reason

URL: https://hl7.org/fhir/STU3/codesystem-communication-not-done-reason.html

This page is part of the FHIR Specification (v3.0.2: STU 3). The current version which supercedes this version is 4.0.1. For a full list of available versions, see the Directory of published versions

Vocabulary Work Group | Maturity Level: 1 | Informative | Use Context: Any

This is a code system defined by the FHIR project.

Summary

Defining URL: | http://hl7.org/fhir/communication-not-done-reason
Name: | CommunicationNotDoneReason
Definition: | Codes for the reason why a communication was not done.
Committee: | Patient Care Work Group
OID: | 2.16.840.1.113883.4.642.1.165 (for OID based terminology systems)
Source Resource | XML / JSON

This Code system is used in the following value sets:

* CommunicationNotDoneReason (Codes for the reason why a communication was not done.)

4.2.12.165.1 Content

4.2.12.165.2 CommunicationNotDoneReason

Codes for the reason why a communication was not done.

This code system http://hl7.org/fhir/communication-not-done-reason defines the following codes:

Code | Display | Definition
unknown | Unknown | The communication was not done due to an unknown reason.
system-error | System Error | The communication was not done due to a system error.
invalid-phone-number | Invalid Phone Number | The communication was not done due to an invalid phone number.
recipient-unavailable | Recipient Unavailable | The communication was not done due to the recipient being unavailable.
family-objection | Family Objection | The communication was not done due to a family objection.
patient-objection | Patient Objection | The communication was not done due to a patient objection.

See the full registry of value sets defined as part of FHIR.

Explanation of the columns that may appear on this page:

Level | A few code lists that FHIR defines are hierarchical - each code is assigned a level. In this scheme, some codes are under other codes, and imply that the code they are under also applies
Source | The source of the definition of the code (when the value set draws in codes defined elsewhere)
Code | The code (used as the code in the resource instance). If the code is in italics, this indicates that the code is not selectable ('Abstract')
Display | The display (used in the display element of a Coding). If there is no display, implementers should not simply display the code, but map the concept into their application
Definition | An explanation of the meaning of the concept
Comments | Additional notes about how to use the code

4.2.12.167 Code System http://hl7.org/fhir/restful-capability-mode

URL: https://hl7.org/fhir/STU3/codesystem-restful-capability-mode.html

This page is part of the FHIR Specification (v3.0.2: STU 3). The current version which supercedes this version is 4.0.1. For a full list of available versions, see the Directory of published versions

Vocabulary Work Group | Maturity Level: 3 | Informative | Use Context: Any

This is a code system defined by the FHIR project.

Summary

Defining URL: | http://hl7.org/fhir/restful-capability-mode
Name: | RestfulCapabilityMode
Definition: | The mode of a RESTful capability statement.
Committee: | FHIR Infrastructure Work Group
OID: | 2.16.840.1.113883.4.642.1.167 (for OID based terminology systems)
Source Resource | XML / JSON

This Code system is used in the following value sets:

* RestfulCapabilityMode (The mode of a RESTful capability statement.)

4.2.12.167.1 Content

4.2.12.167.2 RestfulCapabilityMode

The mode of a RESTful capability statement.

This code system http://hl7.org/fhir/restful-capability-mode defines the following codes:

Code | Display | Definition
client | Client | The application acts as a client for this resource.
server | Server | The application acts as a server for this resource.

See the full registry of value sets defined as part of FHIR.

Explanation of the columns that may appear on this page:

Level | A few code lists that FHIR defines are hierarchical - each code is assigned a level. In this scheme, some codes are under other codes, and imply that the code they are under also applies
Source | The source of the definition of the code (when the value set draws in codes defined elsewhere)
Code | The code (used as the code in the resource instance). If the code is in italics, this indicates that the code is not selectable ('Abstract')
Display | The display (used in the display element of a Coding). If there is no display, implementers should not simply display the code, but map the concept into their application
Definition | An explanation of the meaning of the concept
Comments | Additional notes about how to use the code

4.2.12.169 Code System http://hl7.org/fhir/restful-security-service

URL: https://hl7.org/fhir/STU3/codesystem-restful-security-service.html

This page is part of the FHIR Specification (v3.0.2: STU 3). The current version which supercedes this version is 4.0.1. For a full list of available versions, see the Directory of published versions

Vocabulary Work Group | Maturity Level: 3 | Informative | Use Context: Any

This is a code system defined by the FHIR project.

Summary

Defining URL: | http://hl7.org/fhir/restful-security-service
Name: | RestfulSecurityService
Definition: | Types of security services used with FHIR.
Committee: | FHIR Infrastructure Work Group
OID: | 2.16.840.1.113883.4.642.1.169 (for OID based terminology systems)
Source Resource | XML / JSON

This Code system is used in the following value sets:

* RestfulSecurityService (Types of security services used with FHIR.)

4.2.12.169.1 Content

4.2.12.169.2 RestfulSecurityService

Types of security services used with FHIR.

This code system http://hl7.org/fhir/restful-security-service defines the following codes:

Code | Display | Definition
OAuth | OAuth | Oauth (unspecified version see oauth.net).
SMART-on-FHIR | SMART-on-FHIR | OAuth2 using SMART-on-FHIR profile (see http://docs.smarthealthit.org/).
NTLM | NTLM | Microsoft NTLM Authentication.
Basic | Basic | Basic authentication defined in HTTP specification.
Kerberos | Kerberos | see http://www.ietf.org/rfc/rfc4120.txt.
Certificates | Certificates | SSL where client must have a certificate registered with the server.

See the full registry of value sets defined as part of FHIR.

Explanation of the columns that may appear on this page:

Level | A few code lists that FHIR defines are hierarchical - each code is assigned a level. In this scheme, some codes are under other codes, and imply that the code they are under also applies
Source | The source of the definition of the code (when the value set draws in codes defined elsewhere)
Code | The code (used as the code in the resource instance). If the code is in italics, this indicates that the code is not selectable ('Abstract')
Display | The display (used in the display element of a Coding). If there is no display, implementers should not simply display the code, but map the concept into their application
Definition | An explanation of the meaning of the concept
Comments | Additional notes about how to use the code

4.2.12.173 Code System http://hl7.org/fhir/event-capability-mode

URL: https://hl7.org/fhir/STU3/codesystem-event-capability-mode.html

This page is part of the FHIR Specification (v3.0.2: STU 3). The current version which supercedes this version is 4.0.1. For a full list of available versions, see the Directory of published versions

Vocabulary Work Group | Maturity Level: 3 | Informative | Use Context: Any

This is a code system defined by the FHIR project.

Summary

Defining URL: | http://hl7.org/fhir/event-capability-mode
Name: | EventCapabilityMode
Definition: | The mode of a message capability statement.
Committee: | FHIR Infrastructure Work Group
OID: | 2.16.840.1.113883.4.642.1.173 (for OID based terminology systems)
Source Resource | XML / JSON

This Code system is used in the following value sets:

* EventCapabilityMode (The mode of a message capability statement.)

4.2.12.173.1 Content

4.2.12.173.2 EventCapabilityMode

The mode of a message capability statement.

This code system http://hl7.org/fhir/event-capability-mode defines the following codes:

Code | Display | Definition
sender | Sender | The application sends requests and receives responses.
receiver | Receiver | The application receives requests and sends responses.

See the full registry of value sets defined as part of FHIR.

Explanation of the columns that may appear on this page:

Level | A few code lists that FHIR defines are hierarchical - each code is assigned a level. In this scheme, some codes are under other codes, and imply that the code they are under also applies
Source | The source of the definition of the code (when the value set draws in codes defined elsewhere)
Code | The code (used as the code in the resource instance). If the code is in italics, this indicates that the code is not selectable ('Abstract')
Display | The display (used in the display element of a Coding). If there is no display, implementers should not simply display the code, but map the concept into their application
Definition | An explanation of the meaning of the concept
Comments | Additional notes about how to use the code

4.2.12.175 Code System http://hl7.org/fhir/message-transport

URL: https://hl7.org/fhir/STU3/codesystem-message-transport.html

This page is part of the FHIR Specification (v3.0.2: STU 3). The current version which supercedes this version is 4.0.1. For a full list of available versions, see the Directory of published versions

Vocabulary Work Group | Maturity Level: 3 | Informative | Use Context: Any

This is a code system defined by the FHIR project.

Summary

Defining URL: | http://hl7.org/fhir/message-transport
Name: | MessageTransport
Definition: | The protocol used for message transport.
Committee: | FHIR Infrastructure Work Group
OID: | 2.16.840.1.113883.4.642.1.175 (for OID based terminology systems)
Source Resource | XML / JSON

This Code system is used in the following value sets:

* MessageTransport (The protocol used for message transport.)

4.2.12.175.1 Content

4.2.12.175.2 MessageTransport

The protocol used for message transport.

This code system http://hl7.org/fhir/message-transport defines the following codes:

Code | Display | Definition
http | HTTP | The application sends or receives messages using HTTP POST (may be over http: or https:).
ftp | FTP | The application sends or receives messages using File Transfer Protocol.
mllp | MLLP | The application sends or receives messages using HL7's Minimal Lower Level Protocol.

See the full registry of value sets defined as part of FHIR.

Explanation of the columns that may appear on this page:

Level | A few code lists that FHIR defines are hierarchical - each code is assigned a level. In this scheme, some codes are under other codes, and imply that the code they are under also applies
Source | The source of the definition of the code (when the value set draws in codes defined elsewhere)
Code | The code (used as the code in the resource instance). If the code is in italics, this indicates that the code is not selectable ('Abstract')
Display | The display (used in the display element of a Coding). If there is no display, implementers should not simply display the code, but map the concept into their application
Definition | An explanation of the meaning of the concept
Comments | Additional notes about how to use the code

4.2.12.177 Code System http://hl7.org/fhir/document-mode

URL: https://hl7.org/fhir/STU3/codesystem-document-mode.html

This page is part of the FHIR Specification (v3.0.2: STU 3). The current version which supercedes this version is 4.0.1. For a full list of available versions, see the Directory of published versions

Vocabulary Work Group | Maturity Level: 3 | Informative | Use Context: Any

This is a code system defined by the FHIR project.

Summary

Defining URL: | http://hl7.org/fhir/document-mode
Name: | DocumentMode
Definition: | Whether the application produces or consumes documents.
Committee: | FHIR Infrastructure Work Group
OID: | 2.16.840.1.113883.4.642.1.177 (for OID based terminology systems)
Source Resource | XML / JSON

This Code system is used in the following value sets:

* DocumentMode (Whether the application produces or consumes documents.)

4.2.12.177.1 Content

4.2.12.177.2 DocumentMode

Whether the application produces or consumes documents.

This code system http://hl7.org/fhir/document-mode defines the following codes:

Code | Display | Definition
producer | Producer | The application produces documents of the specified type.
consumer | Consumer | The application consumes documents of the specified type.

See the full registry of value sets defined as part of FHIR.

Explanation of the columns that may appear on this page:

Level | A few code lists that FHIR defines are hierarchical - each code is assigned a level. In this scheme, some codes are under other codes, and imply that the code they are under also applies
Source | The source of the definition of the code (when the value set draws in codes defined elsewhere)
Code | The code (used as the code in the resource instance). If the code is in italics, this indicates that the code is not selectable ('Abstract')
Display | The display (used in the display element of a Coding). If there is no display, implementers should not simply display the code, but map the concept into their application
Definition | An explanation of the meaning of the concept
Comments | Additional notes about how to use the code

4.2.12.179 Code System http://hl7.org/fhir/message-significance-category

URL: https://hl7.org/fhir/STU3/codesystem-message-significance-category.html

This page is part of the FHIR Specification (v3.0.2: STU 3). The current version which supercedes this version is 4.0.1. For a full list of available versions, see the Directory of published versions

Vocabulary Work Group | Maturity Level: 3 | Informative | Use Context: Any

This is a code system defined by the FHIR project.

Summary

Defining URL: | http://hl7.org/fhir/message-significance-category
Name: | MessageSignificanceCategory
Definition: | The impact of the content of a message.
Committee: | FHIR Infrastructure Work Group
OID: | 2.16.840.1.113883.4.642.1.179 (for OID based terminology systems)
Source Resource | XML / JSON

This Code system is used in the following value sets:

* MessageSignificanceCategory (The impact of the content of a message.)

4.2.12.179.1 Content

4.2.12.179.2 MessageSignificanceCategory

The impact of the content of a message.

This code system http://hl7.org/fhir/message-significance-category defines the following codes:

Code | Display | Definition
Consequence | Consequence | The message represents/requests a change that should not be processed more than once; e.g., making a booking for an appointment.
Currency | Currency | The message represents a response to query for current information. Retrospective processing is wrong and/or wasteful.
Notification | Notification | The content is not necessarily intended to be current, and it can be reprocessed, though there may be version issues created by processing old notifications.

See the full registry of value sets defined as part of FHIR.

Explanation of the columns that may appear on this page:

Level | A few code lists that FHIR defines are hierarchical - each code is assigned a level. In this scheme, some codes are under other codes, and imply that the code they are under also applies

Source | The source of the definition of the code (when the value set draws in codes defined elsewhere)
Code | The code (used as the code in the resource instance). If the code is in italics, this indicates that the code is not selectable ('Abstract')
Display | The display (used in the display element of a Coding). If there is no display, implementers should not simply display the code, but map the concept into their application
Definition | An explanation of the meaning of the concept
Comments | Additional notes about how to use the code

4.2.12.181 Code System http://hl7.org/fhir/versioning-policy

URL: https://hl7.org/fhir/STU3/codesystem-versioning-policy.html

This page is part of the FHIR Specification (v3.0.2: STU 3). The current version which supercedes this version is 4.0.1. For a full list of available versions, see the Directory of published versions

Vocabulary Work Group | Maturity Level: 3 | Informative | Use Context: Any

This is a code system defined by the FHIR project.

Summary

Defining URL: | http://hl7.org/fhir/versioning-policy
Name: | ResourceVersionPolicy
Definition: | How the system supports versioning for a resource.
Committee: | FHIR Infrastructure Work Group
OID: | 2.16.840.1.113883.4.642.1.181 (for OID based terminology systems)
Source Resource | XML / JSON

This Code system is used in the following value sets:

* ResourceVersionPolicy (How the system supports versioning for a resource.)

4.2.12.181.1 Content

4.2.12.181.2 ResourceVersionPolicy

How the system supports versioning for a resource.

This code system http://hl7.org/fhir/versioning-policy defines the following codes:

Code | Display | Definition
no-version | No VersionId Support | VersionId meta-property is not supported (server) or used (client).
versioned | Versioned | VersionId meta-property is supported (server) or used (client).
versioned-update | VersionId tracked fully | VersionId must be correct for updates (server) or will be specified (If-match header) for updates (client).

See the full registry of value sets defined as part of FHIR.

Explanation of the columns that may appear on this page:

Level | A few code lists that FHIR defines are hierarchical - each code is assigned a level. In this scheme, some codes are under other codes, and imply that the code they are under also applies
Source | The source of the definition of the code (when the value set draws in codes defined elsewhere)
Code | The code (used as the code in the resource instance). If the code is in italics, this indicates that the code is not selectable ('Abstract')
Display | The display (used in the display element of a Coding). If there is no display, implementers should not simply display the code, but map the concept into their application
Definition | An explanation of the meaning of the concept
Comments | Additional notes about how to use the code

4.2.12.183 Code System http://hl7.org/fhir/transaction-mode

URL: https://hl7.org/fhir/STU3/codesystem-transaction-mode.html

This page is part of the FHIR Specification (v3.0.2: STU 3). The current version which supercedes this version is 4.0.1. For a full list of available versions, see the Directory of published versions

Vocabulary Work Group | Maturity Level: 0 | Informative | Use Context: Any

This is a code system defined by the FHIR project.

Summary

Defining URL: | http://hl7.org/fhir/transaction-mode
Name: | TransactionMode
Definition: | A code that indicates how transactions are supported.
Committee: | FHIR Infrastructure Work Group
OID: | 2.16.840.1.113883.4.642.1.183 (for OID based terminology systems)
Source Resource | XML / JSON

This Code system is used in the following value sets:

* TransactionMode (A code that indicates how transactions are supported.)

4.2.12.183.1 Content

4.2.12.183.2 TransactionMode

A code that indicates how transactions are supported.

This code system http://hl7.org/fhir/transaction-mode defines the following codes:

Code | Display | Definition
not-supported | None | Neither batch or transaction is supported.
batch | Batches supported | Batches are supported.
transaction | Transactions Supported | Transactions are supported.
both | Batches & Transactions | Both batches and transactions are supported.

See the full registry of value sets defined as part of FHIR.

Explanation of the columns that may appear on this page:

Level | A few code lists that FHIR defines are hierarchical - each code is assigned a level. In this scheme, some codes are under other codes, and imply that the code they are under also applies
Source | The source of the definition of the code (when the value set draws in codes defined elsewhere)
Code | The code (used as the code in the resource instance). If the code is in italics, this indicates that the code is not selectable ('Abstract')
Display | The display (used in the display element of a Coding). If there is no display, implementers should not simply display the code, but map the concept into their application
Definition | An explanation of the meaning of the concept
Comments | Additional notes about how to use the code

4.2.12.185 Code System http://hl7.org/fhir/conditional-delete-status

URL: https://hl7.org/fhir/STU3/codesystem-conditional-delete-status.html

This page is part of the FHIR Specification (v3.0.2: STU 3). The current version which supercedes this version is 4.0.1. For a full list of available versions, see the Directory of published versions

Vocabulary Work Group | Maturity Level: 3 | Informative | Use Context: Any

This is a code system defined by the FHIR project.

Summary

Defining URL: | http://hl7.org/fhir/conditional-delete-status
Name: | ConditionalDeleteStatus
Definition: | A code that indicates how the server supports conditional delete.
Committee: | FHIR Infrastructure Work Group
OID: | 2.16.840.1.113883.4.642.1.185 (for OID based terminology systems)
Source Resource | XML / JSON

This Code system is used in the following value sets:

* ConditionalDeleteStatus (A code that indicates how the server supports conditional delete.)

4.2.12.185.1 Content

4.2.12.185.2 ConditionalDeleteStatus

A code that indicates how the server supports conditional delete.

This code system http://hl7.org/fhir/conditional-delete-status defines the following codes:

Code | Display | Definition
not-supported | Not Supported | No support for conditional deletes.
single | Single Deletes Supported | Conditional deletes are supported, but only single resources at a time.
multiple | Multiple Deletes Supported | Conditional deletes are supported, and multiple resources can be deleted in a single interaction.

See the full registry of value sets defined as part of FHIR.

Explanation of the columns that may appear on this page:

Level | A few code lists that FHIR defines are hierarchical - each code is assigned a level. In this scheme, some codes are under other codes, and imply that the code they are under also applies
Source | The source of the definition of the code (when the value set draws in codes defined elsewhere)
Code | The code (used as the code in the resource instance). If the code is in italics, this indicates that the code is not selectable ('Abstract')
Display | The display (used in the display element of a Coding). If there is no display, implementers should not simply display the code, but map the concept into their application
Definition | An explanation of the meaning of the concept
Comments | Additional notes about how to use the code

4.2.12.187 Code System http://hl7.org/fhir/unknown-content-code

URL: https://hl7.org/fhir/STU3/codesystem-unknown-content-code.html

This page is part of the FHIR Specification (v3.0.2: STU 3). The current version which supercedes this version is 4.0.1. For a full list of available versions, see the Directory of published versions

Vocabulary Work Group | Maturity Level: 3 | Informative | Use Context: Any

This is a code system defined by the FHIR project.

Summary

Defining URL: | http://hl7.org/fhir/unknown-content-code

Name: | UnknownContentCode
Definition: | A code that indicates whether an application accepts unknown elements or extensions when reading resources.
Committee: | FHIR Infrastructure Work Group
OID: | 2.16.840.1.113883.4.642.1.187 (for OID based terminology systems)
Source Resource | XML / JSON

This Code system is used in the following value sets:

* UnknownContentCode (A code that indicates whether an application accepts unknown elements or extensions when reading resources.)

4.2.12.187.1 Content

4.2.12.187.2 UnknownContentCode

A code that indicates whether an application accepts unknown elements or extensions when reading resources.

This code system http://hl7.org/fhir/unknown-content-code defines the following codes:

Code | Display | Definition
no | Neither Elements or Extensions | The application does not accept either unknown elements or extensions.
extensions | Unknown Extensions | The application accepts unknown extensions, but not unknown elements.
elements | Unknown Elements | The application accepts unknown elements, but not unknown extensions.
both | Unknown Elements and Extensions | The application accepts unknown elements and extensions.

See the full registry of value sets defined as part of FHIR.

Explanation of the columns that may appear on this page:

Level | A few code lists that FHIR defines are hierarchical - each code is assigned a level. In this scheme, some codes are under other codes, and imply that the code they are under also applies
Source | The source of the definition of the code (when the value set draws in codes defined elsewhere)
Code | The code (used as the code in the resource instance). If the code is in italics, this indicates that the code is not selectable ('Abstract')
Display | The display (used in the display element of a Coding). If there is no display, implementers should not simply display the code, but map the concept into their application
Definition | An explanation of the meaning of the concept
Comments | Additional notes about how to use the code

4.2.12.189 Code System http://hl7.org/fhir/capability-statement-kind

URL: https://hl7.org/fhir/STU3/codesystem-capability-statement-kind.html

This page is part of the FHIR Specification (v3.0.2: STU 3). The current version which supercedes this version is 4.0.1. For a full list of available versions, see the Directory of published versions

Vocabulary Work Group | Maturity Level: 3 | Informative | Use Context: Any

This is a code system defined by the FHIR project.

Summary

Defining URL: | http://hl7.org/fhir/capability-statement-kind
Name: | CapabilityStatementKind
Definition: | How a capability statement is intended to be used.
Committee: | FHIR Infrastructure Work Group
OID: | 2.16.840.1.113883.4.642.1.189 (for OID based terminology systems)
Source Resource | XML / JSON

This Code system is used in the following value sets:

* CapabilityStatementKind (How a capability statement is intended to be used.)

4.2.12.189.1 Content

4.2.12.189.2 CapabilityStatementKind

How a capability statement is intended to be used.

This code system http://hl7.org/fhir/capability-statement-kind defines the following codes:

Code | Display | Definition | Comments
instance | Instance | The CapabilityStatement instance represents the present capabilities of a specific system instance. This is the kind returned by OPTIONS for a FHIR server end-point.
capability | Capability | The CapabilityStatement instance represents the capabilities of a system or piece of software, independent of a particular installation. | Elements marked as 'optional' represent configurable capabilities
requirements | Requirements | The CapabilityStatement instance represents a set of requirements for other systems to meet; e.g. as part of an implementation guide or 'request for proposal'.

See the full registry of value sets defined as part of FHIR.

Explanation of the columns that may appear on this page:

Level | A few code lists that FHIR defines are hierarchical - each code is assigned a level. In this scheme, some codes are under other codes, and imply that the code they are under also applies
Source | The source of the definition of the code (when the value set draws in codes defined elsewhere)

Code | The code (used as the code in the resource instance). If the code is in italics, this indicates that the code is not selectable ('Abstract')
Display | The display (used in the display element of a Coding). If there is no display, implementers should not simply display the code, but map the concept into their application
Definition | An explanation of the meaning of the concept
Comments | Additional notes about how to use the code

4.2.12.191 Code System http://hl7.org/fhir/conditional-read-status

URL: https://hl7.org/fhir/STU3/codesystem-conditional-read-status.html

This page is part of the FHIR Specification (v3.0.2: STU 3). The current version which supercedes this version is 4.0.1. For a full list of available versions, see the Directory of published versions

Vocabulary Work Group | Maturity Level: 3 | Informative | Use Context: Any

This is a code system defined by the FHIR project.

Summary

Defining URL: | http://hl7.org/fhir/conditional-read-status
Name: | ConditionalReadStatus
Definition: | A code that indicates how the server supports conditional read.
Committee: | FHIR Infrastructure Work Group
OID: | 2.16.840.1.113883.4.642.1.191 (for OID based terminology systems)
Source Resource | XML / JSON

This Code system is used in the following value sets:

* ConditionalReadStatus (A code that indicates how the server supports conditional read.)

4.2.12.191.1 Content

4.2.12.191.2 ConditionalReadStatus

A code that indicates how the server supports conditional read.

This code system http://hl7.org/fhir/conditional-read-status defines the following codes:

Code | Display | Definition
not-supported | Not Supported | No support for conditional deletes.
modified-since | If-Modified-Since | Conditional reads are supported, but only with the If-Modified-Since HTTP Header.
not-match | If-None-Match | Conditional reads are supported, but only with the If-None-Match HTTP Header.
full-support | Full Support | Conditional reads are supported, with both If-Modified-Since and If-None-Match HTTP Headers.

See the full registry of value sets defined as part of FHIR.

Explanation of the columns that may appear on this page:

Level | A few code lists that FHIR defines are hierarchical - each code is assigned a level. In this scheme, some codes are under other codes, and imply that the code they are under also applies
Source | The source of the definition of the code (when the value set draws in codes defined elsewhere)
Code | The code (used as the code in the resource instance). If the code is in italics, this indicates that the code is not selectable ('Abstract')
Display | The display (used in the display element of a Coding). If there is no display, implementers should not simply display the code, but map the concept into their application
Definition | An explanation of the meaning of the concept
Comments | Additional notes about how to use the code

4.2.12.193 Code System http://hl7.org/fhir/reference-handling-policy

URL: https://hl7.org/fhir/STU3/codesystem-reference-handling-policy.html

This page is part of the FHIR Specification (v3.0.2: STU 3). The current version which supercedes this version is 4.0.1. For a full list of available versions, see the Directory of published versions

Vocabulary Work Group | Maturity Level: 3 | Informative | Use Context: Any

This is a code system defined by the FHIR project.

Summary

Defining URL: | http://hl7.org/fhir/reference-handling-policy
Name: | ReferenceHandlingPolicy
Definition: | A set of flags that defines how references are supported.
Committee: | FHIR Infrastructure Work Group
OID: | 2.16.840.1.113883.4.642.1.193 (for OID based terminology systems)
Source Resource | XML / JSON

This Code system is used in the following value sets:

* ReferenceHandlingPolicy (A set of flags that defines how references are supported.)

4.2.12.193.1 Content

4.2.12.193.2 ReferenceHandlingPolicy

A set of flags that defines how references are supported.

This code system http://hl7.org/fhir/reference-handling-policy defines the following codes:

Code | Display | Definition
literal | Literal References | The server supports and populates Literal references where they are known (this code does not guarantee that all references are literal; see 'enforced')
logical | Logical References | The server allows logical references
resolves | Resolves References | The server will attempt to resolve logical references to literal references (if resolution fails, the server may still accept resources; see logical)
enforced | Reference Integrity Enforced | The server enforces that references have integrity - e.g. it ensures that references can always be resolved. This is typically the case for clinical record systems, but often not the case for middleware/proxy systems
local | Local References Only | The server does not support references that point to other servers

See the full registry of value sets defined as part of FHIR.

Explanation of the columns that may appear on this page:

Level | A few code lists that FHIR defines are hierarchical - each code is assigned a level. In this scheme, some codes are under other codes, and imply that the code they are under also applies
Source | The source of the definition of the code (when the value set draws in codes defined elsewhere)
Code | The code (used as the code in the resource instance). If the code is in italics, this indicates that the code is not selectable ('Abstract')
Display | The display (used in the display element of a Coding). If there is no display, implementers should not simply display the code, but map the concept into their application
Definition | An explanation of the meaning of the concept
Comments | Additional notes about how to use the code

4.2.12.197 Code System http://hl7.org/fhir/detectedissue-severity

URL: https://hl7.org/fhir/STU3/codesystem-detectedissue-severity.html

This page is part of the FHIR Specification (v3.0.2: STU 3). The current version which supercedes this version is 4.0.1. For a full list of available versions, see the Directory of published versions

Vocabulary Work Group | Maturity Level: 1 | Informative | Use Context: Any

This is a code system defined by the FHIR project.

Summary

Defining URL: | http://hl7.org/fhir/detectedissue-severity
Name: | DetectedIssueSeverity
Definition: | Indicates the potential degree of impact of the identified issue on the patient.
Committee: | Clinical Decision Support Work Group
OID: | 2.16.840.1.113883.4.642.1.197 (for OID based terminology systems)
Source Resource | XML / JSON

This Code system is used in the following value sets:

* DetectedIssueSeverity (Indicates the potential degree of impact of the identified issue on the patient.)

4.2.12.197.1 Content

4.2.12.197.2 DetectedIssueSeverity

Indicates the potential degree of impact of the identified issue on the patient.

This code system http://hl7.org/fhir/detectedissue-severity defines the following codes:

Code | Display | Definition
high | High | Indicates the issue may be life-threatening or has the potential to cause permanent injury.
moderate | Moderate | Indicates the issue may result in noticeable adverse consequences but is unlikely to be life-threatening or cause permanent injury.
low | Low | Indicates the issue may result in some adverse consequences but is unlikely to substantially affect the situation of the subject.

See the full registry of value sets defined as part of FHIR.

Explanation of the columns that may appear on this page:

Level | A few code lists that FHIR defines are hierarchical - each code is assigned a level. In this scheme, some codes are under other codes, and imply that the code they are under also applies
Source | The source of the definition of the code (when the value set draws in codes defined elsewhere)
Code | The code (used as the code in the resource instance). If the code is in italics, this indicates that the code is not selectable ('Abstract')
Display | The display (used in the display element of a Coding). If there is no display, implementers should not simply display the code, but map the concept into their application
Definition | An explanation of the meaning of the concept
Comments | Additional notes about how to use the code

4.2.12.200 Code System http://hl7.org/fhir/device-status

URL: https://hl7.org/fhir/STU3/codesystem-device-status.html

This page is part of the FHIR Specification (v3.0.2: STU 3). The current version which supercedes this version is 4.0.1. For a full list of available versions, see the Directory of published versions

Vocabulary Work Group | Maturity Level: 2 | Informative | Use Context: Any

This is a code system defined by the FHIR project.

Summary

Defining URL: | http://hl7.org/fhir/device-status
Name: | FHIRDeviceStatus
Definition: | The availability status of the device.
Committee: | Orders and Observations Work Group
OID: | 2.16.840.1.113883.4.642.1.200 (for OID based terminology systems)
Source Resource | XML / JSON

This Code system is used in the following value sets:

* FHIRDeviceStatus (The availability status of the device.)

4.2.12.200.1 Content

4.2.12.200.2 FHIRDeviceStatus

The availability status of the device.

This code system http://hl7.org/fhir/device-status defines the following codes:

Code | Display | Definition
active | Active | The Device is available for use. Note: This means for *implanted devices* the device is implanted in the patient.
inactive | Inactive | The Device is no longer available for use (e.g. lost, expired, damaged). Note: This means for *implanted devices* the device has been removed from the patient.
entered-in-error | Entered in Error | The Device was entered in error and voided.
unknown | Unknown | The status of the device has not been determined.

See the full registry of value sets defined as part of FHIR.

Explanation of the columns that may appear on this page:

Level | A few code lists that FHIR defines are hierarchical - each code is assigned a level. In this scheme, some codes are under other codes, and imply that the code they are under also applies
Source | The source of the definition of the code (when the value set draws in codes defined elsewhere)
Code | The code (used as the code in the resource instance). If the code is in italics, this indicates that the code is not selectable ('Abstract')
Display | The display (used in the display element of a Coding). If there is no display, implementers should not simply display the code, but map the concept into their application
Definition | An explanation of the meaning of the concept
Comments | Additional notes about how to use the code

4.2.12.202 Code System http://hl7.org/fhir/udi-entry-type

URL: https://hl7.org/fhir/STU3/codesystem-udi-entry-type.html

This page is part of the FHIR Specification (v3.0.2: STU 3). The current version which supercedes this version is 4.0.1. For a full list of available versions, see the Directory of published versions

Vocabulary Work Group | Maturity Level: 2 | Informative | Use Context: Any

This is a code system defined by the FHIR project.

Summary

Defining URL: | http://hl7.org/fhir/udi-entry-type
Name: | UDIEntryType
Definition: | Codes to identify how UDI data was entered
Committee: | Orders and Observations Work Group
OID: | 2.16.840.1.113883.4.642.1.202 (for OID based terminology systems)
Source Resource | XML / JSON

This Code system is used in the following value sets:

* UDIEntryType (Codes to identify how UDI data was entered)

4.2.12.202.1 Content

4.2.12.202.2 UDIEntryType

Codes to identify how UDI data was entered

This code system http://hl7.org/fhir/udi-entry-type defines the following codes:

Code | Display | Definition
barcode | BarCode | A Barcode scanner captured the data from the device label
rfid | RFID | An RFID chip reader captured the data from the device label
manual | Manual | The data was read from the label by a person and manually entered. (e.g. via a keyboard)
card | Card | The data originated from a patient's implant card and read by an operator.
self-reported | Self Reported | The data originated from a patient source and not directly scanned or read from a label or card.
unknown | Unknown | The method of data capture has not been determined

See the full registry of value sets defined as part of FHIR.

Explanation of the columns that may appear on this page:

Level | A few code lists that FHIR defines are hierarchical - each code is assigned a level. In this scheme, some codes are under other codes, and imply that the code they are under also applies
Source | The source of the definition of the code (when the value set draws in codes defined elsewhere)
Code | The code (used as the code in the resource instance). If the code is in italics, this indicates that the code is not selectable ('Abstract')
Display | The display (used in the display element of a Coding). If there is no display, implementers should not simply display the code, but map the concept into their application
Definition | An explanation of the meaning of the concept
Comments | Additional notes about how to use the code

4.2.12.204 Code System http://hl7.org/fhir/device-statement-status

URL: https://hl7.org/fhir/STU3/codesystem-device-statement-status.html

This page is part of the FHIR Specification (v3.0.2: STU 3). The current version which supercedes this version is 4.0.1. For a full list of available versions, see the Directory of published versions

Vocabulary Work Group | Maturity Level: 0 | Informative | Use Context: Any

This is a code system defined by the FHIR project.

Summary

Defining URL: | http://hl7.org/fhir/device-statement-status
Name: | DeviceUseStatementStatus
Definition: | A coded concept indicating the current status of a the Device Usage
Committee: | Orders and Observations Work Group
OID: | 2.16.840.1.113883.4.642.1.204 (for OID based terminology systems)
Source Resource | XML / JSON

This Code system is used in the following value sets:

* DeviceUseStatementStatus (A coded concept indicating the current status of a the Device Usage)

4.2.12.204.1 Content

4.2.12.204.2 DeviceUseStatementStatus

A coded concept indicating the current status of a the Device Usage

This code system http://hl7.org/fhir/device-statement-status defines the following codes:

Code | Display | Definition
active | Active | The device is still being used.
completed | Completed | The device is no longer being used.
entered-in-error | Entered in Error | The statement was recorded incorrectly.
intended | Intended | The device may be used at some time in the future.
stopped | Stopped | Actions implied by the statement have been permanently halted, before all of them occurred.
on-hold | On Hold | Actions implied by the statement have been temporarily halted, but are expected to continue later. May also be called "suspended".

See the full registry of value sets defined as part of FHIR.

Explanation of the columns that may appear on this page:

Level | A few code lists that FHIR defines are hierarchical - each code is assigned a level. In this scheme, some codes are under other codes, and imply that the code they are under also applies
Source | The source of the definition of the code (when the value set draws in codes defined elsewhere)
Code | The code (used as the code in the resource instance). If the code is in italics, this indicates that the code is not selectable ('Abstract')
Display | The display (used in the display element of a Coding). If there is no display, implementers should not simply display the code, but map the concept into their application
Definition | An explanation of the meaning of the concept
Comments | Additional notes about how to use the code

4.2.12.211 Code System http://hl7.org/fhir/variant-state

URL: https://hl7.org/fhir/STU3/codesystem-variant-state.html

This page is part of the FHIR Specification (v3.0.2: STU 3). The current version which supercedes this version is 4.0.1. For a full list of available versions, see the Directory of published versions

Vocabulary Work Group | Maturity Level: 0 | Informative | Use Context: Any

This is a code system defined by the FHIR project.

Summary

Defining URL: | http://hl7.org/fhir/variant-state
Name: | sequenceStatus
Definition: | Codes providing the status of the variant test result
Committee: | Clinical Genomics Work Group
OID: | 2.16.840.1.113883.4.642.1.211 (for OID based terminology systems)
Source Resource | XML / JSON

This Code system is used in the following value sets:

* sequenceStatus (Codes providing the status of the variant test result)

4.2.12.211.1 Content

4.2.12.211.2 sequenceStatus

Codes providing the status of the variant test result

This code system http://hl7.org/fhir/variant-state defines the following codes:

Code | Display | Definition
positive | positive | the variant is detected
negative | negative | no variant is detected
absent | absent | result of the variant is missing

See the full registry of value sets defined as part of FHIR.

Explanation of the columns that may appear on this page:

Level | A few code lists that FHIR defines are hierarchical - each code is assigned a level. In this scheme, some codes are under other codes, and imply that the code they are under also applies
Source | The source of the definition of the code (when the value set draws in codes defined elsewhere)
Code | The code (used as the code in the resource instance). If the code is in italics, this indicates that the code is not selectable ('Abstract')
Display | The display (used in the display element of a Coding). If there is no display, implementers should not simply display the code, but map the concept into their application
Definition | An explanation of the meaning of the concept
Comments | Additional notes about how to use the code

4.2.12.215 Code System http://hl7.org/fhir/sequence-type

URL: https://hl7.org/fhir/STU3/codesystem-sequence-type.html

This page is part of the FHIR Specification (v3.0.2: STU 3). The current version which supercedes this version is 4.0.1. For a full list of available versions, see the Directory of published versions

Vocabulary Work Group | Maturity Level: 1 | Informative | Use Context: Any

This is a code system defined by the FHIR project.

Summary

Defining URL: | http://hl7.org/fhir/sequence-type
Name: | sequenceType
Definition: | Type if a sequence -- DNA, RNA, or amino acid sequence
Committee: | Clinical Genomics Work Group
OID: | 2.16.840.1.113883.4.642.1.215 (for OID based terminology systems)
Source Resource | XML / JSON

This Code system is used in the following value sets:

* sequenceType (Type if a sequence -- DNA, RNA, or amino acid sequence)

4.2.12.215.1 Content

4.2.12.215.2 sequenceType

Type if a sequence -- DNA, RNA, or amino acid sequence

This code system http://hl7.org/fhir/sequence-type defines the following codes:

Code | Display | Definition
aa | AA Sequence | Amino acid sequence
dna | DNA Sequence | DNA Sequence
rna | RNA Sequence | RNA Sequence

See the full registry of value sets defined as part of FHIR.

Explanation of the columns that may appear on this page:

Level | A few code lists that FHIR defines are hierarchical - each code is assigned a level. In this scheme, some codes are under other codes, and imply that the code they are under also applies
Source | The source of the definition of the code (when the value set draws in codes defined elsewhere)
Code | The code (used as the code in the resource instance). If the code is in italics, this indicates that the code is not selectable ('Abstract')
Display | The display (used in the display element of a Coding). If there is no display, implementers should not simply display the code, but map the concept into their application
Definition | An explanation of the meaning of the concept
Comments | Additional notes about how to use the code

4.2.12.220 Code System http://hl7.org/fhir/chromosome-human

URL: https://hl7.org/fhir/STU3/codesystem-chromosome-human.html

This page is part of the FHIR Specification (v3.0.2: STU 3). The current version which supercedes this version is 4.0.1. For a full list of available versions, see the Directory of published versions

Vocabulary Work Group | Maturity Level: 1 | Informative | Use Context: Any

This is a code system defined by the FHIR project.

Summary

Defining URL: | http://hl7.org/fhir/chromosome-human
Name: | chromosome-human
Definition: | Chromosome number for human
Committee: | Clinical Genomics Work Group
OID: | 2.16.840.1.113883.4.642.1.220 (for OID based terminology systems)
Source Resource | XML / JSON

This Code system is used in the following value sets:

* chromosome-human (Chromosome number for human)

4.2.12.220.1 Content

4.2.12.220.2 chromosome-human

Chromosome number for human

This code system http://hl7.org/fhir/chromosome-human defines the following codes:

Code	Display	Definition
1	chromosome 1	chromosome 1
2	chromosome 2	chromosome 2
3	chromosome 3	chromosome 3
4	chromosome 4	chromosome 4
5	chromosome 5	chromosome 5
6	chromosome 6	chromosome 6
7	chromosome 7	chromosome 7
8	chromosome 8	chromosome 8
9	chromosome 9	chromosome 9
10	chromosome 10	chromosome 10
11	chromosome 11	chromosome 11
12	chromosome 12	chromosome 12
13	chromosome 13	chromosome 13
14	chromosome 14	chromosome 14
15	chromosome 15	chromosome 15
16	chromosome 16	chromosome 16
17	chromosome 17	chromosome 17
18	chromosome 18	chromosome 18
19	chromosome 19	chromosome 19
20	chromosome 20	chromosome 20
21	chromosome 21	chromosome 21
22	chromosome 22	chromosome 22
X	chromosome X	chromosome X
Y	chromosome Y	chromosome Y

See the full registry of value sets defined as part of FHIR.

Explanation of the columns that may appear on this page:

Level | A few code lists that FHIR defines are hierarchical - each code is assigned a level. In this scheme, some codes are under other codes, and imply that the code they are under also applies
Source | The source of the definition of the code (when the value set draws in codes defined elsewhere)
Code | The code (used as the code in the resource instance). If the code is in italics, this indicates that the code is not selectable ('Abstract')
Display | The display (used in the display element of a Coding). If there is no display, implementers should not simply display the code, but map the concept into their application
Definition | An explanation of the meaning of the concept
Comments | Additional notes about how to use the code

4.2.12.222 Code System http://hl7.org/fhir/copy-number-event

URL: https://hl7.org/fhir/STU3/codesystem-copy-number-event.html

This page is part of the FHIR Specification (v3.0.2: STU 3). The current version which supercedes this version is 4.0.1. For a full list of available versions, see the Directory of published versions

Vocabulary Work Group | Maturity Level: 0 | Informative | Use Context: Any

This is a code system defined by the FHIR project.

Summary

Defining URL: | http://hl7.org/fhir/copy-number-event
Name: | CopyNumberEvent
Definition: | Copy Number Event

Committee: | Clinical Genomics Work Group
OID: | 2.16.840.1.113883.4.642.1.222 (for OID based terminology systems)
Source Resource | XML / JSON

This Code system is used in the following value sets:

* CopyNumberEvent (Copy Number Event)

4.2.12.222.1 Content

4.2.12.222.2 CopyNumberEvent

Copy Number Event

This code system http://hl7.org/fhir/copy-number-event defines the following codes:

Code | Display | Definition
amp | amplificaiton | amplificaiton
del | deletion | deletion
lof | loss of function | loss of function

See the full registry of value sets defined as part of FHIR.

Explanation of the columns that may appear on this page:

Level | A few code lists that FHIR defines are hierarchical - each code is assigned a level. In this scheme, some codes are under other codes, and imply that the code they are under also applies
Source | The source of the definition of the code (when the value set draws in codes defined elsewhere)
Code | The code (used as the code in the resource instance). If the code is in italics, this indicates that the code is not selectable ('Abstract')
Display | The display (used in the display element of a Coding). If there is no display, implementers should not simply display the code, but map the concept into their application
Definition | An explanation of the meaning of the concept
Comments | Additional notes about how to use the code

4.2.12.224 Code System http://hl7.org/fhir/quality-type

URL: https://hl7.org/fhir/STU3/codesystem-quality-type.html

This page is part of the FHIR Specification (v3.0.2: STU 3). The current version which supercedes this version is 4.0.1. For a full list of available versions, see the Directory of published versions

Vocabulary Work Group | Maturity Level: 1 | Informative | Use Context: Any

This is a code system defined by the FHIR project.

Summary

Defining URL: | http://hl7.org/fhir/quality-type
Name: | qualityType
Definition: | Type for quality report
Committee: | Clinical Genomics Work Group
OID: | 2.16.840.1.113883.4.642.1.224 (for OID based terminology systems)
Source Resource | XML / JSON

This Code system is used in the following value sets:

* qualityType (Type for quality report)

4.2.12.224.1 Content

4.2.12.224.2 qualityType

Type for quality report

This code system http://hl7.org/fhir/quality-type defines the following codes:

Code | Display | Definition
indel | INDEL Comparison | INDEL Comparison
snp | SNP Comparison | SNP Comparison
unknown | UNKNOWN Comparison | UNKNOWN Comparison

See the full registry of value sets defined as part of FHIR.

Explanation of the columns that may appear on this page:

Level | A few code lists that FHIR defines are hierarchical - each code is assigned a level. In this scheme, some codes are under other codes, and imply that the code they are under also applies
Source | The source of the definition of the code (when the value set draws in codes defined elsewhere)
Code | The code (used as the code in the resource instance). If the code is in italics, this indicates that the code is not selectable ('Abstract')
Display | The display (used in the display element of a Coding). If there is no display, implementers should not simply display the code, but map the concept into their application
Definition | An explanation of the meaning of the concept
Comments | Additional notes about how to use the code

4.2.12.226 Code System http://hl7.org/fhir/repository-type

URL: https://hl7.org/fhir/STU3/codesystem-repository-type.html

This page is part of the FHIR Specification (v3.0.2: STU 3). The current version which supercedes this version is 4.0.1. For a full list of available versions, see the Directory of published versions

Vocabulary Work Group | Maturity Level: 1 | Informative | Use Context: Any

This is a code system defined by the FHIR project.

Summary

Defining URL: | http://hl7.org/fhir/repository-type
Name: | repositoryType
Definition: | Type for access of external URI
Committee: | Clinical Genomics Work Group
OID: | 2.16.840.1.113883.4.642.1.226 (for OID based terminology systems)
Source Resource | XML / JSON

This Code system is used in the following value sets:

* repositoryType (Type for access of external URI)

4.2.12.226.1 Content

4.2.12.226.2 repositoryType

Type for access of external URI

This code system http://hl7.org/fhir/repository-type defines the following codes:

Code | Display | Definition
directlink | Click and see | When URL is clicked, the resource can be seen directly (by webpage or by download link format)
openapi | The URL is the RESTful or other kind of API that can access to the result. | When the API method (e.g. [base_url]/[parameter]) related with the URL of the website is executed, the resource can be seen directly (usually in JSON or XML format)
login | Result cannot be access unless an account is logged in | When logged into the website, the resource can be seen.
oauth | Result need to be fetched with API and need LOGIN(or cookies are required when visiting the link of resource) | When logged in and follow the API in the website related with URL, the resource can be seen.
other | Some other complicated or particular way to get resource from URL. | Some other complicated or particular way to get resource from URL.

See the full registry of value sets defined as part of FHIR.

Explanation of the columns that may appear on this page:

Level | A few code lists that FHIR defines are hierarchical - each code is assigned a level. In this scheme, some codes are under other codes, and imply that the code they are under also applies
Source | The source of the definition of the code (when the value set draws in codes defined elsewhere)
Code | The code (used as the code in the resource instance). If the code is in italics, this indicates that the code is not selectable ('Abstract')
Display | The display (used in the display element of a Coding). If there is no display, implementers should not simply display the code, but map the concept into their application
Definition | An explanation of the meaning of the concept
Comments | Additional notes about how to use the code

4.2.12.231 Code System http://hl7.org/fhir/diagnostic-report-status

URL: https://hl7.org/fhir/STU3/codesystem-diagnostic-report-status.html

This page is part of the FHIR Specification (v3.0.2: STU 3). The current version which supercedes this version is 4.0.1. For a full list of available versions, see the Directory of published versions

Vocabulary Work Group | Maturity Level: 3 | Informative | Use Context: Any

This is a code system defined by the FHIR project.

Summary

Defining URL: | http://hl7.org/fhir/diagnostic-report-status
Name: | DiagnosticReportStatus
Definition: | The status of the diagnostic report as a whole.
Committee: | Orders and Observations Work Group
OID: | 2.16.840.1.113883.4.642.1.231 (for OID based terminology systems)
Source Resource | XML / JSON

This Code system is used in the following value sets:

* DiagnosticReportStatus (The status of the diagnostic report as a whole.)

4.2.12.231.1 Content

4.2.12.231.2 DiagnosticReportStatus

The status of the diagnostic report as a whole.

This code system http://hl7.org/fhir/diagnostic-report-status defines the following codes:

Lvl | Code | Display | Definition

1 | registered | Registered | The existence of the report is registered, but there is nothing yet available.
1 | partial | Partial | This is a partial (e.g. initial, interim or preliminary) report: data in the report may be incomplete or unverified.
2 | preliminary | Preliminary | Verified early results are available, but not all results are final.
1 | final | Final | The report is complete and verified by an authorized person.
1 | amended | Amended | Subsequent to being final, the report has been modified. This includes any change in the results, diagnosis, narrative text, or other content of a report that has been issued.
2 | corrected | Corrected | Subsequent to being final, the report has been modified to correct an error in the report or referenced results.
2 | appended | Appended | Subsequent to being final, the report has been modified by adding new content. The existing content is unchanged.
1 | cancelled | Cancelled | The report is unavailable because the measurement was not started or not completed (also sometimes called "aborted").
1 | entered-in-error | Entered in Error | The report has been withdrawn following a previous final release. This electronic record should never have existed, though it is possible that real-world decisions were based on it. (If real-world activity has occurred, the status should be "cancelled" rather than "entered-in-error".)
1 | unknown | Unknown | The authoring system does not know which of the status values currently applies for this request. Note: This concept is not to be used for "other" - one of the listed statuses is presumed to apply, it's just not known which one.

See the full registry of value sets defined as part of FHIR.

Explanation of the columns that may appear on this page:

Level | A few code lists that FHIR defines are hierarchical - each code is assigned a level. In this scheme, some codes are under other codes, and imply that the code they are under also applies
Source | The source of the definition of the code (when the value set draws in codes defined elsewhere)
Code | The code (used as the code in the resource instance). If the code is in italics, this indicates that the code is not selectable ('Abstract')
Display | The display (used in the display element of a Coding). If there is no display, implementers should not simply display the code, but map the concept into their application
Definition | An explanation of the meaning of the concept
Comments | Additional notes about how to use the code

4.2.12.234 Code System http://hl7.org/fhir/composition-attestation-mode

URL: https://hl7.org/fhir/STU3/codesystem-composition-attestation-mode.html

This page is part of the FHIR Specification (v3.0.2: STU 3). The current version which supercedes this version is 4.0.1. For a full list of available versions, see the Directory of published versions

Vocabulary Work Group | Maturity Level: 2 | Informative | Use Context: Any

This is a code system defined by the FHIR project.

Summary

Defining URL: | http://hl7.org/fhir/composition-attestation-mode
Name: | CompositionAttestationMode
Definition: | The way in which a person authenticated a composition.
Committee: | Structured Documents Work Group
OID: | 2.16.840.1.113883.4.642.1.234 (for OID based terminology systems)
Source Resource | XML / JSON

This Code system is used in the following value sets:

* CompositionAttestationMode (The way in which a person authenticated a composition.)

4.2.12.234.1 Content

4.2.12.234.2 CompositionAttestationMode

The way in which a person authenticated a composition.

This code system http://hl7.org/fhir/composition-attestation-mode defines the following codes:

Code | Display | Definition
personal | Personal | The person authenticated the content in their personal capacity.
professional | Professional | The person authenticated the content in their professional capacity.
legal | Legal | The person authenticated the content and accepted legal responsibility for its content.
official | Official | The organization authenticated the content as consistent with their policies and procedures.

See the full registry of value sets defined as part of FHIR.

Explanation of the columns that may appear on this page:

Level | A few code lists that FHIR defines are hierarchical - each code is assigned a level. In this scheme, some codes are under other codes, and imply that the code they are under also applies
Source | The source of the definition of the code (when the value set draws in codes defined elsewhere)
Code | The code (used as the code in the resource instance). If the code is in italics, this indicates that the code is not selectable ('Abstract')
Display | The display (used in the display element of a Coding). If there is no display, implementers should not simply display the code, but map the concept into their application
Definition | An explanation of the meaning of the concept
Comments | Additional notes about how to use the code

4.2.12.237 Code System http://hl7.org/fhir/composition-status

URL: https://hl7.org/fhir/STU3/codesystem-composition-status.html

This page is part of the FHIR Specification (v3.0.2: STU 3). The current version which supercedes this version is 4.0.1. For a full list of available versions, see the Directory of published versions

Vocabulary Work Group | Maturity Level: 3 | Informative | Use Context: Any

This is a code system defined by the FHIR project.

Summary

Defining URL: | http://hl7.org/fhir/composition-status
Name: | CompositionStatus
Definition: | The workflow/clinical status of the composition.
Committee: | Structured Documents Work Group
OID: | 2.16.840.1.113883.4.642.1.237 (for OID based terminology systems)
Source Resource | XML / JSON

This Code system is used in the following value sets:

* CompositionStatus (The workflow/clinical status of the composition.)

4.2.12.237.1 Content

4.2.12.237.2 CompositionStatus

The workflow/clinical status of the composition.

This code system http://hl7.org/fhir/composition-status defines the following codes:

Code | Display | Definition
preliminary | Preliminary | This is a preliminary composition or document (also known as initial or interim). The content may be incomplete or unverified.
final | Final | This version of the composition is complete and verified by an appropriate person and no further work is planned. Any subsequent updates would be on a new version of the composition.
amended | Amended | The composition content or the referenced resources have been modified (edited or added to) subsequent to being released as "final" and the composition is complete and verified by an authorized person.
entered-in-error | Entered in Error | The composition or document was originally created/issued in error, and this is an amendment that marks that the entire series should not be considered as valid.

See the full registry of value sets defined as part of FHIR.

Explanation of the columns that may appear on this page:

Level | A few code lists that FHIR defines are hierarchical - each code is assigned a level. In this scheme, some codes are under other codes, and imply that the code they are under also applies
Source | The source of the definition of the code (when the value set draws in codes defined elsewhere)
Code | The code (used as the code in the resource instance). If the code is in italics, this indicates that the code is not selectable ('Abstract')
Display | The display (used in the display element of a Coding). If there is no display, implementers should not simply display the code, but map the concept into their application
Definition | An explanation of the meaning of the concept
Comments | Additional notes about how to use the code

4.2.12.240 Code System http://hl7.org/fhir/document-relationship-type

URL: https://hl7.org/fhir/STU3/codesystem-document-relationship-type.html

This page is part of the FHIR Specification (v3.0.2: STU 3). The current version which supercedes this version is 4.0.1. For a full list of available versions, see the Directory of published versions

Vocabulary Work Group | Maturity Level: 3 | Informative | Use Context: Any

This is a code system defined by the FHIR project.

Summary

Defining URL: | http://hl7.org/fhir/document-relationship-type
Name: | DocumentRelationshipType
Definition: | The type of relationship between documents.
Committee: | Structured Documents Work Group
OID: | 2.16.840.1.113883.4.642.1.240 (for OID based terminology systems)
Source Resource | XML / JSON

This Code system is used in the following value sets:

* DocumentRelationshipType (The type of relationship between documents.)

4.2.12.240.1 Content

4.2.12.240.2 DocumentRelationshipType

The type of relationship between documents.

This code system http://hl7.org/fhir/document-relationship-type defines the following codes:

Code | Display | Definition
replaces | Replaces | This document logically replaces or supersedes the target document.
transforms | Transforms | This document was generated by transforming the target document (e.g. format or language conversion).

signs | Signs | This document is a signature of the target document.
appends | Appends | This document adds additional information to the target document.

See the full registry of value sets defined as part of FHIR.

Explanation of the columns that may appear on this page:

Level | A few code lists that FHIR defines are hierarchical - each code is assigned a level. In this scheme, some codes are under other codes, and imply that the code they are under also applies
Source | The source of the definition of the code (when the value set draws in codes defined elsewhere)
Code | The code (used as the code in the resource instance). If the code is in italics, this indicates that the code is not selectable ('Abstract')
Display | The display (used in the display element of a Coding). If there is no display, implementers should not simply display the code, but map the concept into their application
Definition | An explanation of the meaning of the concept
Comments | Additional notes about how to use the code

4.2.12.242 Code System http://hl7.org/fhir/encounter-status

URL: https://hl7.org/fhir/STU3/codesystem-encounter-status.html

This page is part of the FHIR Specification (v3.0.2: STU 3). The current version which supercedes this version is 4.0.1. For a full list of available versions, see the Directory of published versions

Vocabulary Work Group | Maturity Level: 2 | Informative | Use Context: Any

This is a code system defined by the FHIR project.

Summary

Defining URL: | http://hl7.org/fhir/encounter-status
Name: | EncounterStatus
Definition: | Current state of the encounter
Committee: | Patient Administration Work Group
OID: | 2.16.840.1.113883.4.642.1.242 (for OID based terminology systems)
Source Resource | XML / JSON

This Code system is used in the following value sets:

* EncounterStatus (Current state of the encounter)

4.2.12.242.1 Content

4.2.12.242.2 EncounterStatus

Current state of the encounter

This code system http://hl7.org/fhir/encounter-status defines the following codes:

Code | Display | Definition
planned | Planned | The Encounter has not yet started.
arrived | Arrived | The Patient is present for the encounter, however is not currently meeting with a practitioner.
triaged | Triaged | The patient has been assessed for the priority of their treatment based on the severity of their condition.
in-progress | In Progress | The Encounter has begun and the patient is present / the practitioner and the patient are meeting.
onleave | On Leave | The Encounter has begun, but the patient is temporarily on leave.
finished | Finished | The Encounter has ended.
cancelled | Cancelled | The Encounter has ended before it has begun.
entered-in-error | Entered in Error | This instance should not have been part of this patient's medical record.
unknown | Unknown | The encounter status is unknown. Note that "unknown" is a value of last resort and every attempt should be made to provide a meaningful value other than "unknown".

See the full registry of value sets defined as part of FHIR.

Explanation of the columns that may appear on this page:

Level | A few code lists that FHIR defines are hierarchical - each code is assigned a level. In this scheme, some codes are under other codes, and imply that the code they are under also applies
Source | The source of the definition of the code (when the value set draws in codes defined elsewhere)
Code | The code (used as the code in the resource instance). If the code is in italics, this indicates that the code is not selectable ('Abstract')
Display | The display (used in the display element of a Coding). If there is no display, implementers should not simply display the code, but map the concept into their application
Definition | An explanation of the meaning of the concept
Comments | Additional notes about how to use the code

4.2.12.244 Code System http://hl7.org/fhir/encounter-type

URL: https://hl7.org/fhir/STU3/codesystem-encounter-type.html

This page is part of the FHIR Specification (v3.0.2: STU 3). The current version which supercedes this version is 4.0.1. For a full list of available versions, see the Directory of published versions

Vocabulary Work Group | Maturity Level: 1 | Informative | Use Context: Not Intended for Production use

This is a code system defined by the FHIR project.

Summary

Defining URL: | http://hl7.org/fhir/encounter-type
Name: | EncounterType
Definition: | This example value set defines a set of codes that can be used to indicate the type of encounter: a specific code indicating type of service provided.
Committee: | Patient Administration Work Group
OID: | 2.16.840.1.113883.4.642.1.244 (for OID based terminology systems)
Source Resource | XML / JSON

This Code system is used in the following value sets:

* EncounterType (This example value set defines a set of codes that can be used to indicate the type of encounter: a specific code indicating type of service provided.)

4.2.12.244.1 Content

4.2.12.244.2 EncounterType

This example value set defines a set of codes that can be used to indicate the type of encounter: a specific code indicating type of service provided.

This code system http://hl7.org/fhir/encounter-type defines the following codes:

Code | Display | Definition
ADMS | Annual diabetes mellitus screening
BD/BM-clin | Bone drilling/bone marrow punction in clinic
CCS60 | Infant colon screening - 60 minutes
OKI | Outpatient Kenacort injection

See the full registry of value sets defined as part of FHIR.

Explanation of the columns that may appear on this page:

Level | A few code lists that FHIR defines are hierarchical - each code is assigned a level. In this scheme, some codes are under other codes, and imply that the code they are under also applies
Source | The source of the definition of the code (when the value set draws in codes defined elsewhere)
Code | The code (used as the code in the resource instance). If the code is in italics, this indicates that the code is not selectable ('Abstract')
Display | The display (used in the display element of a Coding). If there is no display, implementers should not simply display the code, but map the concept into their application
Definition | An explanation of the meaning of the concept
Comments | Additional notes about how to use the code

4.2.12.246 Code System http://hl7.org/fhir/participant-type

URL: https://hl7.org/fhir/STU3/codesystem-encounter-participant-type.html

This page is part of the FHIR Specification (v3.0.2: STU 3). The current version which supercedes this version is 4.0.1. For a full list of available versions, see the Directory of published versions

Vocabulary Work Group | Maturity Level: 3 | Informative | Use Context: Not Intended for Production use

This is a code system defined by the FHIR project.

Summary

Defining URL: | http://hl7.org/fhir/participant-type
Name: | ParticipantType
Definition: | This value set defines a set of codes that can be used to indicate how an individual participates in an encounter.
Committee: | Patient Administration Work Group
OID: | 2.16.840.1.113883.4.642.1.246 (for OID based terminology systems)
Source Resource | XML / JSON

This Code system is used in the following value sets:

* ParticipantType (This value set defines a set of codes that can be used to indicate how an individual participates in an encounter.)

4.2.12.246.1 Content

4.2.12.246.2 ParticipantType

This value set defines a set of codes that can be used to indicate how an individual participates in an encounter.

This code system http://hl7.org/fhir/participant-type defines the following codes:

Code | Display | Definition
translator | Translator | A translator who is facilitating communication with the patient during the encounter.
emergency | Emergency | A person to be contacted in case of an emergency during the encounter.

See the full registry of value sets defined as part of FHIR.

Explanation of the columns that may appear on this page:

Level | A few code lists that FHIR defines are hierarchical - each code is assigned a level. In this scheme, some codes are under other codes, and imply that the code they are under also applies
Source | The source of the definition of the code (when the value set draws in codes defined elsewhere)

Code | The code (used as the code in the resource instance). If the code is in italics, this indicates that the code is not selectable ('Abstract')
Display | The display (used in the display element of a Coding). If there is no display, implementers should not simply display the code, but map the concept into their application
Definition | An explanation of the meaning of the concept
Comments | Additional notes about how to use the code

4.2.12.249 Code System http://hl7.org/fhir/encounter-special-arrangements

URL: https://hl7.org/fhir/STU3/codesystem-encounter-special-arrangements.html

This page is part of the FHIR Specification (v3.0.2: STU 3). The current version which supercedes this version is 4.0.1. For a full list of available versions, see the Directory of published versions

Vocabulary Work Group | Maturity Level: 2 | Informative | Use Context: Not Intended for Production use

This is a code system defined by the FHIR project.

Summary

Defining URL: | http://hl7.org/fhir/encounter-special-arrangements
Name: | SpecialArrangements
Definition: | This value set defines a set of codes that can be used to indicate the kinds of special arrangements in place for a patients visit.
Committee: | Patient Administration Work Group
OID: | 2.16.840.1.113883.4.642.1.249 (for OID based terminology systems)
Source Resource | XML / JSON

This Code system is used in the following value sets:

* SpecialArrangements (This value set defines a set of codes that can be used to indicate the kinds of special arrangements in place for a patients visit.)

4.2.12.249.1 Content

4.2.12.249.2 SpecialArrangements

This value set defines a set of codes that can be used to indicate the kinds of special arrangements in place for a patients visit.

This code system http://hl7.org/fhir/encounter-special-arrangements defines the following codes:

Code | Display | Definition
wheel | Wheelchair | The patient requires a wheelchair to be made available for the encounter.
add-bed | Additional bedding | An additional bed made available for a person accompanying the patient, for example a parent accompanying a child.
int | Interpreter | The patient is not fluent in the local language and requires an interpreter to be available. Refer to the Patient.Language property for the type of interpreter required.
att | Attendant | A person who accompanies a patient to provide assistive services necessary for the patient's care during the encounter.
dog | Guide dog | The patient has a guide-dog and the location used for the encounter should be able to support the presence of the service animal.

See the full registry of value sets defined as part of FHIR.

Explanation of the columns that may appear on this page:

Level | A few code lists that FHIR defines are hierarchical - each code is assigned a level. In this scheme, some codes are under other codes, and imply that the code they are under also applies
Source | The source of the definition of the code (when the value set draws in codes defined elsewhere)
Code | The code (used as the code in the resource instance). If the code is in italics, this indicates that the code is not selectable ('Abstract')
Display | The display (used in the display element of a Coding). If there is no display, implementers should not simply display the code, but map the concept into their application
Definition | An explanation of the meaning of the concept
Comments | Additional notes about how to use the code

4.2.12.251 Code System http://hl7.org/fhir/diet

URL: https://hl7.org/fhir/STU3/codesystem-encounter-diet.html

This page is part of the FHIR Specification (v3.0.2: STU 3). The current version which supercedes this version is 4.0.1. For a full list of available versions, see the Directory of published versions

Vocabulary Work Group | Maturity Level: 1 | Informative | Use Context: Not Intended for Production use

This is a code system defined by the FHIR project.

Summary

Defining URL: | http://hl7.org/fhir/diet
Name: | Diet
Definition: | This value set defines a set of codes that can be used to indicate dietary preferences or restrictions a patient may have.
Committee: | Patient Administration Work Group
OID: | 2.16.840.1.113883.4.642.1.251 (for OID based terminology systems)
Source Resource | XML / JSON

This Code system is used in the following value sets:

* Diet (This value set defines a set of codes that can be used to indicate dietary preferences or restrictions a patient may have.)

4.2.12.251.1 Content

4.2.12.251.2 Diet

This value set defines a set of codes that can be used to indicate dietary preferences or restrictions a patient may have.

This code system http://hl7.org/fhir/diet defines the following codes:

Code | Display | Definition
vegetarian | Vegetarian | Food without meat, poultry or seafood.
dairy-free | Dairy Free | Excludes dairy products.
nut-free | Nut Free | Excludes ingredients containing nuts.
gluten-free | Gluten Free | Excludes ingredients containing gluten.
vegan | Vegan | Food without meat, poultry, seafood, eggs, dairy products and other animal-derived substances.
halal | Halal | Foods that conform to Islamic law.
kosher | Kosher | Foods that conform to Jewish dietary law.

See the full registry of value sets defined as part of FHIR.

Explanation of the columns that may appear on this page:

Level | A few code lists that FHIR defines are hierarchical - each code is assigned a level. In this scheme, some codes are under other codes, and imply that the code they are under also applies
Source | The source of the definition of the code (when the value set draws in codes defined elsewhere)
Code | The code (used as the code in the resource instance). If the code is in italics, this indicates that the code is not selectable ('Abstract')
Display | The display (used in the display element of a Coding). If there is no display, implementers should not simply display the code, but map the concept into their application
Definition | An explanation of the meaning of the concept
Comments | Additional notes about how to use the code

4.2.12.253 Code System http://hl7.org/fhir/admit-source

URL: https://hl7.org/fhir/STU3/codesystem-encounter-admit-source.html

This page is part of the FHIR Specification (v3.0.2: STU 3). The current version which supercedes this version is 4.0.1. For a full list of available versions, see the Directory of published versions

Vocabulary Work Group | Maturity Level: 2 | Informative | Use Context: Not Intended for Production use

This is a code system defined by the FHIR project.

Summary

Defining URL: | http://hl7.org/fhir/admit-source
Name: | AdmitSource
Definition: | This value set defines a set of codes that can be used to indicate from where the patient came in.
Committee: | Patient Administration Work Group
OID: | 2.16.840.1.113883.4.642.1.253 (for OID based terminology systems)
Source Resource | XML / JSON

This Code system is used in the following value sets:

* AdmitSource (This value set defines a set of codes that can be used to indicate from where the patient came in.)

4.2.12.253.1 Content

4.2.12.253.2 AdmitSource

This value set defines a set of codes that can be used to indicate from where the patient came in.

This code system http://hl7.org/fhir/admit-source defines the following codes:

Code | Display | Definition
hosp-trans | Transferred from other hospital | The Patient has been transferred from another hospital for this encounter.
emd | From accident/emergency department | The patient has been transferred from the emergency department within the hospital. This is typically used in the transition to an inpatient encounter
outp | From outpatient department | The patient has been transferred from an outpatient department within the hospital.
born | Born in hospital | The patient is a newborn and the encounter will track the baby related activities (as opposed to the Mothers encounter - that may be associated using the newborn encounters partof property)
gp | General Practitioner referral | The patient has been admitted due to a referred from a General Practitioner.
mp | Medical Practitioner/physician referral | The patient has been admitted due to a referred from a Specialist (as opposed to a General Practitioner).
nursing | From nursing home | The patient has been transferred from a nursing home.
psych | From psychiatric hospital | The patient has been transferred from a psychiatric facility.
rehab | From rehabilitation facility | The patient has been transferred from a rehabilitiation facility or clinic.
other | Other | The patient has been admitted from a source otherwise not specified here.

See the full registry of value sets defined as part of FHIR.

Explanation of the columns that may appear on this page:

Level | A few code lists that FHIR defines are hierarchical - each code is assigned a level. In this scheme, some codes are under other codes, and imply that the code they are under also applies
Source | The source of the definition of the code (when the value set draws in codes defined elsewhere)
Code | The code (used as the code in the resource instance). If the code is in italics, this indicates that the code is not selectable ('Abstract')
Display | The display (used in the display element of a Coding). If there is no display, implementers should not simply display the code, but map the concept into their application
Definition | An explanation of the meaning of the concept
Comments | Additional notes about how to use the code

4.2.12.255 Code System http://hl7.org/fhir/discharge-disposition

URL: https://hl7.org/fhir/STU3/codesystem-encounter-discharge-disposition.html

This page is part of the FHIR Specification (v3.0.2: STU 3). The current version which supercedes this version is 4.0.1. For a full list of available versions, see the Directory of published versions

Vocabulary Work Group | Maturity Level: 1 | Informative | Use Context: Not Intended for Production use

This is a code system defined by the FHIR project.

Summary

Defining URL: | http://hl7.org/fhir/discharge-disposition
Name: | DischargeDisposition
Definition: | This value set defines a set of codes that can be used to where the patient left the hospital.
Committee: | Patient Administration Work Group
OID: | 2.16.840.1.113883.4.642.1.255 (for OID based terminology systems)
Source Resource | XML / JSON

This Code system is used in the following value sets:

* DischargeDisposition (This value set defines a set of codes that can be used to where the patient left the hospital.)

4.2.12.255.1 Content

4.2.12.255.2 DischargeDisposition

This value set defines a set of codes that can be used to where the patient left the hospital.

This code system http://hl7.org/fhir/discharge-disposition defines the following codes:

Code | Display | Definition
home | Home | The patient was dicharged and has indicated that they are going to return home afterwards.
other-hcf | Other healthcare facility | The patient was transferred to another healthcare facility.
hosp | Hospice | The patient has been discharged into palliative care.
long | Long-term care | The patient has been discharged into long-term care where is likely to be monitored through an ongoing episode-of-care.
aadvice | Left against advice | The patient self discharged against medical advice.
exp | Expired | The patient has deceased during this encounter.
psy | Psychiatric hospital | The patient has been transferred to a psychiatric facility.
rehab | Rehabilitation | The patient was discharged and is to receive post acute care rehabilitation services.
snf | Skilled nursing facility | The patient has been discharged to a skilled nursing facility for the patient to receive additional care.
oth | Other | The discharge disposition has not otherwise defined.

See the full registry of value sets defined as part of FHIR.

Explanation of the columns that may appear on this page:

Level | A few code lists that FHIR defines are hierarchical - each code is assigned a level. In this scheme, some codes are under other codes, and imply that the code they are under also applies
Source | The source of the definition of the code (when the value set draws in codes defined elsewhere)
Code | The code (used as the code in the resource instance). If the code is in italics, this indicates that the code is not selectable ('Abstract')
Display | The display (used in the display element of a Coding). If there is no display, implementers should not simply display the code, but map the concept into their application
Definition | An explanation of the meaning of the concept
Comments | Additional notes about how to use the code

4.2.12.258 Code System http://hl7.org/fhir/encounter-location-status

URL: https://hl7.org/fhir/STU3/codesystem-encounter-location-status.html

This page is part of the FHIR Specification (v3.0.2: STU 3). The current version which supercedes this version is 4.0.1. For a full list of available versions, see the Directory of published versions

Vocabulary Work Group | Maturity Level: 2 | Informative | Use Context: Any

This is a code system defined by the FHIR project.

Summary

Defining URL: | http://hl7.org/fhir/encounter-location-status
Name: | EncounterLocationStatus
Definition: | The status of the location.
Committee: | Patient Administration Work Group

OID: | 2.16.840.1.113883.4.642.1.258 (for OID based terminology systems)
Source Resource | XML / JSON

This Code system is used in the following value sets:

* EncounterLocationStatus (The status of the location.)

4.2.12.258.1 Content

4.2.12.258.2 EncounterLocationStatus

The status of the location.

This code system http://hl7.org/fhir/encounter-location-status defines the following codes:

Code | Display | Definition
planned | Planned | The patient is planned to be moved to this location at some point in the future.
active | Active | The patient is currently at this location, or was between the period specified. A system may update these records when the patient leaves the location to either reserved, or completed
reserved | Reserved | This location is held empty for this patient.
completed | Completed | The patient was at this location during the period specified. Not to be used when the patient is currently at the location

See the full registry of value sets defined as part of FHIR.

Explanation of the columns that may appear on this page:

Level | A few code lists that FHIR defines are hierarchical - each code is assigned a level. In this scheme, some codes are under other codes, and imply that the code they are under also applies
Source | The source of the definition of the code (when the value set draws in codes defined elsewhere)
Code | The code (used as the code in the resource instance). If the code is in italics, this indicates that the code is not selectable ('Abstract')
Display | The display (used in the display element of a Coding). If there is no display, implementers should not simply display the code, but map the concept into their application
Definition | An explanation of the meaning of the concept
Comments | Additional notes about how to use the code

4.2.12.261 Code System http://hl7.org/fhir/system-version-processing-mode

URL: https://hl7.org/fhir/STU3/codesystem-system-version-processing-mode.html

This page is part of the FHIR Specification (v3.0.2: STU 3). The current version which supercedes this version is 4.0.1. For a full list of available versions, see the Directory of published versions

Vocabulary Work Group | Maturity Level: 2 | Informative | Use Context: Any

This is a code system defined by the FHIR project.

Summary

Defining URL: | http://hl7.org/fhir/system-version-processing-mode
Name: | SystemVersionProcessingMode
Definition: | How to manage the intersection between a fixed version in a value set, and a fixed version of the system in the expansion profile
Committee: | Vocabulary Work Group
OID: | 2.16.840.1.113883.4.642.1.261 (for OID based terminology systems)
Source Resource | XML / JSON

This Code system is used in the following value sets:

* SystemVersionProcessingMode (How to manage the intersection between a fixed version in a value set, and a fixed version of the system in the expansion profile)

4.2.12.261.1 Content

4.2.12.261.2 SystemVersionProcessingMode

How to manage the intersection between a fixed version in a value set, and a fixed version of the system in the expansion profile

This code system http://hl7.org/fhir/system-version-processing-mode defines the following codes:

Code | Display | Definition
default | Default Version | Use this version of the code system if a value set doesn't specify a version
check | Check ValueSet Version | Use this version of the code system. If a value set specifies a different version, the expansion operation should fail
override | Override ValueSet Version | Use this version of the code system irrespective of which version is specified by a value set. Note that this has obvious safety issues, in that it may result in a value set expansion giving a different list of codes that is both wrong and unsafe, and implementers should only use this capability reluctantly. It primarily exists to deal with situations where specifications have fallen into decay as time passes. If a version is override, the version used SHALL explicitly be represented in the expansion parameters

See the full registry of value sets defined as part of FHIR.

Explanation of the columns that may appear on this page:

Level | A few code lists that FHIR defines are hierarchical - each code is assigned a level. In this scheme, some codes are under other codes, and imply that the code they are under also applies
Source | The source of the definition of the code (when the value set draws in codes defined elsewhere)

Code | The code (used as the code in the resource instance). If the code is in italics, this indicates that the code is not selectable ('Abstract')
Display | The display (used in the display element of a Coding). If there is no display, implementers should not simply display the code, but map the concept into their application
Definition | An explanation of the meaning of the concept
Comments | Additional notes about how to use the code

4.2.12.263 Code System http://hl7.org/fhir/history-status

URL: https://hl7.org/fhir/STU3/codesystem-history-status.html

This page is part of the FHIR Specification (v3.0.2: STU 3). The current version which supercedes this version is 4.0.1. For a full list of available versions, see the Directory of published versions

Vocabulary Work Group | Maturity Level: 2 | Informative | Use Context: Any

This is a code system defined by the FHIR project.

Summary

Defining URL: | http://hl7.org/fhir/history-status
Name: | FamilyHistoryStatus
Definition: | A code that identifies the status of the family history record.
Committee: | Patient Care Work Group
OID: | 2.16.840.1.113883.4.642.1.263 (for OID based terminology systems)
Source Resource | XML / JSON

This Code system is used in the following value sets:

* FamilyHistoryStatus (A code that identifies the status of the family history record.)

4.2.12.263.1 Content

4.2.12.263.2 FamilyHistoryStatus

A code that identifies the status of the family history record.

This code system http://hl7.org/fhir/history-status defines the following codes:

Code | Display | Definition
partial | Partial | Some health information is known and captured, but not complete - see notes for details.
completed | Completed | All available related health information is captured as of the date (and possibly time) when the family member history was taken.
entered-in-error | Entered in error | This instance should not have been part of this patient's medical record.
health-unknown | Health unknown | Health information for this individual is unavailable/unknown.

See the full registry of value sets defined as part of FHIR.

Explanation of the columns that may appear on this page:

Level | A few code lists that FHIR defines are hierarchical - each code is assigned a level. In this scheme, some codes are under other codes, and imply that the code they are under also applies
Source | The source of the definition of the code (when the value set draws in codes defined elsewhere)
Code | The code (used as the code in the resource instance). If the code is in italics, this indicates that the code is not selectable ('Abstract')
Display | The display (used in the display element of a Coding). If there is no display, implementers should not simply display the code, but map the concept into their application
Definition | An explanation of the meaning of the concept
Comments | Additional notes about how to use the code

4.2.12.265 Code System http://hl7.org/fhir/history-not-done-reason

URL: https://hl7.org/fhir/STU3/codesystem-history-not-done-reason.html

This page is part of the FHIR Specification (v3.0.2: STU 3). The current version which supercedes this version is 4.0.1. For a full list of available versions, see the Directory of published versions

Vocabulary Work Group | Maturity Level: 1 | Informative | Use Context: Any

This is a code system defined by the FHIR project.

Summary

Defining URL: | http://hl7.org/fhir/history-not-done-reason
Name: | FamilyHistoryNotDoneReason
Definition: | Codes describing the reason why a family member history was not done.
Committee: | Patient Care Work Group
OID: | 2.16.840.1.113883.4.642.1.265 (for OID based terminology systems)
Source Resource | XML / JSON

This Code system is used in the following value sets:

* FamilyHistoryNotDoneReason (Codes describing the reason why a family member history was not done.)

4.2.12.265.1 Content

4.2.12.265.2 FamilyHistoryNotDoneReason

Codes describing the reason why a family member history was not done.

This code system http://hl7.org/fhir/history-not-done-reason defines the following codes:

Code | Display | Definition
subject-unknown | Subject Unknown | Patient does not know the subject, e.g. the biological parent of an adopted patient.
withheld | Information Withheld | The patient withheld or refused to share the information.
unable-to-obtain | Unable To Obtain | Information cannot be obtained; e.g. unconscious patient
deferred | Deferred | Patient does not have the information now, but can provide the information at a later date.

See the full registry of value sets defined as part of FHIR.

Explanation of the columns that may appear on this page:

Level | A few code lists that FHIR defines are hierarchical - each code is assigned a level. In this scheme, some codes are under other codes, and imply that the code they are under also applies
Source | The source of the definition of the code (when the value set draws in codes defined elsewhere)
Code | The code (used as the code in the resource instance). If the code is in italics, this indicates that the code is not selectable ('Abstract')
Display | The display (used in the display element of a Coding). If there is no display, implementers should not simply display the code, but map the concept into their application
Definition | An explanation of the meaning of the concept
Comments | Additional notes about how to use the code

4.2.12.267 Code System http://hl7.org/fhir/goal-status

URL: https://hl7.org/fhir/STU3/codesystem-goal-status.html

This page is part of the FHIR Specification (v3.0.2: STU 3). The current version which supercedes this version is 4.0.1. For a full list of available versions, see the Directory of published versions

Vocabulary Work Group | Maturity Level: 2 | Informative | Use Context: Any

This is a code system defined by the FHIR project.

Summary

Defining URL: | http://hl7.org/fhir/goal-status
Name: | GoalStatus
Definition: | Indicates whether the goal has been met and is still being targeted
Committee: | Patient Care Work Group
OID: | 2.16.840.1.113883.4.642.1.267 (for OID based terminology systems)
Source Resource | XML / JSON

This Code system is used in the following value sets:

* GoalStatus (Indicates whether the goal has been met and is still being targeted)

4.2.12.267.1 Content

4.2.12.267.2 GoalStatus

Indicates whether the goal has been met and is still being targeted

This code system http://hl7.org/fhir/goal-status defines the following codes:

Lvl | Code | Display | Definition
1 | proposed | Proposed | A goal is proposed for this patient
1 | accepted | Accepted | A proposed goal was accepted or acknowledged
2 | planned | Planned | A goal is planned for this patient
2 | in-progress | In Progress | The goal is being sought but has not yet been reached. (Also applies if goal was reached in the past but there has been regression and goal is being sought again)
3 | on-target | On Target | The goal is on schedule for the planned timelines
3 | ahead-of-target | Ahead of Target | The goal is ahead of the planned timelines
3 | behind-target | Behind Target | The goal is behind the planned timelines
3 | sustaining | Sustaining | The goal has been met, but ongoing activity is needed to sustain the goal objective
2 | achieved | Achieved | The goal has been met and no further action is needed
2 | on-hold | On Hold | The goal remains a long term objective but is no longer being actively pursued for a temporary period of time.
1 | cancelled | Cancelled | The previously accepted goal is no longer being sought
1 | entered-in-error | Entered In Error | The goal was entered in error and voided.
1 | rejected | Rejected | A proposed goal was rejected

See the full registry of value sets defined as part of FHIR.

Explanation of the columns that may appear on this page:

Level | A few code lists that FHIR defines are hierarchical - each code is assigned a level. In this scheme, some codes are under other codes, and imply that the code they are under also applies
Source | The source of the definition of the code (when the value set draws in codes defined elsewhere)
Code | The code (used as the code in the resource instance). If the code is in italics, this indicates that the code is not selectable ('Abstract')
Display | The display (used in the display element of a Coding). If there is no display, implementers should not simply display the code, but map the concept into their application
Definition | An explanation of the meaning of the concept

Comments | Additional notes about how to use the code

4.2.12.269 Code System http://hl7.org/fhir/goal-priority

URL: https://hl7.org/fhir/STU3/codesystem-goal-priority.html

This page is part of the FHIR Specification (v3.0.2: STU 3). The current version which supercedes this version is 4.0.1. For a full list of available versions, see the Directory of published versions

Vocabulary Work Group | Maturity Level: 2 | Informative | Use Context: Not Intended for Production use

This is a code system defined at http://www.hl7.org/Special/committees/patientcare/ .

Summary

Defining URL: | http://hl7.org/fhir/goal-priority
Name: | GoalPriority
Definition: | Indicates the level of importance associated with reaching or sustaining a goal.
Committee: | Patient Care Work Group
OID: | 2.16.840.1.113883.4.642.1.269 (for OID based terminology systems)
Source Resource | XML / JSON

This Code system is used in the following value sets:

* GoalPriority (Indicates the level of importance associated with reaching or sustaining a goal.)

4.2.12.269.1 Content

4.2.12.269.2 GoalPriority

Indicates the level of importance associated with reaching or sustaining a goal.

This code system http://hl7.org/fhir/goal-priority defines the following codes:

Code | Display | Definition
high-priority | High Priority | Indicates that the goal is of considerable importance and should be a primary focus of care delivery.
medium-priority | Medium Priority | Indicates that the goal has a reasonable degree of importance and that concrete action should be taken towards the goal. Attainment is not as critical as high-priority goals.
low-priority | Low Priority | The goal is desirable but is not sufficiently important to devote significant resources to. Achievement of the goal may be sought when incidental to achieving other goals.

See the full registry of value sets defined as part of FHIR.

Explanation of the columns that may appear on this page:

Level | A few code lists that FHIR defines are hierarchical - each code is assigned a level. In this scheme, some codes are under other codes, and imply that the code they are under also applies
Source | The source of the definition of the code (when the value set draws in codes defined elsewhere)
Code | The code (used as the code in the resource instance). If the code is in italics, this indicates that the code is not selectable ('Abstract')
Display | The display (used in the display element of a Coding). If there is no display, implementers should not simply display the code, but map the concept into their application
Definition | An explanation of the meaning of the concept
Comments | Additional notes about how to use the code

4.2.12.271 Code System http://hl7.org/fhir/goal-category

URL: https://hl7.org/fhir/STU3/codesystem-goal-category.html

This page is part of the FHIR Specification (v3.0.2: STU 3). The current version which supercedes this version is 4.0.1. For a full list of available versions, see the Directory of published versions

Vocabulary Work Group | Maturity Level: 1 | Informative | Use Context: Not Intended for Production use

This is a code system defined at http://www.hl7.org/Special/committees/patientcare/ .

Summary

Defining URL: | http://hl7.org/fhir/goal-category
Name: | GoalCategory
Definition: | Example codes for grouping goals for filtering or presentation.
Committee: | Patient Care Work Group
OID: | 2.16.840.1.113883.4.642.1.271 (for OID based terminology systems)
Source Resource | XML / JSON

This Code system is used in the following value sets:

* GoalCategory (Example codes for grouping goals for filtering or presentation.)

4.2.12.271.1 Content

4.2.12.271.2 GoalCategory

Example codes for grouping goals for filtering or presentation.

This code system http://hl7.org/fhir/goal-category defines the following codes:

Code | Display | Definition
dietary | Dietary | Goals related to the consumption of food and/or beverages.
safety | Safety | Goals related to the personal protection of the subject.
behavioral | Behavioral | Goals related to the manner in which the subject acts.
nursing | Nursing | Goals related to the practice of nursing or established by nurses.
physiotherapy | Physiotherapy | Goals related to the mobility and motor capability of the subject.

See the full registry of value sets defined as part of FHIR.

Explanation of the columns that may appear on this page:

Level | A few code lists that FHIR defines are hierarchical - each code is assigned a level. In this scheme, some codes are under other codes, and imply that the code they are under also applies
Source | The source of the definition of the code (when the value set draws in codes defined elsewhere)
Code | The code (used as the code in the resource instance). If the code is in italics, this indicates that the code is not selectable ('Abstract')
Display | The display (used in the display element of a Coding). If there is no display, implementers should not simply display the code, but map the concept into their application
Definition | An explanation of the meaning of the concept
Comments | Additional notes about how to use the code

4.2.12.273 Code System http://hl7.org/fhir/goal-status-reason

URL: https://hl7.org/fhir/STU3/codesystem-goal-status-reason.html

This page is part of the FHIR Specification (v3.0.2: STU 3). The current version which supercedes this version is 4.0.1. For a full list of available versions, see the Directory of published versions

Vocabulary Work Group | Maturity Level: 0 | Informative | Use Context: Not Intended for Production use

This is a code system defined at http://www.hl7.org/Special/committees/patientcare/ .

Summary

Defining URL: | http://hl7.org/fhir/goal-status-reason
Name: | GoalStatusReason
Definition: | Example codes indicating the reason for a current status. Note that these are in no way complete and may not even be appropriate for some uses.
Committee: | Patient Care Work Group
OID: | 2.16.840.1.113883.4.642.1.273 (for OID based terminology systems)
Source Resource | XML / JSON

This Code system is used in the following value sets:

* GoalStatusReason (Example codes indicating the reason for a current status. Note that these are in no way complete and may not even be appropriate for some uses.)

4.2.12.273.1 Content

4.2.12.273.2 GoalStatusReason

Example codes indicating the reason for a current status. Note that these are in no way complete and may not even be appropriate for some uses.

This code system http://hl7.org/fhir/goal-status-reason defines the following codes:

Code | Display | Definition
surgery | Surgery | Goal suspended or ended because of a surgical procedure.
life-event | Life Event | Goal suspended or ended because of a significant life event (marital change, bereavement, etc.).
replaced | Replaced | Goal has been superseded by a new goal.
patient-request | Patient Request | Patient wishes the goal to be set aside, at least temporarily.
temp-not-attainable | Goal Not Attainable Temporarily | Goal can not be reached temporarily.
permanent-not-attainable | Goal Not Attainable Permanently | Goal can not be reached permanently.
financial-barrier | Financial Reason | Goal can not be reached due to financial barrier or reason.
lack-of-transportation | Lack Of Transportation | Goal can not be reached due to a lack of transportation.
lack-of-social-support | Lack Of Social Support | Goal can not be reached due to a lack of social support.

See the full registry of value sets defined as part of FHIR.

Explanation of the columns that may appear on this page:

Level | A few code lists that FHIR defines are hierarchical - each code is assigned a level. In this scheme, some codes are under other codes, and imply that the code they are under also applies
Source | The source of the definition of the code (when the value set draws in codes defined elsewhere)
Code | The code (used as the code in the resource instance). If the code is in italics, this indicates that the code is not selectable ('Abstract')
Display | The display (used in the display element of a Coding). If there is no display, implementers should not simply display the code, but map the concept into their application
Definition | An explanation of the meaning of the concept
Comments | Additional notes about how to use the code

4.2.12.276 Code System http://hl7.org/fhir/graph-compartment-rule

URL: https://hl7.org/fhir/STU3/codesystem-graph-compartment-rule.html

This page is part of the FHIR Specification (v3.0.2: STU 3). The current version which supercedes this version is 4.0.1. For a full list of available versions, see the Directory of published versions

Vocabulary Work Group | Maturity Level: 0 | Informative | Use Context: Any

This is a code system defined by the FHIR project.

Summary

Defining URL: | http://hl7.org/fhir/graph-compartment-rule
Name: | GraphCompartmentRule
Definition: | How a compartment must be linked
Committee: | FHIR Infrastructure Work Group
OID: | 2.16.840.1.113883.4.642.1.276 (for OID based terminology systems)
Source Resource | XML / JSON

This Code system is used in the following value sets:

* GraphCompartmentRule (How a compartment must be linked)

4.2.12.276.1 Content

4.2.12.276.2 GraphCompartmentRule

How a compartment must be linked

This code system http://hl7.org/fhir/graph-compartment-rule defines the following codes:

Code | Display | Definition
identical | Identical | The compartment must be identical (the same literal reference)
matching | Matching | The compartment must be the same - the record must be about the same patient, but the reference may be different
different | Different | The compartment must be different
custom | Custom | The compartment rule is defined in the accompanying FHIRPath expression

See the full registry of value sets defined as part of FHIR.

Explanation of the columns that may appear on this page:

Level | A few code lists that FHIR defines are hierarchical - each code is assigned a level. In this scheme, some codes are under other codes, and imply that the code they are under also applies
Source | The source of the definition of the code (when the value set draws in codes defined elsewhere)
Code | The code (used as the code in the resource instance). If the code is in italics, this indicates that the code is not selectable ('Abstract')
Display | The display (used in the display element of a Coding). If there is no display, implementers should not simply display the code, but map the concept into their application
Definition | An explanation of the meaning of the concept
Comments | Additional notes about how to use the code

4.2.12.278 Code System http://hl7.org/fhir/group-type

URL: https://hl7.org/fhir/STU3/codesystem-group-type.html

This page is part of the FHIR Specification (v3.0.2: STU 3). The current version which supercedes this version is 4.0.1. For a full list of available versions, see the Directory of published versions

Vocabulary Work Group | Maturity Level: 1 | Informative | Use Context: Any

This is a code system defined by the FHIR project.

Summary

Defining URL: | http://hl7.org/fhir/group-type
Name: | GroupType
Definition: | Types of resources that are part of group
Committee: | FHIR Infrastructure Work Group
OID: | 2.16.840.1.113883.4.642.1.278 (for OID based terminology systems)
Source Resource | XML / JSON

This Code system is used in the following value sets:

* GroupType (Types of resources that are part of group)

4.2.12.278.1 Content

4.2.12.278.2 GroupType

Types of resources that are part of group

This code system http://hl7.org/fhir/group-type defines the following codes:

Code | Display | Definition
person | Person | Group contains "person" Patient resources
animal | Animal | Group contains "animal" Patient resources
practitioner | Practitioner | Group contains healthcare practitioner resources
device | Device | Group contains Device resources
medication | Medication | Group contains Medication resources
substance | Substance | Group contains Substance resources

See the full registry of value sets defined as part of FHIR.

Explanation of the columns that may appear on this page:

Level | A few code lists that FHIR defines are hierarchical - each code is assigned a level. In this scheme, some codes are under other codes, and imply that the code they are under also applies
Source | The source of the definition of the code (when the value set draws in codes defined elsewhere)
Code | The code (used as the code in the resource instance). If the code is in italics, this indicates that the code is not selectable ('Abstract')
Display | The display (used in the display element of a Coding). If there is no display, implementers should not simply display the code, but map the concept into their application
Definition | An explanation of the meaning of the concept
Comments | Additional notes about how to use the code

4.2.12.289 Code System http://hl7.org/fhir/vaccination-protocol-dose-status

URL: https://hl7.org/fhir/STU3/codesystem-vaccination-protocol-dose-status.html

This page is part of the FHIR Specification (v3.0.2: STU 3). The current version which supercedes this version is 4.0.1. For a full list of available versions, see the Directory of published versions

Vocabulary Work Group | Maturity Level: 1 | Informative | Use Context: Not Intended for Production use

This is a code system defined by the FHIR project.

Summary

Defining URL: | http://hl7.org/fhir/vaccination-protocol-dose-status
Name: | Vaccination Protocol Dose Status codes
Definition: | The value set to instantiate this attribute should be drawn from a terminologically robust code system that consists of or contains concepts to support describing the validity of a dose relative to a particular recommended schedule. This value set is provided as a suggestive example.
Committee: | Public Health and Emergency Response Work Group
OID: | 2.16.840.1.113883.4.642.1.289 (for OID based terminology systems)
Source Resource | XML / JSON

This Code system is used in the following value sets:

* Vaccination Protocol Dose Status codes (The value set to instantiate this attribute should be drawn from a terminologically robust code system that consists of or contains concepts to support describing the validity of a dose relative to a particular recommended schedule. This value set is provided as a suggestive example.)

4.2.12.289.1 Content

4.2.12.289.2 Vaccination Protocol Dose Status codes

The value set to instantiate this attribute should be drawn from a terminologically robust code system that consists of or contains concepts to support describing the validity of a dose relative to a particular recommended schedule. This value set is provided as a suggestive example.

This code system http://hl7.org/fhir/vaccination-protocol-dose-status defines the following codes:

Code | Display | Definition
count | Counts | The dose counts toward fulfilling a path to immunity for a patient, providing protection against the target disease.
nocount | Does not Count | The dose does not count toward fulfilling a path to immunity for a patient.

See the full registry of value sets defined as part of FHIR.

Explanation of the columns that may appear on this page:

Level | A few code lists that FHIR defines are hierarchical - each code is assigned a level. In this scheme, some codes are under other codes, and imply that the code they are under also applies
Source | The source of the definition of the code (when the value set draws in codes defined elsewhere)
Code | The code (used as the code in the resource instance). If the code is in italics, this indicates that the code is not selectable ('Abstract')
Display | The display (used in the display element of a Coding). If there is no display, implementers should not simply display the code, but map the concept into their application
Definition | An explanation of the meaning of the concept
Comments | Additional notes about how to use the code

4.2.12.291 Code System http://hl7.org/fhir/vaccination-protocol-dose-status-reason

URL: https://hl7.org/fhir/STU3/codesystem-vaccination-protocol-dose-status-reason.html

This page is part of the FHIR Specification (v3.0.2: STU 3). The current version which supercedes this version is 4.0.1. For a full list of available versions, see the Directory of published versions

Vocabulary Work Group | Maturity Level: 1 | Informative | Use Context: Not Intended for Production use

This is a code system defined by the FHIR project.

Summary

Defining URL: | http://hl7.org/fhir/vaccination-protocol-dose-status-reason
Name: | Vaccination Protocol Dose Status Reason codes
Definition: | The value set to instantiate this attribute should be drawn from a terminologically robust code system that consists of or contains concepts to support describing the reason why an administered dose has been assigned a particular status. Often, this reason describes why a dose is considered invalid. This value set is provided as a suggestive example.
Committee: | Public Health and Emergency Response Work Group
OID: | 2.16.840.1.113883.4.642.1.291 (for OID based terminology systems)
Source Resource | XML / JSON

This Code system is used in the following value sets:

* Vaccination Protocol Dose Status Reason codes (The value set to instantiate this attribute should be drawn from a terminologically robust code system that consists of or contains concepts to support describing the reason why an administered dose has been assigned a particular status. Often, this reason describes why a dose is considered invalid. This value set is provided as a suggestive example.)

4.2.12.291.1 Content

4.2.12.291.2 Vaccination Protocol Dose Status Reason codes

The value set to instantiate this attribute should be drawn from a terminologically robust code system that consists of or contains concepts to support describing the reason why an administered dose has been assigned a particular status. Often, this reason describes why a dose is considered invalid. This value set is provided as a suggestive example.

This code system http://hl7.org/fhir/vaccination-protocol-dose-status-reason defines the following codes:

Code | Display | Definition
advstorage | Adverse storage condition | The product was stored in a manner inconsistent with manufacturer guidelines potentially reducing the effectiveness of the product.
coldchbrk | Cold chain break | The product was stored at a temperature inconsistent with manufacturer guidelines potentially reducing the effectiveness of the product.
explot | Expired lot | The product was administered after the expiration date associated with lot of vaccine.
outsidesched | Administered outside recommended schedule | The product was administered at a time inconsistent with the documented schedule.
prodrecall | Product recall | The product administered has been recalled by the manufacturer.

See the full registry of value sets defined as part of FHIR.

Explanation of the columns that may appear on this page:

Level | A few code lists that FHIR defines are hierarchical - each code is assigned a level. In this scheme, some codes are under other codes, and imply that the code they are under also applies
Source | The source of the definition of the code (when the value set draws in codes defined elsewhere)
Code | The code (used as the code in the resource instance). If the code is in italics, this indicates that the code is not selectable ('Abstract')
Display | The display (used in the display element of a Coding). If there is no display, implementers should not simply display the code, but map the concept into their application
Definition | An explanation of the meaning of the concept
Comments | Additional notes about how to use the code

4.2.12.294 Code System http://hl7.org/fhir/immunization-origin

URL: https://hl7.org/fhir/STU3/codesystem-immunization-origin.html

This page is part of the FHIR Specification (v3.0.2: STU 3). The current version which supercedes this version is 4.0.1. For a full list of available versions, see the Directory of published versions

Vocabulary Work Group | Maturity Level: 1 | Informative | Use Context: Not Intended for Production use

This is a code system defined at http://www.hl7.org/Special/committees/pher/index.cfm .

Summary

Defining URL: | http://hl7.org/fhir/immunization-origin
Name: | Immunization Origin Codes
Definition: | The value set to instantiate this attribute should be drawn from a terminologically robust code system that consists of or contains concepts to support describing the source of the data when the report of the immunization event is not based on information from the person, entity or organization who administered the vaccine. This value set is provided as a suggestive example.
Committee: | Public Health and Emergency Response Work Group
OID: | 2.16.840.1.113883.4.642.1.294 (for OID based terminology systems)
Source Resource | XML / JSON

This Code system is used in the following value sets:

* Immunization Origin Codes (The value set to instantiate this attribute should be drawn from a terminologically robust code system that consists of or contains concepts to support describing the source of the data when the report of the immunization event is not based on information from the person, entity or organization who administered the vaccine. This value set is provided as a suggestive example.)

4.2.12.294.1 Content

4.2.12.294.2 Immunization Origin Codes

The value set to instantiate this attribute should be drawn from a terminologically robust code system that consists of or contains concepts to support describing the source of the data when the report of the immunization event is not based on information from the person, entity or organization who administered the vaccine. This value set is provided as a suggestive example.

This code system http://hl7.org/fhir/immunization-origin defines the following codes:

Code | Display | Definition
provider | Other Provider | The data for the immunization event originated with another provider.
record | Written Record | The data for the immunization event originated with a written record for the patient.
recall | Parent/Guardian/Patient Recall | The data for the immunization event originated from the recollection of the patient or parent/guardian of the patient.
school | School Record | The data for the immunization event originated with a school record for the patient.

See the full registry of value sets defined as part of FHIR.

Explanation of the columns that may appear on this page:

Level | A few code lists that FHIR defines are hierarchical - each code is assigned a level. In this scheme, some codes are under other codes, and imply that the code they are under also applies
Source | The source of the definition of the code (when the value set draws in codes defined elsewhere)
Code | The code (used as the code in the resource instance). If the code is in italics, this indicates that the code is not selectable ('Abstract')
Display | The display (used in the display element of a Coding). If there is no display, implementers should not simply display the code, but map the concept into their application
Definition | An explanation of the meaning of the concept
Comments | Additional notes about how to use the code

4.2.12.297 Code System http://hl7.org/fhir/immunization-recommendation-status

URL: https://hl7.org/fhir/STU3/codesystem-immunization-recommendation-status.html

This page is part of the FHIR Specification (v3.0.2: STU 3). The current version which supercedes this version is 4.0.1. For a full list of available versions, see the Directory of published versions

Vocabulary Work Group | Maturity Level: 1 | Informative | Use Context: Not Intended for Production use

This is a code system defined by the FHIR project.

Summary

Defining URL: | http://hl7.org/fhir/immunization-recommendation-status
Name: | Immunization Recommendation Status Codes
Definition: | The value set to instantiate this attribute should be drawn from a terminologically robust code system that consists of or contains concepts to support describing the status of the patient towards perceived immunity against a vaccine preventable disease. This value set is provided as a suggestive example.
Committee: | Public Health and Emergency Response Work Group
OID: | 2.16.840.1.113883.4.642.1.297 (for OID based terminology systems)
Source Resource | XML / JSON

This Code system is used in the following value sets:

* Immunization Recommendation Status Codes (The value set to instantiate this attribute should be drawn from a terminologically robust code system that consists of or contains concepts to support describing the status of the patient towards perceived immunity against a vaccine preventable disease. This value set is provided as a suggestive example.)

4.2.12.297.1 Content

4.2.12.297.2 Immunization Recommendation Status Codes

The value set to instantiate this attribute should be drawn from a terminologically robust code system that consists of or contains concepts to support describing the status of the patient towards perceived immunity against a vaccine preventable disease. This value set is provided as a suggestive example.

This code system http://hl7.org/fhir/immunization-recommendation-status defines the following codes:

Code | Display | Definition
due | Due | The patient is due for their next vaccination.
overdue | Overdue | The patient is considered overdue for their next vaccination.

See the full registry of value sets defined as part of FHIR.

Explanation of the columns that may appear on this page:

Level | A few code lists that FHIR defines are hierarchical - each code is assigned a level. In this scheme, some codes are under other codes, and imply that the code they are under also applies
Source | The source of the definition of the code (when the value set draws in codes defined elsewhere)
Code | The code (used as the code in the resource instance). If the code is in italics, this indicates that the code is not selectable ('Abstract')
Display | The display (used in the display element of a Coding). If there is no display, implementers should not simply display the code, but map the concept into their application
Definition | An explanation of the meaning of the concept
Comments | Additional notes about how to use the code

4.2.12.299 Code System http://hl7.org/fhir/immunization-recommendation-date-criterion

URL: https://hl7.org/fhir/STU3/codesystem-immunization-recommendation-date-criterion.html

This page is part of the FHIR Specification (v3.0.2: STU 3). The current version which supercedes this version is 4.0.1. For a full list of available versions, see the Directory of published versions

Vocabulary Work Group | Maturity Level: 1 | Informative | Use Context: Not Intended for Production use

This is a code system defined by the FHIR project.

Summary

Defining URL: | http://hl7.org/fhir/immunization-recommendation-date-criterion
Name: | Immunization Recommendation Date Criterion Codes
Definition: | The value set to instantiate this attribute should be drawn from a terminologically robust code system that consists of or contains concepts to support the definition of dates relevant to recommendations for future doses of vaccines. This value set is provided as a suggestive example.
Committee: | Public Health and Emergency Response Work Group
OID: | 2.16.840.1.113883.4.642.1.299 (for OID based terminology systems)
Source Resource | XML / JSON

This Code system is used in the following value sets:

* Immunization Recommendation Date Criterion Codes (The value set to instantiate this attribute should be drawn from a terminologically robust code system that consists of or contains concepts to support the definition of dates relevant to recommendations for future doses of vaccines. This value set is provided as a suggestive example.)

4.2.12.299.1 Content

4.2.12.299.2 Immunization Recommendation Date Criterion Codes

The value set to instantiate this attribute should be drawn from a terminologically robust code system that consists of or contains concepts to support the definition of dates relevant to recommendations for future doses of vaccines. This value set is provided as a suggestive example.

This code system http://hl7.org/fhir/immunization-recommendation-date-criterion defines the following codes:

Code | Display | Definition
due | Due | Date the next dose is considered due.
recommended | Recommended | At the recommended date.
earliest | Earliest Date | As early as possible.
overdue | Past Due Date | Date the next dose is considered overdue.
latest | Latest | The latest date the next dose is to be given.

See the full registry of value sets defined as part of FHIR.

Explanation of the columns that may appear on this page:

Level | A few code lists that FHIR defines are hierarchical - each code is assigned a level. In this scheme, some codes are under other codes, and imply that the code they are under also applies
Source | The source of the definition of the code (when the value set draws in codes defined elsewhere)
Code | The code (used as the code in the resource instance). If the code is in italics, this indicates that the code is not selectable ('Abstract')
Display | The display (used in the display element of a Coding). If there is no display, implementers should not simply display the code, but map the concept into their application
Definition | An explanation of the meaning of the concept
Comments | Additional notes about how to use the code

4.2.12.302 Code System http://hl7.org/fhir/guide-dependency-type

URL: https://hl7.org/fhir/STU3/codesystem-guide-dependency-type.html

This page is part of the FHIR Specification (v3.0.2: STU 3). The current version which supercedes this version is 4.0.1. For a full list of available versions, see the Directory of published versions

Vocabulary Work Group | Maturity Level: 1 | Informative | Use Context: Any

This is a code system defined by the FHIR project.

Summary

Defining URL: | http://hl7.org/fhir/guide-dependency-type
Name: | GuideDependencyType
Definition: | How a dependency is represented when the guide is published.
Committee: | FHIR Infrastructure Work Group
OID: | 2.16.840.1.113883.4.642.1.302 (for OID based terminology systems)
Source Resource | XML / JSON

This Code system is used in the following value sets:

* GuideDependencyType (How a dependency is represented when the guide is published.)

4.2.12.302.1 Content

4.2.12.302.2 GuideDependencyType

How a dependency is represented when the guide is published.

This code system http://hl7.org/fhir/guide-dependency-type defines the following codes:

Code | Display | Definition
reference | Reference | The guide is referred to by URL.
inclusion | Inclusion | The guide is embedded in this guide when published.

See the full registry of value sets defined as part of FHIR.

Explanation of the columns that may appear on this page:

Level | A few code lists that FHIR defines are hierarchical - each code is assigned a level. In this scheme, some codes are under other codes, and imply that the code they are under also applies
Source | The source of the definition of the code (when the value set draws in codes defined elsewhere)
Code | The code (used as the code in the resource instance). If the code is in italics, this indicates that the code is not selectable ('Abstract')
Display | The display (used in the display element of a Coding). If there is no display, implementers should not simply display the code, but map the concept into their application
Definition | An explanation of the meaning of the concept
Comments | Additional notes about how to use the code

4.2.12.304 Code System http://hl7.org/fhir/guide-page-kind

URL: https://hl7.org/fhir/STU3/codesystem-guide-page-kind.html

This page is part of the FHIR Specification (v3.0.2: STU 3). The current version which supercedes this version is 4.0.1. For a full list of available versions, see the Directory of published versions

Vocabulary Work Group | Maturity Level: 1 | Informative | Use Context: Any

This is a code system defined by the FHIR project.

Summary

Defining URL: | http://hl7.org/fhir/guide-page-kind
Name: | GuidePageKind
Definition: | The kind of an included page.
Committee: | FHIR Infrastructure Work Group
OID: | 2.16.840.1.113883.4.642.1.304 (for OID based terminology systems)
Source Resource | XML / JSON

This Code system is used in the following value sets:

* GuidePageKind (The kind of an included page.)

4.2.12.304.1 Content

4.2.12.304.2 GuidePageKind

The kind of an included page.

This code system http://hl7.org/fhir/guide-page-kind defines the following codes:

Lvl | Code | Display | Definition
1 | page | Page | This is a page of content that is included in the implementation guide. It has no particular function.
1 | example | Example | This is a page that represents a human readable rendering of an example.
1 | list | List | This is a page that represents a list of resources of one or more types.
1 | include | Include | This is a page showing where an included guide is injected.
1 | directory | Directory | This is a page that lists the resources of a given type, and also creates pages for all the listed types as other pages in the section.
2 | dictionary | Dictionary | This is a page that creates the listed resources as a dictionary.
1 | toc | Table Of Contents | This is a generated page that contains the table of contents.
1 | resource | Resource | This is a page that represents a presented resource. This is typically used for generated conformance resource presentations.

See the full registry of value sets defined as part of FHIR.

Explanation of the columns that may appear on this page:

Level | A few code lists that FHIR defines are hierarchical - each code is assigned a level. In this scheme, some codes are under other codes, and imply that the code they are under also applies
Source | The source of the definition of the code (when the value set draws in codes defined elsewhere)
Code | The code (used as the code in the resource instance). If the code is in italics, this indicates that the code is not selectable ('Abstract')
Display | The display (used in the display element of a Coding). If there is no display, implementers should not simply display the code, but map the concept into their application
Definition | An explanation of the meaning of the concept
Comments | Additional notes about how to use the code

4.2.12.306 Code System http://hl7.org/fhir/linkage-type

URL: https://hl7.org/fhir/STU3/codesystem-linkage-type.html

This page is part of the FHIR Specification (v3.0.2: STU 3). The current version which supercedes this version is 4.0.1. For a full list of available versions, see the Directory of published versions

Vocabulary Work Group | Maturity Level: 0 | Informative | Use Context: Any

This is a code system defined by the FHIR project.

Summary

Defining URL: | http://hl7.org/fhir/linkage-type
Name: | LinkageType
Definition: | Used to distinguish different roles a resource can play within a set of linked resources
Committee: | Patient Care Work Group
OID: | 2.16.840.1.113883.4.642.1.306 (for OID based terminology systems)
Source Resource | XML / JSON

This Code system is used in the following value sets:

* LinkageType (Used to distinguish different roles a resource can play within a set of linked resources)

4.2.12.306.1 Content

4.2.12.306.2 LinkageType

Used to distinguish different roles a resource can play within a set of linked resources

This code system http://hl7.org/fhir/linkage-type defines the following codes:

Code | Display | Definition
source | Source of truth | The record represents the "source of truth" (from the perspective of this Linkage resource) for the underlying event/condition/etc.
alternate | Alternate record | The record represents the alternative view of the underlying event/condition/etc. The record may still be actively maintained, even though it is not considered to be the source of truth.
historical | Historical/obsolete record | The record represents an obsolete record of the underlyng event/condition/etc. It is not expected to be actively maintained.

See the full registry of value sets defined as part of FHIR.

Explanation of the columns that may appear on this page:

Level | A few code lists that FHIR defines are hierarchical - each code is assigned a level. In this scheme, some codes are under other codes, and imply that the code they are under also applies
Source | The source of the definition of the code (when the value set draws in codes defined elsewhere)
Code | The code (used as the code in the resource instance). If the code is in italics, this indicates that the code is not selectable ('Abstract')
Display | The display (used in the display element of a Coding). If there is no display, implementers should not simply display the code, but map the concept into their application
Definition | An explanation of the meaning of the concept
Comments | Additional notes about how to use the code

4.2.12.308 Code System http://hl7.org/fhir/list-example-use-codes

URL: https://hl7.org/fhir/STU3/codesystem-list-example-codes.html

This page is part of the FHIR Specification (v3.0.2: STU 3). The current version which supercedes this version is 4.0.1. For a full list of available versions, see the Directory of published versions

Vocabulary Work Group | Maturity Level: 1 | Informative | Use Context: Not Intended for Production use

This is a code system defined by the FHIR project.

Summary

Defining URL: | http://hl7.org/fhir/list-example-use-codes
Name: | Example Use Codes for List
Definition: | Example use codes for the List resource - typical kinds of use.
Committee: | FHIR Infrastructure Work Group
OID: | 2.16.840.1.113883.4.642.1.308 (for OID based terminology systems)
Source Resource | XML / JSON

This Code system is used in the following value sets:

* Example Use Codes for List (Example use codes for the List resource - typical kinds of use.)

4.2.12.308.1 Content

4.2.12.308.2 Example Use Codes for List

Example use codes for the List resource - typical kinds of use.

This code system http://hl7.org/fhir/list-example-use-codes defines the following codes:

Code | Display | Definition
alerts | Alerts | A list of alerts for the patient.
adverserxns | Adverse Reactions | A list of part adverse reactions.
allergies | Allergies | A list of Allergies for the patient.
medications | Medication List | A list of medication statements for the patient.

problems | Problem List | A list of problems that the patient is known of have (or have had in the past).
worklist | Worklist | A list of items that constitute a set of work to be performed (typically this code would be specialized for more specific uses, such as a ward round list).
waiting | Waiting List | A list of items waiting for an event (perhaps a surgical patient waiting list).
protocols | Protocols | A set of protocols to be followed.
plans | Care Plans | A set of care plans that apply in a particular context of care.

See the full registry of value sets defined as part of FHIR.

Explanation of the columns that may appear on this page:

Level | A few code lists that FHIR defines are hierarchical - each code is assigned a level. In this scheme, some codes are under other codes, and imply that the code they are under also applies
Source | The source of the definition of the code (when the value set draws in codes defined elsewhere)
Code | The code (used as the code in the resource instance). If the code is in italics, this indicates that the code is not selectable ('Abstract')
Display | The display (used in the display element of a Coding). If there is no display, implementers should not simply display the code, but map the concept into their application
Definition | An explanation of the meaning of the concept
Comments | Additional notes about how to use the code

4.2.12.310 Code System http://hl7.org/fhir/list-mode

URL: https://hl7.org/fhir/STU3/codesystem-list-mode.html

This page is part of the FHIR Specification (v3.0.2: STU 3). The current version which supercedes this version is 4.0.1. For a full list of available versions, see the Directory of published versions

Vocabulary Work Group | Maturity Level: 2 | Informative | Use Context: Any

This is a code system defined by the FHIR project.

Summary

Defining URL: | http://hl7.org/fhir/list-mode
Name: | ListMode
Definition: | The processing mode that applies to this list
Committee: | FHIR Infrastructure Work Group
OID: | 2.16.840.1.113883.4.642.1.310 (for OID based terminology systems)
Source Resource | XML / JSON

This Code system is used in the following value sets:

* ListMode (The processing mode that applies to this list)

4.2.12.310.1 Content

4.2.12.310.2 ListMode

The processing mode that applies to this list

This code system http://hl7.org/fhir/list-mode defines the following codes:

Code | Display | Definition
working | Working List | This list is the master list, maintained in an ongoing fashion with regular updates as the real world list it is tracking changes
snapshot | Snapshot List | This list was prepared as a snapshot. It should not be assumed to be current
changes | Change List | A list that indicates where changes have been made or recommended

See the full registry of value sets defined as part of FHIR.

Explanation of the columns that may appear on this page:

Level | A few code lists that FHIR defines are hierarchical - each code is assigned a level. In this scheme, some codes are under other codes, and imply that the code they are under also applies
Source | The source of the definition of the code (when the value set draws in codes defined elsewhere)
Code | The code (used as the code in the resource instance). If the code is in italics, this indicates that the code is not selectable ('Abstract')
Display | The display (used in the display element of a Coding). If there is no display, implementers should not simply display the code, but map the concept into their application
Definition | An explanation of the meaning of the concept
Comments | Additional notes about how to use the code

4.2.12.312 Code System urn:oid:1.2.36.1.2001.1001.101.104.16592

URL: https://hl7.org/fhir/STU3/codesystem-list-item-flag.html

This page is part of the FHIR Specification (v3.0.2: STU 3). The current version which supercedes this version is 4.0.1. For a full list of available versions, see the Directory of published versions

Vocabulary Work Group | Maturity Level: 1 | Informative | Use Context: Not Intended for Production use

This is a code system defined at http://www.nehta.gov.au .

Summary

Defining URL: | urn:oid:1.2.36.1.2001.1001.101.104.16592
Name: | Patient Medicine Change Types

Definition: | Example Item Flags for the List Resource. In this case, these are the kind of flags that would be used on a medication list at the end of a consultation.

Committee: | FHIR Infrastructure Work Group

OID: | 2.16.840.1.113883.4.642.1.312 (for OID based terminology systems)

Copyright: | Copyright © 2012-2013 National E-Health Transition Authority Ltd : This document contains information which is protected by copyright. All Rights Reserved. No part of this work may be reproduced or used in any form or by any means--graphic, electronic, or mechanical, including photocopying, recording, taping, or information storage and retrieval systems--without the permission of NEHTA. All copies of this document must include the copyright and other information contained on this page. Revision 1 Telephone: 1300 901 001 or email: servicedesk@nehta.gov.au Disclaimer: The National E-Health Transition Authority Ltd (NEHTA) makes the information and other material ('Information') in this document available in good faith but without any representation or warranty as to its accuracy or completeness. NEHTA cannot accept any responsibility for the consequences of any use of the Information. As the Information is of a general nature only, it is up to any person using or relying on the Information to ensure that it is accurate, complete and suitable for the circumstances of its use.

Source Resource | XML / JSON

This Code system is used in the following value sets:

* Patient Medicine Change Types (Example Item Flags for the List Resource. In this case, these are the kind of flags that would be used on a medication list at the end of a consultation.)

4.2.12.312.1 Content

4.2.12.312.2 Patient Medicine Change Types

Example Item Flags for the List Resource. In this case, these are the kind of flags that would be used on a medication list at the end of a consultation.

Copyright Statement: Copyright © 2012-2013 National E-Health Transition Authority Ltd : This document contains information which is protected by copyright. All Rights Reserved. No part of this work may be reproduced or used in any form or by any means--graphic, electronic, or mechanical, including photocopying, recording, taping, or information storage and retrieval systems--without the permission of NEHTA. All copies of this document must include the copyright and other information contained on this page. Revision 1 Telephone: 1300 901 001 or email: servicedesk@nehta.gov.au Disclaimer: The National E-Health Transition Authority Ltd (NEHTA) makes the information and other material ('Information') in this document available in good faith but without any representation or warranty as to its accuracy or completeness. NEHTA cannot accept any responsibility for the consequences of any use of the Information. As the Information is of a general nature only, it is up to any person using or relying on the Information to ensure that it is accurate, complete and suitable for the circumstances of its use.

This code system urn:oid:1.2.36.1.2001.1001.101.104.16592 defines the following codes:

Code | Display | Definition

01 | Unchanged | No change has been made to the status of this medicine item.

02 | Changed | The medicine item has changed. The change may be described in an extension (not defined yet)

03 | Cancelled | The prescription for this medicine item was cancelled by an authorized health care provider. The patient may be advised to complete the course of the prescribed medicine. This advice is a clinical decision made based on assessment of the patient's clinical condition.

04 | Prescribed | A new medicine item has been prescribed

05 | Ceased | Administration of this medication item that the patient is currently taking is stopped or recommended to be stopped (i.e. instructed to be ceased by a health care provider). This cessation is anticipated to be permanent. The Change Description should describe the reason for cessation. Example uses: the medication in question is considered ineffective or has caused serious adverse effects. This value applies both to the cessation of a medication that is prescribed by another healthcare provider or patient self-administration of OTC medicines.

06 | Suspended | Administration of this medication item that the patient is currently taking is on hold, or instructed or recommended by a health care provider to be temporarily stopped, or subject to clinical review (i.e. the stop may be temporary or permanent depending on the outcome of clinical review), or temporarily suspended as a pre-requisite to certain surgical or diagnostic procedures.

See the full registry of value sets defined as part of FHIR.

Explanation of the columns that may appear on this page:

Level | A few code lists that FHIR defines are hierarchical - each code is assigned a level. In this scheme, some codes are under other codes, and imply that the code they are under also applies

Source | The source of the definition of the code (when the value set draws in codes defined elsewhere)

Code | The code (used as the code in the resource instance). If the code is in italics, this indicates that the code is not selectable ('Abstract')

Display | The display (used in the display element of a Coding). If there is no display, implementers should not simply display the code, but map the concept into their application

Definition | An explanation of the meaning of the concept

Comments | Additional notes about how to use the code

4.2.12.314 Code System http://hl7.org/fhir/list-empty-reason

URL: https://hl7.org/fhir/STU3/codesystem-list-empty-reason.html

This page is part of the FHIR Specification (v3.0.2: STU 3). The current version which supercedes this version is 4.0.1. For a full list of available versions, see the Directory of published versions

Vocabulary Work Group | Maturity Level: 2 | Informative | Use Context: Not Intended for Production use

This is a code system defined by the FHIR project.

Summary

Defining URL: | http://hl7.org/fhir/list-empty-reason

Name: | List Empty Reasons

Definition: | General reasons for a list to be empty. Reasons are either related to a summary list (i.e. problem or medication list) or to a workflow related list (i.e. consultation list).
Committee: | FHIR Infrastructure Work Group
OID: | 2.16.840.1.113883.4.642.1.314 (for OID based terminology systems)
Source Resource | XML / JSON

This Code system is used in the following value sets:

* List Empty Reasons (General reasons for a list to be empty. Reasons are either related to a summary list (i.e. problem or medication list) or to a workflow related list (i.e. consultation list).)

4.2.12.314.1 Content

4.2.12.314.2 List Empty Reasons

General reasons for a list to be empty. Reasons are either related to a summary list (i.e. problem or medication list) or to a workflow related list (i.e. consultation list).

This code system http://hl7.org/fhir/list-empty-reason defines the following codes:

Code | Display | Definition
nilknown | Nil Known | Clinical judgment that there are no known items for this list after reasonable investigation. Note that this a positive statement by a clinical user, and not a default position asserted by a computer system in the lack of other information. Example uses: * For allergies: the patient or patient's agent/guardian has asserted that he/she is not aware of any allergies (NKA - nil known allergies) * For medications: the patient or patient's agent/guardian has asserted that the patient is known to be taking no medications * For diagnoses, problems and procedures: the patient or patient's agent/guardian has asserted that there is no known event to record.
notasked | Not Asked | The investigation to find out whether there are items for this list has not occurred.
withheld | Information Withheld | The content of the list was not provided due to privacy or confidentiality concerns. Note that it should not be assumed that this means that the particular information in question was withheld due to its contents - it can also be a policy decision.
unavailable | Unavailable | Information to populate this list cannot be obtained; e.g. unconscious patient.
notstarted | Not Started | The work to populate this list has not yet begun.
closed | Closed | This list has now closed or has ceased to be relevant or useful.

See the full registry of value sets defined as part of FHIR.

Explanation of the columns that may appear on this page:

Level | A few code lists that FHIR defines are hierarchical - each code is assigned a level. In this scheme, some codes are under other codes, and imply that the code they are under also applies
Source | The source of the definition of the code (when the value set draws in codes defined elsewhere)
Code | The code (used as the code in the resource instance). If the code is in italics, this indicates that the code is not selectable ('Abstract')
Display | The display (used in the display element of a Coding). If there is no display, implementers should not simply display the code, but map the concept into their application
Definition | An explanation of the meaning of the concept
Comments | Additional notes about how to use the code

4.2.12.316 Code System http://hl7.org/fhir/list-order

URL: https://hl7.org/fhir/STU3/codesystem-list-order.html

This page is part of the FHIR Specification (v3.0.2: STU 3). The current version which supercedes this version is 4.0.1. For a full list of available versions, see the Directory of published versions

Vocabulary Work Group | Maturity Level: 2 | Informative | Use Context: Not Intended for Production use

This is a code system defined by the FHIR project.

Summary

Defining URL: | http://hl7.org/fhir/list-order
Name: | List Order Codes
Definition: | Base values for the order of the items in a list resource.
Committee: | FHIR Infrastructure Work Group
OID: | 2.16.840.1.113883.4.642.1.316 (for OID based terminology systems)
Source Resource | XML / JSON

This Code system is used in the following value sets:

* List Order Codes (Base values for the order of the items in a list resource.)

4.2.12.316.1 Content

4.2.12.316.2 List Order Codes

Base values for the order of the items in a list resource.

This code system http://hl7.org/fhir/list-order defines the following codes:

Code | Display | Definition
user | Sorted by User | The list was sorted by a user. The criteria the user used are not specified.
system | Sorted by System | The list was sorted by the system. The criteria the user used are not specified; define additional codes to specify a particular order (or use other defined codes).
event-date | Sorted by Event Date | The list is sorted by the data of the event. This can be used when the list has items which are dates with past or future events.

entry-date | Sorted by Item Date | The list is sorted by the date the item was added to the list. Note that the date added to the list is not explicit in the list itself.
priority | Sorted by Priority | The list is sorted by priority. The exact method in which priority has been determined is not specified.
alphabetic | Sorted Alphabetically | The list is sorted alphabetically by an unspecified property of the items in the list.
category | Sorted by Category | The list is sorted categorically by an unspecified property of the items in the list.
patient | Sorted by Patient | The list is sorted by patient, with items for each patient grouped together.

See the full registry of value sets defined as part of FHIR.

Explanation of the columns that may appear on this page:

Level | A few code lists that FHIR defines are hierarchical - each code is assigned a level. In this scheme, some codes are under other codes, and imply that the code they are under also applies
Source | The source of the definition of the code (when the value set draws in codes defined elsewhere)
Code | The code (used as the code in the resource instance). If the code is in italics, this indicates that the code is not selectable ('Abstract')
Display | The display (used in the display element of a Coding). If there is no display, implementers should not simply display the code, but map the concept into their application
Definition | An explanation of the meaning of the concept
Comments | Additional notes about how to use the code

4.2.12.318 Code System http://hl7.org/fhir/list-status

URL: https://hl7.org/fhir/STU3/codesystem-list-status.html

This page is part of the FHIR Specification (v3.0.2: STU 3). The current version which supercedes this version is 4.0.1. For a full list of available versions, see the Directory of published versions

Vocabulary Work Group | Maturity Level: 1 | Informative | Use Context: Any

This is a code system defined by the FHIR project.

Summary

Defining URL: | http://hl7.org/fhir/list-status
Name: | ListStatus
Definition: | The current state of the list
Committee: | FHIR Infrastructure Work Group
OID: | 2.16.840.1.113883.4.642.1.318 (for OID based terminology systems)
Source Resource | XML / JSON

This Code system is used in the following value sets:

* ListStatus (The current state of the list)

4.2.12.318.1 Content

4.2.12.318.2 ListStatus

The current state of the list

This code system http://hl7.org/fhir/list-status defines the following codes:

Code | Display | Definition
current | Current | The list is considered to be an active part of the patient's record.
retired | Retired | The list is "old" and should no longer be considered accurate or relevant.
entered-in-error | Entered In Error | The list was never accurate. It is retained for medico-legal purposes only.

See the full registry of value sets defined as part of FHIR.

Explanation of the columns that may appear on this page:

Level | A few code lists that FHIR defines are hierarchical - each code is assigned a level. In this scheme, some codes are under other codes, and imply that the code they are under also applies
Source | The source of the definition of the code (when the value set draws in codes defined elsewhere)
Code | The code (used as the code in the resource instance). If the code is in italics, this indicates that the code is not selectable ('Abstract')
Display | The display (used in the display element of a Coding). If there is no display, implementers should not simply display the code, but map the concept into their application
Definition | An explanation of the meaning of the concept
Comments | Additional notes about how to use the code

4.2.12.320 Code System http://hl7.org/fhir/location-physical-type

URL: https://hl7.org/fhir/STU3/codesystem-location-physical-type.html

This page is part of the FHIR Specification (v3.0.2: STU 3). The current version which supercedes this version is 4.0.1. For a full list of available versions, see the Directory of published versions

Vocabulary Work Group | Maturity Level: 1 | Informative | Use Context: Not Intended for Production use

This is a code system defined by the FHIR project.

Summary

Defining URL: | http://hl7.org/fhir/location-physical-type
Name: | LocationType
Definition: | This example value set defines a set of codes that can be used to indicate the physical form of the Location.

Committee: | Patient Administration Work Group
OID: | 2.16.840.1.113883.4.642.1.320 (for OID based terminology systems)
Source Resource | XML / JSON

This Code system is used in the following value sets:

* LocationType (This example value set defines a set of codes that can be used to indicate the physical form of the Location.)

4.2.12.320.1 Content

4.2.12.320.2 LocationType

This example value set defines a set of codes that can be used to indicate the physical form of the Location.

This code system http://hl7.org/fhir/location-physical-type defines the following codes:

Code | Display | Definition
si | Site | A collection of buildings or other locations such as a site or a campus.
bu | Building | Any Building or structure. This may contain rooms, corridors, wings, etc. It may not have walls, or a roof, but is considered a defined/allocated space.
wi | Wing | A Wing within a Building, this often contains levels, rooms and corridors.
wa | Ward | A Ward is a section of a medical facility that may contain rooms and other types of location.
lvl | Level | A Level in a multi-level Building/Structure.
co | Corridor | Any corridor within a Building, that may connect rooms.
ro | Room | A space that is allocated as a room, it may have walls/roof etc., but does not require these.
bd | Bed | A space that is allocated for sleeping/laying on. This is not the physical bed/trolley that may be moved about, but the space it may occupy.
ve | Vehicle | A means of transportation.
ho | House | A residential dwelling. Usually used to reference a location that a person/patient may reside.
ca | Cabinet | A container that can store goods, equipment, medications or other items.
rd | Road | A defined path to travel between 2 points that has a known name.
area | Area | A defined physical boundary of something, such as a flood risk zone, region, postcode
jdn | Jurisdiction | A wide scope that covers a conceptual domain, such as a Nation (Country wide community or Federal Government - e.g. Ministry of Health), Province or State (community or Government), Business (throughout the enterprise), Nation with a business scope of an agency (e.g. CDC, FDA etc.) or a Business segment (UK Pharmacy), not just an physical boundry

See the full registry of value sets defined as part of FHIR.

Explanation of the columns that may appear on this page:

Level | A few code lists that FHIR defines are hierarchical - each code is assigned a level. In this scheme, some codes are under other codes, and imply that the code they are under also applies
Source | The source of the definition of the code (when the value set draws in codes defined elsewhere)
Code | The code (used as the code in the resource instance). If the code is in italics, this indicates that the code is not selectable ('Abstract')
Display | The display (used in the display element of a Coding). If there is no display, implementers should not simply display the code, but map the concept into their application
Definition | An explanation of the meaning of the concept
Comments | Additional notes about how to use the code

4.2.12.322 Code System http://hl7.org/fhir/location-mode

URL: https://hl7.org/fhir/STU3/codesystem-location-mode.html

This page is part of the FHIR Specification (v3.0.2: STU 3). The current version which supercedes this version is 4.0.1. For a full list of available versions, see the Directory of published versions

Vocabulary Work Group | Maturity Level: 3 | Informative | Use Context: Any

This is a code system defined by the FHIR project.

Summary

Defining URL: | http://hl7.org/fhir/location-mode
Name: | LocationMode
Definition: | Indicates whether a resource instance represents a specific location or a class of locations.
Committee: | Patient Administration Work Group
OID: | 2.16.840.1.113883.4.642.1.322 (for OID based terminology systems)
Source Resource | XML / JSON

This Code system is used in the following value sets:

* LocationMode (Indicates whether a resource instance represents a specific location or a class of locations.)

4.2.12.322.1 Content

4.2.12.322.2 LocationMode

Indicates whether a resource instance represents a specific location or a class of locations.

This code system http://hl7.org/fhir/location-mode defines the following codes:

Code | Display | Definition
instance | Instance | The Location resource represents a specific instance of a location (e.g. Operating Theatre 1A).
kind | Kind | The Location represents a class of locations (e.g. Any Operating Theatre) although this class of locations could be constrained within a specific boundary (such as organization, or parent location, address etc.).

See the full registry of value sets defined as part of FHIR.

Explanation of the columns that may appear on this page:

Level | A few code lists that FHIR defines are hierarchical - each code is assigned a level. In this scheme, some codes are under other codes, and imply that the code they are under also applies
Source | The source of the definition of the code (when the value set draws in codes defined elsewhere)
Code | The code (used as the code in the resource instance). If the code is in italics, this indicates that the code is not selectable ('Abstract')
Display | The display (used in the display element of a Coding). If there is no display, implementers should not simply display the code, but map the concept into their application
Definition | An explanation of the meaning of the concept
Comments | Additional notes about how to use the code

4.2.12.324 Code System http://hl7.org/fhir/location-status

URL: https://hl7.org/fhir/STU3/codesystem-location-status.html

This page is part of the FHIR Specification (v3.0.2: STU 3). The current version which supercedes this version is 4.0.1. For a full list of available versions, see the Directory of published versions

Vocabulary Work Group | Maturity Level: 3 | Informative | Use Context: Any

This is a code system defined by the FHIR project.

Summary

Defining URL: | http://hl7.org/fhir/location-status
Name: | LocationStatus
Definition: | Indicates whether the location is still in use.
Committee: | Patient Administration Work Group
OID: | 2.16.840.1.113883.4.642.1.324 (for OID based terminology systems)
Source Resource | XML / JSON

This Code system is used in the following value sets:

* LocationStatus (Indicates whether the location is still in use.)

4.2.12.324.1 Content

4.2.12.324.2 LocationStatus

Indicates whether the location is still in use.

This code system http://hl7.org/fhir/location-status defines the following codes:

Code | Display | Definition
active | Active | The location is operational.
suspended | Suspended | The location is temporarily closed.
inactive | Inactive | The location is no longer used.

See the full registry of value sets defined as part of FHIR.

Explanation of the columns that may appear on this page:

Level | A few code lists that FHIR defines are hierarchical - each code is assigned a level. In this scheme, some codes are under other codes, and imply that the code they are under also applies
Source | The source of the definition of the code (when the value set draws in codes defined elsewhere)
Code | The code (used as the code in the resource instance). If the code is in italics, this indicates that the code is not selectable ('Abstract')
Display | The display (used in the display element of a Coding). If there is no display, implementers should not simply display the code, but map the concept into their application
Definition | An explanation of the meaning of the concept
Comments | Additional notes about how to use the code

4.2.12.326 Code System http://hl7.org/fhir/digital-media-type

URL: https://hl7.org/fhir/STU3/codesystem-digital-media-type.html

This page is part of the FHIR Specification (v3.0.2: STU 3). The current version which supercedes this version is 4.0.1. For a full list of available versions, see the Directory of published versions

Vocabulary Work Group | Maturity Level: 1 | Informative | Use Context: Any

This is a code system defined by the FHIR project.

Summary

Defining URL: | http://hl7.org/fhir/digital-media-type
Name: | DigitalMediaType
Definition: | Whether the media is a photo, video, or audio
Committee: | FHIR Infrastructure Work Group
OID: | 2.16.840.1.113883.4.642.1.326 (for OID based terminology systems)
Source Resource | XML / JSON

This Code system is used in the following value sets:

* DigitalMediaType (Whether the media is a photo, video, or audio)

4.2.12.326.1 Content

4.2.12.326.2 DigitalMediaType

Whether the media is a photo, video, or audio

This code system http://hl7.org/fhir/digital-media-type defines the following codes:

Code | Display | Definition
photo | Photo | The media consists of one or more unmoving images, including photographs, computer-generated graphs and charts, and scanned documents
video | Video | The media consists of a series of frames that capture a moving image
audio | Audio | The media consists of a sound recording

See the full registry of value sets defined as part of FHIR.

Explanation of the columns that may appear on this page:

Level | A few code lists that FHIR defines are hierarchical - each code is assigned a level. In this scheme, some codes are under other codes, and imply that the code they are under also applies
Source | The source of the definition of the code (when the value set draws in codes defined elsewhere)
Code | The code (used as the code in the resource instance). If the code is in italics, this indicates that the code is not selectable ('Abstract')
Display | The display (used in the display element of a Coding). If there is no display, implementers should not simply display the code, but map the concept into their application
Definition | An explanation of the meaning of the concept
Comments | Additional notes about how to use the code

4.2.12.328 Code System http://hl7.org/fhir/media-subtype

URL: https://hl7.org/fhir/STU3/codesystem-digital-media-subtype.html

This page is part of the FHIR Specification (v3.0.2: STU 3). The current version which supercedes this version is 4.0.1. For a full list of available versions, see the Directory of published versions

Vocabulary Work Group | Maturity Level: 1 | Informative | Use Context: Not Intended for Production use

This is a code system defined by the FHIR project.

Summary

Defining URL: | http://hl7.org/fhir/media-subtype
Name: | Media SubType
Definition: | Detailed information about the type of the image - its kind, purpose, or the kind of equipment used to generate it.
Committee: | FHIR Infrastructure Work Group
OID: | 2.16.840.1.113883.4.642.1.328 (for OID based terminology systems)
Copyright: | This value set includes content from SNOMED CT, which is copyright © 2002+ International Health Terminology Standards Development Organisation (IHTSDO), and distributed by agreement between IHTSDO and HL7. Implementer use of SNOMED CT is not covered by this agreement.
Source Resource | XML / JSON

This Code system is used in the following value sets:

* Media SubType (Detailed information about the type of the image - its kind, purpose, or the kind of equipment used to generate it.)

4.2.12.328.1 Content

4.2.12.328.2 Media SubType

Detailed information about the type of the image - its kind, purpose, or the kind of equipment used to generate it.

Copyright Statement: This value set includes content from SNOMED CT, which is copyright © 2002+ International Health Terminology Standards Development Organisation (IHTSDO), and distributed by agreement between IHTSDO and HL7. Implementer use of SNOMED CT is not covered by this agreement.

This code system http://hl7.org/fhir/media-subtype defines the following codes:

Code | Display | Definition
diagram | Diagram | A diagram. Often used in diagnostic reports
fax | Fax | A digital record of a fax document
scan | Scanned Document | A digital scan of a document. This is reserved for when there is not enough metadata to create a document reference
retina | Retina scan | A retinal image used for identification purposes
fingerprint | Fingerprint | A finger print scan used for identification purposes
iris | Iris | An iris scan used for identification purposes
palm | Palm | A palm scan used for identification purposes
face | Face | A face scan used for identification purposes

See the full registry of value sets defined as part of FHIR.

Explanation of the columns that may appear on this page:

Level | A few code lists that FHIR defines are hierarchical - each code is assigned a level. In this scheme, some codes are under other codes, and imply that the code they are under also applies
Source | The source of the definition of the code (when the value set draws in codes defined elsewhere)

Code | The code (used as the code in the resource instance). If the code is in italics, this indicates that the code is not selectable ('Abstract')
Display | The display (used in the display element of a Coding). If there is no display, implementers should not simply display the code, but map the concept into their application
Definition | An explanation of the meaning of the concept
Comments | Additional notes about how to use the code

4.2.12.331 Code System http://hl7.org/fhir/medication-admin-status

URL: https://hl7.org/fhir/STU3/codesystem-medication-admin-status.html

This page is part of the FHIR Specification (v3.0.2: STU 3). The current version which supercedes this version is 4.0.1. For a full list of available versions, see the Directory of published versions

Vocabulary Work Group | Maturity Level: 2 | Informative | Use Context: Any

This is a code system defined by the FHIR project.

Summary

Defining URL: | http://hl7.org/fhir/medication-admin-status
Name: | MedicationAdministrationStatus
Definition: | A set of codes indicating the current status of a MedicationAdministration.
Committee: | Pharmacy Work Group
OID: | 2.16.840.1.113883.4.642.1.331 (for OID based terminology systems)
Source Resource | XML / JSON

This Code system is used in the following value sets:

* Immunization Status Codes (The value set to instantiate this attribute should be drawn from a terminologically robust code system that consists of or contains concepts to support describing the current status of the administered dose of vaccine.)

* MedicationAdministrationStatus (A set of codes indicating the current status of a MedicationAdministration.)

4.2.12.331.1 Content

4.2.12.331.2 MedicationAdministrationStatus

A set of codes indicating the current status of a MedicationAdministration.

This code system http://hl7.org/fhir/medication-admin-status defines the following codes:

Code | Display | Definition
in-progress | In Progress | The administration has started but has not yet completed.
on-hold | On Hold | Actions implied by the administration have been temporarily halted, but are expected to continue later. May also be called "suspended".
completed | Completed | All actions that are implied by the administration have occurred.
entered-in-error | Entered in Error | The administration was entered in error and therefore nullified.
stopped | Stopped | Actions implied by the administration have been permanently halted, before all of them occurred.
unknown | Unknown | The authoring system does not know which of the status values currently applies for this request. Note: This concept is not to be used for "other" - one of the listed statuses is presumed to apply, it's just not known which one.

See the full registry of value sets defined as part of FHIR.

Explanation of the columns that may appear on this page:

Level | A few code lists that FHIR defines are hierarchical - each code is assigned a level. In this scheme, some codes are under other codes, and imply that the code they are under also applies
Source | The source of the definition of the code (when the value set draws in codes defined elsewhere)
Code | The code (used as the code in the resource instance). If the code is in italics, this indicates that the code is not selectable ('Abstract')
Display | The display (used in the display element of a Coding). If there is no display, implementers should not simply display the code, but map the concept into their application
Definition | An explanation of the meaning of the concept
Comments | Additional notes about how to use the code

4.2.12.333 Code System http://hl7.org/fhir/reason-medication-not-given

URL: https://hl7.org/fhir/STU3/codesystem-reason-medication-not-given-codes.html

This page is part of the FHIR Specification (v3.0.2: STU 3). The current version which supercedes this version is 4.0.1. For a full list of available versions, see the Directory of published versions

Vocabulary Work Group | Maturity Level: 1 | Informative | Use Context: Not Intended for Production use

This is a code system defined by the FHIR project.

Summary

Defining URL: | http://hl7.org/fhir/reason-medication-not-given
Name: | SNOMED CT Reason Medication Not Given Codes
Definition: | This value set includes all medication refused, medication not administered, and non administration of necessary drug or medicine codes from SNOMED CT - provided as an exemplar value set.
Committee: | Pharmacy Work Group
OID: | 2.16.840.1.113883.4.642.1.333 (for OID based terminology systems)

Copyright: | This value set includes content from SNOMED CT, which is copyright 2002 International Health Terminology Standards Development Organisation (IHTSDO), and distributed by agreement between IHTSDO and HL7. Implementer use of SNOMED CT is not covered by this agreement.

Source Resource | XML / JSON

This Code system is not currently used

4.2.12.333.1 Content

4.2.12.333.2 SNOMED CT Reason Medication Not Given Codes

This value set includes all medication refused, medication not administered, and non administration of necessary drug or medicine codes from SNOMED CT - provided as an exemplar value set.

Copyright Statement: This value set includes content from SNOMED CT, which is copyright 2002 International Health Terminology Standards Development Organisation (IHTSDO), and distributed by agreement between IHTSDO and HL7. Implementer use of SNOMED CT is not covered by this agreement.

This code system http://hl7.org/fhir/reason-medication-not-given defines the following codes:

Code	Display	Definition
a	None	No reason known.
b	Away	The patient was not available when the dose was scheduled.
c	Asleep	The patient was asleep when the dose was scheduled.
d	Vomit	The patient was given the medication and immediately vomited it back.

See the full registry of value sets defined as part of FHIR.

Explanation of the columns that may appear on this page:

Level | A few code lists that FHIR defines are hierarchical - each code is assigned a level. In this scheme, some codes are under other codes, and imply that the code they are under also applies

Source | The source of the definition of the code (when the value set draws in codes defined elsewhere)

Code | The code (used as the code in the resource instance). If the code is in italics, this indicates that the code is not selectable ('Abstract')

Display | The display (used in the display element of a Coding). If there is no display, implementers should not simply display the code, but map the concept into their application

Definition | An explanation of the meaning of the concept

Comments | Additional notes about how to use the code

4.2.12.335 Code System http://hl7.org/fhir/reason-medication-given

URL: https://hl7.org/fhir/STU3/codesystem-reason-medication-given-codes.html

This page is part of the FHIR Specification (v3.0.2: STU 3). The current version which supercedes this version is 4.0.1. For a full list of available versions, see the Directory of published versions

Vocabulary Work Group | Maturity Level: 1 | Informative | Use Context: Not Intended for Production use

This is a code system defined by the FHIR project.

Summary

Defining URL: | http://hl7.org/fhir/reason-medication-given

Name: | Reason Medication Given Codes

Definition: | This value set is provided as an example. The value set to instantiate this attribute should be drawn from a robust terminology code system that consists of or contains concepts to support the medication process.

Committee: | Pharmacy Work Group

OID: | 2.16.840.1.113883.4.642.1.335 (for OID based terminology systems)

Source Resource | XML / JSON

This Code system is used in the following value sets:

* Reason Medication Given Codes (This value set is provided as an example. The value set to instantiate this attribute should be drawn from a robust terminology code system that consists of or contains concepts to support the medication process.)

4.2.12.335.1 Content

4.2.12.335.2 Reason Medication Given Codes

This value set is provided as an example. The value set to instantiate this attribute should be drawn from a robust terminology code system that consists of or contains concepts to support the medication process.

This code system http://hl7.org/fhir/reason-medication-given defines the following codes:

Code	Display	Definition
a	None	No reason known.
b	Given as Ordered	The administration was following an ordered protocol.
c	Emergency	The administration was needed to treat an emergency.

See the full registry of value sets defined as part of FHIR.

Explanation of the columns that may appear on this page:

Level | A few code lists that FHIR defines are hierarchical - each code is assigned a level. In this scheme, some codes are under other codes, and imply that the code they are under also applies

Source | The source of the definition of the code (when the value set draws in codes defined elsewhere)
Code | The code (used as the code in the resource instance). If the code is in italics, this indicates that the code is not selectable ('Abstract')
Display | The display (used in the display element of a Coding). If there is no display, implementers should not simply display the code, but map the concept into their application
Definition | An explanation of the meaning of the concept
Comments | Additional notes about how to use the code

4.2.12.338 Code System http://hl7.org/fhir/medication-admin-category

URL: https://hl7.org/fhir/STU3/codesystem-medication-admin-category.html

This page is part of the FHIR Specification (v3.0.2: STU 3). The current version which supercedes this version is 4.0.1. For a full list of available versions, see the Directory of published versions

Vocabulary Work Group | Maturity Level: 2 | Informative | Use Context: Any

This is a code system defined by the FHIR project.

Summary

Defining URL: | http://hl7.org/fhir/medication-admin-category
Name: | MedicationAdministrationCategory
Definition: | A coded concept describing where the medication administered is expected to occur
Committee: | Pharmacy Work Group
OID: | 2.16.840.1.113883.4.642.1.338 (for OID based terminology systems)
Source Resource | XML / JSON

This Code system is used in the following value sets:

* MedicationAdministrationCategory (A coded concept describing where the medication administered is expected to occur)

4.2.12.338.1 Content

4.2.12.338.2 MedicationAdministrationCategory

A coded concept describing where the medication administered is expected to occur

This code system http://hl7.org/fhir/medication-admin-category defines the following codes:

Code | Display | Definition
inpatient | Inpatient | Includes administrations in an inpatient or acute care setting
outpatient | Outpatient | Includes administrations in an outpatient setting (for example, Emergency Department, Outpatient Clinic, Outpatient Surgery, Doctor's office)
community | Community | Includes administrations by the patient in their home (this would include long term care or nursing homes, hospices, etc)

See the full registry of value sets defined as part of FHIR.

Explanation of the columns that may appear on this page:

Level | A few code lists that FHIR defines are hierarchical - each code is assigned a level. In this scheme, some codes are under other codes, and imply that the code they are under also applies
Source | The source of the definition of the code (when the value set draws in codes defined elsewhere)
Code | The code (used as the code in the resource instance). If the code is in italics, this indicates that the code is not selectable ('Abstract')
Display | The display (used in the display element of a Coding). If there is no display, implementers should not simply display the code, but map the concept into their application
Definition | An explanation of the meaning of the concept
Comments | Additional notes about how to use the code

4.2.12.340 Code System http://hl7.org/fhir/medication-dispense-status

URL: https://hl7.org/fhir/STU3/codesystem-medication-dispense-status.html

This page is part of the FHIR Specification (v3.0.2: STU 3). The current version which supercedes this version is 4.0.1. For a full list of available versions, see the Directory of published versions

Vocabulary Work Group | Maturity Level: 2 | Informative | Use Context: Any

This is a code system defined by the FHIR project.

Summary

Defining URL: | http://hl7.org/fhir/medication-dispense-status
Name: | MedicationDispenseStatus
Definition: | A coded concept specifying the state of the dispense event.
Committee: | Pharmacy Work Group
OID: | 2.16.840.1.113883.4.642.1.340 (for OID based terminology systems)
Source Resource | XML / JSON

This Code system is used in the following value sets:

* MedicationDispenseStatus (A coded concept specifying the state of the dispense event.)

4.2.12.340.1 Content

4.2.12.340.2 MedicationDispenseStatus

A coded concept specifying the state of the dispense event.

This code system http://hl7.org/fhir/medication-dispense-status defines the following codes:

Code | Display | Definition
preparation | Preparation | The core event has not started yet, but some staging activities have begun (e.g. initial compounding or packaging of medication). Preparation stages may be tracked for billing purposes.
in-progress | In Progress | The dispense has started but has not yet completed.
on-hold | On Hold | Actions implied by the administration have been temporarily halted, but are expected to continue later. May also be called "suspended"
completed | Completed | All actions that are implied by the dispense have occurred.
entered-in-error | Entered in-Error | The dispense was entered in error and therefore nullified.
stopped | Stopped | Actions implied by the dispense have been permanently halted, before all of them occurred.

See the full registry of value sets defined as part of FHIR.

Explanation of the columns that may appear on this page:

Level | A few code lists that FHIR defines are hierarchical - each code is assigned a level. In this scheme, some codes are under other codes, and imply that the code they are under also applies
Source | The source of the definition of the code (when the value set draws in codes defined elsewhere)
Code | The code (used as the code in the resource instance). If the code is in italics, this indicates that the code is not selectable ('Abstract')
Display | The display (used in the display element of a Coding). If there is no display, implementers should not simply display the code, but map the concept into their application
Definition | An explanation of the meaning of the concept
Comments | Additional notes about how to use the code

4.2.12.342 Code System http://hl7.org/fhir/medication-dispense-category

URL: https://hl7.org/fhir/STU3/codesystem-medication-dispense-category.html

This page is part of the FHIR Specification (v3.0.2: STU 3). The current version which supercedes this version is 4.0.1. For a full list of available versions, see the Directory of published versions

Vocabulary Work Group | Maturity Level: 2 | Informative | Use Context: Any

This is a code system defined by the FHIR project.

Summary

Defining URL: | http://hl7.org/fhir/medication-dispense-category
Name: | MedicationDispenseCategory
Definition: | A code describing where the dispensed medication is expected to be consumed or administered
Committee: | Pharmacy Work Group
OID: | 2.16.840.1.113883.4.642.1.342 (for OID based terminology systems)
Source Resource | XML / JSON

This Code system is used in the following value sets:

* MedicationDispenseCategory (A code describing where the dispensed medication is expected to be consumed or administered)

4.2.12.342.1 Content

4.2.12.342.2 MedicationDispenseCategory

A code describing where the dispensed medication is expected to be consumed or administered

This code system http://hl7.org/fhir/medication-dispense-category defines the following codes:

Code | Display | Definition
inpatient | Inpatient | Includes dispenses for medications to be administered or consumed in an inpatient or acute care setting
outpatient | Outpatient | Includes dispenses for medications to be administered or consumed in an outpatient setting (for example, Emergency Department, Outpatient Clinic, Outpatient Surgery, Doctor's office)
community | Community | Includes dispenses for medications to be administered or consumed by the patient in their home (this would include long term care or nursing homes, hospices, etc)

See the full registry of value sets defined as part of FHIR.

Explanation of the columns that may appear on this page:

Level | A few code lists that FHIR defines are hierarchical - each code is assigned a level. In this scheme, some codes are under other codes, and imply that the code they are under also applies
Source | The source of the definition of the code (when the value set draws in codes defined elsewhere)
Code | The code (used as the code in the resource instance). If the code is in italics, this indicates that the code is not selectable ('Abstract')
Display | The display (used in the display element of a Coding). If there is no display, implementers should not simply display the code, but map the concept into their application
Definition | An explanation of the meaning of the concept
Comments | Additional notes about how to use the code

4.2.12.344 Code System http://hl7.org/fhir/medication-request-status

URL: https://hl7.org/fhir/STU3/codesystem-medication-request-status.html

This page is part of the FHIR Specification (v3.0.2: STU 3). The current version which supercedes this version is 4.0.1. For a full list of available versions, see the Directory of published versions

Vocabulary Work Group | Maturity Level: 3 | Informative | Use Context: Any

This is a code system defined by the FHIR project.

Summary

Defining URL: | http://hl7.org/fhir/medication-request-status
Name: | MedicationRequestStatus
Definition: | A coded concept specifying the state of the prescribing event. Describes the lifecycle of the prescription
Committee: | Pharmacy Work Group
OID: | 2.16.840.1.113883.4.642.1.344 (for OID based terminology systems)
Source Resource | XML / JSON

This Code system is used in the following value sets:

* MedicationRequestStatus (A coded concept specifying the state of the prescribing event. Describes the lifecycle of the prescription)

4.2.12.344.1 Content

4.2.12.344.2 MedicationRequestStatus

A coded concept specifying the state of the prescribing event. Describes the lifecycle of the prescription

This code system http://hl7.org/fhir/medication-request-status defines the following codes:

Code | Display | Definition
active | Active | The prescription is 'actionable', but not all actions that are implied by it have occurred yet.
on-hold | On Hold | Actions implied by the prescription are to be temporarily halted, but are expected to continue later. May also be called "suspended".
cancelled | Cancelled | The prescription has been withdrawn.
completed | Completed | All actions that are implied by the prescription have occurred.
entered-in-error | Entered In Error | The prescription was entered in error.
stopped | Stopped | Actions implied by the prescription are to be permanently halted, before all of them occurred.
draft | Draft | The prescription is not yet 'actionable', i.e. it is a work in progress, requires sign-off or verification, and needs to be run through decision support process.
unknown | Unknown | The authoring system does not know which of the status values currently applies for this request

See the full registry of value sets defined as part of FHIR.

Explanation of the columns that may appear on this page:

Level | A few code lists that FHIR defines are hierarchical - each code is assigned a level. In this scheme, some codes are under other codes, and imply that the code they are under also applies
Source | The source of the definition of the code (when the value set draws in codes defined elsewhere)
Code | The code (used as the code in the resource instance). If the code is in italics, this indicates that the code is not selectable ('Abstract')
Display | The display (used in the display element of a Coding). If there is no display, implementers should not simply display the code, but map the concept into their application
Definition | An explanation of the meaning of the concept
Comments | Additional notes about how to use the code

4.2.12.346 Code System http://hl7.org/fhir/medication-request-intent

URL: https://hl7.org/fhir/STU3/codesystem-medication-request-intent.html

This page is part of the FHIR Specification (v3.0.2: STU 3). The current version which supercedes this version is 4.0.1. For a full list of available versions, see the Directory of published versions

Vocabulary Work Group | Maturity Level: 3 | Informative | Use Context: Any

This is a code system defined by the FHIR project.

Summary

Defining URL: | http://hl7.org/fhir/medication-request-intent
Name: | MedicationRequestIntent
Definition: | The kind of medication order
Committee: | Pharmacy Work Group
OID: | 2.16.840.1.113883.4.642.1.346 (for OID based terminology systems)
Source Resource | XML / JSON

This Code system is used in the following value sets:

* MedicationRequestIntent (The kind of medication order)

4.2.12.346.1 Content

4.2.12.346.2 MedicationRequestIntent

The kind of medication order

This code system http://hl7.org/fhir/medication-request-intent defines the following codes:

Code | Display | Definition
proposal | Proposal | The request is a suggestion made by someone/something that doesn't have an intention to ensure it occurs and without providing an authorization to act
plan | Plan | The request represents an intension to ensure something occurs without providing an authorization for others to act
order | Order | The request represents a request/demand and authorization for action
instance-order | Instance Order | The request represents an instance for the particular order, for example a medication administration record.

See the full registry of value sets defined as part of FHIR.

Explanation of the columns that may appear on this page:

Level | A few code lists that FHIR defines are hierarchical - each code is assigned a level. In this scheme, some codes are under other codes, and imply that the code they are under also applies
Source | The source of the definition of the code (when the value set draws in codes defined elsewhere)
Code | The code (used as the code in the resource instance). If the code is in italics, this indicates that the code is not selectable ('Abstract')
Display | The display (used in the display element of a Coding). If there is no display, implementers should not simply display the code, but map the concept into their application
Definition | An explanation of the meaning of the concept
Comments | Additional notes about how to use the code

4.2.12.349 Code System http://hl7.org/fhir/medication-request-category

URL: https://hl7.org/fhir/STU3/codesystem-medication-request-category.html

This page is part of the FHIR Specification (v3.0.2: STU 3). The current version which supercedes this version is 4.0.1. For a full list of available versions, see the Directory of published versions

Vocabulary Work Group | Maturity Level: 3 | Informative | Use Context: Any

This is a code system defined by the FHIR project.

Summary

Defining URL: | http://hl7.org/fhir/medication-request-category
Name: | MedicationRequestCategory
Definition: | A coded concept identifying where the medication ordered is expected to be consumed or administered
Committee: | Pharmacy Work Group
OID: | 2.16.840.1.113883.4.642.1.349 (for OID based terminology systems)
Source Resource | XML / JSON

This Code system is used in the following value sets:

* MedicationRequestCategory (A coded concept identifying where the medication ordered is expected to be consumed or administered)

4.2.12.349.1 Content

4.2.12.349.2 MedicationRequestCategory

A coded concept identifying where the medication ordered is expected to be consumed or administered

This code system http://hl7.org/fhir/medication-request-category defines the following codes:

Code | Display | Definition
inpatient | Inpatient | Includes orders for medications to be administered or consumed in an inpatient or acute care setting
outpatient | Outpatient | Includes orders for medications to be administered or consumed in an outpatient setting (for example, Emergency Department, Outpatient Clinic, Outpatient Surgery, Doctor's office)
community | Community | Includes orders for medications to be administered or consumed by the patient in their home (this would include long term care or nursing homes, hospices, etc)

See the full registry of value sets defined as part of FHIR.

Explanation of the columns that may appear on this page:

Level | A few code lists that FHIR defines are hierarchical - each code is assigned a level. In this scheme, some codes are under other codes, and imply that the code they are under also applies
Source | The source of the definition of the code (when the value set draws in codes defined elsewhere)
Code | The code (used as the code in the resource instance). If the code is in italics, this indicates that the code is not selectable ('Abstract')
Display | The display (used in the display element of a Coding). If there is no display, implementers should not simply display the code, but map the concept into their application
Definition | An explanation of the meaning of the concept
Comments | Additional notes about how to use the code

4.2.12.351 Code System http://hl7.org/fhir/medication-request-priority

URL: https://hl7.org/fhir/STU3/codesystem-medication-request-priority.html

This page is part of the FHIR Specification (v3.0.2: STU 3). The current version which supercedes this version is 4.0.1. For a full list of available versions, see the Directory of published versions

Vocabulary Work Group | Maturity Level: 3 | Informative | Use Context: Any

This is a code system defined by the FHIR project.

Summary

Defining URL: | http://hl7.org/fhir/medication-request-priority
Name: | MedicationRequestPriority
Definition: | Identifies the level of importance to be assigned to actioning the request
Committee: | Pharmacy Work Group
OID: | 2.16.840.1.113883.4.642.1.351 (for OID based terminology systems)
Source Resource | XML / JSON

This Code system is used in the following value sets:

* MedicationRequestPriority (Identifies the level of importance to be assigned to actioning the request)

4.2.12.351.1 Content

4.2.12.351.2 MedicationRequestPriority

Identifies the level of importance to be assigned to actioning the request

This code system http://hl7.org/fhir/medication-request-priority defines the following codes:

Code | Display | Definition
routine | Routine | The order has a normal priority .
urgent | Urgent | The order should be urgently.
stat | Stat | The order is time-critical.
asap | ASAP | The order should be acted on as soon as possible.

See the full registry of value sets defined as part of FHIR.

Explanation of the columns that may appear on this page:

Level | A few code lists that FHIR defines are hierarchical - each code is assigned a level. In this scheme, some codes are under other codes, and imply that the code they are under also applies
Source | The source of the definition of the code (when the value set draws in codes defined elsewhere)
Code | The code (used as the code in the resource instance). If the code is in italics, this indicates that the code is not selectable ('Abstract')
Display | The display (used in the display element of a Coding). If there is no display, implementers should not simply display the code, but map the concept into their application
Definition | An explanation of the meaning of the concept
Comments | Additional notes about how to use the code

4.2.12.353 Code System http://hl7.org/fhir/medication-statement-status

URL: https://hl7.org/fhir/STU3/codesystem-medication-statement-status.html

This page is part of the FHIR Specification (v3.0.2: STU 3). The current version which supercedes this version is 4.0.1. For a full list of available versions, see the Directory of published versions

Vocabulary Work Group | Maturity Level: 3 | Informative | Use Context: Any

This is a code system defined by the FHIR project.

Summary

Defining URL: | http://hl7.org/fhir/medication-statement-status
Name: | MedicationStatementStatus
Definition: | A coded concept indicating the current status of a MedicationStatement.
Committee: | Pharmacy Work Group
OID: | 2.16.840.1.113883.4.642.1.353 (for OID based terminology systems)
Source Resource | XML / JSON

This Code system is used in the following value sets:

* MedicationStatementStatus (A coded concept indicating the current status of a MedicationStatement.)

4.2.12.353.1 Content

4.2.12.353.2 MedicationStatementStatus

A coded concept indicating the current status of a MedicationStatement.

This code system http://hl7.org/fhir/medication-statement-status defines the following codes:

Code | Display | Definition
active | Active | The medication is still being taken.
completed | Completed | The medication is no longer being taken.
entered-in-error | Entered in Error | The statement was recorded incorrectly.
intended | Intended | The medication may be taken at some time in the future.
stopped | Stopped | Actions implied by the statement have been permanently halted, before all of them occurred.
on-hold | On Hold | Actions implied by the statement have been temporarily halted, but are expected to continue later. May also be called "suspended".

See the full registry of value sets defined as part of FHIR.

Explanation of the columns that may appear on this page:

Level | A few code lists that FHIR defines are hierarchical - each code is assigned a level. In this scheme, some codes are under other codes, and imply that the code they are under also applies
Source | The source of the definition of the code (when the value set draws in codes defined elsewhere)
Code | The code (used as the code in the resource instance). If the code is in italics, this indicates that the code is not selectable ('Abstract')
Display | The display (used in the display element of a Coding). If there is no display, implementers should not simply display the code, but map the concept into their application
Definition | An explanation of the meaning of the concept
Comments | Additional notes about how to use the code

4.2.12.356 Code System http://hl7.org/fhir/medication-statement-category

URL: https://hl7.org/fhir/STU3/codesystem-medication-statement-category.html

This page is part of the FHIR Specification (v3.0.2: STU 3). The current version which supercedes this version is 4.0.1. For a full list of available versions, see the Directory of published versions

Vocabulary Work Group | Maturity Level: 3 | Informative | Use Context: Any

This is a code system defined by the FHIR project.

Summary

Defining URL: | http://hl7.org/fhir/medication-statement-category
Name: | MedicationStatementCategory
Definition: | A coded concept identifying where the medication included in the medicationstatement is expected to be consumed or administered
Committee: | Pharmacy Work Group
OID: | 2.16.840.1.113883.4.642.1.356 (for OID based terminology systems)
Source Resource | XML / JSON

This Code system is used in the following value sets:

* MedicationStatementCategory (A coded concept identifying where the medication included in the medicationstatement is expected to be consumed or administered)

4.2.12.356.1 Content

4.2.12.356.2 MedicationStatementCategory

A coded concept identifying where the medication included in the medicationstatement is expected to be consumed or administered

This code system http://hl7.org/fhir/medication-statement-category defines the following codes:

Code | Display | Definition
inpatient | Inpatient | Includes orders for medications to be administered or consumed in an inpatient or acute care setting
outpatient | Outpatient | Includes orders for medications to be administered or consumed in an outpatient setting (for example, Emergency Department, Outpatient Clinic, Outpatient Surgery, Doctor's office)
community | Community | Includes orders for medications to be administered or consumed by the patient in their home (this would include long term care or nursing homes, hospices, etc)
patientspecified | Patient Specified | Includes statements about medication use, including over the counter medication, provided by the patient, agent or another provider

See the full registry of value sets defined as part of FHIR.

Explanation of the columns that may appear on this page:

Level | A few code lists that FHIR defines are hierarchical - each code is assigned a level. In this scheme, some codes are under other codes, and imply that the code they are under also applies
Source | The source of the definition of the code (when the value set draws in codes defined elsewhere)
Code | The code (used as the code in the resource instance). If the code is in italics, this indicates that the code is not selectable ('Abstract')
Display | The display (used in the display element of a Coding). If there is no display, implementers should not simply display the code, but map the concept into their application
Definition | An explanation of the meaning of the concept
Comments | Additional notes about how to use the code

4.2.12.358 Code System http://hl7.org/fhir/medication-statement-taken

URL: https://hl7.org/fhir/STU3/codesystem-medication-statement-taken.html

This page is part of the FHIR Specification (v3.0.2: STU 3). The current version which supercedes this version is 4.0.1. For a full list of available versions, see the Directory of published versions

Vocabulary Work Group | Maturity Level: 3 | Informative | Use Context: Any

This is a code system defined by the FHIR project.

Summary

Defining URL: | http://hl7.org/fhir/medication-statement-taken
Name: | MedicationStatementTaken
Definition: | A coded concept identifying level of certainty if patient has taken or has not taken the medication
Committee: | Pharmacy Work Group
OID: | 2.16.840.1.113883.4.642.1.358 (for OID based terminology systems)
Source Resource | XML / JSON

This Code system is used in the following value sets:

* MedicationStatementTaken (A coded concept identifying level of certainty if patient has taken or has not taken the medication)

4.2.12.358.1 Content

4.2.12.358.2 MedicationStatementTaken

A coded concept identifying level of certainty if patient has taken or has not taken the medication

This code system http://hl7.org/fhir/medication-statement-taken defines the following codes:

Code | Display | Definition
y | Yes | Positive assertion that patient has taken medication
n | No | Negative assertion that patient has not taken medication
unk | Unknown | Unknown assertion if patient has taken medication
na | Not Applicable | Patient reporting does not apply

See the full registry of value sets defined as part of FHIR.

Explanation of the columns that may appear on this page:

Level | A few code lists that FHIR defines are hierarchical - each code is assigned a level. In this scheme, some codes are under other codes, and imply that the code they are under also applies
Source | The source of the definition of the code (when the value set draws in codes defined elsewhere)
Code | The code (used as the code in the resource instance). If the code is in italics, this indicates that the code is not selectable ('Abstract')
Display | The display (used in the display element of a Coding). If there is no display, implementers should not simply display the code, but map the concept into their application
Definition | An explanation of the meaning of the concept
Comments | Additional notes about how to use the code

4.2.12.362 Code System http://hl7.org/fhir/medication-package-form

URL: https://hl7.org/fhir/STU3/codesystem-medication-package-form.html

This page is part of the FHIR Specification (v3.0.2: STU 3). The current version which supercedes this version is 4.0.1. For a full list of available versions, see the Directory of published versions

Vocabulary Work Group | Maturity Level: 1 | Informative | Use Context: Any

This is a code system defined by the FHIR project.

Summary

Defining URL: | http://hl7.org/fhir/medication-package-form
Name: | MedicationContainer
Definition: | A coded concept defining the kind of container a medication package is packaged in
Committee: | Pharmacy Work Group
OID: | 2.16.840.1.113883.4.642.1.362 (for OID based terminology systems)
Source Resource | XML / JSON

This Code system is used in the following value sets:

* MedicationContainer (A coded concept defining the kind of container a medication package is packaged in)

4.2.12.362.1 Content

4.2.12.362.2 MedicationContainer

A coded concept defining the kind of container a medication package is packaged in

This code system http://hl7.org/fhir/medication-package-form defines the following codes:

Code | Display | Definition
ampoule | Ampoule | A sealed glass capsule containing a liquid
bottle | Bottle | A container, typically made of glass or plastic and with a narrow neck, used for storing liquids.
box | Box | A container with a flat base and sides, typically square or rectangular and having a lid.
cartridge | Cartridge | A device of various configuration and composition used with a syringe for the application of anesthetic or other materials to a patient.
container | Container | A package intended to store pharmaceuticals.
tube | Tube | A long, hollow cylinder of metal, plastic, glass, etc., for holding medications, typically creams or ointments
unitdose | Unit Dose Blister | A dose of medicine prepared in an individual package for convenience, safety or monitoring.
vial | Vial | A small container, typically cylindrical and made of glass, used especially for holding liquid medications.

See the full registry of value sets defined as part of FHIR.

Explanation of the columns that may appear on this page:

Level | A few code lists that FHIR defines are hierarchical - each code is assigned a level. In this scheme, some codes are under other codes, and imply that the code they are under also applies
Source | The source of the definition of the code (when the value set draws in codes defined elsewhere)
Code | The code (used as the code in the resource instance). If the code is in italics, this indicates that the code is not selectable ('Abstract')

Display | The display (used in the display element of a Coding). If there is no display, implementers should not simply display the code, but map the concept into their application
Definition | An explanation of the meaning of the concept
Comments | Additional notes about how to use the code

4.2.12.364 Code System http://hl7.org/fhir/medication-status

URL: https://hl7.org/fhir/STU3/codesystem-medication-status.html

This page is part of the FHIR Specification (v3.0.2: STU 3). The current version which supercedes this version is 4.0.1. For a full list of available versions, see the Directory of published versions

Vocabulary Work Group | Maturity Level: 3 | Informative | Use Context: Any

This is a code system defined by the FHIR project.

Summary

Defining URL: | http://hl7.org/fhir/medication-status
Name: | MedicationStatus
Definition: | A coded concept defining if the medication is in active use
Committee: | Pharmacy Work Group
OID: | 2.16.840.1.113883.4.642.1.364 (for OID based terminology systems)
Source Resource | XML / JSON

This Code system is used in the following value sets:

* MedicationStatus (A coded concept defining if the medication is in active use)

4.2.12.364.1 Content

4.2.12.364.2 MedicationStatus

A coded concept defining if the medication is in active use

This code system http://hl7.org/fhir/medication-status defines the following codes:

Code | Display | Definition
active | Active | The medication is available for use
inactive | Inactive | The medication is not available for use
entered-in-error | Entered in Error | The medication was entered in error

See the full registry of value sets defined as part of FHIR.

Explanation of the columns that may appear on this page:

Level | A few code lists that FHIR defines are hierarchical - each code is assigned a level. In this scheme, some codes are under other codes, and imply that the code they are under also applies
Source | The source of the definition of the code (when the value set draws in codes defined elsewhere)
Code | The code (used as the code in the resource instance). If the code is in italics, this indicates that the code is not selectable ('Abstract')
Display | The display (used in the display element of a Coding). If there is no display, implementers should not simply display the code, but map the concept into their application
Definition | An explanation of the meaning of the concept
Comments | Additional notes about how to use the code

4.2.12.366 Code System http://hl7.org/fhir/message-reasons-encounter

URL: https://hl7.org/fhir/STU3/codesystem-message-reason-encounter.html

This page is part of the FHIR Specification (v3.0.2: STU 3). The current version which supercedes this version is 4.0.1. For a full list of available versions, see the Directory of published versions

Vocabulary Work Group | Maturity Level: 1 | Informative | Use Context: Not Intended for Production use

This is a code system defined by the FHIR project.

Summary

Defining URL: | http://hl7.org/fhir/message-reasons-encounter
Name: | Example Message Reason Codes
Definition: | Example Message Reasons. These are the set of codes that might be used an updating an encounter using admin-update.
Committee: | Infrastructure And Messaging Work Group
OID: | 2.16.840.1.113883.4.642.1.366 (for OID based terminology systems)
Source Resource | XML / JSON

This Code system is used in the following value sets:

* Example Message Reason Codes (Example Message Reasons. These are the set of codes that might be used an updating an encounter using admin-update.)

4.2.12.366.1 Content

4.2.12.366.2 Example Message Reason Codes

Example Message Reasons. These are the set of codes that might be used an updating an encounter using admin-update.

This code system http://hl7.org/fhir/message-reasons-encounter defines the following codes:

Code | Display | Definition
admit | Admit | The patient has been admitted.
discharge | Discharge | The patient has been discharged.
absent | Absent | The patient has temporarily left the institution.
return | Returned | The patient has returned from a temporary absence.
moved | Moved | The patient has been moved to a new location.
edit | Edit | Encounter details have been updated (e.g. to correct a coding error).

See the full registry of value sets defined as part of FHIR.

Explanation of the columns that may appear on this page:

Level | A few code lists that FHIR defines are hierarchical - each code is assigned a level. In this scheme, some codes are under other codes, and imply that the code they are under also applies
Source | The source of the definition of the code (when the value set draws in codes defined elsewhere)
Code | The code (used as the code in the resource instance). If the code is in italics, this indicates that the code is not selectable ('Abstract')
Display | The display (used in the display element of a Coding). If there is no display, implementers should not simply display the code, but map the concept into their application
Definition | An explanation of the meaning of the concept
Comments | Additional notes about how to use the code

4.2.12.368 Code System http://hl7.org/fhir/response-code

URL: https://hl7.org/fhir/STU3/codesystem-response-code.html

This page is part of the FHIR Specification (v3.0.2: STU 3). The current version which supercedes this version is 4.0.1. For a full list of available versions, see the Directory of published versions

Vocabulary Work Group | Maturity Level: 3 | Informative | Use Context: Any

This is a code system defined by the FHIR project.

Summary

Defining URL: | http://hl7.org/fhir/response-code
Name: | ResponseType
Definition: | The kind of response to a message
Committee: | Infrastructure And Messaging Work Group
OID: | 2.16.840.1.113883.4.642.1.368 (for OID based terminology systems)
Source Resource | XML / JSON

This Code system is used in the following value sets:

* ResponseType (The kind of response to a message)

4.2.12.368.1 Content

4.2.12.368.2 ResponseType

The kind of response to a message

This code system http://hl7.org/fhir/response-code defines the following codes:

Code | Display | Definition
ok | OK | The message was accepted and processed without error.
transient-error | Transient Error | Some internal unexpected error occurred - wait and try again. Note - this is usually used for things like database unavailable, which may be expected to resolve, though human intervention may be required.
fatal-error | Fatal Error | The message was rejected because of a problem with the content. There is no point in re-sending without change. The response narrative SHALL describe the issue.

See the full registry of value sets defined as part of FHIR.

Explanation of the columns that may appear on this page:

Level | A few code lists that FHIR defines are hierarchical - each code is assigned a level. In this scheme, some codes are under other codes, and imply that the code they are under also applies
Source | The source of the definition of the code (when the value set draws in codes defined elsewhere)
Code | The code (used as the code in the resource instance). If the code is in italics, this indicates that the code is not selectable ('Abstract')
Display | The display (used in the display element of a Coding). If there is no display, implementers should not simply display the code, but map the concept into their application
Definition | An explanation of the meaning of the concept
Comments | Additional notes about how to use the code

4.2.12.370 Code System http://hl7.org/fhir/nutrition-request-status

URL: https://hl7.org/fhir/STU3/codesystem-nutrition-request-status.html

This page is part of the FHIR Specification (v3.0.2: STU 3). The current version which supercedes this version is 4.0.1. For a full list of available versions, see the Directory of published versions

Vocabulary Work Group | Maturity Level: 2 | Informative | Use Context: Any

This is a code system defined by the FHIR project.

Summary

Defining URL: | http://hl7.org/fhir/nutrition-request-status
Name: | NutritionOrderStatus
Definition: | Codes specifying the state of the request. Describes the lifecycle of the nutrition order.
Committee: | Orders and Observations Work Group
OID: | 2.16.840.1.113883.4.642.1.370 (for OID based terminology systems)
Source Resource | XML / JSON

This Code system is used in the following value sets:

* NutritionOrderStatus (Codes specifying the state of the request. Describes the lifecycle of the nutrition order.)

4.2.12.370.1 Content

4.2.12.370.2 NutritionOrderStatus

Codes specifying the state of the request. Describes the lifecycle of the nutrition order.

This code system http://hl7.org/fhir/nutrition-request-status defines the following codes:

Code | Display | Definition
proposed | Proposed | The request has been proposed.
draft | Draft | The request is in preliminary form prior to being sent.
planned | Planned | The request has been planned.
requested | Requested | The request has been placed.
active | Active | The request is 'actionable', but not all actions that are implied by it have occurred yet.
on-hold | On-Hold | Actions implied by the request have been temporarily halted, but are expected to continue later. May also be called "suspended".
completed | Completed | All actions that are implied by the order have occurred and no continuation is planned (this will rarely be made explicit).
cancelled | Cancelled | The request has been withdrawn and is no longer actionable.
entered-in-error | Entered in Error | The request was entered in error and voided.

See the full registry of value sets defined as part of FHIR.

Explanation of the columns that may appear on this page:

Level | A few code lists that FHIR defines are hierarchical - each code is assigned a level. In this scheme, some codes are under other codes, and imply that the code they are under also applies
Source | The source of the definition of the code (when the value set draws in codes defined elsewhere)
Code | The code (used as the code in the resource instance). If the code is in italics, this indicates that the code is not selectable ('Abstract')
Display | The display (used in the display element of a Coding). If there is no display, implementers should not simply display the code, but map the concept into their application
Definition | An explanation of the meaning of the concept
Comments | Additional notes about how to use the code

4.2.12.380 Code System http://hl7.org/fhir/entformula-additive

URL: https://hl7.org/fhir/STU3/codesystem-entformula-additive.html

This page is part of the FHIR Specification (v3.0.2: STU 3). The current version which supercedes this version is 4.0.1. For a full list of available versions, see the Directory of published versions

Vocabulary Work Group | Maturity Level: 1 | Informative | Use Context: Not Intended for Production use

This is a code system defined by the FHIR project.

Summary

Defining URL: | http://hl7.org/fhir/entformula-additive
Name: | Enteral Formula Additive Type Code
Definition: | EnteralFormulaAdditiveType: Codes for the type of modular component such as protein, carbohydrate or fiber to be provided in addition to or mixed with the base formula. This value set is provided as a suggestive example.
Committee: | Orders and Observations Work Group
OID: | 2.16.840.1.113883.4.642.1.380 (for OID based terminology systems)
Source Resource | XML / JSON

This Code system is used in the following value sets:

* Enteral Formula Additive Type Code (EnteralFormulaAdditiveType: Codes for the type of modular component such as protein, carbohydrate or fiber to be provided in addition to or mixed with the base formula. This value set is provided as a suggestive example.)

4.2.12.380.1 Content

4.2.12.380.2 Enteral Formula Additive Type Code

EnteralFormulaAdditiveType: Codes for the type of modular component such as protein, carbohydrate or fiber to be provided in addition to or mixed with the base formula. This value set is provided as a suggestive example.

This code system http://hl7.org/fhir/entformula-additive defines the following codes:

Code | Display | Definition
lipid | Lipid | Modular lipid enteral formula component
protein | Protein | Modular protein enteral formula component

carbohydrate | Carbohydrate | Modular carbohydrate enteral formula component
fiber | Fiber | Modular fiber enteral formula component
water | Water | Added water

See the full registry of value sets defined as part of FHIR.

Explanation of the columns that may appear on this page:

Level | A few code lists that FHIR defines are hierarchical - each code is assigned a level. In this scheme, some codes are under other codes, and imply that the code they are under also applies
Source | The source of the definition of the code (when the value set draws in codes defined elsewhere)
Code | The code (used as the code in the resource instance). If the code is in italics, this indicates that the code is not selectable ('Abstract')
Display | The display (used in the display element of a Coding). If there is no display, implementers should not simply display the code, but map the concept into their application
Definition | An explanation of the meaning of the concept
Comments | Additional notes about how to use the code

4.2.12.385 Code System http://hl7.org/fhir/referencerange-meaning

URL: https://hl7.org/fhir/STU3/codesystem-referencerange-meaning.html

This page is part of the FHIR Specification (v3.0.2: STU 3). The current version which supercedes this version is 4.0.1. For a full list of available versions, see the Directory of published versions

Vocabulary Work Group | Maturity Level: 5 | Informative | Use Context: Not Intended for Production use

This is a code system defined by the FHIR project.

Summary

Defining URL: | http://hl7.org/fhir/referencerange-meaning
Name: | Observation Reference Range Meaning Codes
Definition: | This value set defines a set of codes that can be used to indicate the meaning/use of a reference range for a particular target population.
Committee: | Orders and Observations Work Group
OID: | 2.16.840.1.113883.4.642.1.385 (for OID based terminology systems)
Source Resource | XML / JSON

This Code system is used in the following value sets:

* Observation Reference Range Meaning Codes (This value set defines a set of codes that can be used to indicate the meaning/use of a reference range for a particular target population.)

4.2.12.385.1 Content

4.2.12.385.2 Observation Reference Range Meaning Codes

This value set defines a set of codes that can be used to indicate the meaning/use of a reference range for a particular target population.

Properties

Code | URL | Description | Type
abstract | | True if an element is considered 'abstract' - that is the code is not for use as a real concept | boolean

This code system http://hl7.org/fhir/referencerange-meaning defines the following codes:

Lvl | Code | Display | Definition
1 | type | Type | General types of reference range.
2 | normal | Normal Range | Based on 95th percentile for the relevant control population.
2 | recommended | Recommended Range | The range that is recommended by a relevant professional body.
2 | treatment | Treatment Range | The range at which treatment would/should be considered.
2 | therapeutic | Therapeutic Desired Level | The optimal range for best therapeutic outcomes.
3 | pre | Pre Therapeutic Desired Level | The optimal range for best therapeutic outcomes for a specimen taken immediately before administration.
3 | post | Post Therapeutic Desired Level | The optimal range for best therapeutic outcomes for a specimen taken immediately after administration.
1 | endocrine | Endocrine | Endocrine related states that change the expected value.
2 | pre-puberty | Pre-Puberty | An expected range in an individual prior to puberty.
2 | follicular | Follicular Stage | An expected range in an individual during the follicular stage of the cycle.
2 | midcycle | MidCycle | An expected range in an individual during the follicular stage of the cycle.
2 | luteal | Luteal | An expected range in an individual during the luteal stage of the cycle.
2 | postmeopausal | Post-Menopause | An expected range in an individual post-menopause.

See the full registry of value sets defined as part of FHIR.

Explanation of the columns that may appear on this page:

Level | A few code lists that FHIR defines are hierarchical - each code is assigned a level. In this scheme, some codes are under other codes, and imply that the code they are under also applies
Source | The source of the definition of the code (when the value set draws in codes defined elsewhere)
Code | The code (used as the code in the resource instance). If the code is in italics, this indicates that the code is not selectable ('Abstract')
Display | The display (used in the display element of a Coding). If there is no display, implementers should not simply display the code, but map the concept into their application
Definition | An explanation of the meaning of the concept
Comments | Additional notes about how to use the code

4.2.12.388 Code System http://hl7.org/fhir/observation-status

URL: https://hl7.org/fhir/STU3/codesystem-observation-status.html

This page is part of the FHIR Specification (v3.0.2: STU 3). The current version which supercedes this version is 4.0.1. For a full list of available versions, see the Directory of published versions

Vocabulary Work Group | Maturity Level: 5 | Informative | Use Context: Any

This is a code system defined by the FHIR project.

Summary

Defining URL: | http://hl7.org/fhir/observation-status
Name: | ObservationStatus
Definition: | Codes providing the status of an observation.
Committee: | Orders and Observations Work Group
OID: | 2.16.840.1.113883.4.642.1.388 (for OID based terminology systems)
Source Resource | XML / JSON

This Code system is used in the following value sets:

* ObservationStatus (Codes providing the status of an observation.)

4.2.12.388.1 Content

4.2.12.388.2 ObservationStatus

Codes providing the status of an observation.

This code system http://hl7.org/fhir/observation-status defines the following codes:

Lvl | Code | Display | Definition
1 | registered | Registered | The existence of the observation is registered, but there is no result yet available.
1 | preliminary | Preliminary | This is an initial or interim observation: data may be incomplete or unverified.
1 | final | Final | The observation is complete.
1 | amended | Amended | Subsequent to being Final, the observation has been modified subsequent. This includes updates/new information and corrections.
2 | corrected | Corrected | Subsequent to being Final, the observation has been modified to correct an error in the test result.
1 | cancelled | Cancelled | The observation is unavailable because the measurement was not started or not completed (also sometimes called "aborted").
1 | entered-in-error | Entered in Error | The observation has been withdrawn following previous final release. This electronic record should never have existed, though it is possible that real-world decisions were based on it. (If real-world activity has occurred, the status should be "cancelled" rather than "entered-in-error".)
1 | unknown | Unknown | The authoring system does not know which of the status values currently applies for this request. Note: This concept is not to be used for "other" - one of the listed statuses is presumed to apply, but the authoring system does not know which.

See the full registry of value sets defined as part of FHIR.

Explanation of the columns that may appear on this page:

Level | A few code lists that FHIR defines are hierarchical - each code is assigned a level. In this scheme, some codes are under other codes, and imply that the code they are under also applies
Source | The source of the definition of the code (when the value set draws in codes defined elsewhere)
Code | The code (used as the code in the resource instance). If the code is in italics, this indicates that the code is not selectable ('Abstract')
Display | The display (used in the display element of a Coding). If there is no display, implementers should not simply display the code, but map the concept into their application
Definition | An explanation of the meaning of the concept
Comments | Additional notes about how to use the code

4.2.12.390 Code System http://hl7.org/fhir/observation-relationshiptypes

URL: https://hl7.org/fhir/STU3/codesystem-observation-relationshiptypes.html

This page is part of the FHIR Specification (v3.0.2: STU 3). The current version which supercedes this version is 4.0.1. For a full list of available versions, see the Directory of published versions

Vocabulary Work Group | Maturity Level: 5 | Informative | Use Context: Any

This is a code system defined by the FHIR project.

Summary

Defining URL: | http://hl7.org/fhir/observation-relationshiptypes
Name: | ObservationRelationshipType
Definition: | Codes specifying how two observations are related.
Committee: | Orders and Observations Work Group
OID: | 2.16.840.1.113883.4.642.1.390 (for OID based terminology systems)
Source Resource | XML / JSON

This Code system is used in the following value sets:

* ObservationRelationshipType (Codes specifying how two observations are related.)

4.2.12.390.1 Content

4.2.12.390.2 ObservationRelationshipType

Codes specifying how two observations are related.

This code system http://hl7.org/fhir/observation-relationshiptypes defines the following codes:

Code | Display | Definition
has-member | Has Member | This observation is a group observation (e.g. a battery, a panel of tests, a set of vital sign measurements) that includes the target as a member of the group.
derived-from | Derived From | The target resource (Observation or QuestionnaireResponse) is part of the information from which this observation value is derived. (e.g. calculated anion gap, Apgar score) NOTE: "derived-from" is the only logical choice when referencing QuestionnaireResponse.
sequel-to | Sequel To | This observation follows the target observation (e.g. timed tests such as Glucose Tolerance Test).
replaces | Replaces | This observation replaces a previous observation (i.e. a revised value). The target observation is now obsolete.
qualified-by | Qualified By | The value of the target observation qualifies (refines) the semantics of the source observation (e.g. a lipemia measure target from a plasma measure).
interfered-by | Interfered By | The value of the target observation interferes (degrades quality, or prevents valid observation) with the semantics of the source observation (e.g. a hemolysis measure target from a plasma potassium measure, which has no value).

See the full registry of value sets defined as part of FHIR.

Explanation of the columns that may appear on this page:

Level | A few code lists that FHIR defines are hierarchical - each code is assigned a level. In this scheme, some codes are under other codes, and imply that the code they are under also applies
Source | The source of the definition of the code (when the value set draws in codes defined elsewhere)
Code | The code (used as the code in the resource instance). If the code is in italics, this indicates that the code is not selectable ('Abstract')
Display | The display (used in the display element of a Coding). If there is no display, implementers should not simply display the code, but map the concept into their application
Definition | An explanation of the meaning of the concept
Comments | Additional notes about how to use the code

4.2.12.393 Code System http://hl7.org/fhir/observation-category

URL: https://hl7.org/fhir/STU3/codesystem-observation-category.html

This page is part of the FHIR Specification (v3.0.2: STU 3). The current version which supercedes this version is 4.0.1. For a full list of available versions, see the Directory of published versions

Vocabulary Work Group | Maturity Level: 5 | Informative | Use Context: Not Intended for Production use

This is a code system defined by the FHIR project.

Summary

Defining URL: | http://hl7.org/fhir/observation-category
Name: | Observation Category Codes
Definition: | Observation Category codes.
Committee: | Orders and Observations Work Group
OID: | 2.16.840.1.113883.4.642.1.393 (for OID based terminology systems)
Source Resource | XML / JSON

This Code system is used in the following value sets:

* Observation Category Codes (Observation Category codes.)

4.2.12.393.1 Content

4.2.12.393.2 Observation Category Codes

Observation Category codes.

This code system http://hl7.org/fhir/observation-category defines the following codes:

Code | Display | Definition
social-history | Social History | The Social History Observations define the patient's occupational, personal (e.g. lifestyle), social, and environmental history and health risk factors, as well as administrative data such as marital status, race, ethnicity and religious affiliation.
vital-signs | Vital Signs | Clinical observations measure the body's basic functions such as such as blood pressure, heart rate, respiratory rate, height, weight, body mass index, head circumference, pulse oximetry, temperature, and body surface area.
imaging | Imaging | Observations generated by imaging. The scope includes observations, plain x-ray, ultrasound, CT, MRI, angiography, echocardiography, nuclear medicine.
laboratory | Laboratory | The results of observations generated by laboratories. Laboratory results are typically generated by laboratories providing analytic services in areas such as chemistry, hematology, serology, histology, cytology, anatomic pathology, microbiology, and/or virology. These observations are based on analysis of specimens obtained from the patient and submitted to the laboratory.
procedure | Procedure | Observations generated by other procedures. This category includes observations resulting from interventional and non-interventional procedures excluding lab and imaging (e.g. cardiology catheterization, endoscopy, electrodiagnostics, etc.). Procedure results are typically generated by a clinician to provide more granular information about component observations made during a procedure, such as where a gastroenterologist reports the size of a polyp observed during a colonoscopy.
survey | Survey | Assessment tool/survey instrument observations (e.g. Apgar Scores, Montreal Cognitive Assessment (MoCA))
exam | Exam | Observations generated by physical exam findings including direct observations made by a clinician and use of simple instruments and the result of simple maneuvers performed directly on the patient's body.
therapy | Therapy | Observations generated by non-interventional treatment protocols (e.g. occupational, physical, radiation, nutritional and medication therapy)

See the full registry of value sets defined as part of FHIR.

Explanation of the columns that may appear on this page:

Level | A few code lists that FHIR defines are hierarchical - each code is assigned a level. In this scheme, some codes are under other codes, and imply that the code they are under also applies
Source | The source of the definition of the code (when the value set draws in codes defined elsewhere)
Code | The code (used as the code in the resource instance). If the code is in italics, this indicates that the code is not selectable ('Abstract')
Display | The display (used in the display element of a Coding). If there is no display, implementers should not simply display the code, but map the concept into their application
Definition | An explanation of the meaning of the concept
Comments | Additional notes about how to use the code

4.2.12.395 Code System http://hl7.org/fhir/observation-statistics

URL: https://hl7.org/fhir/STU3/codesystem-observation-statistics.html

This page is part of the FHIR Specification (v3.0.2: STU 3). The current version which supercedes this version is 4.0.1. For a full list of available versions, see the Directory of published versions

Vocabulary Work Group | Maturity Level: 0 | Informative | Use Context: Any

This is a code system defined by the FHIR project.

Summary

Defining URL: | http://hl7.org/fhir/observation-statistics
Name: | StatisticsCode
Definition: | The statistical operation parameter -"statistic" - codes
Committee: | Orders and Observations Work Group
OID: | 2.16.840.1.113883.4.642.1.395 (for OID based terminology systems)
Source Resource | XML / JSON

This Code system is used in the following value sets:

* StatisticsCode (The statistical operation parameter -"statistic" - codes)

4.2.12.395.1 Content

4.2.12.395.2 StatisticsCode

The statistical operation parameter -"statistic" - codes

This code system http://hl7.org/fhir/observation-statistics defines the following codes:

Code | Display | Definition
average | Average | The [mean](https://en.wikipedia.org/wiki/Arithmetic_mean) of N measurements over the stated period
maximum | Maximum | The [maximum](https://en.wikipedia.org/wiki/Maximal_element) value of N measurements over the stated period
minimum | Minimum | The [minimum](https://en.wikipedia.org/wiki/Minimal_element) value of N measurements over the stated period
count | Count | The [number] of valid measurements over the stated period that contributed to the other statistical outputs
totalcount | Total Count | The total [number] of valid measurements over the stated period, including observations that were ignored because they did not contain valid result values
median | Median | The [median](https://en.wikipedia.org/wiki/Median) of N measurements over the stated period
std-dev | Standard Deviation | The [standard deviation](https://en.wikipedia.org/wiki/Standard_deviation) of N measurements over the stated period
sum | Sum | The [sum](https://en.wikipedia.org/wiki/Summation) of N measurements over the stated period
variance | Variance | The [variance](https://en.wikipedia.org/wiki/Variance) of N measurements over the stated period
20-percent | 20th Percentile | The 20th [Percentile](https://en.wikipedia.org/wiki/Percentile) of N measurements over the stated period
80-percent | 80th Percentile | The 80th [Percentile](https://en.wikipedia.org/wiki/Percentile) of N measurements over the stated period
4-lower | Lower Quartile | The lower [Quartile](https://en.wikipedia.org/wiki/Quartile) Boundary of N measurements over the stated period
4-upper | Upper Quartile | The upper [Quartile](https://en.wikipedia.org/wiki/Quartile) Boundary of N measurements over the stated period
4-dev | Quartile Deviation | The difference between the upper and lower [Quartiles](https://en.wikipedia.org/wiki/Quartile) is called the Interquartile range. (IQR = Q3-Q1) Quartile deviation or Semi-interquartile range is one-half the difference between the first and the third quartiles.
5-1 | 1st Quintile | The lowest of four values that divide the N measurements into a frequency distribution of five classes with each containing one fifth of the total population
5-2 | 2nd Quintile | The second of four values that divide the N measurements into a frequency distribution of five classes with each containing one fifth of the total population
5-3 | 3rd Quintile | The third of four values that divide the N measurements into a frequency distribution of five classes with each containing one fifth of the total population
5-4 | 4th Quintile | The fourth of four values that divide the N measurements into a frequency distribution of five classes with each containing one fifth of the total population
skew | Skew | Skewness is a measure of the asymmetry of the probability distribution of a real-valued random variable about its mean. The skewness value can be positive or negative, or even undefined. Source: [Wikipedia](https://en.wikipedia.org/wiki/Skewness)
kurtosis | Kurtosis | Kurtosis is a measure of the "tailedness" of the probability distribution of a real-valued random variable. Source: [Wikipedia](https://en.wikipedia.org/wiki/Kurtosis)
regression | Regression | Linear regression is an approach for modeling two-dimensional sample points with one independent variable and one dependent variable (conventionally, the x and y coordinates in a Cartesian coordinate system) and finds a linear function (a non-vertical straight line) that, as accurately as possible, predicts the dependent variable values as a function of the independent variables. Source: [Wikipedia](https://en.wikipedia.org/wiki/Simple_linear_regression) This Statistic code will return both a gradient and an intercept value.

See the full registry of value sets defined as part of FHIR.

Explanation of the columns that may appear on this page:

Level | A few code lists that FHIR defines are hierarchical - each code is assigned a level. In this scheme, some codes are under other codes, and imply that the code they are under also applies
Source | The source of the definition of the code (when the value set draws in codes defined elsewhere)
Code | The code (used as the code in the resource instance). If the code is in italics, this indicates that the code is not selectable ('Abstract')
Display | The display (used in the display element of a Coding). If there is no display, implementers should not simply display the code, but map the concept into their application
Definition | An explanation of the meaning of the concept
Comments | Additional notes about how to use the code

4.2.12.398 Code System http://hl7.org/fhir/issue-severity

URL: https://hl7.org/fhir/STU3/codesystem-issue-severity.html

This page is part of the FHIR Specification (v3.0.2: STU 3). The current version which supercedes this version is 4.0.1. For a full list of available versions, see the Directory of published versions

Vocabulary Work Group | Maturity Level: 5 | Informative | Use Context: Any

This is a code system defined by the FHIR project.

Summary

Defining URL: | http://hl7.org/fhir/issue-severity
Name: | IssueSeverity
Definition: | How the issue affects the success of the action.
Committee: | FHIR Infrastructure Work Group
OID: | 2.16.840.1.113883.4.642.1.398 (for OID based terminology systems)
Source Resource | XML / JSON

This Code system is used in the following value sets:

* IssueSeverity (How the issue affects the success of the action.)

4.2.12.398.1 Content

4.2.12.398.2 IssueSeverity

How the issue affects the success of the action.

This code system http://hl7.org/fhir/issue-severity defines the following codes:

Code | Display | Definition
fatal | Fatal | The issue caused the action to fail, and no further checking could be performed.
error | Error | The issue is sufficiently important to cause the action to fail.
warning | Warning | The issue is not important enough to cause the action to fail, but may cause it to be performed suboptimally or in a way that is not as desired.
information | Information | The issue has no relation to the degree of success of the action.

See the full registry of value sets defined as part of FHIR.

Explanation of the columns that may appear on this page:

Level | A few code lists that FHIR defines are hierarchical - each code is assigned a level. In this scheme, some codes are under other codes, and imply that the code they are under also applies
Source | The source of the definition of the code (when the value set draws in codes defined elsewhere)
Code | The code (used as the code in the resource instance). If the code is in italics, this indicates that the code is not selectable ('Abstract')
Display | The display (used in the display element of a Coding). If there is no display, implementers should not simply display the code, but map the concept into their application
Definition | An explanation of the meaning of the concept
Comments | Additional notes about how to use the code

4.2.12.400 Code System http://hl7.org/fhir/issue-type

URL: https://hl7.org/fhir/STU3/codesystem-issue-type.html

This page is part of the FHIR Specification (v3.0.2: STU 3). The current version which supercedes this version is 4.0.1. For a full list of available versions, see the Directory of published versions

Vocabulary Work Group | Maturity Level: 5 | Informative | Use Context: Any

This is a code system defined by the FHIR project.

Summary

Defining URL: | http://hl7.org/fhir/issue-type
Name: | IssueType
Definition: | A code that describes the type of issue.
Committee: | FHIR Infrastructure Work Group
OID: | 2.16.840.1.113883.4.642.1.400 (for OID based terminology systems)
Source Resource | XML / JSON

This Code system is used in the following value sets:

* IssueType (A code that describes the type of issue.)

4.2.12.400.1 Content

4.2.12.400.2 IssueType

A code that describes the type of issue.

This code system http://hl7.org/fhir/issue-type defines the following codes:

Lvl | Code | Display | Definition
1 | invalid | Invalid Content | Content invalid against the specification or a profile.
2 | structure | Structural Issue | A structural issue in the content such as wrong namespace, or unable to parse the content completely, or invalid json syntax.
2 | required | Required element missing | A required element is missing.
2 | value | Element value invalid | An element value is invalid.
2 | invariant | Validation rule failed | A content validation rule failed - e.g. a schematron rule.
1 | security | Security Problem | An authentication/authorization/permissions issue of some kind.
2 | login | Login Required | The client needs to initiate an authentication process.
2 | unknown | Unknown User | The user or system was not able to be authenticated (either there is no process, or the proferred token is unacceptable).
2 | expired | Session Expired | User session expired; a login may be required.
2 | forbidden | Forbidden | The user does not have the rights to perform this action.
2 | suppressed | Information Suppressed | Some information was not or may not have been returned due to business rules, consent or privacy rules, or access permission constraints. This information may be accessible through alternate processes.
1 | processing | Processing Failure | Processing issues. These are expected to be final e.g. there is no point resubmitting the same content unchanged.
2 | not-supported | Content not supported | The resource or profile is not supported.
2 | duplicate | Duplicate | An attempt was made to create a duplicate record.
2 | not-found | Not Found | The reference provided was not found. In a pure RESTful environment, this would be an HTTP 404 error, but this code may be used where the content is not found further into the application architecture.
2 | too-long | Content Too Long | Provided content is too long (typically, this is a denial of service protection type of error).
2 | code-invalid | Invalid Code | The code or system could not be understood, or it was not valid in the context of a particular ValueSet.code.
2 | extension | Unacceptable Extension | An extension was found that was not acceptable, could not be resolved, or a modifierExtension was not recognized.
2 | too-costly | Operation Too Costly | The operation was stopped to protect server resources; e.g. a request for a value set expansion on all of SNOMED CT.
2 | business-rule | Business Rule Violation | The content/operation failed to pass some business rule, and so could not proceed.
2 | conflict | Edit Version Conflict | Content could not be accepted because of an edit conflict (i.e. version aware updates) (In a pure RESTful environment, this would be an HTTP 404 error, but this code may be used where the conflict is discovered further into the application architecture.)
2 | incomplete | Incomplete Results | Not all data sources typically accessed could be reached, or responded in time, so the returned information may not be complete.
1 | transient | Transient Issue | Transient processing issues. The system receiving the error may be able to resubmit the same content once an underlying issue is resolved.
2 | lock-error | Lock Error | A resource/record locking failure (usually in an underlying database).
2 | no-store | No Store Available | The persistent store is unavailable; e.g. the database is down for maintenance or similar action.
2 | exception | Exception | An unexpected internal error has occurred.
2 | timeout | Timeout | An internal timeout has occurred.
2 | throttled | Throttled | The system is not prepared to handle this request due to load management.
1 | informational | Informational Note | A message unrelated to the processing success of the completed operation (examples of the latter include things like reminders of password expiry, system maintenance times, etc.).

See the full registry of value sets defined as part of FHIR.

Explanation of the columns that may appear on this page:

Level | A few code lists that FHIR defines are hierarchical - each code is assigned a level. In this scheme, some codes are under other codes, and imply that the code they are under also applies
Source | The source of the definition of the code (when the value set draws in codes defined elsewhere)
Code | The code (used as the code in the resource instance). If the code is in italics, this indicates that the code is not selectable ('Abstract')
Display | The display (used in the display element of a Coding). If there is no display, implementers should not simply display the code, but map the concept into their application
Definition | An explanation of the meaning of the concept
Comments | Additional notes about how to use the code

4.2.12.402 Code System http://hl7.org/fhir/operation-outcome

URL: https://hl7.org/fhir/STU3/codesystem-operation-outcome.html

This page is part of the FHIR Specification (v3.0.2: STU 3). The current version which supercedes this version is 4.0.1. For a full list of available versions, see the Directory of published versions

Vocabulary Work Group | Maturity Level: 1 | Informative | Use Context: Any

This is a code system defined by the FHIR project.

Summary

Defining URL: | http://hl7.org/fhir/operation-outcome
Name: | Operation Outcome Codes
Definition: | Operation Outcome codes used by FHIR test servers (see Implementation file translations.xml)
Committee: | FHIR Infrastructure Work Group

OID: | 2.16.840.1.113883.4.642.1.402 (for OID based terminology systems)
Source Resource | XML / JSON

This Code system is used in the following value sets:

* Operation Outcome Codes (Operation Outcome codes used by FHIR test servers (see Implementation file translations.xml))

4.2.12.402.1 Content

4.2.12.402.2 Operation Outcome Codes

Operation Outcome codes used by FHIR test servers (see Implementation file translations.xml)

This code system http://hl7.org/fhir/operation-outcome defines the following codes:

Code | Display | Definition
MSG_AUTH_REQUIRED | You must authenticate before you can use this service
MSG_BAD_FORMAT | Bad Syntax: "%s" must be a %s'
MSG_BAD_SYNTAX | Bad Syntax in %s
MSG_CANT_PARSE_CONTENT | Unable to parse feed (entry content type = "%s")
MSG_CANT_PARSE_ROOT | Unable to parse feed (root element name = "%s")
MSG_CREATED | New resource created
MSG_DATE_FORMAT | The Date value %s is not in the correct format (Xml Date Format required)
MSG_DELETED | This resource has been deleted
MSG_DELETED_DONE | Resource deleted
MSG_DELETED_ID | The resource "%s" has been deleted
MSG_DUPLICATE_ID | Duplicate Id %s for resource type %s
MSG_ERROR_PARSING | Error parsing resource Xml (%s)
MSG_ID_INVALID | Id "%s" has an invalid character "%s"
MSG_ID_TOO_LONG | Id "%s" too long (length limit 36)
MSG_INVALID_ID | Id not accepted
MSG_JSON_OBJECT | Json Source for a resource should start with an object
MSG_LOCAL_FAIL | Unable to resolve local reference to resource %s
MSG_NO_MATCH | No Resource found matching the query "%s"
MSG_NO_EXIST | Resource Id "%s" does not exist
MSG_NO_MODULE | No module could be found to handle the request "%s"
MSG_NO_SUMMARY | No Summary for this resource
MSG_OP_NOT_ALLOWED | Operation %s not allowed for resource %s (due to local configuration)
MSG_PARAM_CHAINED | Unknown chained parameter name "%s"
MSG_PARAM_NO_REPEAT | Parameter "%s" is not allowed to repeat
MSG_PARAM_UNKNOWN | Parameter "%s" not understood
MSG_PARAM_INVALID | Parameter "%s" content is invalid
MSG_PARAM_MODIFIER_INVALID | Parameter "%s" modifier is invalid
MSG_RESOURCE_EXAMPLE_PROTECTED | Resources with identity "example" cannot be deleted (for testing/training purposes)
MSG_RESOURCE_ID_FAIL | unable to allocate resource id
MSG_RESOURCE_NOT_ALLOWED | Not allowed to submit a resource for this operation
MSG_RESOURCE_REQUIRED | A resource is required
MSG_RESOURCE_ID_MISMATCH | Resource Id Mismatch
MSG_RESOURCE_ID_MISSING | Resource Id Missing
MSG_RESOURCE_TYPE_MISMATCH | Resource Type Mismatch
MSG_SORT_UNKNOWN | Unknown sort parameter name "%s"
MSG_TRANSACTION_DUPLICATE_ID | Duplicate Identifier in transaction: %s
MSG_TRANSACTION_MISSING_ID | Missing Identifier in transaction - an entry.id must be provided
MSG_UNHANDLED_NODE_TYPE | Unhandled xml node type "%s"
MSG_UNKNOWN_CONTENT | Unknown Content (%s) at %s
MSG_UNKNOWN_OPERATION | unknown FHIR http operation
MSG_UNKNOWN_TYPE | Resource Type "%s" not recognised
MSG_UPDATED | existing resource updated
MSG_VERSION_AWARE | Version aware updates are required for this resource
MSG_VERSION_AWARE_CONFLICT | Update Conflict (server current version = "%s", client version referenced = "%s")
MSG_VERSION_AWARE_URL | Version specific URL not recognised
MSG_WRONG_NS | This does not appear to be a FHIR element or resource (wrong namespace "%s")
SEARCH_MULTIPLE | Error: Multiple matches exist for %s search parameters "%s"
UPDATE_MULTIPLE_MATCHES | Error: Multiple matches exist for the conditional update
DELETE_MULTIPLE_MATCHES | Error: Multiple matches exist for the conditional delete
SEARCH_NONE | Error: no processable search found for %s search parameters "%s"

Additional Language Displays

Code | ee | Spanish (es) | French (fr) | Italian (it) | Nederlands (Dutch, nl) | pl | ??????? (Russian, ru) | ?? (Chinese, zh)
MSG_AUTH_REQUIRED | | Debe autenticarse antes de poder usar este servicio | Vous devez être authentifié avant de pouvoir utiliser ce service | | U moet zich authenticeren voor gebruik van deze service | Wymagana autentykacja przed u?yciem tego serwisu | | ?????????
MSG_BAD_FORMAT | | Sintaxis Incorrecta: "%s" debe de ser un %s' | Erreur de Syntaxe : "%s" doit être un %s | Sintassi Errata: "%s" deve essere un %s' | Verkeerde syntax: "%s" moet een %s zijn | B??d sk?adni: "%s" powinno by? %s' | ???????? ???????: "%s" ?????? ???? %s | ????: "%s" ????? %s'
MSG_BAD_SYNTAX | | Sintaxis Incorrecta en %s | Erreur de Syntaxe dans %s | Sintassi errata in %s | Verkeerde syntax in %s | B??d sk?adni w %s | ???????? ???????: %s | %s ?????

MSG_CANT_PARSE_CONTENT | | No se pudo parsear el feed (el tipo de contenido de la entry = "%s") | Impossible d'analyser le flux (type de contenu de l'entrée = "%s") | Impossibile effettuare il parsing del feed (tipo del contenuto della entry = "%s") | Kan feed niet verwerken (contenttype inhoud = "%s") | B??d parsowania (typ zawarto?ci wej?ciowej = "%s") | | ????feed (??????? = "%s")

MSG_CANT_PARSE_ROOT | No se pudo parsear el feed (nombre del elemento raiz = "%s") | | Impossible d'analyser le flux (nom de l'élément racine = "%s") | Impossibile effettuare il parsing del feed (nome elemento root = "%s") | Kan feed niet verwerken (rootelementnaam = "%s") | B??d parsowania (nazwa elementu root = "%s") | ?? ??????? ????????? ?????? (???????? ??????? = "%s") | ????feed (???? = "%s")

MSG_CREATED | | | | | Nieuwe resource gemaakt

MSG_DATE_FORMAT | | El valor de la fecha %s no está en el formato correcto (se requiere un formato de fecha Xml) | Le format de la date %s est incorrect (format Date Xml attendu) | Il valore %s per la data non ? nel formato corretto (richiesto il Formato Data Xml) | De Datum-waarde %s heeft niet de juiste structuur (Xml Date vereist) | Niepoprawny format warto?ci daty %s (wymagany format XML) | ???????? Date %s ? ???????? ??????? (????????? Xml Date ??????) | ???? %s ????? (???Xml Date??)

MSG_DELETED | | Este recurso ha sido borrado | La ressource a été supprimée | | Deze resource is verwijderd | Ten zasób zosta? usuni?ty | ?????? ?????? ??? ?????? | ??????

MSG_DELETED_DONE | | Recurso borrado | Ressource supprimée | Risorsa cancellata | Resource verwijderd | Zasób usuni?to | ?????? ?????? | ?????

MSG_DELETED_ID | | El recurso "%s" ha sido borrado | La ressource "%s" a été supprimée | La risorsa "%s" ? stata eliminata | De resource "%s" is verwijderd | Zasób "%s" zosta? usuni?ty | ?????? "%s" ??? ?????? | ?? "%s" ????

MSG_DUPLICATE_ID | | Id %s duplicada para el recurso de tipo %s | Id %s en double pour le type de ressource %s | Id %s duplicato per il tipo di risorsa %s | Duplicaat-id %s voor resourcetype %s | Zdublowany identyfikator %s dla zasobu typu %s | ??????????? Id %s ??? ???? ??????? %s | ID %s ??????? %s?

MSG_ERROR_PARSING | | Error parseando el recurso Xml (%s) | Erreur d'analyse de la ressource Xml (%s) | Errore nel parsing della risorsa Xml (%s) | Fout in verwerking resource Xml (%s) | B??d w trakcie parsowania zasobu XML (%s) | ?????? ???????????????? ??????? ??????? Xml (%s) | ????Xml??? (%s)

MSG_ID_INVALID | | El Id "%s" contiene el caracter inválido "%s" | Id "%s" possède un caractère invalide "%s" | L"Id "%s" ha un carattere non valido: "%s" | Id "%s" heeft een ongeldig teken "%s" | Identyfikator "%s" zawiera niepoprawny znak "%s" | Id "%s" ???????? ???????????? ??????? "%s" | ID "%s" ??????: "%s"

MSG_ID_TOO_LONG | | El Id "%s" es demasiado largo (limite de longitud: 36) | Id "%s" trop long (la longueur limite est 36) | Id "%s" troppo lunga (limite di lunghezza: 36) | Id "%s" te lang (max lengte 36) | Identyfikator "%s" jest zbyt d?ugi (limit d?ugo?ci 36) | ???????????? ????? Id "%s" (??????????? 36) | Id "%s" ?? (????: 36)

MSG_INVALID_ID | | Id no aceptada | Id non accepté | Id non accettato | Id niet geaccepteerd | Identyfikator nie zaakceptowany | Id ?? ??????? | Id????

MSG_JSON_OBJECT | | La fuente Json para un recurso debería empezar con un objeto | La source Json pour une ressource doit commencer par un objet | Il sorgente Json di una risorsa dovrebbe iniziare con un oggetto | Json Source van een resource moeten beginnen met een object | ?ród?o json dla zasobu powinno rozpoczyna? si? od obiektu | Json Source ??? ??????? ?????? ?????????? ? ??????? | ???Json?????object??

MSG_LOCAL_FAIL | | Imposible resolver la referencia al recurso %s | Impossible de résourdre la référence locale à la ressource %s | Impossibile risolvere il riferimento locale alla risorsa %s | De resource met lokale referentie %s is niet gevonden | Zasób wskazywany przez loklan? referencj? %s nie zosta? odnaleziony | ?????????? ?????????? ????????? ?????? ?? ?????? %s | ??????? %s ?????

MSG_NO_MATCH | | | | | Geen resource gevonden met query "%s"

MSG_NO_EXIST | | El recurso con Id "%s" no existe | La ressource avec l'Id "%s" n'existe pas | La risorsa con Id "%s" non esiste | Resource-id "%s" bestaat niet | Zasób o identyfikatorze "%s" nie istnieje | ?????? Id "%s" ?? ?????????? | ??Id "%s"???

MSG_NO_MODULE | | No se encontró un modulo que gestione la petición "%s" | Aucun module disponible pour traiter la requête "%s" | Impossibile trovare un modulo per gestire la richiesta "%s" | Er kon geen module worden gevonden om verzoek "%s" te verwerken | Nie mo?na odnale?? modu?u, aby obs?u?y? ??danie "%s" | ?????? ??? ????????? ??????? "%s" ?? ?????? | ????????"%s"???

MSG_NO_SUMMARY | | No existe un resumen para este recurso | Aucun résumé disponible pour cette ressource | Nessun riepilogo per questa risorsa | Geen samenvatting voor deze resource | Brak podsumowania (Summary) dla tego zasobu | ??????????? Summary ??? ??????? ??????? | ????summary

MSG_OP_NOT_ALLOWED | | Operación %s no permitida para el recurso %s (debido a la configuración local) | L'opération %s n'est pas permise pour la ressource %s (à cause de la configuration locale) | Operazione %s non consentita per la risorsa %s (a causa di configurazioni locali) | Bewerking %s niet toegestaan voor resource %s (vanwege lokale configuratie) | Niedozwolona operacja %s dla zasobu %s (ze wzgl?du na lokaln? konfiguracj?) | ???????? %s ??????????? ??? ??????? %s (?? ??????? ????????? ????????????) | ?? %s ???????? %s (??????)

MSG_PARAM_CHAINED | | Nombre de parametro encadenado desconocido: "%s" | Nom du paramètre chainé inconnu : "%s" | Nome di parametro concatenato sconosciuto: "%s" | Onbekende geschakelde parameternaam "%s" | Nieznana nazwa parametru powi?zanego "%s" | ?????????? ????????? ???????????? ????????? "%s" | ????????: "%s"

MSG_PARAM_NO_REPEAT | | No se permite la repetición del parámetro "%s" | Le paramètre "%s" ne peut pas être répété | Non ? consentito ripetere il parametro "%s" | Parameter "%s" mag niet herhalen | Parametr "%s" nie mo?e zosta? powtórzony | ???????? "%s" ?? ????? ???? ???????? | ??"%s"????

MSG_PARAM_UNKNOWN | | Parámetro "%s" no reconocido | Paramètre "%s" non reconnu | Parametro "%s" non riconosciuto | Parameter "%s" onbekend | Niezrozumia?y parametr "%s" | ???????? "%s" ?? ????? | ??????"%s"

MSG_PARAM_INVALID | | | | | Waarde van parameter "%s" is ongeldig

MSG_PARAM_MODIFIER_INVALID | | | | | Modifier van parameter "%s" is ongeldig

MSG_RESOURCE_EXAMPLE_PROTECTED | | Recursos con la identidad "example" no pueden ser borrados (son usados para pruebas/entrenamiento) | Les ressources ayant l'identité "example" ne peuvent pas être supprimées (utilisées pour les tests/formations) | | Resources met identiteit "voorbeeld" kunnen niet worden verwijderd (ten behoeve van testen/training) | Zasoby oznaczone jako "example" nie mog? zosta? usuni?te (dla celów testów/szkole?) | ?????? ? ???????????????? "example" ?? ????? ???? ?????? (??? ??????? ????????????/????????) | ?"example" ?ID???????? (????/??)

MSG_RESOURCE_ID_FAIL | | imposible encontrar el id del recurso | impossible d'allouer l'id de la ressource | impossibile allocare l"id della risorsa | kan geen resource-id reserveren | nie mo?na nada? identyfikatora zasobu | ?????????? ???????? ????????????? ??????? | ??????ID

MSG_RESOURCE_NOT_ALLOWED | | No se permite el envío de un recurso para esta operación | Non autorisé à soumettre une ressource pour cette opération | Non ? consentito sottomettere una risorsa per questa operazione | Niet toegestaan om een resource in te dienen voor deze bewerking | Nie mo?na zg?osi? zasobu dla tej operacji | ??? ?????? ???????? ???????? ??????? ??????????? | ??????????

MSG_RESOURCE_REQUIRED | | Se requiere un recurso | Une ressource est requise | E" richiesta una risorsa | Een resource is verplicht | Zasób jest wymagany | ????????? ?????? | ????????

MSG_RESOURCE_ID_MISMATCH | | | Problème de correspondance d'Id de la Ressource | | Resource ID's komen niet overeen

MSG_RESOURCE_ID_MISSING | | | Id de la Ressource manquante | | Resource ID ontbreekt

MSG_RESOURCE_TYPE_MISMATCH | | Los Tipos de los recursos no coinciden | Type de ressource incorrect | Tipo Risorsa non corrispondente | Verkeerd resourcetype | Niepoprawny typ zasobu | ????????????? ???? ??????? | ???????

MSG_SORT_UNKNOWN | | Nombre del parámetro de ordenación "%s" desconocido | Nom du paramètre de tri inconnu "%s" | Nome del parametro di ordinamento "%s" non riconosciuto | Onbekende parameternaam "%s" voor sortering | Nieznany parametr sortowania "%s" | ??????????? ??? ????????? ?????????? "%s" | ?????????"%s"

MSG_TRANSACTION_DUPLICATE_ID | | Identificador duplicado en la transacción: %s | Identifiant en double dans la transaction : %s | | Dubbele identificatie in transactie: %s | Zdublowany identyfikator w transakcji: %s | ??????????? ????????????? ? ??????????: %s | ???????Id: %s

MSG_TRANSACTION_MISSING_ID | | Identificador de la transacción no encontrado - se debe proporcionar un entry.id | Identifiant manquant dans la transaction - un élément entry.id doit être fourni | | Ontbrekende identificatie in transactie - entry.id is verplicht | Brak identyfikatora w transakcji - nale?y poda? entry.id | ??????????? ????????????? ? ?????????? - ????????? entry.id | ?????Id - ??????entry.id

MSG_UNHANDLED_NODE_TYPE | | Tipo de nodo Xml no soportado "%s" | Type de noeud xml "%s" non traité | Tipo di nodo Xml non gestito "%s" | Kan xml nodetype "%s" niet verwerken | Nieobs?ugiwany typ w?z?a XML "%s" | ?? ???????????? xml ???? "%s" | ????XML????"%s"

MSG_UNKNOWN_CONTENT | | Contenido desconocido (%s) en %s | Contenu inconnu (%s) à %s | Contenuto Sconosciuto (%s) at %s | Onbekende content (%s) at %s | Nieznana zawarto?? (%s) dla %s | ??????????? ??????? (%s) ? %s | ???? (%s) ?? %s

MSG_UNKNOWN_OPERATION | | Operación http FHIR desconocida | operation http FHIR inconnue | operazione http FHIR sconosciuta | onbekende FHIR http operation | nieznana operacja FHIR http | ??????????? ???????? FHIR http | ???FHIR HTTP??

MSG_UNKNOWN_TYPE | | Tipo de Recurso "%s" no reconocido | Type de ressource "%s" non reconnu | Tipo di Risorsa "%s" non riconosciuto | Resourcetype "%s" niet herkend | Nie rozpoznany typ zasobu: "%s" | ??? ??????? "%s" ?? ????????? | ????"%s"???

MSG_UPDATED | | Recurso existente actualizado | ressource existante mise à jour | risorsa esistente aggiornata | bestaande resource updated | uaktualniono istniej?cy zasób | ???????????? ?????? ???????? | ???????

MSG_VERSION_AWARE | | Este recurso requiere actualizaciones en base a versiones | Des mises à jour en relation avec la version sont requises pour cette ressource | Questa risorsa richiede aggiornamenti per versione | Versie-bewuste updates zijn vereist voor deze resource | Uaktualnienia zak?adaj?ce wersjonowanie s? wymagane dla tego zasobu | ??? ??????? ??????? ?????????? ?????????? ? ?????? ?????? | ???????????

MSG_VERSION_AWARE_CONFLICT | | Conflicto de actualizaciones (versión actual del servidor = "%s", versión del cliente referenciada = "%s") | Conflit de mise à jour (version courante du serveur = "%s", version référencée du client = "%s") | Conflitto nell''aggiornamento (attuale = "%s", quotato = "%s") | Updateconflict (huidige serverversie = "%s", opgegeven clientversie = "%s") | Konflikt podczas uaktualnienia (obecna wersja na serwerze = "%s", wersja wskazana przez klienta = "%s") | ???????? ?????????? (??????? ?????? ??????? = "%s", ????????? ?????? ??????? = "%s") | ???? (??????? = "%s", ???????? = "%s")

MSG_VERSION_AWARE_URL | | URL especifica de la versión no reconocida | URL spécifique à une version non reconnue | URL specifico alla versione non riconosciuto | Versie-specifieke URL niet herkend | Nie rozpoznany URL specyficzny dla wersji | URL ??? ????????? ?????? ?? ????????? | ????????URL

MSG_WRONG_NS | | | | Dit lijkt geen FHIR element of resource te zijn (verkeerde namespace "%s")

SEARCH_MULTIPLE | | Error: Multiples ocurrencias existen para %s parametros de búsqueda "%s" | Erreur : Plusieurs correspondances existent pour ce paramètre de recherche %s | Errore: Trovate corrispondenze multiple per %s parametri di ricerca "%s" | Fout: er is meer dan één resultaat voor %s zoekparameters "%s" | B??d: Istniej? wielokrotne dopasowania dla %s parametrów wyszukiwania "%s" | ??????: ????????????? ?????????? ??? %s ? ??????????? ?????? "%s" | ??: ?? %s ????? "%s"??????

UPDATE_MULTIPLE_MATCHES | | | | Fout: er is meer dan één resultaat voor de conditionele update

DELETE_MULTIPLE_MATCHES | | | | Fout: er is meer dan één resultaat voor de conditionele delete

SEARCH_NONE | | Error: no se encontro una búsqueda apropiada para %s parametros de búsqueda "%s" | Erreur : aucune recherche trouvée pour les paramètres %s "%s" | Errore: non ? stato trovato alcun parametro di ricerca processabile per %s parametri di ricerca "%s" | Fout: geen verwerkbare zoekactie gevonden voor %s zoekparameters "%s" | B??d: Niewykonalne wyszukiwanie dla %s parametrów wyszukiwania "%s" | ??????: ?????????????? ??????????? ?????? ??? %s ? ??????????? ?????? "%s" ?? ??????? | ??: ?%s????"%s"?????????

See the full registry of value sets defined as part of FHIR.

Explanation of the columns that may appear on this page:

Level | A few code lists that FHIR defines are hierarchical - each code is assigned a level. In this scheme, some codes are under other codes, and imply that the code they are under also applies

Source | The source of the definition of the code (when the value set draws in codes defined elsewhere)

Code | The code (used as the code in the resource instance). If the code is in italics, this indicates that the code is not selectable ('Abstract')

Display | The display (used in the display element of a Coding). If there is no display, implementers should not simply display the code, but map the concept into their application

Definition | An explanation of the meaning of the concept

Comments | Additional notes about how to use the code

4.2.12.404 Code System http://hl7.org/fhir/organization-type

URL: https://hl7.org/fhir/STU3/codesystem-organization-type.html

This page is part of the FHIR Specification (v3.0.2: STU 3). The current version which supercedes this version is 4.0.1. For a full list of available versions, see the Directory of published versions

Vocabulary Work Group | Maturity Level: 1 | Informative | Use Context: Not Intended for Production use

This is a code system defined by the FHIR project.

Summary

Defining URL: | http://hl7.org/fhir/organization-type

Name: | OrganizationType

Definition: | This example value set defines a set of codes that can be used to indicate a type of organization.

Committee: | Patient Administration Work Group

OID: | 2.16.840.1.113883.4.642.1.404 (for OID based terminology systems)

Source Resource | XML / JSON

This Code system is used in the following value sets:

* OrganizationType (This example value set defines a set of codes that can be used to indicate a type of organization.)

4.2.12.404.1 Content

4.2.12.404.2 OrganizationType

This example value set defines a set of codes that can be used to indicate a type of organization.

This code system http://hl7.org/fhir/organization-type defines the following codes:

Code | Display | Definition
prov | Healthcare Provider | An organization that provides healthcare services.
dept | Hospital Department | A department or ward within a hospital (Generally is not applicable to top level organizations)
team | Organizational team | An organizational team is usually a grouping of practitioners that perform a specific function within an organization (which could be a top level organization, or a department).
govt | Government | A political body, often used when including organization records for government bodies such as a Federal Government, State or Local Government.
ins | Insurance Company | A company that provides insurance to its subscribers that may include healthcare related policies.
edu | Educational Institute | An educational institution that provides education or research facilities.
reli | Religious Institution | An organization that is identified as a part of a religious institution.
crs | Clinical Research Sponsor | An organization that is identified as a Pharmaceutical/Clinical Research Sponsor.
cg | Community Group | An un-incorporated community group.
bus | Non-Healthcare Business or Corporation | An organization that is a registered business or corporation but not identified by other types.
other | Other | Other type of organization not already specified.

See the full registry of value sets defined as part of FHIR.

Explanation of the columns that may appear on this page:

Level | A few code lists that FHIR defines are hierarchical - each code is assigned a level. In this scheme, some codes are under other codes, and imply that the code they are under also applies
Source | The source of the definition of the code (when the value set draws in codes defined elsewhere)
Code | The code (used as the code in the resource instance). If the code is in italics, this indicates that the code is not selectable ('Abstract')
Display | The display (used in the display element of a Coding). If there is no display, implementers should not simply display the code, but map the concept into their application
Definition | An explanation of the meaning of the concept
Comments | Additional notes about how to use the code

4.2.12.406 Code System http://hl7.org/fhir/contactentity-type

URL: https://hl7.org/fhir/STU3/codesystem-contactentity-type.html

This page is part of the FHIR Specification (v3.0.2: STU 3). The current version which supercedes this version is 4.0.1. For a full list of available versions, see the Directory of published versions

Vocabulary Work Group | Maturity Level: 3 | Informative | Use Context: Not Intended for Production use

This is a code system defined by the FHIR project.

Summary

Defining URL: | http://hl7.org/fhir/contactentity-type
Name: | ContactEntityType
Definition: | This example value set defines a set of codes that can be used to indicate the purpose for which you would contact a contact party.
Committee: | Patient Administration Work Group
OID: | 2.16.840.1.113883.4.642.1.406 (for OID based terminology systems)
Source Resource | XML / JSON

This Code system is used in the following value sets:

* ContactEntityType (This example value set defines a set of codes that can be used to indicate the purpose for which you would contact a contact party.)

4.2.12.406.1 Content

4.2.12.406.2 ContactEntityType

This example value set defines a set of codes that can be used to indicate the purpose for which you would contact a contact party.

This code system http://hl7.org/fhir/contactentity-type defines the following codes:

Code | Display | Definition
BILL | Billing | Contact details for information regarding to billing/general finance enquiries.
ADMIN | Administrative | Contact details for administrative enquiries.
HR | Human Resource | Contact details for issues related to Human Resources, such as staff matters, OH&S etc.
PAYOR | Payor | Contact details for dealing with issues related to insurance claims/adjudication/payment.
PATINF | Patient | Generic information contact for patients.
PRESS | Press | Dedicated contact point for matters relating to press enquiries.

See the full registry of value sets defined as part of FHIR.

Explanation of the columns that may appear on this page:

Level | A few code lists that FHIR defines are hierarchical - each code is assigned a level. In this scheme, some codes are under other codes, and imply that the code they are under also applies
Source | The source of the definition of the code (when the value set draws in codes defined elsewhere)
Code | The code (used as the code in the resource instance). If the code is in italics, this indicates that the code is not selectable ('Abstract')
Display | The display (used in the display element of a Coding). If there is no display, implementers should not simply display the code, but map the concept into their application

Definition | An explanation of the meaning of the concept
Comments | Additional notes about how to use the code

4.2.12.408 Code System http://hl7.org/fhir/animal-genderstatus

URL: https://hl7.org/fhir/STU3/codesystem-animal-genderstatus.html

This page is part of the FHIR Specification (v3.0.2: STU 3). The current version which supercedes this version is 4.0.1. For a full list of available versions, see the Directory of published versions

Vocabulary Work Group | Maturity Level: 1 | Informative | Use Context: Not Intended for Production use

This is a code system defined by the FHIR project.

Summary

Defining URL: | http://hl7.org/fhir/animal-genderstatus
Name: | GenderStatus
Definition: | This example value set defines a set of codes that can be used to indicate the current state of the animal's reproductive organs.
Committee: | Patient Administration Work Group
OID: | 2.16.840.1.113883.4.642.1.408 (for OID based terminology systems)
Source Resource | XML / JSON

This Code system is used in the following value sets:

* GenderStatus (This example value set defines a set of codes that can be used to indicate the current state of the animal's reproductive organs.)

4.2.12.408.1 Content

4.2.12.408.2 GenderStatus

This example value set defines a set of codes that can be used to indicate the current state of the animal's reproductive organs.

This code system http://hl7.org/fhir/animal-genderstatus defines the following codes:

Code | Display | Definition
neutered | Neutered | The animal has been sterilized, castrated or otherwise made infertile.
intact | Intact | The animal's reproductive organs are intact.
unknown | Unknown | Unable to determine whether the animal has been neutered.

Additional Language Displays

Code | Nederlands (Dutch, nl)
neutered | gesteriliseerd
intact | intact
unknown | onbekend

See the full registry of value sets defined as part of FHIR.

Explanation of the columns that may appear on this page:

Level | A few code lists that FHIR defines are hierarchical - each code is assigned a level. In this scheme, some codes are under other codes, and imply that the code they are under also applies
Source | The source of the definition of the code (when the value set draws in codes defined elsewhere)
Code | The code (used as the code in the resource instance). If the code is in italics, this indicates that the code is not selectable ('Abstract')
Display | The display (used in the display element of a Coding). If there is no display, implementers should not simply display the code, but map the concept into their application
Definition | An explanation of the meaning of the concept
Comments | Additional notes about how to use the code

4.2.12.410 Code System http://hl7.org/fhir/animal-species

URL: https://hl7.org/fhir/STU3/codesystem-animal-species.html

This page is part of the FHIR Specification (v3.0.2: STU 3). The current version which supercedes this version is 4.0.1. For a full list of available versions, see the Directory of published versions

Vocabulary Work Group | Maturity Level: 1 | Informative | Use Context: Not Intended for Production use

This is a code system defined by the FHIR project.

Summary

Defining URL: | http://hl7.org/fhir/animal-species
Name: | AnimalSpecies
Definition: | This example value set defines a set of codes that can be used to indicate species of animal patients.
Committee: | Patient Administration Work Group
OID: | 2.16.840.1.113883.4.642.1.410 (for OID based terminology systems)
Copyright: | This value set includes content from SNOMED CT, which is copyright © 2002+ International Health Terminology Standards Development Organisation (IHTSDO), and distributed by agreement between IHTSDO and HL7. Implementer use of SNOMED CT is not covered by this agreement.
Source Resource | XML / JSON

This Code system is not currently used

4.2.12.410.1 Content

4.2.12.410.2 AnimalSpecies

This example value set defines a set of codes that can be used to indicate species of animal patients.

Copyright Statement: This value set includes content from SNOMED CT, which is copyright © 2002+ International Health Terminology Standards Development Organisation (IHTSDO), and distributed by agreement between IHTSDO and HL7. Implementer use of SNOMED CT is not covered by this agreement.

This code system http://hl7.org/fhir/animal-species defines the following codes:

Code	Display	Definition
canislf	Dog	Canis lupus familiaris
ovisa	Sheep	Ovis aries
serinuscd	Domestic Canary	Serinus canaria domestica

See the full registry of value sets defined as part of FHIR.

Explanation of the columns that may appear on this page:

Level	A few code lists that FHIR defines are hierarchical - each code is assigned a level. In this scheme, some codes are under other codes, and imply that the code they are under also applies
Source	The source of the definition of the code (when the value set draws in codes defined elsewhere)
Code	The code (used as the code in the resource instance). If the code is in italics, this indicates that the code is not selectable ('Abstract')
Display	The display (used in the display element of a Coding). If there is no display, implementers should not simply display the code, but map the concept into their application
Definition	An explanation of the meaning of the concept
Comments	Additional notes about how to use the code

4.2.12.413 Code System http://hl7.org/fhir/link-type

URL: https://hl7.org/fhir/STU3/codesystem-link-type.html

This page is part of the FHIR Specification (v3.0.2: STU 3). The current version which supercedes this version is 4.0.1. For a full list of available versions, see the Directory of published versions

Vocabulary Work Group | Maturity Level: 5 | Informative | Use Context: Any

This is a code system defined by the FHIR project.

Summary

Defining URL:	http://hl7.org/fhir/link-type
Name:	LinkType
Definition:	The type of link between this patient resource and another patient resource.
Committee:	Patient Administration Work Group
OID:	2.16.840.1.113883.4.642.1.413 (for OID based terminology systems)
Source Resource	XML / JSON

This Code system is used in the following value sets:

* LinkType (The type of link between this patient resource and another patient resource.)

4.2.12.413.1 Content

4.2.12.413.2 LinkType

The type of link between this patient resource and another patient resource.

This code system http://hl7.org/fhir/link-type defines the following codes:

Code	Display	Definition
replaced-by	Replaced-by	The patient resource containing this link must no longer be used. The link points forward to another patient resource that must be used in lieu of the patient resource that contains this link.
replaces	Replaces	The patient resource containing this link is the current active patient record. The link points back to an inactive patient resource that has been merged into this resource, and should be consulted to retrieve additional referenced information.
refer	Refer	The patient resource containing this link is in use and valid but not considered the main source of information about a patient. The link points forward to another patient resource that should be consulted to retrieve additional patient information.
seealso	See also	The patient resource containing this link is in use and valid, but points to another patient resource that is known to contain data about the same person. Data in this resource might overlap or contradict information found in the other patient resource. This link does not indicate any relative importance of the resources concerned, and both should be regarded as equally valid.

Additional Language Displays

Code	Nederlands (Dutch, nl)
replaced-by	vervangen
replaces	
refer	verwijzing
seealso	zie ook

See the full registry of value sets defined as part of FHIR.

Explanation of the columns that may appear on this page:

Level | A few code lists that FHIR defines are hierarchical - each code is assigned a level. In this scheme, some codes are under other codes, and imply that the code they are under also applies
Source | The source of the definition of the code (when the value set draws in codes defined elsewhere)
Code | The code (used as the code in the resource instance). If the code is in italics, this indicates that the code is not selectable ('Abstract')
Display | The display (used in the display element of a Coding). If there is no display, implementers should not simply display the code, but map the concept into their application
Definition | An explanation of the meaning of the concept
Comments | Additional notes about how to use the code

4.2.12.417 Code System http://hl7.org/fhir/device-action

URL: https://hl7.org/fhir/STU3/codesystem-device-action.html

This page is part of the FHIR Specification (v3.0.2: STU 3). The current version which supercedes this version is 4.0.1. For a full list of available versions, see the Directory of published versions

Vocabulary Work Group | Maturity Level: 3 | Informative | Use Context: Not Intended for Production use

This is a code system defined at http://www.hl7.org/Special/committees/patientcare/ .

Summary

Defining URL: | http://hl7.org/fhir/device-action
Name: | Procedure Device Action Codes
Definition: | Example codes indicating the change that happened to the device during the procedure. Note that these are in no way complete and may not even be appropriate for some uses.
Committee: | Patient Care Work Group
OID: | 2.16.840.1.113883.4.642.1.417 (for OID based terminology systems)
Copyright: | This value set includes content from SNOMED CT, which is copyright © 2002+ International Health Terminology Standards Development Organisation (IHTSDO), and distributed by agreement between IHTSDO and HL7. Implementer use of SNOMED CT is not covered by this agreement.
Source Resource | XML / JSON

This Code system is not currently used

4.2.12.417.1 Content

4.2.12.417.2 Procedure Device Action Codes

Example codes indicating the change that happened to the device during the procedure. Note that these are in no way complete and may not even be appropriate for some uses.

Copyright Statement: This value set includes content from SNOMED CT, which is copyright © 2002+ International Health Terminology Standards Development Organisation (IHTSDO), and distributed by agreement between IHTSDO and HL7. Implementer use of SNOMED CT is not covered by this agreement.

This code system http://hl7.org/fhir/device-action defines the following codes:

Code | Display | Definition
implanted | Implanted | The device was implanted in the patient during the procedure.
explanted | Explanted | The device was explanted from the patient during the procedure.
manipulated | Manipulated | The device remains in that patient, but its location, settings, or functionality was changed.

See the full registry of value sets defined as part of FHIR.

Explanation of the columns that may appear on this page:

Level | A few code lists that FHIR defines are hierarchical - each code is assigned a level. In this scheme, some codes are under other codes, and imply that the code they are under also applies
Source | The source of the definition of the code (when the value set draws in codes defined elsewhere)
Code | The code (used as the code in the resource instance). If the code is in italics, this indicates that the code is not selectable ('Abstract')
Display | The display (used in the display element of a Coding). If there is no display, implementers should not simply display the code, but map the concept into their application
Definition | An explanation of the meaning of the concept
Comments | Additional notes about how to use the code

4.2.12.426 Code System http://hl7.org/fhir/dataelement-stringency

URL: https://hl7.org/fhir/STU3/codesystem-dataelement-stringency.html

This page is part of the FHIR Specification (v3.0.2: STU 3). The current version which supercedes this version is 4.0.1. For a full list of available versions, see the Directory of published versions

Vocabulary Work Group | Maturity Level: 1 | Informative | Use Context: Any

This is a code system defined by the FHIR project.

Summary

Defining URL: | http://hl7.org/fhir/dataelement-stringency
Name: | DataElementStringency
Definition: | Indicates the degree of precision of the data element definition.

Committee: | Orders and Observations Work Group
OID: | 2.16.840.1.113883.4.642.1.426 (for OID based terminology systems)
Source Resource | XML / JSON

This Code system is used in the following value sets:

* DataElementStringency (Indicates the degree of precision of the data element definition.)

4.2.12.426.1 Content

4.2.12.426.2 DataElementStringency

Indicates the degree of precision of the data element definition.

This code system http://hl7.org/fhir/dataelement-stringency defines the following codes:

Lvl | Code | Display | Definition
1 | comparable | Comparable | The data element is sufficiently well-constrained that multiple pieces of data captured according to the constraints of the data element will be comparable (though in some cases, a degree of automated conversion/normalization may be required).
2 | fully-specified | Fully Specified | The data element is fully specified down to a single value set, single unit of measure, single data type, etc. Multiple pieces of data associated with this data element are fully comparable.
2 | equivalent | Equivalent | The data element allows multiple units of measure having equivalent meaning; e.g. "cc" (cubic centimeter) and "mL" (milliliter).
2 | convertable | Convertable | The data element allows multiple units of measure that are convertable between each other (e.g. inches and centimeters) and/or allows data to be captured in multiple value sets for which a known mapping exists allowing conversion of meaning.
3 | scaleable | Scaleable | A convertable data element where unit conversions are different only by a power of 10; e.g. g, mg, kg.
1 | flexible | Flexible | The data element is unconstrained in units, choice of data types and/or choice of vocabulary such that automated comparison of data captured using the data element is not possible.

See the full registry of value sets defined as part of FHIR.

Explanation of the columns that may appear on this page:

Level | A few code lists that FHIR defines are hierarchical - each code is assigned a level. In this scheme, some codes are under other codes, and imply that the code they are under also applies
Source | The source of the definition of the code (when the value set draws in codes defined elsewhere)
Code | The code (used as the code in the resource instance). If the code is in italics, this indicates that the code is not selectable ('Abstract')
Display | The display (used in the display element of a Coding). If there is no display, implementers should not simply display the code, but map the concept into their application
Definition | An explanation of the meaning of the concept
Comments | Additional notes about how to use the code

4.2.12.428 Code System http://hl7.org/fhir/provenance-entity-role

URL: https://hl7.org/fhir/STU3/codesystem-provenance-entity-role.html

This page is part of the FHIR Specification (v3.0.2: STU 3). The current version which supercedes this version is 4.0.1. For a full list of available versions, see the Directory of published versions

Vocabulary Work Group | Maturity Level: 3 | Informative | Use Context: Any

This is a code system defined by the FHIR project.

Summary

Defining URL: | http://hl7.org/fhir/provenance-entity-role
Name: | ProvenanceEntityRole
Definition: | How an entity was used in an activity.
Committee: | Security Work Group
OID: | 2.16.840.1.113883.4.642.1.428 (for OID based terminology systems)
Source Resource | XML / JSON

This Code system is used in the following value sets:

* ProvenanceEntityRole (How an entity was used in an activity.)

4.2.12.428.1 Content

4.2.12.428.2 ProvenanceEntityRole

How an entity was used in an activity.

This code system http://hl7.org/fhir/provenance-entity-role defines the following codes:

Lvl | Code | Display | Definition
1 | derivation | Derivation | A transformation of an entity into another, an update of an entity resulting in a new one, or the construction of a new entity based on a preexisting entity.
2 | revision | Revision | A derivation for which the resulting entity is a revised version of some original.
2 | quotation | Quotation | The repeat of (some or all of) an entity, such as text or image, by someone who may or may not be its original author.
2 | source | Source | A primary source for a topic refers to something produced by some agent with direct experience and knowledge about the topic, at the time of the topic's study, without benefit from hindsight.
2 | removal | Removal | A derivation for which the entity is removed from accessibility usually through the use of the Delete operation.

See the full registry of value sets defined as part of FHIR.

Explanation of the columns that may appear on this page:

Level | A few code lists that FHIR defines are hierarchical - each code is assigned a level. In this scheme, some codes are under other codes, and imply that the code they are under also applies
Source | The source of the definition of the code (when the value set draws in codes defined elsewhere)
Code | The code (used as the code in the resource instance). If the code is in italics, this indicates that the code is not selectable ('Abstract')
Display | The display (used in the display element of a Coding). If there is no display, implementers should not simply display the code, but map the concept into their application
Definition | An explanation of the meaning of the concept
Comments | Additional notes about how to use the code

4.2.12.431 Code System http://hl7.org/fhir/practitioner-role

URL: https://hl7.org/fhir/STU3/codesystem-practitioner-role.html

This page is part of the FHIR Specification (v3.0.2: STU 3). The current version which supercedes this version is 4.0.1. For a full list of available versions, see the Directory of published versions

Vocabulary Work Group | Maturity Level: 1 | Informative | Use Context: Not Intended for Production use

This is a code system defined by the FHIR project.

Summary

Defining URL: | http://hl7.org/fhir/practitioner-role
Name: | PractitionerRole
Definition: | This example value set defines a set of codes that can be used to indicate the role of a Practitioner.
Committee: | Patient Administration Work Group
OID: | 2.16.840.1.113883.4.642.1.431 (for OID based terminology systems)
Source Resource | XML / JSON

This Code system is used in the following value sets:

* PractitionerRole (This example value set defines a set of codes that can be used to indicate the role of a Practitioner.)

4.2.12.431.1 Content

4.2.12.431.2 PractitionerRole

This example value set defines a set of codes that can be used to indicate the role of a Practitioner.

This code system http://hl7.org/fhir/practitioner-role defines the following codes:

Code | Display | Definition
doctor | Doctor | A qualified/registered medical practitioner
nurse | Nurse | A practitoner with nursing experience that may be qualified/registered
pharmacist | Pharmacist | A qualified/registered/licensed pharmacist
researcher | Researcher | A practitioner that may perform research
teacher | Teacher/educator | Someone who is able to provide educational services
ict | ICT professional | Someone who is qualified in Information and Communication Technologies

See the full registry of value sets defined as part of FHIR.

Explanation of the columns that may appear on this page:

Level | A few code lists that FHIR defines are hierarchical - each code is assigned a level. In this scheme, some codes are under other codes, and imply that the code they are under also applies
Source | The source of the definition of the code (when the value set draws in codes defined elsewhere)
Code | The code (used as the code in the resource instance). If the code is in italics, this indicates that the code is not selectable ('Abstract')
Display | The display (used in the display element of a Coding). If there is no display, implementers should not simply display the code, but map the concept into their application
Definition | An explanation of the meaning of the concept
Comments | Additional notes about how to use the code

4.2.12.433 Code System http://hl7.org/fhir/practitioner-specialty

URL: https://hl7.org/fhir/STU3/codesystem-practitioner-specialty.html

This page is part of the FHIR Specification (v3.0.2: STU 3). The current version which supercedes this version is 4.0.1. For a full list of available versions, see the Directory of published versions

Vocabulary Work Group | Maturity Level: 1 | Informative | Use Context: Not Intended for Production use

This is a code system defined by the FHIR project.

Summary

Defining URL: | http://hl7.org/fhir/practitioner-specialty
Name: | PractitionerSpecialty
Definition: | This example value set defines a set of codes that can be used to indicate the specialty of a Practitioner.
Committee: | Patient Administration Work Group
OID: | 2.16.840.1.113883.4.642.1.433 (for OID based terminology systems)
Source Resource | XML / JSON

This Code system is used in the following value sets:

* PractitionerSpecialty (This example value set defines a set of codes that can be used to indicate the specialty of a Practitioner.)

4.2.12.433.1 Content

4.2.12.433.2 PractitionerSpecialty

This example value set defines a set of codes that can be used to indicate the specialty of a Practitioner.

This code system http://hl7.org/fhir/practitioner-specialty defines the following codes:

Code | Display | Definition
cardio | Cardiologist
dent | Dentist
dietary | Dietary consultant
midw | Midwife
sysarch | Systems architect

See the full registry of value sets defined as part of FHIR.

Explanation of the columns that may appear on this page:

Level | A few code lists that FHIR defines are hierarchical - each code is assigned a level. In this scheme, some codes are under other codes, and imply that the code they are under also applies
Source | The source of the definition of the code (when the value set draws in codes defined elsewhere)
Code | The code (used as the code in the resource instance). If the code is in italics, this indicates that the code is not selectable ('Abstract')
Display | The display (used in the display element of a Coding). If there is no display, implementers should not simply display the code, but map the concept into their application
Definition | An explanation of the meaning of the concept
Comments | Additional notes about how to use the code

4.2.12.438 Code System http://hl7.org/fhir/item-type

URL: https://hl7.org/fhir/STU3/codesystem-item-type.html

This page is part of the FHIR Specification (v3.0.2: STU 3). The current version which supercedes this version is 4.0.1. For a full list of available versions, see the Directory of published versions

Vocabulary Work Group | Maturity Level: 3 | Informative | Use Context: Any

This is a code system defined by the FHIR project.

Summary

Defining URL: | http://hl7.org/fhir/item-type
Name: | QuestionnaireItemType
Definition: | Distinguishes groups from questions and display text and indicates data type for questions
Committee: | FHIR Infrastructure Work Group
OID: | 2.16.840.1.113883.4.642.1.438 (for OID based terminology systems)
Source Resource | XML / JSON

This Code system is used in the following value sets:

* QuestionnaireItemType (Distinguishes groups from questions and display text and indicates data type for questions)

4.2.12.438.1 Content

4.2.12.438.2 QuestionnaireItemType

Distinguishes groups from questions and display text and indicates data type for questions

Properties

Code | URL | Description | Type
notSelectable | http://hl7.org/fhir/concept-properties#notSelectable | Indicates that the code is abstract - only intended to be used as a selector for other concepts | boolean

This code system http://hl7.org/fhir/item-type defines the following codes:

Lvl | Code | Display | Definition
1 | group | Group | An item with no direct answer but should have at least one child item.
1 | display | Display | Text for display that will not capture an answer or have child items.
1 | question | Question | An item that defines a specific answer to be captured, and may have child items. (the answer provided in the QuestionnaireResponse should be of the defined datatype)
2 | boolean | Boolean | Question with a yes/no answer (valueBoolean)
2 | decimal | Decimal | Question with is a real number answer (valueDecimal)
2 | integer | Integer | Question with an integer answer (valueInteger)
2 | date | Date | Question with a date answer (valueDate)
2 | dateTime | Date Time | Question with a date and time answer (valueDateTime)
2 | time | Time | Question with a time (hour:minute:second) answer independent of date. (valueTime)
2 | string | String | Question with a short (few words to short sentence) free-text entry answer (valueString)
2 | text | Text | Question with a long (potentially multi-paragraph) free-text entry answer (valueString)
2 | url | Url | Question with a URL (website, FTP site, etc.) answer (valueUri)

2 | choice | Choice | Question with a Coding drawn from a list of options (specified in either the option property, or via the valueset referenced in the options property) as an answer (valueCoding)

2 | open-choice | Open Choice | Answer is a Coding drawn from a list of options (as with the choice type) or a free-text entry in a string (valueCoding or valueString)

2 | attachment | Attachment | Question with binary content such as a image, PDF, etc. as an answer (valueAttachment)

2 | reference | Reference | Question with a reference to another resource (practitioner, organization, etc.) as an answer (valueReference)

2 | quantity | Quantity | Question with a combination of a numeric value and unit, potentially with a comparator (<, >, etc.) as an answer. (valueQuantity) There is an extension 'http://hl7.org/fhir/StructureDefinition/questionnaire-unit' that can be used to define what unit whould be captured (or the a unit that has a ucum conversion from the provided unit)

See the full registry of value sets defined as part of FHIR.

Explanation of the columns that may appear on this page:

Level | A few code lists that FHIR defines are hierarchical - each code is assigned a level. In this scheme, some codes are under other codes, and imply that the code they are under also applies

Source | The source of the definition of the code (when the value set draws in codes defined elsewhere)

Code | The code (used as the code in the resource instance). If the code is in italics, this indicates that the code is not selectable ('Abstract')

Display | The display (used in the display element of a Coding). If there is no display, implementers should not simply display the code, but map the concept into their application

Definition | An explanation of the meaning of the concept

Comments | Additional notes about how to use the code

4.2.12.441 Code System http://hl7.org/fhir/questionnaire-answers-status

URL: https://hl7.org/fhir/STU3/codesystem-questionnaire-answers-status.html

This page is part of the FHIR Specification (v3.0.2: STU 3). The current version which supercedes this version is 4.0.1. For a full list of available versions, see the Directory of published versions

Vocabulary Work Group | Maturity Level: 3 | Informative | Use Context: Any

This is a code system defined by the FHIR project.

Summary

Defining URL: | http://hl7.org/fhir/questionnaire-answers-status

Name: | QuestionnaireResponseStatus

Definition: | Lifecycle status of the questionnaire response.

Committee: | FHIR Infrastructure Work Group

OID: | 2.16.840.1.113883.4.642.1.441 (for OID based terminology systems)

Source Resource | XML / JSON

This Code system is used in the following value sets:

* QuestionnaireResponseStatus (Lifecycle status of the questionnaire response.)

4.2.12.441.1 Content

4.2.12.441.2 QuestionnaireResponseStatus

Lifecycle status of the questionnaire response.

This code system http://hl7.org/fhir/questionnaire-answers-status defines the following codes:

Code | Display | Definition

in-progress | In Progress | This QuestionnaireResponse has been partially filled out with answers, but changes or additions are still expected to be made to it.

completed | Completed | This QuestionnaireResponse has been filled out with answers, and the current content is regarded as definitive.

amended | Amended | This QuestionnaireResponse has been filled out with answers, then marked as complete, yet changes or additions have been made to it afterwards.

entered-in-error | Entered in Error | This QuestionnaireResponse was entered in error and voided.

stopped | Stopped | This QuestionnaireResponse has been partially filled out with answers, but has been abandoned. It is unknown whether changes or additions are expected to be made to it.

See the full registry of value sets defined as part of FHIR.

Explanation of the columns that may appear on this page:

Level | A few code lists that FHIR defines are hierarchical - each code is assigned a level. In this scheme, some codes are under other codes, and imply that the code they are under also applies

Source | The source of the definition of the code (when the value set draws in codes defined elsewhere)

Code | The code (used as the code in the resource instance). If the code is in italics, this indicates that the code is not selectable ('Abstract')

Display | The display (used in the display element of a Coding). If there is no display, implementers should not simply display the code, but map the concept into their application

Definition | An explanation of the meaning of the concept

Comments | Additional notes about how to use the code

4.2.12.444 Code System http://hl7.org/fhir/risk-probability

URL: https://hl7.org/fhir/STU3/codesystem-risk-probability.html

This page is part of the FHIR Specification (v3.0.2: STU 3). The current version which supercedes this version is 4.0.1. For a full list of available versions, see the Directory of published versions

Vocabulary Work Group | Maturity Level: 1 | Informative | Use Context: Not Intended for Production use

This is a code system defined by the FHIR project.

Summary

Defining URL: | http://hl7.org/fhir/risk-probability
Name: | Risk Probability
Definition: | Codes representing the likelihood of a particular outcome in a risk assessment.
Committee: | Clinical Decision Support Work Group
OID: | 2.16.840.1.113883.4.642.1.444 (for OID based terminology systems)
Source Resource | XML / JSON

This Code system is used in the following value sets:

* Risk Probability (Codes representing the likelihood of a particular outcome in a risk assessment.)

4.2.12.444.1 Content

4.2.12.444.2 Risk Probability

Codes representing the likelihood of a particular outcome in a risk assessment.

This code system http://hl7.org/fhir/risk-probability defines the following codes:

Code | Display | Definition
negligible | Negligible likelihood | The specified outcome is exceptionally unlikely.
low | Low likelihood | The specified outcome is possible but unlikely.
moderate | Moderate likelihood | The specified outcome has a reasonable likelihood of occurrence.
high | High likelihood | The specified outcome is more likely to occur than not.
certain | Certain | The specified outcome is effectively guaranteed.

See the full registry of value sets defined as part of FHIR.

Explanation of the columns that may appear on this page:

Level | A few code lists that FHIR defines are hierarchical - each code is assigned a level. In this scheme, some codes are under other codes, and imply that the code they are under also applies
Source | The source of the definition of the code (when the value set draws in codes defined elsewhere)
Code | The code (used as the code in the resource instance). If the code is in italics, this indicates that the code is not selectable ('Abstract')
Display | The display (used in the display element of a Coding). If there is no display, implementers should not simply display the code, but map the concept into their application
Definition | An explanation of the meaning of the concept
Comments | Additional notes about how to use the code

4.2.12.446 Code System http://hl7.org/fhir/audit-event-action

URL: https://hl7.org/fhir/STU3/codesystem-audit-event-action.html

This page is part of the FHIR Specification (v3.0.2: STU 3). The current version which supercedes this version is 4.0.1. For a full list of available versions, see the Directory of published versions

Vocabulary Work Group | Maturity Level: 3 | Informative | Use Context: Any

This is a code system defined by the FHIR project.

Summary

Defining URL: | http://hl7.org/fhir/audit-event-action
Name: | AuditEventAction
Definition: | Indicator for type of action performed during the event that generated the event
Committee: | Security Work Group
OID: | 2.16.840.1.113883.4.642.1.446 (for OID based terminology systems)
Source Resource | XML / JSON

This Code system is used in the following value sets:

* AuditEventAction (Indicator for type of action performed during the event that generated the event)

4.2.12.446.1 Content

4.2.12.446.2 AuditEventAction

Indicator for type of action performed during the event that generated the event

This code system http://hl7.org/fhir/audit-event-action defines the following codes:

Code | Display | Definition
C | Create | Create a new database object, such as placing an order.
R | Read/View/Print | Display or print data, such as a doctor census.
U | Update | Update data, such as revise patient information.
D | Delete | Delete items, such as a doctor master file record.

E | Execute | Perform a system or application function such as log-on, program execution or use of an object's method, or perform a query/search operation.

See the full registry of value sets defined as part of FHIR.

Explanation of the columns that may appear on this page:

Level | A few code lists that FHIR defines are hierarchical - each code is assigned a level. In this scheme, some codes are under other codes, and imply that the code they are under also applies
Source | The source of the definition of the code (when the value set draws in codes defined elsewhere)
Code | The code (used as the code in the resource instance). If the code is in italics, this indicates that the code is not selectable ('Abstract')
Display | The display (used in the display element of a Coding). If there is no display, implementers should not simply display the code, but map the concept into their application
Definition | An explanation of the meaning of the concept
Comments | Additional notes about how to use the code

4.2.12.448 Code System http://hl7.org/fhir/audit-event-outcome

URL: https://hl7.org/fhir/STU3/codesystem-audit-event-outcome.html

This page is part of the FHIR Specification (v3.0.2: STU 3). The current version which supercedes this version is 4.0.1. For a full list of available versions, see the Directory of published versions

Vocabulary Work Group | Maturity Level: 3 | Informative | Use Context: Any

This is a code system defined by the FHIR project.

Summary

Defining URL: | http://hl7.org/fhir/audit-event-outcome
Name: | AuditEventOutcome
Definition: | Indicates whether the event succeeded or failed
Committee: | Security Work Group
OID: | 2.16.840.1.113883.4.642.1.448 (for OID based terminology systems)
Source Resource | XML / JSON

This Code system is used in the following value sets:

* AuditEventOutcome (Indicates whether the event succeeded or failed)

4.2.12.448.1 Content

4.2.12.448.2 AuditEventOutcome

Indicates whether the event succeeded or failed

This code system http://hl7.org/fhir/audit-event-outcome defines the following codes:

Code | Display | Definition
0 | Success | The operation completed successfully (whether with warnings or not).
4 | Minor failure | The action was not successful due to some kind of catered for error (often equivalent to an HTTP 400 response).
8 | Serious failure | The action was not successful due to some kind of unexpected error (often equivalent to an HTTP 500 response).
12 | Major failure | An error of such magnitude occurred that the system is no longer available for use (i.e. the system died).

See the full registry of value sets defined as part of FHIR.

Explanation of the columns that may appear on this page:

Level | A few code lists that FHIR defines are hierarchical - each code is assigned a level. In this scheme, some codes are under other codes, and imply that the code they are under also applies
Source | The source of the definition of the code (when the value set draws in codes defined elsewhere)
Code | The code (used as the code in the resource instance). If the code is in italics, this indicates that the code is not selectable ('Abstract')
Display | The display (used in the display element of a Coding). If there is no display, implementers should not simply display the code, but map the concept into their application
Definition | An explanation of the meaning of the concept
Comments | Additional notes about how to use the code

4.2.12.450 Code System http://hl7.org/fhir/network-type

URL: https://hl7.org/fhir/STU3/codesystem-network-type.html

This page is part of the FHIR Specification (v3.0.2: STU 3). The current version which supercedes this version is 4.0.1. For a full list of available versions, see the Directory of published versions

Vocabulary Work Group | Maturity Level: 3 | Informative | Use Context: Any

This is a code system defined by the FHIR project.

Summary

Defining URL: | http://hl7.org/fhir/network-type
Name: | AuditEventAgentNetworkType
Definition: | The type of network access point of this agent in the audit event
Committee: | Security Work Group
OID: | 2.16.840.1.113883.4.642.1.450 (for OID based terminology systems)
Source Resource | XML / JSON

This Code system is used in the following value sets:

* AuditEventAgentNetworkType (The type of network access point of this agent in the audit event)

4.2.12.450.1 Content

4.2.12.450.2 AuditEventAgentNetworkType

The type of network access point of this agent in the audit event

This code system http://hl7.org/fhir/network-type defines the following codes:

Code | Display | Definition
1 | Machine Name | The machine name, including DNS name.
2 | IP Address | The assigned Internet Protocol (IP) address.
3 | Telephone Number | The assigned telephone number.
4 | Email address | The assigned email address.
5 | URI | URI (User directory, HTTP-PUT, ftp, etc.).

See the full registry of value sets defined as part of FHIR.

Explanation of the columns that may appear on this page:

Level | A few code lists that FHIR defines are hierarchical - each code is assigned a level. In this scheme, some codes are under other codes, and imply that the code they are under also applies
Source | The source of the definition of the code (when the value set draws in codes defined elsewhere)
Code | The code (used as the code in the resource instance). If the code is in italics, this indicates that the code is not selectable ('Abstract')
Display | The display (used in the display element of a Coding). If there is no display, implementers should not simply display the code, but map the concept into their application
Definition | An explanation of the meaning of the concept
Comments | Additional notes about how to use the code

4.2.12.454 Code System http://hl7.org/fhir/object-role

URL: https://hl7.org/fhir/STU3/codesystem-object-role.html

This page is part of the FHIR Specification (v3.0.2: STU 3). The current version which supercedes this version is 4.0.1. For a full list of available versions, see the Directory of published versions

Vocabulary Work Group | Maturity Level: 3 | Informative | Use Context: Any

This is a code system defined by the FHIR project.

Summary

Defining URL: | http://hl7.org/fhir/object-role
Name: | AuditEventEntityRole
Definition: | Code representing the role the entity played in the audit event
Committee: | Security Work Group
OID: | 2.16.840.1.113883.4.642.1.454 (for OID based terminology systems)
Source Resource | XML / JSON

This Code system is used in the following value sets:

* AuditEventEntityRole (Code representing the role the entity played in the audit event)

4.2.12.454.1 Content

4.2.12.454.2 AuditEventEntityRole

Code representing the role the entity played in the audit event

This code system http://hl7.org/fhir/object-role defines the following codes:

Code | Display | Definition
1 | Patient | This object is the patient that is the subject of care related to this event. It is identifiable by patient ID or equivalent. The patient may be either human or animal.
2 | Location | This is a location identified as related to the event. This is usually the location where the event took place. Note that for shipping, the usual events are arrival at a location or departure from a location.
3 | Report | This object is any kind of persistent document created as a result of the event. This could be a paper report, film, electronic report, DICOM Study, etc. Issues related to medical records life cycle management are conveyed elsewhere.
4 | Domain Resource | A logical object related to a health record event. This is any healthcare specific resource (object) not restricted to FHIR defined Resources.
5 | Master file | This is any configurable file used to control creation of documents. Examples include the objects maintained by the HL7 Master File transactions, Value Sets, etc.
6 | User | A human participant not otherwise identified by some other category.
7 | List | (deprecated)
8 | Doctor | Typically a licensed person who is providing or performing care related to the event, generally a physician. The key distinction between doctor and practitioner is with regards to their role, not the licensing. The doctor is the human who actually performed the work. The practitioner is the human or organization that is responsible for the work.
9 | Subscriber | A person or system that is being notified as part of the event. This is relevant in situations where automated systems provide notifications to other parties when an event took place.
10 | Guarantor | Insurance company, or any other organization who accepts responsibility for paying for the healthcare event.

11 | Security User Entity | A person or active system object involved in the event with a security role.
12 | Security User Group | A person or system object involved in the event with the authority to modify security roles of other objects.
13 | Security Resource | A passive object, such as a role table, that is relevant to the event.
14 | Security Granularity Definition | (deprecated) Relevant to certain RBAC security methodologies.
15 | Practitioner | Any person or organization responsible for providing care. This encompasses all forms of care, licensed or otherwise, and all sorts of teams and care groups. Note the distinction between practitioner and the doctor that actually provided the care to the patient.
16 | Data Destination | The source or destination for data transfer, when it does not match some other role.
17 | Data Repository | A source or destination for data transfer that acts as an archive, database, or similar role.
18 | Schedule | An object that holds schedule information. This could be an appointment book, availability information, etc.
19 | Customer | An organization or person that is the recipient of services. This could be an organization that is buying services for a patient, or a person that is buying services for an animal.
20 | Job | An order, task, work item, procedure step, or other description of work to be performed; e.g. a particular instance of an MPPS.
21 | Job Stream | A list of jobs or a system that provides lists of jobs; e.g. an MWL SCP.
22 | Table | (Deprecated)
23 | Routing Criteria | An object that specifies or controls the routing or delivery of items. For example, a distribution list is the routing criteria for mail. The items delivered may be documents, jobs, or other objects.
24 | Query | The contents of a query. This is used to capture the contents of any kind of query. For security surveillance purposes knowing the queries being made is very important.

See the full registry of value sets defined as part of FHIR.

Explanation of the columns that may appear on this page:

Level | A few code lists that FHIR defines are hierarchical - each code is assigned a level. In this scheme, some codes are under other codes, and imply that the code they are under also applies
Source | The source of the definition of the code (when the value set draws in codes defined elsewhere)
Code | The code (used as the code in the resource instance). If the code is in italics, this indicates that the code is not selectable ('Abstract')
Display | The display (used in the display element of a Coding). If there is no display, implementers should not simply display the code, but map the concept into their application
Definition | An explanation of the meaning of the concept
Comments | Additional notes about how to use the code

4.2.12.456 Code System http://hl7.org/fhir/audit-event-type

URL: https://hl7.org/fhir/STU3/codesystem-audit-event-type.html

This page is part of the FHIR Specification (v3.0.2: STU 3). The current version which supercedes this version is 4.0.1. For a full list of available versions, see the Directory of published versions

Vocabulary Work Group | Maturity Level: 3 | Informative | Use Context: Not Intended for Production use

This is a code system defined by the FHIR project.

Summary

Defining URL: | http://hl7.org/fhir/audit-event-type
Name: | Audit Event ID
Definition: | Event Types for Audit Events - defined by DICOM with some FHIR specific additions.
Committee: | Security Work Group
OID: | 2.16.840.1.113883.4.642.1.456 (for OID based terminology systems)
Copyright: | These codes are excerpted from Digital Imaging and Communications in Medicine (DICOM) Standard, Part 16: Content Mapping Resource, Copyright © 2011 by the National Electrical Manufacturers Association.
Source Resource | XML / JSON

This Code system is used in the following value sets:

* Audit Event ID (Event Types for Audit Events - defined by DICOM with some FHIR specific additions.)

4.2.12.456.1 Content

4.2.12.456.2 Audit Event ID

Event Types for Audit Events - defined by DICOM with some FHIR specific additions.

Copyright Statement: These codes are excerpted from Digital Imaging and Communications in Medicine (DICOM) Standard, Part 16: Content Mapping Resource, Copyright © 2011 by the National Electrical Manufacturers Association.

This code system http://hl7.org/fhir/audit-event-type defines the following codes:

Code | Display | Definition
rest | RESTful Operation | Audit Event: Execution of a RESTful operation as defined by FHIR.

See the full registry of value sets defined as part of FHIR.

Explanation of the columns that may appear on this page:

Level | A few code lists that FHIR defines are hierarchical - each code is assigned a level. In this scheme, some codes are under other codes, and imply that the code they are under also applies
Source | The source of the definition of the code (when the value set draws in codes defined elsewhere)
Code | The code (used as the code in the resource instance). If the code is in italics, this indicates that the code is not selectable ('Abstract')
Display | The display (used in the display element of a Coding). If there is no display, implementers should not simply display the code, but map the concept into their application
Definition | An explanation of the meaning of the concept

Comments | Additional notes about how to use the code

4.2.12.460 Code System http://hl7.org/fhir/security-source-type

URL: https://hl7.org/fhir/STU3/codesystem-audit-source-type.html

This page is part of the FHIR Specification (v3.0.2: STU 3). The current version which supercedes this version is 4.0.1. For a full list of available versions, see the Directory of published versions

Vocabulary Work Group | Maturity Level: 3 | Informative | Use Context: Not Intended for Production use

This is a code system defined by the FHIR project.

Summary

Defining URL: | http://hl7.org/fhir/security-source-type
Name: | Audit Event Source Type
Definition: | The type of process where the audit event originated from.
Committee: | Security Work Group
OID: | 2.16.840.1.113883.4.642.1.460 (for OID based terminology systems)
Source Resource | XML / JSON

This Code system is used in the following value sets:

* Audit Event Source Type (The type of process where the audit event originated from.)

4.2.12.460.1 Content

4.2.12.460.2 Audit Event Source Type

The type of process where the audit event originated from.

This code system http://hl7.org/fhir/security-source-type defines the following codes:

Code | Display | Definition
1 | User Device | End-user display device, diagnostic device.
2 | Data Interface | Data acquisition device or instrument.
3 | Web Server | Web Server process or thread.
4 | Application Server | Application Server process or thread.
5 | Database Server | Database Server process or thread.
6 | Security Server | Security server, e.g. a domain controller.
7 | Network Device | ISO level 1-3 network component.
8 | Network Router | ISO level 4-6 operating software.
9 | Other | other kind of device (defined by DICOM, but some other code/system can be used).

See the full registry of value sets defined as part of FHIR.

Explanation of the columns that may appear on this page:

Level | A few code lists that FHIR defines are hierarchical - each code is assigned a level. In this scheme, some codes are under other codes, and imply that the code they are under also applies
Source | The source of the definition of the code (when the value set draws in codes defined elsewhere)
Code | The code (used as the code in the resource instance). If the code is in italics, this indicates that the code is not selectable ('Abstract')
Display | The display (used in the display element of a Coding). If there is no display, implementers should not simply display the code, but map the concept into their application
Definition | An explanation of the meaning of the concept
Comments | Additional notes about how to use the code

4.2.12.465 Code System http://hl7.org/fhir/specimen-status

URL: https://hl7.org/fhir/STU3/codesystem-specimen-status.html

This page is part of the FHIR Specification (v3.0.2: STU 3). The current version which supercedes this version is 4.0.1. For a full list of available versions, see the Directory of published versions

Vocabulary Work Group | Maturity Level: 2 | Informative | Use Context: Any

This is a code system defined by the FHIR project.

Summary

Defining URL: | http://hl7.org/fhir/specimen-status
Name: | SpecimenStatus
Definition: | Codes providing the status/availability of a specimen.
Committee: | Orders and Observations Work Group
OID: | 2.16.840.1.113883.4.642.1.465 (for OID based terminology systems)
Source Resource | XML / JSON

This Code system is used in the following value sets:

* SpecimenStatus (Codes providing the status/availability of a specimen.)

4.2.12.465.1 Content

4.2.12.465.2 SpecimenStatus

Codes providing the status/availability of a specimen.

This code system http://hl7.org/fhir/specimen-status defines the following codes:

Code | Display | Definition
available | Available | The physical specimen is present and in good condition.
unavailable | Unavailable | There is no physical specimen because it is either lost, destroyed or consumed.
unsatisfactory | Unsatisfactory | The specimen cannot be used because of a quality issue such as a broken container, contamination, or too old.
entered-in-error | Entered-in-error | The specimen was entered in error and therefore nullified.

See the full registry of value sets defined as part of FHIR.

Explanation of the columns that may appear on this page:

Level | A few code lists that FHIR defines are hierarchical - each code is assigned a level. In this scheme, some codes are under other codes, and imply that the code they are under also applies
Source | The source of the definition of the code (when the value set draws in codes defined elsewhere)
Code | The code (used as the code in the resource instance). If the code is in italics, this indicates that the code is not selectable ('Abstract')
Display | The display (used in the display element of a Coding). If there is no display, implementers should not simply display the code, but map the concept into their application
Definition | An explanation of the meaning of the concept
Comments | Additional notes about how to use the code

4.2.12.468 Code System http://hl7.org/fhir/substance-status

URL: https://hl7.org/fhir/STU3/codesystem-substance-status.html

This page is part of the FHIR Specification (v3.0.2: STU 3). The current version which supercedes this version is 4.0.1. For a full list of available versions, see the Directory of published versions

Vocabulary Work Group | Maturity Level: 2 | Informative | Use Context: Any

This is a code system defined by the FHIR project.

Summary

Defining URL: | http://hl7.org/fhir/substance-status
Name: | FHIRSubstanceStatus
Definition: | A code to indicate if the substance is actively used
Committee: | Orders and Observations Work Group
OID: | 2.16.840.1.113883.4.642.1.468 (for OID based terminology systems)
Source Resource | XML / JSON

This Code system is used in the following value sets:

* FHIRSubstanceStatus (A code to indicate if the substance is actively used)

4.2.12.468.1 Content

4.2.12.468.2 FHIRSubstanceStatus

A code to indicate if the substance is actively used

This code system http://hl7.org/fhir/substance-status defines the following codes:

Code | Display | Definition
active | Active | The substance is considered for use or reference
inactive | Inactive | The substance is considered for reference, but not for use
entered-in-error | Entered in Error | The substance was entered in error

See the full registry of value sets defined as part of FHIR.

Explanation of the columns that may appear on this page:

Level | A few code lists that FHIR defines are hierarchical - each code is assigned a level. In this scheme, some codes are under other codes, and imply that the code they are under also applies
Source | The source of the definition of the code (when the value set draws in codes defined elsewhere)
Code | The code (used as the code in the resource instance). If the code is in italics, this indicates that the code is not selectable ('Abstract')
Display | The display (used in the display element of a Coding). If there is no display, implementers should not simply display the code, but map the concept into their application
Definition | An explanation of the meaning of the concept
Comments | Additional notes about how to use the code

4.2.12.470 Code System http://hl7.org/fhir/substance-category

URL: https://hl7.org/fhir/STU3/codesystem-substance-category.html

This page is part of the FHIR Specification (v3.0.2: STU 3). The current version which supercedes this version is 4.0.1. For a full list of available versions, see the Directory of published versions

Vocabulary Work Group | Maturity Level: 2 | Informative | Use Context: Not Intended for Production use

This is a code system defined at http://www.hl7.org/Special/committees/orders/index.cfm .

Summary

Defining URL: | http://hl7.org/fhir/substance-category
Name: | Substance Category Codes
Definition: | Substance category codes
Committee: | Orders and Observations Work Group
OID: | 2.16.840.1.113883.4.642.1.470 (for OID based terminology systems)
Source Resource | XML / JSON

This Code system is used in the following value sets:

* Substance Category Codes (Substance category codes)

4.2.12.470.1 Content

4.2.12.470.2 Substance Category Codes

Substance category codes

This code system http://hl7.org/fhir/substance-category defines the following codes:

Code | Display | Definition
allergen | Allergen | A substance that causes an allergic reaction.
biological | Biological Substance | A substance that is produced by or extracted from a biological source.
body | Body Substance | A substance that comes directly from a human or an animal (e.g. blood, urine, feces, tears, etc.).
chemical | Chemical | Any organic or inorganic substance of a particular molecular identity, including -- (i) any combination of such substances occurring in whole or in part as a result of a chemical reaction or occurring in nature and (ii) any element or uncombined radical (http://www.epa.gov/opptintr/import-export/pubs/importguide.pdf).
food | Dietary Substance | A food, dietary ingredient, or dietary supplement for human or animal.
drug | Drug or Medicament | A substance intended for use in the diagnosis, cure, mitigation, treatment, or prevention of disease in man or other animals (Federal Food Drug and Cosmetic Act).
material | Material | A finished product which is not normally ingested, absorbed or injected (e.g. steel, iron, wood, plastic and paper).

See the full registry of value sets defined as part of FHIR.

Explanation of the columns that may appear on this page:

Level | A few code lists that FHIR defines are hierarchical - each code is assigned a level. In this scheme, some codes are under other codes, and imply that the code they are under also applies
Source | The source of the definition of the code (when the value set draws in codes defined elsewhere)
Code | The code (used as the code in the resource instance). If the code is in italics, this indicates that the code is not selectable ('Abstract')
Display | The display (used in the display element of a Coding). If there is no display, implementers should not simply display the code, but map the concept into their application
Definition | An explanation of the meaning of the concept
Comments | Additional notes about how to use the code

4.2.12.472 Code System http://hl7.org/fhir/filter-operator

URL: https://hl7.org/fhir/STU3/codesystem-filter-operator.html

This page is part of the FHIR Specification (v3.0.2: STU 3). The current version which supercedes this version is 4.0.1. For a full list of available versions, see the Directory of published versions

Vocabulary Work Group | Maturity Level: 5 | Informative | Use Context: Any

This is a code system defined by the FHIR project.

Summary

Defining URL: | http://hl7.org/fhir/filter-operator
Name: | FilterOperator
Definition: | The kind of operation to perform as a part of a property based filter.
Committee: | Vocabulary Work Group
OID: | 2.16.840.1.113883.4.642.1.472 (for OID based terminology systems)
Source Resource | XML / JSON

This Code system is used in the following value sets:

* FilterOperator (The kind of operation to perform as a part of a property based filter.)

4.2.12.472.1 Content

4.2.12.472.2 FilterOperator

The kind of operation to perform as a part of a property based filter.

This code system http://hl7.org/fhir/filter-operator defines the following codes:

Code | Display | Definition
= | Equals | The specified property of the code equals the provided value.
is-a | Is A (by subsumption) | Includes all concept ids that have a transitive is-a relationship with the concept Id provided as the value, including the provided concept itself (i.e. include child codes)
descendent-of | Descendent Of (by subsumption) | Includes all concept ids that have a transitive is-a relationship with the concept Id provided as the value, excluding the provided concept itself (i.e. include child codes)

is-not-a | Not (Is A) (by subsumption) | The specified property of the code does not have an is-a relationship with the provided value.
regex | Regular Expression | The specified property of the code matches the regex specified in the provided value.
in | In Set | The specified property of the code is in the set of codes or concepts specified in the provided value (comma separated list).
not-in | Not in Set | The specified property of the code is not in the set of codes or concepts specified in the provided value (comma separated list).
generalizes | Generalizes (by Subsumption) | Includes all concept ids that have a transitive is-a relationship from the concept Id provided as the value, including the provided concept itself (e.g. include parent codes)
exists | Exists | The specified property of the code has at least one value (if the specified value is true; if the specified value is false, then matches when the specified property of the code has no values)

See the full registry of value sets defined as part of FHIR.

Explanation of the columns that may appear on this page:

Level | A few code lists that FHIR defines are hierarchical - each code is assigned a level. In this scheme, some codes are under other codes, and imply that the code they are under also applies
Source | The source of the definition of the code (when the value set draws in codes defined elsewhere)
Code | The code (used as the code in the resource instance). If the code is in italics, this indicates that the code is not selectable ('Abstract')
Display | The display (used in the display element of a Coding). If there is no display, implementers should not simply display the code, but map the concept into their application
Definition | An explanation of the meaning of the concept
Comments | Additional notes about how to use the code

4.2.12.474 Code System http://hl7.org/fhir/conceptmap-unmapped-mode

URL: https://hl7.org/fhir/STU3/codesystem-conceptmap-unmapped-mode.html

This page is part of the FHIR Specification (v3.0.2: STU 3). The current version which supercedes this version is 4.0.1. For a full list of available versions, see the Directory of published versions

Vocabulary Work Group | Maturity Level: 3 | Informative | Use Context: Any

This is a code system defined by the FHIR project.

Summary

Defining URL: | http://hl7.org/fhir/conceptmap-unmapped-mode
Name: | ConceptMapGroupUnmappedMode
Definition: | Defines which action to take if there is no match in the group.
Committee: | Vocabulary Work Group
OID: | 2.16.840.1.113883.4.642.1.474 (for OID based terminology systems)
Source Resource | XML / JSON

This Code system is used in the following value sets:

* ConceptMapGroupUnmappedMode (Defines which action to take if there is no match in the group.)

4.2.12.474.1 Content

4.2.12.474.2 ConceptMapGroupUnmappedMode

Defines which action to take if there is no match in the group.

This code system http://hl7.org/fhir/conceptmap-unmapped-mode defines the following codes:

Code | Display | Definition
provided | Provided Code | Use the code as provided in the $translate request
fixed | Fixed Code | Use the code explicitly provided in the group.unmapped
other-map | Other Map | Use the map identified by the canonical URL in URL

See the full registry of value sets defined as part of FHIR.

Explanation of the columns that may appear on this page:

Level | A few code lists that FHIR defines are hierarchical - each code is assigned a level. In this scheme, some codes are under other codes, and imply that the code they are under also applies
Source | The source of the definition of the code (when the value set draws in codes defined elsewhere)
Code | The code (used as the code in the resource instance). If the code is in italics, this indicates that the code is not selectable ('Abstract')
Display | The display (used in the display element of a Coding). If there is no display, implementers should not simply display the code, but map the concept into their application
Definition | An explanation of the meaning of the concept
Comments | Additional notes about how to use the code

4.2.12.476 Code System http://hl7.org/fhir/slotstatus

URL: https://hl7.org/fhir/STU3/codesystem-slotstatus.html

This page is part of the FHIR Specification (v3.0.2: STU 3). The current version which supercedes this version is 4.0.1. For a full list of available versions, see the Directory of published versions

Vocabulary Work Group | Maturity Level: 3 | Informative | Use Context: Any

This is a code system defined by the FHIR project.

Summary

Defining URL: | http://hl7.org/fhir/slotstatus

Name: | SlotStatus
Definition: | The free/busy status of the slot.
Committee: | Patient Administration Work Group
OID: | 2.16.840.1.113883.4.642.1.476 (for OID based terminology systems)
Source Resource | XML / JSON

This Code system is used in the following value sets:

* SlotStatus (The free/busy status of the slot.)

4.2.12.476.1 Content

4.2.12.476.2 SlotStatus

The free/busy status of the slot.

This code system http://hl7.org/fhir/slotstatus defines the following codes:

Code | Display | Definition
busy | Busy | Indicates that the time interval is busy because one or more events have been scheduled for that interval.
free | Free | Indicates that the time interval is free for scheduling.
busy-unavailable | Busy (Unavailable) | Indicates that the time interval is busy and that the interval can not be scheduled.
busy-tentative | Busy (Tentative) | Indicates that the time interval is busy because one or more events have been tentatively scheduled for that interval.
entered-in-error | Entered in error | This instance should not have been part of this patient's medical record.

See the full registry of value sets defined as part of FHIR.

Explanation of the columns that may appear on this page:

Level | A few code lists that FHIR defines are hierarchical - each code is assigned a level. In this scheme, some codes are under other codes, and imply that the code they are under also applies
Source | The source of the definition of the code (when the value set draws in codes defined elsewhere)
Code | The code (used as the code in the resource instance). If the code is in italics, this indicates that the code is not selectable ('Abstract')
Display | The display (used in the display element of a Coding). If there is no display, implementers should not simply display the code, but map the concept into their application
Definition | An explanation of the meaning of the concept
Comments | Additional notes about how to use the code

4.2.12.478 Code System http://hl7.org/fhir/appointmentstatus

URL: https://hl7.org/fhir/STU3/codesystem-appointmentstatus.html

This page is part of the FHIR Specification (v3.0.2: STU 3). The current version which supercedes this version is 4.0.1. For a full list of available versions, see the Directory of published versions

Vocabulary Work Group | Maturity Level: 3 | Informative | Use Context: Any

This is a code system defined by the FHIR project.

Summary

Defining URL: | http://hl7.org/fhir/appointmentstatus
Name: | AppointmentStatus
Definition: | The free/busy status of an appointment.
Committee: | Patient Administration Work Group
OID: | 2.16.840.1.113883.4.642.1.478 (for OID based terminology systems)
Source Resource | XML / JSON

This Code system is used in the following value sets:

* AppointmentStatus (The free/busy status of an appointment.)

4.2.12.478.1 Content

4.2.12.478.2 AppointmentStatus

The free/busy status of an appointment.

This code system http://hl7.org/fhir/appointmentstatus defines the following codes:

Code | Display | Definition
proposed | Proposed | None of the participant(s) have finalized their acceptance of the appointment request, and the start/end time may not be set yet.
pending | Pending | Some or all of the participant(s) have not finalized their acceptance of the appointment request.
booked | Booked | All participant(s) have been considered and the appointment is confirmed to go ahead at the date/times specified.
arrived | Arrived | Some of the patients have arrived.
fulfilled | Fulfilled | This appointment has completed and may have resulted in an encounter.
cancelled | Cancelled | The appointment has been cancelled.
noshow | No Show | Some or all of the participant(s) have not/did not appear for the appointment (usually the patient).
entered-in-error | Entered in error | This instance should not have been part of this patient's medical record.

See the full registry of value sets defined as part of FHIR.

Explanation of the columns that may appear on this page:

Level | A few code lists that FHIR defines are hierarchical - each code is assigned a level. In this scheme, some codes are under other codes, and imply that the code they are under also applies
Source | The source of the definition of the code (when the value set draws in codes defined elsewhere)
Code | The code (used as the code in the resource instance). If the code is in italics, this indicates that the code is not selectable ('Abstract')
Display | The display (used in the display element of a Coding). If there is no display, implementers should not simply display the code, but map the concept into their application
Definition | An explanation of the meaning of the concept
Comments | Additional notes about how to use the code

4.2.12.480 Code System http://hl7.org/fhir/participationstatus

URL: https://hl7.org/fhir/STU3/codesystem-participationstatus.html

This page is part of the FHIR Specification (v3.0.2: STU 3). The current version which supercedes this version is 4.0.1. For a full list of available versions, see the Directory of published versions

Vocabulary Work Group | Maturity Level: 3 | Informative | Use Context: Any

This is a code system defined by the FHIR project.

Summary

Defining URL: | http://hl7.org/fhir/participationstatus
Name: | ParticipationStatus
Definition: | The Participation status of an appointment.
Committee: | Patient Administration Work Group
OID: | 2.16.840.1.113883.4.642.1.480 (for OID based terminology systems)
Source Resource | XML / JSON

This Code system is used in the following value sets:

* ParticipationStatus (The Participation status of an appointment.)

4.2.12.480.1 Content

4.2.12.480.2 ParticipationStatus

The Participation status of an appointment.

This code system http://hl7.org/fhir/participationstatus defines the following codes:

Code | Display | Definition
accepted | Accepted | The participant has accepted the appointment.
declined | Declined | The participant has declined the appointment and will not participate in the appointment.
tentative | Tentative | The participant has tentatively accepted the appointment. This could be automatically created by a system and requires further processing before it can be accepted. There is no commitment that attendance will occur.
needs-action | Needs Action | The participant needs to indicate if they accept the appointment by changing this status to one of the other statuses.

See the full registry of value sets defined as part of FHIR.

Explanation of the columns that may appear on this page:

Level | A few code lists that FHIR defines are hierarchical - each code is assigned a level. In this scheme, some codes are under other codes, and imply that the code they are under also applies
Source | The source of the definition of the code (when the value set draws in codes defined elsewhere)
Code | The code (used as the code in the resource instance). If the code is in italics, this indicates that the code is not selectable ('Abstract')
Display | The display (used in the display element of a Coding). If there is no display, implementers should not simply display the code, but map the concept into their application
Definition | An explanation of the meaning of the concept
Comments | Additional notes about how to use the code

4.2.12.482 Code System http://hl7.org/fhir/participantrequired

URL: https://hl7.org/fhir/STU3/codesystem-participantrequired.html

This page is part of the FHIR Specification (v3.0.2: STU 3). The current version which supercedes this version is 4.0.1. For a full list of available versions, see the Directory of published versions

Vocabulary Work Group | Maturity Level: 3 | Informative | Use Context: Any

This is a code system defined by the FHIR project.

Summary

Defining URL: | http://hl7.org/fhir/participantrequired
Name: | ParticipantRequired
Definition: | Is the Participant required to attend the appointment.
Committee: | Patient Administration Work Group
OID: | 2.16.840.1.113883.4.642.1.482 (for OID based terminology systems)
Source Resource | XML / JSON

This Code system is used in the following value sets:

* ParticipantRequired (Is the Participant required to attend the appointment.)

4.2.12.482.1 Content

4.2.12.482.2 ParticipantRequired

Is the Participant required to attend the appointment.

This code system http://hl7.org/fhir/participantrequired defines the following codes:

Code | Display | Definition
required | Required | The participant is required to attend the appointment.
optional | Optional | The participant may optionally attend the appointment.
information-only | Information Only | The participant is excluded from the appointment, and may not be informed of the appointment taking place. (Appointment is about them, not for them - such as 2 doctors discussing results about a patient's test).

See the full registry of value sets defined as part of FHIR.

Explanation of the columns that may appear on this page:

Level | A few code lists that FHIR defines are hierarchical - each code is assigned a level. In this scheme, some codes are under other codes, and imply that the code they are under also applies
Source | The source of the definition of the code (when the value set draws in codes defined elsewhere)
Code | The code (used as the code in the resource instance). If the code is in italics, this indicates that the code is not selectable ('Abstract')
Display | The display (used in the display element of a Coding). If there is no display, implementers should not simply display the code, but map the concept into their application
Definition | An explanation of the meaning of the concept
Comments | Additional notes about how to use the code

4.2.12.484 Code System http://hl7.org/fhir/namingsystem-type

URL: https://hl7.org/fhir/STU3/codesystem-namingsystem-type.html

This page is part of the FHIR Specification (v3.0.2: STU 3). The current version which supercedes this version is 4.0.1. For a full list of available versions, see the Directory of published versions

Vocabulary Work Group | Maturity Level: 1 | Informative | Use Context: Any

This is a code system defined by the FHIR project.

Summary

Defining URL: | http://hl7.org/fhir/namingsystem-type
Name: | NamingSystemType
Definition: | Identifies the purpose of the naming system.
Committee: | FHIR Infrastructure Work Group
OID: | 2.16.840.1.113883.4.642.1.484 (for OID based terminology systems)
Source Resource | XML / JSON

This Code system is used in the following value sets:

* NamingSystemType (Identifies the purpose of the naming system.)

4.2.12.484.1 Content

4.2.12.484.2 NamingSystemType

Identifies the purpose of the naming system.

This code system http://hl7.org/fhir/namingsystem-type defines the following codes:

Code | Display | Definition
codesystem | Code System | The naming system is used to define concepts and symbols to represent those concepts; e.g. UCUM, LOINC, NDC code, local lab codes, etc.
identifier | Identifier | The naming system is used to manage identifiers (e.g. license numbers, order numbers, etc.).
root | Root | The naming system is used as the root for other identifiers and naming systems.

See the full registry of value sets defined as part of FHIR.

Explanation of the columns that may appear on this page:

Level | A few code lists that FHIR defines are hierarchical - each code is assigned a level. In this scheme, some codes are under other codes, and imply that the code they are under also applies
Source | The source of the definition of the code (when the value set draws in codes defined elsewhere)
Code | The code (used as the code in the resource instance). If the code is in italics, this indicates that the code is not selectable ('Abstract')
Display | The display (used in the display element of a Coding). If there is no display, implementers should not simply display the code, but map the concept into their application
Definition | An explanation of the meaning of the concept
Comments | Additional notes about how to use the code

4.2.12.486 Code System http://hl7.org/fhir/namingsystem-identifier-type

URL: https://hl7.org/fhir/STU3/codesystem-namingsystem-identifier-type.html

This page is part of the FHIR Specification (v3.0.2: STU 3). The current version which supercedes this version is 4.0.1. For a full list of available versions, see the Directory of published versions

Vocabulary Work Group | Maturity Level: 1 | Informative | Use Context: Any

This is a code system defined by the FHIR project.

Summary

Defining URL: | http://hl7.org/fhir/namingsystem-identifier-type
Name: | NamingSystemIdentifierType
Definition: | Identifies the style of unique identifier used to identify a namespace.
Committee: | FHIR Infrastructure Work Group
OID: | 2.16.840.1.113883.4.642.1.486 (for OID based terminology systems)
Source Resource | XML / JSON

This Code system is used in the following value sets:

* NamingSystemIdentifierType (Identifies the style of unique identifier used to identify a namespace.)

4.2.12.486.1 Content

4.2.12.486.2 NamingSystemIdentifierType

Identifies the style of unique identifier used to identify a namespace.

This code system http://hl7.org/fhir/namingsystem-identifier-type defines the following codes:

Code | Display | Definition
oid | OID | An ISO object identifier; e.g. 1.2.3.4.5.
uuid | UUID | A universally unique identifier of the form a5afddf4-e880-459b-876e-e4591b0acc11.
uri | URI | A uniform resource identifier (ideally a URL - uniform resource locator); e.g. http://unitsofmeasure.org.
other | Other | Some other type of unique identifier; e.g. HL7-assigned reserved string such as LN for LOINC.

See the full registry of value sets defined as part of FHIR.

Explanation of the columns that may appear on this page:

Level | A few code lists that FHIR defines are hierarchical - each code is assigned a level. In this scheme, some codes are under other codes, and imply that the code they are under also applies
Source | The source of the definition of the code (when the value set draws in codes defined elsewhere)
Code | The code (used as the code in the resource instance). If the code is in italics, this indicates that the code is not selectable ('Abstract')
Display | The display (used in the display element of a Coding). If there is no display, implementers should not simply display the code, but map the concept into their application
Definition | An explanation of the meaning of the concept
Comments | Additional notes about how to use the code

4.2.12.488 Code System http://hl7.org/fhir/endpoint-status

URL: https://hl7.org/fhir/STU3/codesystem-endpoint-status.html

This page is part of the FHIR Specification (v3.0.2: STU 3). The current version which supercedes this version is 4.0.1. For a full list of available versions, see the Directory of published versions

Vocabulary Work Group | Maturity Level: 2 | Informative | Use Context: Any

This is a code system defined by the FHIR project.

Summary

Defining URL: | http://hl7.org/fhir/endpoint-status
Name: | EndpointStatus
Definition: | The status of the endpoint
Committee: | Patient Administration Work Group
OID: | 2.16.840.1.113883.4.642.1.488 (for OID based terminology systems)
Source Resource | XML / JSON

This Code system is used in the following value sets:

* EndpointStatus (The status of the endpoint)

4.2.12.488.1 Content

4.2.12.488.2 EndpointStatus

The status of the endpoint

This code system http://hl7.org/fhir/endpoint-status defines the following codes:

Code | Display | Definition
active | Active | This endpoint is expected to be active and can be used
suspended | Suspended | This endpoint is temporarily unavailable
error | Error | This endpoint has exceeded connectivity thresholds and is considered in an error state and should no longer be attempted to connect to until corrective action is taken
off | Off | This endpoint is no longer to be used
entered-in-error | Entered in error | This instance should not have been part of this patient's medical record.

test | Test | This endpoint is not intended for production usage.

See the full registry of value sets defined as part of FHIR.

Explanation of the columns that may appear on this page:

Level | A few code lists that FHIR defines are hierarchical - each code is assigned a level. In this scheme, some codes are under other codes, and imply that the code they are under also applies

Source | The source of the definition of the code (when the value set draws in codes defined elsewhere)

Code | The code (used as the code in the resource instance). If the code is in italics, this indicates that the code is not selectable ('Abstract')

Display | The display (used in the display element of a Coding). If there is no display, implementers should not simply display the code, but map the concept into their application

Definition | An explanation of the meaning of the concept

Comments | Additional notes about how to use the code

4.2.12.490 Code System http://hl7.org/fhir/endpoint-payload-type

URL: https://hl7.org/fhir/STU3/codesystem-endpoint-payload-type.html

This page is part of the FHIR Specification (v3.0.2: STU 3). The current version which supercedes this version is 4.0.1. For a full list of available versions, see the Directory of published versions

Vocabulary Work Group | Maturity Level: 1 | Informative | Use Context: Not Intended for Production use

This is a code system defined by the FHIR project.

Summary

Defining URL: | http://hl7.org/fhir/endpoint-payload-type

Name: | Endpoint Payload Type

Definition: | This is an example value set defined by the FHIR project, that could be used to represent possible payload document types.

Committee: | Patient Administration Work Group

OID: | 2.16.840.1.113883.4.642.1.490 (for OID based terminology systems)

Copyright: | Some content from IHE® Copyright © 2015 IHE International, Inc. This content is from the IHE Technical Frameworks and Supplements, available for free download and use at http://www.ihe.net/Technical_Frameworks/

Source Resource | XML / JSON

This Code system is used in the following value sets:

* Endpoint Payload Type (This is an example value set defined by the FHIR project, that could be used to represent possible payload document types.)

4.2.12.490.1 Content

4.2.12.490.2 Endpoint Payload Type

This is an example value set defined by the FHIR project, that could be used to represent possible payload document types.

Copyright Statement: Some content from IHE® Copyright © 2015 IHE International, Inc. This content is from the IHE Technical Frameworks and Supplements, available for free download and use at http://www.ihe.net/Technical_Frameworks/

This code system http://hl7.org/fhir/endpoint-payload-type defines the following codes:

Code | Display | Definition

any | Any | Any payload type can be used with this endpoint, it is either a payload agnostic infrastructure (such as a storage repository), or some other type of endpoint where payload considerations are internally handled, and not available

none | None | This endpoint does not require any content to be sent, simply connecting to the endpoint is enough notification. This can be used as a 'ping' to wakeup a service to retrieve content, which could be to ensure security considerations are correctly handled

See the full registry of value sets defined as part of FHIR.

Explanation of the columns that may appear on this page:

Level | A few code lists that FHIR defines are hierarchical - each code is assigned a level. In this scheme, some codes are under other codes, and imply that the code they are under also applies

Source | The source of the definition of the code (when the value set draws in codes defined elsewhere)

Code | The code (used as the code in the resource instance). If the code is in italics, this indicates that the code is not selectable ('Abstract')

Display | The display (used in the display element of a Coding). If there is no display, implementers should not simply display the code, but map the concept into their application

Definition | An explanation of the meaning of the concept

Comments | Additional notes about how to use the code

4.2.12.492 Code System http://hl7.org/fhir/endpoint-connection-type

URL: https://hl7.org/fhir/STU3/codesystem-endpoint-connection-type.html

This page is part of the FHIR Specification (v3.0.2: STU 3). The current version which supercedes this version is 4.0.1. For a full list of available versions, see the Directory of published versions

Vocabulary Work Group | Maturity Level: 2 | Informative | Use Context: Not Intended for Production use

This is a code system defined by the FHIR project.

Summary

Defining URL: | http://hl7.org/fhir/endpoint-connection-type

Name: | Endpoint Connection Type
Definition: | This is an example value set defined by the FHIR project, that could be used to represent possible connection type profile values.
Committee: | Patient Administration Work Group
OID: | 2.16.840.1.113883.4.642.1.492 (for OID based terminology systems)
Copyright: | Some content from IHE® Copyright © 2015 IHE International, Inc. This content is from the IHE Technical Frameworks and Supplements, available for free download and use at http://www.ihe.net/Technical_Frameworks/
Source Resource | XML / JSON

This Code system is used in the following value sets:

* Endpoint Connection Type (This is an example value set defined by the FHIR project, that could be used to represent possible connection type profile values.)

4.2.12.492.1 Content

4.2.12.492.2 Endpoint Connection Type

This is an example value set defined by the FHIR project, that could be used to represent possible connection type profile values.

Copyright Statement: Some content from IHE® Copyright © 2015 IHE International, Inc. This content is from the IHE Technical Frameworks and Supplements, available for free download and use at http://www.ihe.net/Technical_Frameworks/

This code system http://hl7.org/fhir/endpoint-connection-type defines the following codes:

Code | Display | Definition
ihe-xcpd | IHE XCPD | IHE Cross Community Patient Discovery Profile (XCPD) - http://wiki.ihe.net/index.php/Cross-Community_Patient_Discovery
ihe-xca | IHE XCA | IHE Cross Community Access Profile (XCA) - http://wiki.ihe.net/index.php/Cross-Community_Access
ihe-xdr | IHE XDR | IHE Cross-Enterprise Document Reliable Exchange (XDR) - http://wiki.ihe.net/index.php/Cross-enterprise_Document_Reliable_Interchange
ihe-xds | IHE XDS | IHE Cross-Enterprise Document Sharing (XDS) - http://wiki.ihe.net/index.php/Cross-Enterprise_Document_Sharing
ihe-iid | IHE IID | IHE Invoke Image Display (IID) - http://wiki.ihe.net/index.php/Invoke_Image_Display
dicom-wado-rs | DICOM WADO-RS | DICOMweb RESTful Image Retrieve - http://dicom.nema.org/medical/dicom/current/output/chtml/part18/sect_6.5.html
dicom-qido-rs | DICOM QIDO-RS | DICOMweb RESTful Image query - http://dicom.nema.org/medical/dicom/current/output/chtml/part18/sect_6.7.html
dicom-stow-rs | DICOM STOW-RS | DICOMweb RESTful image sending and storage - http://dicom.nema.org/medical/dicom/current/output/chtml/part18/sect_6.6.html
dicom-wado-uri | DICOM WADO-URI | DICOMweb Image Retrieve - http://dicom.nema.org/dicom/2013/output/chtml/part18/sect_6.3.html
hl7-fhir-rest | HL7 FHIR | Interact with the server interface using FHIR's RESTful interface. For details on its version/capabilities you should connect the the value in Endpoint.address and retrieve the FHIR CapabilityStatement.
hl7-fhir-msg | HL7 FHIR Messaging | Use the servers FHIR Messaging interface. Details can be found on the messaging.html page in the FHIR Specification. The FHIR server's base address is specified in the Endpoint.address property.
hl7v2-mllp | HL7 v2 MLLP | HL7v2 messages over an LLP TCP connection
secure-email | Secure email | Email delivery using a digital certificate to encrypt the content using the public key, receiver must have the private key to decrypt the content
direct-project | Direct Project | Direct Project information - http://wiki.directproject.org/

See the full registry of value sets defined as part of FHIR.

Explanation of the columns that may appear on this page:

Level | A few code lists that FHIR defines are hierarchical - each code is assigned a level. In this scheme, some codes are under other codes, and imply that the code they are under also applies
Source | The source of the definition of the code (when the value set draws in codes defined elsewhere)
Code | The code (used as the code in the resource instance). If the code is in italics, this indicates that the code is not selectable ('Abstract')
Display | The display (used in the display element of a Coding). If there is no display, implementers should not simply display the code, but map the concept into their application
Definition | An explanation of the meaning of the concept
Comments | Additional notes about how to use the code

4.2.12.494 Code System http://hl7.org/fhir/subscription-channel-type

URL: https://hl7.org/fhir/STU3/codesystem-subscription-channel-type.html

This page is part of the FHIR Specification (v3.0.2: STU 3). The current version which supercedes this version is 4.0.1. For a full list of available versions, see the Directory of published versions

Vocabulary Work Group | Maturity Level: 3 | Informative | Use Context: Any

This is a code system defined by the FHIR project.

Summary

Defining URL: | http://hl7.org/fhir/subscription-channel-type
Name: | SubscriptionChannelType
Definition: | The type of method used to execute a subscription.
Committee: | FHIR Infrastructure Work Group
OID: | 2.16.840.1.113883.4.642.1.494 (for OID based terminology systems)
Source Resource | XML / JSON

This Code system is used in the following value sets:

* SubscriptionChannelType (The type of method used to execute a subscription.)

4.2.12.494.1 Content

4.2.12.494.2 SubscriptionChannelType

The type of method used to execute a subscription.

This code system http://hl7.org/fhir/subscription-channel-type defines the following codes:

Code | Display | Definition
rest-hook | Rest Hook | The channel is executed by making a post to the URI. If a payload is included, the URL is interpreted as the service base, and an update (PUT) is made.
websocket | Websocket | The channel is executed by sending a packet across a web socket connection maintained by the client. The URL identifies the websocket, and the client binds to this URL.
email | Email | The channel is executed by sending an email to the email addressed in the URI (which must be a mailto:).
sms | SMS | The channel is executed by sending an SMS message to the phone number identified in the URL (tel:).
message | Message | The channel is executed by sending a message (e.g. a Bundle with a MessageHeader resource etc.) to the application identified in the URI.

See the full registry of value sets defined as part of FHIR.

Explanation of the columns that may appear on this page:

Level | A few code lists that FHIR defines are hierarchical - each code is assigned a level. In this scheme, some codes are under other codes, and imply that the code they are under also applies
Source | The source of the definition of the code (when the value set draws in codes defined elsewhere)
Code | The code (used as the code in the resource instance). If the code is in italics, this indicates that the code is not selectable ('Abstract')
Display | The display (used in the display element of a Coding). If there is no display, implementers should not simply display the code, but map the concept into their application
Definition | An explanation of the meaning of the concept
Comments | Additional notes about how to use the code

4.2.12.496 Code System http://hl7.org/fhir/subscription-status

URL: https://hl7.org/fhir/STU3/codesystem-subscription-status.html

This page is part of the FHIR Specification (v3.0.2: STU 3). The current version which supercedes this version is 4.0.1. For a full list of available versions, see the Directory of published versions

Vocabulary Work Group | Maturity Level: 3 | Informative | Use Context: Any

This is a code system defined by the FHIR project.

Summary

Defining URL: | http://hl7.org/fhir/subscription-status
Name: | SubscriptionStatus
Definition: | The status of a subscription.
Committee: | FHIR Infrastructure Work Group
OID: | 2.16.840.1.113883.4.642.1.496 (for OID based terminology systems)
Source Resource | XML / JSON

This Code system is used in the following value sets:

* SubscriptionStatus (The status of a subscription.)

4.2.12.496.1 Content

4.2.12.496.2 SubscriptionStatus

The status of a subscription.

This code system http://hl7.org/fhir/subscription-status defines the following codes:

Code | Display | Definition
requested | Requested | The client has requested the subscription, and the server has not yet set it up.
active | Active | The subscription is active.
error | Error | The server has an error executing the notification.
off | Off | Too many errors have occurred or the subscription has expired.

See the full registry of value sets defined as part of FHIR.

Explanation of the columns that may appear on this page:

Level | A few code lists that FHIR defines are hierarchical - each code is assigned a level. In this scheme, some codes are under other codes, and imply that the code they are under also applies
Source | The source of the definition of the code (when the value set draws in codes defined elsewhere)
Code | The code (used as the code in the resource instance). If the code is in italics, this indicates that the code is not selectable ('Abstract')
Display | The display (used in the display element of a Coding). If there is no display, implementers should not simply display the code, but map the concept into their application
Definition | An explanation of the meaning of the concept
Comments | Additional notes about how to use the code

4.2.12.498 Code System http://hl7.org/fhir/subscription-tag

URL: https://hl7.org/fhir/STU3/codesystem-subscription-tag.html

This page is part of the FHIR Specification (v3.0.2: STU 3). The current version which supercedes this version is 4.0.1. For a full list of available versions, see the Directory of published versions

Vocabulary Work Group | Maturity Level: 1 | Informative | Use Context: Any

This is a code system defined by the FHIR project.

Summary

Defining URL: | http://hl7.org/fhir/subscription-tag
Name: | SubscriptionTag
Definition: | Tags to put on a resource after subscriptions have been sent.
Committee: | FHIR Infrastructure Work Group
OID: | 2.16.840.1.113883.4.642.1.498 (for OID based terminology systems)
Source Resource | XML / JSON

This Code system is used in the following value sets:

* SubscriptionTag (Tags to put on a resource after subscriptions have been sent.)

4.2.12.498.1 Content

4.2.12.498.2 SubscriptionTag

Tags to put on a resource after subscriptions have been sent.

This code system http://hl7.org/fhir/subscription-tag defines the following codes:

Code | Display | Definition
queued | Queued | The message has been queued for processing on a destination systems.
delivered | Delivered | The message has been delivered to its intended recipient.

See the full registry of value sets defined as part of FHIR.

Explanation of the columns that may appear on this page:

Level | A few code lists that FHIR defines are hierarchical - each code is assigned a level. In this scheme, some codes are under other codes, and imply that the code they are under also applies
Source | The source of the definition of the code (when the value set draws in codes defined elsewhere)
Code | The code (used as the code in the resource instance). If the code is in italics, this indicates that the code is not selectable ('Abstract')
Display | The display (used in the display element of a Coding). If there is no display, implementers should not simply display the code, but map the concept into their application
Definition | An explanation of the meaning of the concept
Comments | Additional notes about how to use the code

4.2.12.500 Code System http://hl7.org/fhir/operation-kind

URL: https://hl7.org/fhir/STU3/codesystem-operation-kind.html

This page is part of the FHIR Specification (v3.0.2: STU 3). The current version which supercedes this version is 4.0.1. For a full list of available versions, see the Directory of published versions

Vocabulary Work Group | Maturity Level: 4 | Informative | Use Context: Any

This is a code system defined by the FHIR project.

Summary

Defining URL: | http://hl7.org/fhir/operation-kind
Name: | OperationKind
Definition: | Whether an operation is a normal operation or a query.
Committee: | FHIR Infrastructure Work Group
OID: | 2.16.840.1.113883.4.642.1.500 (for OID based terminology systems)
Source Resource | XML / JSON

This Code system is used in the following value sets:

* OperationKind (Whether an operation is a normal operation or a query.)

4.2.12.500.1 Content

4.2.12.500.2 OperationKind

Whether an operation is a normal operation or a query.

This code system http://hl7.org/fhir/operation-kind defines the following codes:

Code | Display | Definition
operation | Operation | This operation is invoked as an operation.
query | Query | This operation is a named query, invoked using the search mechanism.

See the full registry of value sets defined as part of FHIR.

Explanation of the columns that may appear on this page:

Level | A few code lists that FHIR defines are hierarchical - each code is assigned a level. In this scheme, some codes are under other codes, and imply that the code they are under also applies
Source | The source of the definition of the code (when the value set draws in codes defined elsewhere)
Code | The code (used as the code in the resource instance). If the code is in italics, this indicates that the code is not selectable ('Abstract')
Display | The display (used in the display element of a Coding). If there is no display, implementers should not simply display the code, but map the concept into their application
Definition | An explanation of the meaning of the concept
Comments | Additional notes about how to use the code

4.2.12.502 Code System http://hl7.org/fhir/operation-parameter-use

URL: https://hl7.org/fhir/STU3/codesystem-operation-parameter-use.html

This page is part of the FHIR Specification (v3.0.2: STU 3). The current version which supercedes this version is 4.0.1. For a full list of available versions, see the Directory of published versions

Vocabulary Work Group | Maturity Level: 4 | Informative | Use Context: Any

This is a code system defined by the FHIR project.

Summary

Defining URL: | http://hl7.org/fhir/operation-parameter-use
Name: | OperationParameterUse
Definition: | Whether an operation parameter is an input or an output parameter.
Committee: | FHIR Infrastructure Work Group
OID: | 2.16.840.1.113883.4.642.1.502 (for OID based terminology systems)
Source Resource | XML / JSON

This Code system is used in the following value sets:

* OperationParameterUse (Whether an operation parameter is an input or an output parameter.)

4.2.12.502.1 Content

4.2.12.502.2 OperationParameterUse

Whether an operation parameter is an input or an output parameter.

This code system http://hl7.org/fhir/operation-parameter-use defines the following codes:

Code | Display | Definition
in | In | This is an input parameter.
out | Out | This is an output parameter.

See the full registry of value sets defined as part of FHIR.

Explanation of the columns that may appear on this page:

Level | A few code lists that FHIR defines are hierarchical - each code is assigned a level. In this scheme, some codes are under other codes, and imply that the code they are under also applies
Source | The source of the definition of the code (when the value set draws in codes defined elsewhere)
Code | The code (used as the code in the resource instance). If the code is in italics, this indicates that the code is not selectable ('Abstract')
Display | The display (used in the display element of a Coding). If there is no display, implementers should not simply display the code, but map the concept into their application
Definition | An explanation of the meaning of the concept
Comments | Additional notes about how to use the code

4.2.12.505 Code System http://hl7.org/fhir/service-referral-method

URL: https://hl7.org/fhir/STU3/codesystem-service-referral-method.html

This page is part of the FHIR Specification (v3.0.2: STU 3). The current version which supercedes this version is 4.0.1. For a full list of available versions, see the Directory of published versions

Vocabulary Work Group | Maturity Level: 1 | Informative | Use Context: Any

This is a code system defined by the FHIR project.

Summary

Defining URL: | http://hl7.org/fhir/service-referral-method
Name: | ReferralMethod
Definition: | The methods of referral can be used when referring to a specific HealthCareService resource.
Committee: | Patient Administration Work Group
OID: | 2.16.840.1.113883.4.642.1.505 (for OID based terminology systems)
Source Resource | XML / JSON

This Code system is used in the following value sets:

* ReferralMethod (The methods of referral can be used when referring to a specific HealthCareService resource.)

4.2.12.505.1 Content

4.2.12.505.2 ReferralMethod

The methods of referral can be used when referring to a specific HealthCareService resource.

This code system http://hl7.org/fhir/service-referral-method defines the following codes:

Code | Display | Definition
fax | Fax | Referrals may be accepted by fax.
phone | Phone | Referrals may be accepted over the phone from a practitioner.
elec | Secure Messaging | Referrals may be accepted via a secure messaging system. To determine the types of secure messaging systems supported, refer to the identifiers collection. Callers will need to understand the specific identifier system used to know that they are able to transmit messages.
semail | Secure Email | Referrals may be accepted via a secure email. To send please encrypt with the services public key.
mail | Mail | Referrals may be accepted via regular postage (or hand delivered).

See the full registry of value sets defined as part of FHIR.

Explanation of the columns that may appear on this page:

Level | A few code lists that FHIR defines are hierarchical - each code is assigned a level. In this scheme, some codes are under other codes, and imply that the code they are under also applies
Source | The source of the definition of the code (when the value set draws in codes defined elsewhere)
Code | The code (used as the code in the resource instance). If the code is in italics, this indicates that the code is not selectable ('Abstract')
Display | The display (used in the display element of a Coding). If there is no display, implementers should not simply display the code, but map the concept into their application
Definition | An explanation of the meaning of the concept
Comments | Additional notes about how to use the code

4.2.12.507 Code System http://hl7.org/fhir/days-of-week

URL: https://hl7.org/fhir/STU3/codesystem-days-of-week.html

This page is part of the FHIR Specification (v3.0.2: STU 3). The current version which supercedes this version is 4.0.1. For a full list of available versions, see the Directory of published versions

Vocabulary Work Group | Maturity Level: 2 | Informative | Use Context: Any

This is a code system defined by the FHIR project.

Summary

Defining URL: | http://hl7.org/fhir/days-of-week
Name: | DaysOfWeek
Definition: | The days of the week.
Committee: | Patient Administration Work Group
OID: | 2.16.840.1.113883.4.642.1.507 (for OID based terminology systems)
Source Resource | XML / JSON

This Code system is used in the following value sets:

* DaysOfWeek (The days of the week.)

4.2.12.507.1 Content

4.2.12.507.2 DaysOfWeek

The days of the week.

This code system http://hl7.org/fhir/days-of-week defines the following codes:

Code | Display | Definition
mon | Monday | Monday
tue | Tuesday | Tuesday
wed | Wednesday | Wednesday
thu | Thursday | Thursday
fri | Friday | Friday
sat | Saturday | Saturday
sun | Sunday | Sunday

See the full registry of value sets defined as part of FHIR.

Explanation of the columns that may appear on this page:

Level | A few code lists that FHIR defines are hierarchical - each code is assigned a level. In this scheme, some codes are under other codes, and imply that the code they are under also applies
Source | The source of the definition of the code (when the value set draws in codes defined elsewhere)
Code | The code (used as the code in the resource instance). If the code is in italics, this indicates that the code is not selectable ('Abstract')
Display | The display (used in the display element of a Coding). If there is no display, implementers should not simply display the code, but map the concept into their application
Definition | An explanation of the meaning of the concept
Comments | Additional notes about how to use the code

4.2.12.509 Code System http://hl7.org/fhir/service-provision-conditions

URL: https://hl7.org/fhir/STU3/codesystem-service-provision-conditions.html

This page is part of the FHIR Specification (v3.0.2: STU 3). The current version which supercedes this version is 4.0.1. For a full list of available versions, see the Directory of published versions

Vocabulary Work Group | Maturity Level: 1 | Informative | Use Context: Any

This is a code system defined by the FHIR project.

Summary

Defining URL: | http://hl7.org/fhir/service-provision-conditions
Name: | ServiceProvisionConditions
Definition: | The code(s) that detail the conditions under which the healthcare service is available/offered.
Committee: | Patient Administration Work Group
OID: | 2.16.840.1.113883.4.642.1.509 (for OID based terminology systems)
Source Resource | XML / JSON

This Code system is used in the following value sets:

* ServiceProvisionConditions (The code(s) that detail the conditions under which the healthcare service is available/offered.)

4.2.12.509.1 Content

4.2.12.509.2 ServiceProvisionConditions

The code(s) that detail the conditions under which the healthcare service is available/offered.

This code system http://hl7.org/fhir/service-provision-conditions defines the following codes:

Code | Display | Definition
free | Free | This service is available for no patient cost.
disc | Discounts Available | There are discounts available on this service for qualifying patients.
cost | Fees apply | Fees apply for this service.

See the full registry of value sets defined as part of FHIR.

Explanation of the columns that may appear on this page:

Level | A few code lists that FHIR defines are hierarchical - each code is assigned a level. In this scheme, some codes are under other codes, and imply that the code they are under also applies
Source | The source of the definition of the code (when the value set draws in codes defined elsewhere)
Code | The code (used as the code in the resource instance). If the code is in italics, this indicates that the code is not selectable ('Abstract')
Display | The display (used in the display element of a Coding). If there is no display, implementers should not simply display the code, but map the concept into their application
Definition | An explanation of the meaning of the concept
Comments | Additional notes about how to use the code

4.2.12.511 Code System http://hl7.org/fhir/service-category

URL: https://hl7.org/fhir/STU3/codesystem-service-category.html

This page is part of the FHIR Specification (v3.0.2: STU 3). The current version which supercedes this version is 4.0.1. For a full list of available versions, see the Directory of published versions

Vocabulary Work Group | Maturity Level: 1 | Informative | Use Context: Not Intended for Production use

This is a code system defined by the FHIR project.

Summary

Defining URL: | http://hl7.org/fhir/service-category
Name: | ServiceCategory
Definition: | This value set defines an example set of codes that can be used to classify groupings of service-types/specialties.
Committee: | Patient Administration Work Group
OID: | 2.16.840.1.113883.4.642.1.511 (for OID based terminology systems)
Source Resource | XML / JSON

This Code system is used in the following value sets:

* ServiceCategory (This value set defines an example set of codes that can be used to classify groupings of service-types/specialties.)

4.2.12.511.1 Content

4.2.12.511.2 ServiceCategory

This value set defines an example set of codes that can be used to classify groupings of service-types/specialties.

This code system http://hl7.org/fhir/service-category defines many codes, of which the following are some examples:

Code | Display | Definition
1 | Adoption | Adoption
2 | Aged Care | Aged Care
34 | Allied Health | Allied Health
3 | Alternative/Complementary Therapies | Alternative & Complementary Therapies
4 | Child Care /Kindergarten | Child Care and/or Kindergarten

5 | Child Development | Child Development
6 | Child Protection & Family Services | Child Protection & Family Services
7 | Community Health Care | Community Health Care
8 | Counselling | Counselling
36 | Crisis Line (GPAH use only) | Crisis Line (GPAH use only)
9 | Death Services | Death Services
10 | Dental | Dental
11 | Disability Support | Disability Support
12 | Drug/Alcohol | Drug/Alcohol
13 | Education & Learning | Education & Learning
14 | Emergency Department | Emergency Department
15 | Employment | Employment
16 | Financial & Material Aid | Financial & Material aid
17 | General Practice | General Practice/GP (doctor)
35 | Hospital | Hospital
18 | Housing/Homelessness | Housing/Homelessness
19 | Interpreting | Interpreting
20 | Justice | Justice
21 | Legal | Legal
22 | Mental Health | Mental Health
38 | NDIA | NDIA
23 | Physical Activity & Recreation | Physical Activity & Recreation
24 | Regulation | Regulation
25 | Respite/Carer Support | Respite/Carer Support
26 | Specialist Clinical Pathology | Specialist Clinical Pathology - requires referral
27 | Specialist Medical | Specialist Medical - requires referral
28 | Specialist Obstetrics & Gynaecology | Specialist Obstetrics & Gynaecology - requires referral
29 | Specialist Paediatric | Specialist Paediatric - requires referral
30 | Specialist Radiology/Imaging | Specialist Radiology/Imaging - requires referral
31 | Specialist Surgical | Specialist Surgical - requires referral
32 | Support Group/s | Support group/s
37 | Test Message (HSD admin) | Test Message (HSD admin use only)
33 | Transport | Transport

See the full registry of value sets defined as part of FHIR.

Explanation of the columns that may appear on this page:

Level | A few code lists that FHIR defines are hierarchical - each code is assigned a level. In this scheme, some codes are under other codes, and imply that the code they are under also applies
Source | The source of the definition of the code (when the value set draws in codes defined elsewhere)
Code | The code (used as the code in the resource instance). If the code is in italics, this indicates that the code is not selectable ('Abstract')
Display | The display (used in the display element of a Coding). If there is no display, implementers should not simply display the code, but map the concept into their application
Definition | An explanation of the meaning of the concept
Comments | Additional notes about how to use the code

4.2.12.513 Code System http://hl7.org/fhir/service-type

URL: https://hl7.org/fhir/STU3/codesystem-service-type.html

This page is part of the FHIR Specification (v3.0.2: STU 3). The current version which supercedes this version is 4.0.1. For a full list of available versions, see the Directory of published versions

Vocabulary Work Group | Maturity Level: 1 | Informative | Use Context: Not Intended for Production use

This is a code system defined by the FHIR project.

Summary

Defining URL: | http://hl7.org/fhir/service-type
Name: | ServiceType
Definition: | This value set defines an example set of codes of service-types.
Committee: | Patient Administration Work Group
OID: | 2.16.840.1.113883.4.642.1.513 (for OID based terminology systems)
Source Resource | XML / JSON

This Code system is used in the following value sets:

* ServiceType (This value set defines an example set of codes of service-types.)

4.2.12.513.1 Content

4.2.12.513.2 ServiceType

This value set defines an example set of codes of service-types.

This code system http://hl7.org/fhir/service-type defines many codes, of which the following are some examples:

Code | Display | Definition

1 | Adoption/Permanent Care Info/Support | Adoption & permanent care information/support
2 | Aged Care Assessment | Aged care assessment
3 | Aged Care Information/Referral | Aged Care information/referral
4 | Aged Residential Care | Aged Residential Care
5 | Case Management for Older Persons | Case management for older persons
6 | Delivered Meals (Meals On Wheels) | Delivered meals (meals on wheels)
7 | Friendly Visiting | Friendly visiting
8 | Home Care/Housekeeping Assistance | Home care/housekeeping assistance
9 | Home Maintenance and Repair | Home maintenance and repair
10 | Personal Alarms/Alerts | Personal alarms/alerts
11 | Personal Care for Older Persons | Personal care for older persons
12 | Planned Activity Groups | Planned activity groups
13 | Acupuncture | Acupuncture
14 | Alexander Technique Therapy | Alexander technique therapy
15 | Aromatherapy | Aromatherapy
16 | Biorhythm Services | Biorhythm services
17 | Bowen Therapy | Bowen therapy
18 | Chinese Herbal Medicine | Chinese herbal medicine
19 | Feldenkrais | Feldenkrais
20 | Homoeopathy | Homoeopathy
21 | Hydrotherapy | Hydrotherapy
22 | Hypnotherapy | Hypnotherapy
23 | Kinesiology | Kinesiology
24 | Magnetic Therapy | Magnetic therapy
25 | Massage Therapy | Massage therapy
26 | Meditation | Meditation
27 | Myotherapy | Myotherapy
28 | Naturopathy | Naturopathy
29 | Reflexology | Reflexology
30 | Reiki | Reiki
31 | Relaxation Therapy | Relaxation therapy
32 | Shiatsu | Shiatsu
33 | Western Herbal Medicine | Western herbal medicine
34 | Family Day care | Family day care
35 | Holiday Programs | Holiday programs
36 | Kindergarten Inclusion Support | Kindergarten inclusion support for children with a disability
37 | Kindergarten/Preschool | Kindergarten/preschool
38 | Long Day Child Care | Long day child care
39 | Occasional Child Care | Occasional child care
40 | Outside School Hours Care | Outside school hours care
41 | Children's Play Programs | Children's play programs
42 | Parenting/Family Support/Education | Parenting & family management support/education
43 | Playgroup | Playgroup
44 | School Nursing | School nursing
45 | Toy Library | Toy library
46 | Child Protection/Child Abuse Report | Child protection/child abuse report
47 | Foster Care | Foster care
48 | Residential/Out-of-Home Care | Residential/ out of home care
49 | Support - Young People Leaving Care | Support for young people leaving care
50 | Audiology | Audiology
51 | Blood Donation | Blood donation
52 | Chiropractic | Chiropractic
53 | Dietetics | Dietetics
54 | Family Planning | Family planning
55 | Health Advocacy/Liaison Service | Health advocacy/Liaison service
56 | Health Information/Referral | Health information/referral
57 | Immunization | Immunization
58 | Maternal & Child Health | Maternal & child health
59 | Nursing | Nursing
60 | Nutrition | Nutrition
61 | Occupational Therapy | Occupational therapy
62 | Optometry | Optometry
63 | Osteopathy | Osteopathy
64 | Pharmacy | Pharmacy
65 | Physiotherapy | Physiotherapy
66 | Podiatry | Podiatry
67 | Sexual Health | Sexual health
68 | Speech Pathology/Therapy | Speech pathology/therapy
69 | Bereavement Counselling | Bereavement counselling
70 | Crisis Counselling | Crisis counselling
71 | Family Counselling/Therapy | Family counselling and/or family therapy
72 | Family Violence Counselling | Family violence counselling

73 | Financial Counselling | Financial counselling
74 | Generalist Counselling | Generalist counselling
75 | Genetic Counselling | Genetic counselling
76 | Health Counselling | Health counselling
77 | Mediation | Mediation
78 | Problem Gambling Counselling | Problem gambling counselling
79 | Relationship Counselling | Relationship counselling
80 | Sexual Assault Counselling | Sexual assault counselling
81 | Trauma Counselling | Trauma counselling
82 | Victims of Crime Counselling | Victims of crime counselling
83 | Cemetery Operation | Cemetery operation
84 | Cremation | Cremation
85 | Death Service Information | Death service information
86 | Funeral Services | Funeral services
87 | Endodontic | Endodontic
88 | General Dental | General dental
89 | Oral Medicine | Oral medicine
90 | Oral Surgery | Oral surgery
91 | Orthodontic | Orthodontic
92 | Paediatric Dentistry | Paediatric Dentistry
93 | Periodontic | Periodontic
94 | Prosthodontic | Prosthodontic
95 | Acquired Brain Injury Info/Referral | Acquired brain injury information/referral
96 | Disability Advocacy | Disability advocacy
97 | Disability Aids & Equipment | Disability aids & equipment
98 | Disability Case Management | Disability case management
99 | Disability Day Programs/Activities | Disability day programs & activities
100 | Disability Information/Referral | Disability information/referral
101 | Disability Support Packages | Disability support packages
102 | Disability Supported Accommodation | Disability supported accommodation
103 | Early Childhood Intervention | Early childhood intervention
104 | Hearing Aids & Equipment | Hearing aids & equipment
105 | Drug and/or Alcohol Counselling | Drug and/or alcohol counselling
106 | Drug/Alcohol Information/Referral | Drug and/or alcohol information/referral
107 | Needle & Syringe Exchange | Needle & Syringe exchange
108 | Non-resid. Alcohol/Drug Treatment | Non-residential alcohol and/or drug dependence treatment
109 | Pharmacotherapy | Pharmacotherapy (eg. methadone) program
110 | Quit Program | Quit program
111 | Residential Alcohol/Drug Treatment | Residential alcohol and/or drug dependence treatment
112 | Adult/Community Education | Adult/community education
113 | Higher Education | Higher education
114 | Primary Education | Primary education
115 | Secondary Education | Secondary education
116 | Training & Vocational Education | Training & vocational education
117 | Emergency Medical | Emergency medical
118 | Employment Placement and/or Support | Employment placement and/or support
119 | Vocational Rehabilitation | Vocational Rehabilitation
120 | Work Safety/Accident Prevention | Workplace safety and/or accident prevention
121 | Financial Assistance | Financial assistance
122 | Financial Information/Advice | Financial information/advice
123 | Material Aid | Material aid
124 | General Practice | General Practice/GP (doctor)
125 | Accommodation Placement/Support | Accommodation placement and/or support
126 | Crisis/Emergency Accommodation | Crisis/emergency accommodation
127 | Homelessness Support | Homelessness support
128 | Housing Information/Referral | Housing information/referral
129 | Public Rental Housing | Public rental housing
130 | Interpreting/Multilingual Service | Interpreting/Multilingual/Language service
131 | Juvenile Justice | Juvenile Justice
132 | Legal Advocacy | Legal advocacy
133 | Legal Information/Advice/Referral | Legal information/advice/referral
134 | Mental Health Advocacy | Mental health advocacy
135 | Mental Health Assess/Triage/Crisis Response | Mental health assessment/triage/crisis response
136 | Mental Health Case Management | Mental health case management/continuing care
137 | Mental Health Information/Referral | Mental health information/referral
138 | Mental Health Inpatient Services | Mental health inpatient services (hospital psychiatric unit) - requires referral
139 | Mental Health Non-residential Rehab | Mental health non-residential rehabilitation
140 | Mental Health Residential Rehab/CCU | Mental health residential rehabilitation/community care unit
141 | Psychiatry (Requires Referral) | Psychiatry (requires referral)
142 | Psychology | Psychology
143 | Martial Arts | Martial arts
144 | Personal Fitness Training | Personal fitness training

145 | Physical Activity Group | Physical activity group
146 | Physical Activity Programs | Physical activity programs
147 | Physical Fitness Testing | Physical fitness testing
148 | Pilates | Pilates
149 | Self-Defence | Self defence
150 | Sporting Club | Sporting club
151 | Yoga | Yoga
152 | Food Safety | Food safety
153 | Health Regulatory /Inspection /Cert. | Health regulatory, inspection and/or certification
154 | Work Health/Safety Inspection/Cert. | Workplace health and/or safety inspection and/or certification
155 | Carer Support | Carer support
156 | Respite Care | Respite care
157 | Anatomical Pathology | Anatomical Pathology (including Cytopathology & Forensic Pathology)
158 | Pathology - Clinical Chemistry | Pathology - Clinical Chemistry
159 | Pathology - General | Pathology - General
160 | Pathology - Genetics | Pathology - Genetics
161 | Pathology - Haematology | Pathology - Haematology
162 | Pathology - Immunology | Pathology - Immunology
163 | Pathology - Microbiology | Pathology - Microbiology
164 | Anaesthesiology - Pain Medicine | Anaesthesiology - Pain Medicine
165 | Cardiology | Cardiology
166 | Clinical Genetics | Clinical Genetics
167 | Clinical Pharmacology | Clinical Pharmacology
168 | Dermatology | Dermatology
169 | Endocrinology | Endocrinology
170 | Gastroenterology & Hepatology | Gastroenterology & Hepatology
171 | Geriatric Medicine | Geriatric medicine
172 | Immunology & Allergy | Immunology & Allergy
173 | Infectious Diseases | Infectious diseases
174 | Intensive Care Medicine | Intensive care medicine
175 | Medical Oncology | Medical Oncology
176 | Nephrology | Nephrology
177 | Neurology | Neurology
178 | Occupational Medicine | Occupational Medicine
179 | Palliative Medicine | Palliative Medicine
180 | Public Health Medicine | Public Health Medicine
181 | Rehabilitation Medicine | Rehabilitation Medicine
182 | Rheumatology | Rheumatology
183 | Sleep Medicine | Sleep Medicine
184 | Thoracic Medicine | Thoracic medicine
185 | Gynaecological Oncology | Gynaecological Oncology
186 | Obstetrics & Gynaecology | Obstetrics & Gynaecology
187 | Reproductive Endocrinology/Infertility | Reproductive Endocrinology & Infertility
188 | Urogynaecology | Urogynaecology
189 | Neonatology & Perinatology | Neonatology & Perinatology
190 | Paediatric Cardiology | Paediatric Cardiology
191 | Paediatric Clinical Genetics | Paediatric Clinical Genetics
192 | Paediatric Clinical Pharmacology | Paediatric Clinical Pharmacology
193 | Paediatric Endocrinology | Paediatric Endocrinology
194 | Paed. Gastroenterology/Hepatology | Paediatric Gastroenterology & Hepatology
195 | Paediatric Haematology | Paediatric Haematology
196 | Paediatric Immunology & Allergy | Paediatric Immunology & Allergy
197 | Paediatric Infectious Diseases | Paediatric Infectious diseases
198 | Paediatric Intensive Care Medicine | Paediatric intensive care medicine
199 | Paediatric Medical Oncology | Paediatric Medical Oncology
200 | Paediatric Medicine | Paediatric Medicine
201 | Paediatric Nephrology | Paediatric Nephrology
202 | Paediatric Neurology | Paediatric Neurology
203 | Paediatric Nuclear Medicine | Paediatric Nuclear Medicine
204 | Paediatric Rehabilitation Medicine | Paediatric Rehabilitation Medicine
205 | Paediatric Rheumatology | Paediatric Rheumatology
206 | Paediatric Sleep Medicine | Paediatric Sleep Medicine
207 | Paediatric Surgery | Paediatric Surgery
208 | Paediatric Thoracic Medicine | Paediatric Thoracic Medicine
209 | Diag. Radiology /Xray /CT /Fluoroscopy | Diagnostic Radiology/Xray/CT/Fluoroscopy
210 | Diagnostic Ultrasound | Diagnostic Ultrasound
211 | Magnetic Resonance Imaging (MRI) | Magnetic Resonance Imaging (MRI)
212 | Nuclear Medicine | Nuclear Medicine
213 | Obstetric/Gynaecological Ultrasound | Obstetric & Gynaecological Ultrasound
214 | Radiation Oncology | Radiation oncology
215 | Cardiothoracic Surgery | Cardiothoracic surgery
216 | Neurosurgery | Neurosurgery

217 | Ophthalmology | Ophthalmology
218 | Orthopaedic Surgery | Orthopaedic surgery
219 | Otolaryngology/Head & Neck Surgery | Otolaryngology - Head & Neck Surgery
220 | Plastic & Reconstructive Surgery | Plastic & Reconstructive Surgery
221 | Surgery - General | Surgery - General
222 | Urology | Urology
223 | Vascular Surgery | Vascular surgery
224 | Support Groups | Support groups
225 | Air ambulance | Air ambulance
226 | Ambulance | Ambulance
227 | Blood Transport | Blood transport
228 | Community Bus | Community bus
229 | Flying Doctor Service | Flying doctor service
230 | Patient Transport | Patient transport
231 | A&E | A&E
232 | A&EP | A&EP
233 | Abuse | Abuse
234 | ACAS | ACAS
235 | Access | Access
236 | Accident | Accident
237 | Acute Inpatient Serv | Acute Inpatient Service's
238 | Adult Day Programs | Adult Day Programs
239 | Adult Mental Health Services | Adult Mental Health Services
240 | Advice | Advice
241 | Advocacy | Advocacy
242 | Aged Persons Mental | Aged Persons Mental Health Residential Units
243 | Aged Persons Mental | Aged Persons Mental Health Services
244 | Aged Persons Mental | Aged Persons Mental Health Teams
245 | Aids | Aids
246 | Al-Anon | Al-Anon
247 | Alcohol | Alcohol
248 | Al-Teen | Al-Teen
249 | Antenatal | Antenatal
250 | Anxiety | Anxiety
251 | Arthritis | Arthritis
252 | Assessment | Assessment
253 | Assistance | Assistance
254 | Asthma | Asthma
255 | ATSS | ATSS
256 | Attendant Care | Attendant Care
257 | Babies | Babies
258 | Bathroom Modificatio | Bathroom Modification
259 | Behaviour | Behaviour
260 | Behaviour Interventi | Behaviour Intervention
261 | Bereavement | Bereavement
262 | Bipolar | Bipolar
263 | Birth | Birth
264 | Birth Control | Birth Control
265 | Birthing Options | Birthing Options
266 | BIST | BIST
267 | Blood | Blood
268 | Bone | Bone
269 | Bowel | Bowel
270 | Brain | Brain
271 | Breast Feeding | Breast Feeding
272 | Breast Screen | Breast Screen
273 | Brokerage | Brokerage
274 | Cancer | Cancer
275 | Cancer Support | Cancer Support
276 | Cardiovascular Disea | Cardiovascular Disease
277 | Care Packages | Care Packages
278 | Carer | Carer
279 | Case Management | Case Management
280 | Casualty | Casualty
281 | Centrelink | Centrelink
282 | Chemists | Chemists
283 | Child And Adolescent | Child And Adolescent Mental Health Services
284 | Child Care | Child Care
285 | Child Services | Child Services
286 | Children | Children
287 | Children's Services | Children's Services
288 | Cholesterol | Cholesterol

289 | Clothing | Clothing
290 | Community Based Acco | Community Based Accommodation
291 | Community Care Unit | Community Care Unit
292 | Community Child And | Community Child And Adolescent Mental Health Services
293 | Community Health | Community Health
294 | Community Residentia | Community Residential Unit
295 | Community Transport | Community Transport
296 | Companion Visiting | Companion Visiting
297 | Companionship | Companionship
298 | Consumer Advice | Consumer Advice
299 | Consumer Issues | Consumer Issues
300 | Continuing Care Serv | Continuing Care Services
301 | Contraception Inform | Contraception Information
302 | Coordinating Bodies | Coordinating Bodies
303 | Correctional Service | Correctional Services
304 | Council Environmenta | Council Environmental Health
305 | Counselling | Counselling
306 | Criminal | Criminal
307 | Crises | Crises
308 | Crisis Assessment An | Crisis Assessment And Treatment Services (Cats)
309 | Crisis Assistance | Crisis Assistance
310 | Crisis Refuge | Crisis Refuge
311 | Day Program | Day Program
312 | Deaf | Deaf
313 | Dental Hygiene | Dental Hygiene
314 | Dentistry | Dentistry
315 | Dentures | Dentures
316 | Depression | Depression
317 | Detoxification | Detoxification
318 | Diabetes | Diabetes
319 | Diaphragm Fitting | Diaphragm Fitting
320 | Dieticians | Dieticians
321 | Disabled Parking | Disabled Parking
322 | District Nursing | District Nursing
323 | Divorce | Divorce
324 | Doctors | Doctors
325 | Drink-Drive | Drink-Drive
326 | Dual Diagnosis Servi | Dual Diagnosis Services
327 | Early Choice | Early Choice
328 | Eating Disorder | Eating Disorder
330 | Emergency Relief | Emergency Relief
331 | Employment And Train | Employment And Training
332 | Environment | Environment
333 | Equipment | Equipment
334 | Exercise | Exercise
335 | Facility | Facility
336 | Family Choice | Family Choice
337 | Family Law | Family Law
338 | Family Options | Family Options
339 | Family Services | Family Services
340 | FFYA | FFYA
341 | Financial Aid | Financial Aid
342 | Fitness | Fitness
343 | Flexible Care Packag | Flexible Care Packages
344 | Food | Food
345 | Food Vouchers | Food Vouchers
346 | Forensic Mental Heal | Forensic Mental Health Services
347 | Futures | Futures
348 | Futures For Young Ad | Futures For Young Adults
349 | General Practitioner | General Practitioners
350 | Grants | Grants
351 | Grief | Grief
352 | Grief Counselling | Grief Counselling
353 | HACC | HACC
354 | Heart Disease | Heart Disease
355 | Help | Help
356 | High Blood Pressure | High Blood Pressure
357 | Home Help | Home Help
358 | Home Nursing | Home Nursing
359 | Homefirst | Homefirst
360 | Hospice Care | Hospice Care
361 | Hospital Services | Hospital Services

362 | Hospital To Home | Hospital To Home
364 | Hostel | Hostel
365 | Hostel Accommodation | Hostel Accommodation
366 | Household Items | Household Items
367 | Hypertension | Hypertension
368 | Illness | Illness
369 | Independent Living | Independent Living
370 | Information | Information
371 | Injury | Injury
372 | Intake | Intake
373 | Intensive Mobile You | Intensive Mobile Youth Outreach Services (Imyos)
374 | Intervention | Intervention
375 | Job Searching | Job Searching
376 | Justice | Justice
377 | Leisure | Leisure
378 | Loans | Loans
379 | Low Income Earners | Low Income Earners
380 | Lung | Lung
381 | Making A Difference | Making A Difference
382 | Medical Services | Medical Services
383 | Medical Specialists | Medical Specialists
384 | Medication Administr | Medication Administration
385 | Menstrual Informatio | Menstrual Information
386 | Methadone | Methadone
387 | Mobile Support And T | Mobile Support And Treatment Services (MSTS)
388 | Motor Neurone | Motor Neurone
389 | Multiple Sclerosis | Multiple Sclerosis
390 | Neighbourhood House | Neighbourhood House
391 | Nursing Home | Nursing Home
392 | Nursing Mothers | Nursing Mothers
393 | Obesity | Obesity
394 | Occupational Health | Occupational Health & Safety
395 | Optometrist | Optometrist
396 | Oral Hygiene | Oral Hygiene
397 | Outpatients | Outpatients
398 | Outreach Service | Outreach Service
399 | PADP | PADP
400 | Pain | Pain
401 | Pap Smear | Pap Smear
402 | Parenting | Parenting
403 | Peak Organisations | Peak Organisations
404 | Personal Care | Personal Care
405 | Pharmacies | Pharmacies
406 | Phobias | Phobias
407 | Physical | Physical
408 | Physical Activity | Physical Activity
409 | Postnatal | Postnatal
410 | Pregnancy | Pregnancy
411 | Pregnancy Tests | Pregnancy Tests
412 | Preschool | Preschool
413 | Prescriptions | Prescriptions
414 | Primary Mental Healt | Primary Mental Health And Early Intervention Teams
415 | Property Maintenance | Property Maintenance
416 | Prostate | Prostate
417 | Psychiatric | Psychiatric
418 | Psychiatric Disabili | Psychiatric Disability Support Services - Home-Based Outreach
419 | Psychiatric Disabili | Psychiatric Disability Support Services - Planned Respite
420 | Psychiatric Disabili | Psychiatric Disability Support Services - Residential Rehabilitation
421 | Psychiatric Disabili | Psychiatric Disability Support Services Home-Based Outreach
422 | Psychiatric Disabili | Psychiatric Disability Support Services Mutual Support And Self Help
423 | Psychiatric Support | Psychiatric Support
424 | Recreation | Recreation
425 | Referral | Referral
426 | Refuge | Refuge
427 | Rent Assistance | Rent Assistance
428 | Residential Faciliti | Residential Facilities
429 | Residential Respite | Residential Respite
430 | Respiratory | Respiratory
431 | Response | Response
432 | Rooming Houses | Rooming Houses
433 | Safe Sex | Safe Sex
434 | Secure Extended Care | Secure Extended Care Inpatient Services

435 | Self Help | Self Help
436 | Separation | Separation
437 | Services | Services
438 | Sex Education | Sex Education
439 | Sexual Abuse | Sexual Abuse
440 | Sexual Issues | Sexual Issues
441 | Sexually Transmitted | Sexually Transmitted Diseases
442 | SIDS | SIDS
443 | Social Support | Social Support
444 | Socialisation | Socialisation
445 | Special Needs | Special Needs
446 | Speech Therapist | Speech Therapist
447 | Splinting | Splinting
448 | Sport | Sport
449 | Statewide And Specia | Statewide And Specialist Services
450 | STD | STD
451 | STI | STI
452 | Stillbirth | Stillbirth
453 | Stomal Care | Stomal Care
454 | Stroke | Stroke
455 | Substance Abuse | Substance Abuse
456 | Support | Support
457 | Syringes | Syringes
458 | Teeth | Teeth
459 | Tenancy Advice | Tenancy Advice
460 | Terminal Illness | Terminal Illness
461 | Therapy | Therapy
462 | Transcription | Transcription
463 | Translating Services | Translating Services
464 | Translator | Translator
465 | Transport | Transport
466 | Vertebrae | Vertebrae
467 | Violence | Violence
468 | Vocational Guidance | Vocational Guidance
469 | Weight | Weight
470 | Welfare Assistance | Welfare Assistance
471 | Welfare Counselling | Welfare Counselling
472 | Wheelchairs | Wheelchairs
473 | Wound Management | Wound Management
474 | Young People At Risk | Young People At Risk
475 | Further Desc. - Community Health Care | Further Description - Community Health Care
476 | Library | Library
477 | Community Hours | Community Hours
478 | Further Desc. - Specialist Medical | Further Description - Specialist Medical
479 | Hepatology | Hepatology
480 | Gastroenterology | Gastroenterology
481 | Gynaecology | Gynaecology
482 | Obstetrics | Obstetrics
483 | Further Desc. - Specialist Surgical | Further Description - Specialist Surgical
484 | Placement Protection | Placement Protection
485 | Family Violence | Family Violence
486 | Integrated Family Services | Integrated Family Services
488 | Diabetes Educator | Diabetes Educator
489 | Kinship Care | Kinship Care
490 | General Mental Health Services | General Mental Health Services
491 | Exercise Physiology | Exercise Physiology
492 | Medical Research | Medical Research
493 | Youth | Youth
494 | Youth Services | Youth Services
495 | Youth Health | Youth Health
496 | Child and Family Ser | Child and Family Services
497 | Home Visits | Home Visits
498 | Mobile Services | Mobile Services
500 | Before and/or After | Before and/or After School Care
501 | Cancer Services | Cancer Services
502 | Integrated Cancer Se | Integrated Cancer Services
503 | Multidisciplinary Se | Multidisciplinary Services
504 | Multidisciplinary Ca | Multidisciplinary Cancer Services
505 | Meetings | Meetings
506 | Blood pressure monit | Blood pressure monitoring
507 | Dose administration | Dose administration aid
508 | Medical Equipment Hi | Medical Equipment Hire

509 | Parenting/Family Support/Education | Parenting & family support/education
510 | Deputising Service | Deputising Service
513 | Cancer Support Groups | Cancer Support Groups
514 | Community Cancer Services | Community Cancer Services
530 | Disability Care Transport | Disability Care Transport
531 | Aged Care Transport | Aged Care Transport
532 | Diabetes Education s | Diabetes Education service
533 | Cardiac Rehabilitati | Cardiac Rehabilitation Service
534 | Young Adult Diabetes | Young Adult Diabetes services (YADS)
535 | Pulmonary Rehabilita | Pulmonary Rehabilitation Service
536 | Art therapy | Art therapy
537 | Medication Reviews | Medication Reviews
538 | Telephone Counselling | Telephone Counselling
539 | Telephone Help Line | Telephone Help Line
540 | Online Service | Online Service
541 | Crisis - Mental Health | Crisis - Mental Health
542 | Youth Crisis | Youth Crisis
543 | Sexual Assault | Sexual Assault
544 | GPAH Other | GPAH Other
545 | Paediatric Dermatology | Paediatric Dermatology
546 | Veterans Services | Veterans Services
547 | Veterans | Veterans
548 | Food Relief/Food/Meals | Food Relief/food/meals
550 | Dementia Care | Dementia Care
551 | Alzheimer | Alzheimer
552 | Drug and/or Alcohol Support Groups | Drug and/or alcohol support groups
553 | 1-on-1 Support /Mentoring /Coaching | One on One Support/Mentoring/Coaching
554 | Chronic Disease Management | Chronic Disease Management
555 | Liaison Services | Liaison Services
556 | Walk-in Centre /Non-Emergency | Walk in Centre / non emergency
557 | Inpatients | Inpatients
558 | Spiritual Counselling | Spiritual Counselling
559 | Women's Health | Women's Health
560 | Men's Health | Men's Health
561 | Health Education/Awareness Program | Health education/Health awareness program
562 | Test Message | Test Message
563 | Remedial Massage | Remedial Massage
564 | Adolescent Mental Health Services | Adolescent Mental Health Services
565 | Youth Drop In/Assistance/Support | Youth drop in/assistance/support
566 | Aboriginal Health Worker | Aboriginal Health Worker
567 | Women's Health Clinic | Women's Health Clinic
568 | Men's Health Clinic | Men's Health Clinic
569 | Migrant Health Clinic | Migrant Health Clinic
570 | Refugee Health Clinic | Refugee Health Clinic
571 | Aboriginal Health Clinic | Aboriginal Health Clinic
572 | Nurse Practitioner Lead Clinic/s | Nurse Practitioner lead Clinic/s
573 | Nurse Lead Clinic/s | Nurse lead Clinic/s
574 | Culturally Tailored Support Groups | Culturally tailored support groups
575 | Culturally Tailored Health Promotion | Culturally tailored health promotion
576 | Rehabilitation | Rehabilitation
577 | Education Information/Referral | Education information/referral
580 | Social Work | Social Work
581 | Haematology | Haematology
582 | Maternity Shared Car | Maternity Shared Care
583 | Rehabilitation Servi | Rehabilitation Service
584 | Cranio-sacral Therapy | Cranio-Sacral Therapy
585 | Prosthetics & Orthotics | Prosthetics & Orthotics
589 | Home Medicine Review | Home Medicine Review
590 | GPAH - Medical | GPAH - Medical
591 | Music Therapy | Music Therapy
593 | Falls Prevention | Falls Prevention
599 | Accommodation/Tenancy | Accommodation/Tenancy
600 | Assess-Skill, Ability, Needs | Assess-Skill, Ability, Needs
601 | Assist Access/Maintain Employ | Assist Access/Maintain Employ
602 | Assist Prod-Pers Care/Safety | Assist Prod-Pers Care/Safety
603 | Assist-Integrate School/Ed | Assist-Integrate School/Ed
604 | Assist-Life Stage, Transition | Assist-Life Stage, Transition
605 | Assist-Personal Activities | Assist-Personal Activities
606 | Assist-Travel/Transport | Assist-Travel/Transport
607 | Assistive Equip-General Tasks | Assistive Equip-General Tasks
608 | Assistive Equip-Recreation | Assistive Equip-Recreation
609 | Assistive Prod-Household Task | Assistive Prod-Household Task

610 | Behaviour Support | Behaviour Support
611 | Comms & Info Equipment | Comms & Info Equipment
612 | Community Nursing Care | Community Nursing Care
613 | Daily Tasks/Shared Living | Daily Tasks/Shared Living
614 | Development-Life Skills | Development-Life Skills
615 | Early Childhood Supports | Early Childhood Supports
616 | Equipment Special Assess Setup | Equipment Special Assess Setup
617 | Hearing Equipment | Hearing Equipment
618 | Home Modification | Home Modification
619 | Household Tasks | Household Tasks
620 | Interpret/Translate | Interpret/Translate
621 | Other Innovative Supports | Other Innovative Supports
622 | Participate Community | Participate Community
623 | Personal Mobility Equipment | Personal Mobility Equipment
624 | Physical Wellbeing | Physical Wellbeing
625 | Plan Management | Plan Management
626 | Therapeutic Supports | Therapeutic Supports
627 | Training-Travel Independence | Training-Travel Independence
628 | Vehicle modifications | Vehicle modifications
629 | Vision Equipment | Vision Equipment

See the full registry of value sets defined as part of FHIR.

Explanation of the columns that may appear on this page:

Level | A few code lists that FHIR defines are hierarchical - each code is assigned a level. In this scheme, some codes are under other codes, and imply that the code they are under also applies
Source | The source of the definition of the code (when the value set draws in codes defined elsewhere)
Code | The code (used as the code in the resource instance). If the code is in italics, this indicates that the code is not selectable ('Abstract')
Display | The display (used in the display element of a Coding). If there is no display, implementers should not simply display the code, but map the concept into their application
Definition | An explanation of the meaning of the concept
Comments | Additional notes about how to use the code

4.2.12.516 Code System http://hl7.org/fhir/policyholder-relationship

URL: https://hl7.org/fhir/STU3/codesystem-policyholder-relationship.html

This page is part of the FHIR Specification (v3.0.2: STU 3). The current version which supercedes this version is 4.0.1. For a full list of available versions, see the Directory of published versions

Vocabulary Work Group | Maturity Level: 1 | Informative | Use Context: Not Intended for Production use

This is a code system defined by the FHIR project.

Summary

Defining URL: | http://hl7.org/fhir/policyholder-relationship
Name: | Policyholder Relationship Codes
Definition: | This value set includes codes for the relationship between the Policyholder and the Beneficiary (insured/covered party/patient)..
Committee: | Financial Management Work Group
OID: | 2.16.840.1.113883.4.642.1.516 (for OID based terminology systems)
Copyright: | This is an example set.
Source Resource | XML / JSON

This Code system is used in the following value sets:

* Policyholder Relationship Codes (This value set includes codes for the relationship between the Policyholder and the Beneficiary (insured/covered party/patient)..)

4.2.12.516.1 Content

4.2.12.516.2 Policyholder Relationship Codes

This value set includes codes for the relationship between the Policyholder and the Beneficiary (insured/covered party/patient)..

Copyright Statement: This is an example set.

This code system http://hl7.org/fhir/policyholder-relationship defines the following codes:

Code | Display | Definition
child | Child | The Beneficiary is a child of the Policyholder
parent | Parent | The Beneficiary is a parent of the Policyholder
spouse | Spouse | The Beneficiary is a spouse or equivalent of the Policyholder
common | Common Law Spouse | The Beneficiary is a common law spouse or equivalent of the Policyholder
other | Other | The Beneficiary has some other relationship the Policyholder
self | Self | The Beneficiary is the Policyholder

See the full registry of value sets defined as part of FHIR.

Explanation of the columns that may appear on this page:

Level | A few code lists that FHIR defines are hierarchical - each code is assigned a level. In this scheme, some codes are under other codes, and imply that the code they are under also applies
Source | The source of the definition of the code (when the value set draws in codes defined elsewhere)
Code | The code (used as the code in the resource instance). If the code is in italics, this indicates that the code is not selectable ('Abstract')
Display | The display (used in the display element of a Coding). If there is no display, implementers should not simply display the code, but map the concept into their application
Definition | An explanation of the meaning of the concept
Comments | Additional notes about how to use the code

4.2.12.518 Code System http://hl7.org/fhir/coverage-level

URL: https://hl7.org/fhir/STU3/codesystem-coverage-level.html

This page is part of the FHIR Specification (v3.0.2: STU 3). The current version which supercedes this version is 4.0.1. For a full list of available versions, see the Directory of published versions

Vocabulary Work Group | Maturity Level: 0 | Informative | Use Context: Not Intended for Production use

This is a code system defined by the FHIR project.

Summary

Defining URL: | http://hl7.org/fhir/coverage-level
Name: | Coverage Level Codes
Definition: | This value set includes sample Coverage Level codes.
Committee: | Financial Management Work Group
OID: | 2.16.840.1.113883.4.642.1.518 (for OID based terminology systems)
Copyright: | This is an example set.
Source Resource | XML / JSON

This Code system is used in the following value sets:

* Coverage Level Codes (This value set includes sample Coverage Level codes.)

4.2.12.518.1 Content

4.2.12.518.2 Coverage Level Codes

This value set includes sample Coverage Level codes.

Copyright Statement: This is an example set.

This code system http://hl7.org/fhir/coverage-level defines the following codes:

Code | Display | Definition
group | Group | An employee group
subgroup | SubGroup | A sub-group of an employee group
plan | Plan | A specific suite of benefits.
subplan | SubPlan | A subset of a specific suite of benefits.
class | Class | A class of benefits.
subclass | SubClass | A subset of a class of benefits.

See the full registry of value sets defined as part of FHIR.

Explanation of the columns that may appear on this page:

Level | A few code lists that FHIR defines are hierarchical - each code is assigned a level. In this scheme, some codes are under other codes, and imply that the code they are under also applies
Source | The source of the definition of the code (when the value set draws in codes defined elsewhere)
Code | The code (used as the code in the resource instance). If the code is in italics, this indicates that the code is not selectable ('Abstract')
Display | The display (used in the display element of a Coding). If there is no display, implementers should not simply display the code, but map the concept into their application
Definition | An explanation of the meaning of the concept
Comments | Additional notes about how to use the code

4.2.12.520 Code System http://hl7.org/fhir/coverage-selfpay

URL: https://hl7.org/fhir/STU3/codesystem-coverage-selfpay.html

This page is part of the FHIR Specification (v3.0.2: STU 3). The current version which supercedes this version is 4.0.1. For a full list of available versions, see the Directory of published versions

Vocabulary Work Group | Maturity Level: 0 | Informative | Use Context: Not Intended for Production use

This is a code system defined by the FHIR project.

Summary

Defining URL: | http://hl7.org/fhir/coverage-selfpay
Name: | Coverage SelfPay Codes
Definition: | This value set includes Coverage SelfPay codes.
Committee: | Financial Management Work Group
OID: | 2.16.840.1.113883.4.642.1.520 (for OID based terminology systems)
Copyright: | HL7 International.

Source Resource | XML / JSON

This Code system is used in the following value sets:

* Coverage SelfPay Codes (This value set includes Coverage SelfPay codes.)

* Coverage Type and Self-Pay Codes (This value set includes Coverage Type codes.)

4.2.12.520.1 Content

4.2.12.520.2 Coverage SelfPay Codes

This value set includes Coverage SelfPay codes.

Copyright Statement: HL7 International.

This code system http://hl7.org/fhir/coverage-selfpay defines the following codes:

Code	Display	Definition
pay	Pay	An individual or oraganization is paying directly for goods and services.

See the full registry of value sets defined as part of FHIR.

Explanation of the columns that may appear on this page:

Level	A few code lists that FHIR defines are hierarchical - each code is assigned a level. In this scheme, some codes are under other codes, and imply that the code they are under also applies
Source	The source of the definition of the code (when the value set draws in codes defined elsewhere)
Code	The code (used as the code in the resource instance). If the code is in italics, this indicates that the code is not selectable ('Abstract')
Display	The display (used in the display element of a Coding). If there is no display, implementers should not simply display the code, but map the concept into their application
Definition	An explanation of the meaning of the concept
Comments	Additional notes about how to use the code

4.2.12.522 Code System http://hl7.org/fhir/additionalmaterials

URL: https://hl7.org/fhir/STU3/codesystem-additionalmaterials.html

This page is part of the FHIR Specification (v3.0.2: STU 3). The current version which supercedes this version is 4.0.1. For a full list of available versions, see the Directory of published versions

Vocabulary Work Group | Maturity Level: 0 | Informative | Use Context: Not Intended for Production use

This is a code system defined by the FHIR project.

Summary

Defining URL:	http://hl7.org/fhir/additionalmaterials
Name:	Additional Material Codes
Definition:	This value set includes sample additional material type codes.
Committee:	Financial Management Work Group
OID:	2.16.840.1.113883.4.642.1.522 (for OID based terminology systems)
Copyright:	This is an example set.

Source Resource | XML / JSON

This Code system is used in the following value sets:

* Additional Material Codes (This value set includes sample additional material type codes.)

4.2.12.522.1 Content

4.2.12.522.2 Additional Material Codes

This value set includes sample additional material type codes.

Copyright Statement: This is an example set.

This code system http://hl7.org/fhir/additionalmaterials defines the following codes:

Code	Display	Definition
xray	XRay	XRay
image	Image	Image
email	Email	Email
model	Model	Model
document	Document	Document
other	Other	Other

See the full registry of value sets defined as part of FHIR.

Explanation of the columns that may appear on this page:

Level	A few code lists that FHIR defines are hierarchical - each code is assigned a level. In this scheme, some codes are under other codes, and imply that the code they are under also applies
Source	The source of the definition of the code (when the value set draws in codes defined elsewhere)
Code	The code (used as the code in the resource instance). If the code is in italics, this indicates that the code is not selectable ('Abstract')
Display	The display (used in the display element of a Coding). If there is no display, implementers should not simply display the code, but map the concept into their application

Definition | An explanation of the meaning of the concept
Comments | Additional notes about how to use the code

4.2.12.525 Code System http://hl7.org/fhir/intervention

URL: https://hl7.org/fhir/STU3/codesystem-intervention.html

This page is part of the FHIR Specification (v3.0.2: STU 3). The current version which supercedes this version is 4.0.1. For a full list of available versions, see the Directory of published versions

Vocabulary Work Group | Maturity Level: 0 | Informative | Use Context: Not Intended for Production use

This is a code system defined by the FHIR project.

Summary

Defining URL: | http://hl7.org/fhir/intervention
Name: | Intervention Codes
Definition: | This value set includes sample Intervention codes.
Committee: | Financial Management Work Group
OID: | 2.16.840.1.113883.4.642.1.525 (for OID based terminology systems)
Copyright: | This is an example set.
Source Resource | XML / JSON

This Code system is used in the following value sets:

* Intervention Codes (This value set includes sample Intervention codes.)

4.2.12.525.1 Content

4.2.12.525.2 Intervention Codes

This value set includes sample Intervention codes.

Copyright Statement: This is an example set.

This code system http://hl7.org/fhir/intervention defines the following codes:

Code | Display | Definition
unknown | Unknown | Unknown
other | Other | Other

See the full registry of value sets defined as part of FHIR.

Explanation of the columns that may appear on this page:

Level | A few code lists that FHIR defines are hierarchical - each code is assigned a level. In this scheme, some codes are under other codes, and imply that the code they are under also applies
Source | The source of the definition of the code (when the value set draws in codes defined elsewhere)
Code | The code (used as the code in the resource instance). If the code is in italics, this indicates that the code is not selectable ('Abstract')
Display | The display (used in the display element of a Coding). If there is no display, implementers should not simply display the code, but map the concept into their application
Definition | An explanation of the meaning of the concept
Comments | Additional notes about how to use the code

4.2.12.527 Code System http://hl7.org/fhir/missingtoothreason

URL: https://hl7.org/fhir/STU3/codesystem-missing-tooth-reason.html

This page is part of the FHIR Specification (v3.0.2: STU 3). The current version which supercedes this version is 4.0.1. For a full list of available versions, see the Directory of published versions

Vocabulary Work Group | Maturity Level: 1 | Informative | Use Context: Not Intended for Production use

This is a code system defined by the FHIR project.

Summary

Defining URL: | http://hl7.org/fhir/missingtoothreason
Name: | Missing Tooth Reason Codes
Definition: | This value set includes sample Missing Tooth Reason codes.
Committee: | Financial Management Work Group
OID: | 2.16.840.1.113883.4.642.1.527 (for OID based terminology systems)
Copyright: | This is an example set.
Source Resource | XML / JSON

This Code system is used in the following value sets:

* Missing Tooth Reason Codes (This value set includes sample Missing Tooth Reason codes.)

4.2.12.527.1 Content

4.2.12.527.2 Missing Tooth Reason Codes

This value set includes sample Missing Tooth Reason codes.

Copyright Statement: This is an example set.

This code system http://hl7.org/fhir/missingtoothreason defines the following codes:

Code | Display | Definition
e | E | Extraction
c | C | Congenital
u | U | Unknown
o | O | Other

See the full registry of value sets defined as part of FHIR.

Explanation of the columns that may appear on this page:

Level | A few code lists that FHIR defines are hierarchical - each code is assigned a level. In this scheme, some codes are under other codes, and imply that the code they are under also applies
Source | The source of the definition of the code (when the value set draws in codes defined elsewhere)
Code | The code (used as the code in the resource instance). If the code is in italics, this indicates that the code is not selectable ('Abstract')
Display | The display (used in the display element of a Coding). If there is no display, implementers should not simply display the code, but map the concept into their application
Definition | An explanation of the meaning of the concept
Comments | Additional notes about how to use the code

4.2.12.529 Code System http://hl7.org/fhir/modifiers

URL: https://hl7.org/fhir/STU3/codesystem-claim-modifiers.html

This page is part of the FHIR Specification (v3.0.2: STU 3). The current version which supercedes this version is 4.0.1. For a full list of available versions, see the Directory of published versions

Vocabulary Work Group | Maturity Level: 1 | Informative | Use Context: Not Intended for Production use

This is a code system defined by the FHIR project.

Summary

Defining URL: | http://hl7.org/fhir/modifiers
Name: | Modifier type Codes
Definition: | This value set includes sample Modifier type codes.
Committee: | Financial Management Work Group
OID: | 2.16.840.1.113883.4.642.1.529 (for OID based terminology systems)
Copyright: | This is an example set.
Source Resource | XML / JSON

This Code system is used in the following value sets:

* Modifier type Codes (This value set includes sample Modifier type codes.)

4.2.12.529.1 Content

4.2.12.529.2 Modifier type Codes

This value set includes sample Modifier type codes.

Copyright Statement: This is an example set.

This code system http://hl7.org/fhir/modifiers defines the following codes:

Code | Display | Definition
a | Repair of prior service or installation | Repair of prior service or installation.
b | Temporary service or installation | Temporary service or installation.
c | TMJ treatment | Treatment associated with TMJ.
e | Implant or associated with an implant | Implant or associated with an implant.
rooh | Rush or Outside of office hours | A Rush service or service performed outside of normal office hours.
x | None | None.

See the full registry of value sets defined as part of FHIR.

Explanation of the columns that may appear on this page:

Level | A few code lists that FHIR defines are hierarchical - each code is assigned a level. In this scheme, some codes are under other codes, and imply that the code they are under also applies
Source | The source of the definition of the code (when the value set draws in codes defined elsewhere)
Code | The code (used as the code in the resource instance). If the code is in italics, this indicates that the code is not selectable ('Abstract')
Display | The display (used in the display element of a Coding). If there is no display, implementers should not simply display the code, but map the concept into their application
Definition | An explanation of the meaning of the concept
Comments | Additional notes about how to use the code

4.2.12.531 Code System http://hl7.org/fhir/ex-oralprostho

URL: https://hl7.org/fhir/STU3/codesystem-oral-prosthodontic-material.html

This page is part of the FHIR Specification (v3.0.2: STU 3). The current version which supercedes this version is 4.0.1. For a full list of available versions, see the Directory of published versions

Vocabulary Work Group | Maturity Level: 0 | Informative | Use Context: Not Intended for Production use

This is a code system defined by the FHIR project.

Summary

Defining URL: | http://hl7.org/fhir/ex-oralprostho
Name: | Oral Prostho Material type Codes
Definition: | This value set includes sample Oral Prosthodontic Material type codes.
Committee: | Financial Management Work Group
OID: | 2.16.840.1.113883.4.642.1.531 (for OID based terminology systems)
Copyright: | This is an example set.
Source Resource | XML / JSON

This Code system is used in the following value sets:

* Oral Prostho Material type Codes (This value set includes sample Oral Prosthodontic Material type codes.)

4.2.12.531.1 Content

4.2.12.531.2 Oral Prostho Material type Codes

This value set includes sample Oral Prosthodontic Material type codes.

Copyright Statement: This is an example set.

This code system http://hl7.org/fhir/ex-oralprostho defines the following codes:

Code | Display | Definition
1 | Fixed Bridge | Fixed Bridge
2 | Maryland Bridge | Maryland Bridge
3 | Denture Acrylic | Denture Acrylic
4 | Denture Chrome Cobalt | Denture Chrome Cobalt

See the full registry of value sets defined as part of FHIR.

Explanation of the columns that may appear on this page:

Level | A few code lists that FHIR defines are hierarchical - each code is assigned a level. In this scheme, some codes are under other codes, and imply that the code they are under also applies
Source | The source of the definition of the code (when the value set draws in codes defined elsewhere)
Code | The code (used as the code in the resource instance). If the code is in italics, this indicates that the code is not selectable ('Abstract')
Display | The display (used in the display element of a Coding). If there is no display, implementers should not simply display the code, but map the concept into their application
Definition | An explanation of the meaning of the concept
Comments | Additional notes about how to use the code

4.2.12.533 Code System http://hl7.org/fhir/ex-tooth

URL: https://hl7.org/fhir/STU3/codesystem-tooth.html

This page is part of the FHIR Specification (v3.0.2: STU 3). The current version which supercedes this version is 4.0.1. For a full list of available versions, see the Directory of published versions

Vocabulary Work Group | Maturity Level: 1 | Informative | Use Context: Not Intended for Production use

This is a code system defined by the FHIR project.

Summary

Defining URL: | http://hl7.org/fhir/ex-tooth
Name: | Oral Site Codes
Definition: | This value set includes a smattering of FDI oral site codes.
Committee: | Financial Management Work Group
OID: | 2.16.840.1.113883.4.642.1.533 (for OID based terminology systems)
Copyright: | This is an example set.
Source Resource | XML / JSON

This Code system is used in the following value sets:

* Oral Site Codes (This value set includes a smattering of FDI oral site codes.)

4.2.12.533.1 Content

4.2.12.533.2 Oral Site Codes

This value set includes a smattering of FDI oral site codes.

Copyright Statement: This is an example set.

This code system http://hl7.org/fhir/ex-tooth defines the following codes:

Code | Display | Definition
0 | Oral cavity | Oral cavity.
1 | 1 | Permanent teeth Maxillary right.
2 | 2 | Permanent teeth Maxillary left.

3 | 3 | Permanent teeth Mandibular right.
4 | 4 | Permanent teeth Mandibular left.
5 | 5 | Deciduous teeth Maxillary right.
6 | 6 | Deciduous teeth Maxillary left.
7 | 7 | Deciduous teeth Mandibular right.
8 | 8 | Deciduous teeth Mandibular left.
11 | 11 | Upper Right Tooth 1 from the central axis, permanent dentition.
12 | 12 | Upper Right Tooth 2 from the central axis, permanent dentition.
13 | 13 | Upper Right Tooth 3 from the central axis, permanent dentition.
14 | 14 | Upper Right Tooth 4 from the central axis, permanent dentition.
15 | 15 | Upper Right Tooth 5 from the central axis, permanent dentition.
16 | 16 | Upper Right Tooth 6 from the central axis, permanent dentition.
17 | 17 | Upper Right Tooth 7 from the central axis, permanent dentition.
18 | 18 | Upper Right Tooth 8 from the central axis, permanent dentition.
21 | 21 | Upper Left Tooth 1 from the central axis, permanent dentition.
22 | 22 | Upper Left Tooth 2 from the central axis, permanent dentition.
23 | 23 | Upper Left Tooth 3 from the central axis, permanent dentition.
24 | 24 | Upper Left Tooth 4 from the central axis, permanent dentition.
25 | 25 | Upper Left Tooth 5 from the central axis, permanent dentition.
26 | 26 | Upper Left Tooth 6 from the central axis, permanent dentition.
27 | 27 | Upper Left Tooth 7 from the central axis, permanent dentition.
28 | 28 | Upper Left Tooth 8 from the central axis, permanent dentition.
31 | 31 | Lower Left Tooth 1 from the central axis, permanent dentition.
32 | 32 | Lower Left Tooth 2 from the central axis, permanent dentition.
33 | 33 | Lower Left Tooth 3 from the central axis, permanent dentition.
34 | 34 | Lower Left Tooth 4 from the central axis, permanent dentition.
35 | 35 | Lower Left Tooth 5 from the central axis, permanent dentition.
36 | 36 | Lower Left Tooth 6 from the central axis, permanent dentition.
37 | 37 | Lower Left Tooth 7 from the central axis, permanent dentition.
38 | 38 | Lower Left Tooth 8 from the central axis, permanent dentition.
41 | 41 | Lower Right Tooth 1 from the central axis, permanent dentition.
42 | 42 | Lower Right Tooth 2 from the central axis, permanent dentition.
43 | 43 | Lower Right Tooth 3 from the central axis, permanent dentition.
44 | 44 | Lower Right Tooth 4 from the central axis, permanent dentition.
45 | 45 | Lower Right Tooth 5 from the central axis, permanent dentition.
46 | 46 | Lower Right Tooth 6 from the central axis, permanent dentition.
47 | 47 | Lower Right Tooth 7 from the central axis, permanent dentition.
48 | 48 | Lower Right Tooth 8 from the central axis, permanent dentition.

See the full registry of value sets defined as part of FHIR.

Explanation of the columns that may appear on this page:

Level | A few code lists that FHIR defines are hierarchical - each code is assigned a level. In this scheme, some codes are under other codes, and imply that the code they are under also applies
Source | The source of the definition of the code (when the value set draws in codes defined elsewhere)
Code | The code (used as the code in the resource instance). If the code is in italics, this indicates that the code is not selectable ('Abstract')
Display | The display (used in the display element of a Coding). If there is no display, implementers should not simply display the code, but map the concept into their application
Definition | An explanation of the meaning of the concept
Comments | Additional notes about how to use the code

4.2.12.535 Code System http://hl7.org/fhir/ex-USCLS

URL: https://hl7.org/fhir/STU3/codesystem-service-uscls.html

This page is part of the FHIR Specification (v3.0.2: STU 3). The current version which supercedes this version is 4.0.1. For a full list of available versions, see the Directory of published versions

Vocabulary Work Group | Maturity Level: 1 | Informative | Use Context: Not Intended for Production use

This is a code system defined by the FHIR project.

Summary

Defining URL: | http://hl7.org/fhir/ex-USCLS
Name: | USCLS Codes
Definition: | This value set includes a smattering of USCLS codes.
Committee: | Financial Management Work Group
OID: | 2.16.840.1.113883.4.642.1.535 (for OID based terminology systems)
Copyright: | This is an example set.
Source Resource | XML / JSON

This Code system is used in the following value sets:

* USCLS Codes (This value set includes a smattering of USCLS codes.)

4.2.12.535.1 Content

4.2.12.535.2 USCLS Codes

This value set includes a smattering of USCLS codes.

Copyright Statement: This is an example set.

This code system http://hl7.org/fhir/ex-USCLS defines the following codes:

Code	Display	Definition
1101	Exam, comp, primary	Exam, comp, primary
1102	Exam, comp, mixed	Exam, comp, mixed
1103	Exam, comp, permanent	Exam, comp, permanent
1201	Exam, recall	Exam, recall
1205	Exam, emergency	Exam, emergency
2101	Radiograph, series (12)	Radiograph, series (12)
2102	Radiograph, series (16)	Radiograph, series (16)
2141	Radiograph, bytewing	Radiograph, bytewing
2601	Radiograph, panoramic	Radiograph, panoramic
11101	Polishing, 1 unit	Polishing, 1 unit
11102	Polishing, 2 unit	Polishing, 2 unit
11103	Polishing, 3 unit	Polishing, 3 unit
11104	Polishing, 4 unit	Polishing, 4 unit
21211	Amalgam, 1 surface	Amalgam, 1 surface
21212	Amalgam, 2 surface	Amalgam, 2 surface
27211	Crown, PFM	Crown, PFM
67211	Maryland Bridge	Maryland Bridge
99111	Lab, commercial	Lab, commercial
99333	Lab, in office	Lab, in office
99555	Expense	Expense

See the full registry of value sets defined as part of FHIR.

Explanation of the columns that may appear on this page:

Level	A few code lists that FHIR defines are hierarchical - each code is assigned a level. In this scheme, some codes are under other codes, and imply that the code they are under also applies
Source	The source of the definition of the code (when the value set draws in codes defined elsewhere)
Code	The code (used as the code in the resource instance). If the code is in italics, this indicates that the code is not selectable ('Abstract')
Display	The display (used in the display element of a Coding). If there is no display, implementers should not simply display the code, but map the concept into their application
Definition	An explanation of the meaning of the concept
Comments	Additional notes about how to use the code

4.2.12.537 Code System http://hl7.org/fhir/claim-use

URL: https://hl7.org/fhir/STU3/codesystem-claim-use.html

This page is part of the FHIR Specification (v3.0.2: STU 3). The current version which supercedes this version is 4.0.1. For a full list of available versions, see the Directory of published versions

Vocabulary Work Group | Maturity Level: 2 | Informative | Use Context: Any

This is a code system defined by the FHIR project.

Summary

Defining URL:	http://hl7.org/fhir/claim-use
Name:	Use
Definition:	Complete, proposed, exploratory, other
Committee:	Financial Management Work Group
OID:	2.16.840.1.113883.4.642.1.537 (for OID based terminology systems)
Source Resource	XML / JSON

This Code system is used in the following value sets:

* Use (Complete, proposed, exploratory, other)

4.2.12.537.1 Content

4.2.12.537.2 Use

Complete, proposed, exploratory, other

This code system http://hl7.org/fhir/claim-use defines the following codes:

Code	Display	Definition
complete	Complete	The treatment is complete and this represents a Claim for the services.
proposed	Proposed	The treatment is proposed and this represents a Pre-authorization for the services.
exploratory	Exploratory	The treatment is proposed and this represents a Pre-determination for the services.
other	Other	A locally defined or otherwise resolved status.

See the full registry of value sets defined as part of FHIR.

Explanation of the columns that may appear on this page:

Level | A few code lists that FHIR defines are hierarchical - each code is assigned a level. In this scheme, some codes are under other codes, and imply that the code they are under also applies
Source | The source of the definition of the code (when the value set draws in codes defined elsewhere)
Code | The code (used as the code in the resource instance). If the code is in italics, this indicates that the code is not selectable ('Abstract')
Display | The display (used in the display element of a Coding). If there is no display, implementers should not simply display the code, but map the concept into their application
Definition | An explanation of the meaning of the concept
Comments | Additional notes about how to use the code

4.2.12.539 Code System http://hl7.org/fhir/FDI-surface

URL: https://hl7.org/fhir/STU3/codesystem-surface.html

This page is part of the FHIR Specification (v3.0.2: STU 3). The current version which supercedes this version is 4.0.1. For a full list of available versions, see the Directory of published versions

Vocabulary Work Group | Maturity Level: 1 | Informative | Use Context: Not Intended for Production use

This is a code system defined by the FHIR project.

Summary

Defining URL: | http://hl7.org/fhir/FDI-surface
Name: | Surface Codes
Definition: | This value set includes a smattering of FDI tooth surface codes.
Committee: | Financial Management Work Group
OID: | 2.16.840.1.113883.4.642.1.539 (for OID based terminology systems)
Copyright: | This is an example set.
Source Resource | XML / JSON

This Code system is used in the following value sets:

* Surface Codes (This value set includes a smattering of FDI tooth surface codes.)

4.2.12.539.1 Content

4.2.12.539.2 Surface Codes

This value set includes a smattering of FDI tooth surface codes.

Copyright Statement: This is an example set.

This code system http://hl7.org/fhir/FDI-surface defines the following codes:

Code | Display | Definition
M | Mesial | The surface of a tooth that is closest to the midline (middle) of the face.
O | Occlusal | The chewing surface of posterior teeth.
I | Incisal | The biting edge of anterior teeth.
D | Distal | The surface of a tooth that faces away from the midline of the face.
B | Buccal | The surface of a posterior tooth facing the cheeks.
V | Ventral | The surface of a tooth facing the lips.
L | Lingual | The surface of a tooth facing the tongue.
MO | Mesioclusal | The Mesioclusal surfaces of a tooth.
DO | Distoclusal | The Distoclusal surfaces of a tooth.
DI | Distoincisal | The Distoincisal surfaces of a tooth.
MOD | Mesioclusodistal | The Mesioclusodistal surfaces of a tooth.

See the full registry of value sets defined as part of FHIR.

Explanation of the columns that may appear on this page:

Level | A few code lists that FHIR defines are hierarchical - each code is assigned a level. In this scheme, some codes are under other codes, and imply that the code they are under also applies
Source | The source of the definition of the code (when the value set draws in codes defined elsewhere)
Code | The code (used as the code in the resource instance). If the code is in italics, this indicates that the code is not selectable ('Abstract')
Display | The display (used in the display element of a Coding). If there is no display, implementers should not simply display the code, but map the concept into their application
Definition | An explanation of the meaning of the concept
Comments | Additional notes about how to use the code

4.2.12.541 Code System http://hl7.org/fhir/ex-claimitemtype

URL: https://hl7.org/fhir/STU3/codesystem-fm-itemtype.html

This page is part of the FHIR Specification (v3.0.2: STU 3). The current version which supercedes this version is 4.0.1. For a full list of available versions, see the Directory of published versions

Vocabulary Work Group | Maturity Level: 0 | Informative | Use Context: Not Intended for Production use

This is a code system defined by the FHIR project.

Summary

Defining URL: | http://hl7.org/fhir/ex-claimitemtype

Name: | Claim Item Type Codes
Definition: | This value set includes sample Item Type codes.
Committee: | Financial Management Work Group
OID: | 2.16.840.1.113883.4.642.1.541 (for OID based terminology systems)
Copyright: | This is an example set.
Source Resource | XML / JSON

This Code system is used in the following value sets:

* Claim Item Type Codes (This value set includes sample Item Type codes.)

4.2.12.541.1 Content

4.2.12.541.2 Claim Item Type Codes

This value set includes sample Item Type codes.

Copyright Statement: This is an example set.

This code system http://hl7.org/fhir/ex-claimitemtype defines the following codes:

Code | Display | Definition
group | Group | A group of products and/or Services, amount ar the summary or detail level products and services.
product | Product | A billed product line item.
service | Service | A billed service line item.

See the full registry of value sets defined as part of FHIR.

Explanation of the columns that may appear on this page:

Level | A few code lists that FHIR defines are hierarchical - each code is assigned a level. In this scheme, some codes are under other codes, and imply that the code they are under also applies
Source | The source of the definition of the code (when the value set draws in codes defined elsewhere)
Code | The code (used as the code in the resource instance). If the code is in italics, this indicates that the code is not selectable ('Abstract')
Display | The display (used in the display element of a Coding). If there is no display, implementers should not simply display the code, but map the concept into their application
Definition | An explanation of the meaning of the concept
Comments | Additional notes about how to use the code

4.2.12.543 Code System http://hl7.org/fhir/ex-fdi

URL: https://hl7.org/fhir/STU3/codesystem-teeth.html

This page is part of the FHIR Specification (v3.0.2: STU 3). The current version which supercedes this version is 4.0.1. For a full list of available versions, see the Directory of published versions

Vocabulary Work Group | Maturity Level: 0 | Informative | Use Context: Not Intended for Production use

This is a code system defined by the FHIR project.

Summary

Defining URL: | http://hl7.org/fhir/ex-fdi
Name: | Teeth Codes
Definition: | This value set includes the FDI Teeth codes.
Committee: | Financial Management Work Group
OID: | 2.16.840.1.113883.4.642.1.543 (for OID based terminology systems)
Copyright: | This is an example set.
Source Resource | XML / JSON

This Code system is used in the following value sets:

* Teeth Codes (This value set includes the FDI Teeth codes.)

4.2.12.543.1 Content

4.2.12.543.2 Teeth Codes

This value set includes the FDI Teeth codes.

Copyright Statement: This is an example set.

This code system http://hl7.org/fhir/ex-fdi defines the following codes:

Code | Display | Definition
11 | 11 | Upper Right Tooth 1 from the central axis, permanent dentition.
12 | 12 | Upper Right Tooth 2 from the central axis, permanent dentition.
13 | 13 | Upper Right Tooth 3 from the central axis, permanent dentition.
14 | 14 | Upper Right Tooth 4 from the central axis, permanent dentition.
15 | 15 | Upper Right Tooth 5 from the central axis, permanent dentition.
16 | 16 | Upper Right Tooth 6 from the central axis, permanent dentition.
17 | 17 | Upper Right Tooth 7 from the central axis, permanent dentition.
18 | 18 | Upper Right Tooth 8 from the central axis, permanent dentition.
21 | 21 | Upper Left Tooth 1 from the central axis, permanent dentition.

22 | 22 | Upper Left Tooth 2 from the central axis, permanent dentition.
23 | 23 | Upper Left Tooth 3 from the central axis, permanent dentition.
24 | 24 | Upper Left Tooth 4 from the central axis, permanent dentition.
25 | 25 | Upper Left Tooth 5 from the central axis, permanent dentition.
26 | 26 | Upper Left Tooth 6 from the central axis, permanent dentition.
27 | 27 | Upper Left Tooth 7 from the central axis, permanent dentition.
28 | 28 | Upper Left Tooth 8 from the central axis, permanent dentition.
31 | 31 | Lower Left Tooth 1 from the central axis, permanent dentition.
32 | 32 | Lower Left Tooth 2 from the central axis, permanent dentition.
33 | 33 | Lower Left Tooth 3 from the central axis, permanent dentition.
34 | 34 | Lower Left Tooth 4 from the central axis, permanent dentition.
35 | 35 | Lower Left Tooth 5 from the central axis, permanent dentition.
36 | 36 | Lower Left Tooth 6 from the central axis, permanent dentition.
37 | 37 | Lower Left Tooth 7 from the central axis, permanent dentition.
38 | 38 | Lower Left Tooth 8 from the central axis, permanent dentition.
41 | 41 | Lower Right Tooth 1 from the central axis, permanent dentition.
42 | 42 | Lower Right Tooth 2 from the central axis, permanent dentition.
43 | 43 | Lower Right Tooth 3 from the central axis, permanent dentition.
44 | 44 | Lower Right Tooth 4 from the central axis, permanent dentition.
45 | 45 | Lower Right Tooth 5 from the central axis, permanent dentition.
46 | 46 | Lower Right Tooth 6 from the central axis, permanent dentition.
47 | 47 | Lower Right Tooth 7 from the central axis, permanent dentition.
48 | 48 | Lower Right Tooth 8 from the central axis, permanent dentition.

See the full registry of value sets defined as part of FHIR.

Explanation of the columns that may appear on this page:

Level | A few code lists that FHIR defines are hierarchical - each code is assigned a level. In this scheme, some codes are under other codes, and imply that the code they are under also applies
Source | The source of the definition of the code (when the value set draws in codes defined elsewhere)
Code | The code (used as the code in the resource instance). If the code is in italics, this indicates that the code is not selectable ('Abstract')
Display | The display (used in the display element of a Coding). If there is no display, implementers should not simply display the code, but map the concept into their application
Definition | An explanation of the meaning of the concept
Comments | Additional notes about how to use the code

4.2.12.545 Code System http://hl7.org/fhir/processpriority

URL: https://hl7.org/fhir/STU3/codesystem-process-priority.html

This page is part of the FHIR Specification (v3.0.2: STU 3). The current version which supercedes this version is 4.0.1. For a full list of available versions, see the Directory of published versions

Vocabulary Work Group | Maturity Level: 1 | Informative | Use Context: Not Intended for Production use

This is a code system defined by the FHIR project.

Summary

Defining URL: | http://hl7.org/fhir/processpriority
Name: | Process Priority Codes
Definition: | This value set includes the financial processing priority codes.
Committee: | Financial Management Work Group
OID: | 2.16.840.1.113883.4.642.1.545 (for OID based terminology systems)
Copyright: | This is an example set.
Source Resource | XML / JSON

This Code system is used in the following value sets:

* Process Priority Codes (This value set includes the financial processing priority codes.)

4.2.12.545.1 Content

4.2.12.545.2 Process Priority Codes

This value set includes the financial processing priority codes.

Copyright Statement: This is an example set.

This code system http://hl7.org/fhir/processpriority defines the following codes:

Code | Display | Definition
stat | Immediate | Immediately in real time.
normal | Normal | With best effort.
deferred | Deferred | Later, when possible.

See the full registry of value sets defined as part of FHIR.

Explanation of the columns that may appear on this page:

Level | A few code lists that FHIR defines are hierarchical - each code is assigned a level. In this scheme, some codes are under other codes, and imply that the code they are under also applies

Source | The source of the definition of the code (when the value set draws in codes defined elsewhere)
Code | The code (used as the code in the resource instance). If the code is in italics, this indicates that the code is not selectable ('Abstract')
Display | The display (used in the display element of a Coding). If there is no display, implementers should not simply display the code, but map the concept into their application
Definition | An explanation of the meaning of the concept
Comments | Additional notes about how to use the code

4.2.12.547 Code System http://hl7.org/fhir/ex-udi

URL: https://hl7.org/fhir/STU3/codesystem-udi.html

This page is part of the FHIR Specification (v3.0.2: STU 3). The current version which supercedes this version is 4.0.1. For a full list of available versions, see the Directory of published versions

Vocabulary Work Group | Maturity Level: 0 | Informative | Use Context: Not Intended for Production use

This is a code system defined by the FHIR project.

Summary

Defining URL: | http://hl7.org/fhir/ex-udi
Name: | UDI Codes
Definition: | This value set includes sample UDI codes.
Committee: | Financial Management Work Group
OID: | 2.16.840.1.113883.4.642.1.547 (for OID based terminology systems)
Copyright: | This is an example set.
Source Resource | XML / JSON

This Code system is used in the following value sets:

* UDI Codes (This value set includes sample UDI codes.)

4.2.12.547.1 Content

4.2.12.547.2 UDI Codes

This value set includes sample UDI codes.

Copyright Statement: This is an example set.

This code system http://hl7.org/fhir/ex-udi defines the following codes:

Code | Display | Definition
gudid | GUDID (FDA) | GUDID (FDA) US Repository

See the full registry of value sets defined as part of FHIR.

Explanation of the columns that may appear on this page:

Level | A few code lists that FHIR defines are hierarchical - each code is assigned a level. In this scheme, some codes are under other codes, and imply that the code they are under also applies
Source | The source of the definition of the code (when the value set draws in codes defined elsewhere)
Code | The code (used as the code in the resource instance). If the code is in italics, this indicates that the code is not selectable ('Abstract')
Display | The display (used in the display element of a Coding). If there is no display, implementers should not simply display the code, but map the concept into their application
Definition | An explanation of the meaning of the concept
Comments | Additional notes about how to use the code

4.2.12.549 Code System http://hl7.org/fhir/fm-conditions

URL: https://hl7.org/fhir/STU3/codesystem-fm-conditions.html

This page is part of the FHIR Specification (v3.0.2: STU 3). The current version which supercedes this version is 4.0.1. For a full list of available versions, see the Directory of published versions

Vocabulary Work Group | Maturity Level: 0 | Informative | Use Context: Not Intended for Production use

This is a code system defined by the FHIR project.

Summary

Defining URL: | http://hl7.org/fhir/fm-conditions
Name: | FM Condition Codes
Definition: | This value set includes sample Conditions codes.
Committee: | Financial Management Work Group
OID: | 2.16.840.1.113883.4.642.1.549 (for OID based terminology systems)
Copyright: | This is an example set.
Source Resource | XML / JSON

This Code system is used in the following value sets:

* FM Condition Codes (This value set includes sample Conditions codes.)

4.2.12.549.1 Content

4.2.12.549.2 FM Condition Codes

This value set includes sample Conditions codes.

Copyright Statement: This is an example set.

This code system http://hl7.org/fhir/fm-conditions defines the following codes:

Code | Display | Definition
123987 | Headache | Headache

See the full registry of value sets defined as part of FHIR.

Explanation of the columns that may appear on this page:

Level | A few code lists that FHIR defines are hierarchical - each code is assigned a level. In this scheme, some codes are under other codes, and imply that the code they are under also applies
Source | The source of the definition of the code (when the value set draws in codes defined elsewhere)
Code | The code (used as the code in the resource instance). If the code is in italics, this indicates that the code is not selectable ('Abstract')
Display | The display (used in the display element of a Coding). If there is no display, implementers should not simply display the code, but map the concept into their application
Definition | An explanation of the meaning of the concept
Comments | Additional notes about how to use the code

4.2.12.551 Code System http://hl7.org/fhir/ex-claimtype

URL: https://hl7.org/fhir/STU3/codesystem-claim-type.html

This page is part of the FHIR Specification (v3.0.2: STU 3). The current version which supercedes this version is 4.0.1. For a full list of available versions, see the Directory of published versions

Vocabulary Work Group | Maturity Level: 2 | Informative | Use Context: Not Intended for Production use

This is a code system defined by the FHIR project.

Summary

Defining URL: | http://hl7.org/fhir/ex-claimtype
Name: | Example Claim Type Codes
Definition: | This value set includes sample Claim Type codes.
Committee: | Financial Management Work Group
OID: | 2.16.840.1.113883.4.642.1.551 (for OID based terminology systems)
Copyright: | This is an example set.
Source Resource | XML / JSON

This Code system is used in the following value sets:

* Example Claim Type Codes (This value set includes sample Claim Type codes.)

4.2.12.551.1 Content

4.2.12.551.2 Example Claim Type Codes

This value set includes sample Claim Type codes.

Copyright Statement: This is an example set.

This code system http://hl7.org/fhir/ex-claimtype defines the following codes:

Code | Display | Definition
institutional | Institutional | Hospital, clinic and typically inpatient claims.
oral | Oral | Dental, Denture and Hygiene claims.
pharmacy | Pharmacy | Pharmacy claims for goods and services.
professional | Professional | Typically outpatient claims from Physician, Psychological, Chiropractor, Physiotherapy, Speach Pathology, rehabilitative, consulting.
vision | Vision | Vision claims for professional services and products such as glasses and contact lenses.

See the full registry of value sets defined as part of FHIR.

Explanation of the columns that may appear on this page:

Level | A few code lists that FHIR defines are hierarchical - each code is assigned a level. In this scheme, some codes are under other codes, and imply that the code they are under also applies
Source | The source of the definition of the code (when the value set draws in codes defined elsewhere)
Code | The code (used as the code in the resource instance). If the code is in italics, this indicates that the code is not selectable ('Abstract')
Display | The display (used in the display element of a Coding). If there is no display, implementers should not simply display the code, but map the concept into their application
Definition | An explanation of the meaning of the concept
Comments | Additional notes about how to use the code

4.2.12.553 Code System http://hl7.org/fhir/ex-serviceproduct

URL: https://hl7.org/fhir/STU3/codesystem-service-product.html

This page is part of the FHIR Specification (v3.0.2: STU 3). The current version which supercedes this version is 4.0.1. For a full list of available versions, see the Directory of published versions

Vocabulary Work Group | Maturity Level: 0 | Informative | Use Context: Not Intended for Production use

This is a code system defined by the FHIR project.

Summary

Defining URL: | http://hl7.org/fhir/ex-serviceproduct
Name: | Example Service/Product Codes
Definition: | This value set includes a smattering of Service/Product codes.
Committee: | Financial Management Work Group
OID: | 2.16.840.1.113883.4.642.1.553 (for OID based terminology systems)
Copyright: | This is an example set.
Source Resource | XML / JSON

This Code system is used in the following value sets:

* Example Service/Product Codes (This value set includes a smattering of Service/Product codes.)

4.2.12.553.1 Content

4.2.12.553.2 Example Service/Product Codes

This value set includes a smattering of Service/Product codes.

Copyright Statement: This is an example set.

This code system http://hl7.org/fhir/ex-serviceproduct defines the following codes:

Code | Display | Definition
exam | Exam | Exam
flushot | Flu shot | Flu shot

See the full registry of value sets defined as part of FHIR.

Explanation of the columns that may appear on this page:

Level | A few code lists that FHIR defines are hierarchical - each code is assigned a level. In this scheme, some codes are under other codes, and imply that the code they are under also applies
Source | The source of the definition of the code (when the value set draws in codes defined elsewhere)
Code | The code (used as the code in the resource instance). If the code is in italics, this indicates that the code is not selectable ('Abstract')
Display | The display (used in the display element of a Coding). If there is no display, implementers should not simply display the code, but map the concept into their application
Definition | An explanation of the meaning of the concept
Comments | Additional notes about how to use the code

4.2.12.555 Code System http://hl7.org/fhir/ex-pharmaservice

URL: https://hl7.org/fhir/STU3/codesystem-service-pharmacy.html

This page is part of the FHIR Specification (v3.0.2: STU 3). The current version which supercedes this version is 4.0.1. For a full list of available versions, see the Directory of published versions

Vocabulary Work Group | Maturity Level: 0 | Informative | Use Context: Not Intended for Production use

This is a code system defined by the FHIR project.

Summary

Defining URL: | http://hl7.org/fhir/ex-pharmaservice
Name: | Example Pharmacy Service Codes
Definition: | This value set includes a smattering of Pharmacy Service codes.
Committee: | Financial Management Work Group
OID: | 2.16.840.1.113883.4.642.1.555 (for OID based terminology systems)
Copyright: | This is an example set.
Source Resource | XML / JSON

This Code system is used in the following value sets:

* Example Pharmacy Service Codes (This value set includes a smattering of Pharmacy Service codes.)

4.2.12.555.1 Content

4.2.12.555.2 Example Pharmacy Service Codes

This value set includes a smattering of Pharmacy Service codes.

Copyright Statement: This is an example set.

This code system http://hl7.org/fhir/ex-pharmaservice defines the following codes:

Code | Display | Definition
smokecess | Smoking cessation | Smoking cessation
flushot | Flu Shot | Flu Shot
drugcost | Drug Cost | The wholesale price of the medication.
markup | Markup | The additional cost assessed on the drug.
dispensefee | Dispense Fee | The professional fee charged for dispensing the product or service.

compoundfee | Compounding Fee | The professional fee charged for compounding the medication.

See the full registry of value sets defined as part of FHIR.

Explanation of the columns that may appear on this page:

Level | A few code lists that FHIR defines are hierarchical - each code is assigned a level. In this scheme, some codes are under other codes, and imply that the code they are under also applies

Source | The source of the definition of the code (when the value set draws in codes defined elsewhere)

Code | The code (used as the code in the resource instance). If the code is in italics, this indicates that the code is not selectable ('Abstract')

Display | The display (used in the display element of a Coding). If there is no display, implementers should not simply display the code, but map the concept into their application

Definition | An explanation of the meaning of the concept

Comments | Additional notes about how to use the code

4.2.12.557 Code System http://hl7.org/fhir/ex-serviceplace

URL: https://hl7.org/fhir/STU3/codesystem-service-place.html

This page is part of the FHIR Specification (v3.0.2: STU 3). The current version which supercedes this version is 4.0.1. For a full list of available versions, see the Directory of published versions

Vocabulary Work Group | Maturity Level: 1 | Informative | Use Context: Not Intended for Production use

This is a code system defined by the FHIR project.

Summary

Defining URL: | http://hl7.org/fhir/ex-serviceplace

Name: | Example Service Place Codes

Definition: | This value set includes a smattering of Service Place codes.

Committee: | Financial Management Work Group

OID: | 2.16.840.1.113883.4.642.1.557 (for OID based terminology systems)

Copyright: | This is an example set.

Source Resource | XML / JSON

This Code system is used in the following value sets:

* Example Service Place Codes (This value set includes a smattering of Service Place codes.)

4.2.12.557.1 Content

4.2.12.557.2 Example Service Place Codes

This value set includes a smattering of Service Place codes.

Copyright Statement: This is an example set.

This code system http://hl7.org/fhir/ex-serviceplace defines the following codes:

Code | Display | Definition

01 | Pharmacy | A facility or location where drugs and other medically related items and services are sold, dispensed, or otherwise provided directly to patients.

03 | School | A facility whose primary purpose is education.

04 | Homeless Shelter | A facility or location whose primary purpose is to provide temporary housing to homeless individuals (e.g., emergency shelters, individual or family shelters).

05 | Indian Health Service Free-standing Facility | A facility or location, owned and operated by the Indian Health Service, which provides diagnostic, therapeutic (surgical and nonsurgical), and rehabilitation services to American Indians and Alaska Natives who do not require hospitalization.

06 | Indian Health Service Provider-based Facility | A facility or location, owned and operated by the Indian Health Service, which provides diagnostic, therapeutic (surgical and nonsurgical), and rehabilitation services rendered by, or under the supervision of, physicians to American Indians and Alaska Natives admitted as inpatients or outpatients.

07 | Tribal 638 Free-Standing Facility | A facility or location owned and operated by a federally recognized American Indian or Alaska Native tribe or tribal organization under a 638 agreement, which provides diagnostic, therapeutic (surgical and nonsurgical), and rehabilitation services to tribal members who do not require hospitalization.

08 | Tribal 638 Provider-Based Facility | A facility or location owned and operated by a federally recognized American Indian or Alaska Native tribe or tribal organization under a 638 agreement, which provides diagnostic, therapeutic (surgical and nonsurgical), and rehabilitation services to tribal members admitted as inpatients or outpatients.

09 | Prison/Correctional Facility | A prison, jail, reformatory, work farm, detention center, or any other similar facility maintained by either Federal, State or local authorities for the purpose of confinement or rehabilitation of adult or juvenile criminal offenders.

11 | Office | Location, other than a hospital, skilled nursing facility (SNF), military treatment facility, community health center, State or local public health clinic, or intermediate care facility (ICF), where the health professional routinely provides health examinations, diagnosis, and treatment of illness or injury on an ambulatory basis.

12 | Home | Location, other than a hospital or other facility, where the patient receives care in a private residence.

13 | Assisted Living Fa | Congregate residential facility with self-contained living units providing assessment of each resident's needs and on-site support 24 hours a day, 7 days a week, with the capacity to deliver or arrange for services including some health care and other services.

14 | Group Home | A residence, with shared living areas, where clients receive supervision and other services such as social and/or behavioral services, custodial service, and minimal services (e.g., medication administration).

15 | Mobile Unit | A facility/unit that moves from place-to-place equipped to provide preventive, screening, diagnostic, and/or treatment services.

19 | Off Campus-Outpatient Hospital | portion of an off-campus hospital provider based department which provides diagnostic, therapeutic (both surgical and nonsurgical), and rehabilitation services to sick or injured persons who do not require hospitalization or institutionalization.

20 | Urgent Care Facility | Location, distinct from a hospital emergency room, an office, or a clinic, whose purpose is to diagnose and treat illness or injury for unscheduled, ambulatory patients seeking immediate medical attention.

21 | Inpatient Hospital | A facility, other than psychiatric, which primarily provides diagnostic, therapeutic (both surgical and nonsurgical), and rehabilitation services by, or under, the supervision of physicians to patients admitted for a variety of medical conditions.
41 | Ambulance—Land | A land vehicle specifically designed, equipped and staffed for lifesaving and transporting the sick or injured.

See the full registry of value sets defined as part of FHIR.

Explanation of the columns that may appear on this page:

Level | A few code lists that FHIR defines are hierarchical - each code is assigned a level. In this scheme, some codes are under other codes, and imply that the code they are under also applies
Source | The source of the definition of the code (when the value set draws in codes defined elsewhere)
Code | The code (used as the code in the resource instance). If the code is in italics, this indicates that the code is not selectable ('Abstract')
Display | The display (used in the display element of a Coding). If there is no display, implementers should not simply display the code, but map the concept into their application
Definition | An explanation of the meaning of the concept
Comments | Additional notes about how to use the code

4.2.12.559 Code System http://hl7.org/fhir/ex-claimsubtype

URL: https://hl7.org/fhir/STU3/codesystem-claim-subtype.html

This page is part of the FHIR Specification (v3.0.2: STU 3). The current version which supercedes this version is 4.0.1. For a full list of available versions, see the Directory of published versions

Vocabulary Work Group | Maturity Level: 1 | Draft | Use Context: Not Intended for Production use

This is a code system defined by the FHIR project.

Summary

Defining URL: | http://hl7.org/fhir/ex-claimsubtype
Name: | Example Claim SubType Codes
Definition: | This value set includes sample Claim SubType codes which are used to distinguish the claim types for example within type institutional there may be subtypes for emergency services, bedstay and transportation.
Committee: | Financial Management Work Group
OID: | 2.16.840.1.113883.4.642.1.559 (for OID based terminology systems)
Copyright: | This is an example set.
Source Resource | XML / JSON

This Code system is used in the following value sets:

* Example Claim SubType Codes (This value set includes sample Claim SubType codes.)

4.2.12.559.1 Content

4.2.12.559.2 Example Claim SubType Codes

This value set includes sample Claim SubType codes which are used to distinguish the claim types for example within type institutional there may be subtypes for emergency services, bedstay and transportation.

Copyright Statement: This is an example set.

This code system http://hl7.org/fhir/ex-claimsubtype defines the following codes:

Code | Display | Definition
ortho | Orthodontic Claim | A claim for Orthodontic Services.
emergency | Emergency Claim | A claim for emergency services.

See the full registry of value sets defined as part of FHIR.

Explanation of the columns that may appear on this page:

Level | A few code lists that FHIR defines are hierarchical - each code is assigned a level. In this scheme, some codes are under other codes, and imply that the code they are under also applies
Source | The source of the definition of the code (when the value set draws in codes defined elsewhere)
Code | The code (used as the code in the resource instance). If the code is in italics, this indicates that the code is not selectable ('Abstract')
Display | The display (used in the display element of a Coding). If there is no display, implementers should not simply display the code, but map the concept into their application
Definition | An explanation of the meaning of the concept
Comments | Additional notes about how to use the code

4.2.12.561 Code System http://hl7.org/fhir/ex-relatedclaimrelationship

URL: https://hl7.org/fhir/STU3/codesystem-related-claim-relationship.html

This page is part of the FHIR Specification (v3.0.2: STU 3). The current version which supercedes this version is 4.0.1. For a full list of available versions, see the Directory of published versions

Vocabulary Work Group | Maturity Level: 1 | Draft | Use Context: Not Intended for Production use

This is a code system defined by the FHIR project.

Summary

Defining URL: | http://hl7.org/fhir/ex-relatedclaimrelationship
Name: | Example Related Claim Relationship Codes

Definition: | This value set includes sample Related Claim Relationship codes.
Committee: | Financial Management Work Group
OID: | 2.16.840.1.113883.4.642.1.561 (for OID based terminology systems)
Copyright: | This is an example set.
Source Resource | XML / JSON

This Code system is used in the following value sets:

* Example Related Claim Relationship Codes (This value set includes sample Related Claim Relationship codes.)

4.2.12.561.1 Content

4.2.12.561.2 Example Related Claim Relationship Codes

This value set includes sample Related Claim Relationship codes.

Copyright Statement: This is an example set.

This code system http://hl7.org/fhir/ex-relatedclaimrelationship defines the following codes:

Code | Display | Definition
prior | Prior Claim | A prior claim instance for the same intended suite of services.
associated | Associated Claim | A claim for a different suite of services which is related the suite claimed here.

See the full registry of value sets defined as part of FHIR.

Explanation of the columns that may appear on this page:

Level | A few code lists that FHIR defines are hierarchical - each code is assigned a level. In this scheme, some codes are under other codes, and imply that the code they are under also applies
Source | The source of the definition of the code (when the value set draws in codes defined elsewhere)
Code | The code (used as the code in the resource instance). If the code is in italics, this indicates that the code is not selectable ('Abstract')
Display | The display (used in the display element of a Coding). If there is no display, implementers should not simply display the code, but map the concept into their application
Definition | An explanation of the meaning of the concept
Comments | Additional notes about how to use the code

4.2.12.563 Code System http://hl7.org/fhir/ex-providerqualification

URL: https://hl7.org/fhir/STU3/codesystem-provider-qualification.html

This page is part of the FHIR Specification (v3.0.2: STU 3). The current version which supercedes this version is 4.0.1. For a full list of available versions, see the Directory of published versions

Vocabulary Work Group | Maturity Level: 1 | Draft | Use Context: Not Intended for Production use

This is a code system defined by the FHIR project.

Summary

Defining URL: | http://hl7.org/fhir/ex-providerqualification
Name: | Example Provider Qualification Codes
Definition: | This value set includes sample Provider Qualification codes.
Committee: | Financial Management Work Group
OID: | 2.16.840.1.113883.4.642.1.563 (for OID based terminology systems)
Copyright: | This is an example set.
Source Resource | XML / JSON

This Code system is used in the following value sets:

* Example Provider Qualification Codes (This value set includes sample Provider Qualification codes.)

4.2.12.563.1 Content

4.2.12.563.2 Example Provider Qualification Codes

This value set includes sample Provider Qualification codes.

Copyright Statement: This is an example set.

This code system http://hl7.org/fhir/ex-providerqualification defines the following codes:

Code | Display | Definition
311405 | Dentist | Dentist General Practitioner (DDS, DDM).
604215 | Ophthalmologist | Ophthalmologist.
604210 | Optometrist | Optometrist.

See the full registry of value sets defined as part of FHIR.

Explanation of the columns that may appear on this page:

Level | A few code lists that FHIR defines are hierarchical - each code is assigned a level. In this scheme, some codes are under other codes, and imply that the code they are under also applies
Source | The source of the definition of the code (when the value set draws in codes defined elsewhere)
Code | The code (used as the code in the resource instance). If the code is in italics, this indicates that the code is not selectable ('Abstract')
Display | The display (used in the display element of a Coding). If there is no display, implementers should not simply display the code, but map the concept into their application

Definition | An explanation of the meaning of the concept
Comments | Additional notes about how to use the code

4.2.12.565 Code System http://hl7.org/fhir/ex-servicemodifier

URL: https://hl7.org/fhir/STU3/codesystem-service-modifiers.html

This page is part of the FHIR Specification (v3.0.2: STU 3). The current version which supercedes this version is 4.0.1. For a full list of available versions, see the Directory of published versions

Vocabulary Work Group | Maturity Level: 0 | Informative | Use Context: Not Intended for Production use

This is a code system defined by the FHIR project.

Summary

Defining URL: | http://hl7.org/fhir/ex-servicemodifier
Name: | Example Service Modifier Codes
Definition: | This value set includes sample Service Modifier codes which may support differential payment.
Committee: | Financial Management Work Group
OID: | 2.16.840.1.113883.4.642.1.565 (for OID based terminology systems)
Copyright: | This is an example set.
Source Resource | XML / JSON

This Code system is used in the following value sets:

* Example Service Modifier Codes (This value set includes sample Service Modifier codes.)

4.2.12.565.1 Content

4.2.12.565.2 Example Service Modifier Codes

This value set includes sample Service Modifier codes which may support differential payment.

Copyright Statement: This is an example set.

This code system http://hl7.org/fhir/ex-servicemodifier defines the following codes:

Code | Display | Definition
sr | Side of the Road | Services provided on the side of the raod or such other non-conventional setting.
ah | After hours | Services provided outside or normal business hours.

See the full registry of value sets defined as part of FHIR.

Explanation of the columns that may appear on this page:

Level | A few code lists that FHIR defines are hierarchical - each code is assigned a level. In this scheme, some codes are under other codes, and imply that the code they are under also applies
Source | The source of the definition of the code (when the value set draws in codes defined elsewhere)
Code | The code (used as the code in the resource instance). If the code is in italics, this indicates that the code is not selectable ('Abstract')
Display | The display (used in the display element of a Coding). If there is no display, implementers should not simply display the code, but map the concept into their application
Definition | An explanation of the meaning of the concept
Comments | Additional notes about how to use the code

4.2.12.567 Code System http://hl7.org/fhir/sid/ex-icd-10-procedures

URL: https://hl7.org/fhir/STU3/codesystem-icd-10-procedures.html

This page is part of the FHIR Specification (v3.0.2: STU 3). The current version which supercedes this version is 4.0.1. For a full list of available versions, see the Directory of published versions

Vocabulary Work Group | Maturity Level: 1 | Draft | Use Context: Not Intended for Production use

This is a code system defined by the FHIR project.

Summary

Defining URL: | http://hl7.org/fhir/sid/ex-icd-10-procedures
Name: | ICD-10 Procedure Codes
Definition: | This value set includes sample ICD-10 Procedure codes.
Committee: | Financial Management Work Group
OID: | 2.16.840.1.113883.4.642.1.567 (for OID based terminology systems)
Copyright: | This is an example set.
Source Resource | XML / JSON

This Code system is used in the following value sets:

* ICD-10 Procedure Codes (This value set includes sample ICD-10 Procedure codes.)

4.2.12.567.1 Content

4.2.12.567.2 ICD-10 Procedure Codes

This value set includes sample ICD-10 Procedure codes.

Copyright Statement: This is an example set.

This code system http://hl7.org/fhir/sid/ex-icd-10-procedures defines the following codes:

Code | Display | Definition
123001 | PROC-1 | Procedure 1
123002 | PROC-2 | Procedure 2
123003 | PROC-3 | Procedure 3

See the full registry of value sets defined as part of FHIR.

Explanation of the columns that may appear on this page:

Level | A few code lists that FHIR defines are hierarchical - each code is assigned a level. In this scheme, some codes are under other codes, and imply that the code they are under also applies
Source | The source of the definition of the code (when the value set draws in codes defined elsewhere)
Code | The code (used as the code in the resource instance). If the code is in italics, this indicates that the code is not selectable ('Abstract')
Display | The display (used in the display element of a Coding). If there is no display, implementers should not simply display the code, but map the concept into their application
Definition | An explanation of the meaning of the concept
Comments | Additional notes about how to use the code

4.2.12.569 Code System http://hl7.org/fhir/ex-programcode

URL: https://hl7.org/fhir/STU3/codesystem-ex-program-code.html

This page is part of the FHIR Specification (v3.0.2: STU 3). The current version which supercedes this version is 4.0.1. For a full list of available versions, see the Directory of published versions

Vocabulary Work Group | Maturity Level: 1 | Draft | Use Context: Not Intended for Production use

This is a code system defined by the FHIR project.

Summary

Defining URL: | http://hl7.org/fhir/ex-programcode
Name: | Example Program Reason Codes
Definition: | This value set includes sample Program Reason Span codes.
Committee: | Financial Management Work Group
OID: | 2.16.840.1.113883.4.642.1.569 (for OID based terminology systems)
Copyright: | This is an example set.
Source Resource | XML / JSON

This Code system is used in the following value sets:

* Example Program Reason Codes (This value set includes sample Program Reason Span codes.)

4.2.12.569.1 Content

4.2.12.569.2 Example Program Reason Codes

This value set includes sample Program Reason Span codes.

Copyright Statement: This is an example set.

This code system http://hl7.org/fhir/ex-programcode defines the following codes:

Code | Display | Definition
as | Child Asthma | Child Asthma Program
hd | Heamodialisis | Heamodialisis Program.
auscr | Autism Screening | Autism Screening Program.
none | None | No program code applies.

See the full registry of value sets defined as part of FHIR.

Explanation of the columns that may appear on this page:

Level | A few code lists that FHIR defines are hierarchical - each code is assigned a level. In this scheme, some codes are under other codes, and imply that the code they are under also applies
Source | The source of the definition of the code (when the value set draws in codes defined elsewhere)
Code | The code (used as the code in the resource instance). If the code is in italics, this indicates that the code is not selectable ('Abstract')
Display | The display (used in the display element of a Coding). If there is no display, implementers should not simply display the code, but map the concept into their application
Definition | An explanation of the meaning of the concept
Comments | Additional notes about how to use the code

4.2.12.571 Code System http://hl7.org/fhir/ex-onsettype

URL: https://hl7.org/fhir/STU3/codesystem-ex-onsettype.html

This page is part of the FHIR Specification (v3.0.2: STU 3). The current version which supercedes this version is 4.0.1. For a full list of available versions, see the Directory of published versions

Vocabulary Work Group | Maturity Level: 0 | Informative | Use Context: Not Intended for Production use

This is a code system defined by the FHIR project.

Summary

Defining URL: | http://hl7.org/fhir/ex-onsettype
Name: | Example Onset Type (Reason) Codes
Definition: | This value set includes example Onset Type codes which are used to identify the event for which the onset, starting date, is required.
Committee: | Financial Management Work Group
OID: | 2.16.840.1.113883.4.642.1.571 (for OID based terminology systems)
Copyright: | This is an example set.
Source Resource | XML / JSON

This Code system is used in the following value sets:

* Example Onset Type (Reason) Codes (This value set includes sample Service Modifier codes.)

4.2.12.571.1 Content

4.2.12.571.2 Example Onset Type (Reason) Codes

This value set includes example Onset Type codes which are used to identify the event for which the onset, starting date, is required.

Copyright Statement: This is an example set.

This code system http://hl7.org/fhir/ex-onsettype defines the following codes:

Code | Display | Definition
lxm | Last Exam | Date of last examination.
sym | Start of Symptoms | Date when symptoms were first noticed..
lmn | Last Menstruation | Start date of last menstruation.

See the full registry of value sets defined as part of FHIR.

Explanation of the columns that may appear on this page:

Level | A few code lists that FHIR defines are hierarchical - each code is assigned a level. In this scheme, some codes are under other codes, and imply that the code they are under also applies
Source | The source of the definition of the code (when the value set draws in codes defined elsewhere)
Code | The code (used as the code in the resource instance). If the code is in italics, this indicates that the code is not selectable ('Abstract')
Display | The display (used in the display element of a Coding). If there is no display, implementers should not simply display the code, but map the concept into their application
Definition | An explanation of the meaning of the concept
Comments | Additional notes about how to use the code

4.2.12.573 Code System http://hl7.org/fhir/claim-exception

URL: https://hl7.org/fhir/STU3/codesystem-claim-exception.html

This page is part of the FHIR Specification (v3.0.2: STU 3). The current version which supercedes this version is 4.0.1. For a full list of available versions, see the Directory of published versions

Vocabulary Work Group | Maturity Level: 1 | Informative | Use Context: Not Intended for Production use

This is a code system defined by the FHIR project.

Summary

Defining URL: | http://hl7.org/fhir/claim-exception
Name: | Exception Codes
Definition: | This value set includes sample Exception codes.
Committee: | Financial Management Work Group
OID: | 2.16.840.1.113883.4.642.1.573 (for OID based terminology systems)
Copyright: | This is an example set.
Source Resource | XML / JSON

This Code system is used in the following value sets:

* Exception Codes (This value set includes sample Exception codes.)

4.2.12.573.1 Content

4.2.12.573.2 Exception Codes

This value set includes sample Exception codes.

Copyright Statement: This is an example set.

This code system http://hl7.org/fhir/claim-exception defines the following codes:

Code | Display | Definition
student | Student (Fulltime) | Fulltime Student
disabled | Disabled | Disabled

See the full registry of value sets defined as part of FHIR.

Explanation of the columns that may appear on this page:

Level | A few code lists that FHIR defines are hierarchical - each code is assigned a level. In this scheme, some codes are under other codes, and imply that the code they are under also applies
Source | The source of the definition of the code (when the value set draws in codes defined elsewhere)
Code | The code (used as the code in the resource instance). If the code is in italics, this indicates that the code is not selectable ('Abstract')
Display | The display (used in the display element of a Coding). If there is no display, implementers should not simply display the code, but map the concept into their application
Definition | An explanation of the meaning of the concept
Comments | Additional notes about how to use the code

4.2.12.575 Code System http://hl7.org/fhir/claiminformationcategory

URL: https://hl7.org/fhir/STU3/codesystem-claim-informationcategory.html

This page is part of the FHIR Specification (v3.0.2: STU 3). The current version which supercedes this version is 4.0.1. For a full list of available versions, see the Directory of published versions

Vocabulary Work Group | Maturity Level: 1 | Informative | Use Context: Not Intended for Production use

This is a code system defined by the FHIR project.

Summary

Defining URL: | http://hl7.org/fhir/claiminformationcategory
Name: | Claim Information Category Codes
Definition: | This value set includes sample Information Category codes.
Committee: | Financial Management Work Group
OID: | 2.16.840.1.113883.4.642.1.575 (for OID based terminology systems)
Copyright: | This is an example set.
Source Resource | XML / JSON

This Code system is used in the following value sets:

* Claim Information Category Codes (This value set includes sample Information Category codes.)

4.2.12.575.1 Content

4.2.12.575.2 Claim Information Category Codes

This value set includes sample Information Category codes.

Copyright Statement: This is an example set.

This code system http://hl7.org/fhir/claiminformationcategory defines the following codes:

Code | Display | Definition
info | Information | Codes conveying additional situation and condition information.
discharge | Discharge | Discharge status and discharge to locations.
onset | Onset | Period, start or end dates of aspects of the Condition.
related | Related Services | Nature and date of the related event eg. Last exam, service, Xray etc.
exception | Exception | Insurance policy exceptions.
material | Materials Forwarded | Materials being forwarded, eg. Models, molds, images, documents.
attachment | Attachment | Materials attached such as images, documents and resources.
missingtooth | Missing Tooth | Teeth which are missing for any reason, for example: prior extraction, never developed.
prosthesis | Prosthesis | The type of prosthesis and date of supply if a previously supplied prosthesis.
other | Other | Other information identified by the type.system.

See the full registry of value sets defined as part of FHIR.

Explanation of the columns that may appear on this page:

Level | A few code lists that FHIR defines are hierarchical - each code is assigned a level. In this scheme, some codes are under other codes, and imply that the code they are under also applies
Source | The source of the definition of the code (when the value set draws in codes defined elsewhere)
Code | The code (used as the code in the resource instance). If the code is in italics, this indicates that the code is not selectable ('Abstract')
Display | The display (used in the display element of a Coding). If there is no display, implementers should not simply display the code, but map the concept into their application
Definition | An explanation of the meaning of the concept
Comments | Additional notes about how to use the code

4.2.12.577 Code System http://hl7.org/fhir/ex-payee-resource-type

URL: https://hl7.org/fhir/STU3/codesystem-ex-payee-resource-type.html

This page is part of the FHIR Specification (v3.0.2: STU 3). The current version which supercedes this version is 4.0.1. For a full list of available versions, see the Directory of published versions

Vocabulary Work Group | Maturity Level: 1 | Informative | Use Context: Any

This is a code system defined by the FHIR project.

Summary

Defining URL: | http://hl7.org/fhir/ex-payee-resource-type
Name: | ClaimPayeeResourceType

Definition: | The type of Claim payee Resource
Committee: | Financial Management Work Group
OID: | 2.16.840.1.113883.4.642.1.577 (for OID based terminology systems)
Source Resource | XML / JSON

This Code system is used in the following value sets:

* ClaimPayeeResourceType (The type of Claim payee Resource)

4.2.12.577.1 Content

4.2.12.577.2 ClaimPayeeResourceType

The type of Claim payee Resource

This code system http://hl7.org/fhir/ex-payee-resource-type defines the following codes:

Code | Display | Definition
organization | Organization | Organization resource
patient | Patient | Patient resource
practitioner | Practitioner | Practitioner resource
relatedperson | RelatedPerson | RelatedPerson resource

See the full registry of value sets defined as part of FHIR.

Explanation of the columns that may appear on this page:

Level | A few code lists that FHIR defines are hierarchical - each code is assigned a level. In this scheme, some codes are under other codes, and imply that the code they are under also applies
Source | The source of the definition of the code (when the value set draws in codes defined elsewhere)
Code | The code (used as the code in the resource instance). If the code is in italics, this indicates that the code is not selectable ('Abstract')
Display | The display (used in the display element of a Coding). If there is no display, implementers should not simply display the code, but map the concept into their application
Definition | An explanation of the meaning of the concept
Comments | Additional notes about how to use the code

4.2.12.579 Code System http://hl7.org/fhir/claimcareteamrole

URL: https://hl7.org/fhir/STU3/codesystem-claim-careteamrole.html

This page is part of the FHIR Specification (v3.0.2: STU 3). The current version which supercedes this version is 4.0.1. For a full list of available versions, see the Directory of published versions

Vocabulary Work Group | Maturity Level: 1 | Informative | Use Context: Not Intended for Production use

This is a code system defined by the FHIR project.

Summary

Defining URL: | http://hl7.org/fhir/claimcareteamrole
Name: | Claim Care Team Role Codes
Definition: | This value set includes sample Claim Care Team Role codes.
Committee: | Financial Management Work Group
OID: | 2.16.840.1.113883.4.642.1.579 (for OID based terminology systems)
Copyright: | This is an example set.
Source Resource | XML / JSON

This Code system is used in the following value sets:

* Claim Care Team Role Codes (This value set includes sample Claim Care Team Role codes.)

4.2.12.579.1 Content

4.2.12.579.2 Claim Care Team Role Codes

This value set includes sample Claim Care Team Role codes.

Copyright Statement: This is an example set.

This code system http://hl7.org/fhir/claimcareteamrole defines the following codes:

Code | Display | Definition
primary | Primary provider | The primary care provider.
assist | Assisting Provider | Assisting care provider.
supervisor | Supervising Provider | Supervising care provider.
other | Other | Other role on the care team.

See the full registry of value sets defined as part of FHIR.

Explanation of the columns that may appear on this page:

Level | A few code lists that FHIR defines are hierarchical - each code is assigned a level. In this scheme, some codes are under other codes, and imply that the code they are under also applies
Source | The source of the definition of the code (when the value set draws in codes defined elsewhere)
Code | The code (used as the code in the resource instance). If the code is in italics, this indicates that the code is not selectable ('Abstract')

Display | The display (used in the display element of a Coding). If there is no display, implementers should not simply display the code, but map the concept into their application
Definition | An explanation of the meaning of the concept
Comments | Additional notes about how to use the code

4.2.12.581 Code System http://hl7.org/fhir/ex-diagnosisrelatedgroup

URL: https://hl7.org/fhir/STU3/codesystem-ex-diagnosisrelatedgroup.html

This page is part of the FHIR Specification (v3.0.2: STU 3). The current version which supercedes this version is 4.0.1. For a full list of available versions, see the Directory of published versions

Vocabulary Work Group | Maturity Level: 1 | Informative | Use Context: Not Intended for Production use

This is a code system defined by the FHIR project.

Summary

Defining URL: | http://hl7.org/fhir/ex-diagnosisrelatedgroup
Name: | Example Diagnosis Related Group Codes
Definition: | This value set includes example Diagnosis Related Group codes.
Committee: | Financial Management Work Group
OID: | 2.16.840.1.113883.4.642.1.581 (for OID based terminology systems)
Copyright: | This is an example set.
Source Resource | XML / JSON

This Code system is used in the following value sets:

* Example Diagnosis Related Group Codes (This value set includes example Diagnosis Related Group codes.)

4.2.12.581.1 Content

4.2.12.581.2 Example Diagnosis Related Group Codes

This value set includes example Diagnosis Related Group codes.

Copyright Statement: This is an example set.

This code system http://hl7.org/fhir/ex-diagnosisrelatedgroup defines the following codes:

Code | Display | Definition
100 | Normal Vaginal Delivery | Normal Vaginal Delivery.
101 | Appendectomy - uncomplicated | Appendectomy without rupture or other complications.
300 | Tooth abcess | Emergency department treatment of a tooth abcess.
400 | Head trauma - concussion | Head trauma - concussion.

See the full registry of value sets defined as part of FHIR.

Explanation of the columns that may appear on this page:

Level | A few code lists that FHIR defines are hierarchical - each code is assigned a level. In this scheme, some codes are under other codes, and imply that the code they are under also applies
Source | The source of the definition of the code (when the value set draws in codes defined elsewhere)
Code | The code (used as the code in the resource instance). If the code is in italics, this indicates that the code is not selectable ('Abstract')
Display | The display (used in the display element of a Coding). If there is no display, implementers should not simply display the code, but map the concept into their application
Definition | An explanation of the meaning of the concept
Comments | Additional notes about how to use the code

4.2.12.583 Code System http://hl7.org/fhir/ex-diagnosistype

URL: https://hl7.org/fhir/STU3/codesystem-ex-diagnosistype.html

This page is part of the FHIR Specification (v3.0.2: STU 3). The current version which supercedes this version is 4.0.1. For a full list of available versions, see the Directory of published versions

Vocabulary Work Group | Maturity Level: 1 | Informative | Use Context: Not Intended for Production use

This is a code system defined by the FHIR project.

Summary

Defining URL: | http://hl7.org/fhir/ex-diagnosistype
Name: | Example Diagnosis Type Codes
Definition: | This value set includes example Diagnosis Type codes.
Committee: | Financial Management Work Group
OID: | 2.16.840.1.113883.4.642.1.583 (for OID based terminology systems)
Copyright: | This is an example set.
Source Resource | XML / JSON

This Code system is used in the following value sets:

* Example Diagnosis Type Codes (This value set includes example Diagnosis Type codes.)

4.2.12.583.1 Content

4.2.12.583.2 Example Diagnosis Type Codes

This value set includes example Diagnosis Type codes.

Copyright Statement: This is an example set.

This code system http://hl7.org/fhir/ex-diagnosistype defines the following codes:

Code | Display | Definition
admitting | Admitting Diagnosis | The diagnosis given as the reason why the patient was admitted to the hospital.
clinical | Clinical Diagnosis | A diagnosis made on the basis of medical signs and patient-reported symptoms, rather than diagnostic tests.
differential | Differential Diagnosis | One of a set of the possible diagnoses that could be connected to the signs, symptoms, and lab findings.
discharge | Discharge Diagnosis | The diagnosis given when the patient is discharged from the hospital.
laboratory | Laboratory Diagnosis | A diagnosis based significantly on laboratory reports or test results, rather than the physical examination of the patient.
nursing | Nursing Diagnosis | A diagnosis which identifies people's responses to situations in their lives, such as a readiness to change or a willingness to accept assistance.
prenatal | Prenatal Diagnosis | A diagnosis determined prior to birth.
principal | Principal Diagnosis | The single medical diagnosis that is most relevant to the patient's chief complaint or need for treatment.
radiology | Radiology Diagnosis | A diagnosis based primarily on the results from medical imaging studies.
remote | Remote Diagnosis | A diagnosis determined using telemedicine techniques.
retrospective | Retrospective Diagnosis | The labeling of an illness in a specific historical event using modern knowledge, methods and disease classifications.
self | Self Diagnosis | A diagnosis determined by the patient.

See the full registry of value sets defined as part of FHIR.

Explanation of the columns that may appear on this page:

Level | A few code lists that FHIR defines are hierarchical - each code is assigned a level. In this scheme, some codes are under other codes, and imply that the code they are under also applies
Source | The source of the definition of the code (when the value set draws in codes defined elsewhere)
Code | The code (used as the code in the resource instance). If the code is in italics, this indicates that the code is not selectable ('Abstract')
Display | The display (used in the display element of a Coding). If there is no display, implementers should not simply display the code, but map the concept into their application
Definition | An explanation of the meaning of the concept
Comments | Additional notes about how to use the code

4.2.12.585 Code System http://hl7.org/fhir/fm-status

URL: https://hl7.org/fhir/STU3/codesystem-fm-status.html

This page is part of the FHIR Specification (v3.0.2: STU 3). The current version which supercedes this version is 4.0.1. For a full list of available versions, see the Directory of published versions

Vocabulary Work Group | Maturity Level: 2 | Informative | Use Context: Not Intended for Production use

This is a code system defined by the FHIR project.

Summary

Defining URL: | http://hl7.org/fhir/fm-status
Name: | Financial Resource Status Codes
Definition: | This value set includes Status codes.
Committee: | Financial Management Work Group
OID: | 2.16.840.1.113883.4.642.1.585 (for OID based terminology systems)
Copyright: | HL7 International.
Source Resource | XML / JSON

This Code system is used in the following value sets:

* Financial Resource Status Codes (This value set includes Status codes.)

4.2.12.585.1 Content

4.2.12.585.2 Financial Resource Status Codes

This value set includes Status codes.

Copyright Statement: HL7 International.

This code system http://hl7.org/fhir/fm-status defines the following codes:

Code | Display | Definition
active | Active | The instance is currently in-force.
cancelled | Cancelled | The instance is withdrawn, rescinded or reversed.
draft | Draft | A new instance the contents of which is not complete.
entered-in-error | Entered in Error | The instance was entered in error.

See the full registry of value sets defined as part of FHIR.

Explanation of the columns that may appear on this page:

Level | A few code lists that FHIR defines are hierarchical - each code is assigned a level. In this scheme, some codes are under other codes, and imply that the code they are under also applies

Source | The source of the definition of the code (when the value set draws in codes defined elsewhere)
Code | The code (used as the code in the resource instance). If the code is in italics, this indicates that the code is not selectable ('Abstract')
Display | The display (used in the display element of a Coding). If there is no display, implementers should not simply display the code, but map the concept into their application
Definition | An explanation of the meaning of the concept
Comments | Additional notes about how to use the code

4.2.12.587 Code System http://hl7.org/fhir/ex-revenue-center

URL: https://hl7.org/fhir/STU3/codesystem-ex-revenue-center.html

This page is part of the FHIR Specification (v3.0.2: STU 3). The current version which supercedes this version is 4.0.1. For a full list of available versions, see the Directory of published versions

Vocabulary Work Group | Maturity Level: 1 | Informative | Use Context: Not Intended for Production use

This is a code system defined by the FHIR project.

Summary

Defining URL: | http://hl7.org/fhir/ex-revenue-center
Name: | Example Revenue Center Codes
Definition: | This value set includes sample Revenue Center codes.
Committee: | Financial Management Work Group
OID: | 2.16.840.1.113883.4.642.1.587 (for OID based terminology systems)
Copyright: | These codes have been appropriated from the UB04 code set owned and managed by the AHA. Users require a license from the AHA in order to use these codes. Note: the codes have been withdrawn in a later version.
Source Resource | XML / JSON

This Code system is used in the following value sets:

* Example Revenue Center Codes (This value set includes sample Revenue Center codes.)

4.2.12.587.1 Content

4.2.12.587.2 Example Revenue Center Codes

This value set includes sample Revenue Center codes.

Copyright Statement: These codes have been appropriated from the UB04 code set owned and managed by the AHA. Users require a license from the AHA in order to use these codes. Note: the codes have been withdrawn in a later version.

This code system http://hl7.org/fhir/ex-revenue-center defines the following codes:

Code | Display | Definition
0370 | Anaesthesia | Anaesthesia.
0420 | Physical Therapy | Physical Therapy.
0421 | Physical Therapy - | Physical Therapy - visit charge.
0440 | Speech-Language Pathology | Speech-Language Pathology.
0441 | Speech-Language Pathology - Visit | Speech-Language Pathology- visit charge
0450 | Emergency Room | Emergency Room
0451 | Emergency Room - EM/EMTALA | Emergency Room - EM/EMTALA
0452 | Emergency Room - beyond EMTALA | Emergency Room - beyond EMTALA
0010 | Vision Clinic | Vision Clinic

See the full registry of value sets defined as part of FHIR.

Explanation of the columns that may appear on this page:

Level | A few code lists that FHIR defines are hierarchical - each code is assigned a level. In this scheme, some codes are under other codes, and imply that the code they are under also applies
Source | The source of the definition of the code (when the value set draws in codes defined elsewhere)
Code | The code (used as the code in the resource instance). If the code is in italics, this indicates that the code is not selectable ('Abstract')
Display | The display (used in the display element of a Coding). If there is no display, implementers should not simply display the code, but map the concept into their application
Definition | An explanation of the meaning of the concept
Comments | Additional notes about how to use the code

4.2.12.589 Code System http://hl7.org/fhir/adjudication

URL: https://hl7.org/fhir/STU3/codesystem-adjudication.html

This page is part of the FHIR Specification (v3.0.2: STU 3). The current version which supercedes this version is 4.0.1. For a full list of available versions, see the Directory of published versions

Vocabulary Work Group | Maturity Level: 1 | Informative | Use Context: Not Intended for Production use

This is a code system defined by the FHIR project.

Summary

Defining URL: | http://hl7.org/fhir/adjudication
Name: | Adjudication Value Codes

Definition: | This value set includes a smattering of Adjudication Value codes which includes codes to indicate the amounts eligible under the plan, the amount of benefit, copays etc.
Committee: | Financial Management Work Group
OID: | 2.16.840.1.113883.4.642.1.589 (for OID based terminology systems)
Copyright: | This is an example set.
Source Resource | XML / JSON

This Code system is used in the following value sets:

* Adjudication Value Codes (This value set includes a smattering of Adjudication Value codes which includes codes to indicate the amounts eligible under the plan, the amount of benefit, copays etc.)

4.2.12.589.1 Content

4.2.12.589.2 Adjudication Value Codes

This value set includes a smattering of Adjudication Value codes which includes codes to indicate the amounts eligible under the plan, the amount of benefit, copays etc.

Copyright Statement: This is an example set.

This code system http://hl7.org/fhir/adjudication defines the following codes:

Code | Display | Definition
total | Total | Total submitted
copay | CoPay | Patient Co-Payment
eligible | Eligible Amount | Amount of the change which is considered for adjudication
deductible | Deductable | Amount deducted from the eligible amount prior to adjudication
eligpercent | Eligible % | Eligible Percentage
tax | Emergency Department | Emergency Department
benefit | Benefit Amount | Amount payable under the coverage

See the full registry of value sets defined as part of FHIR.

Explanation of the columns that may appear on this page:

Level | A few code lists that FHIR defines are hierarchical - each code is assigned a level. In this scheme, some codes are under other codes, and imply that the code they are under also applies
Source | The source of the definition of the code (when the value set draws in codes defined elsewhere)
Code | The code (used as the code in the resource instance). If the code is in italics, this indicates that the code is not selectable ('Abstract')
Display | The display (used in the display element of a Coding). If there is no display, implementers should not simply display the code, but map the concept into their application
Definition | An explanation of the meaning of the concept
Comments | Additional notes about how to use the code

4.2.12.591 Code System http://hl7.org/fhir/adjudication-reason

URL: https://hl7.org/fhir/STU3/codesystem-adjudication-reason.html

This page is part of the FHIR Specification (v3.0.2: STU 3). The current version which supercedes this version is 4.0.1. For a full list of available versions, see the Directory of published versions

Vocabulary Work Group | Maturity Level: 1 | Informative | Use Context: Not Intended for Production use

This is a code system defined by the FHIR project.

Summary

Defining URL: | http://hl7.org/fhir/adjudication-reason
Name: | Adjudication Reason Codes
Definition: | This value set includes smattering of Adjudication Reason codes.
Committee: | Financial Management Work Group
OID: | 2.16.840.1.113883.4.642.1.591 (for OID based terminology systems)
Copyright: | This is an example set.
Source Resource | XML / JSON

This Code system is used in the following value sets:

* Adjudication Reason Codes (This value set includes smattering of Adjudication Reason codes.)

4.2.12.591.1 Content

4.2.12.591.2 Adjudication Reason Codes

This value set includes smattering of Adjudication Reason codes.

Copyright Statement: This is an example set.

This code system http://hl7.org/fhir/adjudication-reason defines the following codes:

Code | Display | Definition
ar001 | Not covered | Not covered
ar002 | Plan Limit Reached | Plan Limit Reached

See the full registry of value sets defined as part of FHIR.

Explanation of the columns that may appear on this page:

Level | A few code lists that FHIR defines are hierarchical - each code is assigned a level. In this scheme, some codes are under other codes, and imply that the code they are under also applies
Source | The source of the definition of the code (when the value set draws in codes defined elsewhere)
Code | The code (used as the code in the resource instance). If the code is in italics, this indicates that the code is not selectable ('Abstract')
Display | The display (used in the display element of a Coding). If there is no display, implementers should not simply display the code, but map the concept into their application
Definition | An explanation of the meaning of the concept
Comments | Additional notes about how to use the code

4.2.12.593 Code System http://hl7.org/fhir/payment-adjustment-reason

URL: https://hl7.org/fhir/STU3/codesystem-payment-adjustment-reason.html

This page is part of the FHIR Specification (v3.0.2: STU 3). The current version which supercedes this version is 4.0.1. For a full list of available versions, see the Directory of published versions

Vocabulary Work Group | Maturity Level: 1 | Informative | Use Context: Not Intended for Production use

This is a code system defined by the FHIR project.

Summary

Defining URL: | http://hl7.org/fhir/payment-adjustment-reason
Name: | Payment Adjustment Reason Codes
Definition: | This value set includes smattering of Payment Adjustment Reason codes.
Committee: | Financial Management Work Group
OID: | 2.16.840.1.113883.4.642.1.593 (for OID based terminology systems)
Copyright: | This is an example set.
Source Resource | XML / JSON

This Code system is used in the following value sets:

* Payment Adjustment Reason Codes (This value set includes smattering of Payment Adjustment Reason codes.)

4.2.12.593.1 Content

4.2.12.593.2 Payment Adjustment Reason Codes

This value set includes smattering of Payment Adjustment Reason codes.

Copyright Statement: This is an example set.

This code system http://hl7.org/fhir/payment-adjustment-reason defines the following codes:

Code | Display | Definition
a001 | Prior Payment Reversal | Prior Payment Reversal
a002 | Prior Overpayment | Prior Overpayment

See the full registry of value sets defined as part of FHIR.

Explanation of the columns that may appear on this page:

Level | A few code lists that FHIR defines are hierarchical - each code is assigned a level. In this scheme, some codes are under other codes, and imply that the code they are under also applies
Source | The source of the definition of the code (when the value set draws in codes defined elsewhere)
Code | The code (used as the code in the resource instance). If the code is in italics, this indicates that the code is not selectable ('Abstract')
Display | The display (used in the display element of a Coding). If there is no display, implementers should not simply display the code, but map the concept into their application
Definition | An explanation of the meaning of the concept
Comments | Additional notes about how to use the code

4.2.12.595 Code System http://hl7.org/fhir/benefit-category

URL: https://hl7.org/fhir/STU3/codesystem-benefit-category.html

This page is part of the FHIR Specification (v3.0.2: STU 3). The current version which supercedes this version is 4.0.1. For a full list of available versions, see the Directory of published versions

Vocabulary Work Group | Maturity Level: 1 | Informative | Use Context: Not Intended for Production use

This is a code system defined by the FHIR project.

Summary

Defining URL: | http://hl7.org/fhir/benefit-category
Name: | Benefit Category Codes
Definition: | This value set includes a smattering of Benefit Category codes.
Committee: | Financial Management Work Group
OID: | 2.16.840.1.113883.4.642.1.595 (for OID based terminology systems)
Copyright: | This is an example set.
Source Resource | XML / JSON

This Code system is used in the following value sets:

* Benefit Category Codes (This value set includes a smattering of Benefit Category codes.)

4.2.12.595.1 Content

4.2.12.595.2 Benefit Category Codes

This value set includes a smattering of Benefit Category codes.

Copyright Statement: This is an example set.

This code system http://hl7.org/fhir/benefit-category defines the following codes:

Code | Display | Definition
oral | Dental and Oral Health Coverage | Dental and Oral Health Coverage
vision | Vision Health Coverage | Vision Health Coverage
medical | Medical Health Coverage | Medical Health Coverage
pharmacy | Pharmacy Coverage | Pharmacy Coverage

See the full registry of value sets defined as part of FHIR.

Explanation of the columns that may appear on this page:

Level | A few code lists that FHIR defines are hierarchical - each code is assigned a level. In this scheme, some codes are under other codes, and imply that the code they are under also applies
Source | The source of the definition of the code (when the value set draws in codes defined elsewhere)
Code | The code (used as the code in the resource instance). If the code is in italics, this indicates that the code is not selectable ('Abstract')
Display | The display (used in the display element of a Coding). If there is no display, implementers should not simply display the code, but map the concept into their application
Definition | An explanation of the meaning of the concept
Comments | Additional notes about how to use the code

4.2.12.597 Code System http://hl7.org/fhir/benefit-subcategory

URL: https://hl7.org/fhir/STU3/codesystem-benefit-subcategory.html

This page is part of the FHIR Specification (v3.0.2: STU 3). The current version which supercedes this version is 4.0.1. For a full list of available versions, see the Directory of published versions

Vocabulary Work Group | Maturity Level: 1 | Informative | Use Context: Not Intended for Production use

This is a code system defined by the FHIR project.

Summary

Defining URL: | http://hl7.org/fhir/benefit-subcategory
Name: | Benefit SubCategory Codes
Definition: | This value set includes a smattering of Benefit SubCategory codes.
Committee: | Financial Management Work Group
OID: | 2.16.840.1.113883.4.642.1.597 (for OID based terminology systems)
Copyright: | This is an example set.
Source Resource | XML / JSON

This Code system is used in the following value sets:

* Benefit SubCategory Codes (This value set includes a smattering of Benefit SubCategory codes.)

4.2.12.597.1 Content

4.2.12.597.2 Benefit SubCategory Codes

This value set includes a smattering of Benefit SubCategory codes.

Copyright Statement: This is an example set.

This code system http://hl7.org/fhir/benefit-subcategory defines the following codes:

Code | Display | Definition
1 | Medical Care | Medical Care.
2 | Surgical | Surgical.
3 | Consultation | Consultation.
4 | Diagnostic XRay | Diagnostic XRay.
5 | Diagnostic Lab | Diagnostic Lab.
14 | Renal Supplies | Renal Supplies excluding Dialysis.
23 | Diagnostic Dental | Diagnostic Dental.
24 | Periodontics | Periodontics.
25 | Restorative | Restorative.
26 | Endodontics | Endodontics.
27 | Maxillofacilial Prosthetics | Maxillofacilial Prosthetics.
28 | Adjunctive Dental Services | Adjunctive Dental Services.
30 | Health Benefit Plan Coverage | Health Benefit Plan Coverage.
35 | Dental Care | Dental Care.
36 | Dental Crowns | Dental Crowns.
37 | Dental Accident | Dental Accident.

49 | Hospital Room and Board | Hospital Room and Board.
55 | Major Medical | Major Medical.
56 | Medically Related Transportation | Medically Related Transportation.
61 | In-vitro Fertilization | In-vitro Fertilization.
62 | MRI Scan | MRI Scan.
63 | Donor Procedures | Donor Procedures such as organ harvest.
69 | Maternity | Maternity.
76 | Renal Dialysis | Renal dialysis.
F1 | Medical Coverage | Medical Coverage.
F3 | Dental Coverage | Dental Coverage.
F4 | Hearing Coverage | Hearing Coverage.
F6 | Vision Coverage | Vision Coverage.

See the full registry of value sets defined as part of FHIR.

Explanation of the columns that may appear on this page:

Level | A few code lists that FHIR defines are hierarchical - each code is assigned a level. In this scheme, some codes are under other codes, and imply that the code they are under also applies
Source | The source of the definition of the code (when the value set draws in codes defined elsewhere)
Code | The code (used as the code in the resource instance). If the code is in italics, this indicates that the code is not selectable ('Abstract')
Display | The display (used in the display element of a Coding). If there is no display, implementers should not simply display the code, but map the concept into their application
Definition | An explanation of the meaning of the concept
Comments | Additional notes about how to use the code

4.2.12.599 Code System http://hl7.org/fhir/benefit-type

URL: https://hl7.org/fhir/STU3/codesystem-benefit-type.html

This page is part of the FHIR Specification (v3.0.2: STU 3). The current version which supercedes this version is 4.0.1. For a full list of available versions, see the Directory of published versions

Vocabulary Work Group | Maturity Level: 1 | Informative | Use Context: Not Intended for Production use

This is a code system defined by the FHIR project.

Summary

Defining URL: | http://hl7.org/fhir/benefit-type
Name: | Benefit Type Codes
Definition: | This value set includes a smattering of Benefit type codes.
Committee: | Financial Management Work Group
OID: | 2.16.840.1.113883.4.642.1.599 (for OID based terminology systems)
Copyright: | This is an example set.
Source Resource | XML / JSON

This Code system is used in the following value sets:

* Benefit Type Codes (This value set includes a smattering of Benefit type codes.)

4.2.12.599.1 Content

4.2.12.599.2 Benefit Type Codes

This value set includes a smattering of Benefit type codes.

Copyright Statement: This is an example set.

This code system http://hl7.org/fhir/benefit-type defines the following codes:

Code | Display | Definition
benefit | Benefit | Maximum benefit allowable.
deductable | Deductable | Cost to be incurred before benefits are applied
visit | Visit | Service visit
room | Room | Type of room
copay | Copayment per service | Copayment per service
copay-percent | Copayment Percent per service | Copayment percentage per service
copay-maximum | Copayment maximum per service | Copayment maximum per service
vision-exam | Vision Exam | Vision Exam
vision-glasses | Vision Glasses | Frames and lenses
vision-contacts | Vision Contacts Coverage | Contact Lenses
medical-primarycare | Medical Primary Health Coverage | Medical Primary Health Coverage
pharmacy-dispense | Pharmacy Dispense Coverage | Pharmacy Dispense Coverage

See the full registry of value sets defined as part of FHIR.

Explanation of the columns that may appear on this page:

Level | A few code lists that FHIR defines are hierarchical - each code is assigned a level. In this scheme, some codes are under other codes, and imply that the code they are under also applies
Source | The source of the definition of the code (when the value set draws in codes defined elsewhere)
Code | The code (used as the code in the resource instance). If the code is in italics, this indicates that the code is not selectable ('Abstract')

Display | The display (used in the display element of a Coding). If there is no display, implementers should not simply display the code, but map the concept into their application
Definition | An explanation of the meaning of the concept
Comments | Additional notes about how to use the code

4.2.12.601 Code System http://hl7.org/fhir/benefit-network

URL: https://hl7.org/fhir/STU3/codesystem-benefit-network.html

This page is part of the FHIR Specification (v3.0.2: STU 3). The current version which supercedes this version is 4.0.1. For a full list of available versions, see the Directory of published versions

Vocabulary Work Group | Maturity Level: 1 | Informative | Use Context: Not Intended for Production use

This is a code system defined by the FHIR project.

Summary

Defining URL: | http://hl7.org/fhir/benefit-network
Name: | Network Type Codes
Definition: | This value set includes a smattering of Network type codes.
Committee: | Financial Management Work Group
OID: | 2.16.840.1.113883.4.642.1.601 (for OID based terminology systems)
Copyright: | This is an example set.
Source Resource | XML / JSON

This Code system is used in the following value sets:

* Network Type Codes (This value set includes a smattering of Network type codes.)

4.2.12.601.1 Content

4.2.12.601.2 Network Type Codes

This value set includes a smattering of Network type codes.

Copyright Statement: This is an example set.

This code system http://hl7.org/fhir/benefit-network defines the following codes:

Code | Display | Definition
in | In Network | Services rendered by a Network provider
out | Out of Network | Services rendered by a provider who is not in the Network

See the full registry of value sets defined as part of FHIR.

Explanation of the columns that may appear on this page:

Level | A few code lists that FHIR defines are hierarchical - each code is assigned a level. In this scheme, some codes are under other codes, and imply that the code they are under also applies
Source | The source of the definition of the code (when the value set draws in codes defined elsewhere)
Code | The code (used as the code in the resource instance). If the code is in italics, this indicates that the code is not selectable ('Abstract')
Display | The display (used in the display element of a Coding). If there is no display, implementers should not simply display the code, but map the concept into their application
Definition | An explanation of the meaning of the concept
Comments | Additional notes about how to use the code

4.2.12.603 Code System http://hl7.org/fhir/benefit-unit

URL: https://hl7.org/fhir/STU3/codesystem-benefit-unit.html

This page is part of the FHIR Specification (v3.0.2: STU 3). The current version which supercedes this version is 4.0.1. For a full list of available versions, see the Directory of published versions

Vocabulary Work Group | Maturity Level: 1 | Informative | Use Context: Not Intended for Production use

This is a code system defined by the FHIR project.

Summary

Defining URL: | http://hl7.org/fhir/benefit-unit
Name: | Unit Type Codes
Definition: | This value set includes a smattering of Unit type codes.
Committee: | Financial Management Work Group
OID: | 2.16.840.1.113883.4.642.1.603 (for OID based terminology systems)
Copyright: | This is an example set.
Source Resource | XML / JSON

This Code system is used in the following value sets:

* Unit Type Codes (This value set includes a smattering of Unit type codes.)

4.2.12.603.1 Content

4.2.12.603.2 Unit Type Codes

This value set includes a smattering of Unit type codes.

Copyright Statement: This is an example set.

This code system http://hl7.org/fhir/benefit-unit defines the following codes:

Code | Display | Definition
individual | Individual | A single individual
family | Family | A family, typically includes self, spous(s) and children to a defined age

See the full registry of value sets defined as part of FHIR.

Explanation of the columns that may appear on this page:

Level | A few code lists that FHIR defines are hierarchical - each code is assigned a level. In this scheme, some codes are under other codes, and imply that the code they are under also applies
Source | The source of the definition of the code (when the value set draws in codes defined elsewhere)
Code | The code (used as the code in the resource instance). If the code is in italics, this indicates that the code is not selectable ('Abstract')
Display | The display (used in the display element of a Coding). If there is no display, implementers should not simply display the code, but map the concept into their application
Definition | An explanation of the meaning of the concept
Comments | Additional notes about how to use the code

4.2.12.605 Code System http://hl7.org/fhir/benefit-term

URL: https://hl7.org/fhir/STU3/codesystem-benefit-term.html

This page is part of the FHIR Specification (v3.0.2: STU 3). The current version which supercedes this version is 4.0.1. For a full list of available versions, see the Directory of published versions

Vocabulary Work Group | Maturity Level: 1 | Informative | Use Context: Not Intended for Production use

This is a code system defined by the FHIR project.

Summary

Defining URL: | http://hl7.org/fhir/benefit-term
Name: | Benefit Term Codes
Definition: | This value set includes a smattering of Benefit Term codes.
Committee: | Financial Management Work Group
OID: | 2.16.840.1.113883.4.642.1.605 (for OID based terminology systems)
Copyright: | This is an example set.
Source Resource | XML / JSON

This Code system is used in the following value sets:

* Benefit Term Codes (This value set includes a smattering of Benefit Term codes.)

4.2.12.605.1 Content

4.2.12.605.2 Benefit Term Codes

This value set includes a smattering of Benefit Term codes.

Copyright Statement: This is an example set.

This code system http://hl7.org/fhir/benefit-term defines the following codes:

Code | Display | Definition
annual | Annual | Annual, renewing on the anniversary
day | Day | Per day
lifetime | Lifetime | For the total term, lifetime, of the policy or coverage

See the full registry of value sets defined as part of FHIR.

Explanation of the columns that may appear on this page:

Level | A few code lists that FHIR defines are hierarchical - each code is assigned a level. In this scheme, some codes are under other codes, and imply that the code they are under also applies
Source | The source of the definition of the code (when the value set draws in codes defined elsewhere)
Code | The code (used as the code in the resource instance). If the code is in italics, this indicates that the code is not selectable ('Abstract')
Display | The display (used in the display element of a Coding). If there is no display, implementers should not simply display the code, but map the concept into their application
Definition | An explanation of the meaning of the concept
Comments | Additional notes about how to use the code

4.2.12.607 Code System http://hl7.org/fhir/resource-type-link

URL: https://hl7.org/fhir/STU3/codesystem-resource-type-link.html

This page is part of the FHIR Specification (v3.0.2: STU 3). The current version which supercedes this version is 4.0.1. For a full list of available versions, see the Directory of published versions

Vocabulary Work Group | Maturity Level: 2 | Informative | Use Context: Any

This is a code system defined by the FHIR project.

Summary

Defining URL: | http://hl7.org/fhir/resource-type-link
Name: | PayeeResourceType
Definition: | The type of payee Resource
Committee: | Financial Management Work Group
OID: | 2.16.840.1.113883.4.642.1.607 (for OID based terminology systems)
Source Resource | XML / JSON

This Code system is used in the following value sets:

* PayeeResourceType (The type of payee Resource)

4.2.12.607.1 Content

4.2.12.607.2 PayeeResourceType

The type of payee Resource

This code system http://hl7.org/fhir/resource-type-link defines the following codes:

Code | Display | Definition
organization | Organization | Organization resource
patient | Patient | Patient resource
practitioner | Practitioner | Practitioner resource
relatedperson | RelatedPerson | RelatedPerson resource

See the full registry of value sets defined as part of FHIR.

Explanation of the columns that may appear on this page:

Level | A few code lists that FHIR defines are hierarchical - each code is assigned a level. In this scheme, some codes are under other codes, and imply that the code they are under also applies
Source | The source of the definition of the code (when the value set draws in codes defined elsewhere)
Code | The code (used as the code in the resource instance). If the code is in italics, this indicates that the code is not selectable ('Abstract')
Display | The display (used in the display element of a Coding). If there is no display, implementers should not simply display the code, but map the concept into their application
Definition | An explanation of the meaning of the concept
Comments | Additional notes about how to use the code

4.2.12.609 Code System http://hl7.org/fhir/ex-paymenttype

URL: https://hl7.org/fhir/STU3/codesystem-ex-paymenttype.html

This page is part of the FHIR Specification (v3.0.2: STU 3). The current version which supercedes this version is 4.0.1. For a full list of available versions, see the Directory of published versions

Vocabulary Work Group | Maturity Level: 1 | Informative | Use Context: Not Intended for Production use

This is a code system defined by the FHIR project.

Summary

Defining URL: | http://hl7.org/fhir/ex-paymenttype
Name: | Example Payment Type Codes
Definition: | This value set includes example Payment Type codes.
Committee: | Financial Management Work Group
OID: | 2.16.840.1.113883.4.642.1.609 (for OID based terminology systems)
Copyright: | This is an example set.
Source Resource | XML / JSON

This Code system is used in the following value sets:

* Example Payment Type Codes (This value set includes example Payment Type codes.)

4.2.12.609.1 Content

4.2.12.609.2 Example Payment Type Codes

This value set includes example Payment Type codes.

Copyright Statement: This is an example set.

This code system http://hl7.org/fhir/ex-paymenttype defines the following codes:

Code | Display | Definition
complete | Complete | Complete (final) payment of the benefit under the Claim less any adjustments.
partial | Partial | Partial payment of the benefit under the Claim less any adjustments.

See the full registry of value sets defined as part of FHIR.

Explanation of the columns that may appear on this page:

Level | A few code lists that FHIR defines are hierarchical - each code is assigned a level. In this scheme, some codes are under other codes, and imply that the code they are under also applies
Source | The source of the definition of the code (when the value set draws in codes defined elsewhere)

Code | The code (used as the code in the resource instance). If the code is in italics, this indicates that the code is not selectable ('Abstract')
Display | The display (used in the display element of a Coding). If there is no display, implementers should not simply display the code, but map the concept into their application
Definition | An explanation of the meaning of the concept
Comments | Additional notes about how to use the code

4.2.12.611 Code System http://hl7.org/fhir/explanationofbenefit-status

URL: https://hl7.org/fhir/STU3/codesystem-explanationofbenefit-status.html

This page is part of the FHIR Specification (v3.0.2: STU 3). The current version which supercedes this version is 4.0.1. For a full list of available versions, see the Directory of published versions

Vocabulary Work Group | Maturity Level: 2 | Informative | Use Context: Any

This is a code system defined by the FHIR project.

Summary

Defining URL: | http://hl7.org/fhir/explanationofbenefit-status
Name: | ExplanationOfBenefitStatus
Definition: | A code specifying the state of the resource instance.
Committee: | Financial Management Work Group
OID: | 2.16.840.1.113883.4.642.1.611 (for OID based terminology systems)
Source Resource | XML / JSON

This Code system is used in the following value sets:

* ExplanationOfBenefitStatus (A code specifying the state of the resource instance.)

4.2.12.611.1 Content

4.2.12.611.2 ExplanationOfBenefitStatus

A code specifying the state of the resource instance.

This code system http://hl7.org/fhir/explanationofbenefit-status defines the following codes:

Code | Display | Definition
active | Active | The resource instance is currently in-force.
cancelled | Cancelled | The resource instance is withdrawn, rescinded or reversed.
draft | Draft | A new resource instance the contents of which is not complete.
entered-in-error | Entered In Error | The resource instance was entered in error.

See the full registry of value sets defined as part of FHIR.

Explanation of the columns that may appear on this page:

Level | A few code lists that FHIR defines are hierarchical - each code is assigned a level. In this scheme, some codes are under other codes, and imply that the code they are under also applies
Source | The source of the definition of the code (when the value set draws in codes defined elsewhere)
Code | The code (used as the code in the resource instance). If the code is in italics, this indicates that the code is not selectable ('Abstract')
Display | The display (used in the display element of a Coding). If there is no display, implementers should not simply display the code, but map the concept into their application
Definition | An explanation of the meaning of the concept
Comments | Additional notes about how to use the code

4.2.12.613 Code System http://hl7.org/fhir/bundle-type

URL: https://hl7.org/fhir/STU3/codesystem-bundle-type.html

This page is part of the FHIR Specification (v3.0.2: STU 3). The current version which supercedes this version is 4.0.1. For a full list of available versions, see the Directory of published versions

Vocabulary Work Group | Maturity Level: 5 | Informative | Use Context: Any

This is a code system defined by the FHIR project.

Summary

Defining URL: | http://hl7.org/fhir/bundle-type
Name: | BundleType
Definition: | Indicates the purpose of a bundle - how it was intended to be used.
Committee: | FHIR Infrastructure Work Group
OID: | 2.16.840.1.113883.4.642.1.613 (for OID based terminology systems)
Source Resource | XML / JSON

This Code system is used in the following value sets:

* BundleType (Indicates the purpose of a bundle - how it was intended to be used.)

4.2.12.613.1 Content

4.2.12.613.2 BundleType

Indicates the purpose of a bundle - how it was intended to be used.

This code system http://hl7.org/fhir/bundle-type defines the following codes:

Code | Display | Definition
document | Document | The bundle is a document. The first resource is a Composition.
message | Message | The bundle is a message. The first resource is a MessageHeader.
transaction | Transaction | The bundle is a transaction - intended to be processed by a server as an atomic commit.
transaction-response | Transaction Response | The bundle is a transaction response. Because the response is a transaction response, the transaction has succeeded, and all responses are error free.
batch | Batch | The bundle is a transaction - intended to be processed by a server as a group of actions.
batch-response | Batch Response | The bundle is a batch response. Note that as a batch, some responses may indicate failure and others success.
history | History List | The bundle is a list of resources from a history interaction on a server.
searchset | Search Results | The bundle is a list of resources returned as a result of a search/query interaction, operation, or message.
collection | Collection | The bundle is a set of resources collected into a single package for ease of distribution.

See the full registry of value sets defined as part of FHIR.

Explanation of the columns that may appear on this page:

Level | A few code lists that FHIR defines are hierarchical - each code is assigned a level. In this scheme, some codes are under other codes, and imply that the code they are under also applies
Source | The source of the definition of the code (when the value set draws in codes defined elsewhere)
Code | The code (used as the code in the resource instance). If the code is in italics, this indicates that the code is not selectable ('Abstract')
Display | The display (used in the display element of a Coding). If there is no display, implementers should not simply display the code, but map the concept into their application
Definition | An explanation of the meaning of the concept
Comments | Additional notes about how to use the code

4.2.12.615 Code System http://hl7.org/fhir/search-entry-mode

URL: https://hl7.org/fhir/STU3/codesystem-search-entry-mode.html

This page is part of the FHIR Specification (v3.0.2: STU 3). The current version which supercedes this version is 4.0.1. For a full list of available versions, see the Directory of published versions

Vocabulary Work Group | Maturity Level: 5 | Informative | Use Context: Any

This is a code system defined by the FHIR project.

Summary

Defining URL: | http://hl7.org/fhir/search-entry-mode
Name: | SearchEntryMode
Definition: | Why an entry is in the result set - whether it's included as a match or because of an _include requirement.
Committee: | FHIR Infrastructure Work Group
OID: | 2.16.840.1.113883.4.642.1.615 (for OID based terminology systems)
Source Resource | XML / JSON

This Code system is used in the following value sets:

* SearchEntryMode (Why an entry is in the result set - whether it's included as a match or because of an _include requirement.)

4.2.12.615.1 Content

4.2.12.615.2 SearchEntryMode

Why an entry is in the result set - whether it's included as a match or because of an _include requirement.

This code system http://hl7.org/fhir/search-entry-mode defines the following codes:

Code | Display | Definition
match | Match | This resource matched the search specification.
include | Include | This resource is returned because it is referred to from another resource in the search set.
outcome | Outcome | An OperationOutcome that provides additional information about the processing of a search.

See the full registry of value sets defined as part of FHIR.

Explanation of the columns that may appear on this page:

Level | A few code lists that FHIR defines are hierarchical - each code is assigned a level. In this scheme, some codes are under other codes, and imply that the code they are under also applies
Source | The source of the definition of the code (when the value set draws in codes defined elsewhere)
Code | The code (used as the code in the resource instance). If the code is in italics, this indicates that the code is not selectable ('Abstract')
Display | The display (used in the display element of a Coding). If there is no display, implementers should not simply display the code, but map the concept into their application
Definition | An explanation of the meaning of the concept
Comments | Additional notes about how to use the code

4.2.12.617 Code System http://hl7.org/fhir/http-verb

URL: https://hl7.org/fhir/STU3/codesystem-http-verb.html

This page is part of the FHIR Specification (v3.0.2: STU 3). The current version which supercedes this version is 4.0.1. For a full list of available versions, see the Directory of published versions

Vocabulary Work Group | Maturity Level: 5 | Informative | Use Context: Any

This is a code system defined by the FHIR project.

Summary

Defining URL: | http://hl7.org/fhir/http-verb
Name: | HTTPVerb
Definition: | HTTP verbs (in the HTTP command line).
Committee: | FHIR Infrastructure Work Group
OID: | 2.16.840.1.113883.4.642.1.617 (for OID based terminology systems)
Source Resource | XML / JSON

This Code system is used in the following value sets:

* HTTPVerb (HTTP verbs (in the HTTP command line).)

4.2.12.617.1 Content

4.2.12.617.2 HTTPVerb

HTTP verbs (in the HTTP command line).

This code system http://hl7.org/fhir/http-verb defines the following codes:

Code | Display | Definition
GET | GET | HTTP GET
POST | POST | HTTP POST
PUT | PUT | HTTP PUT
DELETE | DELETE | HTTP DELETE

See the full registry of value sets defined as part of FHIR.

Explanation of the columns that may appear on this page:

Level | A few code lists that FHIR defines are hierarchical - each code is assigned a level. In this scheme, some codes are under other codes, and imply that the code they are under also applies
Source | The source of the definition of the code (when the value set draws in codes defined elsewhere)
Code | The code (used as the code in the resource instance). If the code is in italics, this indicates that the code is not selectable ('Abstract')
Display | The display (used in the display element of a Coding). If there is no display, implementers should not simply display the code, but map the concept into their application
Definition | An explanation of the meaning of the concept
Comments | Additional notes about how to use the code

4.2.12.619 Code System http://hl7.org/fhir/measurement-principle

URL: https://hl7.org/fhir/STU3/codesystem-measurement-principle.html

This page is part of the FHIR Specification (v3.0.2: STU 3). The current version which supercedes this version is 4.0.1. For a full list of available versions, see the Directory of published versions

Vocabulary Work Group | Maturity Level: 1 | Informative | Use Context: Any

This is a code system defined by the FHIR project.

Summary

Defining URL: | http://hl7.org/fhir/measurement-principle
Name: | MeasmntPrinciple
Definition: | Different measurement principle supported by the device.
Committee: | Health Care Devices Work Group
OID: | 2.16.840.1.113883.4.642.1.619 (for OID based terminology systems)
Source Resource | XML / JSON

This Code system is used in the following value sets:

* MeasmntPrinciple (Different measurement principle supported by the device.)

4.2.12.619.1 Content

4.2.12.619.2 MeasmntPrinciple

Different measurement principle supported by the device.

This code system http://hl7.org/fhir/measurement-principle defines the following codes:

Code | Display | Definition
other | MSP Other | Measurement principle isn't in the list.
chemical | MSP Chemical | Measurement is done using the chemical principle.
electrical | MSP Electrical | Measurement is done using the electrical principle.
impedance | MSP Impedance | Measurement is done using the impedance principle.
nuclear | MSP Nuclear | Measurement is done using the nuclear principle.
optical | MSP Optical | Measurement is done using the optical principle.

thermal | MSP Thermal | Measurement is done using the thermal principle.
biological | MSP Biological | Measurement is done using the biological principle.
mechanical | MSP Mechanical | Measurement is done using the mechanical principle.
acoustical | MSP Acoustical | Measurement is done using the acoustical principle.
manual | MSP Manual | Measurement is done using the manual principle.

See the full registry of value sets defined as part of FHIR.

Explanation of the columns that may appear on this page:

Level | A few code lists that FHIR defines are hierarchical - each code is assigned a level. In this scheme, some codes are under other codes, and imply that the code they are under also applies
Source | The source of the definition of the code (when the value set draws in codes defined elsewhere)
Code | The code (used as the code in the resource instance). If the code is in italics, this indicates that the code is not selectable ('Abstract')
Display | The display (used in the display element of a Coding). If there is no display, implementers should not simply display the code, but map the concept into their application
Definition | An explanation of the meaning of the concept
Comments | Additional notes about how to use the code

4.2.12.621 Code System http://hl7.org/fhir/search-xpath-usage

URL: https://hl7.org/fhir/STU3/codesystem-search-xpath-usage.html

This page is part of the FHIR Specification (v3.0.2: STU 3). The current version which supercedes this version is 4.0.1. For a full list of available versions, see the Directory of published versions

Vocabulary Work Group | Maturity Level: 3 | Informative | Use Context: Any

This is a code system defined by the FHIR project.

Summary

Defining URL: | http://hl7.org/fhir/search-xpath-usage
Name: | XPathUsageType
Definition: | How a search parameter relates to the set of elements returned by evaluating its xpath query.
Committee: | FHIR Infrastructure Work Group
OID: | 2.16.840.1.113883.4.642.1.621 (for OID based terminology systems)
Source Resource | XML / JSON

This Code system is used in the following value sets:

* XPathUsageType (How a search parameter relates to the set of elements returned by evaluating its xpath query.)

4.2.12.621.1 Content

4.2.12.621.2 XPathUsageType

How a search parameter relates to the set of elements returned by evaluating its xpath query.

This code system http://hl7.org/fhir/search-xpath-usage defines the following codes:

Code | Display | Definition
normal | Normal | The search parameter is derived directly from the selected nodes based on the type definitions.
phonetic | Phonetic | The search parameter is derived by a phonetic transform from the selected nodes.
nearby | Nearby | The search parameter is based on a spatial transform of the selected nodes.
distance | Distance | The search parameter is based on a spatial transform of the selected nodes, using physical distance from the middle.
other | Other | The interpretation of the xpath statement is unknown (and can't be automated).

See the full registry of value sets defined as part of FHIR.

Explanation of the columns that may appear on this page:

Level | A few code lists that FHIR defines are hierarchical - each code is assigned a level. In this scheme, some codes are under other codes, and imply that the code they are under also applies
Source | The source of the definition of the code (when the value set draws in codes defined elsewhere)
Code | The code (used as the code in the resource instance). If the code is in italics, this indicates that the code is not selectable ('Abstract')
Display | The display (used in the display element of a Coding). If there is no display, implementers should not simply display the code, but map the concept into their application
Definition | An explanation of the meaning of the concept
Comments | Additional notes about how to use the code

4.2.12.623 Code System http://hl7.org/fhir/search-comparator

URL: https://hl7.org/fhir/STU3/codesystem-search-comparator.html

This page is part of the FHIR Specification (v3.0.2: STU 3). The current version which supercedes this version is 4.0.1. For a full list of available versions, see the Directory of published versions

Vocabulary Work Group | Maturity Level: 3 | Informative | Use Context: Any

This is a code system defined by the FHIR project.

Summary

Defining URL: | http://hl7.org/fhir/search-comparator

Name: | SearchComparator
Definition: | What Search Comparator Codes are supported in search
Committee: | FHIR Infrastructure Work Group
OID: | 2.16.840.1.113883.4.642.1.623 (for OID based terminology systems)
Source Resource | XML / JSON

This Code system is used in the following value sets:

* SearchComparator (What Search Comparator Codes are supported in search)

4.2.12.623.1 Content

4.2.12.623.2 SearchComparator

What Search Comparator Codes are supported in search

This code system http://hl7.org/fhir/search-comparator defines the following codes:

Code | Display | Definition
eq | Equals | the value for the parameter in the resource is equal to the provided value
ne | Not Equals | the value for the parameter in the resource is not equal to the provided value
gt | Greater Than | the value for the parameter in the resource is greater than the provided value
lt | Less Then | the value for the parameter in the resource is less than the provided value
ge | Greater or Equals | the value for the parameter in the resource is greater or equal to the provided value
le | Less of Equal | the value for the parameter in the resource is less or equal to the provided value
sa | Starts After | the value for the parameter in the resource starts after the provided value
eb | Ends Before | the value for the parameter in the resource ends before the provided value
ap | Approximately | the value for the parameter in the resource is approximately the same to the provided value.

See the full registry of value sets defined as part of FHIR.

Explanation of the columns that may appear on this page:

Level | A few code lists that FHIR defines are hierarchical - each code is assigned a level. In this scheme, some codes are under other codes, and imply that the code they are under also applies
Source | The source of the definition of the code (when the value set draws in codes defined elsewhere)
Code | The code (used as the code in the resource instance). If the code is in italics, this indicates that the code is not selectable ('Abstract')
Display | The display (used in the display element of a Coding). If there is no display, implementers should not simply display the code, but map the concept into their application
Definition | An explanation of the meaning of the concept
Comments | Additional notes about how to use the code

4.2.12.625 Code System http://hl7.org/fhir/search-modifier-code

URL: https://hl7.org/fhir/STU3/codesystem-search-modifier-code.html

This page is part of the FHIR Specification (v3.0.2: STU 3). The current version which supercedes this version is 4.0.1. For a full list of available versions, see the Directory of published versions

Vocabulary Work Group | Maturity Level: 3 | Informative | Use Context: Any

This is a code system defined by the FHIR project.

Summary

Defining URL: | http://hl7.org/fhir/search-modifier-code
Name: | SearchModifierCode
Definition: | A supported modifier for a search parameter.
Committee: | FHIR Infrastructure Work Group
OID: | 2.16.840.1.113883.4.642.1.625 (for OID based terminology systems)
Source Resource | XML / JSON

This Code system is used in the following value sets:

* SearchModifierCode (A supported modifier for a search parameter.)

4.2.12.625.1 Content

4.2.12.625.2 SearchModifierCode

A supported modifier for a search parameter.

This code system http://hl7.org/fhir/search-modifier-code defines the following codes:

Code | Display | Definition
missing | Missing | The search parameter returns resources that have a value or not.
exact | Exact | The search parameter returns resources that have a value that exactly matches the supplied parameter (the whole string, including casing and accents).
contains | Contains | The search parameter returns resources that include the supplied parameter value anywhere within the field being searched.
not | Not | The search parameter returns resources that do not contain a match.
text | Text | The search parameter is processed as a string that searches text associated with the code/value - either CodeableConcept.text, Coding.display, or Identifier.type.text.

in | In | The search parameter is a URI (relative or absolute) that identifies a value set, and the search parameter tests whether the coding is in the specified value set.
not-in | Not In | The search parameter is a URI (relative or absolute) that identifies a value set, and the search parameter tests whether the coding is not in the specified value set.
below | Below | The search parameter tests whether the value in a resource is subsumed by the specified value (is-a, or hierarchical relationships).
above | Above | The search parameter tests whether the value in a resource subsumes the specified value (is-a, or hierarchical relationships).
type | Type | The search parameter only applies to the Resource Type specified as a modifier (e.g. the modifier is not actually :type, but :Patient etc.).

See the full registry of value sets defined as part of FHIR.

Explanation of the columns that may appear on this page:

Level | A few code lists that FHIR defines are hierarchical - each code is assigned a level. In this scheme, some codes are under other codes, and imply that the code they are under also applies
Source | The source of the definition of the code (when the value set draws in codes defined elsewhere)
Code | The code (used as the code in the resource instance). If the code is in italics, this indicates that the code is not selectable ('Abstract')
Display | The display (used in the display element of a Coding). If there is no display, implementers should not simply display the code, but map the concept into their application
Definition | An explanation of the meaning of the concept
Comments | Additional notes about how to use the code

4.2.12.627 Code System http://hl7.org/fhir/payment-type

URL: https://hl7.org/fhir/STU3/codesystem-payment-type.html

This page is part of the FHIR Specification (v3.0.2: STU 3). The current version which supercedes this version is 4.0.1. For a full list of available versions, see the Directory of published versions

Vocabulary Work Group | Maturity Level: 1 | Informative | Use Context: Not Intended for Production use

This is a code system defined by the FHIR project.

Summary

Defining URL: | http://hl7.org/fhir/payment-type
Name: | Payment Type Codes
Definition: | This value set includes sample Payment Type codes.
Committee: | Financial Management Work Group
OID: | 2.16.840.1.113883.4.642.1.627 (for OID based terminology systems)
Copyright: | This is an example set.
Source Resource | XML / JSON

This Code system is used in the following value sets:

* Payment Type Codes (This value set includes sample Payment Type codes.)

4.2.12.627.1 Content

4.2.12.627.2 Payment Type Codes

This value set includes sample Payment Type codes.

Copyright Statement: This is an example set.

This code system http://hl7.org/fhir/payment-type defines the following codes:

Code | Display | Definition
payment | Payment | The amount is partial or complete settlement of the amounts due.
adjustment | Adjustment | The amount is an adjustment regarding claims already paid.
advance | Advance | The amount is an advance against future claims.

See the full registry of value sets defined as part of FHIR.

Explanation of the columns that may appear on this page:

Level | A few code lists that FHIR defines are hierarchical - each code is assigned a level. In this scheme, some codes are under other codes, and imply that the code they are under also applies
Source | The source of the definition of the code (when the value set draws in codes defined elsewhere)
Code | The code (used as the code in the resource instance). If the code is in italics, this indicates that the code is not selectable ('Abstract')
Display | The display (used in the display element of a Coding). If there is no display, implementers should not simply display the code, but map the concept into their application
Definition | An explanation of the meaning of the concept
Comments | Additional notes about how to use the code

4.2.12.629 Code System http://hl7.org/fhir/paymentstatus

URL: https://hl7.org/fhir/STU3/codesystem-payment-status.html

This page is part of the FHIR Specification (v3.0.2: STU 3). The current version which supercedes this version is 4.0.1. For a full list of available versions, see the Directory of published versions

Vocabulary Work Group | Maturity Level: 1 | Informative | Use Context: Not Intended for Production use

This is a code system defined by the FHIR project.

Summary

Defining URL: | http://hl7.org/fhir/paymentstatus
Name: | Payment Status Codes
Definition: | This value set includes a sample set of Payment Status codes.
Committee: | Financial Management Work Group
OID: | 2.16.840.1.113883.4.642.1.629 (for OID based terminology systems)
Copyright: | This is an example set.
Source Resource | XML / JSON

This Code system is used in the following value sets:

* Payment Status Codes (This value set includes a sample set of Payment Status codes.)

4.2.12.629.1 Content

4.2.12.629.2 Payment Status Codes

This value set includes a sample set of Payment Status codes.

Copyright Statement: This is an example set.

This code system http://hl7.org/fhir/paymentstatus defines the following codes:

Code | Display | Definition
paid | Paid | The payment has been sent physically or electronically.
cleared | Cleared | The payment has been received by the payee.

See the full registry of value sets defined as part of FHIR.

Explanation of the columns that may appear on this page:

Level | A few code lists that FHIR defines are hierarchical - each code is assigned a level. In this scheme, some codes are under other codes, and imply that the code they are under also applies
Source | The source of the definition of the code (when the value set draws in codes defined elsewhere)
Code | The code (used as the code in the resource instance). If the code is in italics, this indicates that the code is not selectable ('Abstract')
Display | The display (used in the display element of a Coding). If there is no display, implementers should not simply display the code, but map the concept into their application
Definition | An explanation of the meaning of the concept
Comments | Additional notes about how to use the code

4.2.12.631 Code System http://hl7.org/fhir/metric-operational-status

URL: https://hl7.org/fhir/STU3/codesystem-metric-operational-status.html

This page is part of the FHIR Specification (v3.0.2: STU 3). The current version which supercedes this version is 4.0.1. For a full list of available versions, see the Directory of published versions

Vocabulary Work Group | Maturity Level: 1 | Informative | Use Context: Any

This is a code system defined by the FHIR project.

Summary

Defining URL: | http://hl7.org/fhir/metric-operational-status
Name: | DeviceMetricOperationalStatus
Definition: | Describes the operational status of the DeviceMetric.
Committee: | Health Care Devices Work Group
OID: | 2.16.840.1.113883.4.642.1.631 (for OID based terminology systems)
Source Resource | XML / JSON

This Code system is used in the following value sets:

* DeviceMetricOperationalStatus (Describes the operational status of the DeviceMetric.)

4.2.12.631.1 Content

4.2.12.631.2 DeviceMetricOperationalStatus

Describes the operational status of the DeviceMetric.

This code system http://hl7.org/fhir/metric-operational-status defines the following codes:

Code | Display | Definition
on | On | The DeviceMetric is operating and will generate DeviceObservations.
off | Off | The DeviceMetric is not operating.
standby | Standby | The DeviceMetric is operating, but will not generate any DeviceObservations.
entered-in-error | Entered In Error | The DeviceMetric was entered in error.

See the full registry of value sets defined as part of FHIR.

Explanation of the columns that may appear on this page:

Level | A few code lists that FHIR defines are hierarchical - each code is assigned a level. In this scheme, some codes are under other codes, and imply that the code they are under also applies
Source | The source of the definition of the code (when the value set draws in codes defined elsewhere)

Code | The code (used as the code in the resource instance). If the code is in italics, this indicates that the code is not selectable ('Abstract')
Display | The display (used in the display element of a Coding). If there is no display, implementers should not simply display the code, but map the concept into their application
Definition | An explanation of the meaning of the concept
Comments | Additional notes about how to use the code

4.2.12.633 Code System http://hl7.org/fhir/metric-category

URL: https://hl7.org/fhir/STU3/codesystem-metric-category.html

This page is part of the FHIR Specification (v3.0.2: STU 3). The current version which supercedes this version is 4.0.1. For a full list of available versions, see the Directory of published versions

Vocabulary Work Group | Maturity Level: 1 | Informative | Use Context: Any

This is a code system defined by the FHIR project.

Summary

Defining URL: | http://hl7.org/fhir/metric-category
Name: | DeviceMetricCategory
Definition: | Describes the category of the metric.
Committee: | Health Care Devices Work Group
OID: | 2.16.840.1.113883.4.642.1.633 (for OID based terminology systems)
Source Resource | XML / JSON

This Code system is used in the following value sets:

* DeviceMetricCategory (Describes the category of the metric.)

4.2.12.633.1 Content

4.2.12.633.2 DeviceMetricCategory

Describes the category of the metric.

This code system http://hl7.org/fhir/metric-category defines the following codes:

Code | Display | Definition
measurement | Measurement | DeviceObservations generated for this DeviceMetric are measured.
setting | Setting | DeviceObservations generated for this DeviceMetric is a setting that will influence the behavior of the Device.
calculation | Calculation | DeviceObservations generated for this DeviceMetric are calculated.
unspecified | Unspecified | The category of this DeviceMetric is unspecified.

See the full registry of value sets defined as part of FHIR.

Explanation of the columns that may appear on this page:

Level | A few code lists that FHIR defines are hierarchical - each code is assigned a level. In this scheme, some codes are under other codes, and imply that the code they are under also applies
Source | The source of the definition of the code (when the value set draws in codes defined elsewhere)
Code | The code (used as the code in the resource instance). If the code is in italics, this indicates that the code is not selectable ('Abstract')
Display | The display (used in the display element of a Coding). If there is no display, implementers should not simply display the code, but map the concept into their application
Definition | An explanation of the meaning of the concept
Comments | Additional notes about how to use the code

4.2.12.635 Code System http://hl7.org/fhir/metric-calibration-type

URL: https://hl7.org/fhir/STU3/codesystem-metric-calibration-type.html

This page is part of the FHIR Specification (v3.0.2: STU 3). The current version which supercedes this version is 4.0.1. For a full list of available versions, see the Directory of published versions

Vocabulary Work Group | Maturity Level: 1 | Informative | Use Context: Any

This is a code system defined by the FHIR project.

Summary

Defining URL: | http://hl7.org/fhir/metric-calibration-type
Name: | DeviceMetricCalibrationType
Definition: | Describes the type of a metric calibration.
Committee: | Health Care Devices Work Group
OID: | 2.16.840.1.113883.4.642.1.635 (for OID based terminology systems)
Source Resource | XML / JSON

This Code system is used in the following value sets:

* DeviceMetricCalibrationType (Describes the type of a metric calibration.)

4.2.12.635.1 Content

4.2.12.635.2 DeviceMetricCalibrationType

Describes the type of a metric calibration.

This code system http://hl7.org/fhir/metric-calibration-type defines the following codes:

Code | Display | Definition
unspecified | Unspecified | Metric calibration method has not been identified.
offset | Offset | Offset metric calibration method
gain | Gain | Gain metric calibration method
two-point | Two Point | Two-point metric calibration method

See the full registry of value sets defined as part of FHIR.

Explanation of the columns that may appear on this page:

Level | A few code lists that FHIR defines are hierarchical - each code is assigned a level. In this scheme, some codes are under other codes, and imply that the code they are under also applies
Source | The source of the definition of the code (when the value set draws in codes defined elsewhere)
Code | The code (used as the code in the resource instance). If the code is in italics, this indicates that the code is not selectable ('Abstract')
Display | The display (used in the display element of a Coding). If there is no display, implementers should not simply display the code, but map the concept into their application
Definition | An explanation of the meaning of the concept
Comments | Additional notes about how to use the code

4.2.12.637 Code System http://hl7.org/fhir/metric-calibration-state

URL: https://hl7.org/fhir/STU3/codesystem-metric-calibration-state.html

This page is part of the FHIR Specification (v3.0.2: STU 3). The current version which supercedes this version is 4.0.1. For a full list of available versions, see the Directory of published versions

Vocabulary Work Group | Maturity Level: 1 | Informative | Use Context: Any

This is a code system defined by the FHIR project.

Summary

Defining URL: | http://hl7.org/fhir/metric-calibration-state
Name: | DeviceMetricCalibrationState
Definition: | Describes the state of a metric calibration.
Committee: | Health Care Devices Work Group
OID: | 2.16.840.1.113883.4.642.1.637 (for OID based terminology systems)
Source Resource | XML / JSON

This Code system is used in the following value sets:

* DeviceMetricCalibrationState (Describes the state of a metric calibration.)

4.2.12.637.1 Content

4.2.12.637.2 DeviceMetricCalibrationState

Describes the state of a metric calibration.

This code system http://hl7.org/fhir/metric-calibration-state defines the following codes:

Code | Display | Definition
not-calibrated | Not Calibrated | The metric has not been calibrated.
calibration-required | Calibration Required | The metric needs to be calibrated.
calibrated | Calibrated | The metric has been calibrated.
unspecified | Unspecified | The state of calibration of this metric is unspecified.

See the full registry of value sets defined as part of FHIR.

Explanation of the columns that may appear on this page:

Level | A few code lists that FHIR defines are hierarchical - each code is assigned a level. In this scheme, some codes are under other codes, and imply that the code they are under also applies
Source | The source of the definition of the code (when the value set draws in codes defined elsewhere)
Code | The code (used as the code in the resource instance). If the code is in italics, this indicates that the code is not selectable ('Abstract')
Display | The display (used in the display element of a Coding). If there is no display, implementers should not simply display the code, but map the concept into their application
Definition | An explanation of the meaning of the concept
Comments | Additional notes about how to use the code

4.2.12.639 Code System http://hl7.org/fhir/metric-color

URL: https://hl7.org/fhir/STU3/codesystem-metric-color.html

This page is part of the FHIR Specification (v3.0.2: STU 3). The current version which supercedes this version is 4.0.1. For a full list of available versions, see the Directory of published versions

Vocabulary Work Group | Maturity Level: 1 | Informative | Use Context: Any

This is a code system defined by the FHIR project.

Summary

Defining URL: | http://hl7.org/fhir/metric-color
Name: | DeviceMetricColor
Definition: | Describes the typical color of representation.
Committee: | Health Care Devices Work Group
OID: | 2.16.840.1.113883.4.642.1.639 (for OID based terminology systems)
Source Resource | XML / JSON

This Code system is used in the following value sets:

* DeviceMetricColor (Describes the typical color of representation.)

4.2.12.639.1 Content

4.2.12.639.2 DeviceMetricColor

Describes the typical color of representation.

This code system http://hl7.org/fhir/metric-color defines the following codes:

Code | Display | Definition
black | Color Black | Color for representation - black.
red | Color Red | Color for representation - red.
green | Color Green | Color for representation - green.
yellow | Color Yellow | Color for representation - yellow.
blue | Color Blue | Color for representation - blue.
magenta | Color Magenta | Color for representation - magenta.
cyan | Color Cyan | Color for representation - cyan.
white | Color White | Color for representation - white.

See the full registry of value sets defined as part of FHIR.

Explanation of the columns that may appear on this page:

Level | A few code lists that FHIR defines are hierarchical - each code is assigned a level. In this scheme, some codes are under other codes, and imply that the code they are under also applies
Source | The source of the definition of the code (when the value set draws in codes defined elsewhere)
Code | The code (used as the code in the resource instance). If the code is in italics, this indicates that the code is not selectable ('Abstract')
Display | The display (used in the display element of a Coding). If there is no display, implementers should not simply display the code, but map the concept into their application
Definition | An explanation of the meaning of the concept
Comments | Additional notes about how to use the code

4.2.12.641 Code System http://hl7.org/fhir/identity-assuranceLevel

URL: https://hl7.org/fhir/STU3/codesystem-identity-assuranceLevel.html

This page is part of the FHIR Specification (v3.0.2: STU 3). The current version which supercedes this version is 4.0.1. For a full list of available versions, see the Directory of published versions

Vocabulary Work Group | Maturity Level: 2 | Informative | Use Context: Any

This is a code system defined by the FHIR project.

Summary

Defining URL: | http://hl7.org/fhir/identity-assuranceLevel
Name: | IdentityAssuranceLevel
Definition: | The level of confidence that this link represents the same actual person, based on NIST Authentication Levels.
Committee: | Patient Administration Work Group
OID: | 2.16.840.1.113883.4.642.1.641 (for OID based terminology systems)
Source Resource | XML / JSON

This Code system is used in the following value sets:

* IdentityAssuranceLevel (The level of confidence that this link represents the same actual person, based on NIST Authentication Levels.)

4.2.12.641.1 Content

4.2.12.641.2 IdentityAssuranceLevel

The level of confidence that this link represents the same actual person, based on NIST Authentication Levels.

This code system http://hl7.org/fhir/identity-assuranceLevel defines the following codes:

Code | Display | Definition
level1 | Level 1 | Little or no confidence in the asserted identity's accuracy.
level2 | Level 2 | Some confidence in the asserted identity's accuracy.
level3 | Level 3 | High confidence in the asserted identity's accuracy.
level4 | Level 4 | Very high confidence in the asserted identity's accuracy.

See the full registry of value sets defined as part of FHIR.

Explanation of the columns that may appear on this page:

Level | A few code lists that FHIR defines are hierarchical - each code is assigned a level. In this scheme, some codes are under other codes, and imply that the code they are under also applies
Source | The source of the definition of the code (when the value set draws in codes defined elsewhere)
Code | The code (used as the code in the resource instance). If the code is in italics, this indicates that the code is not selectable ('Abstract')
Display | The display (used in the display element of a Coding). If there is no display, implementers should not simply display the code, but map the concept into their application
Definition | An explanation of the meaning of the concept
Comments | Additional notes about how to use the code

4.2.12.643 Code System http://hl7.org/fhir/ex-visionprescriptionproduct

URL: https://hl7.org/fhir/STU3/codesystem-vision-product.html

This page is part of the FHIR Specification (v3.0.2: STU 3). The current version which supercedes this version is 4.0.1. For a full list of available versions, see the Directory of published versions

Vocabulary Work Group | Maturity Level: 1 | Informative | Use Context: Not Intended for Production use

This is a code system defined by the FHIR project.

Summary

Defining URL: | http://hl7.org/fhir/ex-visionprescriptionproduct
Name: | Example Vision Prescription Product Codes
Definition: | This value set includes a smattering of Prescription Product codes.
Committee: | Financial Management Work Group
OID: | 2.16.840.1.113883.4.642.1.643 (for OID based terminology systems)
Copyright: | This is an example set.
Source Resource | XML / JSON

This Code system is used in the following value sets:

* Example Vision Prescription Product Codes (This value set includes a smattering of Prescription Product codes.)

4.2.12.643.1 Content

4.2.12.643.2 Example Vision Prescription Product Codes

This value set includes a smattering of Prescription Product codes.

Copyright Statement: This is an example set.

This code system http://hl7.org/fhir/ex-visionprescriptionproduct defines the following codes:

Code | Display | Definition
lens | Lens | A lens to be fitted to a frame to comprise a pair of glasses.
contact | Contact Lens | A lens to be fitted for wearing directly on an eye.

See the full registry of value sets defined as part of FHIR.

Explanation of the columns that may appear on this page:

Level | A few code lists that FHIR defines are hierarchical - each code is assigned a level. In this scheme, some codes are under other codes, and imply that the code they are under also applies
Source | The source of the definition of the code (when the value set draws in codes defined elsewhere)
Code | The code (used as the code in the resource instance). If the code is in italics, this indicates that the code is not selectable ('Abstract')
Display | The display (used in the display element of a Coding). If there is no display, implementers should not simply display the code, but map the concept into their application
Definition | An explanation of the meaning of the concept
Comments | Additional notes about how to use the code

4.2.12.645 Code System http://hl7.org/fhir/vision-eye-codes

URL: https://hl7.org/fhir/STU3/codesystem-vision-eye-codes.html

This page is part of the FHIR Specification (v3.0.2: STU 3). The current version which supercedes this version is 4.0.1. For a full list of available versions, see the Directory of published versions

Vocabulary Work Group | Maturity Level: 1 | Informative | Use Context: Any

This is a code system defined by the FHIR project.

Summary

Defining URL: | http://hl7.org/fhir/vision-eye-codes
Name: | VisionEyes
Definition: | A coded concept listing the eye codes.
Committee: | Financial Management Work Group
OID: | 2.16.840.1.113883.4.642.1.645 (for OID based terminology systems)
Source Resource | XML / JSON

This Code system is used in the following value sets:

* VisionEyes (A coded concept listing the eye codes.)

4.2.12.645.1 Content

4.2.12.645.2 VisionEyes

A coded concept listing the eye codes.

This code system http://hl7.org/fhir/vision-eye-codes defines the following codes:

Code | Display | Definition
right | Right Eye | Right Eye
left | Left Eye | Left Eye

See the full registry of value sets defined as part of FHIR.

Explanation of the columns that may appear on this page:

Level | A few code lists that FHIR defines are hierarchical - each code is assigned a level. In this scheme, some codes are under other codes, and imply that the code they are under also applies
Source | The source of the definition of the code (when the value set draws in codes defined elsewhere)
Code | The code (used as the code in the resource instance). If the code is in italics, this indicates that the code is not selectable ('Abstract')
Display | The display (used in the display element of a Coding). If there is no display, implementers should not simply display the code, but map the concept into their application
Definition | An explanation of the meaning of the concept
Comments | Additional notes about how to use the code

4.2.12.647 Code System http://hl7.org/fhir/vision-base-codes

URL: https://hl7.org/fhir/STU3/codesystem-vision-base-codes.html

This page is part of the FHIR Specification (v3.0.2: STU 3). The current version which supercedes this version is 4.0.1. For a full list of available versions, see the Directory of published versions

Vocabulary Work Group | Maturity Level: 1 | Informative | Use Context: Any

This is a code system defined by the FHIR project.

Summary

Defining URL: | http://hl7.org/fhir/vision-base-codes
Name: | VisionBase
Definition: | A coded concept listing the base codes.
Committee: | Financial Management Work Group
OID: | 2.16.840.1.113883.4.642.1.647 (for OID based terminology systems)
Source Resource | XML / JSON

This Code system is used in the following value sets:

* VisionBase (A coded concept listing the base codes.)

4.2.12.647.1 Content

4.2.12.647.2 VisionBase

A coded concept listing the base codes.

This code system http://hl7.org/fhir/vision-base-codes defines the following codes:

Code | Display | Definition
up | Up | top
down | Down | bottom
in | In | inner edge
out | Out | outer edge

See the full registry of value sets defined as part of FHIR.

Explanation of the columns that may appear on this page:

Level | A few code lists that FHIR defines are hierarchical - each code is assigned a level. In this scheme, some codes are under other codes, and imply that the code they are under also applies
Source | The source of the definition of the code (when the value set draws in codes defined elsewhere)
Code | The code (used as the code in the resource instance). If the code is in italics, this indicates that the code is not selectable ('Abstract')
Display | The display (used in the display element of a Coding). If there is no display, implementers should not simply display the code, but map the concept into their application
Definition | An explanation of the meaning of the concept
Comments | Additional notes about how to use the code

4.2.12.649 Code System http://hl7.org/fhir/episode-of-care-status

URL: https://hl7.org/fhir/STU3/codesystem-episode-of-care-status.html

This page is part of the FHIR Specification (v3.0.2: STU 3). The current version which supercedes this version is 4.0.1. For a full list of available versions, see the Directory of published versions

Vocabulary Work Group | Maturity Level: 2 | Informative | Use Context: Any

This is a code system defined by the FHIR project.

Summary

Defining URL: | http://hl7.org/fhir/episode-of-care-status
Name: | EpisodeOfCareStatus
Definition: | The status of the episode of care.
Committee: | Patient Administration Work Group
OID: | 2.16.840.1.113883.4.642.1.649 (for OID based terminology systems)
Source Resource | XML / JSON

This Code system is used in the following value sets:

* EpisodeOfCareStatus (The status of the episode of care.)

4.2.12.649.1 Content

4.2.12.649.2 EpisodeOfCareStatus

The status of the episode of care.

This code system http://hl7.org/fhir/episode-of-care-status defines the following codes:

Code | Display | Definition
planned | Planned | This episode of care is planned to start at the date specified in the period.start. During this status, an organization may perform assessments to determine if the patient is eligible to receive services, or be organizing to make resources available to provide care services.
waitlist | Waitlist | This episode has been placed on a waitlist, pending the episode being made active (or cancelled).
active | Active | This episode of care is current.
onhold | On Hold | This episode of care is on hold, the organization has limited responsibility for the patient (such as while on respite).
finished | Finished | This episode of care is finished and the organization is not expecting to be providing further care to the patient. Can also be known as "closed", "completed" or other similar terms.
cancelled | Cancelled | The episode of care was cancelled, or withdrawn from service, often selected during the planned stage as the patient may have gone elsewhere, or the circumstances have changed and the organization is unable to provide the care. It indicates that services terminated outside the planned/expected workflow.
entered-in-error | Entered in Error | This instance should not have been part of this patient's medical record.

See the full registry of value sets defined as part of FHIR.

Explanation of the columns that may appear on this page:

Level | A few code lists that FHIR defines are hierarchical - each code is assigned a level. In this scheme, some codes are under other codes, and imply that the code they are under also applies
Source | The source of the definition of the code (when the value set draws in codes defined elsewhere)
Code | The code (used as the code in the resource instance). If the code is in italics, this indicates that the code is not selectable ('Abstract')
Display | The display (used in the display element of a Coding). If there is no display, implementers should not simply display the code, but map the concept into their application
Definition | An explanation of the meaning of the concept
Comments | Additional notes about how to use the code

4.2.12.651 Code System http://hl7.org/fhir/episodeofcare-type

URL: https://hl7.org/fhir/STU3/codesystem-episodeofcare-type.html

This page is part of the FHIR Specification (v3.0.2: STU 3). The current version which supercedes this version is 4.0.1. For a full list of available versions, see the Directory of published versions

Vocabulary Work Group | Maturity Level: 1 | Informative | Use Context: Not Intended for Production use

This is a code system defined by the FHIR project.

Summary

Defining URL: | http://hl7.org/fhir/episodeofcare-type
Name: | EpisodeOfCareType
Definition: | This example value set defines a set of codes that can be used to express the usage type of an EpisodeOfCare record.
Committee: | Patient Administration Work Group
OID: | 2.16.840.1.113883.4.642.1.651 (for OID based terminology systems)
Source Resource | XML / JSON

This Code system is used in the following value sets:

* EpisodeOfCareType (This example value set defines a set of codes that can be used to express the usage type of an EpisodeOfCare record.)

4.2.12.651.1 Content

4.2.12.651.2 EpisodeOfCareType

This example value set defines a set of codes that can be used to express the usage type of an EpisodeOfCare record.

This code system http://hl7.org/fhir/episodeofcare-type defines the following codes:

Code | Display | Definition
hacc | Home and Community Care
pac | Post Acute Care

diab | Post co-ordinated diabetes program
da | Drug and alcohol rehabilitation
cacp | Community-based aged care

See the full registry of value sets defined as part of FHIR.

Explanation of the columns that may appear on this page:

Level | A few code lists that FHIR defines are hierarchical - each code is assigned a level. In this scheme, some codes are under other codes, and imply that the code they are under also applies
Source | The source of the definition of the code (when the value set draws in codes defined elsewhere)
Code | The code (used as the code in the resource instance). If the code is in italics, this indicates that the code is not selectable ('Abstract')
Display | The display (used in the display element of a Coding). If there is no display, implementers should not simply display the code, but map the concept into their application
Definition | An explanation of the meaning of the concept
Comments | Additional notes about how to use the code

4.2.12.655 Code System http://hl7.org/fhir/structure-definition-kind

URL: https://hl7.org/fhir/STU3/codesystem-structure-definition-kind.html

This page is part of the FHIR Specification (v3.0.2: STU 3). The current version which supercedes this version is 4.0.1. For a full list of available versions, see the Directory of published versions

Vocabulary Work Group | Maturity Level: 5 | Informative | Use Context: Any

This is a code system defined by the FHIR project.

Summary

Defining URL: | http://hl7.org/fhir/structure-definition-kind
Name: | StructureDefinitionKind
Definition: | Defines the type of structure that a definition is describing.
Committee: | FHIR Infrastructure Work Group
OID: | 2.16.840.1.113883.4.642.1.655 (for OID based terminology systems)
Source Resource | XML / JSON

This Code system is used in the following value sets:

* StructureDefinitionKind (Defines the type of structure that a definition is describing.)

4.2.12.655.1 Content

4.2.12.655.2 StructureDefinitionKind

Defines the type of structure that a definition is describing.

This code system http://hl7.org/fhir/structure-definition-kind defines the following codes:

Code | Display | Definition
primitive-type | Primitive Data Type | A primitive type that has a value and an extension. These can be used throughout Resource and extension definitions. Only the base specification can define primitive types.
complex-type | Complex Data Type | A complex structure that defines a set of data elements. These can be used throughout Resource and extension definitions, and in logical models.
resource | Resource | A resource defined by the FHIR specification.
logical | Logical Model | A conceptual package of data that will be mapped to resources for implementation.

See the full registry of value sets defined as part of FHIR.

Explanation of the columns that may appear on this page:

Level | A few code lists that FHIR defines are hierarchical - each code is assigned a level. In this scheme, some codes are under other codes, and imply that the code they are under also applies
Source | The source of the definition of the code (when the value set draws in codes defined elsewhere)
Code | The code (used as the code in the resource instance). If the code is in italics, this indicates that the code is not selectable ('Abstract')
Display | The display (used in the display element of a Coding). If there is no display, implementers should not simply display the code, but map the concept into their application
Definition | An explanation of the meaning of the concept
Comments | Additional notes about how to use the code

4.2.12.657 Code System http://hl7.org/fhir/extension-context

URL: https://hl7.org/fhir/STU3/codesystem-extension-context.html

This page is part of the FHIR Specification (v3.0.2: STU 3). The current version which supercedes this version is 4.0.1. For a full list of available versions, see the Directory of published versions

Vocabulary Work Group | Maturity Level: 5 | Informative | Use Context: Any

This is a code system defined by the FHIR project.

Summary

Defining URL: | http://hl7.org/fhir/extension-context
Name: | ExtensionContext
Definition: | How an extension context is interpreted.

Committee: | FHIR Infrastructure Work Group
OID: | 2.16.840.1.113883.4.642.1.657 (for OID based terminology systems)
Source Resource | XML / JSON

This Code system is used in the following value sets:

* ExtensionContext (How an extension context is interpreted.)

4.2.12.657.1 Content

4.2.12.657.2 ExtensionContext

How an extension context is interpreted.

This code system http://hl7.org/fhir/extension-context defines the following codes:

Code | Display | Definition
resource | Resource | The context is all elements matching a particular resource element path.
datatype | Datatype | The context is all nodes matching a particular data type element path (root or repeating element) or all elements referencing a particular primitive data type (expressed as the datatype name).
extension | Extension | The context is a particular extension from a particular profile, a uri that identifies the extension definition.

See the full registry of value sets defined as part of FHIR.

Explanation of the columns that may appear on this page:

Level | A few code lists that FHIR defines are hierarchical - each code is assigned a level. In this scheme, some codes are under other codes, and imply that the code they are under also applies
Source | The source of the definition of the code (when the value set draws in codes defined elsewhere)
Code | The code (used as the code in the resource instance). If the code is in italics, this indicates that the code is not selectable ('Abstract')
Display | The display (used in the display element of a Coding). If there is no display, implementers should not simply display the code, but map the concept into their application
Definition | An explanation of the meaning of the concept
Comments | Additional notes about how to use the code

4.2.12.660 Code System http://hl7.org/fhir/type-derivation-rule

URL: https://hl7.org/fhir/STU3/codesystem-type-derivation-rule.html

This page is part of the FHIR Specification (v3.0.2: STU 3). The current version which supercedes this version is 4.0.1. For a full list of available versions, see the Directory of published versions

Vocabulary Work Group | Maturity Level: 5 | Informative | Use Context: Any

This is a code system defined by the FHIR project.

Summary

Defining URL: | http://hl7.org/fhir/type-derivation-rule
Name: | TypeDerivationRule
Definition: | How a type relates to its baseDefinition.
Committee: | FHIR Infrastructure Work Group
OID: | 2.16.840.1.113883.4.642.1.660 (for OID based terminology systems)
Source Resource | XML / JSON

This Code system is used in the following value sets:

* TypeDerivationRule (How a type relates to its baseDefinition.)

4.2.12.660.1 Content

4.2.12.660.2 TypeDerivationRule

How a type relates to its baseDefinition.

This code system http://hl7.org/fhir/type-derivation-rule defines the following codes:

Code | Display | Definition
specialization | Specialization | This definition defines a new type that adds additional elements to the base type
constraint | Constraint | This definition adds additional rules to an existing concrete type

See the full registry of value sets defined as part of FHIR.

Explanation of the columns that may appear on this page:

Level | A few code lists that FHIR defines are hierarchical - each code is assigned a level. In this scheme, some codes are under other codes, and imply that the code they are under also applies
Source | The source of the definition of the code (when the value set draws in codes defined elsewhere)
Code | The code (used as the code in the resource instance). If the code is in italics, this indicates that the code is not selectable ('Abstract')
Display | The display (used in the display element of a Coding). If there is no display, implementers should not simply display the code, but map the concept into their application
Definition | An explanation of the meaning of the concept
Comments | Additional notes about how to use the code

4.2.12.662 Code System http://hl7.org/fhir/map-model-mode

URL: https://hl7.org/fhir/STU3/codesystem-map-model-mode.html

This page is part of the FHIR Specification (v3.0.2: STU 3). The current version which supercedes this version is 4.0.1. For a full list of available versions, see the Directory of published versions

Vocabulary Work Group | Maturity Level: 2 | Informative | Use Context: Any

This is a code system defined by the FHIR project.

Summary

Defining URL: | http://hl7.org/fhir/map-model-mode
Name: | StructureMapModelMode
Definition: | How the referenced structure is used in this mapping
Committee: | FHIR Infrastructure Work Group
OID: | 2.16.840.1.113883.4.642.1.662 (for OID based terminology systems)
Source Resource | XML / JSON

This Code system is used in the following value sets:

* StructureMapModelMode (How the referenced structure is used in this mapping)

4.2.12.662.1 Content

4.2.12.662.2 StructureMapModelMode

How the referenced structure is used in this mapping

This code system http://hl7.org/fhir/map-model-mode defines the following codes:

Code | Display | Definition
source | Source Structure Definition | This structure describes an instance passed to the mapping engine that is used a source of data
queried | Queried Structure Definition | This structure describes an instance that the mapping engine may ask for that is used a source of data
target | Target Structure Definition | This structure describes an instance passed to the mapping engine that is used a target of data
produced | Produced Structure Definition | This structure describes an instance that the mapping engine may ask to create that is used a target of data

See the full registry of value sets defined as part of FHIR.

Explanation of the columns that may appear on this page:

Level | A few code lists that FHIR defines are hierarchical - each code is assigned a level. In this scheme, some codes are under other codes, and imply that the code they are under also applies
Source | The source of the definition of the code (when the value set draws in codes defined elsewhere)
Code | The code (used as the code in the resource instance). If the code is in italics, this indicates that the code is not selectable ('Abstract')
Display | The display (used in the display element of a Coding). If there is no display, implementers should not simply display the code, but map the concept into their application
Definition | An explanation of the meaning of the concept
Comments | Additional notes about how to use the code

4.2.12.664 Code System http://hl7.org/fhir/map-input-mode

URL: https://hl7.org/fhir/STU3/codesystem-map-input-mode.html

This page is part of the FHIR Specification (v3.0.2: STU 3). The current version which supercedes this version is 4.0.1. For a full list of available versions, see the Directory of published versions

Vocabulary Work Group | Maturity Level: 2 | Informative | Use Context: Any

This is a code system defined by the FHIR project.

Summary

Defining URL: | http://hl7.org/fhir/map-input-mode
Name: | StructureMapInputMode
Definition: | Mode for this instance of data
Committee: | FHIR Infrastructure Work Group
OID: | 2.16.840.1.113883.4.642.1.664 (for OID based terminology systems)
Source Resource | XML / JSON

This Code system is used in the following value sets:

* StructureMapInputMode (Mode for this instance of data)

4.2.12.664.1 Content

4.2.12.664.2 StructureMapInputMode

Mode for this instance of data

This code system http://hl7.org/fhir/map-input-mode defines the following codes:

Code | Display | Definition
source | Source Instance | Names an input instance used a source for mapping
target | Target Instance | Names an instance that is being populated

See the full registry of value sets defined as part of FHIR.

Explanation of the columns that may appear on this page:

Level | A few code lists that FHIR defines are hierarchical - each code is assigned a level. In this scheme, some codes are under other codes, and imply that the code they are under also applies
Source | The source of the definition of the code (when the value set draws in codes defined elsewhere)
Code | The code (used as the code in the resource instance). If the code is in italics, this indicates that the code is not selectable ('Abstract')
Display | The display (used in the display element of a Coding). If there is no display, implementers should not simply display the code, but map the concept into their application
Definition | An explanation of the meaning of the concept
Comments | Additional notes about how to use the code

4.2.12.666 Code System http://hl7.org/fhir/map-context-type

URL: https://hl7.org/fhir/STU3/codesystem-map-context-type.html

This page is part of the FHIR Specification (v3.0.2: STU 3). The current version which supercedes this version is 4.0.1. For a full list of available versions, see the Directory of published versions

Vocabulary Work Group | Maturity Level: 2 | Informative | Use Context: Any

This is a code system defined by the FHIR project.

Summary

Defining URL: | http://hl7.org/fhir/map-context-type
Name: | StructureMapContextType
Definition: | How to interpret the context
Committee: | FHIR Infrastructure Work Group
OID: | 2.16.840.1.113883.4.642.1.666 (for OID based terminology systems)
Source Resource | XML / JSON

This Code system is used in the following value sets:

* StructureMapContextType (How to interpret the context)

4.2.12.666.1 Content

4.2.12.666.2 StructureMapContextType

How to interpret the context

This code system http://hl7.org/fhir/map-context-type defines the following codes:

Code | Display | Definition
type | Type | The context specifies a type
variable | Variable | The context specifies a variable

See the full registry of value sets defined as part of FHIR.

Explanation of the columns that may appear on this page:

Level | A few code lists that FHIR defines are hierarchical - each code is assigned a level. In this scheme, some codes are under other codes, and imply that the code they are under also applies
Source | The source of the definition of the code (when the value set draws in codes defined elsewhere)
Code | The code (used as the code in the resource instance). If the code is in italics, this indicates that the code is not selectable ('Abstract')
Display | The display (used in the display element of a Coding). If there is no display, implementers should not simply display the code, but map the concept into their application
Definition | An explanation of the meaning of the concept
Comments | Additional notes about how to use the code

4.2.12.668 Code System http://hl7.org/fhir/map-transform

URL: https://hl7.org/fhir/STU3/codesystem-map-transform.html

This page is part of the FHIR Specification (v3.0.2: STU 3). The current version which supercedes this version is 4.0.1. For a full list of available versions, see the Directory of published versions

Vocabulary Work Group | Maturity Level: 2 | Informative | Use Context: Any

This is a code system defined by the FHIR project.

Summary

Defining URL: | http://hl7.org/fhir/map-transform
Name: | StructureMapTransform
Definition: | How data is copied/created
Committee: | FHIR Infrastructure Work Group
OID: | 2.16.840.1.113883.4.642.1.668 (for OID based terminology systems)
Source Resource | XML / JSON

This Code system is used in the following value sets:

* StructureMapTransform (How data is copied/created)

4.2.12.668.1 Content

4.2.12.668.2 StructureMapTransform

How data is copied/created

This code system http://hl7.org/fhir/map-transform defines the following codes:

Code | Display | Definition
create | create | create(type : string) - type is passed through to the application on the standard API, and must be known by it
copy | copy | copy(source)
truncate | truncate | truncate(source, length) - source must be stringy type
escape | escape | escape(source, fmt1, fmt2) - change source from one kind of escaping to another (plain, java, xml, json). note that this is for when the string itself is escaped
cast | cast | cast(source, type?) - case source from one type to another. target type can be left as implicit if there is one and only one target type known
append | append | append(source...) - source is element or string
translate | translate | translate(source, uri_of_map) - use the translate operation
reference | reference | reference(source : object) - return a string that references the provided tree properly
dateOp | dateOp | Perform a date operation. *Parameters to be documented*
uuid | uuid | Generate a random UUID (in lowercase). No Parameters
pointer | pointer | Return the appropriate string to put in a reference that refers to the resource provided as a parameter
evaluate | evaluate | Execute the supplied fluentpath expression and use the value returned by that
cc | cc | Create a CodeableConcept. Parameters = (text) or (system. Code[, display])
c | c | Create a Coding. Parameters = (system. Code[, display])
qty | qty | Create a quantity. Parameters = (text) or (value, unit, [system, code]) where text is the natural representation e.g. [comparator]value[space]unit
id | id | Create an identifier. Parameters = (system, value[, type]) where type is a code from the identifier type value set
cp | cp | Create a contact details. Parameters = (value) or (system, value). If no system is provided, the system should be inferred from the content of the value

See the full registry of value sets defined as part of FHIR.

Explanation of the columns that may appear on this page:

Level | A few code lists that FHIR defines are hierarchical - each code is assigned a level. In this scheme, some codes are under other codes, and imply that the code they are under also applies
Source | The source of the definition of the code (when the value set draws in codes defined elsewhere)
Code | The code (used as the code in the resource instance). If the code is in italics, this indicates that the code is not selectable ('Abstract')
Display | The display (used in the display element of a Coding). If there is no display, implementers should not simply display the code, but map the concept into their application
Definition | An explanation of the meaning of the concept
Comments | Additional notes about how to use the code

4.2.12.670 Code System http://hl7.org/fhir/map-source-list-mode

URL: https://hl7.org/fhir/STU3/codesystem-map-source-list-mode.html

This page is part of the FHIR Specification (v3.0.2: STU 3). The current version which supercedes this version is 4.0.1. For a full list of available versions, see the Directory of published versions

Vocabulary Work Group | Maturity Level: 2 | Informative | Use Context: Any

This is a code system defined by the FHIR project.

Summary

Defining URL: | http://hl7.org/fhir/map-source-list-mode
Name: | StructureMapSourceListMode
Definition: | If field is a list, how to manage the source
Committee: | FHIR Infrastructure Work Group
OID: | 2.16.840.1.113883.4.642.1.670 (for OID based terminology systems)
Source Resource | XML / JSON

This Code system is used in the following value sets:

* StructureMapSourceListMode (If field is a list, how to manage the source)

4.2.12.670.1 Content

4.2.12.670.2 StructureMapSourceListMode

If field is a list, how to manage the source

This code system http://hl7.org/fhir/map-source-list-mode defines the following codes:

Code | Display | Definition
first | First | Only process this rule for the first in the list
not_first | All but the first | Process this rule for all but the first
last | Last | Only process this rule for the last in the list
not_last | All but the last | Process this rule for all but the last
only_one | Enforce only one | Only process this rule is there is only item

See the full registry of value sets defined as part of FHIR.

Explanation of the columns that may appear on this page:

Level | A few code lists that FHIR defines are hierarchical - each code is assigned a level. In this scheme, some codes are under other codes, and imply that the code they are under also applies
Source | The source of the definition of the code (when the value set draws in codes defined elsewhere)
Code | The code (used as the code in the resource instance). If the code is in italics, this indicates that the code is not selectable ('Abstract')
Display | The display (used in the display element of a Coding). If there is no display, implementers should not simply display the code, but map the concept into their application
Definition | An explanation of the meaning of the concept
Comments | Additional notes about how to use the code

4.2.12.672 Code System http://hl7.org/fhir/map-target-list-mode

URL: https://hl7.org/fhir/STU3/codesystem-map-target-list-mode.html

This page is part of the FHIR Specification (v3.0.2: STU 3). The current version which supercedes this version is 4.0.1. For a full list of available versions, see the Directory of published versions

Vocabulary Work Group | Maturity Level: 2 | Informative | Use Context: Any

This is a code system defined by the FHIR project.

Summary

Defining URL: | http://hl7.org/fhir/map-target-list-mode
Name: | StructureMapTargetListMode
Definition: | If field is a list, how to manage the production
Committee: | FHIR Infrastructure Work Group
OID: | 2.16.840.1.113883.4.642.1.672 (for OID based terminology systems)
Source Resource | XML / JSON

This Code system is used in the following value sets:

* StructureMapTargetListMode (If field is a list, how to manage the production)

4.2.12.672.1 Content

4.2.12.672.2 StructureMapTargetListMode

If field is a list, how to manage the production

This code system http://hl7.org/fhir/map-target-list-mode defines the following codes:

Code | Display | Definition
first | First | when the target list is being assembled, the items for this rule go first. If more that one rule defines a first item (for a given instance of mapping) then this is an error
share | Share | the target instance is shared with the target instances generated by another rule (up to the first common n items, then create new ones)
last | Last | when the target list is being assembled, the items for this rule go last. If more that one rule defines a last item (for a given instance of mapping) then this is an error
collate | Collate | re-use the first item in the list, and keep adding content to it

See the full registry of value sets defined as part of FHIR.

Explanation of the columns that may appear on this page:

Level | A few code lists that FHIR defines are hierarchical - each code is assigned a level. In this scheme, some codes are under other codes, and imply that the code they are under also applies
Source | The source of the definition of the code (when the value set draws in codes defined elsewhere)
Code | The code (used as the code in the resource instance). If the code is in italics, this indicates that the code is not selectable ('Abstract')
Display | The display (used in the display element of a Coding). If there is no display, implementers should not simply display the code, but map the concept into their application
Definition | An explanation of the meaning of the concept
Comments | Additional notes about how to use the code

4.2.12.674 Code System http://hl7.org/fhir/map-group-type-mode

URL: https://hl7.org/fhir/STU3/codesystem-map-group-type-mode.html

This page is part of the FHIR Specification (v3.0.2: STU 3). The current version which supercedes this version is 4.0.1. For a full list of available versions, see the Directory of published versions

Vocabulary Work Group | Maturity Level: 2 | Informative | Use Context: Any

This is a code system defined by the FHIR project.

Summary

Defining URL: | http://hl7.org/fhir/map-group-type-mode
Name: | StructureMapGroupTypeMode
Definition: | If this is the default rule set to apply for the source type, or this combination of types
Committee: | FHIR Infrastructure Work Group
OID: | 2.16.840.1.113883.4.642.1.674 (for OID based terminology systems)

Source Resource | XML / JSON

This Code system is used in the following value sets:

* StructureMapGroupTypeMode (If this is the default rule set to apply for the source type, or this combination of types)

4.2.12.674.1 Content

4.2.12.674.2 StructureMapGroupTypeMode

If this is the default rule set to apply for the source type, or this combination of types

This code system http://hl7.org/fhir/map-group-type-mode defines the following codes:

Code | Display | Definition
none | Not a Default | This group is not a default group for the types
types | Default for Type Combination | This group is a default mapping group for the specified types and for the primary source type
type-and-types | Default for type + combination | This group is a default mapping group for the specified types

See the full registry of value sets defined as part of FHIR.

Explanation of the columns that may appear on this page:

Level | A few code lists that FHIR defines are hierarchical - each code is assigned a level. In this scheme, some codes are under other codes, and imply that the code they are under also applies
Source | The source of the definition of the code (when the value set draws in codes defined elsewhere)
Code | The code (used as the code in the resource instance). If the code is in italics, this indicates that the code is not selectable ('Abstract')
Display | The display (used in the display element of a Coding). If there is no display, implementers should not simply display the code, but map the concept into their application
Definition | An explanation of the meaning of the concept
Comments | Additional notes about how to use the code

4.2.12.676 Code System http://hl7.org/fhir/actionlist

URL: https://hl7.org/fhir/STU3/codesystem-actionlist.html

This page is part of the FHIR Specification (v3.0.2: STU 3). The current version which supercedes this version is 4.0.1. For a full list of available versions, see the Directory of published versions

Vocabulary Work Group | Maturity Level: 2 | Informative | Use Context: Any

This is a code system defined by the FHIR project.

Summary

Defining URL: | http://hl7.org/fhir/actionlist
Name: | ActionList
Definition: | List of allowable action which this resource can request.
Committee: | Financial Management Work Group
OID: | 2.16.840.1.113883.4.642.1.676 (for OID based terminology systems)
Source Resource | XML / JSON

This Code system is used in the following value sets:

* ActionList (List of allowable action which this resource can request.)

4.2.12.676.1 Content

4.2.12.676.2 ActionList

List of allowable action which this resource can request.

This code system http://hl7.org/fhir/actionlist defines the following codes:

Code | Display | Definition
cancel | Cancel, Reverse or Nullify | Cancel, reverse or nullify the target resource.
poll | Poll | Check for previously un-read/ not-retrieved resources.
reprocess | Re-Process | Re-process the target resource.
status | Status Check | Retrieve the processing status of the target resource.

See the full registry of value sets defined as part of FHIR.

Explanation of the columns that may appear on this page:

Level | A few code lists that FHIR defines are hierarchical - each code is assigned a level. In this scheme, some codes are under other codes, and imply that the code they are under also applies
Source | The source of the definition of the code (when the value set draws in codes defined elsewhere)
Code | The code (used as the code in the resource instance). If the code is in italics, this indicates that the code is not selectable ('Abstract')
Display | The display (used in the display element of a Coding). If there is no display, implementers should not simply display the code, but map the concept into their application
Definition | An explanation of the meaning of the concept
Comments | Additional notes about how to use the code

4.2.12.678 Code System http://hl7.org/fhir/processoutcomecodes

URL: https://hl7.org/fhir/STU3/codesystem-process-outcome.html

This page is part of the FHIR Specification (v3.0.2: STU 3). The current version which supercedes this version is 4.0.1. For a full list of available versions, see the Directory of published versions

Vocabulary Work Group | Maturity Level: 1 | Informative | Use Context: Not Intended for Production use

This is a code system defined by the FHIR project.

Summary

Defining URL: | http://hl7.org/fhir/processoutcomecodes
Name: | Process Outcome Codes
Definition: | This value set includes sample Process Outcome codes.
Committee: | Financial Management Work Group
OID: | 2.16.840.1.113883.4.642.1.678 (for OID based terminology systems)
Copyright: | This is an example set.
Source Resource | XML / JSON

This Code system is used in the following value sets:

* Process Outcome Codes (This value set includes sample Process Outcome codes.)

4.2.12.678.1 Content

4.2.12.678.2 Process Outcome Codes

This value set includes sample Process Outcome codes.

Copyright Statement: This is an example set.

This code system http://hl7.org/fhir/processoutcomecodes defines the following codes:

Code	Display	Definition
complete	Complete	The requested processing has completed.
pended	Pended	The requested processing has been suspended.
error	Error	The requested processing has terminated with some errors being found.

See the full registry of value sets defined as part of FHIR.

Explanation of the columns that may appear on this page:

Level | A few code lists that FHIR defines are hierarchical - each code is assigned a level. In this scheme, some codes are under other codes, and imply that the code they are under also applies
Source | The source of the definition of the code (when the value set draws in codes defined elsewhere)
Code | The code (used as the code in the resource instance). If the code is in italics, this indicates that the code is not selectable ('Abstract')
Display | The display (used in the display element of a Coding). If there is no display, implementers should not simply display the code, but map the concept into their application
Definition | An explanation of the meaning of the concept
Comments | Additional notes about how to use the code

4.2.12.680 Code System http://hl7.org/fhir/supply-kind

URL: https://hl7.org/fhir/STU3/codesystem-supplyrequest-kind.html

This page is part of the FHIR Specification (v3.0.2: STU 3). The current version which supercedes this version is 4.0.1. For a full list of available versions, see the Directory of published versions

Vocabulary Work Group | Maturity Level: 1 | Informative | Use Context: Not Intended for Production use

This is a code system defined by the FHIR project.

Summary

Defining URL: | http://hl7.org/fhir/supply-kind
Name: | Supply Type
Definition: | This value sets refers to a Category of supply.
Committee: | Orders and Observations Work Group
OID: | 2.16.840.1.113883.4.642.1.680 (for OID based terminology systems)
Source Resource | XML / JSON

This Code system is used in the following value sets:

* Supply Type (This value sets refers to a Category of supply.)

4.2.12.680.1 Content

4.2.12.680.2 Supply Type

This value sets refers to a Category of supply.

This code system http://hl7.org/fhir/supply-kind defines the following codes:

Code	Display	Definition
central	Central Supply	Supply is stored and requested from central supply.
nonstock	Non-Stock	Supply is not onsite and must be requested from an outside vendor using a non-stock requisition.

See the full registry of value sets defined as part of FHIR.

Explanation of the columns that may appear on this page:

Level | A few code lists that FHIR defines are hierarchical - each code is assigned a level. In this scheme, some codes are under other codes, and imply that the code they are under also applies
Source | The source of the definition of the code (when the value set draws in codes defined elsewhere)
Code | The code (used as the code in the resource instance). If the code is in italics, this indicates that the code is not selectable ('Abstract')
Display | The display (used in the display element of a Coding). If there is no display, implementers should not simply display the code, but map the concept into their application
Definition | An explanation of the meaning of the concept
Comments | Additional notes about how to use the code

4.2.12.682 Code System http://hl7.org/fhir/supplyrequest-status

URL: https://hl7.org/fhir/STU3/codesystem-supplyrequest-status.html

This page is part of the FHIR Specification (v3.0.2: STU 3). The current version which supercedes this version is 4.0.1. For a full list of available versions, see the Directory of published versions

Vocabulary Work Group | Maturity Level: 1 | Informative | Use Context: Any

This is a code system defined by the FHIR project.

Summary

Defining URL: | http://hl7.org/fhir/supplyrequest-status
Name: | SupplyRequestStatus
Definition: | Status of the supply request
Committee: | Orders and Observations Work Group
OID: | 2.16.840.1.113883.4.642.1.682 (for OID based terminology systems)
Source Resource | XML / JSON

This Code system is used in the following value sets:

* SupplyRequestStatus (Status of the supply request)

4.2.12.682.1 Content

4.2.12.682.2 SupplyRequestStatus

Status of the supply request

This code system http://hl7.org/fhir/supplyrequest-status defines the following codes:

Code | Display | Definition
draft | Draft | The request has been created but is not yet complete or ready for action
active | Active | The request is ready to be acted upon
suspended | Suspended | The authorization/request to act has been temporarily withdrawn but is expected to resume in the future
cancelled | Cancelled | The authorization/request to act has been terminated prior to the full completion of the intended actions. No further activity should occur.
completed | Completed | Activity against the request has been sufficiently completed to the satisfaction of the requester
entered-in-error | Entered in Error | This electronic record should never have existed, though it is possible that real-world decisions were based on it. (If real-world activity has occurred, the status should be "cancelled" rather than "entered-in-error".)
unknown | Unknown | The authoring system does not know which of the status values currently applies for this request. Note: This concept is not to be used for "other" - one of the listed statuses is presumed to apply, it's just not known which one.

See the full registry of value sets defined as part of FHIR.

Explanation of the columns that may appear on this page:

Level | A few code lists that FHIR defines are hierarchical - each code is assigned a level. In this scheme, some codes are under other codes, and imply that the code they are under also applies
Source | The source of the definition of the code (when the value set draws in codes defined elsewhere)
Code | The code (used as the code in the resource instance). If the code is in italics, this indicates that the code is not selectable ('Abstract')
Display | The display (used in the display element of a Coding). If there is no display, implementers should not simply display the code, but map the concept into their application
Definition | An explanation of the meaning of the concept
Comments | Additional notes about how to use the code

4.2.12.684 Code System http://hl7.org/fhir/supplyrequest-reason

URL: https://hl7.org/fhir/STU3/codesystem-supplyrequest-reason.html

This page is part of the FHIR Specification (v3.0.2: STU 3). The current version which supercedes this version is 4.0.1. For a full list of available versions, see the Directory of published versions

Vocabulary Work Group | Maturity Level: 1 | Informative | Use Context: Any

This is a code system defined by the FHIR project.

Summary

Defining URL: | http://hl7.org/fhir/supplyrequest-reason
Name: | SupplyRequestReason
Definition: | Why the supply item was requested

Committee: | Orders and Observations Work Group
OID: | 2.16.840.1.113883.4.642.1.684 (for OID based terminology systems)
Source Resource | XML / JSON

This Code system is used in the following value sets:

* SupplyRequestReason (Why the supply item was requested)

4.2.12.684.1 Content

4.2.12.684.2 SupplyRequestReason

Why the supply item was requested

This code system http://hl7.org/fhir/supplyrequest-reason defines the following codes:

Code | Display | Definition
patient-care | Patient Care | The supply has been requested for use in direct patient care.
ward-stock | Ward Stock | The supply has been requested for for creating or replenishing ward stock.

See the full registry of value sets defined as part of FHIR.

Explanation of the columns that may appear on this page:

Level | A few code lists that FHIR defines are hierarchical - each code is assigned a level. In this scheme, some codes are under other codes, and imply that the code they are under also applies
Source | The source of the definition of the code (when the value set draws in codes defined elsewhere)
Code | The code (used as the code in the resource instance). If the code is in italics, this indicates that the code is not selectable ('Abstract')
Display | The display (used in the display element of a Coding). If there is no display, implementers should not simply display the code, but map the concept into their application
Definition | An explanation of the meaning of the concept
Comments | Additional notes about how to use the code

4.2.12.687 Code System http://hl7.org/fhir/supplydelivery-status

URL: https://hl7.org/fhir/STU3/codesystem-supplydelivery-status.html

This page is part of the FHIR Specification (v3.0.2: STU 3). The current version which supercedes this version is 4.0.1. For a full list of available versions, see the Directory of published versions

Vocabulary Work Group | Maturity Level: 1 | Informative | Use Context: Any

This is a code system defined by the FHIR project.

Summary

Defining URL: | http://hl7.org/fhir/supplydelivery-status
Name: | SupplyDeliveryStatus
Definition: | Status of the supply delivery.
Committee: | Orders and Observations Work Group
OID: | 2.16.840.1.113883.4.642.1.687 (for OID based terminology systems)
Source Resource | XML / JSON

This Code system is used in the following value sets:

* SupplyDeliveryStatus (Status of the supply delivery.)

4.2.12.687.1 Content

4.2.12.687.2 SupplyDeliveryStatus

Status of the supply delivery.

This code system http://hl7.org/fhir/supplydelivery-status defines the following codes:

Code | Display | Definition
in-progress | In Progress | Supply has been requested, but not delivered.
completed | Delivered | Supply has been delivered ("completed").
abandoned | Abandoned | Delivery was not completed.
entered-in-error | Entered In Error | This electronic record should never have existed, though it is possible that real-world decisions were based on it. (If real-world activity has occurred, the status should be "cancelled" rather than "entered-in-error".)

See the full registry of value sets defined as part of FHIR.

Explanation of the columns that may appear on this page:

Level | A few code lists that FHIR defines are hierarchical - each code is assigned a level. In this scheme, some codes are under other codes, and imply that the code they are under also applies
Source | The source of the definition of the code (when the value set draws in codes defined elsewhere)
Code | The code (used as the code in the resource instance). If the code is in italics, this indicates that the code is not selectable ('Abstract')
Display | The display (used in the display element of a Coding). If there is no display, implementers should not simply display the code, but map the concept into their application
Definition | An explanation of the meaning of the concept
Comments | Additional notes about how to use the code

4.2.12.689 Code System http://hl7.org/fhir/supply-item-type

URL: https://hl7.org/fhir/STU3/codesystem-supplydelivery-type.html

This page is part of the FHIR Specification (v3.0.2: STU 3). The current version which supercedes this version is 4.0.1. For a full list of available versions, see the Directory of published versions

Vocabulary Work Group | Maturity Level: 1 | Informative | Use Context: Not Intended for Production use

This is a code system defined by the FHIR project.

Summary

Defining URL: | http://hl7.org/fhir/supply-item-type
Name: | Supply Item Type
Definition: | This value sets refers to a specific supply item.
Committee: | Orders and Observations Work Group
OID: | 2.16.840.1.113883.4.642.1.689 (for OID based terminology systems)
Source Resource | XML / JSON

This Code system is used in the following value sets:

* Supply Item Type (This value sets refers to a specific supply item.)

4.2.12.689.1 Content

4.2.12.689.2 Supply Item Type

This value sets refers to a specific supply item.

This code system http://hl7.org/fhir/supply-item-type defines the following codes:

Code | Display | Definition
medication | Medication | Supply is a kind of medication.
device | Device | What is supplied (or requested) is a device.

See the full registry of value sets defined as part of FHIR.

Explanation of the columns that may appear on this page:

Level | A few code lists that FHIR defines are hierarchical - each code is assigned a level. In this scheme, some codes are under other codes, and imply that the code they are under also applies
Source | The source of the definition of the code (when the value set draws in codes defined elsewhere)
Code | The code (used as the code in the resource instance). If the code is in italics, this indicates that the code is not selectable ('Abstract')
Display | The display (used in the display element of a Coding). If there is no display, implementers should not simply display the code, but map the concept into their application
Definition | An explanation of the meaning of the concept
Comments | Additional notes about how to use the code

4.2.12.691 Code System http://hl7.org/fhir/testscript-operation-codes

URL: https://hl7.org/fhir/STU3/codesystem-testscript-operation-codes.html

This page is part of the FHIR Specification (v3.0.2: STU 3). The current version which supercedes this version is 4.0.1. For a full list of available versions, see the Directory of published versions

Vocabulary Work Group | Maturity Level: 2 | Informative | Use Context: Not Intended for Production use

This is a code system defined by the FHIR project.

Summary

Defining URL: | http://hl7.org/fhir/testscript-operation-codes
Name: | TestScriptOperationCode
Definition: | This value set defines a set of codes that are used to indicate the supported operations of a testing engine or tool.
Committee: | FHIR Infrastructure Work Group
OID: | 2.16.840.1.113883.4.642.1.691 (for OID based terminology systems)
Source Resource | XML / JSON

This Code system is used in the following value sets:

* TestScriptOperationCode (This value set defines a set of codes that are used to indicate the supported operations of a testing engine or tool.)

4.2.12.691.1 Content

4.2.12.691.2 TestScriptOperationCode

This value set defines a set of codes that are used to indicate the supported operations of a testing engine or tool.

This code system http://hl7.org/fhir/testscript-operation-codes defines the following codes:

Code | Display | Definition
read | Read | Read the current state of the resource.
vread | Version Read | Read the state of a specific version of the resource.
update | Update | Update an existing resource by its id.

updateCreate | Create using Update | Update an existing resource by its id (or create it if it is new).
delete | Delete | Delete a resource.
deleteCondSingle | Conditional Delete Single | Conditionally delete a single resource based on search parameters.
deleteCondMultiple | Conditional Delete Multiple | Conditionally delete one or more resources based on search parameters.
history | History | Retrieve the change history for a particular resource or resource type.
create | Create | Create a new resource with a server assigned id.
search | Search | Search based on some filter criteria.
batch | Batch | Update, create or delete a set of resources as independent actions.
transaction | Transaction | Update, create or delete a set of resources as a single transaction.
capabilities | Capabilities | Get a capability statement for the system.
apply | $apply | Realize a definition in a specific context
cancel | $cancel | Cancel Task
closure | $closure | Closure Table Maintenance
compose | $compose | Code Composition based on supplied properties
conforms | $conforms | Test if a server implements a client's required operations
data-requirements | $data-requirements | Aggregates and return the parameters and data requirements as a single module definition library
document | $document | Generate a Document
evaluate | $evaluate | Evaluate DecisionSupportRule / DecisionSupportServiceModule
evaluate-measure | $evaluate-measure | Evaluate Measure
everything | $everything | Fetch Encounter/Patient Record
expand | $expand | Value Set Expansion
fail | $fail | Fail Task
find | $find | Find a functional list
finish | $finish | Finish Task
implements | $implements | Test if a server implements a client's required operations
lookup | $lookup | Concept Look Up
match | $match | Find patient matches using MPI based logic
meta | $meta | Access a list of profiles, tags, and security labels
meta-add | $meta-add | Add profiles, tags, and security labels to a resource
meta-delete | $meta-delete | Delete profiles, tags, and security labels for a resource
populate | $populate | Populate Questionnaire
populatehtml | $populatehtml | Generate HTML for Questionnaire
populatelink | $populatelink | Generate a link to a Questionnaire completion webpage
process-message | $process-message | Process Message
questionnaire | $questionnaire | Build Questionnaire
release | $release | Release Task
reserve | $reserve | Reserve Task
resume | $resume | Resume Task
set-input | $set-input | Set Task Input
set-output | $set-output | Set Task Output
start | $start | Start Task
stats | $stats | Observation Statistics
stop | $stop | Stop Task
subset | $subset | Fetch a subset of the CapabilityStatement resource
subsumes | $subsumes | Determine if code A is subsumed by code B
suspend | $suspend | Suspend Task
transform | $transform | Model Instance Transformation
translate | $translate | Concept Translation
validate | $validate | Validate a resource
validate-code | $validate-code | Value Set based Validation

See the full registry of value sets defined as part of FHIR.

Explanation of the columns that may appear on this page:

Level | A few code lists that FHIR defines are hierarchical - each code is assigned a level. In this scheme, some codes are under other codes, and imply that the code they are under also applies
Source | The source of the definition of the code (when the value set draws in codes defined elsewhere)
Code | The code (used as the code in the resource instance). If the code is in italics, this indicates that the code is not selectable ('Abstract')
Display | The display (used in the display element of a Coding). If there is no display, implementers should not simply display the code, but map the concept into their application
Definition | An explanation of the meaning of the concept
Comments | Additional notes about how to use the code

4.2.12.693 Code System http://hl7.org/fhir/content-type

URL: https://hl7.org/fhir/STU3/codesystem-content-type.html

This page is part of the FHIR Specification (v3.0.2: STU 3). The current version which supercedes this version is 4.0.1. For a full list of available versions, see the Directory of published versions

Vocabulary Work Group | Maturity Level: 2 | Informative | Use Context: Any

This is a code system defined by the FHIR project.

Summary

Defining URL: | http://hl7.org/fhir/content-type
Name: | ContentType
Definition: | The content or mime type.
Committee: | FHIR Infrastructure Work Group
OID: | 2.16.840.1.113883.4.642.1.693 (for OID based terminology systems)
Source Resource | XML / JSON

This Code system is used in the following value sets:

* ContentType (The content or mime type.)

4.2.12.693.1 Content

4.2.12.693.2 ContentType

The content or mime type.

This code system http://hl7.org/fhir/content-type defines the following codes:

Code | Display | Definition
xml | xml | XML content-type corresponding to the application/fhir+xml mime-type.
json | json | JSON content-type corresponding to the application/fhir+json mime-type.
ttl | ttl | RDF content-type corresponding to the text/turtle mime-type.
none | none | Prevent the use of the corresponding http header.

See the full registry of value sets defined as part of FHIR.

Explanation of the columns that may appear on this page:

Level | A few code lists that FHIR defines are hierarchical - each code is assigned a level. In this scheme, some codes are under other codes, and imply that the code they are under also applies
Source | The source of the definition of the code (when the value set draws in codes defined elsewhere)
Code | The code (used as the code in the resource instance). If the code is in italics, this indicates that the code is not selectable ('Abstract')
Display | The display (used in the display element of a Coding). If there is no display, implementers should not simply display the code, but map the concept into their application
Definition | An explanation of the meaning of the concept
Comments | Additional notes about how to use the code

4.2.12.695 Code System http://hl7.org/fhir/assert-direction-codes

URL: https://hl7.org/fhir/STU3/codesystem-assert-direction-codes.html

This page is part of the FHIR Specification (v3.0.2: STU 3). The current version which supercedes this version is 4.0.1. For a full list of available versions, see the Directory of published versions

Vocabulary Work Group | Maturity Level: 2 | Informative | Use Context: Any

This is a code system defined by the FHIR project.

Summary

Defining URL: | http://hl7.org/fhir/assert-direction-codes
Name: | AssertionDirectionType
Definition: | The type of direction to use for assertion.
Committee: | FHIR Infrastructure Work Group
OID: | 2.16.840.1.113883.4.642.1.695 (for OID based terminology systems)
Source Resource | XML / JSON

This Code system is used in the following value sets:

* AssertionDirectionType (The type of direction to use for assertion.)

4.2.12.695.1 Content

4.2.12.695.2 AssertionDirectionType

The type of direction to use for assertion.

This code system http://hl7.org/fhir/assert-direction-codes defines the following codes:

Code | Display | Definition
response | response | The assertion is evaluated on the response. This is the default value.
request | request | The assertion is evaluated on the request.

See the full registry of value sets defined as part of FHIR.

Explanation of the columns that may appear on this page:

Level | A few code lists that FHIR defines are hierarchical - each code is assigned a level. In this scheme, some codes are under other codes, and imply that the code they are under also applies
Source | The source of the definition of the code (when the value set draws in codes defined elsewhere)
Code | The code (used as the code in the resource instance). If the code is in italics, this indicates that the code is not selectable ('Abstract')
Display | The display (used in the display element of a Coding). If there is no display, implementers should not simply display the code, but map the concept into their application
Definition | An explanation of the meaning of the concept

Comments | Additional notes about how to use the code

4.2.12.697 Code System http://hl7.org/fhir/assert-operator-codes

URL: https://hl7.org/fhir/STU3/codesystem-assert-operator-codes.html

This page is part of the FHIR Specification (v3.0.2: STU 3). The current version which supercedes this version is 4.0.1. For a full list of available versions, see the Directory of published versions

Vocabulary Work Group | Maturity Level: 2 | Informative | Use Context: Any

This is a code system defined by the FHIR project.

Summary

Defining URL: | http://hl7.org/fhir/assert-operator-codes
Name: | AssertionOperatorType
Definition: | The type of operator to use for assertion.
Committee: | FHIR Infrastructure Work Group
OID: | 2.16.840.1.113883.4.642.1.697 (for OID based terminology systems)
Source Resource | XML / JSON

This Code system is used in the following value sets:

* AssertionOperatorType (The type of operator to use for assertion.)

4.2.12.697.1 Content

4.2.12.697.2 AssertionOperatorType

The type of operator to use for assertion.

This code system http://hl7.org/fhir/assert-operator-codes defines the following codes:

Code | Display | Definition
equals | equals | Default value. Equals comparison.
notEquals | notEquals | Not equals comparison.
in | in | Compare value within a known set of values.
notIn | notIn | Compare value not within a known set of values.
greaterThan | greaterThan | Compare value to be greater than a known value.
lessThan | lessThan | Compare value to be less than a known value.
empty | empty | Compare value is empty.
notEmpty | notEmpty | Compare value is not empty.
contains | contains | Compare value string contains a known value.
notContains | notContains | Compare value string does not contain a known value.
eval | evaluate | Evaluate the fluentpath expression as a boolean condition.

See the full registry of value sets defined as part of FHIR.

Explanation of the columns that may appear on this page:

Level | A few code lists that FHIR defines are hierarchical - each code is assigned a level. In this scheme, some codes are under other codes, and imply that the code they are under also applies
Source | The source of the definition of the code (when the value set draws in codes defined elsewhere)
Code | The code (used as the code in the resource instance). If the code is in italics, this indicates that the code is not selectable ('Abstract')
Display | The display (used in the display element of a Coding). If there is no display, implementers should not simply display the code, but map the concept into their application
Definition | An explanation of the meaning of the concept
Comments | Additional notes about how to use the code

4.2.12.699 Code System http://hl7.org/fhir/assert-response-code-types

URL: https://hl7.org/fhir/STU3/codesystem-assert-response-code-types.html

This page is part of the FHIR Specification (v3.0.2: STU 3). The current version which supercedes this version is 4.0.1. For a full list of available versions, see the Directory of published versions

Vocabulary Work Group | Maturity Level: 2 | Informative | Use Context: Any

This is a code system defined by the FHIR project.

Summary

Defining URL: | http://hl7.org/fhir/assert-response-code-types
Name: | AssertionResponseTypes
Definition: | The type of response code to use for assertion.
Committee: | FHIR Infrastructure Work Group
OID: | 2.16.840.1.113883.4.642.1.699 (for OID based terminology systems)
Source Resource | XML / JSON

This Code system is used in the following value sets:

* AssertionResponseTypes (The type of response code to use for assertion.)

4.2.12.699.1 Content

4.2.12.699.2 AssertionResponseTypes

The type of response code to use for assertion.

This code system http://hl7.org/fhir/assert-response-code-types defines the following codes:

Code | Display | Definition
okay | okay | Response code is 200.
created | created | Response code is 201.
noContent | noContent | Response code is 204.
notModified | notModified | Response code is 304.
bad | bad | Response code is 400.
forbidden | forbidden | Response code is 403.
notFound | notFound | Response code is 404.
methodNotAllowed | methodNotAllowed | Response code is 405.
conflict | conflict | Response code is 409.
gone | gone | Response code is 410.
preconditionFailed | preconditionFailed | Response code is 412.
unprocessable | unprocessable | Response code is 422.

See the full registry of value sets defined as part of FHIR.

Explanation of the columns that may appear on this page:

Level | A few code lists that FHIR defines are hierarchical - each code is assigned a level. In this scheme, some codes are under other codes, and imply that the code they are under also applies
Source | The source of the definition of the code (when the value set draws in codes defined elsewhere)
Code | The code (used as the code in the resource instance). If the code is in italics, this indicates that the code is not selectable ('Abstract')
Display | The display (used in the display element of a Coding). If there is no display, implementers should not simply display the code, but map the concept into their application
Definition | An explanation of the meaning of the concept
Comments | Additional notes about how to use the code

4.2.12.701 Code System http://hl7.org/fhir/testscript-profile-origin-types

URL: https://hl7.org/fhir/STU3/codesystem-testscript-profile-origin-types.html

This page is part of the FHIR Specification (v3.0.2: STU 3). The current version which supercedes this version is 4.0.1. For a full list of available versions, see the Directory of published versions

Vocabulary Work Group | Maturity Level: 2 | Informative | Use Context: Not Intended for Production use

This is a code system defined by the FHIR project.

Summary

Defining URL: | http://hl7.org/fhir/testscript-profile-origin-types
Name: | TestScriptProfileOriginType
Definition: | This value set defines a set of codes that are used to indicate the profile type of a test system when acting as the origin within a TestScript.
Committee: | FHIR Infrastructure Work Group
OID: | 2.16.840.1.113883.4.642.1.701 (for OID based terminology systems)
Source Resource | XML / JSON

This Code system is used in the following value sets:

* TestScriptProfileOriginType (This value set defines a set of codes that are used to indicate the profile type of a test system when acting as the origin within a TestScript.)

4.2.12.701.1 Content

4.2.12.701.2 TestScriptProfileOriginType

This value set defines a set of codes that are used to indicate the profile type of a test system when acting as the origin within a TestScript.

This code system http://hl7.org/fhir/testscript-profile-origin-types defines the following codes:

Code | Display | Definition
FHIR-Client | FHIR Client | General FHIR client used to initiate operations against a FHIR server.
FHIR-SDC-FormFiller | FHIR SDC FormFiller | A FHIR client acting as a Structured Data Capture Form Filler.

See the full registry of value sets defined as part of FHIR.

Explanation of the columns that may appear on this page:

Level | A few code lists that FHIR defines are hierarchical - each code is assigned a level. In this scheme, some codes are under other codes, and imply that the code they are under also applies
Source | The source of the definition of the code (when the value set draws in codes defined elsewhere)
Code | The code (used as the code in the resource instance). If the code is in italics, this indicates that the code is not selectable ('Abstract')
Display | The display (used in the display element of a Coding). If there is no display, implementers should not simply display the code, but map the concept into their application

Definition | An explanation of the meaning of the concept
Comments | Additional notes about how to use the code

4.2.12.703 Code System http://hl7.org/fhir/testscript-profile-destination-types

URL: https://hl7.org/fhir/STU3/codesystem-testscript-profile-destination-types.html

This page is part of the FHIR Specification (v3.0.2: STU 3). The current version which supercedes this version is 4.0.1. For a full list of available versions, see the Directory of published versions

Vocabulary Work Group | Maturity Level: 2 | Informative | Use Context: Not Intended for Production use

This is a code system defined by the FHIR project.

Summary

Defining URL: | http://hl7.org/fhir/testscript-profile-destination-types
Name: | TestScriptProfileDestinationType
Definition: | This value set defines a set of codes that are used to indicate the profile type of a test system when acting as the destination within a TestScript.
Committee: | FHIR Infrastructure Work Group
OID: | 2.16.840.1.113883.4.642.1.703 (for OID based terminology systems)
Source Resource | XML / JSON

This Code system is used in the following value sets:

* TestScriptProfileDestinationType (This value set defines a set of codes that are used to indicate the profile type of a test system when acting as the destination within a TestScript.)

4.2.12.703.1 Content

4.2.12.703.2 TestScriptProfileDestinationType

This value set defines a set of codes that are used to indicate the profile type of a test system when acting as the destination within a TestScript.

This code system http://hl7.org/fhir/testscript-profile-destination-types defines the following codes:

Code | Display | Definition
FHIR-Server | FHIR Server | General FHIR server used to respond to operations sent from a FHIR client.
FHIR-SDC-FormManager | FHIR SDC FormManager | A FHIR server acting as a Structured Data Capture Form Manager.
FHIR-SDC-FormProcessor | FHIR SDC FormProcessor | A FHIR server acting as a Structured Data Capture Form Processor.
FHIR-SDC-FormReceiver | FHIR SDC FormReceiver | A FHIR server acting as a Structured Data Capture Form Receiver.

See the full registry of value sets defined as part of FHIR.

Explanation of the columns that may appear on this page:

Level | A few code lists that FHIR defines are hierarchical - each code is assigned a level. In this scheme, some codes are under other codes, and imply that the code they are under also applies
Source | The source of the definition of the code (when the value set draws in codes defined elsewhere)
Code | The code (used as the code in the resource instance). If the code is in italics, this indicates that the code is not selectable ('Abstract')
Display | The display (used in the display element of a Coding). If there is no display, implementers should not simply display the code, but map the concept into their application
Definition | An explanation of the meaning of the concept
Comments | Additional notes about how to use the code

4.2.12.705 Code System http://hl7.org/fhir/http-operations

URL: https://hl7.org/fhir/STU3/codesystem-http-operations.html

This page is part of the FHIR Specification (v3.0.2: STU 3). The current version which supercedes this version is 4.0.1. For a full list of available versions, see the Directory of published versions

Vocabulary Work Group | Maturity Level: 2 | Informative | Use Context: Any

This is a code system defined by the FHIR project.

Summary

Defining URL: | http://hl7.org/fhir/http-operations
Name: | TestScriptRequestMethodCode
Definition: | The allowable request method or HTTP operation codes.
Committee: | FHIR Infrastructure Work Group
OID: | 2.16.840.1.113883.4.642.1.705 (for OID based terminology systems)
Source Resource | XML / JSON

This Code system is used in the following value sets:

* TestScriptRequestMethodCode (The allowable request method or HTTP operation codes.)

4.2.12.705.1 Content

4.2.12.705.2 TestScriptRequestMethodCode

The allowable request method or HTTP operation codes.

This code system http://hl7.org/fhir/http-operations defines the following codes:

Code | Display | Definition
delete | DELETE | HTTP DELETE operation
get | GET | HTTP GET operation
options | OPTIONS | HTTP OPTIONS operation
patch | PATCH | HTTP PATCH operation
post | POST | HTTP POST operation
put | PUT | HTTP PUT operation

See the full registry of value sets defined as part of FHIR.

Explanation of the columns that may appear on this page:

Level | A few code lists that FHIR defines are hierarchical - each code is assigned a level. In this scheme, some codes are under other codes, and imply that the code they are under also applies
Source | The source of the definition of the code (when the value set draws in codes defined elsewhere)
Code | The code (used as the code in the resource instance). If the code is in italics, this indicates that the code is not selectable ('Abstract')
Display | The display (used in the display element of a Coding). If there is no display, implementers should not simply display the code, but map the concept into their application
Definition | An explanation of the meaning of the concept
Comments | Additional notes about how to use the code

4.2.12.707 Code System http://hl7.org/fhir/report-result-codes

URL: https://hl7.org/fhir/STU3/codesystem-report-result-codes.html

This page is part of the FHIR Specification (v3.0.2: STU 3). The current version which supercedes this version is 4.0.1. For a full list of available versions, see the Directory of published versions

Vocabulary Work Group | Maturity Level: 0 | Informative | Use Context: Any

This is a code system defined by the FHIR project.

Summary

Defining URL: | http://hl7.org/fhir/report-result-codes
Name: | TestReportResult
Definition: | The reported execution result.
Committee: | FHIR Infrastructure Work Group
OID: | 2.16.840.1.113883.4.642.1.707 (for OID based terminology systems)
Source Resource | XML / JSON

This Code system is used in the following value sets:

* TestReportResult (The reported execution result.)

4.2.12.707.1 Content

4.2.12.707.2 TestReportResult

The reported execution result.

This code system http://hl7.org/fhir/report-result-codes defines the following codes:

Code | Display | Definition
pass | Pass | All test operations successfully passed all asserts
fail | Fail | One or more test operations failed one or more asserts
pending | Pending | One or more test operations is pending execution completion

See the full registry of value sets defined as part of FHIR.

Explanation of the columns that may appear on this page:

Level | A few code lists that FHIR defines are hierarchical - each code is assigned a level. In this scheme, some codes are under other codes, and imply that the code they are under also applies
Source | The source of the definition of the code (when the value set draws in codes defined elsewhere)
Code | The code (used as the code in the resource instance). If the code is in italics, this indicates that the code is not selectable ('Abstract')
Display | The display (used in the display element of a Coding). If there is no display, implementers should not simply display the code, but map the concept into their application
Definition | An explanation of the meaning of the concept
Comments | Additional notes about how to use the code

4.2.12.709 Code System http://hl7.org/fhir/report-action-result-codes

URL: https://hl7.org/fhir/STU3/codesystem-report-action-result-codes.html

This page is part of the FHIR Specification (v3.0.2: STU 3). The current version which supercedes this version is 4.0.1. For a full list of available versions, see the Directory of published versions

Vocabulary Work Group | Maturity Level: 0 | Informative | Use Context: Any

This is a code system defined by the FHIR project.

Summary

Defining URL: | http://hl7.org/fhir/report-action-result-codes
Name: | TestReportActionResult
Definition: | The results of executing an action.
Committee: | FHIR Infrastructure Work Group
OID: | 2.16.840.1.113883.4.642.1.709 (for OID based terminology systems)
Source Resource | XML / JSON

This Code system is used in the following value sets:

* TestReportActionResult (The results of executing an action.)

4.2.12.709.1 Content

4.2.12.709.2 TestReportActionResult

The results of executing an action.

This code system http://hl7.org/fhir/report-action-result-codes defines the following codes:

Code | Display | Definition
pass | Pass | The action was successful.
skip | Skip | The action was skipped.
fail | Fail | The action failed.
warning | Warning | The action passed but with warnings.
error | Error | The action encountered a fatal error and the engine was unable to process.

See the full registry of value sets defined as part of FHIR.

Explanation of the columns that may appear on this page:

Level | A few code lists that FHIR defines are hierarchical - each code is assigned a level. In this scheme, some codes are under other codes, and imply that the code they are under also applies
Source | The source of the definition of the code (when the value set draws in codes defined elsewhere)
Code | The code (used as the code in the resource instance). If the code is in italics, this indicates that the code is not selectable ('Abstract')
Display | The display (used in the display element of a Coding). If there is no display, implementers should not simply display the code, but map the concept into their application
Definition | An explanation of the meaning of the concept
Comments | Additional notes about how to use the code

4.2.12.711 Code System http://hl7.org/fhir/report-participant-type

URL: https://hl7.org/fhir/STU3/codesystem-report-participant-type.html

This page is part of the FHIR Specification (v3.0.2: STU 3). The current version which supercedes this version is 4.0.1. For a full list of available versions, see the Directory of published versions

Vocabulary Work Group | Maturity Level: 0 | Informative | Use Context: Any

This is a code system defined by the FHIR project.

Summary

Defining URL: | http://hl7.org/fhir/report-participant-type
Name: | TestReportParticipantType
Definition: | The type of participant.
Committee: | FHIR Infrastructure Work Group
OID: | 2.16.840.1.113883.4.642.1.711 (for OID based terminology systems)
Source Resource | XML / JSON

This Code system is used in the following value sets:

* TestReportParticipantType (The type of participant.)

4.2.12.711.1 Content

4.2.12.711.2 TestReportParticipantType

The type of participant.

This code system http://hl7.org/fhir/report-participant-type defines the following codes:

Code | Display | Definition
test-engine | Test Engine | The test execution engine.
client | Client | A FHIR Client
server | Server | A FHIR Server

See the full registry of value sets defined as part of FHIR.

Explanation of the columns that may appear on this page:

Level | A few code lists that FHIR defines are hierarchical - each code is assigned a level. In this scheme, some codes are under other codes, and imply that the code they are under also applies

Source | The source of the definition of the code (when the value set draws in codes defined elsewhere)
Code | The code (used as the code in the resource instance). If the code is in italics, this indicates that the code is not selectable ('Abstract')
Display | The display (used in the display element of a Coding). If there is no display, implementers should not simply display the code, but map the concept into their application
Definition | An explanation of the meaning of the concept
Comments | Additional notes about how to use the code

4.2.12.713 Code System http://hl7.org/fhir/report-status-codes

URL: https://hl7.org/fhir/STU3/codesystem-report-status-codes.html

This page is part of the FHIR Specification (v3.0.2: STU 3). The current version which supercedes this version is 4.0.1. For a full list of available versions, see the Directory of published versions

Vocabulary Work Group | Maturity Level: 0 | Informative | Use Context: Any

This is a code system defined by the FHIR project.

Summary

Defining URL: | http://hl7.org/fhir/report-status-codes
Name: | TestReportStatus
Definition: | The current status of the test report.
Committee: | FHIR Infrastructure Work Group
OID: | 2.16.840.1.113883.4.642.1.713 (for OID based terminology systems)
Source Resource | XML / JSON

This Code system is used in the following value sets:

* TestReportStatus (The current status of the test report.)

4.2.12.713.1 Content

4.2.12.713.2 TestReportStatus

The current status of the test report.

This code system http://hl7.org/fhir/report-status-codes defines the following codes:

Code | Display | Definition
completed | Completed | All test operations have completed
in-progress | In Progress | A test operations is currently executing
waiting | Waiting | A test operation is waiting for an external client request
stopped | Stopped | The test script execution was manually stopped
entered-in-error | Entered In Error | This test report was entered or created in error

See the full registry of value sets defined as part of FHIR.

Explanation of the columns that may appear on this page:

Level | A few code lists that FHIR defines are hierarchical - each code is assigned a level. In this scheme, some codes are under other codes, and imply that the code they are under also applies
Source | The source of the definition of the code (when the value set draws in codes defined elsewhere)
Code | The code (used as the code in the resource instance). If the code is in italics, this indicates that the code is not selectable ('Abstract')
Display | The display (used in the display element of a Coding). If there is no display, implementers should not simply display the code, but map the concept into their application
Definition | An explanation of the meaning of the concept
Comments | Additional notes about how to use the code

4.2.12.715 Code System http://hl7.org/fhir/account-status

URL: https://hl7.org/fhir/STU3/codesystem-account-status.html

This page is part of the FHIR Specification (v3.0.2: STU 3). The current version which supercedes this version is 4.0.1. For a full list of available versions, see the Directory of published versions

Vocabulary Work Group | Maturity Level: 2 | Informative | Use Context: Any

This is a code system defined by the FHIR project.

Summary

Defining URL: | http://hl7.org/fhir/account-status
Name: | AccountStatus
Definition: | Indicates whether the account is available to be used.
Committee: | Patient Administration Work Group
OID: | 2.16.840.1.113883.4.642.1.715 (for OID based terminology systems)
Source Resource | XML / JSON

This Code system is used in the following value sets:

* AccountStatus (Indicates whether the account is available to be used.)

4.2.12.715.1 Content

4.2.12.715.2 AccountStatus

Indicates whether the account is available to be used.

This code system http://hl7.org/fhir/account-status defines the following codes:

Code | Display | Definition
active | Active | This account is active and may be used.
inactive | Inactive | This account is inactive and should not be used to track financial information.
entered-in-error | Entered in error | This instance should not have been part of this patient's medical record.

See the full registry of value sets defined as part of FHIR.

Explanation of the columns that may appear on this page:

Level | A few code lists that FHIR defines are hierarchical - each code is assigned a level. In this scheme, some codes are under other codes, and imply that the code they are under also applies
Source | The source of the definition of the code (when the value set draws in codes defined elsewhere)
Code | The code (used as the code in the resource instance). If the code is in italics, this indicates that the code is not selectable ('Abstract')
Display | The display (used in the display element of a Coding). If there is no display, implementers should not simply display the code, but map the concept into their application
Definition | An explanation of the meaning of the concept
Comments | Additional notes about how to use the code

4.2.12.718 Code System http://hl7.org/fhir/contracttypecodes

URL: https://hl7.org/fhir/STU3/codesystem-contract-type.html

This page is part of the FHIR Specification (v3.0.2: STU 3). The current version which supercedes this version is 4.0.1. For a full list of available versions, see the Directory of published versions

Vocabulary Work Group | Maturity Level: 1 | Informative | Use Context: Not Intended for Production use

This is a code system defined by the FHIR project.

Summary

Defining URL: | http://hl7.org/fhir/contracttypecodes
Name: | Contract Type Codes
Definition: | This value set includes sample Contract Type codes.
Committee: | Financial Management Work Group
OID: | 2.16.840.1.113883.4.642.1.718 (for OID based terminology systems)
Copyright: | This is an example set.
Source Resource | XML / JSON

This Code system is used in the following value sets:

* Contract Type Codes (This value set includes sample Contract Type codes.)

4.2.12.718.1 Content

4.2.12.718.2 Contract Type Codes

This value set includes sample Contract Type codes.

Copyright Statement: This is an example set.

This code system http://hl7.org/fhir/contracttypecodes defines the following codes:

Code | Display | Definition
privacy | Privacy | Privacy policy.
disclosure | Disclosure | Information disclosure policy.
healthinsurance | Health Insurance | Health Insurance policy.
supply | Supply Contract | Contract to supply goods or services.
consent | Consent | Consent Directive.

See the full registry of value sets defined as part of FHIR.

Explanation of the columns that may appear on this page:

Level | A few code lists that FHIR defines are hierarchical - each code is assigned a level. In this scheme, some codes are under other codes, and imply that the code they are under also applies
Source | The source of the definition of the code (when the value set draws in codes defined elsewhere)
Code | The code (used as the code in the resource instance). If the code is in italics, this indicates that the code is not selectable ('Abstract')
Display | The display (used in the display element of a Coding). If there is no display, implementers should not simply display the code, but map the concept into their application
Definition | An explanation of the meaning of the concept
Comments | Additional notes about how to use the code

4.2.12.720 Code System http://hl7.org/fhir/contractsubtypecodes

URL: https://hl7.org/fhir/STU3/codesystem-contract-subtype.html

This page is part of the FHIR Specification (v3.0.2: STU 3). The current version which supercedes this version is 4.0.1. For a full list of available versions, see the Directory of published versions

Vocabulary Work Group | Maturity Level: 1 | Informative | Use Context: Not Intended for Production use

This is a code system defined by the FHIR project.

Summary

Defining URL: | http://hl7.org/fhir/contractsubtypecodes
Name: | Contract Subtype Codes
Definition: | This value set includes sample Contract Subtype codes.
Committee: | Financial Management Work Group
OID: | 2.16.840.1.113883.4.642.1.720 (for OID based terminology systems)
Copyright: | This is an example set.
Source Resource | XML / JSON

This Code system is used in the following value sets:

* Contract Subtype Codes (This value set includes sample Contract Subtype codes.)

4.2.12.720.1 Content

4.2.12.720.2 Contract Subtype Codes

This value set includes sample Contract Subtype codes.

Copyright Statement: This is an example set.

This code system http://hl7.org/fhir/contractsubtypecodes defines the following codes:

Code | Display | Definition
disclosure-ca | Disclosure-CA | Canadian health information displosure policy.
disclosure-us | Disclosure-US | United States health information displosure policy.

See the full registry of value sets defined as part of FHIR.

Explanation of the columns that may appear on this page:

Level | A few code lists that FHIR defines are hierarchical - each code is assigned a level. In this scheme, some codes are under other codes, and imply that the code they are under also applies
Source | The source of the definition of the code (when the value set draws in codes defined elsewhere)
Code | The code (used as the code in the resource instance). If the code is in italics, this indicates that the code is not selectable ('Abstract')
Display | The display (used in the display element of a Coding). If there is no display, implementers should not simply display the code, but map the concept into their application
Definition | An explanation of the meaning of the concept
Comments | Additional notes about how to use the code

4.2.12.722 Code System http://hl7.org/fhir/contracttermtypecodes

URL: https://hl7.org/fhir/STU3/codesystem-contract-term-type.html

This page is part of the FHIR Specification (v3.0.2: STU 3). The current version which supercedes this version is 4.0.1. For a full list of available versions, see the Directory of published versions

Vocabulary Work Group | Maturity Level: 1 | Informative | Use Context: Not Intended for Production use

This is a code system defined by the FHIR project.

Summary

Defining URL: | http://hl7.org/fhir/contracttermtypecodes
Name: | Contract Term Type Codes
Definition: | This value set includes sample Contract Term Type codes.
Committee: | Financial Management Work Group
OID: | 2.16.840.1.113883.4.642.1.722 (for OID based terminology systems)
Copyright: | This is an example set.
Source Resource | XML / JSON

This Code system is used in the following value sets:

* Contract Term Type Codes (This value set includes sample Contract Term Type codes.)

4.2.12.722.1 Content

4.2.12.722.2 Contract Term Type Codes

This value set includes sample Contract Term Type codes.

Copyright Statement: This is an example set.

This code system http://hl7.org/fhir/contracttermtypecodes defines the following codes:

Code | Display | Definition
statutory | Statutory | Based on specialized statutes that deal with particular subjects.
subject-to | Subject To | Execution of the term in the contract is conditional on the execution of other actions.

See the full registry of value sets defined as part of FHIR.

Explanation of the columns that may appear on this page:

Level | A few code lists that FHIR defines are hierarchical - each code is assigned a level. In this scheme, some codes are under other codes, and imply that the code they are under also applies
Source | The source of the definition of the code (when the value set draws in codes defined elsewhere)
Code | The code (used as the code in the resource instance). If the code is in italics, this indicates that the code is not selectable ('Abstract')
Display | The display (used in the display element of a Coding). If there is no display, implementers should not simply display the code, but map the concept into their application
Definition | An explanation of the meaning of the concept
Comments | Additional notes about how to use the code

4.2.12.724 Code System http://hl7.org/fhir/contracttermsubtypecodes

URL: https://hl7.org/fhir/STU3/codesystem-contract-term-subtype.html

This page is part of the FHIR Specification (v3.0.2: STU 3). The current version which supercedes this version is 4.0.1. For a full list of available versions, see the Directory of published versions

Vocabulary Work Group | Maturity Level: 1 | Informative | Use Context: Not Intended for Production use

This is a code system defined by the FHIR project.

Summary

Defining URL: | http://hl7.org/fhir/contracttermsubtypecodes
Name: | Contract Term Subtype Codes
Definition: | This value set includes sample Contract Term SubType codes.
Committee: | Financial Management Work Group
OID: | 2.16.840.1.113883.4.642.1.724 (for OID based terminology systems)
Copyright: | This is an example set.
Source Resource | XML / JSON

This Code system is used in the following value sets:

* Contract Term Subtype Codes (This value set includes sample Contract Term SubType codes.)

4.2.12.724.1 Content

4.2.12.724.2 Contract Term Subtype Codes

This value set includes sample Contract Term SubType codes.

Copyright Statement: This is an example set.

This code system http://hl7.org/fhir/contracttermsubtypecodes defines the following codes:

Code | Display | Definition
condition | Condition | Terms that go to the very root of a contract.
warranty | Warranty | Less imperative than a condition, so the contract will survive a breach
innominate | Innominate | Breach of which may or may not go to the root of the contract depending upon the nature of the breach

See the full registry of value sets defined as part of FHIR.

Explanation of the columns that may appear on this page:

Level | A few code lists that FHIR defines are hierarchical - each code is assigned a level. In this scheme, some codes are under other codes, and imply that the code they are under also applies
Source | The source of the definition of the code (when the value set draws in codes defined elsewhere)
Code | The code (used as the code in the resource instance). If the code is in italics, this indicates that the code is not selectable ('Abstract')
Display | The display (used in the display element of a Coding). If there is no display, implementers should not simply display the code, but map the concept into their application
Definition | An explanation of the meaning of the concept
Comments | Additional notes about how to use the code

4.2.12.726 Code System http://www.hl7.org/fhir/contractsignertypecodes

URL: https://hl7.org/fhir/STU3/codesystem-contract-signer-type.html

This page is part of the FHIR Specification (v3.0.2: STU 3). The current version which supercedes this version is 4.0.1. For a full list of available versions, see the Directory of published versions

Vocabulary Work Group | Maturity Level: 1 | Informative | Use Context: Not Intended for Production use

This is a code system defined by the FHIR project.

Summary

Defining URL: | http://www.hl7.org/fhir/contractsignertypecodes
Name: | Contract Signer Type Codes
Definition: | This value set includes sample Contract Signer Type codes.
Committee: | Financial Management Work Group
OID: | 2.16.840.1.113883.4.642.1.726 (for OID based terminology systems)
Copyright: | This is an example set based on ASTM Standard, E1762-95 (2013) HL7 RoleClass OID 2.16.840.1.113883.5.110, HL7 Role Code 2.16.840.1.113883.5.111, HL7 ParticipationType OID: 2.16.840.1.113883.5.90, HL7 ParticipationFunction codes at OID: 2.16.840.1.113883.5.88, and HL7 Security and Privacy Domain Analysis Model roles classes.
Source Resource | XML / JSON

This Code system is used in the following value sets:

* Contract Signer Type Codes (This value set includes sample Contract Signer Type codes.)

4.2.12.726.1 Content

4.2.12.726.2 Contract Signer Type Codes

This value set includes sample Contract Signer Type codes.

Copyright Statement: This is an example set based on ASTM Standard, E1762-95 (2013) HL7 RoleClass OID 2.16.840.1.113883.5.110, HL7 Role Code 2.16.840.1.113883.5.111, HL7 ParticipationType OID: 2.16.840.1.113883.5.90, HL7 ParticipationFunction codes at OID: 2.16.840.1.113883.5.88, and HL7 Security and Privacy Domain Analysis Model roles classes.

This code system http://www.hl7.org/fhir/contractsignertypecodes defines the following codes:

Code | Display | Definition

AMENDER | Amender | A person who has corrected, edited, or amended pre-existing information.

AUTHN | Authenticator | A person in the role of verifier who attests to the accuracy of an act, but who does not have privileges to legally authenticate information content. An example would be a resident physician who sees a patient and dictates a note, then later signs it. The resident's signature constitutes an authentication.

AUT | Author | An entity that authored specific content. There can be multiple authors of content, which may take such forms as a contract, a healthcare record entry or document, a policy, or a consent directive.

AFFL | Affiliate | An entity that has a business or professional relationship with another entity in accordance with an agreement.

AGNT | Agent | An entity that acts or is authorized to act on behalf of another entity in accordance with an agreement.

ASSIGNED | Assigned Entity | An agent role in which the agent is an Entity acting in the employ of an organization. The focus is on functional role on behalf of the organization, unlike the Employee role where the focus is on the 'Human Resources' relationship between the employee and the organization.

CIT | Citizen | The member of a jurisdiction afforded certain rights and encumbered with certain obligation in accordance with jurisdictional policy.

CLAIMANT | Claimant | A party that makes a claim for coverage under a policy.

COAUTH | Co-Author | The entity that co-authored content. There can be multiple co-authors of content,which may take such forms as a such as a contract, a healthcare record entry or document, a policy, or a consent directive.

CONSENTER | Consenter | A patient or patient representative who is the grantee in a healthcare related agreement such as a consent for healthcare services, advanced directive, or a privacy consent directive in accordance with jurisdictional, organizational, or patient policy.

CONSWIT | Consent Witness | A person who has witnessed and attests to observing a patient being counseled about a healthcare related agreement such as a consent for healthcare services, advanced directive, or a privacy consent directive.

CONT | Contact | A person or an organization that provides or receives information regarding another entity. Examples; patient NOK and emergency contacts; guarantor contact; employer contact.

COPART | Co-Participant | A person who participates in the generation of and attest to veracity of content, but is not an author or co-author. For example a surgeon who is required by institutional, regulatory, or legal rules to sign an operative report, but who was not involved in the authorship of that report.

COVPTY | Covered Party | An entity, which is the insured, that receives benefits such as healthcare services, reimbursement for out-of-pocket expenses, or compensation for losses through coverage under the terms of an insurance policy. The underwriter of that policy is the scoping entity. The covered party receives coverage because of some contractual or other relationship with the holder of that policy. Note that a particular policy may cover several individuals one of whom may be, but need not be, the policy holder. Thus the notion of covered party is a role that is distinct from that of the policy holder.

DELEGATEE | Delegatee | A party to whom some right or authority is delegated by a delegator.

delegator | Delegator | A party that delegates a right or authority to another party.

DEPEND | Dependent | A person covered under an insurance policy or program based on an association with a subscriber, which is recognized by the policy holder. The dependent has an association with the subscriber such as a financial dependency or personal relationship such as that of a spouse, or a natural or adopted child. The policy holder may be required by law to recognize certain associations or may have discretion about the associations. For example, a policy holder may dictate the criteria for the dependent status of adult children who are students, such as requiring full time enrollment, or may recognize domestic partners as dependents. Under certain circumstances, the dependent may be under the indirect authority of a responsible party acting as a surrogate for the subscriber, for example, if the subscriber is differently-abled or deceased, a guardian ad Lidem or estate executor may be appointed to assume the subscriber's legal standing in the relationship with the dependent.

DPOWATT | Durable Power of Attorney | A person who has been granted the authority to represent or act on another's behalf generally in a manner which is a legally binding upon the person giving such authority as if he or she personally were to do the acts. Unlike ordinary powers of attorney, durable powers can survive for long periods of time, and again, unlike standard powers of attorney, durable powers can continue after incompetency.

EMGCON | Emergency Contact | An entity to be contacted in the event of an emergency

EVTWIT | Event Witness | A person who attests to observing an occurrence. For example, the witness has observed a procedure and is attesting to this fact.

EXCEST | Executor of Estate | A person who has been granted the authority to act as an estate executor for a deceased person who was the responsible party.

GRANTEE | Grantee | A person who grants to another person the authority to represent or act on that person's behalf. Examples include (1) exercising specific rights belonging to the grantee; (2) performing specific duties on behalf of a grantee; and (3) making specific decisions concerning a grantee.

GRANTOR | Grantor | A person who has been granted the authority to represent or act on another's behalf. Examples include (1) exercising specific rights belonging to the grantee; (2) performing specific duties on behalf of a grantee; and (3) making specific decisions concerning a grantee.

GUAR | Guarantor | A person or organization contractually recognized by the issuer as an entity that has assumed fiscal responsibility (e.g., by making or giving a promise, assurance, or pledge) for another entity's financial obligations by guaranteeing to pay for amounts owed to a particular account. In a healthcare context, the account may be a patient's billing account for services rendered by a provider or a health plan premium account.

GUARD | Guardian | A person or organization legally empowered with responsibility for the care of a ward.

GUADLTM | Guardian ad lidem | A person appointed by the court to look out for the best interests of a minor child during the course of legal proceedings.

INF | Informant | An entity that is the source of reported information (e.g., a next of kin who answers questions about the patient's history). For history questions, the patient is logically an informant, yet the informant of history questions is implicitly the subject.

INTPRT | Interpreter | A person who converts spoken or written language into the language of key participants in an event such as when a provider is obtaining a patient's consent to treatment or permission to disclose information.

INSBJ | Investigation Subject | An entity that is the subject of an investigation. This role is scoped by the party responsible for the investigation.

HPOWATT | Healthcare Power of Attorney | A person who has been granted the authority to represent or act on another's behalf for healthcare related matters in a manner which is a legally binding upon the person giving such authority as if he or she personally were to do the acts. Examples include (1) exercising specific healthcare legal rights belonging to the grantee such as signing a consent directive; (2) performing specific healthcare related legal duties on behalf of a grantee such as claims payment; and (3) making specific healthcare legal decisions concerning a grantee such as consenting to healthcare services.

HPROV | Healthcare Provider | An entity that is authorized to provide health care services by an authorizing organization or jurisdiction.

LEGAUTHN | Legal Authenticator | A person in the role of verifier who attests to the accuracy of information content, and who has privileges to certify the legal authenticity of that content with a signature that constitutes a legal authentication. For example, a licensed physician who signs a consult authored by a resident physician who authenticated it.

NMDINS | Named Insured | A party to an insurance policy under which the insurer agrees to indemnify for losses, provides benefits for, or renders services. A named insured may be either a person, non-person living subject, or an organization, or a group of persons, non-person living subject that is the named insured under a comprehensive automobile, disability, or property and casualty policy. The named insured and may or may not be the policy holder.

NOK | Next of Kin | A person, who is a type of contact, designated to receive notifications on behalf of another person who is a relative.

NOTARY | Notary | The party credentialed to legally attest to the contract binding by verifying the identity and capacity of the grantor and grantee, and witnessing their signing of the contract or agreement such as a real estate transaction, pre-nuptial agreement, or a will.

PAT | Patient | A person, animal, or other living subject that is the actual or potential recipient of health care services.

POWATT | Power of Attorney | A person who has been granted the authority to represent or act on another's behalf generally in a manner which is a legally binding upon the person giving such authority as if he or she personally were to do the acts. Examples include (1) exercising specific legal rights belonging to the grantee such as signing a contract; (2) performing specific legal duties on behalf of a grantee such as making loan payments; and (3) making specific legal decisions concerning a grantee such as financial investment decisions.

PRIMAUTH | Primary Author | An entity that is the primary or sole author of information content. In the healthcare context, there can be only one primary author of health information content in a record entry or document.

PRIRECIP | Primary Responsible Party | An entity that may, should receive, or has received information or an object to which it was primarily addressed.

RECIP | Recipient | An entity that may, should receive, or has received information or an object, which may not have been primarily addressed to it. For example, the staff of a provider, a clearinghouse, or other intermediary.

RESPRSN | Responsible Party | An entity that has legal responsibility for another party.

REVIEWER | Reviewer | A person, device, or algorithm that has used approved criteria for filtered data for inclusion into the patient record. Examples: (1) a medical records clerk who scans a document for inclusion in the medical record, enters header information, or catalogues and classifies the data, or a combination thereof; (2) a gateway that receives data from another computer system and interprets that data or changes its format, or both, before entering it into the patient record.

TRANS | Transcriber | An entity entering the data into the originating system. This includes the transcriptionist for dictated text transcribed into electronic form.

SOURCE | Source | An automated data source that generates a signature along with content. Examples: (1) the signature for an image that is generated by a device for inclusion in the patient record; (2) the signature for an ECG derived by an ECG system for inclusion in the patient record; (3) the data from a biomedical monitoring device or system that is for inclusion in the patient record.

SPOWATT | Apecial Power of Attorney | A person who has been granted the authority to represent or act on another's behalf for a limited set of specific matters in a manner which is a legally binding upon the person giving such authority as if he or she personally were to do the acts. Examples include (1) exercising specific legal rights belonging to the grantee such as drafting a will; (2) performing specific legal duties on behalf of a grantee such as making a reversible mortgage to pay for end of life expenses; and (3) making specific legal decisions concerning a grantee such as managing a trust.

VALID | Validator | A person who validates a health information document for inclusion in the patient record. For example, a medical student or resident is credentialed to perform history or physical examinations and to write progress notes. The attending physician signs the history and physical examination to validate the entry for inclusion in the patient's medical record.

VERF | Verifier | A person who asserts the correctness and appropriateness of an act or the recording of the act, and is accountable for the assertion that the act or the recording of the act complies with jurisdictional or organizational policy. For example, a physician is required to countersign a verbal order that has previously been recorded in the medical record by a registered nurse who has carried out the verbal order.

WIT | Witness | A person witnessing the signature of another party. A witness is not knowledgeable about the content being signed, much less approves of anything stated in the content. For example, an advanced directive witness or a witness that a party to a contract signed that certain demographic or financial information is truthful.

See the full registry of value sets defined as part of FHIR.

Explanation of the columns that may appear on this page:

Level | A few code lists that FHIR defines are hierarchical - each code is assigned a level. In this scheme, some codes are under other codes, and imply that the code they are under also applies

Source | The source of the definition of the code (when the value set draws in codes defined elsewhere)

Code | The code (used as the code in the resource instance). If the code is in italics, this indicates that the code is not selectable ('Abstract')

Display | The display (used in the display element of a Coding). If there is no display, implementers should not simply display the code, but map the concept into their application

Definition | An explanation of the meaning of the concept

Comments | Additional notes about how to use the code

4.2.12.728 Code System http://www.hl7.org/fhir/contractaction

URL: https://hl7.org/fhir/STU3/codesystem-contract-action.html

This page is part of the FHIR Specification (v3.0.2: STU 3). The current version which supercedes this version is 4.0.1. For a full list of available versions, see the Directory of published versions

Vocabulary Work Group | Maturity Level: 1 | Informative | Use Context: Not Intended for Production use

This is a code system defined by the FHIR project.

Summary

Defining URL: | http://www.hl7.org/fhir/contractaction
Name: | Contract Action Codes
Definition: | This value set includes sample Contract Action codes.
Committee: | Financial Management Work Group
OID: | 2.16.840.1.113883.4.642.1.728 (for OID based terminology systems)
Copyright: | This is an example set.
Source Resource | XML / JSON

This Code system is used in the following value sets:

* Contract Action Codes (This value set includes sample Contract Action codes.)

4.2.12.728.1 Content

4.2.12.728.2 Contract Action Codes

This value set includes sample Contract Action codes.

Copyright Statement: This is an example set.

This code system http://www.hl7.org/fhir/contractaction defines the following codes:

Code | Display | Definition
action-a | Action A | Definition for Action A
action-b | Action B | Definition for Action B

See the full registry of value sets defined as part of FHIR.

Explanation of the columns that may appear on this page:

Level | A few code lists that FHIR defines are hierarchical - each code is assigned a level. In this scheme, some codes are under other codes, and imply that the code they are under also applies
Source | The source of the definition of the code (when the value set draws in codes defined elsewhere)
Code | The code (used as the code in the resource instance). If the code is in italics, this indicates that the code is not selectable ('Abstract')
Display | The display (used in the display element of a Coding). If there is no display, implementers should not simply display the code, but map the concept into their application
Definition | An explanation of the meaning of the concept
Comments | Additional notes about how to use the code

4.2.12.730 Code System http://www.hl7.org/fhir/contractactorrole

URL: https://hl7.org/fhir/STU3/codesystem-contract-actorrole.html

This page is part of the FHIR Specification (v3.0.2: STU 3). The current version which supercedes this version is 4.0.1. For a full list of available versions, see the Directory of published versions

Vocabulary Work Group | Maturity Level: 1 | Informative | Use Context: Not Intended for Production use

This is a code system defined by the FHIR project.

Summary

Defining URL: | http://www.hl7.org/fhir/contractactorrole
Name: | Contract Actor Role Codes
Definition: | This value set includes sample Contract Actor Role codes.
Committee: | Financial Management Work Group
OID: | 2.16.840.1.113883.4.642.1.730 (for OID based terminology systems)
Copyright: | This is an example set.
Source Resource | XML / JSON

This Code system is used in the following value sets:

* Contract Actor Role Codes (This value set includes sample Contract Actor Role codes.)

4.2.12.730.1 Content

4.2.12.730.2 Contract Actor Role Codes

This value set includes sample Contract Actor Role codes.

Copyright Statement: This is an example set.

This code system http://www.hl7.org/fhir/contractactorrole defines the following codes:

Code | Display | Definition
practitioner | Practitioner | Someone who provides health care related services to people or animals including both clinical and support services.
patient | Patient | A receiver, human or animal, of health care related goods and services.

See the full registry of value sets defined as part of FHIR.

Explanation of the columns that may appear on this page:

Level | A few code lists that FHIR defines are hierarchical - each code is assigned a level. In this scheme, some codes are under other codes, and imply that the code they are under also applies
Source | The source of the definition of the code (when the value set draws in codes defined elsewhere)
Code | The code (used as the code in the resource instance). If the code is in italics, this indicates that the code is not selectable ('Abstract')

Display | The display (used in the display element of a Coding). If there is no display, implementers should not simply display the code, but map the concept into their application

Definition | An explanation of the meaning of the concept

Comments | Additional notes about how to use the code

4.2.12.732 Code System http://hl7.org/fhir/contract-status

URL: https://hl7.org/fhir/STU3/codesystem-contract-status.html

This page is part of the FHIR Specification (v3.0.2: STU 3). The current version which supercedes this version is 4.0.1. For a full list of available versions, see the Directory of published versions

Vocabulary Work Group | Maturity Level: 1 | Informative | Use Context: Not Intended for Production use

This is a code system defined by the FHIR project.

Summary

Defining URL: | http://hl7.org/fhir/contract-status

Name: | Contract Resource Status Codes

Definition: | This value set contract specific codes for status.

Committee: | Financial Management Work Group

OID: | 2.16.840.1.113883.4.642.1.732 (for OID based terminology systems)

Copyright: | HL7 International.

Source Resource | XML / JSON

This Code system is used in the following value sets:

* Contract Resource Status Codes (This value set contract specific codes for status.)

4.2.12.732.1 Content

Each definition includes usage notes explaining the precedence order in contract lifecycle - i.e., while only some stages are required, the order in which they may occur is deterministic; and a map to comparable FHIR and v.3 status codes. It follows guidance about use of status codes in FHIR at http://hl7-fhir.github.io/sc.html.

4.2.12.732.2 Contract Resource Status Codes

This value set contract specific codes for status.

Copyright Statement: HL7 International.

This code system http://hl7.org/fhir/contract-status defines the following codes:

Code | Display | Definition

amended | Amended | Contract is augmented with additional information to correct errors in a predecessor or to updated values in a predecessor. Usage: Contract altered within effective time. Precedence Order = 9. Comparable FHIR and v.3 status codes: revised; replaced.

appended | Appended | Contract is augmented with additional information that was missing from a predecessor Contract. Usage: Contract altered within effective time. Precedence Order = 9. Comparable FHIR and v.3 status codes: updated, replaced.

cancelled | Cancelled | Contract is terminated due to failure of the Grantor and/or the Grantee to fulfil one or more contract provisions. Usage: Abnormal contract termination. Precedence Order = 10. Comparable FHIR and v.3 status codes: stopped; failed; aborted.

disputed | Disputed | Contract is pended to rectify failure of the Grantor or the Grantee to fulfil contract provision(s). E.g., Grantee complaint about Grantor's failure to comply with contract provisions. Usage: Contract pended. Precedence Order = 7.Comparable FHIR and v.3 status codes: on hold; pended; suspended.

entered-in-error | Entered in Error | Contract was created in error. No Precedence Order. Status may be applied to a Contract with any status.

executable | Executable | Contract execution pending; may be executed when either the Grantor or the Grantee accepts the contract provisions by signing. I.e., where either the Grantor or the Grantee has signed, but not both. E.g., when an insurance applicant signs the insurers application, which references the policy. Usage: Optional first step of contract execution activity. May be skipped and contracting activity moves directly to executed state. Precedence Order = 3. Comparable FHIR and v.3 status codes: draft; preliminary; planned; intended; active.

executed | Executed | Contract is activated for period stipulated when both the Grantor and Grantee have signed it. Usage: Required state for normal completion of contracting activity. Precedence Order = 6. Comparable FHIR and v.3 status codes: accepted; completed.

negotiable | Negotiable | Contract execution is suspended while either or both the Grantor and Grantee propose and consider new or revised contract provisions. I.e., where the party which has not signed proposes changes to the terms. E .g., a life insurer declines to agree to the signed application because the life insurer has evidence that the applicant, who asserted to being younger or a non-smoker to get a lower premium rate - but offers instead to agree to a higher premium based on the applicants actual age or smoking status. Usage: Optional contract activity between executable and executed state. Precedence Order = 4. Comparable FHIR and v.3 status codes: in progress; review; held.

offered | Offered | Contract is a proposal by either the Grantor or the Grantee. Aka - A Contract hard copy or electronic 'template','form' or 'application'. E.g., health insurance application; consent directive form. Usage: Beginning of contract negotiation, which may have been completed as a precondition because used for 0..* contracts. Precedence Order = 2. Comparable FHIR and v.3 status codes: requested; new.

policy | Policy | Contract template is available as the basis for an application or offer by the Grantor or Grantee. E.g., health insurance policy; consent directive policy. Usage: Required initial contract activity, which may have been completed as a precondition because used for 0..* contracts. Precedence Order = 1. Comparable FHIR and v.3 status codes: proposed; intended.

rejected | Rejected | Execution of the Contract is not completed because either or both the Grantor and Grantee decline to accept some or all of the contract provisions. Usage: Optional contract activity between executable and abnormal termination. Precedence Order = 5. Comparable FHIR and v.3 status codes: stopped; cancelled.

renewed | Renewed | Beginning of a successor Contract at the termination of predecessor Contract lifecycle. Usage: Follows termination of a preceding Contract that has reached its expiry date. Precedence Order = 13. Comparable FHIR and v.3 status codes: superseded.

revoked | Revoked | A Contract that is rescinded. May be required prior to replacing with an updated Contract. Comparable FHIR and v.3 status codes: nullified.

resolved | Resolved | Contract is reactivated after being pended because of faulty execution. *E.g., competency of the signer(s), or where the policy is substantially different from and did not accompany the application/form so that the applicant could not compare them. Aka - "reactivated". Usage:

Optional stage where a pended contract is reactivated. Precedence Order = 8. Comparable FHIR and v.3 status codes: reactivated.

terminated | Terminated | Contract reaches its expiry date. It may or may not be renewed or renegotiated. Usage: Normal end of contract period. Precedence Order = 12. Comparable FHIR and v.3 status codes: Obsoleted.

See the full registry of value sets defined as part of FHIR.

Explanation of the columns that may appear on this page:

Level | A few code lists that FHIR defines are hierarchical - each code is assigned a level. In this scheme, some codes are under other codes, and imply that the code they are under also applies

Source | The source of the definition of the code (when the value set draws in codes defined elsewhere)

Code | The code (used as the code in the resource instance). If the code is in italics, this indicates that the code is not selectable ('Abstract')

Display | The display (used in the display element of a Coding). If there is no display, implementers should not simply display the code, but map the concept into their application

Definition | An explanation of the meaning of the concept

Comments | Additional notes about how to use the code

4.2.12.734 Code System http://hl7.org/fhir/contract-content-derivative

URL: https://hl7.org/fhir/STU3/codesystem-contract-content-derivative.html

This page is part of the FHIR Specification (v3.0.2: STU 3). The current version which supercedes this version is 4.0.1. For a full list of available versions, see the Directory of published versions

Vocabulary Work Group | Maturity Level: 1 | Informative | Use Context: Not Intended for Production use

This is a code system defined by the FHIR project.

Summary

Defining URL: | http://hl7.org/fhir/contract-content-derivative

Name: | Contract Content Derivation Codes

Definition: | This is an example set of Content Derivative type codes, which represent the minimal content derived from the basal information source at a specific stage in its lifecycle, which is sufficient to manage that source information, for example, in a repository, registry, processes and workflows, for making access control decisions, and providing query responses.

Committee: | Financial Management Work Group

OID: | 2.16.840.1.113883.4.642.1.734 (for OID based terminology systems)

Copyright: | This is an example set.

Source Resource | XML / JSON

This Code system is used in the following value sets:

* Contract Content Derivation Codes (This is an example set of Content Derivative type codes, which represent the minimal content derived from the basal information source at a specific stage in its lifecycle, which is sufficient to manage that source information, for example, in a repository, registry, processes and workflows, for making access control decisions, and providing query responses.)

4.2.12.734.1 Content

This is an example set of Content Derivative type codes, which represent the minimal content derived from the basal information source at a specific stage in its lifecycle, which is sufficient to manage that source information, for example, in a repository, registry, processes and workflows, for making access control decisions, and providing query responses.

4.2.12.734.2 Contract Content Derivation Codes

This is an example set of Content Derivative type codes, which represent the minimal content derived from the basal information source at a specific stage in its lifecycle, which is sufficient to manage that source information, for example, in a repository, registry, processes and workflows, for making access control decisions, and providing query responses.

Copyright Statement: This is an example set.

This code system http://hl7.org/fhir/contract-content-derivative defines the following codes:

Code | Display | Definition

registration | Content Registration | Content derivative that conveys sufficient information needed to register the source basal content from which it is derived. This derivative content may be used to register the basal content as it changes status in its lifecycle. For example, content registration may occur when the basal content is created, updated, inactive, or deleted.

retrieval | Content Retrieval | A content derivative that conveys sufficient information to locate and retrieve the content.

statement | Content Statement | Content derivative that has less than full fidelity to the basal information source from which it was 'transcribed'. It provides recipients with the full content representation they may require for compliance purposes, and typically include a reference to or an attached unstructured representation for recipients needing an exact copy of the legal agreement.

shareable | Shareable Content | A Content Derivative that conveys sufficient information to determine the authorized entities with which the content may be shared.

See the full registry of value sets defined as part of FHIR.

Explanation of the columns that may appear on this page:

Level | A few code lists that FHIR defines are hierarchical - each code is assigned a level. In this scheme, some codes are under other codes, and imply that the code they are under also applies

Source | The source of the definition of the code (when the value set draws in codes defined elsewhere)

Code | The code (used as the code in the resource instance). If the code is in italics, this indicates that the code is not selectable ('Abstract')

Display | The display (used in the display element of a Coding). If there is no display, implementers should not simply display the code, but map the concept into their application

Definition | An explanation of the meaning of the concept
Comments | Additional notes about how to use the code

4.2.12.736 Code System http://hl7.org/fhir/consentcategorycodes

URL: https://hl7.org/fhir/STU3/codesystem-consent-category.html

This page is part of the FHIR Specification (v3.0.2: STU 3). The current version which supercedes this version is 4.0.1. For a full list of available versions, see the Directory of published versions

Vocabulary Work Group | Maturity Level: 1 | Informative | Use Context: Not Intended for Production use

This is a code system defined by the FHIR project.

Summary

Defining URL: | http://hl7.org/fhir/consentcategorycodes
Name: | Consent Category Codes
Definition: | This value set includes sample Consent Directive Type codes, including several consent directive related LOINC codes; HL7 VALUE SET: ActConsentType(2.16.840.1.113883.1.11.19897); examples of US realm consent directive legal descriptions and references to online and/or downloadable forms such as the SSA-827 Authorization to Disclose Information to the Social Security Administration; and other anticipated consent directives related to participation in a clinical trial, medical procedures, reproductive procedures; health care directive (Living Will); advance directive, do not resuscitate (DNR); Physician Orders for Life-Sustaining Treatment (POLST)
Committee: | Community Based Collaborative Care Work Group
OID: | 2.16.840.1.113883.4.642.1.736 (for OID based terminology systems)
Copyright: | This value set includes content from LOINC® which is copyright © 1995 Regenstrief Institute, Inc. and the LOINC Committee, and available at no cost under the license at http://loinc.org/terms-of-use
Source Resource | XML / JSON

This Code system is used in the following value sets:

* Consent Category Codes (This value set includes sample Consent Directive Type codes, including several consent directive related LOINC codes; HL7 VALUE SET: ActConsentType(2.16.840.1.113883.1.11.19897); examples of US realm consent directive legal descriptions and references to online and/or downloadable forms such as the SSA-827 Authorization to Disclose Information to the Social Security Administration; and other anticipated consent directives related to participation in a clinical trial, medical procedures, reproductive procedures; health care directive (Living Will); advance directive, do not resuscitate (DNR); Physician Orders for Life-Sustaining Treatment (POLST))

4.2.12.736.1 Content

4.2.12.736.2 Consent Category Codes

This value set includes sample Consent Directive Type codes, including several consent directive related LOINC codes; HL7 VALUE SET: ActConsentType(2.16.840.1.113883.1.11.19897); examples of US realm consent directive legal descriptions and references to online and/or downloadable forms such as the SSA-827 Authorization to Disclose Information to the Social Security Administration; and other anticipated consent directives related to participation in a clinical trial, medical procedures, reproductive procedures; health care directive (Living Will); advance directive, do not resuscitate (DNR); Physician Orders for Life-Sustaining Treatment (POLST)

Copyright Statement: This value set includes content from LOINC® which is copyright © 1995 Regenstrief Institute, Inc. and the LOINC Committee, and available at no cost under the license at http://loinc.org/terms-of-use

This code system http://hl7.org/fhir/consentcategorycodes defines the following codes:

Code | Display | Definition
42-CFR-2 | 42 CFR Part 2 Form of written consent | Required elements in a written consent to a disclosure of information governed under 42 CFR Part 2. http://www.ecfr.gov/cgi-bin/text-idx?SID=69c4339acd2df9fab9dcbed15181917b&mc=true&node=pt42.1.2&rgn=div5
ACD | advance directive | Any instructions, written or given verbally by a patient to a health care provider in anticipation of potential need for medical treatment. [2005 Honor My Wishes]
CRIC | common rule informed consent | 45 CFR part 46 Â§46.116 General requirements for informed consent; and Â§46.117 Documentation of informed consent. https://www.gpo.gov/fdsys/pkg/FR-2017-01-19/pdf/2017-01058.pdf
DNR | do not resuscitate | A legal document, signed by both the patient and their provider, stating a desire not to have CPR initiated in case of a cardiac event. Note: This form was replaced in 2003 with the Physician Orders for Life-Sustaining Treatment [POLST].
EMRGONLY | emergency only | Opt-in to disclosure of health information for emergency only consent directive. Comment: This general consent directive specifically limits disclosure of health information for purpose of emergency treatment. Additional parameters may further limit the disclosure to specific users, roles, duration, types of information, and impose uses obligations. [ActConsentDirective (2.16.840.1.113883.1.11.20425)]
Illinois-Minor-Procedure | Illinois Consent by Minors to Medical Procedures | The consent to the performance of a medical or surgical procedure by a physician licensed to practice medicine and surgery, a licensed advanced practice nurse, or a licensed physician assistant executed by a married person who is a minor, by a parent who is a minor, by a pregnant woman who is a minor, or by any person 18 years of age or older, is not voidable because of such minority, and, for such purpose, a married person who is a minor, a parent who is a minor, a pregnant woman who is a minor, or any person 18 years of age or older, is deemed to have the same legal capacity to act and has the same powers and obligations as has a person of legal age. Consent by Minors to Medical Procedures Act. (410 ILCS 210/0.01) (from Ch. 111, par. 4500) Sec. 0.01. Short title. This Act may be cited as the Consent by Minors to Medical Procedures Act. (Source: P.A. 86-1324.) http://www.ilga.gov/legislation/ilcs/ilcs3.asp?ActID=1539&ChapterID=35
HCD | health care directive | Patientâ€™s document telling patientâ€™s health care provider what the patient wants or does not want if the patient is diagnosed as being terminally ill and in a persistent vegetative state or in a permanently unconscious condition.[2005 Honor My Wishes]
HIPAA-Auth | HIPAA Authorization | HIPAA 45 CFR Section 164.508 Uses and disclosures for which an authorization is required. (a) Standard: Authorizations for uses and disclosures. (1) Authorization required: General rule. Except as otherwise permitted or required by this subchapter, a covered entity may not use or disclose protected health information without an authorization that is valid under this section. When a covered entity obtains or receives a valid authorization for its use or disclosure of protected health information, such use or disclosure must be consistent with such authorization. Usage Note: Authorizations governed under this regulation meet the definition of an opt in class of consent directive.

HIPAA-NPP | HIPAA Notice of Privacy Practices | Â§ 164.520 â€” Notice of privacy practices for protected health information. (1) Right to notice. Except as provided by paragraph (a)(2) or (3) of this section, an individual has a right to adequate notice of the uses and disclosures of protected health information that may be made by the covered entity, and of the individual's rights and the covered entity's legal duties with respect to protected health information. Usage Note: Restrictions governed under this regulation meet the definition of an implied with an opportunity to dissent class of consent directive.

HIPAA-Restrictions | HIPAA Restrictions | HIPAA 45 CFR Â§ 164.510 - Uses and disclosures requiring an opportunity for the individual to agree or to object. A covered entity may use or disclose protected health information, provided that the individual is informed in advance of the use or disclosure and has the opportunity to agree to or prohibit or restrict the use or disclosure, in accordance with the applicable requirements of this section. The covered entity may orally inform the individual of and obtain the individual's oral agreement or objection to a use or disclosure permitted by this section. Usage Note: Restrictions governed under this regulation meet the definition of an opt out with exception class of consent directive.

HIPAA-Research | HIPAA Research Authorization | HIPAA 45 CFR Â§ 164.508 - Uses and disclosures for which an authorization is required. (a) Standard: Authorizations for uses and disclosures. (3) Compound authorizations. An authorization for use or disclosure of protected health information may not be combined with any other document to create a compound authorization, except as follows: (i) An authorization for the use or disclosure of protected health information for a research study may be combined with any other type of written permission for the same or another research study. This exception includes combining an authorization for the use or disclosure of protected health information for a research study with another authorization for the same research study, with an authorization for the creation or maintenance of a research database or repository, or with a consent to participate in research. Where a covered health care provider has conditioned the provision of research-related treatment on the provision of one of the authorizations, as permitted under paragraph (b)(4)(i) of this section, any compound authorization created under this paragraph must clearly differentiate between the conditioned and unconditioned components and provide the individual with an opportunity to opt in to the research activities described in the unconditioned authorization. Usage Notes: See HHS http://www.hhs.gov/hipaa/for-professionals/special-topics/research/index.html and OCR http://www.hhs.gov/hipaa/for-professionals/special-topics/research/index.html

HIPAA-Self-Pay | HIPAA Self-Pay Restriction | HIPAA 45 CFR Â§ 164.522(a)â€"Right To Request a Restriction of Uses and Disclosures. (vi) A covered entity must agree to the request of an individual to restrict disclosure of protected health information about the individual to a health plan if: (A) The disclosure is for the purpose of carrying out payment or health care operations and is not otherwise required by law; and (B) The protected health information pertains solely to a health care item or service for which the individual, or person other than the health plan on behalf of the individual, has paid the covered entity in full. Usage Note: Restrictions governed under this regulation meet the definition of an opt out with exception class of consent directive. Opt out is limited to disclosures to a payer for payment and operations purpose of use. See HL7 HIPAA Self-Pay code in ActPrivacyLaw (2.16.840.1.113883.1.11.20426).

MDHHS-5515 | Michigan MDHHS-5515 Consent to Share Behavioral Health Information for Care Coordination Purposes | On January 1, 2015, the Michigan Department of Health and Human Services (MDHHS) released a standard consent form for the sharing of health information specific to behavioral health and substance use treatment in accordance with Public Act 129 of 2014. In Michigan, while providers are not required to use this new standard form (MDHHS-5515), they are required to accept it. Note: Form is available at http://www.michigan.gov/documents/mdhhs/Consent_to_Share_Behavioral_Health_Information_for_Care_Coordination_Purposes_548835_7.docx For more information see http://www.michigan.gov/documents/mdhhs/Behavioral_Health_Consent_Form_Background_Information_548864_7.pdf

NYSSIPP | New York State Surgical and Invasive Procedure Protocol | The New York State Surgical and Invasive Procedure Protocol (NYSSIPP) applies to all operative and invasive procedures including endoscopy, general surgery or interventional radiology. Other procedures that involve puncture or incision of the skin, or insertion of an instrument or foreign material into the body are within the scope of the protocol. This protocol also applies to those anesthesia procedures either prior to a surgical procedure or independent of a surgical procedure such as spinal facet blocks. Example: Certain 'minor' procedures such as venipuncture, peripheral IV placement, insertion of nasogastric tube and foley catheter insertion are not within the scope of the protocol. From http://www.health.ny.gov/professionals/protocols_and_guidelines/surgical_and_invasive_procedure/nyssipp_faq.htm Note: HHC 100B-1 Form is available at http://www.downstate.edu/emergency_medicine/documents/Consent_CT_with_contrast.pdf

NPP | notice of privacy practices | Acknowledgement of custodian notice of privacy practices. Usage Notes: This type of consent directive acknowledges a custodian's notice of privacy practices including its permitted collection, access, use and disclosure of health information to users and for purposes of use specified. [ActConsentDirective (2.16.840.1.113883.1.11.20425)]

POLST | POLST | The Physician Order for Life-Sustaining Treatment form records a personâ€™s health care wishes for end of life emergency treatment and translates them into an order by the physician. It must be reviewed and signed by both the patient and the physician, Advanced Registered Nurse Practitioner or Physician Assistant. [2005 Honor My Wishes] Comment: Opt-in Consent Directive with restrictions.

RESEARCH | research information access | Consent to have healthcare information in an electronic health record accessed for research purposes. [VALUE SET: ActConsentType (2.16.840.1.113883.1.11.19897)]

RSDID | de-identified information access | Consent to have de-identified healthcare information in an electronic health record that is accessed for research purposes, but without consent to re-identify the information under any circumstance. [VALUE SET: ActConsentType (2.16.840.1.113883.1.11.19897)

RSREID | re-identifiable information access | Consent to have de-identified healthcare information in an electronic health record that is accessed for research purposes re-identified under specific circumstances outlined in the consent. [VALUE SET: ActConsentType (2.16.840.1.113883.1.11.19897)]

SSA-827 | Form SSA-827 | SSA Form SSA-827 (Authorization to Disclose Information to the Social Security Administration (SSA))and its affiliated State disability determination services use Form SSA-827, Authorization to Disclose Information to the Social Security Administration (SSA) to obtain medical and other information needed to determine whether or not a claimant is disabled. Comment: Opt-in Consent Directive. Note: Form is available at https://www.socialsecurity.gov/forms/ssa-827-inst-sp.pdf

VA-10-0484 | VA Form 10-0484 | VA Form 10-0484 Revocation for Release of Individually-Identifiable Health Information enables a veteran to revoke authorization for the VA to release specified copies of individually-identifiable health information with the non-VA health care provider organizations participating in the eHealth Exchange and partnering with VA. Comment: Opt-in Consent Directive with status = rescinded (aka 'revoked'). Note: Form is available at http://www.va.gov/vaforms/medical/pdf/vha-10-0484-fill.pdf

VA-10-0485 | VA Form 10-0485 | VA Form 10-0485 Request for and Authorization to Release Protected Health Information to eHealth Exchange enables a veteran to request and authorize a VA health care facility to release protected health information (PHI) for treatment purposes only to the communities that are participating in the eHealth Exchange, VLER Directive, and other Health Information Exchanges with who VA has an agreement. This information may consist of the diagnosis of Sickle Cell Anemia, the treatment of or referral for Drug Abuse, treatment of or referral for Alcohol Abuse or the treatment of or testing for infection with Human Immunodeficiency Virus. This authorization covers the diagnoses that I may have upon signing of the authorization and the diagnoses that I may acquire in the future including those protected by 38 U.S.C. 7332. Comment: Opt-in Consent Directive. Note: Form is available at http://www.va.gov/vaforms/medical/pdf/10-0485-fill.pdf

VA-10-5345 | VA Form 10-5345 | VA Form 10-5345 Request for and Authorization to Release Medical Records or Health Information enables a veteran to request and authorize the VA to release specified copies of protected health information (PHI), such as hospital summary or outpatient treatment notes, which may include information about conditions governed under Title 38 Section 7332 (drug abuse, alcoholism or alcohol abuse, testing for or infection with HIV, and sickle cell anemia). Comment: Opt-in Consent Directive. Note: Form is available at http://www.va.gov/vaforms/medical/pdf/vha-10-5345-fill.pdf

VA-10-5345a | VA Form 10-5345a | VA Form 10-5345a Individuals' Request for a Copy of Their Own Health Information enables a veteran to request and authorize the VA to release specified copies of protected health information (PHI), such as hospital summary or outpatient treatment notes. Note: Form is available at http://www.va.gov/vaforms/medical/pdf/vha-10-5345a-fill.pdf

VA-10-5345a-MHV | VA Form 10-5345a-MHV | VA Form 10-5345a-MHV Individualâ€™s Request for a Copy of their own health information from MyHealtheVet enables a veteran to receive a copy of all available personal health information to be delivered through the veteranâ€™s My HealtheVet account. Note: Form is available at http://www.va.gov/vaforms/medical/pdf/vha-10-5345a-MHV-fill.pdf

VA-10-10116 | VA Form 10-10-10116 | VA Form 10-10116 Revocation of Authorization for Use and Release of Individually Identifiable Health Information for Veterans Health Administration Research. Comment: Opt-in with Restriction Consent Directive with status = 'completed'. Note: Form is available at http://www.northerncalifornia.va.gov/northerncalifornia/services/rnd/docs/vha-10-10116.pdf

VA-21-4142 | VA Form 21-4142 | VA Form 21-4142 (Authorization and Consent to Release Information to the Department of Veterans Affairs (VA) enables a veteran to authorize the US Veterans Administration [VA] to request veteranâ€™s health information from non-VA providers. Aka VA Compensation Application Note: Form is available at http://www.vba.va.gov/pubs/forms/VBA-21-4142-ARE.pdf . For additional information regarding VA Form 21-4142, refer to the following website: www.benefits.va.gov/compensation/consent_privateproviders

See the full registry of value sets defined as part of FHIR.

Explanation of the columns that may appear on this page:

Level | A few code lists that FHIR defines are hierarchical - each code is assigned a level. In this scheme, some codes are under other codes, and imply that the code they are under also applies

Source | The source of the definition of the code (when the value set draws in codes defined elsewhere)

Code | The code (used as the code in the resource instance). If the code is in italics, this indicates that the code is not selectable ('Abstract')

Display | The display (used in the display element of a Coding). If there is no display, implementers should not simply display the code, but map the concept into their application

Definition | An explanation of the meaning of the concept

Comments | Additional notes about how to use the code

4.2.12.738 Code System http://hl7.org/fhir/consentaction

URL: https://hl7.org/fhir/STU3/codesystem-consent-action.html

This page is part of the FHIR Specification (v3.0.2: STU 3). The current version which supercedes this version is 4.0.1. For a full list of available versions, see the Directory of published versions

Vocabulary Work Group | Maturity Level: 1 | Informative | Use Context: Not Intended for Production use

This is a code system defined by the FHIR project.

Summary

Defining URL: | http://hl7.org/fhir/consentaction

Name: | Consent Action Codes

Definition: | This value set includes sample Consent Action codes.

Committee: | Community Based Collaborative Care Work Group

OID: | 2.16.840.1.113883.4.642.1.738 (for OID based terminology systems)

Copyright: | This is an example set.

Source Resource | XML / JSON

This Code system is used in the following value sets:

* Consent Action Codes (This value set includes sample Consent Action codes.)

4.2.12.738.1 Content

4.2.12.738.2 Consent Action Codes

This value set includes sample Consent Action codes.

Copyright Statement: This is an example set.

This code system http://hl7.org/fhir/consentaction defines the following codes:

Code | Display | Definition

collect | Collect | Gather/acquire information by an entity to achieve a stated purpose

access | Access | Provide an entity access to information to achieve a stated purpose

use | Use | Use of stored information by an entity fo the stated purpose

disclose | Disclose | Release / transfer of information to an entity

correct | Access and Correct | Allowing an entity to correct a patient's information

See the full registry of value sets defined as part of FHIR.

Explanation of the columns that may appear on this page:

Level | A few code lists that FHIR defines are hierarchical - each code is assigned a level. In this scheme, some codes are under other codes, and imply that the code they are under also applies

Source | The source of the definition of the code (when the value set draws in codes defined elsewhere)

Code | The code (used as the code in the resource instance). If the code is in italics, this indicates that the code is not selectable ('Abstract')

Display | The display (used in the display element of a Coding). If there is no display, implementers should not simply display the code, but map the concept into their application

Definition | An explanation of the meaning of the concept

Comments | Additional notes about how to use the code

4.2.12.740 Code System http://hl7.org/fhir/consent-state-codes

URL: https://hl7.org/fhir/STU3/codesystem-consent-state-codes.html

This page is part of the FHIR Specification (v3.0.2: STU 3). The current version which supercedes this version is 4.0.1. For a full list of available versions, see the Directory of published versions

Vocabulary Work Group | Maturity Level: 1 | Informative | Use Context: Any

This is a code system defined by the FHIR project.

Summary

Defining URL: | http://hl7.org/fhir/consent-state-codes
Name: | ConsentState
Definition: | Indicates the state of the consent
Committee: | Community Based Collaborative Care Work Group
OID: | 2.16.840.1.113883.4.642.1.740 (for OID based terminology systems)
Source Resource | XML / JSON

This Code system is used in the following value sets:

* ConsentState (Indicates the state of the consent)

4.2.12.740.1 Content

4.2.12.740.2 ConsentState

Indicates the state of the consent

This code system http://hl7.org/fhir/consent-state-codes defines the following codes:

Code | Display | Definition
draft | Pending | The consent is in development or awaiting use but is not yet intended to be acted upon.
proposed | Proposed | The consent has been proposed but not yet agreed to by all parties. The negotiation stage.
active | Active | The consent is to be followed and enforced.
rejected | Rejected | The consent has been rejected by one or more of the parties.
inactive | Inactive | The consent is terminated or replaced.
entered-in-error | Entered in Error | The consent was created wrongly (e.g. wrong patient) and should be ignored

See the full registry of value sets defined as part of FHIR.

Explanation of the columns that may appear on this page:

Level | A few code lists that FHIR defines are hierarchical - each code is assigned a level. In this scheme, some codes are under other codes, and imply that the code they are under also applies
Source | The source of the definition of the code (when the value set draws in codes defined elsewhere)
Code | The code (used as the code in the resource instance). If the code is in italics, this indicates that the code is not selectable ('Abstract')
Display | The display (used in the display element of a Coding). If there is no display, implementers should not simply display the code, but map the concept into their application
Definition | An explanation of the meaning of the concept
Comments | Additional notes about how to use the code

4.2.12.742 Code System http://hl7.org/fhir/consent-except-type

URL: https://hl7.org/fhir/STU3/codesystem-consent-except-type.html

This page is part of the FHIR Specification (v3.0.2: STU 3). The current version which supercedes this version is 4.0.1. For a full list of available versions, see the Directory of published versions

Vocabulary Work Group | Maturity Level: 1 | Informative | Use Context: Any

This is a code system defined by the FHIR project.

Summary

Defining URL: | http://hl7.org/fhir/consent-except-type
Name: | ConsentExceptType
Definition: | How an exception statement is applied, such as adding additional consent or removing consent
Committee: | Community Based Collaborative Care Work Group
OID: | 2.16.840.1.113883.4.642.1.742 (for OID based terminology systems)
Source Resource | XML / JSON

This Code system is used in the following value sets:

* ConsentExceptType (How an exception statement is applied, such as adding additional consent or removing consent)

4.2.12.742.1 Content

4.2.12.742.2 ConsentExceptType

How an exception statement is applied, such as adding additional consent or removing consent

This code system http://hl7.org/fhir/consent-except-type defines the following codes:

Code | Display | Definition
deny | Opt Out | Consent is denied for actions meeting these rules
permit | Opt In | Consent is provided for actions meeting these rules

See the full registry of value sets defined as part of FHIR.

Explanation of the columns that may appear on this page:

Level | A few code lists that FHIR defines are hierarchical - each code is assigned a level. In this scheme, some codes are under other codes, and imply that the code they are under also applies
Source | The source of the definition of the code (when the value set draws in codes defined elsewhere)
Code | The code (used as the code in the resource instance). If the code is in italics, this indicates that the code is not selectable ('Abstract')
Display | The display (used in the display element of a Coding). If there is no display, implementers should not simply display the code, but map the concept into their application
Definition | An explanation of the meaning of the concept
Comments | Additional notes about how to use the code

4.2.12.744 Code System http://hl7.org/fhir/consent-data-meaning

URL: https://hl7.org/fhir/STU3/codesystem-consent-data-meaning.html

This page is part of the FHIR Specification (v3.0.2: STU 3). The current version which supercedes this version is 4.0.1. For a full list of available versions, see the Directory of published versions

Vocabulary Work Group | Maturity Level: 1 | Informative | Use Context: Any

This is a code system defined by the FHIR project.

Summary

Defining URL: | http://hl7.org/fhir/consent-data-meaning
Name: | ConsentDataMeaning
Definition: | How a resource reference is interpreted when testing consent restrictions
Committee: | Community Based Collaborative Care Work Group
OID: | 2.16.840.1.113883.4.642.1.744 (for OID based terminology systems)
Source Resource | XML / JSON

This Code system is used in the following value sets:

* ConsentDataMeaning (How a resource reference is interpreted when testing consent restrictions)

4.2.12.744.1 Content

4.2.12.744.2 ConsentDataMeaning

How a resource reference is interpreted when testing consent restrictions

This code system http://hl7.org/fhir/consent-data-meaning defines the following codes:

Code | Display | Definition
instance | Instance | The consent applies directly to the instance of the resource
related | Related | The consent applies directly to the instance of the resource and instances it refers to
dependents | Dependents | The consent applies directly to the instance of the resource and instances that refer to it
authoredby | AuthoredBy | The consent applies to instances of resources that are authored by

See the full registry of value sets defined as part of FHIR.

Explanation of the columns that may appear on this page:

Level | A few code lists that FHIR defines are hierarchical - each code is assigned a level. In this scheme, some codes are under other codes, and imply that the code they are under also applies
Source | The source of the definition of the code (when the value set draws in codes defined elsewhere)
Code | The code (used as the code in the resource instance). If the code is in italics, this indicates that the code is not selectable ('Abstract')
Display | The display (used in the display element of a Coding). If there is no display, implementers should not simply display the code, but map the concept into their application
Definition | An explanation of the meaning of the concept
Comments | Additional notes about how to use the code

4.2.12.748 Code System http://hl7.org/fhir/library-type

URL: https://hl7.org/fhir/STU3/codesystem-library-type.html

This page is part of the FHIR Specification (v3.0.2: STU 3). The current version which supercedes this version is 4.0.1. For a full list of available versions, see the Directory of published versions

Vocabulary Work Group | Maturity Level: 2 | Informative | Use Context: Any

This is a code system defined by the FHIR project.

Summary

Defining URL: | http://hl7.org/fhir/library-type
Name: | LibraryType
Definition: | The type of knowledge asset this library contains
Committee: | Clinical Decision Support Work Group
OID: | 2.16.840.1.113883.4.642.1.748 (for OID based terminology systems)
Source Resource | XML / JSON

This Code system is used in the following value sets:

* LibraryType (The type of knowledge asset this library contains)

4.2.12.748.1 Content

4.2.12.748.2 LibraryType

The type of knowledge asset this library contains

This code system http://hl7.org/fhir/library-type defines the following codes:

Code | Display | Definition
logic-library | Logic Library | The resource is a shareable library of formalized knowledge
model-definition | Model Definition | The resource is a definition of an information model
asset-collection | Asset Collection | The resource is a collection of knowledge assets
module-definition | Module Definition | The resource defines the dependencies, parameters, and data requirements for a particular module or evaluation context

See the full registry of value sets defined as part of FHIR.

Explanation of the columns that may appear on this page:

Level | A few code lists that FHIR defines are hierarchical - each code is assigned a level. In this scheme, some codes are under other codes, and imply that the code they are under also applies
Source | The source of the definition of the code (when the value set draws in codes defined elsewhere)
Code | The code (used as the code in the resource instance). If the code is in italics, this indicates that the code is not selectable ('Abstract')
Display | The display (used in the display element of a Coding). If there is no display, implementers should not simply display the code, but map the concept into their application
Definition | An explanation of the meaning of the concept
Comments | Additional notes about how to use the code

4.2.12.750 Code System http://hl7.org/fhir/measure-population

URL: https://hl7.org/fhir/STU3/codesystem-measure-population.html

This page is part of the FHIR Specification (v3.0.2: STU 3). The current version which supercedes this version is 4.0.1. For a full list of available versions, see the Directory of published versions

Vocabulary Work Group | Maturity Level: 2 | Informative | Use Context: Any

This is a code system defined by the FHIR project.

Summary

Defining URL: | http://hl7.org/fhir/measure-population
Name: | MeasurePopulationType
Definition: | The type of population
Committee: | Clinical Quality Information Work Group
OID: | 2.16.840.1.113883.4.642.1.750 (for OID based terminology systems)
Source Resource | XML / JSON

This Code system is used in the following value sets:

* MeasurePopulationType (The type of population)

4.2.12.750.1 Content

4.2.12.750.2 MeasurePopulationType

The type of population

This code system http://hl7.org/fhir/measure-population defines the following codes:

Code | Display | Definition
initial-population | Initial Population | The initial population refers to all patients or events to be evaluated by a quality measure involving patients who share a common set of specified characterstics. All patients or events counted (for example, as numerator, as denominator) are drawn from the initial population
numerator | Numerator | The upper portion of a fraction used to calculate a rate, proportion, or ratio. Also called the measure focus, it is the target process, condition, event, or outcome. Numerator criteria are the processes or outcomes expected for each patient, or event defined in the denominator. A numerator statement describes the clinical action that satisfies the conditions of the measure
numerator-exclusion | Numerator Exclusion | Numerator exclusion criteria define patients or events to be removed from the numerator. Numerator exclusions are used in proportion and ratio measures to help narrow the numerator (for inverted measures)
denominator | Denominator | The lower portion of a fraction used to calculate a rate, proportion, or ratio. The denominator can be the same as the initial population, or a subset of the initial population to further constrain the population for the purpose of the measure
denominator-exclusion | Denominator Exclusion | Denominator exclusion criteria define patients or events that should be removed from the denominator before determining if numerator criteria are met. Denominator exclusions are used in proportion and ratio measures to help narrow the denominator. For example, patients with bilateral lower extremity amputations would be listed as a denominator exclusion for a measure requiring foot exams
denominator-exception | Denominator Exception | Denominator exceptions are conditions that should remove a patient or event from the denominator of a measure only if the numerator criteria are not met. Denominator exception allows for adjustment of the calculated score for those providers with higher risk populations. Denominator exception criteria are only used in proportion measures
measure-population | Measure Population | Measure population criteria define the patients or events for which the individual observation for the measure should be taken. Measure populations are used for continuous variable measures rather than numerator and denominator criteria

measure-population-exclusion | Measure Population Exclusion | Measure population criteria define the patients or events that should be removed from the measure population before determining the outcome of one or more continuous variables defined for the measure observation. Measure population exclusion criteria are used within continuous variable measures to help narrow the measure population
measure-observation | Measure Observation | Defines the individual observation to be performed for each patient or event in the measure population. Measure observations for each case in the population are aggregated to determine the overall measure score for the population

See the full registry of value sets defined as part of FHIR.

Explanation of the columns that may appear on this page:

Level | A few code lists that FHIR defines are hierarchical - each code is assigned a level. In this scheme, some codes are under other codes, and imply that the code they are under also applies
Source | The source of the definition of the code (when the value set draws in codes defined elsewhere)
Code | The code (used as the code in the resource instance). If the code is in italics, this indicates that the code is not selectable ('Abstract')
Display | The display (used in the display element of a Coding). If there is no display, implementers should not simply display the code, but map the concept into their application
Definition | An explanation of the meaning of the concept
Comments | Additional notes about how to use the code

4.2.12.752 Code System http://hl7.org/fhir/measure-scoring

URL: https://hl7.org/fhir/STU3/codesystem-measure-scoring.html

This page is part of the FHIR Specification (v3.0.2: STU 3). The current version which supercedes this version is 4.0.1. For a full list of available versions, see the Directory of published versions

Vocabulary Work Group | Maturity Level: 2 | Informative | Use Context: Any

This is a code system defined by the FHIR project.

Summary

Defining URL: | http://hl7.org/fhir/measure-scoring
Name: | MeasureScoring
Definition: | The scoring type of the measure
Committee: | Clinical Quality Information Work Group
OID: | 2.16.840.1.113883.4.642.1.752 (for OID based terminology systems)
Source Resource | XML / JSON

This Code system is used in the following value sets:

* MeasureScoring (The scoring type of the measure)

4.2.12.752.1 Content

4.2.12.752.2 MeasureScoring

The scoring type of the measure

This code system http://hl7.org/fhir/measure-scoring defines the following codes:

Code | Display | Definition
proportion | Proportion | The measure score is defined using a proportion
ratio | Ratio | The measure score is defined using a ratio
continuous-variable | Continuous Variable | The score is defined by a calculation of some quantity
cohort | Cohort | The measure is a cohort definition

See the full registry of value sets defined as part of FHIR.

Explanation of the columns that may appear on this page:

Level | A few code lists that FHIR defines are hierarchical - each code is assigned a level. In this scheme, some codes are under other codes, and imply that the code they are under also applies
Source | The source of the definition of the code (when the value set draws in codes defined elsewhere)
Code | The code (used as the code in the resource instance). If the code is in italics, this indicates that the code is not selectable ('Abstract')
Display | The display (used in the display element of a Coding). If there is no display, implementers should not simply display the code, but map the concept into their application
Definition | An explanation of the meaning of the concept
Comments | Additional notes about how to use the code

4.2.12.754 Code System http://hl7.org/fhir/measure-type

URL: https://hl7.org/fhir/STU3/codesystem-measure-type.html

This page is part of the FHIR Specification (v3.0.2: STU 3). The current version which supercedes this version is 4.0.1. For a full list of available versions, see the Directory of published versions

Vocabulary Work Group | Maturity Level: 2 | Informative | Use Context: Any

This is a code system defined by the FHIR project.

Summary

Defining URL: | http://hl7.org/fhir/measure-type
Name: | MeasureType
Definition: | The type of measure (includes codes from 2.16.840.1.113883.1.11.20368)

Committee: | Clinical Quality Information Work Group
OID: | 2.16.840.1.113883.4.642.1.754 (for OID based terminology systems)
Source Resource | XML / JSON

This Code system is used in the following value sets:

* MeasureType (The type of measure (includes codes from 2.16.840.1.113883.1.11.20368))

4.2.12.754.1 Content

4.2.12.754.2 MeasureType

The type of measure (includes codes from 2.16.840.1.113883.1.11.20368)

This code system http://hl7.org/fhir/measure-type defines the following codes:

Code | Display | Definition
process | Process | A measure which focuses on a process which leads to a certain outcome, meaning that a scientific basis exists for believing that the process, when executed well, will increase the probability of achieving a desired outcome
outcome | Outcome | A measure that indicates the result of the performance (or non-performance) of a function or process
structure | Structure | A measure that focuses on a health care provider's capacity, systems, and processes to provide high-quality care
patient-reported-outcome | Patient Reported Outcome | A measure that focuses on patient-reported information such as patient engagement or patient experience measures
composite | Composite | A measure that combines multiple component measures in to a single quality measure

See the full registry of value sets defined as part of FHIR.

Explanation of the columns that may appear on this page:

Level | A few code lists that FHIR defines are hierarchical - each code is assigned a level. In this scheme, some codes are under other codes, and imply that the code they are under also applies
Source | The source of the definition of the code (when the value set draws in codes defined elsewhere)
Code | The code (used as the code in the resource instance). If the code is in italics, this indicates that the code is not selectable ('Abstract')
Display | The display (used in the display element of a Coding). If there is no display, implementers should not simply display the code, but map the concept into their application
Definition | An explanation of the meaning of the concept
Comments | Additional notes about how to use the code

4.2.12.756 Code System http://hl7.org/fhir/measure-data-usage

URL: https://hl7.org/fhir/STU3/codesystem-measure-data-usage.html

This page is part of the FHIR Specification (v3.0.2: STU 3). The current version which supercedes this version is 4.0.1. For a full list of available versions, see the Directory of published versions

Vocabulary Work Group | Maturity Level: 2 | Informative | Use Context: Any

This is a code system defined by the FHIR project.

Summary

Defining URL: | http://hl7.org/fhir/measure-data-usage
Name: | MeasureDataUsage
Definition: | The intended usage for supplemental data elements in the measure
Committee: | Clinical Quality Information Work Group
OID: | 2.16.840.1.113883.4.642.1.756 (for OID based terminology systems)
Source Resource | XML / JSON

This Code system is used in the following value sets:

* MeasureDataUsage (The intended usage for supplemental data elements in the measure)

4.2.12.756.1 Content

4.2.12.756.2 MeasureDataUsage

The intended usage for supplemental data elements in the measure

This code system http://hl7.org/fhir/measure-data-usage defines the following codes:

Code | Display | Definition
supplemental-data | Supplemental Data | The data is intended to be provided as additional information alongside the measure results
risk-adjustment-factor | Risk Adjustment Factor | The data is intended to be used to calculate and apply a risk adjustment model for the measure

See the full registry of value sets defined as part of FHIR.

Explanation of the columns that may appear on this page:

Level | A few code lists that FHIR defines are hierarchical - each code is assigned a level. In this scheme, some codes are under other codes, and imply that the code they are under also applies
Source | The source of the definition of the code (when the value set draws in codes defined elsewhere)
Code | The code (used as the code in the resource instance). If the code is in italics, this indicates that the code is not selectable ('Abstract')
Display | The display (used in the display element of a Coding). If there is no display, implementers should not simply display the code, but map the concept into their application
Definition | An explanation of the meaning of the concept

Comments | Additional notes about how to use the code

4.2.12.758 Code System http://hl7.org/fhir/composite-measure-scoring

URL: https://hl7.org/fhir/STU3/codesystem-composite-measure-scoring.html

This page is part of the FHIR Specification (v3.0.2: STU 3). The current version which supercedes this version is 4.0.1. For a full list of available versions, see the Directory of published versions

Vocabulary Work Group | Maturity Level: 2 | Informative | Use Context: Any

This is a code system defined by the FHIR project.

Summary

Defining URL: | http://hl7.org/fhir/composite-measure-scoring
Name: | CompositeMeasureScoring
Definition: | The composite scoring method of the measure
Committee: | Clinical Quality Information Work Group
OID: | 2.16.840.1.113883.4.642.1.758 (for OID based terminology systems)
Source Resource | XML / JSON

This Code system is used in the following value sets:

* CompositeMeasureScoring (The composite scoring method of the measure)

4.2.12.758.1 Content

4.2.12.758.2 CompositeMeasureScoring

The composite scoring method of the measure

This code system http://hl7.org/fhir/composite-measure-scoring defines the following codes:

Code | Display | Definition
opportunity | Opportunity | Opportunity scoring combines the scores from component measures by combining the numerators and denominators for each component
all-or-nothing | All-or-nothing | All-or-nothing scoring includes an individual in the numerator of the composite measure if they are in the numerators of all of the component measures in which they are in the denominator
linear | Linear | Linear scoring gives an individual a score based on the number of numerators in which they appear
weighted | Weighted | Weighted scoring gives an individual a score based on a weighted factor for each component numerator in which they appear

See the full registry of value sets defined as part of FHIR.

Explanation of the columns that may appear on this page:

Level | A few code lists that FHIR defines are hierarchical - each code is assigned a level. In this scheme, some codes are under other codes, and imply that the code they are under also applies
Source | The source of the definition of the code (when the value set draws in codes defined elsewhere)
Code | The code (used as the code in the resource instance). If the code is in italics, this indicates that the code is not selectable ('Abstract')
Display | The display (used in the display element of a Coding). If there is no display, implementers should not simply display the code, but map the concept into their application
Definition | An explanation of the meaning of the concept
Comments | Additional notes about how to use the code

4.2.12.760 Code System http://hl7.org/fhir/measure-report-status

URL: https://hl7.org/fhir/STU3/codesystem-measure-report-status.html

This page is part of the FHIR Specification (v3.0.2: STU 3). The current version which supercedes this version is 4.0.1. For a full list of available versions, see the Directory of published versions

Vocabulary Work Group | Maturity Level: 2 | Informative | Use Context: Any

This is a code system defined by the FHIR project.

Summary

Defining URL: | http://hl7.org/fhir/measure-report-status
Name: | MeasureReportStatus
Definition: | The status of the measure report
Committee: | Clinical Quality Information Work Group
OID: | 2.16.840.1.113883.4.642.1.760 (for OID based terminology systems)
Source Resource | XML / JSON

This Code system is used in the following value sets:

* MeasureReportStatus (The status of the measure report)

4.2.12.760.1 Content

4.2.12.760.2 MeasureReportStatus

The status of the measure report

This code system http://hl7.org/fhir/measure-report-status defines the following codes:

Code | Display | Definition
complete | Complete | The report is complete and ready for use
pending | Pending | The report is currently being generated
error | Error | An error occurred attempting to generate the report

See the full registry of value sets defined as part of FHIR.

Explanation of the columns that may appear on this page:

Level | A few code lists that FHIR defines are hierarchical - each code is assigned a level. In this scheme, some codes are under other codes, and imply that the code they are under also applies
Source | The source of the definition of the code (when the value set draws in codes defined elsewhere)
Code | The code (used as the code in the resource instance). If the code is in italics, this indicates that the code is not selectable ('Abstract')
Display | The display (used in the display element of a Coding). If there is no display, implementers should not simply display the code, but map the concept into their application
Definition | An explanation of the meaning of the concept
Comments | Additional notes about how to use the code

4.2.12.762 Code System http://hl7.org/fhir/measure-report-type

URL: https://hl7.org/fhir/STU3/codesystem-measure-report-type.html

This page is part of the FHIR Specification (v3.0.2: STU 3). The current version which supercedes this version is 4.0.1. For a full list of available versions, see the Directory of published versions

Vocabulary Work Group | Maturity Level: 2 | Informative | Use Context: Any

This is a code system defined by the FHIR project.

Summary

Defining URL: | http://hl7.org/fhir/measure-report-type
Name: | MeasureReportType
Definition: | The type of the measure report
Committee: | Clinical Quality Information Work Group
OID: | 2.16.840.1.113883.4.642.1.762 (for OID based terminology systems)
Source Resource | XML / JSON

This Code system is used in the following value sets:

* MeasureReportType (The type of the measure report)

4.2.12.762.1 Content

4.2.12.762.2 MeasureReportType

The type of the measure report

This code system http://hl7.org/fhir/measure-report-type defines the following codes:

Code | Display | Definition
individual | Individual | An individual report that provides information on the performance for a given measure with respect to a single patient
patient-list | Patient List | A patient list report that includes a listing of patients that satisfied each population criteria in the measure
summary | Summary | A summary report that returns the number of patients in each population criteria for the measure

See the full registry of value sets defined as part of FHIR.

Explanation of the columns that may appear on this page:

Level | A few code lists that FHIR defines are hierarchical - each code is assigned a level. In this scheme, some codes are under other codes, and imply that the code they are under also applies
Source | The source of the definition of the code (when the value set draws in codes defined elsewhere)
Code | The code (used as the code in the resource instance). If the code is in italics, this indicates that the code is not selectable ('Abstract')
Display | The display (used in the display element of a Coding). If there is no display, implementers should not simply display the code, but map the concept into their application
Definition | An explanation of the meaning of the concept
Comments | Additional notes about how to use the code

4.2.12.764 Code System http://hl7.org/fhir/concept-property-type

URL: https://hl7.org/fhir/STU3/codesystem-concept-property-type.html

This page is part of the FHIR Specification (v3.0.2: STU 3). The current version which supercedes this version is 4.0.1. For a full list of available versions, see the Directory of published versions

Vocabulary Work Group | Maturity Level: 5 | Informative | Use Context: Any

This is a code system defined by the FHIR project.

Summary

Defining URL: | http://hl7.org/fhir/concept-property-type
Name: | PropertyType
Definition: | The type of a property value
Committee: | Vocabulary Work Group

OID: | 2.16.840.1.113883.4.642.1.764 (for OID based terminology systems)
Source Resource | XML / JSON

This Code system is used in the following value sets:

* PropertyType (The type of a property value)

4.2.12.764.1 Content

4.2.12.764.2 PropertyType

The type of a property value

This code system http://hl7.org/fhir/concept-property-type defines the following codes:

Code | Display | Definition
code | code (internal reference) | The property value is a code that identifies a concept defined in the code system
Coding | Coding (external reference) | The property value is a code defined in an external code system. This may be used for translations, but is not the intent
string | string | The property value is a string
integer | integer | The property value is a string (often used to assign ranking values to concepts for supporting score assessments)
boolean | boolean | The property value is a boolean true | false
dateTime | dateTime | The property is a date or a date + time

See the full registry of value sets defined as part of FHIR.

Explanation of the columns that may appear on this page:

Level | A few code lists that FHIR defines are hierarchical - each code is assigned a level. In this scheme, some codes are under other codes, and imply that the code they are under also applies
Source | The source of the definition of the code (when the value set draws in codes defined elsewhere)
Code | The code (used as the code in the resource instance). If the code is in italics, this indicates that the code is not selectable ('Abstract')
Display | The display (used in the display element of a Coding). If there is no display, implementers should not simply display the code, but map the concept into their application
Definition | An explanation of the meaning of the concept
Comments | Additional notes about how to use the code

4.2.12.766 Code System http://hl7.org/fhir/codesystem-content-mode

URL: https://hl7.org/fhir/STU3/codesystem-codesystem-content-mode.html

This page is part of the FHIR Specification (v3.0.2: STU 3). The current version which supercedes this version is 4.0.1. For a full list of available versions, see the Directory of published versions

Vocabulary Work Group | Maturity Level: 5 | Informative | Use Context: Any

This is a code system defined by the FHIR project.

Summary

Defining URL: | http://hl7.org/fhir/codesystem-content-mode
Name: | CodeSystemContentMode
Definition: | How much of the content of the code system - the concepts and codes it defines - are represented in a code system resource
Committee: | Vocabulary Work Group
OID: | 2.16.840.1.113883.4.642.1.766 (for OID based terminology systems)
Source Resource | XML / JSON

This Code system is used in the following value sets:

* CodeSystemContentMode (How much of the content of the code system - the concepts and codes it defines - are represented in a code system resource)

4.2.12.766.1 Content

4.2.12.766.2 CodeSystemContentMode

How much of the content of the code system - the concepts and codes it defines - are represented in a code system resource

This code system http://hl7.org/fhir/codesystem-content-mode defines the following codes:

Code | Display | Definition
not-present | Not Present | None of the concepts defined by the code system are included in the code system resource
example | Example | A few representative concepts are included in the code system resource
fragment | Fragment | A subset of the code system concepts are included in the code system resource
complete | Complete | All the concepts defined by the code system are included in the code system resource

See the full registry of value sets defined as part of FHIR.

Explanation of the columns that may appear on this page:

Level | A few code lists that FHIR defines are hierarchical - each code is assigned a level. In this scheme, some codes are under other codes, and imply that the code they are under also applies
Source | The source of the definition of the code (when the value set draws in codes defined elsewhere)
Code | The code (used as the code in the resource instance). If the code is in italics, this indicates that the code is not selectable ('Abstract')

Display | The display (used in the display element of a Coding). If there is no display, implementers should not simply display the code, but map the concept into their application
Definition | An explanation of the meaning of the concept
Comments | Additional notes about how to use the code

4.2.12.768 Code System http://hl7.org/fhir/codesystem-hierarchy-meaning

URL: https://hl7.org/fhir/STU3/codesystem-codesystem-hierarchy-meaning.html

This page is part of the FHIR Specification (v3.0.2: STU 3). The current version which supercedes this version is 4.0.1. For a full list of available versions, see the Directory of published versions

Vocabulary Work Group | Maturity Level: 5 | Informative | Use Context: Any

This is a code system defined by the FHIR project.

Summary

Defining URL: | http://hl7.org/fhir/codesystem-hierarchy-meaning
Name: | CodeSystemHierarchyMeaning
Definition: | The meaning of the hierarchy of concepts in a code system
Committee: | Vocabulary Work Group
OID: | 2.16.840.1.113883.4.642.1.768 (for OID based terminology systems)
Source Resource | XML / JSON

This Code system is used in the following value sets:

* CodeSystemHierarchyMeaning (The meaning of the hierarchy of concepts in a code system)

4.2.12.768.1 Content

4.2.12.768.2 CodeSystemHierarchyMeaning

The meaning of the hierarchy of concepts in a code system

This code system http://hl7.org/fhir/codesystem-hierarchy-meaning defines the following codes:

Code | Display | Definition
grouped-by | Grouped By | No particular relationship between the concepts can be assumed, except what can be determined by inspection of the definitions of the elements (possible reasons to use this: importing from a source where this is not defined, or where various parts of the hierarchy have different meanings)
is-a | Is-A | A hierarchy where the child concepts have an IS-A relationship with the parents - that is, all the properties of the parent are also true for its child concepts
part-of | Part Of | Child elements list the individual parts of a composite whole (e.g. body site)
classified-with | Classified With | Child concepts in the hierarchy may have only one parent, and there is a presumption that the code system is a "closed world" meaning all things must be in the hierarchy. This results in concepts such as "not otherwise classified."

See the full registry of value sets defined as part of FHIR.

Explanation of the columns that may appear on this page:

Level | A few code lists that FHIR defines are hierarchical - each code is assigned a level. In this scheme, some codes are under other codes, and imply that the code they are under also applies
Source | The source of the definition of the code (when the value set draws in codes defined elsewhere)
Code | The code (used as the code in the resource instance). If the code is in italics, this indicates that the code is not selectable ('Abstract')
Display | The display (used in the display element of a Coding). If there is no display, implementers should not simply display the code, but map the concept into their application
Definition | An explanation of the meaning of the concept
Comments | Additional notes about how to use the code

4.2.12.770 Code System http://hl7.org/fhir/compartment-type

URL: https://hl7.org/fhir/STU3/codesystem-compartment-type.html

This page is part of the FHIR Specification (v3.0.2: STU 3). The current version which supercedes this version is 4.0.1. For a full list of available versions, see the Directory of published versions

Vocabulary Work Group | Maturity Level: 1 | Informative | Use Context: Any

This is a code system defined by the FHIR project.

Summary

Defining URL: | http://hl7.org/fhir/compartment-type
Name: | CompartmentType
Definition: | Which compartment a compartment definition describes
Committee: | FHIR Infrastructure Work Group
OID: | 2.16.840.1.113883.4.642.1.770 (for OID based terminology systems)
Source Resource | XML / JSON

This Code system is used in the following value sets:

* CompartmentType (Which compartment a compartment definition describes)

4.2.12.770.1 Content

4.2.12.770.2 CompartmentType

Which compartment a compartment definition describes

This code system http://hl7.org/fhir/compartment-type defines the following codes:

Code | Display | Definition
Patient | Patient | The compartment definition is for the patient compartment
Encounter | Encounter | The compartment definition is for the encounter compartment
RelatedPerson | RelatedPerson | The compartment definition is for the related-person compartment
Practitioner | Practitioner | The compartment definition is for the practitioner compartment
Device | Device | The compartment definition is for the device compartment

See the full registry of value sets defined as part of FHIR.

Explanation of the columns that may appear on this page:

Level | A few code lists that FHIR defines are hierarchical - each code is assigned a level. In this scheme, some codes are under other codes, and imply that the code they are under also applies
Source | The source of the definition of the code (when the value set draws in codes defined elsewhere)
Code | The code (used as the code in the resource instance). If the code is in italics, this indicates that the code is not selectable ('Abstract')
Display | The display (used in the display element of a Coding). If there is no display, implementers should not simply display the code, but map the concept into their application
Definition | An explanation of the meaning of the concept
Comments | Additional notes about how to use the code

4.2.12.772 Code System http://hl7.org/fhir/task-performer-type

URL: https://hl7.org/fhir/STU3/codesystem-task-performer-type.html

This page is part of the FHIR Specification (v3.0.2: STU 3). The current version which supercedes this version is 4.0.1. For a full list of available versions, see the Directory of published versions

Vocabulary Work Group | Maturity Level: 2 | Informative | Use Context: Any

This is a code system defined by the FHIR project.

Summary

Defining URL: | http://hl7.org/fhir/task-performer-type
Name: | TaskPerformerType
Definition: | The type(s) of task performers allowed
Committee: | Orders and Observations Work Group
OID: | 2.16.840.1.113883.4.642.1.772 (for OID based terminology systems)
Source Resource | XML / JSON

This Code system is used in the following value sets:

* TaskPerformerType (The type(s) of task performers allowed)

4.2.12.772.1 Content

4.2.12.772.2 TaskPerformerType

The type(s) of task performers allowed

This code system http://hl7.org/fhir/task-performer-type defines the following codes:

Lvl | Code | Display | Definition
1 | requester | Requester | A workflow participant that requests services.
1 | dispatcher | Dispatcher | A workflow participant that dispatches services (assigns another task to a participant).
2 | scheduler | Scheduler | A workflow participant that schedules (dispatches and sets the time or date for performance of) services.
1 | performer | Performer | A workflow participant that performs services.
1 | monitor | Monitor | A workflow participant that monitors task activity.
1 | manager | Manager | A workflow participant that manages task activity.
1 | acquirer | Acquirer | A workflow participant that acquires resources (specimens, images, etc) necessary to perform the task.
1 | reviewer | Reviewer | A workflow participant that reviews task inputs or outputs.

See the full registry of value sets defined as part of FHIR.

Explanation of the columns that may appear on this page:

Level | A few code lists that FHIR defines are hierarchical - each code is assigned a level. In this scheme, some codes are under other codes, and imply that the code they are under also applies
Source | The source of the definition of the code (when the value set draws in codes defined elsewhere)
Code | The code (used as the code in the resource instance). If the code is in italics, this indicates that the code is not selectable ('Abstract')
Display | The display (used in the display element of a Coding). If there is no display, implementers should not simply display the code, but map the concept into their application
Definition | An explanation of the meaning of the concept
Comments | Additional notes about how to use the code

4.2.12.774 Code System http://hl7.org/fhir/task-status

URL: https://hl7.org/fhir/STU3/codesystem-task-status.html

This page is part of the FHIR Specification (v3.0.2: STU 3). The current version which supercedes this version is 4.0.1. For a full list of available versions, see the Directory of published versions

Vocabulary Work Group | Maturity Level: 2 | Informative | Use Context: Any

This is a code system defined by the FHIR project.

Summary

Defining URL: | http://hl7.org/fhir/task-status
Name: | TaskStatus
Definition: | The current status of the task.
Committee: | Orders and Observations Work Group
OID: | 2.16.840.1.113883.4.642.1.774 (for OID based terminology systems)
Source Resource | XML / JSON

This Code system is used in the following value sets:

* TaskStatus (The current status of the task.)

4.2.12.774.1 Content

4.2.12.774.2 TaskStatus

The current status of the task.

This code system http://hl7.org/fhir/task-status defines the following codes:

Code | Display | Definition
draft | Draft | The task is not yet ready to be acted upon.
requested | Requested | The task is ready to be acted upon and action is sought.
received | Received | A potential performer has claimed ownership of the task and is evaluating whether to perform it.
accepted | Accepted | The potential performer has agreed to execute the task but has not yet started work.
rejected | Rejected | The potential performer who claimed ownership of the task has decided not to execute it prior to performing any action.
ready | Ready | Task is ready to be performed, but no action has yet been taken. Used in place of requested/received/accepted/rejected when request assignment and acceptance is a given.
cancelled | Cancelled | The task was not completed.
in-progress | In Progress | Task has been started but is not yet complete.
on-hold | On Hold | Task has been started but work has been paused.
failed | Failed | The task was attempted but could not be completed due to some error.
completed | Completed | The task has been completed.
entered-in-error | Entered in Error | The task should never have existed and is retained only because of the possibility it may have used.

See the full registry of value sets defined as part of FHIR.

Explanation of the columns that may appear on this page:

Level | A few code lists that FHIR defines are hierarchical - each code is assigned a level. In this scheme, some codes are under other codes, and imply that the code they are under also applies
Source | The source of the definition of the code (when the value set draws in codes defined elsewhere)
Code | The code (used as the code in the resource instance). If the code is in italics, this indicates that the code is not selectable ('Abstract')
Display | The display (used in the display element of a Coding). If there is no display, implementers should not simply display the code, but map the concept into their application
Definition | An explanation of the meaning of the concept
Comments | Additional notes about how to use the code

4.2.12.776 Code System http://hl7.org/fhir/activity-definition-category

URL: https://hl7.org/fhir/STU3/codesystem-activity-definition-category.html

This page is part of the FHIR Specification (v3.0.2: STU 3). The current version which supercedes this version is 4.0.1. For a full list of available versions, see the Directory of published versions

Vocabulary Work Group | Maturity Level: 0 | Informative | Use Context: Any

This is a code system defined by the FHIR project.

Summary

Defining URL: | http://hl7.org/fhir/activity-definition-category
Name: | ActivityDefinitionCategory
Definition: | High-level categorization of the type of activity
Committee: | Clinical Decision Support Work Group
OID: | 2.16.840.1.113883.4.642.1.776 (for OID based terminology systems)
Source Resource | XML / JSON

This Code system is used in the following value sets:

* ActivityDefinitionCategory (High-level categorization of the type of activity)

4.2.12.776.1 Content

4.2.12.776.2 ActivityDefinitionCategory

High-level categorization of the type of activity

This code system http://hl7.org/fhir/activity-definition-category defines the following codes:

Code | Display | Definition
treatment | Treatment | The activity is intended to provide or is related to treatment of the patient
education | Education | The activity is intended to provide or is related to education of the patient
assessment | Assessment | The activity is intended to perform or is related to assessment of the patient

See the full registry of value sets defined as part of FHIR.

Explanation of the columns that may appear on this page:

Level | A few code lists that FHIR defines are hierarchical - each code is assigned a level. In this scheme, some codes are under other codes, and imply that the code they are under also applies
Source | The source of the definition of the code (when the value set draws in codes defined elsewhere)
Code | The code (used as the code in the resource instance). If the code is in italics, this indicates that the code is not selectable ('Abstract')
Display | The display (used in the display element of a Coding). If there is no display, implementers should not simply display the code, but map the concept into their application
Definition | An explanation of the meaning of the concept
Comments | Additional notes about how to use the code

4.2.12.778 Code System http://hl7.org/fhir/definition-topic

URL: https://hl7.org/fhir/STU3/codesystem-definition-topic.html

This page is part of the FHIR Specification (v3.0.2: STU 3). The current version which supercedes this version is 4.0.1. For a full list of available versions, see the Directory of published versions

Vocabulary Work Group | Maturity Level: 1 | Informative | Use Context: Any

This is a code system defined by the FHIR project.

Summary

Defining URL: | http://hl7.org/fhir/definition-topic
Name: | DefinitionTopic
Definition: | High-level categorization of the definition, used for searching, sorting, and filtering
Committee: | Clinical Decision Support Work Group
OID: | 2.16.840.1.113883.4.642.1.778 (for OID based terminology systems)
Source Resource | XML / JSON

This Code system is used in the following value sets:

* DefinitionTopic (High-level categorization of the definition, used for searching, sorting, and filtering)

4.2.12.778.1 Content

4.2.12.778.2 DefinitionTopic

High-level categorization of the definition, used for searching, sorting, and filtering

This code system http://hl7.org/fhir/definition-topic defines the following codes:

Code | Display | Definition
treatment | Treatment | The definition is related to treatment of the patient
education | Education | The definition is related to education of the patient
assessment | Assessment | The definition is related to assessment of the patient

See the full registry of value sets defined as part of FHIR.

Explanation of the columns that may appear on this page:

Level | A few code lists that FHIR defines are hierarchical - each code is assigned a level. In this scheme, some codes are under other codes, and imply that the code they are under also applies
Source | The source of the definition of the code (when the value set draws in codes defined elsewhere)
Code | The code (used as the code in the resource instance). If the code is in italics, this indicates that the code is not selectable ('Abstract')
Display | The display (used in the display element of a Coding). If there is no display, implementers should not simply display the code, but map the concept into their application
Definition | An explanation of the meaning of the concept
Comments | Additional notes about how to use the code

4.2.12.781 Code System http://hl7.org/fhir/plan-definition-type

URL: https://hl7.org/fhir/STU3/codesystem-plan-definition-type.html

This page is part of the FHIR Specification (v3.0.2: STU 3). The current version which supercedes this version is 4.0.1. For a full list of available versions, see the Directory of published versions

Vocabulary Work Group | Maturity Level: 2 | Informative | Use Context: Any

This is a code system defined by the FHIR project.

Summary

Defining URL: | http://hl7.org/fhir/plan-definition-type
Name: | PlanDefinitionType

Definition: | The type of PlanDefinition
Committee: | Clinical Decision Support Work Group
OID: | 2.16.840.1.113883.4.642.1.781 (for OID based terminology systems)
Source Resource | XML / JSON

This Code system is used in the following value sets:

* PlanDefinitionType (The type of PlanDefinition)

4.2.12.781.1 Content

4.2.12.781.2 PlanDefinitionType

The type of PlanDefinition

This code system http://hl7.org/fhir/plan-definition-type defines the following codes:

Code | Display | Definition
order-set | Order Set | A pre-defined and approved group of orders related to a particular clinical condition (e.g. hypertension treatment and monitoring) or stage of care (e.g. hospital admission to Coronary Care Unit). An order set is used as a checklist for the clinician when managing a patient with a specific condition. It is a structured collection of orders relevant to that condition and presented to the clinician in a computerized provider order entry (CPOE) system
protocol | Protocol | A set of activities that can be performed that have relationships in terms of order, pre-conditions, etc.
eca-rule | ECA Rule | A decision support rule of the form [on Event] if Condition then Action. It is intended to be a shareable, computable definition of actions that should be taken whenever some condition is met in response to a particular event or events

See the full registry of value sets defined as part of FHIR.

Explanation of the columns that may appear on this page:

Level | A few code lists that FHIR defines are hierarchical - each code is assigned a level. In this scheme, some codes are under other codes, and imply that the code they are under also applies
Source | The source of the definition of the code (when the value set draws in codes defined elsewhere)
Code | The code (used as the code in the resource instance). If the code is in italics, this indicates that the code is not selectable ('Abstract')
Display | The display (used in the display element of a Coding). If there is no display, implementers should not simply display the code, but map the concept into their application
Definition | An explanation of the meaning of the concept
Comments | Additional notes about how to use the code

4.2.12.783 Code System http://hl7.org/fhir/action-grouping-behavior

URL: https://hl7.org/fhir/STU3/codesystem-action-grouping-behavior.html

This page is part of the FHIR Specification (v3.0.2: STU 3). The current version which supercedes this version is 4.0.1. For a full list of available versions, see the Directory of published versions

Vocabulary Work Group | Maturity Level: 2 | Informative | Use Context: Any

This is a code system defined by the FHIR project.

Summary

Defining URL: | http://hl7.org/fhir/action-grouping-behavior
Name: | ActionGroupingBehavior
Definition: | Defines organization behavior of a group
Committee: | Clinical Decision Support Work Group
OID: | 2.16.840.1.113883.4.642.1.783 (for OID based terminology systems)
Source Resource | XML / JSON

This Code system is used in the following value sets:

* ActionGroupingBehavior (Defines organization behavior of a group)

4.2.12.783.1 Content

4.2.12.783.2 ActionGroupingBehavior

Defines organization behavior of a group

This code system http://hl7.org/fhir/action-grouping-behavior defines the following codes:

Code | Display | Definition
visual-group | Visual Group | Any group marked with this behavior should be displayed as a visual group to the end user
logical-group | Logical Group | A group with this behavior logically groups its sub-elements, and may be shown as a visual group to the end user, but it is not required to do so
sentence-group | Sentence Group | A group of related alternative actions is a sentence group if the target referenced by the action is the same in all the actions and each action simply constitutes a different variation on how to specify the details for the target. For example, two actions that could be in a SentenceGroup are "aspirin, 500 mg, 2 times per day" and "aspirin, 300 mg, 3 times per day". In both cases, aspirin is the target referenced by the action, and the two actions represent different options for how aspirin might be ordered for the patient. Note that a SentenceGroup would almost always have an associated selection behavior of "AtMostOne", unless it's a required action, in which case, it would be "ExactlyOne"

See the full registry of value sets defined as part of FHIR.

Explanation of the columns that may appear on this page:

Level | A few code lists that FHIR defines are hierarchical - each code is assigned a level. In this scheme, some codes are under other codes, and imply that the code they are under also applies
Source | The source of the definition of the code (when the value set draws in codes defined elsewhere)
Code | The code (used as the code in the resource instance). If the code is in italics, this indicates that the code is not selectable ('Abstract')
Display | The display (used in the display element of a Coding). If there is no display, implementers should not simply display the code, but map the concept into their application
Definition | An explanation of the meaning of the concept
Comments | Additional notes about how to use the code

4.2.12.785 Code System http://hl7.org/fhir/action-selection-behavior

URL: https://hl7.org/fhir/STU3/codesystem-action-selection-behavior.html

This page is part of the FHIR Specification (v3.0.2: STU 3). The current version which supercedes this version is 4.0.1. For a full list of available versions, see the Directory of published versions

Vocabulary Work Group | Maturity Level: 2 | Informative | Use Context: Any

This is a code system defined by the FHIR project.

Summary

Defining URL: | http://hl7.org/fhir/action-selection-behavior
Name: | ActionSelectionBehavior
Definition: | Defines selection behavior of a group
Committee: | Clinical Decision Support Work Group
OID: | 2.16.840.1.113883.4.642.1.785 (for OID based terminology systems)
Source Resource | XML / JSON

This Code system is used in the following value sets:

* ActionSelectionBehavior (Defines selection behavior of a group)

4.2.12.785.1 Content

4.2.12.785.2 ActionSelectionBehavior

Defines selection behavior of a group

This code system http://hl7.org/fhir/action-selection-behavior defines the following codes:

Code | Display | Definition
any | Any | Any number of the actions in the group may be chosen, from zero to all
all | All | All the actions in the group must be selected as a single unit
all-or-none | All Or None | All the actions in the group are meant to be chosen as a single unit: either all must be selected by the end user, or none may be selected
exactly-one | Exactly One | The end user must choose one and only one of the selectable actions in the group. The user may not choose none of the actions in the group
at-most-one | At Most One | The end user may choose zero or at most one of the actions in the group
one-or-more | One Or More | The end user must choose a minimum of one, and as many additional as desired

See the full registry of value sets defined as part of FHIR.

Explanation of the columns that may appear on this page:

Level | A few code lists that FHIR defines are hierarchical - each code is assigned a level. In this scheme, some codes are under other codes, and imply that the code they are under also applies
Source | The source of the definition of the code (when the value set draws in codes defined elsewhere)
Code | The code (used as the code in the resource instance). If the code is in italics, this indicates that the code is not selectable ('Abstract')
Display | The display (used in the display element of a Coding). If there is no display, implementers should not simply display the code, but map the concept into their application
Definition | An explanation of the meaning of the concept
Comments | Additional notes about how to use the code

4.2.12.787 Code System http://hl7.org/fhir/action-required-behavior

URL: https://hl7.org/fhir/STU3/codesystem-action-required-behavior.html

This page is part of the FHIR Specification (v3.0.2: STU 3). The current version which supercedes this version is 4.0.1. For a full list of available versions, see the Directory of published versions

Vocabulary Work Group | Maturity Level: 2 | Informative | Use Context: Any

This is a code system defined by the FHIR project.

Summary

Defining URL: | http://hl7.org/fhir/action-required-behavior
Name: | ActionRequiredBehavior
Definition: | Defines requiredness behavior for selecting an action or an action group
Committee: | Clinical Decision Support Work Group
OID: | 2.16.840.1.113883.4.642.1.787 (for OID based terminology systems)
Source Resource | XML / JSON

This Code system is used in the following value sets:

* ActionRequiredBehavior (Defines requiredness behavior for selecting an action or an action group)

4.2.12.787.1 Content

4.2.12.787.2 ActionRequiredBehavior

Defines requiredness behavior for selecting an action or an action group

This code system http://hl7.org/fhir/action-required-behavior defines the following codes:

Code | Display | Definition
must | Must | An action with this behavior must be included in the actions processed by the end user; the end user may not choose not to include this action
could | Could | An action with this behavior may be included in the set of actions processed by the end user
must-unless-documented | Must Unless Documented | An action with this behavior must be included in the set of actions processed by the end user, unless the end user provides documentation as to why the action was not included

See the full registry of value sets defined as part of FHIR.

Explanation of the columns that may appear on this page:

Level | A few code lists that FHIR defines are hierarchical - each code is assigned a level. In this scheme, some codes are under other codes, and imply that the code they are under also applies
Source | The source of the definition of the code (when the value set draws in codes defined elsewhere)
Code | The code (used as the code in the resource instance). If the code is in italics, this indicates that the code is not selectable ('Abstract')
Display | The display (used in the display element of a Coding). If there is no display, implementers should not simply display the code, but map the concept into their application
Definition | An explanation of the meaning of the concept
Comments | Additional notes about how to use the code

4.2.12.789 Code System http://hl7.org/fhir/action-precheck-behavior

URL: https://hl7.org/fhir/STU3/codesystem-action-precheck-behavior.html

This page is part of the FHIR Specification (v3.0.2: STU 3). The current version which supercedes this version is 4.0.1. For a full list of available versions, see the Directory of published versions

Vocabulary Work Group | Maturity Level: 2 | Informative | Use Context: Any

This is a code system defined by the FHIR project.

Summary

Defining URL: | http://hl7.org/fhir/action-precheck-behavior
Name: | ActionPrecheckBehavior
Definition: | Defines selection frequency behavior for an action or group
Committee: | Clinical Decision Support Work Group
OID: | 2.16.840.1.113883.4.642.1.789 (for OID based terminology systems)
Source Resource | XML / JSON

This Code system is used in the following value sets:

* ActionPrecheckBehavior (Defines selection frequency behavior for an action or group)

4.2.12.789.1 Content

4.2.12.789.2 ActionPrecheckBehavior

Defines selection frequency behavior for an action or group

This code system http://hl7.org/fhir/action-precheck-behavior defines the following codes:

Code | Display | Definition
yes | Yes | An action with this behavior is one of the most frequent action that is, or should be, included by an end user, for the particular context in which the action occurs. The system displaying the action to the end user should consider "pre-checking" such an action as a convenience for the user
no | No | An action with this behavior is one of the less frequent actions included by the end user, for the particular context in which the action occurs. The system displaying the actions to the end user would typically not "pre-check" such an action

See the full registry of value sets defined as part of FHIR.

Explanation of the columns that may appear on this page:

Level | A few code lists that FHIR defines are hierarchical - each code is assigned a level. In this scheme, some codes are under other codes, and imply that the code they are under also applies
Source | The source of the definition of the code (when the value set draws in codes defined elsewhere)
Code | The code (used as the code in the resource instance). If the code is in italics, this indicates that the code is not selectable ('Abstract')
Display | The display (used in the display element of a Coding). If there is no display, implementers should not simply display the code, but map the concept into their application
Definition | An explanation of the meaning of the concept
Comments | Additional notes about how to use the code

4.2.12.791 Code System http://hl7.org/fhir/action-cardinality-behavior

URL: https://hl7.org/fhir/STU3/codesystem-action-cardinality-behavior.html

This page is part of the FHIR Specification (v3.0.2: STU 3). The current version which supercedes this version is 4.0.1. For a full list of available versions, see the Directory of published versions

Vocabulary Work Group | Maturity Level: 2 | Informative | Use Context: Any

This is a code system defined by the FHIR project.

Summary

Defining URL: | http://hl7.org/fhir/action-cardinality-behavior
Name: | ActionCardinalityBehavior
Definition: | Defines behavior for an action or a group for how many times that item may be repeated
Committee: | Clinical Decision Support Work Group
OID: | 2.16.840.1.113883.4.642.1.791 (for OID based terminology systems)
Source Resource | XML / JSON

This Code system is used in the following value sets:

* ActionCardinalityBehavior (Defines behavior for an action or a group for how many times that item may be repeated)

4.2.12.791.1 Content

4.2.12.791.2 ActionCardinalityBehavior

Defines behavior for an action or a group for how many times that item may be repeated

This code system http://hl7.org/fhir/action-cardinality-behavior defines the following codes:

Code | Display | Definition
single | Single | The action may only be selected one time
multiple | Multiple | The action may be selected multiple times

See the full registry of value sets defined as part of FHIR.

Explanation of the columns that may appear on this page:

Level | A few code lists that FHIR defines are hierarchical - each code is assigned a level. In this scheme, some codes are under other codes, and imply that the code they are under also applies
Source | The source of the definition of the code (when the value set draws in codes defined elsewhere)
Code | The code (used as the code in the resource instance). If the code is in italics, this indicates that the code is not selectable ('Abstract')
Display | The display (used in the display element of a Coding). If there is no display, implementers should not simply display the code, but map the concept into their application
Definition | An explanation of the meaning of the concept
Comments | Additional notes about how to use the code

4.2.12.793 Code System http://hl7.org/fhir/action-type

URL: https://hl7.org/fhir/STU3/codesystem-action-type.html

This page is part of the FHIR Specification (v3.0.2: STU 3). The current version which supercedes this version is 4.0.1. For a full list of available versions, see the Directory of published versions

Vocabulary Work Group | Maturity Level: 2 | Informative | Use Context: Any

This is a code system defined by the FHIR project.

Summary

Defining URL: | http://hl7.org/fhir/action-type
Name: | ActionType
Definition: | The type of action to be performed
Committee: | Clinical Decision Support Work Group
OID: | 2.16.840.1.113883.4.642.1.793 (for OID based terminology systems)
Source Resource | XML / JSON

This Code system is used in the following value sets:

* ActionType (The type of action to be performed)

4.2.12.793.1 Content

4.2.12.793.2 ActionType

The type of action to be performed

This code system http://hl7.org/fhir/action-type defines the following codes:

Code | Display | Definition
create | Create | The action is to create a new resource
update | Update | The action is to update an existing resource
remove | Remove | The action is to remove an existing resource
fire-event | Fire Event | The action is to fire a specific event

See the full registry of value sets defined as part of FHIR.

Explanation of the columns that may appear on this page:

Level | A few code lists that FHIR defines are hierarchical - each code is assigned a level. In this scheme, some codes are under other codes, and imply that the code they are under also applies
Source | The source of the definition of the code (when the value set draws in codes defined elsewhere)
Code | The code (used as the code in the resource instance). If the code is in italics, this indicates that the code is not selectable ('Abstract')
Display | The display (used in the display element of a Coding). If there is no display, implementers should not simply display the code, but map the concept into their application
Definition | An explanation of the meaning of the concept
Comments | Additional notes about how to use the code

4.2.12.795 Code System http://hl7.org/fhir/action-participant-type

URL: https://hl7.org/fhir/STU3/codesystem-action-participant-type.html

This page is part of the FHIR Specification (v3.0.2: STU 3). The current version which supercedes this version is 4.0.1. For a full list of available versions, see the Directory of published versions

Vocabulary Work Group | Maturity Level: 2 | Informative | Use Context: Any

This is a code system defined by the FHIR project.

Summary

Defining URL: | http://hl7.org/fhir/action-participant-type
Name: | ActionParticipantType
Definition: | The type of participant for the action
Committee: | Clinical Decision Support Work Group
OID: | 2.16.840.1.113883.4.642.1.795 (for OID based terminology systems)
Source Resource | XML / JSON

This Code system is used in the following value sets:

* ActionParticipantType (The type of participant for the action)

4.2.12.795.1 Content

4.2.12.795.2 ActionParticipantType

The type of participant for the action

This code system http://hl7.org/fhir/action-participant-type defines the following codes:

Code | Display | Definition
patient | Patient | The participant is the patient under evaluation
practitioner | Practitioner | The participant is a practitioner involved in the patient's care
related-person | Related Person | The participant is a person related to the patient

See the full registry of value sets defined as part of FHIR.

Explanation of the columns that may appear on this page:

Level | A few code lists that FHIR defines are hierarchical - each code is assigned a level. In this scheme, some codes are under other codes, and imply that the code they are under also applies
Source | The source of the definition of the code (when the value set draws in codes defined elsewhere)
Code | The code (used as the code in the resource instance). If the code is in italics, this indicates that the code is not selectable ('Abstract')
Display | The display (used in the display element of a Coding). If there is no display, implementers should not simply display the code, but map the concept into their application
Definition | An explanation of the meaning of the concept
Comments | Additional notes about how to use the code

4.2.12.797 Code System http://hl7.org/fhir/action-relationship-type

URL: https://hl7.org/fhir/STU3/codesystem-action-relationship-type.html

This page is part of the FHIR Specification (v3.0.2: STU 3). The current version which supercedes this version is 4.0.1. For a full list of available versions, see the Directory of published versions

Vocabulary Work Group | Maturity Level: 2 | Informative | Use Context: Any

This is a code system defined by the FHIR project.

Summary

Defining URL: | http://hl7.org/fhir/action-relationship-type
Name: | ActionRelationshipType
Definition: | Defines the types of relationships between actions
Committee: | Clinical Decision Support Work Group
OID: | 2.16.840.1.113883.4.642.1.797 (for OID based terminology systems)
Source Resource | XML / JSON

This Code system is used in the following value sets:

* ActionRelationshipType (Defines the types of relationships between actions)

4.2.12.797.1 Content

4.2.12.797.2 ActionRelationshipType

Defines the types of relationships between actions

This code system http://hl7.org/fhir/action-relationship-type defines the following codes:

Code | Display | Definition
before-start | Before Start | The action must be performed before the start of the related action
before | Before | The action must be performed before the related action
before-end | Before End | The action must be performed before the end of the related action
concurrent-with-start | Concurrent With Start | The action must be performed concurrent with the start of the related action
concurrent | Concurrent | The action must be performed concurrent with the related action
concurrent-with-end | Concurrent With End | The action must be performed concurrent with the end of the related action
after-start | After Start | The action must be performed after the start of the related action
after | After | The action must be performed after the related action
after-end | After End | The action must be performed after the end of the related action

See the full registry of value sets defined as part of FHIR.

Explanation of the columns that may appear on this page:

Level | A few code lists that FHIR defines are hierarchical - each code is assigned a level. In this scheme, some codes are under other codes, and imply that the code they are under also applies
Source | The source of the definition of the code (when the value set draws in codes defined elsewhere)
Code | The code (used as the code in the resource instance). If the code is in italics, this indicates that the code is not selectable ('Abstract')
Display | The display (used in the display element of a Coding). If there is no display, implementers should not simply display the code, but map the concept into their application
Definition | An explanation of the meaning of the concept
Comments | Additional notes about how to use the code

4.2.12.799 Code System http://hl7.org/fhir/action-condition-kind

URL: https://hl7.org/fhir/STU3/codesystem-action-condition-kind.html

This page is part of the FHIR Specification (v3.0.2: STU 3). The current version which supercedes this version is 4.0.1. For a full list of available versions, see the Directory of published versions

Vocabulary Work Group | Maturity Level: 2 | Informative | Use Context: Any

This is a code system defined by the FHIR project.

Summary

Defining URL: | http://hl7.org/fhir/action-condition-kind
Name: | ActionConditionKind
Definition: | Defines the kinds of conditions that can appear on actions
Committee: | Clinical Decision Support Work Group
OID: | 2.16.840.1.113883.4.642.1.799 (for OID based terminology systems)
Source Resource | XML / JSON

This Code system is used in the following value sets:

* ActionConditionKind (Defines the kinds of conditions that can appear on actions)

4.2.12.799.1 Content

4.2.12.799.2 ActionConditionKind

Defines the kinds of conditions that can appear on actions

This code system http://hl7.org/fhir/action-condition-kind defines the following codes:

Code | Display | Definition
applicability | Applicability | The condition describes whether or not a given action is applicable
start | Start | The condition is a starting condition for the action
stop | Stop | The condition is a stop, or exit condition for the action

See the full registry of value sets defined as part of FHIR.

Explanation of the columns that may appear on this page:

Level | A few code lists that FHIR defines are hierarchical - each code is assigned a level. In this scheme, some codes are under other codes, and imply that the code they are under also applies
Source | The source of the definition of the code (when the value set draws in codes defined elsewhere)
Code | The code (used as the code in the resource instance). If the code is in italics, this indicates that the code is not selectable ('Abstract')
Display | The display (used in the display element of a Coding). If there is no display, implementers should not simply display the code, but map the concept into their application
Definition | An explanation of the meaning of the concept
Comments | Additional notes about how to use the code

4.2.12.801 Code System http://hl7.org/fhir/guidance-response-status

URL: https://hl7.org/fhir/STU3/codesystem-guidance-response-status.html

This page is part of the FHIR Specification (v3.0.2: STU 3). The current version which supercedes this version is 4.0.1. For a full list of available versions, see the Directory of published versions

Vocabulary Work Group | Maturity Level: 2 | Informative | Use Context: Any

This is a code system defined by the FHIR project.

Summary

Defining URL: | http://hl7.org/fhir/guidance-response-status
Name: | GuidanceResponseStatus
Definition: | The status of a guidance response
Committee: | Clinical Decision Support Work Group
OID: | 2.16.840.1.113883.4.642.1.801 (for OID based terminology systems)
Source Resource | XML / JSON

This Code system is used in the following value sets:

* GuidanceResponseStatus (The status of a guidance response)

4.2.12.801.1 Content

4.2.12.801.2 GuidanceResponseStatus

The status of a guidance response

This code system http://hl7.org/fhir/guidance-response-status defines the following codes:

Code | Display | Definition
success | Success | The request was processed successfully
data-requested | Data Requested | The request was processed successfully, but more data may result in a more complete evaluation
data-required | Data Required | The request was processed, but more data is required to complete the evaluation
in-progress | In Progress | The request is currently being processed
failure | Failure | The request was not processed successfully
entered-in-error | Entered In Error | The response was entered in error

See the full registry of value sets defined as part of FHIR.

Explanation of the columns that may appear on this page:

Level | A few code lists that FHIR defines are hierarchical - each code is assigned a level. In this scheme, some codes are under other codes, and imply that the code they are under also applies
Source | The source of the definition of the code (when the value set draws in codes defined elsewhere)
Code | The code (used as the code in the resource instance). If the code is in italics, this indicates that the code is not selectable ('Abstract')
Display | The display (used in the display element of a Coding). If there is no display, implementers should not simply display the code, but map the concept into their application
Definition | An explanation of the meaning of the concept
Comments | Additional notes about how to use the code

4.2.12.803 Code System http://hl7.org/fhir/research-study-status

URL: https://hl7.org/fhir/STU3/codesystem-research-study-status.html

This page is part of the FHIR Specification (v3.0.2: STU 3). The current version which supercedes this version is 4.0.1. For a full list of available versions, see the Directory of published versions

Vocabulary Work Group | Maturity Level: 0 | Informative | Use Context: Any

This is a code system defined by the FHIR project.

Summary

Defining URL: | http://hl7.org/fhir/research-study-status
Name: | ResearchStudyStatus
Definition: | Codes that convey the current status of the research study
Committee: | Regulated Clinical Research Information Management Work Group
OID: | 2.16.840.1.113883.4.642.1.803 (for OID based terminology systems)
Source Resource | XML / JSON

This Code system is used in the following value sets:

* ResearchStudyStatus (Codes that convey the current status of the research study)

4.2.12.803.1 Content

4.2.12.803.2 ResearchStudyStatus

Codes that convey the current status of the research study

This code system http://hl7.org/fhir/research-study-status defines the following codes:

Code | Display | Definition
draft | Draft | The study is undergoing design but the process of selecting study subjects and capturing data has not yet begun.
in-progress | In-progress | The study is currently being executed
suspended | Suspended | Execution of the study has been temporarily paused

stopped | Stopped | The study was terminated prior to the final determination of results
completed | Completed | The information sought by the study has been gathered and compiled and no further work is being performed
entered-in-error | Entered in error | This study never actually existed. The record is retained for tracking purposes in the event decisions may have been made based on this erroneous information.

See the full registry of value sets defined as part of FHIR.

Explanation of the columns that may appear on this page:

Level | A few code lists that FHIR defines are hierarchical - each code is assigned a level. In this scheme, some codes are under other codes, and imply that the code they are under also applies
Source | The source of the definition of the code (when the value set draws in codes defined elsewhere)
Code | The code (used as the code in the resource instance). If the code is in italics, this indicates that the code is not selectable ('Abstract')
Display | The display (used in the display element of a Coding). If there is no display, implementers should not simply display the code, but map the concept into their application
Definition | An explanation of the meaning of the concept
Comments | Additional notes about how to use the code

4.2.12.805 Code System http://hl7.org/fhir/research-subject-status

URL: https://hl7.org/fhir/STU3/codesystem-research-subject-status.html

This page is part of the FHIR Specification (v3.0.2: STU 3). The current version which supercedes this version is 4.0.1. For a full list of available versions, see the Directory of published versions

Vocabulary Work Group | Maturity Level: 0 | Informative | Use Context: Any

This is a code system defined by the FHIR project.

Summary

Defining URL: | http://hl7.org/fhir/research-subject-status
Name: | ResearchSubjectStatus
Definition: | Indicates the progression of a study subject through a study
Committee: | Regulated Clinical Research Information Management Work Group
OID: | 2.16.840.1.113883.4.642.1.805 (for OID based terminology systems)
Source Resource | XML / JSON

This Code system is used in the following value sets:

* ResearchSubjectStatus (Indicates the progression of a study subject through a study)

4.2.12.805.1 Content

4.2.12.805.2 ResearchSubjectStatus

Indicates the progression of a study subject through a study

This code system http://hl7.org/fhir/research-subject-status defines the following codes:

Code | Display | Definition
candidate | Candidate | The subject has been identified as a potential participant in the study but has not yet agreed to participate
enrolled | Enrolled | The subject has agreed to participate in the study but has not yet begun performing any action within the study
active | Active | The subject is currently being monitored and/or subject to treatment as part of the study
suspended | Suspended | The subject has temporarily discontinued monitoring/treatment as part of the study
withdrawn | Withdrawn | The subject has permanently ended participation in the study prior to completion of the intended monitoring/treatment
completed | Completed | All intended monitoring/treatment of the subject has been completed and their engagement with the study is now ended

See the full registry of value sets defined as part of FHIR.

Explanation of the columns that may appear on this page:

Level | A few code lists that FHIR defines are hierarchical - each code is assigned a level. In this scheme, some codes are under other codes, and imply that the code they are under also applies
Source | The source of the definition of the code (when the value set draws in codes defined elsewhere)
Code | The code (used as the code in the resource instance). If the code is in italics, this indicates that the code is not selectable ('Abstract')
Display | The display (used in the display element of a Coding). If there is no display, implementers should not simply display the code, but map the concept into their application
Definition | An explanation of the meaning of the concept
Comments | Additional notes about how to use the code

4.2.12.807 Code System http://hl7.org/fhir/adverse-event-category

URL: https://hl7.org/fhir/STU3/codesystem-adverse-event-category.html

This page is part of the FHIR Specification (v3.0.2: STU 3). The current version which supercedes this version is 4.0.1. For a full list of available versions, see the Directory of published versions

Vocabulary Work Group | Maturity Level: 0 | Informative | Use Context: Any

This is a code system defined by the FHIR project.

Summary

Defining URL: | http://hl7.org/fhir/adverse-event-category
Name: | AdverseEventCategory

Definition: | Overall categorization of the event, e.g. real or potential
Committee: | Regulated Clinical Research Information Management Work Group
OID: | 2.16.840.1.113883.4.642.1.807 (for OID based terminology systems)
Source Resource | XML / JSON

This Code system is used in the following value sets:

* AdverseEventCategory (Overall categorization of the event, e.g. real or potential)

4.2.12.807.1 Content

4.2.12.807.2 AdverseEventCategory

Overall categorization of the event, e.g. real or potential

This code system http://hl7.org/fhir/adverse-event-category defines the following codes:

Code | Display | Definition
AE | Adverse Event
PAE | Potential Adverse Event

See the full registry of value sets defined as part of FHIR.

Explanation of the columns that may appear on this page:

Level | A few code lists that FHIR defines are hierarchical - each code is assigned a level. In this scheme, some codes are under other codes, and imply that the code they are under also applies
Source | The source of the definition of the code (when the value set draws in codes defined elsewhere)
Code | The code (used as the code in the resource instance). If the code is in italics, this indicates that the code is not selectable ('Abstract')
Display | The display (used in the display element of a Coding). If there is no display, implementers should not simply display the code, but map the concept into their application
Definition | An explanation of the meaning of the concept
Comments | Additional notes about how to use the code

4.2.12.810 Code System http://hl7.org/fhir/adverse-event-outcome

URL: https://hl7.org/fhir/STU3/codesystem-adverse-event-outcome.html

This page is part of the FHIR Specification (v3.0.2: STU 3). The current version which supercedes this version is 4.0.1. For a full list of available versions, see the Directory of published versions

Vocabulary Work Group | Maturity Level: 0 | Informative | Use Context: Any

This is a code system defined by the FHIR project.

Summary

Defining URL: | http://hl7.org/fhir/adverse-event-outcome
Name: | AdverseEventOutcome
Definition: | TODO (and should this be required?)
Committee: | Regulated Clinical Research Information Management Work Group
OID: | 2.16.840.1.113883.4.642.1.810 (for OID based terminology systems)
Source Resource | XML / JSON

This Code system is used in the following value sets:

* AdverseEventOutcome (TODO (and should this be required?))

4.2.12.810.1 Content

4.2.12.810.2 AdverseEventOutcome

TODO (and should this be required?)

This code system http://hl7.org/fhir/adverse-event-outcome defines the following codes:

Code | Display | Definition
resolved | Resolved
recovering | Recovering
ongoing | Ongoing
resolvedWithSequelae | Resolved with Sequelae
fatal | Fatal
unknown | Unknown

See the full registry of value sets defined as part of FHIR.

Explanation of the columns that may appear on this page:

Level | A few code lists that FHIR defines are hierarchical - each code is assigned a level. In this scheme, some codes are under other codes, and imply that the code they are under also applies
Source | The source of the definition of the code (when the value set draws in codes defined elsewhere)
Code | The code (used as the code in the resource instance). If the code is in italics, this indicates that the code is not selectable ('Abstract')
Display | The display (used in the display element of a Coding). If there is no display, implementers should not simply display the code, but map the concept into their application
Definition | An explanation of the meaning of the concept

Comments | Additional notes about how to use the code

4.2.12.812 Code System http://hl7.org/fhir/adverse-event-seriousness

URL: https://hl7.org/fhir/STU3/codesystem-adverse-event-seriousness.html

This page is part of the FHIR Specification (v3.0.2: STU 3). The current version which supercedes this version is 4.0.1. For a full list of available versions, see the Directory of published versions

Vocabulary Work Group | Maturity Level: 1 | Informative | Use Context: Any

This is a code system defined by the FHIR project.

Summary

Defining URL: | http://hl7.org/fhir/adverse-event-seriousness
Name: | AdverseEventSeriousness
Definition: | Overall seriousness of this event for the patient
Committee: | Regulated Clinical Research Information Management Work Group
OID: | 2.16.840.1.113883.4.642.1.812 (for OID based terminology systems)
Source Resource | XML / JSON

This Code system is used in the following value sets:

* AdverseEventSeriousness (Overall seriousness of this event for the patient)

4.2.12.812.1 Content

4.2.12.812.2 AdverseEventSeriousness

Overall seriousness of this event for the patient

This code system http://hl7.org/fhir/adverse-event-seriousness defines the following codes:

Code | Display | Definition
Mild | Mild
Moderate | Moderate
Severe | Severe

See the full registry of value sets defined as part of FHIR.

Explanation of the columns that may appear on this page:

Level | A few code lists that FHIR defines are hierarchical - each code is assigned a level. In this scheme, some codes are under other codes, and imply that the code they are under also applies
Source | The source of the definition of the code (when the value set draws in codes defined elsewhere)
Code | The code (used as the code in the resource instance). If the code is in italics, this indicates that the code is not selectable ('Abstract')
Display | The display (used in the display element of a Coding). If there is no display, implementers should not simply display the code, but map the concept into their application
Definition | An explanation of the meaning of the concept
Comments | Additional notes about how to use the code

4.2.12.814 Code System http://hl7.org/fhir/adverse-event-causality

URL: https://hl7.org/fhir/STU3/codesystem-adverse-event-causality.html

This page is part of the FHIR Specification (v3.0.2: STU 3). The current version which supercedes this version is 4.0.1. For a full list of available versions, see the Directory of published versions

Vocabulary Work Group | Maturity Level: 0 | Informative | Use Context: Any

This is a code system defined by the FHIR project.

Summary

Defining URL: | http://hl7.org/fhir/adverse-event-causality
Name: | AdverseEventCausality
Definition: | TODO
Committee: | Regulated Clinical Research Information Management Work Group
OID: | 2.16.840.1.113883.4.642.1.814 (for OID based terminology systems)
Source Resource | XML / JSON

This Code system is used in the following value sets:

* AdverseEventCausality (TODO)

4.2.12.814.1 Content

4.2.12.814.2 AdverseEventCausality

TODO

This code system http://hl7.org/fhir/adverse-event-causality defines the following codes:

Code | Display | Definition
causality1 | causality1 placeholder

causality2 | causality2 placeholder

See the full registry of value sets defined as part of FHIR.

Explanation of the columns that may appear on this page:

Level | A few code lists that FHIR defines are hierarchical - each code is assigned a level. In this scheme, some codes are under other codes, and imply that the code they are under also applies
Source | The source of the definition of the code (when the value set draws in codes defined elsewhere)
Code | The code (used as the code in the resource instance). If the code is in italics, this indicates that the code is not selectable ('Abstract')
Display | The display (used in the display element of a Coding). If there is no display, implementers should not simply display the code, but map the concept into their application
Definition | An explanation of the meaning of the concept
Comments | Additional notes about how to use the code

4.2.12.816 Code System http://hl7.org/fhir/adverse-event-causality-assess

URL: https://hl7.org/fhir/STU3/codesystem-adverse-event-causality-assess.html

This page is part of the FHIR Specification (v3.0.2: STU 3). The current version which supercedes this version is 4.0.1. For a full list of available versions, see the Directory of published versions

Vocabulary Work Group | Maturity Level: 1 | Informative | Use Context: Any

This is a code system defined by the FHIR project.

Summary

Defining URL: | http://hl7.org/fhir/adverse-event-causality-assess
Name: | AdverseEventCausalityAssessment
Definition: | TODO
Committee: | Regulated Clinical Research Information Management Work Group
OID: | 2.16.840.1.113883.4.642.1.816 (for OID based terminology systems)
Source Resource | XML / JSON

This Code system is used in the following value sets:

* AdverseEventCausalityAssessment (TODO)

4.2.12.816.1 Content

4.2.12.816.2 AdverseEventCausalityAssessment

TODO

This code system http://hl7.org/fhir/adverse-event-causality-assess defines the following codes:

Code | Display | Definition
assess1 | assess1 placeholder
assess2 | assess2 placeholder

See the full registry of value sets defined as part of FHIR.

Explanation of the columns that may appear on this page:

Level | A few code lists that FHIR defines are hierarchical - each code is assigned a level. In this scheme, some codes are under other codes, and imply that the code they are under also applies
Source | The source of the definition of the code (when the value set draws in codes defined elsewhere)
Code | The code (used as the code in the resource instance). If the code is in italics, this indicates that the code is not selectable ('Abstract')
Display | The display (used in the display element of a Coding). If there is no display, implementers should not simply display the code, but map the concept into their application
Definition | An explanation of the meaning of the concept
Comments | Additional notes about how to use the code

4.2.12.818 Code System http://hl7.org/fhir/adverse-event-causality-method

URL: https://hl7.org/fhir/STU3/codesystem-adverse-event-causality-method.html

This page is part of the FHIR Specification (v3.0.2: STU 3). The current version which supercedes this version is 4.0.1. For a full list of available versions, see the Directory of published versions

Vocabulary Work Group | Maturity Level: 1 | Informative | Use Context: Any

This is a code system defined by the FHIR project.

Summary

Defining URL: | http://hl7.org/fhir/adverse-event-causality-method
Name: | AdverseEventCausalityMethod
Definition: | TODO
Committee: | Regulated Clinical Research Information Management Work Group
OID: | 2.16.840.1.113883.4.642.1.818 (for OID based terminology systems)
Source Resource | XML / JSON

This Code system is used in the following value sets:

* AdverseEventCausalityMethod (TODO)

4.2.12.818.1 Content

4.2.12.818.2 AdverseEventCausalityMethod

TODO

This code system http://hl7.org/fhir/adverse-event-causality-method defines the following codes:

Code | Display | Definition
method1 | placeholder
method2 | placeholder

See the full registry of value sets defined as part of FHIR.

Explanation of the columns that may appear on this page:

Level | A few code lists that FHIR defines are hierarchical - each code is assigned a level. In this scheme, some codes are under other codes, and imply that the code they are under also applies
Source | The source of the definition of the code (when the value set draws in codes defined elsewhere)
Code | The code (used as the code in the resource instance). If the code is in italics, this indicates that the code is not selectable ('Abstract')
Display | The display (used in the display element of a Coding). If there is no display, implementers should not simply display the code, but map the concept into their application
Definition | An explanation of the meaning of the concept
Comments | Additional notes about how to use the code

4.2.12.820 Code System http://hl7.org/fhir/adverse-event-causality-result

URL: https://hl7.org/fhir/STU3/codesystem-adverse-event-causality-result.html

This page is part of the FHIR Specification (v3.0.2: STU 3). The current version which supercedes this version is 4.0.1. For a full list of available versions, see the Directory of published versions

Vocabulary Work Group | Maturity Level: 1 | Informative | Use Context: Any

This is a code system defined by the FHIR project.

Summary

Defining URL: | http://hl7.org/fhir/adverse-event-causality-result
Name: | AdverseEventCausalityResult
Definition: | TODO
Committee: | Regulated Clinical Research Information Management Work Group
OID: | 2.16.840.1.113883.4.642.1.820 (for OID based terminology systems)
Source Resource | XML / JSON

This Code system is used in the following value sets:

* AdverseEventCausalityResult (TODO)

4.2.12.820.1 Content

4.2.12.820.2 AdverseEventCausalityResult

TODO

This code system http://hl7.org/fhir/adverse-event-causality-result defines the following codes:

Code | Display | Definition
result1 | placeholder
result2 | placeholder

See the full registry of value sets defined as part of FHIR.

Explanation of the columns that may appear on this page:

Level | A few code lists that FHIR defines are hierarchical - each code is assigned a level. In this scheme, some codes are under other codes, and imply that the code they are under also applies
Source | The source of the definition of the code (when the value set draws in codes defined elsewhere)
Code | The code (used as the code in the resource instance). If the code is in italics, this indicates that the code is not selectable ('Abstract')
Display | The display (used in the display element of a Coding). If there is no display, implementers should not simply display the code, but map the concept into their application
Definition | An explanation of the meaning of the concept
Comments | Additional notes about how to use the code

4.2.12.822 Code System http://hl7.org/fhir/chargeitem-status

URL: https://hl7.org/fhir/STU3/codesystem-chargeitem-status.html

This page is part of the FHIR Specification (v3.0.2: STU 3). The current version which supercedes this version is 4.0.1. For a full list of available versions, see the Directory of published versions

Vocabulary Work Group | Maturity Level: 0 | Informative | Use Context: Any

This is a code system defined by the FHIR project.

Summary

Defining URL: | http://hl7.org/fhir/chargeitem-status
Name: | ChargeItemStatus
Definition: | Codes identifying the stage lifecycle stage of a ChargeItem
Committee: | Patient Administration Work Group
OID: | 2.16.840.1.113883.4.642.1.822 (for OID based terminology systems)
Source Resource | XML / JSON

This Code system is used in the following value sets:

* ChargeItemStatus (Codes identifying the stage lifecycle stage of a ChargeItem)

4.2.12.822.1 Content

4.2.12.822.2 ChargeItemStatus

Codes identifying the stage lifecycle stage of a ChargeItem

This code system http://hl7.org/fhir/chargeitem-status defines the following codes:

Code | Display | Definition
planned | Planned | The charge item has been entered, but the charged service is not yet complete, so it shall not be billed yet but might be used in the context of pre-authorization
billable | Billable | The charge item is ready for billing
not-billable | Not billable | The charge item has been determined to be not billable (e.g. due to rules associated with the billing code)
aborted | Aborted | The processing of the charge was aborted
billed | Billed | The charge item has been billed (e.g. a billing engine has generated financial transactions by applying the associated ruled for the charge item to the context of the Encounter, and placed them into Claims/Invoices
entered-in-error | Entered in Error | The charge item has been entered in error and should not be processed for billing
unknown | Unknown | The authoring system does not know which of the status values currently applies for this charge item Note: This concept is not to be used for "other" - one of the listed statuses is presumed to apply, it's just not known which one.

See the full registry of value sets defined as part of FHIR.

Explanation of the columns that may appear on this page:

Level | A few code lists that FHIR defines are hierarchical - each code is assigned a level. In this scheme, some codes are under other codes, and imply that the code they are under also applies
Source | The source of the definition of the code (when the value set draws in codes defined elsewhere)
Code | The code (used as the code in the resource instance). If the code is in italics, this indicates that the code is not selectable ('Abstract')
Display | The display (used in the display element of a Coding). If there is no display, implementers should not simply display the code, but map the concept into their application
Definition | An explanation of the meaning of the concept
Comments | Additional notes about how to use the code

4.2.12.824 Code System http://hl7.org/fhir/chargeitem-billingcodes

URL: https://hl7.org/fhir/STU3/codesystem-chargeitem-billingcodes.html

This page is part of the FHIR Specification (v3.0.2: STU 3). The current version which supercedes this version is 4.0.1. For a full list of available versions, see the Directory of published versions

Vocabulary Work Group | Maturity Level: 1 | Informative | Use Context: Any

This is a code system defined by the FHIR project.

Summary

Defining URL: | http://hl7.org/fhir/chargeitem-billingcodes
Name: | ChargeItemCode
Definition: | Example set of codes that can be used for billing purposes
Committee: | Patient Administration Work Group
OID: | 2.16.840.1.113883.4.642.1.824 (for OID based terminology systems)
Source Resource | XML / JSON

This Code system is used in the following value sets:

* ChargeItemCode (Example set of codes that can be used for billing purposes)

4.2.12.824.1 Content

4.2.12.824.2 ChargeItemCode

Example set of codes that can be used for billing purposes

This code system http://hl7.org/fhir/chargeitem-billingcodes defines the following codes:

Code | Display | Definition
1100 | Unvorhergesehene Inanspruchnahme | From German EBM billing system: Unvorhergesehene Inanspruchnahme des Vertragsarztes durch einen Patienten;zwischen 19:00 und 22:00 Uhr;an Samstagen, Sonntagen und gesetzlichen Feiertagen, am 24.12. und 31.12. zwischen 07:00 und 19:00 Uhr
1210 | Notfallpauschale | From German EBM billing system: Notfallpauschale im organisierten Not(-fall)dienst und für nicht an der vertragsärztlichen Versorgung teilnehmende Ärzte, Institute und Krankenhäuser bei Inanspruchnahme;zwischen 07:00 und 19:00 Uhr
1320 | Grundpauschale | From German EBM billing system: Grundpauschale für Ärzte, Institute und Krankenhäuser, die zur Erbringung von Leistungen innerhalb mindestens eines der Fachgebiete Anästhesiologie, Frauenheilkunde und Geburtshilfe, Haut- und Geschlechtskrankheiten,

Mund-, Kiefer- und Gesichtschirurgie und Humangenetik ermächtigt sind

See the full registry of value sets defined as part of FHIR.

Explanation of the columns that may appear on this page:

Level | A few code lists that FHIR defines are hierarchical - each code is assigned a level. In this scheme, some codes are under other codes, and imply that the code they are under also applies
Source | The source of the definition of the code (when the value set draws in codes defined elsewhere)
Code | The code (used as the code in the resource instance). If the code is in italics, this indicates that the code is not selectable ('Abstract')
Display | The display (used in the display element of a Coding). If there is no display, implementers should not simply display the code, but map the concept into their application
Definition | An explanation of the meaning of the concept
Comments | Additional notes about how to use the code

4.2.12.833 Code System http://hl7.org/fhir/name-assembly-order

URL: https://hl7.org/fhir/STU3/codesystem-name-assembly-order.html

This page is part of the FHIR Specification (v3.0.2: STU 3). The current version which supercedes this version is 4.0.1. For a full list of available versions, see the Directory of published versions

Vocabulary Work Group | Maturity Level: 0 | Informative | Use Context: Any

This is a code system defined by the FHIR project.

Summary

Defining URL: | http://hl7.org/fhir/name-assembly-order
Name: | HumanNameAssemblyOrder
Definition: | A code that represents the preferred display order of the components of a human name
Committee: | FHIR Infrastructure Work Group
OID: | 2.16.840.1.113883.4.642.1.833 (for OID based terminology systems)
Source Resource | XML / JSON

This Code system is used in the following value sets:

* HumanNameAssemblyOrder (A code that represents the preferred display order of the components of a human name)

4.2.12.833.1 Content

4.2.12.833.2 HumanNameAssemblyOrder

A code that represents the preferred display order of the components of a human name

This code system http://hl7.org/fhir/name-assembly-order defines the following codes:

Code | Display | Definition
NL1 | Own Name
NL2 | Partner Name
NL3 | Partner Name followed by Maiden Name
NL4 | Own Name followed by Partner Name

See the full registry of value sets defined as part of FHIR.

Explanation of the columns that may appear on this page:

Level | A few code lists that FHIR defines are hierarchical - each code is assigned a level. In this scheme, some codes are under other codes, and imply that the code they are under also applies
Source | The source of the definition of the code (when the value set draws in codes defined elsewhere)
Code | The code (used as the code in the resource instance). If the code is in italics, this indicates that the code is not selectable ('Abstract')
Display | The display (used in the display element of a Coding). If there is no display, implementers should not simply display the code, but map the concept into their application
Definition | An explanation of the meaning of the concept
Comments | Additional notes about how to use the code

4.2.12.835 Code System http://hl7.org/fhir/goal-relationship-type

URL: https://hl7.org/fhir/STU3/codesystem-goal-relationship-type.html

This page is part of the FHIR Specification (v3.0.2: STU 3). The current version which supercedes this version is 4.0.1. For a full list of available versions, see the Directory of published versions

Vocabulary Work Group | Maturity Level: 0 | Informative | Use Context: Any

This is a code system defined by the FHIR project.

Summary

Defining URL: | http://hl7.org/fhir/goal-relationship-type
Name: | GoalRelationshipType
Definition: | Types of relationships between two goals
Committee: | Patient Care Work Group
OID: | 2.16.840.1.113883.4.642.1.835 (for OID based terminology systems)
Source Resource | XML / JSON

This Code system is used in the following value sets:

* GoalRelationshipType (Types of relationships between two goals)

4.2.12.835.1 Content

4.2.12.835.2 GoalRelationshipType

Types of relationships between two goals

This code system http://hl7.org/fhir/goal-relationship-type defines the following codes:

Code | Display | Definition
predecessor | Predecessor | Indicates that the target goal is one which must be met before striving for the current goal
successor | Successor | Indicates that the target goal is a desired objective once the current goal is met
replacement | Replacement | Indicates that this goal has been replaced by the target goal
milestone | Milestone | Indicates that the target goal is considered to be a "piece" of attaining this goal.
other | Other | Indicates that the relationship is not covered by one of the pre-defined codes. (An extension may convey more information about the meaning of the relationship.)

See the full registry of value sets defined as part of FHIR.

Explanation of the columns that may appear on this page:

Level | A few code lists that FHIR defines are hierarchical - each code is assigned a level. In this scheme, some codes are under other codes, and imply that the code they are under also applies
Source | The source of the definition of the code (when the value set draws in codes defined elsewhere)
Code | The code (used as the code in the resource instance). If the code is in italics, this indicates that the code is not selectable ('Abstract')
Display | The display (used in the display element of a Coding). If there is no display, implementers should not simply display the code, but map the concept into their application
Definition | An explanation of the meaning of the concept
Comments | Additional notes about how to use the code

4.2.12.837 Code System http://hl7.org/fhir/goal-acceptance-status

URL: https://hl7.org/fhir/STU3/codesystem-goal-acceptance-status.html

This page is part of the FHIR Specification (v3.0.2: STU 3). The current version which supercedes this version is 4.0.1. For a full list of available versions, see the Directory of published versions

Vocabulary Work Group | Maturity Level: 0 | Informative | Use Context: Any

This is a code system defined by the FHIR project.

Summary

Defining URL: | http://hl7.org/fhir/goal-acceptance-status
Name: | GoalAcceptanceStatus
Definition: | Codes indicating whether the goal has been accepted by a stakeholder
Committee: | Patient Care Work Group
OID: | 2.16.840.1.113883.4.642.1.837 (for OID based terminology systems)
Source Resource | XML / JSON

This Code system is used in the following value sets:

* GoalAcceptanceStatus (Codes indicating whether the goal has been accepted by a stakeholder)

4.2.12.837.1 Content

4.2.12.837.2 GoalAcceptanceStatus

Codes indicating whether the goal has been accepted by a stakeholder

This code system http://hl7.org/fhir/goal-acceptance-status defines the following codes:

Code | Display | Definition
agree | Agree | Stakeholder supports pursuit of the goal
disagree | Disagree | Stakeholder is not in support of the pursuit of the goal
pending | Pending | Stakeholder has not yet made a decision on whether they support the goal

See the full registry of value sets defined as part of FHIR.

Explanation of the columns that may appear on this page:

Level | A few code lists that FHIR defines are hierarchical - each code is assigned a level. In this scheme, some codes are under other codes, and imply that the code they are under also applies
Source | The source of the definition of the code (when the value set draws in codes defined elsewhere)
Code | The code (used as the code in the resource instance). If the code is in italics, this indicates that the code is not selectable ('Abstract')
Display | The display (used in the display element of a Coding). If there is no display, implementers should not simply display the code, but map the concept into their application
Definition | An explanation of the meaning of the concept
Comments | Additional notes about how to use the code

4.2.12.839 Code System http://hl7.org/fhir/conformance-expectation

URL: https://hl7.org/fhir/STU3/codesystem-conformance-expectation.html

This page is part of the FHIR Specification (v3.0.2: STU 3). The current version which supercedes this version is 4.0.1. For a full list of available versions, see the Directory of published versions

Vocabulary Work Group | Maturity Level: 0 | Informative | Use Context: Any

This is a code system defined by the FHIR project.

Summary

Defining URL: | http://hl7.org/fhir/conformance-expectation
Name: | ConformanceExpectation
Definition: | Indicates the degree of adherence to a specified behavior or capability expected for a system to be deemed conformant with a specification.
Committee: | FHIR Infrastructure Work Group
OID: | 2.16.840.1.113883.4.642.1.839 (for OID based terminology systems)
Source Resource | XML / JSON

This Code system is used in the following value sets:

* ConformanceExpectation (Indicates the degree of adherence to a specified behavior or capability expected for a system to be deemed conformant with a specification.)

4.2.12.839.1 Content

4.2.12.839.2 ConformanceExpectation

Indicates the degree of adherence to a specified behavior or capability expected for a system to be deemed conformant with a specification.

This code system http://hl7.org/fhir/conformance-expectation defines the following codes:

Code | Display | Definition
SHALL | SHALL | Support for the specified capability is required to be considered conformant.
SHOULD | SHOULD | Support for the specified capability is strongly encouraged, and failure to support it should only occur after careful consideration.
MAY | MAY | Support for the specified capability is not necessary to be considered conformant, and the requirement should be considered strictly optional.
SHOULD-NOT | SHOULD-NOT | Support for the specified capability is strongly discouraged and should occur only after careful consideration.

See the full registry of value sets defined as part of FHIR.

Explanation of the columns that may appear on this page:

Level | A few code lists that FHIR defines are hierarchical - each code is assigned a level. In this scheme, some codes are under other codes, and imply that the code they are under also applies
Source | The source of the definition of the code (when the value set draws in codes defined elsewhere)
Code | The code (used as the code in the resource instance). If the code is in italics, this indicates that the code is not selectable ('Abstract')
Display | The display (used in the display element of a Coding). If there is no display, implementers should not simply display the code, but map the concept into their application
Definition | An explanation of the meaning of the concept
Comments | Additional notes about how to use the code

4.2.12.844 Code System http://hl7.org/fhir/messageheader-response-request

URL: https://hl7.org/fhir/STU3/codesystem-messageheader-response-request.html

This page is part of the FHIR Specification (v3.0.2: STU 3). The current version which supercedes this version is 4.0.1. For a full list of available versions, see the Directory of published versions

Vocabulary Work Group | Maturity Level: 0 | Informative | Use Context: Any

This is a code system defined by the FHIR project.

Summary

Defining URL: | http://hl7.org/fhir/messageheader-response-request
Name: | messageheader-response-request
Definition: | HL7-defined table of codes which identify conditions under which acknowledgments are required to be returned in response to a message.
Committee: | Infrastructure And Messaging Work Group
OID: | 2.16.840.1.113883.4.642.1.844 (for OID based terminology systems)
Source Resource | XML / JSON

This Code system is used in the following value sets:

* messageheader-response-request (HL7-defined table of codes which identify conditions under which acknowledgments are required to be returned in response to a message.)

4.2.12.844.1 Content

4.2.12.844.2 messageheader-response-request

HL7-defined table of codes which identify conditions under which acknowledgments are required to be returned in response to a message.

This code system http://hl7.org/fhir/messageheader-response-request defines the following codes:

Code | Display | Definition
always | Always | initiator expects a response for this message
on-error | Error/reject conditions only | initiator expects a response only if in error
never | Never | initiator does not expect a response
on-success | Successful completion only | initiator expects a response only if successful

See the full registry of value sets defined as part of FHIR.

Explanation of the columns that may appear on this page:

Level | A few code lists that FHIR defines are hierarchical - each code is assigned a level. In this scheme, some codes are under other codes, and imply that the code they are under also applies
Source | The source of the definition of the code (when the value set draws in codes defined elsewhere)
Code | The code (used as the code in the resource instance). If the code is in italics, this indicates that the code is not selectable ('Abstract')
Display | The display (used in the display element of a Coding). If there is no display, implementers should not simply display the code, but map the concept into their application
Definition | An explanation of the meaning of the concept
Comments | Additional notes about how to use the code

4.2.12.847 Code System http://hl7.org/fhir/question-max-occurs

URL: https://hl7.org/fhir/STU3/codesystem-question-max-occurs.html

This page is part of the FHIR Specification (v3.0.2: STU 3). The current version which supercedes this version is 4.0.1. For a full list of available versions, see the Directory of published versions

Vocabulary Work Group | Maturity Level: 0 | Informative | Use Context: Any

This is a code system defined by the FHIR project.

Summary

Defining URL: | http://hl7.org/fhir/question-max-occurs
Name: | MaxOccurs
Definition: | Flags an element as having unlimited repetitions
Committee: | FHIR Infrastructure Work Group
OID: | 2.16.840.1.113883.4.642.1.847 (for OID based terminology systems)
Source Resource | XML / JSON

This Code system is used in the following value sets:

* MaxOccurs (Flags an element as having unlimited repetitions)

4.2.12.847.1 Content

4.2.12.847.2 MaxOccurs

Flags an element as having unlimited repetitions

This code system http://hl7.org/fhir/question-max-occurs defines the following codes:

Code | Display | Definition
* | Repeating | Element can repeat an unlimited number of times

See the full registry of value sets defined as part of FHIR.

Explanation of the columns that may appear on this page:

Level | A few code lists that FHIR defines are hierarchical - each code is assigned a level. In this scheme, some codes are under other codes, and imply that the code they are under also applies
Source | The source of the definition of the code (when the value set draws in codes defined elsewhere)
Code | The code (used as the code in the resource instance). If the code is in italics, this indicates that the code is not selectable ('Abstract')
Display | The display (used in the display element of a Coding). If there is no display, implementers should not simply display the code, but map the concept into their application
Definition | An explanation of the meaning of the concept
Comments | Additional notes about how to use the code

4.2.12.849 Code System http://hl7.org/fhir/questionnaire-item-control

URL: https://hl7.org/fhir/STU3/codesystem-questionnaire-item-control.html

This page is part of the FHIR Specification (v3.0.2: STU 3). The current version which supercedes this version is 4.0.1. For a full list of available versions, see the Directory of published versions

Vocabulary Work Group | Maturity Level: 0 | Informative | Use Context: Not Intended for Production use

This is a code system defined at http://www.hl7.org/Special/committees/patientcare .

Summary

Defining URL: | http://hl7.org/fhir/questionnaire-item-control
Name: | Questionnaire Item UI Control Codes

Definition: | Starter set of user interface control/display mechanisms that might be used when rendering an item in a questionnaire.
Committee: | FHIR Infrastructure Work Group
OID: | 2.16.840.1.113883.4.642.1.849 (for OID based terminology systems)
Source Resource | XML / JSON

This Code system is used in the following value sets:

* Questionnaire Item UI Control Codes (Starter set of user interface control/display mechanisms that might be used when rendering an item in a questionnaire.)

4.2.12.849.1 Content

4.2.12.849.2 Questionnaire Item UI Control Codes

Starter set of user interface control/display mechanisms that might be used when rendering an item in a questionnaire.

Properties

Code | URL | Description | Type
abstract | | True if an element is considered 'abstract' - that is the code is not for use as a real concept | boolean

This code system http://hl7.org/fhir/questionnaire-item-control defines the following codes:

Lvl | Code | Display | Definition
1 | group | | UI controls relevant to organizing groups of questions
2 | list | List | Questions within the group should be listed sequentially
2 | table | Table | Questions within the group are rows in the table with possible answers as columns
2 | header | Header | The group is to be continuously visible at the top of the questionnaire
2 | footer | Footer | The group is to be continuously visible at the bottom of the questionnaire
1 | text | | UI controls relevant to rendering questionnaire text items
2 | inline | In-line | Text is displayed as a paragraph in a sequential position between sibling items (default behavior)
2 | prompt | Prompt | Text is displayed immediately below or within the answer-entry area of the containing question item (typically as a guide for what to enter)
2 | unit | Unit | Text is displayed adjacent (horizontally or vertically) to the answer space for the parent question, typically to indicate a unit of measure
2 | lower | Lower-bound | Text is displayed to the left of the set of answer choices or a scaling control for the parent question item to indicate the meaning of the 'lower' bound. E.g. 'Strongly disagree'
2 | upper | Upper-bound | Text is displayed to the right of the set of answer choices or a scaling control for the parent question item to indicate the meaning of the 'upper' bound. E.g. 'Strongly agree'
2 | flyover | Fly-over | Text is temporarily visible over top of an item if the mouse is positioned over top of the text for the containing item
2 | help | Help-Button | Text is displayed in a dialog box or similar control if invoked by pushing a button or some other UI-appropriate action to request 'help' for a question, group or the questionnaire as a whole (depending what the text is nested within)
1 | question | | UI controls relevant to capturing question data
2 | autocomplete | Auto-complete | A control which provides a list of potential matches based on text entered into a control. Used for large choice sets where text-matching is an appropriate discovery mechanism.
2 | drop-down | Drop down | A control where an item (or multiple items) can be selected from a list that is only displayed when the user is editing the field.
2 | check-box | Check-box | A control where choices are listed with a box beside them. The box can be toggled to select or de-select a given choice. Multiple selections may be possible.
2 | lookup | Lookup | A control where editing an item spawns a separate dialog box or screen permitting a user to navigate, filter or otherwise discover an appropriate match. Useful for large choice sets where text matching is not an appropriate discovery mechanism. Such screens must generally be tuned for the specific choice list structure.
2 | radio-button | Radio Button | A control where choices are listed with a button beside them. The button can be toggled to select or de-select a given choice. Selecting one item deselects all others.
2 | slider | Slider | A control where an axis is displayed between the high and low values and the control can be visually manipulated to select a value anywhere on the axis.
2 | spinner | Spinner | A control where a list of numeric or other ordered values can be scrolled through via arrows.
2 | text-box | Text Box | A control where a user can type in their answer freely.

See the full registry of value sets defined as part of FHIR.

Explanation of the columns that may appear on this page:

Level | A few code lists that FHIR defines are hierarchical - each code is assigned a level. In this scheme, some codes are under other codes, and imply that the code they are under also applies
Source | The source of the definition of the code (when the value set draws in codes defined elsewhere)
Code | The code (used as the code in the resource instance). If the code is in italics, this indicates that the code is not selectable ('Abstract')
Display | The display (used in the display element of a Coding). If there is no display, implementers should not simply display the code, but map the concept into their application
Definition | An explanation of the meaning of the concept
Comments | Additional notes about how to use the code

4.2.12.851 Code System http://hl7.org/fhir/choice-list-orientation

URL: https://hl7.org/fhir/STU3/codesystem-choice-list-orientation.html

This page is part of the FHIR Specification (v3.0.2: STU 3). The current version which supercedes this version is 4.0.1. For a full list of available versions, see the Directory of published versions

Vocabulary Work Group | Maturity Level: 0 | Informative | Use Context: Any

This is a code system defined by the FHIR project.

Summary

Defining URL: | http://hl7.org/fhir/choice-list-orientation
Name: | ChoiceListOrientation
Definition: | Direction in which lists of question options should be displayed
Committee: | FHIR Infrastructure Work Group
OID: | 2.16.840.1.113883.4.642.1.851 (for OID based terminology systems)
Source Resource | XML / JSON

This Code system is used in the following value sets:

* ChoiceListOrientation (Direction in which lists of question options should be displayed)

4.2.12.851.1 Content

4.2.12.851.2 ChoiceListOrientation

Direction in which lists of question options should be displayed

This code system http://hl7.org/fhir/choice-list-orientation defines the following codes:

Code | Display | Definition
horizontal | Horizontal | List choices along the horizontal axis
vertical | Vertical | List choices down the vertical axis

See the full registry of value sets defined as part of FHIR.

Explanation of the columns that may appear on this page:

Level | A few code lists that FHIR defines are hierarchical - each code is assigned a level. In this scheme, some codes are under other codes, and imply that the code they are under also applies
Source | The source of the definition of the code (when the value set draws in codes defined elsewhere)
Code | The code (used as the code in the resource instance). If the code is in italics, this indicates that the code is not selectable ('Abstract')
Display | The display (used in the display element of a Coding). If there is no display, implementers should not simply display the code, but map the concept into their application
Definition | An explanation of the meaning of the concept
Comments | Additional notes about how to use the code

4.2.12.853 Code System http://hl7.org/fhir/questionnaire-display-category

URL: https://hl7.org/fhir/STU3/codesystem-questionnaire-display-category.html

This page is part of the FHIR Specification (v3.0.2: STU 3). The current version which supercedes this version is 4.0.1. For a full list of available versions, see the Directory of published versions

Vocabulary Work Group | Maturity Level: 0 | Informative | Use Context: Not Intended for Production use

This is a code system defined at http://www.hl7.org/Special/committees/patientcare .

Summary

Defining URL: | http://hl7.org/fhir/questionnaire-display-category
Name: | Questionnaire Text Categories
Definition: | Codes defining the purpose of a Questionnaire item of type 'text'.
Committee: | FHIR Infrastructure Work Group
OID: | 2.16.840.1.113883.4.642.1.853 (for OID based terminology systems)
Source Resource | XML / JSON

This Code system is used in the following value sets:

* Questionnaire Text Categories (Codes defining the purpose of a Questionnaire item of type 'text'.)

4.2.12.853.1 Content

4.2.12.853.2 Questionnaire Text Categories

Codes defining the purpose of a Questionnaire item of type 'text'.

This code system http://hl7.org/fhir/questionnaire-display-category defines the following codes:

Code | Display | Definition
instructions | Instructions | The text provides guidances on how to populate or use a portion of the questionnaire (or the questionnaire as a whole).
security | Security | The text provides guidance on how the information should be or will be handled from a security/confidentiality/access control perspective when completed

See the full registry of value sets defined as part of FHIR.

Explanation of the columns that may appear on this page:

Level | A few code lists that FHIR defines are hierarchical - each code is assigned a level. In this scheme, some codes are under other codes, and imply that the code they are under also applies
Source | The source of the definition of the code (when the value set draws in codes defined elsewhere)
Code | The code (used as the code in the resource instance). If the code is in italics, this indicates that the code is not selectable ('Abstract')
Display | The display (used in the display element of a Coding). If there is no display, implementers should not simply display the code, but map the concept into their application
Definition | An explanation of the meaning of the concept

Comments | Additional notes about how to use the code

4.2.12.855 Code System http://hl7.org/fhir/questionnaire-usage-mode

URL: https://hl7.org/fhir/STU3/codesystem-questionnaire-usage-mode.html

This page is part of the FHIR Specification (v3.0.2: STU 3). The current version which supercedes this version is 4.0.1. For a full list of available versions, see the Directory of published versions

Vocabulary Work Group | Maturity Level: 0 | Informative | Use Context: Any

This is a code system defined by the FHIR project.

Summary

Defining URL: | http://hl7.org/fhir/questionnaire-usage-mode
Name: | QuestionnaireItemUsageMode
Definition: | Identifies the modes of usage of a questionnaire that should enable a particular questionnaire item
Committee: | FHIR Infrastructure Work Group
OID: | 2.16.840.1.113883.4.642.1.855 (for OID based terminology systems)
Source Resource | XML / JSON

This Code system is used in the following value sets:

* QuestionnaireItemUsageMode (Identifies the modes of usage of a questionnaire that should enable a particular questionnaire item)

4.2.12.855.1 Content

4.2.12.855.2 QuestionnaireItemUsageMode

Identifies the modes of usage of a questionnaire that should enable a particular questionnaire item

This code system http://hl7.org/fhir/questionnaire-usage-mode defines the following codes:

Code | Display | Definition
capture-display | Capture & Display | Render the item regardless of usage mode
capture | Capture Only | Render the item only when capturing data
display | Display Only | Render the item only when displaying a completed form
display-non-empty | Display when Answered | Render the item only when displaying a completed form and the item has been answered (or has child items that have been answered)
capture-display-non-empty | Capture or, if answered, Display | Render the item when capturing data or when displaying a completed form and the item has been answered (or has child items that have been answered)

See the full registry of value sets defined as part of FHIR.

Explanation of the columns that may appear on this page:

Level | A few code lists that FHIR defines are hierarchical - each code is assigned a level. In this scheme, some codes are under other codes, and imply that the code they are under also applies
Source | The source of the definition of the code (when the value set draws in codes defined elsewhere)
Code | The code (used as the code in the resource instance). If the code is in italics, this indicates that the code is not selectable ('Abstract')
Display | The display (used in the display element of a Coding). If there is no display, implementers should not simply display the code, but map the concept into their application
Definition | An explanation of the meaning of the concept
Comments | Additional notes about how to use the code

4.2.12.858 Code System http://hl7.org/fhir/allerg-intol-substance-exp-risk

URL: https://hl7.org/fhir/STU3/codesystem-allerg-intol-substance-exp-risk.html

This page is part of the FHIR Specification (v3.0.2: STU 3). The current version which supercedes this version is 4.0.1. For a full list of available versions, see the Directory of published versions

Vocabulary Work Group | Maturity Level: 0 | Informative | Use Context: Any

This is a code system defined by the FHIR project.

Summary

Defining URL: | http://hl7.org/fhir/allerg-intol-substance-exp-risk
Name: | AllergyIntoleranceSubstanceExposureRisk
Definition: | The risk of an adverse reaction (allergy or intolerance) for this patient upon exposure to the substance (including pharmaceutical products).
Committee: | Patient Care Work Group
OID: | 2.16.840.1.113883.4.642.1.858 (for OID based terminology systems)
Source Resource | XML / JSON

This Code system is used in the following value sets:

* AllergyIntoleranceSubstanceExposureRisk (The risk of an adverse reaction (allergy or intolerance) for this patient upon exposure to the substance (including pharmaceutical products).)

4.2.12.858.1 Content

4.2.12.858.2 AllergyIntoleranceSubstanceExposureRisk

The risk of an adverse reaction (allergy or intolerance) for this patient upon exposure to the substance (including pharmaceutical products).

This code system http://hl7.org/fhir/allerg-intol-substance-exp-risk defines the following codes:

Code | Display | Definition
known-reaction-risk | Known Reaction Risk | Known risk of allergy or intolerance reaction upon exposure to the specified substance.
no-known-reaction-risk | No Known Reaction Risk | No known risk of allergy or intolerance reaction upon exposure to the specified substance.

See the full registry of value sets defined as part of FHIR.

Explanation of the columns that may appear on this page:

Level | A few code lists that FHIR defines are hierarchical - each code is assigned a level. In this scheme, some codes are under other codes, and imply that the code they are under also applies
Source | The source of the definition of the code (when the value set draws in codes defined elsewhere)
Code | The code (used as the code in the resource instance). If the code is in italics, this indicates that the code is not selectable ('Abstract')
Display | The display (used in the display element of a Coding). If there is no display, implementers should not simply display the code, but map the concept into their application
Definition | An explanation of the meaning of the concept
Comments | Additional notes about how to use the code

4.2.12.860 Code System http://hl7.org/fhir/reaction-event-certainty

URL: https://hl7.org/fhir/STU3/codesystem-reaction-event-certainty.html

This page is part of the FHIR Specification (v3.0.2: STU 3). The current version which supercedes this version is 4.0.1. For a full list of available versions, see the Directory of published versions

Vocabulary Work Group | Maturity Level: 0 | Informative | Use Context: Any

This is a code system defined by the FHIR project.

Summary

Defining URL: | http://hl7.org/fhir/reaction-event-certainty
Name: | AllergyIntoleranceCertainty
Definition: | Statement about the degree of clinical certainty that a specific substance was the cause of the manifestation in a reaction event.
Committee: | Patient Care Work Group
OID: | 2.16.840.1.113883.4.642.1.860 (for OID based terminology systems)
Source Resource | XML / JSON

This Code system is used in the following value sets:

* AllergyIntoleranceCertainty (Statement about the degree of clinical certainty that a specific substance was the cause of the manifestation in a reaction event.)

4.2.12.860.1 Content

4.2.12.860.2 AllergyIntoleranceCertainty

Statement about the degree of clinical certainty that a specific substance was the cause of the manifestation in a reaction event.

This code system http://hl7.org/fhir/reaction-event-certainty defines the following codes:

Code | Display | Definition
unlikely | Unlikely | There is a low level of clinical certainty that the reaction was caused by the identified substance.
likely | Likely | There is a high level of clinical certainty that the reaction was caused by the identified substance.
confirmed | Confirmed | There is a very high level of clinical certainty that the reaction was due to the identified substance, which may include clinical evidence by testing or rechallenge.
unknown | Unknown | The clinical certainty that the reaction was caused by the identified substance is unknown. It is an explicit assertion that certainty is not known.

See the full registry of value sets defined as part of FHIR.

Explanation of the columns that may appear on this page:

Level | A few code lists that FHIR defines are hierarchical - each code is assigned a level. In this scheme, some codes are under other codes, and imply that the code they are under also applies
Source | The source of the definition of the code (when the value set draws in codes defined elsewhere)
Code | The code (used as the code in the resource instance). If the code is in italics, this indicates that the code is not selectable ('Abstract')
Display | The display (used in the display element of a Coding). If there is no display, implementers should not simply display the code, but map the concept into their application
Definition | An explanation of the meaning of the concept
Comments | Additional notes about how to use the code

4.2.12.862 Code System http://hl7.org/fhir/hl7-work-group

URL: https://hl7.org/fhir/STU3/codesystem-hl7-work-group.html

This page is part of the FHIR Specification (v3.0.2: STU 3). The current version which supercedes this version is 4.0.1. For a full list of available versions, see the Directory of published versions

Vocabulary Work Group | Maturity Level: 0 | Informative | Use Context: Any

This is a code system defined by the FHIR project.

Summary

Defining URL: | http://hl7.org/fhir/hl7-work-group
Name: | HL7Workgroup
Definition: | An HL7 administrative unit that owns artifacts in the FHIR specification
Committee: | FHIR Infrastructure Work Group
OID: | 2.16.840.1.113883.4.642.1.862 (for OID based terminology systems)
Source Resource | XML / JSON

This Code system is used in the following value sets:

* HL7Workgroup (An HL7 administrative unit that owns artifacts in the FHIR specification)

4.2.12.862.1 Content

4.2.12.862.2 HL7Workgroup

An HL7 administrative unit that owns artifacts in the FHIR specification

This code system http://hl7.org/fhir/hl7-work-group defines the following codes:

Code | Display | Definition
cbcc | Community Based Collaborative Care | Community Based Collaborative Care (http://www.hl7.org/Special/committees/cbcc/index.cfm)
cds | Clinical Decision Support | Clinical Decision Support (http://www.hl7.org/Special/committees/dss/index.cfm)
cqi | Clinical Quality Information | Clinical Quality Information (http://www.hl7.org/Special/committees/cqi/index.cfm)
cg | Clinical Genomics | Clinical Genomics (http://www.hl7.org/Special/committees/clingenomics/index.cfm)
dev | Health Care Devices | Health Care Devices (http://www.hl7.org/Special/committees/healthcaredevices/index.cfm)
ehr | Electronic Health Records | Electronic Health Records (http://www.hl7.org/special/committees/ehr/index.cfm)
fhir | FHIR Infrastructure | FHIR Infrastructure (http://www.hl7.org/Special/committees/fiwg/index.cfm)
fm | Financial Management | Financial Management (http://www.hl7.org/Special/committees/fm/index.cfm)
hsi | Health Standards Integration | Health Standards Integration (http://www.hl7.org/Special/committees/hsi/index.cfm)
ii | Imaging Integration | Imaging Integration (http://www.hl7.org/Special/committees/imagemgt/index.cfm)
inm | Infrastructure And Messaging | Infrastructure And Messaging (http://www.hl7.org/special/committees/inm/index.cfm)
its | Implementable Technology Specifications | Implementable Technology Specifications (http://www.hl7.org/special/committees/xml/index.cfm)
oo | Orders and Observations | Orders and Observations (http://www.hl7.org/Special/committees/orders/index.cfm)
pa | Patient Administration | Patient Administration (http://www.hl7.org/Special/committees/pafm/index.cfm)
pc | Patient Care | Patient Care (http://www.hl7.org/Special/committees/patientcare/index.cfm)
pher | Public Health and Emergency Response | Public Health and Emergency Response (http://www.hl7.org/Special/committees/pher/index.cfm)
phx | Pharmacy | Pharmacy (http://www.hl7.org/Special/committees/medication/index.cfm)
rcrim | Regulated Clinical Research Information Management | Regulated Clinical Research Information Management (http://www.hl7.org/Special/committees/rcrim/index.cfm)
sd | Structured Documents | Structured Documents (http://www.hl7.org/Special/committees/structure/index.cfm)
sec | Security | Security (http://www.hl7.org/Special/committees/secure/index.cfm)
us | US Realm Taskforce | US Realm Taskforce (http://wiki.hl7.org/index.php?title=US_Realm_Task_Force)
vocab | Vocabulary | Vocabulary (http://www.hl7.org/Special/committees/Vocab/index.cfm)
aid | Application Implementation and Design | Application Implementation and Design (http://www.hl7.org/Special/committees/java/index.cfm)

See the full registry of value sets defined as part of FHIR.

Explanation of the columns that may appear on this page:

Level | A few code lists that FHIR defines are hierarchical - each code is assigned a level. In this scheme, some codes are under other codes, and imply that the code they are under also applies
Source | The source of the definition of the code (when the value set draws in codes defined elsewhere)
Code | The code (used as the code in the resource instance). If the code is in italics, this indicates that the code is not selectable ('Abstract')
Display | The display (used in the display element of a Coding). If there is no display, implementers should not simply display the code, but map the concept into their application
Definition | An explanation of the meaning of the concept
Comments | Additional notes about how to use the code

4.2.12.864 Code System http://hl7.org/fhir/procedure-progress-status-code

URL: https://hl7.org/fhir/STU3/codesystem-procedure-progress-status-codes.html

This page is part of the FHIR Specification (v3.0.2: STU 3). The current version which supercedes this version is 4.0.1. For a full list of available versions, see the Directory of published versions

Vocabulary Work Group | Maturity Level: 0 | Informative | Use Context: Not Intended for Production use

This is a code system defined by the FHIR project.

Summary

Defining URL: | http://hl7.org/fhir/procedure-progress-status-code
Name: | Procedure Progress Status Codes

Definition: | This value set is provided as an example. The value set to instantiate this attribute should be drawn from a robust terminology code system that consists of or contains concepts to support the procedure performance process.
Committee: | Patient Care Work Group
OID: | 2.16.840.1.113883.4.642.1.864 (for OID based terminology systems)
Source Resource | XML / JSON

This Code system is used in the following value sets:

* Procedure Progress Status Codes (This value set is provided as an example. The value set to instantiate this attribute should be drawn from a robust terminology code system that consists of or contains concepts to support the procedure performance process.)

4.2.12.864.1 Content

4.2.12.864.2 Procedure Progress Status Codes

This value set is provided as an example. The value set to instantiate this attribute should be drawn from a robust terminology code system that consists of or contains concepts to support the procedure performance process.

This code system http://hl7.org/fhir/procedure-progress-status-code defines the following codes:

Code | Display | Definition
in-operating-room | In Operating Room | A patient is in the Operating Room.
prepared | Prepared | The patient is prepared for a procedure.
anesthesia-induced | Anesthesia Induced | The patient is under anesthesia.
open-incision | Open Incision | The patient has open incision(s).
closed-incision | Closed Incision | The patient has incision(s) closed.
in-recovery-room | In Recovery Room | The patient is in the recovery room.

See the full registry of value sets defined as part of FHIR.

Explanation of the columns that may appear on this page:

Level | A few code lists that FHIR defines are hierarchical - each code is assigned a level. In this scheme, some codes are under other codes, and imply that the code they are under also applies
Source | The source of the definition of the code (when the value set draws in codes defined elsewhere)
Code | The code (used as the code in the resource instance). If the code is in italics, this indicates that the code is not selectable ('Abstract')
Display | The display (used in the display element of a Coding). If there is no display, implementers should not simply display the code, but map the concept into their application
Definition | An explanation of the meaning of the concept
Comments | Additional notes about how to use the code

4.2.12.866 Code System http://hl7.org/fhir/implant-status

URL: https://hl7.org/fhir/STU3/codesystem-implant-status.html

This page is part of the FHIR Specification (v3.0.2: STU 3). The current version which supercedes this version is 4.0.1. For a full list of available versions, see the Directory of published versions

Vocabulary Work Group | Maturity Level: 0 | Informative | Use Context: Any

This is a code system defined by the FHIR project.

Summary

Defining URL: | http://hl7.org/fhir/implant-status
Name: | Implant Status
Definition: | A set codes that define the functional status of an implanted device.
Committee: | Orders and Observations Work Group
OID: | 2.16.840.1.113883.4.642.1.866 (for OID based terminology systems)
Source Resource | XML / JSON

This Code system is used in the following value sets:

* Implant Status (A set codes that define the functional status of an implanted device.)

4.2.12.866.1 Content

4.2.12.866.2 Implant Status

A set codes that define the functional status of an implanted device.

This code system http://hl7.org/fhir/implant-status defines the following codes:

Code | Display | Definition
functional | Functional | The implanted device is working normally
non-functional | Non-Functional | The implanted device is not working
disabled | Disabled | The implanted device has been turned off
unknown | Unknown | the functional status of the implant has not been determined

See the full registry of value sets defined as part of FHIR.

Explanation of the columns that may appear on this page:

Level | A few code lists that FHIR defines are hierarchical - each code is assigned a level. In this scheme, some codes are under other codes, and imply that the code they are under also applies
Source | The source of the definition of the code (when the value set draws in codes defined elsewhere)
Code | The code (used as the code in the resource instance). If the code is in italics, this indicates that the code is not selectable ('Abstract')
Display | The display (used in the display element of a Coding). If there is no display, implementers should not simply display the code, but map the concept into their application
Definition | An explanation of the meaning of the concept
Comments | Additional notes about how to use the code

4.2.12.868 Code System http://hl7.org/fhir/flag-priority-code

URL: https://hl7.org/fhir/STU3/codesystem-flag-priority.html

This page is part of the FHIR Specification (v3.0.2: STU 3). The current version which supercedes this version is 4.0.1. For a full list of available versions, see the Directory of published versions

Vocabulary Work Group | Maturity Level: 0 | Informative | Use Context: Not Intended for Production use

This is a code system defined by the FHIR project.

Summary

Defining URL: | http://hl7.org/fhir/flag-priority-code
Name: | Flag Priority Codes
Definition: | This value set is provided as an exemplar. The value set is driven by IHE Table B.8-4: Abnormal Flags, Alert Priority.
Committee: | Patient Care Work Group
OID: | 2.16.840.1.113883.4.642.1.868 (for OID based terminology systems)
Source Resource | XML / JSON

This Code system is used in the following value sets:

* Flag Priority Codes (This value set is provided as an exemplar. The value set is driven by IHE Table B.8-4: Abnormal Flags, Alert Priority.)

4.2.12.868.1 Content

4.2.12.868.2 Flag Priority Codes

This value set is provided as an exemplar. The value set is driven by IHE Table B.8-4: Abnormal Flags, Alert Priority.

This code system http://hl7.org/fhir/flag-priority-code defines the following codes:

Code | Display | Definition
PN | No alarm | No alarm.
PL | Low priority | Low priority.
PM | Medium priority | Medium priority.
PH | High priority | High priority.

See the full registry of value sets defined as part of FHIR.

Explanation of the columns that may appear on this page:

Level | A few code lists that FHIR defines are hierarchical - each code is assigned a level. In this scheme, some codes are under other codes, and imply that the code they are under also applies
Source | The source of the definition of the code (when the value set draws in codes defined elsewhere)
Code | The code (used as the code in the resource instance). If the code is in italics, this indicates that the code is not selectable ('Abstract')
Display | The display (used in the display element of a Coding). If there is no display, implementers should not simply display the code, but map the concept into their application
Definition | An explanation of the meaning of the concept
Comments | Additional notes about how to use the code

4.2.12.876 Code System http://hl7.org/fhir/classification-or-context

URL: https://hl7.org/fhir/STU3/codesystem-classification-or-context.html

This page is part of the FHIR Specification (v3.0.2: STU 3). The current version which supercedes this version is 4.0.1. For a full list of available versions, see the Directory of published versions

Vocabulary Work Group | Maturity Level: 0 | Informative | Use Context: Any

This is a code system defined by the FHIR project.

Summary

Defining URL: | http://hl7.org/fhir/classification-or-context
Name: | ClassificationOrContext
Definition: | Identifies whether a useContext represents a context or classification for the element
Committee: | Orders and Observations Work Group
OID: | 2.16.840.1.113883.4.642.1.876 (for OID based terminology systems)
Source Resource | XML / JSON

This Code system is used in the following value sets:

* ClassificationOrContext (Identifies whether a useContext represents a context or classification for the element)

4.2.12.876.1 Content

4.2.12.876.2 ClassificationOrContext

Identifies whether a useContext represents a context or classification for the element

This code system http://hl7.org/fhir/classification-or-context defines the following codes:

Code | Display | Definition
classification | Classification | Indicates the useContext is a classification - e.g. Administrative, financial, etc.
context | Context | Indicates the useContext is a context - a domain of use - e.g. Particular country, organization or system

See the full registry of value sets defined as part of FHIR.

Explanation of the columns that may appear on this page:

Level | A few code lists that FHIR defines are hierarchical - each code is assigned a level. In this scheme, some codes are under other codes, and imply that the code they are under also applies
Source | The source of the definition of the code (when the value set draws in codes defined elsewhere)
Code | The code (used as the code in the resource instance). If the code is in italics, this indicates that the code is not selectable ('Abstract')
Display | The display (used in the display element of a Coding). If there is no display, implementers should not simply display the code, but map the concept into their application
Definition | An explanation of the meaning of the concept
Comments | Additional notes about how to use the code

4.2.12.878 Code System http://hl7.org/fhir/condition-state

URL: https://hl7.org/fhir/STU3/codesystem-condition-state.html

This page is part of the FHIR Specification (v3.0.2: STU 3). The current version which supercedes this version is 4.0.1. For a full list of available versions, see the Directory of published versions

Vocabulary Work Group | Maturity Level: 0 | Informative | Use Context: Any

This is a code system defined by the FHIR project.

Summary

Defining URL: | http://hl7.org/fhir/condition-state
Name: | ConditionState
Definition: | Enumeration indicating whether the condition is currently active, inactive, or has been resolved.
Committee: | Patient Care Work Group
OID: | 2.16.840.1.113883.4.642.1.878 (for OID based terminology systems)
Source Resource | XML / JSON

This Code system is used in the following value sets:

* ConditionState (Enumeration indicating whether the condition is currently active, inactive, or has been resolved.)

4.2.12.878.1 Content

4.2.12.878.2 ConditionState

Enumeration indicating whether the condition is currently active, inactive, or has been resolved.

This code system http://hl7.org/fhir/condition-state defines the following codes:

Code | Display | Definition
active | Active | The condition is active.
inactive | Inactive | The condition is inactive, but not resolved.
resolved | Resolved | The condition is resolved.

See the full registry of value sets defined as part of FHIR.

Explanation of the columns that may appear on this page:

Level | A few code lists that FHIR defines are hierarchical - each code is assigned a level. In this scheme, some codes are under other codes, and imply that the code they are under also applies
Source | The source of the definition of the code (when the value set draws in codes defined elsewhere)
Code | The code (used as the code in the resource instance). If the code is in italics, this indicates that the code is not selectable ('Abstract')
Display | The display (used in the display element of a Coding). If there is no display, implementers should not simply display the code, but map the concept into their application
Definition | An explanation of the meaning of the concept
Comments | Additional notes about how to use the code

4.2.12.883 Code System http://hl7.org/fhir/match-grade

URL: https://hl7.org/fhir/STU3/codesystem-match-grade.html

This page is part of the FHIR Specification (v3.0.2: STU 3). The current version which supercedes this version is 4.0.1. For a full list of available versions, see the Directory of published versions

Vocabulary Work Group | Maturity Level: 0 | Informative | Use Context: Any

This is a code system defined by the FHIR project.

Summary

Defining URL: | http://hl7.org/fhir/match-grade
Name: | MatchGrade
Definition: | A Master Patient Index (MPI) assessment of whether a candidate patient record is a match or not.
Committee: | FHIR Infrastructure Work Group
OID: | 2.16.840.1.113883.4.642.1.883 (for OID based terminology systems)
Source Resource | XML / JSON

This Code system is used in the following value sets:

* MatchGrade (A Master Patient Index (MPI) assessment of whether a candidate patient record is a match or not.)

4.2.12.883.1 Content

4.2.12.883.2 MatchGrade

A Master Patient Index (MPI) assessment of whether a candidate patient record is a match or not.

This code system http://hl7.org/fhir/match-grade defines the following codes:

Code | Display | Definition
certain | Certain Match | This record meets the matching criteria to be automatically considered as a full match.
probable | Probable Match | This record is a close match, but not a certain match. Additional review (e.g. by a human) may be required before using this as a match.
possible | Possible Match | This record may be a matching one. Additional review (e.g. by a human) SHOULD be performed before using this as a match.
certainly-not | Certainly Not a Match | This record is known not to be a match. Note that usually non-matching records are not returned, but in some cases records previously or likely considered as a match may specifically be negated by the matching engine

See the full registry of value sets defined as part of FHIR.

Explanation of the columns that may appear on this page:

Level | A few code lists that FHIR defines are hierarchical - each code is assigned a level. In this scheme, some codes are under other codes, and imply that the code they are under also applies
Source | The source of the definition of the code (when the value set draws in codes defined elsewhere)
Code | The code (used as the code in the resource instance). If the code is in italics, this indicates that the code is not selectable ('Abstract')
Display | The display (used in the display element of a Coding). If there is no display, implementers should not simply display the code, but map the concept into their application
Definition | An explanation of the meaning of the concept
Comments | Additional notes about how to use the code

4.2.12.887 Code System http://hl7.org/fhir/evidence-quality

URL: https://hl7.org/fhir/STU3/codesystem-cqif-evidence-quality.html

This page is part of the FHIR Specification (v3.0.2: STU 3). The current version which supercedes this version is 4.0.1. For a full list of available versions, see the Directory of published versions

Vocabulary Work Group | Maturity Level: 0 | Informative | Use Context: Any

This is a code system defined by the FHIR project.

Summary

Defining URL: | http://hl7.org/fhir/evidence-quality
Name: | QualityOfEvidenceRating
Definition: | A rating system that describes the quality of evidence such as the GRADE, DynaMed, or Oxford CEBM systems
Committee: | Clinical Decision Support Work Group
OID: | 2.16.840.1.113883.4.642.1.887 (for OID based terminology systems)
Source Resource | XML / JSON

This Code system is used in the following value sets:

* QualityOfEvidenceRating (A rating system that describes the quality of evidence such as the GRADE, DynaMed, or Oxford CEBM systems)

4.2.12.887.1 Content

4.2.12.887.2 QualityOfEvidenceRating

A rating system that describes the quality of evidence such as the GRADE, DynaMed, or Oxford CEBM systems

This code system http://hl7.org/fhir/evidence-quality defines the following codes:

Code | Display | Definition
high | High quality | High quality evidence
moderate | Moderate quality | Moderate quality evidence
low | Low quality | Low quality evidence
very-low | Very low quality | Very low quality evidence

See the full registry of value sets defined as part of FHIR.

Explanation of the columns that may appear on this page:

Level | A few code lists that FHIR defines are hierarchical - each code is assigned a level. In this scheme, some codes are under other codes, and imply that the code they are under also applies
Source | The source of the definition of the code (when the value set draws in codes defined elsewhere)
Code | The code (used as the code in the resource instance). If the code is in italics, this indicates that the code is not selectable ('Abstract')
Display | The display (used in the display element of a Coding). If there is no display, implementers should not simply display the code, but map the concept into their application
Definition | An explanation of the meaning of the concept
Comments | Additional notes about how to use the code

4.2.12.889 Code System http://hl7.org/fhir/recommendation-strength

URL: https://hl7.org/fhir/STU3/codesystem-cqif-recommendation-strength.html

This page is part of the FHIR Specification (v3.0.2: STU 3). The current version which supercedes this version is 4.0.1. For a full list of available versions, see the Directory of published versions

Vocabulary Work Group | Maturity Level: 0 | Informative | Use Context: Any

This is a code system defined by the FHIR project.

Summary

Defining URL: | http://hl7.org/fhir/recommendation-strength
Name: | StrengthOfRecommendationRating
Definition: | A rating system that describes the strength of the recommendation, such as the GRADE, DynaMed, or HGPS systems
Committee: | Clinical Decision Support Work Group
OID: | 2.16.840.1.113883.4.642.1.889 (for OID based terminology systems)
Source Resource | XML / JSON

This Code system is used in the following value sets:

* StrengthOfRecommendationRating (A rating system that describes the strength of the recommendation, such as the GRADE, DynaMed, or HGPS systems)

4.2.12.889.1 Content

4.2.12.889.2 StrengthOfRecommendationRating

A rating system that describes the strength of the recommendation, such as the GRADE, DynaMed, or HGPS systems

This code system http://hl7.org/fhir/recommendation-strength defines the following codes:

Code | Display | Definition
strong | Strong | Strong recommendation
weak | Weak | Weak recommendation

See the full registry of value sets defined as part of FHIR.

Explanation of the columns that may appear on this page:

Level | A few code lists that FHIR defines are hierarchical - each code is assigned a level. In this scheme, some codes are under other codes, and imply that the code they are under also applies
Source | The source of the definition of the code (when the value set draws in codes defined elsewhere)
Code | The code (used as the code in the resource instance). If the code is in italics, this indicates that the code is not selectable ('Abstract')
Display | The display (used in the display element of a Coding). If there is no display, implementers should not simply display the code, but map the concept into their application
Definition | An explanation of the meaning of the concept
Comments | Additional notes about how to use the code

4.2.12.896 Code System http://hl7.org/fhir/operational-status

URL: https://hl7.org/fhir/STU3/codesystem-operational-status.html

This page is part of the FHIR Specification (v3.0.2: STU 3). The current version which supercedes this version is 4.0.1. For a full list of available versions, see the Directory of published versions

Vocabulary Work Group | Maturity Level: 1 | Informative | Use Context: Any

This is a code system defined by the FHIR project.

Summary

Defining URL: | http://hl7.org/fhir/operational-status
Name: | DeviceComponentOperationalStatus
Definition: | Codes representing the current status of the device - on, off, suspended, etc.
Committee: | Health Care Devices Work Group
OID: | 2.16.840.1.113883.4.642.1.896 (for OID based terminology systems)
Source Resource | XML / JSON

This Code system is used in the following value sets:

* DeviceComponentOperationalStatus (Codes representing the current status of the device - on, off, suspended, etc.)

4.2.12.896.1 Content

4.2.12.896.2 DeviceComponentOperationalStatus

Codes representing the current status of the device - on, off, suspended, etc.

This code system http://hl7.org/fhir/operational-status defines the following codes:

Code | Display | Definition
off | Off | The device is off.
on | On | The device is fully operational.
not-ready | Not Ready | The device is not ready.
standby | Standby | The device is ready but not actively operating.
transduc-discon | Transducer Diconnected | The device transducer is diconnected.
hw-discon | Hardware Disconnectd | The device hardware is disconnected.
entered-in-error | Entered In Error | The device was entered in error.

See the full registry of value sets defined as part of FHIR.

Explanation of the columns that may appear on this page:

Level | A few code lists that FHIR defines are hierarchical - each code is assigned a level. In this scheme, some codes are under other codes, and imply that the code they are under also applies
Source | The source of the definition of the code (when the value set draws in codes defined elsewhere)
Code | The code (used as the code in the resource instance). If the code is in italics, this indicates that the code is not selectable ('Abstract')
Display | The display (used in the display element of a Coding). If there is no display, implementers should not simply display the code, but map the concept into their application
Definition | An explanation of the meaning of the concept
Comments | Additional notes about how to use the code

4.2.12.898 Code System http://hl7.org/fhir/specification-type

URL: https://hl7.org/fhir/STU3/codesystem-specification-type.html

This page is part of the FHIR Specification (v3.0.2: STU 3). The current version which supercedes this version is 4.0.1. For a full list of available versions, see the Directory of published versions

Vocabulary Work Group | Maturity Level: 1 | Informative | Use Context: Any

This is a code system defined by the FHIR project.

Summary

Defining URL: | http://hl7.org/fhir/specification-type
Name: | DeviceSpecificationSpecType
Definition: | Codes for device specification types such as serial number, part number, hardware revision, software revision, etc.
Committee: | Health Care Devices Work Group
OID: | 2.16.840.1.113883.4.642.1.898 (for OID based terminology systems)
Source Resource | XML / JSON

This Code system is used in the following value sets:

* DeviceSpecificationSpecType (Codes for device specification types such as serial number, part number, hardware revision, software revision, etc.)

4.2.12.898.1 Content

4.2.12.898.2 DeviceSpecificationSpecType

Codes for device specification types such as serial number, part number, hardware revision, software revision, etc.

This code system http://hl7.org/fhir/specification-type defines the following codes:

Code | Display | Definition
unspecified | Unspecified Production Specification | Unspecified Production Specification - MDC_ID_PROD_SPEC_UNSPECIFIED
serial-number | Serial Number | Serial Number - MDC_ID_PROD_SPEC_SERIAL
part-number | Part Number | Part Number - MDC_ID_PROD_SPEC_PART
hardware-revision | Hardware Revision | Hardware Revision - MDC_ID_PROD_SPEC_HW
software-revision | Software Revision | Software Revision - MDC_ID_PROD_SPEC_SW
firmware-revision | Firmware Revision | Firmware Revision - MDC_ID_PROD_SPEC_FW
protocol-revision | Protocol Revision | Protocol Revision - MDC_ID_PROD_SPEC_PROTOCOL
gmdn | GMDN | GMDN - MDC_ID_PROD_SPEC_GMDN

See the full registry of value sets defined as part of FHIR.

Explanation of the columns that may appear on this page:

Level | A few code lists that FHIR defines are hierarchical - each code is assigned a level. In this scheme, some codes are under other codes, and imply that the code they are under also applies
Source | The source of the definition of the code (when the value set draws in codes defined elsewhere)
Code | The code (used as the code in the resource instance). If the code is in italics, this indicates that the code is not selectable ('Abstract')
Display | The display (used in the display element of a Coding). If there is no display, implementers should not simply display the code, but map the concept into their application
Definition | An explanation of the meaning of the concept
Comments | Additional notes about how to use the code

4.2.12.900 Code System http://hl7.org/fhir/parameter-group

URL: https://hl7.org/fhir/STU3/codesystem-parameter-group.html

This page is part of the FHIR Specification (v3.0.2: STU 3). The current version which supercedes this version is 4.0.1. For a full list of available versions, see the Directory of published versions

Vocabulary Work Group | Maturity Level: 1 | Informative | Use Context: Any

This is a code system defined by the FHIR project.

Summary

Defining URL: | http://hl7.org/fhir/parameter-group
Name: | DeviceComponentParameterGroup
Definition: | Codes identifying groupings of parameters; e.g. Cardiovascular.
Committee: | Health Care Devices Work Group
OID: | 2.16.840.1.113883.4.642.1.900 (for OID based terminology systems)
Source Resource | XML / JSON

This Code system is used in the following value sets:

* DeviceComponentParameterGroup (Codes identifying groupings of parameters; e.g. Cardiovascular.)

4.2.12.900.1 Content

4.2.12.900.2 DeviceComponentParameterGroup

Codes identifying groupings of parameters; e.g. Cardiovascular.

This code system http://hl7.org/fhir/parameter-group defines the following codes:

Code | Display | Definition
haemodynamic | Haemodynamic Parameter Group | Haemodynamic Parameter Group - MDC_PGRP_HEMO
ecg | ECG Parameter Group | ECG Parameter Group - MDC_PGRP_ECG
respiratory | Respiratory Parameter Group | Respiratory Parameter Group - MDC_PGRP_RESP
ventilation | Ventilation Parameter Group | Ventilation Parameter Group - MDC_PGRP_VENT
neurological | Neurological Parameter Group | Neurological Parameter Group - MDC_PGRP_NEURO
drug-delivery | Drug Delivery Parameter Group | Drug Delivery Parameter Group - MDC_PGRP_DRUG
fluid-chemistry | Fluid Chemistry Parameter Group | Fluid Chemistry Parameter Group - MDC_PGRP_FLUID
blood-chemistry | Blood Chemistry Parameter Group | Blood Chemistry Parameter Group - MDC_PGRP_BLOOD_CHEM
miscellaneous | Miscellaneous Parameter Group | Miscellaneous Parameter Group - MDC_PGRP_MISC

See the full registry of value sets defined as part of FHIR.

Explanation of the columns that may appear on this page:

Level | A few code lists that FHIR defines are hierarchical - each code is assigned a level. In this scheme, some codes are under other codes, and imply that the code they are under also applies
Source | The source of the definition of the code (when the value set draws in codes defined elsewhere)
Code | The code (used as the code in the resource instance). If the code is in italics, this indicates that the code is not selectable ('Abstract')
Display | The display (used in the display element of a Coding). If there is no display, implementers should not simply display the code, but map the concept into their application
Definition | An explanation of the meaning of the concept
Comments | Additional notes about how to use the code

4.2.12.903 Code System http://hl7.org/fhir/audit-entity-type

URL: https://hl7.org/fhir/STU3/codesystem-audit-entity-type.html

This page is part of the FHIR Specification (v3.0.2: STU 3). The current version which supercedes this version is 4.0.1. For a full list of available versions, see the Directory of published versions

Vocabulary Work Group | Maturity Level: 3 | Informative | Use Context: Not Intended for Production use

This is a code system defined by the FHIR project.

Summary

Defining URL: | http://hl7.org/fhir/audit-entity-type
Name: | AuditEventEntityType
Definition: | Code for the entity type involved in the audit event.
Committee: | Security Work Group
OID: | 2.16.840.1.113883.4.642.1.903 (for OID based terminology systems)
Source Resource | XML / JSON

This Code system is used in the following value sets:

* AuditEventEntityType (Code for the entity type involved in the audit event.)

4.2.12.903.1 Content

4.2.12.903.2 AuditEventEntityType

Code for the entity type involved in the audit event.

This code system http://hl7.org/fhir/audit-entity-type defines the following codes:

Code | Display | Definition
1 | Person | Person
2 | System Object | System Object
3 | Organization | Organization
4 | Other | Other

See the full registry of value sets defined as part of FHIR.

Explanation of the columns that may appear on this page:

Level | A few code lists that FHIR defines are hierarchical - each code is assigned a level. In this scheme, some codes are under other codes, and imply that the code they are under also applies
Source | The source of the definition of the code (when the value set draws in codes defined elsewhere)
Code | The code (used as the code in the resource instance). If the code is in italics, this indicates that the code is not selectable ('Abstract')
Display | The display (used in the display element of a Coding). If there is no display, implementers should not simply display the code, but map the concept into their application
Definition | An explanation of the meaning of the concept
Comments | Additional notes about how to use the code

4.2.12.null Code System http://hl7.org/fhir/resource-types

URL: https://hl7.org/fhir/STU3/codesystem-resource-types.html

This page is part of the FHIR Specification (v3.0.2: STU 3). The current version which supercedes this version is 4.0.1. For a full list of available versions, see the Directory of published versions

Vocabulary Work Group | Maturity Level: 4 | Informative | Use Context: Any

This is a code system defined by the FHIR project.

Summary

Defining URL: | http://hl7.org/fhir/resource-types
Name: | ResourceType
Definition: | One of the resource types defined as part of FHIR.
Committee: | FHIR Infrastructure Work Group
OID: | (for OID based terminology systems)
Source Resource | XML / JSON

This Code system is used in the following value sets:

* ResourceType (One of the resource types defined as part of FHIR.)

* AuditEventEntityType (Code for the entity type involved in the audit event.)

* FHIRDefinedType (Either a resource or a data type.)

* Consent Content Class (This value set includes the FHIR resource types, along with some other important content class codes)

* FHIRAllTypes (Either an abstract type, a resource or a data type.)

4.2.12.null.1 Content

4.2.12.null.2 ResourceType

One of the resource types defined as part of FHIR.

This code system http://hl7.org/fhir/resource-types defines the following codes:

Code | Display | Definition
Account | Account | A financial tool for tracking value accrued for a particular purpose. In the healthcare field, used to track charges for a patient, cost centers, etc.
ActivityDefinition | ActivityDefinition | This resource allows for the definition of some activity to be performed, independent of a particular patient, practitioner, or other performance context.
AdverseEvent | AdverseEvent | Actual or potential/avoided event causing unintended physical injury resulting from or contributed to by medical care, a research study or other healthcare setting factors that requires additional monitoring, treatment, or hospitalization, or that results in death.
AllergyIntolerance | AllergyIntolerance | Risk of harmful or undesirable, physiological response which is unique to an individual and associated with exposure to a substance.
Appointment | Appointment | A booking of a healthcare event among patient(s), practitioner(s), related person(s) and/or device(s) for a specific date/time. This may result in one or more Encounter(s).
AppointmentResponse | AppointmentResponse | A reply to an appointment request for a patient and/or practitioner(s), such as a confirmation or rejection.
AuditEvent | AuditEvent | A record of an event made for purposes of maintaining a security log. Typical uses include detection of intrusion attempts and monitoring for inappropriate usage.
Basic | Basic | Basic is used for handling concepts not yet defined in FHIR, narrative-only resources that don't map to an existing resource, and custom resources not appropriate for inclusion in the FHIR specification.
Binary | Binary | A binary resource can contain any content, whether text, image, pdf, zip archive, etc.
BodySite | BodySite | Record details about the anatomical location of a specimen or body part. This resource may be used when a coded concept does not provide the necessary detail needed for the use case.
Bundle | Bundle | A container for a collection of resources.

CapabilityStatement | CapabilityStatement | A Capability Statement documents a set of capabilities (behaviors) of a FHIR Server that may be used as a statement of actual server functionality or a statement of required or desired server implementation.

CarePlan | CarePlan | Describes the intention of how one or more practitioners intend to deliver care for a particular patient, group or community for a period of time, possibly limited to care for a specific condition or set of conditions.

CareTeam | CareTeam | The Care Team includes all the people and organizations who plan to participate in the coordination and delivery of care for a patient.

ChargeItem | ChargeItem | The resource ChargeItem describes the provision of healthcare provider products for a certain patient, therefore referring not only to the product, but containing in addition details of the provision, like date, time, amounts and participating organizations and persons. Main Usage of the ChargeItem is to enable the billing process and internal cost allocation.

Claim | Claim | A provider issued list of services and products provided, or to be provided, to a patient which is provided to an insurer for payment recovery.

ClaimResponse | ClaimResponse | This resource provides the adjudication details from the processing of a Claim resource.

ClinicalImpression | ClinicalImpression | A record of a clinical assessment performed to determine what problem(s) may affect the patient and before planning the treatments or management strategies that are best to manage a patient's condition. Assessments are often 1:1 with a clinical consultation / encounter, but this varies greatly depending on the clinical workflow. This resource is called "ClinicalImpression" rather than "ClinicalAssessment" to avoid confusion with the recording of assessment tools such as Apgar score.

CodeSystem | CodeSystem | A code system resource specifies a set of codes drawn from one or more code systems.

Communication | Communication | An occurrence of information being transmitted; e.g. an alert that was sent to a responsible provider, a public health agency was notified about a reportable condition.

CommunicationRequest | CommunicationRequest | A request to convey information; e.g. the CDS system proposes that an alert be sent to a responsible provider, the CDS system proposes that the public health agency be notified about a reportable condition.

CompartmentDefinition | CompartmentDefinition | A compartment definition that defines how resources are accessed on a server.

Composition | Composition | A set of healthcare-related information that is assembled together into a single logical document that provides a single coherent statement of meaning, establishes its own context and that has clinical attestation with regard to who is making the statement. While a Composition defines the structure, it does not actually contain the content: rather the full content of a document is contained in a Bundle, of which the Composition is the first resource contained.

ConceptMap | ConceptMap | A statement of relationships from one set of concepts to one or more other concepts - either code systems or data elements, or classes in class models.

Condition | Condition | A clinical condition, problem, diagnosis, or other event, situation, issue, or clinical concept that has risen to a level of concern.

Consent | Consent | A record of a healthcare consumer’s policy choices, which permits or denies identified recipient(s) or recipient role(s) to perform one or more actions within a given policy context, for specific purposes and periods of time.

Contract | Contract | A formal agreement between parties regarding the conduct of business, exchange of information or other matters.

Coverage | Coverage | Financial instrument which may be used to reimburse or pay for health care products and services.

DataElement | DataElement | The formal description of a single piece of information that can be gathered and reported.

DetectedIssue | DetectedIssue | Indicates an actual or potential clinical issue with or between one or more active or proposed clinical actions for a patient; e.g. Drug-drug interaction, Ineffective treatment frequency, Procedure-condition conflict, etc.

Device | Device | This resource identifies an instance or a type of a manufactured item that is used in the provision of healthcare without being substantially changed through that activity. The device may be a medical or non-medical device. Medical devices include durable (reusable) medical equipment, implantable devices, as well as disposable equipment used for diagnostic, treatment, and research for healthcare and public health. Non-medical devices may include items such as a machine, cellphone, computer, application, etc.

DeviceComponent | DeviceComponent | The characteristics, operational status and capabilities of a medical-related component of a medical device.

DeviceMetric | DeviceMetric | Describes a measurement, calculation or setting capability of a medical device.

DeviceRequest | DeviceRequest | Represents a request for a patient to employ a medical device. The device may be an implantable device, or an external assistive device, such as a walker.

DeviceUseStatement | DeviceUseStatement | A record of a device being used by a patient where the record is the result of a report from the patient or another clinician.

DiagnosticReport | DiagnosticReport | The findings and interpretation of diagnostic tests performed on patients, groups of patients, devices, and locations, and/or specimens derived from these. The report includes clinical context such as requesting and provider information, and some mix of atomic results, images, textual and coded interpretations, and formatted representation of diagnostic reports.

DocumentManifest | DocumentManifest | A collection of documents compiled for a purpose together with metadata that applies to the collection.

DocumentReference | DocumentReference | A reference to a document.

DomainResource | DomainResource | A resource that includes narrative, extensions, and contained resources.

EligibilityRequest | EligibilityRequest | The EligibilityRequest provides patient and insurance coverage information to an insurer for them to respond, in the form of an EligibilityResponse, with information regarding whether the stated coverage is valid and in-force and optionally to provide the insurance details of the policy.

EligibilityResponse | EligibilityResponse | This resource provides eligibility and plan details from the processing of an Eligibility resource.

Encounter | Encounter | An interaction between a patient and healthcare provider(s) for the purpose of providing healthcare service(s) or assessing the health status of a patient.

Endpoint | Endpoint | The technical details of an endpoint that can be used for electronic services, such as for web services providing XDS.b or a REST endpoint for another FHIR server. This may include any security context information.

EnrollmentRequest | EnrollmentRequest | This resource provides the insurance enrollment details to the insurer regarding a specified coverage.

EnrollmentResponse | EnrollmentResponse | This resource provides enrollment and plan details from the processing of an Enrollment resource.

EpisodeOfCare | EpisodeOfCare | An association between a patient and an organization / healthcare provider(s) during which time encounters may occur. The managing organization assumes a level of responsibility for the patient during this time.

ExpansionProfile | ExpansionProfile | Resource to define constraints on the Expansion of a FHIR ValueSet.

ExplanationOfBenefit | ExplanationOfBenefit | This resource provides: the claim details; adjudication details from the processing of a Claim; and optionally account balance information, for informing the subscriber of the benefits provided.

FamilyMemberHistory | FamilyMemberHistory | Significant health events and conditions for a person related to the patient relevant in the context of care for the patient.

Flag | Flag | Prospective warnings of potential issues when providing care to the patient.

Goal | Goal | Describes the intended objective(s) for a patient, group or organization care, for example, weight loss, restoring an activity of daily living, obtaining herd immunity via immunization, meeting a process improvement objective, etc.

GraphDefinition | GraphDefinition | A formal computable definition of a graph of resources - that is, a coherent set of resources that form a graph by following references. The Graph Definition resource defines a set and makes rules about the set.

Group | Group | Represents a defined collection of entities that may be discussed or acted upon collectively but which are not expected to act collectively and are not formally or legally recognized; i.e. a collection of entities that isn't an Organization.

GuidanceResponse | GuidanceResponse | A guidance response is the formal response to a guidance request, including any output parameters returned by the evaluation, as well as the description of any proposed actions to be taken.

HealthcareService | HealthcareService | The details of a healthcare service available at a location.

ImagingManifest | ImagingManifest | A text description of the DICOM SOP instances selected in the ImagingManifest; or the reason for, or significance of, the selection.

ImagingStudy | ImagingStudy | Representation of the content produced in a DICOM imaging study. A study comprises a set of series, each of which includes a set of Service-Object Pair Instances (SOP Instances - images or other data) acquired or produced in a common context. A series is of only one modality (e.g. X-ray, CT, MR, ultrasound), but a study may have multiple series of different modalities.

Immunization | Immunization | Describes the event of a patient being administered a vaccination or a record of a vaccination as reported by a patient, a clinician or another party and may include vaccine reaction information and what vaccination protocol was followed.

ImmunizationRecommendation | ImmunizationRecommendation | A patient's point-in-time immunization and recommendation (i.e. forecasting a patient's immunization eligibility according to a published schedule) with optional supporting justification.

ImplementationGuide | ImplementationGuide | A set of rules of how FHIR is used to solve a particular problem. This resource is used to gather all the parts of an implementation guide into a logical whole and to publish a computable definition of all the parts.

Library | Library | The Library resource is a general-purpose container for knowledge asset definitions. It can be used to describe and expose existing knowledge assets such as logic libraries and information model descriptions, as well as to describe a collection of knowledge assets.

Linkage | Linkage | Identifies two or more records (resource instances) that are referring to the same real-world "occurrence".

List | List | A set of information summarized from a list of other resources.

Location | Location | Details and position information for a physical place where services are provided and resources and participants may be stored, found, contained or accommodated.

Measure | Measure | The Measure resource provides the definition of a quality measure.

MeasureReport | MeasureReport | The MeasureReport resource contains the results of evaluating a measure.

Media | Media | A photo, video, or audio recording acquired or used in healthcare. The actual content may be inline or provided by direct reference.

Medication | Medication | This resource is primarily used for the identification and definition of a medication. It covers the ingredients and the packaging for a medication.

MedicationAdministration | MedicationAdministration | Describes the event of a patient consuming or otherwise being administered a medication. This may be as simple as swallowing a tablet or it may be a long running infusion. Related resources tie this event to the authorizing prescription, and the specific encounter between patient and health care practitioner.

MedicationDispense | MedicationDispense | Indicates that a medication product is to be or has been dispensed for a named person/patient. This includes a description of the medication product (supply) provided and the instructions for administering the medication. The medication dispense is the result of a pharmacy system responding to a medication order.

MedicationRequest | MedicationRequest | An order or request for both supply of the medication and the instructions for administration of the medication to a patient. The resource is called "MedicationRequest" rather than "MedicationPrescription" or "MedicationOrder" to generalize the use across inpatient and outpatient settings, including care plans, etc., and to harmonize with workflow patterns.

MedicationStatement | MedicationStatement | A record of a medication that is being consumed by a patient. A MedicationStatement may indicate that the patient may be taking the medication now, or has taken the medication in the past or will be taking the medication in the future. The source of this information can be the patient, significant other (such as a family member or spouse), or a clinician. A common scenario where this information is captured is during the history taking process during a patient visit or stay. The medication information may come from sources such as the patient's memory, from a prescription bottle, or from a list of medications the patient, clinician or other party maintains The primary difference between a medication statement and a medication administration is that the medication administration has complete administration information and is based on actual administration information from the person who administered the medication. A medication statement is often, if not always, less specific. There is no required date/time when the medication was administered, in fact we only know that a source has reported the patient is taking this medication, where details such as time, quantity, or rate or even medication product may be incomplete or missing or less precise. As stated earlier, the medication statement information may come from the patient's memory, from a prescription bottle or from a list of medications the patient, clinician or other party maintains. Medication administration is more formal and is not missing detailed information.

MessageDefinition | MessageDefinition | Defines the characteristics of a message that can be shared between systems, including the type of event that initiates the message, the content to be transmitted and what response(s), if any, are permitted.

MessageHeader | MessageHeader | The header for a message exchange that is either requesting or responding to an action. The reference(s) that are the subject of the action as well as other information related to the action are typically transmitted in a bundle in which the MessageHeader resource instance is the first resource in the bundle.

NamingSystem | NamingSystem | A curated namespace that issues unique symbols within that namespace for the identification of concepts, people, devices, etc. Represents a "System" used within the Identifier and Coding data types.

NutritionOrder | NutritionOrder | A request to supply a diet, formula feeding (enteral) or oral nutritional supplement to a patient/resident.

Observation | Observation | Measurements and simple assertions made about a patient, device or other subject.

OperationDefinition | OperationDefinition | A formal computable definition of an operation (on the RESTful interface) or a named query (using the search interaction).

OperationOutcome | OperationOutcome | A collection of error, warning or information messages that result from a system action.

Organization | Organization | A formally or informally recognized grouping of people or organizations formed for the purpose of achieving some form of collective action. Includes companies, institutions, corporations, departments, community groups, healthcare practice groups, etc.

Parameters | Parameters | This special resource type is used to represent an operation request and response (operations.html). It has no other use, and there is no RESTful endpoint associated with it.

Patient | Patient | Demographics and other administrative information about an individual or animal receiving care or other health-related services.

PaymentNotice | PaymentNotice | This resource provides the status of the payment for goods and services rendered, and the request and response resource references.

PaymentReconciliation | PaymentReconciliation | This resource provides payment details and claim references supporting a bulk payment.

Person | Person | Demographics and administrative information about a person independent of a specific health-related context.

PlanDefinition | PlanDefinition | This resource allows for the definition of various types of plans as a sharable, consumable, and executable artifact. The resource is general enough to support the description of a broad range of clinical artifacts such as clinical decision support rules, order sets and protocols.

Practitioner | Practitioner | A person who is directly or indirectly involved in the provisioning of healthcare.

PractitionerRole | PractitionerRole | A specific set of Roles/Locations/specialties/services that a practitioner may perform at an organization for a period of time.

Procedure | Procedure | An action that is or was performed on a patient. This can be a physical intervention like an operation, or less invasive like counseling or hypnotherapy.

ProcedureRequest | ProcedureRequest | A record of a request for diagnostic investigations, treatments, or operations to be performed.

ProcessRequest | ProcessRequest | This resource provides the target, request and response, and action details for an action to be performed by the target on or about existing resources.

ProcessResponse | ProcessResponse | This resource provides processing status, errors and notes from the processing of a resource.

Provenance | Provenance | Provenance of a resource is a record that describes entities and processes involved in producing and delivering or otherwise influencing that resource. Provenance provides a critical foundation for assessing authenticity, enabling trust, and allowing reproducibility. Provenance assertions are a form of contextual metadata and can themselves become important records with their own provenance. Provenance statement indicates clinical significance in terms of confidence in authenticity, reliability, and trustworthiness, integrity, and stage in lifecycle (e.g. Document Completion - has the artifact been legally authenticated), all of which may impact security, privacy, and trust policies.

Questionnaire | Questionnaire | A structured set of questions intended to guide the collection of answers from end-users. Questionnaires provide detailed control over order, presentation, phraseology and grouping to allow coherent, consistent data collection.

QuestionnaireResponse | QuestionnaireResponse | A structured set of questions and their answers. The questions are ordered and grouped into coherent subsets, corresponding to the structure of the grouping of the questionnaire being responded to.

ReferralRequest | ReferralRequest | Used to record and send details about a request for referral service or transfer of a patient to the care of another provider or provider organization.

RelatedPerson | RelatedPerson | Information about a person that is involved in the care for a patient, but who is not the target of healthcare, nor has a formal responsibility in the care process.

RequestGroup | RequestGroup | A group of related requests that can be used to capture intended activities that have inter-dependencies such as "give this medication after that one".

ResearchStudy | ResearchStudy | A process where a researcher or organization plans and then executes a series of steps intended to increase the field of healthcare-related knowledge. This includes studies of safety, efficacy, comparative effectiveness and other information about medications, devices, therapies and other interventional and investigative techniques. A ResearchStudy involves the gathering of information about human or animal subjects.

ResearchSubject | ResearchSubject | A process where a researcher or organization plans and then executes a series of steps intended to increase the field of healthcare-related knowledge. This includes studies of safety, efficacy, comparative effectiveness and other information about medications, devices, therapies and other interventional and investigative techniques. A ResearchStudy involves the gathering of information about human or animal subjects.

Resource | Resource | This is the base resource type for everything.

RiskAssessment | RiskAssessment | An assessment of the likely outcome(s) for a patient or other subject as well as the likelihood of each outcome.

Schedule | Schedule | A container for slots of time that may be available for booking appointments.

SearchParameter | SearchParameter | A search parameter that defines a named search item that can be used to search/filter on a resource.

Sequence | Sequence | Raw data describing a biological sequence.

ServiceDefinition | ServiceDefinition | The ServiceDefinition describes a unit of decision support functionality that is made available as a service, such as immunization modules or drug-drug interaction checking.

Slot | Slot | A slot of time on a schedule that may be available for booking appointments.

Specimen | Specimen | A sample to be used for analysis.

StructureDefinition | StructureDefinition | A definition of a FHIR structure. This resource is used to describe the underlying resources, data types defined in FHIR, and also for describing extensions and constraints on resources and data types.

StructureMap | StructureMap | A Map of relationships between 2 structures that can be used to transform data.

Subscription | Subscription | The subscription resource is used to define a push based subscription from a server to another system. Once a subscription is registered with the server, the server checks every resource that is created or updated, and if the resource matches the given criteria, it sends a message on the defined "channel" so that another system is able to take an appropriate action.

Substance | Substance | A homogeneous material with a definite composition.

SupplyDelivery | SupplyDelivery | Record of delivery of what is supplied.

SupplyRequest | SupplyRequest | A record of a request for a medication, substance or device used in the healthcare setting.

Task | Task | A task to be performed.

TestReport | TestReport | A summary of information based on the results of executing a TestScript.

TestScript | TestScript | A structured set of tests against a FHIR server implementation to determine compliance against the FHIR specification.

ValueSet | ValueSet | A value set specifies a set of codes drawn from one or more code systems.

VisionPrescription | VisionPrescription | An authorization for the supply of glasses and/or contact lenses to a patient.

See the full registry of value sets defined as part of FHIR.

Explanation of the columns that may appear on this page:

Level | A few code lists that FHIR defines are hierarchical - each code is assigned a level. In this scheme, some codes are under other codes, and imply that the code they are under also applies

Source | The source of the definition of the code (when the value set draws in codes defined elsewhere)

Code | The code (used as the code in the resource instance). If the code is in italics, this indicates that the code is not selectable ('Abstract')

Display | The display (used in the display element of a Coding). If there is no display, implementers should not simply display the code, but map the concept into their application

Definition | An explanation of the meaning of the concept

Comments | Additional notes about how to use the code

4.2.13.1 HL7 Version 2 Table 0001

URL: https://hl7.org/fhir/STU3/v2/0001/index.html

This page is part of the FHIR Specification (v3.0.2: STU 3). The current version which supercedes this version is 4.0.1. For a full list of available versions, see the Directory of published versions

Vocabulary Work Group | Maturity Level: N/A | External | Use Context: Any

This is a table defined as part of HL7 v2 . Related FHIR content: v2 Administrative Sex.

Summary

Name: | v2 Administrative Sex

Definition: | FHIR Value set/code system definition for HL7 v2 table 0001 (Administrative Sex)

Code System URL: | http://hl7.org/fhir/v2/0001
Value Set URL: | http://hl7.org/fhir/ValueSet/v2-0001
OID: | ??
CodeSystem Resource | XML / JSON
ValueSet Resource | XML / JSON

Concept Maps for this value set:

from AdministrativeGender | v2 map for AdministrativeGender | XML | JSON

This value set is used in the following places:

* This value set is the designated 'entire code system' value set for v2 Administrative Sex

* This value set is the target of translations in the ConceptMap v2 map for AdministrativeGender

4.2.13.1.1 Code System Content

Administrative Sex

Code | Description | Deutsch (German) | Nederlands (Dutch) | Comment | Version
A | Ambiguous | mehrdeutig | Ambigu | | added v2.4
F | Female | weiblich | Vrouw | | from v2.1
M | Male | männlich | Man | | from v2.1
N | Not applicable | nicht zutreffend | Niet van toepassing | | added v2.4
O | Other | andere | Anders | | from v2.1
U | Unknown | unbekannt | Onbekend | | from v2.1

4.2.13.2 HL7 Version 2 Table 0002

URL: https://hl7.org/fhir/STU3/v2/0002/index.html

This page is part of the FHIR Specification (v3.0.2: STU 3). The current version which supercedes this version is 4.0.1. For a full list of available versions, see the Directory of published versions

Vocabulary Work Group | Maturity Level: N/A | External | Use Context: Any

This is a table defined as part of HL7 v2 . Related FHIR content: v2 Marital Status.

Summary

Name: | v2 Marital Status
Definition: | FHIR Value set/code system definition for HL7 v2 table 0002 (Marital Status)
Code System URL: | http://hl7.org/fhir/v2/0002
Value Set URL: | http://hl7.org/fhir/ValueSet/v2-0002
OID: | ??
CodeSystem Resource | XML / JSON
ValueSet Resource | XML / JSON

This value set is used in the following places:

* This value set is the designated 'entire code system' value set for v2 Marital Status

4.2.13.2.1 Code System Content

Marital Status

Code | Description | Deutsch (German) | Nederlands (Dutch) | Comment | Version
A | Separated | getrennt lebend | Uit elkaar | | from v2.1
B | Unmarried | ledig | Niet getrouwd | | added v2.4
C | Common law | eheähnliche Gemeinschaft | Volgens jurisprudentie | | added v2.4
D | Divorced | geschieden | Gescheiden na huwelijk | | from v2.1
E | Legally Separated | rechtskräftig getrennt | Wettelijk gescheiden | | added v2.4
G | Living together | zusammenlebend | Samenlevend | | added v2.4
I | Interlocutory | | Tijdelijke overeenkomst | | added v2.4
M | Married | verheiratet | Getrouwd | | from v2.1
N | Annulled | annulliert | Nietig verklaard | | added v2.4
O | Other | sonstiges | Anders | | added v2.4
P | Domestic partner | häuslicher Partner | Huisgenoot | | added v2.4
R | Registered domestic partner | | Geregistreerd partnerschap | | added v2.4
S | Single | allein lebend | Alleenstaand | | from v2.1
T | Unreported | keine Angabe | Niet vermeld | | added v2.4
U | Unknown | unbekannt | Onbekend | | added v2.4
W | Widowed | verwitwet | Weduwe/weduwnaar | | from v2.1

4.2.13.3 HL7 Version 2 Table 0003

URL: https://hl7.org/fhir/STU3/v2/0003/index.html

This page is part of the FHIR Specification (v3.0.2: STU 3). The current version which supercedes this version is 4.0.1. For a full list of available versions, see the Directory of published versions

Vocabulary Work Group | Maturity Level: N/A | External | Use Context: Any

This is a table defined as part of HL7 v2 . Related FHIR content: v2 Event Type.

Summary

Name: | v2 Event Type
Definition: | FHIR Value set/code system definition for HL7 v2 table 0003 (Event Type)
Code System URL: | http://hl7.org/fhir/v2/0003
Value Set URL: | http://hl7.org/fhir/ValueSet/v2-0003
OID: | ??
CodeSystem Resource | XML / JSON
ValueSet Resource | XML / JSON

This value set is used in the following places:

* This value set is the designated 'entire code system' value set for v2 Event Type

4.2.13.3.1 Code System Content

Event Type

Code | Description | Deutsch (German) | Nederlands (Dutch) | Comment | Version
A01 | ADT/ACK - Admit/visit notification | stationäre Aufnahme | ADT/ACK - Opname/bezoek notificatie | | from v2.1
A02 | ADT/ACK - Transfer a patient | Verlegung | ADT/ACK - Overplaatsing van een patiënt | | from v2.1
A03 | ADT/ACK - Discharge/end visit | Entlassung | ADT/ACK - Ontslag/einde bezoek | | from v2.1
A04 | ADT/ACK - Register a patient | Besuchsmeldung (nicht-stationär) | ADT/ACK - Registratie van een patiënt | | from v2.1
A05 | ADT/ACK - Pre-admit a patient | Voraufnahme eines Patienten | Vooropname van een patiënt | | from v2.1
A06 | ADT/ACK - Change an outpatient to an inpatient | Änderung von ambulant in stationär | ADT/ACK - Wijzig poliklinische patiënt naar klinische patiënt | | from v2.1
A07 | ADT/ACK - Change an inpatient to an outpatient | Änderung von stationär in ambulant | ADT/ACK - Wijzig klinische patiënt naar poliklinische patiënt | | from v2.1
A08 | ADT/ACK - Update patient information | Änderung von Patienteninformationen | ADT/ACK - Update patiëntinformatie | | from v2.1
A09 | ADT/ACK - Patient departing - tracking | Patient verläßt Einrichtung | ADT/ACK - Patiënt vertrekt - tracking | | from v2.1
A10 | ADT/ACK - Patient arriving - tracking | Patient erreicht Einrichtung | ADT/ACK - Patiënt keert terug - tracking | | from v2.1
A11 | ADT/ACK - Cancel admit/visit notification | Stornierung für A01 und A04 | ADT/ACK - Annuleer opname/bezoek notificatie | | from v2.1
A12 | ADT/ACK - Cancel transfer | Stornierung für A02 | ADT/ACK - Annulering overplaatsing | | from v2.1
A13 | ADT/ACK - Cancel discharge/end visit | Stornierung für A03 | ADT/ACK - Annuleer ontslag/einde bezoek | | from v2.1
A14 | ADT/ACK - Pending admit | Geplante Aufnahme | ADT/ACK - Geplande opname | | from v2.1
A15 | ADT/ACK - Pending transfer | Geplante Verlegung | ADT/ACK - Geplande overplaatsing | | from v2.1
A16 | ADT/ACK - Pending discharge | Geplante Entlassung | ADT/ACK - Gepland ontslag | | from v2.1
A17 | ADT/ACK - Swap patients | Bettentausch zweier Patienten | ADT/ACK - Bedwissel patiënten | | from v2.1
A18 | ADT/ACK - Merge patient information | Patienteninf. zusammenf. (veraltet, neu: A34ff.) | ADT/ACK - Samenvoeging patiëntinformatie | Deprecated | from v2.1
A19 | QRY/ADR - Patient query | Anfrage nach Patientendaten | Patiëntopvraging | Deprecated | from v2.1
A20 | ADT/ACK - Bed status update | Änderung des Bettenstatus | ADT/ACK - Update bedstatus | | from v2.1
A21 | ADT/ACK - Patient goes on a "leave of absence" | Beginn einer Patientenabwesenheit | ADT/ACK - Patiënt gaat met “verlof” | | from v2.1
A22 | ADT/ACK - Patient returns from a "leave of absence" | Ende einer Patientenabwesenheit | ADT/ACK - Patiënt keert terug van “verlof” | | from v2.1
A23 | ADT/ACK - Delete a patient record | Löschen eines Patientensatzes | ADT/ACK - Verwijder een patiëntrecord | | from v2.1
A24 | ADT/ACK - Link patient information | Verknüpfen von Patientendaten | ADT/ACK - Koppel patiëntinformatie | | from v2.1
A25 | ADT/ACK - Cancel pending discharge | Stornierung einer eingeleiteten Entlassung | ADT/ACK - Annuleer gepland ontslag | | added v2.2
A26 | ADT/ACK - Cancel pending transfer | Stornierung einer eingeleiteten Verlegung | ADT/ACK - Annuleer geplande overplaatsing | | added v2.2
A27 | ADT/ACK - Cancel pending admit | Stornierung einer eingeleiteten Aufnahme | ADT/ACK - Annuleer geplande opname | | added v2.2
A28 | ADT/ACK - Add person information | Personendaten hinzufügen | ADT/ACK - Voeg persoonsinformatie toe | | added v2.2
A29 | ADT/ACK - Delete person information | Löschung von personenbezogenen Daten | ADT/ACK - Verwijder persoonsinformatie | | added v2.2
A30 | ADT/ACK - Merge person information | veraltet | ADT/ACK - Voeg persoonsinformatie samen | Deprecated | added v2.2
A31 | ADT/ACK - Update person information | Ändern personenbezogener Daten | ADT/ACK - Update persoonsinformatie | | added v2.2
A32 | ADT/ACK - Cancel patient arriving - tracking | Stornierung eines Patientenzugangs (Bettenzuweisung) | ADT/ACK - Annuleer aankomst patiënt - tracking | | added v2.2
A33 | ADT/ACK - Cancel patient departing - tracking | Stornierung eines Patientenabgangs (Bettenfreigabe) | ADT/ACK - Annuleer vertrek patiënt - tracking | | added v2.2
A34 | ADT/ACK - Merge patient information - patient ID only | Abgleich nur der Patientennummer (veraltet) | ADT/ACK - Voeg patiëntinformatie samen - alleen patiënt ID | Deprecated | added v2.2
A35 | ADT/ACK - Merge patient information - account number only | Abgleich nur der Abrechnungsnummer / Debitorenkontonummer (veraltet) | ADT/ACK - Voeg patiëntinformatie samen - alleen accountnummer | Deprecated | added v2.2
A36 | ADT/ACK - Merge patient information - patient ID and account number | Abgleich von Patientennummer und Abrechnungsnummer / Debitorenkontonummer (veraltet) | ADT/ACK - Voeg patiëntinformatie samen - patiënt ID en accountnummer | Deprecated | added v2.2
A37 | ADT/ACK - Unlink patient information | Auflösung einer Verknüpfung von Patientendaten | ADT/ACK - Ontkoppel patiëntinformatie | | added v2.2
A38 | ADT/ACK - Cancel pre-admit | Stornierung zu A05 | ADT/ACK - Annuleer opname op wachtlijst | | added v2.3
A39 | ADT/ACK - Merge person - patient ID | Zusammenführung von Information über externe ID (veraltet) | ADT/ACK - Voeg persoon samen - patiënt ID | Deprecated | added v2.3
A40 | ADT/ACK - Merge patient - patient identifier list | Zusammenführung v. Pat-Information über ID-Liste | ADT/ACK - Voeg patiënt samen - lijst patiënt ID's | | added v2.3
A41 | ADT/ACK - Merge account - patient account number | Zusammenführung von Konten über Kontonummer | ADT/ACK - Samenvoeging account - patiënt accountnummer | | added v2.3
A42 | ADT/ACK - Merge visit - visit number | Zusammenführung v.Fall-Information über Fallnummer | ADT/ACK - Samenvoeging bezoek - bezoeknummer | | added v2.3

A43 | ADT/ACK - Move patient information - patient identifier list | Korrektur einer falschen Zuordnung bzgl. PID-Liste | ADT/ACK - Verplaats patiëntinformatie - lijst patiënt ID's | | added v2.3
A44 | ADT/ACK - Move account information - patient account number | Korrektur einer falschen Zuordnung bzgl.Abrechungsnummer | ADT/ACK - Verplaats accountinformatie - patiënt accountnummer | | added v2.3
A45 | ADT/ACK - Move visit information - visit number | Korrektur einer falschen Zuordnung bzgl.Fallnummer | ADT/ACK - Verplaats bezoekinformatie - bezoeknummer | | added v2.3
A46 | ADT/ACK - Change patient ID | Änderung der externen Pat.ID (PID-2) | ADT/ACK - Wijzig patiënt ID | Deprecated | added v2.3
A47 | ADT/ACK - Change patient identifier list | Änderung der internen Pat.ID (PID-3) | ADT/ACK - Wijzig lijst patiënt ID's | | added v2.3
A48 | ADT/ACK - Change alternate patient ID | Änderung der alternativen Pat.ID (PID-4) | ADT/ACK - Wijzig alternatief patiënt ID | Deprecated | added v2.3
A49 | ADT/ACK - Change patient account number | Änderung der Abrechungsnummer (PID-18) | ADT/ACK - Wijzig patiënt accountnummer | | added v2.3
A50 | ADT/ACK - Change visit number | Änderung der Fallnummer (PV1-19) | ADT/ACK - Wijzig bezoeknummer | | added v2.3
A51 | ADT/ACK - Change alternate visit ID | Änderung der alternativen Fallnummer (PV1-50) | ADT/ACK - Wijzig alternatief bezoeknummer | | added v2.3
A52 | ADT/ACK - Cancel leave of absence for a patient | | ADT/ACK - Annuleer verlof voor een patiënt | | added v2.4
A53 | ADT/ACK - Cancel patient returns from a leave of absence | | ADT/ACK - Annuleer terugkeer van verlof voor een patiënt | | added v2.4
A54 | ADT/ACK - Change attending doctor | | ADT/ACK - Wijzig behandelend arts | | added v2.4
A55 | ADT/ACK - Cancel change attending doctor | | ADT/ACK - Annuleer wijzigen behandelend arts | | added v2.4
A60 | ADT/ACK - Update allergy information | | ADT/ACK - Update allergie-informatie | | added v2.4
A61 | ADT/ACK - Change consulting doctor | | ADT/ACK - Wijzig consulterend arts | | added v2.4
A62 | ADT/ACK - Cancel change consulting doctor | | ADT/ACK - Annuleer wijzigen consulterend arts | | added v2.4
B01 | PMU/ACK - Add personnel record | | PMU/ACK - Voeg personeelrecord toe | | added v2.4
B02 | PMU/ACK - Update personnel record | | PMU/ACK - Update personeelrecord | | added v2.4
B03 | PMU/ACK - Delete personnel re cord | | PMU/ACK - Verwijder personeelrecord | | added v2.4
B04 | PMU/ACK - Active practicing person | | PMU/ACK - Activeer praktiserend persoon | | added v2.4
B05 | PMU/ACK - Deactivate practicing person | | PMU/ACK - Deactiveer praktiserend persoon | | added v2.4
B06 | PMU/ACK - Terminate practicing person | | PMU/ACK - Beëindig praktiserend persoon | | added v2.4
B07 | PMU/ACK - Grant Certificate/Permission | | PMU/ACK - Geef certificaat/toestemming | | added v2.5
B08 | PMU/ACK - Revoke Certificate/Permission | | PMU/ACK - Trek certificaat/toestemming in | | added v2.5
C01 | CRM - Register a patient on a clinical trial | Registrierung eines Patienten f.eine klin.Studie | CRM - Registreer patiënt voor clinical trial | | added v2.3
C02 | CRM - Cancel a patient registration on clinical trial (for clerical mistakes only) | Löschung der Registrierung | CRM - Annuleer patiëntregistratie voor clinical trial (invoerfout) | | added v2.3
C03 | CRM - Correct/update registration information | Korrektur/Änderung der Registrierung | CRM - Corrigeer/update registratie-informatie | | added v2.3
C04 | CRM - Patient has gone off a clinical trial | Patient ist aus der Studie ausgeschieden | CRM - Patiënt heeft clinical trial verlaten | | added v2.3
C05 | CRM - Patient enters phase of clinical trial | Patient tritt in Studienphase ein | CRM - Patiënt gaat in fase van clinical trial | | added v2.3
C06 | CRM - Cancel patient entering a phase (clerical mistake) | Löschung des Eintritts in eine Studienphase | CRM - Annuleer patiënt gaat in fase van clinical trial (invoerfout) | | added v2.3
C07 | CRM - Correct/update phase information | Korrektur/Änderung der Angaben zur Studienphase | CRM - Corrigeer/update fase-informatie | | added v2.3
C08 | CRM - Patient has gone off phase of clinical trial | Patient ist aus Studienphase ausgeschieden | CRM - Patiënt heeft fase clinical trial verlaten | | added v2.3
C09 | CSU - Automated time intervals for reporting, like monthly | Festlegung des Zeitintervalls für autom. Berichte | CSU - Geautomatiseerde rapportageintervallen, zoals maandelijks | | added v2.3
C10 | CSU - Patient completes the clinical trial | Patient beendet Studie | CSU - Patiënt voltooit de clinical trial | | added v2.3
C11 | CSU - Patient completes a phase of the clinical trial | Patient beendet eine Studienphase | CSU - Patiënt voltooit een fase van de clinical trial | | added v2.3
C12 | CSU - Update/correction of patient order/result information | Korrektur/Änderung von Anforderungen/Ergebnissen | CSU - Update/correctie van patiënt aanvraag-/resultaatinformatie | | added v2.3
CNQ | Cancel Query | Stornierung einer Anfrage | Annuleer query | deprecated | added v2.3, removed after v2.5.1
E01 | Submit HealthCare Services Invoice | | Dien factuur zorgproducten in | | added v2.6
E02 | Cancel HealthCare Services Invoice | | Annuleer factuur zorgproducten | | added v2.6
E03 | HealthCare Services Invoice Status | | Status factuur zorgproducten | | added v2.6
E04 | Re-Assess HealthCare Services Invoice Request | | Beoordeel factuuraanvraag zorgproducten opnieuw | | added v2.6
E10 | Edit/Adjudication Results | | Wijzig/beslissing resultaten | | added v2.6
E12 | Request Additional Information | | Verzoek om aanvullende informatie | | added v2.6
E13 | Additional Information Response | | Antwoord aanvullende informatie | | added v2.6
E15 | Payment/Remittance Advice | | Advies betaling/teruggave | | added v2.6
E20 | Submit Authorization Request | | Dien autorisatieverzoek in | | added v2.6
E21 | Cancel Authorization Request | | Annuleer autorisatieverzoek | | added v2.6
E22 | Authorization Request Status | | Status autorisatieverzoek | | added v2.6
E24 | Authorization Response | | Antwoord autorisatieverzoek | | added v2.6
E30 | Submit Health Document related to Authorization Request | | Dien zorgdocument gerelateerd aan autorisatieverzoek in | reserved for future/not yet defined | added v2.6
E31 | Cancel Health Document related to Authorization Request | | Annuleer zorgdocument gerelateerd aan autorisatieverzoek | reserved for future/not yet defined | added v2.6
I01 | RQI/RPI - Request for insurance information | Anforderung von Versicherungsdaten | RQI/RPI - Verzoek om verzekeringsgegevens | | added v2.3
I02 | RQI/RPL - Request/receipt of patient selection display list | Anforderg.einer Patientenauswahlliste (zur Anzeige) | RQI/RPL - Verzoek/afschrift van patiëntselectie weergavelijst | | added v2.3
I03 | RQI/RPR - Request/receipt of patient selection list | Anforderg.einer strukt. Patientenauswahlliste | RQI/RPR - Verzoek/afschrift van patiëntselectielijst | | added v2.3

I04 | RQD/RPI - Request for patient demographic data | Anforderung demographischer Informationen | RQD/RPI - Verzoek om demografische patiëntgegevens | | added v2.3
I05 | RQC/RCI - Request for patient clinical information | Anforderung klinischer Informationen | RQC/RCI - Verzoek om klinische patiëntgegevens | Deprecated | added v2.3
I06 | RQC/RCL - Request/receipt of clinical data listing | Anforderung strukt. klinischer Informationen | RQC/RCL - Verzoek/afschrift van overzicht klinische gegevens | Deprecated | added v2.3
I07 | PIN/ACK - Unsolicited insurance information | unaufgeforderte Übermittlung v. Versicherungsdaten | PIN/ACK - Ongevraagde verzekeringsinformatie | | added v2.3
I08 | RQA/RPA - Request for treatment authorization information | Anforderung Kostenübernahmeerklärung | RQA/RPA - Verzoek om autorisatie-informatie behandeling | | added v2.3
I09 | RQA/RPA - Request for modification to an authorization | Anforderg bzgl. Änderung Kostenübernahmeerklärung | RQA/RPA - Verzoek om wijziging in autorisatie | | added v2.3
I10 | RQA/RPA - Request for resubmission of an authorization | erneute Anforderung Kostenübernahmeerklärung | RQA/RPA - Verzoek om autorisatie opnieuw in te dienen | | added v2.3
I11 | RQA/RPA - Request for cancellation of an authorization | Anfordrg Stornierg einer Kostenübernahmeerklärung | RQA/RPA - Verzoek om annulering van een autorisatie | | added v2.3
I12 | REF/RRI - Patient referral | Überweisung eines Patienten | REF/RRI - Patiëntverwijzing | | added v2.3
I13 | REF/RRI - Modify patient referral | Änderung einer Patientenüberweisung | REF/RRI - Wijzig patiëntverwijzing | | added v2.3
I14 | REF/RRI - Cancel patient referral | Stornierung einer Patientenüberweisung | REF/RRI - Annuleer patiëntverwijzing | | added v2.3
I15 | REF/RRI - Request patient referral status | Statusabfrage bzgl. Patientenüberweisung | REF/RRI - Verzoek om status patiëntverwijzing | | added v2.3
I16 | Collaborative Care Referral | | Multidisciplinaire verwijzing | | added v2.7
I17 | Modify Collaborative Care Referral | | Wijzig multidisciplinaire verwijzing | Deprecated | added v2.7
I18 | Cancel Collaborative Care Referral | | Annuleer multidisciplinaire verwijzing | Deprecated | added v2.7
I19 | Collaborative Care Query/Collaborative Care Query Update | | Query multidisciplinaire zorg/Query update multidisciplinaire zorg | | added v2.7
I20 | Asynchronous Collaborative Care Update | | Asynchrone update multidisciplinaire zorg | | added v2.7
I21 | Collaborative Care Message | | Multidisciplinair bericht | | added v2.7
I22 | Collaborative Care Fetch / Collaborative Care Information | | Multidisciplinaire zorg ophalen/multidisciplinaire zorg informatie | | added v2.7
J01 | QCN/ACK - Cancel query/acknowledge message | | QCN/ACK - Annuleer query/bevestigingsbericht | | added v2.4
J02 | QSX/ACK - Cancel subscription/acknowledge message | | QSX/ACK - Annuleer abonnement/bevestigingsbericht | | added v2.4
K11 | RSP - Segment pattern response in response to QBP^Q11 | | RSP - Segmentpatroon antwoord op QBP^Q11 | | added v2.5
K13 | RTB - Tabular response in response to QBP^Q13 | | RTB - Tabelpatroon antwoord op QBP^Q13 | | added v2.5
K15 | RDY - Display response in response to QBP^Q15 | | RDY - Weergavepatroon antwoord op QBP^Q15 | | added v2.5
K21 | RSP - Get person demographics response | | RSP - Antwoord query demografische persoonsgegevens | | added v2.4
K22 | RSP - Find candidates response | | RSP - Antwoord zoek kandidaten | | added v2.4
K23 | RSP - Get corresponding identifiers response | | RSP - Antwoord bijbehorende ID's | | added v2.4
K24 | RSP - Allocate identifiers response | | RSP - Antwoord alloceer ID's | | added v2.4
K25 | RSP - Personnel Information by Segment Response | | RSP - Antwoord personeelsinformatie op segment | | added v2.4
K31 | RSP -Dispense History Response | | RSP - Antwoord verstrekkingshistorie | | added v2.5.1
K32 | Find Candidates including Visit Information Response | | Antwoord zoek kandidaten inclusief bezoekinformatie | | added v2.7
K33 | Get Donor Record Candidates Response Message | | Antwoord zoek donorrecord-kandidaten | | added v2.8
K34 | Segment Pattern Response Message | | Segmentpatroon antwoordbericht | | added v2.8
M01 | MFN/MFK - Master file not otherwise specified | Stammdatenänderung (veraltet) | MFN/MFK - Masterbestand - niet anderszins gespecificeerd | Deprecated | added v2.2
M02 | MFN/MFK - Master file - staff practitioner | Stammdatenänderung - Ärzte | MFN/MFK - Masterbestand - Medewerker zorgverlener | | added v2.2
M03 | MFN/MFK - Master file - test/observation | Stammdatenänderung - Tests / Untersuchungen | MFN/MFK - Masterbestand - Test/observatie | Deprecated | added v2.2
M04 | MFN/MFK - Master files charge description | Stammdatenänderung - delayed appl ack | MFN/MFK - Masterbestand - Prijsomschrijving | | added v2.3
M05 | MFN/MFK - Patient location master file | Stammdatenänderung - Aufenthaltsorte | MFN/MFK - Masterbestand - Patiëntlocatie | | added v2.3
M06 | MFN/MFK - Clinical study with phases and schedules master file | Stammdatenänderung - Abrechnungskataloge | MFN/MFK - Masterbestand - Klinische studie met fases en planning | | added v2.3
M07 | MFN/MFK - Clinical study without phases but with schedules master file | Stammdatenänderung - klinische Studien ohne Phasen | MFN/MFK - Masterbestand - Klinische studie zonder fases maar met planning | | added v2.3
M08 | MFN/MFK - Test/observation (numeric) master file | Stammdatenänderung - Tests/Untersuchung mit numerischen Ergebnissen | MFN/MFK - Masterbestand - Test/observatie (numeriek) | | added v2.3
M09 | MFN/MFK - Test/observation (categorical) master file | Stammdatenänderung - Tests mit nicht numerischen Ergebnissen | MFN/MFK - Masterbestand - Test/observatie (categorieën) | | added v2.3
M10 | MFN/MFK - Test /observation batteries master file | Stammdatenänderung - Testprofile | MFN/MFK - Masterbestand - Test/observatie batteries | | added v2.3
M11 | MFN/MFK - Test/calculated observations master file | Stammdatenänderung - berechnete Ergebnisse | MFN/MFK - Masterbestand - Test/berekende observaties | | added v2.3
M12 | MFN/MFK - Master file notification message | | MFN/MFK - Masterbestand - Notificatiebericht | | added v2.4
M13 | MFN/MFK - Master file notification - general | | MFN/MFK - Masterbestand - Notificatiebericht algemeen | | added v2.5
M14 | MFN/MFK - Master file notification - site defined | | MFN/MFK - Masterbestand - Notificatiebericht lokale overeenkomst | | added v2.5
M15 | MFN/MFK - Inventory item master file notification | | MFN/MFK - Masterbestand voorraaditems - Notificatiebericht | | added v2.5
M16 | MFN/MFK - Master File Notification Inventory Item Enhanced | | MFN/MFK - Masterbestand voorraaditems - Notificatiebericht verbeterd | | added v2.6
M17 | DRG Master File Message | | DRG - Masterbestand bericht | | added v2.6
M18 | MFN/MFK - Master file notification - Test/Observation (Payer) | | MFN/MFK - Master file notification - Test/Observatie (Betaler) | | added v2.8.2
N01 | NMQ/NMR - Application management query message | | NMQ/NMR - Query Applicatiemanagement | Deprecated | added v2.4
N02 | NMD/ACK - Application management data message (unsolicited) | | NMD/NMR - Applicatiemanagementgegevens (ongevraagd) | | added v2.4

O01 | ORM - Order message (also RDE, RDS, RGV, RAS) | Auftrag / Verordnung | ORM - Aanvraagbericht (ook RDE, RDS, RGV, RAS) | Deprecated | from v2.1
O02 | ORR - Order response (also RRE, RRD, RRG, RRA) | Auftragsbestätigung | ORR - Antwoord aanvraagbericht (ook RRE, RRD, RRG, RRA) | Deprecated | from v2.1
O03 | OMD - Diet order | | OMD - Maaltijdaanvraag | | added v2.4
O04 | ORD - Diet order acknowledgment | | ORD - Bevestiging maaltijdaanvraag | | added v2.4
O05 | OMS - Stock requisition order | | OMS - Aanvraag aanvulling voorraad | | added v2.4
O06 | ORS - Stock requisition acknowledgment | | ORS - Bevestiging aanvraag aanvulling voorraad | | added v2.4
O07 | OMN - Non-stock requisition order | | OMN - Aanvraag aanvulling niet-voorraad | | added v2.4
O08 | ORN - Non-stock requisition acknowledgment | | ORN - Bevestiging aanvraag aanvulling niet-voorraad | | added v2.4
O09 | OMP - Pharmacy/treatment order | | OMP - Medicatie/therapie aanvraag | | added v2.4
O10 | ORP - Pharmacy/treatment order acknowledgment | | ORP - Bevestiging medicatie/therapie aanvraag | | added v2.4
O11 | RDE - Pharmacy/treatment encoded order | | RDE - Gecodeerde aanvraag medicatie/therapie | | added v2.4
O12 | RRE - Pharmacy/treatment encoded order acknowledgment | | RRE - Bevestiging gecodeerde aanvraag medicatie/therapie | | added v2.4
O13 | RDS - Pharmacy/treatment dispense | | RDS - Medicatie/therapieverstrekking | | added v2.4
O14 | RRD - Pharmacy/treatment dispense acknowledgment | | RRD - Bevestiging medicatie/therapieverstrekking | | added v2.4
O15 | RGV - Pharmacy/treatment give | | RGV - Medicatie/therapie gegeven | | added v2.4
O16 | RRG - Pharmacy/treatment give acknowledgment | | RRG - Bevestiging medicatie/therapie gegeven | | added v2.4
O17 | RAS - Pharmacy/treatment administration | | RAS - Medicatie/therapietoediening | | added v2.4
O18 | RRA - Pharmacy/treatment administration acknowledgment | | RRA - Bevestiging medicatie/therapietoediening | | added v2.4
O19 | OMG - General clinical order | | OMG - Algemene klinische aanvraag | | added v2.4
O20 | ORG/ORL - General clinical order response | | ORG/ORL - Antwoord algemene klinische aanvraag | | added v2.4
O21 | OML - Laboratory order | | OML - Laboratoriumaanvraag | | added v2.4
O22 | ORL - General laboratory order response message to any OML | | ORL - Algemeen laboratoriumaanvraag antwoordbericht op alle OML | | added v2.5
O23 | OMI - Imaging order | | OMI - Beeldaanvraag | | added v2.5
O24 | ORI - Imaging order response message to any OMI | | ORI - Beeldaanvraag antwoordbericht op alle OMI | | added v2.5
O25 | RDE - Pharmacy/treatment refill authorization request | | RDE - Autorisatieverzoek voor herhaal medicatie/therapie | | added v2.5
O26 | RRE - Pharmacy/Treatment Refill Authorization Acknowledgement | | RRE - Antwoord autorisatieverzoek voor herhaal medicatie/therapie | | added v2.5
O27 | OMB - Blood product order | | OMB - Bloedproductaanvraag | | added v2.5
O28 | ORB - Blood product order acknowledgment | | ORB - Antwoordbericht bloedproductaanvraag | | added v2.5
O29 | BPS - Blood product dispense status | | BPS - Bloedproduct verstrekkingstatus | | added v2.5
O30 | BRP - Blood product dispense status acknowledgment | | BRP - Antwoordbericht bloedproduct verstrekkingstatus | | added v2.5
O31 | BTS - Blood product transfusion/disposition | | BTS - Bloedproduct transfusie/dispositie | | added v2.5
O32 | BRT - Blood product transfusion/disposition acknowledgment | | BRT - Antwoordbericht bloedproduct transfusie/dispositie | | added v2.5
O33 | OML - Laboratory order for multiple orders related to a single specimen | | OML - Laboratoriumaanvraag voor meerdere aanvragen met betrekking tot één monster | | added v2.5
O34 | ORL - Laboratory order response message to a multiple order related to single specimen OML | | ORL - Antwoordbericht laboratoriumaanvraag voor meerdere aanvragen met betrekking tot één monster OML | | added v2.5
O35 | OML - Laboratory order for multiple orders related to a single container of a specimen | | OML - Laboratoriumaanvraag voor meerdere aanvragen met betrekking tot één container van een monster OML | | added v2.5
O36 | ORL - Laboratory order response message to a single container of a specimen OML | | ORL - Antwoordbericht laboratoriumaanvraag voor meerdere aanvragen met betrekking tot één container van een monster OML | | added v2.5
O37 | OPL - Population/Location-Based Laboratory Order Message | | OPL - Populatie/locatie-gebaseerd laboratoriumaanvraag bericht | | added v2.6
O38 | OPR - Population/Location-Based Laboratory Order Acknowledgment Message | | OPR - Bevestiging populatie/locatie-gebaseerd laboratoriumaanvraag bericht | | added v2.6
O39 | Specimen shipment centric laboratory order | | Monsterverzending-georiënteerde laboratoriumaanvraag | | added v2.7
O40 | Specimen Shipment Centric Laboratory Order Acknowledgment Message | | Antwoord monsterverzending-georiënteerde laboratoriumaanvraag | | added v2.7
O41 | DBC - Create Donor Record Message | | DBC - Maak donorrecord bericht | | added v2.8
O42 | DBU - Update Donor Record Message | | DBU - Update donorrecord bericht | | added v2.8
O43 | General Order Message with Document Payload Acknowledgement Message | | Algemeen aanvraagbericht met documentinhoud bevestigingsbericht | | added v2.8
O44 | Donor Registration - Minimal Message | | Donorregistratie - minimaal bericht | | added v2.8
O45 | Donor Eligibility Observations Message | | Donorkwalificatie observaties bericht | | added v2.8
O46 | Donor Eligiblity Message | | Donorkwalificatie bericht | | added v2.8
O47 | Donor Request to Collect Message | | Verzoekbericht donatie verzameling | | added v2.8
O48 | Donation Procedure Message | | Procedurebericht donatie | | added v2.8
P01 | BAR/ACK - Add patient accounts | Eröffnung eines Patientenkontos | BAR/ACK - Voeg patiëntaccounts toe | | from v2.1
P02 | BAR/ACK - Purge patient accounts | Löschen der Abrechnungsdaten eines Patientenkontos | BAR/ACK - Verwijder patiëntaccounts | | from v2.1
P03 | DFT/ACK - Post detail financial transaction | Leistungs- und Abrechnungsinformationen | Details financiële verrichting | | from v2.1
P04 | QRY/DSP - Generate bill and A/R statements | Druck und Anzeige von Rechnungen | QRY/DSP - Maak factuur en verkregen diensten | Deprecated | from v2.1
P05 | BAR/ACK - Update account | Änderung eines Patientenkontos | BAR/ACK - Update account | | added v2.3
P06 | BAR/ACK - End account | Abschluß eines Patientenkontos | BAR/ACK - Beëindig account | | added v2.3
P07 | PEX - Unsolicited initial individual product experience report | unaufgeforderte individueller Produktersterfahrungsbericht | PEX - Ongevraagd initieel rapport individueel productervaringen | | added v2.3
P08 | PEX - Unsolicited update individual product experience report | Änderung individueller Produktersterfahrungsbericht | PEX - Ongevraagde update rapport individueel productervaringen | | added v2.3
P09 | SUR - Summary product experience report | zusammenfassender Produkterfahrungsbericht | SUR - Samenvatting rapport productervaringen | Deprecated | added v2.3

P10 | BAR/ACK -Transmit Ambulatory Payment Classification(APC) | | BAR/ACK - Verstuur Ambulatory Payment Classification (APC) | | added v2.4
P11 | DFT/ACK - Post Detail Financial Transactions - New | | DFT/ACK - Verstuur financiële verrichtingen - Nieuw | | added v2.5
P12 | BAR/ACK - Update Diagnosis/Procedure | | BAR/ACK - Update diagnose/behandeling | | added v2.5
PC1 | PPR - PC/ problem add | Problem hinzufügen | PPR - PC/Voeg probleem toe | | added v2.3
PC2 | PPR - PC/ problem update | Problem ändern | PPR - PC/Update probleem | | added v2.3
PC3 | PPR - PC/ problem delete | Problem löschen | PPR - PC/Verwijder probleem | | added v2.3
PC4 | QRY - PC/ problem query | Problem abfragen | PPR - PC/Query problemen | Deprecated | added v2.3
PC5 | PRR - PC/ problem response | Problem Anfrage beantworten | PPR - PC/Antwoord problemen | Deprecated | added v2.3
PC6 | PGL - PC/ goal add | Ziel hinzufügen | PGL - PC/Voeg doel toe | | added v2.3
PC7 | PGL - PC/ goal update | Ziel ändern | PGL - PC/Update doel | | added v2.3
PC8 | PGL - PC/ goal delete | Ziel löschen | PGL - PC/Verwijder doel | | added v2.3
PC9 | QRY - PC/ goal query | Ziel abfragen | PGL - PC/Query doelen | Deprecated | added v2.3
PCA | PPV - PC/ goal response | Ziel Anfrage beantworten | PPV - PC/Antwoord doelen | Deprecated | added v2.3
PCB | PPP - PC/ pathway (problem-oriented) add | (problemorientierte) Leitlinie hinzufügen | PPP - PC/Voeg zorgpad toe (probleemgeoriënteerd) | | added v2.3
PCC | PPP - PC/ pathway (problem-oriented) update | (problemorientierte) Leitlinie ändern | PPP - PC/Update zorgpad (probleemgeoriënteerd) | | added v2.3
PCD | PPP - PC/ pathway (problem-oriented) delete | (problemorientierte) Leitlinie löschen | PPP - PC/Verwijder zorgpad (probleemgeoriënteerd) | | added v2.3
PCE | QRY - PC/ pathway (problem-oriented) query | (problemorientierte) Leitlinie abfragen | QRY - PC/Query zorgpaden (probleemgeoriënteerd) | Deprecated | added v2.3
PCF | PTR - PC/ pathway (problem-oriented) query response | (problemorientierte) Leitlinie Anfrage beantworten | PTR - PC/Antwoord zorgpaden (probleemgeoriënteerd) | Deprecated | added v2.3
PCG | PPG - PC/ pathway (goal-oriented) add | (zielorientierte) Leitlinie hinzufügen | PPG - PC/Voeg zorgpad toe (doelgeoriënteerd) | | added v2.3
PCH | PPG - PC/ pathway (goal-oriented) update | (zielorientierte) Leitlinie ändern | PPG - PC/Update zorgpad (doelgeoriënteerd) | | added v2.3
PCJ | PPG - PC/ pathway (goal-oriented) delete | (zielorientierte) Leitlinie löschen | PPG - PC/Verwijder zorgpad (doelgeoriënteerd) | | added v2.3
PCK | QRY - PC/ pathway (goal-oriented) query | (zielorientierte) Leitlinie abfragen | QRY - PC/Query zorgpaden (doelgeoriënteerd) | Deprecated | added v2.3
PCL | PPT - PC/ pathway (goal-oriented) query response | (zielorientierte) Leitlinie Anfrage beantworten | PPT - PC/Antwoord zorgpaden (doelgeoriënteerd) | Deprecated | added v2.3
Q01 | QRY/DSR - Query sent for immediate response | Anfrage mit sofortiger Antwort | QRY/DSR - Query verzonden voor directe beantwoording | Deprecated | from v2.1
Q02 | QRY/QCK - Query sent for deferred response | Anfrage mit verzögerter Antwort | QRY/QCK - Query verzonden voor indirecte beantwoording | Deprecated | from v2.1
Q03 | DSR/ACK - Deferred response to a query | Verzögerte Antwort auf Anfrage | DSR/ACK - Indirect antwoord op een query | Deprecated | added v2.2
Q04 | EQQ - Embedded query language query | | EQQ - Embedded query language query | deprecated | added v2.3.1, removed after v2.5.1
Q05 | UDM/ACK - Unsolicited display update message | Sofortige Bildschirmanzeige (Eilmeldung) | UDM/ACK - Ongevraagd bericht voor weergave update | | added v2.2
Q06 | OSQ/OSR - Query for order status | Abfrage des Auftragsstatus | OSQ/OSR - Query om aanvraagstatus | Deprecated | added v2.3
Q07 | VQQ - Virtual table query | | VQQ - Virtuele tabel query | deprecated | added v2.3.1, removed after v2.5.1
Q08 | SPQ - Stored procedure request | | SPQ - Verzoek stored procedure | deprecated | added v2.3.1, removed after v2.5.1
Q09 | RQQ - event replay query | | RQQ - Query event replay | deprecated | added v2.3.1, removed after v2.5.1
Q11 | QBP - Query by parameter requesting an RSP segment pattern response | | QBP - Query op parameter met als antwoord een RSP-segmentpatroon | | added v2.5
Q13 | QBP - Query by parameter requesting an RTB - tabular response | | QBP - Query op parameter met als antwoord een RTB-tabelpatroon | | added v2.5
Q15 | QBP - Query by parameter requesting an RDY display response | | QBP - Query op parameter met als antwoord een RDY-weergavepatroon | | added v2.5
Q16 | QSB - Create subscription | | QSB - Maak abonnement | | added v2.4
Q17 | QVR - Query for previous events | | QVR - Query op vorige events | | added v2.4
Q21 | QBP - Get person demographics | | QBP - Query persoonsgegevens | | added v2.4
Q22 | QBP - Find candidates | | QBP - Zoek kandidaten | | added v2.4
Q23 | QBP - Get corresponding identifiers | | QBP - Query bijbehorende ID's | | added v2.4
Q24 | QBP - Allocate identifiers | | QBP - Alloceer ID's | | added v2.4
Q25 | QBP - Personnel Information by Segment Query | | QBP - Query personeelinformatie op segment | | added v2.4
Q26 | ROR - Pharmacy/treatment order response | | ROR - Antwoordbericht aanvraag medicatie/therapie | Deprecated | added v2.5
Q27 | RAR - Pharmacy/treatment administration information | | RAR - Medicatie/therapie toedieningsinformatie | Deprecated | added v2.5
Q28 | RDR - Pharmacy/treatment dispense information | | RDR - Medicatie/therapie verstrekkingsinformatie | Deprecated | added v2.5
Q29 | RER - Pharmacy/treatment encoded order information | | RER - Medicatie/therapie gecodeerde aanvraag-informatie | Deprecated | added v2.5
Q30 | RGR - Pharmacy/treatment dose information | | RER - Medicatie/therapie doseringsinformatie | Deprecated | added v2.5
Q31 | QBP Query Dispense history | | QBP - Query verstrekkingshistorie | | added v2.5.1
Q32 | Find Candidates including Visit Information | | Zoek kandidaten inclusief bezoekinformatie | | added v2.7
Q33 | QBP - Get Donor Record Candidates | | QBP - Ophalen donorrecord kandidaten | | added v2.8
Q34 | QBP - Get Donor Record | | QBP - Ophalen donorrecord | | added v2.8
R01 | ORU/ACK - Unsolicited transmission of an observation message | unangeforderte Übermittlung eines Befundes | ORU/ACK - Ongevraagde verzending van een observatiebericht | | from v2.1
R02 | QRY - Query for results of observation | Anfrage nach Untersuchungsergebnis | Query op observatieresultaten | Deprecated | added v2.2
R03 | QRY/DSR Display-oriented results, query/unsol. update (for backward compatibility only) (Replaced by Q05) | Anzeigeorientiertes Ergebnis | QRY/DSR - Weergave-georiënteerde resultaten, query/ongevr. update (voor backward compatibiliteit) (Vervangen door Q05) | deprecated | from v2.1, removed after v2.5.1
R04 | ORF - Response to query; transmission of requested observation | Antwort auf Anfrage / Übermittlung eines angeforderten Ergebnisses | ORF - Antwoord op query; verzending van aangevraagde observatie | Deprecated | added v2.2

R05 | QRY/DSR - query for display results (See Q01) | Anfrage nach anzeigeorientierten Ergebnissen | QRY/DSR - Query op weergave resultaten (zie Q01) | deprecated | added v2.3, removed after v2.4

R06 | UDM - unsolicited update/display results (See Q05) | unaufgeforderte Änderung anzeigeorientierter Ergebnisse | UDM - Ongevraagde update/weergave resultaten (zie Q05) | deprecated | added v2.3, removed after v2.4

R07 | EDR - Enhanced Display Response | | EDR - Antwoord verrijkte weergave | deprecated | added v2.3.1, removed after v2.5.1

R08 | TBR - Tabular Data Response | | TBR - Antwoord gegevens in tabelvorm | deprecated | added v2.3.1, removed after v2.5.1

R09 | ERP - Event Replay Response | | ERP - Antwoord event replay | deprecated | added v2.3.1, removed after v2.5.1

R0R | R0R - Pharmacy prescription order query response | | R0R - Medicatievoorschriftaanvraag query antwoord | deprecated | added v2.3.1, removed after v2.3.1

R21 | OUL - Unsolicited laboratory observation | | OUL - Ongevraagde laboratoriumobservatie | Deprecated | added v2.4

R22 | OUL - Unsolicited Specimen Oriented Observation Message | | OUL - Ongevraagde monster-georiënteerde observatie | | added v2.5

R23 | OUL - Unsolicited Specimen Container Oriented Observation Message | | OUL - Ongevraagde monstercontainer-georiënteerde observatie | | added v2.5

R24 | OUL - Unsolicited Order Oriented Observation Message | | OUL - Ongevraagde aanvraag-georiënteerde observatie | | added v2.5

R25 | OPU - Unsolicited Population/Location-Based Laboratory Observation Message | | OPU - Ongevraagde populatie/locatie-gebaseerd laboratoriumobservatie | | added v2.6

R26 | OSM - Unsolicited Specimen Shipment Manifest Message | | OSM - Ongevraagde monsterverzending manifest | | added v2.7

R30 | ORU - Unsolicited Point-Of-Care Observation Message Without Existing Order - Place An Order | | ORU - Ongevraagde Point-Of-Care observatie zonder voorafgaande aanvraag - Plaats een aanvraag | | added v2.5

R31 | ORU - Unsolicited New Point-Of-Care Observation Message - Search For An Order | | ORU - Ongevraagde nieuwe Point-Of-Care observatie - Zoek een aanvraag | | added v2.5

R32 | ORU - Unsolicited Pre-Ordered Point-Of-Care Observation | | ORU - Ongevraagde pre-ordered Point-Of-Care observatie | | added v2.5

R33 | ORA - Observation Report Acknowledgement | | ORA - Bevestiging observatieverslag | | added v2.7

R40 | ORU - Unsolicited Report Alarm | | ORU - Ongevraagd rapport alarm | | added v2.8

R41 | Observation Report Alert Acknowledgement | | Bevestiging observatierapport waarschuwing | | added v2.8

RAR | RAR - Pharmacy administration information query response | Antwort bzgl. der Behandlungs-/Darreichungsform | RAR - Medicatietoediening-informatie query antwoord | deprecated | added v2.3, removed after v2.4

RDR | RDR - Pharmacy dispense information query response | Antwort bzgl. des zu verabreichenden Medikamentes bzw. der Behandlung | RDR - Medicatieverstrekking-informatie query antwoord | deprecated | added v2.3, removed after v2.4

RER | RER - Pharmacy encoded order information query response | Antwort bzgl. des zu verabreichenden Medikamentes bzw. der Behandlung | RER - Medicatie gecodeerde aanvraaginformatie query antwoord | deprecated | added v2.3, removed after v2.4

RGR | RGR - Pharmacy dose information query response | Antwort bzgl. der Dosis bzw. der Frequenz der Behandlung | RGR - Medicatiedosering-informatie query antwoord | deprecated | added v2.3, removed after v2.4

ROR | ROR - Pharmacy prescription order query response | Antwort bzgl. der Verschreibungsanforderung des Arzneiverordnung bzw. d.Behandlg | ROR - Medicatievoorschrift aanvraag query antwoord | Deprecated | added v2.3

S01 | SRM/SRR - Request new appointment booking | Terminanforderung | SRM/SRR - Verzoek boeken nieuwe afspraak | | added v2.3

S02 | SRM/SRR - Request appointment rescheduling | Anforderung für Terminverschiebung | SRM/SRR - Verzoek verzetten afspraak | | added v2.3

S03 | SRM/SRR - Request appointment modification | Anforderung für inhaltliche Terminänderung | SRM/SRR - Verzoek aanpassen afspraak | | added v2.3

S04 | SRM/SRR - Request appointment cancellation | Absage eines Termins | SRM/SRR - Verzoek annuleren afspraak | | added v2.3

S05 | SRM/SRR - Request appointment discontinuation | Aussetzung des aktuellen oder weiterer Termine | SRM/SRR - Verzoek stopzetten afspraak | | added v2.3

S06 | SRM/SRR - Request appointment deletion | Stornierung eines Termins | SRM/SRR - Verzoek verwijderen afspraak | | added v2.3

S07 | SRM/SRR - Request addition of service/resource on appointment | Anforderung zusätzlicher Leistungen/Voraussetzungen zu einem Termin | SRM/SRR - Verzoek toevoegen dienst/resource bij afspraak | | added v2.3

S08 | SRM/SRR - Request modification of service/resource on appointment | Änderungsanforderung für zusätzliche Leistungen/Voraussetzungen zu einem Termin | SRM/SRR - Verzoek wijzigen dienst/resource bij afspraak | | added v2.3

S09 | SRM/SRR - Request cancellation of service/resource on appointment | Absage für zusätzliche Leistungen/Voraussetzungen zu einem Termin | SRM/SRR - Verzoek annuleren dienst/resource bij afspraak | | added v2.3

S10 | SRM/SRR - Request discontinuation of service/resource on appointment | Aussetzung für zusätzliche Leistungen/Voraussetzungen zu einem Termin | SRM/SRR - Verzoek stopzetten dienst/resource bij afspraak | | added v2.3

S11 | SRM/SRR - Request deletion of service/resource on appointment | Stornierung für zusätzliche Leistungen/Voraussetzungen zu einem Termin | SRM/SRR - Verzoek verwijderen dienst/resource bij afspraak | | added v2.3

S12 | SIU/ACK - Notification of new appointment booking | Benachrichtigung über Terminvergabe | SIU/ACK - Notificatie van nieuw geboekte afspraak | | added v2.3

S13 | SIU/ACK - Notification of appointment rescheduling | Benachrichtigung für Terminverschiebung | SIU/ACK - Notificatie van verzetten afspraak | | added v2.3

S14 | SIU/ACK - Notification of appointment modification | Benachrichtigung für inhaltliche Terminänderung | SIU/ACK - Notificatie van wijzigen afspraak | | added v2.3

S15 | SIU/ACK - Notification of appointment cancellation | Benachrichtigung über Terminabsage | SIU/ACK - Notificatie van annuleren afspraak | | added v2.3

S16 | SIU/ACK - Notification of appointment discontinuation | Benachrichtigung über Aussetzung des aktuellen oder weiterer Termine | SIU/ACK - Notificatie van stopzetten afspraak | | added v2.3

S17 | SIU/ACK - Notification of appointment deletion | Benachrichtigung über Stornierung eines Termins | SIU/ACK - Notificatie van verwijderen afspraak | | added v2.3

S18 | SIU/ACK - Notification of addition of service/resource on appointment | Benachrichtigung über zusätzlicher Leistungen/Voraussetzungen zu einem Termin | SIU/ACK - Notificatie van toevoegen dienst/resource bij afspraak | | added v2.3

S19 | SIU/ACK - Notification of modification of service/resource on appointment | Änderungsbenachrichtigung f.zusätzl. Leistungen/Voraussetzungen zu einem Termin | SIU/ACK - Notificatie van wijzigen dienst/resource bij afspraak | | added v2.3

S20 | SIU/ACK - Notification of cancellation of service/resource on appointment | Benachrichtigung f. zusätzliche Leistungen/Voraussetzungen zu einem Terminabsage | SIU/ACK - Notificatie van annuleren dienst/resource bij afspraak | | added v2.3

S21 | SIU/ACK - Notification of discontinuation of service/resource on appointment | Benachrichtigung über Aussetzung für zusätzliche Leistungen/Voraussetzungen | SIU/ACK - Notificatie van stopzetten dienst/resource bij afspraak | | added v2.3

S22 | SIU/ACK - Notification of deletion of service/resource on appointment | Benachrichtigung Stornierg.f.zusätzl.Leistungen/Voraussetzungen zu einem Termin | SIU/ACK - Notificatie van verwijderen dienst/resource bij afspraak | | added v2.3

S23 | SIU/ACK - Notification of blocked schedule time slot(s) | Benachrichtigung über nicht verfügbare Zeitbereiche | SIU/ACK - Notificatie van geblokkeerde agenda tijdblok(ken) | | added v2.3
S24 | SIU/ACK - Notification of opened ("unblocked") schedule time slot(s) | Benachrichtigung über (wieder) verfügbare Zeitbereiche | SIU/ACK - Notificatie van open (niet-geblokkeerde) agenda tijdblok(ken) | | added v2.3
S25 | SQM/SQR - Schedule query message and response | Anfrage nach Zeitplaninformation | SQM/SQR - Query agenda-informatie en antwoord | Deprecated | added v2.3
S26 | SIU/ACK Notification that patient did not show up for schedule appointment | Benachrichtigung über Nichterscheinen eines Patienten | SIU/ACK - Notificatie dat patiënt niet is komen opdagen voor agenda-afspraak | | added v2.3
S27 | SIU/ACK - Broadcast Notification of Scheduled Appointments | | SIU/ACK - Broadcast notificatie van geplande afspraken | | added v2.7
S28 | SLR/SLS - Request new sterilization lot | | SLR/SLS - Verzoek nieuwe lot sterilisatie | | added v2.6
S29 | SLR/SLS - Request Sterilization lot deletion | | SLR/SLS - Verzoek verwijderen lot sterilisatie | | added v2.6
S30 | STI/STS - Request item | | STI/STS - Verzoek item | | added v2.6
S31 | SDR/SDS - Request anti-microbial device data | | SDR/SDS - Verzoek anti-microbisch apparaatgegevens | | added v2.6
S32 | SMD/SMS - Request anti-microbial device cycle data | | SMD/SMS - Verzoek anti-microbisch apparaatomloopgegevens | | added v2.6
S33 | STC/ACK - Notification of sterilization configuration | | STC/ACK - Notificatie van sterilisatie configuratie | | added v2.6
S34 | SLN/ACK - Notification of sterilization lot | | SLN/ACK - Notificatie van sterilisatie lot | | added v2.6
S35 | SLN/ACK - Notification of sterilization lot deletion | | SLN/ACK - Notificatie verwijdering van sterilisatie lot | | added v2.6
S36 | SDN/ACK - Notification of anti-microbial device data | | SDN/ACK - Notificatie anti-microbisch apparaatgegevens | | added v2.6
S37 | SCN/ACK - Notification of anti-microbial device cycle data | | SDN/ACK - Notificatie anti-microbisch apparaatomloopgegevens | | added v2.6
T01 | MDM/ACK - Original document notification | Benachrichtigung über die Neuanlage eines Dokuments ohne Inhalt | MDM/ACK - Notificatie origineel document | | added v2.3
T02 | MDM/ACK - Original document notification and content | Benachrichtigung über die Neuanlage eines Dokuments mit Inhaltsübermittlung | MDM/ACK - Notificatie origineel document met inhoud | | added v2.3
T03 | MDM/ACK - Document status change notification | Benachrichtigung über die Statusänderung eines Dokuments (ohne Inhalt) | MDM/ACK - Notificatie wijzigen documentstatus | | added v2.3
T04 | MDM/ACK - Document status change notification and content | Benachrichtigung über die Statusänderung eines Dokuments (mit Inhalt) | MDM/ACK - Notificatie wijzigen documentstatus met inhoud | | added v2.3
T05 | MDM/ACK - Document addendum notification | Benachrichtigung über die Ergänzung eines Dokuments (ohne Inhalt) | MDM/ACK - Notificatie documentaddendum | | added v2.3
T06 | MDM/ACK - Document addendum notification and content | Benachrichtigung über die Ergänzung eines Dokuments (mit Inhalt) | MDM/ACK - Notificatie documentaddendum met inhoud | | added v2.3
T07 | MDM/ACK - Document edit notification | Benachrichtigung über die Änderung eines Dokuments (ohne Inhalt) | MDM/ACK - Notificatie wijziging document | | added v2.3
T08 | MDM/ACK - Document edit notification and content | Benachrichtigung über die Änderung eines Dokuments (mit Inhalt) | MDM/ACK - Notificatie wijziging document met inhoud | | added v2.3
T09 | MDM/ACK - Document replacement notification | Benachrichtigung über den Austausch eines Dokuments (ohne Inhalt) | MDM/ACK - Notificatie vervanging document | | added v2.3
T10 | MDM/ACK - Document replacement notification and content | Benachrichtigung über den Austausch eines Dokuments (mit Inhalt) | MDM/ACK - Notificatie vervanging document met inhoud | | added v2.3
T11 | MDM/ACK - Document cancel notification | Benachrichtigung über die Löschung eines Dokuments | MDM/ACK - Notificatie annuleren document | | added v2.3
T12 | QRY/DOC - Document query | Dokumentanfrage | QRY/DOC - Query documenten | Deprecated | added v2.3
U01 | ESU/ACK - Automated equipment status update | | ESU/ACK - Geautomatiseerde materiaal status update | | added v2.4
U02 | ESR/ACK - Automated equipment status request | | ESR/ACK - Geautomatiseerde materiaal status verzoek | | added v2.4
U03 | SSU/ACK - Specimen status update | | SSU/ACK - Monster status update | | added v2.4
U04 | SSR/ACK - specimen status request | | SSR/ACK - Monster status verzoek | | added v2.4
U05 | INU/ACK - Automated equipment inventory update | | INU/ACK - Geautomatiseerde materiaal voorraad update | | added v2.4
U06 | INR/ACK - Automated equipment inventory request | | INR/ACK - Geautomatiseerde materiaal voorraad verzoek | | added v2.4
U07 | EAC/ACK - Automated equipment command | | EAC/ACK - Geautomatiseerde materiaal commando | | added v2.4
U08 | EAR/ACK - Automated equipment response | | EAR/ACK - Geautomatiseerde materiaal antwoord | | added v2.4
U09 | EAN/ACK - Automated equipment notification | | EAN/ACK - Geautomatiseerde materiaal notificatie | | added v2.4
U10 | TCU/ACK - Automated equipment test code settings update | | TCU/ACK - Geautomatiseerde materiaal testcode instellingen update | | added v2.4
U11 | TCR/ACK - Automated equipment test code settings request | | TCR/ACK - Geautomatiseerde materiaal testcode instellingen verzoek | | added v2.4
U12 | LSU/ACK - Automated equipment log/service update | | LSU/ACK - Geautomatiseerde materiaal log/service update | | added v2.4
U13 | LSR/ACK - Automated equipment log/service request | | LSR/ACK - Geautomatiseerde materiaal log/service verzoek | | added v2.4
V01 | VXQ - Query for vaccination record | Anfrage nach Impfstatus eines Patienten | VQX - Query op vaccinatiegegevens | Deprecated | added v2.3
V02 | VXX - Response to vaccination query returning multiple PID matches | Antwort auf Impfstatusanfrage bei nicht-eindeutiger Patienten-ID | VXX - Antwoord op query vaccinatiegegevens met meerdere PID's | Deprecated | added v2.3
V03 | VXR - Vaccination record response | Antwort auf Impfstatusanfrage zu einem Patienten | VXR - Antwoord op query vaccinatiegegevens | Deprecated | added v2.3
V04 | VXU - Unsolicited vaccination record update | unaufgeforderte Änderung zu dem Impfstatus eines Patienten | VXU - Ongevraagde update vaccinatiegegevens | | added v2.3
Varies | MFQ/MFR - Master files query (use event same as asking for e.g. M05 - location) | allgemeine Stammdatenanfrage | MFQ/MFR - Masterbestanden query (gebruik event zoals bij vragen naar bijv. M05 - locatie) | | added v2.3
W01 | ORU - Waveform result, unsolicited transmission of requested information | unaufgeforderte Übermittlung von Signaldaten | ORU - Waveformresultaat, ongevraagde verzending van aangevraagde informatie | Deprecated | added v2.3
W02 | QRF - Waveform result, response to query | angeforderte Übermittlung von Signaldaten | QRF - Waveformresultaat, antwoord op query | Deprecated | added v2.3
X01 | PEX - Product experience | | PEX - Productervaring | deprecated | added v2.3, removed after v2.3

4.2.13.4 HL7 Version 2 Table 0004

URL: https://hl7.org/fhir/STU3/v2/0004/index.html

This page is part of the FHIR Specification (v3.0.2: STU 3). The current version which supercedes this version is 4.0.1. For a full list of available versions, see the Directory of published versions

Vocabulary Work Group | Maturity Level: N/A | External | Use Context: Any

This is a table defined as part of HL7 v2 . Related FHIR content: v2 Patient Class.

Summary

Name: | v2 Patient Class
Definition: | FHIR Value set/code system definition for HL7 v2 table 0004 (Patient Class)
Code System URL: | http://hl7.org/fhir/v2/0004
Value Set URL: | http://hl7.org/fhir/ValueSet/v2-0004
OID: | ??
CodeSystem Resource | XML / JSON
ValueSet Resource | XML / JSON

This value set is used in the following places:

* This value set is the designated 'entire code system' value set for v2 Patient Class

4.2.13.4.1 Code System Content

Patient Class

Code | Description | Deutsch (German) | Nederlands (Dutch) | Comment | Version
B | Obstetrics | Geburtshilfe | Obstetrie | | added v2.2
C | Commercial Account | | Commercieel account | | added v2.4
E | Emergency | Notfall | Spoed | | from v2.1
I | Inpatient | stationär | Klinisch | | from v2.1
N | Not Applicable | Segment nicht anwendbar | Niet van toepassing | | added v2.4
O | Outpatient | ambulant | Poliklinisch | | from v2.1
P | Preadmit | Voraufnahme | Vooropname | | from v2.1
R | Recurring patient | Wiederholungspatient | Routine | | added v2.2
U | Unknown | unbekannt | Onbekend | | added v2.4

4.2.13.5 HL7 Version 2 Table 0005

URL: https://hl7.org/fhir/STU3/v2/0005/index.html

This page is part of the FHIR Specification (v3.0.2: STU 3). The current version which supercedes this version is 4.0.1. For a full list of available versions, see the Directory of published versions

Vocabulary Work Group | Maturity Level: N/A | External | Use Context: Any

This is a table defined as part of HL7 v2 . Related FHIR content: v2 Race.

Summary

Name: | v2 Race
Definition: | FHIR Value set/code system definition for HL7 v2 table 0005 (Race)
Value Set URL: | http://hl7.org/fhir/ValueSet/v2-0005
OID: | ??
ValueSet Resource | XML / JSON

This value set is not currently used

4.2.13.5.1 Logical Definition

Race

Code | System | Description | Comment | Version
1002-5 | http://hl7.org/fhir/v3/Race | American Indian or Alaska Native | | added v2.4
2028-9 | http://hl7.org/fhir/v3/Race | Asian | | added v2.4
2054-5 | http://hl7.org/fhir/v3/Race | Black or African American | | added v2.4
2076-8 | http://hl7.org/fhir/v3/Race | Native Hawaiian or Other Pacific Islander | | added v2.4
2106-3 | http://hl7.org/fhir/v3/Race | White | | added v2.4
2131-1 | http://hl7.org/fhir/v3/Race | Other Race | | added v2.4

4.2.13.7 HL7 Version 2 Table 0007

URL: https://hl7.org/fhir/STU3/v2/0007/index.html

This page is part of the FHIR Specification (v3.0.2: STU 3). The current version which supercedes this version is 4.0.1. For a full list of available versions, see the Directory of published versions

Vocabulary Work Group | Maturity Level: N/A | External | Use Context: Any

This is a table defined as part of HL7 v2 . Related FHIR content: v2 Admission Type.

Summary

Name: | v2 Admission Type
Definition: | FHIR Value set/code system definition for HL7 v2 table 0007 (Admission Type)

Code System URL: | http://hl7.org/fhir/v2/0007
Value Set URL: | http://hl7.org/fhir/ValueSet/v2-0007
OID: | ??
CodeSystem Resource | XML / JSON
ValueSet Resource | XML / JSON

This value set is used in the following places:

* This value set is the designated 'entire code system' value set for v2 Admission Type

4.2.13.7.1 Code System Content

Admission Type

Code | Description | Deutsch (German) | Nederlands (Dutch) | Comment | Version
A | Accident | Unfall / Notarztwagen | Ongeluk | | from v2.1
C | Elective | wahlfreie Aufnahme | Eigen keuze | | added v2.4
E | Emergency | Notfall ohne Einweisung | Spoed | | from v2.1
L | Labor and Delivery | Entbindung / Geburt | Geboorte en bevalling | | from v2.1
N | Newborn (Birth in healthcare facility) | Neugeborenes | Nieuwgeborene (geboorte in zorginstelling) | | added v2.4
R | Routine | Normalaufnahme | Routine | | from v2.1
U | Urgent | dringliche Aufnahme | Urgent | | added v2.4

4.2.13.8 HL7 Version 2 Table 0008

URL: https://hl7.org/fhir/STU3/v2/0008/index.html

This page is part of the FHIR Specification (v3.0.2: STU 3). The current version which supercedes this version is 4.0.1. For a full list of available versions, see the Directory of published versions

Vocabulary Work Group | Maturity Level: N/A | External | Use Context: Any

This is a table defined as part of HL7 v2 . Related FHIR content: v2 Acknowledgment code.

Summary

Name: | v2 Acknowledgment code
Definition: | FHIR Value set/code system definition for HL7 v2 table 0008 (Acknowledgment code)
Code System URL: | http://hl7.org/fhir/v2/0008
Value Set URL: | http://hl7.org/fhir/ValueSet/v2-0008
OID: | ??
CodeSystem Resource | XML / JSON
ValueSet Resource | XML / JSON

This value set is used in the following places:

* This value set is the designated 'entire code system' value set for v2 Acknowledgment code

4.2.13.8.1 Code System Content

Acknowledgment code

Code | Description | Deutsch (German) | Nederlands (Dutch) | Comment | Version
AA | Original mode: Application Accept - Enhanced mode: Application acknowledgment: Accept | akzeptiert durch Anwendung | Original modus: Applicatiebevestiging - Enhanced modus: Applicatiebevestiging: accepteer | | from v2.1
AE | Original mode: Application Error - Enhanced mode: Application acknowledgment: Error | Fehler in Anwendung | Original modus: Applicatiefout - Enhanced modus: Applicatiebevestiging: fout | | from v2.1
AR | Original mode: Application Reject - Enhanced mode: Application acknowledgment: Reject | Abgelehnt durch Anwendung | Original modus: Applicatieweigering - Enhanced modus: Applicatiebevestiging: weiger | | from v2.1
CA | Enhanced mode: Accept acknowledgment: Commit Accept | Bei Eingangsprüfung akzeptiert ("committed") | Enhanced modus: Ontvangstbevestiging: accepteer ontvangst | | added v2.2
CE | Enhanced mode: Accept acknowledgment: Commit Error | Fehler bei Eingangsprüfung | Enhanced modus: Ontvangstbevestiging: fout in ontvangst | | added v2.2
CR | Enhanced mode: Accept acknowledgment: Commit Reject | Bei Eingangsprüfung abgelehnt | Enhanced modus: Ontvangstbevestiging: weigering te ontvangen | | added v2.2

4.2.13.9 HL7 Version 2 Table 0009

URL: https://hl7.org/fhir/STU3/v2/0009/index.html

This page is part of the FHIR Specification (v3.0.2: STU 3). The current version which supercedes this version is 4.0.1. For a full list of available versions, see the Directory of published versions

Vocabulary Work Group | Maturity Level: N/A | External | Use Context: Any

This is a table defined as part of HL7 v2 . Related FHIR content: v2 Ambulatory Status.

Summary

Name: | v2 Ambulatory Status
Definition: | FHIR Value set/code system definition for HL7 v2 table 0009 (Ambulatory Status)
Code System URL: | http://hl7.org/fhir/v2/0009
Value Set URL: | http://hl7.org/fhir/ValueSet/v2-0009
OID: | ??

CodeSystem Resource | XML / JSON
ValueSet Resource | XML / JSON

This value set is used in the following places:

* This value set is the designated 'entire code system' value set for v2 Ambulatory Status

4.2.13.9.1 Code System Content

Ambulatory Status

Code | Description | Deutsch (German) | Nederlands (Dutch) | Comment | Version
A0 | No functional limitations | Keine funktionalen Einschränkungen | Geen functionele beperkingen | | from v2.1
A1 | Ambulates with assistive device | Patient benötigt Hilfsmittel | Loopt met ondersteunend middel | | from v2.1
A2 | Wheelchair/stretcher bound | Rollstuhl / Trage notwendig | Gebonden aan rolstoel/stretcher | | from v2.1
A3 | Comatose; non-responsive | Komatös; nicht ansprechbar | Comateus; niet-responsief | | from v2.1
A4 | Disoriented | Desorientiert | Gedesoriënteerd | | from v2.1
A5 | Vision impaired | Sehstörung | Visueel beperkt | | from v2.1
A6 | Hearing impaired | Schwerhörigkeit | Auditief beperkt | | from v2.1
A7 | Speech impaired | Sprachstörung | Spraak beperkt | | from v2.1
A8 | Non-English speaking | der Landessprache nicht mächtig | Niet-Engelssprekend | | from v2.1
A9 | Functional level unknown | Unbekannter Zustand | Functioneel niveau onbekend | | from v2.1
B1 | Oxygen therapy | Sauerstofftherapie | Zuurstoftherapie | | from v2.1
B2 | Special equipment (tubes, IVs, catheters) | Besondere Hilfsmittel | Speciale middelen (slangen, infuzen, catethers) | | from v2.1
B3 | Amputee | Amputation | Amputatie | | from v2.1
B4 | Mastectomy | Brustamputation | Mastectomie | | from v2.1
B5 | Paraplegic | (Querschnitt-) Lähmung | Dwarslaesie | | from v2.1
B6 | Pregnant | Schwanger | Zwanger | | from v2.1

4.2.13.12 HL7 Version 2 Table 0012

URL: https://hl7.org/fhir/STU3/v2/0012/index.html

This page is part of the FHIR Specification (v3.0.2: STU 3). The current version which supercedes this version is 4.0.1. For a full list of available versions, see the Directory of published versions

Vocabulary Work Group | Maturity Level: N/A | External | Use Context: Any

This is a table defined as part of HL7 v2 . Related FHIR content: v2 STOCK LOCATION.

Summary

Name: | v2 STOCK LOCATION
Definition: | FHIR Value set/code system definition for HL7 v2 table 0012 (STOCK LOCATION)
Code System URL: | http://hl7.org/fhir/v2/0012
Value Set URL: | http://hl7.org/fhir/ValueSet/v2-0012
OID: | ??
CodeSystem Resource | XML / JSON
ValueSet Resource | XML / JSON

This value set is used in the following places:

* This value set is the designated 'entire code system' value set for v2 STOCK LOCATION

4.2.13.12.1 Code System Content

STOCK LOCATION

Code | Description | Deutsch (German) | Nederlands (Dutch) | Comment | Version
AN | Filled from ancillary department stock | (Tabelle 12 ist veraltet und wird nicht mehr verwendet) | Aangevuld uit verdere afdelingsvoorraad | deprecated | from v2.1, removed after v2.2
FL | Filled from floor stock | Etagenlager | Aangevuld uit verdiepingsvoorraad | deprecated | from v2.1, removed after v2.2

4.2.13.17 HL7 Version 2 Table 0017

URL: https://hl7.org/fhir/STU3/v2/0017/index.html

This page is part of the FHIR Specification (v3.0.2: STU 3). The current version which supercedes this version is 4.0.1. For a full list of available versions, see the Directory of published versions

Vocabulary Work Group | Maturity Level: N/A | External | Use Context: Any

This is a table defined as part of HL7 v2 . Related FHIR content: v2 Transaction Type.

Summary

Name: | v2 Transaction Type
Definition: | FHIR Value set/code system definition for HL7 v2 table 0017 (Transaction Type)
Code System URL: | http://hl7.org/fhir/v2/0017
Value Set URL: | http://hl7.org/fhir/ValueSet/v2-0017
OID: | ??
CodeSystem Resource | XML / JSON
ValueSet Resource | XML / JSON

This value set is used in the following places:

* This value set is the designated 'entire code system' value set for v2 Transaction Type

4.2.13.17.1 Code System Content

Transaction Type

Code | Description | Deutsch (German) | Nederlands (Dutch) | Comment | Version
AJ | Adjustment | nicht verwendet | Aanpassing | | added v2.3
CD | Credit | nicht verwendet | Krediet | | added v2.3
CG | Charge | nicht verwendet | Belast | | added v2.3
CO | Co-payment | nicht verwendet | Gedeelde betaling | | added v2.4
PY | Payment | nicht verwendet | Betaling | | added v2.3

4.2.13.23 HL7 Version 2 Table 0023

URL: https://hl7.org/fhir/STU3/v2/0023/index.html

This page is part of the FHIR Specification (v3.0.2: STU 3). The current version which supercedes this version is 4.0.1. For a full list of available versions, see the Directory of published versions

Vocabulary Work Group | Maturity Level: N/A | External | Use Context: Any

This is a table defined as part of HL7 v2 . Related FHIR content: v2 Admit Source.

Summary

Name: | v2 Admit Source
Definition: | FHIR Value set/code system definition for HL7 v2 table 0023 (Admit Source)
Code System URL: | http://hl7.org/fhir/v2/0023
Value Set URL: | http://hl7.org/fhir/ValueSet/v2-0023
OID: | ??
CodeSystem Resource | XML / JSON
ValueSet Resource | XML / JSON

This value set is used in the following places:

* This value set is the designated 'entire code system' value set for v2 Admit Source

4.2.13.23.1 Code System Content

Admit Source

Code | Description | Deutsch (German) | Nederlands (Dutch) | Comment | Version
... | No suggested values defined | | geen voorgestelde waarden | | added v2.7
1 | Physician referral | Überweisung durch Arzt | Verwijzing arts | deprecated | added v2.3.1, removed after v2.6
2 | Clinic referral | Überweisung durch Klinik | Kliniek verwijzing | deprecated | added v2.3.1, removed after v2.6
3 | HMO referral | nicht verwendet | HMO verwijzing | deprecated | added v2.3.1, removed after v2.6
4 | Transfer from a hospital | Verlegung aus Krankenhaus | Overplaatsing vanuit een ziekenhuis | deprecated | added v2.3.1, removed after v2.6
5 | Transfer from a skilled nursing facility | Verlegung aus Pflegeeinrichtung | Overplaatsing vanuit opgeleide verpleegkundige organisatie | deprecated | added v2.3.1, removed after v2.6
6 | Transfer from another health care facility | Verlegung aus sonstiger Gesundheitseinrichtung | Overplaatsing vanuit andere zorginstelling | deprecated | added v2.3.1, removed after v2.6
7 | Emergency room | Notfallambulanz | Spoedkamer | deprecated | added v2.3.1, removed after v2.6
8 | Court/law enforcement | Zwangseinweisung | Gerechterlijke/juridische dwang | deprecated | added v2.3.1, removed after v2.6
9 | Information not available | keine Information verfügbar | Informatie niet beschikbaar | deprecated | added v2.3.1, removed after v2.6

4.2.13.27 HL7 Version 2 Table 0027

URL: https://hl7.org/fhir/STU3/v2/0027/index.html

This page is part of the FHIR Specification (v3.0.2: STU 3). The current version which supercedes this version is 4.0.1. For a full list of available versions, see the Directory of published versions

Vocabulary Work Group | Maturity Level: N/A | External | Use Context: Any

This is a table defined as part of HL7 v2 . Related FHIR content: v2 Priority.

Summary

Name: | v2 Priority
Definition: | FHIR Value set/code system definition for HL7 v2 table 0027 (Priority)
Code System URL: | http://hl7.org/fhir/v2/0027
Value Set URL: | http://hl7.org/fhir/ValueSet/v2-0027
OID: | ??
CodeSystem Resource | XML / JSON
ValueSet Resource | XML / JSON

This value set is used in the following places:

* This value set is the designated 'entire code system' value set for v2 Priority

4.2.13.27.1 Code System Content

Priority

Code | Description | Deutsch (German) | Nederlands (Dutch) | Comment | Version
A | As soon as possible (a priority lower than stat) | schnellstmöglich | Zo snel mogelijk. (prioriteit lager dan stat) | | from v2.1
P | Preoperative (to be done prior to surgery) | präoperativ | Preoperatief (doen voorafgaand aan operatie) | | added v2.2
R | Routine | Routine | Routine | | added v2.2
S | Stat (do immediately) | sofort | Stat (onmiddellijk uitvoeren) | | from v2.1
T | Timing critical (do as near as possible to requested time) | zum vereinbarten Zeitpunkt | timing kritiek (uitvoering zo dicht mogelijk bij gevraagde tijd) | | from v2.1

4.2.13.33 HL7 Version 2 Table 0033

URL: https://hl7.org/fhir/STU3/v2/0033/index.html

This page is part of the FHIR Specification (v3.0.2: STU 3). The current version which supercedes this version is 4.0.1. For a full list of available versions, see the Directory of published versions

Vocabulary Work Group | Maturity Level: N/A | External | Use Context: Any

This is a table defined as part of HL7 v2 . Related FHIR content: v2 ROUTE.

Summary

Name: | v2 ROUTE
Definition: | FHIR Value set/code system definition for HL7 v2 table 0033 (ROUTE)
Code System URL: | http://hl7.org/fhir/v2/0033
Value Set URL: | http://hl7.org/fhir/ValueSet/v2-0033
OID: | ??
CodeSystem Resource | XML / JSON
ValueSet Resource | XML / JSON

This value set is used in the following places:

* This value set is the designated 'entire code system' value set for v2 ROUTE

4.2.13.33.1 Code System Content

ROUTE

Code | Description | Deutsch (German) | Nederlands (Dutch) | Comment | Version
AP | Apply externally | externe Applikatione | Uitwendig gebruiken | deprecated | from v2.1, removed after v2.1
CH | Chew | Kautablette | Kauwen | deprecated | from v2.1, removed after v2.1
DU | Dust | Puder | Stof | deprecated | from v2.1, removed after v2.1
EA | Ear | Ohr | Oor | deprecated | from v2.1, removed after v2.1
EY | Eye | Auge | Oog | deprecated | from v2.1, removed after v2.1
IA | Intro-arterial | intraarteriell | Intro-arteriaal | deprecated | from v2.1, removed after v2.1
ID | Intra-dermal | intradermal | Intra-dermaal | deprecated | from v2.1, removed after v2.1
IF | Infiltrate | infiltrieren | Infiltratie | deprecated | from v2.1, removed after v2.1
IH | Inhalation | Inhalation | Inhalatie | deprecated | from v2.1, removed after v2.1
IM | Intra-muscular | intramuskulär | Intra-musculair | deprecated | from v2.1, removed after v2.1
IN | Intra-nasal | intranasal | Intro-nasaal | deprecated | from v2.1, removed after v2.1
IR | Irrigate | Einlauf | Irrigatie | deprecated | from v2.1, removed after v2.1
IS | Inserted | Implantat | Ingebracht | deprecated | from v2.1, removed after v2.1
IT | Intrathecal | intrathekal | Intrathecaal | deprecated | from v2.1, removed after v2.1
IV | Intravenous | intravenös | Intraveneus | deprecated | from v2.1, removed after v2.1
NB | Nebulized | vernebelt | Verneveld | deprecated | from v2.1, removed after v2.1
NG | Nathogasic | nasogastral | | deprecated | from v2.1, removed after v2.1
PA | Peri-anally | peranal | Peri-anaal | deprecated | from v2.1, removed after v2.1
PT | Paint | aufpinseln | Verf | deprecated | from v2.1, removed after v2.1
PU | IV push | intravenöser Bolus | IV push | deprecated | from v2.1, removed after v2.1
RC | Rectally | rektal | Rectaal | deprecated | from v2.1, removed after v2.1
SH | Shampoo | Shampoo | Shampoo | deprecated | from v2.1, removed after v2.1
SL | Sublingual | subligual | Sublinguaal | deprecated | from v2.1, removed after v2.1
SO | Soak | drchtränken | Soppen | deprecated | from v2.1, removed after v2.1
SS | IV soluset | Iv-Lösung | IV soluset | deprecated | from v2.1, removed after v2.1
TP | Topically | topisch | Topicaal | deprecated | from v2.1, removed after v2.1
WA | Wash | waschen | Wassen | deprecated | from v2.1, removed after v2.1
WI | Wipe | wischen | Vegen | deprecated | from v2.1, removed after v2.1

4.2.13.34 HL7 Version 2 Table 0034

URL: https://hl7.org/fhir/STU3/v2/0034/index.html

This page is part of the FHIR Specification (v3.0.2: STU 3). The current version which supercedes this version is 4.0.1. For a full list of available versions, see the Directory of published versions

Vocabulary Work Group | Maturity Level: N/A | External | Use Context: Any

This is a table defined as part of HL7 v2 . Related FHIR content: v2 SITE ADMINISTERED.

Summary

Name: | v2 SITE ADMINISTERED
Definition: | FHIR Value set/code system definition for HL7 v2 table 0034 (SITE ADMINISTERED)
Code System URL: | http://hl7.org/fhir/v2/0034
Value Set URL: | http://hl7.org/fhir/ValueSet/v2-0034
OID: | ??
CodeSystem Resource | XML / JSON
ValueSet Resource | XML / JSON

This value set is used in the following places:

* This value set is the designated 'entire code system' value set for v2 SITE ADMINISTERED

4.2.13.34.1 Code System Content

SITE ADMINISTERED

Code | Description | Deutsch (German) | Nederlands (Dutch) | Comment | Version
B | Buttock | Gesäß | Bil | deprecated | from v2.1, removed after v2.1
L | Left arm | linker Arm | Linker arm | deprecated | from v2.1, removed after v2.1

4.2.13.38 HL7 Version 2 Table 0038

URL: https://hl7.org/fhir/STU3/v2/0038/index.html

This page is part of the FHIR Specification (v3.0.2: STU 3). The current version which supercedes this version is 4.0.1. For a full list of available versions, see the Directory of published versions

Vocabulary Work Group | Maturity Level: N/A | External | Use Context: Any

This is a table defined as part of HL7 v2 . Related FHIR content: v2 Order status.

Summary

Name: | v2 Order status
Definition: | FHIR Value set/code system definition for HL7 v2 table 0038 (Order status)
Code System URL: | http://hl7.org/fhir/v2/0038
Value Set URL: | http://hl7.org/fhir/ValueSet/v2-0038
OID: | ??
CodeSystem Resource | XML / JSON
ValueSet Resource | XML / JSON

This value set is used in the following places:

* This value set is the designated 'entire code system' value set for v2 Order status

4.2.13.38.1 Code System Content

Order status

Code | Description | Deutsch (German) | Nederlands (Dutch) | Comment | Version
A | Some, but not all, results available | einige, aber nicht alle, Resultate verfügbar | Sommige maar niet alle resultaten beschikbaar | | added v2.3
CA | Order was canceled | Auftrag storniert | Aanvraag is geannuleerd | | from v2.1
CM | Order is completed | Auftrag ausgeführt | Aanvraag is afgerond | | from v2.1
DC | Order was discontinued | Ausführung des Auftrags abgebrochen | Aanvraag is afgebroken | | from v2.1
ER | Error, order not found | Auftrag nicht gefunden | Fout, aanvraag niet gevonden | | from v2.1
HD | Order is on hold | Auftragsbearbeitung ausgesetzt | Aanvraag is aangehouden | | from v2.1
IP | In process, unspecified | Auftrag in Bearbeitung | Aanvraag loopt, niet-specificeerd | | from v2.1
RP | Order has been replaced | Auftrag ist ersetzt worden | Aanvraag is vervangen | | added v2.2
SC | In process, scheduled | Auftrag hat Termin oder ist in Ausführung | Aanvraag loopt, is gepland | | from v2.1

4.2.13.43 HL7 Version 2 Table 0043

URL: https://hl7.org/fhir/STU3/v2/0043/index.html

This page is part of the FHIR Specification (v3.0.2: STU 3). The current version which supercedes this version is 4.0.1. For a full list of available versions, see the Directory of published versions

Vocabulary Work Group | Maturity Level: N/A | External | Use Context: Any

This is a table defined as part of HL7 v2 . Related FHIR content: v2 Condition Code.

Summary

Name: | v2 Condition Code
Definition: | FHIR Value set/code system definition for HL7 v2 table 0043 (Condition Code)
Code System URL: | http://hl7.org/fhir/v2/0043
Value Set URL: | http://hl7.org/fhir/ValueSet/v2-0043
OID: | ??
CodeSystem Resource | XML / JSON
ValueSet Resource | XML / JSON

This value set is used in the following places:

* This value set is the designated 'entire code system' value set for v2 Condition Code

4.2.13.43.1 Code System Content

Condition Code

Code | Description | Deutsch (German) | Nederlands (Dutch) | Comment | Version

... | No suggested values defined | keine Werte vorgeschlagen | geen voorgestelde waarden | | added v2.5.1

01 | Military service related | | Militaire dienst gerelateerd | deprecated | added v2.3.1, removed after v2.4

02 | Condition is employment related | | Conditie is werkgerelateerd | deprecated | added v2.3.1, removed after v2.4

03 | Patient covered by insurance not reflected here | | Patiënt verzekerd door verzekering niet zichtbaar hier | deprecated | added v2.3.1, removed after v2.4

04 | HMO enrollee | | HMO gerechtigde | deprecated | added v2.3.1, removed after v2.4

05 | Lien has been filed | | Retentierecht is geregistreerd | deprecated | added v2.3.1, removed after v2.4

06 | ESRD patient in first 18 months of entitlement covered by employer group health insurance | | ESRD patiënt in eerste 18 maanden van toekenning gedekt door werkgever groepszorgpolis | deprecated | added v2.3.1, removed after v2.4

07 | Treatment of non-terminal condition for hospice patient | | Behandeling van niet-terminale aandoening voor hospice patiënt | deprecated | added v2.3.1, removed after v2.4

08 | Beneficiary would not provide information concerning other insurance coverage | | Begunstigde wilde geen informatie over andere verzekeringsdekking geven | deprecated | added v2.3.1, removed after v2.4

09 | Neither patient nor spouse is employed | | Zowel patiënt als echtgenoot heeft werk | deprecated | added v2.3.1, removed after v2.4

10 | Patient and/or spouse is employed but no EGHP exists | | Patiënt en/of echtgenoot heeft werk maar er is geen EGHP | deprecated | added v2.3.1, removed after v2.4

11 | Disabled beneficiary but no LGHP | | Gehandicapte begunstigde maar geen LGHP | deprecated | added v2.3.1, removed after v2.4

12 | Payer codes. | | Betaler codes. | deprecated | added v2.3.1, removed after v2.4

12 ... 16 | Payer codes. | | Betaler codes. | deprecated | added v2.3.1, removed after v2.4

13 | Payer codes. | | Betaler codes. | deprecated | added v2.3.1, removed after v2.4

14 | Payer codes. | | Betaler codes. | deprecated | added v2.3.1, removed after v2.4

15 | Payer codes. | | Betaler codes. | deprecated | added v2.3.1, removed after v2.4

16 | Payer codes. | | Betaler codes. | deprecated | added v2.3.1, removed after v2.4

18 | Maiden name retained | | Meisjesnaam behouden | deprecated | added v2.3.1, removed after v2.4

19 | Child retains mother's name | | Kind behoudt moeders' naam | deprecated | added v2.3.1, removed after v2.4

20 | Beneficiary requested billing | | Begunstige heeft facturatie gevraagd | deprecated | added v2.3.1, removed after v2.4

21 | Billing for Denial Notice | | Facturatie voor afgewezen melding | deprecated | added v2.3.1, removed after v2.4

26 | VA eligible patient chooses to receive services in a Medicare certified facility | | VA-gerechtigde patiënt wil services in een Medicare gecertificeerde instelling | deprecated | added v2.3.1, removed after v2.4

27 | Patient referred to a sole community hospital for a diagnostic laboratory test | | Patiënt verwezen naar één algemeen ziekenhuis voor diagnostische laboratoriumtest | deprecated | added v2.3.1, removed after v2.4

28 | Patient and/or spouse's EGHP is secondary to Medicare | | Patiënt en/of echtgenoot EGHP is aanvullend op Medicare | deprecated | added v2.3.1, removed after v2.4

29 | Disabled beneficiary and/or family member's LGHP is secondary to Medicare | | Gehandicapte begunstigde en/or familielid LGHP is aanvullend op Medicare | deprecated | added v2.3.1, removed after v2.4

31 | Patient is student (full time-day) | | Patiënt is student (voltijds dag) | deprecated | added v2.3.1, removed after v2.4

32 | Patient is student (cooperative/work study program) | | Patiënt is student (samenwerkend/werk studie programma) | deprecated | added v2.3.1, removed after v2.4

33 | Patient is student (full time-night) | | Patiënt is student (voltijds nacht) | deprecated | added v2.3.1, removed after v2.4

34 | Patient is student (Part time) | | Patiënt is student (parttime) | deprecated | added v2.3.1, removed after v2.4

36 | General care patient in a special unit | | Algemene zorg patiënt in speciale afdeling | deprecated | added v2.3.1, removed after v2.4

37 | Ward accommodation as patient request | | Afdelingsaccomodatie op patiëntverzoek | deprecated | added v2.3.1, removed after v2.4

38 | Semi-private room not available | | Semi-eigen kamer niet beschikbaar | deprecated | added v2.3.1, removed after v2.4

39 | Private room medically necessary | | Eigen kamer medisch noodzakelijk | deprecated | added v2.3.1, removed after v2.4

40 | Same day transfer | | Overplaatsing op zelfde dag | deprecated | added v2.3.1, removed after v2.4

41 | Partial hospitalization | | Gedeeltelijke opname | deprecated | added v2.3.1, removed after v2.4

46 | Non-availability statement on file | | Niet-beschikbaarheid uitspraak opgeslagen | deprecated | added v2.3.1, removed after v2.4

48 | Psychiatric residential treatment centers for children and adolescents | | Psychiatrisch behandelcentra voor kinderen en adolescents | deprecated | added v2.3.1, removed after v2.4

55 | SNF bed not available | | SNF bed niet beschikbaar | deprecated | added v2.3.1, removed after v2.4

56 | Medical appropriateness | | Medische relevantie | deprecated | added v2.3.1, removed after v2.4

57 | SNF readmission | | SNF heropname | deprecated | added v2.3.1, removed after v2.4

60 | Day outlier | | Dag afwijking | deprecated | added v2.3.1, removed after v2.4

61 | Cost outlier | | Kosten afwijking | deprecated | added v2.3.1, removed after v2.4

62 | Payer code | | Betaler code | deprecated | added v2.3.1, removed after v2.4

66 | Provider does not wish cost outlier payment | | Zorgaanbieder wil geen betaling van afwijkende kosten | deprecated | added v2.3.1, removed after v2.4

67 | Beneficiary elects not to use life time reserve (LTR) days | | Begunstigde kiest ervoor niet de levenslange reserve dagen (LTR) te gebruiken | deprecated | added v2.3.1, removed after v2.4

68 | Beneficiary elects to use life time reserve (LTR) days | | Begunstigde kiest ervoor de levenslange reserve dagen (LTR) te gebruiken | deprecated | added v2.3.1, removed after v2.4

70 | Self-administered EPO | | Zelf-toegediende EPO | deprecated | added v2.3.1, removed after v2.4

71 | Full care in unit | | Volledige zorg in eenheid | deprecated | added v2.3.1, removed after v2.4

72 | Self-care in unit | | Zelfzorg in eenheid | deprecated | added v2.3.1, removed after v2.4

73 | Self-care training | | Zelfzorg in training | deprecated | added v2.3.1, removed after v2.4

74 | Home | | Thuis | deprecated | added v2.3.1, removed after v2.4

75 | Home - 100% reimbursement | | Thuis - 100% vergoed | deprecated | added v2.3.1, removed after v2.4

76 | Back-up in facility dialysis | | Back-up in instelling dialyse | deprecated | added v2.3.1, removed after v2.4

77 | Provider accepts or is obligated/required due to a contractual arrangement or law to accept payment by a primary payer as payment in full | | Zorgaanbieder accepteert of is contractueel of juridisch verplicht om betaling te accepteren van een primaire betaler als volledige vertaling | deprecated | added v2.3.1, removed after v2.4

78 | New coverage not implemented by HMO | | Nieuwe dekking niet geïmplementeerd door HMO | deprecated | added v2.3.1, removed after v2.4

79 | Corf services provided off-site | | Corf services worden off-site gegeven | deprecated | added v2.3.1, removed after v2.4

80 | Pregnant | | Zwanger | deprecated | added v2.3.1, removed after v2.4

4.2.13.48 HL7 Version 2 Table 0048

URL: https://hl7.org/fhir/STU3/v2/0048/index.html

This page is part of the FHIR Specification (v3.0.2: STU 3). The current version which supercedes this version is 4.0.1. For a full list of available versions, see the Directory of published versions

Vocabulary Work Group | Maturity Level: N/A | External | Use Context: Any

This is a table defined as part of HL7 v2 . Related FHIR content: v2 What subject filter.

Summary

Name: | v2 What subject filter

Definition: | FHIR Value set/code system definition for HL7 v2 table 0048 (What subject filter)

Code System URL: | http://hl7.org/fhir/v2/0048

Value Set URL: | http://hl7.org/fhir/ValueSet/v2-0048

OID: | ??

CodeSystem Resource | XML / JSON

ValueSet Resource | XML / JSON

This value set is used in the following places:

* This value set is the designated 'entire code system' value set for v2 What subject filter

4.2.13.48.1 Code System Content

What subject filter

Code | Description | Deutsch (German) | Nederlands (Dutch) | Comment | Version

ADV | Advice/diagnosis | Ratschlag / Diagnose | Advies/diagnose | deprecated | from v2.1, removed after v2.6

ANU | Nursing unit lookup (returns patients in beds, excluding empty beds) | Stationsinformation (ohne freie Betten) | Verpleegafdeling opzoeken (levert patiënten in bedden, zonder lege bedden) | deprecated | from v2.1, removed after v2.6

APA | Account number query, return matching visit | Fälle zu angefragter Rechnungsnummer | Accountnummer query, levert bijbehorende bezoeken | deprecated | added v2.2, removed after v2.6

APM | Medical record number query, returns visits for a medical record number | Fälle zu angefragter Krankenaktennummer | Medisch dossiernummer query, levert bezoeken op basis van een medisch dossiernummer | deprecated | added v2.2, removed after v2.6

APN | Patient name lookup | Patientendaten zu gegebenem Patientennamen | Patiëntnaam opzoeken | deprecated | from v2.1, removed after v2.6

APP | Physician lookup | Patienten des spezifizierten Arztes | Arts opzoeken | deprecated | added v2.2, removed after v2.6

ARN | Nursing unit lookup (returns patients in beds, including empty beds) | Stationsinformation (einschließlich freier Betten) | Verpleegafdeling opzoeken (levert patiënten in bedden, inclusief lege bedden) | deprecated | added v2.2, removed after v2.6

CAN | Cancel. Used to cancel a query | Anfrage stornieren | Annuleren (gebruikt voor annuleren van een query) | deprecated | from v2.1, removed after v2.6

DEM | Demographics | Demographische Daten | Demografie | deprecated | from v2.1, removed after v2.6

FIN | Financial | Finanzdaten | Financieel | deprecated | added v2.2, removed after v2.6

GID | Generate new identifier | | Genereer nieuwe identificatie | deprecated | added v2.4, removed after v2.6

GOL | Goals | Ziele | Goals | deprecated | added v2.3, removed after v2.6

MFQ | Master file query | Stammdaten | Master file query | deprecated | added v2.2, removed after v2.2

MRI | Most recent inpatient | Letzter stationärer Patient | Meest recente klinische patiënt | deprecated | from v2.1, removed after v2.6

MRO | Most recent outpatient | Letzter ambulanter Patient | Meest recente poliklinische patiënt | deprecated | from v2.1, removed after v2.6

NCK | Network clock | Netzwerk-Uhrzeit | Netwerkklok | deprecated | added v2.2, removed after v2.6

NSC | Network status change | Änderung des Netzwerkstatus | Netwerk statuswijziging | deprecated | added v2.2, removed after v2.6

NST | Network statistic | Netzwerkstatistik | Netwerkstatistiek | deprecated | added v2.2, removed after v2.6

ORD | Order | Auftrag / Verordnung | Aanvraag | deprecated | added v2.2, removed after v2.6

OTH | Other | anderes | Anders | deprecated | from v2.1, removed after v2.6

PRB | Problems | Probleme | Problemen | deprecated | added v2.3, removed after v2.6

PRO | Procedure | Prozedur | Procedure | deprecated | from v2.1, removed after v2.6

RAR | Pharmacy administration information | Erfolgte Verabreichung von Medikamenten | Medicatietoediening informatie | deprecated | added v2.2, removed after v2.6

RDR | Pharmacy dispense information | Abgabe von Medikamenten | Medicatieverstrekking informatie | deprecated | added v2.2, removed after v2.6

RER | Pharmacy encoded order information | Medikamentenverordnung (Apotheke) | Medicatie gecodeerde aanvraag informatie | deprecated | added v2.2, removed after v2.6

RES | Result | Ergebnis / Befund | Resultaat | deprecated | from v2.1, removed after v2.6

RGR | Pharmacy give information | Verabreichunsgsvorschrift für Medikamente | Medicatie gegeven informatie | deprecated | added v2.2, removed after v2.6

ROR | Pharmacy prescription information | Medikamentenverordnung | Medicatievoorschrift informatie | deprecated | added v2.2, removed after v2.6

SAL | All schedule related information, including open slots, booked slots, blocked slots | | Alle agenda gerelateerde informatie, inclusief open afspraakposities, geboekte afspraakposities, geblokkeerde afspraakposities | deprecated | added v2.3.1, removed after v2.6

SBK | Booked slots on the identified schedule | | Geboekte afspraakposities op de geïdentificeerde agenda | deprecated | added v2.3.1, removed after v2.6

SBL | Blocked slots on the identified schedule | | Geblokkeerde afspraakposities op de geïdentificeerde agenda | deprecated | added v2.3.1, removed after v2.6

SOF | First open slot on the identified schedule after the start date/tiem | | Eerste open afspraakpositie op de geïdentificeerde agenda na de startdatum/tijd | deprecated | added v2.4, removed after v2.6
SOP | Open slots on the identified schedule between the begin and end of the start date/time range | | Eerste open afspraakpositie op de geïdentificeerde agenda in de startdatum/tijd periode | deprecated | added v2.3.1, removed after v2.6
SSA | Time slots available for a single appointment | | Beschikbare afspraakposities voor één enkele afspraak | deprecated | added v2.3.1, removed after v2.6
SSR | Time slots available for a recurring appointment | | Beschikbare afspraakposities voor een herhalende afspraak | deprecated | added v2.3.1, removed after v2.6
STA | Status | Status | Status | deprecated | from v2.1, removed after v2.6
VXI | Vaccine Information | Impfinformation | Vaccinatie informatie | deprecated | added v2.3, removed after v2.6
XID | Get cross-referenced identifiers | | Ophalen gekoppelde identificaties | deprecated | added v2.4, removed after v2.6

4.2.13.52 HL7 Version 2 Table 0052

URL: https://hl7.org/fhir/STU3/v2/0052/index.html

This page is part of the FHIR Specification (v3.0.2: STU 3). The current version which supercedes this version is 4.0.1. For a full list of available versions, see the Directory of published versions

Vocabulary Work Group | Maturity Level: N/A | External | Use Context: Any

This is a table defined as part of HL7 v2 . Related FHIR content: v2 Diagnosis Type.

Summary

Name: | v2 Diagnosis Type
Definition: | FHIR Value set/code system definition for HL7 v2 table 0052 (Diagnosis Type)
Code System URL: | http://hl7.org/fhir/v2/0052
Value Set URL: | http://hl7.org/fhir/ValueSet/v2-0052
OID: | ??
CodeSystem Resource | XML / JSON
ValueSet Resource | XML / JSON

This value set is used in the following places:

* This value set is the designated 'entire code system' value set for v2 Diagnosis Type

4.2.13.52.1 Code System Content

Diagnosis Type

Code | Description | Deutsch (German) | Nederlands (Dutch) | Comment | Version
A | Admitting | Aufnahme | Opname | | added v2.3
F | Final | Enddiagnose | Definitief | | added v2.3
W | Working | | Werk | | added v2.3

4.2.13.61 HL7 Version 2 Table 0061

URL: https://hl7.org/fhir/STU3/v2/0061/index.html

This page is part of the FHIR Specification (v3.0.2: STU 3). The current version which supercedes this version is 4.0.1. For a full list of available versions, see the Directory of published versions

Vocabulary Work Group | Maturity Level: N/A | External | Use Context: Any

This is a table defined as part of HL7 v2 . Related FHIR content: v2 Check Digit Scheme.

Summary

Name: | v2 Check Digit Scheme
Definition: | FHIR Value set/code system definition for HL7 v2 table 0061 (Check Digit Scheme)
Code System URL: | http://hl7.org/fhir/v2/0061
Value Set URL: | http://hl7.org/fhir/ValueSet/v2-0061
OID: | ??
CodeSystem Resource | XML / JSON
ValueSet Resource | XML / JSON

This value set is used in the following places:

* This value set is the designated 'entire code system' value set for v2 Check Digit Scheme

4.2.13.61.1 Code System Content

Check Digit Scheme

Code | Description | Deutsch (German) | Nederlands (Dutch) | Comment | Version
BCV | Bank Card Validation Number | | Bancaire kaart validatienummer | A non-embossed number included on bank cards and used to validate authenticity of the card and the person presenting the card | added v2.6
ISO | ISO 7064: 1983 | | ISO 7064: 1983 | | added v2.3.1
M10 | Mod 10 algorithm | Modulo10-Verfahren | Mod 10 algoritme | | added v2.2
M11 | Mod 11 algorithm | Modulo11-Verfahren | Mod 11 algoritme | | from v2.1
NPI | Check digit algorithm in the US National Provider Identifier | | Controlegetal algoritme van de Amerikaanse Nationale Provider identificatie | | added v2.3.1

4.2.13.62 HL7 Version 2 Table 0062

URL: https://hl7.org/fhir/STU3/v2/0062/index.html

This page is part of the FHIR Specification (v3.0.2: STU 3). The current version which supercedes this version is 4.0.1. For a full list of available versions, see the Directory of published versions

Vocabulary Work Group | Maturity Level: N/A | External | Use Context: Any

This is a table defined as part of HL7 v2 . Related FHIR content: v2 Event Reason.

Summary

Name: | v2 Event Reason
Definition: | FHIR Value set/code system definition for HL7 v2 table 0062 (Event Reason)
Code System URL: | http://hl7.org/fhir/v2/0062
Value Set URL: | http://hl7.org/fhir/ValueSet/v2-0062
OID: | ??
CodeSystem Resource | XML / JSON
ValueSet Resource | XML / JSON

This value set is used in the following places:

* This value set is the designated 'entire code system' value set for v2 Event Reason

4.2.13.62.1 Code System Content

Event Reason

Code | Description | Deutsch (German) | Nederlands (Dutch) | Comment | Version
01 | Patient request | Veranlassung durch Patient | Op verzoek patiënt | | from v2.1
02 | Physician/health practitioner order | Veranlassung durch den Arzt | Op aanvraag arts/zorgverlener | | from v2.1
03 | Census management | Veranlassung durch Patientenverwaltung | Gezamenlijk besluit | | added v2.2
O | Other | andere Veranlassung | Anders | | added v2.5
U | Unknown | Veranlassung unbekannt | Onbekend | | added v2.5

4.2.13.63 HL7 Version 2 Table 0063

URL: https://hl7.org/fhir/STU3/v2/0063/index.html

This page is part of the FHIR Specification (v3.0.2: STU 3). The current version which supercedes this version is 4.0.1. For a full list of available versions, see the Directory of published versions

Vocabulary Work Group | Maturity Level: N/A | External | Use Context: Any

This is a table defined as part of HL7 v2 . Related FHIR content: v2 Relationship.

Summary

Name: | v2 Relationship
Definition: | FHIR Value set/code system definition for HL7 v2 table 0063 (Relationship)
Code System URL: | http://hl7.org/fhir/v2/0063
Value Set URL: | http://hl7.org/fhir/ValueSet/v2-0063
OID: | ??
CodeSystem Resource | XML / JSON
ValueSet Resource | XML / JSON

This value set is used in the following places:

* This value set is the designated 'entire code system' value set for v2 Relationship

4.2.13.63.1 Code System Content

Relationship

Code | Description | Deutsch (German) | Nederlands (Dutch) | Comment | Version
ASC | Associate | Collègue | Zakenpartner | | added v2.4
BRO | Brother | Bruder | Broer | | added v2.4
CGV | Care giver | Pflegeeltern | Zorgverlener | | added v2.4
CHD | Child | Kind | Kind | | added v2.4
DEP | Handicapped dependent | Begleitperson für Hilfsbedürftige | Gehandicapt afhankelijke | | added v2.4
DOM | Life partner | Lebenspartner | Levenspartner | | added v2.4
EMC | Emergency contact | Ansprechpartner in Notfällen | Noodgeval contact | | added v2.4
EME | Employee | Angestellter | Werknemer | | added v2.4
EMR | Employer | Arbeitgeber | Eployer | | added v2.4
EXF | Extended family | erweiterter Familienkreis | Verre familie | | added v2.4
FCH | Foster child | Pflegekind | Pleegkind | | added v2.4
FND | Friend | Freund | Friend | | added v2.4
FTH | Father | Vater | Vader | | added v2.4
GCH | Grandchild | Enkel | Kleinkind | | added v2.4
GRD | Guardian | Pate | Voogd | | added v2.4
GRP | Grandparent | Großeltern | Grootouder | | added v2.4
MGR | Manager | Manager | Manager | | added v2.4

MTH | Mother | Mutter | Moeder | | added v2.4
NCH | Natural child | eigenes Kind | Biologisch kind | | added v2.4
NON | None | keine | Geen | | added v2.4
OAD | Other adult | anderer Erwachsener | Andere volwassene | | added v2.4
OTH | Other | andere | Anders | | added v2.4
OWN | Owner | Eigentümer | Eigenaar | | added v2.4
PAR | Parent | Eltern | Ouder | | added v2.4
SCH | Stepchild | Stiefkind | Stiefkind | | added v2.4
SEL | Self | selbst | Zelf | | added v2.4
SIB | Sibling | Geschwister | Broer/zus | | added v2.4
SIS | Sister | Schwester | Zus | | added v2.4
SPO | Spouse | Partner | Huwelijkse partner | | added v2.4
TRA | Trainer | Trainer | Trainer | | added v2.4
UNK | Unknown | unbekannt | Onbekend | | added v2.4
WRD | Ward of court | Vormund | Wettelijke voogd | | added v2.4

4.2.13.65 HL7 Version 2 Table 0065

URL: https://hl7.org/fhir/STU3/v2/0065/index.html

This page is part of the FHIR Specification (v3.0.2: STU 3). The current version which supercedes this version is 4.0.1. For a full list of available versions, see the Directory of published versions

Vocabulary Work Group | Maturity Level: N/A | External | Use Context: Any

This is a table defined as part of HL7 v2 . Related FHIR content: v2 Specimen Action Code.

Summary

Name: | v2 Specimen Action Code
Definition: | FHIR Value set/code system definition for HL7 v2 table 0065 (Specimen Action Code)
Code System URL: | http://hl7.org/fhir/v2/0065
Value Set URL: | http://hl7.org/fhir/ValueSet/v2-0065
OID: | ??
CodeSystem Resource | XML / JSON
ValueSet Resource | XML / JSON

This value set is used in the following places:

* This value set is the designated 'entire code system' value set for v2 Specimen Action Code

4.2.13.65.1 Code System Content

Specimen Action Code

Code | Description | Deutsch (German) | Nederlands (Dutch) | Comment | Version
A | Add ordered tests to the existing specimen | Zusätzliche Tests zur vorhandenen Probe | Voeg gevraagde tests toe aan bestaande monster | | from v2.1
C | Cancel order for battery or tests named | Stornoauftrag zu bekannter Probe | Annuleer aanvraag voor genoemde battery of tests | deprecated | from v2.1, removed after v2.1
G | Generated order; reflex order | Nachgeordneter Auftrag / Auftrag als Reaktion auf Untersuchungsergebnis | Gegenereerde aanvraag / reflexaanvraag | | from v2.1
L | Lab to obtain specimen from patient | Holauftrag für Labor | Lab verzamelt monster van patiënt | | from v2.1
O | Specimen obtained by service other than Lab | Probe wird / wurde mit dem Auftrag zur Verfügung gestellt | Monster wordt afgenomen door een service anders dan het Lab | | from v2.1
P | Pending specimen; Order sent prior to delivery | Probe steht noch aus - Auftrag liegt schon vor | Wachtend op monster - Aanvraag gestuurd voorafgaand aan levering | | from v2.1
R | Revised order | Geänderter Auftrag | Herziene aanvraag | | added v2.2
S | Schedule the tests specified below | Spezifizierte Untersuchungen einplanen | Plan de tests zoals hieronder gespecificeerd | | from v2.1

4.2.13.66 HL7 Version 2 Table 0066

URL: https://hl7.org/fhir/STU3/v2/0066/index.html

This page is part of the FHIR Specification (v3.0.2: STU 3). The current version which supercedes this version is 4.0.1. For a full list of available versions, see the Directory of published versions

Vocabulary Work Group | Maturity Level: N/A | External | Use Context: Any

This is a table defined as part of HL7 v2 . Related FHIR content: v2 Employment Status.

Summary

Name: | v2 Employment Status
Definition: | FHIR Value set/code system definition for HL7 v2 table 0066 (Employment Status)
Code System URL: | http://hl7.org/fhir/v2/0066
Value Set URL: | http://hl7.org/fhir/ValueSet/v2-0066
OID: | ??
CodeSystem Resource | XML / JSON
ValueSet Resource | XML / JSON

This value set is used in the following places:

* This value set is the designated 'entire code system' value set for v2 Employment Status

4.2.13.66.1 Code System Content

Employment Status

Code | Description | Deutsch (German) | Nederlands (Dutch) | Comment | Version
... | see chapter 6 | | zie hoofdstuk 6 | deprecated | added v2.6, removed after v2.6
1 | Full time employed | | Voltijd baan | | added v2.4
2 | Part time employed | | Parttime baan | | added v2.4
3 | Unemployed | | Werkloos | | added v2.4
4 | Self-employed, | | Zelfstandige | | added v2.4
5 | Retired | | Gepensioneerd | | added v2.4
6 | On active military duty | | In actieve militaire dienst | | added v2.4
9 | Unknown | unbekannt | Onbekend | | added v2.4
C | Contract, per diem | | Contract, per diem | | added v2.4
D | Per Diem | | Per diem | deprecated | added v2.4, removed after v2.4
F | Full Time | | Voltijd | deprecated | added v2.4, removed after v2.4
L | Leave of absence (e.g. family leave, sabbatical, etc.) | | Verlof (bijv. familieomstandigheden, sabbatical, etc.) | | added v2.4
O | Other | | Anders | | added v2.4
P | Part Time | | Parttime | deprecated | added v2.4, removed after v2.4
T | Temporarily unemployed | | Tijdelijk werkloos | | added v2.4

4.2.13.69 HL7 Version 2 Table 0069

URL: https://hl7.org/fhir/STU3/v2/0069/index.html

This page is part of the FHIR Specification (v3.0.2: STU 3). The current version which supercedes this version is 4.0.1. For a full list of available versions, see the Directory of published versions

Vocabulary Work Group | Maturity Level: N/A | External | Use Context: Any

This is a table defined as part of HL7 v2 . Related FHIR content: v2 Hospital Service.

Summary

Name: | v2 Hospital Service
Definition: | FHIR Value set/code system definition for HL7 v2 table 0069 (Hospital Service)
Code System URL: | http://hl7.org/fhir/v2/0069
Value Set URL: | http://hl7.org/fhir/ValueSet/v2-0069
OID: | ??
CodeSystem Resource | XML / JSON
ValueSet Resource | XML / JSON

This value set is used in the following places:

* This value set is the designated 'entire code system' value set for v2 Hospital Service

4.2.13.69.1 Code System Content

Hospital Service

Code | Description | Nederlands (Dutch) | Comment | Version
CAR | Cardiac Service | Hart behandeling | | added v2.4
MED | Medical Service | Medisch behandeling | | added v2.4
PUL | Pulmonary Service | Pulmonaire behandeling | | added v2.4
SUR | Surgical Service | Chirurgische behandeling | | added v2.4
URO | Urology Service | Uologische behandeling | | added v2.4

4.2.13.70 HL7 Version 2 Table 0070

URL: https://hl7.org/fhir/STU3/v2/0070/index.html

This page is part of the FHIR Specification (v3.0.2: STU 3). The current version which supercedes this version is 4.0.1. For a full list of available versions, see the Directory of published versions

Vocabulary Work Group | Maturity Level: N/A | External | Use Context: Any

This is a table defined as part of HL7 v2 . Related FHIR content: v2 Specimen Source Codes.

Summary

Name: | v2 Specimen Source Codes
Definition: | FHIR Value set/code system definition for HL7 v2 table 0070 (Specimen Source Codes)
Code System URL: | http://hl7.org/fhir/v2/0070
Value Set URL: | http://hl7.org/fhir/ValueSet/v2-0070
OID: | ??
CodeSystem Resource | XML / JSON
ValueSet Resource | XML / JSON

This value set is used in the following places:

* This value set is the designated 'entire code system' value set for v2 Specimen Source Codes

4.2.13.70.1 Code System Content

Specimen Source Codes

Code | Description | Deutsch (German) | Nederlands (Dutch) | Comment | Version
ABLD | Arterial blood | Arterielles Blut | Arterieel bloed | deprecated | added v2.2, removed after v2.2
ABS | Abscess | Abszeß | Abces | deprecated | added v2.2, removed after v2.6
AMN | Amniotic fluid | Fruchtwasser | Amniotisch vocht | deprecated | added v2.2, removed after v2.6
ASP | Aspirate | Aspirationssubstrat | Aspiraat | deprecated | added v2.2, removed after v2.6
BBL | Blood bag | Blutkonserve | Bloedzak | deprecated | added v2.2, removed after v2.6
BDY | Whole body | Gesamter Körper | Geheel lichaam | deprecated | added v2.2, removed after v2.6
BIFL | Bile fluid | | Galvocht | deprecated | added v2.3, removed after v2.6
BLD | Whole blood | Gesamtes Blut | Geheel bloed | deprecated | from v2.1, removed after v2.6
BLDA | Blood arterial | | Arterieel bloed | deprecated | added v2.3, removed after v2.6
BLDC | Blood capillary | | Capillair bloed | deprecated | added v2.3, removed after v2.6
BLDCO | Cord blood | | Streng bloed | deprecated | added v2.4, removed after v2.6
BLDV | Blood venous | | Veneus bloed | deprecated | added v2.3, removed after v2.6
BON | Bone | Knochen | Bot | deprecated | from v2.1, removed after v2.6
BPH | Basophils | Basophile | Basofiel | deprecated | added v2.2, removed after v2.6
BPU | Blood product unit | | Bloedproduct eenheid | deprecated | added v2.3, removed after v2.6
BRN | Burn | Brandwunde | Brandwond | deprecated | from v2.1, removed after v2.6
BRO | Bronchial | Bronchialwege | Bronchiaal | deprecated | added v2.2, removed after v2.6
BRTH | Breath (use EXHLD) | Atemluft | Adem (gebruik EXHLD) | deprecated | added v2.2, removed after v2.6
CALC | Calculus (=Stone) | Steinchen, Konkrement | Calculus (=Steen) | deprecated | added v2.2, removed after v2.6
CBLD | Cord blood | Nabelschnurblut | Streng bloed | deprecated | added v2.2, removed after v2.4
CDM | Cardiac muscle | Herzmuskel | Hartspier | deprecated | added v2.2, removed after v2.6
CNJT | Conjunctiva | Konjunktiven | Conjunctiva | deprecated | from v2.1, removed after v2.6
CNL | Cannula | Kanüle | Cannula | deprecated | added v2.2, removed after v2.6
COL | Colostrum | Kolostrum, Vormilch | Colostrum | deprecated | added v2.2, removed after v2.6
CSF | Cerebral spinal fluid | Cerebralflüssigkeit | Hersenvocht | deprecated | from v2.1, removed after v2.6
CTP | Catheter tip | Katheterspitze | Catether tip | deprecated | added v2.2, removed after v2.6
CUR | Curettage | Curettagematerial | Curettage | deprecated | added v2.2, removed after v2.6
CVM | Cervical mucus | Cervicalschleim | Cervicale mucus | deprecated | added v2.2, removed after v2.6
CVX | Cervix | Zervix | Cervix | deprecated | from v2.1, removed after v2.6
CYST | Cyst | Zyste | Cyste | deprecated | added v2.2, removed after v2.6
DIAF | Dialysis fluid | | Dialyse vocht | deprecated | added v2.3, removed after v2.6
DOSE | Dose med or substance | | Medicatie of substantie | deprecated | added v2.3, removed after v2.6
DRN | Drain | Drainage | Stoma | deprecated | added v2.2, removed after v2.6
DUFL | Duodenal fluid | | Duodenaal vocht | deprecated | added v2.3, removed after v2.6
EAR | Ear | Ohr | Oor | deprecated | from v2.1, removed after v2.6
EARW | Ear wax (cerumen) | | Oorsmeer (cerumen) | deprecated | added v2.3, removed after v2.6
ELT | Electrode | Elektrode | Electrode | deprecated | added v2.2, removed after v2.6
ENDC | Endocardium | Endocard | Endocardium | deprecated | added v2.2, removed after v2.6
ENDM | Endometrium | Endometrium | Endometrium | deprecated | added v2.2, removed after v2.6
EOS | Eosinophils | Eosinophile | Eosinofiel | deprecated | added v2.2, removed after v2.6
EXG | Exhaled gas (=breath) | | Uitgeademde lucht (=adem) | deprecated | added v2.4, removed after v2.6
EXHLD | Exhaled gas (=breath) | | Uitgeademde lucht (=adem) | deprecated | added v2.3, removed after v2.4
EYE | Eye | | Oog | deprecated | added v2.3, removed after v2.6
FIB | Fibroblasts | Fibroblasten | Fibroblasts | deprecated | from v2.1, removed after v2.6
FIST | Fistula | Fistel | Fistel | deprecated | added v2.2, removed after v2.6
FLT | Filter | Filter | Filter | deprecated | added v2.2, removed after v2.6
FLU | Body fluid, unsp | Körperflüssigkeit (unspezifiziert) | Lichaamsvocht, niet-gesp | deprecated | added v2.2, removed after v2.6
GAS | Gas | | Lucht | deprecated | added v2.3, removed after v2.6
GAST | Gastric fluid/contents | Magenflüssigkeit | Maagvocht/inhoud | deprecated | added v2.2, removed after v2.6
GEN | Genital | Genitale | Genitaal | deprecated | added v2.2, removed after v2.6
GENC | Genital cervix | Genitale - Cervix | Genitaal cervix | deprecated | added v2.2, removed after v2.6
GENL | Genital lochia | Wochenfluß / Lochien | Genitaal lochia | deprecated | added v2.2, removed after v2.6
GENV | Genital vaginal | Genitale - Vagina | Genitaal vaginaal | deprecated | added v2.2, removed after v2.6
HAR | Hair | Haare | Haar | deprecated | from v2.1, removed after v2.6
IHG | Inhaled Gas | | Geïnhaleerde lucht | deprecated | added v2.3, removed after v2.6
ISLT | Isolate | | Isolaat | deprecated | added v2.3, removed after v2.6
IT | Intubation tube | Tubus | Intubatieslang | deprecated | added v2.2, removed after v2.6
LAM | Lamella | Lamellen | Lamella | deprecated | added v2.2, removed after v2.6
LIQ | Liquid NOS | | Vloeistof, niet anders gespecificeerd | deprecated | added v2.3, removed after v2.6
LN | Line | Zugang | Lijn | deprecated | added v2.2, removed after v2.6
LNA | Line arterial | Arterieller Zugang | Arteriële lijn | deprecated | added v2.2, removed after v2.6
LNV | Line venous | Venöser Zugang | Veneuze lijn | deprecated | added v2.2, removed after v2.6
LYM | Lymphocytes | Lymphozyten | Lymfocyten | deprecated | added v2.2, removed after v2.6
MAC | Macrophages | Makrophagen | Macrofagen | deprecated | added v2.2, removed after v2.6
MAR | Marrow | Knochenmark | Merg | deprecated | added v2.2, removed after v2.6
MBLD | Menstrual blood | Menstruationsblut | Menstruatiebloed | deprecated | added v2.2, removed after v2.6
MEC | Meconium | Meconium | Meconium | deprecated | added v2.2, removed after v2.6
MILK | Breast milk | Brustmilch | Borstmelk | deprecated | added v2.2, removed after v2.6

MLK | Milk | Milch | Melk | deprecated | added v2.2, removed after v2.6
MN | Amniotic Fluid | Fruchtwasser | Amniotisch vocht | deprecated | from v2.1, removed after v2.1
NAIL | Nail | Nagel | Nagel | deprecated | added v2.2, removed after v2.6
NOS | Nose (nasal passage) | Nase (Nasenwege) | Neus (nasale doorgang) | deprecated | from v2.1, removed after v2.6
ORH | Other | Andere | Anders | deprecated | added v2.2, removed after v2.6
OTH | Other | Diverse | Anders | deprecated | from v2.1, removed after v2.1
PAFL | Pancreatic fluid | | Pancreas vocht | deprecated | added v2.3, removed after v2.6
PAT | Patient | | Patiënt | deprecated | added v2.3, removed after v2.6
PER | Peritoneum | Peritoneum | Peritoneum | deprecated | added v2.2, removed after v2.2
PLAS | Plasma | Plasma | Plasma | deprecated | from v2.1, removed after v2.6
PLB | Plasma bag | Plasmabeutel | Plasmazak | deprecated | added v2.2, removed after v2.6
PLC | Placenta | Placenta | Placenta | deprecated | added v2.2, removed after v2.6
PLR | Pleural fluid (thoracentesis fld) | Pleuraflüssigkeit (nach Thoracocentese) | Pleuraal vocht (thoracentesis vocht) | deprecated | added v2.2, removed after v2.6
PMN | Polymorphonuclear neutrophils | Polymorphkernige Neutrophile | Polymorfonucleaire neutrofielen | deprecated | added v2.2, removed after v2.6
PPP | Platelet poor plasma | | Patelet-arm plasma | deprecated | added v2.3, removed after v2.6
PRP | Platelet rich plasma | | Patelet-rijk plasma | deprecated | added v2.3, removed after v2.6
PRT | Peritoneal fluid /ascites | Peritonealflüssigkeit / Ascites | Peritoneaal vocht / ascites | deprecated | from v2.1, removed after v2.6
PUS | Pus | Eiter | Pus | deprecated | added v2.2, removed after v2.6
RBC | Erythrocytes | Erythrozyten | Erythrocyten | deprecated | from v2.1, removed after v2.6
RT | Route of medicine | | Route van zorg | deprecated | added v2.3, removed after v2.6
SAL | Saliva | Speichel | Speeksel | deprecated | from v2.1, removed after v2.6
SEM | Seminal fluid | Sperma | Seminaal vocht | deprecated | from v2.1, removed after v2.4
SER | Serum | Serum | Serum | deprecated | from v2.1, removed after v2.6
SKM | Skeletal muscle | Skelettmuskel | Skeletspier | deprecated | added v2.2, removed after v2.6
SKN | Skin | Haut | Huid | deprecated | from v2.1, removed after v2.6
SMN | Seminal fluid | | Seminaal vocht | deprecated | added v2.4, removed after v2.6
SNV | Synovial fluid (Joint fluid) | Synovialflüssigkeit | Synoviaal vocht (gewrichtvocht) | deprecated | from v2.1, removed after v2.6
SPRM | Spermatozoa | Spermien | Spermatozoïden | deprecated | added v2.2, removed after v2.6
SPT | Sputum | Sputum | Sputum | deprecated | added v2.2, removed after v2.6
SPTC | Sputum - coughed | Sputum - Hustenauswurf | Sputum - gehoest | deprecated | added v2.2, removed after v2.6
SPTT | Sputum - tracheal aspirate | Sputum - tracheal aspiriert | Sputum - tracheaal aspiraat | deprecated | added v2.2, removed after v2.6
STL | Stool = Fecal | Stuhl | Ontlasting = Feces | deprecated | from v2.1, removed after v2.6
STON | Stone (use CALC) | Steine | Steen (gebruik CALC) | deprecated | added v2.2, removed after v2.6
SWT | Sweat | Schweiß | Zweet | deprecated | from v2.1, removed after v2.6
TEAR | Tears | Tränen | Tranen | deprecated | added v2.2, removed after v2.6
THRB | Thrombocyte (platelet) | Thrombozyten | Trombocyt (platelet) | deprecated | added v2.2, removed after v2.6
THRT | Throat | Rachanbstrich | Keel | deprecated | from v2.1, removed after v2.6
TIS | Tissue | Gewebe | Weefsel | deprecated | from v2.1, removed after v2.1
TISB | Tissue bone marrow | Knochenmarksgewebe | Weefsel beenmerg | deprecated | added v2.2, removed after v2.2
TISC | Tissue curettage | Kürettagegewebe | Weefsel curettage | deprecated | added v2.2, removed after v2.2
TISG | Tissue gall bladder | Gallenblasengewebe | Weefsel galblaas | deprecated | added v2.2, removed after v2.6
TISL | Tissue lung | Lungengewebe | Weefsel long | deprecated | added v2.2, removed after v2.2
TISP | Tissue peritoneum | Peritonealgewebe | Weefsel peritoneum | deprecated | added v2.2, removed after v2.2
TISPL | Tissue placenta | Placentagewebe | Weefsel placenta | deprecated | added v2.2, removed after v2.6
TISS | Tissue | Gewebe | Weefsel | deprecated | added v2.2, removed after v2.6
TISU | Tissue ulcer | Ulcusgewebe | Weefsel maagzweer | deprecated | added v2.2, removed after v2.6
TLGI | Tissue large intestine | | Weefsel groot intestinaal | deprecated | added v2.3, removed after v2.6
TLNG | Tissue lung | | Weefsel long | deprecated | added v2.3, removed after v2.6
TSMI | Tissue small intestine | | Weefsel klein intestinaal | deprecated | added v2.3, removed after v2.6
TUB | Tube NOS | | Slang, niet anders gespecificeerd | deprecated | added v2.3, removed after v2.6
ULC | Ulcer | Geschwür | Maagzweer | deprecated | added v2.2, removed after v2.6
UMB | Umbilical blood | Nabelblut | Navelstreng bloed | deprecated | from v2.1, removed after v2.6
UMED | Unknown medicine | | Onbekende medicatie | deprecated | added v2.3, removed after v2.6
UR | Urine | Urin | Urine | deprecated | from v2.1, removed after v2.6
URC | Urine clean catch | Mittelstrahlurin | Urine midstream | deprecated | added v2.2, removed after v2.6
URNS | Urine sediment | | Urine sediment | deprecated | added v2.3, removed after v2.6
URT | Urine catheter | Katheterurin | Urine catether | deprecated | added v2.2, removed after v2.6
URTH | Urethra | Urethra | Urinebuis | deprecated | from v2.1, removed after v2.6
USUB | Unknown substance | | Onbekende substantie | deprecated | added v2.3, removed after v2.6
VITF | Vitreous Fluid | | Glasvocht | deprecated | added v2.4, removed after v2.6
VOM | Vomitus | Erbrochenes | Vomitus | deprecated | added v2.2, removed after v2.6
WAT | Water | | Water | deprecated | added v2.3, removed after v2.6
WBC | Leukocytes | Leukozyten | Leukocyten | deprecated | from v2.1, removed after v2.6
WICK | Wick | Zwischengefäß bei Infusoren (?) | Lont | deprecated | added v2.2, removed after v2.6
WND | Wound | Wundabstrich | Wond | deprecated | from v2.1, removed after v2.6
WNDA | Wound abscess | Wundabszeß | Wondabces | deprecated | added v2.2, removed after v2.6
WNDD | Wound drainage | Wunddrainage | Wond drainage | deprecated | added v2.2, removed after v2.6
WNDE | Wound exudate | Wundexsudat | Wond exsudaat | deprecated | added v2.2, removed after v2.6
XXX | To be specified in another part of the message | | Wordt gespecificeerd in een ander deel van het bericht | deprecated | added v2.3, removed after v2.6

4.2.13.74 HL7 Version 2 Table 0074

URL: https://hl7.org/fhir/STU3/v2/0074/index.html

This page is part of the FHIR Specification (v3.0.2: STU 3). The current version which supercedes this version is 4.0.1. For a full list of available versions, see the Directory of published versions

Vocabulary Work Group | Maturity Level: N/A | External | Use Context: Any

This is a table defined as part of HL7 v2 . Related FHIR content: v2 Diagnostic Service Section ID.

Summary

Name: | v2 Diagnostic Service Section ID
Definition: | FHIR Value set/code system definition for HL7 v2 table 0074 (Diagnostic Service Section ID)
Code System URL: | http://hl7.org/fhir/v2/0074
Value Set URL: | http://hl7.org/fhir/ValueSet/v2-0074
OID: | ??
CodeSystem Resource | XML / JSON
ValueSet Resource | XML / JSON

This value set is used in the following places:

* This value set is the designated 'entire code system' value set for v2 Diagnostic Service Section ID

4.2.13.74.1 Code System Content

Diagnostic Service Section ID

Code | Description | Deutsch (German) | Nederlands (Dutch) | Comment | Version
AU | Audiology | Audiologie | Audiologie | | added v2.2
BG | Blood Gases | Blutgase | Bloedgassen | | from v2.1
BLB | Blood Bank | Blutbank | Bloedbank | | added v2.2
CG | Cytogenetics | | Cytogenetica | | added v2.8.2
CH | Chemistry | Klinische Chemie | Chemie | | from v2.1
CP | Cytopathology | Zellpathologie | Cytopathologie | | from v2.1
CT | CAT Scan | Computertomographie | CAT-scan | | from v2.1
CTH | Cardiac Catheterization | Herzkatheter | Hartcatetherisatie | | added v2.2
CUS | Cardiac Ultrasound | Kardiologische Ultraschalluntersuchung | Hart ultrasound | | from v2.1
EC | Electrocardiac (e.g. EKG, EEC, Holter) | Elektrokardiographie | Electrocardiac (bijv. EKG, EEC, Holter) | | from v2.1
EN | Electroneuro (EEG, EMG,EP,PSG) | Elektroneurographie, Elektroencephalographie | Electroneuro (EEG, EMG,EP,PSG) | | added v2.2
GE | Genetics | | Genetica | | added v2.8.2
HM | Hematology | Hämatologie | Hematologie | | from v2.1
ICU | Bedside ICU Monitoring | | IC monitoring naast het bed | | added v2.3
IMG | Diagnostic Imaging | | Diagnostisch beeldvorming | deprecated | added v2.4, removed after v2.4
IMM | Immunology | Immunologie | Immunologie | | from v2.1
LAB | Laboratory | | Laboratorium | | added v2.3
MB | Microbiology | Mikrobiologie | Microbiologie | | from v2.1
MCB | Mycobacteriology | Mykobakteriologie | Mycobacteriologie | | from v2.1
MYC | Mycology | Mykologie | Mycology | | from v2.1
NMR | Nuclear Magnetic Resonance | Kernspintomographie (MR) | Nucleaire magnetisch resonantie | | from v2.1
NMS | Nuclear Medicine Scan | Szintigramm | Nucleaire geneeskunde scan | | from v2.1
NRS | Nursing Service Measures | Pflegemaßnahme | Verpleegkundige service maatregelen | | from v2.1
OSL | Outside Lab | Externes Labor | Outside Lab | | added v2.2
OT | Occupational Therapy | Beschäftigungstherapie | Ergotherapie | | from v2.1
OTH | Other | Andere | Anders | | from v2.1
OUS | OB Ultrasound | Geburtshilfiche Ultraschalluntersuchung | OB Ultrasound | | from v2.1
PAR | Parasitology | | Parasitologie | deprecated | added v2.4, removed after v2.4
PAT | Pathology (gross & histopath, not surgical) | | Pathologie (gross & histopath, niet chirurgisch) | deprecated | added v2.4, removed after v2.4
PF | Pulmonary Function | Lungenfunktion | Pulmonaire functie | | added v2.2
PHR | Pharmacy | Apotheke | Medicatie | | from v2.1
PHY | Physician (Hx. Dx, admission note, etc.) | Arzt (Krankengeschichte, Diagnose, Aufnahmeuntersuchung) | Arts (Hx. Dx, opnameverslag, etc.) | | added v2.2
PT | Physical Therapy | physiklische Therapie | Lichamelijke oefening | | from v2.1
RAD | Radiology | Radiologie | Radiologie | | added v2.3
RC | Respiratory Care (therapy) | Atemtherapie | Respiratoire zorg (therapie) | | from v2.1
RT | Radiation Therapy | Strahlentherapie | Stralingstherapie | | from v2.1
RUS | Radiology Ultrasound | Radiologische Ultraschalluntersuchung | Radiologie ultrasound | | from v2.1
RX | Radiograph | Röntgenaufnahme | Radiograph | | added v2.2
SP | Surgical Pathology | Operative Pathologie | Chirurgische pathologie | | from v2.1
SR | Serology | Serologie | Serologie | | from v2.1
TX | Toxicology | Toxikologie | Toxicologie | | from v2.1
URN | Urinalysis | | Urinalyse | deprecated | added v2.4, removed after v2.4
VR | Virology | Virologie | Virologie | | added v2.2
VUS | Vascular Ultrasound | Ultraschalluntersuchung der Gefäße | Vasculaire Ultrasound | | from v2.1
XRC | Cineradiograph | Röntgenkinematographie | Cineradiograph | | from v2.1

4.2.13.76 HL7 Version 2 Table 0076

URL: https://hl7.org/fhir/STU3/v2/0076/index.html

This page is part of the FHIR Specification (v3.0.2: STU 3). The current version which supercedes this version is 4.0.1. For a full list of available versions, see the Directory of published versions

Vocabulary Work Group | Maturity Level: N/A | External | Use Context: Any

This is a table defined as part of HL7 v2 . Related FHIR content: v2 Message Type.

Summary

Name: | v2 Message Type
Definition: | FHIR Value set/code system definition for HL7 v2 table 0076 (Message Type)
Code System URL: | http://hl7.org/fhir/v2/0076
Value Set URL: | http://hl7.org/fhir/ValueSet/v2-0076
OID: | ??
CodeSystem Resource | XML / JSON
ValueSet Resource | XML / JSON

This value set is used in the following places:

* This value set is the designated 'entire code system' value set for v2 Message Type

4.2.13.76.1 Code System Content

Message Type

Code | Description | Deutsch (German) | Nederlands (Dutch) | Comment | Version
ACK | General acknowledgment message | Empfangsbestätigung | Algemeen bevestigingsbericht | 2 | from v2.1
ADR | ADT response | Antwort auf Anfrage bezüglich Aufnahme / Verlegung / Entlassung von Patienten | ADT antwoord | 3 - Deprecated | added v2.2
ADT | ADT message | Aufnahme / Entlassung / Verlegung | ADT-bericht | 3 | added v2.2
ARD | Ancillary RPT (display) (for backward compatibility only) | Befundbericht | Aanvullend RPT (weergave) (alleen voor backward compatbiliteit) | deprecated | from v2.1, removed after v2.3.1
BAR | Add/change billing account | Hinzufügen / Ändern von Abrechnungsdaten | Toevoegen/wijzigen facturatie-account | 6 | from v2.1
BPS | Blood product dispense status message | | Bloedproduct verstrekking status bericht | 4 | added v2.5
BRP | Blood product dispense status acknowledgement message | | Bloedproduct verstrekking status bevestigingsbericht | 4 | added v2.5
BRT | Blood product transfusion/disposition acknowledgement message | | Bloedproduct transfusie/dispositie bevestigingsbericht | 4 | added v2.5
BTS | Blood product transfusion/disposition message | | Bloedproduct transfusie/dispositie bericht | 4 | added v2.5
CCF | Collaborative Care Fetch | | Ketenzorg ophalen | 7 | added v2.7
CCI | Collaborative Care Information | | Ketenzorg informatie | 7 | added v2.7
CCM | Collaborative Care Message | | Ketenzorg bericht | 7 | added v2.7
CCQ | Collaborative Care Referral | | Ketenzorg verwijzing | 7 | added v2.7
CCU | Collaborative Care Referral | | Ketenzorg verwijzing | 7 | added v2.7
CNQ | Cancel query | | Annuleren query | deprecated | added v2.3, removed after v2.3
CQU | Collaborative Care Referral | | Ketenzorg verwijzing | 7 | added v2.7
CRM | Clinical study registration message | | Klinische studie registratie bericht | 7 | added v2.3.1
CSU | Unsolicited study data message | | Ongevraagde studie gegevens bericht | 7 | added v2.3
DBC | Create Donor Record | | Maak donorrecord | 4 | added v2.8
DBU | Update Donor Record | | Update donorrecord | 4 | added v2.8
DEL | Donor Eligibility | | Donor geschiktheid | 4 | added v2.8
DEO | Donor Eligibility Observation | | Donor geschiktheid observation | 4 | added v2.8
DER | Donor Eligibility Request | | Donor geschiktheid verzoek | 4 | added v2.8
DFT | Detail financial transactions | Einzelbuchung | Detail financiële transactions | 6 | added v2.2
DOC | Document response | | Document antwoord | 9 - Deprecated | added v2.3
DPR | Donation Procedure | | Donatie procedure | 4 | added v2.8
DRC | Donor Request to Collect | | Donor verzoek om te verzamelen | 4 | added v2.8
DSR | Display response | Antwort im Anzeigeformat | Weergave antwoord | 5 - Deprecated | from v2.1
EAC | Automated equipment command message | | Geautomatiseerd apparaat commando bericht | 13 | added v2.4
EAN | Automated equipment notification message | | Geautomatiseerd apparaat notificatie bericht | 13 | added v2.4
EAR | Automated equipment response message | | Geautomatiseerd apparaat antwoord bericht | 13 | added v2.4
EDR | Enhanced display response | | Verbeterd weergaveantwoord | deprecated | added v2.3, removed after v2.5.1
EHC | Health Care Invoice | | Zorgfactuur | 16 | added v2.6
EQQ | Embedded query language query | | Embedded query language query | deprecated | added v2.3, removed after v2.5.1
ERP | Event replay response | | Event replay response | deprecated | added v2.3, removed after v2.5.1
ERQ | Event replay query | | Event replay query | deprecated | added v2.3, removed after v2.3
ESR | Automated equipment status update acknowledgment message | | Geautomatiseerd apparaat statusupdate bevestigingsbericht | 13 | added v2.4
ESU | Automated equipment status update message | | Geautomatiseerd apparaat statusupdate bericht | 13 | added v2.4
INR | Automated equipment inventory request message | | Geautomatiseerd apparaat voorraad verzoekbericht | 13 | added v2.4
INU | Automated equipment inventory update message | | Geautomatiseerd apparaat voorraad update verzoekbericht | 13 | added v2.4
LSR | Automated equipment log/service request message | | Geautomatiseerd apparaat log/service verzoekbericht | 13 | added v2.4
LSU | Automated equipment log/service update message | | Geautomatiseerd apparaat log/service update bericht | 13 | added v2.4
MCF | Delayed Acknowledgment (Retained for backward compatibility only) | Verzögerte Empfangsbestätigung (veraltet; ACK benutzen) | Uitgestelde bevestiging (alleen voor backward compatibiliteit) | deprecated | from v2.1, removed after v2.5.1
MDM | Medical document management | | Medische document management | 9 | added v2.3

MFD | Master files delayed application acknowledgment | Verzögerte Empfangsbestätigung für Stammdateiänderung | Master files uitgesteld applicatie antwoord | 8 - Deprecated | added v2.2
MFK | Master files application acknowledgment | Empfangsbestätigung für Stammdateiänderung | Master files applicatie antwoord | 8 | added v2.2
MFN | Master files notification | Stammdateiänderung | Master files notificatie | 8 | added v2.2
MFQ | Master files query | | Master files query | 8 - Deprecated | added v2.3
MFR | Master files response | Antwort auf Stammdateianfrage | Master files antwoord | 8 - Deprecated | added v2.2
NMD | Application management data message | Asynchrone Statusmeldung eines Systems | Applicatie management gegevens bericht | 14 | added v2.2
NMQ | Application management query message | Anfrage / Kommando an ein anderes System im Netz | Applicatie management query bericht | 14 - Deprecated | added v2.2
NMR | Application management response message | Antwort auf Anfrage / Kommando | Applicatie management antwoord bericht | 14 - Deprecated | added v2.2
OMB | Blood product order message | | Bloedproduct aanvraag bericht | 4 | added v2.5
OMD | Dietary order | | Dieet-gerelateerde aanvraag | 4 | added v2.4
OMG | General clinical order message | | Algemeen klinisch aanvraagbericht | 4 | added v2.4
OMI | Imaging order | | Beeld aanvraag | 4 | added v2.5
OML | Laboratory order message | | Laboratorium aanvraagbericht | 4 | added v2.4
OMN | Non-stock requisition order message | | Niet-voorraad verzoek aanvraag bericht | 4 | added v2.4
OMP | Pharmacy/treatment order message | | Medicatie/behandeling aanvraagbericht | 4 | added v2.4
OMQ | General order message with document payload | | Algemeen aanvraag bericht met document inhoud | 4 | added v2.8
OMS | Stock requisition order message | | Voorraad verzoek aanvraag bericht | 4 | added v2.4
OPL | Population/Location-Based Laboratory Order Message | | Populatie/locatie-gebaseerde laboratorium aanvraag bericht | 4 | added v2.6
OPR | Population/Location-Based Laboratory Order Acknowledgment Message | | Populatie/locatie-gebaseerde laboratorium aanvraag bevestigingsbericht | 4 | added v2.6
OPU | Unsolicited Population/Location-Based Laboratory Observation Message | | Ongevraagd populatie/locatie-gebaseerde laboratoriumobservatie bericht | 7 | added v2.6
ORA | Observation Report Acknowledgment | | Observatieverslag bevestiging | 7 | added v2.7
ORB | Blood product order acknowledgement message | | Bloedproduct aanvraag bevestigingsbericht | 4 | added v2.5
ORD | Dietary order acknowledgment message | | Dieet/voedsel aanvraag bevestigingsbericht | 4 | added v2.4
ORF | Query for results of observation | Untersuchungsergebnisse | Query voor observatieresultaten | 7 - Deprecated | from v2.1
ORG | General clinical order acknowledgment message | | Algemene klinische aanvraag bevestigingsbericht | 4 | added v2.4
ORI | Imaging order acknowledgement message | | Beeld aanvraag bevestigingsbericht | 4 | added v2.5
ORL | Laboratory acknowledgment message (unsolicited) | | Laboratorium aanvraag bevestigingsbericht (ongevraagd) | 7 | added v2.4
ORM | Pharmacy/treatment order message | Auftrag / Verordnung | Medicatie/therapie aanvraagbericht | 4 - Deprecated | from v2.1
ORN | Non-stock requisition - General order acknowledgment message | | Niet-voorraad verzoek - Algemeen aanvraag bevestigingbericht | 4 | added v2.4
ORP | Pharmacy/treatment order acknowledgment message | | Medicatie/therapie aanvraag bevestigingsbericht | 4 | added v2.4
ORR | General order response message response to any ORM | Empfangsbestätigung von der Anwendung für einen Auftrag | Algemeen aanvraag antwoordbericht op een ORM | 4 - Deprecated | from v2.1
ORS | Stock requisition - Order acknowledgment message | | Voorraad verzoek - Algemeen aanvraag bevestigingbericht | 4 | added v2.4
ORU | Unsolicited transmission of an observation message | Nicht angeforderte Untersuchungsergebnisse | Ongevraagde verzending van een observatiebericht | 7 | from v2.1
ORX | General Order Message with Document Payload Acknowledgement | | Algemeen aanvraag bericht met document inhoud bevestiging | 4 | added v2.8
OSM | Specimen Shipment Message | | Monster verzending bericht | 7 | added v2.7
OSQ | Query response for order status | Anfrage nach Auftragsstatus | Antwoord op orderstatus | 4 - Deprecated | from v2.1
OSR | Query response for order status | | Antwoord op orderstatus | 4 - Deprecated | added v2.3
OSU | Order status update | | Order status update | 4 | added v2.8
OUL | Unsolicited laboratory observation message | | Ongevraagd laboratoriumobservatiebericht | 7 | added v2.4
PEX | Product experience message | | Productervaring bericht | 7 | added v2.3
PGL | Patient goal message | | Patiënt doel bericht | 12 | added v2.3
PIN | Patient insurance information | | Patiënt verzekeringsinformatie | 11 | added v2.3
PMU | Add personnel record | | Toevoegen personeel record | 15 | added v2.4
PPG | Patient pathway message (goal-oriented) | | Patiënt zorgpad bericht (doel-georiënteerd) | 12 | added v2.3
PPP | Patient pathway message (problem-oriented) | | Patiënt zorgpad bericht (probleem-georiënteerd) | 12 | added v2.3.1
PPR | Patient problem message | | Patiënt probleem bericht | 12 | added v2.3
PPT | Patient pathway goal-oriented response | | Patiënt zorgpad doel-georiënteerd antwoord | Deprecated | added v2.3
PPV | Patient goal response | | Patiënt doel antwoord | Deprecated | added v2.3
PRR | Patient problem response | | Patiënt probleem antwoord | Deprecated | added v2.3
PTR | Patient pathway problem-oriented response | | Patiënt zorgpad probleem-georiënteerd antwoord | Deprecated | added v2.3
QBP | Query by parameter | | Query met parameters | 5 | added v2.4
QCK | Query general acknowledgment | | Query algemene bevestiging | 5 - Deprecated | added v2.3
QCN | Cancel query | | Annuleer query | 5 | added v2.4
QRY | Query, original mode | Anfrage | Query, original modus | 3 | added v2.2
QSB | Create subscription | | Maak abonnement | 5 | added v2.4
QSX | Cancel subscription/acknowledge message | | Annuleer abonnement/bevestigingsbericht | 5 | added v2.4
QVR | Query for previous events | | Query voor vorige events | 5 | added v2.4
RAR | Pharmacy/treatment administration information | Antwort auf Anfrage bezüglich Verabreichung von Medikamenten | Medicatie/therapie toediening informatie | 4 - Deprecated | added v2.2
RAS | Pharmacy/treatment administration message | Erfolgte Verabreichung von Medikamenten | Medicatie/therapie toediening bericht | 4 | added v2.2
RCI | Return clinical information | | Antwoord klinische informatie | 11 | added v2.3
RCL | Return clinical list | | Opleveren klinische lijst | 11 | added v2.3

RDE | Pharmacy/treatment encoded order message | Medikamentenverordnung (Apotheke) | Medicatie/therapie gecodeerde aanvraag bericht | 4 | added v2.2
RDR | Pharmacy/treatment dispense information | Antwort auf Anfrage bezüglich Abgabe von Medikamenten | Medicatie/therapie verstrekking informatie | 4 | added v2.2
RDS | Pharmacy/treatment dispense message | Abgabe von Medikamenten | Medicatie/therapie verstrekking bericht | 4 | added v2.2
RDY | Display based response | | Weergave-gebaseerd antwoord | 5 | added v2.4
REF | Patient referral | | Patiënt verwijzing | 11 | added v2.3
RER | Pharmacy/treatment encoded order information | Antwort auf Anfrage bezüglich Medikamentenverordnung (Apotheke) | Medicatie/therapie gecodeerde aanvraag informatie | 4 - Deprecated | added v2.2
RGR | Pharmacy/treatment dose information | Antwort auf Anfrage bezüglich Verabreichungsvorschrift für Medikamente | Medicatie/therapie dosering informatie | 4 - Deprecated | added v2.2
RGV | Pharmacy/treatment give message | Verabreichungsvorschrift für Medikamente | Medicatie/therapie gegeven informatie | 4 | added v2.2
ROC | Request clinical information | | Verzoek voor klinische informatie | deprecated | added v2.3, removed after v2.3
ROD | Request pateint demographics | | Verzoek voor demografische patiëntgegevens | deprecated | added v2.3, removed after v2.3
ROR | Pharmacy/treatment order response | Antwort auf Anfrage bezüglich Medikamentenverordnung | Medicatie/therapie aanvraag antwoord | 4 - Deprecated | added v2.2
RPA | Return patient authorization | | Antwoord patiënt authorisatie | 11 | added v2.3
RPI | Return patient information | | Antwoord patiënt informatie | 11 | added v2.3
RPL | Return patient display list | | Antwoord patiënt weergavelijst | 11 | added v2.3
RPR | Return patient list | | Antwoord patiëntlijst | 11 | added v2.3
RQA | Request patient authorization | | Verzoek voor patiënt autorisatie | 11 | added v2.3
RQC | Request clinical information | | Verzoek voor klinische informatie | 11 | added v2.3
RQI | Request patient information | | Verzoek voor patiënt informatie | 11 | added v2.3
RQP | Request patient demographics | | Verzoek voor demografische patiëntgegevens | 11 | added v2.3
RQQ | Event replay query | | Event replay query | deprecated | added v2.3, removed after v2.5.1
RRA | Pharmacy/treatment administration acknowledgment message | Empfangsbestätigung für Verabreichungsmeldung | Medicatie/therapie toediening bevestigingsbericht | 4 | added v2.2
RRD | Pharmacy/treatment dispense acknowledgment message | Empfangsbestätigung für Abgabemeldung | Medicatie/therapie verstrekking bevestigingsbericht | 4 | added v2.2
RRE | Pharmacy/treatment encoded order acknowledgment message | Empfangsbestätigung für Verordnung (Apotheke) | Medicatie/therapie gecodeerde aanvraag bevestigingsbericht | 4 | added v2.2
RRG | Pharmacy/treatment give acknowledgment message | Empfangsbestätigung für Verabreichungsvorschrift | Medicatie/therapie gegevens bevestigingsbericht | 4 | added v2.2
RRI | Return referral information | | Antwoord verwijzing informatie | 11 | added v2.3
RSP | Segment pattern response | | Segmentpatroon antwoord | 5 | added v2.4
RTB | Tabular response | | Tabelpatroon antwoord | 5 | added v2.4
SCN | Notification of Anti-Microbial Device Cycle Data | | Notificatie van anti-microbiële apparaat cycle gegevens | 17 | added v2.6
SDN | Notification of Anti-Microbial Device Data | | Notificatie van anti-microbiële apparaat gegevens | 17 | added v2.6
SDR | Sterilization anti-microbial device data request | | Sterilisatie anti-microbiële apparaat gegevens verzoek | 17 | added v2.6
SIU | Schedule information unsolicited | | Agenda informatie ongevraagd | 10 | added v2.3
SLN | Notification of New Sterilization Lot | | Notificatie voor nieuwe sterilisatie batch | 17 | added v2.6
SLR | Sterilization lot request | | Verzoek voor sterilisatie batch | 17 | added v2.6
SMD | Sterilization anti-microbial device cycle data request | | Sterilisatie anti-microbiële apparaat cycle gegevens verzoek | 17 | added v2.6
SPQ | Stored procedure request | | Stored procedure verzoek | deprecated | added v2.3, removed after v2.5.1
SQM | Schedule query message | | Agenda query bericht | 10 - Deprecated | added v2.3
SQR | Schedule query response | | Agenda query antwoord | 10 - Deprecated | added v2.3
SRM | Schedule request message | | Agenda verzoek bericht | 10 | added v2.3
SRR | Scheduled request response | | Antwoord agenda verzoek | 10 | added v2.3
SSR | Specimen status request message | | Monster status verzoek bericht | 13 | added v2.4
SSU | Specimen status update message | | Monster status update bericht | 13 | added v2.4
STC | Notification of Sterilization Configuration | | Notificatie voor sterilisatie configuratie | 17 | added v2.6
STI | Sterilization item request | | Sterilisatie item verzoek | 17 | added v2.6
SUR | Summary product experience report | | Samenvatting productervaring rapport | 7 - Deprecated | added v2.3.1
TBR | Tabular data response | | Tabel gegevens antwoord | 5 - Deprecated | added v2.3
TCR | Automated equipment test code settings request message | | Geautomatiseerd apparaat testcode instellingen verzoek bericht | 13 | added v2.4
TCU | Automated equipment test code settings update message | | Geautomatiseerd apparaat testcode instellingen update bericht | 13 | added v2.4
UDM | Unsolicited display update message | Nicht angeforderte Nachricht im Anzeigeformat | Ongevraagd weergave updte bericht | 5 | from v2.1
VQQ | Virtual table query | | Virtuele tabel query | deprecated | added v2.3, removed after v2.5.1
VXQ | Query for vaccination record | | Vaccinatierecord query | 4 - Deprecated | added v2.3
VXR | Vaccination record response | | Vaccinatierecord antwoord | 4 - Deprecated | added v2.3
VXU | Unsolicited vaccination record update | | Ongevraagde vaccinatierecord update | 4 | added v2.3
VXX | Response for vaccination query with multiple PID matches | | Antwoord vaccinatie query met meerdere PID matches | 4 -Deprecated | added v2.3

4.2.13.78 HL7 Version 2 Table 0078

URL: https://hl7.org/fhir/STU3/v2/0078/index.html

This page is part of the FHIR Specification (v3.0.2: STU 3). The current version which supercedes this version is 4.0.1. For a full list of available versions, see the Directory of published versions

Vocabulary Work Group | Maturity Level: N/A | External | Use Context: Any

This is a table defined as part of HL7 v2 . Related FHIR content: v2 Interpretation Codes.

Summary

Name: | v2 Interpretation Codes
Definition: | FHIR Value set/code system definition for HL7 v2 table 0078 (Interpretation Codes)
Code System URL: | http://hl7.org/fhir/v2/0078
Value Set URL: | http://hl7.org/fhir/ValueSet/v2-0078
OID: | ??
CodeSystem Resource | XML / JSON
ValueSet Resource | XML / JSON

This value set is used in the following places:

* This value set is the designated 'entire code system' value set for v2 Interpretation Codes

4.2.13.78.1 Code System Content

Interpretation Codes

Code | Description | Deutsch (German) | Nederlands (Dutch) | Comment | Version

< | Off scale low | Unter Meßbereich (Extremwertverletzung) | Onder absolute ondergrens instrumentschaal | The result is below the minimum detection limit (the test procedure or equipment is the limiting factor).<p>Synonyms: Below analytical limit, low off scale | from v2.1

> | Off scale high | Über Meßbereich (Extremwertverletzung) | Boven absolute bovengrens instrumentschaal | The result is above the maximum quantifiable limit (the test procedure or equipment is the limiting factor).<p>Synonyms: Above analytical limit, high off scale | added v2.2

A | Abnormal | anormal (nicht numerisch) | Abnormaal | The result or observation value is outside the reference range or expected norm (as defined for the respective test procedure).<p>Note: Typically applies to non-numeric results. | from v2.1

AA | Critically abnormal | Pathologisch (nicht numerisch) | Kritiek abnormaal | The result or observation value is outside a reference range or expected norm at a level at which immediate action should be considered for patient safety (as defined for the respective test procedure).<p>[Note: Typically applies to non-numeric results. | from v2.1

AC | Anti-complementary substances present | | Anti-complementaire stoffen aanwezig | Deprecated | added v2.7

B | Better | Verbesserung | Beter | The current result or observation value has improved compared to the previous result or observation value (the change is significant as defined in the respective test procedure).<p>Note: This can be applied to quantitative or qualitative observations. | added v2.2

D | Significant change down | Deutlicher Trend nach unten | Significante wijzging omlaag | The current result has decreased from the previous result for a quantitative observation (the change is significant as defined in the respective test procedure). | from v2.1

DET | Detected | | Gedetecteerd | The measurement of the specified component / analyte, organism or clinical sign above the limit of detection of the performed test or procedure. | added v2.7

H | High | Oberhalb oberer Grenze Referenzbereich | Hoog | The result for a quantitative observation is above the upper limit of the reference range (as defined for the respective test procedure).<p>Synonym: Above high normal | from v2.1

HH | Critically high | Oberhalb oberer pathologischer Grenze | Kritiek hoog | The result for a quantitative observation is above a reference level at which immediate action should be considered for patient safety (as defined for the respective test procedure).<p>Synonym: Above upper panic limits | from v2.1

HM | Hold for Medical Review | | Vastgehouden voor medische review | Deprecated | added v2.8

HU | Very high | | Zeer hoog | Significantly high: A test result that is significantly higher than the reference (normal) or therapeutic interval, butÂ has not reached theÂ criticallyÂ high valueÂ andÂ might need special attention, as defined by the laboratory or the clinician.<p>Note: | added v2.8.2

I | Intermediate | Intermediär | Gemiddeld | Bacterial strain inhibited in vitro by a<p>concentration of an antimicrobial agent that is associated with<p>uncertain therapeutic effect.<p>Reference: CLSI (http://www.clsi.org/Content/NavigationMenu/Resources/HarmonizedTerminologyDatabase/Harmonized_Ter | from v2.1

IE | Insufficient evidence | | Onvoldoende bewijs | There is insufficient evidence that the species in question is a good target for therapy with the drug. A categorical interpretation is not possible.<p>Reference: EUCAST<p>Note: A MIC with "IE" and/or a comment may be reported (without an accompanying S, | added v2.8.2

IND | Indeterminate | | Onbepaald | The specified component / analyte, organism or clinical sign could neither be declared positive / negative or detected / not detected by the performed test or procedure. | added v2.7

L | Low | Unterhalb unterer Grenze Referenzbereich | Laag | The result for a quantitative observation is below the lower limit of the reference range (as defined for the respective test procedure).<p>Synonym: Below low normal | added v2.2

LL | Critically low | Unterhalb unterer pathologischer Grenze | Kritiek laag | The result for a quantitative observation is below a reference level at which immediate action should be considered for patient safety (as defined for the respective test procedure).<p>Synonym: Below lower panic limits | from v2.1

LU | Very low | | Zeer laag | Significantly low: A test result that is significantly lower than the reference (normal) or therapeutic interval, butÂ has not reached theÂ criticallyÂ low valueÂ andÂ mightÂ need special attention, as defined by the laboratory or the clinician.<p>Note: T | added v2.8.2

MS | Moderately susceptible. Indicates for microbiology susceptibilities only. | mäßig empfindlich | Gemiddeld gevoelig. Alleen voor microbiologische gevoeligheid. | Deprecated - CLSI now only supports S, I & R. This information can be found in CLSI document M100-S22; Vol. 32 No.3; CLSI Performance<p>Standards for Antimicrobial Susceptibility Testing; Twenty-Second Informational Supplement. Jan 2012. | from v2.1

N | Normal | Normal (nicht numerisch) | Normaal | The result or observation value is within the reference range or expected norm (as defined for the respective test procedure).<p>Note: Applies to numeric or non-numeric results. | added v2.2

ND | Not Detected | | Niet-gedetecteerd | The presence of the specified component / analyte, organism or clinical sign could not be determined within the limit of detection of the performed test or procedure. | added v2.7

NEG | Negative | | Negatief | An absence finding of the specified component / analyte, organism or clinical sign based on the established threshold of the performed test or procedure.<p>Note: Negative does not necessarily imply the complete absence of the specified item. | added v2.7

NR | Non-reactive | | Niet-reactief | An absence finding used to indicate that the specified component / analyte did not react measurably with the reagent. | added v2.7

NS | Non-susceptible | | Niet-gevoelig | A category used for isolates for which only a susceptible interpretive criterion has been designated because of the absence or rare occurrence of resistant strains. Isolates that have MICs above or zone diameters below the value indicated for the suscepti | added v2.8.2

null | No range defined, or normal ranges don't apply | Kein Referenzbereich / Referenzbereich nicht anwendbar | Geen referentiewaarden gedefinieerd of normale waarden niet van toepassing | Deprecated | from v2.1

OBX | Interpretation qualifiers in separate OBX segments | | Interpretatie qualifiers in afzonderlijke OBX-segmenten | Deprecated | added v2.8

POS | Positive | | Positief | A presence finding of the specified component / analyte, organism or clinical sign based on the established threshold of the performed test or procedure. | added v2.7

QCF | Quality Control Failure | | Kwaliteitscontrole fout | Deprecated | added v2.7
R | Resistant | Resistent | Resistent | Bacterial strain inhibited in vitro by a concentration of an antimicrobial agent that is associated with a high likelihood of therapeutic failure.<p>Reference: CLSI (http://www.clsi.org/Content/NavigationMenu/Resources/HarmonizedTerminologyDatabase/Harmon | from v2.1
RR | Reactive | | Reactief | A presence finding used to indicate that the specified component / analyte reacted with the reagent above the reliably measurable limit of the performed test. | added v2.7
S | Susceptible | Empfindlich | Gevoelig | Bacterial strain inhibited by in vitro concentration of an antimicrobial agent that is associated with a high likelihood of therapeutic success.<p>Reference: CLSI (http://www.clsi.org/Content/NavigationMenu/Resources/HarmonizedTerminologyDatabase/Harmoniz | from v2.1
SDD | Susceptible-dose dependent | | Gevoelig dosis-afhankelijk | A category that includes isolates with antimicrobial agent minimum inhibitory concentrations (MICs) that approach usually attainable blood and tissue levels and for which response rates may be lower than for susceptible isolates.<p>Reference: CLSI documen | added v2.8.2
SYN-R | Synergy - resistant | | Synergie - resistent | A category for isolates where the bacteria (e.g. enterococci) are not susceptible in vitro to a combination therapy (e.g. high-level aminoglycoside and cell wall active agent). This is predictive that this combination therapy will not be effective.<p>Usa | added v2.8.2
SYN-S | Synergy - susceptible | | Synergie - gevoelig | A category for isolates where the bacteria (e.g. enterococci) are susceptible in vitro to a combination therapy (e.g. high-level aminoglycoside and cell wall active agent). This is predictive that this combination therapy will be effective.<p>Usage Note: | added v2.8.2
TOX | Cytotoxic substance present | | Cytotoxische stoffen aanwezig | Deprecated | added v2.7
U | Significant change up | Deutlicher Trend nach oben | Significante wijzging omhoog | The current result has increased from the previous result for a quantitative observation (the change is significant as defined in the respective test procedure). | from v2.1
VS | Very susceptible. Indicates for microbiology susceptibilities only. | Sehr empfindlich | Zeer gevoelig. Alleen voor microbiologische gevoeligheid. | Deprecated - CLSI now only supports S, I & R. This information can be found in CLSI document M100-S22; Vol. 32 No.3; CLSI Performance<p>Standards for Antimicrobial Susceptibility Testing; Twenty-Second Informational Supplement. Jan 2012. | from v2.1
W | Worse | Verschlechterung | Slechter | The current result or observation value has degraded compared to the previous result or observation value (the change is significant as defined in the respective test procedure).<p>Note: This can be applied to quantitative or qualitative observations. | added v2.2
WR | Weakly reactive | | Zwak reactief | A weighted presence finding used to indicate that the specified component / analyte reacted with the reagent, but below the reliably measurable limit of the performed test. | added v2.7

4.2.13.80 HL7 Version 2 Table 0080

URL: https://hl7.org/fhir/STU3/v2/0080/index.html

This page is part of the FHIR Specification (v3.0.2: STU 3). The current version which supercedes this version is 4.0.1. For a full list of available versions, see the Directory of published versions

Vocabulary Work Group | Maturity Level: N/A | External | Use Context: Any

This is a table defined as part of HL7 v2 . Related FHIR content: v2 Nature of Abnormal Testing.

Summary

Name: | v2 Nature of Abnormal Testing
Definition: | FHIR Value set/code system definition for HL7 v2 table 0080 (Nature of Abnormal Testing)
Code System URL: | http://hl7.org/fhir/v2/0080
Value Set URL: | http://hl7.org/fhir/ValueSet/v2-0080
OID: | ??
CodeSystem Resource | XML / JSON
ValueSet Resource | XML / JSON

This value set is used in the following places:

* This value set is the designated 'entire code system' value set for v2 Nature of Abnormal Testing

4.2.13.80.1 Code System Content

Nature of Abnormal Testing

Code | Description | Deutsch (German) | Nederlands (Dutch) | Comment | Version
A | An age-based population | Altersabhängig | Een op leeftijd gebaseerde populatie | | from v2.1
B | Breed | abhängig von Rasse oder Zucht | Dierenras | | added v2.5
N | None - generic normal range | Genereller Normalwert | Geen - algemene normale reeks | | from v2.1
R | A race-based population | Rasseabhängig | Een op ras gebaseerde populatie | | from v2.1
S | A sex-based population | Geschlechtsabhängig | Een op geslacht gebaseerde populatie | | from v2.1
SP | Species | abhängig von Spezies | Soort | | added v2.5
ST | Strain | abhängig von Bakterienstamm | Stam | | added v2.5

4.2.13.83 HL7 Version 2 Table 0083

URL: https://hl7.org/fhir/STU3/v2/0083/index.html

This page is part of the FHIR Specification (v3.0.2: STU 3). The current version which supercedes this version is 4.0.1. For a full list of available versions, see the Directory of published versions

Vocabulary Work Group | Maturity Level: N/A | External | Use Context: Any

This is a table defined as part of HL7 v2 . Related FHIR content: v2 Outlier Type.

Summary

Name: | v2 Outlier Type

Definition: | FHIR Value set/code system definition for HL7 v2 table 0083 (Outlier Type)
Code System URL: | http://hl7.org/fhir/v2/0083
Value Set URL: | http://hl7.org/fhir/ValueSet/v2-0083
OID: | ??
CodeSystem Resource | XML / JSON
ValueSet Resource | XML / JSON

This value set is used in the following places:

* This value set is the designated 'entire code system' value set for v2 Outlier Type

4.2.13.83.1 Code System Content

Outlier Type

Code | Description | Nederlands (Dutch) | Comment | Version
C | Outlier cost | Retentierecht kosten | | added v2.3.1
D | Outlier days | Retentierecht dagen | | added v2.3.1

4.2.13.85 HL7 Version 2 Table 0085

URL: https://hl7.org/fhir/STU3/v2/0085/index.html

This page is part of the FHIR Specification (v3.0.2: STU 3). The current version which supercedes this version is 4.0.1. For a full list of available versions, see the Directory of published versions

Vocabulary Work Group | Maturity Level: N/A | External | Use Context: Any

This is a table defined as part of HL7 v2 . Related FHIR content: v2 Observation Result Status Codes Interpretation.

Summary

Name: | v2 Observation Result Status Codes Interpretation
Definition: | FHIR Value set/code system definition for HL7 v2 table 0085 (Observation Result Status Codes Interpretation)
Code System URL: | http://hl7.org/fhir/v2/0085
Value Set URL: | http://hl7.org/fhir/ValueSet/v2-0085
OID: | ??
CodeSystem Resource | XML / JSON
ValueSet Resource | XML / JSON

This value set is used in the following places:

* This value set is the designated 'entire code system' value set for v2 Observation Result Status Codes Interpretation

4.2.13.85.1 Code System Content

Observation Result Status Codes Interpretation

Code | Description | Deutsch (German) | Nederlands (Dutch) | Comment | Version
A | Amended based on adjustments provided by the Placer (Physician) regarding patient demographics (such as age and/or gender or other patient specific information | | Aangevuld op basis van aanpassingen van de Placer (Arts) met betrekking tot patiënt demografie (zoals leeftijd en/of geslacht of andere patiënt-specifieke informatie | | added v2.8
B | Appended Report - Final results reviewed and further information provided for clarity without change to the original result values. | | Aangevuld verslag - Definitieve resultaten en verdere informatie gegeven voor duidelijkheid zonder dat de oorspronkelijke resultaatwaarden wijzigen | | added v2.8
C | Record coming over is a correction and thus replaces a final result | Korrektur bereits gemeldeter Ergebnisse | Dit record is een correctie en vervangt het definitief resultaat | | added v2.2
D | Deletes the OBX record | Gemeldete Ergebnisse löschen | Verwijdert het OBX record | | from v2.1
F | Final results | Endergebnis | Definitieve resultaten | | from v2.1
I | Specimen in lab; results pending | Probe im Labor - Ergebnisse stehen an | Monster in lab; resultaten volgen | | from v2.1
N | Not asked; used to affirmatively document that the observation identified in the OBX was not sought when the universal service ID in OBR-4 implies that it would be sought. | ungefragte Übertragung | Niet gevraagd; gebruikt om op schrift te stellen dat de observatie geïdentificeerd in de OBX niet werd gevraagd toen de universal section ID in OBR-4 implicileerde dat deze wel werd gezocht. | | added v2.3.1
O | Order detail description only (no result) | Anforderungsbeschreibung (ohne Ergebnisse) | Alleen aanvraag detail (geen resultaat) | | added v2.3.1
P | Preliminary results | Vorläufige Ergebnisse | Voorlopige resultaten | | added v2.2
R | Results entered -- not verified | Nicht validierte Ergebnisse | Resultaten ingevoerd -- niet geverifieerd | | from v2.1
S | Partial results. Deprecated. Retained only for backward compatibility as of V2.6. | Teilergebnisse | Gedeeltelijke resultaten. Vervallen. Alleen voor backward compatibiliteit sinds V2.6 | Deprecated. | from v2.1
U | Results status change to final without retransmitting results already sent as 'preliminary.' E.g. radiology changes status from preliminary to final | Vorläufiges Ergebnis wird Endergebnis, da keine Änderung | Result statuswijziging naar Definitief zonder de voorlopige resultaten opnieuw te sturen. Bijv. radiologie wijzigt status van voorlopig naar definitief | | added v2.2
V | Verified - Final results reviewed and confirmed to be correct, no change to result value, normal range or abnormal flag | | Geverifieerd - Definitieve resultaten gereviewd en correct bevonden, geen wijziging aan resultaatwaarde, normaalwaarde of abnormaal indicatie | | added v2.8
W | Post original as wrong, e.g. transmitted for wrong patient | fehlerhafte Übertragung | Oorspronkelijke resultaten verkeerd verstuurd, bijv. voor verkeerde patiënt | | added v2.3.1
X | Results cannot be obtained for this observation | Untersuchung führt zu keinem Ergebnis | Resultaten kunnen niet worden opgehaald voor deze observatie | | added v2.2

4.2.13.91 HL7 Version 2 Table 0091

URL: https://hl7.org/fhir/STU3/v2/0091/index.html

This page is part of the FHIR Specification (v3.0.2: STU 3). The current version which supercedes this version is 4.0.1. For a full list of available versions, see the Directory of published versions

Vocabulary Work Group | Maturity Level: N/A | External | Use Context: Any

This is a table defined as part of HL7 v2 . Related FHIR content: v2 Query Priority.

Summary

Name: | v2 Query Priority
Definition: | FHIR Value set/code system definition for HL7 v2 table 0091 (Query Priority)
Code System URL: | http://hl7.org/fhir/v2/0091
Value Set URL: | http://hl7.org/fhir/ValueSet/v2-0091
OID: | ??
CodeSystem Resource | XML / JSON
ValueSet Resource | XML / JSON

This value set is used in the following places:

* This value set is the designated 'entire code system' value set for v2 Query Priority

4.2.13.91.1 Code System Content

Query Priority

Code | Description | Deutsch (German) | Nederlands (Dutch) | Comment | Version
D | Deferred | Zeitverzögert | Uitgesteld | | from v2.1
I | Immediate | Sofort | Onmiddellijk | | from v2.1

4.2.13.92 HL7 Version 2 Table 0092

URL: https://hl7.org/fhir/STU3/v2/0092/index.html

This page is part of the FHIR Specification (v3.0.2: STU 3). The current version which supercedes this version is 4.0.1. For a full list of available versions, see the Directory of published versions

Vocabulary Work Group | Maturity Level: N/A | External | Use Context: Any

This is a table defined as part of HL7 v2 . Related FHIR content: v2 Re-Admission Indicator.

Summary

Name: | v2 Re-Admission Indicator
Definition: | FHIR Value set/code system definition for HL7 v2 table 0092 (Re-Admission Indicator)
Code System URL: | http://hl7.org/fhir/v2/0092
Value Set URL: | http://hl7.org/fhir/ValueSet/v2-0092
OID: | ??
CodeSystem Resource | XML / JSON
ValueSet Resource | XML / JSON

This value set is used in the following places:

* This value set is the designated 'entire code system' value set for v2 Re-Admission Indicator
* Encounter.hospitalization.reAdmission (Example)

4.2.13.92.1 Code System Content

Re-Admission Indicator

Code | Description | Deutsch (German) | Nederlands (Dutch) | Comment | Version
R | Re-admission | Wiederaufnahme | Heropname | | from v2.1

4.2.13.98 HL7 Version 2 Table 0098

URL: https://hl7.org/fhir/STU3/v2/0098/index.html

This page is part of the FHIR Specification (v3.0.2: STU 3). The current version which supercedes this version is 4.0.1. For a full list of available versions, see the Directory of published versions

Vocabulary Work Group | Maturity Level: N/A | External | Use Context: Any

This is a table defined as part of HL7 v2 . Related FHIR content: v2 Type of Agreement.

Summary

Name: | v2 Type of Agreement
Definition: | FHIR Value set/code system definition for HL7 v2 table 0098 (Type of Agreement)
Code System URL: | http://hl7.org/fhir/v2/0098
Value Set URL: | http://hl7.org/fhir/ValueSet/v2-0098
OID: | ??
CodeSystem Resource | XML / JSON
ValueSet Resource | XML / JSON

This value set is used in the following places:

* This value set is the designated 'entire code system' value set for v2 Type of Agreement

4.2.13.98.1 Code System Content

Type of Agreement

Code | Description | Nederlands (Dutch) | Comment | Version
M | Maternity | Moederschap | | added v2.3
S | Standard | Standaard | | added v2.3
U | Unified | Geünificeerd | | added v2.3

4.2.13.100 HL7 Version 2 Table 0100

URL: https://hl7.org/fhir/STU3/v2/0100/index.html

This page is part of the FHIR Specification (v3.0.2: STU 3). The current version which supercedes this version is 4.0.1. For a full list of available versions, see the Directory of published versions

Vocabulary Work Group | Maturity Level: N/A | External | Use Context: Any

This is a table defined as part of HL7 v2 . Related FHIR content: v2 Invocation event.

Summary

Name: | v2 Invocation event
Definition: | FHIR Value set/code system definition for HL7 v2 table 0100 (Invocation event)
Code System URL: | http://hl7.org/fhir/v2/0100
Value Set URL: | http://hl7.org/fhir/ValueSet/v2-0100
OID: | ??
CodeSystem Resource | XML / JSON
ValueSet Resource | XML / JSON

This value set is used in the following places:

* This value set is the designated 'entire code system' value set for v2 Invocation event

4.2.13.100.1 Code System Content

Invocation event

Code | Description | Deutsch (German) | Nederlands (Dutch) | Comment | Version
D | On discharge | Bei Entlassung | Bij ontslag | | from v2.1
O | On receipt of order | Bei Auftragseingang | Bij ontvangst van aanvraag | | from v2.1
R | At time service is completed | Mit Ende der Leistungserbringung | Bij voltooiing service | | from v2.1
S | At time service is started | Am Beginn der Leistungserbringung | Bij aanvang service | | from v2.1
T | At a designated date/time | Zum angegebenen Zeitpunkt | Op opgegeven moment | | from v2.1

4.2.13.102 HL7 Version 2 Table 0102

URL: https://hl7.org/fhir/STU3/v2/0102/index.html

This page is part of the FHIR Specification (v3.0.2: STU 3). The current version which supercedes this version is 4.0.1. For a full list of available versions, see the Directory of published versions

Vocabulary Work Group | Maturity Level: N/A | External | Use Context: Any

This is a table defined as part of HL7 v2 . Related FHIR content: v2 Delayed acknowledgment type.

Summary

Name: | v2 Delayed acknowledgment type
Definition: | FHIR Value set/code system definition for HL7 v2 table 0102 (Delayed acknowledgment type)
Code System URL: | http://hl7.org/fhir/v2/0102
Value Set URL: | http://hl7.org/fhir/ValueSet/v2-0102
OID: | ??
CodeSystem Resource | XML / JSON
ValueSet Resource | XML / JSON

This value set is used in the following places:

* This value set is the designated 'entire code system' value set for v2 Delayed acknowledgment type

4.2.13.102.1 Code System Content

Delayed acknowledgment type

Code | Description | Deutsch (German) | Nederlands (Dutch) | Comment | Version
D | Message received, stored for later processing | Nachricht erhalten, zur Bearbeitung gespeichert | Bericht ontvangen, opgeslagen voor verdere verwerking | deprecated | from v2.1, removed after v2.4
F | acknowledgment after processing | Bestätigung nach Verarbeitung (veraltet) | Bevestiging na verwerking | deprecated | added v2.2, removed after v2.4

4.2.13.103 HL7 Version 2 Table 0103

URL: https://hl7.org/fhir/STU3/v2/0103/index.html

This page is part of the FHIR Specification (v3.0.2: STU 3). The current version which supercedes this version is 4.0.1. For a full list of available versions, see the Directory of published versions

Vocabulary Work Group | Maturity Level: N/A | External | Use Context: Any

This is a table defined as part of HL7 v2 . Related FHIR content: v2 Processing ID.

Summary

Name: | v2 Processing ID
Definition: | FHIR Value set/code system definition for HL7 v2 table 0103 (Processing ID)
Code System URL: | http://hl7.org/fhir/v2/0103
Value Set URL: | http://hl7.org/fhir/ValueSet/v2-0103
OID: | ??
CodeSystem Resource | XML / JSON
ValueSet Resource | XML / JSON

This value set is used in the following places:

* This value set is the designated 'entire code system' value set for v2 Processing ID

4.2.13.103.1 Code System Content

Processing ID

Code	Description	Deutsch (German)	Nederlands (Dutch)	Comment	Version
D	Debugging	Test	Debugging		from v2.1
P	Production	Routine / Produktion	Productie		from v2.1
T	Training	Schulung	Training		from v2.1

4.2.13.104 HL7 Version 2 Table 0104

URL: https://hl7.org/fhir/STU3/v2/0104/index.html

This page is part of the FHIR Specification (v3.0.2: STU 3). The current version which supercedes this version is 4.0.1. For a full list of available versions, see the Directory of published versions

Vocabulary Work Group | Maturity Level: N/A | External | Use Context: Any

This is a table defined as part of HL7 v2 . Related FHIR content: v2 Version ID.

Summary

Name: | v2 Version ID
Definition: | FHIR Value set/code system definition for HL7 v2 table 0104 (Version ID)
Code System URL: | http://hl7.org/fhir/v2/0104
Value Set URL: | http://hl7.org/fhir/ValueSet/v2-0104
OID: | ??
CodeSystem Resource | XML / JSON
ValueSet Resource | XML / JSON

This value set is used in the following places:

* This value set is the designated 'entire code system' value set for v2 Version ID

4.2.13.104.1 Code System Content

Version ID

Code	Description	Deutsch (German)	Nederlands (Dutch)	Comment	Version
2.0	Release 2.0	Version 2.0, September 1988	Versie 2.0	September 1988	from v2.1
2.0D	Demo 2.0	Version 2.0, October 1988 (nur zu Demonstrationszwecken)	Demo 2.0	October 1988	from v2.1
2.1	Release 2.1	Version 2.1, März 1990	Versie 2.1	March 1990	from v2.1
2.2	Release 2.2	Version 2.2, Dezember 1994	Versie 2.2	December 1994	added v2.2
2.3	Release 2.3		Versie 2.3	March 1997	added v2.3
2.3.1	Release 2.3.1		Versie 2.3.1	May 1999	added v2.3.1
2.3.2	Release 2.3.2		Versie 2.3.2	deprecated	added v2.3.1, removed after v2.3.1
2.4	Release 2.4		Versie 2.4	November 2000	added v2.4
2.5	Release 2.5		Versie 2.5	May 2003	added v2.5
2.5.1	Release 2.5.1		Versie 2.5.1	January 2007	added v2.5.1
2.6	Release 2.6		Versie 2.6	July 2007	added v2.6
2.7	Release 2.7		Versie 2.6	November 2010	added v2.7
2.7.1	Release 2.7.1		Versie 2.7.1	July 2012	added v2.7.1
2.8	Release 2.8		Versie 2.8	February 2014	added v2.8
2.8.1	Release 2.8.1		Versie 2.8.1	April 2014	added v2.8.1

4.2.13.105 HL7 Version 2 Table 0105

URL: https://hl7.org/fhir/STU3/v2/0105/index.html

This page is part of the FHIR Specification (v3.0.2: STU 3). The current version which supercedes this version is 4.0.1. For a full list of available versions, see the Directory of published versions

Vocabulary Work Group | Maturity Level: N/A | External | Use Context: Any

This is a table defined as part of HL7 v2 . Related FHIR content: v2 Source of Comment.

Summary

Name: | v2 Source of Comment
Definition: | FHIR Value set/code system definition for HL7 v2 table 0105 (Source of Comment)
Code System URL: | http://hl7.org/fhir/v2/0105
Value Set URL: | http://hl7.org/fhir/ValueSet/v2-0105
OID: | ??
CodeSystem Resource | XML / JSON
ValueSet Resource | XML / JSON

This value set is used in the following places:

* This value set is the designated 'entire code system' value set for v2 Source of Comment

4.2.13.105.1 Code System Content

Source of Comment

Code | Description | Deutsch (German) | Nederlands (Dutch) | Comment | Version
L | Ancillary (filler) department is source of comment | Leistungsstelle | Andere (filler) afdeling is bron van opmerking | | from v2.1
O | Other system is source of comment | Andere Stelle | Ander systeem is bron van opmerking | | added v2.2
P | Orderer (placer) is source of comment | Auftraggeber / auftraggebende Stelle | Aanvrager (placer) is bron van opmerking | | from v2.1

4.2.13.106 HL7 Version 2 Table 0106

URL: https://hl7.org/fhir/STU3/v2/0106/index.html

This page is part of the FHIR Specification (v3.0.2: STU 3). The current version which supercedes this version is 4.0.1. For a full list of available versions, see the Directory of published versions

Vocabulary Work Group | Maturity Level: N/A | External | Use Context: Any

This is a table defined as part of HL7 v2 . Related FHIR content: v2 Query/response format code.

Summary

Name: | v2 Query/response format code
Definition: | FHIR Value set/code system definition for HL7 v2 table 0106 (Query/response format code)
Code System URL: | http://hl7.org/fhir/v2/0106
Value Set URL: | http://hl7.org/fhir/ValueSet/v2-0106
OID: | ??
CodeSystem Resource | XML / JSON
ValueSet Resource | XML / JSON

This value set is used in the following places:

* This value set is the designated 'entire code system' value set for v2 Query/response format code

4.2.13.106.1 Code System Content

Query/response format code

Code | Description | Deutsch (German) | Nederlands (Dutch) | Comment | Version
D | Response is in display format | Antwort im Anzeige-Format | Antwoord is in weergavestructuur | deprecated | added v2.2, removed after v2.6
R | Response is in record-oriented format | Antwort im datensatzorientierten Format | Antwoord is in record-georiënteerde structuur | deprecated | from v2.1, removed after v2.6
T | Response is in tabular format | | Antwoord is in tabelstructuur | deprecated | added v2.3, removed after v2.6

4.2.13.107 HL7 Version 2 Table 0107

URL: https://hl7.org/fhir/STU3/v2/0107/index.html

This page is part of the FHIR Specification (v3.0.2: STU 3). The current version which supercedes this version is 4.0.1. For a full list of available versions, see the Directory of published versions

Vocabulary Work Group | Maturity Level: N/A | External | Use Context: Any

This is a table defined as part of HL7 v2 . Related FHIR content: v2 Deferred response type.

Summary

Name: | v2 Deferred response type
Definition: | FHIR Value set/code system definition for HL7 v2 table 0107 (Deferred response type)
Code System URL: | http://hl7.org/fhir/v2/0107
Value Set URL: | http://hl7.org/fhir/ValueSet/v2-0107
OID: | ??
CodeSystem Resource | XML / JSON
ValueSet Resource | XML / JSON

This value set is used in the following places:

* This value set is the designated 'entire code system' value set for v2 Deferred response type

4.2.13.107.1 Code System Content

Deferred response type

Code | Description | Deutsch (German) | Nederlands (Dutch) | Comment | Version
B | Before the Date/Time specified | Vor dem angegebenen Zeitpunkt | Voor de opgegeven datum/tijd | deprecated | from v2.1, removed after v2.6
L | Later than the Date/Time specified | Nach dem angegebenen Zeitpunkt | Na de opgegeven datum/tijd | deprecated | from v2.1, removed after v2.6

4.2.13.108 HL7 Version 2 Table 0108

URL: https://hl7.org/fhir/STU3/v2/0108/index.html

This page is part of the FHIR Specification (v3.0.2: STU 3). The current version which supercedes this version is 4.0.1. For a full list of available versions, see the Directory of published versions

Vocabulary Work Group | Maturity Level: N/A | External | Use Context: Any

This is a table defined as part of HL7 v2 . Related FHIR content: v2 Query results level.

Summary

Name: | v2 Query results level
Definition: | FHIR Value set/code system definition for HL7 v2 table 0108 (Query results level)
Code System URL: | http://hl7.org/fhir/v2/0108
Value Set URL: | http://hl7.org/fhir/ValueSet/v2-0108
OID: | ??
CodeSystem Resource | XML / JSON
ValueSet Resource | XML / JSON

This value set is used in the following places:

* This value set is the designated 'entire code system' value set for v2 Query results level

4.2.13.108.1 Code System Content

Query results level

Code | Description | Deutsch (German) | Nederlands (Dutch) | Comment | Version
O | Order plus order status | Auftrag und Auftragsstatus | Aanvraag plus aanvragstatus | deprecated | from v2.1, removed after v2.6
R | Results without bulk text | Ergebnisse / Befunde ohne umfänglichen Text | Resultaten zonder bulktest | deprecated | from v2.1, removed after v2.6
S | Status only | nur Statusinformation | Alleen status | deprecated | from v2.1, removed after v2.6
T | Full results | Komplette Ergebnisse / Befunde | Volledige resultaten | deprecated | from v2.1, removed after v2.6

4.2.13.109 HL7 Version 2 Table 0109

URL: https://hl7.org/fhir/STU3/v2/0109/index.html

This page is part of the FHIR Specification (v3.0.2: STU 3). The current version which supercedes this version is 4.0.1. For a full list of available versions, see the Directory of published versions

Vocabulary Work Group | Maturity Level: N/A | External | Use Context: Any

This is a table defined as part of HL7 v2 . Related FHIR content: v2 Report priority.

Summary

Name: | v2 Report priority
Definition: | FHIR Value set/code system definition for HL7 v2 table 0109 (Report priority)
Code System URL: | http://hl7.org/fhir/v2/0109
Value Set URL: | http://hl7.org/fhir/ValueSet/v2-0109
OID: | ??
CodeSystem Resource | XML / JSON
ValueSet Resource | XML / JSON

This value set is used in the following places:

* This value set is the designated 'entire code system' value set for v2 Report priority

4.2.13.109.1 Code System Content

Report priority

Code | Description | Deutsch (German) | Nederlands (Dutch) | Comment | Version
R | Routine | Routine | Normaal | deprecated | from v2.1, removed after v2.6
S | Stat | Eilig | Stat | deprecated | from v2.1, removed after v2.6

4.2.13.116 HL7 Version 2 Table 0116

URL: https://hl7.org/fhir/STU3/v2/0116/index.html

This page is part of the FHIR Specification (v3.0.2: STU 3). The current version which supercedes this version is 4.0.1. For a full list of available versions, see the Directory of published versions

Vocabulary Work Group | Maturity Level: N/A | External | Use Context: Any

This is a table defined as part of HL7 v2 . Related FHIR content: v2 Bed Status.

Summary

Name: | v2 Bed Status
Definition: | FHIR Value set/code system definition for HL7 v2 table 0116 (Bed Status)
Code System URL: | http://hl7.org/fhir/v2/0116
Value Set URL: | http://hl7.org/fhir/ValueSet/v2-0116
OID: | ??
CodeSystem Resource | XML / JSON
ValueSet Resource | XML / JSON

This value set is used in the following places:

* This value set is the designated 'entire code system' value set for v2 Bed Status

* Location.operationalStatus (Preferred)

4.2.13.116.1 Code System Content

Bed Status

Code | Description | Deutsch (German) | Nederlands (Dutch) | Comment | Version
C | Closed | Nicht verfügbar | Gesloten | | from v2.1
H | Housekeeping | Reinigung | Onderhoud | | from v2.1
I | Isolated | Isoliert | In isolatie | | added v2.2
K | Contaminated | Kontaminiert | Besmet | | added v2.2
O | Occupied | belegt | Bezet | | from v2.1
U | Unoccupied | libre | Niet-bezet | | from v2.1

4.2.13.119 HL7 Version 2 Table 0119

URL: https://hl7.org/fhir/STU3/v2/0119/index.html

This page is part of the FHIR Specification (v3.0.2: STU 3). The current version which supercedes this version is 4.0.1. For a full list of available versions, see the Directory of published versions

Vocabulary Work Group | Maturity Level: N/A | External | Use Context: Any

This is a table defined as part of HL7 v2 . Related FHIR content: v2 Order Control Codes.

Summary

Name: | v2 Order Control Codes
Definition: | FHIR Value set/code system definition for HL7 v2 table 0119 (Order Control Codes)
Code System URL: | http://hl7.org/fhir/v2/0119
Value Set URL: | http://hl7.org/fhir/ValueSet/v2-0119
OID: | ??
CodeSystem Resource | XML / JSON
ValueSet Resource | XML / JSON

This value set is used in the following places:

* This value set is the designated 'entire code system' value set for v2 Order Control Codes

4.2.13.119.1 Code System Content

Order Control Codes

Code | Description | Deutsch (German) | Nederlands (Dutch) | Comment | Version
AF | Order/service refill request approval | | Aanvraag/service herhaling verzoek goedgekeurd | Placer Applications.<p>AF is a response to RF where the placer authorizing a refill or quantity of refills. | added v2.3
CA | Cancel order/service request | Auftrag stornieren | Annuleer aanvraag/service verzoek | Placer or Filler Applications.<p>A cancellation is a request by the placer for the filler, or the filler to the placer, not to do a previously ordered service. Confirmation of the cancellation request is provided by the filler or placer, e.g. a message w | from v2.1
CH | Child order/service | nachgeordneter Auftrag | Onderliggende/deel aanvraag/service | Placer or Filler Applications.<p>Used in conjunction with the PA - Parent order control code. Refer to PA order control code for discussion. | from v2.1
CN | Combined result | Kumulatives Ergebnis (zu mehreren Aufträgen) | Gecombineerd resultaat | Filler Applications.<p>The combined result code provides a mechanism to transmit results that are associated with two or more orders. This situation occurs commonly in radiology reports when the radiologist dictates a single report for two or more exams r | from v2.1
CP | Cancel process step | | Annuleer processtap | Filler Applications.<p>The control code CP - Cancel process step should be used in the ORC-1 for communication Filler-to-Filler, e.g. LIS-to-Analyzer, to differentiate from code CA (Placer-to-Filler).<p>The Filler should response with an acceptance of th | added v2.8
CR | Canceled as requested | Auftrag anweisungsgemäß storniert | Geannuleerd zoals gevraagd | Filler or Placer Applications.<p>A response by the filler or placer application that a request to cancel (CA by the placer application) was performed successfully. | added v2.2
DC | Discontinue order/service request | Auftragsausführung abbrechen | Breek aanvraag/service verzoek af | Placer or Filler Applications.<p>A request by the placer for the filler, or the filler to the placer, to discontinue a previously requested service. The differentiation between discontinue and cancel is that discontinue effects the order/service and all | from v2.1
DE | Data errors | Datenfehler | Gegevens fouten | Placer or Filler Applications. | from v2.1
DF | Order/service refill request denied | | Aanvraag/service herhaal verzoek afgekeurd | Placer Applications.<p>In response to a Filler application requesting refill authorization (RF), DF indicates that the placer does not authorize refills for the order. ORC-16 Order Control Code reason may be used to indicate the reason for the request den | added v2.3

DR | Discontinued as requested | Auftragsausführung anweisungsgemäß abgebrochen | Afgebroken zoals gevraagd | Filler or Placer Applications.<p>The filler or placer, in response to a request to discontinue (DC from the placer or filler application), has discontinued the order/service. | from v2.1

FU | Order/service refilled, unsolicited | | Aanvraag/service herhaald, ongevraagd | Filler Applications.<p>FU notifies the placer that the filler issued a refill for the order at the patient's request. | added v2.3

HD | Hold order request | Auftragsbearbeitung aussetzen | Houd aanvraag aan verzoek | Placer Applications.<p>Typical responses include, but are not limited to, CR - Cancelled as requested, UC - Unable to Cancel. | from v2.1

HR | On hold as requested | Auftragsbearbeitung anweisungsgemäß ausgesetzt | Aangehouden zoals gevraagd | Filler Applications. | from v2.1

LI | Link order/service to patient care problem or goal | | Koppel aanvraag/service aan patiënt zorgprobleem of doel | Placer or Filler Applications.<p>Refer to Chapter 12 Patient Care for complete discussion. | added v2.3.1

MC | Miscellaneous Charge - not associated with an order | | Overige charge - niet gekoppeld aan een aanvraag | applies to DFT^P03^DFT_P03 and DFT^P11^DFT_P11 | added v2.6

NA | Number assigned | Nummer zugewiesen | Nummer toegekend | Placer Applications.<p>There are three circumstances that involve requesting an order number (ORC-2-placer order number or ORC-3-filler order number):<p>(1) When the filler application needs to request an ORC-3-filler order number from a centralized appli | from v2.1

NW | New order/service | Neuer Auftrag | Nieuwe aanvraag/service | Placer Applications.<p>See comments for NA - Number Assigned. | from v2.1

OC | Order/service canceled | Auftrag storniert | Aanvraag/service geannuleerd | Filler Applications. | added v2.2

OD | Order/service discontinued | Auftragsausführung abgebrochen | Aanvraag/service afgebroken | Filler Applications. | from v2.1

OE | Order/service released | | Aanvraag/service vrijgegeven | Filler Applications. | added v2.3

OF | Order/service refilled as requested | | Aanvraag/service herhaald zoals gevraagd | Filler Applications.<p>OF directly responds to the placer system's request for a refill. | added v2.3

OH | Order/service held | Auftragsbearbeitung ausgesetzt | Aanvraag/service aangehouden | Filler Applications. | added v2.2

OK | Order/service accepted & OK | Auftrag akzeptiert | Aanvraag/service geaccepteerd en OK | Filler Applications.<p>See comments for NA - Number Assigned. | from v2.1

OP | Notification of order for outside dispense | | Notificatie van aanvraag voor verstrekking door derde | Placer Applications.<p>These order control codes are used to communicate an order between systems where the order is intended for informational purposes. For example, an order that will be performed by a vendor outside the enterprise of communicating syst | added v2.5

OR | Released as requested | Auftragsbearbeitung anweisungsgemäß wiederaufgenommen | Vrijgegeven zoals gevraagd | Filler Applications. | from v2.1

PA | Parent order/service | Hauptauftrag | Bovenliggende aanvraag/service | Filler Applications.<p>The parent (PA) and child (CH) order control codes allow the spawning of "child" orders from a "parent" order without changing the parent (original order). One or more ORC segments with an ORC-1-order control value of PA are followe | from v2.1

PR | Previous Results with new order/service | | Vorige resultaten met nieuwe aanvraag/service | Placer Applications.<p>PR indicates that this ORC is part of an ORU structure containing previous observation, which is embedded in the order.<p>At least two main use cases require that the complete results of the previous observations be transmitted with | added v2.4

PY | Notification of replacement order for outside dispense | | Notificatie van vervangende aanvraag voor verstrekking door derde | Placer Applications.<p>See comments for OP - Notification of order for outside dispense. | added v2.5

RE | Observations/Performed Service to follow | Untersuchungsergebnisse folgen (in späteren Segmenten dieser Nachricht) | Observaties/uitgevoerde server volgen | Placer or Filler Applications.<p>The observations-to-follow code is used to transmit patient-specific information with an order. An order detail segment (e.g. OBR) can be followed by one or more observation segments (OBX). Any observation that can be tra | from v2.1

RF | Refill order/service request | | Herhaal aanvraag/service verzoek | Placer or Filler Applications.<p>RF accommodates requests by either the filler or the placer. The filler may be requesting refill authorization from the placer. A placer system may be requesting a refill to be done by the filler system.<p>Typical response | added v2.3

RL | Release previous hold | Auftragsberabeitung wiederaufnehmen | Geef vorige vastgehouden vrij | Placer Applications. | added v2.2

RO | Replacement order | Ersatzauftrag | Vervangende aanvraag | Placer or Filler Applications.<p>A replacement is the substitution of one or more orders for one or more previously ordered services.<p>The replaced orders are treated as though they were canceled. If and when an ordered service can be replaced are local | from v2.1

RP | Order/service replace request | Auftrag ersetzen | Aanvraag/service vervanging verzoek | Placer Applications.<p>A replacement is the substitution of one or more orders for one or more previously ordered services. See comment 1 on RO - Replacement Order for further discussion.<p>The order replace request code permits the order filler to replac | from v2.1

RQ | Replaced as requested | Auftrag anweisungsgemäß ersetzt | Vervangen zoals gevraagd | Filler Applications.<p>A replacement is the substitution of one or more orders for one or more previously ordered services. See comment 1 on RO - Replacement Order for further discussion.<p>The order replace request code permits the order filler to replac | added v2.2

RR | Request received | Anforderung erhalten (veraltet) | Verzoek ontvangen | Placer or Filler Applications.<p>Left in for backward compatibility. In the current version it is equivalent to an accept acknowledgment. The request-received code indicates that an order message has been received and will be processed later. The order ha | from v2.1

RU | Replaced unsolicited | Auftrag ersetzt (ohne Anweisung) | Vervangen ongevraagd | Filler Applications.<p>A replacement is the substitution of one or more orders for one or more previously ordered services. See comment 1 on RO - Replacement Order for further discussion.<p>The unsolicited replacement code permits the filler application t | from v2.1

SC | Status changed | Statusänderung | Status gewijzigd | Placer or Filler Applications. | added v2.2

SN | Send order/service number | Auftrags- bzw. Bearbeitungsnummer zuweisen / übermitteln | Stuur aanvraag/service nummer | Placer Applications.<p>See comments for NA - Number Assigned. | from v2.1

SR | Response to send order/service status request | Auftragsstatus (Antwort) | Antwoord op stuur aanvraag/service status verzoek | Filler Applications. | added v2.2

SS | Send order/service status request | Auftragsstatus senden | Stuur aanvraag/service status verzoek | Placer Applications. | from v2.1

UA | Unable to accept order/service | | Kon aanvraag/service niet accepteren | Filler Applications.<p>An unable-to-accept code is used when a new order cannot be accepted by the filler. Possible reasons include requesting a prescription for a drug which the patient is allergic to or for an order which requires certain equipment reso | added v2.3

UC | Unable to cancel | Auftragsstornierung nicht möglich | Kon niet annuleren | Filler or Placer Applications.<p>An unable-to-cancel code is used when the ordered service is at a point that it cannot be canceled by the placer or filler or when local rules prevent cancellation by the filler. The use of this code is dependent on the va | added v2.2

UD | Unable to discontinue | Abbrechen nicht möglich | Kon niet afbreken | Filler or Placer Applications.<p>An unable-to-discontinue code is used when the ordered service is at a point that it cannot be discontinued by the placer or filler or when local rules prevent discontinuance by the filler. The use of this code is dependen | from v2.1

UF | Unable to refill | | Kon niet herhalen | Filler Applications.<p>Negative response to RF Refill order/service request, indicating that the receiving application was not able to complete the refill request. | added v2.3
UH | Unable to put on hold | Aussetzen nicht möglich | Kon niet aanhouden | Filler Applications. | from v2.1
UM | Unable to replace | Ersetzen nicht möglich | Kon niet vervangen | Filler Applications. | added v2.2
UN | Unlink order/service from patient care problem or goal | | Ontkoppel aanvraag/service van patiënt zorgprobleem of doel | Placer or Filler Applications.<p>Refer to Chapter 12 Patient Care for complete discussion. | added v2.3.1
UR | Unable to release | Wiederaufnahme nicht möglich | Kon niet vrijgeven | Filler Applications. | from v2.1
UX | Unable to change | Änderung nicht möglich | Kon niet wijzigen | Filler Applications. | from v2.1
XO | Change order/service request | Auftrag ändern | Wijzig aanvraag/service verzoek | Placer Applications. | added v2.2
XR | Changed as requested | Auftrag anweisungsgemäß geändert | Gewijzigd zoals gevraagd | Filler Applications. | from v2.1
XX | Order/service changed, unsol. | Auftrag geändert (ohne Anweisung) | Order/service gewijzigd, ongevraagd | Filler Applications. | from v2.1

4.2.13.121 HL7 Version 2 Table 0121

URL: https://hl7.org/fhir/STU3/v2/0121/index.html

This page is part of the FHIR Specification (v3.0.2: STU 3). The current version which supercedes this version is 4.0.1. For a full list of available versions, see the Directory of published versions

Vocabulary Work Group | Maturity Level: N/A | External | Use Context: Any

This is a table defined as part of HL7 v2 . Related FHIR content: v2 Response Flag.

Summary

Name: | v2 Response Flag
Definition: | FHIR Value set/code system definition for HL7 v2 table 0121 (Response Flag)
Code System URL: | http://hl7.org/fhir/v2/0121
Value Set URL: | http://hl7.org/fhir/ValueSet/v2-0121
OID: | ??
CodeSystem Resource | XML / JSON
ValueSet Resource | XML / JSON

This value set is used in the following places:

* This value set is the designated 'entire code system' value set for v2 Response Flag

4.2.13.121.1 Code System Content

Response Flag

Code | Description | Deutsch (German) | Nederlands (Dutch) | Comment | Version
D | Same as R, also other associated segments | Wie R, zusätzlich Detail-Segmente (OBR usw.) von nachgeordneten und Ersatzaufträ | Zelfde als R, ook andere gekoppelde segmenten | | from v2.1
E | Report exceptions only | Nur OK oder Fehlercode nach Auftragsprüfung / -bearbeitung | Meld alleen uitzonderingen. | | from v2.1
F | Same as D, plus confirmations explicitly | Wie D, zusätzlich ausdrückliche Bestätigungen | Zelfde als D, plus expliciete bevestigingen. | | from v2.1
N | Only the MSA segment is returned | Nur Eingangsbestätigung | Alleen het MSA-segment wordt geretourneerd. | | from v2.1
R | Same as E, also Replacement and Parent-Child | Wie E, zusätzlich ORC-Segmente von nachgeordneten und Ersatzaufträgen | Zelfde als E, ook Vervanging en Parent-Child | | from v2.1

4.2.13.122 HL7 Version 2 Table 0122

URL: https://hl7.org/fhir/STU3/v2/0122/index.html

This page is part of the FHIR Specification (v3.0.2: STU 3). The current version which supercedes this version is 4.0.1. For a full list of available versions, see the Directory of published versions

Vocabulary Work Group | Maturity Level: N/A | External | Use Context: Any

This is a table defined as part of HL7 v2 . Related FHIR content: v2 Charge Type.

Summary

Name: | v2 Charge Type
Definition: | FHIR Value set/code system definition for HL7 v2 table 0122 (Charge Type)
Code System URL: | http://hl7.org/fhir/v2/0122
Value Set URL: | http://hl7.org/fhir/ValueSet/v2-0122
OID: | ??
CodeSystem Resource | XML / JSON
ValueSet Resource | XML / JSON

This value set is used in the following places:

* This value set is the designated 'entire code system' value set for v2 Charge Type

4.2.13.122.1 Code System Content

Charge Type

Code | Description | Deutsch (German) | Nederlands (Dutch) | Comment | Version
CH | Charge | Rechnung | Belasten | | from v2.1
CO | Contract | Vertrag | Contract | | from v2.1
CR | Credit | Kredit | Krediet | | from v2.1

DP | Department | Abteilung | Afdeling | | from v2.1
GR | Grant | Zuschuß | Toelage | | from v2.1
NC | No Charge | Keine Rechnung | Niet belasten | | from v2.1
PC | Professional | Berufsgenossenschaft | Professional | | from v2.1
RS | Research | Forschung | Research | | from v2.1

4.2.13.123 HL7 Version 2 Table 0123

URL: https://hl7.org/fhir/STU3/v2/0123/index.html

This page is part of the FHIR Specification (v3.0.2: STU 3). The current version which supercedes this version is 4.0.1. For a full list of available versions, see the Directory of published versions

Vocabulary Work Group | Maturity Level: N/A | External | Use Context: Any

This is a table defined as part of HL7 v2 . Related FHIR content: v2 Result Status.

Summary

Name: | v2 Result Status
Definition: | FHIR Value set/code system definition for HL7 v2 table 0123 (Result Status)
Code System URL: | http://hl7.org/fhir/v2/0123
Value Set URL: | http://hl7.org/fhir/ValueSet/v2-0123
OID: | ??
CodeSystem Resource | XML / JSON
ValueSet Resource | XML / JSON

This value set is used in the following places:

* This value set is the designated 'entire code system' value set for v2 Result Status

4.2.13.123.1 Code System Content

Result Status

Code | Description | Deutsch (German) | Nederlands (Dutch) | Comment | Version
A | Some, but not all, results available | einige, aber nicht alle Ergebnisse verfügbar | Sommige maar nog niet alle resultaten beschikbaar | | added v2.3
C | Correction to results | Ergebniskorrektur | Gecorrigeerde resultaten | | from v2.1
F | Final results; results stored and verified. Can only be changed with a corrected result. | Endergebnis - Auftrag erledigt, Ergebnisse validiert | Definitieve resultaten; resultaten opgeslagen en geverifieerd. Kunnen alleen nog worden gewijzigd door een gecorrigeerd resultaat. | | from v2.1
I | No results available; specimen received, procedure incomplete | Keine Ergebnisse - Probe liegt vor, Untersuchung unvollständig | Geen resultaat beschikbaar; monster ontvangen, procedure incompleet | | from v2.1
O | Order received; specimen not yet received | Auftrag erhalten - Probe steht noch aus | Aanvraag ontvangen; monster nog niet gearriveerd | | added v2.2
P | Preliminary: A verified early result is available, final results not yet obtained | Vorläufig - Validiertes Zwischenergebnis liegt vor, aber noch keine endgültigen | Voorlopig: er is een geverifieerd eerste resultaat beschikbaar, definitieve resultaten nog niet beschikbaar | | from v2.1
R | Results stored; not yet verified | Ergebnisse gespeichert, aber noch nicht validiert | Resultaten opgeslagen; nog niet geverifieerd | | from v2.1
S | No results available; procedure scheduled, but not done | Keine Ergebnisse - Untersuchung eingeplant, aber noch nicht durchgeführt | Geen resultaat beschikbaar; procedure gepland maar nog niet uitgevoerd | | from v2.1
X | No results available; Order canceled. | Keine Ergebnisse - Auftrag storniert | Geen resultaat beschikbaar; aanvraag geannuleerd. | | added v2.2
Y | No order on record for this test. (Used only on queries) | Kein Auftrag zu dieser Untersuchung | Geen aanvraag opgeslagen voor deze test. (Alleen van toepassing bij queries) | | from v2.1
Z | No record of this patient. (Used only on queries) | Keine Daten über diesen Patienten | Patiënt niet bekend. (Alleen van toepassing bij queries) | | from v2.1

4.2.13.124 HL7 Version 2 Table 0124

URL: https://hl7.org/fhir/STU3/v2/0124/index.html

This page is part of the FHIR Specification (v3.0.2: STU 3). The current version which supercedes this version is 4.0.1. For a full list of available versions, see the Directory of published versions

Vocabulary Work Group | Maturity Level: N/A | External | Use Context: Any

This is a table defined as part of HL7 v2 . Related FHIR content: v2 Transportation Mode.

Summary

Name: | v2 Transportation Mode
Definition: | FHIR Value set/code system definition for HL7 v2 table 0124 (Transportation Mode)
Code System URL: | http://hl7.org/fhir/v2/0124
Value Set URL: | http://hl7.org/fhir/ValueSet/v2-0124
OID: | ??
CodeSystem Resource | XML / JSON
ValueSet Resource | XML / JSON

This value set is used in the following places:

* This value set is the designated 'entire code system' value set for v2 Transportation Mode

4.2.13.124.1 Code System Content

Transportation Mode

Code | Description | Deutsch (German) | Nederlands (Dutch) | Comment | Version
CART | Cart - patient travels on cart or gurney | Patient wird auf Trage transportiert | Wagentje - patiënt reist per karretje of ziekenhuisbed | | from v2.1
PORT | The examining device goes to patient's location | Untersuchung am Krankenbett | Het onderzoeksapparaat gaat naar de patiëntlocatie | | from v2.1
WALK | Patient walks to diagnostic service | Patient geht zu Fuß zum Funktionsbereich | Patiënt loopt naar diagnostische service | | from v2.1
WHLC | Wheelchair | Rollstuhl | Rolstoel | | from v2.1

4.2.13.125 HL7 Version 2 Table 0125

URL: https://hl7.org/fhir/STU3/v2/0125/index.html

This page is part of the FHIR Specification (v3.0.2: STU 3). The current version which supercedes this version is 4.0.1. For a full list of available versions, see the Directory of published versions

Vocabulary Work Group | Maturity Level: N/A | External | Use Context: Any

This is a table defined as part of HL7 v2 . Related FHIR content: v2 Value Type.

Summary

Name: | v2 Value Type
Definition: | FHIR Value set/code system definition for HL7 v2 table 0125 (Value Type)
Value Set URL: | http://hl7.org/fhir/ValueSet/v2-0125
OID: | ??
ValueSet Resource | XML / JSON

This value set is not currently used

4.2.13.125.1 Logical Definition

Value Type

Code | System | Description | Comment | Version
AD | http://hl7.org/fhir/v2/0440 | Address | Retained for backward compatibility as of v2.6. | added v2.1, removed after v2.8.1
AUI | http://hl7.org/fhir/v2/0440 | Authorization information | | added v2.8.2
CCD | http://hl7.org/fhir/v2/0440 | Charge code and date | | added v2.8.2
CCP | http://hl7.org/fhir/v2/0440 | Channel calibration parameters | | added v2.8.2
CD | http://hl7.org/fhir/v2/0440 | Channel definition | | added v2.8.2
CE | http://hl7.org/fhir/v2/0440 | Coded Entry | | added v2.2, removed after v2.5.1
CF | http://hl7.org/fhir/v2/0440 | Coded element with formatted values | Withdrawn from this table only as of v2.7. | added v2.2
CK | http://hl7.org/fhir/v2/0440 | Composite ID With Check Digit | Withdrawn as of v2.5. | added v2.1, removed after v2.8.1
CM | http://hl7.org/fhir/v2/0440 | Composite | | added v2.2, removed after v2.2
CN | http://hl7.org/fhir/v2/0440 | Composite ID And Name | Withdrawn as of v2.5. | added v2.2, removed after v2.8.1
CNE | http://hl7.org/fhir/v2/0440 | Coded with no exceptions | | added v2.7
CNN | http://hl7.org/fhir/v2/0440 | Composite ID number and name simplified | | added v2.8.2
CP | http://hl7.org/fhir/v2/0440 | Composite price | Withdrawn from this table only as of v2.7. | added v2.3
CQ | http://hl7.org/fhir/v2/0440 | Composite quantity with units | | added v2.2, removed after v2.2
CSU | http://hl7.org/fhir/v2/0440 | Channel sensitivity and units | | added v2.8.2
CWE | http://hl7.org/fhir/v2/0440 | Coded with exceptions | | added v2.6
CX | http://hl7.org/fhir/v2/0440 | Extended composite ID with check digit | | added v2.3
DDI | http://hl7.org/fhir/v2/0440 | Daily deductible information | | added v2.8.2
DIN | http://hl7.org/fhir/v2/0440 | Date and institution name | | added v2.8.2
DLD | http://hl7.org/fhir/v2/0440 | Discharge to location and date | | added v2.8.2
DLN | http://hl7.org/fhir/v2/0440 | Driver's license number | | added v2.8.2
DLT | http://hl7.org/fhir/v2/0440 | Delta | | added v2.8.2
DR | http://hl7.org/fhir/v2/0440 | Date/time range | | added v2.7
DT | http://hl7.org/fhir/v2/0440 | Date | | added v2.2
DTM | http://hl7.org/fhir/v2/0440 | Date/time | | added v2.6
DTN | http://hl7.org/fhir/v2/0440 | Day type and number | | added v2.8.2
ED | http://hl7.org/fhir/v2/0440 | Encapsulated data | | added v2.3
EI | http://hl7.org/fhir/v2/0440 | Entity identifier | | added v2.8.2
EIP | http://hl7.org/fhir/v2/0440 | Entity identifier pair | | added v2.8.2
ERL | http://hl7.org/fhir/v2/0440 | Error location | | added v2.8.2
FC | http://hl7.org/fhir/v2/0440 | Financial class | | added v2.8.2
FT | http://hl7.org/fhir/v2/0440 | Formatted text | | added v2.1
GTS | http://hl7.org/fhir/v2/0440 | General timing specification | | added v2.8.2
HD | http://hl7.org/fhir/v2/0440 | Hierarchic designator | | added v2.8.2
ICD | http://hl7.org/fhir/v2/0440 | Insurance certification definition | | added v2.8.2
ID | http://hl7.org/fhir/v2/0440 | Coded Value for HL7 Defined Tables | | added v2.2, removed after v2.8.1
IS | http://hl7.org/fhir/v2/0440 | Coded value for user-defined tables | | added v2.7
JCC | http://hl7.org/fhir/v2/0440 | Job code/class | | added v2.8.2
LA1 | http://hl7.org/fhir/v2/0440 | Location with address variation 1 | | added v2.8.2
LA2 | http://hl7.org/fhir/v2/0440 | Location with address variation 2 | | added v2.8.2
MA | http://hl7.org/fhir/v2/0440 | Multiplexed array | | added v2.7
MO | http://hl7.org/fhir/v2/0440 | Money | Withdrawn from this table only as of v2.7. | added v2.2

MOC | http://hl7.org/fhir/v2/0440 | Money and charge code | | added v2.8.2
MOP | http://hl7.org/fhir/v2/0440 | Money or percentage | | added v2.8.2
MSG | http://hl7.org/fhir/v2/0440 | Message type | | added v2.8.2
NA | http://hl7.org/fhir/v2/0440 | Numeric array | | added v2.7
NDL | http://hl7.org/fhir/v2/0440 | Name with date and location | | added v2.8.2
NM | http://hl7.org/fhir/v2/0440 | Numeric | | added v2.2
NR | http://hl7.org/fhir/v2/0440 | Numeric range | | added v2.8.2
OCD | http://hl7.org/fhir/v2/0440 | Occurrence code and date | | added v2.8.2
OSP | http://hl7.org/fhir/v2/0440 | Occurrence span code and date | | added v2.8.2
PIP | http://hl7.org/fhir/v2/0440 | Practitioner institutional privileges | | added v2.8.2
PL | http://hl7.org/fhir/v2/0440 | Person location | | added v2.8.2
PLN | http://hl7.org/fhir/v2/0440 | Practitioner license or other ID number | | added v2.8.2
PN | http://hl7.org/fhir/v2/0440 | Person Name | Withdrawn as of v2.5. | added v2.1, removed after v2.8.1
PPN | http://hl7.org/fhir/v2/0440 | Performing person time stamp | | added v2.8.2
PRL | http://hl7.org/fhir/v2/0440 | Parent result link | | added v2.8.2
PT | http://hl7.org/fhir/v2/0440 | Processing type | | added v2.8.2
PTA | http://hl7.org/fhir/v2/0440 | Policy type and amount | | added v2.8.2
QIP | http://hl7.org/fhir/v2/0440 | Query input parameter list | | added v2.8.2
QSC | http://hl7.org/fhir/v2/0440 | Query selection criteria | | added v2.8.2
RCD | http://hl7.org/fhir/v2/0440 | Row column definition | | added v2.8.2
RFR | http://hl7.org/fhir/v2/0440 | Reference range | | added v2.8.2
RI | http://hl7.org/fhir/v2/0440 | Repeat interval | | added v2.8.2
RMC | http://hl7.org/fhir/v2/0440 | Room coverage | | added v2.8.2
RP | http://hl7.org/fhir/v2/0440 | Reference pointer | | added v2.2
RPT | http://hl7.org/fhir/v2/0440 | Repeat pattern | | added v2.8.2
SCV | http://hl7.org/fhir/v2/0440 | Scheduling class value pair | | added v2.8.2
SI | http://hl7.org/fhir/v2/0440 | Sequence ID | | added v2.2, removed after v2.2
SN | http://hl7.org/fhir/v2/0440 | Structured numeric | | added v2.3
SNM | http://hl7.org/fhir/v2/0440 | String of telephone number digits | | added v2.8.2
SPD | http://hl7.org/fhir/v2/0440 | Specialty description | | added v2.8.2
SRT | http://hl7.org/fhir/v2/0440 | Sort order | | added v2.8.2
ST | http://hl7.org/fhir/v2/0440 | String data | | added v2.1
TM | http://hl7.org/fhir/v2/0440 | Time | | added v2.1
TN | http://hl7.org/fhir/v2/0440 | Telephone Number | Withdrawn as of v2.5. | added v2.2, removed after v2.8.1
TQ | http://hl7.org/fhir/v2/0440 | Timing / quantity | | added v2.2, removed after v2.2
TS | http://hl7.org/fhir/v2/0440 | Time Stamp (Date & Time) | | added v2.1, removed after v2.5.1
TX | http://hl7.org/fhir/v2/0440 | Text data | | added v2.1
UVC | http://hl7.org/fhir/v2/0440 | UB value code and amount | | added v2.8.2
VH | http://hl7.org/fhir/v2/0440 | Visiting hours | | added v2.8.2
VID | http://hl7.org/fhir/v2/0440 | Version identifier | | added v2.8.2
VR | http://hl7.org/fhir/v2/0440 | Value range | | added v2.8.2
WVI | http://hl7.org/fhir/v2/0440 | Channel Identifier | | added v2.8.2
WVS | http://hl7.org/fhir/v2/0440 | Waveform source | | added v2.8.2
XAD | http://hl7.org/fhir/v2/0440 | Extended address | Withdrawn from this table only as of v2.7. | added v2.3
XCN | http://hl7.org/fhir/v2/0440 | Extended composite ID number and name for persons | Withdrawn from this table only as of v2.7. | added v2.3
XON | http://hl7.org/fhir/v2/0440 | Extended composite name and ID number for organizations | Withdrawn from this table only as of v2.7. | added v2.3
XPN | http://hl7.org/fhir/v2/0440 | Extended person name | Withdrawn from this table only as of v2.7. | added v2.3
XTN | http://hl7.org/fhir/v2/0440 | Extended telecommunications number | Withdrawn from this table only as of v2.7. | added v2.3

4.2.13.126 HL7 Version 2 Table 0126

URL: https://hl7.org/fhir/STU3/v2/0126/index.html

This page is part of the FHIR Specification (v3.0.2: STU 3). The current version which supercedes this version is 4.0.1. For a full list of available versions, see the Directory of published versions

Vocabulary Work Group | Maturity Level: N/A | External | Use Context: Any

This is a table defined as part of HL7 v2 . Related FHIR content: v2 Quantity Limited Request.

Summary

Name: | v2 Quantity Limited Request
Definition: | FHIR Value set/code system definition for HL7 v2 table 0126 (Quantity Limited Request)
Code System URL: | http://hl7.org/fhir/v2/0126
Value Set URL: | http://hl7.org/fhir/ValueSet/v2-0126
OID: | ??
CodeSystem Resource | XML / JSON
ValueSet Resource | XML / JSON

This value set is used in the following places:

* This value set is the designated 'entire code system' value set for v2 Quantity Limited Request

4.2.13.126.1 Code System Content

Quantity Limited Request

Code | Description | Deutsch (German) | Nederlands (Dutch) | Comment | Version
CH | Characters | Zeichen | Tekens | RSP/RTB/RDY | from v2.1
LI | Lines | Zeilen | Regels | RTB/RDY | from v2.1
PG | Pages | Seiten | Pagina's | RDY | from v2.1
RD | Records | Datensätze | Records | RSP/RTB/RDY | added v2.2
ZO | Locally defined | lokal definiert | Lokaal gedefinieerd | | from v2.1

4.2.13.127 HL7 Version 2 Table 0127

URL: https://hl7.org/fhir/STU3/v2/0127/index.html

This page is part of the FHIR Specification (v3.0.2: STU 3). The current version which supercedes this version is 4.0.1. For a full list of available versions, see the Directory of published versions

Vocabulary Work Group | Maturity Level: N/A | External | Use Context: Any

This is a table defined as part of HL7 v2 . Related FHIR content: v2 Allergen Type.

Summary

Name: | v2 Allergen Type
Definition: | FHIR Value set/code system definition for HL7 v2 table 0127 (Allergen Type)
Code System URL: | http://hl7.org/fhir/v2/0127
Value Set URL: | http://hl7.org/fhir/ValueSet/v2-0127
OID: | ??
CodeSystem Resource | XML / JSON
ValueSet Resource | XML / JSON

This value set is used in the following places:

* This value set is the designated 'entire code system' value set for v2 Allergen Type

4.2.13.127.1 Code System Content

Allergen Type

Code | Description | Deutsch (German) | Nederlands (Dutch) | Comment | Version
AA | Animal Allergy | | Dierenallergie | | added v2.4
DA | Drug allergy | Medikamentenallergie | Medicatieallergie | | added v2.2
EA | Environmental Allergy | | Omgevingsallergie | | added v2.4
FA | Food allergy | Nahrungsmittelallergie | Voedselallergie | | added v2.2
LA | Pollen Allergy | | Pollenallergie | | added v2.4
MA | Miscellaneous allergy | Sonstige Allergie | Overige allergie | | added v2.2
MC | Miscellaneous contraindication | Sonstige Kontraindikation | Overige contraindicatie | | added v2.2
PA | Plant Allergy | | Plantallergie | | added v2.4

4.2.13.128 HL7 Version 2 Table 0128

URL: https://hl7.org/fhir/STU3/v2/0128/index.html

This page is part of the FHIR Specification (v3.0.2: STU 3). The current version which supercedes this version is 4.0.1. For a full list of available versions, see the Directory of published versions

Vocabulary Work Group | Maturity Level: N/A | External | Use Context: Any

This is a table defined as part of HL7 v2 . Related FHIR content: v2 Allergy Severity.

Summary

Name: | v2 Allergy Severity
Definition: | FHIR Value set/code system definition for HL7 v2 table 0128 (Allergy Severity)
Code System URL: | http://hl7.org/fhir/v2/0128
Value Set URL: | http://hl7.org/fhir/ValueSet/v2-0128
OID: | ??
CodeSystem Resource | XML / JSON
ValueSet Resource | XML / JSON

This value set is used in the following places:

* This value set is the designated 'entire code system' value set for v2 Allergy Severity

4.2.13.128.1 Code System Content

Allergy Severity

Code | Description | Deutsch (German) | Nederlands (Dutch) | Comment | Version
MI | Mild | Leicht | Mild | | added v2.2
MO | Moderate | Mittel | Gemiddeld | | added v2.2
SV | Severe | Lebensbedrohlich | Ernstig | | added v2.2
U | Unknown | | Onbekend | | added v2.4

4.2.13.130 HL7 Version 2 Table 0130

URL: https://hl7.org/fhir/STU3/v2/0130/index.html

This page is part of the FHIR Specification (v3.0.2: STU 3). The current version which supercedes this version is 4.0.1. For a full list of available versions, see the Directory of published versions

Vocabulary Work Group | Maturity Level: N/A | External | Use Context: Any

This is a table defined as part of HL7 v2 . Related FHIR content: v2 Visit User Code.

Summary

Name: | v2 Visit User Code
Definition: | FHIR Value set/code system definition for HL7 v2 table 0130 (Visit User Code)
Code System URL: | http://hl7.org/fhir/v2/0130
Value Set URL: | http://hl7.org/fhir/ValueSet/v2-0130
OID: | ??
CodeSystem Resource | XML / JSON
ValueSet Resource | XML / JSON

This value set is used in the following places:

* This value set is the designated 'entire code system' value set for v2 Visit User Code

4.2.13.130.1 Code System Content

Visit User Code

Code | Description | Nederlands (Dutch) | Comment | Version
HO | Home | Thuis | | added v2.4
MO | Mobile Unit | Mobiele eenheid | | added v2.4
PH | Phone | Telefoon | | added v2.4
TE | Teaching | Geeft onderwijs | | added v2.4

4.2.13.131 HL7 Version 2 Table 0131

URL: https://hl7.org/fhir/STU3/v2/0131/index.html

This page is part of the FHIR Specification (v3.0.2: STU 3). The current version which supercedes this version is 4.0.1. For a full list of available versions, see the Directory of published versions

Vocabulary Work Group | Maturity Level: N/A | External | Use Context: Any

This is a table defined as part of HL7 v2 . Related FHIR content: v2 Contact Role.

Summary

Name: | v2 Contact Role
Definition: | FHIR Value set/code system definition for HL7 v2 table 0131 (Contact Role)
Code System URL: | http://hl7.org/fhir/v2/0131
Value Set URL: | http://hl7.org/fhir/ValueSet/v2-0131
OID: | ??
CodeSystem Resource | XML / JSON
ValueSet Resource | XML / JSON

This value set is used in the following places:

* This value set is the designated 'entire code system' value set for v2 Contact Role

* Patient.contact.relationship (Extensible)

4.2.13.131.1 Code System Content

Contact Role

Code | Description | Deutsch (German) | Nederlands (Dutch) | Comment | Version
BP | Billing contact person | Kontaktperson für Abrechnung | Facturatie contactpersoon | deprecated | added v2.3, removed after v2.3
C | Emergency Contact | Ansprechpartner in Notfällen | Contact bij nood | | added v2.5
CP | Contact person | Kontaktperson | Contactpersoon | deprecated | added v2.3, removed after v2.3
E | Employer | Arbeitgeber | Werkgever | | added v2.5
EP | Emergency contact person | Kontaktperson für Notfälle | Contactpersoon bij nood | deprecated | added v2.3, removed after v2.3
F | Federal Agency | Bundesbehörde | Federale overheidsinstelling | | added v2.5
I | Insurance Company | Versicherung | Verzekeraar | | added v2.5
N | Next-of-Kin | Kontaktperson | Familielid | | added v2.5
O | Other | andere | Anders | | added v2.5
PR | Person preparing referral | Person, die die Überweisung vorbereitet | Persoon die verwijzing voorbereidt | deprecated | added v2.3, removed after v2.3
S | State Agency | Landesbehörde | Staat overheidsinstelling | | added v2.5
U | Unknown | unbekannt | Onbekend | | added v2.5

4.2.13.133 HL7 Version 2 Table 0133

URL: https://hl7.org/fhir/STU3/v2/0133/index.html

This page is part of the FHIR Specification (v3.0.2: STU 3). The current version which supercedes this version is 4.0.1. For a full list of available versions, see the Directory of published versions

Vocabulary Work Group | Maturity Level: N/A | External | Use Context: Any

This is a table defined as part of HL7 v2 . Related FHIR content: v2 Procedure Practitioner Identifier Code Type.

Summary

Name: | v2 Procedure Practitioner Identifier Code Type
Definition: | FHIR Value set/code system definition for HL7 v2 table 0133 (Procedure Practitioner Identifier Code Type)
Code System URL: | http://hl7.org/fhir/v2/0133
Value Set URL: | http://hl7.org/fhir/ValueSet/v2-0133
OID: | ??
CodeSystem Resource | XML / JSON
ValueSet Resource | XML / JSON

This value set is used in the following places:

* This value set is the designated 'entire code system' value set for v2 Procedure Practitioner Identifier Code Type

4.2.13.133.1 Code System Content

Procedure Practitioner Identifier Code Type

Code | Description | Deutsch (German) | Nederlands (Dutch) | Comment | Version
AN | Anesthesiologist/Anesthetist | Anästhesist | Anesthesioloog/Anesthesist | deprecated | added v2.2, removed after v2.5.1
AS | Assistant Surgeon | Assistenzchirurg | Assistent chirurg | deprecated | added v2.3, removed after v2.5.1
CM | Certified Nurse Midwife | Hebamme | Gecertificeerde verloskundig verpleegkundige | deprecated | added v2.2, removed after v2.5.1
NP | Nurse Practitioner | Krankenschwester | Nurse practitioner | deprecated | added v2.2, removed after v2.5.1
PR | Procedure MD/ Surgeon | ausführender Arzt (Chirurg) | Chirurg | deprecated | added v2.2, removed after v2.5.1
PS | Primary Surgeon | verantwortlicher Chirurg | Hoofdchirurg | deprecated | added v2.3, removed after v2.5.1
RD | Radiologist | Radiologe | Radioloog | deprecated | added v2.2, removed after v2.5.1
RS | Resident | Krankenhausarzt | Medewerker | deprecated | added v2.2, removed after v2.5.1
SN | Scrub Nurse | | Operatieassistent | deprecated | added v2.3, removed after v2.5.1

4.2.13.135 HL7 Version 2 Table 0135

URL: https://hl7.org/fhir/STU3/v2/0135/index.html

This page is part of the FHIR Specification (v3.0.2: STU 3). The current version which supercedes this version is 4.0.1. For a full list of available versions, see the Directory of published versions

Vocabulary Work Group | Maturity Level: N/A | External | Use Context: Any

This is a table defined as part of HL7 v2 . Related FHIR content: v2 Assignment of Benefits.

Summary

Name: | v2 Assignment of Benefits
Definition: | FHIR Value set/code system definition for HL7 v2 table 0135 (Assignment of Benefits)
Code System URL: | http://hl7.org/fhir/v2/0135
Value Set URL: | http://hl7.org/fhir/ValueSet/v2-0135
OID: | ??
CodeSystem Resource | XML / JSON
ValueSet Resource | XML / JSON

This value set is used in the following places:

* This value set is the designated 'entire code system' value set for v2 Assignment of Benefits

4.2.13.135.1 Code System Content

Assignment of Benefits

Code | Description | Deutsch (German) | Nederlands (Dutch) | Comment | Version
M | Modified assignment | Sonderabmachung | Aangepaste toekenning | | added v2.2
N | No | Nein | Nee | | added v2.2
Y | Yes | Ja | Ja | | added v2.2

4.2.13.136 HL7 Version 2 Table 0136

URL: https://hl7.org/fhir/STU3/v2/0136/index.html

This page is part of the FHIR Specification (v3.0.2: STU 3). The current version which supercedes this version is 4.0.1. For a full list of available versions, see the Directory of published versions

Vocabulary Work Group | Maturity Level: N/A | External | Use Context: Any

This is a table defined as part of HL7 v2 . Related FHIR content: v2 Yes/no Indicator.

Summary

Name: | v2 Yes/no Indicator
Definition: | FHIR Value set/code system definition for HL7 v2 table 0136 (Yes/no Indicator)

Code System URL: | http://hl7.org/fhir/v2/0136
Value Set URL: | http://hl7.org/fhir/ValueSet/v2-0136
OID: | ??
CodeSystem Resource | XML / JSON
ValueSet Resource | XML / JSON

This value set is used in the following places:

* This value set is the designated 'entire code system' value set for v2 Yes/no Indicator

4.2.13.136.1 Code System Content

Yes/no Indicator

Code | Description | Deutsch (German) | Nederlands (Dutch) | Comment | Version
N | No | Nein | Nee | | added v2.2
Y | Yes | Ja | Ja | | added v2.2

4.2.13.137 HL7 Version 2 Table 0137

URL: https://hl7.org/fhir/STU3/v2/0137/index.html

This page is part of the FHIR Specification (v3.0.2: STU 3). The current version which supercedes this version is 4.0.1. For a full list of available versions, see the Directory of published versions

Vocabulary Work Group | Maturity Level: N/A | External | Use Context: Any

This is a table defined as part of HL7 v2 . Related FHIR content: v2 Mail Claim Party.

Summary

Name: | v2 Mail Claim Party
Definition: | FHIR Value set/code system definition for HL7 v2 table 0137 (Mail Claim Party)
Code System URL: | http://hl7.org/fhir/v2/0137
Value Set URL: | http://hl7.org/fhir/ValueSet/v2-0137
OID: | ??
CodeSystem Resource | XML / JSON
ValueSet Resource | XML / JSON

This value set is used in the following places:

* This value set is the designated 'entire code system' value set for v2 Mail Claim Party

4.2.13.137.1 Code System Content

Mail Claim Party

Code | Description | Deutsch (German) | Nederlands (Dutch) | Comment | Version
E | Employer | Arbeitgeber | Werkgever | | added v2.2
G | Guarantor | Zahlungspflichtiger | Garantstaande | | added v2.2
I | Insurance company | Versicherung / Krankenkasse | Verzekeraar | | added v2.2
O | Other | andere | Anders | | added v2.2
P | Patient | Patient / Selbstzahler | Patiënt | | added v2.2

4.2.13.140 HL7 Version 2 Table 0140

URL: https://hl7.org/fhir/STU3/v2/0140/index.html

This page is part of the FHIR Specification (v3.0.2: STU 3). The current version which supercedes this version is 4.0.1. For a full list of available versions, see the Directory of published versions

Vocabulary Work Group | Maturity Level: N/A | External | Use Context: Any

This is a table defined as part of HL7 v2 . Related FHIR content: v2 Military Service.

Summary

Name: | v2 Military Service
Definition: | FHIR Value set/code system definition for HL7 v2 table 0140 (Military Service)
Code System URL: | http://hl7.org/fhir/v2/0140
Value Set URL: | http://hl7.org/fhir/ValueSet/v2-0140
OID: | ??
CodeSystem Resource | XML / JSON
ValueSet Resource | XML / JSON

This value set is used in the following places:

* This value set is the designated 'entire code system' value set for v2 Military Service

4.2.13.140.1 Code System Content

Military Service

Code | Description | Nederlands (Dutch) | Comment | Version
AUSA | Australian Army | Australische leger | | added v2.4

AUSAF | Australian Air Force | Australische luchtmacht | | added v2.4
AUSN | Australian Navy | Australische marine | | added v2.4
NATO | North Atlantic Treaty Organization | Noord-Atlantische Verdragsorganisatie (NAVO) | | added v2.3.1
NOAA | National Oceanic and Atmospheric Administration | Amerikaanse oceanische en atmosferische dienst | | added v2.3.1
USA | US Army | Amerikaans leger | | added v2.3.1
USAF | US Air Force | Amerikaanse luchtmacht | | added v2.3.1
USCG | US Coast Guard | Amerikaanse kustwacht | | added v2.3.1
USMC | US Marine Corps | Amerikaanse korps mariniers | | added v2.3.1
USN | US Navy | Amerikaanse marine | | added v2.3.1
USPHS | US Public Health Service | Amerikaanse volksgezondheiddienst | | added v2.3.1

4.2.13.141 HL7 Version 2 Table 0141

URL: https://hl7.org/fhir/STU3/v2/0141/index.html

This page is part of the FHIR Specification (v3.0.2: STU 3). The current version which supercedes this version is 4.0.1. For a full list of available versions, see the Directory of published versions

Vocabulary Work Group | Maturity Level: N/A | External | Use Context: Any

This is a table defined as part of HL7 v2 . Related FHIR content: v2 Military Rank/Grade.

Summary

Name: | v2 Military Rank/Grade
Definition: | FHIR Value set/code system definition for HL7 v2 table 0141 (Military Rank/Grade)
Code System URL: | http://hl7.org/fhir/v2/0141
Value Set URL: | http://hl7.org/fhir/ValueSet/v2-0141
OID: | ??
CodeSystem Resource | XML / JSON
ValueSet Resource | XML / JSON

This value set is used in the following places:

* This value set is the designated 'entire code system' value set for v2 Military Rank/Grade

4.2.13.141.1 Code System Content

Military Rank/Grade

Code | Description | Nederlands (Dutch) | Comment | Version
E1 ... E9 | Enlisted | Ingetekend | deprecated | added v2.3.1, removed after v2.4
E1... E9 | Enlisted | Ingetekend | | added v2.5
O1 ... O10 | Officers | Officieren | deprecated | added v2.3.1, removed after v2.4
O1 ... O9 | Officers | Officieren | | added v2.5
W1 ... W4 | Warrant Officers | Warrant-officieren | | added v2.3.1

4.2.13.142 HL7 Version 2 Table 0142

URL: https://hl7.org/fhir/STU3/v2/0142/index.html

This page is part of the FHIR Specification (v3.0.2: STU 3). The current version which supercedes this version is 4.0.1. For a full list of available versions, see the Directory of published versions

Vocabulary Work Group | Maturity Level: N/A | External | Use Context: Any

This is a table defined as part of HL7 v2 . Related FHIR content: v2 Military Status.

Summary

Name: | v2 Military Status
Definition: | FHIR Value set/code system definition for HL7 v2 table 0142 (Military Status)
Code System URL: | http://hl7.org/fhir/v2/0142
Value Set URL: | http://hl7.org/fhir/ValueSet/v2-0142
OID: | ??
CodeSystem Resource | XML / JSON
ValueSet Resource | XML / JSON

This value set is used in the following places:

* This value set is the designated 'entire code system' value set for v2 Military Status

4.2.13.142.1 Code System Content

Military Status

Code | Description | Nederlands (Dutch) | Comment | Version
ACT | Active duty | Actieve dienst | | added v2.3.1
DEC | Deceased | Overleden | | added v2.3.1
RET | Retired | Gepensioneerd | | added v2.3.1

4.2.13.144 HL7 Version 2 Table 0144

URL: https://hl7.org/fhir/STU3/v2/0144/index.html

This page is part of the FHIR Specification (v3.0.2: STU 3). The current version which supercedes this version is 4.0.1. For a full list of available versions, see the Directory of published versions

Vocabulary Work Group | Maturity Level: N/A | External | Use Context: Any

This is a table defined as part of HL7 v2 . Related FHIR content: v2 Eligibility Source.

Summary

Name: | v2 Eligibility Source
Definition: | FHIR Value set/code system definition for HL7 v2 table 0144 (Eligibility Source)
Code System URL: | http://hl7.org/fhir/v2/0144
Value Set URL: | http://hl7.org/fhir/ValueSet/v2-0144
OID: | ??
CodeSystem Resource | XML / JSON
ValueSet Resource | XML / JSON

This value set is used in the following places:

* This value set is the designated 'entire code system' value set for v2 Eligibility Source

4.2.13.144.1 Code System Content

Eligibility Source

Code	Description	Deutsch (German)	Nederlands (Dutch)	Comment	Version
1	Insurance company	Versicherung / Krankenkasse	Verzekeraar		added v2.2
2	Employer	Arbeitgeber	Werkgever		added v2.2
3	Insured presented policy	vorgelegte Versicherungspolice	Door verzekerde getoonde polis		added v2.2
4	Insured presented card	Vorgelegte Krankenversichertenkarte (KVK)	Door verzekerde getoonde kaart		added v2.2
5	Signed statement on file	Unterschriebenene Bestätigung	Ondertekenende mededeling op schrift		added v2.2
6	Verbal information	mündliche Angabe	Mondelinge mededeling		added v2.2
7	None	keine	Geen		added v2.2

4.2.13.145 HL7 Version 2 Table 0145

URL: https://hl7.org/fhir/STU3/v2/0145/index.html

This page is part of the FHIR Specification (v3.0.2: STU 3). The current version which supercedes this version is 4.0.1. For a full list of available versions, see the Directory of published versions

Vocabulary Work Group | Maturity Level: N/A | External | Use Context: Any

This is a table defined as part of HL7 v2 . Related FHIR content: v2 Room Type.

Summary

Name: | v2 Room Type
Definition: | FHIR Value set/code system definition for HL7 v2 table 0145 (Room Type)
Code System URL: | http://hl7.org/fhir/v2/0145
Value Set URL: | http://hl7.org/fhir/ValueSet/v2-0145
OID: | ??
CodeSystem Resource | XML / JSON
ValueSet Resource | XML / JSON

This value set is used in the following places:

* This value set is the designated 'entire code system' value set for v2 Room Type

4.2.13.145.1 Code System Content

Room Type

Code	Description	Deutsch (German)	Nederlands (Dutch)	Comment	Version
2ICU	Second intensive care unit	nicht verwendet	Tweede intensive care unit		added v2.2
2PRI	Second private room	nicht verwendet	Tweede eigen kamer		added v2.2
2SPR	Second semi-private room	nicht verwendet	Tweede semi-eigen kamer		added v2.2
ICU	Intensive care unit	Intensivstation	Intensive care unit		added v2.2
PRI	Private room	Einbettzimmer	Eigen kamer		added v2.2
SPR	Semi-private room	Zweibettzimmer	Semi-eigen kamer		added v2.2

4.2.13.146 HL7 Version 2 Table 0146

URL: https://hl7.org/fhir/STU3/v2/0146/index.html

This page is part of the FHIR Specification (v3.0.2: STU 3). The current version which supercedes this version is 4.0.1. For a full list of available versions, see the Directory of published versions

Vocabulary Work Group | Maturity Level: N/A | External | Use Context: Any

This is a table defined as part of HL7 v2 . Related FHIR content: v2 Amount Type.

Summary

Name: | v2 Amount Type
Definition: | FHIR Value set/code system definition for HL7 v2 table 0146 (Amount Type)
Code System URL: | http://hl7.org/fhir/v2/0146
Value Set URL: | http://hl7.org/fhir/ValueSet/v2-0146
OID: | ??
CodeSystem Resource | XML / JSON
ValueSet Resource | XML / JSON

This value set is used in the following places:

* This value set is the designated 'entire code system' value set for v2 Amount Type

4.2.13.146.1 Code System Content

Amount Type

Code | Description | Deutsch (German) | Nederlands (Dutch) | Comment | Version
DF | Differential | Differenzbetrag | Differentieel | | added v2.2
LM | Limit | Höchstbetrag | Grens | | added v2.2
PC | Percentage | Prozentsatz | Percentage | Retained for backward compatibility only as of v 2.5 | added v2.2
RT | Rate | Tagessatz | Kostprijs | | added v2.2
UL | Unlimited | unbegrenzt | Onbeperkt | | added v2.2

4.2.13.147 HL7 Version 2 Table 0147

URL: https://hl7.org/fhir/STU3/v2/0147/index.html

This page is part of the FHIR Specification (v3.0.2: STU 3). The current version which supercedes this version is 4.0.1. For a full list of available versions, see the Directory of published versions

Vocabulary Work Group | Maturity Level: N/A | External | Use Context: Any

This is a table defined as part of HL7 v2 . Related FHIR content: v2 Policy Type.

Summary

Name: | v2 Policy Type
Definition: | FHIR Value set/code system definition for HL7 v2 table 0147 (Policy Type)
Code System URL: | http://hl7.org/fhir/v2/0147
Value Set URL: | http://hl7.org/fhir/ValueSet/v2-0147
OID: | ??
CodeSystem Resource | XML / JSON
ValueSet Resource | XML / JSON

This value set is used in the following places:

* This value set is the designated 'entire code system' value set for v2 Policy Type

4.2.13.147.1 Code System Content

Policy Type

Code | Description | Deutsch (German) | Nederlands (Dutch) | Comment | Version
2ANC | Second ancillary | weitere Zusatzversicherung | Tweede aanvullend | | added v2.2
2MMD | Second major medical | weitere Hauptversicherung | | | added v2.2
3MMD | Third major medical | weitere Hauptversicherung | | | added v2.2
ANC | Ancillary | Zusatzversicherung | Aanvullend | | added v2.2
MMD | Major medical | Hauptversicherung | Basisverzekering | | added v2.2

4.2.13.148 HL7 Version 2 Table 0148

URL: https://hl7.org/fhir/STU3/v2/0148/index.html

This page is part of the FHIR Specification (v3.0.2: STU 3). The current version which supercedes this version is 4.0.1. For a full list of available versions, see the Directory of published versions

Vocabulary Work Group | Maturity Level: N/A | External | Use Context: Any

This is a table defined as part of HL7 v2 . Related FHIR content: v2 Money or Percentage Indicator.

Summary

Name: | v2 Money or Percentage Indicator
Definition: | FHIR Value set/code system definition for HL7 v2 table 0148 (Money or Percentage Indicator)
Code System URL: | http://hl7.org/fhir/v2/0148
Value Set URL: | http://hl7.org/fhir/ValueSet/v2-0148
OID: | ??
CodeSystem Resource | XML / JSON
ValueSet Resource | XML / JSON

This value set is used in the following places:

* This value set is the designated 'entire code system' value set for v2 Money or Percentage Indicator

4.2.13.148.1 Code System Content

Money or Percentage Indicator

Code | Description | Deutsch (German) | Nederlands (Dutch) | Comment | Version
AT | Currency amount | Betrag (Tabelle 148 wird nicht verwendet) | Geldbedrag | | added v2.2
PC | Percentage | Prozentsatz | Percentage | | added v2.2

4.2.13.149 HL7 Version 2 Table 0149

URL: https://hl7.org/fhir/STU3/v2/0149/index.html

This page is part of the FHIR Specification (v3.0.2: STU 3). The current version which supercedes this version is 4.0.1. For a full list of available versions, see the Directory of published versions

Vocabulary Work Group | Maturity Level: N/A | External | Use Context: Any

This is a table defined as part of HL7 v2 . Related FHIR content: v2 Day Type.

Summary

Name: | v2 Day Type
Definition: | FHIR Value set/code system definition for HL7 v2 table 0149 (Day Type)
Code System URL: | http://hl7.org/fhir/v2/0149
Value Set URL: | http://hl7.org/fhir/ValueSet/v2-0149
OID: | ??
CodeSystem Resource | XML / JSON
ValueSet Resource | XML / JSON

This value set is used in the following places:

* This value set is the designated 'entire code system' value set for v2 Day Type

4.2.13.149.1 Code System Content

Day Type

Code | Description | Deutsch (German) | Nederlands (Dutch) | Comment | Version
AP | Approved | (Tabelle 149 wird nicht verwendet) | Goedgekeurd | | added v2.2
DE | Denied | | Afgekeurd | | added v2.2
PE | Pending | | Beslissing volgt | | added v2.2

4.2.13.150 HL7 Version 2 Table 0150

URL: https://hl7.org/fhir/STU3/v2/0150/index.html

This page is part of the FHIR Specification (v3.0.2: STU 3). The current version which supercedes this version is 4.0.1. For a full list of available versions, see the Directory of published versions

Vocabulary Work Group | Maturity Level: N/A | External | Use Context: Any

This is a table defined as part of HL7 v2 . Related FHIR content: v2 Certification Patient Type.

Summary

Name: | v2 Certification Patient Type
Definition: | FHIR Value set/code system definition for HL7 v2 table 0150 (Certification Patient Type)
Code System URL: | http://hl7.org/fhir/v2/0150
Value Set URL: | http://hl7.org/fhir/ValueSet/v2-0150
OID: | ??
CodeSystem Resource | XML / JSON
ValueSet Resource | XML / JSON

This value set is used in the following places:

* This value set is the designated 'entire code system' value set for v2 Certification Patient Type

4.2.13.150.1 Code System Content

Certification Patient Type

Code | Description | Deutsch (German) | Nederlands (Dutch) | Comment | Version
ER | Emergency | (Tabelle 150 wird nicht verwendet) | Spoed | | added v2.2
IPE | Inpatient elective | | Klinisch eigen keuze | | added v2.2
OPE | Outpatient elective | | Poliklinisch eigen keuze | | added v2.2
UR | Urgent | | Spoed | | added v2.2

4.2.13.153 HL7 Version 2 Table 0153

URL: https://hl7.org/fhir/STU3/v2/0153/index.html

This page is part of the FHIR Specification (v3.0.2: STU 3). The current version which supercedes this version is 4.0.1. For a full list of available versions, see the Directory of published versions

Vocabulary Work Group | Maturity Level: N/A | External | Use Context: Any

This is a table defined as part of HL7 v2 . Related FHIR content: v2 Value Code.

Summary

Name: | v2 Value Code
Definition: | FHIR Value set/code system definition for HL7 v2 table 0153 (Value Code)
Code System URL: | http://hl7.org/fhir/v2/0153
Value Set URL: | http://hl7.org/fhir/ValueSet/v2-0153
OID: | ??
CodeSystem Resource | XML / JSON
ValueSet Resource | XML / JSON

This value set is used in the following places:

* This value set is the designated 'entire code system' value set for v2 Value Code

4.2.13.153.1 Code System Content

Value Code

Code | Description | Nederlands (Dutch) | Comment | Version
... | See NUBC codes | Zie (Amerikaanse) NUBC codes | | added v2.5.1
01 | Most common semi-private rate | Meest algemeen semi-privé | deprecated | added v2.3.1, removed after v2.4
02 | Hospital has no semi-private rooms | Ziekenhuis heeft geen semi-eigen kamers | deprecated | added v2.3.1, removed after v2.4
04 | Inpatient professional component charges which are combined billed | | deprecated | added v2.3.1, removed after v2.4
05 | Professional component included in charges and also billed separate to carrier | | deprecated | added v2.3.1, removed after v2.4
06 | Medicare blood deductible | | deprecated | added v2.3.1, removed after v2.4
08 | Medicare life time reserve amount in the first calendar year | | deprecated | added v2.3.1, removed after v2.4
09 | Medicare co-insurance amount in the first calendar year | | deprecated | added v2.3.1, removed after v2.4
10 | Lifetime reserve amount in the second calendar year | | deprecated | added v2.3.1, removed after v2.4
11 | Co-insurance amount in the second calendar year | | deprecated | added v2.3.1, removed after v2.4
12 | Working aged beneficiary/spouse with employer group health plan | | deprecated | added v2.3.1, removed after v2.4
13 | ESRD beneficiary in a Medicare coordination period with an employer group health plan | | deprecated | added v2.3.1, removed after v2.4
14 | No Fault including auto/other | | deprecated | added v2.3.1, removed after v2.4
15 | Worker's Compensation | Werknemer compensatie | deprecated | added v2.3.1, removed after v2.4
16 | PHS, or other federal agency | | deprecated | added v2.3.1, removed after v2.4
17 | Payer code | Betalercode | deprecated | added v2.3.1, removed after v2.4
21 | Catastrophic | Catastrofaal | deprecated | added v2.3.1, removed after v2.4
22 | Surplus | Surplus | deprecated | added v2.3.1, removed after v2.4
23 | Recurring monthly incode | Regelmatig maandelijks inkomen | deprecated | added v2.3.1, removed after v2.4
24 | Medicaid rate code | Medicaid tariefcode | deprecated | added v2.3.1, removed after v2.4
30 | Pre-admission testing | Vooropname testen | deprecated | added v2.3.1, removed after v2.4
31 | Patient liability amount | Patiënt aansprakelijkheid bedrag | deprecated | added v2.3.1, removed after v2.4
37 | Pints of blood furnished | | deprecated | added v2.3.1, removed after v2.4
38 | Blood deductible pints | | deprecated | added v2.3.1, removed after v2.4
39 | Pints of blood replaced | | deprecated | added v2.3.1, removed after v2.4
40 | New coverage not implemented by HMO (for inpatient service only) | | deprecated | added v2.3.1, removed after v2.4
41 | Black lung | Stoflong | deprecated | added v2.3.1, removed after v2.4
42 | VA | Amerikaanse Veterans Affairs | deprecated | added v2.3.1, removed after v2.4
43 | Disabled beneficiary under age 64 with LGHP | | deprecated | added v2.3.1, removed after v2.4
44 | Amount provider agreed to accept from primary payer when this amount is less than charges but higher than payment received,, then a Medicare secondary payment is due | | deprecated | added v2.3.1, removed after v2.4
45 | Accident hour | | deprecated | added v2.3.1, removed after v2.4
46 | Number of grace days | | deprecated | added v2.3.1, removed after v2.4
47 | Any liability insurance | Een of andere aansprakelijkheidsverzekering | deprecated | added v2.3.1, removed after v2.4
48 | Hemoglobin reading | Hemoglobinewaarde | deprecated | added v2.3.1, removed after v2.4
49 | Hematocrit reading | Hematocrietwaarde | deprecated | added v2.3.1, removed after v2.4
50 | Physical therapy visits | Lichamelijke oefening bezoeken | deprecated | added v2.3.1, removed after v2.4
51 | Occupational therapy visits | Ergotherapie bezoeken | deprecated | added v2.3.1, removed after v2.4
52 | Speech therapy visits | Stemoefening bezoeken | deprecated | added v2.3.1, removed after v2.4
53 | Cardiac rehab visits | Hartrevalidatie bezoeken | deprecated | added v2.3.1, removed after v2.4
56 | Skilled nurse - home visit hours | | deprecated | added v2.3.1, removed after v2.4
57 | Home health aide - home visit hours | Thuiszorg hulp - thuisbezoekuren | deprecated | added v2.3.1, removed after v2.4
58 | Arterial blood gas | Arterieel bloedgas | deprecated | added v2.3.1, removed after v2.4
59 | Oxygen saturation | Zuurstofsaturatie | deprecated | added v2.3.1, removed after v2.4
60 | HHA branch MSA | | deprecated | added v2.3.1, removed after v2.4
67 | Peritoneal dialysis | Peritoneale dialyse | deprecated | added v2.3.1, removed after v2.4
68 | EPO-drug | EPO-medicatie | deprecated | added v2.3.1, removed after v2.4
70 | Payer codes | Betalercodes | deprecated | added v2.3.1, removed after v2.4
70 ... 72 | Payer codes | Betalercodes | deprecated | added v2.3.1, removed after v2.4
71 | Payer codes | Betalercodes | deprecated | added v2.3.1, removed after v2.4
72 | Payer codes | Betalercodes | deprecated | added v2.3.1, removed after v2.4
75 | Payer codes | Betalercodes | deprecated | added v2.3.1, removed after v2.4
75 ... 79 | Payer codes | Betalercodes | deprecated | added v2.3.1, removed after v2.4
76 | Payer codes | Betalercodes | deprecated | added v2.3.1, removed after v2.4
77 | Payer codes | Betalercodes | deprecated | added v2.3.1, removed after v2.4

78 | Payer codes | Betalercodes | deprecated | added v2.3.1, removed after v2.4
79 | Payer codes | Betalercodes | deprecated | added v2.3.1, removed after v2.4
80 | Psychiatric visits | Psychiatrische bezoeken | deprecated | added v2.3.1, removed after v2.4
81 | Visits subject to co-payment | Bezoeken vallen onder co-betaling | deprecated | added v2.3.1, removed after v2.4
A1 | Deductible payer A | Eigen risico betaler A | deprecated | added v2.3.1, removed after v2.4
A2 | Coinsurance payer A | Medeverzekerd betaler A | deprecated | added v2.3.1, removed after v2.4
A3 | Estimated responsibility payer A | Geschatte verantwoordelijkheid betaler A | deprecated | added v2.3.1, removed after v2.4
X0 | Service excluded on primary policy | Service uitgesloten van primaire polis | deprecated | added v2.3.1, removed after v2.4
X4 | Supplemental coverage | Aanvullende dekking | deprecated | added v2.3.1, removed after v2.4
… | See NUBC codes | Zie (Amerikaanse) NUBC codes | deprecated | added v2.7.1, removed after v2.7.1

4.2.13.155 HL7 Version 2 Table 0155

URL: https://hl7.org/fhir/STU3/v2/0155/index.html

This page is part of the FHIR Specification (v3.0.2: STU 3). The current version which supercedes this version is 4.0.1. For a full list of available versions, see the Directory of published versions

Vocabulary Work Group | Maturity Level: N/A | External | Use Context: Any

This is a table defined as part of HL7 v2 . Related FHIR content: v2 Accept/Application Acknowledgment Conditions.

Summary

Name: | v2 Accept/Application Acknowledgment Conditions
Definition: | FHIR Value set/code system definition for HL7 v2 table 0155 (Accept/Application Acknowledgment Conditions)
Code System URL: | http://hl7.org/fhir/v2/0155
Value Set URL: | http://hl7.org/fhir/ValueSet/v2-0155
OID: | ??
CodeSystem Resource | XML / JSON
ValueSet Resource | XML / JSON

This value set is used in the following places:

* This value set is the designated 'entire code system' value set for v2 Accept/Application Acknowledgment Conditions

4.2.13.155.1 Code System Content

Accept/Application Acknowledgment Conditions

Code | Description | Deutsch (German) | Nederlands (Dutch) | Comment | Version
AL | Always | immer | Altijd | | added v2.2
ER | Error/reject conditions only | Nur bei Auftreten von Fehlerbedingungen | Alleen bij fout/weigering | | added v2.2
NE | Never | niemals | Nooit | | added v2.2
SU | Successful completion only | Nur bei erfolgreichem Abschluß | Alleen bij succes | | added v2.2

4.2.13.156 HL7 Version 2 Table 0156

URL: https://hl7.org/fhir/STU3/v2/0156/index.html

This page is part of the FHIR Specification (v3.0.2: STU 3). The current version which supercedes this version is 4.0.1. For a full list of available versions, see the Directory of published versions

Vocabulary Work Group | Maturity Level: N/A | External | Use Context: Any

This is a table defined as part of HL7 v2 . Related FHIR content: v2 Which date/time qualifier.

Summary

Name: | v2 Which date/time qualifier
Definition: | FHIR Value set/code system definition for HL7 v2 table 0156 (Which date/time qualifier)
Code System URL: | http://hl7.org/fhir/v2/0156
Value Set URL: | http://hl7.org/fhir/ValueSet/v2-0156
OID: | ??
CodeSystem Resource | XML / JSON
ValueSet Resource | XML / JSON

This value set is used in the following places:

* This value set is the designated 'entire code system' value set for v2 Which date/time qualifier

4.2.13.156.1 Code System Content

Which date/time qualifier

Code | Description | Deutsch (German) | Nederlands (Dutch) | Comment | Version
ANY | Any date/time within a range | Alle Ereignisse | Elke datum/tijd binnen periode | deprecated | added v2.2, removed after v2.6
CAN | Cancellation date/time | Stornierung | Annulering datum/tijd | deprecated | added v2.2, removed after v2.3
COL | Collection date/time, equivalent to film or sample collection date/time | Probenentnahme / Untersuchung | Verzamel datum/tijd (equivalent aan film of monster verzamel datum/tijd) | deprecated | added v2.2, removed after v2.6
ORD | Order date/time | Auftragseingabe | Aanvraag datum/tijd | deprecated | added v2.2, removed after v2.6
RCT | Specimen receipt date/time, receipt of specimen in filling ancillary (Lab) | Probeneingang | Monster ontvangen datum/tijd (ontvangst van monster bij filler (lab)) | deprecated | added v2.2, removed after v2.6

REP | Report date/time, report date/time at filling ancillary (i.e., Lab) | Berichtserstellung | Verslag datum/tijd (verslag datum/tijd bij filler (lab)) | deprecated | added v2.2, removed after v2.6
SCHED | Schedule date/time | Terminvergabe | Planning datum/tijd | deprecated | added v2.2, removed after v2.6

4.2.13.157 HL7 Version 2 Table 0157

URL: https://hl7.org/fhir/STU3/v2/0157/index.html

This page is part of the FHIR Specification (v3.0.2: STU 3). The current version which supercedes this version is 4.0.1. For a full list of available versions, see the Directory of published versions

Vocabulary Work Group | Maturity Level: N/A | External | Use Context: Any

This is a table defined as part of HL7 v2 . Related FHIR content: v2 Which date/time status qualifier.

Summary

Name: | v2 Which date/time status qualifier
Definition: | FHIR Value set/code system definition for HL7 v2 table 0157 (Which date/time status qualifier)
Code System URL: | http://hl7.org/fhir/v2/0157
Value Set URL: | http://hl7.org/fhir/ValueSet/v2-0157
OID: | ??
CodeSystem Resource | XML / JSON
ValueSet Resource | XML / JSON

This value set is used in the following places:

* This value set is the designated 'entire code system' value set for v2 Which date/time status qualifier

4.2.13.157.1 Code System Content

Which date/time status qualifier

Code | Description | Deutsch (German) | Nederlands (Dutch) | Comment | Version
ANY | Any status | Beliebiger Status | Willekeurige status | deprecated | added v2.2, removed after v2.6
CFN | Current final value, whether final or corrected | Aktuelles Endergebnis | Huidige definitieve waarde (definitief en/of gecorrigeerd) | deprecated | added v2.2, removed after v2.6
COR | Corrected only (no final with corrections) | Ursprüngliche Ergebnisse, die später korrigiert wurden | Alleen correcties (geen definitief met correcties) | deprecated | added v2.2, removed after v2.6
FIN | Final only (no corrections) | Endergebnisse, die niemals korrigiert wurden | Alleen definitief (geen correcties) | deprecated | added v2.2, removed after v2.6
PRE | Preliminary | Vorläufig | Voorlopig | deprecated | added v2.2, removed after v2.6
REP | Report completion date/time | Bericht abgeschlossen | Verslag voltooiing datum/tijd | deprecated | added v2.2, removed after v2.6

4.2.13.158 HL7 Version 2 Table 0158

URL: https://hl7.org/fhir/STU3/v2/0158/index.html

This page is part of the FHIR Specification (v3.0.2: STU 3). The current version which supercedes this version is 4.0.1. For a full list of available versions, see the Directory of published versions

Vocabulary Work Group | Maturity Level: N/A | External | Use Context: Any

This is a table defined as part of HL7 v2 . Related FHIR content: v2 Date/time selection qualifier.

Summary

Name: | v2 Date/time selection qualifier
Definition: | FHIR Value set/code system definition for HL7 v2 table 0158 (Date/time selection qualifier)
Code System URL: | http://hl7.org/fhir/v2/0158
Value Set URL: | http://hl7.org/fhir/ValueSet/v2-0158
OID: | ??
CodeSystem Resource | XML / JSON
ValueSet Resource | XML / JSON

This value set is used in the following places:

* This value set is the designated 'entire code system' value set for v2 Date/time selection qualifier

4.2.13.158.1 Code System Content

Date/time selection qualifier

Code | Description | Deutsch (German) | Nederlands (Dutch) | Comment | Version
1ST | First value within range | erster Wert | Eerste waarde binnen bereik | deprecated | added v2.2, removed after v2.6
ALL | All values within the range | alle Werte | Alle waarden binnen bereik | deprecated | added v2.2, removed after v2.6
LST | Last value within the range | letzter Wert | Laatste waarde binnen bereik | deprecated | added v2.2, removed after v2.6
REV | All values within the range returned in reverse chronological order (This is the default if not otherwise specified.) | alle Werte in umgekehrter chronologischer Reihenfolge | Alle waarden binnen bereik in omgekeerde chronologische volgorde. (Standaard tenzij anders gespecificeerd.) | deprecated | added v2.2, removed after v2.6

4.2.13.159 HL7 Version 2 Table 0159

URL: https://hl7.org/fhir/STU3/v2/0159/index.html

This page is part of the FHIR Specification (v3.0.2: STU 3). The current version which supercedes this version is 4.0.1. For a full list of available versions, see the Directory of published versions

Vocabulary Work Group | Maturity Level: N/A | External | Use Context: Any

This is a table defined as part of HL7 v2 . Related FHIR content: v2 Diet Code Specification Type.

Summary

Name: | v2 Diet Code Specification Type
Definition: | FHIR Value set/code system definition for HL7 v2 table 0159 (Diet Code Specification Type)
Code System URL: | http://hl7.org/fhir/v2/0159
Value Set URL: | http://hl7.org/fhir/ValueSet/v2-0159
OID: | ??
CodeSystem Resource | XML / JSON
ValueSet Resource | XML / JSON

This value set is used in the following places:

* This value set is the designated 'entire code system' value set for v2 Diet Code Specification Type

4.2.13.159.1 Code System Content

Diet Code Specification Type

Code | Description | Deutsch (German) | Nederlands (Dutch) | Comment | Version
D | Diet | Diät | Dieet | | added v2.2
P | Preference | bevorzugte Verpflegung | Voorkeur | | added v2.2
S | Supplement | Zusatzverpflegung | Supplement | | added v2.2

4.2.13.160 HL7 Version 2 Table 0160

URL: https://hl7.org/fhir/STU3/v2/0160/index.html

This page is part of the FHIR Specification (v3.0.2: STU 3). The current version which supercedes this version is 4.0.1. For a full list of available versions, see the Directory of published versions

Vocabulary Work Group | Maturity Level: N/A | External | Use Context: Any

This is a table defined as part of HL7 v2 . Related FHIR content: v2 Tray Type.

Summary

Name: | v2 Tray Type
Definition: | FHIR Value set/code system definition for HL7 v2 table 0160 (Tray Type)
Code System URL: | http://hl7.org/fhir/v2/0160
Value Set URL: | http://hl7.org/fhir/ValueSet/v2-0160
OID: | ??
CodeSystem Resource | XML / JSON
ValueSet Resource | XML / JSON

This value set is used in the following places:

* This value set is the designated 'entire code system' value set for v2 Tray Type

4.2.13.160.1 Code System Content

Tray Type

Code | Description | Deutsch (German) | Nederlands (Dutch) | Comment | Version
EARLY | Early tray | früh servieren | Vroege tray | | added v2.2
GUEST | Guest tray | Gästeessen | Bezoeker-tray | | added v2.2
LATE | Late tray | spät servieren | Late tray | | added v2.2
MSG | Tray message only | Ergänzende Hinweise | Alleen tray-bericht | | added v2.2
NO | No tray | kein Essen | Geen tray | | added v2.2

4.2.13.161 HL7 Version 2 Table 0161

URL: https://hl7.org/fhir/STU3/v2/0161/index.html

This page is part of the FHIR Specification (v3.0.2: STU 3). The current version which supercedes this version is 4.0.1. For a full list of available versions, see the Directory of published versions

Vocabulary Work Group | Maturity Level: N/A | External | Use Context: Any

This is a table defined as part of HL7 v2 . Related FHIR content: v2 Allow Substitution.

Summary

Name: | v2 Allow Substitution
Definition: | FHIR Value set/code system definition for HL7 v2 table 0161 (Allow Substitution)
Code System URL: | http://hl7.org/fhir/v2/0161
Value Set URL: | http://hl7.org/fhir/ValueSet/v2-0161
OID: | ??

CodeSystem Resource | XML / JSON
ValueSet Resource | XML / JSON

This value set is used in the following places:

* This value set is the designated 'entire code system' value set for v2 Allow Substitution

4.2.13.161.1 Code System Content

Allow Substitution

Code | Description | Deutsch (German) | Nederlands (Dutch) | Comment | Version
G | Allow generic substitutions. | Substitution durch Generika erlaubt | Generieke substituties toegestaan | | added v2.2
N | Substitutions are NOT authorized. (This is the default - null.) | Substitution nicht erlaubt | Substituties NIET geautoriseerd (Standaardwaarde.) | | added v2.2
T | Allow therapeutic substitutions | Therapieorientierte Substitution erlaubt | Therapeutische substituties toegestaan | | added v2.2

4.2.13.162 HL7 Version 2 Table 0162

URL: https://hl7.org/fhir/STU3/v2/0162/index.html

This page is part of the FHIR Specification (v3.0.2: STU 3). The current version which supercedes this version is 4.0.1. For a full list of available versions, see the Directory of published versions

Vocabulary Work Group | Maturity Level: N/A | External | Use Context: Any

This is a table defined as part of HL7 v2 . Related FHIR content: v2 Route of Administration.

Summary

Name: | v2 Route of Administration
Definition: | FHIR Value set/code system definition for HL7 v2 table 0162 (Route of Administration)
Code System URL: | http://hl7.org/fhir/v2/0162
Value Set URL: | http://hl7.org/fhir/ValueSet/v2-0162
OID: | ??
CodeSystem Resource | XML / JSON
ValueSet Resource | XML / JSON

This value set is used in the following places:

* This value set is the designated 'entire code system' value set for v2 Route of Administration

4.2.13.162.1 Code System Content

Route of Administration

Code | Description | Deutsch (German) | Nederlands (Dutch) | Comment | Version
AP | Apply Externally | Externe Applikation | Uitwendig gebruik | | added v2.2
B | Buccal | buccal | Wang | | added v2.2
DT | Dental | dental | Dentaal | | added v2.2
EP | Epidural | epidural | Epiduraal | | added v2.3
ET | Endotrachial Tube* | endotrachialer Schlauch (insbes.f.respirat.Ther.+Anästh.) | Endotrachiale sonde* | used primarily for respiratory therapy and anesthesia delivery | added v2.3
GTT | Gastrostomy Tube | Magenschlauch | Maagsonde | | added v2.2
GU | GU Irrigant | Magenspülung | GU Irrigatiemiddel | | added v2.2
IA | Intra-arterial | Intraarteriell | Intra-arteriaal | | added v2.2
IB | Intrabursal | Intrabursal | Intrabursaal | | added v2.3
IC | Intracardiac | Intracardial | Intracardiaal | | added v2.2
ICV | Intracervical (uterus) | Intracervikal (Uterus) | Intracervicaal (uterus) | | added v2.3
ID | Intradermal | Intradermal | Intradermaal | | added v2.2
IH | Inhalation | Inhalation | Inhalatie | | added v2.2
IHA | Intrahepatic Artery | | Intrahepatische ader | | added v2.3.1
IM | Intramuscular | Intramuskulär | Intramusculair | | added v2.2
IMR | Immerse (Soak) Body Part | | Dompel (Week) lichaamsdeel | | added v2.3
IN | Intranasal | Intranasal | Intranasaal | | added v2.2
IO | Intraocular | Intraokular | Intraoculair | | added v2.2
IP | Intraperitoneal | Intraperitoneal | Intraperitoneaal | | added v2.2
IS | Intrasynovial | Intrasynovial | Intrasynoviaal | | added v2.2
IT | Intrathecal | Intrathekal | Intrathecaal | | added v2.2
IU | Intrauterine | | Intra-uterine | | added v2.3.1
IV | Intravenous | Intravenös | Intraveneus | | added v2.2
MM | Mucous Membrane | Mukosamembran | Slijmvlies | | added v2.3
MTH | Mouth/Throat | | Mond/keel | | added v2.3.1
NG | Nasogastric | Nasogastral | Nasogastrisch | | added v2.2
NP | Nasal Prongs* | Nasenklemme (insbes.f.respirat.Ther.+Anästh.) | Neuskap* | used primarily for respiratory therapy and anesthesia delivery | added v2.3
NS | Nasal | Nasal | Nasaal | | added v2.2
NT | Nasotrachial Tube | | Neussonde | | added v2.3
OP | Ophthalmic | In das Auge | Oculair | | added v2.2
OT | Otic | In das Ohr | Auriculair | | added v2.2

OTH | Other/Miscellaneous | | Anders/overig | | added v2.3
PF | Perfusion | Perfusion | Perfusie | | added v2.3
PO | Oral | Oral | Oraal | | added v2.2
PR | Rectal | Rektal | Rectaal | | added v2.2
RM | Rebreather Mask* | Beatmungsmaske (insbes.f.respirat.Ther.+Anästh.) | Rebreather-masker* | used primarily for respiratory therapy and anesthesia delivery | added v2.3
SC | Subcutaneous | Subkutan | Subcutaan | | added v2.2
SD | Soaked Dressing | | Verzadigde dressing | | added v2.3
SL | Sublingual | Sublingual | Sublinguaal | | added v2.2
TD | Transdermal | Transdermal | Transdermaal | | added v2.2
TL | Translingual | Translingual | Translinguaal | | added v2.2
TP | Topical | Lokal | Topicaal | | added v2.2
TRA | Tracheostomy* | Tracheostomie (insbes.f.respirat.Ther.+Anästh.) | Tracheostomie* | used primarily for respiratory therapy and anesthesia delivery | added v2.3
UR | Urethral | Urethral | Urethraal | | added v2.2
VG | Vaginal | Vaginal | Vaginaal | | added v2.2
VM | Ventimask | | Ventimasker | | added v2.3
WND | Wound | | Wond | | added v2.3

4.2.13.163 HL7 Version 2 Table 0163

URL: https://hl7.org/fhir/STU3/v2/0163/index.html

This page is part of the FHIR Specification (v3.0.2: STU 3). The current version which supercedes this version is 4.0.1. For a full list of available versions, see the Directory of published versions

Vocabulary Work Group | Maturity Level: N/A | External | Use Context: Any

This is a table defined as part of HL7 v2 . Related FHIR content: v2 Body Site.

Summary

Name: | v2 Body Site
Definition: | FHIR Value set/code system definition for HL7 v2 table 0163 (Body Site)
Code System URL: | http://hl7.org/fhir/v2/0163
Value Set URL: | http://hl7.org/fhir/ValueSet/v2-0163
OID: | ??
CodeSystem Resource | XML / JSON
ValueSet Resource | XML / JSON

This value set is used in the following places:

* This value set is the designated 'entire code system' value set for v2 Body Site

4.2.13.163.1 Code System Content

Body Site

Code | Description | Deutsch (German) | Nederlands (Dutch) | Comment | Version
BE | Bilateral Ears | Beide Ohren | Beide oren | | added v2.2
BN | Bilateral Nares | Beide Nasenlöcher | Beide neusgaten | | added v2.2
BU | Buttock | Gesäß | Bil | | added v2.2
CT | Chest Tube | Tubus | Borst slang | | added v2.2
LA | Left Arm | linker Arm | Linker arm | | added v2.2
LAC | Left Anterior Chest | Linker vorderer Thorax | Linker anterior borst | | added v2.2
LACF | Left Antecubital Fossa | Linke Fossa antecubitalis | Linker antecubitale fossa | | added v2.2
LD | Left Deltoid | Linker Deltoideus | Linker deltoideus | | added v2.2
LE | Left Ear | linkes Ohr | Linker oor | | added v2.2
LEJ | Left External Jugular | Linke Vena jugularis externa | Linker uitwendige jugularis | | added v2.2
LF | Left Foot | linker Fuß | Linker voet | | added v2.2
LG | Left Gluteus Medius | Linker Glutäus maximus | Linker glutaeus medius | | added v2.2
LH | Left Hand | linke Hand | Linker hand | | added v2.2
LIJ | Left Internal Jugular | Linke Vena jugularis interna | Linker inwendige jugularis | | added v2.2
LLAQ | Left Lower Abd Quadrant | Linker unterer Quadrant Abdomen | Linker onderste abdomen quadrant | | added v2.2
LLFA | Left Lower Forearm | Linker Unterarm (unten) | Linker onderste onderarm | | added v2.2
LMFA | Left Mid Forearm | Linker Unterarm (Mitte) | Linker mid onderarm | | added v2.2
LN | Left Naris | Linkes Nasenloch | Linker neusgat | | added v2.2
LNB | Nebulized | | Verneveld | deprecated | added v2.3, removed after v2.3
LPC | Left Posterior Chest | Linker hinterer Thorax | Linker posterior borst | | added v2.2
LSC | Left Subclavian | Linke Subclavia | Linker subclavia | | added v2.2
LT | Left Thigh | Linker Oberschenkel | Linker dij | | added v2.2
LUA | Left Upper Arm | Linker Oberarm | Linker bovenarm | | added v2.2
LUAQ | Left Upper Abd Quadrant | Linker oberer Quadrant Abdomen | Linker bovenste abdomen quadrant | | added v2.2
LUFA | Left Upper Forearm | Linker Unterarm (oben) | Linker bovenste onderarm | | added v2.2
LV | Left Vastus Lateralis | | Linker vastus lateralis | deprecated | added v2.3, removed after v2.3
LVG | Left Ventragluteal | Linke Bauch- / Glutealgegend | Linker ventragluteaal | | added v2.2
LVL | Left Vastus Lateralis | Linker Musculus vastus lateralis (Offiziersstreifen) | Linker vastus lateralis | | added v2.2
NB | Nebulized | Vernebelt | Verneveld | | added v2.2

OD | Right Eye | rechtes Auge | Rechter oog | | added v2.2
OS | Left Eye | linkes Auge | Linker oog | | added v2.2
OU | Bilateral Eyes | Beide Augen | Beide ogen | | added v2.2
PA | Perianal | Perianal | Perianaal | | added v2.2
PERIN | Perineal | Perineum / Dammbereich | Perineaal | | added v2.2
RA | Right Arm | Rechter Arm | Rechter arm | | added v2.2
RAC | Right Anterior Chest | Rechter vorderer Thorax | Rechter anterior borst | | added v2.2
RACF | Right Antecubital Fossa | Rechte Fossa antecubitalis | Rechter antecubitale fossa | | added v2.2
RD | Right Deltoid | Rechter Deltoideus | Rechter deltoideus | | added v2.2
RE | Right Ear | Rechtes Ohr | Rechter oor | | added v2.2
REJ | Right External Jugular | Rechte Vena jugularis externa | Rechter uitwendige jugularis | | added v2.2
RF | Right Foot | Rechter Fuß | Rechter voet | | added v2.2
RG | Right Gluteus Medius | Rechter Glutäus maximus | Rechter gluteus medius | | added v2.2
RH | Right Hand | Rechte Hand | Rechter hand | | added v2.2
RIJ | Right Internal Jugular | Rechte Vena jugularis interna | Rechter inwendige jugularis | | added v2.2
RLAQ | Rt Lower Abd Quadrant | Rechter unterer Quadrant Abdomen | Rechter onderste abdomen quadrant | | added v2.2
RLFA | Right Lower Forearm | Rechter Unterarm (unten) | Rechter onderste onderarm | | added v2.2
RMFA | Right Mid Forearm | Rechter Unterarm (Mitte) | Rechter mid onderarm | | added v2.2
RN | Right Naris | Rechtes Nasenloch | Rechter neusgat | | added v2.2
RPC | Right Posterior Chest | Rechter hinterer Thorax | Rechter posterior borst | | added v2.2
RSC | Right Subclavian | Rechte Subclavia | Rechter subclavia | | added v2.2
RT | Right Thigh | Rechter Oberschenkel | Rechter dij | | added v2.2
RUA | Right Upper Arm | Rechter Oberarm | Rechter bovenarm | | added v2.2
RUAQ | Right Upper Abd Quadrant | Rechter oberer Quadrant Abdomen | Rechter bovenste abdomen quadrant | | added v2.2
RUFA | Right Upper Forearm | Rechter Unterarm (oben) | Rechter bovenste onderarm | | added v2.2
RVG | Right Ventragluteal | Rechte Bauch- / Glutealgegend | Rechter ventragluteaal | | added v2.2
RVL | Right Vastus Lateralis | Rechter Musculus vastus lateralis (Offiziersstreifen) | Rechter vastus lateralis | | added v2.2

4.2.13.164 HL7 Version 2 Table 0164

URL: https://hl7.org/fhir/STU3/v2/0164/index.html

This page is part of the FHIR Specification (v3.0.2: STU 3). The current version which supercedes this version is 4.0.1. For a full list of available versions, see the Directory of published versions

Vocabulary Work Group | Maturity Level: N/A | External | Use Context: Any

This is a table defined as part of HL7 v2 . Related FHIR content: v2 Administration Device.

Summary

Name: | v2 Administration Device
Definition: | FHIR Value set/code system definition for HL7 v2 table 0164 (Administration Device)
Code System URL: | http://hl7.org/fhir/v2/0164
Value Set URL: | http://hl7.org/fhir/ValueSet/v2-0164
OID: | ??
CodeSystem Resource | XML / JSON
ValueSet Resource | XML / JSON

This value set is used in the following places:

* This value set is the designated 'entire code system' value set for v2 Administration Device

4.2.13.164.1 Code System Content

Administration Device

Code | Description | Deutsch (German) | Nederlands (Dutch) | Comment | Version
AP | Applicator | Applikator | Applicator | | added v2.2
BT | Buretrol | | Buretrol | | added v2.2
HL | Heparin Lock | Infusionskanüle | Heprine lock | | added v2.2
IPPB | IPPB | Intermittierende Überdruckbeatmung | Intermittent positive pressure breathing | | added v2.2
IVP | IV Pump | Perfusor | Infuuspomp | | added v2.2
IVS | IV Soluset | Infusionsbesteck | Infuus soluset | | added v2.2
MI | Metered Inhaler | Inhalator | Dosis-inhalator | | added v2.2
NEB | Nebulizer | Vernebler | Vernevelaar | | added v2.2
PCA | PCA Pump | Patientengesteuerte Analgesiepumpe | PCA-pomp | | added v2.2

4.2.13.165 HL7 Version 2 Table 0165

URL: https://hl7.org/fhir/STU3/v2/0165/index.html

This page is part of the FHIR Specification (v3.0.2: STU 3). The current version which supercedes this version is 4.0.1. For a full list of available versions, see the Directory of published versions

Vocabulary Work Group | Maturity Level: N/A | External | Use Context: Any

This is a table defined as part of HL7 v2 . Related FHIR content: v2 Administration Method.

Summary

Name: | v2 Administration Method
Definition: | FHIR Value set/code system definition for HL7 v2 table 0165 (Administration Method)
Code System URL: | http://hl7.org/fhir/v2/0165
Value Set URL: | http://hl7.org/fhir/ValueSet/v2-0165
OID: | ??
CodeSystem Resource | XML / JSON
ValueSet Resource | XML / JSON

This value set is used in the following places:

* This value set is the designated 'entire code system' value set for v2 Administration Method

4.2.13.165.1 Code System Content

Administration Method

Code | Description | Deutsch (German) | Nederlands (Dutch) | Comment | Version
CH | Chew | Kauen | Kauwen | | added v2.2
DI | Dissolve | Auflösen | Oplossen | | added v2.2
DU | Dust | Zerstäuben | Poeder | | added v2.2
IF | Infiltrate | Infiltrieren | Infiltratie | | added v2.2
IR | Irrigate | Spülen | Irrigeren | | added v2.2
IS | Insert | Einfügen / einsetzen | Inbrengen | | added v2.2
IVP | IV Push | Intravenöse Spritze | Infuusinjectie | | added v2.2
IVPB | IV Piggyback | IV-Kurzinfusion | Infuus meeliften | | added v2.2
NB | Nebulized | Vernebeln | Verneveld | | added v2.2
PF | Perfuse | Perfundieren | Perfusie | | added v2.2
PT | Paint | Schmerz | Smeren | | added v2.2
SH | Shampoo | Shampoo | Shampoo | | added v2.2
SO | Soak | Aufweichen | Soppen | | added v2.2
WA | Wash | Waschen | Wassen | | added v2.2
WI | Wipe | Wischen | Vegen | | added v2.2

4.2.13.166 HL7 Version 2 Table 0166

URL: https://hl7.org/fhir/STU3/v2/0166/index.html

This page is part of the FHIR Specification (v3.0.2: STU 3). The current version which supercedes this version is 4.0.1. For a full list of available versions, see the Directory of published versions

Vocabulary Work Group | Maturity Level: N/A | External | Use Context: Any

This is a table defined as part of HL7 v2 . Related FHIR content: v2 RX Component Type.

Summary

Name: | v2 RX Component Type
Definition: | FHIR Value set/code system definition for HL7 v2 table 0166 (RX Component Type)
Code System URL: | http://hl7.org/fhir/v2/0166
Value Set URL: | http://hl7.org/fhir/ValueSet/v2-0166
OID: | ??
CodeSystem Resource | XML / JSON
ValueSet Resource | XML / JSON

This value set is used in the following places:

* This value set is the designated 'entire code system' value set for v2 RX Component Type

4.2.13.166.1 Code System Content

RX Component Type

Code | Description | Deutsch (German) | Nederlands (Dutch) | Comment | Version
A | Additive | Additiv | Additief | | added v2.2
B | Base | Basissubstanz | Basis | | added v2.2

4.2.13.167 HL7 Version 2 Table 0167

URL: https://hl7.org/fhir/STU3/v2/0167/index.html

This page is part of the FHIR Specification (v3.0.2: STU 3). The current version which supercedes this version is 4.0.1. For a full list of available versions, see the Directory of published versions

Vocabulary Work Group | Maturity Level: N/A | External | Use Context: Any

This is a table defined as part of HL7 v2 . Related FHIR content: v2 Substitution Status.

Summary

Name: | v2 Substitution Status
Definition: | FHIR Value set/code system definition for HL7 v2 table 0167 (Substitution Status)
Code System URL: | http://hl7.org/fhir/v2/0167
Value Set URL: | http://hl7.org/fhir/ValueSet/v2-0167

OID: | ??
CodeSystem Resource | XML / JSON
ValueSet Resource | XML / JSON

This value set is used in the following places:

* This value set is the designated 'entire code system' value set for v2 Substitution Status

4.2.13.167.1 Code System Content

Substitution Status

Code | Description | Deutsch (German) | Nederlands (Dutch) | Comment | Version
0 | No product selection indicated | | Geen productselectie aangegeven | | added v2.3.1
1 | Substitution not allowed by prescriber | | Substitutie niet toegestaan door voorschrijver | | added v2.3.1
2 | Substitution allowed - patient requested product dispensed | | Substitutie toegestaan - patiënt vroeg om verstrekte product | | added v2.3.1
3 | Substitution allowed - pharmacist selected product dispensed | | Substitutie toegestaan - apotheek selecteerde verstrekte product | | added v2.3.1
4 | Substitution allowed - generic drug not in stock | | Substitutie toegestaan - generieke medicatie niet op voorraad | | added v2.3.1
5 | Substitution allowed - brand drug dispensed as a generic | | Substitutie toegestaan - merkmedicatie verstrekt als generiek | | added v2.3.1
7 | Substitution not allowed - brand drug mandated by law | | Substitutie toegestaan - merkmedicatie wettelijk verplicht | | added v2.3.1
8 | Substitution allowed - generic drug not available in marketplace | | Substitutie toegestaan - generieke medicatie niet beschikbaar op de markt | | added v2.3.1
G | A generic substitution was dispensed. | Substitution durch Generika | Er is een generiek substituut verstrekt | | added v2.2
N | No substitute was dispensed. This is equivalent to the default (null) value. | keine Substitution | Er is geen substituut verstrekt. Dit is de standaardwaarde. | | added v2.2
T | A therapeutic substitution was dispensed. | therapieorientierte Substitution | Er is een therapeutisch substituut verstrekt | | added v2.2

4.2.13.168 HL7 Version 2 Table 0168

URL: https://hl7.org/fhir/STU3/v2/0168/index.html

This page is part of the FHIR Specification (v3.0.2: STU 3). The current version which supercedes this version is 4.0.1. For a full list of available versions, see the Directory of published versions

Vocabulary Work Group | Maturity Level: N/A | External | Use Context: Any

This is a table defined as part of HL7 v2 . Related FHIR content: v2 Processing Priority.

Summary

Name: | v2 Processing Priority
Definition: | FHIR Value set/code system definition for HL7 v2 table 0168 (Processing Priority)
Code System URL: | http://hl7.org/fhir/v2/0168
Value Set URL: | http://hl7.org/fhir/ValueSet/v2-0168
OID: | ??
CodeSystem Resource | XML / JSON
ValueSet Resource | XML / JSON

This value set is used in the following places:

* This value set is the designated 'entire code system' value set for v2 Processing Priority

4.2.13.168.1 Code System Content

Processing Priority

Code | Description | Deutsch (German) | Nederlands (Dutch) | Comment | Version
A | As soon as possible (a priority lower than stat) | schnellsmöglich | Zo snel mogelijk (een prioteit lager dan stat) | | added v2.2
B | Do at bedside or portable (may be used with other codes) | am Patientenbett | Doe aan het bed of mobiele (mag worden gebruikt in combinatie met andere codes) | | added v2.2
C | Measure continuously (e.g. arterial line blood pressure) | kontinuierlich | Meet continu (bijv. arteriële lijn bloeddruk) | | added v2.2
P | Preoperative (to be done prior to surgery) | präoperativ | Preoperatief (doe voorafgaand aan operatie) | | added v2.2
R | Routine | Routine | Routine | | added v2.2
S | Stat (do immediately) | sofort | Stat (doe onmiddellijk) | | added v2.2
T | Timing critical (do as near as possible to requested time) | zum vereinbarten Zeitpunkt | Timing kritiek (doe zo dicht mogelijk op gevraagde tijd) | | added v2.2

4.2.13.169 HL7 Version 2 Table 0169

URL: https://hl7.org/fhir/STU3/v2/0169/index.html

This page is part of the FHIR Specification (v3.0.2: STU 3). The current version which supercedes this version is 4.0.1. For a full list of available versions, see the Directory of published versions

Vocabulary Work Group | Maturity Level: N/A | External | Use Context: Any

This is a table defined as part of HL7 v2 . Related FHIR content: v2 Reporting Priority.

Summary

Name: | v2 Reporting Priority
Definition: | FHIR Value set/code system definition for HL7 v2 table 0169 (Reporting Priority)
Code System URL: | http://hl7.org/fhir/v2/0169

Value Set URL: | http://hl7.org/fhir/ValueSet/v2-0169
OID: | ??
CodeSystem Resource | XML / JSON
ValueSet Resource | XML / JSON

This value set is used in the following places:

* This value set is the designated 'entire code system' value set for v2 Reporting Priority

4.2.13.169.1 Code System Content

Reporting Priority

Code | Description | Deutsch (German) | Nederlands (Dutch) | Comment | Version
C | Call back results | sofortige Übermittlung notwendig | Telefonische terugkoppeling resultaten | | added v2.2
R | Rush reporting | beschleunigte Übermittlung | Haast bij verslag | | added v2.2

4.2.13.170 HL7 Version 2 Table 0170

URL: https://hl7.org/fhir/STU3/v2/0170/index.html

This page is part of the FHIR Specification (v3.0.2: STU 3). The current version which supercedes this version is 4.0.1. For a full list of available versions, see the Directory of published versions

Vocabulary Work Group | Maturity Level: N/A | External | Use Context: Any

This is a table defined as part of HL7 v2 . Related FHIR content: v2 Derived Specimen.

Summary

Name: | v2 Derived Specimen
Definition: | FHIR Value set/code system definition for HL7 v2 table 0170 (Derived Specimen)
Code System URL: | http://hl7.org/fhir/v2/0170
Value Set URL: | http://hl7.org/fhir/ValueSet/v2-0170
OID: | ??
CodeSystem Resource | XML / JSON
ValueSet Resource | XML / JSON

This value set is used in the following places:

* This value set is the designated 'entire code system' value set for v2 Derived Specimen

4.2.13.170.1 Code System Content

Derived Specimen

Code | Description | Deutsch (German) | Nederlands (Dutch) | Comment | Version
C | Child Observation | Untersuchung an sekundärem Probenmaterial | Onderliggende/deel observatie | | added v2.2
N | Not Applicable | Nicht Anwendbar | Niet van toepassing | | added v2.2
P | Parent Observation | Untersuchung an primärem Probenmaterial | Bovenliggende observatie | | added v2.2

4.2.13.173 HL7 Version 2 Table 0173

URL: https://hl7.org/fhir/STU3/v2/0173/index.html

This page is part of the FHIR Specification (v3.0.2: STU 3). The current version which supercedes this version is 4.0.1. For a full list of available versions, see the Directory of published versions

Vocabulary Work Group | Maturity Level: N/A | External | Use Context: Any

This is a table defined as part of HL7 v2 . Related FHIR content: v2 Coordination of Benefits.

Summary

Name: | v2 Coordination of Benefits
Definition: | FHIR Value set/code system definition for HL7 v2 table 0173 (Coordination of Benefits)
Code System URL: | http://hl7.org/fhir/v2/0173
Value Set URL: | http://hl7.org/fhir/ValueSet/v2-0173
OID: | ??
CodeSystem Resource | XML / JSON
ValueSet Resource | XML / JSON

This value set is used in the following places:

* This value set is the designated 'entire code system' value set for v2 Coordination of Benefits

4.2.13.173.1 Code System Content

Coordination of Benefits

Code | Description | Deutsch (German) | Nederlands (Dutch) | Comment | Version
CO | Coordination | koordiniert | Coördinatie | | added v2.2
IN | Independent | unabhängig | Onafhankelijk | | added v2.2

4.2.13.174 HL7 Version 2 Table 0174

URL: https://hl7.org/fhir/STU3/v2/0174/index.html

This page is part of the FHIR Specification (v3.0.2: STU 3). The current version which supercedes this version is 4.0.1. For a full list of available versions, see the Directory of published versions

Vocabulary Work Group | Maturity Level: N/A | External | Use Context: Any

This is a table defined as part of HL7 v2 . Related FHIR content: v2 Nature of Service/Test/Observation.

Summary

Name: | v2 Nature of Service/Test/Observation
Definition: | FHIR Value set/code system definition for HL7 v2 table 0174 (Nature of Service/Test/Observation)
Code System URL: | http://hl7.org/fhir/v2/0174
Value Set URL: | http://hl7.org/fhir/ValueSet/v2-0174
OID: | ??
CodeSystem Resource | XML / JSON
ValueSet Resource | XML / JSON

This value set is used in the following places:

* This value set is the designated 'entire code system' value set for v2 Nature of Service/Test/Observation

4.2.13.174.1 Code System Content

Nature of Service/Test/Observation

Code | Description | Deutsch (German) | Nederlands (Dutch) | Comment | Version
A | Atomic service/test/observation (test code or treatment code) | Einzeluntersuchung | Atomische service/test/observatie (testcode of behandelingcode) | can be associated with one or more OM4 (specimen) segments<p>a single direct observation and would usually be associated with an OM2 and/or OM3 segments | added v2.2
C | Single observation calculated via a rule or formula from other independent observations (e.g. Alveolar-arterial ratio, cardiac output) | Berechnetes Einzelergebnis | Enkelvoudige observatie berekend via regels of formule uit andere onafhankelijke observaties (bijv. Alveolair--arteriële gradiënt, hart-minuut-volume) | can be associated with one or more OM4 (specimen) segments<p>a derived quantity and would usually be associated with an OM6 segment | added v2.2
F | Functional procedure that may consist of one or more interrelated measures (e.g. glucose tolerance test, creatinine clearance), usually done at different times and/or on different specimens | Funktionstest | Functionele behandeling die kan bestaan uit een of meer gerelateerde metingen (bijv. glucosetolerantietest, creatinineklaring), meestal uitgevoerd op verschillende momenten en/of verschillende monsters | can be associated with one or more OM4 (specimen) segments<p>See comment for value S | added v2.2
P | Profile or battery consisting of many independent atomic observations (e.g. SMA12, electrolytes), usually done at one instrument on one specimen | Batterieanordnung | Profiel of battery bestaande uit vele onafhankelijke atomische observaties (bijv. SMA12, electrolyten), meestal met één instrument op één monster | can be associated with one or more OM4 (specimen) segments<p>See comment for value S | added v2.2
S | Superset-a set of batteries or procedures ordered under a single code unit but processed as separate batteries (e.g. routines = CBC, UA, electrolytes)<p>This set indicates that the code being described is used to order multiple service/test/observation b | Latte von mehreren Batterieanforderungen (Aufnahmelatte) | Superset--een set batteries of procedures aangevraagd onder een enkele aanvraagcode maar behandeld als afzonderlijke batteries (bijv. routines = CBC, UA, electrolyten); Deze set geeft aan dat de bedoelde code wordt gebruikt voor het aanvragen van meerdere services/tests/observaties | can be associated with one or more OM4 (specimen) segments<p>Codes P, F, and S identify sets (batteries) and should be associated with an OM5 segment that defines the list of elements. The definitions for the contained elements would have to be sent in o | added v2.2

4.2.13.175 HL7 Version 2 Table 0175

URL: https://hl7.org/fhir/STU3/v2/0175/index.html

This page is part of the FHIR Specification (v3.0.2: STU 3). The current version which supercedes this version is 4.0.1. For a full list of available versions, see the Directory of published versions

Vocabulary Work Group | Maturity Level: N/A | External | Use Context: Any

This is a table defined as part of HL7 v2 . Related FHIR content: v2 Master File Identifier Code.

Summary

Name: | v2 Master File Identifier Code
Definition: | FHIR Value set/code system definition for HL7 v2 table 0175 (Master File Identifier Code)
Code System URL: | http://hl7.org/fhir/v2/0175
Value Set URL: | http://hl7.org/fhir/ValueSet/v2-0175
OID: | ??
CodeSystem Resource | XML / JSON
ValueSet Resource | XML / JSON

This value set is used in the following places:

* This value set is the designated 'entire code system' value set for v2 Master File Identifier Code

4.2.13.175.1 Code System Content

Master File Identifier Code

Code | Description | Deutsch (German) | Nederlands (Dutch) | Comment | Version
CDM | Charge description master file | Leistungskatalog | Tariefomschrijving masterbestand | | added v2.2
CLN | Clinic master file | | Kliniek masterbestand | | added v2.4
CM0 | Clinical study master | | Klinisch onderzoek masterbestand | deprecated | added v2.3, removed after v2.3

CM1 | Clinical study phase master | | Klinisch onderzoeksfases masterbestand | deprecated | added v2.3, removed after v2.3
CM2 | Clinical study Data Schedule Master | | Klinisch onderzoek gegevensschema masterbestand | deprecated | added v2.3, removed after v2.3
CMA | Clinical study with phases and scheduled master file | | Klinisch onderzoek met fases en schema masterbestand | | added v2.3.1
CMB | Clinical study without phases but with scheduled master file | | Klinisch onderzoek zonder fases maar met schema masterbestand | | added v2.3.1
INV | Inventory master file | | Voorraad masterbestand | | added v2.5
LOC | Location master file | | Locatie masterbestand | | added v2.3
MACP | Medicare Approved Coverage Process | | Medicare goedgekeurde dekking proces | This identifies Universal Service Identifier that are approved for an ICD based on the CPT. | added v2.8.2
MLCP | Medicare Limited Coverage Process | | Medicare beperkte dekking proces | This identifies Universal Service Identifiers that are not approved for a CPT code based on an ICD. | added v2.8.2
OM1 | Observation text master file segments (e.g. Lab) | | Observatietekst masterbestand-segmenten (d.w.z. Lab) | deprecated | added v2.2, removed after v2.3
OM1-OM6 | Observation text master file segments (e.g. Lab) | | Observatietekst masterbestand-segmenten (d.w.z. Lab) | deprecated | added v2.3, removed after v2.3
OM2 | Observation text master file segments (e.g. Lab) | | Observatietekst masterbestand-segmenten (d.w.z. Lab) | deprecated | added v2.2, removed after v2.3
OM3 | Observation text master file segments (e.g. Lab) | | Observatietekst masterbestand-segmenten (d.w.z. Lab) | deprecated | added v2.2, removed after v2.3
OM4 | Observation text master file segments (e.g. Lab) | | Observatietekst masterbestand-segmenten (d.w.z. Lab) | deprecated | added v2.2, removed after v2.3
OM5 | Observation text master file segments (e.g. Lab) | | Observatietekst masterbestand-segmenten (d.w.z. Lab) | deprecated | added v2.2, removed after v2.3
OM6 | Observation text master file segments (e.g. Lab) | | Observatietekst masterbestand-segmenten (d.w.z. Lab) | deprecated | added v2.2, removed after v2.3
OMA | Numerical observation master file | | Numeriek observaties masterbestand | | added v2.3.1
OMB | Categorical observation master file | | Categorische observaties masterbestand | | added v2.3.1
OMC | Observation batteries master file | | Observatie-betteries masterbestand | | added v2.3.1
OMD | Calculated observations master file | | Berekende observaties masterbestand | | added v2.3.1
OME | Other Observation/Service Item master file | | Andere observatie/service items masterbestand | | added v2.4
OMM | Mixed type observation master file | | Gemengd type observatie masterbestand | | added v2.8.2
PRA | Practitioner master file | Ärztekatalog | Zorgverleners masterbestand | | added v2.2
STF | Staff master file | Mitarbeiterkatalog | Medewerkers masterbestand | | added v2.2

4.2.13.177 HL7 Version 2 Table 0177

URL: https://hl7.org/fhir/STU3/v2/0177/index.html

This page is part of the FHIR Specification (v3.0.2: STU 3). The current version which supercedes this version is 4.0.1. For a full list of available versions, see the Directory of published versions

Vocabulary Work Group | Maturity Level: N/A | External | Use Context: Any

This is a table defined as part of HL7 v2 . Related FHIR content: v2 Confidentiality Code.

Summary

Name: | v2 Confidentiality Code
Definition: | FHIR Value set/code system definition for HL7 v2 table 0177 (Confidentiality Code)
Code System URL: | http://hl7.org/fhir/v2/0177
Value Set URL: | http://hl7.org/fhir/ValueSet/v2-0177
OID: | ??
CodeSystem Resource | XML / JSON
ValueSet Resource | XML / JSON

This value set is used in the following places:

* This value set is the designated 'entire code system' value set for v2 Confidentiality Code

4.2.13.177.1 Code System Content

Confidentiality Code

Code | Description | Deutsch (German) | Nederlands (Dutch) | Comment | Version
AID | AIDS patient | AIDS-Patient | AIDS-patiënt | | added v2.2
EMP | Employee | Mitarbeiter | Werknemer | | added v2.2
ETH | Alcohol/drug treatment patient | Alkohol-/medikamentenabhängiger Patient | Alcohol-/drugstherapie patiënt | | added v2.2
HIV | HIV(+) patient | HIV-positiver Patient | HIV(+)-patiënt | | added v2.2
PSY | Psychiatric patient | Psychatriepatient | Psychiatrisch patiënt | | added v2.2
R | Restricted | vertraulich | Beperkt | | added v2.2
U | Usual control | normaler Zugriff | Gebruikelijke waarde | | added v2.2
UWM | Unwed mother | unverheiratete Mutter | Ongehuwde moeder | | added v2.2
V | Very restricted | streng vertraulich | Zeer beperkt | | added v2.2
VIP | Very important person or celebrity | VIP | Belangrijk persoon of beroemdheid | | added v2.2

4.2.13.178 HL7 Version 2 Table 0178

URL: https://hl7.org/fhir/STU3/v2/0178/index.html

This page is part of the FHIR Specification (v3.0.2: STU 3). The current version which supercedes this version is 4.0.1. For a full list of available versions, see the Directory of published versions

Vocabulary Work Group | Maturity Level: N/A | External | Use Context: Any

This is a table defined as part of HL7 v2 . Related FHIR content: v2 File Level Event Code.

Summary

Name: | v2 File Level Event Code
Definition: | FHIR Value set/code system definition for HL7 v2 table 0178 (File Level Event Code)
Code System URL: | http://hl7.org/fhir/v2/0178
Value Set URL: | http://hl7.org/fhir/ValueSet/v2-0178
OID: | ??
CodeSystem Resource | XML / JSON
ValueSet Resource | XML / JSON

This value set is used in the following places:

* This value set is the designated 'entire code system' value set for v2 File Level Event Code

4.2.13.178.1 Code System Content

File Level Event Code

Code | Description | Deutsch (German) | Nederlands (Dutch) | Comment | Version
REP | Replace current version of this master file with the version contained in this message | Ersetzen der gesamten Datei | Vervangen huidige versie van dit masterbestand met de versie uit dit bericht | | added v2.2
UPD | Change file records as defined in the record-level event codes for each record that follows | Änderung einzelner Sätze | Wijzigen bestandrecords zoals gedefinieerd in de record-niveau eventscodes voor ieder volgend record | | added v2.2

4.2.13.179 HL7 Version 2 Table 0179

URL: https://hl7.org/fhir/STU3/v2/0179/index.html

This page is part of the FHIR Specification (v3.0.2: STU 3). The current version which supercedes this version is 4.0.1. For a full list of available versions, see the Directory of published versions

Vocabulary Work Group | Maturity Level: N/A | External | Use Context: Any

This is a table defined as part of HL7 v2 . Related FHIR content: v2 Response Level.

Summary

Name: | v2 Response Level
Definition: | FHIR Value set/code system definition for HL7 v2 table 0179 (Response Level)
Code System URL: | http://hl7.org/fhir/v2/0179
Value Set URL: | http://hl7.org/fhir/ValueSet/v2-0179
OID: | ??
CodeSystem Resource | XML / JSON
ValueSet Resource | XML / JSON

This value set is used in the following places:

* This value set is the designated 'entire code system' value set for v2 Response Level

4.2.13.179.1 Code System Content

Response Level

Code | Description | Deutsch (German) | Nederlands (Dutch) | Comment | Version
AL | Always. All MFA segments (whether denoting errors or not) must be returned via the application-level acknowledgment message | Rückmeldung immer erforderlich | Altijd. Alle MFA-segmenten (fouten en/of succes) moeten worden geretourneerd via de applicatieniveau-bevestiging | | added v2.2
ER | Error/Reject conditions only. Only MFA segments denoting errors must be returned via the application-level acknowledgment for this message | Rückmeldung bei auftretenden Fehlern | Alleen bij fout/weigering. Er mogen voor dit bericht alleen MFA-segmenten die fouten aanduiden worden geretourneerd via de applicatieniveau-bevestiging | | added v2.2
NE | Never. No application-level response needed | Keine Rückmeldung erforderlich | Nooit - er is geen antwoord op applicatieniveau nodig | | added v2.2
SU | Success. Only MFA segments denoting success must be returned via the application-level acknowledgment for this message | Rückmeldung bei erfolgreicher Verarbeitung | Alleen bij succes. Er mogen voor dit bericht alleen MFA-segmenten die succes aanduiden worden geretourneerd via de applicatieniveau-bevestiging | | added v2.2

4.2.13.180 HL7 Version 2 Table 0180

URL: https://hl7.org/fhir/STU3/v2/0180/index.html

This page is part of the FHIR Specification (v3.0.2: STU 3). The current version which supercedes this version is 4.0.1. For a full list of available versions, see the Directory of published versions

Vocabulary Work Group | Maturity Level: N/A | External | Use Context: Any

This is a table defined as part of HL7 v2 . Related FHIR content: v2 Record-level Event Code.

Summary

Name: | v2 Record-level Event Code
Definition: | FHIR Value set/code system definition for HL7 v2 table 0180 (Record-level Event Code)
Code System URL: | http://hl7.org/fhir/v2/0180
Value Set URL: | http://hl7.org/fhir/ValueSet/v2-0180
OID: | ??
CodeSystem Resource | XML / JSON
ValueSet Resource | XML / JSON

This value set is used in the following places:

* This value set is the designated 'entire code system' value set for v2 Record-level Event Code

4.2.13.180.1 Code System Content

Record-level Event Code

Code | Description | Deutsch (German) | Nederlands (Dutch) | Comment | Version
MAC | Reactivate deactivated record | Datensatz wieder aktivieren | Reactiveren van gedeactiveerd record | | added v2.2
MAD | Add record to master file | Datensatz hinzufügen | Toevoegen aan masterbestand | | added v2.2
MDC | Deactivate: discontinue using record in master file, but do not delete from database | Datensatz inaktivieren, aber nicht löschen | Deactiveren - stop gebruik van record in masterbestand, maar niet verwijderen uit database | | added v2.2
MDL | Delete record from master file | Datensatz löschen | Verwijderen uit masterbestand | | added v2.2
MUP | Update record for master file | Datensatz ändern | Updaten in masterbestand | | added v2.2

4.2.13.181 HL7 Version 2 Table 0181

URL: https://hl7.org/fhir/STU3/v2/0181/index.html

This page is part of the FHIR Specification (v3.0.2: STU 3). The current version which supercedes this version is 4.0.1. For a full list of available versions, see the Directory of published versions

Vocabulary Work Group | Maturity Level: N/A | External | Use Context: Any

This is a table defined as part of HL7 v2 . Related FHIR content: v2 MFN Record-level Error Return.

Summary

Name: | v2 MFN Record-level Error Return
Definition: | FHIR Value set/code system definition for HL7 v2 table 0181 (MFN Record-level Error Return)
Code System URL: | http://hl7.org/fhir/v2/0181
Value Set URL: | http://hl7.org/fhir/ValueSet/v2-0181
OID: | ??
CodeSystem Resource | XML / JSON
ValueSet Resource | XML / JSON

This value set is used in the following places:

* This value set is the designated 'entire code system' value set for v2 MFN Record-level Error Return

4.2.13.181.1 Code System Content

MFN Record-level Error Return

Code | Description | Deutsch (German) | Nederlands (Dutch) | Comment | Version
S | Successful posting of the record defined by the MFE segment | Erfolgreiche Übernahme des Datensatzes | Succesvolle verzending van het gedefinieerde record in het MFE-segment | | added v2.2
U | Unsuccessful posting of the record defined by the MFE segment | Übernahme des Datensatzes nicht erfolgreich | Niet-succesvolle verzending van het gedefinieerde record in het MFE-segment | | added v2.2

4.2.13.183 HL7 Version 2 Table 0183

URL: https://hl7.org/fhir/STU3/v2/0183/index.html

This page is part of the FHIR Specification (v3.0.2: STU 3). The current version which supercedes this version is 4.0.1. For a full list of available versions, see the Directory of published versions

Vocabulary Work Group | Maturity Level: N/A | External | Use Context: Any

This is a table defined as part of HL7 v2 . Related FHIR content: v2 Active/Inactive.

Summary

Name: | v2 Active/Inactive
Definition: | FHIR Value set/code system definition for HL7 v2 table 0183 (Active/Inactive)
Code System URL: | http://hl7.org/fhir/v2/0183
Value Set URL: | http://hl7.org/fhir/ValueSet/v2-0183
OID: | ??
CodeSystem Resource | XML / JSON
ValueSet Resource | XML / JSON

This value set is used in the following places:

* This value set is the designated 'entire code system' value set for v2 Active/Inactive

4.2.13.183.1 Code System Content

Active/Inactive

Code | Description | Deutsch (German) | Nederlands (Dutch) | Comment | Version
A | Active Staff | Aktiver Mitarbeiter | Actieve medewerker | | added v2.2
I | Inactive Staff | Inaktiver / beurlaubter Mitarbeiter | Inactieve medewerker | | added v2.2

4.2.13.185 HL7 Version 2 Table 0185

URL: https://hl7.org/fhir/STU3/v2/0185/index.html

This page is part of the FHIR Specification (v3.0.2: STU 3). The current version which supercedes this version is 4.0.1. For a full list of available versions, see the Directory of published versions

Vocabulary Work Group | Maturity Level: N/A | External | Use Context: Any

This is a table defined as part of HL7 v2 . Related FHIR content: v2 Preferred Method of Contact.

Summary

Name: | v2 Preferred Method of Contact
Definition: | FHIR Value set/code system definition for HL7 v2 table 0185 (Preferred Method of Contact)
Code System URL: | http://hl7.org/fhir/v2/0185
Value Set URL: | http://hl7.org/fhir/ValueSet/v2-0185
OID: | ??
CodeSystem Resource | XML / JSON
ValueSet Resource | XML / JSON

This value set is used in the following places:

* This value set is the designated 'entire code system' value set for v2 Preferred Method of Contact

4.2.13.185.1 Code System Content

Preferred Method of Contact

Code | Description | Deutsch (German) | Nederlands (Dutch) | Comment | Version
B | Beeper Number | Beeper | Beeper-nummer | | added v2.2
C | Cellular Phone Number | Handy | Mobiele telefoonnummer | | added v2.2
E | E-Mail Address (for backward compatibility) | E-Mail-Adresse | E-mailadres (alleen voor backward compatibiliteit) | | added v2.2
F | FAX Number | Fax | Faxnummer | | added v2.2
H | Home Phone Number | private Telefonnummer | Privé telefoonnummer | | added v2.2
O | Office Phone Number | Dienstliche Telefonnummer | Werk telefoonnummer | | added v2.2

4.2.13.187 HL7 Version 2 Table 0187

URL: https://hl7.org/fhir/STU3/v2/0187/index.html

This page is part of the FHIR Specification (v3.0.2: STU 3). The current version which supercedes this version is 4.0.1. For a full list of available versions, see the Directory of published versions

Vocabulary Work Group | Maturity Level: N/A | External | Use Context: Any

This is a table defined as part of HL7 v2 . Related FHIR content: v2 Provider Billing.

Summary

Name: | v2 Provider Billing
Definition: | FHIR Value set/code system definition for HL7 v2 table 0187 (Provider Billing)
Code System URL: | http://hl7.org/fhir/v2/0187
Value Set URL: | http://hl7.org/fhir/ValueSet/v2-0187
OID: | ??
CodeSystem Resource | XML / JSON
ValueSet Resource | XML / JSON

This value set is used in the following places:

* This value set is the designated 'entire code system' value set for v2 Provider Billing

4.2.13.187.1 Code System Content

Provider Billing

Code | Description | Deutsch (German) | Nederlands (Dutch) | Comment | Version
I | Institution bills for provider | Haus rechnet ab | Instelling doet facturatie voor zorgverlener | | added v2.2
P | Provider does own billing | Eigene Abrechnung | Zorgverlener doet eigen facturatie | | added v2.2

4.2.13.189 HL7 Version 2 Table 0189

URL: https://hl7.org/fhir/STU3/v2/0189/index.html

This page is part of the FHIR Specification (v3.0.2: STU 3). The current version which supercedes this version is 4.0.1. For a full list of available versions, see the Directory of published versions

Vocabulary Work Group | Maturity Level: N/A | External | Use Context: Any

This is a table defined as part of HL7 v2 . Related FHIR content: v2 Ethnic Group.

Summary

Name: | v2 Ethnic Group
Definition: | FHIR Value set/code system definition for HL7 v2 table 0189 (Ethnic Group)
Code System URL: | http://hl7.org/fhir/v2/0189
Value Set URL: | http://hl7.org/fhir/ValueSet/v2-0189
OID: | ??
CodeSystem Resource | XML / JSON
ValueSet Resource | XML / JSON

This value set is used in the following places:

* This value set is the designated 'entire code system' value set for v2 Ethnic Group

4.2.13.189.1 Code System Content

Ethnic Group

Code | Description | Nederlands (Dutch) | Comment | Version
H | Hispanic or Latino | Hispanic of Latino | | added v2.4
N | Not Hispanic or Latino | Niet hispanic of Latino | | added v2.4
U | Unknown | Onbekend | | added v2.4

4.2.13.190 HL7 Version 2 Table 0190

URL: https://hl7.org/fhir/STU3/v2/0190/index.html

This page is part of the FHIR Specification (v3.0.2: STU 3). The current version which supercedes this version is 4.0.1. For a full list of available versions, see the Directory of published versions

Vocabulary Work Group | Maturity Level: N/A | External | Use Context: Any

This is a table defined as part of HL7 v2 . Related FHIR content: v2 Address Type.

Summary

Name: | v2 Address Type
Definition: | FHIR Value set/code system definition for HL7 v2 table 0190 (Address Type)
Code System URL: | http://hl7.org/fhir/v2/0190
Value Set URL: | http://hl7.org/fhir/ValueSet/v2-0190
OID: | ??
CodeSystem Resource | XML / JSON
ValueSet Resource | XML / JSON

Concept Maps for this value set:

from AddressUse | v2 map for AddressUse | XML | JSON

This value set is used in the following places:

* This value set is the designated 'entire code system' value set for v2 Address Type

* This value set is the target of translations in the ConceptMap v2 map for AddressUse

4.2.13.190.1 Code System Content

Address Type

Code | Description | Deutsch (German) | Nederlands (Dutch) | Comment | Version
B | Firm/Business | Firma/Geschäft | Bedrijf/zakelijk | Refers to an address specific to an organization, such as an insurance company or employer, versus an individual's work location or place of employment. It would be specific to a firm or organization that has some sort of business relationship with the su | added v2.2
BA | Bad address | | Incorrect adres | Retained for backward compatibility only as of v2.6. Refer to XAD.17 | added v2.3.1
BDL | Birth delivery location (address where birth occurred) | genauer Geburtsort | Ter-wereld-komst locatie (adres waar geboorte plaatsvond) | Refers to the address where birth occurred. | added v2.3.1
BI | Billing Address | | Facturatieadres | May also be used for the validation/authorization of credit cards | added v2.6
BR | Residence at birth (home address at time of birth) | Wohnort zum Zeitpunkt der Geburt | Verblijfplaats bij geboorte (woonadres op moment van geboorte) | Refers to the home address at time of birth. | added v2.3.1
C | Current Or Temporary | Derzeitige Adresse | Huidig of tijdelijk | Retained for backward compatibility only as of v2.6. Refer to XAD.16 | added v2.2
F | Country Of Origin | Herkunftsland | Land van herkomst | | added v2.3
H | Home | Privatadresse | Huis | Refers to a residence or domicile, literally the place where the subject resides the majority of the time. Generally speaking most people will have a home address and it will represent their primary address. Home address is mutually exclusive of permanent | added v2.2
L | Legal Address | registrierte Adresse | Wettelijk adres | Refers to a special case address specific to the status of a subject or legal action involving the subject. For example, prisoners being treated at a healthcare facility may have home addresses, but their status mandates an address specific to their place | added v2.3.1
M | Mailing | Postalische Adresse | Post | Retained for backward compatibility only as of v2.6. Refer to XAD.18 | added v2.2
N | Birth (nee) (birth address, not otherwise specified) | | Geboorte (geboorteadres, tenzij anders gespecificeerd) | Refers to the birth address, not otherwise specified | added v2.3.1
O | Office/Business | Büroadresse | Kantoor/zakelijk | Refers to a work address specific to the subject. | added v2.2

P | Permanent | Dauernder Wohnsitz | Permanent | Refers to a place where the residents know the subject and where correspondence addressed to the subject will eventually reach the subject regardless of their physical location. A permanent address generally reflects a tax jurisdiction. Members of the mi | added v2.2

RH | Registry home. Refers to the information system, typically managed by a public health agency, that stores patient information such as immunization histories or cancer data, regardless of where the patient obtains services. | | Registertehuis | Refers to the information system, typically managed by a public health agency that stores patient information such as immunization histories or cancer data, regardless of where the patient obtains services | added v2.3.1

S | Service Location | | Servicelocatie | Refers to the location in which service is rendered. This would be used if reimbursement is based on the location of the service (to take into account the cost of those services). | added v2.6

SH | Shipping Address | | Verzendadres | | added v2.6

TM | Tube Address | | Buisadres | Pneumatic tube address (to which letters may be sent). A special transport system to transport small samples/containers and/or normal mail in small carriages on rail or in a tube. (German Rohrpost) | added v2.7

V | Vacation | | Vakantie | | added v2.6

4.2.13.191 HL7 Version 2 Table 0191

URL: https://hl7.org/fhir/STU3/v2/0191/index.html

This page is part of the FHIR Specification (v3.0.2: STU 3). The current version which supercedes this version is 4.0.1. For a full list of available versions, see the Directory of published versions

Vocabulary Work Group | Maturity Level: N/A | External | Use Context: Any

This is a table defined as part of HL7 v2 . Related FHIR content: v2 Type of Referenced Data.

Summary

Name: | v2 Type of Referenced Data
Definition: | FHIR Value set/code system definition for HL7 v2 table 0191 (Type of Referenced Data)
Code System URL: | http://hl7.org/fhir/v2/0191
Value Set URL: | http://hl7.org/fhir/ValueSet/v2-0191
OID: | ??
CodeSystem Resource | XML / JSON
ValueSet Resource | XML / JSON

This value set is used in the following places:

* This value set is the designated 'entire code system' value set for v2 Type of Referenced Data

4.2.13.191.1 Code System Content

Type of Referenced Data

Code | Description | Deutsch (German) | Nederlands (Dutch) | Comment | Version

AP | Other application data, typically uninterpreted binary data (HL7 V2.3 and later) | sonstige (binären) Daten | Overige applicatiegegevens, meestal niet-verwerkte binaire gegevens (sinds v2.3) | | added v2.3

Application | Other application data, typically uninterpreted binary data (HL7 V2.3 and later) | | Overige applicatiegegevens, meestal niet-verwerkte binaire gegevens (sinds v2.3) | deprecated | added v2.3.1, removed after v2.3.1

AU | Audio data (HL7 V2.3 and later) | Audio-Daten | Audiogegevens (sinds v2.3) | | added v2.3

Audio | Audio data (HL7 V2.3 and later) | | Audiogegevens (sinds v2.3) | deprecated | added v2.3.1, removed after v2.3.1

FT | Formatted text (HL7 V2.2 only) | Formatierter Text | Tekst met opmaak (alleen v2.2) | | added v2.2

IM | Image data (HL7 V2.3 and later) | Bilddaten | Beeldgegevens (sinds v2.3) | | added v2.3

Image | Image data (HL7 V2.3 and later) | | Beeldgegevens (sinds v2.3) | deprecated | added v2.3.1, removed after v2.3.1

multipart | MIME multipart package | | MIME multipart package | | added v2.4

NS | Non-scanned image (HL7 V2.2 only) | Nicht über Scanner erzeugtes Bild | Niet-gescand beeld (alleen v2.2) | | added v2.2

SD | Scanned document (HL7 V2.2 only) | Über Scanner eingelesenes Dokument | Gescand document (alleen v2.2) | | added v2.2

SI | Scanned image (HL7 V2.2 only) | Über Scanner eingelesenes Bild | Gescand beeld (alleen v2.2) | | added v2.2

TEXT | Machine readable text document (HL7 V2.3.1 and later) | | Geautomatiseerd leesbaar tekstdocument (sinds v2.3.1) | | added v2.3.1

TX | Machine readable text document (HL7 V2.2 only) | Maschinenlesbarer Text | Geautomatiseerd leesbaar tekstdocument (alleen v2.2) | | added v2.2

4.2.13.193 HL7 Version 2 Table 0193

URL: https://hl7.org/fhir/STU3/v2/0193/index.html

This page is part of the FHIR Specification (v3.0.2: STU 3). The current version which supercedes this version is 4.0.1. For a full list of available versions, see the Directory of published versions

Vocabulary Work Group | Maturity Level: N/A | External | Use Context: Any

This is a table defined as part of HL7 v2 . Related FHIR content: v2 Amount Class.

Summary

Name: | v2 Amount Class
Definition: | FHIR Value set/code system definition for HL7 v2 table 0193 (Amount Class)
Code System URL: | http://hl7.org/fhir/v2/0193
Value Set URL: | http://hl7.org/fhir/ValueSet/v2-0193
OID: | ??
CodeSystem Resource | XML / JSON
ValueSet Resource | XML / JSON

This value set is used in the following places:

* This value set is the designated 'entire code system' value set for v2 Amount Class

4.2.13.193.1 Code System Content

Amount Class

Code | Description | Deutsch (German) | Nederlands (Dutch) | Comment | Version
AT | Amount | Betrag | Bedrag | Retained for backward compatibility only as of v 2.5 | added v2.2
LM | Limit | Höchstbetrag | Limiet | | added v2.2
PC | Percentage | Prozentsatz | Percentage | Retained for backward compatibility only as of v 2.5 | added v2.2
UL | Unlimited | Unbegrenzt | Onbeperkt | | added v2.2

4.2.13.200 HL7 Version 2 Table 0200

URL: https://hl7.org/fhir/STU3/v2/0200/index.html

This page is part of the FHIR Specification (v3.0.2: STU 3). The current version which supercedes this version is 4.0.1. For a full list of available versions, see the Directory of published versions

Vocabulary Work Group | Maturity Level: N/A | External | Use Context: Any

This is a table defined as part of HL7 v2 . Related FHIR content: v2 Name Type.

Summary

Name: | v2 Name Type
Definition: | FHIR Value set/code system definition for HL7 v2 table 0200 (Name Type)
Code System URL: | http://hl7.org/fhir/v2/0200
Value Set URL: | http://hl7.org/fhir/ValueSet/v2-0200
OID: | ??
CodeSystem Resource | XML / JSON
ValueSet Resource | XML / JSON

Concept Maps for this value set:

from NameUse | v2 map for NameUse | XML | JSON

This value set is used in the following places:

* This value set is the designated 'entire code system' value set for v2 Name Type
* This value set is the target of translations in the ConceptMap v2 map for NameUse

4.2.13.200.1 Code System Content

Name Type

Code | Description | Deutsch (German) | Nederlands (Dutch) | Comment | Version
... | | | | added v2.8.2
A | Assigned | Aliasname | Toegekend | A name assigned to a person. Reasons some organizations assign alternate names may include not knowing the person's name, or to maintain anonymity. Some, but not necessarily all, of the name types that people call "alias" may fit into this category. | added v2.3
B | Birth name | Geburtsname | Geboortenaam | A name that a person had shortly after being born. Usually for family names but may be used to mark given names at birth that may have changed later.<p>This is not for temporary names assigned at birth while a newborn is not yet named | added v2.3.1
BAD | Bad Name | | Incorrecte naam | A name that was wrongly used in the past and is now maintained only for the purposes of searching | added v2.7
C | Adopted Name | angenommener Name | Adoptienaam | A name acquired by adoption | added v2.3
D | Customary Name | angezeigter Name | Reguliere naam | Known as/conventional/the one you use. May also be known asa preferred name. | added v2.3
F | Fathers Name | | Vaders' naam | Fathers Name (Patronymic Name) | added v2.8
I | Licensing Name | nicht verwendet | Licentienaam | | added v2.4
K | Business name | Künstler- oder Ordensname | Zakelijke naam | A name used in a Professional or Business context. Also includes writer's pseudonym, artist's name, stage name, street name, etc.<p>An example of use is where a person with multiple proper names (i.e. married) uses one of the particular names in a profess | added v2.6
L | Official Registry Name | gesetzlicher Name | Officieel geregistreerde naam | The formal name as registered in an official (government) registry, but which name might not be commonly used. May correspond to legal name<p>For many people, customary name is also their official name | added v2.3
M | Maiden Name | Name als ledige Person (Ledigenname) | Eigennaam | A name you had just before you got married | added v2.3
MSK | Masked | | Gemaskeerd | There is information on this item available but it has not been provided by the sender due to security, privacy or other reasons. There may be an alternate mechanism for gaining access to this information.<p>Note: using this null flavor does provide infor | added v2.7
N | Nickname | Spitzname | Bijnaam | Nickname /"Call me" Name/Street Name | added v2.4
NAV | Temporarily Unavailable | | Tijdelijk niet beschikbaar | Information is not available at this time but it is expected that it will be available later.<p>Includes John or Jane Doe situations | added v2.7
NB | Newborn Name | | Naam nieuwgeborene | A name assigned on a temporary basis at birth. i.e. "Baby of Smith" | added v2.7
NOUSE | No Longer To Be Used | | Niet langer gebruiken | Name not to be used anymore for personal reasons | added v2.7
O | Other | sonstiger Name | Anders | deprecated | added v2.3, removed after v2.3
P | Name of Partner/Spouse | nicht verwendet | Naam van partner/echtgenoot | Retained for backward compatibility only as of v2.7. | added v2.3.1
R | Registered Name | Zuchtname bei Tieren | Geregistreerde naam | (animals only)<p>Retained for backwards compatibility only as of v2.7. Use "L" instead - has same meaning | added v2.4

REL | Religious | | Religieus | e.g. Sister Mary Francis, Brother John | added v2.7
S | Pseudonym | Pseudonym (z.B. für Studien) | Pseudoniem | Coded Pseudo-Name to ensure anonymity | added v2.3.1
T | Indigenous/Tribal | Stammesname | Inheemse-/tribae naam | Indigenous/Tribal/Community Name e.g. Chief Red Cloud | added v2.3.1
TEMP | Temporary Name | | Tijdelijke naam | A temporary name. Note that a name valid time can provide more detailed information. | added v2.7
U | Unknown | sonstiger Name | Onbekend | Unknown | added v2.3.1

4.2.13.201 HL7 Version 2 Table 0201

URL: https://hl7.org/fhir/STU3/v2/0201/index.html

This page is part of the FHIR Specification (v3.0.2: STU 3). The current version which supercedes this version is 4.0.1. For a full list of available versions, see the Directory of published versions

Vocabulary Work Group | Maturity Level: N/A | External | Use Context: Any

This is a table defined as part of HL7 v2 . Related FHIR content: v2 Telecommunication Use Code.

Summary

Name: | v2 Telecommunication Use Code
Definition: | FHIR Value set/code system definition for HL7 v2 table 0201 (Telecommunication Use Code)
Code System URL: | http://hl7.org/fhir/v2/0201
Value Set URL: | http://hl7.org/fhir/ValueSet/v2-0201
OID: | ??
CodeSystem Resource | XML / JSON
ValueSet Resource | XML / JSON

Concept Maps for this value set:

from ContactPointUse | v2 map for ContactPointUse | XML | JSON

This value set is used in the following places:

* This value set is the designated 'entire code system' value set for v2 Telecommunication Use Code

* This value set is the target of translations in the ConceptMap v2 map for ContactPointUse

4.2.13.201.1 Code System Content

Telecommunication Use Code

Code | Description | Deutsch (German) | Nederlands (Dutch) | Comment | Version
ASN | Answering Service Number | Auftragsdienst | Antwoorddienstnummer | | added v2.3
BPN | Beeper Number | Pagernummer (Cityruf o.ä.) | Beeper-nummer | Retained for backward compatibility as of v 2.6 | added v2.3.1
EMR | Emergency Number | Notfallnummer | Noodnummer | | added v2.3
NET | Network (email) Address | Netzwerkadresse (E-Mail) | Netwerk (e-mail)adres | Retained for backward compatibility as of v 2.6 | added v2.3
ORN | Other Residence Number | Nebenwohnsitznummer | Ander privénummer | | added v2.3
PRN | Primary Residence Number | Hauptwohnsitznummer | Primair privénummer | | added v2.3
PRS | Personal | | Persoonlijk | Not tied to a location or role | added v2.6
VHN | Vacation Home Number | Ferienwohnsitznummer | Vakantie privénummer | | added v2.3
WPN | Work Number | Dienstnummer | Zakelijk nummer | | added v2.3

4.2.13.202 HL7 Version 2 Table 0202

URL: https://hl7.org/fhir/STU3/v2/0202/index.html

This page is part of the FHIR Specification (v3.0.2: STU 3). The current version which supercedes this version is 4.0.1. For a full list of available versions, see the Directory of published versions

Vocabulary Work Group | Maturity Level: N/A | External | Use Context: Any

This is a table defined as part of HL7 v2 . Related FHIR content: v2 Telecommunication Equipment Type.

Summary

Name: | v2 Telecommunication Equipment Type
Definition: | FHIR Value set/code system definition for HL7 v2 table 0202 (Telecommunication Equipment Type)
Code System URL: | http://hl7.org/fhir/v2/0202
Value Set URL: | http://hl7.org/fhir/ValueSet/v2-0202
OID: | ??
CodeSystem Resource | XML / JSON
ValueSet Resource | XML / JSON

Concept Maps for this value set:

from ContactPointSystem | v2 map for ContactPointSystem | XML | JSON

This value set is used in the following places:

* This value set is the designated 'entire code system' value set for v2 Telecommunication Equipment Type

* This value set is the target of translations in the ConceptMap v2 map for ContactPointSystem

4.2.13.202.1 Code System Content

Telecommunication Equipment Type

Code | Description | Deutsch (German) | Nederlands (Dutch) | Comment | Version
BP | Beeper | Beeper/Pager | Beeper | | added v2.3
CP | Cellular or Mobile Phone | Mobiltelephon | Mobiel | | added v2.3
FX | Fax | Fax | Fax | | added v2.3
Internet | Internet Address | Internet | Internetadres | | added v2.3
MD | Modem | Modem | Modem | | added v2.3
PH | Telephone | Telephon | Telefoon | | added v2.3
SAT | Satellite Phone | | Satelliettelefoon | | added v2.6
TDD | Telecommunications Device for the Deaf | | Telecommunicatie-apparaat voor doven | | added v2.5
TTY | Teletypewriter | | Teletypewriter | | added v2.5
X.400 | X.400 email address | X.400-Nummer | X.400 e-mailadres | | added v2.3

4.2.13.203 HL7 Version 2 Table 0203

URL: https://hl7.org/fhir/STU3/v2/0203/index.html

This page is part of the FHIR Specification (v3.0.2: STU 3). The current version which supercedes this version is 4.0.1. For a full list of available versions, see the Directory of published versions

Vocabulary Work Group | Maturity Level: N/A | External | Use Context: Any

This is a table defined as part of HL7 v2 . Related FHIR content: v2 Identifier Type.

Summary

Name: | v2 Identifier Type
Definition: | FHIR Value set/code system definition for HL7 v2 table 0203 (Identifier Type)
Code System URL: | http://hl7.org/fhir/v2/0203
Value Set URL: | http://hl7.org/fhir/ValueSet/v2-0203
OID: | ??
CodeSystem Resource | XML / JSON
ValueSet Resource | XML / JSON

This value set is used in the following places:

* This value set is the designated 'entire code system' value set for v2 Identifier Type

4.2.13.203.1 Code System Content

Identifier Type

Code | Description | Deutsch (German) | Nederlands (Dutch) | Comment | Version
ACSN | Accession ID | | Accession ID | Accession Identifier | added v2.7
AM | American Express | American Express | American Express | Deprecated and replaced by BC in v 2.5. | added v2.3
AMA | American Medical Association Number | | American Medical Association nummer | A physician identifier assigned by the AMA. | added v2.6
AN | Account number | Kontonummer | Accountnummer | An identifier that is unique to an account. | added v2.3
An identifier for a provi | | | | deprecated | added v2.7.1, removed after v2.7.1
An Identifier for a provider a | | | | | added v2.8
An identifier for a provider r | | | | | added v2.8
ANC | Account number Creditor | | Accountnummer crediteur | Class: Financial<p>A more precise definition of an account number: sometimes two distinct account numbers must be transmitted in the same message, one as the creditor, the other as the debitor.<p>Kreditorenkontonummer | added v2.5
AND | Account number debitor | | Accountnummer debiteur | Class: Financial<p>A more precise definition of an account number: sometimes two distinct account numbers must be transmitted in the same message, one as the creditor, the other as the debitor.<p>Debitorenkontonummer | added v2.5
ANON | Anonymous identifier | | Anonieme identificatie | An identifier for a living subject whose real identity is protected or suppressed<p>Justification: For public health reporting purposes, anonymous identifiers are occasionally used for protecting patient identity in reporting certain results. For instance | added v2.5
ANT | Temporary Account Number | | Tijdelijk accountnummer | Class: Financial<p>Temporary version of an Account Number.<p>Use Case: An ancillary system that does not normally assign account numbers is the first time to register a patient. This ancillary system will generate a temporary account number that will only | added v2.5
APRN | Advanced Practice Registered Nurse number | | | An identifier that is unique to an advanced practice registered nurse within the jurisdiction of a certifying board | added v2.5
ASID | Ancestor Specimen ID | | Oorspronkelijk monster ID | A unique identifier for the ancestor specimen. All child, grandchild, etc. specimens of the ancestor specimen share the same Ancestor Specimen ID. | added v2.7
BA | Bank Account Number | | Bankrekeningnummer | Class: Financial | added v2.4
BC | Bank Card Number | | Bankrekeningnummer | Class: Financial<p>An identifier that is unique to a person's bank card. Replaces AM, DI, DS, MS, and VS beginning in v 2.5. | added v2.5
BCT | Birth Certificate | | Geboortecertificaat | A number associated with a document identifying the event of a person's birth. | added v2.6
BR | Birth registry number | Geburtsregisternummer | Geboorteregister-nummer | An identifier unique within the Assigning Authority that is the official legal record of a person's birth. | added v2.3
BRN | Breed Registry Number | | Dierenras-registernummer | | added v2.4
BSNR | Primary physician office number | | Primair zorgverlenerpraktijknummer | Betriebsstättennummer - for use in the German realm. | added v2.7
CC | Cost Center number | | Kostenplaatsnummer | Class: Financial<p>Use Case: needed especially for transmitting information about invoices. | added v2.5
CONM | Change of Name Document | | Naamswijzigingdocument | A number associated with a document identifying a person's legal change of name. | added v2.6
CY | County number | | County-nummer | | added v2.5

CZ | Citizenship Card | | Staatsburgerschapkaart | A number assigned by a person's country of residence to identify a person's citizenship. | added v2.6

DDS | Dentist license number | | Tandarts licentienummer | An identifier that is unique to a dentist within the jurisdiction of the licensing board | added v2.5

DEA | Drug Enforcement Administration registration number | | Amerikaanse Drug Enforcement Administration registratienummer | An identifier for an individual or organization relative to controlled substance regulation and transactions.<p>Use case: This is a registration number that identifies an individual or organization relative to controlled substance regulation and transacti | added v2.5

DFN | Drug Furnishing or prescriptive authority Number | | Medicatieverstrekker of voorschrijver autoriteitnummer | An identifier issued to a health care provider authorizing the person to write drug orders<p>Use Case: A nurse practitioner has authorization to furnish or prescribe pharmaceutical substances; this identifier is in component 1. | added v2.5

DI | Diner's Club card | Diners Club | Diner's Club | Deprecated and replaced by BC in v 2.5. | added v2.3

DL | Driver's license number | Führerscheinnummer | Rijbewijsnummer | | added v2.3

DN | Doctor number | Arztnummer | Artsnummer | | added v2.3

DO | Osteopathic License number | | Osteopatisch licentienummer | An identifier that is unique to an osteopath within the jurisdiction of a licensing board. | added v2.5

DP | Diplomatic Passport | | Diplomatiek paspoort | A number assigned to a diplomatic passport. | added v2.6

DPM | Podiatrist license number | | Podoloog licentienummer | An identifier that is unique to a podiatrist within the jurisdiction of the licensing board. | added v2.5

DR | Donor Registration Number | | Donorregistratienummer | | added v2.4

DS | Discover Card | Discover Card | Discover kaart | Deprecated and replaced by BC in v 2.5. | added v2.3

EI | Employee number | Arbeitnehmernummer | Werknemernummer | A number that uniquely identifies an employee to an employer. | added v2.3

EN | Employer number | Arbeitgebernummer | Werkgevernummer | | added v2.3

ESN | Staff Enterprise Number | | Medewerker bedrijfsnummer | An identifier that is unique to a staff member within an enterprise (as identified by the Assigning Authority). | added v2.6

FI | Facility ID | | Afdeling-ID | | added v2.3.1

GI | Guarantor internal identifier | interne ID des Zahlungspflichtigen | Interne garantsteller identificatie | Class: Financial | added v2.3

GL | General ledger number | | Grootboeknummer | Class: Financial | added v2.5

GN | Guarantor external identifier | externe ID des Zahlungspflichtigen | Externe garantsteller identificatie | Class: Financial | added v2.3

HC | Health Card Number | | Gezondheidskaartnummer | | added v2.4

IND | Indigenous/Aboriginal | | Inheems/Aboriginal | A number assigned to a member of an indigenous or aboriginal group outside of Canada. | added v2.5

JHN | Jurisdictional health number (Canada) | | Rechtsgebied gezondheidsnummer (Canada) | Class: Insurance<p>2 uses: a) UK jurisdictional CHI number; b) Canadian provincial health card number: | added v2.4

LACSN | Laboratory Accession ID | | Laboratorium Accessie ID | A laboratory accession id is used in the laboratory domain. The concept of accession is used in other domains such as radiology, so the LACSN is used to distinguish a lab accession id from an radiology accession id | added v2.7

LANR | Lifelong physician number | | Levenslang zorgverlenernummer | Lebenslange Arztnummer - for use in German realm. | added v2.7

LI | Labor and industries number | | Arbeid en industrienummer | | added v2.5

LN | License number | | Licentienummer | | added v2.3.1

LR | Local Registry ID | | Lokaal register ID | | added v2.3.1

MA | Patient Medicaid number | Armennummer | Medicaid patiëntnummer | Class: Insurance | added v2.3

MB | Member Number | | Lidnummer | An identifier for the insured of an insurance policy (this insured always has a subscriber), usually assigned by the insurance carrier.<p>Use Case: Person is covered by an insurance policy. This person may or may not be the subscriber of the policy. | added v2.5

MC | Patient's Medicare number | Rentnernummer | Medicare patiëntnummer | Class: Insurance | added v2.3

MCD | Practitioner Medicaid number | | Medicaid zorgverlenernummer | Class: Insurance | added v2.5

MCN | Microchip Number | | Microchip-nummer | | added v2.4

MCR | Practitioner Medicare number | | Medicare zorgverlenernummer | Class: Insurance | added v2.5

MCT | Marriage Certificate | | Huwelijkscertificaat | A number associated with a document identifying the event of a person's marriage. | added v2.6

MD | Medical License number | | Geneeskundig licentienummer | An identifier that is unique to a medical doctor within the jurisdiction of a licensing board.<p>Use Case: These license numbers are sometimes used as identifiers. In some states, the same authority issues all three identifiers, e.g. medical, osteopathic | added v2.5

MI | Military ID number | | Militaire identificatie | A number assigned to an individual who has had military duty, but is not currently on active duty. The number is assigned by the DOD or Veterans' Affairs (VA). | added v2.5

MR | Medical record number | Krankenaktennummer | Medisch dossiernummer | An identifier that is unique to a patient within a set of medical records, not necessarily unique within an application. | added v2.3

MRT | Temporary Medical Record Number | | Tijdelijke medisch dossiernummer | Temporary version of a Medical Record Number<p>Use Case: An ancillary system that does not normally assign medical record numbers is the first time to register a patient. This ancillary system will generate a temporary medical record number that will only | added v2.5

MS | MasterCard | MasterCard | MasterCard | Deprecated and replaced by BC in v 2.5. | added v2.3

NBSNR | Secondary physician office number | | Secundaire zorgverlenerpraktijknummer | Nebenbetriebsstättennummer - for use in the German realm. | added v2.7

NCT | Naturalization Certificate | | Naturalisatiecertificaat | A number associated with a document identifying a person's retention of citizenship in a particular country. | added v2.6

NE | National employer identifier | | Nationale werkgeveridentificatie | In the US, the Assigning Authority for this value is typically CMS, but it may be used by all providers and insurance companies in HIPAA related transactions. | added v2.3.1

NH | National Health Plan Identifier | | Nationaal zorgverzekeringsnummer | Class: Insurance<p>Used for the UK NHS national identifier.<p>In the US, the Assigning Authority for this value is typically CMS, but it may be used by all providers and insurance companies in HIPAA related transactions. | added v2.3.1

NI | National unique individual identifier | | Nationale unieke identificatie persoon | Class: Insurance<p>In the US, the Assigning Authority for this value is typically CMS, but it may be used by all providers and insurance companies in HIPAA related transactions. | added v2.3.1

NII | National Insurance Organization Identifier | Institutskennzeichen der Krankenkasse | Nationale verzekeraar identificatie | Class: Insurance<p>In Germany a national identifier for an insurance company. It is printed on the insurance card (health card). It is not to be confused with the health card number itself.<p>Krankenkassen-ID der KV-Karte | added v2.5

NIIP | National Insurance Payor Identifier (Payor) | Vertragskassennummer (VKNR) | Nationale verzekeraar betaler identificatie (Betaler) | Class: Insurance<p>In Germany the insurance identifier addressed as the payor.<p>Krankenkassen-ID des Rechnungsempfängers<p>Use case: a subdivision issues the card with their identifier, but the main division is going to pay the invoices. | added v2.5

NNxxx | National Person Identifier where the xxx is the ISO table 3166 3-character (alphabetic) country code | | Nationale persoonsidentificatie waarbij xxx de ISO-tabel 3166 3-tekens (alfabetisch) landcode is | | added v2.3.1

NP | Nurse practitioner number | | Nurse practitioner nummer | An identifier that is unique to a nurse practitioner within the jurisdiction of a certifying board. | added v2.5

NPI | National provider identifier | | Nationale zorgaanbieder/zorgverlener identificatie | Class: Insurance<p>In the US, the Assigning Authority for this value is typically CMS, but it may be used by all providers and insurance companies in HIPAA related transactions. | added v2.3.1

OD | Optometrist license number | | Optometrist nummer | A number that is unique to an individual optometrist within the jurisdiction of the licensing board. | added v2.5

PA | Physician Assistant number | Assistenzarztnummer | Zorgverlener nummer | An identifier that is unique to a physician assistant within the jurisdiction of a licensing board | added v2.5

PC | Parole Card | | Reclasseringskaart | A number identifying a person on parole. | added v2.6

PCN | Penitentiary/correctional institution Number | | Penitentiaire instellings-nummer | A number assigned to individual who is incarcerated. | added v2.5

PE | Living Subject Enterprise Number | | Levend wezen bedrijfs-nummer | An identifier that is unique to a living subject within an enterprise (as identified by the Assigning Authority). | added v2.5

PEN | Pension Number | | Pensioennummer | | added v2.4

PI | Patient internal identifier | interne Patienten-ID | Intern patiëntnummer | A number that is unique to a patient within an Assigning Authority. | added v2.3

PN | Person number | Personen-ID | Persoonsnummer | A number that is unique to a living subject within an Assigning Authority. | added v2.3.1

PNT | Temporary Living Subject Number | | Tijdelijk levend wezen nummer | Temporary version of a Lining Subject Number. | added v2.5

PPIN | Medicare/CMS Performing Provider Identification Number | | Medicare/CMS Uitvoerende zorgaanbieder/zorgverlener identificatienummer | Class: Insurance | added v2.6

PPN | Passport number | Passnummer | Paspoortnummer | A unique number assigned to the document affirming that a person is a citizen of the country. In the US this number is issued only by the State Department. | added v2.5

PRC | Permanent Resident Card Number | | Permanente verblijfsvergunning-nummer | | added v2.5

PRN | Provider number | | Zorgaanbieder/zorgverlener-nummer | A number that is unique to an individual provider, a provider group or an organization within an Assigning Authority.<p>Use case: This allows PRN to represent either an individual (a nurse) or a group/organization (orthopedic surgery team). | added v2.3.1

PT | Patient external identifier | externe Patienten-ID | Extern patiëntnummer | | added v2.3

QA | QA number | | Quality Assurance-nummer | | added v2.5

RI | Resource identifier | | Resource identicatie | A generalized resource identifier.<p>Use Case: An identifier type is needed to accommodate what are commonly known as resources. The resources can include human (e.g. a respiratory therapist), non-human (e.g. a companion animal), inanimate object (e.g. | added v2.5

RN | Registered Nurse Number | | Verpleegkundige registratienummer | An identifier that is unique to a registered nurse within the jurisdiction of the licensing board. | added v2.5

RPH | Pharmacist license number | | Apotheek licentienummer | An identifier that is unique to a pharmacist within the jurisdiction of the licensing board. | added v2.5

RR | Railroad Retirement number | Seniorenkartennummer | Spoorwegen pensioneringsnummer | An identifier for an individual enrolled with the Railroad Retirement Administration. Analogous to, but distinct from, a Social Security Number | added v2.3

RRI | Regional registry ID | | Regionaal register-ID | | added v2.3.1

RRP | Railroad Retirement Provider | | Spoorwegen pensioenaanbieder | Class: Insurance | added v2.6

SID | Specimen ID | | Monsternummer | Identifier for a specimen. Used when it is not known if the specimen ID is a unique specimen ID (USID) or an ancestor ID (ASID). | added v2.7

SL | State license | | Staat-licentie | | added v2.3.1

SN | Subscriber Number | | Hoofdverzekerdenummer | Class: Insurance<p>An identifier for a subscriber of an insurance policy which is unique for, and usually assigned by, the insurance carrier.<p>Use Case: A person is the subscriber of an insurance policy. The person's family may be plan members, but are n | added v2.5

SP | Study Permit | | Opleidingsvisum | A number associated with a permit identifying a person who is a resident of a jurisdiction for the purpose of education. | added v2.6

SR | State registry ID | | Staat register-ID | | added v2.3.1

SS | Social Security number | Sozialversicherungsnummer | SOFI-nummer | | added v2.3

TAX | Tax ID number | | Belasting identificatie | | added v2.5

TN | Treaty Number/ (Canada) | | Verdragnummer/ (Canada) | A number assigned to a member of an indigenous group in Canada.<p>Use Case: First Nation. | added v2.5

TPR | Temporary Permanent Resident (Canada) | | Tijdelijk permanente inwoner (Canada) | A number associated with a document identifying a person's temporary permanent resident status. | added v2.6

U | Unspecified identifier | | Niet-gspecificeerde identificatie | | added v2.3.1

UPIN | Medicare/CMS (formerly HCFA)'s Universal Physician Identification numbers | | Medicare/HCFA's Universele Zorgverlener Identificatie Nummers | Class: Insurance<p>An identifier for a provider within the CMS/Medicare program. A globally unique identifier for the provider in the Medicare program. | added v2.3.1

USID | Unique Specimen ID | | Uniek monsternummer | A unique identifier for a specimen. | added v2.7

VN | Visit number | Fallnummer | Bezoeknummer | | added v2.3

VP | Visitor Permit | | Toeristenvisum | A number associated with a document identifying a person as a visitor of a jurisdiction or country. | added v2.6

VS | VISA | VISA | VISA | Deprecated and replaced by BC in v 2.5. | added v2.3

WC | WIC identifier | | WIC identificatie | | added v2.3.1

WCN | Workers' Comp Number | | Werknemerscompensatie-nummer | | added v2.4

WP | Work Permit | | Werkvisum | A number associated with a permit for a person who is granted permission to work in a country for a specified time period. | added v2.6

XX | Organization identifier | Organisations-ID | Organisatie identificatie | | added v2.3

4.2.13.204 HL7 Version 2 Table 0204

URL: https://hl7.org/fhir/STU3/v2/0204/index.html

This page is part of the FHIR Specification (v3.0.2: STU 3). The current version which supercedes this version is 4.0.1. For a full list of available versions, see the Directory of published versions

Vocabulary Work Group | Maturity Level: N/A | External | Use Context: Any

This is a table defined as part of HL7 v2 . Related FHIR content: v2 Organizational Name Type.

Summary

Name: | v2 Organizational Name Type
Definition: | FHIR Value set/code system definition for HL7 v2 table 0204 (Organizational Name Type)
Code System URL: | http://hl7.org/fhir/v2/0204
Value Set URL: | http://hl7.org/fhir/ValueSet/v2-0204
OID: | ??
CodeSystem Resource | XML / JSON
ValueSet Resource | XML / JSON

This value set is used in the following places:

* This value set is the designated 'entire code system' value set for v2 Organizational Name Type

4.2.13.204.1 Code System Content

Organizational Name Type

Code | Description | Deutsch (German) | Nederlands (Dutch) | Comment | Version
A | Alias name | Aliasname | Aliasnaam | | added v2.3
D | Display name | angezeigter Name | Weergavenaam | | added v2.3
L | Legal name | gesetzlicher Name | Juridische naam | | added v2.3
SL | Stock exchange listing name | Börsenlistenname | Beursgenoteerde naam | | added v2.3

4.2.13.205 HL7 Version 2 Table 0205

URL: https://hl7.org/fhir/STU3/v2/0205/index.html

This page is part of the FHIR Specification (v3.0.2: STU 3). The current version which supercedes this version is 4.0.1. For a full list of available versions, see the Directory of published versions

Vocabulary Work Group | Maturity Level: N/A | External | Use Context: Any

This is a table defined as part of HL7 v2 . Related FHIR content: v2 Price Type.

Summary

Name: | v2 Price Type
Definition: | FHIR Value set/code system definition for HL7 v2 table 0205 (Price Type)
Code System URL: | http://hl7.org/fhir/v2/0205
Value Set URL: | http://hl7.org/fhir/ValueSet/v2-0205
OID: | ??
CodeSystem Resource | XML / JSON
ValueSet Resource | XML / JSON

This value set is used in the following places:

* This value set is the designated 'entire code system' value set for v2 Price Type

4.2.13.205.1 Code System Content

Price Type

Code | Description | Nederlands (Dutch) | Comment | Version
AP | administrative price or handling fee | Administratieve prijs of verwerkingsvergoeding | | added v2.3
DC | direct unit cost | Direct stuksprijs | | added v2.3
IC | indirect unit cost | Indirecte stuksprijs | | added v2.3
PF | professional fee for performing provider | Zakelijke vergoeding voor uitvoerende zorgverlener | | added v2.3
TF | technology fee for use of equipment | Technologievergoeding voor apparaatgebruik | | added v2.3
TP | total price | Totaalprijs | | added v2.3
UP | unit price, may be based on length of procedure or service | Stuksprijs, mogelijk gebaseerd op duur van behandeling of service | | added v2.3

4.2.13.206 HL7 Version 2 Table 0206

URL: https://hl7.org/fhir/STU3/v2/0206/index.html

This page is part of the FHIR Specification (v3.0.2: STU 3). The current version which supercedes this version is 4.0.1. For a full list of available versions, see the Directory of published versions

Vocabulary Work Group | Maturity Level: N/A | External | Use Context: Any

This is a table defined as part of HL7 v2 . Related FHIR content: v2 Segment Action Code.

Summary

Name: | v2 Segment Action Code
Definition: | FHIR Value set/code system definition for HL7 v2 table 0206 (Segment Action Code)

Code System URL: | http://hl7.org/fhir/v2/0206
Value Set URL: | http://hl7.org/fhir/ValueSet/v2-0206
OID: | ??
CodeSystem Resource | XML / JSON
ValueSet Resource | XML / JSON

This value set is used in the following places:

* This value set is the designated 'entire code system' value set for v2 Segment Action Code

4.2.13.206.1 Code System Content

Segment Action Code

Code | Description | Deutsch (German) | Nederlands (Dutch) | Comment | Version
A | Add/Insert | Einfügen | Toevoegen/invoegen | | added v2.3
D | Delete | Löschen/Stornieren | Verwijderen | | added v2.3
U | Update | Ändern | Updaten | | added v2.3
X | No Change | | Geen wijziging | | added v2.6

4.2.13.207 HL7 Version 2 Table 0207

URL: https://hl7.org/fhir/STU3/v2/0207/index.html

This page is part of the FHIR Specification (v3.0.2: STU 3). The current version which supercedes this version is 4.0.1. For a full list of available versions, see the Directory of published versions

Vocabulary Work Group | Maturity Level: N/A | External | Use Context: Any

This is a table defined as part of HL7 v2 . Related FHIR content: v2 Processing Mode.

Summary

Name: | v2 Processing Mode
Definition: | FHIR Value set/code system definition for HL7 v2 table 0207 (Processing Mode)
Code System URL: | http://hl7.org/fhir/v2/0207
Value Set URL: | http://hl7.org/fhir/ValueSet/v2-0207
OID: | ??
CodeSystem Resource | XML / JSON
ValueSet Resource | XML / JSON

This value set is used in the following places:

* This value set is the designated 'entire code system' value set for v2 Processing Mode

4.2.13.207.1 Code System Content

Processing Mode

Code | Description | Nederlands (Dutch) | Comment | Version
A | Archive | Archiveren | | added v2.3
I | Initial load | Initieel laden | | added v2.3
Not present | Not present (the default, meaning current processing) | Niet aanwezig | | added v2.3
R | Restore from archive | Herstellen uit archief | | added v2.3
T | Current processing, transmitted at intervals (scheduled or on demand) | Huidige verwerking, verstuurd op basis van intervallen (gepland of op aanvraag) | | added v2.3.1

4.2.13.208 HL7 Version 2 Table 0208

URL: https://hl7.org/fhir/STU3/v2/0208/index.html

This page is part of the FHIR Specification (v3.0.2: STU 3). The current version which supercedes this version is 4.0.1. For a full list of available versions, see the Directory of published versions

Vocabulary Work Group | Maturity Level: N/A | External | Use Context: Any

This is a table defined as part of HL7 v2 . Related FHIR content: v2 Query Response Status.

Summary

Name: | v2 Query Response Status
Definition: | FHIR Value set/code system definition for HL7 v2 table 0208 (Query Response Status)
Code System URL: | http://hl7.org/fhir/v2/0208
Value Set URL: | http://hl7.org/fhir/ValueSet/v2-0208
OID: | ??
CodeSystem Resource | XML / JSON
ValueSet Resource | XML / JSON

This value set is used in the following places:

* This value set is the designated 'entire code system' value set for v2 Query Response Status

4.2.13.208.1 Code System Content

Query Response Status

Code | Description | Nederlands (Dutch) | Comment | Version
AE | Application error | Applicatiefout | | added v2.3.1
AR | Application reject | Applicatieweigering | | added v2.3.1
NF | No data found, no errors | Geen gegevens gevonden, geen fouten | | added v2.3
OK | Data found, no errors (this is the default) | Gegevens gevonden, geen fouten (dit is de standaardwaarde) | | added v2.3

4.2.13.209 HL7 Version 2 Table 0209

URL: https://hl7.org/fhir/STU3/v2/0209/index.html

This page is part of the FHIR Specification (v3.0.2: STU 3). The current version which supercedes this version is 4.0.1. For a full list of available versions, see the Directory of published versions

Vocabulary Work Group | Maturity Level: N/A | External | Use Context: Any

This is a table defined as part of HL7 v2 . Related FHIR content: v2 Relational Operator.

Summary

Name: | v2 Relational Operator
Definition: | FHIR Value set/code system definition for HL7 v2 table 0209 (Relational Operator)
Code System URL: | http://hl7.org/fhir/v2/0209
Value Set URL: | http://hl7.org/fhir/ValueSet/v2-0209
OID: | ??
CodeSystem Resource | XML / JSON
ValueSet Resource | XML / JSON

This value set is used in the following places:

* This value set is the designated 'entire code system' value set for v2 Relational Operator

4.2.13.209.1 Code System Content

Relational Operator

Code | Description | Nederlands (Dutch) | Comment | Version
CT | Contains | Bevat | | added v2.3
EQ | Equal | Gelijk aan | | added v2.3
GE | Greater than or equal | Groter of gelijk aan | | added v2.3
GN | Generic | Generiek | | added v2.3
GT | Greater than | Groter dan | | added v2.3
LE | Less than or equal | Kleiner dan of gelijk aan | | added v2.3
LT | Less than | Kleiner dan | | added v2.3
NE | Not Equal | Ongelijk aan | | added v2.3

4.2.13.210 HL7 Version 2 Table 0210

URL: https://hl7.org/fhir/STU3/v2/0210/index.html

This page is part of the FHIR Specification (v3.0.2: STU 3). The current version which supercedes this version is 4.0.1. For a full list of available versions, see the Directory of published versions

Vocabulary Work Group | Maturity Level: N/A | External | Use Context: Any

This is a table defined as part of HL7 v2 . Related FHIR content: v2 Relational Conjunction.

Summary

Name: | v2 Relational Conjunction
Definition: | FHIR Value set/code system definition for HL7 v2 table 0210 (Relational Conjunction)
Code System URL: | http://hl7.org/fhir/v2/0210
Value Set URL: | http://hl7.org/fhir/ValueSet/v2-0210
OID: | ??
CodeSystem Resource | XML / JSON
ValueSet Resource | XML / JSON

This value set is used in the following places:

* This value set is the designated 'entire code system' value set for v2 Relational Conjunction

4.2.13.210.1 Code System Content

Relational Conjunction

Code | Description | Nederlands (Dutch) | Comment | Version
AND | Default | Standaard | | added v2.3
OR | | OF | | added v2.3

4.2.13.211 HL7 Version 2 Table 0211

URL: https://hl7.org/fhir/STU3/v2/0211/index.html

This page is part of the FHIR Specification (v3.0.2: STU 3). The current version which supercedes this version is 4.0.1. For a full list of available versions, see the Directory of published versions

Vocabulary Work Group | Maturity Level: N/A | External | Use Context: Any

This is a table defined as part of HL7 v2 . Related FHIR content: v2 Alternate Character Sets.

Summary

Name: | v2 Alternate Character Sets
Definition: | FHIR Value set/code system definition for HL7 v2 table 0211 (Alternate Character Sets)
Code System URL: | http://hl7.org/fhir/v2/0211
Value Set URL: | http://hl7.org/fhir/ValueSet/v2-0211
OID: | ??
CodeSystem Resource | XML / JSON
ValueSet Resource | XML / JSON

This value set is used in the following places:

* This value set is the designated 'entire code system' value set for v2 Alternate Character Sets

4.2.13.211.1 Code System Content

Alternate Character Sets

Code | Description | Nederlands (Dutch) | Comment | Version
8859/1 | The printable characters from the ISO 8859/1 Character set | De leesbare tekens uit de ISO 8859/1 tekenset | | added v2.3
8859/15 | The printable characters from the ISO 8859/15 (Latin-15) | De leesbare tekens uit de ISO 8859/15 tekenset (Latin-15) | | added v2.6
8859/2 | The printable characters from the ISO 8859/2 Character set | De leesbare tekens uit de ISO 8859/2 tekenset | | added v2.3
8859/3 | The printable characters from the ISO 8859/3 Character set | De leesbare tekens uit de ISO 8859/3 tekenset | | added v2.3
8859/4 | The printable characters from the ISO 8859/4 Character set | De leesbare tekens uit de ISO 8859/4 tekenset | | added v2.3
8859/5 | The printable characters from the ISO 8859/5 Character set | De leesbare tekens uit de ISO 8859/5 tekenset | | added v2.3
8859/6 | The printable characters from the ISO 8859/6 Character set | De leesbare tekens uit de ISO 8859/6 tekenset | | added v2.3
8859/7 | The printable characters from the ISO 8859/7 Character set | De leesbare tekens uit de ISO 8859/7 tekenset | | added v2.3
8859/8 | The printable characters from the ISO 8859/8 Character set | De leesbare tekens uit de ISO 8859/8 tekenset | | added v2.3
8859/9 | The printable characters from the ISO 8859/9 Character set | De leesbare tekens uit de ISO 8859/9 tekenset | | added v2.3
ASCII | The printable 7-bit ASCII character set. | De leesbare 7-bit ASCII tekenset. | (This is the default if this field is omitted) | added v2.3
BIG-5 | Code for Taiwanese Character Set (BIG-5) | Code voor Taiwanese tekenset (BIG-5) | Does not need an escape sequence.<p>BIG-5 does not need an escape sequence. ASCII is a 7 bit character set, which means that the top bit of the byte is "0". The parser knows that when the top bit of the byte is "0", the character set is ASCII. When it is | added v2.5
CNS 11643-1992 | Code for Taiwanese Character Set (CNS 11643-1992) | Code voor Taiwanese tekenset (CNS 11643-1992) | Does not need an escape sequence. | added v2.5
GB 18030-2000 | Code for Chinese Character Set (GB 18030-2000) | Code voor Chinese tekenset (GB 18030-2000) | Does not need an escape sequence. | added v2.5
ISO IR14 | Code for Information Exchange (one byte)(JIS X 0201-1976). | Code voor informatieuitwisseling (één byte)(JIS X 0201-1976). | Note that the code contains a space, i.e., "ISO IR14". | added v2.3.1
ISO IR159 | Code of the supplementary Japanese Graphic Character set for information interchange (JIS X 0212-1990). | Code voor het aanvullende Japanse ideogramschrift voor informatieuitwisseling (JIS X 0212-1990). | Note that the code contains a space, i.e., "ISO IR159". | added v2.3.1
ISO IR6 | ASCII graphic character set consisting of 94 characters. | ASCII ideogramtekenset bestaande uit 94 tekens. | http://www.itscj.ipsj.or.jp/ISO-IR/006.pdf | added v2.7
ISO IR87 | Code for the Japanese Graphic Character set for information interchange (JIS X 0208-1990), | Code voor de Japanse ideogramschrift voor informatieuitwisseling (JIS X 0208-1990). | Note that the code contains a space, i.e., "ISO IR87".<p>The JIS X 0208 needs an escape sequence. In Japan, the escape technique is ISO 2022. From basic ASCII, escape sequence "escape" $ B (in HEX, 1B 24 42) lets the parser know that following bytes shoul | added v2.3.1
JAS2020 | A subset of ISO2020 used for most Kanjii transmissions | Een subset van ISO 2020 meestal gebruikt voor Kanjii verzendingen | deprecated | added v2.3, removed after v2.3
JIS X 0202 | ISO 2022 with escape sequences for Kanjii | ISO 2022 met escape-sequenties voor Kanjii | deprecated | added v2.3, removed after v2.3
KS X 1001 | Code for Korean Character Set (KS X 1001) | Code voor Koreaanse tekenset (KS X 1001) | | added v2.5
UNICODE | The world wide character standard from ISO/IEC 10646-1-1993 | De wereldwijde tekensetstandaard van ISO/IEC 10646-1-1993 | Deprecated. Retained for backward compatibility only as v 2.5. Replaced by specific Unicode encoding codes. | added v2.3
UNICODE UTF-16 | UCS Transformation Format, 16-bit form | UCS Transformatieformaat, 16-bits vorm | UTF-16 is identical to ISO/IEC 10646 UCS-2. Note that the code contains a space before UTF but not before and after the hyphen. | added v2.5, removed after v2.7.1
UNICODE UTF-32 | UCS Transformation Format, 32-bit form | UCS Transformatieformaat, 32-bits vorm | UTF-32 is defined by Unicode Technical Report #19, and is an officially recognized encoding as of Unicode Version 3.1. UTF-32 is a proper subset of ISO/IEC 10646 UCS-4. Note that the code contains a space before UTF but not before and after the hyphen. | added v2.5, removed after v2.7.1
UNICODE UTF-8 | UCS Transformation Format, 8-bit form | UCS Transformatieformaat, 8-bits vorm | UTF-8 is a variable-length encoding, each code value is represented by 1,2 or 3 bytes, depending on the code value. 7 bit ASCII is a proper subset of UTF-8. Note that the code contains a space before UTF but not before and after the hyphen. Since UTF-8 re | added v2.5

4.2.13.213 HL7 Version 2 Table 0213

URL: https://hl7.org/fhir/STU3/v2/0213/index.html

This page is part of the FHIR Specification (v3.0.2: STU 3). The current version which supercedes this version is 4.0.1. For a full list of available versions, see the Directory of published versions

Vocabulary Work Group | Maturity Level: N/A | External | Use Context: Any

This is a table defined as part of HL7 v2 . Related FHIR content: v2 Purge Status Code.

Summary

Name: | v2 Purge Status Code
Definition: | FHIR Value set/code system definition for HL7 v2 table 0213 (Purge Status Code)
Code System URL: | http://hl7.org/fhir/v2/0213
Value Set URL: | http://hl7.org/fhir/ValueSet/v2-0213
OID: | ??
CodeSystem Resource | XML / JSON
ValueSet Resource | XML / JSON

This value set is used in the following places:

* This value set is the designated 'entire code system' value set for v2 Purge Status Code

4.2.13.213.1 Code System Content

Purge Status Code

Code | Description | Nederlands (Dutch) | Comment | Version
D | The visit is marked for deletion and the user cannot enter new data against it. | Het bezoek is gemarkeerd voor verwijdering en de gebruiker kan geen nieuwe gegevens bij het bezoek invoeren | | added v2.3
I | The visit is marked inactive and the user cannot enter new data against it. | Het bezoek is gemarkeerd als inactief en de gebruiker kan geen nieuwe gegevens bij het bezoek invoeren | | added v2.3
P | Marked for purge. User is no longer able to update the visit. | Gemarkeerd voor opruiming. Gebruiker kan het bezoek niet langer bijwerken. | | added v2.3

4.2.13.214 HL7 Version 2 Table 0214

URL: https://hl7.org/fhir/STU3/v2/0214/index.html

This page is part of the FHIR Specification (v3.0.2: STU 3). The current version which supercedes this version is 4.0.1. For a full list of available versions, see the Directory of published versions

Vocabulary Work Group | Maturity Level: N/A | External | Use Context: Any

This is a table defined as part of HL7 v2 . Related FHIR content: v2 Special Program Code.

Summary

Name: | v2 Special Program Code
Definition: | FHIR Value set/code system definition for HL7 v2 table 0214 (Special Program Code)
Code System URL: | http://hl7.org/fhir/v2/0214
Value Set URL: | http://hl7.org/fhir/ValueSet/v2-0214
OID: | ??
CodeSystem Resource | XML / JSON
ValueSet Resource | XML / JSON

This value set is used in the following places:

* This value set is the designated 'entire code system' value set for v2 Special Program Code

4.2.13.214.1 Code System Content

Special Program Code

Code | Description | Nederlands (Dutch) | Comment | Version
CH | Child Health Assistance | Jeugdgezondheid assistentie | | added v2.5
ES | Elective Surgery Program | Electief chirurgisch programma | | added v2.5
FP | Family Planning | Gezinsplanning | | added v2.5
O | Other | Anders | | added v2.5
U | Unknown | Onbekend | | added v2.5

4.2.13.215 HL7 Version 2 Table 0215

URL: https://hl7.org/fhir/STU3/v2/0215/index.html

This page is part of the FHIR Specification (v3.0.2: STU 3). The current version which supercedes this version is 4.0.1. For a full list of available versions, see the Directory of published versions

Vocabulary Work Group | Maturity Level: N/A | External | Use Context: Any

This is a table defined as part of HL7 v2 . Related FHIR content: v2 Publicity Code.

Summary

Name: | v2 Publicity Code
Definition: | FHIR Value set/code system definition for HL7 v2 table 0215 (Publicity Code)
Code System URL: | http://hl7.org/fhir/v2/0215
Value Set URL: | http://hl7.org/fhir/ValueSet/v2-0215
OID: | ??
CodeSystem Resource | XML / JSON
ValueSet Resource | XML / JSON

This value set is used in the following places:

* This value set is the designated 'entire code system' value set for v2 Publicity Code

4.2.13.215.1 Code System Content

Publicity Code

Code | Description | Nederlands (Dutch) | Comment | Version
F | Family only | Alleen familie | | added v2.5
N | No Publicity | Geen publiciteit | | added v2.5
O | Other | Anders | | added v2.5
U | Unknown | Onbekend | | added v2.5

4.2.13.216 HL7 Version 2 Table 0216

URL: https://hl7.org/fhir/STU3/v2/0216/index.html

This page is part of the FHIR Specification (v3.0.2: STU 3). The current version which supercedes this version is 4.0.1. For a full list of available versions, see the Directory of published versions

Vocabulary Work Group | Maturity Level: N/A | External | Use Context: Any

This is a table defined as part of HL7 v2 . Related FHIR content: v2 Patient Status Code.

Summary

Name: | v2 Patient Status Code
Definition: | FHIR Value set/code system definition for HL7 v2 table 0216 (Patient Status Code)
Code System URL: | http://hl7.org/fhir/v2/0216
Value Set URL: | http://hl7.org/fhir/ValueSet/v2-0216
OID: | ??
CodeSystem Resource | XML / JSON
ValueSet Resource | XML / JSON

This value set is used in the following places:

* This value set is the designated 'entire code system' value set for v2 Patient Status Code

4.2.13.216.1 Code System Content

Patient Status Code

Code | Description | Nederlands (Dutch) | Comment | Version
AI | Active Inpatient | Actieve patiënt | | added v2.5
DI | Discharged Inpatient | Ontslagen patiënt | | added v2.5

4.2.13.217 HL7 Version 2 Table 0217

URL: https://hl7.org/fhir/STU3/v2/0217/index.html

This page is part of the FHIR Specification (v3.0.2: STU 3). The current version which supercedes this version is 4.0.1. For a full list of available versions, see the Directory of published versions

Vocabulary Work Group | Maturity Level: N/A | External | Use Context: Any

This is a table defined as part of HL7 v2 . Related FHIR content: v2 Visit Priority Code.

Summary

Name: | v2 Visit Priority Code
Definition: | FHIR Value set/code system definition for HL7 v2 table 0217 (Visit Priority Code)
Code System URL: | http://hl7.org/fhir/v2/0217
Value Set URL: | http://hl7.org/fhir/ValueSet/v2-0217
OID: | ??
CodeSystem Resource | XML / JSON
ValueSet Resource | XML / JSON

This value set is used in the following places:

* This value set is the designated 'entire code system' value set for v2 Visit Priority Code

4.2.13.217.1 Code System Content

Visit Priority Code

Code | Description | Nederlands (Dutch) | Comment | Version
1 | Emergency | Spoed | | added v2.4
2 | Urgent | Urgent | | added v2.4
3 | Elective | Zelf gekozen | | added v2.4

4.2.13.220 HL7 Version 2 Table 0220

URL: https://hl7.org/fhir/STU3/v2/0220/index.html

This page is part of the FHIR Specification (v3.0.2: STU 3). The current version which supercedes this version is 4.0.1. For a full list of available versions, see the Directory of published versions

Vocabulary Work Group | Maturity Level: N/A | External | Use Context: Any

This is a table defined as part of HL7 v2 . Related FHIR content: v2 Living Arrangement.

Summary

Name: | v2 Living Arrangement
Definition: | FHIR Value set/code system definition for HL7 v2 table 0220 (Living Arrangement)
Code System URL: | http://hl7.org/fhir/v2/0220
Value Set URL: | http://hl7.org/fhir/ValueSet/v2-0220
OID: | ??
CodeSystem Resource | XML / JSON
ValueSet Resource | XML / JSON

This value set is used in the following places:

* This value set is the designated 'entire code system' value set for v2 Living Arrangement

4.2.13.220.1 Code System Content

Living Arrangement

Code | Description | Deutsch (German) | Nederlands (Dutch) | Comment | Version
A | Alone | Seul | Zelfstandig | | added v2.3
F | Family | | Familie | | added v2.3
I | Institution | | Instituut | | added v2.3
R | Relative | | Familielid | | added v2.3
S | Spouse Only | | Alleen echtgenoot | | added v2.3
U | Unknown | | Onbekend | | added v2.3

4.2.13.223 HL7 Version 2 Table 0223

URL: https://hl7.org/fhir/STU3/v2/0223/index.html

This page is part of the FHIR Specification (v3.0.2: STU 3). The current version which supercedes this version is 4.0.1. For a full list of available versions, see the Directory of published versions

Vocabulary Work Group | Maturity Level: N/A | External | Use Context: Any

This is a table defined as part of HL7 v2 . Related FHIR content: v2 Living Dependency.

Summary

Name: | v2 Living Dependency
Definition: | FHIR Value set/code system definition for HL7 v2 table 0223 (Living Dependency)
Code System URL: | http://hl7.org/fhir/v2/0223
Value Set URL: | http://hl7.org/fhir/ValueSet/v2-0223
OID: | ??
CodeSystem Resource | XML / JSON
ValueSet Resource | XML / JSON

This value set is used in the following places:

* This value set is the designated 'entire code system' value set for v2 Living Dependency

4.2.13.223.1 Code System Content

Living Dependency

Code | Description | Nederlands (Dutch) | Comment | Version
C | Small Children Dependent | Afhankelijke kleine kinderen | | added v2.4
CB | Common Bath | Gedeeld bad | deprecated | added v2.3, removed after v2.4
D | Spouse dependent | Echtgenoot afhankelijk | deprecated | added v2.3, removed after v2.4
M | Medical Supervision Required | Medisch toezicht vereist | | added v2.3
O | Other | Anders | | added v2.4
S | Spouse Dependent | Echtgenoot afhankelijk | | added v2.3
U | Unknown | Onbekend | | added v2.4
WU | Walk up | Loopt naar boven | deprecated | added v2.3, removed after v2.4

4.2.13.224 HL7 Version 2 Table 0224

URL: https://hl7.org/fhir/STU3/v2/0224/index.html

This page is part of the FHIR Specification (v3.0.2: STU 3). The current version which supercedes this version is 4.0.1. For a full list of available versions, see the Directory of published versions

Vocabulary Work Group | Maturity Level: N/A | External | Use Context: Any

This is a table defined as part of HL7 v2 . Related FHIR content: v2 Transport Arranged.

Summary

Name: | v2 Transport Arranged
Definition: | FHIR Value set/code system definition for HL7 v2 table 0224 (Transport Arranged)
Code System URL: | http://hl7.org/fhir/v2/0224
Value Set URL: | http://hl7.org/fhir/ValueSet/v2-0224

OID: | ??
CodeSystem Resource | XML / JSON
ValueSet Resource | XML / JSON

This value set is used in the following places:

* This value set is the designated 'entire code system' value set for v2 Transport Arranged

4.2.13.224.1 Code System Content

Transport Arranged

Code | Description | Nederlands (Dutch) | Comment | Version
A | Arranged | Geregeld | | added v2.3
N | Not Arranged | Niet geregeld | | added v2.3
U | Unknown | Onbekend | | added v2.3

4.2.13.225 HL7 Version 2 Table 0225

URL: https://hl7.org/fhir/STU3/v2/0225/index.html

This page is part of the FHIR Specification (v3.0.2: STU 3). The current version which supercedes this version is 4.0.1. For a full list of available versions, see the Directory of published versions

Vocabulary Work Group | Maturity Level: N/A | External | Use Context: Any

This is a table defined as part of HL7 v2 . Related FHIR content: v2 Escort Required.

Summary

Name: | v2 Escort Required
Definition: | FHIR Value set/code system definition for HL7 v2 table 0225 (Escort Required)
Code System URL: | http://hl7.org/fhir/v2/0225
Value Set URL: | http://hl7.org/fhir/ValueSet/v2-0225
OID: | ??
CodeSystem Resource | XML / JSON
ValueSet Resource | XML / JSON

This value set is used in the following places:

* This value set is the designated 'entire code system' value set for v2 Escort Required

4.2.13.225.1 Code System Content

Escort Required

Code | Description | Nederlands (Dutch) | Comment | Version
N | Not Required | Niet vereist | | added v2.3
R | Required | Vereist | | added v2.3
U | Unknown | Onbekend | | added v2.3

4.2.13.227 HL7 Version 2 Table 0227

URL: https://hl7.org/fhir/STU3/v2/0227/index.html

This page is part of the FHIR Specification (v3.0.2: STU 3). The current version which supercedes this version is 4.0.1. For a full list of available versions, see the Directory of published versions

Vocabulary Work Group | Maturity Level: N/A | External | Use Context: Any

This is a table defined as part of HL7 v2 . Related FHIR content: v2 Manufacturers of Vaccines (code=MVX).

Summary

Name: | v2 Manufacturers of Vaccines (code=MVX)
Definition: | FHIR Value set/code system definition for HL7 v2 table 0227 (Manufacturers of Vaccines (code=MVX))
Code System URL: | http://hl7.org/fhir/v2/0227
Value Set URL: | http://hl7.org/fhir/ValueSet/v2-0227
OID: | ??
CodeSystem Resource | XML / JSON
ValueSet Resource | XML / JSON

This value set is used in the following places:

* This value set is the designated 'entire code system' value set for v2 Manufacturers of Vaccines (code=MVX)

4.2.13.227.1 Code System Content

Manufacturers of Vaccines (code=MVX)

Code | Description | Nederlands (Dutch) | Comment | Version
AB | Abbott Laboratories | Abbott Laboratories | (includes Ross Products Division) | added v2.3
AD | Adams Laboratories, Inc. | Adams Laboratories, Inc. | | added v2.3
ALP | Alpha Therapeutic Corporation | Alpha Therapeutic Corporation | | added v2.3
AR | Armour | Armour | [Inactive--use AVB] | added v2.3

AVB | Aventis Behring L.L.C. | Aventis Behring L.L.C. | (formerly Centeon L.L.C.; includes Armour Pharmaceutical Company) [Inactive--use ZLB] CDC Changes made on: Feb. 28, 2006 | added v2.5

AVI | Aviron | Aviron | | added v2.3.1

BA | Baxter Healthcare Corporation | Baxter Healthcare Corporation | [Inactive--use BAH] | added v2.3

BAH | Baxter Healthcare Corporation | Baxter Healthcare Corporation | (includes Hyland Immuno, Immuno International AG, and North American Vaccine, Inc.) | added v2.5

BAY | Bayer Corporation | Bayer Corporation | (includes Miles, Inc. and Cutter Laboratories) | added v2.3

BP | Berna Products | Berna Products | [Inactive--use BPC] | added v2.3

BPC | Berna Products Corporation | Berna Products Corporation | (includes Swiss Serum and Vaccine Institute Berne) | added v2.3.1

CEN | Centeon L.L.C. | Centeon L.L.C. | [Inactive--use AVB] | added v2.3.1

CHI | Chiron Corporation | Chiron Corporation | [Inactive--use NOV] includes PowderJect Pharmaceuticals, Celltech Medeva Vaccines and Evans Medical Limited CDC Changes made on: July 14, 2006 | added v2.3.1

CMP | Celltech Medeva Pharmaceuticals | Celltech Medeva Pharmaceuticals | [Inactive--use NOV] CDC Changes made on: July 14, 2006 | added v2.5

CNJ | Cangene Corporation | Cangene Corporation | CDC Changes made on: Feb. 28, 2006 | added v2.6

CON | Connaught | Connaught | [Inactive--use PMC] | added v2.3

DVC | DynPort Vaccine Company, LLC | DynPort Vaccine Company, LLC | CDC Changes made on: July 14, 2006 | added v2.6

EVN | Evans Medical Limited | Evans Medical Limited | [Inactive--use NOV] CDC Changes made on: July 14, 2006 | added v2.3

GEO | GeoVax Labs, Inc. | GeoVax Labs, Inc. | CDC Changes made on: July 14, 2006 | added v2.6

GRE | Greer Laboratories, Inc. | Greer Laboratories, Inc. | | added v2.3

IAG | Immuno International AG | Immuno International AG | [Inactive--use BAH] | added v2.3.1

IM | Merieux | Merieux | [Inactive--use PMC] | added v2.3

IUS | Immuno-U.S., Inc. | Immuno-U.S., Inc. | | added v2.3

JPN | The Research Foundation for Microbial Diseases of Osaka University | The Research Foundation for Microbial Diseases of Osaka University | (BIKEN) | added v2.3

KGC | Korea Green Cross Corporation | Korea Green Cross Corporation | | added v2.3

LED | Lederle | Lederle | [Inactive--use WAL] | added v2.3

MA | Massachusetts Public Health Biologic Laboratories | Massachusetts Public Health Biologic Laboratories | [Inactive--use MBL] | added v2.3

MBL | Massachusetts Biologic Laboratories | Massachusetts Biologic Laboratories | (formerly Massachusetts Public Health Biologic Laboratories) | added v2.5

MED | MedImmune, Inc. | MedImmune, Inc. | | added v2.3.1

MIL | Miles | Miles | [Inactive--use BAY] | added v2.3

MIP | Bioport Corporation | Bioport Corporation | (formerly Michigan Biologic Products Institute) | added v2.3

MSD | Merck & Co., Inc. | Merck & Co., Inc. | | added v2.3

NAB | NABI | NABI | (formerly North American Biologicals, Inc.) | added v2.3

NAV | North American Vaccine, Inc. | North American Vaccine, Inc. | [Inactive--use BAH] | added v2.3.1

NOV | Novartis Pharmaceutical Corporation | Novartis Pharmaceutical Corporation | (includes Chiron, PowderJect Pharmaceuticals, Celltech Medeva Vaccines and Evans Limited, Ciba-Geigy Limited and Sandoz Limited) | added v2.3.1

NVX | Novavax, Inc. | Novavax, Inc. | CDC Changes made on: July 14, 2006 | added v2.6

NYB | New York Blood Center | New York Blood Center | | added v2.3

ORT | Ortho-Clinical Diagnostics | Ortho-Clinical Diagnostics | (formerly Ortho Diagnostic Systems, Inc.) | added v2.3.1

OTC | Organon Teknika Corporation | Organon Teknika Corporation | | added v2.3

OTH | Other manufacturer | Andere fabrikant | | added v2.3

PD | Parkedale Pharmaceuticals | Parkedale Pharmaceuticals | (formerly Parke-Davis) | added v2.3

PMC | sanofi pasteur | sanofi pasteur | (formerly Aventis Pasteur, Pasteur Merieux Connaught; includes Connaught Laboratories and Pasteur Merieux) CDC Changes made on: Feb. 28, 2006 | added v2.3.1

PRX | Praxis Biologics | Praxis Biologics | [Inactive--use WAL] | added v2.3

PWJ | PowderJect Pharmaceuticals | PowderJect Pharmaceuticals | (includes Celltech Medeva Vaccines and Evans Medical Limited) [Inactive--use NOV] CDC Changes made on: July 14, 2006 | added v2.5

SCL | Sclavo, Inc. | Sclavo, Inc. | | added v2.3

SI | Swiss Serum and Vaccine Inst. | Swiss Serum and Vaccine Inst. | [Inactive--use BPC] | added v2.3

SKB | GlaxoSmithKline | GlaxoSmithKline | (formerly SmithKline Beecham; includes SmithKline Beecham and Glaxo Welcome) | added v2.3

SOL | Solvay Pharmaceuticals | Solvay, Pharmaceuticals | CDC Changes made on: July 14, 2006 | added v2.6

TAL | Talecris Biotherapeutics | Talecris Biotherapeutics | (includes Bayer Biologicals) CDC Changes made on: Feb. 28, 2006 | added v2.6

UNK | Unknown manufacturer | Unknown manufacturer | | added v2.3

USA | United States Army Medical Research and Material Command | United States Army Medical Research and Material Command | | added v2.3.1

VXG | VaxGen | VaxGen | CDC Changes made on: July 14, 2006 | added v2.6

WA | Wyeth-Ayerst | Wyeth-Ayerst | [Inactive--use WAL] | added v2.3

WAL | Wyeth-Ayerst | Wyeth-Ayerst | (includes Wyeth-Lederle Vaccines and Pediatrics, Wyeth Laboratories, Lederle Laboratories, and Praxis Biologics) | added v2.3.1

ZLB | ZLB Behring | ZLB Behring | (includes Aventis Behring and Armour Pharmaceutical Company) CDC Changes made on: Feb. 28, 2006 | added v2.6

4.2.13.228 HL7 Version 2 Table 0228

URL: https://hl7.org/fhir/STU3/v2/0228/index.html

This page is part of the FHIR Specification (v3.0.2: STU 3). The current version which supercedes this version is 4.0.1. For a full list of available versions, see the Directory of published versions

Vocabulary Work Group | Maturity Level: N/A | External | Use Context: Any

This is a table defined as part of HL7 v2 . Related FHIR content: v2 Diagnosis Classification.

Summary

Name: | v2 Diagnosis Classification
Definition: | FHIR Value set/code system definition for HL7 v2 table 0228 (Diagnosis Classification)
Code System URL: | http://hl7.org/fhir/v2/0228
Value Set URL: | http://hl7.org/fhir/ValueSet/v2-0228
OID: | ??
CodeSystem Resource | XML / JSON
ValueSet Resource | XML / JSON

This value set is used in the following places:

* This value set is the designated 'entire code system' value set for v2 Diagnosis Classification

4.2.13.228.1 Code System Content

Diagnosis Classification

Code | Description | Deutsch (German) | Nederlands (Dutch) | Comment | Version
C | Consultation | Behandlung | Consult | | added v2.3
D | Diagnosis | Diagnose | Diagnose | | added v2.3
I | Invasive procedure not classified elsewhere (I.V., catheter, etc.) | Maßnahme | Invasieve procedure niet anders geclassificeerd (infuus, catether, etc.) | | added v2.3
M | Medication (antibiotic) | Medikation | Medicatie (antibioticum) | | added v2.3
O | Other | andere | Anders | | added v2.3
R | Radiological scheduling (not using ICDA codes) | Planung von radiologischen Untersuchungen | Radiologische planning (zonder gebruik te maken van ICDA codes) | | added v2.3
S | Sign and symptom | Symptome | Teken en symptoom | | added v2.3
T | Tissue diagnosis | Gewebebestimmung | Weefseldiagnose | | added v2.3

4.2.13.229 HL7 Version 2 Table 0229

URL: https://hl7.org/fhir/STU3/v2/0229/index.html

This page is part of the FHIR Specification (v3.0.2: STU 3). The current version which supercedes this version is 4.0.1. For a full list of available versions, see the Directory of published versions

Vocabulary Work Group | Maturity Level: N/A | External | Use Context: Any

This is a table defined as part of HL7 v2 . Related FHIR content: v2 DRG Payor.

Summary

Name: | v2 DRG Payor
Definition: | FHIR Value set/code system definition for HL7 v2 table 0229 (DRG Payor)
Code System URL: | http://hl7.org/fhir/v2/0229
Value Set URL: | http://hl7.org/fhir/ValueSet/v2-0229
OID: | ??
CodeSystem Resource | XML / JSON
ValueSet Resource | XML / JSON

This value set is used in the following places:

* This value set is the designated 'entire code system' value set for v2 DRG Payor

4.2.13.229.1 Code System Content

DRG Payor

Code | Description | Nederlands (Dutch) | Comment | Version
... | No suggested values defined | geen voorgestelde waarden | | added v2.8.2
C | Champus | Civilian Health and Medical Program of the Uniformed Services | deprecated | added v2.3, removed after v2.7.1
G | Managed Care Organization | Managed Care organisatie | deprecated | added v2.3, removed after v2.7.1
M | Medicare | Medicare | deprecated | added v2.3, removed after v2.7.1

4.2.13.230 HL7 Version 2 Table 0230

URL: https://hl7.org/fhir/STU3/v2/0230/index.html

This page is part of the FHIR Specification (v3.0.2: STU 3). The current version which supercedes this version is 4.0.1. For a full list of available versions, see the Directory of published versions

Vocabulary Work Group | Maturity Level: N/A | External | Use Context: Any

This is a table defined as part of HL7 v2 . Related FHIR content: v2 Procedure Functional Type.

Summary

Name: | v2 Procedure Functional Type
Definition: | FHIR Value set/code system definition for HL7 v2 table 0230 (Procedure Functional Type)
Code System URL: | http://hl7.org/fhir/v2/0230
Value Set URL: | http://hl7.org/fhir/ValueSet/v2-0230
OID: | ??
CodeSystem Resource | XML / JSON
ValueSet Resource | XML / JSON

This value set is used in the following places:

* This value set is the designated 'entire code system' value set for v2 Procedure Functional Type

4.2.13.230.1 Code System Content

Procedure Functional Type

Code | Description | Deutsch (German) | Nederlands (Dutch) | Comment | Version
A | Anesthesia | Narkose | Anesthesie | | added v2.3
D | Diagnostic procedure | Diagnosestellung | Diagnostische behandeling | | added v2.3
I | Invasive procedure not classified elsewhere (e.g. IV, catheter, etc.) | operativer Eingriff | Invasieve procedure niet anders geclassificeerd (bijv. infuus, catether, etc.) | | added v2.3
P | Procedure for treatment (therapeutic, including operations) | Behandlung | Behandelingsprocedure (therapeutisch inclusief operaties) | | added v2.3

4.2.13.231 HL7 Version 2 Table 0231

URL: https://hl7.org/fhir/STU3/v2/0231/index.html

This page is part of the FHIR Specification (v3.0.2: STU 3). The current version which supercedes this version is 4.0.1. For a full list of available versions, see the Directory of published versions

Vocabulary Work Group | Maturity Level: N/A | External | Use Context: Any

This is a table defined as part of HL7 v2 . Related FHIR content: v2 Student Status.

Summary

Name: | v2 Student Status
Definition: | FHIR Value set/code system definition for HL7 v2 table 0231 (Student Status)
Code System URL: | http://hl7.org/fhir/v2/0231
Value Set URL: | http://hl7.org/fhir/ValueSet/v2-0231
OID: | ??
CodeSystem Resource | XML / JSON
ValueSet Resource | XML / JSON

This value set is used in the following places:

* This value set is the designated 'entire code system' value set for v2 Student Status

4.2.13.231.1 Code System Content

Student Status

Code | Description | Nederlands (Dutch) | Comment | Version
F | Full-time student | Voltijdsstudent | | added v2.3
N | Not a student | Geen student | | added v2.3
P | Part-time student | Deeltijdstudent | | added v2.3

4.2.13.232 HL7 Version 2 Table 0232

URL: https://hl7.org/fhir/STU3/v2/0232/index.html

This page is part of the FHIR Specification (v3.0.2: STU 3). The current version which supercedes this version is 4.0.1. For a full list of available versions, see the Directory of published versions

Vocabulary Work Group | Maturity Level: N/A | External | Use Context: Any

This is a table defined as part of HL7 v2 . Related FHIR content: v2 - Insurance Company Contact Reason.

Summary

Name: | v2 - Insurance Company Contact Reason
Definition: | FHIR Value set/code system definition for HL7 v2 table 0232 (- Insurance Company Contact Reason)
Code System URL: | http://hl7.org/fhir/v2/0232
Value Set URL: | http://hl7.org/fhir/ValueSet/v2-0232
OID: | ??
CodeSystem Resource | XML / JSON
ValueSet Resource | XML / JSON

This value set is used in the following places:

* This value set is the designated 'entire code system' value set for v2 - Insurance Company Contact Reason

4.2.13.232.1 Code System Content

- Insurance Company Contact Reason

Code | Description | Nederlands (Dutch) | Comment | Version
01 | Medicare claim status | Medicare declaratiestatus | | added v2.3
02 | Medicaid claim status | Medicaid declaratiestatus | | added v2.3
03 | Name/address change | Naam/adreswijziging | | added v2.3

4.2.13.234 HL7 Version 2 Table 0234

URL: https://hl7.org/fhir/STU3/v2/0234/index.html

This page is part of the FHIR Specification (v3.0.2: STU 3). The current version which supercedes this version is 4.0.1. For a full list of available versions, see the Directory of published versions

Vocabulary Work Group | Maturity Level: N/A | External | Use Context: Any

This is a table defined as part of HL7 v2 . Related FHIR content: v2 Report Timing.

Summary

Name: | v2 Report Timing
Definition: | FHIR Value set/code system definition for HL7 v2 table 0234 (Report Timing)
Code System URL: | http://hl7.org/fhir/v2/0234
Value Set URL: | http://hl7.org/fhir/ValueSet/v2-0234
OID: | ??
CodeSystem Resource | XML / JSON
ValueSet Resource | XML / JSON

This value set is used in the following places:

* This value set is the designated 'entire code system' value set for v2 Report Timing

4.2.13.234.1 Code System Content

Report Timing

Code	Description	Nederlands (Dutch)	Comment	Version
10D	10 day report	10-daags verslag		added v2.3
15D	15 day report	15-daags verslag		added v2.3
30D	30 day report	30-daags verslag		added v2.3
3D	3 day report	3-daags verslag		added v2.3
7D	7 day report	7-daags verslag		added v2.3
AD	Additional information	Aanvullende informatie		added v2.3
CO	Correction	Correctie		added v2.3
DE	Device evaluation	Apparaatevaluatie		added v2.3
PD	Periodic	Periodiek		added v2.3
RQ	Requested information	Gevraagde informatie		added v2.3

4.2.13.235 HL7 Version 2 Table 0235

URL: https://hl7.org/fhir/STU3/v2/0235/index.html

This page is part of the FHIR Specification (v3.0.2: STU 3). The current version which supercedes this version is 4.0.1. For a full list of available versions, see the Directory of published versions

Vocabulary Work Group | Maturity Level: N/A | External | Use Context: Any

This is a table defined as part of HL7 v2 . Related FHIR content: v2 Report Source.

Summary

Name: | v2 Report Source
Definition: | FHIR Value set/code system definition for HL7 v2 table 0235 (Report Source)
Code System URL: | http://hl7.org/fhir/v2/0235
Value Set URL: | http://hl7.org/fhir/ValueSet/v2-0235
OID: | ??
CodeSystem Resource | XML / JSON
ValueSet Resource | XML / JSON

This value set is used in the following places:

* This value set is the designated 'entire code system' value set for v2 Report Source

4.2.13.235.1 Code System Content

Report Source

Code	Description	Nederlands (Dutch)	Comment	Version
C	Clinical trial	Clinical trial		added v2.3
D	Database/registry/poison control center	Database/register/toxicologisch centrum		added v2.3
E	Distributor	Distributeur		added v2.3
H	Health professional	Zorgprofessional		added v2.3
L	Literature	Literatuur		added v2.3
M	Manufacturer/marketing authority holder	Fabrikant/marketing autoriteithouder		added v2.3
N	Non-healthcare professional	Niet-zorg professional		added v2.3
O	Other	Anders		added v2.3
P	Patient	Patiënt		added v2.3
R	Regulatory agency	Toezichthoudend orgaan		added v2.3

4.2.13.236 HL7 Version 2 Table 0236

URL: https://hl7.org/fhir/STU3/v2/0236/index.html

This page is part of the FHIR Specification (v3.0.2: STU 3). The current version which supercedes this version is 4.0.1. For a full list of available versions, see the Directory of published versions

Vocabulary Work Group | Maturity Level: N/A | External | Use Context: Any

This is a table defined as part of HL7 v2 . Related FHIR content: v2 Event Reported To.

Summary

Name: | v2 Event Reported To
Definition: | FHIR Value set/code system definition for HL7 v2 table 0236 (Event Reported To)
Code System URL: | http://hl7.org/fhir/v2/0236
Value Set URL: | http://hl7.org/fhir/ValueSet/v2-0236
OID: | ??
CodeSystem Resource | XML / JSON
ValueSet Resource | XML / JSON

This value set is used in the following places:

* This value set is the designated 'entire code system' value set for v2 Event Reported To

4.2.13.236.1 Code System Content

Event Reported To

Code | Description | Nederlands (Dutch) | Comment | Version
D | Distributor | Distributeur | | added v2.3
L | Local facility/user facility | Lokale afdeling/gebruiker afdeling | | added v2.3
M | Manufacturer | Fabrikant | | added v2.3
R | Regulatory agency | Toezichthoudend orgaan | | added v2.3

4.2.13.237 HL7 Version 2 Table 0237

URL: https://hl7.org/fhir/STU3/v2/0237/index.html

This page is part of the FHIR Specification (v3.0.2: STU 3). The current version which supercedes this version is 4.0.1. For a full list of available versions, see the Directory of published versions

Vocabulary Work Group | Maturity Level: N/A | External | Use Context: Any

This is a table defined as part of HL7 v2 . Related FHIR content: v2 Event Qualification.

Summary

Name: | v2 Event Qualification
Definition: | FHIR Value set/code system definition for HL7 v2 table 0237 (Event Qualification)
Code System URL: | http://hl7.org/fhir/v2/0237
Value Set URL: | http://hl7.org/fhir/ValueSet/v2-0237
OID: | ??
CodeSystem Resource | XML / JSON
ValueSet Resource | XML / JSON

This value set is used in the following places:

* This value set is the designated 'entire code system' value set for v2 Event Qualification

4.2.13.237.1 Code System Content

Event Qualification

Code | Description | Nederlands (Dutch) | Comment | Version
A | Abuse | Misbruik | | added v2.3
B | Unexpected beneficial effect | Onverwacht goedaardig effect | | added v2.3
D | Dependency | Afhankelijkheid | | added v2.3
I | Interaction | Interactie | | added v2.3
L | Lack of expect therapeutic effect | Uitgebleven verwacht therapeutisch effect | | added v2.3
M | Misuse | Verkeerd gebruik | | added v2.3
O | Overdose | Overdosis | | added v2.3
W | Drug withdrawal | Medicatie onthouden | | added v2.3

4.2.13.238 HL7 Version 2 Table 0238

URL: https://hl7.org/fhir/STU3/v2/0238/index.html

This page is part of the FHIR Specification (v3.0.2: STU 3). The current version which supercedes this version is 4.0.1. For a full list of available versions, see the Directory of published versions

Vocabulary Work Group | Maturity Level: N/A | External | Use Context: Any

This is a table defined as part of HL7 v2 . Related FHIR content: v2 Event Seriousness.

Summary

Name: | v2 Event Seriousness
Definition: | FHIR Value set/code system definition for HL7 v2 table 0238 (Event Seriousness)
Code System URL: | http://hl7.org/fhir/v2/0238
Value Set URL: | http://hl7.org/fhir/ValueSet/v2-0238
OID: | ??
CodeSystem Resource | XML / JSON
ValueSet Resource | XML / JSON

This value set is used in the following places:

* This value set is the designated 'entire code system' value set for v2 Event Seriousness

4.2.13.238.1 Code System Content

Event Seriousness

Code | Description | Deutsch (German) | Nederlands (Dutch) | Comment | Version
N | No | Nein | Nee | | added v2.3
S | Significant | | Significant | | added v2.3
Y | Yes | Ja | Ja | | added v2.3

4.2.13.239 HL7 Version 2 Table 0239

URL: https://hl7.org/fhir/STU3/v2/0239/index.html

This page is part of the FHIR Specification (v3.0.2: STU 3). The current version which supercedes this version is 4.0.1. For a full list of available versions, see the Directory of published versions

Vocabulary Work Group | Maturity Level: N/A | External | Use Context: Any

This is a table defined as part of HL7 v2 . Related FHIR content: v2 Event Expected.

Summary

Name: | v2 Event Expected
Definition: | FHIR Value set/code system definition for HL7 v2 table 0239 (Event Expected)
Code System URL: | http://hl7.org/fhir/v2/0239
Value Set URL: | http://hl7.org/fhir/ValueSet/v2-0239
OID: | ??
CodeSystem Resource | XML / JSON
ValueSet Resource | XML / JSON

This value set is used in the following places:

* This value set is the designated 'entire code system' value set for v2 Event Expected

4.2.13.239.1 Code System Content

Event Expected

Code | Description | Deutsch (German) | Nederlands (Dutch) | Comment | Version
N | No | Nein | Nee | | added v2.3
U | Unknown | | Onbekend | | added v2.3
Y | Yes | Ja | Ja | | added v2.3

4.2.13.240 HL7 Version 2 Table 0240

URL: https://hl7.org/fhir/STU3/v2/0240/index.html

This page is part of the FHIR Specification (v3.0.2: STU 3). The current version which supercedes this version is 4.0.1. For a full list of available versions, see the Directory of published versions

Vocabulary Work Group | Maturity Level: N/A | External | Use Context: Any

This is a table defined as part of HL7 v2 . Related FHIR content: v2 Event Consequence.

Summary

Name: | v2 Event Consequence
Definition: | FHIR Value set/code system definition for HL7 v2 table 0240 (Event Consequence)
Code System URL: | http://hl7.org/fhir/v2/0240
Value Set URL: | http://hl7.org/fhir/ValueSet/v2-0240
OID: | ??
CodeSystem Resource | XML / JSON
ValueSet Resource | XML / JSON

This value set is used in the following places:

* This value set is the designated 'entire code system' value set for v2 Event Consequence

4.2.13.240.1 Code System Content

Event Consequence

Code | Description | Nederlands (Dutch) | Comment | Version
C | Congenital anomaly/birth defect | Congenitale anomalie/geboorteafwijking | | added v2.3
D | Death | Dood | | added v2.3
H | Caused hospitalized | Veroorzaakte hospitalisatie | | added v2.3
I | Incapacity which is significant, persistent or permanent | Significante beperking, langdurig of permanent | | added v2.3
J | Disability which is significant, persistent or permanent | Significante handicap, langdurig of permanent | | added v2.3
L | Life threatening | Levensbedreigend | | added v2.3
O | Other | Anders | | added v2.3
P | Prolonged hospitalization | Verlenging hospitalisatie | | added v2.3
R | Required intervention to prevent permanent impairment/damage | Vereiste interventie ter preventie van permanente handicap/schade | | added v2.3

4.2.13.241 HL7 Version 2 Table 0241

URL: https://hl7.org/fhir/STU3/v2/0241/index.html

This page is part of the FHIR Specification (v3.0.2: STU 3). The current version which supercedes this version is 4.0.1. For a full list of available versions, see the Directory of published versions

Vocabulary Work Group | Maturity Level: N/A | External | Use Context: Any

This is a table defined as part of HL7 v2 . Related FHIR content: v2 Patient Outcome.

Summary

Name: | v2 Patient Outcome
Definition: | FHIR Value set/code system definition for HL7 v2 table 0241 (Patient Outcome)
Code System URL: | http://hl7.org/fhir/v2/0241
Value Set URL: | http://hl7.org/fhir/ValueSet/v2-0241
OID: | ??
CodeSystem Resource | XML / JSON
ValueSet Resource | XML / JSON

This value set is used in the following places:

* This value set is the designated 'entire code system' value set for v2 Patient Outcome

4.2.13.241.1 Code System Content

Patient Outcome

Code | Description | Nederlands (Dutch) | Comment | Version
D | Died | Overleden | | added v2.3
F | Fully recovered | Volledig hersteld | | added v2.3
N | Not recovering/unchanged | Herstelt niet/ongewijzigd | | added v2.3
R | Recovering | Herstellende | | added v2.3
S | Sequelae | Sequenlae | | added v2.3
U | Unknown | Onbekend | | added v2.3
W | Worsening | Verslechterend | | added v2.3

4.2.13.242 HL7 Version 2 Table 0242

URL: https://hl7.org/fhir/STU3/v2/0242/index.html

This page is part of the FHIR Specification (v3.0.2: STU 3). The current version which supercedes this version is 4.0.1. For a full list of available versions, see the Directory of published versions

Vocabulary Work Group | Maturity Level: N/A | External | Use Context: Any

This is a table defined as part of HL7 v2 . Related FHIR content: v2 Primary Observer's Qualification.

Summary

Name: | v2 Primary Observer's Qualification
Definition: | FHIR Value set/code system definition for HL7 v2 table 0242 (Primary Observer's Qualification)
Code System URL: | http://hl7.org/fhir/v2/0242
Value Set URL: | http://hl7.org/fhir/ValueSet/v2-0242
OID: | ??
CodeSystem Resource | XML / JSON
ValueSet Resource | XML / JSON

This value set is used in the following places:

* This value set is the designated 'entire code system' value set for v2 Primary Observer's Qualification

4.2.13.242.1 Code System Content

Primary Observer's Qualification

Code | Description | Nederlands (Dutch) | Comment | Version
C | Health care consumer/patient | Zorgconsument/patiënt | | added v2.3
H | Other health professional | Andere zorgprofessional | | added v2.3
L | Lawyer/attorney | Advocaat/aanklager | | added v2.3

M | Mid-level professional (nurse, nurse practitioner, physician's assistant) | Mid-level professional (verpleegkundige, nurse practitioner, arts-assistent) | | added v2.3
O | Other non-health professional | Andere niet-zorg professional | | added v2.3
P | Physician (osteopath, homeopath) | Zorgverlener (osteopaat, homeopaat) | | added v2.3
R | Pharmacist | Apotheker | | added v2.3

4.2.13.243 HL7 Version 2 Table 0243

URL: https://hl7.org/fhir/STU3/v2/0243/index.html

This page is part of the FHIR Specification (v3.0.2: STU 3). The current version which supercedes this version is 4.0.1. For a full list of available versions, see the Directory of published versions

Vocabulary Work Group | Maturity Level: N/A | External | Use Context: Any

This is a table defined as part of HL7 v2 . Related FHIR content: v2 Identity May Be Divulged.

Summary

Name: | v2 Identity May Be Divulged
Definition: | FHIR Value set/code system definition for HL7 v2 table 0243 (Identity May Be Divulged)
Code System URL: | http://hl7.org/fhir/v2/0243
Value Set URL: | http://hl7.org/fhir/ValueSet/v2-0243
OID: | ??
CodeSystem Resource | XML / JSON
ValueSet Resource | XML / JSON

This value set is used in the following places:

* This value set is the designated 'entire code system' value set for v2 Identity May Be Divulged

4.2.13.243.1 Code System Content

Identity May Be Divulged

Code | Description | Deutsch (German) | Nederlands (Dutch) | Comment | Version
N | No | Nein | Nee | | added v2.3
NA | Not applicable | | Niet van toepassing | | added v2.3
Y | Yes | Ja | Ja | | added v2.3

4.2.13.247 HL7 Version 2 Table 0247

URL: https://hl7.org/fhir/STU3/v2/0247/index.html

This page is part of the FHIR Specification (v3.0.2: STU 3). The current version which supercedes this version is 4.0.1. For a full list of available versions, see the Directory of published versions

Vocabulary Work Group | Maturity Level: N/A | External | Use Context: Any

This is a table defined as part of HL7 v2 . Related FHIR content: v2 Status of Evaluation.

Summary

Name: | v2 Status of Evaluation
Definition: | FHIR Value set/code system definition for HL7 v2 table 0247 (Status of Evaluation)
Code System URL: | http://hl7.org/fhir/v2/0247
Value Set URL: | http://hl7.org/fhir/ValueSet/v2-0247
OID: | ??
CodeSystem Resource | XML / JSON
ValueSet Resource | XML / JSON

This value set is used in the following places:

* This value set is the designated 'entire code system' value set for v2 Status of Evaluation

4.2.13.247.1 Code System Content

Status of Evaluation

Code | Description | Nederlands (Dutch) | Comment | Version
A | Evaluation anticipated, but not yet begun | Evaluatie, nog niet begonnen | | added v2.3
C | Product received in condition which made analysis impossible | Product ontvangen in conditie die analyse onmogelijk maakt | | added v2.3
D | Product discarded -- unable to follow up | Product weggegooid -- kon niet opvolgen | | added v2.3
I | Product remains implanted -- unable to follow up | Product blijft geïmplanteerd -- kan niet opvolgen | | added v2.3
K | Problem already known, no evaluation necessary | Probleem reeds bekend, geen evaluatie noodzakelijk | | added v2.3
O | Other | Anders | | added v2.3
P | Evaluation in progress | Evaluatie is gaande | | added v2.3
Q | Product under quarantine -- unable to follow up | Product in quarantaine -- kan niet opvolgen | | added v2.3
R | Product under recall/corrective action | Product wordt teruggeroepen/correctieve actie | | added v2.3
U | Product unavailable for follow up investigation | Product niet beschikbaar voor opvolgend onderzoek | | added v2.3
X | Product not made by company | Product wordt niet door bedrijf gemaakt | | added v2.3
Y | Evaluation completed | Evaluatie voltooid | | added v2.3

4.2.13.248 HL7 Version 2 Table 0248

URL: https://hl7.org/fhir/STU3/v2/0248/index.html

This page is part of the FHIR Specification (v3.0.2: STU 3). The current version which supercedes this version is 4.0.1. For a full list of available versions, see the Directory of published versions

Vocabulary Work Group | Maturity Level: N/A | External | Use Context: Any

This is a table defined as part of HL7 v2 . Related FHIR content: v2 Product Source.

Summary

Name: | v2 Product Source
Definition: | FHIR Value set/code system definition for HL7 v2 table 0248 (Product Source)
Code System URL: | http://hl7.org/fhir/v2/0248
Value Set URL: | http://hl7.org/fhir/ValueSet/v2-0248
OID: | ??
CodeSystem Resource | XML / JSON
ValueSet Resource | XML / JSON

This value set is used in the following places:

* This value set is the designated 'entire code system' value set for v2 Product Source

4.2.13.248.1 Code System Content

Product Source

Code | Description | Nederlands (Dutch) | Comment | Version
A | Actual product involved in incident was evaluated | Exacte product betrokken in incident is geëvalueerd | | added v2.3
L | A product from the same lot as the actual product involved was evaluated | Een product uit dezelfde partij als het exacte betrokken product is geëvalueerd | | added v2.3
N | A product from a controlled/non-related inventory was evaluated | Een product van een beheerde/niet-gerelateerde voorraad geëvalueerd | | added v2.3
R | A product from a reserve sample was evaluated | Een product uit een reserve sample is geëvalueerd | | added v2.3

4.2.13.250 HL7 Version 2 Table 0250

URL: https://hl7.org/fhir/STU3/v2/0250/index.html

This page is part of the FHIR Specification (v3.0.2: STU 3). The current version which supercedes this version is 4.0.1. For a full list of available versions, see the Directory of published versions

Vocabulary Work Group | Maturity Level: N/A | External | Use Context: Any

This is a table defined as part of HL7 v2 . Related FHIR content: v2 Relatedness Assessment.

Summary

Name: | v2 Relatedness Assessment
Definition: | FHIR Value set/code system definition for HL7 v2 table 0250 (Relatedness Assessment)
Code System URL: | http://hl7.org/fhir/v2/0250
Value Set URL: | http://hl7.org/fhir/ValueSet/v2-0250
OID: | ??
CodeSystem Resource | XML / JSON
ValueSet Resource | XML / JSON

This value set is used in the following places:

* This value set is the designated 'entire code system' value set for v2 Relatedness Assessment

4.2.13.250.1 Code System Content

Relatedness Assessment

Code | Description | Nederlands (Dutch) | Comment | Version
H | Highly probable | Zeer waarschijnlijk | | added v2.3
I | Improbable | Niet waarschijnlijk | | added v2.3
M | Moderately probable | Gemiddeld waarschijnlijk | | added v2.3
N | Not related | Niet gerelateerd | | added v2.3
S | Somewhat probable | Enigzins waarschijnlijk | | added v2.3

4.2.13.251 HL7 Version 2 Table 0251

URL: https://hl7.org/fhir/STU3/v2/0251/index.html

This page is part of the FHIR Specification (v3.0.2: STU 3). The current version which supercedes this version is 4.0.1. For a full list of available versions, see the Directory of published versions

Vocabulary Work Group | Maturity Level: N/A | External | Use Context: Any

This is a table defined as part of HL7 v2 . Related FHIR content: v2 Action Taken in Response to the Event.

Summary

Name: | v2 Action Taken in Response to the Event
Definition: | FHIR Value set/code system definition for HL7 v2 table 0251 (Action Taken in Response to the Event)
Code System URL: | http://hl7.org/fhir/v2/0251
Value Set URL: | http://hl7.org/fhir/ValueSet/v2-0251
OID: | ??
CodeSystem Resource | XML / JSON
ValueSet Resource | XML / JSON

This value set is used in the following places:

* This value set is the designated 'entire code system' value set for v2 Action Taken in Response to the Event

4.2.13.251.1 Code System Content

Action Taken in Response to the Event

Code | Description | Nederlands (Dutch) | Comment | Version
DI | Product dose or frequency of use increased | Productdosis of gebruiksfrequentie verhoogd | | added v2.3
DR | Product dose or frequency of use reduced | Productdosis of gebruiksfrequentie verlaagd | | added v2.3
N | None | Geen | | added v2.3
OT | Other | Anders | | added v2.3
WP | Product withdrawn permanently | Product permanent teruggetrokken | | added v2.3
WT | Product withdrawn temporarily | Product tijdelijk teruggetrokken | | added v2.3

4.2.13.252 HL7 Version 2 Table 0252

URL: https://hl7.org/fhir/STU3/v2/0252/index.html

This page is part of the FHIR Specification (v3.0.2: STU 3). The current version which supercedes this version is 4.0.1. For a full list of available versions, see the Directory of published versions

Vocabulary Work Group | Maturity Level: N/A | External | Use Context: Any

This is a table defined as part of HL7 v2 . Related FHIR content: v2 Causality Observations.

Summary

Name: | v2 Causality Observations
Definition: | FHIR Value set/code system definition for HL7 v2 table 0252 (Causality Observations)
Code System URL: | http://hl7.org/fhir/v2/0252
Value Set URL: | http://hl7.org/fhir/ValueSet/v2-0252
OID: | ??
CodeSystem Resource | XML / JSON
ValueSet Resource | XML / JSON

This value set is used in the following places:

* This value set is the designated 'entire code system' value set for v2 Causality Observations

4.2.13.252.1 Code System Content

Causality Observations

Code | Description | Nederlands (Dutch) | Comment | Version
AW | Abatement of event after product withdrawn | Vermindering gebeurtenis na terugtrekken product | | added v2.3
BE | Event recurred after product reintroduced | Gebeurtenis trad opnieuw op na herintroductie product | | added v2.3
DR | Dose response observed | Dosis reactie geobserveerd | | added v2.3
EX | Alternative explanations for the event available | Alternatieve verklaringen voor gebeurtenis beschikbaar | | added v2.3
IN | Event occurred after product introduced | Gebeurtenis trad op na introductie product | | added v2.3
LI | Literature reports association of product with event | Literatuur vermeldt koppeling van product met gebeurtenis | | added v2.3
OE | Occurrence of event was confirmed by objective evidence | Optreden van gebeurtenis is bevestigd door objectief bewijs | | added v2.3
OT | Other | Anders | | added v2.3
PL | Effect observed when patient receives placebo | Effect geobserveerd wanneer patiënt placebo krijgt | | added v2.3
SE | Similar events in past for this patient | Vergelijkbare gebeurtenissen in verleden voor deze patiënt | | added v2.3
TC | Toxic levels of product documented in blood or body fluids | Toxische niveaus van product gedocumenteerd in bloed of lichaamssappen | | added v2.3

4.2.13.253 HL7 Version 2 Table 0253

URL: https://hl7.org/fhir/STU3/v2/0253/index.html

This page is part of the FHIR Specification (v3.0.2: STU 3). The current version which supercedes this version is 4.0.1. For a full list of available versions, see the Directory of published versions

Vocabulary Work Group | Maturity Level: N/A | External | Use Context: Any

This is a table defined as part of HL7 v2 . Related FHIR content: v2 Indirect Exposure Mechanism.

Summary

Name: | v2 Indirect Exposure Mechanism
Definition: | FHIR Value set/code system definition for HL7 v2 table 0253 (Indirect Exposure Mechanism)
Code System URL: | http://hl7.org/fhir/v2/0253

Value Set URL: | http://hl7.org/fhir/ValueSet/v2-0253
OID: | ??
CodeSystem Resource | XML / JSON
ValueSet Resource | XML / JSON

This value set is used in the following places:

* This value set is the designated 'entire code system' value set for v2 Indirect Exposure Mechanism

4.2.13.253.1 Code System Content

Indirect Exposure Mechanism

Code | Description | Nederlands (Dutch) | Comment | Version
B | Breast milk | Borstmelk | | added v2.3
F | Father | Vader | | added v2.3
O | Other | Anders | | added v2.3
P | Transplacental | Via placenta | | added v2.3
X | Blood product | Bloedproduct | | added v2.3

4.2.13.254 HL7 Version 2 Table 0254

URL: https://hl7.org/fhir/STU3/v2/0254/index.html

This page is part of the FHIR Specification (v3.0.2: STU 3). The current version which supercedes this version is 4.0.1. For a full list of available versions, see the Directory of published versions

Vocabulary Work Group | Maturity Level: N/A | External | Use Context: Any

This is a table defined as part of HL7 v2 . Related FHIR content: v2 Kind of Quantity.

Summary

Name: | v2 Kind of Quantity
Definition: | FHIR Value set/code system definition for HL7 v2 table 0254 (Kind of Quantity)
Code System URL: | http://hl7.org/fhir/v2/0254
Value Set URL: | http://hl7.org/fhir/ValueSet/v2-0254
OID: | ??
CodeSystem Resource | XML / JSON
ValueSet Resource | XML / JSON

This value set is used in the following places:

* This value set is the designated 'entire code system' value set for v2 Kind of Quantity

4.2.13.254.1 Code System Content

Kind of Quantity

Code | Description | Nederlands (Dutch) | Comment | Version
ABS | Absorbance | Absorptie | | added v2.3
ACNC | Concentration, Arbitrary Substance | Concentratie, arbitraire substantie | | added v2.3
ACT | Activity | Activiteit | * | added v2.3
APER | Appearance | Voorkomen | | added v2.3
ARB | Arbitrary | Arbitrair | * | added v2.3
AREA | Area | Gebied | | added v2.3
ASPECT | Aspect | Aspect | | added v2.3
CACT | Catalytic Activity | Katalytische activiteit | * | added v2.3
CCNT | Catalytic Content | Katalytische inhoud | * | added v2.3
CCRTO | Catalytic Concentration Ratio | Katalytische concentratieverhouding | | added v2.3
CFR | Catalytic Fraction | Katalytische fractie | * | added v2.3
CLAS | Class | Klasse | | added v2.3
CNC | Catalytic Concentration | Katalytische concentratie | * | added v2.3
CNST | Constant | Constante | * | added v2.3
COEF | Coefficient | Coëfficiënt | * | added v2.3
COLOR | Color | Kleur | | added v2.3
CONS | Consistency | Consistentie | | added v2.3
CRAT | Catalytic Rate | Katalytische snelheid | * | added v2.3
CRTO | Catalytic Ratio | Katalytische verhouding | | added v2.3
DEN | Density | Dichtheid | | added v2.3
DEV | Device | Apparaat | | added v2.3
DIFF | Difference | Verschil | * | added v2.3
ELAS | Elasticity | Elasticiteit | | added v2.3
ELPOT | Electrical Potential (Voltage) | Electrische potentiaal (voltage) | | added v2.3
ELRAT | Electrical current (amperage) | Electrische stroom (amperage) | | added v2.3
ELRES | Electrical Resistance | Electrische weerstand | | added v2.3
ENGR | Energy | Energie | | added v2.3
ENT | Entitic | Entiteit-gerelateerd | * | added v2.3
ENTCAT | Entitic Catalytic Activity | Entiteit-gerelateerde katalytische activiteit | * | added v2.3
ENTNUM | Entitic Number | Entiteit-gerelateerd aantal | * | added v2.3

ENTSUB | Entitic Substance of Amount | Entiteit-gerelateerde substantie van hoeveelheid | * | added v2.3
ENTVOL | Entitic Volume | Entiteit-gerelateerd volume | * | added v2.3
EQL | Equilibrium | Evenwicht | | added v2.3
FORCE | Mechanical force | Mechanische kracht | | added v2.3
FREQ | Frequency | Frequentie | | added v2.3
IMP | Impression/ interpretation of study | Indruk/interpretatie van onderzoek | | added v2.3
KINV | Kinematic Viscosity | Kinematische viscositeit | * | added v2.3
LEN | Length | Lengte | | added v2.3
LINC | Length Increment | Lengte increment | * | added v2.3
LIQ | Liquefaction | Liquefactie | * | added v2.3
MASS | Mass | Massa | * | added v2.3
MCNC | Mass Concentration | Massa concentratie | * | added v2.3
MCNT | Mass Content | Massa inhoud | | added v2.3
MCRTO | Mass Concentration Ratio | Massa concentratie verhouding | * | added v2.3
MFR | Mass Fraction | Massa fractie | * | added v2.3
MGFLUX | Magnetic flux | Magnetische flux | | added v2.3
MINC | Mass Increment | Massa increment | * | added v2.3
MORPH | Morphology | Morfologie | | added v2.3
MOTIL | Motility | Beweeglijkheid | | added v2.3
MRAT | Mass Rate | Massa snelheid | * | added v2.3
MRTO | Mass Ratio | Massa verhouding | * | added v2.3
NCNC | Number Concentration | Aantal concentratie | * | added v2.3
NCNT | Number Content | Aantal inhoud | * | added v2.3
NFR | Number Fraction | Aantal fractie | * | added v2.3
NRTO | Number Ratio | Aantal verhouding | * | added v2.3
NUM | Number | Aantal | * | added v2.3
OD | Optical density | Optische dichtheid | | added v2.3
OSMOL | Osmolality | Osmolaliteit | * | added v2.3
PRES | Pressure (Partial) | Druk (partiële) | | added v2.3
PRID | Presence/Identity/Existence | Aanwezigheid/identiteit/existentie | | added v2.3
PWR | Power (wattage) | Kracht (wattage) | | added v2.3
RANGE | Ranges | Bereiken | * | added v2.3
RATIO | Ratios | Verhoudingen | * | added v2.3
RCRLTM | Reciprocal Relative Time | Wederzijdse relatieve tijd | * | added v2.3
RDEN | Relative Density | Relatieve dichtheid | * | added v2.3
REL | Relative | Relatief | * | added v2.3
RLMCNC | Relative Mass Concentration | Relatieve massa concentratie | * | added v2.3
RLSCNC | Relative Substance Concentration | Relatieve substantie concentratie | * | added v2.3
RLTM | Relative Time | Relatieve tijd | * | added v2.3
SATFR | Saturation Fraction | Saturatie factie | * | added v2.3
SCNC | Substance Concentration | Substantie concentratie | * | added v2.3
SCNCIN | Substance Concentration Increment | Substantie concentratie increment | * | added v2.3
SCNT | Substance Content | Substantie inhoud | * | added v2.3
SCNTR | Substance Content Rate | Substantie inhoud verhouding | * | added v2.3
SCRTO | Substance Concentration Ratio | Substantie concentratie verhouding | * | added v2.3
SFR | Substance Fraction | Substantie fractie | * | added v2.3
SHAPE | Shape | Vorm | | added v2.3
SMELL | Smell | Reuk | | added v2.3
SRAT | Substance Rate | Substantie snelheid | * | added v2.3
SRTO | Substance Ratio | Substantie verhouding | * | added v2.3
SUB | Substance Amount | Substantie hoeveelheid | * | added v2.3
SUSC | Susceptibility | Gevoeligheid | * | added v2.3
TASTE | Taste | Smaak | | added v2.3
TEMP | Temperature | Temperatuur | * | added v2.3
TEMPDF | Temperature Difference | Temperatuurverschil | * | added v2.3
TEMPIN | Temperature Increment | Temperatuur increment | * | added v2.3
THRMCNC | Threshold Mass Concentration | Grenswaarde massa concentratie | * | added v2.3
THRSCNC | Threshold Substance Concentration | Grenswaarde substantie concentratie | * | added v2.3
TIME | Time (e.g. seconds) | Tijd (bijv. seconden) | * | added v2.3
TITR | Dilution Factor (Titer) | Verdunningsfactor (titer) | * | added v2.3
TMDF | Time Difference | Tijdverschil | * | added v2.3
TMSTP | Time Stamp-Date and Time | Tijdstempel - Datum en tijd | * | added v2.3
TRTO | Time Ratio | Tijd verhouding | * | added v2.3
TYPE | Type | Type | * | added v2.3
VCNT | Volume Content | Volume inhoud | * | added v2.3
VEL | Velocity | Snelheid | * | added v2.3
VELRT | Velocity Ratio | Snelheid verhouding | * | added v2.3
VFR | Volume Fraction | Volume fractie | * | added v2.3
VISC | Viscosity | Viscositeit | * | added v2.3
VOL | Volume | Volume | * | added v2.3
VRAT | Volume Rate | Volume snelheid | * | added v2.3
VRTO | Volume Ratio | Volume verhouding | * | added v2.3

4.2.13.255 HL7 Version 2 Table 0255

URL: https://hl7.org/fhir/STU3/v2/0255/index.html

This page is part of the FHIR Specification (v3.0.2: STU 3). The current version which supercedes this version is 4.0.1. For a full list of available versions, see the Directory of published versions

Vocabulary Work Group | Maturity Level: N/A | External | Use Context: Any

This is a table defined as part of HL7 v2 . Related FHIR content: v2 Duration Categories.

Summary

Name: | v2 Duration Categories
Definition: | FHIR Value set/code system definition for HL7 v2 table 0255 (Duration Categories)
Code System URL: | http://hl7.org/fhir/v2/0255
Value Set URL: | http://hl7.org/fhir/ValueSet/v2-0255
OID: | ??
CodeSystem Resource | XML / JSON
ValueSet Resource | XML / JSON

This value set is used in the following places:

* This value set is the designated 'entire code system' value set for v2 Duration Categories

4.2.13.255.1 Code System Content

Duration Categories

Code | Description | Nederlands (Dutch) | Comment | Version
* | (asterisk) Life of the "unit." Used for blood products. | (asterisk) Leven van de "eenheid". Voor bloedproducten | | added v2.4
* (star) | Life of the "unit." Used for blood products. | Leven van de "eenheid". Voor bloedproducten | Used for blood products. | added v2.3, removed after v2.3.1
12H | 12 hours | 12 uur | | added v2.3
1H | 1 hour | 1 uur | | added v2.3
1L | 1 months (30 days) | 1 maand (30 dagen) | | added v2.3
1W | 1 week | 1 week | | added v2.3
2.5H | 2Â½ hours | 2 1/2 uur | | added v2.3
24H | 24 hours | 24 uur | | added v2.3
2D | 2 days | 2 dagen | | added v2.3
2H | 2 hours | 2 uur | | added v2.3
2L | 2 months | 2 maanden | | added v2.3
2W | 2 weeks | 2 weken | | added v2.3
30M | 30 minutes | 30 minuten | | added v2.3
3D | 3 days | 3 dagen | | added v2.3
3H | 3 hours | 3 uur | | added v2.3
3L | 3 months | 3 maanden | | added v2.3
3W | 3 weeks | 3 weken | | added v2.3
4D | 4 days | 4 dagen | | added v2.3
4H | 4 hours | 4 uur | | added v2.3
4W | 4 weeks | 4 weken | | added v2.3
5D | 5 days | 5 dagen | | added v2.3
5H | 5 hours | 4 uur | | added v2.3
6D | 6 days | 6 dagen | | added v2.3
6H | 6 hours | 6 uur | | added v2.3
7H | 7 hours | 7 uur | | added v2.3
8H | 8 hours | 8 uur | | added v2.3
PT | To identify measures at a point in time. This is a synonym for "spot" or "random" as applied to urine measurements. | Voor identificatie metingen op een moment in de tijd. Dit is een een synoniem voor "punt" or "willekeurig" zoals toegepast in urinemetingen. | This is a synonym for "spot" or "random" as applied to ine measurements. | added v2.3

4.2.13.256 HL7 Version 2 Table 0256

URL: https://hl7.org/fhir/STU3/v2/0256/index.html

This page is part of the FHIR Specification (v3.0.2: STU 3). The current version which supercedes this version is 4.0.1. For a full list of available versions, see the Directory of published versions

Vocabulary Work Group | Maturity Level: N/A | External | Use Context: Any

This is a table defined as part of HL7 v2 . Related FHIR content: v2 Time Delay Post Challenge.

Summary

Name: | v2 Time Delay Post Challenge
Definition: | FHIR Value set/code system definition for HL7 v2 table 0256 (Time Delay Post Challenge)
Code System URL: | http://hl7.org/fhir/v2/0256
Value Set URL: | http://hl7.org/fhir/ValueSet/v2-0256
OID: | ??
CodeSystem Resource | XML / JSON
ValueSet Resource | XML / JSON

This value set is used in the following places:

* This value set is the designated 'entire code system' value set for v2 Time Delay Post Challenge

4.2.13.256.1 Code System Content

Time Delay Post Challenge

Code | Description | Nederlands (Dutch) | Comment | Version
10D | 10 days | 10 dagen | | added v2.3
10M | 10 minutes post challenge | 10 minuten post uitdaging | | added v2.3
12H | 12 hours post challenge | 12 uur post uitdaging | | added v2.3
15M | 15 minutes post challenge | 15 minuten post uitdaging | | added v2.3
1H | 1 hour post challenge | 1 uur post uitdaging | | added v2.3
1L | 1 month (30 days) post challenge | 1 maand (30 dagen) post uitdaging | | added v2.3
1M | 1 minute post challenge | 1 minuut post uitdaging | | added v2.3
1W | 1 week | 1 week | | added v2.3
2.5H | 2 Â½ hours post challenge | 2 1/2 uur post uitdaging | | added v2.3
20M | 20 minutes post challenge | 20 minuten post uitdaging | | added v2.3
24H | 24 hours post challenge | 24 uur post uitdaging | | added v2.3
25M | 25 minutes post challenge | 25 minuten post uitdaging | | added v2.3
2D | 2 days | 2 dagen | | added v2.3
2H | 2 hours post challenge | 2 uur post uitdaging | | added v2.3
2L | 2 months (60 days) post challenge | 2 maanden (60 dagen) post uitdaging | | added v2.3
2M | 2 minutes post challenge | 2 minuten post uitdaging | | added v2.3
2W | 2 weeks | 2 weken | | added v2.3
30M | 30 minutes post challenge | 30 minuten post uitdaging | | added v2.3
3D | 3 days | 3 dagen | | added v2.3
3H | 3 hours post challenge | 3 uur post uitdaging | | added v2.3
3L | 3 months (90 days) post challenge | 3 maanden (90 dagen) post uitdaging | | added v2.3
3M | 3 minutes post challenge | 3 minuten post uitdaging | | added v2.3
3W | 3 weeks | 3 weken | | added v2.3
4D | 4 days | 4 dagen | | added v2.3
4H | 4 hours post challenge | 4 uur post uitdaging | | added v2.3
4M | 4 minutes post challenge | 4 minuten post uitdaging | | added v2.3
4W | 4 weeks | 4 weken | | added v2.3
5D | 5 days | 5 dagen | | added v2.3
5H | 5 hours post challenge | 5 uur post uitdaging | | added v2.3
5M | 5 minutes post challenge | 5 minuten post uitdaging | | added v2.3
6D | 6 days | 7 dagen | | added v2.3
6H | 6 hours post challenge | 6 uur post uitdaging | | added v2.3
6M | 6 minutes post challenge | 6 minuten post uitdaging | | added v2.3
7D | 7 days | 7 dagen | | added v2.3
7H | 7 hours post challenge | 7 uur post uitdaging | | added v2.3
7M | 7 minutes post challenge | 7 minuten post uitdaging | | added v2.3
8H | 8 hours post challenge | 8 uur post uitdaging | | added v2.3
8H SHIFT | 8 hours aligned on nursing shifts | 8 uur volgens verleegdiensten | | added v2.3
8M | 8 minutes post challenge | 8 minuten post uitdaging | | added v2.3
9M | 9 minutes post challenge | 9 minuten post uitdaging | | added v2.3
BS | Baseline (time just before the challenge) | Nulmeting (tijd net voor de uitdaging) | | added v2.3
PEAK | The time post drug dose at which the highest drug level is reached (differs by drug) | De tijd na medicatiedosis waarop het hoogste medicatieniveau is bereikt (verschilt per medicament) | | added v2.3
RANDOM | Time from the challenge, or dose not specified. (random) | Tijd vanaf uitdaging of dosis niet gespecificeerd. (willekeurig) | | added v2.3
TROUGH | The time post drug dose at which the lowest drug level is reached (varies with drug) | De tijd na medicatiedosis waarop het laagste medicatieniveau is bereikt (verschilt per medicament) | | added v2.3

4.2.13.257 HL7 Version 2 Table 0257

URL: https://hl7.org/fhir/STU3/v2/0257/index.html

This page is part of the FHIR Specification (v3.0.2: STU 3). The current version which supercedes this version is 4.0.1. For a full list of available versions, see the Directory of published versions

Vocabulary Work Group | Maturity Level: N/A | External | Use Context: Any

This is a table defined as part of HL7 v2 . Related FHIR content: v2 Nature of Challenge.

Summary

Name: | v2 Nature of Challenge
Definition: | FHIR Value set/code system definition for HL7 v2 table 0257 (Nature of Challenge)
Code System URL: | http://hl7.org/fhir/v2/0257
Value Set URL: | http://hl7.org/fhir/ValueSet/v2-0257
OID: | ??
CodeSystem Resource | XML / JSON
ValueSet Resource | XML / JSON

This value set is used in the following places:

* This value set is the designated 'entire code system' value set for v2 Nature of Challenge

4.2.13.257.1 Code System Content

Nature of Challenge

Code | Description | Nederlands (Dutch) | Comment | Version
CFST | Fasting (no calorie intake) for the period specified in the time component of the term, e.g. 1H POST CFST | Vasten (geen calorische inname) voor de opgegeven periode in het tijdcomponent van de termijn, bijv. 1H POST CFST | | added v2.3
EXCZ | Exercise undertaken as challenge (can be quantified) | Oefening ondernomen als uitdaging (kan worden gekwantificeerd) | | added v2.3
FFST | No fluid intake for the period specified in the time component of the term | Geen vloeistofinname voor de opgegeven periode in het tijdcomponent van de termijn | | added v2.3

4.2.13.258 HL7 Version 2 Table 0258

URL: https://hl7.org/fhir/STU3/v2/0258/index.html

This page is part of the FHIR Specification (v3.0.2: STU 3). The current version which supercedes this version is 4.0.1. For a full list of available versions, see the Directory of published versions

Vocabulary Work Group | Maturity Level: N/A | External | Use Context: Any

This is a table defined as part of HL7 v2 . Related FHIR content: v2 Relationship Modifier.

Summary

Name: | v2 Relationship Modifier
Definition: | FHIR Value set/code system definition for HL7 v2 table 0258 (Relationship Modifier)
Code System URL: | http://hl7.org/fhir/v2/0258
Value Set URL: | http://hl7.org/fhir/ValueSet/v2-0258
OID: | ??
CodeSystem Resource | XML / JSON
ValueSet Resource | XML / JSON

This value set is used in the following places:

* This value set is the designated 'entire code system' value set for v2 Relationship Modifier

4.2.13.258.1 Code System Content

Relationship Modifier

Code | Description | Nederlands (Dutch) | Comment | Version
BPU | Blood product unit | Bloedproducteenheid | | added v2.3
CONTROL | Control | | | added v2.3
DONOR | Donor | Donor | | added v2.3
PATIENT | Patient | Patiënt | | added v2.3

4.2.13.259 HL7 Version 2 Table 0259

URL: https://hl7.org/fhir/STU3/v2/0259/index.html

This page is part of the FHIR Specification (v3.0.2: STU 3). The current version which supercedes this version is 4.0.1. For a full list of available versions, see the Directory of published versions

Vocabulary Work Group | Maturity Level: N/A | External | Use Context: Any

This is a table defined as part of HL7 v2 . Related FHIR content: v2 Modality.

Summary

Name: | v2 Modality
Definition: | FHIR Value set/code system definition for HL7 v2 table 0259 (Modality)
Code System URL: | http://hl7.org/fhir/v2/0259
Value Set URL: | http://hl7.org/fhir/ValueSet/v2-0259
OID: | ??
CodeSystem Resource | XML / JSON
ValueSet Resource | XML / JSON

This value set is used in the following places:

* This value set is the designated 'entire code system' value set for v2 Modality

4.2.13.259.1 Code System Content

Modality

Code | Description | Nederlands (Dutch) | Comment | Version
AS | Angioscopy | Angioscopie | | added v2.3
BS | Biomagnetic imaging | Biomagnetische beeldvorming | | added v2.3
CD | Color flow Doppler | Kleurverloop Doppler | | added v2.3
CP | Colposcopy | Colposcopie | | added v2.3
CR | Computed radiography | Computed Radiography | | added v2.3
CS | Cystoscopy | Cystoscopie | | added v2.3

CT | Computed tomography | Computed Tomography | | added v2.3
DD | Duplex Doppler | Duplex Doppler | | added v2.3
DG | Diapanography | Mammografie | | added v2.3
DM | Digital microscopy | Digitale microscopie | | added v2.3
EC | Echocardiography | Echocardiografie | | added v2.3
ES | Endoscopy | Endoscopie | | added v2.3
FA | Fluorescein angiography | Fluoresceïne angiografie | | added v2.3
FS | Fundoscopy | Fundoscopie | | added v2.3
LP | Laparoscopy | Laparoscopie | | added v2.3
LS | Laser surface scan | Laser oppervlakte scan | | added v2.3
MA | Magnetic resonance angiography | Magnetische resonantie angiografie | | added v2.3
MS | Magnetic resonance spectroscopy | Magnetische resonantie spectrografie | | added v2.3
NM | Nuclear Medicine (radioisotope study) | Nucleaire geneeskunde (radio-isotopisch onderzoek) | | added v2.3
OT | Other | Anders | | added v2.3
PT | Positron emission tomography (PET) | Positron Emissie Tomografie (PET) | | added v2.3
RF | Radio fluoroscopy | Radiofluoroscopie | | added v2.3
ST | Single photon emission computed tomography (SPECT) | Single Photon Emission Tomography Computed Tomography (SPECT) | | added v2.3
TG | Thermography | Thermografie | | added v2.3
US | Ultrasound | Ultrasound | | added v2.3
XA | X-ray Angiography | Röntgen angiografie | | added v2.3

4.2.13.260 HL7 Version 2 Table 0260

URL: https://hl7.org/fhir/STU3/v2/0260/index.html

This page is part of the FHIR Specification (v3.0.2: STU 3). The current version which supercedes this version is 4.0.1. For a full list of available versions, see the Directory of published versions

Vocabulary Work Group | Maturity Level: N/A | External | Use Context: Any

This is a table defined as part of HL7 v2 . Related FHIR content: v2 Patient Location Type.

Summary

Name: | v2 Patient Location Type
Definition: | FHIR Value set/code system definition for HL7 v2 table 0260 (Patient Location Type)
Code System URL: | http://hl7.org/fhir/v2/0260
Value Set URL: | http://hl7.org/fhir/ValueSet/v2-0260
OID: | ??
CodeSystem Resource | XML / JSON
ValueSet Resource | XML / JSON

This value set is used in the following places:

* This value set is the designated 'entire code system' value set for v2 Patient Location Type

4.2.13.260.1 Code System Content

Patient Location Type

Code | Description | Nederlands (Dutch) | Comment | Version
B | Bed | Bed | | added v2.3
C | Clinic | Kliniek | | added v2.3
D | Department | Afdeling | | added v2.3
E | Exam Room | Onderzoeksruimte | | added v2.3
L | Other Location | Andere locatie | | added v2.3
N | Nursing Unit | Verpleegafdeling | | added v2.3
O | Operating Room | Operatiekamer | | added v2.3
R | Room | Kamer | | added v2.3

4.2.13.261 HL7 Version 2 Table 0261

URL: https://hl7.org/fhir/STU3/v2/0261/index.html

This page is part of the FHIR Specification (v3.0.2: STU 3). The current version which supercedes this version is 4.0.1. For a full list of available versions, see the Directory of published versions

Vocabulary Work Group | Maturity Level: N/A | External | Use Context: Any

This is a table defined as part of HL7 v2 . Related FHIR content: v2 Location Equipment.

Summary

Name: | v2 Location Equipment
Definition: | FHIR Value set/code system definition for HL7 v2 table 0261 (Location Equipment)
Code System URL: | http://hl7.org/fhir/v2/0261
Value Set URL: | http://hl7.org/fhir/ValueSet/v2-0261
OID: | ??
CodeSystem Resource | XML / JSON
ValueSet Resource | XML / JSON

This value set is used in the following places:

* This value set is the designated 'entire code system' value set for v2 Location Equipment

4.2.13.261.1 Code System Content

Location Equipment

Code | Description | Nederlands (Dutch) | Comment | Version
EEG | Electro-Encephalogram | Electroencefalogram | | added v2.3
EKG | Electro-Cardiogram | Electrocardiogram | | added v2.3
INF | Infusion pump | Infusiepomp | | added v2.3
IVP | IV pump | Infuuspomp | | added v2.3
OXY | Oxygen | Zuurstof | | added v2.3
SUC | Suction | Suctie | | added v2.3
VEN | Ventilator | Ventilator | | added v2.3
VIT | Vital signs monitor | Vitale functies monitor | | added v2.3

4.2.13.262 HL7 Version 2 Table 0262

URL: https://hl7.org/fhir/STU3/v2/0262/index.html

This page is part of the FHIR Specification (v3.0.2: STU 3). The current version which supercedes this version is 4.0.1. For a full list of available versions, see the Directory of published versions

Vocabulary Work Group | Maturity Level: N/A | External | Use Context: Any

This is a table defined as part of HL7 v2 . Related FHIR content: v2 Privacy Level.

Summary

Name: | v2 Privacy Level
Definition: | FHIR Value set/code system definition for HL7 v2 table 0262 (Privacy Level)
Code System URL: | http://hl7.org/fhir/v2/0262
Value Set URL: | http://hl7.org/fhir/ValueSet/v2-0262
OID: | ??
CodeSystem Resource | XML / JSON
ValueSet Resource | XML / JSON

This value set is used in the following places:

* This value set is the designated 'entire code system' value set for v2 Privacy Level

4.2.13.262.1 Code System Content

Privacy Level

Code | Description | Nederlands (Dutch) | Comment | Version
F | Isolation | Isolatie | | added v2.3
J | Private room - medically justified | Eigen kamer - medisch onderbouwd | | added v2.3
P | Private room | Eigen kamer | | added v2.3
Q | Private room - due to overflow | Eigen kamer - wegens drukte | | added v2.3
S | Semi-private room | Semi-eigen kamer | | added v2.3
W | Ward | Afdeling | | added v2.3

4.2.13.263 HL7 Version 2 Table 0263

URL: https://hl7.org/fhir/STU3/v2/0263/index.html

This page is part of the FHIR Specification (v3.0.2: STU 3). The current version which supercedes this version is 4.0.1. For a full list of available versions, see the Directory of published versions

Vocabulary Work Group | Maturity Level: N/A | External | Use Context: Any

This is a table defined as part of HL7 v2 . Related FHIR content: v2 Level of Care.

Summary

Name: | v2 Level of Care
Definition: | FHIR Value set/code system definition for HL7 v2 table 0263 (Level of Care)
Code System URL: | http://hl7.org/fhir/v2/0263
Value Set URL: | http://hl7.org/fhir/ValueSet/v2-0263
OID: | ??
CodeSystem Resource | XML / JSON
ValueSet Resource | XML / JSON

This value set is used in the following places:

* This value set is the designated 'entire code system' value set for v2 Level of Care

4.2.13.263.1 Code System Content

Level of Care

Code | Description | Nederlands (Dutch) | Comment | Version

A | Ambulatory | Dagbehandeling | | added v2.3
C | Critical care | Kritieke zorg | | added v2.3
E | Emergency | Spoed | | added v2.3
F | Isolation | Isolatie | | added v2.3
N | Intensive care | Intensive care | | added v2.3
R | Routine | Routine | | added v2.3
S | Surgery | Chirurgie | | added v2.3

4.2.13.265 HL7 Version 2 Table 0265

URL: https://hl7.org/fhir/STU3/v2/0265/index.html

This page is part of the FHIR Specification (v3.0.2: STU 3). The current version which supercedes this version is 4.0.1. For a full list of available versions, see the Directory of published versions

Vocabulary Work Group | Maturity Level: N/A | External | Use Context: Any

This is a table defined as part of HL7 v2 . Related FHIR content: v2 Specialty Type.

Summary

Name: | v2 Specialty Type
Definition: | FHIR Value set/code system definition for HL7 v2 table 0265 (Specialty Type)
Code System URL: | http://hl7.org/fhir/v2/0265
Value Set URL: | http://hl7.org/fhir/ValueSet/v2-0265
OID: | ??
CodeSystem Resource | XML / JSON
ValueSet Resource | XML / JSON

This value set is used in the following places:

* This value set is the designated 'entire code system' value set for v2 Specialty Type

4.2.13.265.1 Code System Content

Specialty Type

Code | Description | Nederlands (Dutch) | Comment | Version
ALC | Allergy | Allergie | | added v2.3
AMB | Ambulatory | Dagbehandeling | | added v2.3
CAN | Cancer | Kanker | | added v2.3
CAR | Coronary/cardiac care | Cornaire/hartzorg | | added v2.3
CCR | Critical care | Kritieke zorg | | added v2.3
CHI | Chiropractic | Chiropractisch | | added v2.3
EDI | Education | Onderwijs | | added v2.3
EMR | Emergency | Spoed | | added v2.3
FPC | Family planning | Gezinsplanning | | added v2.3
INT | Intensive care | Intensieve care | | added v2.3
ISO | Isolation | Isolatie | | added v2.3
NAT | Naturopathic | Natuurgeneeskundig | | added v2.3
NBI | Newborn, nursery, infants | Nieuwgeborene, kinderkamer, zuigelingen | | added v2.3
OBG | Obstetrics, gynecology | Obstetrie, gynaecologie | | added v2.3
OBS | Observation | Observaties | | added v2.3
OTH | Other specialty | Ander specialisme | | added v2.3
PED | Pediatrics | Pediatrie | | added v2.3
PHY | General/family practice | Algemeen/gezinspraktijk | | added v2.3
PIN | Pediatric/neonatal intensive care | Pediatrie/neonatale intensive care | | added v2.3
PPS | Pediatric psychiatric | Psychiatrische pediatrie | | added v2.3
PRE | Pediatric rehabilitation | Pediatrische revalidatie | | added v2.3
PSI | Psychiatric intensive care | Psychiatrische intensive care | | added v2.3
PSY | Psychiatric | Psychiatrisch | | added v2.3
REH | Rehabilitation | Revalidatie | | added v2.3
SUR | Surgery | Chirurgie | | added v2.3
WIC | Walk-in clinic | Inloopkliniek | | added v2.3

4.2.13.267 HL7 Version 2 Table 0267

URL: https://hl7.org/fhir/STU3/v2/0267/index.html

This page is part of the FHIR Specification (v3.0.2: STU 3). The current version which supercedes this version is 4.0.1. For a full list of available versions, see the Directory of published versions

Vocabulary Work Group | Maturity Level: N/A | External | Use Context: Any

This is a table defined as part of HL7 v2 . Related FHIR content: v2 Days of the Week.

Summary

Name: | v2 Days of the Week
Definition: | FHIR Value set/code system definition for HL7 v2 table 0267 (Days of the Week)
Code System URL: | http://hl7.org/fhir/v2/0267

Value Set URL: | http://hl7.org/fhir/ValueSet/v2-0267
OID: | ??
CodeSystem Resource | XML / JSON
ValueSet Resource | XML / JSON

This value set is used in the following places:

* This value set is the designated 'entire code system' value set for v2 Days of the Week

4.2.13.267.1 Code System Content

Days of the Week

Code | Description | Nederlands (Dutch) | Comment | Version
FRI | Friday | Vrijdag | | added v2.3
MON | Monday | Maandag | | added v2.3
SAT | Saturday | Zaterdag | | added v2.3
SUN | Sunday | Zondag | | added v2.3
THU | Thursday | Donderdag | | added v2.3
TUE | Tuesday | Dinsdag | | added v2.3
WED | Wednesday | Woensdag | | added v2.3

4.2.13.268 HL7 Version 2 Table 0268

URL: https://hl7.org/fhir/STU3/v2/0268/index.html

This page is part of the FHIR Specification (v3.0.2: STU 3). The current version which supercedes this version is 4.0.1. For a full list of available versions, see the Directory of published versions

Vocabulary Work Group | Maturity Level: N/A | External | Use Context: Any

This is a table defined as part of HL7 v2 . Related FHIR content: v2 Override.

Summary

Name: | v2 Override
Definition: | FHIR Value set/code system definition for HL7 v2 table 0268 (Override)
Code System URL: | http://hl7.org/fhir/v2/0268
Value Set URL: | http://hl7.org/fhir/ValueSet/v2-0268
OID: | ??
CodeSystem Resource | XML / JSON
ValueSet Resource | XML / JSON

This value set is used in the following places:

* This value set is the designated 'entire code system' value set for v2 Override

4.2.13.268.1 Code System Content

Override

Code | Description | Nederlands (Dutch) | Comment | Version
A | Override allowed | Override toegestaan | | added v2.3
R | Override required | Override vereist | | added v2.3
X | Override not allowed | Override niet toegestaan | | added v2.3

4.2.13.269 HL7 Version 2 Table 0269

URL: https://hl7.org/fhir/STU3/v2/0269/index.html

This page is part of the FHIR Specification (v3.0.2: STU 3). The current version which supercedes this version is 4.0.1. For a full list of available versions, see the Directory of published versions

Vocabulary Work Group | Maturity Level: N/A | External | Use Context: Any

This is a table defined as part of HL7 v2 . Related FHIR content: v2 Charge On Indicator.

Summary

Name: | v2 Charge On Indicator
Definition: | FHIR Value set/code system definition for HL7 v2 table 0269 (Charge On Indicator)
Code System URL: | http://hl7.org/fhir/v2/0269
Value Set URL: | http://hl7.org/fhir/ValueSet/v2-0269
OID: | ??
CodeSystem Resource | XML / JSON
ValueSet Resource | XML / JSON

This value set is used in the following places:

* This value set is the designated 'entire code system' value set for v2 Charge On Indicator

4.2.13.269.1 Code System Content

Charge On Indicator

Code | Description | Nederlands (Dutch) | Comment | Version
O | Charge on Order | Facturatie bij aanvraag | | added v2.3
R | Charge on Result | Facturatie bij resultaat | | added v2.3

4.2.13.270 HL7 Version 2 Table 0270

URL: https://hl7.org/fhir/STU3/v2/0270/index.html

This page is part of the FHIR Specification (v3.0.2: STU 3). The current version which supercedes this version is 4.0.1. For a full list of available versions, see the Directory of published versions

Vocabulary Work Group | Maturity Level: N/A | External | Use Context: Any

This is a table defined as part of HL7 v2 . Related FHIR content: v2 Document Type.

Summary

Name: | v2 Document Type
Definition: | FHIR Value set/code system definition for HL7 v2 table 0270 (Document Type)
Code System URL: | http://hl7.org/fhir/v2/0270
Value Set URL: | http://hl7.org/fhir/ValueSet/v2-0270
OID: | ??
CodeSystem Resource | XML / JSON
ValueSet Resource | XML / JSON

This value set is used in the following places:

* This value set is the designated 'entire code system' value set for v2 Document Type

4.2.13.270.1 Code System Content

Document Type

Code | Description | Nederlands (Dutch) | Comment | Version
AR | Autopsy report | Autopsierapport | | added v2.3
CD | Cardiodiagnostics | Cardiodiagnostiek | | added v2.3
CN | Consultation | Consultatie | | added v2.3
DI | Diagnostic imaging | Diagnostische beeldvorming | | added v2.3
DS | Discharge summary | Ontslagsamenvatting | | added v2.3
ED | Emergency department report | Spoedafdeling rapport | | added v2.3
HP | History and physical examination | Historie en lichamelijk onderzoek | | added v2.3
OP | Operative report | Operatieverslag | | added v2.3
PC | Psychiatric consultation | Psychiatrisch consult | | added v2.3
PH | Psychiatric history and physical examination | Psychiatrische historie en lichamelijk onderzoek | | added v2.3
PN | Procedure note | Behandelnotitie | | added v2.3
PR | Progress note | Voortgangsnotitie | | added v2.3
SP | Surgical pathology | Chirurgische pathologie | | added v2.3
TS | Transfer summary | Overplaatsing samenvatting | | added v2.3

4.2.13.271 HL7 Version 2 Table 0271

URL: https://hl7.org/fhir/STU3/v2/0271/index.html

This page is part of the FHIR Specification (v3.0.2: STU 3). The current version which supercedes this version is 4.0.1. For a full list of available versions, see the Directory of published versions

Vocabulary Work Group | Maturity Level: N/A | External | Use Context: Any

This is a table defined as part of HL7 v2 . Related FHIR content: v2 Document Completion Status.

Summary

Name: | v2 Document Completion Status
Definition: | FHIR Value set/code system definition for HL7 v2 table 0271 (Document Completion Status)
Code System URL: | http://hl7.org/fhir/v2/0271
Value Set URL: | http://hl7.org/fhir/ValueSet/v2-0271
OID: | ??
CodeSystem Resource | XML / JSON
ValueSet Resource | XML / JSON

This value set is used in the following places:

* This value set is the designated 'entire code system' value set for v2 Document Completion Status

4.2.13.271.1 Code System Content

Document Completion Status

Code | Description | Deutsch (German) | Nederlands (Dutch) | Comment | Version
AU | Authenticated | Freigegeben | Geauthenticeerd | | added v2.3
DI | Dictated | Diktiert | Gedicteerd | | added v2.3
DO | Documented | Dokumentiert | Gedocumenteerd | | added v2.3
IN | Incomplete | Unvollständig | Incompleet | | added v2.3

IP | In Progress | In Bearbeitung | Wordt aan gewerkt | | added v2.3
LA | Legally authenticated | unterschrieben | Wettelijk geauthenticeerd | | added v2.3
PA | Pre-authenticated | Vorabfreigabe | Pre-authenticatie | | added v2.3

4.2.13.272 HL7 Version 2 Table 0272

URL: https://hl7.org/fhir/STU3/v2/0272/index.html

This page is part of the FHIR Specification (v3.0.2: STU 3). The current version which supercedes this version is 4.0.1. For a full list of available versions, see the Directory of published versions

Vocabulary Work Group | Maturity Level: N/A | External | Use Context: Any

This is a table defined as part of HL7 v2 . Related FHIR content: v2 Document Confidentiality Status.

Summary

Name: | v2 Document Confidentiality Status
Definition: | FHIR Value set/code system definition for HL7 v2 table 0272 (Document Confidentiality Status)
Code System URL: | http://hl7.org/fhir/v2/0272
Value Set URL: | http://hl7.org/fhir/ValueSet/v2-0272
OID: | ??
CodeSystem Resource | XML / JSON
ValueSet Resource | XML / JSON

This value set is used in the following places:

* This value set is the designated 'entire code system' value set for v2 Document Confidentiality Status

4.2.13.272.1 Code System Content

Document Confidentiality Status

Code | Description | Nederlands (Dutch) | Comment | Version
1 | ASTM Level 1 | ASTM Level 1 | deprecated | added v2.3, removed after v2.3
2 | ASTM Level 2 | ASTM Level 2 | deprecated | added v2.3, removed after v2.3
3 | ASTM Level 3 | ASTM Level 3 | deprecated | added v2.3, removed after v2.3
R | Restricted | Beperkte toegang | | added v2.3.1
RE | Restricted | Beperkte toegang | deprecated | added v2.3, removed after v2.3
U | Usual control | Normale toegang | | added v2.3.1
UC | Usual control | Normale toegang | deprecated | added v2.3, removed after v2.3
V | Very restricted | Zeer beperkte toegang | | added v2.3.1
VR | Very restricted | Zeer beperkte toegang | deprecated | added v2.3, removed after v2.3

4.2.13.273 HL7 Version 2 Table 0273

URL: https://hl7.org/fhir/STU3/v2/0273/index.html

This page is part of the FHIR Specification (v3.0.2: STU 3). The current version which supercedes this version is 4.0.1. For a full list of available versions, see the Directory of published versions

Vocabulary Work Group | Maturity Level: N/A | External | Use Context: Any

This is a table defined as part of HL7 v2 . Related FHIR content: v2 Document Availability Status.

Summary

Name: | v2 Document Availability Status
Definition: | FHIR Value set/code system definition for HL7 v2 table 0273 (Document Availability Status)
Code System URL: | http://hl7.org/fhir/v2/0273
Value Set URL: | http://hl7.org/fhir/ValueSet/v2-0273
OID: | ??
CodeSystem Resource | XML / JSON
ValueSet Resource | XML / JSON

This value set is used in the following places:

* This value set is the designated 'entire code system' value set for v2 Document Availability Status

4.2.13.273.1 Code System Content

Document Availability Status

Code | Description | Deutsch (German) | Nederlands (Dutch) | Comment | Version
AV | Available for patient care | Verfügbar (Kann zur Behandlung herangezogen werden.) | Beschikbaar voor patiëntzorg | | added v2.3
CA | Deleted | Gelöscht | Verwijderd | | added v2.3.1
OB | Obsolete | Nicht mehr relevant | Obsoleet | | added v2.3.1
UN | Unavailable for patient care | Nicht verfügbar (Kann nicht zur Behandlung verwendet werden.) | Niet beschikbaar voor patiëntzorg | | added v2.3

4.2.13.275 HL7 Version 2 Table 0275

URL: https://hl7.org/fhir/STU3/v2/0275/index.html

This page is part of the FHIR Specification (v3.0.2: STU 3). The current version which supercedes this version is 4.0.1. For a full list of available versions, see the Directory of published versions

Vocabulary Work Group | Maturity Level: N/A | External | Use Context: Any

This is a table defined as part of HL7 v2 . Related FHIR content: v2 Document Storage Status.

Summary

Name: | v2 Document Storage Status
Definition: | FHIR Value set/code system definition for HL7 v2 table 0275 (Document Storage Status)
Code System URL: | http://hl7.org/fhir/v2/0275
Value Set URL: | http://hl7.org/fhir/ValueSet/v2-0275
OID: | ??
CodeSystem Resource | XML / JSON
ValueSet Resource | XML / JSON

This value set is used in the following places:

* This value set is the designated 'entire code system' value set for v2 Document Storage Status

4.2.13.275.1 Code System Content

Document Storage Status

Code | Description | Deutsch (German) | Nederlands (Dutch) | Comment | Version
AA | Active and archived | Aktiv und archiviert | Actief en gearchiveerd | | added v2.3
AC | Active | Aktiv | Actief | | added v2.3
AR | Archived (not active) | Archiviert (inaktiv) | Gearchiveerd (niet actief) | | added v2.3
PU | Purged | Bereinigt (gelöscht) | Verwijderd | | added v2.3

4.2.13.276 HL7 Version 2 Table 0276

URL: https://hl7.org/fhir/STU3/v2/0276/index.html

This page is part of the FHIR Specification (v3.0.2: STU 3). The current version which supercedes this version is 4.0.1. For a full list of available versions, see the Directory of published versions

Vocabulary Work Group | Maturity Level: N/A | External | Use Context: Any

This is a table defined as part of HL7 v2 . Related FHIR content: v2 Appointment reason codes.

Summary

Name: | v2 Appointment reason codes
Definition: | FHIR Value set/code system definition for HL7 v2 table 0276 (Appointment reason codes)
Code System URL: | http://hl7.org/fhir/v2/0276
Value Set URL: | http://hl7.org/fhir/ValueSet/v2-0276
OID: | ??
CodeSystem Resource | XML / JSON
ValueSet Resource | XML / JSON

This value set is used in the following places:

* This value set is the designated 'entire code system' value set for v2 Appointment reason codes
* Appointment.appointmentType (Preferred)
* Slot.appointmentType (Preferred)

4.2.13.276.1 Code System Content

Appointment reason codes

Code | Description | Nederlands (Dutch) | Comment | Version
CHECKUP | A routine check-up, such as an annual physical | Routinecontrole, zoals jaarlijks lichamelijk onderzoek | | added v2.3
EMERGENCY | Emergency appointment | Spoedafspraak | | added v2.3
FOLLOWUP | A follow up visit from a previous appointment | Een vervolgbezoek na een vorige afspraak | | added v2.3
ROUTINE | Routine appointment - default if not valued | Routine afspraak - standaardwaarde bij geen waarde | | added v2.3
WALKIN | A previously unscheduled walk-in visit | Een niet eerder gepland inloopbezoek | | added v2.3

4.2.13.277 HL7 Version 2 Table 0277

URL: https://hl7.org/fhir/STU3/v2/0277/index.html

This page is part of the FHIR Specification (v3.0.2: STU 3). The current version which supercedes this version is 4.0.1. For a full list of available versions, see the Directory of published versions

Vocabulary Work Group | Maturity Level: N/A | External | Use Context: Any

This is a table defined as part of HL7 v2 . Related FHIR content: v2 Appointment Type Codes.

Summary

Name: | v2 Appointment Type Codes
Definition: | FHIR Value set/code system definition for HL7 v2 table 0277 (Appointment Type Codes)
Code System URL: | http://hl7.org/fhir/v2/0277

Value Set URL: | http://hl7.org/fhir/ValueSet/v2-0277
OID: | ??
CodeSystem Resource | XML / JSON
ValueSet Resource | XML / JSON

This value set is used in the following places:

* This value set is the designated 'entire code system' value set for v2 Appointment Type Codes

4.2.13.277.1 Code System Content

Appointment Type Codes

Code | Description | Nederlands (Dutch) | Comment | Version
Complete | A request to add a completed appointment, used to maintain records of completed appointments that did not appear in the schedule (e.g. STAT, walk-in, etc.) | Een verzoek voor toevoegen voltooide afspraak, gebruikt voor bijhouden naslag van voltooide afspraken die niet in de agenda verschenen (bijv. STAT, inloop, etc.) | | added v2.3
Normal | Routine schedule request type – default if not valued | Routine agendaverzoek type - standaardwaarde als geen waarde | | added v2.3
Tentative | A request for a tentative (e.g. “penciled in”) appointment | Een verzoek voor een voorlopige afspraak (bijv. "met potlood toegevoegd") | | added v2.3

4.2.13.278 HL7 Version 2 Table 0278

URL: https://hl7.org/fhir/STU3/v2/0278/index.html

This page is part of the FHIR Specification (v3.0.2: STU 3). The current version which supercedes this version is 4.0.1. For a full list of available versions, see the Directory of published versions

Vocabulary Work Group | Maturity Level: N/A | External | Use Context: Any

This is a table defined as part of HL7 v2 . Related FHIR content: v2 Filler status codes.

Summary

Name: | v2 Filler status codes
Definition: | FHIR Value set/code system definition for HL7 v2 table 0278 (Filler status codes)
Code System URL: | http://hl7.org/fhir/v2/0278
Value Set URL: | http://hl7.org/fhir/ValueSet/v2-0278
OID: | ??
CodeSystem Resource | XML / JSON
ValueSet Resource | XML / JSON

This value set is used in the following places:

* This value set is the designated 'entire code system' value set for v2 Filler status codes

4.2.13.278.1 Code System Content

Filler status codes

Code | Description | Nederlands (Dutch) | Comment | Version
Blocked | The indicated time slot(s) is(are) blocked | De aangegeven afspraakpositie(s) zijn geblokkeerd | Not used in the AIS, AIG, AIL, AIP segments. | added v2.3
Booked | The indicated appointment is booked | De aangegeven afspraak is geboekt | | added v2.3
Cancelled | The indicated appointment was stopped from occurring (canceled prior to starting) | De aangegeven afspraak is gestopt voordat deze actief werd (geannuleerd vóór starten) | | added v2.3
Complete | The indicated appointment has completed normally (was not discontinued, canceled, or deleted) | De aangegeven afspraak is normaal voltooid (niet afgebroken, geannuleerd of verwijderd) | | added v2.3
Dc | The indicated appointment was discontinued (DC’ed while in progress, discontinued parent appointment, or discontinued child appointment) | De aangegeven afspraak is afgebroken (afgebroken terwijl deze gaande was, afgebroken bovenliggende afspraak, of afgebroken onderliggende afspraak) | | added v2.3
Deleted | The indicated appointment was deleted from the filler application | De aangegeven afspraak is verwijderd van de filler applicatie | | added v2.3
Noshow | The patient did not show up for the appointment | De patiënt is niet verschenen bij de afspraak | | added v2.5
Overbook | The appointment has been confirmed; however it is confirmed in an overbooked state | De aangegeven afspraak is bevestigd; het is echter tevens in overboekte status | | added v2.3
Pending | Appointment has not yet been confirmed | Afspraak is nog niet bevestigd | | added v2.3
Started | The indicated appointment has begun and is currently in progress | De aangegeven afspraak is begonnen en is momenteel bezig | | added v2.3
Waitlist | Appointment has been placed on a waiting list for a particular slot, or set of slots | De afspraak is op een wachtlijst gezet voor een bepaald afspraakposities, of set van afspraakposities | | added v2.3

4.2.13.279 HL7 Version 2 Table 0279

URL: https://hl7.org/fhir/STU3/v2/0279/index.html

This page is part of the FHIR Specification (v3.0.2: STU 3). The current version which supercedes this version is 4.0.1. For a full list of available versions, see the Directory of published versions

Vocabulary Work Group | Maturity Level: N/A | External | Use Context: Any

This is a table defined as part of HL7 v2 . Related FHIR content: v2 Allow Substitution Codes.

Summary

Name: | v2 Allow Substitution Codes
Definition: | FHIR Value set/code system definition for HL7 v2 table 0279 (Allow Substitution Codes)
Code System URL: | http://hl7.org/fhir/v2/0279
Value Set URL: | http://hl7.org/fhir/ValueSet/v2-0279
OID: | ??
CodeSystem Resource | XML / JSON
ValueSet Resource | XML / JSON

This value set is used in the following places:

* This value set is the designated 'entire code system' value set for v2 Allow Substitution Codes

4.2.13.279.1 Code System Content

Allow Substitution Codes

Code | Description | Nederlands (Dutch) | Comment | Version
Confirm | Contact the Placer Contact Person prior to making any substitutions of this resource | Neem contact op met placer contactpersoon voorafgaand aan eventuele substituties van deze resource | | added v2.3
No | Substitution of this resource is not allowed | Substitutie van deze resource is niet toegestaan | | added v2.3
Notify | Notify the Placer Contact Person, through normal institutional procedures, that a substitution of this resource has been made | Melden bij placer contactpersoon via normale institutionele afspraken indien een substitutie van deze resource heeft plaatsgevonden | | added v2.3
Yes | Substitution of this resource is allowed | Substitutie van deze resource is toegestaan | | added v2.3

4.2.13.280 HL7 Version 2 Table 0280

URL: https://hl7.org/fhir/STU3/v2/0280/index.html

This page is part of the FHIR Specification (v3.0.2: STU 3). The current version which supercedes this version is 4.0.1. For a full list of available versions, see the Directory of published versions

Vocabulary Work Group | Maturity Level: N/A | External | Use Context: Any

This is a table defined as part of HL7 v2 . Related FHIR content: v2 Referral Priority.

Summary

Name: | v2 Referral Priority
Definition: | FHIR Value set/code system definition for HL7 v2 table 0280 (Referral Priority)
Code System URL: | http://hl7.org/fhir/v2/0280
Value Set URL: | http://hl7.org/fhir/ValueSet/v2-0280
OID: | ??
CodeSystem Resource | XML / JSON
ValueSet Resource | XML / JSON

This value set is used in the following places:

* This value set is the designated 'entire code system' value set for v2 Referral Priority

4.2.13.280.1 Code System Content

Referral Priority

Code | Description | Nederlands (Dutch) | Comment | Version
A | ASAP | ZSM | | added v2.3
R | Routine | Routine | | added v2.3
S | STAT | STAT | | added v2.3

4.2.13.281 HL7 Version 2 Table 0281

URL: https://hl7.org/fhir/STU3/v2/0281/index.html

This page is part of the FHIR Specification (v3.0.2: STU 3). The current version which supercedes this version is 4.0.1. For a full list of available versions, see the Directory of published versions

Vocabulary Work Group | Maturity Level: N/A | External | Use Context: Any

This is a table defined as part of HL7 v2 . Related FHIR content: v2 Referral Type.

Summary

Name: | v2 Referral Type
Definition: | FHIR Value set/code system definition for HL7 v2 table 0281 (Referral Type)
Code System URL: | http://hl7.org/fhir/v2/0281
Value Set URL: | http://hl7.org/fhir/ValueSet/v2-0281
OID: | ??
CodeSystem Resource | XML / JSON
ValueSet Resource | XML / JSON

This value set is used in the following places:

* This value set is the designated 'entire code system' value set for v2 Referral Type

4.2.13.281.1 Code System Content

Referral Type

Code | Description | Nederlands (Dutch) | Comment | Version
Hom | Home Care | Thuiszorg | | added v2.3
Lab | Laboratory | Laboratorium | | added v2.3
Med | Medical | Medisch | | added v2.3
Psy | Psychiatric | Psychiatrisch | | added v2.3
Rad | Radiology | Radiologie | | added v2.3
Skn | Skilled Nursing | | | added v2.3

4.2.13.282 HL7 Version 2 Table 0282

URL: https://hl7.org/fhir/STU3/v2/0282/index.html

This page is part of the FHIR Specification (v3.0.2: STU 3). The current version which supercedes this version is 4.0.1. For a full list of available versions, see the Directory of published versions

Vocabulary Work Group | Maturity Level: N/A | External | Use Context: Any

This is a table defined as part of HL7 v2 . Related FHIR content: v2 Referral Disposition.

Summary

Name: | v2 Referral Disposition
Definition: | FHIR Value set/code system definition for HL7 v2 table 0282 (Referral Disposition)
Code System URL: | http://hl7.org/fhir/v2/0282
Value Set URL: | http://hl7.org/fhir/ValueSet/v2-0282
OID: | ??
CodeSystem Resource | XML / JSON
ValueSet Resource | XML / JSON

This value set is used in the following places:

* This value set is the designated 'entire code system' value set for v2 Referral Disposition

4.2.13.282.1 Code System Content

Referral Disposition

Code | Description | Nederlands (Dutch) | Comment | Version
AM | Assume Management | Verondersteld management | | added v2.3
RP | Return Patient After Evaluation | Terugkomst patiënt na onderzoek | | added v2.3
SO | Second Opinion | Second opinion | | added v2.3
WR | Send Written Report | Stuur geschreven verslag | | added v2.3

4.2.13.283 HL7 Version 2 Table 0283

URL: https://hl7.org/fhir/STU3/v2/0283/index.html

This page is part of the FHIR Specification (v3.0.2: STU 3). The current version which supercedes this version is 4.0.1. For a full list of available versions, see the Directory of published versions

Vocabulary Work Group | Maturity Level: N/A | External | Use Context: Any

This is a table defined as part of HL7 v2 . Related FHIR content: v2 Referral Status.

Summary

Name: | v2 Referral Status
Definition: | FHIR Value set/code system definition for HL7 v2 table 0283 (Referral Status)
Code System URL: | http://hl7.org/fhir/v2/0283
Value Set URL: | http://hl7.org/fhir/ValueSet/v2-0283
OID: | ??
CodeSystem Resource | XML / JSON
ValueSet Resource | XML / JSON

This value set is used in the following places:

* This value set is the designated 'entire code system' value set for v2 Referral Status

4.2.13.283.1 Code System Content

Referral Status

Code | Description | Nederlands (Dutch) | Comment | Version
A | Accepted | Geaccepteerd | | added v2.3
E | Expired | Verlopen | | added v2.3
P | Pending | Bezig | | added v2.3
R | Rejected | Geweigerd | | added v2.3

4.2.13.284 HL7 Version 2 Table 0284

URL: https://hl7.org/fhir/STU3/v2/0284/index.html

This page is part of the FHIR Specification (v3.0.2: STU 3). The current version which supercedes this version is 4.0.1. For a full list of available versions, see the Directory of published versions

Vocabulary Work Group | Maturity Level: N/A | External | Use Context: Any

This is a table defined as part of HL7 v2 . Related FHIR content: v2 Referral Category.

Summary

Name: | v2 Referral Category
Definition: | FHIR Value set/code system definition for HL7 v2 table 0284 (Referral Category)
Code System URL: | http://hl7.org/fhir/v2/0284
Value Set URL: | http://hl7.org/fhir/ValueSet/v2-0284
OID: | ??
CodeSystem Resource | XML / JSON
ValueSet Resource | XML / JSON

This value set is used in the following places:

* This value set is the designated 'entire code system' value set for v2 Referral Category

4.2.13.284.1 Code System Content

Referral Category

Code	Description	Nederlands (Dutch)	Comment	Version
A	Ambulatory	Dagbehandeling		added v2.3
E	Emergency	Spoed		added v2.3
I	Inpatient	Klinisch		added v2.3
O	Outpatient	Poliklinisch		added v2.3

4.2.13.286 HL7 Version 2 Table 0286

URL: https://hl7.org/fhir/STU3/v2/0286/index.html

This page is part of the FHIR Specification (v3.0.2: STU 3). The current version which supercedes this version is 4.0.1. For a full list of available versions, see the Directory of published versions

Vocabulary Work Group | Maturity Level: N/A | External | Use Context: Any

This is a table defined as part of HL7 v2 . Related FHIR content: v2 Provider Role.

Summary

Name: | v2 Provider Role
Definition: | FHIR Value set/code system definition for HL7 v2 table 0286 (Provider Role)
Code System URL: | http://hl7.org/fhir/v2/0286
Value Set URL: | http://hl7.org/fhir/ValueSet/v2-0286
OID: | ??
CodeSystem Resource | XML / JSON
ValueSet Resource | XML / JSON

This value set is used in the following places:

* This value set is the designated 'entire code system' value set for v2 Provider Role

4.2.13.286.1 Code System Content

Provider Role

Code	Description	Nederlands (Dutch)	Comment	Version
CP	Consulting Provider	Adviserende zorgverlener		added v2.3
PP	Primary Care Provider	Eerstelijns zorgverlener		added v2.3
RP	Referring Provider	Verwijzende zorgverlener		added v2.3
RT	Referred to Provider	Verwezen naar zorgverlener		added v2.3

4.2.13.287 HL7 Version 2 Table 0287

URL: https://hl7.org/fhir/STU3/v2/0287/index.html

This page is part of the FHIR Specification (v3.0.2: STU 3). The current version which supercedes this version is 4.0.1. For a full list of available versions, see the Directory of published versions

Vocabulary Work Group | Maturity Level: N/A | External | Use Context: Any

This is a table defined as part of HL7 v2 . Related FHIR content: v2 Problem/Goal Action Code.

Summary

Name: | v2 Problem/Goal Action Code
Definition: | FHIR Value set/code system definition for HL7 v2 table 0287 (Problem/Goal Action Code)
Code System URL: | http://hl7.org/fhir/v2/0287
Value Set URL: | http://hl7.org/fhir/ValueSet/v2-0287
OID: | ??

CodeSystem Resource | XML / JSON
ValueSet Resource | XML / JSON

This value set is used in the following places:

* This value set is the designated 'entire code system' value set for v2 Problem/Goal Action Code

4.2.13.287.1 Code System Content

Problem/Goal Action Code

Code | Description | Deutsch (German) | Nederlands (Dutch) | Comment | Version
AD | ADD | hinzufügen | Toevoegen | | added v2.3
CO | CORRECT | ändern | Corrigeren | | added v2.3
DE | DELETE | löschen | Verwijderen | | added v2.3
LI | LINK | verknüpfen | Koppelen | | added v2.3
UC | UNCHANGED | | Ongewijzigd | | added v2.3
UN | UNLINK | Verknüpfung auflösen | Ontkoppelen | | added v2.3
UP | UPDATE | ändern | Updaten | | added v2.3

4.2.13.290 HL7 Version 2 Table 0290

URL: https://hl7.org/fhir/STU3/v2/0290/index.html

This page is part of the FHIR Specification (v3.0.2: STU 3). The current version which supercedes this version is 4.0.1. For a full list of available versions, see the Directory of published versions

Vocabulary Work Group | Maturity Level: N/A | External | Use Context: Any

This is a table defined as part of HL7 v2 . Related FHIR content: v2 MIME base64 encoding characters.

Summary

Name: | v2 MIME base64 encoding characters
Definition: | FHIR Value set/code system definition for HL7 v2 table 0290 (MIME base64 encoding characters)
Code System URL: | http://hl7.org/fhir/v2/0290
Value Set URL: | http://hl7.org/fhir/ValueSet/v2-0290
OID: | ??
CodeSystem Resource | XML / JSON
ValueSet Resource | XML / JSON

This value set is used in the following places:

* This value set is the designated 'entire code system' value set for v2 MIME base64 encoding characters

4.2.13.290.1 Code System Content

MIME base64 encoding characters

Code | Description | Nederlands (Dutch) | Comment | Version
(pad) | = | = | deprecated | added v2.3, removed after v2.4
0 | A | A | deprecated | added v2.3, removed after v2.4
1 | B | B | deprecated | added v2.3, removed after v2.4
10 | K | K | deprecated | added v2.3, removed after v2.4
11 | L | L | deprecated | added v2.3, removed after v2.4
12 | M | M | deprecated | added v2.3, removed after v2.4
13 | N | N | deprecated | added v2.3, removed after v2.4
14 | O | O | deprecated | added v2.3, removed after v2.4
15 | P | P | deprecated | added v2.3, removed after v2.4
16 | Q | Q | deprecated | added v2.3, removed after v2.4
17 | R | R | deprecated | added v2.3, removed after v2.4
18 | S | S | deprecated | added v2.3, removed after v2.4
19 | T | T | deprecated | added v2.3, removed after v2.4
2 | C | C | deprecated | added v2.3, removed after v2.4
20 | U | U | deprecated | added v2.3, removed after v2.4
21 | V | V | deprecated | added v2.3, removed after v2.4
22 | W | W | deprecated | added v2.3, removed after v2.4
23 | X | X | deprecated | added v2.3, removed after v2.4
24 | Y | Y | deprecated | added v2.3, removed after v2.4
25 | Z | Z | deprecated | added v2.3, removed after v2.4
26 | a | a | deprecated | added v2.3, removed after v2.4
27 | b | b | deprecated | added v2.3, removed after v2.4
28 | c | c | deprecated | added v2.3, removed after v2.4
29 | d | d | deprecated | added v2.3, removed after v2.4
3 | D | D | deprecated | added v2.3, removed after v2.4
30 | e | e | deprecated | added v2.3, removed after v2.4
31 | f | f | deprecated | added v2.3, removed after v2.4
32 | g | g | deprecated | added v2.3, removed after v2.4
33 | h | h | deprecated | added v2.3, removed after v2.4
34 | I | I | deprecated | added v2.3, removed after v2.4

35 | j | j | deprecated | added v2.3, removed after v2.4
36 | k | k | deprecated | added v2.3, removed after v2.4
37 | l | l | deprecated | added v2.3, removed after v2.4
38 | m | m | deprecated | added v2.3, removed after v2.4
39 | n | n | deprecated | added v2.3, removed after v2.4
4 | E | E | deprecated | added v2.3, removed after v2.4
40 | o | o | deprecated | added v2.3, removed after v2.4
41 | p | p | deprecated | added v2.3, removed after v2.4
42 | q | q | deprecated | added v2.3, removed after v2.4
43 | r | r | deprecated | added v2.3, removed after v2.4
44 | s | s | deprecated | added v2.3, removed after v2.4
45 | t | t | deprecated | added v2.3, removed after v2.4
46 | u | u | deprecated | added v2.3, removed after v2.4
47 | v | v | deprecated | added v2.3, removed after v2.4
48 | w | w | deprecated | added v2.3, removed after v2.4
49 | x | x | deprecated | added v2.3, removed after v2.4
5 | F | F | deprecated | added v2.3, removed after v2.4
50 | y | y | deprecated | added v2.3, removed after v2.4
51 | z | z | deprecated | added v2.3, removed after v2.4
52 | 0 | 0 | deprecated | added v2.3, removed after v2.4
53 | 1 | 1 | deprecated | added v2.3, removed after v2.4
54 | 2 | 2 | deprecated | added v2.3, removed after v2.4
55 | 3 | 3 | deprecated | added v2.3, removed after v2.4
56 | 4 | 4 | deprecated | added v2.3, removed after v2.4
57 | 5 | 5 | deprecated | added v2.3, removed after v2.4
58 | 6 | 6 | deprecated | added v2.3, removed after v2.4
59 | 7 | 7 | deprecated | added v2.3, removed after v2.4
6 | G | G | deprecated | added v2.3, removed after v2.4
60 | 8 | 8 | deprecated | added v2.3, removed after v2.4
61 | 9 | 9 | deprecated | added v2.3, removed after v2.4
62 | + | + | deprecated | added v2.3, removed after v2.4
63 | / | / | deprecated | added v2.3, removed after v2.4
7 | H | H | deprecated | added v2.3, removed after v2.4
8 | I | I | deprecated | added v2.3, removed after v2.4
9 | J | J | deprecated | added v2.3, removed after v2.4

4.2.13.291 HL7 Version 2 Table 0291

URL: https://hl7.org/fhir/STU3/v2/0291/index.html

This page is part of the FHIR Specification (v3.0.2: STU 3). The current version which supercedes this version is 4.0.1. For a full list of available versions, see the Directory of published versions

Vocabulary Work Group | Maturity Level: N/A | External | Use Context: Any

This is a table defined as part of HL7 v2 . Related FHIR content: v2 Subtype of Referenced Data.

Summary

Name: | v2 Subtype of Referenced Data
Definition: | FHIR Value set/code system definition for HL7 v2 table 0291 (Subtype of Referenced Data)
Code System URL: | http://hl7.org/fhir/v2/0291
Value Set URL: | http://hl7.org/fhir/ValueSet/v2-0291
OID: | ??
CodeSystem Resource | XML / JSON
ValueSet Resource | XML / JSON

This value set is used in the following places:

* This value set is the designated 'entire code system' value set for v2 Subtype of Referenced Data

4.2.13.291.1 Code System Content

Subtype of Referenced Data

Code | Description | Nederlands (Dutch) | Comment | Version
... | Source RFC 2046 | Bron RFC 2046 | | added v2.6
BASIC | ISDN PCM audio data | ISDN PCM audiogegevens | deprecated | added v2.3, removed after v2.5.1
DICOM | Digital Imaging and Communications in Medicine | Digital Imaging and Communications in Medicine | deprecated | added v2.3, removed after v2.5.1
FAX | Facsimile data | Faxgegevens | deprecated | added v2.3, removed after v2.5.1
GIF | Graphics Interchange Format | Graphics Interchange Format | deprecated | added v2.3, removed after v2.5.1
HTML | Hypertext Markup Language | Hypertext Markup Language | deprecated | added v2.3, removed after v2.5.1
JOT | Electronic ink data (Jot 1.0 standard) | Electronische Inktgegevens (Jot 1.0 standaard) | deprecated | added v2.3, removed after v2.5.1
JPEG | Joint Photographic Experts Group | Joint Photographic Expert Group | deprecated | added v2.3, removed after v2.5.1
Octet-stream | Uninterpreted binary data | Ongeïnterpreteerde binaire gegevens | deprecated | added v2.3, removed after v2.5.1
PICT | PICT format image data | PICT formaat beeldgegevens | deprecated | added v2.3, removed after v2.5.1
PostScript | PostScript program | PostScript | deprecated | added v2.3, removed after v2.5.1

RTF | Rich Text Format | Rich Text Format | deprecated | added v2.3, removed after v2.5.1
SGML | Standard Generalized Markup Language (HL7 V2.3.1 and later) | Standard Generalized Markup Language (vanaf HL7 v2.3.1) | deprecated | added v2.3.1, removed after v2.5.1
TIFF | TIFF image data | TIFF afbeeldinggegevens | deprecated | added v2.3, removed after v2.5.1
x-hl7-cda-level-one | HL7 Clinical Document Architecture Level One document | HL7 Clinical Document Architecture Level One document | Retained for backwards compatibility only as of v2.6 and CDA R 2. Preferred value is text/xml. | added v2.4
XML | Extensible Markup Language (HL7 V2.3.1 and later) | Extensible Markup Language (vanaf HL7 v2.3.1) | deprecated | added v2.3.1, removed after v2.5.1
… | Source RFC 2046 | Bron RFC 2046 | deprecated | added v2.7.1, removed after v2.7.1

4.2.13.292 HL7 Version 2 Table 0292

URL: https://hl7.org/fhir/STU3/v2/0292/index.html

This page is part of the FHIR Specification (v3.0.2: STU 3). The current version which supercedes this version is 4.0.1. For a full list of available versions, see the Directory of published versions

Vocabulary Work Group | Maturity Level: N/A | External | Use Context: Any

This is a table defined as part of HL7 v2 . Related FHIR content: v2 Vaccines Administered (code = CVX) (parenteral, un.

Summary

Name: | v2 Vaccines Administered (code = CVX) (parenteral, un
Definition: | FHIR Value set/code system definition for HL7 v2 table 0292 (Vaccines Administered (code = CVX) (parenteral, un)
Code System URL: | http://hl7.org/fhir/v2/0292
Value Set URL: | http://hl7.org/fhir/ValueSet/v2-0292
OID: | ??
CodeSystem Resource | XML / JSON
ValueSet Resource | XML / JSON

This value set is used in the following places:

* This value set is the designated 'entire code system' value set for v2 Vaccines Administered (code = CVX) (parenteral, un

4.2.13.292.1 Code System Content

Vaccines Administered (code = CVX) (parenteral, un

Code | Description | Nederlands (Dutch) | Comment | Version
01 | DTP | DKT - difterie-kinkhoest-tetanus | diphtheria, tetanus toxoids and pertussis vaccine | added v2.3
02 | OPV | OPV | poliovirus vaccine, live, oral | added v2.3
03 | MMR | BMR - bof, mazelen, rodehond | measles, mumps and rubella virus vaccine | added v2.3
04 | M/R | M/R | measles and rubella virus vaccine | added v2.3
05 | measles | mazelen | measles virus vaccine | added v2.3
06 | rubella | rodehond | rubella virus vaccine | added v2.3
07 | mumps | bof | mumps virus vaccine | added v2.3
08 | Hep B, adolescent or pediatric | Hep B, adolescent of pediatrie | hepatitis B vaccine, pediatric or pediatric/adolescent dosage | added v2.3
09 | Td (adult) | DT - difterie en tetanus (volwassene) | tetanus and diphtheria toxoids, adsorbed for adult use | added v2.3
10 | IPV | IPV | poliovirus vaccine, inactivated | added v2.3
100 | pneumococcal conjugate | pneumokokken conjugaat | pneumococcal conjugate vaccine, polyvalent | added v2.4
101 | typhoid, ViCPs | tyfus, ViCPs | typhoid Vi capsular polysaccharide vaccine | added v2.4
102 | DTP-Hib-Hep B | DKT-Hib-Hep B | DTP- Haemophilus influenzae type b conjugate and hepatitis b vaccine | added v2.5
103 | meningococcal C conjugate | meningokokken C conjugaat | meningococcal C conjugate vaccine | added v2.5
104 | Hep A-Hep B | Hep A-Hep B | hepatitis A and hepatitis B vaccine | added v2.5
105 | vaccinia (smallpox) diluted | vaccinia (pokken) verzwakt | vaccinia (smallpox) vaccine, diluted | added v2.5
106 | DTaP, 5 pertussis antigens6 | DaKT, 5 kinkhoest antigenen6 | diphtheria, tetanus toxoids and acellular pertussis vaccine, 5 pertussis antigens | added v2.5
107 | DTaP, NOS | DaKT, niet anders gespecificeerd | diphtheria, tetanus toxoids and acellular pertussis vaccine, NOS | added v2.5
108 | meningococcal, NOS | meningokokken, niet anders gespecificeerd | meningococcal vaccine, NOS | added v2.5
109 | pneumococcal, NOS | pneumokokken, niet anders gespecificeerd | pneumococcal vaccine, NOS | added v2.5
11 | pertussis | kinkhoest | pertussis vaccine | added v2.3
110 | DTaP-Hep B-IPV | DaKT-Hep B-IPV | DTaP-hepatitis B and poliovirus vaccine | added v2.6
111 | influenza, live, intranasal | influenza, levend, intranasaal | influenza virus vaccine, live, attenuated, for intranasal use | added v2.6
112 | tetanus toxoid, NOS | tetanus toxoïde, niet anders gespecificeerd | tetanus toxoid, NOS | added v2.6
113 | Td (adult) | DT - difterie en tetanus (volwassene) | tetanus and diphtheria toxoids, adsorbed, preservative free, for adult use | added v2.6
114 | meningococcal A,C,Y,W-135 diphtheria conjugate | meningokokken A,C,Y,W-135 difterie conjugaat | meningococcal polysaccharide (groups A, C, Y and W-135) diphtheria toxoid conjugate vaccine (MCV4) | added v2.6
115 | Tdap | tetanus toxoïde, verminderde difterie toxoïde, en acellulaire kinkhoest | tetanus toxoid, reduced diphtheria toxoid, and acellular pertussis vaccine, adsorbed | added v2.6
116 | rotavirus, pentavalent | rotavirus, pentavalent | rotavirus, live, pentavalent vaccine | added v2.6
117 | VZIG (IND) | VZIG (IND) | varicella zoster immune globulin (Investigational New Drug) | added v2.6
118 | HPV, bivalent | HPV, bivalent | human papilloma virus vaccine, bivalent | added v2.6
119 | rotavirus, monovalent | rotavirus, monovalent | rotavirus, live, monovalent vaccine | added v2.6
12 | diphtheria antitoxin | difterie antitoxine | diphtheria antitoxin | added v2.3
120 | DTaP-Hib-IPV | DaKT-Hib-IPV | diphtheria, tetanus toxoids and acellular pertussis vaccine, Haemophilus influenzae type b conjugate, and poliovirus vaccine, inactivated (DTaP-Hib-IPV) | added v2.6
121 | zoster | gordelroos | zoster vaccine, live | added v2.6

122 | rotavirus, NOS1 | rotavirus, niet anders gespecificeerd1 | rotavirus vaccine, NOS | added v2.6
13 | TIG | TIG | tetanus immune globulin | added v2.3
14 | IG, NOS | IG, niet anders gespecificeerd | immune globulin, NOS | added v2.3
15 | influenza, split (incl. purified surface antigen) | influenza, gesplitst (incl. gezuiverd oppervlakte antigen) | influenza virus vaccine, split virus (incl. purified surface antigen) | added v2.3
16 | influenza, whole | influenza, geheel | influenza virus vaccine, whole virus | added v2.3
17 | Hib, NOS | Hib, niet anders gespecificeerd | Haemophilus influenzae type b vaccine, conjugate NOS | added v2.3
18 | rabies, intramuscular injection | hondsdolheid, intramusculaire injectie | rabies vaccine, for intramuscular injection | added v2.3
19 | BCG | BCG | Bacillus Calmette-Guerin vaccine | added v2.3
20 | DTaP | DaKT -difterie-acellulaire kinkhoest-tetanus | diphtheria, tetanus toxoids and acellular pertussis vaccine | added v2.3
21 | varicella | varicella | varicella virus vaccine | added v2.3
22 | DTP-Hib | DKT-Hib | DTP-Haemophilus influenzae type b conjugate vaccine | added v2.3
23 | plague | pest | plague vaccine | added v2.3
24 | anthrax | miltvuur | anthrax vaccine | added v2.3
25 | typhoid, oral | tyfus, oral | typhoid vaccine, live, oral | added v2.3
26 | cholera | cholera | cholera vaccine | added v2.3
27 | botulinum antitoxin | botulisme antitoxine | botulinum antitoxin | added v2.3
28 | DT (pediatric) | DT - difterie-tetanus (pediatrie) | diphtheria and tetanus toxoids, adsorbed for pediatric use | added v2.3
29 | CMVIG | CMVIG | cytomegalovirus immune globulin, intravenous | added v2.3
30 | HBIG | HBIG | hepatitis B immune globulin | added v2.3
31 | Hep A, pediatric, NOS | Hep A, pediatrie, niet anders gespecificeerd | hepatitis A vaccine, pediatric dosage, NOS | added v2.3
32 | meningococcal | meningokokken | meningococcal polysaccharide vaccine (MPSV4) | added v2.3
33 | pneumococcal | pneumokokken | pneumococcal polysaccharide vaccine | added v2.3
34 | RIG | hondsdolheid immunoglobuline | rabies immune globulin | added v2.3
35 | tetanus toxoid | tetanus toxoïde | tetanus toxoid, adsorbed | added v2.3
36 | VZIG | VZIG | varicella zoster immune globulin | added v2.3
37 | yellow fever | gele koorts | yellow fever vaccine | added v2.3
38 | rubella/mumps | rodehond/bof | rubella and mumps virus vaccine | added v2.3
39 | Japanese encephalitis | Japanse encefalitis | Japanese encephalitis vaccine | added v2.3
40 | rabies, intradermal injection | hondsdolheid, intradermale injectie | rabies vaccine, for intradermal injection | added v2.3
41 | typhoid, parenteral | tyfus, parenteraal | typhoid vaccine, parenteral, other than acetone-killed, dried | added v2.3
42 | Hep B, adolescent/high risk infant2 | Hep B, adolescent/hoogrisico zuigeling2 | hepatitis B vaccine, adolescent/high risk infant dosage | added v2.3
43 | Hep B, adult4 | Hep B, volwassen4 | hepatitis B vaccine, adult dosage | added v2.3
44 | Hep B, dialysis | Hep B, dialyse | hepatitis B vaccine, dialysis patient dosage | added v2.3
45 | Hep B, NOS | Hep B, niet anders gespecificeerd | hepatitis B vaccine, NOS | added v2.3
46 | Hib (PRP-D) | Hib (PRP-D) | Haemophilus influenzae type b vaccine, PRP-D conjugate | added v2.3
47 | Hib (HbOC) | Hib (HbOC) | Haemophilus influenzae type b vaccine, HbOC conjugate | added v2.3
48 | Hib (PRP-T) | Hib (PRP-T) | Haemophilus influenzae type b vaccine, PRP-T conjugate | added v2.3
49 | Hib (PRP-OMP) | Hib (PRP-OMP) | Haemophilus influenzae type b vaccine, PRP-OMP conjugate | added v2.3
50 | DTaP-Hib | DaKT-Hib | DTaP-Haemophilus influenzae type b conjugate vaccine | added v2.3
51 | Hib-Hep B | Hib-Hep B | Haemophilus influenzae type b conjugate and Hepatitis B vaccine | added v2.3
52 | Hep A, adult | Hep A, volwassene | hepatitis A vaccine, adult dosage | added v2.3
53 | typhoid, parenteral, AKD (U.S. military) | tyfus, parenteraal, AKD (Amerikaanse leger) | typhoid vaccine, parenteral, acetone-killed, dried (U.S. military) | added v2.3.1
54 | adenovirus, type 4 | adenovirus, type 4 | adenovirus vaccine, type 4, live, oral | added v2.3.1
55 | adenovirus, type 7 | adenovirus, type 7 | adenovirus vaccine, type 7, live, oral | added v2.3.1
56 | dengue fever | knokkelkoorts | dengue fever vaccine | added v2.3.1
57 | hantavirus | hantavirus | hantavirus vaccine | added v2.3.1
58 | Hep C | Hep C | hepatitis C vaccine | added v2.3.1
59 | Hep E | Hep E | hepatitis E vaccine | added v2.3.1
60 | herpes simplex 2 | herpes simplex 2 | herpes simplex virus, type 2 vaccine | added v2.3.1
61 | HIV | HIV | human immunodeficiency virus vaccine | added v2.3.1
62 | HPV, quadrivalent | HPV, quadrivalent | human papilloma virus vaccine, quadrivalent | added v2.3.1
63 | Junin virus | Junín virus | Junin virus vaccine | added v2.3.1
64 | leishmaniasis | leishmaniase | leishmaniasis vaccine | added v2.3.1
65 | leprosy | lepra | leprosy vaccine | added v2.3.1
66 | Lyme disease | ziekte van Lyme | Lyme disease vaccine | added v2.3.1
67 | malaria | malaria | malaria vaccine | added v2.3.1
68 | melanoma | melanoom | melanoma vaccine | added v2.3.1
69 | parainfluenza-3 | parainfluenza-3 | parainfluenza-3 virus vaccine | added v2.3.1
70 | Q fever | Q-koorts | Q fever vaccine | added v2.3.1
71 | RSV-IGIV | RSV-IGIV | respiratory syncytial virus immune globulin, intravenous | added v2.3.1
72 | rheumatic fever | reumatische koorts | rheumatic fever vaccine | added v2.3.1
73 | Rift Valley fever | Riftdalkoorts | Rift Valley fever vaccine | added v2.3.1
74 | rotavirus, tetravalent | rotavirus, tetravalent | rotavirus, live, tetravalent vaccine | added v2.3.1
75 | vaccinia (smallpox) | vaccinia (pokken) | vaccinia (smallpox) vaccine | added v2.3.1
76 | Staphylococcus bacterio lysate | Staphylococcus bacterio lysate | Staphylococcus bacteriophage lysate | added v2.3.1
77 | tick-borne encephalitis | frühsommer-meningoenzephalitis vaccin | tick-borne encephalitis vaccine | added v2.3.1
78 | tularemia vaccine | tularemia vaccin | tularemia vaccine | added v2.3.1
79 | vaccinia immune globulin | vaccinia immunoglobuline | vaccinia immune globulin | added v2.3.1
80 | VEE, live | VEE, levend | Venezuelan equine encephalitis, live, attenuated | added v2.3.1

81 | VEE, inactivated | VEE, inactief | Venezuelan equine encephalitis, inactivated | added v2.3.1
82 | adenovirus, NOS1 | adenovirus, niet anders gespecificeerd1 | adenovirus vaccine, NOS | added v2.3.1
83 | Hep A, ped/adol, 2 dose | Hep A, ped/adol, 2 dosis | hepatitis A vaccine, pediatric/adolescent dosage, 2 dose schedule | added v2.3.1
84 | Hep A, ped/adol, 3 dose | Hep A, ped/adol, 3 dosis | hepatitis A vaccine, pediatric/adolescent dosage, 3 dose schedule | added v2.3.1
85 | Hep A, NOS | Hep A, niet anders gespecificeerd | hepatitis A vaccine, NOS | added v2.3.1
86 | IG | IG | immune globulin, intramuscular | added v2.3.1
87 | IGIV | IGIV | immune globulin, intravenous | added v2.3.1
88 | influenza, NOS | influenza, niet anders gespecificeerd | influenza virus vaccine, NOS | added v2.3.1
89 | polio, NOS | polio, niet anders gespecificeerd | poliovirus vaccine, NOS | added v2.3.1
90 | rabies, NOS | hondsdolheid, niet anders gespecificeerd | rabies vaccine, NOS | added v2.3.1
91 | typhoid, NOS | tyfus, niet anders gespecificeerd | typhoid vaccine, NOS | added v2.3.1
92 | VEE, NOS | VEE, niet anders gespecificeerd | Venezuelan equine encephalitis vaccine, NOS | added v2.3.1
93 | RSV-MAb | RSV-MAb | respiratory syncytial virus monoclonal antibody (palivizumab), intramuscular | added v2.4
94 | MMRV | BMRV - bof, mazelen, rodehond en varicella | measles, mumps, rubella, and varicella virus vaccine | added v2.4
95 | TST-OT tine test | TST-OT tine test | tuberculin skin test; old tuberculin, multipuncture device | added v2.4
96 | TST-PPD intradermal | TST-PPD intradermal | tuberculin skin test; purified protein derivative solution, intradermal | added v2.4
97 | TST-PPD tine test | TST-PPD tine test | tuberculin skin test; purified protein derivative, multipuncture device | added v2.4
98 | TST, NOS | TST, niet anders gespecificeerd | tuberculin skin test; NOS | added v2.4
99 | RESERVED - do not use3 | GERESERVEERD - niet gebruiken3 | RESERVED - do not use | added v2.4
998 | no vaccine administered5 | geen vaccin toegediend5 | no vaccine administered | added v2.5
999 | unknown | onbekend | unknown vaccine or immune globulin | added v2.4

4.2.13.294 HL7 Version 2 Table 0294

URL: https://hl7.org/fhir/STU3/v2/0294/index.html

This page is part of the FHIR Specification (v3.0.2: STU 3). The current version which supercedes this version is 4.0.1. For a full list of available versions, see the Directory of published versions

Vocabulary Work Group | Maturity Level: N/A | External | Use Context: Any

This is a table defined as part of HL7 v2 . Related FHIR content: v2 Time Selection Criteria Parameter Class Codes.

Summary

Name: | v2 Time Selection Criteria Parameter Class Codes
Definition: | FHIR Value set/code system definition for HL7 v2 table 0294 (Time Selection Criteria Parameter Class Codes)
Code System URL: | http://hl7.org/fhir/v2/0294
Value Set URL: | http://hl7.org/fhir/ValueSet/v2-0294
OID: | ??
CodeSystem Resource | XML / JSON
ValueSet Resource | XML / JSON

This value set is used in the following places:

* This value set is the designated 'entire code system' value set for v2 Time Selection Criteria Parameter Class Codes

4.2.13.294.1 Code System Content

Time Selection Criteria Parameter Class Codes

Code | Description | Nederlands (Dutch) | Comment | Version
Fri | An indicator that Friday is or is not preferred for the day on which the appointment will occur. | Indicator dat vrijdag wel of niet de voorkeur heeft als de dag waarop de afspraak plaats zal vinden. | In component 2, specify OK or NO.<p>OK = Preferred appointment day NO = Day is not preferred | added v2.3
Mon | An indicator that Monday is or is not preferred for the day on which the appointment will occur. | Indicator dat maandag wel of niet de voorkeur heeft als de dag waarop de afspraak plaats zal vinden. | In component 2, specify OK or NO.<p>OK = Preferred appointment day NO = Day is not preferred | added v2.3
Prefend | An indicator that there is a preferred end time for the appointment request, service or resource. | De geprefereerde eindtijd voor de afspraakverzoek, service, of resource. | In component 2, specify any valid time in the format HHMM, using 24-hour clock notation where HH = hour and MM = minutes | added v2.3
Prefstart | An indicator that there is a preferred start time for the appointment request, service or resource. | De geprefereerde starttijd voor de afspraakverzoek, service, of resource. | In component 2, specify any valid time in the format HHMM, using 24-hour clock notation where HH = hour and MM = minutes | added v2.3
Sat | An indicator that Saturday is or is not preferred for the day on which the appointment will occur. | Indicator dat zaterdag wel of niet de voorkeur heeft als de dag waarop de afspraak plaats zal vinden. | In component 2, specify OK or NO.<p>OK = Preferred appointment day NO = Day is not preferred | added v2.3
Sun | An indicator that Sunday is or is not preferred for the day on which the appointment will occur. | Indicator dat zondag wel of niet de voorkeur heeft als de dag waarop de afspraak plaats zal vinden. | In component 2, specify OK or NO.<p>OK = Preferred appointment day NO = Day is not preferred | added v2.3
Thu | An indicator that Thursday is or is not preferred for the day on which the appointment will occur. | Indicator dat donderdag wel of niet de voorkeur heeft als de dag waarop de afspraak plaats zal vinden. | In component 2, specify OK or NO.<p>OK = Preferred appointment day NO = Day is not preferred | added v2.3
Tue | An indicator that Tuesday is or is not preferred for the day on which the appointment will occur. | Indicator dat dinsdag wel of niet de voorkeur heeft als de dag waarop de afspraak plaats zal vinden. | In component 2, specify OK or NO.<p>OK = Preferred appointment day NO = Day is not preferred | added v2.3
Wed | An indicator that Wednesday is or is not preferred for the day on which the appointment will occur. | Indicator dat woensdag wel of niet de voorkeur heeft als de dag waarop de afspraak plaats zal vinden. | In component 2, specify OK or NO.<p>OK = Preferred appointment day NO = Day is not preferred | added v2.3

4.2.13.298 HL7 Version 2 Table 0298

URL: https://hl7.org/fhir/STU3/v2/0298/index.html

This page is part of the FHIR Specification (v3.0.2: STU 3). The current version which supercedes this version is 4.0.1. For a full list of available versions, see the Directory of published versions

Vocabulary Work Group | Maturity Level: N/A | External | Use Context: Any

This is a table defined as part of HL7 v2 . Related FHIR content: v2 CP Range Type.

Summary

Name: | v2 CP Range Type
Definition: | FHIR Value set/code system definition for HL7 v2 table 0298 (CP Range Type)
Code System URL: | http://hl7.org/fhir/v2/0298
Value Set URL: | http://hl7.org/fhir/ValueSet/v2-0298
OID: | ??
CodeSystem Resource | XML / JSON
ValueSet Resource | XML / JSON

This value set is used in the following places:

* This value set is the designated 'entire code system' value set for v2 CP Range Type

4.2.13.298.1 Code System Content

CP Range Type

Code | Description | Nederlands (Dutch) | Comment | Version
F | Flat-rate. Apply the entire price to this interval, do not pro-rate the price if the full interval has not occurred/been consumed | Vaste prijs. Pas de gehele prijs toe op dit interval, bereken niet naar rato in het geval dat niet het hele interval is opgetreden/is verbruikt | | added v2.3
P | Pro-rate. Apply this price to this interval, pro-rated by whatever portion of the interval has occurred/been consumed | Pro rato. Pas deze prijs toe op dit interval, naar rato van het deel van het interval dat is opgetreden/is verbruikt | | added v2.3

4.2.13.299 HL7 Version 2 Table 0299

URL: https://hl7.org/fhir/STU3/v2/0299/index.html

This page is part of the FHIR Specification (v3.0.2: STU 3). The current version which supercedes this version is 4.0.1. For a full list of available versions, see the Directory of published versions

Vocabulary Work Group | Maturity Level: N/A | External | Use Context: Any

This is a table defined as part of HL7 v2 . Related FHIR content: v2 Encoding.

Summary

Name: | v2 Encoding
Definition: | FHIR Value set/code system definition for HL7 v2 table 0299 (Encoding)
Code System URL: | http://hl7.org/fhir/v2/0299
Value Set URL: | http://hl7.org/fhir/ValueSet/v2-0299
OID: | ??
CodeSystem Resource | XML / JSON
ValueSet Resource | XML / JSON

This value set is used in the following places:

* This value set is the designated 'entire code system' value set for v2 Encoding

4.2.13.299.1 Code System Content

Encoding

Code | Description | Deutsch (German) | Nederlands (Dutch) | Comment | Version
A | No encoding - data are displayable ASCII characters. | keine Kodierung | geen codering - gegevens zijn leesbare ASCII-tekens | | added v2.3
Base64 | Encoding as defined by MIME (Multipurpose Internet Mail Extensions) standard RFC 1521. Four consecutive ASCII characters represent three consecutive octets of binary data. Base64 utilizes a 65-character subset of US-ASCII, consisting of both the upper and | | codering zoals gedefinieerd door MIME (Multipurpose Internet Mail Extensions) standaard RFC 1521. Vier opeenvolgende ASCII-tekens stellen drie, enkelvoudige octetten binaire gegevens voor. Base64 gebruikt een subset van 65-tekens uit US-ASCII, bestaande uit zowel de alfabetische hoofd- als de kleine letters, de cijfers "0" tot en met "9", "+", "/" en "=". | The Request For Comment (RFC) 1521 standard is available at: http://www.ietf.org/rfc/rfc1521.txt | added v2.3
Hex | Hexadecimal encoding - consecutive pairs of hexadecimal digits represent consecutive single octets. | | hexadecimale codering - paarsgewijze hexadecimale getallen stellen sequentiële, enkelvoudige octetten voor | | added v2.3

4.2.13.301 HL7 Version 2 Table 0301

URL: https://hl7.org/fhir/STU3/v2/0301/index.html

This page is part of the FHIR Specification (v3.0.2: STU 3). The current version which supercedes this version is 4.0.1. For a full list of available versions, see the Directory of published versions

Vocabulary Work Group | Maturity Level: N/A | External | Use Context: Any

This is a table defined as part of HL7 v2 . Related FHIR content: v2 Universal ID Type.

Summary

Name: | v2 Universal ID Type
Definition: | FHIR Value set/code system definition for HL7 v2 table 0301 (Universal ID Type)
Code System URL: | http://hl7.org/fhir/v2/0301
Value Set URL: | http://hl7.org/fhir/ValueSet/v2-0301
OID: | ??
CodeSystem Resource | XML / JSON
ValueSet Resource | XML / JSON

This value set is used in the following places:

* This value set is the designated 'entire code system' value set for v2 Universal ID Type

4.2.13.301.1 Code System Content

Universal ID Type

Code | Description | Deutsch (German) | Nederlands (Dutch) | Comment | Version
B | | reserviert für lokale Tabellen | | deprecated | added v2.5.1, removed after v2.5.1
CLIA | Clinical Laboratory Improvement Amendments. Allows for the ability to designate organization identifier as a "CLIA" assigned number (for labs) | | Clinical laboratory Improvement Amendments. Ondersteunt gebruik van organisatie-identificatie als een nummer toegekend door "CLIA" (voor labs). In gebruik bij Amerikaanse ministerie van defensie | | added v2.7
CLIP | Clinical laboratory Improvement Program. Allows for the ability to designate organization identifier as a "CLIP" assigned number (for labs).Â Used by US Department of Defense. | | Clinical laboratory Improvement Program. Ondersteunt gebruik van organisatie-identificatie als een nummer toegekend door "CLIP" (voor labs). In gebruik bij Amerikaanse ministerie van defensie | | added v2.7
DNS | An Internet host name, in accordance with RFC 1035; or an IP address. Either in ASCII or as integers, with periods between components ("dotted" notation). | Internet-Adresse | Een internet hostname, conform RFC 1035; of een IP-adres. In ASCII-tekens of als integers, met punten tussen componenten ("puntnotatie"). | | added v2.3
EUI64 | IEEE 64-bit Extended Unique Identifier is comprised of a 24-bit company identifier and a 40-bit instance identifier. The value shall be formatted as 16 ASCII HEX digits, for example, "AABBCC1122334455". The 24-bit company identifier, formally known as | | IEEE 64-bit Extended Unique Identifier bestaat uit een 24-bit bedrijfsidentificatie en een 40-bit instance-identificatie. De waarde moet 16 ASCII HEX tekens lang zijn, bijvoorbeeld, "AABBCC1122334455". De 24-bit bedrijfsidentificatie, voorheen bekend als Organizationally Unique Identifier (OUI-24), is gegarandeerd wereldwijd uniek. De 40-bit extensies worden toegekend door fabrikanten. Deze identificatie wordt meest gebruikt in apparaatinterfaces (bijv., "MAC" adressen voor IPv4 & IPv6). [Zie http://standards.ieee.org/regauth/oui/tutorials/EUI64.html voor een gedetailleerde uitleg van de structuur.] | OUI-24 values are administered by the IEEE Registration Authority. | added v2.7
GUID | Same as UUID. | GUID | Zelfde als UUID. | Retained for backward compatibility only as of v2.7; use UUID instead | added v2.3
HCD | The CEN Healthcare Coding Scheme Designator | | De CEN Healthcare Coding Scheme Designator | Retained for backward compatibility only as of v2.7; does not identify Assigning Authorities | added v2.3
HL7 | HL7 registration schemes | für HL7 reserviert | HL7 registratieschema's | Retained for backward compatibility only as of v2.7; HL7 assigns ISO OIDs for Assigning Authorities | added v2.3
ISO | An International Standards Organization Object Identifier (OID), in accordance with ISO/IEC 8824. Formatted as decimal digits separated by periods; recommended limit of 64 characters | ISO-ID | Een Internationaal Standaardisatie Orgaan Object IDentificatie (OID), conform ISO/IEC 8824. Structuur is decimale getallen gescheiden door punten; aanbevolen grens is 64 tekens. | | added v2.3
L | These are reserved for locally defined coding schemes. | reserviert für lokale Tabellen | Deze zijn gereserveerd voor lokaal gedefinieerde codesystemen | Retained for backward compatibility only as of v 2.8 | added v2.3
L,M,N | Locally defined coding entity identifier. | reserviert für lokale Tabellen | Deze zijn gereserveerd voor lokaal gedefinieerde codesystemen | Retained for backward compatibility only as of v 2.8 | added v2.3
M | These are reserved for locally defined coding schemes. | reserviert für lokale Tabellen | Deze zijn gereserveerd voor lokaal gedefinieerde codesystemen | Retained for backward compatibility only as of v 2.8 | added v2.3
N | These are reserved for locally defined coding schemes. | reserviert für lokale Tabellen | Deze zijn gereserveerd voor lokaal gedefinieerde codesystemen | Retained for backward compatibility only as of v 2.8 | added v2.3
Random | Usually a base64 encoded string of random bits. | beliebig | Meestal een base64 gecodeerde string met willekeurige bits. | Retained for backward compatibility only as of v2.7; equivalent to a locally defined entity identifier scheme; use L. M, or N instead. | added v2.3
URI | Uniform Resource Identifier | URI | Uniform Resource Identifier | | added v2.5
UUID | The DCE Universal Unique Identifier, in accordance with RFC 4122. Recommended format is 32 hexadecimal digits separated by hyphens, in the digit grouping 8-4-4-4-12 | UUID | De DCE Universal Unique Identifier, conform RFC 4122. Aanbevolen structuur is 32 hexadecimale getalen gescheiden door koppeltekens, met cijfergroepering 8-4-4-4-12 | | added v2.3
x400 | An X.400 MHS identifier. Recommended format is in accordance with RFC 1649 | X.400 | Een X.400 MHS identificatie. Aanbevolen format is conform RFC 1649 | | added v2.3
x500 | An X.500 directory name | X.500 Verzeichnisname | Een X.500 directory-naam | | added v2.3

4.2.13.305 HL7 Version 2 Table 0305

URL: https://hl7.org/fhir/STU3/v2/0305/index.html

This page is part of the FHIR Specification (v3.0.2: STU 3). The current version which supercedes this version is 4.0.1. For a full list of available versions, see the Directory of published versions

Vocabulary Work Group | Maturity Level: N/A | External | Use Context: Any

This is a table defined as part of HL7 v2 . Related FHIR content: v2 Person Location Type.

Summary

Name: | v2 Person Location Type
Definition: | FHIR Value set/code system definition for HL7 v2 table 0305 (Person Location Type)
Code System URL: | http://hl7.org/fhir/v2/0305
Value Set URL: | http://hl7.org/fhir/ValueSet/v2-0305
OID: | ??

CodeSystem Resource | XML / JSON
ValueSet Resource | XML / JSON

This value set is used in the following places:

* This value set is the designated 'entire code system' value set for v2 Person Location Type

4.2.13.305.1 Code System Content

Person Location Type

Code | Description | Deutsch (German) | Nederlands (Dutch) | Comment | Version
C | Clinic | Klinik | Kliniek | | added v2.4
D | Department | Abteilung | Afdeling | | added v2.4
H | Home | zu Hause | Thuis | | added v2.4
N | Nursing Unit | Station | Verpleegafdeling | | added v2.4
O | Provider's Office | Sprechzimmer | Kantoor zorgaanbieder | | added v2.4
P | Phone | Telefon(zelle) | Telefonisch | | added v2.4
S | SNF | | Skilled Nursing Facility | | added v2.4

4.2.13.309 HL7 Version 2 Table 0309

URL: https://hl7.org/fhir/STU3/v2/0309/index.html

This page is part of the FHIR Specification (v3.0.2: STU 3). The current version which supercedes this version is 4.0.1. For a full list of available versions, see the Directory of published versions

Vocabulary Work Group | Maturity Level: N/A | External | Use Context: Any

This is a table defined as part of HL7 v2 . Related FHIR content: v2 Coverage Type.

Summary

Name: | v2 Coverage Type
Definition: | FHIR Value set/code system definition for HL7 v2 table 0309 (Coverage Type)
Code System URL: | http://hl7.org/fhir/v2/0309
Value Set URL: | http://hl7.org/fhir/ValueSet/v2-0309
OID: | ??
CodeSystem Resource | XML / JSON
ValueSet Resource | XML / JSON

This value set is used in the following places:

* This value set is the designated 'entire code system' value set for v2 Coverage Type

4.2.13.309.1 Code System Content

Coverage Type

Code | Description | Nederlands (Dutch) | Comment | Version
B | Both hospital and physician | Zowel ziekenhuis als arts | | added v2.3
H | Hospital/institutional | Ziekenhuis/instelling | | added v2.3
P | Physician/professional | Arts/professional | | added v2.3
RX | Pharmacy | Apotheek | | added v2.6

4.2.13.311 HL7 Version 2 Table 0311

URL: https://hl7.org/fhir/STU3/v2/0311/index.html

This page is part of the FHIR Specification (v3.0.2: STU 3). The current version which supercedes this version is 4.0.1. For a full list of available versions, see the Directory of published versions

Vocabulary Work Group | Maturity Level: N/A | External | Use Context: Any

This is a table defined as part of HL7 v2 . Related FHIR content: v2 Job Status.

Summary

Name: | v2 Job Status
Definition: | FHIR Value set/code system definition for HL7 v2 table 0311 (Job Status)
Code System URL: | http://hl7.org/fhir/v2/0311
Value Set URL: | http://hl7.org/fhir/ValueSet/v2-0311
OID: | ??
CodeSystem Resource | XML / JSON
ValueSet Resource | XML / JSON

This value set is used in the following places:

* This value set is the designated 'entire code system' value set for v2 Job Status

4.2.13.311.1 Code System Content

Job Status

Code | Description | Deutsch (German) | Nederlands (Dutch) | Comment | Version

O | Other | anderes Beschäftigungsverhältnis | Anders | | added v2.4
P | Permanent | festangestellt | Permanent | | added v2.4
T | Temporary | befristet angestellt | Tijdelijk | | added v2.4
U | Unknown | unbekannt | Onbekend | | added v2.4

4.2.13.315 HL7 Version 2 Table 0315

URL: https://hl7.org/fhir/STU3/v2/0315/index.html

This page is part of the FHIR Specification (v3.0.2: STU 3). The current version which supercedes this version is 4.0.1. For a full list of available versions, see the Directory of published versions

Vocabulary Work Group | Maturity Level: N/A | External | Use Context: Any

This is a table defined as part of HL7 v2 . Related FHIR content: v2 Living Will Code.

Summary

Name: | v2 Living Will Code
Definition: | FHIR Value set/code system definition for HL7 v2 table 0315 (Living Will Code)
Code System URL: | http://hl7.org/fhir/v2/0315
Value Set URL: | http://hl7.org/fhir/ValueSet/v2-0315
OID: | ??
CodeSystem Resource | XML / JSON
ValueSet Resource | XML / JSON

This value set is used in the following places:

* This value set is the designated 'entire code system' value set for v2 Living Will Code

4.2.13.315.1 Code System Content

Living Will Code

Code | Description | Nederlands (Dutch) | Comment | Version
F | Yes, patient has a living will but it is not on file | Ja, patiënt heeft een testament maar deze zit niet in archief | | added v2.3
I | No, patient does not have a living will but information was provided | Nee, patiënt heeft geen testament maar informatie is gegeven | | added v2.3
N | No, patient does not have a living will and no information was provided | Nee, patiënt heeft geen testament en er is geen informatie gegeven | | added v2.3
U | Unknown | Onbekend | | added v2.3
Y | Yes, patient has a living will | Ja, patiënt heeft een testament | | added v2.3

4.2.13.316 HL7 Version 2 Table 0316

URL: https://hl7.org/fhir/STU3/v2/0316/index.html

This page is part of the FHIR Specification (v3.0.2: STU 3). The current version which supercedes this version is 4.0.1. For a full list of available versions, see the Directory of published versions

Vocabulary Work Group | Maturity Level: N/A | External | Use Context: Any

This is a table defined as part of HL7 v2 . Related FHIR content: v2 Organ Donor Code.

Summary

Name: | v2 Organ Donor Code
Definition: | FHIR Value set/code system definition for HL7 v2 table 0316 (Organ Donor Code)
Code System URL: | http://hl7.org/fhir/v2/0316
Value Set URL: | http://hl7.org/fhir/ValueSet/v2-0316
OID: | ??
CodeSystem Resource | XML / JSON
ValueSet Resource | XML / JSON

This value set is used in the following places:

* This value set is the designated 'entire code system' value set for v2 Organ Donor Code

4.2.13.316.1 Code System Content

Organ Donor Code

Code | Description | Nederlands (Dutch) | Comment | Version
F | Yes, patient is a documented donor, but documentation is not on file | Ja, patiënt is een gedocumenteerde donor maar afschrift is niet beschikbaar | | added v2.3
I | No, patient is not a documented donor, but information was provided | Nee, patiënt is geen gedocumenteerde donor, maar informatie is gegeven | | added v2.3.1
N | No, patient has not agreed to be a donor | Nee, patiënt heeft geen toestemming voor donatie gegeven | | added v2.3
P | Patient leaves organ donation decision to a specific person | Patiënt laat beslissing orgaandonatie over aan specifiek persoon | | added v2.4
R | Patient leaves organ donation decision to relatives | Patiënt laat beslissing orgaandonatie over aan familie | | added v2.4
U | Unknown | Onbekend | | added v2.3
Y | Yes, patient is a documented donor and documentation is on file | Ja, patiënt is een gedocumenteerde donor en afschrift is beschikbaar | | added v2.3

4.2.13.317 HL7 Version 2 Table 0317

URL: https://hl7.org/fhir/STU3/v2/0317/index.html

This page is part of the FHIR Specification (v3.0.2: STU 3). The current version which supercedes this version is 4.0.1. For a full list of available versions, see the Directory of published versions

Vocabulary Work Group | Maturity Level: N/A | External | Use Context: Any

This is a table defined as part of HL7 v2 . Related FHIR content: v2 Annotations.

Summary

Name: | v2 Annotations
Definition: | FHIR Value set/code system definition for HL7 v2 table 0317 (Annotations)
Code System URL: | http://hl7.org/fhir/v2/0317
Value Set URL: | http://hl7.org/fhir/ValueSet/v2-0317
OID: | ??
CodeSystem Resource | XML / JSON
ValueSet Resource | XML / JSON

This value set is used in the following places:

* This value set is the designated 'entire code system' value set for v2 Annotations

4.2.13.317.1 Code System Content

Annotations

Code	Description	Comment	Version
9900	Pace spike		added v2.3
9901	SAS marker		added v2.3
9902	Sense marker		added v2.3
9903	Beat marker		added v2.3
9904	etc.		added v2.3

4.2.13.321 HL7 Version 2 Table 0321

URL: https://hl7.org/fhir/STU3/v2/0321/index.html

This page is part of the FHIR Specification (v3.0.2: STU 3). The current version which supercedes this version is 4.0.1. For a full list of available versions, see the Directory of published versions

Vocabulary Work Group | Maturity Level: N/A | External | Use Context: Any

This is a table defined as part of HL7 v2 . Related FHIR content: v2 Dispense Method.

Summary

Name: | v2 Dispense Method
Definition: | FHIR Value set/code system definition for HL7 v2 table 0321 (Dispense Method)
Code System URL: | http://hl7.org/fhir/v2/0321
Value Set URL: | http://hl7.org/fhir/ValueSet/v2-0321
OID: | ??
CodeSystem Resource | XML / JSON
ValueSet Resource | XML / JSON

This value set is used in the following places:

* This value set is the designated 'entire code system' value set for v2 Dispense Method

4.2.13.321.1 Code System Content

Dispense Method

Code	Description	Nederlands (Dutch)	Comment	Version
AD	Automatic Dispensing	Automatische verstrekking		added v2.3
F	Floor Stock	Afdelingsvoorraad		added v2.3
TR	Traditional	Traditioneel		added v2.3
UD	Unit Dose	Eenheid dosis		added v2.3

4.2.13.322 HL7 Version 2 Table 0322

URL: https://hl7.org/fhir/STU3/v2/0322/index.html

This page is part of the FHIR Specification (v3.0.2: STU 3). The current version which supercedes this version is 4.0.1. For a full list of available versions, see the Directory of published versions

Vocabulary Work Group | Maturity Level: N/A | External | Use Context: Any

This is a table defined as part of HL7 v2 . Related FHIR content: v2 Completion Status.

Summary

Name: | v2 Completion Status
Definition: | FHIR Value set/code system definition for HL7 v2 table 0322 (Completion Status)

Code System URL: | http://hl7.org/fhir/v2/0322
Value Set URL: | http://hl7.org/fhir/ValueSet/v2-0322
OID: | ??
CodeSystem Resource | XML / JSON
ValueSet Resource | XML / JSON

This value set is used in the following places:

* This value set is the designated 'entire code system' value set for v2 Completion Status

4.2.13.322.1 Code System Content

Completion Status

Code | Description | Nederlands (Dutch) | Comment | Version
CP | Complete | Voltooid | | added v2.3
NA | Not Administered | Niet toegediend | | added v2.3
PA | Partially Administered | Gedeeltelijk toegediend | | added v2.3
RE | Refused | Geweigerd | | added v2.3

4.2.13.323 HL7 Version 2 Table 0323

URL: https://hl7.org/fhir/STU3/v2/0323/index.html

This page is part of the FHIR Specification (v3.0.2: STU 3). The current version which supercedes this version is 4.0.1. For a full list of available versions, see the Directory of published versions

Vocabulary Work Group | Maturity Level: N/A | External | Use Context: Any

This is a table defined as part of HL7 v2 . Related FHIR content: v2 Action Code.

Summary

Name: | v2 Action Code
Definition: | FHIR Value set/code system definition for HL7 v2 table 0323 (Action Code)
Code System URL: | http://hl7.org/fhir/v2/0323
Value Set URL: | http://hl7.org/fhir/ValueSet/v2-0323
OID: | ??
CodeSystem Resource | XML / JSON
ValueSet Resource | XML / JSON

This value set is used in the following places:

* This value set is the designated 'entire code system' value set for v2 Action Code

4.2.13.323.1 Code System Content

Action Code

Code | Description | Nederlands (Dutch) | Comment | Version
A | Add/Insert | Toevoeging/invoeging | deprecated | added v2.3, removed after v2.5.1
D | Delete | Verwijdering | deprecated | added v2.3, removed after v2.5.1
U | Update | Update | deprecated | added v2.3, removed after v2.5.1
X | No change | Geen wijziging | deprecated | added v2.5, removed after v2.5.1

4.2.13.324 HL7 Version 2 Table 0324

URL: https://hl7.org/fhir/STU3/v2/0324/index.html

This page is part of the FHIR Specification (v3.0.2: STU 3). The current version which supercedes this version is 4.0.1. For a full list of available versions, see the Directory of published versions

Vocabulary Work Group | Maturity Level: N/A | External | Use Context: Any

This is a table defined as part of HL7 v2 . Related FHIR content: v2 Location Characteristic ID.

Summary

Name: | v2 Location Characteristic ID
Definition: | FHIR Value set/code system definition for HL7 v2 table 0324 (Location Characteristic ID)
Code System URL: | http://hl7.org/fhir/v2/0324
Value Set URL: | http://hl7.org/fhir/ValueSet/v2-0324
OID: | ??
CodeSystem Resource | XML / JSON
ValueSet Resource | XML / JSON

This value set is used in the following places:

* This value set is the designated 'entire code system' value set for v2 Location Characteristic ID

4.2.13.324.1 Code System Content

Location Characteristic ID

Code | Description | Nederlands (Dutch) | Comment | Version

GEN | Gender of patient(s) | Geslacht van patiënt(en) | | added v2.3
IMP | Implant: can be used for radiation implant patients | Implantatie: geschikt voor patiënten met stralingsimplantaten | | added v2.3
INF | Infectious disease: this location can be used for isolation | Infectieziekten: geschikt voor isolatie | | added v2.3
LCR | Level of care | Niveau van zorg | | added v2.3
LIC | Licensed | Gelicenseerd | | added v2.3
OVR | Overflow | Buffer | | added v2.3
PRL | Privacy level: indicating the level of private versus non-private room | Privé niveau: niveau-indicatie van privé/eigen kamer ten opzichte van een niet-privé kamer/gedeelde kamer | | added v2.3
SET | Bed is set up | Bed staat klaar | | added v2.3
SHA | Shadow: a temporary holding location that does not physically exist | Schaduw: een tijdelijke verblijflocatie die niet feitelijk bestaat | | added v2.3
SMK | Smoking | Roken | | added v2.3
STF | Bed is staffed | Er is bedpersoneel | | added v2.3
TEA | Teaching location | Leslocatie | | added v2.3

4.2.13.325 HL7 Version 2 Table 0325

URL: https://hl7.org/fhir/STU3/v2/0325/index.html

This page is part of the FHIR Specification (v3.0.2: STU 3). The current version which supercedes this version is 4.0.1. For a full list of available versions, see the Directory of published versions

Vocabulary Work Group | Maturity Level: N/A | External | Use Context: Any

This is a table defined as part of HL7 v2 . Related FHIR content: v2 Location Relationship ID.

Summary

Name: | v2 Location Relationship ID
Definition: | FHIR Value set/code system definition for HL7 v2 table 0325 (Location Relationship ID)
Code System URL: | http://hl7.org/fhir/v2/0325
Value Set URL: | http://hl7.org/fhir/ValueSet/v2-0325
OID: | ??
CodeSystem Resource | XML / JSON
ValueSet Resource | XML / JSON

This value set is used in the following places:

* This value set is the designated 'entire code system' value set for v2 Location Relationship ID

4.2.13.325.1 Code System Content

Location Relationship ID

Code | Description | Nederlands (Dutch) | Comment | Version
ALI | Location Alias(es) | Locatiealias(sen) | | added v2.3
DTY | Nearest dietary location | Dichtstbijzijnde eetlocatie | | added v2.3
LAB | Nearest lab | Dichtstbijzijnde lab | | added v2.3
LB2 | Second nearest lab | Tweede dichtstbijzijnde lab | | added v2.3
PAR | Parent location | Parent locatie | | added v2.3
RX | Nearest pharmacy | Dichtstbijzijnde apotheek | | added v2.3
RX2 | Second nearest pharmacy | Tweede dichtstbijzijnde apotheek | | added v2.3

4.2.13.326 HL7 Version 2 Table 0326

URL: https://hl7.org/fhir/STU3/v2/0326/index.html

This page is part of the FHIR Specification (v3.0.2: STU 3). The current version which supercedes this version is 4.0.1. For a full list of available versions, see the Directory of published versions

Vocabulary Work Group | Maturity Level: N/A | External | Use Context: Any

This is a table defined as part of HL7 v2 . Related FHIR content: v2 Visit Indicator.

Summary

Name: | v2 Visit Indicator
Definition: | FHIR Value set/code system definition for HL7 v2 table 0326 (Visit Indicator)
Code System URL: | http://hl7.org/fhir/v2/0326
Value Set URL: | http://hl7.org/fhir/ValueSet/v2-0326
OID: | ??
CodeSystem Resource | XML / JSON
ValueSet Resource | XML / JSON

This value set is used in the following places:

* This value set is the designated 'entire code system' value set for v2 Visit Indicator

4.2.13.326.1 Code System Content

Visit Indicator

Code | Description | Deutsch (German) | Nederlands (Dutch) | Comment | Version

A | Account level (default) | Fallanlage bei ambulanten Fällen ohne Erfassung eines Besuchstages | Accountniveau (standaard) | | added v2.3
V | Visit level | Aufnahme (ambulanter Besuch, stationäre Episode) | Bezoekniveau | | added v2.3

4.2.13.329 HL7 Version 2 Table 0329

URL: https://hl7.org/fhir/STU3/v2/0329/index.html

This page is part of the FHIR Specification (v3.0.2: STU 3). The current version which supercedes this version is 4.0.1. For a full list of available versions, see the Directory of published versions

Vocabulary Work Group | Maturity Level: N/A | External | Use Context: Any

This is a table defined as part of HL7 v2 . Related FHIR content: v2 Quantity Method.

Summary

Name: | v2 Quantity Method
Definition: | FHIR Value set/code system definition for HL7 v2 table 0329 (Quantity Method)
Code System URL: | http://hl7.org/fhir/v2/0329
Value Set URL: | http://hl7.org/fhir/ValueSet/v2-0329
OID: | ??
CodeSystem Resource | XML / JSON
ValueSet Resource | XML / JSON

This value set is used in the following places:

* This value set is the designated 'entire code system' value set for v2 Quantity Method

4.2.13.329.1 Code System Content

Quantity Method

Code | Description | Nederlands (Dutch) | Comment | Version
A | Actual count | Werkelijke telling | | added v2.3
E | Estimated (see comment) | Geschat (zie opmerking) | | added v2.3

4.2.13.330 HL7 Version 2 Table 0330

URL: https://hl7.org/fhir/STU3/v2/0330/index.html

This page is part of the FHIR Specification (v3.0.2: STU 3). The current version which supercedes this version is 4.0.1. For a full list of available versions, see the Directory of published versions

Vocabulary Work Group | Maturity Level: N/A | External | Use Context: Any

This is a table defined as part of HL7 v2 . Related FHIR content: v2 Marketing Basis.

Summary

Name: | v2 Marketing Basis
Definition: | FHIR Value set/code system definition for HL7 v2 table 0330 (Marketing Basis)
Code System URL: | http://hl7.org/fhir/v2/0330
Value Set URL: | http://hl7.org/fhir/ValueSet/v2-0330
OID: | ??
CodeSystem Resource | XML / JSON
ValueSet Resource | XML / JSON

This value set is used in the following places:

* This value set is the designated 'entire code system' value set for v2 Marketing Basis

4.2.13.330.1 Code System Content

Marketing Basis

Code | Description | Nederlands (Dutch) | Comment | Version
510E | 510 (K) exempt | 510 (K) vrijstelling | | added v2.3
510K | 510 (K) | 510 (K) | | added v2.3
522S | Post marketing study (522) | Post-marketingonderzoek (522) | | added v2.3
PMA | Premarketing authorization | Pre-marketing autorisatie | | added v2.3
PRE | Preamendment | Pre amendement | | added v2.3
TXN | Transitional | Transitioneel | | added v2.3

4.2.13.331 HL7 Version 2 Table 0331

URL: https://hl7.org/fhir/STU3/v2/0331/index.html

This page is part of the FHIR Specification (v3.0.2: STU 3). The current version which supercedes this version is 4.0.1. For a full list of available versions, see the Directory of published versions

Vocabulary Work Group | Maturity Level: N/A | External | Use Context: Any

This is a table defined as part of HL7 v2 . Related FHIR content: v2 Facility Type.

Summary

Name: | v2 Facility Type
Definition: | FHIR Value set/code system definition for HL7 v2 table 0331 (Facility Type)
Code System URL: | http://hl7.org/fhir/v2/0331
Value Set URL: | http://hl7.org/fhir/ValueSet/v2-0331
OID: | ??
CodeSystem Resource | XML / JSON
ValueSet Resource | XML / JSON

This value set is used in the following places:

* This value set is the designated 'entire code system' value set for v2 Facility Type

4.2.13.331.1 Code System Content

Facility Type

Code | Description | Nederlands (Dutch) | Comment | Version
A | Agent for a foreign manufacturer | Agent voor een buitenlandse fabrikant | | added v2.3
D | Distributor | Distributeur | | added v2.3
M | Manufacturer | Fabrikant | | added v2.3
U | User | Gebruiker | | added v2.3

4.2.13.332 HL7 Version 2 Table 0332

URL: https://hl7.org/fhir/STU3/v2/0332/index.html

This page is part of the FHIR Specification (v3.0.2: STU 3). The current version which supercedes this version is 4.0.1. For a full list of available versions, see the Directory of published versions

Vocabulary Work Group | Maturity Level: N/A | External | Use Context: Any

This is a table defined as part of HL7 v2 . Related FHIR content: v2 Source Type.

Summary

Name: | v2 Source Type
Definition: | FHIR Value set/code system definition for HL7 v2 table 0332 (Source Type)
Code System URL: | http://hl7.org/fhir/v2/0332
Value Set URL: | http://hl7.org/fhir/ValueSet/v2-0332
OID: | ??
CodeSystem Resource | XML / JSON
ValueSet Resource | XML / JSON

This value set is used in the following places:

* This value set is the designated 'entire code system' value set for v2 Source Type

4.2.13.332.1 Code System Content

Source Type

Code | Description | Nederlands (Dutch) | Comment | Version
A | Accept | Accepteren | | added v2.3
I | Initiate | Initiëren | | added v2.3

4.2.13.334 HL7 Version 2 Table 0334

URL: https://hl7.org/fhir/STU3/v2/0334/index.html

This page is part of the FHIR Specification (v3.0.2: STU 3). The current version which supercedes this version is 4.0.1. For a full list of available versions, see the Directory of published versions

Vocabulary Work Group | Maturity Level: N/A | External | Use Context: Any

This is a table defined as part of HL7 v2 . Related FHIR content: v2 Disabled Person Code.

Summary

Name: | v2 Disabled Person Code
Definition: | FHIR Value set/code system definition for HL7 v2 table 0334 (Disabled Person Code)
Code System URL: | http://hl7.org/fhir/v2/0334
Value Set URL: | http://hl7.org/fhir/ValueSet/v2-0334
OID: | ??
CodeSystem Resource | XML / JSON
ValueSet Resource | XML / JSON

This value set is used in the following places:

* This value set is the designated 'entire code system' value set for v2 Disabled Person Code

4.2.13.334.1 Code System Content

Disabled Person Code

Code | Description | Deutsch (German) | Nederlands (Dutch) | Comment | Version

AP | Associated party | | Gerelateerde partij | | added v2.3
GT | Guarantor | Zahlugnspflichtiger | Garantstaande | | added v2.3
IN | Insured | Versicherter | Verzekerde | | added v2.3
PT | Patient | Patient | Patiënt | | added v2.3

4.2.13.335 HL7 Version 2 Table 0335

URL: https://hl7.org/fhir/STU3/v2/0335/index.html

This page is part of the FHIR Specification (v3.0.2: STU 3). The current version which supercedes this version is 4.0.1. For a full list of available versions, see the Directory of published versions

Vocabulary Work Group | Maturity Level: N/A | External | Use Context: Any

This is a table defined as part of HL7 v2 . Related FHIR content: v2 Repeat Pattern.

Summary

Name: | v2 Repeat Pattern
Definition: | FHIR Value set/code system definition for HL7 v2 table 0335 (Repeat Pattern)
Code System URL: | http://hl7.org/fhir/v2/0335
Value Set URL: | http://hl7.org/fhir/ValueSet/v2-0335
OID: | ??
CodeSystem Resource | XML / JSON
ValueSet Resource | XML / JSON

This value set is used in the following places:

* This value set is the designated 'entire code system' value set for v2 Repeat Pattern

4.2.13.335.1 Code System Content

Repeat Pattern

Code | Description | Nederlands (Dutch) | Comment | Version
A | Ante (before) | Ante (vóór) | | added v2.4
BID | twice a day at institution-specified times | twee maal per dag op vastgestelde tijden | (e.g. 9AM-4PM) | added v2.4
C | service is provided continuously between start time and stop time | service wordt continu geleverd tussen starttijd en stoptijd | | added v2.4
D | Cibus Diurnus (lunch) | Cibus Diurnus (lunch) | | added v2.4
I | Inter | Inter | (e.g. between this meal and the next, between dinner and sleep | added v2.4
M | Cibus Matutinus (breakfast) | Cibus Matutinus (ontbijt) | | added v2.4
Meal Related Timings | <timing>C ("cum")<meal> | <timing>C ("cum")<maaltijd> | | added v2.4
Once | one time only. | eenmalig. | This is also the default when this component is null. | added v2.4
P | Post (after) | Post (na) | | added v2.4
PRN | given as needed | zo nodig | | added v2.4
PRNxxx | where xxx is some frequency code | waarbij xxx een of andere frequentiecode is | (e.g. PRNQ6H); given as needed over the frequency period. | added v2.4
Q<integer>D | every <integer> days | elke <integer> dagen | | added v2.4
Q<integer>H | every <integer> hours | elke <integer> uur | | added v2.4
Q<integer>J<day#> | repeats on a particular day of the week, | herhaalt op een bepaalde dag in de week. | From the French jour (day). If <integer> is missing, the repeat rate is assumed to be 1. Day numbers are counted from 1=Monday to 7=Sunday. So Q2J2 means every second Tuesday; Q1J6 means every Saturday. | added v2.4
Q<integer>L | every <integer> months (Lunar cycle) | elke <integer> maanden (maancyclus) | | added v2.4
Q<integer>M | every <integer> minutes | elke <integer> minuten | | added v2.4
Q<integer>S | every <integer> seconds | elke <integer> seconden | | added v2.4
Q<integer>W | every <integer> weeks | elke <integer> weken | | added v2.4
QAM | in the morning at institution-specified time | in de morgen op vastgestelde tijd | | added v2.4
QHS | every day before the hour of sleep | elke dag voor het slapen gaan | | added v2.4
QID | four times a day at institution-specified times | vier maal per dag op vastgestelde tijden | (e.g. 9AM-11AM-4PM-9PM) | added v2.4
QOD | every other day | om de dag | (same as Q2D) | added v2.4
QPM | in the evening at institution-specified time | in de avond op vastgestelde tijden | | added v2.4
QSHIFT | during each of three eight-hour shifts at institution-specified times | tijdens elke van de drie achtuursdiensten op vastgestelde tijden | | added v2.4
TID | three times a day at institution-specified times | drie maal per dag op vastgestelde tijden | (e.g. 9AM-4PM-9PM) | added v2.4
U <spec> | for future use, where <spec> is an interval specification as defined by the UNIX cron specification. | voor toekomstig gebruik, waarbij <spec> een intervalspecificatie is zoals gedefinieerd door de UNIX cron specificatie. | | added v2.4
V | Cibus Vespertinus (dinner) | Cibus Vespertinus (avondeten) | | added v2.4
xID | "X" times per day at institution-specified times, where X is a numeral 5 or greater. | "X" maal per dag op vastgestelde tijden waarbij X een getal van 5 of hoger is. | (e.g. 5ID=five times per day; 8ID=8 times per day) | added v2.4

4.2.13.336 HL7 Version 2 Table 0336

URL: https://hl7.org/fhir/STU3/v2/0336/index.html

This page is part of the FHIR Specification (v3.0.2: STU 3). The current version which supercedes this version is 4.0.1. For a full list of available versions, see the Directory of published versions

Vocabulary Work Group | Maturity Level: N/A | External | Use Context: Any

This is a table defined as part of HL7 v2 . Related FHIR content: v2 Referral Reason.

Summary

Name: | v2 Referral Reason
Definition: | FHIR Value set/code system definition for HL7 v2 table 0336 (Referral Reason)
Code System URL: | http://hl7.org/fhir/v2/0336
Value Set URL: | http://hl7.org/fhir/ValueSet/v2-0336
OID: | ??
CodeSystem Resource | XML / JSON
ValueSet Resource | XML / JSON

This value set is used in the following places:

* This value set is the designated 'entire code system' value set for v2 Referral Reason

4.2.13.336.1 Code System Content

Referral Reason

Code | Description | Nederlands (Dutch) | Comment | Version
O | Provider Ordered | Verzoek zorgverlener | | added v2.3
P | Patient Preference | Verzoek patiënt | | added v2.3
S | Second Opinion | Second opinion | | added v2.3
W | Work Load | Werkdruk | | added v2.3

4.2.13.337 HL7 Version 2 Table 0337

URL: https://hl7.org/fhir/STU3/v2/0337/index.html

This page is part of the FHIR Specification (v3.0.2: STU 3). The current version which supercedes this version is 4.0.1. For a full list of available versions, see the Directory of published versions

Vocabulary Work Group | Maturity Level: N/A | External | Use Context: Any

This is a table defined as part of HL7 v2 . Related FHIR content: v2 Certification Status.

Summary

Name: | v2 Certification Status
Definition: | FHIR Value set/code system definition for HL7 v2 table 0337 (Certification Status)
Code System URL: | http://hl7.org/fhir/v2/0337
Value Set URL: | http://hl7.org/fhir/ValueSet/v2-0337
OID: | ??
CodeSystem Resource | XML / JSON
ValueSet Resource | XML / JSON

This value set is used in the following places:

* This value set is the designated 'entire code system' value set for v2 Certification Status

4.2.13.337.1 Code System Content

Certification Status

Code | Description | Nederlands (Dutch) | Comment | Version
C | Certified | Gecertificeerd | | added v2.3
E | Eligible | Komt in aanmerking | | added v2.3

4.2.13.338 HL7 Version 2 Table 0338

URL: https://hl7.org/fhir/STU3/v2/0338/index.html

This page is part of the FHIR Specification (v3.0.2: STU 3). The current version which supercedes this version is 4.0.1. For a full list of available versions, see the Directory of published versions

Vocabulary Work Group | Maturity Level: N/A | External | Use Context: Any

This is a table defined as part of HL7 v2 . Related FHIR content: v2 Practitioner ID Number Type.

Summary

Name: | v2 Practitioner ID Number Type
Definition: | FHIR Value set/code system definition for HL7 v2 table 0338 (Practitioner ID Number Type)
Code System URL: | http://hl7.org/fhir/v2/0338
Value Set URL: | http://hl7.org/fhir/ValueSet/v2-0338
OID: | ??
CodeSystem Resource | XML / JSON
ValueSet Resource | XML / JSON

This value set is used in the following places:

* This value set is the designated 'entire code system' value set for v2 Practitioner ID Number Type

4.2.13.338.1 Code System Content

Practitioner ID Number Type

Code | Description | Nederlands (Dutch) | Comment | Version
CY | County number | Provincie-nummer | | added v2.3
DEA | Drug Enforcement Agency no. | Drug Enforcement Agency-nummer | | added v2.3
GL | General ledger number | Grootboek-nummer | | added v2.3
L&I | Labor and industries number | Arbeid en Industrie-nummer | Deprecated as of v 2.5; Use LI instead | added v2.3
LI | Labor and industries number | Arbeid en Industrie-nummer | | added v2.5
MCD | Medicaid number | Medicaid-nummer | | added v2.3
MCR | Medicare number | Medicare-nummer | | added v2.3
QA | QA number | QA-nummer | | added v2.3
SL | State license number | Staat licentienummer | | added v2.3
TAX | Tax ID number | SoFi-nummer | | added v2.3
TRL | Training license number | Opleiding licentie-nummer | | added v2.3
UPIN | Unique physician ID no. | Uniek Arts ID-nummer | | added v2.3

4.2.13.339 HL7 Version 2 Table 0339

URL: https://hl7.org/fhir/STU3/v2/0339/index.html

This page is part of the FHIR Specification (v3.0.2: STU 3). The current version which supercedes this version is 4.0.1. For a full list of available versions, see the Directory of published versions

Vocabulary Work Group | Maturity Level: N/A | External | Use Context: Any

This is a table defined as part of HL7 v2 . Related FHIR content: v2 Advanced Beneficiary Notice Code.

Summary

Name: | v2 Advanced Beneficiary Notice Code
Definition: | FHIR Value set/code system definition for HL7 v2 table 0339 (Advanced Beneficiary Notice Code)
Code System URL: | http://hl7.org/fhir/v2/0339
Value Set URL: | http://hl7.org/fhir/ValueSet/v2-0339
OID: | ??
CodeSystem Resource | XML / JSON
ValueSet Resource | XML / JSON

This value set is used in the following places:

* This value set is the designated 'entire code system' value set for v2 Advanced Beneficiary Notice Code

4.2.13.339.1 Code System Content

Advanced Beneficiary Notice Code

Code | Description | Deutsch (German) | Comment | Version
1 | Service is subject to medical necessity procedures | Zuzahlung muss abgeklärt werden | | added v2.3.1
2 | Patient has been informed of responsibility, and agrees to pay for service | | | added v2.3.1
3 | Patient has been informed of responsibility, and asks that the payer be billed | Patient fragt nach Rechnung | | added v2.3.1
4 | Advanced Beneficiary Notice has not been signed | Zustimmung zur Zuzahlung liegt nicht vor | | added v2.3.1

4.2.13.344 HL7 Version 2 Table 0344

URL: https://hl7.org/fhir/STU3/v2/0344/index.html

This page is part of the FHIR Specification (v3.0.2: STU 3). The current version which supercedes this version is 4.0.1. For a full list of available versions, see the Directory of published versions

Vocabulary Work Group | Maturity Level: N/A | External | Use Context: Any

This is a table defined as part of HL7 v2 . Related FHIR content: v2 Patient's Relationship to Insured.

Summary

Name: | v2 Patient's Relationship to Insured
Definition: | FHIR Value set/code system definition for HL7 v2 table 0344 (Patient's Relationship to Insured)
Code System URL: | http://hl7.org/fhir/v2/0344
Value Set URL: | http://hl7.org/fhir/ValueSet/v2-0344
OID: | ??
CodeSystem Resource | XML / JSON
ValueSet Resource | XML / JSON

This value set is used in the following places:

* This value set is the designated 'entire code system' value set for v2 Patient's Relationship to Insured

4.2.13.344.1 Code System Content

Patient's Relationship to Insured

Code | Description | Deutsch (German) | Nederlands (Dutch) | Comment | Version
01 | Patient is insured | | Patiënt is zelf verzekerd | | added v2.3.1
02 | Spouse | | Echtgenoot | | added v2.3.1
03 | Natural child/insured financial responsibility | | Biologisch kind/financiële verantwoordelijkheid verzekerde | | added v2.3.1
04 | Natural child/Insured does not have financial responsibility | | Biologisch kind/geen financiële verantwoordelijkheid verzekerde | | added v2.3.1

05 | Step child | | Stiefkind | | added v2.3.1
06 | Foster child | | Pleegkind | | added v2.3.1
07 | Ward of the court | | Wettelijk voogd | | added v2.3.1
08 | Employee | | Werknemer | | added v2.3.1
09 | Unknown | | Onbekend | | added v2.3.1
10 | Handicapped dependent | behinderter Angehöriger | Gehandicapt afhankelijke | | added v2.3.1
11 | Organ donor | Organspender | Orgaandonor | | added v2.3.1
12 | Cadaver donor | Körper-/Leichenspender (bspw. für anatomische Studien; wir Organspender, nur nach dem Tod) | Kadaverdonor | | added v2.3.1
13 | Grandchild | Enkel | Kleinkind | | added v2.3.1
14 | Niece/nephew | Nichte/Neffe | Nicht/neef | | added v2.3.1
15 | Injured plaintiff | verletzter Kläger | Gewonde aanklagende partij | | added v2.3.1
16 | Sponsored dependent | Unterhaltsberechtigter | Gesponsorde afhankelijke | | added v2.3.1
17 | Minor dependent of a minor dependent | Kind eines Minderjährigen | Minderjarige afhankelijke van minderjarige afhankelijke | | added v2.3.1
18 | Parent | Eltern | Ouder | | added v2.3.1
19 | Grandparent | Großeltern | Grootouder | | added v2.3.1

4.2.13.350 HL7 Version 2 Table 0350

URL: https://hl7.org/fhir/STU3/v2/0350/index.html

This page is part of the FHIR Specification (v3.0.2: STU 3). The current version which supercedes this version is 4.0.1. For a full list of available versions, see the Directory of published versions

Vocabulary Work Group | Maturity Level: N/A | External | Use Context: Any

This is a table defined as part of HL7 v2 . Related FHIR content: v2 Occurrence Code.

Summary

Name: | v2 Occurrence Code
Definition: | FHIR Value set/code system definition for HL7 v2 table 0350 (Occurrence Code)
Code System URL: | http://hl7.org/fhir/v2/0350
Value Set URL: | http://hl7.org/fhir/ValueSet/v2-0350
OID: | ??
CodeSystem Resource | XML / JSON
ValueSet Resource | XML / JSON

This value set is used in the following places:

* This value set is the designated 'entire code system' value set for v2 Occurrence Code

4.2.13.350.1 Code System Content

Occurrence Code

Code | Description | Nederlands (Dutch) | Comment | Version
... | Use NUBC codes | Zie (Amerikaanse) NUBC codes | | added v2.5.1
01 | Auto accident | | deprecated | added v2.3.1, removed after v2.4
02 | No fault insurance involved-including auto accident/other | | deprecated | added v2.3.1, removed after v2.4
03 | Accident/tort liability | | deprecated | added v2.3.1, removed after v2.4
04 | Accident/employment related | | deprecated | added v2.3.1, removed after v2.4
05 | Other accident | | deprecated | added v2.3.1, removed after v2.4
06 | Crime victim | | deprecated | added v2.3.1, removed after v2.4
09 | Start of infertility treatment cycle | | deprecated | added v2.3.1, removed after v2.4
10 | Last menstrual period | | deprecated | added v2.3.1, removed after v2.4
11 | Onset of symptoms/illness | | deprecated | added v2.3.1, removed after v2.4
12 | Date of onset for a chronically dependent individual | | deprecated | added v2.3.1, removed after v2.4
17 | Date outpatient occupational therapy plan established or last reviewed | | deprecated | added v2.3.1, removed after v2.4
18 | Date of retirement patient/beneficiary | | deprecated | added v2.3.1, removed after v2.4
19 | Date of retirement spouse | | deprecated | added v2.3.1, removed after v2.4
20 | Guarantee of payment began | | deprecated | added v2.3.1, removed after v2.4
21 | UR notice received | | deprecated | added v2.3.1, removed after v2.4
22 | Date active care ended | | deprecated | added v2.3.1, removed after v2.4
24 | Date insurance denied | | deprecated | added v2.3.1, removed after v2.4
25 | Date benefits terminated by primary payor | | deprecated | added v2.3.1, removed after v2.4
26 | Date SNF bed available | | deprecated | added v2.3.1, removed after v2.4
27 | Date home health plan established | | deprecated | added v2.3.1, removed after v2.4
28 | Spouse's date of birth | | deprecated | added v2.3.1, removed after v2.4
29 | Date outpatient physical therapy plan established or last reviewed | | deprecated | added v2.3.1, removed after v2.4
30 | Date outpatient speech pathology plan established or last reviewed | | deprecated | added v2.3.1, removed after v2.4
31 | Date beneficiary notified of intent to bill (accommodations) | | deprecated | added v2.3.1, removed after v2.4
32 | Date beneficiary notified of intent to bill (procedures or treatments) | | deprecated | added v2.3.1, removed after v2.4
33 | First day of the Medicare coordination period for ESRD beneficiaries covered by EGHP | | deprecated | added v2.3.1, removed after v2.4
34 | Date of election of extended care facilities | | deprecated | added v2.3.1, removed after v2.4
35 | Date treatment started for P.T. | | deprecated | added v2.3.1, removed after v2.4
36 | Date of inpatient hospital discharge for covered transplant patients | | deprecated | added v2.3.1, removed after v2.4
37 | Date of inpatient hospital discharge for non-covered transplant patient | | deprecated | added v2.3.1, removed after v2.4

40 | Scheduled date of admission | | deprecated | added v2.3.1, removed after v2.4
41 | Date of first test for pre-admission testing | | deprecated | added v2.3.1, removed after v2.4
42 | Date of discharge | | deprecated | added v2.3.1, removed after v2.4
43 | Scheduled date of canceled surgery | | deprecated | added v2.3.1, removed after v2.4
44 | Date treatment started for O.T. | | deprecated | added v2.3.1, removed after v2.4
45 | Date treatment started for S.T. | | deprecated | added v2.3.1, removed after v2.4
46 | Date treatment started for cardiac rehab. | | deprecated | added v2.3.1, removed after v2.4
47 | Payer codes | | deprecated | added v2.3.1, removed after v2.4
47 ... 49 | Payer codes | | deprecated | added v2.3.1, removed after v2.4
48 | Payer codes | | deprecated | added v2.3.1, removed after v2.4
49 | Payer codes | | deprecated | added v2.3.1, removed after v2.4
50 | Date lien released | | deprecated | added v2.3.1, removed after v2.4
51 | Date treatment started for psychiatric care | | deprecated | added v2.3.1, removed after v2.4
70 | Occurrence span codes and dates | | deprecated | added v2.3.1, removed after v2.4
70 ... 99 | Occurrence span codes and dates | | deprecated | added v2.3.1, removed after v2.4
71 | Occurrence span codes and dates | | deprecated | added v2.3.1, removed after v2.4
72 | Occurrence span codes and dates | | deprecated | added v2.3.1, removed after v2.4
73 | Occurrence span codes and dates | | deprecated | added v2.3.1, removed after v2.4
74 | Occurrence span codes and dates | | deprecated | added v2.3.1, removed after v2.4
75 | Occurrence span codes and dates | | deprecated | added v2.3.1, removed after v2.4
76 | Occurrence span codes and dates | | deprecated | added v2.3.1, removed after v2.4
77 | Occurrence span codes and dates | | deprecated | added v2.3.1, removed after v2.4
78 | Occurrence span codes and dates | | deprecated | added v2.3.1, removed after v2.4
79 | Occurrence span codes and dates | | deprecated | added v2.3.1, removed after v2.4
80 | Occurrence span codes and dates | | deprecated | added v2.3.1, removed after v2.4
81 | Occurrence span codes and dates | | deprecated | added v2.3.1, removed after v2.4
82 | Occurrence span codes and dates | | deprecated | added v2.3.1, removed after v2.4
83 | Occurrence span codes and dates | | deprecated | added v2.3.1, removed after v2.4
84 | Occurrence span codes and dates | | deprecated | added v2.3.1, removed after v2.4
85 | Occurrence span codes and dates | | deprecated | added v2.3.1, removed after v2.4
86 | Occurrence span codes and dates | | deprecated | added v2.3.1, removed after v2.4
87 | Occurrence span codes and dates | | deprecated | added v2.3.1, removed after v2.4
88 | Occurrence span codes and dates | | deprecated | added v2.3.1, removed after v2.4
89 | Occurrence span codes and dates | | deprecated | added v2.3.1, removed after v2.4
90 | Occurrence span codes and dates | | deprecated | added v2.3.1, removed after v2.4
91 | Occurrence span codes and dates | | deprecated | added v2.3.1, removed after v2.4
92 | Occurrence span codes and dates | | deprecated | added v2.3.1, removed after v2.4
93 | Occurrence span codes and dates | | deprecated | added v2.3.1, removed after v2.4
94 | Occurrence span codes and dates | | deprecated | added v2.3.1, removed after v2.4
95 | Occurrence span codes and dates | | deprecated | added v2.3.1, removed after v2.4
96 | Occurrence span codes and dates | | deprecated | added v2.3.1, removed after v2.4
97 | Occurrence span codes and dates | | deprecated | added v2.3.1, removed after v2.4
98 | Occurrence span codes and dates | | deprecated | added v2.3.1, removed after v2.4
99 | Occurrence span codes and dates | | deprecated | added v2.3.1, removed after v2.4
A1 | Birthdate - insured A | | deprecated | added v2.3.1, removed after v2.4
A2 | Effective date - insured A policy | | deprecated | added v2.3.1, removed after v2.4
A3 | Benefits exhausted payer A | | deprecated | added v2.3.1, removed after v2.4
… | Use NUBC codes | Zie (Amerikaanse) NUBC codes | deprecated | added v2.7.1, removed after v2.7.1

4.2.13.351 HL7 Version 2 Table 0351

URL: https://hl7.org/fhir/STU3/v2/0351/index.html

This page is part of the FHIR Specification (v3.0.2: STU 3). The current version which supercedes this version is 4.0.1. For a full list of available versions, see the Directory of published versions

Vocabulary Work Group | Maturity Level: N/A | External | Use Context: Any

This is a table defined as part of HL7 v2 . Related FHIR content: v2 Occurrence Span.

Summary

Name: | v2 Occurrence Span
Definition: | FHIR Value set/code system definition for HL7 v2 table 0351 (Occurrence Span)
Code System URL: | http://hl7.org/fhir/v2/0351
Value Set URL: | http://hl7.org/fhir/ValueSet/v2-0351
OID: | ??
CodeSystem Resource | XML / JSON
ValueSet Resource | XML / JSON

This value set is used in the following places:

* This value set is the designated 'entire code system' value set for v2 Occurrence Span

4.2.13.351.1 Code System Content

Occurrence Span

Code | Description | Nederlands (Dutch) | Comment | Version
... | use NUBC codes | Zie (Amerikaanse) NUBC codes | | added v2.6
70 | Qualifying stay dates for SNF | | deprecated | added v2.3.1, removed after v2.4
71 | Prior stay dates | | deprecated | added v2.3.1, removed after v2.4
72 | First/last visit | | deprecated | added v2.3.1, removed after v2.4
73 | Benefit eligibility period | | deprecated | added v2.3.1, removed after v2.4
74 | Non-covered level of care | | deprecated | added v2.3.1, removed after v2.4
75 | SNF level of care | | deprecated | added v2.3.1, removed after v2.4
76 | Patient liability | | deprecated | added v2.3.1, removed after v2.4
77 | Provider liability period | | deprecated | added v2.3.1, removed after v2.4
78 | SNF prior stay dates | | deprecated | added v2.3.1, removed after v2.4
79 | Payer code | | deprecated | added v2.3.1, removed after v2.4
M0 | PSRO/UR approved stay dates | | deprecated | added v2.3.1, removed after v2.4
… | use NUBC codes | | deprecated | added v2.5.1, removed after v2.7.1

4.2.13.353 HL7 Version 2 Table 0353

URL: https://hl7.org/fhir/STU3/v2/0353/index.html

This page is part of the FHIR Specification (v3.0.2: STU 3). The current version which supercedes this version is 4.0.1. For a full list of available versions, see the Directory of published versions

Vocabulary Work Group | Maturity Level: N/A | External | Use Context: Any

This is a table defined as part of HL7 v2 . Related FHIR content: v2 CWE statuses.

Summary

Name: | v2 CWE statuses
Definition: | FHIR Value set/code system definition for HL7 v2 table 0353 (CWE statuses)
Value Set URL: | http://hl7.org/fhir/ValueSet/v2-0353
OID: | ??
ValueSet Resource | XML / JSON

This value set is not currently used

4.2.13.353.1 Logical Definition

CWE statuses

Code | System | Description | Comment | Version
NA | http://hl7.org/fhir/v3/NullFlavor | Not applicable | | added v2.3.1
NASK | http://hl7.org/fhir/v3/NullFlavor | Not asked | | added v2.3.1
NAV | http://hl7.org/fhir/v3/NullFlavor | Not available | | added v2.3.1
U | ??::UNK | Unknown | Wrongly Included as U. | added v2.3.1
UASK | ??::ASKU | Asked but Unknown | Wrongly Included as UASK. | added v2.3.1

4.2.13.354 HL7 Version 2 Table 0354

URL: https://hl7.org/fhir/STU3/v2/0354/index.html

This page is part of the FHIR Specification (v3.0.2: STU 3). The current version which supercedes this version is 4.0.1. For a full list of available versions, see the Directory of published versions

Vocabulary Work Group | Maturity Level: N/A | External | Use Context: Any

This is a table defined as part of HL7 v2 . Related FHIR content: v2 Message Structure.

Summary

Name: | v2 Message Structure
Definition: | FHIR Value set/code system definition for HL7 v2 table 0354 (Message Structure)
Code System URL: | http://hl7.org/fhir/v2/0354
Value Set URL: | http://hl7.org/fhir/ValueSet/v2-0354
OID: | ??
CodeSystem Resource | XML / JSON
ValueSet Resource | XML / JSON

This value set is used in the following places:

* This value set is the designated 'entire code system' value set for v2 Message Structure

4.2.13.354.1 Code System Content

Message Structure

Code | Description | Nederlands (Dutch) | Comment | Version
ACK | Varies | Varies | | added v2.3.1
ADR_A19 | | A19 | Deprecated and removed as of V2.7 | added v2.3.1
ADT_A01 | A01, A04, A08, A13 | A01, A04, A08, A13 | | added v2.3.1
ADT_A02 | A02 | A02 | | added v2.3.1
ADT_A03 | A03 | A03 | | added v2.3.1

ADT_A05 | A05, A14, A28, A31 | A05, A14, A28, A31 | | added v2.4
ADT_A06 | A06, A07 | A06, A07 | | added v2.3.1
ADT_A09 | A09, A10, A11 | A09, A10, A11 | | added v2.3.1
ADT_A12 | A12 | A12 | | added v2.3.1
ADT_A15 | A15 | A15 | | added v2.4
ADT_A16 | A16 | A16 | | added v2.3.1
ADT_A17 | A17 | A17 | | added v2.3.1
ADT_A18 | | A18 | Deprecated and removed as of V2.7 | added v2.3.1
ADT_A20 | A20 | A20 | | added v2.3.1
ADT_A21 | A21, A22, A23, A25, A26, A27, A29, A32, A33 | A21, A22, A23, A25, A26, A27, A29, A32, A33 | | added v2.4
ADT_A24 | A24 | A24 | | added v2.3.1
ADT_A28 | A28, A31 | A28, A31 | deprecated | added v2.3.1, removed after v2.3.1
ADT_A30 | | A30, A34, A35, A36, A46, A47, A48, A49 | Deprecated and removed as of V2.7 | added v2.3.1
ADT_A37 | A37 | A37 | | added v2.3.1
ADT_A38 | A38 | A38 | | added v2.3.1
ADT_A39 | A39, A40, A41, A42 | A39, A40, A41, A42 | | added v2.3.1
ADT_A43 | A43 | A43 | | added v2.3.1
ADT_A44 | A44 | A44 | | added v2.7
ADT_A45 | A45 | A45 | | added v2.3.1
ADT_A50 | A50, A51 | A50, A51 | | added v2.3.1
ADT_A52 | A52, A53 | A52, A53 | | added v2.4
ADT_A54 | A54, A55 | A54, A55 | | added v2.4
ADT_A60 | A60 | A60 | | added v2.4
ADT_A61 | A61, A62 | A61, A62 | | added v2.4
ARD_A19 | A19 | A19 | type (ADR_A19) | added v2.3.1, removed after v2.3.1
BAR_P01 | P01 | P01 | | added v2.3.1
BAR_P02 | P02 | P02 | | added v2.3.1
BAR_P05 | P05 | P05 | | added v2.4
BAR_P06 | P06 | P06 | | added v2.3.1
BAR_P10 | P10 | P10 | | added v2.4
BAR_P12 | P12 | P12 | | added v2.5
BPS_O29 | O29 | O29 | | added v2.5
BRP_030 | O30 | O30 | this is a typo BRP_O30) and should be removed | added v2.5, removed after v2.5
BRP_O30 | O30 | O30 | added as a correction for BRP_030 | added v2.5
BRT_O32 | O32 | O32 | | added v2.5
BTS_O31 | O31 | O31 | | added v2.5
CCF_I22 | I22 | I22 | | added v2.7
CCI_I22 | I22 | I22 | | added v2.7
CCM_I21 | I21 | I21 | | added v2.7
CCQ_I19 | I19 | I19 | | added v2.7
CCR_I16 | I16, |17, |18 | I16, |17, |18 | | added v2.7
CCU_I20 | I20 | I20 | | added v2.7
CQU_I19 | I19 | I19 | | added v2.7
CRM_C01 | C01, C02, C03, C04, C05, C06, C07, C08 | C01, C02, C03, C04, C05, C06, C07, C08 | | added v2.3.1
CSU_C09 | C09, C10, C11, C12 | C09, C10, C11, C12 | | added v2.3.1
DBC_O41 | O41 | O41 | | added v2.8
DBC_O42 | O42 | O42 | | added v2.8
DEL_O46 | O46 | O46 | | added v2.8
DEO_O45 | O45 | O45 | | added v2.8
DER_O44 | O44 | O44 | | added v2.8
DFT_P03 | P03 | P03 | | added v2.3.1
DFT_P11 | P11 | P11 | | added v2.5
DOC_T12 | | T12 | Deprecated and removed as of V2.7 | added v2.3.1
DPR_O48 | O48 | O48 | | added v2.8
DRC_O47 | O47 | O47 | | added v2.8
DRG_O43 | O43 | O43 | | added v2.8
DSR_P04 | P04 | P04 | deprecated | added v2.4, removed after v2.5.1
DSR_Q01 | Q01 | Q01 | deprecated | added v2.3.1, removed after v2.6
DSR_Q03 | Q03 | Q03 | deprecated | added v2.3.1, removed after v2.6
EAC_U07 | U07 | U07 | | added v2.4
EAN_U09 | U09 | U09 | | added v2.4
EAR_U08 | U08 | U08 | | added v2.4
EDR_R07 | R07 | R07 | deprecated | added v2.3.1, removed after v2.5.1
EHC_E01 | E01 | E01 | | added v2.6
EHC_E02 | E02 | E02 | | added v2.6
EHC_E04 | E04 | E04 | | added v2.6
EHC_E10 | E10 | E10 | | added v2.6
EHC_E12 | E12 | E12 | | added v2.6
EHC_E13 | E13 | E13 | | added v2.6
EHC_E15 | E15 | E15 | | added v2.6
EHC_E20 | E20 | E20 | | added v2.6
EHC_E21 | E21 | E21 | | added v2.6

EHC_E24 | E24 | E24 | | added v2.6
EQQ_Q04 | Q04 | Q04 | deprecated | added v2.3.1, removed after v2.5.1
ERP_R09 | R09 | R09 | deprecated | added v2.3.1, removed after v2.5.1
ESR_U02 | U02 | U02 | | added v2.4
ESU_U01 | U01 | U01 | | added v2.4
INR_U06 | U06 | U06 | | added v2.4
INU_U05 | U05 | U05 | | added v2.4
LSU_U12 | U12, U13 | U12, U13 | | added v2.4
MDM_T01 | T01, T03, T05, T07, T09, T11 | T01, T03, T05, T07, T09, T11 | | added v2.3.1
MDM_T02 | T02, T04, T06, T08, T10 | T02, T04, T06, T08, T10 | | added v2.3.1
MFD_MFA | MFA | MFA | deprecated | added v2.4, removed after v2.5.1
MFD_P09 | P09 | P09 | error -> SUR_P09 | added v2.3.1, removed after v2.3.1
MFK_M01 | M01, M02, M03, M04, M05, M06, M07, M08, M09, M10, M11 | M01, M02, M03, M04, M05, M06, M07, M08, M09, M10, M11 | | added v2.3.1
MFN_M01 | | M01 | Deprecated and removed as of V2.7 | added v2.3.1
MFN_M02 | M02 | M02 | | added v2.3.1
MFN_M03 | M03 | M03 | Deprecated | added v2.3.1
MFN_M04 | M04 | M04 | | added v2.4
MFN_M05 | M05 | M05 | | added v2.3.1
MFN_M06 | M06 | M06 | | added v2.3.1
MFN_M07 | M07 | M07 | | added v2.3.1
MFN_M08 | M08 | M08 | | added v2.3.1
MFN_M09 | M09 | M09 | | added v2.3.1
MFN_M10 | M10 | M10 | | added v2.3.1
MFN_M11 | M11 | M11 | | added v2.3.1
MFN_M12 | M12 | M12 | | added v2.4
MFN_M13 | M13 | M13 | | added v2.5
MFN_M15 | M15 | M15 | | added v2.5
MFN_M16 | M16 | M16 | | added v2.6
MFN_M17 | M17 | M17 | | added v2.6
MFN_M18 | M18 | M18 | | added v2.8.2
MFQ_M01 | M01, M02, M03, M04, M05, M06 | M01, M02, M03, M04, M05, M06 | Deprecated | added v2.4
MFR_M01 | M01, M02, M03, | M01, M02, M03, | Deprecated | added v2.4
MFR_M04 | M04 | M04 | Deprecated | added v2.5.1
MFR_M05 | M05 | M05 | Deprecated | added v2.5.1
MFR_M06 | M06 | M06 | Deprecated | added v2.5.1
MFR_M07 | M07 | M07 | Deprecated | added v2.5.1
NMD_N02 | N02 | N02 | | added v2.4
NMQ_N01 | N01 | N01 | Deprecated | added v2.4
NMR_N01 | N01 | N01 | Deprecated | added v2.4
OMB_O27 | O27 | O27 | | added v2.5
OMD_O01 | | | deprecated | added v2.3.1, removed after v2.3.1
OMD_O03 | O03 | O03 | | added v2.4
OMG_O19 | O19 | O19 | | added v2.4
OMI_O23 | O23 | O23 | | added v2.5
OML_O21 | O21 | O21 | | added v2.4
OML_O33 | O33 | O33 | | added v2.5
OML_O35 | O35 | O35 | | added v2.5
OML_O39 | O39 | O39 | | added v2.7
OMN_O01 | | | deprecated | added v2.3.1, removed after v2.3.1
OMN_O07 | O07 | O07 | | added v2.4
OMP_O09 | O09 | O09 | | added v2.4
OMQ_O42 | O42 | O42 | | added v2.8
OMS_O01 | | | deprecated | added v2.3.1, removed after v2.3.1
OMS_O05 | O05 | O05 | | added v2.4
OPL_O37 | O37 | O37 | | added v2.6
OPR_O38 | O38 | O38 | | added v2.6
OPU_R25 | R25 | R25 | | added v2.6
ORA_R33 | R33 | R33 | | added v2.7
ORA_R41 | R41 | R41 | | added v2.8
ORB_O28 | O28 | O28 | | added v2.5
ORD_O02 | | | deprecated | added v2.3.1, removed after v2.3.1
ORD_O04 | O04 | O04 | | added v2.4
ORF_R02 | R02, R04 | R02, R04 | deprecated | added v2.3.1, removed after v2.3.1
ORF_R04 | R04 | R04 | Deprecated | added v2.4
ORG_O20 | O20 | O20 | | added v2.4
ORI_O24 | O24 | O24 | | added v2.5
ORL_O22 | O22 | O22 | | added v2.4
ORL_O34 | O34 | O34 | | added v2.5
ORL_O36 | O36 | O36 | | added v2.5
ORL_O40 | O40 | O40 | | added v2.7
ORL_O41 | O41 | O41 | | added v2.8.1

ORL_O42 | O42 | O42 | | added v2.8.1
ORL_O43 | O43 | O43 | | added v2.8.1
ORL_O44 | O44 | O44 | | added v2.8.1
ORM_O01 | O01 | O01 | Deprecated | added v2.3.1
ORM_Q06 | Q06 | Q06 | deprecated | added v2.3.1, removed after v2.3.1
ORN_O02 | | | deprecated | added v2.3.1, removed after v2.3.1
ORN_O08 | O08 | O08 | | added v2.4
ORP_O10 | O10 | O10 | | added v2.4
ORR_O02 | O02 | O02 | Deprecated | added v2.3.1
ORR_Q06 | Q06 | Q06 | deprecated | added v2.3.1, removed after v2.3.1
ORS_O02 | | | deprecated | added v2.3.1, removed after v2.3.1
ORS_O06 | O06 | O06 | | added v2.4
ORU_R01 | R01 | R01 | | added v2.3.1
ORU_R30 | R30 | R30 | | added v2.5
ORU_R31 | R31 | R31 | deprecated | added v2.5, removed after v2.5
ORU_R32 | R32 | R32 | deprecated | added v2.5, removed after v2.5
ORU_W01 | W01 | W01 | Deprecated | added v2.3.1
ORX_O43 | O43 | O43 | | added v2.8
OSM_R26 | R26 | R26 | | added v2.7
OSQ_Q06 | Q06 | Q06 | Deprecated | added v2.3.1
OSR_Q06 | Q06 | Q06 | Deprecated | added v2.3.1
OSU_O41 | O41 | O41 | | added v2.8
OUL_R21 | R21 | R21 | Deprecated | added v2.4
OUL_R22 | R22 | R22 | | added v2.5
OUL_R23 | R23 | R23 | | added v2.5
OUL_R24 | R24 | R24 | | added v2.5
PEX_P07 | P07, P08 | P07, P08 | | added v2.3.1
PGL_PC6 | PC6, PC7, PC8 | PC6, PC7, PC8 | | added v2.3.1
PIN_I07 | I07 | I07 | deprecated | added v2.3.1, removed after v2.3.1
PMU_B01 | B01, B02 | B01, B02 | | added v2.4
PMU_B03 | B03 | B03 | | added v2.4
PMU_B04 | B04, B05, B06 | B04, B05, B06 | | added v2.4
PMU_B07 | B07 | B07 | | added v2.5
PMU_B08 | B08 | B08 | | added v2.5
PPG_PCG | PCC, PCG, PCH, PCJ | PCC, PCG, PCH, PCJ | | added v2.3.1
PPP_PCB | PCB, PCD | PCB, PCD | | added v2.3.1
PPR_PC1 | PC1, PC2, PC3 | PC1, PC2, PC3 | | added v2.3.1
PPT_PCL | PCL | PCL | Deprecated | added v2.3.1
PPV_PCA | PCA | PCA | Deprecated | added v2.3.1
PRR_PC5 | PC5 | PC5 | Deprecated | added v2.3.1
PTR_PCF | PCF | PCF | Deprecated | added v2.3.1
QBP_E03 | E03 | E03 | | added v2.6
QBP_E22 | E22 | E22 | | added v2.6
QBP_O33 | O33 | O33 | | added v2.8
QBP_O34 | O34 | O34 | | added v2.8
QBP_Q11 | Q11 | Q11 | | added v2.4
QBP_Q13 | Q13 | Q13 | | added v2.4
QBP_Q15 | Q15 | Q15 | | added v2.4
QBP_Q21 | Q21, Q22, Q23,Q24, Q25 | Q21, Q22, Q23,Q24, Q25 | | added v2.4
QBP_Qnn | Qnn | Qnn | deprecated | added v2.7, removed after v2.7
QBP_Z73 | Z73 | Z73 | deprecated | added v2.7, removed after v2.7
QCK_Q02 | Q02 | Q02 | Deprecated | added v2.3.1
QCN_J01 | J01, J02 | J01, J02 | | added v2.4
QRF_W02 | W02 | W02 | Deprecated | added v2.5
QRY_A19 | A19 | A19 | Deprecated | added v2.3.1
QRY_P04 | P04 | P04 | deprecated | added v2.5, removed after v2.5.1
QRY_PC4 | PC4, PC9, PCE, PCK | PC4, PC9, PCE, PCK | Deprecated | added v2.3.1
QRY_Q01 | Q01, Q26, Q27, Q28, Q29, Q30 | Q01, Q26, Q27, Q28, Q29, Q30 | Deprecated | added v2.3.1
QRY_Q02 | Q02 | Q02 | Deprecated | added v2.3.1
QRY_R02 | R02 | R02 | Deprecated | added v2.3.1
QRY_T12 | T12 | T12 | Deprecated | added v2.3.1
QSB_Q16 | Q16 | Q16 | | added v2.4
QVR_Q17 | Q17 | Q17 | | added v2.4
RAR_RAR | RAR | RAR | Deprecated | added v2.3.1
RAS_O01 | O01 | O01 | deprecated | added v2.3.1, removed after v2.3.1
RAS_O02 | O022 | O022 | deprecated | added v2.3.1, removed after v2.3.1
RAS_O17 | O17 | O17 | | added v2.4
RCI_I05 | I05 | I05 | Deprecated | added v2.3.1
RCL_I06 | I06 | I06 | Deprecated | added v2.3.1
RDE_O01 | O01 | O01 | deprecated | added v2.3.1, removed after v2.5
RDE_O11 | O11, O25 | O11, O25 | | added v2.4
RDO_O01 | | | deprecated | added v2.3.1, removed after v2.3.1

RDR_RDR | RDR | RDR | | added v2.3.1
RDS_O01 | O01 | O01 | deprecated | added v2.3.1, removed after v2.3.1
RDS_O13 | O13 | O13 | | added v2.4
RDY_K11 | K11 | K11 | deprecated | added v2.4, removed after v2.4
RDY_K15 | K15 | K15 | | added v2.4
REF_I12 | I12, I13, I14, I15 | I12, I13, I14, I15 | | added v2.3.1
RER_RER | RER | RER | Deprecated | added v2.3.1
RGR_RGR | RGR | RGR | Deprecated | added v2.3.1
RGV_O01 | O01 | O01 | deprecated | added v2.3.1, removed after v2.3.1
RGV_O15 | O15 | O15 | | added v2.4
ROR_ROR | ROR | ROR | Deprecated | added v2.3.1
RPA_I08 | I08, I09. I10, I11 | I08, I09. I10, I11 | | added v2.3.1
RPI_I01 | I01, I04 | I01, I04 | | added v2.4
RPI_I04 | I04 | I04 | | added v2.4
RPI_I0I | I01, I04 | I01, I04 | deprecated | added v2.3.1, removed after v2.3.1
RPL_I02 | I02 | I02 | | added v2.3.1
RPR_I03 | I03 | I03 | | added v2.3.1
RQA_I08 | I08, I09, I10, I11 | I08, I09, I10, I11 | | added v2.3.1
RQC_I05 | I05, I06 | I05, I06 | Deprecated | added v2.3.1
RQC_I06 | I06 | I06 | deprecated | added v2.3.1, removed after v2.3.1
RQI_I01 | I01, I02, I03, I07 | I01, I02, I03, I07 | | added v2.4
RQI_I0I | I01, I02, I03 | I01, I02, I03 | deprecated | added v2.3.1, removed after v2.3.1
RQP_I04 | I04 | I04 | | added v2.3.1
RQQ_Q09 | Q09 | Q09 | deprecated | added v2.3.1, removed after v2.5.1
RRA_O02 | O02 | O02 | deprecated | added v2.3.1, removed after v2.5
RRA_O18 | O18 | O18 | | added v2.4
RRD_O02 | O02 | O02 | deprecated | added v2.3.1, removed after v2.3.1
RRD_O14 | O14 | O14 | | added v2.4
RRE_O02 | O02 | O02 | deprecated | added v2.3.1, removed after v2.3.1
RRE_O12 | O12, O26 | O12, O26 | | added v2.4
RRG_O02 | O02 | O02 | deprecated | added v2.3.1, removed after v2.3.1
RRG_O16 | O16 | O16 | | added v2.4
RRI_I12 | I12, I13, I14, I15 | I12, I13, I14, I15 | | added v2.3.1
RRO_O02 | | | deprecated | added v2.3.1, removed after v2.3.1
RSP_E03 | E03 | E03 | | added v2.6
RSP_E22 | E22 | E22 | | added v2.6
RSP_K11 | K11 | K11 | | added v2.5
RSP_K21 | K21 | K21 | | added v2.4
RSP_K22 | K22 | K22 | | added v2.4
RSP_K23 | K23, K24 | K23, K24 | | added v2.4
RSP_K24 | K24 | K24 | deprecated | added v2.4, removed after v2.4
RSP_K25 | K25 | K25 | | added v2.4
RSP_K31 | K31 | K31 | | added v2.5.1
RSP_K32 | K32 | K32 | | added v2.7
RSP_O33 | O33 | O33 | | added v2.8
RSP_O34 | O34 | O34 | | added v2.8
RSP_Q11 | Q11 | Q11 | Deprecated | added v2.5.1
RSP_Z82 | Z82 | Z82 | deprecated | added v2.7, removed after v2.7
RSP_Z86 | Z86 | Z86 | deprecated | added v2.7, removed after v2.7
RSP_Z88 | Z88 | Z88 | deprecated | added v2.7, removed after v2.7
RSP_Z90 | Z90 | Z90 | deprecated | added v2.7, removed after v2.7
RTB_K13 | K13 | K13 | | added v2.4
RTB_Knn | Knn | Knn | deprecated | added v2.7, removed after v2.7
RTB_Z74 | Z74 | Z74 | deprecated | added v2.7, removed after v2.7
SDR_S31 | S31, S36 | S31, S36 | | added v2.6
SDR_S32 | S32, S37 | S32, S37 | | added v2.6
SIU_S12 | S12, S13, S14, S15, S16, S17, S18, S19, S20, S21, S22, S23, S24, S26 | S12, S13, S14, S15, S16, S17, S18, S19, S20, S21, S22, S23, S24, S26 | | added v2.3.1
SLR_S28 | S28, S29, S30, S34, S35 | S28, S29, S30, S34, S35 | | added v2.6
SPQ_Q08 | Q08 | Q08 | deprecated | added v2.3.1, removed after v2.5.1
SQM_S25 | S25 | S25 | Deprecated | added v2.3.1
SQR_S25 | S25 | S25 | Deprecated | added v2.3.1
SRM_S01 | S01, S02, S03, S04, S05, S06, S07, S08, S09, S10, S11 | S01, S02, S03, S04, S05, S06, S07, S08, S09, S10, S11 | | added v2.3.1
SRM_T12 | T12 | T12 | deprecated | added v2.3.1, removed after v2.3.1
SRR_S01 | S01, S02, S03, S04, S05, S06, S07, S08, S09, S10, S11 | S01, S02, S03, S04, S05, S06, S07, S08, S09, S10, S11 | | added v2.3.1
SRR_T12 | T12 | T12 | deprecated | added v2.3.1, removed after v2.3.1
SSR_U04 | U04 | U04 | | added v2.4
SSU_U03 | U03 | U03 | | added v2.4
STC_S33 | S33 | S33 | | added v2.6
SUR_P09 | P09 | P09 | Deprecated | added v2.3.1
TBR_R08 | R08 | R08 | deprecated | added v2.4, removed after v2.5.1
TBR_R09 | R09 | R09 | deprecated | added v2.3.1, removed after v2.5.1

TCU_U10 | U10, U11 | U10, U11 | | added v2.4
UDM_Q05 | Q05 | Q05 | | added v2.3.1
VQQ_Q07 | Q07 | Q07 | deprecated | added v2.3.1, removed after v2.5.1
VXQ_V01 | V01 | V01 | Deprecated | added v2.3.1
VXR_V03 | V03 | V03 | Deprecated | added v2.3.1
VXU_V04 | V04 | V04 | | added v2.3.1
VXX_V02 | V02 | V02 | Deprecated | added v2.3.1

4.2.13.355 HL7 Version 2 Table 0355

URL: https://hl7.org/fhir/STU3/v2/0355/index.html

This page is part of the FHIR Specification (v3.0.2: STU 3). The current version which supercedes this version is 4.0.1. For a full list of available versions, see the Directory of published versions

Vocabulary Work Group | Maturity Level: N/A | External | Use Context: Any

This is a table defined as part of HL7 v2 . Related FHIR content: v2 Primary Key Value Type.

Summary

Name: | v2 Primary Key Value Type
Definition: | FHIR Value set/code system definition for HL7 v2 table 0355 (Primary Key Value Type)
Code System URL: | http://hl7.org/fhir/v2/0355
Value Set URL: | http://hl7.org/fhir/ValueSet/v2-0355
OID: | ??
CodeSystem Resource | XML / JSON
ValueSet Resource | XML / JSON

This value set is used in the following places:

* This value set is the designated 'entire code system' value set for v2 Primary Key Value Type

4.2.13.355.1 Code System Content

Primary Key Value Type

Code | Description | Nederlands (Dutch) | Comment | Version
CE | Coded element | Gecodeerd element | Withdrawn as of v2.6 - CE has been replaced by CNE and CWE | added v2.3.1
CWE | Coded with Exceptions | Gecodeerd met uitzonderingen | | added v2.6
PL | Person location | Persoonslocatie | | added v2.3.1

4.2.13.356 HL7 Version 2 Table 0356

URL: https://hl7.org/fhir/STU3/v2/0356/index.html

This page is part of the FHIR Specification (v3.0.2: STU 3). The current version which supercedes this version is 4.0.1. For a full list of available versions, see the Directory of published versions

Vocabulary Work Group | Maturity Level: N/A | External | Use Context: Any

This is a table defined as part of HL7 v2 . Related FHIR content: v2 Alternate Character Set Handling Scheme.

Summary

Name: | v2 Alternate Character Set Handling Scheme
Definition: | FHIR Value set/code system definition for HL7 v2 table 0356 (Alternate Character Set Handling Scheme)
Code System URL: | http://hl7.org/fhir/v2/0356
Value Set URL: | http://hl7.org/fhir/ValueSet/v2-0356
OID: | ??
CodeSystem Resource | XML / JSON
ValueSet Resource | XML / JSON

This value set is used in the following places:

* This value set is the designated 'entire code system' value set for v2 Alternate Character Set Handling Scheme

4.2.13.356.1 Code System Content

Alternate Character Set Handling Scheme

Code | Description | Nederlands (Dutch) | Comment | Version
2.3 | The character set switching mode specified in HL7 2.5, section 2.7.2 and section 2.A.46, "XPN - extended person name". | De modus om te wisselen van tekenset gedefinieerd in HL7 2.5, sectie 2.A.46, "XPN - uitgebreide persoonsnaam". | Note that the escape sequences used in this mode do not use the ASCII "esc" character, as defined in ISO 2022-1994. They are "HL7 escape sequences" as first defined in HL7 2.3, sec. 2.9.2. (Also, note that sections 2.8.28.6.1and 2.9.2 in HL7 2.3 correspon | added v2.3.1
<null> | This is the default, indicating that there is no character set switching occurring in this message. | Dit is de standaardwaarde, om aan te geven dat er geen wisselingen van tekenset voorkomen in dit bericht. | This is the default. | added v2.3.1
ISO 2022-1994 | This standard is titled "Information Technology - Character Code Structure and Extension Technique". . | Deze standaard heet "Information Technology - Character Code Structure and Extension Technique". | This standard specifies an escape sequence from basic one byte character set to specified other character set, and vice versa. The escape sequence explicitly specifies what alternate character set to be evoked. Note that in this mode, the actual ASCII esc | added v2.3.1

4.2.13.357 HL7 Version 2 Table 0357

URL: https://hl7.org/fhir/STU3/v2/0357/index.html

This page is part of the FHIR Specification (v3.0.2: STU 3). The current version which supercedes this version is 4.0.1. For a full list of available versions, see the Directory of published versions

Vocabulary Work Group | Maturity Level: N/A | External | Use Context: Any

This is a table defined as part of HL7 v2 . Related FHIR content: v2 Message Error Condition Codes.

Summary

Name: | v2 Message Error Condition Codes
Definition: | FHIR Value set/code system definition for HL7 v2 table 0357 (Message Error Condition Codes)
Code System URL: | http://hl7.org/fhir/v2/0357
Value Set URL: | http://hl7.org/fhir/ValueSet/v2-0357
OID: | ??
CodeSystem Resource | XML / JSON
ValueSet Resource | XML / JSON

This value set is used in the following places:

* This value set is the designated 'entire code system' value set for v2 Message Error Condition Codes

4.2.13.357.1 Code System Content

Message Error Condition Codes

Code | Description | Deutsch (German) | Nederlands (Dutch) | Comment | Version
0 | Message accepted | Nachricht akzeptiert | Bericht geaccepteerd | Success. Optional, as the AA conveys success. Used for systems that must always return a status code. | added v2.3.1
100 | Segment sequence error | Fehler in der Segmentreihenfolge | Fout in segmentvolgorde | Error: The message segments were not in the proper order, or required segments are missing. | added v2.3.1
101 | Required field missing | erforderliches Feld leer | Verplicht veld ontbreekt | Error: A required field is missing from a segment | added v2.3.1
102 | Data type error | Datentypfehler | Fout in datatype | Error: The field contained data of the wrong data type, e.g. an NM field contained "FOO". | added v2.3.1
103 | Table value not found | fehlender Eintrag in der Tabelle | Tabelwaarde niet gevonden | Error: A field of data type ID or IS was compared against the corresponding table, and no match was found. | added v2.3.1
104 | Value too long | | Waarde te lang | Error: a value exceeded the normative length, or the length that the application is able to safely handle. | added v2.7
200 | Unsupported message type | Nachrichtentyp wird nicht unterstützt | Niet-ondersteund berichttype | Rejection: The Message Type is not supported. | added v2.3.1
201 | Unsupported event code | Ereignis wird nicht unterstützt | Niet-ondersteunde eventcode | Rejection: The Event Code is not supported. | added v2.3.1
202 | Unsupported processing id | Processing-ID wird nicht unterstützt | Niet-ondersteunde processing id | Rejection: The Processing ID is not supported. | added v2.3.1
203 | Unsupported version id | Version wird nicht unterstützt | Niet-ondersteunde versie | Rejection: The Version ID is not supported. | added v2.3.1
204 | Unknown key identifier | Schlüsselwert nicht gefunden | Onbekende sleutel-identificatie | Rejection: The ID of the patient, order, etc., was not found. Used for transactions other than additions, e.g. transfer of a non-existent patient. | added v2.3.1
205 | Duplicate key identifier | doppelter Schlüsselwert | Duplicaat sleutel-identificatie | Rejection: The ID of the patient, order, etc., already exists. Used in response to addition transactions (Admit, New Order, etc.). | added v2.3.1
206 | Application record locked | Datensatz durch Applikation gesperrt | Applicatie record vergrendeld | Rejection: The transaction could not be performed at the application storage level, e.g. database locked. | added v2.3.1
207 | Application internal error | applikationsinterner Fehler | Interne applicatiefout | Rejection: A catchall for internal errors not explicitly covered by other codes. | added v2.3.1

4.2.13.359 HL7 Version 2 Table 0359

URL: https://hl7.org/fhir/STU3/v2/0359/index.html

This page is part of the FHIR Specification (v3.0.2: STU 3). The current version which supercedes this version is 4.0.1. For a full list of available versions, see the Directory of published versions

Vocabulary Work Group | Maturity Level: N/A | External | Use Context: Any

This is a table defined as part of HL7 v2 . Related FHIR content: v2 Diagnosis Priority.

Summary

Name: | v2 Diagnosis Priority
Definition: | FHIR Value set/code system definition for HL7 v2 table 0359 (Diagnosis Priority)
Code System URL: | http://hl7.org/fhir/v2/0359
Value Set URL: | http://hl7.org/fhir/ValueSet/v2-0359
OID: | ??
CodeSystem Resource | XML / JSON
ValueSet Resource | XML / JSON

This value set is used in the following places:

* This value set is the designated 'entire code system' value set for v2 Diagnosis Priority

4.2.13.359.1 Code System Content

Diagnosis Priority

Code | Description | Nederlands (Dutch) | Comment | Version
... | | | | added v2.6
0 | Not included in diagnosis ranking | niet in diagnoseranglijst | | added v2.3.1
1 | The primary diagnosis | de primaire diagnose | | added v2.3.1
2 | For ranked secondary diagnosis | voor gerangschikte secundaire diagnoses | | added v2.6
2 ... | For ranked secondary diagnoses | voor gerangschikte secundaire diagnoses | deprecated | added v2.4, removed after v2.5.1
2 and higher | for ranked secondary diagnoses | voor gerangschikte secundaire diagnoses | deprecated | added v2.3.1, removed after v2.3.1

4.2.13.363 HL7 Version 2 Table 0363

URL: https://hl7.org/fhir/STU3/v2/0363/index.html

This page is part of the FHIR Specification (v3.0.2: STU 3). The current version which supercedes this version is 4.0.1. For a full list of available versions, see the Directory of published versions

Vocabulary Work Group | Maturity Level: N/A | External | Use Context: Any

This is a table defined as part of HL7 v2 . Related FHIR content: v2 Assigning Authority.

Summary

Name: | v2 Assigning Authority
Definition: | FHIR Value set/code system definition for HL7 v2 table 0363 (Assigning Authority)
Code System URL: | http://hl7.org/fhir/v2/0363
Value Set URL: | http://hl7.org/fhir/ValueSet/v2-0363
OID: | ??
CodeSystem Resource | XML / JSON
ValueSet Resource | XML / JSON

This value set is used in the following places:

* This value set is the designated 'entire code system' value set for v2 Assigning Authority

4.2.13.363.1 Code System Content

Assigning Authority

Code | Description | Deutsch (German) | Nederlands (Dutch) | Comment | Version
... | No suggested values defined | keine Werte vorgeschlagen | geen voorgestelde waarden | | added v2.5.1
AUSDVA | Australia - Dept. of Veterans Affairs | | | deprecated | added v2.4, removed after v2.4
AUSHIC | Australia - Health Insurance Commission | | | deprecated | added v2.4, removed after v2.4
CANAB | Canada - Alberta | | | deprecated | added v2.4, removed after v2.4
CANBC | Canada - British Columbia | | | deprecated | added v2.4, removed after v2.4
CANMB | Canada - Manitoba | | | deprecated | added v2.4, removed after v2.4
CANNB | Canada - New Brunswick | | | deprecated | added v2.4, removed after v2.4
CANNF | Canada - Newfoundland | | | deprecated | added v2.4, removed after v2.4
CANNS | Canada - Nova Scotia | | | deprecated | added v2.4, removed after v2.4
CANNT | Canada - Northwest Territories | | | deprecated | added v2.4, removed after v2.4
CANNU | Canada - Nanavut | | | deprecated | added v2.4, removed after v2.4
CANON | Canada - Ontario | | | deprecated | added v2.4, removed after v2.4
CANPE | Canada - Prince Edward Island | | | deprecated | added v2.4, removed after v2.4
CANQC | Canada - Quebec | | | deprecated | added v2.4, removed after v2.4
CANSK | Canada - Saskatchewan | | | deprecated | added v2.4, removed after v2.4
CANYT | Canada - Yukon Territories | | | deprecated | added v2.4, removed after v2.4
NLVWS | NL - Ministerie van Volksgezondheid, Welzijn en Sport | | NL - Ministerie van Volksgezondheid, Welzijn en Sport | deprecated | added v2.4, removed after v2.4
USCDC | US Center for Disease Control | | | deprecated | added v2.4, removed after v2.4
USHCFA | US Healthcare Finance Authority | | | deprecated | added v2.4, removed after v2.4
USSSA | US Social Security Administration | | | deprecated | added v2.4, removed after v2.4

4.2.13.364 HL7 Version 2 Table 0364

URL: https://hl7.org/fhir/STU3/v2/0364/index.html

This page is part of the FHIR Specification (v3.0.2: STU 3). The current version which supercedes this version is 4.0.1. For a full list of available versions, see the Directory of published versions

Vocabulary Work Group | Maturity Level: N/A | External | Use Context: Any

This is a table defined as part of HL7 v2 . Related FHIR content: v2 Comment Type.

Summary

Name: | v2 Comment Type
Definition: | FHIR Value set/code system definition for HL7 v2 table 0364 (Comment Type)
Code System URL: | http://hl7.org/fhir/v2/0364
Value Set URL: | http://hl7.org/fhir/ValueSet/v2-0364
OID: | ??
CodeSystem Resource | XML / JSON

ValueSet Resource | XML / JSON

This value set is used in the following places:

* This value set is the designated 'entire code system' value set for v2 Comment Type

4.2.13.364.1 Code System Content

Comment Type

Code | Description | Nederlands (Dutch) | Comment | Version
1R | Primary Reason | Primaire reden | | added v2.3.1
2R | Secondary Reason | Secundaire reden | | added v2.3.1
AI | Ancillary Instructions | Aanvullende instructies | | added v2.3.1
DR | Duplicate/Interaction Reason | Duplicaat/interactie reden | | added v2.3.1
GI | General Instructions | Algemene instructies | | added v2.3.1
GR | General Reason | Algemene reden | | added v2.3.1
PI | Patient Instructions | Patiëntinstructies | | added v2.3.1
RE | Remark | Opmerking | | added v2.3.1

4.2.13.365 HL7 Version 2 Table 0365

URL: https://hl7.org/fhir/STU3/v2/0365/index.html

This page is part of the FHIR Specification (v3.0.2: STU 3). The current version which supercedes this version is 4.0.1. For a full list of available versions, see the Directory of published versions

Vocabulary Work Group | Maturity Level: N/A | External | Use Context: Any

This is a table defined as part of HL7 v2 . Related FHIR content: v2 Equipment State.

Summary

Name: | v2 Equipment State
Definition: | FHIR Value set/code system definition for HL7 v2 table 0365 (Equipment State)
Code System URL: | http://hl7.org/fhir/v2/0365
Value Set URL: | http://hl7.org/fhir/ValueSet/v2-0365
OID: | ??
CodeSystem Resource | XML / JSON
ValueSet Resource | XML / JSON

This value set is used in the following places:

* This value set is the designated 'entire code system' value set for v2 Equipment State

4.2.13.365.1 Code System Content

Equipment State

Code | Description | Nederlands (Dutch) | Comment | Version
... | (null) No state change | (null) Geen statuswijziging | | added v2.6
CL | Clearing | Wissen | | added v2.4
CO | Configuring | Configureren | | added v2.4
DI | Diagnose | Diagnose | | added v2.8
ES | E-stopped | E-gestopt | | added v2.4
ID | Idle | Idle | | added v2.4
IN | Initializing | Initialiseren | | added v2.4
MA | Maintenance | Onderhoud | | added v2.8
OP | Normal Operation | Normaal in bedrijf | | added v2.4
PA | Pausing | Pauzeren | | added v2.4
PD | Paused | Gepauzeerd | | added v2.4
PU | Powered Up | Opgestart | | added v2.4
SD | Shutting down | Afsluiten | | added v2.8
SS | Sampling stopped | Sampling gestopt | | added v2.8
TS | Transport stopped | Transport gestopt | | added v2.8
… | (null) No state change | (null) Geen statuswijziging | deprecated | added v2.7.1, removed after v2.7.1

4.2.13.366 HL7 Version 2 Table 0366

URL: https://hl7.org/fhir/STU3/v2/0366/index.html

This page is part of the FHIR Specification (v3.0.2: STU 3). The current version which supercedes this version is 4.0.1. For a full list of available versions, see the Directory of published versions

Vocabulary Work Group | Maturity Level: N/A | External | Use Context: Any

This is a table defined as part of HL7 v2 . Related FHIR content: v2 Local/Remote Control State.

Summary

Name: | v2 Local/Remote Control State
Definition: | FHIR Value set/code system definition for HL7 v2 table 0366 (Local/Remote Control State)
Code System URL: | http://hl7.org/fhir/v2/0366

Value Set URL: | http://hl7.org/fhir/ValueSet/v2-0366
OID: | ??
CodeSystem Resource | XML / JSON
ValueSet Resource | XML / JSON

This value set is used in the following places:

* This value set is the designated 'entire code system' value set for v2 Local/Remote Control State

4.2.13.366.1 Code System Content

Local/Remote Control State

Code | Description | Nederlands (Dutch) | Comment | Version
... | (null) No state change | (null) geen statuswijziging | | added v2.6
L | Local | Lokaal | | added v2.4
R | Remote | Extern | | added v2.4
… | (null) No state change | (null) Geen statuswijziging | deprecated | added v2.7.1, removed after v2.7.1

4.2.13.367 HL7 Version 2 Table 0367

URL: https://hl7.org/fhir/STU3/v2/0367/index.html

This page is part of the FHIR Specification (v3.0.2: STU 3). The current version which supercedes this version is 4.0.1. For a full list of available versions, see the Directory of published versions

Vocabulary Work Group | Maturity Level: N/A | External | Use Context: Any

This is a table defined as part of HL7 v2 . Related FHIR content: v2 Alert Level.

Summary

Name: | v2 Alert Level
Definition: | FHIR Value set/code system definition for HL7 v2 table 0367 (Alert Level)
Code System URL: | http://hl7.org/fhir/v2/0367
Value Set URL: | http://hl7.org/fhir/ValueSet/v2-0367
OID: | ??
CodeSystem Resource | XML / JSON
ValueSet Resource | XML / JSON

This value set is used in the following places:

* This value set is the designated 'entire code system' value set for v2 Alert Level

4.2.13.367.1 Code System Content

Alert Level

Code | Description | Nederlands (Dutch) | Comment | Version
... | (null) No level change | (null) geen niveauwijziging | | added v2.6
C | Critical | Kritiek | Shut Down, Fix Problem and Re-init | added v2.4
N | Normal | Normaal | No Corrective Action Needed | added v2.4
S | Serious | Serieus | Corrective Action Required | added v2.4
W | Warning | Waarschuwing | Corrective Action Anticipated | added v2.4
… | (null) No level change | (null) Geen statuswijziging | deprecated | added v2.7.1, removed after v2.7.1

4.2.13.368 HL7 Version 2 Table 0368

URL: https://hl7.org/fhir/STU3/v2/0368/index.html

This page is part of the FHIR Specification (v3.0.2: STU 3). The current version which supercedes this version is 4.0.1. For a full list of available versions, see the Directory of published versions

Vocabulary Work Group | Maturity Level: N/A | External | Use Context: Any

This is a table defined as part of HL7 v2 . Related FHIR content: v2 Remote Control Command.

Summary

Name: | v2 Remote Control Command
Definition: | FHIR Value set/code system definition for HL7 v2 table 0368 (Remote Control Command)
Code System URL: | http://hl7.org/fhir/v2/0368
Value Set URL: | http://hl7.org/fhir/ValueSet/v2-0368
OID: | ??
CodeSystem Resource | XML / JSON
ValueSet Resource | XML / JSON

This value set is used in the following places:

* This value set is the designated 'entire code system' value set for v2 Remote Control Command

4.2.13.368.1 Code System Content

Remote Control Command

Code | Description | Nederlands (Dutch) | Comment | Version
AB | Abort | Afbreken | | added v2.4
AF | Aliquot From container | Aliquot uit container | See desc. below | added v2.8
AT | Aliquot To container | Aliquot naar container | See desc. below | added v2.8
CL | Clear | Wissen | | added v2.4
CN | Clear Notification | Wis melding | | added v2.4
DI | Disable Sending Events | Versturen event deactiveren | | added v2.4
EN | Enable Sending Events | Versturen events activeren | | added v2.4
ES | Emergency -stop | Noodstop | | added v2.4
EX | Execute (command specified in field Parameters (ST) 01394) | Uitvoeren (commando gespecificeerd in veld Parameters (ST) 01394) | | added v2.4
IN | Initialize/Initiate | Initialiseren/Starten | | added v2.4
LC | Local Control Request | Lokaal besturingsverzoek | | added v2.4
LK | Lock | Vergrendelen | | added v2.4
LO | Load | Laden | | added v2.4
PA | Pause | Pauzeren | | added v2.4
RC | Remote Control Request | Extern besturingsverzoek | | added v2.4
RE | Resume | Hervatten | | added v2.4
SA | Sampling | Sampelen | | added v2.4
SU | Setup | Instellingen | | added v2.4
TT | Transport To | Transport naar | | added v2.4
UC | Unlock | Ontgrendelen | | added v2.4
UN | Unload | Uitladen | | added v2.4

4.2.13.369 HL7 Version 2 Table 0369

URL: https://hl7.org/fhir/STU3/v2/0369/index.html

This page is part of the FHIR Specification (v3.0.2: STU 3). The current version which supercedes this version is 4.0.1. For a full list of available versions, see the Directory of published versions

Vocabulary Work Group | Maturity Level: N/A | External | Use Context: Any

This is a table defined as part of HL7 v2 . Related FHIR content: v2 Specimen Role.

Summary

Name: | v2 Specimen Role
Definition: | FHIR Value set/code system definition for HL7 v2 table 0369 (Specimen Role)
Code System URL: | http://hl7.org/fhir/v2/0369
Value Set URL: | http://hl7.org/fhir/ValueSet/v2-0369
OID: | ??
CodeSystem Resource | XML / JSON
ValueSet Resource | XML / JSON

This value set is used in the following places:

* This value set is the designated 'entire code system' value set for v2 Specimen Role

4.2.13.369.1 Code System Content

Specimen Role

Code | Description | Nederlands (Dutch) | Comment | Version
B | Blind Sample | Blind monster | | added v2.4
C | Calibrator, used for initial setting of calibration | Calibratie, gebruikt voor initiële calibratie | | added v2.4
E | Electronic QC, used with manufactured reference providing signals that simulate QC results | Electronische QC, gebruikt met fabrieksreferentie die signalen afgeeft die QC-resultaten stimuleren | | added v2.5
F | Specimen used for testing proficiency of the organization performing the testing (Filler) | Monster gebruikt voor testen van vakbekwaamheid van de organisatie die de testen uitvoert (Filler) | | added v2.5
G | Group (where a specimen consists of multiple individual elements that are not individually identified) | Groep (waarbij een monster bestaat uit meerdere individuele elementen die niet individueel worden geïdenticeerd) | | added v2.5
L | Pool (aliquots of individual specimens combined to form a single specimen representing all of the components.) | Pool (aliquots van individuele monsters gecombineerd tot een enkel monster dat alle componenten bevat.) | | added v2.5
O | Specimen used for testing Operator Proficiency | Monster gebruikt voor het testen van de vakbekwaamheid van de operator | | added v2.5
P | Patient (default if blank component value) | Patiënt (standaard indien component geen waarde heeft) | | added v2.4
Q | Control specimen | Control monster | | added v2.4
R | Replicate (of patient sample as a control) | Replicatie (van patiëntmonster ter controle) | | added v2.4
V | Verifying Calibrator, used for periodic calibration checks | Verificatie calibrator, gebruikt voor periodieke calibratietesten | | added v2.5

4.2.13.370 HL7 Version 2 Table 0370

URL: https://hl7.org/fhir/STU3/v2/0370/index.html

This page is part of the FHIR Specification (v3.0.2: STU 3). The current version which supercedes this version is 4.0.1. For a full list of available versions, see the Directory of published versions

Vocabulary Work Group | Maturity Level: N/A | External | Use Context: Any

This is a table defined as part of HL7 v2 . Related FHIR content: v2 Container Status.

Summary

Name: | v2 Container Status
Definition: | FHIR Value set/code system definition for HL7 v2 table 0370 (Container Status)
Code System URL: | http://hl7.org/fhir/v2/0370
Value Set URL: | http://hl7.org/fhir/ValueSet/v2-0370
OID: | ??
CodeSystem Resource | XML / JSON
ValueSet Resource | XML / JSON

This value set is used in the following places:

* This value set is the designated 'entire code system' value set for v2 Container Status

4.2.13.370.1 Code System Content

Container Status

Code | Description | Nederlands (Dutch) | Comment | Version
I | Identified | Geïdentificeerd | | added v2.4
L | Left Equipment | Apparatuur verlaten | | added v2.4
M | Missing | Ontbreekt | | added v2.4
O | In Process | In behandeling | | added v2.4
P | In Position | Op zijn plaats | | added v2.4
R | Process Completed | Prcoes voltooid | | added v2.4
U | Unknown | Onbekend | | added v2.4
X | Container Unavailable | Container niet beschikbaar | | added v2.4

4.2.13.371 HL7 Version 2 Table 0371

URL: https://hl7.org/fhir/STU3/v2/0371/index.html

This page is part of the FHIR Specification (v3.0.2: STU 3). The current version which supercedes this version is 4.0.1. For a full list of available versions, see the Directory of published versions

Vocabulary Work Group | Maturity Level: N/A | External | Use Context: Any

This is a table defined as part of HL7 v2 . Related FHIR content: v2 Additive/Preservative.

Summary

Name: | v2 Additive/Preservative
Definition: | FHIR Value set/code system definition for HL7 v2 table 0371 (Additive/Preservative)
Code System URL: | http://hl7.org/fhir/v2/0371
Value Set URL: | http://hl7.org/fhir/ValueSet/v2-0371
OID: | ??
CodeSystem Resource | XML / JSON
ValueSet Resource | XML / JSON

This value set is used in the following places:

* This value set is the designated 'entire code system' value set for v2 Additive/Preservative

* Specimen.container.additive[x] (Example)

4.2.13.371.1 Code System Content

Additive/Preservative

Code | Description | Nederlands (Dutch) | Comment | Version
ACDA | ACD Solution A | | Yellow top tube | added v2.5
ACDB | ACD Solution B | | Yellow top tube | added v2.5
ACET | Acetic Acid | | Urine preservative | added v2.5
AMIES | Amies transport medium | | Protozoa | added v2.5
BACTM | Bacterial Transport medium | | Microbiological culture | added v2.5
BF10 | Buffered 10% formalin | | Tissue | added v2.5
BOR | Borate Boric Acid | | 24HR Urine Additive | added v2.4
BOUIN | Bouin's solution | | Tissue | added v2.5
BSKM | Buffered skim milk | | Viral isolation | added v2.5
C32 | 3.2% Citrate | 3,2% Citraat | Blue top tube | added v2.4
C38 | 3.8% Citrate | 3,8% Citraat | Blue top tube | added v2.4
CARS | Carson's Modified 10% formalin | | Tissue | added v2.5
CARY | Cary Blair Medium | | Stool Cultures | added v2.5
CHLTM | Chlamydia transport medium | | Chlamydia culture | added v2.5
CTAD | CTAD (this should be spelled out if not universally understood) | | Blue top tube | added v2.5
EDTK | Potassium/K EDTA | | Deprecated. Replaced by EDTK15 and EDTK75 | added v2.4
EDTK15 | Potassium/K EDTA 15% | | Purple top tube | added v2.5
EDTK75 | Potassium/K EDTA 7.5% | | Purple top tube | added v2.5
EDTN | Sodium/Na EDTA | | Dark Blue top tube | added v2.4
ENT | Enteric bacteria transport medium | | Bacterial culture | added v2.5
ENT+ | Enteric plus | | Stool Cultures | added v2.5

F10 | 10% Formalin | | Tissue preservative | added v2.5
FDP | Thrombin NIH; soybean trypsin inhibitor (Fibrin Degradation Products) | | Dark Blue top tube | added v2.5
FL10 | Sodium Fluoride, 10mg | | Urine | added v2.5
FL100 | Sodium Fluoride, 100mg | | Urine | added v2.5
HCL6 | 6N HCL | | 24 HR Urine Additive | added v2.4
HEPA | Ammonium heparin | | Green top tube | added v2.5
HEPL | Lithium/Li Heparin | | Green top tube | added v2.4
HEPN | Sodium/Na Heparin | | Green top tube | added v2.4
HNO3 | Nitric Acid | | Urine | added v2.5
JKM | Jones Kendrick Medium | | Bordetella pertussis | added v2.5
KARN | Karnovsky's fixative | | Tissue | added v2.5
KOX | Potassium Oxalate | | Gray top tube | added v2.5
LIA | Lithium iodoacetate | | Gray top tube | added v2.5
M4 | M4 | | Microbiological culture | added v2.5
M4RT | M4-RT | | Microbiological culture | added v2.5
M5 | M5 | | Microbiological culture | added v2.5
MICHTM | Michel's transport medium | | IF tests | added v2.5
MMDTM | MMD transport medium | | Immunofluorescence | added v2.5
NAF | Sodium Fluoride | | Gray top tube | added v2.5
NAPS | Sodium polyanethol sulfonate 0.35% in 0.85% sodium chloride | | Yellow (Blood Culture) | added v2.5
NONE | None | | Red or Pink top tube | added v2.5
PAGE | Pages's Saline | | Acanthaoemba | added v2.5
PHENOL | Phenol | | 24 Hr Urine Additive | added v2.5
PVA | PVA (polyvinylalcohol) | | O&P | added v2.5
RLM | Reagan Lowe Medium | | Bordetella pertussis cultures | added v2.5
SILICA | Siliceous earth, 12 mg | | Gray top tube | added v2.5
SPS | SPS(this should be spelled out if not universally understood) | | Anticoagulant w/o bacteriocidal properties | added v2.5
SST | Serum Separator Tube (Polymer Gel) | | 'Tiger' Top tube | added v2.5
STUTM | Stuart transport medium | | Bacterial culture | added v2.5
THROM | Thrombin | | Orange or Grey/Yellow (STAT Chem) | added v2.5
THYMOL | Thymol | | 24 Hr Urine Additive | added v2.5
THYO | Thyoglycollate broth | | Bacterial Isolation | added v2.5
TOLU | Toluene | | 24 Hr Urine Additive | added v2.5
URETM | Ureaplasma transport medium | | Ureaplasma culture | added v2.5
VIRTM | Viral Transport medium | | Virus cultures | added v2.5
WEST | Buffered Citrate (Westergren Sedimentation Rate) | | Black top tube | added v2.5

4.2.13.372 HL7 Version 2 Table 0372

URL: https://hl7.org/fhir/STU3/v2/0372/index.html

This page is part of the FHIR Specification (v3.0.2: STU 3). The current version which supercedes this version is 4.0.1. For a full list of available versions, see the Directory of published versions

Vocabulary Work Group | Maturity Level: N/A | External | Use Context: Any

This is a table defined as part of HL7 v2 . Related FHIR content: v2 Specimen Component.

Summary

Name: | v2 Specimen Component
Definition: | FHIR Value set/code system definition for HL7 v2 table 0372 (Specimen Component)
Code System URL: | http://hl7.org/fhir/v2/0372
Value Set URL: | http://hl7.org/fhir/ValueSet/v2-0372
OID: | ??
CodeSystem Resource | XML / JSON
ValueSet Resource | XML / JSON

This value set is used in the following places:

* This value set is the designated 'entire code system' value set for v2 Specimen Component

4.2.13.372.1 Code System Content

Specimen Component

Code | Description | Comment | Version
BLD | Whole blood, homogeneous | | added v2.4
BSEP | Whole blood, separated | | added v2.4
PLAS | Plasma, NOS (not otherwise specified) | | added v2.4
PPP | Platelet poor plasma | | added v2.4
PRP | Platelet rich plasma | | added v2.4
SED | Sediment | | added v2.4
SER | Serum, NOS (not otherwise specified) | | added v2.4
SUP | Supernatant | | added v2.4

4.2.13.373 HL7 Version 2 Table 0373

URL: https://hl7.org/fhir/STU3/v2/0373/index.html

This page is part of the FHIR Specification (v3.0.2: STU 3). The current version which supercedes this version is 4.0.1. For a full list of available versions, see the Directory of published versions

Vocabulary Work Group | Maturity Level: N/A | External | Use Context: Any

This is a table defined as part of HL7 v2 . Related FHIR content: v2 Treatment.

Summary

Name: | v2 Treatment
Definition: | FHIR Value set/code system definition for HL7 v2 table 0373 (Treatment)
Code System URL: | http://hl7.org/fhir/v2/0373
Value Set URL: | http://hl7.org/fhir/ValueSet/v2-0373
OID: | ??
CodeSystem Resource | XML / JSON
ValueSet Resource | XML / JSON

This value set is used in the following places:

* This value set is the designated 'entire code system' value set for v2 Treatment

4.2.13.373.1 Code System Content

Treatment

Code | Description | Comment | Version
ACID | Acidification | | added v2.4
ALK | Alkalization | | added v2.4
DEFB | Defibrination | | added v2.4
FILT | Filtration | | added v2.4
LDLP | LDL Precipitation | | added v2.4
NEUT | Neutralization | | added v2.4
RECA | Recalification | | added v2.4
UFIL | Ultrafiltration | | added v2.4

4.2.13.374 HL7 Version 2 Table 0374

URL: https://hl7.org/fhir/STU3/v2/0374/index.html

This page is part of the FHIR Specification (v3.0.2: STU 3). The current version which supercedes this version is 4.0.1. For a full list of available versions, see the Directory of published versions

Vocabulary Work Group | Maturity Level: N/A | External | Use Context: Any

This is a table defined as part of HL7 v2 . Related FHIR content: v2 System Induced Contaminants.

Summary

Name: | v2 System Induced Contaminants
Definition: | FHIR Value set/code system definition for HL7 v2 table 0374 (System Induced Contaminants)
Code System URL: | http://hl7.org/fhir/v2/0374
Value Set URL: | http://hl7.org/fhir/ValueSet/v2-0374
OID: | ??
CodeSystem Resource | XML / JSON
ValueSet Resource | XML / JSON

This value set is used in the following places:

* This value set is the designated 'entire code system' value set for v2 System Induced Contaminants

4.2.13.374.1 Code System Content

System Induced Contaminants

Code | Description | Nederlands (Dutch) | Comment | Version
CNTM | Present, type of contamination unspecified | Aanwezig, type contaminatie niet-gedefinieerd | | added v2.4

4.2.13.375 HL7 Version 2 Table 0375

URL: https://hl7.org/fhir/STU3/v2/0375/index.html

This page is part of the FHIR Specification (v3.0.2: STU 3). The current version which supercedes this version is 4.0.1. For a full list of available versions, see the Directory of published versions

Vocabulary Work Group | Maturity Level: N/A | External | Use Context: Any

This is a table defined as part of HL7 v2 . Related FHIR content: v2 Artificial Blood.

Summary

Name: | v2 Artificial Blood
Definition: | FHIR Value set/code system definition for HL7 v2 table 0375 (Artificial Blood)
Code System URL: | http://hl7.org/fhir/v2/0375
Value Set URL: | http://hl7.org/fhir/ValueSet/v2-0375

OID: | ??
CodeSystem Resource | XML / JSON
ValueSet Resource | XML / JSON

This value set is used in the following places:

* This value set is the designated 'entire code system' value set for v2 Artificial Blood

4.2.13.375.1 Code System Content

Artificial Blood

Code | Description | Comment | Version
FLUR | Fluorocarbons | | added v2.4
SFHB | Stromal free hemoglobin preparations | | added v2.4

4.2.13.376 HL7 Version 2 Table 0376

URL: https://hl7.org/fhir/STU3/v2/0376/index.html

This page is part of the FHIR Specification (v3.0.2: STU 3). The current version which supercedes this version is 4.0.1. For a full list of available versions, see the Directory of published versions

Vocabulary Work Group | Maturity Level: N/A | External | Use Context: Any

This is a table defined as part of HL7 v2 . Related FHIR content: v2 Special Handling Code.

Summary

Name: | v2 Special Handling Code
Definition: | FHIR Value set/code system definition for HL7 v2 table 0376 (Special Handling Code)
Code System URL: | http://hl7.org/fhir/v2/0376
Value Set URL: | http://hl7.org/fhir/ValueSet/v2-0376
OID: | ??
CodeSystem Resource | XML / JSON
ValueSet Resource | XML / JSON

This value set is used in the following places:

* This value set is the designated 'entire code system' value set for v2 Special Handling Code

4.2.13.376.1 Code System Content

Special Handling Code

Code | Description | Comment | Version
AMB | Ambient temperature | Keep at ambient (room) temperature, approximately 22 (2 degrees C. Accidental refrigeration or freezing is of little consequence | added v2.5
C37 | Body temperature | Critical to keep at body temperature: 36 - 38(C. | added v2.4
CAMB | Critical ambient temperature | Critical ambient - must not be refrigerated or frozen. | added v2.4
CATM | Protect from air | Critical. Do not expose to atmosphere. Do not uncap. | added v2.4
CFRZ | Critical frozen temperature | Critical frozen - must not be allowed to thaw until immediately prior to testing | added v2.4
CREF | Critical refrigerated temperature | Critical refrigerated - must not be allowed to freeze or warm until immediately prior to testing | added v2.4
DFRZ | Deep frozen | Deep frozen: -16 to -20(C. | added v2.5
DRY | Dry | Keep in a dry environment. | added v2.5
FRZ | Frozen temperature | Keep at frozen temperature: -4(C. Accidental thawing is of little consequence | added v2.5
MTLF | Metal Free | Container is free of heavy metals including lead. | added v2.5
NTR | Liquid nitrogen | Keep in liquid nitrogen. | added v2.5
PRTL | Protect from light | Protect from light (e.g. wrap in aluminum foil). | added v2.4
PSA | Do not shake | Do not shake. | added v2.5
PSO | No shock | Protect from shock. | added v2.5
REF | Refrigerated temperature | Keep at refrigerated temperature: 4-8(C. Accidental warming or freezing is of little consequence | added v2.5
UFRZ | Ultra frozen | Ultra cold frozen: ~ -75 to -85(C. (ultra cold freezer is typically at temperature of dry ice). | added v2.5
UPR | Upright | Keep upright. Do not turn upside down. | added v2.5

4.2.13.377 HL7 Version 2 Table 0377

URL: https://hl7.org/fhir/STU3/v2/0377/index.html

This page is part of the FHIR Specification (v3.0.2: STU 3). The current version which supercedes this version is 4.0.1. For a full list of available versions, see the Directory of published versions

Vocabulary Work Group | Maturity Level: N/A | External | Use Context: Any

This is a table defined as part of HL7 v2 . Related FHIR content: v2 Other Environmental Factors.

Summary

Name: | v2 Other Environmental Factors
Definition: | FHIR Value set/code system definition for HL7 v2 table 0377 (Other Environmental Factors)
Code System URL: | http://hl7.org/fhir/v2/0377
Value Set URL: | http://hl7.org/fhir/ValueSet/v2-0377
OID: | ??

CodeSystem Resource | XML / JSON
ValueSet Resource | XML / JSON

This value set is used in the following places:

* This value set is the designated 'entire code system' value set for v2 Other Environmental Factors

4.2.13.377.1 Code System Content

Other Environmental Factors

Code	Description	Comment	Version
A60	Opened container, indoor atmosphere, 60 minutes duration		added v2.4
ATM	Opened container, atmosphere and duration unspecified		added v2.4

4.2.13.383 HL7 Version 2 Table 0383

URL: https://hl7.org/fhir/STU3/v2/0383/index.html

This page is part of the FHIR Specification (v3.0.2: STU 3). The current version which supercedes this version is 4.0.1. For a full list of available versions, see the Directory of published versions

Vocabulary Work Group | Maturity Level: N/A | External | Use Context: Any

This is a table defined as part of HL7 v2 . Related FHIR content: v2 Substance Status.

Summary

Name: | v2 Substance Status
Definition: | FHIR Value set/code system definition for HL7 v2 table 0383 (Substance Status)
Code System URL: | http://hl7.org/fhir/v2/0383
Value Set URL: | http://hl7.org/fhir/ValueSet/v2-0383
OID: | ??
CodeSystem Resource | XML / JSON
ValueSet Resource | XML / JSON

This value set is used in the following places:

* This value set is the designated 'entire code system' value set for v2 Substance Status

4.2.13.383.1 Code System Content

Substance Status

Code	Description	Nederlands (Dutch)	Comment	Version
CE	Calibration Error	Calibratie fout		added v2.4
CW	Calibration Warning	Calibratie waarschuwing		added v2.4
EE	Expired Error	Verlopen fout		added v2.4
EW	Expired Warning	Verlopen waarschuwing		added v2.4
NE	Not Available Error	Niet beschikbaar fout		added v2.4
NW	Not Available Warning	Niet beschikbaar waarschuwing		added v2.4
OE	Other Error	Andere fout		added v2.4
OK	OK Status	Status OK		added v2.4
OW	Other Warning	Andere waarschuwing		added v2.4
QE	QC Error	QC fout		added v2.4
QW	QC Warning	QC waarschuwing		added v2.4

4.2.13.384 HL7 Version 2 Table 0384

URL: https://hl7.org/fhir/STU3/v2/0384/index.html

This page is part of the FHIR Specification (v3.0.2: STU 3). The current version which supercedes this version is 4.0.1. For a full list of available versions, see the Directory of published versions

Vocabulary Work Group | Maturity Level: N/A | External | Use Context: Any

This is a table defined as part of HL7 v2 . Related FHIR content: v2 Substance Type.

Summary

Name: | v2 Substance Type
Definition: | FHIR Value set/code system definition for HL7 v2 table 0384 (Substance Type)
Code System URL: | http://hl7.org/fhir/v2/0384
Value Set URL: | http://hl7.org/fhir/ValueSet/v2-0384
OID: | ??
CodeSystem Resource | XML / JSON
ValueSet Resource | XML / JSON

This value set is used in the following places:

* This value set is the designated 'entire code system' value set for v2 Substance Type

4.2.13.384.1 Code System Content

Substance Type

Code | Description | Nederlands (Dutch) | Comment | Version
CO | Control | | | added v2.4
DI | Diluent | | | added v2.4
LI | Measurable Liquid Item | | | added v2.4
LW | Liquid Waste | | | added v2.4
MR | Multiple Test Reagent | | The consumption cannot be tied to orders for a single test | added v2.4
OT | Other | Anders | | added v2.4
PT | Pretreatment | | | added v2.4
PW | Purified Water | | | added v2.4
RC | Reagent Calibrator | | | added v2.4
SC | Countable Solid Item | | E.g. Pipetting tip | added v2.4
SR | Single Test Reagent | | | added v2.4
SW | Solid Waste | | | added v2.4

4.2.13.387 HL7 Version 2 Table 0387

URL: https://hl7.org/fhir/STU3/v2/0387/index.html

This page is part of the FHIR Specification (v3.0.2: STU 3). The current version which supercedes this version is 4.0.1. For a full list of available versions, see the Directory of published versions

Vocabulary Work Group | Maturity Level: N/A | External | Use Context: Any

This is a table defined as part of HL7 v2 . Related FHIR content: v2 Command Response.

Summary

Name: | v2 Command Response
Definition: | FHIR Value set/code system definition for HL7 v2 table 0387 (Command Response)
Code System URL: | http://hl7.org/fhir/v2/0387
Value Set URL: | http://hl7.org/fhir/ValueSet/v2-0387
OID: | ??
CodeSystem Resource | XML / JSON
ValueSet Resource | XML / JSON

This value set is used in the following places:

* This value set is the designated 'entire code system' value set for v2 Command Response

4.2.13.387.1 Code System Content

Command Response

Code | Description | Nederlands (Dutch) | Comment | Version
ER | Command cannot be completed because of error condition | Commando kan niet worden uitgevoerd vanwege een foutconditie | See response parameters. | added v2.4
OK | Command completed successfully | Commando succesvol uitgevoerd | | added v2.4
ST | Command cannot be completed because of the status of the requested equipment | Commando kan niet worden uitgevoerd vanwege de status van de gevraagde apparatuur | | added v2.4
TI | Command cannot be completed within requested completion time | Commando kan niet worden uitgevoerd binnen de gevraagde tijd voor voltooiing | | added v2.4
UN | Command cannot be completed for unknown reasons | Commando kan om onbekende redenen niet worden uitgevoerd | | added v2.4

4.2.13.388 HL7 Version 2 Table 0388

URL: https://hl7.org/fhir/STU3/v2/0388/index.html

This page is part of the FHIR Specification (v3.0.2: STU 3). The current version which supercedes this version is 4.0.1. For a full list of available versions, see the Directory of published versions

Vocabulary Work Group | Maturity Level: N/A | External | Use Context: Any

This is a table defined as part of HL7 v2 . Related FHIR content: v2 Processing Type.

Summary

Name: | v2 Processing Type
Definition: | FHIR Value set/code system definition for HL7 v2 table 0388 (Processing Type)
Code System URL: | http://hl7.org/fhir/v2/0388
Value Set URL: | http://hl7.org/fhir/ValueSet/v2-0388
OID: | ??
CodeSystem Resource | XML / JSON
ValueSet Resource | XML / JSON

This value set is used in the following places:

* This value set is the designated 'entire code system' value set for v2 Processing Type

4.2.13.388.1 Code System Content

Processing Type

Code | Description | Nederlands (Dutch) | Comment | Version

E | Evaluation | Evaluatie | | added v2.4
P | Regular Production | Reguliere productie | | added v2.4

4.2.13.389 HL7 Version 2 Table 0389

URL: https://hl7.org/fhir/STU3/v2/0389/index.html

This page is part of the FHIR Specification (v3.0.2: STU 3). The current version which supercedes this version is 4.0.1. For a full list of available versions, see the Directory of published versions

Vocabulary Work Group | Maturity Level: N/A | External | Use Context: Any

This is a table defined as part of HL7 v2 . Related FHIR content: v2 Analyte Repeat Status.

Summary

Name: | v2 Analyte Repeat Status
Definition: | FHIR Value set/code system definition for HL7 v2 table 0389 (Analyte Repeat Status)
Code System URL: | http://hl7.org/fhir/v2/0389
Value Set URL: | http://hl7.org/fhir/ValueSet/v2-0389
OID: | ??
CodeSystem Resource | XML / JSON
ValueSet Resource | XML / JSON

This value set is used in the following places:

* This value set is the designated 'entire code system' value set for v2 Analyte Repeat Status

4.2.13.389.1 Code System Content

Analyte Repeat Status

Code | Description | Comment | Version
D | Repeated with dilution | | added v2.4
F | Reflex test | | added v2.4
O | Original, first run | | added v2.4
R | Repeated without dilution | | added v2.4

4.2.13.392 HL7 Version 2 Table 0392

URL: https://hl7.org/fhir/STU3/v2/0392/index.html

This page is part of the FHIR Specification (v3.0.2: STU 3). The current version which supercedes this version is 4.0.1. For a full list of available versions, see the Directory of published versions

Vocabulary Work Group | Maturity Level: N/A | External | Use Context: Any

This is a table defined as part of HL7 v2 . Related FHIR content: v2 Match Reason.

Summary

Name: | v2 Match Reason
Definition: | FHIR Value set/code system definition for HL7 v2 table 0392 (Match Reason)
Code System URL: | http://hl7.org/fhir/v2/0392
Value Set URL: | http://hl7.org/fhir/ValueSet/v2-0392
OID: | ??
CodeSystem Resource | XML / JSON
ValueSet Resource | XML / JSON

This value set is used in the following places:

* This value set is the designated 'entire code system' value set for v2 Match Reason

4.2.13.392.1 Code System Content

Match Reason

Code | Description | Nederlands (Dutch) | Comment | Version
DB | Match on Date of Birth | Match op geboortedatum | | added v2.4
NA | Match on Name (Alpha Match) | Match op naam (alfabetisch) | | added v2.4
NP | Match on Name (Phonetic Match) | Match op naam (fonetisch) | | added v2.4
SS | Match on Social Security Number | Match op SOFI-nummer | | added v2.4

4.2.13.393 HL7 Version 2 Table 0393

URL: https://hl7.org/fhir/STU3/v2/0393/index.html

This page is part of the FHIR Specification (v3.0.2: STU 3). The current version which supercedes this version is 4.0.1. For a full list of available versions, see the Directory of published versions

Vocabulary Work Group | Maturity Level: N/A | External | Use Context: Any

This is a table defined as part of HL7 v2 . Related FHIR content: v2 Match Algorithms.

Summary

Name: | v2 Match Algorithms
Definition: | FHIR Value set/code system definition for HL7 v2 table 0393 (Match Algorithms)
Code System URL: | http://hl7.org/fhir/v2/0393
Value Set URL: | http://hl7.org/fhir/ValueSet/v2-0393
OID: | ??
CodeSystem Resource | XML / JSON
ValueSet Resource | XML / JSON

This value set is used in the following places:

* This value set is the designated 'entire code system' value set for v2 Match Algorithms

4.2.13.393.1 Code System Content

Match Algorithms

Code | Description | Nederlands (Dutch) | Comment | Version
LINKSOFT_2.01 | Proprietary algorithm for LinkSoft v2.01 | Propriëtair algoritme voor LinkSoft v2.01 | | added v2.4
MATCHWARE_1.2 | Proprietary algorithm for MatchWare v1.2 | Propriëtair algoritme voor MatchWare v1.2 | | added v2.4

4.2.13.394 HL7 Version 2 Table 0394

URL: https://hl7.org/fhir/STU3/v2/0394/index.html

This page is part of the FHIR Specification (v3.0.2: STU 3). The current version which supercedes this version is 4.0.1. For a full list of available versions, see the Directory of published versions

Vocabulary Work Group | Maturity Level: N/A | External | Use Context: Any

This is a table defined as part of HL7 v2 . Related FHIR content: v2 Response Modality.

Summary

Name: | v2 Response Modality
Definition: | FHIR Value set/code system definition for HL7 v2 table 0394 (Response Modality)
Code System URL: | http://hl7.org/fhir/v2/0394
Value Set URL: | http://hl7.org/fhir/ValueSet/v2-0394
OID: | ??
CodeSystem Resource | XML / JSON
ValueSet Resource | XML / JSON

This value set is used in the following places:

* This value set is the designated 'entire code system' value set for v2 Response Modality

4.2.13.394.1 Code System Content

Response Modality

Code | Description | Nederlands (Dutch) | Comment | Version
B | Batch | Batch/bundel | | added v2.4
R | Real Time | Real time | | added v2.4
T | Bolus (a series of responses sent at the same time without use of batch formatting) | Bolus (een serie antwoorden tegelijk verzonden zonder gebruik te maken van een batch/bundel) | | added v2.4

4.2.13.395 HL7 Version 2 Table 0395

URL: https://hl7.org/fhir/STU3/v2/0395/index.html

This page is part of the FHIR Specification (v3.0.2: STU 3). The current version which supercedes this version is 4.0.1. For a full list of available versions, see the Directory of published versions

Vocabulary Work Group | Maturity Level: N/A | External | Use Context: Any

This is a table defined as part of HL7 v2 . Related FHIR content: v2 Modify Indicator.

Summary

Name: | v2 Modify Indicator
Definition: | FHIR Value set/code system definition for HL7 v2 table 0395 (Modify Indicator)
Code System URL: | http://hl7.org/fhir/v2/0395
Value Set URL: | http://hl7.org/fhir/ValueSet/v2-0395
OID: | ??
CodeSystem Resource | XML / JSON
ValueSet Resource | XML / JSON

This value set is used in the following places:

* This value set is the designated 'entire code system' value set for v2 Modify Indicator

4.2.13.395.1 Code System Content

Modify Indicator

Code | Description | Nederlands (Dutch) | Comment | Version

M | Modified Subscription | Gewijzigd abonnement | | added v2.4
N | New Subscription | Nieuw abonnement | | added v2.4

4.2.13.396 HL7 Version 2 Table 0396

URL: https://hl7.org/fhir/STU3/v2/0396/index.html

This page is part of the FHIR Specification (v3.0.2: STU 3). The current version which supercedes this version is 4.0.1. For a full list of available versions, see the Directory of published versions

Vocabulary Work Group | Maturity Level: N/A | External | Use Context: Any

This is a table defined as part of HL7 v2 . Related FHIR content: v2 Coding System.

Summary

Name: | v2 Coding System
Definition: | FHIR Value set/code system definition for HL7 v2 table 0396 (Coding System)
Code System URL: | http://hl7.org/fhir/v2/0396
Value Set URL: | http://hl7.org/fhir/ValueSet/v2-0396
OID: | ??
CodeSystem Resource | XML / JSON
ValueSet Resource | XML / JSON

This value set is used in the following places:

* This value set is the designated 'entire code system' value set for v2 Coding System

4.2.13.396.1 Code System Content

Coding System

Code | Description | Nederlands (Dutch) | Comment | Version
99zzz | Local general code where z is an alphanumeric character | Lokale algemene code waarbij z een alfanumeriek teken is | Locally defined codes for purpose of sender or receiver - 99zzz (where z is an alphanumeric character). | added v2.7
99zzz or L | Local general code (where z is an alphanumeric character) | Lokale algemene code (waarbij z een alfanumeriek teken is) | General code | added v2.4, removed after v2.6
ACR | American College of Radiology finding codes | American College of Radiology bevindingen codes | Index for Radiological Diagnosis Revised, 3rd Edition 1986, American College of Radiology, Reston, VA. | added v2.4
ALPHAID2006 | German Alpha-ID v2006 | Duitse Alpha-ID v2006 | ID of the alphabetical Index ICD-10-GM-2006. Alpha-ID. | added v2.6
ALPHAID2007 | German Alpha-ID v2007 | Duitse Alpha-ID v2007 | ID of the alphabetical Index ICD-10-GM-2007. Alpha-ID. | added v2.6
ALPHAID2008 | German Alpha-ID v2008 | Duitse Alpha-ID v2008 | ID of the alphabetical Index ICD-10-GM-2008. Alpha-ID. | added v2.6
ALPHAID2009 | German Alpha-ID v2009 | Duitse Alpha-ID v2009 | ID of the alphabetical Index ICD-10-GM-2009. Alpha-ID. | added v2.7
ALPHAID2010 | German Alpha-ID v2010 | Duitse Alpha-ID v2010 | ID of the alphabetical Index ICD-10-GM-2010. Alpha-ID. | added v2.7
ALPHAID2011 | German Alpha-ID v2011 | Duitse Alpha-ID v2011 | ID of the alphabetical Index ICD-10-GM-2011. Alpha-ID. | added v2.7
ANS+ | HL7 set of units of measure | HL7 set van meeteenheden | HL7 set of units of measure based upon ANSI X3.50 - 1986, ISO 2988-83, and US customary units / see chapter 7, section 7.4.2.6. | added v2.5
ART | WHO Adverse Reaction Terms | WHO Allergische reactie termen | WHO Collaborating Centre for International Drug Monitoring, Box 26, S-751 03, Uppsala, Sweden. | added v2.4
AS4 | ASTM E1238/ E1467 Universal | ASTM E1238/ E1467 Universal | American Society for Testing & Materials and CPT4 (see Appendix X1 of Specification E1238 and Appendix X2 of Specification E1467). | added v2.4
AS4E | AS4 Neurophysiology Codes | AS4 Neurophysiology Codes | ASTM's diagnostic codes and test result coding/grading systems for clinical neurophysiology. See ASTM Specification E1467, Appendix 2. | added v2.4
ATC | American Type Culture Collection | American Type Culture Collection | Reference cultures (microorganisms, tissue cultures, etc.), related biological materials and associated data. American Type Culture Collection, 12301 Parklawn Dr, Rockville MD, 20852. (301) 881-2600. http://www.atcc.org | added v2.4
C4 | CPT-4 | CPT-4 | American Medical Association, P.O. Box 10946, Chicago IL 60610. | added v2.4
C5 | CPT-5 | CPT-5 | Specific Non-Drug Code | added v2.4, removed after v2.6
CAPECC | College of American Pathologists Electronic Cancer Checklist | | Each code in this system represents a single line in a database template for the College of American Pathologists Electronic Cancer Checklist (CAP eCC). Each line and its code corresponds to either a question or an answer selection. The code is in a dec | added v2.7
CAS | Chemical abstract codes | Chemical abstract codes | These include unique codes for each unique chemical, including all generic drugs. The codes do not distinguish among different dosing forms. When multiple equivalent CAS numbers exist, use the first one listed in USAN. USAN 1990 and the USP dictionary of | added v2.4
CCC | Clinical Care Classification system | | Clinical Care Classification System (formerly Home Health Care Classification system) codes. The Clinical Care Classification (CCC) consists of two terminologies: CCC of Nursing Diagnose and CCC of Nursing Interventions both of which are classified by 21 | added v2.6
CD2 | CDT-2 Codes | CDT-2 Codes | American Dental Association's Current Dental Terminology (CDT-2) code. American Dental Association, 211 E. Chicago Avenue,. Chicago, Illinois 60611. | added v2.4
CDCA | CDC Analyte Codes | CDC Analyte Codes | As above, for CDCM | added v2.4
CDCEDACUITY | CDC Emergency Department Acuity | | Patient Acuity indicates level of care required (Acute, Chronic, Critical) | added v2.7
CDCM | CDC Methods/Instruments Codes | CDC Methods/Instruments Codes | Public Health Practice Program Office, Centers for Disease Control and Prevention, 4770 Buford Highway, Atlanta, GA, 30421. Also available via FTP: ftp.cdc.gov/pub/laboratory _info/CLIA and Gopher: gopher.cdc.gov:70/11/laboratory_info/CLIA | added v2.4
CDCOBS | CDC BioSense RT observations (Census) - CDC | | List of BioSense RT observations (Clinical) used in OBX-3 like Temperature, Bloodpressure and Census related observations. | added v2.7
CDCPHINVS | CDC PHIN Vocabulary Coding System | | CDC Public Health Information Network Vocabulary Service (PHIN VS) coding system concepts are used when the public health concepts are not available in the Standard Development Organization(SDO) Vocabulary like SNOMED CT, LOINC, ICD-9, etc.. The concepts | added v2.7

CDCREC | Race & Ethnicity - CDC | | The U.S. Centers for Disease Control and Prevention (CDC) has prepared a code set for use in coding race and ethnicity data. This code set is based on current federal standards for classifying data on race and ethnicity, specifically the minimum race and | added v2.7

CDS | CDC Surveillance | CDC Surveillance | CDC Surveillance Codes. For data unique to specific public health surveillance requirements. Epidemiology Program Office, Centers for Disease Control and Prevention, 1600 Clifton Rd, Atlanta, GA, 30333. (404) 639-3661. | added v2.4

CE | CEN ECG diagnostic codes | CEN ECG diagnostic codes | Specific Non-Drug Code | added v2.4, removed after v2.5.1

CE (obsolete) | CEN ECG diagnostic codes | | CEN ECG diagnostic codes - (Obsolete, retained for backwards compatibility only. See the entry for the MDC coding system.) | added v2.6

CLP | CLIP | CLIP | Simon Leeming, Beth Israel Hospital, Boston MA. Codes for radiology reports. | added v2.4

CPTM | CPT Modifier Code | CPT Modifier Codes | Available for the AMA at the address listed for CPT above. These codes are found in Appendix A of CPT 2000 Standard Edition. (CPT 2000 Standard Edition, American Medical Association, Chicago, IL). | added v2.4

CST | COSTART | COSTART | International coding system for adverse drug reactions. In the USA, maintained by the FDA, Rockville, MD. | added v2.4

CVX | CDC Vaccine Codes | CDC Vaccine Codes | National Immunization Program, Centers for Disease Control and Prevention, 1660 Clifton Road, Atlanta, GA, 30333 | added v2.4

DCL | DICOM Class Label | DICOM Class Label | deprecated | added v2.4, removed after v2.4

DCM | DICOM Controlled Terminology | DICOM modality codes | Codes defined in DICOM Content Mapping Resource. Digital Imaging and Communications in Medicine (DICOM). NEMA Publication PS-3.16 National Electrical Manufacturers Association (NEMA). Rosslyn, VA, 22209. Available at: http://medical.nema.org | added v2.4

DQL | DICOM Query Label | DICOM Query Label | deprecated | added v2.4, removed after v2.4

E | EUCLIDES | EUCLIDES | Available from Euclides Foundation International nv, Excelsiorlaan 4A, B-1930 Zaventem, Belgium; Phone: 32 2 720 90 60. | added v2.4

E5 | Euclides quantity codes | Euclides quantity codes | Available from Euclides Foundation International nv (see above) | added v2.4

E6 | Euclides Lab method codes | Euclides Lab method codes | Available from Euclides Foundation International nv, Excelsiorlaan 4A, B-1930 Zaventem, Belgium; Phone: 32 2 720 90 60. | added v2.4

E7 | Euclides Lab equipment codes | Euclides Lab equipment codes | Available from Euclides Foundation International nv (see above) | added v2.4

ENZC | Enzyme Codes | Enzyme Codes | Enzyme Committee of the International Union of Biochemistry and Molecular Biology. Enzyme Nomenclature: Recommendations on the Nomenclature and Classification of Enzyme-Catalysed Reactions. London: Academic Press, 1992. | added v2.4

EPASRS | EPA SRS | | Subset of EPA SRS listing chemicals that are present in ECOTOX, STORET and TRI. | added v2.7

FDAUDI | FDA Unique Device Identifier | | Represents the approved agencies by the FDA that assign UDI Device Identifiers. | added v2.8.2

FDAUNII | Unique Ingredient Identifier (UNII) | | The Unique Ingredient Identifier (UNII) generated from the FDA Substance Registration System (SRS). | added v2.7

FDDC | First DataBank Drug Codes | First DataBank Drug Codes | National Drug Data File. Proprietary product of First DataBank, Inc. (800) 633-3453, or http://www.firstdatabank.com. | added v2.4

FDDX | First DataBank Diagnostic Codes | First DataBank Diagnostic Codes | Used for drug-diagnosis interaction checking. Proprietary product of First DataBank, Inc. As above for FDDC. | added v2.4

FDK | FDA K10 | FDA K10 | Dept. of Health & Human Services, Food & Drug Administration, Rockville, MD 20857. (device & analyte process codes). | added v2.4

FIPS5_2 | FIPS 5-2 (State) | | Codes for the Identification of the States, the District of Columbia and the Outlying Areas of the United States, and Associated Areas. | added v2.7

FIPS6_4 | FIPS 6-4 (County) | | Federal Information Processing Standard (FIPS) 6-4 provides the names and codes that represent the counties and other entities treated as equivalent legal and/or statistical subdivisions of the 50 States, the District of Columbia, and the possessions and | added v2.7

GDRG2004 | G-DRG German DRG Codes v2004 | G-DRG Duitse DRG Codes v2004 | German Handbook for DRGs 2004. | added v2.6

GDRG2005 | G-DRG German DRG Codes v2005 | G-DRG Duitse DRG Codes v2005 | German Handbook for DRGs 2005. | added v2.6

GDRG2006 | G-DRG German DRG Codes v2006 | G-DRG Duitse DRG Codes v2006 | German Handbook for DRGs 2006. | added v2.6

GDRG2007 | G-DRG German DRG Codes v2007 | G-DRG Duitse DRG Codes v2007 | German Handbook for DRGs 2007. | added v2.6

GDRG2008 | G-DRG German DRG Codes v2008 | G-DRG Duitse DRG Codes v2008 | German Handbook for DRGs 2008. | added v2.6

GDRG2009 | G-DRG German DRG Codes v2009 | G-DRG Duitse DRG Codes v2009 | German Handbook for DRGs 2009. | added v2.7

General code | Active | | deprecated | added v2.7.1, removed after v2.7.1

GMDC2004 | German Major Diagnostic Codes v2004 | Duitse Major Diagnostic Codes v2004 | German Major Diagnostic Codes version 2004. | added v2.6

GMDC2005 | German Major Diagnostic Codes v2005 | Duitse Major Diagnostic Codes v2005 | German Major Diagnostic Codes version 2005. | added v2.6

GMDC2006 | German Major Diagnostic Codes v2006 | Duitse Major Diagnostic Codes v2006 | German Major Diagnostic Codes version 2006. | added v2.6

GMDC2007 | German Major Diagnostic Codes v2007 | Duitse Major Diagnostic Codes v2007 | German Major Diagnostic Codes version 2007. | added v2.6

GMDC2008 | German Major Diagnostic Codes v2008 | Duitse Major Diagnostic Codes v2008 | German Major Diagnostic Codes version 2008. | added v2.6

GMDC2009 | German Major Diagnostic Codes v2009 | Duitse Major Diagnostic Codes v2009 | German Major Diagnostic Codes version 2009. | added v2.7

GS1UDI | GS1 Unique Device Identifier | GS1 Unique Device Identifier | | added v2.8.2

HB | HIBCC | HIBCC | Health Industry Business Communications Council, 5110 N. 40th St., Ste 120, Phoenix, AZ 85018. | added v2.4

HCPCS | CMS (formerly HCFA) Common Procedure Coding System | HCFA Common Procedure Coding System | HCPCS: contains codes for medical equipment, injectable drugs, transportation services, and other services not found in CPT4.<p>http://www.cms.hhs.gov/MedHCPCSGenInfo/ | added v2.4

HCPT | Health Care Provider Taxonomy | | The Blue Cross and Blue Shield Association will act as the administrator of the Provider Taxonomy so that the code structure is classified as external to X12. Ongoing maintenance is solely the responsibility of Workgroup 15 (Provider Information) within A | added v2.5

HHC | Home Health Care | Home Health Care | Home Health Care Classification System; Virginia Saba, EdD, RN; Georgetown University School of Nursing; Washington, DC. Superceded by 'CCC' (see above); this entry is retained for backward-compatibility. | added v2.4

HI | Health Outcomes | Health Outcomes | Health Outcomes Institute codes for outcome variables available (with responses) from Stratis Health (formerly Foundation for Health Care Evaluation and Health Outcomes Institute), 2901 Metro Drive, Suite 400, Bloomington, MN, 55425-1525; (612)

854-3306 (| added v2.4

HIBUDI | HIBCC Unique Device Identifier | HIBCC Unieke Apparaat Identificatie | | added v2.8.2

HL7nnnn | HL7 Defined Codes where nnnn is the HL7 table number | HL7 Gedefinieerde codes waarbij nnnn het HL7 tabelnummer is | Health Level Seven where nnnn is the HL7 table number. | added v2.4

HOT | Japanese Nationwide Medicine Code | Japanse nationale medicatiecode | | added v2.5

HPC | CMS (formerly HCFA)Procedure Codes (HCPCS) | CMS (voormalig HCFA) Procedure Codes (HCPCS) | Health Care Financing Administration (HCFA) Common Procedure Coding System (HCPCS) including modifiers.[1] | added v2.4

I10 | ICD-10 | ICD-10 | World Health Publications, Albany, NY. | added v2.4

I10G2004 | ICD 10 Germany 2004 | | Three code sets exist I10G2004, I10G2005, I10G2006 | added v2.6

I10G2005 | ICD 10 Germany 2005 | | Three code sets exist I10G2004 | added v2.6

I10G2006 | ICD 10 Germany 2006 | | Three code sets exist I10G2004 | added v2.6

I10P | ICD-10 Procedure Codes | ICD-10 Procedure Codes | Procedure Coding System (ICD-10-PCS.) See http://www.cms.hhs.gov/ICD9ProviderDiagnosticCodes/08_ICD10.asp for more information. | added v2.4

I9 | ICD9 | ICD-9 | World Health Publications, Albany, NY. | added v2.4

I9C | ICD-9CM | ICD-9CM | International Classification Of Diseases-9-CM, (1979)<p>Commission on Professional and Hospital Activities, 1968 Green Road, Ann Arbor, MI 48105 (includes all procedures and diagnostic tests). | added v2.4

I9CDX | ICD-9CM Diagnosis codes | | Indicates codes from ICD-9-CM drawn from Volumes 1 and 2, which cover diagnosis codes only. | added v2.6

I9CP | ICD-9CM Procedure codes | | Indicates codes from ICD-9-CM drawn from Volume 3, which covers procedure codes only. | added v2.6

IBT | ISBT | ISBT | Retained for backward compatibility only as of v 2.5. This code value has been superseded by IBTnnnn.<p>International Society of Blood Transfusion. Blood Group Terminology 1990. VOX Sanquines 1990 58(2):152-169. | added v2.4

IBTnnnn | ISBT 128 codes where nnnn specifies a specific table within ISBT 128. | | International Society of Blood Transfusion. (specific contact information will be supplied to editor.)<p>The variable suffix (nnnn) identifies a specific table within ISBT 128. | added v2.5

IC2 | ICHPPC-2 | ICHPPC-2 | International Classification of Health Problems in Primary Care, Classification Committee of World Organization of National Colleges, Academies and Academic Associations of General Practitioners (WONCA), 3rd edition. An adaptation of ICD9 intended for use | added v2.4

ICCUDI | ICCBBA Unique Device Identifier | ICCBBA Unique Device Identifier | | added v2.8.2

ICD10AM | ICD-10 Australian modification | ICD 10 Australische wijzigingen | | added v2.5

ICD10CA | ICD-10 Canada | ICD-10 Canada | | added v2.5

ICD10GM2007 | ICD 10 Germany v2007 | ICD-10 Duitsland v2007 | ICD German modification for 2007. | added v2.6

ICD10GM2008 | ICD 10 Germany v2008 | ICD-10 Duitsland v2008 | ICD German modification for 2008. | added v2.6

ICD10GM2009 | ICD 10 Germany v2009 | ICD-10 Duitsland v2009 | ICD German modification for 2009 | added v2.7

ICD10GM2010 | ICD 10 Germany v2010 | ICD-10 Duitsland v2010 | ICD German modification for 2010 | added v2.7

ICD10GM2011 | ICD 10 Germany v2011 | ICD-10 Duitsland v2011 | ICD German modification for 2011 | added v2.7

ICDO | International Classification of Diseases for Oncology | Internationale Classificatie van Ziektes voor Oncologie | International Classification of Diseases for Oncology, 2nd Edition. World Health Organization: Geneva, Switzerland, 1990. Order from: College of American Pathologists, 325 Waukegan Road, Northfield, IL, 60093-2750. (847) 446-8800. | added v2.4

ICDO2 | International Classification of Disease for Oncology Second Edition | | Percy C, VanHolten V, and Muir C, editors. International Classification of Diseases for Oncology. Second Edition. Geneva: World Health Organization; 1990.<p>The ICD-9 neoplasm structure did not include morphology and there was a growing interest by physic | added v2.7

ICDO3 | International Classification of Disease for Oncology Third Edition | | Fritz A, Percy C, Jack A, Shanmugaratnam K, Sobin L, Parkin D, et al, editors. International Classification of Diseases for Oncology. Third Edition. Geneva: World Health Organization; 2000.<p>The ICD-9 neoplasm structure did not include morphology and the | added v2.7

ICS | ICCS | ICCS | Commission on Professional and Hospital Activities, 1968 Green Road, Ann Arbor, MI 48105. | added v2.4

ICSD | International Classification of Sleep Disorders | Internationale Classificatie van Slaapproblemen | International Classification of Sleep Disorders Diagnostic and Coding Manual, 1990, available from American Sleep Disorders Association, 604 Second Street SW, Rochester, MN 55902 | added v2.4

ISO | ISO 2955.83 (units of measure) with HL7 extensions | ISO 2955.83 (meeteenheden) met HL7 extensies | See chapter 7, section 7.4.2.6 | added v2.7

ISO+ | ISO 2955.83 (units of measure) with HL7 extensions | | deprecated | added v2.5, removed after v2.6

ISO3166_1 | ISO 3166-1 Country Codes | ISO 3166-1 Landcodes | International Standards Organization standard 3166 contains 3 parts. Part 1 contains three tables for codes for countries of the world. These are 2-character alphabetic, 3-character alphabetic, and numeric codes. | added v2.7

ISO3166_2 | ISO 3166-2 Country subdivisions | ISO 3166-2 Landdelen | International Standards Organization standard 3166 contains 3 parts. Part 2 contains a complete breakdown into a relevant level of administrative subdivisions of all countries listed in ISO 3166-1. The code elements used consist of the alpha-2 code eleme | added v2.7

ISO4217 | ISO4217 Currency Codes | ISO 4217 Munteenheden | ISO's currency codes, which are based on the ISO country codes are published in the standard ISO 4217:2008 Codes for the representation of currencies and funds. This International Standard specifies the structure for a three-letter alphabetic code and an | added v2.7

ISO639 | ISO 639 Language | ISO 639 Taal | International Standards Organization codes for the representation of names of languages. ISO 639 provides two sets of language codes, one as a two-character code set (639-1) and another as a three-character code set (639-2) for the representation of name | added v2.7

ISOnnnn | ISO Defined Codes where nnnn is the ISO table number | ISO gedefinieerde codes waarbij nnnn het ISO tabelnummer is | General code | added v2.4, removed after v2.6

ISOnnnn (deprecated) | ISO Defined Codes where nnnn is the ISO table number | ISO gedefinieerde codes waarbij nnnn staat voor het ISO-tabelnummer | International Standards Organization where nnnn is the ISO table number | added v2.7

ITIS | Integrated Taxonomic Information System | Integrated Taxonomic Information System | Source= www.itis.usda.gov. This is a taxonomic hierarchy for living organisms. | added v2.6

IUPC | IUPAC/IFCC Component Codes | IUPAC/IFCC Compoent Codes | Codes used by IUPAC/IFF to identify the component (analyte) measured. Contact Henrik Olesen, as above for IUPP. | added v2.4

IUPP | IUPAC/IFCC Property Codes | IUPAC/IFCC Property Codes | International Union of Pure and Applied Chemistry/International Federation of Clinical Chemistry. The Silver Book: Compendium of terminology and nomenclature of properties in clinical laboratory sciences. Oxford: Blackwell Scientific Publishers, 1995. Hen | added v2.4

JC10 | JLAC/JSLM, nationwide laboratory code | | Source: Classification &Coding for Clinical Laboratory. Japanese Society of Laboratory Medicine(JSLM, Old:Japan Society of Clinical Pathology). Version 10, 1997. A multiaxial code including a analyte code (e.g. Rubella = 5f395), identification code (e.g | added v2.5

JC8 | Japanese Chemistry | Japanese Chemistry | Clinical examination classification code. Japan Association of Clinical Pathology. Version 8, 1990. A multiaxial code including a subject code (e.g. Rubella = 5f395, identification code (e.g. virus ab IGG), a specimen code (e.g. serum =023) and a meth | added v2.4

JJ1017 | Japanese Image Examination Cache | Japanse beeldonderzoek cache | Â | added v2.5

L | Local general code | Lokale algemene code | Locally defined codes for purpose of sender or receiver. Local codes can be identified by L (for backward compatibility) | added v2.7

LB | Local billing code | Lokale facturatiecode | Local billing codes/names (with extensions if needed). | added v2.4

LN | Logical Observation Identifier Names and Codes (LOINCÂ®) | Logical Observation Identifier Names and Codes (LOINC®) | Regenstrief Institute, c/o LOINC, 1050 Wishard Blvd., 5th floor, Indianapolis, IN 46202. 317/630-7433. Available from the Regenstrief Institute server at http://www.Regenstrief.org/loinc/loinc.htm. Also available via HL7 file server: FTP/Gopher (www.mcis | added v2.4

MCD | Medicaid | Medicaid | Medicaid billing codes/names. | added v2.4

MCR | Medicare | Medicare | Medicare billing codes/names. | added v2.4

MDC | Medical Device Communication | Medische Apparaat Communicatie | EN ISO/IEEE 11073-10101 Health informatics - Point-of-care medical device communication - Nomenclature | added v2.6

MDDX | Medispan Diagnostic Codes | Medispan Diagnostic Codes | Codes Used for drug-diagnosis interaction checking. Proprietary product. Hierarchical drug codes for identifying drugs down to manufacturer and pill size. MediSpan, Inc., 8425 Woodfield Crossing Boulevard, Indianapolis, IN 46240. Tel: (800) 428-4495. URL: | added v2.4

MEDC | Medical Economics Drug Codes | Medispan Economics Drug Codes | Proprietary Codes for identifying drugs. Proprietary product of Medical Economics Data, Inc. (800) 223-0581. | added v2.4

MEDR | Medical Dictionary for Drug Regulatory Affairs (MEDDRA) | Medical Dictionary for Drug Regulatory Affairs (MEDDRA) | Patrick Revelle, Director MSSO<p>12011 Sunset Hills Road, VAR1/7B52<p>Reston, VA
20190<p>Patrick.Revelle@ngc.com<p>http://www.meddramsso.com/MSSOWeb/index.htm | added v2.4

MEDX | Medical Economics Diagnostic Codes | Medical Economics Diagnostic Codes | Used for drug-diagnosis interaction checking. Proprietary product of Medical Economics Data, Inc. (800) 223-0581. | added v2.4

MGPI | Medispan GPI | Medispan GPI | Medispan hierarchical drug codes for identifying drugs down to manufacturer and pill size. Proprietary product of MediSpan, Inc., 8425 Woodfield Crossing Boulevard, Indianapolis, IN 46240. Tel: (800) 428-4495. | added v2.4

MVX | CDC Vaccine Manufacturer Codes | CDC Vaccine Manufacturer Codes | As above, for CVX | added v2.4

NAICS | Industry (NAICS) | | The North American Industry Classification System (NAICS) consists of a set of six digit codes that classify and categorize industries. It also organizes the categories on a production/process-oriented basis. This new, uniform, industry-wide classificat | added v2.7

NCPDPnnnnsss | NCPDP code list for data element nnnn [as used in segment sss] | | NCPDP maintain code list associated with the specified Data Element (nnnn) and Segment (sss). The Segment portion is optional if there is no specialization of the Data Element codes between segments.<p>Examples:<p>NCPDP1131RES = code set defined for NCPD | added v2.6

NDA | NANDA | NANDA | North American Nursing Diagnosis Association, Philadelphia, PA. | added v2.4

NDC | National drug codes | Nationale medicatiecodes | These provide unique codes for each distinct drug, dosing form, manufacturer, and packaging. (Available from the National Drug Code Directory, FDA, Rockville, MD, and other sources.) | added v2.4

NDFRT | NDF-RT (Drug Classification) | | The National Drug File RT (NDF-RT) is published by the US Veterans' Administration (VA). NDF-RT covers clinical drugs used at the VA. The NCI version of NDF-RT is used by NCI to provide automated terminology access to the Food and Drug Administration (FDA | added v2.7

NIC | Nursing Interventions Classification | Nursing Interventions Classification | Iowa Intervention Project, College of Nursing, University of Iowa, Iowa City, Iowa | added v2.4

NIP001 | Source of Information (Immunization) | | CDC National Immunization Program's (NIP) defined table to be used in HL7 2.x message RXA-9 for documenting the source of information regarding immunization; e.g. From school, provider,public health agency. | added v2.7

NIP002 | Substance refusal reason | | CDC National Immunization Program's (NIP) defined table to be used in HL7 2.x message RXA-18 for substance refusal reason (reasons for not having vaccination); e.g. Religious exemption, parental decision | added v2.7

NIP004 | Vaccination - Contraindications, Precautions, and Immunities | | CDC National Immunization Program's (NIP) defined table for vaccine contraindications and precautions; e.g. Allergy to egg ingestion, thimerosol | added v2.7

NIP007 | Vaccinated at location (facility) | | CDC National Immunization Program's (NIP) defined table for vaccinated at location (facility); e.g. Private doctor's office, Public Health Clinic | added v2.7

NIP008 | Vaccine purchased with (Type of funding) | | CDC National Immunization Program's (NIP) defined table enumerates the type of funds used for purchasing vaccine; e.g. Public funds, Military funds | added v2.7

NIP009 | Reported adverse event previously | | CDC National Immunization Program's (NIP) defined table enumerates the authorities to whom the vaccination related adverse events were previously reported; e.g. To health department, To manufacturer | added v2.7

NIP010 | VAERS Report type | | CDC National Immunization Program's (NIP) defined table enumerates the type of report used in VAERS (Vaccination Adverse Event Reporting System); e.g. Initial, Follow-up | added v2.7

NND | Notifiable Event (Disease/Condition) Code List | | List of notifiable events, which includes infectious and non-infectious disease or conditions. This list includes events that are notifiable at the state and national level. | added v2.7

NPI | National Provider Identifier | Nationaal Zorgverlener Identificatie | This is the US Realm Health Care Provider National Identifier. It is produced and maintained by CMS (The US Government Centers for Medicare & Medicaid Services http://www.cms.gov), US Dept. of Health and Human Services, 7500 Security Blvd., Baltimore, MD | added v2.4

NUBC | National Uniform Billing Committee | | The NUBC was formed to develop a single billing form and standard data set that could be used nationwide by institutional providers and payers for handling health care claims. The NUBC holds meetings and conference calls throughout the year and change re | added v2.5

NULLFL | Null Flavor | Null Flavor | System of coded values for Flavors of Null, as used in HL7 Version 3 standards. Identical to the HL7 version 3<p>coding system 2.16.840.1.113883.5.1008 NullFlavor | added v2.7

O301 | German Procedure Codes | Duitse Behandelcodes | Source: OPS Operationen- und Prozedurenschluessel. | added v2.6

O3012004 | OPS Germany v2004 | OPS Duitsland v2004 | Source: OPS Operationen- und Prozedurenschluessel 2004. | added v2.6

O3012005 | OPS Germany v2005 | OPS Duitsland v2004 | Source: OPS Operationen- und Prozedurenschluessel 2005. | added v2.6

O3012006 | OPS Germany v2006 | OPS Duitsland v2004 | Source: OPS Operationen- und Prozedurenschluessel 2006. | added v2.6

OHA | Omaha System | Omaha System | Omaha Visiting Nurse Association, Omaha, NB. | added v2.4

OPS2007 | OPS Germany v2007 | OPS Duitsland v2004 | Source: OPS Operationen- und Prozedurenschluessel 2007. | added v2.6

OPS2008 | OPS Germany v2008 | OPS Duitsland v2004 | Source: OPS Operationen- und Prozedurenschluessel 2008. | added v2.6

OPS2009 | OPS Germany v2009 | OPS Duitsland v2004 | Source: OPS Operationen- und Prozedurenschluessel 2009. | added v2.7

OPS2010 | OPS Germany v2010 | OPS Duitsland v2004 | Source: OPS Operationen- und Prozedurenschluessel 2010. | added v2.7

OPS2011 | OPS Germany v2011 | OPS Duitsland v2004 | Source: OPS Operationen- und Prozedurenschluessel 2011. | added v2.7

PHINQUESTION | CDC Public Health Information Network (PHIN) Question | | CDC Public Health Questions used in HL7 Message as observation identifiers. These question or observation identifiers are used in CDC's message implementation guides and will be passed in HL7 OBX-3 or Observation.Code | added v2.7

PLR | CDC PHLIP Lab result codes that are not covered in SNOMED at the time of this implementation | | APHL CDC co-sponsored PHLIP | added v2.7

PLT | CDC PHLIP Lab test codes, where LOINC concept is too broad or not yet available, especially as needed for ordering and or lab to lab reporting) | | APHL CDC co-sponsored PHLIP | added v2.7

POS | POS Codes | POS Codes | HCFA Place of Service Codes for Professional Claims (see http://www.cms.hhs.gov/PlaceofServiceCodes/). | added v2.4

RC | Read Classification | Read Classification | The Read Clinical Classification of Medicine, Park View Surgery, 26 Leicester Rd., Loughborough LE11 2AG (includes drug procedure and other codes, as well as diagnostic codes). | added v2.4

RXNORM | RxNorm | | RxNorm provides standard names for clinical drugs (active ingredient + strength + dose form) and for dose forms as administered to a patient. It provides links from clinical drugs, both branded and generic, to their active ingredients, drug components (ac | added v2.7

SCT | SNOMED Clinical Terms | SNOMED Clinical Terms | SNOMED-CT concept identifier codes.<p>SNOMED International, I325 Waukegan Rd, Northfield, IL, 60093, +1 800-323-4040, mailto:snomed@cap.org http://www.snomed.org | added v2.6

SCT2 | SNOMED Clinical Terms alphanumeric codes | SNOMED Clinical Terms alfanumeriek codes | Used to indicate that the code value is the legacy-style SNOMED alphanumeric codes, rather than the concept identifier codes.<p>SNOMED International, I325 Waukegan Rd, Northfield, IL, 60093, +1 800-323-4040, mailto:snomed@cap.org http://www.snomed.org | added v2.6

SDM | SNOMED- DICOM Microglossary | SNOMED- DICOM Microglossary | College of American Pathologists, Skokie, IL, 60077-1034. (formerly designated as 99SDM). | added v2.4

SIC | Industry (SIC) | | Standard Industry Classification - 1987. Use NAICS 2002. This is mainly for mapping and backward compatibility purposes. | added v2.7

SNM | Systemized Nomenclature of Medicine (SNOMED) | Systemized Nomenclature of Medicine (SNOMED) | Systemized Nomenclature of Medicine, 2nd Edition 1984 Vols 1, 2, College of American Pathologists, Skokie, IL. | added v2.4

SNM3 | SNOMED International | SNOMED Internationaal | SNOMED International, 1993 Vols 1-4, College of American Pathologists, Skokie, IL, 60077-1034. | added v2.4

SNT | SNOMED topology codes (anatomic sites) | SNOMED topologiecodes (anatomische gebieden) | College of American Pathologists, 5202 Old Orchard Road, Skokie, IL 60077-1034. | added v2.4

SOC | Occupation (SOC 2000) | | The 2000 Standard Occupational Classification (SOC) system is used by Federal statistical agencies to classify workers into occupational categories for the purpose of collecting, calculating, or disseminating data. | added v2.7

UB04FL14 | Priority (Type) of Visit | | Source: Official UB-04 Data Specification Manual, published each July, by the National Uniform Billing Committee (NUBC). To access the information you must be a member of NUBC. This coding system superseded UB92 in July, 2007. More information can be f | added v2.6

UB04FL15 | Point of Origin | | Source: Official UB-04 Data Specification Manual, published each July, by the National Uniform Billing Committee (NUBC). To access the information you must be a member of NUBC. This coding system superseded UB92 in July, 2007. More information can be f | added v2.6

UB04FL17 | Patient Discharge Status | | Source: Official UB-04 Data Specification Manual, published each July, by the National Uniform Billing Committee (NUBC). To access the information you must be a member of NUBC. This coding system superseded UB92 in July, 2007. More information can be f | added v2.6

UB04FL31 | Occurrence Code | | Source: Official UB-04 Data Specification Manual, published each July, by the National Uniform Billing Committee (NUBC). To access the information you must be a member of NUBC. This coding system superseded UB92 in July, 2007. More information can be f | added v2.7

UB04FL35 | Occurrence Span | | Source: Official UB-04 Data Specification Manual, published each July, by the National Uniform Billing Committee (NUBC). To access the information you must be a member of NUBC. This coding system superseded UB92 in July, 2007. More information can be f | added v2.7

UB04FL39 | Value Code | | Source: Official UB-04 Data Specification Manual, published each July, by the National Uniform Billing Committee (NUBC). To access the information you must be a member of NUBC. This coding system superseded UB92 in July, 2007. More information can be f | added v2.7

UC | UCDS | UCDS | Uniform Clinical Data Systems. Ms. Michael McMullan, Office of Peer Review Health Care Finance Administration, The Meadows East Bldg., 6325 Security Blvd., Baltimore, MD 21207; (301) 966 6851. | added v2.4

UCUM | UCUM code set for units of measure(from Regenstrief) | UCUM - Unified Codes of Measure | Added by motion of VOCABULARY T.C. 20060308 14-0-3 | added v2.6

UMD | MDNS | MDNS | Universal Medical Device Nomenclature System. ECRI, 5200 Butler Pike, Plymouth Meeting, PA 19462 USA. Phone: 215-825-6000, Fax: 215-834-1275. | added v2.4

UML | Unified Medical Language | Unified Medical Language | National Library of Medicine, 8600 Rockville Pike, Bethesda, MD 20894. | added v2.4

UPC | Universal Product Code | Universal Product Code | The Uniform Code Council. 8163 Old Yankee Road, Suite J, Dayton, OH 45458; (513) 435 3070 | added v2.4

UPIN | UPIN | UPIN | Medicare/CMS 's (formerly HCFA) universal physician identification numbers, available from Health Care Financing Administration, U.S. Dept. of Health and Human Services, Bureau of Program Operations, 6325 Security Blvd., Meadows East Bldg., Room 300, Bal | added v2.4

USPS | United States Postal Service | | Two Letter State and Possession Abbreviations are listed in Publication 28, Postal Addressing Standards which can be obtained from Address Information Products, National Address Information Center, 6060 Primacy Parkway, Suite 101, Memphis, Tennessee 381 | added v2.5

W1 | WHO record # drug codes (6 digit) | WHO record # drug codes (6 cijferig) | World Health organization record number code. A unique sequential number is assigned to each unique single component drug and to each multi-component drug. Eight digits are allotted to each such code, six to identify the active agent, and 2 to identify th | added v2.4

W2 | WHO record # drug codes (8 digit) | WHO record # drug codes (8 cijferig) | World Health organization record number code. A unique sequential number is assigned to each unique single component drug and to each multi-component drug. Eight digits are allotted to each such code, six to identify the active agent, and 2 to identify th | added v2.4

W4 | WHO record # code with ASTM extension | WHO record # code met ASTM extensie | With ASTM extensions (see Implementation Guide), the WHO codes can be used to report serum (and other) levels, patient compliance with drug usage instructions, average daily doses and more (see Appendix X1 the Implementation Guide). | added v2.4

WC | WHO ATC | WHO ATC | WHO's ATC codes provide a hierarchical classification of drugs by therapeutic class. They are linked to the record number codes listed above. | added v2.4

X12Dennnn | ASC X12 Code List nnnn | | Code list associated with X12 Data Element nnnn. Example::<p>X12DE738 - code set defined for X12 data element 738 (Measurement Qualifier)<p>The Accredited Standards Committee (ASC) X12<p>http://www.x12.org | added v2.6

4.2.13.397 HL7 Version 2 Table 0397

URL: https://hl7.org/fhir/STU3/v2/0397/index.html

This page is part of the FHIR Specification (v3.0.2: STU 3). The current version which supercedes this version is 4.0.1. For a full list of available versions, see the Directory of published versions

Vocabulary Work Group | Maturity Level: N/A | External | Use Context: Any

This is a table defined as part of HL7 v2 . Related FHIR content: v2 Sequencing.

Summary

Name: | v2 Sequencing
Definition: | FHIR Value set/code system definition for HL7 v2 table 0397 (Sequencing)
Code System URL: | http://hl7.org/fhir/v2/0397
Value Set URL: | http://hl7.org/fhir/ValueSet/v2-0397
OID: | ??
CodeSystem Resource | XML / JSON
ValueSet Resource | XML / JSON

This value set is used in the following places:

* This value set is the designated 'entire code system' value set for v2 Sequencing

4.2.13.397.1 Code System Content

Sequencing

Code | Description | Nederlands (Dutch) | Comment | Version
A | Ascending | Oplopend | | added v2.4
AN | Ascending, case insensitive | Oplopend, niet-hoofdlettergevoelig | | added v2.4
D | Descending | Aflopend | | added v2.4
DN | Descending, case insensitive | Aflopend, niet-hoofdlettergevoelig | | added v2.4
N | None | Geen | | added v2.4

4.2.13.398 HL7 Version 2 Table 0398

URL: https://hl7.org/fhir/STU3/v2/0398/index.html

This page is part of the FHIR Specification (v3.0.2: STU 3). The current version which supercedes this version is 4.0.1. For a full list of available versions, see the Directory of published versions

Vocabulary Work Group | Maturity Level: N/A | External | Use Context: Any

This is a table defined as part of HL7 v2 . Related FHIR content: v2 Continuation Style Code.

Summary

Name: | v2 Continuation Style Code
Definition: | FHIR Value set/code system definition for HL7 v2 table 0398 (Continuation Style Code)
Code System URL: | http://hl7.org/fhir/v2/0398
Value Set URL: | http://hl7.org/fhir/ValueSet/v2-0398
OID: | ??
CodeSystem Resource | XML / JSON
ValueSet Resource | XML / JSON

This value set is used in the following places:

* This value set is the designated 'entire code system' value set for v2 Continuation Style Code

4.2.13.398.1 Code System Content

Continuation Style Code

Code | Description | Nederlands (Dutch) | Comment | Version
F | Fragmentation | Fragmentatie | | added v2.4
I | Interactive Continuation | Interactieve continuatie | | added v2.4

4.2.13.401 HL7 Version 2 Table 0401

URL: https://hl7.org/fhir/STU3/v2/0401/index.html

This page is part of the FHIR Specification (v3.0.2: STU 3). The current version which supercedes this version is 4.0.1. For a full list of available versions, see the Directory of published versions

Vocabulary Work Group | Maturity Level: N/A | External | Use Context: Any

This is a table defined as part of HL7 v2 . Related FHIR content: v2 Government Reimbursement Program.

Summary

Name: | v2 Government Reimbursement Program

Definition: | FHIR Value set/code system definition for HL7 v2 table 0401 (Government Reimbursement Program)
Code System URL: | http://hl7.org/fhir/v2/0401
Value Set URL: | http://hl7.org/fhir/ValueSet/v2-0401
OID: | ??
CodeSystem Resource | XML / JSON
ValueSet Resource | XML / JSON

This value set is used in the following places:

* This value set is the designated 'entire code system' value set for v2 Government Reimbursement Program

4.2.13.401.1 Code System Content

Government Reimbursement Program

Code | Description | Nederlands (Dutch) | Comment | Version
C | Medi-Cal | Medi-Cal | | added v2.4
MM | Medicare | Medicare | | added v2.4

4.2.13.402 HL7 Version 2 Table 0402

URL: https://hl7.org/fhir/STU3/v2/0402/index.html

This page is part of the FHIR Specification (v3.0.2: STU 3). The current version which supercedes this version is 4.0.1. For a full list of available versions, see the Directory of published versions

Vocabulary Work Group | Maturity Level: N/A | External | Use Context: Any

This is a table defined as part of HL7 v2 . Related FHIR content: v2 School Type.

Summary

Name: | v2 School Type
Definition: | FHIR Value set/code system definition for HL7 v2 table 0402 (School Type)
Code System URL: | http://hl7.org/fhir/v2/0402
Value Set URL: | http://hl7.org/fhir/ValueSet/v2-0402
OID: | ??
CodeSystem Resource | XML / JSON
ValueSet Resource | XML / JSON

This value set is used in the following places:

* This value set is the designated 'entire code system' value set for v2 School Type

4.2.13.402.1 Code System Content

School Type

Code | Description | Nederlands (Dutch) | Comment | Version
D | Dental | Tandheelkunde | | added v2.4
G | Graduate | | | added v2.4
M | Medical | Geneeskunde | | added v2.4
U | Undergraduate | | | added v2.4

4.2.13.403 HL7 Version 2 Table 0403

URL: https://hl7.org/fhir/STU3/v2/0403/index.html

This page is part of the FHIR Specification (v3.0.2: STU 3). The current version which supercedes this version is 4.0.1. For a full list of available versions, see the Directory of published versions

Vocabulary Work Group | Maturity Level: N/A | External | Use Context: Any

This is a table defined as part of HL7 v2 . Related FHIR content: v2 Language Ability.

Summary

Name: | v2 Language Ability
Definition: | FHIR Value set/code system definition for HL7 v2 table 0403 (Language Ability)
Code System URL: | http://hl7.org/fhir/v2/0403
Value Set URL: | http://hl7.org/fhir/ValueSet/v2-0403
OID: | ??
CodeSystem Resource | XML / JSON
ValueSet Resource | XML / JSON

This value set is used in the following places:

* This value set is the designated 'entire code system' value set for v2 Language Ability

4.2.13.403.1 Code System Content

Language Ability

Code | Description | Nederlands (Dutch) | Comment | Version
1 | Read | Lezen | | added v2.4

2 | Write | Schrijven | | added v2.4
3 | Speak | Spreken | | added v2.4
4 | Understand | Verstaan | | added v2.4
5 | Sign | Gebarentaal | | added v2.4

4.2.13.404 HL7 Version 2 Table 0404

URL: https://hl7.org/fhir/STU3/v2/0404/index.html

This page is part of the FHIR Specification (v3.0.2: STU 3). The current version which supercedes this version is 4.0.1. For a full list of available versions, see the Directory of published versions

Vocabulary Work Group | Maturity Level: N/A | External | Use Context: Any

This is a table defined as part of HL7 v2 . Related FHIR content: v2 Language Proficiency.

Summary

Name: | v2 Language Proficiency
Definition: | FHIR Value set/code system definition for HL7 v2 table 0404 (Language Proficiency)
Code System URL: | http://hl7.org/fhir/v2/0404
Value Set URL: | http://hl7.org/fhir/ValueSet/v2-0404
OID: | ??
CodeSystem Resource | XML / JSON
ValueSet Resource | XML / JSON

This value set is used in the following places:

* This value set is the designated 'entire code system' value set for v2 Language Proficiency

4.2.13.404.1 Code System Content

Language Proficiency

Code | Description | Nederlands (Dutch) | Comment | Version
1 | Excellent | Excellent | | added v2.4
2 | Good | Goed | | added v2.4
3 | Fair | Redelijk | | added v2.4
4 | Poor | Matig | | added v2.4
5 | Some (level unknown) | Enige (niveau onbekend) | | added v2.4
6 | None | Geen | | added v2.4

4.2.13.406 HL7 Version 2 Table 0406

URL: https://hl7.org/fhir/STU3/v2/0406/index.html

This page is part of the FHIR Specification (v3.0.2: STU 3). The current version which supercedes this version is 4.0.1. For a full list of available versions, see the Directory of published versions

Vocabulary Work Group | Maturity Level: N/A | External | Use Context: Any

This is a table defined as part of HL7 v2 . Related FHIR content: v2 Organization Unit Type.

Summary

Name: | v2 Organization Unit Type
Definition: | FHIR Value set/code system definition for HL7 v2 table 0406 (Organization Unit Type)
Code System URL: | http://hl7.org/fhir/v2/0406
Value Set URL: | http://hl7.org/fhir/ValueSet/v2-0406
OID: | ??
CodeSystem Resource | XML / JSON
ValueSet Resource | XML / JSON

This value set is used in the following places:

* This value set is the designated 'entire code system' value set for v2 Organization Unit Type

4.2.13.406.1 Code System Content

Organization Unit Type

Code | Description | Nederlands (Dutch) | Comment | Version
1 | Hospital | Ziekenhuis | | added v2.4
2 | Physician Clinic | Zorgverlener kliniek | | added v2.4
3 | Long Term Care | Langdurige zorg | | added v2.4
4 | Acute Care | Acute zorg | | added v2.4
5 | Other | Anders | | added v2.4
H | Home | Privé | | added v2.4
O | Office | Zakelijk | | added v2.4

4.2.13.409 HL7 Version 2 Table 0409

URL: https://hl7.org/fhir/STU3/v2/0409/index.html

This page is part of the FHIR Specification (v3.0.2: STU 3). The current version which supercedes this version is 4.0.1. For a full list of available versions, see the Directory of published versions

Vocabulary Work Group | Maturity Level: N/A | External | Use Context: Any

This is a table defined as part of HL7 v2 . Related FHIR content: v2 Application Change Type.

Summary

Name: | v2 Application Change Type
Definition: | FHIR Value set/code system definition for HL7 v2 table 0409 (Application Change Type)
Code System URL: | http://hl7.org/fhir/v2/0409
Value Set URL: | http://hl7.org/fhir/ValueSet/v2-0409
OID: | ??
CodeSystem Resource | XML / JSON
ValueSet Resource | XML / JSON

This value set is used in the following places:

* This value set is the designated 'entire code system' value set for v2 Application Change Type

4.2.13.409.1 Code System Content

Application Change Type

Code | Description | Nederlands (Dutch) | Comment | Version
M | Migrates to different CPU | Migreert naar andere CPU | | added v2.3.1
SD | Shut down | Afsluiten | | added v2.3.1
SU | Start up | Opstarten | | added v2.3.1

4.2.13.411 HL7 Version 2 Table 0411

URL: https://hl7.org/fhir/STU3/v2/0411/index.html

This page is part of the FHIR Specification (v3.0.2: STU 3). The current version which supercedes this version is 4.0.1. For a full list of available versions, see the Directory of published versions

Vocabulary Work Group | Maturity Level: N/A | External | Use Context: Any

This is a table defined as part of HL7 v2 . Related FHIR content: v2 Supplemental Service Information Values.

Summary

Name: | v2 Supplemental Service Information Values
Definition: | FHIR Value set/code system definition for HL7 v2 table 0411 (Supplemental Service Information Values)
Code System URL: | http://hl7.org/fhir/v2/0411
Value Set URL: | http://hl7.org/fhir/ValueSet/v2-0411
OID: | ??
CodeSystem Resource | XML / JSON
ValueSet Resource | XML / JSON

This value set is used in the following places:

* This value set is the designated 'entire code system' value set for v2 Supplemental Service Information Values

4.2.13.411.1 Code System Content

Supplemental Service Information Values

Code | Description | Deutsch (German) | Nederlands (Dutch) | Comment | Version
... | No suggested values defined. | keine Werte vorgeschlagen | geen voorgestelde waarden | | added v2.5.1
1ST | First | | | deprecated | added v2.4, removed after v2.4
2ND | Second | | | deprecated | added v2.4, removed after v2.4
3RD | Third | | | deprecated | added v2.4, removed after v2.4
4TH | Fourth | | | deprecated | added v2.4, removed after v2.4
5TH | Fifth | | | deprecated | added v2.4, removed after v2.4
A/P | Anterior/Posterior | | | deprecated | added v2.4, removed after v2.4
ANT | Anterior | | | deprecated | added v2.4, removed after v2.4
BLT | Bilateral | | | deprecated | added v2.4, removed after v2.4
DEC | Decubitus | | | deprecated | added v2.4, removed after v2.4
DST | Distal | | | deprecated | added v2.4, removed after v2.4
LAT | Lateral | | | deprecated | added v2.4, removed after v2.4
LFT | Left | | | deprecated | added v2.4, removed after v2.4
LLQ | Left Lower Quadrant | | | deprecated | added v2.4, removed after v2.4
LOW | Lower | | | deprecated | added v2.4, removed after v2.4
LUQ | Left Upper Quadrant | | | deprecated | added v2.4, removed after v2.4
MED | Medial | | | deprecated | added v2.4, removed after v2.4
OR | Operating Room | | | deprecated | added v2.4, removed after v2.4
PED | Pediatric | | | deprecated | added v2.4, removed after v2.4
POS | Posterior | | | deprecated | added v2.4, removed after v2.4
PRT | Portable | | | deprecated | added v2.4, removed after v2.4
PRX | Proximal | | | deprecated | added v2.4, removed after v2.4

REC | Recumbent | | | deprecated | added v2.4, removed after v2.4
RGH | Right | | | deprecated | added v2.4, removed after v2.4
RLQ | Right Lower Quadrant | | | deprecated | added v2.4, removed after v2.4
RUQ | Right Upper Quadrant | | | deprecated | added v2.4, removed after v2.4
UPP | Upper | | | deprecated | added v2.4, removed after v2.4
UPR | Upright | | | deprecated | added v2.4, removed after v2.4
WCT | With Contrast | | | deprecated | added v2.4, removed after v2.4
WOC | Without Contrast | | | deprecated | added v2.4, removed after v2.4
WSD | With Sedation | | | deprecated | added v2.4, removed after v2.4

4.2.13.415 HL7 Version 2 Table 0415

URL: https://hl7.org/fhir/STU3/v2/0415/index.html

This page is part of the FHIR Specification (v3.0.2: STU 3). The current version which supercedes this version is 4.0.1. For a full list of available versions, see the Directory of published versions

Vocabulary Work Group | Maturity Level: N/A | External | Use Context: Any

This is a table defined as part of HL7 v2 . Related FHIR content: v2 Transfer Type.

Summary

Name: | v2 Transfer Type
Definition: | FHIR Value set/code system definition for HL7 v2 table 0415 (Transfer Type)
Code System URL: | http://hl7.org/fhir/v2/0415
Value Set URL: | http://hl7.org/fhir/ValueSet/v2-0415
OID: | ??
CodeSystem Resource | XML / JSON
ValueSet Resource | XML / JSON

This value set is used in the following places:

* This value set is the designated 'entire code system' value set for v2 Transfer Type

4.2.13.415.1 Code System Content

Transfer Type

Code | Description | Comment | Version
E | DRG Exempt | | added v2.4
N | DRG Non Exempt | | added v2.4

4.2.13.416 HL7 Version 2 Table 0416

URL: https://hl7.org/fhir/STU3/v2/0416/index.html

This page is part of the FHIR Specification (v3.0.2: STU 3). The current version which supercedes this version is 4.0.1. For a full list of available versions, see the Directory of published versions

Vocabulary Work Group | Maturity Level: N/A | External | Use Context: Any

This is a table defined as part of HL7 v2 . Related FHIR content: v2 Procedure DRG Type.

Summary

Name: | v2 Procedure DRG Type
Definition: | FHIR Value set/code system definition for HL7 v2 table 0416 (Procedure DRG Type)
Code System URL: | http://hl7.org/fhir/v2/0416
Value Set URL: | http://hl7.org/fhir/ValueSet/v2-0416
OID: | ??
CodeSystem Resource | XML / JSON
ValueSet Resource | XML / JSON

This value set is used in the following places:

* This value set is the designated 'entire code system' value set for v2 Procedure DRG Type

4.2.13.416.1 Code System Content

Procedure DRG Type

Code | Description | Nederlands (Dutch) | Comment | Version
1 | 1st non-Operative | 1ste niet-operatief | | added v2.4
2 | 2nd non-Operative | 2de niet-operatief | | added v2.4
3 | Major Operative | groot operatief | | added v2.4
4 | 2nd Operative | 2de operatief | | added v2.4
5 | 3rd Operative | 3de operatief | | added v2.4

4.2.13.417 HL7 Version 2 Table 0417

URL: https://hl7.org/fhir/STU3/v2/0417/index.html

This page is part of the FHIR Specification (v3.0.2: STU 3). The current version which supercedes this version is 4.0.1. For a full list of available versions, see the Directory of published versions

Vocabulary Work Group | Maturity Level: N/A | External | Use Context: Any

This is a table defined as part of HL7 v2 . Related FHIR content: v2 Tissue Type Code.

Summary

Name: | v2 Tissue Type Code
Definition: | FHIR Value set/code system definition for HL7 v2 table 0417 (Tissue Type Code)
Code System URL: | http://hl7.org/fhir/v2/0417
Value Set URL: | http://hl7.org/fhir/ValueSet/v2-0417
OID: | ??
CodeSystem Resource | XML / JSON
ValueSet Resource | XML / JSON

This value set is used in the following places:

* This value set is the designated 'entire code system' value set for v2 Tissue Type Code

4.2.13.417.1 Code System Content

Tissue Type Code

Code | Description | Comment | Version
0 | No tissue expected | | added v2.4
1 | Insufficient Tissue | | added v2.4
2 | Not abnormal | | added v2.4
3 | Abnormal-not categorized | | added v2.4
4 | Mechanical abnormal | | added v2.4
5 | Growth alteration | | added v2.4
6 | Degeneration & necrosis | | added v2.4
7 | Non-acute inflammation | | added v2.4
8 | Non-malignant neoplasm | | added v2.4
9 | Malignant neoplasm | | added v2.4
B | Basal cell carcinoma | | added v2.4
C | Carcinoma-unspecified type | | added v2.4
G | Additional tissue required | | added v2.4

4.2.13.418 HL7 Version 2 Table 0418

URL: https://hl7.org/fhir/STU3/v2/0418/index.html

This page is part of the FHIR Specification (v3.0.2: STU 3). The current version which supercedes this version is 4.0.1. For a full list of available versions, see the Directory of published versions

Vocabulary Work Group | Maturity Level: N/A | External | Use Context: Any

This is a table defined as part of HL7 v2 . Related FHIR content: v2 Procedure Priority.

Summary

Name: | v2 Procedure Priority
Definition: | FHIR Value set/code system definition for HL7 v2 table 0418 (Procedure Priority)
Code System URL: | http://hl7.org/fhir/v2/0418
Value Set URL: | http://hl7.org/fhir/ValueSet/v2-0418
OID: | ??
CodeSystem Resource | XML / JSON
ValueSet Resource | XML / JSON

This value set is used in the following places:

* This value set is the designated 'entire code system' value set for v2 Procedure Priority

4.2.13.418.1 Code System Content

Procedure Priority

Code | Description | Nederlands (Dutch) | Comment | Version
... | | | | added v2.6
0 | the admitting procedure | Opname procedure | | added v2.4
1 | the primary procedure | Primaire procedure | | added v2.4
2 | for ranked secondary procedures | Secundaire procedures | | added v2.4
… | | | deprecated | added v2.4, removed after v2.5.1

4.2.13.421 HL7 Version 2 Table 0421

URL: https://hl7.org/fhir/STU3/v2/0421/index.html

This page is part of the FHIR Specification (v3.0.2: STU 3). The current version which supercedes this version is 4.0.1. For a full list of available versions, see the Directory of published versions

Vocabulary Work Group | Maturity Level: N/A | External | Use Context: Any

This is a table defined as part of HL7 v2 . Related FHIR content: v2 Severity of Illness Code.

Summary

Name: | v2 Severity of Illness Code
Definition: | FHIR Value set/code system definition for HL7 v2 table 0421 (Severity of Illness Code)
Code System URL: | http://hl7.org/fhir/v2/0421
Value Set URL: | http://hl7.org/fhir/ValueSet/v2-0421
OID: | ??
CodeSystem Resource | XML / JSON
ValueSet Resource | XML / JSON

This value set is used in the following places:

* This value set is the designated 'entire code system' value set for v2 Severity of Illness Code

4.2.13.421.1 Code System Content

Severity of Illness Code

Code | Description | Nederlands (Dutch) | Comment | Version
MI | Mild | Mild | | added v2.4
MO | Moderate | Gemiddeld | | added v2.4
SE | Severe | Ernstig | | added v2.4

4.2.13.422 HL7 Version 2 Table 0422

URL: https://hl7.org/fhir/STU3/v2/0422/index.html

This page is part of the FHIR Specification (v3.0.2: STU 3). The current version which supercedes this version is 4.0.1. For a full list of available versions, see the Directory of published versions

Vocabulary Work Group | Maturity Level: N/A | External | Use Context: Any

This is a table defined as part of HL7 v2 . Related FHIR content: v2 Triage Code.

Summary

Name: | v2 Triage Code
Definition: | FHIR Value set/code system definition for HL7 v2 table 0422 (Triage Code)
Code System URL: | http://hl7.org/fhir/v2/0422
Value Set URL: | http://hl7.org/fhir/ValueSet/v2-0422
OID: | ??
CodeSystem Resource | XML / JSON
ValueSet Resource | XML / JSON

This value set is used in the following places:

* This value set is the designated 'entire code system' value set for v2 Triage Code

4.2.13.422.1 Code System Content

Triage Code

Code | Description | Nederlands (Dutch) | Comment | Version
1 | Non-acute | Niet-acuut | | added v2.4
2 | Acute | Acuut | | added v2.4
3 | Urgent | Urgent | | added v2.4
4 | Severe | Ernstig | | added v2.4
5 | Dead on Arrival (DOA) | Overleden bij aankomst (DOA) | | added v2.4
99 | Other | Anders | | added v2.4

4.2.13.423 HL7 Version 2 Table 0423

URL: https://hl7.org/fhir/STU3/v2/0423/index.html

This page is part of the FHIR Specification (v3.0.2: STU 3). The current version which supercedes this version is 4.0.1. For a full list of available versions, see the Directory of published versions

Vocabulary Work Group | Maturity Level: N/A | External | Use Context: Any

This is a table defined as part of HL7 v2 . Related FHIR content: v2 Case Category Code.

Summary

Name: | v2 Case Category Code
Definition: | FHIR Value set/code system definition for HL7 v2 table 0423 (Case Category Code)
Code System URL: | http://hl7.org/fhir/v2/0423
Value Set URL: | http://hl7.org/fhir/ValueSet/v2-0423
OID: | ??
CodeSystem Resource | XML / JSON
ValueSet Resource | XML / JSON

This value set is used in the following places:

* This value set is the designated 'entire code system' value set for v2 Case Category Code

4.2.13.423.1 Code System Content

Case Category Code

Code | Description | Comment | Version
D | Doctor's Office Closed | | added v2.4

4.2.13.424 HL7 Version 2 Table 0424

URL: https://hl7.org/fhir/STU3/v2/0424/index.html

This page is part of the FHIR Specification (v3.0.2: STU 3). The current version which supercedes this version is 4.0.1. For a full list of available versions, see the Directory of published versions

Vocabulary Work Group | Maturity Level: N/A | External | Use Context: Any

This is a table defined as part of HL7 v2 . Related FHIR content: v2 Gestation Category Code.

Summary

Name: | v2 Gestation Category Code
Definition: | FHIR Value set/code system definition for HL7 v2 table 0424 (Gestation Category Code)
Code System URL: | http://hl7.org/fhir/v2/0424
Value Set URL: | http://hl7.org/fhir/ValueSet/v2-0424
OID: | ??
CodeSystem Resource | XML / JSON
ValueSet Resource | XML / JSON

This value set is used in the following places:

* This value set is the designated 'entire code system' value set for v2 Gestation Category Code

4.2.13.424.1 Code System Content

Gestation Category Code

Code | Description | Deutsch (German) | Comment | Version
1 | Premature / Pre-term | vorzeitig | | added v2.4
2 | Full Term | normal | | added v2.4
3 | Overdue / Post-term | übertragen | | added v2.4

4.2.13.425 HL7 Version 2 Table 0425

URL: https://hl7.org/fhir/STU3/v2/0425/index.html

This page is part of the FHIR Specification (v3.0.2: STU 3). The current version which supercedes this version is 4.0.1. For a full list of available versions, see the Directory of published versions

Vocabulary Work Group | Maturity Level: N/A | External | Use Context: Any

This is a table defined as part of HL7 v2 . Related FHIR content: v2 Newborn Code.

Summary

Name: | v2 Newborn Code
Definition: | FHIR Value set/code system definition for HL7 v2 table 0425 (Newborn Code)
Code System URL: | http://hl7.org/fhir/v2/0425
Value Set URL: | http://hl7.org/fhir/ValueSet/v2-0425
OID: | ??
CodeSystem Resource | XML / JSON
ValueSet Resource | XML / JSON

This value set is used in the following places:

* This value set is the designated 'entire code system' value set for v2 Newborn Code

4.2.13.425.1 Code System Content

Newborn Code

Code | Description | Deutsch (German) | Nederlands (Dutch) | Comment | Version
1 | Born in facility | in der Klinik | Geboren in instelling | | added v2.4
2 | Transfer in | | Overplaatsing naar binnen | | added v2.4
3 | Born en route | unterwegs | Onderweg geboren | | added v2.4
4 | Other | sonstiger Ort | Anders | | added v2.4
5 | Born at home | zuhause | Thuisgeboren | | added v2.4

4.2.13.426 HL7 Version 2 Table 0426

URL: https://hl7.org/fhir/STU3/v2/0426/index.html

This page is part of the FHIR Specification (v3.0.2: STU 3). The current version which supercedes this version is 4.0.1. For a full list of available versions, see the Directory of published versions

Vocabulary Work Group | Maturity Level: N/A | External | Use Context: Any

This is a table defined as part of HL7 v2 . Related FHIR content: v2 Blood Product Code.

Summary

Name: | v2 Blood Product Code
Definition: | FHIR Value set/code system definition for HL7 v2 table 0426 (Blood Product Code)
Code System URL: | http://hl7.org/fhir/v2/0426
Value Set URL: | http://hl7.org/fhir/ValueSet/v2-0426
OID: | ??
CodeSystem Resource | XML / JSON
ValueSet Resource | XML / JSON

This value set is used in the following places:

* This value set is the designated 'entire code system' value set for v2 Blood Product Code

4.2.13.426.1 Code System Content

Blood Product Code

Code | Description | Comment | Version
CRYO | Cryoprecipitated AHF | | added v2.4
CRYOP | Pooled Cryoprecipitate | | added v2.4
FFP | Fresh Frozen Plasma | | added v2.4
FFPTH | Fresh Frozen Plasma - Thawed | | added v2.4
PC | Packed Cells | | added v2.4
PCA | Autologous Packed Cells | | added v2.4
PCNEO | Packed Cells - Neonatal | | added v2.4
PCW | Washed Packed Cells | | added v2.4
PLT | Platelet Concentrate | | added v2.4
PLTNEO | Reduced Volume Platelets | | added v2.4
PLTP | Pooled Platelets | | added v2.4
PLTPH | Platelet Pheresis | | added v2.4
PLTPHLR | Leukoreduced Platelet Pheresis | | added v2.4
RWB | Reconstituted Whole Blood | | added v2.4
WBA | Autologous Whole Blood | | added v2.4

4.2.13.427 HL7 Version 2 Table 0427

URL: https://hl7.org/fhir/STU3/v2/0427/index.html

This page is part of the FHIR Specification (v3.0.2: STU 3). The current version which supercedes this version is 4.0.1. For a full list of available versions, see the Directory of published versions

Vocabulary Work Group | Maturity Level: N/A | External | Use Context: Any

This is a table defined as part of HL7 v2 . Related FHIR content: v2 Risk Management Incident Code.

Summary

Name: | v2 Risk Management Incident Code
Definition: | FHIR Value set/code system definition for HL7 v2 table 0427 (Risk Management Incident Code)
Code System URL: | http://hl7.org/fhir/v2/0427
Value Set URL: | http://hl7.org/fhir/ValueSet/v2-0427
OID: | ??
CodeSystem Resource | XML / JSON
ValueSet Resource | XML / JSON

This value set is used in the following places:

* This value set is the designated 'entire code system' value set for v2 Risk Management Incident Code

4.2.13.427.1 Code System Content

Risk Management Incident Code

Code | Description | Nederlands (Dutch) | Comment | Version
B | Body fluid exposure | | | added v2.4
C | Contaminated Substance | | | added v2.4
D | Diet Errors | | | added v2.4
E | Equipment problem | | | added v2.4
F | Patient fell (not from bed) | | | added v2.4
H | Patient fell from bed | | | added v2.4
I | Infusion error | | | added v2.4
J | Foreign object left during surgery | | | added v2.4
K | Sterile precaution violated | | | added v2.4
O | Other | Anders | | added v2.4

P | Procedure error | | | added v2.4
R | Pharmaceutical error | | | added v2.4
S | Suicide Attempt | | | added v2.4
T | Transfusion error | | | added v2.4

4.2.13.428 HL7 Version 2 Table 0428

URL: https://hl7.org/fhir/STU3/v2/0428/index.html

This page is part of the FHIR Specification (v3.0.2: STU 3). The current version which supercedes this version is 4.0.1. For a full list of available versions, see the Directory of published versions

Vocabulary Work Group | Maturity Level: N/A | External | Use Context: Any

This is a table defined as part of HL7 v2 . Related FHIR content: v2 Incident Type Code.

Summary

Name: | v2 Incident Type Code
Definition: | FHIR Value set/code system definition for HL7 v2 table 0428 (Incident Type Code)
Code System URL: | http://hl7.org/fhir/v2/0428
Value Set URL: | http://hl7.org/fhir/ValueSet/v2-0428
OID: | ??
CodeSystem Resource | XML / JSON
ValueSet Resource | XML / JSON

This value set is used in the following places:

* This value set is the designated 'entire code system' value set for v2 Incident Type Code

4.2.13.428.1 Code System Content

Incident Type Code

Code | Description | Nederlands (Dutch) | Comment | Version
O | Other | Anders | | added v2.4
P | Preventable | Vermijdbaar | | added v2.4
U | User Error | Gebruikersfout | | added v2.4

4.2.13.429 HL7 Version 2 Table 0429

URL: https://hl7.org/fhir/STU3/v2/0429/index.html

This page is part of the FHIR Specification (v3.0.2: STU 3). The current version which supercedes this version is 4.0.1. For a full list of available versions, see the Directory of published versions

Vocabulary Work Group | Maturity Level: N/A | External | Use Context: Any

This is a table defined as part of HL7 v2 . Related FHIR content: v2 Production Class Code.

Summary

Name: | v2 Production Class Code
Definition: | FHIR Value set/code system definition for HL7 v2 table 0429 (Production Class Code)
Code System URL: | http://hl7.org/fhir/v2/0429
Value Set URL: | http://hl7.org/fhir/ValueSet/v2-0429
OID: | ??
CodeSystem Resource | XML / JSON
ValueSet Resource | XML / JSON

This value set is used in the following places:

* This value set is the designated 'entire code system' value set for v2 Production Class Code

4.2.13.429.1 Code System Content

Production Class Code

Code | Description | Nederlands (Dutch) | Comment | Version
BR | Breeding/genetic stock | Fokken/genetische voorraad | | added v2.4
DA | Dairy | Melkproduct | | added v2.4
DR | Draft | | | added v2.4
DU | Dual Purpose | Meervoudig doel | | added v2.4
LY | Layer, Includes Multiplier flocks | | | added v2.4
MT | Meat | Vlees | | added v2.4
NA | Not Applicable | Niet van toepassing | | added v2.4
OT | Other | Anders | | added v2.4
PL | Pleasure | Hobby | | added v2.4
RA | Racing | Racen | | added v2.4
SH | Show | Show | | added v2.4
U | Unknown | Onbekend | | added v2.4

4.2.13.430 HL7 Version 2 Table 0430

URL: https://hl7.org/fhir/STU3/v2/0430/index.html

This page is part of the FHIR Specification (v3.0.2: STU 3). The current version which supercedes this version is 4.0.1. For a full list of available versions, see the Directory of published versions

Vocabulary Work Group | Maturity Level: N/A | External | Use Context: Any

This is a table defined as part of HL7 v2 . Related FHIR content: v2 Mode of Arrival Code.

Summary

Name: | v2 Mode of Arrival Code
Definition: | FHIR Value set/code system definition for HL7 v2 table 0430 (Mode of Arrival Code)
Code System URL: | http://hl7.org/fhir/v2/0430
Value Set URL: | http://hl7.org/fhir/ValueSet/v2-0430
OID: | ??
CodeSystem Resource | XML / JSON
ValueSet Resource | XML / JSON

This value set is used in the following places:

* This value set is the designated 'entire code system' value set for v2 Mode of Arrival Code

* Extension http://hl7.org/fhir/StructureDefinition/encounter-modeOfArrival: modeOfArrival ((Example))

4.2.13.430.1 Code System Content

Mode of Arrival Code

Code	Description	Deutsch (German)	Nederlands (Dutch)	Comment	Version
A	Ambulance	Krankenwagen	Ambulance		added v2.4
C	Car	Auto	Auto		added v2.4
F	On foot	zu Fuß	Te voet		added v2.4
H	Helicopter	Helicopter	Helicopter		added v2.4
O	Other	andere	Anders		added v2.4
P	Public Transport	öffentliche Verkehrsmittel	Openbaar vervoer		added v2.4
U	Unknown	unbekannt	Onbekend		added v2.4

4.2.13.431 HL7 Version 2 Table 0431

URL: https://hl7.org/fhir/STU3/v2/0431/index.html

This page is part of the FHIR Specification (v3.0.2: STU 3). The current version which supercedes this version is 4.0.1. For a full list of available versions, see the Directory of published versions

Vocabulary Work Group | Maturity Level: N/A | External | Use Context: Any

This is a table defined as part of HL7 v2 . Related FHIR content: v2 Recreational Drug Use Code.

Summary

Name: | v2 Recreational Drug Use Code
Definition: | FHIR Value set/code system definition for HL7 v2 table 0431 (Recreational Drug Use Code)
Code System URL: | http://hl7.org/fhir/v2/0431
Value Set URL: | http://hl7.org/fhir/ValueSet/v2-0431
OID: | ??
CodeSystem Resource | XML / JSON
ValueSet Resource | XML / JSON

This value set is used in the following places:

* This value set is the designated 'entire code system' value set for v2 Recreational Drug Use Code

4.2.13.431.1 Code System Content

Recreational Drug Use Code

Code	Description	Deutsch (German)	Nederlands (Dutch)	Comment	Version
A	Alcohol	Alkohol	Alcohol		added v2.4
C	Tobacco - chewed	Tabak - gekaut	Tabak - gekauwd		added v2.4
K	Kava	Kava	Kava		added v2.4
M	Marijuana	Marihuana	Marihuana		added v2.4
O	Other	andere	Anders		added v2.4
T	Tobacco - smoked	Tabak - geraucht	Tabak - gerookt		added v2.4
U	Unknown	unbekannt	Onbekend		added v2.4

4.2.13.432 HL7 Version 2 Table 0432

URL: https://hl7.org/fhir/STU3/v2/0432/index.html

This page is part of the FHIR Specification (v3.0.2: STU 3). The current version which supercedes this version is 4.0.1. For a full list of available versions, see the Directory of published versions

Vocabulary Work Group | Maturity Level: N/A | External | Use Context: Any

This is a table defined as part of HL7 v2 . Related FHIR content: v2 Admission Level of Care Code.

Summary

Name: | v2 Admission Level of Care Code
Definition: | FHIR Value set/code system definition for HL7 v2 table 0432 (Admission Level of Care Code)
Code System URL: | http://hl7.org/fhir/v2/0432
Value Set URL: | http://hl7.org/fhir/ValueSet/v2-0432
OID: | ??
CodeSystem Resource | XML / JSON
ValueSet Resource | XML / JSON

This value set is used in the following places:

* This value set is the designated 'entire code system' value set for v2 Admission Level of Care Code

4.2.13.432.1 Code System Content

Admission Level of Care Code

Code | Description | Deutsch (German) | Nederlands (Dutch) | Comment | Version
AC | Acute | akut | Acuut | | added v2.4
CH | Chronic | chronisch | Chronisch | | added v2.4
CO | Comatose | komatös | Comateus | | added v2.4
CR | Critical | kritisch | Kritiek | | added v2.4
IM | Improved | verbessert | Verbeterd | | added v2.4
MO | Moribund | | Stervende | | added v2.4

4.2.13.433 HL7 Version 2 Table 0433

URL: https://hl7.org/fhir/STU3/v2/0433/index.html

This page is part of the FHIR Specification (v3.0.2: STU 3). The current version which supercedes this version is 4.0.1. For a full list of available versions, see the Directory of published versions

Vocabulary Work Group | Maturity Level: N/A | External | Use Context: Any

This is a table defined as part of HL7 v2 . Related FHIR content: v2 Precaution Code.

Summary

Name: | v2 Precaution Code
Definition: | FHIR Value set/code system definition for HL7 v2 table 0433 (Precaution Code)
Code System URL: | http://hl7.org/fhir/v2/0433
Value Set URL: | http://hl7.org/fhir/ValueSet/v2-0433
OID: | ??
CodeSystem Resource | XML / JSON
ValueSet Resource | XML / JSON

This value set is used in the following places:

* This value set is the designated 'entire code system' value set for v2 Precaution Code

4.2.13.433.1 Code System Content

Precaution Code

Code | Description | Deutsch (German) | Nederlands (Dutch) | Comment | Version
A | Aggressive | agressiv | Aggressief | | added v2.4
B | Blind | blind | Blind | | added v2.4
C | Confused | konfus | Verward | | added v2.4
D | Deaf | taub | Doof | | added v2.4
I | On IV | | Aan infuus | | added v2.4
N | "No-code" (i.e. Do not resuscitate) | | "Geen-code" (bijv. niet reanimeren) | | added v2.4
O | Other | sonstiges | Anders | | added v2.4
P | Paraplegic | | Dwarslaesie | | added v2.4
U | Unknown | unbekannt | Onbekend | | added v2.4

4.2.13.434 HL7 Version 2 Table 0434

URL: https://hl7.org/fhir/STU3/v2/0434/index.html

This page is part of the FHIR Specification (v3.0.2: STU 3). The current version which supercedes this version is 4.0.1. For a full list of available versions, see the Directory of published versions

Vocabulary Work Group | Maturity Level: N/A | External | Use Context: Any

This is a table defined as part of HL7 v2 . Related FHIR content: v2 Patient Condition Code.

Summary

Name: | v2 Patient Condition Code
Definition: | FHIR Value set/code system definition for HL7 v2 table 0434 (Patient Condition Code)

Code System URL: | http://hl7.org/fhir/v2/0434
Value Set URL: | http://hl7.org/fhir/ValueSet/v2-0434
OID: | ??
CodeSystem Resource | XML / JSON
ValueSet Resource | XML / JSON

This value set is used in the following places:

* This value set is the designated 'entire code system' value set for v2 Patient Condition Code

4.2.13.434.1 Code System Content

Patient Condition Code

Code | Description | Deutsch (German) | Nederlands (Dutch) | Comment | Version
A | Satisfactory | zufriedenstellend | Goed | | added v2.4
C | Critical | kritisch | Kritiek | | added v2.4
O | Other | sonstiges | Anders | | added v2.4
P | Poor | schlecht | Matig | | added v2.4
S | Stable | stabil | Stabiel | | added v2.4
U | Unknown | unbekannt | Onbekend | | added v2.4

4.2.13.435 HL7 Version 2 Table 0435

URL: https://hl7.org/fhir/STU3/v2/0435/index.html

This page is part of the FHIR Specification (v3.0.2: STU 3). The current version which supercedes this version is 4.0.1. For a full list of available versions, see the Directory of published versions

Vocabulary Work Group | Maturity Level: N/A | External | Use Context: Any

This is a table defined as part of HL7 v2 . Related FHIR content: v2 Advance Directive Code.

Summary

Name: | v2 Advance Directive Code
Definition: | FHIR Value set/code system definition for HL7 v2 table 0435 (Advance Directive Code)
Code System URL: | http://hl7.org/fhir/v2/0435
Value Set URL: | http://hl7.org/fhir/ValueSet/v2-0435
OID: | ??
CodeSystem Resource | XML / JSON
ValueSet Resource | XML / JSON

This value set is used in the following places:

* This value set is the designated 'entire code system' value set for v2 Advance Directive Code

4.2.13.435.1 Code System Content

Advance Directive Code

Code | Description | Nederlands (Dutch) | Comment | Version
DNR | Do not resuscitate | Niet reanimeren | | added v2.4
N | No directive | Geen wilsverklaring | | added v2.6

4.2.13.436 HL7 Version 2 Table 0436

URL: https://hl7.org/fhir/STU3/v2/0436/index.html

This page is part of the FHIR Specification (v3.0.2: STU 3). The current version which supercedes this version is 4.0.1. For a full list of available versions, see the Directory of published versions

Vocabulary Work Group | Maturity Level: N/A | External | Use Context: Any

This is a table defined as part of HL7 v2 . Related FHIR content: v2 Sensitivity to Causative Agent Code.

Summary

Name: | v2 Sensitivity to Causative Agent Code
Definition: | FHIR Value set/code system definition for HL7 v2 table 0436 (Sensitivity to Causative Agent Code)
Code System URL: | http://hl7.org/fhir/v2/0436
Value Set URL: | http://hl7.org/fhir/ValueSet/v2-0436
OID: | ??
CodeSystem Resource | XML / JSON
ValueSet Resource | XML / JSON

This value set is used in the following places:

* This value set is the designated 'entire code system' value set for v2 Sensitivity to Causative Agent Code

4.2.13.436.1 Code System Content

Sensitivity to Causative Agent Code

Code | Description | Nederlands (Dutch) | Comment | Version

AD | Adverse Reaction (Not otherwise classified) | Overgevoeligheidsreactie (niet verder gedefinieerd) | | added v2.4
AL | Allergy | Allergie | | added v2.4
CT | Contraindication | Contra-indicatie | | added v2.4
IN | Intolerance | Intolerantie | | added v2.4
SE | Side Effect | Bijwerking | | added v2.7

4.2.13.437 HL7 Version 2 Table 0437

URL: https://hl7.org/fhir/STU3/v2/0437/index.html

This page is part of the FHIR Specification (v3.0.2: STU 3). The current version which supercedes this version is 4.0.1. For a full list of available versions, see the Directory of published versions

Vocabulary Work Group | Maturity Level: N/A | External | Use Context: Any

This is a table defined as part of HL7 v2 . Related FHIR content: v2 Alert Device Code.

Summary

Name: | v2 Alert Device Code
Definition: | FHIR Value set/code system definition for HL7 v2 table 0437 (Alert Device Code)
Code System URL: | http://hl7.org/fhir/v2/0437
Value Set URL: | http://hl7.org/fhir/ValueSet/v2-0437
OID: | ??
CodeSystem Resource | XML / JSON
ValueSet Resource | XML / JSON

This value set is used in the following places:

* This value set is the designated 'entire code system' value set for v2 Alert Device Code

4.2.13.437.1 Code System Content

Alert Device Code

Code | Description | Deutsch (German) | Nederlands (Dutch) | Comment | Version
B | Bracelet | Armband | Armband | | added v2.4
N | Necklace | Kette | Halsketting | | added v2.4
W | Wallet Card | | Portemonnee kaart | | added v2.4

4.2.13.438 HL7 Version 2 Table 0438

URL: https://hl7.org/fhir/STU3/v2/0438/index.html

This page is part of the FHIR Specification (v3.0.2: STU 3). The current version which supercedes this version is 4.0.1. For a full list of available versions, see the Directory of published versions

Vocabulary Work Group | Maturity Level: N/A | External | Use Context: Any

This is a table defined as part of HL7 v2 . Related FHIR content: v2 Allergy Clinical Status.

Summary

Name: | v2 Allergy Clinical Status
Definition: | FHIR Value set/code system definition for HL7 v2 table 0438 (Allergy Clinical Status)
Code System URL: | http://hl7.org/fhir/v2/0438
Value Set URL: | http://hl7.org/fhir/ValueSet/v2-0438
OID: | ??
CodeSystem Resource | XML / JSON
ValueSet Resource | XML / JSON

This value set is used in the following places:

* This value set is the designated 'entire code system' value set for v2 Allergy Clinical Status

4.2.13.438.1 Code System Content

Allergy Clinical Status

Code | Description | Nederlands (Dutch) | Comment | Version
C | Confirmed or verified | Bevestigd of gecontroleerd | | added v2.4
D | Doubt raised | Twijfelachtig | | added v2.4
E | Erroneous | Foutief | | added v2.4
I | Confirmed but inactive | Bevestigd maar inactief | | added v2.4
P | Pending | In bewerking | | added v2.4
S | Suspect | Verdacht | | added v2.4
U | Unconfirmed | Niet-bevestigd | | added v2.4

4.2.13.440 HL7 Version 2 Table 0440

URL: https://hl7.org/fhir/STU3/v2/0440/index.html

This page is part of the FHIR Specification (v3.0.2: STU 3). The current version which supercedes this version is 4.0.1. For a full list of available versions, see the Directory of published versions

Vocabulary Work Group | Maturity Level: N/A | External | Use Context: Any

This is a table defined as part of HL7 v2 . Related FHIR content: v2 Data Types.

Summary

Name: | v2 Data Types
Definition: | FHIR Value set/code system definition for HL7 v2 table 0440 (Data Types)
Code System URL: | http://hl7.org/fhir/v2/0440
Value Set URL: | http://hl7.org/fhir/ValueSet/v2-0440
OID: | ??
CodeSystem Resource | XML / JSON
ValueSet Resource | XML / JSON

This value set is used in the following places:

* This value set is the designated 'entire code system' value set for v2 Data Types

4.2.13.440.1 Code System Content

Data Types

Code | Description | Nederlands (Dutch) | Comment | Version
AD | Address | Adres | Replaced by XAD as of v 2.3 | added v2.4
AUI | Authorization information | Autorisatie informatie | Replaces the CM data type used in sections 6.5.6.14 IN1-14, as of v 2.5. | added v2.5
CCD | Charge code and date | Facturatiecode en datum | Replaces the CM data type used in section 4.5.2.1 BLG-1, as of v 2.5. | added v2.5
CCP | Channel calibration parameters | Kanaalcalibratie parameters | Replaces the CM data type used in 7.14.1.5 OBX-5.3 where OBX-5Observation value (*) is data type CD as of v 2.5. | added v2.5
CD | Channel definition | Kanaaldefinitie | For waveform data only;. | added v2.4
CE | Coded element | Gecodeerd element | WITHDRAWN | added v2.4
CF | Coded element with formatted values | Gecodeerd element met waarden met opmaak | 65536 | added v2.4
CK | Composite ID with check digit | Samengesteld ID met controlegetal | WITHDRAWN | added v2.4
CM | Composite | Samengesteld | WITHDRAWN Replaced by numerous new unambiguous data types in v 2.5 | added v2.4
CN | Composite ID number and name | Samengesteld ID en naam | WITHDRAWN. Replaced by XCN as of v 2.3 | added v2.4
CNE | Coded with no exceptions | Gecodeerd zonder uitzonderingen | 705 | added v2.4
CNN | Composite ID number and name simplified | Samengesteld ID en naam vereenvoudigd | Restores the original data type CN as was initially implementable in the CM used in sections 4.5.3.32 and 7.4.1.32-(OBR-32), 4.5.3.33 and 7.4.1.33 - (OBR-33) 4.5.3.34 and 7.4.1.34 - (OBR-34) 4.5.3.35 and 7.4.1.35 - (OBR-35). Components 7 and 8, however, h | added v2.7
CNS | Composite ID number and name simplified | | deprecated | added v2.5, removed after v2.6
CP | Composite price | Samengestelde prijs | . | added v2.4
CQ | Composite quantity with units | Samengestelde hoeveelheid met eenheden | CQ cannot be legally expressed when embedded within another data type. Its use is constrained to a segment field. | added v2.4
CSU | Channel sensitivity and units | Kanaal gevoeligheid en eenheden | Replaces the CM data type used in 7.14.1.5 OBX-5.3 where OBX-5Observation value (*) is data type CD as of v 2.5. | added v2.5
CWE | Coded with exceptions | Gecodeerd met uitzonderingen | 705 | added v2.4
CX | Extended composite ID with check digit | Uitgebreid samengesteld ID met controlegetal | 1913 | added v2.4
DDI | Daily deductible information | Dagelijks aftrekbaar informatie | Replaces the CM data type used in section 6.5.7.30 IN2-30, as of v 2.5. | added v2.5
DIN | Date and institution name | Datum en naam instelling | Replaces the CM data type used in sections 15.4.6.12 STF-12 and 15.4.6.14 STF-13, as of v 2.5. | added v2.5
DLD | Discharge to location and date | Ontslag naar locatie en datum | Replaces the CM data type used in section 8.8.4.9 - OM2-9, as of v 2.5 | added v2.5
DLN | Driver's license number | Rijbewijsnummer | 66 | added v2.4
DLT | Delta | Delta | 45 | added v2.5
DR | Date/time range | Datum/tijd bereik | 53 | added v2.4
DT | Date | Datum | 8 | added v2.4
DTM | Date/time | Datum/tijd | 24 | added v2.5
DTN | Day type and number | Dag type en nummer | Replaces the CM data type used in section 6.5.8.11 IN3-11, as of v 2.5. | added v2.5
ED | Encapsulated data | Ingekapselde gegevens | Supports ASCII MIME-encoding of binary data. | added v2.4
EI | Entity identifier | Entiteit identificatie | 427 | added v2.4
EIP | Entity identifier pair | Entiteit identificatie paar | Replaces the CM data type used in sections 4.5.1.8 - ORC-8, 4.5.3.29 - OBR-29, 7.3.1.29 - OBR-29, as of v 2.5. | added v2.5
ELD | Error location and description | Foutlocatie en omschrijving | WITHDRAWN | added v2.5
ERL | Error location | Foutlocatie | 18 | added v2.5
FC | Financial class | Financiële klasse | 47 | added v2.4
FN | Family name | Achternaam | Appears ONLY in the PPN, XCN, and XPN. | added v2.4
FT | Formatted text | Tekst met opmaak | 65536 | added v2.4
GTS | General timing specification | Algemene specificatie van tijd | 199 | added v2.5
HD | Hierarchic designator | Hiërarchische aanduiding | 227 | added v2.4
ICD | Insurance certification definition | Verzekeringcertificatie definitie | Replaces the CM data type used in section 6.5.8.20 IN3-20, as of v 2.5. | added v2.5
ID | Coded values for HL7 tables | Gecodeerd waarde voor HL7-tabellen | Variable | added v2.4
IS | Coded value for user-defined tables | Gecodeerde waarde voor gebruiker-gedefinieerde tabellen | 20 | added v2.4
JCC | Job code/class | Baan code/klassificatie | 292 | added v2.4

LA1 | Location with address variation 1 | Locatie met adres variatie 1 | Replaces the CM data type used in 4.14.1.8 RXO-8 and 4.14.4.8 RXE-8 as of v 2.5. Retained for backward compatibility only as of v 2.5 | added v2.5

LA2 | Location with address variation 2 | Locatie met adres variatie 2 | Replaces the CM data type used in 4.14.5.13 RXD-13, 4.14.6.11 RXG-11 and 4.14.7.11 RXA-11 as of v 2.5. Retained for backward compatibility only as of v 2.5, | added v2.5

MA | Multiplexed array | Multiplexed arred | For waveform data only | added v2.4

MO | Money | | 20 | added v2.4

MOC | Money and charge code | Geld en facturatiecode | Replaces the CM data type used in sections 4.5.3.23 OBR-23 and 7.4.1.23- OBR-23 as of v 2.5. | added v2.5

MOP | Money or percentage | Geld of percentage | Replaces the CM data type used in section 6.5.8.5 IN3-5, as of v 2.5. This data type is restricted to this field. | added v2.5

MSG | Message type | Berichttype | Replaces the CM data type used in 2.16.9.9 MSH-9 as of v 2.5. | added v2.5

NA | Numeric array | Numerieke array | For waveform data only | added v2.4

NDL | Name with date and location | Naam met datum en locatie | Replaces the CM data type used in sections 4.5.3.32 and 7.4.1.32-(OBR-32) , 4.5.3.33 and 7.4.1.33 - (OBR-33) 4.5.3.34 and 7.4.1.34 - (OBR-34) 4.5.3.35 and 7.4.1.35 - (OBR-35) as of v 2.5. | added v2.5

NM | Numeric | Numeriek | 16 | added v2.4

NR | Numeric range | Numeriek bereik | Replaces the CM data type used in sections 8.8.4.6.1- OM2-6.1, 8.8.4.6.3- OM2-6.3and 8.8.4.6.4- OM2-6.4, as of v 2.5. | added v2.5

OCD | Occurrence code and date | Gebeurtenis code en datum | Replaces the CM data type used in sections 6.5.10.10 UB1-16 and 6.5.11.7 UB2-7, as of v 2.5. | added v2.5

OSD | Order sequence definition | Aanvraagvolgorde definitie | WITHDRAWN | added v2.5

OSP | Occurrence span code and date | Gebeurtenis spanne code en datum | Replaces the CM data type used in section 6.5.11.8 UB2-8, as of v 2.5. | added v2.5

PIP | Practitioner institutional privileges | Zorgverlener instellingsprivileges | Replaces the CM data type used in 15.4.5.7 PRA-7 as of v 2.5. | added v2.5

PL | Person location | Persoon locatie | 1230 | added v2.4

PLN | Practitioner license or other ID number | Zorgverlener licentie of ander ID | Replaces the CM data type used in 15.4.5.6 PRA-6, 11.6.3.7 PRD-7 and 11.6.4.7 CTD-7 as of v 2.5. | added v2.5

PN | Person name | Persoonsnaam | WITHDRAWN | added v2.4

PPN | Performing person time stamp | Uivoerende persoon en tijdstip | equivalent of an XCN joined with a TS | added v2.4

PRL | Parent result link | Parent resultaat link | Replaces the CM data type used in sections 4.5.3.26 - OBR-26 and 7.4.1.26 - OBR-26 as of v 2.5. | added v2.5

PT | Processing type | Verwerkingstype | 3 | added v2.4

PTA | Policy type and amount | Polistype en hoeveelheid | Replaces the CM data type used in section 6.5.7.29 IN2-29, as of v 2.5. | added v2.5

QIP | Query input parameter list | Query invoerparameterlijst | 212 | added v2.4

QSC | Query selection criteria | Queryselectie criteria | 219 | added v2.4

RCD | Row column definition | Rij-kolom definitie | 19 | added v2.4

RFR | Reference range | Referentiewaardenbereik | Replaces the CM data type used in sections 8.8.4.6 - OM2-6, 8.8.4.7 - OM2-7 and8.8.4.8 - OM2-8 as of v 2.5. | added v2.5

RI | Repeat interval | Herhaalinterval | 206 | added v2.4

RMC | Room coverage | Kamerdekking | Replaces the CM data type used in section 6.5.7.28 IN2-28, as of v 2.5. | added v2.5

RP | Reference pointer | Verwijzing | 273 | added v2.4

RPT | Repeat pattern | Herhaalpatroon | 984 | added v2.5

SAD | Street Address | Straatadres | Appears ONLY in the XAD data type. | added v2.4

SCV | Scheduling class value pair | Planningsklasse waardepaar | For scheduling data only. See Chapter 10 | added v2.4

SI | Sequence ID | Sequence ID | 4 | added v2.4

SN | Structured numeric | Gestructureerde numerieke waarde | 36 | added v2.4

SNM | String of telephone number digits | String met telefoonnummercijfers | Definition: a string whose characters are limited to "+" and the decimal digits 0 through 9. As a string, leading zeros are always considered significant. Maximum length: Not specified for the type. May be specified in the context of use. | added v2.7

SPD | Specialty description | Specialisme omschrijving | Replaces the CM data type used in 15.4.5.5 PRA-5 as of v 2.5. | added v2.5

SPS | Specimen source | Monster bron | WITHDRAWN | added v2.5

SRT | Sort order | Sorteervolgorde | 15 | added v2.4

ST | String data | Platte tekst | 199 | added v2.4

TM | Time | Tijd | 16 | added v2.4

TN | Telephone number | Telefoonnummer | WITHDRAWN | added v2.4

TQ | Timing/quantity | Timing/hoeveelheid | WITHDRAWN | added v2.4

TS | Time stamp | Tijdstempel | WITHDRAWN | added v2.4

TX | Text data | Tekstuele gegevens | 65536 | added v2.4

UVC | UB value code and amount | UB waardecode en hoeveelheid | Replaces the CM data type used in sections 6.5.10.10 UB1-10 and 6.5.11.6 UB2-6, as of v 2.5. | added v2.5

VH | Visiting hours | Bezoekuren | 41 | added v2.4

VID | Version identifier | Versie identificatie | 973 | added v2.4

VR | Value range | Waardebereik | Replaces the CM data type used in 5.10.5.3.11 QRD-11 as of v 2.5. | added v2.5

WVI | Channel Identifier | Kanaal identificatie | Replaces the CM data type used in 7.14.1.3.1 OBX-5.1 where OBX-5 Observation value (*) is data type CD as of v 2.5. | added v2.5

WVS | Waveform source | Waveform bron | Replaces the CM data type used in 7.14.1.4 OBX-5.2 where OBX-5 Observation value (*) is data type CD as of v 2.5. | added v2.5

XAD | Extended address | Uitgebreid adres | Replaces AD as of v 2.3 | added v2.4

XCN | Extended composite ID number and name for persons | Uitgebreide samengestelde ID en naam voor personen | Replaces CN as of v 2.3 | added v2.4

XON | Extended composite name and ID number for organizations | Uitgebreide samengestelde ID en naam voor organisaties | 567 | added v2.4

XPN | Extended person name | Uitgebreide persoonsnaam | Replaces PN as of v 2.3. | added v2.4

XTN | Extended telecommunications number | Uitgebreid telecommunicatienummer | Replaces TN as of v 2.3 | added v2.4

4.2.13.441 HL7 Version 2 Table 0441

URL: https://hl7.org/fhir/STU3/v2/0441/index.html

This page is part of the FHIR Specification (v3.0.2: STU 3). The current version which supercedes this version is 4.0.1. For a full list of available versions, see the Directory of published versions

Vocabulary Work Group | Maturity Level: N/A | External | Use Context: Any

This is a table defined as part of HL7 v2 . Related FHIR content: v2 Immunization Registry Status.

Summary

Name: | v2 Immunization Registry Status
Definition: | FHIR Value set/code system definition for HL7 v2 table 0441 (Immunization Registry Status)
Code System URL: | http://hl7.org/fhir/v2/0441
Value Set URL: | http://hl7.org/fhir/ValueSet/v2-0441
OID: | ??
CodeSystem Resource | XML / JSON
ValueSet Resource | XML / JSON

This value set is used in the following places:

* This value set is the designated 'entire code system' value set for v2 Immunization Registry Status

4.2.13.441.1 Code System Content

Immunization Registry Status

Code | Description | Nederlands (Dutch) | Comment | Version
A | Active | | | added v2.4
I | Inactive | | | added v2.4
L | Inactive - Lost to follow-up (cancel contract) | | | added v2.4
M | Inactive - Moved or gone elsewhere (cancel contract) | | | added v2.4
O | Other | Anders | | added v2.4
P | Inactive - Permanently inactive (Do not reactivate or add new entries to the record) | | | added v2.4
U | Unknown | Onbekend | | added v2.4

4.2.13.442 HL7 Version 2 Table 0442

URL: https://hl7.org/fhir/STU3/v2/0442/index.html

This page is part of the FHIR Specification (v3.0.2: STU 3). The current version which supercedes this version is 4.0.1. For a full list of available versions, see the Directory of published versions

Vocabulary Work Group | Maturity Level: N/A | External | Use Context: Any

This is a table defined as part of HL7 v2 . Related FHIR content: v2 Location Service Code.

Summary

Name: | v2 Location Service Code
Definition: | FHIR Value set/code system definition for HL7 v2 table 0442 (Location Service Code)
Code System URL: | http://hl7.org/fhir/v2/0442
Value Set URL: | http://hl7.org/fhir/ValueSet/v2-0442
OID: | ??
CodeSystem Resource | XML / JSON
ValueSet Resource | XML / JSON

This value set is used in the following places:

* This value set is the designated 'entire code system' value set for v2 Location Service Code

4.2.13.442.1 Code System Content

Location Service Code

Code | Description | Comment | Version
D | Diagnostic | | added v2.4
E | Emergency Room Casualty | | added v2.4
P | Primary Care | | added v2.4
T | Therapeutic | | added v2.4

4.2.13.443 HL7 Version 2 Table 0443

URL: https://hl7.org/fhir/STU3/v2/0443/index.html

This page is part of the FHIR Specification (v3.0.2: STU 3). The current version which supercedes this version is 4.0.1. For a full list of available versions, see the Directory of published versions

Vocabulary Work Group | Maturity Level: N/A | External | Use Context: Any

This is a table defined as part of HL7 v2 . Related FHIR content: v2 Provider Role.

Summary

Name: | v2 Provider Role
Definition: | FHIR Value set/code system definition for HL7 v2 table 0443 (Provider Role)
Code System URL: | http://hl7.org/fhir/v2/0443
Value Set URL: | http://hl7.org/fhir/ValueSet/v2-0443
OID: | ??
CodeSystem Resource | XML / JSON
ValueSet Resource | XML / JSON

This value set is used in the following places:

* This value set is the designated 'entire code system' value set for v2 Provider Role

4.2.13.443.1 Code System Content

Provider Role

Code | Description | Deutsch (German) | Nederlands (Dutch) | Comment | Version
AD | Admitting | Aufnehmender Arzt | PV1-17 Admitting doctor | PV1-17 Admitting doctor | added v2.4
AI | Assistant/Alternate Interpreter | alternativer (oder Assistent des) Befundsarzt | Assistent/tweede vertaler | | added v2.6
AP | Administering Provider | | RXA-10 Administering Provider | RXA-10 Administering Provider | added v2.7
AT | Attending | Behandelnder Arzt | PV1-7 Attending doctor | PV1-7 Attending doctor | added v2.4
CLP | Collecting Provider | | OBR-10 Collector Identifier | OBR-10 Collector Identifier | added v2.7
CP | Consulting Provider | Beratender Arzt | | | added v2.4
DP | Dispensing Provider | | RXD-10 Dispensing Provider | RXD-10 Dispensing Provider | added v2.7
EP | Entering Provider (probably not the same as transcriptionist?) | | ORC-10 Entered By | ORC-10 Entered By | added v2.7
FHCP | Family Health Care Professional | Hausarzt | | | added v2.4
IP | Initiating Provider (as in action by) | | ORC-19 Action By | ORC-19 Action By | added v2.7
MDIR | Medical Director | | OBX-25 Performing Organization Medical Director | OBX-25 Performing Organization Medical Director | added v2.7
OP | Ordering Provider | | ORC-12 Ordering Provider, OBR-16 Ordering Provider, RXO-14 Ordering Provider's DEA Number, RXE-13 Ordering Provider's DEA Number, ORC-24 Ordering Provider Address | ORC-12 Ordering Provider, OBR-16 Ordering Provider, RXO-14 Ordering Provider's DEA Number, RXE-13 Ordering Provider's DEA Number, ORC-24 Ordering Provider Address | added v2.7
PH | Pharmacist (not sure how to dissect Pharmacist/Treatment Supplier's Verifier ID) | | Apotheker (onduidelijk hoe je "Pharmacist/Treatment Supplier's Verifier ID" uit elkaar haalt) | RXE-14 Pharmacist/Treatment Supplier's Verifier ID | added v2.7
PI | Primary Interpreter | Verantwortlicher Übersetzer | Primaire tolk | | added v2.6
PP | Primary Care Provider | Durchgangsarzt | Eerstelijns zorgverlener | | added v2.4
RO | Responsible Observer | | Verantwoordelijk observator | OBX-16 Responsible Observer | added v2.7
RP | Referring Provider | überweisender/einweisender Arzt | Verwijzend | PV1-8 Referring doctor | added v2.4
RT | Referred to Provider | Überweisungsempfänger | Zorgverlener naar wie is verwezen | | added v2.4
TN | Technician | MTA | Technisch personeel | | added v2.6
TR | Transcriptionist | Schreibkraft | Transscribent | | added v2.6
VP | Verifying Provider | | Controlerend | ORC-11 Verified By | added v2.7
VPS | Verifying Pharmaceutical Supplier (not sure how to dissect Pharmacist/Treatment Supplier's Verifier ID) | | Controlerend farmaceutische leverancier (onduidelijk hoe je "Pharmacist/Treatment Supplier's Verifier ID" uit elkaar haalt) | RXE-14 Pharmacist/Treatment Supplier's Verifier ID | added v2.7
VTS | Verifying Treatment Supplier (not sure how to dissect Pharmacist/Treatment Supplier's Verifier ID) | | Controlerend behandeling leverancier (onduidelijk hoe je "Pharmacist/Treatment Supplier's Verifier ID" uit elkaar haalt) | RXE-14 Pharmacist/Treatment Supplier's Verifier ID | added v2.7

4.2.13.444 HL7 Version 2 Table 0444

URL: https://hl7.org/fhir/STU3/v2/0444/index.html

This page is part of the FHIR Specification (v3.0.2: STU 3). The current version which supercedes this version is 4.0.1. For a full list of available versions, see the Directory of published versions

Vocabulary Work Group | Maturity Level: N/A | External | Use Context: Any

This is a table defined as part of HL7 v2 . Related FHIR content: v2 Name Assembly Order.

Summary

Name: | v2 Name Assembly Order
Definition: | FHIR Value set/code system definition for HL7 v2 table 0444 (Name Assembly Order)
Code System URL: | http://hl7.org/fhir/v2/0444
Value Set URL: | http://hl7.org/fhir/ValueSet/v2-0444
OID: | ??
CodeSystem Resource | XML / JSON
ValueSet Resource | XML / JSON

This value set is used in the following places:

* This value set is the designated 'entire code system' value set for v2 Name Assembly Order

4.2.13.444.1 Code System Content

Name Assembly Order

Code | Description | Deutsch (German) | Nederlands (Dutch) | Comment | Version
F | Prefix Family Middle Given Suffix | Familienname zuerst | Prefix Achternaam Middle Voornaam Suffix | | added v2.4
G | Prefix Given Middle Family Suffix | Familienname hinten | Prefix Voornaam Middle Achternaam Suffix | | added v2.4

4.2.13.445 HL7 Version 2 Table 0445

URL: https://hl7.org/fhir/STU3/v2/0445/index.html

This page is part of the FHIR Specification (v3.0.2: STU 3). The current version which supercedes this version is 4.0.1. For a full list of available versions, see the Directory of published versions

Vocabulary Work Group | Maturity Level: N/A | External | Use Context: Any

This is a table defined as part of HL7 v2 . Related FHIR content: v2 Identity Reliability Code.

Summary

Name: | v2 Identity Reliability Code
Definition: | FHIR Value set/code system definition for HL7 v2 table 0445 (Identity Reliability Code)
Code System URL: | http://hl7.org/fhir/v2/0445
Value Set URL: | http://hl7.org/fhir/ValueSet/v2-0445
OID: | ??
CodeSystem Resource | XML / JSON
ValueSet Resource | XML / JSON

This value set is used in the following places:

* This value set is the designated 'entire code system' value set for v2 Identity Reliability Code

4.2.13.445.1 Code System Content

Identity Reliability Code

Code | Description | Comment | Version
AL | Patient/Person Name is an Alias | | added v2.4
UA | Unknown/Default Address | | added v2.4
UD | Unknown/Default Date of Birth | | added v2.4
US | Unknown/Default Social Security Number | | added v2.4

4.2.13.450 HL7 Version 2 Table 0450

URL: https://hl7.org/fhir/STU3/v2/0450/index.html

This page is part of the FHIR Specification (v3.0.2: STU 3). The current version which supercedes this version is 4.0.1. For a full list of available versions, see the Directory of published versions

Vocabulary Work Group | Maturity Level: N/A | External | Use Context: Any

This is a table defined as part of HL7 v2 . Related FHIR content: v2 Event Type.

Summary

Name: | v2 Event Type
Definition: | FHIR Value set/code system definition for HL7 v2 table 0450 (Event Type)
Code System URL: | http://hl7.org/fhir/v2/0450
Value Set URL: | http://hl7.org/fhir/ValueSet/v2-0450
OID: | ??
CodeSystem Resource | XML / JSON
ValueSet Resource | XML / JSON

This value set is used in the following places:

* This value set is the designated 'entire code system' value set for v2 Event Type

4.2.13.450.1 Code System Content

Event Type

Code | Description | Comment | Version
LOG | Log Event | | added v2.4
SER | Service Event | | added v2.4

4.2.13.455 HL7 Version 2 Table 0455

URL: https://hl7.org/fhir/STU3/v2/0455/index.html

This page is part of the FHIR Specification (v3.0.2: STU 3). The current version which supercedes this version is 4.0.1. For a full list of available versions, see the Directory of published versions

Vocabulary Work Group | Maturity Level: N/A | External | Use Context: Any

This is a table defined as part of HL7 v2 . Related FHIR content: v2 Type of Bill Code.

Summary

Name: | v2 Type of Bill Code
Definition: | FHIR Value set/code system definition for HL7 v2 table 0455 (Type of Bill Code)
Code System URL: | http://hl7.org/fhir/v2/0455
Value Set URL: | http://hl7.org/fhir/ValueSet/v2-0455
OID: | ??

CodeSystem Resource | XML / JSON
ValueSet Resource | XML / JSON

This value set is used in the following places:

* This value set is the designated 'entire code system' value set for v2 Type of Bill Code

4.2.13.455.1 Code System Content

Type of Bill Code

Code | Description | Deutsch (German) | Nederlands (Dutch) | Comment | Version
... | No suggested values defined | keine Werte vorgeschlagen | geen voorgestelde waarden | | added v2.4
131 | Hospital - Outpatient - Admit thru Discharge Claim | | | deprecated | added v2.4, removed after v2.4
141 | Hospital - Other - Admit thru Discharge Claim | | | deprecated | added v2.4, removed after v2.4

4.2.13.456 HL7 Version 2 Table 0456

URL: https://hl7.org/fhir/STU3/v2/0456/index.html

This page is part of the FHIR Specification (v3.0.2: STU 3). The current version which supercedes this version is 4.0.1. For a full list of available versions, see the Directory of published versions

Vocabulary Work Group | Maturity Level: N/A | External | Use Context: Any

This is a table defined as part of HL7 v2 . Related FHIR content: v2 Revenue code.

Summary

Name: | v2 Revenue code
Definition: | FHIR Value set/code system definition for HL7 v2 table 0456 (Revenue code)
Code System URL: | http://hl7.org/fhir/v2/0456
Value Set URL: | http://hl7.org/fhir/ValueSet/v2-0456
OID: | ??
CodeSystem Resource | XML / JSON
ValueSet Resource | XML / JSON

This value set is used in the following places:

* This value set is the designated 'entire code system' value set for v2 Revenue code

4.2.13.456.1 Code System Content

Revenue code

Code | Description | Deutsch (German) | Nederlands (Dutch) | Comment | Version
... | No suggested values defined | keine Werte vorgeschlagen | geen voorgestelde waarden | | added v2.4
260 | IV Therapy | | Vruchtbaarheidstherapie | deprecated | added v2.4, removed after v2.4
280 | Oncology | | Oncologie | deprecated | added v2.4, removed after v2.4
301 | Lab/Chemistry | | Lab/chemie | deprecated | added v2.4, removed after v2.4
991 | Cafeteria /Guest Tray | | Cafetaria/gastdienblad | deprecated | added v2.4, removed after v2.4
993 | Telephone/Telegraph | | Telefoon/telegraaf | deprecated | added v2.4, removed after v2.4
994 | TV/Radio | | TV/radio | deprecated | added v2.4, removed after v2.4

4.2.13.457 HL7 Version 2 Table 0457

URL: https://hl7.org/fhir/STU3/v2/0457/index.html

This page is part of the FHIR Specification (v3.0.2: STU 3). The current version which supercedes this version is 4.0.1. For a full list of available versions, see the Directory of published versions

Vocabulary Work Group | Maturity Level: N/A | External | Use Context: Any

This is a table defined as part of HL7 v2 . Related FHIR content: v2 Overall Claim Disposition Code.

Summary

Name: | v2 Overall Claim Disposition Code
Definition: | FHIR Value set/code system definition for HL7 v2 table 0457 (Overall Claim Disposition Code)
Code System URL: | http://hl7.org/fhir/v2/0457
Value Set URL: | http://hl7.org/fhir/ValueSet/v2-0457
OID: | ??
CodeSystem Resource | XML / JSON
ValueSet Resource | XML / JSON

This value set is used in the following places:

* This value set is the designated 'entire code system' value set for v2 Overall Claim Disposition Code

4.2.13.457.1 Code System Content

Overall Claim Disposition Code

Code | Description | Comment | Version
0 | No edits present on claim | | added v2.4

1 | Only edits present are for line item denial or rejection | | added v2.4
2 | Multiple-day claim with one or more days denied or rejected | | added v2.4
3 | Claim denied, rejected, suspended or returned to provider with only post payment edits | | added v2.4
4 | Claim denied, rejected, suspended or returned to provider with only pre payment edits | | added v2.4

4.2.13.459 HL7 Version 2 Table 0459

URL: https://hl7.org/fhir/STU3/v2/0459/index.html

This page is part of the FHIR Specification (v3.0.2: STU 3). The current version which supercedes this version is 4.0.1. For a full list of available versions, see the Directory of published versions

Vocabulary Work Group | Maturity Level: N/A | External | Use Context: Any

This is a table defined as part of HL7 v2 . Related FHIR content: v2 Reimbursement Action Code.

Summary

Name: | v2 Reimbursement Action Code
Definition: | FHIR Value set/code system definition for HL7 v2 table 0459 (Reimbursement Action Code)
Code System URL: | http://hl7.org/fhir/v2/0459
Value Set URL: | http://hl7.org/fhir/ValueSet/v2-0459
OID: | ??
CodeSystem Resource | XML / JSON
ValueSet Resource | XML / JSON

This value set is used in the following places:

* This value set is the designated 'entire code system' value set for v2 Reimbursement Action Code

4.2.13.459.1 Code System Content

Reimbursement Action Code

Code | Description | Comment | Version
0 | OCE line item denial or rejection is not ignored | | added v2.4
1 | OCE line item denial or rejection is ignored | | added v2.4
2 | External line item denial. Line item is denied even if no OCE edits | | added v2.4
3 | External line item rejection. Line item is rejected even if no OCE edits | | added v2.4

4.2.13.460 HL7 Version 2 Table 0460

URL: https://hl7.org/fhir/STU3/v2/0460/index.html

This page is part of the FHIR Specification (v3.0.2: STU 3). The current version which supercedes this version is 4.0.1. For a full list of available versions, see the Directory of published versions

Vocabulary Work Group | Maturity Level: N/A | External | Use Context: Any

This is a table defined as part of HL7 v2 . Related FHIR content: v2 Denial or Rejection Code.

Summary

Name: | v2 Denial or Rejection Code
Definition: | FHIR Value set/code system definition for HL7 v2 table 0460 (Denial or Rejection Code)
Code System URL: | http://hl7.org/fhir/v2/0460
Value Set URL: | http://hl7.org/fhir/ValueSet/v2-0460
OID: | ??
CodeSystem Resource | XML / JSON
ValueSet Resource | XML / JSON

This value set is used in the following places:

* This value set is the designated 'entire code system' value set for v2 Denial or Rejection Code

4.2.13.460.1 Code System Content

Denial or Rejection Code

Code | Description | Comment | Version
0 | Line item not denied or rejected | | added v2.4
1 | Line item denied or rejected | | added v2.4
2 | Line item is on a multiple-day claim. The line item is not denied or rejected, but occurs on a day that has been denied or rejected. | | added v2.4

4.2.13.465 HL7 Version 2 Table 0465

URL: https://hl7.org/fhir/STU3/v2/0465/index.html

This page is part of the FHIR Specification (v3.0.2: STU 3). The current version which supercedes this version is 4.0.1. For a full list of available versions, see the Directory of published versions

Vocabulary Work Group | Maturity Level: N/A | External | Use Context: Any

This is a table defined as part of HL7 v2 . Related FHIR content: v2 Name/address representation.

Summary

Name: | v2 Name/Address Representation
Definition: | FHIR Value set/code system definition for HL7 v2 table 0465 (Name/Address Representation)
Code System URL: | http://hl7.org/fhir/v2/0465
Value Set URL: | http://hl7.org/fhir/ValueSet/v2-0465
OID: | ??
CodeSystem Resource | XML / JSON
ValueSet Resource | XML / JSON

This value set is used in the following places:

* This value set is the designated 'entire code system' value set for v2 Name/Address Representation

4.2.13.465.1 Code System Content

Name/Address Representation

Code | Description | Deutsch (German) | Comment | Version
A | Alphabetic (i.e., Default or some single-byte) | alphabetisch | | added v2.4
I | Ideographic (i.e., Kanji) | | | added v2.4
P | Phonetic (i.e., ASCII, Katakana, Hiragana, etc.) | | | added v2.4

4.2.13.466 HL7 Version 2 Table 0466

URL: https://hl7.org/fhir/STU3/v2/0466/index.html

This page is part of the FHIR Specification (v3.0.2: STU 3). The current version which supercedes this version is 4.0.1. For a full list of available versions, see the Directory of published versions

Vocabulary Work Group | Maturity Level: N/A | External | Use Context: Any

This is a table defined as part of HL7 v2 . Related FHIR content: v2 Ambulatory Payment Classification Code.

Summary

Name: | v2 Ambulatory Payment Classification Code
Definition: | FHIR Value set/code system definition for HL7 v2 table 0466 (Ambulatory Payment Classification Code)
Code System URL: | http://hl7.org/fhir/v2/0466
Value Set URL: | http://hl7.org/fhir/ValueSet/v2-0466
OID: | ??
CodeSystem Resource | XML / JSON
ValueSet Resource | XML / JSON

This value set is used in the following places:

* This value set is the designated 'entire code system' value set for v2 Ambulatory Payment Classification Code

4.2.13.466.1 Code System Content

Ambulatory Payment Classification Code

Code | Description | Nederlands (Dutch) | Comment | Version
... | | | added v2.4
031 | Dental procedures | Tandheelkundige behandeling | | added v2.4
163 | Excision/biopsy | Excisie/biopt | | added v2.4
181 | Level 1 skin repair. | Niveau 1 huidherstel | | added v2.4

4.2.13.468 HL7 Version 2 Table 0468

URL: https://hl7.org/fhir/STU3/v2/0468/index.html

This page is part of the FHIR Specification (v3.0.2: STU 3). The current version which supercedes this version is 4.0.1. For a full list of available versions, see the Directory of published versions

Vocabulary Work Group | Maturity Level: N/A | External | Use Context: Any

This is a table defined as part of HL7 v2 . Related FHIR content: v2 Payment Adjustment Code.

Summary

Name: | v2 Payment Adjustment Code
Definition: | FHIR Value set/code system definition for HL7 v2 table 0468 (Payment Adjustment Code)
Code System URL: | http://hl7.org/fhir/v2/0468
Value Set URL: | http://hl7.org/fhir/ValueSet/v2-0468
OID: | ??
CodeSystem Resource | XML / JSON
ValueSet Resource | XML / JSON

This value set is used in the following places:

* This value set is the designated 'entire code system' value set for v2 Payment Adjustment Code

4.2.13.468.1 Code System Content

Payment Adjustment Code

Code | Description | Comment | Version
1 | No payment adjustment | | added v2.4
2 | Designated current drug or biological payment adjustment applies to APC (status indicator G) | | added v2.4
3 | Designated new device payment adjustment applies to APC (status indicator H) | | added v2.4
4 | Designated new drug or new biological payment adjustment applies to APC (status indicator J) | | added v2.4
5 | Deductible not applicable (specific list of HCPCS codes) | | added v2.4

4.2.13.469 HL7 Version 2 Table 0469

URL: https://hl7.org/fhir/STU3/v2/0469/index.html

This page is part of the FHIR Specification (v3.0.2: STU 3). The current version which supercedes this version is 4.0.1. For a full list of available versions, see the Directory of published versions

Vocabulary Work Group | Maturity Level: N/A | External | Use Context: Any

This is a table defined as part of HL7 v2 . Related FHIR content: v2 Packaging Status Code.

Summary

Name: | v2 Packaging Status Code
Definition: | FHIR Value set/code system definition for HL7 v2 table 0469 (Packaging Status Code)
Code System URL: | http://hl7.org/fhir/v2/0469
Value Set URL: | http://hl7.org/fhir/ValueSet/v2-0469
OID: | ??
CodeSystem Resource | XML / JSON
ValueSet Resource | XML / JSON

This value set is used in the following places:

* This value set is the designated 'entire code system' value set for v2 Packaging Status Code

4.2.13.469.1 Code System Content

Packaging Status Code

Code | Description | Nederlands (Dutch) | Comment | Version
0 | Not packaged | Geen verpakking | | added v2.4
1 | Packaged service (status indicator N, or no HCPCS code and certain revenue codes) | Verpakte service (statusindicator N, of geen HCPCS code en bepaalde margecodes) | | added v2.4
2 | Packaged as part of partial hospitalization per diem or daily mental health service per diem | Verpakt als deel van een gedeeltelijke opname per dag of dagelijkse geestelijke verzorging per dag | | added v2.4

4.2.13.470 HL7 Version 2 Table 0470

URL: https://hl7.org/fhir/STU3/v2/0470/index.html

This page is part of the FHIR Specification (v3.0.2: STU 3). The current version which supercedes this version is 4.0.1. For a full list of available versions, see the Directory of published versions

Vocabulary Work Group | Maturity Level: N/A | External | Use Context: Any

This is a table defined as part of HL7 v2 . Related FHIR content: v2 - Reimbursement Type Code.

Summary

Name: | v2 - Reimbursement Type Code
Definition: | FHIR Value set/code system definition for HL7 v2 table 0470 (- Reimbursement Type Code)
Code System URL: | http://hl7.org/fhir/v2/0470
Value Set URL: | http://hl7.org/fhir/ValueSet/v2-0470
OID: | ??
CodeSystem Resource | XML / JSON
ValueSet Resource | XML / JSON

This value set is used in the following places:

* This value set is the designated 'entire code system' value set for v2 - Reimbursement Type Code

4.2.13.470.1 Code System Content

- Reimbursement Type Code

Code | Description | Comment | Version
Crnl | Corneal Tissue APC | | added v2.4
DME | Durable Medical Equipment | | added v2.4
EPO | Epotein | | added v2.4
Lab | Clinical Laboratory APC | | added v2.4
Mamm | Screening Mammography APC | | added v2.4
NoPay | This APC is not paid | | added v2.4
OPPS | Outpatient Prospective Payment System | | added v2.4
PartH | Partial Hospitalization APC | | added v2.4
Pckg | Packaged APC | | added v2.4

Thrpy | Therapy APC | | added v2.4

4.2.13.472 HL7 Version 2 Table 0472

URL: https://hl7.org/fhir/STU3/v2/0472/index.html

This page is part of the FHIR Specification (v3.0.2: STU 3). The current version which supercedes this version is 4.0.1. For a full list of available versions, see the Directory of published versions

Vocabulary Work Group | Maturity Level: N/A | External | Use Context: Any

This is a table defined as part of HL7 v2 . Related FHIR content: v2 TQ Conjunction ID.

Summary

Name: | v2 TQ Conjunction ID
Definition: | FHIR Value set/code system definition for HL7 v2 table 0472 (TQ Conjunction ID)
Code System URL: | http://hl7.org/fhir/v2/0472
Value Set URL: | http://hl7.org/fhir/ValueSet/v2-0472
OID: | ??
CodeSystem Resource | XML / JSON
ValueSet Resource | XML / JSON

This value set is used in the following places:

* This value set is the designated 'entire code system' value set for v2 TQ Conjunction ID

4.2.13.472.1 Code System Content

TQ Conjunction ID

Code | Description | Nederlands (Dutch) | Comment | Version
A | Asynchronous | Asynchroon | Do the next specification in parallel with this one (unless otherwise constrained by the following fields: TQ1-7-start date/time and TQ1-8-end date/time). The conjunction of "A" specifies two parallel instructions, as are sometimes used in medication, e. | added v2.4
C | Actuation Time | Actuatietijd | It will be followed by a completion time for the service. This code allows one to distinguish between the time and priority at which a service should be actuated (e.g. blood should be drawn) and the time and priority at which a service should be complet | added v2.4
S | Synchronous | Synchroon | Do the next specification after this one (unless otherwise constrained by the following fields: TQ1-7-start date/time and TQ1-8-end date/time). An "S" specification implies that the second timing sequence follows the first, e.g. when a service request is | added v2.4

4.2.13.473 HL7 Version 2 Table 0473

URL: https://hl7.org/fhir/STU3/v2/0473/index.html

This page is part of the FHIR Specification (v3.0.2: STU 3). The current version which supercedes this version is 4.0.1. For a full list of available versions, see the Directory of published versions

Vocabulary Work Group | Maturity Level: N/A | External | Use Context: Any

This is a table defined as part of HL7 v2 . Related FHIR content: v2 Formulary Status.

Summary

Name: | v2 Formulary Status
Definition: | FHIR Value set/code system definition for HL7 v2 table 0473 (Formulary Status)
Code System URL: | http://hl7.org/fhir/v2/0473
Value Set URL: | http://hl7.org/fhir/ValueSet/v2-0473
OID: | ??
CodeSystem Resource | XML / JSON
ValueSet Resource | XML / JSON

This value set is used in the following places:

* This value set is the designated 'entire code system' value set for v2 Formulary Status

4.2.13.473.1 Code System Content

Formulary Status

Code | Description | Nederlands (Dutch) | Comment | Version
G | This observation/service is on the formulary, and has guidelines | Deze test/service zit in het formularium en er zijn richtlijnen | | added v2.4
N | This observation/service is not on the formulary | Deze test/service zit niet in het formularium | | added v2.4
R | This observation/service is on the formulary, but is restricted | Deze test/service zit in het formularium maar er gelden beperkingen | | added v2.4
Y | This observation/service is on the formulary | Deze test/service zit in het formularium | | added v2.4

4.2.13.474 HL7 Version 2 Table 0474

URL: https://hl7.org/fhir/STU3/v2/0474/index.html

This page is part of the FHIR Specification (v3.0.2: STU 3). The current version which supercedes this version is 4.0.1. For a full list of available versions, see the Directory of published versions

Vocabulary Work Group | Maturity Level: N/A | External | Use Context: Any

This is a table defined as part of HL7 v2 . Related FHIR content: v2 Organization Unit Type.

Summary

Name: | v2 Organization Unit Type
Definition: | FHIR Value set/code system definition for HL7 v2 table 0474 (Organization Unit Type)
Code System URL: | http://hl7.org/fhir/v2/0474
Value Set URL: | http://hl7.org/fhir/ValueSet/v2-0474
OID: | ??
CodeSystem Resource | XML / JSON
ValueSet Resource | XML / JSON

This value set is used in the following places:

* This value set is the designated 'entire code system' value set for v2 Organization Unit Type

4.2.13.474.1 Code System Content

Organization Unit Type

Code | Description | Nederlands (Dutch) | Comment | Version
D | Department | Afdeling | | added v2.4
F | Facility | Kliniek | | added v2.4
L | Local market area | | deprecated | added v2.4, removed after v2.4
M | Medical Center Area | | deprecated | added v2.4, removed after v2.4
S | Subdivision | Subdivisie | | added v2.4
U | Subdepartment | Subafdeling | | added v2.4
V | Division | Divisie | | added v2.4

4.2.13.475 HL7 Version 2 Table 0475

URL: https://hl7.org/fhir/STU3/v2/0475/index.html

This page is part of the FHIR Specification (v3.0.2: STU 3). The current version which supercedes this version is 4.0.1. For a full list of available versions, see the Directory of published versions

Vocabulary Work Group | Maturity Level: N/A | External | Use Context: Any

This is a table defined as part of HL7 v2 . Related FHIR content: v2 Charge Type Reason.

Summary

Name: | v2 Charge Type Reason
Definition: | FHIR Value set/code system definition for HL7 v2 table 0475 (Charge Type Reason)
Code System URL: | http://hl7.org/fhir/v2/0475
Value Set URL: | http://hl7.org/fhir/ValueSet/v2-0475
OID: | ??
CodeSystem Resource | XML / JSON
ValueSet Resource | XML / JSON

This value set is used in the following places:

* This value set is the designated 'entire code system' value set for v2 Charge Type Reason

4.2.13.475.1 Code System Content

Charge Type Reason

Code | Description | Nederlands (Dutch) | Comment | Version
01 | Allergy | Allergie | | added v2.5
02 | Intolerance | Intolerantie | | added v2.5
03 | Treatment Failure | Behandeling mislukt | | added v2.5
04 | Patient Request | Patiëntverzoek | | added v2.5
05 | No Exception | Geen uitzondering | | added v2.5

4.2.13.477 HL7 Version 2 Table 0477

URL: https://hl7.org/fhir/STU3/v2/0477/index.html

This page is part of the FHIR Specification (v3.0.2: STU 3). The current version which supercedes this version is 4.0.1. For a full list of available versions, see the Directory of published versions

Vocabulary Work Group | Maturity Level: N/A | External | Use Context: Any

This is a table defined as part of HL7 v2 . Related FHIR content: v2 Controlled Substance Schedule.

Summary

Name: | v2 Controlled Substance Schedule
Definition: | FHIR Value set/code system definition for HL7 v2 table 0477 (Controlled Substance Schedule)
Code System URL: | http://hl7.org/fhir/v2/0477
Value Set URL: | http://hl7.org/fhir/ValueSet/v2-0477
OID: | ??
CodeSystem Resource | XML / JSON
ValueSet Resource | XML / JSON

This value set is used in the following places:

* This value set is the designated 'entire code system' value set for v2 Controlled Substance Schedule

4.2.13.477.1 Code System Content

Controlled Substance Schedule

Code | Description | Comment | Version
I | Schedule I | Includes drugs that have a high potential for abuse, no currently accepted medical use in the United States and a lack of accepted safety for use under medical supervision. | added v2.5
II | Schedule II | Includes drugs having currently accepted medical use in the United States and a high abuse potential, with severe psychological or physical dependence liability. | added v2.5
III | Schedule III | Includes drugs having an abuse potential less than that of drugs listed in Schedules I and II. All CS III drugs have a currently accepted medical use in the United States. | added v2.5
IV | Schedule IV | Includes drugs having a lesser potential for abuse than those listed in Schedule III. CS IV drugs have a currently accepted medical use in the United States. | added v2.5
V | Schedule V | Includes drugs having low abuse potential and limited physical or psychological dependence relative to those listed in IV and have an accepted medical use in the United States. | added v2.5
VI | Schedule VI | State defined | added v2.5

4.2.13.478 HL7 Version 2 Table 0478

URL: https://hl7.org/fhir/STU3/v2/0478/index.html

This page is part of the FHIR Specification (v3.0.2: STU 3). The current version which supercedes this version is 4.0.1. For a full list of available versions, see the Directory of published versions

Vocabulary Work Group | Maturity Level: N/A | External | Use Context: Any

This is a table defined as part of HL7 v2 . Related FHIR content: v2 Formulary Status.

Summary

Name: | v2 Formulary Status
Definition: | FHIR Value set/code system definition for HL7 v2 table 0478 (Formulary Status)
Code System URL: | http://hl7.org/fhir/v2/0478
Value Set URL: | http://hl7.org/fhir/ValueSet/v2-0478
OID: | ??
CodeSystem Resource | XML / JSON
ValueSet Resource | XML / JSON

This value set is used in the following places:

* This value set is the designated 'entire code system' value set for v2 Formulary Status

4.2.13.478.1 Code System Content

Formulary Status

Code | Description | Nederlands (Dutch) | Comment | Version
G | Pharmaceutical substance is in the formulary, but guidelines apply | Farmaceutische substantie zit in het formularium maar er zijn richtlijnen | | added v2.5
N | Pharmaceutical substance is NOT in the formulary | Farmaceutische substantie zit NIET in het formularium | | added v2.5
R | Pharmaceutical substance is in the formulary, but restrictions apply | Farmaceutische substantie zit in het formularium maar er zijn beperkingen | | added v2.5
Y | Pharmaceutical substance is in the formulary | Farmaceutische substantie zit in het formularium | | added v2.5

4.2.13.480 HL7 Version 2 Table 0480

URL: https://hl7.org/fhir/STU3/v2/0480/index.html

This page is part of the FHIR Specification (v3.0.2: STU 3). The current version which supercedes this version is 4.0.1. For a full list of available versions, see the Directory of published versions

Vocabulary Work Group | Maturity Level: N/A | External | Use Context: Any

This is a table defined as part of HL7 v2 . Related FHIR content: v2 Pharmacy Order Types.

Summary

Name: | v2 Pharmacy Order Types
Definition: | FHIR Value set/code system definition for HL7 v2 table 0480 (Pharmacy Order Types)
Code System URL: | http://hl7.org/fhir/v2/0480
Value Set URL: | http://hl7.org/fhir/ValueSet/v2-0480
OID: | ??
CodeSystem Resource | XML / JSON
ValueSet Resource | XML / JSON

This value set is used in the following places:

* This value set is the designated 'entire code system' value set for v2 Pharmacy Order Types

4.2.13.480.1 Code System Content

Pharmacy Order Types

Code | Description | Comment | Version
M | Medication | Default value. Includes, but is not limited to, tables, capsules, powders, puffs, and other non-injected/non-infused products. | added v2.5
O | Other solution as medication orders | Includes, but is not limited to, piggybacks and syringes | added v2.5
S | IV Large Volume Solutions | Includes, but is not limited to, TPNs, admixtures, solutions and drips. | added v2.5

4.2.13.482 HL7 Version 2 Table 0482

URL: https://hl7.org/fhir/STU3/v2/0482/index.html

This page is part of the FHIR Specification (v3.0.2: STU 3). The current version which supercedes this version is 4.0.1. For a full list of available versions, see the Directory of published versions

Vocabulary Work Group | Maturity Level: N/A | External | Use Context: Any

This is a table defined as part of HL7 v2 . Related FHIR content: v2 Order Type.

Summary

Name: | v2 Order Type
Definition: | FHIR Value set/code system definition for HL7 v2 table 0482 (Order Type)
Code System URL: | http://hl7.org/fhir/v2/0482
Value Set URL: | http://hl7.org/fhir/ValueSet/v2-0482
OID: | ??
CodeSystem Resource | XML / JSON
ValueSet Resource | XML / JSON

This value set is used in the following places:

* This value set is the designated 'entire code system' value set for v2 Order Type

4.2.13.482.1 Code System Content

Order Type

Code | Description | Nederlands (Dutch) | Comment | Version
I | Inpatient Order | Klinische aanvraag | | added v2.5
O | Outpatient Order | Poliklinische aanvraag | | added v2.5

4.2.13.483 HL7 Version 2 Table 0483

URL: https://hl7.org/fhir/STU3/v2/0483/index.html

This page is part of the FHIR Specification (v3.0.2: STU 3). The current version which supercedes this version is 4.0.1. For a full list of available versions, see the Directory of published versions

Vocabulary Work Group | Maturity Level: N/A | External | Use Context: Any

This is a table defined as part of HL7 v2 . Related FHIR content: v2 Authorization Mode.

Summary

Name: | v2 Authorization Mode
Definition: | FHIR Value set/code system definition for HL7 v2 table 0483 (Authorization Mode)
Code System URL: | http://hl7.org/fhir/v2/0483
Value Set URL: | http://hl7.org/fhir/ValueSet/v2-0483
OID: | ??
CodeSystem Resource | XML / JSON
ValueSet Resource | XML / JSON

This value set is used in the following places:

* This value set is the designated 'entire code system' value set for v2 Authorization Mode

4.2.13.483.1 Code System Content

Authorization Mode

Code | Description | Nederlands (Dutch) | Comment | Version
EL | Electronic | Electronisch | | added v2.5
EM | E-mail | E-mail | | added v2.5
FX | Fax | Fax | | added v2.5
IP | In Person | In persoon | | added v2.5
MA | Mail | Post | | added v2.5
PA | Paper | Papier | | added v2.5
PH | Phone | Telefoon | | added v2.5
RE | Reflexive (Automated system) | Reflexief (geautomatiseerd systeem) | | added v2.5
VC | Video-conference | Videoconferentie | | added v2.5
VO | Voice | Stem | | added v2.5

4.2.13.484 HL7 Version 2 Table 0484

URL: https://hl7.org/fhir/STU3/v2/0484/index.html

This page is part of the FHIR Specification (v3.0.2: STU 3). The current version which supercedes this version is 4.0.1. For a full list of available versions, see the Directory of published versions

Vocabulary Work Group | Maturity Level: N/A | External | Use Context: Any

This is a table defined as part of HL7 v2 . Related FHIR content: v2 Dispense Type.

Summary

Name: | v2 Dispense Type
Definition: | FHIR Value set/code system definition for HL7 v2 table 0484 (Dispense Type)
Code System URL: | http://hl7.org/fhir/v2/0484
Value Set URL: | http://hl7.org/fhir/ValueSet/v2-0484
OID: | ??
CodeSystem Resource | XML / JSON
ValueSet Resource | XML / JSON

This value set is used in the following places:

* This value set is the designated 'entire code system' value set for v2 Dispense Type

4.2.13.484.1 Code System Content

Dispense Type

Code | Description | Comment | Version
B | Trial Quantity Balance | | added v2.5
C | Compassionate Fill | | added v2.5
N | New/Renew - Full Fill | | added v2.5
P | New/Renew - Part Fill | | added v2.5
Q | Refill - Part Fill | | added v2.5
R | Refill - Full Fill | | added v2.5
S | Manufacturer Sample | | added v2.5
T | Trial Quantity | | added v2.5
Z | Non-Prescription Fill | | added v2.5

4.2.13.485 HL7 Version 2 Table 0485

URL: https://hl7.org/fhir/STU3/v2/0485/index.html

This page is part of the FHIR Specification (v3.0.2: STU 3). The current version which supercedes this version is 4.0.1. For a full list of available versions, see the Directory of published versions

Vocabulary Work Group | Maturity Level: N/A | External | Use Context: Any

This is a table defined as part of HL7 v2 . Related FHIR content: v2 Extended Priority Codes.

Summary

Name: | v2 Extended Priority Codes
Definition: | FHIR Value set/code system definition for HL7 v2 table 0485 (Extended Priority Codes)
Code System URL: | http://hl7.org/fhir/v2/0485
Value Set URL: | http://hl7.org/fhir/ValueSet/v2-0485
OID: | ??
CodeSystem Resource | XML / JSON
ValueSet Resource | XML / JSON

This value set is used in the following places:

* This value set is the designated 'entire code system' value set for v2 Extended Priority Codes

4.2.13.485.1 Code System Content

Extended Priority Codes

Code | Description | Nederlands (Dutch) | Comment | Version
A | ASAP | Zo spoedig mogelijk | Fill after S orders | added v2.5
C | Callback | Terugbellen | | added v2.5
P | Preop | Pre-op | | added v2.5
PRN | As needed | Zoals noodzakelijk | | added v2.5
R | Routine | Routine | Default | added v2.5
S | Stat | STAT | With highest priority | added v2.5
T | Timing critical | Timing kritiek | A request implying that it is critical to come as close as possible to the requested time, e.g. for a trough anti-microbial level. | added v2.5
TD<integer> | Timing critical within <integer> days. | Timing kritiek binnen <integer> dagen. | Timing critical within <integer> days. | added v2.5
TH<integer> | Timing critical within <integer> hours. | Timing kritiek binnen <integer> uur. | Timing critical within <integer> hours. | added v2.5
TL<integer> | Timing critical within <integer> months. | Timing kritiek binnen <integer> maanden. | Timing critical within <integer> months. | added v2.5
TM<integer> | Timing critical within <integer> minutes. | Timing kritiek binnen <integer> minuten. | Timing critical within <integer> minutes. | added v2.5
TS<integer> | Timing critical within <integer> seconds. | Timing kritiek binnen <integer> seconden. | Timing critical within <integer> seconds. | added v2.5

TW<integer> | Timing critical within <integer> weeks. | Timing kritiek binnen <integer> weken. | Timing critical within <integer> weeks. | added v2.5

4.2.13.487 HL7 Version 2 Table 0487

URL: https://hl7.org/fhir/STU3/v2/0487/index.html

This page is part of the FHIR Specification (v3.0.2: STU 3). The current version which supercedes this version is 4.0.1. For a full list of available versions, see the Directory of published versions

Vocabulary Work Group | Maturity Level: N/A | External | Use Context: Any

This is a table defined as part of HL7 v2 . Related FHIR content: v2 Specimen Type.

Summary

Name: | v2 Specimen Type
Definition: | FHIR Value set/code system definition for HL7 v2 table 0487 (Specimen Type)
Code System URL: | http://hl7.org/fhir/v2/0487
Value Set URL: | http://hl7.org/fhir/ValueSet/v2-0487
OID: | ??
CodeSystem Resource | XML / JSON
ValueSet Resource | XML / JSON

Concept Maps for this value set:

to http://snomed.info/id?fhir_vs | Specimen mapping from v2 table 0487 to SNOMED CT | XML | JSON

This value set is used in the following places:

* This value set is the designated 'entire code system' value set for v2 Specimen Type

* This value set has translations in the ConceptMap Specimen mapping from v2 table 0487 to SNOMED CT

* Specimen.type (Example)

4.2.13.487.1 Code System Content

Specimen Type

Code | Description | Deutsch (German) | Nederlands (Dutch) | Comment | Version
... | No suggested values | keine Werte vorgeschlagen | geen voorgestelde waarden | deprecated | added v2.6, removed after v2.6
ABS | Abscess | | Abces | | added v2.5
ACNE | Tissue, Acne | | Weefsel, Acné | Tissue | added v2.5
ACNFLD | Fluid, Acne | | Vocht, Acné | Fluid | added v2.5
AIRS | Air Sample | | Luchtmonster | Environment | added v2.5
ALL | Allograft | | Allograft | Tissue | added v2.5
AMN | Amniotic fluid | | Amniotisch vocht | | added v2.8.2
AMP | Amputation | | Amputatie | Tissue | added v2.5
ANGI | Catheter Tip, Angio | | | Device | added v2.5
ARTC | Catheter Tip, Arterial | | | Device | added v2.5
ASERU | Serum, Acute | | | Blood | added v2.5
ASP | Aspirate | | Aspiraat | | added v2.5
ATTE | Environment, Attest | | | Environment | added v2.5
AUTOA | Environmental, Autoclave Ampule | | | Environment | added v2.7
AUTOC | Environmental, Autoclave Capsule | | | Environment | added v2.5
AUTP | Autopsy | | Autopsie | Tissue | added v2.5
BBL | Blood bag | | Bloedzak | Blood | added v2.5
BCYST | Cyst, Baker's | | | Condition | added v2.5
BDY | Whole body | | Heel lichaam | Body submitted for autopsy / carcass submitted | added v2.8.2
BIFL | Bile Fluid | | Galvloeistof | | added v2.8.2
BITE | Bite | | | Conditions | added v2.5
BLD | Whole blood | | | | added v2.8.2
BLDA | Blood arterial | | Arterieel bloed | | added v2.8.2
BLDCO | Cord blood | | | | added v2.8.2
BLDV | Blood venous | | Veneus bloed | | added v2.8.2
BLEB | Bleb | | Blaar | Condition, Fluid/Tissue | added v2.5
BLIST | Blister | | Blaas | Condition, Fluid/Tissue | added v2.5
BOIL | Boil | | | Condition | added v2.5
BON | Bone | | Bot | | added v2.5.1
BONE | Bone | | | deprecated | added v2.5, removed after v2.5
BOWL | Bowel contents | | Darminhoud | Condition | added v2.5
BPH | Basophils | | | | added v2.8.2
BPU | Blood product unit | | | Blood | added v2.5
BRN | Burn | | Verbranding | | added v2.5
BRSH | Brush | | | Product; Brush or brushing (these may be 2 separate entries as in a physical brush or a portion thereof vs the substance obtained after a surface has been brushed) | added v2.5
BRTH | Breath (use EXHLD) | | Adem (gebruik (EXHLD) | | added v2.5
BRUS | Brushing | | | Product | added v2.5
BUB | Bubo | | | Condition | added v2.5
BULLA | Bulla/Bullae | | | Condition | added v2.5

BX | Biopsy | | Biopt | Tissue | added v2.5
CALC | Calculus (=Stone) | | | | added v2.5
CARBU | Carbuncle | | | Condition | added v2.5
CAT | Catheter | | Catether | Device | added v2.5
CBITE | Bite, Cat | | | Conditions | added v2.5
CDM | Cardiac muscle | | Hartspier | | added v2.8.2
CLIPP | Clippings | | | Condition | added v2.5
CNJT | Conjunctiva | | | | added v2.5
CNL | Cannula | | | | added v2.8.2
COL | Colostrum | | | | added v2.5
CONE | Biospy, Cone | | | Tissue | added v2.5
CSCR | Scratch, Cat | | | Condition | added v2.5
CSERU | Serum, Convalescent | | | Blood | added v2.5
CSF | Cerebral spinal fluid | | | | added v2.8.2
CSITE | Catheter Insertion Site | | | Device | added v2.5
CSMY | Fluid, Cystostomy Tube | | | Fluid | added v2.5
CST | Fluid, Cyst | | | Fluid | added v2.5
CSVR | Blood, Cell Saver | | | Transfusion | added v2.5
CTP | Catheter tip | | | Device | added v2.5
CUR | Curretage | | | Uterine specimen obtained by curettage = Currettings | added v2.8.2
CVM | Cervical Mucus | | | | added v2.8.2
CVPS | Site, CVP | | | Site | added v2.5
CVPT | Catheter Tip, CVP | | | Device | added v2.5
CYN | Nodule, Cystic | | | Condition | added v2.5
CYST | Cyst | | | | added v2.5
DBITE | Bite, Dog | | | Conditions | added v2.5
DCS | Sputum, Deep Cough | | | Condition | added v2.5
DEC | Ulcer, Decubitus | | | Condition | added v2.5
DEION | Environmental, Water (Deionized) | | | Environment | added v2.5
DIA | Dialysate | | | Condition | added v2.5
DIAF | Dialysis Fluid | | | Fluid used for dialysis - is a product | added v2.8.2
DISCHG | Discharge | | | Condition | added v2.5
DIV | Diverticulum | | | Condition | added v2.5
DRN | Drain | | | Device | added v2.5
DRNG | Drainage, Tube | | | Device | added v2.5
DRNGP | Drainage, Penrose | | | Condition | added v2.5
DUFL | Duodenal fluid | | | | added v2.8.2
EARW | Ear wax (cerumen) | | | | added v2.5
EBRUSH | Brush, Esophageal | | | Product | added v2.5
EEYE | Environmental, Eye Wash | | | Environment | added v2.5
EFF | Environmental, Effluent | | | Environment | added v2.5
EFFUS | Effusion | | | Condition | added v2.5
EFOD | Environmental, Food | | | Environment | added v2.5
EISO | Environmental, Isolette | | | Environment | added v2.5
ELT | Electrode | | | | added v2.5
ENVIR | Environmental, Unidentified Substance | | | Environment | added v2.5
EOS | Eosinophils | | | | added v2.8.2
EOTH | Environmental, Other Substance | | | Environment; (Substance is Known but not in code Table) | added v2.5
ESOI | Environmental, Soil | | | Environment | added v2.5
ESOS | Environmental, Solution (Sterile) | | | Environment | added v2.5
ETA | Aspirate, Endotrach | | | Aspirate | added v2.5
ETTP | Catheter Tip, Endotracheal | | | Device | added v2.5
ETTUB | Tube, Endotracheal | | | Device | added v2.5
EWHI | Environmental, Whirlpool | | | Environment | added v2.5
EXG | Gas, exhaled (=breath) | | | | added v2.5
EXS | Shunt, External | | | Condition | added v2.5
EXUDTE | Exudate | | | Condition | added v2.5
FAW | Environmental, Water (Well) | | | Environment | added v2.5
FBLOOD | Blood, Fetal | | Bloed, feutaal | Blood | added v2.5
FGA | Fluid, Abdomen | | | Fluid | added v2.5
FIB | Fibroblasts | | | | added v2.8.2
FIST | Fistula | | Fistel | | added v2.5
FLD | Fluid, Other | | Vocht, anders | Fluid | added v2.5
FLT | Filter | | Filter | | added v2.5
FLU | Fluid, Body unsp | | Vocht, lichaam niet-gesp. | | added v2.5
FLUID | Fluid | | Vocht | Fluid | added v2.5
FOLEY | Catheter Tip, Foley | | | Device | added v2.5
FRS | Fluid, Respiratory | | | Fluid | added v2.5
FSCLP | Scalp, Fetal | | | Condition | added v2.5
FUR | Furuncle | | | Condition | added v2.5
GAS | Gas | | | | added v2.5
GASA | Aspirate, Gastric | | | Aspirate | added v2.5

GASAN | Antrum, Gastric | | | Tissue | added v2.5
GASBR | Brushing, Gastric | | | Product | added v2.5
GASD | Drainage, Gastric | | | Condition | added v2.5
GAST | Fluid/contents, Gastric | | | | added v2.5
GENL | Genital lochia | | | | added v2.8.2
GENV | Genital vaginal | | Genitaal vaginaal | | added v2.5
GRAFT | Graft | | | Condition | added v2.5
GRAFTS | Graft Site | | | Condition | added v2.7
GRANU | Granuloma | | Granuloom | Condition | added v2.5
GROSH | Catheter, Groshong | | | Device | added v2.5
GSOL | Solution, Gastrostomy | | | Product | added v2.5
GSPEC | Biopsy, Gastric | | Biopt, maag | Tissue | added v2.5
GT | Tube, Gastric | | | Device | added v2.5
GTUBE | Drainage Tube, Drainage (Gastrostomy) | | | Condition | added v2.5
HAR | Hair | | Haar | | added v2.8.2
HBITE | Bite, Human | | Beet, menselijk | Conditions | added v2.5
HBLUD | Blood, Autopsy | | Bloed, autopsie | Blood | added v2.5
HEMAQ | Catheter Tip, Hemaquit | | | Device | added v2.5
HEMO | Catheter Tip, Hemovac | | | Device | added v2.5
HERNI | Tissue, Herniated | | | Tissue | added v2.5
HEV | Drain, Hemovac | | | Device | added v2.5
HIC | Catheter, Hickman | | | Device | added v2.5
HYDC | Fluid, Hydrocele | | | Fluid | added v2.5
IBITE | Bite, Insect | | | Conditions | added v2.5
ICYST | Cyst, Inclusion | | | Condition | added v2.5
IDC | Catheter Tip, Indwelling | | | Device | added v2.5
IHG | Gas, Inhaled | | | | added v2.5
ILEO | Drainage, Ileostomy | | | Condition | added v2.5
ILLEG | Source of Specimen Is Illigible | | | | added v2.5
IMP | Implant | | Implantaat | Device | added v2.5
INCI | Site, Incision/Surgical | | | Site | added v2.5
INFIL | Infiltrate | | | Condition | added v2.5
INS | Insect | | Insect | Object | added v2.5
INTRD | Catheter Tip, Introducer | | | Device | added v2.5
ISLT | Isolate | | Isolaat | | added v2.8.2
IT | Intubation tube | | Intubatieslang | | added v2.5
IUD | Intrauterine Device | | | Device (Common Usage) | added v2.5
IVCAT | Catheter Tip, IV | | | Device | added v2.5
IVFLD | Fluid, IV | | | Fluid | added v2.5
IVTIP | Tubing Tip, IV | | | Device | added v2.5
JEJU | Drainage, Jejunal | | | Condition | added v2.5
JNTFLD | Fluid, Joint | | Vocht, gewricht | Fluid | added v2.5
JP | Drainage, Jackson Pratt | | | Condition | added v2.5
KELOI | Lavage | | | Product | added v2.5
KIDFLD | Fluid, Kidney | | Vocht, nier | Fluid | added v2.5
LAVG | Lavage, Bronhial | | | Product | added v2.5
LAVGG | Lavage, Gastric | | | Product | added v2.5
LAVGP | Lavage, Peritoneal | | | Product | added v2.5
LAVPG | Lavage, Pre-Bronch | | | Product | added v2.5
LENS1 | Contact Lens | | | Device | added v2.5
LENS2 | Contact Lens Case | | | Device | added v2.5
LESN | Lesion | | | Condition | added v2.5
LIQ | Liquid, Unspecified | | Vocht, niet gespecificeerd | | added v2.5
LIQO | Liquid, Other | | Vocht, anders | | added v2.5
LNA | Line arterial | | | Arterial blood collected via arterial line | added v2.8.2
LNV | Line venous | | | Venous blood collected via venous line | added v2.8.2
LSAC | Fluid, Lumbar Sac | | | Fluid | added v2.5
LYM | Lymphocytes | | Lymfocyten | | added v2.8.2
MAC | Macrophages | | | | added v2.8.2
MAHUR | Catheter Tip, Makurkour | | | Device | added v2.5
MAR | Marrow | | Merg | Bone marrow | added v2.8.2
MASS | Mass | | | Condition | added v2.5
MBLD | Blood, Menstrual | | Menstruatiebloed | Blood | added v2.5
MEC | Meconium | | Meconium | | added v2.8.2
MILK | Breast milk | | Borstmelk | Mother's milk specimen | added v2.8.2
MLK | Milk | | Melk | Food specimen | added v2.8.2
MUCOS | Mucosa | | | Condition | added v2.5
MUCUS | Mucus | | Slijm | Condition | added v2.5
NAIL | Nail | | Nagel | Finger or toe nail sample | added v2.8.2
NASDR | Drainage, Nasal | | | Condition | added v2.5
NEDL | Needle | | Naald | Device | added v2.5
NEPH | Site, Nephrostomy | | | Site | added v2.5

NGASP | Aspirate, Nasogastric | | | Aspirate | added v2.5
NGAST | Drainage, Nasogastric | | | Condition | added v2.5
NGS | Site, Naso/Gastric | | | Site | added v2.5
NODUL | Nodule(s) | | | Condition | added v2.5
NSECR | Secretion, Nasal | | Secretie, nasaal | Condition | added v2.5
ORH | Other | | Anders | | added v2.5
ORL | Lesion, Oral | | | Condition (Common Usage) | added v2.5
OTH | Source, Other | | Bron, anders | | added v2.5
PACEM | Pacemaker | | | Device | added v2.5
PAFL | Pancreatic fluid | | | | added v2.8.2
PCFL | Fluid, Pericardial | | | | added v2.5
PDSIT | Site, Peritoneal Dialysis | | | Site | added v2.5
PDTS | Site, Peritoneal Dialysis Tunnel | | | Site | added v2.5
PELVA | Abscess, Pelvic | | | Condition | added v2.5
PENIL | Lesion, Penile | | | Condition (Common Usage) | added v2.5
PERIA | Abscess, Perianal | | | Condition, Abscess & Body Part | added v2.5
PILOC | Cyst, Pilonidal | | | Condition | added v2.5
PINS | Site, Pin | | | Site | added v2.5
PIS | Site, Pacemaker Insetion | | | Site | added v2.5
PLAN | Plant Material | | Plantaardig materiaal | Object | added v2.5
PLAS | Plasma | | Plasma | Blood | added v2.5
PLB | Plasma bag | | Plasmazak | Blood | added v2.5
PLC | Placenta | | Placenta | | added v2.8.2
PLEVS | Serum, Peak Level | | | Blood | added v2.5
PLR | Pleural fluid (thoracentesis fluid) | | | | added v2.8.2
PMN | Polymorphonuclear neutrophils | | | | added v2.8.2
PND | Drainage, Penile | | | Condition | added v2.5
POL | Polyps | | | Condition | added v2.5
POPGS | Graft Site, Popliteal | | | Condition | added v2.5
POPLG | Graft, Popliteal | | | Condition | added v2.5
POPLV | Site, Popliteal Vein | | | Site | added v2.5
PORTA | Catheter, Porta | | | Device | added v2.5
PPP | Plasma, Platelet poor | | | Blood | added v2.5
PROST | Prosthetic Device | | | Device | added v2.5
PRP | Plasma, Platelet rich | | | Blood | added v2.5
PSC | Pseudocyst | | | Condition | added v2.5
PUNCT | Wound, Puncture | | | Condition | added v2.5
PUS | Pus | | Pus | | added v2.5.1
PUSFR | Pustule | | | Condition | added v2.5
PUST | Pus | | | Condition | added v2.5
QC3 | Quality Control | | | Environment | added v2.5
RANDU | Urine, Random | | | Condition | added v2.5
RBC | Erythrocytes | | | | added v2.8.2
RBITE | Bite, Reptile | | | Conditions | added v2.5
RECT | Drainage, Rectal | | | Condition | added v2.5
RECTA | Abscess, Rectal | | | Condition | added v2.5
RENALC | Cyst, Renal | | | Condition | added v2.5
RENC | Fluid, Renal Cyst | | | Fluid | added v2.5
RES | Respiratory | | | Condition (Ambiguous) | added v2.5
SAL | Saliva | | Speeksel | | added v2.5
SCAR | Tissue, Keloid (Scar) | | | Tissue | added v2.5
SCLV | Catheter Tip, Subclavian | | | Device | added v2.5
SCROA | Abscess, Scrotal | | Abces, scrotaal | Condition | added v2.5
SECRE | Secretion(s) | | Secretie(s) | Fluid/Secretion | added v2.5
SER | Serum | | Serum | | added v2.5
SHU | Site, Shunt | | | Site | added v2.5
SHUNF | Fluid, Shunt | | | Fluid | added v2.5
SHUNT | Shunt | | | Condition | added v2.5
SITE | Site | | | Site | added v2.5
SKBP | Biopsy, Skin | | Biopt, huid | Tissue | added v2.5
SKN | Skin | | Huid | | added v2.5
SMM | Mass, Sub-Mandibular | | | Condition | added v2.5
SMN | Seminal fluid | | Seminaal vocht | | added v2.8.2
SNV | Fluid, synovial (Joint fluid) | | | | added v2.5
SPRM | Spermatozoa | | Spermatozoïden | | added v2.5
SPRP | Catheter Tip, Suprapubic | | | Device | added v2.5
SPRPB | Cathether Tip, Suprapubic | | | Device | added v2.5
SPS | Environmental, Spore Strip | | | Environment | added v2.5
SPT | Sputum | | Sputum | | added v2.5
SPTC | Sputum - coughed | | Sputum, opgehoest | | added v2.5
SPTT | Sputum - tracheal aspirate | | | | added v2.5
SPUT1 | Sputum, Simulated | | | Condition | added v2.5

SPUTIN | Sputum, Inducted | | | Condition | added v2.5
SPUTSP | Sputum, Spontaneous | | | Condition | added v2.5
STER | Environmental, Sterrad | | | Environment | added v2.5
STL | Stool = Fecal | | | | added v2.5
STONE | Stone, Kidney | | | Condition | added v2.5
SUBMA | Abscess, Submandibular | | | Condition | added v2.5
SUBMX | Abscess, Submaxillary | | | Condition | added v2.5
SUMP | Drainage, Sump | | | Condition | added v2.5
SUP | Suprapubic Tap | | | Product | added v2.5
SUTUR | Suture | | | Object | added v2.5
SWGZ | Catheter Tip, Swan Gantz | | | Device | added v2.5
SWT | Sweat | | Zweet | | added v2.8.2
TASP | Aspirate, Tracheal | | | Aspirate | added v2.5
TEAR | Tears | | Traanvocht | | added v2.8.2
THRB | Thrombocyte (platelet) | | | | added v2.8.2
TISS | Tissue | | Weefsel | | added v2.5
TISU | Tissue ulcer | | | | added v2.5
TLC | Cathether Tip, Triple Lumen | | | Device | added v2.5
TRAC | Site, Tracheostomy | | | Site | added v2.5
TRANS | Transudate | | | Condition | added v2.5
TSERU | Serum, Trough | | | Blood | added v2.5
TSTES | Abscess, Testicular | | | Condition | added v2.5
TTRA | Aspirate, Transtracheal | | | Aspirate | added v2.5
TUBES | Tubes | | | Device | added v2.5
TUMOR | Tumor | | Tumor | Condition | added v2.5
TZANC | Smear, Tzanck | | | | added v2.5
UDENT | Source, Unidentified | | | | added v2.5
UMED | Unknown Medicine | | | for forensic and possibly chemistry testing | added v2.8.2
UR | Urine | | Urine | | added v2.5
URC | Urine clean catch | | | | added v2.5
URINB | Urine, Bladder Washings | | | Condition | added v2.5
URINC | Urine, Catheterized | | | Condition | added v2.5
URINM | Urine, Midstream | | Urine, midstream | Condition | added v2.5
URINN | Urine, Nephrostomy | | | Condition | added v2.5
URINP | Urine, Pedibag | | | Device | added v2.5
URNS | Urine sediment | | Urine, sediment | | added v2.8.2
URT | Urine catheter | | | | added v2.5
USCOP | Urine, Cystoscopy | | | Condition | added v2.5
USPEC | Source, Unspecified | | Bron, ongedefinieerd | | added v2.5
USUB | Unkown substance | | Onbekende substantie | | added v2.8.2
VASTIP | Catheter Tip, Vas | | | Device | added v2.5
VENT | Catheter Tip, Ventricular | | | Device | added v2.5
VITF | Vitreous Fluid | | | | added v2.5
VOM | Vomitus | | Braaksel | | added v2.5.1
WASH | Wash | | | Product | added v2.5
WASI | Washing, e.g. bronchial washing | | | Product | added v2.5
WAT | Water | | Water | | added v2.5
WB | Blood, Whole | | | Blood | added v2.5
WBC | Leukocytes | | Leukocyten | | added v2.8.2
WEN | Wen | | | Tissue | added v2.5
WICK | Wick | | Lont | | added v2.5
WND | Wound | | Wond | | added v2.5
WNDA | Wound abscess | | Wond abces | | added v2.5
WNDD | Wound drainage | | | | added v2.5
WNDE | Wound exudate | | | | added v2.5
WORM | Worm | | Worm | Object | added v2.5
WRT | Wart | | Wrat | Tissue | added v2.5
WWA | Environmental, Water | | Milieu, water | Environment | added v2.5
WWO | Environmental, Water (Ocean) | | Milieu, water (oceaan) | | added v2.5
WWT | Environmental, Water (Tap) | | Milieu, water (kraan) | Environment | added v2.5

4.2.13.488 HL7 Version 2 Table 0488

URL: https://hl7.org/fhir/STU3/v2/0488/index.html

This page is part of the FHIR Specification (v3.0.2: STU 3). The current version which supercedes this version is 4.0.1. For a full list of available versions, see the Directory of published versions

Vocabulary Work Group | Maturity Level: N/A | External | Use Context: Any

This is a table defined as part of HL7 v2 . Related FHIR content: v2 Specimen Collection Method.

Summary

Name: | v2 Specimen Collection Method

Definition: | FHIR Value set/code system definition for HL7 v2 table 0488 (Specimen Collection Method)
Code System URL: | http://hl7.org/fhir/v2/0488
Value Set URL: | http://hl7.org/fhir/ValueSet/v2-0488
OID: | ??
CodeSystem Resource | XML / JSON
ValueSet Resource | XML / JSON

This value set is used in the following places:

* This value set is the designated 'entire code system' value set for v2 Specimen Collection Method

4.2.13.488.1 Code System Content

Specimen Collection Method

Code | Description | Comment | Version
ANP | Plates, Anaerobic | | added v2.5
BAP | Plates, Blood Agar | | added v2.5
BCAE | Blood Culture, Aerobic Bottle | | added v2.5
BCAN | Blood Culture, Anaerobic Bottle | | added v2.5
BCPD | Blood Culture, Pediatric Bottle | | added v2.5
BIO | Biopsy | | added v2.5
CAP | Capillary Specimen | | added v2.5
CATH | Catheterized | | added v2.5
CVP | Line, CVP | | added v2.5
EPLA | Environmental, Plate | | added v2.5
ESWA | Environmental, Swab | | added v2.5
FNA | Aspiration, Fine Needle | | added v2.5
KOFFP | Plate, Cough | | added v2.5
LNA | Line, Arterial | | added v2.5
LNV | Line, Venous | | added v2.5
MARTL | Martin-Lewis Agar | | added v2.5
ML11 | Mod. Martin-Lewis Agar | | added v2.5
MLP | Plate, Martin-Lewis | | added v2.5
NYP | Plate, New York City | | added v2.5
PACE | Pace, Gen-Probe | | added v2.5
PIN | Pinworm Prep | | added v2.5
PNA | Arterial puncture | | added v2.5
PRIME | Pump Prime | | added v2.5
PUMP | Pump Specimen | | added v2.5
QC5 | Quality Control For Micro | | added v2.5
SCLP | Scalp, Fetal Vein | | added v2.5
SCRAPS | Scrapings | | added v2.5
SHA | Shaving | | added v2.5
SWA | Swab | | added v2.5
SWD | Swab, Dacron tipped | | added v2.5
TMAN | Transport Media, Anaerobic | | added v2.5
TMCH | Transport Media, Chalamydia | | added v2.5
TMM4 | Transport Media, M4 | | added v2.5
TMMY | Transport Media, Mycoplasma | | added v2.5
TMOT | Transport Media, | | added v2.5
TMP | Plate, Thayer-Martin | | added v2.5
TMPV | Transport Media, PVA | | added v2.5
TMSC | Transport Media, Stool Culture | | added v2.5
TMUP | Transport Media, Ureaplasma | | added v2.5
TMVI | Transport Media, Viral | | added v2.5
VENIP | Venipuncture | | added v2.5
WOOD | Swab, Wooden Shaft | | added v2.5

4.2.13.489 HL7 Version 2 Table 0489

URL: https://hl7.org/fhir/STU3/v2/0489/index.html

This page is part of the FHIR Specification (v3.0.2: STU 3). The current version which supercedes this version is 4.0.1. For a full list of available versions, see the Directory of published versions

Vocabulary Work Group | Maturity Level: N/A | External | Use Context: Any

This is a table defined as part of HL7 v2 . Related FHIR content: v2 Risk Codes.

Summary

Name: | v2 Risk Codes
Definition: | FHIR Value set/code system definition for HL7 v2 table 0489 (Risk Codes)
Code System URL: | http://hl7.org/fhir/v2/0489
Value Set URL: | http://hl7.org/fhir/ValueSet/v2-0489
OID: | ??
CodeSystem Resource | XML / JSON

ValueSet Resource | XML / JSON

This value set is used in the following places:

* This value set is the designated 'entire code system' value set for v2 Risk Codes

4.2.13.489.1 Code System Content

Risk Codes

Code | Description | Comment | Version
AGG | Aggressive | A danger that can be associated with certain living subjects, including humans. | added v2.5
BHZ | Biohazard | Material contains microorganisms that are an environmental hazard. Must be handled with special care. | added v2.5
BIO | Biological | The dangers associated with normal biological materials. I.e. potential risk of unknown infections. Routine biological materials from living subjects. | added v2.5
COR | Corrosive | Material is corrosive and may cause severe injury to skin, mucous membranes and eyes. Avoid any unprotected contact. | added v2.5
ESC | Escape Risk | The entity is at risk for escaping from containment or control. | added v2.5
EXP | Explosive | Material is an explosive mixture. Keep away from fire, sparks, and heat. | added v2.5
IFL | MaterialDangerInflammable | Material is highly inflammable and in certain mixtures (with air) may lead to explosions. Keep away from fire, sparks and excessive heat. | added v2.5
INF | MaterialDangerInfectious | Material known to be infectious with human pathogenic microorganisms. Those who handle this material must take precautions for their protection. | added v2.5
INJ | Injury Hazard | Material is solid and sharp (e.g. cannulas.) Dispose in hard container. | added v2.5
POI | Poison | Material is poisonous to humans and/or animals. Special care must be taken to avoid incorporation, even of small amounts. | added v2.5
RAD | Radioactive | Material is a source for ionizing radiation and must be handled with special care to avoid injury of those who handle it and to avoid environmental hazards. | added v2.5

4.2.13.490 HL7 Version 2 Table 0490

URL: https://hl7.org/fhir/STU3/v2/0490/index.html

This page is part of the FHIR Specification (v3.0.2: STU 3). The current version which supercedes this version is 4.0.1. For a full list of available versions, see the Directory of published versions

Vocabulary Work Group | Maturity Level: N/A | External | Use Context: Any

This is a table defined as part of HL7 v2 . Related FHIR content: v2 Specimen Reject Reason.

Summary

Name: | v2 Specimen Reject Reason
Definition: | FHIR Value set/code system definition for HL7 v2 table 0490 (Specimen Reject Reason)
Code System URL: | http://hl7.org/fhir/v2/0490
Value Set URL: | http://hl7.org/fhir/ValueSet/v2-0490
OID: | ??
CodeSystem Resource | XML / JSON
ValueSet Resource | XML / JSON

This value set is used in the following places:

* This value set is the designated 'entire code system' value set for v2 Specimen Reject Reason

4.2.13.490.1 Code System Content

Specimen Reject Reason

Code | Description | Comment | Version
EX | Expired | | added v2.5
QS | Quantity not sufficient | | added v2.5
RA | Missing patient ID number | | added v2.5
RB | Broken container | | added v2.5
RC | Clotting | | added v2.5
RD | Missing collection date | | added v2.5
RE | Missing patient name | | added v2.5
RH | Hemolysis | | added v2.5
RI | Identification problem | | added v2.5
RM | Labeling | | added v2.5
RN | Contamination | | added v2.5
RP | Missing phlebotomist ID | | added v2.5
RR | Improper storage | | added v2.5
RS | Name misspelling | | added v2.5

4.2.13.491 HL7 Version 2 Table 0491

URL: https://hl7.org/fhir/STU3/v2/0491/index.html

This page is part of the FHIR Specification (v3.0.2: STU 3). The current version which supercedes this version is 4.0.1. For a full list of available versions, see the Directory of published versions

Vocabulary Work Group | Maturity Level: N/A | External | Use Context: Any

This is a table defined as part of HL7 v2 . Related FHIR content: v2 Specimen Quality.

Summary

Name: | v2 Specimen Quality
Definition: | FHIR Value set/code system definition for HL7 v2 table 0491 (Specimen Quality)
Code System URL: | http://hl7.org/fhir/v2/0491
Value Set URL: | http://hl7.org/fhir/ValueSet/v2-0491
OID: | ??
CodeSystem Resource | XML / JSON
ValueSet Resource | XML / JSON

This value set is used in the following places:

* This value set is the designated 'entire code system' value set for v2 Specimen Quality

4.2.13.491.1 Code System Content

Specimen Quality

Code | Description | Comment | Version
E | Excellent | | added v2.5
F | Fair | | added v2.5
G | Good | | added v2.5
P | Poor | | added v2.5

4.2.13.492 HL7 Version 2 Table 0492

URL: https://hl7.org/fhir/STU3/v2/0492/index.html

This page is part of the FHIR Specification (v3.0.2: STU 3). The current version which supercedes this version is 4.0.1. For a full list of available versions, see the Directory of published versions

Vocabulary Work Group | Maturity Level: N/A | External | Use Context: Any

This is a table defined as part of HL7 v2 . Related FHIR content: v2 Specimen Appropriateness.

Summary

Name: | v2 Specimen Appropriateness
Definition: | FHIR Value set/code system definition for HL7 v2 table 0492 (Specimen Appropriateness)
Code System URL: | http://hl7.org/fhir/v2/0492
Value Set URL: | http://hl7.org/fhir/ValueSet/v2-0492
OID: | ??
CodeSystem Resource | XML / JSON
ValueSet Resource | XML / JSON

This value set is used in the following places:

* This value set is the designated 'entire code system' value set for v2 Specimen Appropriateness

4.2.13.492.1 Code System Content

Specimen Appropriateness

Code | Description | Comment | Version
?? | Inappropriate due to ... | deprecated | added v2.5, removed after v2.7.1
A | Appropriate | | added v2.5
I | Inappropriate | | added v2.5
P | Preferred | | added v2.5

4.2.13.493 HL7 Version 2 Table 0493

URL: https://hl7.org/fhir/STU3/v2/0493/index.html

This page is part of the FHIR Specification (v3.0.2: STU 3). The current version which supercedes this version is 4.0.1. For a full list of available versions, see the Directory of published versions

Vocabulary Work Group | Maturity Level: N/A | External | Use Context: Any

This is a table defined as part of HL7 v2 . Related FHIR content: v2 Specimen Condition.

Summary

Name: | v2 Specimen Condition
Definition: | FHIR Value set/code system definition for HL7 v2 table 0493 (Specimen Condition)
Code System URL: | http://hl7.org/fhir/v2/0493
Value Set URL: | http://hl7.org/fhir/ValueSet/v2-0493
OID: | ??
CodeSystem Resource | XML / JSON
ValueSet Resource | XML / JSON

This value set is used in the following places:

* This value set is the designated 'entire code system' value set for v2 Specimen Condition

4.2.13.493.1 Code System Content

Specimen Condition

Code | Description | Comment | Version
AUT | Autolyzed | | added v2.5
CFU | Centrifuged | | added v2.8
CLOT | Clotted | | added v2.5
CON | Contaminated | | added v2.5
COOL | Cool | | added v2.5
FROZ | Frozen | | added v2.5
HEM | Hemolyzed | | added v2.5
LIVE | Live | | added v2.5
ROOM | Room temperature | | added v2.5
SNR | Sample not received | Deprecated in v 2.8 | added v2.5

4.2.13.494 HL7 Version 2 Table 0494

URL: https://hl7.org/fhir/STU3/v2/0494/index.html

This page is part of the FHIR Specification (v3.0.2: STU 3). The current version which supercedes this version is 4.0.1. For a full list of available versions, see the Directory of published versions

Vocabulary Work Group | Maturity Level: N/A | External | Use Context: Any

This is a table defined as part of HL7 v2 . Related FHIR content: v2 Specimen Child Role.

Summary

Name: | v2 Specimen Child Role
Definition: | FHIR Value set/code system definition for HL7 v2 table 0494 (Specimen Child Role)
Code System URL: | http://hl7.org/fhir/v2/0494
Value Set URL: | http://hl7.org/fhir/ValueSet/v2-0494
OID: | ??
CodeSystem Resource | XML / JSON
ValueSet Resource | XML / JSON

This value set is used in the following places:

* This value set is the designated 'entire code system' value set for v2 Specimen Child Role

4.2.13.494.1 Code System Content

Specimen Child Role

Code | Description | Comment | Version
A | Aliquot | | added v2.5
C | Component | | added v2.5
M | Modified from original specimen | | added v2.5

4.2.13.495 HL7 Version 2 Table 0495

URL: https://hl7.org/fhir/STU3/v2/0495/index.html

This page is part of the FHIR Specification (v3.0.2: STU 3). The current version which supercedes this version is 4.0.1. For a full list of available versions, see the Directory of published versions

Vocabulary Work Group | Maturity Level: N/A | External | Use Context: Any

This is a table defined as part of HL7 v2 . Related FHIR content: v2 Body Site Modifier.

Summary

Name: | v2 Body Site Modifier
Definition: | FHIR Value set/code system definition for HL7 v2 table 0495 (Body Site Modifier)
Code System URL: | http://hl7.org/fhir/v2/0495
Value Set URL: | http://hl7.org/fhir/ValueSet/v2-0495
OID: | ??
CodeSystem Resource | XML / JSON
ValueSet Resource | XML / JSON

This value set is used in the following places:

* This value set is the designated 'entire code system' value set for v2 Body Site Modifier

4.2.13.495.1 Code System Content

Body Site Modifier

Code | Description | Deutsch (German) | Comment | Version
ANT | Anterior | | | added v2.5
BIL | Bilateral | | | added v2.5
DIS | Distal | | | added v2.5
EXT | External | | | added v2.5

L | Left | links | | added v2.5
LAT | Lateral | | | added v2.5
LLQ | Quadrant, Left Lower | | | added v2.5
LOW | Lower | | | added v2.5
LUQ | Quadrant, Left Upper | | | added v2.5
MED | Medial | | | added v2.5
POS | Posterior | | | added v2.5
PRO | Proximal | | | added v2.5
R | Right | | | added v2.5
RLQ | Quadrant, Right Lower | | | added v2.5
RUQ | Quadrant, Right Upper | | | added v2.5
UPP | Upper | | | added v2.5

4.2.13.496 HL7 Version 2 Table 0496

URL: https://hl7.org/fhir/STU3/v2/0496/index.html

This page is part of the FHIR Specification (v3.0.2: STU 3). The current version which supercedes this version is 4.0.1. For a full list of available versions, see the Directory of published versions

Vocabulary Work Group | Maturity Level: N/A | External | Use Context: Any

This is a table defined as part of HL7 v2 . Related FHIR content: v2 Consent Type.

Summary

Name: | v2 Consent Type
Definition: | FHIR Value set/code system definition for HL7 v2 table 0496 (Consent Type)
Code System URL: | http://hl7.org/fhir/v2/0496
Value Set URL: | http://hl7.org/fhir/ValueSet/v2-0496
OID: | ??
CodeSystem Resource | XML / JSON
ValueSet Resource | XML / JSON

This value set is used in the following places:

* This value set is the designated 'entire code system' value set for v2 Consent Type

4.2.13.496.1 Code System Content

Consent Type

Code | Description | Comment | Version
001 | Release of Information/MR / Authorization to Disclosure Protected Health Information | Release of Info/ Disclosure | added v2.5
002 | Medical Procedure (invasive) | Medical Treatment/ Procedure | added v2.5
003 | Acknowledge Receipt of Privacy Notice | Acknowledgement/ Notification | added v2.5
004 | Abortion | Medical Treatment/ Procedure | added v2.5
005 | Abortion/Laminaria | Medical Treatment/ Procedure | added v2.5
006 | Accutane - Information | Medical Treatment/ Procedure | added v2.5
007 | Accutane - Woman | Medical Treatment/ Procedure | added v2.5
008 | Advanced Beneficiary Notice | Acknowledgement/ Notification | added v2.5
009 | AFP (Alpha Fetoprotein) Screening | Medical Treatment/ Procedure | added v2.5
010 | Amniocentesis (consent & refusal) | Medical Treatment/ Procedure | added v2.5
011 | Anatomical Gift (organ donation) | Administrative | added v2.5
012 | Anesthesia - Complications | Medical Treatment/ Procedure | added v2.5
013 | Anesthesia - Questionnaire | Medical Treatment/ Procedure | added v2.5
014 | Angiogram | Medical Treatment/ Procedure | added v2.5
015 | Angioplasty | Medical Treatment/ Procedure | added v2.5
016 | Anticancer Drugs | Medical Treatment/ Procedure | added v2.5
017 | Antipsychotic Medications | Medical Treatment/ Procedure | added v2.5
018 | Arthrogram | Medical Treatment/ Procedure | added v2.5
019 | Autopsy | Administrative | added v2.5
020 | AZT Therapy | Medical Treatment/ Procedure | added v2.5
021 | Biliary Drainage | Medical Treatment/ Procedure | added v2.5
022 | Biliary Stone Extraction | Medical Treatment/ Procedure | added v2.5
023 | Biopsy | Medical Treatment/ Procedure | added v2.5
024 | Bleeding Time Test | Medical Treatment/ Procedure | added v2.5
025 | Bronchogram | Medical Treatment/ Procedure | added v2.5
026 | Cardiac Catheterization | Medical Treatment/ Procedure | added v2.5
027 | Coronary Angiography | Medical Treatment/ Procedure | added v2.5
028 | "" "" w/o Surgery Capability | Medical Treatment/ Procedure | added v2.5
029 | Cataract Op/Implant of FDA Aprvd Lens | Medical Treatment/ Procedure | added v2.5
030 | Cataract Op/Implant of Investigational Lens | Medical Treatment/ Procedure | added v2.5
031 | Cataract Surgery | Medical Treatment/ Procedure | added v2.5
032 | Cholera Immunization | Medical Treatment/ Procedure | added v2.5
033 | Cholesterol Screening | Medical Treatment/ Procedure | added v2.5
034 | Circumcision - Newborn | Medical Treatment/ Procedure | added v2.5
035 | Colonoscopy | Medical Treatment/ Procedure | added v2.5

036 | Contact Lenses | Medical Treatment/ Procedure | added v2.5
037 | CT Scan - Cervical & Lumbar | Medical Treatment/ Procedure | added v2.5
038 | CT Scan w/ IV Contrast Media into Vein | Medical Treatment/ Procedure | added v2.5
039 | CVS (Chorionic Villus) Sampling | Medical Treatment/ Procedure | added v2.5
040 | Cystospy | Medical Treatment/ Procedure | added v2.5
041 | Disclosure of Protected Health Information to Family/Friends | Release of Info/ Disclosure | added v2.5
042 | D & C and Conization | Medical Treatment/ Procedure | added v2.5
043 | Dacryocystogram | Medical Treatment/ Procedure | added v2.5
044 | Diagnostic Isotope | Medical Treatment/ Procedure | added v2.5
045 | Drainage of an Abscess | Medical Treatment/ Procedure | added v2.5
046 | Drug Screening | Medical Treatment/ Procedure | added v2.5
047 | Electronic Monitoring of Labor - Refusal | Medical Treatment/ Procedure | added v2.5
048 | Endometrial Biopsy | Medical Treatment/ Procedure | added v2.5
049 | Endoscopy/Sclerosis of Esophageal Varices | Medical Treatment/ Procedure | added v2.5
050 | ERCP | Medical Treatment/ Procedure | added v2.5
051 | Exposure to reportable Communicable Disease | Medical Treatment/ Procedure | added v2.5
052 | External Version | Medical Treatment/ Procedure | added v2.5
053 | Fluorescein Angioscopy | Medical Treatment/ Procedure | added v2.5
054 | Hepatitis B - Consent/Declination | Medical Treatment/ Procedure | added v2.5
055 | Herniogram | Medical Treatment/ Procedure | added v2.5
056 | HIV Test - Consent Refusal | Medical Treatment/ Procedure | added v2.5
057 | HIV Test - Disclosure | Medical Treatment/ Procedure | added v2.5
058 | HIV Test - Prenatal | Medical Treatment/ Procedure | added v2.5
059 | Home IV Treatment Program | Medical Treatment/ Procedure | added v2.5
060 | Home Parenteral Treatment Program | Medical Treatment/ Procedure | added v2.5
061 | Hysterectomy | Medical Treatment/ Procedure | added v2.5
062 | Hysterosalpingogram | Medical Treatment/ Procedure | added v2.5
063 | Injection Slip/ Consent | Medical Treatment/ Procedure | added v2.5
064 | Intrauterine Device | Medical Treatment/ Procedure | added v2.5
065 | Intrauterine Device/Sterilization | Medical Treatment/ Procedure | added v2.5
066 | Intravascular Infusion of Streptokinase/Urokinase | Medical Treatment/ Procedure | added v2.5
067 | Intravenous Cholangiogram | Medical Treatment/ Procedure | added v2.5
068 | Intravenous Digital Angiography | Medical Treatment/ Procedure | added v2.5
069 | Iodine Administration | Medical Treatment/ Procedure | added v2.5
070 | ISG | Medical Treatment/ Procedure | added v2.5
071 | IVP | Medical Treatment/ Procedure | added v2.5
072 | Laser Photocoagulation | Medical Treatment/ Procedure | added v2.5
073 | Laser treatment | Medical Treatment/ Procedure | added v2.5
074 | Lithium Carbonate | Medical Treatment/ Procedure | added v2.5
075 | Liver Biopsy | Medical Treatment/ Procedure | added v2.5
076 | Lumbar Puncture | Medical Treatment/ Procedure | added v2.5
077 | Lymphangiogram | Medical Treatment/ Procedure | added v2.5
078 | MAO Inhibitors | Medical Treatment/ Procedure | added v2.5
079 | Med, Psych, and/or Drug/Alcohol | Release of Info/ Disclosure | added v2.5
080 | Medical Treatment - Refusal | Administrative | added v2.5
081 | Morning-after Pill | Medical Treatment/ Procedure | added v2.5
082 | MRI - Adult | Medical Treatment/ Procedure | added v2.5
083 | MRI - Pediatric | Medical Treatment/ Procedure | added v2.5
084 | Myelogram | Medical Treatment/ Procedure | added v2.5
085 | Needle Biopsy | Medical Treatment/ Procedure | added v2.5
086 | Needle Biopsy of Lung | Medical Treatment/ Procedure | added v2.5
087 | Newborn Treatment and Release | Medical Treatment/ Procedure | added v2.5
088 | Norplant Subdermal Birth Control Implant | Medical Treatment/ Procedure | added v2.5
089 | Operations, Anesthesia, Transfusions | Medical Treatment/ Procedure | added v2.5
090 | Oral Contraceptives | Medical Treatment/ Procedure | added v2.5
091 | Organ Donation | Administrative | added v2.5
092 | Patient Permits, Consents | Administrative | added v2.5
093 | Patient Treatment Permit, Release & Admission | Administrative | added v2.5
094 | Penile Injections | Medical Treatment/ Procedure | added v2.5
095 | Percutaneous Nephrostomy | Medical Treatment/ Procedure | added v2.5
096 | Percutaneous Transhepatic Cholangiogram | Medical Treatment/ Procedure | added v2.5
097 | Photographs | Release of Info/ Disclosure | added v2.5
098 | Photographs - Employee | Release of Info/ Disclosure | added v2.5
099 | Photographs - Medical Research | Release of Info/ Disclosure | added v2.5
100 | Photographs - news Media | Release of Info/ Disclosure | added v2.5
101 | Psychiatric Admission - Next of Kin | Medical Treatment/ Procedure | added v2.5
102 | Psychiatric Information During Hospital Stay | Release of Info/ Disclosure | added v2.5
103 | Public Release of Information | Release of Info/ Disclosure | added v2.5
104 | Radiologic Procedure | Medical Treatment/ Procedure | added v2.5
105 | Refusal of Treatment | Administrative | added v2.5
106 | Release of Body | Administrative | added v2.5
107 | Release of Limb | Administrative | added v2.5

108 | Rh Immune Globulin | Medical Treatment/ Procedure | added v2.5
109 | Rights of Medical Research Participants | Administrative | added v2.5
110 | Request to Restrict Access/Disclosure to Medical Record/Protected Health Information | Release of Info/ Disclosure | added v2.5
111 | Request for Remain Anonymous | Release of Info/ Disclosure | added v2.5
112 | Seat Belt Exemption | Administrative | added v2.5
113 | Sialogram | Medical Treatment/ Procedure | added v2.5
1137 | Voiding Cystogram | Medical Treatment/ Procedure | added v2.5
114 | Sigmoidoscopy | Medical Treatment/ Procedure | added v2.5
115 | Sterilization - Anesthesia & Medical Services | Medical Treatment/ Procedure | added v2.5
116 | Sterilization -Federally Funded | Medical Treatment/ Procedure | added v2.5
117 | Sterilization - Female | Medical Treatment/ Procedure | added v2.5
118 | Sterilization - Laparoscopy/Pomeroy | Medical Treatment/ Procedure | added v2.5
119 | Sterilization - Non-Federally Funded | Medical Treatment/ Procedure | added v2.5
120 | Sterilization - Secondary | Medical Treatment/ Procedure | added v2.5
121 | Tranquilizers | Medical Treatment/ Procedure | added v2.5
122 | Transfer - Acknowledgement | Medical Treatment/ Procedure | added v2.5
123 | Transfer - Authorization | Medical Treatment/ Procedure | added v2.5
124 | Transfer Certification - Physician | Medical Treatment/ Procedure | added v2.5
125 | Transfer/Discharge Request | Medical Treatment/ Procedure | added v2.5
126 | Transfer for Non-Medical Reasons | Medical Treatment/ Procedure | added v2.5
127 | Transfer - Interfaculty Neonatal | Medical Treatment/ Procedure | added v2.5
128 | Transfer Refusal | Medical Treatment/ Procedure | added v2.5
129 | Transfer Refusal of Further Treatment | Medical Treatment/ Procedure | added v2.5
130 | Treadmill & EKG | Medical Treatment/ Procedure | added v2.5
131 | Treadmill, Thallium-201 | Medical Treatment/ Procedure | added v2.5
132 | Typhoid | Medical Treatment/ Procedure | added v2.5
133 | Use of Investigational Device | Medical Treatment/ Procedure | added v2.5
134 | Use of Investigational Drug | Medical Treatment/ Procedure | added v2.5
135 | Venogram | Medical Treatment/ Procedure | added v2.5
136 | Videotape | Release of Info/ Disclosure | added v2.5

4.2.13.497 HL7 Version 2 Table 0497

URL: https://hl7.org/fhir/STU3/v2/0497/index.html

This page is part of the FHIR Specification (v3.0.2: STU 3). The current version which supercedes this version is 4.0.1. For a full list of available versions, see the Directory of published versions

Vocabulary Work Group | Maturity Level: N/A | External | Use Context: Any

This is a table defined as part of HL7 v2 . Related FHIR content: v2 Consent Mode.

Summary

Name: | v2 Consent Mode
Definition: | FHIR Value set/code system definition for HL7 v2 table 0497 (Consent Mode)
Code System URL: | http://hl7.org/fhir/v2/0497
Value Set URL: | http://hl7.org/fhir/ValueSet/v2-0497
OID: | ??
CodeSystem Resource | XML / JSON
ValueSet Resource | XML / JSON

This value set is used in the following places:

* This value set is the designated 'entire code system' value set for v2 Consent Mode

4.2.13.497.1 Code System Content

Consent Mode

Code | Description | Nederlands (Dutch) | Comment | Version
T | Telephone | Telefonisch | | added v2.5
V | Verbal | Mondeling | | added v2.5
W | Written | Op schrift | | added v2.5

4.2.13.498 HL7 Version 2 Table 0498

URL: https://hl7.org/fhir/STU3/v2/0498/index.html

This page is part of the FHIR Specification (v3.0.2: STU 3). The current version which supercedes this version is 4.0.1. For a full list of available versions, see the Directory of published versions

Vocabulary Work Group | Maturity Level: N/A | External | Use Context: Any

This is a table defined as part of HL7 v2 . Related FHIR content: v2 Consent Status.

Summary

Name: | v2 Consent Status
Definition: | FHIR Value set/code system definition for HL7 v2 table 0498 (Consent Status)
Code System URL: | http://hl7.org/fhir/v2/0498

Value Set URL: | http://hl7.org/fhir/ValueSet/v2-0498
OID: | ??
CodeSystem Resource | XML / JSON
ValueSet Resource | XML / JSON

This value set is used in the following places:

* This value set is the designated 'entire code system' value set for v2 Consent Status

4.2.13.498.1 Code System Content

Consent Status

Code | Description | Nederlands (Dutch) | Comment | Version
A | Active - Consent has been granted | Actief - Toestemming is gegeven | | added v2.5
B | Bypassed (Consent not sought) | Overgeslagen - Toestemming is niet gevraagd | | added v2.5
L | Limited - Consent has been granted with limitations | Beperkt - Toestemming is gegeven met beperkingen | | added v2.5
P | Pending - Consent has not yet been sought | In bewerking - Toestemming is nog niet gevraagd | | added v2.5
R | Refused - Consent has been refused | Geweigerd - Toestemming is geweigerd | | added v2.5
X | Rescinded - Consent was initially granted, but was subsequently revoked or ended. | Ingetrokken - Toestemming is gegeven maar vervolgens ingetrokken of beëindigd | | added v2.5

4.2.13.499 HL7 Version 2 Table 0499

URL: https://hl7.org/fhir/STU3/v2/0499/index.html

This page is part of the FHIR Specification (v3.0.2: STU 3). The current version which supercedes this version is 4.0.1. For a full list of available versions, see the Directory of published versions

Vocabulary Work Group | Maturity Level: N/A | External | Use Context: Any

This is a table defined as part of HL7 v2 . Related FHIR content: v2 Consent Bypass Reason.

Summary

Name: | v2 Consent Bypass Reason
Definition: | FHIR Value set/code system definition for HL7 v2 table 0499 (Consent Bypass Reason)
Code System URL: | http://hl7.org/fhir/v2/0499
Value Set URL: | http://hl7.org/fhir/ValueSet/v2-0499
OID: | ??
CodeSystem Resource | XML / JSON
ValueSet Resource | XML / JSON

This value set is used in the following places:

* This value set is the designated 'entire code system' value set for v2 Consent Bypass Reason

4.2.13.499.1 Code System Content

Consent Bypass Reason

Code | Description | Nederlands (Dutch) | Comment | Version
E | Emergency | Noodgeval | | added v2.5
PJ | Professional Judgment | Professioneel oordeel | | added v2.5

4.2.13.500 HL7 Version 2 Table 0500

URL: https://hl7.org/fhir/STU3/v2/0500/index.html

This page is part of the FHIR Specification (v3.0.2: STU 3). The current version which supercedes this version is 4.0.1. For a full list of available versions, see the Directory of published versions

Vocabulary Work Group | Maturity Level: N/A | External | Use Context: Any

This is a table defined as part of HL7 v2 . Related FHIR content: v2 Consent Disclosure Level.

Summary

Name: | v2 Consent Disclosure Level
Definition: | FHIR Value set/code system definition for HL7 v2 table 0500 (Consent Disclosure Level)
Code System URL: | http://hl7.org/fhir/v2/0500
Value Set URL: | http://hl7.org/fhir/ValueSet/v2-0500
OID: | ??
CodeSystem Resource | XML / JSON
ValueSet Resource | XML / JSON

This value set is used in the following places:

* This value set is the designated 'entire code system' value set for v2 Consent Disclosure Level

4.2.13.500.1 Code System Content

Consent Disclosure Level

Code | Description | Nederlands (Dutch) | Comment | Version

F | Full Disclosure | Volledige toelichting | | added v2.5
N | No Disclosure | Geen toelichting | | added v2.5
P | Partial Disclosure | Gedeeltelijke toelichting | | added v2.5

4.2.13.501 HL7 Version 2 Table 0501

URL: https://hl7.org/fhir/STU3/v2/0501/index.html

This page is part of the FHIR Specification (v3.0.2: STU 3). The current version which supercedes this version is 4.0.1. For a full list of available versions, see the Directory of published versions

Vocabulary Work Group | Maturity Level: N/A | External | Use Context: Any

This is a table defined as part of HL7 v2 . Related FHIR content: v2 Consent Non-Disclosure Reason.

Summary

Name: | v2 Consent Non-Disclosure Reason
Definition: | FHIR Value set/code system definition for HL7 v2 table 0501 (Consent Non-Disclosure Reason)
Code System URL: | http://hl7.org/fhir/v2/0501
Value Set URL: | http://hl7.org/fhir/ValueSet/v2-0501
OID: | ??
CodeSystem Resource | XML / JSON
ValueSet Resource | XML / JSON

This value set is used in the following places:

* This value set is the designated 'entire code system' value set for v2 Consent Non-Disclosure Reason

4.2.13.501.1 Code System Content

Consent Non-Disclosure Reason

Code | Description | Nederlands (Dutch) | Comment | Version
E | Emergency | Noodgeval | | added v2.5
PR | Patient Request | Op verzoek patiënt | | added v2.5
RX | Rx Private | Medicatie privacy | | added v2.5

4.2.13.502 HL7 Version 2 Table 0502

URL: https://hl7.org/fhir/STU3/v2/0502/index.html

This page is part of the FHIR Specification (v3.0.2: STU 3). The current version which supercedes this version is 4.0.1. For a full list of available versions, see the Directory of published versions

Vocabulary Work Group | Maturity Level: N/A | External | Use Context: Any

This is a table defined as part of HL7 v2 . Related FHIR content: v2 Non-Subject Consenter Reason.

Summary

Name: | v2 Non-Subject Consenter Reason
Definition: | FHIR Value set/code system definition for HL7 v2 table 0502 (Non-Subject Consenter Reason)
Code System URL: | http://hl7.org/fhir/v2/0502
Value Set URL: | http://hl7.org/fhir/ValueSet/v2-0502
OID: | ??
CodeSystem Resource | XML / JSON
ValueSet Resource | XML / JSON

This value set is used in the following places:

* This value set is the designated 'entire code system' value set for v2 Non-Subject Consenter Reason

4.2.13.502.1 Code System Content

Non-Subject Consenter Reason

Code | Description | Nederlands (Dutch) | Comment | Version
LM | Legally mandated | Wettelijk vereist | | added v2.5
MIN | Subject is a minor | Subject is minderjairg | | added v2.5
NC | Subject is not competent to consent | Subject is niet in staat tot toestemming | | added v2.5

4.2.13.503 HL7 Version 2 Table 0503

URL: https://hl7.org/fhir/STU3/v2/0503/index.html

This page is part of the FHIR Specification (v3.0.2: STU 3). The current version which supercedes this version is 4.0.1. For a full list of available versions, see the Directory of published versions

Vocabulary Work Group | Maturity Level: N/A | External | Use Context: Any

This is a table defined as part of HL7 v2 . Related FHIR content: v2 Sequence/Results Flag.

Summary

Name: | v2 Sequence/Results Flag

Definition: | FHIR Value set/code system definition for HL7 v2 table 0503 (Sequence/Results Flag)
Code System URL: | http://hl7.org/fhir/v2/0503
Value Set URL: | http://hl7.org/fhir/ValueSet/v2-0503
OID: | ??
CodeSystem Resource | XML / JSON
ValueSet Resource | XML / JSON

This value set is used in the following places:

* This value set is the designated 'entire code system' value set for v2 Sequence/Results Flag

4.2.13.503.1 Code System Content

Sequence/Results Flag

Code | Description | Comment | Version
C | Cyclical | Used for indicating a repeating cycle of service requests; for example, individual intravenous solutions used in a cyclical sequence (a.k.a. "Alternating IVs"). This value would be compatible with linking separate service requests or with having all cycli | added v2.5
R | Reserved for future use | | added v2.5
S | Sequential | | added v2.5

4.2.13.504 HL7 Version 2 Table 0504

URL: https://hl7.org/fhir/STU3/v2/0504/index.html

This page is part of the FHIR Specification (v3.0.2: STU 3). The current version which supercedes this version is 4.0.1. For a full list of available versions, see the Directory of published versions

Vocabulary Work Group | Maturity Level: N/A | External | Use Context: Any

This is a table defined as part of HL7 v2 . Related FHIR content: v2 Sequence Condition Code.

Summary

Name: | v2 Sequence Condition Code
Definition: | FHIR Value set/code system definition for HL7 v2 table 0504 (Sequence Condition Code)
Code System URL: | http://hl7.org/fhir/v2/0504
Value Set URL: | http://hl7.org/fhir/ValueSet/v2-0504
OID: | ??
CodeSystem Resource | XML / JSON
ValueSet Resource | XML / JSON

This value set is used in the following places:

* This value set is the designated 'entire code system' value set for v2 Sequence Condition Code

4.2.13.504.1 Code System Content

Sequence Condition Code

Code | Description | Comment | Version
EE | End related service request(s), end current service request. | | added v2.5
ES | End related service request(s), start current service request. | | added v2.5
SE | Start related service request(s), end current service request. | | added v2.5
SS | Start related service request(s), start current service request. | | added v2.5

4.2.13.505 HL7 Version 2 Table 0505

URL: https://hl7.org/fhir/STU3/v2/0505/index.html

This page is part of the FHIR Specification (v3.0.2: STU 3). The current version which supercedes this version is 4.0.1. For a full list of available versions, see the Directory of published versions

Vocabulary Work Group | Maturity Level: N/A | External | Use Context: Any

This is a table defined as part of HL7 v2 . Related FHIR content: v2 Cyclic Entry/Exit Indicator.

Summary

Name: | v2 Cyclic Entry/Exit Indicator
Definition: | FHIR Value set/code system definition for HL7 v2 table 0505 (Cyclic Entry/Exit Indicator)
Code System URL: | http://hl7.org/fhir/v2/0505
Value Set URL: | http://hl7.org/fhir/ValueSet/v2-0505
OID: | ??
CodeSystem Resource | XML / JSON
ValueSet Resource | XML / JSON

This value set is used in the following places:

* This value set is the designated 'entire code system' value set for v2 Cyclic Entry/Exit Indicator

4.2.13.505.1 Code System Content

Cyclic Entry/Exit Indicator

Code | Description | Nederlands (Dutch) | Comment | Version
| The last service request in a cyclic group. | Het laatste serviceverzoek in een cyclische groep | | added v2.5
* | The first service request in a cyclic group | Het eerste serviceverzoek in een cyclische groep | | added v2.5

4.2.13.506 HL7 Version 2 Table 0506

URL: https://hl7.org/fhir/STU3/v2/0506/index.html

This page is part of the FHIR Specification (v3.0.2: STU 3). The current version which supercedes this version is 4.0.1. For a full list of available versions, see the Directory of published versions

Vocabulary Work Group | Maturity Level: N/A | External | Use Context: Any

This is a table defined as part of HL7 v2 . Related FHIR content: v2 Service Request Relationship.

Summary

Name: | v2 Service Request Relationship
Definition: | FHIR Value set/code system definition for HL7 v2 table 0506 (Service Request Relationship)
Code System URL: | http://hl7.org/fhir/v2/0506
Value Set URL: | http://hl7.org/fhir/ValueSet/v2-0506
OID: | ??
CodeSystem Resource | XML / JSON
ValueSet Resource | XML / JSON

This value set is used in the following places:

* This value set is the designated 'entire code system' value set for v2 Service Request Relationship

4.2.13.506.1 Code System Content

Service Request Relationship

Code | Description | Comment | Version
C | Compound | A compound is an extempo order which may be made up of multiple drugs. For example, many hospitals have a standard item called "Magic Mouthwash". The item is ordered that way by the physician. The extempo items will contain multiple products, such as Ma | added v2.5
E | Exclusive | An exclusive order is an order where only one of the multiple items should be administered at any one dosage time. The nurse may chose between the alternatives, but should only give ONE of them. An example would be: Phenergan 25 mg PO, IM or R q6h prn (| added v2.5
N | Nurse prerogative | Where a set of two or more orders exist and the Nurse, or other caregiver, has the prerogative to choose which order will be administered at a particular point in time. For example,<p> Milk of Magnesia PO 30 ml qhs (at bedtime)<p> Dulcolax Supp R @ hs pr | added v2.5
S | Simultaneous | A simultaneous order is 2 or more drugs which are ordered to be given at the same time. A common example of this would be Demerol and Phenergan (Phenergan is given with the Demerol to control the nausea that Demerol can cause). The order could be: Demer | added v2.5
T | Tapering | A tapering order is one in which the same drug is used, but it has a declining dosage over a number of days.<p>For example, Decadron 0.5 mg is often ordered this way. The order would look like this:<p> Decadron 0.5 mg qid (four times a day) for 2 days, t | added v2.5

4.2.13.507 HL7 Version 2 Table 0507

URL: https://hl7.org/fhir/STU3/v2/0507/index.html

This page is part of the FHIR Specification (v3.0.2: STU 3). The current version which supercedes this version is 4.0.1. For a full list of available versions, see the Directory of published versions

Vocabulary Work Group | Maturity Level: N/A | External | Use Context: Any

This is a table defined as part of HL7 v2 . Related FHIR content: v2 Observation Result Handling.

Summary

Name: | v2 Observation Result Handling
Definition: | FHIR Value set/code system definition for HL7 v2 table 0507 (Observation Result Handling)
Code System URL: | http://hl7.org/fhir/v2/0507
Value Set URL: | http://hl7.org/fhir/ValueSet/v2-0507
OID: | ??
CodeSystem Resource | XML / JSON
ValueSet Resource | XML / JSON

This value set is used in the following places:

* This value set is the designated 'entire code system' value set for v2 Observation Result Handling

4.2.13.507.1 Code System Content

Observation Result Handling

Code | Description | Comment | Version
A | Alert provider when abnormal | | added v2.7.1
BCC | Blind Copy | deprecated | added v2.7.1, removed after v2.7.1
CC | Copies Requested | deprecated | added v2.7.1, removed after v2.7.1
F | Film-with-patient | | added v2.5
N | Notify provider when ready | | added v2.5

4.2.13.508 HL7 Version 2 Table 0508

URL: https://hl7.org/fhir/STU3/v2/0508/index.html

This page is part of the FHIR Specification (v3.0.2: STU 3). The current version which supercedes this version is 4.0.1. For a full list of available versions, see the Directory of published versions

Vocabulary Work Group | Maturity Level: N/A | External | Use Context: Any

This is a table defined as part of HL7 v2 . Related FHIR content: v2 Blood Product Processing Requirements.

Summary

Name: | v2 Blood Product Processing Requirements
Definition: | FHIR Value set/code system definition for HL7 v2 table 0508 (Blood Product Processing Requirements)
Code System URL: | http://hl7.org/fhir/v2/0508
Value Set URL: | http://hl7.org/fhir/ValueSet/v2-0508
OID: | ??
CodeSystem Resource | XML / JSON
ValueSet Resource | XML / JSON

This value set is used in the following places:

* This value set is the designated 'entire code system' value set for v2 Blood Product Processing Requirements

4.2.13.508.1 Code System Content

Blood Product Processing Requirements

Code | Description | Comment | Version
AU | Autologous Unit | | added v2.5
CM | CMV Negative | | added v2.5
CS | CMV Safe | | added v2.5
DI | Directed Unit | | added v2.5
FR | Fresh unit | | added v2.5
HB | Hemoglobin S Negative | | added v2.5
HL | HLA Matched | | added v2.5
IG | IgA Deficient | | added v2.5
IR | Irradiated | | added v2.5
LR | Leukoreduced | | added v2.5
WA | Washed | | added v2.5

4.2.13.510 HL7 Version 2 Table 0510

URL: https://hl7.org/fhir/STU3/v2/0510/index.html

This page is part of the FHIR Specification (v3.0.2: STU 3). The current version which supercedes this version is 4.0.1. For a full list of available versions, see the Directory of published versions

Vocabulary Work Group | Maturity Level: N/A | External | Use Context: Any

This is a table defined as part of HL7 v2 . Related FHIR content: v2 Blood Product Dispense Status.

Summary

Name: | v2 Blood Product Dispense Status
Definition: | FHIR Value set/code system definition for HL7 v2 table 0510 (Blood Product Dispense Status)
Code System URL: | http://hl7.org/fhir/v2/0510
Value Set URL: | http://hl7.org/fhir/ValueSet/v2-0510
OID: | ??
CodeSystem Resource | XML / JSON
ValueSet Resource | XML / JSON

This value set is used in the following places:

* This value set is the designated 'entire code system' value set for v2 Blood Product Dispense Status

4.2.13.510.1 Code System Content

Blood Product Dispense Status

Code | Description | Comment | Version
CR | Released into inventory for general availability | Status determined by Filler | added v2.5
DS | Dispensed to patient location | Status determined by Filler | added v2.5
PT | Presumed transfused (dispensed and not returned) | Status determined by Filler | added v2.5
RA | Returned unused/no longer needed | Status determined by Filler | added v2.5
RD | Reserved and ready to dispense | Status determined by Filler | added v2.5
RE | Released (no longer allocated for the patient) | Status determined by Placer or Filler | added v2.5
RI | Received into inventory (for specified patient) | Status determined by Filler | added v2.5
RL | Returned unused/keep linked to patient for possible use later | Status determined by Filler | added v2.5
RQ | Request to dispense blood product | Status determined by Placer | added v2.5
RS | Reserved (ordered and product allocated for the patient) | Status determined by Filler | added v2.5
WA | Wasted (product no longer viable) | Status determined by Filler | added v2.5