FHIR-STU3 — Terminology Module — part 4 of 4 (sections 4.3.2.41 – 4.11.9)

Source: HL7 FHIR STU3 (v3.0.2). Text-only edition for AI ingestion (NotebookLM); pages follow the source order (its table of contents when one exists).

4.3.2.41 HL7 v3 Code System EntityClass

URL: https://hl7.org/fhir/STU3/v3/EntityClass/cs.html

This page is part of the FHIR Specification (v3.0.2: STU 3). The current version which supercedes this version is 4.0.1. For a full list of available versions, see the Directory of published versions

Vocabulary Work Group | Maturity Level: N/A | External | Use Context: Any

This code system (http://hl7.org/fhir/v3/EntityClass) is defined as part of HL7 v3.

Summary

Defining URL: | http://hl7.org/fhir/v3/EntityClass
Name: | v3 Code System EntityClass
Definition: | Classifies the Entity class and all of its subclasses. The terminology is hierarchical. At the top is this HL7-defined domain of high-level categories (such as represented by the Entity subclasses). Each of these terms must be harmonized and is specializable. The value sets beneath are drawn from multiple, frequently external, domains that reflect much more fine-grained typing.
OID: | 2.16.840.1.113883.5.41 (for OID based terminology systems)
Source Resource | XML / JSON

This Code system is used in the following value sets:

* EntityClassOrganization (A social or legal structure formed by human beings.)

* EntityClassDevice (A subtype of ManufacturedMaterial used in an activity, without being substantially changed through that activity. The kind of device is identified by the code attribute inherited from Entity. Usage: This includes durable (reusable) medical equipment as well as disposable equipment.)

* EntityClassPlace (A physicial place or site with its containing structure. May be natural or man-made. The geographic position of a place may or may not be constant.)

* EntityClassRoot (Corresponds to the Entity class)

* EntityClassLivingSubject (Anything that essentially has the property of life, independent of current state (a dead human corpse is still essentially a living subject.))

* EntityClassManufacturedMaterial (Corresponds to the ManufacturedMaterial class)

* v3 Code System EntityClass (Classifies the Entity class and all of its subclasses. The terminology is hierarchical. At the top is this HL7-defined domain of high-level categories (such as represented by the Entity subclasses). Each of these terms must be harmonized and is specializable. The value sets beneath are drawn from multiple, frequently external, domains that reflect much more fine-grained typing.)

4.3.2.41.1 Code System Content

Release Date: 2016-11-11

Level | Code | Display | Definition
1 | ENT | entity | Corresponds to the Entity class
2 | HCE | health chart entity | A health chart included to serve as a document receiving entity in the management of medical records.
2 | LIV | living subject | Anything that essentially has the property of life, independent of current state (a dead human corpse is still essentially a living subject).
3 | NLIV | non-person living subject | A subtype of living subject that includes all living things except the species Homo Sapiens.
4 | ANM | animal | A living subject from the animal kingdom.
4 | MIC | microorganism | All single celled living organisms including protozoa, bacteria, yeast, viruses, etc.
4 | PLNT | plant | A living subject from the order of plants.
3 | PSN | person | A living subject of the species homo sapiens.
2 | MAT | material | Any thing that has extension in space and mass, may be of living or non-living origin.
3 | CHEM | chemical substance | A substance that is fully defined by an organic or inorganic chemical formula, includes mixtures of other chemical substances. Refine using, e.g., IUPAC codes.
3 | FOOD | food | Naturally occurring, processed or manufactured entities that are primarily used as food for humans and animals.
3 | MMAT | manufactured material | Corresponds to the ManufacturedMaterial class
4 | CONT | container | A container of other entities.
5 | HOLD | holder | A type of container that can hold other containers or other holders.
4 | DEV | device | A subtype of ManufacturedMaterial used in an activity, without being substantially changed through that activity. The kind of device is identified by the code attribute inherited from Entity. Usage: This includes durable (reusable) medical equipment as well as disposable equipment.
5 | CER | certificate representation | A physical artifact that stores information about the granting of authorization.
5 | MODDV | imaging modality | Class to contain unique attributes of diagnostic imaging equipment.
2 | ORG | organization | A social or legal structure formed by human beings.
3 | PUB | public institution | An agency of the people of a state often assuming some authority over a certain matter. Includes government, governmental agencies, associations.
3 | STATE | state | A politically organized body of people bonded by territory, culture, or ethnicity, having sovereignty (to a certain extent) granted by other states (enclosing or neighboring states). This includes countries (nations), provinces (e.g., one of the United States of America or a French

departement), counties or municipalities. Refine using, e.g., ISO country codes, FIPS-PUB state codes, etc.
4 | NAT | Nation | A politically organized body of people bonded by territory and known as a nation.
2 | PLC | place | A physical place or site with its containing structure. May be natural or man-made. The geographic position of a place may or may not be constant.
3 | CITY | city or town | The territory of a city, town or other municipality.
3 | COUNTRY | country | The territory of a sovereign nation.
3 | COUNTY | county or parish | The territory of a county, parish or other division of a state or province.
3 | PROVINCE | state or province | The territory of a state, province, department or other division of a sovereign country.
2 | RGRP | group | A grouping of resources (personnel, material, or places) to be used for scheduling purposes. May be a pool of like-type resources, a team, or combination of personnel, material and places.

4.3.2.42 HL7 v3 Code System EntityHandling

URL: https://hl7.org/fhir/STU3/v3/EntityHandling/cs.html

This page is part of the FHIR Specification (v3.0.2: STU 3). The current version which supercedes this version is 4.0.1. For a full list of available versions, see the Directory of published versions

Vocabulary Work Group | Maturity Level: N/A | External | Use Context: Any

This code system (http://hl7.org/fhir/v3/EntityHandling) is defined as part of HL7 v3.

Summary

Defining URL: | http://hl7.org/fhir/v3/EntityHandling
Name: | v3 Code System EntityHandling
Definition: | **** MISSING DEFINITIONS ****
OID: | 2.16.840.1.113883.5.42 (for OID based terminology systems)
Source Resource | XML / JSON

This Code system is used in the following value sets:

* v3 Code System EntityHandling (**** MISSING DEFINITIONS ****)

4.3.2.42.1 Code System Content

Release Date: 2016-11-11

Level | Code | Display | Definition
1 | AMB | Ambient Temperature | Keep at ambient temperature, 22 +/- 2C
1 | C37 | Body Temperature | Critical to keep at body temperature 36-38C
1 | CAMB | Critical Ambient temperature | Critical ambient - must not be refrigerated or frozen.
1 | CATM | Protect from Air | Critical. Do not expose to atmosphere. Do not uncap.
1 | CFRZ | Critical frozen | Critical frozen. Specimen must not be allowed to thaw until immediately prior to testing.
1 | CREF | Critical refrigerated temperature | Critical refrigerated - must not be allowed to freeze or warm until imediately prior to testing.
1 | DFRZ | Deep Frozen | Deep Frozen -16 to -20C.
1 | DRY | dry | Keep in a dry environment
1 | FRZ | frozen | Keep frozen below 0 ?C
1 | MTLF | Metal Free | Container is free of heavy metals, including lead.
1 | NTR | nitrogen | Keep in liquid nitrogen
1 | PRTL | Protect from Light | Protect from light (eg. Wrap in aluminum foil).
1 | PSA | do not shake | Do not shake
1 | PSO | no shock | Protect against shock
1 | REF | Refrigerated temperature | Keep at refrigerated temperature:4-8C Accidental warming or freezing is of little consequence.
1 | SBU | Shake before use | Shake thoroughly before using
1 | UFRZ | Ultra frozen | Ultra cold frozen -75 to -85C. Ultra cold freezer is typically at temperature of dry ice.
1 | UPR | upright | Keep upright, do not turn upside down

4.3.2.43 HL7 v3 Code System EntityNamePartQualifier

URL: https://hl7.org/fhir/STU3/v3/EntityNamePartQualifier/cs.html

This page is part of the FHIR Specification (v3.0.2: STU 3). The current version which supercedes this version is 4.0.1. For a full list of available versions, see the Directory of published versions

Vocabulary Work Group | Maturity Level: N/A | External | Use Context: Any

This code system (http://hl7.org/fhir/v3/EntityNamePartQualifier) is defined as part of HL7 v3. Related FHIR content: EntityNamePartQualifier.

Summary

Defining URL: | http://hl7.org/fhir/v3/EntityNamePartQualifier
Name: | v3 Code System EntityNamePartQualifier
Definition: | OpenIssue: Needs description
OID: | 2.16.840.1.113883.5.43 (for OID based terminology systems)
Source Resource | XML / JSON

This Code system is used in the following value sets:

* EntityNamePartQualifier (A set of codes each of which specifies a certain subcategory of the name part in addition to the main name part type)

* v3 Code System EntityNamePartQualifier (OpenIssue: Needs description)

4.3.2.43.1 Code System Content

Release Date: 2016-11-11

Level | Code | Display | Definition

1 | (_OrganizationNamePartQualifier) Abstract

2 | AC | academic | Indicates that a prefix like "Dr." or a suffix like "M.D." or "Ph.D." is an academic title.

2 | AD | adopted | The name the person was given at the time of adoption.

2 | BR | birth | A name that a person had shortly after being born. Usually for family names but may be used to mark given names at birth that may have changed later.

2 | CL | callme | A callme name is (usually a given name) that is preferred when a person is directly addressed.

2 | IN | initial | Indicates that a name part is just an initial. Initials do not imply a trailing period since this would not work with non-Latin scripts. Initials may consist of more than one letter, e.g., "Ph." could stand for "Philippe" or "Th." for "Thomas".

2 | LS | Legal status | For organizations a suffix indicating the legal status, e.g., "Inc.", "Co.", "AG", "GmbH", "B.V." "S.A.", "Ltd." etc.

2 | NB | nobility | In Europe and Asia, there are still people with nobility titles (aristocrats). German "von" is generally a nobility title, not a mere voorvoegsel. Others are "Earl of" or "His Majesty King of..." etc. Rarely used nowadays, but some systems do keep track of this.

2 | PR | professional | Primarily in the British Imperial culture people tend to have an abbreviation of their professional organization as part of their credential suffices.

2 | SP | spouse | The name assumed from the partner in a marital relationship (hence the "SP"). Usually the spouse's family name. Note that no inference about gender can be made from the existence of spouse names.

2 | TITLE | title | Indicates that a prefix or a suffix is a title that applies to the whole name, not just the adjacent name part.

2 | VV | voorvoegsel | A Dutch "voorvoegsel" is something like "van" or "de" that might have indicated nobility in the past but no longer so. Similar prefixes exist in other languages such as Spanish, French or Portugese.

1 | (PharmaceuticalEntityNamePartQualifiers) Abstract | | Description: Medication Name Parts are a means of specifying a range of acceptable "official" forms of the name of a product. They are used as patterns against which input name strings may be matched for automatic identification of products from input text reports. While they cover the concepts held under "doseForm" or "route" or "strength" the name parts are not the same and do not fit into a controlled vocabulary in the same way. By specifying up to 8 name parts a much larger range of possible names can be generated.

2 | CON | container name | Description: This refers to the container if present in the medicinal product name. EXAMPLES: For Optaflu suspension for injection in pre-filled syringe Influenza vaccine (surface antigen, inactivated, prepared in cell culture) (2007/2008 season): pre-filled syringe

2 | DEV | device name | Description: This refers to the qualifiers in the name for devices and is at the moment mainly applicable to insulins and inhalation products. EXAMPLES: For the medicinal product Actrapid FlexPen 100 IU/ml Solution for injection Subcutaneous use: FlexPen.

2 | FLAV | FlavorName | Description: This refers to a flavor of the medicinal product if present in the medicinal product name. Examples: For 'CoughCure Linctus Orange Flavor', the flavor part is "Orange" For 'Wonderdrug Syrup Cherry Flavor', the flavor part is "Cherry"

2 | FORMUL | FormulationPartName | Description: This refers to the formulation of the medicinal product if present in the medicinal product name. Examples: For 'SpecialMed Sugar Free Cough Syrup', the formulation name part is "Sugar Free" For 'QuickCure Gluten-free Bulk Fibre', the formulation name part is "gluten-free"

2 | FRM | form name | Description: This refers to the pharmaceutical form/ if present in the medicinal product name. EXAMPLES: For Agenerase 50 mg soft capsules: Soft Capsules For Ludiomil 25mg-Filmtabletten: Filmtabletten For Optaflu suspension for injection in pre-filled syringe Influenza vaccine (surface antigen, inactivated, prepared in cell culture) (2007/2008 season): suspension for injection

2 | INV | invented name | Description: This refers to the product name without the trademark or the name of the marketing authorization holder or any other descriptor reflected in the product name and, if appropriate, whether it is intended e.g. for babies, children or adults. EXAMPLES: Agenerase Optaflu Ludiomil

2 | POPUL | TargetPopulationName | Description: This refers to the target population for the medicinal product if present in the medicinal product name Examples: For 'Broncho-Drug 3.5 mg-capsules for children', the target population part is "children" For 'Adult Chesty Cough Syrup', the target population part is "adult"

2 | SCI | scientific name | Description: This refers to the product common or scientific name without the trademark or the name of the marketing authorization holder or any other descriptor reflected in the product name. EXAMPLES: For Agenerase: N/A For Optaflu: Influenza vaccine (surface antigen, inactivated, prepared in cell culture) (2007/2008 season) For Ludiomil: N/A

2 | STR | strength name | Description: This refers to the strength if present in the medicinal product name. The use of decimal points should be accommodated if required. EXAMPLES: For Agenerase 50 mg soft capsules: 50mg For Ludiomil 25mg-Filmtabletten: 25 mg For Optaflu suspension for injection in pre-filled syringe Influenza vaccine (surface antigen, inactivated, prepared in cell culture) (2007/2008 season): N/A

2 | TIME | TimeOrPeriodName | Description: This refers to a time or time period that may be specified in the text of the medicinal product name Example: For an influenza vaccine 'Drug-FLU season 2008/2009', the time/period part is "2008/2009 season"

2 | TMK | trademark name | Description: This refers to trademark/company element if present in the medicinal product name. EXAMPLES: for Insulin Human Winthrop Comb 15: Winthrop

2 | USE | intended use name | Description: This refers to the intended use if present in the medicinal product name without the trademark or the name of the marketing authorization holder or any other descriptor reflected in the product name. Examples: For 'Drug-BI Caplets - Heartburn Relief', the intended use part is: "Heartburn Relief" For 'Medicine Honey Syrup for Soothing Coughs' the intended use part is "Soothing Coughs"

1 | (_PersonNamePartQualifier) Abstract

2 | IN

2 | TITLE

2 | (_PersonNamePartAffixTypes) Abstract

3 | AC

3 | NB

3 | PR

3 | VV

2 | (_PersonNamePartChangeQualifier) Abstract

3 | AD

3 | BR

3 | SP

2 | (_PersonNamePartMiscQualifier) Abstract

3 | CL

4.3.2.44 HL7 v3 Code System EntityNamePartType

URL: https://hl7.org/fhir/STU3/v3/EntityNamePartType/cs.html

This page is part of the FHIR Specification (v3.0.2: STU 3). The current version which supercedes this version is 4.0.1. For a full list of available versions, see the Directory of published versions

Vocabulary Work Group | Maturity Level: N/A | External | Use Context: Any

This code system (http://hl7.org/fhir/v3/EntityNamePartType) is defined as part of HL7 v3.

Summary

Defining URL: | http://hl7.org/fhir/v3/EntityNamePartType
Name: | v3 Code System EntityNamePartType
Definition: | **** MISSING DEFINITIONS ****
OID: | 2.16.840.1.113883.5.44 (for OID based terminology systems)
Source Resource | XML / JSON

This Code system is used in the following value sets:

* v3 Code System EntityNamePartType (**** MISSING DEFINITIONS ****)

4.3.2.44.1 Code System Content

Release Date: 2016-11-11

Level | Code | Display | Definition
1 | DEL | delimiter | A delimiter has no meaning other than being literally printed in this name representation. A delimiter has no implicit leading and trailing white space.
1 | FAM | family | Family name, this is the name that links to the genealogy. In some cultures (e.g. Eritrea) the family name of a son is the first name of his father.
1 | GIV | given | Given name (don't call it "first name" since this given names do not always come first)
1 | PFX | prefix | A prefix has a strong association to the immediately following name part. A prefix has no implicit trailing white space (it has implicit leading white space though). Note that prefixes can be inverted.
1 | SFX | suffix | Description:A suffix has a strong association to the immediately preceding name part. A suffix has no implicit leading white space (it has implicit trailing white space though). Suffices cannot be inverted.

4.3.2.45 HL7 v3 Code System EntityNameUse

URL: https://hl7.org/fhir/STU3/v3/EntityNameUse/cs.html

This page is part of the FHIR Specification (v3.0.2: STU 3). The current version which supercedes this version is 4.0.1. For a full list of available versions, see the Directory of published versions

Vocabulary Work Group | Maturity Level: N/A | External | Use Context: Any

This code system (http://hl7.org/fhir/v3/EntityNameUse) is defined as part of HL7 v3.

Summary

Defining URL: | http://hl7.org/fhir/v3/EntityNameUse
Name: | v3 Code System EntityNameUse
Definition: | **** MISSING DEFINITIONS ****
OID: | 2.16.840.1.113883.5.45 (for OID based terminology systems)
Source Resource | XML / JSON

This Code system is used in the following value sets:

* NameRepresentationUse (A set of codes for each different representation of a name)

* v3 Code System EntityNameUse (**** MISSING DEFINITIONS ****)

4.3.2.45.1 Code System Content

Release Date: 2016-11-11

Level | Code | Display | Definition
1 | (_NameRepresentationUse) Abstract | | Identifies the different representations of a name. The representation may affect how the name is used. (E.g. use of Ideographic for formal communications.)
2 | ABC | Alphabetic | Alphabetic transcription of name (Japanese: romaji)
2 | IDE | Ideographic | Ideographic representation of name (e.g., Japanese kanji, Chinese characters)
2 | SYL | Syllabic | Syllabic transcription of name (e.g., Japanese kana, Korean hangul)
1 | ASGN | assigned | A name assigned to a person. Reasons some organizations assign alternate names may include not knowing the person's name, or to maintain anonymity. Some, but not necessarily all, of the name types that people call "alias" may fit into this category.
1 | C | License | As recorded on a license, record, certificate, etc. (only if different from legal name)
1 | I | Indigenous/Tribal | e.g. Chief Red Cloud
1 | L | Legal | Known as/conventional/the one you use
2 | OR | official registry | Definition:The formal name as registered in an official (government) registry, but which name might not be commonly used. Particularly used in countries with a law system based on Napoleonic law.
1 | P | pseudonym | A self asserted name that the person is using or has used.
2 | A | Artist/Stage | Includes writer's pseudonym, stage name, etc
1 | R | Religious | e.g. Sister Mary Francis, Brother John
1 | SRCH | search | A name intended for use in searching or matching.

2 | PHON | phonetic | A name spelled phonetically. There are a variety of phonetic spelling algorithms. This code value does not distinguish between these.Discussion:
2 | SNDX | Soundex | A name spelled according to the SoundEx algorithm.

4.3.2.46 HL7 v3 Code System EntityRisk

URL: https://hl7.org/fhir/STU3/v3/EntityRisk/cs.html

This page is part of the FHIR Specification (v3.0.2: STU 3). The current version which supercedes this version is 4.0.1. For a full list of available versions, see the Directory of published versions

Vocabulary Work Group | Maturity Level: N/A | External | Use Context: Any

This code system (http://hl7.org/fhir/v3/EntityRisk) is defined as part of HL7 v3.

Summary

Defining URL: | http://hl7.org/fhir/v3/EntityRisk
Name: | v3 Code System EntityRisk
Definition: | Kinds of risks associated with the handling of the material..
OID: | 2.16.840.1.113883.5.46 (for OID based terminology systems)
Source Resource | XML / JSON

This Code system is used in the following value sets:

* v3 Code System EntityRisk (Kinds of risks associated with the handling of the material..)

4.3.2.46.1 Code System Content

Release Date: 2016-11-11

Level | Code | Display | Definition
1 | AGG | aggressive | A danger that can be associated with certain living subjects, including humans.
1 | BIO | Biological | The dangers associated with normal biological materials. I.e. potential risk of unknown infections. Routine biological materials from living subjects.
1 | COR | Corrosive | Material is corrosive and may cause severe injury to skin, mucous membranes and eyes. Avoid any unprotected contact.
1 | ESC | Escape Risk | The entity is at risk for escaping from containment or control.
1 | IFL | inflammable | Material is highly inflammable and in certain mixtures (with air) may lead to explosions. Keep away from fire, sparks and excessive heat.
2 | EXP | explosive | Material is an explosive mixture. Keep away from fire, sparks, and heat.
1 | INF | infectious | Material known to be infectious with human pathogenic microorganisms. Those who handle this material must take precautions for their protection.
2 | BHZ | biohazard | Material contains microorganisms that is an environmental hazard. Must be handled with special care.
1 | INJ | injury hazard | Material is solid and sharp (e.g., cannulas). Dispose in hard container.
1 | POI | poison | Material is poisonous to humans and/or animals. Special care must be taken to avoid incorporation, even of small amounts.
1 | RAD | radioactive | Material is a source for ionizing radiation and must be handled with special care to avoid injury of those who handle it and to avoid environmental hazards.

4.3.2.49 HL7 v3 Code System EquipmentAlertLevel

URL: https://hl7.org/fhir/STU3/v3/EquipmentAlertLevel/cs.html

This page is part of the FHIR Specification (v3.0.2: STU 3). The current version which supercedes this version is 4.0.1. For a full list of available versions, see the Directory of published versions

Vocabulary Work Group | Maturity Level: N/A | External | Use Context: Any

This code system (http://hl7.org/fhir/v3/EquipmentAlertLevel) is defined as part of HL7 v3.

Summary

Defining URL: | http://hl7.org/fhir/v3/EquipmentAlertLevel
Name: | v3 Code System EquipmentAlertLevel
Definition: | **** MISSING DEFINITIONS ****
OID: | 2.16.840.1.113883.5.49 (for OID based terminology systems)
Source Resource | XML / JSON

This Code system is used in the following value sets:

* v3 Code System EquipmentAlertLevel (**** MISSING DEFINITIONS ****)

4.3.2.49.1 Code System Content

Release Date: 2016-11-11

Level | Code | Display | Definition
1 | C | Critical | Shut Down, Fix Problem and Re-init
1 | N | Normal | No Corrective Action Needed
1 | S | Serious | Corrective Action Required
1 | W | Warning | Corrective Action Anticipated

4.3.2.50 HL7 v3 Code System Ethnicity

URL: https://hl7.org/fhir/STU3/v3/Ethnicity/cs.html

This page is part of the FHIR Specification (v3.0.2: STU 3). The current version which supercedes this version is 4.0.1. For a full list of available versions, see the Directory of published versions

Vocabulary Work Group | Maturity Level: N/A | External | Use Context: Any

This code system (http://hl7.org/fhir/v3/Ethnicity) is defined as part of HL7 v3.

Summary

Defining URL: | http://hl7.org/fhir/v3/Ethnicity

Name: | v3 Code System Ethnicity

Definition: | In the United States, federal standards for classifying data on ethnicity determine the categories used by federal agencies and exert a strong influence on categorization by state and local agencies and private sector organizations. The federal standards do not conceptually define ethnicity, and they recognize the absence of an anthropological or scientific basis for ethnicity classification. Instead, the federal standards acknowledge that ethnicity is a social-political construct in which an individual's own identification with a particular ethnicity is preferred to observer identification. The standards specify two minimum ethnicity categories: Hispanic or Latino, and Not Hispanic or Latino. The standards define a Hispanic or Latino as a person of "Mexican, Puerto Rican, Cuban, South or Central America, or other Spanish culture or origin, regardless of race." The standards stipulate that ethnicity data need not be limited to the two minimum categories, but any expansion must be collapsible to those categories. In addition, the standards stipulate that an individual can be Hispanic or Latino or can be Not Hispanic or Latino, but cannot be both.

OID: | 2.16.840.1.113883.5.50 (for OID based terminology systems)

Source Resource | XML / JSON

This Code system is used in the following value sets:

* v3 Code System Ethnicity (In the United States, federal standards for classifying data on ethnicity determine the categories used by federal agencies and exert a strong influence on categorization by state and local agencies and private sector organizations. The federal standards do not conceptually define ethnicity, and they recognize the absence of an anthropological or scientific basis for ethnicity classification. Instead, the federal standards acknowledge that ethnicity is a social-political construct in which an individual's own identification with a particular ethnicity is preferred to observer identification. The standards specify two minimum ethnicity categories: Hispanic or Latino, and Not Hispanic or Latino. The standards define a Hispanic or Latino as a person of "Mexican, Puerto Rican, Cuban, South or Central America, or other Spanish culture or origin, regardless of race." The standards stipulate that ethnicity data need not be limited to the two minimum categories, but any expansion must be collapsible to those categories. In addition, the standards stipulate that an individual can be Hispanic or Latino or can be Not Hispanic or Latino, but cannot be both.)

4.3.2.50.1 Code System Content

Release Date: 2016-11-11

Level	Code	Display	Definition
1	2135-2	Hispanic or Latino	
2	2137-8	Spaniard	
3	2138-6	Andalusian	
3	2139-4	Asturian	
3	2140-2	Castillian	
3	2141-0	Catalonian	
3	2142-8	Belearic Islander	
3	2143-6	Gallego	
3	2144-4	Valencian	
3	2145-1	Canarian	
3	2146-9	Spanish Basque	
2	2148-5	Mexican	
3	2149-3	Mexican American	
3	2150-1	Mexicano	
3	2151-9	Chicano	
3	2152-7	La Raza	
3	2153-5	Mexican American Indian	
2	2155-0	Central American	
3	2156-8	Costa Rican	
3	2157-6	Guatemalan	
3	2158-4	Honduran	
3	2159-2	Nicaraguan	
3	2160-0	Panamanian	
3	2161-8	Salvadoran	
3	2162-6	Central American Indian	
3	2163-4	Canal Zone	
2	2165-9	South American	
3	2166-7	Argentinean	
3	2167-5	Bolivian	
3	2168-3	Chilean	
3	2169-1	Colombian	
3	2170-9	Ecuadorian	
3	2171-7	Paraguayan	
3	2172-5	Peruvian	
3	2173-3	Uruguayan	
3	2174-1	Venezuelan	

3 | 2175-8 | South American Indian
3 | 2176-6 | Criollo
2 | 2178-2 | Latin American
2 | 2180-8 | Puerto Rican
2 | 2182-4 | Cuban
2 | 2184-0 | Dominican
1 | 2186-5 | Not Hispanic or Latino | Note that this term remains in the table for completeness, even though within HL7, the notion of "not otherwise coded" term is deprecated.

4.3.2.51 HL7 v3 Code System GenderStatus

URL: https://hl7.org/fhir/STU3/v3/GenderStatus/cs.html

This page is part of the FHIR Specification (v3.0.2: STU 3). The current version which supercedes this version is 4.0.1. For a full list of available versions, see the Directory of published versions

Vocabulary Work Group | Maturity Level: N/A | External | Use Context: Any

This code system (http://hl7.org/fhir/v3/GenderStatus) is defined as part of HL7 v3. Related FHIR content: GenderStatus.

Summary

Defining URL: | http://hl7.org/fhir/v3/GenderStatus
Name: | v3 Code System GenderStatus
Definition: | **** MISSING DEFINITIONS ****
OID: | 2.16.840.1.113883.5.51 (for OID based terminology systems)
Source Resource | XML / JSON

This Code system is used in the following value sets:

* v3 Code System GenderStatus (**** MISSING DEFINITIONS ****)

4.3.2.51.1 Code System Content

Release Date: 2016-11-11

Level | Code | Display | Definition
1 | I | Intact | Reproductively intact
1 | N | Neutered | Reproductively neutered

4.3.2.57 HL7 v3 Code System HL7UpdateMode

URL: https://hl7.org/fhir/STU3/v3/HL7UpdateMode/cs.html

This page is part of the FHIR Specification (v3.0.2: STU 3). The current version which supercedes this version is 4.0.1. For a full list of available versions, see the Directory of published versions

Vocabulary Work Group | Maturity Level: N/A | External | Use Context: Any

This code system (http://hl7.org/fhir/v3/HL7UpdateMode) is defined as part of HL7 v3.

Summary

Defining URL: | http://hl7.org/fhir/v3/HL7UpdateMode
Name: | v3 Code System HL7UpdateMode
Definition: | The possible modes of updating that occur when an attribute is received by a system that already contains values for that attribute.
OID: | 2.16.840.1.113883.5.57 (for OID based terminology systems)
Source Resource | XML / JSON

This Code system is used in the following value sets:

* v3 Code System HL7UpdateMode (The possible modes of updating that occur when an attribute is received by a system that already contains values for that attribute.)

4.3.2.57.1 Code System Content

Release Date: 2016-11-11

Level | Code | Display | Definition
1 | A | Add | Description:The item was (or is to be) added, having not been present immediately before. (If it is already present, this may be treated as an error condition.)
1 | AR | Add or Replace | Description:The item was (or is to be) either added or replaced.
1 | D | Remove | Description:The item was (or is to be) removed (sometimes referred to as deleted). If the item is part of a collection, delete any matching items.
1 | K | Key | Description:This item is part of the identifying information for this object.
1 | N | No Change | Description:There was (or is to be) no change to the item. This is primarily used when this element has not changed, but other attributes in the instance have changed.
1 | R | Replace | Description:The item existed previously and has (or is to be) revised. (If an item does not already exist, this may be treated as an error condition.)
1 | REF | Reference | Description:This item provides enough information to allow a processing system to locate the full applicable record by identifying the object.
1 | U | Unknown | Description:Description:It is not specified whether or what kind of change has occurred to the item, or whether the item is present as a reference or identifying property.
1 | (_SetUpdateMode) Abstract | | These concepts apply when the element and/or message is updating a set of items.

2 | ESA | Set Add | Add the message element to the collection of items on the receiving system that correspond to the message element.

2 | ESAC | Set Add or Change | Change the item on the receiving system that corresponds to this message element; if a matching element does not exist, add a new one created with the values in the message.

2 | ESC | Set Change | Change the item on the receiving system that corresponds to this message element; do not process if a matching element does not exist.

2 | ESD | Set Delete | Delete the item on the receiving system that corresponds to this message element.

1 | AU | Add or Update | Description: AU: If this item exists, update it with these values. If it does not exist, create it with these values. If the item is part of the collection, update each item that matches this item, and if no items match, add a new item to the collection.

1 | I | Ignore | Ignore this role, it is not relevant to the update.

1 | V | Verify | Verify - this message element must match a value already in the receiving systems database in order to process the message.

4.3.2.58 HL7 v3 Code System HtmlLinkType

URL: https://hl7.org/fhir/STU3/v3/HtmlLinkType/cs.html

This page is part of the FHIR Specification (v3.0.2: STU 3). The current version which supercedes this version is 4.0.1. For a full list of available versions, see the Directory of published versions

Vocabulary Work Group | Maturity Level: N/A | External | Use Context: Any

This code system (http://hl7.org/fhir/v3/HtmlLinkType) is defined as part of HL7 v3.

Summary

Defining URL: | http://hl7.org/fhir/v3/HtmlLinkType

Name: | v3 Code System HtmlLinkType

Definition: | HtmlLinkType values are drawn from HTML 4.0 and describe the relationship between the current document and the anchor that is the target of the link

OID: | 2.16.840.1.113883.5.58 (for OID based terminology systems)

Source Resource | XML / JSON

This Code system is used in the following value sets:

* v3 Code System HtmlLinkType (HtmlLinkType values are drawn from HTML 4.0 and describe the relationship between the current document and the anchor that is the target of the link)

4.3.2.58.1 Code System Content

Release Date: 2016-11-11

Level | Code | Display | Definition

1 | alternate | alternate | Designates substitute versions for the document in which the link occurs. When used together with the lang attribute, it implies a translated version of the document. When used together with the media attribute, it implies a version designed for a different medium (or media).

1 | appendix | appendix | Refers to a document serving as an appendix in a collection of documents.

1 | bookmark | bookmark | Refers to a bookmark. A bookmark is a link to a key entry point within an extended document. The title attribute may be used, for example, to label the bookmark. Note that several bookmarks may be defined in each document.

1 | chapter | chapter | Refers to a document serving as a chapter in a collection of documents.

1 | contents | contents | Refers to a document serving as a table of contents. Some user agents also support the synonym ToC (from "Table of Contents").

1 | copyright | copyright | Refers to a copyright statement for the current document.

1 | glossary | glossary | Refers to a document providing a glossary of terms that pertain to the current document.

1 | help | help | Refers to a document offering help (more information, links to other sources of information, etc.).

1 | index | index | Refers to a document providing an index for the current document.

1 | next | next | Refers to the next document in a linear sequence of documents. User agents may choose to preload the "next" document, to reduce the perceived load time.

1 | prev | prev | Refers to the previous document in an ordered series of documents. Some user agents also support the synonym "Previous".

1 | section | section | Refers to a document serving as a section in a collection of documents.

1 | start | start | Refers to the first document in a collection of documents. This link type tells search engines which document is considered by the author to be the starting point of the collection.

1 | stylesheet | stylesheet | Refers to an external style sheet. See the section on external style sheets for details. This is used together with the link type "Alternate" for user-selectable alternate style sheets.

1 | subsection | subsection | Refers to a document serving as a subsection in a collection of documents.

4.3.2.60 HL7 v3 Code System LanguageAbilityMode

URL: https://hl7.org/fhir/STU3/v3/LanguageAbilityMode/cs.html

This page is part of the FHIR Specification (v3.0.2: STU 3). The current version which supercedes this version is 4.0.1. For a full list of available versions, see the Directory of published versions

Vocabulary Work Group | Maturity Level: N/A | External | Use Context: Any

This code system (http://hl7.org/fhir/v3/LanguageAbilityMode) is defined as part of HL7 v3.

Summary

Defining URL: | http://hl7.org/fhir/v3/LanguageAbilityMode

Name: | v3 Code System LanguageAbilityMode

Definition: | A value representing the method of expression of the language. Example: Expressed spoken, expressed written, expressed signed, received spoken, received written, received signed. OpenIssue: Description copied from Concept Domain of same name. Must be verified.

OID: | 2.16.840.1.113883.5.60 (for OID based terminology systems)

Source Resource | XML / JSON

This Code system is used in the following value sets:

* v3 Code System LanguageAbilityMode (A value representing the method of expression of the language. Example: Expressed spoken, expressed written, expressed signed, received spoken, received written, received signed. OpenIssue: Description copied from Concept Domain of same name. Must be verified.)

4.3.2.60.1 Code System Content

Release Date: 2016-11-11

Level	Code	Display	Definition
1	ESGN	Expressed signed	
1	ESP	Expressed spoken	
1	EWR	Expressed written	
1	RSGN	Received signed	
1	RSP	Received spoken	
1	RWR	Received written	

4.3.2.61 HL7 v3 Code System LanguageAbilityProficiency

URL: https://hl7.org/fhir/STU3/v3/LanguageAbilityProficiency/cs.html

This page is part of the FHIR Specification (v3.0.2: STU 3). The current version which supercedes this version is 4.0.1. For a full list of available versions, see the Directory of published versions

Vocabulary Work Group | Maturity Level: N/A | External | Use Context: Any

This code system (http://hl7.org/fhir/v3/LanguageAbilityProficiency) is defined as part of HL7 v3.

Summary

Defining URL: | http://hl7.org/fhir/v3/LanguageAbilityProficiency
Name: | v3 Code System LanguageAbilityProficiency
Definition: | A value representing the level of proficiency in a language. Example: Excellent, good, fair, poor. OpenIssue: Description copied from Concept Domain of same name. Must be verified.
OID: | 2.16.840.1.113883.5.61 (for OID based terminology systems)
Source Resource | XML / JSON

This Code system is used in the following value sets:

* v3 Code System LanguageAbilityProficiency (A value representing the level of proficiency in a language. Example: Excellent, good, fair, poor. OpenIssue: Description copied from Concept Domain of same name. Must be verified.)

4.3.2.61.1 Code System Content

Release Date: 2016-11-11

Level	Code	Display	Definition
1	E	Excellent	
1	F	Fair	
1	G	Good	
1	P	Poor	

4.3.2.63 HL7 v3 Code System LivingArrangement

URL: https://hl7.org/fhir/STU3/v3/LivingArrangement/cs.html

This page is part of the FHIR Specification (v3.0.2: STU 3). The current version which supercedes this version is 4.0.1. For a full list of available versions, see the Directory of published versions

Vocabulary Work Group | Maturity Level: N/A | External | Use Context: Any

This code system (http://hl7.org/fhir/v3/LivingArrangement) is defined as part of HL7 v3.

Summary

Defining URL: | http://hl7.org/fhir/v3/LivingArrangement
Name: | v3 Code System LivingArrangement
Definition: | A code depicting the living arrangements of a person
OID: | 2.16.840.1.113883.5.63 (for OID based terminology systems)
Source Resource | XML / JSON

This Code system is used in the following value sets:

* v3 Code System LivingArrangement (A code depicting the living arrangements of a person)

4.3.2.63.1 Code System Content

Release Date: 2016-11-11

Level	Code	Display	Definition
1	HL	homeless	Definition: Living arrangements lacking a permanent residence.
2	M	Nomadic	Nomadic

2 | T | Transient | Transient
1 | I | Institution | Institution
2 | CS | community shelter | Definition: A group living arrangement specifically for the care of those in need of temporary and crisis housing assistance. Examples include domestic violence shelters, shelters for displaced or homeless individuals, Salvation Army, Jesus House, etc. Community based services may be provided.
2 | G | Group Home | Group Home
2 | N | Nursing Home | Nursing Home
2 | X | Extended care facility | Extended care facility
1 | PR | private residence | Definition: A living arrangement within a private residence for single family.
2 | H | Independent Household | Independent Household
2 | R | Retirement Community | Retirement Community
2 | SL | supported living | Definition: Assisted living in a single family residence for persons with physical, behavioral, or functional health, or socio-economic challenges. There may or may not be on-site supervision but the housing is designed to assist the client with developing independent living skills. Community based services may be provided.

4.3.2.65 HL7 v3 Code System LocalMarkupIgnore

URL: https://hl7.org/fhir/STU3/v3/LocalMarkupIgnore/cs.html

This page is part of the FHIR Specification (v3.0.2: STU 3). The current version which supercedes this version is 4.0.1. For a full list of available versions, see the Directory of published versions

Vocabulary Work Group | Maturity Level: N/A | External | Use Context: Any

This code system (http://hl7.org/fhir/v3/LocalMarkupIgnore) is defined as part of HL7 v3.

Summary

Defining URL: | http://hl7.org/fhir/v3/LocalMarkupIgnore
Name: | v3 Code System LocalMarkupIgnore
Definition: | Tells a receiver to ignore just the local markup tags (local_markup, local_header, local_attr) when value="markup", or to ignore the local markup tags and all contained content when value="all"
OID: | 2.16.840.1.113883.5.65 (for OID based terminology systems)
Source Resource | XML / JSON

This Code system is used in the following value sets:

* v3 Code System LocalMarkupIgnore (Tells a receiver to ignore just the local markup tags (local_markup, local_header, local_attr) when value="markup", or to ignore the local markup tags and all contained content when value="all")

4.3.2.65.1 Code System Content

Release Date: 2016-11-11

Level | Code | Display | Definition
1 | all | all
1 | markup | markup

4.3.2.66 HL7 v3 Code System LocalRemoteControlState

URL: https://hl7.org/fhir/STU3/v3/LocalRemoteControlState/cs.html

This page is part of the FHIR Specification (v3.0.2: STU 3). The current version which supercedes this version is 4.0.1. For a full list of available versions, see the Directory of published versions

Vocabulary Work Group | Maturity Level: N/A | External | Use Context: Any

This code system (http://hl7.org/fhir/v3/LocalRemoteControlState) is defined as part of HL7 v3.

Summary

Defining URL: | http://hl7.org/fhir/v3/LocalRemoteControlState
Name: | v3 Code System LocalRemoteControlState
Definition: | **** MISSING DEFINITIONS ****
OID: | 2.16.840.1.113883.5.66 (for OID based terminology systems)
Source Resource | XML / JSON

This Code system is used in the following value sets:

* v3 Code System LocalRemoteControlState (**** MISSING DEFINITIONS ****)

4.3.2.66.1 Code System Content

Release Date: 2016-11-11

Level | Code | Display | Definition
1 | L | Local | An equipment can either work autonomously ('Local' control state).
1 | R | Remote | An equipment can be controlled by another system, e.g., LAS computer ('Remote' control state).

4.3.2.67 HL7 v3 Code System MapRelationship

URL: https://hl7.org/fhir/STU3/v3/MapRelationship/cs.html

This page is part of the FHIR Specification (v3.0.2: STU 3). The current version which supercedes this version is 4.0.1. For a full list of available versions, see the Directory of published versions

Vocabulary Work Group | Maturity Level: N/A | External | Use Context: Any

This code system (http://hl7.org/fhir/v3/MapRelationship) is defined as part of HL7 v3.

Summary

Defining URL: | http://hl7.org/fhir/v3/MapRelationship
Name: | v3 Code System MapRelationship
Definition: | The closeness or quality of the mapping between the HL7 concept (as represented by the HL7 concept identifier) and the source coding system. The values are patterned after the similar relationships used in the UMLS Metathesaurus. Because the HL7 coding sy
OID: | 2.16.840.1.113883.5.67 (for OID based terminology systems)
Source Resource | XML / JSON

This Code system is used in the following value sets:

* v3 Code System MapRelationship (The closeness or quality of the mapping between the HL7 concept (as represented by the HL7 concept identifier) and the source coding system. The values are patterned after the similar relationships used in the UMLS Metathesaurus. Because the HL7 coding sy)

4.3.2.67.1 Code System Content

Release Date: 2016-11-11

Level | Code | Display | Definition
1 | BT | Broader Than | The first concept is at a more abstract level than the second concept. For example, Hepatitis is broader than Hepatitis A, and endocrine disease is broader than Diabetes Mellitus. Broader than is the opposite of the narrower than relationship.
1 | E | Exact | The two concepts have identical meaning.
1 | NT | Narrower Than | The first concept is at a more detailed level than the second concept. For example, Pennicillin G is narrower than Pennicillin, and vellus hair is narrower than hair. Narrower than is the opposite of broader than.

4.3.2.81 HL7 v3 Code System ModifyIndicator

URL: https://hl7.org/fhir/STU3/v3/ModifyIndicator/cs.html

This page is part of the FHIR Specification (v3.0.2: STU 3). The current version which supercedes this version is 4.0.1. For a full list of available versions, see the Directory of published versions

Vocabulary Work Group | Maturity Level: N/A | External | Use Context: Any

This code system (http://hl7.org/fhir/v3/ModifyIndicator) is defined as part of HL7 v3.

Summary

Defining URL: | http://hl7.org/fhir/v3/ModifyIndicator
Name: | v3 Code System ModifyIndicator
Definition: | **** MISSING DEFINITIONS ****
OID: | 2.16.840.1.113883.5.81 (for OID based terminology systems)
Source Resource | XML / JSON

This Code system is used in the following value sets:

* v3 Code System ModifyIndicator (**** MISSING DEFINITIONS ****)

4.3.2.81.1 Code System Content

Release Date: 2016-11-11

Level | Code | Display | Definition
1 | M | Modified subscription | Modified subscription to a query server.
1 | N | New subscription | New subscription to a query server.

4.3.2.83 HL7 v3 Code System ObservationInterpretation

URL: https://hl7.org/fhir/STU3/v3/ObservationInterpretation/cs.html

This page is part of the FHIR Specification (v3.0.2: STU 3). The current version which supercedes this version is 4.0.1. For a full list of available versions, see the Directory of published versions

Vocabulary Work Group | Maturity Level: N/A | External | Use Context: Any

This code system (http://hl7.org/fhir/v3/ObservationInterpretation) is defined as part of HL7 v3. Related FHIR content: Observation Interpretation Codes.

Summary

Defining URL: | http://hl7.org/fhir/v3/ObservationInterpretation
Name: | v3 Code System ObservationInterpretation
Definition: | One or more codes specifying a rough qualitative interpretation of the observation, such as "normal", "abnormal", "below normal", "change up", "resistant", "susceptible", etc. OpenIssue: Description copied from Concept Domain of same name. Must be verified. Note also that this might be identical to the V2 code system of interpretation codes (formerly Abnormal Flags in older versions).
OID: | 2.16.840.1.113883.5.83 (for OID based terminology systems)
Source Resource | XML / JSON

This Code system is used in the following value sets:

* v3 Code System ObservationInterpretation (One or more codes specifying a rough qualitative interpretation of the observation, such as "normal", "abnormal", "below normal", "change up", "resistant", "susceptible", etc. OpenIssue: Description copied from Concept Domain of same name. Must be verified. Note also that this might be identical to the V2 code system of interpretation codes (formerly Abnormal Flags in older versions).)

4.3.2.83.1 Code System Content

Release Date: 2016-11-11

Level | Code | Display | Definition

1 | (_GeneticObservationInterpretation) Abstract | | Codes that specify interpretation of genetic analysis, such as "positive", "negative", "carrier", "responsive", etc.

2 | CAR | Carrier | The patient is considered as carrier based on the testing results. A carrier is an individual who carries an altered form of a gene which can lead to having a child or offspring in future generations with a genetic disorder.

2 | Carrier Deprecated | Carrier | The patient is considered as carrier based on the testing results. A carrier is an individual who carries an altered form of a gene which can lead to having a child or offspring in future generations with a genetic disorder. Deprecation Comment: This code is currently the same string as the print name for this concept and is inconsistent with the conventions being used for the other codes in the coding system, as it is a full word with initial capitalization, rather than an all upper case mnemonic. The recommendation from OO is to deprecate the code "Carrier" and to add "CAR" as the new active code representation for this concept.

1 | (_ObservationInterpretationChange) Abstract | | Interpretations of change of quantity and/or severity. At most one of B or W and one of U or D allowed.

2 | B | Better | The current result or observation value has improved compared to the previous result or observation value (the change is significant as defined in the respective test procedure). [Note: This can be applied to quantitative or qualitative observations.]

2 | D | Significant change down | The current result has decreased from the previous result for a quantitative observation (the change is significant as defined in the respective test procedure).

2 | U | Significant change up | The current result has increased from the previous result for a quantitative observation (the change is significant as defined in the respective test procedure).

2 | W | Worse | The current result or observation value has degraded compared to the previous result or observation value (the change is significant as defined in the respective test procedure). [Note: This can be applied to quantitative or qualitative observations.]

1 | (_ObservationInterpretationExceptions) Abstract | | Technical exceptions resulting in the inability to provide an interpretation. At most one allowed. Does not imply normality or severity.

2 | < | Off scale low | The result is below the minimum detection limit (the test procedure or equipment is the limiting factor). Synonyms: Below analytical limit, low off scale.

2 | > | Off scale high | The result is above the maximum quantifiable limit (the test procedure or equipment is the limiting factor). Synonyms: Above analytical limit, high off scale.

2 | AC Deprecated | Anti-complementary substances present | A valid result cannot be obtained for the specified component / analyte due to the presence of anti-complementary substances in the sample. Deprecation Comment: This code is being deprecated to match the status in V2 Table 0078 "Interpretation Codes.

2 | IE | Insufficient evidence | There is insufficient evidence that the species in question is a good target for therapy with the drug. A categorical interpretation is not possible. [Note: A MIC with "IE" and/or a comment may be reported (without an accompanying S, I or R-categorization).]

2 | QCF Deprecated | Quality control failure | A result cannot be considered valid for the specified component / analyte or organism due to failure in the quality control testing component. Deprecation Comment: This code is being deprecated to match the status in V2 Table 0078 "Interpretation Codes.

2 | TOX Deprecated | Cytotoxic substance present | A valid result cannot be obtained for the specified organism or cell line due to the presence of cytotoxic substances in the sample or culture. Deprecation Comment: This code is being deprecated to match the status in V2 Table 0078 "Interpretation Codes.

1 | (_ObservationInterpretationNormality) Abstract | | Interpretation of normality or degree of abnormality (including critical or "alert" level). Concepts in this category are mutually exclusive, i.e., at most one is allowed.

2 | A | Abnormal | The result or observation value is outside the reference range or expected norm (as defined for the respective test procedure). [Note: Typically applies to non-numeric results.]

3 | AA | Critical abnormal | The result or observation value is outside a reference range or expected norm at a level at which immediate action should be considered for patient safety (as defined for the respective test procedure). [Note: Typically applies to non-numeric results. Analogous to critical/panic limits for numeric results.]

4 | HH | Critical high | The result for a quantitative observation is above a reference level at which immediate action should be considered for patient safety (as defined for the respective test procedure). Synonym: Above upper panic limits.

4 | LL | Critical low | The result for a quantitative observation is below a reference level at which immediate action should be considered for patient safety (as defined for the respective test procedure). Synonym: Below lower panic limits.

3 | H | High | The result for a quantitative observation is above the upper limit of the reference range (as defined for the respective test procedure). Synonym: Above high normal

4 | H> Deprecated | Significantly high | A test result that is significantly higher than the reference (normal) or therapeutic interval, but has not reached the critically high value and might need special attention, as defined by the laboratory or the clinician.[Note: This level is situated between 'H' and 'HH'.] Deprecation Comment: The code 'H>' is being deprecated in order to align with the use of the code 'HU' for "Very high" in V2 Table 0078 "Interpretation Codes". [Note: The use of code 'H>' is non-preferred, as this code is deprecated and on track to be retired; use code 'HU' instead.

5 | HH

4 | HU | Significantly high | A test result that is significantly higher than the reference (normal) or therapeutic interval, but has not reached the critically high value and might need special attention, as defined by the laboratory or the clinician.

5 | HH

3 | L | Low | The result for a quantitative observation is below the lower limit of the reference range (as defined for the respective test procedure). Synonym: Below low normal

4 | L< Deprecated | Significantly low | A test result that is significantly lower than the reference (normal) or therapeutic interval, but has not reached the critically low value and might need special attention, as defined by the laboratory or the clinician.[Note: This level is situated between 'L' and 'LL'.] Deprecation Comment: The code 'L<' is being deprecated in order to align with the use of the code 'LU' for "Very low" in V2 Table 0078 "Interpretation Codes". [Note: The use of code 'L<' is non-preferred, as this code is deprecated and on track to be retired; use code 'LU' instead.

5 | LL

4 | LU | Significantly low | A test result that is significantly lower than the reference (normal) or therapeutic interval, but has not reached the critically low value and might need special attention, as defined by the laboratory or the clinician.

5 | LL

2 | N | Normal | The result or observation value is within the reference range or expected norm (as defined for the respective test procedure). [Note: Applies to numeric or non-numeric results.]

1 | (_ObservationInterpretationSusceptibility) Abstract | | Interpretations of anti-microbial susceptibility testing results (microbiology). At most one allowed.

2 | IE

2 | I | Intermediate | Bacterial strain inhibited in vitro by a concentration of an antimicrobial agent that is associated with uncertain therapeutic effect. Reference: CLSI (http://www.clsi.org/Content/NavigationMenu/Resources/HarmonizedTerminologyDatabase/Harmonized_Terminolo.htm) Projects: ISO 20776-1, ISO 20776-2 [Note 1: Bacterial strains are categorized as intermediate by applying the appropriate breakpoints in a defined phenotypic test system.] [Note 2: This class of susceptibility implies that an infection due to the isolate can be appropriately treated in body sites where the drugs are physiologically concentrated or when a high dosage of drug can be used.] [Note 3: This class also indicates a "buffer zone," to prevent small, uncontrolled, technical factors from causing major discrepancies in interpretations.] [Note 4: These breakpoints can be altered due to changes in circumstances (e.g., changes in commonly used drug dosages, emergence of new resistance mechanisms).]

2 | MS Deprecated | moderately susceptible | The patient is considered as carrier based on the testing results. A carrier is an individual who carries an altered form of a gene which can lead to having a child or offspring in future generations with a genetic disorder. Deprecation Comment: This antimicrobial susceptibility test interpretation concept is recommended by OO to be deprecated as it is no longer recommended for use in susceptibility testing by CLSI (reference CLSI document M100-S22; Vol. 32 No.3; CLSI Performance Standards for Antimicrobial Susceptibility Testing; Twenty-Second Informational Supplement. Jan 2012).

2 | NS | Non-susceptible | A category used for isolates for which only a susceptible interpretive criterion has been designated because of the absence or rare occurrence of resistant strains. Isolates that have MICs above or zone diameters below the value indicated for the susceptible breakpoint should be reported as non-susceptible. NOTE 1: An isolate that is interpreted as non-susceptible does not necessarily mean that the isolate has a resistance mechanism. It is possible that isolates with MICs above the susceptible breakpoint that lack resistance mechanisms may be encountered within the wild-type distribution subsequent to the time the susceptible-only breakpoint is set. NOTE 2: For strains yielding results in the "nonsusceptible" category, organism identification and antimicrobial susceptibility test results should be confirmed. Synonym: decreased susceptibility.

2 | R | Resistant | Bacterial strain inhibited in vitro by a concentration of an antimicrobial agent that is associated with a high likelihood of therapeutic failure. Reference: CLSI (http://www.clsi.org/Content/NavigationMenu/Resources/HarmonizedTerminologyDatabase/Harmonized_Terminolo.htm) Projects: ISO 20776-1, ISO 20776-2 [Note 1: Bacterial strains are categorized as resistant by applying the appropriate breakpoints in a defined phenotypic test system.] [Note 2: This breakpoint can be altered due to changes in circumstances (e.g., changes in commonly used drug dosages, emergence of new resistance mechanisms).]

3 | SYN-R | Synergy - resistant | A category for isolates where the bacteria (e.g. enterococci) are not susceptible in vitro to a combination therapy (e.g., high-level aminoglycoside and cell wall active agent). This is predictive that this combination therapy will not be effective. Usage Note: Since the use of penicillin or ampicillin alone often results in treatment failure of serious enterococcal or other bacterial infections, combination therapy is usually indicated to enhance bactericidal activity. The synergy between a cell wall active agent (such as penicillin, ampicillin, or vancomycin) and an aminoglycoside (such as gentamicin, kanamycin or streptomycin) is best predicted by screening for high-level bacterial resistance to the aminoglycoside. Open Issue: The print name of the code is very general and the description is very specific to a pair of classes of agents, which may lead to confusion of these concepts in the future should other synergies be found.

2 | S | Susceptible | Bacterial strain inhibited by in vitro concentration of an antimicrobial agent that is associated with a high likelihood of therapeutic success. Reference: CLSI (http://www.clsi.org/Content/NavigationMenu/Resources/HarmonizedTerminologyDatabase/Harmonized_Terminolo.htm) Synonym (earlier term): Sensitive Projects: ISO 20776-1, ISO 20776-2 [Note 1: Bacterial strains are categorized as susceptible by applying the appropriate breakpoints in a defined phenotypic system.] [Note 2: This breakpoint can be altered due to changes in circumstances (e.g., changes in commonly used drug dosages, emergence of new resistance mechanisms).]

3 | SDD | Susceptible-dose dependent | A category that includes isolates with antimicrobial agent minimum inhibitory concentrations (MICs) that approach usually attainable blood and tissue levels and for which response rates may be lower than for susceptible isolates. Reference: CLSI document M44-A2 2009 "Method for antifungal disk diffusion susceptibility testing of yeasts; approved guideline - second edition" - page 2.

3 | SYN-S | Synergy - susceptible | A category for isolates where the bacteria (e.g. enterococci) are susceptible in vitro to a combination therapy (e.g., high-level aminoglycoside and cell wall active agent). This is predictive that this combination therapy will be effective. Usage Note: Since the use of penicillin or ampicillin alone often results in treatment failure of serious enterococcal or other bacterial infections, combination therapy is usually indicated to enhance bactericidal activity. The synergy between a cell wall active agent (such as penicillin, ampicillin, or vancomycin) and an aminoglycoside (such as gentamicin, kanamycin or streptomycin) is best predicted by screening for high-level bacterial resistance to the aminoglycoside. Open Issue: The print name of the code is very general and the description is very specific to a pair of classes of agents, which may lead to confusion of these concepts in the future should other synergies be found.

2 | VS Deprecated | very susceptible | The patient is considered as carrier based on the testing results. A carrier is an individual who carries an altered form of a gene which can lead to having a child or offspring in future generations with a genetic disorder. Deprecation Comment: This antimicrobial susceptibility test interpretation concept is recommended by OO to be deprecated as it is no longer recommended for use in susceptibility testing by CLSI (reference CLSI document M100-S22; Vol. 32 No.3; CLSI Performance Standards for Antimicrobial Susceptibility Testing; Twenty-Second Informational Supplement. Jan 2012).

1 | EX | outside threshold | The observation/test result is interpreted as being outside the inclusion range for a particular protocol within which the result is being reported. Example: A positive result on a Hepatitis screening test. Open Issue: EX, HX, LX: These three concepts do not seem to meet a clear need in the vocabulary, and their use in observation interpretation appears likely to be covered by other existing concepts (e.g., A, H, L). The only apparent significant difference is their reference to use in protocols for exclusion of study subjects. These concepts/codes were proposed by RCRIM for use in the CTLaboratory message. They were submitted and approved in the November 2005 Harmonization cycle in proposal "030103C_VOCAB_RCRIM_l_quade_RCRIM Obs Interp_20051028154455". However, this proposal was not fully implemented in the vocabulary. The proposal recommended creation of the x_ClinicalResearchExclusion domain in ObservationInterpretation with a value set including those three concepts/codes, but there is no subdomain of that name or equivalent with a binding to either of the value sets that contain these concepts/codes. Members of the OO WG have recently attempted to contact members of RCRIM regarding these concepts, both by email and at the recent WGM in Atlanta, without response. It is felt by OO that the best course of action to take at this time is to add this comprehensive Open Issue rather than deprecate these three concepts at this time, until further discussion is held.

2 | HX | above high threshold | The observation/test result is interpreted as being outside the inclusion range for a particular protocol within which the result is being reported. Example: A positive result on a Hepatitis screening test. Open Issue: EX, HX, LX: These three concepts do not seem to meet a clear need in the vocabulary, and their use in observation interpretation appears likely to be covered by other existing concepts (e.g., A, H, L). The only apparent significant difference is their reference to use in protocols for exclusion of study subjects. These concepts/codes were proposed by RCRIM for use in the CTLaboratory message. They were submitted and approved in the November 2005 Harmonization cycle in proposal "030103C_VOCAB_RCRIM_l_quade_RCRIM Obs Interp_20051028154455". However, this proposal was not fully implemented in the vocabulary. The proposal recommended creation of the x_ClinicalResearchExclusion domain in ObservationInterpretation with a value set including those three concepts/codes, but there is no subdomain of that name or equivalent with a binding to either of the value sets that contain these concepts/codes.

Members of the OO WG have recently attempted to contact members of RCRIM regarding these concepts, both by email and at the recent WGM in Atlanta, without response. It is felt by OO that the best course of action to take at this time is to add this comprehensive Open Issue rather than deprecate these three concepts at this time, until further discussion is held.

2 | LX | below low threshold | The numeric observation/test result is interpreted as being below the low threshold value for a particular protocol within which the result is being reported. Example: A Total White Blood Cell Count falling below a protocol-defined threshold value of 3000/mm^3 Open Issue: EX, HX, LX: These three concepts do not seem to meet a clear need in the vocabulary, and their use in observation interpretation appears likely to be covered by other existing concepts (e.g., A, H, L). The only apparent significant difference is their reference to use in protocols for exclusion of study subjects. These concepts/codes were proposed by RCRIM for use in the CTLaboratory message. They were submitted and approved in the November 2005 Harmonization cycle in proposal "030103C_VOCAB_RCRIM_I_quade_RCRIM Obs Interp_20051028154455". However, this proposal was not fully implemented in the vocabulary. The proposal recommended creation of the x_ClinicalResearchExclusion domain in ObservationInterpretation with a value set including those three concepts/codes, but there is no subdomain of that name or equivalent with a binding to either of the value sets that contain these concepts/codes. Members of the OO WG have recently attempted to contact members of RCRIM regarding these concepts, both by email and at the recent WGM in Atlanta, without response. It is felt by OO that the best course of action to take at this time is to add this comprehensive Open Issue rather than deprecate these three concepts at this time, until further discussion is held.

1 | HM Deprecated | Hold for Medical Review | Hold for Medical Review Usage Note: This code is not intended for use in V3 artifacts. It is included in the code system to maintain alignment with the V2 Table 0078 "Interpretation Codes."

1 | (ObservationInterpretationDetection) Abstract | | Interpretations of the presence or absence of a component / analyte or organism in a test or of a sign in a clinical observation. In keeping with laboratory data processing practice, these concepts provide a categorical interpretation of the "meaning" of the quantitative value for the same observation.

2 | IND | Indeterminate | The specified component / analyte, organism or clinical sign could neither be declared positive / negative nor detected / not detected by the performed test or procedure. Usage Note: For example, if the specimen was degraded, poorly processed, or was missing the required anatomic structures, then "indeterminate" (i.e. "cannot be determined") is the appropriate response, not "equivocal".

3 | E | Equivocal | The test or procedure was successfully performed, but the results are borderline and can neither be declared positive / negative nor detected / not detected according to the current established criteria.

2 | NEG | Negative | An absence finding of the specified component / analyte, organism or clinical sign based on the established threshold of the performed test or procedure. [Note: Negative does not necessarily imply the complete absence of the specified item.]

3 | ND | Not detected | The presence of the specified component / analyte, organism or clinical sign could not be determined within the limit of detection of the performed test or procedure.

2 | POS | Positive | A presence finding of the specified component / analyte, organism or clinical sign based on the established threshold of the performed test or procedure.

3 | DET | Detected | The measurement of the specified component / analyte, organism or clinical sign above the limit of detection of the performed test or procedure.

1 | (ObservationInterpretationExpectation) Abstract | | Interpretation of the observed result taking into account additional information (contraindicators) about the patient's situation. Concepts in this category are mutually exclusive, i.e., at most one is allowed.

2 | EXP | Expected | This result has been evaluated in light of known contraindicators. Once those contraindicators have been taken into account the result is determined to be "Expected" (e.g., presence of drugs in a patient that is taking prescription medication for pain management).

2 | UNE | Unexpected | This result has been evaluated in light of known contraindicators. Once those contraindicators have been taken into account the result is determined to be "Unexpected" (e.g., presence of non-prescribed drugs in a patient that is taking prescription medication for pain management).

1 | OBX Deprecated | Interpretation qualifiers in separate OBX segments | Interpretation qualifiers in separate OBX segments Usage Note: This code is not intended for use in V3 artifacts. It is included in the code system to maintain alignment with the V2 Table 0078 "Interpretation Codes."

1 | (ReactivityObservationInterpretation) Abstract | | Interpretations of the presence and level of reactivity of the specified component / analyte with the reagent in the performed laboratory test.

2 | NR | Non-reactive | An absence finding used to indicate that the specified component / analyte did not react measurably with the reagent.

2 | RR | Reactive | A presence finding used to indicate that the specified component / analyte reacted with the reagent above the reliably measurable limit of the performed test.

3 | WR | Weakly reactive | A weighted presence finding used to indicate that the specified component / analyte reacted with the reagent, but below the reliably measurable limit of the performed test.

4.3.2.84 HL7 v3 Code System ObservationMethod

URL: https://hl7.org/fhir/STU3/v3/ObservationMethod/cs.html

This page is part of the FHIR Specification (v3.0.2: STU 3). The current version which supercedes this version is 4.0.1. For a full list of available versions, see the Directory of published versions

Vocabulary Work Group | Maturity Level: N/A | External | Use Context: Any

This code system (http://hl7.org/fhir/v3/ObservationMethod) is defined as part of HL7 v3.

Summary

Defining URL: | http://hl7.org/fhir/v3/ObservationMethod

Name: | v3 Code System ObservationMethod

Definition: | A code that provides additional detail about the means or technique used to ascertain the observation. Examples: Blood pressure measurement method: arterial puncture vs. sphygmomanometer (Riva-Rocci), sitting vs. supine position, etc. OpenIssue: Description copied from Concept Domain of same name. Must be verified. Note that the Domain has a full discussion about use of the attribute and constraining that is not appropriate for the code system description. Needs to be improved.

OID: | 2.16.840.1.113883.5.84 (for OID based terminology systems)

Source Resource | XML / JSON

This Code system is used in the following value sets:

* v3 Code System ObservationMethod (A code that provides additional detail about the means or technique used to ascertain the observation. Examples: Blood pressure measurement method: arterial puncture vs. sphygmomanometer (Riva-Rocci), sitting vs. supine position, etc. OpenIssue: Description copied from Concept Domain of same name. Must be verified. Note that the Domain has a full discussion about use of the attribute and constraining that is not appropriate for the code system description. Needs to be improved.)

* VerificationMethod (No Description Provided)

4.3.2.84.1 Code System Content

Release Date: 2016-11-11

Level | Code | Display | Definition
1 | (_DecisionObservationMethod) Abstract | | Provides codes for decision methods, initially for assessing the causality of events.
2 | ALGM | algorithm | Reaching a decision through the application of an algorithm designed to weigh the different factors involved.
3 | BYCL | bayesian calculation | Reaching a decision through the use of Bayesian statistical analysis.
2 | GINT | global introspection | Reaching a decision by consideration of the totality of factors involved in order to reach a judgement.
1 | (_GeneticObservationMethod) Abstract | | A code that provides additional detail about the means or technique used to ascertain the genetic analysis. Example, PCR, Micro Array
2 | PCR | PCR | Description: Polymerase Chain Reaction
1 | (_ObservationMethodAggregate) Abstract | | Provides additional detail about the aggregation methods used to compute the aggregated values for an observation. This is an abstract code.
2 | AVERAGE | average | Average of non-null values in the referenced set of values
2 | COUNT | count | Count of non-null values in the referenced set of values
2 | MAX | maxima | Largest of all non-null values in the referenced set of values.
2 | MEDIAN | median | The median of all non-null values in the referenced set of values.
2 | MIN | minima | Smallest of all non-null values in the referenced set of values.
2 | MODE | mode | The most common value of all non-null values in the referenced set of values.
2 | STDEV.P | population standard deviation | Standard Deviation of the values in the referenced set of values, computed over the population.
2 | STDEV.S | sample standard deviation | Standard Deviation of the values in the referenced set of values, computed over a sample of the population.
2 | SUM | sum | Sum of non-null values in the referenced set of values
2 | VARIANCE.P | population variance | Variance of the values in the referenced set of values, computed over the population.
2 | VARIANCE.S | sample variance | Variance of the values in the referenced set of values, computed over a sample of the population.
1 | (_VerificationMethod) Abstract
2 | VDOC | document verification | Verification by means of document. Example: Fax, letter, attachment to e-mail.
2 | VREG | registry verification | verification by means of a response to an electronic query Example: query message to a Covered Party registry application or Coverage Administrator.
2 | VTOKEN | electronic token verification | Verification by means of electronic token. Example: smartcard, magnetic swipe card, RFID device.
2 | VVOICE | voice-based verification | Verification by means of voice. Example: By speaking with or calling the Coverage Administrator or Covered Party
1 | 0001 | Complement fixation | Complement fixation
1 | 0002 | Computed axial tomography | Computed axial tomography
1 | 0003 | HLAR agar test | Susceptibility, High Level Aminoglycoside Resistance agar test
1 | 0004 | Macroscopic observation | Visual, Macroscopic observation
1 | 0005 | Magnetic resonance | Computed, Magnetic resonance
1 | 0006 | Morphometry | Computed, Morphometry
1 | 0007 | Positron emission tomography | Computed, Positron emission tomography
1 | 0008 | SAMHSA confirmation | SAMHSA drug assay confirmation
1 | 0009 | SAMHSA screening | SAMHSA drug assay screening
1 | 0010 | Serum Neutralization | Serum Neutralization
1 | 0011 | Titration | Titration
1 | 0012 | Ultrasound | Ultrasound
1 | 0013 | X-ray crystallography | X-ray crystallography
1 | 0014 | Agglutination | Agglutination
1 | 0015 | Buffered acidified plate agglutination | Agglutination, Buffered acidified plate
1 | 0016 | Card agglutination | Agglutination, Card
1 | 0017 | Hemagglutination | Agglutination, Hemagglutination
1 | 0018 | Hemagglutination inhibition | Agglutination, Hemagglutination inhibition
1 | 0019 | Latex agglutination | Agglutination, Latex
1 | 0020 | Plate agglutination | Agglutination, Plate
1 | 0021 | Rapid agglutination | Agglutination, Rapid Plate
1 | 0022 | RBC agglutination | Agglutination, RBC
1 | 0023 | Rivanol agglutination | Agglutination, Rivanol
1 | 0024 | Tube agglutination | Agglutination, Tube
1 | 0025 | Bioassay | Bioassay
1 | 0026 | Animal Inoculation | Bioassay, Animal Inoculation
1 | 0027 | Cytotoxicity | Bioassay, Cytotoxicity
1 | 0028 | Embryo infective dose 50 | Bioassay, Embryo Infective Dose 50
1 | 0029 | Embryo lethal dose 50 | Bioassay, Embryo Lethal Dose 50
1 | 0030 | Mouse intercerebral inoculation | Bioassay, Mouse intercerebral inoculation
1 | 0031 | Bioassay, qualitative | Bioassay, qualitative
1 | 0032 | Bioassay, quantitative | Bioassay, quantitative
1 | 0033 | Chemical method | Chemical
1 | 0034 | Differential light absorption chemical test | Chemical, Differential light absorption
1 | 0035 | Dipstick | Chemical, Dipstick
1 | 0036 | Dipstick colorimetric laboratory test | Chemical, Dipstick colorimetric laboratory test
1 | 0037 | Test strip | Chemical, Test strip
1 | 0038 | Chromatography | Chromatography
1 | 0039 | Affinity chromatography | Chromatography, Affinity
1 | 0040 | Gas liquid chromatography | Chromatography, Gas liquid
1 | 0041 | High performance liquid chromatography | Chromatography, High performance liquid

1 | 0042 | Liquid Chromatography | Chromatography, Liquid
1 | 0043 | Protein A affinity chromatography | Chromatography, Protein A affinity
1 | 0044 | Coagulation | Coagulation
1 | 0045 | Tilt tube coagulation time | Coagulation, Tilt tube
1 | 0046 | Tilt tube reptilase induced coagulation | Coagulation, Tilt tube reptilase induced
1 | 0047 | Automated count | Count, Automated
1 | 0048 | Manual cell count | Count, Manual
1 | 0049 | Platelet count, Rees-Ecker | Count, Platelet, Rees-Ecker
1 | 0050 | Aerobic Culture | Culture, Aerobic
1 | 0051 | Anaerobic Culture | Culture, Anaerobic
1 | 0052 | Chicken embryo culture | Culture, Chicken Embryo
1 | 0053 | Delayed secondary enrichment | Culture, Delayed secondary enrichment
1 | 0054 | Microaerophilic Culture | Culture, Microaerophilic
1 | 0055 | Quantitative microbial culture, cup | Culture, Quantitative microbial, cup
1 | 0056 | Quantitative microbial culture, droplet | Culture, Quantitative microbial, droplet
1 | 0057 | Quantitative microbial culture, filter paper | Culture, Quantitative microbial, filter paper
1 | 0058 | Quantitative microbial culture, pad culture | Culture, Quantitative microbial, pad
1 | 0059 | Quantitative microbial culture, pour plate | Culture, Quantitative microbial, pour plate
1 | 0060 | Quantitative microbial culture, surface streak | Culture, Quantitative microbial, surface streak
1 | 0061 | Somatic Cell culture | Culture, Somatic Cell
1 | 0062 | Agar diffusion | Diffusion, Agar
1 | 0063 | Agar Gel Immunodiffusion | Diffusion, Agar Gel Immunodiffusion
1 | 0064 | Electrophoresis | Electrophoresis
1 | 0065 | Agaorse gel electrophoresis | Electrophoresis, Agaorse gel
1 | 0066 | Electrophoresis, citrate agar | Electrophoresis, citrate agar
1 | 0067 | Immunoelectrophoresis | Electrophoresis, Immuno
1 | 0068 | Polyacrylamide gel electrophoresis | Electrophoresis, Polyacrylamide gel
1 | 0069 | Starch gel electrophoresis | Electrophoresis, Starch gel
1 | 0070 | ELISA | ELISA
1 | 0071 | ELISA, antigen capture | ELISA, antigen capture
1 | 0072 | ELISA, avidin biotin peroxidase complex | ELISA, avidin biotin peroxidase complex
1 | 0073 | Kinetic ELISA | ELISA, Kinetic
1 | 0074 | ELISA, peroxidase-antiperoxidase | ELISA, peroxidase-antiperoxidase
1 | 0075 | API 20 Strep | Identification, API 20 Strep
1 | 0076 | API 20A | Identification, API 20A
1 | 0077 | API 20C AUX | Identification, API 20C AUX
1 | 0078 | API 20E | Identification, API 20E
1 | 0079 | API 20NE | Identification, API 20NE
1 | 0080 | API 50 CH | Identification, API 50 CH
1 | 0081 | API An-IDENT | Identification, API An-IDENT
1 | 0082 | API Coryne | Identification, API Coryne
1 | 0083 | API Rapid 20E | Identification, API Rapid 20E
1 | 0084 | API Staph | Identification, API Staph
1 | 0085 | API ZYM | Identification, API ZYM
1 | 0086 | Bacterial identification | Identification, Bacterial
1 | 0087 | mini VIDAS | Identification, mini VIDAS
1 | 0088 | Phage susceptibility typing | Identification, Phage susceptibility typing
1 | 0089 | Quad-FERM+ | Identification, Quad-FERM+
1 | 0090 | RAPIDEC Staph | Identification, RAPIDEC Staph
1 | 0091 | Staphaurex | Identification, Staphaurex
1 | 0092 | VIDAS | Identification, VIDAS
1 | 0093 | Vitek | Identification, Vitek
1 | 0094 | VITEK 2 | Identification, VITEK 2
1 | 0095 | Immune stain | Immune stain
1 | 0096 | Immunofluorescent antibody, direct | Immune stain, Immunofluorescent antibody, direct
1 | 0097 | Immunofluorescent antibody, indirect | Immune stain, Immunofluorescent antibody, indirect
1 | 0098 | Immunoperoxidase, Avidin-Biotin Complex | Immune stain, Immunoperoxidase, Avidin-Biotin Complex
1 | 0099 | Immunoperoxidase, Peroxidase anti-peroxidase complex | Immune stain, Immunoperoxidase, Peroxidase anti-peroxidase complex
1 | 0100 | Immunoperoxidase, Protein A-peroxidase complex | Immune stain, Immunoperoxidase, Protein A-peroxidase complex
1 | 0101 | Immunoassay | Immunoassay
1 | 0102 | Immunoassay, qualitative, multiple step | Immunoassay, qualitative, multiple step
1 | 0103 | Immunoassay, qualitative, single step | Immunoassay, qualitative, single step
1 | 0104 | Radioimmunoassay | Immunoassay, Radioimmunoassay
1 | 0105 | Immunoassay, semi-quantitative, multiple step | Immunoassay, semi-quantitative, multiple step
1 | 0106 | Immunoassay, semi-quantitative, single step | Immunoassay, semi-quantitative, single step
1 | 0107 | Microscopy | Microscopy
1 | 0108 | Darkfield microscopy | Microscopy, Darkfield
1 | 0109 | Electron microscopy | Microscopy, Electron
1 | 0110 | Electron microscopy tomography | Microscopy, Electron microscopy tomography
1 | 0111 | Electron microscopy, negative stain | Microscopy, Electron, negative stain
1 | 0112 | Electron microscopy, thick section | Microscopy, Electron, thick section transmission
1 | 0113 | Electron microscopy, thin section | Microscopy, Electron, thin section transmission

1 | 0114 | Microscopy, Light | Microscopy, Light
1 | 0115 | Polarizing light microscopy | Microscopy, Polarized light
1 | 0116 | Scanning electron microscopy | Microscopy, Scanning electron
1 | 0117 | Transmission electron microscopy | Microscopy, Transmission electron
1 | 0118 | Transparent tape direct examination | Microscopy, Transparent tape direct examination
1 | 0119 | 3 Self-Sustaining Sequence Replication | Molecular, 3 Self-Sustaining Sequence Replication
1 | 0120 | Branched Chain DNA | Molecular, Branched Chain DNA
1 | 0121 | Hybridization Protection Assay | Molecular, Hybridization Protection Assay
1 | 0122 | Immune blot | Molecular, Immune blot
1 | 0123 | In-situ hybridization | Molecular, In-situ hybridization
1 | 0124 | Ligase Chain Reaction | Molecular, Ligase Chain Reaction
1 | 0125 | Ligation Activated Transcription | Molecular, Ligation Activated Transcription
1 | 0126 | Nucleic Acid Probe | Molecular, Nucleic Acid Probe
1 | 0128 | Nucleic acid probe with amplification | Molecular, Nucleic acid probe with amplification Rationale: Duplicate of code 0126. Use code 0126 instead.
1 | 0129 | Nucleic acid probe with target amplification | Molecular, Nucleic acid probe with target amplification
1 | 0130 | Nucleic acid reverse transcription | Molecular, Nucleic acid reverse transcription
1 | 0131 | Nucleic Acid Sequence Based Analysis | Molecular, Nucleic Acid Sequence Based Analysis
1 | 0132 | Polymerase chain reaction | Molecular, Polymerase chain reaction
1 | 0133 | Q-Beta Replicase or probe amplification category method | Molecular, Q-Beta Replicase or probe amplification category method
1 | 0134 | Restriction Fragment Length Polymorphism | Molecular, Restriction Fragment Length Polymorphism
1 | 0135 | Southern Blot | Molecular, Southern Blot
1 | 0136 | Strand Displacement Amplification | Molecular, Strand Displacement Amplification
1 | 0137 | Transcription Mediated Amplification | Molecular, Transcription Mediated Amplification
1 | 0138 | Western Blot | Molecular, Western Blot
1 | 0139 | Flocculation | Precipitation, Flocculation
1 | 0140 | Immune precipitation | Precipitation, Immune precipitation
1 | 0141 | Milk ring test | Precipitation, Milk ring test
1 | 0142 | Precipitin | Precipitation, Precipitin
1 | 0143 | Acid fast stain | Stain, Acid fast
1 | 0144 | Acid fast stain, fluorochrome | Stain, Acid fast, fluorochrome
1 | 0145 | Acid fast stain, Kinyoun's cold carbolfuchsin | Stain, Acid fast, Kinyoun's cold carbolfuchsin
1 | 0146 | Acid fast stain, Ziehl-Neelsen | Stain, Acid fast, Ziehl-Neelsen
1 | 0147 | Acid phosphatase stain | Stain, Acid phosphatase
1 | 0148 | Acridine orange stain | Stain, Acridine orange
1 | 0149 | Active brilliant orange KH stain | Stain, Active brilliant orange KH
1 | 0150 | Alazarin red S stain | Stain, Alazarin red S
1 | 0151 | Alcian blue stain | Stain, Alcian blue
1 | 0152 | Alcian blue with Periodic acid Schiff stain | Stain, Alcian blue with Periodic acid Schiff
1 | 0153 | Argentaffin stain | Stain, Argentaffin
1 | 0154 | Argentaffin silver stain | Stain, Argentaffin silver
1 | 0155 | Azure-eosin stain | Stain, Azure-eosin
1 | 0156 | Basic Fuschin stain | Stain, Basic Fuschin
1 | 0157 | Bennhold stain | Stain, Bennhold
1 | 0158 | Bennhold's Congo red stain | Stain, Bennhold's Congo red
1 | 0159 | Bielschowsky stain | Stain, Bielschowsky
1 | 0160 | Bielschowsky's silver stain | Stain, Bielschowsky's silver
1 | 0161 | Bleach stain | Stain, Bleach
1 | 0162 | Bodian stain | Stain, Bodian
1 | 0163 | Brown-Brenn stain | Stain, Brown-Brenn
1 | 0164 | Butyrate-esterase stain | Stain, Butyrate-esterase
1 | 0165 | Calcofluor white fluorescent stain | Stain, Calcofluor white fluorescent
1 | 0166 | Carbol-fuchsin stain | Stain, Carbol-fuchsin
1 | 0167 | Carmine stain | Stain, Carmine
1 | 0168 | Churukian-Schenk stain | Stain, Churukian-Schenk
1 | 0169 | Congo red stain | Stain, Congo red
1 | 0170 | Cresyl echt violet stain | Stain, Cresyl echt violet
1 | 0171 | Crystal violet stain | Stain, Crystal violet
1 | 0172 | De Galantha stain | Stain, De Galantha
1 | 0173 | Dieterle silver impregnation stain | Stain, Dieterle silver impregnation
1 | 0174 | Fite-Farco stain | Stain, Fite-Farco
1 | 0175 | Fontana-Masson silver stain | Stain, Fontana-Masson silver
1 | 0176 | Fouchet stain | Stain, Fouchet
1 | 0177 | Gomori stain | Stain, Gomori
1 | 0178 | Gomori methenamine silver stain | Stain, Gomori methenamine silver
1 | 0179 | Gomori-Wheatly trichrome stain | Stain, Gomori-Wheatly trichrome
1 | 0180 | Gridley stain | Stain, Gridley
1 | 0181 | Grimelius silver stain | Stain, Grimelius silver
1 | 0182 | Grocott stain | Stain, Grocott
1 | 0183 | Grocott methenamine silver stain | Stain, Grocott methenamine silver
1 | 0184 | Hale's colloidal ferric oxide stain | Stain, Hale's colloidal ferric oxide
1 | 0185 | Hale's colloidal iron stain | Stain, Hale's colloidal iron

1 | 0186 | Hansel stain | Stain, Hansel
1 | 0187 | Harris regressive hematoxylin and eosin stain | Stain, Harris regressive hematoxylin and eosin
1 | 0188 | Hematoxylin and eosin stain | Stain, Hematoxylin and eosin
1 | 0189 | Highman stain | Stain, Highman
1 | 0190 | Holzer stain | Stain, Holzer
1 | 0191 | Iron hematoxylin stain | Stain, Iron hematoxylin
1 | 0192 | Jones stain | Stain, Jones
1 | 0193 | Jones methenamine silver stain | Stain, Jones methenamine silver
1 | 0194 | Kossa stain | Stain, Kossa
1 | 0195 | Lawson-Van Gieson stain | Stain, Lawson-Van Gieson
1 | 0196 | Loeffler methylene blue stain | Stain, Loeffler methylene blue
1 | 0197 | Luxol fast blue with cresyl violet stain | Stain, Luxol fast blue with cresyl violet
1 | 0198 | Luxol fast blue with Periodic acid-Schiff stain | Stain, Luxol fast blue with Periodic acid-Schiff
1 | 0199 | MacNeal's tetrachrome blood stain | Stain, MacNeal's tetrachrome blood
1 | 0200 | Mallory-Heidenhain stain | Stain, Mallory-Heidenhain
1 | 0201 | Masson trichrome stain | Stain, Masson trichrome
1 | 0202 | Mayer mucicarmine stain | Stain, Mayer mucicarmine
1 | 0203 | Mayers progressive hematoxylin and eosin stain | Stain, Mayers progressive hematoxylin and eosin
1 | 0204 | May-Grunwald Giemsa stain | Stain, May-Grunwald Giemsa
1 | 0205 | Methyl green stain | Stain, Methyl green
1 | 0206 | Methyl green pyronin stain | Stain, Methyl green pyronin
1 | 0207 | Modified Gomori-Wheatly trichrome stain | Stain, Modified Gomori-Wheatly trichrome
1 | 0208 | Modified Masson trichrome stain | Stain, Modified Masson trichrome
1 | 0209 | Modified trichrome stain | Stain, Modified trichrome
1 | 0210 | Movat pentachrome stain | Stain, Movat pentachrome
1 | 0211 | Mucicarmine stain | Stain, Mucicarmine
1 | 0212 | Neutral red stain | Stain, Neutral red
1 | 0213 | Night blue stain | Stain, Night blue
1 | 0214 | Non-specific esterase stain | Stain, Non-specific esterase
1 | 0215 | Oil red-O stain | Stain, Oil red-O
1 | 0216 | Orcein stain | Stain, Orcein
1 | 0217 | Perls' stain | Stain, Perls'
1 | 0218 | Phosphotungstic acid-hematoxylin stain | Stain, Phosphotungstic acid-hematoxylin
1 | 0219 | Potassium ferrocyanide stain | Stain, Potassium ferrocyanide
1 | 0220 | Prussian blue stain | Stain, Prussian blue
1 | 0221 | Putchler modified Bennhold stain | Stain, Putchler modified Bennhold
1 | 0222 | Quinacrine fluorescent stain | Stain, Quinacrine fluorescent
1 | 0223 | Reticulin stain | Stain, Reticulin
1 | 0224 | Rhodamine stain | Stain, Rhodamine
1 | 0225 | Safranin stain | Stain, Safranin
1 | 0226 | Schmorl stain | Stain, Schmorl
1 | 0227 | Seiver-Munger stain | Stain, Seiver-Munger
1 | 0228 | Silver stain | Stain, Silver
1 | 0229 | Specific esterase stain | Stain, Specific esterase
1 | 0230 | Steiner silver stain | Stain, Steiner silver
1 | 0231 | Sudan III stain | Stain, Sudan III
1 | 0232 | Sudan IVI stain | Stain, Sudan IVI
1 | 0233 | Sulfated alcian blue stain | Stain, Sulfated alcian blue
1 | 0234 | Supravital stain | Stain, Supravital
1 | 0235 | Thioflavine-S stain | Stain, Thioflavine-S
1 | 0236 | Three micron Giemsa stain | Stain, Three micron Giemsa
1 | 0237 | Vassar-Culling stain | Stain, Vassar-Culling
1 | 0238 | Vital Stain | Stain, Vital
1 | 0239 | von Kossa stain | Stain, von Kossa
1 | 0243 | Minimum bactericidal concentration test, macrodilution | Susceptibility, Minimum bactericidal concentration, macrodilution
1 | 0244 | Minimum bactericidal concentration test, microdilution | Susceptibility, Minimum bactericidal concentration, microdilution
1 | 0247 | Turbidometric | Turbidometric
1 | 0248 | Refractometric | Turbidometric, Refractometric
1 | 0249 | Thin layer chromatography (TLC) | Chromatography, Thin Layer
1 | 0250 | EMIT | Immunoassay, enzyme-multiplied technique (EMIT)
1 | 0251 | Flow cytometry (FC) | Flow Cytometry
1 | 0252 | Radial immunodiffusion (RID) | Radial Immunodiffusion
1 | 0253 | Fluorescence polarization immunoassay (FPIA) | Immunoassay, Fluorescence Polarization
1 | 0254 | Immunofixation electrophoresis (IFE) | Electrophoresis, Immunofixation
1 | 0255 | Equilibrium dialysis | Dialysis, Direct Equilibrium
1 | 0256 | Kleihauer-Betke acid elution | Acid Elution, Kleihauer-Betke Method
1 | 0257 | Anti-complement immunofluorescence (ACIF) | Immunofluorescence, Anti-Complement
1 | 0258 | GC/MS | Gas Chromatography/Mass Spectroscopy
1 | 0259 | Nephelometry | Light Scatter, Nephelometry
1 | 0260 | IgE immunoassay antibody | Immunoassay, IgE Antibody Test
1 | 0261 | Lymphocyte Microcytotoxicity Assay | Lymphocyte Microcytotoxicity Assay
1 | 0262 | Spectrophotometry | Spectrophotometry

1 | 0263 | Atomic absorption spectrophotometry (AAS) | Spectrophotometry, Atomic Absorption
1 | 0264 | Ion selective electrode (ISE) | Electrochemical, Ion Selective Electrode
1 | 0265 | Gas chromatography (GC) | Chromatography, Gas
1 | 0266 | Isoelectric focusing (IEF) | Isoelectric Focusing
1 | 0267 | Immunochemiluminescence | Immunoassay, Chemiluminescent
1 | 0268 | Microparticle enzyme immunoassay (MEIA) | Immunoassay, Microparticle Enzyme
1 | 0269 | ICP/MS | Inductively-Coupled Plasma/Mass Spectrometry
1 | 0270 | Immunoradiometric assay (IRMA) | Immunoassay, Immunoradiometric Assay
1 | 0271 | Photo optical clot detection | Coagulation, Photo Optical Clot Detection
1 | 0280 | Susceptibility Testing | Test methods designed to determine a microorganismaTMs susceptibility to being killed by an antibiotic.
2 | 0240 | Antibiotic sensitivity, disk | Susceptibility, Antibiotic sensitivity, disk
2 | 0241 | BACTEC susceptibility test | Susceptibility, BACTEC susceptibility test
2 | 0242 | Disk dilution | Susceptibility, Disk dilution
2 | 0272 | Minimum Inhibitory Concentration | Testing to measure the minimum concentration of the antibacterial agent in a given culture medium below which bacterial growth is not inhibited.
3 | 0245 | Minimum Inhibitory Concentration, macrodilution | Susceptibility, Minimum Inhibitory concentration, macrodilution
3 | 0246 | Minimum Inhibitory Concentration, microdilution | Susceptibility, Minimum Inhibitory concentration, microdilution
2 | 0273 | Viral Genotype Susceptibility
2 | 0274 | Viral Phenotype Susceptibility
2 | 0275 | Gradient Strip
2 | 0275a | Minimum Lethal Concentration (MLC)
2 | 0276 | Slow Mycobacteria Susceptibility | Testing to measure the minimum concentration of the antibacterial agent in a given culture medium below which bacterial growth is not inhibited.
2 | 0277 | Serum bactericidal titer
2 | 0278 | Agar screen
2 | 0279 | Disk induction
1 | 0127 | Nucleic acid probe | Molecular, Nucleic acid probe

4.3.2.85 HL7 v3 Code System orderableDrugForm

URL: https://hl7.org/fhir/STU3/v3/orderableDrugForm/cs.html

This page is part of the FHIR Specification (v3.0.2: STU 3). The current version which supercedes this version is 4.0.1. For a full list of available versions, see the Directory of published versions

Vocabulary Work Group | Maturity Level: N/A | External | Use Context: Any

This code system (http://hl7.org/fhir/v3/orderableDrugForm) is defined as part of HL7 v3.

Summary

Defining URL: | http://hl7.org/fhir/v3/orderableDrugForm
Name: | v3 Code System orderableDrugForm
Definition: | OpenIssue: Missing description.
OID: | 2.16.840.1.113883.5.85 (for OID based terminology systems)
Source Resource | XML / JSON

This Code system is used in the following value sets:

* v3 Code System orderableDrugForm (OpenIssue: Missing description.)

4.3.2.85.1 Code System Content

Release Date: 2016-11-11

Level | Code | Display | Definition
1 | (_AdministrableDrugForm) Abstract
2 | APPFUL | Applicatorful
2 | DROP | Drops
3 | NDROP | Nasal Drops
3 | OPDROP | Ophthalmic Drops
3 | ORDROP | Oral Drops
3 | OTDROP | Otic Drops
2 | PUFF | Puff
2 | SCOOP | Scoops
2 | SPRY | Sprays
1 | (_DispensableDrugForm) Abstract
2 | (_GasDrugForm) Abstract | | Any elastic aeriform fluid in which the molecules are separated from one another and have free paths.
3 | GASINHL | Gas for Inhalation
2 | (_GasLiquidMixture) Abstract
3 | AER | Aerosol
4 | BAINHL | Breath Activated Inhaler
4 | INHLSOL | Inhalant Solution
4 | MDINHL | Metered Dose Inhaler
4 | NASSPRY | Nasal Spray
3 | DERMSPRY | Dermal Spray
3 | FOAM | Foam
4 | FOAMAPL | Foam with Applicator

4 | RECFORM | Rectal foam
4 | VAGFOAM | Vaginal foam
5 | VAGFOAMAPL | Vaginal foam with applicator
3 | RECSPRY | Rectal Spray
3 | VAGSPRY | Vaginal Spray
2 | (_GasSolidSpray) Abstract
3 | INHL | Inhalant
4 | BAINHLPWD | Breath Activated Powder Inhaler
4 | INHLPWD | Inhalant Powder
4 | MDINHLPWD | Metered Dose Powder Inhaler
4 | NASINHL | Nasal Inhalant
4 | ORINHL | Oral Inhalant
3 | PWDSPRY | Powder Spray
3 | SPRYADAPT | Spray with Adaptor
2 | (_Liquid) Abstract | | A state of substance that is an intermediate one entered into as matter goes from solid to gas; liquids are also intermediate in that they have neither the orderliness of a crystal nor the randomness of a gas. (Note: This term should not be used to describe solutions, only pure chemicals in their liquid state.)
3 | LIQCLN | Liquid Cleanser
4 | LIQSOAP | Medicated Liquid Soap
4 | SHMP | Shampoo | A liquid soap or detergent used to clean the hair and scalp and is often used as a vehicle for dermatologic agents.
3 | OIL | Oil | An unctuous, combustible substance which is liquid, or easily liquefiable, on warming, and is soluble in ether but insoluble in water. Such substances, depending on their origin, are classified as animal, mineral, or vegetable oils.
4 | TOPOIL | Topical Oil
3 | SOL | Solution | A liquid preparation that contains one or more chemical substances dissolved, i.e., molecularly dispersed, in a suitable solvent or mixture of mutually miscible solvents.
4 | DROP
4 | IPSOL | Intraperitoneal Solution
4 | IRSOL | Irrigation Solution | A sterile solution intended to bathe or flush open wounds or body cavities; they're used topically, never parenterally.
5 | DOUCHE | Douche | A liquid preparation, intended for the irrigative cleansing of the vagina, that is prepared from powders, liquid solutions, or liquid concentrates and contains one or more chemical substances dissolved in a suitable solvent or mutually miscible solvents.
5 | ENEMA | Enema | A rectal preparation for therapeutic, diagnostic, or nutritive purposes.
5 | OPIRSOL | Ophthalmic Irrigation Solution
4 | IVSOL | Intravenous Solution
4 | ORALSOL | Oral Solution
5 | ORDROP
5 | ELIXIR | Elixir | A clear, pleasantly flavored, sweetened hydroalcoholic liquid containing dissolved medicinal agents; it is intended for oral use.
5 | RINSE | Mouthwash/Rinse | An aqueous solution which is most often used for its deodorant, refreshing, or antiseptic effect.
5 | SYRUP | Syrup | An oral solution containing high concentrations of sucrose or other sugars; the term has also been used to include any other liquid dosage form prepared in a sweet and viscid vehicle, including oral suspensions.
4 | RECSOL | Rectal Solution
4 | TOPSOL | Topical Solution
5 | LIN | Liniment | A solution or mixture of various substances in oil, alcoholic solutions of soap, or emulsions intended for external application.
5 | MUCTOPSOL | Mucous Membrane Topical Solution
5 | TINC | Tincture
2 | (_LiquidLiquidEmulsion) Abstract | | A two-phase system in which one liquid is dispersed throughout another liquid in the form of small droplets.
3 | CRM | Cream | A semisolid dosage form containing one or more drug substances dissolved or dispersed in a suitable base; more recently, the term has been restricted to products consisting of oil-in-water emulsions or aqueous microcrystalline dispersions of long chain fatty acids or alcohols that are water washable and more cosmetically and aesthetically acceptable.
4 | NASCRM | Nasal Cream
4 | OPCRM | Ophthalmic Cream
4 | ORCRM | Oral Cream
4 | OTCRM | Otic Cream
4 | RECCRM | Rectal Cream
4 | TOPCRM | Topical Cream
4 | VAGCRM | Vaginal Cream
5 | VAGCRMAPL | Vaginal Cream with Applicator
3 | LTN | Lotion | The term "lotion" has been used to categorize many topical suspensions, solutions and emulsions intended for application to the skin.
4 | TOPLTN | Topical Lotion
3 | OINT | Ointment | A semisolid preparation intended for external application to the skin or mucous membranes.
4 | NASOINT | Nasal Ointment
4 | OINTAPL | Ointment with Applicator
4 | OPOINT | Ophthalmic Ointment
4 | OTOINT | Otic Ointment
4 | RECOINT | Rectal Ointment
4 | TOPOINT | Topical Ointment
4 | VAGOINT | Vaginal Ointment
5 | VAGOINTAPL | Vaginal Ointment with Applicator
2 | (_LiquidSolidSuspension) Abstract | | A liquid preparation which consists of solid particles dispersed throughout a liquid phase in which the particles are not soluble.
3 | GEL | Gel | A semisolid system consisting of either suspensions made up of small inorganic particles or large organic molecules interpenetrated by a liquid.
4 | GELAPL | Gel with Applicator

4 | NASGEL | Nasal Gel
4 | OPGEL | Ophthalmic Gel
4 | OTGEL | Otic Gel
4 | TOPGEL | Topical Gel
4 | URETHGEL | Urethral Gel
4 | VAGGEL | Vaginal Gel
5 | VGELAPL | Vaginal Gel with Applicator
3 | PASTE | Paste | A semisolid dosage form that contains one or more drug substances intended for topical application.
4 | PUD | Pudding
4 | TPASTE | Toothpaste | A paste formulation intended to clean and/or polish the teeth, and which may contain certain additional agents.
3 | SUSP | Suspension
4 | ITSUSP | Intrathecal Suspension
4 | OPSUSP | Ophthalmic Suspension
4 | ORSUSP | Oral Suspension
5 | ERSUSP | Extended-Release Suspension
6 | ERSUSP12 | 12 Hour Extended-Release Suspension
6 | ERSUSP24 | 24 Hour Extended Release Suspension
4 | OTSUSP | Otic Suspension
4 | RECSUSP | Rectal Suspension
2 | (_SolidDrugForm) Abstract
3 | BAR | Bar
4 | BARSOAP | Bar Soap
5 | MEDBAR | Medicated Bar Soap
4 | CHEWBAR | Chewable Bar | A solid dosage form usually in the form of a rectangle that is meant to be chewed.
3 | BEAD | Beads | A solid dosage form in the shape of a small ball.
3 | CAKE | Cake
3 | CEMENT | Cement | A substance that serves to produce solid union between two surfaces.
3 | CRYS | Crystals | A naturally produced angular solid of definite form in which the ultimate units from which it is built up are systematically arranged; they are usually evenly spaced on a regular space lattice.
3 | DISK | Disk | A circular plate-like organ or structure.
3 | FLAKE | Flakes
3 | GRAN | Granules | A small particle or grain.
3 | GUM | ChewingGum | A sweetened and flavored insoluble plastic material of various shapes which when chewed, releases a drug substance into the oral cavity.
3 | PAD | Pad
4 | MEDPAD | Medicated Pad
3 | PATCH | Patch | A drug delivery system that contains an adhesived backing and that permits its ingredients to diffuse from some portion of it (e.g., the backing itself, a reservoir, the adhesive, or some other component) into the body from the external site where it is applied.
4 | TPATCH | Transdermal Patch
5 | TPATH16 | 16 Hour Transdermal Patch
5 | TPATH24 | 24 Hour Transdermal Patch
5 | TPATH2WK | Biweekly Transdermal Patch
5 | TPATH72 | 72 Hour Transdermal Patch
5 | TPATHWK | Weekly Transdermal Patch
3 | PELLET | Pellet | A small sterile solid mass consisting of a highly purified drug (with or without excipients) made by the formation of granules, or by compression and molding.
3 | PILL | Pill | A small, round solid dosage form containing a medicinal agent intended for oral administration.
4 | CAP | Capsule | A solid dosage form in which the drug is enclosed within either a hard or soft soluble container or "shell" made from a suitable form of gelatin.
5 | ORCAP | Oral Capsule
6 | ENTCAP | Enteric Coated Capsule
7 | ERENTCAP | Extended Release Enteric Coated Capsule
6 | ERCAP | Extended Release Capsule | A solid dosage form in which the drug is enclosed within either a hard or soft soluble container made from a suitable form of gelatin, and which releases a drug (or drugs) in such a manner to allow a reduction in dosing frequency as compared to that drug (or drugs) presented as a conventional dosage form.
7 | ERENTCAP
7 | ERCAP12 | 12 Hour Extended Release Capsule
7 | ERCAP24 | 24 Hour Extended Release Capsule
7 | ERECCAP | Extended Release Enteric Coated Capsule | Rationale: Duplicate of code ERENTCAP. Use code ERENTCAP instead.
4 | TAB | Tablet | A solid dosage form containing medicinal substances with or without suitable diluents.
5 | ORTAB | Oral Tablet
6 | BUCTAB | Buccal Tablet
7 | SRBUCTAB | Sustained Release Buccal Tablet
6 | CAPLET | Caplet
6 | CHEWTAB | Chewable Tablet | A solid dosage form containing medicinal substances with or without suitable diluents that is intended to be chewed, producing a pleasant tasting residue in the oral cavity that is easily swallowed and does not leave a bitter or unpleasant after-taste.
6 | CPTAB | Coated Particles Tablet
6 | DISINTAB | Disintegrating Tablet | A solid dosage form containing medicinal substances which disintegrates rapidly, usually within a matter of seconds, when placed upon the tongue.
6 | DRTAB | Delayed Release Tablet
6 | ECTAB | Enteric Coated Tablet
7 | ERECTAB | Extended Release Enteric Coated Tablet

6 | ERTAB | Extended Release Tablet | A solid dosage form containing a drug which allows at least a reduction in dosing frequency as compared to that drug presented in conventional dosage form.
7 | ERECTAB
7 | ERTAB12 | 12 Hour Extended Release Tablet
7 | ERTAB24 | 24 Hour Extended Release Tablet
6 | ORTROCHE | Lozenge/Oral Troche | A solid preparation containing one or more medicaments, usually in a flavored, sweetened base which is intended to dissolve or disintegrate slowly in the mouth.
6 | SLTAB | Sublingual Tablet
5 | VAGTAB | Vaginal Tablet
3 | POWD | Powder | An intimate mixture of dry, finely divided drugs and/or chemicals that may be intended for internal or external use.
4 | TOPPWD | Topical Powder
5 | RECPWD | Rectal Powder
5 | VAGPWD | Vaginal Powder
3 | SUPP | Suppository | A solid body of various weights and shapes, adapted for introduction into the rectal, vaginal, or urethral orifice of the human body; they usually melt, soften, or dissolve at body temperature.
4 | RECSUPP | Rectal Suppository
4 | URETHSUPP | Urethral suppository
4 | VAGSUPP | Vaginal Suppository
3 | SWAB | Swab | A wad of absorbent material usually wound around one end of a small stick and used for applying medication or for removing material from an area.
4 | MEDSWAB | Medicated swab
3 | WAFER | Wafer | A thin slice of material containing a medicinal agent.

4.3.2.88 HL7 v3 Code System ParticipationFunction

URL: https://hl7.org/fhir/STU3/v3/ParticipationFunction/cs.html

This page is part of the FHIR Specification (v3.0.2: STU 3). The current version which supercedes this version is 4.0.1. For a full list of available versions, see the Directory of published versions

Vocabulary Work Group | Maturity Level: N/A | External | Use Context: Any

This code system (http://hl7.org/fhir/v3/ParticipationFunction) is defined as part of HL7 v3.

Summary

Defining URL: | http://hl7.org/fhir/v3/ParticipationFunction
Name: | v3 Code System ParticipationFunction
Definition: | This code is used to specify the exact function an actor had in a service in all necessary detail. This domain may include local extensions (CWE).
OID: | 2.16.840.1.113883.5.88 (for OID based terminology systems)
Source Resource | XML / JSON

This Code system is used in the following value sets:

* v3 Code System ParticipationFunction (This code is used to specify the exact function an actor had in a service in all necessary detail. This domain may include local extensions (CWE).)

4.3.2.88.1 Code System Content

Release Date: 2016-11-11

Level | Code | Display | Definition
1 | (_AuthorizedParticipationFunction) Abstract | | This code is used to specify the exact function an actor is authorized to have in a service in all necessary detail.
2 | (_AuthorizedReceiverParticipationFunction) Abstract | | This code is used to specify the exact function an actor is authorized to have as a receiver of information that is the subject of a consent directive or consent override.
3 | AUCG | caregiver information receiver | Description:Caregiver authorized to receive patient health information.
3 | AULR | legitimate relationship information receiver | Description:Provider with legitimate relationship authorized to receive patient health information.
3 | AUTM | care team information receiver | Description:Member of care team authorized to receive patient health information.
3 | AUWA | work area information receiver | Description:Entities within specified work area authorized to receive patient health information.
2 | (_ConsenterParticipationFunction) Abstract | | This code is used to specify the exact function an actor is authorized to have in authoring a consent directive.
3 | GRDCON | legal guardian consent author | Description:Legal guardian of the subject of consent authorized to author a consent directive for the subject of consent.
3 | POACON | healthcare power of attorney consent author | Description:Person authorized with healthcare power of attorney to author a consent directive for the subject of consent.
3 | PRCON | personal representative consent author | Description:Personal representative of the subject of consent authorized to author a consent directive for the subject of consent.
3 | PROMSK | authorized provider masking author | Definition:Provider authorized to mask information to protect the patient, a third party, or to ensure that the provider has consulted with the patient prior to release of this information.
3 | SUBCON | subject of consent author | Description:Subject of consent authorized to author a consent directive.
2 | (_OverriderParticipationFunction) Abstract | | This code is used to specify the exact function an actor is authorized to have in authoring a consent override.
3 | AUCOV | consent overrider | Description:Entity authorized to override a consent directive.
3 | AUEMROV | emergency overrider | Description:Entity authorized to override a consent directive or privacy policy in an emergency.
1 | (_CoverageParticipationFunction) Abstract | | Definition: Set of codes indicating the manner in which sponsors, underwriters, and payers participate in a policy or program.

2 | (_PayorParticipationFunction) Abstract | | Definition: Set of codes indicating the manner in which payors participate in a policy or program.</
3 | CLMADJ | claims adjudication | Definition: Manages all operations required to adjudicate fee for service claims or managed care encounter reports.
3 | ENROLL | enrollment broker | Definition: Managing the enrollment of covered parties.
3 | FFSMGT | ffs management | Definition: Managing all operations required to administer a fee for service or indemnity health plan including enrolling covered parties and providing customer service, provider contracting, claims payment, care management and utilization review.
3 | MCMGT | managed care management | Definition: Managing all operations required to administer a managed care plan including enrolling covered parties and providing customer service,, provider contracting, claims payment, care management and utilization review.
3 | PROVMGT | provider management | Definition: Managing provider contracting, provider services, credentialing, profiling, performance measures, and ensuring network adequacy.
3 | UMGT | utilization management | Definition: Managing utilization of services by ensuring that providers adhere to, e.g., payeraTMs clinical protocols for medical appropriateness and standards of medical necessity. May include management of authorizations for services and referrals.
2 | (_SponsorParticipationFunction) Abstract | | Definition: Set of codes indicating the manner in which sponsors participate in a policy or program. NOTE: use only when the Sponsor is not further specified with a SponsorRoleType as being either a fully insured sponsor or a self insured sponsor.
3 | FULINRD | fully insured | Definition: Responsibility taken by a sponsor to contract with one or more underwriters for the assumption of full responsibility for the risk and administration of a policy or program.
3 | SELFINRD | self insured | Definition: Responsibility taken by a sponsor to organize the underwriting of risk and administration of a policy or program.
2 | (_UnderwriterParticipationFunction) Abstract | | Definition: Set of codes indicating the manner in which underwriters participate in a policy or program.
3 | PAYORCNTR | payor contracting | Definition: Contracting for the provision and administration of health services to payors while retaining the risk for coverage. Contracting may be for all provision and administration; or for provision of certain types of services; for provision of services by region; and by types of administration, e.g., claims adjudication, enrollment, provider management, and utilization management. Typically done by underwriters for sponsors who need coverage provided to covered parties in multiple regions. The underwriter may act as the payor in some, but not all of the regions in which coverage is provided.
3 | REINS | reinsures | Definition: Underwriting reinsurance for another underwriter for the policy or program.
3 | RETROCES | retrocessionaires | Definition: Underwriting reinsurance for another reinsurer.
3 | SUBCTRT | subcontracting risk | Definition: Delegating risk for a policy or program to one or more subcontracting underwriters, e.g., a major health insurer may delegate risk for provision of coverage under a national health plan to other underwriters by region .
3 | UNDERWRTNG | underwriting | Definition: Provision of underwriting analysis for another underwriter without assumption of risk.
1 | ADMPHYS | admitting physician | A physician who admitted a patient to a hospital or other care unit that is the context of this service.
1 | ANEST | anesthesist | In a typical anesthesia setting an anesthesiologist or anesthesia resident in charge of the anesthesia and life support, but only a witness to the surgical procedure itself. To clarify responsibilities anesthesia should always be represented as a separate service related to the surgery.
1 | ANRS | anesthesia nurse | In a typical anesthesia setting the nurse principally assisting the anesthesiologist during the critical periods.
1 | ASSEMBLER | assembly software | A device that operates independently of an author on custodian's algorithms for data extraction of existing information for purpose of generating a new artifact. UsageConstraint: ASSEMBLER ParticipationFunction should be used with DEV (device) ParticipationType.
1 | ATTPHYS | attending physician | A physician who is primarily responsible for a patient during the hospitalization, which is the context of the service.
1 | COMPOSER | composer software | A device used by an author to record new information, which may also be used by the author to select existing information for aggregation with newly recorded information for the purpose of generating a new artifact. UsageConstraint: COMPOSER ParticipationFunction should be used with DEV (device) ParticipationType. Usage Note: This code will enable implementers to more specifically represent the manner in which a Device participated in and facilitated the generation of a CDA Clinical Document or a CDA Entry by the responsible Author, which is comprised of the Author's newly entered content, and may include the pre-existing content selected by the Author, for the purpose of establishing the provenance and accountability for these acts.
1 | DISPHYS | discharging physician | A physician who discharged a patient from a hospital or other care unit that is the context of this service.
1 | FASST | first assistant surgeon | In a typical surgery setting the assistant facing the primary surgeon. The first assistant performs parts of the operation and assists in others (e.g., incision, approach, electrocoutering, ligatures, sutures).
1 | MDWF | midwife | A person (usually female) helping a woman deliver a baby. Responsibilities vary locally, ranging from a mere optional assistant to a full required participant, responsible for (normal) births and pre- and post-natal care for both mother and baby.
1 | NASST | nurse assistant | In a typical surgery setting the non-sterile nurse handles material supply from the stock, forwards specimen to pathology, and helps with other non-sterile tasks (e.g., phone calls, etc.).
1 | PCP | primary care physician | The healthcare provider that holds primary responsibility for the overall care of a patient.
1 | PRISURG | primary surgeon | In a typical surgery setting the primary performing surgeon.
1 | REVIEWER | reviewer | A verifier who is accountable for reviewing and asserting that the verification of an Act complies with jurisdictional or organizational policy. UsageConstraint: UsageConstraint: Specifies the exact function that an actor is authorized to have as a verifier of an Act. Connotes that a specialized verifier asserts compliance for veracity of the review per jurisdictional or organizational policy. E.g., The Provider who takes responsibility for authenticity of a record submitted to a payer. REVIEW ParticipationFunction should be used with VFR (verifier)
1 | RNDPHYS | rounding physician | A physician who made rounds on a patient in a hospital or other care center.
1 | SASST | second assistant surgeon | In a typical surgery setting the assistant who primarily holds the hooks.
1 | SNRS | scrub nurse | In a typical surgery setting the nurse in charge of the instrumentation.
1 | TASST | third assistant | In a typical surgery setting there is rarely a third assistant (e.g., in some Hip operations the third assistant postures the affected leg).

4.3.2.89 HL7 v3 Code System ParticipationSignature

URL: https://hl7.org/fhir/STU3/v3/ParticipationSignature/cs.html

This page is part of the FHIR Specification (v3.0.2: STU 3). The current version which supercedes this version is 4.0.1. For a full list of available versions, see the Directory of published versions

Vocabulary Work Group | Maturity Level: N/A | External | Use Context: Any

This code system (http://hl7.org/fhir/v3/ParticipationSignature) is defined as part of HL7 v3.

Summary

Defining URL: | http://hl7.org/fhir/v3/ParticipationSignature
Name: | v3 Code System ParticipationSignature
Definition: | A set of codes specifying whether and how the participant has attested his participation through a signature and or whether such a signature is needed. Examples: A surgical Procedure act object (representing a procedure report) requires a signature of the performing and responsible surgeon, and possibly other participants. (See also: Participation.signatureText.)
OID: | 2.16.840.1.113883.5.89 (for OID based terminology systems)
Source Resource | XML / JSON

This Code system is used in the following value sets:

* v3 Code System ParticipationSignature (A set of codes specifying whether and how the participant has attested his participation through a signature and or whether such a signature is needed. Examples: A surgical Procedure act object (representing a procedure report) requires a signature of the performing and responsible surgeon, and possibly other participants. (See also: Participation.signatureText.))

4.3.2.89.1 Code System Content

Release Date: 2016-11-11

Level | Code | Display | Definition
1 | I | intended | The particpant intends to provide a signature.
1 | S | signed | Signature has been affixed, either written on file, or electronic (incl. digital) signature in Participation.signatureText.
1 | X | required | A signature for the service is required of this actor.

4.3.2.90 HL7 v3 Code System ParticipationType

URL: https://hl7.org/fhir/STU3/v3/ParticipationType/cs.html
This page is part of the FHIR Specification (v3.0.2: STU 3). The current version which supercedes this version is 4.0.1. For a full list of available versions, see the Directory of published versions

Vocabulary Work Group | Maturity Level: N/A | External | Use Context: Any

This code system (http://hl7.org/fhir/v3/ParticipationType) is defined as part of HL7 v3.

Summary

Defining URL: | http://hl7.org/fhir/v3/ParticipationType
Name: | v3 Code System ParticipationType
Definition: | **** MISSING DEFINITIONS ****
OID: | 2.16.840.1.113883.5.90 (for OID based terminology systems)
Source Resource | XML / JSON

This Code system is used in the following value sets:

* ParticipationTargetDirect (Target that is substantially present in the service and which is directly affected by the service action (includes consumed material, devices, etc.).)

* ParticipationTargetSubject (The principle target that the service acts on. E.g. the patient in physical examination, a specimen in a lab observation. May also be a patient's family member (teaching) or a device or room (cleaning, disinfecting, housekeeping). Note: not all direct targets are subjects, consumables, and devices used as tools for a service are not subjects. However, a device may be a subject of a maintenance service.)

* ParticipationPhysicalPerformer (A person who actually and principally carries out the action. Need not be the principal responsible actor, e.g. a surgery resident operating under supervision of attending surgeon, and may be the patient in self-care, e.g. fingerstick blood sugar. The traditional order filler is a performer. This information should accompany every service event.)

* Focal Subject Codes (Example VS composed from SNOMED CT and HL7 v3 codes for observation targets: donor, fetus, spouse. As use cases are discovered more values may be added.)

* ParticipationInformationTranscriber (An entity entering the data into the originating system. The data entry entity is collected optionally for internal quality control purposes. This includes the transcriptionist for dictated text transcribed into electronic form.)

* ParticipationInformationGenerator (Parties that may or should contribute or have contributed information to the Act. Such information includes information leading to the decision to perform the Act and how to perform the Act (e.g., consultant), information that the Act itself seeks to reveal (e.g., informant of clinical history), or information about what Act was performed (e.g., informant witness).)

* ParticipationVerifier (A person who verifies the correctness and appropriateness of the service (plan, order, event, etc.) and hence takes on accountability.)

* ParticipantType (This value set defines a set of codes that can be used to indicate how an individual participates in an encounter.)

* ParticipationIndirectTarget (Target that is not substantially present in the act and which is not directly affected by the act, but which will be a focus of the record or documentation of the act.)

* v3 Code System ParticipationType (**** MISSING DEFINITIONS ****)

* ParticipationTargetLocation (The facility where the service is done. May be a static building (or room therein) or a moving location (e.g., ambulance, helicopter, aircraft, train, truck, ship, etc.))

4.3.2.90.1 Code System Content

Release Date: 2016-11-11

Level | Code | Display | Definition

1 | PART | Participation | Indicates that the target of the participation is involved in some manner in the act, but does not qualify how.

2 | (_ParticipationAncillary) Abstract | | Participations related, but not primary to an act. The Referring, Admitting, and Discharging practitioners must be the same person as those authoring the ControlAct event for their respective trigger events.

3 | ADM | admitter | The practitioner who is responsible for admitting a patient to a patient encounter.

3 | ATND | attender | The practitioner that has responsibility for overseeing a patient's care during a patient encounter.

3 | CALLBCK | callback contact | A person or organization who should be contacted for follow-up questions about the act in place of the author.

3 | CON | consultant | An advisor participating in the service by performing evaluations and making recommendations.

3 | DIS | discharger | The practitioner who is responsible for the discharge of a patient from a patient encounter.

3 | ESC | escort | Only with Transportation services. A person who escorts the patient.

3 | REF | referrer | A person having referred the subject of the service to the performer (referring physician). Typically, a referring physician will receive a report.

2 | (_ParticipationInformationGenerator) Abstract | | Parties that may or should contribute or have contributed information to the Act. Such information includes information leading to the decision to perform the Act and how to perform the Act (e.g., consultant), information that the Act itself seeks to reveal (e.g., informant of clinical history), or information about what Act was performed (e.g., informant witness).

3 | AUT | author (originator) | Definition: A party that originates the Act and therefore has responsibility for the information given in the Act and ownership of this Act. Example: the report writer, the person writing the act definition, the guideline author, the placer of an order, the EKG cart (device) creating a report etc. Every Act should have an author. Authorship is regardless of mood always actual authorship. Examples of such policies might include: The author and anyone they explicitly delegate may update the report; All administrators within the same clinic may cancel and reschedule appointments created by other administrators within that clinic; A party that is neither an author nor a party who is extended authorship maintenance rights by policy, may only amend, reverse, override, replace, or follow up in other ways on this Act, whereby the Act remains intact and is linked to another Act authored by that other party.

3 | INF | informant | A source of reported information (e.g., a next of kin who answers questions about the patient's history). For history questions, the patient is logically an informant, yet the informant of history questions is implicitly the subject.

3 | TRANS | Transcriber | An entity entering the data into the originating system. The data entry entity is collected optionally for internal quality control purposes. This includes the transcriptionist for dictated text transcribed into electronic form.

4 | ENT | data entry person | A person entering the data into the originating system. The data entry person is collected optionally for internal quality control purposes. This includes the transcriptionist for dictated text.

3 | WIT | witness | Only with service events. A person witnessing the action happening without doing anything. A witness is not necessarily aware, much less approves of anything stated in the service event. Example for a witness is students watching an operation or an advanced directive witness.

2 | CST | custodian | An entity (person, organization or device) that is in charge of maintaining the information of this act (e.g., who maintains the report or the master service catalog item, etc.).

2 | DIR | direct target | Target participant that is substantially present in the act and which is directly involved in the action (includes consumed material, devices, etc.).

3 | ALY | analyte | The target of an Observation action. Links an observation to a Role whose player is the substance or most specific component entity (material, micro-organism, etc.) being measured within the subject. Examples: A "plasma porcelain substance concentration" has analyte a Role with player substance Entity "porcelain". UsageNotes: The Role that this participation connects to may be any Role whose player is that substance measured. Very often, the scoper may indicate the system in which the component is being measured. E.g., for "plasma porcelain" the scoper could be "Plasma".

3 | BBY | baby | In an obstetric service, the baby.

3 | CAT | catalyst | The catalyst of a chemical reaction, such as an enzyme or a platinum surface. In biochemical reactions, connects the enzyme with the molecular interaction

3 | CSM | consumable | Participant material that is taken up, diminished, altered, or disappears in the act.

4 | TPA | therapeutic agent | Something incorporated in the subject of a therapy service to achieve a physiologic effect (e.g., heal, relieve, provoke a condition, etc.) on the subject. In an administration service the therapeutic agent is a consumable, in a preparation or dispense service, it is a product. Thus, consumable or product must be specified in accordance with the kind of service.

3 | DEV | device | Participant used in performing the act without being substantially affected by the act (i.e. durable or inert with respect to that particular service). Examples: monitoring equipment, tools, but also access/drainage lines, prostheses, pace maker, etc.

4 | NRD | non-reuseable device | A device that changes ownership due to the service, e.g., a pacemaker, a prosthesis, an insulin injection equipment (pen), etc. Such material may need to be restocked after he service.

4 | RDV | reusable device | A device that does not change ownership due to the service, i.e., a surgical instrument or tool or an endoscope. The distinction between reuseable and non-reuseable must be made in order to know whether material must be re-stocked.

3 | DON | donor | In some organ transplantation services and rarely in transfusion services a donor will be a target participant in the service. However, in most cases transplantation is decomposed in three services: explantation, transport, and implantation. The identity of the donor (recipient) is often irrelevant for the explantation (implantation) service.

3 | EXPAGNT | ExposureAgent | Description: The entity playing the associated role is the physical (including energy), chemical or biological substance that is participating in the exposure. For example in communicable diseases, the associated playing entity is the disease causing pathogen.

3 | EXPART | ExposureParticipation | Description:Direct participation in an exposure act where it is unknown that the participant is the source or subject of the exposure. If the participant is known to be the contact of an exposure then the SBJ participation type should be used. If the participant is known to be the source then the EXSRC participation type should be used.

4 | EXPTRGT | ExposureTarget | Description: The entity playing the associated role is the target (contact) of exposure.

4 | EXSRC | ExposureSource | Description:The entity playing the associated role is the source of exposure.

3 | PRD | product | Participant material that is brought forth (produced) in the act (e.g., specimen in a specimen collection, access or drainage in a placement service, medication package in a dispense service). It does not matter whether the material produced had existence prior to the service, or whether it is created in the service (e.g., in supply services the product is taken from a stock).

3 | SBJ | subject | The principle target on which the action happens. Examples: The patient in physical examination, a specimen in a lab observation. May also be a patient's family member (teaching) or a device or room (cleaning, disinfecting, housekeeping). UsageNotes: Not all direct targets are subjects. Consumables and devices used as tools for an act are not subjects. However, a device may be a subject of a maintenance action.

4 | SPC | specimen | The subject of non-clinical (e.g. laboratory) observation services is a specimen.

2 | IND | indirect target | Target that is not substantially present in the act and which is not directly affected by the act, but which will be a focus of the record or documentation of the act.

3 | BEN | beneficiary | Target on behalf of whom the service happens, but that is not necessarily present in the service. Can occur together with direct target to indicate that a target is both, as in the case where the patient is the indirect beneficiary of a service rendered to a family member, e.g. counseling or given home care instructions. This concept includes a participant, such as a covered party, who derives benefits from a service act covered by a coverage act. Note that the semantic role of the intended recipient who benefits from the happening denoted by the verb in the clause. Thus, a patient who has no coverage under a policy or program may be a beneficiary of a health service while not being the beneficiary of coverage for that service.

3 | CAGNT | causative agent | Definition: A factor, such as a microorganism, chemical substance, or form of radiation, whose presence, excessive presence, or (in deficiency diseases) relative absence is essential, in whole or in part, for the occurrence of a condition. Constraint: The use of this participation is limited to observations.

3 | COV | coverage target | The target participation for an individual in a health care coverage act in which the target role is either the policy holder of the coverage, or a covered party under the coverage.

3 | GUAR | guarantor party | The target person or organization contractually recognized by the issuer as a participant who has assumed fiscal responsibility for another personaTMs financial obligations by guaranteeing to pay for amounts owed to a particular account Example:The subscriber of the patientaTMs health insurance policy signs a contract with the provider to be fiscally responsible for the patient billing account balance amount owed.

3 | HLD | holder | Participant who posses an instrument such as a financial contract (insurance policy) usually based on some agreement with the author.

3 | RCT | record target | The record target indicates whose medical record holds the documentation of this act. This is especially important when the subject of a service is not the patient himself.

3 | RCV | receiver | The person (or organization) who receives the product of an Act.

2 | IRCP | information recipient | A party, who may or should receive or who has recieved the Act or subsequent or derivative information of that Act. Information recipient is inert, i.e., independent of mood." Rationale: this is a generalization of a too diverse family that the definition can't be any more specific, and the concept is abstract so one of the specializations should be used.

3 | NOT | ugent notification contact | An information recipient to notify for urgent matters about this Act. (e.g., in a laboratory order, critical results are being called by phone right away, this is the contact to call; or for an inpatient encounter, a next of kin to notify when the patient becomes critically ill).

3 | PRCP | primary information recipient | Information recipient to whom an act statement is primarily directed. E.g., a primary care provider receiving a discharge letter from a hospitalist, a health department receiving information on a suspected case of infectious disease. Multiple of these participations may exist on the same act without requiring that recipients be ranked as primary vs. secondary.

3 | REFB | Referred By | A participant (e.g. provider) who has referred the subject of an act (e.g. patient). Typically, a referred by participant will provide a report (e.g. referral).

3 | REFT | Referred to | The person who receives the patient

3 | TRC | tracker | A secondary information recipient, who receives copies (e.g., a primary care provider receiving copies of results as ordered by specialist).

2 | LOC | location | The facility where the service is done. May be a static building (or room therein) or a moving location (e.g., ambulance, helicopter, aircraft, train, truck, ship, etc.)

3 | DST | destination | The destination for services. May be a static building (or room therein) or a movable facility (e.g., ship).

3 | ELOC | entry location | A location where data about an Act was entered.

3 | ORG | origin | The location of origin for services. May be a static building (or room therein) or a movable facility (e.g., ship).

3 | RML | remote | Some services take place at multiple concurrent locations (e.g., telemedicine, telephone consultation). The location where the principal performing actor is located is taken as the primary location (LOC) while the other location(s) are considered "remote."

3 | VIA | via | For services, an intermediate location that specifies a path between origin an destination.

2 | PRF | performer | Definition: A person, non-person living subject, organization or device that who actually and principally carries out the action. Device should only be assigned as a performer in circumstances where the device is performing independent of human intervention. Need not be the principal responsible actor. Exampe: A surgery resident operating under supervision of attending surgeon, a search and rescue dog locating survivors, an electronic laboratory analyzer or the laboratory discipline requested to perform a laboratory test. The performer may also be the patient in self-care, e.g. fingerstick blood sugar. The traditional order filler is a performer. This information should accompany every service event. Note: that existing HL7 designs assign an organization as the playing entity of the Role that is the performer. These designs should be revised in subsequent releases to make this the scooping entity for the role involved.

3 | DIST | distributor | Distributes material used in or generated during the act.

3 | PPRF | primary performer | The principal or primary performer of the act.

3 | SPRF | secondary performer | A person assisting in an act through his substantial presence and involvement This includes: assistants, technicians, associates, or whatever the job titles may be.

2 | RESP | responsible party | The person or organization that has primary responsibility for the act. The responsible party is not necessarily present in an action, but is accountable for the action through the power to delegate, and the duty to review actions with the performing actor after the fact. This responsibility may be ethical, legal, contractual, fiscal, or fiduciary in nature. Example: A person who is the head of a biochemical laboratory; a sponsor for a policy or government program.

2 | VRF | verifier | A person who verifies the correctness and appropriateness of the service (plan, order, event, etc.) and hence takes on accountability.

3 | AUTHEN | authenticator | A verifier who attests to the accuracy of an act, but who does not have privileges to legally authenticate the act. An example would be a resident physician who sees a patient and dictates a note, then later signs it. Their signature constitutes an authentication.

3 | LA | legal authenticator | A verifier who legally authenticates the accuracy of an act. An example would be a staff physician who sees a patient and dictates a note, then later signs it. Their signature constitutes a legal authentication.

4.3.2.91 HL7 v3 Code System PaymentTerms

URL: https://hl7.org/fhir/STU3/v3/PaymentTerms/cs.html

This page is part of the FHIR Specification (v3.0.2: STU 3). The current version which supercedes this version is 4.0.1. For a full list of available versions, see the Directory of published versions

Vocabulary Work Group | Maturity Level: N/A | External | Use Context: Any

This code system (http://hl7.org/fhir/v3/PaymentTerms) is defined as part of HL7 v3.

Summary

Defining URL: | http://hl7.org/fhir/v3/PaymentTerms

Name: | v3 Code System PaymentTerms

Definition: | Describes payment terms for a financial transaction, used in an invoice. This is typically expressed as a responsibility of the acceptor or payor of an invoice.
OID: | 2.16.840.1.113883.5.91 (for OID based terminology systems)
Source Resource | XML / JSON

This Code system is used in the following value sets:

* v3 Code System PaymentTerms (Describes payment terms for a financial transaction, used in an invoice. This is typically expressed as a responsibility of the acceptor or payor of an invoice.)

4.3.2.91.1 Code System Content

Release Date: 2016-11-11

Level | Code | Display | Definition
1 | COD | Cash on Delivery | Payment in full for products and/or services is required as soon as the service is performed or goods delivered.
1 | N30 | Net 30 days | Payment in full for products and/or services is required 30 days from the time the service is performed or goods delivered.
1 | N60 | Net 60 days | Payment in full for products and/or services is required 60 days from the time the service is performed or goods delivered.
1 | N90 | Net 90 days | Payment in full for products and/or services is required 90 days from the time the service is performed or goods delivered.

4.3.2.93 HL7 v3 Code System PersonDisabilityType

URL: https://hl7.org/fhir/STU3/v3/PersonDisabilityType/cs.html

This page is part of the FHIR Specification (v3.0.2: STU 3). The current version which supercedes this version is 4.0.1. For a full list of available versions, see the Directory of published versions

Vocabulary Work Group | Maturity Level: N/A | External | Use Context: Any

This code system (http://hl7.org/fhir/v3/PersonDisabilityType) is defined as part of HL7 v3.

Summary

Defining URL: | http://hl7.org/fhir/v3/PersonDisabilityType
Name: | v3 Code System PersonDisabilityType
Definition: | A code identifying a person's disability.
OID: | 2.16.840.1.113883.5.93 (for OID based terminology systems)
Source Resource | XML / JSON

This Code system is used in the following value sets:

* v3 Code System PersonDisabilityType (A code identifying a person's disability.)

4.3.2.93.1 Code System Content

Release Date: 2016-11-11

Level | Code | Display | Definition
1 | 1 | Vision impaired | Vision impaired
1 | 2 | Hearing impaired | Hearing impaired
1 | 3 | Speech impaired | Speech impaired
1 | 4 | Mentally impaired | Mentally impaired
1 | 5 | Mobility impaired
2 | CB | Requires crib | A crib is required to move the person
2 | CR | Requires crutches | Person requires crutches to ambulate
2 | G | Requires gurney | A gurney is required to move the person
2 | WC | Requires wheelchair | Person requires a wheelchair to be ambulatory
2 | WK | Requires walker | Person requires a walker to ambulate

4.3.2.100 HL7 v3 Code System ProcessingID

URL: https://hl7.org/fhir/STU3/v3/ProcessingID/cs.html

This page is part of the FHIR Specification (v3.0.2: STU 3). The current version which supercedes this version is 4.0.1. For a full list of available versions, see the Directory of published versions

Vocabulary Work Group | Maturity Level: N/A | External | Use Context: Any

This code system (http://hl7.org/fhir/v3/ProcessingID) is defined as part of HL7 v3.

Summary

Defining URL: | http://hl7.org/fhir/v3/ProcessingID
Name: | v3 Code System ProcessingID
Definition: | Codes used to specify whether a message is part of a production, training, or debugging system.
OID: | 2.16.840.1.113883.5.100 (for OID based terminology systems)
Source Resource | XML / JSON

This Code system is used in the following value sets:

* v3 Code System ProcessingID (Codes used to specify whether a message is part of a production, training, or debugging system.)

4.3.2.100.1 Code System Content

Release Date: 2016-11-11

Level	Code	Display	Definition
1	D	Debugging	Identifies debugging type of processing.
1	P	Production	Identifies production type of processing.
1	T	Training	Identifies training type of processing.

4.3.2.101 HL7 v3 Code System ProcessingMode

URL: https://hl7.org/fhir/STU3/v3/ProcessingMode/cs.html

This page is part of the FHIR Specification (v3.0.2: STU 3). The current version which supercedes this version is 4.0.1. For a full list of available versions, see the Directory of published versions

Vocabulary Work Group | Maturity Level: N/A | External | Use Context: Any

This code system (http://hl7.org/fhir/v3/ProcessingMode) is defined as part of HL7 v3.

Summary

Defining URL:	http://hl7.org/fhir/v3/ProcessingMode
Name:	v3 Code System ProcessingMode
Definition:	**** MISSING DEFINITIONS ****
OID:	2.16.840.1.113883.5.101 (for OID based terminology systems)
Source Resource	XML / JSON

This Code system is used in the following value sets:

* v3 Code System ProcessingMode (**** MISSING DEFINITIONS ****)

4.3.2.101.1 Code System Content

Release Date: 2016-11-11

Level	Code	Display	Definition
1	A	Archive	Identifies archive mode of processing.
1	I	Initial load	Identifies initial load mode of processing.
1	R	Restore from archive	Identifies restore mode of processing.
1	T	Current processing	Identifies on-line mode of processing.

4.3.2.102 HL7 v3 Code System QueryPriority

URL: https://hl7.org/fhir/STU3/v3/QueryPriority/cs.html

This page is part of the FHIR Specification (v3.0.2: STU 3). The current version which supercedes this version is 4.0.1. For a full list of available versions, see the Directory of published versions

Vocabulary Work Group | Maturity Level: N/A | External | Use Context: Any

This code system (http://hl7.org/fhir/v3/QueryPriority) is defined as part of HL7 v3.

Summary

Defining URL:	http://hl7.org/fhir/v3/QueryPriority
Name:	v3 Code System QueryPriority
Definition:	**** MISSING DEFINITIONS ****
OID:	2.16.840.1.113883.5.102 (for OID based terminology systems)
Source Resource	XML / JSON

This Code system is used in the following value sets:

* v3 Code System QueryPriority (**** MISSING DEFINITIONS ****)

4.3.2.102.1 Code System Content

Release Date: 2016-11-11

Level	Code	Display	Definition
1	D	Deferred	Query response is deferred.
1	I	Immediate	Query response is immediate.

4.3.2.103 HL7 v3 Code System QueryStatusCode

URL: https://hl7.org/fhir/STU3/v3/QueryStatusCode/cs.html

This page is part of the FHIR Specification (v3.0.2: STU 3). The current version which supercedes this version is 4.0.1. For a full list of available versions, see the Directory of published versions

Vocabulary Work Group | Maturity Level: N/A | External | Use Context: Any

This code system (http://hl7.org/fhir/v3/QueryStatusCode) is defined as part of HL7 v3.

Summary

Defining URL:	http://hl7.org/fhir/v3/QueryStatusCode
Name:	v3 Code System QueryStatusCode
Definition:	A code specifying the state of the Query.

OID: | 2.16.840.1.113883.5.103 (for OID based terminology systems)
Source Resource | XML / JSON

This Code system is used in the following value sets:

* v3 Code System QueryStatusCode (A code specifying the state of the Query.)

4.3.2.103.1 Code System Content

Release Date: 2016-11-11

Level | Code | Display | Definition
1 | aborted | aborted | Query status aborted
1 | deliveredResponse | deliveredResponse | Query Status delivered response
1 | executing | executing | Query Status executing
1 | new | new | Query Status new
1 | waitContinuedQueryResponse | waitContinuedQueryResponse | Query Status wait continued

4.3.2.104 HL7 v3 Code System Race

URL: https://hl7.org/fhir/STU3/v3/Race/cs.html

This page is part of the FHIR Specification (v3.0.2: STU 3). The current version which supercedes this version is 4.0.1. For a full list of available versions, see the Directory of published versions

Vocabulary Work Group | Maturity Level: N/A | External | Use Context: Any

This code system (http://hl7.org/fhir/v3/Race) is defined as part of HL7 v3.

Summary

Defining URL: | http://hl7.org/fhir/v3/Race
Name: | v3 Code System Race
Definition: | In the United States, federal standards for classifying data on race determine the categories used by federal agencies and exert a strong influence on categorization by state and local agencies and private sector organizations. The federal standards do not conceptually define race, and they recognize the absence of an anthropological or scientific basis for racial classification. Instead, the federal standards acknowledge that race is a social-political construct in which an individual's own identification with one more race categories is preferred to observer identification. The standards use a variety of features to define five minimum race categories. Among these features are descent from "the original peoples" of a specified region or nation. The minimum race categories are American Indian or Alaska Native, Asian, Black or African American, Native Hawaiian or Other Pacific Islander, and White. The federal standards stipulate that race data need not be limited to the five minimum categories, but any expansion must be collapsible to those categories.
OID: | 2.16.840.1.113883.5.104 (for OID based terminology systems)
Source Resource | XML / JSON

This Code system is used in the following value sets:

* v3 Code System Race (In the United States, federal standards for classifying data on race determine the categories used by federal agencies and exert a strong influence on categorization by state and local agencies and private sector organizations. The federal standards do not conceptually define race, and they recognize the absence of an anthropological or scientific basis for racial classification. Instead, the federal standards acknowledge that race is a social-political construct in which an individual's own identification with one more race categories is preferred to observer identification. The standards use a variety of features to define five minimum race categories. Among these features are descent from "the original peoples" of a specified region or nation. The minimum race categories are American Indian or Alaska Native, Asian, Black or African American, Native Hawaiian or Other Pacific Islander, and White. The federal standards stipulate that race data need not be limited to the five minimum categories, but any expansion must be collapsible to those categories.)

* v2 Race (FHIR Value set/code system definition for HL7 v2 table 0005 (Race))

4.3.2.104.1 Code System Content

Release Date: 2016-11-11

Level | Code | Display | Definition
1 | 1002-5 | American Indian or Alaska Native
2 | 1004-1 | American Indian
3 | 1006-6 | Abenaki
3 | 1008-2 | Algonquian
3 | 1010-8 | Apache
4 | 1011-6 | Chiricahua
4 | 1012-4 | Fort Sill Apache
4 | 1013-2 | Jicarilla Apache
4 | 1014-0 | Lipan Apache
4 | 1015-7 | Mescalero Apache
4 | 1016-5 | Oklahoma Apache
4 | 1017-3 | Payson Apache
4 | 1018-1 | San Carlos Apache
4 | 1019-9 | White Mountain Apache
3 | 1021-5 | Arapaho
4 | 1022-3 | Northern Arapaho
4 | 1023-1 | Southern Arapaho

4 | 1024-9 | Wind River Arapaho
3 | 1026-4 | Arikara
3 | 1028-0 | Assiniboine
3 | 1030-6 | Assiniboine Sioux
4 | 1031-4 | Fort Peck Assiniboine Sioux
3 | 1033-0 | Bannock
3 | 1035-5 | Blackfeet
3 | 1037-1 | Brotherton
3 | 1039-7 | Burt Lake Band
3 | 1041-3 | Caddo
4 | 1042-1 | Oklahoma Cado
3 | 1044-7 | Cahuilla
4 | 1045-4 | Agua Caliente Cahuilla
4 | 1046-2 | Augustine
4 | 1047-0 | Cabazon
4 | 1048-8 | Los Coyotes
4 | 1049-6 | Morongo
4 | 1050-4 | Santa Rosa Cahuilla
4 | 1051-2 | Torres-Martinez
3 | 1053-8 | California Tribes
4 | 1054-6 | Cahto
4 | 1055-3 | Chimariko
4 | 1056-1 | Coast Miwok
4 | 1057-9 | Digger
4 | 1058-7 | Kawaiisu
4 | 1059-5 | Kern River
4 | 1060-3 | Mattole
4 | 1061-1 | Red Wood
4 | 1062-9 | Santa Rosa
4 | 1063-7 | Takelma
4 | 1064-5 | Wappo
4 | 1065-2 | Yana
4 | 1066-0 | Yuki
3 | 1068-6 | Canadian and Latin American Indian
4 | 1069-4 | Canadian Indian
4 | 1070-2 | Central American Indian
4 | 1071-0 | French American Indian
4 | 1072-8 | Mexican American Indian
4 | 1073-6 | South American Indian
3 | 1074-4 | Spanish American Indian
3 | 1076-9 | Catawba
4 | 1741-8 | Alatna
4 | 1742-6 | Alexander
4 | 1743-4 | Allakaket
4 | 1744-2 | Alanvik
4 | 1745-9 | Anvik
4 | 1746-7 | Arctic
4 | 1747-5 | Beaver
4 | 1748-3 | Birch Creek
4 | 1749-1 | Cantwell
4 | 1750-9 | Chalkyitsik
4 | 1751-7 | Chickaloon
4 | 1752-5 | Chistochina
4 | 1753-3 | Chitina
4 | 1754-1 | Circle
4 | 1755-8 | Cook Inlet
4 | 1756-6 | Copper Center
4 | 1757-4 | Copper River
4 | 1758-2 | Dot Lake
4 | 1759-0 | Doyon
4 | 1760-8 | Eagle
4 | 1761-6 | Eklutna
4 | 1762-4 | Evansville
4 | 1763-2 | Fort Yukon
4 | 1764-0 | Gakona
4 | 1765-7 | Galena
4 | 1766-5 | Grayling
4 | 1767-3 | Gulkana
4 | 1768-1 | Healy Lake
4 | 1769-9 | Holy Cross
4 | 1770-7 | Hughes
4 | 1771-5 | Huslia

4 | 1772-3 | Iliamna
4 | 1773-1 | Kaltag
4 | 1774-9 | Kluti Kaah
4 | 1775-6 | Knik
4 | 1776-4 | Koyukuk
4 | 1777-2 | Lake Minchumina
4 | 1778-0 | Lime
4 | 1779-8 | Mcgrath
4 | 1780-6 | Manley Hot Springs
4 | 1781-4 | Mentasta Lake
4 | 1782-2 | Minto
4 | 1783-0 | Nenana
4 | 1784-8 | Nikolai
4 | 1785-5 | Ninilchik
4 | 1786-3 | Nondalton
4 | 1787-1 | Northway
4 | 1788-9 | Nulato
4 | 1789-7 | Pedro Bay
4 | 1790-5 | Rampart
4 | 1791-3 | Ruby
4 | 1792-1 | Salamatof
4 | 1793-9 | Seldovia
4 | 1794-7 | Slana
4 | 1795-4 | Shageluk
4 | 1796-2 | Stevens
4 | 1797-0 | Stony River
4 | 1798-8 | Takotna
4 | 1799-6 | Tanacross
4 | 1800-2 | Tanaina
4 | 1801-0 | Tanana
4 | 1802-8 | Tanana Chiefs
4 | 1803-6 | Tazlina
4 | 1804-4 | Telida
4 | 1805-1 | Tetlin
4 | 1806-9 | Tok
4 | 1807-7 | Tyonek
4 | 1808-5 | Venetie
4 | 1809-3 | Wiseman
3 | 1078-5 | Cayuse
3 | 1080-1 | Chehalis
3 | 1082-7 | Chemakuan
4 | 1083-5 | Hoh
4 | 1084-3 | Quileute
3 | 1086-8 | Chemehuevi
3 | 1088-4 | Cherokee
4 | 1089-2 | Cherokee Alabama
4 | 1090-0 | Cherokees of Northeast Alabama
4 | 1091-8 | Cherokees of Southeast Alabama
4 | 1092-6 | Eastern Cherokee
4 | 1093-4 | Echota Cherokee
4 | 1094-2 | Etowah Cherokee
4 | 1095-9 | Northern Cherokee
4 | 1096-7 | Tuscola
4 | 1097-5 | United Keetowah Band of Cherokee
4 | 1098-3 | Western Cherokee
3 | 1100-7 | Cherokee Shawnee
3 | 1102-3 | Cheyenne
4 | 1103-1 | Northern Cheyenne
4 | 1104-9 | Southern Cheyenne
3 | 1106-4 | Cheyenne-Arapaho
3 | 1108-0 | Chickahominy
4 | 1109-8 | Eastern Chickahominy
4 | 1110-6 | Western Chickahominy
3 | 1112-2 | Chickasaw
3 | 1114-8 | Chinook
4 | 1115-5 | Clatsop
4 | 1116-3 | Columbia River Chinook
4 | 1117-1 | Kathlamet
4 | 1118-9 | Upper Chinook
4 | 1119-7 | Wakiakum Chinook
4 | 1120-5 | Willapa Chinook
4 | 1121-3 | Wishram

3 | 1123-9 | Chippewa
4 | 1124-7 | Bad River
4 | 1125-4 | Bay Mills Chippewa
4 | 1126-2 | Bois Forte
4 | 1127-0 | Burt Lake Chippewa
4 | 1128-8 | Fond du Lac
4 | 1129-6 | Grand Portage
4 | 1130-4 | Grand Traverse Band of Ottawa-Chippewa
4 | 1131-2 | Keweenaw
4 | 1132-0 | Lac Courte Oreilles
4 | 1133-8 | Lac du Flambeau
4 | 1134-6 | Lac Vieux Desert Chippewa
4 | 1135-3 | Lake Superior
4 | 1136-1 | Leech Lake
4 | 1137-9 | Little Shell Chippewa
4 | 1138-7 | Mille Lacs
4 | 1139-5 | Minnesota Chippewa
4 | 1140-3 | Ontonagon
4 | 1141-1 | Red Cliff Chippewa
4 | 1142-9 | Red Lake Chippewa
4 | 1143-7 | Saginaw Chippewa
4 | 1144-5 | St. Croix Chippewa
4 | 1145-2 | Sault Ste. Marie Chippewa
4 | 1146-0 | Sokoagon Chippewa
4 | 1147-8 | Turtle Mountain
4 | 1148-6 | White Earth
3 | 1150-2 | Chippewa Cree
4 | 1151-0 | Rocky Boy's Chippewa Cree
3 | 1153-6 | Chitimacha
3 | 1155-1 | Choctaw
4 | 1156-9 | Clifton Choctaw
4 | 1157-7 | Jena Choctaw
4 | 1158-5 | Mississippi Choctaw
4 | 1159-3 | Mowa Band of Choctaw
4 | 1160-1 | Oklahoma Choctaw
3 | 1162-7 | Chumash
4 | 1163-5 | Santa Ynez
3 | 1165-0 | Clear Lake
3 | 1167-6 | Coeur D'Alene
3 | 1169-2 | Coharie
3 | 1171-8 | Colorado River
3 | 1173-4 | Colville
3 | 1175-9 | Comanche
4 | 1176-7 | Oklahoma Comanche
3 | 1178-3 | Coos, Lower Umpqua, Siuslaw
3 | 1180-9 | Coos
3 | 1182-5 | Coquilles
3 | 1184-1 | Costanoan
3 | 1186-6 | Coushatta
4 | 1187-4 | Alabama Coushatta
3 | 1189-0 | Cowlitz
3 | 1191-6 | Cree
3 | 1193-2 | Creek
4 | 1194-0 | Alabama Creek
4 | 1195-7 | Alabama Quassarte
4 | 1196-5 | Eastern Creek
4 | 1197-3 | Eastern Muscogee
4 | 1198-1 | Kialegee
4 | 1199-9 | Lower Muscogee
4 | 1200-5 | Machis Lower Creek Indian
4 | 1201-3 | Poarch Band
4 | 1202-1 | Principal Creek Indian Nation
4 | 1203-9 | Star Clan of Muscogee Creeks
4 | 1204-7 | Thlopthlocco
4 | 1205-4 | Tuckabachee
3 | 1207-0 | Croatan
3 | 1209-6 | Crow
3 | 1211-2 | Cupeno
4 | 1212-0 | Agua Caliente
3 | 1214-6 | Delaware
4 | 1215-3 | Eastern Delaware
4 | 1216-1 | Lenni-Lenape

4 | 1217-9 | Munsee
4 | 1218-7 | Oklahoma Delaware
4 | 1219-5 | Rampough Mountain
4 | 1220-3 | Sand Hill
3 | 1222-9 | Diegueno
4 | 1223-7 | Campo
4 | 1224-5 | Capitan Grande
4 | 1225-2 | Cuyapaipe
4 | 1226-0 | La Posta
4 | 1227-8 | Manzanita
4 | 1228-6 | Mesa Grande
4 | 1229-4 | San Pasqual
4 | 1230-2 | Santa Ysabel
4 | 1231-0 | Sycuan
3 | 1233-6 | Eastern Tribes
4 | 1234-4 | Attacapa
4 | 1235-1 | Biloxi
4 | 1236-9 | Georgetown
4 | 1237-7 | Moor
4 | 1238-5 | Nansemond
4 | 1239-3 | Natchez
4 | 1240-1 | Nausu Waiwash
4 | 1241-9 | Nipmuc
4 | 1242-7 | Paugussett
4 | 1243-5 | Pocomoke Acohonock
4 | 1244-3 | Southeastern Indians
4 | 1245-0 | Susquehanock
4 | 1246-8 | Tunica Biloxi
4 | 1247-6 | Waccamaw-Siousan
4 | 1248-4 | Wicomico
3 | 1250-0 | Esselen
3 | 1252-6 | Fort Belknap
3 | 1254-2 | Fort Berthold
3 | 1256-7 | Fort Mcdowell
3 | 1258-3 | Fort Hall
3 | 1260-9 | Gabrieleno
3 | 1262-5 | Grand Ronde
3 | 1264-1 | Gros Ventres
4 | 1265-8 | Atsina
3 | 1267-4 | Haliwa
3 | 1269-0 | Hidatsa
3 | 1271-6 | Hoopa
4 | 1272-4 | Trinity
4 | 1273-2 | Whilkut
3 | 1275-7 | Hoopa Extension
3 | 1277-3 | Houma
3 | 1279-9 | Inaja-Cosmit
3 | 1281-5 | Iowa
4 | 1282-3 | Iowa of Kansas-Nebraska
4 | 1283-1 | Iowa of Oklahoma
3 | 1285-6 | Iroquois
4 | 1286-4 | Cayuga
4 | 1287-2 | Mohawk
4 | 1288-0 | Oneida
4 | 1289-8 | Onondaga
4 | 1290-6 | Seneca
4 | 1291-4 | Seneca Nation
4 | 1292-2 | Seneca-Cayuga
4 | 1293-0 | Tonawanda Seneca
4 | 1294-8 | Tuscarora
4 | 1295-5 | Wyandotte
3 | 1297-1 | Juaneno
3 | 1299-7 | Kalispel
3 | 1301-1 | Karuk
3 | 1303-7 | Kaw
3 | 1305-2 | Kickapoo
4 | 1306-0 | Oklahoma Kickapoo
4 | 1307-8 | Texas Kickapoo
3 | 1309-4 | Kiowa
4 | 1310-2 | Oklahoma Kiowa
3 | 1312-8 | Klallam
4 | 1313-6 | Jamestown

4 | 1314-4 | Lower Elwha
4 | 1315-1 | Port Gamble Klallam
3 | 1317-7 | Klamath
3 | 1319-3 | Konkow
3 | 1321-9 | Kootenai
3 | 1323-5 | Lassik
3 | 1325-0 | Long Island
4 | 1326-8 | Matinecock
4 | 1327-6 | Montauk
4 | 1328-4 | Poospatuck
4 | 1329-2 | Setauket
3 | 1331-8 | Luiseno
4 | 1332-6 | La Jolla
4 | 1333-4 | Pala
4 | 1334-2 | Pauma
4 | 1335-9 | Pechanga
4 | 1336-7 | Soboba
4 | 1337-5 | Twenty-Nine Palms
4 | 1338-3 | Temecula
3 | 1340-9 | Lumbee
3 | 1342-5 | Lummi
3 | 1344-1 | Maidu
4 | 1345-8 | Mountain Maidu
4 | 1346-6 | Nishinam
3 | 1348-2 | Makah
3 | 1350-8 | Maliseet
3 | 1352-4 | Mandan
3 | 1354-0 | Mattaponi
3 | 1356-5 | Menominee
3 | 1358-1 | Miami
4 | 1359-9 | Illinois Miami
4 | 1360-7 | Indiana Miami
4 | 1361-5 | Oklahoma Miami
3 | 1363-1 | Miccosukee
3 | 1365-6 | Micmac
4 | 1366-4 | Aroostook
3 | 1368-0 | Mission Indians
3 | 1370-6 | Miwok
3 | 1372-2 | Modoc
3 | 1374-8 | Mohegan
3 | 1376-3 | Mono
3 | 1378-9 | Nanticoke
3 | 1380-5 | Narragansett
3 | 1382-1 | Navajo
4 | 1383-9 | Alamo Navajo
4 | 1384-7 | Canoncito Navajo
4 | 1385-4 | Ramah Navajo
3 | 1387-0 | Nez Perce
3 | 1389-6 | Nomalaki
3 | 1391-2 | Northwest Tribes
4 | 1392-0 | Alsea
4 | 1393-8 | Celilo
4 | 1394-6 | Columbia
4 | 1395-3 | Kalapuya
4 | 1396-1 | Molala
4 | 1397-9 | Talakamish
4 | 1398-7 | Tenino
4 | 1399-5 | Tillamook
4 | 1400-1 | Wenatchee
4 | 1401-9 | Yahooskin
3 | 1403-5 | Omaha
3 | 1405-0 | Oregon Athabaskan
3 | 1407-6 | Osage
3 | 1409-2 | Otoe-Missouria
3 | 1411-8 | Ottawa
4 | 1412-6 | Burt Lake Ottawa
4 | 1413-4 | Michigan Ottawa
4 | 1414-2 | Oklahoma Ottawa
3 | 1416-7 | Paiute
4 | 1417-5 | Bishop
4 | 1418-3 | Bridgeport
4 | 1419-1 | Burns Paiute

4 | 1420-9 | Cedarville
4 | 1421-7 | Fort Bidwell
4 | 1422-5 | Fort Independence
4 | 1423-3 | Kaibab
4 | 1424-1 | Las Vegas
4 | 1425-8 | Lone Pine
4 | 1426-6 | Lovelock
4 | 1427-4 | Malheur Paiute
4 | 1428-2 | Moapa
4 | 1429-0 | Northern Paiute
4 | 1430-8 | Owens Valley
4 | 1431-6 | Pyramid Lake
4 | 1432-4 | San Juan Southern Paiute
4 | 1433-2 | Southern Paiute
4 | 1434-0 | Summit Lake
4 | 1435-7 | Utu Utu Gwaitu Paiute
4 | 1436-5 | Walker River
4 | 1437-3 | Yerington Paiute
3 | 1439-9 | Pamunkey
3 | 1441-5 | Passamaquoddy
4 | 1442-3 | Indian Township
4 | 1443-1 | Pleasant Point Passamaquoddy
3 | 1445-6 | Pawnee
4 | 1446-4 | Oklahoma Pawnee
3 | 1448-0 | Penobscot
3 | 1450-6 | Peoria
4 | 1451-4 | Oklahoma Peoria
3 | 1453-0 | Pequot
4 | 1454-8 | Marshantucket Pequot
3 | 1456-3 | Pima
4 | 1457-1 | Gila River Pima-Maricopa
4 | 1458-9 | Salt River Pima-Maricopa
3 | 1460-5 | Piscataway
3 | 1462-1 | Pit River
3 | 1464-7 | Pomo
4 | 1465-4 | Central Pomo
4 | 1466-2 | Dry Creek
4 | 1467-0 | Eastern Pomo
4 | 1468-8 | Kashia
4 | 1469-6 | Northern Pomo
4 | 1470-4 | Scotts Valley
4 | 1471-2 | Stonyford
4 | 1472-0 | Sulphur Bank
3 | 1474-6 | Ponca
4 | 1475-3 | Nebraska Ponca
4 | 1476-1 | Oklahoma Ponca
3 | 1478-7 | Potawatomi
4 | 1479-5 | Citizen Band Potawatomi
4 | 1480-3 | Forest County
4 | 1481-1 | Hannahville
4 | 1482-9 | Huron Potawatomi
4 | 1483-7 | Pokagon Potawatomi
4 | 1484-5 | Prairie Band
4 | 1485-2 | Wisconsin Potawatomi
3 | 1487-8 | Powhatan
3 | 1489-4 | Pueblo
4 | 1490-2 | Acoma
4 | 1491-0 | Arizona Tewa
4 | 1492-8 | Cochiti
4 | 1493-6 | Hopi
4 | 1494-4 | Isleta
4 | 1495-1 | Jemez
4 | 1496-9 | Keres
4 | 1497-7 | Laguna
4 | 1498-5 | Nambe
4 | 1499-3 | Picuris
4 | 1500-8 | Piro
4 | 1501-6 | Pojoaque
4 | 1502-4 | San Felipe
4 | 1503-2 | San Ildefonso
4 | 1504-0 | San Juan Pueblo
4 | 1505-7 | San Juan De

4 | 1506-5 | San Juan
4 | 1507-3 | Sandia
4 | 1508-1 | Santa Ana
4 | 1509-9 | Santa Clara
4 | 1510-7 | Santo Domingo
4 | 1511-5 | Taos
4 | 1512-3 | Tesuque
4 | 1513-1 | Tewa
4 | 1514-9 | Tigua
4 | 1515-6 | Zia
4 | 1516-4 | Zuni
3 | 1518-0 | Puget Sound Salish
4 | 1519-8 | Duwamish
4 | 1520-6 | Kikiallus
4 | 1521-4 | Lower Skagit
4 | 1522-2 | Muckleshoot
4 | 1523-0 | Nisqually
4 | 1524-8 | Nooksack
4 | 1525-5 | Port Madison
4 | 1526-3 | Puyallup
4 | 1527-1 | Samish
4 | 1528-9 | Sauk-Suiattle
4 | 1529-7 | Skokomish
4 | 1530-5 | Skykomish
4 | 1531-3 | Snohomish
4 | 1532-1 | Snoqualmie
4 | 1533-9 | Squaxin Island
4 | 1534-7 | Steilacoom
4 | 1535-4 | Stillaguamish
4 | 1536-2 | Suquamish
4 | 1537-0 | Swinomish
4 | 1538-8 | Tulalip
4 | 1539-6 | Upper Skagit
3 | 1541-2 | Quapaw
3 | 1543-8 | Quinault
3 | 1545-3 | Rappahannock
3 | 1547-9 | Reno-Sparks
3 | 1549-5 | Round Valley
3 | 1551-1 | Sac and Fox
4 | 1552-9 | Iowa Sac and Fox
4 | 1553-7 | Missouri Sac and Fox
4 | 1554-5 | Oklahoma Sac and Fox
3 | 1556-0 | Salinan
3 | 1558-6 | Salish
3 | 1560-2 | Salish and Kootenai
3 | 1562-8 | Schaghticoke
3 | 1564-4 | Scott Valley
3 | 1566-9 | Seminole
4 | 1567-7 | Big Cypress
4 | 1568-5 | Brighton
4 | 1569-3 | Florida Seminole
4 | 1570-1 | Hollywood Seminole
4 | 1571-9 | Oklahoma Seminole
3 | 1573-5 | Serrano
4 | 1574-3 | San Manual
3 | 1576-8 | Shasta
3 | 1578-4 | Shawnee
4 | 1579-2 | Absentee Shawnee
4 | 1580-0 | Eastern Shawnee
3 | 1582-6 | Shinnecock
3 | 1584-2 | Shoalwater Bay
3 | 1586-7 | Shoshone
4 | 1587-5 | Battle Mountain
4 | 1588-3 | Duckwater
4 | 1589-1 | Elko
4 | 1590-9 | Ely
4 | 1591-7 | Goshute
4 | 1592-5 | Panamint
4 | 1593-3 | Ruby Valley
4 | 1594-1 | Skull Valley
4 | 1595-8 | South Fork Shoshone
4 | 1596-6 | Te-Moak Western Shoshone

4 | 1597-4 | Timbi-Sha Shoshone
4 | 1598-2 | Washakie
4 | 1599-0 | Wind River Shoshone
4 | 1600-6 | Yomba
3 | 1602-2 | Shoshone Paiute
4 | 1603-0 | Duck Valley
4 | 1604-8 | Fallon
4 | 1605-5 | Fort McDermitt
3 | 1607-1 | Siletz
3 | 1609-7 | Sioux
4 | 1610-5 | Blackfoot Sioux
4 | 1611-3 | Brule Sioux
4 | 1612-1 | Cheyenne River Sioux
4 | 1613-9 | Crow Creek Sioux
4 | 1614-7 | Dakota Sioux
4 | 1615-4 | Flandreau Santee
4 | 1616-2 | Fort Peck
4 | 1617-0 | Lake Traverse Sioux
4 | 1618-8 | Lower Brule Sioux
4 | 1619-6 | Lower Sioux
4 | 1620-4 | Mdewakanton Sioux
4 | 1621-2 | Miniconjou
4 | 1622-0 | Oglala Sioux
4 | 1623-8 | Pine Ridge Sioux
4 | 1624-6 | Pipestone Sioux
4 | 1625-3 | Prairie Island Sioux
4 | 1626-1 | Prior Lake Sioux
4 | 1627-9 | Rosebud Sioux
4 | 1628-7 | Sans Arc Sioux
4 | 1629-5 | Santee Sioux
4 | 1630-3 | Sisseton-Wahpeton
4 | 1631-1 | Sisseton Sioux
4 | 1632-9 | Spirit Lake Sioux
4 | 1633-7 | Standing Rock Sioux
4 | 1634-5 | Teton Sioux
4 | 1635-2 | Two Kettle Sioux
4 | 1636-0 | Upper Sioux
4 | 1637-8 | Wahpekute Sioux
4 | 1638-6 | Wahpeton Sioux
4 | 1639-4 | Wazhaza Sioux
4 | 1640-2 | Yankton Sioux
4 | 1641-0 | Yanktonai Sioux
3 | 1643-6 | Siuslaw
3 | 1645-1 | Spokane
3 | 1647-7 | Stewart
3 | 1649-3 | Stockbridge
3 | 1651-9 | Susanville
3 | 1653-5 | Tohono O'Odham
4 | 1654-3 | Ak-Chin
4 | 1655-0 | Gila Bend
4 | 1656-8 | San Xavier
4 | 1657-6 | Sells
3 | 1659-2 | Tolowa
3 | 1661-8 | Tonkawa
3 | 1663-4 | Tygh
3 | 1665-9 | Umatilla
3 | 1667-5 | Umpqua
4 | 1668-3 | Cow Creek Umpqua
3 | 1670-9 | Ute
4 | 1671-7 | Allen Canyon
4 | 1672-5 | Uintah Ute
4 | 1673-3 | Ute Mountain Ute
3 | 1675-8 | Wailaki
3 | 1677-4 | Walla-Walla
3 | 1679-0 | Wampanoag
4 | 1680-8 | Gay Head Wampanoag
4 | 1681-6 | Mashpee Wampanoag
3 | 1683-2 | Warm Springs
3 | 1685-7 | Wascopum
3 | 1687-3 | Washoe
4 | 1688-1 | Alpine
4 | 1689-9 | Carson

4 | 1690-7 | Dresslerville
3 | 1692-3 | Wichita
3 | 1694-9 | Wind River
3 | 1696-4 | Winnebago
4 | 1697-2 | Ho-chunk
4 | 1698-0 | Nebraska Winnebago
3 | 1700-4 | Winnemucca
3 | 1702-0 | Wintun
3 | 1704-6 | Wiyot
4 | 1705-3 | Table Bluff
3 | 1707-9 | Yakama
3 | 1709-5 | Yakama Cowlitz
3 | 1711-1 | Yaqui
4 | 1712-9 | Barrio Libre
4 | 1713-7 | Pascua Yaqui
3 | 1715-2 | Yavapai Apache
3 | 1717-8 | Yokuts
4 | 1718-6 | Chukchansi
4 | 1719-4 | Tachi
4 | 1720-2 | Tule River
3 | 1722-8 | Yuchi
3 | 1724-4 | Yuman
4 | 1725-1 | Cocopah
4 | 1726-9 | Havasupai
4 | 1727-7 | Hualapai
4 | 1728-5 | Maricopa
4 | 1729-3 | Mohave
4 | 1730-1 | Quechan
4 | 1731-9 | Yavapai
3 | 1732-7 | Yurok
4 | 1733-5 | Coast Yurok
2 | 1735-0 | Alaska Native
3 | 1737-6 | Alaska Indian
4 | 1739-2 | Alaskan Athabascan
5 | 1740-0 | Ahtna
4 | 1811-9 | Southeast Alaska
5 | 1813-5 | Tlingit-Haida
6 | 1814-3 | Angoon
6 | 1815-0 | Central Council of Tlingit and Haida Tribes
6 | 1816-8 | Chilkat
6 | 1817-6 | Chilkoot
6 | 1818-4 | Craig
6 | 1819-2 | Douglas
6 | 1820-0 | Haida
6 | 1821-8 | Hoonah
6 | 1822-6 | Hydaburg
6 | 1823-4 | Kake
6 | 1824-2 | Kasaan
6 | 1825-9 | Kenaitze
6 | 1826-7 | Ketchikan
6 | 1827-5 | Klawock
6 | 1828-3 | Pelican
6 | 1829-1 | Petersburg
6 | 1830-9 | Saxman
6 | 1831-7 | Sitka
6 | 1832-5 | Tenakee Springs
6 | 1833-3 | Tlingit
6 | 1834-1 | Wrangell
6 | 1835-8 | Yakutat
5 | 1837-4 | Tsimshian
6 | 1838-2 | Metlakatla
3 | 1840-8 | Eskimo
4 | 1842-4 | Greenland Eskimo
4 | 1844-0 | Inupiat Eskimo
5 | 1845-7 | Ambler
5 | 1846-5 | Anaktuvuk
5 | 1847-3 | Anaktuvuk Pass
5 | 1848-1 | Arctic Slope Inupiat
5 | 1849-9 | Arctic Slope Corporation
5 | 1850-7 | Atqasuk
5 | 1851-5 | Barrow
5 | 1852-3 | Bering Straits Inupiat

5 | 1853-1 | Brevig Mission
5 | 1854-9 | Buckland
5 | 1855-6 | Chinik
5 | 1856-4 | Council
5 | 1857-2 | Deering
5 | 1858-0 | Elim
5 | 1859-8 | Golovin
5 | 1860-6 | Inalik Diomede
5 | 1861-4 | Inupiaq
5 | 1862-2 | Kaktovik
5 | 1863-0 | Kawerak
5 | 1864-8 | Kiana
5 | 1865-5 | Kivalina
5 | 1866-3 | Kobuk
5 | 1867-1 | Kotzebue
5 | 1868-9 | Koyuk
5 | 1869-7 | Kwiguk
5 | 1870-5 | Mauneluk Inupiat
5 | 1871-3 | Nana Inupiat
5 | 1872-1 | Noatak
5 | 1873-9 | Nome
5 | 1874-7 | Noorvik
5 | 1875-4 | Nuiqsut
5 | 1876-2 | Point Hope
5 | 1877-0 | Point Lay
5 | 1878-8 | Selawik
5 | 1879-6 | Shaktoolik
5 | 1880-4 | Shishmaref
5 | 1881-2 | Shungnak
5 | 1882-0 | Solomon
5 | 1883-8 | Teller
5 | 1884-6 | Unalakleet
5 | 1885-3 | Wainwright
5 | 1886-1 | Wales
5 | 1887-9 | White Mountain
5 | 1888-7 | White Mountain Inupiat
5 | 1889-5 | Mary's Igloo
4 | 1891-1 | Siberian Eskimo
5 | 1892-9 | Gambell
5 | 1893-7 | Savoonga
5 | 1894-5 | Siberian Yupik
4 | 1896-0 | Yupik Eskimo
5 | 1897-8 | Akiachak
5 | 1898-6 | Akiak
5 | 1899-4 | Alakanuk
5 | 1900-0 | Aleknagik
5 | 1901-8 | Andreafsky
5 | 1902-6 | Aniak
5 | 1903-4 | Atmautluak
5 | 1904-2 | Bethel
5 | 1905-9 | Bill Moore's Slough
5 | 1906-7 | Bristol Bay Yupik
5 | 1907-5 | Calista Yupik
5 | 1908-3 | Chefornak
5 | 1909-1 | Chevak
5 | 1910-9 | Chuathbaluk
5 | 1911-7 | Clark's Point
5 | 1912-5 | Crooked Creek
5 | 1913-3 | Dillingham
5 | 1914-1 | Eek
5 | 1915-8 | Ekuk
5 | 1916-6 | Ekwok
5 | 1917-4 | Emmonak
5 | 1918-2 | Goodnews Bay
5 | 1919-0 | Hooper Bay
5 | 1920-8 | Iqurmuit (Russian Mission)
5 | 1921-6 | Kalskag
5 | 1922-4 | Kasigluk
5 | 1923-2 | Kipnuk
5 | 1924-0 | Koliganek
5 | 1925-7 | Kongiganak
5 | 1926-5 | Kotlik

5 | 1927-3 | Kwethluk
5 | 1928-1 | Kwigillingok
5 | 1929-9 | Levelock
5 | 1930-7 | Lower Kalskag
5 | 1931-5 | Manokotak
5 | 1932-3 | Marshall
5 | 1933-1 | Mekoryuk
5 | 1934-9 | Mountain Village
5 | 1935-6 | Naknek
5 | 1936-4 | Napaumute
5 | 1937-2 | Napakiak
5 | 1938-0 | Napaskiak
5 | 1939-8 | Newhalen
5 | 1940-6 | New Stuyahok
5 | 1941-4 | Newtok
5 | 1942-2 | Nightmute
5 | 1943-0 | Nunapitchukv
5 | 1944-8 | Oscarville
5 | 1945-5 | Pilot Station
5 | 1946-3 | Pitkas Point
5 | 1947-1 | Platinum
5 | 1948-9 | Portage Creek
5 | 1949-7 | Quinhagak
5 | 1950-5 | Red Devil
5 | 1951-3 | St. Michael
5 | 1952-1 | Scammon Bay
5 | 1953-9 | Sheldon's Point
5 | 1954-7 | Sleetmute
5 | 1955-4 | Stebbins
5 | 1956-2 | Togiak
5 | 1957-0 | Toksook
5 | 1958-8 | Tulukskak
5 | 1959-6 | Tuntutuliak
5 | 1960-4 | Tununak
5 | 1961-2 | Twin Hills
5 | 1962-0 | Georgetown
5 | 1963-8 | St. Mary's
5 | 1964-6 | Umkumiate
3 | 1966-1 | Aleut
4 | 1968-7 | Alutiiq Aleut
5 | 1969-5 | Tatitlek
5 | 1970-3 | Ugashik
4 | 1972-9 | Bristol Bay Aleut
5 | 1973-7 | Chignik
5 | 1974-5 | Chignik Lake
5 | 1975-2 | Egegik
5 | 1976-0 | Igiugig
5 | 1977-8 | Ivanof Bay
5 | 1978-6 | King Salmon
5 | 1979-4 | Kokhanok
5 | 1980-2 | Perryville
5 | 1981-0 | Pilot Point
5 | 1982-8 | Port Heiden
4 | 1984-4 | Chugach Aleut
5 | 1985-1 | Chenega
5 | 1986-9 | Chugach Corporation
5 | 1987-7 | English Bay
5 | 1988-5 | Port Graham
4 | 1990-1 | Eyak
4 | 1992-7 | Koniag Aleut
5 | 1993-5 | Akhiok
5 | 1994-3 | Agdaagux
5 | 1995-0 | Karluk
5 | 1996-8 | Kodiak
5 | 1997-6 | Larsen Bay
5 | 1998-4 | Old Harbor
5 | 1999-2 | Ouzinkie
5 | 2000-8 | Port Lions
4 | 2002-4 | Sugpiaq
4 | 2004-0 | Suqpigaq
4 | 2006-5 | Unangan Aleut
5 | 2007-3 | Akutan

5 | 2008-1 | Aleut Corporation
5 | 2009-9 | Aleutian
5 | 2010-7 | Aleutian Islander
5 | 2011-5 | Atka
5 | 2012-3 | Belkofski
5 | 2013-1 | Chignik Lagoon
5 | 2014-9 | King Cove
5 | 2015-6 | False Pass
5 | 2016-4 | Nelson Lagoon
5 | 2017-2 | Nikolski
5 | 2018-0 | Pauloff Harbor
5 | 2019-8 | Qagan Toyagungin
5 | 2020-6 | Qawalangin
5 | 2021-4 | St. George
5 | 2022-2 | St. Paul
5 | 2023-0 | Sand Point
5 | 2024-8 | South Naknek
5 | 2025-5 | Unalaska
5 | 2026-3 | Unga
1 | 2028-9 | Asian
2 | 2029-7 | Asian Indian
2 | 2030-5 | Bangladeshi
2 | 2031-3 | Bhutanese
2 | 2032-1 | Burmese
2 | 2033-9 | Cambodian
2 | 2034-7 | Chinese
2 | 2035-4 | Taiwanese
2 | 2036-2 | Filipino
2 | 2037-0 | Hmong
2 | 2038-8 | Indonesian
2 | 2039-6 | Japanese
2 | 2040-4 | Korean
2 | 2041-2 | Laotian
2 | 2042-0 | Malaysian
2 | 2043-8 | Okinawan
2 | 2044-6 | Pakistani
2 | 2045-3 | Sri Lankan
2 | 2046-1 | Thai
2 | 2047-9 | Vietnamese
2 | 2048-7 | Iwo Jiman
2 | 2049-5 | Maldivian
2 | 2050-3 | Nepalese
2 | 2051-1 | Singaporean
2 | 2052-9 | Madagascar
1 | 2054-5 | Black or African American
2 | 2056-0 | Black
2 | 2058-6 | African American
2 | 2060-2 | African
3 | 2061-0 | Botswanan
3 | 2062-8 | Ethiopian
3 | 2063-6 | Liberian
3 | 2064-4 | Namibian
3 | 2065-1 | Nigerian
3 | 2066-9 | Zairean
2 | 2067-7 | Bahamian
2 | 2068-5 | Barbadian
2 | 2069-3 | Dominican
2 | 2070-1 | Dominica Islander
2 | 2071-9 | Haitian
2 | 2072-7 | Jamaican
2 | 2073-5 | Tobagoan
2 | 2074-3 | Trinidadian
2 | 2075-0 | West Indian
1 | 2076-8 | Native Hawaiian or Other Pacific Islander
2 | 2078-4 | Polynesian
3 | 2079-2 | Native Hawaiian
3 | 2080-0 | Samoan
3 | 2081-8 | Tahitian
3 | 2082-6 | Tongan
3 | 2083-4 | Tokelauan
2 | 2085-9 | Micronesian
3 | 2086-7 | Guamanian or Chamorro

3 | 2087-5 | Guamanian
3 | 2088-3 | Chamorro
3 | 2089-1 | Mariana Islander
3 | 2090-9 | Marshallese
3 | 2091-7 | Palauan
3 | 2092-5 | Carolinian
3 | 2093-3 | Kosraean
3 | 2094-1 | Pohnpeian
3 | 2095-8 | Saipanese
3 | 2096-6 | Kiribati
3 | 2097-4 | Chuukese
3 | 2098-2 | Yapese
2 | 2100-6 | Melanesian
3 | 2101-4 | Fijian
3 | 2102-2 | Papua New Guinean
3 | 2103-0 | Solomon Islander
3 | 2104-8 | New Hebrides
2 | 2500-7 | Other Pacific Islander | Note that this term remains in the table for completeness, even though within HL7, the notion of Other code is deprecated.
1 | 2106-3 | White
2 | 2108-9 | European
3 | 2109-7 | Armenian
3 | 2110-5 | English
3 | 2111-3 | French
3 | 2112-1 | German
3 | 2113-9 | Irish
3 | 2114-7 | Italian
3 | 2115-4 | Polish
3 | 2116-2 | Scottish
2 | 2118-8 | Middle Eastern or North African
3 | 2119-6 | Assyrian
3 | 2120-4 | Egyptian
3 | 2121-2 | Iranian
3 | 2122-0 | Iraqi
3 | 2123-8 | Lebanese
3 | 2124-6 | Palestinian
3 | 2125-3 | Syrian
3 | 2126-1 | Afghanistani
3 | 2127-9 | Israeili
2 | 2129-5 | Arab
1 | 2131-1 | Other Race | Note that this term remains in the table for completeness, even though within HL7, the notion of Other code is deprecated.

4.3.2.105 HL7 v3 Code System RelationalOperator

URL: https://hl7.org/fhir/STU3/v3/RelationalOperator/cs.html

This page is part of the FHIR Specification (v3.0.2: STU 3). The current version which supercedes this version is 4.0.1. For a full list of available versions, see the Directory of published versions

Vocabulary Work Group | Maturity Level: N/A | External | Use Context: Any

This code system (http://hl7.org/fhir/v3/RelationalOperator) is defined as part of HL7 v3.

Summary

Defining URL: | http://hl7.org/fhir/v3/RelationalOperator
Name: | v3 Code System RelationalOperator
Definition: | **** MISSING DEFINITIONS ****
OID: | 2.16.840.1.113883.5.105 (for OID based terminology systems)
Source Resource | XML / JSON

This Code system is used in the following value sets:

* v3 Code System RelationalOperator (**** MISSING DEFINITIONS ****)

4.3.2.105.1 Code System Content

Release Date: 2016-11-11

Level | Code | Display | Definition
1 | CT | Contains | Specified set of things includes value being evaluated.
1 | EQ | Equal | Equal condition applied to comparisons.
1 | GE | Greater than or equal | Greater than or equal condition applied to comparisons.
1 | GN | Generic | A generic comparison selects a record for inclusion in the response if the beginning of the designated element value matches the select string.
1 | GT | Greater than | Greater than condition applied to comparisons.
1 | LE | Less than or equal | Less than or equal condition applied to comparisons.
1 | LT | Less than | Less than condition applied to comparisons.

1 | NE | Not Equal | Not equal condition applied to comparisons.

4.3.2.106 HL7 v3 Code System RelationshipConjunction

URL: https://hl7.org/fhir/STU3/v3/RelationshipConjunction/cs.html

This page is part of the FHIR Specification (v3.0.2: STU 3). The current version which supercedes this version is 4.0.1. For a full list of available versions, see the Directory of published versions

Vocabulary Work Group | Maturity Level: N/A | External | Use Context: Any

This code system (http://hl7.org/fhir/v3/RelationshipConjunction) is defined as part of HL7 v3.

Summary

Defining URL: | http://hl7.org/fhir/v3/RelationshipConjunction
Name: | v3 Code System RelationshipConjunction
Definition: | **** MISSING DEFINITIONS ****
OID: | 2.16.840.1.113883.5.106 (for OID based terminology systems)
Source Resource | XML / JSON

This Code system is used in the following value sets:

* v3 Code System RelationshipConjunction (**** MISSING DEFINITIONS ****)

4.3.2.106.1 Code System Content

Release Date: 2016-11-11

Level | Code | Display | Definition
1 | AND | and | This condition must be true.
1 | OR | or | At least one of the condition among all OR conditions must be true.
1 | XOR | exclusive or | One and only one of the XOR conditions must be true.

4.3.2.107 HL7 v3 Code System RoleLinkType

URL: https://hl7.org/fhir/STU3/v3/RoleLinkType/cs.html

This page is part of the FHIR Specification (v3.0.2: STU 3). The current version which supercedes this version is 4.0.1. For a full list of available versions, see the Directory of published versions

Vocabulary Work Group | Maturity Level: N/A | External | Use Context: Any

This code system (http://hl7.org/fhir/v3/RoleLinkType) is defined as part of HL7 v3.

Summary

Defining URL: | http://hl7.org/fhir/v3/RoleLinkType
Name: | v3 Code System RoleLinkType
Definition: | **** MISSING DEFINITIONS ****
OID: | 2.16.840.1.113883.5.107 (for OID based terminology systems)
Source Resource | XML / JSON

This Code system is used in the following value sets:

* v3 Code System RoleLinkType (**** MISSING DEFINITIONS ****)

4.3.2.107.1 Code System Content

Release Date: 2016-11-11

Level | Code | Display | Definition
1 | REL | related | An action taken with respect to a subject Entity by a regulatory or authoritative body with supervisory capacity over that entity. The action is taken in response to behavior by the subject Entity that body finds to be undesirable. Suspension, license restrictions, monetary fine, letter of reprimand, mandated training, mandated supervision, etc.Examples:
2 | BACKUP | is backup for | This relationship indicates the source Role is available to the target Role as a backup. An entity in a backup role will be available as a substitute or replacement in the event that the entity assigned the role is unavailable. In medical roles where it is critical that the function be performed and there is a possibility that the individual assigned may be ill or otherwise indisposed, another individual is assigned to cover for the individual originally assigned the role. A backup may be required to be identified, but unless the backup is actually used, he/she would not assume the assigned entity role.
2 | CONT | has contact | This relationship indicates the target Role provides or receives information regarding the target role. For example, AssignedEntity is a contact for a ServiceDeliveryLocation.
2 | DIRAUTH | has direct authority over | The source Role has direct authority over the target role in a chain of authority.
2 | IDENT | Identification | Description: The source role provides identification for the target role. The source role must be IDENT. The player entity of the source role is constrained to be the same as (i.e. the equivalent of, or equal to) the player of the target role if present. If the player is absent from the source role, then it is assumed to be the same as the player of the target role.
2 | INDAUTH | has indirect authority over | The source Role has indirect authority over the target role in a chain of authority.
2 | PART | has part | The target Role is part of the Source Role.
2 | REPL | replaces | This relationship indicates that the source Role replaces (or subsumes) the target Role. Allows for new identifiers and/or new effective time for a registry entry or a certification, etc.

4.3.2.108 HL7 v3 Code System ResponseLevel

URL: https://hl7.org/fhir/STU3/v3/ResponseLevel/cs.html

This page is part of the FHIR Specification (v3.0.2: STU 3). The current version which supercedes this version is 4.0.1. For a full list of available versions, see the Directory of published versions

Vocabulary Work Group | Maturity Level: N/A | External | Use Context: Any

This code system (http://hl7.org/fhir/v3/ResponseLevel) is defined as part of HL7 v3.

Summary

Defining URL: | http://hl7.org/fhir/v3/ResponseLevel
Name: | v3 Code System ResponseLevel
Definition: | Specifies whether a response is expected from the addressee of this interaction and what level of detail that response should include
OID: | 2.16.840.1.113883.5.108 (for OID based terminology systems)
Source Resource | XML / JSON

This Code system is used in the following value sets:

* v3 Code System ResponseLevel (Specifies whether a response is expected from the addressee of this interaction and what level of detail that response should include)

4.3.2.108.1 Code System Content

Release Date: 2016-11-11

Level | Code | Display | Definition
1 | C | completion | Respond with exceptions and a notification of completion
1 | D | detail | Respond with exceptions, completion, modifications and include more detail information (if applicable)
1 | E | exception | Respond with exceptions only
1 | F | confirmation | Respond with exceptions, completion, and modification with detail (as above), and send positive confirmations even if no modifications are being made.
1 | N | message-control | Respond only with message level acknowledgements, i.e., only notify acceptance or rejection of the message, do not include any application-level detail
1 | R | modification | Respond with exceptions, completions and modifications or revisions done before completion
1 | X | none | Do not send any kind of response

4.3.2.109 HL7 v3 Code System ResponseModality

URL: https://hl7.org/fhir/STU3/v3/ResponseModality/cs.html

This page is part of the FHIR Specification (v3.0.2: STU 3). The current version which supercedes this version is 4.0.1. For a full list of available versions, see the Directory of published versions

Vocabulary Work Group | Maturity Level: N/A | External | Use Context: Any

This code system (http://hl7.org/fhir/v3/ResponseModality) is defined as part of HL7 v3.

Summary

Defining URL: | http://hl7.org/fhir/v3/ResponseModality
Name: | v3 Code System ResponseModality
Definition: | Defines the timing and grouping of the response instances. OpenIssue: Description copied from Concept Domain of same name. Must be verified.
OID: | 2.16.840.1.113883.5.109 (for OID based terminology systems)
Source Resource | XML / JSON

This Code system is used in the following value sets:

* v3 Code System ResponseModality (Defines the timing and grouping of the response instances. OpenIssue: Description copied from Concept Domain of same name. Must be verified.)

4.3.2.109.1 Code System Content

Release Date: 2016-11-11

Level | Code | Display | Definition
1 | B | Batch | Query response to be sent as an HL7 Batch.
1 | R | Real Time | Query response to occur in real time.
1 | T | Bolus | Query response to sent as a series of responses at the same time without the use of batch formatting.

4.3.2.110 HL7 v3 Code System RoleClass

URL: https://hl7.org/fhir/STU3/v3/RoleClass/cs.html

This page is part of the FHIR Specification (v3.0.2: STU 3). The current version which supercedes this version is 4.0.1. For a full list of available versions, see the Directory of published versions

Vocabulary Work Group | Maturity Level: N/A | External | Use Context: Any

This code system (http://hl7.org/fhir/v3/RoleClass) is defined as part of HL7 v3.

Summary

Defining URL: | http://hl7.org/fhir/v3/RoleClass
Name: | v3 Code System RoleClass
Definition: | Codes for the Role class hierarchy. The values in this hierarchy, represent a Role which is an association or relationship between two entities - the entity that plays the role and the entity that scopes the role. Roles names are derived from the name of the playing entity in that role.

The role hierarchy stems from three core concepts, or abstract domains: RoleClassOntological is an abstract domain that collects roles in which the playing entity is defined or specified by the scoping entity. RoleClassPartitive collects roles in which the playing entity is in some sense a "part" of the scoping entity. RoleClassAssociative collects all of the remaining forms of association between the playing entity and the scoping entity. This set of roles is further partitioned between: RoleClassPassive which are roles in which the playing entity is used, known, treated, handled, built, or destroyed, etc. under the auspices of the scoping entity. The playing entity is passive in these roles in that the role exists without an agreement from the playing entity. RoleClassMutualRelationship which are relationships based on mutual behavior of the two entities. The basis of these relationship may be formal agreements or they may bede facto behavior. Thus, this sub-domain is further divided into: RoleClassRelationshipFormal in which the relationship is formally defined, frequently by a contract or agreement. Personal relationship which inks two people in a personal relationship. The hierarchy discussed above is represented In the current vocabulary tables as a set of abstract domains, with the exception of the "Personal relationship" which is a leaf concept. OpenIssue: Description copied from Concept Domain of same name. Must be verified.

OID: | 2.16.840.1.113883.5.110 (for OID based terminology systems)

Source Resource | XML / JSON

This Code system is used in the following value sets:

* v3 Code System RoleClass (Codes for the Role class hierarchy. The values in this hierarchy, represent a Role which is an association or relationship between two entities - the entity that plays the role and the entity that scopes the role. Roles names are derived from the name of the playing entity in that role. The role hierarchy stems from three core concepts, or abstract domains: RoleClassOntological is an abstract domain that collects roles in which the playing entity is defined or specified by the scoping entity. RoleClassPartitive collects roles in which the playing entity is in some sense a "part" of the scoping entity. RoleClassAssociative collects all of the remaining forms of association between the playing entity and the scoping entity. This set of roles is further partitioned between: RoleClassPassive which are roles in which the playing entity is used, known, treated, handled, built, or destroyed, etc. under the auspices of the scoping entity. The playing entity is passive in these roles in that the role exists without an agreement from the playing entity. RoleClassMutualRelationship which are relationships based on mutual behavior of the two entities. The basis of these relationship may be formal agreements or they may bede facto behavior. Thus, this sub-domain is further divided into: RoleClassRelationshipFormal in which the relationship is formally defined, frequently by a contract or agreement. Personal relationship which inks two people in a personal relationship. The hierarchy discussed above is represented In the current vocabulary tables as a set of abstract domains, with the exception of the "Personal relationship" which is a leaf concept. OpenIssue: Description copied from Concept Domain of same name. Must be verified.)

* RoleClassManufacturedProduct (Scoped by the manufacturer)

* RoleClassRelationshipFormal (A relationship between two entities that is formally recognized, frequently by a contract or similar agreement.)

* RoleClassPartitive (An association between two Entities where the playing Entity is considered in some way "part" of the scoping Entity, e.g., as a member, component, ingredient, or content. Being "part" in the broadest sense of the word can mean anything from being an integral structural component to a mere incidental temporary association of a playing Entity with a (generally larger) scoping Entity.)

* RoleClassPassive (An association for a playing Entity that is used, known, treated, handled, built, or destroyed, etc. under the auspices of the scoping Entity. The playing Entity is passive in these roles (even though it may be active in other roles), in the sense that the kinds of things done to it in this role happen without an agreement from the playing Entity.)

* RoleClassRoot (Corresponds to the Role class)

* RoleClassSpecimen (A role played by a material entity that is a specimen for an act. It is scoped by the source of the specimen.)

* RoleClassAssociative (A general association between two entities that is neither partitive nor ontological.)

* RoleClassAgent (An entity (player) that acts or is authorized to act on behalf of another entity (scoper).)

* RoleClassMutualRelationship (A relationship that is based on mutual behavior of the two Entities as being related. The basis of such relationship may be agreements (e.g., spouses, contract parties) or they may bede facto behavior (e.g. friends) or may be an incidental involvement with each other (e.g. parties over a dispute, siblings, children).)

* RoleClassServiceDeliveryLocation (A role played by a place at which services may be provided.)

4.3.2.110.1 Code System Content

Release Date: 2016-11-11

Level | Code | Display | Definition

1 | ROL | role | Corresponds to the Role class

2 | (_RoleClassAssociative) Abstract | | A general association between two entities that is neither partitive nor ontological.

3 | (_RoleClassMutualRelationship) Abstract | | A relationship that is based on mutual behavior of the two Entities as being related. The basis of such relationship may be agreements (e.g., spouses, contract parties) or they may be de facto behavior (e.g. friends) or may be an incidental involvement with each other (e.g. parties over a dispute, siblings, children).

4 | (_RoleClassRelationshipFormal) Abstract | | A relationship between two entities that is formally recognized, frequently by a contract or similar agreement.

5 | AFFL | affiliate | Player of the Affiliate role has a business/professional relationship with scoper. Player and scoper may be persons or organization. The Affiliate relationship does not imply membership in a group, nor does it exist for resource scheduling purposes. Example: A healthcare provider is affiliated with another provider as a business associate.

5 | AGNT | agent | An entity (player) that acts or is authorized to act on behalf of another entity (scoper).

6 | ASSIGNED | assigned entity | An agent role in which the agent is an Entity acting in the employ of an organization. The focus is on functional role on behalf of the organization, unlike the Employee role where the focus is on the 'Human Resources' relationship between the employee and the organization.

7 | COMPAR | commissioning party | An Entity that is authorized to issue or instantiate permissions, privileges, credentials or other formal/legal authorizations.

7 | SGNOFF | signing authority or officer | The role of a person (player) who is the officer or signature authority for of a scoping entity, usually an organization (scoper).

6 | CON | contact | A person or an organization (player) which provides or receives information regarding another entity (scoper). Examples; patient NOK and emergency contacts; guarantor contact; employer contact.

7 | ECON | emergency contact | An entity to be contacted in the event of an emergency.

7 | NOK | next of kin | An individual designated for notification as the next of kin for a given entity.

6 | GUARD | guardian | Guardian of a ward

5 | CIT | citizen | Citizen of apolitical entity

5 | COVPTY | covered party | A role class played by a person who receives benefit coverage under the terms of a particular insurance policy. The underwriter of that policy is the scoping entity. The covered party receives coverage because of some contractual or other relationship with the holder of that policy. Discussion:This reason for coverage is captured in 'Role.code' and a relationship link with type code of indirect authority should be included using the policy holder role as the source, and the covered party role as the target. Note that a particular policy may cover several individuals one of whom may be, but need not be, the policy holder. Thus the notion of covered party is a role that is distinct from that of the policy holder.

6 | CLAIM | claimant | Description: A role played by a party making a claim for coverage under a policy or program. A claimant must be either a person or organization, or a group of persons or organizations. A claimant is not a named insured or a program eligible. Discussion: With respect to liability insurance such as property and casualty insurance, a claimant must file a claim requesting indemnification for a loss that the claimant considers covered under the policy of a named insured. The claims adjuster for the policy underwriter will review the claim to determine whether the loss meets the benefit coverage criteria under a policy, and base any indemnification or coverage payment on that review. If a third party is liable in whole or part for the loss, the underwriter may pursue third party liability recovery. A claimant may be involved in civil or criminal legal proceedings involving claims against a defendant party that is indemnified by an insurance policy or to protest the finding of a claims adjustor. With respect to life insurance, a beneficiary designated by a named insured becomes a claimant of the proceeds of coverage, as in the case of a life insurance policy. However, a claimant for coverage under life insurance is not necessarily a designated beneficiary. Note: A claimant is not a named insured. However, a named insured may make a claim under a policy, e.g., an insured driver may make a claim for an injury under his or her comprehensive automobile insurance policy. Similarly, a program eligible may make a claim under program, e.g., an unemployed worker may claim benefits under an unemployment insurance program, but parties playing these covered party role classes are not, for purposes of this vocabulary and in an effort to clearly distinguish role classes, considered claimants. In the case of a named insured making a claim, a role type code INSCLM (insured claimant) subtypes the class to indicate that either a named insured or an individual insured has filed a claim for a loss. In the case of a program eligible, a role type code INJWKR (injured worker) subtypes the class to indicate that the covered party in a workers compensation program is an injured worker, and as such, has filed a "claim" under the program for benefits. Likewise, a covered role type code UNEMP (unemployed worker) subtypes the program eligible class to indicate that the covered party in an unemployment insurance program has filed a claim for unemployment benefits. Example: A claimant under automobile policy that is not the named insured.

6 | NAMED | named insured | Description: A role played by a party to an insurance policy to which the insurer agrees to indemnify for losses, provides benefits for, or renders services. A named insured may be either a person, non-person living subject, or an organization, or a group of persons, non-person living subjects, or organizations. Discussion: The coded concept NAMED should not be used where a more specific child concept in this Specializable value set applies. In some cases, the named insured may not be the policy holder, e.g., where a policy holder purchases life insurance policy in which another party is the named insured and the policy holder is the beneficiary of the policy. Note: The party playing the role of a named insured is not a claimant in the sense conveyed by the RoleClassCoveredParty CLAIM (claimant). However, a named insured may make a claim under a policy, e.g., e.g., a party that is the named insured and policy holder under a comprehensive automobile insurance policy may become the claimant for coverage under that policy e.g., if injured in an automobile accident and there is no liable third party. In the case of a named insured making a claim, a role type code INSCLM (insured claimant) subtypes the class to indicate that a named insured has filed a claim for a loss. Example: The named insured under a comprehensive automobile, disability, or property and casualty policy that is the named insured and may or may not be the policy holder.

7 | DEPEN | dependent | Description: A role played by a person covered under a policy or program based on an association with a subscriber, which is recognized by the policy holder. Note: The party playing the role of a dependent is not a claimant in the sense conveyed by the RoleClassCoveredParty CLAIM (claimant). However, a dependent may make a claim under a policy, e.g., a dependent under a health insurance policy may become the claimant for coverage under that policy for wellness examines or if injured and there is no liable third party. In the case of a dependent making a claim, a role type code INSCLM (insured claimant) subtypes the class to indicate that the dependent has filed a claim for services covered under the health insurance policy. Example: The dependent has an association with the subscriber such as a financial dependency or personal relationship such as that of a spouse, or a natural or adopted child. The policy holder may be required by law to recognize certain associations or may have discretion about the associations. For example, a policy holder may dictate the criteria for the dependent status of adult children who are students, such as requiring full time enrollment, or may recognize domestic partners as dependents. Under certain circumstances, the dependent may be under the indirect authority of a responsible party acting as a surrogate for the subscriber, for example, if the subscriber is differently abled or deceased, a guardian ad Lidem or estate executor may be appointed to assume the subscriberaTMs legal standing in the relationship with the dependent.

7 | INDIV | individual | Description: A role played by a party covered under a policy as the policy holder. An individual may be either a person or an organization. Note: The party playing the role of an individual insured is not a claimant in the sense conveyed by the RoleClassCoveredParty CLAIM (claimant). However, a named insured may make a claim under a policy, e.g., a party that is the named insured and policy holder under a comprehensive automobile insurance policy may become the claimant for coverage under that policy if injured in an automobile accident and there is no liable third party. In the case of an individual insured making a claim, a role type code INSCLM (insured claimant) subtypes the class to indicate that an individual insured has filed a claim for a loss. Example: The individual insured under a comprehensive automobile, disability, or property and casualty policy that is the policy holder.

7 | SUBSCR | subscriber | Description: A role played by a person covered under a policy based on association with a sponsor who is the policy holder, and whose association may provide for the eligibility of dependents for coverage. Discussion: The policy holder holds the contract with the policy or program underwriter. The subscriber holds a certificate of coverage under the contract. In legal proceedings concerning the policy or program, the terms of the contract takes precedence over the terms of the certificate of coverage if there are any inconsistencies. Note: The party playing the role of a subscriber is not a claimant in the sense conveyed by the RoleClassCoveredParty CLAIM (claimant). However, a subscriber may make a claim under a policy, e.g., a subscriber under a health insurance policy may become the claimant for coverage under that policy for wellness examines or if injured and there is no liable third party. In the case of a subscriber making a claim, a role type code INSCLM (insured claimant) subtypes the class to indicate that the subscriber has filed a claim for services covered under the health insurance policy. Example: An employee or a member of an association.

6 | PROG | program eligible | Description: A role played by a party that meets the eligibility criteria for coverage under a program. A program eligible may be either a person, non-person living subject, or an organization, or a group of persons, non-person living subjects, or organizations. Discussion: A program as typically government administered coverage for parties determined eligible under the terms of the program. Note: The party playing a program eligible is not a claimant in the sense conveyed by the RoleClassCoveredParty CLAIM (claimant). However a program eligible may make a claim under program, e.g., an unemployed worker may claim benefits under an unemployment insurance program, but parties playing these covered

party role classes are not, for purposes of this vocabulary and in an effort to clearly distinguish role classes, considered claimants. In the case of a program eligible, a role type code INJWKR (injured worker) subtypes the class to indicate that the covered party in a workers compensation program is an injured worker, and as such, has filed a "claim" under the program for benefits. Likewise, a covered role type code UNEMP (unemployed worker) subtypes the program eligible class to indicate that the covered party in an unemployment insurance program has filed a claim for unemployment benefits. Example: A party meeting eligibility criteria related to health or financial status, e.g., in the U.S., persons meeting health, demographic, or financial criteria established by state and federal law are eligible for Medicaid.

5 | CRINV | clinical research investigator | A role played by a provider, always a person, who has agency authority from a Clinical Research Sponsor to direct the conduct of a clinical research trial or study on behalf of the sponsor.

5 | CRSPNSR | clinical research sponsor | A role played by an entity, usually an organization, that is the sponsor of a clinical research trial or study. The sponsor commissions the study, bears the expenses, is responsible for satisfying all legal requirements concerning subject safety and privacy, and is generally responsible for collection, storage and analysis of the data generated during the trial. No scoper is necessary, as a clinical research sponsor undertakes the role on its own authority and declaration. Clinical research sponsors are usually educational or other research organizations, government agencies or biopharmaceutical companies.

5 | EMP | employee | A relationship between a person or organization and a person or organization formed for the purpose of exchanging work for compensation. The purpose of the role is to identify the type of relationship the employee has to the employer, rather than the nature of the work actually performed. (Contrast with AssignedEntity.)

6 | MIL | military person | A role played by a member of a military service. Scoper is the military service (e.g. Army, Navy, Air Force, etc.) or, more specifically, the unit (e.g. Company C, 3rd Battalion, 4th Division, etc.)

5 | GUAR | guarantor | A person or organization (player) that serves as a financial guarantor for another person or organization (scoper).

5 | INVSBJ | Investigation Subject | An entity that is the subject of an investigation. This role is scoped by the party responsible for the investigation.

6 | CASEBJ | Case Subject | A person, non-person living subject, or place that is the subject of an investigation related to a notifiable condition (health circumstance that is reportable within the applicable public health jurisdiction)

6 | RESBJ | research subject | Definition:Specifies the administrative functionality within a formal experimental design for which the ResearchSubject role was established. Examples: Screening - role is used for pre-enrollment evaluation portion of the design; enrolled - role is used for subjects admitted to the experimental portion of the design.

5 | LIC | licensed entity | A relationship in which the scoper certifies the player (e. g. a medical care giver, a medical device or a provider organization) to perform certain activities that fall under the jurisdiction of the scoper (e.g., a health authority licensing healthcare providers, a medical quality authority certifying healthcare professionals).

6 | NOT | notary public

6 | PROV | healthcare provider | An Entity (player) that is authorized to provide health care services by some authorizing agency (scoper).

5 | PAT | patient | A Role of a LivingSubject (player) as an actual or potential recipient of health care services from a healthcare provider organization (scoper). Usage Note: Communication about relationships between patients and specific healthcare practitioners (people) is not done via scoper. Instead this is generally done using the CareProvision act. This allows linkage between patient and a particular healthcare practitioner role and also allows description of the type of care involved in the relationship.

5 | PAYEE | payee | The role of an organization or individual designated to receive payment for a claim against a particular coverage. The scoping entity is the organization that is the submitter of the invoice in question.

5 | PAYOR | invoice payor | The role of an organization that undertakes to accept claims invoices, assess the coverage or payments due for those invoices and pay to the designated payees for those invoices. This role may be either the underwriter or a third-party organization authorized by the underwriter. The scoping entity is the organization that underwrites the claimed coverage.

5 | POLHOLD | policy holder | A role played by a person or organization that holds an insurance policy. The underwriter of that policy is the scoping entity. Discussion:The identifier of the policy is captured in 'Role.id' when the Role is a policy holder. A particular policy may cover several individuals one of whom may be, but need not be, the policy holder. Thus the notion of covered party is a role that is distinct from that of the policy holder.

5 | QUAL | qualified entity | An entity (player) that has been recognized as having certain training/experience or other characteristics that would make said entity an appropriate performer for a certain activity. The scoper is an organization that educates or qualifies entities.

5 | SPNSR | coverage sponsor | A role played by an entity, usually an organization that is the sponsor of an insurance plan or a health program. A sponsor is the party that is ultimately accountable for the coverage by employment contract or by law. A sponsor can be an employer, union, government agency, or association. Fully insured sponsors establish the terms of the plan and contract with health insurance plans to assume the risk and to administer the plan. Self-insured sponsors delegate coverage administration, but not risk, to third-party administrators. Program sponsors designate services to be covered in accordance with statute. Program sponsors may administer the coverage themselves, delegate coverage administration, but not risk to third-party administrators, or contract with health insurance plans to assume the risk and administrator a program. Sponsors qualify individuals who may become a policy holder of the plan; where the sponsor is the policy holder, who may become a subscriber or a dependent to a policy under the plan; or where the sponsor is a government agency, who may become program eligibles under a program. The sponsor role may be further qualified by the SponsorRole.code. Entities playing the sponsor role may also play the role of a Coverage Administrator. Example: An employer, union, government agency, or association.

5 | STD | student | A role played by an individual who is a student of a school, which is the scoping entity.

5 | UNDWRT | underwriter | A role played by a person or an organization. It is the party that accepts fiscal responsibility for insurance plans and the policies created under those plans; administers and accepts fiscal responsibility for a program that provides coverage for services to eligible individuals; and/or has the responsibility to assess the merits of each risk and decide a suitable premium for accepting all or part of the risk. If played by an organization, this role may be further specified by an appropriate RoleCode. Example: A health insurer; Medicaid Program; Lloyd's of London

4 | CAREGIVER | caregiver | A person responsible for the primary care of a patient at home.

4 | PRS | personal relationship | Links two entities with classCode PSN (person) in a personal relationship. The character of the relationship must be defined by a PersonalRelationshipRoleType code. The player and scoper are determined by PersonalRelationshipRoleType code as well.

4 | SELF | self | The "same" roleclass asserts an identity between playing and scoping entities: that they are in fact instances of the same entity and, in the case of discrepancies (e.g different DOB, gender), that one or both are in error. Usage: playing and scoping entities must have same classcode, but need not have identical attributes or values. Example: a provider registry maintains sets of conflicting demographic data for what is reported to be the same individual.

3 | (_RoleClassPassive) Abstract | | An association for a playing Entity that is used, known, treated, handled, built, or destroyed, etc. under the auspices of the scoping Entity. The playing Entity is passive in these roles (even though it may be active in other roles), in the sense that the kinds of things done to it in this role happen without an agreement from the playing Entity.

4 | ACCESS | access | A role in which the playing entity (material) provides access to another entity. The principal use case is intravenous (or other bodily) access lines that preexist and need to be referred to for medication routing instructions.

4 | ADJY | adjacency | A physical association whereby two Entities are in some (even lose) spatial relationship with each other such that they touch each other in some way. Examples: the colon is connected (and therefore adjacent) to the jejunum; the colon is adjacent to the liver (even if not actually connected.) UsageConstraints: Adjacency is in principle a symmetrical connection, but scoper and player of the role should, where applicable, be assigned to have scoper be the larger, more central Entity and player the smaller, more distant, appendage.

5 | CONC | connection | An adjacency of two Entities held together by a bond which attaches to each of the two entities. Examples: biceps brachii muscle connected to the radius bone, port 3 on a network switch connected to port 5 on a patch panel. UsageConstraints: See Adjacency for the

assignment of scoper (larger, more central) and player (smaller, more distant).

6 | BOND | molecular bond | A connection between two atoms of a molecule. Examples: double bond between first and second C in ethane, peptide bond between two amino-acid, disulfide bridge between two proteins, chelate and ion associations, even the much weaker van-der-Waals bonds can be considered molecular bonds. UsageConstraints: See connection and adjacency for the assignment of player and scoper.

6 | CONY | continuity | A connection between two regional parts. Examples: the connection between ascending aorta and the aortic arc, connection between descending colon and sigmoid. UsageConstraints: See connection and adjacency for the assignment of player and scoper.

4 | ADMM | Administerable Material | A material (player) that can be administered to an Entity (scoper).

4 | BIRTHPL | birthplace | Relates a place (playing Entity) as the location where a living subject (scoping Entity) was born.

4 | DEATHPLC | place of death | Definition: Relates a place (playing Entity) as the location where a living subject (scoping Entity) died.

4 | DST | distributed material | A material (player) distributed by a distributor (scoper) who functions between a manufacturer and a buyer or retailer.

5 | RET | retailed material | Material (player) sold by a retailer (scoper), who also give advice to prospective buyers.

4 | EXLOC | event location | A role played by a place at which the location of an event may be recorded.

5 | SDLOC | service delivery location | A role played by a place at which services may be provided.

6 | DSDLOC | dedicated service delivery location | A role of a place (player) that is intended to house the provision of services. Scoper is the Entity (typically Organization) that provides these services. This is not synonymous with "ownership."

6 | ISDLOC | incidental service delivery location | A role played by a place at which health care services may be provided without prior designation or authorization.

4 | EXPR | exposed entity | A role played by an entity that has been exposed to a person or animal suffering a contagious disease, or with a location from which a toxin has been distributed. The player of the role is normally a person or animal, but it is possible that other entity types could become exposed. The role is scoped by the source of the exposure, and it is quite possible for a person playing the role of exposed party to also become the scoper a role played by another person. That is to say, once a person has become infected, it is possible, perhaps likely, for that person to infect others. Management of exposures and tracking exposed parties is a key function within public health, and within most public health contexts - exposed parties are known as "contacts."

4 | HLD | held entity | Entity that is currently in the possession of a holder (scoper), who holds, or uses it, usually based on some agreement with the owner.

4 | HLTHCHRT | health chart | The role of a material (player) that is the physical health chart belonging to an organization (scoper).

4 | IDENT | identified entity | A role in which the scoping entity designates an identifier for a playing entity.

4 | MANU | manufactured product | Scoped by the manufacturer

5 | THER | therapeutic agent | A manufactured material (player) that is used for its therapeutic properties. The manufacturer is the scoper.

4 | MNT | maintained entity | An entity (player) that is maintained by another entity (scoper). This is typical role held by durable equipment. The scoper assumes responsibility for proper operation, quality, and safety.

4 | OWN | owned entity | An Entity (player) for which someone (scoper) is granted by law the right to call the material (player) his own. This entitles the scoper to make decisions about the disposition of that material.

4 | RGPR | regulated product | A product regulated by some governmentatl orgnization. The role is played by Material and scoped by Organization. Rationale: To support an entity clone used to identify the NDC number for a drug product.

4 | TERR | territory of authority | Relates a place entity (player) as the region over which the scoper (typically an Organization) has certain authority (jurisdiction). For example, the Calgary Regional Health Authority (scoper) has authority over the territory "Region 4 of Alberta" (player) in matters of health.

4 | USED | used entity | Description:An entity (player) that is used by another entity (scoper)

4 | WRTE | warranted product | A role a product plays when a guarantee is given to the purchaser by the seller (scoping entity) stating that the product is reliable and free from known defects and that the seller will repair or replace defective parts within a given time limit and under certain conditions.

2 | (_RoleClassOntological) Abstract | | A relationship in which the scoping Entity defines or specifies what the playing Entity is. Thus, the player's "being" (Greek: ontos) is specified.

3 | EQUIV | equivalent entity | Description: Specifies the player Entity (the equivalent Entity) as an Entity that is considered to be equivalent to a reference Entity (scoper). The equivalence is in principle a symmetric relationship, however, it is expected that the scoper is a reference entity which serves as reference entity for multiple different equivalent entities. Examples: An innovator's medicine formulation is the reference for "generics", i.e., formulations manufactured differently but having been proven to be biologically equivalent to the reference medicine. Another example is a reference ingredient that serves as basis for quantity specifications (basis of strength, e.g., metoprolol succinate specified in terms of metoprolol tartrate.)

4 | SAME | same | The "same" role asserts an identity between playing and scoping entities, i.e., that they are in fact two records of the same entity instance, and, in the case of discrepancies (e.g different DOB, gender), that one or both are in error. Usage: playing and scoping entities must have same classCode, but need not have identical attributes or values. Example: a provider registry maintains sets of conflicting demographic data for what is reported to be the same individual.

4 | SUBY | subsumed by | Relates a prevailing record of an Entity (scoper) with another record (player) that it subsumes. Examples: Show a correct new Person object (scoper) that subsumes one or more duplicate Person objects that had accidentally been created for the same physical person. Constraints: Both the player and scoper must have the same classCode.

3 | GEN | has generalization | Relates a specialized material concept (player) to its generalization (scoper).

4 | GRIC | has generic | A special link between pharmaceuticals indicating that the target (scoper) is a generic for the source (player).

3 | INST | instance | An individual piece of material (player) instantiating a class of material (scoper).

3 | SUBS Deprecated | subsumer | An entity that subsumes the identity of another. Used in the context of merging documented entity instances. Both the player and scoper must have the same classCode. The use of this code is deprecated in favor of the term SUBY which is its inverse and is more ontologically correct.

2 | (_RoleClassPartitive) Abstract | | An association between two Entities where the playing Entity is considered in some way "part" of the scoping Entity, e.g., as a member, component, ingredient, or content. Being "part" in the broadest sense of the word can mean anything from being an integral structural component to a mere incidental temporary association of a playing Entity with a (generally larger) scoping Entity.

3 | CONT | content | Relates a material as the content (player) to a container (scoper). Unlike ingredients, the content and a container remain separate (not mixed) and the content can be removed from the container. A content is not part of an empty container.

3 | EXPAGTCAR | exposure agent carrier | An exposure agent carrier is an entity that is capable of conveying an exposure agent from one entity to another. The scoper of the role must be the exposure agent (e.g., pathogen).

4 | EXPVECTOR | exposure vector | Description: A vector is a living subject that carries an exposure agent. The vector does not cause the disease itself, but exposes targets to the exposure agent. A mosquito carrying malaria is an example of a vector. The scoper of the role must be the exposure agent (e.g., pathogen).

4 | FOMITE | fomite | Description: A fomite is a non-living entity that is capable of conveying exposure agent from one entity to another. A doorknob contaminated with a Norovirus is an example of a fomite. Anyone touching the doorknob would be exposed to the virus. The scoper of the role must be the exposure agent (e.g., pathogen).

3 | INGR | ingredient | Relates a component (player) to a mixture (scoper). E.g., Glucose and Water are ingredients of D5W, latex may be an ingredient in a tracheal tube.

4 | ACTI | active ingredient | Definition: a therapeutically active ingredient (player) in a mixture (scoper), where the mixture is typically a manufactured pharmaceutical. It is unknown if the quantity of such an ingredient is expressed precisely in terms of the playing ingredient substance, or, if it is specified in terms of a closely related substance (active moiety or reference substance).

5 | ACTIB | active ingredient - basis of strength | Description: Active ingredient, where the ingredient substance (player) is itself the "basis of strength", i.e., where the Role.quantity specifies exactly the quantity of the player substance in the medicine formulation. Examples: Lopressor 50 mg actually contains 50 mg of metoprolol succinate, even though the active moiety is metoprolol, but also: Tenormin 50 mg contain 50 mg of atenolol, as free base, i.e., where the active ingredient atenolol is also the active moiety.

5 | ACTIM | active ingredient - moiety is basis of strength | Description: Active ingredient, where not the ingredient substance (player), but itaTMs active moiety is the "basis of strength", i.e., where the Role.quantity specifies the quantity of the player substance's active moiety in the medicine formulation. Examples: 1 mL of Betopic 5mg/mL eye drops contains 5.6 mg betaxolol hydrochloride equivalent to betaxolol base 5 mg.

5 | ACTIR | active ingredient - reference substance is basis of strength | Description: Active ingredient, where not the ingredient substance (player) but another reference substance with the same active moiety, is the "basis of strength", i.e., where the Role.quantity specifies the quantity of a reference substance, similar but different from the player substance's in the medicine formulation. Examples: Toprol-XL 50 mg contains 47.5 mg of metoprolol succinate equivalent to 50 mg of metoprolol tartrate.

4 | ADJV | adjuvant | A component (player) added to enhance the action of an active ingredient (scoper) (in the manner of a catalyst) but which has no active effect in and of itself. Such ingredients are significant in defining equivalence of products in a way that inactive ingredients are not.

4 | ADTV | additive | An ingredient (player) that is added to a base (scoper), that amounts to a minor part of the overall mixture.

4 | BASE | base | A base ingredient (player) is what comprises the major part of a mixture (scoper). E.g., Water in most i.v. solutions, or Vaseline in salves. Among all ingredients of a material, there should be only one base. A base substance can, in turn, be a mixture.

4 | CNTM | contaminant ingredient | An ingredient whose presence is not intended but may not be reasonably avoided given the circumstances of the mixture's nature or origin.

4 | IACT | inactive ingredient | An ingredient which is not considered therapeutically active, e.g., colors, flavors, stabilizers, or preservatives, fillers, or structural components added to an active ingredient in order to facilitate administration of the active ingredient but without being considered therapeutically active. An inactive ingredient need not be biologically inert, e.g., might be active as an allergen or might have a pleasant taste, but is not an essential constituent delivering the therapeutic effect.

5 | COLR | color additive | A substance (player) influencing the optical aspect of material (scoper).

5 | FLVR | flavor additive | A substance (player) added to a mixture (scoper) to make it taste a certain way. In food the use is obvious, in pharmaceuticals flavors can hide disgusting taste of the active ingredient (important in pediatric treatments).

5 | PRSV | preservative | A substance (player) added to a mixture (scoper) to prevent microorganisms (fungi, bacteria) to spoil the mixture.

5 | STBL | stabilizer | A stabilizer (player) added to a mixture (scoper) in order to prevent the molecular disintegration of the main substance.

4 | MECH | mechanical ingredient | An ingredient (player) of a medication (scoper) that is inseparable from the active ingredients, but has no intended chemical or pharmaceutical effect itself, but which may have some systemic effect on the patient. An example is a collagen matrix used as a base for transplanting skin cells. The collagen matrix can be left permanently in the graft site. Because it is of bovine origin, the patient may exhibit allergies or may have cultural objections to its use.

3 | LOCE | located entity | Relates an entity (player) to a location (scoper) at which it is present in some way. This presence may be limited in time.

4 | STOR | stored entity | Relates an entity (player) (e.g. a device) to a location (scoper) at which it is normally found or stored when not used.

3 | MBR | member | A role played by an entity that is a member of a group. The group provides the scope for this role. Among other uses, groups as used in insurance (groups of covered individuals) and in scheduling where resources may be grouped for scheduling and logistical purposes.

3 | PART | part | Definition: an association between two Entities where the playing Entity (the part) is a component of the whole (scoper) in the sense of an integral structural component, that is distinct from other parts in the same whole, has a distinct function in the whole, and, as an effect, the full integrity of the whole depends (to some degree) on the presence of this part, even though the part may often be separable from the whole. Discussion: Part is defined in opposition to (a) ingredient (not separable), (b) content (not a functional component), and (c) member (not functionally distinct from other members).

4 | ACTM | active moiety | The molecule or ion that is responsible for the intended pharmacological action of the drug substance, excluding those appended or associated parts of the molecule that make the molecule an ester, salt (including a salt with hydrogen or coordination bonds), or other noncovalent derivative (such as a complex, chelate, or clathrate). Examples: heparin-sodium and heparin-potassium have the same active moiety, heparin; the active moiety of morphine-hydrochloride is morphine.

3 | SPEC | specimen | A role played by a material entity that is a specimen for an act. It is scoped by the source of the specimen.

4 | ALQT | aliquot | A portion (player) of an original or source specimen (scoper) used for testing or transportation.

4 | ISLT | isolate | A microorganism that has been isolated from other microorganisms or a source matrix.

1 | CHILD | child | The player of the role is a child of the scoping entity, in a generic sense.

1 | CRED | credentialed entity | A role played by an entity that receives credentials from the scoping entity.

1 | NURPRAC | nurse practitioner

1 | NURS | nurse

1 | PA | physician assistant

1 | PHYS | physician

4.3.2.111 HL7 v3 Code System RoleCode

URL: https://hl7.org/fhir/STU3/v3/RoleCode/cs.html

This page is part of the FHIR Specification (v3.0.2: STU 3). The current version which supercedes this version is 4.0.1. For a full list of available versions, see the Directory of published versions

Vocabulary Work Group | Maturity Level: N/A | External | Use Context: Any

This code system (http://hl7.org/fhir/v3/RoleCode) is defined as part of HL7 v3.

Summary

Defining URL: | http://hl7.org/fhir/v3/RoleCode

Name: | v3 Code System RoleCode

Definition: | A set of codes further specifying the kind of Role; specific classification codes for further qualifying RoleClass codes.

OID: | 2.16.840.1.113883.5.111 (for OID based terminology systems)

Source Resource | XML / JSON

This Code system is used in the following value sets:

* ServiceDeliveryLocationRoleType (A role of a place that further classifies the setting (e.g., accident site, road side, work site, community location) in which services are delivered.)

* Parent Relationship Codes (The value set includes the v3 RoleCode PRN (parent), TWIN (twin) and all of their specializations. It covers the relationships needed to establish genetic pedigree relationships between family members.)

* Sibling Relationship Codes (The value set includes the v3 RoleCode SIB (sibling) and all of its specializations. It covers the relationships needed to establish genetic pedigree relationships between family members.)

* PatientRelationshipType (A set of codes that can be used to indicate the relationship between a Patient and a Related Person.)

* Focal Subject Codes (Example VS composed from SNOMED CT and HL7 v3 codes for observation targets: donor, fetus, spouse. As use cases are discovered more values may be added.)

* v3 Code System RoleCode (A set of codes further specifying the kind of Role; specific classification codes for further qualifying RoleClass codes.)

* MilitaryRoleType (Definition: A person playing the role of program eligible under a program based on military status. Discussion: This CoveredPartyRoleType.code is typically used when the CoveredPartyRole class code is either "program eligible" or "subscriber" and the person's status as a member of the military meets jurisdictional or program criteria)

* PersonalRelationshipRoleType (Types of personal relationships between two living subjects. Example: Parent, sibling, unrelated friend, neighbor)

* FamilyMember (A relationship between two people characterizing their "familial" relationship)

4.3.2.111.1 Code System Content

Release Date: 2016-11-11

Level | Code | Display | Definition

1 | (_AffiliationRoleType) Abstract | | Concepts characterizing the type of association formed by player and scoper when there is a recognized Affiliate role by which the two parties are related. Examples: Business Partner, Business Associate, Colleague

2 | (_AgentRoleType) Abstract | | Parties that may or should contribute or have contributed to an Act.

3 | AMENDER | amender | An entity which corrected, edited, or amended pre-existing information.

3 | CLASSIFIER | classifier | An individual authorized to assign an original classification to information, including compilations of unclassified information, based on a determination that the information requires protection against unauthorized disclosure. The individual marks the information with immutable, computable, and human readable security labels in accordance with applicable security labeling policies. The labeling policies provide instructions on whether and if so how the security labels may be later reclassified [i.e., upgraded, downgraded, used in derivative classification, or declassified] in a manner that preserves the overridden original classification binding and provenance.

3 | CONSENTER | consenter | An entity or an entity's delegatee who is the grantee in an agreement such as a consent for services, advanced directive, or a privacy consent directive in accordance with jurisdictional, organizational, or patient policy.

3 | CONSWIT | consent witness | An entity which has witnessed and attests to observing another entity being counseled about an agreement such as a consent for services, advanced directive, or a privacy consent directive.

3 | COPART | co-participant | An entity which participates in the generation of and attest to veracity of content, but is not an author or coauthor. For example a surgeon who is required by institutional, regulatory, or legal rules to sign an operative report, but who was not involved in the authorship of that report.

3 | DECLASSIFIER | declassifier | An individual which is authorized to declassify information based on a determination that the information no longer requires protection against unauthorized disclosure. The individual marks the information being declassified using computable and human readable security labels indicating that this is copy of previously classified information is unclassified in accordance with applicable security labeling policies. The labeling policies provide instructions on whether and if so how the security labels may be later reclassified [i.e., upgraded or used in derivative classification] in a manner that preserves the overridden original classification binding and provenance.

3 | DELEGATEE | delegatee | A party to whom some right or authority is granted by a delegator.

3 | DELEGATOR | delegator | A party that grants all or some portion its right or authority to another party.

3 | DOWNGRDER | downgrader | An individual authorized to lower the classification level of labeled content and provide rationale for doing so as directed by a classification guide.

3 | DRIVCLASSIFIER | derivative classifier | An individual who is only authorized to classify reproduced, extracted, or summarized classified information, or compile classified and unclassified information by applying classification markings derived from source material or as directed by a classification guide.

3 | GRANTEE | grantee | An entity which accepts certain rights or authority from a grantor.

3 | GRANTOR | grantor | An entity which agrees to confer certain rights or authority to a grantee.

3 | INTPRTER | interpreter | An entity which converts spoken or written language into the language of key participants in an event such as when a provider is obtaining a patient's consent to treatment or permission to disclose information.

3 | REVIEWER | reviewer | An entity authorized to filter information according to approved criteria.

3 | VALIDATOR | validator | An entity authorized to validate information for inclusion in a record.

2 | (_CoverageSponsorRoleType) Abstract | | Description:Codes that indicate a specific type of sponsor. Used when the sponsor's role is only either as a fully insured sponsor or only as a self-insured sponsor. NOTE: Where a sponsor may be either, use the SponsorParticipationFunction.code (fully insured or self insured) to indicate the type of responsibility. (CO6-0057)

3 | FULLINS | Fully insured coverage sponsor | Description:An employer or organization that contracts with an underwriter to assumes the financial risk and administrative responsibility for coverage of health services for covered parties.

3 | SELFINS | Self insured coverage sponsor | Description:An employer or organization that assumes the financial risk and administrative responsibility for coverage of health services for covered parties.

2 | (_PayorRoleType) Abstract | | Description:PayorRoleType for a particular type of policy or program benefit package or plan where more detail about the coverage administration role of the Payor is required. The functions performed by a Payor qualified by a PayorRoleType may be specified by the PayorParticpationFunction value set. Examples:A Payor that is a TPA may administer a managed care plan without underwriting the risk.

3 | ENROLBKR | Enrollment Broker | Description:A payor that is responsible for functions related to the enrollment of covered parties.

3 | TPA | Third party administrator | Description:Third party administrator (TPA) is a payor organization that processes health care claims without carrying insurance risk. Third party administrators are prominent players in the managed care industry and have the expertise and capability to administer all or a portion of the claims process. They are normally contracted by a health insurer or self-insuring companies to administer services, including claims administration, premium collection, enrollment and other administrative activities. Self-insured employers often contract with third party administrator to handle their insurance functions. Insurance companies oftentimes outsource the claims, utilization review or membership functions to a TPA. Sometimes TPAs only manage provider networks, only claims or only utilization review. While some third-party administrators may operate as units of insurance companies, they are often independent. However, hospitals or provider organizations desiring to set up their own health plans will often outsource certain responsibilities to TPAs. TPAs may perform one or several payor functions, specified by the PayorParticipationFunction value set, such as provider management, enrollment, utilization management, and fee for service claims adjudication management.

3 | UMO | Utilization management organization | Description:A payor that is responsible for review and case management of health services covered under a policy or program.

2 | RESPRSN | responsible party | The role played by a party who has legal responsibility for another party.

3 | EXCEST | executor of estate | The role played by a person acting as the estate executor for a deceased subscriber or policyholder who was the responsible party

3 | GUADLTM | guardian ad lidem | The role played by a person appointed by the court to look out for the best interests of a minor child during the course of legal proceedings.

3 | GUARD | guardian | The role played by a person or institution legally empowered with responsibility for the care of a ward.

3 | POWATT | power of attorney | A relationship between two people in which one person authorizes another to act for him in a manner which is a legally binding upon the person giving such authority as if he or she personally were to do the acts.

4 | DPOWATT | durable power of attorney | A relationship between two people in which one person authorizes another, usually a family member or relative, to act for him or her in a manner which is a legally binding upon the person giving such authority as if he or she personally were to do the acts that is often limited in the kinds of powers that can be assigned. Unlike ordinary powers of attorney, durable powers can survive for long periods of time, and again, unlike standard powers of attorney, durable powers can continue after incompetency.

4 | HPOWATT | healthcare power of attorney | A relationship between two people in which one person authorizes another to act for him or her in a manner which is a legally binding upon the person giving such authority as if he or she personally were to do the acts that continues (by its terms) to be effective even though the grantor has become mentally incompetent after signing the document.

4 | SPOWATT | special power of attorney | A relationship between two people in which one person authorizes another to act for him or her in a manner which is a legally binding upon the person giving such authority as if he or she personally were to do the acts that is often limited in the kinds of powers that can be assigned.

1 | (_AssignedRoleType) Abstract

2 | (_AssignedNonPersonLivingSubjectRoleType) Abstract | | Description:A role type that is used to further qualify a non-person subject playing a role where the role class attribute is set to RoleClass AssignedEntity

3 | ASSIST | Assistive non-person living subject | Description:Dogs trained to assist the ill or physically challenged.

3 | BIOTH | Biotherapeutic non-person living subject | Description:Animals, including fish and insects, and microorganisms which may participate as assigned entities in biotherapies.

4 | ANTIBIOT | Antibiotic | Description:Non-person living subject used as antibiotic. Examples:Bacteriophage, is a virus that infects bacteria.

4 | DEBR | Debridement | Description:Maggots raised for biodebridement. Discussion: Maggot Debridement Therapy is the medical use of live maggots for cleaning non-healing wounds. Examples:Removal of burnt skin.

3 | CCO | Clinical Companion | Description:Companion animals, such as dogs, cats, and rabbits, which may be provided to patients to improve general mood, decrease depression and loneliness, and distract from stress-inducing concerns to improve quality of life.

3 | SEE | Seeing | Description:Dogs trained to assist persons who are seeing impaired or blind.

3 | SNIFF | Sniffing | Description:Dogs trained or having the ability to detect imminent seizures or cancers in humans, probably as a result of volatile chemical (odors) given off by the malignancy of the host.

1 | (_CertifiedEntityType) Abstract | | Defines types of certifications for all entities

1 | _CitizenRoleType | CitizenRoleType | A role type used to qualify a person's legal status within a country or nation.

2 | CAS | asylum seeker | A person who has fled his or her home country to find a safe place elsewhere.

3 | CASM | single minor asylum seeker | A person who is someone of below legal age who has fled his or her home country, without his or her parents, to find a safe place elsewhere at time of categorization.

2 | CN | national | A person who is legally recognized as a member of a nation or country, with associated rights and obligations.

2 | CNRP | non-country member without residence permit | A foreigner who is present in a country (which is foreign to him/her) unlawfully or without the country's authorization (may be called an illegal alien).

3 | CNRPM | non-country member minor without residence permit | A person who is below legal age present in a country, without his or her parents, (which is foreign to him/her) unlawfully or without the country's authorization.

2 | CPCA | permit card applicant | A non-country member admitted to the territory of a nation or country as a non-resident for an explicit purpose.

2 | CRP | non-country member with residence permit | A foreigner who is a resident of the country but does not have citizenship.

3 | CRPM | non-country member minor with residence permit | A person who is a resident below legal age of the country without his or her parents and does not have citizenship.

1 | (_ContactRoleType) Abstract | | Types of contact for Role code "CON"

2 | (_AdministrativeContactRoleType) Abstract | | A contact role used for business and/or administrative purposes.

3 | BILL | Billing Contact | A contact role used to identify a person within a Provider organization that can be contacted for billing purposes (e.g. about the content of the Invoice).

3 | ORG | organizational contact | A contact for an organization for administrative purposes. Contact role specifies a person acting as a liason for the organization. Example: HR Department representative.

3 | PAYOR | Payor Contact | A contact role used to identify a person within a Payor organization to whom this communication is addressed.

2 | ECON Deprecated | emergency contact | A contact designated for contact in emergent situations.

2 | NOK Deprecated | next of kin | Played by an individual who is designated as the next of kin for another individual which scopes the role.

1 | (_IdentifiedEntityType) Abstract | | Definition: A code representing the type of identifier that has been assigned to the identified entity (IDENT). Examples: Example values include Social Insurance Number, Product Catalog ID, Product Model Number.

2 | (_LocationIdentifiedEntityRoleCode) Abstract | | Description:Describes types of identifiers other than the primary location registry identifier for a service delivery location. Identifiers may be assigned by a local service delivery organization, a formal body capable of accrediting the location for the capability to provide specific services or the identifier may be assigned at a jurisdictional level.

3 | ACHFID | accreditation location identifier | Description:Identifier assigned to a location by the organization responsible for accrediting the location.

3 | JURID | jurisdiction location identifier | Description:Identifier assigned to a location by a jurisdiction.

3 | LOCHFID | local location identifier | Description:Identifier assigned to a location by a local party (which could be the facility itself or organization overseeing a group of facilities).
1 | (_LivingSubjectProductionClass) Abstract | | Code indicating the primary use for which a living subject is bred or grown
2 | BF | Beef | Cattle used for meat production
2 | BL | Broiler | Chickens raised for meat
2 | BR | Breeder | Breeding/genetic stock
2 | CO | Companion | Companion animals
2 | DA | Dairy | Milk production
2 | DR | Draft | Draft animals
2 | DU | Dual | Dual purpose. Defined purposes based on species and breed
2 | FI | Fiber | Animals raised for their fur, hair or skins
2 | LY | Layer | Chickens raised for egg production
2 | MT | Meat | Animals raised for meat production
2 | MU | Multiplier | Poultry flocks used for chick/poult production
2 | PL | Pleasure | Animals rasied for recreation
2 | RC | Racing | Animals raised for racing perfomance
2 | SH | Show | Animals raised for shows
2 | VL | Veal | Cattle raised for veal meat production. Implicit is the husbandry method.
2 | WL | Wool | Sheep, goats and other mammals raised for their fiber
2 | WO | Working | Animals used to perform work
1 | (_MedicationGeneralizationRoleType) Abstract | | Identifies the specific hierarchical relationship between the playing and scoping medications. Examples: Generic, Generic Formulation, Therapeutic Class, etc.
2 | DC | therapeutic class | Description:A categorization of medicinal products by their therapeutic properties and/or main therapeutic use.
2 | GD | generic drug | Relates a manufactured drug product to the non-proprietary (generic) representation of its ingredients independent of strength, and form. The scoping entity identifies a unique combination of medicine ingredients; sometimes referred to as "ingredient set".
3 | GDF | generic drug form | Relates a manufactured drug product to the non-proprietary (generic) representation of its ingredients and dose form, independent of strength of the ingredients. The scoping entity identifies a unique combination of medicine ingredients in a specific dose form.
3 | GDS | generic drug strength | Relates a manufactured drug product to the non-proprietary (generic) representation of is ingredients with their strength. The scoping entity identifies a unique combination of medicine ingredients with their strength.
3 | GDSF | generic drug strength form | Relates a manufactured drug product to the non-proprietary (generic) representation of its ingredients with their strength in a specific dose form. The scoping entity identifies a unique combination of medicine ingredients with their strength in a single dose form.
2 | MGDSF | manufactured drug strength form | Relates a manufactured drug product to the non-proprietary (generic) representation of its ingredients with their strength in a specific dose form. The scoping entity identifies a unique combination of medicine ingredients with their strength in a single dose form.
1 | (_MemberRoleType) Abstract | | Types of membership for Role code "MBR"
2 | TRB | Tribal Member | A person who is a member of a tribe.
1 | (_PersonalRelationshipRoleType) Abstract
2 | FAMMEMB | family member | A relationship between two people characterizing their "familial" relationship
3 | CHILD | child | The player of the role is a child of the scoping entity.
4 | CHLDADOPT | adopted child | The player of the role is a child taken into a family through legal means and raised by the scoping person (parent) as his or her own child.
5 | DAUADOPT | adopted daughter | The player of the role is a female child taken into a family through legal means and raised by the scoping person (parent) as his or her own child.
5 | SONADOPT | adopted son | The player of the role is a male child taken into a family through legal means and raised by the scoping person (parent) as his or her own child.
4 | CHLDFOST | foster child | The player of the role is a child receiving parental care and nurture from the scoping person (parent) but not related to him or her through legal or blood ties.
5 | DAUFOST | foster daughter | The player of the role is a female child receiving parental care and nurture from the scoping person (parent) but not related to him or her through legal or blood ties.
5 | SONFOST | foster son | The player of the role is a male child receiving parental care and nurture from the scoping person (parent) but not related to him or her through legal or blood ties.
4 | DAUC | daughter | Description: The player of the role is a female child (of any type) of scoping entity (parent)
5 | DAUADOPT
5 | DAUFOST
5 | DAU | natural daughter | The player of the role is a female offspring of the scoping entity (parent).
5 | STPDAU | stepdaughter | The player of the role is a daughter of the scoping person's spouse by a previous union.
4 | NCHILD | natural child | The player of the role is an offspring of the scoping entity as determined by birth.
5 | DAU
5 | SON | natural son | The player of the role is a male offspring of the scoping entity (parent).
4 | SONC | son | Description: The player of the role is a male child (of any type) of scoping entity (parent)
5 | SONADOPT
5 | SONFOST
5 | SON
5 | STPSON | stepson | The player of the role is a son of the scoping person's spouse by a previous union.
4 | STPCHLD | step child | The player of the role is a child of the scoping person's spouse by a previous union.
5 | STPDAU
5 | STPSON
3 | EXT | extended family member | Description: A family member not having an immediate genetic or legal relationship e.g. Aunt, cousin, great grandparent, grandchild, grandparent, niece, nephew or uncle.
4 | AUNT | aunt | The player of the role is a sister of the scoping person's mother or father.
5 | MAUNT | maternal aunt | Description:The player of the role is a biological sister of the scoping person's biological mother.
5 | PAUNT | paternal aunt | Description:The player of the role is a biological sister of the scoping person's biological father.

4 | COUSN | cousin | The player of the role is a relative of the scoping person descended from a common ancestor, such as a grandparent, by two or more steps in a diverging line.
5 | MCOUSN | maternal cousin | Description:The player of the role is a biological relative of the scoping person descended from a common ancestor on the player's mother's side, such as a grandparent, by two or more steps in a diverging line.
5 | PCOUSN | paternal cousin | Description:The player of the role is a biological relative of the scoping person descended from a common ancestor on the player's father's side, such as a grandparent, by two or more steps in a diverging line.
4 | GGRPRN | great grandparent | The player of the role is a parent of the scoping person's grandparent.
5 | GGRFTH | great grandfather | The player of the role is the father of the scoping person's grandparent.
6 | MGGRFTH | maternal great-grandfather | Description:The player of the role is the biological father of the scoping person's biological mother's parent.
6 | PGGRFTH | paternal great-grandfather | Description:The player of the role is the biological father of the scoping person's biological father's parent.
5 | GGRMTH | great grandmother | The player of the role is the mother of the scoping person's grandparent.
6 | MGGRMTH | maternal great-grandmother | Description:The player of the role is the biological mother of the scoping person's biological mother's parent.
6 | PGGRMTH | paternal great-grandmother | Description:The player of the role is the biological mother of the scoping person's biological father's parent.
5 | MGGRPRN | maternal great-grandparent | Description:The player of the role is a biological parent of the scoping person's biological mother's parent.
6 | MGGRFTH
6 | MGGRMTH
5 | PGGRPRN | paternal great-grandparent | Description:The player of the role is a biological parent of the scoping person's biological father's parent.
6 | PGGRFTH
6 | PGGRMTH
4 | GRNDCHILD | grandchild | The player of the role is a child of the scoping person's son or daughter.
5 | GRNDDAU | granddaughter | The player of the role is a daughter of the scoping person's son or daughter.
5 | GRNDSON | grandson | The player of the role is a son of the scoping person's son or daughter.
4 | GRPRN | grandparent | The player of the role is a parent of the scoping person's mother or father.
5 | GRFTH | grandfather | The player of the role is the father of the scoping person's mother or father.
6 | MGRFTH | maternal grandfather | Description:The player of the role is the biological father of the scoping person's biological mother.
6 | PGRFTH | paternal grandfather | Description:The player of the role is the biological father of the scoping person's biological father.
5 | GRMTH | grandmother | The player of the role is the mother of the scoping person's mother or father.
6 | MGRMTH | maternal grandmother | Description:The player of the role is the biological mother of the scoping person's biological mother.
6 | PGRMTH | paternal grandmother | Description:The player of the role is the biological mother of the scoping person's biological father.
5 | MGRPRN | maternal grandparent | Description:The player of the role is the biological parent of the scoping person's biological mother.
6 | MGRFTH
6 | MGRMTH
5 | PGRPRN | paternal grandparent | Description:The player of the role is the biological parent of the scoping person's biological father.
6 | PGRFTH
6 | PGRMTH
4 | INLAW | inlaw | A relationship between an individual and a member of their spousal partner's immediate family.
5 | CHLDINLAW | child-in-law | The player of the role is the spouse of scoping person's child.
6 | DAUINLAW | daughter in-law | The player of the role is the wife of scoping person's son.
6 | SONINLAW | son in-law | The player of the role is the husband of scoping person's daughter.
5 | PRNINLAW | parent in-law | The player of the role is the parent of scoping person's husband or wife.
6 | FTHINLAW | father-in-law | The player of the role is the father of the scoping person's husband or wife.
6 | MTHINLAW | mother-in-law | The player of the role is the mother of the scoping person's husband or wife.
5 | SIBINLAW | sibling in-law | The player of the role is: (1) a sibling of the scoping person's spouse, or (2) the spouse of the scoping person's sibling, or (3) the spouse of a sibling of the scoping person's spouse.
6 | BROINLAW | brother-in-law | The player of the role is: (1) a brother of the scoping person's spouse, or (2) the husband of the scoping person's sister, or (3) the husband of a sister of the scoping person's spouse.
6 | SISINLAW | sister-in-law | The player of the role is: (1) a sister of the scoping person's spouse, or (2) the wife of the scoping person's brother, or (3) the wife of a brother of the scoping person's spouse.
4 | NIENEPH | niece/nephew | The player of the role is a child of scoping person's brother or sister or of the brother or sister of the scoping person's spouse.
5 | NEPHEW | nephew | The player of the role is a son of the scoping person's brother or sister or of the brother or sister of the scoping person's spouse.
5 | NIECE | niece | The player of the role is a daughter of the scoping person's brother or sister or of the brother or sister of the scoping person's spouse.
4 | UNCLE | uncle | The player of the role is a brother of the scoping person's mother or father.
5 | MUNCLE | maternal uncle | Description:The player of the role is a biological brother of the scoping person's biological mother.
5 | PUNCLE | paternal uncle | Description:The player of the role is a biological brother of the scoping person's biological father.
3 | PRN | parent | The player of the role is one who begets, gives birth to, or nurtures and raises the scoping entity (child).
4 | ADOPTP | adoptive parent | The player of the role (parent) has taken the scoper (child) into their family through legal means and raises them as his or her own child.
5 | ADOPTF | adoptive father | The player of the role (father) is a male who has taken the scoper (child) into their family through legal means and raises them as his own child.
5 | ADOPTM | adoptive mother | The player of the role (father) is a female who has taken the scoper (child) into their family through legal means and raises them as her own child.
4 | FTH | father | The player of the role is a male who begets or raises or nurtures the scoping entity (child).
5 | ADOPTF
5 | FTHFOST | foster father | The player of the role (parent) who is a male state-certified caregiver responsible for the scoper (child) who has been placed in the parent's care. The placement of the child is usually arranged through the government or a social-service agency, and temporary. The

state, via a jurisdiction recognized child protection agency, stands as in loco parentis to the child, making all legal decisions while the foster parent is responsible for the day-to-day care of the specified child.
5 | NFTH | natural father | The player of the role is a male who begets the scoping entity (child).
6 | NFTHF | natural father of fetus | Indicates the biologic male parent of a fetus.
5 | STPFTH | stepfather | The player of the role is the husband of scoping person's mother and not the scoping person's natural father.
4 | MTH | mother | The player of the role is a female who conceives, gives birth to, or raises and nurtures the scoping entity (child).
5 | ADOPTM
5 | GESTM | gestational mother | The player is a female whose womb carries the fetus of the scoper. Generally used when the gestational mother and natural mother are not the same.
5 | MTHFOST | foster mother | The player of the role (parent) who is a female state-certified caregiver responsible for the scoper (child) who has been placed in the parent's care. The placement of the child is usually arranged through the government or a social-service agency, and temporary. The state, via a jurisdiction recognized child protection agency, stands as in loco parentis to the child, making all legal decisions while the foster parent is responsible for the day-to-day care of the specified child.
5 | NMTH | natural mother | The player of the role is a female who conceives or gives birth to the scoping entity (child).
6 | NMTHF | natural mother of fetus | The player is the biologic female parent of the scoping fetus.
5 | STPMTH | stepmother | The player of the role is the wife of scoping person's father and not the scoping person's natural mother.
4 | NPRN | natural parent
5 | NFTH
5 | NMTH
4 | PRNFOST | foster parent | The player of the role (parent) who is a state-certified caregiver responsible for the scoper (child) who has been placed in the parent's care. The placement of the child is usually arranged through the government or a social-service agency, and temporary. The state, via a jurisdiction recognized child protection agency, stands as in loco parentis to the child, making all legal decisions while the foster parent is responsible for the day-to-day care of the specified child.
5 | FTHFOST
5 | MTHFOST
4 | STPPRN | step parent | The player of the role is the spouse of the scoping person's parent and not the scoping person's natural parent.
5 | STPFTH
5 | STPMTH
3 | SIB | sibling | The player of the role shares one or both parents in common with the scoping entity.
4 | BRO | brother | The player of the role is a male sharing one or both parents in common with the scoping entity.
5 | HBRO | half-brother | The player of the role is a male related to the scoping entity by sharing only one biological parent.
5 | NBRO | natural brother | The player of the role is a male having the same biological parents as the scoping entity.
6 | TWINBRO | twin brother | The scoper was carried in the same womb as the male player and shares common biological parents.
7 | FTWINBRO | fraternal twin brother | The scoper was carried in the same womb as the male player and shares common biological parents but is the product of a distinct egg/sperm pair.
7 | ITWINBRO | identical twin brother | The male scoper is an offspring of the same egg-sperm pair as the male player.
5 | STPBRO | stepbrother | The player of the role is a son of the scoping person's stepparent.
4 | HSIB | half-sibling | The player of the role is related to the scoping entity by sharing only one biological parent.
5 | HBRO
5 | HSIS | half-sister | The player of the role is a female related to the scoping entity by sharing only one biological parent.
4 | NSIB | natural sibling | The player of the role has both biological parents in common with the scoping entity.
5 | NBRO
5 | NSIS | natural sister | The player of the role is a female having the same biological parents as the scoping entity.
6 | TWINSIS | twin sister | The scoper was carried in the same womb as the female player and shares common biological parents.
7 | FTWINSIS | fraternal twin sister | The scoper was carried in the same womb as the female player and shares common biological parents but is the product of a distinct egg/sperm pair.
7 | ITWINSIS | identical twin sister | The female scoper is an offspring of the same egg-sperm pair as the female player.
5 | TWIN | twin | The scoper and player were carried in the same womb and shared common biological parents.
6 | TWINBRO
6 | TWINSIS
6 | FTWIN | fraternal twin | The scoper and player were carried in the same womb and share common biological parents but are the product of distinct egg/sperm pairs.
7 | FTWINBRO
7 | FTWINSIS
6 | ITWIN | identical twin | The scoper and player are offspring of the same egg-sperm pair.
7 | ITWINBRO
7 | ITWINSIS
4 | SIS | sister | The player of the role is a female sharing one or both parents in common with the scoping entity.
5 | HSIS
5 | NSIS
5 | STPSIS | stepsister | The player of the role is a daughter of the scoping person's stepparent.
4 | STPSIB | step sibling | The player of the role is a child of the scoping person's stepparent.
5 | STPBRO
5 | STPSIS
3 | SIGOTHR | significant other | A person who is important to one's well being; especially a spouse or one in a similar relationship. (The player is the one who is important)
4 | DOMPART | domestic partner | The player of the role cohabits with the scoping person but is not the scoping person's spouse.
4 | FMRSPS | former spouse | Player of the role was previously joined to the scoping person in marriage and this marriage is now dissolved and inactive. Usage Note: This is significant to indicate as some jurisdictions have different legal requirements for former spouse to access the patient's record, from a general friend.
4 | SPS | spouse | The player of the role is a marriage partner of the scoping person.
5 | HUSB | husband | The player of the role is a man joined to a woman (scoping person) in marriage.
5 | WIFE | wife | The player of the role is a woman joined to a man (scoping person) in marriage.

2 | FRND | unrelated friend | The player of the role is a person who is known, liked, and trusted by the scoping person.

2 | NBOR | neighbor | The player of the role lives near or next to the scoping person.

2 | ONESELF | self | The relationship that a person has with his or her self.

2 | ROOM | Roommate | One who shares living quarters with the subject.

1 | (_PolicyOrProgramCoverageRoleType) Abstract | | Description: A role recognized through the eligibility of an identified party for benefits covered under an insurance policy or a program based on meeting eligibility criteria. Eligibility as a covered party may be conditioned on the party meeting criteria to qualify for coverage under a policy or program, which may be mandated by law. These criteria may be: The sole basis for coverage, e.g., being differently abled may qualify a person for disability coverage May more fully qualify a covered party role e.g, being differently abled may qualify an adult child as a dependent May impact the level of coverage for a covered party under a policy or program, e.g., being differently abled may qualify a program eligible for additional benefits. Discussion: The Abstract Value Set "CoverageRoleType", which was developed for use in the Canadian realm "pre-coordinate" coverage roles with other roles that a covered party must play in order to be eligible for coverage, e.g., "handicapped dependent". These role.codes may only be used with COVPTY to avoid overlapping concepts that would result from using them to specify the specializations of COVPTY, e.g., the role.class DEPEN should not be used with the role.code family dependent because that relationship has overlapping concepts due to the role.code precoodination and is conveyed in FICO with the personal relationship role that has a PART role link to the covered party role. For the same reasons, the role.class DEPEN should not be used with the role.code HANDIC (handicapped dependent); the role.code DIFFABLE (differently abled) should be used instead. In summary, the coded concepts in the Abstract Value Set "CoveredPartyRoleType" can be "post-coordinated" with the "RoleClassCoveredParty" Abstract Value Set. Decoupling these concepts is intended to support an expansive range of covered party concepts and their semantic comparability.

2 | (_CoverageRoleType) Abstract | | Role recognized through the issuance of insurance coverage to an identified covered party who has this relationship with the policy holder such as the policy holder themselves (self), spouse, child, etc

3 | FAMDEP | family dependent | The player of the role is dependent of the scoping entity.

3 | HANDIC | handicapped dependent | Covered party is a dependent of the policy holder with a physical or mental disability causing a disadvantage that makes independent achievement unusually difficult.

3 | INJ | injured plaintiff | Covered party is an injured party with a legal claim for compensation against a policy holder under an insurance policy.

3 | SELF | self | Covered party is the policy holder. Also known as the subscriber.

3 | SPON | sponsored dependent | Covered party is an individual that the policy holder has assumed responsibility for, such as foster child or legal ward.

3 | STUD | student | Covered party to an insurance policy has coverage through full-time or part-time attendance at a recognized educational institution as defined by a particular insurance policy.

4 | FSTUD | full-time student | Covered party to an insurance policy has coverage through full-time attendance at a recognized educational institution as defined by a particular insurance policy.

4 | PSTUD | part-time student | Covered party to an insurance policy has coverage through part-time attendance at a recognized educational institution as defined by a particular insurance policy.

3 | ADOPT | adopted child | A child taken into one's family through legal means and raised as one's own child.

3 | GCHILD | grandchild | A child of one's son or daughter.

3 | GPARNT | grandparent | parent of a parent of the subject.

3 | NAT | natural child | A child as determined by birth.

3 | NIENE | niece/nephew | A child of one's brother or sister or of the brother or sister of one's spouse.

3 | PARNT | parent | One that begets or brings forth offspring or a person who brings up and cares for for another (Webster's Collegiate Dictionary)

3 | SPSE | spouse | A marriage partner; a husband or wife.

3 | STEP | step child | A child receiving parental care and nurture from a person who is related to them through marriage to their parent.

2 | (_CoveredPartyRoleType) Abstract | | A role recognized through the eligibility of an identified living subject for benefits covered under an insurance policy or a program. Eligibility as a covered party may be conditioned on a relationship with (1) the policy holder such as the policy holder who is covered as an individual under a poliy or as a party sponsored for coverage by the policy holder. Example:An employee as a subscriber; or (2) on being scoped another covered party such as the subscriber, as in the case of a dependent. Discussion: The Abstract Value Set "CoverageRoleType", which was developed for use in the Canadian realm "pre-coordinate" coverage roles with other roles that a covered party must play in order to be eligible for coverage, e.g., "handicapped dependent". Other codes in the Abstract Value Set CoveredPartyRoleType domain can be "post-coordinated" with the EligiblePartyRoleType codes to denote comparable concepts. Decoupling the concepts is intended to support a wider range of concepts and semantic comparability of coded concepts.

3 | (_ClaimantCoveredPartyRoleType) Abstract | | DescriptionA role recognized through the eligibility of a party play a claimant for benefits covered or provided under an insurance policy.

4 | CRIMEVIC | crime victim | Description: A person playing the role of program eligible under a program based on allegations of being the victim of a crime. Discussion: This CoveredPartyRoleType.code is typically used when the CoveredPartyRole class code is "program eligible" and the person's status as a crime victim meets jurisdictional or program criteria.

4 | INJWKR | injured worker | Description: A person playing the role of program eligible under a workers compensation program based on the filing of work-related injury claim. Discussion: This CoveredPartyRoleType.code is used when the CoveredPartyRole class code is either "program eligible", a "named insured", and "individual insured", or "dependent", and the person's status as differently abled or "handicapped" meets jurisdictional, policy, or program criteria.

3 | (_DependentCoveredPartyRoleType) Abstract | | Description: A role recognized through the eligibility of a party to play a dependent for benefits covered or provided under a health insurance policy because of an association with the subscriber that is recognized by the policy underwriter.

4 | COCBEN | continuity of coverage beneficiary | Description: A person playing the role of an individual insured with continuity of coverage under a policy which is being terminated based on loss of original status that was the basis for coverage. Criteria for qualifying for continuity of coverage may be set by law. Discussion: This CoveredPartyRoleType.code is typically used when the CoveredPartyRole class code is either "program eligible" or "subscriber" and the person's status as a continuity of coverage beneficiary meets jurisdictional or policy criteria.

4 | DIFFABL | differently abled | Description: A person playing the role of program eligible under a program based on meeting criteria for health or functional limitation set by law or by the program. Discussion: This CoveredPartyRoleType.code is typically used when the CoveredPartyRole class code is either "program eligible", "named insured", "individual insured", or "dependent", and the person's status as differently abled meets jurisdictional, policy, or program criteria.

4 | WARD | ward | Description: A person, who is a minor or is deemed incompetent, who plays the role of a program eligible where eligibility for coverage is based on meeting program eligibility criteria for status as a ward of a court or jurisdiction. Discussion: This CoveredPartyRoleType.code is typically used when the CoveredPartyRole class code is a "claimant", "program eligible", a "named insured", an "individual Insured" or a "dependent", and the person's status as a ward meets program or policy criteria. In the case of a ward covered under a program providing financial or health benefits, a governmental agency may take temporary custody of a minor or incompetent for his/her protection and care, e.g., if the ward is suffering from neglect or abuse, or has been in trouble with the law.

3 | (_IndividualInsuredPartyRoleType) Abstract | | A role recognized through the eligibility of a party to play an individual insured for benefits covered or provided under an insurance policy where the party is also the policy holder.

4 | COCBEN

4 | RETIREE | retiree | Description: A person playing the role of an individual insured under a policy based on meeting criteria for the employment status of retired set by law or the policy. Discussion: This CoveredPartyRoleType.code is typically used when the CoveredPartyRole class code is either "program eligible" or "subscriber" and the person's status as a retiree meets jurisdictional or policy criteria.

3 | (_ProgramEligiblePartyRoleType) Abstract | | Description:A role recognized through the eligibility of a party to play a program eligible for benefits covered or provided under a program.

4 | CRIMEVIC

4 | INJWKR

4 | DIFFABL

4 | WARD

4 | INDIG | member of an indigenous people | Description: A person playing the role of program eligible under a program based on aboriginal ancestry or as a member of an aboriginal community. Discussion: This CoveredPartyRoleType.code is typically used when the CoveredPartyRole class code is "program eligible" and the person's status as a member of an indigenous people meets jurisdictional or program criteria.

4 | MIL | military | Definition: A person playing the role of program eligible under a program based on military status. Discussion: This CoveredPartyRoleType.code is typically used when the CoveredPartyRole class code is either "program eligible" or "subscriber" and the person's status as a member of the military meets jurisdictional or program criteria

5 | ACTMIL | active duty military | Description: A person playing the role of program eligible under a program based on active military status. Discussion: This CoveredPartyRoleType.code is typically used when the CoveredPartyRole class code is either "program eligible" or "subscriber" and the persons status as active duty military meets jurisdictional or program criteria.

5 | RETMIL | retired military | Description: A person playing the role of program eligible under a program based on retired military status. Discussion: This CoveredPartyRoleType.code is typically used when the CoveredPartyRole class code is either "program eligible" or "subscriber" and the persons status as retired military meets jurisdictional or program criteria.

5 | VET | veteran | Description: A person playing the role of program eligible under a program based on status as a military veteran. Discussion: This CoveredPartyRoleType.code is typically used when the CoveredPartyRole class code is either "program eligible" or "subscriber" and the persons status as a veteran meets jurisdictional or program criteria.

3 | (_SubscriberCoveredPartyRoleType) Abstract | | Description: A role recognized through the eligibility of a party to play a subscriber for benefits covered or provided under a health insurance policy.

4 | COCBEN

4 | RETIREE

4 | MIL

1 | (_ResearchSubjectRoleBasis) Abstract | | Specifies the administrative functionality within a formal experimental design for which the ResearchSubject role was established. Examples: screening - role is used for pre-enrollment evaluation portion of the design; enrolled - role is used for subjects admitted to the active treatment portion of the design.

2 | ERL | enrollment | Definition:The specific role being played by a research subject participating in the active treatment or primary data collection portion of a research study.

2 | SCN | screening | Definition:The specific role being played by a research subject participating in the pre-enrollment evaluation portion of a research study.

1 | (_ServiceDeliveryLocationRoleType) Abstract | | A role of a place that further classifies the setting (e.g., accident site, road side, work site, community location) in which services are delivered.

2 | (_DedicatedServiceDeliveryLocationRoleType) Abstract | | A role of a place that further classifies a setting that is intended to house the provision of services.

3 | (_DedicatedClinicalLocationRoleType) Abstract | | A role of a place that further classifies the clinical setting (e.g., cardiology clinic, primary care clinic, rehabilitation hospital, skilled nursing facility) in which care is delivered during an encounter.

4 | DX | Diagnostics or therapeutics unit | A practice setting where diagnostic procedures or therapeutic interventions are performed

5 | CVDX | Cardiovascular diagnostics or therapeutics unit | A practice setting where cardiovascular diagnostic procedures or therapeutic interventions are performed (e.g., cardiac catheterization lab, echocardiography suite)

6 | CATH | Cardiac catheterization lab

6 | ECHO | Echocardiography lab

5 | GIDX | Gastroenterology diagnostics or therapeutics lab | A practice setting where GI procedures (such as endoscopies) are performed

6 | ENDOS | Endoscopy lab | (X12N 261QD0000N)

5 | RADDX | Radiology diagnostics or therapeutics unit | A practice setting where radiology services (diagnostic or therapeutic) are provided (X12N 261QR0200N)

6 | RADO | Radiation oncology unit | (X12N 261QX0203N)

6 | RNEU | Neuroradiology unit

4 | HOSP | Hospital | An acute care institution that provides medical, surgical, or psychiatric care and treatment for the sick or the injured.

5 | CHR | Chronic Care Facility | (1) A hospital including a physical plant and personnel that provides multidisciplinary diagnosis and treatment for diseases that have one or more of the following characteristics: is permanent; leaves residual disability; is caused by nonreversible pathological alteration; requires special training of the patient for rehabilitation; and/or may be expected to require a long period of supervision or care. In addition, patients require the safety, security, and shelter of these specialized inpatient or partial hospitalization settings. (2) A hospital that provides medical and skilled nursing services to patients with long-term illnesses who are not in an acute phase but who require an intensity of services not available in nursing homes

5 | GACH | Hospitals; General Acute Care Hospital | (X12N 282N00000N)

5 | MHSP | Military Hospital | A health care facility operated by the Department of Defense or other military operation.

5 | PSYCHF | Psychatric Care Facility | Healthcare facility that cares for patients with psychiatric illness(s).

5 | RH | Rehabilitation hospital | (X12N 283X00000N)

6 | RHAT | addiction treatment center | Description: A location that plays the role of delivering services which may include life training and/or social support to people with addictions.

6 | RHII | intellectual impairment center | Description: A location that plays the role of delivering services which may include adaptation, rehabilitation and social integration services for people with intellectual and/or pervasive development disorders such as autism or severe behaviour disorder.

6 | RHMAD | parents with adjustment difficulties center | Description: A location that plays the role of delivering services which may social support services for adolescents who are pregnant or have child and are experiencing adaptation issues/difficulties in their current or eventual parenting role.

6 | RHPI | physical impairment center | Description: A location that plays the role of delivering services which may include adaptation, rehabilitation and social integration services for people with physical impairments.

7 | RHPIH | physical impairment - hearing center | Description: A location that plays the role of delivering services for people with hearing impairments.

7 | RHPIMS | physical impairment - motor skills center | Description: A location that plays the role of delivering services for people with motor skill impairments.
7 | RHPIVS | physical impairment - visual skills center | Description: A location that plays the role of delivering services for people with visual skill impairments.
6 | RHYAD | youths with adjustment difficulties center | Description: A location that plays the role of delivering services which may include life training and/or social support services for the adaption, rehabilitation and social integration of youths with adjustment difficulties.
4 | HU | Hospital unit
5 | BMTU | Bone marrow transplant unit
5 | CCU | Coronary care unit
5 | CHEST | Chest unit | A specialty unit in hospital that focuses on chronic respirator patients and pulmonary failure
5 | EPIL | Epilepsy unit
5 | ER | Emergency room | The section of a health care facility for providing rapid treatment to victims of sudden illness or trauma.
6 | ETU | Emergency trauma unit
5 | HD | Hemodialysis unit
5 | HLAB | hospital laboratory | Description: A location that plays the role of delivering services which may include tests done based on clinical specimens to get health information about a patient as pertaining to the diagnosis, treatment and prevention of disease. Hospital laboratories may be further divided into specialized units such as Anatomic Pathology, Microbiology, and Biochemistry.
6 | INLAB | inpatient laboratory | Description: A location that plays the role of delivering services which may include tests are done on clinical specimens to get health information about a patient pertaining to the diagnosis, treatment, and prevention of disease for a hospital visit longer than one day.
6 | OUTLAB | outpatient laboratory | Description: A location that plays the role of delivering services which may include tests are done on clinical specimens to get health information about a patient pertaining to the diagnosis, treatment, and prevention of disease for same day visits.
5 | HRAD | radiology unit | Description: A location that plays the role of delivering services which may include the branch of medicine that uses ionizing and non-ionizing radiation to diagnose and treat diseases. The radiology unit may be further divided into subspecialties such as Imaging, Cardiovascular, Thoracic, and Ultrasound.
5 | HUSCS | specimen collection site | Description: A location that plays the role of delivering services which may include collecting specimens and/or samples from patients for laboratory testing purposes, but does not perform any tests or analysis functions.
5 | ICU | Intensive care unit
6 | PEDICU | Pediatric intensive care unit
7 | PEDNICU | Pediatric neonatal intensive care unit
5 | INPHARM | inpatient pharmacy | Description: A location that plays the role of delivering services which may include providing judicious, safe, efficacious, appropriate and cost effective use of medicines for treatment of patients for visits longer than one day. The distinction between inpatient pharmacies and retail (or outpatient) pharmacies is that they are part of a patient's continuity of care while staying in the hospital.
5 | MBL | medical laboratory | Description: A location that plays the role of delivering services which include biochemistry, hematology, microbiology, immunochemistry, and toxicology.
5 | NCCS | Neurology critical care and stroke unit
5 | NS | Neurosurgery unit
5 | OUTPHARM | outpatient pharmacy | Description: A location that plays the role of delivering services which may include providing judicious, safe, efficacious, appropriate and cost effective use of medicines for treatment of patients for outpatient visits and may also be used for discharge prescriptions.
5 | PEDU | Pediatric unit
6 | PEDICU
5 | PHU | Psychiatric hospital unit | (X12N 273R00000N)
5 | RHU | Rehabilitation hospital unit
5 | SLEEP | Sleep disorders unit | (X12N 261QA1200N)
4 | NCCF | Nursing or custodial care facility
5 | SNF | Skilled nursing facility | (X12N 314000000N)
4 | OF | Outpatient facility
5 | ALL | Allergy clinic
5 | AMPUT | Amputee clinic
5 | BMTC | Bone marrow transplant clinic
5 | BREAST | Breast clinic
5 | CANC | Child and adolescent neurology clinic
5 | CAPC | Child and adolescent psychiatry clinic
5 | CARD | Ambulatory Health Care Facilities; Clinic/Center; Rehabilitation: Cardiac Facilities
6 | PEDCARD | Pediatric cardiology clinic
5 | COAG | Coagulation clinic
5 | CRS | Colon and rectal surgery clinic
5 | DERM | Dermatology clinic
5 | ENDO | Endocrinology clinic
6 | PEDE | Pediatric endocrinology clinic
5 | ENT | Otorhinolaryngology clinic
5 | FMC | Family medicine clinic
5 | GI | Gastroenterology clinic
6 | PEDGI | Pediatric gastroenterology clinic
5 | GIM | General internal medicine clinic
5 | GYN | Gynecology clinic
5 | HEM | Hematology clinic
6 | PEDHEM | Pediatric hematology clinic
5 | HTN | Hypertension clinic
5 | IEC | Impairment evaluation center | Focuses on assessing disability
5 | INFD | Infectious disease clinic
6 | PEDID | Pediatric infectious disease clinic
5 | INV | Infertility clinic

5 | LYMPH | Lympedema clinic
5 | MGEN | Medical genetics clinic
5 | NEPH | Nephrology clinic
6 | PEDNEPH | Pediatric nephrology clinic
5 | NEUR | Neurology clinic
5 | OB | Obstetrics clinic
5 | OMS | Oral and maxillofacial surgery clinic
5 | ONCL | Medical oncology clinic
6 | PEDHO | Pediatric oncology clinic
5 | OPH | Opthalmology clinic
5 | OPTC | optometry clinic | Description: A location that plays the role of delivering services which may include examination, diagnosis, treatment, management, and prevention of diseases and disorders of the eye as well as prescribing and fitting appropriate corrective lenses (glasses or contact lenses) as needed. Optometry clinics may also provide tests for visual field screening, measuring intra-ocular pressure and ophthalmoscopy, as and when required.
5 | ORTHO | Orthopedics clinic
6 | HAND | Hand clinic
5 | PAINCL | Pain clinic | (X12N 261QP3300N)
5 | PC | Primary care clinic | (X12N 261QP2300N)
5 | PEDC | Pediatrics clinic
6 | PEDCARD
6 | PEDE
6 | PEDGI
6 | PEDHEM
6 | PEDID
6 | PEDNEPH
6 | PEDHO
6 | PEDRHEUM | Pediatric rheumatology clinic
5 | POD | Podiatry clinic | (X12N 261QP1100N)
5 | PREV | Preventive medicine clinic
5 | PROCTO | Proctology clinic
5 | PROFF | Provider's Office | Location where healthcare service was delivered, identified as the healthcare provider's practice office.
5 | PROS | Prosthodontics clinic
5 | PSI | Psychology clinic
5 | PSY | Psychiatry clinic
5 | RHEUM | Rheumatology clinic
6 | PEDRHEUM
5 | SPMED | Sports medicine clinic
5 | SU | Surgery clinic
6 | PLS | Plastic surgery clinic
6 | URO | Urology clinic
5 | TR | Transplant clinic
5 | TRAVEL | Travel and geographic medicine clinic
5 | WND | Wound clinic
4 | RTF | Residential treatment facility
5 | PRC | Pain rehabilitation center
5 | SURF | Substance use rehabilitation facility | (X12N 324500000N)
3 | (_DedicatedNonClinicalLocationRoleType) Abstract | | A role of a place that further classifies a setting that is intended to house the provision of non-clinical services.
4 | DADDR | Delivery Address | Location address where medical supplies were transported to for use.
4 | MOBL | Mobile Unit | Location (mobile) where healthcare service was delivered.
5 | AMB | Ambulance | Location (mobile) where healthcare service was delivered, identified specifically as an ambulance.
4 | PHARM | Pharmacy | Location where healthcare service was delivered, identified as a pharmacy.
5 | INPHARM
5 | OUTPHARM
2 | (_IncidentalServiceDeliveryLocationRoleType) Abstract
3 | ACC | accident site | Location of an accident where healthcare service was delivered, such as a roadside.
3 | COMM | Community Location | Community location where healthcare is delivered.
4 | CSC | community service center | Description: A location that plays the role of delivering services which may include providing front-line services to the population of a defined geographic area such as: healthcare services and social services, preventive or curative, rehabilitation or reintegration.
3 | PTRES | Patient's Residence | location where healthcare was delivered which is the residence of the Patient.
3 | SCHOOL | school | Location where healthcare service was delivered, identified as a school or educational facility.
3 | UPC | underage protection center | Description: A location that plays the role of delivering services which may include: social emergency services required for a young person as required under any jurisdictional youth laws, child placement, and family mediation in the defined geographical area the SDL is responsible for. It may provide expertise in a judiciary setting on child custody, adoption and biological history research.
3 | WORK | work site | Location where healthcare service was delivered, identified as a work place.
1 | (_SpecimenRoleType) Abstract
2 | C | Calibrator | A specimen used for initial calibration settings of an instrument
2 | G | Group | A set of patient samples in which the individuals of the group may or may not be identified.
2 | L | Pool | Aliquots of individual specimens combined to form a single specimen representing all of the included individuals.
2 | P | Patient | A specimen that has been collected from a patient.
2 | Q | Quality Control | A specimen specifically used to verify the sensitivity, specificity, accuracy or other perfomance parameter of a diagnostic test.
3 | B | Blind | Quality Control specimen submitted to the lab whose identity and composition is not known to the lab.
3 | E | Electronic QC | An electronically simulated QC specimen

3 | F | Filler Proficiency | Specimen used for testing proficiency of an organization performing testing (how does this differ from O?)
3 | O | Operator Proficiency | A specimen used for evaluation of operator proficiency (operator in what context?)
3 | V | Verifying | A specimen used for periodic calibration checks of instruments
2 | R | Replicate | A portion of an original patent sample that is tested at the same time as the original sample
1 | CLAIM | claimant | A party that makes a claim for coverage under a policy.
1 | communityLaboratory | Community Laboratory
1 | GT | Guarantor | An individual or organization that makes or gives a promise, assurance, pledge to pay or has paid the healthcare service provider.
1 | homeHealth | Home Health
1 | laboratory | Laboratory
1 | pathologist | Pathologist
1 | PH | Policy Holder | Policy holder for the insurance policy.
1 | phlebotomist | Phlebotomist
1 | PROG | program eligible | A party that meets the eligibility criteria for coverage under a program.
1 | PT | Patient | The recipient for the service(s) and/or product(s) when they are not the covered party.
1 | subject | Self
1 | thirdParty | Third Party
1 | DEP
1 | DEPEN | dependent | A party covered under a policy based on association with a subscriber.
1 | FM | Family Member | A member of the covered party's family. This could be the spouse, a parent, a grand parent, a sibling, etc.
1 | INDIV | individual | A party covered under a policy as the policyholder.
1 | NAMED | named insured | A party to an insurance policy to whom the insurer agrees to indemnify for losses, provides benefits for, or renders services.
1 | PSYCHCF
1 | SUBSCR | subscriber | A party covered under a policy based on association with a sponsor who is the policy holder, and whose association may provide for the eligibility of dependents for coverage

4.3.2.112 HL7 v3 Code System RouteOfAdministration

URL: https://hl7.org/fhir/STU3/v3/RouteOfAdministration/cs.html

This page is part of the FHIR Specification (v3.0.2: STU 3). The current version which supercedes this version is 4.0.1. For a full list of available versions, see the Directory of published versions

Vocabulary Work Group | Maturity Level: N/A | External | Use Context: Any

This code system (http://hl7.org/fhir/v3/RouteOfAdministration) is defined as part of HL7 v3.

Summary

Defining URL: | http://hl7.org/fhir/v3/RouteOfAdministration
Name: | v3 Code System RouteOfAdministration
Definition: | The path the administered medication takes to get into the body or into contact with the body.
OID: | 2.16.840.1.113883.5.112 (for OID based terminology systems)
Source Resource | XML / JSON

This Code system is used in the following value sets:

* Immunization Route Codes (The value set to instantiate this attribute should be drawn from a terminologically robust code system that consists of or contains concepts to support describing the administrative routes used during vaccination. This value set is provided as a suggestive example.)

* Enteral Route Codes (EnteralRouteOfAdministration: Codes specifying the route of administration of enteral formula. This value set is composed of HL7 v3 codes and is provided as a suggestive example.)

* v3 Code System RouteOfAdministration (The path the administered medication takes to get into the body or into contact with the body.)

4.3.2.112.1 Code System Content

Release Date: 2016-11-11

Level | Code | Display | Definition
1 | (_RouteByMethod) Abstract | | Route of substance administration classified by administration method.
2 | SOAK | Immersion (soak) | Immersion (soak)
2 | SHAMPOO | Shampoo | Shampoo
2 | TRNSLING | Translingual | Translingual
2 | PO | Swallow, oral | Swallow, oral
2 | GARGLE | Gargle | Gargle
2 | SUCK | Suck, oromucosal | Suck, oromucosal
2 | (_Chew) Abstract | | Chew
3 | CHEW | Chew, oral | Chew, oral
2 | (_Diffusion) Abstract | | Diffusion
3 | EXTCORPDIF | Diffusion, extracorporeal | Diffusion, extracorporeal
3 | HEMODIFF | Diffusion, hemodialysis | Diffusion, hemodialysis
3 | TRNSDERMD | Diffusion, transdermal | Diffusion, transdermal
2 | (_Dissolve) Abstract | | Dissolve
3 | DISSOLVE | Dissolve, oral | Dissolve, oral
3 | SL | Dissolve, sublingual | Dissolve, sublingual

2 | (_Douche) Abstract | | Douche
3 | DOUCHE | Douche, vaginal | Douche, vaginal
2 | (_ElectroOsmosisRoute) Abstract | | Electro-osmosis
3 | ELECTOSMOS | Electro-osmosis | Electro-osmosis
2 | (_Enema) Abstract | | Enema
3 | ENEMA | Enema, rectal | Enema, rectal
3 | RETENEMA | Enema, rectal retention | Enema, rectal retention
2 | (_Flush) Abstract | | Flush
3 | IVFLUSH | Flush, intravenous catheter | Flush, intravenous catheter
2 | (_Implantation) Abstract | | Implantation
3 | IDIMPLNT | Implantation, intradermal | Implantation, intradermal
3 | IVITIMPLNT | Implantation, intravitreal | Implantation, intravitreal
3 | SQIMPLNT | Implantation, subcutaneous | Implantation, subcutaneous
2 | (_Infusion) Abstract | | Infusion
3 | EPI | Infusion, epidural | Infusion, epidural
3 | IA | Infusion, intraarterial catheter | Infusion, intraarterial catheter
3 | IC | Infusion, intracardiac | Infusion, intracardiac
3 | ICOR | Infusion, intracoronary | Infusion, intracoronary
3 | IOSSC | Infusion, intraosseous, continuous | Infusion, intraosseous, continuous
3 | IT | Infusion, intrathecal | Infusion, intrathecal
3 | IV | Infusion, intravenous | Infusion, intravenous
4 | IVC | Infusion, intravenous catheter | Infusion, intravenous catheter
4 | IVCC | Infusion, intravenous catheter, continuous | Infusion, intravenous catheter, continuous
4 | IVCI | Infusion, intravenous catheter, intermittent | Infusion, intravenous catheter, intermittent
4 | PCA | Infusion, intravenous catheter, pca pump | Infusion, intravenous catheter, pca pump
3 | IVASCINFUS | Infusion, intravascular | Infusion, intravascular
3 | SQINFUS | Infusion, subcutaneous | Infusion, subcutaneous
2 | (_Inhalation) Abstract | | Inhalation
3 | IPINHL | Inhalation, respiratory | Inhalation, oral
4 | ORIFINHL | Inhalation, oral intermittent flow | Inhalation, oral intermittent flow
4 | REBREATH | Inhalation, oral rebreather mask | Inhalation, oral rebreather mask
3 | IPPB | Inhalation, intermittent positive pressure breathing (ippb) | Inhalation, intermittent positive pressure breathing (ippb)
3 | NASINHL | Inhalation, nasal | Inhalation, nasal
4 | NASINHLC | Inhalation, nasal cannula | Inhalation, nasal, prongs
3 | NEB | Inhalation, nebulization | Inhalation, nebulization
4 | NASNEB | Inhalation, nebulization, nasal | Inhalation, nebulization, nasal
4 | ORNEB | Inhalation, nebulization, oral | Inhalation, nebulization, oral
3 | TRACH | Inhalation, tracheostomy | Inhalation, tracheostomy
3 | VENT | Inhalation, ventilator | Inhalation, ventilator
3 | VENTMASK | Inhalation, ventimask | Inhalation, ventimask
2 | (_Injection) Abstract | | Injection
3 | AMNINJ | Injection, amniotic fluid | Injection, amniotic fluid
3 | BILINJ | Injection, biliary tract | Injection, biliary tract
3 | CHOLINJ | Injection, for cholangiography | Injection, for cholangiography
3 | CERVINJ | Injection, cervical | Injection, cervical
3 | EPIDURINJ | Injection, epidural | Injection, epidural
3 | EPIINJ | Injection, epidural, push | Injection, epidural, push
3 | EPINJSP | Injection, epidural, slow push | Injection, epidural, slow push
3 | EXTRAMNINJ | Injection, extra-amniotic | Injection, extra-amniotic
3 | EXTCORPINJ | Injection, extracorporeal | Injection, extracorporeal
3 | GBINJ | Injection, gastric button | Injection, gastric button
3 | GINGINJ | Injection, gingival | Injection, gingival
3 | BLADINJ | Injection, urinary bladder | Injection, urinary bladder
3 | ENDOSININJ | Injection, endosinusial | Injection, endosinusial
3 | HEMOPORT | Injection, hemodialysis port | Injection, hemodialysis port
3 | IABDINJ | Injection, intra-abdominal | Injection, intra-abdominal
3 | IAINJ | Injection, intraarterial | Injection, intraarterial
4 | IAINJP | Injection, intraarterial, push | Injection, intraarterial, push
4 | IAINJSP | Injection, intraarterial, slow push | Injection, intraarterial, slow push
3 | IARTINJ | Injection, intraarticular | Injection, intraarticular
3 | IBURSINJ | Injection, intrabursal | Injection, intrabursal
3 | ICARDINJ | Injection, intracardiac | Injection, intracardiac
4 | ICARDINJRP | Injection, intracardiac, rapid push | Injection, intracardiac, rapid push
4 | ICARDINJSP | Injection, intracardiac, slow push | Injection, intracardiac, slow push
4 | ICARINJP | Injection, intracardiac, push | Injection, intracardiac, push
3 | ICARTINJ | Injection, intracartilaginous | Injection, intracartilaginous
3 | ICAUDINJ | Injection, intracaudal | Injection, intracaudal
3 | ICAVINJ | Injection, intracavernous | Injection, intracavernous
3 | ICAVITINJ | Injection, intracavitary | Injection, intracavitary
3 | ICEREBINJ | Injection, intracerebral | Injection, intracerebral
3 | ICISTERNINJ | Injection, intracisternal | Injection, intracisternal
3 | ICORONINJ | Injection, intracoronary | Injection, intracoronary

4 | ICORONINJP | Injection, intracoronary, push | Injection, intracoronary, push
3 | ICORPCAVINJ | Injection, intracorpus cavernosum | Injection, intracorpus cavernosum
3 | IDINJ | Injection, intradermal | Injection, intradermal
3 | IDISCINJ | Injection, intradiscal | Injection, intradiscal
3 | IDUCTINJ | Injection, intraductal | Injection, intraductal
3 | IDURINJ | Injection, intradural | Injection, intradural
3 | IEPIDINJ | Injection, intraepidermal | Injection, intraepidermal
3 | IEPITHINJ | Injection, intraepithelial | Injection, intraepithelial
3 | ILESINJ | Injection, intralesional | Injection, intralesional
3 | ILUMINJ | Injection, intraluminal | Injection, intraluminal
3 | ILYMPJINJ | Injection, intralymphatic | Injection, intralymphatic
3 | IM | Injection, intramuscular | Injection, intramuscular
4 | IMD | Injection, intramuscular, deep | Injection, intramuscular, deep
4 | IMZ | Injection, intramuscular, z track | Injection, intramuscular, z track
3 | IMEDULINJ | Injection, intramedullary | Injection, intramedullary
3 | INTERMENINJ | Injection, interameningeal | Injection, interameningeal
3 | INTERSTITINJ | Injection, interstitial | Injection, interstitial
3 | IOINJ | Injection, intraocular | Injection, intraocular
3 | IOSSINJ | Injection, intraosseous | Injection, intraosseous
3 | IOVARINJ | Injection, intraovarian | Injection, intraovarian
3 | IPCARDINJ | Injection, intrapericardial | Injection, intrapericardial
3 | IPERINJ | Injection, intraperitoneal | Injection, intraperitoneal
3 | IPINJ | Injection, intrapulmonary | Injection, intrapulmonary
3 | IPLRINJ | Injection, intrapleural | Injection, intrapleural
3 | IPROSTINJ | Injection, intraprostatic | Injection, intraprostatic
3 | IPUMPINJ | Injection, insulin pump | Injection, insulin pump
3 | ISINJ | Injection, intraspinal | Injection, intraspinal
3 | ISTERINJ | Injection, intrasternal | Injection, intrasternal
3 | ISYNINJ | Injection, intrasynovial | Injection, intrasynovial
3 | ITENDINJ | Injection, intratendinous | Injection, intratendinous
3 | ITESTINJ | Injection, intratesticular | Injection, intratesticular
3 | ITHORINJ | Injection, intrathoracic | Injection, intrathoracic
3 | ITINJ | Injection, intrathecal | Injection, intrathecal
3 | ITUBINJ | Injection, intratubular | Injection, intratubular
3 | ITUMINJ | Injection, intratumor | Injection, intratumor
3 | ITYMPINJ | Injection, intratympanic | Injection, intratympanic
3 | IUINJ | Injection, intrauterine | Injection, intracervical (uterus)
3 | IUINJC | Injection, intracervical (uterus) | Injection, intracervical (uterus)
3 | IURETINJ | Injection, intraureteral, retrograde | Injection, intraureteral, retrograde
3 | IVASCINJ | Injection, intravascular | Injection, intravascular
3 | IVENTINJ | Injection, intraventricular (heart) | Injection, intraventricular (heart)
3 | IVESINJ | Injection, intravesicle | Injection, intravesicle
3 | IVINJ | Injection, intravenous | Injection, intravenous
4 | IVINJBOL | Injection, intravenous, bolus | Injection, intravenous, bolus
4 | IVPUSH | Injection, intravenous, push | Injection, intravenous, push
4 | IVRPUSH | Injection, intravenous, rapid push | Injection, intravenous, rapid push
4 | IVSPUSH | Injection, intravenous, slow push | Injection, intravenous, slow push
3 | IVITINJ | Injection, intravitreal | Injection, intravitreal
3 | PAINJ | Injection, periarticular | Injection, periarticular
3 | PARENTINJ | Injection, parenteral | Injection, parenteral
3 | PDONTINJ | Injection, periodontal | Injection, periodontal
3 | PDPINJ | Injection, peritoneal dialysis port | Injection, peritoneal dialysis port
3 | PDURINJ | Injection, peridural | Injection, peridural
3 | PNINJ | Injection, perineural | Injection, perineural
3 | PNSINJ | Injection, paranasal sinuses | Injection, paranasal sinuses
3 | RBINJ | Injection, retrobulbar | Injection, retrobulbar
3 | SCINJ | Injection, subconjunctival | Injection, subconjunctival
3 | SLESINJ | Injection, sublesional | Injection, sublesional
3 | SOFTISINJ | Injection, soft tissue | Injection, soft tissue
3 | SQ | Injection, subcutaneous | Injection, subcutaneous
3 | SUBARACHINJ | Injection, subarachnoid | Injection, subarachnoid
3 | SUBMUCINJ | Injection, submucosal | Injection, submucosal
3 | TRPLACINJ | Injection, transplacental | Injection, transplacental
3 | TRTRACHINJ | Injection, transtracheal | Injection, transtracheal
3 | URETHINJ | Injection, urethral | Injection, urethral
3 | URETINJ | Injection, ureteral | Injection, ureteral
2 | (_Insertion) Abstract | | Insertion
3 | CERVINS | Insertion, cervical (uterine) | Insertion, cervical (uterine)
3 | IOSURGINS | Insertion, intraocular, surgical | Insertion, intraocular, surgical
3 | IU | Insertion, intrauterine | Insertion, intrauterine
3 | LPINS | Insertion, lacrimal puncta | Insertion, lacrimal puncta
3 | PR | Insertion, rectal | Insertion, rectal

3 | SQSURGINS | Insertion, subcutaneous, surgical | Insertion, subcutaneous, surgical
3 | URETHINS | Insertion, urethral | Insertion, urethral
3 | VAGINSI | Insertion, vaginal | Insertion, vaginal
2 | (_Instillation) Abstract | | Instillation
3 | CECINSTL | Instillation, cecostomy | Instillation, cecostomy
3 | EFT | Instillation, enteral feeding tube | Instillation, enteral feeding tube
3 | ENTINSTL | Instillation, enteral | Instillation, enteral
3 | GT | Instillation, gastrostomy tube | Instillation, gastrostomy tube
3 | NGT | Instillation, nasogastric tube | Instillation, nasogastric tube
3 | OGT | Instillation, orogastric tube | Instillation, orogastric tube
3 | BLADINSTL | Instillation, urinary catheter | Instillation, urinary catheter
3 | CAPDINSTL | Instillation, continuous ambulatory peritoneal dialysis port | Instillation, continuous ambulatory peritoneal dialysis port
3 | CTINSTL | Instillation, chest tube | Instillation, chest tube
3 | ETINSTL | Instillation, endotracheal tube | Instillation, endotracheal tube
3 | GJT | Instillation, gastro-jejunostomy tube | Instillation, gastro-jejunostomy tube
3 | IBRONCHINSTIL | Instillation, intrabronchial | Instillation, intrabronchial
3 | IDUODINSTIL | Instillation, intraduodenal | Instillation, intraduodenal
3 | IESOPHINSTIL | Instillation, intraesophageal | Instillation, intraesophageal
3 | IGASTINSTIL | Instillation, intragastric | Instillation, intragastric
3 | IILEALINJ | Instillation, intraileal | Instillation, intraileal
3 | IOINSTL | Instillation, intraocular | Instillation, intraocular
3 | ISININSTIL | Instillation, intrasinal | Instillation, intrasinal
3 | ITRACHINSTIL | Instillation, intratracheal | Instillation, intratracheal
3 | IUINSTL | Instillation, intrauterine | Instillation, intrauterine
3 | JJTINSTL | Instillation, jejunostomy tube | Instillation, jejunostomy tube
3 | LARYNGINSTIL | Instillation, laryngeal | Instillation, laryngeal
3 | NASALINSTIL | Instillation, nasal | Instillation, nasal
3 | NASOGASINSTIL | Instillation, nasogastric | Instillation, nasogastric
3 | NTT | Instillation, nasotracheal tube | Instillation, nasotracheal tube
3 | OJJ | Instillation, orojejunum tube | Instillation, orojejunum tube
3 | OT | Instillation, otic | Instillation, otic
3 | PDPINSTL | Instillation, peritoneal dialysis port | Instillation, peritoneal dialysis port
3 | PNSINSTL | Instillation, paranasal sinuses | Instillation, paranasal sinuses
3 | RECINSTL | Instillation, rectal | Instillation, rectal
4 | RECTINSTL | Instillation, rectal tube | Instillation, rectal tube
3 | SININSTIL | Instillation, sinus, unspecified | Instillation, sinus, unspecified
3 | SOFTISINSTIL | Instillation, soft tissue | Instillation, soft tissue
3 | TRACHINSTL | Instillation, tracheostomy | Instillation, tracheostomy
3 | TRTYMPINSTIL | Instillation, transtympanic | Instillation, transtympanic
3 | URETHINSTL | instillation, urethral | Instillation, urethral
2 | (_IontophoresisRoute) Abstract | | Iontophoresis
3 | IONTO | Topical application, iontophoresis | Topical application, iontophoresis
2 | (_Irrigation) Abstract | | Irrigation
3 | GUIRR | Irrigation, genitourinary | Irrigation, genitourinary
3 | IGASTIRR | Irrigation, intragastric | Irrigation, intragastric
3 | ILESIRR | Irrigation, intralesional | Irrigation, intralesional
3 | IOIRR | Irrigation, intraocular | Irrigation, intraocular
3 | BLADIRR | Irrigation, urinary bladder | Irrigation, urinary bladder
4 | BLADIRRC | Irrigation, urinary bladder, continuous | Irrigation, urinary bladder, continuous
4 | BLADIRRT | Irrigation, urinary bladder, tidal | Irrigation, urinary bladder, tidal
3 | RECIRR | Irrigation, rectal | Irrigation, rectal
2 | (_LavageRoute) Abstract | | Lavage
3 | IGASTLAV | Lavage, intragastric | Lavage, intragastric
2 | (_MucosalAbsorptionRoute) Abstract | | Mucosal absorption
3 | IDOUDMAB | Mucosal absorption, intraduodenal | Mucosal absorption, intraduodenal
3 | ITRACHMAB | Mucosal absorption, intratracheal | Mucosal absorption, intratracheal
3 | SMUCMAB | Mucosal absorption, submucosal | Mucosal absorption, submucosal
2 | (_Nebulization) Abstract | | Nebulization
3 | ETNEB | Nebulization, endotracheal tube | Nebulization, endotracheal tube
2 | (_Rinse) Abstract | | Rinse
3 | DENRINSE | Rinse, dental | Rinse, dental
3 | ORRINSE | Rinse, oral | Rinse, oral
2 | (_SuppositoryRoute) Abstract | | Suppository
3 | URETHSUP | Suppository, urethral | Suppository, urethral
2 | (_Swish) Abstract | | Swish
3 | SWISHSPIT | Swish and spit out, oromucosal | Swish and spit out, oromucosal
3 | SWISHSWAL | Swish and swallow, oromucosal | Swish and swallow, oromucosal
2 | (_TopicalAbsorptionRoute) Abstract | | Topical absorption
3 | TTYMPTABSORP | Topical absorption, transtympanic | Topical absorption, transtympanic
2 | (_TopicalApplication) Abstract | | Topical application
3 | DRESS | Topical application, soaked dressing | Topical application, soaked dressing
3 | IONTO

3 | SWAB | Topical application, swab | Topical application, swab
3 | TOPICAL | Topical | Topical
3 | BUC | Topical application, buccal | Topical application, buccal
3 | CERV | Topical application, cervical | Topical application, cervical
3 | DEN | Topical application, dental | Topical application, dental
3 | GIN | Topical application, gingival | Topical application, gingival
3 | HAIR | Topical application, hair | Topical application, hair
3 | ICORNTA | Topical application, intracorneal | Topical application, intracorneal
3 | ICORONTA | Topical application, intracoronal (dental) | Topical application, intracoronal (dental)
3 | IESOPHTA | Topical application, intraesophageal | Topical application, intraesophageal
3 | IILEALTA | Topical application, intraileal | Topical application, intraileal
3 | ILTOP | Topical application, intralesional | Topical application, intralesional
3 | ILUMTA | Topical application, intraluminal | Topical application, intraluminal
3 | IOTOP | Topical application, intraocular | Topical application, intraocular
3 | LARYNGTA | Topical application, laryngeal | Topical application, laryngeal
3 | MUC | Topical application, mucous membrane | Topical application, mucous membrane
3 | NAIL | Topical application, nail | Topical application, nail
3 | NASAL | Topical application, nasal | Topical application, nasal
3 | OPTHALTA | Topical application, ophthalmic | Topical application, ophthalmic
3 | ORALTA | Topical application, oral | Topical application, oral
3 | ORMUC | Topical application, oromucosal | Topical application, oromucosal
3 | OROPHARTA | Topical application, oropharyngeal | Topical application, oropharyngeal
3 | PERIANAL | Topical application, perianal | Topical application, perianal
3 | PERINEAL | Topical application, perineal | Topical application, perineal
3 | PDONTTA | Topical application, periodontal | Topical application, periodontal
3 | RECTAL | Topical application, rectal | Topical application, rectal
3 | SCALP | Topical application, scalp | Topical application, scalp
3 | OCDRESTA | Occlusive dressing technique | Occlusive dressing technique
3 | SKIN | Topical application, skin | Topical application, skin
3 | SUBCONJTA | Subconjunctival | Subconjunctival
3 | TMUCTA | Topical application, transmucosal | Topical application, transmucosal
3 | VAGINS | Topical application, vaginal | Insertion, vaginal
2 | INSUF | Insufflation | Insufflation
2 | TRNSDERM | Transdermal | Transdermal
3 | TRNSDERMD
1 | (_RouteBySite) Abstract | | Route of substance administration classified by site.
2 | TRNSDERM
2 | (_AmnioticFluidSacRoute) Abstract | | Amniotic fluid sac
3 | AMNINJ
2 | (_BiliaryRoute) Abstract | | Biliary tract
3 | BILINJ
3 | CHOLINJ
2 | (_BodySurfaceRoute) Abstract | | Body surface
3 | DRESS
3 | ELECTOSMOS
3 | IONTO
3 | SOAK
3 | SWAB
3 | TOPICAL
2 | (_BuccalMucosaRoute) Abstract | | Buccal mucosa
3 | BUC
2 | (_CecostomyRoute) Abstract | | Cecostomy
3 | CECINSTL
2 | (_CervicalRoute) Abstract | | Cervix of the uterus
3 | CERV
3 | CERVINJ
3 | CERVINS
3 | DEN
3 | DENRINSE
2 | (_EndocervicalRoute) Abstract | | Endocervical
3 | AMNINJ
3 | BILINJ
2 | (_EnteralRoute) Abstract | | Enteral
3 | EFT
3 | ENTINSTL
2 | (_EpiduralRoute) Abstract | | Epidural
3 | EPI
3 | EPIDURINJ
3 | EPIINJ
3 | EPINJSP
2 | (_ExtraAmnioticRoute) Abstract | | Extra-amniotic
3 | EXTRAMNINJ

2 | (_ExtracorporealCirculationRoute) Abstract | | Extracorporeal circulation
3 | EXTCORPDIF
3 | EXTCORPINJ
2 | (_GastricRoute) Abstract | | Gastric
3 | GBINJ
3 | GT
3 | NGT
3 | OGT
2 | (_GenitourinaryRoute) Abstract | | Genitourinary
3 | GUIRR
2 | (_GingivalRoute) Abstract | | Gingival
3 | GIN
3 | GINGINJ
2 | (_HairRoute) Abstract | | Hair
3 | HAIR
3 | SHAMPOO
2 | (_InterameningealRoute) Abstract | | Interameningeal
3 | INTERMENINJ
2 | (_InterstitialRoute) Abstract | | Interstitial
3 | INTERSTITINJ
2 | (_IntraabdominalRoute) Abstract | | Intra-abdominal
3 | IABDINJ
2 | (_IntraarterialRoute) Abstract | | Intra-arterial
3 | IA
3 | IAINJ
2 | (_IntraarticularRoute) Abstract | | Intraarticular
3 | IARTINJ
2 | (_IntrabronchialRoute) Abstract | | Intrabronchial
3 | IBRONCHINSTIL
2 | (_IntrabursalRoute) Abstract | | Intrabursal
3 | IBURSINJ
2 | (_IntracardiacRoute) Abstract | | Intracardiac
3 | IC
3 | ICARDINJ
2 | (_IntracartilaginousRoute) Abstract | | Intracartilaginous
3 | ICARTINJ
2 | (_IntracaudalRoute) Abstract | | Intracaudal
3 | ICAUDINJ
2 | (_IntracavernosalRoute) Abstract | | Intracavernosal
3 | ICAVINJ
2 | (_IntracavitaryRoute) Abstract | | Intracavitary
3 | ICAVITINJ
2 | (_IntracerebralRoute) Abstract | | Intracerebral
3 | ICEREBINJ
2 | (_IntracervicalRoute) Abstract | | Intracervical
3 | IUINJC
2 | (_IntracisternalRoute) Abstract | | Intracisternal
3 | ICISTERNINJ
2 | (_IntracornealRoute) Abstract | | Intracorneal
3 | ICORNTA
2 | (_IntracoronalRoute) Abstract | | Intracoronal (dental)
3 | ICORONTA
2 | (_IntracoronaryRoute) Abstract | | Intracoronary
3 | ICOR
3 | ICORONINJ
2 | (_IntracorpusCavernosumRoute) Abstract | | Intracorpus cavernosum
3 | ICORPCAVINJ
2 | (_IntradermalRoute) Abstract | | Intradermal
3 | IDIMPLNT
3 | IDINJ
2 | (_IntradiscalRoute) Abstract | | Intradiscal
3 | IDISCINJ
2 | (_IntraductalRoute) Abstract | | Intraductal
3 | IDUCTINJ
2 | (_IntraduodenalRoute) Abstract | | Intraduodenal
3 | IDUODINSTIL
3 | IDOUDMAB
2 | (_IntraduralRoute) Abstract | | Intradural
3 | IDURINJ
2 | (_IntraepidermalRoute) Abstract | | Intraepidermal
3 | IEPIDINJ
2 | (_IntraepithelialRoute) Abstract | | Intraepithelial

3 | IEPITHINJ
2 | (_IntraesophagealRoute) Abstract | | Intraesophageal
3 | IESOPHINSTIL
3 | IESOPHTA
2 | (_IntragastricRoute) Abstract | | Intragastric
3 | IGASTINSTIL
3 | IGASTIRR
3 | IGASTLAV
2 | (_IntrailealRoute) Abstract | | Intraileal
3 | IILEALINJ
3 | IILEALTA
2 | (_IntralesionalRoute) Abstract | | Intralesional
3 | ILESINJ
3 | ILESIRR
3 | ILTOP
2 | (_IntraluminalRoute) Abstract | | Intraluminal
3 | ILUMINJ
3 | ILUMTA
2 | (_IntralymphaticRoute) Abstract | | Intralymphatic
3 | ILYMPJINJ
2 | (_IntramedullaryRoute) Abstract | | Intramedullary
3 | IMEDULINJ
2 | (_IntramuscularRoute) Abstract | | Intramuscular
3 | IM
2 | (_IntraocularRoute) Abstract | | Intraocular
3 | IOINJ
3 | IOSURGINS
3 | IOINSTL
3 | IOIRR
3 | IOTOP
2 | (_IntraosseousRoute) Abstract | | Intraosseous
3 | IOSSC
3 | IOSSINJ
2 | (_IntraovarianRoute) Abstract | | Intraovarian
3 | IOVARINJ
2 | (_IntrapericardialRoute) Abstract | | Intrapericardial
3 | IPCARDINJ
2 | (_IntraperitonealRoute) Abstract | | Intraperitoneal
3 | IPERINJ
3 | PDPINJ
3 | CAPDINSTL
3 | PDPINSTL
2 | (_IntrapleuralRoute) Abstract | | Intrapleural
3 | IPLRINJ
3 | CTINSTL
2 | (_IntraprostaticRoute) Abstract | | Intraprostatic
3 | IPROSTINJ
2 | (_IntrapulmonaryRoute) Abstract | | Intrapulmonary
3 | EXTCORPINJ
3 | IPINJ
2 | (_IntrasinalRoute) Abstract | | Intrasinal
3 | ISININSTIL
2 | (_IntraspinalRoute) Abstract | | Intraspinal
3 | ISINJ
2 | (_IntrasternalRoute) Abstract | | Intrasternal
3 | ISTERINJ
2 | (_IntrasynovialRoute) Abstract | | Intrasynovial
3 | ISYNINJ
2 | (_IntratendinousRoute) Abstract | | Intratendinous
3 | ITENDINJ
2 | (_IntratesticularRoute) Abstract | | Intratesticular
3 | ITESTINJ
2 | (_IntrathecalRoute) Abstract | | Intrathecal
3 | IT
3 | ITINJ
2 | (_IntrathoracicRoute) Abstract | | Intrathoracic
3 | ITHORINJ
2 | (_IntratrachealRoute) Abstract | | Intratracheal
3 | ITRACHINSTIL
3 | ITRACHMAB
2 | (_IntratubularRoute) Abstract | | Intratubular
3 | ITUBINJ

2 | (_IntratumorRoute) Abstract | | Intratumor
3 | ITUMINJ
2 | (_IntratympanicRoute) Abstract | | Intratympanic
3 | ITYMPINJ
2 | (_IntrauterineRoute) Abstract | | Intrauterine
3 | IUINJ
3 | IURETINJ
3 | IU
3 | IUINSTL
2 | (_IntravascularRoute) Abstract | | Intravascular
3 | HEMODIFF
3 | IVASCINFUS
3 | HEMOPORT
3 | IVASCINJ
2 | (_IntravenousRoute) Abstract | | Intravenous
3 | IVFLUSH
3 | IVINJ
2 | (_IntraventricularRoute) Abstract | | Intraventricular
3 | IVENTINJ
2 | (_IntravesicleRoute) Abstract | | Intravesicle
3 | IVESINJ
2 | (_IntravitrealRoute) Abstract | | Intravitreal
3 | IVITINJ
2 | (_JejunumRoute) Abstract | | Jejunum
3 | GJT
3 | JJTINSTL
3 | OJJ
2 | (_LacrimalPunctaRoute) Abstract | | Lacrimal puncta
3 | LPINS
2 | (_LaryngealRoute) Abstract | | Laryngeal
3 | LARYNGINSTIL
3 | LARYNGTA
2 | (_LingualRoute) Abstract | | Lingual
3 | TRNSLING
2 | (_MucousMembraneRoute) Abstract | | Mucous membrane
3 | MUC
2 | (_NailRoute) Abstract | | Nail
3 | NAIL
2 | (_NasalRoute) Abstract | | Nasal
3 | NASINHL
3 | NASALINSTIL
3 | NASOGASINSTIL
3 | NASAL
2 | (_OphthalmicRoute) Abstract | | Ophthalmic
3 | OPTHALTA
2 | (_OralRoute) Abstract | | Oral
3 | CHEW
3 | DISSOLVE
3 | IPINHL
3 | ORALTA
3 | ORRINSE
3 | PO
2 | (_OromucosalRoute) Abstract | | Oromucosal
3 | GARGLE
3 | ORMUC
3 | SUCK
3 | SWISHSPIT
3 | SWISHSWAL
2 | (_OropharyngealRoute) Abstract | | Oropharyngeal
3 | OROPHARTA
2 | (_OticRoute) Abstract | | Otic
3 | OT
2 | (_ParanasalSinusesRoute) Abstract | | Paranasal sinuses
3 | PNSINJ
3 | PNSINSTL
2 | (_ParenteralRoute) Abstract | | Parenteral
3 | PARENTINJ
2 | (_PerianalRoute) Abstract | | Perianal
3 | PERIANAL
2 | (_PeriarticularRoute) Abstract | | Periarticular
3 | PAINJ
2 | (_PeriduralRoute) Abstract | | Peridural

3 | PDURINJ
2 | (_PerinealRoute) Abstract | | Perineal
3 | PERINEAL
2 | (_PerineuralRoute) Abstract | | Perineural
3 | PNINJ
2 | (_PeriodontalRoute) Abstract | | Periodontal
3 | PDONTINJ
3 | PDONTTA
2 | (_PulmonaryRoute) Abstract | | Pulmonary
3 | IPPB
3 | VENT
3 | VENTMASK
3 | ETINSTL
3 | NTT
3 | ETNEB
2 | (_RectalRoute) Abstract | | Rectal
3 | ENEMA
3 | RETENEMA
3 | PR
3 | RECINSTL
3 | RECIRR
3 | RECTAL
2 | (_RespiratoryTractRoute) Abstract | | Respiratory tract
3 | IPINHL
2 | (_RetrobulbarRoute) Abstract | | Retrobulbar
3 | RBINJ
2 | (_ScalpRoute) Abstract | | Scalp
3 | SCALP
2 | (_SinusUnspecifiedRoute) Abstract | | Sinus, unspecified
3 | ENDOSININJ
3 | SININSTIL
2 | (_SkinRoute) Abstract | | Skin
3 | OCDRESTA
3 | SKIN
2 | (_SoftTissueRoute) Abstract | | Soft tissue
3 | SOFTISINJ
3 | SOFTISINSTIL
2 | (_SubarachnoidRoute) Abstract | | Subarachnoid
3 | SUBARACHINJ
2 | (_SubconjunctivalRoute) Abstract | | Subconjunctival
3 | SCINJ
3 | SUBCONJTA
2 | (_SubcutaneousRoute) Abstract | | Subcutaneous
3 | SQIMPLNT
3 | SQINFUS
3 | IPUMPINJ
3 | SQ
3 | SQSURGINS
2 | (_SublesionalRoute) Abstract | | Sublesional
3 | SLESINJ
2 | (_SublingualRoute) Abstract | | Sublingual
3 | SL
2 | (_SubmucosalRoute) Abstract | | Submucosal
3 | SUBMUCINJ
3 | SMUCMAB
2 | (_TracheostomyRoute) Abstract | | Tracheostomy
3 | TRACH
3 | TRACHINSTL
2 | (_TransmucosalRoute) Abstract | | Transmucosal
3 | TMUCTA
2 | (_TransplacentalRoute) Abstract | | Transplacental
3 | TRPLACINJ
2 | (_TranstrachealRoute) Abstract | | Transtracheal
3 | TRTRACHINJ
2 | (_TranstympanicRoute) Abstract | | Transtympanic
3 | TRTYMPINSTIL
3 | TTYMPTABSORP
2 | (_UreteralRoute) Abstract | | Ureteral
3 | URETINJ
2 | (_UrethralRoute) Abstract | | Urethral
3 | URETHINJ
3 | URETHINS

3 | URETHINSTL
3 | URETHSUP
2 | (_UrinaryBladderRoute) Abstract | | Urinary bladder
3 | BLADINJ
3 | BLADIRR
2 | (_UrinaryTractRoute) Abstract | | Urinary tract
3 | BLADINSTL
2 | (_VaginalRoute) Abstract | | Vaginal
3 | DOUCHE
3 | VAGINSI
3 | VAGINS
2 | (_VitreousHumourRoute) Abstract | | Vitreous humour
3 | IVITIMPLNT

4.3.2.113 HL7 v3 Code System Sequencing

URL: https://hl7.org/fhir/STU3/v3/Sequencing/cs.html

This page is part of the FHIR Specification (v3.0.2: STU 3). The current version which supercedes this version is 4.0.1. For a full list of available versions, see the Directory of published versions

Vocabulary Work Group | Maturity Level: N/A | External | Use Context: Any

This code system (http://hl7.org/fhir/v3/Sequencing) is defined as part of HL7 v3.

Summary

Defining URL: | http://hl7.org/fhir/v3/Sequencing
Name: | v3 Code System Sequencing
Definition: | Specifies sequence of sort order.
OID: | 2.16.840.1.113883.5.113 (for OID based terminology systems)
Source Resource | XML / JSON

This Code system is used in the following value sets:

* v3 Code System Sequencing (Specifies sequence of sort order.)

4.3.2.113.1 Code System Content

Release Date: 2016-11-11

Level | Code | Display | Definition
1 | A | Ascending | Ascending sequence order.
1 | D | Descending | Descending sequence order.
1 | N | None | No enforced sequence order.

4.3.2.129 HL7 v3 Code System SpecimenType

URL: https://hl7.org/fhir/STU3/v3/SpecimenType/cs.html

This page is part of the FHIR Specification (v3.0.2: STU 3). The current version which supercedes this version is 4.0.1. For a full list of available versions, see the Directory of published versions

Vocabulary Work Group | Maturity Level: N/A | External | Use Context: Any

This code system (http://hl7.org/fhir/v3/SpecimenType) is defined as part of HL7 v3.

Summary

Defining URL: | http://hl7.org/fhir/v3/SpecimenType
Name: | v3 Code System SpecimenType
Definition: | **** MISSING DEFINITIONS ****
OID: | 2.16.840.1.113883.5.129 (for OID based terminology systems)
Source Resource | XML / JSON

This Code system is used in the following value sets:

* v3 Code System SpecimenType (**** MISSING DEFINITIONS ****)

4.3.2.129.1 Code System Content

Release Date: 2016-11-11

Level | Code | Display | Definition
1 | (_SpecimenEntityType) Abstract
2 | ABS | Abcess
2 | AMN | Amniotic fluid
2 | ASP | Aspirate
2 | BBL | Blood bag
2 | BDY | Whole body
2 | BIFL | Bile fluid
2 | BLD | Whole blood
2 | BLDA | Blood arterial

2 | BLDC | Blood capillary
2 | BLDCO | Blood - cord
2 | BLDV | Blood venous
2 | BON | Bone
2 | BPH | Basophils
2 | BPU | Blood product unit
2 | BRN | Burn
2 | BRO | Bronchial
2 | BRTH | Exhaled gas (=breath)
2 | CALC | Calculus (=Stone)
2 | CDM | Cardiac muscle
2 | CNJT | Conjunctiva
2 | CNL | Cannula
2 | COL | Colostrum
2 | CRN | Cornea
2 | CSF | Cerebral spinal fluid
2 | CTP | Catheter tip
2 | CUR | Curettage
2 | CVM | Cervical mucus
2 | CVX | Cervix
2 | CYST | Cyst
2 | DIAF | Dialysis fluid
2 | DOSE | Dose med or substance
2 | DRN | Drain
2 | DUFL | Duodenal fluid
2 | EAR | Ear
2 | EARW | Ear wax (cerumen)
2 | ELT | Electrode
2 | ENDC | Endocardium
2 | ENDM | Endometrium
2 | EOS | Eosinophils
2 | EYE | Eye
2 | FIB | Fibroblasts
2 | FIST | Fistula
2 | FLT | Filter
2 | FLU | Body fluid, unsp
2 | FOOD | Food sample
2 | GAS | Gas
2 | GAST | Gastric fluid/contents
2 | GEN | Genital
2 | GENC | Genital cervix
2 | GENF | Genital fluid
2 | GENL | Genital lochia
2 | GENV | Genital vaginal
2 | HAR | Hair
2 | IHG | Inhaled Gas
2 | ISLT | Isolate
2 | IT | Intubation tube
2 | LAM | Lamella
2 | LIQ | Liquid NOS
2 | LN | Line
2 | LNA | Line arterial
2 | LNV | Line venous
2 | LYM | Lymphocytes
2 | MAC | Macrophages
2 | MAR | Marrow (bone)
2 | MBLD | Menstrual blood
2 | MEC | Meconium
2 | MILK | Breast milk
2 | MLK | Milk
2 | NAIL | Nail
2 | NOS | Nose (nasal passage)
2 | PAFL | Pancreatic fluid
2 | PAT | Patient
2 | PLAS | Plasma
2 | PLB | Plasma bag
2 | PLC | Placenta
2 | PLR | Pleural fluid (thoracentesis fld)
2 | PMN | Polymorphonuclear neutrophils
2 | PPP | Platelet poor plasma
2 | PRP | Platelet rich plasma
2 | PRT | Peritoneal fluid /ascites

2 | PUS | Pus
2 | RBC | Erythrocytes
2 | SAL | Saliva
2 | SER | Serum
2 | SKM | Skeletal muscle
2 | SKN | Skin
2 | SMN | Seminal fluid
2 | SMPLS | Seminal plasma
2 | SNV | Synovial fluid (Joint fluid)
2 | SPRM | Spermatozoa
2 | SPT | Sputum
2 | SPTC | Sputum - coughed
2 | SPTT | Sputum - tracheal aspirate
2 | STL | Stool = Fecal
2 | SWT | Sweat
2 | TEAR | Tears
2 | THRB | Thrombocyte (platelet)
2 | THRT | Throat
2 | TISG | Tissue gall bladder
2 | TISPL | Tissue placenta
2 | TISS | Tissue, unspecified
2 | TISU | Tissue ulcer
2 | TLGI | Tissue large intestine
2 | TLNG | Tissue lung
2 | TSMI | Tissue small intestine Tissue ulcer
2 | TUB | Tube, unspecified
2 | ULC | Ulcer
2 | UMB | Umbilical blood
2 | UMED | Unknown medicine
2 | UR | Urine
2 | URC | Urine clean catch
2 | URNS | Urine sediment
2 | URT | Urine catheter
2 | URTH | Urethra
2 | USUB | Unknown substance
2 | VOM | Vomitus
2 | WAT | Water
2 | WBC | Leukocytes
2 | WICK | Wick
2 | WND | Wound
2 | WNDA | Wound abscess
2 | WNDD | Wound drainage
2 | WNDE | Wound exudate

4.3.2.131 HL7 v3 Code System TableCellHorizontalAlign

URL: https://hl7.org/fhir/STU3/v3/TableCellHorizontalAlign/cs.html

This page is part of the FHIR Specification (v3.0.2: STU 3). The current version which supercedes this version is 4.0.1. For a full list of available versions, see the Directory of published versions

Vocabulary Work Group | Maturity Level: N/A | External | Use Context: Any

This code system (http://hl7.org/fhir/v3/TableCellHorizontalAlign) is defined as part of HL7 v3.

Summary

Defining URL: | http://hl7.org/fhir/v3/TableCellHorizontalAlign
Name: | v3 Code System TableCellHorizontalAlign
Definition: | These values are defined within the XHTML 4.0 Table Model
OID: | 2.16.840.1.113883.5.131 (for OID based terminology systems)
Source Resource | XML / JSON

This Code system is used in the following value sets:

* v3 Code System TableCellHorizontalAlign (These values are defined within the XHTML 4.0 Table Model)

4.3.2.131.1 Code System Content

Release Date: 2016-11-11

Level | Code | Display | Definition
1 | center | center
1 | char | char
1 | justify | justify
1 | left | left
1 | right | right

4.3.2.132 HL7 v3 Code System TableCellScope

URL: https://hl7.org/fhir/STU3/v3/TableCellScope/cs.html

This page is part of the FHIR Specification (v3.0.2: STU 3). The current version which supercedes this version is 4.0.1. For a full list of available versions, see the Directory of published versions

Vocabulary Work Group | Maturity Level: N/A | External | Use Context: Any

This code system (http://hl7.org/fhir/v3/TableCellScope) is defined as part of HL7 v3.

Summary

Defining URL: | http://hl7.org/fhir/v3/TableCellScope
Name: | v3 Code System TableCellScope
Definition: | These values are defined within the XHTML 4.0 Table Model
OID: | 2.16.840.1.113883.5.132 (for OID based terminology systems)
Source Resource | XML / JSON

This Code system is used in the following value sets:

* v3 Code System TableCellScope (These values are defined within the XHTML 4.0 Table Model)

4.3.2.132.1 Code System Content

Release Date: 2016-11-11

Level	Code	Display	Definition
1	col	col	
1	colgroup	colgroup	
1	row	row	
1	rowgroup	rowgroup	

4.3.2.133 HL7 v3 Code System TableCellVerticalAlign

URL: https://hl7.org/fhir/STU3/v3/TableCellVerticalAlign/cs.html

This page is part of the FHIR Specification (v3.0.2: STU 3). The current version which supercedes this version is 4.0.1. For a full list of available versions, see the Directory of published versions

Vocabulary Work Group | Maturity Level: N/A | External | Use Context: Any

This code system (http://hl7.org/fhir/v3/TableCellVerticalAlign) is defined as part of HL7 v3.

Summary

Defining URL: | http://hl7.org/fhir/v3/TableCellVerticalAlign
Name: | v3 Code System TableCellVerticalAlign
Definition: | These values are defined within the XHTML 4.0 Table Model
OID: | 2.16.840.1.113883.5.133 (for OID based terminology systems)
Source Resource | XML / JSON

This Code system is used in the following value sets:

* v3 Code System TableCellVerticalAlign (These values are defined within the XHTML 4.0 Table Model)

4.3.2.133.1 Code System Content

Release Date: 2016-11-11

Level	Code	Display	Definition
1	baseline	baseline	
1	bottom	bottom	
1	middle	middle	
1	top	top	

4.3.2.134 HL7 v3 Code System TableFrame

URL: https://hl7.org/fhir/STU3/v3/TableFrame/cs.html

This page is part of the FHIR Specification (v3.0.2: STU 3). The current version which supercedes this version is 4.0.1. For a full list of available versions, see the Directory of published versions

Vocabulary Work Group | Maturity Level: N/A | External | Use Context: Any

This code system (http://hl7.org/fhir/v3/TableFrame) is defined as part of HL7 v3.

Summary

Defining URL: | http://hl7.org/fhir/v3/TableFrame
Name: | v3 Code System TableFrame
Definition: | These values are defined within the XHTML 4.0 Table Model
OID: | 2.16.840.1.113883.5.134 (for OID based terminology systems)
Source Resource | XML / JSON

This Code system is used in the following value sets:

* v3 Code System TableFrame (These values are defined within the XHTML 4.0 Table Model)

4.3.2.134.1 Code System Content

Release Date: 2016-11-11

Level	Code	Display	Definition
1	above	above	
1	below	below	
1	border	border	
1	box	box	
1	hsides	hsides	
1	lhs	lhs	
1	rhs	rhs	
1	void	void	
1	vsides	vsides	

4.3.2.136 HL7 v3 Code System TableRules

URL: https://hl7.org/fhir/STU3/v3/TableRules/cs.html

This page is part of the FHIR Specification (v3.0.2: STU 3). The current version which supercedes this version is 4.0.1. For a full list of available versions, see the Directory of published versions

Vocabulary Work Group | Maturity Level: N/A | External | Use Context: Any

This code system (http://hl7.org/fhir/v3/TableRules) is defined as part of HL7 v3.

Summary

Defining URL: | http://hl7.org/fhir/v3/TableRules
Name: | v3 Code System TableRules
Definition: | These values are defined within the XHTML 4.0 Table Model
OID: | 2.16.840.1.113883.5.136 (for OID based terminology systems)
Source Resource | XML / JSON

This Code system is used in the following value sets:

* v3 Code System TableRules (These values are defined within the XHTML 4.0 Table Model)

4.3.2.136.1 Code System Content

Release Date: 2016-11-11

Level	Code	Display	Definition
1	all	all	
1	cols	cols	
1	groups	groups	
1	none	none	
1	rows	rows	

4.3.2.137 HL7 v3 Code System TargetAwareness

URL: https://hl7.org/fhir/STU3/v3/TargetAwareness/cs.html

This page is part of the FHIR Specification (v3.0.2: STU 3). The current version which supercedes this version is 4.0.1. For a full list of available versions, see the Directory of published versions

Vocabulary Work Group | Maturity Level: N/A | External | Use Context: Any

This code system (http://hl7.org/fhir/v3/TargetAwareness) is defined as part of HL7 v3.

Summary

Defining URL: | http://hl7.org/fhir/v3/TargetAwareness
Name: | v3 Code System TargetAwareness
Definition: | **** MISSING DEFINITIONS ****
OID: | 2.16.840.1.113883.5.137 (for OID based terminology systems)
Source Resource | XML / JSON

This Code system is used in the following value sets:

* v3 Code System TargetAwareness (**** MISSING DEFINITIONS ****)

4.3.2.137.1 Code System Content

Release Date: 2016-11-11

Level	Code	Display	Definition
1	D	denying	Target person has been informed about the issue but currently denies it.
1	F	full awareness	Target person is fully aware of the issue.
1	I	incapable	Target person is not capable of comprehending the issue.
1	M	marginal	Target person is marginally aware of the issue.
1	P	partial	Target person is partially aware of the issue.

1 | U | uninformed | Target person has not yet been informed of the issue.

4.3.2.139 HL7 v3 Code System TimingEvent

URL: https://hl7.org/fhir/STU3/v3/TimingEvent/cs.html

This page is part of the FHIR Specification (v3.0.2: STU 3). The current version which supercedes this version is 4.0.1. For a full list of available versions, see the Directory of published versions

Vocabulary Work Group | Maturity Level: N/A | External | Use Context: Any

This code system (http://hl7.org/fhir/v3/TimingEvent) is defined as part of HL7 v3.

Summary

Defining URL: | http://hl7.org/fhir/v3/TimingEvent
Name: | v3 Code System TimingEvent
Definition: | **** MISSING DEFINITIONS ****
OID: | 2.16.840.1.113883.5.139 (for OID based terminology systems)
Source Resource | XML / JSON

This Code system is used in the following value sets:

* EventTiming (Real world event relating to the schedule.)

* v3 Code System TimingEvent (**** MISSING DEFINITIONS ****)

4.3.2.139.1 Code System Content

Release Date: 2016-11-11

Level | Code | Display | Definition
1 | AC | AC | before meal (from lat. ante cibus)
1 | ACD | ACD | before lunch (from lat. ante cibus diurnus)
1 | ACM | ACM | before breakfast (from lat. ante cibus matutinus)
1 | ACV | ACV | before dinner (from lat. ante cibus vespertinus)
1 | C | C | Description: meal (from lat. ante cibus)
2 | CD | CD | Description: lunch (from lat. cibus diurnus)
2 | CM | CM | Description: breakfast (from lat. cibus matutinus)
2 | CV | CV | Description: dinner (from lat. cibus vespertinus)
1 | HS | HS | Description: Prior to beginning a regular period of extended sleep (this would exclude naps). Note that this might occur at different times of day depending on a person's regular sleep schedule.
1 | IC | IC | between meals (from lat. inter cibus)
1 | ICD | ICD | between lunch and dinner
1 | ICM | ICM | between breakfast and lunch
1 | ICV | ICV | between dinner and the hour of sleep
1 | PC | PC | after meal (from lat. post cibus)
1 | PCD | PCD | after lunch (from lat. post cibus diurnus)
1 | PCM | PCM | after breakfast (from lat. post cibus matutinus)
1 | PCV | PCV | after dinner (from lat. post cibus vespertinus)
1 | WAKE | WAKE | Description: Upon waking up from a regular period of sleep, in order to start regular activities (this would exclude waking up from a nap or temporarily waking up during a period of sleep) Usage Notes: e.g. Take pulse rate on waking in management of thyrotoxicosis. Take BP on waking in management of hypertension Take basal body temperature on waking in establishing date of ovulation

4.3.2.140 HL7 v3 Code System TribalEntityUS

URL: https://hl7.org/fhir/STU3/v3/TribalEntityUS/cs.html

This page is part of the FHIR Specification (v3.0.2: STU 3). The current version which supercedes this version is 4.0.1. For a full list of available versions, see the Directory of published versions

Vocabulary Work Group | Maturity Level: N/A | External | Use Context: Any

This code system (http://hl7.org/fhir/v3/TribalEntityUS) is defined as part of HL7 v3.

Summary

Defining URL: | http://hl7.org/fhir/v3/TribalEntityUS
Name: | v3 Code System TribalEntityUS
Definition: | INDIAN ENTITIES RECOGNIZED AND ELIGIBLE TO RECEIVE SERVICES FROM THE UNITED STATES BUREAU OF INDIAN AFFAIRS
OID: | 2.16.840.1.113883.5.140 (for OID based terminology systems)
Source Resource | XML / JSON

This Code system is used in the following value sets:

* v3 Code System TribalEntityUS (INDIAN ENTITIES RECOGNIZED AND ELIGIBLE TO RECEIVE SERVICES FROM THE UNITED STATES BUREAU OF INDIAN AFFAIRS)

4.3.2.140.1 Code System Content

Release Date: 2016-11-11

Level | Code | Display | Definition

1 | (_NativeEntityAlaska) Abstract | | NATIVE ENTITIES WITHIN THE STATE OF ALASKA RECOGNIZED AND ELIGIBLE TO RECEIVE SERVICES FROM THE UNITED STATES BUREAU OF INDIAN AFFAIRS
2 | 338 | Village of Afognak
2 | 339 | Agdaagux Tribe of King Cove
2 | 340 | Native Village of Akhiok
2 | 341 | Akiachak Native Community
2 | 342 | Akiak Native Community
2 | 343 | Native Village of Akutan
2 | 344 | Village of Alakanuk
2 | 345 | Alatna Village
2 | 346 | Native Village of Aleknagik
2 | 347 | Algaaciq Native Village (St. Mary's)
2 | 348 | Allakaket Village
2 | 349 | Native Village of Ambler
2 | 350 | Village of Anaktuvuk Pass
2 | 351 | Yupiit of Andreafski
2 | 352 | Angoon Community Association
2 | 353 | Village of Aniak
2 | 354 | Anvik Village
2 | 355 | Arctic Village (See Native Village of Venetie Trib
2 | 356 | Asa carsarmiut Tribe (formerly Native Village of M
2 | 357 | Native Village of Atka
2 | 358 | Village of Atmautluak
2 | 359 | Atqasuk Village (Atkasook)
2 | 360 | Native Village of Barrow Inupiat Traditional Gover
2 | 361 | Beaver Village
2 | 362 | Native Village of Belkofski
2 | 363 | Village of Bill Moore's Slough
2 | 364 | Birch Creek Tribe
2 | 365 | Native Village of Brevig Mission
2 | 366 | Native Village of Buckland
2 | 367 | Native Village of Cantwell
2 | 368 | Native Village of Chanega (aka Chenega)
2 | 369 | Chalkyitsik Village
2 | 370 | Village of Chefornak
2 | 371 | Chevak Native Village
2 | 372 | Chickaloon Native Village
2 | 373 | Native Village of Chignik
2 | 374 | Native Village of Chignik Lagoon
2 | 375 | Chignik Lake Village
2 | 376 | Chilkat Indian Village (Klukwan)
2 | 377 | Chilkoot Indian Association (Haines)
2 | 378 | Chinik Eskimo Community (Golovin)
2 | 379 | Native Village of Chistochina
2 | 380 | Native Village of Chitina
2 | 381 | Native Village of Chuathbaluk (Russian Mission, Ku
2 | 382 | Chuloonawick Native Village
2 | 383 | Circle Native Community
2 | 384 | Village of Clark's Point
2 | 385 | Native Village of Council
2 | 386 | Craig Community Association
2 | 387 | Village of Crooked Creek
2 | 388 | Curyung Tribal Council (formerly Native Village of
2 | 389 | Native Village of Deering
2 | 390 | Native Village of Diomede (aka Inalik)
2 | 391 | Village of Dot Lake
2 | 392 | Douglas Indian Association
2 | 393 | Native Village of Eagle
2 | 394 | Native Village of Eek
2 | 395 | Egegik Village
2 | 396 | Eklutna Native Village
2 | 397 | Native Village of Ekuk
2 | 398 | Ekwok Village
2 | 399 | Native Village of Elim
2 | 400 | Emmonak Village
2 | 401 | Evansville Village (aka Bettles Field)
2 | 402 | Native Village of Eyak (Cordova)
2 | 403 | Native Village of False Pass
2 | 404 | Native Village of Fort Yukon
2 | 405 | Native Village of Gakona
2 | 406 | Galena Village (aka Louden Village)
2 | 407 | Native Village of Gambell

2 | 408 | Native Village of Georgetown
2 | 409 | Native Village of Goodnews Bay
2 | 410 | Organized Village of Grayling (aka Holikachuk)
2 | 411 | Gulkana Village
2 | 412 | Native Village of Hamilton
2 | 413 | Healy Lake Village
2 | 414 | Holy Cross Village
2 | 415 | Hoonah Indian Association
2 | 416 | Native Village of Hooper Bay
2 | 417 | Hughes Village
2 | 418 | Huslia Village
2 | 419 | Hydaburg Cooperative Association
2 | 420 | Igiugig Village
2 | 421 | Village of Iliamna
2 | 422 | Inupiat Community of the Arctic Slope
2 | 423 | Iqurmuit Traditional Council (formerly Native Vill
2 | 424 | Ivanoff Bay Village
2 | 425 | Kaguyak Village
2 | 426 | Organized Village of Kake
2 | 427 | Kaktovik Village (aka Barter Island)
2 | 428 | Village of Kalskag
2 | 429 | Village of Kaltag
2 | 430 | Native Village of Kanatak
2 | 431 | Native Village of Karluk
2 | 432 | Organized Village of Kasaan
2 | 433 | Native Village of Kasigluk
2 | 434 | Kenaitze Indian Tribe
2 | 435 | Ketchikan Indian Corporation
2 | 436 | Native Village of Kiana
2 | 437 | King Island Native Community
2 | 438 | King Salmon Tribe
2 | 439 | Native Village of Kipnuk
2 | 440 | Native Village of Kivalina
2 | 441 | Klawock Cooperative Association
2 | 442 | Native Village of Kluti Kaah (aka Copper Center)
2 | 443 | Knik Tribe
2 | 444 | Native Village of Kobuk
2 | 445 | Kokhanok Village
2 | 446 | Native Village of Kongiganak
2 | 447 | Village of Kotlik
2 | 448 | Native Village of Kotzebue
2 | 449 | Native Village of Koyuk
2 | 450 | Koyukuk Native Village
2 | 451 | Organized Village of Kwethluk
2 | 452 | Native Village of Kwigillingok
2 | 453 | Native Village of Kwinhagak (aka Quinhagak)
2 | 454 | Native Village of Larsen Bay
2 | 455 | Levelock Village
2 | 456 | Lesnoi Village (aka Woody Island)
2 | 457 | Lime Village
2 | 458 | Village of Lower Kalskag
2 | 459 | Manley Hot Springs Village
2 | 460 | Manokotak Village
2 | 461 | Native Village of Marshall (aka Fortuna Ledge)
2 | 462 | Native Village of Mary's Igloo
2 | 463 | McGrath Native Village
2 | 464 | Native Village of Mekoryuk
2 | 465 | Mentasta Traditional Council
2 | 466 | Metlakatla Indian Community, Annette Island Reserv
2 | 467 | Native Village of Minto
2 | 468 | Naknek Native Village
2 | 469 | Native Village of Nanwalek (aka English Bay)
2 | 470 | Native Village of Napaimute
2 | 471 | Native Village of Napakiak
2 | 472 | Native Village of Napaskiak
2 | 473 | Native Village of Nelson Lagoon
2 | 474 | Nenana Native Association
2 | 475 | New Koliganek Village Council (formerly Koliganek
2 | 476 | New Stuyahok Village
2 | 477 | Newhalen Village
2 | 478 | Newtok Village
2 | 479 | Native Village of Nightmute

2 | 480 | Nikolai Village
2 | 481 | Native Village of Nikolski
2 | 482 | Ninilchik Village
2 | 483 | Native Village of Noatak
2 | 484 | Nome Eskimo Community
2 | 485 | Nondalton Village
2 | 486 | Noorvik Native Community
2 | 487 | Northway Village
2 | 488 | Native Village of Nuiqsut (aka Nooiksut)
2 | 489 | Nulato Village
2 | 490 | Nunakauyarmiut Tribe (formerly Native Village of T
2 | 491 | Native Village of Nunapitchuk
2 | 492 | Village of Ohogamiut
2 | 493 | Village of Old Harbor
2 | 494 | Orutsararmuit Native Village (aka Bethel)
2 | 495 | Oscarville Traditional Village
2 | 496 | Native Village of Ouzinkie
2 | 497 | Native Village of Paimiut
2 | 498 | Pauloff Harbor Village
2 | 499 | Pedro Bay Village
2 | 500 | Native Village of Perryville
2 | 501 | Petersburg Indian Association
2 | 502 | Native Village of Pilot Point
2 | 503 | Pilot Station Traditional Village
2 | 504 | Native Village of Pitka's Point
2 | 505 | Platinum Traditional Village
2 | 506 | Native Village of Point Hope
2 | 507 | Native Village of Point Lay
2 | 508 | Native Village of Port Graham
2 | 509 | Native Village of Port Heiden
2 | 510 | Native Village of Port Lions
2 | 511 | Portage Creek Village (aka Ohgsenakale)
2 | 512 | Pribilof Islands Aleut Communities of St. Paul & S
2 | 513 | Qagan Tayagungin Tribe of Sand Point Village
2 | 514 | Qawalangin Tribe of Unalaska
2 | 515 | Rampart Village
2 | 516 | Village of Red Devil
2 | 517 | Native Village of Ruby
2 | 518 | Saint George Island(See Pribilof Islands Aleut Com
2 | 519 | Native Village of Saint Michael
2 | 520 | Saint Paul Island (See Pribilof Islands Aleut Comm
2 | 521 | Village of Salamatoff
2 | 522 | Native Village of Savoonga
2 | 523 | Organized Village of Saxman
2 | 524 | Native Village of Scammon Bay
2 | 525 | Native Village of Selawik
2 | 526 | Seldovia Village Tribe
2 | 527 | Shageluk Native Village
2 | 528 | Native Village of Shaktoolik
2 | 529 | Native Village of Sheldon's Point
2 | 530 | Native Village of Shishmaref
2 | 531 | Shoonaq Tribe of Kodiak
2 | 532 | Native Village of Shungnak
2 | 533 | Sitka Tribe of Alaska
2 | 534 | Skagway Village
2 | 535 | Village of Sleetmute
2 | 536 | Village of Solomon
2 | 537 | South Naknek Village
2 | 538 | Stebbins Community Association
2 | 539 | Native Village of Stevens
2 | 540 | Village of Stony River
2 | 541 | Takotna Village
2 | 542 | Native Village of Tanacross
2 | 543 | Native Village of Tanana
2 | 544 | Native Village of Tatitlek
2 | 545 | Native Village of Tazlina
2 | 546 | Telida Village
2 | 547 | Native Village of Teller
2 | 548 | Native Village of Tetlin
2 | 549 | Central Council of the Tlingit and Haida Indian Tb
2 | 550 | Traditional Village of Togiak
2 | 551 | Tuluksak Native Community

2 | 552 | Native Village of Tuntutuliak
2 | 553 | Native Village of Tununak
2 | 554 | Twin Hills Village
2 | 555 | Native Village of Tyonek
2 | 556 | Ugashik Village
2 | 557 | Umkumiute Native Village
2 | 558 | Native Village of Unalakleet
2 | 559 | Native Village of Unga
2 | 560 | Village of Venetie (See Native Village of Venetie
2 | 561 | Native Village of Venetie Tribal Government (Arcti
2 | 562 | Village of Wainwright
2 | 563 | Native Village of Wales
2 | 564 | Native Village of White Mountain
2 | 565 | Wrangell Cooperative Association
2 | 566 | Yakutat Tlingit Tribe
1 | (_NativeEntityContiguous) Abstract | | NATIVE ENTITIES WITHIN THE CONTIGUOUS 48 STATES
2 | 1 | Absentee-Shawnee Tribe of Indians of Oklahoma
2 | 10 | Assiniboine and Sioux Tribes of the Fort Peck Indi
2 | 100 | Havasupai Tribe of the Havasupai Reservation, Ariz
2 | 101 | Ho-Chunk Nation of Wisconsin (formerly known as th
2 | 102 | Hoh Indian Tribe of the Hoh Indian Reservation, Wa
2 | 103 | Hoopa Valley Tribe, California
2 | 104 | Hopi Tribe of Arizona
2 | 105 | Hopland Band of Pomo Indians of the Hopland Ranche
2 | 106 | Houlton Band of Maliseet Indians of Maine
2 | 107 | Hualapai Indian Tribe of the Hualapai Indian Reser
2 | 108 | Huron Potawatomi, Inc., Michigan
2 | 109 | Inaja Band of Diegueno Mission Indians of the Inaj
2 | 11 | Augustine Band of Cahuilla Mission Indians of the
2 | 110 | Ione Band of Miwok Indians of California
2 | 111 | Iowa Tribe of Kansas and Nebraska
2 | 112 | Iowa Tribe of Oklahoma
2 | 113 | Jackson Rancheria of Me-Wuk Indians of California
2 | 114 | Jamestown S'Klallam Tribe of Washington
2 | 115 | Jamul Indian Village of California
2 | 116 | Jena Band of Choctaw Indians, Louisiana
2 | 117 | Jicarilla Apache Tribe of the Jicarilla Apache Ind
2 | 118 | Kaibab Band of Paiute Indians of the Kaibab Indian
2 | 119 | Kalispel Indian Community of the Kalispel Reservat
2 | 12 | Bad River Band of the Lake Superior Tribe of Chipp
2 | 120 | Karuk Tribe of California
2 | 121 | Kashia Band of Pomo Indians of the Stewarts Point
2 | 122 | Kaw Nation, Oklahoma
2 | 123 | Keweenaw Bay Indian Community of L'Anse and Ontona
2 | 124 | Kialegee Tribal Town, Oklahoma
2 | 125 | Kickapoo Tribe of Indians of the Kickapoo Reservat
2 | 126 | Kickapoo Tribe of Oklahoma
2 | 127 | Kickapoo Traditional Tribe of Texas
2 | 128 | Kiowa Indian Tribe of Oklahoma
2 | 129 | Klamath Indian Tribe of Oregon
2 | 13 | Bay Mills Indian Community of the Sault Ste. Marie
2 | 130 | Kootenai Tribe of Idaho
2 | 131 | La Jolla Band of Luiseno Mission Indians of the La
2 | 132 | La Posta Band of Diegueno Mission Indians of the L
2 | 133 | Lac Courte Oreilles Band of Lake Superior Chippewa
2 | 134 | Lac du Flambeau Band of Lake Superior Chippewa Ind
2 | 135 | Lac Vieux Desert Band of Lake Superior Chippewa In
2 | 136 | Las Vegas Tribe of Paiute Indians of the Las Vegas
2 | 137 | Little River Band of Ottawa Indians of Michigan
2 | 138 | Little Traverse Bay Bands of Odawa Indians of Mich
2 | 139 | Lower Lake Rancheria, California
2 | 14 | Bear River Band of the Rohnerville Rancheria, Cali
2 | 140 | Los Coyotes Band of Cahuilla Mission Indians of th
2 | 141 | Lovelock Paiute Tribe of the Lovelock Indian Colon
2 | 142 | Lower Brule Sioux Tribe of the Lower Brule Reserva
2 | 143 | Lower Elwha Tribal Community of the Lower Elwha Re
2 | 144 | Lower Sioux Indian Community of Minnesota Mdewakan
2 | 145 | Lummi Tribe of the Lummi Reservation, Washington
2 | 146 | Lytton Rancheria of California
2 | 147 | Makah Indian Tribe of the Makah Indian Reservation
2 | 148 | Manchester Band of Pomo Indians of the Manchester-
2 | 149 | Manzanita Band of Diegueno Mission Indians of the

2 | 15 | Berry Creek Rancheria of Maidu Indians of Californ
2 | 150 | Mashantucket Pequot Tribe of Connecticut
2 | 151 | Match-e-be-nash-she-wish Band of Pottawatomi India
2 | 152 | Mechoopda Indian Tribe of Chico Rancheria, Califor
2 | 153 | Menominee Indian Tribe of Wisconsin
2 | 154 | Mesa Grande Band of Diegueno Mission Indians of th
2 | 155 | Mescalero Apache Tribe of the Mescalero Reservatio
2 | 156 | Miami Tribe of Oklahoma
2 | 157 | Miccosukee Tribe of Indians of Florida
2 | 158 | Middletown Rancheria of Pomo Indians of California
2 | 159 | Minnesota Chippewa Tribe, Minnesota (Six component
2 | 16 | Big Lagoon Rancheria, California
2 | 160 | Bois Forte Band (Nett Lake); Fond du Lac Band; Gra
2 | 161 | Mississippi Band of Choctaw Indians, Mississippi
2 | 162 | Moapa Band of Paiute Indians of the Moapa River In
2 | 163 | Modoc Tribe of Oklahoma
2 | 164 | Mohegan Indian Tribe of Connecticut
2 | 165 | Mooretown Rancheria of Maidu Indians of California
2 | 166 | Morongo Band of Cahuilla Mission Indians of the Mo
2 | 167 | Muckleshoot Indian Tribe of the Muckleshoot Reserv
2 | 168 | Muscogee (Creek) Nation, Oklahoma
2 | 169 | Narragansett Indian Tribe of Rhode Island
2 | 17 | Big Pine Band of Owens Valley Paiute Shoshone Indi
2 | 170 | Navajo Nation, Arizona, New Mexico & Utah
2 | 171 | Nez Perce Tribe of Idaho
2 | 172 | Nisqually Indian Tribe of the Nisqually Reservatio
2 | 173 | Nooksack Indian Tribe of Washington
2 | 174 | Northern Cheyenne Tribe of the Northern Cheyenne I
2 | 175 | Northfork Rancheria of Mono Indians of California
2 | 176 | Northwestern Band of Shoshoni Nation of Utah (Wash
2 | 177 | Oglala Sioux Tribe of the Pine Ridge Reservation,
2 | 178 | Omaha Tribe of Nebraska
2 | 179 | Oneida Nation of New York
2 | 18 | Big Sandy Rancheria of Mono Indians of California
2 | 180 | Oneida Tribe of Wisconsin
2 | 181 | Onondaga Nation of New York
2 | 182 | Osage Tribe, Oklahoma
2 | 183 | Ottawa Tribe of Oklahoma
2 | 184 | Otoe-Missouria Tribe of Indians, Oklahoma
2 | 185 | Paiute Indian Tribe of Utah
2 | 186 | Paiute-Shoshone Indians of the Bishop Community of
2 | 187 | Paiute-Shoshone Tribe of the Fallon Reservation an
2 | 188 | Paiute-Shoshone Indians of the Lone Pine Community
2 | 189 | Pala Band of Luiseno Mission Indians of the Pala R
2 | 19 | Big Valley Band of Pomo Indians of the Big Valley
2 | 190 | Pascua Yaqui Tribe of Arizona
2 | 191 | Paskenta Band of Nomlaki Indians of California
2 | 192 | Passamaquoddy Tribe of Maine
2 | 193 | Pauma Band of Luiseno Mission Indians of the Pauma
2 | 194 | Pawnee Nation of Oklahoma
2 | 195 | Pechanga Band of Luiseno Mission Indians of the Pe
2 | 196 | Penobscot Tribe of Maine
2 | 197 | Peoria Tribe of Indians of Oklahoma
2 | 198 | Picayune Rancheria of Chukchansi Indians of Califo
2 | 199 | Pinoleville Rancheria of Pomo Indians of Californi
2 | 2 | Agua Caliente Band of Cahuilla Indians of the Agua
2 | 20 | Blackfeet Tribe of the Blackfeet Indian Reservatio
2 | 200 | Pit River Tribe, California (includes Big Bend, Lo
2 | 201 | Poarch Band of Creek Indians of Alabama
2 | 202 | Pokagon Band of Potawatomi Indians of Michigan
2 | 203 | Ponca Tribe of Indians of Oklahoma
2 | 204 | Ponca Tribe of Nebraska
2 | 205 | Port Gamble Indian Community of the Port Gamble Re
2 | 206 | Potter Valley Rancheria of Pomo Indians of Califor
2 | 207 | Prairie Band of Potawatomi Indians, Kansas
2 | 208 | Prairie Island Indian Community of Minnesota Mdewa
2 | 209 | Pueblo of Acoma, New Mexico
2 | 21 | Blue Lake Rancheria, California
2 | 210 | Pueblo of Cochiti, New Mexico
2 | 211 | Pueblo of Jemez, New Mexico
2 | 212 | Pueblo of Isleta, New Mexico
2 | 213 | Pueblo of Laguna, New Mexico

2 | 214 | Pueblo of Nambe, New Mexico
2 | 215 | Pueblo of Picuris, New Mexico
2 | 216 | Pueblo of Pojoaque, New Mexico
2 | 217 | Pueblo of San Felipe, New Mexico
2 | 218 | Pueblo of San Juan, New Mexico
2 | 219 | Pueblo of San Ildefonso, New Mexico
2 | 22 | Bridgeport Paiute Indian Colony of California
2 | 220 | Pueblo of Sandia, New Mexico
2 | 221 | Pueblo of Santa Ana, New Mexico
2 | 222 | Pueblo of Santa Clara, New Mexico
2 | 223 | Pueblo of Santo Domingo, New Mexico
2 | 224 | Pueblo of Taos, New Mexico
2 | 225 | Pueblo of Tesuque, New Mexico
2 | 226 | Pueblo of Zia, New Mexico
2 | 227 | Puyallup Tribe of the Puyallup Reservation, Washin
2 | 228 | Pyramid Lake Paiute Tribe of the Pyramid Lake Rese
2 | 229 | Quapaw Tribe of Indians, Oklahoma
2 | 23 | Buena Vista Rancheria of Me-Wuk Indians of Califor
2 | 230 | Quartz Valley Indian Community of the Quartz Valle
2 | 231 | Quechan Tribe of the Fort Yuma Indian Reservation,
2 | 232 | Quileute Tribe of the Quileute Reservation, Washin
2 | 233 | Quinault Tribe of the Quinault Reservation, Washin
2 | 234 | Ramona Band or Village of Cahuilla Mission Indians
2 | 235 | Red Cliff Band of Lake Superior Chippewa Indians o
2 | 236 | Red Lake Band of Chippewa Indians of the Red Lake
2 | 237 | Redding Rancheria, California
2 | 238 | Redwood Valley Rancheria of Pomo Indians of Califo
2 | 239 | Reno-Sparks Indian Colony, Nevada
2 | 24 | Burns Paiute Tribe of the Burns Paiute Indian Colo
2 | 240 | Resighini Rancheria, California (formerly known as
2 | 241 | Rincon Band of Luiseno Mission Indians of the Rinc
2 | 242 | Robinson Rancheria of Pomo Indians of California
2 | 243 | Rosebud Sioux Tribe of the Rosebud Indian Reservat
2 | 244 | Round Valley Indian Tribes of the Round Valley Res
2 | 245 | Rumsey Indian Rancheria of Wintun Indians of Calif
2 | 246 | Sac and Fox Tribe of the Mississippi in Iowa
2 | 247 | Sac and Fox Nation of Missouri in Kansas and Nebra
2 | 248 | Sac and Fox Nation, Oklahoma
2 | 249 | Saginaw Chippewa Indian Tribe of Michigan, Isabell
2 | 25 | Cabazon Band of Cahuilla Mission Indians of the Ca
2 | 250 | Salt River Pima-Maricopa Indian Community of the S
2 | 251 | Samish Indian Tribe, Washington
2 | 252 | San Carlos Apache Tribe of the San Carlos Reservat
2 | 253 | San Juan Southern Paiute Tribe of Arizona
2 | 254 | San Manual Band of Serrano Mission Indians of the
2 | 255 | San Pasqual Band of Diegueno Mission Indians of Ca
2 | 256 | Santa Rosa Indian Community of the Santa Rosa Ranc
2 | 257 | Santa Rosa Band of Cahuilla Mission Indians of the
2 | 258 | Santa Ynez Band of Chumash Mission Indians of the
2 | 259 | Santa Ysabel Band of Diegueno Mission Indians of t
2 | 26 | Cachil DeHe Band of Wintun Indians of the Colusa I
2 | 260 | Santee Sioux Tribe of the Santee Reservation of Ne
2 | 261 | Sauk-Suiattle Indian Tribe of Washington
2 | 262 | Sault Ste. Marie Tribe of Chippewa Indians of Mich
2 | 263 | Scotts Valley Band of Pomo Indians of California
2 | 264 | Seminole Nation of Oklahoma
2 | 265 | Seminole Tribe of Florida, Dania, Big Cypress, Bri
2 | 266 | Seneca Nation of New York
2 | 267 | Seneca-Cayuga Tribe of Oklahoma
2 | 268 | Shakopee Mdewakanton Sioux Community of Minnesota
2 | 269 | Shawnee Tribe, Oklahoma
2 | 27 | Caddo Indian Tribe of Oklahoma
2 | 270 | Sherwood Valley Rancheria of Pomo Indians of Calif
2 | 271 | Shingle Springs Band of Miwok Indians, Shingle Spr
2 | 272 | Shoalwater Bay Tribe of the Shoalwater Bay Indian
2 | 273 | Shoshone Tribe of the Wind River Reservation, Wyom
2 | 274 | Shoshone-Bannock Tribes of the Fort Hall Reservati
2 | 275 | Shoshone-Paiute Tribes of the Duck Valley Reservat
2 | 276 | Sisseton-Wahpeton Sioux Tribe of the Lake Traverse
2 | 277 | Skokomish Indian Tribe of the Skokomish Reservatio
2 | 278 | Skull Valley Band of Goshute Indians of Utah
2 | 279 | Smith River Rancheria, California

2 | 28 | Cahuilla Band of Mission Indians of the Cahuilla R
2 | 280 | Snoqualmie Tribe, Washington
2 | 281 | Soboba Band of Luiseno Indians, California (former
2 | 282 | Sokaogon Chippewa Community of the Mole Lake Band
2 | 283 | Southern Ute Indian Tribe of the Southern Ute Rese
2 | 284 | Spirit Lake Tribe, North Dakota (formerly known as
2 | 285 | Spokane Tribe of the Spokane Reservation, Washingt
2 | 286 | Squaxin Island Tribe of the Squaxin Island Reserva
2 | 287 | St. Croix Chippewa Indians of Wisconsin, St. Croix
2 | 288 | St. Regis Band of Mohawk Indians of New York
2 | 289 | Standing Rock Sioux Tribe of North & South Dakota
2 | 29 | Cahto Indian Tribe of the Laytonville Rancheria, C
2 | 290 | Stockbridge-Munsee Community of Mohican Indians of
2 | 291 | Stillaguamish Tribe of Washington
2 | 292 | Summit Lake Paiute Tribe of Nevada
2 | 293 | Suquamish Indian Tribe of the Port Madison Reserva
2 | 294 | Susanville Indian Rancheria, California
2 | 295 | Swinomish Indians of the Swinomish Reservation, Wa
2 | 296 | Sycuan Band of Diegueno Mission Indians of Califor
2 | 297 | Table Bluff Reservation - Wiyot Tribe, California
2 | 298 | Table Mountain Rancheria of California
2 | 299 | Te-Moak Tribe of Western Shoshone Indians of Nevad
2 | 3 | Ak Chin Indian Community of the Maricopa (Ak Chin)
2 | 30 | California Valley Miwok Tribe, California (formerl
2 | 300 | Thlopthlocco Tribal Town, Oklahoma
2 | 301 | Three Affiliated Tribes of the Fort Berthold Reser
2 | 302 | Tohono O'odham Nation of Arizona
2 | 303 | Tonawanda Band of Seneca Indians of New York
2 | 304 | Tonkawa Tribe of Indians of Oklahoma
2 | 305 | Tonto Apache Tribe of Arizona
2 | 306 | Torres-Martinez Band of Cahuilla Mission Indians o
2 | 307 | Tule River Indian Tribe of the Tule River Reservat
2 | 308 | Tulalip Tribes of the Tulalip Reservation, Washing
2 | 309 | Tunica-Biloxi Indian Tribe of Louisiana
2 | 31 | Campo Band of Diegueno Mission Indians of the Camp
2 | 310 | Tuolumne Band of Me-Wuk Indians of the Tuolumne Ra
2 | 311 | Turtle Mountain Band of Chippewa Indians of North
2 | 312 | Tuscarora Nation of New York
2 | 313 | Twenty-Nine Palms Band of Mission Indians of Calif
2 | 314 | United Auburn Indian Community of the Auburn Ranch
2 | 315 | United Keetoowah Band of Cherokee Indians of Oklah
2 | 316 | Upper Lake Band of Pomo Indians of Upper Lake Ranc
2 | 317 | Upper Sioux Indian Community of the Upper Sioux Re
2 | 318 | Upper Skagit Indian Tribe of Washington
2 | 319 | Ute Indian Tribe of the Uintah & Ouray Reservation
2 | 32 | Capitan Grande Band of Diegueno Mission Indians of
2 | 320 | Ute Mountain Tribe of the Ute Mountain Reservation
2 | 321 | Utu Utu Gwaitu Paiute Tribe of the Benton Paiute R
2 | 322 | Walker River Paiute Tribe of the Walker River Rese
2 | 323 | Wampanoag Tribe of Gay Head (Aquinnah) of Massachu
2 | 324 | Washoe Tribe of Nevada & California (Carson Colony
2 | 325 | White Mountain Apache Tribe of the Fort Apache Res
2 | 326 | Wichita and Affiliated Tribes (Wichita, Keechi, Wa
2 | 327 | Winnebago Tribe of Nebraska
2 | 328 | Winnemucca Indian Colony of Nevada
2 | 329 | Wyandotte Tribe of Oklahoma
2 | 33 | Barona Group of Capitan Grande Band of Mission Ind
2 | 330 | Yankton Sioux Tribe of South Dakota
2 | 331 | Yavapai-Apache Nation of the Camp Verde Indian Res
2 | 332 | Yavapai-Prescott Tribe of the Yavapai Reservation,
2 | 333 | Yerington Paiute Tribe of the Yerington Colony & C
2 | 334 | Yomba Shoshone Tribe of the Yomba Reservation, Nev
2 | 335 | Ysleta Del Sur Pueblo of Texas
2 | 336 | Yurok Tribe of the Yurok Reservation, California
2 | 337 | Zuni Tribe of the Zuni Reservation, New Mexico
2 | 34 | Viejas (Baron Long) Group of Capitan Grande Band o
2 | 35 | Catawba Indian Nation (aka Catawba Tribe of South
2 | 36 | Cayuga Nation of New York
2 | 37 | Cedarville Rancheria, California
2 | 38 | Chemehuevi Indian Tribe of the Chemehuevi Reservat
2 | 39 | Cher-Ae Heights Indian Community of the Trinidad R
2 | 4 | Alabama-Coushatta Tribes of Texas

2 | 40 | Cherokee Nation, Oklahoma
2 | 41 | Cheyenne-Arapaho Tribes of Oklahoma
2 | 42 | Cheyenne River Sioux Tribe of the Cheyenne River R
2 | 43 | Chickasaw Nation, Oklahoma
2 | 44 | Chicken Ranch Rancheria of Me-Wuk Indians of Calif
2 | 45 | Chippewa-Cree Indians of the Rocky Boy's Reservati
2 | 46 | Chitimacha Tribe of Louisiana
2 | 47 | Choctaw Nation of Oklahoma
2 | 48 | Citizen Potawatomi Nation, Oklahoma
2 | 49 | Cloverdale Rancheria of Pomo Indians of California
2 | 5 | Alabama-Quassarte Tribal Town, Oklahoma
2 | 50 | Cocopah Tribe of Arizona
2 | 51 | Coeur D'Alene Tribe of the Coeur D'Alene Reservati
2 | 52 | Cold Springs Rancheria of Mono Indians of Californ
2 | 53 | Colorado River Indian Tribes of the Colorado River
2 | 54 | Comanche Indian Tribe, Oklahoma
2 | 55 | Confederated Salish & Kootenai Tribes of the Flath
2 | 56 | Confederated Tribes of the Chehalis Reservation, W
2 | 57 | Confederated Tribes of the Colville Reservation, W
2 | 58 | Confederated Tribes of the Coos, Lower Umpqua and
2 | 59 | Confederated Tribes of the Goshute Reservation, Ne
2 | 6 | Alturas Indian Rancheria, California
2 | 60 | Confederated Tribes of the Grand Ronde Community o
2 | 61 | Confederated Tribes of the Siletz Reservation, Ore
2 | 62 | Confederated Tribes of the Umatilla Reservation, O
2 | 63 | Confederated Tribes of the Warm Springs Reservatio
2 | 64 | Confederated Tribes and Bands of the Yakama Indian
2 | 65 | Coquille Tribe of Oregon
2 | 66 | Cortina Indian Rancheria of Wintun Indians of Cali
2 | 67 | Coushatta Tribe of Louisiana
2 | 68 | Cow Creek Band of Umpqua Indians of Oregon
2 | 69 | Coyote Valley Band of Pomo Indians of California
2 | 7 | Apache Tribe of Oklahoma
2 | 70 | Crow Tribe of Montana
2 | 71 | Crow Creek Sioux Tribe of the Crow Creek Reservati
2 | 72 | Cuyapaipe Community of Diegueno Mission Indians of
2 | 73 | Death Valley Timbi-Sha Shoshone Band of California
2 | 74 | Delaware Nation, Oklahoma (formerly Delaware Tribe
2 | 75 | Delaware Tribe of Indians, Oklahoma
2 | 76 | Dry Creek Rancheria of Pomo Indians of California
2 | 77 | Duckwater Shoshone Tribe of the Duckwater Reservat
2 | 78 | Eastern Band of Cherokee Indians of North Carolina
2 | 79 | Eastern Shawnee Tribe of Oklahoma
2 | 8 | Arapahoe Tribe of the Wind River Reservation, Wyom
2 | 80 | Elem Indian Colony of Pomo Indians of the Sulphur
2 | 81 | Elk Valley Rancheria, California
2 | 82 | Ely Shoshone Tribe of Nevada
2 | 83 | Enterprise Rancheria of Maidu Indians of Californi
2 | 84 | Flandreau Santee Sioux Tribe of South Dakota
2 | 85 | Forest County Potawatomi Community of Wisconsin Po
2 | 86 | Fort Belknap Indian Community of the Fort Belknap
2 | 87 | Fort Bidwell Indian Community of the Fort Bidwell
2 | 88 | Fort Independence Indian Community of Paiute India
2 | 89 | Fort McDermitt Paiute and Shoshone Tribes of the F
2 | 9 | Aroostook Band of Micmac Indians of Maine
2 | 90 | Fort McDowell Yavapai Nation, Arizona (formerly th
2 | 91 | Fort Mojave Indian Tribe of Arizona, California
2 | 92 | Fort Sill Apache Tribe of Oklahoma
2 | 93 | Gila River Indian Community of the Gila River Indi
2 | 94 | Grand Traverse Band of Ottawa & Chippewa Indians o
2 | 95 | Graton Rancheria, California
2 | 96 | Greenville Rancheria of Maidu Indians of Californi
2 | 97 | Grindstone Indian Rancheria of Wintun-Wailaki Indi
2 | 98 | Guidiville Rancheria of California
2 | 99 | Hannahville Indian Community of Wisconsin Potawato

4.3.2.144 HL7 v3 Code System VaccineManufacturer

URL: https://hl7.org/fhir/STU3/v3/VaccineManufacturer/cs.html

This page is part of the FHIR Specification (v3.0.2: STU 3). The current version which supercedes this version is 4.0.1. For a full list of available versions, see the Directory of published versions

Vocabulary Work Group | Maturity Level: N/A | External | Use Context: Any

This code system (http://hl7.org/fhir/v3/VaccineManufacturer) is defined as part of HL7 v3.

Summary

Defining URL: | http://hl7.org/fhir/v3/VaccineManufacturer
Name: | v3 Code System VaccineManufacturer
Definition: | The manufacturer of a vaccine.
OID: | 2.16.840.1.113883.5.144 (for OID based terminology systems)
Source Resource | XML / JSON

This Code system is used in the following value sets:

* v3 Code System VaccineManufacturer (The manufacturer of a vaccine.)

4.3.2.144.1 Code System Content

Release Date: 2016-11-11

Level | Code | Display | Definition
1 | AB | Abbott Laboratories (includes Ross Products Division) | Abbott Laboratories (includes Ross Products Division)
1 | AD | Adams Laboratories | Adams Laboratories
1 | ALP | Alpha Therapeutic Corporation | Alpha Therapeutic Corporation
1 | AR | Armour [Inactive - use CEN] | Armour [Inactive-use CEN]
1 | AVI | Aviron | Aviron
1 | BA | Baxter Healthcare Corporation | Baxter Healthcare Corporation
1 | BAY | Bayer Corporation (includes Miles, Inc. and Cutter Laboratories) | Bayer Corporation (includes Miles, Inc. and Cutter Laboratories)
1 | BP | Berna Products [Inactive - use BPC] | Berna Products [Inactive-use BPC]
1 | BPC | Berna Products Corporation (includes Swiss Serum and Vaccine Institute Berne) | Berna Products Corporation (includes Swiss Serum and Vaccine Institute Berne)
1 | CEN | Centeon L.L.C. (includes Armour Pharmaceutical Company) | Centeon L.L.C. (includes Armour Pharmaceutical Company)
1 | CHI | Chiron Corporation | Chiron Corporation
1 | CON | Connaught [Inactive - use PMC] | Connaught [Inactive-use PMC]
1 | EVN | Evans Medical Limited (an affiliate of Medeva Pharmaceuticals, Inc.) | Evans Medical Limited (an affiliate of Medeva Pharmaceuticals, Inc.)
1 | GRE | Greer Laboratories, Inc. | Greer Laboratories, Inc.
1 | IAG | Immuno International AG | Immuno International AG
1 | IM | Merieux [Inactive - use PMC] | Merieux [Inactive-use PMC]
1 | IUS | Immuno-U.S., Inc. | Immuno-U.S., Inc.
1 | JPN | The Research Foundation for Microbial Diseases of Osaka University (BIKEN) | The Research Foundation for Microbial Diseases of Osaka University (BIKEN)
1 | KGC | Korea Green Cross Corporation | Korea Green Cross Corporation
1 | LED | Lederle [Inactive - use WAL] | Lederle [Inactive-use WAL]
1 | MA | Massachusetts Public Health Biologic Laboratories | Massachusetts Public Health Biologic Laboratories
1 | MED | MedImmune, Inc. | MedImmune, Inc.
1 | MIL | Miles [Inactive - use BAY] | Miles [Inactive-use BAY]
1 | MIP | Bioport Corporation (formerly Michigan Biologic Products Institute) | Bioport Corporation (formerly Michigan Biologic Products Institute)
1 | MSD | Merck and Co., Inc. | Merck & Co., Inc.
1 | NAB | NABI (formerly North American Biologicals, Inc.) | NABI (formerly North American Biologicals, Inc.)
1 | NAV | North American Vaccine, Inc. | North American Vaccine, Inc.
1 | NOV | Novartis Pharmaceutical Corporation (includes Ciba-Geigy Limited and Sandoz Limited) | Novartis Pharmaceutical Corporation (includes Ciba-Geigy Limited and Sandoz Limited)
1 | NYB | New York Blood Center | New York Blood Center
1 | ORT | Ortho Diagnostic Systems, Inc. | Ortho Diagnostic Systems, Inc.
1 | OTC | Organon Teknika Corporation | Organon Teknika Corporation
1 | PD | Parkedale Pharmaceuticals (formerly Parke-Davis) | Parkedale Pharmaceuticals (formerly Parke-Davis)
1 | PMC | Aventis Pasteur Inc. (formerly Pasteur Merieux Connaught; includes Connaught Laboratories and Pasteur Merieux) | Aventis Pasteur Inc. (formerly Pasteur Merieux Connaught; includes Connaught Laboratories and Pasteur Merieux)
1 | PRX | Praxis Biologics [Inactive - use WAL] | Praxis Biologics [Inactive-use WAL]
1 | SCL | Sclavo, Inc. | Sclavo, Inc.
1 | SI | Swiss Serum and Vaccine Inst. [Inactive - use BPC] | Swiss Serum and Vaccine Inst. [Inactive-use BPC]
1 | SKB | SmithKline Beecham | SmithKline Beecham
1 | USA | United States Army Medical Research and Materiel Command | United States Army Medical Research and Materiel Command
1 | WA | Wyeth-Ayerst [Inactive - use WAL] | Wyeth-Ayerst [Inactive-use WAL]
1 | WAL | Wyeth-Ayerst (includes Wyeth-Lederle Vaccines and Pediatrics, Wyeth Laboratories, Lederle Laboratories, and Praxis Biologics) | Wyeth-Ayerst (includes Wyeth-Lederle Vaccines and Pediatrics, Wyeth Laboratories, Lederle Laboratories, and Praxis Biologics)

4.3.2.1001 HL7 v3 Code System ActMood

URL: https://hl7.org/fhir/STU3/v3/ActMood/cs.html

This page is part of the FHIR Specification (v3.0.2: STU 3). The current version which supercedes this version is 4.0.1. For a full list of available versions, see the Directory of published versions

Vocabulary Work Group | Maturity Level: N/A | External | Use Context: Any

This code system (http://hl7.org/fhir/v3/ActMood) is defined as part of HL7 v3.

Summary

Defining URL: | http://hl7.org/fhir/v3/ActMood

Name: | v3 Code System ActMood

Definition: | OpenIssue: In Ballot 2009May, a strong Negative vote was lodged against several of the concept definitions in the vocabulary used for Act.moodCode. The vote was found "Persuasive With Mod", with the understanding that M and M would undertake a detailed review of these concept definitions for a future release of the RIM.

OID: | 2.16.840.1.113883.5.1001 (for OID based terminology systems)

Source Resource | XML / JSON

This Code system is used in the following value sets:

* v3 Code System ActMood (OpenIssue: In Ballot 2009May, a strong Negative vote was lodged against several of the concept definitions in the vocabulary used for Act.moodCode. The vote was found "Persuasive With Mod", with the understanding that M and M would undertake a detailed review of these concept definitions for a future release of the RIM.)

* ActMoodIntent (An intention or plan to perform a service. Historical note: in previous RIM versions, the intent mood was captured as a separate class hierarchy, called Service_intent_or_order.)

* ActMoodPredicate (Any of the above service moods (e.g., event, intent, or goal) can be turned into a predicate used as a criterion to express conditionals (or queries.) However, currently we allow only criteria on service events.)

* Example-inactive (HL7 v3 ActMood Prdicate codes, including inactive codes)

4.3.2.1001.1 Code System Content

Release Date: 2016-11-11

Level | Code | Display | Definition

1 | (_ActMoodCompletionTrack) Abstract | | These are moods describing activities as they progress in the business cycle, from defined, through planned and ordered to completed.

2 | (_ActMoodPotential) Abstract | | Definition: A possible act.

3 | DEF | definition | Definition: A definition of a kind of act that can occur . OpenIssue: The semantic constructs embodied in DEF and CRT moods seem indistinguishable, and their uses can readily be determined by the context in which these are used. Therefore, this OpenIssue has been created to declare that it is likely that ActMood.DEF will be "retired" in the future in favor of the more general ActMood.CRT.

3 | PERM | permission | Definition: A kind of act that defines a permission that has been granted.

3 | SLOT | resource slot | Definition: A kind of act that may occur during the specified time period.

2 | EVN | event (occurrence) | Definition: An act that actually happens (may be an ongoing act or a documentation of a past act).

2 | INT | intent | Definition: An intention or plan for an act. >UsageNotes: The final outcome of the intent, the act that is intended to occur, is always an event. However the final outcome may be reached indirectly via steps through other intents, such as promise, permission request, or an appointment that may lead to an actual event to occur. Alternatively, the intended act may never occur.

3 | (_ActMoodDesire) Abstract | | Definition: A desire to have an act occur.

4 | (_ActMoodActRequest) Abstract | | Definition: A request (or order) for an act that is part of a defined request/fulfillment cycle. UsageNotes: Use of an HL7 defined request/fulfillment framework is not required to use this mood code.

5 | ARQ | appointment request | Definition: A request act that is specialized for the appointment scheduling request/fulfillment cycle. An appointment request is fulfilled only and completely by an appointment (APT), i.e., all that the appointment request intends is to create an appointment (the actual act may well not happen if that is the professional decision during the appointment).

5 | PERMRQ | permission request | Definition: A request for a permission to perform the act. Typically a payer (or possibly a supervisor) is being requested to give permission to perform the act. As opposed to the RQO, the requestee is not asked to perform or cause to perform the act but only to give the permission.

5 | RQO | request | Definition: A request act that is specialized for an event request/fulfillment cycle. UsageNotes: The fulfillment cycle may involve intermediary fulfilling acts in moods such as PRMS, APT, or even another RQO before being fulfilled by the final event. UsageNotes: The concepts of a "request" and an "order" are viewed as different, because there is an implication of a mandate associated with order. In practice, however, this distinction has no general functional value in the inter-operation of health care computing. "Orders" are commonly refused for a variety of clinical and business reasons, and the notion of a "request" obligates the recipient (the fulfiller) to respond to the sender (the author). Indeed, in many regions, including Australia and Europe, the common term used is "request." Thus, the concept embodies both notions, as there is no useful distinction to be made. If a mandate is to be associated with a request, this will be embodied in the "local" business rules applied to the transactions. Should HL7 desire to provide a distinction between these in the future, the individual concepts could be added as specializations of this concept. The critical distinction here, is the difference between this concept and an "intent", of which it is a specialization. An intent involves decisions by a single party, the author. A request, however, involves decisions by two parties, the author and the fulfiller, with an obligation on the part of the fulfiller to respond to the request indicating that the fulfiller will indeed fulfill the request.

4 | PRP | proposal | Definition: A suggestion that an act might be performed. Not an explicit request, and professional responsibility may or may not be present.

5 | RMD | recommendation | Definition: A suggestion that an act should be performed with an acceptance of some degree of professional responsibility for the resulting act. Not an explicit request. . UsageNotes: Where there is no clear definition or applicable concept of "professional responsibilityâ€?, RMD becomes indistinguishable from PRP. .

3 | PRMS | promise | Definition: A commitment to perform an act (may be either solicited or unsolicited). The committer becomes responsible to the other party for executing the act, and, as a consequence, the other party may rely on the first party to perform or cause to perform the act. UsageNotes: Commitments may be retracted or cancelled.

4 | APT | appointment | Definition: An act that has been scheduled to be performed at a specific place and time.

1 | (_ActMoodPredicate) Abstract | | Definition: An act that expresses condition statements for other acts.

2 | CRT Deprecated | criterion | Deprecation Comment: This concept This codes should no longer be used. Instead, set attribute Act.isCriterionInd to "true" and use the desired mood for your criterion. Definition: A condition that must be true for the source act to be considered.

3 | EVN.CRT Deprecated | event criterion | Deprecation Comment: This concept This codes should no longer be used. Instead, set attribute Act.isCriterionInd to "true" and use the desired mood for your criterion. Definition: A criterion (CRT) that has_match = an event (EVN).

3 | GOL.CRT | goal criterion | A criterion expressed over goals (ActMood.GOL).

3 | INT.CRT | intent criterion | A criterion expressed over intents (ActMood.INT).

4 | PRMS.CRT | promise criterion | A criterion expressed over promises (ActMood.PRMS).

4 | RQO.CRT | request criterion | A criterion expressed over requests or orders (ActMood.RQO).

3 | RSK.CRT | risk criterion | A criterion expressed over risks (ActMood.RSK).

2 | EXPEC | expectation | Definition: An act that is considered to have some noteworthy likelihood of occurring in the future (has_match = event). Examples:Prognosis of a condition, Expected date of discharge from hospital, patient will likely need an emergency decompression of the intracranial pressure by morning. UsageNotes:INT (intent) reflects a plan for the future, which is a declaration to do something. This contrasts with expectation, which is a prediction that something will happen in the future. GOL (goal) reflects a hope rather than a prediction. RSK (risk) reflects a potential negative event that may or may not be expected to happen.

3 | GOL | Goal | Definition: An expectation that is considered to be desirable to occur in the future Examples:Target weight below 80Kg, Stop smoking, Regain ability to walk, goal is to administer thrombolytics to candidate patients presenting with acute myocardial infarction. UsageNotes: INT (intent) reflects a plan for the future, which is a declaration to do something. This contrasts with goal which doesn't represent an intention to act, merely a hope for an eventual result. A goal is distinct from the intended actions to reach that goal. "I will reduce the dose of drug x to 20mg" is an intent. "I hope to be able to get the patient to the point where I can reduce the dose of drug x to 20mg" is a goal. EXPEC (expectation) reflects a prediction rather than a hope. RSK (risk) reflects a potential negative event rather than a hope.

3 | RSK | risk | Definition:An act that may occur in the future and which is regarded as undesirable Examples:Increased risk of DVT, at risk for sub-acute bacterial endocarditis. UsageNotes:Note: An observation in RSK mood expresses the undesirable act, and not the underlying risk factor. A risk factor that is present (e.g. obesity, smoking, etc) should be expressed in event mood. INT (intent) reflects a plan for the future, which is a declaration to do something. This contrasts with RSK (risk), which is the potential that something negative will occur that may or may not ever happen. GOL (goal) reflects a hope to achieve something. EXPEC (expectation) is the prediction of a positive or negative event. This contrasts with RSK (risk), which is the potential that something negative will occur that may or may not ever happen, and may not be expected to happen.

2 | OPT | option | Definition: One of a set of acts that specify an option for the property values that the parent act may have. Typically used in definitions or orders to describe alternatives. An option can only be used as a group, that is, all assigned values must be used together. The actual mood of the act is the same as the parent act, and they must be linked by an actrelationship with type = OPTN.

4.3.2.1002 HL7 v3 Code System ActRelationshipType

URL: https://hl7.org/fhir/STU3/v3/ActRelationshipType/cs.html

This page is part of the FHIR Specification (v3.0.2: STU 3). The current version which supercedes this version is 4.0.1. For a full list of available versions, see the Directory of published versions

Vocabulary Work Group | Maturity Level: N/A | External | Use Context: Any

This code system (http://hl7.org/fhir/v3/ActRelationshipType) is defined as part of HL7 v3.

Summary

Defining URL: | http://hl7.org/fhir/v3/ActRelationshipType
Name: | v3 Code System ActRelationshipType
Definition: | The source is an excerpt from the target.
OID: | 2.16.840.1.113883.5.1002 (for OID based terminology systems)
Source Resource | XML / JSON

This Code system is used in the following value sets:

* ActRelationshipHasComponent (A collection of sub-services as steps or subtasks performed for the source service. Services may be performed sequentially or concurrently.)

* ActRelationshipPertains (This is a very unspecific relationship from one item of clinical information to another. It does not judge about the role the pertinent information plays.)

* v3 Code System ActRelationshipType (The source is an excerpt from the target.)

* ActRelationshipConditional (Specifies under what circumstances (target Act) the source-Act may, must, must not or has occurred)

* ActRelationshipFulfills (The source act fulfills (in whole or in part) the target act. Source act must be in a mood equal or more actual than the target act.)

4.3.2.1002.1 Code System Content

Release Date: 2016-11-11

Level | Code | Display | Definition

1 | ART | act relationship type | Description: A directed association between a source Act and a target Act. Usage Note: This code should never be transmitted in an instance as the value of ActRelationship.typeCode (attribute)

2 | (_ActClassTemporallyPertains) Abstract

2 | (_ActRelationshipAccounting) Abstract | | Codes that describe the relationship between an Act and a financial instrument such as a financial transaction, account or invoice element.

3 | (_ActRelationshipCostTracking) Abstract | | Expresses values for describing the relationship relationship between an InvoiceElement or InvoiceElementGroup and a billable act.

4 | CHRG | has charge | A relationship that provides an ability to associate a financial transaction (target) as a charge to a clinical act (source). A clinical act may have a charge associated with the execution or delivery of the service. The financial transaction will define the charge (bill) for delivery or performance of the service. Charges and costs are distinct terms. A charge defines what is charged or billed to another organization or entity within an organization. The cost defines what it costs an organization to perform or deliver a service or product.

4 | COST | has cost | A relationship that provides an ability to associate a financial transaction (target) as a cost to a clinical act (source). A clinical act may have an inherit cost associated with the execution or delivery of the service. The financial transaction will define the cost of delivery or performance of the service. Charges and costs are distinct terms. A charge defines what is charged or billed to another organization or entity within an organization. The cost defines what it costs an organization to perform or deliver a service or product.

3 | (_ActRelationshipPosting) Abstract | | Expresses values for describing the relationship between a FinancialTransaction and an Account.

4 | CREDIT | has credit | A credit relationship ties a financial transaction (target) to an account (source). A credit, once applied (posted), may have either a positive or negative effect on the account balance, depending on the type of account. An asset account credit will decrease the account balance. A non-asset account credit will decrease the account balance.

4 | DEBIT | has debit | A debit relationship ties a financial transaction (target) to an account (source). A debit, once applied (posted), may have either a positive or negative effect on the account balance, depending on the type of account. An asset account debit will increase the account balance. A

non-asset account debit will decrease the account balance.

2 | (_ActRelationshipConditional) Abstract | | Specifies under what circumstances (target Act) the source-Act may, must, must not or has occurred

3 | CIND | has contra-indication | A contraindication is just a negation of a reason, i.e. it gives a condition under which the action is not to be done. Both, source and target can be any kind of service; target service is in criterion mood. How the strength of a contraindication is expressed (e.g., relative, absolute) is left as an open issue. The priorityNumber attribute could be used.

3 | PRCN | has pre-condition | A requirement to be true before a service is performed. The target can be any service in criterion mood. For multiple pre-conditions a conjunction attribute (AND, OR, XOR) is applicable.

3 | RSON | has reason | Description: The reason or rationale for a service. A reason link is weaker than a trigger, it only suggests that some service may be or might have been a reason for some action, but not that this reason requires/required the action to be taken. Also, as opposed to the trigger, there is no strong timely relation between the reason and the action. As well as providing various types of information about the rationale for a service, the RSON act relationship is routinely used between a SBADM act and an OBS act to describe the indication for use of a medication. Child concepts may be used to describe types of indication. Discussion: In prior releases, the code "SUGG" (suggests) was expressed as "an inversion of the reason link." That code has been retired in favor of the inversion indicator that is an attribute of ActRelationship.

4 | BLOCK | blocks | Definition: The source act is performed to block the effects of the target act. This act relationship should be used when describing near miss type incidents where potential harm could have occurred, but the action described in the source act blocked the potential harmful effects of the incident actually occurring.

4 | DIAG | diagnoses | Description: The source act is intended to help establish the presence of a (an adverse) situation described by the target act. This is not limited to diseases but can apply to any adverse situation or condition of medical or technical nature.

4 | IMM | immunization against | Description: The source act is intented to provide immunity against the effects of the target act (the target act describes an infectious disease)

5 | ACTIMM | active immunization against | Description: The source act is intended to provide active immunity against the effects of the target act (the target act describes an infectious disease)

5 | PASSIMM | passive immunization against | Description: The source act is intended to provide passive immunity against the effects of the target act (the target act describes an infectious disease).

4 | MITGT | mitigates | The source act removes or lessens the occurrence or effect of the target act.

5 | RCVY | recovers | Definition: The source act is performed to recover from the effects of the target act.

4 | PRYLX | prophylaxis of | Description: The source act is intended to reduce the risk of of an adverse situation to emerge as described by the target act. This is not limited to diseases but can apply to any adverse situation or condition of medical or technical nature.

4 | TREAT | treats | Description: The source act is intended to improve a pre-existing adverse situation described by the target act. This is not limited to diseases but can apply to any adverse situation or condition of medical or technical nature.

5 | ADJUNCT | adjunctive treatment | Description: The source act is intended to offer an additional treatment for the management or cure of a pre-existing adverse situation described by the target act. This is not limited to diseases but can apply to any adverse situation or condition of medical or technical nature. It is not a requirement that the non-adjunctive treatment is explicitly specified.

5 | MTREAT | maintenance treatment | Description: The source act is intended to provide long term maintenance improvement or management of a pre-existing adverse situation described by the target act. This is not limited to diseases but can apply to any adverse situation or condition of medical or technical nature.

5 | PALLTREAT | palliates | Description: The source act is intended to provide palliation for the effects of the target act.

5 | SYMP | symptomatic relief | Description: The source act is intented to provide symptomatic relief for the effects of the target act.

3 | TRIG | has trigger | A pre-condition that if true should result in the source Act being executed. The target is in typically in criterion mood. When reported after the fact (i.e. the criterion has been met) it may be in Event mood. A delay between the trigger and the triggered action can be specified. Discussion: This includes the concept of a required act for a service or financial instrument such as an insurance plan or policy. In such cases, the trigger is the occurrence of a specific condition such as coverage limits being exceeded.

2 | (_ActRelationshipTemporallyPertains) Abstract | | Abstract collector for ActRelationhsip types that relate two acts by their timing.

3 | (_ActRelationshipTemporallyPertainsApproximates) Abstract | | Abstract collector for ActRelationship types that relate two acts by their approximate timing.

4 | ENE | ends near end | A relationship in which the source act's effective time ends near the end of the target act's effective time. Near is defined separately as a time interval. Usage Note: Inverse code is ENS

5 | ECW | ends concurrent with | A relationship in which the source act's effective time ends with the end of the target act's effective time. UsageNote: This code is reflexive. Therefore its inverse code is itself.

6 | CONCURRENT | concurrent with | A relationship in which the source act's effective time is the same as the target act's effective time. UsageNote: This code is reflexive. Therefore its inverse code is itself.

6 | SBSECWE | starts before start of, ends with | The source Act starts before the start of the target Act, and ends with the target Act. UsageNote: Inverse code is SASECWE

4 | ENS | ends near start | A relationship in which the source act's effective time ends near the start of the target act's effective time. Near is defined separately as a time interval. Usage Note: Inverse code is ENE

5 | ECWS | ends concurrent with start of | The source Act ends when the target act starts (i.e. if we say "ActOne ECWS ActTwo", it means that ActOne ends when ActTwo starts, therefore ActOne is the source and ActTwo is the target). UsageNote: Inverse code is SCWE

4 | SNE | starts near end | A relationship in which the source act's effective time starts near the end of the target act's effective time. Near is defined separately as a time interval. Usage Note: Inverse code is SNS

5 | SCWE | starts concurrent with end of | The source Act starts when the target act ends (i.e. if we say "ActOne SCWE ActTwo", it means that ActOne starts when ActTwo ends, therefore ActOne is the source and ActTwo is the target). UsageNote: Inverse code is SBSECWS

4 | SNS | starts near start | A relationship in which the source act's effective time starts near the start of the target act's effective time. Near is defined separately as a time interval. Usage Note: Inverse code is SNE

5 | SCW | starts concurrent with | A relationship in which the source act's effective time starts with the start of the target act's effective time. UsageNote: This code is reflexive. Therefore its inverse code is itself.

6 | CONCURRENT

6 | SCWSEBE | starts with. ends before end of | The source Act starts with.the target Act and ends before the end of the target Act. UsageNote: Inverse code is SCWSEAE

6 | SCWSEAE | starts with, ends after end of | The source Act starts with the target Act, and ends after the end of the target Act.

3 | EAS | ends after start of | A relationship in which the source act ends after the target act starts. UsageNote: Inverse code is SBE

4 | EAE | ends after end of | A relationship in which the source act ends after the target act ends. UsageNote: Inverse code is EBE

5 | SASEAE | starts after start of, ends after end of | The source Act starts after start of the target Act and ends after end of the target Act. UsageNote: Inverse code is SBSEBE

6 | SBEEAE | contains end of | The source Act contains the end of the target Act. UsageNote: Inverse code is EDU

7 | SASSBEEAS | start after start of, contains end of | The source Act start after the start of the target Act, and contains the end of the target Act. UsageNote: Inverse code is SBSEASEBE

7 | SBSEAE | contains time of | The source Act contains the time of the target Act. UsageNote: Inverse code is DURING
7 | SCWSEAE
6 | SASSBEEAS
4 | SAS | starts after start of | The source Act starts after the start of the target Act (i.e. if we say "ActOne SAS ActTwo", it means that ActOne starts after the start of ActTwo, therefore ActOne is the source and ActTwo is the target). UsageNote: Inverse code is SBS
5 | SASEAE
5 | SAE | starts after end of | A relationship in which the source act starts after the target act ends. UsageNote: Inverse code is EBS
5 | DURING | occurs during | A relationship in which the source act's effective time is wholly within the target act's effective time (including end points, as defined in the act's effective times) UsageNote: Inverse code is SBSEAE
5 | SASECWE | starts after start of, ends with | The source Act starts after start of the target Act, and ends with the target Act. UsageNote: Inverse code is SBSECWE
3 | EASORECWS | ends after or concurrent with start of | A relationship in which the source act's effective time ends after or concurrent with the start of the target act's effective time. Usage Note: Inverse code is EBSORECWS
4 | EAS
4 | EAEORECW | ends after or concurrent with end of | A relationship in which the source act's effective time ends after or concurrent with the end of the target act's effective time. Usage Note: Inverse code is EBEORECW
5 | EAE
5 | ECW
4 | ECWS
3 | INDEPENDENT | independent of time of | The source Act is independent of the time of the target Act. UsageNote: This code is reflexive. Therefore its inverse code is itself.
3 | SAEORSCWE | starts after or concurrent with end of | A relationship in which the source act's effective time starts after or concurrent with the end of the target act's effective time. Usage Note: Inverse code is SBEORSCWE
4 | SCWE
4 | SAE
3 | SASORSCW | starts after or concurrent with start of | A relationship in which the source act's effective time starts after or concurrent with the start of the target act's effective time. Usage Note: Inverse code is SBSORSCW
4 | SAS
4 | SCW
3 | SBEORSCWE | starts before or concurrent with end of | A relationship in which the source act's effective time starts before or concurrent with the end of the target act's effective time. Usage Note: Inverse code is SAEORSCWE
4 | OVERLAP | overlaps with | A relationship in which the source act's effective time overlaps the target act's effective time in any way. UsageNote: This code is reflexive. Therefore its inverse code is itself.
5 | ECW
5 | EDU | ends during | A relationship in which the source act ends within the target act's effective time (including end points, as defined in the act's effective times) UsageNote: Inverse code is SBEEAE
6 | SBSEASEBE | contains start of, ends before end of | The source Act contains the start of the target Act, and ends before the end of the target Act. UsageNote: Inverse code is SASSBEEAS
6 | SCWSEBE
5 | SBEEAE
5 | SBSEAS | contains start of | The source Act contains the start of the target Act. UsageNote: Inverse code is SDU
6 | SBSECWE
6 | SBSEASEBE
6 | SBSEAE
5 | SCW
5 | SCWE
5 | SDU | starts during | A relationship in which the source act starts within the target act's effective time (including end points, as defined in the act's effective times) UsageNote: Inverse code is SBSEAS
6 | SASSBEEAS
4 | SBE | starts before end of | The source Act starts before the end of the target Act (i.e. if we say "ActOne SBE ActTwo", it means that ActOne starts before the end of ActTwo, therefore ActOne is the source and ActTwo is the target). UsageNote: Inverse code is EAS
5 | EBE | ends before end of | The source Act ends before the end of the target Act (i.e. if we say "ActOne EBE ActTwo", it means that ActOne ends before the end of ActTwo, therefore ActOne is the source and ActTwo is the target). UsageNote: Inverse code is EAE
6 | SBSEBE | starts before start of, ends before end of | The source Act starts before the start of the target Act, and ends before the end of the target Act. UsageNote: Inverse code is SASEAE
7 | SBSEASEBE
7 | EBSORECWS | ends before or concurrent with start of | A relationship in which the source act's effective time ends before or concurrent with the start of the target act's effective time. Usage Note: Inverse code is EASORECWS
8 | ECWS
8 | EBS | ends before start of | A relationship in which the source act ends before the target act starts. UsageNote: Inverse code is SAE
5 | SBSEASEBE
5 | SCWSEBE
5 | EBEORECW | ends before or concurrent with end of | A relationship in which the source act's effective time ends before or concurrent with the end of the target act's effective time. Usage Note: Inverse code is EAEORECW
6 | ECW
6 | EBE
5 | SBSORSCW | starts before or concurrent with start of | A relationship in which the source act's effective time starts before or concurrent with the start of the target act's effective time. Usage Note: Inverse code is SASORSCW
6 | SCW
6 | SBS | starts before start of | A relationship in which the source act begins before the target act begins. UsageNote: Inverse code is SAS
7 | SBSEBE
7 | SBSEAS
2 | AUTH | authorized by | A relationship in which the target act authorizes or certifies the source act.

2 | CAUS | is etiology for | Description: An assertion that an act was the cause of another act.This is stronger and more specific than the support link. The source (cause) is typically an observation, but may be any act, while the target may be any act. Examples: a growth of Staphylococcus aureus may be considered the cause of an abscess contamination of the infusion bag was deemed to be the cause of the infection that the patient experienced lack of staff on the shift was deemed to be a supporting factor (proximal factor) causing the patient safety incident where the patient fell out of bed because the bed-sides had not been put up which caused the night patient to fall out of bed

2 | COMP | has component | The target act is a component of the source act, with no semantics regarding composition or aggregation implied.

3 | CTRLV | has control variable | A relationship from an Act to a Control Variable. For example, if a Device makes an Observation, this relates the Observation to its Control Variables documenting the device's settings that influenced the observation.

3 | MBR | has member | The target Acts are aggregated by the source Act. Target Acts may have independent existence, participate in multiple ActRelationships, and do not contribute to the meaning of the source. UsageNotes: This explicitly represents the conventional notion of aggregation. The target Act is part of a collection of Acts (no implication is made of cardinality, a source of Acts may contain zero, one, or more member target Acts). It is expected that this will be primarily used with _ActClassRecordOrganizer, BATTERY, and LIST

4 | STEP | has step | A collection of sub-services as steps or subtasks performed for the source service. Services may be performed sequentially or concurrently. UsageNotes: Sequence of steps may be indicated by use of _ActRelationshipTemporallyPertains, as well as via ActRelationship.sequenceNumber, ActRelationship.pauseQuantity, Target.priorityCode. OpenIssue: Need Additional guidelines on when each approach should be used.

5 | ARR | arrival | The relationship that links to a Transportation Act (target) from another Act (source) indicating that the subject of the source Act entered into the source Act by means of the target Transportation act.

5 | DEP | departure | The relationship that links to a Transportation Act (target) from another Act (source) indicating that the subject of the source Act departed from the source Act by means of the target Transportation act.

3 | PART | has part | The source Act is a composite of the target Acts. The target Acts do not have an existence independent of the source Act. UsageNote: In UML 1.1, this is a "composition" defined as: "A form of aggregation with strong ownership and coincident lifetime as part of the whole. Parts with non-fixed multiplicity may be created after the composite itself, but once created they live and die with it (i.e., they share lifetimes). Such parts can also be explicitly removed before the death of the composite. Composition may be recursive."

2 | COVBY | covered by | A relationship in which the source act is covered by or is under the authority of a target act. A financial instrument such as an Invoice Element is covered by one or more specific instances of an Insurance Policy.

2 | DRIV | is derived from | Associates a derived Act with its input parameters. E.G., an anion-gap observation can be associated as being derived from given sodium-, (potassium-,), chloride-, and bicarbonate-observations. The narrative content (Act.text) of a source act is wholly machine-derived from the collection of target acts.

2 | ELNK | episodeLink | Expresses an association that links two instances of the same act over time, indicating that the instance are part of the same episode, e.g. linking two condition nodes for episode of illness; linking two encounters for episode of encounter.

2 | EVID | provides evidence for | Indicates that the target Act provides evidence in support of the action represented by the source Act. The target is not a 'reason' for the source act, but rather gives supporting information on why the source act is an appropriate course of action. Possible targets might be clinical trial results, journal articles, similar successful therapies, etc. Rationale: Provides a mechanism for conveying clinical justification for non-approved or otherwise non-traditional therapies.

2 | EXACBY | exacerbated by | Description:The source act is aggravated by the target act. (Example "chest pain" EXACBY "exercise")

2 | EXPL | has explanation | This is the inversion of support. Used to indicate that a given observation is explained by another observation or condition.

2 | INTF | interfered by | the target act documents a set of circumstances (events, risks) which prevent successful completion, or degradation of quality of, the source Act. UsageNote: This provides the semantics to document barriers to care

2 | ITEMSLOC | items located | Items located

2 | LIMIT | limited by | A relationship that limits or restricts the source act by the elements of the target act. For example, an authorization may be limited by a financial amount (up to $500). Target Act must be in EVN.CRIT mood.

2 | META | has metadata | Definition: Indicates that the attributes and associations of the target act provide metadata (for example, identifiers, authorship, etc.) for the source act. Constraint: Source act must have either a mood code that is not "EVN" (event) or its "isCriterion" attribute must set to "true". Target act must be an Act with a mood code of EVN and with isCriterionInd attribute set to "true".

2 | MFST | is manifestation of | An assertion that a new observation may be the manifestation of another existing observation or action. This assumption is attributed to the same actor who asserts the manifestation. This is stronger and more specific than an inverted support link. For example, an agitated appearance can be asserted to be the manifestation (effect) of a known hyperthyroxia. This expresses that one might not have realized a symptom if it would not be a common manifestation of a known condition. The target (cause) may be any service, while the source (manifestation) must be an observation.

2 | NAME | assigns name | Used to assign a "name" to a condition thread. Source is a condition node, target can be any service.

2 | OUTC | has outcome | An observation that should follow or does actually follow as a result or consequence of a condition or action (sometimes called "post-conditional".) Target must be an observation as a goal, risk or any criterion. For complex outcomes a conjunction attribute (AND, OR, XOR) can be used. An outcome link is often inverted to describe an outcome assessment.

3 | (_ActRelationsipObjective) Abstract | | The target act is a desired outcome of the source act. Source is any act (typically an intervention). Target must be an observation in criterion mood.

4 | OBJC | has continuing objective | A desired state that a service action aims to maintain. E.g., keep systolic blood pressure between 90 and 110 mm Hg. Source is an intervention service. Target must be an observation in criterion mood.

4 | OBJF | has final objective | A desired outcome that a service action aims to meet finally. Source is any service (typically an intervention). Target must be an observation in criterion mood.

3 | GOAL | has goal | A goal that one defines given a patient's health condition. Subsequently planned actions aim to meet that goal. Source is an observation or condition node, target must be an observation in goal mood.

3 | RISK | has risk | A noteworthy undesired outcome of a patient's condition that is either likely enough to become an issue or is less likely but dangerous enough to be addressed.

2 | PERT | has pertinent information | This is a very unspecific relationship from one item of clinical information to another. It does not judge about the role the pertinent information plays.

2 | PREV | has previous instance | A relationship in which the target act is a predecessor instance to the source act. Generally each of these instances is similar, but no identical. In healthcare coverage it is used to link a claim item to a previous claim item that might have claimed for the same set of services.

2 | REFR | refers to | A relationship in which the target act is referred to by the source act. This permits a simple reference relationship that distinguishes between the referent and the referee.

3 | USE | uses | Indicates that the source act makes use of (or will make use of) the information content of the target act. UsageNotes: A usage relationship only makes sense if the target act is authored and occurs independently of the source act. Otherwise a simpler relationship such as COMP would be appropriate. Rationale: There is a need when defining a clinical trial protocol to indicate that the protocol makes use of other protocol or treatment specifications. This is stronger than the assertion of "references". References may exist without usage, and in a clinical trial protocol is common to assert both: what other specifications does this trial use and what other specifications does it merely reference.

2 | REFV | has reference values | Reference ranges are essentially descriptors of a class of result values assumed to be "normal", "abnormal", or "critical." Those can vary by sex, age, or any other criterion. Source and target are observations, the target is in criterion mood. This link type can act as a trigger in case of alarms being triggered by critical results.

2 | RELVBY | relieved by | Description:The source act is wholly or partially alleviated by the target act. (Example "chest pain" RELVBY "sublingual nitroglycerin administration")

2 | SEQL | is sequel | An act relationship indicating that the source act follows the target act. The source act should in principle represent the same kind of act as the target. Source and target need not have the same mood code (mood will often differ). The target of a sequel is called antecedent. Examples for sequel relationships are: revision, transformation, derivation from a prototype (as a specialization is a derivation of a generalization), followup, realization, instantiation.

3 | APND | is appendage | An addendum (source) to an existing service object (target), containing supplemental information. The addendum is itself an original service object linked to the supplemented service object. The supplemented service object remains in place and its content and status are unaltered.

3 | BSLN | has baseline | Indicates that the target observation(s) provide an initial reference for the source observation or observation group. UsageConstraints: Both source and target must be Observations or specializations thereof.

3 | COMPLY | complies with | Description:The source act complies with, adheres to, conforms to, or is permissible under (in whole or in part) the policy, contract, agreement, law, conformance criteria, certification guidelines or requirement conveyed by the target act. Examples for compliance relationships are: audits of adherence with a security policy, certificate of conformance to system certification requirements, or consent directive in compliance with or permissible under a privacy policy.

3 | DOC | documents | The source act documents the target act.

3 | FLFS | fulfills | The source act fulfills (in whole or in part) the target act. Source act must be in a mood equal or more actual than the target act.

4 | OCCR | occurrence | The source act is a single occurrence of a repeatable target act. The source and target act can be in any mood on the "completion track" but the source act must be as far as or further along the track than the target act (i.e., the occurrence of an intent can be an event but not vice versa).

4 | OREF | references order | Relates either an appointment request or an appointment to the order for the service being scheduled.

4 | SCH | schedules request | Associates a specific time (and associated resources) with a scheduling request or other intent.

3 | GEN | has generalization | The generalization relationship can be used to express categorical knowledge about services (e.g., amilorid, triamterene, and spironolactone have the common generalization potassium sparing diuretic).

3 | GEVL | evaluates (goal) | A goal-evaluation links an observation (intent or actual) to a goal to indicate that the observation evaluates the goal. Given the goal and the observation, a "goal distance" (e.g., goal to observation) can be "calculated" and need not be sent explicitly.

3 | INST | instantiates (master) | Used to capture the link between a potential service ("master" or plan) and an actual service, where the actual service instantiates the potential service. The instantiation may override the master's defaults.

3 | MOD | modifies | Definition: Used to link a newer version or 'snapshot' of a business object (source) to an older version or 'snapshot' of the same business object (target). Usage:The identifier of the Act should be the same for both source and target. If the identifiers are distinct, RPLC should be used instead. Name from source to target = "modifiesPrior" Name from target to source = "modifiesByNew"

3 | MTCH | matches (trigger) | A trigger-match links an actual service (e.g., an observation or procedure that took place) with a service in criterion mood. For example if the trigger is "observation of pain" and pain is actually observed, and if that pain-observation caused the trigger to fire, that pain-observation can be linked with the trigger.

3 | OPTN | has option | A relationship between a source Act that provides more detailed properties to the target Act. The source act thus is a specialization of the target act, but instead of mentioning all the inherited properties it only mentions new property bindings or refinements. The typical use case is to specify certain alternative variants of one kind of Act. The priorityNumber attribute is used to weigh refinements as preferred over other alternative refinements. Example: several routing options for a drug are specified as one SubstanceAdministration for the general treatment with attached refinements for the various routing options.

3 | RCHAL | re-challenge | Description:A relationship in which the target act is carried out to determine whether an effect attributed to the source act can be recreated.

3 | REV | reverses | A relationship between a source Act that seeks to reverse or undo the action of the prior target Act. Example: A posted financial transaction (e.g., a debit transaction) was applied in error and must be reversed (e.g., by a credit transaction) the credit transaction is identified as an undo (or reversal) of the prior target transaction. Constraints: the "completion track" mood of the target Act must be equally or more "actual" than the source act. I.e., when the target act is EVN the source act can be EVN, or any INT. If the target act is INT, the source act can be INT.

3 | RPLC | replaces | A replacement source act replaces an existing target act. The state of the target act being replaced becomes obselete, but the act is typically still retained in the system for historical reference. The source and target must be of the same type.

3 | SUCC | succeeds | Definition: A new act that carries forward the intention of the original act, but does not completely replace it. The status of the predecessor act must be 'completed'. The original act is the target act and the successor is the source act.

3 | UPDT | updates (condition) | A condition thread relationship specifically links condition nodes together to form a condition thread. The source is the new condition node and the target links to the most recent node of the existing condition thread.

3 | XCRPT | Excerpts | The source is an excerpt from the target.

4 | VRXCRPT | Excerpt verbatim | The source is a direct quote from the target.

3 | XFRM | transformation | Used when the target Act is a transformation of the source Act. (For instance, used to show that a CDA document is a transformation of a DICOM SR document.)

2 | SPRT | has support | Used to indicate that an existing service is suggesting evidence for a new observation. The assumption of support is attributed to the same actor who asserts the observation. Source must be an observation, target may be any service (e.g., to indicate a status post).

3 | SPRTBND | has bounded support | A specialization of "has support" (SPRT), used to relate a secondary observation to a Region of Interest on a multidimensional observation, if the ROI specifies the true boundaries of the secondary observation as opposed to only marking the approximate area. For example, if the start and end of an ST elevation episode is visible in an EKG, this relation would indicate the ROI bounds the "ST elevation" observation -- the ROI defines the true beginning and ending of the episode. Conversely, if a ROI simply contains ST elevation, but it does not define the bounds (start and end) of the episode, the more general "has support" relation is used. Likewise, if a ROI on an image defines the true bounds of a "1st degree burn", the relation "has bounded support" is used; but if the ROI only points to the approximate area of the burn, the general "has support" relation is used.

2 | SUBJ | has subject | Relates an Act to its subject Act that the first Act is primarily concerned with. Examples The first Act may be a ControlAct manipulating the subject Act The first act is a region of interest (ROI) that defines a region within the subject Act. The first act is a reporting or notification Act, that echos the subject Act for a specific new purpose. Constraints An Act may have multiple subject acts. Rationale The ActRelationshipType "has subject" is similar to the ParticipationType "subject", Acts that primarily operate on physical subjects use the Participation, those Acts that primarily operate on other Acts (other information) use the ActRelationship.

3 | QUALF | has qualifier | The target observation qualifies (refines) the semantics of the source observation. UsageNote: This is not intended to replace concept refinement and qualification via vocabulary. It is used when there are multiple components which together provide the complete understanding of the source Act.

2 | SUMM | summarized by | An act that contains summary values for a list or set of subordinate acts. For example, a summary of transactions for a particular accounting period.

2 | VALUE | has value | Description:Indicates that the target Act represents the result of the source observation Act. FormalConstraint: Source Act must be an Observation or specialization there-of. Source Act must not have the value attribute specified UsageNote: This relationship allows the result of an observation to be fully expressed as RIM acts as opposed to being embedded in the value attribute. For example, sending a Document act as the result of an imaging observation, sending a list of Procedures and/or other acts as the result of a medical history observation. The valueNegationInd attribute on the source Act has the same semantics of "negated finding" when it applies to the target of a VALUE ActRelationship as it does to the value attribute. On the other hand, if the ActRelationship.negationInd is true for a VALUE ActRelationship, that means the specified observation does not have the indicated value but does not imply a negated finding. Because the semantics are extremely close, it is recommended that Observation.valueNegationInd be used, not ActRelationship.negationInd. OpenIssue: The implications of negationInd on ActRelationship and the valueNegationind on Observation.
1 | CURE | curative indication
1 | CURE.ADJ | adjunct curative indication
1 | MTGT.ADJ | adjunct mitigation
1 | RACT
1 | SUGG

4.3.2.1008 HL7 v3 Code System NullFlavor

URL: https://hl7.org/fhir/STU3/v3/NullFlavor/cs.html

This page is part of the FHIR Specification (v3.0.2: STU 3). The current version which supercedes this version is 4.0.1. For a full list of available versions, see the Directory of published versions

Vocabulary Work Group | Maturity Level: N/A | External | Use Context: Any

This code system (http://hl7.org/fhir/v3/NullFlavor) is defined as part of HL7 v3.

Summary

Defining URL: | http://hl7.org/fhir/v3/NullFlavor
Name: | v3 Code System NullFlavor
Definition: | A collection of codes specifying why a valid value is not present.
OID: | 2.16.840.1.113883.5.1008 (for OID based terminology systems)
Source Resource | XML / JSON

This Code system is used in the following value sets:

* HumanNameAssemblyOrder (A code that represents the preferred display order of the components of a human name)

* Marital Status Codes (This value set defines the set of codes that can be used to indicate the marital status of a person.)

* v2 Expanded Yes/no Indicator (FHIR Value set/code system definition for HL7 v2 table 0532 (Expanded Yes/no Indicator))

* SpecialCourtesy (This value set defines a set of codes that can be used to indicate special courtesies provided to the patient.)

* v2 CWE statuses (FHIR Value set/code system definition for HL7 v2 table 0353 (CWE statuses))

* v3 Code System NullFlavor (A collection of codes specifying why a valid value is not present.)

4.3.2.1008.1 Code System Content

Release Date: 2016-11-11

Level | Code | Display | Definition
1 | NI | NoInformation | Description:The value is exceptional (missing, omitted, incomplete, improper). No information as to the reason for being an exceptional value is provided. This is the most general exceptional value. It is also the default exceptional value.
2 | INV | invalid | Description:The value as represented in the instance is not a member of the set of permitted data values in the constrained value domain of a variable.
3 | DER | derived | Description:An actual value may exist, but it must be derived from the provided information (usually an EXPR generic data type extension will be used to convey the derivation expressionexpression .
3 | OTH | other | Description:The actual value is not a member of the set of permitted data values in the constrained value domain of a variable. (e.g., concept not provided by required code system). Usage Notes: This flavor and its specializations are most commonly used with the CD datatype and its flavors. However, it may apply to *any* datatype where the constraints of the type are tighter than can be conveyed. For example, a PQ that is for a true measured amount whose units are not supported in UCUM, a need to convey a REAL when the type has been constrained to INT, etc. With coded datatypes, this null flavor may only be used if the vocabulary binding has a coding strength of CNE. By definition, all local codes and original text are part of the value set if the coding strength is CWE.
4 | NINF | negative infinity | Negative infinity of numbers.
4 | PINF | positive infinity | Positive infinity of numbers.
3 | UNC | un-encoded | Description: The actual value has not yet been encoded within the approved value domain. Example: Original text or a local code has been specified but translation or encoding to the approved value set has not yet occurred due to limitations of the sending system. Original text has been captured for a PQ, but not attempt has been made to split the value and unit or to encode the unit in UCUM. Usage Notes: If it is known that it is not possible to encode the concept, OTH should be used instead. However, use of UNC does not necessarily guarantee the concept will be encodable, only that encoding has not been attempted. Data type properties such as original text and translations may be present when this null flavor is included.
2 | MSK | masked | There is information on this item available but it has not been provided by the sender due to security, privacy or other reasons. There may be an alternate mechanism for gaining access to this information. Note: using this null flavor does provide information that may be a breach of confidentiality, even though no detail data is provided. Its primary purpose is for those circumstances where it is necessary to inform the receiver that the information does exist without providing any detail.
2 | NA | not applicable | Known to have no proper value (e.g., last menstrual period for a male).
2 | UNK | unknown | Description:A proper value is applicable, but not known. Usage Notes: This means the actual value is not known. If the only thing that is unknown is how to properly express the value in the necessary constraints (value set, datatype, etc.), then the OTH or UNC flavor should be used. No properties should be included for a datatype with this property unless: Those properties themselves directly translate to a semantic of "unknown". (E.g. a local code sent as a translation that conveys 'unknown') Those properties further qualify the nature of what is unknown. (E.g.

specifying a use code of "H" and a URL prefix of "tel:" to convey that it is the home phone number that is unknown.)
3 | ASKU | asked but unknown | Information was sought but not found (e.g., patient was asked but didn't know)
4 | NAV | temporarily unavailable | Information is not available at this time but it is expected that it will be available later.
3 | NASK | not asked | This information has not been sought (e.g., patient was not asked)
3 | NAVU | Not available | Information is not available at this time (with no expectation regarding whether it will or will not be available in the future).
4 | NAV
3 | QS | Sufficient Quantity | Description:The specific quantity is not known, but is known to be non-zero and is not specified because it makes up the bulk of the material. e.g. 'Add 10mg of ingredient X, 50mg of ingredient Y, and sufficient quantity of water to 100mL.' The null flavor would be used to express the quantity of water.
3 | TRC | trace | The content is greater than zero, but too small to be quantified.
1 | NP | not present | Value is not present in a message. This is only defined in messages, never in application data! All values not present in the message must be replaced by the applicable default, or no-information (NI) as the default of all defaults.

4.3.2.1009 HL7 v3 Code System CompressionAlgorithm

URL: https://hl7.org/fhir/STU3/v3/CompressionAlgorithm/cs.html

This page is part of the FHIR Specification (v3.0.2: STU 3). The current version which supercedes this version is 4.0.1. For a full list of available versions, see the Directory of published versions

Vocabulary Work Group | Maturity Level: N/A | External | Use Context: Any

This code system (http://hl7.org/fhir/v3/CompressionAlgorithm) is defined as part of HL7 v3.

Summary

Defining URL: | http://hl7.org/fhir/v3/CompressionAlgorithm
Name: | v3 Code System CompressionAlgorithm
Definition: | **** MISSING DEFINITIONS ****
OID: | 2.16.840.1.113883.5.1009 (for OID based terminology systems)
Source Resource | XML / JSON

This Code system is used in the following value sets:

* v3 Code System CompressionAlgorithm (**** MISSING DEFINITIONS ****)

4.3.2.1009.1 Code System Content

Release Date: 2016-11-11

Level | Code | Display | Definition
1 | BZ | bzip | bzip-2 compression format. See [http://www.bzip.org/] for more information.
1 | DF | deflate | The deflate compressed data format as specified in RFC 1951 [http://www.ietf.org/rfc/rfc1951.txt].
1 | GZ | gzip | A compressed data format that is compatible with the widely used GZIP utility as specified in RFC 1952 [http://www.ietf.org/rfc/rfc1952.txt] (uses the deflate algorithm).
1 | Z | compress | Original UNIX compress algorithm and file format using the LZC algorithm (a variant of LZW). Patent encumbered and less efficient than deflate.
1 | Z7 | Z7 | 7z compression file format. See [http://www.7-zip.org/7z.html] for more information.
1 | ZL | zlib | A compressed data format that also uses the deflate algorithm. Specified as RFC 1950 [http://www.ietf.org/rfc/rfc1952.txt]

4.3.2.1010 HL7 v3 Code System IntegrityCheckAlgorithm

URL: https://hl7.org/fhir/STU3/v3/IntegrityCheckAlgorithm/cs.html

This page is part of the FHIR Specification (v3.0.2: STU 3). The current version which supercedes this version is 4.0.1. For a full list of available versions, see the Directory of published versions

Vocabulary Work Group | Maturity Level: N/A | External | Use Context: Any

This code system (http://hl7.org/fhir/v3/IntegrityCheckAlgorithm) is defined as part of HL7 v3.

Summary

Defining URL: | http://hl7.org/fhir/v3/IntegrityCheckAlgorithm
Name: | v3 Code System IntegrityCheckAlgorithm
Definition: | **** MISSING DEFINITIONS ****
OID: | 2.16.840.1.113883.5.1010 (for OID based terminology systems)
Source Resource | XML / JSON

This Code system is used in the following value sets:

* v3 Code System IntegrityCheckAlgorithm (**** MISSING DEFINITIONS ****)

4.3.2.1010.1 Code System Content

Release Date: 2016-11-11

Level | Code | Display | Definition
1 | SHA-1 | secure hash algorithm - 1 | This algorithm is defined in FIPS PUB 180-1: Secure Hash Standard. As of April 17, 1995.
1 | SHA-256 | secure hash algorithm - 256 | This algorithm is defined in FIPS PUB 180-2: Secure Hash Standard.

4.3.2.1017 HL7 v3 Code System CalendarType

URL: https://hl7.org/fhir/STU3/v3/CalendarType/cs.html

This page is part of the FHIR Specification (v3.0.2: STU 3). The current version which supercedes this version is 4.0.1. For a full list of available versions, see the Directory of published versions

Vocabulary Work Group | Maturity Level: N/A | External | Use Context: Any

This code system (http://hl7.org/fhir/v3/CalendarType) is defined as part of HL7 v3.

Summary

Defining URL: | http://hl7.org/fhir/v3/CalendarType
Name: | v3 Code System CalendarType
Definition: | **** MISSING DEFINITIONS ****
OID: | 2.16.840.1.113883.5.1017 (for OID based terminology systems)
Source Resource | XML / JSON

This Code system is used in the following value sets:

* v3 Code System CalendarType (**** MISSING DEFINITIONS ****)

4.3.2.1017.1 Code System Content

Release Date: 2016-11-11

Level | Code | Display | Definition
1 | GREG | Gregorian | The Gregorian calendar is in effect in the most countries of Christian influence since approximately 1582. This calendar superceded the Julian calendar.

4.3.2.1020 HL7 v3 Code System ProbabilityDistributionType

URL: https://hl7.org/fhir/STU3/v3/ProbabilityDistributionType/cs.html

This page is part of the FHIR Specification (v3.0.2: STU 3). The current version which supercedes this version is 4.0.1. For a full list of available versions, see the Directory of published versions

Vocabulary Work Group | Maturity Level: N/A | External | Use Context: Any

This code system (http://hl7.org/fhir/v3/ProbabilityDistributionType) is defined as part of HL7 v3. Related FHIR content: ProbabilityDistributionType.

Summary

Defining URL: | http://hl7.org/fhir/v3/ProbabilityDistributionType
Name: | v3 Code System ProbabilityDistributionType
Definition: | **** MISSING DEFINITIONS ****
OID: | 2.16.840.1.113883.5.1020 (for OID based terminology systems)
Source Resource | XML / JSON

This Code system is used in the following value sets:

* v3 Code System ProbabilityDistributionType (**** MISSING DEFINITIONS ****)

* ProbabilityDistributionType (Codes specifying the type of probability distribution)

4.3.2.1020.1 Code System Content

Release Date: 2016-11-11

Level | Code | Display | Definition
1 | B | beta | The beta-distribution is used for data that is bounded on both sides and may or may not be skewed (e.g., occurs when probabilities are estimated.) Two parameters a and b are available to adjust the curve. The mean m and variance s2 relate as follows: m = a/ (a + b) and s2 = ab/((a + b)2 (a + b + 1)).
1 | E | exponential | Used for data that describes extinction. The exponential distribution is a special form of g-distribution where a = 1, hence, the relationship to mean m and variance s2 are m = b and s2 = b2.
1 | F | F | Used to describe the quotient of two c2 random variables. The F-distribution has two parameters n1 and n2, which are the numbers of degrees of freedom of the numerator and denominator variable respectively. The relationship to mean m and variance s2 are: m = n2 / (n2 - 2) and s2 = (2 n2 (n2 + n1 - 2)) / (n1 (n2 - 2)2 (n2 - 4)).
1 | G | (gamma) | The gamma-distribution used for data that is skewed and bounded to the right, i.e. where the maximum of the distribution curve is located near the origin. The g-distribution has a two parameters a and b. The relationship to mean m and variance s2 is m = a b and s2 = a b2.
1 | LN | log-normal | The logarithmic normal distribution is used to transform skewed random variable X into a normally distributed random variable U = log X. The log-normal distribution can be specified with the properties mean m and standard deviation s. Note however that mean m and standard deviation s are the parameters of the raw value distribution, not the transformed parameters of the lognormal distribution that are conventionally referred to by the same letters. Those log-normal parameters mlog and slog relate to the mean m and standard deviation s of the data value through slog2 = log (s2/m2 + 1) and mlog = log m - slog2/2.
1 | N | normal (Gaussian) | This is the well-known bell-shaped normal distribution. Because of the central limit theorem, the normal distribution is the distribution of choice for an unbounded random variable that is an outcome of a combination of many stochastic processes. Even for values bounded on a single side (i.e. greater than 0) the normal distribution may be accurate enough if the mean is "far away" from the bound of the scale measured in terms of standard deviations.
1 | T | T | Used to describe the quotient of a normal random variable and the square root of a c2 random variable. The t-distribution has one parameter n, the number of degrees of freedom. The relationship to mean m and variance s2 are: m = 0 and s2 = n / (n - 2)
1 | U | uniform | The uniform distribution assigns a constant probability over the entire interval of possible outcomes, while all outcomes outside this interval are assumed to have zero probability. The width of this interval is 2s sqrt(3). Thus, the uniform distribution assigns the probability densities f(x) = sqrt(2 s sqrt(3)) to values m - s sqrt(3) >= x <= m + s sqrt(3) and f(x) = 0 otherwise.
1 | X2 | chi square | Used to describe the sum of squares of random variables which occurs when a variance is estimated (rather than presumed) from the sample. The only parameter of the c2-distribution is n, so called the number of degrees of freedom (which is the number of independent

parts in the sum). The c2-distribution is a special type of g-distribution with parameter a = n /2 and b = 2. Hence, m = n and s2 = 2 n.

4.3.2.1022 HL7 v3 Code System GTSAbbreviation

URL: https://hl7.org/fhir/STU3/v3/GTSAbbreviation/cs.html

This page is part of the FHIR Specification (v3.0.2: STU 3). The current version which supercedes this version is 4.0.1. For a full list of available versions, see the Directory of published versions

Vocabulary Work Group | Maturity Level: N/A | External | Use Context: Any

This code system (http://hl7.org/fhir/v3/GTSAbbreviation) is defined as part of HL7 v3.

Summary

Defining URL: | http://hl7.org/fhir/v3/GTSAbbreviation
Name: | v3 Code System GTSAbbreviation
Definition: | **** MISSING DEFINITIONS ****
OID: | 2.16.840.1.113883.5.1022 (for OID based terminology systems)
Source Resource | XML / JSON

This Code system is used in the following value sets:

* TimingAbbreviation (Code for a known / defined timing pattern.)

* v3 Code System GTSAbbreviation (**** MISSING DEFINITIONS ****)

4.3.2.1022.1 Code System Content

Release Date: 2016-11-11

Level | Code | Display | Definition
1 | AM | AM | Every morning at institution specified times.
1 | BID | BID | Two times a day at institution specified time
1 | JB | JB | Regular business days (Monday to Friday excluding holidays)
1 | JE | JE | Regular weekends (Saturday and Sunday excluding holidays)
1 | JH | GTSAbbreviationHolidays | Holidays
2 | (_GTSAbbreviationHolidaysChristianRoman) Abstract | | Christian Holidays (Roman/Gregorian [Western] Tradition.)
3 | JHCHREAS | JHCHREAS | Easter Sunday. The Easter date is a rather complex calculation based on Astronomical tables describing full moon dates. Details can be found at [http://www.assa.org.au/edm.html, and http://aa.usno.navy.mil/AA/faq/docs/easter.html]. Note that the Christian Orthodox Holidays are based on the Julian calendar.
3 | JHCHRGFR | JHCHRGFR | Good Friday, is the Friday right before Easter Sunday.
3 | JHCHRNEW | JHCHRNEW | New Year's Day (January 1)
3 | JHCHRPEN | JHCHRPEN | Pentecost Sunday, is seven weeks after Easter (the 50th day of Easter).
3 | JHCHRXME | JHCHRXME | Christmas Eve (December 24)
3 | JHCHRXMS | JHCHRXMS | Christmas Day (December 25)
2 | JHNNL | The Netherlands National Holidays | Description:The Netherlands National Holidays.
3 | JHNNLLD | Liberation day (May 5 every five years) | Description:Liberation day (May 5 every five years)
3 | JHNNLQD | Queen's day (April 30) | Description:Queen's day (April 30)
3 | JHNNLSK | Sinterklaas (December 5) | Description:Sinterklaas (December 5)
2 | JHNUS | GTSAbbreviationHolidaysUSNational | United States National Holidays (public holidays for federal employees established by U.S. Federal law 5 U.S.C. 6103).
3 | JHNUSCLM | JHNUSCLM | Columbus Day, the second Monday in October.
3 | JHNUSIND | JHNUSIND | Independence Day (4th of July)
3 | JHNUSIND1 | JHNUSIND1 | Alternative Monday after 4th of July Weekend [5 U.S.C. 6103(b)].
3 | JHNUSIND5 | JHNUSIND5 | Alternative Friday before 4th of July Weekend [5 U.S.C. 6103(b)].
3 | JHNUSLBR | JHNUSLBR | Labor Day, the first Monday in September.
3 | JHNUSMEM | JHNUSMEM | Memorial Day, the last Monday in May.
3 | JHNUSMEM5 | JHNUSMEM5 | Friday before Memorial Day Weekend
3 | JHNUSMEM6 | JHNUSMEM6 | Saturday of Memorial Day Weekend
3 | JHNUSMLK | JHNUSMLK | Dr. Martin Luther King, Jr. Day, the third Monday in January.
3 | JHNUSPRE | JHNUSPRE | Washington's Birthday (Presidential Day) the third Monday in February.
3 | JHNUSTKS | JHNUSTKS | Thanksgiving Day, the fourth Thursday in November.
3 | JHNUSTKS5 | JHNUSTKS5 | Friday after Thanksgiving.
3 | JHNUSVET | JHNUSVET | Veteran's Day, November 11.
1 | PM | PM | Every afternoon at institution specified times.
1 | Q4H | Q4H | Every 4 hours at institution specified time
1 | Q6H | Q6H | Every 6 hours at institution specified time
1 | QD | QD | Every day at institution specified times.
1 | QID | QID | Four times a day at institution specified time
1 | QOD | QOD | Every other day at institution specified times.
1 | TID | TID | Three times a day at institution specified time

4.3.2.1050 HL7 v3 Code System AcknowledgementCondition

URL: https://hl7.org/fhir/STU3/v3/AcknowledgementCondition/cs.html

This page is part of the FHIR Specification (v3.0.2: STU 3). The current version which supercedes this version is 4.0.1. For a full list of available versions, see the Directory of published versions

Vocabulary Work Group | Maturity Level: N/A | External | Use Context: Any

This code system (http://hl7.org/fhir/v3/AcknowledgementCondition) is defined as part of HL7 v3.

Summary

Defining URL: | http://hl7.org/fhir/v3/AcknowledgementCondition
Name: | v3 Code System AcknowledgementCondition
Definition: | The codes identify the conditions under which accept acknowledgements are required to be returned in response to this message. Note that accept acknowledgement address two different issues at the same time: reliable transport as well as syntactical correctness
OID: | 2.16.840.1.113883.5.1050 (for OID based terminology systems)
Source Resource | XML / JSON

This Code system is used in the following value sets:

* v3 Code System AcknowledgementCondition (The codes identify the conditions under which accept acknowledgements are required to be returned in response to this message. Note that accept acknowledgement address two different issues at the same time: reliable transport as well as syntactical correctness)

4.3.2.1050.1 Code System Content

Release Date: 2016-11-11

Level | Code | Display | Definition
1 | AL | Always | Always send an acknowledgement.
1 | ER | Error/reject only | Send an acknowledgement for error/reject conditions only.
1 | NE | Never | Never send an acknowledgement.
1 | SU | Successful only | Send an acknowledgement for successful completions only.

4.3.2.1051 HL7 v3 Code System ActInvoiceElementModifier

URL: https://hl7.org/fhir/STU3/v3/ActInvoiceElementModifier/cs.html

This page is part of the FHIR Specification (v3.0.2: STU 3). The current version which supercedes this version is 4.0.1. For a full list of available versions, see the Directory of published versions

Vocabulary Work Group | Maturity Level: N/A | External | Use Context: Any

This code system (http://hl7.org/fhir/v3/ActInvoiceElementModifier) is defined as part of HL7 v3.

Summary

Defining URL: | http://hl7.org/fhir/v3/ActInvoiceElementModifier
Name: | v3 Code System ActInvoiceElementModifier
Definition: | Processing consideration and clarification codes.
OID: | 2.16.840.1.113883.5.1051 (for OID based terminology systems)
Source Resource | XML / JSON

This Code system is used in the following value sets:

* v3 Code System ActInvoiceElementModifier (Processing consideration and clarification codes.)

4.3.2.1051.1 Code System Content

Release Date: 2016-11-11

Level | Code | Display | Definition
1 | EFORM | Electronic Form To Follow | Electronic form with supporting information to follow.
1 | FAX | Fax To Follow | Fax with supporting information to follow.
1 | LINV | Last Invoice | Represents the last invoice from the perspective of the provider.
1 | PAPER | Paper Documentation To Follow | Paper documentation (or other physical format) with supporting information to follow.

4.3.2.1052 HL7 v3 Code System ActSite

URL: https://hl7.org/fhir/STU3/v3/ActSite/cs.html

This page is part of the FHIR Specification (v3.0.2: STU 3). The current version which supercedes this version is 4.0.1. For a full list of available versions, see the Directory of published versions

Vocabulary Work Group | Maturity Level: N/A | External | Use Context: Any

This code system (http://hl7.org/fhir/v3/ActSite) is defined as part of HL7 v3.

Summary

Defining URL: | http://hl7.org/fhir/v3/ActSite
Name: | v3 Code System ActSite
Definition: | An anatomical location on an organism which can be the focus of an act.
OID: | 2.16.840.1.113883.5.1052 (for OID based terminology systems)
Source Resource | XML / JSON

This Code system is used in the following value sets:

* v3 Code System ActSite (An anatomical location on an organism which can be the focus of an act.)

* Codes for Immunization Site of Administration (The value set to instantiate this attribute should be drawn from a terminologically robust code system that consists of or contains concepts to support describing the body site where the

vaccination occurred. This value set is provided as a suggestive example.)

4.3.2.1052.1 Code System Content

Release Date: 2016-11-11

Level | Code | Display | Definition
1 | (_HumanActSite) Abstract | | An anatomical location on a human which can be the focus of an act.
2 | (_HumanSubstanceAdministrationSite) Abstract | | The set of body locations to or through which a drug product may be administered.
3 | BE | bilateral ears
3 | BN | bilateral nares
3 | BU | buttock
3 | LA | left arm
3 | LAC | left anterior chest
3 | LACF | left antecubital fossa
3 | LD | left deltoid
3 | LE | left ear
3 | LEJ | left external jugular
3 | LF | left foot
3 | LG | left gluteus medius
3 | LH | left hand
3 | LIJ | left internal jugular
3 | LLAQ | left lower abd quadrant
3 | LLFA | left lower forearm
3 | LMFA | left mid forearm
3 | LN | left naris
3 | LPC | left posterior chest
3 | LSC | left subclavian
3 | LT | left thigh
3 | LUA | left upper arm
3 | LUAQ | left upper abd quadrant
3 | LUFA | left upper forearm
3 | LVG | left ventragluteal
3 | LVL | left vastus lateralis
3 | OD | right eye
3 | OS | left eye
3 | OU | bilateral eyes
3 | PA | perianal
3 | PERIN | perineal
3 | RA | right arm
3 | RAC | right anterior chest
3 | RACF | right antecubital fossa
3 | RD | right deltoid
3 | RE | right ear
3 | REJ | right external jugular
3 | RF | right foot
3 | RG | right gluteus medius
3 | RH | right hand
3 | RIJ | right internal jugular
3 | RLAQ | right lower abd quadrant
3 | RLFA | right lower forearm
3 | RMFA | right mid forearm
3 | RN | right naris
3 | RPC | right posterior chest
3 | RSC | right subclavian
3 | RT | right thigh
3 | RUA | right upper arm
3 | RUAQ | right upper abd quadrant
3 | RUFA | right upper forearm
3 | RVG | right ventragluteal
3 | RVL | right vastus lateralis

4.3.2.1053 HL7 v3 Code System ActUncertainty

URL: https://hl7.org/fhir/STU3/v3/ActUncertainty/cs.html

This page is part of the FHIR Specification (v3.0.2: STU 3). The current version which supercedes this version is 4.0.1. For a full list of available versions, see the Directory of published versions

Vocabulary Work Group | Maturity Level: N/A | External | Use Context: Any

This code system (http://hl7.org/fhir/v3/ActUncertainty) is defined as part of HL7 v3.

Summary

Defining URL: | http://hl7.org/fhir/v3/ActUncertainty

Name: | v3 Code System ActUncertainty
Definition: | OpenIssue: Missing Description
OID: | 2.16.840.1.113883.5.1053 (for OID based terminology systems)
Source Resource | XML / JSON

This Code system is used in the following value sets:

* v3 Code System ActUncertainty (OpenIssue: Missing Description)

4.3.2.1053.1 Code System Content

Release Date: 2016-11-11

Level | Code | Display | Definition
1 | N | stated with no assertion of uncertainty | Specifies that the act statement is made without explicit tagging of uncertainty. This is the normal statement, meaning that it is not free of errors and uncertainty may still exist.
1 | U | stated with uncertainty | Specifies that the originator of the Act statement does not have full confidence in the applicability (i.e., in event mood: factual truth) of the statement.

4.3.2.1054 HL7 v3 Code System AmericanIndianAlaskaNativeLanguages

URL: https://hl7.org/fhir/STU3/v3/AmericanIndianAlaskaNativeLanguages/cs.html

This page is part of the FHIR Specification (v3.0.2: STU 3). The current version which supercedes this version is 4.0.1. For a full list of available versions, see the Directory of published versions

Vocabulary Work Group | Maturity Level: N/A | External | Use Context: Any

This code system (http://hl7.org/fhir/v3/AmericanIndianAlaskaNativeLanguages) is defined as part of HL7 v3.

Summary

Defining URL: | http://hl7.org/fhir/v3/AmericanIndianAlaskaNativeLanguages
Name: | v3 Code System AmericanIndianAlaskaNativeLanguages
Definition: | American Indian and Alaska Native languages currently being used in the United States.
OID: | 2.16.840.1.113883.5.1054 (for OID based terminology systems)
Source Resource | XML / JSON

This Code system is used in the following value sets:

* v3 Code System AmericanIndianAlaskaNativeLanguages (American Indian and Alaska Native languages currently being used in the United States.)

4.3.2.1054.1 Code System Content

Release Date: 2016-11-11

Level | Code | Display | Definition
1 | (_Algic) Abstract
2 | (_Algonquian) Abstract
3 | (_Arapahoan) Abstract
4 | (_ArapahoGrosVentre) Abstract
5 | x-ARP | Arapaho
5 | x-ATS | Gros Ventre
3 | (_CreeMontagnais) Abstract
4 | (_Cree) Abstract
5 | x-CRP | Western Cree
3 | (_EasternAlgonquin) Abstract
4 | (_Abenakian) Abstract
5 | x-AAQ | Eastern Abenaki
5 | x-ABE | Western Abenaki
5 | x-MAC | Maliseet-Passamaquoddy
4 | (_Delawaran) Abstract
5 | x-DEL | Unami Delaware
4 | x-MIC | Micmac
3 | (_Ojibwayan) Abstract
4 | x-OJB | Southern Ojibwa
4 | x-POT | Potawatami
3 | (_SaukFoxKickapoo) Abstract
4 | x-KIC | Kickapoo
4 | x-SAC | Mesquakie
4 | x-SJW | Shawnee
3 | x-BLC | Blackfoot
3 | x-CHY | Cheyenne
3 | x-MEZ | Menominee
2 | (_Ritwan) Abstract
3 | x-YUR | Yurok
1 | (_Caddoan) Abstract
2 | (_NorthernCaddoan) Abstract
3 | x-ARI | Arikara

3 | x-PAW | Pawnee
3 | x-WIC | Wichita
2 | (_SouthernCaddoan) Abstract
3 | x-CAD | Caddo
1 | (_Chimakuan) Abstract
2 | x-QUI | Quileute
1 | (_EskimoAleut) Abstract
2 | (_Aleut) Abstract
3 | x-ALW | Aleut
2 | (_Eskimoan) Abstract
3 | (_InuitInupiaq) Abstract
4 | x-ESI | North Alaskan Inuktitut
4 | x-ESK | Northwest Alaska Inuktitut
3 | (_SirenikskiYupik) Abstract
4 | x-EMS | Pacific Yupik Gulf
4 | x-ESS | Central Siberian Yupik
4 | x-ESU | Central Alaskan Yupik
1 | (_Hokan) Abstract
2 | (_CochimiYuman) Abstract
3 | (_Yuman) Abstract
4 | (_DeltaCalifornia) Abstract
5 | (_Diegueno) Abstract
6 | x-DIH | Kumeyaay
5 | x-COC | Cocopa
4 | (_Pai) Abstract
5 | x-YUF | Havasupai
4 | (_River) Abstract
5 | x-MOV | Mohave
5 | x-MRC | Maricopa
5 | x-YUM | Quechan
2 | (_Palaihnihan) Abstract
3 | x-ACH | Achumawi
3 | x-ATW | Atsugewi
2 | (_Pomoan) Abstract
3 | x-KJU | Kashaya
3 | x-PEF | Northeastern Pomo
3 | x-PEO | Southeastern Pomo
3 | x-PEQ | Southern Pomo
3 | x-POO | Central Pomo
2 | (_Shasta) Abstract
3 | x-SHT | Shasta
2 | x-KYH | Karok
2 | x-WAS | Washoe
1 | (_Iroquoian) Abstract
2 | (_NorthernIroquoian) Abstract
3 | x-CAY | Cayuga
3 | x-MOH | Mohawk
3 | x-ONE | Oneida
3 | x-ONO | Onondaga
3 | x-SEE | Seneca
3 | x-TUS | Tuscarora
2 | x-CER | Cherokee
1 | (_Keresan) Abstract
2 | x-KEE | Rio Grande Keresan
2 | x-KJQ | Acoma-Laguna
1 | (_KiowaTanoan) Abstract
2 | (_Tiwa) Abstract
3 | x-TAO | Northern Tiwa
3 | x-TIX | Southern Tiwa
2 | x-KIO | Kiowa
2 | x-TEW | Tewa
2 | x-TOW | Jemez
1 | (_Muskogean) Abstract
2 | (_CentralMuskogean) Abstract
3 | x-AKZ | Alabama
3 | x-CKU | Koasati
3 | x-MIK | Mikasuki
2 | (_WesternMuskogean) Abstract
3 | x-CCT | Choctaw
3 | x-CIC | Chickasaw
2 | x-CRK | Creek
1 | (_Nadene) Abstract

2 | (_AthapaskanEyak) Abstract
3 | (_Athapaskan) Abstract
4 | (_Apachean) Abstract
5 | (_EasternApachean) Abstract
6 | x-APJ | Jicarilla
6 | x-APL | Lipan
5 | (_WesternApachean) Abstract
6 | x-APM | Mescalero-Chiricahua
6 | x-APW | Western Apache
6 | x-NAV | Dine
5 | x-APK | Kiowa Apache
4 | (_CentralAlaskaYukon) Abstract
5 | (_KoyukonIngalik) Abstract
6 | x-HOI | Holikachuk
6 | x-ING | Degexit'an
6 | x-KOY | Koyukon
5 | (_KutchinHan) Abstract
6 | x-HAA | Han
6 | x-KUC | Kutchin
5 | (_TananaTutchone) Abstract
6 | (_Tanana) Abstract
7 | x-TAA | Lower Tanana
7 | x-TAU | Upper Tanana
7 | x-TCB | Tanacross
6 | x-KUU | Upper Kuskokwim
4 | (_PacificCoastAthapaskan) Abstract
5 | (_CaliforniaAthapaskan) Abstract
6 | x-HUP | Hupa
6 | x-KTW | Cahto
5 | (_OregonAthapaskan) Abstract
6 | x-TOL | Tolowa
6 | x-TUU | Tututni
4 | (_SouthernAlaska) Abstract
5 | x-AHT | Ahtna
5 | x-TFN | Tanaina
3 | x-EYA | Eyak
2 | x-TLI | Tlingit
1 | (_Penutian) Abstract
2 | (_Chinookan) Abstract
3 | (_UpperChinook) Abstract
4 | x-WAC | Kiksht
2 | (_Coosan) Abstract
3 | x-COS | Hanis
2 | (_Maiduan) Abstract
3 | x-MAI | Northwest Maidu
3 | x-NMU | Northeast Maidu
3 | x-NSZ | Nisenan
2 | (_PlateauPenutian) Abstract
3 | (_Sahaptian) Abstract
4 | x-UMA | Umatilla
4 | x-WAA | Walla Walla
4 | x-WAR | Tenino
4 | x-YAK | Yakima
3 | x-KLA | Klamath-Modoc
3 | x-NEZ | Nez Perce
2 | (_Takelman) Abstract
3 | (_Kalapuyan) Abstract
4 | x-KAL | Central Kalapuyan
2 | (_Tsimshianic) Abstract
3 | x-TSI | Coast Tsimshain
2 | (_Utian) Abstract
3 | (_Miwokan) Abstract
4 | (_EasternMiwok) Abstract
5 | x-CSM | Central Sierra Miwok
5 | x-NSQ | Northern Sierra Miwok
5 | x-PMW | Plains Miwok
5 | x-SKD | Southern Sierra Miwok
4 | (_WesternMiwok) Abstract
5 | x-CSI | Coast Miwok
5 | x-LMW | Lake Miwok
2 | (_Wintuan) Abstract
3 | x-WIT | Wintu-Nomlaki

2 | (_Yokutsan) Abstract
3 | x-ENH | Kings River
3 | x-GSH | Gashowu
3 | x-PYL | Poso Creek
3 | x-TKH | Tule-Kaweah
1 | (_Pidgin) Abstract
2 | x-CHH | Chinook Wawa
1 | (_Salishan) Abstract
2 | (_CentralSalish) Abstract
3 | x-CLM | Clallam
3 | x-LUT | Lushootseed
3 | x-STR | Northern Straits
2 | (_InteriorSalish) Abstract
3 | x-COL | Columbian
3 | x-CRD | Coeur D'alene
3 | x-FLA | Kalispel
3 | x-OKA | Okanagan
2 | (_Tsamosan) Abstract
3 | x-CEA | Lower Chehalis
3 | x-CJH | Upper Chehalis
3 | x-COW | Cowlitz
3 | x-QUN | Quinault
1 | (_SiouanCatawba) Abstract
2 | (_Siouan) Abstract
3 | (_MississippiValley) Abstract
4 | (_ChiwereWinnebago) Abstract
5 | x-IOW | Chiwere
5 | x-WIN | Hocak
4 | (_Dakotan) Abstract
5 | x-ASB | Assiniboine
5 | x-DHG | Dakota
5 | x-LKT | Lakota
5 | x-NKT | Nakota
4 | (_Dhegiha) Abstract
5 | x-KAA | Kansa
5 | x-OMA | Omaha-Ponca
5 | x-OSA | Osage
5 | x-QUA | Quapaw
3 | (_MissouriRiver) Abstract
4 | x-CRO | Crow
4 | x-HID | Hidatsa
3 | x-MHQ | Mandan
1 | (_UtoAztecan) Abstract
2 | (_Numic) Abstract
3 | (_CentralNumic) Abstract
4 | x-COM | Comanche
4 | x-PAR | Panamint
4 | x-SHH | Shoshone
3 | (_SouthernNumic) Abstract
4 | x-KAW | Kawaiisu
4 | x-UTE | Ute-Southern Paiute
3 | (_WesternNumic) Abstract
4 | x-MON | Mono
4 | x-PAO | Northern Paiute-Bannock
2 | (_Takic) Abstract
3 | (_Cupan) Abstract
4 | x-CHL | Cahuilla
4 | x-CUP | Cupeno
4 | x-LUI | Luiseno
3 | (_SerranoGabrielino) Abstract
4 | x-SER | Serrano
2 | (_Taracahitan) Abstract
3 | (_Cahitan) Abstract
4 | x-YAQ | Yaqui
2 | (_Tepiman) Abstract
3 | x-PAP | Papago-Pima
2 | x-HOP | Hopi
2 | x-TUB | Tubatululabal
1 | (_Wakashan) Abstract
2 | (_Nootkan) Abstract
3 | x-MYH | Makah
1 | (_Yukian) Abstract

2 | x-WAO | Wappo
2 | x-YUK | Yuki
1 | x-HAI | Haida
1 | x-KUN | Kootenai
1 | x-PSD | Plains Indian Sign Language
1 | x-YUC | Yuchi
1 | x-ZUN | Zuni

4.3.2.1055 HL7 v3 Code System Calendar

URL: https://hl7.org/fhir/STU3/v3/Calendar/cs.html

This page is part of the FHIR Specification (v3.0.2: STU 3). The current version which supercedes this version is 4.0.1. For a full list of available versions, see the Directory of published versions

Vocabulary Work Group | Maturity Level: N/A | External | Use Context: Any

This code system (http://hl7.org/fhir/v3/Calendar) is defined as part of HL7 v3.

Summary

Defining URL: | http://hl7.org/fhir/v3/Calendar
Name: | v3 Code System Calendar
Definition: | **** MISSING DEFINITIONS ****
OID: | 2.16.840.1.113883.5.1055 (for OID based terminology systems)
Source Resource | XML / JSON

This Code system is used in the following value sets:

* v3 Code System Calendar (**** MISSING DEFINITIONS ****)

4.3.2.1055.1 Code System Content

Release Date: 2016-11-11

Level | Code | Display | Definition
1 | GREG | Gregorian | The Gregorian calendar is the calendar in effect in most countries of Christian influence since approximately 1582. This calendar superceded the Julian calendar.

4.3.2.1056 HL7 v3 Code System CommunicationFunctionType

URL: https://hl7.org/fhir/STU3/v3/CommunicationFunctionType/cs.html

This page is part of the FHIR Specification (v3.0.2: STU 3). The current version which supercedes this version is 4.0.1. For a full list of available versions, see the Directory of published versions

Vocabulary Work Group | Maturity Level: N/A | External | Use Context: Any

This code system (http://hl7.org/fhir/v3/CommunicationFunctionType) is defined as part of HL7 v3.

Summary

Defining URL: | http://hl7.org/fhir/v3/CommunicationFunctionType
Name: | v3 Code System CommunicationFunctionType
Definition: | Describes the type of communication function that the associated entity plays in the associated transmission.
OID: | 2.16.840.1.113883.5.1056 (for OID based terminology systems)
Source Resource | XML / JSON

This Code system is used in the following value sets:

* v3 Code System CommunicationFunctionType (Describes the type of communication function that the associated entity plays in the associated transmission.)

4.3.2.1056.1 Code System Content

Release Date: 2016-11-11

Level | Code | Display | Definition
1 | RCV | receiver | The entity is the receiver of the transmission.
1 | RSP | respond to | The entity is the one to which the response or reply to the transmission should be sent.
1 | SND | sender | The entity is the sender of the transmission.

4.3.2.1057 HL7 v3 Code System ContextControl

URL: https://hl7.org/fhir/STU3/v3/ContextControl/cs.html

This page is part of the FHIR Specification (v3.0.2: STU 3). The current version which supercedes this version is 4.0.1. For a full list of available versions, see the Directory of published versions

Vocabulary Work Group | Maturity Level: N/A | External | Use Context: Any

This code system (http://hl7.org/fhir/v3/ContextControl) is defined as part of HL7 v3.

Summary

Defining URL: | http://hl7.org/fhir/v3/ContextControl

Name: | v3 Code System ContextControl

Definition: | A code that specifies how an ActRelationship or Participation contributes to the context of an Act, and whether it may be propagated to descendent Acts whose association allows such propagation (see also attributes Participation.contextControlCode, ActRelationship.contextControlCode, ActRelationship.contextConductionInd).

OID: | 2.16.840.1.113883.5.1057 (for OID based terminology systems)

Source Resource | XML / JSON

This Code system is used in the following value sets:

* v3 Code System ContextControl (A code that specifies how an ActRelationship or Participation contributes to the context of an Act, and whether it may be propagated to descendent Acts whose association allows such propagation (see also attributes Participation.contextControlCode, ActRelationship.contextControlCode, ActRelationship.contextConductionInd).)

4.3.2.1057.1 Code System Content

Release Date: 2016-11-11

Level | Code | Display | Definition

1 | (_ContextControlAdditive) Abstract | | The association adds to the existing context associated with the Act. Both this association and any associations propagated from ancestor Acts are interpreted as being related to this Act.

2 | AN | additive, non-propagating | The association adds to the existing context associated with the Act, but will not propagate to any descendant Acts reached by conducting ActRelationships (see contextControlCode). Examples: If an 'Author' Participation were marked as "Additive, Non-Propagating" it means that the author will be added to the set of author participations that have propagated from ancestor Acts for the purpose of this Act. However only the previously propagated authors will propagate to any child Acts that allow context to be propagated.

2 | AP | additive, propagating | The association adds to the existing context associated with the Act, and will propagate to any descendant Acts reached by conducting ActRelationships (see contextControlCode). Examples: If an 'Author' Participation were marked as "Additive, Propagating" it means that the author will be added to the set of author participations that have propagated from ancestor Acts, and will itself propagate with the other authors to any child Acts that allow context to be propagated.

1 | (_ContextControlNonPropagating) Abstract | | The association applies only to the current Act and will not propagate to any child Acts that are related via a conducting ActRelationship (refer to contextConductionInd).

2 | AN

2 | ON | overriding, non-propagating | The association is added to the existing context associated with the Act, but overrides an association with the same typeCode. However, this overriding association will not propagate to any descendant Acts reached by conducting ActRelationships (see contextControlCode). Examples: If an 'Author' Participation were marked as "Overriding, Non-Propagating" it means that the author will replace the set of author participations that have propagated from ancestor Acts. Furthermore, no author participations whatsoever will propagate to any child Acts that allow context to be propagated.

1 | (_ContextControlOverriding) Abstract | | The association adds to the existing context associated with the Act, but replaces associations propagated from ancestor Acts whose typeCodes are the same or more specific.

2 | ON

2 | OP | overriding, propagating | The association is added to the existing context associated with the Act, but overrides an association with the same typeCode. This overriding association will propagate to any descendant Acts reached by conducting ActRelationships (see contextControlCode). Examples: If an 'Author' Participation were marked as "Overriding, Propagating" it means that the author will replace the set of author participations that have propagated from ancestor Acts, and will itself be the only author to propagate to any child Acts that allow context to be propagated.

1 | (_ContextControlPropagating) Abstract | | The association propagates to any child Acts that are related via a conducting ActRelationship (refer to contextConductionInd).

2 | AP

2 | OP

4.3.2.1059 HL7 v3 Code System EmployeeJobClass

URL: https://hl7.org/fhir/STU3/v3/EmployeeJobClass/cs.html

This page is part of the FHIR Specification (v3.0.2: STU 3). The current version which supercedes this version is 4.0.1. For a full list of available versions, see the Directory of published versions

Vocabulary Work Group | Maturity Level: N/A | External | Use Context: Any

This code system (http://hl7.org/fhir/v3/EmployeeJobClass) is defined as part of HL7 v3.

Summary

Defining URL: | http://hl7.org/fhir/v3/EmployeeJobClass

Name: | v3 Code System EmployeeJobClass

Definition: | **** MISSING DEFINITIONS ****

OID: | 2.16.840.1.113883.5.1059 (for OID based terminology systems)

Source Resource | XML / JSON

This Code system is used in the following value sets:

* v3 Code System EmployeeJobClass (**** MISSING DEFINITIONS ****)

4.3.2.1059.1 Code System Content

Release Date: 2016-11-11

Level | Code | Display | Definition

1 | FT | full-time | Employment in which the employee is expected to work at least a standard work week (defined by the US Bureau of Labor Statistics as 35-44 hours per week)

1 | PT | part-time | Employment in which the employee is expected to work less than a standard work week (defined by the US Bureau of Labor Statistics as 35-44 hours per week)

4.3.2.1060 HL7 v3 Code System EntityCode

URL: https://hl7.org/fhir/STU3/v3/EntityCode/cs.html

This page is part of the FHIR Specification (v3.0.2: STU 3). The current version which supercedes this version is 4.0.1. For a full list of available versions, see the Directory of published versions

Vocabulary Work Group | Maturity Level: N/A | External | Use Context: Any

This code system (http://hl7.org/fhir/v3/EntityCode) is defined as part of HL7 v3.

Summary

Defining URL: | http://hl7.org/fhir/v3/EntityCode
Name: | v3 Code System EntityCode
Definition: | OpenIssue: Missing description.
OID: | 2.16.840.1.113883.5.1060 (for OID based terminology systems)
Source Resource | XML / JSON

This Code system is used in the following value sets:

* v3 Code System EntityCode (OpenIssue: Missing description.)

4.3.2.1060.1 Code System Content

Release Date: 2016-11-11

Level | Code | Display | Definition
1 | (_MaterialEntityClassType) Abstract | | Types of Material for EntityClass "MAT"
2 | (_ContainerEntityType) Abstract | | Material intended to hold another material for purpose of storage or transport.
3 | PKG | Package | A material intended to hold other materials for purposes of storage or transportation
4 | (_NonRigidContainerEntityType) Abstract | | A container having dimensions that adjust somewhat based on the amount and shape of the material placed within it.
5 | BAG | Bag | A pouched or pendulous container.
5 | PACKT | Packet | A paper
5 | PCH | Pouch | A small bag or container made of a soft material.
5 | SACH | Sachet | A small bag or packet containing a small portion of a substance.
4 | (_RigidContainerEntityType) Abstract | | A container having a fixed and inflexible dimensions and volume
5 | (_IndividualPackageEntityType) Abstract | | Container intended to contain sufficient material for only one use.
6 | AMP | Ampule | A small sealed glass container that holds a measured amount of a medicinal substance.
6 | MINIM | Minim | Individually dosed ophthalmic solution. One time eye dropper dispenser.
6 | NEBAMP | Nebuamp | Individually dosed inhalation solution.
6 | OVUL | Ovule | A container either glass or plastic and a narrow neck, for storing liquid.
5 | (_MultiUseContainerEntityType) Abstract | | A container intended to contain sufficient material for more than one use. (I.e. Material is intended to be removed from the container at more than one discrete time period.)
6 | BOT | Bottle | A container, typically rounded, either glass or plastic with a narrow neck and capable of storing liquid.
7 | BOTA | Amber Bottle | A bottle of yellow to brown color. Used to store light-sensitive materials
7 | BOTD | Dropper Bottle | A bottle with a cap designed to release the contained liquid in droplets of a specific size.
7 | BOTG | Glass Bottle | A bottle made of glass
7 | BOTP | Plastic Bottle | A bottle made of plastic
8 | BOTPLY | Polyethylene Bottle | A bottle made of polyethylene
6 | BOX | Box | A 6-sided container commonly made from paper or cardboard used for solid forms.
6 | CAN | Can | A metal container in which a material is hermetically sealed to enable storage over long periods.
6 | CART | Cartridge | A sealed container of liquid or powder intended to be loaded into a device.
6 | CNSTR | Canister | A pressurized metal container holding a substance released as a spray or aerosol.
6 | JAR | Jar | A container of glass, earthenware, plastic, etc. Top of the container has a diameter of similar size to the diameter of the container as a whole
6 | JUG | Jug | A deep vessel for holding liquids, with a handle and often with a spout or lip shape for pouring.
6 | TIN | Tin | A lidded container made of thin sheet metal.
6 | TUB | Tub | An open flat bottomed round container.
6 | TUBE | Tube | A long hollow rigid or flexible cylinder. Material is extruded by squeezing the container.
6 | VIAL | Vial | A small cylindrical glass for holding liquid medicines.
5 | BLSTRPK | Blister Pack | A bubblepack. Medications sealed individually, separated into doses.
6 | CARD | Card | A bubble pack card. Multiple individual/separated doses.
4 | COMPPKG | Compliance Package | A container intended to contain sufficient material for more than one use, but grouped or organized to provide individual access to sufficient material for a single use. Often used to ensure that the proper type and amount of material is consumed/expended for each use.
5 | BLSTRPK
5 | DIALPK | Dial Pack | Rotatable dispenser. Eg. Birth control package.
5 | DISK | Disk | Object that is thin, flat, and circular. Doses of medication often contained in bubbles on the disk.
5 | DOSET | Dosette | Special packaging that will help patients take their medications on a regular basis.
5 | STRIP | Strip | A continuous strip of plastic sectioned into individual pouches, each one containing the quantity of 1 or more medications intended to be administered at a specific time
4 | KIT | Kit | A container for a diverse collection of products intended to be used together for some purpose (e.g. Medicinal kits often contain a syringe, a needle and the injectable medication).
5 | SYSTM | System | A kit in which the components are interconnected.
2 | (_MedicalDevice) Abstract | | A device with direct or indirect therapeutic purpose. Values for EntityCode when EntityClass = "DEV"
3 | (_AccessMedicalDevice) Abstract | | A device used to allow access to a part of a body

4 | LINE | Line | A hollow tube used to administer a substance into a vein, artery or body cavity
5 | IALINE | Intra-arterial Line | A line used to administer a substance into an artery
5 | IVLINE | Intraveneous Line | A line used to administer a substance into a vein
3 | (_AdministrationMedicalDevice) Abstract | | A device intended to administer a substance to a subject
4 | (_InjectionMedicalDevice) Abstract | | A device intended to administer liquid into a subject via a
5 | AINJ | AutoInjector | Automatically injects medication.
5 | PEN | Pen | A device which can contain a cartridge for injection purposes. Eg. Insulin pen.
5 | SYR | Syringe | A barrel with a plunger.
4 | APLCTR | Applicator | A device used to apply a liquid or powder to a surface.
4 | INH | Inhaler | A small device used for inhaling medicine in the form of a vapour or gas in order to ease a respiratory condition such as asthma or to relieve nasal congestion.
5 | DSKS | Diskus | The device used to inhale the doses of medication contained in the disk form.
5 | DSKUNH | Diskhaler | The device used to inhale the doses of medication contained in the disk form.
5 | TRBINH | Turbuhaler | Asthma medication delivery device.
4 | PMP | Pump | A device that is used to raise, compress, or transfer liquids or gases and is operated by a piston or similar mechanism.
2 | (_SpecimenAdditiveEntity) Abstract | | Set of codes related to specimen additives
3 | ACDA | ACD Solution A | ACD Solution A of trisodium citrate, 22.0g/L; citric acid, 8.0 g/L; and dextrose 24.5 g/L. Used in Blood banking and histocompatibilty testing
3 | ACDB | ACD Solution B | ACD Solution B of trisodium citrate, 13.2g/L; citric acid, 4.8 g/L; and dextrose 14.7 g/L. Used in Blood banking and histocompatibilty testing.
3 | ACET | Acetic Acid | 50% V/V acetic acid in water. Used as a urine preservative
3 | AMIES | Amies transport medium | Sodium Chloride 3.0g, Potassium Chloride 0.2g, Calcium Chloride 0.1g, Magnesium Chloride 0.1g, Monopotassium Phosphate 0.2g, Disodium Phosphate 1.15g, Sodium Thiogly collate 1.0g, Distilled Water 1 liter
3 | BACTM | Bacterial Transport medium | Any medium used to maintain bacterial viability (e.g. Stuart's, Cary-Blair, Amies)
3 | BF10 | Buffered 10% formalin | Formaldehyde 4% w/v; methyl alcohol 1% w/v; phosphate buffering salts. Tissue preservative
3 | BOR | Boric Acid | Powdered boric acid (usually 10 g) added to 24-hour urine collections as a preservative.
3 | BOUIN | Bouin's solution | Picric acid, saturated aqueous solution (750.0 ml), 37-40% formalin (250.0 ml), glacial acetic acid (50.0 ml). Tissue preservative.
3 | BSKM | Buffered skim milk | 50% skim milk in 0.01 M phosphate-buffered saline. Maintain virus viability
3 | C32 | 3.2% Citrate | A 3.2% solution of Sodium Citrate in water. Used as a blood preservative
3 | C38 | 3.8% Citrate | A 3.8% solution of Sodium Citrate in water. Used as a blood preservative
3 | CARS | Carson's Modified 10% formalin | A modification of buffered 10% formalin used as a general tissue preservative.
3 | CARY | Cary Blair Medium | Sodium Thioglycollate 1.5 g, Disodium Hydrogen Phosphate 1.1 g, Sodium Chloride 5.0 g, Calcium Chloride 0.09 g, Agar 5.0 g, per Liter of Water
3 | CHLTM | Chlamydia transport medium | Any of a number of non-nutritive buffered media used to maintain Chlamydia viability during transportation to the laboratory
3 | CTAD | CTAD | Buffered tri-sodium citrate solution with theophylline, adenosine and dipyridamole
3 | EDTK15 | Potassium/K EDTA 15% | Potassium EDTA 15% solution in water
3 | EDTK75 | Potassium/K EDTA 7.5% | Potassium EDTA 7.5% solution in water
3 | EDTN | Sodium/Na EDTA | Sodium fluoride and Disodium EDTA
3 | ENT | Enteric bacteria transport medium | Any of a number of non-nutritive buffered media used to maintain enteric bacterial viability during transportation to the laboratory
3 | F10 | 10% Formalin | A 10% v/v solution in water of formalin(a 37% solution of formaldehyde and water). Used for tissue preservation.
3 | FDP | Thrombin NIH; soybean trypsin inhibitor | Thrombin plus soybean trypsin inhibitor. For use in identifying fibrn degredation products.
3 | FL10 | Sodium Fluoride, 10mg | Sodium fluoride, 10mg added as a urine preservative.
3 | FL100 | Sodium Fluoride, 100mg | Sodium fluoride, 100mg added as a urine preservative.
3 | HCL6 | 6N HCL | A solution of HCl containing 6moles of hydrogen ion/L. Used as a Urine Preservative.
3 | HEPA | Ammonium heparin | Ammonium heparin
3 | HEPL | Lithium/Li Heparin | Lithium heparin salt
3 | HEPN | Sodium/Na Heparin | Sodium heparin salt
3 | HNO3 | Nitric Acid | 6N Nitric acid used to preserve urine for heavy metal analysis.
3 | JKM | Jones Kendrick Medium | A transport medium formulated to maintain Bordetella pertussis viability.
3 | KARN | Karnovsky's fixative | 5% Glutaraldehyde, 4% Formaldehyde in 0.08M buffer. Tissue preservation
3 | KOX | Potassium Oxalate | Potassium oxalate and sodium fluoride in a 1.25:1 ratio
3 | LIA | Lithium iodoacetate | Iodoacetate lithium salt
3 | M4 | M4 | Modified Hank's balanced salt solution supplemented with bovine serum albumin, gelatin, sucrose and glutamic acid. It is buffered to pH 7.3+ or - 0.2 with HEPES buffer. Phenol red is used to indicate pH. Vancomycin, Amphotericin B and Colistin are used to
3 | M4RT | M4-RT | Modified Hank's balanced salt solution supplemented with bovine serum albumin, gelatin, sucrose and glutamic acid. It is buffered to pH 7.3+ or - 0.2 with Hepes buffer. Phenol red is used to indicate pH. Gentamicin and amphotericin B are used to inhibit c
3 | M5 | M5 | Modified Hank's balanced salt solution supplemented with protein stabilizers, sucrose and glutamic acid. It is buffered to pH 7.3+ or - 0.2 with Hepes buffer. Phenol red is used to indicate pH. Vancomycin, Amphotericin B and Colistin are used to inhibit c
3 | MICHTM | Michel's transport medium | 1M potassium citrate, pH 7.0 2.5 ml, 0.1M magnesium sulfate 5.0 ml, 0.1M N-ethyl malemide 5.0 ml, dH2O 87.5 ml, ammonium sulfate 55gm. Preserve antigens for Immunofluorescence procedures
3 | MMDTM | MMD transport medium | A buffered medium with ammonium sulfate added to preserve antigens for Immunofluorescence procedures
3 | NAF | Sodium Fluoride | Sodium fluoride
3 | NONE | None | No additive. Specifically identifes the specimen as having no additives.
3 | PAGE | Page's Saline | 0.12 g NaCl, 0.004 g MgSO, 0.004 g, CaCl, 0.142 g Na2HPO4 and 0.136 g KH2PO4 per liter of distilled water. Maintain Acanthaoemba viability.
3 | PHENOL | Phenol | Phenol. Urine preservative
3 | PVA | Polyvinylalcohol | Polyvinyl alcohol
3 | RLM | Reagan Lowe Medium | A transport medium formulated to maintain Bordetella pertussis viability.
3 | SILICA | Siliceous earth | Diatomaceous earth. For glucose determination blood samples

3 | SPS | Sodium polyanethol sulfonate 0.35% in 0.85% sodium chloride | Sodium polyanethol sulfonate in saline. Anticomplementary and antiphagocytic properties. Used in blood culture collection.
3 | SST | Serum Separator Tube | Polymer separator gel with clot activator
3 | STUTM | Stuart transport medium | Sodium Glycerophosphate 10.0g, Calcium Chloride 0.1g, Mercaptoacetic Acid 1.0ml, Distilled Water 1 liter
3 | THROM | Thrombin | Thrombin. Accelerates clotting.
3 | THYMOL | Thymol | 2-Isopropyl-5-methyl phenol. A preservative for 24 Hr Urine samples
3 | THYO | Thyoglycolate broth | A nutritive medium with a reducing agent (sodium thioglycolate) which, due to a chemical reaction, removes oxygen from the broth.
3 | TOLU | Toluene | Also known as Methylbenzene; Toluol; Phenylmethane. A preservative for 24 Hr Urine samples
3 | URETM | Ureaplasma transport medium | A buffered salt solution with antifungal agents added for the collection and transport of Ureaplasma specimens.
3 | VIRTM | Viral Transport medium | Sucrose 74.6g, Potassium hydrogenphosphate 0.52g, L-glutamic acid 0.72g, Bovine serum albumin 5.0g, Gentamicin 50mg, Potassium dihydrogenphosphate 1.25g, L-15 medium 9.9L, Water to 10L. Maintain Virus viability.
3 | WEST | Buffered Citrate | 3.8% Citrate buffered to a pH of 5.5 for Westergren Sedimentation Rate
2 | BLDPRD | Blood Product | A manufactured product that is produced from the raw blood oi a donor with the intention of using it in a recipient transfusion.
2 | VCCNE | Vaccine | A Type of medicine that creates an immune protection without the recipient experiencing the disease.
2 | (_DrugEntity) Abstract | | A substance whose therapeutic effect is produced by chemical action within the body.
3 | (_ClinicalDrug) Abstract | | Any substance or mixture of substances manufactured, sold or represented for use in: (a) the diagnosis, treatment, mitigation or prevention of a disease, disorder, abnormal physical state, or its symptoms, in human beings or animals; (b) restoring, correcting or modifying organic functions in human beings or animals.
1 | (_NonDrugAgentEntity) Abstract | | Indicates types of allergy and intolerance agents which are non-drugs. (E.g. foods, latex, etc.)
2 | NDA01 | egg
2 | NDA02 | fish
2 | NDA03 | lactose
2 | NDA04 | peanut
2 | NDA05 | soy
2 | NDA06 | sulfites
2 | NDA07 | wheat or gluten
2 | NDA08 | isocyanates
2 | NDA09 | solvents
2 | NDA10 | oils
2 | NDA11 | venoms
2 | NDA12 | latex
2 | NDA13 | shellfish
2 | NDA14 | strawberries
2 | NDA15 | tomatoes
2 | NDA16 | dust
2 | NDA17 | dust mites
1 | (_OrganizationEntityType) Abstract | | Further classifies entities of classCode ORG.
2 | HHOLD | household | The group of persons who occupy a single housing unit.
2 | NAT | NationEntityType | Codes identifying nation states. Allows for finer grained specification of Entity with classcode <= NAT Example:ISO3166 country codes.
2 | RELIG | religious institution | An organization that provides religious rites of worship.
1 | (_PlaceEntityType) Abstract | | Types of places for EntityClass "PLC"
2 | BED | Bed Location | The location of a bed
2 | BLDG | Building Location | The location of a building
2 | FLOOR | Floor Location | The location of a floor of a building
2 | ROOM | Room Location | The location of a room
2 | WING | Wing Location | The location of a wing of a building (e.g. East Wing). The same room number for the same floor number can be distinguished by wing number in some situations
1 | (_ResourceGroupEntityType) Abstract | | Codes to characterize a Resource Group using categories that typify its membership and/or function . Example: PractitionerGroup
2 | PRAC | PractitionerGroup

4.3.2.1061 HL7 v3 Code System EntityStatus

URL: https://hl7.org/fhir/STU3/v3/EntityStatus/cs.html

This page is part of the FHIR Specification (v3.0.2: STU 3). The current version which supercedes this version is 4.0.1. For a full list of available versions, see the Directory of published versions

Vocabulary Work Group | Maturity Level: N/A | External | Use Context: Any

This code system (http://hl7.org/fhir/v3/EntityStatus) is defined as part of HL7 v3.

Summary

Defining URL: | http://hl7.org/fhir/v3/EntityStatus
Name: | v3 Code System EntityStatus
Definition: | Codes representing the defined possible states of an Entity, as defined by the Entity class state machine.
OID: | 2.16.840.1.113883.5.1061 (for OID based terminology systems)
Source Resource | XML / JSON

This Code system is used in the following value sets:

* v3 Code System EntityStatus (Codes representing the defined possible states of an Entity, as defined by the Entity class state machine.)

4.3.2.1061.1 Code System Content

Release Date: 2016-11-11

Level | Code | Display | Definition
1 | normal | normal | The 'typical' state. Excludes "nullified" which represents the termination state of an Entity record instance that was created in error.
2 | active | active | The state representing the fact that the Entity record is currently active.
2 | inactive | inactive | Definition: The state representing the fact that the entity is inactive.
2 | terminated | terminated | The state representing the normal termination of an Entity record.
1 | nullified | nullified | The state representing the termination of an Entity record instance that was created in error.

4.3.2.1062 HL7 v3 Code System ManagedParticipationStatus

URL: https://hl7.org/fhir/STU3/v3/ManagedParticipationStatus/cs.html

This page is part of the FHIR Specification (v3.0.2: STU 3). The current version which supercedes this version is 4.0.1. For a full list of available versions, see the Directory of published versions

Vocabulary Work Group | Maturity Level: N/A | External | Use Context: Any

This code system (http://hl7.org/fhir/v3/ManagedParticipationStatus) is defined as part of HL7 v3.

Summary

Defining URL: | http://hl7.org/fhir/v3/ManagedParticipationStatus
Name: | v3 Code System ManagedParticipationStatus
Definition: | Codes representing the defined possible states of a Managed Participation, as defined by the Managed Participation class state machine.
OID: | 2.16.840.1.113883.5.1062 (for OID based terminology systems)
Source Resource | XML / JSON

This Code system is used in the following value sets:

* v3 Code System ManagedParticipationStatus (Codes representing the defined possible states of a Managed Participation, as defined by the Managed Participation class state machine.)

4.3.2.1062.1 Code System Content

Release Date: 2016-11-11

Level | Code | Display | Definition
1 | normal | normal | The 'typical' state. Excludes "nullified" which represents the termination state of a participation instance that was created in error.
2 | active | active | The state representing the fact that the Participation is in progress.
2 | cancelled | cancelled | The terminal state resulting from cancellation of the Participation prior to activation.
2 | completed | completed | The terminal state representing the successful completion of the Participation.
2 | pending | pending | The state representing that fact that the Participation has not yet become active.
1 | nullified | nullified | The state representing the termination of a Participation instance that was created in error.

4.3.2.1063 HL7 v3 Code System ObservationValue

URL: https://hl7.org/fhir/STU3/v3/ObservationValue/cs.html

This page is part of the FHIR Specification (v3.0.2: STU 3). The current version which supercedes this version is 4.0.1. For a full list of available versions, see the Directory of published versions

Vocabulary Work Group | Maturity Level: N/A | External | Use Context: Any

This code system (http://hl7.org/fhir/v3/ObservationValue) is defined as part of HL7 v3.

Summary

Defining URL: | http://hl7.org/fhir/v3/ObservationValue
Name: | v3 Code System ObservationValue
Definition: | This domain is the root domain to which all HL7-recognized value sets for the Observation.value attribute will be linked when Observation.value has a coded data type. OpenIssue: Description copied from Concept Domain of same name. Must be corrected..
OID: | 2.16.840.1.113883.5.1063 (for OID based terminology systems)
Source Resource | XML / JSON

This Code system is used in the following value sets:

* SecurityIntegrityObservationValue (No Description Provided)

* v3 Code System ObservationValue (This domain is the root domain to which all HL7-recognized value sets for the Observation.value attribute will be linked when Observation.value has a coded data type. OpenIssue: Description copied from Concept Domain of same name. Must be corrected..)

* SeverityObservation (Potential values for observations of severity.)

4.3.2.1063.1 Code System Content

Release Date: 2016-11-11

Level | Code | Display | Definition

1 | (_ActCoverageAssessmentObservationValue) Abstract | | Codes specify the category of observation, evidence, or document used to assess for services, e.g., discharge planning, or to establish eligibility for coverage under a policy or program. The type of evidence is coded as observation values.

2 | (_ActFinancialStatusObservationValue) Abstract | | Code specifying financial indicators used to assess or establish eligibility for coverage under a policy or program; e.g., pay stub; tax or income document; asset document; living expenses.

3 | ASSET | asset | Codes specifying asset indicators used to assess or establish eligibility for coverage under a policy or program.

4 | ANNUITY | annuity | Indicator of annuity ownership or status as beneficiary.

4 | PROP | real property | Indicator of real property ownership, e.g., deed or real estate contract.

4 | RETACCT | retirement investment account | Indicator of retirement investment account ownership.

4 | TRUST | trust | Indicator of status as trust beneficiary.

3 | INCOME | income | Code specifying income indicators used to assess or establish eligibility for coverage under a policy or program; e.g., pay or pension check, child support payments received or provided, and taxes paid.

4 | CHILD | child support | Indicator of child support payments received or provided.

4 | DISABL | disability pay | Indicator of disability income replacement payment.

4 | INVEST | investment income | Indicator of investment income, e.g., dividend check, annuity payment; real estate rent, investment divestiture proceeds; trust or endowment check.

4 | PAY | paid employment | Indicator of paid employment, e.g., letter of hire, contract, employer letter; copy of pay check or pay stub.

4 | RETIRE | retirement pay | Indicator of retirement payment, e.g., pension check.

4 | SPOUSAL | spousal or partner support | Indicator of spousal or partner support payments received or provided; e.g., alimony payment; support stipulations in a divorce settlement.

4 | SUPPLE | income supplement | Indicator of income supplement, e.g., gifting, parental income support; stipend, or grant.

4 | TAX | tax obligation | Indicator of tax obligation or payment, e.g., statement of taxable income.

3 | LIVEXP | living expense | Codes specifying living expense indicators used to assess or establish eligibility for coverage under a policy or program.

4 | CLOTH | clothing expense | Indicator of clothing expenses.

4 | FOOD | food expense | Indicator of transportation expenses.

4 | HEALTH | health expense | Indicator of health expenses; including medication costs, health service costs, financial participations, and health coverage premiums.

4 | HOUSE | household expense | Indicator of housing expense, e.g., household appliances, fixtures, furnishings, and maintenance and repairs.

4 | LEGAL | legal expense | Indicator of legal expenses.

4 | MORTG | mortgage | Indicator of mortgage amount, interest, and payments.

4 | RENT | rent | Indicator of rental or lease payments.

4 | SUNDRY | sundry expense | Indicator of transportation expenses.

4 | TRANS | transportation expense | Indicator of transportation expenses, e.g., vehicle payments, vehicle insurance, vehicle fuel, and vehicle maintenance and repairs.

4 | UTIL | utility expense | Indicator of transportation expenses.

2 | ELSTAT | eligibility indicator | Code specifying eligibility indicators used to assess or establish eligibility for coverage under a policy or program eligibility status, e.g., certificates of creditable coverage; student enrollment; adoption, marriage or birth certificate.

3 | ADOPT | adoption document | Indicator of adoption.

3 | BTHCERT | birth certificate | Indicator of birth.

3 | CCOC | creditable coverage document | Indicator of creditable coverage.

3 | DRLIC | driver license | Indicator of driving status.

3 | FOSTER | foster child document | Indicator of foster child status.

3 | MEMBER | program or policy member | Indicator of status as covered member under a policy or program, e.g., member id card or coverage document.

3 | MIL | military identification | Indicator of military status.

3 | MRGCERT | marriage certificate | Indicator of marriage status.

3 | PASSPORT | passport | Indicator of citizenship.

3 | STUDENRL | student enrollment | Indicator of student status.

2 | HLSTAT | health status | Code specifying non-clinical indicators related to health status used to assess or establish eligibility for coverage under a policy or program, e.g., pregnancy, disability, drug use, mental health issues.

3 | DISABLE | disabled | Indication of disability.

3 | DRUG | drug use | Indication of drug use.

3 | IVDRG | IV drug use | Indication of IV drug use .

3 | PGNT | pregnant | Non-clinical report of pregnancy.

2 | LIVDEP | living dependency | Code specifying observations related to living dependency, such as dependent upon spouse for activities of daily living.

3 | RELDEP | relative dependent | Continued living in private residence requires functional and health care assistance from one or more relatives.

3 | SPSDEP | spouse dependent | Continued living in private residence requires functional and health care assistance from spouse or life partner.

3 | URELDEP | unrelated person dependent | Continued living in private residence requires functional and health care assistance from one or more unrelated persons.

2 | LIVSIT | living situation | Code specifying observations related to living situation for a person in a private residence.

3 | ALONE | alone | Living alone. Maps to PD1-2 Living arrangement (IS) 00742 [A]

3 | DEPCHD | dependent children | Living with one or more dependent children requiring moderate supervision.

3 | DEPSPS | dependent spouse | Living with disabled spouse requiring functional and health care assistance

3 | DEPYGCHD | dependent young children | Living with one or more dependent children requiring intensive supervision

3 | FAM | live with family | Living with family. Maps to PD1-2 Living arrangement (IS) 00742 [F]

3 | RELAT | relative | Living with one or more relatives. Maps to PD1-2 Living arrangement (IS) 00742 [R]

3 | SPS | spouse only | Living only with spouse or life partner. Maps to PD1-2 Living arrangement (IS) 00742 [S]

3 | UNREL | unrelated person | Living with one or more unrelated persons.

2 | SOECSTAT | socio economic status | Code specifying observations or indicators related to socio-economic status used to assess to assess for services, e.g., discharge planning, or to establish eligibility for coverage under a policy or program.

3 | ABUSE | abuse victim | Indication of abuse victim.
3 | HMLESS | homeless | Indication of status as homeless.
3 | ILGIM | illegal immigrant | Indication of status as illegal immigrant.
3 | INCAR | incarcerated | Indication of status as incarcerated.
3 | PROB | probation | Indication of probation status.
3 | REFUG | refugee | Indication of refugee status.
3 | UNEMPL | unemployed | Indication of unemployed status.
1 | (_AllergyTestValue) Abstract | | Indicates the result of a particular allergy test. E.g. Negative, Mild, Moderate, Severe
2 | A0 | no reaction | Description:Patient exhibits no reaction to the challenge agent.
2 | A1 | minimal reaction | Description:Patient exhibits a minimal reaction to the challenge agent.
2 | A2 | mild reaction | Description:Patient exhibits a mild reaction to the challenge agent.
2 | A3 | moderate reaction | Description:Patient exhibits moderate reaction to the challenge agent.
2 | A4 | severe reaction | Description:Patient exhibits a severe reaction to the challenge agent.
1 | (_CompositeMeasureScoring) Abstract | | Observation values that communicate the method used in a quality measure to combine the component measure results included in an composite measure.
2 | ALLORNONESCR | All-or-nothing Scoring | Code specifying that the measure uses all-or-nothing scoring. All-or-nothing scoring places an individual in the numerator of the composite measure if and only if they are in the numerator of all component measures in which they are in the denominator.
2 | LINEARSCR | Linear Scoring | Code specifying that the measure uses linear scoring. Linear scoring computes the fraction of component measures in which the individual appears in the numerator, giving equal weight to each component measure.
2 | OPPORSCR | Opportunity Scoring | Code specifying that the measure uses opportunity-based scoring. In opportunity-based scoring the measure score is determined by combining the denominator and numerator of each component measure to determine an overall composite score.
2 | WEIGHTSCR | Weighted Scoring | Code specifying that the measure uses weighted scoring. Weighted scoring assigns a factor to each component measure to weight that measure's contribution to the overall score.
1 | (_CoverageLimitObservationValue) Abstract | | Description:Coded observation values for coverage limitations, for e.g., types of claims or types of parties covered under a policy or program.
2 | (_CoverageLevelObservationValue) Abstract | | Description:Coded observation values for types of covered parties under a policy or program based on their personal relationships or employment status.
3 | ADC | adult child | Description:Child over an age as specified by coverage policy or program, e.g., student, differently abled, and income dependent.
3 | CHD | child | Description:Dependent biological, adopted, foster child as specified by coverage policy or program.
3 | DEP | dependent | Description:Person requiring functional and/or financial assistance from another person as specified by coverage policy or program.
3 | DP | domestic partner | Description:Persons registered as a family unit in a domestic partner registry as specified by law and by coverage policy or program.
3 | ECH | employee | Description:An individual employed by an employer who receive remuneration in wages, salary, commission, tips, piece-rates, or pay-in-kind through the employeraTMs payment system (i.e., not a contractor) as specified by coverage policy or program.
3 | FLY | family coverage | Description:As specified by coverage policy or program.
3 | IND | individual | Description:Person as specified by coverage policy or program.
3 | SSP | same sex partner | Description:A pair of people of the same gender who live together as a family as specified by coverage policy or program, e.g., Naomi and Ruth from the Book of Ruth; Socrates and Alcibiades
1 | (_CriticalityObservationValue) Abstract | | A clinical judgment as to the worst case result of a future exposure (including substance administration). When the worst case result is assessed to have a life-threatening or organ system threatening potential, it is considered to be of high criticality.
2 | CRITH | high criticality | Worst case result of a future exposure is assessed to be life-threatening or having high potential for organ system failure.
2 | CRITL | low criticality | Worst case result of a future exposure is not assessed to be life-threatening or having high potential for organ system failure.
2 | CRITU | unable to assess criticality | Unable to assess the worst case result of a future exposure.
1 | (_GeneticObservationValue) Abstract | | Description: The domain contains genetic analysis specific observation values, e.g. Homozygote, Heterozygote, etc.
2 | Homozygote | HOMO | Description: An individual having different alleles at one or more loci regarding a specific character
1 | (_ObservationMeasureScoring) Abstract | | Observation values used to indicate the type of scoring (e.g. proportion, ratio) used by a health quality measure.
2 | COHORT | cohort measure scoring | A measure in which either short-term cross-section or long-term longitudinal analysis is performed over a group of subjects defined by a set of common properties or defining characteristics (e.g., Male smokers between the ages of 40 and 50 years, exposure to treatment, exposure duration).
2 | CONTVAR | continuous variable measure scoring | A measure score in which each individual value for the measure can fall anywhere along a continuous scale (e.g., mean time to thrombolytics which aggregates the time in minutes from a case presenting with chest pain to the time of administration of thrombolytics).
2 | PROPOR | proportion measure scoring | A score derived by dividing the number of cases that meet a criterion for quality (the numerator) by the number of eligible cases within a given time frame (the denominator) where the numerator cases are a subset of the denominator cases (e.g., percentage of eligible women with a mammogram performed in the last year).
2 | RATIO | ratio measure scoring | A score that may have a value of zero or greater that is derived by dividing a count of one type of data by a count of another type of data (e.g., the number of patients with central lines who develop infection divided by the number of central line days).
1 | (_ObservationMeasureType) Abstract | | Observation values used to indicate what kind of health quality measure is used.
2 | COMPOSITE | composite measure type | A measure that is composed from one or more other measures and indicates an overall summary of those measures.
2 | EFFICIENCY | efficiency measure type | A measure related to the efficiency of medical treatment.
2 | EXPERIENCE | experience measure type | A measure related to the level of patient engagement or patient experience of care.
2 | OUTCOME | outcome measure type | A measure that indicates the result of the performance (or non-performance) of a function or process.
2 | PROCESS | process measure type | A measure which focuses on a process which leads to a certain outcome, meaning that a scientific basis exists for believing that the process, when executed well, will increase the probability of achieving a desired outcome.
2 | RESOURCE | resource use measure type | A measure related to the extent of use of clinical resources or cost of care.
2 | STRUCTURE | structure measure type | A measure related to the structure of patient care.
1 | _ObservationPopulationInclusion Deprecated | ObservationPopulationInclusion | Observation values used to assert various populations that a subject falls into.

2 | DENEX Deprecated | denominator exclusions | Patients who should be removed from the eMeasure population and denominator before determining if numerator criteria are met. Denominator exclusions are used in proportion and ratio measures to help narrow the denominator.

2 | DENEXCEP Deprecated | denominator exceptions | Denominator exceptions are those conditions that should remove a patient, procedure or unit of measurement from the denominator only if the numerator criteria are not met. Denominator exceptions allow for adjustment of the calculated score for those providers with higher risk populations. Denominator exceptions are used only in proportion eMeasures. They are not appropriate for ratio or continuous variable eMeasures. Denominator exceptions allow for the exercise of clinical judgment and should be specifically defined where capturing the information in a structured manner fits the clinical workflow. Generic denominator exception reasons used in proportion eMeasures fall into three general categories: Medical reasons Patient reasons System reasons

2 | DENOM Deprecated | denominator | It can be the same as the initial patient population or a subset of the initial patient population to further constrain the population for the purpose of the eMeasure. Different measures within an eMeasure set may have different Denominators. Continuous Variable eMeasures do not have a Denominator, but instead define a Measure Population.

2 | IP Deprecated | initial population | The initial population refers to all entities to be evaluated by a specific quality measure who share a common set of specified characteristics within a specific measurement set to which a given measure belongs.

3 | IPP Deprecated | initial patient population | The initial patient population refers to all patients to be evaluated by a specific quality measure who share a common set of specified characteristics within a specific measurement set to which a given measure belongs. Details often include information based upon specific age groups, diagnoses, diagnostic and procedure codes, and enrollment periods.

2 | MSRPOPL Deprecated | measure population | Measure population is used only in continuous variable eMeasures. It is a narrative description of the eMeasure population. (e.g., all patients seen in the Emergency Department during the measurement period).

2 | NUMER Deprecated | numerator | Numerators are used in proportion and ratio eMeasures. In proportion measures the numerator criteria are the processes or outcomes expected for each patient, procedure, or other unit of measurement defined in the denominator. In ratio measures the numerator is related, but not directly derived from the denominator (e.g., a numerator listing the number of central line blood stream infections and a denominator indicating the days per thousand of central line usage in a specific time period).

2 | NUMEX Deprecated | numerator exclusions | Numerator Exclusions are used only in ratio eMeasures to define instances that should not be included in the numerator data. (e.g., if the number of central line blood stream infections per 1000 catheter days were to exclude infections with a specific bacterium, that bacterium would be listed as a numerator exclusion.)

1 | (_PartialCompletionScale) Abstract

2 | G | Great extent | Value for Act.partialCompletionCode attribute that implies 81-99% completion

2 | LE | Large extent | Value for Act.partialCompletionCode attribute that implies 61-80% completion

2 | ME | Medium extent | Value for Act.partialCompletionCode attribute that implies 41-60% completion

2 | MI | Minimal extent | Value for Act.partialCompletionCode attribute that implies 1-20% completion

2 | N | None | Value for Act.partialCompletionCode attribute that implies 0% completion

2 | S | Some extent | Value for Act.partialCompletionCode attribute that implies 21-40% completion

1 | (_SecurityObservationValue) Abstract | | Observation values used to indicate security observation metadata.

2 | (_SECINTOBV) Abstract | | Abstract security observation values used to indicate security integrity metadata. Examples: Codes conveying integrity status, integrity confidence, and provenance.

3 | (_SECALTINTOBV) Abstract | | Abstract security metadata observation values used to indicate mechanism used for authorized alteration of an IT resource (data, information object, service, or system capability)

4 | ABSTRED | abstracted | Security metadata observation values used to indicate the use of a more abstract version of the content, e.g., replacing exact value of an age or date field with a range, or remove the left digits of a credit card number or SSN.

4 | AGGRED | aggregated | Security metadata observation values used to indicate the use of an algorithmic combination of actual values with the result of an aggregate function, e.g., average, sum, or count in order to limit disclosure of an IT resource (data, information object, service, or system capability) to the minimum necessary.

4 | ANONYED | anonymized | Security metadata observation value conveying the alteration integrity of an IT resource (data, information object, service, or system capability) by used to indicate the mechanism by which software systems can strip portions of the resource that could allow the identification of the source of the information or the information subject. No key to relink the data is retained.

4 | MAPPED | mapped | Security metadata observation value used to indicate that the IT resource semantic content has been transformed from one encoding to another. Usage Note: "MAP" code does not indicate the semantic fidelity of the transformed content. To indicate semantic fidelity for maps of HL7 to other code systems, this security alteration integrity observation may be further specified using an Act valued with Value Set: MapRelationship (2.16.840.1.113883.1.11.11052). Semantic fidelity of the mapped IT Resource may also be indicated using a SecurityIntegrityConfidenceObservation.

4 | MASKED | masked | Security metadata observation value conveying the alteration integrity of an IT resource (data, information object, service, or system capability) by indicating the mechanism by which software systems can make data unintelligible (that is, as unreadable and unusable by algorithmically transforming plaintext into ciphertext) such that it can only be accessed or used by authorized users. An authorized user may be provided a key to decrypt per license or "shared secret". Usage Note: "MASKED" may be used, per applicable policy, as a flag to indicate to a user or receiver that some portion of an IT resource has been further encrypted, and may be accessed only by an authorized user or receiver to which a decryption key is provided.

4 | PSEUDED | pseudonymized | Security metadata observation value conveying the alteration integrity of an IT resource (data, information object, service, or system capability), by indicating the mechanism by which software systems can strip portions of the resource that could allow the identification of the source of the information or the information subject. Custodian may retain a key to relink data necessary to reidentify the information subject. Rationale: Personal data which has been processed to make it impossible to know whose data it is. Used particularly for secondary use of health data. In some cases, it may be possible for authorized individuals to restore the identity of the individual, e.g.,for public health case management. Based on ISO/TS 25237:2008 Health informaticsâ€"Pseudonymization

4 | REDACTED | redacted | Security metadata observation value used to indicate the mechanism by which software systems can filter an IT resource (data, information object, service, or system capability) to remove any portion of the resource that is not authorized to be access, used, or disclosed. Usage Note: "REDACTED" may be used, per applicable policy, as a flag to indicate to a user or receiver that some portion of an IT resource has filtered and not included in the content accessed or received.

4 | SUBSETTED | subsetted | Metadata observation used to indicate that some information has been removed from the source object when the view this object contains was constructed because of configuration options when the view was created. The content may not be suitable for use as the basis of a record update Usage Note: This is not suitable to be used when information is removed for security reasons - see the code REDACTED for this use.

4 | SYNTAC | syntactic transform | Security metadata observation value used to indicate that the IT resource syntax has been transformed from one syntactical representation to another. Usage Note: "SYNTAC" code does not indicate the syntactical correctness of the syntactically transformed IT resource.

4 | TRSLT | translated | Security metadata observation value used to indicate that the IT resource has been translated from one human language to another. Usage Note: "TRSLT" does not indicate the fidelity of the translation or the languages translated. The fidelity of the IT Resource translation may be indicated using a SecurityIntegrityConfidenceObservation. To indicate languages, use the Value Set:HumanLanguage (2.16.840.1.113883.1.11.11526)

4 | VERSIONED | versioned | Security metadata observation value conveying the alteration integrity of an IT resource (data, information object, service, or system capability) which indicates that the resource only retains versions of an IT resource for access and use per applicable policy Usage Note: When this code is used, expectation is that the system has removed historical versions of the data that falls outside the time period deemed to be the effective time of the applicable version.

3 | (_SECDATINTOBV) Abstract | | Abstract security observation values used to indicate data integrity metadata. Examples: Codes conveying the mechanism used to preserve the accuracy and consistency of an IT resource such as a digital signature and a cryptographic hash function.

4 | CRYTOHASH | cryptographic hash function | Security metadata observation value used to indicate the mechanism by which software systems can establish that data was not modified in transit. Rationale: This definition is intended to align with the ISO 22600-2 3.3.19 definition of cryptographic checkvalue: Information which is derived by performing a cryptographic transformation (see cryptography) on the data unit. The derivation of the checkvalue may be performed in one or more steps and is a result of a mathematical function of the key and a data unit. It is usually used to check the integrity of a data unit. Examples: SHA-1 SHA-2 (Secure Hash Algorithm)

4 | DIGSIG | digital signature | Security metadata observation value used to indicate the mechanism by which software systems use digital signature to establish that data has not been modified. Rationale: This definition is intended to align with the ISO 22600-2 3.3.26 definition of digital signature: Data appended to, or a cryptographic transformation (see cryptography) of, a data unit that allows a recipient of the data unit to prove the source and integrity of the data unit and protect against forgery e.g., by the recipient.

3 | (_SECINTCONOBV) Abstract | | Abstract security observation value used to indicate integrity confidence metadata. Examples: Codes conveying the level of reliability and trustworthiness of an IT resource.

4 | HRELIABLE | highly reliable | Security metadata observation value used to indicate that the veracity or trustworthiness of an IT resource (data, information object, service, or system capability) for a specified purpose of use is perceived to be or deemed by policy to be very high.

4 | RELIABLE | reliable | Security metadata observation value used to indicate that the veracity or trustworthiness of an IT resource (data, information object, service, or system capability) for a specified purpose of use is perceived to be or deemed by policy to be adequate.

4 | UNCERTREL | uncertain reliability | Security metadata observation value used to indicate that the veracity or trustworthiness of an IT resource (data, information object, service, or system capability) for a specified purpose of use is perceived to be or deemed by policy to be uncertain.

4 | UNRELIABLE | unreliable | Security metadata observation value used to indicate that the veracity or trustworthiness of an IT resource (data, information object, service, or system capability) for a specified purpose of use is perceived to be or deemed by policy to be inadequate.

3 | (_SECINTPRVOBV) Abstract | | Abstract security metadata observation value used to indicate the provenance of an IT resource (data, information object, service, or system capability). Examples: Codes conveying the provenance metadata about the entity reporting an IT resource.

4 | (_SECINTPRVABOBV) Abstract | | Abstract security provenance metadata observation value used to indicate the entity that asserted an IT resource (data, information object, service, or system capability). Examples: Codes conveying the provenance metadata about the entity asserting the resource.

5 | CLINAST | clinician asserted | Security provenance metadata observation value used to indicate that an IT resource (data, information object, service, or system capability) was asserted by a clinician.

5 | DEVAST | device asserted | Security provenance metadata observation value used to indicate that an IT resource (data, information object, service, or system capability) was asserted by a device.

5 | HCPAST | healthcare professional asserted | Security provenance metadata observation value used to indicate that an IT resource (data, information object, service, or system capability) was asserted by a healthcare professional.

5 | PACQAST | patient acquaintance asserted | Security provenance metadata observation value used to indicate that an IT resource (data, information object, service, or system capability) was asserted by a patient acquaintance.

5 | PATAST | patient asserted | Security provenance metadata observation value used to indicate that an IT resource (data, information object, service, or system capability) was asserted by a patient.

5 | PAYAST | payer asserted | Security provenance metadata observation value used to indicate that an IT resource (data, information object, service, or system capability) was asserted by a payer.

5 | PROAST | professional asserted | Security provenance metadata observation value used to indicate that an IT resource (data, information object, service, or system capability) was asserted by a professional.

5 | SDMAST | substitute decision maker asserted | Security provenance metadata observation value used to indicate that an IT resource (data, information object, service, or system capability) was asserted by a substitute decision maker.

4 | (_SECINTPRVRBOBV) Abstract | | Abstract security provenance metadata observation value used to indicate the entity that reported the resource (data, information object, service, or system capability). Examples: Codes conveying the provenance metadata about the entity reporting an IT resource.

5 | CLINRPT | clinician reported | Security provenance metadata observation value used to indicate that an IT resource (data, information object, service, or system capability) was reported by a clinician.

5 | DEVRPT | device reported | Security provenance metadata observation value used to indicate that an IT resource (data, information object, service, or system capability) was reported by a device.

5 | HCPRPT | healthcare professional reported | Security provenance metadata observation value used to indicate that an IT resource (data, information object, service, or system capability) was reported by a healthcare professional.

5 | PACQRPT | patient acquaintance reported | Security provenance metadata observation value used to indicate that an IT resource (data, information object, service, or system capability) was reported by a patient acquaintance.

5 | PATRPT | patient reported | Security provenance metadata observation value used to indicate that an IT resource (data, information object, service, or system capability) was reported by a patient.

5 | PAYRPT | payer reported | Security provenance metadata observation value used to indicate that an IT resource (data, information object, service, or system capability) was reported by a payer.

5 | PRORPT | professional reported | Security provenance metadata observation value used to indicate that an IT resource (data, information object, service, or system capability) was reported by a professional.

5 | SDMRPT | substitute decision maker reported | Security provenance metadata observation value used to indicate that an IT resource (data, information object, service, or system capability) was reported by a substitute decision maker.

2 | (SECTRSTOBV) Abstract | | Observation value used to indicate aspects of trust applicable to an IT resource (data, information object, service, or system capability).

3 | TRSTACCRDOBV | trust accreditation observation | Values for security trust accreditation metadata observation made about the formal declaration by an authority or neutral third party that validates the technical, security, trust, and business practice conformance of Trust Agents to facilitate security, interoperability, and trust among participants within a security domain or trust framework.

3 | TRSTAGREOBV | trust agreement observation | Values for security trust agreement metadata observation made about privacy and security requirements with which a security domain must comply. [ISO IEC 10181-1] [ISO IEC 10181-1]

3 | TRSTCERTOBV | trust certificate observation | Values for security trust certificate metadata observation made about a set of security-relevant data issued by a security authority or trusted third party, together with security information which is used to provide the integrity and data origin authentication services for an IT resource (data, information object, service, or system capability). [Based on ISO IEC 10181-1] For example, a Certificate Policy (CP), which is a named set of rules that indicates the applicability of a certificate to a particular community and/or class of

application with common security requirements. A particular Certificate Policy might indicate the applicability of a type of certificate to the authentication of electronic data interchange transactions for the trading of goods within a given price range. Another example is Cross Certification with Federal Bridge.

3 | (TRSTLOAOBV) Abstract | | Values for security trust assurance metadata observation made about the digital quality or reliability of a trust assertion, activity, capability, information exchange, mechanism, process, or protocol.

4 | (LOAAN) Abstract | | The value assigned as the indicator of the digital quality or reliability of the verification and validation process used to verify the claimed identity of an entity by securely associating an identifier and its authenticator. [Based on ISO 7498-2] For example, the degree of confidence in the vetting process used to establish the identity of the individual to whom the credential was issued, and 2) the degree of confidence that the individual who uses the credential is the individual to whom the credential was issued. [OMB M-04-04 E-Authentication Guidance for Federal Agencies]

5 | LOAAN1 | low authentication level of assurance | Indicator of low digital quality or reliability of the digital reliability of the verification and validation process used to verify the claimed identity of an entity by securely associating an identifier and its authenticator. [Based on ISO 7498-2] The degree of confidence in the vetting process used to establish the identity of the individual to whom the credential was issued, and 2) the degree of confidence that the individual who uses the credential is the individual to whom the credential was issued. [OMB M-04-04 E-Authentication Guidance for Federal Agencies] Low authentication level of assurance indicates that the relying party may have little or no confidence in the asserted identity's validity. Level 1 requires little or no confidence in the asserted identity. No identity proofing is required at this level, but the authentication mechanism should provide some assurance that the same claimant is accessing the protected transaction or data. A wide range of available authentication technologies can be employed and any of the token methods of Levels 2, 3, or 4, including Personal Identification Numbers (PINs), may be used. To be authenticated, the claimant must prove control of the token through a secure authentication protocol. At Level 1, long-term shared authentication secrets may be revealed to verifiers. Assertions issued about claimants as a result of a successful authentication are either cryptographically authenticated by relying parties (using approved methods) or are obtained directly from a trusted party via a secure authentication protocol. [Summary of the technical requirements specified in NIST SP 800-63 for the four levels of assurance defined by the December 2003, the Office of Management and Budget (OMB) issued Memorandum M-04-04, E-Authentication Guidance for Federal Agencies.]

5 | LOAAN2 | basic authentication level of assurance | Indicator of basic digital quality or reliability of the digital reliability of the verification and validation process used to verify the claimed identity of an entity by securely associating an identifier and its authenticator. [Based on ISO 7498-2] The degree of confidence in the vetting process used to establish the identity of the individual to whom the credential was issued, and 2) the degree of confidence that the individual who uses the credential is the individual to whom the credential was issued. [OMB M-04-04 E-Authentication Guidance for Federal Agencies] Basic authentication level of assurance indicates that the relying party may have some confidence in the asserted identity's validity. Level 2 requires confidence that the asserted identity is accurate. Level 2 provides for single-factor remote network authentication, including identity-proofing requirements for presentation of identifying materials or information. A wide range of available authentication technologies can be employed, including any of the token methods of Levels 3 or 4, as well as passwords. Successful authentication requires that the claimant prove through a secure authentication protocol that the claimant controls the token. Eavesdropper, replay, and online guessing attacks are prevented. Long-term shared authentication secrets, if used, are never revealed to any party except the claimant and verifiers operated by the CSP; however, session (temporary) shared secrets may be provided to independent verifiers by the CSP. Approved cryptographic techniques are required. Assertions issued about claimants as a result of a successful authentication are either cryptographically authenticated by relying parties (using approved methods) or are obtained directly from a trusted party via a secure authentication protocol. [Summary of the technical requirements specified in NIST SP 800-63 for the four levels of assurance defined by the December 2003, the Office of Management and Budget (OMB) issued Memorandum M-04-04, E-Authentication Guidance for Federal Agencies.]

5 | LOAAN3 | medium authentication level of assurance | Indicator of medium digital quality or reliability of the digital reliability of verification and validation of the process used to verify the claimed identity of an entity by securely associating an identifier and its authenticator. [Based on ISO 7498-2] The degree of confidence in the vetting process used to establish the identity of the individual to whom the credential was issued, and 2) the degree of confidence that the individual who uses the credential is the individual to whom the credential was issued. [OMB M-04-04 E-Authentication Guidance for Federal Agencies] Medium authentication level of assurance indicates that the relying party may have high confidence in the asserted identity's validity. Level 3 is appropriate for transactions that need high confidence in the accuracy of the asserted identity. Level 3 provides multifactor remote network authentication. At this level, identity-proofing procedures require verification of identifying materials and information. Authentication is based on proof of possession of a key or password through a cryptographic protocol. Cryptographic strength mechanisms should protect the primary authentication token (a cryptographic key) against compromise by the protocol threats, including eavesdropper, replay, online guessing, verifier impersonation, and man-in-the-middle attacks. A minimum of two authentication factors is required. Three kinds of tokens may be used: "soft" cryptographic token, which has the key stored on a general-purpose computer, "hard" cryptographic token, which has the key stored on a special hardware device, and "one-time password" device token, which has symmetric key stored on a personal hardware device that is a cryptographic module validated at FIPS 140-2 Level 1 or higher. Validation testing of cryptographic modules and algorithms for conformance to Federal Information Processing Standard (FIPS) 140-2, Security Requirements for Cryptographic Modules, is managed by NIST. Authentication requires that the claimant prove control of the token through a secure authentication protocol. The token must be unlocked with a password or biometric representation, or a password must be used in a secure authentication protocol, to establish two-factor authentication. Long-term shared authentication secrets, if used, are never revealed to any party except the claimant and verifiers operated directly by the CSP; however, session (temporary) shared secrets may be provided to independent verifiers by the CSP. Approved cryptographic techniques are used for all operations. Assertions issued about claimants as a result of a successful authentication are either cryptographically authenticated by relying parties (using approved methods) or are obtained directly from a trusted party via a secure authentication protocol. [Summary of the technical requirements specified in NIST SP 800-63 for the four levels of assurance defined by the December 2003, the Office of Management and Budget (OMB) issued Memorandum M-04-04, E-Authentication Guidance for Federal Agencies.]

5 | LOAAN4 | high authentication level of assurance | Indicator of high digital quality or reliability of the digital reliability of the verification and validation process used to verify the claimed identity of an entity by securely associating an identifier and its authenticator. [Based on ISO 7498-2] The degree of confidence in the vetting process used to establish the identity of the individual to whom the credential was issued, and 2) the degree of confidence that the individual who uses the credential is the individual to whom the credential was issued. [OMB M-04-04 E-Authentication Guidance for Federal Agencies] High authentication level of assurance indicates that the relying party may have very high confidence in the asserted identity's validity. Level 4 is for transactions that need very high confidence in the accuracy of the asserted identity. Level 4 provides the highest practical assurance of remote network authentication. Authentication is based on proof of possession of a key through a cryptographic protocol. This level is similar to Level 3 except that only â€œhardâ€? cryptographic tokens are allowed, cryptographic module validation requirements are strengthened, and subsequent critical data transfers must be authenticated via a key that is bound to the authentication process. The token should be a hardware cryptographic module validated at FIPS 140-2 Level 2 or higher overall with at least FIPS 140-2 Level 3 physical security. This level requires a physical token, which cannot readily be copied, and operator authentication at Level 2 and higher, and ensures good, two-factor remote authentication. Level 4 requires strong cryptographic authentication of all parties and all sensitive data transfers between the parties. Either public key or symmetric key technology may be used. Authentication requires that the claimant prove through a secure authentication protocol that the claimant controls the token. Eavesdropper, replay, online guessing, verifier impersonation, and man-in-the-middle attacks are prevented. Long-term shared authentication secrets, if used, are never revealed to any party except the claimant and verifiers operated directly by the CSP; however, session (temporary) shared secrets may be provided to independent verifiers by the CSP. Strong approved cryptographic techniques are used for all operations. All sensitive data transfers are cryptographically authenticated using keys bound to the authentication process. [Summary of the technical requirements specified in NIST SP 800-63 for the four levels of assurance defined by the December 2003, the Office of Management and Budget (OMB) issued Memorandum M-04-04, E-Authentication Guidance for Federal Agencies.]

4 | (LOAAP) Abstract | | The value assigned as the indicator of the digital quality or reliability of a defined sequence of messages between a Claimant and a Verifier that demonstrates that the Claimant has possession and control of a valid token to establish his/her identity, and optionally, demonstrates to the Claimant that he or she is communicating with the intended Verifier. [Based on NIST SP 800-63-2]

5 | LOAAP1 | low authentication process level of assurance | Indicator of the low digital quality or reliability of a defined sequence of messages between a Claimant and a Verifier that demonstrates that the Claimant has possession and control of a valid token to establish his/her identity, and optionally, demonstrates to the Claimant that he or she is communicating with the intended Verifier. [Based on NIST SP 800-63-2] Low authentication process level of assurance indicates that (1) long-term shared authentication secrets may be revealed to verifiers; and (2) assertions and assertion references require protection from manufacture/modification and reuse attacks. [Summary of the technical requirements specified in NIST SP 800-63 for the four levels of assurance defined by the December 2003, the Office of Management and Budget (OMB) issued Memorandum M-04-04, E-Authentication Guidance for Federal Agencies.]

5 | LOAAP2 | basic authentication process level of assurance | Indicator of the basic digital quality or reliability of a defined sequence of messages between a Claimant and a Verifier that demonstrates that the Claimant has possession and control of a valid token to establish his/her identity, and optionally, demonstrates to the Claimant that he or she is communicating with the intended Verifier. [Based on NIST SP 800-63-2] Basic authentication process level of assurance indicates that long-term shared authentication secrets are never revealed to any other party except Credential Service Provider (CSP). Sessions (temporary) shared secrets may be provided to independent verifiers by CSP. Long-term shared authentication secrets, if used, are never revealed to any other party except Verifiers operated by the Credential Service Provider (CSP); however, session (temporary) shared secrets may be provided to independent Verifiers by the CSP. In addition to Level 1 requirements, assertions are resistant to disclosure, redirection, capture and substitution attacks. Approved cryptographic techniques are required. [Summary of the technical requirements specified in NIST SP 800-63 for the four levels of assurance defined by the December 2003, the Office of Management and Budget (OMB) issued Memorandum M-04-04, E-Authentication Guidance for Federal Agencies.]

5 | LOAAP3 | medium authentication process level of assurance | Indicator of the medium digital quality or reliability of a defined sequence of messages between a Claimant and a Verifier that demonstrates that the Claimant has possession and control of a valid token to establish his/her identity, and optionally, demonstrates to the Claimant that he or she is communicating with the intended Verifier. [Based on NIST SP 800-63-2] Medium authentication process level of assurance indicates that the token can be unlocked with password, biometric, or uses a secure multi-token authentication protocol to establish two-factor authentication. Long-term shared authentication secrets are never revealed to any party except the Claimant and Credential Service Provider (CSP). Authentication requires that the Claimant prove, through a secure authentication protocol, that he or she controls the token. The Claimant unlocks the token with a password or biometric, or uses a secure multi-token authentication protocol to establish two-factor authentication (through proof of possession of a physical or software token in combination with some memorized secret knowledge). Long-term shared authentication secrets, if used, are never revealed to any party except the Claimant and Verifiers operated directly by the CSP; however, session (temporary) shared secrets may be provided to independent Verifiers by the CSP. In addition to Level 2 requirements, assertions are protected against repudiation by the Verifier.

5 | LOAAP4 | high authentication process level of assurance | Indicator of the high digital quality or reliability of a defined sequence of messages between a Claimant and a Verifier that demonstrates that the Claimant has possession and control of a valid token to establish his/her identity, and optionally, demonstrates to the Claimant that he or she is communicating with the intended Verifier. [Based on NIST SP 800-63-2] High authentication process level of assurance indicates all sensitive data transfer are cryptographically authenticated using keys bound to the authentication process. Level 4 requires strong cryptographic authentication of all communicating parties and all sensitive data transfers between the parties. Either public key or symmetric key technology may be used. Authentication requires that the Claimant prove through a secure authentication protocol that he or she controls the token. All protocol threats at Level 3 are required to be prevented at Level 4. Protocols shall also be strongly resistant to man-in-the-middle attacks. Long-term shared authentication secrets, if used, are never revealed to any party except the Claimant and Verifiers operated directly by the CSP; however, session (temporary) shared secrets may be provided to independent Verifiers by the CSP. Approved cryptographic techniques are used for all operations. All sensitive data transfers are cryptographically authenticated using keys bound to the authentication process. [Summary of the technical requirements specified in NIST SP 800-63 for the four levels of assurance defined by the December 2003, the Office of Management and Budget (OMB) issued Memorandum M-04-04, E-Authentication Guidance for Federal Agencies.]

4 | (LOAAS) Abstract | | The value assigned as the indicator of the high quality or reliability of the statement from a Verifier to a Relying Party (RP) that contains identity information about a Subscriber. Assertions may also contain verified attributes.

5 | LOAAS1 | low assertion level of assurance | Indicator of the low quality or reliability of the statement from a Verifier to a Relying Party (RP) that contains identity information about a Subscriber. Assertions may also contain verified attributes. Assertions and assertion references require protection from modification and reuse attacks. [Summary of the technical requirements specified in NIST SP 800-63 for the four levels of assurance defined by the December 2003, the Office of Management and Budget (OMB) issued Memorandum M-04-04, E-Authentication Guidance for Federal Agencies.]

5 | LOAAS2 | basic assertion level of assurance | Indicator of the basic quality or reliability of the statement from a Verifier to a Relying Party (RP) that contains identity information about a Subscriber. Assertions may also contain verified attributes. Assertions are resistant to disclosure, redirection, capture and substitution attacks. Approved cryptographic techniques are required for all assertion protocols. [Summary of the technical requirements specified in NIST SP 800-63 for the four levels of assurance defined by the December 2003, the Office of Management and Budget (OMB) issued Memorandum M-04-04, E-Authentication Guidance for Federal Agencies.]

5 | LOAAS3 | medium assertion level of assurance | Indicator of the medium quality or reliability of the statement from a Verifier to a Relying Party (RP) that contains identity information about a Subscriber. Assertions may also contain verified attributes. Assertions are protected against repudiation by the verifier. [Summary of the technical requirements specified in NIST SP 800-63 for the four levels of assurance defined by the December 2003, the Office of Management and Budget (OMB) issued Memorandum M-04-04, E-Authentication Guidance for Federal Agencies.]

5 | LOAAS4 | high assertion level of assurance | Indicator of the high quality or reliability of the statement from a Verifier to a Relying Party (RP) that contains identity information about a Subscriber. Assertions may also contain verified attributes. Strongly resistant to man-in-the-middle attacks. "Bearer" assertions are not used. "Holder-of-key" assertions may be used. RP maintains records of the assertions. [Summary of the technical requirements specified in NIST SP 800-63 for the four levels of assurance defined by the December 2003, the Office of Management and Budget (OMB) issued Memorandum M-04-04, E-Authentication Guidance for Federal Agencies.]

4 | (LOACM) Abstract | | Indicator of the digital quality or reliability of the activities performed by the Credential Service Provider (CSP) subsequent to electronic authentication registration, identity proofing and issuance activities to manage and safeguard the integrity of an issued credential and its binding to an identity. [Electronic Authentication Guideline - Recommendations of the National Institute of Standards and Technology, NIST Special Publication 800-63-1, Dec 2011]

5 | LOACM1 | low token and credential management level of assurance | Indicator of the low digital quality or reliability of the activities performed by the Credential Service Provider (CSP) subsequent to electronic authentication registration, identity proofing and issuance activities to manage and safeguard the integrity of an issued credential and its binding to an identity. Little or no confidence that an individual has maintained control over a token that has been entrusted to him or her and that that token has not been compromised. Characteristics include weak identity binding to tokens and plaintext passwords or secrets not transmitted across a network. [Electronic Authentication Guideline - Recommendations of the National Institute of Standards and Technology, NIST Special Publication 800-63-1, Dec 2011]

5 | LOACM2 | basic token and credential management level of assurance | Indicator of the basic digital quality or reliability of the activities performed by the Credential Service Provider (CSP) subsequent to electronic authentication registration, identity proofing and issuance activities to manage and safeguard the integrity of an issued credential and its binding to an identity. Some confidence that an individual has maintained control over a token that has been entrusted to him or her and that that token has not been compromised. Characteristics include: Verification must prove claimant

controls the token; token resists online guessing, replay, session hijacking, and eavesdropping attacks; and token is at least weakly resistant to man-in-the middle attacks. [Electronic Authentication Guideline - Recommendations of the National Institute of Standards and Technology, NIST Special Publication 800-63-1, Dec 2011]

5 | LOACM3 | medium token and credential management level of assurance | Indicator of the medium digital quality or reliability of the activities performed by the Credential Service Provider (CSP) subsequent to electronic authentication registration, identity proofing and issuance activities to manage and safeguard the integrity of an issued credential and itâ€™s binding to an identity. High confidence that an individual has maintained control over a token that has been entrusted to him or her and that that token has not been compromised. Characteristics include: Ownership of token verifiable through security authentication protocol and credential management protects against verifier impersonation attacks. [Electronic Authentication Guideline - Recommendations of the National Institute of Standards and Technology, NIST Special Publication 800-63-1, Dec 2011]

5 | LOACM4 | high token and credential management level of assurance | Indicator of the high digital quality or reliability of the activities performed by the Credential Service Provider (CSP) subsequent to electronic authentication registration, identity proofing and issuance activities to manage and safeguard the integrity of an issued credential and itâ€™s binding to an identity. Very high confidence that an individual has maintained control over a token that has been entrusted to him or her and that that token has not been compromised. Characteristics include: Verifier can prove control of token through a secure protocol; credential management supports strong cryptographic authentication of all communication parties. [Electronic Authentication Guideline - Recommendations of the National Institute of Standards and Technology, NIST Special Publication 800-63-1, Dec 2011]

4 | (LOAID) Abstract | | Indicator of the quality or reliability in the process of ascertaining that an individual is who he or she claims to be.

5 | LOAID1 | low identity proofing level of assurance | Indicator of low digital quality or reliability in the process of ascertaining that an individual is who he or she claims to be. Requires that a continuity of identity be maintained but does not require identity proofing. [Based on Electronic Authentication Guideline - Recommendations of the National Institute of Standards and Technology, NIST Special Publication 800-63-1, Dec 2011]

5 | LOAID2 | basic identity proofing level of assurance | Indicator of some digital quality or reliability in the process of ascertaining that that an individual is who he or she claims to be. Requires identity proofing via presentation of identifying material or information. [Based on Electronic Authentication Guideline - Recommendations of the National Institute of Standards and Technology, NIST Special Publication 800-63-1, Dec 2011]

5 | LOAID3 | medium identity proofing level of assurance | Indicator of high digital quality or reliability in the process of ascertaining that an individual is who he or she claims to be. Requires identity proofing procedures for verification of identifying materials and information. [Based on Electronic Authentication Guideline - Recommendations of the National Institute of Standards and Technology, NIST Special Publication 800-63-1, Dec 2011]

5 | LOAID4 | high identity proofing level of assurance | Indicator of high digital quality or reliability in the process of ascertaining that an individual is who he or she claims to be. Requires identity proofing procedures for verification of identifying materials and information. [Based on Electronic Authentication Guideline - Recommendations of the National Institute of Standards and Technology, NIST Special Publication 800-63-1, Dec 2011]

4 | (LOANR) Abstract | | Indicator of the digital quality or reliability in the process of establishing proof of delivery and proof of origin. [Based on ISO 7498-2]

5 | LOANR1 | low non-repudiation level of assurance | Indicator of low digital quality or reliability in the process of establishing proof of delivery and proof of origin. [Based on ISO 7498-2]

5 | LOANR2 | basic non-repudiation level of assurance | Indicator of basic digital quality or reliability in the process of establishing proof of delivery and proof of origin. [Based on ISO 7498-2]

5 | LOANR3 | medium non-repudiation level of assurance | Indicator of medium digital quality or reliability in the process of establishing proof of delivery and proof of origin. [Based on ISO 7498-2]

5 | LOANR4 | high non-repudiation level of assurance | Indicator of high digital quality or reliability in the process of establishing proof of delivery and proof of origin. [Based on ISO 7498-2]

4 | (LOARA) Abstract | | Indicator of the digital quality or reliability of the information exchange between network-connected devices where the information cannot be reliably protected end-to-end by a single organizationâ€™s security controls. [Based on NIST SP 800-63-2]

5 | LOARA1 | low remote access level of assurance | Indicator of low digital quality or reliability of the information exchange between network-connected devices where the information cannot be reliably protected end-to-end by a single organizationâ€™s security controls. [Based on NIST SP 800-63-2]

5 | LOARA2 | basic remote access level of assurance | Indicator of basic digital quality or reliability of the information exchange between network-connected devices where the information cannot be reliably protected end-to-end by a single organizationâ€™s security controls. [Based on NIST SP 800-63-2]

5 | LOARA3 | medium remote access level of assurance | Indicator of medium digital quality or reliability of the information exchange between network-connected devices where the information cannot be reliably protected end-to-end by a single organizationâ€™s security controls. [Based on NIST SP 800-63-2]

5 | LOARA4 | high remote access level of assurance | Indicator of high digital quality or reliability of the information exchange between network-connected devices where the information cannot be reliably protected end-to-end by a single organization's security controls. [Based on NIST SP 800-63-2]

4 | (LOATK) Abstract | | Indicator of the digital quality or reliability of single and multi-token authentication. [Electronic Authentication Guideline - Recommendations of the National Institute of Standards and Technology, NIST Special Publication 800-63-1, Dec 2011]

5 | LOATK1 | low token level of assurance | Indicator of the low digital quality or reliability of single and multi-token authentication. Permits the use of any of the token methods of Levels 2, 3, or 4. [Electronic Authentication Guideline - Recommendations of the National Institute of Standards and Technology, NIST Special Publication 800-63-1, Dec 2011]

5 | LOATK2 | basic token level of assurance | Indicator of the basic digital quality or reliability of single and multi-token authentication. Requires single factor authentication using memorized secret tokens, pre-registered knowledge tokens, look-up secret tokens, out of band tokens, or single factor one-time password devices. [Electronic Authentication Guideline - Recommendations of the National Institute of Standards and Technology, NIST Special Publication 800-63-1, Dec 2011]

5 | LOATK3 | medium token level of assurance | Indicator of the medium digital quality or reliability of single and multi-token authentication. Requires two authentication factors. Provides multi-factor remote network authentication. Permits multi-factor software cryptographic token. [Electronic Authentication Guideline - Recommendations of the National Institute of Standards and Technology, NIST Special Publication 800-63-1, Dec 2011]

5 | LOATK4 | high token level of assurance | Indicator of the high digital quality or reliability of single and multi-token authentication. Requires token that is a hardware cryptographic module validated at validated at Federal Information Processing Standard (FIPS) 140-2 Level 2 or higher overall with at least FIPS 140-2 Level 3 physical security. Level 4 token requirements can be met by using the PIV authentication key of a FIPS 201 compliant Personal Identity Verification (PIV) Card. [Electronic Authentication Guideline - Recommendations of the National Institute of Standards and Technology, NIST Special Publication 800-63-1, Dec 2011]

3 | TRSTMECOBV | none supplied 6 | Values for security trust mechanism metadata observation made about a security architecture system component that supports enforcement of security policies.

1 | (_SeverityObservation) Abstract | | Potential values for observations of severity.

2 | H | High | Indicates the condition may be life-threatening or has the potential to cause permanent injury.

2 | L | Low | Indicates the condition may result in some adverse consequences but is unlikely to substantially affect the situation of the subject.

2 | M | Moderate | Indicates the condition may result in noticable adverse adverse consequences but is unlikely to be life-threatening or cause permanent injury.

1 | (_SubjectBodyPosition) Abstract | | Contains codes for defining the observed, physical position of a subject, such as during an observation, assessment, collection of a specimen, etc. ECG waveforms and vital signs, such as blood pressure, are two examples where a general, observed position typically needs to be noted.
2 | LLD | left lateral decubitus | Lying on the left side.
2 | PRN | prone | Lying with the front or ventral surface downward; lying face down.
2 | RLD | right lateral decubitus | Lying on the right side.
2 | SFWL | Semi-Fowler's | A semi-sitting position in bed with the head of the bed elevated approximately 45 degrees.
2 | SIT | sitting | Resting the body on the buttocks, typically with upper torso erect or semi erect.
2 | STN | standing | To be stationary, upright, vertical, on one's legs.
2 | SUP | supine
3 | RTRD | reverse trendelenburg | Lying on the back, on an inclined plane, typically about 30-45 degrees with head raised and feet lowered.
3 | TRD | trendelenburg | Lying on the back, on an inclined plane, typically about 30-45 degrees, with head lowered and feet raised.
1 | (_VerificationOutcomeValue) Abstract | | Values for observations of verification act results Examples: Verified, not verified, verified with warning.
2 | ACT | active coverage | Definition: Coverage is in effect for healthcare service(s) and/or product(s).
2 | ACTPEND | active - pending investigation | Definition: Coverage is in effect for healthcare service(s) and/or product(s) - Pending Investigation
2 | ELG | eligible | Definition: Coverage is in effect for healthcare service(s) and/or product(s).
2 | INACT | inactive | Definition: Coverage is not in effect for healthcare service(s) and/or product(s).
2 | INPNDINV | inactive - pending investigation | Definition: Coverage is not in effect for healthcare service(s) and/or product(s) - Pending Investigation.
2 | INPNDUPD | inactive - pending eligibility update | Definition: Coverage is not in effect for healthcare service(s) and/or product(s) - Pending Eligibility Update.
2 | NELG | not eligible | Definition: Coverage is not in effect for healthcare service(s) and/or product(s). May optionally include reasons for the ineligibility.
1 | (_AnnotationValue) Abstract
1 | (_CommonClinicalObservationValue) Abstract | | Description:Used in a patient care message to value simple clinical (non-lab) observations.
1 | (_IndividualCaseSafetyReportValueDomains) Abstract | | This domain is established as a parent to a variety of value domains being defined to support the communication of Individual Case Safety Reports to regulatory bodies. Arguably, this aggregation is not taxonomically pure, but the grouping will facilitate the management of these domains.
1 | (_IndicationValue) Abstract | | Indicates the specific observation result which is the reason for the action (prescription, lab test, etc.). E.g. Headache, Ear infection, planned diagnostic image (requiring contrast agent), etc.

4.3.2.1064 HL7 v3 Code System ParticipationMode

URL: https://hl7.org/fhir/STU3/v3/ParticipationMode/cs.html

This page is part of the FHIR Specification (v3.0.2: STU 3). The current version which supercedes this version is 4.0.1. For a full list of available versions, see the Directory of published versions

Vocabulary Work Group | Maturity Level: N/A | External | Use Context: Any

This code system (http://hl7.org/fhir/v3/ParticipationMode) is defined as part of HL7 v3.

Summary

Defining URL: | http://hl7.org/fhir/v3/ParticipationMode
Name: | v3 Code System ParticipationMode
Definition: | A set of codes specifying the modality by which the Entity playing the Role is participating in the Act. Examples: Physically present, over the telephone, written communication. Rationale: Particularly for author (originator) participants this is used to specify whether the information represented by the act was initially provided verbally, (hand-)written, or electronically. Open Issue: There needs to be a reexamination of the hierarchies as there seems to be some muddling between ELECTRONIC and other concepts that involve electronic communication that are in other hierarchies.
OID: | 2.16.840.1.113883.5.1064 (for OID based terminology systems)
Source Resource | XML / JSON

This Code system is used in the following value sets:

* v3 Code System ParticipationMode (A set of codes specifying the modality by which the Entity playing the Role is participating in the Act. Examples: Physically present, over the telephone, written communication. Rationale: Particularly for author (originator) participants this is used to specify whether the information represented by the act was initially provided verbally, (hand-)written, or electronically. Open Issue: There needs to be a reexamination of the hierarchies as there seems to be some muddling between ELECTRONIC and other concepts that involve electronic communication that are in other hierarchies.)

4.3.2.1064.1 Code System Content

Release Date: 2016-11-11

Level | Code | Display | Definition
1 | ELECTRONIC | electronic data | Participation by non-human-languaged based electronic signal
1 | PHYSICAL | physical presence | Participation by direct action where subject and actor are in the same location. (The participation involves more than communication.)
1 | REMOTE | remote presence | Participation by direct action where subject and actor are in separate locations, and the actions of the actor are transmitted by electronic or mechanical means. (The participation involves more than communication.)
1 | VERBAL | verbal | Participation by voice communication
2 | DICTATE | dictated | Participation by pre-recorded voice. Communication is limited to one direction (from the recorder to recipient).
2 | FACE | face-to-face | Participation by voice communication where parties speak to each other directly.
2 | PHONE | telephone | Participation by voice communication where the voices of the communicating parties are transported over an electronic medium

2 | VIDEOCONF | videoconferencing | Participation by voice and visual communication where the voices and images of the communicating parties are transported over an electronic medium
1 | WRITTEN | written | Participation by human language recorded on a physical material
2 | FAXWRIT | telefax | Participation by text or diagrams printed on paper that have been transmitted over a fax device
2 | HANDWRIT | handwritten | Participation by text or diagrams printed on paper or other recording medium
2 | MAILWRIT | mail | Participation by text or diagrams printed on paper transmitted physically (e.g. by courier service, postal service).
2 | ONLINEWRIT | online written | Participation by text or diagrams submitted by computer network, e.g. online survey.
3 | EMAILWRIT | email | Participation by text or diagrams transmitted over an electronic mail system.
2 | TYPEWRIT | typewritten | Participation by text or diagrams printed on paper or other recording medium where the recording was performed using a typewriter, typesetter, computer or similar mechanism.

4.3.2.1067 HL7 v3 Code System QueryResponse

URL: https://hl7.org/fhir/STU3/v3/QueryResponse/cs.html

This page is part of the FHIR Specification (v3.0.2: STU 3). The current version which supercedes this version is 4.0.1. For a full list of available versions, see the Directory of published versions

Vocabulary Work Group | Maturity Level: N/A | External | Use Context: Any

This code system (http://hl7.org/fhir/v3/QueryResponse) is defined as part of HL7 v3.

Summary

Defining URL: | http://hl7.org/fhir/v3/QueryResponse
Name: | v3 Code System QueryResponse
Definition: | A code classifying the general nature of the response to a given query. Includes whether or not data was found, or whether an error occurred.
OID: | 2.16.840.1.113883.5.1067 (for OID based terminology systems)
Source Resource | XML / JSON

This Code system is used in the following value sets:

* v3 Code System QueryResponse (A code classifying the general nature of the response to a given query. Includes whether or not data was found, or whether an error occurred.)

4.3.2.1067.1 Code System Content

Release Date: 2016-11-11

Level | Code | Display | Definition
1 | AE | ApplicationError | Query Error. Application Error.
1 | NF | No data found | No errors, but no data was found matching the query request specification.
1 | OK | Data found | Query reponse data found for 1 or more result sets matching the query request specification.
1 | QE | QueryParameterError | QueryError. Problem with input ParmetersError

4.3.2.1068 HL7 v3 Code System RoleStatus

URL: https://hl7.org/fhir/STU3/v3/RoleStatus/cs.html

This page is part of the FHIR Specification (v3.0.2: STU 3). The current version which supercedes this version is 4.0.1. For a full list of available versions, see the Directory of published versions

Vocabulary Work Group | Maturity Level: N/A | External | Use Context: Any

This code system (http://hl7.org/fhir/v3/RoleStatus) is defined as part of HL7 v3.

Summary

Defining URL: | http://hl7.org/fhir/v3/RoleStatus
Name: | v3 Code System RoleStatus
Definition: | Codes representing the defined possible states of an Role, as defined by the Role class state machine.
OID: | 2.16.840.1.113883.5.1068 (for OID based terminology systems)
Source Resource | XML / JSON

This Code system is used in the following value sets:

* v3 Code System RoleStatus (Codes representing the defined possible states of an Role, as defined by the Role class state machine.)

4.3.2.1068.1 Code System Content

Release Date: 2016-11-11

Level | Code | Display | Definition
1 | normal | normal | The 'typical' state. Excludes "nullified" which represents the termination state of a Role instance that was created in error.
2 | active | active | The state representing the fact that the Entity is currently active in the Role.
2 | cancelled | cancelled | The terminal state resulting from cancellation of the role prior to activation.
2 | pending | pending | The state representing that fact that the role has not yet become active.
2 | suspended | suspended | The state that represents a suspension of the Entity playing the Role. This state is arrived at from the "active" state.
2 | terminated | terminated | The state representing the successful termination of the Role.
1 | nullified | nullified | The state representing the termination of a Role instance that was created in error.

4.3.2.1069 HL7 v3 Code System SetOperator

URL: https://hl7.org/fhir/STU3/v3/SetOperator/cs.html

This page is part of the FHIR Specification (v3.0.2: STU 3). The current version which supercedes this version is 4.0.1. For a full list of available versions, see the Directory of published versions

Vocabulary Work Group | Maturity Level: N/A | External | Use Context: Any

This code system (http://hl7.org/fhir/v3/SetOperator) is defined as part of HL7 v3.

Summary

Defining URL: | http://hl7.org/fhir/v3/SetOperator
Name: | v3 Code System SetOperator
Definition: | **** MISSING DEFINITIONS ****
OID: | 2.16.840.1.113883.5.1069 (for OID based terminology systems)
Source Resource | XML / JSON

This Code system is used in the following value sets:

* v3 Code System SetOperator (**** MISSING DEFINITIONS ****)

4.3.2.1069.1 Code System Content

Release Date: 2016-11-11

Level | Code | Display | Definition
1 | (_ValueSetOperator) Abstract | | Operations that can be used to associate concepts in a terminology.
2 | E | exclude | Form the set-difference with this value, i.e., exclude this element or set from the resulting set.
2 | I | include | Form the union with this value, i.e., include this element or set in the resulting set.
1 | A | intersect | Form the intersection with the value.
1 | H | convex hull | Form the convex hull with the value. The convex hull is defined over ordered domains and is the smallest contiguous superset (interval) that of all the operand sets.
1 | P | periodic hull | Form the periodic hull with the value. The periodic hull is defined over ordered domains and is the periodic set that contains all contiguous supersets of pairs of intervals generated by the operand periodic intervals.

4.3.2.1070 HL7 v3 Code System substanceAdminSubstitution

URL: https://hl7.org/fhir/STU3/v3/substanceAdminSubstitution/cs.html

This page is part of the FHIR Specification (v3.0.2: STU 3). The current version which supercedes this version is 4.0.1. For a full list of available versions, see the Directory of published versions

Vocabulary Work Group | Maturity Level: N/A | External | Use Context: Any

This code system (http://hl7.org/fhir/v3/substanceAdminSubstitution) is defined as part of HL7 v3.

Summary

Defining URL: | http://hl7.org/fhir/v3/substanceAdminSubstitution
Name: | v3 Code System substanceAdminSubstitution
Definition: | Identifies what sort of change is permitted or has occurred between the therapy that was ordered and the therapy that was/will be provided.
OID: | 2.16.840.1.113883.5.1070 (for OID based terminology systems)
Source Resource | XML / JSON

This Code system is used in the following value sets:

* v3 Code System substanceAdminSubstitution (Identifies what sort of change is permitted or has occurred between the therapy that was ordered and the therapy that was/will be provided.)

* ActSubstanceAdminSubstitutionCode (No Description Provided)

4.3.2.1070.1 Code System Content

Release Date: 2016-11-11

Level | Code | Display | Definition
1 | (_ActSubstanceAdminSubstitutionCode) Abstract | | Description: Substitution occurred or is permitted with another product that may potentially have different ingredients, but having the same biological and therapeutic effects.
2 | E | equivalent | Description: Substitution occurred or is permitted with another bioequivalent and therapeutically equivalent product.
3 | EC | equivalent composition | Description: Substitution occurred or is permitted with another product that is a: pharmaceutical alternative containing the same active ingredient but is formulated with different salt, ester pharmaceutical equivalent that has the same active ingredient, strength, dosage form and route of administration Examples: Pharmaceutical alternative: Erythromycin Ethylsuccinate for Erythromycin Stearate Pharmaceutical equivalent: Lisonpril for Zestril
4 | BC | brand composition | Description: Substitution occurred or is permitted between equivalent Brands but not Generics Examples: Zestril for Prinivil Coumadin for Jantoven
4 | G | generic composition | Description: Substitution occurred or is permitted between equivalent Generics but not Brands Examples: Lisnopril (Lupin Corp) for Lisnopril (Wockhardt Corp)
3 | TE | therapeutic alternative | Description: Substitution occurred or is permitted with another product having the same therapeutic objective and safety profile. Examples: ranitidine for Tagamet
4 | TB | therapeutic brand | Description: Substitution occurred or is permitted between therapeutically equivalent Brands but not Generics > Examples: Zantac for Tagamet

4 | TG | therapeutic generic | Description: Substitution occurred or is permitted between therapeutically equivalent Generics but not Brands > Examples: Ranitidine for cimetidine
2 | F | formulary | Description: This substitution was performed or is permitted based on formulary guidelines.
2 | N | none | No substitution occurred or is permitted.

4.3.2.1071 HL7 v3 Code System SubstitutionCondition

URL: https://hl7.org/fhir/STU3/v3/SubstitutionCondition/cs.html

This page is part of the FHIR Specification (v3.0.2: STU 3). The current version which supercedes this version is 4.0.1. For a full list of available versions, see the Directory of published versions

Vocabulary Work Group | Maturity Level: N/A | External | Use Context: Any

This code system (http://hl7.org/fhir/v3/SubstitutionCondition) is defined as part of HL7 v3.

Summary

Defining URL: | http://hl7.org/fhir/v3/SubstitutionCondition
Name: | v3 Code System SubstitutionCondition
Definition: | Identifies what sort of change is permitted or has occurred between the item that was ordered/requested and the one that was/will be provided.
OID: | 2.16.840.1.113883.5.1071 (for OID based terminology systems)
Source Resource | XML / JSON

This Code system is used in the following value sets:

* v3 Code System SubstitutionCondition (Identifies what sort of change is permitted or has occurred between the item that was ordered/requested and the one that was/will be provided.)

4.3.2.1071.1 Code System Content

Release Date: 2016-11-11

Level | Code | Display | Definition
1 | (_Conditional) Abstract | | Some conditions may be attached to an allowable substitution. An allowable substitution is based on a match to any other attributes that may be specified.
2 | CONFIRM | Confirm first | Confirmation with Contact Person prior to making any substitutions has or will occur.
2 | NOTIFY | Notify first | Notification to the Contact Person, prior to substitution and through normal institutional procedures, has or will be made.
1 | NOSUB | No substitution | Substitution is not permitted.
1 | UNCOND | Unconditional | No conditions are required.

4.3.2.1074 HL7 v3 Code System CodingRationale

URL: https://hl7.org/fhir/STU3/v3/CodingRationale/cs.html

This page is part of the FHIR Specification (v3.0.2: STU 3). The current version which supercedes this version is 4.0.1. For a full list of available versions, see the Directory of published versions

Vocabulary Work Group | Maturity Level: N/A | External | Use Context: Any

This code system (http://hl7.org/fhir/v3/CodingRationale) is defined as part of HL7 v3.

Summary

Defining URL: | http://hl7.org/fhir/v3/CodingRationale
Name: | v3 Code System CodingRationale
Definition: | Identifies how to interpret the instance of the code, codeSystem value in a set of translations. Since HL7 (or a government body) may mandate that codes from certain code systems be sent in conformant messages, other synonyms that are sent in the translation set need to be distinguished among the originally captured source, the HL7 specified code, or some future role. When this code is NULL, it indicates that the translation is an undefined type. When valued, this property must contain one of the following values: SRC - Source (or original) code HL7 - HL7 Specified or Mandated SH - both HL7 mandated and the original code (precoordination) There may be additional values added to this value set as we work through the use of codes in messages and determine other Use Cases requiring special interpretation of the translations.
OID: | 2.16.840.1.113883.5.1074 (for OID based terminology systems)
Source Resource | XML / JSON

This Code system is used in the following value sets:

* v3 Code System CodingRationale (Identifies how to interpret the instance of the code, codeSystem value in a set of translations. Since HL7 (or a government body) may mandate that codes from certain code systems be sent in conformant messages, other synonyms that are sent in the translation set need to be distinguished among the originally captured source, the HL7 specified code, or some future role. When this code is NULL, it indicates that the translation is an undefined type. When valued, this property must contain one of the following values: SRC - Source (or original) code HL7 - HL7 Specified or Mandated SH - both HL7 mandated and the original code (precoordination) There may be additional values added to this value set as we work through the use of codes in messages and determine other Use Cases requiring special interpretation of the translations.)

4.3.2.1074.1 Code System Content

Release Date: 2016-11-11

Level | Code | Display | Definition
1 | O | originally produced code | Description: Originally produced code.

1 | OR | original and required | Originally produced code, required by the specification describing the use of the coded concept.
1 | P | post-coded | Description: Post-coded from free text source</description>
1 | PR | post-coded and required | Post-coded from free text source, required by the specification describing the use of the coded concept.
1 | R | required | Description: Required standard code for HL7.
1 | HL7 | HL7 Specified or Mandated | HL7 Specified or Mandated
1 | SH | Both HL7 mandated and the original code | Both HL7 mandated and the original code (precoordination)
1 | SRC | Source (or original) code | Source (or original) code

4.3.2.1075 HL7 v3 Code System PatientImportance

URL: https://hl7.org/fhir/STU3/v3/PatientImportance/cs.html

This page is part of the FHIR Specification (v3.0.2: STU 3). The current version which supercedes this version is 4.0.1. For a full list of available versions, see the Directory of published versions

Vocabulary Work Group | Maturity Level: N/A | External | Use Context: Any

This code system (http://hl7.org/fhir/v3/PatientImportance) is defined as part of HL7 v3.

Summary

Defining URL: | http://hl7.org/fhir/v3/PatientImportance
Name: | v3 Code System PatientImportance
Definition: | Patient VIP code
OID: | 2.16.840.1.113883.5.1075 (for OID based terminology systems)
Source Resource | XML / JSON

This Code system is used in the following value sets:

* v3 Code System PatientImportance (Patient VIP code)

4.3.2.1075.1 Code System Content

Release Date: 2016-11-11

Level | Code | Display | Definition
1 | BM | Board Member | Board member of health care organization
1 | DFM | Physician Family Member | Family member of staff physician
1 | DR | Staff Physician | Member of the health care organization physician staff
1 | FD | Financial Donor | Financial donor to the health care organization
1 | FOR | Foreign Dignitary | Foreign citizen dignitary of interest to the health care organization
1 | GOVT | Government Dignitary | Government dignitary of interest to the organization
1 | SFM | Staff Family Member | Family member of staff member
1 | STF | Staff Member | Staff member of the health care organization
1 | VIP | Very Important Person | Very important person of interest to the health care organization

4.3.2.1076 HL7 v3 Code System ReligiousAffiliation

URL: https://hl7.org/fhir/STU3/v3/ReligiousAffiliation/cs.html

This page is part of the FHIR Specification (v3.0.2: STU 3). The current version which supercedes this version is 4.0.1. For a full list of available versions, see the Directory of published versions

Vocabulary Work Group | Maturity Level: N/A | External | Use Context: Any

This code system (http://hl7.org/fhir/v3/ReligiousAffiliation) is defined as part of HL7 v3.

Summary

Defining URL: | http://hl7.org/fhir/v3/ReligiousAffiliation
Name: | v3 Code System ReligiousAffiliation
Definition: | Assigment of spiritual faith affiliation
OID: | 2.16.840.1.113883.5.1076 (for OID based terminology systems)
Source Resource | XML / JSON

This Code system is used in the following value sets:

* v3 Code System ReligiousAffiliation (Assigment of spiritual faith affiliation)

4.3.2.1076.1 Code System Content

Release Date: 2016-11-11

Level | Code | Display | Definition
1 | 1001 | Adventist
1 | 1002 | African Religions
1 | 1003 | Afro-Caribbean Religions
1 | 1004 | Agnosticism
1 | 1005 | Anglican
1 | 1006 | Animism
1 | 1007 | Atheism
1 | 1008 | Babi & Baha'I faiths
1 | 1009 | Baptist

1 | 1010 | Bon
1 | 1011 | Cao Dai
1 | 1012 | Celticism
1 | 1013 | Christian (non-Catholic, non-specific)
1 | 1014 | Confucianism
1 | 1015 | Cyberculture Religions
1 | 1016 | Divination
1 | 1017 | Fourth Way
1 | 1018 | Free Daism
1 | 1019 | Gnosis
1 | 1020 | Hinduism
1 | 1021 | Humanism
1 | 1022 | Independent
1 | 1023 | Islam
1 | 1024 | Jainism
1 | 1025 | Jehovah's Witnesses
1 | 1026 | Judaism
1 | 1027 | Latter Day Saints
1 | 1028 | Lutheran
1 | 1029 | Mahayana
1 | 1030 | Meditation
1 | 1031 | Messianic Judaism
1 | 1032 | Mitraism
1 | 1033 | New Age
1 | 1034 | non-Roman Catholic
1 | 1035 | Occult
1 | 1036 | Orthodox
1 | 1037 | Paganism
1 | 1038 | Pentecostal
1 | 1039 | Process, The
1 | 1040 | Reformed/Presbyterian
1 | 1041 | Roman Catholic Church
1 | 1042 | Satanism
1 | 1043 | Scientology
1 | 1044 | Shamanism
1 | 1045 | Shiite (Islam)
1 | 1046 | Shinto
1 | 1047 | Sikism
1 | 1048 | Spiritualism
1 | 1049 | Sunni (Islam)
1 | 1050 | Taoism
1 | 1051 | Theravada
1 | 1052 | Unitarian-Universalism
1 | 1053 | Universal Life Church
1 | 1054 | Vajrayana (Tibetan)
1 | 1055 | Veda
1 | 1056 | Voodoo
1 | 1057 | Wicca
1 | 1058 | Yaohushua
1 | 1059 | Zen Buddhism
1 | 1060 | Zoroastrianism
1 | 1061 | Assembly of God
1 | 1062 | Brethren
1 | 1063 | Christian Scientist
1 | 1064 | Church of Christ
1 | 1065 | Church of God
1 | 1066 | Congregational
1 | 1067 | Disciples of Christ
1 | 1068 | Eastern Orthodox
1 | 1069 | Episcopalian
1 | 1070 | Evangelical Covenant
1 | 1071 | Friends
1 | 1072 | Full Gospel
1 | 1073 | Methodist
1 | 1074 | Native American
1 | 1075 | Nazarene
1 | 1076 | Presbyterian
1 | 1077 | Protestant
1 | 1078 | Protestant, No Denomination
1 | 1079 | Reformed
1 | 1080 | Salvation Army
1 | 1081 | Unitarian Universalist

1 | 1082 | United Church of Christ

4.3.2.1077 HL7 v3 Code System EducationLevel

URL: https://hl7.org/fhir/STU3/v3/EducationLevel/cs.html

This page is part of the FHIR Specification (v3.0.2: STU 3). The current version which supercedes this version is 4.0.1. For a full list of available versions, see the Directory of published versions

Vocabulary Work Group | Maturity Level: N/A | External | Use Context: Any

This code system (http://hl7.org/fhir/v3/EducationLevel) is defined as part of HL7 v3.

Summary

Defining URL: | http://hl7.org/fhir/v3/EducationLevel
Name: | v3 Code System EducationLevel
Definition: | Years of education that a person has completed
OID: | 2.16.840.1.113883.5.1077 (for OID based terminology systems)
Source Resource | XML / JSON

This Code system is used in the following value sets:

* v3 Code System EducationLevel (Years of education that a person has completed)

4.3.2.1077.1 Code System Content

Release Date: 2016-11-11

Level | Code | Display | Definition
1 | ASSOC | Associate's or technical degree complete | Associate's or technical degree complete
1 | BD | College or baccalaureate degree complete | College or baccalaureate degree complete
1 | ELEM | Elementary School | Elementary School
1 | GD | Graduate or professional Degree complete | Graduate or professional Degree complete
1 | HS | High School or secondary school degree complete | High School or secondary school degree complete
1 | PB | Some post-baccalaureate education | Some post-baccalaureate education
1 | POSTG | Doctoral or post graduate education | Doctoral or post graduate education
1 | SCOL | Some College education | Some College education
1 | SEC | Some secondary or high school education | Some secondary or high school education

4.3.2.1082 HL7 v3 Code System AcknowledgementDetailType

URL: https://hl7.org/fhir/STU3/v3/AcknowledgementDetailType/cs.html

This page is part of the FHIR Specification (v3.0.2: STU 3). The current version which supercedes this version is 4.0.1. For a full list of available versions, see the Directory of published versions

Vocabulary Work Group | Maturity Level: N/A | External | Use Context: Any

This code system (http://hl7.org/fhir/v3/AcknowledgementDetailType) is defined as part of HL7 v3.

Summary

Defining URL: | http://hl7.org/fhir/v3/AcknowledgementDetailType
Name: | v3 Code System AcknowledgementDetailType
Definition: | A code identifying the specific message to be provided. Discussion: A textual value may be specified as the print name, or for non-coded messages, as the original text. Examples: 'Required attribute xxx is missing', 'System will be unavailable March 19 from 0100 to 0300'
OID: | 2.16.840.1.113883.5.1082 (for OID based terminology systems)
Source Resource | XML / JSON

This Code system is used in the following value sets:

* v3 Code System AcknowledgementDetailType (A code identifying the specific message to be provided. Discussion: A textual value may be specified as the print name, or for non-coded messages, as the original text. Examples: 'Required attribute xxx is missing', 'System will be unavailable March 19 from 0100 to 0300')

4.3.2.1082.1 Code System Content

Release Date: 2016-11-11

Level | Code | Display | Definition
1 | E | Error | Definition:An issue which has prevented, or will prevent (unless a management is provided for the issue by the sender), the successful processing of an interaction. Response interactions which include an issue which is an Error are a 'rejection', indicating that the request was not successfully processed. Example:Unable to find specified patient.
1 | I | Information | Definition: The message relates to an issue which has no bearing on the successful processing of the request. Information issues cannot be overridden by specifying a management. Example: A Patient's coverage will expire in 5 days.
1 | W | Warning | Definition: The message relates to an issue which cannot prevent the successful processing of a request, but which could result in the processing not having the ideal or intended effect. Managing a warning issue is not required for successful processing, but will suppress the warning from being raised. Example: Unexpected additional repetitions of phone number have been ignored.
1 | ERR
1 | INFO
1 | WARN

4.3.2.1083 HL7 v3 Code System MessageWaitingPriority

URL: https://hl7.org/fhir/STU3/v3/MessageWaitingPriority/cs.html

This page is part of the FHIR Specification (v3.0.2: STU 3). The current version which supercedes this version is 4.0.1. For a full list of available versions, see the Directory of published versions

Vocabulary Work Group | Maturity Level: N/A | External | Use Context: Any

This code system (http://hl7.org/fhir/v3/MessageWaitingPriority) is defined as part of HL7 v3.

Summary

Defining URL: | http://hl7.org/fhir/v3/MessageWaitingPriority
Name: | v3 Code System MessageWaitingPriority
Definition: | Indicates that the receiver has messages for the sender OpenIssue: Description does not make sense relative to name of coding system. Must be reviewed and improved.
OID: | 2.16.840.1.113883.5.1083 (for OID based terminology systems)
Source Resource | XML / JSON

This Code system is used in the following value sets:

* v3 Code System MessageWaitingPriority (Indicates that the receiver has messages for the sender OpenIssue: Description does not make sense relative to name of coding system. Must be reviewed and improved.)

4.3.2.1083.1 Code System Content

Release Date: 2016-11-11

Level | Code | Display | Definition
1 | H | High | High priority messages are available
1 | L | Low | Low priority messages are available
1 | M | Medium | Medium priority messages are available

4.3.2.1096 HL7 v3 Code System QueryParameterValue

URL: https://hl7.org/fhir/STU3/v3/QueryParameterValue/cs.html

This page is part of the FHIR Specification (v3.0.2: STU 3). The current version which supercedes this version is 4.0.1. For a full list of available versions, see the Directory of published versions

Vocabulary Work Group | Maturity Level: N/A | External | Use Context: Any

This code system (http://hl7.org/fhir/v3/QueryParameterValue) is defined as part of HL7 v3.

Summary

Defining URL: | http://hl7.org/fhir/v3/QueryParameterValue
Name: | v3 Code System QueryParameterValue
Definition: | The domain of coded values used as parameters within QueryByParameter queries.
OID: | 2.16.840.1.113883.5.1096 (for OID based terminology systems)
Source Resource | XML / JSON

This Code system is used in the following value sets:

* v3 Code System QueryParameterValue (The domain of coded values used as parameters within QueryByParameter queries.)

4.3.2.1096.1 Code System Content

Release Date: 2016-11-11

Level | Code | Display | Definition
1 | (_DispenseQueryFilterCode) Abstract | | Description:Filter codes used to manage volume of dispenses returned by a parameter-based queries.
2 | ALLDISP | all dispenses | Description:Returns all dispenses to date for a prescription.
2 | LASTDISP | last dispense | Description:Returns the most recent dispense for a prescription.
2 | NODISP | no dispense | Description:Returns no dispense for a prescription.
1 | (_OrderFilterCode) Abstract | | Filter codes used to manage types of orders being returned by a parameter-based query.
2 | AO | all orders | Return all orders.
2 | ONR | orders without results | Return only those orders that do not have results.
2 | OWR | orders with results | Return only those orders that have results.
1 | (_PrescriptionDispenseFilterCode) Abstract | | A "helper" vocabulary used to construct complex query filters based on how and whether a prescription has been dispensed.
2 | C | Completely dispensed | Filter to only include SubstanceAdministration orders which have no remaining quantity authorized to be dispensed.
2 | N | Never Dispensed | Filter to only include SubstanceAdministration orders which have no fulfilling supply events performed.
2 | R | Dispensed with remaining fills | Filter to only include SubstanceAdministration orders which have had at least one fulfilling supply event, but which still have outstanding quantity remaining to be authorized.
1 | (_QueryParameterValue) Abstract | | Description:Indicates how result sets should be filtered based on whether they have associated issues.
2 | ISSFA | all | Description:Result set should not be filtered based on the presence of issues.
2 | ISSFI | with issues | Description:Result set should be filtered to only include records with associated issues.
2 | ISSFU | with unmanaged issues | Description:Result set should be filtered to only include records with associated unmanaged issues.

4.3.2.1099 HL7 v3 Code System ActRelationshipSubset

URL: https://hl7.org/fhir/STU3/v3/ActRelationshipSubset/cs.html

This page is part of the FHIR Specification (v3.0.2: STU 3). The current version which supercedes this version is 4.0.1. For a full list of available versions, see the Directory of published versions

Vocabulary Work Group | Maturity Level: N/A | External | Use Context: Any

This code system (http://hl7.org/fhir/v3/ActRelationshipSubset) is defined as part of HL7 v3.

Summary

Defining URL: | http://hl7.org/fhir/v3/ActRelationshipSubset
Name: | v3 Code System ActRelationshipSubset
Definition: | <ns1:p>Used to indicate that the target of the relationship will be a filtered subset of the total related set of targets.</ns1:p><ns1:p>Used when there is a need to limit the number of components to the first, the last, the next, the total, the average or some other filtered or calculated subset.</ns1:p>
OID: | 2.16.840.1.113883.5.1099 (for OID based terminology systems)
Source Resource | XML / JSON

This Code system is used in the following value sets:

* v3 Code System ActRelationshipSubset (<ns1:p>Used to indicate that the target of the relationship will be a filtered subset of the total related set of targets.</ns1:p><ns1:p>Used when there is a need to limit the number of components to the first, the last, the next, the total, the average or some other filtered or calculated subset.</ns1:p>)

4.3.2.1099.1 Code System Content

Release Date: 2016-11-11

Level | Code | Display | Definition
1 | (_ParticipationSubset) Abstract | | Used to indicate that the participation is a filtered subset of the total participations of the same type owned by the Act. Used when there is a need to limit the participations to the first, the last, the next or some other filtered subset.
2 | FUTURE | expected future | An occurrence that is scheduled to occur in the future. An Act whose effective time is greater than 'now', where 'now' is the time the instance is authored.
3 | FUTSUM | future summary | Represents a 'summary' of all acts that are scheduled to occur in the future (whose effective time is greater than 'now' where is the time the instance is authored.). The effectiveTime represents the outer boundary of all occurrences, repeatNumber represents the total number of repetitions, etc.
3 | LAST | expected last | Restricted to the latest known occurrence that is scheduled to occur. The Act with the highest known effective time.
3 | NEXT | expected next | Restricted to the nearest recent known occurrence scheduled to occur in the future. The Act with the lowest effective time, still greater than 'now'. ('now' is the time the instance is authored.)
2 | PAST | previous | An occurrence that occurred or was scheduled to occur in the past. An Act whose effective time is less than 'now'. ('now' is the time the instance is authored.)
3 | FIRST | first known | Restricted to the earliest known occurrence that occurred or was scheduled to occur in the past. The Act with the lowest effective time. ('now' is the time the instance is authored.)
3 | PREVSUM | previous summary | Represents a 'summary' of all acts that previously occurred or were scheduled to occur. The effectiveTime represents the outer boundary of all occurrences, repeatNumber represents the total number of repetitions, etc. ('now' is the time the instance is authored.)
3 | RECENT | most recent | Restricted to the most recent known occurrence that occurred or was scheduled to occur in the past. The Act with the most recent effective time, still less than 'now'. ('now' is the time the instance is authored.)
2 | SUM | summary | Represents a 'summary' of all acts that have occurred or were scheduled to occur and which are scheduled to occur in the future. The effectiveTime represents the outer boundary of all occurrences, repeatNumber represents the total number of repetitions, etc.
1 | ActRelationshipExpectedSubset | ActRelationshipExpectedSubset
1 | ActRelationshipPastSubset | ActRelationshipPastSubset
1 | MAX | maximum | The occurrence whose value attribute is greater than all other occurrences at the time the instance is created.
1 | MIN | minimum | The occurrence whose value attribute is less than all other occurrences at the time the instance is created.

4.3.2.1100 HL7 v3 Code System AcknowledgementDetailCode

URL: https://hl7.org/fhir/STU3/v3/AcknowledgementDetailCode/cs.html

This page is part of the FHIR Specification (v3.0.2: STU 3). The current version which supercedes this version is 4.0.1. For a full list of available versions, see the Directory of published versions

Vocabulary Work Group | Maturity Level: N/A | External | Use Context: Any

This code system (http://hl7.org/fhir/v3/AcknowledgementDetailCode) is defined as part of HL7 v3.

Summary

Defining URL: | http://hl7.org/fhir/v3/AcknowledgementDetailCode
Name: | v3 Code System AcknowledgementDetailCode
Definition: | OpenIssue: Missing description.
OID: | 2.16.840.1.113883.5.1100 (for OID based terminology systems)
Source Resource | XML / JSON

This Code system is used in the following value sets:

* v3 Code System AcknowledgementDetailCode (OpenIssue: Missing description.)

4.3.2.1100.1 Code System Content

Release Date: 2016-11-11

Level | Code | Display | Definition
1 | (_AcknowledgementDetailNotSupportedCode) Abstract | | Refelects rejections because elements of the communication are not supported in the current context.
2 | NS200 | Unsupported interaction | The interaction (or: this version of the interaction) is not supported.
2 | NS202 | Unsupported processing id | The Processing ID is not supported.
2 | NS203 | Unsupported version id | The Version ID is not supported.
2 | NS250 | Unsupported processing Mode | The processing mode is not supported.
2 | NS260 | Unknown sender | The Device.id of the sender is unknown.
2 | NS261 | Unrecognized attentionline | The receiver requires information in the attentionLine classes for routing purposes.
1 | INTERR | Internal system error | An internal software component (database, application, queue mechanism, etc.) has failed, leading to inability to process the message.
1 | NOSTORE | No storage space for message. | Rejection: The message can't be stored by the receiver due to an unspecified internal application issue. The message was neither processed nor stored by the receiving application.
1 | RTEDEST | Message routing error, destination unreachable. | Error: The destination of this message is known to the receiving application. Messages have been successfully routed to that destination in the past. The link to the destination application or an intermediate application is unavailable.
1 | RTUDEST | Error: Message routing error, unknown destination. | The destination of this message is unknown to the receiving application. The receiving application in the message does not match the application which received the message. The message was neither routed, processed nor stored by the receiving application.
1 | RTWDEST | Message routing warning, destination unreachable. | Warning: The destination of this message is known to the receiving application. Messages have been successfully routed to that destination in the past. The link to the destination application or an intermediate application is (temporarily) unavailable. The receiving application will forward the message as soon as the destination can be reached again.
1 | SYN | Syntax error | Reflects errors in the syntax or structure of the communication.
2 | SYN102 | Data type error | The attribute contained data of the wrong data type, e.g. a numeric attribute contained "FOO".
2 | SYN105 | Required element missing | Description: Required association or attribute missing in message; or the sequence of the classes is different than required by the standard or one of the conformance profiles identified in the message.
3 | SYN100 | Required association missing | Required association missing in message; or the sequence of the classes is different than required by the standard or one of the conformance profiles identified in the message.
3 | SYN101 | Required attribute missing | A required attribute is missing in a class.
3 | SYN114 | Insufficient repetitions | Description: The number of repetitions of a group of association or attributes is less than the required minimum for the standard or of one of the conformance profiles or templates identified in the message.
2 | SYN106 | Terminology error | Description: A coded attribute or datatype property violates one of the terminology constraints specified in the standard or one of the conformance profiles or templates declared by the instance.
3 | SYN103 | Value not found in code system | An attribute value was compared against the corresponding code system, and no match was found.
3 | SYN104 | Invalid code system in CNE | An attribute value referenced a code system that is not valid for an attribute constrained to CNE.
3 | SYN107 | Deprecated code | Description: A coded attribute is referencing a code that has been deprecated by the owning code system.
2 | SYN108 | Number of repetitions exceeds limit | Description: The number of repetitions of a (group of) association(s) or attribute(s) exceeds the limits of the standard or of one of the conformance profiles or templates identified in the message.
3 | SYN110 | Number of association repetitions exceeds limit | The number of repetitions of a (group of) association(s) exceeds the limits of the standard or of one of the conformance profiles identified in the message.
3 | SYN112 | Number of attribute repetitions exceeds limit | The number of repetitions of an attribute exceeds the limits of the standard or of one of the conformance profiles identified in the message.
2 | SYN109 | Mandatory element with null value | Description: An attribute or association identified as mandatory in a specification or declared conformance profile or template has been specified with a null flavor.
2 | SYN111 | Value does not match fixed value | Description: The value of an attribute or property differs from the fixed value asserted in the standard or one of the conformance profiles or templates declared in the message.
2 | SYN113 | Formal constraint violation | Description: A formal constraint asserted in the standard or one of the conformance profiles or templates declared in the message has been violated.

4.3.2.1110 HL7 v3 Code System ContentProcessingMode

URL: https://hl7.org/fhir/STU3/v3/ContentProcessingMode/cs.html

This page is part of the FHIR Specification (v3.0.2: STU 3). The current version which supercedes this version is 4.0.1. For a full list of available versions, see the Directory of published versions

Vocabulary Work Group | Maturity Level: N/A | External | Use Context: Any

This code system (http://hl7.org/fhir/v3/ContentProcessingMode) is defined as part of HL7 v3.

Summary

Defining URL: | http://hl7.org/fhir/v3/ContentProcessingMode
Name: | v3 Code System ContentProcessingMode
Definition: | Description: Identifies the order in which content should be processed.
OID: | 2.16.840.1.113883.5.1110 (for OID based terminology systems)
Source Resource | XML / JSON

This Code system is used in the following value sets:

* v3 Code System ContentProcessingMode (Description: Identifies the order in which content should be processed.)

4.3.2.1110.1 Code System Content

Release Date: 2016-11-11

Level | Code | Display | Definition
1 | SEQL | Sequential | Description:The content should be processed in a sequential fashion.

1 | UNOR | Unordered | Description:The content may be processed in any order.

4.3.2.1111 HL7 v3 Code System TransmissionRelationshipTypeCode

URL: https://hl7.org/fhir/STU3/v3/TransmissionRelationshipTypeCode/cs.html

This page is part of the FHIR Specification (v3.0.2: STU 3). The current version which supercedes this version is 4.0.1. For a full list of available versions, see the Directory of published versions

Vocabulary Work Group | Maturity Level: N/A | External | Use Context: Any

This code system (http://hl7.org/fhir/v3/TransmissionRelationshipTypeCode) is defined as part of HL7 v3.

Summary

Defining URL: | http://hl7.org/fhir/v3/TransmissionRelationshipTypeCode
Name: | v3 Code System TransmissionRelationshipTypeCode
Definition: | Description: A code specifying the meaning and purpose of every TransmissionRelationship instance. Each of its values implies specific constraints to what kinds of Transmission objects can be related and in which way.
OID: | 2.16.840.1.113883.5.1111 (for OID based terminology systems)
Source Resource | XML / JSON

This Code system is used in the following value sets:

* v3 Code System TransmissionRelationshipTypeCode (Description: A code specifying the meaning and purpose of every TransmissionRelationship instance. Each of its values implies specific constraints to what kinds of Transmission objects can be related and in which way.)

4.3.2.1111.1 Code System Content

Release Date: 2016-11-11

Level | Code | Display | Definition
1 | SEQL | sequence | Description:A transmission relationship indicating that the source transmission follows the target transmission.

4.3.2.1112 HL7 v3 Code System QueryRequestLimit

URL: https://hl7.org/fhir/STU3/v3/QueryRequestLimit/cs.html

This page is part of the FHIR Specification (v3.0.2: STU 3). The current version which supercedes this version is 4.0.1. For a full list of available versions, see the Directory of published versions

Vocabulary Work Group | Maturity Level: N/A | External | Use Context: Any

This code system (http://hl7.org/fhir/v3/QueryRequestLimit) is defined as part of HL7 v3.

Summary

Defining URL: | http://hl7.org/fhir/v3/QueryRequestLimit
Name: | v3 Code System QueryRequestLimit
Definition: | Definition: Defines the units associated with the magnitude of the maximum size limit of a query response that can be accepted by the requesting application.
OID: | 2.16.840.1.113883.5.1112 (for OID based terminology systems)
Source Resource | XML / JSON

This Code system is used in the following value sets:

* v3 Code System QueryRequestLimit (Definition: Defines the units associated with the magnitude of the maximum size limit of a query response that can be accepted by the requesting application.)

4.3.2.1112.1 Code System Content

Release Date: 2016-11-11

Level | Code | Display | Definition
1 | (_QueryRequestLimit) Abstract | | Definition: The number of matching instances (number of focal classes). The document header class is the focal class of a document, a record would therefore be equal to a document.
2 | RD | record | Definition: The number of matching instances (number of focal classes). The document header class is the focal class of a document, a record would therefore be equal to a document.

4.3.2.1113 HL7 v3 Code System ExposureMode

URL: https://hl7.org/fhir/STU3/v3/ExposureMode/cs.html

This page is part of the FHIR Specification (v3.0.2: STU 3). The current version which supercedes this version is 4.0.1. For a full list of available versions, see the Directory of published versions

Vocabulary Work Group | Maturity Level: N/A | External | Use Context: Any

This code system (http://hl7.org/fhir/v3/ExposureMode) is defined as part of HL7 v3.

Summary

Defining URL: | http://hl7.org/fhir/v3/ExposureMode
Name: | v3 Code System ExposureMode

Definition: | Code for the mechanism by which the exposure agent was exchanged or potentially exchanged by the participants involved in the exposure.
OID: | 2.16.840.1.113883.5.1113 (for OID based terminology systems)
Source Resource | XML / JSON

This Code system is used in the following value sets:

* v3 Code System ExposureMode (Code for the mechanism by which the exposure agent was exchanged or potentially exchanged by the participants involved in the exposure.)

4.3.2.1113.1 Code System Content

Release Date: 2016-11-11

Level | Code | Display | Definition
1 | (_ExposureMode) Abstract | | Code for the mechanism by which the exposure agent was exchanged or potentially exchanged by the participants involved in the exposure.
2 | AIRBORNE | airborne | Description: Communication of an agent from a living subject or environmental source to a living subject through indirect contact via oral or nasal inhalation.
2 | CONTACT | contact | Description: Communication of an agent from a living subject or environmental source to a living subject through direct physical contact.
2 | FOODBORNE | foodborne | Description: Communication of an agent from a food source to a living subject via oral consumption.
2 | WATERBORNE | waterborne | Description: Communication of an agent to a living subject by contact and/or consumption via an aqueous medium

4.3.2.1114 HL7 v3 Code System ActExposureLevelCode

URL: https://hl7.org/fhir/STU3/v3/ActExposureLevelCode/cs.html

This page is part of the FHIR Specification (v3.0.2: STU 3). The current version which supercedes this version is 4.0.1. For a full list of available versions, see the Directory of published versions

Vocabulary Work Group | Maturity Level: N/A | External | Use Context: Any

This code system (http://hl7.org/fhir/v3/ActExposureLevelCode) is defined as part of HL7 v3.

Summary

Defining URL: | http://hl7.org/fhir/v3/ActExposureLevelCode
Name: | v3 Code System ActExposureLevelCode
Definition: | A qualitative measure of the degree of exposure to the causative agent. This includes concepts such as "low", "medium" and "high". This quantifies how the quantity that was available to be administered to the target differs from typical or background levels of the substance.
OID: | 2.16.840.1.113883.5.1114 (for OID based terminology systems)
Source Resource | XML / JSON

This Code system is used in the following value sets:

* v3 Code System ActExposureLevelCode (A qualitative measure of the degree of exposure to the causative agent. This includes concepts such as "low", "medium" and "high". This quantifies how the quantity that was available to be administered to the target differs from typical or background levels of the substance.)

4.3.2.1114.1 Code System Content

Release Date: 2016-11-11

Level | Code | Display | Definition
1 | (_ActExposureLevelCode) Abstract | | A qualitative measure of the degree of exposure to the causative agent. This includes concepts such as "low", "medium" and "high". This quantifies how the quantity that was available to be administered to the target differs from typical or background levels of the substance.
2 | HIGH | high | Description: Exposure to an agent at a relatively high level above background.
2 | LOW | low | Description: Exposure to an agent at a relatively low level above background.
2 | MEDIUM | medium | Description: Exposure to an agent at a relatively moderate level above background.A

4.3.2.1116 HL7 v3 Code System IdentifierScope

URL: https://hl7.org/fhir/STU3/v3/IdentifierScope/cs.html

This page is part of the FHIR Specification (v3.0.2: STU 3). The current version which supercedes this version is 4.0.1. For a full list of available versions, see the Directory of published versions

Vocabulary Work Group | Maturity Level: N/A | External | Use Context: Any

This code system (http://hl7.org/fhir/v3/IdentifierScope) is defined as part of HL7 v3.

Summary

Defining URL: | http://hl7.org/fhir/v3/IdentifierScope
Name: | v3 Code System IdentifierScope
Definition: | Description: Codes to specify the scope in which the identifier applies to the object with which it is associated, and used in the datatype property II.
OID: | 2.16.840.1.113883.5.1116 (for OID based terminology systems)
Source Resource | XML / JSON

This Code system is used in the following value sets:

* v3 Code System IdentifierScope (Description: Codes to specify the scope in which the identifier applies to the object with which it is associated, and used in the datatype property II.)

4.3.2.1116.1 Code System Content

Release Date: 2016-11-11

Level | Code | Display | Definition

1 | BUSN | Business Identifier | Description: An identifier whose scope is defined by the business practices associated with the object. In contrast to the other scope identifiers, the scope of the use of the id is not necessarily restricted to a single object, but may be reused for other objects closely associated with the object due to business practice.

1 | OBJ | Object Identifier | Description: The identifier associated with a particular object. It remains consistent as the object undergoes state transitions.

1 | VER | Version Identifier | Description: An identifier that references a particular object as it existed at a given point in time. The identifier SHALL change with each state transition on the object. I.e. The version identifier of an object prior to a 'suspend' state transition is distinct from the identifier of the object after the state transition. Each version identifier can be tied to exactly one ControlAct event which brought that version into being (though the control act may never be instantiated). NOTE: Applications that do not support versioning of objects must ignore and not persist these ids to avoid confusion resulting from leaving the same identifier on an object that undergoes changes.

1 | VW | View Specific Identifier | Description: An identifier that references a particular object as it existed at a given point in time. The identifier SHALL change with each state transition on the object. Example The version identifier of an object prior to a 'suspend' state transition is distinct from the identifier of the object after the state transition. Each version identifier can be tied to exactly one ControlAct event which brought that version into being (though the control act may never be instantiated). NOTE: Applications that do not support versioning of objects must ignore and not persist these ids to avoid confusion resulting from leaving the same identifier on an object that undergoes changes.

4.3.2.1117 HL7 v3 Code System IdentifierReliability

URL: https://hl7.org/fhir/STU3/v3/IdentifierReliability/cs.html

This page is part of the FHIR Specification (v3.0.2: STU 3). The current version which supercedes this version is 4.0.1. For a full list of available versions, see the Directory of published versions

Vocabulary Work Group | Maturity Level: N/A | External | Use Context: Any

This code system (http://hl7.org/fhir/v3/IdentifierReliability) is defined as part of HL7 v3.

Summary

Defining URL: | http://hl7.org/fhir/v3/IdentifierReliability

Name: | v3 Code System IdentifierReliability

Definition: | Specifies the reliability with which the identifier is known. This attribute MAY be used to assist with identifier matching algorithms.

OID: | 2.16.840.1.113883.5.1117 (for OID based terminology systems)

Source Resource | XML / JSON

This Code system is used in the following value sets:

* v3 Code System IdentifierReliability (Specifies the reliability with which the identifier is known. This attribute MAY be used to assist with identifier matching algorithms.)

4.3.2.1117.1 Code System Content

Release Date: 2016-11-11

Level | Code | Display | Definition

1 | ISS | Issued by System | Description: The identifier was issued by the system responsible for constructing the instance.

1 | UNV | Unverified by system | Description: The identifier was provided to the system that constructed the instance, but has not been verified. e.g. a Drivers license entered manually into a system by a user.

1 | VRF | Verified by system | Description: The identifier was not issued by the system responsible for constructing the instance, but the system that captured the id has verified the identifier with the issuing authority, or with another system that has verified the identifier.

4.3.2.1118 HL7 v3 Code System TelecommunicationCapabilities

URL: https://hl7.org/fhir/STU3/v3/TelecommunicationCapabilities/cs.html

This page is part of the FHIR Specification (v3.0.2: STU 3). The current version which supercedes this version is 4.0.1. For a full list of available versions, see the Directory of published versions

Vocabulary Work Group | Maturity Level: N/A | External | Use Context: Any

This code system (http://hl7.org/fhir/v3/TelecommunicationCapabilities) is defined as part of HL7 v3.

Summary

Defining URL: | http://hl7.org/fhir/v3/TelecommunicationCapabilities

Name: | v3 Code System TelecommunicationCapabilities

Definition: | Description: Concepts that define the telecommunication capabilities of a particular device. Used to identify the expected capabilities to be found at a particular telecommunication address.

OID: | 2.16.840.1.113883.5.1118 (for OID based terminology systems)

Source Resource | XML / JSON

This Code system is used in the following value sets:

* v3 Code System TelecommunicationCapabilities (Description: Concepts that define the telecommunication capabilities of a particular device. Used to identify the expected capabilities to be found at a particular telecommunication address.)

4.3.2.1118.1 Code System Content

Release Date: 2016-11-11

Level | Code | Display | Definition
1 | data | data | Description: This device can receive data calls (i.e. modem).
1 | fax | fax | Description: This device can receive faxes.
1 | sms | sms | Description: This device can receive SMS messages.
1 | tty | text | Description: This device is a text telephone.
1 | voice | voice | Description: This device can receive voice calls (i.e. talking to another person, or a recording device, or a voice activated computer).

4.3.2.1119 HL7 v3 Code System AddressUse

URL: https://hl7.org/fhir/STU3/v3/AddressUse/cs.html

This page is part of the FHIR Specification (v3.0.2: STU 3). The current version which supercedes this version is 4.0.1. For a full list of available versions, see the Directory of published versions

Vocabulary Work Group | Maturity Level: N/A | External | Use Context: Any

This code system (http://hl7.org/fhir/v3/AddressUse) is defined as part of HL7 v3. Related FHIR content: AddressUse.

Summary

Defining URL: | http://hl7.org/fhir/v3/AddressUse
Name: | v3 Code System AddressUse
Definition: | Codes that provide guidance around the circumstances in which a given address should be used.
OID: | 2.16.840.1.113883.5.1119 (for OID based terminology systems)
Source Resource | XML / JSON

This Code system is used in the following value sets:

* PostalAddressUse (Uses of an address not included in Address.use)

* v3 Code System AddressUse (Codes that provide guidance around the circumstances in which a given address should be used.)

4.3.2.1119.1 Code System Content

Release Date: 2016-11-11

Level | Code | Display | Definition
1 | (_GeneralAddressUse) Abstract | | Description: Address uses that can apply to both postal and telecommunication addresses.
2 | BAD | bad address | Description: A flag indicating that the address is bad, in fact, useless.
2 | CONF | confidential address | Description: Indicates that the address is considered sensitive and should only be shared or published in accordance with organizational controls governing patient demographic information with increased sensitivity. Uses of Addresses. Lloyd to supply more complete description.
2 | H | home address | Description: A communication address at a home, attempted contacts for business purposes might intrude privacy and chances are one will contact family or other household members instead of the person one wishes to call. Typically used with urgent cases, or if no other contacts are available.
3 | HP | primary home | Description: The primary home, to reach a person after business hours.
3 | HV | vacation home | Description: A vacation home, to reach a person while on vacation.
2 | OLD | no longer in use | This address is no longer in use. Usage Note: Address may also carry valid time ranges. This code is used to cover the situations where it is known that the address is no longer valid, but no particular time range for its use is known.
2 | TMP | temporary address | Description: A temporary address, may be good for visit or mailing. Note that an address history can provide more detailed information.
2 | WP | work place | Description: An office address. First choice for business related contacts during business hours.
3 | DIR | direct | Description: Indicates a work place address or telecommunication address that reaches the individual or organization directly without intermediaries. For phones, often referred to as a 'private line'.
3 | PUB | public | Description: Indicates a work place address or telecommunication address that is a 'standard' address which may reach a reception service, mail-room, or other intermediary prior to the target entity.
1 | (_PostalAddressUse) Abstract | | Description: Address uses that only apply to postal addresses, not telecommunication addresses.
2 | PHYS | physical visit address | Description: Used primarily to visit an address.
2 | PST | postal address | Description: Used to send mail.
1 | (_TelecommunicationAddressUse) Abstract | | Description: Address uses that only apply to telecommunication addresses, not postal addresses.
2 | AS | answering service | Description: An automated answering machine used for less urgent cases and if the main purpose of contact is to leave a message or access an automated announcement.
2 | EC | emergency contact | Description: A contact specifically designated to be used for emergencies. This is the first choice in emergencies, independent of any other use codes.
2 | MC | mobile contact) | Description: A telecommunication device that moves and stays with its owner. May have characteristics of all other use codes, suitable for urgent matters, not the first choice for routine business.
2 | PG | pager | Description: A paging device suitable to solicit a callback or to leave a very short message.

4.3.2.1120 HL7 v3 Code System EntityNameUseR2

URL: https://hl7.org/fhir/STU3/v3/EntityNameUseR2/cs.html

This page is part of the FHIR Specification (v3.0.2: STU 3). The current version which supercedes this version is 4.0.1. For a full list of available versions, see the Directory of published versions

Vocabulary Work Group | Maturity Level: N/A | External | Use Context: Any

This code system (http://hl7.org/fhir/v3/EntityNameUseR2) is defined as part of HL7 v3.

Summary

Defining URL: | http://hl7.org/fhir/v3/EntityNameUseR2
Name: | v3 Code System EntityNameUseR2
Definition: | Description: A set of codes advising a system or user which name in a set of names to select for a given purpose.
OID: | 2.16.840.1.113883.5.1120 (for OID based terminology systems)
Source Resource | XML / JSON

This Code system is used in the following value sets:

* v3 Code System EntityNameUseR2 (Description: A set of codes advising a system or user which name in a set of names to select for a given purpose.)

4.3.2.1120.1 Code System Content

Release Date: 2016-11-11

Level | Code | Display | Definition
1 | (Assumed) Abstract | | Description:A name that a person has assumed or has been assumed to them.
2 | A | business name | Description:A name used in a Professional or Business context . Examples: Continuing to use a maiden name in a professional context, or using a stage performing name (some of these names are also pseudonyms)
2 | ANON | Anonymous | Description:Anonymous assigned name (used to protect a persons identity for privacy reasons)
2 | I | Indigenous/Tribal | Description:e.g . Chief Red Cloud
2 | P | Other/Pseudonym/Alias | Description:A non-official name by which the person is sometimes known. (This may also be used to record informal names such as a nickname)
2 | R | religious | Description:A name assumed as part of a religious vocation . e.g . Sister Mary Francis, Brother John
1 | C | customary | Description:Known as/conventional/the one you normally use
1 | M | maiden name | Description:A name used prior to marriage.Note that marriage naming customs vary greatly around the world. This name use is for use by applications that collect and store maiden names. Though the concept of maiden name is often gender specific, the use of this term is not gender specific. The use of this term does not imply any particular history for a person's name, nor should the maiden name be determined algorithmically
1 | (NameRepresentationUse) Abstract | | Description:Identifies the different representations of a name . The representation may affect how the name is used . (E.g . use of Ideographic for formal communications.)
2 | ABC | alphabetic | Description:Alphabetic transcription of name in latin alphabet (Japanese: romaji)
2 | IDE | ideographic | Description:Ideographic representation of name (e.g., Japanese kanji, Chinese characters)
2 | SYL | syllabic | Description:Syllabic transcription of name (e.g., Japanese kana, Korean hangul)
1 | OLD | no longer in use | Description:This name is no longer in use (note: Names may also carry valid time ranges . This code is used to cover the situations where it is known that the name is no longer valid, but no particular time range for its use is known)
2 | DN | do not use | Description:This name should no longer be used when interacting with the person (i.e . in addition to no longer being used, the name should not be even mentioned when interacting with the person)Note: applications are not required to compare names labeled "Do Not Use" and other names in order to eliminate name parts that are common between the other name and a name labeled "Do Not Use".
1 | OR | official registry name | Description:The formal name as registered in an official (government) registry, but which name might not be commonly used . May correspond to the concept of legal name
1 | PHON | phonetic | Description:The name as understood by the data enterer, i.e. a close approximation of a phonetic spelling of the name, not based on a phonetic algorithm.
1 | SRCH | search | Description:A name intended for use in searching or matching. This is used when the name is incomplete and contains enough details for search matching, but not enough for other uses.
1 | T | temporary | Description:A temporary name. Note that a name valid time can provide more detailed information. This may also be used for temporary names assigned at birth or in emergency situations.

4.3.2.1121 HL7 v3 Code System EntityNamePartTypeR2

URL: https://hl7.org/fhir/STU3/v3/EntityNamePartTypeR2/cs.html

This page is part of the FHIR Specification (v3.0.2: STU 3). The current version which supercedes this version is 4.0.1. For a full list of available versions, see the Directory of published versions

Vocabulary Work Group | Maturity Level: N/A | External | Use Context: Any

This code system (http://hl7.org/fhir/v3/EntityNamePartTypeR2) is defined as part of HL7 v3.

Summary

Defining URL: | http://hl7.org/fhir/v3/EntityNamePartTypeR2
Name: | v3 Code System EntityNamePartTypeR2
Definition: | Description: Indicates whether the name part is a given name, family name, prefix, suffix, etc.
OID: | 2.16.840.1.113883.5.1121 (for OID based terminology systems)
Source Resource | XML / JSON

This Code system is used in the following value sets:

* v3 Code System EntityNamePartTypeR2 (Description: Indicates whether the name part is a given name, family name, prefix, suffix, etc.)

4.3.2.1121.1 Code System Content

Release Date: 2016-11-11

Level | Code | Display | Definition

1 | DEL | delimiter | Description:A delimiter has no meaning other than being literally printed in this name representation. A delimiter has no implicit leading and trailing white space.

1 | FAM | family | Description:Family name, this is the name that links to the genealogy. In some cultures (e.g. Eritrea) the family name of a son is the first name of his father.

1 | GIV | given | Description:Given name. Note: don't call it "first name" since the given names do not always come first.

1 | TITLE | title | Description:Part of the name that is acquired as a title due to academic, legal, employment or nobility status etc. Note:Title name parts include name parts that come after the name such as qualifications, even if they are not always considered to be titles.

4.3.2.1122 HL7 v3 Code System EntityNamePartQualifierR2

URL: https://hl7.org/fhir/STU3/v3/EntityNamePartQualifierR2/cs.html

This page is part of the FHIR Specification (v3.0.2: STU 3). The current version which supercedes this version is 4.0.1. For a full list of available versions, see the Directory of published versions

Vocabulary Work Group | Maturity Level: N/A | External | Use Context: Any

This code system (http://hl7.org/fhir/v3/EntityNamePartQualifierR2) is defined as part of HL7 v3.

Summary

Defining URL: | http://hl7.org/fhir/v3/EntityNamePartQualifierR2

Name: | v3 Code System EntityNamePartQualifierR2

Definition: | Description: The qualifier is a set of codes each of which specifies a certain subcategory of the name part in addition to the main name part type. For example, a given name may be flagged as a nickname, a family name may be a pseudonym or a name of public records.

OID: | 2.16.840.1.113883.5.1122 (for OID based terminology systems)

Source Resource | XML / JSON

This Code system is used in the following value sets:

* EntityNamePartQualifier (A set of codes each of which specifies a certain subcategory of the name part in addition to the main name part type)

* v3 Code System EntityNamePartQualifierR2 (Description: The qualifier is a set of codes each of which specifies a certain subcategory of the name part in addition to the main name part type. For example, a given name may be flagged as a nickname, a family name may be a pseudonym or a name of public records.)

4.3.2.1122.1 Code System Content

Release Date: 2016-11-11

Level | Code | Display | Definition

1 | AD | acquired | Description:A name part a person acquired. The name part may be acquired by adoption, or the person may have chosen to use the name part for some other reason. Note: this differs from an Other/Psuedonym/Alias in that an acquired name part is acquired on a formal basis rather than an informal one (e.g. registered as part of the official name).

2 | SP | spouse | Description:The name assumed from the partner in a marital relationship. Usually the spouse's family name. Note that no inference about gender can be made from the existence of spouse names.

1 | BR | birth | Description:A name that a person was given at birth or established as a consequence of adoption. Note: This is not used for temporary names assigned at birth such as "Baby of Smith" a" which is just a name with a use code of "TEMP".

1 | CL | callme | Description:Used to indicate which of the various name parts is used when interacting with the person.

1 | IN | initial | Description:Indicates that a name part is just an initial. Initials do not imply a trailing period since this would not work with non-Latin scripts. In some languages, initials may consist of more than one letter, e.g., "Ph" could stand for "Philippe" or "Th" For "Thomas".

1 | LS | legal status | Description:For organizations a suffix indicating the legal status, e.g., "Inc.", "Co.", "AG", "GmbH", "B.V." "S.A.", "Ltd." etc.

1 | MID | middle name | Description:Indicates that the name part is a middle name. Usage Notes: In general, the english "middle name" concept is all of the given names after the first. This qualifier may be used to explicitly indicate which given names are considered to be middle names. The middle name qualifier may also be used with family names. This is a Scandinavian use case, matching the concept of "mellomnavn","mellannamn". Note that there are specific rules that indicate what names may be taken as a mellannamn in different Scandinavian countries.

1 | PFX | prefix | Description:A prefix has a strong association to the immediately following name part. A prefix has no implicit trailing white space (it has implicit leading white space though).

1 | (PharmaceuticalEntityNamePartQualifiers) Abstract | | Description: Medication Name Parts are a means of specifying a range of acceptable "official" forms of the name of a product. They are used as patterns against which input name strings may be matched for automatic identification of products from input text reports. While they cover the concepts held under "doseForm" or "route" or "strength" the name parts are not the same and do not fit into a controlled vocabulary in the same way. By specifying up to 8 name parts a much larger range of possible names can be generated.

2 | CON | container name | Description: This refers to the container if present in the medicinal product name. EXAMPLES: For Optaflu suspension for injection in pre-filled syringe Influenza vaccine (surface antigen, inactivated, prepared in cell culture) (2007/2008 season): pre-filled syringe

2 | DEV | device name | Description: This refers to the qualifiers in the name for devices and is at the moment mainly applicable to insulins and inhalation products. EXAMPLES: For the medicinal product Actrapid FlexPen 100 IU/ml Solution for injection Subcutaneous use: FlexPen.

2 | FLAV | FlavorName | Description: This refers to a flavor of the medicinal product if present in the medicinal product name. Examples: For 'CoughCure Linctus Orange Flavor', the flavor part is "Orange" For 'Wonderdrug Syrup Cherry Flavor', the flavor part is "Cherry"

2 | FORMUL | FormulationPartName | Description: This refers to the formulation of the medicinal product if present in the medicinal product name. Examples: For 'SpecialMed Sugar Free Cough Syrup', the formulation name part is "Sugar Free" For 'QuickCure Gluten-free Bulk Fibre', the formulation name part is "gluten-free"

2 | FRM | form name | Description: This refers to the pharmaceutical form/ if present in the medicinal product name. EXAMPLES: For Agenerase 50 mg soft capsules: Soft Capsules For Ludiomil 25mg-Filmtabletten: Filmtabletten For Optaflu suspension for injection in pre-filled syringe Influenza vaccine (surface antigen, inactivated, prepared in cell culture) (2007/2008 season): suspension for injection

2 | INV | invented name | Description: This refers to the product name without the trademark or the name of the marketing authorization holder or any other descriptor reflected in the product name and, if appropriate, whether it is intended e.g. for babies, children or adults. EXAMPLES: Agenerase Optaflu Ludiomil

2 | POPUL | TargetPopulationName | Description: This refers to the target population for the medicinal product if present in the medicinal product name Examples: For 'Broncho-Drug 3.5 mg-capsules for children', the target population part is "children" For 'Adult Chesty Cough Syrup', the target

population part is "adult"

2 | SCI | scientific name | Description: This refers to the product common or scientific name without the trademark or the name of the marketing authorization holder or any other descriptor reflected in the product name. EXAMPLES: For Agenerase: N/A For Optaflu: Influenza vaccine (surface antigen, inactivated, prepared in cell culture) (2007/2008 season) For Ludiomil: N/A

2 | STR | strength name | Description: This refers to the strength if present in the medicinal product name. The use of decimal points should be accommodated if required. EXAMPLES: For Agenerase 50 mg soft capsules: 50mg For Ludiomil 25mg-Filmtabletten: 25 mg For Optaflu suspension for injection in pre-filled syringe Influenza vaccine (surface antigen, inactivated, prepared in cell culture) (2007/2008 season): N/A

2 | TIME | TimeOrPeriodName | Description: This refers to a time or time period that may be specified in the text of the medicinal product name Example: For an influenza vaccine 'Drug-FLU season 2008/2009', the time/period part is "2008/2009 season"

2 | TMK | trademark name | Description: This refers to trademark/company element if present in the medicinal product name. EXAMPLES: for Insulin Human Winthrop Comb 15: Winthrop

2 | USE | intended use name | Description: This refers to the intended use if present in the medicinal product name without the trademark or the name of the marketing authorization holder or any other descriptor reflected in the product name. Examples: For 'Drug-BI Caplets - Heartburn Relief', the intended use part is: "Heartburn Relief" For 'Medicine Honey Syrup for Soothing Coughs' the intended use part is "Soothing Coughs"

1 | SFX | suffix | Description:A suffix has a strong association to the immediately preceding name part. A suffix has no implicit leading white space (it has implicit trailing white space though).

1 | (TitleStyles) Abstract | | Description:Extra information about the style of a title

2 | AC | academic | Description:Indicates that a title like "Dr.", "M.D." or "Ph.D." is an academic title.

2 | HON | honorific | Description:A honorific such as "The Right Honourable" or "Weledelgeleerde Heer".

2 | NB | nobility | Description:A nobility title such as Sir, Count, Grafin.

2 | PR | professional | Description:Primarily in the British Imperial culture people tend to have an abbreviation of their professional organization as part of their credential titles.

4.3.2.1123 HL7 v3 Code System DataOperation

URL: https://hl7.org/fhir/STU3/v3/DataOperation/cs.html

This page is part of the FHIR Specification (v3.0.2: STU 3). The current version which supercedes this version is 4.0.1. For a full list of available versions, see the Directory of published versions

Vocabulary Work Group | Maturity Level: N/A | External | Use Context: Any

This code system (http://hl7.org/fhir/v3/DataOperation) is defined as part of HL7 v3.

Summary

Defining URL: | http://hl7.org/fhir/v3/DataOperation
Name: | v3 Code System DataOperation
Definition: | **** MISSING DEFINITIONS ****
OID: | 2.16.840.1.113883.5.1123 (for OID based terminology systems)
Source Resource | XML / JSON

This Code system is used in the following value sets:

* v3 Code System DataOperation (**** MISSING DEFINITIONS ****)

* ProvenanceActivityType (This value set contains representative Activity Type codes, which includes codes from the HL7 DocumentCompletion, ActStatus, and DataOperations code system, W3C PROV-DM and PROV-N concepts and display names, several HL7 Lifecycle Event codes for which there are agreed upon definitions, and non-duplicated codes from the HL7 Security and Privacy Ontology Operations codes.)

4.3.2.1123.1 Code System Content

Release Date: 2016-11-11

Level | Code | Display | Definition

1 | OPERATE | operate | Description:Act on an object or objects.

2 | CREATE | create | Description:Fundamental operation in an Information System (IS) that results only in the act of bringing an object into existence. Note: The preceding definition is taken from the HL7 RBAC specification. There is no restriction on how the operation is invoked, e.g., via a user interface. For an HL7 Act, the state transitions per the HL7 Reference Information Model.

2 | DELETE | delete | Description:Fundamental operation in an Information System (IS) that results only in the removal of information about an object from memory or storage. Note: The preceding definition is taken from the HL7 RBAC specification. There is no restriction on how the operation is invoked, e.g., via a user interface.

2 | EXECUTE | execute | Description:Fundamental operation in an IS that results only in initiating performance of a single or set of programs (i.e., software objects). Note: The preceding definition is taken from the HL7 RBAC specification. There is no restriction on how the operation is invoked, e.g., via a user interface.

2 | READ | read | Description:Fundamental operation in an Information System (IS) that results only in the flow of information about an object to a subject. Note: The preceding definition is taken from the HL7 RBAC specification. There is no restriction on how the operation is invoked, e.g., via a user interface.

2 | UPDATE | revise | Definition:Fundamental operation in an Information System (IS) that results only in the revision or alteration of an object. Note: The preceding definition is taken from the HL7 RBAC specification. There is no restriction on how the operation is invoked, e.g., via a user interface.

3 | APPEND | append | Description:Fundamental operation in an Information System (IS) that results only in the addition of information to an object already in existence. Note: The preceding definition is taken from the HL7 RBAC specification. There is no restriction on how the operation is invoked, e.g., via a user interface.

3 | MODIFYSTATUS | modify status | Description:Change the status of an object representing an Act.

4 | ABORT | abort | Description:Change the status of an object representing an Act to "aborted", i.e., terminated prior to the originally intended completion. For an HL7 Act, the state transitions per the HL7 Reference Information Model.

4 | ACTIVATE | activate | Description:Change the status of an object representing an Act to "active", i.e., so it can be performed or is being performed, for the first time. (Contrast with REACTIVATE.) For an HL7 Act, the state transitions per the HL7 Reference Information Model.

4 | CANCEL | cancel | Description:Change the status of an object representing an Act to "cancelled", i.e., abandoned before activation. For an HL7 Act, the state transitions per the HL7 Reference Information Model.

4 | COMPLETE | complete | Description:Change the status of an object representing an Act to "completed", i.e., terminated normally after all of its constituents have been performed. For an HL7 Act, the state transitions per the HL7 Reference Information Model.

4 | HOLD | hold | Description:Change the status of an object representing an Act to "held", i.e., put aside an Act that is still in preparatory stages. No action can occur until the Act is released. For an HL7 Act, the state transitions per the HL7 Reference Information Model.

4 | JUMP | jump | Description:Change the status of an object representing an Act to a normal state. For an HL7 Act, the state transitions per the HL7 Reference Information Model.

4 | NULLIFY | nullify | Description:Change the status of an object representing an Act to "nullified", i.e., treat as though it never existed. For an HL7 Act, the state transitions per the HL7 Reference Information Model.

4 | OBSOLETE | obsolete | Description:Change the status of an object representing an Act to "obsolete" when it has been replaced by a new instance. For an HL7 Act, the state transitions per the HL7 Reference Information Model.

4 | REACTIVATE | reactivate | Description:Change the status of a formerly active object representing an Act to "active", i.e., so it can again be performed or is being performed. (Contrast with ACTIVATE.) For an HL7 Act, the state transitions per the HL7 Reference Information Model.

4 | RELEASE | release | Description:Change the status of an object representing an Act so it is no longer "held", i.e., allow action to occur. For an HL7 Act, the state transitions per the HL7 Reference Information Model.

4 | RESUME | resume | Description:Change the status of a suspended object representing an Act to "active", i.e., so it can be performed or is being performed. For an HL7 Act, the state transitions per the HL7 Reference Information Model.

4 | SUSPEND | suspend | Definition:Change the status of an object representing an Act to suspended, i.e., so it is temporarily not in service.

4.3.2.1124 HL7 v3 Code System hl7Realm

URL: https://hl7.org/fhir/STU3/v3/hl7Realm/cs.html

This page is part of the FHIR Specification (v3.0.2: STU 3). The current version which supercedes this version is 4.0.1. For a full list of available versions, see the Directory of published versions

Vocabulary Work Group | Maturity Level: N/A | External | Use Context: Any

This code system (http://hl7.org/fhir/v3/hl7Realm) is defined as part of HL7 v3.

Summary

Defining URL: | http://hl7.org/fhir/v3/hl7Realm

Name: | v3 Code System hl7Realm

Definition: | Description: Coded concepts representing Binding Realms (used for Context Binding of terminology in HL7 models) and/or Namespace Realms (used to help ensure unique identification of HL7 artifacts). This code system is partitioned into three sections: Affiliate realms, Binding realms and Namespace realms. All affiliate realm codes may automatically be used as both binding realms and namespace realms. Furthermore, affiliate realms are the only realms that have authority over the creation of binding realms. (Note that 'affiliate' includes the idea of both international affiliates and the HL7 International organization.) All other codes must be associated with an owning affiliate realm and must appear as a specialization of _BindingRealm or _NamespaceRealm. For affiliates whose concepts align with nations, the country codes from ISO 3166-1 2-character alpha are used for the code when possible so these codes should not be used for other realm types. It is recommended that binding realm and namespace codes submitted by affiliates use the realm code as a prefix to avoid possible collisions with ISO codes. However, tooling does not currently support namepace realm codes greater than 2 characters. Open Issue: The name of the concept property "owningAffiliate" should be changed to better reflect that the property value is the human readable name of the organizational entity that manages the Realm identified by the Realm Code. Open Issue: In spite of the inability of tooling to process codes longer than 2 characters, there is at least one realm codes ('SOA') that was added that is 3 characters in length.

OID: | 2.16.840.1.113883.5.1124 (for OID based terminology systems)

Source Resource | XML / JSON

This Code system is used in the following value sets:

* v3 Code System hl7Realm (Description: Coded concepts representing Binding Realms (used for Context Binding of terminology in HL7 models) and/or Namespace Realms (used to help ensure unique identification of HL7 artifacts). This code system is partitioned into three sections: Affiliate realms, Binding realms and Namespace realms. All affiliate realm codes may automatically be used as both binding realms and namespace realms. Furthermore, affiliate realms are the only realms that have authority over the creation of binding realms. (Note that 'affiliate' includes the idea of both international affiliates and the HL7 International organization.) All other codes must be associated with an owning affiliate realm and must appear as a specialization of _BindingRealm or _NamespaceRealm. For affiliates whose concepts align with nations, the country codes from ISO 3166-1 2-character alpha are used for the code when possible so these codes should not be used for other realm types. It is recommended that binding realm and namespace codes submitted by affiliates use the realm code as a prefix to avoid possible collisions with ISO codes. However, tooling does not currently support namepace realm codes greater than 2 characters. Open Issue: The name of the concept property "owningAffiliate" should be changed to better reflect that the property value is the human readable name of the organizational entity that manages the Realm identified by the Realm Code. Open Issue: In spite of the inability of tooling to process codes longer than 2 characters, there is at least one realm codes ('SOA') that was added that is 3 characters in length.)

4.3.2.1124.1 Code System Content

Release Date: 2016-11-11

Level | Code | Display | Definition

1 | (BindingRealms) Abstract | | Description: Concepts that can be used as Binding Realms when creating Binding Statements. These codes are permitted to appear in the InfrastructureRoot.realmCode attribute.

2 | (AffiliateRealms) Abstract | | Description: Realm codes for official HL7 organizational bodies. This includes both the HL7 International organization as well as all recognized international affiliates (past and present). These groups have the ability to bind vocabulary and develop artifacts. As well, they have the ability to have "ownership" over other binding realms and namespace realms via the owningAffiliate property of those other realm codes.

3 | AR | Argentina | Description: Realm code for use of Argentina

3 | AT | Austria | Description: Realm code for use of Austria
3 | AU | Australia | Description: Realm code for use of Australia
3 | BR | Brazil | Description: Realm code for use of Brazil
3 | CA | Canada | Description: Realm code for use of Canada
3 | CH | Switzerland | Description: Realm code for use of Switzerland
3 | CL | Chile | Description: Realm code for use of Chile
3 | CN | China | Description: Realm code for use of China
3 | CO | Columbia | Description: Realm code for use of Localized Version
3 | CZ | Czech Republic | Description: Realm code for use of Czech Republic
3 | DE | Germany | Description: Realm code for use of Germany
3 | DK | Denmark | Description: Realm code for use of Denmark
3 | ES | Spain | Description: Realm code for use of Spain
3 | FI | Finland | Description: Realm code for use of Finland
3 | FR | France | Description: Realm code for use of France
3 | GR | Greece | Description: Realm code for use of Greece
3 | HR | Croatia | Description: Realm code for use of Croatia
3 | IE | Ireland | Description: Realm code for use of Ireland
3 | IN | India | Description: Realm code for use of India
3 | IT | Italy | Description: Realm code for use of Italy
3 | JP | Japan | Description: Realm code for use of Japan
3 | KR | Korea | Description: Realm code for use of Korea
3 | LT | Lithuania | Description: Realm code for use of Lithuania
3 | MX | Mexico | Description: Realm code for use of Mexico
3 | NL | The Netherlands | Description: Realm code for use of The Netherlands
3 | NZ | New Zealand | Description: Realm code for use of New Zealand
3 | RO | Romania | Description: Realm code for use of Romania
3 | RU | Russian Federation | Description: Realm code for use of Russian Federation
3 | SE | Sweden | Description: Realm code for use of Sweden
3 | SG | Singapore | Description: Realm code for use of Localized Version
3 | SOA | Southern Africa | Description: Realm code for use of Southern Africa
3 | TR | Turkey | Description: Realm code for use of Turkey
3 | TW | Taiwan | Description: Realm code for use of Taiwan
3 | UK | United Kingdom | Description: Realm code for use of United Kingdom
3 | US | United States of America | Description: Realm code for use of United States of America
3 | UV | Universal | Description: Realm code for use of Universal realm or context, used in every instance
3 | UY | Uruguay | Description: Realm code for use of Uruguay
2 | C1 | Unclassified Realm | Description: Realm code for use of Unclassified Realm
2 | GB | Great Britain | Description: Realm code for use of Great Britain
2 | R1 | Representative Realm | Description: Realm code for use of Representative Realm
2 | X1 | Example Realm | Description: Realm code for use of Example Realm
1 | (NamespaceRealms) Abstract | | Description: Codes that can be used in the "realm" portion of HL7 v3 artifact identifiers.
2 | AffiliateRealms
2 | GB
2 | ZZ | Localized Version | Description: An artifact created for local use only. This realm namespace has no owning affiliate. Its use is uncontrolled, i.e. anyone can create artifacts using this realm namespace. Because of this, there is a significant likelihood of artifact identifier collisions. Implementers are encouraged to register their artifacts under an affiliate owned and controlled namespace to avoid such collision problems where possible.

4.3.2.1125 HL7 v3 Code System hl7V3Conformance

URL: https://hl7.org/fhir/STU3/v3/hl7V3Conformance/cs.html

This page is part of the FHIR Specification (v3.0.2: STU 3). The current version which supercedes this version is 4.0.1. For a full list of available versions, see the Directory of published versions

Vocabulary Work Group | Maturity Level: N/A | External | Use Context: Any

This code system (http://hl7.org/fhir/v3/hl7V3Conformance) is defined as part of HL7 v3.

Summary

Defining URL: | http://hl7.org/fhir/v3/hl7V3Conformance
Name: | v3 Code System hl7V3Conformance
Definition: | Description: Identifies allowed codes for HL7aTMs v3 conformance property.
OID: | 2.16.840.1.113883.5.1125 (for OID based terminology systems)
Source Resource | XML / JSON

This Code system is used in the following value sets:

* v3 Code System hl7V3Conformance (Description: Identifies allowed codes for HL7aTMs v3 conformance property.)

4.3.2.1125.1 Code System Content

Release Date: 2016-11-11

Level | Code | Display | Definition
1 | I | ignored | Description: Implementers receiving this property must not raise an error if the data is received, but will not perform any useful function with the data. This conformance level is not used in profiles or other artifacts that are specific to the "sender" or "initiator" of a communication.

1 | NP | not permitted | Description: All implementers are prohibited from transmitting this content, and may raise an error if they receive it.
1 | R | required | Description: All implementers must support this property. I.e. they must be able to transmit, or to receive and usefully handle the concept.
1 | RC | required for consumer | Description: The element is considered "required" (i.e. must be supported) from the perspective of systems that consume instances, but is "undetermined" for systems that generate instances. Used only as part of specifications that define both initiator and consumer expectations.
1 | RI | required for initiator | Description: The element is considered "required" (i.e. must be supported) from the perspective of systems that generate instances, but is "undetermined" for systems that consume instances. Used only as part of specifications that define both initiator and consumer expectations.
1 | U | undetermined | Description: The conformance expectations for this element have not yet been determined.

4.3.2.1126 HL7 v3 Code System ResponseMode

URL: https://hl7.org/fhir/STU3/v3/ResponseMode/cs.html

This page is part of the FHIR Specification (v3.0.2: STU 3). The current version which supercedes this version is 4.0.1. For a full list of available versions, see the Directory of published versions

Vocabulary Work Group | Maturity Level: N/A | External | Use Context: Any

This code system (http://hl7.org/fhir/v3/ResponseMode) is defined as part of HL7 v3.

Summary

Defining URL: | http://hl7.org/fhir/v3/ResponseMode
Name: | v3 Code System ResponseMode
Definition: | Specifies the mode, immediate versus deferred or queued, by which a receiver should communicate its receiver responsibilities.
OID: | 2.16.840.1.113883.5.1126 (for OID based terminology systems)
Source Resource | XML / JSON

This Code system is used in the following value sets:

* v3 Code System ResponseMode (Specifies the mode, immediate versus deferred or queued, by which a receiver should communicate its receiver responsibilities.)

4.3.2.1126.1 Code System Content

Release Date: 2016-11-11

Level | Code | Display | Definition
1 | D | deferred | The receiver may respond in a non-immediate manner. Note: this will be the default value.
1 | I | immediate | The receiver is required to assume that the sender is blocking and behave appropriately by sending an immediate response.
1 | Q | queue | The receiver shall keep any application responses in a queue until such time as the queue is polled.

4.3.2.1137 HL7 v3 Code System RoleLinkStatus

URL: https://hl7.org/fhir/STU3/v3/RoleLinkStatus/cs.html

This page is part of the FHIR Specification (v3.0.2: STU 3). The current version which supercedes this version is 4.0.1. For a full list of available versions, see the Directory of published versions

Vocabulary Work Group | Maturity Level: N/A | External | Use Context: Any

This code system (http://hl7.org/fhir/v3/RoleLinkStatus) is defined as part of HL7 v3.

Summary

Defining URL: | http://hl7.org/fhir/v3/RoleLinkStatus
Name: | v3 Code System RoleLinkStatus
Definition: | Description: Codes representing possible states of a RoleLink, as defined by the RoleLink class state machine.
OID: | 2.16.840.1.113883.5.1137 (for OID based terminology systems)
Source Resource | XML / JSON

This Code system is used in the following value sets:

* v3 Code System RoleLinkStatus (Description: Codes representing possible states of a RoleLink, as defined by the RoleLink class state machine.)

4.3.2.1137.1 Code System Content

Release Date: 2016-11-11

Level | Code | Display | Definition
1 | NORMAL | normal | Description: The 'typical' state. Excludes "nullified" which represents the termination state of a RoleLink instance that was created in error.
2 | ACTIVE | active | Description: The state indicates the RoleLink is in progress.
2 | CANCELLED | cancelled | Description: The terminal state resulting from abandoning the RoleLink prior to or after activation.
2 | COMPLETED | completed | Description: The terminal state representing the successful completion of the RoleLink.
2 | PENDING | pending | Description: The state indicates the RoleLink has not yet become active.
1 | NULLIFIED | nullified | Description: The state representing the termination of a RoleLink instance that was created in error.

4.3.2.1138 HL7 v3 Code System ActUSPrivacyLaw

URL: https://hl7.org/fhir/STU3/v3/ActUSPrivacyLaw/cs.html

This page is part of the FHIR Specification (v3.0.2: STU 3). The current version which supercedes this version is 4.0.1. For a full list of available versions, see the Directory of published versions

Vocabulary Work Group | Maturity Level: N/A | External | Use Context: Any

This code system (http://hl7.org/fhir/v3/ActUSPrivacyLaw) is defined as part of HL7 v3.

Summary

Defining URL: | http://hl7.org/fhir/v3/ActUSPrivacyLaw

Name: | v3 Code System ActUSPrivacyLaw

Definition: | A jurisdictional mandate in the US relating to privacy. Deprecation Comment: Content moved to ActCode under _ActPrivacyLaw; use that instead.

OID: | 2.16.840.1.113883.5.1138 (for OID based terminology systems)

Source Resource | XML / JSON

This Code system is used in the following value sets:

* v3 Code System ActUSPrivacyLaw (A jurisdictional mandate in the US relating to privacy. Deprecation Comment: Content moved to ActCode under _ActPrivacyLaw; use that instead.)

4.3.2.1138.1 Code System Content

Release Date: 2016-11-11

Level | Code | Display | Definition

1 | _ActUSPrivacyLaw Deprecated | ActUSPrivacyLaw | Definition: A jurisdictional mandate in the U.S. relating to privacy. Usage Note: ActPrivacyLaw codes may be associated with an Act or a Role to indicate the legal provision to which the assignment of an Act.confidentialityCode or Role.confidentialtyCode complies. May be used to further specify rationale for assignment of other ActPrivacyPolicy codes in the US realm, e.g., ETH and 42CFRPart2 can be differentiated from ETH and Title38Part1.

2 | 42CFRPart2 Deprecated | 42 CFR Part2 | 42 CFR Part 2 stipulates the right of an individual who has applied for or been given diagnosis or treatment for alcohol or drug abuse at a federally assisted program. Definition: Non-disclosure of health information relating to health care paid for by a federally assisted substance abuse program without patient consent. Usage Note: May be associated with an Act or a Role to indicate the legal provision to which the assignment of an Act.confidentialityCode or Role.confidentialtyCode complies.

2 | CommonRule Deprecated | Common Rule | U.S. Federal regulations governing the protection of human subjects in research (codified at Subpart A of 45 CFR part 46) that has been adopted by 15 U.S. Federal departments and agencies in an effort to promote uniformity, understanding, and compliance with human subject protections. Existing regulations governing the protection of human subjects in Food and Drug Administration (FDA)-regulated research (21 CFR parts 50, 56, 312, and 812) are separate from the Common Rule but include similar requirements. Definition: U.S. federal laws governing research-related privacy policies. Usage Note: May be associated with an Act or a Role to indicate the legal provision to which the assignment of an Act.confidentialityCode or Role.confidentialtyCode complies.

2 | HIPAANOPP Deprecated | HIPAA notice of privacy practices | The U.S. Public Law 104-191 Health Insurance Portability and Accountability Act (HIPAA) Privacy Rule (45 CFR Part 164 Subpart E) permits access, use and disclosure of certain personal health information (PHI as defined under the law) for purposes of Treatment, Payment, and Operations, and requires that the provider ask that patients acknowledge the Provider's Notice of Privacy Practices as permitted conduct under the law. Definition: Notification of HIPAA Privacy Practices. Usage Note: May be associated with an Act or a Role to indicate the legal provision to which the assignment of an Act.confidentialityCode or Role.confidentialtyCode complies.

2 | HIPAAPsyNotes Deprecated | HIPAA psychotherapy notes | The U.S. Public Law 104-191 Health Insurance Portability and Accountability Act (HIPAA) Privacy Rule (45 CFR Part 164 Section 164.508) requires authorization for certain uses and disclosure of psychotherapy notes. Definition: Authorization that must be obtained for disclosure of psychotherapy notes. Usage Note: May be associated with an Act or a Role to indicate the legal provision to which the assignment of an Act.confidentialityCode or Role.confidentialtyCode complies.

2 | HIPAASelfPay Deprecated | HIPAA self-pay | Section 13405(a) of the Health Information Technology for Economic and Clinical Health Act (HITECH) stipulates the right of an individual to have disclosures regarding certain health care items or services for which the individual pays out of pocket in full restricted from a health plan. Definition: Non-disclosure of health information to a health plan relating to health care items or services for which an individual pays out of pocket in full. Usage Note: May be associated with an Act or a Role to indicate the legal provision to which the assignment of an Act.confidentialityCode or Role.confidentialtyCode complies.

2 | Title38Section7332 Deprecated | Title 38 Section 7332 | Title 38 Part 1-protected information may only be disclosed to a third party with the special written consent of the patient except where expressly authorized by 38 USC 7332. VA may disclose this information for specific purposes to: VA employees on a need to know basis - more restrictive than Privacy Act need to know; contractors who need the information in order to perform or fulfill the duties of the contract; and researchers who provide assurances that the information will not be identified in any report. This information may also be disclosed without consent where patient lacks decision-making capacity; in a medical emergency for the purpose of treating a condition which poses an immediate threat to the health of any individual and which requires immediate medical intervention; for eye, tissue, or organ donation purposes; and disclosure of HIV information for public health purposes. Definition: Title 38 Part 1 - Â§1.462 Confidentiality restrictions. (a) General. The patient records to which Â§Â§1.460 through 1.499 of this part apply may be disclosed or used only as permitted by these regulations and may not otherwise be disclosed or used in any civil, criminal, administrative, or legislative proceedings conducted by any Federal, State, or local authority. Any disclosure made under these regulations must be limited to that information which is necessary to carry out the purpose of the disclosure. SUBCHAPTER III--PROTECTION OF PATIENT RIGHTS Sec. 7332. Confidentiality of certain medical records (a)(1) Records of the identity, diagnosis, prognosis, or treatment of any patient or subject which are maintained in connection with the performance of any program or activity (including education, training, treatment, rehabilitation, or research) relating to drug abuse, alcoholism or alcohol abuse, infection with the human immunodeficiency virus, or sickle cell anemia which is carried out by or for the Department under this title shall, except as provided in subsections (e) and (f), be confidential, and (section 5701 of this title to the contrary notwithstanding) such records may be disclosed only for the purposes and under the circumstances expressly authorized under subsection (b). Usage Note: May be associated with an Act or a Role to indicate the legal provision to which the assignment of an Act.confidentialityCode or Role.confidentialtyCode complies.

4.3.2.10199 HL7 v3 Value Set ActMoodIntent

URL: https://hl7.org/fhir/STU3/v3/ActMoodIntent/vs.html

This page is part of the FHIR Specification (v3.0.2: STU 3). The current version which supercedes this version is 4.0.1. For a full list of available versions, see the Directory of published versions

Vocabulary Work Group | Maturity Level: N/A | External | Use Context: Any

This value set (http://hl7.org/fhir/ValueSet/v3-ActMoodIntent) is defined as part of HL7 v3. Related FHIR content: ActMoodIntent.

Summary

Defining URL: | http://hl7.org/fhir/ValueSet/v3-ActMoodIntent
Name: | ActMoodIntent
Definition: | An intention or plan to perform a service. Historical note: in previous RIM versions, the intent mood was captured as a separate class hierarchy, called Service_intent_or_order.
OID: | 2.16.840.1.113883.1.11.10199 (for OID based terminology systems)
Source Resource | XML / JSON

This value set is not currently used

4.3.2.10199.1 Content Logical Definition

This value set includes codes from the following code systems:

* Include codes from http://hl7.org/fhir/v3/ActMood where concept is-a INT

4.3.2.10199.2 Expansion

This expansion generated 19 Apr 2017

This value set contains 8 concepts

Expansion based on http://hl7.org/fhir/v3/ActMood version 2016-11-11

All codes from system http://hl7.org/fhir/v3/ActMood

Code | Display | Definition
INT | intent | Definition: An intention or plan for an act. >UsageNotes: The final outcome of the intent, the act that is intended to occur, is always an event. However the final outcome may be reached indirectly via steps through other intents, such as promise, permission request, or an appointment that may lead to an actual event to occur. Alternatively, the intended act may never occur.
_ActMoodDesire | desire | Definition: A desire to have an act occur.
_ActMoodActRequest | act request | Definition: A request (or order) for an act that is part of a defined request/fulfillment cycle. UsageNotes: Use of an HL7 defined request/fulfillment framework is not required to use this mood code.
ARQ | appointment request | Definition: A request act that is specialized for the appointment scheduling request/fulfillment cycle. An appointment request is fulfilled only and completely by an appointment (APT), i.e., all that the appointment request intends is to create an appointment (the actual act may well not happen if that is the professional decision during the appointment).
PERMRQ | permission request | Definition: A request for a permission to perform the act. Typically a payer (or possibly a supervisor) is being requested to give permission to perform the act. As opposed to the RQO, the requestee is not asked to perform or cause to perform the act but only to give the permission.
RQO | request | Definition: A request act that is specialized for an event request/fulfillment cycle. UsageNotes: The fulfillment cycle may involve intermediary fulfilling acts in moods such as PRMS, APT, or even another RQO before being fulfilled by the final event. UsageNotes: The concepts of a "request" and an "order" are viewed as different, because there is an implication of a mandate associated with order. In practice, however, this distinction has no general functional value in the inter-operation of health care computing. "Orders" are commonly refused for a variety of clinical and business reasons, and the notion of a "request" obligates the recipient (the fulfiller) to respond to the sender (the author). Indeed, in many regions, including Australia and Europe, the common term used is "request." Thus, the concept embodies both notions, as there is no useful distinction to be made. If a mandate is to be associated with a request, this will be embodied in the "local" business rules applied to the transactions. Should HL7 desire to provide a distinction between these in the future, the individual concepts could be added as specializations of this concept. The critical distinction here, is the difference between this concept and an "intent", of which it is a specialization. An intent involves decisions by a single party, the author. A request, however, involves decisions by two parties, the author and the fulfiller, with an obligation on the part of the fulfiller to respond to the request indicating that the fulfiller will indeed fulfill the request.
PRP | proposal | Definition: A suggestion that an act might be performed. Not an explicit request, and professional responsibility may or may not be present.
RMD | recommendation | Definition: A suggestion that an act should be performed with an acceptance of some degree of professional responsibility for the resulting act. Not an explicit request. . UsageNotes: Where there is no clear definition or applicable concept of "professional responsibilityâ€?, RMD becomes indistinguishable from PRP. .
PRMS | promise | Definition: A commitment to perform an act (may be either solicited or unsolicited). The committer becomes responsible to the other party for executing the act, and, as a consequence, the other party may rely on the first party to perform or cause to perform the act. UsageNotes: Commitments may be retracted or cancelled.
APT | appointment | Definition: An act that has been scheduled to be performed at a specific place and time.

4.3.2.10202 HL7 v3 Value Set ActMoodPredicate

URL: https://hl7.org/fhir/STU3/v3/ActMoodPredicate/vs.html

This page is part of the FHIR Specification (v3.0.2: STU 3). The current version which supercedes this version is 4.0.1. For a full list of available versions, see the Directory of published versions

Vocabulary Work Group | Maturity Level: N/A | External | Use Context: Any

This value set (http://hl7.org/fhir/ValueSet/v3-ActMoodPredicate) is defined as part of HL7 v3. Related FHIR content: ActMoodPredicate.

Summary

Defining URL: | http://hl7.org/fhir/ValueSet/v3-ActMoodPredicate
Name: | ActMoodPredicate
Definition: | Any of the above service moods (e.g., event, intent, or goal) can be turned into a predicate used as a criterion to express conditionals (or queries.) However, currently we allow only criteria on service events.
OID: | 2.16.840.1.113883.1.11.10202 (for OID based terminology systems)

Source Resource | XML / JSON

This value set is not currently used

4.3.2.10202.1 Content Logical Definition

This value set includes codes from the following code systems:

* Include codes from http://hl7.org/fhir/v3/ActMood where concept is-a _ActMoodPredicate

* Exclude these codes as defined in

http://hl7.org/fhir/v3/ActMood

Code | Display

_ActMoodPredicate | ActMoodPredicate | Definition: An act that expresses condition statements for other acts.

4.3.2.10202.2 Expansion

This expansion generated 19 Apr 2017

This value set contains 11 concepts

Expansion based on http://hl7.org/fhir/v3/ActMood version 2016-11-11

All codes from system http://hl7.org/fhir/v3/ActMood

Code | Display | Definition

CRT | criterion | Deprecation Comment: This concept This codes should no longer be used. Instead, set attribute Act.isCriterionInd to "true" and use the desired mood for your criterion. Definition: A condition that must be true for the source act to be considered.

EVN.CRT | event criterion | Deprecation Comment: This concept This codes should no longer be used. Instead, set attribute Act.isCriterionInd to "true" and use the desired mood for your criterion. Definition: A criterion (CRT) that has_match = an event (EVN).

GOL.CRT | goal criterion | A criterion expressed over goals (ActMood.GOL).

INT.CRT | intent criterion | A criterion expressed over intents (ActMood.INT).

PRMS.CRT | promise criterion | A criterion expressed over promises (ActMood.PRMS).

RQO.CRT | request criterion | A criterion expressed over requests or orders (ActMood.RQO).

RSK.CRT | risk criterion | A criterion expressed over risks (ActMood.RSK).

EXPEC | expectation | Definition: An act that is considered to have some noteworthy likelihood of occurring in the future (has_match = event). Examples:Prognosis of a condition, Expected date of discharge from hospital, patient will likely need an emergency decompression of the intracranial pressure by morning. UsageNotes:INT (intent) reflects a plan for the future, which is a declaration to do something. This contrasts with expectation, which is a prediction that something will happen in the future. GOL (goal) reflects a hope rather than a prediction. RSK (risk) reflects a potential negative event that may or may not be expected to happen.

GOL | Goal | Definition: An expectation that is considered to be desirable to occur in the future Examples:Target weight below 80Kg, Stop smoking, Regain ability to walk, goal is to administer thrombolytics to candidate patients presenting with acute myocardial infarction. UsageNotes: INT (intent) reflects a plan for the future, which is a declaration to do something. This contrasts with goal which doesn't represent an intention to act, merely a hope for an eventual result. A goal is distinct from the intended actions to reach that goal. "I will reduce the dose of drug x to 20mg" is an intent. "I hope to be able to get the patient to the point where I can reduce the dose of drug x to 20mg" is a goal. EXPEC (expectation) reflects a prediction rather than a hope. RSK (risk) reflects a potential negative event rather than a hope.

RSK | risk | Definition:An act that may occur in the future and which is regarded as undesirable Examples:Increased risk of DVT, at risk for sub-acute bacterial endocarditis. UsageNotes:Note: An observation in RSK mood expresses the undesirable act, and not the underlying risk factor. A risk factor that is present (e.g. obesity, smoking, etc) should be expressed in event mood. INT (intent) reflects a plan for the future, which is a declaration to do something. This contrasts with RSK (risk), which is the potential that something negative will occur that may or may not ever happen. GOL (goal) reflects a hope to achieve something. EXPEC (expectation) is the prediction of a positive or negative event. This contrasts with RSK (risk), which is the potential that something negative will occur that may or may not ever happen, and may not be expected to happen.

OPT | option | Definition: One of a set of acts that specify an option for the property values that the parent act may have. Typically used in definitions or orders to describe alternatives. An option can only be used as a group, that is, all assigned values must be used together. The actual mood of the act is the same as the parent act, and they must be linked by an actrelationship with type = OPTN.

4.3.2.10228 HL7 v3 Value Set ConfidentialityClassification

URL: https://hl7.org/fhir/STU3/v3/ConfidentialityClassification/vs.html

This page is part of the FHIR Specification (v3.0.2: STU 3). The current version which supercedes this version is 4.0.1. For a full list of available versions, see the Directory of published versions

Vocabulary Work Group | Maturity Level: N/A | External | Use Context: Any

This value set (http://hl7.org/fhir/ValueSet/v3-ConfidentialityClassification) is defined as part of HL7 v3. Related FHIR content: ConfidentialityClassification.

Summary

Defining URL: | http://hl7.org/fhir/ValueSet/v3-ConfidentialityClassification

Name: | ConfidentialityClassification

Definition: | Set of codes used to value Act.Confidentiality and Role.Confidentiality attribute in accordance with the definition for concept domain "Confidentiality".

OID: | 2.16.840.1.113883.1.11.10228 (for OID based terminology systems)

Source Resource | XML / JSON

This value set is used in the following places:

* Composition.confidentiality (Required)

* StructureDefinition ClinicalDocument: Composition.confidentiality ((Required))

4.3.2.10228.1 Content Logical Definition

This value set includes codes from the following code systems:

* Include these codes as defined in

http://hl7.org/fhir/v3/Confidentiality

Code | Display

U | unrestricted | Definition: Privacy metadata indicating that the information is not classified as sensitive. Examples: Includes publicly available information, e.g., business name, phone, email or physical address. Usage Note: This metadata indicates that the receiver has no obligation to consider additional policies when making access control decisions. Note that in some jurisdictions, personally identifiable information must be protected as confidential, so it would not be appropriate to assign a confidentiality code of "unrestricted" to that information even if it is publicly available.

L | low | Definition: Privacy metadata indicating that the information has been de-identified, and there are mitigating circumstances that prevent re-identification, which minimize risk of harm from unauthorized disclosure. The information requires protection to maintain low sensitivity. Examples: Includes anonymized, pseudonymized, or non-personally identifiable information such as HIPAA limited data sets. Map: No clear map to ISO 13606-4 Sensitivity Level (1) Care Management: RECORD_COMPONENTs that might need to be accessed by a wide range of administrative staff to manage the subject of care's access to health services. Usage Note: This metadata indicates the receiver may have an obligation to comply with a data use agreement.

M | moderate | Definition: Privacy metadata indicating moderately sensitive information, which presents moderate risk of harm if disclosed without authorization. Examples: Includes allergies of non-sensitive nature used inform food service; health information a patient authorizes to be used for marketing, released to a bank for a health credit card or savings account; or information in personal health record systems that are not governed under health privacy laws. Map: Partial Map to ISO 13606-4 Sensitivity Level (2) Clinical Management: Less sensitive RECORD_COMPONENTs that might need to be accessed by a wider range of personnel not all of whom are actively caring for the patient (e.g. radiology staff). Usage Note: This metadata indicates that the receiver may be obligated to comply with the receiver's terms of use or privacy policies.

N | normal | Definition: Privacy metadata indicating that the information is typical, non-stigmatizing health information, which presents typical risk of harm if disclosed without authorization. Examples: In the US, this includes what HIPAA identifies as the minimum necessary protected health information (PHI) given a covered purpose of use (treatment, payment, or operations). Includes typical, non-stigmatizing health information disclosed in an application for health, workers compensation, disability, or life insurance. Map: Partial Map to ISO 13606-4 Sensitivity Level (3) Clinical Care: Default for normal clinical care access (i.e. most clinical staff directly caring for the patient should be able to access nearly all of the EHR). Maps to normal confidentiality for treatment information but not to ancillary care, payment and operations. Usage Note: This metadata indicates that the receiver may be obligated to comply with applicable jurisdictional privacy law or disclosure authorization.

R | restricted | Privacy metadata indicating highly sensitive, potentially stigmatizing information, which presents a high risk to the information subject if disclosed without authorization. May be pre-empted by jurisdictional law, e.g., for public health reporting or emergency treatment. Examples: Includes information that is additionally protected such as sensitive conditions mental health, HIV, substance abuse, domestic violence, child abuse, genetic disease, and reproductive health; or sensitive demographic information such as a patient's standing as an employee or a celebrity. May be used to indicate proprietary or classified information that is not related to an individual, e.g., secret ingredients in a therapeutic substance; or the name of a manufacturer. Map: Partial Map to ISO 13606-4 Sensitivity Level (3) Clinical Care: Default for normal clinical care access (i.e. most clinical staff directly caring for the patient should be able to access nearly all of the EHR). Maps to normal confidentiality for treatment information but not to ancillary care, payment and operations.. Usage Note: This metadata indicates that the receiver may be obligated to comply with applicable, prevailing (default) jurisdictional privacy law or disclosure authorization..

V | very restricted | . Privacy metadata indicating that the information is extremely sensitive and likely stigmatizing health information that presents a very high risk if disclosed without authorization. This information must be kept in the highest confidence. Examples: Includes information about a victim of abuse, patient requested information sensitivity, and taboo subjects relating to health status that must be discussed with the patient by an attending provider before sharing with the patient. May also include information held under â€œlegal lockâ€? or attorney-client privilege Map: This metadata indicates that the receiver may not disclose this information except as directed by the information custodian, who may be the information subject. Usage Note: This metadata indicates that the receiver may not disclose this information except as directed by the information custodian, who may be the information subject.

4.3.2.10248 HL7 v3 Value Set ParticipationPhysicalPerformer

URL: https://hl7.org/fhir/STU3/v3/ParticipationPhysicalPerformer/vs.html

This page is part of the FHIR Specification (v3.0.2: STU 3). The current version which supercedes this version is 4.0.1. For a full list of available versions, see the Directory of published versions

Vocabulary Work Group | Maturity Level: N/A | External | Use Context: Any

This value set (http://hl7.org/fhir/ValueSet/v3-ParticipationPhysicalPerformer) is defined as part of HL7 v3. Related FHIR content: ParticipationPhysicalPerformer.

Summary

Defining URL: | http://hl7.org/fhir/ValueSet/v3-ParticipationPhysicalPerformer

Name: | ParticipationPhysicalPerformer

Definition: | A person who actually and principally carries out the action. Need not be the principal responsible actor, e.g. a surgery resident operating under supervision of attending surgeon, and may be the patient in self-care, e.g. fingerstick blood sugar. The traditional order filler is a performer. This information should accompany every service event.

OID: | 2.16.840.1.113883.1.11.10248 (for OID based terminology systems)

Source Resource | XML / JSON

This value set is not currently used

4.3.2.10248.1 Content Logical Definition

This value set includes codes from the following code systems:

* Include codes from http://hl7.org/fhir/v3/ParticipationType where concept is-a PRF

4.3.2.10248.2 Expansion

This expansion generated 19 Apr 2017

This value set contains 4 concepts

Expansion based on http://hl7.org/fhir/v3/ParticipationType version 2016-11-11

All codes from system http://hl7.org/fhir/v3/ParticipationType

Code | Display | Definition

PRF | performer | Definition: A person, non-person living subject, organization or device that who actually and principally carries out the action. Device should only be assigned as a performer in circumstances where the device is performing independent of human intervention. Need not be the principal responsible actor. Exampe: A surgery resident operating under supervision of attending surgeon, a search and rescue dog locating survivors, an electronic laboratory analyzer or the laboratory discipline requested to perform a laboratory test. The performer may also be the patient in self-care, e.g. fingerstick blood sugar. The traditional order filler is a performer. This information should accompany every service event. Note: that existing HL7 designs assign an organization as the playing entity of the Role that is the performer. These designs should be revised in subsequent releases to make this the scooping entity for the role involved.

DIST | distributor | Distributes material used in or generated during the act.

PPRF | primary performer | The principal or primary performer of the act.

SPRF | secondary performer | A person assisting in an act through his substantial presence and involvement This includes: assistants, technicians, associates, or whatever the job titles may be.

4.3.2.10251 HL7 v3 Value Set ParticipationInformationGenerator

URL: https://hl7.org/fhir/STU3/v3/ParticipationInformationGenerator/vs.html

This page is part of the FHIR Specification (v3.0.2: STU 3). The current version which supercedes this version is 4.0.1. For a full list of available versions, see the Directory of published versions

Vocabulary Work Group | Maturity Level: N/A | External | Use Context: Any

This value set (http://hl7.org/fhir/ValueSet/v3-ParticipationInformationGenerator) is defined as part of HL7 v3. Related FHIR content: ParticipationInformationGenerator.

Summary

Defining URL: | http://hl7.org/fhir/ValueSet/v3-ParticipationInformationGenerator

Name: | ParticipationInformationGenerator

Definition: | Parties that may or should contribute or have contributed information to the Act. Such information includes information leading to the decision to perform the Act and how to perform the Act (e.g., consultant), information that the Act itself seeks to reveal (e.g., informant of clinical history), or information about what Act was performed (e.g., informant witness).

OID: | 2.16.840.1.113883.1.11.10251 (for OID based terminology systems)

Source Resource | XML / JSON

This value set is not currently used

4.3.2.10251.1 Content Logical Definition

This value set includes codes from the following code systems:

* Include codes from http://hl7.org/fhir/v3/ParticipationType where concept is-a _ParticipationInformationGenerator

* Exclude these codes as defined in

http://hl7.org/fhir/v3/ParticipationType

Code | Display

_ParticipationInformationGenerator | ParticipationInformationGenerator | Parties that may or should contribute or have contributed information to the Act. Such information includes information leading to the decision to perform the Act and how to perform the Act (e.g., consultant), information that the Act itself seeks to reveal (e.g., informant of clinical history), or information about what Act was performed (e.g., informant witness).

4.3.2.10251.2 Expansion

This expansion generated 19 Apr 2017

This value set contains 5 concepts

Expansion based on http://hl7.org/fhir/v3/ParticipationType version 2016-11-11

All codes from system http://hl7.org/fhir/v3/ParticipationType

Code | Display | Definition

AUT | author (originator) | Definition: A party that originates the Act and therefore has responsibility for the information given in the Act and ownership of this Act. Example: the report writer, the person writing the act definition, the guideline author, the placer of an order, the EKG cart (device) creating a report etc. Every Act should have an author. Authorship is regardless of mood always actual authorship. Examples of such policies might include: The author and anyone they explicitly delegate may update the report; All administrators within the same clinic may cancel and reschedule appointments created by other administrators within that clinic; A party that is neither an author nor a party who is extended authorship maintenance rights by policy, may only amend, reverse, override, replace, or follow up in other ways on this Act, whereby the Act remains intact and is linked to another Act authored by that other party.

INF | informant | A source of reported information (e.g., a next of kin who answers questions about the patient's history). For history questions, the patient is logically an informant, yet the informant of history questions is implicitly the subject.

TRANS | Transcriber | An entity entering the data into the originating system. The data entry entity is collected optionally for internal quality control purposes. This includes the transcriptionist for dictated text transcribed into electronic form.

ENT | data entry person | A person entering the data into the originating system. The data entry person is collected optionally for internal quality control purposes. This includes the transcriptionist for dictated text.

WIT | witness | Only with service events. A person witnessing the action happening without doing anything. A witness is not necessarily aware, much less approves of anything stated in the service event. Example for a witness is students watching an operation or an advanced directive witness.

4.3.2.10259 HL7 v3 Value Set ParticipationVerifier

URL: https://hl7.org/fhir/STU3/v3/ParticipationVerifier/vs.html

This page is part of the FHIR Specification (v3.0.2: STU 3). The current version which supercedes this version is 4.0.1. For a full list of available versions, see the Directory of published versions

Vocabulary Work Group | Maturity Level: N/A | External | Use Context: Any

This value set (http://hl7.org/fhir/ValueSet/v3-ParticipationVerifier) is defined as part of HL7 v3. Related FHIR content: ParticipationVerifier.

Summary

Defining URL: | http://hl7.org/fhir/ValueSet/v3-ParticipationVerifier
Name: | ParticipationVerifier
Definition: | A person who verifies the correctness and appropriateness of the service (plan, order, event, etc.) and hence takes on accountability.
OID: | 2.16.840.1.113883.1.11.10259 (for OID based terminology systems)
Source Resource | XML / JSON

This value set is not currently used

4.3.2.10259.1 Content Logical Definition

This value set includes codes from the following code systems:

* Include codes from http://hl7.org/fhir/v3/ParticipationType where concept is-a VRF

4.3.2.10259.2 Expansion

This expansion generated 19 Apr 2017

This value set contains 3 concepts

Expansion based on http://hl7.org/fhir/v3/ParticipationType version 2016-11-11

All codes from system http://hl7.org/fhir/v3/ParticipationType

Code | Display | Definition
VRF | verifier | A person who verifies the correctness and appropriateness of the service (plan, order, event, etc.) and hence takes on accountability.
AUTHEN | authenticator | A verifier who attests to the accuracy of an act, but who does not have privileges to legally authenticate the act. An example would be a resident physician who sees a patient and dictates a note, then later signs it. Their signature constitutes an authentication.
LA | legal authenticator | A verifier who legally authenticates the accuracy of an act. An example would be a staff physician who sees a patient and dictates a note, then later signs it. Their signature constitutes a legal authentication.

4.3.2.10286 HL7 v3 Value Set ParticipationTargetDirect

URL: https://hl7.org/fhir/STU3/v3/ParticipationTargetDirect/vs.html

This page is part of the FHIR Specification (v3.0.2: STU 3). The current version which supercedes this version is 4.0.1. For a full list of available versions, see the Directory of published versions

Vocabulary Work Group | Maturity Level: N/A | External | Use Context: Any

This value set (http://hl7.org/fhir/ValueSet/v3-ParticipationTargetDirect) is defined as part of HL7 v3. Related FHIR content: ParticipationTargetDirect.

Summary

Defining URL: | http://hl7.org/fhir/ValueSet/v3-ParticipationTargetDirect
Name: | ParticipationTargetDirect
Definition: | Target that is substantially present in the service and which is directly affected by the service action (includes consumed material, devices, etc.).
OID: | 2.16.840.1.113883.1.11.10286 (for OID based terminology systems)
Source Resource | XML / JSON

This value set is not currently used

4.3.2.10286.1 Content Logical Definition

This value set includes codes from the following code systems:

* Include codes from http://hl7.org/fhir/v3/ParticipationType where concept is-a DIR

4.3.2.10286.2 Expansion

This expansion generated 19 Apr 2017

This value set contains 17 concepts

Expansion based on http://hl7.org/fhir/v3/ParticipationType version 2016-11-11

All codes from system http://hl7.org/fhir/v3/ParticipationType

Code | Display | Definition
DIR | direct target | Target participant that is substantially present in the act and which is directly involved in the action (includes consumed material, devices, etc.).

ALY | analyte | The target of an Observation action. Links an observation to a Role whose player is the substance or most specific component entity (material, micro-organism, etc.) being measured within the subject. Examples: A "plasma porcelain substance concentration" has analyte a Role with player substance Entity "porcelain". UsageNotes: The Role that this participation connects to may be any Role whose player is that substance measured. Very often, the scoper may indicate the system in which the component is being measured. E.g., for "plasma porcelain" the scoper could be "Plasma".

BBY | baby | In an obstetric service, the baby.

CAT | catalyst | The catalyst of a chemical reaction, such as an enzyme or a platinum surface. In biochemical reactions, connects the enzyme with the molecular interaction

CSM | consumable | Participant material that is taken up, diminished, altered, or disappears in the act.

TPA | therapeutic agent | Something incorporated in the subject of a therapy service to achieve a physiologic effect (e.g., heal, relieve, provoke a condition, etc.) on the subject. In an administration service the therapeutic agent is a consumable, in a preparation or dispense service, it is a product. Thus, consumable or product must be specified in accordance with the kind of service.

DEV | device | Participant used in performing the act without being substantially affected by the act (i.e. durable or inert with respect to that particular service). Examples: monitoring equipment, tools, but also access/drainage lines, prostheses, pace maker, etc.

NRD | non-reuseable device | A device that changes ownership due to the service, e.g., a pacemaker, a prosthesis, an insulin injection equipment (pen), etc. Such material may need to be restocked after he service.

RDV | reusable device | A device that does not change ownership due to the service, i.e., a surgical instrument or tool or an endoscope. The distinction between reuseable and non-reuseable must be made in order to know whether material must be re-stocked.

DON | donor | In some organ transplantation services and rarely in transfusion services a donor will be a target participant in the service. However, in most cases transplantation is decomposed in three services: explantation, transport, and implantation. The identity of the donor (recipient) is often irrelevant for the explantation (implantation) service.

EXPAGNT | ExposureAgent | Description: The entity playing the associated role is the physical (including energy), chemical or biological substance that is participating in the exposure. For example in communicable diseases, the associated playing entity is the disease causing pathogen.

EXPART | ExposureParticipation | Description:Direct participation in an exposure act where it is unknown that the participant is the source or subject of the exposure. If the participant is known to be the contact of an exposure then the SBJ participation type should be used. If the participant is known to be the source then the EXSRC participation type should be used.

EXPTRGT | ExposureTarget | Description: The entity playing the associated role is the target (contact) of exposure.

EXSRC | ExposureSource | Description:The entity playing the associated role is the source of exposure.

PRD | product | Participant material that is brought forth (produced) in the act (e.g., specimen in a specimen collection, access or drainage in a placement service, medication package in a dispense service). It does not matter whether the material produced had existence prior to the service, or whether it is created in the service (e.g., in supply services the product is taken from a stock).

SBJ | subject | The principle target on which the action happens. Examples: The patient in physical examination, a specimen in a lab observation. May also be a patient's family member (teaching) or a device or room (cleaning, disinfecting, housekeeping). UsageNotes: Not all direct targets are subjects. Consumables and devices used as tools for an act are not subjects. However, a device may be a subject of a maintenance action.

SPC | specimen | The subject of non-clinical (e.g. laboratory) observation services is a specimen.

4.3.2.10302 HL7 v3 Value Set ParticipationTargetLocation

URL: https://hl7.org/fhir/STU3/v3/ParticipationTargetLocation/vs.html

This page is part of the FHIR Specification (v3.0.2: STU 3). The current version which supercedes this version is 4.0.1. For a full list of available versions, see the Directory of published versions

Vocabulary Work Group | Maturity Level: N/A | External | Use Context: Any

This value set (http://hl7.org/fhir/ValueSet/v3-ParticipationTargetLocation) is defined as part of HL7 v3. Related FHIR content: ParticipationTargetLocation.

Summary

Defining URL: | http://hl7.org/fhir/ValueSet/v3-ParticipationTargetLocation

Name: | ParticipationTargetLocation

Definition: | The facility where the service is done. May be a static building (or room therein) or a moving location (e.g., ambulance, helicopter, aircraft, train, truck, ship, etc.)

OID: | 2.16.840.1.113883.1.11.10302 (for OID based terminology systems)

Source Resource | XML / JSON

This value set is not currently used

4.3.2.10302.1 Content Logical Definition

This value set includes codes from the following code systems:

* Include codes from http://hl7.org/fhir/v3/ParticipationType where concept is-a LOC

4.3.2.10302.2 Expansion

This expansion generated 19 Apr 2017

This value set contains 6 concepts

Expansion based on http://hl7.org/fhir/v3/ParticipationType version 2016-11-11

All codes from system http://hl7.org/fhir/v3/ParticipationType

Code | Display | Definition

LOC | location | The facility where the service is done. May be a static building (or room therein) or a moving location (e.g., ambulance, helicopter, aircraft, train, truck, ship, etc.)

DST | destination | The destination for services. May be a static building (or room therein) or a movable facility (e.g., ship).

ELOC | entry location | A location where data about an Act was entered.

ORG | origin | The location of origin for services. May be a static building (or room therein) or a movable facility (e.g., ship).

RML | remote | Some services take place at multiple concurrent locations (e.g., telemedicine, telephone consultation). The location where the principal performing actor is located is taken as the primary location (LOC) while the other location(s) are considered "remote."
VIA | via | For services, an intermediate location that specifies a path between origin an destination.

4.3.2.10318 HL7 v3 Value Set ActRelationshipHasComponent

URL: https://hl7.org/fhir/STU3/v3/ActRelationshipHasComponent/vs.html

This page is part of the FHIR Specification (v3.0.2: STU 3). The current version which supercedes this version is 4.0.1. For a full list of available versions, see the Directory of published versions

Vocabulary Work Group | Maturity Level: N/A | External | Use Context: Any

This value set (http://hl7.org/fhir/ValueSet/v3-ActRelationshipHasComponent) is defined as part of HL7 v3. Related FHIR content: ActRelationshipHasComponent.

Summary

Defining URL: | http://hl7.org/fhir/ValueSet/v3-ActRelationshipHasComponent
Name: | ActRelationshipHasComponent
Definition: | A collection of sub-services as steps or subtasks performed for the source service. Services may be performed sequentially or concurrently.
OID: | 2.16.840.1.113883.1.11.10318 (for OID based terminology systems)
Source Resource | XML / JSON

This value set is not currently used

4.3.2.10318.1 Content Logical Definition

This value set includes codes from the following code systems:

* Include codes from http://hl7.org/fhir/v3/ActRelationshipType where concept is-a COMP

4.3.2.10318.2 Expansion

This expansion generated 19 Apr 2017

This value set contains 7 concepts

Expansion based on http://hl7.org/fhir/v3/ActRelationshipType version 2016-11-11

All codes from system http://hl7.org/fhir/v3/ActRelationshipType

Code | Display | Definition
COMP | has component | The target act is a component of the source act, with no semantics regarding composition or aggregation implied.
CTRLV | has control variable | A relationship from an Act to a Control Variable. For example, if a Device makes an Observation, this relates the Observation to its Control Variables documenting the device's settings that influenced the observation.
MBR | has member | The target Acts are aggregated by the source Act. Target Acts may have independent existence, participate in multiple ActRelationships, and do not contribute to the meaning of the source. UsageNotes: This explicitly represents the conventional notion of aggregation. The target Act is part of a collection of Acts (no implication is made of cardinality, a source of Acts may contain zero, one, or more member target Acts). It is expected that this will be primarily used with _ActClassRecordOrganizer, BATTERY, and LIST
STEP | has step | A collection of sub-services as steps or subtasks performed for the source service. Services may be performed sequentially or concurrently. UsageNotes: Sequence of steps may be indicated by use of _ActRelationshipTemporallyPertains, as well as via ActRelationship.sequenceNumber, ActRelationship.pauseQuantity, Target.priorityCode. OpenIssue: Need Additional guidelines on when each approach should be used.
ARR | arrival | The relationship that links to a Transportation Act (target) from another Act (source) indicating that the subject of the source Act entered into the source Act by means of the target Transportation act.
DEP | departure | The relationship that links to a Transportation Act (target) from another Act (source) indicating that the subject of the source Act departed from the source Act by means of the target Transportation act.
PART | has part | The source Act is a composite of the target Acts. The target Acts do not have an existence independent of the source Act. UsageNote: In UML 1.1, this is a "composition" defined as: "A form of aggregation with strong ownership and coincident lifetime as part of the whole. Parts with non-fixed multiplicity may be created after the composite itself, but once created they live and die with it (i.e., they share lifetimes). Such parts can also be explicitly removed before the death of the composite. Composition may be recursive."

4.3.2.10329 HL7 v3 Value Set ActRelationshipPertains

URL: https://hl7.org/fhir/STU3/v3/ActRelationshipPertains/vs.html

This page is part of the FHIR Specification (v3.0.2: STU 3). The current version which supercedes this version is 4.0.1. For a full list of available versions, see the Directory of published versions

Vocabulary Work Group | Maturity Level: N/A | External | Use Context: Any

This value set (http://hl7.org/fhir/ValueSet/v3-ActRelationshipPertains) is defined as part of HL7 v3. Related FHIR content: ActRelationshipPertains.

Summary

Defining URL: | http://hl7.org/fhir/ValueSet/v3-ActRelationshipPertains
Name: | ActRelationshipPertains
Definition: | This is a very unspecific relationship from one item of clinical information to another. It does not judge about the role the pertinent information plays.
OID: | 2.16.840.1.113883.1.11.10329 (for OID based terminology systems)
Source Resource | XML / JSON

This value set is not currently used

4.3.2.10329.1 Content Logical Definition

This value set includes codes from the following code systems:

* Include codes from http://hl7.org/fhir/v3/ActRelationshipType where concept is-a PERT

4.3.2.10329.2 Expansion

This expansion generated 19 Apr 2017

This value set contains 1 concepts

Expansion based on http://hl7.org/fhir/v3/ActRelationshipType version 2016-11-11

All codes from system http://hl7.org/fhir/v3/ActRelationshipType

Code	Display	Definition
PERT	has pertinent information	This is a very unspecific relationship from one item of clinical information to another. It does not judge about the role the pertinent information plays.

4.3.2.10342 HL7 v3 Value Set ActRelationshipFulfills

URL: https://hl7.org/fhir/STU3/v3/ActRelationshipFulfills/vs.html

This page is part of the FHIR Specification (v3.0.2: STU 3). The current version which supercedes this version is 4.0.1. For a full list of available versions, see the Directory of published versions

Vocabulary Work Group | Maturity Level: N/A | External | Use Context: Any

This value set (http://hl7.org/fhir/ValueSet/v3-ActRelationshipFulfills) is defined as part of HL7 v3. Related FHIR content: ActRelationshipFulfills.

Summary

Defining URL: | http://hl7.org/fhir/ValueSet/v3-ActRelationshipFulfills
Name: | ActRelationshipFulfills
Definition: | The source act fulfills (in whole or in part) the target act. Source act must be in a mood equal or more actual than the target act.
OID: | 2.16.840.1.113883.1.11.10342 (for OID based terminology systems)
Source Resource | XML / JSON

This value set is not currently used

4.3.2.10342.1 Content Logical Definition

This value set includes codes from the following code systems:

* Include codes from http://hl7.org/fhir/v3/ActRelationshipType where concept is-a FLFS

4.3.2.10342.2 Expansion

This expansion generated 19 Apr 2017

This value set contains 4 concepts

Expansion based on http://hl7.org/fhir/v3/ActRelationshipType version 2016-11-11

All codes from system http://hl7.org/fhir/v3/ActRelationshipType

Code	Display	Definition
FLFS	fulfills	The source act fulfills (in whole or in part) the target act. Source act must be in a mood equal or more actual than the target act.
OCCR	occurrence	The source act is a single occurrence of a repeatable target act. The source and target act can be in any mood on the "completion track" but the source act must be as far as or further along the track than the target act (i.e., the occurrence of an intent can be an event but not vice versa).
OREF	references order	Relates either an appointment request or an appointment to the order for the service being scheduled.
SCH	schedules request	Associates a specific time (and associated resources) with a scheduling request or other intent.

4.3.2.10416 HL7 v3 Value Set RoleClassRelationshipFormal

URL: https://hl7.org/fhir/STU3/v3/RoleClassRelationshipFormal/vs.html

This page is part of the FHIR Specification (v3.0.2: STU 3). The current version which supercedes this version is 4.0.1. For a full list of available versions, see the Directory of published versions

Vocabulary Work Group | Maturity Level: N/A | External | Use Context: Any

This value set (http://hl7.org/fhir/ValueSet/v3-RoleClassRelationshipFormal) is defined as part of HL7 v3. Related FHIR content: RoleClassRelationshipFormal.

Summary

Defining URL: | http://hl7.org/fhir/ValueSet/v3-RoleClassRelationshipFormal
Name: | RoleClassRelationshipFormal
Definition: | A relationship between two entities that is formally recognized, frequently by a contract or similar agreement.
OID: | 2.16.840.1.113883.1.11.10416 (for OID based terminology systems)
Source Resource | XML / JSON

This value set is not currently used

4.3.2.10416.1 Content Logical Definition

This value set includes codes from the following code systems:

* Include codes from http://hl7.org/fhir/v3/RoleClass where concept is-a _RoleClassRelationshipFormal

* Exclude these codes as defined in

http://hl7.org/fhir/v3/RoleClass

Code | Display

_RoleClassRelationshipFormal | RoleClassRelationshipFormal | A relationship between two entities that is formally recognized, frequently by a contract or similar agreement.

4.3.2.10416.2 Expansion

This expansion generated 19 Apr 2017

This value set contains 36 concepts

Expansion based on http://hl7.org/fhir/v3/RoleClass version 2016-11-11

All codes from system http://hl7.org/fhir/v3/RoleClass

Code | Display | Definition

AFFL | affiliate | Player of the Affiliate role has a business/professional relationship with scoper. Player and scoper may be persons or organization. The Affiliate relationship does not imply membership in a group, nor does it exist for resource scheduling purposes. Example: A healthcare provider is affiliated with another provider as a business associate.

AGNT | agent | An entity (player) that acts or is authorized to act on behalf of another entity (scoper).

ASSIGNED | assigned entity | An agent role in which the agent is an Entity acting in the employ of an organization. The focus is on functional role on behalf of the organization, unlike the Employee role where the focus is on the 'Human Resources' relationship between the employee and the organization.

COMPAR | commissioning party | An Entity that is authorized to issue or instantiate permissions, privileges, credentials or other formal/legal authorizations.

SGNOFF | signing authority or officer | The role of a person (player) who is the officer or signature authority for of a scoping entity, usually an organization (scoper).

CON | contact | A person or an organization (player) which provides or receives information regarding another entity (scoper). Examples; patient NOK and emergency contacts; guarantor contact; employer contact.

ECON | emergency contact | An entity to be contacted in the event of an emergency.

NOK | next of kin | An individual designated for notification as the next of kin for a given entity.

GUARD | guardian | Guardian of a ward

CIT | citizen | Citizen of apolitical entity

COVPTY | covered party | A role class played by a person who receives benefit coverage under the terms of a particular insurance policy. The underwriter of that policy is the scoping entity. The covered party receives coverage because of some contractual or other relationship with the holder of that policy. Discussion:This reason for coverage is captured in 'Role.code' and a relationship link with type code of indirect authority should be included using the policy holder role as the source, and the covered party role as the target. Note that a particular policy may cover several individuals one of whom may be, but need not be, the policy holder. Thus the notion of covered party is a role that is distinct from that of the policy holder.

CLAIM | claimant | Description: A role played by a party making a claim for coverage under a policy or program. A claimant must be either a person or organization, or a group of persons or organizations. A claimant is not a named insured or a program eligible. Discussion: With respect to liability insurance such as property and casualty insurance, a claimant must file a claim requesting indemnification for a loss that the claimant considers covered under the policy of a named insured. The claims adjuster for the policy underwriter will review the claim to determine whether the loss meets the benefit coverage criteria under a policy, and base any indemnification or coverage payment on that review. If a third party is liable in whole or part for the loss, the underwriter may pursue third party liability recovery. A claimant may be involved in civil or criminal legal proceedings involving claims against a defendant party that is indemnified by an insurance policy or to protest the finding of a claims adjustor. With respect to life insurance, a beneficiary designated by a named insured becomes a claimant of the proceeds of coverage, as in the case of a life insurance policy. However, a claimant for coverage under life insurance is not necessarily a designated beneficiary. Note: A claimant is not a named insured. However, a named insured may make a claim under a policy, e.g., an insured driver may make a claim for an injury under his or her comprehensive automobile insurance policy. Similarly, a program eligible may make a claim under program, e.g., an unemployed worker may claim benefits under an unemployment insurance program, but parties playing these covered party role classes are not, for purposes of this vocabulary and in an effort to clearly distinguish role classes, considered claimants. In the case of a named insured making a claim, a role type code INSCLM (insured claimant) subtypes the class to indicate that either a named insured or an individual insured has filed a claim for a loss. In the case of a program eligible, a role type code INJWKR (injured worker) subtypes the class to indicate that the covered party in a workers compensation program is an injured worker, and as such, has filed a "claim" under the program for benefits. Likewise, a covered role type code UNEMP (unemployed worker) subtypes the program eligible class to indicate that the covered party in an unemployment insurance program has filed a claim for unemployment benefits. Example: A claimant under automobile policy that is not the named insured.

NAMED | named insured | Description: A role played by a party to an insurance policy to which the insurer agrees to indemnify for losses, provides benefits for, or renders services. A named insured may be either a person, non-person living subject, or an organization, or a group of persons, non-person living subjects, or organizations. Discussion: The coded concept NAMED should not be used where a more specific child concept in this Specializable value set applies. In some cases, the named insured may not be the policy holder, e.g., where a policy holder purchases life insurance policy in which another party is the named insured and the policy holder is the beneficiary of the policy. Note: The party playing the role of a named insured is not a claimant in the sense conveyed by the RoleClassCoveredParty CLAIM (claimant). However, a named insured may make a claim under a policy, e.g., e.g., a party that is the named insured and policy holder under a comprehensive automobile insurance policy may become the claimant for coverage under that policy e.g., if injured in an automobile accident and there is no liable third party. In the case of a named insured making a claim, a role type code INSCLM (insured claimant) subtypes the class to indicate that a named insured has filed a claim for a loss. Example: The named insured under a comprehensive automobile, disability, or property and casualty policy that is the named insured and may or may not be the policy holder.

DEPEN | dependent | Description: A role played by a person covered under a policy or program based on an association with a subscriber, which is recognized by the policy holder. Note: The party playing the role of a dependent is not a claimant in the sense conveyed by the RoleClassCoveredParty CLAIM (claimant). However, a dependent may make a claim under a policy, e.g., a dependent under a health insurance

policy may become the claimant for coverage under that policy for wellness examines or if injured and there is no liable third party. In the case of a dependent making a claim, a role type code INSCLM (insured claimant) subtypes the class to indicate that the dependent has filed a claim for services covered under the health insurance policy. Example: The dependent has an association with the subscriber such as a financial dependency or personal relationship such as that of a spouse, or a natural or adopted child. The policy holder may be required by law to recognize certain associations or may have discretion about the associations. For example, a policy holder may dictate the criteria for the dependent status of adult children who are students, such as requiring full time enrollment, or may recognize domestic partners as dependents. Under certain circumstances, the dependent may be under the indirect authority of a responsible party acting as a surrogate for the subscriber, for example, if the subscriber is differently abled or deceased, a guardian ad Lidem or estate executor may be appointed to assume the subscriberaTMs legal standing in the relationship with the dependent.

INDIV | individual | Description: A role played by a party covered under a policy as the policy holder. An individual may be either a person or an organization. Note: The party playing the role of an individual insured is not a claimant in the sense conveyed by the RoleClassCoveredParty CLAIM (claimant). However, a named insured may make a claim under a policy, e.g., a party that is the named insured and policy holder under a comprehensive automobile insurance policy may become the claimant for coverage under that policy if injured in an automobile accident and there is no liable third party. In the case of an individual insured making a claim, a role type code INSCLM (insured claimant) subtypes the class to indicate that an individual insured has filed a claim for a loss. Example: The individual insured under a comprehensive automobile, disability, or property and casualty policy that is the policy holder.

SUBSCR | subscriber | Description: A role played by a person covered under a policy based on association with a sponsor who is the policy holder, and whose association may provide for the eligibility of dependents for coverage. Discussion: The policy holder holds the contract with the policy or program underwriter. The subscriber holds a certificate of coverage under the contract. In legal proceedings concerning the policy or program, the terms of the contract takes precedence over the terms of the certificate of coverage if there are any inconsistencies. Note: The party playing the role of a subscriber is not a claimant in the sense conveyed by the RoleClassCoveredParty CLAIM (claimant). However, a subscriber may make a claim under a policy, e.g., a subscriber under a health insurance policy may become the claimant for coverage under that policy for wellness examines or if injured and there is no liable third party. In the case of a subscriber making a claim, a role type code INSCLM (insured claimant) subtypes the class to indicate that the subscriber has filed a claim for services covered under the health insurance policy. Example: An employee or a member of an association.

PROG | program eligible | Description: A role played by a party that meets the eligibility criteria for coverage under a program. A program eligible may be either a person, non-person living subject, or an organization, or a group of persons, non-person living subjects, or organizations. Discussion: A program as typically government administered coverage for parties determined eligible under the terms of the program. Note: The party playing a program eligible is not a claimant in the sense conveyed by the RoleClassCoveredParty CLAIM (claimant). However a program eligible may make a claim under program, e.g., an unemployed worker may claim benefits under an unemployment insurance program, but parties playing these covered party role classes are not, for purposes of this vocabulary and in an effort to clearly distinguish role classes, considered claimants. In the case of a program eligible, a role type code INJWKR (injured worker) subtypes the class to indicate that the covered party in a workers compensation program is an injured worker, and as such, has filed a "claim" under the program for benefits. Likewise, a covered role type code UNEMP (unemployed worker) subtypes the program eligible class to indicate that the covered party in an unemployment insurance program has filed a claim for unemployment benefits. Example: A party meeting eligibility criteria related to health or financial status, e.g., in the U.S., persons meeting health, demographic, or financial criteria established by state and federal law are eligible for Medicaid.

CRINV | clinical research investigator | A role played by a provider, always a person, who has agency authority from a Clinical Research Sponsor to direct the conduct of a clinical research trial or study on behalf of the sponsor.

CRSPNSR | clinical research sponsor | A role played by an entity, usually an organization, that is the sponsor of a clinical research trial or study. The sponsor commissions the study, bears the expenses, is responsible for satisfying all legal requirements concerning subject safety and privacy, and is generally responsible for collection, storage and analysis of the data generated during the trial. No scoper is necessary, as a clinical research sponsor undertakes the role on its own authority and declaration. Clinical research sponsors are usually educational or other research organizations, government agencies or biopharmaceutical companies.

EMP | employee | A relationship between a person or organization and a person or organization formed for the purpose of exchanging work for compensation. The purpose of the role is to identify the type of relationship the employee has to the employer, rather than the nature of the work actually performed. (Contrast with AssignedEntity.)

MIL | military person | A role played by a member of a military service. Scoper is the military service (e.g. Army, Navy, Air Force, etc.) or, more specifically, the unit (e.g. Company C, 3rd Battalion, 4th Division, etc.)

GUAR | guarantor | A person or organization (player) that serves as a financial guarantor for another person or organization (scoper).

INVSBJ | Investigation Subject | An entity that is the subject of an investigation. This role is scoped by the party responsible for the investigation.

CASEBJ | Case Subject | A person, non-person living subject, or place that is the subject of an investigation related to a notifiable condition (health circumstance that is reportable within the applicable public health jurisdiction)

RESBJ | research subject | Definition:Specifies the administrative functionality within a formal experimental design for which the ResearchSubject role was established. Examples: Screening - role is used for pre-enrollment evaluation portion of the design; enrolled - role is used for subjects admitted to the experimental portion of the design.

LIC | licensed entity | A relationship in which the scoper certifies the player (e. g. a medical care giver, a medical device or a provider organization) to perform certain activities that fall under the jurisdiction of the scoper (e.g., a health authority licensing healthcare providers, a medical quality authority certifying healthcare professionals).

NOT | notary public | notary public

PROV | healthcare provider | An Entity (player) that is authorized to provide health care services by some authorizing agency (scoper).

PAT | patient | A Role of a LivingSubject (player) as an actual or potential recipient of health care services from a healthcare provider organization (scoper). Usage Note: Communication about relationships between patients and specific healthcare practitioners (people) is not done via scoper. Instead this is generally done using the CareProvision act. This allows linkage between patient and a particular healthcare practitioner role and also allows description of the type of care involved in the relationship.

PAYEE | payee | The role of an organization or individual designated to receive payment for a claim against a particular coverage. The scoping entity is the organization that is the submitter of the invoice in question.

PAYOR | invoice payor | The role of an organization that undertakes to accept claims invoices, assess the coverage or payments due for those invoices and pay to the designated payees for those invoices. This role may be either the underwriter or a third-party organization authorized by the underwriter. The scoping entity is the organization that underwrites the claimed coverage.

POLHOLD | policy holder | A role played by a person or organization that holds an insurance policy. The underwriter of that policy is the scoping entity. Discussion:The identifier of the policy is captured in 'Role.id' when the Role is a policy holder. A particular policy may cover several individuals one of whom may be, but need not be, the policy holder. Thus the notion of covered party is a role that is distinct from that of the policy holder.

QUAL | qualified entity | An entity (player) that has been recognized as having certain training/experience or other characteristics that would make said entity an appropriate performer for a certain activity. The scoper is an organization that educates or qualifies entities.

SPNSR | coverage sponsor | A role played by an entity, usually an organization that is the sponsor of an insurance plan or a health program. A sponsor is the party that is ultimately accountable for the coverage by employment contract or by law. A sponsor can be an employer, union, government agency, or association. Fully insured sponsors establish the terms of the plan and contract with health insurance plans to assume the risk and to administer the plan. Self-insured sponsors delegate coverage administration, but not risk, to third-party administrators. Program sponsors

designate services to be covered in accordance with statute. Program sponsors may administer the coverage themselves, delegate coverage administration, but not risk to third-party administrators, or contract with health insurance plans to assume the risk and administrator a program. Sponsors qualify individuals who may become a policy holder of the plan; where the sponsor is the policy holder, who may become a subscriber or a dependent to a policy under the plan; or where the sponsor is a government agency, who may become program eligibles under a program. The sponsor role may be further qualified by the SponsorRole.code. Entities playing the sponsor role may also play the role of a Coverage Administrator. Example: An employer, union, government agency, or association.

STD | student | A role played by an individual who is a student of a school, which is the scoping entity.

UNDWRT | underwriter | A role played by a person or an organization. It is the party that accepts fiscal responsibility for insurance plans and the policies created under those plans; administers and accepts fiscal responsibility for a program that provides coverage for services to eligible individuals; and/or has the responsibility to assess the merits of each risk and decide a suitable premium for accepting all or part of the risk. If played by an organization, this role may be further specified by an appropriate RoleCode. Example: A health insurer; Medicaid Program; Lloyd's of London

4.3.2.10429 HL7 v3 Value Set RoleClassPartitive

URL: https://hl7.org/fhir/STU3/v3/RoleClassPartitive/vs.html

This page is part of the FHIR Specification (v3.0.2: STU 3). The current version which supercedes this version is 4.0.1. For a full list of available versions, see the Directory of published versions

Vocabulary Work Group | Maturity Level: N/A | External | Use Context: Any

This value set (http://hl7.org/fhir/ValueSet/v3-RoleClassPartitive) is defined as part of HL7 v3. Related FHIR content: RoleClassPartitive.

Summary

Defining URL: | http://hl7.org/fhir/ValueSet/v3-RoleClassPartitive

Name: | RoleClassPartitive

Definition: | An association between two Entities where the playing Entity is considered in some way "part" of the scoping Entity, e.g., as a member, component, ingredient, or content. Being "part" in the broadest sense of the word can mean anything from being an integral structural component to a mere incidental temporary association of a playing Entity with a (generally larger) scoping Entity.

OID: | 2.16.840.1.113883.1.11.10429 (for OID based terminology systems)

Source Resource | XML / JSON

This value set is not currently used

4.3.2.10429.1 Content Logical Definition

This value set includes codes from the following code systems:

* Include codes from http://hl7.org/fhir/v3/RoleClass where concept is-a _RoleClassPartitive

* Exclude these codes as defined in

http://hl7.org/fhir/v3/RoleClass

Code | Display

_RoleClassPartitive | RoleClassPartitive | An association between two Entities where the playing Entity is considered in some way "part" of the scoping Entity, e.g., as a member, component, ingredient, or content. Being "part" in the broadest sense of the word can mean anything from being an integral structural component to a mere incidental temporary association of a playing Entity with a (generally larger) scoping Entity.

4.3.2.10429.2 Expansion

This expansion generated 19 Apr 2017

This value set contains 27 concepts

Expansion based on http://hl7.org/fhir/v3/RoleClass version 2016-11-11

All codes from system http://hl7.org/fhir/v3/RoleClass

Code | Display | Definition

CONT | content | Relates a material as the content (player) to a container (scoper). Unlike ingredients, the content and a container remain separate (not mixed) and the content can be removed from the container. A content is not part of an empty container.

EXPAGTCAR | exposure agent carrier | An exposure agent carrier is an entity that is capable of conveying an exposure agent from one entity to another. The scoper of the role must be the exposure agent (e.g., pathogen).

EXPVECTOR | exposure vector | Description: A vector is a living subject that carries an exposure agent. The vector does not cause the disease itself, but exposes targets to the exposure agent. A mosquito carrying malaria is an example of a vector. The scoper of the role must be the exposure agent (e.g., pathogen).

FOMITE | fomite | Description: A fomite is a non-living entity that is capable of conveying exposure agent from one entity to another. A doorknob contaminated with a Norovirus is an example of a fomite. Anyone touching the doorknob would be exposed to the virus. The scoper of the role must be the exposure agent (e.g., pathogen).

INGR | ingredient | Relates a component (player) to a mixture (scoper). E.g., Glucose and Water are ingredients of D5W, latex may be an ingredient in a tracheal tube.

ACTI | active ingredient | Definition: a therapeutically active ingredient (player) in a mixture (scoper), where the mixture is typically a manufactured pharmaceutical. It is unknown if the quantity of such an ingredient is expressed precisely in terms of the playing ingredient substance, or, if it is specified in terms of a closely related substance (active moiety or reference substance).

ACTIB | active ingredient - basis of strength | Description: Active ingredient, where the ingredient substance (player) is itself the "basis of strength", i.e., where the Role.quantity specifies exactly the quantity of the player substance in the medicine formulation. Examples: Lopressor 50 mg actually contains 50 mg of metoprolol succinate, even though the active moiety is metoprolol, but also: Tenormin 50 mg contain 50 mg of atenolol, as free base, i.e., where the active ingredient atenolol is also the active moiety.

ACTIM | active ingredient - moiety is basis of strength | Description: Active ingredient, where not the ingredient substance (player), but itaTMs active moiety is the "basis of strength", i.e., where the Role.quantity specifies the quantity of the player substance's active moiety in the medicine formulation. Examples: 1 mL of Betopic 5mg/mL eye drops contains 5.6 mg betaxolol hydrochloride equivalent to betaxolol base 5 mg.

ACTIR | active ingredient - reference substance is basis of strength | Description: Active ingredient, where not the ingredient substance (player) but another reference substance with the same active moiety, is the "basis of strength", i.e., where the Role.quantity specifies the quantity of a reference substance, similar but different from the player substance's in the medicine formulation. Examples: Toprol-XL 50 mg contains 47.5 mg of metoprolol succinate equivalent to 50 mg of metoprolol tartrate.

ADJV | adjuvant | A component (player) added to enhance the action of an active ingredient (scoper) (in the manner of a catalyst) but which has no active effect in and of itself. Such ingredients are significant in defining equivalence of products in a way that inactive ingredients are not.

ADTV | additive | An ingredient (player) that is added to a base (scoper), that amounts to a minor part of the overall mixture.

BASE | base | A base ingredient (player) is what comprises the major part of a mixture (scoper). E.g., Water in most i.v. solutions, or Vaseline in salves. Among all ingredients of a material, there should be only one base. A base substance can, in turn, be a mixture.

CNTM | contaminant ingredient | An ingredient whose presence is not intended but may not be reasonably avoided given the circumstances of the mixture's nature or origin.

IACT | inactive ingredient | An ingredient which is not considered therapeutically active, e.g., colors, flavors, stabilizers, or preservatives, fillers, or structural components added to an active ingredient in order to facilitate administration of the active ingredient but without being considered therapeutically active. An inactive ingredient need not be biologically inert, e.g., might be active as an allergen or might have a pleasant taste, but is not an essential constituent delivering the therapeutic effect.

COLR | color additive | A substance (player) influencing the optical aspect of material (scoper).

FLVR | flavor additive | A substance (player) added to a mixture (scoper) to make it taste a certain way. In food the use is obvious, in pharmaceuticals flavors can hide disgusting taste of the active ingredient (important in pediatric treatments).

PRSV | preservative | A substance (player) added to a mixture (scoper) to prevent microorganisms (fungi, bacteria) to spoil the mixture.

STBL | stabilizer | A stabilizer (player) added to a mixture (scoper) in order to prevent the molecular disintegration of the main substance.

MECH | mechanical ingredient | An ingredient (player) of a medication (scoper) that is inseparable from the active ingredients, but has no intended chemical or pharmaceutical effect itself, but which may have some systemic effect on the patient. An example is a collagen matrix used as a base for transplanting skin cells. The collagen matrix can be left permanently in the graft site. Because it is of bovine origin, the patient may exhibit allergies or may have cultural objections to its use.

LOCE | located entity | Relates an entity (player) to a location (scoper) at which it is present in some way. This presence may be limited in time.

STOR | stored entity | Relates an entity (player) (e.g. a device) to a location (scoper) at which it is normally found or stored when not used.

MBR | member | A role played by an entity that is a member of a group. The group provides the scope for this role. Among other uses, groups as used in insurance (groups of covered individuals) and in scheduling where resources may be grouped for scheduling and logistical purposes.

PART | part | Definition: an association between two Entities where the playing Entity (the part) is a component of the whole (scoper) in the sense of an integral structural component, that is distinct from other parts in the same whole, has a distinct function in the whole, and, as an effect, the full integrity of the whole depends (to some degree) on the presence of this part, even though the part may often be separable from the whole. Discussion: Part is defined in opposition to (a) ingredient (not separable), (b) content (not a functional component), and (c) member (not functionally distinct from other members).

ACTM | active moiety | The molecule or ion that is responsible for the intended pharmacological action of the drug substance, excluding those appended or associated parts of the molecule that make the molecule an ester, salt (including a salt with hydrogen or coordination bonds), or other noncovalent derivative (such as a complex, chelate, or clathrate). Examples: heparin-sodium and heparin-potassium have the same active moiety, heparin; the active moiety of morphine-hydrochloride is morphine.

SPEC | specimen | A role played by a material entity that is a specimen for an act. It is scoped by the source of the specimen.

ALQT | aliquot | A portion (player) of an original or source specimen (scoper) used for testing or transportation.

ISLT | isolate | A microorganism that has been isolated from other microorganisms or a source matrix.

4.3.2.10871 HL7 v3 Value Set DocumentSectionType

URL: https://hl7.org/fhir/STU3/v3/DocumentSectionType/vs.html

This page is part of the FHIR Specification (v3.0.2: STU 3). The current version which supercedes this version is 4.0.1. For a full list of available versions, see the Directory of published versions

Vocabulary Work Group | Maturity Level: N/A | External | Use Context: Any

This value set (http://hl7.org/fhir/ValueSet/v3-DocumentSectionType) is defined as part of HL7 v3. Related FHIR content: DocumentSectionType.

Summary

Defining URL: | http://hl7.org/fhir/ValueSet/v3-DocumentSectionType
Name: | DocumentSectionType
Definition: | The type of document section. Possible values: review of systems, medical history, family history, microscopic findings, etc.
OID: | 2.16.840.1.113883.1.11.10871 (for OID based terminology systems)
Source Resource | XML / JSON

This value set is not currently used

4.3.2.10871.1 Content Logical Definition

This value set includes codes from the following code systems:

* Include all codes defined in http://loinc.org

4.3.2.10871.2 Expansion

This expansion generated 19 Apr 2017

This value set has >1000 codes in it. In order to keep the publication size manageable, only a selection (1000 codes) of the whole set of codes is shown

All codes from system http://loinc.org

Code | Display
1-8 | Acyclovir [Susceptibility]
10-9 | Amdinocillin [Susceptibility] by Serum bactericidal titer

100-8 | Cefoperazone [Susceptibility] by Minimum inhibitory concentration (MIC)
1000-9 | DBG Ab [Presence] in Serum or Plasma from Blood product unit
10000-8 | R wave duration in lead AVR
10001-6 | R wave duration in lead I
10002-4 | R wave duration in lead II
10003-2 | R wave duration in lead III
10004-0 | R wave duration in lead V1
10005-7 | R wave duration in lead V2
10006-5 | R wave duration in lead V3
10007-3 | R wave duration in lead V4
10008-1 | R wave duration in lead V5
10009-9 | R wave duration in lead V6
1001-7 | DBG Ab [Presence] in Serum or Plasma from donor
10010-7 | R' wave amplitude in lead AVF
10011-5 | R' wave amplitude in lead AVL
10012-3 | R' wave amplitude in lead AVR
10013-1 | R' wave amplitude in lead I
10014-9 | R' wave amplitude in lead II
10015-6 | R' wave amplitude in lead III
10016-4 | R' wave amplitude in lead V1
10017-2 | R' wave amplitude in lead V2
10018-0 | R' wave amplitude in lead V3
10019-8 | R' wave amplitude in lead V4
1002-5 | DBG Ab [Presence] in Serum or Plasma
10020-6 | R' wave amplitude in lead V5
10021-4 | R' wave amplitude in lead V6
10022-2 | R' wave duration in lead AVF
10023-0 | R' wave duration in lead AVL
10024-8 | R' wave duration in lead AVR
10025-5 | R' wave duration in lead I
10026-3 | R' wave duration in lead II
10027-1 | R' wave duration in lead III
10028-9 | R' wave duration in lead V1
10029-7 | R' wave duration in lead V2
1003-3 | Indirect antiglobulin test.complement specific reagent [Presence] in Serum or Plasma
10030-5 | R' wave duration in lead V3
10031-3 | R' wave duration in lead V4
10032-1 | R' wave duration in lead V5
10033-9 | R' wave duration in lead V6
10034-7 | S wave amplitude in lead AVF
10035-4 | S wave amplitude in lead AVL
10036-2 | S wave amplitude in lead AVR
10037-0 | S wave amplitude in lead I
10038-8 | S wave amplitude in lead II
10039-6 | S wave amplitude in lead III
1004-1 | Direct antiglobulin test.complement specific reagent [Presence] on Red Blood Cells
10040-4 | S wave amplitude in lead V1
10041-2 | S wave amplitude in lead V2
10042-0 | S wave amplitude in lead V3
10043-8 | S wave amplitude in lead V4
10044-6 | S wave amplitude in lead V5
10045-3 | S wave amplitude in lead V6
10046-1 | S wave duration in lead AVF
10047-9 | S wave duration in lead AVL
10048-7 | S wave duration in lead AVR
10049-5 | S wave duration in lead I
1005-8 | Indirect antiglobulin test.IgG specific reagent [Presence] in Serum or Plasma
10050-3 | S wave duration in lead II
10051-1 | S wave duration in lead III
10052-9 | S wave duration in lead V1
10053-7 | S wave duration in lead V2
10054-5 | S wave duration in lead V3
10055-2 | S wave duration in lead V4
10056-0 | S wave duration in lead V5
10057-8 | S wave duration in lead V6
10058-6 | S' wave amplitude in lead AVF
10059-4 | S' wave amplitude in lead AVL
1006-6 | Direct antiglobulin test.IgG specific reagent [Interpretation] on Red Blood Cells
10060-2 | S' wave amplitude in lead AVR
10061-0 | S' wave amplitude in lead I
10062-8 | S' wave amplitude in lead II
10063-6 | S' wave amplitude in lead III

10064-4 | S' wave amplitude in lead V1
10065-1 | S' wave amplitude in lead V2
10066-9 | S' wave amplitude in lead V3
10067-7 | S' wave amplitude in lead V4
10068-5 | S' wave amplitude in lead V5
10069-3 | S' wave amplitude in lead V6
1007-4 | Direct antiglobulin test.poly specific reagent [Presence] on Red Blood Cells
10070-1 | S' wave duration in lead AVF
10071-9 | S' wave duration in lead AVL
10072-7 | S' wave duration in lead AVR
10073-5 | S' wave duration in lead I
10074-3 | S' wave duration in lead II
10075-0 | S' wave duration in lead III
10076-8 | S' wave duration in lead V1
10077-6 | S' wave duration in lead V2
10078-4 | S' wave duration in lead V3
10079-2 | S' wave duration in lead V4
1008-2 | Indirect antiglobulin test.poly specific reagent [Presence] in Serum or Plasma
10080-0 | S' wave duration in lead V5
10081-8 | S' wave duration in lead V6
10082-6 | ST initial amplitude 6 ms in lead AVF
10083-4 | ST initial amplitude 6 ms in lead AVL
10084-2 | ST initial amplitude 6 ms in lead AVR
10085-9 | ST initial amplitude 6 ms in lead I
10086-7 | ST initial amplitude 6 ms in lead II
10087-5 | ST initial amplitude 6 ms in lead III
10088-3 | ST initial amplitude 6 ms in lead V1
10089-1 | ST initial amplitude 6 ms in lead V2
1009-0 | Deprecated Direct antiglobulin test.poly specific reagent [Presence] on Red Blood Cells
10090-9 | ST initial amplitude 6 ms in lead V3
10091-7 | ST initial amplitude 6 ms in lead V4
10092-5 | ST initial amplitude 6 ms in lead V5
10093-3 | ST initial amplitude 6 ms in lead V6
10094-1 | ST slope in lead AVF
10095-8 | ST slope in lead AVL
10096-6 | ST slope in lead AVR
10097-4 | ST slope in lead I
10098-2 | ST slope in lead II
10099-0 | ST slope in lead III
101-6 | Cefoperazone [Susceptibility] by Disk diffusion (KB)
1010-8 | Ew Ab [Presence] in Serum or Plasma from Blood product unit
10100-6 | ST slope in lead V1
10101-4 | ST slope in lead V2
10102-2 | ST slope in lead V3
10103-0 | ST slope in lead V4
10104-8 | ST slope in lead V5
10105-5 | ST slope in lead V6
10106-3 | ST wave end displacement in lead AVF
10107-1 | ST wave end displacement in lead AVL
10108-9 | ST wave end displacement in lead AVR
10109-7 | ST wave end displacement in lead I
1011-6 | Ew Ab [Presence] in Serum or Plasma from donor
10110-5 | ST wave end displacement in lead II
10111-3 | ST wave end displacement in lead III
10112-1 | ST wave end displacement in lead V1
10113-9 | ST wave end displacement in lead V2
10114-7 | ST wave end displacement in lead V3
10115-4 | ST wave end displacement in lead V4
10116-2 | ST wave end displacement in lead V5
10117-0 | ST wave end displacement in lead V6
10118-8 | ST wave mid displacement in lead AVF
10119-6 | ST wave mid displacement in lead AVL
1012-4 | Ew Ab [Presence] in Serum or Plasma
10120-4 | ST wave mid displacement in lead AVR
10121-2 | ST wave mid displacement in lead I
10122-0 | ST wave mid displacement in lead II
10123-8 | ST wave mid displacement in lead III
10124-6 | ST wave mid displacement in lead V1
10125-3 | ST wave mid displacement in lead V2
10126-1 | ST wave mid displacement in lead V3
10127-9 | ST wave mid displacement in lead V4
10128-7 | ST wave mid displacement in lead V5

10129-5 | ST wave mid displacement in lead V6
1013-2 | Ew Ag [Presence] on Red Blood Cells from Blood product unit
10130-3 | T' wave amplitude in lead AVF
10131-1 | T' wave amplitude in lead AVL
10132-9 | T' wave amplitude in lead AVR
10133-7 | T' wave amplitude in lead I
10134-5 | T' wave amplitude in lead II
10135-2 | T' wave amplitude in lead III
10136-0 | T' wave amplitude in lead V1
10137-8 | T' wave amplitude in lead V2
10138-6 | T' wave amplitude in lead V3
10139-4 | T' wave amplitude in lead V4
1014-0 | Ew Ag [Presence] on Red Blood Cells from donor
10140-2 | T' wave amplitude in lead V5
10141-0 | T' wave amplitude in lead V6
10142-8 | T wave amplitude in lead AVF
10143-6 | T wave amplitude in lead AVL
10144-4 | T wave amplitude in lead AVR
10145-1 | T wave amplitude in lead I
10146-9 | T wave amplitude in lead II
10147-7 | T wave amplitude in lead III
10148-5 | T wave amplitude in lead V1
10149-3 | T wave amplitude in lead V2
1015-7 | Ew Ag [Presence] on Red Blood Cells
10150-1 | T wave amplitude in lead V3
10151-9 | T wave amplitude in lead V4
10152-7 | T wave amplitude in lead V5
10153-5 | T wave amplitude in lead V6
10154-3 | Chief complaint Narrative - Reported
10155-0 | History of allergies, reported
10156-8 | History of Childhood diseases Narrative
10157-6 | History of family member diseases Narrative
10158-4 | History of Functional status Narrative
10159-2 | History of Industrial exposure Narrative
1016-5 | E Ab [Presence] in Serum or Plasma from Blood product unit
10160-0 | History of Medication use Narrative
10161-8 | History of Occupational exposure Narrative
10162-6 | History of pregnancies Narrative
10163-4 | History of pregnancies
10164-2 | History of Present illness Narrative
10165-9 | Deprecated History of psychiatric symptoms and diseases Narrative
10166-7 | History of Social function Narrative
10167-5 | History of Surgical procedures Narrative
10168-3 | History of Cardiovascular system disorders Narrative
10169-1 | History of Ear disorders Narrative
1017-3 | E Ab [Presence] in Serum or Plasma from donor
10170-9 | History of Endocrine system disorders Narrative
10171-7 | History of Eyes disorders Narrative
10172-5 | History of Hematologic system disorders Narrative
10173-3 | History of Musculoskeletal system disorders Narrative
10174-1 | History of Nose disorders Narrative
10175-8 | History of Oral cavity disorders Narrative
10176-6 | History of Reproductive system disorders Narrative
10177-4 | History of Respiratory system disorders Narrative
10178-2 | History of Skin disorders Narrative
10179-0 | History of Throat and Neck disorders Narrative
1018-1 | E Ab [Presence] in Serum or Plasma
10180-8 | History of Throat and Neck disorders
10181-6 | History of Urinary tract disorders Narrative
10182-4 | History of Travel Narrative
10183-2 | Hospital discharge medications Narrative
10184-0 | Hospital discharge physical findings Narrative
10185-7 | Hospital discharge procedures Narrative
10186-5 | Identifying information Narrative Observed
10187-3 | Review of systems Narrative - Reported
10188-1 | Review of systems overview Narrative - Reported
10189-9 | Review of systems overview - Reported
1019-9 | E Ag [Presence] on Red Blood Cells from Blood product unit
10190-7 | Mental status Narrative
10191-5 | Physical findings of Abdomen Narrative
10192-3 | Physical findings of Back Narrative
10193-1 | Physical findings of Breasts Narrative

10194-9 | Physical findings of Neurologic deep tendon reflexes Narrative
10195-6 | Physical findings of Ear Narrative
10196-4 | Physical findings of Extremities Narrative
10197-2 | Physical findings of Eye Narrative
10198-0 | Physical findings of Genitourinary tract Narrative
10199-8 | Physical findings of Head Narrative
102-4 | Cefoperazone [Susceptibility] by Serum bactericidal titer
1020-7 | E Ag [Presence] on Red Blood Cells from donor
10200-4 | Physical findings of Heart Narrative
10201-2 | Physical findings of Mouth and Throat and Teeth Narrative
10202-0 | Physical findings of Nervous system Narrative
10203-8 | Physical findings of Nose Narrative
10204-6 | Physical findings of Pelvis Narrative
10205-3 | Physical findings of Rectum Narrative
10206-1 | Physical findings of Skin Narrative
10207-9 | Physical findings of Thorax and Lungs Narrative
10208-7 | Physical findings of Vessels Narrative
10209-5 | Physical findings of Neurologic balance and Coordination Narrative
1021-5 | E Ag [Presence] on Red Blood Cells
10210-3 | Physical findings of General status Narrative
10211-1 | Physical findings of Sense of touch Narrative
10212-9 | Physical findings of Strength Narrative
10213-7 | Surgical operation note anesthesia Narrative
10214-5 | Surgical operation note anesthesia duration
10215-2 | Surgical operation note findings Narrative
10216-0 | Surgical operation note fluids Narrative
10217-8 | Surgical operation note indications [Interpretation] Narrative
10218-6 | Surgical operation note postoperative diagnosis Narrative
10219-4 | Surgical operation note preoperative diagnosis Narrative
1022-3 | Fy sup(a) Ab [Presence] in Serum or Plasma from Blood product unit
10220-2 | Surgical operation note prep time duration
10221-0 | Surgical operation note specimens taken Narrative
10222-8 | Surgical operation note surgical complications [Interpretation] Narrative
10223-6 | Surgical operation note surgical procedure Narrative
10224-4 | Hemodynamic method special circumstances
10225-1 | Cardiac measurement device Institution inventory number
10226-9 | Oxygen content in Intravascular space
10227-7 | Cardiac measurement device Vendor model number
10228-5 | Cardiac measurement device Vendor serial number
10229-3 | Hemodynamic method Type of
1023-1 | Fy sup(a) Ab [Presence] in Serum or Plasma from donor
10230-1 | Left ventricular Ejection fraction
10231-9 | Right ventricular Ejection fraction
10232-7 | Oxygen content in Aorta root
10233-5 | Oxygen content in Left atrium
10234-3 | Oxygen content in Right atrium
10235-0 | Oxygen content in High right atrium
10236-8 | Oxygen content in Low right atrium
10237-6 | Oxygen content in Mid right atrium
10238-4 | Oxygen content in Left ventricle
10239-2 | Oxygen content in Right ventricular outflow tract
1024-9 | Fy sup(a) Ab [Presence] in Serum or Plasma
10240-0 | Oxygen content in Right ventricle
10241-8 | Oxygen content in Coronary sinus
10242-6 | Oxygen content in Ductus arteriosus
10243-4 | Oxygen content in Inferior vena cava
10244-2 | Oxygen content in Left pulmonary artery
10245-9 | Oxygen content in Main pulmonary artery
10246-7 | Oxygen content in Right pulmonary artery
10247-5 | Oxygen content in Pulmonary wedge
10248-3 | Oxygen content in Superior vena cava
10249-1 | Heart rate device Institution inventory number
1025-6 | Fy sup(a) Ag [Presence] on Red Blood Cells from Blood product unit
10250-9 | Heart rate device Vendor model number
10251-7 | Heart rate device Vendor serial number
10252-5 | Biliary drain site
10253-3 | Type of Biliary drain
10254-1 | Type of Peritoneal drain
10255-8 | Type of Subarachnoid drain
10256-6 | Biliary drain Institution inventory number
10257-4 | Chest tube Institution inventory number
10258-2 | Enteral tube Institution inventory number

10259-0 | Gastrostomy tube Institution inventory number
1026-4 | Fy sup(a) Ag [Presence] on Red Blood Cells from donor
10260-8 | GI tube Institution inventory number
10261-6 | Intravascular tube Institution inventory number
10262-4 | IO tube Institution inventory number
10263-2 | Nasogastric tube Institution inventory number
10264-0 | Oral tube Institution inventory number
10265-7 | Peritoneal drain Institution inventory number
10266-5 | Peritoneal tube Institution inventory number
10267-3 | Rate control device Institution inventory number
10268-1 | Stool collection device Institution inventory number
10269-9 | Subarachnoid drain Institution inventory number
1027-2 | Fy sup(a) Ag [Presence] on Red Blood Cells
10270-7 | Synovial drain Institution inventory number
10271-5 | Tube or drain Institution inventory number
10272-3 | Upper GI tube Institution inventory number
10273-1 | Bladder irrigation tube Institution inventory number
10274-9 | Urine tube Institution inventory number
10275-6 | Wound drain device Institution inventory number
10276-4 | Peritoneal drain site
10277-2 | Stool collection site
10278-0 | Subarachnoid drain site
10279-8 | Biliary drain Vendor model number
1028-0 | Fy sup(b) Ab [Presence] in Serum or Plasma from Blood product unit
10280-6 | Chest tube Vendor model number
10281-4 | Enteral tube Vendor model number
10282-2 | Gastrostomy tube Vendor model number
10283-0 | GI tube Vendor model number
10284-8 | Intravascular tube Vendor model number
10285-5 | IO tube Vendor model number
10286-3 | Nasogastric tube Vendor model number
10287-1 | Oral tube Vendor model number
10288-9 | Peritoneal drain Vendor model number
10289-7 | Peritoneal tube Vendor model number
1029-8 | Fy sup(b) Ab [Presence] in Serum or Plasma from donor
10290-5 | Rate control device Vendor model number
10291-3 | Stool collection device Vendor model number
10292-1 | Subarachnoid drain Vendor model number
10293-9 | Synovial drain Vendor model number
10294-7 | Tube or drain Vendor model number
10295-4 | Upper GI tube Vendor model number
10296-2 | Bladder irrigation tube Vendor model number
10297-0 | Urine tube Vendor model number
10298-8 | Wound drain device Vendor model number
10299-6 | Biliary drain Vendor serial number
103-2 | Ceforanide [Susceptibility] by Minimum lethal concentration (MLC)
1030-6 | Fy sup(b) Ab [Presence] in Serum or Plasma
10300-2 | Chest tube Vendor serial number
10301-0 | Enteral tube Vendor serial number
10302-8 | Gastrostomy tube Vendor serial number
10303-6 | GI tube Vendor serial number
10304-4 | Intravascular tube Vendor serial number
10305-1 | IO tube Vendor serial number
10306-9 | Nasogastric tube Vendor serial number
10307-7 | Oral tube Vendor serial number
10308-5 | Peritoneal drain Vendor serial number
10309-3 | Peritoneal tube Vendor serial number
1031-4 | Fy sup(b) Ag [Presence] on Red Blood Cells from Blood product unit
10310-1 | Rate control device Vendor serial number
10311-9 | Stool collection device Vendor serial number
10312-7 | Subarachnoid drain Vendor serial number
10313-5 | Synovial drain Vendor serial number
10314-3 | Tube or drain Vendor serial number
10315-0 | Upper GI tube Vendor serial number
10316-8 | Bladder irrigation tube Vendor serial number
10317-6 | Urine tube Vendor serial number
10318-4 | Wound drain device Vendor serial number
10319-2 | Enema device Institution inventory number
1032-2 | Fy sup(b) Ag [Presence] on Red Blood Cells from donor
10320-0 | Enema device Vendor model number
10321-8 | Enema device Vendor serial number
10322-6 | Potassium intake 24 hour

10323-4 | Wound drain fluid [Appearance] Lower GI tract
10324-2 | Breath rate device Institution inventory number
10325-9 | Breath rate device Vendor model number
10326-7 | Breath rate device Vendor serial number
10327-5 | Eosinophils/100 leukocytes in Sputum by Manual count
10328-3 | Lymphocytes/100 leukocytes in Cerebral spinal fluid by Manual count
10329-1 | Monocytes/100 leukocytes in Cerebral spinal fluid by Manual count
1033-0 | Fy sup(b) Ag [Presence] on Red Blood Cells
10330-9 | Monocytes/100 leukocytes in Body fluid by Manual count
10331-7 | Rh [Type] in Blood
10332-5 | Cortisol [Mass/volume] in Serum or Plasma --pre 250 ug corticotropin IM
10333-3 | Appearance of Cerebral spinal fluid
10334-1 | Cancer Ag 125 [Units/volume] in Serum or Plasma
10335-8 | Color of Cerebral spinal fluid
10336-6 | Gonadotropin peptide [Mass/volume] in Urine
10337-4 | Procollagen type I [Mass/volume] in Serum
10338-2 | Barbiturates [Mass/volume] in Serum or Plasma
10339-0 | Fluoxetine+Norfluoxetine [Mass/volume] in Serum or Plasma
1034-8 | Fetal cell screen [Interpretation] in Blood
10340-8 | Molindone [Mass/volume] in Serum or Plasma
10341-6 | Norpropoxyphene [Mass/volume] in Serum or Plasma
10342-4 | Sulfamethoxazole [Mass/volume] in Serum or Plasma
10343-2 | Temazepam [Mass/volume] in Serum or Plasma
10344-0 | Tranylcypromine [Mass/volume] in Serum or Plasma
10345-7 | Trihexyphenidyl [Mass/volume] in Urine
10346-5 | Hemoglobin A [Units/volume] in Blood by Electrophoresis
10347-3 | Babesia microti identified in Blood by Light microscopy
10348-1 | Bordetella parapertussis Ab [Presence] in Serum
10349-9 | Brucella sp Ab [Units/volume] in Serum
1035-5 | Fresh frozen plasma given [Volume]
10350-7 | Herpes simplex virus IgM Ab [Titer] in Serum by Immunoassay
10351-5 | HIV 1 RNA [Units/volume] (viral load) in Serum or Plasma by Probe with amplification
10352-3 | Bacteria identified in Genital specimen by Aerobe culture
10353-1 | Bacteria identified in Nose by Aerobe culture
10354-9 | Bacteria identified in Urethra by Culture
10355-6 | Microscopic observation [Identifier] in Bone marrow by Wright Giemsa stain
10356-4 | Deprecated Microscopic observation [Identifier] in Stool by Trichrome stain
10357-2 | Microscopic observation [Identifier] in Wound by Gram stain
10358-0 | Teichoate Ab [Titer] in Serum by Immune diffusion (ID)
10359-8 | Asialoganglioside GM1 IgM Ab [Titer] in Serum
1036-3 | G Ab [Presence] in Serum or Plasma from Blood product unit
10360-6 | DNA single strand IgG Ab [Units/volume] in Serum
10361-4 | DNA single strand IgM Ab [Units/volume] in Serum
10362-2 | Endomysium IgA Ab [Presence] in Serum
10363-0 | Barbiturates [Presence] in Unspecified specimen
10364-8 | Cotinine [Mass/mass] in Hair
10365-5 | Cotinine [Mass/volume] in Serum or Plasma
10366-3 | Cotinine [Mass/volume] in Urine
10367-1 | Ethanol [Mass/volume] in Gastric fluid
10368-9 | Lead [Mass/volume] in Capillary blood
10369-7 | Opiates [Mass/mass] in Hair
1037-1 | G Ab [Presence] in Serum or Plasma from donor
10370-5 | Phencyclidine [Mass/mass] in Hair
10371-3 | Bite cells [Presence] in Blood by Light microscopy
10372-1 | Blister cells [Presence] in Blood by Light microscopy
10373-9 | Fragments [Presence] in Blood by Light microscopy
10374-7 | Helmet cells [Presence] in Blood by Light microscopy
10375-4 | Irregularly contracted cells [Presence] in Blood by Light microscopy
10376-2 | Oval macrocytes [Presence] in Blood by Light microscopy
10377-0 | Pencil cells [Presence] in Blood by Light microscopy
10378-8 | Polychromasia [Presence] in Blood by Light microscopy
10379-6 | Erythrocytes.dual population [Presence] in Blood by Light microscopy
1038-9 | G Ab [Presence] in Serum or Plasma
10380-4 | Stomatocytes [Presence] in Blood by Light microscopy
10381-2 | Target cells [Presence] in Blood by Light microscopy
10382-0 | A,B variant NOS Ag [Presence] on Red Blood Cells from Blood product unit
10383-8 | A,B variant NOS Ag [Presence] on Red Blood Cells from donor
10384-6 | A,B variant NOS Ag [Presence] on Red Blood Cells
10385-3 | Albumin concentration given
10386-1 | Albumin given [Volume]
10387-9 | Autologous erythrocytes given [Volume]
10388-7 | Autologous whole blood given [Volume]

10389-5 | Blood product.other [Type]
1039-7 | G Ag [Presence] on Red Blood Cells from Blood product unit
10390-3 | Blood product special preparation [Type]
10391-1 | Cytomegalovirus immune globulin given [Volume]
10392-9 | Cryoprecipitate given [Volume]
10393-7 | Factor IX given [Type]
10394-5 | Factor IX given [Volume]
10395-2 | Factor VIII given [Type]
10396-0 | Factor VIII given [Volume]
10397-8 | Hepatitis B immune globulin given [Volume]
10398-6 | I Ag [Presence] on Red Blood Cells from Blood product unit
10399-4 | I Ag [Presence] on Red Blood Cells from donor
104-0 | Ceforanide [Susceptibility] by Minimum inhibitory concentration (MIC)
1040-5 | G Ag [Presence] on Red Blood Cells from donor
10400-0 | I Ag [Presence] on Red Blood Cells
10401-8 | Immune serum globulin given [Type]
10402-6 | Immune serum globulin given [Volume]
10403-4 | Inject immune serum globulin [Volume]
10404-2 | Inject Rh immune globulin [Volume]
10405-9 | Inject varicella zoster virus immune globulin [Volume]
10406-7 | little i Ag [Presence] on Red Blood Cells from Blood product unit
10407-5 | little i Ag [Presence] on Red Blood Cells from donor
10408-3 | little i Ag [Presence] on Red Blood Cells
10409-1 | Pentaspan given [Volume]
1041-3 | G Ag [Presence] on Red Blood Cells
10410-9 | Plasma given [Type]
10411-7 | Plasma given [Volume]
10412-5 | Platelets given [Type]
10413-3 | Rh immune globulin given [Volume]
10414-1 | Transfuse albumin [Volume]
10415-8 | Transfuse blood exchange transfusion [Volume]
10416-6 | Transfuse blood product other [Volume]
10417-4 | Transfuse cryoprecipitate [Volume]
10418-2 | Transfuse factor IX [Volume]
10419-0 | Transfuse factor VIII [Volume]
1042-1 | H Ab [Presence] in Serum or Plasma from Blood product unit
10420-8 | Transfuse immune serum globulin [Volume]
10421-6 | Transfuse Pentaspan [Volume]
10422-4 | Transfuse plasma [Volume]
10423-2 | Transfuse platelets [Volume]
10424-0 | Transfuse erythrocytes [Volume]
10425-7 | Transfuse Rh immune globulin [Volume]
10426-5 | Transfuse whole blood [Volume]
10427-3 | Transfuse whole blood autologous [Volume]
10428-1 | Varicella zoster virus immune globulin given [Volume]
10429-9 | AE 1 Ag [Presence] in Tissue by Immune stain
1043-9 | H Ab [Presence] in Serum or Plasma from donor
10430-7 | AE 3 Ag [Presence] in Tissue by Immune stain
10431-5 | B-cell Ag [Presence] in Tissue by Immune stain
10432-3 | CD30 Ag [Presence] in Tissue by Immune stain
10433-1 | BR-2 Ag [Presence] in Tissue by Immune stain
10434-9 | Complement C3 Ag [Presence] in Tissue by Immune stain
10435-6 | C5B-9 Ag [Presence] in Tissue by Immune stain
10436-4 | CD15 Ag [Presence] in Tissue by Immune stain
10437-2 | CD16 Ag [Presence] in Tissue by Immune stain
10438-0 | CD20 Ag [Presence] in Tissue by Immune stain
10439-8 | CD3 Ag [Presence] in Tissue by Immune stain
1044-7 | H Ab [Presence] in Serum
10440-6 | Deprecated CD30 Ag [Presence] in Tissue by Immune stain
10441-4 | CD34 Ag [Presence] in Tissue by Immune stain
10442-2 | CD56 Ag [Presence] in Tissue by Immune stain
10443-0 | CD43 T-cell monocyte+myeloid cell Ag [Presence] in Tissue by Immune stain
10444-8 | CD57 Ag [Presence] in Tissue by Immune stain
10445-5 | CD11c Ag [Presence] in Tissue by Immune stain
10446-3 | Leukocyte common Ag [Presence] in Tissue by Immune stain
10447-1 | M-5 Ag [Presence] in Tissue by Immune stain
10448-9 | T-cell Ag [Presence] in Tissue by Immune stain
10449-7 | Glucose [Mass/volume] in Serum or Plasma --1 hour post meal
1045-4 | H NOS Ab [Presence] in Serum or Plasma from Blood product unit
10450-5 | Glucose [Mass/volume] in Serum or Plasma --10 hours fasting
10451-3 | Proinsulin [Moles/volume] in Serum or Plasma --12 hours fasting
10452-1 | Xylose [Mass/volume] in Serum or Plasma --1 hour post 25 g xylose PO

10453-9 | Xylose [Mass/volume] in Serum or Plasma --1 hour post dose xylose PO
10454-7 | Xylose [Mass/volume] in Serum or Plasma --2 hours post 25 g xylose PO
10455-4 | Xylose [Mass/volume] in Serum or Plasma --30 minutes post 25 g xylose PO
10456-2 | Xylose [Mass/volume] in Serum or Plasma --6 hours fasting
10457-0 | Actin Ag [Presence] in Tissue by Immune stain
10458-8 | Alkaline phosphatase.placental Ag [Presence] in Tissue by Immune stain
10459-6 | Alpha-1-Fetoprotein Ag [Presence] in Tissue by Immune stain
1046-2 | H NOS Ab [Presence] in Serum or Plasma from donor
10460-4 | Lactalbumin alpha Ag [Presence] in Tissue by Immune stain
10461-2 | Alpha-1-Antichymotrypsin Ag [Presence] in Tissue by Immune stain
10462-0 | Alpha 1 antitrypsin Ag [Presence] in Tissue by Immune stain
10463-8 | Amyloid A component Ag [Presence] in Tissue by Immune stain
10464-6 | Amyloid P component Ag [Presence] in Tissue by Immune stain
10465-3 | Amyloid.prealbumin Ag [Presence] in Tissue by Immune stain
10466-1 | Anion gap 3 in Serum or Plasma
10467-9 | Beta-2-Microglobulin amyloid Ag [Presence] in Tissue by Immune stain
10468-7 | Calcitonin Ag [Presence] in Tissue by Immune stain
10469-5 | Carcinoembryonic Ag [Presence] in Tissue by Immune stain
1047-0 | H NOS Ab [Presence] in Serum or Plasma
10470-3 | Choriogonadotropin Ag [Presence] in Tissue by Immune stain
10471-1 | Chromogranin A Ag [Presence] in Tissue by Immune stain
10472-9 | Chromogranin Ag [Presence] in Tissue by Immune stain
10473-7 | Chymotrypsin Ag [Presence] in Tissue by Immune stain
10474-5 | Collagen type 4 Ag [Presence] in Tissue by Immune stain
10475-2 | Corticotropin Ag [Presence] in Tissue by Immune stain
10476-0 | Desmin Ag [Presence] in Tissue by Immune stain
10477-8 | Enolase.neuron specific Ag [Presence] in Tissue by Immune stain
10478-6 | Eosinophil major basic protein Ag [Presence] in Tissue by Immune stain
10479-4 | CD227 Ag [Presence] in Tissue by Immune stain
1048-8 | H NOS Ag [Presence] on Red Blood Cells from Blood product unit
10480-2 | Estrogen+Progesterone receptor Ag [Presence] in Tissue by Immune stain
10481-0 | Follitropin.alpha subunit Ag [Presence] in Tissue by Immune stain
10482-8 | Follitropin.beta subunit Ag [Presence] in Tissue by Immune stain
10483-6 | Gastrin Ag [Presence] in Tissue by Immune stain
10484-4 | Glial fibrillary acidic protein Ag [Presence] in Tissue by Immune stain
10485-1 | Glucagon Ag [Presence] in Tissue by Immune stain
10486-9 | Hemoglobin Ag [Presence] in Tissue by Immune stain
10487-7 | HMB-45 Ag [Presence] in Tissue by Immune stain
10488-5 | IgA Ag [Presence] in Tissue by Immune stain
10489-3 | IgA.heavy chain Ag [Presence] in Tissue by Immune stain
1049-6 | H NOS Ag [Presence] on Red Blood Cells from donor
10490-1 | IgE Ag [Presence] in Tissue by Immune stain
10491-9 | IgG Ag [Presence] in Tissue by Immune stain
10492-7 | IgG.heavy chain Ag [Presence] in Tissue by Immune stain
10493-5 | IgM Ag [Presence] in Tissue by Immune stain
10494-3 | IgM.heavy chain Ag [Presence] in Tissue by Immune stain
10495-0 | Insulin Ag [Presence] in Tissue by Immune stain
10496-8 | Immunoglobulin light chains.kappa Ag [Presence] in Tissue by Immune stain
10497-6 | Immunoglobulin light chains.kappa amyloid Ag [Presence] in Tissue by Immune stain
10498-4 | Keratin Ag [Presence] in Tissue by Immune stain
10499-2 | Immunoglobulin light chains.lambda Ag [Presence] in Tissue by Immune stain
105-7 | Ceforanide [Susceptibility] by Disk diffusion (KB)
1050-4 | H NOS Ag [Presence] on Red Blood Cells
10500-7 | Immunoglobulin light chains.lambda amyloid Ag [Presence] in Tissue by Immune stain
10501-5 | Lutropin [Units/volume] in Serum or Plasma
10502-3 | Lutropin Ag [Presence] in Tissue by Immune stain
10503-1 | Lysozyme Ag [Presence] in Tissue by Immune stain
10504-9 | Myelin basic protein Ag [Presence] in Tissue by Immune stain
10505-6 | Myoglobin Ag [Presence] in Tissue by Immune stain
10506-4 | Peanut agglutinin Ag [Presence] in Tissue by Immune stain
10507-2 | Prolactin Ag [Presence] in Tissue by Immune stain
10508-0 | Prostate specific Ag [Presence] in Tissue by Immune stain
10509-8 | Prostatic acid phosphatase Ag [Presence] in Tissue by Immune stain
1051-2 | Hemolytic disease of newborn screen [Interpretation] in Blood
10510-6 | S-100 Ag Ag [Presence] in Tissue by Immune stain
10511-4 | Serotonin Ag [Presence] in Tissue by Immune stain
10512-2 | Somatostatin Ag [Presence] in Tissue by Immune stain
10513-0 | Somatotropin Ag [Presence] in Tissue by Immune stain
10514-8 | Synaptophysin Ag [Presence] in Tissue by Immune stain
10515-5 | Thyroglobulin Ag [Presence] in Tissue by Immune stain
10516-3 | Thyrotropin Ag [Presence] in Tissue by Immune stain
10517-1 | Trypsin Ag [Presence] in Tissue by Immune stain

10518-9 | Ulex europaeus I lectin Ag [Presence] in Tissue by Immune stain
10519-7 | Vimentin Ag [Presence] in Tissue by Immune stain
1052-0 | Deprecated I (intermediate) subtype [Presence] in Serum or Plasma from Blood product unit
10520-5 | Coagulation factor VI Ag [Presence] in Tissue by Immune stain
10521-3 | Coagulation factor VIII Ag [Presence] in Tissue by Immune stain
10522-1 | Coagulation factor XIII Ag [Presence] in Tissue by Immune stain
10523-9 | Fibrinogen Ag [Presence] in Tissue by Immune stain
10524-7 | Microscopic observation [Identifier] in Cervix by Cyto stain
10525-4 | Microscopic observation [Identifier] in Unspecified specimen by Cyto stain
10526-2 | Microscopic observation [Identifier] in Sputum by Cyto stain
10527-0 | Microscopic observation [Identifier] in Tissue by Cyto stain
10528-8 | Acetophenazine [Mass/volume] in Serum or Plasma
10529-6 | Amoxapine metabolite [Mass/volume] in Serum or Plasma
1053-8 | Deprecated I (intermediate) subtype [Presence] in serum or plasma from donor
10530-4 | Aprobarbital [Mass/volume] in Serum or Plasma
10531-2 | Bretylium [Mass/volume] in Serum or Plasma
10532-0 | Deprecated Desethylamiodarone [Mass/volume] in Serum or Plasma
10533-8 | Propoxyphene+Acetaminophen [Mass/volume] in Serum or Plasma
10534-6 | Diazoxide [Mass/volume] in Serum or Plasma
10535-3 | Digoxin [Mass/volume] in Serum or Plasma
10536-1 | Dipyridamole [Mass/volume] in Serum or Plasma
10537-9 | Deprecated Doxepin+Nordoxepin [Mass/volume] in Serum or Plasma
10538-7 | Deprecated Fluoxetine+Norfluoxetine [Mass/volume] in Serum or Plasma
10539-5 | Glipizide [Mass/volume] in Serum or Plasma
1054-6 | Deprecated I (intermediate) subtype [Presence] in srum
10540-3 | Glyburide [Mass/volume] in Serum or Plasma
10541-1 | Mepivacaine [Mass/volume] in Serum or Plasma
10542-9 | Metharbital [Mass/volume] in Serum or Plasma
10543-7 | Methsuximide+Normethsuximide [Mass/volume] in Serum or Plasma
10544-5 | Normeperidine [Presence] in Serum or Plasma
10545-2 | Normephenytoin [Mass/volume] in Serum or Plasma
10546-0 | Normethsuximide [Mass/volume] in Serum or Plasma
10547-8 | Primidone+Phenobarbital [Mass/volume] in Serum or Plasma
10548-6 | Phenytoin Free/Phenytoin.total in Serum or Plasma
10549-4 | Pirmenol [Mass/volume] in Serum or Plasma
1055-3 | Deprecated I (intermediate) subtype [Presence] on Red Blood Cells from Blood product unit
10550-2 | Deprecated Temazepam [Mass/volume] in Serum or Plasma
10551-0 | Triamterene [Mass/volume] in Serum or Plasma
10552-8 | Tricyclic antidepressants [Mass/volume] in Serum or Plasma
10553-6 | Prostatic acid phosphatase [Enzymatic activity/volume] in Genital fluid
10554-4 | Deprecated Prostatic acid phosphatase [Enzymatic activity/volume] in Seminal plasma
10555-1 | Acrosin [Entitic Catalytic Activity] in Spermatozoa
10556-9 | Deprecated Adenosine triphosphatase [Enzymatic activity/volume] in Seminal plasma
10557-7 | Adenosine triphosphate [Moles/volume] in Semen
10558-5 | Albumin [Moles/volume] in Semen
10559-3 | Deprecated Calcium [Molecules/volume] in Semen
1056-1 | Deprecated I (intermediate) subtype [Presence] on Red Blood Cells from donor
10560-1 | Carcinoembryonic Ag [Units/volume] in Semen
10561-9 | Carnitine [Moles/volume] in Semen
10562-7 | Cells [#/volume] in Cervical mucus
10563-5 | Cells other than spermatozoa [#/volume] in Semen
10564-3 | Cervical mucus [Volume]
10565-0 | Choriogonadotropin [Units/volume] in Semen
10566-8 | Deprecated Choriogonadotropin [Molecules/volume] in Semen
10567-6 | Citrate [Moles/volume] in Semen
10568-4 | Clarity of Semen
10569-2 | Color of Semen
1057-9 | Deprecated I (intermediate) subtype [Presence] on Red Blood Cells
10570-0 | Consistency of Cervical mucus
10571-8 | Deprecated Consistency of Semen
10572-6 | Deprecated Duration^post ejaculation
10573-4 | Ferning [Type] in Cervical mucus
10574-2 | Fructose [Moles/volume] in Semen
10575-9 | Deprecated Gamma glutamyl transferase [Enzymatic activity/volume] in Semen
10576-7 | Germ cells.immature [#/volume] in Semen
10577-5 | Glucosidase [Enzymatic activity/volume] in Seminal plasma
10578-3 | Glycerophosphocholine [Moles/volume] in Seminal plasma
10579-1 | Leukocytes [#/volume] in Semen
1058-7 | I Ab [Presence] in Serum or Plasma from Blood product unit
10580-9 | Liquefaction [Time] in Semen
10581-7 | Deprecated Number of entities [#] in Spermatozoa
10582-5 | pH of Cervical mucus

10583-3 | Prostaglandin F1 alpha [Moles/volume] in Semen
10584-1 | Deprecated Protein [Mass/volume] in Semen
10585-8 | Round cells [#/volume] in Semen
10586-6 | Deprecated Volume of Semen
10587-4 | Sexual abstinence duration
10588-2 | Spermatogonia [#/volume] in Semen
10589-0 | Spermatids [#/volume] in Semen by Streptoavidin-biotin method (SAB)
1059-5 | I Ab [Presence] in Serum or Plasma from donor
10590-8 | Spermatids [#/volume] in Semen by Sertoli cell barrier method (SCB)
10591-6 | Primary Spermatocytes [#/volume] in Semen
10592-4 | Secondary Spermatocytes [#/volume] in Semen
10593-2 | Spermatozoa Pyriform Head/100 spermatozoa in Semen
10594-0 | Spermatozoa Tapering Head/100 spermatozoa in Semen
10595-7 | Deprecated Spermatozoa [#/volume] in Semen
10596-5 | Deprecated Spermatozoa Ab in cervical mucosa
10597-3 | Deprecated Spermatozoa Ab in semen
10598-1 | Deprecated Spermatozoa Ab in serum
10599-9 | Spermatozoa penetration [Presence] in Seminal fluid and Cervical mucosa by Kremer test
106-5 | Ceforanide [Susceptibility] by Serum bactericidal titer
1060-3 | I Ab [Presence] in Serum or Plasma
10600-5 | Spermatozoa penetration [Presence] in Seminal fluid and Cervical mucosa
10601-3 | Spermatozoa penetration [Presence] in Seminal fluid and Cervical mucosa --post coitus
10602-1 | Spermatozoa Abnormal Head/100 spermatozoa in Semen
10603-9 | Spermatozoa Abnormal Midpiece/100 spermatozoa in Semen
10604-7 | Spermatozoa Abnormal Tail/100 spermatozoa in Semen
10605-4 | Spermatozoa Agglutinated/100 spermatozoa in Semen
10606-2 | Spermatozoa Amorphous Head/100 spermatozoa in Semen
10607-0 | Spermatozoa Coiled Tail/100 spermatozoa in Semen
10608-8 | Spermatozoa Cytoplasmic Droplet/100 spermatozoa in Semen
10609-6 | Spermatozoa Duplicate Head/100 spermatozoa in Semen
1061-1 | I NOS Ab [Presence] in Serum or Plasma from Blood product unit
10610-4 | Spermatozoa Duplicate Tail/100 spermatozoa in Semen
10611-2 | Spermatozoa Immotile/100 spermatozoa in Semen
10612-0 | Spermatozoa Large Oval Head/100 spermatozoa in Semen
10613-8 | Spermatozoa Viable/100 spermatozoa in Semen
10614-6 | Spermatozoa Motile w IgA/100 spermatozoa in Semen by Immunobead
10615-3 | Spermatozoa Motile w IgA/100 spermatozoa in Semen by Mixed antiglobulin reaction
10616-1 | Spermatozoa Motile w IgG/100 spermatozoa in Semen by Immunobead
10617-9 | Spermatozoa Motile w IgG/100 spermatozoa in Semen by Mixed antiglobulin reaction
10618-7 | Spermatozoa Motile w IgM/100 spermatozoa in Semen by Immunobead
10619-5 | Spermatozoa Motile w IgM/100 spermatozoa in Semen by Mixed antiglobulin reaction
1062-9 | I NOS Ab [Presence] in Serum or Plasma from donor
10620-3 | Spermatozoa Nonprogressive/100 spermatozoa in Semen
10621-1 | Spermatozoa Normal Head/100 spermatozoa in Semen
10622-9 | Spermatozoa Normal/100 spermatozoa in Semen
10623-7 | Spermatozoa Pin Head/100 spermatozoa in Semen
10624-5 | Spermatozoa Rapid/100 spermatozoa in Semen
10625-2 | Spermatozoa Round Head/100 spermatozoa in Semen
10626-0 | Spermatozoa Slow/100 spermatozoa in Semen
10627-8 | Spermatozoa Small Oval Head/100 spermatozoa in Semen
10628-6 | Spermatozoa Tail Swelling/100 spermatozoa in Semen
10629-4 | Spermatozoa Vacuolated Head/100 spermatozoa in Semen
1063-7 | I NOS Ab [Presence] in Serum or Plasma
10630-2 | Spinnbarkeit [Length] in Cervical mucus
10631-0 | Testosterone [Moles/volume] in Semen
10632-8 | Time until next menstrual period
10633-6 | Zinc [Moles/volume] in Semen
10634-4 | Complement C1 esterase inhibitor.functional/Complement C1 esterase inhibitor.total in Serum or Plasma
10635-1 | Acanthamoeba sp identified in Eye by Organism specific culture
10636-9 | Acanthamoeba sp identified in Eye by Wet preparation
10637-7 | Microscopic observation [Identifier] in Tissue by Night blue stain
10638-5 | Thermophilic Actinomycetes colony count [#/volume] in Unspecified specimen by Organism specific culture
10639-3 | Thermophilic Actinomycetes identified in Unspecified specimen by Organism specific culture
1064-5 | I NOS Ag [Presence] on Red Blood Cells from Blood product unit
10640-1 | Deprecated Adenovirus 40+41 [Identifier] in Stool by Electron microscopy
10641-9 | Amoeba identified in Aspirate by Immune stain
10642-7 | Amoeba identified in Aspirate by Wet preparation
10643-5 | Amoeba identified in Stool by Organism specific culture
10644-3 | Arthropod identified in Unspecified specimen
10645-0 | Aspergillus fumigatus Ag [Presence] in Tissue by Immunofluorescence
10646-8 | Astrovirus [Identifier] in Stool by Electron microscopy
10647-6 | Babesia sp identified in Blood by Thick film

10648-4 | Babesia sp identified in Blood by Thin film
10649-2 | Calicivirus [Identifier] in Stool by Electron microscopy
1065-2 | I NOS Ag [Presence] on Red Blood Cells from donor
10650-0 | Candida sp DNA [Presence] in Blood by Probe with amplification
10651-8 | Chlamydophila pneumoniae Ag [Presence] in Sputum or Bronchial
10652-6 | Chlamydophila pneumoniae DNA [Presence] in Sputum or Bronchial by Probe with amplification
10653-4 | Clotrimazole [Susceptibility] by Minimum inhibitory concentration (MIC)
10654-2 | Clotrimazole [Susceptibility] by Minimum lethal concentration (MLC)
10655-9 | Coccidia identified in Duodenal fluid by Acid fast stain
10656-7 | Coccidia identified in Stool by Acid fast stain
10657-5 | Deprecated Cryptococcus neoformans Ag [Presence] in Tissue by Immunofluorescence
10658-3 | Cyanobacterium identified in Water by Light microscopy
10659-1 | Cyclospora sp identified in Stool by Acid fast stain
1066-0 | I NOS Ag [Presence] on Red Blood Cells
10660-9 | Cytomegalovirus Ag [Presence] in Tissue by Immune stain
10661-7 | Dinoflagellate identified in Water by Light microscopy
10662-5 | Filaria identified in Blood by Concentration
10663-3 | Filaria identified in Blood by Thick film
10664-1 | Filaria identified in Blood by Thin film
10665-8 | Fungus colony count [#/volume] in Unspecified specimen by Environmental culture
10666-6 | Fungus identified in Tissue by Fontana-Masson stain
10667-4 | Fungus identified in Unspecified specimen by Animal inoculation
10668-2 | Fungus identified in Unspecified specimen by Environmental culture
10669-0 | Fungus identified in Unspecified specimen by Sticky tape for environmental fungus
1067-8 | Jk sup(a) Ab [Presence] in Serum or Plasma from Blood product unit
10670-8 | Giardia lamblia [Presence] in Stool by Organism specific culture
10671-6 | Helminth identified in Unspecified specimen
10672-4 | Helminth+Arthropod identified in Unspecified specimen
10673-2 | Hepatitis B virus core Ag [Presence] in Tissue by Immune stain
10674-0 | Hepatitis B virus surface Ag [Presence] in Tissue by Immune stain
10675-7 | Hepatitis B virus surface Ag [Presence] in Tissue by Orcein stain
10676-5 | Hepatitis C virus RNA [Units/volume] (viral load) in Serum or Plasma by Probe with amplification
10677-3 | Herpes simplex virus 1 Ag [Presence] in Tissue by Immune stain
10678-1 | Herpes simplex virus 1+2 Ag [Presence] in Tissue by Immune stain
10679-9 | Herpes simplex virus 2 Ag [Presence] in Tissue by Immune stain
1068-6 | Jk sup(a) Ab [Presence] in Serum or Plasma from donor
10680-7 | Herpes simplex virus identified in Cerebral spinal fluid by Electron microscopy
10681-5 | Herpes simplex virus identified in Tissue by Electron microscopy
10682-3 | Deprecated HIV 1 RNA [Units/volume] in Serum or Plasma by Probe with amplification
10683-1 | Hydatid cyst identified in Aspirate by Immune stain
10684-9 | Hydatid cyst identified in Liver by Wet preparation
10685-6 | Hydatid cyst identified in Lung tissue by Wet preparation
10686-4 | Leishmania sp identified in Tissue by Giemsa stain
10687-2 | Leishmania sp identified in Tissue by Organism specific culture
10688-0 | Microscopic observation [Identifier] in Hair by KOH preparation
10689-8 | Microscopic observation [Identifier] in Nail by KOH preparation
1069-4 | Jk sup(a) Ab [Presence] in Serum or Plasma
10690-6 | Microsporidia identified in Duodenal fluid by Trichrome stain modified
10691-4 | Mushroom.toxic identified by Inspection
10692-2 | Mushroom.toxic identified in Food by Light microscopy
10693-0 | Mushroom.toxic identified in Vomitus by Light microscopy
10694-8 | Naegleria sp identified in Tissue by Organism specific culture
10695-5 | Naegleria sp identified in Tissue by Wet preparation
10696-3 | Norovirus [Identifier] in Stool by Electron microscopy
10697-1 | Nystatin [Susceptibility] by Minimum inhibitory concentration (MIC)
10698-9 | Nystatin [Susceptibility] by Minimum lethal concentration (MLC)
10699-7 | Onchocerca sp identified in Tissue by Wet preparation
107-3 | Cefotaxime [Susceptibility] by Minimum lethal concentration (MLC)
1070-2 | Jk sup(a) Ag [Presence] on Red Blood Cells from Blood product unit
10700-3 | Orthopoxvirus [Identifier] in Skin by Electron microscopy
10701-1 | Ova and parasites identified in Stool by Concentration
10702-9 | Ova and parasites identified in Stool by Immune stain
10703-7 | Ova and parasites identified in Stool by Kinyoun iron hematoxylin stain
10704-5 | Ova and parasites identified in Stool by Light microscopy
10705-2 | Human papilloma virus Ag [Presence] in Tissue by Immune stain
10706-0 | Picornavirus [Identifier] in Stool by Electron microscopy
10707-8 | Toxic Plant identified in plant specimen by Inspection
10708-6 | Toxic Plant identified in Vomitus by Light microscopy
10709-4 | Plasmodium falciparum Ag [Units/volume] in Blood by Immunofluorescence
1071-0 | Jk sup(a) Ag [Presence] on Red Blood Cells from donor
10710-2 | Plasmodium sp identified in Blood by Thin film
10711-0 | Plasmodium vivax Ag [Units/volume] in Blood by Immunofluorescence

10712-8 | Pneumocystis sp identified in Lung tissue
10713-6 | Prototheca identified in Unspecified specimen by Culture
10714-4 | Deprecated Rotavirus [Identifier] in Stool by Electron microscopy
10715-1 | Schistosoma sp identified in Urine sediment by Light microscopy
10716-9 | Schistosoma sp identified in Unspecified specimen by Organism specific culture
10717-7 | Streptococcus pneumoniae Ab [Units/volume] in Serum by Latex agglutination
10718-5 | Strongyloides sp Ab [Units/volume] in Serum by Immunoassay
10719-3 | Taenia solium adult Ab [Units/volume] in Serum by Immunoblot (IB)
1072-8 | Jk sup(a) Ag [Presence] on Red Blood Cells
10720-1 | Terbinafine [Susceptibility] by Minimum inhibitory concentration (MIC)
10721-9 | Terbinafine [Susceptibility] by Minimum lethal concentration (MLC)
10722-7 | Torovirus [Identifier] in Stool by Electron microscopy
10723-5 | Toxoplasma gondii IgA Ab [Units/volume] in Serum by Immunoassay
10724-3 | Toxoplasma gondii IgE Ab [Units/volume] in Serum by Immunoassay
10725-0 | Toxoplasma gondii DNA [Units/volume] in Body fluid by Probe with amplification
10726-8 | Toxoplasma gondii [Presence] in Tissue by Giemsa stain
10727-6 | Toxoplasma gondii identified in Tissue
10728-4 | Trichomonas sp identified in Genital specimen by Organism specific culture
10729-2 | Trypanosoma sp identified in Blood by Light microscopy
1073-6 | Jk sup(b) Ab [Presence] in Serum or Plasma from Blood product unit
10730-0 | Trypanosoma sp identified in Blood by Organism specific culture
10731-8 | Trypanosoma sp identified in Blood by Thick film
10732-6 | Trypanosoma sp identified in Blood by Thin film
10733-4 | Trypanosoma sp identified in Blood by Wet preparation
10734-2 | Varicella zoster virus identified in Skin by Electron microscopy
10735-9 | Viral sequencing [Identifier] in Serum by Sequencing
10736-7 | Virus identified in Cerebral spinal fluid by Electron microscopy
10737-5 | Virus identified in Stool by Electron microscopy
10738-3 | Virus identified in Tissue by Electron microscopy
10739-1 | Virus identified in Unspecified specimen by Electron microscopy
1074-4 | Jk sup(b) Ab [Presence] in Serum or Plasma from donor
10740-9 | Aluminum.microscopic observation [Identifier] in Bone by Histomorphometry stain
10741-7 | Amyloid.microscopic observation [Identifier] in Brain by Thioflavine-S stain
10742-5 | Amyloid.microscopic observation [Identifier] in Tissue by Bennhold stain.Putchler modified
10743-3 | Amyloid.microscopic observation [Identifier] in Tissue by Highman stain
10744-1 | Amyloid.microscopic observation [Identifier] in Tissue by Vassar-culling stain
10745-8 | Bile.microscopic observation [Identifier] in Tissue by Fouchet stain
10746-6 | Calcium.microscopic observation [Identifier] in Tissue by Von Kossa stain
10747-4 | Collagen fibers+Elastic fibers.microscopic observation [Identifier] in Tissue by Lawson-Van Gieson stain
10748-2 | Collagen fibers+Elastic fibers.microscopic observation [Identifier] in Tissue by Verhoeff-Van Gieson stain
10749-0 | Collagen fibers.microscopic observation [Identifier] in Tissue by Van Gieson stain
1075-1 | Jk sup(b) Ab [Presence] in Serum or Plasma
10750-8 | Connective tissue.microscopic observation [Identifier] in Tissue by Trichrome stain.Masson
10751-6 | Copper.microscopic observation [Identifier] in Tissue by Rhodamine stain
10752-4 | Fat.microscopic observation [Identifier] in Milk by Sudan IV stain
10753-2 | Fat.microscopic observation [Identifier] in Stool by Sudan IV stain
10754-0 | Fat.microscopic observation [Identifier] in Tissue by Sudan IV stain
10755-7 | Fungus.microscopic observation [Identifier] in Tissue by Methenamine silver stain.Grocott
10756-5 | Glial fibers.microscopic observation [Identifier] in Tissue by Holzer stain
10757-3 | Hematologic+Nuclear elements.microscopic observation [Identifier] in Tissue by Giemsa stain.May-Grunwald
10758-1 | Iron.microscopic observation [Identifier] in Bone by Histomorphometry stain
10759-9 | Iron.microscopic observation [Identifier] in Sputum by Gomori stain
1076-9 | Jk sup(b) Ag [Presence] on Red Blood Cells from Blood product unit
10760-7 | Iron.microscopic observation [Identifier] in Tissue by Gomori stain
10761-5 | Iron.microscopic observation [Identifier] in Tissue by Other stain
10762-3 | Microscopic observation [Identifier] in Blood by Hemosiderin stain
10763-1 | Microscopic observation [Identifier] in Body fluid by Sudan black stain
10764-9 | Microscopic observation [Identifier] in Sputum by Silver stain
10765-6 | Microscopic observation [Identifier] in Tissue by Acetate esterase stain
10766-4 | Microscopic observation [Identifier] in Tissue by Alcian blue stain
10767-2 | Microscopic observation [Identifier] in Tissue by Alcian blue stain.sulfated
10768-0 | Microscopic observation [Identifier] in Tissue by Alcian blue stain.with periodic acid-Schiff
10769-8 | Microscopic observation [Identifier] in Tissue by Alizarin red S stain
1077-7 | Jk sup(b) Ag [Presence] on Red Blood Cells from donor
10770-6 | Microscopic observation [Identifier] in Tissue by Argentaffin stain
10771-4 | Deprecated Microscopic observation [Identifier] in Tissue by Rhodamine-auramine fluorochrome stain
10772-2 | Microscopic observation [Identifier] in Tissue by Azure-eosin stain
10773-0 | Microscopic observation [Identifier] in Tissue by Basic fuchsin stain
10774-8 | Microscopic observation [Identifier] in Tissue by Bielschowsky stain
10775-5 | Microscopic observation [Identifier] in Tissue by Bleach stain
10776-3 | Microscopic observation [Identifier] in Tissue by Bodian stain
10777-1 | Microscopic observation [Identifier] in Tissue by Brown and Brenn stain

10778-9 | Microscopic observation [Identifier] in Tissue by Butyrate esterase stain
10779-7 | Microscopic observation [Identifier] in Tissue by Carmine stain.Best
1078-5 | Jk sup(b) Ag [Presence] on Red Blood Cells
10780-5 | Microscopic observation [Identifier] in Tissue by Chloracetate esterase stain
10781-3 | Microscopic observation [Identifier] in Tissue by Churukian-Schenk stain
10782-1 | Microscopic observation [Identifier] in Tissue by Congo red stain
10783-9 | Microscopic observation [Identifier] in Tissue by Crystal violet stain
10784-7 | Microscopic observation [Identifier] in Tissue by Esterase stain.non-specific
10785-4 | Microscopic observation [Identifier] in Tissue by Fite-Faraco stain
10786-2 | Microscopic observation [Identifier] in Tissue by Giemsa stain.3 micron
10787-0 | Microscopic observation [Identifier] in Tissue by Gridley stain
10788-8 | Microscopic observation [Identifier] in Tissue by Hansel stain
10789-6 | Microscopic observation [Identifier] in Tissue by Hematoxylin-eosin-Harris regressive stain
1079-3 | Js sup(a) Ab [Presence] in Serum or Plasma from Blood product unit
10790-4 | Microscopic observation [Identifier] in Tissue by Hematoxylin-eosin-Mayers progressive stain
10791-2 | Microscopic observation [Identifier] in Tissue by Mallory-Heidenhain stain
10792-0 | Microscopic observation [Identifier] in Tissue by Methenamine silver stain.Jones
10793-8 | Microscopic observation [Identifier] in Tissue by Methyl green stain
10794-6 | Microscopic observation [Identifier] in Tissue by Methyl green-pyronine Y stain
10795-3 | Microscopic observation [Identifier] in Tissue by Methyl violet stain
10796-1 | Microscopic observation [Identifier] in Tissue by Mucicarmine stain
10797-9 | Microscopic observation [Identifier] in Tissue by Neutral red stain
10798-7 | Microscopic observation [Identifier] in Tissue by Oil red O stain
10799-5 | Microscopic observation [Identifier] in Tissue by Pentachrome stain.Movat
108-1 | Cefotaxime [Susceptibility] by Minimum inhibitory concentration (MIC)
1080-1 | Js sup(a) Ab [Presence] in Serum or Plasma from donor
10800-1 | Microscopic observation [Identifier] in Tissue by Periodic acid-Schiff stain with diatase digestion
10801-9 | Microscopic observation [Identifier] in Tissue by Phosphotungstic acid Hematoxylin (PTAH) Stain
10802-7 | Microscopic observation [Identifier] in Tissue by Prussian blue stain
10803-5 | Microscopic observation [Identifier] in Tissue by Quinacrine fluorescent stain
10804-3 | Microscopic observation [Identifier] in Tissue by Reticulin stain
10805-0 | Microscopic observation [Identifier] in Tissue by Safranin stain
10806-8 | Microscopic observation [Identifier] in Tissue by Schmorl stain
10807-6 | Microscopic observation [Identifier] in Tissue by Sevier-Munger stain
10808-4 | Microscopic observation [Identifier] in Tissue by Silver impregnation stain.Dieterle
10809-2 | Microscopic observation [Identifier] in Tissue by Silver nitrate stain
1081-9 | Js sup(a) Ab [Presence] in Serum or Plasma
10810-0 | Microscopic observation [Identifier] in Tissue by Silver stain.Fontana-Masson
10811-8 | Microscopic observation [Identifier] in Tissue by Silver stain.Grimelius
10812-6 | Microscopic observation [Identifier] in Tissue by Steiner stain
10813-4 | Microscopic observation [Identifier] in Tissue by Sudan black stain
10814-2 | Microscopic observation [Identifier] in Tissue by Supravital stain
10815-9 | Microscopic observation [Identifier] in Tissue by Tetrachrome stain
10816-7 | Deprecated Microscopic observation [Identifier] in Tissue by Toluidine blue O stain
10817-5 | Microscopic observation [Identifier] in Tissue by Trichrome stain.Gomori-Wheatley
10818-3 | Microscopic observation [Identifier] in Tissue by Trichrome stain.Masson modified
10819-1 | Microscopic observation [Identifier] in Tissue by Wade stain
1082-7 | Js sup(a) Ag [Presence] on Red Blood Cells from Blood product unit
10820-9 | Deprecated Microscopic observation [Identifier] in Tissue by Warthin-Starry stain
10821-7 | Deprecated Microscopic observation [Identifier] in Tissue by Wright Giemsa stain
10822-5 | Mucin.microscopic observation [Identifier] in Tissue by Mucicarmine stain.Mayer
10823-3 | Mucopolysaccharides.microscopic observation [Identifier] in Tissue by Colloidal ferric oxide stain.Hale
10824-1 | Myelin+Myelin breakdown products.microscopic observation [Identifier] in Tissue by Luxol fast blue/Periodic acid-Schiff stain
10825-8 | Myelin+Nerve cells.microscopic observation [Identifier] in Tissue by Luxol fast blue/Cresyl violet stain
10826-6 | Nissel.microscopic observation [Identifier] in Tissue by Cresyl echt violet stain
10827-4 | Reticulum.microscopic observation [Identifier] in Tissue by Gomori stain
10828-2 | Urate crystals.microscopic observation [type] in Tissue by De Galantha stain
10829-0 | Silicon [Mass/volume] in Serum or Plasma
1083-5 | Js sup(a) Ag [Presence] on Red Blood Cells from donor
10830-8 | Deprecated Surgical operation note complications
10831-6 | Surgical operation note complications [Interpretation]
10832-4 | Glucose [Mass/volume] in Serum or Plasma --15 minutes post 50 g lactose PO
10833-2 | Insulin [Mass/volume] in Serum or Plasma --7 hours post 75 g glucose PO
10834-0 | Globulin [Mass/volume] in Serum by calculation
10835-7 | Lipoprotein a [Mass/volume] in Serum or Plasma
10836-5 | Niacin [Mass/volume] in Blood
10837-3 | Organic acids [Presence] in Serum or Plasma
10838-1 | Phosphoserine [Mass/volume] in Serum or Plasma
10839-9 | Troponin I.cardiac [Mass/volume] in Serum or Plasma
1084-3 | Js sup(a) Ag [Presence] on Red Blood Cells
10840-7 | Atropine [Mass/volume] in Urine
10841-5 | Methazolamide [Mass/volume] in Serum or Plasma

10842-3 | Deprecated HLA-DQ1 [Presence]
10843-1 | Deprecated HLA-DQ2 [Presence]
10844-9 | Deprecated HLA-DQ3 [Presence]
10845-6 | Deprecated HLA-DQ4 [Presence]
10846-4 | Borrelia burgdorferi DNA [Presence] in Blood by Probe with amplification
10847-2 | Borrelia burgdorferi DNA [Presence] in Body fluid by Probe with amplification
10848-0 | Chlamydia sp IgG Ab [Titer] in Serum by Immunofluorescence
10849-8 | Chlamydia sp IgM Ab [Titer] in Serum by Immunofluorescence
1085-0 | Js sup(b) Ab [Presence] in Serum or Plasma from Blood product unit
10850-6 | Cyclospora cayetanensis [Presence] in Unspecified specimen
10851-4 | Escherichia coli O157:H7 [Presence] in Stool by Organism specific culture
10852-2 | Deprecated Fungus identified in Blood by Culture
10853-0 | Isospora belli [Presence] in Unspecified specimen by Acid fast stain.Kinyoun modified
10854-8 | Deprecated Midrofilaria identified in Blood by Concentration
10855-5 | Ova and parasites identified in Duodenal fluid or Gastric fluid by Light microscopy
10856-3 | Microscopic observation [Identifier] in Genital mucus by Gram stain
10857-1 | Microsporidia identified in Unspecified specimen by Light microscopy
10858-9 | Teichoate Ab [Presence] in Serum
10859-7 | Trypanosoma sp [Identifier] in Blood by Acridine Orange + Giemsa Stain
1086-8 | Js sup(b) Ab [Presence] in Serum or Plasma from donor
10860-5 | Varicella zoster virus [Presence] in Unspecified specimen by Organism specific culture
10861-3 | Progesterone receptor [Mass/mass] in Tissue
10862-1 | Basement membrane Ab [Titer] in Serum
10863-9 | Endomysium IgA Ab [Titer] in Serum
10864-7 | Immune complex [Units/volume] in Serum or Plasma by Raji cell assay
10865-4 | Intercellular substance Ab [Presence] in Serum
10866-2 | Sulfatide IgG Ab [Titer] in Serum
10867-0 | Sulfatide IgM Ab [Titer] in Serum
10868-8 | Bacitracin [Susceptibility] by Disk diffusion (KB)
10869-6 | Xylose [Mass/volume] in Blood --3 hours post 25 g xylose PO
1087-6 | Js sup(b) Ab [Presence] in Serum or Plasma
10870-4 | Xylose [Mass/volume] in Blood --4 hours post 25 g xylose PO
10871-2 | Xylose [Mass/volume] in Blood --5 hours post 25 g xylose PO
10872-0 | Xylose [Mass/volume] in Blood --baseline
10873-8 | Beta-2-Microglobulin [Mass/time] in 24 hour Urine
10874-6 | Bombesin [Mass/volume] in Plasma
10875-3 | Carnitine esters [Mass/volume] in Urine
10876-1 | Carnitine esters [Mass/volume] in Serum or Plasma
10877-9 | Carnitine free (C0) [Mass/volume] in Urine
10878-7 | Iodine.protein bound [Mass/volume] in Serum or Plasma
10879-5 | Isovalerylglycine [Mass/volume] in Urine
1088-4 | Js sup(b) Ag [Presence] on Red Blood Cells from Blood product unit
10880-3 | Magnesium [Mass/mass] in Stool
10881-1 | Pentacarboxylporphyrins [Mass/volume] in Red Blood Cells
10882-9 | Pentacarboxylporphyrins [Mass/volume] in Serum or Plasma
10883-7 | Phenolphthalein [Mass/mass] in Stool
10884-5 | Phosphate [Mass/mass] in Stool
10885-2 | Porphyrins [Mass/time] in 24 hour Urine
10886-0 | Prostate Specific Ag Free [Mass/volume] in Serum or Plasma
10887-8 | Pyridinoline [Mass/time] in 24 hour Urine
10888-6 | Lipase [Enzymatic activity/volume] in Urine
10889-4 | Bisacodyl [Mass/mass] in Stool
1089-2 | Js sup(b) Ag [Presence] on Red Blood Cells from donor
10890-2 | Deprecated Normethsuximide [Mass/volume] in Serum or Plasma
10891-0 | Oxyphenisatin [Mass/mass] in Stool
10892-8 | Pentoxifylline [Mass/volume] in Serum or Plasma
10893-6 | Trenbolone [Mass/volume] in Urine
10894-4 | Aspergillus niger Ab [Presence] in Serum by Immune diffusion (ID)
10895-1 | Clostridium difficile toxin B [Presence] in Stool
10896-9 | Eastern equine encephalitis virus IgG Ab [Titer] in Serum by Immunofluorescence
10897-7 | Eastern equine encephalitis virus IgG Ab [Titer] in Cerebral spinal fluid by Immunofluorescence
10898-5 | Eastern equine encephalitis virus IgM Ab [Titer] in Serum by Immunofluorescence

4.3.2.10879 HL7 v3 Value Set EntityDeterminerDetermined

URL: https://hl7.org/fhir/STU3/v3/EntityDeterminerDetermined/vs.html

This page is part of the FHIR Specification (v3.0.2: STU 3). The current version which supercedes this version is 4.0.1. For a full list of available versions, see the Directory of published versions

Vocabulary Work Group | Maturity Level: N/A | External | Use Context: Any

This value set (http://hl7.org/fhir/ValueSet/v3-EntityDeterminerDetermined) is defined as part of HL7 v3. Related FHIR content: EntityDeterminerDetermined.

Summary

Defining URL: | http://hl7.org/fhir/ValueSet/v3-EntityDeterminerDetermined
Name: | EntityDeterminerDetermined
Definition: | The described determiner is used to indicate that the given Entity is taken as a general description of a kind of thing that can be taken in whole, in part, or in multiples.
OID: | 2.16.840.1.113883.1.11.10879 (for OID based terminology systems)
Source Resource | XML / JSON

This value set is not currently used

4.3.2.10879.1 Content Logical Definition

This value set includes codes from the following code systems:

* Include codes from http://hl7.org/fhir/v3/EntityDeterminer where concept is-a KIND

4.3.2.10879.2 Expansion

This expansion generated 19 Apr 2017

This value set contains 3 concepts

Expansion based on http://hl7.org/fhir/v3/EntityDeterminer version 2016-11-11

All codes from system http://hl7.org/fhir/v3/EntityDeterminer

Code | Display | Definition
KIND | described | Description:A determiner that specifies that the Entity object represents a universal, kind or class of physical thing (as opposed to a particular thing).
GROUPKIND | described group | A determiner that specifies that the Entity object represents a universal, kind or class of collections physical things. While the collection may resolve to having only a single individual (or even no individuals), the potential should exist for it to cover multiple individuals.
QUANTIFIED_KIND | described quantified | The described quantified determiner indicates that the given Entity is taken as a general description of a specific amount of a thing. For example, QUANTIFIED_KIND of syringe (quantity = 3,) stands for exactly three syringes.

4.3.2.10884 HL7 v3 Value Set EntityClassLivingSubject

URL: https://hl7.org/fhir/STU3/v3/EntityClassLivingSubject/vs.html

This page is part of the FHIR Specification (v3.0.2: STU 3). The current version which supercedes this version is 4.0.1. For a full list of available versions, see the Directory of published versions

Vocabulary Work Group | Maturity Level: N/A | External | Use Context: Any

This value set (http://hl7.org/fhir/ValueSet/v3-EntityClassLivingSubject) is defined as part of HL7 v3. Related FHIR content: EntityClassLivingSubject.

Summary

Defining URL: | http://hl7.org/fhir/ValueSet/v3-EntityClassLivingSubject
Name: | EntityClassLivingSubject
Definition: | Anything that essentially has the property of life, independent of current state (a dead human corpse is still essentially a living subject.)
OID: | 2.16.840.1.113883.1.11.10884 (for OID based terminology systems)
Source Resource | XML / JSON

This value set is not currently used

4.3.2.10884.1 Content Logical Definition

This value set includes codes from the following code systems:

* Include codes from http://hl7.org/fhir/v3/EntityClass where concept is-a LIV

4.3.2.10884.2 Expansion

This expansion generated 19 Apr 2017

This value set contains 6 concepts

Expansion based on http://hl7.org/fhir/v3/EntityClass version 2016-11-11

All codes from system http://hl7.org/fhir/v3/EntityClass

Code | Display | Definition
LIV | living subject | Anything that essentially has the property of life, independent of current state (a dead human corpse is still essentially a living subject).
NLIV | non-person living subject | A subtype of living subject that includes all living things except the species Homo Sapiens.
ANM | animal | A living subject from the animal kingdom.
MIC | microorganism | All single celled living organisms including protozoa, bacteria, yeast, viruses, etc.
PLNT | plant | A living subject from the order of plants.
PSN | person | A living subject of the species homo sapiens.

4.3.2.10889 HL7 v3 Value Set EntityClassOrganization

URL: https://hl7.org/fhir/STU3/v3/EntityClassOrganization/vs.html

This page is part of the FHIR Specification (v3.0.2: STU 3). The current version which supercedes this version is 4.0.1. For a full list of available versions, see the Directory of published versions

Vocabulary Work Group | Maturity Level: N/A | External | Use Context: Any

This value set (http://hl7.org/fhir/ValueSet/v3-EntityClassOrganization) is defined as part of HL7 v3. Related FHIR content: EntityClassOrganization.

Summary

Defining URL: | http://hl7.org/fhir/ValueSet/v3-EntityClassOrganization
Name: | EntityClassOrganization
Definition: | A social or legal structure formed by human beings.
OID: | 2.16.840.1.113883.1.11.10889 (for OID based terminology systems)
Source Resource | XML / JSON

This value set is not currently used

4.3.2.10889.1 Content Logical Definition

This value set includes codes from the following code systems:

* Include codes from http://hl7.org/fhir/v3/EntityClass where concept is-a ORG

4.3.2.10889.2 Expansion

This expansion generated 19 Apr 2017

This value set contains 4 concepts

Expansion based on http://hl7.org/fhir/v3/EntityClass version 2016-11-11

All codes from system http://hl7.org/fhir/v3/EntityClass

Code | Display | Definition
ORG | organization | A social or legal structure formed by human beings.
PUB | public institution | An agency of the people of a state often assuming some authority over a certain matter. Includes government, governmental agencies, associations.
STATE | state | A politically organized body of people bonded by territory, culture, or ethnicity, having sovereignty (to a certain extent) granted by other states (enclosing or neighboring states). This includes countries (nations), provinces (e.g., one of the United States of America or a French departement), counties or municipalities. Refine using, e.g., ISO country codes, FIPS-PUB state codes, etc.
NAT | Nation | A politically organized body of people bonded by territory and known as a nation.

4.3.2.10892 HL7 v3 Value Set EntityClassPlace

URL: https://hl7.org/fhir/STU3/v3/EntityClassPlace/vs.html

This page is part of the FHIR Specification (v3.0.2: STU 3). The current version which supercedes this version is 4.0.1. For a full list of available versions, see the Directory of published versions

Vocabulary Work Group | Maturity Level: N/A | External | Use Context: Any

This value set (http://hl7.org/fhir/ValueSet/v3-EntityClassPlace) is defined as part of HL7 v3. Related FHIR content: EntityClassPlace.

Summary

Defining URL: | http://hl7.org/fhir/ValueSet/v3-EntityClassPlace
Name: | EntityClassPlace
Definition: | A physicial place or site with its containing structure. May be natural or man-made. The geographic position of a place may or may not be constant.
OID: | 2.16.840.1.113883.1.11.10892 (for OID based terminology systems)
Source Resource | XML / JSON

This value set is not currently used

4.3.2.10892.1 Content Logical Definition

This value set includes codes from the following code systems:

* Include codes from http://hl7.org/fhir/v3/EntityClass where concept is-a PLC

4.3.2.10892.2 Expansion

This expansion generated 19 Apr 2017

This value set contains 5 concepts

Expansion based on http://hl7.org/fhir/v3/EntityClass version 2016-11-11

All codes from system http://hl7.org/fhir/v3/EntityClass

Code | Display | Definition
PLC | place | A physical place or site with its containing structure. May be natural or man-made. The geographic position of a place may or may not be constant.
CITY | city or town | The territory of a city, town or other municipality.

COUNTRY | country | The territory of a sovereign nation.
COUNTY | county or parish | The territory of a county, parish or other division of a state or province.
PROVINCE | state or province | The territory of a state, province, department or other division of a sovereign country.

4.3.2.11526 HL7 v3 Value Set HumanLanguage

URL: https://hl7.org/fhir/STU3/v3/HumanLanguage/vs.html

This page is part of the FHIR Specification (v3.0.2: STU 3). The current version which supercedes this version is 4.0.1. For a full list of available versions, see the Directory of published versions

Vocabulary Work Group | Maturity Level: N/A | External | Use Context: Any

This value set (http://hl7.org/fhir/ValueSet/v3-HumanLanguage) is defined as part of HL7 v3. Related FHIR content: HumanLanguage.

Summary

Defining URL: | http://hl7.org/fhir/ValueSet/v3-HumanLanguage
Name: | HumanLanguage
Definition: | Codes for the representation of the names of human languages.
OID: | 2.16.840.1.113883.1.11.11526 (for OID based terminology systems)
Source Resource | XML / JSON

This value set is not currently used

4.3.2.11526.1 Content Logical Definition

This value set includes codes from the following code systems:

* Include all codes defined in urn:iso:std:iso:3166

4.3.2.11526.2 Expansion

This expansion generated 19 Apr 2017

This value set contains 273 concepts

All codes from system urn:iso:std:iso:3166

Code | Display
AD | Andorra
AE | United Arab Emirates (the)
AF | Afghanistan
AG | Antigua and Barbuda
AI | Anguilla
AL | Albania
AM | Armenia
AN | Netherlands Antilles
AO | Angola
AQ | Antarctica
AR | Argentina
AS | American Samoa
AT | Austria
AU | Australia
AW | Aruba
AX | Åland Islands
AZ | Azerbaijan
BA | Bosnia and Herzegovina
BB | Barbados
BD | Bangladesh
BE | Belgium
BF | Burkina Faso
BG | Bulgaria
BH | Bahrain
BI | Burundi
BJ | Benin
BL | Saint Barthélemy
BM | Bermuda
BN | Brunei Darussalam
BO | Bolivia (Plurinational State of)
BQ | Bonaire, Sint Eustatius and Saba
BR | Brazil
BS | Bahamas (the)
BT | Bhutan
BU | Burma
BV | Bouvet Island
BW | Botswana
BY | Belarus

BZ | Belize
CA | Canada
CC | Cocos (Keeling) Islands (the)
CD | Congo (the Democratic Republic of the)
CF | Central African Republic (the)
CG | Congo (the)
CH | Switzerland
CI | Côte d'Ivoire
CK | Cook Islands (the)
CL | Chile
CM | Cameroon
CN | China
CO | Colombia
CR | Costa Rica
CS | Serbia and Montenegro
CT | Canton and Enderbury Islands
CU | Cuba
CV | Cabo Verde
CW | Curaçao
CX | Christmas Island
CY | Cyprus
CZ | Czech Republic (the)
DD | German Democratic Republic
DE | Germany
DJ | Djibouti
DK | Denmark
DM | Dominica
DO | Dominican Republic (the)
DY | Dahomey
DZ | Algeria
EC | Ecuador
EE | Estonia
EG | Egypt
EH | Western Sahara*
ER | Eritrea
ES | Spain
ET | Ethiopia
FI | Finland
FJ | Fiji
FK | Falkland Islands (the) [Malvinas]
FM | Micronesia (Federated States of)
FO | Faroe Islands (the)
FQ | French Southern and Antarctic Territories
FR | France
GA | Gabon
GB | United Kingdom of Great Britain and Northern Ireland (the)
GD | Grenada
GE | Georgia
GF | French Guiana
GG | Guernsey
GH | Ghana
GI | Gibraltar
GL | Greenland
GM | Gambia (the)
GN | Guinea
GP | Guadeloupe
GQ | Equatorial Guinea
GR | Greece
GS | South Georgia and the South Sandwich Islands
GT | Guatemala
GU | Guam
GW | Guinea-Bissau
GY | Guyana
HK | Hong Kong
HM | Heard Island and McDonald Islands
HN | Honduras
HR | Croatia
HT | Haiti
HU | Hungary
HV | Upper Volta
ID | Indonesia
IE | Ireland

IL | Israel
IM | Isle of Man
IN | India
IO | British Indian Ocean Territory (the)
IQ | Iraq
IR | Iran (Islamic Republic of)
IS | Iceland
IT | Italy
JE | Jersey
JM | Jamaica
JO | Jordan
JP | Japan
JT | Johnston Island
KE | Kenya
KG | Kyrgyzstan
KH | Cambodia
KI | Kiribati
KM | Comoros (the)
KN | Saint Kitts and Nevis
KP | Korea (the Democratic People's Republic of)
KR | Korea (the Republic of)
KW | Kuwait
KY | Cayman Islands (the)
KZ | Kazakhstan
LA | Lao People's Democratic Republic (the)
LB | Lebanon
LC | Saint Lucia
LI | Liechtenstein
LK | Sri Lanka
LR | Liberia
LS | Lesotho
LT | Lithuania
LU | Luxembourg
LV | Latvia
LY | Libya
MA | Morocco
MC | Monaco
MD | Moldova (the Republic of)
ME | Montenegro
MF | Saint Martin (French part)
MG | Madagascar
MH | Marshall Islands (the)
MI | Midway Islands
MK | Macedonia (the former Yugoslav Republic of)
ML | Mali
MM | Myanmar
MN | Mongolia
MO | Macao
MP | Northern Mariana Islands (the)
MQ | Martinique
MR | Mauritania
MS | Montserrat
MT | Malta
MU | Mauritius
MV | Maldives
MW | Malawi
MX | Mexico
MY | Malaysia
MZ | Mozambique
NA | Namibia
NC | New Caledonia
NE | Niger (the)
NF | Norfolk Island
NG | Nigeria
NH | New Hebrides
NI | Nicaragua
NL | Netherlands (the)
NO | Norway
NP | Nepal
NQ | Dronning Maud Land
NR | Nauru
NT | Neutral Zone

NU | Niue
NZ | New Zealand
OM | Oman
PA | Panama
PC | Pacific Islands (Trust Territory)
PE | Peru
PF | French Polynesia
PG | Papua New Guinea
PH | Philippines (the)
PK | Pakistan
PL | Poland
PM | Saint Pierre and Miquelon
PN | Pitcairn
PR | Puerto Rico
PS | Palestine, State of
PT | Portugal
PU | United States Miscellaneous Pacific Islands
PW | Palau
PY | Paraguay
PZ | Panama Canal Zone
QA | Qatar
RE | Réunion
RH | Southern Rhodesia
RO | Romania
RS | Serbia
RU | Russian Federation (the)
RW | Rwanda
SA | Saudi Arabia
SB | Solomon Islands
SC | Seychelles
SD | Sudan (the)
SE | Sweden
SG | Singapore
SH | Saint Helena, Ascension and Tristan da Cunha
SI | Slovenia
SJ | Svalbard and Jan Mayen
SK | Slovakia
SL | Sierra Leone
SM | San Marino
SN | Senegal
SO | Somalia
SR | Suriname
SS | South Sudan
ST | Sao Tome and Principe
SU | USSR
SV | El Salvador
SX | Sint Maarten (Dutch part)
SY | Syrian Arab Republic
SZ | Swaziland
TC | Turks and Caicos Islands (the)
TD | Chad
TF | French Southern Territories (the)
TG | Togo
TH | Thailand
TJ | Tajikistan
TK | Tokelau
TL | Timor-Leste
TM | Turkmenistan
TN | Tunisia
TO | Tonga
TP | East Timor
TR | Turkey
TT | Trinidad and Tobago
TV | Tuvalu
TW | Taiwan (Province of China)
TZ | Tanzania, United Republic of
UA | Ukraine
UG | Uganda
UM | United States
US | United States of America (the)
UY | Uruguay
UZ | Uzbekistan

VA | Holy See (the)
VC | Saint Vincent and the Grenadines
VD | Viet-Nam, Democratic Republic of
VE | Venezuela (Bolivarian Republic of)
VG | Virgin Islands (British)
VI | Virgin Islands (U.S.)
VN | Viet Nam
VU | Vanuatu
WF | Wallis and Futuna
WK | Wake Island
WS | Samoa
YD | Yemen, Democratic
YE | Yemen
YT | Mayotte
YU | Yugoslavia
ZA | South Africa
ZM | Zambia
ZR | Zaire
ZW | Zimbabwe

4.3.2.11529 HL7 v3 Value Set ActClassObservation

URL: https://hl7.org/fhir/STU3/v3/ActClassObservation/vs.html

This page is part of the FHIR Specification (v3.0.2: STU 3). The current version which supercedes this version is 4.0.1. For a full list of available versions, see the Directory of published versions

Vocabulary Work Group | Maturity Level: N/A | External | Use Context: Any

This value set (http://hl7.org/fhir/ValueSet/v3-ActClassObservation) is defined as part of HL7 v3. Related FHIR content: ActClassObservation.

Summary

Defining URL: | http://hl7.org/fhir/ValueSet/v3-ActClassObservation
Name: | ActClassObservation
Definition: | Description: An act that is intended to result in new information about a subject. The main difference between Observations and other Acts is that Observations have a value attribute. Thecode attribute of Observation and thevalue attribute of Observation must be considered in combination to determine the semantics of the observation. Discussion: Structurally, many observations are name-value-pairs, where the Observation.code (inherited from Act) is the name and the Observation.value is the value of the property. Such a construct is also known as a variable (a named feature that can assume a value) hence, the Observation class is always used to hold generic name-value-pairs or variables, even though the variable valuation may not be the result of an elaborate observation method. It may be a simple answer to a question or it may be an assertion or setting of a parameter. As with all Act statements, Observation statements describe what was done, and in the case of Observations, this includes a description of what was actually observed (results or answers); and those results or answers are part of the observation and not split off into other objects. The method of action is asserted by the Observation classCode or its subclasses at the least granular level, by the Observation.code attribute value at the medium level of granularity, and by the attribute value of observation.methodCode when a finer level of granularity is required. The method in whole or in part may also appear in the attribute value of Observation.value when using coded data types to express the value of the attribute. Relevant aspects of methodology may also be restated in value when the results themselves imply or state a methodology. An observation may consist of component observations each having their own Observation.code and Observation.value. In this case, the composite observation may not have an Observation.value for itself. For instance, a white blood cell count consists of the sub-observations for the counts of the various granulocytes, lymphocytes and other normal or abnormal blood cells (e.g., blasts). The overall white blood cell count Observation itself may therefore not have a value by itself (even though it could have one, e.g., the sum total of white blood cells). Thus, as long as an Act is essentially an Act of recognizing and noting information about a subject, it is an Observation, regardless of whether it has a simple value by itself or whether it has sub-observations. Even though observations are professional acts (see Act) and as such are intentional actions, this does not require that every possible outcome of an observation be pondered in advance of it being actually made. For instance, differential white blood cell counts (WBC) rarely show blasts, but if they do, this is part of the WBC observation even though blasts might not be predefined in the structure of a normal WBC. Clinical documents commonly have Subjective and Objective findings, both of which are kinds of Observations. In addition, clinical documents commonly contain Assessments, which are also kinds of Observations. Thus, the establishment of a diagnosis is an Observation. Examples: Recording the results of a Family History Assessment Laboratory test and associated result Physical exam test and associated result Device temperature Soil lead level
OID: | 2.16.840.1.113883.1.11.11529 (for OID based terminology systems)
Source Resource | XML / JSON

This value set is not currently used

4.3.2.11529.1 Content Logical Definition

This value set includes codes from the following code systems:

* Include codes from http://hl7.org/fhir/v3/ActClass where concept is-a OBS

4.3.2.11529.2 Expansion

This expansion generated 19 Apr 2017

This value set contains 36 concepts

Expansion based on http://hl7.org/fhir/v3/ActClass version 2016-11-11

All codes from system http://hl7.org/fhir/v3/ActClass

Code | Display | Definition

OBS | observation | Description:An act that is intended to result in new information about a subject. The main difference between Observations and other Acts is that Observations have a value attribute. The code attribute of Observation and the value attribute of Observation must be considered in combination to determine the semantics of the observation. Discussion: Structurally, many observations are name-value-pairs, where the Observation.code (inherited from Act) is the name and the Observation.value is the value of the property. Such a construct is also known as a variable (a named feature that can assume a value) hence, the Observation class is always used to hold generic name-value-pairs or variables, even though the variable valuation may not be the result of an elaborate observation method. It may be a simple answer to a question or it may be an assertion or setting of a parameter. As with all Act statements, Observation statements describe what was done, and in the case of Observations, this includes a description of what was actually observed (results or answers); and those results or answers are part of the observation and not split off into other objects. The method of action is asserted by the Observation classCode or its subclasses at the least granular level, by the Observation.code attribute value at the medium level of granularity, and by the attribute value of observation.methodCode when a finer level of granularity is required. The method in whole or in part may also appear in the attribute value of Observation.value when using coded data types to express the value of the attribute. Relevant aspects of methodology may also be restated in value when the results themselves imply or state a methodology. An observation may consist of component observations each having their own Observation.code and Observation.value. In this case, the composite observation may not have an Observation.value for itself. For instance, a white blood cell count consists of the sub-observations for the counts of the various granulocytes, lymphocytes and other normal or abnormal blood cells (e.g., blasts). The overall white blood cell count Observation itself may therefore not have a value by itself (even though it could have one, e.g., the sum total of white blood cells). Thus, as long as an Act is essentially an Act of recognizing and noting information about a subject, it is an Observation, regardless of whether it has a simple value by itself or whether it has sub-observations. Even though observations are professional acts (see Act) and as such are intentional actions, this does not require that every possible outcome of an observation be pondered in advance of it being actually made. For instance, differential white blood cell counts (WBC) rarely show blasts, but if they do, this is part of the WBC observation even though blasts might not be predefined in the structure of a normal WBC. Clinical documents commonly have Subjective and Objective findings, both of which are kinds of Observations. In addition, clinical documents commonly contain Assessments, which are also kinds of Observations. Thus, the establishment of a diagnosis is an Observation. Examples: Recording the results of a Family History Assessment Laboratory test and associated result Physical exam test and associated result Device temperature Soil lead level

_ActClassROI | ActClassROI | Regions of Interest (ROI) within a subject Act. Primarily used for making secondary observations on a subset of a subject observation. The relationship between a ROI and its referenced Act is specified through an ActRelationship of type "subject" (SUBJ), which must always be present.

ROIBND | bounded ROI | A Region of Interest (ROI) specified for a multidimensional observation, such as an Observation Series (OBSSER). The ROI is specified using a set of observation criteria, each delineating the boundary of the region in one of the dimensions in the multidimensional observation. The relationship between a ROI and its referenced Act is specified through an ActRelationship of type subject (SUBJ), which must always be present. Each of the boundary criteria observations is connected with the ROI using ActRelationships of type "has component" (COMP). In each boundary criterion, the Act.code names the dimension and the Observation.value specifies the range of values inside the region. Typically the bounded dimension is continuous, and so the Observation.value will be an interval (IVL) data type. The Observation.value need not be specified if the respective dimension is only named but not constrained. For example, an ROI for the QT interval of a certain beat in ECG Lead II would contain 2 boundary criteria, one naming the interval in time (constrained), and the other naming the interval in ECG Lead II (only named, but not constrained).

ROIOVL | overlay ROI | A Region of Interest (ROI) specified for an image using an overlay shape. Typically used to make reference to specific regions in images, e.g., to specify the location of a radiologic finding in an image or to specify the site of a physical finding by "circling" a region in a schematic picture of a human body. The units of the coordinate values are in pixels. The origin is in the upper left hand corner, with positive X values going to the right and positive Y values going down. The relationship between a ROI and its referenced Act is specified through an ActRelationship of type "subject" (SUBJ), which must always be present.

_SubjectPhysicalPosition | subject physical position | The spatial relationship of a subject whether human, other animal, or plant, to a frame of reference such as gravity or a collection device.

_SubjectBodyPosition | subject body position | Contains codes for defining the observed, physical position of a subject, such as during an observation, assessment, collection of a specimen, etc. ECG waveforms and vital signs, such as blood pressure, are two examples where a general, observed position typically needs to be noted. Deprecation Comment: This concept has been deprecated because it does not describe a type of Act (as it should in the ActClass code system), but rather encodes the result or value of an observation. The same code has been added to the ObservationValue code system.

LLD | left lateral decubitus | Lying on the left side. Deprecation Comment: This concept has been deprecated because it does not describe a type of Act (as it should in the ActClass code system), but rather encodes the result or value of an observation. The same code has been added to the ObservationValue code system.

PRN | prone | Lying with the front or ventral surface downward; lying face down. Deprecation Comment: This concept has been deprecated because it does not describe a type of Act (as it should in the ActClass code system), but rather encodes the result or value of an observation. The same code has been added to the ObservationValue code system.

RLD | right lateral decubitus | Lying on the right side. Deprecation Comment: This concept has been deprecated because it does not describe a type of Act (as it should in the ActClass code system), but rather encodes the result or value of an observation. The same code has been added to the ObservationValue code system.

SFWL | Semi-Fowler's | A semi-sitting position in bed with the head of the bed elevated approximately 45 degrees. Deprecation Comment: This concept has been deprecated because it does not describe a type of Act (as it should in the ActClass code system), but rather encodes the result or value of an observation. The same code has been added to the ObservationValue code system.

SIT | sitting | Resting the body on the buttocks, typically with upper torso erect or semi erect. Deprecation Comment: This concept has been deprecated because it does not describe a type of Act (as it should in the ActClass code system), but rather encodes the result or value of an observation. The same code has been added to the ObservationValue code system.

STN | standing | To be stationary, upright, vertical, on one's legs. Deprecation Comment: This concept has been deprecated because it does not describe a type of Act (as it should in the ActClass code system), but rather encodes the result or value of an observation. The same code has been added to the ObservationValue code system.

SUP | supine | Deprecation Comment: This concept has been deprecated because it does not describe a type of Act (as it should in the ActClass code system), but rather encodes the result or value of an observation. The same code has been added to the ObservationValue code system.

RTRD | reverse trendelenburg | Lying on the back, on an inclined plane, typically about 30-45 degrees with head raised and feet lowered. Deprecation Comment: This concept has been deprecated because it does not describe a type of Act (as it should in the ActClass code system), but rather encodes the result or value of an observation. The same code has been added to the ObservationValue code system.

TRD | trendelenburg | Lying on the back, on an inclined plane, typically about 30-45 degrees, with head lowered and feet raised. Deprecation Comment: This concept has been deprecated because it does not describe a type of Act (as it should in the ActClass code system), but rather encodes the result or value of an observation. The same code has been added to the ObservationValue code system.

ALRT | detected issue | An observation identifying a potential adverse outcome as a result of an Act or combination of Acts. Examples: Detection of a drug-drug interaction; Identification of a late-submission for an invoice; Requesting discharge for a patient who does not meet hospital-defined discharge criteria. Discussion: This class is commonly used for identifying 'business rule' or 'process' problems that may result in a refusal to carry out a particular request. In some circumstances it may be possible to 'bypass' a problem by modifying the request to acknowledge the issue and/or by providing some form of mitigation. Constraints: the Act or Acts that may cause the the adverse outcome are the target of a subject

ActRelationship. The subbtypes of this concept indicate the type of problem being detected (e.g. drug-drug interaction) while the Observation.value is used to repesent a specific problem code (e.g. specific drug-drug interaction id).

BATTERY | battery | Definition: An observation that is composed of a set of observations. These observations typically have a logical or practical grouping for generally accepted clinical or functional purposes, such as observations that are run together because of automation. A battery can define required and optional component observations and, in some cases, will define complex rules that determine whether or not a particular observation is made. BATTERY is a constraint on the Observation class in that it is understood to always be composed of component observations. UsageNotes: The focus in a BATTERY is that it is composed of individual observations. In request (RQO) mood, a battery is a request to perform the component observations. In event (EVN) mood a battery is a reporting of associated set of observation events. In definition mood a battery is the definition of the associated set of observations. Examples: Vital signs, Full blood count, Chemistry panel.

CLNTRL | clinical trial | The set of actions that define an experiment to assess the effectiveness and/or safety of a biopharmaceutical product (food, drug, device, etc.). In definition mood, this set of actions is often embodied in a clinical trial protocol; in event mood, this designates the aggregate act of applying the actions to one or more subjects.

CNOD | Condition Node | An instance of Observation of a Condition at a point in time that includes any Observations or Procedures associated with that Condition as well as links to previous instances of Condition Node for the same Condition Deprecation Comment: This concept has been deprecated because an alternative structure for tracking the evolution of a problem has been presented and adopted by the Care Provision Work Group.

COND | Condition | An observable finding or state that persists over time and tends to require intervention or management, and, therefore, distinguished from an Observation made at a point in time; may exist before an Observation of the Condition is made or after interventions to manage the Condition are undertaken. Examples: equipment repair status, device recall status, a health risk, a financial risk, public health risk, pregnancy, health maintenance, chronic illness

CASE | public health case | A public health case is an Observation representing a condition or event that has a specific significance for public health. Typically it involves an instance or instances of a reportable infectious disease or other condition. The public health case can include a health-related event concerning a single individual or it may refer to multiple health-related events that are occurrences of the same disease or condition of interest to public health. An outbreak involving multiple individuals may be considered as a type of public health case. A public health case definition (Act.moodCode = "definition") includes the description of the clinical, laboratory, and epidemiologic indicators associated with a disease or condition of interest to public health. There are case definitions for conditions that are reportable, as well as for those that are not. There are also case definitions for outbreaks. A public health case definition is a construct used by public health for the purpose of counting cases, and should not be used as clinical indications for treatment. Examples include AIDS, toxic-shock syndrome, and salmonellosis and their associated indicators that are used to define a case.

OUTB | outbreak | An outbreak represents a series of public health cases. The date on which an outbreak starts is the earliest date of onset among the cases assigned to the outbreak, and its ending date is the last date of onset among the cases assigned to the outbreak.

DGIMG | diagnostic image | Class for holding attributes unique to diagnostic images.

GEN | genomic observation | Description:An observation of genomic phenomena.

DETPOL | determinant peptide | Description:A determinant peptide in a polypeptide as described by polypeptide.

EXP | expression level | Description:An expression level of genes/proteins or other expressed genomic entities.

LOC | locus | Description:The position of a gene (or other significant sequence) on the genome.

PHN | phenotype | Description:A genomic phenomenon that is expressed externally in the organism.

POL | polypeptide | Description:A polypeptide resulting from the translation of a gene.

SEQ | bio sequence | Description:A sequence of biomolecule like the DNA, RNA, protein and the like.

SEQVAR | bio sequence variation | Description:A variation in a sequence as described by BioSequence.

INVSTG | investigation | An formalized inquiry into the circumstances surrounding a particular unplanned event or potential event for the purposes of identifying possible causes and contributing factors for the event. This investigation could be conducted at a local institutional level or at the level of a local or national government.

OBSSER | observation series | Container for Correlated Observation Sequences sharing a common frame of reference. All Observations of the same cd must be comparable and relative to the common frame of reference. For example, a 3-channel ECG device records a 12-lead ECG in 4 steps (3 leads at a time). Each of the separate 3-channel recordings would be in their own "OBSCOR". And, all 4 OBSCOR would be contained in one OBSSER because all the times are relative to the same origin (beginning of the recording) and all the ECG signals were from a fixed set of electrodes.

OBSCOR | correlated observation sequences | Container for Observation Sequences (Observations whose values are contained in LIST<>'s) having values correlated with each other. Each contained Observation Sequence LIST<> must be the same length. Values in the LIST<>'s are correlated based on index. E.g. the values in position 2 in all the LIST<>'s are correlated. This is analogous to a table where each column is an Observation Sequence with a LIST<> of values, and each row in the table is a correlation between the columns. For example, a 12-lead ECG would contain 13 sequences: one sequence for time, and a sequence for each of the 12 leads.

POS | position | An observation denoting the physical location of a person or thing based on a reference coordinate system.

POSACC | position accuracy | Description:An observation representing the degree to which the assignment of the spatial coordinates, based on a matching algorithm by a geocoding engine against a reference spatial database, matches true or accepted values.

POSCOORD | position coordinate | Description:An observation representing one of a set of numerical values used to determine the position of a place. The name of the coordinate value is determined by the reference coordinate system.

SPCOBS | specimen observation | An observation on a specimen in a laboratory environment that may affect processing, analysis or result interpretation

VERIF | Verification | An act which describes the process whereby a 'verifying party' validates either the existence of the Role attested to by some Credential or the actual Vetting act and its details.

4.3.2.11535 HL7 v3 Value Set ActClassSupply

URL: https://hl7.org/fhir/STU3/v3/ActClassSupply/vs.html

This page is part of the FHIR Specification (v3.0.2: STU 3). The current version which supercedes this version is 4.0.1. For a full list of available versions, see the Directory of published versions

Vocabulary Work Group | Maturity Level: N/A | External | Use Context: Any

This value set (http://hl7.org/fhir/ValueSet/v3-ActClassSupply) is defined as part of HL7 v3. Related FHIR content: ActClassSupply.

Summary

Defining URL: | http://hl7.org/fhir/ValueSet/v3-ActClassSupply

Name: | ActClassSupply

Definition: | Supply orders and deliveries are simple Acts that focus on the delivered product. The product is associated with the Supply Act via Participation.typeCode="product". With general Supply Acts, the precise identification of the Material (manufacturer, serial numbers, etc.) is important. Most of the detailed information about the Supply should be represented using the Material class. If delivery needs to be scheduled, tracked, and billed separately, one can associate a Transportation Act with the Supply Act. Pharmacy dispense services are represented as Supply Acts, associated with a SubstanceAdministration Act. The SubstanceAdministration class represents the administration of medication, while dispensing is supply.
OID: | 2.16.840.1.113883.1.11.11535 (for OID based terminology systems)
Source Resource | XML / JSON

This value set is not currently used

4.3.2.11535.1 Content Logical Definition

This value set includes codes from the following code systems:

* Include codes from http://hl7.org/fhir/v3/ActClass where concept is-a SPLY

4.3.2.11535.2 Expansion

This expansion generated 19 Apr 2017

This value set contains 2 concepts

Expansion based on http://hl7.org/fhir/v3/ActClass version 2016-11-11

All codes from system http://hl7.org/fhir/v3/ActClass

Code | Display | Definition
SPLY | supply | Supply orders and deliveries are simple Acts that focus on the delivered product. The product is associated with the Supply Act via Participation.typeCode="product". With general Supply Acts, the precise identification of the Material (manufacturer, serial numbers, etc.) is important. Most of the detailed information about the Supply should be represented using the Material class. If delivery needs to be scheduled, tracked, and billed separately, one can associate a Transportation Act with the Supply Act. Pharmacy dispense services are represented as Supply Acts, associated with a SubstanceAdministration Act. The SubstanceAdministration class represents the administration of medication, while dispensing is supply.
DIET | diet | Diet services are supply services, with some aspects resembling Medication services: the detail of the diet is given as a description of the Material associated via Participation.typeCode="product". Medically relevant diet types may be communicated in the Diet.code attribute using domain ActDietCode, however, the detail of the food supplied and the various combinations of dishes should be communicated as Material instances. Deprecation Note Class: Use either the Supply class (if dealing with what should be given to the patient) or SubstanceAdministration class (if dealing with what the patient should consume) energyQuantity: This quantity can be conveyed by using a Content relationship with a quantity attribute expressing the calories carbohydrateQuantity:This quantity can be conveyed using a Content relationship to an Entity with a code of carbohydrate and a quantity attribute on the content relationship.

4.3.2.11580 HL7 v3 Value Set RoleClassManufacturedProduct

URL: https://hl7.org/fhir/STU3/v3/RoleClassManufacturedProduct/vs.html

This page is part of the FHIR Specification (v3.0.2: STU 3). The current version which supercedes this version is 4.0.1. For a full list of available versions, see the Directory of published versions

Vocabulary Work Group | Maturity Level: N/A | External | Use Context: Any

This value set (http://hl7.org/fhir/ValueSet/v3-RoleClassManufacturedProduct) is defined as part of HL7 v3. Related FHIR content: RoleClassManufacturedProduct.

Summary

Defining URL: | http://hl7.org/fhir/ValueSet/v3-RoleClassManufacturedProduct
Name: | RoleClassManufacturedProduct
Definition: | Scoped by the manufacturer
OID: | 2.16.840.1.113883.1.11.11580 (for OID based terminology systems)
Source Resource | XML / JSON

This value set is not currently used

4.3.2.11580.1 Content Logical Definition

This value set includes codes from the following code systems:

* Include codes from http://hl7.org/fhir/v3/RoleClass where concept is-a MANU

4.3.2.11580.2 Expansion

This expansion generated 19 Apr 2017

This value set contains 2 concepts

Expansion based on http://hl7.org/fhir/v3/RoleClass version 2016-11-11

All codes from system http://hl7.org/fhir/v3/RoleClass

Code | Display | Definition
MANU | manufactured product | Scoped by the manufacturer
THER | therapeutic agent | A manufactured material (player) that is used for its therapeutic properties. The manufacturer is the scoper.

4.3.2.11591 HL7 v3 Value Set RoleClassSpecimen

URL: https://hl7.org/fhir/STU3/v3/RoleClassSpecimen/vs.html

This page is part of the FHIR Specification (v3.0.2: STU 3). The current version which supercedes this version is 4.0.1. For a full list of available versions, see the Directory of published versions

Vocabulary Work Group | Maturity Level: N/A | External | Use Context: Any

This value set (http://hl7.org/fhir/ValueSet/v3-RoleClassSpecimen) is defined as part of HL7 v3. Related FHIR content: RoleClassSpecimen.

Summary

Defining URL: | http://hl7.org/fhir/ValueSet/v3-RoleClassSpecimen
Name: | RoleClassSpecimen
Definition: | A role played by a material entity that is a specimen for an act. It is scoped by the source of the specimen.
OID: | 2.16.840.1.113883.1.11.11591 (for OID based terminology systems)
Source Resource | XML / JSON

This value set is not currently used

4.3.2.11591.1 Content Logical Definition

This value set includes codes from the following code systems:

* Include codes from http://hl7.org/fhir/v3/RoleClass where concept is-a SPEC

4.3.2.11591.2 Expansion

This expansion generated 19 Apr 2017

This value set contains 3 concepts

Expansion based on http://hl7.org/fhir/v3/RoleClass version 2016-11-11

All codes from system http://hl7.org/fhir/v3/RoleClass

Code | Display | Definition
SPEC | specimen | A role played by a material entity that is a specimen for an act. It is scoped by the source of the specimen.
ALQT | aliquot | A portion (player) of an original or source specimen (scoper) used for testing or transportation.
ISLT | isolate | A microorganism that has been isolated from other microorganisms or a source matrix.

4.3.2.11623 HL7 v3 Value Set EntityClassDevice

URL: https://hl7.org/fhir/STU3/v3/EntityClassDevice/vs.html

This page is part of the FHIR Specification (v3.0.2: STU 3). The current version which supercedes this version is 4.0.1. For a full list of available versions, see the Directory of published versions

Vocabulary Work Group | Maturity Level: N/A | External | Use Context: Any

This value set (http://hl7.org/fhir/ValueSet/v3-EntityClassDevice) is defined as part of HL7 v3. Related FHIR content: EntityClassDevice.

Summary

Defining URL: | http://hl7.org/fhir/ValueSet/v3-EntityClassDevice
Name: | EntityClassDevice
Definition: | A subtype of ManufacturedMaterial used in an activity, without being substantially changed through that activity. The kind of device is identified by the code attribute inherited from Entity. Usage: This includes durable (reusable) medical equipment as well as disposable equipment.
OID: | 2.16.840.1.113883.1.11.11623 (for OID based terminology systems)
Source Resource | XML / JSON

This value set is not currently used

4.3.2.11623.1 Content Logical Definition

This value set includes codes from the following code systems:

* Include codes from http://hl7.org/fhir/v3/EntityClass where concept is-a DEV

4.3.2.11623.2 Expansion

This expansion generated 19 Apr 2017

This value set contains 3 concepts

Expansion based on http://hl7.org/fhir/v3/EntityClass version 2016-11-11

All codes from system http://hl7.org/fhir/v3/EntityClass

Code | Display | Definition
DEV | device | A subtype of ManufacturedMaterial used in an activity, without being substantially changed through that activity. The kind of device is identified by the code attribute inherited from Entity. Usage: This includes durable (reusable) medical equipment as well as disposable equipment.
CER | certificate representation | A physical artifact that stores information about the granting of authorization.
MODDV | imaging modality | Class to contain unique attributes of diagnostic imaging equipment.

4.3.2.13922 HL7 v3 Value Set EntityClassRoot

URL: https://hl7.org/fhir/STU3/v3/EntityClassRoot/vs.html

This page is part of the FHIR Specification (v3.0.2: STU 3). The current version which supercedes this version is 4.0.1. For a full list of available versions, see the Directory of published versions

Vocabulary Work Group | Maturity Level: N/A | External | Use Context: Any

This value set (http://hl7.org/fhir/ValueSet/v3-EntityClassRoot) is defined as part of HL7 v3. Related FHIR content: EntityClassRoot.

Summary

Defining URL: | http://hl7.org/fhir/ValueSet/v3-EntityClassRoot
Name: | EntityClassRoot
Definition: | Corresponds to the Entity class
OID: | 2.16.840.1.113883.1.11.13922 (for OID based terminology systems)
Source Resource | XML / JSON

This value set is not currently used

4.3.2.13922.1 Content Logical Definition

This value set includes codes from the following code systems:

* Include codes from http://hl7.org/fhir/v3/EntityClass where concept is-a ENT

4.3.2.13922.2 Expansion

This expansion generated 19 Apr 2017

This value set contains 27 concepts

Expansion based on http://hl7.org/fhir/v3/EntityClass version 2016-11-11

All codes from system http://hl7.org/fhir/v3/EntityClass

Code | Display | Definition
ENT | entity | Corresponds to the Entity class
HCE | health chart entity | A health chart included to serve as a document receiving entity in the management of medical records.
LIV | living subject | Anything that essentially has the property of life, independent of current state (a dead human corpse is still essentially a living subject).
NLIV | non-person living subject | A subtype of living subject that includes all living things except the species Homo Sapiens.
ANM | animal | A living subject from the animal kingdom.
MIC | microorganism | All single celled living organisms including protozoa, bacteria, yeast, viruses, etc.
PLNT | plant | A living subject from the order of plants.
PSN | person | A living subject of the species homo sapiens.
MAT | material | Any thing that has extension in space and mass, may be of living or non-living origin.
CHEM | chemical substance | A substance that is fully defined by an organic or inorganic chemical formula, includes mixtures of other chemical substances. Refine using, e.g., IUPAC codes.
FOOD | food | Naturally occurring, processed or manufactured entities that are primarily used as food for humans and animals.
MMAT | manufactured material | Corresponds to the ManufacturedMaterial class
CONT | container | A container of other entities.
HOLD | holder | A type of container that can hold other containers or other holders.
DEV | device | A subtype of ManufacturedMaterial used in an activity, without being substantially changed through that activity. The kind of device is identified by the code attribute inherited from Entity. Usage: This includes durable (reusable) medical equipment as well as disposable equipment.
CER | certificate representation | A physical artifact that stores information about the granting of authorization.
MODDV | imaging modality | Class to contain unique attributes of diagnostic imaging equipment.
ORG | organization | A social or legal structure formed by human beings.
PUB | public institution | An agency of the people of a state often assuming some authority over a certain matter. Includes government, governmental agencies, associations.
STATE | state | A politically organized body of people bonded by territory, culture, or ethnicity, having sovereignty (to a certain extent) granted by other states (enclosing or neighboring states). This includes countries (nations), provinces (e.g., one of the United States of America or a French departement), counties or municipalities. Refine using, e.g., ISO country codes, FIPS-PUB state codes, etc.
NAT | Nation | A politically organized body of people bonded by territory and known as a nation.
PLC | place | A physical place or site with its containing structure. May be natural or man-made. The geographic position of a place may or may not be constant.
CITY | city or town | The territory of a city, town or other municipality.
COUNTRY | country | The territory of a sovereign nation.
COUNTY | county or parish | The territory of a county, parish or other division of a state or province.
PROVINCE | state or province | The territory of a state, province, department or other division of a sovereign country.
RGRP | group | A grouping of resources (personnel, material, or places) to be used for scheduling purposes. May be a pool of like-type resources, a team, or combination of personnel, material and places.

4.3.2.13934 HL7 v3 Value Set EntityClassManufacturedMaterial

URL: https://hl7.org/fhir/STU3/v3/EntityClassManufacturedMaterial/vs.html

This page is part of the FHIR Specification (v3.0.2: STU 3). The current version which supercedes this version is 4.0.1. For a full list of available versions, see the Directory of published versions

Vocabulary Work Group | Maturity Level: N/A | External | Use Context: Any

This value set (http://hl7.org/fhir/ValueSet/v3-EntityClassManufacturedMaterial) is defined as part of HL7 v3. Related FHIR content: EntityClassManufacturedMaterial.

Summary

Defining URL: | http://hl7.org/fhir/ValueSet/v3-EntityClassManufacturedMaterial
Name: | EntityClassManufacturedMaterial
Definition: | Corresponds to the ManufacturedMaterial class
OID: | 2.16.840.1.113883.1.11.13934 (for OID based terminology systems)
Source Resource | XML / JSON

This value set is not currently used

4.3.2.13934.1 Content Logical Definition

This value set includes codes from the following code systems:

* Include codes from http://hl7.org/fhir/v3/EntityClass where concept is-a MMAT

4.3.2.13934.2 Expansion

This expansion generated 19 Apr 2017

This value set contains 6 concepts

Expansion based on http://hl7.org/fhir/v3/EntityClass version 2016-11-11

All codes from system http://hl7.org/fhir/v3/EntityClass

Code | Display | Definition
MMAT | manufactured material | Corresponds to the ManufacturedMaterial class
CONT | container | A container of other entities.
HOLD | holder | A type of container that can hold other containers or other holders.
DEV | device | A subtype of ManufacturedMaterial used in an activity, without being substantially changed through that activity. The kind of device is identified by the code attribute inherited from Entity. Usage: This includes durable (reusable) medical equipment as well as disposable equipment.
CER | certificate representation | A physical artifact that stores information about the granting of authorization.
MODDV | imaging modality | Class to contain unique attributes of diagnostic imaging equipment.

4.3.2.13940 HL7 v3 Value Set RoleClassRoot

URL: https://hl7.org/fhir/STU3/v3/RoleClassRoot/vs.html

This page is part of the FHIR Specification (v3.0.2: STU 3). The current version which supercedes this version is 4.0.1. For a full list of available versions, see the Directory of published versions

Vocabulary Work Group | Maturity Level: N/A | External | Use Context: Any

This value set (http://hl7.org/fhir/ValueSet/v3-RoleClassRoot) is defined as part of HL7 v3. Related FHIR content: RoleClassRoot.

Summary

Defining URL: | http://hl7.org/fhir/ValueSet/v3-RoleClassRoot
Name: | RoleClassRoot
Definition: | Corresponds to the Role class
OID: | 2.16.840.1.113883.1.11.13940 (for OID based terminology systems)
Source Resource | XML / JSON

This value set is not currently used

4.3.2.13940.1 Content Logical Definition

This value set includes codes from the following code systems:

* Include codes from http://hl7.org/fhir/v3/RoleClass where concept is-a ROL

4.3.2.13940.2 Expansion

This expansion generated 19 Apr 2017

This value set contains 100 concepts

Expansion based on http://hl7.org/fhir/v3/RoleClass version 2016-11-11

All codes from system http://hl7.org/fhir/v3/RoleClass

Code | Display | Definition
ROL | role | Corresponds to the Role class
_RoleClassAssociative | RoleClassAssociative | A general association between two entities that is neither partitive nor ontological.
_RoleClassMutualRelationship | RoleClassMutualRelationship | A relationship that is based on mutual behavior of the two Entities as being related. The basis of such relationship may be agreements (e.g., spouses, contract parties) or they may be de facto behavior (e.g. friends) or may be an incidental involvement with each other (e.g. parties over a dispute, siblings, children).
_RoleClassRelationshipFormal | RoleClassRelationshipFormal | A relationship between two entities that is formally recognized, frequently by a contract or similar agreement.
AFFL | affiliate | Player of the Affiliate role has a business/professional relationship with scoper. Player and scoper may be persons or organization. The Affiliate relationship does not imply membership in a group, nor does it exist for resource scheduling purposes. Example: A healthcare provider

is affiliated with another provider as a business associate.

AGNT | agent | An entity (player) that acts or is authorized to act on behalf of another entity (scoper).

ASSIGNED | assigned entity | An agent role in which the agent is an Entity acting in the employ of an organization. The focus is on functional role on behalf of the organization, unlike the Employee role where the focus is on the 'Human Resources' relationship between the employee and the organization.

COMPAR | commissioning party | An Entity that is authorized to issue or instantiate permissions, privileges, credentials or other formal/legal authorizations.

SGNOFF | signing authority or officer | The role of a person (player) who is the officer or signature authority for of a scoping entity, usually an organization (scoper).

CON | contact | A person or an organization (player) which provides or receives information regarding another entity (scoper). Examples; patient NOK and emergency contacts; guarantor contact; employer contact.

ECON | emergency contact | An entity to be contacted in the event of an emergency.

NOK | next of kin | An individual designated for notification as the next of kin for a given entity.

GUARD | guardian | Guardian of a ward

CIT | citizen | Citizen of apolitical entity

COVPTY | covered party | A role class played by a person who receives benefit coverage under the terms of a particular insurance policy. The underwriter of that policy is the scoping entity. The covered party receives coverage because of some contractual or other relationship with the holder of that policy. Discussion:This reason for coverage is captured in 'Role.code' and a relationship link with type code of indirect authority should be included using the policy holder role as the source, and the covered party role as the target. Note that a particular policy may cover several individuals one of whom may be, but need not be, the policy holder. Thus the notion of covered party is a role that is distinct from that of the policy holder.

CLAIM | claimant | Description: A role played by a party making a claim for coverage under a policy or program. A claimant must be either a person or organization, or a group of persons or organizations. A claimant is not a named insured or a program eligible. Discussion: With respect to liability insurance such as property and casualty insurance, a claimant must file a claim requesting indemnification for a loss that the claimant considers covered under the policy of a named insured. The claims adjuster for the policy underwriter will review the claim to determine whether the loss meets the benefit coverage criteria under a policy, and base any indemnification or coverage payment on that review. If a third party is liable in whole or part for the loss, the underwriter may pursue third party liability recovery. A claimant may be involved in civil or criminal legal proceedings involving claims against a defendant party that is indemnified by an insurance policy or to protest the finding of a claims adjustor. With respect to life insurance, a beneficiary designated by a named insured becomes a claimant of the proceeds of coverage, as in the case of a life insurance policy. However, a claimant for coverage under life insurance is not necessarily a designated beneficiary. Note: A claimant is not a named insured. However, a named insured may make a claim under a policy, e.g., an insured driver may make a claim for an injury under his or her comprehensive automobile insurance policy. Similarly, a program eligible may make a claim under program, e.g., an unemployed worker may claim benefits under an unemployment insurance program, but parties playing these covered party role classes are not, for purposes of this vocabulary and in an effort to clearly distinguish role classes, considered claimants. In the case of a named insured making a claim, a role type code INSCLM (insured claimant) subtypes the class to indicate that either a named insured or an individual insured has filed a claim for a loss. In the case of a program eligible, a role type code INJWKR (injured worker) subtypes the class to indicate that the covered party in a workers compensation program is an injured worker, and as such, has filed a "claim" under the program for benefits. Likewise, a covered role type code UNEMP (unemployed worker) subtypes the program eligible class to indicate that the covered party in an unemployment insurance program has filed a claim for unemployment benefits. Example: A claimant under automobile policy that is not the named insured.

NAMED | named insured | Description: A role played by a party to an insurance policy to which the insurer agrees to indemnify for losses, provides benefits for, or renders services. A named insured may be either a person, non-person living subject, or an organization, or a group of persons, non-person living subjects, or organizations. Discussion: The coded concept NAMED should not be used where a more specific child concept in this Specializable value set applies. In some cases, the named insured may not be the policy holder, e.g., where a policy holder purchases life insurance policy in which another party is the named insured and the policy holder is the beneficiary of the policy. Note: The party playing the role of a named insured is not a claimant in the sense conveyed by the RoleClassCoveredParty CLAIM (claimant). However, a named insured may make a claim under a policy, e.g., e.g., a party that is the named insured and policy holder under a comprehensive automobile insurance policy may become the claimant for coverage under that policy e.g., if injured in an automobile accident and there is no liable third party. In the case of a named insured making a claim, a role type code INSCLM (insured claimant) subtypes the class to indicate that a named insured has filed a claim for a loss. Example: The named insured under a comprehensive automobile, disability, or property and casualty policy that is the named insured and may or may not be the policy holder.

DEPEN | dependent | Description: A role played by a person covered under a policy or program based on an association with a subscriber, which is recognized by the policy holder. Note: The party playing the role of a dependent is not a claimant in the sense conveyed by the RoleClassCoveredParty CLAIM (claimant). However, a dependent may make a claim under a policy, e.g., a dependent under a health insurance policy may become the claimant for coverage under that policy for wellness examines or if injured and there is no liable third party. In the case of a dependent making a claim, a role type code INSCLM (insured claimant) subtypes the class to indicate that the dependent has filed a claim for services covered under the health insurance policy. Example: The dependent has an association with the subscriber such as a financial dependency or personal relationship such as that of a spouse, or a natural or adopted child. The policy holder may be required by law to recognize certain associations or may have discretion about the associations. For example, a policy holder may dictate the criteria for the dependent status of adult children who are students, such as requiring full time enrollment, or may recognize domestic partners as dependents. Under certain circumstances, the dependent may be under the indirect authority of a responsible party acting as a surrogate for the subscriber, for example, if the subscriber is differently abled or deceased, a guardian ad Lidem or estate executor may be appointed to assume the subscriberaTMs legal standing in the relationship with the dependent.

INDIV | individual | Description: A role played by a party covered under a policy as the policy holder. An individual may be either a person or an organization. Note: The party playing the role of an individual insured is not a claimant in the sense conveyed by the RoleClassCoveredParty CLAIM (claimant). However, a named insured may make a claim under a policy, e.g., a party that is the named insured and policy holder under a comprehensive automobile insurance policy may become the claimant for coverage under that policy if injured in an automobile accident and there is no liable third party. In the case of an individual insured making a claim, a role type code INSCLM (insured claimant) subtypes the class to indicate that an individual insured has filed a claim for a loss. Example: The individual insured under a comprehensive automobile, disability, or property and casualty policy that is the policy holder.

SUBSCR | subscriber | Description: A role played by a person covered under a policy based on association with a sponsor who is the policy holder, and whose association may provide for the eligibility of dependents for coverage. Discussion: The policy holder holds the contract with the policy or program underwriter. The subscriber holds a certificate of coverage under the contract. In legal proceedings concerning the policy or program, the terms of the contract takes precedence over the terms of the certificate of coverage if there are any inconsistencies. Note: The party playing the role of a subscriber is not a claimant in the sense conveyed by the RoleClassCoveredParty CLAIM (claimant). However, a subscriber may make a claim under a policy, e.g., a subscriber under a health insurance policy may become the claimant for coverage under that policy for wellness examines or if injured and there is no liable third party. In the case of a subscriber making a claim, a role type code INSCLM (insured claimant) subtypes the class to indicate that the subscriber has filed a claim for services covered under the health insurance policy. Example: An employee or a member of an association.

PROG | program eligible | Description: A role played by a party that meets the eligibility criteria for coverage under a program. A program eligible may be either a person, non-person living subject, or an organization, or a group of persons, non-person living subjects, or organizations. Discussion: A program as typically government administered coverage for parties determined eligible under the terms of the program. Note: The party playing a program eligible is not a claimant in the sense conveyed by the RoleClassCoveredParty CLAIM (claimant). However a program eligible may make a claim under program, e.g., an unemployed worker may claim benefits under an unemployment insurance program, but parties playing these covered party role classes are not, for purposes of this vocabulary and in an effort to clearly distinguish role classes, considered claimants. In the case of a program eligible, a role type code INJWKR (injured worker) subtypes the class to indicate that the covered party in a workers compensation program is an injured worker, and as such, has filed a "claim" under the program for benefits. Likewise, a covered role type code UNEMP (unemployed worker) subtypes the program eligible class to indicate that the covered party in an unemployment insurance program has filed a claim for unemployment benefits. Example: A party meeting eligibility criteria related to health or financial status, e.g., in the U.S., persons meeting health, demographic, or financial criteria established by state and federal law are eligible for Medicaid.

CRINV | clinical research investigator | A role played by a provider, always a person, who has agency authority from a Clinical Research Sponsor to direct the conduct of a clinical research trial or study on behalf of the sponsor.

CRSPNSR | clinical research sponsor | A role played by an entity, usually an organization, that is the sponsor of a clinical research trial or study. The sponsor commissions the study, bears the expenses, is responsible for satisfying all legal requirements concerning subject safety and privacy, and is generally responsible for collection, storage and analysis of the data generated during the trial. No scoper is necessary, as a clinical research sponsor undertakes the role on its own authority and declaration. Clinical research sponsors are usually educational or other research organizations, government agencies or biopharmaceutical companies.

EMP | employee | A relationship between a person or organization and a person or organization formed for the purpose of exchanging work for compensation. The purpose of the role is to identify the type of relationship the employee has to the employer, rather than the nature of the work actually performed. (Contrast with AssignedEntity.)

MIL | military person | A role played by a member of a military service. Scoper is the military service (e.g. Army, Navy, Air Force, etc.) or, more specifically, the unit (e.g. Company C, 3rd Battalion, 4th Division, etc.)

GUAR | guarantor | A person or organization (player) that serves as a financial guarantor for another person or organization (scoper).

INVSBJ | Investigation Subject | An entity that is the subject of an investigation. This role is scoped by the party responsible for the investigation.

CASEBJ | Case Subject | A person, non-person living subject, or place that is the subject of an investigation related to a notifiable condition (health circumstance that is reportable within the applicable public health jurisdiction)

RESBJ | research subject | Definition:Specifies the administrative functionality within a formal experimental design for which the ResearchSubject role was established. Examples: Screening - role is used for pre-enrollment evaluation portion of the design; enrolled - role is used for subjects admitted to the experimental portion of the design.

LIC | licensed entity | A relationship in which the scoper certifies the player (e. g. a medical care giver, a medical device or a provider organization) to perform certain activities that fall under the jurisdiction of the scoper (e.g., a health authority licensing healthcare providers, a medical quality authority certifying healthcare professionals).

NOT | notary public | notary public

PROV | healthcare provider | An Entity (player) that is authorized to provide health care services by some authorizing agency (scoper).

PAT | patient | A Role of a LivingSubject (player) as an actual or potential recipient of health care services from a healthcare provider organization (scoper). Usage Note: Communication about relationships between patients and specific healthcare practitioners (people) is not done via scoper. Instead this is generally done using the CareProvision act. This allows linkage between patient and a particular healthcare practitioner role and also allows description of the type of care involved in the relationship.

PAYEE | payee | The role of an organization or individual designated to receive payment for a claim against a particular coverage. The scoping entity is the organization that is the submitter of the invoice in question.

PAYOR | invoice payor | The role of an organization that undertakes to accept claims invoices, assess the coverage or payments due for those invoices and pay to the designated payees for those invoices. This role may be either the underwriter or a third-party organization authorized by the underwriter. The scoping entity is the organization that underwrites the claimed coverage.

POLHOLD | policy holder | A role played by a person or organization that holds an insurance policy. The underwriter of that policy is the scoping entity. Discussion:The identifier of the policy is captured in 'Role.id' when the Role is a policy holder. A particular policy may cover several individuals one of whom may be, but need not be, the policy holder. Thus the notion of covered party is a role that is distinct from that of the policy holder.

QUAL | qualified entity | An entity (player) that has been recognized as having certain training/experience or other characteristics that would make said entity an appropriate performer for a certain activity. The scoper is an organization that educates or qualifies entities.

SPNSR | coverage sponsor | A role played by an entity, usually an organization that is the sponsor of an insurance plan or a health program. A sponsor is the party that is ultimately accountable for the coverage by employment contract or by law. A sponsor can be an employer, union, government agency, or association. Fully insured sponsors establish the terms of the plan and contract with health insurance plans to assume the risk and to administer the plan. Self-insured sponsors delegate coverage administration, but not risk, to third-party administrators. Program sponsors designate services to be covered in accordance with statute. Program sponsors may administer the coverage themselves, delegate coverage administration, but not risk to third-party administrators, or contract with health insurance plans to assume the risk and administrator a program. Sponsors qualify individuals who may become a policy holder of the plan; where the sponsor is the policy holder, who may become a subscriber or a dependent to a policy under the plan; or where the sponsor is a government agency, who may become program eligibles under a program. The sponsor role may be further qualified by the SponsorRole.code. Entities playing the sponsor role may also play the role of a Coverage Administrator. Example: An employer, union, government agency, or association.

STD | student | A role played by an individual who is a student of a school, which is the scoping entity.

UNDWRT | underwriter | A role played by a person or an organization. It is the party that accepts fiscal responsibility for insurance plans and the policies created under those plans; administers and accepts fiscal responsibility for a program that provides coverage for services to eligible individuals; and/or has the responsibility to assess the merits of each risk and decide a suitable premium for accepting all or part of the risk. If played by an organization, this role may be further specified by an appropriate RoleCode. Example: A health insurer; Medicaid Program; Lloyd's of London

CAREGIVER | caregiver | A person responsible for the primary care of a patient at home.

PRS | personal relationship | Links two entities with classCode PSN (person) in a personal relationship. The character of the relationship must be defined by a PersonalRelationshipRoleType code. The player and scoper are determined by PersonalRelationshipRoleType code as well.

SELF | self | The "same" roleclass asserts an identity between playing and scoping entities: that they are in fact instances of the same entity and, in the case of discrepancies (e.g different DOB, gender), that one or both are in error. Usage: playing and scoping entities must have same classcode, but need not have identical attributes or values. Example: a provider registry maintains sets of conflicting demographic data for what is reported to be the same individual.

_RoleClassPassive | RoleClassPassive | An association for a playing Entity that is used, known, treated, handled, built, or destroyed, etc. under the auspices of the scoping Entity. The playing Entity is passive in these roles (even though it may be active in other roles), in the sense that the kinds of things done to it in this role happen without an agreement from the playing Entity.

ACCESS | access | A role in which the playing entity (material) provides access to another entity. The principal use case is intravenous (or other bodily) access lines that preexist and need to be referred to for medication routing instructions.

ADJY | adjacency | A physical association whereby two Entities are in some (even lose) spatial relationship with each other such that they touch each other in some way. Examples: the colon is connected (and therefore adjacent) to the jejunum; the colon is adjacent to the liver (even if not actually connected.) UsageConstraints: Adjacency is in principle a symmetrical connection, but scoper and player of the role should, where applicable, be assigned to have scoper be the larger, more central Entity and player the smaller, more distant, appendage.

CONC | connection | An adjacency of two Entities held together by a bond which attaches to each of the two entities. Examples: biceps brachii muscle connected to the radius bone, port 3 on a network switch connected to port 5 on a patch panel. UsageConstraints: See Adjacency for the assignment of scoper (larger, more central) and player (smaller, more distant).

BOND | molecular bond | A connection between two atoms of a molecule. Examples: double bond between first and second C in ethane, peptide bond between two amino-acid, disulfide bridge between two proteins, chelate and ion associations, even the much weaker van-der-Waals bonds can be considered molecular bonds. UsageConstraints: See connection and adjacency for the assignment of player and scoper.

CONY | continuity | A connection between two regional parts. Examples: the connection between ascending aorta and the aortic arc, connection between descending colon and sigmoid. UsageConstraints: See connection and adjacency for the assignment of player and scoper.

ADMM | Administerable Material | A material (player) that can be administered to an Entity (scoper).

BIRTHPL | birthplace | Relates a place (playing Entity) as the location where a living subject (scoping Entity) was born.

DEATHPLC | place of death | Definition: Relates a place (playing Entity) as the location where a living subject (scoping Entity) died.

DST | distributed material | A material (player) distributed by a distributor (scoper) who functions between a manufacturer and a buyer or retailer.

RET | retailed material | Material (player) sold by a retailer (scoper), who also give advice to prospective buyers.

EXLOC | event location | A role played by a place at which the location of an event may be recorded.

SDLOC | service delivery location | A role played by a place at which services may be provided.

DSDLOC | dedicated service delivery location | A role of a place (player) that is intended to house the provision of services. Scoper is the Entity (typically Organization) that provides these services. This is not synonymous with "ownership."

ISDLOC | incidental service delivery location | A role played by a place at which health care services may be provided without prior designation or authorization.

EXPR | exposed entity | A role played by an entity that has been exposed to a person or animal suffering a contagious disease, or with a location from which a toxin has been distributed. The player of the role is normally a person or animal, but it is possible that other entity types could become exposed. The role is scoped by the source of the exposure, and it is quite possible for a person playing the role of exposed party to also become the scoper a role played by another person. That is to say, once a person has become infected, it is possible, perhaps likely, for that person to infect others. Management of exposures and tracking exposed parties is a key function within public health, and within most public health contexts - exposed parties are known as "contacts."

HLD | held entity | Entity that is currently in the possession of a holder (scoper), who holds, or uses it, usually based on some agreement with the owner.

HLTHCHRT | health chart | The role of a material (player) that is the physical health chart belonging to an organization (scoper).

IDENT | identified entity | A role in which the scoping entity designates an identifier for a playing entity.

MANU | manufactured product | Scoped by the manufacturer

THER | therapeutic agent | A manufactured material (player) that is used for its therapeutic properties. The manufacturer is the scoper.

MNT | maintained entity | An entity (player) that is maintained by another entity (scoper). This is typical role held by durable equipment. The scoper assumes responsibility for proper operation, quality, and safety.

OWN | owned entity | An Entity (player) for which someone (scoper) is granted by law the right to call the material (player) his own. This entitles the scoper to make decisions about the disposition of that material.

RGPR | regulated product | A product regulated by some governmentatl orgnization. The role is played by Material and scoped by Organization. Rationale: To support an entity clone used to identify the NDC number for a drug product.

TERR | territory of authority | Relates a place entity (player) as the region over which the scoper (typically an Organization) has certain authority (jurisdiction). For example, the Calgary Regional Health Authority (scoper) has authority over the territory "Region 4 of Alberta" (player) in matters of health.

USED | used entity | Description:An entity (player) that is used by another entity (scoper)

WRTE | warranted product | A role a product plays when a guarantee is given to the purchaser by the seller (scoping entity) stating that the product is reliable and free from known defects and that the seller will repair or replace defective parts within a given time limit and under certain conditions.

_RoleClassOntological | RoleClassOntological | A relationship in which the scoping Entity defines or specifies what the playing Entity is. Thus, the player's "being" (Greek: ontos) is specified.

EQUIV | equivalent entity | Description: Specifies the player Entity (the equivalent Entity) as an Entity that is considered to be equivalent to a reference Entity (scoper). The equivalence is in principle a symmetric relationship, however, it is expected that the scoper is a reference entity which serves as reference entity for multiple different equivalent entities. Examples: An innovator's medicine formulation is the reference for "generics", i.e., formulations manufactured differently but having been proven to be biologically equivalent to the reference medicine. Another example is a reference ingredient that serves as basis for quantity specifications (basis of strength, e.g., metoprolol succinate specified in terms of metoprolol tartrate.)

SAME | same | The "same" role asserts an identity between playing and scoping entities, i.e., that they are in fact two records of the same entity instance, and, in the case of discrepancies (e.g different DOB, gender), that one or both are in error. Usage: playing and scoping entities must have same classCode, but need not have identical attributes or values. Example: a provider registry maintains sets of conflicting demographic data for what is reported to be the same individual.

SUBY | subsumed by | Relates a prevailing record of an Entity (scoper) with another record (player) that it subsumes. Examples: Show a correct new Person object (scoper) that subsumes one or more duplicate Person objects that had accidentally been created for the same physical person. Constraints: Both the player and scoper must have the same classCode.

GEN | has generalization | Relates a specialized material concept (player) to its generalization (scoper).

GRIC | has generic | A special link between pharmaceuticals indicating that the target (scoper) is a generic for the source (player).

INST | instance | An individual piece of material (player) instantiating a class of material (scoper).

SUBS | subsumer | An entity that subsumes the identity of another. Used in the context of merging documented entity instances. Both the player and scoper must have the same classCode. The use of this code is deprecated in favor of the term SUBY which is its inverse and is more ontologically correct.

_RoleClassPartitive | RoleClassPartitive | An association between two Entities where the playing Entity is considered in some way "part" of the scoping Entity, e.g., as a member, component, ingredient, or content. Being "part" in the broadest sense of the word can mean anything from being an integral structural component to a mere incidental temporary association of a playing Entity with a (generally larger) scoping Entity.

CONT | content | Relates a material as the content (player) to a container (scoper). Unlike ingredients, the content and a container remain separate (not mixed) and the content can be removed from the container. A content is not part of an empty container.

EXPAGTCAR | exposure agent carrier | An exposure agent carrier is an entity that is capable of conveying an exposure agent from one entity to another. The scoper of the role must be the exposure agent (e.g., pathogen).

EXPVECTOR | exposure vector | Description: A vector is a living subject that carries an exposure agent. The vector does not cause the disease itself, but exposes targets to the exposure agent. A mosquito carrying malaria is an example of a vector. The scoper of the role must be the exposure

agent (e.g., pathogen).

FOMITE | fomite | Description: A fomite is a non-living entity that is capable of conveying exposure agent from one entity to another. A doorknob contaminated with a Norovirus is an example of a fomite. Anyone touching the doorknob would be exposed to the virus. The scoper of the role must be the exposure agent (e.g., pathogen).

INGR | ingredient | Relates a component (player) to a mixture (scoper). E.g., Glucose and Water are ingredients of D5W, latex may be an ingredient in a tracheal tube.

ACTI | active ingredient | Definition: a therapeutically active ingredient (player) in a mixture (scoper), where the mixture is typically a manufactured pharmaceutical. It is unknown if the quantity of such an ingredient is expressed precisely in terms of the playing ingredient substance, or, if it is specified in terms of a closely related substance (active moiety or reference substance).

ACTIB | active ingredient - basis of strength | Description: Active ingredient, where the ingredient substance (player) is itself the "basis of strength", i.e., where the Role.quantity specifies exactly the quantity of the player substance in the medicine formulation. Examples: Lopressor 50 mg actually contains 50 mg of metoprolol succinate, even though the active moiety is metoprolol, but also: Tenormin 50 mg contain 50 mg of atenolol, as free base, i.e., where the active ingredient atenolol is also the active moiety.

ACTIM | active ingredient - moiety is basis of strength | Description: Active ingredient, where not the ingredient substance (player), but itaTMs active moiety is the "basis of strength", i.e., where the Role.quantity specifies the quantity of the player substance's active moiety in the medicine formulation. Examples: 1 mL of Betopic 5mg/mL eye drops contains 5.6 mg betaxolol hydrochloride equivalent to betaxolol base 5 mg.

ACTIR | active ingredient - reference substance is basis of strength | Description: Active ingredient, where not the ingredient substance (player) but another reference substance with the same active moiety, is the "basis of strength", i.e., where the Role.quantity specifies the quantity of a reference substance, similar but different from the player substance's in the medicine formulation. Examples: Toprol-XL 50 mg contains 47.5 mg of metoprolol succinate equivalent to 50 mg of metoprolol tartrate.

ADJV | adjuvant | A component (player) added to enhance the action of an active ingredient (scoper) (in the manner of a catalyst) but which has no active effect in and of itself. Such ingredients are significant in defining equivalence of products in a way that inactive ingredients are not.

ADTV | additive | An ingredient (player) that is added to a base (scoper), that amounts to a minor part of the overall mixture.

BASE | base | A base ingredient (player) is what comprises the major part of a mixture (scoper). E.g., Water in most i.v. solutions, or Vaseline in salves. Among all ingredients of a material, there should be only one base. A base substance can, in turn, be a mixture.

CNTM | contaminant ingredient | An ingredient whose presence is not intended but may not be reasonably avoided given the circumstances of the mixture's nature or origin.

IACT | inactive ingredient | An ingredient which is not considered therapeutically active, e.g., colors, flavors, stabilizers, or preservatives, fillers, or structural components added to an active ingredient in order to facilitate administration of the active ingredient but without being considered therapeutically active. An inactive ingredient need not be biologically inert, e.g., might be active as an allergen or might have a pleasant taste, but is not an essential constituent delivering the therapeutic effect.

COLR | color additive | A substance (player) influencing the optical aspect of material (scoper).

FLVR | flavor additive | A substance (player) added to a mixture (scoper) to make it taste a certain way. In food the use is obvious, in pharmaceuticals flavors can hide disgusting taste of the active ingredient (important in pediatric treatments).

PRSV | preservative | A substance (player) added to a mixture (scoper) to prevent microorganisms (fungi, bacteria) to spoil the mixture.

STBL | stabilizer | A stabilizer (player) added to a mixture (scoper) in order to prevent the molecular disintegration of the main substance.

MECH | mechanical ingredient | An ingredient (player) of a medication (scoper) that is inseparable from the active ingredients, but has no intended chemical or pharmaceutical effect itself, but which may have some systemic effect on the patient. An example is a collagen matrix used as a base for transplanting skin cells. The collagen matrix can be left permanently in the graft site. Because it is of bovine origin, the patient may exhibit allergies or may have cultural objections to its use.

LOCE | located entity | Relates an entity (player) to a location (scoper) at which it is present in some way. This presence may be limited in time.

STOR | stored entity | Relates an entity (player) (e.g. a device) to a location (scoper) at which it is normally found or stored when not used.

MBR | member | A role played by an entity that is a member of a group. The group provides the scope for this role. Among other uses, groups as used in insurance (groups of covered individuals) and in scheduling where resources may be grouped for scheduling and logistical purposes.

PART | part | Definition: an association between two Entities where the playing Entity (the part) is a component of the whole (scoper) in the sense of an integral structural component, that is distinct from other parts in the same whole, has a distinct function in the whole, and, as an effect, the full integrity of the whole depends (to some degree) on the presence of this part, even though the part may often be separable from the whole. Discussion: Part is defined in opposition to (a) ingredient (not separable), (b) content (not a functional component), and (c) member (not functionally distinct from other members).

ACTM | active moiety | The molecule or ion that is responsible for the intended pharmacological action of the drug substance, excluding those appended or associated parts of the molecule that make the molecule an ester, salt (including a salt with hydrogen or coordination bonds), or other noncovalent derivative (such as a complex, chelate, or clathrate). Examples: heparin-sodium and heparin-potassium have the same active moiety, heparin; the active moiety of morphine-hydrochloride is morphine.

SPEC | specimen | A role played by a material entity that is a specimen for an act. It is scoped by the source of the specimen.

ALQT | aliquot | A portion (player) of an original or source specimen (scoper) used for testing or transportation.

ISLT | isolate | A microorganism that has been isolated from other microorganisms or a source matrix.

4.3.2.13948 HL7 v3 Value Set ActClassClinicalDocument

URL: https://hl7.org/fhir/STU3/v3/ActClassClinicalDocument/vs.html

This page is part of the FHIR Specification (v3.0.2: STU 3). The current version which supercedes this version is 4.0.1. For a full list of available versions, see the Directory of published versions

Vocabulary Work Group | Maturity Level: N/A | External | Use Context: Any

This value set (http://hl7.org/fhir/ValueSet/v3-ActClassClinicalDocument) is defined as part of HL7 v3. Related FHIR content: ActClassClinicalDocument.

Summary

Defining URL: | http://hl7.org/fhir/ValueSet/v3-ActClassClinicalDocument

Name: | ActClassClinicalDocument

Definition: | A clinical document is a documentation of clinical observations and services, with the following characteristics: (1) Persistence - A clinical document continues to exist in an unaltered state, for a time period defined by local and regulatory requirements; (2) Stewardship - A clinical document is maintained by a person or organization entrusted with its care; (3) Potential for authentication - A clinical document is an assemblage of information that is intended to be legally authenticated; (4) Wholeness - Authentication of a clinical document applies to the whole and does not apply to portions of the document without the full context of the document; (5) Human readability - A clinical document is human readable."

OID: | 2.16.840.1.113883.1.11.13948 (for OID based terminology systems)
Source Resource | XML / JSON

This value set is not currently used

4.3.2.13948.1 Content Logical Definition

This value set includes codes from the following code systems:

* Include codes from http://hl7.org/fhir/v3/ActClass where concept is-a DOCCLIN

4.3.2.13948.2 Expansion

This expansion generated 19 Apr 2017

This value set contains 2 concepts

Expansion based on http://hl7.org/fhir/v3/ActClass version 2016-11-11

All codes from system http://hl7.org/fhir/v3/ActClass

Code | Display | Definition
DOCCLIN | clinical document | A clinical document is a documentation of clinical observations and services, with the following characteristics: Persistence - A clinical document continues to exist in an unaltered state, for a time period defined by local and regulatory requirements; Stewardship - A clinical document is maintained by a person or organization entrusted with its care; Potential for authentication - A clinical document is an assemblage of information that is intended to be legally authenticated; Wholeness - Authentication of a clinical document applies to the whole and does not apply to portions of the document without the full context of the document; Human readability - A clinical document is human readable.
CDALVLONE | CDA Level One clinical document | A clinical document that conforms to Level One of the HL7 Clinical Document Architecture (CDA)

4.3.2.13955 HL7 v3 Value Set ActEncounterCode

URL: https://hl7.org/fhir/STU3/v3/ActEncounterCode/vs.html

This page is part of the FHIR Specification (v3.0.2: STU 3). The current version which supercedes this version is 4.0.1. For a full list of available versions, see the Directory of published versions

Vocabulary Work Group | Maturity Level: N/A | External | Use Context: Any

This value set (http://hl7.org/fhir/ValueSet/v3-ActEncounterCode) is defined as part of HL7 v3. Related FHIR content: ActEncounterCode.

Summary

Defining URL: | http://hl7.org/fhir/ValueSet/v3-ActEncounterCode
Name: | ActEncounterCode
Definition: | Domain provides codes that qualify the ActEncounterClass (ENC)
OID: | 2.16.840.1.113883.1.11.13955 (for OID based terminology systems)
Source Resource | XML / JSON

This value set is used in the following places:

* Encounter.class (Extensible)

* Encounter.classHistory.class (Extensible)

4.3.2.13955.1 Content Logical Definition

This value set includes codes from the following code systems:

* Include codes from http://hl7.org/fhir/v3/ActCode where concept is-a _ActEncounterCode

* Exclude these codes as defined in

http://hl7.org/fhir/v3/ActCode

Code | Display
_ActEncounterCode | ActEncounterCode | Domain provides codes that qualify the ActEncounterClass (ENC)

4.3.2.13955.2 Expansion

This expansion generated 19 Apr 2017

This value set contains 10 concepts

Expansion based on http://hl7.org/fhir/v3/ActCode version 2016-11-11

All codes from system http://hl7.org/fhir/v3/ActCode

Code | Display | Definition
AMB | ambulatory | A comprehensive term for health care provided in a healthcare facility (e.g. a practitioneraTMs office, clinic setting, or hospital) on a nonresident basis. The term ambulatory usually implies that the patient has come to the location and is not assigned to a bed. Sometimes referred to as an outpatient encounter.
EMER | emergency | A patient encounter that takes place at a dedicated healthcare service delivery location where the patient receives immediate evaluation and treatment, provided until the patient can be discharged or responsibility for the patient's care is transferred elsewhere (for example, the patient could be admitted as an inpatient or transferred to another facility.)
FLD | field | A patient encounter that takes place both outside a dedicated service delivery location and outside a patient's residence. Example locations might include an accident site and at a supermarket.
HH | home health | Healthcare encounter that takes place in the residence of the patient or a designee

IMP | inpatient encounter | A patient encounter where a patient is admitted by a hospital or equivalent facility, assigned to a location where patients generally stay at least overnight and provided with room, board, and continuous nursing service.
ACUTE | inpatient acute | An acute inpatient encounter.
NONAC | inpatient non-acute | Any category of inpatient encounter except 'acute'
PRENC | pre-admission | A patient encounter where patient is scheduled or planned to receive service delivery in the future, and the patient is given a pre-admission account number. When the patient comes back for subsequent service, the pre-admission encounter is selected and is encapsulated into the service registration, and a new account number is generated. Usage Note: This is intended to be used in advance of encounter types such as ambulatory, inpatient encounter, virtual, etc.
SS | short stay | An encounter where the patient is admitted to a health care facility for a predetermined length of time, usually less than 24 hours.
VR | virtual | A patient encounter where the patient and the practitioner(s) are not in the same physical location. Examples include telephone conference, email exchange, robotic surgery, and televideo conference.

4.3.2.14006 HL7 v3 Value Set RoleClassAgent

URL: https://hl7.org/fhir/STU3/v3/RoleClassAgent/vs.html

This page is part of the FHIR Specification (v3.0.2: STU 3). The current version which supercedes this version is 4.0.1. For a full list of available versions, see the Directory of published versions

Vocabulary Work Group | Maturity Level: N/A | External | Use Context: Any

This value set (http://hl7.org/fhir/ValueSet/v3-RoleClassAgent) is defined as part of HL7 v3. Related FHIR content: RoleClassAgent.

Summary

Defining URL: | http://hl7.org/fhir/ValueSet/v3-RoleClassAgent
Name: | RoleClassAgent
Definition: | An entity (player) that acts or is authorized to act on behalf of another entity (scoper).
OID: | 2.16.840.1.113883.1.11.14006 (for OID based terminology systems)
Source Resource | XML / JSON

This value set is not currently used

4.3.2.14006.1 Content Logical Definition

This value set includes codes from the following code systems:

* Include codes from http://hl7.org/fhir/v3/RoleClass where concept is-a AGNT

4.3.2.14006.2 Expansion

This expansion generated 19 Apr 2017

This value set contains 8 concepts

Expansion based on http://hl7.org/fhir/v3/RoleClass version 2016-11-11

All codes from system http://hl7.org/fhir/v3/RoleClass

Code | Display | Definition
AGNT | agent | An entity (player) that acts or is authorized to act on behalf of another entity (scoper).
ASSIGNED | assigned entity | An agent role in which the agent is an Entity acting in the employ of an organization. The focus is on functional role on behalf of the organization, unlike the Employee role where the focus is on the 'Human Resources' relationship between the employee and the organization.
COMPAR | commissioning party | An Entity that is authorized to issue or instantiate permissions, privileges, credentials or other formal/legal authorizations.
SGNOFF | signing authority or officer | The role of a person (player) who is the officer or signature authority for of a scoping entity, usually an organization (scoper).
CON | contact | A person or an organization (player) which provides or receives information regarding another entity (scoper). Examples; patient NOK and emergency contacts; guarantor contact; employer contact.
ECON | emergency contact | An entity to be contacted in the event of an emergency.
NOK | next of kin | An individual designated for notification as the next of kin for a given entity.
GUARD | guardian | Guardian of a ward

4.3.2.16208 HL7 v3 Value Set ActPharmacySupplyType

URL: https://hl7.org/fhir/STU3/v3/ActPharmacySupplyType/vs.html

This page is part of the FHIR Specification (v3.0.2: STU 3). The current version which supercedes this version is 4.0.1. For a full list of available versions, see the Directory of published versions

Vocabulary Work Group | Maturity Level: N/A | External | Use Context: Any

This value set (http://hl7.org/fhir/ValueSet/v3-ActPharmacySupplyType) is defined as part of HL7 v3. Related FHIR content: ActPharmacySupplyType.

Summary

Defining URL: | http://hl7.org/fhir/ValueSet/v3-ActPharmacySupplyType
Name: | ActPharmacySupplyType
Definition: | Identifies types of dispensing events
OID: | 2.16.840.1.113883.1.11.16208 (for OID based terminology systems)
Source Resource | XML / JSON

This value set is used in the following places:

* MedicationDispense.type (Example)

4.3.2.16208.1 Content Logical Definition

This value set includes codes from the following code systems:

* Include codes from http://hl7.org/fhir/v3/ActCode where concept is-a _ActPharmacySupplyType

* Exclude these codes as defined in

http://hl7.org/fhir/v3/ActCode

Code | Display

_ActPharmacySupplyType | ActPharmacySupplyType | Identifies types of dispensing events

4.3.2.16208.2 Expansion

This expansion generated 19 Apr 2017

This value set contains 22 concepts

Expansion based on http://hl7.org/fhir/v3/ActCode version 2016-11-11

All codes from system http://hl7.org/fhir/v3/ActCode

Code | Display | Definition

DF | Daily Fill | A fill providing sufficient supply for one day

EM | Emergency Supply | A supply action where there is no 'valid' order for the supplied medication. E.g. Emergency vacation supply, weekend supply (when prescriber is unavailable to provide a renewal prescription)

SO | Script Owing | An emergency supply where the expectation is that a formal order authorizing the supply will be provided at a later date.

FF | First Fill | The initial fill against an order. (This includes initial fills against refill orders.)

FFC | First Fill - Complete | A first fill where the quantity supplied is equal to one full repetition of the ordered amount. (e.g. If the order was 90 tablets, 3 refills, a complete fill would be for the full 90 tablets).

FFP | First Fill - Part Fill | A first fill where the quantity supplied is less than one full repetition of the ordered amount. (e.g. If the order was 90 tablets, 3 refills, a partial fill might be for only 30 tablets.)

FFSS | first fill, partial strength | A first fill where the strength supplied is less than the ordered strength. (e.g. 10mg for an order of 50mg where a subsequent fill will dispense 40mg tablets).

TF | Trial Fill | A fill where a small portion is provided to allow for determination of the therapy effectiveness and patient tolerance.

FS | Floor stock | A supply action to restock a smaller more local dispensary.

MS | Manufacturer Sample | A supply of a manufacturer sample

RF | Refill | A fill against an order that has already been filled (or partially filled) at least once.

UD | Unit Dose | A supply action that provides sufficient material for a single dose.

RFC | Refill - Complete | A refill where the quantity supplied is equal to one full repetition of the ordered amount. (e.g. If the order was 90 tablets, 3 refills, a complete fill would be for the full 90 tablets.)

RFCS | refill complete partial strength | A refill where the quantity supplied is equal to one full repetition of the ordered amount. (e.g. If the order was 90 tablets, 3 refills, a complete fill would be for the full 90 tablets.) and where the strength supplied is less than the ordered strength (e.g. 10mg for an order of 50mg where a subsequent fill will dispense 40mg tablets).

RFF | Refill (First fill this facility) | The first fill against an order that has already been filled at least once at another facility.

RFFS | refill partial strength (first fill this facility) | The first fill against an order that has already been filled at least once at another facility and where the strength supplied is less than the ordered strength (e.g. 10mg for an order of 50mg where a subsequent fill will dispense 40mg tablets).

RFP | Refill - Part Fill | A refill where the quantity supplied is less than one full repetition of the ordered amount. (e.g. If the order was 90 tablets, 3 refills, a partial fill might be for only 30 tablets.)

RFPS | refill part fill partial strength | A refill where the quantity supplied is less than one full repetition of the ordered amount. (e.g. If the order was 90 tablets, 3 refills, a partial fill might be for only 30 tablets.) and where the strength supplied is less than the ordered strength (e.g. 10mg for an order of 50mg where a subsequent fill will dispense 40mg tablets).

RFS | refill partial strength | A fill against an order that has already been filled (or partially filled) at least once and where the strength supplied is less than the ordered strength (e.g. 10mg for an order of 50mg where a subsequent fill will dispense 40mg tablets).

TB | Trial Balance | A fill where the remainder of a 'complete' fill is provided after a trial fill has been provided.

TBS | trial balance partial strength | A fill where the remainder of a 'complete' fill is provided after a trial fill has been provided and where the strength supplied is less than the ordered strength (e.g. 10mg for an order of 50mg where a subsequent fill will dispense 40mg tablets).

UDE | unit dose equivalent | A supply action that provides sufficient material for a single dose via multiple products. E.g. 2 50mg tablets for a 100mg unit dose.

4.3.2.16226 HL7 v3 Value Set ObservationType

URL: https://hl7.org/fhir/STU3/v3/ObservationType/vs.html

This page is part of the FHIR Specification (v3.0.2: STU 3). The current version which supercedes this version is 4.0.1. For a full list of available versions, see the Directory of published versions

Vocabulary Work Group | Maturity Level: N/A | External | Use Context: Any

This value set (http://hl7.org/fhir/ValueSet/v3-ObservationType) is defined as part of HL7 v3. Related FHIR content: ObservationType.

Summary

Defining URL: | http://hl7.org/fhir/ValueSet/v3-ObservationType

Name: | ObservationType

Definition: | Identifies the kinds of observations that can be performed

OID: | 2.16.840.1.113883.1.11.16226 (for OID based terminology systems)
Source Resource | XML / JSON

This value set is not currently used

4.3.2.16226.1 Content Logical Definition

This value set includes codes from the following code systems:

* Include codes from http://hl7.org/fhir/v3/ActCode where concept is-a _ObservationType

* Include all codes defined in http://loinc.org

4.3.2.16226.2 Expansion

This expansion generated 19 Apr 2017

This value set has >1000 codes in it. In order to keep the publication size manageable, only a selection (1000 codes) of the whole set of codes is shown

Code | System | Display | Definition
_ObservationType | http://hl7.org/fhir/v3/ActCode | ObservationType | Identifies the kinds of observations that can be performed
_ActSpecObsCode | http://hl7.org/fhir/v3/ActCode | ActSpecObsCode | Identifies the type of observation that is made about a specimen that may affect its processing, analysis or further result interpretation
ARTBLD | http://hl7.org/fhir/v3/ActCode | ActSpecObsArtBldCode | Describes the artificial blood identifier that is associated with the specimen.
DILUTION | http://hl7.org/fhir/v3/ActCode | ActSpecObsDilutionCode | An observation that reports the dilution of a sample.
AUTO-HIGH | http://hl7.org/fhir/v3/ActCode | Auto-High Dilution | The dilution of a sample performed by automated equipment. The value is specified by the equipment
AUTO-LOW | http://hl7.org/fhir/v3/ActCode | Auto-Low Dilution | The dilution of a sample performed by automated equipment. The value is specified by the equipment
PRE | http://hl7.org/fhir/v3/ActCode | Pre-Dilution | The dilution of the specimen made prior to being loaded onto analytical equipment
RERUN | http://hl7.org/fhir/v3/ActCode | Rerun Dilution | The value of the dilution of a sample after it had been analyzed at a prior dilution value
EVNFCTS | http://hl7.org/fhir/v3/ActCode | ActSpecObsEvntfctsCode | Domain provides codes that qualify the ActLabObsEnvfctsCode domain. (Environmental Factors)
INTFR | http://hl7.org/fhir/v3/ActCode | ActSpecObsInterferenceCode | An observation that relates to factors that may potentially cause interference with the observation
FIBRIN | http://hl7.org/fhir/v3/ActCode | Fibrin | The Fibrin Index of the specimen. In the case of only differentiating between Absent and Present, recommend using 0 and 1
HEMOLYSIS | http://hl7.org/fhir/v3/ActCode | Hemolysis | An observation of the hemolysis index of the specimen in g/L
ICTERUS | http://hl7.org/fhir/v3/ActCode | Icterus | An observation that describes the icterus index of the specimen. It is recommended to use mMol/L of bilirubin
LIPEMIA | http://hl7.org/fhir/v3/ActCode | Lipemia | An observation used to describe the Lipemia Index of the specimen. It is recommended to use the optical turbidity at 600 nm (in absorbance units).
VOLUME | http://hl7.org/fhir/v3/ActCode | ActSpecObsVolumeCode | An observation that reports the volume of a sample.
AVAILABLE | http://hl7.org/fhir/v3/ActCode | Available Volume | The available quantity of specimen. This is the current quantity minus any planned consumption (e.g., tests that are planned)
CONSUMPTION | http://hl7.org/fhir/v3/ActCode | Consumption Volume | The quantity of specimen that is used each time the equipment uses this substance
CURRENT | http://hl7.org/fhir/v3/ActCode | Current Volume | The current quantity of the specimen, i.e., initial quantity minus what has been actually used.
INITIAL | http://hl7.org/fhir/v3/ActCode | Initial Volume | The initial quantity of the specimen in inventory
_AnnotationType | http://hl7.org/fhir/v3/ActCode | AnnotationType | AnnotationType
_ActPatientAnnotationType | http://hl7.org/fhir/v3/ActCode | ActPatientAnnotationType | Description:Provides a categorization for annotations recorded directly against the patient .
ANNDI | http://hl7.org/fhir/v3/ActCode | diagnostic image note | Description:A note that is specific to a patient's diagnostic images, either historical, current or planned.
ANNGEN | http://hl7.org/fhir/v3/ActCode | general note | Description:A general or uncategorized note.
ANNIMM | http://hl7.org/fhir/v3/ActCode | immunization note | A note that is specific to a patient's immunizations, either historical, current or planned.
ANNLAB | http://hl7.org/fhir/v3/ActCode | laboratory note | Description:A note that is specific to a patient's laboratory results, either historical, current or planned.
ANNMED | http://hl7.org/fhir/v3/ActCode | medication note | Description:A note that is specific to a patient's medications, either historical, current or planned.
_GeneticObservationType | http://hl7.org/fhir/v3/ActCode | GeneticObservationType | Description: None provided
GENE | http://hl7.org/fhir/v3/ActCode | gene | Description: A DNA segment that contributes to phenotype/function. In the absence of demonstrated function a gene may be characterized by sequence, transcription or homology
_ImmunizationObservationType | http://hl7.org/fhir/v3/ActCode | ImmunizationObservationType | Description: Observation codes which describe characteristics of the immunization material.
OBSANTC | http://hl7.org/fhir/v3/ActCode | antigen count | Description: Indicates the valid antigen count.
OBSANTV | http://hl7.org/fhir/v3/ActCode | antigen validity | Description: Indicates whether an antigen is valid or invalid.
_IndividualCaseSafetyReportType | http://hl7.org/fhir/v3/ActCode | Individual Case Safety Report Type | A code that is used to indicate the type of case safety report received from sender. The current code example reference is from the International Conference on Harmonisation (ICH) Expert Workgroup guideline on Clinical Safety Data Management: Data Elements for Transmission of Individual Case Safety Reports. The unknown/unavailable option allows the transmission of information from a secondary sender where the initial sender did not specify the type of report. Example concepts include: Spontaneous, Report from study, Other.
PAT_ADV_EVNT | http://hl7.org/fhir/v3/ActCode | patient adverse event | Indicates that the ICSR is describing problems that a patient experienced after receiving a vaccine product.
VAC_PROBLEM | http://hl7.org/fhir/v3/ActCode | vaccine product problem | Indicates that the ICSR is describing a problem with the actual vaccine product such as physical defects (cloudy, particulate matter) or inability to confer immunity.

_LOINCObservationActContextAgeType | http://hl7.org/fhir/v3/ActCode | LOINCObservationActContextAgeType | Definition:The set of LOINC codes for the act of determining the period of time that has elapsed since an entity was born or created.

21611-9 | http://hl7.org/fhir/v3/ActCode | age patient qn est | Definition:Estimated age.

21612-7 | http://hl7.org/fhir/v3/ActCode | age patient qn reported | Definition:Reported age.

29553-5 | http://hl7.org/fhir/v3/ActCode | age patient qn calc | Definition:Calculated age.

30525-0 | http://hl7.org/fhir/v3/ActCode | age patient qn definition | Definition:General specification of age with no implied method of determination.

30972-4 | http://hl7.org/fhir/v3/ActCode | age at onset of adverse event | Definition:Age at onset of associated adverse event; no implied method of determination.

_MedicationObservationType | http://hl7.org/fhir/v3/ActCode | MedicationObservationType | MedicationObservationType

REP_HALF_LIFE | http://hl7.org/fhir/v3/ActCode | representative half-life | Description:This observation represents an 'average' or 'expected' half-life typical of the product.

SPLCOATING | http://hl7.org/fhir/v3/ActCode | coating | Definition: A characteristic of an oral solid dosage form of a medicinal product, indicating whether it has one or more coatings such as sugar coating, film coating, or enteric coating. Only coatings to the external surface or the dosage form should be considered (for example, coatings to individual pellets or granules inside a capsule or tablet are excluded from consideration). Constraints: The Observation.value must be a Boolean (BL) with true for the presence or false for the absence of one or more coatings on a solid dosage form.

SPLCOLOR | http://hl7.org/fhir/v3/ActCode | color | Definition: A characteristic of an oral solid dosage form of a medicinal product, specifying the color or colors that most predominantly define the appearance of the dose form. SPLCOLOR is not an FDA specification for the actual color of solid dosage forms or the names of colors that can appear in labeling. Constraints: The Observation.value must be a single coded value or a list of multiple coded values, specifying one or more distinct colors that approximate of the color(s) of distinct areas of the solid dosage form, such as the different sides of a tablet or one-part capsule, or the different halves of a two-part capsule. Bands on banded capsules, regardless of the color, are not considered when assigning an SPLCOLOR. Imprints on the dosage form, regardless of their color are not considered when assigning an SPLCOLOR. If more than one color exists on a particular side or half, then the most predominant color on that side or half is recorded. If the gelatin capsule shell is colorless and transparent, use the predominant color of the contents that appears through the colorless and transparent capsule shell. Colors can include: Black;Gray;White;Red;Pink;Purple;Green;Yellow;Orange;Brown;Blue;Turquoise.

SPLIMAGE | http://hl7.org/fhir/v3/ActCode | image | Description: A characteristic representing a single file reference that contains two or more views of the same dosage form of the product; in most cases this should represent front and back views of the dosage form, but occasionally additional views might be needed in order to capture all of the important physical characteristics of the dosage form. Any imprint and/or symbol should be clearly identifiable, and the viewer should not normally need to rotate the image in order to read it. Images that are submitted with SPL should be included in the same directory as the SPL file.

SPLIMPRINT | http://hl7.org/fhir/v3/ActCode | imprint | Definition: A characteristic of an oral solid dosage form of a medicinal product, specifying the alphanumeric text that appears on the solid dosage form, including text that is embossed, debossed, engraved or printed with ink. The presence of other non-textual distinguishing marks or symbols is recorded by SPLSYMBOL. Examples: Included in SPLIMPRINT are alphanumeric text that appears on the bands of banded capsules and logos and other symbols that can be interpreted as letters or numbers. Constraints: The Observation.value must be of type Character String (ST). Excluded from SPLIMPRINT are internal and external cut-outs in the form of alphanumeric text and the letter 'R' with a circle around it (when referring to a registered trademark) and the letters 'TM' (when referring to a 'trade mark'). To record text, begin on either side or part of the dosage form. Start at the top left and progress as one would normally read a book. Enter a semicolon to show separation between words or line divisions.

SPLSCORING | http://hl7.org/fhir/v3/ActCode | scoring | Definition: A characteristic of an oral solid dosage form of a medicinal product, specifying the number of equal pieces that the solid dosage form can be divided into using score line(s). Example: One score line creating two equal pieces is given a value of 2, two parallel score lines creating three equal pieces is given a value of 3. Constraints: Whether three parallel score lines create four equal pieces or two intersecting score lines create two equal pieces using one score line and four equal pieces using both score lines, both have the scoring value of 4. Solid dosage forms that are not scored are given a value of 1. Solid dosage forms that can only be divided into unequal pieces are given a null-value with nullFlavor other (OTH).

SPLSHAPE | http://hl7.org/fhir/v3/ActCode | shape | Description: A characteristic of an oral solid dosage form of a medicinal product, specifying the two dimensional representation of the solid dose form, in terms of the outside perimeter of a solid dosage form when the dosage form, resting on a flat surface, is viewed from directly above, including slight rounding of corners. SPLSHAPE does not include embossing, scoring, debossing, or internal cut-outs. SPLSHAPE is independent of the orientation of the imprint and logo. Shapes can include: Triangle (3 sided); Square; Round; Semicircle; Pentagon (5 sided); Diamond; Double circle; Bullet; Hexagon (6 sided); Rectangle; Gear; Capsule; Heptagon (7 sided); Trapezoid; Oval; Clover; Octagon (8 sided); Tear; Freeform.

SPLSIZE | http://hl7.org/fhir/v3/ActCode | size | Definition: A characteristic of an oral solid dosage form of a medicinal product, specifying the longest single dimension of the solid dosage form as a physical quantity in the dimension of length (e.g., 3 mm). The length is should be specified in millimeters and should be rounded to the nearest whole millimeter. Example: SPLSIZE for a rectangular shaped tablet is the length and SPLSIZE for a round shaped tablet is the diameter.

SPLSYMBOL | http://hl7.org/fhir/v3/ActCode | symbol | Definition: A characteristic of an oral solid dosage form of a medicinal product, to describe whether or not the medicinal product has a mark or symbol appearing on it for easy and definite recognition. Score lines, letters, numbers, and internal and external cut-outs are not considered marks or symbols. See SPLSCORING and SPLIMPRINT for these characteristics. Constraints: The Observation.value must be a Boolean (BL) with <u>true</u> indicating the presence and <u>false</u> for the absence of marks or symbols. Example:

_ObservationIssueTriggerCodedObservationType | http://hl7.org/fhir/v3/ActCode | ObservationIssueTriggerCodedObservationType | Distinguishes the kinds of coded observations that could be the trigger for clinical issue detection. These are observations that are not measurable, but instead can be defined with codes. Coded observation types include: Allergy, Intolerance, Medical Condition, Pregnancy status, etc.

_CaseTransmissionMode | http://hl7.org/fhir/v3/ActCode | case transmission mode | Code for the mechanism by which disease was acquired by the living subject involved in the public health case. Includes sexually transmitted, airborne, bloodborne, vectorborne, foodborne, zoonotic, nosocomial, mechanical, dermal, congenital, environmental exposure, indeterminate.

AIRTRNS | http://hl7.org/fhir/v3/ActCode | airborne transmission | Communication of an agent from a living subject or environmental source to a living subject through indirect contact via oral or nasal inhalation.

ANANTRNS | http://hl7.org/fhir/v3/ActCode | animal to animal transmission | Communication of an agent from one animal to another proximate animal.

ANHUMTRNS | http://hl7.org/fhir/v3/ActCode | animal to human transmission | Communication of an agent from an animal to a proximate person.

BDYFLDTRNS | http://hl7.org/fhir/v3/ActCode | body fluid contact transmission | Communication of an agent from one living subject to another living subject through direct contact with any body fluid.

BLDTRNS | http://hl7.org/fhir/v3/ActCode | blood borne transmission | Communication of an agent to a living subject through direct contact with blood or blood products whether the contact with blood is part of a therapeutic procedure or not.

DERMTRNS | http://hl7.org/fhir/v3/ActCode | transdermal transmission | Communication of an agent from a living subject or environmental source to a living subject via agent migration through intact skin.

ENVTRNS | http://hl7.org/fhir/v3/ActCode | environmental exposure transmission | Communication of an agent from an environmental surface or source to a living subject by direct contact.

FECTRNS | http://hl7.org/fhir/v3/ActCode | fecal-oral transmission | Communication of an agent from a living subject or environmental source to a living subject through oral contact with material contaminated by person or animal fecal material.
FOMTRNS | http://hl7.org/fhir/v3/ActCode | fomite transmission | Communication of an agent from an non-living material to a living subject through direct contact.
FOODTRNS | http://hl7.org/fhir/v3/ActCode | food-borne transmission | Communication of an agent from a food source to a living subject via oral consumption.
HUMHUMTRNS | http://hl7.org/fhir/v3/ActCode | human to human transmission | Communication of an agent from a person to a proximate person.
INDTRNS | http://hl7.org/fhir/v3/ActCode | indeterminate disease transmission mode | Communication of an agent to a living subject via an undetermined route.
LACTTRNS | http://hl7.org/fhir/v3/ActCode | lactation transmission | Communication of an agent from one living subject to another living subject through direct contact with mammalian milk or colostrum.
NOSTRNS | http://hl7.org/fhir/v3/ActCode | nosocomial transmission | Communication of an agent from any entity to a living subject while the living subject is in the patient role in a healthcare facility.
PARTRNS | http://hl7.org/fhir/v3/ActCode | parenteral transmission | Communication of an agent from a living subject or environmental source to a living subject where the acquisition of the agent is not via the alimentary canal.
PLACTRNS | http://hl7.org/fhir/v3/ActCode | transplacental transmission | Communication of an agent from a living subject to the progeny of that living subject via agent migration across the maternal-fetal placental membranes while in utero.
SEXTRNS | http://hl7.org/fhir/v3/ActCode | sexual transmission | Communication of an agent from one living subject to another living subject through direct contact with genital or oral tissues as part of a sexual act.
TRNSFTRNS | http://hl7.org/fhir/v3/ActCode | transfusion transmission | Communication of an agent from one living subject to another living subject through direct contact with blood or blood products where the contact with blood is part of a therapeutic procedure.
VECTRNS | http://hl7.org/fhir/v3/ActCode | vector-borne transmission | Communication of an agent from a living subject acting as a required intermediary in the agent transmission process to a recipient living subject via direct contact.
WATTRNS | http://hl7.org/fhir/v3/ActCode | water-borne transmission | Communication of an agent from a contaminated water source to a living subject whether the water is ingested as a food or not. The route of entry of the water may be through any bodily orifice.
_ObservationQualityMeasureAttribute | http://hl7.org/fhir/v3/ActCode | ObservationQualityMeasureAttribute | Codes used to define various metadata aspects of a health quality measure.
AGGREGATE | http://hl7.org/fhir/v3/ActCode | aggregate measure observation | Indicates that the observation is carrying out an aggregation calculation, contained in the value element.
CMPMSRMTH | http://hl7.org/fhir/v3/ActCode | composite measure method | Indicates what method is used in a quality measure to combine the component measure results included in an composite measure.
CMPMSRSCRWGHT | http://hl7.org/fhir/v3/ActCode | component measure scoring weight | An attribute of a quality measure describing the weight this component measure score is to carry in determining the overall composite measure final score. The value is real value greater than 0 and less than 1.0. Each component measure score will be multiplied by its CMPMSRSCRWGHT and then summed with the other component measures to determine the final overall composite measure score. The sum across all CMPMSRSCRWGHT values within a single composite measure SHALL be 1.0. The value assigned is scoped to the composite measure referencing this component measure only.
COPY | http://hl7.org/fhir/v3/ActCode | copyright | Identifies the organization(s) who own the intellectual property represented by the eMeasure.
CRS | http://hl7.org/fhir/v3/ActCode | clinical recommendation statement | Summary of relevant clinical guidelines or other clinical recommendations supporting this eMeasure.
DEF | http://hl7.org/fhir/v3/ActCode | definition | Description of individual terms, provided as needed.
DISC | http://hl7.org/fhir/v3/ActCode | disclaimer | Disclaimer information for the eMeasure.
FINALDT | http://hl7.org/fhir/v3/ActCode | finalized date/time | The timestamp when the eMeasure was last packaged in the Measure Authoring Tool.
GUIDE | http://hl7.org/fhir/v3/ActCode | guidance | Used to allow measure developers to provide additional guidance for implementers to understand greater specificity than could be provided in the logic for data criteria.
IDUR | http://hl7.org/fhir/v3/ActCode | improvement notation | Information on whether an increase or decrease in score is the preferred result (e.g., a higher score indicates better quality OR a lower score indicates better quality OR quality is within a range).
ITMCNT | http://hl7.org/fhir/v3/ActCode | items counted | Describes the items counted by the measure (e.g., patients, encounters, procedures, etc.)
KEY | http://hl7.org/fhir/v3/ActCode | keyword | A significant word that aids in discoverability.
MEDT | http://hl7.org/fhir/v3/ActCode | measurement end date | The end date of the measurement period.
MSD | http://hl7.org/fhir/v3/ActCode | measurement start date | The start date of the measurement period.
MSRADJ | http://hl7.org/fhir/v3/ActCode | risk adjustment | The method of adjusting for clinical severity and conditions present at the start of care that can influence patient outcomes for making valid comparisons of outcome measures across providers. Indicates whether an eMeasure is subject to the statistical process for reducing, removing, or clarifying the influences of confounding factors to allow more useful comparisons.
MSRAGG | http://hl7.org/fhir/v3/ActCode | rate aggregation | Describes how to combine information calculated based on logic in each of several populations into one summarized result. It can also be used to describe how to risk adjust the data based on supplemental data elements described in the eMeasure. (e.g., pneumonia hospital measures antibiotic selection in the ICU versus non-ICU and then the roll-up of the two). Open Issue: The description does NOT align well with the definition used in the HQMF specfication; correct the MSGAGG definition, and the possible distinction of MSRAGG as a child of AGGREGATE.
MSRIMPROV | http://hl7.org/fhir/v3/ActCode | health quality measure improvement notation | Information on whether an increase or decrease in score is the preferred result. This should reflect information on which way is better, an increase or decrease in score.
MSRJUR | http://hl7.org/fhir/v3/ActCode | jurisdiction | The list of jurisdiction(s) for which the measure applies.
MSRRPTR | http://hl7.org/fhir/v3/ActCode | reporter type | Type of person or organization that is expected to report the issue.
MSRRPTTIME | http://hl7.org/fhir/v3/ActCode | timeframe for reporting | The maximum time that may elapse following completion of the measure until the measure report must be sent to the receiver.
MSRSCORE | http://hl7.org/fhir/v3/ActCode | measure scoring | Indicates how the calculation is performed for the eMeasure (e.g., proportion, continuous variable, ratio)
MSRSET | http://hl7.org/fhir/v3/ActCode | health quality measure care setting | Location(s) in which care being measured is rendered Usage Note: MSRSET is used rather than RoleCode because the setting applies to what is being measured, as opposed to participating directly in the health quality measure documantion itself).
MSRTOPIC | http://hl7.org/fhir/v3/ActCode | health quality measure topic type | health quality measure topic type
MSRTP | http://hl7.org/fhir/v3/ActCode | measurement period | The time period for which the eMeasure applies.
MSRTYPE | http://hl7.org/fhir/v3/ActCode | measure type | Indicates whether the eMeasure is used to examine a process or an outcome over time (e.g., Structure, Process, Outcome).
RAT | http://hl7.org/fhir/v3/ActCode | rationale | Succinct statement of the need for the measure. Usually includes statements pertaining to Importance criterion: impact, gap in care and evidence.

REF | http://hl7.org/fhir/v3/ActCode | reference | Identifies bibliographic citations or references to clinical practice guidelines, sources of evidence, or other relevant materials supporting the intent and rationale of the eMeasure.

SDE | http://hl7.org/fhir/v3/ActCode | supplemental data elements | Comparison of results across strata can be used to show where disparities exist or where there is a need to expose differences in results. For example, Centers for Medicare & Medicaid Services (CMS) in the U.S. defines four required Supplemental Data Elements (payer, ethnicity, race, and gender), which are variables used to aggregate data into various subgroups. Additional supplemental data elements required for risk adjustment or other purposes of data aggregation can be included in the Supplemental Data Element section.

STRAT | http://hl7.org/fhir/v3/ActCode | stratification | Describes the strata for which the measure is to be evaluated. There are three examples of reasons for stratification based on existing work. These include: (1) evaluate the measure based on different age groupings within the population described in the measure (e.g., evaluate the whole [age 14-25] and each sub-stratum [14-19] and [20-25]); (2) evaluate the eMeasure based on either a specific condition, a specific discharge location, or both; (3) evaluate the eMeasure based on different locations within a facility (e.g., evaluate the overall rate for all intensive care units and also some strata include additional findings [specific birth weights for neonatal intensive care units]).

TRANF | http://hl7.org/fhir/v3/ActCode | transmission format | Can be a URL or hyperlinks that link to the transmission formats that are specified for a particular reporting program.

USE | http://hl7.org/fhir/v3/ActCode | notice of use | Usage notes.

_ObservationSequenceType | http://hl7.org/fhir/v3/ActCode | ObservationSequenceType | ObservationSequenceType

TIME_ABSOLUTE | http://hl7.org/fhir/v3/ActCode | absolute time sequence | A sequence of values in the "absolute" time domain. This is the same time domain that all HL7 timestamps use. It is time as measured by the Gregorian calendar

TIME_RELATIVE | http://hl7.org/fhir/v3/ActCode | relative time sequence | A sequence of values in a "relative" time domain. The time is measured relative to the earliest effective time in the Observation Series containing this sequence.

_ObservationSeriesType | http://hl7.org/fhir/v3/ActCode | ObservationSeriesType | ObservationSeriesType

_ECGObservationSeriesType | http://hl7.org/fhir/v3/ActCode | ECGObservationSeriesType | ECGObservationSeriesType

REPRESENTATIVE_BEAT | http://hl7.org/fhir/v3/ActCode | ECG representative beat waveforms | This Observation Series type contains waveforms of a "representative beat" (a.k.a. "median beat" or "average beat"). The waveform samples are measured in relative time, relative to the beginning of the beat as defined by the Observation Series effective time. The waveforms are not directly acquired from the subject, but rather algorithmically derived from the "rhythm" waveforms.

RHYTHM | http://hl7.org/fhir/v3/ActCode | ECG rhythm waveforms | This Observation type contains ECG "rhythm" waveforms. The waveform samples are measured in absolute time (a.k.a. "subject time" or "effective time"). These waveforms are usually "raw" with some minimal amount of noise reduction and baseline filtering applied.

_PatientImmunizationRelatedObservationType | http://hl7.org/fhir/v3/ActCode | PatientImmunizationRelatedObservationType | Description: Reporting codes that are related to an immunization event.

CLSSRM | http://hl7.org/fhir/v3/ActCode | classroom | Description: The class room associated with the patient during the immunization event.

GRADE | http://hl7.org/fhir/v3/ActCode | grade | Description: The school grade or level the patient was in when immunized.

SCHL | http://hl7.org/fhir/v3/ActCode | school | Description: The school the patient attended when immunized.

SCHLDIV | http://hl7.org/fhir/v3/ActCode | school division | Description: The school division or district associated with the patient during the immunization event.

TEACHER | http://hl7.org/fhir/v3/ActCode | teacher | Description: The patient's teacher when immunized.

_PopulationInclusionObservationType | http://hl7.org/fhir/v3/ActCode | PopulationInclusionObservationType | Observation types for specifying criteria used to assert that a subject is included in a particular population.

DENEX | http://hl7.org/fhir/v3/ActCode | denominator exclusions | Criteria which specify subjects who should be removed from the eMeasure population and denominator before determining if numerator criteria are met. Denominator exclusions are used in proportion and ratio measures to help narrow the denominator.

DENEXCEP | http://hl7.org/fhir/v3/ActCode | denominator exceptions | Criteria which specify the removal of a subject, procedure or unit of measurement from the denominator, only if the numerator criteria are not met. Denominator exceptions allow for adjustment of the calculated score for those providers with higher risk populations. Denominator exceptions are used only in proportion eMeasures. They are not appropriate for ratio or continuous variable eMeasures. Denominator exceptions allow for the exercise of clinical judgment and should be specifically defined where capturing the information in a structured manner fits the clinical workflow. Generic denominator exception reasons used in proportion eMeasures fall into three general categories: Medical reasons Patient (or subject) reasons System reasons

DENOM | http://hl7.org/fhir/v3/ActCode | denominator | Criteria for specifying the entities to be evaluated by a specific quality measure, based on a shared common set of characteristics (within a specific measurement set to which a given measure belongs). The denominator can be the same as the initial population, or it may be a subset of the initial population to further constrain it for the purpose of the eMeasure. Different measures within an eMeasure set may have different denominators. Continuous Variable eMeasures do not have a denominator, but instead define a measure population.

IPOP | http://hl7.org/fhir/v3/ActCode | initial population | Criteria for specifying the entities to be evaluated by a specific quality measure, based on a shared common set of characteristics (within a specific measurement set to which a given measure belongs).

IPPOP | http://hl7.org/fhir/v3/ActCode | initial patient population | Criteria for specifying the patients to be evaluated by a specific quality measure, based on a shared common set of characteristics (within a specific measurement set to which a given measure belongs). Details often include information based upon specific age groups, diagnoses, diagnostic and procedure codes, and enrollment periods.

MSRPOPL | http://hl7.org/fhir/v3/ActCode | measure population | Criteria for specifying the measure population as a narrative description (e.g., all patients seen in the Emergency Department during the measurement period). This is used only in continuous variable eMeasures.

MSRPOPLEX | http://hl7.org/fhir/v3/ActCode | measure population exclusions | Criteria for specifying subjects who should be removed from the eMeasure's Initial Population and Measure Population. Measure Population Exclusions are used in Continuous Variable measures to help narrow the Measure Population before determining the value(s) of the continuous variable(s).

NUMER | http://hl7.org/fhir/v3/ActCode | numerator | Criteria for specifying the processes or outcomes expected for each patient, procedure, or other unit of measurement defined in the denominator for proportion measures, or related to (but not directly derived from) the denominator for ratio measures (e.g., a numerator listing the number of central line blood stream infections and a denominator indicating the days per thousand of central line usage in a specific time period).

NUMEX | http://hl7.org/fhir/v3/ActCode | numerator exclusions | Criteria for specifying instances that should not be included in the numerator data. (e.g., if the number of central line blood stream infections per 1000 catheter days were to exclude infections with a specific bacterium, that bacterium would be listed as a numerator exclusion). Numerator Exclusions are used only in ratio eMeasures.

_PreferenceObservationType | http://hl7.org/fhir/v3/ActCode | _PreferenceObservationType | Types of observations that can be made about Preferences.

PREFSTRENGTH | http://hl7.org/fhir/v3/ActCode | preference strength | An observation about how important a preference is to the target of the preference.

ADVERSE_REACTION | http://hl7.org/fhir/v3/ActCode | Adverse Reaction | Indicates that the observation is of an unexpected negative occurrence in the subject suspected to result from the subject's exposure to one or more agents. Observation values would be the symptom resulting from the

reaction.

ASSERTION | http://hl7.org/fhir/v3/ActCode | Assertion | Description:Refines classCode OBS to indicate an observation in which observation.value contains a finding or other nominalized statement, where the encoded information in Observation.value is not altered by Observation.code. For instance, observation.code="ASSERTION" and observation.value="fracture of femur present" is an assertion of a clinical finding of femur fracture.

CASESER | http://hl7.org/fhir/v3/ActCode | case seriousness criteria | Definition:An observation that provides a characterization of the level of harm to an investigation subject as a result of a reaction or event.

CDIO | http://hl7.org/fhir/v3/ActCode | case disease imported observation | An observation that states whether the disease was likely acquired outside the jurisdiction of observation, and if so, the nature of the inter-jurisdictional relationship. OpenIssue: This code could be moved to LOINC if it can be done before there are significant implemenations using it.

CRIT | http://hl7.org/fhir/v3/ActCode | criticality | A clinical judgment as to the worst case result of a future exposure (including substance administration). When the worst case result is assessed to have a life-threatening or organ system threatening potential, it is considered to be of high criticality.

CTMO | http://hl7.org/fhir/v3/ActCode | case transmission mode observation | An observation that states the mechanism by which disease was acquired by the living subject involved in the public health case. OpenIssue: This code could be moved to LOINC if it can be done before there are significant implemenations using it.

DX | http://hl7.org/fhir/v3/ActCode | ObservationDiagnosisTypes | Includes all codes defining types of indications such as diagnosis, symptom and other indications such as contrast agents for lab tests.

ADMDX | http://hl7.org/fhir/v3/ActCode | admitting diagnosis | Admitting diagnosis are the diagnoses documented for administrative purposes as the basis for a hospital admission.

DISDX | http://hl7.org/fhir/v3/ActCode | discharge diagnosis | Discharge diagnosis are the diagnoses documented for administrative purposes as the time of hospital discharge.

INTDX | http://hl7.org/fhir/v3/ActCode | intermediate diagnosis | Intermediate diagnoses are those diagnoses documented for administrative purposes during the course of a hospital stay.

NOI | http://hl7.org/fhir/v3/ActCode | nature of injury | The type of injury that the injury coding specifies.

GISTIER | http://hl7.org/fhir/v3/ActCode | GIS tier | Description: Accuracy determined as per the GIS tier code system.

HHOBS | http://hl7.org/fhir/v3/ActCode | household situation observation | Indicates that the observation is of a person’s living situation in a household including the household composition and circumstances.

ISSUE | http://hl7.org/fhir/v3/ActCode | detected issue | There is a clinical issue for the therapy that makes continuation of the therapy inappropriate. Open Issue: The definition of this code does not correctly represent the concept space of its specializations (children)

_ActAdministrativeDetectedIssueCode | http://hl7.org/fhir/v3/ActCode | ActAdministrativeDetectedIssueCode | Identifies types of detectyed issues for Act class "ALRT" for the administrative and patient administrative acts domains.

_ActAdministrativeAuthorizationDetectedIssueCode | http://hl7.org/fhir/v3/ActCode | ActAdministrativeAuthorizationDetectedIssueCode | ActAdministrativeAuthorizationDetectedIssueCode

NAT | http://hl7.org/fhir/v3/ActCode | Insufficient authorization | The requesting party has insufficient authorization to invoke the interaction.

SUPPRESSED | http://hl7.org/fhir/v3/ActCode | record suppressed | Description: One or more records in the query response have been suppressed due to consent or privacy restrictions.

VALIDAT | http://hl7.org/fhir/v3/ActCode | validation issue | Description:The specified element did not pass business-rule validation.

KEY204 | http://hl7.org/fhir/v3/ActCode | Unknown key identifier | The ID of the patient, order, etc., was not found. Used for transactions other than additions, e.g. transfer of a non-existent patient.

KEY205 | http://hl7.org/fhir/v3/ActCode | Duplicate key identifier | The ID of the patient, order, etc., already exists. Used in response to addition transactions (Admit, New Order, etc.).

COMPLY | http://hl7.org/fhir/v3/ActCode | Compliance Alert | There may be an issue with the patient complying with the intentions of the proposed therapy

DUPTHPY | http://hl7.org/fhir/v3/ActCode | Duplicate Therapy Alert | The proposed therapy appears to duplicate an existing therapy

DUPTHPCLS | http://hl7.org/fhir/v3/ActCode | duplicate therapeutic alass alert | Description:The proposed therapy appears to have the same intended therapeutic benefit as an existing therapy, though the specific mechanisms of action vary.

DUPTHPGEN | http://hl7.org/fhir/v3/ActCode | duplicate generic alert | Description:The proposed therapy appears to have the same intended therapeutic benefit as an existing therapy and uses the same mechanisms of action as the existing therapy.

ABUSE | http://hl7.org/fhir/v3/ActCode | commonly abused/misused alert | Description:The proposed therapy is frequently misused or abused and therefore should be used with caution and/or monitoring.

FRAUD | http://hl7.org/fhir/v3/ActCode | potential fraud | Description:The request is suspected to have a fraudulent basis.

PLYDOC | http://hl7.org/fhir/v3/ActCode | Poly-orderer Alert | A similar or identical therapy was recently ordered by a different practitioner.

PLYPHRM | http://hl7.org/fhir/v3/ActCode | Poly-supplier Alert | This patient was recently supplied a similar or identical therapy from a different pharmacy or supplier.

DOSE | http://hl7.org/fhir/v3/ActCode | Dosage problem | Proposed dosage instructions for therapy differ from standard practice.

DOSECOND | http://hl7.org/fhir/v3/ActCode | dosage-condition alert | Description:Proposed dosage is inappropriate due to patient's medical condition.

DOSEDUR | http://hl7.org/fhir/v3/ActCode | Dose-Duration Alert | Proposed length of therapy differs from standard practice.

DOSEDURH | http://hl7.org/fhir/v3/ActCode | Dose-Duration High Alert | Proposed length of therapy is longer than standard practice

DOSEDURHIND | http://hl7.org/fhir/v3/ActCode | Dose-Duration High for Indication Alert | Proposed length of therapy is longer than standard practice for the identified indication or diagnosis

DOSEDURL | http://hl7.org/fhir/v3/ActCode | Dose-Duration Low Alert | Proposed length of therapy is shorter than that necessary for therapeutic effect

DOSEDURLIND | http://hl7.org/fhir/v3/ActCode | Dose-Duration Low for Indication Alert | Proposed length of therapy is shorter than standard practice for the identified indication or diagnosis

DOSEH | http://hl7.org/fhir/v3/ActCode | High Dose Alert | Proposed dosage exceeds standard practice

DOSEHINDA | http://hl7.org/fhir/v3/ActCode | High Dose for Age Alert | Proposed dosage exceeds standard practice for the patient's age

DOSEHIND | http://hl7.org/fhir/v3/ActCode | High Dose for Indication Alert | High Dose for Indication Alert

DOSEHINDSA | http://hl7.org/fhir/v3/ActCode | High Dose for Height/Surface Area Alert | Proposed dosage exceeds standard practice for the patient's height or body surface area

DOSEHINDW | http://hl7.org/fhir/v3/ActCode | High Dose for Weight Alert | Proposed dosage exceeds standard practice for the patient's weight

DOSEIVL | http://hl7.org/fhir/v3/ActCode | Dose-Interval Alert | Proposed dosage interval/timing differs from standard practice

DOSEIVLIND | http://hl7.org/fhir/v3/ActCode | Dose-Interval for Indication Alert | Proposed dosage interval/timing differs from standard practice for the identified indication or diagnosis

DOSEL | http://hl7.org/fhir/v3/ActCode | Low Dose Alert | Proposed dosage is below suggested therapeutic levels

DOSELINDA | http://hl7.org/fhir/v3/ActCode | Low Dose for Age Alert | Proposed dosage is below suggested therapeutic levels for the patient's age
DOSELIND | http://hl7.org/fhir/v3/ActCode | Low Dose for Indication Alert | Low Dose for Indication Alert
DOSELINDSA | http://hl7.org/fhir/v3/ActCode | Low Dose for Height/Surface Area Alert | Proposed dosage is below suggested therapeutic levels for the patient's height or body surface area
DOSELINDW | http://hl7.org/fhir/v3/ActCode | Low Dose for Weight Alert | Proposed dosage is below suggested therapeutic levels for the patient's weight
MDOSE | http://hl7.org/fhir/v3/ActCode | maximum dosage reached | Description:The maximum quantity of this drug allowed to be administered within a particular time-range (month, year, lifetime) has been reached or exceeded.
OBSA | http://hl7.org/fhir/v3/ActCode | Observation Alert | Proposed therapy may be inappropriate or contraindicated due to conditions or characteristics of the patient
AGE | http://hl7.org/fhir/v3/ActCode | Age Alert | Proposed therapy may be inappropriate or contraindicated due to patient age
ADALRT | http://hl7.org/fhir/v3/ActCode | adult alert | Proposed therapy is outside of the standard practice for an adult patient.
GEALRT | http://hl7.org/fhir/v3/ActCode | geriatric alert | Proposed therapy is outside of standard practice for a geriatric patient.
PEALRT | http://hl7.org/fhir/v3/ActCode | pediatric alert | Proposed therapy is outside of the standard practice for a pediatric patient.
COND | http://hl7.org/fhir/v3/ActCode | Condition Alert | Proposed therapy may be inappropriate or contraindicated due to an existing/recent patient condition or diagnosis
HGHT | http://hl7.org/fhir/v3/ActCode | HGHT
LACT | http://hl7.org/fhir/v3/ActCode | Lactation Alert | Proposed therapy may be inappropriate or contraindicated when breast-feeding
PREG | http://hl7.org/fhir/v3/ActCode | Pregnancy Alert | Proposed therapy may be inappropriate or contraindicated during pregnancy
WGHT | http://hl7.org/fhir/v3/ActCode | WGHT
CREACT | http://hl7.org/fhir/v3/ActCode | common reaction alert | Description:Proposed therapy may be inappropriate or contraindicated because of a common but non-patient specific reaction to the product. Example:There is no record of a specific sensitivity for the patient, but the presence of the sensitivity is common and therefore caution is warranted.
GEN | http://hl7.org/fhir/v3/ActCode | Genetic Alert | Proposed therapy may be inappropriate or contraindicated due to patient genetic indicators.
GEND | http://hl7.org/fhir/v3/ActCode | Gender Alert | Proposed therapy may be inappropriate or contraindicated due to patient gender.
LAB | http://hl7.org/fhir/v3/ActCode | Lab Alert | Proposed therapy may be inappropriate or contraindicated due to recent lab test results
REACT | http://hl7.org/fhir/v3/ActCode | Reaction Alert | Proposed therapy may be inappropriate or contraindicated based on the potential for a patient reaction to the proposed product
ALGY | http://hl7.org/fhir/v3/ActCode | Allergy Alert | Proposed therapy may be inappropriate or contraindicated because of a recorded patient allergy to the proposed product. (Allergies are immune based reactions.)
INT | http://hl7.org/fhir/v3/ActCode | Intolerance Alert | Proposed therapy may be inappropriate or contraindicated because of a recorded patient intolerance to the proposed product. (Intolerances are non-immune based sensitivities.)
RREACT | http://hl7.org/fhir/v3/ActCode | Related Reaction Alert | Proposed therapy may be inappropriate or contraindicated because of a potential patient reaction to a cross-sensitivity related product.
RALG | http://hl7.org/fhir/v3/ActCode | Related Allergy Alert | Proposed therapy may be inappropriate or contraindicated because of a recorded patient allergy to a cross-sensitivity related product. (Allergies are immune based reactions.)
RAR | http://hl7.org/fhir/v3/ActCode | Related Prior Reaction Alert | Proposed therapy may be inappropriate or contraindicated because of a recorded prior adverse reaction to a cross-sensitivity related product.
RINT | http://hl7.org/fhir/v3/ActCode | Related Intolerance Alert | Proposed therapy may be inappropriate or contraindicated because of a recorded patient intolerance to a cross-sensitivity related product. (Intolerances are non-immune based sensitivities.)
BUS | http://hl7.org/fhir/v3/ActCode | business constraint violation | Description:A local business rule relating multiple elements has been violated.
CODE_INVAL | http://hl7.org/fhir/v3/ActCode | code is not valid | Description:The specified code is not valid against the list of codes allowed for the element.
CODE_DEPREC | http://hl7.org/fhir/v3/ActCode | code has been deprecated | Description:The specified code has been deprecated and should no longer be used. Select another code from the code system.
FORMAT | http://hl7.org/fhir/v3/ActCode | invalid format | Description:The element does not follow the formatting or type rules defined for the field.
ILLEGAL | http://hl7.org/fhir/v3/ActCode | illegal | Description:The request is missing elements or contains elements which cause it to not meet the legal standards for actioning.
LEN_RANGE | http://hl7.org/fhir/v3/ActCode | length out of range | Description:The length of the data specified falls out of the range defined for the element.
LEN_LONG | http://hl7.org/fhir/v3/ActCode | length is too long | Description:The length of the data specified is greater than the maximum length defined for the element.
LEN_SHORT | http://hl7.org/fhir/v3/ActCode | length is too short | Description:The length of the data specified is less than the minimum length defined for the element.
MISSCOND | http://hl7.org/fhir/v3/ActCode | conditional element missing | Description:The specified element must be specified with a non-null value under certain conditions. In this case, the conditions are true but the element is still missing or null.
MISSMAND | http://hl7.org/fhir/v3/ActCode | mandatory element missing | Description:The specified element is mandatory and was not included in the instance.
NODUPS | http://hl7.org/fhir/v3/ActCode | duplicate values are not permitted | Description:More than one element with the same value exists in the set. Duplicates not permission in this set in a set.
NOPERSIST | http://hl7.org/fhir/v3/ActCode | element will not be persisted | Description: Element in submitted message will not persist in data storage based on detected issue.
REP_RANGE | http://hl7.org/fhir/v3/ActCode | repetitions out of range | Description:The number of repeating elements falls outside the range of the allowed number of repetitions.
MAXOCCURS | http://hl7.org/fhir/v3/ActCode | repetitions above maximum | Description:The number of repeating elements is above the maximum number of repetitions allowed.
MINOCCURS | http://hl7.org/fhir/v3/ActCode | repetitions below minimum | Description:The number of repeating elements is below the minimum number of repetitions allowed.
_ActAdministrativeRuleDetectedIssueCode | http://hl7.org/fhir/v3/ActCode | ActAdministrativeRuleDetectedIssueCode | ActAdministrativeRuleDetectedIssueCode
KEY206 | http://hl7.org/fhir/v3/ActCode | non-matching identification | Description: Metadata associated with the identification (e.g. name or gender) does not match the identification being verified.
OBSOLETE | http://hl7.org/fhir/v3/ActCode | obsolete record returned | Description: One or more records in the query response have a status of 'obsolete'.

_ActSuppliedItemDetectedIssueCode | http://hl7.org/fhir/v3/ActCode | ActSuppliedItemDetectedIssueCode | Identifies types of detected issues regarding the administration or supply of an item to a patient.
_AdministrationDetectedIssueCode | http://hl7.org/fhir/v3/ActCode | AdministrationDetectedIssueCode | Administration of the proposed therapy may be inappropriate or contraindicated as proposed
_AppropriatenessDetectedIssueCode | http://hl7.org/fhir/v3/ActCode | AppropriatenessDetectedIssueCode | AppropriatenessDetectedIssueCode
_InteractionDetectedIssueCode | http://hl7.org/fhir/v3/ActCode | InteractionDetectedIssueCode | InteractionDetectedIssueCode
FOOD | http://hl7.org/fhir/v3/ActCode | Food Interaction Alert | Proposed therapy may interact with certain foods
TPROD | http://hl7.org/fhir/v3/ActCode | Therapeutic Product Alert | Proposed therapy may interact with an existing or recent therapeutic product
DRG | http://hl7.org/fhir/v3/ActCode | Drug Interaction Alert | Proposed therapy may interact with an existing or recent drug therapy
NHP | http://hl7.org/fhir/v3/ActCode | Natural Health Product Alert | Proposed therapy may interact with existing or recent natural health product therapy
NONRX | http://hl7.org/fhir/v3/ActCode | Non-Prescription Interaction Alert | Proposed therapy may interact with a non-prescription drug (e.g. alcohol, tobacco, Aspirin)
PREVINEF | http://hl7.org/fhir/v3/ActCode | previously ineffective | Definition:The same or similar treatment has previously been attempted with the patient without achieving a positive effect.
DACT | http://hl7.org/fhir/v3/ActCode | drug action detected issue | Description:Proposed therapy may be contraindicated or ineffective based on an existing or recent drug therapy.
TIME | http://hl7.org/fhir/v3/ActCode | timing detected issue | Description:Proposed therapy may be inappropriate or ineffective based on the proposed start or end time.
ALRTENDLATE | http://hl7.org/fhir/v3/ActCode | end too late alert | Definition:Proposed therapy may be inappropriate or ineffective because the end of administration is too close to another planned therapy.
ALRTSTRTLATE | http://hl7.org/fhir/v3/ActCode | start too late alert | Definition:Proposed therapy may be inappropriate or ineffective because the start of administration is too late after the onset of the condition.
_TimingDetectedIssueCode | http://hl7.org/fhir/v3/ActCode | TimingDetectedIssueCode | Proposed therapy may be inappropriate or ineffective based on the proposed start or end time.
ENDLATE | http://hl7.org/fhir/v3/ActCode | End Too Late Alert | Proposed therapy may be inappropriate or ineffective because the end of administration is too close to another planned therapy
STRTLATE | http://hl7.org/fhir/v3/ActCode | Start Too Late Alert | Proposed therapy may be inappropriate or ineffective because the start of administration is too late after the onset of the condition
_SupplyDetectedIssueCode | http://hl7.org/fhir/v3/ActCode | SupplyDetectedIssueCode | Supplying the product at this time may be inappropriate or indicate compliance issues with the associated therapy
ALLDONE | http://hl7.org/fhir/v3/ActCode | already performed | Definition:The requested action has already been performed and so this request has no effect
FULFIL | http://hl7.org/fhir/v3/ActCode | fulfillment alert | Definition:The therapy being performed is in some way out of alignment with the requested therapy.
NOTACTN | http://hl7.org/fhir/v3/ActCode | no longer actionable | Definition:The status of the request being fulfilled has changed such that it is no longer actionable. This may be because the request has expired, has already been completely fulfilled or has been otherwise stopped or disabled. (Not used for 'suspended' orders.)
NOTEQUIV | http://hl7.org/fhir/v3/ActCode | not equivalent alert | Definition:The therapy being performed is not sufficiently equivalent to the therapy which was requested.
NOTEQUIVGEN | http://hl7.org/fhir/v3/ActCode | not generically equivalent alert | Definition:The therapy being performed is not generically equivalent (having the identical biological action) to the therapy which was requested.
NOTEQUIVTHER | http://hl7.org/fhir/v3/ActCode | not therapeutically equivalent alert | Definition:The therapy being performed is not therapeutically equivalent (having the same overall patient effect) to the therapy which was requested.
TIMING | http://hl7.org/fhir/v3/ActCode | event timing incorrect alert | Definition:The therapy is being performed at a time which diverges from the time the therapy was requested
INTERVAL | http://hl7.org/fhir/v3/ActCode | outside requested time | Definition:The therapy action is being performed outside the bounds of the time period requested
MINFREQ | http://hl7.org/fhir/v3/ActCode | too soon within frequency based on the usage | Definition:The therapy action is being performed too soon after the previous occurrence based on the requested frequency
HELD | http://hl7.org/fhir/v3/ActCode | held/suspended alert | Definition:There should be no actions taken in fulfillment of a request that has been held or suspended.
TOOLATE | http://hl7.org/fhir/v3/ActCode | Refill Too Late Alert | The patient is receiving a subsequent fill significantly later than would be expected based on the amount previously supplied and the therapy dosage instructions
TOOSOON | http://hl7.org/fhir/v3/ActCode | Refill Too Soon Alert | The patient is receiving a subsequent fill significantly earlier than would be expected based on the amount previously supplied and the therapy dosage instructions
HISTORIC | http://hl7.org/fhir/v3/ActCode | record recorded as historical | Description: While the record was accepted in the repository, there is a more recent version of a record of this type.
PATPREF | http://hl7.org/fhir/v3/ActCode | violates stated preferences | Definition:The proposed therapy goes against preferences or consent constraints recorded in the patient's record.
PATPREFALT | http://hl7.org/fhir/v3/ActCode | violates stated preferences, alternate available | Definition:The proposed therapy goes against preferences or consent constraints recorded in the patient's record. An alternate therapy meeting those constraints is available.
KSUBJ | http://hl7.org/fhir/v3/ActCode | knowledge subject | Categorization of types of observation that capture the main clinical knowledge subject which may be a medication, a laboratory test, a disease.
KSUBT | http://hl7.org/fhir/v3/ActCode | knowledge subtopic | Categorization of types of observation that capture a knowledge subtopic which might be treatment, etiology, or prognosis.
OINT | http://hl7.org/fhir/v3/ActCode | intolerance | Hypersensitivity resulting in an adverse reaction upon exposure to an agent.
ALG | http://hl7.org/fhir/v3/ActCode | Allergy | Hypersensitivity to an agent caused by an immunologic response to an initial exposure
DALG | http://hl7.org/fhir/v3/ActCode | Drug Allergy | An allergy to a pharmaceutical product.
EALG | http://hl7.org/fhir/v3/ActCode | Environmental Allergy | An allergy to a substance other than a drug or a food. E.g. Latex, pollen, etc.
FALG | http://hl7.org/fhir/v3/ActCode | Food Allergy | An allergy to a substance generally consumed for nutritional purposes.
DINT | http://hl7.org/fhir/v3/ActCode | Drug Intolerance | Hypersensitivity resulting in an adverse reaction upon exposure to a drug.
DNAINT | http://hl7.org/fhir/v3/ActCode | Drug Non-Allergy Intolerance | Hypersensitivity to an agent caused by a mechanism other than an immunologic response to an initial exposure

EINT | http://hl7.org/fhir/v3/ActCode | Environmental Intolerance | Hypersensitivity resulting in an adverse reaction upon exposure to environmental conditions.
ENAINT | http://hl7.org/fhir/v3/ActCode | Environmental Non-Allergy Intolerance | Hypersensitivity to an agent caused by a mechanism other than an immunologic response to an initial exposure
FINT | http://hl7.org/fhir/v3/ActCode | Food Intolerance | Hypersensitivity resulting in an adverse reaction upon exposure to food.
FNAINT | http://hl7.org/fhir/v3/ActCode | Food Non-Allergy Intolerance | Hypersensitivity to an agent caused by a mechanism other than an immunologic response to an initial exposure
NAINT | http://hl7.org/fhir/v3/ActCode | Non-Allergy Intolerance | Hypersensitivity to an agent caused by a mechanism other than an immunologic response to an initial exposure
SEV | http://hl7.org/fhir/v3/ActCode | Severity Observation | A subjective evaluation of the seriousness or intensity associated with another observation.
_FDALabelData | http://hl7.org/fhir/v3/ActCode | FDALabelData | FDA label data
FDACOATING | http://hl7.org/fhir/v3/ActCode | coating | FDA label coating
FDACOLOR | http://hl7.org/fhir/v3/ActCode | color | FDA label color
FDAIMPRINTCD | http://hl7.org/fhir/v3/ActCode | imprint code | FDA label imprint code
FDALOGO | http://hl7.org/fhir/v3/ActCode | logo | FDA label logo
FDASCORING | http://hl7.org/fhir/v3/ActCode | scoring | FDA label scoring
FDASHAPE | http://hl7.org/fhir/v3/ActCode | shape | FDA label shape
FDASIZE | http://hl7.org/fhir/v3/ActCode | size | FDA label size
1-8 | http://loinc.org | Acyclovir [Susceptibility]
10-9 | http://loinc.org | Amdinocillin [Susceptibility] by Serum bactericidal titer
100-8 | http://loinc.org | Cefoperazone [Susceptibility] by Minimum inhibitory concentration (MIC)
1000-9 | http://loinc.org | DBG Ab [Presence] in Serum or Plasma from Blood product unit
10000-8 | http://loinc.org | R wave duration in lead AVR
10001-6 | http://loinc.org | R wave duration in lead I
10002-4 | http://loinc.org | R wave duration in lead II
10003-2 | http://loinc.org | R wave duration in lead III
10004-0 | http://loinc.org | R wave duration in lead V1
10005-7 | http://loinc.org | R wave duration in lead V2
10006-5 | http://loinc.org | R wave duration in lead V3
10007-3 | http://loinc.org | R wave duration in lead V4
10008-1 | http://loinc.org | R wave duration in lead V5
10009-9 | http://loinc.org | R wave duration in lead V6
1001-7 | http://loinc.org | DBG Ab [Presence] in Serum or Plasma from donor
10010-7 | http://loinc.org | R' wave amplitude in lead AVF
10011-5 | http://loinc.org | R' wave amplitude in lead AVL
10012-3 | http://loinc.org | R' wave amplitude in lead AVR
10013-1 | http://loinc.org | R' wave amplitude in lead I
10014-9 | http://loinc.org | R' wave amplitude in lead II
10015-6 | http://loinc.org | R' wave amplitude in lead III
10016-4 | http://loinc.org | R' wave amplitude in lead V1
10017-2 | http://loinc.org | R' wave amplitude in lead V2
10018-0 | http://loinc.org | R' wave amplitude in lead V3
10019-8 | http://loinc.org | R' wave amplitude in lead V4
1002-5 | http://loinc.org | DBG Ab [Presence] in Serum or Plasma
10020-6 | http://loinc.org | R' wave amplitude in lead V5
10021-4 | http://loinc.org | R' wave amplitude in lead V6
10022-2 | http://loinc.org | R' wave duration in lead AVF
10023-0 | http://loinc.org | R' wave duration in lead AVL
10024-8 | http://loinc.org | R' wave duration in lead AVR
10025-5 | http://loinc.org | R' wave duration in lead I
10026-3 | http://loinc.org | R' wave duration in lead II
10027-1 | http://loinc.org | R' wave duration in lead III
10028-9 | http://loinc.org | R' wave duration in lead V1
10029-7 | http://loinc.org | R' wave duration in lead V2
1003-3 | http://loinc.org | Indirect antiglobulin test.complement specific reagent [Presence] in Serum or Plasma
10030-5 | http://loinc.org | R' wave duration in lead V3
10031-3 | http://loinc.org | R' wave duration in lead V4
10032-1 | http://loinc.org | R' wave duration in lead V5
10033-9 | http://loinc.org | R' wave duration in lead V6
10034-7 | http://loinc.org | S wave amplitude in lead AVF
10035-4 | http://loinc.org | S wave amplitude in lead AVL
10036-2 | http://loinc.org | S wave amplitude in lead AVR
10037-0 | http://loinc.org | S wave amplitude in lead I
10038-8 | http://loinc.org | S wave amplitude in lead II
10039-6 | http://loinc.org | S wave amplitude in lead III
1004-1 | http://loinc.org | Direct antiglobulin test.complement specific reagent [Presence] on Red Blood Cells
10040-4 | http://loinc.org | S wave amplitude in lead V1
10041-2 | http://loinc.org | S wave amplitude in lead V2
10042-0 | http://loinc.org | S wave amplitude in lead V3
10043-8 | http://loinc.org | S wave amplitude in lead V4
10044-6 | http://loinc.org | S wave amplitude in lead V5
10045-3 | http://loinc.org | S wave amplitude in lead V6

10046-1 | http://loinc.org | S wave duration in lead AVF
10047-9 | http://loinc.org | S wave duration in lead AVL
10048-7 | http://loinc.org | S wave duration in lead AVR
10049-5 | http://loinc.org | S wave duration in lead I
1005-8 | http://loinc.org | Indirect antiglobulin test.IgG specific reagent [Presence] in Serum or Plasma
10050-3 | http://loinc.org | S wave duration in lead II
10051-1 | http://loinc.org | S wave duration in lead III
10052-9 | http://loinc.org | S wave duration in lead V1
10053-7 | http://loinc.org | S wave duration in lead V2
10054-5 | http://loinc.org | S wave duration in lead V3
10055-2 | http://loinc.org | S wave duration in lead V4
10056-0 | http://loinc.org | S wave duration in lead V5
10057-8 | http://loinc.org | S wave duration in lead V6
10058-6 | http://loinc.org | S' wave amplitude in lead AVF
10059-4 | http://loinc.org | S' wave amplitude in lead AVL
1006-6 | http://loinc.org | Direct antiglobulin test.IgG specific reagent [Interpretation] on Red Blood Cells
10060-2 | http://loinc.org | S' wave amplitude in lead AVR
10061-0 | http://loinc.org | S' wave amplitude in lead I
10062-8 | http://loinc.org | S' wave amplitude in lead II
10063-6 | http://loinc.org | S' wave amplitude in lead III
10064-4 | http://loinc.org | S' wave amplitude in lead V1
10065-1 | http://loinc.org | S' wave amplitude in lead V2
10066-9 | http://loinc.org | S' wave amplitude in lead V3
10067-7 | http://loinc.org | S' wave amplitude in lead V4
10068-5 | http://loinc.org | S' wave amplitude in lead V5
10069-3 | http://loinc.org | S' wave amplitude in lead V6
1007-4 | http://loinc.org | Direct antiglobulin test.poly specific reagent [Presence] on Red Blood Cells
10070-1 | http://loinc.org | S' wave duration in lead AVF
10071-9 | http://loinc.org | S' wave duration in lead AVL
10072-7 | http://loinc.org | S' wave duration in lead AVR
10073-5 | http://loinc.org | S' wave duration in lead I
10074-3 | http://loinc.org | S' wave duration in lead II
10075-0 | http://loinc.org | S' wave duration in lead III
10076-8 | http://loinc.org | S' wave duration in lead V1
10077-6 | http://loinc.org | S' wave duration in lead V2
10078-4 | http://loinc.org | S' wave duration in lead V3
10079-2 | http://loinc.org | S' wave duration in lead V4
1008-2 | http://loinc.org | Indirect antiglobulin test.poly specific reagent [Presence] in Serum or Plasma
10080-0 | http://loinc.org | S' wave duration in lead V5
10081-8 | http://loinc.org | S' wave duration in lead V6
10082-6 | http://loinc.org | ST initial amplitude 6 ms in lead AVF
10083-4 | http://loinc.org | ST initial amplitude 6 ms in lead AVL
10084-2 | http://loinc.org | ST initial amplitude 6 ms in lead AVR
10085-9 | http://loinc.org | ST initial amplitude 6 ms in lead I
10086-7 | http://loinc.org | ST initial amplitude 6 ms in lead II
10087-5 | http://loinc.org | ST initial amplitude 6 ms in lead III
10088-3 | http://loinc.org | ST initial amplitude 6 ms in lead V1
10089-1 | http://loinc.org | ST initial amplitude 6 ms in lead V2
1009-0 | http://loinc.org | Deprecated Direct antiglobulin test.poly specific reagent [Presence] on Red Blood Cells
10090-9 | http://loinc.org | ST initial amplitude 6 ms in lead V3
10091-7 | http://loinc.org | ST initial amplitude 6 ms in lead V4
10092-5 | http://loinc.org | ST initial amplitude 6 ms in lead V5
10093-3 | http://loinc.org | ST initial amplitude 6 ms in lead V6
10094-1 | http://loinc.org | ST slope in lead AVF
10095-8 | http://loinc.org | ST slope in lead AVL
10096-6 | http://loinc.org | ST slope in lead AVR
10097-4 | http://loinc.org | ST slope in lead I
10098-2 | http://loinc.org | ST slope in lead II
10099-0 | http://loinc.org | ST slope in lead III
101-6 | http://loinc.org | Cefoperazone [Susceptibility] by Disk diffusion (KB)
1010-8 | http://loinc.org | Ew Ab [Presence] in Serum or Plasma from Blood product unit
10100-6 | http://loinc.org | ST slope in lead V1
10101-4 | http://loinc.org | ST slope in lead V2
10102-2 | http://loinc.org | ST slope in lead V3
10103-0 | http://loinc.org | ST slope in lead V4
10104-8 | http://loinc.org | ST slope in lead V5
10105-5 | http://loinc.org | ST slope in lead V6
10106-3 | http://loinc.org | ST wave end displacement in lead AVF
10107-1 | http://loinc.org | ST wave end displacement in lead AVL
10108-9 | http://loinc.org | ST wave end displacement in lead AVR
10109-7 | http://loinc.org | ST wave end displacement in lead I
1011-6 | http://loinc.org | Ew Ab [Presence] in Serum or Plasma from donor

10110-5 | http://loinc.org | ST wave end displacement in lead II
10111-3 | http://loinc.org | ST wave end displacement in lead III
10112-1 | http://loinc.org | ST wave end displacement in lead V1
10113-9 | http://loinc.org | ST wave end displacement in lead V2
10114-7 | http://loinc.org | ST wave end displacement in lead V3
10115-4 | http://loinc.org | ST wave end displacement in lead V4
10116-2 | http://loinc.org | ST wave end displacement in lead V5
10117-0 | http://loinc.org | ST wave end displacement in lead V6
10118-8 | http://loinc.org | ST wave mid displacement in lead AVF
10119-6 | http://loinc.org | ST wave mid displacement in lead AVL
1012-4 | http://loinc.org | Ew Ab [Presence] in Serum or Plasma
10120-4 | http://loinc.org | ST wave mid displacement in lead AVR
10121-2 | http://loinc.org | ST wave mid displacement in lead I
10122-0 | http://loinc.org | ST wave mid displacement in lead II
10123-8 | http://loinc.org | ST wave mid displacement in lead III
10124-6 | http://loinc.org | ST wave mid displacement in lead V1
10125-3 | http://loinc.org | ST wave mid displacement in lead V2
10126-1 | http://loinc.org | ST wave mid displacement in lead V3
10127-9 | http://loinc.org | ST wave mid displacement in lead V4
10128-7 | http://loinc.org | ST wave mid displacement in lead V5
10129-5 | http://loinc.org | ST wave mid displacement in lead V6
1013-2 | http://loinc.org | Ew Ag [Presence] on Red Blood Cells from Blood product unit
10130-3 | http://loinc.org | T' wave amplitude in lead AVF
10131-1 | http://loinc.org | T' wave amplitude in lead AVL
10132-9 | http://loinc.org | T' wave amplitude in lead AVR
10133-7 | http://loinc.org | T' wave amplitude in lead I
10134-5 | http://loinc.org | T' wave amplitude in lead II
10135-2 | http://loinc.org | T' wave amplitude in lead III
10136-0 | http://loinc.org | T' wave amplitude in lead V1
10137-8 | http://loinc.org | T' wave amplitude in lead V2
10138-6 | http://loinc.org | T' wave amplitude in lead V3
10139-4 | http://loinc.org | T' wave amplitude in lead V4
1014-0 | http://loinc.org | Ew Ag [Presence] on Red Blood Cells from donor
10140-2 | http://loinc.org | T' wave amplitude in lead V5
10141-0 | http://loinc.org | T' wave amplitude in lead V6
10142-8 | http://loinc.org | T wave amplitude in lead AVF
10143-6 | http://loinc.org | T wave amplitude in lead AVL
10144-4 | http://loinc.org | T wave amplitude in lead AVR
10145-1 | http://loinc.org | T wave amplitude in lead I
10146-9 | http://loinc.org | T wave amplitude in lead II
10147-7 | http://loinc.org | T wave amplitude in lead III
10148-5 | http://loinc.org | T wave amplitude in lead V1
10149-3 | http://loinc.org | T wave amplitude in lead V2
1015-7 | http://loinc.org | Ew Ag [Presence] on Red Blood Cells
10150-1 | http://loinc.org | T wave amplitude in lead V3
10151-9 | http://loinc.org | T wave amplitude in lead V4
10152-7 | http://loinc.org | T wave amplitude in lead V5
10153-5 | http://loinc.org | T wave amplitude in lead V6
10154-3 | http://loinc.org | Chief complaint Narrative - Reported
10155-0 | http://loinc.org | History of allergies, reported
10156-8 | http://loinc.org | History of Childhood diseases Narrative
10157-6 | http://loinc.org | History of family member diseases Narrative
10158-4 | http://loinc.org | History of Functional status Narrative
10159-2 | http://loinc.org | History of Industrial exposure Narrative
1016-5 | http://loinc.org | E Ab [Presence] in Serum or Plasma from Blood product unit
10160-0 | http://loinc.org | History of Medication use Narrative
10161-8 | http://loinc.org | History of Occupational exposure Narrative
10162-6 | http://loinc.org | History of pregnancies Narrative
10163-4 | http://loinc.org | History of pregnancies
10164-2 | http://loinc.org | History of Present illness Narrative
10165-9 | http://loinc.org | Deprecated History of psychiatric symptoms and diseases Narrative
10166-7 | http://loinc.org | History of Social function Narrative
10167-5 | http://loinc.org | History of Surgical procedures Narrative
10168-3 | http://loinc.org | History of Cardiovascular system disorders Narrative
10169-1 | http://loinc.org | History of Ear disorders Narrative
1017-3 | http://loinc.org | E Ab [Presence] in Serum or Plasma from donor
10170-9 | http://loinc.org | History of Endocrine system disorders Narrative
10171-7 | http://loinc.org | History of Eyes disorders Narrative
10172-5 | http://loinc.org | History of Hematologic system disorders Narrative
10173-3 | http://loinc.org | History of Musculoskeletal system disorders Narrative
10174-1 | http://loinc.org | History of Nose disorders Narrative
10175-8 | http://loinc.org | History of Oral cavity disorders Narrative

10176-6 | http://loinc.org | History of Reproductive system disorders Narrative
10177-4 | http://loinc.org | History of Respiratory system disorders Narrative
10178-2 | http://loinc.org | History of Skin disorders Narrative
10179-0 | http://loinc.org | History of Throat and Neck disorders Narrative
1018-1 | http://loinc.org | E Ab [Presence] in Serum or Plasma
10180-8 | http://loinc.org | History of Throat and Neck disorders
10181-6 | http://loinc.org | History of Urinary tract disorders Narrative
10182-4 | http://loinc.org | History of Travel Narrative
10183-2 | http://loinc.org | Hospital discharge medications Narrative
10184-0 | http://loinc.org | Hospital discharge physical findings Narrative
10185-7 | http://loinc.org | Hospital discharge procedures Narrative
10186-5 | http://loinc.org | Identifying information Narrative Observed
10187-3 | http://loinc.org | Review of systems Narrative - Reported
10188-1 | http://loinc.org | Review of systems overview Narrative - Reported
10189-9 | http://loinc.org | Review of systems overview - Reported
1019-9 | http://loinc.org | E Ag [Presence] on Red Blood Cells from Blood product unit
10190-7 | http://loinc.org | Mental status Narrative
10191-5 | http://loinc.org | Physical findings of Abdomen Narrative
10192-3 | http://loinc.org | Physical findings of Back Narrative
10193-1 | http://loinc.org | Physical findings of Breasts Narrative
10194-9 | http://loinc.org | Physical findings of Neurologic deep tendon reflexes Narrative
10195-6 | http://loinc.org | Physical findings of Ear Narrative
10196-4 | http://loinc.org | Physical findings of Extremities Narrative
10197-2 | http://loinc.org | Physical findings of Eye Narrative
10198-0 | http://loinc.org | Physical findings of Genitourinary tract Narrative
10199-8 | http://loinc.org | Physical findings of Head Narrative
102-4 | http://loinc.org | Cefoperazone [Susceptibility] by Serum bactericidal titer
1020-7 | http://loinc.org | E Ag [Presence] on Red Blood Cells from donor
10200-4 | http://loinc.org | Physical findings of Heart Narrative
10201-2 | http://loinc.org | Physical findings of Mouth and Throat and Teeth Narrative
10202-0 | http://loinc.org | Physical findings of Nervous system Narrative
10203-8 | http://loinc.org | Physical findings of Nose Narrative
10204-6 | http://loinc.org | Physical findings of Pelvis Narrative
10205-3 | http://loinc.org | Physical findings of Rectum Narrative
10206-1 | http://loinc.org | Physical findings of Skin Narrative
10207-9 | http://loinc.org | Physical findings of Thorax and Lungs Narrative
10208-7 | http://loinc.org | Physical findings of Vessels Narrative
10209-5 | http://loinc.org | Physical findings of Neurologic balance and Coordination Narrative
1021-5 | http://loinc.org | E Ag [Presence] on Red Blood Cells
10210-3 | http://loinc.org | Physical findings of General status Narrative
10211-1 | http://loinc.org | Physical findings of Sense of touch Narrative
10212-9 | http://loinc.org | Physical findings of Strength Narrative
10213-7 | http://loinc.org | Surgical operation note anesthesia Narrative
10214-5 | http://loinc.org | Surgical operation note anesthesia duration
10215-2 | http://loinc.org | Surgical operation note findings Narrative
10216-0 | http://loinc.org | Surgical operation note fluids Narrative
10217-8 | http://loinc.org | Surgical operation note indications [Interpretation] Narrative
10218-6 | http://loinc.org | Surgical operation note postoperative diagnosis Narrative
10219-4 | http://loinc.org | Surgical operation note preoperative diagnosis Narrative
1022-3 | http://loinc.org | Fy sup(a) Ab [Presence] in Serum or Plasma from Blood product unit
10220-2 | http://loinc.org | Surgical operation note prep time duration
10221-0 | http://loinc.org | Surgical operation note specimens taken Narrative
10222-8 | http://loinc.org | Surgical operation note surgical complications [Interpretation] Narrative
10223-6 | http://loinc.org | Surgical operation note surgical procedure Narrative
10224-4 | http://loinc.org | Hemodynamic method special circumstances
10225-1 | http://loinc.org | Cardiac measurement device Institution inventory number
10226-9 | http://loinc.org | Oxygen content in Intravascular space
10227-7 | http://loinc.org | Cardiac measurement device Vendor model number
10228-5 | http://loinc.org | Cardiac measurement device Vendor serial number
10229-3 | http://loinc.org | Hemodynamic method Type of
1023-1 | http://loinc.org | Fy sup(a) Ab [Presence] in Serum or Plasma from donor
10230-1 | http://loinc.org | Left ventricular Ejection fraction
10231-9 | http://loinc.org | Right ventricular Ejection fraction
10232-7 | http://loinc.org | Oxygen content in Aorta root
10233-5 | http://loinc.org | Oxygen content in Left atrium
10234-3 | http://loinc.org | Oxygen content in Right atrium
10235-0 | http://loinc.org | Oxygen content in High right atrium
10236-8 | http://loinc.org | Oxygen content in Low right atrium
10237-6 | http://loinc.org | Oxygen content in Mid right atrium
10238-4 | http://loinc.org | Oxygen content in Left ventricle
10239-2 | http://loinc.org | Oxygen content in Right ventricular outflow tract
1024-9 | http://loinc.org | Fy sup(a) Ab [Presence] in Serum or Plasma

10240-0 | http://loinc.org | Oxygen content in Right ventricle
10241-8 | http://loinc.org | Oxygen content in Coronary sinus
10242-6 | http://loinc.org | Oxygen content in Ductus arteriosus
10243-4 | http://loinc.org | Oxygen content in Inferior vena cava
10244-2 | http://loinc.org | Oxygen content in Left pulmonary artery
10245-9 | http://loinc.org | Oxygen content in Main pulmonary artery
10246-7 | http://loinc.org | Oxygen content in Right pulmonary artery
10247-5 | http://loinc.org | Oxygen content in Pulmonary wedge
10248-3 | http://loinc.org | Oxygen content in Superior vena cava
10249-1 | http://loinc.org | Heart rate device Institution inventory number
1025-6 | http://loinc.org | Fy sup(a) Ag [Presence] on Red Blood Cells from Blood product unit
10250-9 | http://loinc.org | Heart rate device Vendor model number
10251-7 | http://loinc.org | Heart rate device Vendor serial number
10252-5 | http://loinc.org | Biliary drain site
10253-3 | http://loinc.org | Type of Biliary drain
10254-1 | http://loinc.org | Type of Peritoneal drain
10255-8 | http://loinc.org | Type of Subarachnoid drain
10256-6 | http://loinc.org | Biliary drain Institution inventory number
10257-4 | http://loinc.org | Chest tube Institution inventory number
10258-2 | http://loinc.org | Enteral tube Institution inventory number
10259-0 | http://loinc.org | Gastrostomy tube Institution inventory number
1026-4 | http://loinc.org | Fy sup(a) Ag [Presence] on Red Blood Cells from donor
10260-8 | http://loinc.org | GI tube Institution inventory number
10261-6 | http://loinc.org | Intravascular tube Institution inventory number
10262-4 | http://loinc.org | IO tube Institution inventory number
10263-2 | http://loinc.org | Nasogastric tube Institution inventory number
10264-0 | http://loinc.org | Oral tube Institution inventory number
10265-7 | http://loinc.org | Peritoneal drain Institution inventory number
10266-5 | http://loinc.org | Peritoneal tube Institution inventory number
10267-3 | http://loinc.org | Rate control device Institution inventory number
10268-1 | http://loinc.org | Stool collection device Institution inventory number
10269-9 | http://loinc.org | Subarachnoid drain Institution inventory number
1027-2 | http://loinc.org | Fy sup(a) Ag [Presence] on Red Blood Cells
10270-7 | http://loinc.org | Synovial drain Institution inventory number
10271-5 | http://loinc.org | Tube or drain Institution inventory number
10272-3 | http://loinc.org | Upper GI tube Institution inventory number
10273-1 | http://loinc.org | Bladder irrigation tube Institution inventory number
10274-9 | http://loinc.org | Urine tube Institution inventory number
10275-6 | http://loinc.org | Wound drain device Institution inventory number
10276-4 | http://loinc.org | Peritoneal drain site
10277-2 | http://loinc.org | Stool collection site
10278-0 | http://loinc.org | Subarachnoid drain site
10279-8 | http://loinc.org | Biliary drain Vendor model number
1028-0 | http://loinc.org | Fy sup(b) Ab [Presence] in Serum or Plasma from Blood product unit
10280-6 | http://loinc.org | Chest tube Vendor model number
10281-4 | http://loinc.org | Enteral tube Vendor model number
10282-2 | http://loinc.org | Gastrostomy tube Vendor model number
10283-0 | http://loinc.org | GI tube Vendor model number
10284-8 | http://loinc.org | Intravascular tube Vendor model number
10285-5 | http://loinc.org | IO tube Vendor model number
10286-3 | http://loinc.org | Nasogastric tube Vendor model number
10287-1 | http://loinc.org | Oral tube Vendor model number
10288-9 | http://loinc.org | Peritoneal drain Vendor model number
10289-7 | http://loinc.org | Peritoneal tube Vendor model number
1029-8 | http://loinc.org | Fy sup(b) Ab [Presence] in Serum or Plasma from donor
10290-5 | http://loinc.org | Rate control device Vendor model number
10291-3 | http://loinc.org | Stool collection device Vendor model number
10292-1 | http://loinc.org | Subarachnoid drain Vendor model number
10293-9 | http://loinc.org | Synovial drain Vendor model number
10294-7 | http://loinc.org | Tube or drain Vendor model number
10295-4 | http://loinc.org | Upper GI tube Vendor model number
10296-2 | http://loinc.org | Bladder irrigation tube Vendor model number
10297-0 | http://loinc.org | Urine tube Vendor model number
10298-8 | http://loinc.org | Wound drain device Vendor model number
10299-6 | http://loinc.org | Biliary drain Vendor serial number
103-2 | http://loinc.org | Ceforanide [Susceptibility] by Minimum lethal concentration (MLC)
1030-6 | http://loinc.org | Fy sup(b) Ab [Presence] in Serum or Plasma
10300-2 | http://loinc.org | Chest tube Vendor serial number
10301-0 | http://loinc.org | Enteral tube Vendor serial number
10302-8 | http://loinc.org | Gastrostomy tube Vendor serial number
10303-6 | http://loinc.org | GI tube Vendor serial number
10304-4 | http://loinc.org | Intravascular tube Vendor serial number

10305-1 | http://loinc.org | IO tube Vendor serial number
10306-9 | http://loinc.org | Nasogastric tube Vendor serial number
10307-7 | http://loinc.org | Oral tube Vendor serial number
10308-5 | http://loinc.org | Peritoneal drain Vendor serial number
10309-3 | http://loinc.org | Peritoneal tube Vendor serial number
1031-4 | http://loinc.org | Fy sup(b) Ag [Presence] on Red Blood Cells from Blood product unit
10310-1 | http://loinc.org | Rate control device Vendor serial number
10311-9 | http://loinc.org | Stool collection device Vendor serial number
10312-7 | http://loinc.org | Subarachnoid drain Vendor serial number
10313-5 | http://loinc.org | Synovial drain Vendor serial number
10314-3 | http://loinc.org | Tube or drain Vendor serial number
10315-0 | http://loinc.org | Upper GI tube Vendor serial number
10316-8 | http://loinc.org | Bladder irrigation tube Vendor serial number
10317-6 | http://loinc.org | Urine tube Vendor serial number
10318-4 | http://loinc.org | Wound drain device Vendor serial number
10319-2 | http://loinc.org | Enema device Institution inventory number
1032-2 | http://loinc.org | Fy sup(b) Ag [Presence] on Red Blood Cells from donor
10320-0 | http://loinc.org | Enema device Vendor model number
10321-8 | http://loinc.org | Enema device Vendor serial number
10322-6 | http://loinc.org | Potassium intake 24 hour
10323-4 | http://loinc.org | Wound drain fluid [Appearance] Lower GI tract
10324-2 | http://loinc.org | Breath rate device Institution inventory number
10325-9 | http://loinc.org | Breath rate device Vendor model number
10326-7 | http://loinc.org | Breath rate device Vendor serial number
10327-5 | http://loinc.org | Eosinophils/100 leukocytes in Sputum by Manual count
10328-3 | http://loinc.org | Lymphocytes/100 leukocytes in Cerebral spinal fluid by Manual count
10329-1 | http://loinc.org | Monocytes/100 leukocytes in Cerebral spinal fluid by Manual count
1033-0 | http://loinc.org | Fy sup(b) Ag [Presence] on Red Blood Cells
10330-9 | http://loinc.org | Monocytes/100 leukocytes in Body fluid by Manual count
10331-7 | http://loinc.org | Rh [Type] in Blood
10332-5 | http://loinc.org | Cortisol [Mass/volume] in Serum or Plasma --pre 250 ug corticotropin IM
10333-3 | http://loinc.org | Appearance of Cerebral spinal fluid
10334-1 | http://loinc.org | Cancer Ag 125 [Units/volume] in Serum or Plasma
10335-8 | http://loinc.org | Color of Cerebral spinal fluid
10336-6 | http://loinc.org | Gonadotropin peptide [Mass/volume] in Urine
10337-4 | http://loinc.org | Procollagen type I [Mass/volume] in Serum
10338-2 | http://loinc.org | Barbiturates [Mass/volume] in Serum or Plasma
10339-0 | http://loinc.org | Fluoxetine+Norfluoxetine [Mass/volume] in Serum or Plasma
1034-8 | http://loinc.org | Fetal cell screen [Interpretation] in Blood
10340-8 | http://loinc.org | Molindone [Mass/volume] in Serum or Plasma
10341-6 | http://loinc.org | Norpropoxyphene [Mass/volume] in Serum or Plasma
10342-4 | http://loinc.org | Sulfamethoxazole [Mass/volume] in Serum or Plasma
10343-2 | http://loinc.org | Temazepam [Mass/volume] in Serum or Plasma
10344-0 | http://loinc.org | Tranylcypromine [Mass/volume] in Serum or Plasma
10345-7 | http://loinc.org | Trihexyphenidyl [Mass/volume] in Urine
10346-5 | http://loinc.org | Hemoglobin A [Units/volume] in Blood by Electrophoresis
10347-3 | http://loinc.org | Babesia microti identified in Blood by Light microscopy
10348-1 | http://loinc.org | Bordetella parapertussis Ab [Presence] in Serum
10349-9 | http://loinc.org | Brucella sp Ab [Units/volume] in Serum
1035-5 | http://loinc.org | Fresh frozen plasma given [Volume]
10350-7 | http://loinc.org | Herpes simplex virus IgM Ab [Titer] in Serum by Immunoassay
10351-5 | http://loinc.org | HIV 1 RNA [Units/volume] (viral load) in Serum or Plasma by Probe with amplification
10352-3 | http://loinc.org | Bacteria identified in Genital specimen by Aerobe culture
10353-1 | http://loinc.org | Bacteria identified in Nose by Aerobe culture
10354-9 | http://loinc.org | Bacteria identified in Urethra by Culture
10355-6 | http://loinc.org | Microscopic observation [Identifier] in Bone marrow by Wright Giemsa stain
10356-4 | http://loinc.org | Deprecated Microscopic observation [Identifier] in Stool by Trichrome stain
10357-2 | http://loinc.org | Microscopic observation [Identifier] in Wound by Gram stain
10358-0 | http://loinc.org | Teichoate Ab [Titer] in Serum by Immune diffusion (ID)
10359-8 | http://loinc.org | Asialoganglioside GM1 IgM Ab [Titer] in Serum
1036-3 | http://loinc.org | G Ab [Presence] in Serum or Plasma from Blood product unit
10360-6 | http://loinc.org | DNA single strand IgG Ab [Units/volume] in Serum
10361-4 | http://loinc.org | DNA single strand IgM Ab [Units/volume] in Serum
10362-2 | http://loinc.org | Endomysium IgA Ab [Presence] in Serum
10363-0 | http://loinc.org | Barbiturates [Presence] in Unspecified specimen
10364-8 | http://loinc.org | Cotinine [Mass/mass] in Hair
10365-5 | http://loinc.org | Cotinine [Mass/volume] in Serum or Plasma
10366-3 | http://loinc.org | Cotinine [Mass/volume] in Urine
10367-1 | http://loinc.org | Ethanol [Mass/volume] in Gastric fluid
10368-9 | http://loinc.org | Lead [Mass/volume] in Capillary blood
10369-7 | http://loinc.org | Opiates [Mass/mass] in Hair
1037-1 | http://loinc.org | G Ab [Presence] in Serum or Plasma from donor

10370-5 | http://loinc.org | Phencyclidine [Mass/mass] in Hair
10371-3 | http://loinc.org | Bite cells [Presence] in Blood by Light microscopy
10372-1 | http://loinc.org | Blister cells [Presence] in Blood by Light microscopy
10373-9 | http://loinc.org | Fragments [Presence] in Blood by Light microscopy
10374-7 | http://loinc.org | Helmet cells [Presence] in Blood by Light microscopy
10375-4 | http://loinc.org | Irregularly contracted cells [Presence] in Blood by Light microscopy
10376-2 | http://loinc.org | Oval macrocytes [Presence] in Blood by Light microscopy
10377-0 | http://loinc.org | Pencil cells [Presence] in Blood by Light microscopy
10378-8 | http://loinc.org | Polychromasia [Presence] in Blood by Light microscopy
10379-6 | http://loinc.org | Erythrocytes.dual population [Presence] in Blood by Light microscopy
1038-9 | http://loinc.org | G Ab [Presence] in Serum or Plasma
10380-4 | http://loinc.org | Stomatocytes [Presence] in Blood by Light microscopy
10381-2 | http://loinc.org | Target cells [Presence] in Blood by Light microscopy
10382-0 | http://loinc.org | A,B variant NOS Ag [Presence] on Red Blood Cells from Blood product unit
10383-8 | http://loinc.org | A,B variant NOS Ag [Presence] on Red Blood Cells from donor
10384-6 | http://loinc.org | A,B variant NOS Ag [Presence] on Red Blood Cells
10385-3 | http://loinc.org | Albumin concentration given
10386-1 | http://loinc.org | Albumin given [Volume]
10387-9 | http://loinc.org | Autologous erythrocytes given [Volume]
10388-7 | http://loinc.org | Autologous whole blood given [Volume]
10389-5 | http://loinc.org | Blood product.other [Type]
1039-7 | http://loinc.org | G Ag [Presence] on Red Blood Cells from Blood product unit
10390-3 | http://loinc.org | Blood product special preparation [Type]
10391-1 | http://loinc.org | Cytomegalovirus immune globulin given [Volume]
10392-9 | http://loinc.org | Cryoprecipitate given [Volume]
10393-7 | http://loinc.org | Factor IX given [Type]
10394-5 | http://loinc.org | Factor IX given [Volume]
10395-2 | http://loinc.org | Factor VIII given [Type]
10396-0 | http://loinc.org | Factor VIII given [Volume]
10397-8 | http://loinc.org | Hepatitis B immune globulin given [Volume]
10398-6 | http://loinc.org | I Ag [Presence] on Red Blood Cells from Blood product unit
10399-4 | http://loinc.org | I Ag [Presence] on Red Blood Cells from donor
104-0 | http://loinc.org | Ceforanide [Susceptibility] by Minimum inhibitory concentration (MIC)
1040-5 | http://loinc.org | G Ag [Presence] on Red Blood Cells from donor
10400-0 | http://loinc.org | I Ag [Presence] on Red Blood Cells
10401-8 | http://loinc.org | Immune serum globulin given [Type]
10402-6 | http://loinc.org | Immune serum globulin given [Volume]
10403-4 | http://loinc.org | Inject immune serum globulin [Volume]
10404-2 | http://loinc.org | Inject Rh immune globulin [Volume]
10405-9 | http://loinc.org | Inject varicella zoster virus immune globulin [Volume]
10406-7 | http://loinc.org | little i Ag [Presence] on Red Blood Cells from Blood product unit
10407-5 | http://loinc.org | little i Ag [Presence] on Red Blood Cells from donor
10408-3 | http://loinc.org | little i Ag [Presence] on Red Blood Cells
10409-1 | http://loinc.org | Pentaspan given [Volume]
1041-3 | http://loinc.org | G Ag [Presence] on Red Blood Cells
10410-9 | http://loinc.org | Plasma given [Type]
10411-7 | http://loinc.org | Plasma given [Volume]
10412-5 | http://loinc.org | Platelets given [Type]
10413-3 | http://loinc.org | Rh immune globulin given [Volume]
10414-1 | http://loinc.org | Transfuse albumin [Volume]
10415-8 | http://loinc.org | Transfuse blood exchange transfusion [Volume]
10416-6 | http://loinc.org | Transfuse blood product other [Volume]
10417-4 | http://loinc.org | Transfuse cryoprecipitate [Volume]
10418-2 | http://loinc.org | Transfuse factor IX [Volume]
10419-0 | http://loinc.org | Transfuse factor VIII [Volume]
1042-1 | http://loinc.org | H Ab [Presence] in Serum or Plasma from Blood product unit
10420-8 | http://loinc.org | Transfuse immune serum globulin [Volume]
10421-6 | http://loinc.org | Transfuse Pentaspan [Volume]
10422-4 | http://loinc.org | Transfuse plasma [Volume]
10423-2 | http://loinc.org | Transfuse platelets [Volume]
10424-0 | http://loinc.org | Transfuse erythrocytes [Volume]
10425-7 | http://loinc.org | Transfuse Rh immune globulin [Volume]
10426-5 | http://loinc.org | Transfuse whole blood [Volume]
10427-3 | http://loinc.org | Transfuse whole blood autologous [Volume]
10428-1 | http://loinc.org | Varicella zoster virus immune globulin given [Volume]
10429-9 | http://loinc.org | AE 1 Ag [Presence] in Tissue by Immune stain
1043-9 | http://loinc.org | H Ab [Presence] in Serum or Plasma from donor
10430-7 | http://loinc.org | AE 3 Ag [Presence] in Tissue by Immune stain
10431-5 | http://loinc.org | B-cell Ag [Presence] in Tissue by Immune stain
10432-3 | http://loinc.org | CD30 Ag [Presence] in Tissue by Immune stain
10433-1 | http://loinc.org | BR-2 Ag [Presence] in Tissue by Immune stain
10434-9 | http://loinc.org | Complement C3 Ag [Presence] in Tissue by Immune stain

10435-6 | http://loinc.org | C5B-9 Ag [Presence] in Tissue by Immune stain
10436-4 | http://loinc.org | CD15 Ag [Presence] in Tissue by Immune stain
10437-2 | http://loinc.org | CD16 Ag [Presence] in Tissue by Immune stain
10438-0 | http://loinc.org | CD20 Ag [Presence] in Tissue by Immune stain
10439-8 | http://loinc.org | CD3 Ag [Presence] in Tissue by Immune stain
1044-7 | http://loinc.org | H Ab [Presence] in Serum
10440-6 | http://loinc.org | Deprecated CD30 Ag [Presence] in Tissue by Immune stain
10441-4 | http://loinc.org | CD34 Ag [Presence] in Tissue by Immune stain
10442-2 | http://loinc.org | CD56 Ag [Presence] in Tissue by Immune stain
10443-0 | http://loinc.org | CD43 T-cell monocyte+myeloid cell Ag [Presence] in Tissue by Immune stain
10444-8 | http://loinc.org | CD57 Ag [Presence] in Tissue by Immune stain
10445-5 | http://loinc.org | CD11c Ag [Presence] in Tissue by Immune stain
10446-3 | http://loinc.org | Leukocyte common Ag [Presence] in Tissue by Immune stain
10447-1 | http://loinc.org | M-5 Ag [Presence] in Tissue by Immune stain
10448-9 | http://loinc.org | T-cell Ag [Presence] in Tissue by Immune stain
10449-7 | http://loinc.org | Glucose [Mass/volume] in Serum or Plasma --1 hour post meal
1045-4 | http://loinc.org | H NOS Ab [Presence] in Serum or Plasma from Blood product unit
10450-5 | http://loinc.org | Glucose [Mass/volume] in Serum or Plasma --10 hours fasting
10451-3 | http://loinc.org | Proinsulin [Moles/volume] in Serum or Plasma --12 hours fasting
10452-1 | http://loinc.org | Xylose [Mass/volume] in Serum or Plasma --1 hour post 25 g xylose PO
10453-9 | http://loinc.org | Xylose [Mass/volume] in Serum or Plasma --1 hour post dose xylose PO
10454-7 | http://loinc.org | Xylose [Mass/volume] in Serum or Plasma --2 hours post 25 g xylose PO
10455-4 | http://loinc.org | Xylose [Mass/volume] in Serum or Plasma --30 minutes post 25 g xylose PO
10456-2 | http://loinc.org | Xylose [Mass/volume] in Serum or Plasma --6 hours fasting
10457-0 | http://loinc.org | Actin Ag [Presence] in Tissue by Immune stain
10458-8 | http://loinc.org | Alkaline phosphatase.placental Ag [Presence] in Tissue by Immune stain
10459-6 | http://loinc.org | Alpha-1-Fetoprotein Ag [Presence] in Tissue by Immune stain
1046-2 | http://loinc.org | H NOS Ab [Presence] in Serum or Plasma from donor
10460-4 | http://loinc.org | Lactalbumin alpha Ag [Presence] in Tissue by Immune stain
10461-2 | http://loinc.org | Alpha-1-Antichymotrypsin Ag [Presence] in Tissue by Immune stain
10462-0 | http://loinc.org | Alpha 1 antitrypsin Ag [Presence] in Tissue by Immune stain
10463-8 | http://loinc.org | Amyloid A component Ag [Presence] in Tissue by Immune stain
10464-6 | http://loinc.org | Amyloid P component Ag [Presence] in Tissue by Immune stain
10465-3 | http://loinc.org | Amyloid.prealbumin Ag [Presence] in Tissue by Immune stain
10466-1 | http://loinc.org | Anion gap 3 in Serum or Plasma
10467-9 | http://loinc.org | Beta-2-Microglobulin amyloid Ag [Presence] in Tissue by Immune stain
10468-7 | http://loinc.org | Calcitonin Ag [Presence] in Tissue by Immune stain
10469-5 | http://loinc.org | Carcinoembryonic Ag [Presence] in Tissue by Immune stain
1047-0 | http://loinc.org | H NOS Ab [Presence] in Serum or Plasma
10470-3 | http://loinc.org | Choriogonadotropin Ag [Presence] in Tissue by Immune stain
10471-1 | http://loinc.org | Chromogranin A Ag [Presence] in Tissue by Immune stain
10472-9 | http://loinc.org | Chromogranin Ag [Presence] in Tissue by Immune stain
10473-7 | http://loinc.org | Chymotrypsin Ag [Presence] in Tissue by Immune stain
10474-5 | http://loinc.org | Collagen type 4 Ag [Presence] in Tissue by Immune stain
10475-2 | http://loinc.org | Corticotropin Ag [Presence] in Tissue by Immune stain
10476-0 | http://loinc.org | Desmin Ag [Presence] in Tissue by Immune stain
10477-8 | http://loinc.org | Enolase.neuron specific Ag [Presence] in Tissue by Immune stain
10478-6 | http://loinc.org | Eosinophil major basic protein Ag [Presence] in Tissue by Immune stain
10479-4 | http://loinc.org | CD227 Ag [Presence] in Tissue by Immune stain
1048-8 | http://loinc.org | H NOS Ag [Presence] on Red Blood Cells from Blood product unit
10480-2 | http://loinc.org | Estrogen+Progesterone receptor Ag [Presence] in Tissue by Immune stain
10481-0 | http://loinc.org | Follitropin.alpha subunit Ag [Presence] in Tissue by Immune stain
10482-8 | http://loinc.org | Follitropin.beta subunit Ag [Presence] in Tissue by Immune stain
10483-6 | http://loinc.org | Gastrin Ag [Presence] in Tissue by Immune stain
10484-4 | http://loinc.org | Glial fibrillary acidic protein Ag [Presence] in Tissue by Immune stain
10485-1 | http://loinc.org | Glucagon Ag [Presence] in Tissue by Immune stain
10486-9 | http://loinc.org | Hemoglobin Ag [Presence] in Tissue by Immune stain
10487-7 | http://loinc.org | HMB-45 Ag [Presence] in Tissue by Immune stain
10488-5 | http://loinc.org | IgA Ag [Presence] in Tissue by Immune stain
10489-3 | http://loinc.org | IgA.heavy chain Ag [Presence] in Tissue by Immune stain
1049-6 | http://loinc.org | H NOS Ag [Presence] on Red Blood Cells from donor
10490-1 | http://loinc.org | IgE Ag [Presence] in Tissue by Immune stain
10491-9 | http://loinc.org | IgG Ag [Presence] in Tissue by Immune stain
10492-7 | http://loinc.org | IgG.heavy chain Ag [Presence] in Tissue by Immune stain
10493-5 | http://loinc.org | IgM Ag [Presence] in Tissue by Immune stain
10494-3 | http://loinc.org | IgM.heavy chain Ag [Presence] in Tissue by Immune stain
10495-0 | http://loinc.org | Insulin Ag [Presence] in Tissue by Immune stain
10496-8 | http://loinc.org | Immunoglobulin light chains.kappa Ag [Presence] in Tissue by Immune stain
10497-6 | http://loinc.org | Immunoglobulin light chains.kappa amyloid Ag [Presence] in Tissue by Immune stain
10498-4 | http://loinc.org | Keratin Ag [Presence] in Tissue by Immune stain
10499-2 | http://loinc.org | Immunoglobulin light chains.lambda Ag [Presence] in Tissue by Immune stain
105-7 | http://loinc.org | Ceforanide [Susceptibility] by Disk diffusion (KB)

1050-4 | http://loinc.org | H NOS Ag [Presence] on Red Blood Cells
10500-7 | http://loinc.org | Immunoglobulin light chains.lambda amyloid Ag [Presence] in Tissue by Immune stain
10501-5 | http://loinc.org | Lutropin [Units/volume] in Serum or Plasma
10502-3 | http://loinc.org | Lutropin Ag [Presence] in Tissue by Immune stain
10503-1 | http://loinc.org | Lysozyme Ag [Presence] in Tissue by Immune stain
10504-9 | http://loinc.org | Myelin basic protein Ag [Presence] in Tissue by Immune stain
10505-6 | http://loinc.org | Myoglobin Ag [Presence] in Tissue by Immune stain
10506-4 | http://loinc.org | Peanut agglutinin Ag [Presence] in Tissue by Immune stain
10507-2 | http://loinc.org | Prolactin Ag [Presence] in Tissue by Immune stain
10508-0 | http://loinc.org | Prostate specific Ag [Presence] in Tissue by Immune stain
10509-8 | http://loinc.org | Prostatic acid phosphatase Ag [Presence] in Tissue by Immune stain
1051-2 | http://loinc.org | Hemolytic disease of newborn screen [Interpretation] in Blood
10510-6 | http://loinc.org | S-100 Ag Ag [Presence] in Tissue by Immune stain
10511-4 | http://loinc.org | Serotonin Ag [Presence] in Tissue by Immune stain
10512-2 | http://loinc.org | Somatostatin Ag [Presence] in Tissue by Immune stain
10513-0 | http://loinc.org | Somatotropin Ag [Presence] in Tissue by Immune stain
10514-8 | http://loinc.org | Synaptophysin Ag [Presence] in Tissue by Immune stain
10515-5 | http://loinc.org | Thyroglobulin Ag [Presence] in Tissue by Immune stain
10516-3 | http://loinc.org | Thyrotropin Ag [Presence] in Tissue by Immune stain
10517-1 | http://loinc.org | Trypsin Ag [Presence] in Tissue by Immune stain
10518-9 | http://loinc.org | Ulex europaeus I lectin Ag [Presence] in Tissue by Immune stain
10519-7 | http://loinc.org | Vimentin Ag [Presence] in Tissue by Immune stain
1052-0 | http://loinc.org | Deprecated I (intermediate) subtype [Presence] in Serum or Plasma from Blood product unit
10520-5 | http://loinc.org | Coagulation factor VI Ag [Presence] in Tissue by Immune stain
10521-3 | http://loinc.org | Coagulation factor VIII Ag [Presence] in Tissue by Immune stain
10522-1 | http://loinc.org | Coagulation factor XIII Ag [Presence] in Tissue by Immune stain
10523-9 | http://loinc.org | Fibrinogen Ag [Presence] in Tissue by Immune stain
10524-7 | http://loinc.org | Microscopic observation [Identifier] in Cervix by Cyto stain
10525-4 | http://loinc.org | Microscopic observation [Identifier] in Unspecified specimen by Cyto stain
10526-2 | http://loinc.org | Microscopic observation [Identifier] in Sputum by Cyto stain
10527-0 | http://loinc.org | Microscopic observation [Identifier] in Tissue by Cyto stain
10528-8 | http://loinc.org | Acetophenazine [Mass/volume] in Serum or Plasma
10529-6 | http://loinc.org | Amoxapine metabolite [Mass/volume] in Serum or Plasma
1053-8 | http://loinc.org | Deprecated I (intermediate) subtype [Presence] in serum or plasma from donor
10530-4 | http://loinc.org | Aprobarbital [Mass/volume] in Serum or Plasma
10531-2 | http://loinc.org | Bretylium [Mass/volume] in Serum or Plasma
10532-0 | http://loinc.org | Deprecated Desethylamiodarone [Mass/volume] in Serum or Plasma
10533-8 | http://loinc.org | Propoxyphene+Acetaminophen [Mass/volume] in Serum or Plasma
10534-6 | http://loinc.org | Diazoxide [Mass/volume] in Serum or Plasma
10535-3 | http://loinc.org | Digoxin [Mass/volume] in Serum or Plasma
10536-1 | http://loinc.org | Dipyridamole [Mass/volume] in Serum or Plasma
10537-9 | http://loinc.org | Deprecated Doxepin+Nordoxepin [Mass/volume] in Serum or Plasma
10538-7 | http://loinc.org | Deprecated Fluoxetine+Norfluoxetine [Mass/volume] in Serum or Plasma
10539-5 | http://loinc.org | Glipizide [Mass/volume] in Serum or Plasma
1054-6 | http://loinc.org | Deprecated I (intermediate) subtype [Presence] in srum
10540-3 | http://loinc.org | Glyburide [Mass/volume] in Serum or Plasma
10541-1 | http://loinc.org | Mepivacaine [Mass/volume] in Serum or Plasma
10542-9 | http://loinc.org | Metharbital [Mass/volume] in Serum or Plasma
10543-7 | http://loinc.org | Methsuximide+Normethsuximide [Mass/volume] in Serum or Plasma
10544-5 | http://loinc.org | Normeperidine [Presence] in Serum or Plasma
10545-2 | http://loinc.org | Normephenytoin [Mass/volume] in Serum or Plasma
10546-0 | http://loinc.org | Normethsuximide [Mass/volume] in Serum or Plasma
10547-8 | http://loinc.org | Primidone+Phenobarbital [Mass/volume] in Serum or Plasma
10548-6 | http://loinc.org | Phenytoin Free/Phenytoin.total in Serum or Plasma
10549-4 | http://loinc.org | Pirmenol [Mass/volume] in Serum or Plasma
1055-3 | http://loinc.org | Deprecated I (intermediate) subtype [Presence] on Red Blood Cells from Blood product unit
10550-2 | http://loinc.org | Deprecated Temazepam [Mass/volume] in Serum or Plasma
10551-0 | http://loinc.org | Triamterene [Mass/volume] in Serum or Plasma
10552-8 | http://loinc.org | Tricyclic antidepressants [Mass/volume] in Serum or Plasma
10553-6 | http://loinc.org | Prostatic acid phosphatase [Enzymatic activity/volume] in Genital fluid
10554-4 | http://loinc.org | Deprecated Prostatic acid phosphatase [Enzymatic activity/volume] in Seminal plasma
10555-1 | http://loinc.org | Acrosin [Entitic Catalytic Activity] in Spermatozoa
10556-9 | http://loinc.org | Deprecated Adenosine triphosphatase [Enzymatic activity/volume] in Seminal plasma
10557-7 | http://loinc.org | Adenosine triphosphate [Moles/volume] in Semen
10558-5 | http://loinc.org | Albumin [Moles/volume] in Semen
10559-3 | http://loinc.org | Deprecated Calcium [Molecules/volume] in Semen
1056-1 | http://loinc.org | Deprecated I (intermediate) subtype [Presence] on Red Blood Cells from donor
10560-1 | http://loinc.org | Carcinoembryonic Ag [Units/volume] in Semen
10561-9 | http://loinc.org | Carnitine [Moles/volume] in Semen
10562-7 | http://loinc.org | Cells [#/volume] in Cervical mucus
10563-5 | http://loinc.org | Cells other than spermatozoa [#/volume] in Semen
10564-3 | http://loinc.org | Cervical mucus [Volume]

10565-0 | http://loinc.org | Choriogonadotropin [Units/volume] in Semen
10566-8 | http://loinc.org | Deprecated Choriogonadotropin [Molecules/volume] in Semen
10567-6 | http://loinc.org | Citrate [Moles/volume] in Semen
10568-4 | http://loinc.org | Clarity of Semen
10569-2 | http://loinc.org | Color of Semen
1057-9 | http://loinc.org | Deprecated I (intermediate) subtype [Presence] on Red Blood Cells
10570-0 | http://loinc.org | Consistency of Cervical mucus
10571-8 | http://loinc.org | Deprecated Consistency of Semen
10572-6 | http://loinc.org | Deprecated Duration^post ejaculation
10573-4 | http://loinc.org | Ferning [Type] in Cervical mucus
10574-2 | http://loinc.org | Fructose [Moles/volume] in Semen
10575-9 | http://loinc.org | Deprecated Gamma glutamyl transferase [Enzymatic activity/volume] in Semen
10576-7 | http://loinc.org | Germ cells.immature [#/volume] in Semen
10577-5 | http://loinc.org | Glucosidase [Enzymatic activity/volume] in Seminal plasma
10578-3 | http://loinc.org | Glycerophosphocholine [Moles/volume] in Seminal plasma
10579-1 | http://loinc.org | Leukocytes [#/volume] in Semen
1058-7 | http://loinc.org | I Ab [Presence] in Serum or Plasma from Blood product unit
10580-9 | http://loinc.org | Liquefaction [Time] in Semen
10581-7 | http://loinc.org | Deprecated Number of entities [#] in Spermatozoa
10582-5 | http://loinc.org | pH of Cervical mucus
10583-3 | http://loinc.org | Prostaglandin F1 alpha [Moles/volume] in Semen
10584-1 | http://loinc.org | Deprecated Protein [Mass/volume] in Semen
10585-8 | http://loinc.org | Round cells [#/volume] in Semen
10586-6 | http://loinc.org | Deprecated Volume of Semen
10587-4 | http://loinc.org | Sexual abstinence duration
10588-2 | http://loinc.org | Spermatogonia [#/volume] in Semen
10589-0 | http://loinc.org | Spermatids [#/volume] in Semen by Streptoavidin-biotin method (SAB)
1059-5 | http://loinc.org | I Ab [Presence] in Serum or Plasma from donor
10590-8 | http://loinc.org | Spermatids [#/volume] in Semen by Sertoli cell barrier method (SCB)
10591-6 | http://loinc.org | Primary Spermatocytes [#/volume] in Semen
10592-4 | http://loinc.org | Secondary Spermatocytes [#/volume] in Semen
10593-2 | http://loinc.org | Spermatozoa Pyriform Head/100 spermatozoa in Semen
10594-0 | http://loinc.org | Spermatozoa Tapering Head/100 spermatozoa in Semen
10595-7 | http://loinc.org | Deprecated Spermatozoa [#/volume] in Semen
10596-5 | http://loinc.org | Deprecated Spermatozoa Ab in cervical mucosa
10597-3 | http://loinc.org | Deprecated Spermatozoa Ab in semen
10598-1 | http://loinc.org | Deprecated Spermatozoa Ab in serum
10599-9 | http://loinc.org | Spermatozoa penetration [Presence] in Seminal fluid and Cervical mucosa by Kremer test
106-5 | http://loinc.org | Ceforanide [Susceptibility] by Serum bactericidal titer
1060-3 | http://loinc.org | I Ab [Presence] in Serum or Plasma
10600-5 | http://loinc.org | Spermatozoa penetration [Presence] in Seminal fluid and Cervical mucosa
10601-3 | http://loinc.org | Spermatozoa penetration [Presence] in Seminal fluid and Cervical mucosa --post coitus
10602-1 | http://loinc.org | Spermatozoa Abnormal Head/100 spermatozoa in Semen
10603-9 | http://loinc.org | Spermatozoa Abnormal Midpiece/100 spermatozoa in Semen
10604-7 | http://loinc.org | Spermatozoa Abnormal Tail/100 spermatozoa in Semen
10605-4 | http://loinc.org | Spermatozoa Agglutinated/100 spermatozoa in Semen
10606-2 | http://loinc.org | Spermatozoa Amorphous Head/100 spermatozoa in Semen
10607-0 | http://loinc.org | Spermatozoa Coiled Tail/100 spermatozoa in Semen
10608-8 | http://loinc.org | Spermatozoa Cytoplasmic Droplet/100 spermatozoa in Semen
10609-6 | http://loinc.org | Spermatozoa Duplicate Head/100 spermatozoa in Semen
1061-1 | http://loinc.org | I NOS Ab [Presence] in Serum or Plasma from Blood product unit
10610-4 | http://loinc.org | Spermatozoa Duplicate Tail/100 spermatozoa in Semen
10611-2 | http://loinc.org | Spermatozoa Immotile/100 spermatozoa in Semen
10612-0 | http://loinc.org | Spermatozoa Large Oval Head/100 spermatozoa in Semen
10613-8 | http://loinc.org | Spermatozoa Viable/100 spermatozoa in Semen
10614-6 | http://loinc.org | Spermatozoa Motile w IgA/100 spermatozoa in Semen by Immunobead
10615-3 | http://loinc.org | Spermatozoa Motile w IgA/100 spermatozoa in Semen by Mixed antiglobulin reaction
10616-1 | http://loinc.org | Spermatozoa Motile w IgG/100 spermatozoa in Semen by Immunobead
10617-9 | http://loinc.org | Spermatozoa Motile w IgG/100 spermatozoa in Semen by Mixed antiglobulin reaction
10618-7 | http://loinc.org | Spermatozoa Motile w IgM/100 spermatozoa in Semen by Immunobead
10619-5 | http://loinc.org | Spermatozoa Motile w IgM/100 spermatozoa in Semen by Mixed antiglobulin reaction
1062-9 | http://loinc.org | I NOS Ab [Presence] in Serum or Plasma from donor
10620-3 | http://loinc.org | Spermatozoa Nonprogressive/100 spermatozoa in Semen
10621-1 | http://loinc.org | Spermatozoa Normal Head/100 spermatozoa in Semen
10622-9 | http://loinc.org | Spermatozoa Normal/100 spermatozoa in Semen
10623-7 | http://loinc.org | Spermatozoa Pin Head/100 spermatozoa in Semen
10624-5 | http://loinc.org | Spermatozoa Rapid/100 spermatozoa in Semen
10625-2 | http://loinc.org | Spermatozoa Round Head/100 spermatozoa in Semen
10626-0 | http://loinc.org | Spermatozoa Slow/100 spermatozoa in Semen
10627-8 | http://loinc.org | Spermatozoa Small Oval Head/100 spermatozoa in Semen
10628-6 | http://loinc.org | Spermatozoa Tail Swelling/100 spermatozoa in Semen
10629-4 | http://loinc.org | Spermatozoa Vacuolated Head/100 spermatozoa in Semen

1063-7 | http://loinc.org | I NOS Ab [Presence] in Serum or Plasma
10630-2 | http://loinc.org | Spinnbarkeit [Length] in Cervical mucus
10631-0 | http://loinc.org | Testosterone [Moles/volume] in Semen
10632-8 | http://loinc.org | Time until next menstrual period
10633-6 | http://loinc.org | Zinc [Moles/volume] in Semen
10634-4 | http://loinc.org | Complement C1 esterase inhibitor.functional/Complement C1 esterase inhibitor.total in Serum or Plasma
10635-1 | http://loinc.org | Acanthamoeba sp identified in Eye by Organism specific culture
10636-9 | http://loinc.org | Acanthamoeba sp identified in Eye by Wet preparation
10637-7 | http://loinc.org | Microscopic observation [Identifier] in Tissue by Night blue stain
10638-5 | http://loinc.org | Thermophilic Actinomycetes colony count [#/volume] in Unspecified specimen by Organism specific culture
10639-3 | http://loinc.org | Thermophilic Actinomycetes identified in Unspecified specimen by Organism specific culture
1064-5 | http://loinc.org | I NOS Ag [Presence] on Red Blood Cells from Blood product unit
10640-1 | http://loinc.org | Deprecated Adenovirus 40+41 [Identifier] in Stool by Electron microscopy
10641-9 | http://loinc.org | Amoeba identified in Aspirate by Immune stain
10642-7 | http://loinc.org | Amoeba identified in Aspirate by Wet preparation
10643-5 | http://loinc.org | Amoeba identified in Stool by Organism specific culture
10644-3 | http://loinc.org | Arthropod identified in Unspecified specimen
10645-0 | http://loinc.org | Aspergillus fumigatus Ag [Presence] in Tissue by Immunofluorescence
10646-8 | http://loinc.org | Astrovirus [Identifier] in Stool by Electron microscopy
10647-6 | http://loinc.org | Babesia sp identified in Blood by Thick film
10648-4 | http://loinc.org | Babesia sp identified in Blood by Thin film
10649-2 | http://loinc.org | Calicivirus [Identifier] in Stool by Electron microscopy
1065-2 | http://loinc.org | I NOS Ag [Presence] on Red Blood Cells from donor
10650-0 | http://loinc.org | Candida sp DNA [Presence] in Blood by Probe with amplification
10651-8 | http://loinc.org | Chlamydophila pneumoniae Ag [Presence] in Sputum or Bronchial

4.3.2.16508 HL7 v3 Value Set ActIncidentCode

URL: https://hl7.org/fhir/STU3/v3/ActIncidentCode/vs.html

This page is part of the FHIR Specification (v3.0.2: STU 3). The current version which supercedes this version is 4.0.1. For a full list of available versions, see the Directory of published versions

Vocabulary Work Group | Maturity Level: N/A | External | Use Context: Any

This value set (http://hl7.org/fhir/ValueSet/v3-ActIncidentCode) is defined as part of HL7 v3. Related FHIR content: ActIncidentCode.

Summary

Defining URL: | http://hl7.org/fhir/ValueSet/v3-ActIncidentCode
Name: | ActIncidentCode
Definition: | Set of codes indicating the type of incident or accident.
OID: | 2.16.840.1.113883.1.11.16508 (for OID based terminology systems)
Source Resource | XML / JSON

This value set is used in the following places:

* ExplanationOfBenefit.accident.type (Required)

* Claim.accident.type (Required)

4.3.2.16508.1 Content Logical Definition

This value set includes codes from the following code systems:

* Include codes from http://hl7.org/fhir/v3/ActCode where concept is-a _ActIncidentCode

* Exclude these codes as defined in

http://hl7.org/fhir/v3/ActCode

Code | Display
_ActIncidentCode | ActIncidentCode | Set of codes indicating the type of incident or accident.

4.3.2.16508.2 Expansion

This expansion generated 19 Apr 2017

This value set contains 4 concepts

Expansion based on http://hl7.org/fhir/v3/ActCode version 2016-11-11

All codes from system http://hl7.org/fhir/v3/ActCode

Code | Display | Definition
MVA | Motor vehicle accident | Incident or accident as the result of a motor vehicle accident
SCHOOL | School Accident | Incident or accident is the result of a school place accident.
SPT | Sporting Accident | Incident or accident is the result of a sporting accident.
WPA | Workplace accident | Incident or accident is the result of a work place accident

4.3.2.16621 HL7 v3 Value Set ActSubstanceAdminSubstitutionCode

URL: https://hl7.org/fhir/STU3/v3/ActSubstanceAdminSubstitutionCode/vs.html

This page is part of the FHIR Specification (v3.0.2: STU 3). The current version which supercedes this version is 4.0.1. For a full list of available versions, see the Directory of published versions

Vocabulary Work Group | Maturity Level: N/A | External | Use Context: Any

This value set (http://hl7.org/fhir/ValueSet/v3-ActSubstanceAdminSubstitutionCode) is defined as part of HL7 v3. Related FHIR content: ActSubstanceAdminSubstitutionCode.

Summary

Defining URL: | http://hl7.org/fhir/ValueSet/v3-ActSubstanceAdminSubstitutionCode
Name: | ActSubstanceAdminSubstitutionCode
Definition: | No Description Provided
OID: | 2.16.840.1.113883.1.11.16621 (for OID based terminology systems)
Source Resource | XML / JSON

This value set is used in the following places:

* MedicationDispense.substitution.type (Example)

4.3.2.16621.1 Content Logical Definition

This value set includes codes from the following code systems:

* Include codes from http://hl7.org/fhir/v3/substanceAdminSubstitution where concept is-a _ActSubstanceAdminSubstitutionCode

* Exclude these codes as defined in

http://hl7.org/fhir/v3/substanceAdminSubstitution

Code | Display
_ActSubstanceAdminSubstitutionCode | ActSubstanceAdminSubstitutionCode | Description: Substitution occurred or is permitted with another product that may potentially have different ingredients, but having the same biological and therapeutic effects.

4.3.2.16621.2 Expansion

This expansion generated 19 Apr 2017

This value set contains 9 concepts

Expansion based on http://hl7.org/fhir/v3/substanceAdminSubstitution version 2016-11-11

All codes from system http://hl7.org/fhir/v3/substanceAdminSubstitution

Code | Display | Definition
E | equivalent | Description: Substitution occurred or is permitted with another bioequivalent and therapeutically equivalent product.
EC | equivalent composition | Description: Substitution occurred or is permitted with another product that is a: pharmaceutical alternative containing the same active ingredient but is formulated with different salt, ester pharmaceutical equivalent that has the same active ingredient, strength, dosage form and route of administration Examples: Pharmaceutical alternative: Erythromycin Ethylsuccinate for Erythromycin Stearate Pharmaceutical equivalent: Lisonpril for Zestril
BC | brand composition | Description: Substitution occurred or is permitted between equivalent Brands but not Generics Examples: Zestril for Prinivil Coumadin for Jantoven
G | generic composition | Description: Substitution occurred or is permitted between equivalent Generics but not Brands Examples: Lisnopril (Lupin Corp) for Lisnopril (Wockhardt Corp)
TE | therapeutic alternative | Description: Substitution occurred or is permitted with another product having the same therapeutic objective and safety profile. Examples: ranitidine for Tagamet
TB | therapeutic brand | Description: Substitution occurred or is permitted between therapeutically equivalent Brands but not Generics > Examples: Zantac for Tagamet
TG | therapeutic generic | Description: Substitution occurred or is permitted between therapeutically equivalent Generics but not Brands > Examples: Ranitidine for cimetidine
F | formulary | Description: This substitution was performed or is permitted based on formulary guidelines.
N | none | No substitution occurred or is permitted.

4.3.2.16643 HL7 v3 Value Set SeverityObservation

URL: https://hl7.org/fhir/STU3/v3/SeverityObservation/vs.html

This page is part of the FHIR Specification (v3.0.2: STU 3). The current version which supercedes this version is 4.0.1. For a full list of available versions, see the Directory of published versions

Vocabulary Work Group | Maturity Level: N/A | External | Use Context: Any

This value set (http://hl7.org/fhir/ValueSet/v3-SeverityObservation) is defined as part of HL7 v3. Related FHIR content: SeverityObservation.

Summary

Defining URL: | http://hl7.org/fhir/ValueSet/v3-SeverityObservation
Name: | SeverityObservation
Definition: | Potential values for observations of severity.
OID: | 2.16.840.1.113883.1.11.16643 (for OID based terminology systems)
Source Resource | XML / JSON

This value set is used in the following places:

* This value set is the target of translations in the ConceptMap v3 map for DetectedIssueSeverity

4.3.2.16643.1 Content Logical Definition

This value set includes codes from the following code systems:

* Include codes from http://hl7.org/fhir/v3/ObservationValue where concept is-a _SeverityObservation

* Exclude these codes as defined in

http://hl7.org/fhir/v3/ObservationValue

Code | Display
_SeverityObservation | SeverityObservation | Potential values for observations of severity.

4.3.2.16643.2 Expansion

This expansion generated 19 Apr 2017

This value set contains 3 concepts

Expansion based on http://hl7.org/fhir/v3/ObservationValue version 2016-11-11

All codes from system http://hl7.org/fhir/v3/ObservationValue

Code | Display | Definition
H | High | Indicates the condition may be life-threatening or has the potential to cause permanent injury.
L | Low | Indicates the condition may result in some adverse consequences but is unlikely to substantially affect the situation of the subject.
M | Moderate | Indicates the condition may result in noticable adverse adverse consequences but is unlikely to be life-threatening or cause permanent injury.

4.3.2.16926 HL7 v3 Value Set x_BasicConfidentialityKind

URL: https://hl7.org/fhir/STU3/v3/x_BasicConfidentialityKind/vs.html

This page is part of the FHIR Specification (v3.0.2: STU 3). The current version which supercedes this version is 4.0.1. For a full list of available versions, see the Directory of published versions

Vocabulary Work Group | Maturity Level: N/A | External | Use Context: Any

This value set (http://hl7.org/fhir/ValueSet/v3-x_BasicConfidentialityKind) is defined as part of HL7 v3. Related FHIR content: x_BasicConfidentialityKind.

Summary

Defining URL: | http://hl7.org/fhir/ValueSet/v3-xBasicConfidentialityKind
Name: | x_BasicConfidentialityKind
Definition: | Description: Used to enumerate the typical confidentiality constraints placed upon a clinical document. Usage Note: x_BasicConfidentialityKind is a subset of Confidentiality codes that are used as metadata indicating the receiver responsibility to comply with normally applicable jurisdictional privacy law or disclosure authorization; that the receiver may not disclose this information except as directed by the information custodian, who may be the information subject; or that the receiver may not disclose this information except as directed by the information custodian, who may be the information subject.
OID: | 2.16.840.1.113883.1.11.16926 (for OID based terminology systems)
Source Resource | XML / JSON

This value set is not currently used

4.3.2.16926.1 Content Logical Definition

This value set includes codes from the following code systems:

* Include these codes as defined in

http://hl7.org/fhir/v3/Confidentiality

Code | Display
N | normal | Definition: Privacy metadata indicating that the information is typical, non-stigmatizing health information, which presents typical risk of harm if disclosed without authorization. Examples: In the US, this includes what HIPAA identifies as the minimum necessary protected health information (PHI) given a covered purpose of use (treatment, payment, or operations). Includes typical, non-stigmatizing health information disclosed in an application for health, workers compensation, disability, or life insurance. Map: Partial Map to ISO 13606-4 Sensitivity Level (3) Clinical Care: Default for normal clinical care access (i.e. most clinical staff directly caring for the patient should be able to access nearly all of the EHR). Maps to normal confidentiality for treatment information but not to ancillary care, payment and operations. Usage Note: This metadata indicates that the receiver may be obligated to comply with applicable jurisdictional privacy law or disclosure authorization.
R | restricted | Privacy metadata indicating highly sensitive, potentially stigmatizing information, which presents a high risk to the information subject if disclosed without authorization. May be pre-empted by jurisdictional law, e.g., for public health reporting or emergency treatment. Examples: Includes information that is additionally protected such as sensitive conditions mental health, HIV, substance abuse, domestic violence, child abuse, genetic disease, and reproductive health; or sensitive demographic information such as a patient's standing as an employee or a celebrity. May be used to indicate proprietary or classified information that is not related to an individual, e.g., secret ingredients in a therapeutic substance; or the name of a manufacturer. Map: Partial Map to ISO 13606-4 Sensitivity Level (3) Clinical Care: Default for normal clinical care access (i.e. most clinical staff directly caring for the patient should be able to access nearly all of the EHR). Maps to normal confidentiality for treatment information but not to ancillary care, payment and operations.. Usage Note: This metadata indicates that the receiver may be obligated to comply with applicable, prevailing (default) jurisdictional privacy law or disclosure authorization..
V | very restricted | . Privacy metadata indicating that the information is extremely sensitive and likely stigmatizing health information that presents a very high risk if disclosed without authorization. This information must be kept in the highest confidence. Examples: Includes information about a victim of abuse, patient requested information sensitivity, and taboo subjects relating to health status that must be discussed with the patient by an attending provider before sharing with the patient. May also include information held under â€œlegal lockâ€? or attorney-client privilege Map: This

metadata indicates that the receiver may not disclose this information except as directed by the information custodian, who may be the information subject. Usage Note: This metadata indicates that the receiver may not disclose this information except as directed by the information custodian, who may be the information subject.

4.3.2.16927 HL7 v3 Value Set RoleClassServiceDeliveryLocation

URL: https://hl7.org/fhir/STU3/v3/RoleClassServiceDeliveryLocation/vs.html

This page is part of the FHIR Specification (v3.0.2: STU 3). The current version which supercedes this version is 4.0.1. For a full list of available versions, see the Directory of published versions

Vocabulary Work Group | Maturity Level: N/A | External | Use Context: Any

This value set (http://hl7.org/fhir/ValueSet/v3-RoleClassServiceDeliveryLocation) is defined as part of HL7 v3. Related FHIR content: RoleClassServiceDeliveryLocation.

Summary

Defining URL: | http://hl7.org/fhir/ValueSet/v3-RoleClassServiceDeliveryLocation
Name: | RoleClassServiceDeliveryLocation
Definition: | A role played by a place at which services may be provided.
OID: | 2.16.840.1.113883.1.11.16927 (for OID based terminology systems)
Source Resource | XML / JSON

This value set is not currently used

4.3.2.16927.1 Content Logical Definition

This value set includes codes from the following code systems:

* Include codes from http://hl7.org/fhir/v3/RoleClass where concept is-a SDLOC

4.3.2.16927.2 Expansion

This expansion generated 19 Apr 2017

This value set contains 3 concepts

Expansion based on http://hl7.org/fhir/v3/RoleClass version 2016-11-11

All codes from system http://hl7.org/fhir/v3/RoleClass

Code | Display | Definition
SDLOC | service delivery location | A role played by a place at which services may be provided.
DSDLOC | dedicated service delivery location | A role of a place (player) that is intended to house the provision of services. Scoper is the Entity (typically Organization) that provides these services. This is not synonymous with "ownership."
ISDLOC | incidental service delivery location | A role played by a place at which health care services may be provided without prior designation or authorization.

4.3.2.17660 HL7 v3 Value Set ServiceDeliveryLocationRoleType

URL: https://hl7.org/fhir/STU3/v3/ServiceDeliveryLocationRoleType/vs.html

This page is part of the FHIR Specification (v3.0.2: STU 3). The current version which supercedes this version is 4.0.1. For a full list of available versions, see the Directory of published versions

Vocabulary Work Group | Maturity Level: N/A | External | Use Context: Any

This value set (http://hl7.org/fhir/ValueSet/v3-ServiceDeliveryLocationRoleType) is defined as part of HL7 v3. Related FHIR content: ServiceDeliveryLocationRoleType.

Summary

Defining URL: | http://hl7.org/fhir/ValueSet/v3-ServiceDeliveryLocationRoleType
Name: | ServiceDeliveryLocationRoleType
Definition: | A role of a place that further classifies the setting (e.g., accident site, road side, work site, community location) in which services are delivered.
OID: | 2.16.840.1.113883.1.11.17660 (for OID based terminology systems)
Source Resource | XML / JSON

This value set is used in the following places:

* Location.type (Extensible)

4.3.2.17660.1 Content Logical Definition

This value set includes codes from the following code systems:

* Include codes from http://hl7.org/fhir/v3/RoleCode where concept is-a _ServiceDeliveryLocationRoleType

* Exclude these codes as defined in

http://hl7.org/fhir/v3/RoleCode

Code | Display
_ServiceDeliveryLocationRoleType | ServiceDeliveryLocationRoleType | A role of a place that further classifies the setting (e.g., accident site, road side, work site, community location) in which services are delivered.

4.3.2.17660.2 Expansion

This expansion generated 19 Apr 2017

This value set contains 123 concepts

Expansion based on http://hl7.org/fhir/v3/RoleCode version 2016-11-11

All codes from system http://hl7.org/fhir/v3/RoleCode

Code | Display | Definition

DX | Diagnostics or therapeutics unit | A practice setting where diagnostic procedures or therapeutic interventions are performed

CVDX | Cardiovascular diagnostics or therapeutics unit | A practice setting where cardiovascular diagnostic procedures or therapeutic interventions are performed (e.g., cardiac catheterization lab, echocardiography suite)

CATH | Cardiac catheterization lab | Cardiac catheterization lab

ECHO | Echocardiography lab | Echocardiography lab

GIDX | Gastroenterology diagnostics or therapeutics lab | A practice setting where GI procedures (such as endoscopies) are performed

ENDOS | Endoscopy lab | (X12N 261QD0000N)

RADDX | Radiology diagnostics or therapeutics unit | A practice setting where radiology services (diagnostic or therapeutic) are provided (X12N 261QR0200N)

RADO | Radiation oncology unit | (X12N 261QX0203N)

RNEU | Neuroradiology unit | Neuroradiology unit

HOSP | Hospital | An acute care institution that provides medical, surgical, or psychiatric care and treatment for the sick or the injured.

CHR | Chronic Care Facility | (1) A hospital including a physical plant and personnel that provides multidisciplinary diagnosis and treatment for diseases that have one or more of the following characteristics: is permanent; leaves residual disability; is caused by nonreversible pathological alteration; requires special training of the patient for rehabilitation; and/or may be expected to require a long period of supervision or care. In addition, patients require the safety, security, and shelter of these specialized inpatient or partial hospitalization settings. (2) A hospital that provides medical and skilled nursing services to patients with long-term illnesses who are not in an acute phase but who require an intensity of services not available in nursing homes

GACH | Hospitals; General Acute Care Hospital | (X12N 282N00000N)

MHSP | Military Hospital | A health care facility operated by the Department of Defense or other military operation.

PSYCHF | Psychatric Care Facility | Healthcare facility that cares for patients with psychiatric illness(s).

RH | Rehabilitation hospital | (X12N 283X00000N)

RHAT | addiction treatment center | Description: A location that plays the role of delivering services which may include life training and/or social support to people with addictions.

RHII | intellectual impairment center | Description: A location that plays the role of delivering services which may include adaptation, rehabilitation and social integration services for people with intellectual and/or pervasive development disorders such as autism or severe behaviour disorder.

RHMAD | parents with adjustment difficulties center | Description: A location that plays the role of delivering services which may social support services for adolescents who are pregnant or have child and are experiencing adaptation issues/difficulties in their current or eventual parenting role.

RHPI | physical impairment center | Description: A location that plays the role of delivering services which may include adaptation, rehabilitation and social integration services for people with physical impairments.

RHPIH | physical impairment - hearing center | Description: A location that plays the role of delivering services for people with hearing impairments.

RHPIMS | physical impairment - motor skills center | Description: A location that plays the role of delivering services for people with motor skill impairments.

RHPIVS | physical impairment - visual skills center | Description: A location that plays the role of delivering services for people with visual skill impairments.

RHYAD | youths with adjustment difficulties center | Description: A location that plays the role of delivering services which may include life training and/or social support services for the adaption, rehabilitation and social integration of youths with adjustment difficulties.

HU | Hospital unit | Hospital unit

BMTU | Bone marrow transplant unit | Bone marrow transplant unit

CCU | Coronary care unit | Coronary care unit

CHEST | Chest unit | A specialty unit in hospital that focuses on chronic respirator patients and pulmonary failure

EPIL | Epilepsy unit | Epilepsy unit

ER | Emergency room | The section of a health care facility for providing rapid treatment to victims of sudden illness or trauma.

ETU | Emergency trauma unit | Emergency trauma unit

HD | Hemodialysis unit | Hemodialysis unit

HLAB | hospital laboratory | Description: A location that plays the role of delivering services which may include tests done based on clinical specimens to get health information about a patient as pertaining to the diagnosis, treatment and prevention of disease. Hospital laboratories may be further divided into specialized units such as Anatomic Pathology, Microbiology, and Biochemistry.

INLAB | inpatient laboratory | Description: A location that plays the role of delivering services which may include tests are done on clinical specimens to get health information about a patient pertaining to the diagnosis, treatment, and prevention of disease for a hospital visit longer than one day.

OUTLAB | outpatient laboratory | Description: A location that plays the role of delivering services which may include tests are done on clinical specimens to get health information about a patient pertaining to the diagnosis, treatment, and prevention of disease for same day visits.

HRAD | radiology unit | Description: A location that plays the role of delivering services which may include the branch of medicine that uses ionizing and non-ionizing radiation to diagnose and treat diseases. The radiology unit may be further divided into subspecialties such as Imaging, Cardiovascular, Thoracic, and Ultrasound.

HUSCS | specimen collection site | Description: A location that plays the role of delivering services which may include collecting specimens and/or samples from patients for laboratory testing purposes, but does not perform any tests or analysis functions.

ICU | Intensive care unit | Intensive care unit

PEDICU | Pediatric intensive care unit | Pediatric intensive care unit

PEDNICU | Pediatric neonatal intensive care unit | Pediatric neonatal intensive care unit

INPHARM | inpatient pharmacy | Description: A location that plays the role of delivering services which may include providing judicious, safe, efficacious, appropriate and cost effective use of medicines for treatment of patients for visits longer than one day. The distinction between inpatient pharmacies and retail (or outpatient) pharmacies is that they are part of a patient's continuity of care while staying in the hospital.

MBL | medical laboratory | Description: A location that plays the role of delivering services which include biochemistry, hematology, microbiology, immunochemistry, and toxicology.

NCCS | Neurology critical care and stroke unit | Neurology critical care and stroke unit

NS | Neurosurgery unit | Neurosurgery unit
OUTPHARM | outpatient pharmacy | Description: A location that plays the role of delivering services which may include providing judicious, safe, efficacious, appropriate and cost effective use of medicines for treatment of patients for outpatient visits and may also be used for discharge prescriptions.
PEDU | Pediatric unit | Pediatric unit
PHU | Psychiatric hospital unit | (X12N 273R00000N)
RHU | Rehabilitation hospital unit | Rehabilitation hospital unit
SLEEP | Sleep disorders unit | (X12N 261QA1200N)
NCCF | Nursing or custodial care facility | Nursing or custodial care facility
SNF | Skilled nursing facility | (X12N 314000000N)
OF | Outpatient facility | Outpatient facility
ALL | Allergy clinic | Allergy clinic
AMPUT | Amputee clinic | Amputee clinic
BMTC | Bone marrow transplant clinic | Bone marrow transplant clinic
BREAST | Breast clinic | Breast clinic
CANC | Child and adolescent neurology clinic | Child and adolescent neurology clinic
CAPC | Child and adolescent psychiatry clinic | Child and adolescent psychiatry clinic
CARD | Ambulatory Health Care Facilities; Clinic/Center; Rehabilitation: Cardiac Facilities | Ambulatory Health Care Facilities; Clinic/Center; Rehabilitation: Cardiac Facilities
PEDCARD | Pediatric cardiology clinic | Pediatric cardiology clinic
COAG | Coagulation clinic | Coagulation clinic
CRS | Colon and rectal surgery clinic | Colon and rectal surgery clinic
DERM | Dermatology clinic | Dermatology clinic
ENDO | Endocrinology clinic | Endocrinology clinic
PEDE | Pediatric endocrinology clinic | Pediatric endocrinology clinic
ENT | Otorhinolaryngology clinic | Otorhinolaryngology clinic
FMC | Family medicine clinic | Family medicine clinic
GI | Gastroenterology clinic | Gastroenterology clinic
PEDGI | Pediatric gastroenterology clinic | Pediatric gastroenterology clinic
GIM | General internal medicine clinic | General internal medicine clinic
GYN | Gynecology clinic | Gynecology clinic
HEM | Hematology clinic | Hematology clinic
PEDHEM | Pediatric hematology clinic | Pediatric hematology clinic
HTN | Hypertension clinic | Hypertension clinic
IEC | Impairment evaluation center | Focuses on assessing disability
INFD | Infectious disease clinic | Infectious disease clinic
PEDID | Pediatric infectious disease clinic | Pediatric infectious disease clinic
INV | Infertility clinic | Infertility clinic
LYMPH | Lympedema clinic | Lympedema clinic
MGEN | Medical genetics clinic | Medical genetics clinic
NEPH | Nephrology clinic | Nephrology clinic
PEDNEPH | Pediatric nephrology clinic | Pediatric nephrology clinic
NEUR | Neurology clinic | Neurology clinic
OB | Obstetrics clinic | Obstetrics clinic
OMS | Oral and maxillofacial surgery clinic | Oral and maxillofacial surgery clinic
ONCL | Medical oncology clinic | Medical oncology clinic
PEDHO | Pediatric oncology clinic | Pediatric oncology clinic
OPH | Opthalmology clinic | Opthalmology clinic
OPTC | optometry clinic | Description: A location that plays the role of delivering services which may include examination, diagnosis, treatment, management, and prevention of diseases and disorders of the eye as well as prescribing and fitting appropriate corrective lenses (glasses or contact lenses) as needed. Optometry clinics may also provide tests for visual field screening, measuring intra-ocular pressure and ophthalmoscopy, as and when required.
ORTHO | Orthopedics clinic | Orthopedics clinic
HAND | Hand clinic | Hand clinic
PAINCL | Pain clinic | (X12N 261QP3300N)
PC | Primary care clinic | (X12N 261QP2300N)
PEDC | Pediatrics clinic | Pediatrics clinic
PEDRHEUM | Pediatric rheumatology clinic | Pediatric rheumatology clinic
POD | Podiatry clinic | (X12N 261QP1100N)
PREV | Preventive medicine clinic | Preventive medicine clinic
PROCTO | Proctology clinic | Proctology clinic
PROFF | Provider's Office | Location where healthcare service was delivered, identified as the healthcare provider's practice office.
PROS | Prosthodontics clinic | Prosthodontics clinic
PSI | Psychology clinic | Psychology clinic
PSY | Psychiatry clinic | Psychiatry clinic
RHEUM | Rheumatology clinic | Rheumatology clinic
SPMED | Sports medicine clinic | Sports medicine clinic
SU | Surgery clinic | Surgery clinic
PLS | Plastic surgery clinic | Plastic surgery clinic
URO | Urology clinic | Urology clinic
TR | Transplant clinic | Transplant clinic
TRAVEL | Travel and geographic medicine clinic | Travel and geographic medicine clinic
WND | Wound clinic | Wound clinic

RTF | Residential treatment facility | Residential treatment facility
PRC | Pain rehabilitation center | Pain rehabilitation center
SURF | Substance use rehabilitation facility | (X12N 324500000N)
DADDR | Delivery Address | Location address where medical supplies were transported to for use.
MOBL | Mobile Unit | Location (mobile) where healthcare service was delivered.
AMB | Ambulance | Location (mobile) where healthcare service was delivered, identified specifically as an ambulance.
PHARM | Pharmacy | Location where healthcare service was delivered, identified as a pharmacy.
ACC | accident site | Location of an accident where healthcare service was delivered, such as a roadside.
COMM | Community Location | Community location where healthcare is delivered.
CSC | community service center | Description: A location that plays the role of delivering services which may include providing front-line services to the population of a defined geographic area such as: healthcare services and social services, preventive or curative, rehabilitation or reintegration.
PTRES | Patient's Residence | location where healthcare was delivered which is the residence of the Patient.
SCHOOL | school | Location where healthcare service was delivered, identified as a school or educational facility.
UPC | underage protection center | Description: A location that plays the role of delivering services which may include: social emergency services required for a young person as required under any jurisdictional youth laws, child placement, and family mediation in the defined geographical area the SDL is responsible for. It may provide expertise in a judiciary setting on child custody, adoption and biological history research.
WORK | work site | Location where healthcare service was delivered, identified as a work place.

4.3.2.17893 HL7 v3 Value Set ActClassROI

URL: https://hl7.org/fhir/STU3/v3/ActClassROI/vs.html

This page is part of the FHIR Specification (v3.0.2: STU 3). The current version which supercedes this version is 4.0.1. For a full list of available versions, see the Directory of published versions

Vocabulary Work Group | Maturity Level: N/A | External | Use Context: Any

This value set (http://hl7.org/fhir/ValueSet/v3-ActClassROI) is defined as part of HL7 v3. Related FHIR content: ActClassROI.

Summary

Defining URL: | http://hl7.org/fhir/ValueSet/v3-ActClassROI
Name: | ActClassROI
Definition: | Regions of Interest (ROI) within a subject Act. Primarily used for making secondary observations on a subset of a subject observation. The relationship between a ROI and its referenced Act is specified through an ActRelationship of type "subject" (SUBJ), which must always be present.
OID: | 2.16.840.1.113883.1.11.17893 (for OID based terminology systems)
Source Resource | XML / JSON

This value set is not currently used

4.3.2.17893.1 Content Logical Definition

This value set includes codes from the following code systems:

* Include codes from http://hl7.org/fhir/v3/ActClass where concept is-a _ActClassROI

* Exclude these codes as defined in

http://hl7.org/fhir/v3/ActClass

Code | Display
_ActClassROI | ActClassROI | Regions of Interest (ROI) within a subject Act. Primarily used for making secondary observations on a subset of a subject observation. The relationship between a ROI and its referenced Act is specified through an ActRelationship of type "subject" (SUBJ), which must always be present.

4.3.2.17893.2 Expansion

This expansion generated 19 Apr 2017

This value set contains 2 concepts

Expansion based on http://hl7.org/fhir/v3/ActClass version 2016-11-11

All codes from system http://hl7.org/fhir/v3/ActClass

Code | Display | Definition
ROIBND | bounded ROI | A Region of Interest (ROI) specified for a multidimensional observation, such as an Observation Series (OBSSER). The ROI is specified using a set of observation criteria, each delineating the boundary of the region in one of the dimensions in the multidimensional observation. The relationship between a ROI and its referenced Act is specified through an ActRelationship of type subject (SUBJ), which must always be present. Each of the boundary criteria observations is connected with the ROI using ActRelationships of type "has component" (COMP). In each boundary criterion, the Act.code names the dimension and the Observation.value specifies the range of values inside the region. Typically the bounded dimension is continuous, and so the Observation.value will be an interval (IVL) data type. The Observation.value need not be specified if the respective dimension is only named but not constrained. For example, an ROI for the QT interval of a certain beat in ECG Lead II would contain 2 boundary criteria, one naming the interval in time (constrained), and the other naming the interval in ECG Lead II (only named, but not constrained).
ROIOVL | overlay ROI | A Region of Interest (ROI) specified for an image using an overlay shape. Typically used to make reference to specific regions in images, e.g., to specify the location of a radiologic finding in an image or to specify the site of a physical finding by "circling" a region in a schematic picture of a human body. The units of the coordinate values are in pixels. The origin is in the upper left hand corner, with positive X values going to the right and positive Y values going down. The relationship between a ROI and its referenced Act is specified through an ActRelationship of type "subject" (SUBJ), which must always be present.

4.3.2.18938 HL7 v3 Value Set ActClassDocument

URL: https://hl7.org/fhir/STU3/v3/ActClassDocument/vs.html

This page is part of the FHIR Specification (v3.0.2: STU 3). The current version which supercedes this version is 4.0.1. For a full list of available versions, see the Directory of published versions

Vocabulary Work Group | Maturity Level: N/A | External | Use Context: Any

This value set (http://hl7.org/fhir/ValueSet/v3-ActClassDocument) is defined as part of HL7 v3. Related FHIR content: ActClassDocument.

Summary

Defining URL: | http://hl7.org/fhir/ValueSet/v3-ActClassDocument
Name: | ActClassDocument
Definition: | Specialization of Act to add the characteristics unique to document management services.
OID: | 2.16.840.1.113883.1.11.18938 (for OID based terminology systems)
Source Resource | XML / JSON

This value set is not currently used

4.3.2.18938.1 Content Logical Definition

This value set includes codes from the following code systems:

* Include codes from http://hl7.org/fhir/v3/ActClass where concept is-a DOC

4.3.2.18938.2 Expansion

This expansion generated 19 Apr 2017

This value set contains 3 concepts

Expansion based on http://hl7.org/fhir/v3/ActClass version 2016-11-11

All codes from system http://hl7.org/fhir/v3/ActClass

Code | Display | Definition
DOC | document | The notion of a document comes particularly from the paper world, where it corresponds to the contents recorded on discrete pieces of paper. In the electronic world, a document is a kind of composition that bears resemblance to their paper world counter-parts. Documents typically are meant to be human-readable. HL7's notion of document differs from that described in the W3C XML Recommendation, in which a document refers specifically to the contents that fall between the root element's start-tag and end-tag. Not all XML documents are HL7 documents.
DOCCLIN | clinical document | A clinical document is a documentation of clinical observations and services, with the following characteristics: Persistence - A clinical document continues to exist in an unaltered state, for a time period defined by local and regulatory requirements; Stewardship - A clinical document is maintained by a person or organization entrusted with its care; Potential for authentication - A clinical document is an assemblage of information that is intended to be legally authenticated; Wholeness - Authentication of a clinical document applies to the whole and does not apply to portions of the document without the full context of the document; Human readability - A clinical document is human readable.
CDALVLONE | CDA Level One clinical document | A clinical document that conforms to Level One of the HL7 Clinical Document Architecture (CDA)

4.3.2.18977 HL7 v3 Value Set ActRelationshipConditional

URL: https://hl7.org/fhir/STU3/v3/ActRelationshipConditional/vs.html

This page is part of the FHIR Specification (v3.0.2: STU 3). The current version which supercedes this version is 4.0.1. For a full list of available versions, see the Directory of published versions

Vocabulary Work Group | Maturity Level: N/A | External | Use Context: Any

This value set (http://hl7.org/fhir/ValueSet/v3-ActRelationshipConditional) is defined as part of HL7 v3. Related FHIR content: ActRelationshipConditional.

Summary

Defining URL: | http://hl7.org/fhir/ValueSet/v3-ActRelationshipConditional
Name: | ActRelationshipConditional
Definition: | Specifies under what circumstances (target Act) the source-Act may, must, must not or has occurred
OID: | 2.16.840.1.113883.1.11.18977 (for OID based terminology systems)
Source Resource | XML / JSON

This value set is not currently used

4.3.2.18977.1 Content Logical Definition

This value set includes codes from the following code systems:

* Include codes from http://hl7.org/fhir/v3/ActRelationshipType where concept is-a _ActRelationshipConditional

* Exclude these codes as defined in

http://hl7.org/fhir/v3/ActRelationshipType

Code | Display
_ActRelationshipConditional | ActRelationshipConditional | Specifies under what circumstances (target Act) the source-Act may, must, must not or has occurred

4.3.2.18977.2 Expansion

This expansion generated 19 Apr 2017

This value set contains 17 concepts

Expansion based on http://hl7.org/fhir/v3/ActRelationshipType version 2016-11-11

All codes from system http://hl7.org/fhir/v3/ActRelationshipType

Code | Display | Definition

CIND | has contra-indication | A contraindication is just a negation of a reason, i.e. it gives a condition under which the action is not to be done. Both, source and target can be any kind of service; target service is in criterion mood. How the strength of a contraindication is expressed (e.g., relative, absolute) is left as an open issue. The priorityNumber attribute could be used.

PRCN | has pre-condition | A requirement to be true before a service is performed. The target can be any service in criterion mood. For multiple pre-conditions a conjunction attribute (AND, OR, XOR) is applicable.

RSON | has reason | Description: The reason or rationale for a service. A reason link is weaker than a trigger, it only suggests that some service may be or might have been a reason for some action, but not that this reason requires/required the action to be taken. Also, as opposed to the trigger, there is no strong timely relation between the reason and the action. As well as providing various types of information about the rationale for a service, the RSON act relationship is routinely used between a SBADM act and an OBS act to describe the indication for use of a medication. Child concepts may be used to describe types of indication. Discussion: In prior releases, the code "SUGG" (suggests) was expressed as "an inversion of the reason link." That code has been retired in favor of the inversion indicator that is an attribute of ActRelationship.

BLOCK | blocks | Definition: The source act is performed to block the effects of the target act. This act relationship should be used when describing near miss type incidents where potential harm could have occurred, but the action described in the source act blocked the potential harmful effects of the incident actually occurring.

DIAG | diagnoses | Description: The source act is intended to help establish the presence of a (an adverse) situation described by the target act. This is not limited to diseases but can apply to any adverse situation or condition of medical or technical nature.

IMM | immunization against | Description: The source act is intented to provide immunity against the effects of the target act (the target act describes an infectious disease)

ACTIMM | active immunization against | Description: The source act is intended to provide active immunity against the effects of the target act (the target act describes an infectious disease)

PASSIMM | passive immunization against | Description: The source act is intended to provide passive immunity against the effects of the target act (the target act describes an infectious disease).

MITGT | mitigates | The source act removes or lessens the occurrence or effect of the target act.

RCVY | recovers | Definition: The source act is performed to recover from the effects of the target act.

PRYLX | prophylaxis of | Description: The source act is intended to reduce the risk of of an adverse situation to emerge as described by the target act. This is not limited to diseases but can apply to any adverse situation or condition of medical or technical nature.

TREAT | treats | Description: The source act is intended to improve a pre-existing adverse situation described by the target act. This is not limited to diseases but can apply to any adverse situation or condition of medical or technical nature.

ADJUNCT | adjunctive treatment | Description: The source act is intended to offer an additional treatment for the management or cure of a pre-existing adverse situation described by the target act. This is not limited to diseases but can apply to any adverse situation or condition of medical or technical nature. It is not a requirement that the non-adjunctive treatment is explicitly specified.

MTREAT | maintenance treatment | Description: The source act is intended to provide long term maintenance improvement or management of a pre-existing adverse situation described by the target act. This is not limited to diseases but can apply to any adverse situation or condition of medical or technical nature.

PALLTREAT | palliates | Description: The source act is intended to provide palliation for the effects of the target act.

SYMP | symptomatic relief | Description: The source act is intented to provide symptomatic relief for the effects of the target act.

TRIG | has trigger | A pre-condition that if true should result in the source Act being executed. The target is in typically in criterion mood. When reported after the fact (i.e. the criterion has been met) it may be in Event mood. A delay between the trigger and the triggered action can be specified. Discussion: This includes the concept of a required act for a service or financial instrument such as an insurance plan or policy. In such cases, the trigger is the occurrence of a specific condition such as coverage limits being exceeded.

4.3.2.19032 HL7 v3 Value Set ParticipationIndirectTarget

URL: https://hl7.org/fhir/STU3/v3/ParticipationIndirectTarget/vs.html

This page is part of the FHIR Specification (v3.0.2: STU 3). The current version which supercedes this version is 4.0.1. For a full list of available versions, see the Directory of published versions

Vocabulary Work Group | Maturity Level: N/A | External | Use Context: Any

This value set (http://hl7.org/fhir/ValueSet/v3-ParticipationIndirectTarget) is defined as part of HL7 v3. Related FHIR content: ParticipationIndirectTarget.

Summary

Defining URL: | http://hl7.org/fhir/ValueSet/v3-ParticipationIndirectTarget

Name: | ParticipationIndirectTarget

Definition: | Target that is not substantially present in the act and which is not directly affected by the act, but which will be a focus of the record or documentation of the act.

OID: | 2.16.840.1.113883.1.11.19032 (for OID based terminology systems)

Source Resource | XML / JSON

This value set is not currently used

4.3.2.19032.1 Content Logical Definition

This value set includes codes from the following code systems:

* Include codes from http://hl7.org/fhir/v3/ParticipationType where concept is-a IND

4.3.2.19032.2 Expansion

This expansion generated 19 Apr 2017

This value set contains 8 concepts

Expansion based on http://hl7.org/fhir/v3/ParticipationType version 2016-11-11

All codes from system http://hl7.org/fhir/v3/ParticipationType

Code | Display | Definition

IND | indirect target | Target that is not substantially present in the act and which is not directly affected by the act, but which will be a focus of the record or documentation of the act.

BEN | beneficiary | Target on behalf of whom the service happens, but that is not necessarily present in the service. Can occur together with direct target to indicate that a target is both, as in the case where the patient is the indirect beneficiary of a service rendered to a family member, e.g. counseling or given home care instructions. This concept includes a participant, such as a covered party, who derives benefits from a service act covered by a coverage act. Note that the semantic role of the intended recipient who benefits from the happening denoted by the verb in the clause. Thus, a patient who has no coverage under a policy or program may be a beneficiary of a health service while not being the beneficiary of coverage for that service.

CAGNT | causative agent | Definition: A factor, such as a microorganism, chemical substance, or form of radiation, whose presence, excessive presence, or (in deficiency diseases) relative absence is essential, in whole or in part, for the occurrence of a condition. Constraint: The use of this participation is limited to observations.

COV | coverage target | The target participation for an individual in a health care coverage act in which the target role is either the policy holder of the coverage, or a covered party under the coverage.

GUAR | guarantor party | The target person or organization contractually recognized by the issuer as a participant who has assumed fiscal responsibility for another personaTMs financial obligations by guaranteeing to pay for amounts owed to a particular account Example:The subscriber of the patientaTMs health insurance policy signs a contract with the provider to be fiscally responsible for the patient billing account balance amount owed.

HLD | holder | Participant who posses an instrument such as a financial contract (insurance policy) usually based on some agreement with the author.

RCT | record target | The record target indicates whose medical record holds the documentation of this act. This is especially important when the subject of a service is not the patient himself.

RCV | receiver | The person (or organization) who receives the product of an Act.

4.3.2.19105 HL7 v3 Value Set RoleClassPassive

URL: https://hl7.org/fhir/STU3/v3/RoleClassPassive/vs.html

This page is part of the FHIR Specification (v3.0.2: STU 3). The current version which supercedes this version is 4.0.1. For a full list of available versions, see the Directory of published versions

Vocabulary Work Group | Maturity Level: N/A | External | Use Context: Any

This value set (http://hl7.org/fhir/ValueSet/v3-RoleClassPassive) is defined as part of HL7 v3. Related FHIR content: RoleClassPassive.

Summary

Defining URL: | http://hl7.org/fhir/ValueSet/v3-RoleClassPassive

Name: | RoleClassPassive

Definition: | An association for a playing Entity that is used, known, treated, handled, built, or destroyed, etc. under the auspices of the scoping Entity. The playing Entity is passive in these roles (even though it may be active in other roles), in the sense that the kinds of things done to it in this role happen without an agreement from the playing Entity.

OID: | 2.16.840.1.113883.1.11.19105 (for OID based terminology systems)

Source Resource | XML / JSON

This value set is not currently used

4.3.2.19105.1 Content Logical Definition

This value set includes codes from the following code systems:

* Include codes from http://hl7.org/fhir/v3/RoleClass where concept is-a _RoleClassPassive

* Exclude these codes as defined in

http://hl7.org/fhir/v3/RoleClass

Code | Display

_RoleClassPassive | RoleClassPassive | An association for a playing Entity that is used, known, treated, handled, built, or destroyed, etc. under the auspices of the scoping Entity. The playing Entity is passive in these roles (even though it may be active in other roles), in the sense that the kinds of things done to it in this role happen without an agreement from the playing Entity.

4.3.2.19105.2 Expansion

This expansion generated 19 Apr 2017

This value set contains 26 concepts

Expansion based on http://hl7.org/fhir/v3/RoleClass version 2016-11-11

All codes from system http://hl7.org/fhir/v3/RoleClass

Code | Display | Definition

ACCESS | access | A role in which the playing entity (material) provides access to another entity. The principal use case is intravenous (or other bodily) access lines that preexist and need to be referred to for medication routing instructions.

ADJY | adjacency | A physical association whereby two Entities are in some (even lose) spatial relationship with each other such that they touch each other in some way. Examples: the colon is connected (and therefore adjacent) to the jejunum; the colon is adjacent to the liver (even if not actually connected.) UsageConstraints: Adjacency is in principle a symmetrical connection, but scoper and player of the role should, where applicable, be assigned to have scoper be the larger, more central Entity and player the smaller, more distant, appendage.

CONC | connection | An adjacency of two Entities held together by a bond which attaches to each of the two entities. Examples: biceps brachii muscle connected to the radius bone, port 3 on a network switch connected to port 5 on a patch panel. UsageConstraints: See Adjacency for the assignment of scoper (larger, more central) and player (smaller, more distant).

BOND | molecular bond | A connection between two atoms of a molecule. Examples: double bond between first and second C in ethane, peptide bond between two amino-acid, disulfide bridge between two proteins, chelate and ion associations, even the much weaker van-der-Waals bonds can be considered molecular bonds. UsageConstraints: See connection and adjacency for the assignment of player and scoper.

CONY | continuity | A connection between two regional parts. Examples: the connection between ascending aorta and the aortic arc, connection between descending colon and sigmoid. UsageConstraints: See connection and adjacency for the assignment of player and scoper.

ADMM | Administerable Material | A material (player) that can be administered to an Entity (scoper).

BIRTHPL | birthplace | Relates a place (playing Entity) as the location where a living subject (scoping Entity) was born.

DEATHPLC | place of death | Definition: Relates a place (playing Entity) as the location where a living subject (scoping Entity) died.

DST | distributed material | A material (player) distributed by a distributor (scoper) who functions between a manufacturer and a buyer or retailer.

RET | retailed material | Material (player) sold by a retailer (scoper), who also give advice to prospective buyers.

EXLOC | event location | A role played by a place at which the location of an event may be recorded.

SDLOC | service delivery location | A role played by a place at which services may be provided.

DSDLOC | dedicated service delivery location | A role of a place (player) that is intended to house the provision of services. Scoper is the Entity (typically Organization) that provides these services. This is not synonymous with "ownership."

ISDLOC | incidental service delivery location | A role played by a place at which health care services may be provided without prior designation or authorization.

EXPR | exposed entity | A role played by an entity that has been exposed to a person or animal suffering a contagious disease, or with a location from which a toxin has been distributed. The player of the role is normally a person or animal, but it is possible that other entity types could become exposed. The role is scoped by the source of the exposure, and it is quite possible for a person playing the role of exposed party to also become the scoper a role played by another person. That is to say, once a person has become infected, it is possible, perhaps likely, for that person to infect others. Management of exposures and tracking exposed parties is a key function within public health, and within most public health contexts - exposed parties are known as "contacts."

HLD | held entity | Entity that is currently in the possession of a holder (scoper), who holds, or uses it, usually based on some agreement with the owner.

HLTHCHRT | health chart | The role of a material (player) that is the physical health chart belonging to an organization (scoper).

IDENT | identified entity | A role in which the scoping entity designates an identifier for a playing entity.

MANU | manufactured product | Scoped by the manufacturer

THER | therapeutic agent | A manufactured material (player) that is used for its therapeutic properties. The manufacturer is the scoper.

MNT | maintained entity | An entity (player) that is maintained by another entity (scoper). This is typical role held by durable equipment. The scoper assumes responsibility for proper operation, quality, and safety.

OWN | owned entity | An Entity (player) for which someone (scoper) is granted by law the right to call the material (player) his own. This entitles the scoper to make decisions about the disposition of that material.

RGPR | regulated product | A product regulated by some governmentatl orgnization. The role is played by Material and scoped by Organization. Rationale: To support an entity clone used to identify the NDC number for a drug product.

TERR | territory of authority | Relates a place entity (player) as the region over which the scoper (typically an Organization) has certain authority (jurisdiction). For example, the Calgary Regional Health Authority (scoper) has authority over the territory "Region 4 of Alberta" (player) in matters of health.

USED | used entity | Description:An entity (player) that is used by another entity (scoper)

WRTE | warranted product | A role a product plays when a guarantee is given to the purchaser by the seller (scoping entity) stating that the product is reliable and free from known defects and that the seller will repair or replace defective parts within a given time limit and under certain conditions.

4.3.2.19313 HL7 v3 Value Set RoleClassAssociative

URL: https://hl7.org/fhir/STU3/v3/RoleClassAssociative/vs.html

This page is part of the FHIR Specification (v3.0.2: STU 3). The current version which supercedes this version is 4.0.1. For a full list of available versions, see the Directory of published versions

Vocabulary Work Group | Maturity Level: N/A | External | Use Context: Any

This value set (http://hl7.org/fhir/ValueSet/v3-RoleClassAssociative) is defined as part of HL7 v3. Related FHIR content: RoleClassAssociative.

Summary

Defining URL: | http://hl7.org/fhir/ValueSet/v3-RoleClassAssociative
Name: | RoleClassAssociative
Definition: | A general association between two entities that is neither partitive nor ontological.
OID: | 2.16.840.1.113883.1.11.19313 (for OID based terminology systems)
Source Resource | XML / JSON

This value set is not currently used

4.3.2.19313.1 Content Logical Definition

This value set includes codes from the following code systems:

* Include codes from http://hl7.org/fhir/v3/RoleClass where concept is-a _RoleClassAssociative

* Exclude these codes as defined in

http://hl7.org/fhir/v3/RoleClass

Code | Display
_RoleClassAssociative | RoleClassAssociative | A general association between two entities that is neither partitive nor ontological.

4.3.2.19313.2 Expansion

This expansion generated 19 Apr 2017

This value set contains 65 concepts

Expansion based on http://hl7.org/fhir/v3/RoleClass version 2016-11-11

All codes from system http://hl7.org/fhir/v3/RoleClass

Code | Display | Definition

AFFL | affiliate | Player of the Affiliate role has a business/professional relationship with scoper. Player and scoper may be persons or organization. The Affiliate relationship does not imply membership in a group, nor does it exist for resource scheduling purposes. Example: A healthcare provider is affiliated with another provider as a business associate.

AGNT | agent | An entity (player) that acts or is authorized to act on behalf of another entity (scoper).

ASSIGNED | assigned entity | An agent role in which the agent is an Entity acting in the employ of an organization. The focus is on functional role on behalf of the organization, unlike the Employee role where the focus is on the 'Human Resources' relationship between the employee and the organization.

COMPAR | commissioning party | An Entity that is authorized to issue or instantiate permissions, privileges, credentials or other formal/legal authorizations.

SGNOFF | signing authority or officer | The role of a person (player) who is the officer or signature authority for of a scoping entity, usually an organization (scoper).

CON | contact | A person or an organization (player) which provides or receives information regarding another entity (scoper). Examples; patient NOK and emergency contacts; guarantor contact; employer contact.

ECON | emergency contact | An entity to be contacted in the event of an emergency.

NOK | next of kin | An individual designated for notification as the next of kin for a given entity.

GUARD | guardian | Guardian of a ward

CIT | citizen | Citizen of apolitical entity

COVPTY | covered party | A role class played by a person who receives benefit coverage under the terms of a particular insurance policy. The underwriter of that policy is the scoping entity. The covered party receives coverage because of some contractual or other relationship with the holder of that policy. Discussion:This reason for coverage is captured in 'Role.code' and a relationship link with type code of indirect authority should be included using the policy holder role as the source, and the covered party role as the target. Note that a particular policy may cover several individuals one of whom may be, but need not be, the policy holder. Thus the notion of covered party is a role that is distinct from that of the policy holder.

CLAIM | claimant | Description: A role played by a party making a claim for coverage under a policy or program. A claimant must be either a person or organization, or a group of persons or organizations. A claimant is not a named insured or a program eligible. Discussion: With respect to liability insurance such as property and casualty insurance, a claimant must file a claim requesting indemnification for a loss that the claimant considers covered under the policy of a named insured. The claims adjuster for the policy underwriter will review the claim to determine whether the loss meets the benefit coverage criteria under a policy, and base any indemnification or coverage payment on that review. If a third party is liable in whole or part for the loss, the underwriter may pursue third party liability recovery. A claimant may be involved in civil or criminal legal proceedings involving claims against a defendant party that is indemnified by an insurance policy or to protest the finding of a claims adjustor. With respect to life insurance, a beneficiary designated by a named insured becomes a claimant of the proceeds of coverage, as in the case of a life insurance policy. However, a claimant for coverage under life insurance is not necessarily a designated beneficiary. Note: A claimant is not a named insured. However, a named insured may make a claim under a policy, e.g., an insured driver may make a claim for an injury under his or her comprehensive automobile insurance policy. Similarly, a program eligible may make a claim under program, e.g., an unemployed worker may claim benefits under an unemployment insurance program, but parties playing these covered party role classes are not, for purposes of this vocabulary and in an effort to clearly distinguish role classes, considered claimants. In the case of a named insured making a claim, a role type code INSCLM (insured claimant) subtypes the class to indicate that either a named insured or an individual insured has filed a claim for a loss. In the case of a program eligible, a role type code INJWKR (injured worker) subtypes the class to indicate that the covered party in a workers compensation program is an injured worker, and as such, has filed a "claim" under the program for benefits. Likewise, a covered role type code UNEMP (unemployed worker) subtypes the program eligible class to indicate that the covered party in an unemployment insurance program has filed a claim for unemployment benefits. Example: A claimant under automobile policy that is not the named insured.

NAMED | named insured | Description: A role played by a party to an insurance policy to which the insurer agrees to indemnify for losses, provides benefits for, or renders services. A named insured may be either a person, non-person living subject, or an organization, or a group of persons, non-person living subjects, or organizations. Discussion: The coded concept NAMED should not be used where a more specific child concept in this Specializable value set applies. In some cases, the named insured may not be the policy holder, e.g., where a policy holder purchases life insurance policy in which another party is the named insured and the policy holder is the beneficiary of the policy. Note: The party playing the role of a named insured is not a claimant in the sense conveyed by the RoleClassCoveredParty CLAIM (claimant). However, a named insured may make a claim under a policy, e.g., e.g., a party that is the named insured and policy holder under a comprehensive automobile insurance policy may become the claimant for coverage under that policy e.g., if injured in an automobile accident and there is no liable third party. In the case of a named insured making a claim, a role type code INSCLM (insured claimant) subtypes the class to indicate that a named insured has filed a claim for a loss. Example: The named insured under a comprehensive automobile, disability, or property and casualty policy that is the named insured and may or may not be the policy holder.

DEPEN | dependent | Description: A role played by a person covered under a policy or program based on an association with a subscriber, which is recognized by the policy holder. Note: The party playing the role of a dependent is not a claimant in the sense conveyed by the RoleClassCoveredParty CLAIM (claimant). However, a dependent may make a claim under a policy, e.g., a dependent under a health insurance policy may become the claimant for coverage under that policy for wellness examines or if injured and there is no liable third party. In the case of a dependent making a claim, a role type code INSCLM (insured claimant) subtypes the class to indicate that the dependent has filed a claim for services covered under the health insurance policy. Example: The dependent has an association with the subscriber such as a financial dependency or personal relationship such as that of a spouse, or a natural or adopted child. The policy holder may be required by law to recognize certain associations or may have discretion about the associations. For example, a policy holder may dictate the criteria for the dependent status of adult children who are students, such as requiring full time enrollment, or may recognize domestic partners as dependents. Under certain circumstances, the dependent may be under the indirect authority of a responsible party acting as a surrogate for the subscriber, for example, if the subscriber is differently abled or deceased, a guardian ad Lidem or estate executor may be appointed to assume the subscriberaTMs legal standing in the relationship with the dependent.

INDIV | individual | Description: A role played by a party covered under a policy as the policy holder. An individual may be either a person or an organization. Note: The party playing the role of an individual insured is not a claimant in the sense conveyed by the RoleClassCoveredParty CLAIM (claimant). However, a named insured may make a claim under a policy, e.g., a party that is the named insured and policy holder under a comprehensive automobile insurance policy may become the claimant for coverage under that policy if injured in an automobile accident and there is no liable third party. In the case of an individual insured making a claim, a role type code INSCLM (insured claimant) subtypes the class to indicate that an individual insured has filed a claim for a loss. Example: The individual insured under a comprehensive automobile, disability, or property and casualty policy that is the policy holder.

SUBSCR | subscriber | Description: A role played by a person covered under a policy based on association with a sponsor who is the policy holder, and whose association may provide for the eligibility of dependents for coverage. Discussion: The policy holder holds the contract with the policy or program underwriter. The subscriber holds a certificate of coverage under the contract. In legal proceedings concerning the policy or program, the terms of the contract takes precedence over the terms of the certificate of coverage if there are any inconsistencies. Note: The party playing the role of a subscriber is not a claimant in the sense conveyed by the RoleClassCoveredParty CLAIM (claimant). However, a subscriber may make a claim under a policy, e.g., a subscriber under a health insurance policy may become the claimant for coverage under that policy for wellness examines or if injured and there is no liable third party. In the case of a subscriber making a claim, a role type code INSCLM (insured claimant) subtypes the class to indicate that the subscriber has filed a claim for services covered under the health insurance policy. Example: An employee or a member of an association.

PROG | program eligible | Description: A role played by a party that meets the eligibility criteria for coverage under a program. A program eligible may be either a person, non-person living subject, or an organization, or a group of persons, non-person living subjects, or organizations. Discussion: A program as typically government administered coverage for parties determined eligible under the terms of the program. Note: The party playing a program eligible is not a claimant in the sense conveyed by the RoleClassCoveredParty CLAIM (claimant). However a program eligible may make a claim under program, e.g., an unemployed worker may claim benefits under an unemployment insurance program, but parties playing these covered party role classes are not, for purposes of this vocabulary and in an effort to clearly distinguish role classes, considered claimants. In the case of a program eligible, a role type code INJWKR (injured worker) subtypes the class to indicate that the covered party in a workers compensation program is an injured worker, and as such, has filed a "claim" under the program for benefits. Likewise, a covered role type code UNEMP (unemployed worker) subtypes the program eligible class to indicate that the covered party in an unemployment insurance program has filed a claim for unemployment benefits. Example: A party meeting eligibility criteria related to health or financial status, e.g., in the U.S., persons meeting health, demographic, or financial criteria established by state and federal law are eligible for Medicaid.

CRINV | clinical research investigator | A role played by a provider, always a person, who has agency authority from a Clinical Research Sponsor to direct the conduct of a clinical research trial or study on behalf of the sponsor.

CRSPNSR | clinical research sponsor | A role played by an entity, usually an organization, that is the sponsor of a clinical research trial or study. The sponsor commissions the study, bears the expenses, is responsible for satisfying all legal requirements concerning subject safety and privacy, and is generally responsible for collection, storage and analysis of the data generated during the trial. No scoper is necessary, as a clinical research sponsor undertakes the role on its own authority and declaration. Clinical research sponsors are usually educational or other research organizations, government agencies or biopharmaceutical companies.

EMP | employee | A relationship between a person or organization and a person or organization formed for the purpose of exchanging work for compensation. The purpose of the role is to identify the type of relationship the employee has to the employer, rather than the nature of the work actually performed. (Contrast with AssignedEntity.)

MIL | military person | A role played by a member of a military service. Scoper is the military service (e.g. Army, Navy, Air Force, etc.) or, more specifically, the unit (e.g. Company C, 3rd Battalion, 4th Division, etc.)

GUAR | guarantor | A person or organization (player) that serves as a financial guarantor for another person or organization (scoper).

INVSBJ | Investigation Subject | An entity that is the subject of an investigation. This role is scoped by the party responsible for the investigation.

CASEBJ | Case Subject | A person, non-person living subject, or place that is the subject of an investigation related to a notifiable condition (health circumstance that is reportable within the applicable public health jurisdiction)

RESBJ | research subject | Definition:Specifies the administrative functionality within a formal experimental design for which the ResearchSubject role was established. Examples: Screening - role is used for pre-enrollment evaluation portion of the design; enrolled - role is used for subjects admitted to the experimental portion of the design.

LIC | licensed entity | A relationship in which the scoper certifies the player (e. g. a medical care giver, a medical device or a provider organization) to perform certain activities that fall under the jurisdiction of the scoper (e.g., a health authority licensing healthcare providers, a medical quality authority certifying healthcare professionals).

NOT | notary public | notary public

PROV | healthcare provider | An Entity (player) that is authorized to provide health care services by some authorizing agency (scoper).

PAT | patient | A Role of a LivingSubject (player) as an actual or potential recipient of health care services from a healthcare provider organization (scoper). Usage Note: Communication about relationships between patients and specific healthcare practitioners (people) is not done via scoper. Instead this is generally done using the CareProvision act. This allows linkage between patient and a particular healthcare practitioner role and also allows description of the type of care involved in the relationship.

PAYEE | payee | The role of an organization or individual designated to receive payment for a claim against a particular coverage. The scoping entity is the organization that is the submitter of the invoice in question.

PAYOR | invoice payor | The role of an organization that undertakes to accept claims invoices, assess the coverage or payments due for those invoices and pay to the designated payees for those invoices. This role may be either the underwriter or a third-party organization authorized by the underwriter. The scoping entity is the organization that underwrites the claimed coverage.

POLHOLD | policy holder | A role played by a person or organization that holds an insurance policy. The underwriter of that policy is the scoping entity. Discussion:The identifier of the policy is captured in 'Role.id' when the Role is a policy holder. A particular policy may cover several individuals one of whom may be, but need not be, the policy holder. Thus the notion of covered party is a role that is distinct from that of the policy holder.

QUAL | qualified entity | An entity (player) that has been recognized as having certain training/experience or other characteristics that would make said entity an appropriate performer for a certain activity. The scoper is an organization that educates or qualifies entities.

SPNSR | coverage sponsor | A role played by an entity, usually an organization that is the sponsor of an insurance plan or a health program. A sponsor is the party that is ultimately accountable for the coverage by employment contract or by law. A sponsor can be an employer, union, government agency, or association. Fully insured sponsors establish the terms of the plan and contract with health insurance plans to assume the risk and to administer the plan. Self-insured sponsors delegate coverage administration, but not risk, to third-party administrators. Program sponsors designate services to be covered in accordance with statute. Program sponsors may administer the coverage themselves, delegate coverage administration, but not risk to third-party administrators, or contract with health insurance plans to assume the risk and administrator a program. Sponsors qualify individuals who may become a policy holder of the plan; where the sponsor is the policy holder, who may become a subscriber or a dependent to a policy under the plan; or where the sponsor is a government agency, who may become program eligibles under a program. The sponsor role may be further qualified by the SponsorRole.code. Entities playing the sponsor role may also play the role of a Coverage Administrator. Example: An employer, union, government agency, or association.

STD | student | A role played by an individual who is a student of a school, which is the scoping entity.

UNDWRT | underwriter | A role played by a person or an organization. It is the party that accepts fiscal responsibility for insurance plans and the policies created under those plans; administers and accepts fiscal responsibility for a program that provides coverage for services to eligible individuals; and/or has the responsibility to assess the merits of each risk and decide a suitable premium for accepting all or part of the risk. If played by an organization, this role may be further specified by an appropriate RoleCode. Example: A health insurer; Medicaid Program; Lloyd's of London

CAREGIVER | caregiver | A person responsible for the primary care of a patient at home.

PRS | personal relationship | Links two entities with classCode PSN (person) in a personal relationship. The character of the relationship must be defined by a PersonalRelationshipRoleType code. The player and scoper are determined by PersonalRelationshipRoleType code as well.

SELF | self | The "same" roleclass asserts an identity between playing and scoping entities: that they are in fact instances of the same entity and, in the case of discrepancies (e.g different DOB, gender), that one or both are in error. Usage: playing and scoping entities must have same classcode, but need not have identical attributes or values. Example: a provider registry maintains sets of conflicting demographic data for what is reported to be the same individual.

ACCESS | access | A role in which the playing entity (material) provides access to another entity. The principal use case is intravenous (or other bodily) access lines that preexist and need to be referred to for medication routing instructions.

ADJY | adjacency | A physical association whereby two Entities are in some (even lose) spatial relationship with each other such that they touch each other in some way. Examples: the colon is connected (and therefore adjacent) to the jejunum; the colon is adjacent to the liver (even if not actually connected.) UsageConstraints: Adjacency is in principle a symmetrical connection, but scoper and player of the role should, where applicable, be assigned to have scoper be the larger, more central Entity and player the smaller, more distant, appendage.

CONC | connection | An adjacency of two Entities held together by a bond which attaches to each of the two entities. Examples: biceps brachii muscle connected to the radius bone, port 3 on a network switch connected to port 5 on a patch panel. UsageConstraints: See Adjacency for the assignment of scoper (larger, more central) and player (smaller, more distant).

BOND | molecular bond | A connection between two atoms of a molecule. Examples: double bond between first and second C in ethane, peptide bond between two amino-acid, disulfide bridge between two proteins, chelate and ion associations, even the much weaker van-der-Waals bonds can be considered molecular bonds. UsageConstraints: See connection and adjacency for the assignment of player and scoper.

CONY | continuity | A connection between two regional parts. Examples: the connection between ascending aorta and the aortic arc, connection between descending colon and sigmoid. UsageConstraints: See connection and adjacency for the assignment of player and scoper.

ADMM | Administerable Material | A material (player) that can be administered to an Entity (scoper).

BIRTHPL | birthplace | Relates a place (playing Entity) as the location where a living subject (scoping Entity) was born.

DEATHPLC | place of death | Definition: Relates a place (playing Entity) as the location where a living subject (scoping Entity) died.

DST | distributed material | A material (player) distributed by a distributor (scoper) who functions between a manufacturer and a buyer or retailer.

RET | retailed material | Material (player) sold by a retailer (scoper), who also give advice to prospective buyers.

EXLOC | event location | A role played by a place at which the location of an event may be recorded.

SDLOC | service delivery location | A role played by a place at which services may be provided.

DSDLOC | dedicated service delivery location | A role of a place (player) that is intended to house the provision of services. Scoper is the Entity (typically Organization) that provides these services. This is not synonymous with "ownership."

ISDLOC | incidental service delivery location | A role played by a place at which health care services may be provided without prior designation or authorization.

EXPR | exposed entity | A role played by an entity that has been exposed to a person or animal suffering a contagious disease, or with a location from which a toxin has been distributed. The player of the role is normally a person or animal, but it is possible that other entity types could become exposed. The role is scoped by the source of the exposure, and it is quite possible for a person playing the role of exposed party to also become the scoper a role played by another person. That is to say, once a person has become infected, it is possible, perhaps likely, for that person to infect others. Management of exposures and tracking exposed parties is a key function within public health, and within most public health contexts - exposed parties are known as "contacts."

HLD | held entity | Entity that is currently in the possession of a holder (scoper), who holds, or uses it, usually based on some agreement with the owner.

HLTHCHRT | health chart | The role of a material (player) that is the physical health chart belonging to an organization (scoper).

IDENT | identified entity | A role in which the scoping entity designates an identifier for a playing entity.

MANU | manufactured product | Scoped by the manufacturer

THER | therapeutic agent | A manufactured material (player) that is used for its therapeutic properties. The manufacturer is the scoper.

MNT | maintained entity | An entity (player) that is maintained by another entity (scoper). This is typical role held by durable equipment. The scoper assumes responsibility for proper operation, quality, and safety.

OWN | owned entity | An Entity (player) for which someone (scoper) is granted by law the right to call the material (player) his own. This entitles the scoper to make decisions about the disposition of that material.

RGPR | regulated product | A product regulated by some governmentatl orgnization. The role is played by Material and scoped by Organization. Rationale: To support an entity clone used to identify the NDC number for a drug product.

TERR | territory of authority | Relates a place entity (player) as the region over which the scoper (typically an Organization) has certain authority (jurisdiction). For example, the Calgary Regional Health Authority (scoper) has authority over the territory "Region 4 of Alberta" (player) in matters of health.

USED | used entity | Description:An entity (player) that is used by another entity (scoper)

WRTE | warranted product | A role a product plays when a guarantee is given to the purchaser by the seller (scoping entity) stating that the product is reliable and free from known defects and that the seller will repair or replace defective parts within a given time limit and under certain conditions.

4.3.2.19316 HL7 v3 Value Set RoleClassMutualRelationship

URL: https://hl7.org/fhir/STU3/v3/RoleClassMutualRelationship/vs.html

This page is part of the FHIR Specification (v3.0.2: STU 3). The current version which supercedes this version is 4.0.1. For a full list of available versions, see the Directory of published versions

Vocabulary Work Group | Maturity Level: N/A | External | Use Context: Any

This value set (http://hl7.org/fhir/ValueSet/v3-RoleClassMutualRelationship) is defined as part of HL7 v3. Related FHIR content: RoleClassMutualRelationship.

Summary

Defining URL: | http://hl7.org/fhir/ValueSet/v3-RoleClassMutualRelationship

Name: | RoleClassMutualRelationship

Definition: | A relationship that is based on mutual behavior of the two Entities as being related. The basis of such relationship may be agreements (e.g., spouses, contract parties) or they may bede facto behavior (e.g. friends) or may be an incidental involvement with each other (e.g. parties over a dispute, siblings, children).

OID: | 2.16.840.1.113883.1.11.19316 (for OID based terminology systems)

Source Resource | XML / JSON

This value set is not currently used

4.3.2.19316.1 Content Logical Definition

This value set includes codes from the following code systems:

* Include codes from http://hl7.org/fhir/v3/RoleClass where concept is-a _RoleClassMutualRelationship

* Exclude these codes as defined in

http://hl7.org/fhir/v3/RoleClass

Code | Display

_RoleClassMutualRelationship | RoleClassMutualRelationship | A relationship that is based on mutual behavior of the two Entities as being related. The basis of such relationship may be agreements (e.g., spouses, contract parties) or they may be de facto behavior (e.g. friends) or may be an incidental involvement with each other (e.g. parties over a dispute, siblings, children).

4.3.2.19316.2 Expansion

This expansion generated 19 Apr 2017

This value set contains 39 concepts

Expansion based on http://hl7.org/fhir/v3/RoleClass version 2016-11-11

All codes from system http://hl7.org/fhir/v3/RoleClass

Code | Display | Definition

AFFL | affiliate | Player of the Affiliate role has a business/professional relationship with scoper. Player and scoper may be persons or organization. The Affiliate relationship does not imply membership in a group, nor does it exist for resource scheduling purposes. Example: A healthcare provider is affiliated with another provider as a business associate.

AGNT | agent | An entity (player) that acts or is authorized to act on behalf of another entity (scoper).

ASSIGNED | assigned entity | An agent role in which the agent is an Entity acting in the employ of an organization. The focus is on functional role on behalf of the organization, unlike the Employee role where the focus is on the 'Human Resources' relationship between the employee and the organization.

COMPAR | commissioning party | An Entity that is authorized to issue or instantiate permissions, privileges, credentials or other formal/legal authorizations.

SGNOFF | signing authority or officer | The role of a person (player) who is the officer or signature authority for of a scoping entity, usually an organization (scoper).

CON | contact | A person or an organization (player) which provides or receives information regarding another entity (scoper). Examples; patient NOK and emergency contacts; guarantor contact; employer contact.

ECON | emergency contact | An entity to be contacted in the event of an emergency.

NOK | next of kin | An individual designated for notification as the next of kin for a given entity.

GUARD | guardian | Guardian of a ward

CIT | citizen | Citizen of apolitical entity

COVPTY | covered party | A role class played by a person who receives benefit coverage under the terms of a particular insurance policy. The underwriter of that policy is the scoping entity. The covered party receives coverage because of some contractual or other relationship with the holder of that policy. Discussion:This reason for coverage is captured in 'Role.code' and a relationship link with type code of indirect authority should be included using the policy holder role as the source, and the covered party role as the target. Note that a particular policy may cover several individuals one of whom may be, but need not be, the policy holder. Thus the notion of covered party is a role that is distinct from that of the policy holder.

CLAIM | claimant | Description: A role played by a party making a claim for coverage under a policy or program. A claimant must be either a person or organization, or a group of persons or organizations. A claimant is not a named insured or a program eligible. Discussion: With respect to liability insurance such as property and casualty insurance, a claimant must file a claim requesting indemnification for a loss that the claimant considers covered under the policy of a named insured. The claims adjuster for the policy underwriter will review the claim to determine whether the loss meets the benefit coverage criteria under a policy, and base any indemnification or coverage payment on that review. If a third party is liable in whole or part for the loss, the underwriter may pursue third party liability recovery. A claimant may be involved in civil or criminal legal proceedings involving claims against a defendant party that is indemnified by an insurance policy or to protest the finding of a claims adjustor. With respect to life insurance, a beneficiary designated by a named insured becomes a claimant of the proceeds of coverage, as in the case of a life insurance policy. However, a claimant for coverage under life insurance is not necessarily a designated beneficiary. Note: A claimant is not a named insured. However, a named insured may make a claim under a policy, e.g., an insured driver may make a claim for an injury under his or her comprehensive automobile insurance policy. Similarly, a program eligible may make a claim under program, e.g., an unemployed worker may claim benefits under an unemployment insurance program, but parties playing these covered party role classes are not, for purposes of this vocabulary and in an effort to clearly distinguish role classes, considered claimants. In the case of a named insured making a claim, a role type code INSCLM (insured claimant) subtypes the class to indicate that either a named insured or an individual insured has filed a claim for a loss. In the case of a program eligible, a role type code INJWKR (injured worker) subtypes the class to indicate that the covered party in a workers compensation program is an injured worker, and as such, has filed a "claim" under the program for benefits. Likewise, a covered role type code UNEMP (unemployed worker) subtypes the program eligible class to indicate that the covered party in an unemployment insurance program has filed a claim for unemployment benefits. Example: A claimant under automobile policy that is not the named insured.

NAMED | named insured | Description: A role played by a party to an insurance policy to which the insurer agrees to indemnify for losses, provides benefits for, or renders services. A named insured may be either a person, non-person living subject, or an organization, or a group of persons, non-person living subjects, or organizations. Discussion: The coded concept NAMED should not be used where a more specific child concept in this Specializable value set applies. In some cases, the named insured may not be the policy holder, e.g., where a policy holder purchases life insurance policy in which another party is the named insured and the policy holder is the beneficiary of the policy. Note: The party playing the role of a named insured is not a claimant in the sense conveyed by the RoleClassCoveredParty CLAIM (claimant). However, a named insured may make a claim under a policy, e.g., e.g., a party that is the named insured and policy holder under a comprehensive automobile insurance policy may become the claimant for coverage under that policy e.g., if injured in an automobile accident and there is no liable third party. In the case of a named insured making a claim, a role type code INSCLM (insured claimant) subtypes the class to indicate that a named insured has filed a claim for a loss. Example: The named insured under a comprehensive automobile, disability, or property and casualty policy that is the named insured and may or may not be the policy holder.

DEPEN | dependent | Description: A role played by a person covered under a policy or program based on an association with a subscriber, which is recognized by the policy holder. Note: The party playing the role of a dependent is not a claimant in the sense conveyed by the RoleClassCoveredParty CLAIM (claimant). However, a dependent may make a claim under a policy, e.g., a dependent under a health insurance policy may become the claimant for coverage under that policy for wellness examines or if injured and there is no liable third party. In the case of a

dependent making a claim, a role type code INSCLM (insured claimant) subtypes the class to indicate that the dependent has filed a claim for services covered under the health insurance policy. Example: The dependent has an association with the subscriber such as a financial dependency or personal relationship such as that of a spouse, or a natural or adopted child. The policy holder may be required by law to recognize certain associations or may have discretion about the associations. For example, a policy holder may dictate the criteria for the dependent status of adult children who are students, such as requiring full time enrollment, or may recognize domestic partners as dependents. Under certain circumstances, the dependent may be under the indirect authority of a responsible party acting as a surrogate for the subscriber, for example, if the subscriber is differently abled or deceased, a guardian ad Lidem or estate executor may be appointed to assume the subscriberaTMs legal standing in the relationship with the dependent.

INDIV | individual | Description: A role played by a party covered under a policy as the policy holder. An individual may be either a person or an organization. Note: The party playing the role of an individual insured is not a claimant in the sense conveyed by the RoleClassCoveredParty CLAIM (claimant). However, a named insured may make a claim under a policy, e.g., a party that is the named insured and policy holder under a comprehensive automobile insurance policy may become the claimant for coverage under that policy if injured in an automobile accident and there is no liable third party. In the case of an individual insured making a claim, a role type code INSCLM (insured claimant) subtypes the class to indicate that an individual insured has filed a claim for a loss. Example: The individual insured under a comprehensive automobile, disability, or property and casualty policy that is the policy holder.

SUBSCR | subscriber | Description: A role played by a person covered under a policy based on association with a sponsor who is the policy holder, and whose association may provide for the eligibility of dependents for coverage. Discussion: The policy holder holds the contract with the policy or program underwriter. The subscriber holds a certificate of coverage under the contract. In legal proceedings concerning the policy or program, the terms of the contract takes precedence over the terms of the certificate of coverage if there are any inconsistencies. Note: The party playing the role of a subscriber is not a claimant in the sense conveyed by the RoleClassCoveredParty CLAIM (claimant). However, a subscriber may make a claim under a policy, e.g., a subscriber under a health insurance policy may become the claimant for coverage under that policy for wellness examines or if injured and there is no liable third party. In the case of a subscriber making a claim, a role type code INSCLM (insured claimant) subtypes the class to indicate that the subscriber has filed a claim for services covered under the health insurance policy. Example: An employee or a member of an association.

PROG | program eligible | Description: A role played by a party that meets the eligibility criteria for coverage under a program. A program eligible may be either a person, non-person living subject, or an organization, or a group of persons, non-person living subjects, or organizations. Discussion: A program as typically government administered coverage for parties determined eligible under the terms of the program. Note: The party playing a program eligible is not a claimant in the sense conveyed by the RoleClassCoveredParty CLAIM (claimant). However a program eligible may make a claim under program, e.g., an unemployed worker may claim benefits under an unemployment insurance program, but parties playing these covered party role classes are not, for purposes of this vocabulary and in an effort to clearly distinguish role classes, considered claimants. In the case of a program eligible, a role type code INJWKR (injured worker) subtypes the class to indicate that the covered party in a workers compensation program is an injured worker, and as such, has filed a "claim" under the program for benefits. Likewise, a covered role type code UNEMP (unemployed worker) subtypes the program eligible class to indicate that the covered party in an unemployment insurance program has filed a claim for unemployment benefits. Example: A party meeting eligibility criteria related to health or financial status, e.g., in the U.S., persons meeting health, demographic, or financial criteria established by state and federal law are eligible for Medicaid.

CRINV | clinical research investigator | A role played by a provider, always a person, who has agency authority from a Clinical Research Sponsor to direct the conduct of a clinical research trial or study on behalf of the sponsor.

CRSPNSR | clinical research sponsor | A role played by an entity, usually an organization, that is the sponsor of a clinical research trial or study. The sponsor commissions the study, bears the expenses, is responsible for satisfying all legal requirements concerning subject safety and privacy, and is generally responsible for collection, storage and analysis of the data generated during the trial. No scoper is necessary, as a clinical research sponsor undertakes the role on its own authority and declaration. Clinical research sponsors are usually educational or other research organizations, government agencies or biopharmaceutical companies.

EMP | employee | A relationship between a person or organization and a person or organization formed for the purpose of exchanging work for compensation. The purpose of the role is to identify the type of relationship the employee has to the employer, rather than the nature of the work actually performed. (Contrast with AssignedEntity.)

MIL | military person | A role played by a member of a military service. Scoper is the military service (e.g. Army, Navy, Air Force, etc.) or, more specifically, the unit (e.g. Company C, 3rd Battalion, 4th Division, etc.)

GUAR | guarantor | A person or organization (player) that serves as a financial guarantor for another person or organization (scoper).

INVSBJ | Investigation Subject | An entity that is the subject of an investigation. This role is scoped by the party responsible for the investigation.

CASEBJ | Case Subject | A person, non-person living subject, or place that is the subject of an investigation related to a notifiable condition (health circumstance that is reportable within the applicable public health jurisdiction)

RESBJ | research subject | Definition:Specifies the administrative functionality within a formal experimental design for which the ResearchSubject role was established. Examples: Screening - role is used for pre-enrollment evaluation portion of the design; enrolled - role is used for subjects admitted to the experimental portion of the design.

LIC | licensed entity | A relationship in which the scoper certifies the player (e. g. a medical care giver, a medical device or a provider organization) to perform certain activities that fall under the jurisdiction of the scoper (e.g., a health authority licensing healthcare providers, a medical quality authority certifying healthcare professionals).

NOT | notary public | notary public

PROV | healthcare provider | An Entity (player) that is authorized to provide health care services by some authorizing agency (scoper).

PAT | patient | A Role of a LivingSubject (player) as an actual or potential recipient of health care services from a healthcare provider organization (scoper). Usage Note: Communication about relationships between patients and specific healthcare practitioners (people) is not done via scoper. Instead this is generally done using the CareProvision act. This allows linkage between patient and a particular healthcare practitioner role and also allows description of the type of care involved in the relationship.

PAYEE | payee | The role of an organization or individual designated to receive payment for a claim against a particular coverage. The scoping entity is the organization that is the submitter of the invoice in question.

PAYOR | invoice payor | The role of an organization that undertakes to accept claims invoices, assess the coverage or payments due for those invoices and pay to the designated payees for those invoices. This role may be either the underwriter or a third-party organization authorized by the underwriter. The scoping entity is the organization that underwrites the claimed coverage.

POLHOLD | policy holder | A role played by a person or organization that holds an insurance policy. The underwriter of that policy is the scoping entity. Discussion:The identifier of the policy is captured in 'Role.id' when the Role is a policy holder. A particular policy may cover several individuals one of whom may be, but need not be, the policy holder. Thus the notion of covered party is a role that is distinct from that of the policy holder.

QUAL | qualified entity | An entity (player) that has been recognized as having certain training/experience or other characteristics that would make said entity an appropriate performer for a certain activity. The scoper is an organization that educates or qualifies entities.

SPNSR | coverage sponsor | A role played by an entity, usually an organization that is the sponsor of an insurance plan or a health program. A sponsor is the party that is ultimately accountable for the coverage by employment contract or by law. A sponsor can be an employer, union, government agency, or association. Fully insured sponsors establish the terms of the plan and contract with health insurance plans to assume the risk and to administer the plan. Self-insured sponsors delegate coverage administration, but not risk, to third-party administrators. Program sponsors designate services to be covered in accordance with statute. Program sponsors may administer the coverage themselves, delegate coverage

administration, but not risk to third-party administrators, or contract with health insurance plans to assume the risk and administrator a program. Sponsors qualify individuals who may become a policy holder of the plan; where the sponsor is the policy holder, who may become a subscriber or a dependent to a policy under the plan; or where the sponsor is a government agency, who may become program eligibles under a program. The sponsor role may be further qualified by the SponsorRole.code. Entities playing the sponsor role may also play the role of a Coverage Administrator. Example: An employer, union, government agency, or association.

STD | student | A role played by an individual who is a student of a school, which is the scoping entity.

UNDWRT | underwriter | A role played by a person or an organization. It is the party that accepts fiscal responsibility for insurance plans and the policies created under those plans; administers and accepts fiscal responsibility for a program that provides coverage for services to eligible individuals; and/or has the responsibility to assess the merits of each risk and decide a suitable premium for accepting all or part of the risk. If played by an organization, this role may be further specified by an appropriate RoleCode. Example: A health insurer; Medicaid Program; Lloyd's of London

CAREGIVER | caregiver | A person responsible for the primary care of a patient at home.

PRS | personal relationship | Links two entities with classCode PSN (person) in a personal relationship. The character of the relationship must be defined by a PersonalRelationshipRoleType code. The player and scoper are determined by PersonalRelationshipRoleType code as well.

SELF | self | The "same" roleclass asserts an identity between playing and scoping entities: that they are in fact instances of the same entity and, in the case of discrepancies (e.g different DOB, gender), that one or both are in error. Usage: playing and scoping entities must have same classcode, but need not have identical attributes or values. Example: a provider registry maintains sets of conflicting demographic data for what is reported to be the same individual.

4.3.2.19377 HL7 v3 Value Set SubstanceAdminSubstitutionReason

URL: https://hl7.org/fhir/STU3/v3/SubstanceAdminSubstitutionReason/vs.html

This page is part of the FHIR Specification (v3.0.2: STU 3). The current version which supercedes this version is 4.0.1. For a full list of available versions, see the Directory of published versions

Vocabulary Work Group | Maturity Level: N/A | External | Use Context: Any

This value set (http://hl7.org/fhir/ValueSet/v3-SubstanceAdminSubstitutionReason) is defined as part of HL7 v3. Related FHIR content: SubstanceAdminSubstitutionReason.

Summary

Defining URL: | http://hl7.org/fhir/ValueSet/v3-SubstanceAdminSubstitutionReason
Name: | SubstanceAdminSubstitutionReason
Definition: | No Description Provided
OID: | 2.16.840.1.113883.1.11.19377 (for OID based terminology systems)
Source Resource | XML / JSON

This value set is used in the following places:

* MedicationRequest.substitution.reason (Example)

* MedicationDispense.substitution.reason (Example)

4.3.2.19377.1 Content Logical Definition

This value set includes codes from the following code systems:

* Include codes from http://hl7.org/fhir/v3/ActReason where concept is-a _SubstanceAdminSubstitutionReason

* Exclude these codes as defined in

http://hl7.org/fhir/v3/ActReason

Code | Display
_SubstanceAdminSubstitutionReason | SubstanceAdminSubstitutionReason | SubstanceAdminSubstitutionReason

4.3.2.19377.2 Expansion

This expansion generated 19 Apr 2017

This value set contains 4 concepts

Expansion based on http://hl7.org/fhir/v3/ActReason version 2016-11-11

All codes from system http://hl7.org/fhir/v3/ActReason

Code | Display | Definition

CT | continuing therapy | Indicates that the decision to substitute or to not substitute was driven by a desire to maintain consistency with a pre-existing therapy. I.e. The performer provided the same item/service as had been previously provided rather than providing exactly what was ordered, or rather than substituting with a lower-cost equivalent.

FP | formulary policy | Indicates that the decision to substitute or to not substitute was driven by a policy expressed within the formulary.

OS | out of stock | In the case of 'substitution', indicates that the substitution occurred because the ordered item was not in stock. In the case of 'no substitution', indicates that a cheaper equivalent was not substituted because it was not in stock.

RR | regulatory requirement | Indicates that the decision to substitute or to not substitute was driven by a jurisdictional regulatory requirement mandating or prohibiting substitution.

4.3.2.19398 HL7 v3 Value Set ActInvoiceGroupCode

URL: https://hl7.org/fhir/STU3/v3/ActInvoiceGroupCode/vs.html

This page is part of the FHIR Specification (v3.0.2: STU 3). The current version which supercedes this version is 4.0.1. For a full list of available versions, see the Directory of published versions

Vocabulary Work Group | Maturity Level: N/A | External | Use Context: Any

This value set (http://hl7.org/fhir/ValueSet/v3-ActInvoiceGroupCode) is defined as part of HL7 v3. Related FHIR content: ActInvoiceGroupCode.

Summary

Defining URL: | http://hl7.org/fhir/ValueSet/v3-ActInvoiceGroupCode
Name: | ActInvoiceGroupCode
Definition: | Type of invoice element that is used to assist in describing an Invoice that is either submitted for adjudication or for which is returned on adjudication results. Invoice elements of this type signify a grouping of one or more children (detail) invoice elements. They do not have intrinsic costing associated with them, but merely reflect the sum of all costing for it's immediate children invoice elements.
OID: | 2.16.840.1.113883.1.11.19398 (for OID based terminology systems)
Source Resource | XML / JSON

This value set is used in the following places:

* ExplanationOfBenefit.item.detail.type (Required)

* ExplanationOfBenefit.item.detail.subDetail.type (Required)

4.3.2.19398.1 Content Logical Definition

This value set includes codes from the following code systems:

* Include codes from http://hl7.org/fhir/v3/ActCode where concept is-a _ActInvoiceGroupCode

* Exclude these codes as defined in

http://hl7.org/fhir/v3/ActCode

Code | Display
_ActInvoiceGroupCode | ActInvoiceGroupCode | Type of invoice element that is used to assist in describing an Invoice that is either submitted for adjudication or for which is returned on adjudication results. Invoice elements of this type signify a grouping of one or more children (detail) invoice elements. They do not have intrinsic costing associated with them, but merely reflect the sum of all costing for it's immediate children invoice elements.

4.3.2.19398.2 Expansion

This expansion generated 19 Apr 2017

This value set contains 17 concepts

Expansion based on http://hl7.org/fhir/v3/ActCode version 2016-11-11

All codes from system http://hl7.org/fhir/v3/ActCode

Code | Display | Definition
CPNDDRGING | compound drug invoice group | A grouping of invoice element groups and details including the ones specifying the compound ingredients being invoiced. It may also contain generic detail items such as markup.
CPNDINDING | compound ingredient invoice group | A grouping of invoice element details including the one specifying an ingredient drug being invoiced. It may also contain generic detail items such as tax or markup.
CPNDSUPING | compound supply invoice group | A grouping of invoice element groups and details including the ones specifying the compound supplies being invoiced. It may also contain generic detail items such as markup.
DRUGING | drug invoice group | A grouping of invoice element details including the one specifying the drug being invoiced. It may also contain generic detail items such as markup.
FRAMEING | frame invoice group | A grouping of invoice element details including the ones specifying the frame fee and the frame dispensing cost that are being invoiced.
LENSING | lens invoice group | A grouping of invoice element details including the ones specifying the lens fee and the lens dispensing cost that are being invoiced.
PRDING | product invoice group | A grouping of invoice element details including the one specifying the product (good or supply) being invoiced. It may also contain generic detail items such as tax or discount.
CPINV | clinical product invoice | Clinical product invoice where the Invoice Grouping contains one or more billable item and is supported by clinical product(s). For example, a crutch or a wheelchair.
CSINV | clinical service invoice | Clinical Services Invoice which can be used to describe a single service, multiple services or repeated services. [1] Single Clinical services invoice where the Invoice Grouping contains one billable item and is supported by one clinical service. For example, a single service for an office visit or simple clinical procedure (e.g. knee mobilization). [2] Multiple Clinical services invoice where the Invoice Grouping contains more than one billable item, supported by one or more clinical services. The services can be distinct and over multiple dates, but for the same patient. This type of invoice includes a series of treatments which must be adjudicated together. For example, an adjustment and ultrasound for a chiropractic session where fees are associated for each of the services and adjudicated (invoiced) together. [3] Repeated Clinical services invoice where the Invoice Grouping contains one or more billable item, supported by the same clinical service repeated over a period of time. For example, the same Chiropractic adjustment (service or treatment) delivered on 3 separate occasions over a period of time at the discretion of the provider (e.g. month).
CSPINV | clinical service and product | A clinical Invoice Grouping consisting of one or more services and one or more product. Billing for these service(s) and product(s) are supported by multiple clinical billable events (acts). All items in the Invoice Grouping must be adjudicated together to be acceptable to the Adjudicator. For example , a brace (product) invoiced together with the fitting (service).
FININV | financial invoice | Invoice Grouping without clinical justification. These will not require identification of participants and associations from a clinical context such as patient and provider. Examples are interest charges and mileage.
OHSINV | oral health service | A clinical Invoice Grouping consisting of one or more oral health services. Billing for these service(s) are supported by multiple clinical billable events (acts). All items in the Invoice Grouping must be adjudicated together to be acceptable to the Adjudicator.
PAINV | preferred accommodation invoice | HealthCare facility preferred accommodation invoice.
RXCINV | Rx compound invoice | Pharmacy dispense invoice for a compound.
RXDINV | Rx dispense invoice | Pharmacy dispense invoice not involving a compound
SBFINV | sessional or block fee invoice | Clinical services invoice where the Invoice Group contains one billable item for multiple clinical services in one or more sessions.

VRXINV | vision dispense invoice | Vision dispense invoice for up to 2 lens (left and right), frame and optional discount. Eye exams are invoiced as a clinical service invoice.

4.3.2.19563 HL7 v3 Value Set PersonalRelationshipRoleType

URL: https://hl7.org/fhir/STU3/v3/PersonalRelationshipRoleType/vs.html

This page is part of the FHIR Specification (v3.0.2: STU 3). The current version which supercedes this version is 4.0.1. For a full list of available versions, see the Directory of published versions

Vocabulary Work Group | Maturity Level: N/A | External | Use Context: Any

This value set (http://hl7.org/fhir/ValueSet/v3-PersonalRelationshipRoleType) is defined as part of HL7 v3. Related FHIR content: PersonalRelationshipRoleType.

Summary

Defining URL: | http://hl7.org/fhir/ValueSet/v3-PersonalRelationshipRoleType
Name: | PersonalRelationshipRoleType
Definition: | Types of personal relationships between two living subjects. Example: Parent, sibling, unrelated friend, neighbor
OID: | 2.16.840.1.113883.1.11.19563 (for OID based terminology systems)
Source Resource | XML / JSON

This value set is not currently used

4.3.2.19563.1 Content Logical Definition

This value set includes codes from the following code systems:

* Include codes from http://hl7.org/fhir/v3/RoleCode where concept is-a _PersonalRelationshipRoleType

* Exclude these codes as defined in

http://hl7.org/fhir/v3/RoleCode

Code | Display
_PersonalRelationshipRoleType | PersonalRelationshipRoleType | PersonalRelationshipRoleType

4.3.2.19563.2 Expansion

This expansion generated 19 Apr 2017

This value set contains 109 concepts

Expansion based on http://hl7.org/fhir/v3/RoleCode version 2016-11-11

All codes from system http://hl7.org/fhir/v3/RoleCode

Code | Display | Definition
FAMMEMB | family member | A relationship between two people characterizing their "familial" relationship
CHILD | child | The player of the role is a child of the scoping entity.
CHLDADOPT | adopted child | The player of the role is a child taken into a family through legal means and raised by the scoping person (parent) as his or her own child.
DAUADOPT | adopted daughter | The player of the role is a female child taken into a family through legal means and raised by the scoping person (parent) as his or her own child.
SONADOPT | adopted son | The player of the role is a male child taken into a family through legal means and raised by the scoping person (parent) as his or her own child.
CHLDFOST | foster child | The player of the role is a child receiving parental care and nurture from the scoping person (parent) but not related to him or her through legal or blood ties.
DAUFOST | foster daughter | The player of the role is a female child receiving parental care and nurture from the scoping person (parent) but not related to him or her through legal or blood ties.
SONFOST | foster son | The player of the role is a male child receiving parental care and nurture from the scoping person (parent) but not related to him or her through legal or blood ties.
DAUC | daughter | Description: The player of the role is a female child (of any type) of scoping entity (parent)
DAU | natural daughter | The player of the role is a female offspring of the scoping entity (parent).
STPDAU | stepdaughter | The player of the role is a daughter of the scoping person's spouse by a previous union.
NCHILD | natural child | The player of the role is an offspring of the scoping entity as determined by birth.
SON | natural son | The player of the role is a male offspring of the scoping entity (parent).
SONC | son | Description: The player of the role is a male child (of any type) of scoping entity (parent)
STPSON | stepson | The player of the role is a son of the scoping person's spouse by a previous union.
STPCHLD | step child | The player of the role is a child of the scoping person's spouse by a previous union.
EXT | extended family member | Description: A family member not having an immediate genetic or legal relationship e.g. Aunt, cousin, great grandparent, grandchild, grandparent, niece, nephew or uncle.
AUNT | aunt | The player of the role is a sister of the scoping person's mother or father.
MAUNT | maternal aunt | Description:The player of the role is a biological sister of the scoping person's biological mother.
PAUNT | paternal aunt | Description:The player of the role is a biological sister of the scoping person's biological father.
COUSN | cousin | The player of the role is a relative of the scoping person descended from a common ancestor, such as a grandparent, by two or more steps in a diverging line.
MCOUSN | maternal cousin | Description:The player of the role is a biological relative of the scoping person descended from a common ancestor on the player's mother's side, such as a grandparent, by two or more steps in a diverging line.
PCOUSN | paternal cousin | Description:The player of the role is a biological relative of the scoping person descended from a common ancestor on the player's father's side, such as a grandparent, by two or more steps in a diverging line.

GGRPRN | great grandparent | The player of the role is a parent of the scoping person's grandparent.
GGRFTH | great grandfather | The player of the role is the father of the scoping person's grandparent.
MGGRFTH | maternal great-grandfather | Description:The player of the role is the biological father of the scoping person's biological mother's parent.
PGGRFTH | paternal great-grandfather | Description:The player of the role is the biological father of the scoping person's biological father's parent.
GGRMTH | great grandmother | The player of the role is the mother of the scoping person's grandparent.
MGGRMTH | maternal great-grandmother | Description:The player of the role is the biological mother of the scoping person's biological mother's parent.
PGGRMTH | paternal great-grandmother | Description:The player of the role is the biological mother of the scoping person's biological father's parent.
MGGRPRN | maternal great-grandparent | Description:The player of the role is a biological parent of the scoping person's biological mother's parent.
PGGRPRN | paternal great-grandparent | Description:The player of the role is a biological parent of the scoping person's biological father's parent.
GRNDCHILD | grandchild | The player of the role is a child of the scoping person's son or daughter.
GRNDDAU | granddaughter | The player of the role is a daughter of the scoping person's son or daughter.
GRNDSON | grandson | The player of the role is a son of the scoping person's son or daughter.
GRPRN | grandparent | The player of the role is a parent of the scoping person's mother or father.
GRFTH | grandfather | The player of the role is the father of the scoping person's mother or father.
MGRFTH | maternal grandfather | Description:The player of the role is the biological father of the scoping person's biological mother.
PGRFTH | paternal grandfather | Description:The player of the role is the biological father of the scoping person's biological father.
GRMTH | grandmother | The player of the role is the mother of the scoping person's mother or father.
MGRMTH | maternal grandmother | Description:The player of the role is the biological mother of the scoping person's biological mother.
PGRMTH | paternal grandmother | Description:The player of the role is the biological mother of the scoping person's biological father.
MGRPRN | maternal grandparent | Description:The player of the role is the biological parent of the scoping person's biological mother.
PGRPRN | paternal grandparent | Description:The player of the role is the biological parent of the scoping person's biological father.
INLAW | inlaw | A relationship between an individual and a member of their spousal partner's immediate family.
CHLDINLAW | child-in-law | The player of the role is the spouse of scoping person's child.
DAUINLAW | daughter in-law | The player of the role is the wife of scoping person's son.
SONINLAW | son in-law | The player of the role is the husband of scoping person's daughter.
PRNINLAW | parent in-law | The player of the role is the parent of scoping person's husband or wife.
FTHINLAW | father-in-law | The player of the role is the father of the scoping person's husband or wife.
MTHINLAW | mother-in-law | The player of the role is the mother of the scoping person's husband or wife.
SIBINLAW | sibling in-law | The player of the role is: (1) a sibling of the scoping person's spouse, or (2) the spouse of the scoping person's sibling, or (3) the spouse of a sibling of the scoping person's spouse.
BROINLAW | brother-in-law | The player of the role is: (1) a brother of the scoping person's spouse, or (2) the husband of the scoping person's sister, or (3) the husband of a sister of the scoping person's spouse.
SISINLAW | sister-in-law | The player of the role is: (1) a sister of the scoping person's spouse, or (2) the wife of the scoping person's brother, or (3) the wife of a brother of the scoping person's spouse.
NIENEPH | niece/nephew | The player of the role is a child of scoping person's brother or sister or of the brother or sister of the scoping person's spouse.
NEPHEW | nephew | The player of the role is a son of the scoping person's brother or sister or of the brother or sister of the scoping person's spouse.
NIECE | niece | The player of the role is a daughter of the scoping person's brother or sister or of the brother or sister of the scoping person's spouse.
UNCLE | uncle | The player of the role is a brother of the scoping person's mother or father.
MUNCLE | maternal uncle | Description:The player of the role is a biological brother of the scoping person's biological mother.
PUNCLE | paternal uncle | Description:The player of the role is a biological brother of the scoping person's biological father.
PRN | parent | The player of the role is one who begets, gives birth to, or nurtures and raises the scoping entity (child).
ADOPTP | adoptive parent | The player of the role (parent) has taken the scoper (child) into their family through legal means and raises them as his or her own child.
ADOPTF | adoptive father | The player of the role (father) is a male who has taken the scoper (child) into their family through legal means and raises them as his own child.
ADOPTM | adoptive mother | The player of the role (father) is a female who has taken the scoper (child) into their family through legal means and raises them as her own child.
FTH | father | The player of the role is a male who begets or raises or nurtures the scoping entity (child).
FTHFOST | foster father | The player of the role (parent) who is a male state-certified caregiver responsible for the scoper (child) who has been placed in the parent's care. The placement of the child is usually arranged through the government or a social-service agency, and temporary. The state, via a jurisdiction recognized child protection agency, stands as in loco parentis to the child, making all legal decisions while the foster parent is responsible for the day-to-day care of the specified child.
NFTH | natural father | The player of the role is a male who begets the scoping entity (child).
NFTHF | natural father of fetus | Indicates the biologic male parent of a fetus.
STPFTH | stepfather | The player of the role is the husband of scoping person's mother and not the scoping person's natural father.
MTH | mother | The player of the role is a female who conceives, gives birth to, or raises and nurtures the scoping entity (child).
GESTM | gestational mother | The player is a female whose womb carries the fetus of the scoper. Generally used when the gestational mother and natural mother are not the same.
MTHFOST | foster mother | The player of the role (parent) who is a female state-certified caregiver responsible for the scoper (child) who has been placed in the parent's care. The placement of the child is usually arranged through the government or a social-service agency, and temporary. The state, via a jurisdiction recognized child protection agency, stands as in loco parentis to the child, making all legal decisions while the foster parent is responsible for the day-to-day care of the specified child.
NMTH | natural mother | The player of the role is a female who conceives or gives birth to the scoping entity (child).
NMTHF | natural mother of fetus | The player is the biologic female parent of the scoping fetus.
STPMTH | stepmother | The player of the role is the wife of scoping person's father and not the scoping person's natural mother.
NPRN | natural parent | natural parent
PRNFOST | foster parent | The player of the role (parent) who is a state-certified caregiver responsible for the scoper (child) who has been placed in the parent's care. The placement of the child is usually arranged through the government or a social-service agency, and temporary. The state, via a jurisdiction recognized child protection agency, stands as in loco parentis to the child, making all legal decisions while the foster parent is responsible for the day-to-day care of the specified child.

STPPRN | step parent | The player of the role is the spouse of the scoping person's parent and not the scoping person's natural parent.
SIB | sibling | The player of the role shares one or both parents in common with the scoping entity.
BRO | brother | The player of the role is a male sharing one or both parents in common with the scoping entity.
HBRO | half-brother | The player of the role is a male related to the scoping entity by sharing only one biological parent.
NBRO | natural brother | The player of the role is a male having the same biological parents as the scoping entity.
TWINBRO | twin brother | The scoper was carried in the same womb as the male player and shares common biological parents.
FTWINBRO | fraternal twin brother | The scoper was carried in the same womb as the male player and shares common biological parents but is the product of a distinct egg/sperm pair.
ITWINBRO | identical twin brother | The male scoper is an offspring of the same egg-sperm pair as the male player.
STPBRO | stepbrother | The player of the role is a son of the scoping person's stepparent.
HSIB | half-sibling | The player of the role is related to the scoping entity by sharing only one biological parent.
HSIS | half-sister | The player of the role is a female related to the scoping entity by sharing only one biological parent.
NSIB | natural sibling | The player of the role has both biological parents in common with the scoping entity.
NSIS | natural sister | The player of the role is a female having the same biological parents as the scoping entity.
TWINSIS | twin sister | The scoper was carried in the same womb as the female player and shares common biological parents.
FTWINSIS | fraternal twin sister | The scoper was carried in the same womb as the female player and shares common biological parents but is the product of a distinct egg/sperm pair.
ITWINSIS | identical twin sister | The female scoper is an offspring of the same egg-sperm pair as the female player.
TWIN | twin | The scoper and player were carried in the same womb and shared common biological parents.
FTWIN | fraternal twin | The scoper and player were carried in the same womb and share common biological parents but are the product of distinct egg/sperm pairs.
ITWIN | identical twin | The scoper and player are offspring of the same egg-sperm pair.
SIS | sister | The player of the role is a female sharing one or both parents in common with the scoping entity.
STPSIS | stepsister | The player of the role is a daughter of the scoping person's stepparent.
STPSIB | step sibling | The player of the role is a child of the scoping person's stepparent.
SIGOTHR | significant other | A person who is important to one's well being; especially a spouse or one in a similar relationship. (The player is the one who is important)
DOMPART | domestic partner | The player of the role cohabits with the scoping person but is not the scoping person's spouse.
FMRSPS | former spouse | Player of the role was previously joined to the scoping person in marriage and this marriage is now dissolved and inactive. Usage Note: This is significant to indicate as some jurisdictions have different legal requirements for former spouse to access the patient's record, from a general friend.
SPS | spouse | The player of the role is a marriage partner of the scoping person.
HUSB | husband | The player of the role is a man joined to a woman (scoping person) in marriage.
WIFE | wife | The player of the role is a woman joined to a man (scoping person) in marriage.
FRND | unrelated friend | The player of the role is a person who is known, liked, and trusted by the scoping person.
NBOR | neighbor | The player of the role lives near or next to the scoping person.
ONESELF | self | The relationship that a person has with his or her self.
ROOM | Roommate | One who shares living quarters with the subject.

4.3.2.19579 HL7 v3 Value Set FamilyMember

URL: https://hl7.org/fhir/STU3/v3/FamilyMember/vs.html

This page is part of the FHIR Specification (v3.0.2: STU 3). The current version which supercedes this version is 4.0.1. For a full list of available versions, see the Directory of published versions

Vocabulary Work Group | Maturity Level: N/A | External | Use Context: Any

This value set (http://hl7.org/fhir/ValueSet/v3-FamilyMember) is defined as part of HL7 v3. Related FHIR content: FamilyMember.

Summary

Defining URL: | http://hl7.org/fhir/ValueSet/v3-FamilyMember
Name: | FamilyMember
Definition: | A relationship between two people characterizing their "familial" relationship
OID: | 2.16.840.1.113883.1.11.19579 (for OID based terminology systems)
Source Resource | XML / JSON

This value set is used in the following places:

* FamilyMemberHistory.relationship (Example)

* StructureDefinition FamilyMemberHistory-Genetic: FamilyMemberHistory.relationship ((Example))

4.3.2.19579.1 Content Logical Definition

This value set includes codes from the following code systems:

* Include codes from http://hl7.org/fhir/v3/RoleCode where concept is-a FAMMEMB

4.3.2.19579.2 Expansion

This expansion generated 19 Apr 2017

This value set contains 105 concepts

Expansion based on http://hl7.org/fhir/v3/RoleCode version 2016-11-11

All codes from system http://hl7.org/fhir/v3/RoleCode

Code | Display | Definition

FAMMEMB | family member | A relationship between two people characterizing their "familial" relationship

CHILD | child | The player of the role is a child of the scoping entity.

CHLDADOPT | adopted child | The player of the role is a child taken into a family through legal means and raised by the scoping person (parent) as his or her own child.

DAUADOPT | adopted daughter | The player of the role is a female child taken into a family through legal means and raised by the scoping person (parent) as his or her own child.

SONADOPT | adopted son | The player of the role is a male child taken into a family through legal means and raised by the scoping person (parent) as his or her own child.

CHLDFOST | foster child | The player of the role is a child receiving parental care and nurture from the scoping person (parent) but not related to him or her through legal or blood ties.

DAUFOST | foster daughter | The player of the role is a female child receiving parental care and nurture from the scoping person (parent) but not related to him or her through legal or blood ties.

SONFOST | foster son | The player of the role is a male child receiving parental care and nurture from the scoping person (parent) but not related to him or her through legal or blood ties.

DAUC | daughter | Description: The player of the role is a female child (of any type) of scoping entity (parent)

DAU | natural daughter | The player of the role is a female offspring of the scoping entity (parent).

STPDAU | stepdaughter | The player of the role is a daughter of the scoping person's spouse by a previous union.

NCHILD | natural child | The player of the role is an offspring of the scoping entity as determined by birth.

SON | natural son | The player of the role is a male offspring of the scoping entity (parent).

SONC | son | Description: The player of the role is a male child (of any type) of scoping entity (parent)

STPSON | stepson | The player of the role is a son of the scoping person's spouse by a previous union.

STPCHLD | step child | The player of the role is a child of the scoping person's spouse by a previous union.

EXT | extended family member | Description: A family member not having an immediate genetic or legal relationship e.g. Aunt, cousin, great grandparent, grandchild, grandparent, niece, nephew or uncle.

AUNT | aunt | The player of the role is a sister of the scoping person's mother or father.

MAUNT | maternal aunt | Description:The player of the role is a biological sister of the scoping person's biological mother.

PAUNT | paternal aunt | Description:The player of the role is a biological sister of the scoping person's biological father.

COUSN | cousin | The player of the role is a relative of the scoping person descended from a common ancestor, such as a grandparent, by two or more steps in a diverging line.

MCOUSN | maternal cousin | Description:The player of the role is a biological relative of the scoping person descended from a common ancestor on the player's mother's side, such as a grandparent, by two or more steps in a diverging line.

PCOUSN | paternal cousin | Description:The player of the role is a biological relative of the scoping person descended from a common ancestor on the player's father's side, such as a grandparent, by two or more steps in a diverging line.

GGRPRN | great grandparent | The player of the role is a parent of the scoping person's grandparent.

GGRFTH | great grandfather | The player of the role is the father of the scoping person's grandparent.

MGGRFTH | maternal great-grandfather | Description:The player of the role is the biological father of the scoping person's biological mother's parent.

PGGRFTH | paternal great-grandfather | Description:The player of the role is the biological father of the scoping person's biological father's parent.

GGRMTH | great grandmother | The player of the role is the mother of the scoping person's grandparent.

MGGRMTH | maternal great-grandmother | Description:The player of the role is the biological mother of the scoping person's biological mother's parent.

PGGRMTH | paternal great-grandmother | Description:The player of the role is the biological mother of the scoping person's biological father's parent.

MGGRPRN | maternal great-grandparent | Description:The player of the role is a biological parent of the scoping person's biological mother's parent.

PGGRPRN | paternal great-grandparent | Description:The player of the role is a biological parent of the scoping person's biological father's parent.

GRNDCHILD | grandchild | The player of the role is a child of the scoping person's son or daughter.

GRNDDAU | granddaughter | The player of the role is a daughter of the scoping person's son or daughter.

GRNDSON | grandson | The player of the role is a son of the scoping person's son or daughter.

GRPRN | grandparent | The player of the role is a parent of the scoping person's mother or father.

GRFTH | grandfather | The player of the role is the father of the scoping person's mother or father.

MGRFTH | maternal grandfather | Description:The player of the role is the biological father of the scoping person's biological mother.

PGRFTH | paternal grandfather | Description:The player of the role is the biological father of the scoping person's biological father.

GRMTH | grandmother | The player of the role is the mother of the scoping person's mother or father.

MGRMTH | maternal grandmother | Description:The player of the role is the biological mother of the scoping person's biological mother.

PGRMTH | paternal grandmother | Description:The player of the role is the biological mother of the scoping person's biological father.

MGRPRN | maternal grandparent | Description:The player of the role is the biological parent of the scoping person's biological mother.

PGRPRN | paternal grandparent | Description:The player of the role is the biological parent of the scoping person's biological father.

INLAW | inlaw | A relationship between an individual and a member of their spousal partner's immediate family.

CHLDINLAW | child-in-law | The player of the role is the spouse of scoping person's child.

DAUINLAW | daughter in-law | The player of the role is the wife of scoping person's son.

SONINLAW | son in-law | The player of the role is the husband of scoping person's daughter.

PRNINLAW | parent in-law | The player of the role is the parent of scoping person's husband or wife.

FTHINLAW | father-in-law | The player of the role is the father of the scoping person's husband or wife.

MTHINLAW | mother-in-law | The player of the role is the mother of the scoping person's husband or wife.

SIBINLAW | sibling in-law | The player of the role is: (1) a sibling of the scoping person's spouse, or (2) the spouse of the scoping person's sibling, or (3) the spouse of a sibling of the scoping person's spouse.

BROINLAW | brother-in-law | The player of the role is: (1) a brother of the scoping person's spouse, or (2) the husband of the scoping person's sister, or (3) the husband of a sister of the scoping person's spouse.

SISINLAW | sister-in-law | The player of the role is: (1) a sister of the scoping person's spouse, or (2) the wife of the scoping person's brother, or (3) the wife of a brother of the scoping person's spouse.

NIENEPH | niece/nephew | The player of the role is a child of scoping person's brother or sister or of the brother or sister of the scoping person's spouse.

NEPHEW | nephew | The player of the role is a son of the scoping person's brother or sister or of the brother or sister of the scoping person's spouse.

NIECE | niece | The player of the role is a daughter of the scoping person's brother or sister or of the brother or sister of the scoping person's spouse.

UNCLE | uncle | The player of the role is a brother of the scoping person's mother or father.

MUNCLE | maternal uncle | Description:The player of the role is a biological brother of the scoping person's biological mother.

PUNCLE | paternal uncle | Description:The player of the role is a biological brother of the scoping person's biological father.

PRN | parent | The player of the role is one who begets, gives birth to, or nurtures and raises the scoping entity (child).

ADOPTP | adoptive parent | The player of the role (parent) has taken the scoper (child) into their family through legal means and raises them as his or her own child.

ADOPTF | adoptive father | The player of the role (father) is a male who has taken the scoper (child) into their family through legal means and raises them as his own child.

ADOPTM | adoptive mother | The player of the role (father) is a female who has taken the scoper (child) into their family through legal means and raises them as her own child.

FTH | father | The player of the role is a male who begets or raises or nurtures the scoping entity (child).

FTHFOST | foster father | The player of the role (parent) who is a male state-certified caregiver responsible for the scoper (child) who has been placed in the parent's care. The placement of the child is usually arranged through the government or a social-service agency, and temporary. The state, via a jurisdiction recognized child protection agency, stands as in loco parentis to the child, making all legal decisions while the foster parent is responsible for the day-to-day care of the specified child.

NFTH | natural father | The player of the role is a male who begets the scoping entity (child).

NFTHF | natural father of fetus | Indicates the biologic male parent of a fetus.

STPFTH | stepfather | The player of the role is the husband of scoping person's mother and not the scoping person's natural father.

MTH | mother | The player of the role is a female who conceives, gives birth to, or raises and nurtures the scoping entity (child).

GESTM | gestational mother | The player is a female whose womb carries the fetus of the scoper. Generally used when the gestational mother and natural mother are not the same.

MTHFOST | foster mother | The player of the role (parent) who is a female state-certified caregiver responsible for the scoper (child) who has been placed in the parent's care. The placement of the child is usually arranged through the government or a social-service agency, and temporary. The state, via a jurisdiction recognized child protection agency, stands as in loco parentis to the child, making all legal decisions while the foster parent is responsible for the day-to-day care of the specified child.

NMTH | natural mother | The player of the role is a female who conceives or gives birth to the scoping entity (child).

NMTHF | natural mother of fetus | The player is the biologic female parent of the scoping fetus.

STPMTH | stepmother | The player of the role is the wife of scoping person's father and not the scoping person's natural mother.

NPRN | natural parent | natural parent

PRNFOST | foster parent | The player of the role (parent) who is a state-certified caregiver responsible for the scoper (child) who has been placed in the parent's care. The placement of the child is usually arranged through the government or a social-service agency, and temporary. The state, via a jurisdiction recognized child protection agency, stands as in loco parentis to the child, making all legal decisions while the foster parent is responsible for the day-to-day care of the specified child.

STPPRN | step parent | The player of the role is the spouse of the scoping person's parent and not the scoping person's natural parent.

SIB | sibling | The player of the role shares one or both parents in common with the scoping entity.

BRO | brother | The player of the role is a male sharing one or both parents in common with the scoping entity.

HBRO | half-brother | The player of the role is a male related to the scoping entity by sharing only one biological parent.

NBRO | natural brother | The player of the role is a male having the same biological parents as the scoping entity.

TWINBRO | twin brother | The scoper was carried in the same womb as the male player and shares common biological parents.

FTWINBRO | fraternal twin brother | The scoper was carried in the same womb as the male player and shares common biological parents but is the product of a distinct egg/sperm pair.

ITWINBRO | identical twin brother | The male scoper is an offspring of the same egg-sperm pair as the male player.

STPBRO | stepbrother | The player of the role is a son of the scoping person's stepparent.

HSIB | half-sibling | The player of the role is related to the scoping entity by sharing only one biological parent.

HSIS | half-sister | The player of the role is a female related to the scoping entity by sharing only one biological parent.

NSIB | natural sibling | The player of the role has both biological parents in common with the scoping entity.

NSIS | natural sister | The player of the role is a female having the same biological parents as the scoping entity.

TWINSIS | twin sister | The scoper was carried in the same womb as the female player and shares common biological parents.

FTWINSIS | fraternal twin sister | The scoper was carried in the same womb as the female player and shares common biological parents but is the product of a distinct egg/sperm pair.

ITWINSIS | identical twin sister | The female scoper is an offspring of the same egg-sperm pair as the female player.

TWIN | twin | The scoper and player were carried in the same womb and shared common biological parents.

FTWIN | fraternal twin | The scoper and player were carried in the same womb and share common biological parents but are the product of distinct egg/sperm pairs.

ITWIN | identical twin | The scoper and player are offspring of the same egg-sperm pair.

SIS | sister | The player of the role is a female sharing one or both parents in common with the scoping entity.

STPSIS | stepsister | The player of the role is a daughter of the scoping person's stepparent.

STPSIB | step sibling | The player of the role is a child of the scoping person's stepparent.

SIGOTHR | significant other | A person who is important to one's well being; especially a spouse or one in a similar relationship. (The player is the one who is important)

DOMPART | domestic partner | The player of the role cohabits with the scoping person but is not the scoping person's spouse.

FMRSPS | former spouse | Player of the role was previously joined to the scoping person in marriage and this marriage is now dissolved and inactive. Usage Note: This is significant to indicate as some jurisdictions have different legal requirements for former spouse to access the patient's record, from a general friend.

SPS | spouse | The player of the role is a marriage partner of the scoping person.

HUSB | husband | The player of the role is a man joined to a woman (scoping person) in marriage.

WIFE | wife | The player of the role is a woman joined to a man (scoping person) in marriage.

4.3.2.19584 HL7 v3 Value Set ParticipationTargetSubject

URL: https://hl7.org/fhir/STU3/v3/ParticipationTargetSubject/vs.html

This page is part of the FHIR Specification (v3.0.2: STU 3). The current version which supercedes this version is 4.0.1. For a full list of available versions, see the Directory of published versions

Vocabulary Work Group | Maturity Level: N/A | External | Use Context: Any

This value set (http://hl7.org/fhir/ValueSet/v3-ParticipationTargetSubject) is defined as part of HL7 v3. Related FHIR content: ParticipationTargetSubject.

Summary

Defining URL: | http://hl7.org/fhir/ValueSet/v3-ParticipationTargetSubject
Name: | ParticipationTargetSubject
Definition: | The principle target that the service acts on. E.g. the patient in physical examination, a specimen in a lab observation. May also be a patient's family member (teaching) or a device or room (cleaning, disinfecting, housekeeping). Note: not all direct targets are subjects, consumables, and devices used as tools for a service are not subjects. However, a device may be a subject of a maintenance service.
OID: | 2.16.840.1.113883.1.11.19584 (for OID based terminology systems)
Source Resource | XML / JSON

This value set is not currently used

4.3.2.19584.1 Content Logical Definition

This value set includes codes from the following code systems:

* Include codes from http://hl7.org/fhir/v3/ParticipationType where concept is-a SBJ

4.3.2.19584.2 Expansion

This expansion generated 19 Apr 2017

This value set contains 2 concepts

Expansion based on http://hl7.org/fhir/v3/ParticipationType version 2016-11-11

All codes from system http://hl7.org/fhir/v3/ParticipationType

Code | Display | Definition
SBJ | subject | The principle target on which the action happens. Examples: The patient in physical examination, a specimen in a lab observation. May also be a patient's family member (teaching) or a device or room (cleaning, disinfecting, housekeeping). UsageNotes: Not all direct targets are subjects. Consumables and devices used as tools for an act are not subjects. However, a device may be a subject of a maintenance action.
SPC | specimen | The subject of non-clinical (e.g. laboratory) observation services is a specimen.

4.3.2.19665 HL7 v3 Value Set ActClassProcedure

URL: https://hl7.org/fhir/STU3/v3/ActClassProcedure/vs.html

This page is part of the FHIR Specification (v3.0.2: STU 3). The current version which supercedes this version is 4.0.1. For a full list of available versions, see the Directory of published versions

Vocabulary Work Group | Maturity Level: N/A | External | Use Context: Any

This value set (http://hl7.org/fhir/ValueSet/v3-ActClassProcedure) is defined as part of HL7 v3. Related FHIR content: ActClassProcedure.

Summary

Defining URL: | http://hl7.org/fhir/ValueSet/v3-ActClassProcedure
Name: | ActClassProcedure
Definition: | An Act whose immediate and primary outcome (post-condition) is the alteration of the physical condition of the subject. Examples: : Procedures may involve the disruption of some body surface (e.g. an incision in a surgical procedure), but they also include conservative procedures such as reduction of a luxated join, chiropractic treatment, massage, balneotherapy, acupuncture, shiatsu, etc. Outside of clinical medicine, procedures may be such things as alteration of environments (e.g. straightening rivers, draining swamps, building dams) or the repair or change of machinery etc.
OID: | 2.16.840.1.113883.1.11.19665 (for OID based terminology systems)
Source Resource | XML / JSON

This value set is not currently used

4.3.2.19665.1 Content Logical Definition

This value set includes codes from the following code systems:

* Include codes from http://hl7.org/fhir/v3/ActClass where concept is-a PROC

4.3.2.19665.2 Expansion

This expansion generated 19 Apr 2017

This value set contains 4 concepts

Expansion based on http://hl7.org/fhir/v3/ActClass version 2016-11-11

All codes from system http://hl7.org/fhir/v3/ActClass

Code | Display | Definition
PROC | procedure | An Act whose immediate and primary outcome (post-condition) is the alteration of the physical condition of the subject. Examples: : Procedures may involve the disruption of some body surface (e.g. an incision in a surgical procedure), but they also include conservative procedures such as reduction of a luxated join, chiropractic treatment, massage, balneotherapy, acupuncture, shiatsu, etc. Outside of clinical medicine, procedures may be such things as alteration of environments (e.g. straightening rivers, draining swamps, building dams) or the repair or change of machinery etc.

SBADM | substance administration | The act of introducing or otherwise applying a substance to the subject. Discussion: The effect of the substance is typically established on a biochemical basis, however, that is not a requirement. For example, radiotherapy can largely be described in the same way, especially if it is a systemic therapy such as radio-iodine. This class also includes the application of chemical treatments to an area. Examples: Chemotherapy protocol; Drug prescription; Vaccination record

SBEXT | Substance Extraction | Description: The act of removing a substance from the subject.

SPECCOLLECT | Specimen Collection | A procedure for obtaining a specimen from a source entity.

4.3.2.19676 HL7 v3 Value Set ParticipationInformationTranscriber

URL: https://hl7.org/fhir/STU3/v3/ParticipationInformationTranscriber/vs.html

This page is part of the FHIR Specification (v3.0.2: STU 3). The current version which supercedes this version is 4.0.1. For a full list of available versions, see the Directory of published versions

Vocabulary Work Group | Maturity Level: N/A | External | Use Context: Any

This value set (http://hl7.org/fhir/ValueSet/v3-ParticipationInformationTranscriber) is defined as part of HL7 v3. Related FHIR content: ParticipationInformationTranscriber.

Summary

Defining URL: | http://hl7.org/fhir/ValueSet/v3-ParticipationInformationTranscriber

Name: | ParticipationInformationTranscriber

Definition: | An entity entering the data into the originating system. The data entry entity is collected optionally for internal quality control purposes. This includes the transcriptionist for dictated text transcribed into electronic form.

OID: | 2.16.840.1.113883.1.11.19676 (for OID based terminology systems)

Source Resource | XML / JSON

This value set is not currently used

4.3.2.19676.1 Content Logical Definition

This value set includes codes from the following code systems:

* Include codes from http://hl7.org/fhir/v3/ParticipationType where concept is-a TRANS

4.3.2.19676.2 Expansion

This expansion generated 19 Apr 2017

This value set contains 2 concepts

Expansion based on http://hl7.org/fhir/v3/ParticipationType version 2016-11-11

All codes from system http://hl7.org/fhir/v3/ParticipationType

Code | Display | Definition

TRANS | Transcriber | An entity entering the data into the originating system. The data entry entity is collected optionally for internal quality control purposes. This includes the transcriptionist for dictated text transcribed into electronic form.

ENT | data entry person | A person entering the data into the originating system. The data entry person is collected optionally for internal quality control purposes. This includes the transcriptionist for dictated text.

4.3.2.19707 HL7 v3 Value Set VerificationMethod

URL: https://hl7.org/fhir/STU3/v3/VerificationMethod/vs.html

This page is part of the FHIR Specification (v3.0.2: STU 3). The current version which supercedes this version is 4.0.1. For a full list of available versions, see the Directory of published versions

Vocabulary Work Group | Maturity Level: N/A | External | Use Context: Any

This value set (http://hl7.org/fhir/ValueSet/v3-VerificationMethod) is defined as part of HL7 v3. Related FHIR content: VerificationMethod.

Summary

Defining URL: | http://hl7.org/fhir/ValueSet/v3-VerificationMethod

Name: | VerificationMethod

Definition: | No Description Provided

OID: | 2.16.840.1.113883.1.11.19707 (for OID based terminology systems)

Source Resource | XML / JSON

This value set is not currently used

4.3.2.19707.1 Content Logical Definition

This value set includes codes from the following code systems:

* Include codes from http://hl7.org/fhir/v3/ObservationMethod where concept is-a _VerificationMethod

4.3.2.19707.2 Expansion

This expansion generated 19 Apr 2017

This value set contains 4 concepts

Expansion based on http://hl7.org/fhir/v3/ObservationMethod version 2016-11-11

All codes from system http://hl7.org/fhir/v3/ObservationMethod

Code | Display | Definition
_VerificationMethod | VerificationMethod | VerificationMethod
VDOC | document verification | Verification by means of document. Example: Fax, letter, attachment to e-mail.
VREG | registry verification | verification by means of a response to an electronic query Example: query message to a Covered Party registry application or Coverage Administrator.
VTOKEN | electronic token verification | Verification by means of electronic token. Example: smartcard, magnetic swipe card, RFID device.
VVOICE | voice-based verification | Verification by means of voice. Example: By speaking with or calling the Coverage Administrator or Covered Party

4.3.2.19812 HL7 v3 Value Set MilitaryRoleType

URL: https://hl7.org/fhir/STU3/v3/MilitaryRoleType/vs.html

This page is part of the FHIR Specification (v3.0.2: STU 3). The current version which supercedes this version is 4.0.1. For a full list of available versions, see the Directory of published versions

Vocabulary Work Group | Maturity Level: N/A | External | Use Context: Any

This value set (http://hl7.org/fhir/ValueSet/v3-MilitaryRoleType) is defined as part of HL7 v3. Related FHIR content: MilitaryRoleType.

Summary

Defining URL: | http://hl7.org/fhir/ValueSet/v3-MilitaryRoleType
Name: | MilitaryRoleType
Definition: | Definition: A person playing the role of program eligible under a program based on military status. Discussion: This CoveredPartyRoleType.code is typically used when the CoveredPartyRole class code is either "program eligible" or "subscriber" and the person's status as a member of the military meets jurisdictional or program criteria
OID: | 2.16.840.1.113883.1.11.19812 (for OID based terminology systems)
Source Resource | XML / JSON

This value set is not currently used

4.3.2.19812.1 Content Logical Definition

This value set includes codes from the following code systems:

* Include codes from http://hl7.org/fhir/v3/RoleCode where concept is-a MIL

4.3.2.19812.2 Expansion

This expansion generated 19 Apr 2017

This value set contains 4 concepts

Expansion based on http://hl7.org/fhir/v3/RoleCode version 2016-11-11

All codes from system http://hl7.org/fhir/v3/RoleCode

Code | Display | Definition
MIL | military | Definition: A person playing the role of program eligible under a program based on military status. Discussion: This CoveredPartyRoleType.code is typically used when the CoveredPartyRole class code is either "program eligible" or "subscriber" and the person's status as a member of the military meets jurisdictional or program criteria
ACTMIL | active duty military | Description: A person playing the role of program eligible under a program based on active military status. Discussion: This CoveredPartyRoleType.code is typically used when the CoveredPartyRole class code is either "program eligible" or "subscriber" and the persons status as active duty military meets jurisdictional or program criteria.
RETMIL | retired military | Description: A person playing the role of program eligible under a program based on retired military status. Discussion: This CoveredPartyRoleType.code is typically used when the CoveredPartyRole class code is either "program eligible" or "subscriber" and the persons status as retired military meets jurisdictional or program criteria.
VET | veteran | Description: A person playing the role of program eligible under a program based on status as a military veteran. Discussion: This CoveredPartyRoleType.code is typically used when the CoveredPartyRole class code is either "program eligible" or "subscriber" and the persons status as a veteran meets jurisdictional or program criteria.

4.3.2.19846 HL7 v3 Value Set ActTaskCode

URL: https://hl7.org/fhir/STU3/v3/ActTaskCode/vs.html

This page is part of the FHIR Specification (v3.0.2: STU 3). The current version which supercedes this version is 4.0.1. For a full list of available versions, see the Directory of published versions

Vocabulary Work Group | Maturity Level: N/A | External | Use Context: Any

This value set (http://hl7.org/fhir/ValueSet/v3-ActTaskCode) is defined as part of HL7 v3. Related FHIR content: ActTaskCode.

Summary

Defining URL: | http://hl7.org/fhir/ValueSet/v3-ActTaskCode
Name: | ActTaskCode
Definition: | Description: A task or action that a user may perform in a clinical information system.
OID: | 2.16.840.1.113883.1.11.19846 (for OID based terminology systems)
Source Resource | XML / JSON

This value set is not currently used

4.3.2.19846.1 Content Logical Definition

This value set includes codes from the following code systems:

* Include codes from http://hl7.org/fhir/v3/ActCode where concept is-a _ActTaskCode

4.3.2.19846.2 Expansion

This expansion generated 19 Apr 2017

This value set contains 37 concepts

Expansion based on http://hl7.org/fhir/v3/ActCode version 2016-11-11

All codes from system http://hl7.org/fhir/v3/ActCode

Code | Display | Definition
_ActTaskCode | ActTaskCode | Description: A task or action that a user may perform in a clinical information system (e.g., medication order entry, laboratory test results review, problem list entry).
OE | order entry task | A clinician creates a request for a service to be performed for a given patient.
LABOE | laboratory test order entry task | A clinician creates a request for a laboratory test to be done for a given patient.
MEDOE | medication order entry task | A clinician creates a request for the administration of one or more medications to a given patient.
PATDOC | patient documentation task | A person enters documentation about a given patient.
ALLERLREV | allergy list review | Description: A person reviews a list of known allergies of a given patient.
CLINNOTEE | clinical note entry task | A clinician enters a clinical note about a given patient
DIAGLISTE | diagnosis list entry task | A clinician enters a diagnosis for a given patient.
DISCHINSTE | discharge instruction entry | A person provides a discharge instruction to a patient.
DISCHSUME | discharge summary entry task | A clinician enters a discharge summary for a given patient.
PATEDUE | patient education entry | A person provides a patient-specific education handout to a patient.
PATREPE | pathology report entry task | A pathologist enters a report for a given patient.
PROBLISTE | problem list entry task | A clinician enters a problem for a given patient.
RADREPE | radiology report entry task | A radiologist enters a report for a given patient.
IMMLREV | immunization list review | Description: A person reviews a list of immunizations due or received for a given patient.
REMLREV | reminder list review | Description: A person reviews a list of health care reminders for a given patient.
WELLREMLREV | wellness reminder list review | Description: A person reviews a list of wellness or preventive care reminders for a given patient.
PATINFO | patient information review task | A person (e.g., clinician, the patient herself) reviews patient information in the electronic medical record.
ALLERLE | allergy list entry | Description: A person enters a known allergy for a given patient.
CDSREV | clinical decision support intervention review | A person reviews a recommendation/assessment provided automatically by a clinical decision support application for a given patient.
CLINNOTEREV | clinical note review task | A person reviews a clinical note of a given patient.
DISCHSUMREV | discharge summary review task | A person reviews a discharge summary of a given patient.
DIAGLISTREV | diagnosis list review task | A person reviews a list of diagnoses of a given patient.
IMMLE | immunization list entry | Description: A person enters an immunization due or received for a given patient.
LABRREV | laboratory results review task | A person reviews a list of laboratory results of a given patient.
MICRORREV | microbiology results review task | A person reviews a list of microbiology results of a given patient.
MICROORGRREV | microbiology organisms results review task | A person reviews organisms of microbiology results of a given patient.
MICROSENSRREV | microbiology sensitivity test results review task | A person reviews the sensitivity test of microbiology results of a given patient.
MLREV | medication list review task | A person reviews a list of medication orders submitted to a given patient
MARWLREV | medication administration record work list review task | A clinician reviews a work list of medications to be administered to a given patient.
OREV | orders review task | A person reviews a list of orders submitted to a given patient.
PATREPREV | pathology report review task | A person reviews a pathology report of a given patient.
PROBLISTREV | problem list review task | A person reviews a list of problems of a given patient.
RADREPREV | radiology report review task | A person reviews a radiology report of a given patient.
REMLE | reminder list entry | Description: A person enters a health care reminder for a given patient.
WELLREMLE | wellness reminder list entry | Description: A person enters a wellness or preventive care reminder for a given patient.
RISKASSESS | risk assessment instrument task | A person reviews a Risk Assessment Instrument report of a given patient.
FALLRISK | falls risk assessment instrument task | A person reviews a Falls Risk Assessment Instrument report of a given patient.

4.3.2.19855 HL7 v3 Value Set ActCoverageTypeCode

URL: https://hl7.org/fhir/STU3/v3/ActCoverageTypeCode/vs.html

This page is part of the FHIR Specification (v3.0.2: STU 3). The current version which supercedes this version is 4.0.1. For a full list of available versions, see the Directory of published versions

Vocabulary Work Group | Maturity Level: N/A | External | Use Context: Any

This value set (http://hl7.org/fhir/ValueSet/v3-ActCoverageTypeCode) is defined as part of HL7 v3. Related FHIR content: ActCoverageTypeCode.

Summary

Defining URL: | http://hl7.org/fhir/ValueSet/v3-ActCoverageTypeCode
Name: | ActCoverageTypeCode
Definition: | Definition: Set of codes indicating the type of insurance policy or program that pays for the cost of benefits provided to covered parties.
OID: | 2.16.840.1.113883.1.11.19855 (for OID based terminology systems)

Source Resource | XML / JSON

This value set is not currently used

4.3.2.19855.1 Content Logical Definition

This value set includes codes from the following code systems:

* Include codes from http://hl7.org/fhir/v3/ActCode where concept is-a _ActCoverageTypeCode

4.3.2.19855.2 Expansion

This expansion generated 19 Apr 2017

This value set contains 52 concepts

Expansion based on http://hl7.org/fhir/v3/ActCode version 2016-11-11

All codes from system http://hl7.org/fhir/v3/ActCode

Code | Display | Definition

_ActCoverageTypeCode | ActCoverageTypeCode | Definition: Set of codes indicating the type of insurance policy or program that pays for the cost of benefits provided to covered parties.

_ActInsurancePolicyCode | ActInsurancePolicyCode | Set of codes indicating the type of insurance policy or other source of funds to cover healthcare costs.

EHCPOL | extended healthcare | Private insurance policy that provides coverage in addition to other policies (e.g. in addition to a Public Healthcare insurance policy).

HSAPOL | health spending account | Insurance policy that provides for an allotment of funds replenished on a periodic (e.g. annual) basis. The use of the funds under this policy is at the discretion of the covered party.

AUTOPOL | automobile | Insurance policy for injuries sustained in an automobile accident. Will also typically covered non-named parties to the policy, such as pedestrians and passengers.

COL | collision coverage policy | Definition: An automobile insurance policy under which the insurance company will cover the cost of damages to an automobile owned by the named insured that are caused by accident or intentionally by another party.

UNINSMOT | uninsured motorist policy | Definition: An automobile insurance policy under which the insurance company will indemnify a loss for which another motorist is liable if that motorist is unable to pay because he or she is uninsured. Coverage under the policy applies to bodily injury damages only. Injuries to the covered party caused by a hit-and-run driver are also covered.

PUBLICPOL | public healthcare | Insurance policy funded by a public health system such as a provincial or national health plan. Examples include BC MSP (British Columbia Medical Services Plan) OHIP (Ontario Health Insurance Plan), NHS (National Health Service).

DENTPRG | dental program | Definition: A public or government health program that administers and funds coverage for dental care to assist program eligible who meet financial and health status criteria.

DISEASEPRG | public health program | Definition: A public or government health program that administers and funds coverage for health and social services to assist program eligible who meet financial and health status criteria related to a particular disease. Example: Reproductive health, sexually transmitted disease, and end renal disease programs.

CANPRG | women's cancer detection program | Definition: A program that provides low-income, uninsured, and underserved women access to timely, high-quality screening and diagnostic services, to detect breast and cervical cancer at the earliest stages. Example: To improve women's access to screening for breast and cervical cancers, Congress passed the Breast and Cervical Cancer Mortality Prevention Act of 1990, which guided CDC in creating the National Breast and Cervical Cancer Early Detection Program (NBCCEDP), which provides access to critical breast and cervical cancer screening services for underserved women in the United States. An estimated 7 to 10% of U.S. women of screening age are eligible to receive NBCCEDP services. Federal guidelines establish an eligibility baseline to direct services to uninsured and underinsured women at or below 250% of federal poverty level; ages 18 to 64 for cervical screening; ages 40 to 64 for breast screening.

ENDRENAL | end renal program | Definition: A public or government program that administers publicly funded coverage of kidney dialysis and kidney transplant services. Example: In the U.S., the Medicare End-stage Renal Disease program (ESRD), the National Kidney Foundation (NKF) American Kidney Fund (AKF) The Organ Transplant Fund.

HIVAIDS | HIV-AIDS program | Definition: Government administered and funded HIV-AIDS program for beneficiaries meeting financial and health status criteria. Administration, funding levels, eligibility criteria, covered benefits, provider types, and financial participation are typically set by a regulatory process. Payer responsibilities for administering the program may be delegated to contractors. Example: In the U.S., the Ryan White program, which is administered by the Health Resources and Services Administration.

MANDPOL | mandatory health program | mandatory health program

MENTPRG | mental health program | Definition: Government administered and funded mental health program for beneficiaries meeting financial and mental health status criteria. Administration, funding levels, eligibility criteria, covered benefits, provider types, and financial participation are typically set by a regulatory process. Payer responsibilities for administering the program may be delegated to contractors. Example: In the U.S., states receive funding for substance use programs from the Substance Abuse Mental Health Administration (SAMHSA).

SAFNET | safety net clinic program | Definition: Government administered and funded program to support provision of care to underserved populations through safety net clinics. Example: In the U.S., safety net providers such as federally qualified health centers (FQHC) receive funding under PHSA Section 330 grants administered by the Health Resources and Services Administration.

SUBPRG | substance use program | Definition: Government administered and funded substance use program for beneficiaries meeting financial, substance use behavior, and health status criteria. Beneficiaries may be required to enroll as a result of legal proceedings. Administration, funding levels, eligibility criteria, covered benefits, provider types, and financial participation are typically set by a regulatory process. Payer responsibilities for administering the program may be delegated to contractors. Example: In the U.S., states receive funding for substance use programs from the Substance Abuse Mental Health Administration (SAMHSA).

SUBSIDIZ | subsidized health program | Definition: A government health program that provides coverage for health services to persons meeting eligibility criteria such as income, location of residence, access to other coverages, health condition, and age, the cost of which is to some extent subsidized by public funds.

SUBSIDMC | subsidized managed care program | Definition: A government health program that provides coverage through managed care contracts for health services to persons meeting eligibility criteria such as income, location of residence, access to other coverages, health condition, and age, the cost of which is to some extent subsidized by public funds. Discussion: The structure and business processes for underwriting and administering a subsidized managed care program is further specified by the Underwriter and Payer Role.class and Role.code.

SUBSUPP | subsidized supplemental health program | Definition: A government health program that provides coverage for health services to persons meeting eligibility criteria for a supplemental health policy or program such as income, location of residence, access to other coverages, health condition, and age, the cost of which is to some extent subsidized by public funds. Example: Supplemental health coverage program may cover the cost of a health program or policy financial participations, such as the copays and the premiums, and may provide coverage for services in

addition to those covered under the supplemented health program or policy. In the U.S., Medicaid programs may pay the premium for a covered party who is also covered under the Medicare program or a private health policy. Discussion: The structure and business processes for underwriting and administering a subsidized supplemental retiree health program is further specified by the Underwriter and Payer Role.class and Role.code.

WCBPOL | worker's compensation | Insurance policy for injuries sustained in the work place or in the course of employment.

_ActInsuranceTypeCode | ActInsuranceTypeCode | Definition: Set of codes indicating the type of insurance policy. Insurance, in law and economics, is a form of risk management primarily used to hedge against the risk of potential financial loss. Insurance is defined as the equitable transfer of the risk of a potential loss, from one entity to another, in exchange for a premium and duty of care. A policy holder is an individual or an organization enters into a contract with an underwriter which stipulates that, in exchange for payment of a sum of money (a premium), one or more covered parties (insureds) is guaranteed compensation for losses resulting from certain perils under specified conditions. The underwriter analyzes the risk of loss, makes a decision as to whether the risk is insurable, and prices the premium accordingly. A policy provides benefits that indemnify or cover the cost of a loss incurred by a covered party, and may include coverage for services required to remediate a loss. An insurance policy contains pertinent facts about the policy holder, the insurance coverage, the covered parties, and the insurer. A policy may include exemptions and provisions specifying the extent to which the indemnification clause cannot be enforced for intentional tortious conduct of a covered party, e.g., whether the covered parties are jointly or severably insured. Discussion: In contrast to programs, an insurance policy has one or more policy holders, who own the policy. The policy holder may be the covered party, a relative of the covered party, a partnership, or a corporation, e.g., an employer. A subscriber of a self-insured health insurance policy is a policy holder. A subscriber of an employer sponsored health insurance policy is holds a certificate of coverage, but is not a policy holder; the policy holder is the employer. See CoveredRoleType.

_ActHealthInsuranceTypeCode | ActHealthInsuranceTypeCode | Definition: Set of codes indicating the type of health insurance policy that covers health services provided to covered parties. A health insurance policy is a written contract for insurance between the insurance company and the policyholder, and contains pertinent facts about the policy owner (the policy holder), the health insurance coverage, the insured subscribers and dependents, and the insurer. Health insurance is typically administered in accordance with a plan, which specifies (1) the type of health services and health conditions that will be covered under what circumstances (e.g., exclusion of a pre-existing condition, service must be deemed medically necessary; service must not be experimental; service must provided in accordance with a protocol; drug must be on a formulary; service must be prior authorized; or be a referral from a primary care provider); (2) the type and affiliation of providers (e.g., only allopathic physicians, only in network, only providers employed by an HMO); (3) financial participations required of covered parties (e.g., co-pays, coinsurance, deductibles, out-of-pocket); and (4) the manner in which services will be paid (e.g., under indemnity or fee-for-service health plans, the covered party typically pays out-of-pocket and then file a claim for reimbursement, while health plans that have contractual relationships with providers, i.e., network providers, typically do not allow the providers to bill the covered party for the cost of the service until after filing a claim with the payer and receiving reimbursement).

DENTAL | dental care policy | Definition: A health insurance policy that that covers benefits for dental services.

DISEASE | disease specific policy | Definition: A health insurance policy that covers benefits for healthcare services provided for named conditions under the policy, e.g., cancer, diabetes, or HIV-AIDS.

DRUGPOL | drug policy | Definition: A health insurance policy that covers benefits for prescription drugs, pharmaceuticals, and supplies.

HIP | health insurance plan policy | Definition: A health insurance policy that covers healthcare benefits by protecting covered parties from medical expenses arising from health conditions, sickness, or accidental injury as well as preventive care. Health insurance policies explicitly exclude coverage for losses insured under a disability policy, workers' compensation program, liability insurance (including automobile insurance); or for medical expenses, coverage for on-site medical clinics or for limited dental or vision benefits when these are provided under a separate policy. Discussion: Health insurance policies are offered by health insurance plans that typically reimburse providers for covered services on a fee-for-service basis, that is, a fee that is the allowable amount that a provider may charge. This is in contrast to managed care plans, which typically prepay providers a per-member/per-month amount or capitation as reimbursement for all covered services rendered. Health insurance plans include indemnity and healthcare services plans.

LTC | long term care policy | Definition: An insurance policy that covers benefits for long-term care services people need when they no longer can care for themselves. This may be due to an accident, disability, prolonged illness or the simple process of aging. Long-term care services assist with activities of daily living including: Help at home with day-to-day activities, such as cooking, cleaning, bathing and dressing Care in the community, such as in an adult day care facility Supervised care provided in an assisted living facility Skilled care provided in a nursing home

MCPOL | managed care policy | Definition: Government mandated program providing coverage, disability income, and vocational rehabilitation for injuries sustained in the work place or in the course of employment. Employers may either self-fund the program, purchase commercial coverage, or pay a premium to a government entity that administers the program. Employees may be required to pay premiums toward the cost of coverage as well. Managed care policies specifically exclude coverage for losses insured under a disability policy, workers' compensation program, liability insurance (including automobile insurance); or for medical expenses, coverage for on-site medical clinics or for limited dental or vision benefits when these are provided under a separate policy. Discussion: Managed care policies are offered by managed care plans that contract with selected providers or health care organizations to provide comprehensive health care at a discount to covered parties and coordinate the financing and delivery of health care. Managed care uses medical protocols and procedures agreed on by the medical profession to be cost effective, also known as medical practice guidelines. Providers are typically reimbursed for covered services by a capitated amount on a per member per month basis that may reflect difference in the health status and level of services anticipated to be needed by the member.

POS | point of service policy | Definition: A policy for a health plan that has features of both an HMO and a FFS plan. Like an HMO, a POS plan encourages the use its HMO network to maintain discounted fees with participating providers, but recognizes that sometimes covered parties want to choose their own provider. The POS plan allows a covered party to use providers who are not part of the HMO network (non-participating providers). However, there is a greater cost associated with choosing these non-network providers. A covered party will usually pay deductibles and coinsurances that are substantially higher than the payments when he or she uses a plan provider. Use of non-participating providers often requires the covered party to pay the provider directly and then to file a claim for reimbursement, like in an FFS plan.

HMO | health maintenance organization policy | Definition: A policy for a health plan that provides coverage for health care only through contracted or employed physicians and hospitals located in particular geographic or service areas. HMOs emphasize prevention and early detection of illness. Eligibility to enroll in an HMO is determined by where a covered party lives or works.

PPO | preferred provider organization policy | Definition: A network-based, managed care plan that allows a covered party to choose any health care provider. However, if care is received from a "preferred" (participating in-network) provider, there are generally higher benefit coverage and lower deductibles.

MENTPOL | mental health policy | Definition: A health insurance policy that covers benefits for mental health services and prescriptions.

SUBPOL | substance use policy | Definition: A health insurance policy that covers benefits for substance use services.

VISPOL | vision care policy | Definition: Set of codes for a policy that provides coverage for health care expenses arising from vision services. A health insurance policy that covers benefits for vision care services, prescriptions, and products.

DIS | disability insurance policy | Definition: An insurance policy that provides a regular payment to compensate for income lost due to the covered party's inability to work because of illness or injury.

EWB | employee welfare benefit plan policy | Definition: An insurance policy under a benefit plan run by an employer or employee organization for the purpose of providing benefits other than pension-related to employees and their families. Typically provides health-related benefits, benefits for disability, disease or unemployment, or day care and scholarship benefits, among others. An employer sponsored health policy includes coverage of health care expenses arising from sickness or accidental injury, coverage for on-site medical clinics or for dental or vision benefits, which are typically provided under a separate policy. Coverage excludes health care expenses covered by accident or disability, workers' compensation, liability or

automobile insurance.

FLEXP | flexible benefit plan policy | Definition: An insurance policy that covers qualified benefits under a Flexible Benefit plan such as group medical insurance, long and short term disability income insurance, group term life insurance for employees only up to $50,000 face amount, specified disease coverage such as a cancer policy, dental and/or vision insurance, hospital indemnity insurance, accidental death and dismemberment insurance, a medical expense reimbursement plan and a dependent care reimbursement plan. Discussion: See UnderwriterRoleTypeCode flexible benefit plan which is defined as a benefit plan that allows employees to choose from several life, health, disability, dental, and other insurance plans according to their individual needs. Also known as cafeteria plans. Authorized under Section 125 of the Revenue Act of 1978.

LIFE | life insurance policy | Definition: A policy under which the insurer agrees to pay a sum of money upon the occurrence of the covered partys death. In return, the policyholder agrees to pay a stipulated amount called a premium at regular intervals. Life insurance indemnifies the beneficiary for the loss of the insurable interest that a beneficiary has in the life of a covered party. For persons related by blood, a substantial interest established through love and affection, and for all other persons, a lawful and substantial economic interest in having the life of the insured continue. An insurable interest is required when purchasing life insurance on another person. Specific exclusions are often written into the contract to limit the liability of the insurer; for example claims resulting from suicide or relating to war, riot and civil commotion. Discussion:A life insurance policy may be used by the covered party as a source of health care coverage in the case of a viatical settlement, which is the sale of a life insurance policy by the policy owner, before the policy matures. Such a sale, at a price discounted from the face amount of the policy but usually in excess of the premiums paid or current cash surrender value, provides the seller an immediate cash settlement. Generally, viatical settlements involve insured individuals with a life expectancy of less than two years. In countries without state-subsidized healthcare and high healthcare costs (e.g. United States), this is a practical way to pay extremely high health insurance premiums that severely ill people face. Some people are also familiar with life settlements, which are similar transactions but involve insureds with longer life expectancies (two to fifteen years).

ANNU | annuity policy | Definition: A policy that, after an initial premium or premiums, pays out a sum at pre-determined intervals. For example, a policy holder may pay $10,000, and in return receive $150 each month until he dies; or $1,000 for each of 14 years or death benefits if he dies before the full term of the annuity has elapsed.

TLIFE | term life insurance policy | Definition: Life insurance under which the benefit is payable only if the insured dies during a specified period. If an insured dies during that period, the beneficiary receives the death payments. If the insured survives, the policy ends and the beneficiary receives nothing.

ULIFE | universal life insurance policy | Definition: Life insurance under which the benefit is payable upon the insuredaTMs death or diagnosis of a terminal illness. If an insured dies during that period, the beneficiary receives the death payments. If the insured survives, the policy ends and the beneficiary receives nothing

PNC | property and casualty insurance policy | Definition: A type of insurance that covers damage to or loss of the policyholderaTMs property by providing payments for damages to property damage or the injury or death of living subjects. The terms "casualty" and "liability" insurance are often used interchangeably. Both cover the policyholder's legal liability for damages caused to other persons and/or their property.

REI | reinsurance policy | Definition: An agreement between two or more insurance companies by which the risk of loss is proportioned. Thus the risk of loss is spread and a disproportionately large loss under a single policy does not fall on one insurance company. Acceptance by an insurer, called a reinsurer, of all or part of the risk of loss of another insurance company. Discussion: Reinsurance is a means by which an insurance company can protect itself against the risk of losses with other insurance companies. Individuals and corporations obtain insurance policies to provide protection for various risks (hurricanes, earthquakes, lawsuits, collisions, sickness and death, etc.). Reinsurers, in turn, provide insurance to insurance companies. For example, an HMO may purchase a reinsurance policy to protect itself from losing too much money from one insured's particularly expensive health care costs. An insurance company issuing an automobile liability policy, with a limit of $100,000 per accident may reinsure its liability in excess of $10,000. A fire insurance company which issues a large policy generally reinsures a portion of the risk with one or several other companies. Also called risk control insurance or stop-loss insurance.

SURPL | surplus line insurance policy | Definition: A risk or part of a risk for which there is no normal insurance market available. Insurance written by unauthorized insurance companies. Surplus lines insurance is insurance placed with unauthorized insurance companies through licensed surplus lines agents or brokers.

UMBRL | umbrella liability insurance policy | Definition: A form of insurance protection that provides additional liability coverage after the limits of your underlying policy are reached. An umbrella liability policy also protects you (the insured) in many situations not covered by the usual liability policies.

_ActProgramTypeCode | ActProgramTypeCode | Definition: A set of codes used to indicate coverage under a program. A program is an organized structure for administering and funding coverage of a benefit package for covered parties meeting eligibility criteria, typically related to employment, health, financial, and demographic status. Programs are typically established or permitted by legislation with provisions for ongoing government oversight. Regulations may mandate the structure of the program, the manner in which it is funded and administered, covered benefits, provider types, eligibility criteria and financial participation. A government agency may be charged with implementing the program in accordance to the regulation. Risk of loss under a program in most cases would not meet what an underwriter would consider an insurable risk, i.e., the risk is not random in nature, not financially measurable, and likely requires subsidization with government funds. Discussion: Programs do not have policy holders or subscribers. Program eligibles are enrolled based on health status, statutory eligibility, financial status, or age. Program eligibles who are covered parties under the program may be referred to as members, beneficiaries, eligibles, or recipients. Programs risk are underwritten by not for profit organizations such as governmental entities, and the beneficiaries typically do not pay for any or some portion of the cost of coverage. See CoveredPartyRoleType.

CHAR | charity program | Definition: A program that covers the cost of services provided directly to a beneficiary who typically has no other source of coverage without charge.

CRIME | crime victim program | Definition: A program that covers the cost of services provided to crime victims for injuries or losses related to the occurrence of a crime.

EAP | employee assistance program | Definition: An employee assistance program is run by an employer or employee organization for the purpose of providing benefits and covering all or part of the cost for employees to receive counseling, referrals, and advice in dealing with stressful issues in their lives. These may include substance abuse, bereavement, marital problems, weight issues, or general wellness issues. The services are usually provided by a third-party, rather than the company itself, and the company receives only summary statistical data from the service provider. Employee's names and services received are kept confidential.

GOVEMP | government employee health program | Definition: A set of codes used to indicate a government program that is an organized structure for administering and funding coverage of a benefit package for covered parties meeting eligibility criteria, typically related to employment, health and financial status. Government programs are established or permitted by legislation with provisions for ongoing government oversight. Regulation mandates the structure of the program, the manner in which it is funded and administered, covered benefits, provider types, eligibility criteria and financial participation. A government agency is charged with implementing the program in accordance to the regulation Example: Federal employee health benefit program in the U.S.

HIRISK | high risk pool program | Definition: A government program that provides health coverage to individuals who are considered medically uninsurable or high risk, and who have been denied health insurance due to a serious health condition. In certain cases, it also applies to those who have been quoted very high premiums a" again, due to a serious health condition. The pool charges premiums for coverage. Because the pool covers high-risk people, it incurs a higher level of claims than premiums can cover. The insurance industry pays into the pool to make up the difference and help it remain viable.

IND | indigenous peoples health program | Definition: Services provided directly and through contracted and operated indigenous peoples health programs. Example: Indian Health Service in the U.S.

MILITARY | military health program | Definition: A government program that provides coverage for health services to military personnel, retirees, and dependents. A covered party who is a subscriber can choose from among Fee-for-Service (FFS) plans, and their Preferred Provider Organizations (PPO), or Plans offering a Point of Service (POS) Product, or Health Maintenance Organizations. Example: In the U.S., TRICARE, CHAMPUS.

RETIRE | retiree health program | Definition: A government mandated program with specific eligibility requirements based on premium contributions made during employment, length of employment, age, and employment status, e.g., being retired, disabled, or a dependent of a covered party under this program. Benefits typically include ambulatory, inpatient, and long-term care, such as hospice care, home health care and respite care.

SOCIAL | social service program | Definition: A social service program funded by a public or governmental entity. Example: Programs providing habilitation, food, lodging, medicine, transportation, equipment, devices, products, education, training, counseling, alteration of living or work space, and other resources to persons meeting eligibility criteria.

VET | veteran health program | Definition: Services provided directly and through contracted and operated veteran health programs.

4.3.2.19897 HL7 v3 Value Set ActConsentType

URL: https://hl7.org/fhir/STU3/v3/ActConsentType/vs.html

This page is part of the FHIR Specification (v3.0.2: STU 3). The current version which supercedes this version is 4.0.1. For a full list of available versions, see the Directory of published versions

Vocabulary Work Group | Maturity Level: N/A | External | Use Context: Any

This value set (http://hl7.org/fhir/ValueSet/v3-ActConsentType) is defined as part of HL7 v3. Related FHIR content: ActConsentType.

Summary

Defining URL: | http://hl7.org/fhir/ValueSet/v3-ActConsentType

Name: | ActConsentType

Definition: | Definition: The type of consent directive, e.g., to consent or dissent to collect, access, or use in specific ways within an EHRS or for health information exchange; or to disclose health information for purposes such as research.

OID: | 2.16.840.1.113883.1.11.19897 (for OID based terminology systems)

Source Resource | XML / JSON

This value set is not currently used

4.3.2.19897.1 Content Logical Definition

This value set includes codes from the following code systems:

* Include codes from http://hl7.org/fhir/v3/ActCode where concept is-a _ActConsentType

4.3.2.19897.2 Expansion

This expansion generated 19 Apr 2017

This value set contains 9 concepts

Expansion based on http://hl7.org/fhir/v3/ActCode version 2016-11-11

All codes from system http://hl7.org/fhir/v3/ActCode

Code | Display | Definition

_ActConsentType | ActConsentType | Definition: The type of consent directive, e.g., to consent or dissent to collect, access, or use in specific ways within an EHRS or for health information exchange; or to disclose health information for purposes such as research.

ICOL | information collection | Definition: Consent to have healthcare information collected in an electronic health record. This entails that the information may be used in analysis, modified, updated.

IDSCL | information disclosure | Definition: Consent to have collected healthcare information disclosed.

INFA | information access | Definition: Consent to access healthcare information.

INFAO | access only | Definition: Consent to access or "read" only, which entails that the information is not to be copied, screen printed, saved, emailed, stored, re-disclosed or altered in any way. This level ensures that data which is masked or to which access is restricted will not be. Example: Opened and then emailed or screen printed for use outside of the consent directive purpose.

INFASO | access and save only | Definition: Consent to access and save only, which entails that access to the saved copy will remain locked.

IRDSCL | information redisclosure | Definition: Information re-disclosed without the patient's consent.

RESEARCH | research information access | Definition: Consent to have healthcare information in an electronic health record accessed for research purposes.

RSDID | de-identified information access | Definition: Consent to have de-identified healthcare information in an electronic health record that is accessed for research purposes, but without consent to re-identify the information under any circumstance.

RSREID | re-identifiable information access | Definition: Consent to have de-identified healthcare information in an electronic health record that is accessed for research purposes re-identified under specific circumstances outlined in the consent. Example:: Where there is a need to inform the subject of potential health issues.

4.3.2.20224 HL7 v3 Value Set ActClassInvestigation

URL: https://hl7.org/fhir/STU3/v3/ActClassInvestigation/vs.html

This page is part of the FHIR Specification (v3.0.2: STU 3). The current version which supercedes this version is 4.0.1. For a full list of available versions, see the Directory of published versions

Vocabulary Work Group | Maturity Level: N/A | External | Use Context: Any

This value set (http://hl7.org/fhir/ValueSet/v3-ActClassInvestigation) is defined as part of HL7 v3. Related FHIR content: ActClassInvestigation.

Summary

Defining URL: | http://hl7.org/fhir/ValueSet/v3-ActClassInvestigation
Name: | ActClassInvestigation
Definition: | An formalized inquiry into the circumstances surrounding a particular unplanned event or potential event for the purposes of identifying possible causes and contributing factors for the event. This investigation could be conducted at a local institutional level or at the level of a local or national government.
OID: | 2.16.840.1.113883.1.11.20224 (for OID based terminology systems)
Source Resource | XML / JSON

This value set is not currently used

4.3.2.20224.1 Content Logical Definition

This value set includes codes from the following code systems:

* Include codes from http://hl7.org/fhir/v3/ActClass where concept is-a INVSTG

4.3.2.20224.2 Expansion

This expansion generated 19 Apr 2017

This value set contains 1 concepts

Expansion based on http://hl7.org/fhir/v3/ActClass version 2016-11-11

All codes from system http://hl7.org/fhir/v3/ActClass

Code | Display | Definition
INVSTG | investigation | An formalized inquiry into the circumstances surrounding a particular unplanned event or potential event for the purposes of identifying possible causes and contributing factors for the event. This investigation could be conducted at a local institutional level or at the level of a local or national government.

4.3.2.20425 HL7 v3 Value Set ActConsentDirective

URL: https://hl7.org/fhir/STU3/v3/ActConsentDirective/vs.html

This page is part of the FHIR Specification (v3.0.2: STU 3). The current version which supercedes this version is 4.0.1. For a full list of available versions, see the Directory of published versions

Vocabulary Work Group | Maturity Level: N/A | External | Use Context: Any

This value set (http://hl7.org/fhir/ValueSet/v3-ActConsentDirective) is defined as part of HL7 v3. Related FHIR content: ActConsentDirective.

Summary

Defining URL: | http://hl7.org/fhir/ValueSet/v3-ActConsentDirective
Name: | ActConsentDirective
Definition: | ActConsentDirective codes are used to specify the type of Consent Directive to which a Consent Directive Act conforms.
OID: | 2.16.840.1.113883.1.11.20425 (for OID based terminology systems)
Source Resource | XML / JSON

This value set is used in the following places:

* Contract.decisionType (Extensible)

4.3.2.20425.1 Content Logical Definition

This value set includes codes from the following code systems:

* Include codes from http://hl7.org/fhir/v3/ActCode where concept is-a _ActConsentDirective

4.3.2.20425.2 Expansion

This expansion generated 19 Apr 2017

This value set contains 10 concepts

Expansion based on http://hl7.org/fhir/v3/ActCode version 2016-11-11

All codes from system http://hl7.org/fhir/v3/ActCode

Code | Display | Definition
_ActConsentDirective | ActConsentDirective | Specifies the type of agreement between one or more grantor and grantee in which rights and obligations related to one or more shared items of interest are allocated. Usage Note: Such agreements may be considered "consent directives" or "contracts" depending on the context, and are considered closely related or synonymous from a legal perspective. Examples: Healthcare Privacy Consent Directive permitting or restricting in whole or part the collection, access, use, and disclosure of health information, and any associated handling caveats. Healthcare Medical Consent Directive to receive medical procedures after being informed of risks and benefits, thereby reducing the grantee's liability. Research Informed Consent for participation in clinical trials and disclosure of health information after being informed of risks and benefits, thereby reducing the grantee's liability. Substitute decision maker delegation in which the grantee assumes responsibility to act on behalf of the grantor. Contracts in which the agreement requires assent/dissent by the grantor of terms offered by a grantee, a consumer opts out of an "award" system for use of a retailer's marketing or credit card vendor's point collection cards in exchange for allowing purchase tracking and profiling. A mobile device or App privacy policy and terms of service to which a user must agree in whole or in part in order to utilize the service. Agreements between a client and an authorization server or between an authorization server and a resource operator and/or resource owner permitting or restricting e.g., collection, access, use, and disclosure of information, and any associated handling caveats.
EMRGONLY | emergency only | This general consent directive specifically limits disclosure of health information for purpose of emergency treatment. Additional parameters may further limit the disclosure to specific users, roles, duration, types of information, and impose uses obligations. Definition: Opt-in to disclosure of health information for emergency only consent directive.

GRANTORCHOICE | grantor choice | A grantor's terms of agreement to which a grantee may assent or dissent, and which may include an opportunity for a grantee to request restrictions or extensions. Comment: A grantor typically is able to stipulate preferred terms of agreement when the grantor has control over the topic of the agreement, which a grantee must accept in full or may be offered an opportunity to extend or restrict certain terms. Usage Note: If the grantor's term of agreement must be accepted in full, then this is considered "basic consent". If a grantee is offered an opportunity to extend or restrict certain terms, then the agreement is considered "granular consent". Examples: Healthcare: A PHR account holder [grantor] may require any PHR user [grantee] to accept the terms of agreement in full, or may permit a PHR user to extend or restrict terms selected by the account holder or requested by the PHR user. Non-healthcare: The owner of a resource server [grantor] may require any authorization server [grantee] to meet authorization requirements stipulated in the grantor's terms of agreement.

IMPLIED | implied consent | A grantor's presumed assent to the grantee's terms of agreement is based on the grantor's behavior, which may result from not expressly assenting to the consent directive offered, or from having no right to assent or dissent offered by the grantee. Comment: Implied or "implicit" consent occurs when the behavior of the grantor is understood by a reasonable person to signal agreement to the grantee's terms. Usage Note: Implied consent with no opportunity to assent or dissent to certain terms is considered "basic consent". Examples: Healthcare: A patient schedules an appointment with a provider, and either does not take the opportunity to expressly assent or dissent to the provider's consent directive, does not have an opportunity to do so, as in the case where emergency care is required, or simply behaves as though the patient [grantor] agrees to the rights granted to the provider [grantee] in an implicit consent directive. An injured and unconscious patient is deemed to have assented to emergency treatment by those permitted to do so under jurisdictional laws, e.g., Good Samaritan laws. Non-healthcare: Upon receiving a driver's license, the driver is deemed to have assented without explicitly consenting to undergoing field sobriety tests. A corporation that does business in a foreign nation is deemed to have deemed to have assented without explicitly consenting to abide by that nation's laws.

IMPLIEDD | implied consent with opportunity to dissent | A grantor's presumed assent to the grantee's terms of agreement, which is based on the grantor's behavior, and includes a right to dissent to certain terms. Comment: A grantor assenting to the grantee's terms of agreement may or may not exercise a right to dissent to grantor selected terms or to grantee's selected terms to which a grantor may dissent. Usage Note: Implied or "implicit" consent with an "opportunity to dissent" occurs when the grantor's behavior is understood by a reasonable person to signal assent to the grantee's terms of agreement whether the grantor requests or the grantee approves further restrictions, is considered "granular consent". Examples: Healthcare Examples: A healthcare provider deems a patient's assent to disclosure of health information to family members and friends, but offers an opportunity or permits the patient to dissent to such disclosures. A health information exchanges deems a patient to have assented to disclosure of health information for treatment purposes, but offers the patient an opportunity to dissents to disclosure to particular provider organizations. Non-healthcare Examples: A bank deems a banking customer's assent to specified collection, access, use, or disclosure of financial information as a requirement of holding a bank account, but provides the user an opportunity to limit third-party collection, access, use or disclosure of that information for marketing purposes.

NOCONSENT | no consent | No notification or opportunity is provided for a grantor to assent or dissent to a grantee's terms of agreement. Comment: A "No Consent" policy scheme provides no opportunity for accommodation of an individual's preferences, and may not comply with Fair Information Practice Principles [FIPP] by enabling the data subject to object, access collected information, correct errors, or have accounting of disclosures. Usage Note: The grantee's terms of agreement, may be available to the grantor by reviewing the grantee's privacy policies, but there is no notice by which a grantor is apprised of the policy directly or able to acknowledge. Examples: Healthcare: Without notification or an opportunity to assent or dissent, a patient's health information is automatically included in and available (often according to certain rules) through a health information exchange. Note that this differs from implied consent, where the patient is assumed to have consented. Without notification or an opportunity to assent or dissent, a patient's health information is collected, accessed, used, or disclosed for research, public health, security, fraud prevention, court order, or law enforcement. Non-healthcare: Without notification or an opportunity to assent or dissent, a consumer's healthcare or non-healthcare internet searches are aggregated for secondary uses such as behavioral tracking and profiling. Without notification or an opportunity to assent or dissent, a consumer's location and activities in a shopping mall are tracked by RFID tags on purchased items.

NOPP | notice of privacy practices | Acknowledgement of custodian notice of privacy practices. Usage Notes: This type of consent directive acknowledges a custodian's notice of privacy practices including its permitted collection, access, use and disclosure of health information to users and for purposes of use specified.

OPTIN | opt-in | A grantor's assent to the terms of an agreement offered by a grantee without an opportunity for to dissent to any terms. Comment: Acceptance of a grantee's terms pertaining, for example, to permissible activities, purposes of use, handling caveats, expiry date, and revocation policies. Usage Note: Opt-in with no opportunity for a grantor to restrict certain permissions sought by the grantee is considered "basic consent". Examples: Healthcare: A patient [grantor] signs a provider's [grantee's] consent directive form, which lists permissible collection, access, use, or disclosure activities, purposes of use, handling caveats, and revocation policies. Non-healthcare: An employee [grantor] signs an employer's [grantee's] non-disclosure and non-compete agreement.

OPTINR | opt-in with restrictions | A grantor's assent to the grantee's terms of an agreement with an opportunity for to dissent to certain grantor or grantee selected terms. Comment: A grantor dissenting to the grantee's terms of agreement may or may not exercise a right to assent to grantor's pre-approved restrictions or to grantee's selected terms to which a grantor may dissent. Usage Note: Opt-in with restrictions is considered "granular consent" because the grantor has an opportunity to narrow the permissions sought by the grantee. Examples: Healthcare: A patient assent to grantee's consent directive terms for collection, access, use, or disclosure of health information, and dissents to disclosure to certain recipients as allowed by the provider's pre-approved restriction list. Non-Healthcare: A cell phone user assents to the cell phone's privacy practices and terms of use, but dissents from location tracking by turning off the cell phone's tracking capability.

OPTOUT | op-out | A grantor's dissent to the terms of agreement offered by a grantee without an opportunity for to assent to any terms. Comment: Rejection of a grantee's terms of agreement pertaining, for example, to permissible activities, purposes of use, handling caveats, expiry date, and revocation policies. Usage Note: Opt-out with no opportunity for a grantor to permit certain permissions sought by the grantee is considered "basic consent". Examples: Healthcare: A patient [grantor] declines to sign a provider's [grantee's] consent directive form, which lists permissible collection, access, use, or disclosure activities, purposes of use, handling caveats, revocation policies, and consequences of not assenting. Non-healthcare: An employee [grantor] refuses to sign an employer's [grantee's] agreement not to join unions or participate in a strike where state law protects employee's collective bargaining rights. A citizen [grantor] refuses to enroll in mandatory government [grantee] health insurance based on religious beliefs, which is an exemption.

OPTOUTE | opt-out with exceptions | A grantor's dissent to the grantee's terms of agreement except for certain grantor or grantee selected terms. Comment: A rejection of a grantee's terms of agreement while assenting to certain permissions sought by the grantee or requesting approval of additional grantor terms. Usage Note: Opt-out with exceptions is considered a "granular consent" because the grantor has an opportunity to accept certain permissions sought by the grantee or request additional grantor terms, while rejecting other grantee terms. Examples: Healthcare: A patient [grantor] dissents to a health information exchange consent directive with the exception of disclosure based on a limited "time to live" shared secret [e.g., a token or password], which the patient can give to a provider when seeking care. Non-healthcare: A social media user [grantor] dissents from public access to their account, but assents to access to a circle of friends.

4.3.2.20428 HL7 v3 Value Set InformationSensitivityPolicy

URL: https://hl7.org/fhir/STU3/v3/InformationSensitivityPolicy/vs.html

This page is part of the FHIR Specification (v3.0.2: STU 3). The current version which supercedes this version is 4.0.1. For a full list of available versions, see the Directory of published versions

Vocabulary Work Group | Maturity Level: N/A | External | Use Context: Any

This value set (http://hl7.org/fhir/ValueSet/v3-InformationSensitivityPolicy) is defined as part of HL7 v3. Related FHIR content: InformationSensitivityPolicy.

Summary

Defining URL: | http://hl7.org/fhir/ValueSet/v3-InformationSensitivityPolicy

Name: | InformationSensitivityPolicy

Definition: | Sensitivity codes are not useful for interoperability outside of a policy domain because sensitivity policies are typically localized and vary drastically across policy domains even for the same information category because of differing organizational business rules, security policies, and jurisdictional requirements. For example, an "employee" sensitivity code would make little sense for use outside of a policy domain. "Taboo" would rarely be useful outside of a policy domain unless there are jurisdictional requirements requiring that a provider disclose sensitive information to a patient directly. Sensitivity codes may be more appropriate in a legacy system's Master Files in order to notify those who access a patient's orders and observations about the sensitivity policies that apply. Newer systems may have a security engine that uses a sensitivity policy's criteria directly. The specializable Sensitivity Act.code may be useful in some scenarious if used in combination with a sensitivity identifier and/or Act.title.

OID: | 2.16.840.1.113883.1.11.20428 (for OID based terminology systems)

Source Resource | XML / JSON

This value set is not currently used

4.3.2.20428.1 Content Logical Definition

This value set includes codes from the following code systems:

* Include codes from http://hl7.org/fhir/v3/ActCode where concept is-a _InformationSensitivityPolicy

4.3.2.20428.2 Expansion

This expansion generated 19 Apr 2017

This value set contains 29 concepts

Expansion based on http://hl7.org/fhir/v3/ActCode version 2016-11-11

All codes from system http://hl7.org/fhir/v3/ActCode

Code | Display | Definition

_InformationSensitivityPolicy | InformationSensitivityPolicy | A mandate, obligation, requirement, rule, or expectation characterizing the value or importance of a resource and may include its vulnerability. (Based on ISO7498-2:1989. Note: The vulnerability of personally identifiable sensitive information may be based on concerns that the unauthorized disclosure may result in social stigmatization or discrimination.) Description: Types of Sensitivity policy that apply to Acts or Roles. A sensitivity policy is adopted by an enterprise or group of enterprises (a 'policy domain') through a formal data use agreement that stipulates the value, importance, and vulnerability of information. A sensitivity code representing a sensitivity policy may be associated with criteria such as categories of information or sets of information identifiers (e.g., a value set of clinical codes or branch in a code system hierarchy). These criteria may in turn be used for the Policy Decision Point in a Security Engine. A sensitivity code may be used to set the confidentiality code used on information about Acts and Roles to trigger the security mechanisms required to control how security principals (i.e., a person, a machine, a software application) may act on the information (e.g., collection, access, use, or disclosure). Sensitivity codes are never assigned to the transport or business envelope containing patient specific information being exchanged outside of a policy domain as this would disclose the information intended to be protected by the policy. When sensitive information is exchanged with others outside of a policy domain, the confidentiality code on the transport or business envelope conveys the receiver's responsibilities and indicates the how the information is to be safeguarded without unauthorized disclosure of the sensitive information. This ensures that sensitive information is treated by receivers as the sender intends, accomplishing interoperability without point to point negotiations. Usage Note: Sensitivity codes are not useful for interoperability outside of a policy domain because sensitivity policies are typically localized and vary drastically across policy domains even for the same information category because of differing organizational business rules, security policies, and jurisdictional requirements. For example, an employee's sensitivity code would make little sense for use outside of a policy domain. 'Taboo' would rarely be useful outside of a policy domain unless there are jurisdictional requirements requiring that a provider disclose sensitive information to a patient directly. Sensitivity codes may be more appropriate in a legacy system's Master Files in order to notify those who access a patient's orders and observations about the sensitivity policies that apply. Newer systems may have a security engine that uses a sensitivity policy's criteria directly. The specializable InformationSensitivityPolicy Act.code may be useful in some scenarios if used in combination with a sensitivity identifier and/or Act.title.

_ActInformationSensitivityPolicy | ActInformationSensitivityPolicy | Types of sensitivity policies that apply to Acts. Act.confidentialityCode is defined in the RIM as "constraints around appropriate disclosure of information about this Act, regardless of mood." Usage Note: ActSensitivity codes are used to bind information to an Act.confidentialityCode according to local sensitivity policy so that those confidentiality codes can then govern its handling across enterprises. Internally to a policy domain, however, local policies guide the access control system on how end users in that policy domain are able to use information tagged with these sensitivity values.

ETH | substance abuse information sensitivity | Policy for handling alcohol or drug-abuse information, which will be afforded heightened confidentiality. Information handling protocols based on organizational policies related to alcohol or drug-abuse information that is deemed sensitive. Usage Note: If there is a jurisdictional mandate, then use the applicable ActPrivacyLaw code system, and specify the law rather than or in addition to this more generic code.

GDIS | genetic disease information sensitivity | Policy for handling genetic disease information, which will be afforded heightened confidentiality. Information handling protocols based on organizational policies related to genetic disease information that is deemed sensitive. Usage Note: If there is a jurisdictional mandate, then use the applicable ActPrivacyLaw code system, and specify the law rather than or in addition to this more generic code.

HIV | HIV/AIDS information sensitivity | Policy for handling HIV or AIDS information, which will be afforded heightened confidentiality. Information handling protocols based on organizational policies related to HIV or AIDS information that is deemed sensitive. Usage Note: If there is a jurisdictional mandate, then use the applicable ActPrivacyLaw code system, and specify the law rather than or in addition to this more generic code.

PSY | psychiatry information sensitivity | Policy for handling psychiatry information, which will be afforded heightened confidentiality. Information handling protocols based on organizational policies related to psychiatry information that is deemed sensitive. Usage Note: If there is a jurisdictional mandate, then use the applicable ActPrivacyLaw code system, and specify the law rather than or in addition to this more generic code.

SCA | sickle cell anemia | Policy for handling sickle cell disease information, which is afforded heightened confidentiality. Information handling protocols are based on organizational policies related to sickle cell disease information, which is deemed sensitive. Usage Note: If there is a jurisdictional mandate, then the Act valued with this ActCode should be associated with an Act valued with any applicable laws from the ActPrivacyLaw code system.

SOC | social services sensitivity | Information about provision of social services. Usage Note: This is a temporary addition to FHIR to be proposed in harmonization.

SDV | sexual assault, abuse, or domestic violence information sensitivity | Policy for handling sexual assault, abuse, or domestic violence information, which will be afforded heightened confidentiality. Information handling protocols based on organizational policies related to sexual assault, abuse, or domestic violence information that is deemed sensitive. Usage Note: If there is a jurisdictional mandate, then use the applicable ActPrivacyLaw code system, and specify the law rather than or in addition to this more generic code.

SEX | sexuality and reproductive health information sensitivity | Policy for handling sexuality and reproductive health information, which will be afforded heightened confidentiality. Information handling protocols based on organizational policies related to sexuality and reproductive health information that is deemed sensitive. Usage Note: If there is a jurisdictional mandate, then use the applicable ActPrivacyLaw code system, and specify the law rather than or in addition to this more generic code.

STD | sexually transmitted disease information sensitivity | Policy for handling sexually transmitted disease information, which will be afforded heightened confidentiality. Information handling protocols based on organizational policies related to sexually transmitted disease information that is deemed sensitive. Usage Note: If there is a jurisdictional mandate, then use the applicable ActPrivacyLaw code system, and specify the law rather than or in addition to this more generic code.

TBOO | taboo | Policy for handling information not to be initially disclosed or discussed with patient except by a physician assigned to patient in this case. Information handling protocols based on organizational policies related to sensitive patient information that must be initially discussed with the patient by an attending physician before being disclosed to the patient. Usage Note: If there is a jurisdictional mandate, then use the applicable ActPrivacyLaw code system, and specify the law rather than or in addition to this more generic code. Open Issue: This definition conflates a rule and a characteristic, and there may be a similar issue with ts sibling codes.

SICKLE | sickle cell | Types of sensitivity policies that apply to Acts. Act.confidentialityCode is defined in the RIM as "constraints around appropriate disclosure of information about this Act, regardless of mood." Usage Note: ActSensitivity codes are used to bind information to an Act.confidentialityCode according to local sensitivity policy so that those confidentiality codes can then govern its handling across enterprises. Internally to a policy domain, however, local policies guide the access control system on how end users in that policy domain are able to use information tagged with these sensitivity values.

_EntitySensitivityPolicyType | EntityInformationSensitivityPolicy | Types of sensitivity policies that may apply to a sensitive attribute on an Entity. Usage Note: EntitySensitivity codes are used to convey a policy that is applicable to sensitive information conveyed by an entity attribute. May be used to bind a Role.confidentialityCode associated with an Entity per organizational policy. Role.confidentialityCode is defined in the RIM as "an indication of the appropriate disclosure of information about this Role with respect to the playing Entity."

DEMO | all demographic information sensitivity | Policy for handling all demographic information about an information subject, which will be afforded heightened confidentiality. Policies may govern sensitivity of information related to all demographic about an information subject, the disclosure of which could impact the privacy, well-being, or safety of that subject. Usage Note: If there is a jurisdictional mandate, then use the applicable ActPrivacyLaw code system, and specify the law rather than or in addition to this more generic code.

DOB | date of birth information sensitivity | Policy for handling information related to an information subject's date of birth, which will be afforded heightened confidentiality.Policies may govern sensitivity of information related to an information subject's date of birth, the disclosure of which could impact the privacy, well-being, or safety of that subject. Usage Note: If there is a jurisdictional mandate, then use the applicable ActPrivacyLaw code system, and specify the law rather than or in addition to this more generic code.

GENDER | gender and sexual orientation information sensitivity | Policy for handling information related to an information subject's gender and sexual orientation, which will be afforded heightened confidentiality. Policies may govern sensitivity of information related to an information subject's gender and sexual orientation, the disclosure of which could impact the privacy, well-being, or safety of that subject. Usage Note: If there is a jurisdictional mandate, then use the applicable ActPrivacyLaw code system, and specify the law rather than or in addition to this more generic code.

LIVARG | living arrangement information sensitivity | Policy for handling information related to an information subject's living arrangement, which will be afforded heightened confidentiality. Policies may govern sensitivity of information related to an information subject's living arrangement, the disclosure of which could impact the privacy, well-being, or safety of that subject. Usage Note: If there is a jurisdictional mandate, then use the applicable ActPrivacyLaw code system, and specify the law rather than or in addition to this more generic code.

MARST | marital status information sensitivity | Policy for handling information related to an information subject's marital status, which will be afforded heightened confidentiality. Policies may govern sensitivity of information related to an information subject's marital status, the disclosure of which could impact the privacy, well-being, or safety of that subject. Usage Note: If there is a jurisdictional mandate, then use the applicable ActPrivacyLaw code system, and specify the law rather than or in addition to this more generic code.

RACE | race information sensitivity | Policy for handling information related to an information subject's race, which will be afforded heightened confidentiality. Policies may govern sensitivity of information related to an information subject's race, the disclosure of which could impact the privacy, well-being, or safety of that subject. Usage Note: If there is a jurisdictional mandate, then use the applicable ActPrivacyLaw code system, and specify the law rather than or in addition to this more generic code.

REL | religion information sensitivity | Policy for handling information related to an information subject's religious affiliation, which will be afforded heightened confidentiality. Policies may govern sensitivity of information related to an information subject's religion, the disclosure of which could impact the privacy, well-being, or safety of that subject. Usage Notes: If there is a jurisdictional mandate, then use the applicable ActPrivacyLaw code system, and specify the law rather than or in addition to this more generic code.

_RoleInformationSensitivityPolicy | RoleInformationSensitivityPolicy | Types of sensitivity policies that apply to Roles. Usage Notes: RoleSensitivity codes are used to bind information to a Role.confidentialityCode per organizational policy. Role.confidentialityCode is defined in the RIM as "an indication of the appropriate disclosure of information about this Role with respect to the playing Entity."

B | business information sensitivity | Policy for handling trade secrets such as financial information or intellectual property, which will be afforded heightened confidentiality. Description: Since the service class can represent knowledge structures that may be considered a trade or business secret, there is sometimes (though rarely) the need to flag those items as of business level confidentiality. Usage Notes: No patient related information may ever be of this confidentiality level. If there is a jurisdictional mandate, then use the applicable ActPrivacyLaw code system, and specify the law rather than or in addition to this more generic code.

EMPL | employer information sensitivity | Policy for handling information related to an employer which is deemed classified to protect an employee who is the information subject, and which will be afforded heightened confidentiality. Description: Policies may govern sensitivity of information related to an employer, such as law enforcement or national security, the identity of which could impact the privacy, well-being, or safety of an information subject who is an employee. Usage Notes: If there is a jurisdictional mandate, then use the applicable ActPrivacyLaw code system, and specify the law rather than or in addition to this more generic code.

LOCIS | location information sensitivity | Policy for handling information related to the location of the information subject, which will be afforded heightened confidentiality. Description: Policies may govern sensitivity of information related to the location of the information subject, the disclosure of which could impact the privacy, well-being, or safety of that subject. Usage Notes: If there is a jurisdictional mandate, then use the applicable ActPrivacyLaw code system, and specify the law rather than or in addition to this more generic code.

SSP | sensitive service provider information sensitivity | Policy for handling information related to a provider of sensitive services, which will be afforded heightened confidentiality. Description: Policies may govern sensitivity of information related to providers who deliver sensitive healthcare services in order to protect the privacy, well-being, and safety of the provider and of patients receiving sensitive services. Usage Notes: If there is a jurisdictional mandate, then use the applicable ActPrivacyLaw code system, and specify the law rather than or in addition to this more generic code.

ADOL | adolescent information sensitivity | Policy for handling information related to an adolescent, which will be afforded heightened confidentiality per applicable organizational or jurisdictional policy. An enterprise may have a policy that requires that adolescent patient information be provided heightened confidentiality. Information deemed sensitive typically includes health information and patient role information including patient status, demographics, next of kin, and location. Usage Note: For use within an enterprise in which an adolescent is the information subject. If there is a jurisdictional mandate, then use the applicable ActPrivacyLaw code system, and specify the law rather than or in addition to this more generic code.

CEL | celebrity information sensitivity | Policy for handling information related to a celebrity (people of public interest (VIP), which will be afforded heightened confidentiality. Celebrities are people of public interest (VIP) about whose information an enterprise may have a policy that requires heightened confidentiality. Information deemed sensitive may include health information and patient role information including patient status, demographics, next of kin, and location. Usage Note: For use within an enterprise in which the information subject is deemed a celebrity or very important person. If there is a jurisdictional mandate, then use the applicable ActPrivacyLaw code system, and specify the law rather than or in addition to this more generic code.

DIA | diagnosis information sensitivity | Policy for handling information related to a diagnosis, health condition or health problem, which will be afforded heightened confidentiality. Diagnostic, health condition or health problem related information may be deemed sensitive by organizational policy, and require heightened confidentiality. Usage Note: For use within an enterprise that provides heightened confidentiality to diagnostic, health condition or health problem related information deemed sensitive. If there is a jurisdictional mandate, then use the applicable ActPrivacyLaw code system, and specify the law rather than or in addition to this more generic code.

DRGIS | drug information sensitivity | Policy for handling information related to a drug, which will be afforded heightened confidentiality. Drug information may be deemed sensitive by organizational policy, and require heightened confidentiality. Usage Note: For use within an enterprise that provides heightened confidentiality to drug information deemed sensitive. If there is a jurisdictional mandate, then use the applicable ActPrivacyLaw code system, and specify the law rather than or in addition to this more generic code.

EMP | employee information sensitivity | Policy for handling information related to an employee, which will be afforded heightened confidentiality. When a patient is an employee, an enterprise may have a policy that requires heightened confidentiality. Information deemed sensitive typically includes health information and patient role information including patient status, demographics, next of kin, and location. Usage Note: Policy for handling information related to an employee, which will be afforded heightened confidentiality. Description: When a patient is an employee, an enterprise may have a policy that requires heightened confidentiality. Information deemed sensitive typically includes health information and patient role information including patient status, demographics, next of kin, and location.

PDS | patient default sensitivity | Policy for handling information reported by the patient about another person, e.g., a family member, which will be afforded heightened confidentiality. Sensitive information reported by the patient about another person, e.g., family members may be deemed sensitive by default. The flag may be set or cleared on patient's request. Usage Note: For sensitive information relayed by or about a patient, which is deemed sensitive within the enterprise (i.e., by default regardless of whether the patient requested that the information be deemed sensitive.) If there is a jurisdictional mandate, then use the applicable ActPrivacyLaw code system, and specify the law rather than or in addition to this more generic code.

PRS | patient requested sensitivity | For sensitive information relayed by or about a patient, which is deemed sensitive within the enterprise (i.e., by default regardless of whether the patient requested that the information be deemed sensitive.) If there is a jurisdictional mandate, then use the applicable ActPrivacyLaw code system, and specify the law rather than or in addition to this more generic code. Usage Note: For use within an enterprise that provides heightened confidentiality to certain types of information designated by a patient as sensitive. If there is a jurisdictional mandate, then use the applicable ActPrivacyLaw code system, and specify the law rather than or in addition to this more generic code.

4.3.2.20444 HL7 v3 Value Set SecurityPolicy

URL: https://hl7.org/fhir/STU3/v3/SecurityPolicy/vs.html

This page is part of the FHIR Specification (v3.0.2: STU 3). The current version which supercedes this version is 4.0.1. For a full list of available versions, see the Directory of published versions

Vocabulary Work Group | Maturity Level: N/A | External | Use Context: Any

This value set (http://hl7.org/fhir/ValueSet/v3-SecurityPolicy) is defined as part of HL7 v3. Related FHIR content: SecurityPolicy.

Summary

Defining URL: | http://hl7.org/fhir/ValueSet/v3-SecurityPolicy

Name: | SecurityPolicy

Definition: | Types of security policies that further specify the ActClassPolicy value set. Examples: encrypt prohibit redisclosure without consent directive

OID: | 2.16.840.1.113883.1.11.20444 (for OID based terminology systems)

Source Resource | XML / JSON

This value set is not currently used

4.3.2.20444.1 Content Logical Definition

This value set includes codes from the following code systems:

* Include codes from http://hl7.org/fhir/v3/ActCode where concept is-a SecurityPolicy

4.3.2.20444.2 Expansion

This expansion generated 19 Apr 2017

This value set contains 48 concepts

Expansion based on http://hl7.org/fhir/v3/ActCode version 2016-11-11

All codes from system http://hl7.org/fhir/v3/ActCode

Code | Display | Definition

SecurityPolicy | security policy | Types of security policies that further specify the ActClassPolicy value set. Examples: obligation to encrypt refrain from redisclosure without consent

ObligationPolicy | obligation policy | Conveys the mandated workflow action that an information custodian, receiver, or user must perform. Usage Notes: Per ISO 22600-2, ObligationPolicy instances 'are event-triggered and define actions to be performed by manager agent'. Per HL7 Composite Security and Privacy Domain Analysis Model: This value set refers to the action required to receive the permission specified in the privacy rule. Per

OASIS XACML, an obligation is an operation specified in a policy or policy that is performed in conjunction with the enforcement of an access control decision.

ANONY | anonymize | Custodian system must remove any information that could result in identifying the information subject.

AOD | accounting of disclosure | Custodian system must make available to an information subject upon request an accounting of certain disclosures of the individualâ€™s protected health information over a period of time. Policy may dictate that the accounting include information about the information disclosed, the date of disclosure, the identification of the receiver, the purpose of the disclosure, the time in which the disclosing entity must provide a response and the time period for which accountings of disclosure can be requested.

AUDIT | audit | Custodian system must monitor systems to ensure that all users are authorized to operate on information objects.

AUDTR | audit trail | Custodian system must monitor and maintain retrievable log for each user and operation on information.

CPLYCC | comply with confidentiality code | Custodian security system must retrieve, evaluate, and comply with the information handling directions of the Confidentiality Code associated with an information target.

CPLYCD | comply with consent directive | Custodian security system must retrieve, evaluate, and comply with applicable information subject consent directives.

CPLYJPP | comply with jurisdictional privacy policy | Custodian security system must retrieve, evaluate, and comply with applicable jurisdictional privacy policies associated with the target information.

CPLYOPP | comply with organizational privacy policy | Custodian security system must retrieve, evaluate, and comply with applicable organizational privacy policies associated with the target information.

CPLYOSP | comply with organizational security policy | Custodian security system must retrieve, evaluate, and comply with the organizational security policies associated with the target information.

CPLYPOL | comply with policy | Custodian security system must retrieve, evaluate, and comply with applicable policies associated with the target information.

DECLASSIFYLABEL | declassify security label | Custodian security system must declassify information assigned security labels by instantiating a new version of the classified information so as to break the binding of the classifying security label when assigning a new security label that marks the information as unclassified in accordance with applicable jurisdictional privacy policies associated with the target information. The system must retain an immutable record of the previous assignment and binding.

DEID | deidentify | Custodian system must strip information of data that would allow the identification of the source of the information or the information subject.

DELAU | delete after use | Custodian system must remove target information from access after use.

DOWNGRDLABEL | downgrade security label | Custodian security system must downgrade information assigned security labels by instantiating a new version of the classified information so as to break the binding of the classifying security label when assigning a new security label that marks the information as classified at a less protected level in accordance with applicable jurisdictional privacy policies associated with the target information. The system must retain an immutable record of the previous assignment and binding.

DRIVLABEL | derive security label | Custodian security system must assign and bind security labels derived from compilations of information by aggregation or disaggregation in order to classify information compiled in the information systems under its control for collection, access, use and disclosure in accordance with applicable jurisdictional privacy policies associated with the target information. The system must retain an immutable record of the previous assignment and binding.

ENCRYPT | encrypt | Custodian system must render information unreadable by algorithmically transforming plaintext into ciphertext. Usage Notes: A mathematical transposition of a file or data stream so that it cannot be deciphered at the receiving end without the proper key. Encryption is a security feature that assures that only the parties who are supposed to be participating in a videoconference or data transfer are able to do so. It can include a password, public and private keys, or a complex combination of all. (Per Infoway.)

ENCRYPTR | encrypt at rest | Custodian system must render information unreadable and unusable by algorithmically transforming plaintext into ciphertext when "at rest" or in storage.

ENCRYPTT | encrypt in transit | Custodian system must render information unreadable and unusable by algorithmically transforming plaintext into ciphertext while "in transit" or being transported by any means.

ENCRYPTU | encrypt in use | Custodian system must render information unreadable and unusable by algorithmically transforming plaintext into ciphertext while in use such that operations permitted on the target information are limited by the license granted to the end user.

HUAPRV | human approval | Custodian system must require human review and approval for permission requested.

LABEL | assign security label | Custodian security system must assign and bind security labels in order to classify information created in the information systems under its control for collection, access, use and disclosure in accordance with applicable jurisdictional privacy policies associated with the target information. The system must retain an immutable record of the assignment and binding. Usage Note: In security systems, security policy label assignments do not change, they may supersede prior assignments, and such reassignments are always tracked for auditing and other purposes.

MASK | mask | Custodian system must render information unreadable and unusable by algorithmically transforming plaintext into ciphertext. User may be provided a key to decrypt per license or "shared secret".

MINEC | minimum necessary | Custodian must limit access and disclosure to the minimum information required to support an authorized user's purpose of use. Usage Note: Limiting the information available for access and disclosure to that an authorized user or receiver "needs to know" in order to perform permitted workflow or purpose of use.

PERSISTLABEL | persist security label | Custodian security system must persist the binding of security labels to classify information received or imported by information systems under its control for collection, access, use and disclosure in accordance with applicable jurisdictional privacy policies associated with the target information. The system must retain an immutable record of the assignment and binding.

PRIVMARK | privacy mark | Custodian must create and/or maintain human readable security label tags as required by policy. Map: Aligns with ISO 22600-3 Section A.3.4.3 description of privacy mark: "If present, the privacy-mark is not used for access control. The content of the privacy-mark may be defined by the security policy in force (identified by the security-policy-identifier) which may define a list of values to be used. Alternately, the value may be determined by the originator of the security-label."

PSEUD | pseudonymize | Custodian system must strip information of data that would allow the identification of the source of the information or the information subject. Custodian may retain a key to relink data necessary to reidentify the information subject.

REDACT | redact | Custodian system must remove information, which is not authorized to be access, used, or disclosed from records made available to otherwise authorized users.

UPGRDLABEL | upgrade security label | Custodian security system must declassify information assigned security labels by instantiating a new version of the classified information so as to break the binding of the classifying security label when assigning a new security label that marks the information as classified at a more protected level in accordance with applicable jurisdictional privacy policies associated with the target information. The system must retain an immutable record of the previous assignment and binding.

RefrainPolicy | refrain policy | Conveys prohibited actions which an information custodian, receiver, or user is not permitted to perform unless otherwise authorized or permitted under specified circumstances. Usage Notes: ISO 22600-2 species that a Refrain Policy "defines actions the subjects must refrain from performing". Per HL7 Composite Security and Privacy Domain Analysis Model: May be used to indicate that a specific action is prohibited based on specific access control attributes e.g., purpose of use, information type, user role, etc.

NOAUTH | no disclosure without subject authorization | Prohibition on disclosure without information subject's authorization.

NOCOLLECT | no collection | Prohibition on collection or storage of the information.

NODSCLCD | no disclosure without consent directive | Prohibition on disclosure without organizational approved patient restriction.

NODSCLCDS | no disclosure without information subject's consent directive | Prohibition on disclosure without a consent directive from the information subject.

NOINTEGRATE | no integration | Prohibition on Integration into other records.

NOLIST | no unlisted entity disclosure | Prohibition on disclosure except to entities on specific access list.

NOMOU | no disclosure without MOU | Prohibition on disclosure without an interagency service agreement or memorandum of understanding (MOU).

NOORGPOL | no disclosure without organizational authorization | Prohibition on disclosure without organizational authorization.

NOPAT | no disclosure to patient, family or caregivers without attending provider's authorization | Prohibition on disclosing information to patient, family or caregivers without attending provider's authorization. Usage Note: The information may be labeled with the ActInformationSensitivity TBOO code, triggering application of this RefrainPolicy code as a handling caveat controlling access. Maps to FHIR NOPAT: Typically, this is used on an Alert resource, when the alert records information on patient abuse or non-compliance. FHIR print name is "keep information from patient". Maps to the French realm - code: INVISIBLE_PATIENT. displayName: Document non visible par le patient codingScheme: 1.2.250.1.213.1.1.4.13 French use case: A label for documents that the author chose to hide from the patient until the content can be disclose to the patient in a face to face meeting between a healthcare professional and the patient (in French law some results like cancer diagnosis or AIDS diagnosis must be announced to the patient by a healthcare professional and should not be find out by the patient alone).

NOPERSISTP | no collection beyond purpose of use | Prohibition on collection of the information beyond time necessary to accomplish authorized purpose of use is prohibited.

NORDSCLCD | no redisclosure without consent directive | Prohibition on redisclosure without patient consent directive.

NORDSCLCDS | no redisclosure without information subject's consent directive | Prohibition on redisclosure without a consent directive from the information subject.

NORDSCLW | no disclosure without jurisdictional authorization | Prohibition on disclosure without authorization under jurisdictional law.

NORELINK | no relinking | Prohibition on associating de-identified or pseudonymized information with other information in a manner that could or does result in disclosing information intended to be masked.

NOREUSE | no reuse beyond purpose of use | Prohibition on use of the information beyond the purpose of use initially authorized.

NOVIP | no unauthorized VIP disclosure | Prohibition on disclosure except to principals with access permission to specific VIP information.

ORCON | no disclosure without originator authorization | Prohibition on disclosure except as permitted by the information originator.

4.3.2.20445 HL7 v3 Value Set ObligationPolicy

URL: https://hl7.org/fhir/STU3/v3/ObligationPolicy/vs.html

This page is part of the FHIR Specification (v3.0.2: STU 3). The current version which supercedes this version is 4.0.1. For a full list of available versions, see the Directory of published versions

Vocabulary Work Group | Maturity Level: N/A | External | Use Context: Any

This value set (http://hl7.org/fhir/ValueSet/v3-ObligationPolicy) is defined as part of HL7 v3. Related FHIR content: ObligationPolicy.

Summary

Defining URL: | http://hl7.org/fhir/ValueSet/v3-ObligationPolicy

Name: | ObligationPolicy

Definition: | Conveys the mandated workflow action that an information custodian, receiver, or user must perform. Examples: encrypt Usage Note: Per OASIS XACML, an obligation is an operation specified in a policy or policy that is performed in conjunction with the enforcement of an access control decision.

OID: | 2.16.840.1.113883.1.11.20445 (for OID based terminology systems)

Source Resource | XML / JSON

This value set is not currently used

4.3.2.20445.1 Content Logical Definition

This value set includes codes from the following code systems:

* Include codes from http://hl7.org/fhir/v3/ActCode where concept is-a ObligationPolicy

4.3.2.20445.2 Expansion

This expansion generated 19 Apr 2017

This value set contains 29 concepts

Expansion based on http://hl7.org/fhir/v3/ActCode version 2016-11-11

All codes from system http://hl7.org/fhir/v3/ActCode

Code | Display | Definition

ObligationPolicy | obligation policy | Conveys the mandated workflow action that an information custodian, receiver, or user must perform. Usage Notes: Per ISO 22600-2, ObligationPolicy instances 'are event-triggered and define actions to be performed by manager agent'. Per HL7 Composite Security and Privacy Domain Analysis Model: This value set refers to the action required to receive the permission specified in the privacy rule. Per OASIS XACML, an obligation is an operation specified in a policy or policy that is performed in conjunction with the enforcement of an access control decision.

ANONY | anonymize | Custodian system must remove any information that could result in identifying the information subject.

AOD | accounting of disclosure | Custodian system must make available to an information subject upon request an accounting of certain disclosures of the individualâ€™s protected health information over a period of time. Policy may dictate that the accounting include information about the information disclosed, the date of disclosure, the identification of the receiver, the purpose of the disclosure, the time in which the disclosing entity must provide a response and the time period for which accountings of disclosure can be requested.

AUDIT | audit | Custodian system must monitor systems to ensure that all users are authorized to operate on information objects.

AUDTR | audit trail | Custodian system must monitor and maintain retrievable log for each user and operation on information.

CPLYCC | comply with confidentiality code | Custodian security system must retrieve, evaluate, and comply with the information handling directions of the Confidentiality Code associated with an information target.

CPLYCD | comply with consent directive | Custodian security system must retrieve, evaluate, and comply with applicable information subject consent directives.

CPLYJPP | comply with jurisdictional privacy policy | Custodian security system must retrieve, evaluate, and comply with applicable jurisdictional privacy policies associated with the target information.

CPLYOPP | comply with organizational privacy policy | Custodian security system must retrieve, evaluate, and comply with applicable organizational privacy policies associated with the target information.

CPLYOSP | comply with organizational security policy | Custodian security system must retrieve, evaluate, and comply with the organizational security policies associated with the target information.

CPLYPOL | comply with policy | Custodian security system must retrieve, evaluate, and comply with applicable policies associated with the target information.

DECLASSIFYLABEL | declassify security label | Custodian security system must declassify information assigned security labels by instantiating a new version of the classified information so as to break the binding of the classifying security label when assigning a new security label that marks the information as unclassified in accordance with applicable jurisdictional privacy policies associated with the target information. The system must retain an immutable record of the previous assignment and binding.

DEID | deidentify | Custodian system must strip information of data that would allow the identification of the source of the information or the information subject.

DELAU | delete after use | Custodian system must remove target information from access after use.

DOWNGRDLABEL | downgrade security label | Custodian security system must downgrade information assigned security labels by instantiating a new version of the classified information so as to break the binding of the classifying security label when assigning a new security label that marks the information as classified at a less protected level in accordance with applicable jurisdictional privacy policies associated with the target information. The system must retain an immutable record of the previous assignment and binding.

DRIVLABEL | derive security label | Custodian security system must assign and bind security labels derived from compilations of information by aggregation or disaggregation in order to classify information compiled in the information systems under its control for collection, access, use and disclosure in accordance with applicable jurisdictional privacy policies associated with the target information. The system must retain an immutable record of the previous assignment and binding.

ENCRYPT | encrypt | Custodian system must render information unreadable by algorithmically transforming plaintext into ciphertext. Usage Notes: A mathematical transposition of a file or data stream so that it cannot be deciphered at the receiving end without the proper key. Encryption is a security feature that assures that only the parties who are supposed to be participating in a videoconference or data transfer are able to do so. It can include a password, public and private keys, or a complex combination of all. (Per Infoway.)

ENCRYPTR | encrypt at rest | Custodian system must render information unreadable and unusable by algorithmically transforming plaintext into ciphertext when "at rest" or in storage.

ENCRYPTT | encrypt in transit | Custodian system must render information unreadable and unusable by algorithmically transforming plaintext into ciphertext while "in transit" or being transported by any means.

ENCRYPTU | encrypt in use | Custodian system must render information unreadable and unusable by algorithmically transforming plaintext into ciphertext while in use such that operations permitted on the target information are limited by the license granted to the end user.

HUAPRV | human approval | Custodian system must require human review and approval for permission requested.

LABEL | assign security label | Custodian security system must assign and bind security labels in order to classify information created in the information systems under its control for collection, access, use and disclosure in accordance with applicable jurisdictional privacy policies associated with the target information. The system must retain an immutable record of the assignment and binding. Usage Note: In security systems, security policy label assignments do not change, they may supersede prior assignments, and such reassignments are always tracked for auditing and other purposes.

MASK | mask | Custodian system must render information unreadable and unusable by algorithmically transforming plaintext into ciphertext. User may be provided a key to decrypt per license or "shared secret".

MINEC | minimum necessary | Custodian must limit access and disclosure to the minimum information required to support an authorized user's purpose of use. Usage Note: Limiting the information available for access and disclosure to that an authorized user or receiver "needs to know" in order to perform permitted workflow or purpose of use.

PERSISTLABEL | persist security label | Custodian security system must persist the binding of security labels to classify information received or imported by information systems under its control for collection, access, use and disclosure in accordance with applicable jurisdictional privacy policies associated with the target information. The system must retain an immutable record of the assignment and binding.

PRIVMARK | privacy mark | Custodian must create and/or maintain human readable security label tags as required by policy. Map: Aligns with ISO 22600-3 Section A.3.4.3 description of privacy mark: "If present, the privacy-mark is not used for access control. The content of the privacy-mark may be defined by the security policy in force (identified by the security-policy-identifier) which may define a list of values to be used. Alternately, the value may be determined by the originator of the security-label."

PSEUD | pseudonymize | Custodian system must strip information of data that would allow the identification of the source of the information or the information subject. Custodian may retain a key to relink data necessary to reidentify the information subject.

REDACT | redact | Custodian system must remove information, which is not authorized to be access, used, or disclosed from records made available to otherwise authorized users.

UPGRDLABEL | upgrade security label | Custodian security system must declassify information assigned security labels by instantiating a new version of the classified information so as to break the binding of the classifying security label when assigning a new security label that marks the information as classified at a more protected level in accordance with applicable jurisdictional privacy policies associated with the target information. The system must retain an immutable record of the previous assignment and binding.

4.3.2.20446 HL7 v3 Value Set RefrainPolicy

URL: https://hl7.org/fhir/STU3/v3/RefrainPolicy/vs.html

This page is part of the FHIR Specification (v3.0.2: STU 3). The current version which supercedes this version is 4.0.1. For a full list of available versions, see the Directory of published versions

Vocabulary Work Group | Maturity Level: N/A | External | Use Context: Any

This value set (http://hl7.org/fhir/ValueSet/v3-RefrainPolicy) is defined as part of HL7 v3. Related FHIR content: RefrainPolicy.

Summary

Defining URL: | http://hl7.org/fhir/ValueSet/v3-RefrainPolicy

Name: | RefrainPolicy
Definition: | Conveys prohibited actions which an information custodian, receiver, or user is not permitted to perform unless otherwise authorized or permitted under specified circumstances. Examples: prohibit redisclosure without consent directive
OID: | 2.16.840.1.113883.1.11.20446 (for OID based terminology systems)
Source Resource | XML / JSON

This value set is not currently used

4.3.2.20446.1 Content Logical Definition

This value set includes codes from the following code systems:

* Include codes from http://hl7.org/fhir/v3/ActCode where concept is-a RefrainPolicy

4.3.2.20446.2 Expansion

This expansion generated 19 Apr 2017

This value set contains 18 concepts

Expansion based on http://hl7.org/fhir/v3/ActCode version 2016-11-11

All codes from system http://hl7.org/fhir/v3/ActCode

Code | Display | Definition
RefrainPolicy | refrain policy | Conveys prohibited actions which an information custodian, receiver, or user is not permitted to perform unless otherwise authorized or permitted under specified circumstances. Usage Notes: ISO 22600-2 species that a Refrain Policy "defines actions the subjects must refrain from performing". Per HL7 Composite Security and Privacy Domain Analysis Model: May be used to indicate that a specific action is prohibited based on specific access control attributes e.g., purpose of use, information type, user role, etc.
NOAUTH | no disclosure without subject authorization | Prohibition on disclosure without information subject's authorization.
NOCOLLECT | no collection | Prohibition on collection or storage of the information.
NODSCLCD | no disclosure without consent directive | Prohibition on disclosure without organizational approved patient restriction.
NODSCLCDS | no disclosure without information subject's consent directive | Prohibition on disclosure without a consent directive from the information subject.
NOINTEGRATE | no integration | Prohibition on Integration into other records.
NOLIST | no unlisted entity disclosure | Prohibition on disclosure except to entities on specific access list.
NOMOU | no disclosure without MOU | Prohibition on disclosure without an interagency service agreement or memorandum of understanding (MOU).
NOORGPOL | no disclosure without organizational authorization | Prohibition on disclosure without organizational authorization.
NOPAT | no disclosure to patient, family or caregivers without attending provider's authorization | Prohibition on disclosing information to patient, family or caregivers without attending provider's authorization. Usage Note: The information may be labeled with the ActInformationSensitivity TBOO code, triggering application of this RefrainPolicy code as a handling caveat controlling access. Maps to FHIR NOPAT: Typically, this is used on an Alert resource, when the alert records information on patient abuse or non-compliance. FHIR print name is "keep information from patient". Maps to the French realm - code: INVISIBLE_PATIENT. displayName: Document non visible par le patient codingScheme: 1.2.250.1.213.1.1.4.13 French use case: A label for documents that the author chose to hide from the patient until the content can be disclose to the patient in a face to face meeting between a healthcare professional and the patient (in French law some results like cancer diagnosis or AIDS diagnosis must be announced to the patient by a healthcare professional and should not be find out by the patient alone).
NOPERSISTP | no collection beyond purpose of use | Prohibition on collection of the information beyond time necessary to accomplish authorized purpose of use is prohibited.
NORDSCLCD | no redisclosure without consent directive | Prohibition on redisclosure without patient consent directive.
NORDSCLCDS | no redisclosure without information subject's consent directive | Prohibition on redisclosure without a consent directive from the information subject.
NORDSCLW | no disclosure without jurisdictional authorization | Prohibition on disclosure without authorization under jurisdictional law.
NORELINK | no relinking | Prohibition on associating de-identified or pseudonymized information with other information in a manner that could or does result in disclosing information intended to be masked.
NOREUSE | no reuse beyond purpose of use | Prohibition on use of the information beyond the purpose of use initially authorized.
NOVIP | no unauthorized VIP disclosure | Prohibition on disclosure except to principals with access permission to specific VIP information.
ORCON | no disclosure without originator authorization | Prohibition on disclosure except as permitted by the information originator.

4.3.2.20448 HL7 v3 Value Set PurposeOfUse

URL: https://hl7.org/fhir/STU3/v3/PurposeOfUse/vs.html

This page is part of the FHIR Specification (v3.0.2: STU 3). The current version which supercedes this version is 4.0.1. For a full list of available versions, see the Directory of published versions

Vocabulary Work Group | Maturity Level: N/A | External | Use Context: Any

This value set (http://hl7.org/fhir/ValueSet/v3-PurposeOfUse) is defined as part of HL7 v3. Related FHIR content: PurposeOfUse.

Summary

Defining URL: | http://hl7.org/fhir/ValueSet/v3-PurposeOfUse
Name: | PurposeOfUse
Definition: | Supports communication of purpose of use at a general level.
OID: | 2.16.840.1.113883.1.11.20448 (for OID based terminology systems)
Source Resource | XML / JSON

This value set is used in the following places:

* Consent.purpose (Extensible)

* Consent.except.purpose (Extensible)
* Contract.actionReason (Example)
* Contract.term.actionReason (Example)
* StructureDefinition Consent Directive: Contract.actionReason ((Example))
* StructureDefinition Consent Directive: Contract.term.actionReason ((Example))
* Provenance.reason (Extensible)
* AuditEvent.purposeOfEvent (Extensible)
* AuditEvent.agent.purposeOfUse (Extensible)

4.3.2.20448.1 Content Logical Definition

This value set includes codes from the following code systems:

* Include codes from http://hl7.org/fhir/v3/ActReason where concept is-a PurposeOfUse

4.3.2.20448.2 Expansion

This expansion generated 19 Apr 2017

This value set contains 43 concepts

Expansion based on http://hl7.org/fhir/v3/ActReason version 2016-11-11

All codes from system http://hl7.org/fhir/v3/ActReason

Code | Display | Definition

PurposeOfUse | purpose of use | Reason for performing one or more operations on information, which may be permitted by source system's security policy in accordance with one or more privacy policies and consent directives. Usage Notes: The rationale or purpose for an act relating to the management of personal health information, such as collecting personal health information for research or public health purposes.

HMARKT | healthcare marketing | To perform one or more operations on information for marketing services and products related to health care.

HOPERAT | healthcare operations | To perform one or more operations on information used for conducting administrative and contractual activities related to the provision of health care.

DONAT | donation | To perform one or more operations on information used for cadaveric organ, eye or tissue donation.

FRAUD | fraud | To perform one or more operations on information used for fraud detection and prevention processes.

GOV | government | To perform one or more operations on information used within government processes.

HACCRED | health accreditation | To perform one or more operations on information for conducting activities related to meeting accreditation criteria.

HCOMPL | health compliance | To perform one or more operations on information used for conducting activities required to meet a mandate.

HDECD | decedent | To perform one or more operations on information used for handling deceased patient matters.

HDIRECT | directory | To perform one or more operation operations on information used to manage a patient directory. Examples: facility enterprise payer health information exchange patient directory

HLEGAL | legal | To perform one or more operations on information for conducting activities required by legal proceeding.

HOUTCOMS | health outcome measure | To perform one or more operations on information used for assessing results and comparative effectiveness achieved by health care practices and interventions.

HPRGRP | health program reporting | To perform one or more operations on information used for conducting activities to meet program accounting requirements.

HQUALIMP | health quality improvement | To perform one or more operations on information used for conducting administrative activities to improve health care quality.

HSYSADMIN | health system administration | To perform one or more operations on information to administer the electronic systems used for the delivery of health care.

MEMADMIN | member administration | To perform one or more operations on information to administer health care coverage to an enrollee under a policy or program.

PATADMIN | patient administration | To perform one or more operations on information used for operational activities conducted to administer the delivery of health care to a patient.

PATSFTY | patient safety | To perform one or more operations on information in processes related to ensuring the safety of health care.

PERFMSR | performance measure | To perform one or more operations on information used for monitoring performance of recommended health care practices and interventions.

RECORDMGT | records management | To perform one or more operations on information used within the health records management process.

TRAIN | training | To perform one or more operations on information used in training and education.

HPAYMT | healthcare payment | To perform one or more operations on information for conducting financial or contractual activities related to payment for provision of health care.

CLMATTCH | claim attachment | To perform one or more operations on information for provision of additional clinical evidence in support of a request for coverage or payment for health services.

COVAUTH | coverage authorization | To perform one or more operations on information for conducting prior authorization or predetermination of coverage for services.

COVERAGE | coverage under policy or program | To perform one or more operations on information for conducting activities related to coverage under a program or policy.

ELIGDTRM | eligibility determination | To perform one or more operations on information used for conducting eligibility determination for coverage in a program or policy. May entail review of financial status or disability assessment.

ELIGVER | eligibility verification | To perform one or more operations on information used for conducting eligibility verification of coverage in a program or policy. May entail provider contacting coverage source (e.g., government health program such as workers compensation or health plan) for confirmation of enrollment, eligibility for specific services, and any applicable copays.

ENROLLM | enrollment | To perform one or more operations on information used for enrolling a covered party in a program or policy. May entail recording of covered party's and any dependent's demographic information and benefit choices.

REMITADV | remittance advice | To perform one or more operations on information about the amount remitted for a health care claim.

HRESCH | healthcare research | To perform one or more operations on information for conducting scientific investigations to obtain health care knowledge.
CLINTRCH | clinical trial research | To perform one or more operations on information for conducting scientific investigations in accordance with clinical trial protocols to obtain health care knowledge.
PATRQT | patient requested | To perform one or more operations on information in response to a patient's request.
FAMRQT | family requested | To perform one or more operations on information in response to a request by a family member authorized by the patient.
PWATRNY | power of attorney | To perform one or more operations on information in response to a request by a person appointed as the patient's legal representative.
SUPNWK | support network | To perform one or more operations on information in response to a request by a person authorized by the patient.
PUBHLTH | public health | To perform one or more operations on information for conducting public health activities, such as the reporting of notifiable conditions.
DISASTER | disaster | To perform one or more operations on information used for provision of immediately needed health care to a population of living subjects located in a disaster zone.
THREAT | threat | To perform one or more operations on information used to prevent injury or disease to living subjects who may be the target of violence.
TREAT | treatment | To perform one or more operations on information for provision of health care.
CAREMGT | Care Management | To perform one or more operations on information for provision of health care coordination.
CLINTRL | clinical trial | To perform health care as part of the clinical trial protocol.
ETREAT | Emergency Treatment | To perform one or more operations on information for provision of immediately needed health care for an emergent condition.
POPHLTH | population health | To perform one or more operations on information for provision of health care to a population of living subjects, e.g., needle exchange program.

4.3.2.20449 HL7 v3 Value Set GeneralPurposeOfUse

URL: https://hl7.org/fhir/STU3/v3/GeneralPurposeOfUse/vs.html

This page is part of the FHIR Specification (v3.0.2: STU 3). The current version which supercedes this version is 4.0.1. For a full list of available versions, see the Directory of published versions

Vocabulary Work Group | Maturity Level: N/A | External | Use Context: Any

This value set (http://hl7.org/fhir/ValueSet/v3-GeneralPurposeOfUse) is defined as part of HL7 v3. Related FHIR content: GeneralPurposeOfUse.

Summary

Defining URL: | http://hl7.org/fhir/ValueSet/v3-GeneralPurposeOfUse
Name: | GeneralPurposeOfUse
Definition: | Supports communication of purpose of use at a general level.
OID: | 2.16.840.1.113883.1.11.20449 (for OID based terminology systems)
Source Resource | XML / JSON

This value set is not currently used

4.3.2.20449.1 Content Logical Definition

This value set includes codes from the following code systems:

* Include these codes as defined in

http://hl7.org/fhir/v3/ActReason

Code | Display
COVERAGE | coverage under policy or program | To perform one or more operations on information for conducting activities related to coverage under a program or policy.
ETREAT | Emergency Treatment | To perform one or more operations on information for provision of immediately needed health care for an emergent condition.
HMARKT | healthcare marketing | To perform one or more operations on information for marketing services and products related to health care.
HOPERAT | healthcare operations | To perform one or more operations on information used for conducting administrative and contractual activities related to the provision of health care.
HPAYMT | healthcare payment | To perform one or more operations on information for conducting financial or contractual activities related to payment for provision of health care.
HRESCH | healthcare research | To perform one or more operations on information for conducting scientific investigations to obtain health care knowledge.
PATRQT | patient requested | To perform one or more operations on information in response to a patient's request.
PUBHLTH | public health | To perform one or more operations on information for conducting public health activities, such as the reporting of notifiable conditions.
TREAT | treatment | To perform one or more operations on information for provision of health care.

4.3.2.20471 HL7 v3 Value Set SecurityControlObservationValue

URL: https://hl7.org/fhir/STU3/v3/SecurityControlObservationValue/vs.html

This page is part of the FHIR Specification (v3.0.2: STU 3). The current version which supercedes this version is 4.0.1. For a full list of available versions, see the Directory of published versions

Vocabulary Work Group | Maturity Level: N/A | External | Use Context: Any

This value set (http://hl7.org/fhir/ValueSet/v3-SecurityControlObservationValue) is defined as part of HL7 v3. Related FHIR content: SecurityControlObservationValue.

Summary

Defining URL: | http://hl7.org/fhir/ValueSet/v3-SecurityControlObservationValue
Name: | SecurityControlObservationValue
Definition: | Security observation values used to indicate security control metadata. V:SecurityControl is the union of V:SecurityPolicy,V:ObligationPolicy, V:RefrainPolicy, V:PurposeOfUse, and V:GeneralPurpose of Use used to populate the SecurityControlObservationValue attribute in order to convey one or more nonhierarchical security control metadata dictating handling caveats, purpose of use, dissemination controls and other refrain policies, and obligations to which a custodian or receiver is required to comply.
OID: | 2.16.840.1.113883.1.11.20471 (for OID based terminology systems)
Source Resource | XML / JSON

This value set is not currently used

4.3.2.20471.1 Content Logical Definition

This value set includes codes from the following code systems:

* Import all the codes that are contained in http://hl7.org/fhir/ValueSet/v3-SecurityPolicy

* Import all the codes that are contained in http://hl7.org/fhir/ValueSet/v3-ObligationPolicy

* Import all the codes that are contained in http://hl7.org/fhir/ValueSet/v3-RefrainPolicy

* Import all the codes that are contained in http://hl7.org/fhir/ValueSet/v3-PurposeOfUse

* Import all the codes that are contained in http://hl7.org/fhir/ValueSet/v3-GeneralPurposeOfUse

4.3.2.20471.2 Expansion

This expansion generated 19 Apr 2017

This value set contains 91 concepts

Expansion based on http://hl7.org/fhir/v3/ActCode version 2016-11-11, http://hl7.org/fhir/ValueSet/v3-RefrainPolicy version 2014-03-26, http://hl7.org/fhir/ValueSet/v3-SecurityPolicy version 2014-03-26, http://hl7.org/fhir/v3/ActReason version 2016-11-11, http://hl7.org/fhir/ValueSet/v3-GeneralPurposeOfUse version 2014-03-26, http://hl7.org/fhir/ValueSet/v3-PurposeOfUse version 2014-03-26, http://hl7.org/fhir/ValueSet/v3-ObligationPolicy version 2014-03-26

Code | System | Display | Definition
SecurityPolicy | http://hl7.org/fhir/v3/ActCode | security policy | Types of security policies that further specify the ActClassPolicy value set. Examples: obligation to encrypt refrain from redisclosure without consent
ObligationPolicy | http://hl7.org/fhir/v3/ActCode | obligation policy | Conveys the mandated workflow action that an information custodian, receiver, or user must perform. Usage Notes: Per ISO 22600-2, ObligationPolicy instances 'are event-triggered and define actions to be performed by manager agent'. Per HL7 Composite Security and Privacy Domain Analysis Model: This value set refers to the action required to receive the permission specified in the privacy rule. Per OASIS XACML, an obligation is an operation specified in a policy or policy that is performed in conjunction with the enforcement of an access control decision.
ANONY | http://hl7.org/fhir/v3/ActCode | anonymize | Custodian system must remove any information that could result in identifying the information subject.
AOD | http://hl7.org/fhir/v3/ActCode | accounting of disclosure | Custodian system must make available to an information subject upon request an accounting of certain disclosures of the individualâ€™s protected health information over a period of time. Policy may dictate that the accounting include information about the information disclosed, the date of disclosure, the identification of the receiver, the purpose of the disclosure, the time in which the disclosing entity must provide a response and the time period for which accountings of disclosure can be requested.
AUDIT | http://hl7.org/fhir/v3/ActCode | audit | Custodian system must monitor systems to ensure that all users are authorized to operate on information objects.
AUDTR | http://hl7.org/fhir/v3/ActCode | audit trail | Custodian system must monitor and maintain retrievable log for each user and operation on information.
CPLYCC | http://hl7.org/fhir/v3/ActCode | comply with confidentiality code | Custodian security system must retrieve, evaluate, and comply with the information handling directions of the Confidentiality Code associated with an information target.
CPLYCD | http://hl7.org/fhir/v3/ActCode | comply with consent directive | Custodian security system must retrieve, evaluate, and comply with applicable information subject consent directives.
CPLYJPP | http://hl7.org/fhir/v3/ActCode | comply with jurisdictional privacy policy | Custodian security system must retrieve, evaluate, and comply with applicable jurisdictional privacy policies associated with the target information.
CPLYOPP | http://hl7.org/fhir/v3/ActCode | comply with organizational privacy policy | Custodian security system must retrieve, evaluate, and comply with applicable organizational privacy policies associated with the target information.
CPLYOSP | http://hl7.org/fhir/v3/ActCode | comply with organizational security policy | Custodian security system must retrieve, evaluate, and comply with the organizational security policies associated with the target information.
CPLYPOL | http://hl7.org/fhir/v3/ActCode | comply with policy | Custodian security system must retrieve, evaluate, and comply with applicable policies associated with the target information.
DECLASSIFYLABEL | http://hl7.org/fhir/v3/ActCode | declassify security label | Custodian security system must declassify information assigned security labels by instantiating a new version of the classified information so as to break the binding of the classifying security label when assigning a new security label that marks the information as unclassified in accordance with applicable jurisdictional privacy policies associated with the target information. The system must retain an immutable record of the previous assignment and binding.
DEID | http://hl7.org/fhir/v3/ActCode | deidentify | Custodian system must strip information of data that would allow the identification of the source of the information or the information subject.
DELAU | http://hl7.org/fhir/v3/ActCode | delete after use | Custodian system must remove target information from access after use.
DOWNGRDLABEL | http://hl7.org/fhir/v3/ActCode | downgrade security label | Custodian security system must downgrade information assigned security labels by instantiating a new version of the classified information so as to break the binding of the classifying security label when assigning a new security label that marks the information as classified at a less protected level in accordance with applicable jurisdictional privacy policies

associated with the target information. The system must retain an immutable record of the previous assignment and binding.

DRIVLABEL | http://hl7.org/fhir/v3/ActCode | derive security label | Custodian security system must assign and bind security labels derived from compilations of information by aggregation or disaggregation in order to classify information compiled in the information systems under its control for collection, access, use and disclosure in accordance with applicable jurisdictional privacy policies associated with the target information. The system must retain an immutable record of the previous assignment and binding.

ENCRYPT | http://hl7.org/fhir/v3/ActCode | encrypt | Custodian system must render information unreadable by algorithmically transforming plaintext into ciphertext. Usage Notes: A mathematical transposition of a file or data stream so that it cannot be deciphered at the receiving end without the proper key. Encryption is a security feature that assures that only the parties who are supposed to be participating in a videoconference or data transfer are able to do so. It can include a password, public and private keys, or a complex combination of all. (Per Infoway.)

ENCRYPTR | http://hl7.org/fhir/v3/ActCode | encrypt at rest | Custodian system must render information unreadable and unusable by algorithmically transforming plaintext into ciphertext when "at rest" or in storage.

ENCRYPTT | http://hl7.org/fhir/v3/ActCode | encrypt in transit | Custodian system must render information unreadable and unusable by algorithmically transforming plaintext into ciphertext while "in transit" or being transported by any means.

ENCRYPTU | http://hl7.org/fhir/v3/ActCode | encrypt in use | Custodian system must render information unreadable and unusable by algorithmically transforming plaintext into ciphertext while in use such that operations permitted on the target information are limited by the license granted to the end user.

HUAPRV | http://hl7.org/fhir/v3/ActCode | human approval | Custodian system must require human review and approval for permission requested.

LABEL | http://hl7.org/fhir/v3/ActCode | assign security label | Custodian security system must assign and bind security labels in order to classify information created in the information systems under its control for collection, access, use and disclosure in accordance with applicable jurisdictional privacy policies associated with the target information. The system must retain an immutable record of the assignment and binding. Usage Note: In security systems, security policy label assignments do not change, they may supersede prior assignments, and such reassignments are always tracked for auditing and other purposes.

MASK | http://hl7.org/fhir/v3/ActCode | mask | Custodian system must render information unreadable and unusable by algorithmically transforming plaintext into ciphertext. User may be provided a key to decrypt per license or "shared secret".

MINEC | http://hl7.org/fhir/v3/ActCode | minimum necessary | Custodian must limit access and disclosure to the minimum information required to support an authorized user's purpose of use. Usage Note: Limiting the information available for access and disclosure to that an authorized user or receiver "needs to know" in order to perform permitted workflow or purpose of use.

PERSISTLABEL | http://hl7.org/fhir/v3/ActCode | persist security label | Custodian security system must persist the binding of security labels to classify information received or imported by information systems under its control for collection, access, use and disclosure in accordance with applicable jurisdictional privacy policies associated with the target information. The system must retain an immutable record of the assignment and binding.

PRIVMARK | http://hl7.org/fhir/v3/ActCode | privacy mark | Custodian must create and/or maintain human readable security label tags as required by policy. Map: Aligns with ISO 22600-3 Section A.3.4.3 description of privacy mark: "If present, the privacy-mark is not used for access control. The content of the privacy-mark may be defined by the security policy in force (identified by the security-policy-identifier) which may define a list of values to be used. Alternately, the value may be determined by the originator of the security-label."

PSEUD | http://hl7.org/fhir/v3/ActCode | pseudonymize | Custodian system must strip information of data that would allow the identification of the source of the information or the information subject. Custodian may retain a key to relink data necessary to reidentify the information subject.

REDACT | http://hl7.org/fhir/v3/ActCode | redact | Custodian system must remove information, which is not authorized to be access, used, or disclosed from records made available to otherwise authorized users.

UPGRDLABEL | http://hl7.org/fhir/v3/ActCode | upgrade security label | Custodian security system must declassify information assigned security labels by instantiating a new version of the classified information so as to break the binding of the classifying security label when assigning a new security label that marks the information as classified at a more protected level in accordance with applicable jurisdictional privacy policies associated with the target information. The system must retain an immutable record of the previous assignment and binding.

RefrainPolicy | http://hl7.org/fhir/v3/ActCode | refrain policy | Conveys prohibited actions which an information custodian, receiver, or user is not permitted to perform unless otherwise authorized or permitted under specified circumstances. Usage Notes: ISO 22600-2 species that a Refrain Policy "defines actions the subjects must refrain from performing". Per HL7 Composite Security and Privacy Domain Analysis Model: May be used to indicate that a specific action is prohibited based on specific access control attributes e.g., purpose of use, information type, user role, etc.

NOAUTH | http://hl7.org/fhir/v3/ActCode | no disclosure without subject authorization | Prohibition on disclosure without information subject's authorization.

NOCOLLECT | http://hl7.org/fhir/v3/ActCode | no collection | Prohibition on collection or storage of the information.

NODSCLCD | http://hl7.org/fhir/v3/ActCode | no disclosure without consent directive | Prohibition on disclosure without organizational approved patient restriction.

NODSCLCDS | http://hl7.org/fhir/v3/ActCode | no disclosure without information subject's consent directive | Prohibition on disclosure without a consent directive from the information subject.

NOINTEGRATE | http://hl7.org/fhir/v3/ActCode | no integration | Prohibition on Integration into other records.

NOLIST | http://hl7.org/fhir/v3/ActCode | no unlisted entity disclosure | Prohibition on disclosure except to entities on specific access list.

NOMOU | http://hl7.org/fhir/v3/ActCode | no disclosure without MOU | Prohibition on disclosure without an interagency service agreement or memorandum of understanding (MOU).

NOORGPOL | http://hl7.org/fhir/v3/ActCode | no disclosure without organizational authorization | Prohibition on disclosure without organizational authorization.

NOPAT | http://hl7.org/fhir/v3/ActCode | no disclosure to patient, family or caregivers without attending provider's authorization | Prohibition on disclosing information to patient, family or caregivers without attending provider's authorization. Usage Note: The information may be labeled with the ActInformationSensitivity TBOO code, triggering application of this RefrainPolicy code as a handling caveat controlling access. Maps to FHIR NOPAT: Typically, this is used on an Alert resource, when the alert records information on patient abuse or non-compliance. FHIR print name is "keep information from patient". Maps to the French realm - code: INVISIBLE_PATIENT. displayName: Document non visible par le patient codingScheme: 1.2.250.1.213.1.1.4.13 French use case: A label for documents that the author chose to hide from the patient until the content can be disclose to the patient in a face to face meeting between a healthcare professional and the patient (in French law some results like cancer diagnosis or AIDS diagnosis must be announced to the patient by a healthcare professional and should not be find out by the patient alone).

NOPERSISTP | http://hl7.org/fhir/v3/ActCode | no collection beyond purpose of use | Prohibition on collection of the information beyond time necessary to accomplish authorized purpose of use is prohibited.

NORDSCLCD | http://hl7.org/fhir/v3/ActCode | no redisclosure without consent directive | Prohibition on redisclosure without patient consent directive.

NORDSCLCDS | http://hl7.org/fhir/v3/ActCode | no redisclosure without information subject's consent directive | Prohibition on redisclosure without a consent directive from the information subject.

NORDSCLW | http://hl7.org/fhir/v3/ActCode | no disclosure without jurisdictional authorization | Prohibition on disclosure without authorization under jurisdictional law.

NORELINK | http://hl7.org/fhir/v3/ActCode | no relinking | Prohibition on associating de-identified or pseudonymized information with other information in a manner that could or does result in disclosing information intended to be masked.
NOREUSE | http://hl7.org/fhir/v3/ActCode | no reuse beyond purpose of use | Prohibition on use of the information beyond the purpose of use initially authorized.
NOVIP | http://hl7.org/fhir/v3/ActCode | no unauthorized VIP disclosure | Prohibition on disclosure except to principals with access permission to specific VIP information.
ORCON | http://hl7.org/fhir/v3/ActCode | no disclosure without originator authorization | Prohibition on disclosure except as permitted by the information originator.
PurposeOfUse | http://hl7.org/fhir/v3/ActReason | purpose of use | Reason for performing one or more operations on information, which may be permitted by source system's security policy in accordance with one or more privacy policies and consent directives. Usage Notes: The rationale or purpose for an act relating to the management of personal health information, such as collecting personal health information for research or public health purposes.
HMARKT | http://hl7.org/fhir/v3/ActReason | healthcare marketing | To perform one or more operations on information for marketing services and products related to health care.
HOPERAT | http://hl7.org/fhir/v3/ActReason | healthcare operations | To perform one or more operations on information used for conducting administrative and contractual activities related to the provision of health care.
DONAT | http://hl7.org/fhir/v3/ActReason | donation | To perform one or more operations on information used for cadaveric organ, eye or tissue donation.
FRAUD | http://hl7.org/fhir/v3/ActReason | fraud | To perform one or more operations on information used for fraud detection and prevention processes.
GOV | http://hl7.org/fhir/v3/ActReason | government | To perform one or more operations on information used within government processes.
HACCRED | http://hl7.org/fhir/v3/ActReason | health accreditation | To perform one or more operations on information for conducting activities related to meeting accreditation criteria.
HCOMPL | http://hl7.org/fhir/v3/ActReason | health compliance | To perform one or more operations on information used for conducting activities required to meet a mandate.
HDECD | http://hl7.org/fhir/v3/ActReason | decedent | To perform one or more operations on information used for handling deceased patient matters.
HDIRECT | http://hl7.org/fhir/v3/ActReason | directory | To perform one or more operation operations on information used to manage a patient directory. Examples: facility enterprise payer health information exchange patient directory
HLEGAL | http://hl7.org/fhir/v3/ActReason | legal | To perform one or more operations on information for conducting activities required by legal proceeding.
HOUTCOMS | http://hl7.org/fhir/v3/ActReason | health outcome measure | To perform one or more operations on information used for assessing results and comparative effectiveness achieved by health care practices and interventions.
HPRGRP | http://hl7.org/fhir/v3/ActReason | health program reporting | To perform one or more operations on information used for conducting activities to meet program accounting requirements.
HQUALIMP | http://hl7.org/fhir/v3/ActReason | health quality improvement | To perform one or more operations on information used for conducting administrative activities to improve health care quality.
HSYSADMIN | http://hl7.org/fhir/v3/ActReason | health system administration | To perform one or more operations on information to administer the electronic systems used for the delivery of health care.
MEMADMIN | http://hl7.org/fhir/v3/ActReason | member administration | To perform one or more operations on information to administer health care coverage to an enrollee under a policy or program.
PATADMIN | http://hl7.org/fhir/v3/ActReason | patient administration | To perform one or more operations on information used for operational activities conducted to administer the delivery of health care to a patient.
PATSFTY | http://hl7.org/fhir/v3/ActReason | patient safety | To perform one or more operations on information in processes related to ensuring the safety of health care.
PERFMSR | http://hl7.org/fhir/v3/ActReason | performance measure | To perform one or more operations on information used for monitoring performance of recommended health care practices and interventions.
RECORDMGT | http://hl7.org/fhir/v3/ActReason | records management | To perform one or more operations on information used within the health records management process.
TRAIN | http://hl7.org/fhir/v3/ActReason | training | To perform one or more operations on information used in training and education.
HPAYMT | http://hl7.org/fhir/v3/ActReason | healthcare payment | To perform one or more operations on information for conducting financial or contractual activities related to payment for provision of health care.
CLMATTCH | http://hl7.org/fhir/v3/ActReason | claim attachment | To perform one or more operations on information for provision of additional clinical evidence in support of a request for coverage or payment for health services.
COVAUTH | http://hl7.org/fhir/v3/ActReason | coverage authorization | To perform one or more operations on information for conducting prior authorization or predetermination of coverage for services.
COVERAGE | http://hl7.org/fhir/v3/ActReason | coverage under policy or program | To perform one or more operations on information for conducting activities related to coverage under a program or policy.
ELIGDTRM | http://hl7.org/fhir/v3/ActReason | eligibility determination | To perform one or more operations on information used for conducting eligibility determination for coverage in a program or policy. May entail review of financial status or disability assessment.
ELIGVER | http://hl7.org/fhir/v3/ActReason | eligibility verification | To perform one or more operations on information used for conducting eligibility verification of coverage in a program or policy. May entail provider contacting coverage source (e.g., government health program such as workers compensation or health plan) for confirmation of enrollment, eligibility for specific services, and any applicable copays.
ENROLLM | http://hl7.org/fhir/v3/ActReason | enrollment | To perform one or more operations on information used for enrolling a covered party in a program or policy. May entail recording of covered party's and any dependent's demographic information and benefit choices.
REMITADV | http://hl7.org/fhir/v3/ActReason | remittance advice | To perform one or more operations on information about the amount remitted for a health care claim.
HRESCH | http://hl7.org/fhir/v3/ActReason | healthcare research | To perform one or more operations on information for conducting scientific investigations to obtain health care knowledge.
CLINTRCH | http://hl7.org/fhir/v3/ActReason | clinical trial research | To perform one or more operations on information for conducting scientific investigations in accordance with clinical trial protocols to obtain health care knowledge.
PATRQT | http://hl7.org/fhir/v3/ActReason | patient requested | To perform one or more operations on information in response to a patient's request.
FAMRQT | http://hl7.org/fhir/v3/ActReason | family requested | To perform one or more operations on information in response to a request by a family member authorized by the patient.
PWATRNY | http://hl7.org/fhir/v3/ActReason | power of attorney | To perform one or more operations on information in response to a request by a person appointed as the patient's legal representative.

SUPNWK | http://hl7.org/fhir/v3/ActReason | support network | To perform one or more operations on information in response to a request by a person authorized by the patient.
PUBHLTH | http://hl7.org/fhir/v3/ActReason | public health | To perform one or more operations on information for conducting public health activities, such as the reporting of notifiable conditions.
DISASTER | http://hl7.org/fhir/v3/ActReason | disaster | To perform one or more operations on information used for provision of immediately needed health care to a population of living subjects located in a disaster zone.
THREAT | http://hl7.org/fhir/v3/ActReason | threat | To perform one or more operations on information used to prevent injury or disease to living subjects who may be the target of violence.
TREAT | http://hl7.org/fhir/v3/ActReason | treatment | To perform one or more operations on information for provision of health care.
CAREMGT | http://hl7.org/fhir/v3/ActReason | Care Management | To perform one or more operations on information for provision of health care coordination.
CLINTRL | http://hl7.org/fhir/v3/ActReason | clinical trial | To perform health care as part of the clinical trial protocol.
ETREAT | http://hl7.org/fhir/v3/ActReason | Emergency Treatment | To perform one or more operations on information for provision of immediately needed health care for an emergent condition.
POPHLTH | http://hl7.org/fhir/v3/ActReason | population health | To perform one or more operations on information for provision of health care to a population of living subjects, e.g., needle exchange program.

4.3.2.20478 HL7 v3 Value Set Compartment

URL: https://hl7.org/fhir/STU3/v3/Compartment/vs.html

This page is part of the FHIR Specification (v3.0.2: STU 3). The current version which supercedes this version is 4.0.1. For a full list of available versions, see the Directory of published versions

Vocabulary Work Group | Maturity Level: N/A | External | Use Context: Any

This value set (http://hl7.org/fhir/ValueSet/v3-Compartment) is defined as part of HL7 v3. Related FHIR content: Compartment.

Summary

Defining URL: | http://hl7.org/fhir/ValueSet/v3-Compartment
Name: | Compartment
Definition: | A named tag set for metadata used to populate a security category label field that "segments" an IT resource per policy by indicating that access and use is restricted to members of a defined community or project. (HL7 Healthcare Privacy and Security Classification System) Usage Note: This is the healthcare analog to the US Intelligence Community's concept of a Special Access Program. Compartment codes may be used in as a field value in an initiator's clearance to indicate permission to access and use an IT Resource with a security label having the same compartment value in security category label field. Map: Aligns with ISO 2382-8 definition of Compartment - "A division of data into isolated blocks with separate security controls for the purpose of reducing risk."
OID: | 2.16.840.1.113883.1.11.20478 (for OID based terminology systems)
Source Resource | XML / JSON

This value set is not currently used

4.3.2.20478.1 Content Logical Definition

This value set includes codes from the following code systems:

* Include codes from http://hl7.org/fhir/v3/ActCode where concept is-a COMPT

4.3.2.20478.2 Expansion

This expansion generated 19 Apr 2017

This value set contains 4 concepts

Expansion based on http://hl7.org/fhir/v3/ActCode version 2016-11-11

All codes from system http://hl7.org/fhir/v3/ActCode

Code | Display | Definition
COMPT | compartment | This is the healthcare analog to the US Intelligence Community's concept of a Special Access Program. Compartment codes may be used in as a field value in an initiator's clearance to indicate permission to access and use an IT Resource with a security label having the same compartment value in security category label field. Map: Aligns with ISO 2382-8 definition of Compartment - "A division of data into isolated blocks with separate security controls for the purpose of reducing risk."
HRCOMPT | human resource compartment | A security category label field value, which indicates that access and use of an IT resource is restricted to members of human resources department or workflow.
RESCOMPT | research project compartment | A security category label field value, which indicates that access and use of an IT resource is restricted to members of a research project.
RMGTCOMPT | records management compartment | A security category label field value, which indicates that access and use of an IT resource is restricted to members of records management department or workflow.

4.3.2.20481 HL7 v3 Value Set SecurityIntegrityObservationValue

URL: https://hl7.org/fhir/STU3/v3/SecurityIntegrityObservationValue/vs.html

This page is part of the FHIR Specification (v3.0.2: STU 3). The current version which supercedes this version is 4.0.1. For a full list of available versions, see the Directory of published versions

Vocabulary Work Group | Maturity Level: N/A | External | Use Context: Any

This value set (http://hl7.org/fhir/ValueSet/v3-SecurityIntegrityObservationValue) is defined as part of HL7 v3. Related FHIR content: SecurityIntegrityObservationValue.

Summary

Defining URL: | http://hl7.org/fhir/ValueSet/v3-SecurityIntegrityObservationValue
Name: | SecurityIntegrityObservationValue
Definition: | No Description Provided
OID: | 2.16.840.1.113883.1.11.20481 (for OID based terminology systems)
Source Resource | XML / JSON

This value set is not currently used

4.3.2.20481.1 Content Logical Definition

This value set includes codes from the following code systems:

* Include codes from http://hl7.org/fhir/v3/ObservationValue where concept is-a _SECINTOBV

* Exclude these codes as defined in

http://hl7.org/fhir/v3/ObservationValue

Code | Display
_SECINTOBV | security integrity | Abstract security observation values used to indicate security integrity metadata. Examples: Codes conveying integrity status, integrity confidence, and provenance.

4.3.2.20481.2 Expansion

This expansion generated 19 Apr 2017

This value set contains 33 concepts

Expansion based on http://hl7.org/fhir/v3/ObservationValue version 2016-11-11

All codes from system http://hl7.org/fhir/v3/ObservationValue

Code | Display | Definition
ABSTRED | abstracted | Security metadata observation values used to indicate the use of a more abstract version of the content, e.g., replacing exact value of an age or date field with a range, or remove the left digits of a credit card number or SSN.
AGGRED | aggregated | Security metadata observation values used to indicate the use of an algorithmic combination of actual values with the result of an aggregate function, e.g., average, sum, or count in order to limit disclosure of an IT resource (data, information object, service, or system capability) to the minimum necessary.
ANONYED | anonymized | Security metadata observation value conveying the alteration integrity of an IT resource (data, information object, service, or system capability) by used to indicate the mechanism by which software systems can strip portions of the resource that could allow the identification of the source of the information or the information subject. No key to relink the data is retained.
MAPPED | mapped | Security metadata observation value used to indicate that the IT resource semantic content has been transformed from one encoding to another. Usage Note: "MAP" code does not indicate the semantic fidelity of the transformed content. To indicate semantic fidelity for maps of HL7 to other code systems, this security alteration integrity observation may be further specified using an Act valued with Value Set: MapRelationship (2.16.840.1.113883.1.11.11052). Semantic fidelity of the mapped IT Resource may also be indicated using a SecurityIntegrityConfidenceObservation.
MASKED | masked | Security metadata observation value conveying the alteration integrity of an IT resource (data, information object, service, or system capability) by indicating the mechanism by which software systems can make data unintelligible (that is, as unreadable and unusable by algorithmically transforming plaintext into ciphertext) such that it can only be accessed or used by authorized users. An authorized user may be provided a key to decrypt per license or "shared secret". Usage Note: "MASKED" may be used, per applicable policy, as a flag to indicate to a user or receiver that some portion of an IT resource has been further encrypted, and may be accessed only by an authorized user or receiver to which a decryption key is provided.
PSEUDED | pseudonymized | Security metadata observation value conveying the alteration integrity of an IT resource (data, information object, service, or system capability), by indicating the mechanism by which software systems can strip portions of the resource that could allow the identification of the source of the information or the information subject. Custodian may retain a key to relink data necessary to reidentify the information subject. Rationale: Personal data which has been processed to make it impossible to know whose data it is. Used particularly for secondary use of health data. In some cases, it may be possible for authorized individuals to restore the identity of the individual, e.g.,for public health case management. Based on ISO/TS 25237:2008 Health informaticsâ€"Pseudonymization
REDACTED | redacted | Security metadata observation value used to indicate the mechanism by which software systems can filter an IT resource (data, information object, service, or system capability) to remove any portion of the resource that is not authorized to be access, used, or disclosed. Usage Note: "REDACTED" may be used, per applicable policy, as a flag to indicate to a user or receiver that some portion of an IT resource has filtered and not included in the content accessed or received.
SUBSETTED | subsetted | Metadata observation used to indicate that some information has been removed from the source object when the view this object contains was constructed because of configuration options when the view was created. The content may not be suitable for use as the basis of a record update Usage Note: This is not suitable to be used when information is removed for security reasons - see the code REDACTED for this use.
SYNTAC | syntactic transform | Security metadata observation value used to indicate that the IT resource syntax has been transformed from one syntactical representation to another. Usage Note: "SYNTAC" code does not indicate the syntactical correctness of the syntactically transformed IT resource.
TRSLT | translated | Security metadata observation value used to indicate that the IT resource has been translated from one human language to another. Usage Note: "TRSLT" does not indicate the fidelity of the translation or the languages translated. The fidelity of the IT Resource translation may be indicated using a SecurityIntegrityConfidenceObservation. To indicate languages, use the Value Set:HumanLanguage (2.16.840.1.113883.1.11.11526)
VERSIONED | versioned | Security metadata observation value conveying the alteration integrity of an IT resource (data, information object, service, or system capability) which indicates that the resource only retains versions of an IT resource for access and use per applicable policy Usage Note: When this code is used, expectation is that the system has removed historical versions of the data that falls outside the time period deemed to be the effective time of the applicable version.
CRYTOHASH | cryptographic hash function | Security metadata observation value used to indicate the mechanism by which software systems can establish that data was not modified in transit. Rationale: This definition is intended to align with the ISO 22600-2 3.3.19 definition of cryptographic checkvalue: Information which is derived by performing a cryptographic transformation (see cryptography) on the data unit. The derivation of the checkvalue may be performed in one or more steps and is a result of a mathematical function of the key and a data unit. It is usually used to check

the integrity of a data unit. Examples: SHA-1 SHA-2 (Secure Hash Algorithm)

DIGSIG | digital signature | Security metadata observation value used to indicate the mechanism by which software systems use digital signature to establish that data has not been modified. Rationale: This definition is intended to align with the ISO 22600-2 3.3.26 definition of digital signature: Data appended to, or a cryptographic transformation (see cryptography) of, a data unit that allows a recipient of the data unit to prove the source and integrity of the data unit and protect against forgery e.g., by the recipient.

HRELIABLE | highly reliable | Security metadata observation value used to indicate that the veracity or trustworthiness of an IT resource (data, information object, service, or system capability) for a specified purpose of use is perceived to be or deemed by policy to be very high.

RELIABLE | reliable | Security metadata observation value used to indicate that the veracity or trustworthiness of an IT resource (data, information object, service, or system capability) for a specified purpose of use is perceived to be or deemed by policy to be adequate.

UNCERTREL | uncertain reliability | Security metadata observation value used to indicate that the veracity or trustworthiness of an IT resource (data, information object, service, or system capability) for a specified purpose of use is perceived to be or deemed by policy to be uncertain.

UNRELIABLE | unreliable | Security metadata observation value used to indicate that the veracity or trustworthiness of an IT resource (data, information object, service, or system capability) for a specified purpose of use is perceived to be or deemed by policy to be inadequate.

CLINAST | clinician asserted | Security provenance metadata observation value used to indicate that an IT resource (data, information object, service, or system capability) was asserted by a clinician.

DEVAST | device asserted | Security provenance metadata observation value used to indicate that an IT resource (data, information object, service, or system capability) was asserted by a device.

HCPAST | healthcare professional asserted | Security provenance metadata observation value used to indicate that an IT resource (data, information object, service, or system capability) was asserted by a healthcare professional.

PACQAST | patient acquaintance asserted | Security provenance metadata observation value used to indicate that an IT resource (data, information object, service, or system capability) was asserted by a patient acquaintance.

PATAST | patient asserted | Security provenance metadata observation value used to indicate that an IT resource (data, information object, service, or system capability) was asserted by a patient.

PAYAST | payer asserted | Security provenance metadata observation value used to indicate that an IT resource (data, information object, service, or system capability) was asserted by a payer.

PROAST | professional asserted | Security provenance metadata observation value used to indicate that an IT resource (data, information object, service, or system capability) was asserted by a professional.

SDMAST | substitute decision maker asserted | Security provenance metadata observation value used to indicate that an IT resource (data, information object, service, or system capability) was asserted by a substitute decision maker.

CLINRPT | clinician reported | Security provenance metadata observation value used to indicate that an IT resource (data, information object, service, or system capability) was reported by a clinician.

DEVRPT | device reported | Security provenance metadata observation value used to indicate that an IT resource (data, information object, service, or system capability) was reported by a device.

HCPRPT | healthcare professional reported | Security provenance metadata observation value used to indicate that an IT resource (data, information object, service, or system capability) was reported by a healthcare professional.

PACQRPT | patient acquaintance reported | Security provenance metadata observation value used to indicate that an IT resource (data, information object, service, or system capability) was reported by a patient acquaintance.

PATRPT | patient reported | Security provenance metadata observation value used to indicate that an IT resource (data, information object, service, or system capability) was reported by a patient.

PAYRPT | payer reported | Security provenance metadata observation value used to indicate that an IT resource (data, information object, service, or system capability) was reported by a payer.

PRORPT | professional reported | Security provenance metadata observation value used to indicate that an IT resource (data, information object, service, or system capability) was reported by a professional.

SDMRPT | substitute decision maker reported | Security provenance metadata observation value used to indicate that an IT resource (data, information object, service, or system capability) was reported by a substitute decision maker.

4.3.2.20545 HL7 v3 Value Set ProvenanceEventCurrentState-AS

URL: https://hl7.org/fhir/STU3/v3/ProvenanceEventCurrentState-AS/vs.html

This page is part of the FHIR Specification (v3.0.2: STU 3). The current version which supercedes this version is 4.0.1. For a full list of available versions, see the Directory of published versions

Vocabulary Work Group | Maturity Level: N/A | External | Use Context: Any

This value set (http://hl7.org/fhir/ValueSet/v3-ProvenanceEventCurrentState-AS) is defined as part of HL7 v3. Related FHIR content: ProvenanceEventCurrentState-AS.

Summary

Defining URL: | http://hl7.org/fhir/ValueSet/v3-ProvenanceEventCurrentState-AS

Name: | ProvenanceEventCurrentState-AS

Definition: | Specifies the state change of a target Act, using ActStatus codes, from its previous state as a predecessor Act. For example, if the target Act is the result of a predecessor Act being "obsoleted" and replaced with the target Act, the source ProvenanceEventCurrentState Act code would be "obsoleted".

OID: | 2.16.840.1.113883.1.11.20545 (for OID based terminology systems)

Source Resource | XML / JSON

This value set is not currently used

4.3.2.20545.1 Content Logical Definition

This value set includes codes from the following code systems:

* Include these codes as defined in

http://hl7.org/fhir/v3/ActStatus

Code | Display

aborted | aborted | The Act has been terminated prior to the originally intended completion.

cancelled | cancelled | The Act has been abandoned before activation.
completed | completed | An Act that has terminated normally after all of its constituents have been performed.
new | new | An Act that is in the preparatory stages and may not yet be acted upon
nullified | nullified | This Act instance was created in error and has been 'removed' and is treated as though it never existed. A record is retained for audit purposes only.
obsolete | obsolete | This Act instance has been replaced by a new instance.

4.3.2.20546 HL7 v3 Value Set ProvenanceEventCurrentState-DC

URL: https://hl7.org/fhir/STU3/v3/ProvenanceEventCurrentState-DC/vs.html

This page is part of the FHIR Specification (v3.0.2: STU 3). The current version which supercedes this version is 4.0.1. For a full list of available versions, see the Directory of published versions

Vocabulary Work Group | Maturity Level: N/A | External | Use Context: Any

This value set (http://hl7.org/fhir/ValueSet/v3-ProvenanceEventCurrentState-DC) is defined as part of HL7 v3. Related FHIR content: ProvenanceEventCurrentState-DC.

Summary

Defining URL: | http://hl7.org/fhir/ValueSet/v3-ProvenanceEventCurrentState-DC
Name: | ProvenanceEventCurrentState-DC
Definition: | Specifies the state change of a target Act using DocuymentCompletion codes, from its previous state as a predecessor Act. For example, if the target Act is the result of a predecessor Act being "obsoleted" and replaced with the target Act, the source ProvenanceEventCurrentState Act code would be "obsoleted".
OID: | 2.16.840.1.113883.1.11.20546 (for OID based terminology systems)
Source Resource | XML / JSON

This value set is not currently used

4.3.2.20546.1 Content Logical Definition

This value set includes codes from the following code systems:

* Include these codes as defined in

http://hl7.org/fhir/v3/DocumentCompletion

Code | Display
AU | authenticated | A completion status in which a document has been signed manually or electronically by one or more individuals who attest to its accuracy. No explicit determination is made that the assigned individual has performed the authentication. While the standard allows multiple instances of authentication, it would be typical to have a single instance of authentication, usually by the assigned individual.
DI | dictated | A completion status in which information has been orally recorded but not yet transcribed.
DO | documented | A completion status in which document content, other than dictation, has been received but has not been translated into the final electronic format. Examples include paper documents, whether hand-written or typewritten, and intermediate electronic forms, such as voice to text.
LA | legally authenticated | A completion status in which a document has been signed manually or electronically by the individual who is legally responsible for that document. This is the most mature state in the workflow progression.
UC | unsigned completed document | A completion status where the document is complete and there is no expectation that the document will be signed.

4.3.2.20547 HL7 v3 Value Set ProvenanceEventCurrentState

URL: https://hl7.org/fhir/STU3/v3/ProvenanceEventCurrentState/vs.html

This page is part of the FHIR Specification (v3.0.2: STU 3). The current version which supercedes this version is 4.0.1. For a full list of available versions, see the Directory of published versions

Vocabulary Work Group | Maturity Level: N/A | External | Use Context: Any

This value set (http://hl7.org/fhir/ValueSet/v3-ProvenanceEventCurrentState) is defined as part of HL7 v3. Related FHIR content: ProvenanceEventCurrentState.

Summary

Defining URL: | http://hl7.org/fhir/ValueSet/v3-ProvenanceEventCurrentState
Name: | ProvenanceEventCurrentState
Definition: | Specifies the state change of a target Act, such as a document or an entry, from its previous state as a predecessor Act. For example, if the target Act is the result of a predecessor Act being "obsoleted" and replaced with the target Act, the source ProvenanceEventCurrentState Act code would be "obsoleted".
OID: | 2.16.840.1.113883.1.11.20547 (for OID based terminology systems)
Source Resource | XML / JSON

This value set is not currently used

4.3.2.20547.1 Content Logical Definition

This value set includes codes from the following code systems:

* Import all the codes that are contained in http://hl7.org/fhir/ValueSet/v3-ProvenanceEventCurrentState-AS

* Import all the codes that are contained in http://hl7.org/fhir/ValueSet/v3-ProvenanceEventCurrentState-DC

4.3.2.20547.2 Expansion

This expansion generated 19 Apr 2017

This value set contains 11 concepts

Expansion based on http://hl7.org/fhir/ValueSet/v3-ProvenanceEventCurrentState-AS version 2014-08-07, http://hl7.org/fhir/ValueSet/v3-ProvenanceEventCurrentState-DC version 2014-08-07, http://hl7.org/fhir/v3/ActStatus version 2016-11-11, http://hl7.org/fhir/v3/DocumentCompletion version 2016-11-11

Code | System | Display | Definition
aborted | http://hl7.org/fhir/v3/ActStatus | aborted | The Act has been terminated prior to the originally intended completion.
cancelled | http://hl7.org/fhir/v3/ActStatus | cancelled | The Act has been abandoned before activation.
completed | http://hl7.org/fhir/v3/ActStatus | completed | An Act that has terminated normally after all of its constituents have been performed.
new | http://hl7.org/fhir/v3/ActStatus | new | An Act that is in the preparatory stages and may not yet be acted upon
nullified | http://hl7.org/fhir/v3/ActStatus | nullified | This Act instance was created in error and has been 'removed' and is treated as though it never existed. A record is retained for audit purposes only.
obsolete | http://hl7.org/fhir/v3/ActStatus | obsolete | This Act instance has been replaced by a new instance.
AU | http://hl7.org/fhir/v3/DocumentCompletion | authenticated | A completion status in which a document has been signed manually or electronically by one or more individuals who attest to its accuracy. No explicit determination is made that the assigned individual has performed the authentication. While the standard allows multiple instances of authentication, it would be typical to have a single instance of authentication, usually by the assigned individual.
DI | http://hl7.org/fhir/v3/DocumentCompletion | dictated | A completion status in which information has been orally recorded but not yet transcribed.
DO | http://hl7.org/fhir/v3/DocumentCompletion | documented | A completion status in which document content, other than dictation, has been received but has not been translated into the final electronic format. Examples include paper documents, whether hand-written or typewritten, and intermediate electronic forms, such as voice to text.
LA | http://hl7.org/fhir/v3/DocumentCompletion | legally authenticated | A completion status in which a document has been signed manually or electronically by the individual who is legally responsible for that document. This is the most mature state in the workflow progression.
UC | http://hl7.org/fhir/v3/DocumentCompletion | unsigned completed document | A completion status where the document is complete and there is no expectation that the document will be signed.

4.4 Mappings between Value Sets Defined in FHIR

URL: https://hl7.org/fhir/STU3/terminologies-conceptmaps.html

This page is part of the FHIR Specification (v3.0.2: STU 3). The current version which supercedes this version is 4.0.1. For a full list of available versions, see the Directory of published versions

4.4 Mappings between Value Sets Defined in FHIR

This table contains a list of all the mappings between value sets that are defined as part of the FHIR specification.

Name | Source | Target
FHIR-v3-Address-Use | AddressUse | v3 Code System AddressUse
Specimen mapping from v2 table 0487 to SNOMED CT | v2 Specimen Type | http://snomed.info/id?fhir_vs
SNOMED CT to ICD-10-CM mappings for fracture of ulna | http://snomed.info/id?fhir_vs | http://hl7.org/fhir/sid/icd-10-us
v3 map for AddressType | AddressType | v3 Code System AddressUse
v2 map for AddressUse | AddressUse | v2 Address Type
v3 map for AddressUse | AddressUse | v3 Code System AddressUse
v2 map for AdministrativeGender | AdministrativeGender | v2 Administrative Sex
v3 map for AdministrativeGender | AdministrativeGender | v3 Code System AdministrativeGender
v3 map for CompositionStatus | CompositionStatus | v3 Code System ActStatus
v2 map for ContactPointSystem | ContactPointSystem | v2 Telecommunication Equipment Type
v2 map for ContactPointUse | ContactPointUse | v2 Telecommunication Use Code
v3 map for ContactPointUse | ContactPointUse | v3 Code System AddressUse
v3 map for DataAbsentReason | DataAbsentReason | v3 Code System NullFlavor
v3 map for DetectedIssueSeverity | DetectedIssueSeverity | SeverityObservation
v3 map for DocumentReferenceStatus | DocumentReferenceStatus | v3 Code System ActStatus
v3 map for MedicationAdministrationStatus | MedicationAdministrationStatus | v3 Code System ActStatus
v3 map for MedicationDispenseStatus | MedicationDispenseStatus | v3 Code System ActStatus
v3 map for MedicationRequestStatus | MedicationRequestStatus | v3 Code System ActStatus
v3 map for MedicationStatementStatus | MedicationStatementStatus | v3 Code System ActStatus
v2 map for NameUse | NameUse | v2 Name Type
v3 map for NameUse | NameUse | v3 Code System EntityNameUseR2
v3 map for ObservationRelationshipType | ObservationRelationshipType | v3 Code System ActRelationshipType
FHIR-exanple-2 | http://example.org/fhir/example1 | http://example.org/fhir/example2

4.5 Known Identifier Systems

URL: https://hl7.org/fhir/STU3/identifier-registry.html

This page is part of the FHIR Specification (v3.0.2: STU 3). The current version which supercedes this version is 4.0.1. For a full list of available versions, see the Directory of published versions

4.5 Known Identifier Systems

FHIR Infrastructure Work Group | Maturity Level: 3 | Ballot Status: Trial Use

The following names (URIs) may be used in the system element of the Identifier data type. If a URI is defined here, it SHALL be used in preference to any other identifying mechanism. If an identifier system is not listed here, the correct URI may be determined by working through the following list, in order:

* the HL7 OID Registry

* the documentation associated with the identifier

* consulting the owner of the identifier

* asking on the HL7 vocabulary mailing list

See also the list of known coding systems that can be used in the system element of the Coding data type. Additional identifier systems may be registered on the HL7 FHIR registry at http://hl7.org/fhir/registry .

Important Note: This list of URIs is incomplete and subject to change. Some values may be dropped and others will likely be added in the coming months as HL7 institutes formal processes around URIs in vocabulary.

The URI column indicates the correct value to use in the Identifier.system. The OID is provided for compatibility with HL7 v2 /CDA based systems. Note that any URL in http://example.org is reserved for testing and documentation purposes.

identifier | URI | OID (for non-FHIR systems) | Type | Comment
URIs (W3C): when the identifier is a URI | urn:ietf:rfc:3986 | 2.16.840.1.113883.4.873 | | As defined by RFC 3986 (with many schemes defined in many RFCs). For OIDs and UUIDs, use the URN form (urn:oid: (note: lowercase) and urn:uuid:
United States Social Security Number | http://hl7.org/fhir/sid/us-ssn | 2.16.840.1.113883.4.1 | SB (US) | The SSN is represented in resources with dashes removed
United States Medicare Number | http://hl7.org/fhir/sid/us-medicare | 2.16.840.1.113883.4.572 | SB (US) | Medicare Numbers (HIC or HICN) are represented without any spaces or dashes
United States National Provider Identifier | http://hl7.org/fhir/sid/us-npi | 2.16.840.1.113883.4.6 | PRN (US)
Alaska Driver's License | urn:oid:2.16.840.1.113883.4.3.2 | 2.16.840.1.113883.4.3.2 | DL (US)
Alabama Driver's License | urn:oid:2.16.840.1.113883.4.3.1 | 2.16.840.1.113883.4.3.1 | DL (US)
Arkansas Driver's License | urn:oid:2.16.840.1.113883.4.3.5 | 2.16.840.1.113883.4.3.5 | DL (US)
Arizona Driver's License | urn:oid:2.16.840.1.113883.4.3.4 | 2.16.840.1.113883.4.3.4 | DL (US)
California Driver's License | urn:oid:2.16.840.1.113883.4.3.6 | 2.16.840.1.113883.4.3.6 | DL (US)
Colorado Driver's License | urn:oid:2.16.840.1.113883.4.3.8 | 2.16.840.1.113883.4.3.8 | DL (US)
Connecticut Driver's License | urn:oid:2.16.840.1.113883.4.3.9 | 2.16.840.1.113883.4.3.9 | DL (US)
DC Driver's License | urn:oid:2.16.840.1.113883.4.3.11 | 2.16.840.1.113883.4.3.11 | DL (US)
Delaware Driver's License | urn:oid:2.16.840.1.113883.4.3.10 | 2.16.840.1.113883.4.3.10 | DL (US)
Florida Driver's License | urn:oid:2.16.840.1.113883.4.3.12 | 2.16.840.1.113883.4.3.12 | DL (US)
Georgia Driver's License | urn:oid:2.16.840.1.113883.4.3.13 | 2.16.840.1.113883.4.3.13 | DL (US)
Hawaii Driver's License | urn:oid:2.16.840.1.113883.4.3.15 | 2.16.840.1.113883.4.3.15 | DL (US)
Indiana Driver's License | urn:oid:2.16.840.1.113883.4.3.18 | 2.16.840.1.113883.4.3.18 | DL (US)
Iowa Driver's License | urn:oid:2.16.840.1.113883.4.3.19 | 2.16.840.1.113883.4.3.19 | DL (US)
Idaho Driver's License | urn:oid:2.16.840.1.113883.4.3.16 | 2.16.840.1.113883.4.3.16 | DL (US)
Illinois Driver's License | urn:oid:2.16.840.1.113883.4.3.17 | 2.16.840.1.113883.4.3.17 | DL (US)
Kansas Driver's License | urn:oid:2.16.840.1.113883.4.3.20 | 2.16.840.1.113883.4.3.20 | DL (US)
Kentucky Driver's License | urn:oid:2.16.840.1.113883.4.3.21 | 2.16.840.1.113883.4.3.21 | DL (US)
Louisiana Driver's License | urn:oid:2.16.840.1.113883.4.3.22 | 2.16.840.1.113883.4.3.22 | DL (US)
Massachusetts Driver's License | urn:oid:2.16.840.1.113883.4.3.25 | 2.16.840.1.113883.4.3.25 | DL (US)
Maryland Driver's License | urn:oid:2.16.840.1.113883.4.3.24 | 2.16.840.1.113883.4.3.24 | DL (US)
Maine Driver's License | urn:oid:2.16.840.1.113883.4.3.23 | 2.16.840.1.113883.4.3.23 | DL (US)
Michigan Driver's License | urn:oid:2.16.840.1.113883.4.3.26 | 2.16.840.1.113883.4.3.26 | DL (US)
Minnesota Driver's License | urn:oid:2.16.840.1.113883.4.3.27 | 2.16.840.1.113883.4.3.27 | DL (US)
Missouri Driver's License | urn:oid:2.16.840.1.113883.4.3.29 | 2.16.840.1.113883.4.3.29 | DL (US)
Mississippi Driver's License | urn:oid:2.16.840.1.113883.4.3.28 | 2.16.840.1.113883.4.3.28 | DL (US)
Montana Driver's License | urn:oid:2.16.840.1.113883.4.3.30 | 2.16.840.1.113883.4.3.30 | DL (US)
New York Driver's License | urn:oid:2.16.840.1.113883.4.3.36 | 2.16.840.1.113883.4.3.36 | DL (US)
North Carolina Driver's License | urn:oid:2.16.840.1.113883.4.3.37 | 2.16.840.1.113883.4.3.37 | DL (US)
North Dakota Driver's License | urn:oid:2.16.840.1.113883.4.3.38 | 2.16.840.1.113883.4.3.38 | DL (US)
Nebraska Driver's License | urn:oid:2.16.840.1.113883.4.3.31 | 2.16.840.1.113883.4.3.31 | DL (US)
New Hampshire Driver's License | urn:oid:2.16.840.1.113883.4.3.33 | 2.16.840.1.113883.4.3.33 | DL (US)
New Jersey Driver's License | urn:oid:2.16.840.1.113883.4.3.34 | 2.16.840.1.113883.4.3.34 | DL (US)
New Mexico Driver's License | urn:oid:2.16.840.1.113883.4.3.35 | 2.16.840.1.113883.4.3.35 | DL (US)
Nevada Driver's License | urn:oid:2.16.840.1.113883.4.3.32 | 2.16.840.1.113883.4.3.32 | DL (US)
Ohio Driver's License | urn:oid:2.16.840.1.113883.4.3.39 | 2.16.840.1.113883.4.3.39 | DL (US)
Oklahoma Driver's License | urn:oid:2.16.840.1.113883.4.3.40 | 2.16.840.1.113883.4.3.40 | DL (US)
Oregon Driver's License | urn:oid:2.16.840.1.113883.4.3.41 | 2.16.840.1.113883.4.3.41 | DL (US)
Pennsylvania Driver's License | urn:oid:2.16.840.1.113883.4.3.42 | 2.16.840.1.113883.4.3.42 | DL (US)
Rhode Island Driver's License | urn:oid:2.16.840.1.113883.4.3.44 | 2.16.840.1.113883.4.3.44 | DL (US)
South Carolina Driver's License | urn:oid:2.16.840.1.113883.4.3.45 | 2.16.840.1.113883.4.3.45 | DL (US)
South Dakota Driver's License | urn:oid:2.16.840.1.113883.4.3.46 | 2.16.840.1.113883.4.3.46 | DL (US)
Tennessee Driver's License | urn:oid:2.16.840.1.113883.4.3.47 | 2.16.840.1.113883.4.3.47 | DL (US)
Texas Driver's License | urn:oid:2.16.840.1.113883.4.3.48 | 2.16.840.1.113883.4.3.48 | DL (US)
Utah Driver's License | urn:oid:2.16.840.1.113883.4.3.49 | 2.16.840.1.113883.4.3.49 | DL (US)
Virginia Driver's License | urn:oid:2.16.840.1.113883.4.3.51 | 2.16.840.1.113883.4.3.51 | DL (US)
Vermont Driver's License | urn:oid:2.16.840.1.113883.4.3.50 | 2.16.840.1.113883.4.3.50 | DL (US)
Washington Driver's License | urn:oid:2.16.840.1.113883.4.3.53 | 2.16.840.1.113883.4.3.53 | DL (US)

Wisconsin Driver's License | urn:oid:2.16.840.1.113883.4.3.55 | 2.16.840.1.113883.4.3.55 | DL (US)
West Virginia Driver's License | urn:oid:2.16.840.1.113883.4.3.54 | 2.16.840.1.113883.4.3.54 | DL (US)
Wyoming Driver's License | urn:oid:2.16.840.1.113883.4.3.56 | 2.16.840.1.113883.4.3.56 | DL (US)

4.6 Terminology Service

URL: https://hl7.org/fhir/STU3/terminology-service.html

This page is part of the FHIR Specification (v3.0.2: STU 3). The current version which supercedes this version is 4.0.1. For a full list of available versions, see the Directory of published versions

4.6 Terminology Service

FHIR Infrastructure Work Group | Maturity Level: 5 | Ballot Status: Trial Use

This specification includes support for the provision of a terminology service - that is, a service that lets healthcare applications make use of codes and value sets without having to become experts in the fine details of code system, value set and concept map resources, and the underlying code systems and terminological principles. A server that supports all the functionality described here can be described as a "FHIR Terminology Service", and SHALL conform to the Terminology Service Capability Statement. Note that servers can declare that they provide terminology services in their capability statement:

```
<CapabilityStatement xmlns="http://hl7.org/fhir">
  <!-- snip -->
  <instantiates value="http://hl7.org/fhir/CapabilityStatement/terminology-server"/>
  <!-- snip -->
</CapabilityStatement>
```

4.6.1 Security

Generally, SSL SHOULD be used for all production health care data exchange. Even though terminology servers do not generally handle patient information directly, observers may still be able to infer information about patients by observing the codes and concepts used in terminology service operations, so encryption is still recommended.

A terminology server may choose not to authenticate the clients/users in any fashion, but can do so in order to limit or account for usage. For a value set maintenance server that allows terminologies to be edited, some form of authorization and/or authentication would be appropriate. This specification does not require any particular approach to security.

4.6.2 Basic Concepts

A FHIR terminology service is simply a set of functions built on the definitions provided by a collection of CodeSystem, ValueSet and ConceptMap resources, with additional inherently known terminologies providing support.

The terminology service builds on the basic principles for using terminologies in FHIR. Implementers should be familiar with:

* Using codes in FHIR

* The CodeSystem resource

* The ValueSet resource

* The ConceptMap resource

In addition, implementers should be familiar with the operations framework. Further useful information about terminologies may be found in:

* Underlying Principles: HL7 v3 Core Principles

* SNOMED CT technical documentation . Note: "namespace" is used differently here from the way it is used by IHTSDO (see discussion here)

4.6.2.1 External Code Systems

In order to be used with a value set, code systems and their content must be defined somewhere. They can be defined explicitly using the code system resource, or they can be defined elsewhere, and then used in a value set by referencing the correct system url. The FHIR specification defines a set of namespaces for commonly encountered code systems, and defines how some work with FHIR (e.g. SNOMED CT, LOINC, RxNorm). These code systems are often large, and have many internally defined properties that are part of their formal definitions. The CodeSystem resource is not an appropriate way to distribute the contents of these code systems; the standard FHIR code system resource simply represents the properties of the code system. Instead, these terminologies provide their own distribution formats, and it is assumed that the content of these code systems are externally known to the terminology server.

Most useful terminology servers will make one or more of these external code systems available for use within the value sets that they manage. The list of additional terminologies that a terminology server supports beyond those defined in its value sets is published to clients by referencing code system resources in the server's Capability Statement.

```
{
 "resourceType" : "CapabilityStatement",
 "extension" : [
   {
     "url" : "http://hl7.org/fhir/StructureDefinition/capabilitystatement-supported-system",
     "valueUri" : "http://loinc.org"
   }]
}
```

This extension is added to the root Capability Statement.

4.6.2.2 Implementation Note

When a terminology server exposes an external code system, it makes a set of services available internally that serve the operational interfaces below. The internal server depends on the following logical information for a terminology:

* its URL (namespace, and how versioning works)

* what codes are valid

* what properties can be used to select codes

* what implicit value sets exist

The FHIR specification itself defines these things for common terminologies (including SNOMED CT, LOINC, RxNorm), and provides the CodeSystem infrastructure for supporting typical relatively simple small code systems.

Implementers Note: Implementers interested in working with existing published terminologies for which the CodeSystem infrastructure is not suitable should discuss their needs with HL7 to get the list above extended.

Note: A terminology service may choose to expose additional external code system specific related functionality such as summation, or structured search, but these services are outside the scope of the FHIR terminology service.

4.6.2.3 Operations across all value sets

For some of the operations below, it can be useful to perform them across all value sets known to the system. For example, $expand using a text filter, and searching all value sets at once. A special value set is defined that means "all value sets known to the server":

```
http://hl7.org/fhir/ValueSet/@all
```

Technically, this value set automatically imports all the existing value sets on the server. Note that this URL has no fixed meaning - its interpretation is server specific (e.g. whether it includes all versions of all value sets). This URL can only be used as a parameter to the operations described on this page.

4.6.2.4 Terminology Maintenance

The terminology service uses the code systems and value set resources defined on the system - both the implicit ones associated with the external code systems and those explicitly available at the /CodeSystem and /ValueSet endpoints - to serve the operational interface defined below. As code systems and value sets are created, updated or deleted, the outcomes of the operational services change. A terminology server should validate incoming resources, and ensure integrity of the terminology services. Typically, servers provide a test and production environment, but there is no explicit notion of this in the interface itself.

4.6.3 Value Set Expansion

A value set describes a set of rules for what codes or concepts are considered to be in the value set. These rules might be simple (e.g. a direct list of codes from a specified version of a code system), or they might be quite complex (e.g. all codes with a particular property from an unspecified version of a code system).

A FHIR enabled application can simply ask a terminology server to figure out all the details, and return it a list of the current codes in the value set. This is known as "expanding" the valueset. As a summary, the client passes the server the following information:

* the value set (either by its URL on the RESTful interface, by its logical identifier (ValueSet.url), or directly as a parameter to the call)

* (Optionally) a text filter to use to restrict the codes that are returned (e.g. user input text). It is left to server discretion to choose how to apply the text filter

* (Optionally) a date at which the expansion should be evaluated (usually, this is the current date/time, but there are circumstances where that is not appropriate)

* (Optionally) which page to retrieve - asking the server to break the expansion into a set of chunks

* (Optionally) a reference to an ExpansionProfile resource that supplies additional information about how to perform the expansion

The server returns a value set that contains the current list of codes that meet the filter criteria (or an OperationOutcome with an error if the expansion fails). Note that some value sets expand to many thousands of codes, or even an infinite number, and for these, the server SHOULD return an error code too-costly. In these cases the client can try again with a more specific text filter to reduce the number of codes returned - this may result in a valid expansion.

For further information, consult the definition of the operation.

The $expand operation has support for paging - for a client to retrieve a big expansion in a set of partial views, in order to present the most optimal user experience. The client specifies both an offset and a count - how many codes per page, and where in the sequence to start. The return expansion specifies the number of concepts in the expansion, and the offset at which this partial view starts. Note that all expansions SHOULD include the total code count, but the offset element SHALL only exist when paging is being used. Expansions that are hierarchical trees of concepts are not subject to paging and the server simply returns the entire expansion.

Some example uses for the expansion operation:

* get a list of codes to display in a User interface (e.g. a drop down interface)

* a variation on this is to offer the user a text box to type in. As the user types, call the expand operation to provide the user with a list of matching codes/concepts (like a browser search)

* fetch a list of codes to use when generating software programming instructions

* get a list of codes so that software can check whether a code is valid or not in a particular context

Examples

Expanding a value set that is already registered on the server as "23", with a text filter of "abdo":

```
GET [base]/ValueSet/23/$expand?filter=abdo
```

Expanding a value set that is specified by the client (using JSON):

```
POST [base]/ValueSet/$expand
[other headers]

{
  "resourceType" : "Parameters",
  "parameter" : [
     {
     "name" : "valueSet",
     "resource" : {
       "resourceType" : "ValueSet",
     [value set details]
     }
   }
  ]
}
```

The server responds with a value set (this example in XML):

```
HTTP/1.1 200 OK
[other headers]

<ValueSet xmlns="http://hl7.org/fhir">
  <!-- the server SHOULD populate the id with a newly created UUID
    so clients can easily track a particular expansion  -->
  <id value="43770626-f685-4ba8-8d66-fb63e674c467"/>
  <!-- no need for meta, though it is allowed for security labels, profiles -->

  <!-- other value set details -->
  <expansion>
    <!-- when expanded -->
    <timestamp value="20141203T08:50:00+11:00"/>
  <contains>
    <!-- expansion contents -->
  </contains>
  </expansion>
</ValueSet>
```

4.6.4 Concept Lookup / Decomposition

A system can ask a terminology server to return a set of information about a particular system/code combination using the lookup operation. The server returns information for both display and processing purposes. The client passes the server the following information:

* the code value (either a code, or a Coding data type)

* (Optionally) the id or the url of the code system in which the code is being checked

* (Optionally) a date at which the code information should be returned (usually, this is the current date/time, but there are circumstances where that is not appropriate)

* (Optionally) a set of properties to return about the code

The server returns some or all of the following information:

* a human description of the system

* a recommended display for the code

* properties of the code (e.g. status)

* other designations for the code (a value, optionally with language and/or a use code)

* relationships between this code and other codes (parent/child properties, etc)

* Component properties of the specified code (e.g. to support reasoning) (e.g. decomposition)

The recommended display for the code is a text representation of the code that the terminology server recommends as the default choice to show to the user, though a client may choose out of the other designations if it has reason to.

If the client does not ask for any particular properties to be returned, it is at the discretion of the server to decide which properties to return (though note that the "version" property is always returned if the code system has a version).

Examples

Looking up a code in a code system:

```
GET [base]/CodeSystem/loinc/$lookup?code=1963-8
```

Note that the logical id "loinc" is not a reliable identifer across systems; each server assigns logical ids to code system resources however it sees fit. A more reliable query is this:

```
GET [base]/CodeSystem/$lookup?system=http://loinc.org&code=1963-8&property=code&property=display&property=designations
```

Lookup the code system using a Coding (this example in XML):

```
POST [base]/CodeSystem/$lookup
[other headers]

<Parameters xmlns="http://hl7.org/fhir">
  <parameter>
    <name value="coding"/>
    <valueCoding>
      <system value="http://loinc.org"/>
      <code value="1963-8"/>
    </valueCoding>
  </parameter>
</Parameters>
```

The server responds with a set of information (JSON this time):

```
HTTP/1.1 200 OK
[other headers]

{
  "resourceType" : "Parameters",
  "parameter" : [
    {
    "name" : "name",
    "valueString" : "LOINC"
  },
  {
    "name" : "version",
    "valueString" : "2.56"
  },
  {
    "name" : "display",
    "valueString" : "Bicarbonate [Moles/volume] in Serum"
  },
  {
    "name" : "abstract",
    "valueString" : "false"
  }
  ]
}
```

4.6.4.1 Standard Properties

The following properties are defined for all code systems:

Name	Usage
system	The name of the code system
version	The version of the code system used for the look up operation
display	The recommended display for the code, if one is known
definition	The definition for the code
designation	Other designations for the code
lang.X	Designations in language X (where X is an IETF Language code, see BCP-47
parent	Parent codes for this code (for code systems with a defined hierarchy)
child	child codes of this code (for code systems with a defined hierarchy)

In addition, any property codes defined by the code system (CodeSysem.property.code) can be used (and see the definitions for SNOMED CT, LOINC, and RxNorm).

4.6.5 Value Set Validation

One way to determine whether a code is in a value set is to expand the value set (as described above), and then look at the returned codes to see if the code is in the expansion. However this is not an efficient way to test whether a code is valid, and for some value sets (e.g. with infinite number of members), it cannot work. Instead, a FHIR terminology server provides a "validate-code" operation. The client passes the server the following information:

* the value set (either by its URL on the RESTful interface, by its logical identifier (ValueSet.url), or directly as a parameter to the call)

* the code value (either a code + system, a Coding data type, or a CodeableConcept

* (Optionally) a date at which the expansion should be evaluated (usually, and by default, this is the current date/time, but there are circumstances where that is not appropriate)

The server returns a true/false indicating whether the code/concept is valid, and a list of errors and warnings associated with it. The server should also return an appropriate display for the concept for use in a UI context.

Note that if the server is passed a CodeableConcept, the server is able to check whether any of the codes are valid against the value set, and also check whether multiple codings are allowed and/or the codings provided are consistent with each other.

Every code system has an implicit value set that is "all the concepts defined in the code system" (CodeSystem.valueSet). For some code systems, these value set URIs are defined in advance (e.g. for LOINC, it is http://loinc.org/vs). However for some

code systems, they are not known. Clients can refer to these implicit value sets by providing the URI for the code system itself.

Examples

Simple validation of a code/system against a known value set:

```
GET [base]/ValueSet/23/$validate-code?system=http://loinc.org&code=1963-8&display=test
```

Validate a CodeableConcept against a client specified value set (this example in JSON):

```
POST [base]/ValueSet/$validate-code
[other headers]

{
  "ResourceType" : "Parameters",
  "parameter" : [
    {
    "name" : "coding",
    "valueCodeableConcept" : {
      "coding" : {
        "system" : "http://loinc.org",
          "code" : "1963-8",
      "display" : "test"
      }
    }
  },
  {
    "name" : "valueSet",
    "resource": {
      "resourceType" : "ValueSet",
    [etc]
    }
  }
  ]
}
```

The server responds with validation information (JSON this time):

```
HTTP/1.1 200 OK
[other headers]

{
  "resourceType" : "Parameters",
  "parameter" : [
    {
    "name" : "result",
    "valueBoolean" : "false"
  },
  {
    "name" : "message",
    "valueString" : "The display \"test\" is incorrect"
  },
  {
    "name" : "display",
    "valueString" : "Bicarbonate [Moles/volume] in Serum"
  }
  ]
}
```

4.6.6 Subsumption testing

To test the subsumption relationship between code/Coding A and code/Coding B, perform a $subsumes operation. Subsumption testing is based on the CodeSystem definition of subsumption. The client passes the server the following information:

* the system that identifies the code system in which subsumption testing is to be performed (either by invoking the operation on the code system directly, or referring to it by its canonical URL)

* Concepts A and B - either as codes, or Codings

* (Optionally) the version of the code system to use (mostly, this should not matter)

If the client passes Codings, it is allowed to use code system values that are different from the code system in which subsumption testing is to be performed. In this case, the server SHALL return an error unless the relationships between the various code systems is well defined.

If the concepts can be compared, then the server returns an outcome code:

equivalent	Concepts A and B are equivalent
subsumes	Concept A subsumes Concept B
subsumed-by	Concept A is subsumed by Concept B
not-subsumed	Concepts A and B are not related by any subsumption relationship

Examples

Test whether a SNOMED CT Concept 'Disorder of liver' (235856003) subsumes 'Viral hepatitis' (3738000):

```
GET [base]/CodeSystem/$subsumes?system=http://snomed.info/sct&codeA=235856003&codeB=3738000
```

Or using Codings:

```
POST [base]/CodeSystem/$subsumes
```

```
[other headers]

<Parameters xmlns="http://hl7.org/fhir">
  <!-- Subsumption testing - use SNOMED CT rules -->
  <parameter>
    <name value="system"/>
    <valueUri value="http://snomed.info/sct"/>
  </parameter>
  <!-- Australian distribution -->
  <parameter>
    <name value="version"/>
    <valueString value="http://snomed.info/sct/32506021000036107/version/20160430"/>
  </parameter>
  <parameter>
    <name value="codingA"/>
    <valueCoding>
      <system value="http://snomed.info/sct"/>
      <code value="235856003"/>
    </valueCoding>
  </parameter>
  <parameter>
    <name value="codingB"/>
    <valueCoding>
      <system value="http://snomed.info/sct"/>
      <code value="3738000"/>
    </valueCoding>
  </parameter>
</Parameters>
```

Server response:

```
HTTP/1.1 200 OK
[other headers]

{
  "resourceType" : "Parameters",
  "parameter" : [
    {
    "name" : "outcome",
    "valueCode" : "subsumes"
  },
  ]
}
```

4.6.7 Batch Validation

It is also possible to validate a set of concepts against their relevant value sets by using the $validate-code operation in a Batch interaction.

Example

A request to validate 2 concepts from a CDA document, with OIDs for value set identifiers:

```
POST [base]
[other headers]

{
  "ResourceType": "Bundle",
  "type": "batch",
  "entry": [{
    "request": {
      "method": "Get",
      "url": "ValueSet/$validate-code?system=http://loinc.org&code=2324-4&uri=urn:oid:1.2.3.4.6"
    }
  },
  {
    "request": {
      "method": "GET",
      "url": "ValueSet/$validate-code?system=http://snomed.info/sct&codes=22298006&uri=urn:oid:1.2.3.4.7"
    }
  }]
}
```

The server responds with a series of validation outcomes (JSON this time):

```
HTTP/1.1 200 OK
[other headers]

{
  "ResourceType": "Bundle",
  "type": "batch-response",
  "entry": [{
    "resource": {
      "resourceType": "Parameters",
      "parameter": [{
        "name": "result",
        "valueBoolean": "false"
      },
      {
        "name": "message",
        "valueString": "'2324-4' is not a valid LOINC code"
      }]
```

```
    }
  },
  {
    "resource": {
      "resourceType": "Parameters",
      "parameter": [{
        "name": "result",
        "valueBoolean": "false"
      },
      {
        "name": "message",
        "valueString": "The concept is not in the specified value set (\"Organisms\")"
      },
      {
        "name": "display",
        "valueString": "Myocardial infarction"
      }]
    }]
  }
```

4.6.8 Translations

A client can ask a server to translate a concept from one value set to another. Typically, this is used to translate between code systems (e.g. from LOINC to SNOMED CT, or from a HL7 V3 code to a HL7 V2 code). The client calls the translate operation and passes the following parameters:

* a code + system, Coding, or CodeableConcept

* a Concept Map to use for the translation

* the value set for the context of the source

* the value set for the destination

The client passes either a concept map, or the value sets for the source and destination context. If there is no concept map, then the server may determine the appropriate map to use from context provided in the value sets. If there is no particular context, the appropriate value sets would be the value sets for the entire coding system at question (e.g. from http://snomed.info/sct to http://loinc.org/vs). The server performs the translation as it is able based on the concept maps that it knows about. If no single mapping can be determined, then the server returns an error. Some servers may require a concept map to use for the translation.

Example

Translate from FHIR Composition status to HL7 v3 Act Status (based on this defined concept map:

```
GET [base]/ConceptMap/$translate?system=http://hl7.org/fhir/composition-status
  &code=preliminary&source= http://hl7.org/fhir/ValueSet/composition-status
  &target=http://hl7.org/fhir/ValueSet/v3-ActStatus
```

The server responds with validation information:

```
HTTP/1.1 200 OK
[other headers]

{
  "resourceType" : "Parameters",
  "parameter" : [
    {
    "name" : "result",
    "valueBoolean" : "true"
    },
    {
      "name" : "outcome",
      "valueCoding" : {
        "system" : "http://hl7.org/fhir/v3/ActStatus",
        "code" : "active",
      }
    }
  ]
}
```

4.6.9 Batch Translation

It is also possible to translate a set of concepts against their relevant value sets by using the $translate operation in a Batch interaction.

Example

A request to translate 2 concepts from a CDA document, with OIDs for value set identifiers:

```
POST [base]
[other headers]

{
  "ResourceType": "Bundle",
  "type": "batch",
  "entry": [{
    "resource": {
      "ResourceType": "Parameters",
      "parameter": [{
        "name": "concept",
```

```
        "valueCodeableConcept": {
          "system": "http://loinc.org",
          "code": "2324-4"
        }
      },
      {
        "name": "target",
        "valueUri": "urn:oid:1.2.3.4.6"
      }]
    },
    "request": {
      "method": "POST",
      "url": "ConceptMap/$translate"
    }
  },
  {
    "resource": {
      "ResourceType": "Parameters",
      "parameter": [{
        "name": "concept",
        "valueCodeableConcept": {
          "system": "http://snomed.info/sct",
          "code": "22298006"
        }
      },
      {
        "name": "target",
        "valueUri": "urn:oid:1.2.3.4.7"
      }]
    },
    {
      "request": {
        "method": "POST",
        "url": "ConceptMap/$translate"
      }
    }]
  }
```

The server responds with a series of translation outcomes:

```
HTTP/1.1 200 OK
[other headers]

{
  "ResourceType": "Bundle",
  "type": "batch-response",
  "entry": [{
    "resource": {
      "resourceType": "Parameters",
      "parameter": [{
        "name": "result",
        "valueBoolean": "false"
      },
      {
        "name": "message",
        "valueString": "'2324-4' is not a valid LOINC code"
      }]
    }
  },
  {
    "resource": {
      "resourceType": "Parameters",
      "parameter": [{
        "name": "result",
        "valueBoolean": "true"
      },
      {
        "name": "outcome",
        "valueCodeableConcept": {
          "coding": {
            "system": "http://example.com/codesystems/example",
            "code": "xxxx"
          }
        }
      }]
    }
  }]
}
```

4.6.10 Maintaining a Closure Table

The 5 operations Expand, Lookup, Validate, Subsumes, and Translate account for most operational requirements associated with terminology use. However, there is one difficult but important use case that they do not address, which is integrating terminologically based logic into application searches.

A typical example of this is a user that wants to find any observations for male patients over the age of 50 who attended a particular clinic within a particular 2 week period, with a diagnosis of gout, and who had an elevated serum creatinine.

In this case, both "diagnosis of gout" and "serum creatinine" involve value set and/or subsumption queries (e.g. against SNOMED CT and LOINC respectively). This search has to be executed by some logical processing engine that knows how to find patient related data in a given persistence store. Often, this is some kind of SQL query, though many other technological choices are available. However, this is done, the challenge with an operation like this is to integrate the terminological knowledge into a search execution that also covers other relationships expressed in the search criteria.

One approach to this problem would be to using the expand operation above, so that the system executing the search could generate expansions, and then search for these expansions. This has a couple of problems:

* the list of subsumed codes could be very long, and the search operation becomes correspondingly inefficient

* the expansion of the subsumption might not be closed, and so the search operation cannot be correct

An alternative approach is to generate a transitive closure table which lists all the possible transitive subsumption relationships, and allows for rapid execution of these kind of queries . However, this has other problems:

* the subsumption table can be very large (>500000 records for SNOMED CT), even though very few of the codes are used

* subsumption tables are generally built up front, and do not deal with new codes as they are encountered very well

* they still do not offer a solution for non-closed expansions

This is the main reason why most systems do not support post-coordination or other forms of coded expressions.

In FHIR, this problem is solved by building a closure table on the fly as new codes are seen. This technique leaves the FHIR terminology server responsible for the terminological reasoning and the client responsible for the closure table maintenance. To the client, it doesn't matter whether the concept is post-coordinated or not. Here's a description of how the process works:

* the client defines a name associated with a particular context in which it wishes to maintain a subsumption based closure table

* the client registers this name with the FHIR Terminology server using the $closure operation (described below), with only one parameter, the name of the context

* any time the client system encounters a new Coding that is not entered in the closure table, it calls the $closure operation with the context name, and the Coding value it has encountered

* the server returns a ConceptMap resource with a list of new entries (code : system -> code : system) that the client should add to its closure table

* the server can indicate that entries should be removed from the table by providing a (code : system -> code : system) with equivalence "unmatched" (though it's not known why that would be needed)

* the client makes these entries into its closure table

* to facilitate the initialization process, a client can call $closure with multiple Coding values

The $closure operation takes 2 parameters:

* closure table context name

* concepts to enter into the table (0 or more - 0 codings is a request to (re-)initialise the table)

The operation returns a concept map which has a list of mappings that represent new entries to make in the closure table. The subsumption testing performed when building a closure table is the same as for the $subsumes operation, and is based on the CodeSystem definition of subsumption.

The closure table can be resynchronized by passing an additional "version" parameter, which is a value taken from the version in one of the delta responses. This is a request to replay all the mapping changes since that delta was sent.

4.6.10.1 Initializing a Closure Table

Before it can be used, a closure table has to be initialised. To initialise a closure table, POST the following to [base]/ConceptMap/$closure:

```
{
  "resourceType" : "Parameters",
   "parameter" : [{
     "name" : "name",
     "valueString" : "[name]"
  }]
}
```

A successful response is a 200 OK from the server, with an associated ConceptMap:

```
{
    "resourceType": "ConceptMap",
    "id": "[name]",
    "version": "0",
    "name": "Closure Table [name] Creation",
    "status": "active",
    "experimental": true,
    "date": "2015-12-20T23:10:55Z"
}
```

If there is an error (usually involving the closure name) the server returns a HTTP status 400 with an operation outcome:

```
{
  "resourceType": "OperationOutcome",
  "text": {
    "status": "generated",
```

```
    "div": "<div xmlns=\"http://www.w3.org/1999/xhtml\"><p>invalid closure name \"invalid-id!\":</p></div>"
  },
  "issue": [
    {
      "severity": "error",
      "details": {
        "text" : "invalid closure name \"invalid-id!\""
      }
    }
  ]
}
```

What closure names are valid is at the discretion of the server.

4.6.10.2 Adding to a Closure Table

When the consumer (client) encounters a new code, it POSTs the following to [base]/ConceptMap/$closure:

```
{
  "resourceType" : "Parameters",
  "parameter" : [{
    "name" : "name",
    "valueString" : "[name]"
  }, {
    "name" : "concept",
    "valueCoding" : {
       "system" : "http://snomed.info/sct",
       "code" : "22298006",
       "display" : "Myocardial infarction"
    }
  }]
}
```

Note that this example only includes one concept, but more than one is allowed:

```
{
  "resourceType" : "Parameters",
  "parameter" : [{
    "name" : "name",
    "valueString" : "[name]"
  }, {
    "name" : "concept",
    "valueCoding" : {
       "system" : "http://snomed.info/sct",
       "code" : "22298006",
       "display" : "Myocardial infarction"
    }
  }, {
    "name" : "concept",
    "valueCoding" : {
       "system" : "http://snomed.info/sct",
       "code" : "128599005",
       "display" : "Structural disorder of heart"
    }
  }]
}
```

The response varies depending on the conditions on the server. Possible responses: If the closure table has not been initialised: Return a 404 Not Found with

```
{
  "resourceType": "OperationOutcome",
  "text": {
    "status": "generated",
    "div": "<div xmlns=\"http://www.w3.org/1999/xhtml\"><p>invalid closure name \"[name]\":</p></div>"
  },
  "issue": [
    {
      "severity": "error",
      "details": {
        "text" : "invalid closure name \"[name]\""
      }
    }
  ]
}
```

If the closure table needs to be reinitialised: Return a 422 Unprocessable Entity with

```
{
  "resourceType": "OperationOutcome",
  "text": {
    "status": "generated",
    "div": "<div xmlns=\"http://www.w3.org/1999/xhtml\"><p>closure \"[name\" must be reinitialised</p></div>"
   },
   "issue": [{
       "severity": "error",
       "details": {
         "text" : "closure \"[name]\" must be reinitialised"
       }
     }
   ]
}
```

The server should only send this when it's underlying terminology conditions have been changed (e.g. a new version of SNOMED CT has been loaded). When a client gets this, it's only choice is to initialise the closure table, and process all the codes in the closure table again (the assumption here is that the system has some external source of 'all the codes' so it can rebuild the table again). If the concept(s) submitted are processed ok, but there's no new concepts, or no new entries in the table, return a 200 OK with :

```
{
    "resourceType": "ConceptMap",
    "id": "[name]",
    "version": "[version]",
    "name": "Updates for Closure Table [name]",
    "status": "active",
    "experimental": true,
    "date": "2015-12-20T23:12:55Z"
}
```

If there's new entries in the closure table, the server returns a 200 OK with:

```
{
    "resourceType": "ConceptMap",
    "id": "b87db127-9996-4d0c-bda9-a278d7a24a69",
    "version": "[version]",
    "name": "Updates for Closure Table [name]",
    "status": "active",
    "experimental": true,
    "date": "2015-12-20T23:16:24Z",
    "element": [{
        "codeSystem": "http://snomed.info/sct",
        "code": "22298006",
        "target": [{
           "codeSystem": "http://snomed.info/sct",
           "code": "128599005",
           "equivalence": "subsumes"
        }]
    }]
}
```

Notes

* The server can return multiple elements, each with 1 or more targets

* servers may return the relationship represented in either direction

* it's important to understand the relationship the right way around. From the spec: The equivalence is read from target to source (e.g. the target is 'wider' than the source). So in this case, 128599005 (Structural disorder of heart) subsumes 22298006 (Myocardial infarction)

* In the $closure operation, the response never explicitly states that a code is subsumed by itself. Clients should assume that this is implicit

* The version is important. Each new invocation of the $closure operation returns a new version of the concept map. The server must keep track of the versions is has issued for replay (see below)

* As well as entering codes that are actually used, the client also enters search terms into the closure table

* The combination of the system and code is the key to the closure table; if the server encounters two different codes that have the same meaning (e.g. syntactical variation), it should create an "equals" relationship between them

4.6.10.3 Re-running Closure operation

Given the way that the closure operation functions, it's possible for a client to lose a response from the server before it is committed to safe storage (or the client may not have particularly safe storage). For this reason, when a client is starting up, it should check that there has been no missing operations. It can do this by passing the last version (from the Concept Map response) it is sure it processed in the request:

```
{
  "resourceType" : "Parameters",
   "parameter" : [{
     "name" : "name",
     "valueString" : "[name]"
  }, {
     "name" : "version",
     "valueString" : "3"
  }]
 }
```

That's a request to return all the additions to the closure table since version 3. The server returns its latest version in the concept map, along with anything added to the closure table since version 3 (not including version 3)

Notes:

* The client can pass a concept or version, but not both

* These examples (and my server) use a serially incrementing sequential integer, but this is not required, and clients should not assume that there is any meaning or order in the version. Just recall the last version, and treat it as a magic value. There is, however, one special value: '0'. Passing a last version of 0 should be understood as resyncing the entire closure table

4.6.10.4 Making use of the Closure Table

The client uses the result of the closure operation to maintain a closure table. Simplistically, it might look like this:

Scope | Source | Target
patient-problems | http://snomed.info/sct|22298006 | http://snomed.info/sct|128599005
patient-problems | http://snomed.info/sct|24595009 | http://snomed.info/sct|90560007
obs-code | http://loinc.org|14682-9 | http://loinc.org|LP41281-4

The client can then use a table like this as part of its general search conditions. Using the example from above: "Find any observations for male patients over the age of 50 who attended a particular clinic within a particular 2 week period, with a diagnosis of gout, and who had an elevated serum creatinine." This query could be done, for instance, with an SQL query like this:

```
Select * from Observations, Patients, Encounters, Conditions, Observations as Obs2 where
  Observations.patient = Patients.Key and Patients.Age > 50 and
  Observations.encounter = Encounters.Key and Encounter.clinic = [key]
    and encounter.date >= [date] and encounter.date <= [date] and
  Conditions.patient = Patients.Key and Conditions.code
    in (select Source From ClosureTable
      where Scope = "patient-problems" and Target = "http://snomed.info/sct|90560007") and
  Obs2.patient = Patients.Key and Obs2.value > 0.19 and Obs2.code
    in (select Source From ClosureTable
      where Scope = "obs-code" and Target = "http://loinc.org|LP41281-4")
```

Note that in real clinical systems, tables are usually far more structured than this example implies, and the query is correspondingly more complex. The closure table would usually be normalised - this example is kept simple to demonstrate the concept.

4.7 Resource CodeSystem - Content

URL: https://hl7.org/fhir/STU3/codesystem.html

This page is part of the FHIR Specification (v3.0.2: STU 3). The current version which supercedes this version is 4.0.1. For a full list of available versions, see the Directory of published versions

Vocabulary Work Group | Maturity Level: 5 | Trial Use | Compartments: Not linked to any defined compartments

A code system resource specifies a set of codes drawn from one or more code systems.

4.7.1 Scope and Usage

The FHIR terminology specification is based on two key concepts, originally defined in HL7 v3 Core Principles :

* code system - defines a set of codes with meanings (also known as enumeration, terminology, classification, and/or ontology)

* value set - selects a set of codes from those defined by one or more code systems

Code systems define which codes (symbols and/or expressions) exist, and how they are understood. Value Sets select a set of codes from one or more code systems to specify which codes can be used in a particular context.

The CodeSystem resource is used to declare the existence of a code system, and its key properties:

* Identifying URL and version

* Description, Copyright, publication date, and other metadata

* Some key properties of the code system itself - whether it's case sensitive, version safe, and whether it defines a compositional grammar

* What filters can be used in value sets that use the code system in a ValueSet.compose element

* What properties the concepts defined by the code system

In addition, the CodeSystem resource may list some or all of the concepts in the code system, along with their basic properties (code, display, definition), designations, and additional properties.

The CodeSystem resource is not intended to support the process of maintaining a code system. Instead, the focus is on publishing the properties and optionally the content of a code system for use throughout the FHIR eco-system, such as to support value set expansion and validation. Note that the important existing (large) code systems (SNOMED CT, LOINC, RxNorm, ICD family, etc) all have their own distribution formats, and there is no intent that the CodeSystem resource be used for distributing these kind of terminologies. Instead, it is intended to be used for distributing the smaller ad-hoc code systems that are ubiqutiously encountered through out the healthcare process.

4.7.2 Boundaries and Relationships

* Code systems are used in ValueSet resources

* The Coding data type refers to CodeSystem resources by their canonical URL

* The CodeSystem resource design is based on the functionality described in the OMG CTS 2 specification. CodeSystem resources can be converted to CTS2 code system resources.

The CodeSystem resource defines the content of a code system, and also its preferred identifier. The NamingSystem resource identifies the existence of a code or identifier system, and its possible and preferred identifiers. The key difference between the resources is who creates and manages them - CodeSystem resources are managed by the owner of the code system resource, who can properly define the features and content of the code system. NamingSystem resources, on the

other hand, are frequently defined by 3rd parties that encounter the code system in use, and need to describe the use, but do not have the authority to define the features and content. Additionally, there may be multiple authoritative NamingSystem resources for a code systemn, but there should only be one CodeSystem resource.

4.7.3 Background and Context

When using code systems and value sets, proper differentiation between a code system and a value set is important. This is one very common area where significant clinical safety risks occur in practice. Implementers should be familiar with the content in Using Codes in resources.

Each code system has 2 different URLs that can be used to reference it - its logical identifier, and its location.

The location of the code system is a URL by which it may be retrieved, usually from a FHIR server, and may be a relative reference to a code system on the same server. The logical identifier is in the code system itself, in CodeSystem.url. This is the logical identity (sometimes called the canonical URL) that refers to this code system across all systems. Ideally, the URL should also be the location of the master version of the code system, though this is not always possible.

For example, the code systems published as part of FHIR all have a logical URL which is also a location by which they may be accessed in the FHIR specification itself. However, while a new version of the FHIR Specification is being prepared, code systems that are published in the drafts will not be found in the current FHIR specification.

Because it is common practice to copy (cache) code systems locally, most references to code systems can be either a logical or a literal URL.

4.7.3.1 CodeSystem Identification

A code system has 3 identifiers:

* CodeSystem.id: the logical id on the system that holds the code system - this changes as it moves from server to server (this id, with the server address prepended, is called the 'literal identity' of the resource)

* CodeSystem.url: the canonical URL that never changes for this code system - it is the same in every copy. Ideally, the URL should also be the location of the master version of the code system, though this is not always possible

* CodeSystem.identifier: A system/value pair that is used to identify the code system in other contexts (such as an OID in an HL7 v3 specification)

For further information regarding resource identification, see Resource Identity.

This means that each code system has 2 different URLs that can be used to reference it - its canonical url, and its local location from which it may be retrieved. Because it is common practice to copy (cache) code systems locally, most references to code systems use the canonical URL.

For example, the code systems published as part of FHIR all have a canonical URL which is also a location by which they may be accessed in the FHIR specification itself. Note, though, that while a new version of the FHIR Specification is being prepared, code systems that are published in the drafts will not be found in the published FHIR specification at their canonical URL.

Alternatively, the identifier and version elements may be used to reference this code system in a design, a profile, a CDA template or HL7 v3 message (in the CD data type codeSystem and codeSystemVersion properties). These different contexts may make additional restrictions on the possible values of these elements. The identifier is generally not needed when using code systems in a FHIR context, where the canonical URL is always the focus.

4.7.4 Resource Content

* Structure

* UML

* XML

* JSON

* Turtle

* R2 Diff

* All

Structure

Name | Flags | Card. | Type | Description & Constraints
CodeSystem | I | | DomainResource | A set of codes drawn from one or more code systems + Within a code system definition, all the codes SHALL be unique Elements defined in Ancestors: id, meta, implicitRules, language, text, contained, extension, modifierExtension
url | ? | 0..1 | uri | Logical URI to reference this code system (globally unique) (Coding.system)
identifier | ? | 0..1 | Identifier | Additional identifier for the code system
version | ? | 0..1 | string | Business version of the code system (Coding.version)
name | ? | 0..1 | string | Name for this code system (computer friendly)
title | ? | 0..1 | string | Name for this code system (human friendly)
status | ?!? | 1..1 | code | draft | active | retired | unknown PublicationStatus (Required)
experimental | ?!? | 0..1 | boolean | For testing purposes, not real usage
date | ? | 0..1 | dateTime | Date this was last changed
publisher | ? | 0..1 | string | Name of the publisher (organization or individual)
contact | ? | 0..* | ContactDetail | Contact details for the publisher

description | | 0..1 | markdown | Natural language description of the code system
useContext | ? | 0..* | UsageContext | Context the content is intended to support
jurisdiction | ? | 0..* | CodeableConcept | Intended jurisdiction for code system (if applicable) Jurisdiction ValueSet (Extensible)
purpose | | 0..1 | markdown | Why this code system is defined
copyright | | 0..1 | markdown | Use and/or publishing restrictions
caseSensitive | ? | 0..1 | boolean | If code comparison is case sensitive
valueSet | ? | 0..1 | uri | Canonical URL for value set with entire code system
hierarchyMeaning | ? | 0..1 | code | grouped-by | is-a | part-of | classified-with CodeSystemHierarchyMeaning (Required)
compositional | ? | 0..1 | boolean | If code system defines a post-composition grammar
versionNeeded | ? | 0..1 | boolean | If definitions are not stable
content | ? | 1..1 | code | not-present | example | fragment | complete CodeSystemContentMode (Required)
count | ? | 0..1 | unsignedInt | Total concepts in the code system
filter | ? | 0..* | BackboneElement | Filter that can be used in a value set
code | ? | 1..1 | code | Code that identifies the filter
description | ? | 0..1 | string | How or why the filter is used
operator | ? | 1..* | code | Operators that can be used with filter FilterOperator (Required)
value | ? | 1..1 | string | What to use for the value
property | ? | 0..* | BackboneElement | Additional information supplied about each concept
code | ? | 1..1 | code | Identifies the property on the concepts, and when referred to in operations
uri | ? | 0..1 | uri | Formal identifier for the property
description | ? | 0..1 | string | Why the property is defined, and/or what it conveys
type | ? | 1..1 | code | code | Coding | string | integer | boolean | dateTime PropertyType (Required)
concept | | 0..* | BackboneElement | Concepts in the code system
code | | 1..1 | code | Code that identifies concept
display | | 0..1 | string | Text to display to the user
definition | | 0..1 | string | Formal definition
designation | | 0..* | BackboneElement | Additional representations for the concept
language | | 0..1 | code | Human language of the designation Common Languages (Extensible but limited to All Languages)
use | | 0..1 | Coding | Details how this designation would be used Designation Use (Extensible)
value | | 1..1 | string | The text value for this designation
property | | 0..* | BackboneElement | Property value for the concept
code | | 1..1 | code | Reference to CodeSystem.property.code
value[x] | | 1..1 | | Value of the property for this concept
valueCode | | | code
valueCoding | | | Coding
valueString | | | string
valueInteger | | | integer
valueBoolean | | | boolean
valueDateTime | | | dateTime
concept | | 0..* | see concept | Child Concepts (is-a/contains/categorizes)
Documentation for this format

UML Diagram (Legend)

XML Template

```
<CodeSystem xmlns="http://hl7.org/fhir">
 <!-- from Resource: id, meta, implicitRules, and language -->
 <!-- from DomainResource: text, contained, extension, and modifierExtension -->
 <url value="[uri]"/><!-- 0..1 Logical URI to reference this code system (globally unique) (Coding.system) -->
 <identifier><!-- 0..1 Identifier Additional identifier for the code system --></identifier>
 <version value="[string]"/><!-- 0..1 Business version of the code system (Coding.version) -->
 <name value="[string]"/><!-- 0..1 Name for this code system (computer friendly) -->
 <title value="[string]"/><!-- 0..1 Name for this code system (human friendly) -->
 <status value="[code]"/><!-- 1..1 draft | active | retired | unknown -->
 <experimental value="[boolean]"/><!-- 0..1 For testing purposes, not real usage -->
 <date value="[dateTime]"/><!-- 0..1 Date this was last changed -->
 <publisher value="[string]"/><!-- 0..1 Name of the publisher (organization or individual) -->
 <contact><!-- 0..* ContactDetail Contact details for the publisher --></contact>
 <description value="[markdown]"/><!-- 0..1 Natural language description of the code system -->
 <useContext><!-- 0..* UsageContext Context the content is intended to support --></useContext>
 <jurisdiction><!-- 0..* CodeableConcept Intended jurisdiction for code system (if applicable) --></jurisdiction>
 <purpose value="[markdown]"/><!-- 0..1 Why this code system is defined -->
 <copyright value="[markdown]"/><!-- 0..1 Use and/or publishing restrictions -->
 <caseSensitive value="[boolean]"/><!-- 0..1 If code comparison is case sensitive -->
 <valueSet value="[uri]"/><!-- 0..1 Canonical URL for value set with entire code system -->
 <hierarchyMeaning value="[code]"/><!-- 0..1 grouped-by | is-a | part-of | classified-with -->
 <compositional value="[boolean]"/><!-- 0..1 If code system defines a post-composition grammar -->
 <versionNeeded value="[boolean]"/><!-- 0..1 If definitions are not stable -->
 <content value="[code]"/><!-- 1..1 not-present | example | fragment | complete -->
 <count value="[unsignedInt]"/><!-- 0..1 Total concepts in the code system -->
 <filter>  <!-- 0..* Filter that can be used in a value set -->
  <code value="[code]"/><!-- 1..1 Code that identifies the filter -->
  <description value="[string]"/><!-- 0..1 How or why the filter is used -->
  <operator value="[code]"/><!-- 1..* Operators that can be used with filter -->
  <value value="[string]"/><!-- 1..1 What to use for the value -->
 </filter>
 <property>  <!-- 0..* Additional information supplied about each concept -->
  <code value="[code]"/><!-- 1..1 Identifies the property on the concepts, and when referred to in operations -->
  <uri value="[uri]"/><!-- 0..1 Formal identifier for the property -->
  <description value="[string]"/><!-- 0..1 Why the property is defined, and/or what it conveys -->
```

```
  <type value="[code]"/><!-- 1..1 code | Coding | string | integer | boolean | dateTime -->
 </property>
 <concept>  <!-- 0..* Concepts in the code system -->
  <code value="[code]"/><!-- 1..1 Code that identifies concept -->
  <display value="[string]"/><!-- 0..1 Text to display to the user -->
  <definition value="[string]"/><!-- 0..1 Formal definition -->
  <designation>  <!-- 0..* Additional representations for the concept -->
   <language value="[code]"/><!-- 0..1 Human language of the designation -->
   <use><!-- 0..1 Coding Details how this designation would be used --></use>
   <value value="[string]"/><!-- 1..1 The text value for this designation -->
  </designation>
  <property>  <!-- 0..* Property value for the concept -->
   <code value="[code]"/><!-- 1..1 Reference to CodeSystem.property.code -->
   <value[x]><!-- 1..1 code|Coding|string|integer|boolean|dateTime Value of the property for this concept --></value[x]>
  </property>
  <concept><!-- 0..* Content as for CodeSystem.concept Child Concepts (is-a/contains/categorizes) --></concept>
 </concept>
</CodeSystem>
```

JSON Template

```
{
  "resourceType" : "CodeSystem",
  // from Resource: id, meta, implicitRules, and language
  // from DomainResource: text, contained, extension, and modifierExtension
  "url" : "<uri>", // Logical URI to reference this code system (globally unique) (Coding.system)
  "identifier" : { Identifier }, // Additional identifier for the code system
  "version" : "<string>", // Business version of the code system (Coding.version)
  "name" : "<string>", // Name for this code system (computer friendly)
  "title" : "<string>", // Name for this code system (human friendly)
  "status" : "<code>", // R!  draft | active | retired | unknown
  "experimental" : <boolean>, // For testing purposes, not real usage
  "date" : "<dateTime>", // Date this was last changed
  "publisher" : "<string>", // Name of the publisher (organization or individual)
  "contact" : [{ ContactDetail }], // Contact details for the publisher
  "description" : "<markdown>", // Natural language description of the code system
  "useContext" : [{ UsageContext }], // Context the content is intended to support
  "jurisdiction" : [{ CodeableConcept }], // Intended jurisdiction for code system (if applicable)
  "purpose" : "<markdown>", // Why this code system is defined
  "copyright" : "<markdown>", // Use and/or publishing restrictions
  "caseSensitive" : <boolean>, // If code comparison is case sensitive
  "valueSet" : "<uri>", // Canonical URL for value set with entire code system
  "hierarchyMeaning" : "<code>", // grouped-by | is-a | part-of | classified-with
  "compositional" : <boolean>, // If code system defines a post-composition grammar
  "versionNeeded" : <boolean>, // If definitions are not stable
  "content" : "<code>", // R!  not-present | example | fragment | complete
  "count" : "<unsignedInt>", // Total concepts in the code system
  "filter" : [{ // Filter that can be used in a value set
    "code" : "<code>", // R!  Code that identifies the filter
    "description" : "<string>", // How or why the filter is used
    "operator" : ["<code>"], // R!  Operators that can be used with filter
    "value" : "<string>" // R!  What to use for the value
  }],
  "property" : [{ // Additional information supplied about each concept
    "code" : "<code>", // R!  Identifies the property on the concepts, and when referred to in operations
    "uri" : "<uri>", // Formal identifier for the property
    "description" : "<string>", // Why the property is defined, and/or what it conveys
    "type" : "<code>" // R!  code | Coding | string | integer | boolean | dateTime
  }],
  "concept" : [{ // Concepts in the code system
    "code" : "<code>", // R!  Code that identifies concept
    "display" : "<string>", // Text to display to the user
    "definition" : "<string>", // Formal definition
    "designation" : [{ // Additional representations for the concept
      "language" : "<code>", // Human language of the designation
      "use" : { Coding }, // Details how this designation would be used
      "value" : "<string>" // R!  The text value for this designation
    }],
    "property" : [{ // Property value for the concept
      "code" : "<code>", // R!  Reference to CodeSystem.property.code
      // value[x]: Value of the property for this concept. One of these 6:
      "valueCode" : "<code>"
      "valueCoding" : { Coding }
      "valueString" : "<string>"
      "valueInteger" : <integer>
      "valueBoolean" : <boolean>
      "valueDateTime" : "<dateTime>"
    }],
    "concept" : [{ Content as for CodeSystem.concept }] // Child Concepts (is-a/contains/categorizes)
  }]
}
```

Turtle Template

```
@prefix fhir: <http://hl7.org/fhir/> .


[ a fhir:CodeSystem;
  fhir:nodeRole fhir:treeRoot; # if this is the parser root

  # from Resource: .id, .meta, .implicitRules, and .language
```

```
  # from DomainResource: .text, .contained, .extension, and .modifierExtension
  fhir:CodeSystem.url [ uri ]; # 0..1 Logical URI to reference this code system (globally unique) (Coding.system)
  fhir:CodeSystem.identifier [ Identifier ]; # 0..1 Additional identifier for the code system
  fhir:CodeSystem.version [ string ]; # 0..1 Business version of the code system (Coding.version)
  fhir:CodeSystem.name [ string ]; # 0..1 Name for this code system (computer friendly)
  fhir:CodeSystem.title [ string ]; # 0..1 Name for this code system (human friendly)
  fhir:CodeSystem.status [ code ]; # 1..1 draft | active | retired | unknown
  fhir:CodeSystem.experimental [ boolean ]; # 0..1 For testing purposes, not real usage
  fhir:CodeSystem.date [ dateTime ]; # 0..1 Date this was last changed
  fhir:CodeSystem.publisher [ string ]; # 0..1 Name of the publisher (organization or individual)
  fhir:CodeSystem.contact [ ContactDetail ], ... ; # 0..* Contact details for the publisher
  fhir:CodeSystem.description [ markdown ]; # 0..1 Natural language description of the code system
  fhir:CodeSystem.useContext [ UsageContext ], ... ; # 0..* Context the content is intended to support
  fhir:CodeSystem.jurisdiction [ CodeableConcept ], ... ; # 0..* Intended jurisdiction for code system (if applicable)
  fhir:CodeSystem.purpose [ markdown ]; # 0..1 Why this code system is defined
  fhir:CodeSystem.copyright [ markdown ]; # 0..1 Use and/or publishing restrictions
  fhir:CodeSystem.caseSensitive [ boolean ]; # 0..1 If code comparison is case sensitive
  fhir:CodeSystem.valueSet [ uri ]; # 0..1 Canonical URL for value set with entire code system
  fhir:CodeSystem.hierarchyMeaning [ code ]; # 0..1 grouped-by | is-a | part-of | classified-with
  fhir:CodeSystem.compositional [ boolean ]; # 0..1 If code system defines a post-composition grammar
  fhir:CodeSystem.versionNeeded [ boolean ]; # 0..1 If definitions are not stable
  fhir:CodeSystem.content [ code ]; # 1..1 not-present | example | fragment | complete
  fhir:CodeSystem.count [ unsignedInt ]; # 0..1 Total concepts in the code system
  fhir:CodeSystem.filter [ # 0..* Filter that can be used in a value set
    fhir:CodeSystem.filter.code [ code ]; # 1..1 Code that identifies the filter
    fhir:CodeSystem.filter.description [ string ]; # 0..1 How or why the filter is used
    fhir:CodeSystem.filter.operator [ code ], ... ; # 1..* Operators that can be used with filter
    fhir:CodeSystem.filter.value [ string ]; # 1..1 What to use for the value
  ], ...;
  fhir:CodeSystem.property [ # 0..* Additional information supplied about each concept
    fhir:CodeSystem.property.code [ code ]; # 1..1 Identifies the property on the concepts, and when referred to in
    operations
    fhir:CodeSystem.property.uri [ uri ]; # 0..1 Formal identifier for the property
    fhir:CodeSystem.property.description [ string ]; # 0..1 Why the property is defined, and/or what it conveys
    fhir:CodeSystem.property.type [ code ]; # 1..1 code | Coding | string | integer | boolean | dateTime
  ], ...;
  fhir:CodeSystem.concept [ # 0..* Concepts in the code system
    fhir:CodeSystem.concept.code [ code ]; # 1..1 Code that identifies concept
    fhir:CodeSystem.concept.display [ string ]; # 0..1 Text to display to the user
    fhir:CodeSystem.concept.definition [ string ]; # 0..1 Formal definition
    fhir:CodeSystem.concept.designation [ # 0..* Additional representations for the concept
      fhir:CodeSystem.concept.designation.language [ code ]; # 0..1 Human language of the designation
      fhir:CodeSystem.concept.designation.use [ Coding ]; # 0..1 Details how this designation would be used
      fhir:CodeSystem.concept.designation.value [ string ]; # 1..1 The text value for this designation
    ], ...;
    fhir:CodeSystem.concept.property [ # 0..* Property value for the concept
      fhir:CodeSystem.concept.property.code [ code ]; # 1..1 Reference to CodeSystem.property.code
      # CodeSystem.concept.property.value[x] : 1..1 Value of the property for this concept. One of these 6
        fhir:CodeSystem.concept.property.valueCode [ code ]
        fhir:CodeSystem.concept.property.valueCoding [ Coding ]
        fhir:CodeSystem.concept.property.valueString [ string ]
        fhir:CodeSystem.concept.property.valueInteger [ integer ]
        fhir:CodeSystem.concept.property.valueBoolean [ boolean ]
        fhir:CodeSystem.concept.property.valueDateTime [ dateTime ]
    ], ...;
    fhir:CodeSystem.concept.concept [ See CodeSystem.concept ], ... ; # 0..* Child Concepts (is-a/contains/categorizes)
  ], ...;
]
```

Changes since DSTU2

This resource did not exist in Release 2

This analysis is available as XML or JSON.

Structure

Name | Flags | Card. | Type | Description & Constraints

CodeSystem | I | | DomainResource | A set of codes drawn from one or more code systems + Within a code system definition, all the codes SHALL be unique Elements defined in Ancestors: id, meta, implicitRules, language, text, contained, extension, modifierExtension

url | ? | 0..1 | uri | Logical URI to reference this code system (globally unique) (Coding.system)

identifier | ? | 0..1 | Identifier | Additional identifier for the code system

version | ? | 0..1 | string | Business version of the code system (Coding.version)

name | ? | 0..1 | string | Name for this code system (computer friendly)

title | ? | 0..1 | string | Name for this code system (human friendly)

status | ?!? | 1..1 | code | draft | active | retired | unknown PublicationStatus (Required)

experimental | ?!? | 0..1 | boolean | For testing purposes, not real usage

date | ? | 0..1 | dateTime | Date this was last changed

publisher | ? | 0..1 | string | Name of the publisher (organization or individual)

contact | ? | 0..* | ContactDetail | Contact details for the publisher

description | | 0..1 | markdown | Natural language description of the code system

useContext | ? | 0..* | UsageContext | Context the content is intended to support

jurisdiction | ? | 0..* | CodeableConcept | Intended jurisdiction for code system (if applicable) Jurisdiction ValueSet (Extensible)

purpose | | 0..1 | markdown | Why this code system is defined

copyright | | 0..1 | markdown | Use and/or publishing restrictions

caseSensitive | ? | 0..1 | boolean | If code comparison is case sensitive

valueSet | ? | 0..1 | uri | Canonical URL for value set with entire code system
hierarchyMeaning | ? | 0..1 | code | grouped-by | is-a | part-of | classified-with CodeSystemHierarchyMeaning (Required)
compositional | ? | 0..1 | boolean | If code system defines a post-composition grammar
versionNeeded | ? | 0..1 | boolean | If definitions are not stable
content | ? | 1..1 | code | not-present | example | fragment | complete CodeSystemContentMode (Required)
count | ? | 0..1 | unsignedInt | Total concepts in the code system
filter | ? | 0..* | BackboneElement | Filter that can be used in a value set
code | ? | 1..1 | code | Code that identifies the filter
description | ? | 0..1 | string | How or why the filter is used
operator | ? | 1..* | code | Operators that can be used with filter FilterOperator (Required)
value | ? | 1..1 | string | What to use for the value
property | ? | 0..* | BackboneElement | Additional information supplied about each concept
code | ? | 1..1 | code | Identifies the property on the concepts, and when referred to in operations
uri | ? | 0..1 | uri | Formal identifier for the property
description | ? | 0..1 | string | Why the property is defined, and/or what it conveys
type | ? | 1..1 | code | code | Coding | string | integer | boolean | dateTime PropertyType (Required)
concept | | 0..* | BackboneElement | Concepts in the code system
code | | 1..1 | code | Code that identifies concept
display | | 0..1 | string | Text to display to the user
definition | | 0..1 | string | Formal definition
designation | | 0..* | BackboneElement | Additional representations for the concept
language | | 0..1 | code | Human language of the designation Common Languages (Extensible but limited to All Languages)
use | | 0..1 | Coding | Details how this designation would be used Designation Use (Extensible)
value | | 1..1 | string | The text value for this designation
property | | 0..* | BackboneElement | Property value for the concept
code | | 1..1 | code | Reference to CodeSystem.property.code
value[x] | | 1..1 | | Value of the property for this concept
valueCode | | | code
valueCoding | | | Coding
valueString | | | string
valueInteger | | | integer
valueBoolean | | | boolean
valueDateTime | | | dateTime
concept | | 0..* | see concept | Child Concepts (is-a/contains/categorizes)
Documentation for this format

UML Diagram (Legend)

XML Template

```
<CodeSystem xmlns="http://hl7.org/fhir">
 <!-- from Resource: id, meta, implicitRules, and language -->
 <!-- from DomainResource: text, contained, extension, and modifierExtension -->
 <url value="[uri]"/><!-- 0..1 Logical URI to reference this code system (globally unique) (Coding.system) -->
 <identifier><!-- 0..1 Identifier Additional identifier for the code system --></identifier>
 <version value="[string]"/><!-- 0..1 Business version of the code system (Coding.version) -->
 <name value="[string]"/><!-- 0..1 Name for this code system (computer friendly) -->
 <title value="[string]"/><!-- 0..1 Name for this code system (human friendly) -->
 <status value="[code]"/><!-- 1..1 draft | active | retired | unknown -->
 <experimental value="[boolean]"/><!-- 0..1 For testing purposes, not real usage -->
 <date value="[dateTime]"/><!-- 0..1 Date this was last changed -->
 <publisher value="[string]"/><!-- 0..1 Name of the publisher (organization or individual) -->
 <contact><!-- 0..* ContactDetail Contact details for the publisher --></contact>
 <description value="[markdown]"/><!-- 0..1 Natural language description of the code system -->
 <useContext><!-- 0..* UsageContext Context the content is intended to support --></useContext>
 <jurisdiction><!-- 0..* CodeableConcept Intended jurisdiction for code system (if applicable) --></jurisdiction>
 <purpose value="[markdown]"/><!-- 0..1 Why this code system is defined -->
 <copyright value="[markdown]"/><!-- 0..1 Use and/or publishing restrictions -->
 <caseSensitive value="[boolean]"/><!-- 0..1 If code comparison is case sensitive -->
 <valueSet value="[uri]"/><!-- 0..1 Canonical URL for value set with entire code system -->
 <hierarchyMeaning value="[code]"/><!-- 0..1 grouped-by | is-a | part-of | classified-with -->
 <compositional value="[boolean]"/><!-- 0..1 If code system defines a post-composition grammar -->
 <versionNeeded value="[boolean]"/><!-- 0..1 If definitions are not stable -->
 <content value="[code]"/><!-- 1..1 not-present | example | fragment | complete -->
 <count value="[unsignedInt]"/><!-- 0..1 Total concepts in the code system -->
 <filter>  <!-- 0..* Filter that can be used in a value set -->
  <code value="[code]"/><!-- 1..1 Code that identifies the filter -->
  <description value="[string]"/><!-- 0..1 How or why the filter is used -->
  <operator value="[code]"/><!-- 1..* Operators that can be used with filter -->
  <value value="[string]"/><!-- 1..1 What to use for the value -->
 </filter>
 <property>  <!-- 0..* Additional information supplied about each concept -->
  <code value="[code]"/><!-- 1..1 Identifies the property on the concepts, and when referred to in operations -->
  <uri value="[uri]"/><!-- 0..1 Formal identifier for the property -->
  <description value="[string]"/><!-- 0..1 Why the property is defined, and/or what it conveys -->
  <type value="[code]"/><!-- 1..1 code | Coding | string | integer | boolean | dateTime -->
 </property>
 <concept>  <!-- 0..* Concepts in the code system -->
  <code value="[code]"/><!-- 1..1 Code that identifies concept -->
  <display value="[string]"/><!-- 0..1 Text to display to the user -->
  <definition value="[string]"/><!-- 0..1 Formal definition -->
  <designation>  <!-- 0..* Additional representations for the concept -->
```

```
   <language value="[code]"/><!-- 0..1 Human language of the designation -->
   <use><!-- 0..1 Coding Details how this designation would be used --></use>
   <value value="[string]"/><!-- 1..1 The text value for this designation -->
  </designation>
  <property>  <!-- 0..* Property value for the concept -->
   <code value="[code]"/><!-- 1..1 Reference to CodeSystem.property.code -->
   <value[x]><!-- 1..1 code|Coding|string|integer|boolean|dateTime Value of the property for this concept --></value[x]>
  </property>
  <concept><!-- 0..* Content as for CodeSystem.concept Child Concepts (is-a/contains/categorizes) --></concept>
 </concept>
</CodeSystem>
```

JSON Template

```
{
  "resourceType" : "CodeSystem",
  // from Resource: id, meta, implicitRules, and language
  // from DomainResource: text, contained, extension, and modifierExtension
  "url" : "<uri>", // Logical URI to reference this code system (globally unique) (Coding.system)
  "identifier" : { Identifier }, // Additional identifier for the code system
  "version" : "<string>", // Business version of the code system (Coding.version)
  "name" : "<string>", // Name for this code system (computer friendly)
  "title" : "<string>", // Name for this code system (human friendly)
  "status" : "<code>", // R!  draft | active | retired | unknown
  "experimental" : <boolean>, // For testing purposes, not real usage
  "date" : "<dateTime>", // Date this was last changed
  "publisher" : "<string>", // Name of the publisher (organization or individual)
  "contact" : [{ ContactDetail }], // Contact details for the publisher
  "description" : "<markdown>", // Natural language description of the code system
  "useContext" : [{ UsageContext }], // Context the content is intended to support
  "jurisdiction" : [{ CodeableConcept }], // Intended jurisdiction for code system (if applicable)
  "purpose" : "<markdown>", // Why this code system is defined
  "copyright" : "<markdown>", // Use and/or publishing restrictions
  "caseSensitive" : <boolean>, // If code comparison is case sensitive
  "valueSet" : "<uri>", // Canonical URL for value set with entire code system
  "hierarchyMeaning" : "<code>", // grouped-by | is-a | part-of | classified-with
  "compositional" : <boolean>, // If code system defines a post-composition grammar
  "versionNeeded" : <boolean>, // If definitions are not stable
  "content" : "<code>", // R!  not-present | example | fragment | complete
  "count" : "<unsignedInt>", // Total concepts in the code system
  "filter" : [{ // Filter that can be used in a value set
    "code" : "<code>", // R!  Code that identifies the filter
    "description" : "<string>", // How or why the filter is used
    "operator" : ["<code>"], // R!  Operators that can be used with filter
    "value" : "<string>" // R!  What to use for the value
  }],
  "property" : [{ // Additional information supplied about each concept
    "code" : "<code>", // R!  Identifies the property on the concepts, and when referred to in operations
    "uri" : "<uri>", // Formal identifier for the property
    "description" : "<string>", // Why the property is defined, and/or what it conveys
    "type" : "<code>" // R!  code | Coding | string | integer | boolean | dateTime
  }],
  "concept" : [{ // Concepts in the code system
    "code" : "<code>", // R!  Code that identifies concept
    "display" : "<string>", // Text to display to the user
    "definition" : "<string>", // Formal definition
    "designation" : [{ // Additional representations for the concept
      "language" : "<code>", // Human language of the designation
      "use" : { Coding }, // Details how this designation would be used
      "value" : "<string>" // R!  The text value for this designation
    }],
    "property" : [{ // Property value for the concept
      "code" : "<code>", // R!  Reference to CodeSystem.property.code
      // value[x]: Value of the property for this concept. One of these 6:
      "valueCode" : "<code>"
      "valueCoding" : { Coding }
      "valueString" : "<string>"
      "valueInteger" : <integer>
      "valueBoolean" : <boolean>
      "valueDateTime" : "<dateTime>"
    }],
    "concept" : [{ Content as for CodeSystem.concept }] // Child Concepts (is-a/contains/categorizes)
  }]
}
```

Turtle Template

```
@prefix fhir: <http://hl7.org/fhir/> .


[ a fhir:CodeSystem;
  fhir:nodeRole fhir:treeRoot; # if this is the parser root

  # from Resource: .id, .meta, .implicitRules, and .language
  # from DomainResource: .text, .contained, .extension, and .modifierExtension
  fhir:CodeSystem.url [ uri ]; # 0..1 Logical URI to reference this code system (globally unique) (Coding.system)
  fhir:CodeSystem.identifier [ Identifier ]; # 0..1 Additional identifier for the code system
  fhir:CodeSystem.version [ string ]; # 0..1 Business version of the code system (Coding.version)
  fhir:CodeSystem.name [ string ]; # 0..1 Name for this code system (computer friendly)
  fhir:CodeSystem.title [ string ]; # 0..1 Name for this code system (human friendly)
  fhir:CodeSystem.status [ code ]; # 1..1 draft | active | retired | unknown
```

```
  fhir:CodeSystem.experimental [ boolean ]; # 0..1 For testing purposes, not real usage
  fhir:CodeSystem.date [ dateTime ]; # 0..1 Date this was last changed
  fhir:CodeSystem.publisher [ string ]; # 0..1 Name of the publisher (organization or individual)
  fhir:CodeSystem.contact [ ContactDetail ], ... ; # 0..* Contact details for the publisher
  fhir:CodeSystem.description [ markdown ]; # 0..1 Natural language description of the code system
  fhir:CodeSystem.useContext [ UsageContext ], ... ; # 0..* Context the content is intended to support
  fhir:CodeSystem.jurisdiction [ CodeableConcept ], ... ; # 0..* Intended jurisdiction for code system (if applicable)
  fhir:CodeSystem.purpose [ markdown ]; # 0..1 Why this code system is defined
  fhir:CodeSystem.copyright [ markdown ]; # 0..1 Use and/or publishing restrictions
  fhir:CodeSystem.caseSensitive [ boolean ]; # 0..1 If code comparison is case sensitive
  fhir:CodeSystem.valueSet [ uri ]; # 0..1 Canonical URL for value set with entire code system
  fhir:CodeSystem.hierarchyMeaning [ code ]; # 0..1 grouped-by | is-a | part-of | classified-with
  fhir:CodeSystem.compositional [ boolean ]; # 0..1 If code system defines a post-composition grammar
  fhir:CodeSystem.versionNeeded [ boolean ]; # 0..1 If definitions are not stable
  fhir:CodeSystem.content [ code ]; # 1..1 not-present | example | fragment | complete
  fhir:CodeSystem.count [ unsignedInt ]; # 0..1 Total concepts in the code system
  fhir:CodeSystem.filter [ # 0..* Filter that can be used in a value set
    fhir:CodeSystem.filter.code [ code ]; # 1..1 Code that identifies the filter
    fhir:CodeSystem.filter.description [ string ]; # 0..1 How or why the filter is used
    fhir:CodeSystem.filter.operator [ code ], ... ; # 1..* Operators that can be used with filter
    fhir:CodeSystem.filter.value [ string ]; # 1..1 What to use for the value
  ], ...;
  fhir:CodeSystem.property [ # 0..* Additional information supplied about each concept
    fhir:CodeSystem.property.code [ code ]; # 1..1 Identifies the property on the concepts, and when referred to in
    operations
    fhir:CodeSystem.property.uri [ uri ]; # 0..1 Formal identifier for the property
    fhir:CodeSystem.property.description [ string ]; # 0..1 Why the property is defined, and/or what it conveys
    fhir:CodeSystem.property.type [ code ]; # 1..1 code | Coding | string | integer | boolean | dateTime
  ], ...;
  fhir:CodeSystem.concept [ # 0..* Concepts in the code system
    fhir:CodeSystem.concept.code [ code ]; # 1..1 Code that identifies concept
    fhir:CodeSystem.concept.display [ string ]; # 0..1 Text to display to the user
    fhir:CodeSystem.concept.definition [ string ]; # 0..1 Formal definition
    fhir:CodeSystem.concept.designation [ # 0..* Additional representations for the concept
      fhir:CodeSystem.concept.designation.language [ code ]; # 0..1 Human language of the designation
      fhir:CodeSystem.concept.designation.use [ Coding ]; # 0..1 Details how this designation would be used
      fhir:CodeSystem.concept.designation.value [ string ]; # 1..1 The text value for this designation
    ], ...;
    fhir:CodeSystem.concept.property [ # 0..* Property value for the concept
      fhir:CodeSystem.concept.property.code [ code ]; # 1..1 Reference to CodeSystem.property.code
      # CodeSystem.concept.property.value[x] : 1..1 Value of the property for this concept. One of these 6
        fhir:CodeSystem.concept.property.valueCode [ code ]
        fhir:CodeSystem.concept.property.valueCoding [ Coding ]
        fhir:CodeSystem.concept.property.valueString [ string ]
        fhir:CodeSystem.concept.property.valueInteger [ integer ]
        fhir:CodeSystem.concept.property.valueBoolean [ boolean ]
        fhir:CodeSystem.concept.property.valueDateTime [ dateTime ]
    ], ...;
    fhir:CodeSystem.concept.concept [ See CodeSystem.concept ], ... ; # 0..* Child Concepts (is-a/contains/categorizes)
  ], ...;
]
```

Changes since DSTU2

This resource did not exist in Release 2

This analysis is available as XML or JSON.

Alternate definitions: Master Definition (XML, JSON), XML Schema/Schematron (for) + JSON Schema, ShEx (for Turtle)

4.7.4.1 Terminology Bindings

Path	Definition	Type	Reference
CodeSystem.status	The lifecycle status of a Value Set or Concept Map.	Required	PublicationStatus
CodeSystem.jurisdiction	Countries and regions within which this artifact is targeted for use	Extensible	Jurisdiction ValueSet
CodeSystem.hierarchyMeaning	The meaning of the hierarchy of concepts in a code system	Required	CodeSystemHierarchyMeaning
CodeSystem.content	How much of the content of the code system - the concepts and codes it defines - are represented in a code system resource	Required	CodeSystemContentMode
CodeSystem.filter.operator	The kind of operation to perform as a part of a property based filter.	Required	FilterOperator
CodeSystem.property.type	The type of a property value	Required	PropertyType
CodeSystem.concept.designation.language	A human language.	Extensible, but limited to All Languages	Common Languages
CodeSystem.concept.designation.use	Details of how a designation would be used.	Extensible	Designation Use

4.7.4.2 Constraints

* csd-1: Within a code system definition, all the codes SHALL be unique (expression : (concept.code | descendants().concept.code).isDistinct())

4.7.4.3 Versioning Code Systems

Most code systems evolve over time, due to corrections, clarifications, and changes to approach or underlying knowledge or reality. If these changes lead to the meanings of existing codes changing significantly, then the interpretation of the code system becomes version dependent. This significantly complicates implementation based on the code system, to the point where it is not clear that safety can be assured, so changing the meaning of an existing code SHOULD be avoided whenever possible. It is preferable to assign a new identifier to a code system when any concepts in it have a significant change in meaning (for example, the German diagnostic classification code system ICD10GM2009 has a different system to

ICD10GM2008), but this also can have substantial impact on implementation, so is often not practical - for instance, SNOMED CT has a complex version release framework, which may lead to variations in meaning of concepts, but there is only one identifier for SNOMED CT.

For this reason, a code system MAY provide a version identifier which can be specified in CodeSystem.version. The version specific identifier SHOULD be provided whenever there are potentially significant changes in meaning across multiple releases of a code system. There is no particular format requirement for the version identifier, though HL7 recommends a date based approach.

When the CodeSystem.versionNeeded is 'true', then the version identifier SHALL be used in Coding instances that refer to the code system.

Where the terminology does not clearly define what string should be used to identify code system versions, the recommendation is to use as the version string the date (expressed in FHIR date format) on which the version of the code system that is being used was officially published.

4.7.5 Properties

Each code system can have one or more properties. Each concept defined by the code system may have one more values for each property defined by the code system. Typical uses for properties include:

* Tracking administrative status (inactive, deprecation date)

* Providing additional statements about the meaning of the concept

* Defining structured relationships with other concepts in the code system

* Assigning scoring values to the concepts

Properties are identified by their master URI (CodeSystem.property.uri), and then, by their code (CodeSystem.property.code), which is used both internally within the code system resource (CodeSystem.concept.property.code) and also externally, in the following places:

* ConceptMap: ConceptMap.element.target.dependsOn.property and ConceptMap.element.target.product.property

* ValueSet: ValueSet.compose.include.filter.property can refer to any defined code system property

* $lookup operation: In Parameters.parameter.name when returning information about a code

* $translate operation: In Parameters.parameter.part.name for dependencies and products

* $compose operation: In Parameters.parameter.name when providing codes, and in Parameters.parameter.name when asking for codes

Properties are defined using the following elements:

Name | Details | Description
code | code | Used to identify the property, as enumerated above
uri | optional uri | Reference to the formal meaning of the property. One possible source of meaning is the Concept Properties code system. This part of the definition is optional, but is recommended to provide an additional level of definitional consistency
description | optional string | A description of the property- why it is defined, and how its value might be used
type | code | Coding | string | integer | boolean | dateTime | The type of the property value. Properties of type "code" contain a code defined by the code system (e.g. a reference to anotherr defined concept)

Note that properties provide a common view of concept relationships that is common across all code systems. Some code systems define properties with more sophistication, such as groups of properties, or subsumption relationships between properties (e.g. SNOMED CT). Servers providing support for these code systems will need to know full details about the underlying relationships in order to provide the correct information about concepts and their properties, but this information does not surface in the resources or operations defined by the FHIR specification.

4.7.6 Concept Status

Many Code Systems have a 'status' associated with the concept. This may categorise the concept as:

* Experimental - provided for trial, but may be removed in the future

* Active - in normal use

* Deprecated - planned to be removed from use

* Retired - still present for historical reasons, but no longer allowed to be used

There is wide variation in the life cycles supported by the different code systems, the words they use to describe the various status values they use, and some code systems have additional status values. HL7 uses Active and Retired. In addition to these status codes, concepts may be also be labeled as ''Abstract' (not to be used in some circumstances), and have dates associated with their retirement or deprecation. All this information is represented as properties of the concepts. In order to assist with consistency between code systems, the following basic property URIs are defined:

http://hl7.org/fhir/concept-properties#status | A property that indicates the status of the concept. If the property is identified by this URL, then it SHALL use at least these status values (where appropriate): active - the concept is for normal use (this is the default value) experimental - provided for trial, but may be removed in the future deprecated - planned to be removed from use retired - still present for historical reasons, but no longer allowed to be used
http://hl7.org/fhir/concept-properties#retirementDate | Date Concept was retired
http://hl7.org/fhir/concept-properties#deprecationDate | Date Concept was deprecated
http://hl7.org/fhir/concept-properties#parent | An immediate parent of the concept in the hierarchy

http://hl7.org/fhir/concept-properties#child | An immediate child of the concept in the hierarchy
http://hl7.org/fhir/concept-properties#notSelectable | This concept is a grouping concept and not intended to be used in the normal use of the code system (though my be used for filters etc). This is also known as 'Abstract'

Typically, Code systems are presented hierachically, where the hierachy has a defined meaning. For this reason, the parent and child properties are mostly only used when performing concept lookup. Note that in some code systems, concepts may have multiple parents, so the parent property may repeat. These code systems are not usually presented in a hierachical fashion in a CodeSystem if they are represented in a CodeSystem at all. If they are, then the subsumes extension must be used.

4.7.6.1 Subsumption Testing

The words 'subsume', 'subsumes', 'subsumed' and 'subsumption' are defined in terms of the CodeSystem hierarchy (i.e. CodeSystem.hierarchyMeaning). Concept A is considered to be subsumed by Concept B if it comes under Concept B in the hierarchy, or if subsumption is declared explicitly using the subsumes extension).

Where a CodeSystem does not declare its hierarchy meaning directly, then the code system documentation must be consulted manually to determinw how subsumption is determined. If there is no definition, none of the subsumption based features can be used with the code system.

Subsumption based logic arises explicitly or implicitly in the following places in the FHIR specification:

* CodeSystem $subsumes operation

* CodeSystem $lookup operation

* ConceptMap $closure operation

* Search by subsumption

* ValueSet $expand operation

* ValueSet $validate-code operation

4.7.6.2 Filters

The following filters are defined for all code systems:

Property Name | Operation | Value | Definition | Notes
[property] | = | [string] | Includes all codes that have a property value equal to the specified string, where [property] is the code for any defined property
[property] | in | [string,string...] | Includes all codes that have a property value equal to one of the specified strings, where [property] is the code for any defined property | The values cannot include ",", since it is being used as a delimited

4.7.6.3 Code systems with detailed metadata

Sometimes code systems may be used to represent more complex information than just code, display name and code system. For example, a code system of drug information which contains information about the content of the medication (e.g., RxNorm), or a set of observation types, that contain methods, units, etc. (e.g., LOINC). In FHIR, these are handled by splitting the concept into two distinct parts - the Terminology, (Code System & ValueSet resources) is used to manage the codes, display names and relationships. A separate "detail" resource (e.g., Medication for drugs, DataElement for observation types, Location for location, etc.) is used to convey detailed information (dose form & strength, allowed data type or permitted values, address & hours of operation, etc.). One "detail" resource instance is created for each code.

This division accomplishes several things:

* It allows generic systems that support terminology management to perform standard terminology operations on code systems dealing with complex structures - code lookup, validation, subsumption testing, mapping and translation.

* It allows information to be exchanged about individual medications, data elements and locations. Codes can't be retrieved individually in FHIR - it is necessary to retrieve the entire resource. By packaging the detailed information in separate resources, independent retrieval and update is possible.

* It supports use-cases for sharing medication, location, observation type and similar information in circumstances where the code may be unknown, unavailable or occasionally non-existent (e.g., custom compounds, non-registered locations). Having a distinct resource supports these capabilities, which would not be possible using CodeSystem/ValueSet.

Note that this division in FHIR does not imply that a similar division is required in the internal representation used by systems exposing a FHIR interface. Similarly, some systems may choose to only expose or maintain one aspect of such information types (i.e. only the discrete resource instances or only the value set).

The linkage between the "detail" resource and the Terminology resources is accomplished via the code element (or equivalent) on the detail resource. As well, the "name" or "title" on the detail resource generally corresponds with the display name on the matching code. Most detail resources will also have an "identifier" element. This can be set to the same value and namespace as the code, but if the only identifier a resource has is its defining code, it may be better to omit the identifier entirely. For further information, see Implicit Code Systems.

4.7.7 Search Parameters

Search parameters for this resource. The common parameters also apply. See Searching for more information about searching in REST, messaging, and services.

Name | Type | Description | Expression | In Common

code | token | A code defined in the code system | CodeSystem.concept.code
content-mode | token | not-present | example | fragment | complete | CodeSystem.content
date | date | The code system publication date | CodeSystem.date
description | string | The description of the code system | CodeSystem.description
identifier | token | External identifier for the code system | CodeSystem.identifier
jurisdiction | token | Intended jurisdiction for the code system | CodeSystem.jurisdiction
language | token | A language in which a designation is provided | CodeSystem.concept.designation.language
name | string | Computationally friendly name of the code system | CodeSystem.name
publisher | string | Name of the publisher of the code system | CodeSystem.publisher
status | token | The current status of the code system | CodeSystem.status
system | uri | The system for any codes defined by this code system (same as 'url') | CodeSystem.url
title | string | The human-friendly name of the code system | CodeSystem.title
url | uri | The uri that identifies the code system | CodeSystem.url
version | token | The business version of the code system | CodeSystem.version

4.7.8 Resource CodeSystem - Examples

URL: https://hl7.org/fhir/STU3/codesystem-examples.html

This page is part of the FHIR Specification (v3.0.2: STU 3). The current version which supercedes this version is 4.0.1. For a full list of available versions, see the Directory of published versions

4.7.8 Resource CodeSystem - Examples

Vocabulary Work Group | Maturity Level: N/A | Ballot Status: Informative | Compartments: Not linked to any defined compartments

Example List:

Simple Code System | example | XML | JSON | Turtle
NHIN Purpose of Use | nhin-purposeofuse | XML | JSON | Turtle
Canonical Definition for SNOMED CT | snomedct | XML | JSON | Turtle
Code system summary | summary | XML | JSON | Turtle

Usage note: every effort has been made to ensure that the examples are correct and useful, but they are not a normative part of the specification.

4.7.9 Resource CodeSystem - Detailed Descriptions

URL: https://hl7.org/fhir/STU3/codesystem-definitions.html

This page is part of the FHIR Specification (v3.0.2: STU 3). The current version which supercedes this version is 4.0.1. For a full list of available versions, see the Directory of published versions

4.7.9 Resource CodeSystem - Detailed Descriptions

Vocabulary Work Group | Maturity Level: 5 | Trial Use | Compartments: Not linked to any defined compartments

Detailed Descriptions for the elements in the CodeSystem resource.

CodeSystem
Definition | A code system resource specifies a set of codes drawn from one or more code systems.
Control | 1..1
Invariants | Defined on this element csd-1: Within a code system definition, all the codes SHALL be unique (expression : (concept.code | descendants().concept.code).isDistinct(), xpath: count(distinct-values(descendant::f:concept/f:code/@value))=count(descendant::f:concept))
CodeSystem.url
Definition | An absolute URI that is used to identify this code system when it is referenced in a specification, model, design or an instance. This SHALL be a URL, SHOULD be globally unique, and SHOULD be an address at which this code system is (or will be) published. The URL SHOULD include the major version of the code system. For more information see Technical and Business Versions. This is used in [Coding]{datatypes.html#Coding}.system.
Control | 0..1
Type | uri
Requirements | Allows the code system to be referenced by a single globally unique identifier.
Summary | true
Comments | Can be a urn:uuid: or a urn:oid:, but real http: addresses are preferred. Multiple instances may share the same url if they have a distinct version.
CodeSystem.identifier
Definition | A formal identifier that is used to identify this code system when it is represented in other formats, or referenced in a specification, model, design or an instance.
Note | This is a business identifer, not a resource identifier (see discussion)
Control | 0..1
Type | Identifier
Requirements | Allows externally provided and/or usable business identifiers to be easily associated with the module.
Summary | true
Comments | Typically, this is used for identifiers that can go in an HL7 V3 II (instance identifier) data type, e.g., to identify this code system outside of FHIR, where it is not possible to use the logical URI.
CodeSystem.version
Definition | The identifier that is used to identify this version of the code system when it is referenced in a specification, model, design or instance. This is an arbitrary value managed by the code system author and is not expected to be globally unique. For example, it might be a timestamp (e.g.

yyyymmdd) if a managed version is not available. There is also no expectation that versions can be placed in a lexicographical sequence. This is used in [Coding]{datatypes.html#Coding}.version.
Note | This is a business versionId, not a resource version id (see discussion)
Control | 0..1
Type | string
Summary | true
Comments | There may be different code system instances that have the same identifier but different versions. The version can be appended to the url in a reference to allow a refrence to a particular business version of the code system with the format [url]|[version].
CodeSystem.name
Definition | A natural language name identifying the code system. This name should be usable as an identifier for the module by machine processing applications such as code generation.
Control | 0..1
Type | string
Requirements | Support human navigation and code generation.
Summary | true
Comments | The name is not expected to be globally unique. The name should be a simple alpha-numeric type name to ensure that it is computable friendly.
CodeSystem.title
Definition | A short, descriptive, user-friendly title for the code system.
Control | 0..1
Type | string
Summary | true
Comments | This name does not need to be machine-processing friendly and may contain punctuation, white-space, etc.
CodeSystem.status
Definition | The status of this code system. Enables tracking the life-cycle of the content.
Control | 1..1
Terminology Binding | PublicationStatus (Required)
Type | code
Is Modifier | true
Summary | true
Comments | Allows filtering of code systems that are appropriate for use vs. not. This is labeled as "Is Modifier" because applications should not use a retired code system without due consideration.
CodeSystem.experimental
Definition | A boolean value to indicate that this code system is authored for testing purposes (or education/evaluation/marketing), and is not intended to be used for genuine usage.
Control | 0..1
Type | boolean
Is Modifier | true
Requirements | Enables experimental content to be developed following the same lifecycle that would be used for a production-level code system.
Summary | true
Comments | Allows filtering of code system that are appropriate for use vs. not. This is labeled as "Is Modifier" because applications should not use an experimental code system in production.
CodeSystem.date
Definition | The date (and optionally time) when the code system was published. The date must change if and when the business version changes and it must change if the status code changes. In addition, it should change when the substantive content of the code system changes.
Control | 0..1
Type | dateTime
Alternate Names | Revision Date
Summary | true
Comments | Note that this is not the same as the resource last-modified-date, since the resource may be a secondary representation of the code system. Additional specific dates may be added as extensions or be found by consulting Provenances associated with past versions of the resource.
CodeSystem.publisher
Definition | The name of the individual or organization that published the code system.
Control | 0..1
Type | string
Requirements | Helps establish the "authority/credibility" of the code system. May also allow for contact.
Summary | true
Comments | Usually an organization, but may be an individual. The publisher (or steward) of the code system is the organization or individual primarily responsible for the maintenance and upkeep of the code system. This is not necessarily the same individual or organization that developed and initially authored the content. The publisher is the primary point of contact for questions or issues with the code system. This item SHOULD be populated unless the information is available from context.
CodeSystem.contact
Definition | Contact details to assist a user in finding and communicating with the publisher.
Control | 0..*
Type | ContactDetail
Summary | true
Comments | May be a web site, an email address, a telephone number, etc.
CodeSystem.description
Definition | A free text natural language description of the code system from a consumer's perspective.
Control | 0..1
Type | markdown
Alternate Names | Scope; Purpose

Comments | This description can be used to capture details such as why the code system was built, comments about misuse, instructions for clinical use and interpretation, literature references, examples from the paper world, etc. It is not a rendering of the code system as conveyed in the 'text' field of the resource itself. This item SHOULD be populated unless the information is available from context (e.g. the language of the profile is presumed to be the predominant language in the place the profile was created).
CodeSystem.useContext
Definition | The content was developed with a focus and intent of supporting the contexts that are listed. These terms may be used to assist with indexing and searching for appropriate code system instances.
Control | 0..*
Type | UsageContext
Requirements | Assist in searching for appropriate content.
Summary | true
Comments | When multiple useContexts are specified, there is no expectation whether all or any of the contexts apply.
CodeSystem.jurisdiction
Definition | A legal or geographic region in which the code system is intended to be used.
Control | 0..*
Terminology Binding | Jurisdiction ValueSet (Extensible)
Type | CodeableConcept
Summary | true
Comments | It may be possible for the code system to be used in jurisdictions other than those for which it was originally designed or intended.
CodeSystem.purpose
Definition | Explaination of why this code system is needed and why it has been designed as it has.
Control | 0..1
Type | markdown
Comments | This element does not describe the usage of the code system Instead it provides traceability of ''why'' the resource is either needed or ''why'' it is defined as it is. This may be used to point to source materials or specifications that drove the structure of this code system.
CodeSystem.copyright
Definition | A copyright statement relating to the code system and/or its contents. Copyright statements are generally legal restrictions on the use and publishing of the code system.
Control | 0..1
Type | markdown
Requirements | Consumers must be able to determine any legal restrictions on the use of the code system and/or its content.
Alternate Names | License; Restrictions
Comments | ... Sometimes, the copyright differs between the code system and the codes that are included. The copyright statement should clearly differentiate between these when required.
CodeSystem.caseSensitive
Definition | If code comparison is case sensitive when codes within this system are compared to each other.
Control | 0..1
Type | boolean
Summary | true
Comments | If this value is missing, then it is not specified whether a code system is case sensitive or not. When the rule is not known, Postel's law should be followed: produce codes with the correct case, and accept codes in any case. This element is primarily provided to support validation software.
CodeSystem.valueSet
Definition | Canonical URL of value set that contains the entire code system.
Control | 0..1
Type | uri
Summary | true
Comments | The definition of the value set SHALL include all codes from this code system, and it SHALL be immutable.
CodeSystem.hierarchyMeaning
Definition | The meaning of the hierarchy of concepts.
Control | 0..1
Terminology Binding | CodeSystemHierarchyMeaning (Required)
Type | code
Summary | true
CodeSystem.compositional
Definition | True If code system defines a post-composition grammar.
Control | 0..1
Type | boolean
Alternate Names | grammar
Summary | true
Comments | Note that the code system resource does not define what the compositional grammar is, only whether or not there is one.
CodeSystem.versionNeeded
Definition | This flag is used to signify that the code system has not (or does not) maintain the definitions, and a version must be specified when referencing this code system.
Control | 0..1
Type | boolean
Summary | true
Comments | Best practice is that code systems do not redefine concepts, or that if concepts are redefined, a new code system definition is created. But this is not always possible, so some code systems may be defined as 'versionNeeded'.
CodeSystem.content
Definition | How much of the content of the code system - the concepts and codes it defines - are represented in this resource.
Control | 1..1
Terminology Binding | CodeSystemContentMode (Required)

Type | code
Summary | true
CodeSystem.count
Definition | The total number of concepts defined by the code system. Where the code system has a compositional grammar, the count refers to the number of base (primitive) concepts.
Control | 0..1
Type | unsignedInt
Summary | true
Comments | The count of concepts defined in this resource cannot be more than this value, but may be less for several reasons - see the content value.
CodeSystem.filter
Definition | A filter that can be used in a value set compose statement when selecting concepts using a filter.
Control | 0..*
Summary | true
CodeSystem.filter.code
Definition | The code that identifies this filter when it is used in the instance.
Control | 1..1
Type | code
Summary | true
CodeSystem.filter.description
Definition | A description of how or why the filter is used.
Control | 0..1
Type | string
Summary | true
CodeSystem.filter.operator
Definition | A list of operators that can be used with the filter.
Control | 1..*
Terminology Binding | FilterOperator (Required)
Type | code
Summary | true
CodeSystem.filter.value
Definition | A description of what the value for the filter should be.
Control | 1..1
Type | string
Summary | true
CodeSystem.property
Definition | A property defines an additional slot through which additional information can be provided about a concept.
Control | 0..*
Summary | true
CodeSystem.property.code
Definition | A code that is used to identify the property. The code is used internally (in CodeSystem.concept.property.code) and also externally, such as in property filters.
Control | 1..1
Type | code
Summary | true
CodeSystem.property.uri
Definition | Reference to the formal meaning of the property. One possible source of meaning is the Concept Properties code system.
Control | 0..1
Type | uri
Summary | true
CodeSystem.property.description
Definition | A description of the property- why it is defined, and how its value might be used.
Control | 0..1
Type | string
Summary | true
CodeSystem.property.type
Definition | The type of the property value. Properties of type "code" contain a code defined by the code system (e.g. a reference to anotherr defined concept).
Control | 1..1
Terminology Binding | PropertyType (Required)
Type | code
Summary | true
CodeSystem.concept
Definition | Concepts that are in the code system. The concept definitions are inherently hierarchical, but the definitions must be consulted to determine what the meaning of the hierarchical relationships are.
Control | 0..*
Comments | If this is empty, it means that the code system resource does not represent the content of the code system.
CodeSystem.concept.code
Definition | A code - a text symbol - that uniquely identifies the concept within the code system.
Control | 1..1
Type | code
CodeSystem.concept.display
Definition | A human readable string that is the recommended default way to present this concept to a user.

Control | 0..1
Type | string
CodeSystem.concept.definition
Definition | The formal definition of the concept. The code system resource does not make formal definitions required, because of the prevalence of legacy systems. However, they are highly recommended, as without them there is no formal meaning associated with the concept.
Control | 0..1
Type | string
CodeSystem.concept.designation
Definition | Additional representations for the concept - other languages, aliases, specialized purposes, used for particular purposes, etc.
Control | 0..*
Requirements | Many concept definition systems support multiple representations, in multiple languages, and for multiple purposes.
CodeSystem.concept.designation.language
Definition | The language this designation is defined for.
Control | 0..1
Terminology Binding | Common Languages (Extensible but limited to ??)
Type | code
Comments | In the absence of a language, the resource language applies.
CodeSystem.concept.designation.use
Definition | A code that details how this designation would be used.
Control | 0..1
Terminology Binding | Designation Use (Extensible)
Type | Coding
Comments | If no use is provided, the designation can be assumed to be suitable for general display to a human user.
CodeSystem.concept.designation.value
Definition | The text value for this designation.
Control | 1..1
Type | string
CodeSystem.concept.property
Definition | A property value for this concept.
Control | 0..*
CodeSystem.concept.property.code
Definition | A code that is a reference to CodeSystem.property.code.
Control | 1..1
Type | code
CodeSystem.concept.property.value[x]
Definition | The value of this property.
Control | 1..1
Type | code|Coding|string|integer|boolean|dateTime
[x] Note | See Choice of Data Types for further information about how to use [x]
CodeSystem.concept.concept
Definition | Defines children of a concept to produce a hierarchy of concepts. The nature of the relationships is variable (is-a/contains/categorizes) - see hierarchyMeaning.
Control | 0..*
Type | See CodeSystem.concept

4.7.10 Resource CodeSystem - Mappings

URL: https://hl7.org/fhir/STU3/codesystem-mappings.html

This page is part of the FHIR Specification (v3.0.2: STU 3). The current version which supercedes this version is 4.0.1. For a full list of available versions, see the Directory of published versions

4.7.10 Resource CodeSystem - Mappings

Vocabulary Work Group | Maturity Level: N/A | Ballot Status: Informative | Compartments: Not linked to any defined compartments

Mappings:

RIM Mapping

Mappings for the codesystem resource.

4.7.10.1 Mappings for RIM Mapping (http://hl7.org/v3)

CodeSystem | N/A

4.7.11 Resource CodeSystem - Design Notes

URL: https://hl7.org/fhir/STU3/codesystem-explanations.html

This page is part of the FHIR Specification (v3.0.2: STU 3). The current version which supercedes this version is 4.0.1. For a full list of available versions, see the Directory of published versions

4.7.11 Resource CodeSystem - Design Notes

to do

4.7.12 Resource CodeSystem - Extensions & Profiles

URL: https://hl7.org/fhir/STU3/codesystem-profiles.html

This page is part of the FHIR Specification (v3.0.2: STU 3). The current version which supercedes this version is 4.0.1. For a full list of available versions, see the Directory of published versions

4.7.12 Resource CodeSystem - Extensions & Profiles

Vocabulary Work Group | Maturity Level: N/A | Ballot Status: Informative

This table lists profiles and extensions for the CodeSystem resource. For background information, see Profiling Resources and Extensibility. Additional profiles and resources may be found in published Implementation Guides , or in the Conformance resource registry .

4.7.12.1 Profiles

ShareableCodeSystem | Enforces the minimum information set for the value set metadata required by HL7 and other organisations that share and publish value sets | for Shareable CodeSystem

4.7.12.2 Extensions

codesystem-author | author | for CodeSystem HL7 Extensions
codesystem-comment | comment | for CodeSystem HL7 Extensions
codesystem-comments | comments | for CodeSystem HL7 Extensions
codesystem-conceptOrder | conceptOrder | for CodeSystem HL7 Extensions
codesystem-deprecated | deprecated | for CodeSystem HL7 Extensions
codesystem-effectiveDate | effectiveDate | for CodeSystem HL7 Extensions
codesystem-expirationDate | expirationDate | for CodeSystem HL7 Extensions
codesystem-history | history | for CodeSystem HL7 Extensions
codesystem-keyWord | keyWord | for CodeSystem HL7 Extensions
codesystem-label | label | for CodeSystem HL7 Extensions
codesystem-map | map | for CodeSystem HL7 Extensions
codesystem-ordinalValue | ordinalValue | for CodeSystem HL7 Extensions
codesystem-otherName | otherName | for CodeSystem HL7 Extensions
codesystem-replacedby | replacedby | for CodeSystem HL7 Extensions
codesystem-sourceReference | sourceReference | for CodeSystem HL7 Extensions
codesystem-subsumes | subsumes | for CodeSystem HL7 Extensions
codesystem-trusted-expansion | trusted-expansion | for CodeSystem HL7 Extensions
codesystem-usage | usage | for CodeSystem HL7 Extensions
codesystem-warning | warning | for CodeSystem HL7 Extensions
codesystem-workflowStatus | workflowStatus | for CodeSystem HL7 Extensions
resource-approvalDate | approvalDate | for Resource HL7 Extensions
resource-effectivePeriod | effectivePeriod | for Resource HL7 Extensions
resource-lastReviewDate | lastReviewDate | for Resource HL7 Extensions

Extensions that reference this resource:

valueset-system | system | for ValueSet HL7 Extensions

4.7.12.3 Search Extensions

No Search Extensions defined for this resource

4.7.13 CodeSystem HL7 Extensions

URL: https://hl7.org/fhir/STU3/codesystem-extensions.html

Defines common extensions used with or related to the CodeSystem resource

This page is part of the FHIR Specification (v3.0.2: STU 3). The current version which supercedes this version is 4.0.1. For a full list of available versions, see the Directory of published versions

4.7.13 CodeSystem HL7 Extensions

(No assigned work group) | Maturity Level: N/A | Ballot Status: Informative

4.7.13.1 Content

Extensions:

codesystem-deprecated | deprecated : Set to true of the concept has been deprecated (still can be used, but soon to be withdrawn).
codesystem-comments | comments : A comment that explains how this code is used in this context (where the value set is expected to be used).
codesystem-subsumes | subsumes : Refers to another code defined within the code system that is also subsumed by this code. I.e. This concept subsumes the referenced concept. Because meaning is inferred from hierarchy as well as definition, the presence of this extension modifies the meaning of the extended concept.
codesystem-otherName | otherName : Human readable names for the codesystem.
codesystem-sourceReference | sourceReference : This text is intended to act as a citation to work done elsewhere that is not part of the current stewarding process where the referenced source is in some way a basis of the current value set definition.
codesystem-keyWord | keyWord : Word or words used in an information retrieval system to indicate the content of the value set.
codesystem-usage | usage : Consumers of the value set and the implementations, projects or standards that the author has utilized the value set in.

codesystem-workflowStatus | workflowStatus : Workflow Status is used to represent details of the value set development process while the value set has an Activity Status of Preliminary. The development of a value set often follows a formal workflow process from initiation to completion, and this element carries the state variable for this state machine. The assumption is that when first created a value set would have a workflow state of Draft. Additional workflow states may be used.

codesystem-effectiveDate | effectiveDate : This is the first date-time when the value set version becomes active, so this value is present on Inactive value set versions as well. The start Date_time is expected to be as of 0001 UTC of the Effective Date.

codesystem-expirationDate | expirationDate : The date when the value set version is no longer expected to be used to create new content. This is the first date-time when the value set version becomes Inactive, so this value MUST present on all Inactive value set versions. The start Date_time is expected to be as of 0001 UTC of the Expiration Date.

codesystem-author | author : User or Org actually involved in creating the value set content.

codesystem-comment | comment : Each comment is a time-stamped entry of arbitrary length that is not editable except by anyone in the author group.

codesystem-trusted-expansion | trusted-expansion : Indicates an authoritative source for performing value set expansions.

codesystem-history | history : Information on changes made to the Value Set Definition over time, and also has a contained audit trail of all such changes.

codesystem-label | label : The label to list in front of a code when presenting a list of possible values in a questionnaire-like fashion.

codesystem-ordinalValue | ordinalValue : A numeric value that allows the comparison (less than, greater than) or other numerical manipulation of a concept (e.g. adding up components of a score).

codesystem-conceptOrder | conceptOrder : Identifies the relative order in which concepts within the value set should be presented to a user.

codesystem-reference | reference : A logical reference (e.g. a reference to CodeSystem.url) that identifies the value set/version that identifies the set of possible coded values this coding was chosen from or constrained by.

codesystem-map | map : A reference to a concept map that is relevant for the interpretation of this value set.

codesystem-replacedby | replacedby : A code that replaces this - use this code instead.

codesystem-warning | warning : An extra warning about the correct use of the value set.

4.7.13.2 Search Parameters

Search parameters defined by this package. See Searching for more information about searching in REST, messaging, and services.

Name | Type | Description | Paths | Source

author | string | Optional Extensions Element | f:CodeSystem/f:extension[@url='http://hl7.org/fhir/StructureDefinition/codesystem-author'] | /f:#author | XML / JSON

effective | date | Optional Extensions Element | f:CodeSystem/f:extension[@url='http://hl7.org/fhir/StructureDefinition/codesystem-effectiveDate'] | /f:#effectiveDate | XML / JSON

end | date | Optional Extensions Element | f:CodeSystem/f:extension[@url='http://hl7.org/fhir/StructureDefinition/codesystem-expirationDate'] | /f:#expirationDate | XML / JSON

keyword | string | Optional Extensions Element | f:CodeSystem/f:extension[@url='http://hl7.org/fhir/StructureDefinition/codesystem-keyWord'] | /f:#keyWord | XML / JSON

workflow | token | Optional Extensions Element | f:CodeSystem/f:extension[@url='http://hl7.org/fhir/StructureDefinition/codesystem-workflowStatus'] | /f:#workflowStatus | XML / JSON

4.7.13.3 Codesystem-extensions-CodeSystem-keyword

URL: https://hl7.org/fhir/STU3/codesystem-extensions-CodeSystem-keyword.html

This page is part of the FHIR Specification (v3.0.2: STU 3). The current version which supercedes this version is 4.0.1. For a full list of available versions, see the Directory of published versions

4.7.13.3 Codesystem-extensions-CodeSystem-keyword

Search Parameter keyword (type: string) defined as part of the codesystem-extensions Profile.

Optional Extensions Element

Other Details:

* Full URL : http://hl7.org/fhir/SearchParameter/codesystem-extensions-CodeSystem-keyword

* Paths : f:CodeSystem/f:extension[@url='http://hl7.org/fhir/StructureDefinition/codesystem-keyWord'] | /f:#keyWord

* Targets :

4.7.13.4 Codesystem-extensions-CodeSystem-workflow

URL: https://hl7.org/fhir/STU3/codesystem-extensions-CodeSystem-workflow.html

This page is part of the FHIR Specification (v3.0.2: STU 3). The current version which supercedes this version is 4.0.1. For a full list of available versions, see the Directory of published versions

4.7.13.4 Codesystem-extensions-CodeSystem-workflow

Search Parameter workflow (type: token) defined as part of the codesystem-extensions Profile.

Optional Extensions Element

Other Details:

* Full URL : http://hl7.org/fhir/SearchParameter/codesystem-extensions-CodeSystem-workflow

* Paths : f:CodeSystem/f:extension[@url='http://hl7.org/fhir/StructureDefinition/codesystem-workflowStatus'] | /f:#workflowStatus

* Targets :

4.7.13.5 Codesystem-extensions-CodeSystem-effective

URL: https://hl7.org/fhir/STU3/codesystem-extensions-CodeSystem-effective.html

This page is part of the FHIR Specification (v3.0.2: STU 3). The current version which supercedes this version is 4.0.1. For a full list of available versions, see the Directory of published versions

4.7.13.5 Codesystem-extensions-CodeSystem-effective

Search Parameter effective (type: date) defined as part of the codesystem-extensions Profile.

Optional Extensions Element

Other Details:

* Full URL : http://hl7.org/fhir/SearchParameter/codesystem-extensions-CodeSystem-effective

* Paths : f:CodeSystem/f:extension[@url='http://hl7.org/fhir/StructureDefinition/codesystem-effectiveDate'] | /f:#effectiveDate

* Targets :

4.7.13.6 Codesystem-extensions-CodeSystem-end

URL: https://hl7.org/fhir/STU3/codesystem-extensions-CodeSystem-end.html

This page is part of the FHIR Specification (v3.0.2: STU 3). The current version which supercedes this version is 4.0.1. For a full list of available versions, see the Directory of published versions

4.7.13.6 Codesystem-extensions-CodeSystem-end

Search Parameter end (type: date) defined as part of the codesystem-extensions Profile.

Optional Extensions Element

Other Details:

* Full URL : http://hl7.org/fhir/SearchParameter/codesystem-extensions-CodeSystem-end

* Paths : f:CodeSystem/f:extension[@url='http://hl7.org/fhir/StructureDefinition/codesystem-expirationDate'] | /f:#expirationDate

* Targets :

4.7.13.7 Codesystem-extensions-CodeSystem-author

URL: https://hl7.org/fhir/STU3/codesystem-extensions-CodeSystem-author.html

This page is part of the FHIR Specification (v3.0.2: STU 3). The current version which supercedes this version is 4.0.1. For a full list of available versions, see the Directory of published versions

4.7.13.7 Codesystem-extensions-CodeSystem-author

Search Parameter author (type: string) defined as part of the codesystem-extensions Profile.

Optional Extensions Element

Other Details:

* Full URL : http://hl7.org/fhir/SearchParameter/codesystem-extensions-CodeSystem-author

* Paths : f:CodeSystem/f:extension[@url='http://hl7.org/fhir/StructureDefinition/codesystem-author'] | /f:#author

* Targets :

4.7.14 Shareable CodeSystem

URL: https://hl7.org/fhir/STU3/codesystem-shareable.html

Enforces the minimum information set for the value set metadata required by HL7 and other organisations that share and publish value sets

This page is part of the FHIR Specification (v3.0.2: STU 3). The current version which supercedes this version is 4.0.1. For a full list of available versions, see the Directory of published versions

4.7.14 Shareable CodeSystem

(No assigned work group) | Maturity Level: N/A | Ballot Status: Informative

4.7.14.1 Content

Profiles:

ShareableCodeSystem | Enforces the minimum information set for the value set metadata required by HL7 and other organisations that share and publish value sets

4.7.14.2 StructureDefinition: ShareableCodeSystem

URL: https://hl7.org/fhir/STU3/shareablecodesystem.html

This page is part of the FHIR Specification (v3.0.2: STU 3). The current version which supercedes this version is 4.0.1. For a full list of available versions, see the Directory of published versions

4.7.14.2 StructureDefinition: ShareableCodeSystem

(No assigned work group) | Maturity Level: 2 | Informative | Use Context: Any

The official URL for this profile is:

`http://hl7.org/fhir/StructureDefinition/shareablecodesystem`

Enforces the minimum information set for the value set metadata required by HL7 and other organisations that share and publish value sets

This profile was published on [no date] as a draft by HL7.

4.7.14.2.1 Formal Views of Profile Content

Description of Profiles, Differentials, Snapshots, and how the XML and JSON presentations work.

* Text Summary

* Differential Table

* Snapshot Table

* XML Template

* JSON Template

* All

This structure is derived from CodeSystem.

Summary

Mandatory: 10 elements

This structure is derived from CodeSystem.

Name | Flags | Card. | Type | Description & Constraints
CodeSystem | | 1..1
url | | 1..1 | uri
version | | 1..1 | string
name | | 1..1 | string
status | | 1..1 | code
experimental | | 1..1 | boolean
publisher | | 1..1 | string
description | | 1..1 | markdown
caseSensitive | | 1..1 | boolean
concept | | 1..* | BackboneElement
code | | 1..1 | code
display | | 0..1 | string
definition | | 0..1 | string
concept | | 0..* | | Unknown reference to #CodeSystem.concept
Documentation for this format

Name | Flags | Card. | Type | Description & Constraints
CodeSystem | I | 1..1 | | A set of codes drawn from one or more code systems
id | ? | 0..1 | id | Logical id of this artifact
meta | ? | 0..1 | Meta | Metadata about the resource
implicitRules | ?!? | 0..1 | uri | A set of rules under which this content was created
language | | 0..1 | code | Language of the resource content Binding: Common Languages (extensible)
text | I | 0..1 | Narrative | Text summary of the resource, for human interpretation
contained | | 0..* | Resource | Contained, inline Resources
extension | | 0..* | Extension | Additional Content defined by implementations
modifierExtension | ?! | 0..* | Extension | Extensions that cannot be ignored
url | ? | 1..1 | uri | Logical URI to reference this code system (globally unique) (Coding.system)
identifier | ? | 0..1 | Identifier | Additional identifier for the code system
version | ? | 1..1 | string | Business version of the code system (Coding.version)
name | ? | 1..1 | string | Name for this code system (computer friendly)
title | ? | 0..1 | string | Name for this code system (human friendly)
status | ?!? | 1..1 | code | draft | active | retired | unknown Binding: PublicationStatus (required)
experimental | ?!? | 1..1 | boolean | For testing purposes, not real usage
date | ? | 0..1 | dateTime | Date this was last changed
publisher | ? | 1..1 | string | Name of the publisher (organization or individual)
contact | ? | 0..* | ContactDetail | Contact details for the publisher
description | | 1..1 | markdown | Natural language description of the code system
useContext | ? | 0..* | UsageContext | Context the content is intended to support
jurisdiction | ? | 0..* | CodeableConcept | Intended jurisdiction for code system (if applicable) Binding: Jurisdiction ValueSet (extensible)
purpose | | 0..1 | markdown | Why this code system is defined
copyright | | 0..1 | markdown | Use and/or publishing restrictions
caseSensitive | ? | 1..1 | boolean | If code comparison is case sensitive
valueSet | ? | 0..1 | uri | Canonical URL for value set with entire code system

hierarchyMeaning | ? | 0..1 | code | grouped-by | is-a | part-of | classified-with Binding: CodeSystemHierarchyMeaning (required)
compositional | ? | 0..1 | boolean | If code system defines a post-composition grammar
versionNeeded | ? | 0..1 | boolean | If definitions are not stable
content | ? | 1..1 | code | not-present | example | fragment | complete Binding: CodeSystemContentMode (required)
count | ? | 0..1 | unsignedInt | Total concepts in the code system
filter | ?I | 0..* | BackboneElement | Filter that can be used in a value set
id | | 0..1 | string | xml:id (or equivalent in JSON)
extension | | 0..* | Extension | Additional Content defined by implementations
modifierExtension | ?!? | 0..* | Extension | Extensions that cannot be ignored
code | ? | 1..1 | code | Code that identifies the filter
description | ? | 0..1 | string | How or why the filter is used
operator | ? | 1..* | code | Operators that can be used with filter Binding: FilterOperator (required)
value | ? | 1..1 | string | What to use for the value
property | ?I | 0..* | BackboneElement | Additional information supplied about each concept
id | | 0..1 | string | xml:id (or equivalent in JSON)
extension | | 0..* | Extension | Additional Content defined by implementations
modifierExtension | ?!? | 0..* | Extension | Extensions that cannot be ignored
code | ? | 1..1 | code | Identifies the property on the concepts, and when referred to in operations
uri | ? | 0..1 | uri | Formal identifier for the property
description | ? | 0..1 | string | Why the property is defined, and/or what it conveys
type | ? | 1..1 | code | code | Coding | string | integer | boolean | dateTime Binding: PropertyType (required)
concept | I | 1..* | BackboneElement | Concepts in the code system
id | | 0..1 | string | xml:id (or equivalent in JSON)
extension | | 0..* | Extension | Additional Content defined by implementations
modifierExtension | ?!? | 0..* | Extension | Extensions that cannot be ignored
code | | 1..1 | code | Code that identifies concept
display | | 0..1 | string | Text to display to the user
definition | | 0..1 | string | Formal definition
designation | I | 0..* | BackboneElement | Additional representations for the concept
id | | 0..1 | string | xml:id (or equivalent in JSON)
extension | | 0..* | Extension | Additional Content defined by implementations
modifierExtension | ?!? | 0..* | Extension | Extensions that cannot be ignored
language | | 0..1 | code | Human language of the designation Binding: Common Languages (extensible)
use | | 0..1 | Coding | Details how this designation would be used Binding: Designation Use (extensible)
value | | 1..1 | string | The text value for this designation
property | I | 0..* | BackboneElement | Property value for the concept
id | | 0..1 | string | xml:id (or equivalent in JSON)
extension | | 0..* | Extension | Additional Content defined by implementations
modifierExtension | ?!? | 0..* | Extension | Extensions that cannot be ignored
code | | 1..1 | code | Reference to CodeSystem.property.code
value[x] | | 1..1 | code, Coding, string, integer, boolean, dateTime | Value of the property for this concept
concept | | 0..* | | Unknown reference to #CodeSystem.concept Child Concepts (is-a/contains/categorizes)
Documentation for this format

```
<!-- Shareable CodeSystem -->

<CodeSystem xmlns="http://hl7.org/fhir"
>
  <!-- from Element: extension -->
 <id value="[id]"/><!-- 0..1 Logical id of this artifact -->
 <meta><!-- 0..1 Meta Metadata about the resource --></meta>
 <implicitRules value="[uri]"/><!-- 0..1 A set of rules under which this content was created -->
 <language value="[code]"/><!-- 0..1 Language of the resource content  -->
 <text><!-- 0..1 Narrative
     Text summary of the resource, for human interpretation --></text>
 <contained><!-- 0..* Resource Contained, inline Resources --></contained>
 <modifierExtension><!-- 0..* Extension  Extensions that cannot be ignored  --></modifierExtension>
 <url value="[uri]"/><!-- 1..1 Logical URI to reference this code system (globally unique) (Coding.system) -->
 <identifier><!-- 0..1 Identifier
     Additional identifier for the code system --></identifier>
 <version value="[string]"/><!-- 1..1 Business version of the code system (Coding.version) -->
 <name value="[string]"/><!-- 1..1 Name for this code system (computer friendly) -->
 <title value="[string]"/><!-- 0..1 Name for this code system (human friendly) -->
 <status value="[code]"/><!-- 1..1 draft | active | retired | unknown  -->
 <experimental value="[boolean]"/><!-- 1..1 For testing purposes, not real usage -->
 <date value="[dateTime]"/><!-- 0..1 Date this was last changed -->
 <publisher value="[string]"/><!-- 1..1 Name of the publisher (organization or individual) -->
 <contact><!-- 0..* ContactDetail Contact details for the publisher --></contact>
 <description value="[markdown]"/><!-- 1..1 Natural language description of the code system -->
 <useContext><!-- 0..* UsageContext
     Context the content is intended to support --></useContext>
 <jurisdiction><!-- 0..* CodeableConcept Intended jurisdiction for code system (if applicable)  --></jurisdiction>
 <purpose value="[markdown]"/><!-- 0..1 Why this code system is defined -->
 <copyright value="[markdown]"/><!-- 0..1 Use and/or publishing restrictions -->
 <caseSensitive value="[boolean]"/><!-- 1..1 If code comparison is case sensitive -->
 <valueSet value="[uri]"/><!-- 0..1 Canonical URL for value set with entire code system -->
 <hierarchyMeaning value="[code]"/><!-- 0..1 grouped-by | is-a | part-of | classified-with  -->
 <compositional value="[boolean]"/><!-- 0..1 If code system defines a post-composition grammar -->
 <versionNeeded value="[boolean]"/><!-- 0..1 If definitions are not stable -->
 <content value="[code]"/><!-- 1..1 not-present | example | fragment | complete  -->
```

```
 <count value="[unsignedInt]"/><!-- 0..1 Total concepts in the code system -->
 <filter>  0..* BackboneElement  <!--  0..* Filter that can be used in a value set -->
  <modifierExtension><!-- 0..* Extension  Extensions that cannot be ignored  --></modifierExtension>
  <code value="[code]"/><!-- 1..1 Code that identifies the filter -->
  <description value="[string]"/><!-- 0..1 How or why the filter is used -->
  <operator value="[code]"/><!-- 1..* Operators that can be used with filter  -->
  <value value="[string]"/><!-- 1..1 What to use for the value -->
 </filter>
 <property>  0..* BackboneElement  <!--  0..* Additional information supplied about each concept -->
  <modifierExtension><!-- 0..* Extension  Extensions that cannot be ignored  --></modifierExtension>
  <code value="[code]"/><!-- 1..1
      Identifies the property on the concepts, and when referred to in operations -->
  <uri value="[uri]"/><!-- 0..1 Formal identifier for the property -->
  <description value="[string]"/><!-- 0..1 Why the property is defined, and/or what it conveys -->
  <type value="[code]"/><!-- 1..1 code | Coding | string | integer | boolean | dateTime  -->
 </property>
 <concept>  1..* BackboneElement  <!--  1..* Concepts in the code system -->
  <modifierExtension><!-- 0..* Extension  Extensions that cannot be ignored  --></modifierExtension>
  <code value="[code]"/><!-- 1..1 Code that identifies concept -->
  <display value="[string]"/><!-- 0..1 Text to display to the user -->
  <definition value="[string]"/><!-- 0..1 Formal definition -->
  <designation>  0..* BackboneElement  <!--  0..* Additional representations for the concept -->
   <modifierExtension><!-- 0..* Extension  Extensions that cannot be ignored  --></modifierExtension>
   <language value="[code]"/><!-- 0..1 Human language of the designation  -->
   <use><!-- 0..1 Coding Details how this designation would be used  --></use>
   <value value="[string]"/><!-- 1..1 The text value for this designation -->
  </designation>
  <property>  0..* BackboneElement  <!--  0..* Property value for the concept -->
   <modifierExtension><!-- 0..* Extension  Extensions that cannot be ignored  --></modifierExtension>
   <code value="[code]"/><!-- 1..1 Reference to CodeSystem.property.code -->
   <value[x]><!-- 1..1 code|Coding|string|integer|
     boolean|dateTime Value of the property for this concept --></value[x]>
  </property>
  <concept><!-- See #CodeSystem.concept  Child Concepts (is-a/contains/categorizes) --></concept>
 </concept>
</CodeSystem>
```

```
{ // Shareable CodeSystem
  // from Element: extension
    "meta" : { Meta }, //Metadata about the resource
    "implicitRules" : "<uri>", //A set of rules under which this content was created
    "language" : "<code>", //Language of the resource content
    "text" : { Narrative }, //Text summary of the resource, for human interpretation
    "contained" : [{ Resource }], //Contained, inline Resources
    "modifierExtension" : [{ Extension }], //Extensions that cannot be ignored
    "url" : "<uri>", // R! Logical URI to reference this code system (globally unique) (Coding.system)
    "identifier" : { Identifier }, //Additional identifier for the code system
    "version" : "<string>", // R! Business version of the code system (Coding.version)
    "name" : "<string>", // R! Name for this code system (computer friendly)
    "title" : "<string>", //Name for this code system (human friendly)
    "status" : "<code>", // R! draft | active | retired | unknown
    "experimental" : <boolean>, // R! For testing purposes, not real usage
    "date" : "<dateTime>", //Date this was last changed
    "publisher" : "<string>", // R! Name of the publisher (organization or individual)
    "contact" : [{ ContactDetail }], //Contact details for the publisher
    "description" : "<markdown>", // R! Natural language description of the code system
    "useContext" : [{ UsageContext }], //Context the content is intended to support
    "jurisdiction" : [{ CodeableConcept }], //Intended jurisdiction for code system (if applicable)
    "purpose" : "<markdown>", //Why this code system is defined
    "copyright" : "<markdown>", //Use and/or publishing restrictions
    "caseSensitive" : <boolean>, // R! If code comparison is case sensitive
    "valueSet" : "<uri>", //Canonical URL for value set with entire code system
    "hierarchyMeaning" : "<code>", //grouped-by | is-a | part-of | classified-with
    "compositional" : <boolean>, //If code system defines a post-composition grammar
    "versionNeeded" : <boolean>, //If definitions are not stable
    "content" : "<code>", // R! not-present | example | fragment | complete
    "count" : "<unsignedInt>", //Total concepts in the code system
    "filter" : [{ BackboneElement }], // C?Filter that can be used in a value set
    "property" : [{ BackboneElement }], // C?Additional information supplied about each concept
    "concept" : [{ BackboneElement }] // C? R! Concepts in the code system
  }
```

This structure is derived from CodeSystem.

Summary

Mandatory: 10 elements

Differential View

This structure is derived from CodeSystem.

Name	Flags	Card.	Type	Description & Constraints
CodeSystem		1..1		
url		1..1	uri	
version		1..1	string	
name		1..1	string	
status		1..1	code	
experimental		1..1	boolean	
publisher		1..1	string	

description | | 1..1 | markdown
caseSensitive | | 1..1 | boolean
concept | | 1..* | BackboneElement
code | | 1..1 | code
display | | 0..1 | string
definition | | 0..1 | string
concept | | 0..* | | Unknown reference to #CodeSystem.concept
Documentation for this format

Snapshot View

Name | Flags | Card. | Type | Description & Constraints
CodeSystem | I | 1..1 | | A set of codes drawn from one or more code systems
id | ? | 0..1 | id | Logical id of this artifact
meta | ? | 0..1 | Meta | Metadata about the resource
implicitRules | ?!? | 0..1 | uri | A set of rules under which this content was created
language | | 0..1 | code | Language of the resource content Binding: Common Languages (extensible)
text | I | 0..1 | Narrative | Text summary of the resource, for human interpretation
contained | | 0..* | Resource | Contained, inline Resources
extension | | 0..* | Extension | Additional Content defined by implementations
modifierExtension | ?! | 0..* | Extension | Extensions that cannot be ignored
url | ? | 1..1 | uri | Logical URI to reference this code system (globally unique) (Coding.system)
identifier | ? | 0..1 | Identifier | Additional identifier for the code system
version | ? | 1..1 | string | Business version of the code system (Coding.version)
name | ? | 1..1 | string | Name for this code system (computer friendly)
title | ? | 0..1 | string | Name for this code system (human friendly)
status | ?!? | 1..1 | code | draft | active | retired | unknown Binding: PublicationStatus (required)
experimental | ?!? | 1..1 | boolean | For testing purposes, not real usage
date | ? | 0..1 | dateTime | Date this was last changed
publisher | ? | 1..1 | string | Name of the publisher (organization or individual)
contact | ? | 0..* | ContactDetail | Contact details for the publisher
description | | 1..1 | markdown | Natural language description of the code system
useContext | ? | 0..* | UsageContext | Context the content is intended to support
jurisdiction | ? | 0..* | CodeableConcept | Intended jurisdiction for code system (if applicable) Binding: Jurisdiction ValueSet (extensible)
purpose | | 0..1 | markdown | Why this code system is defined
copyright | | 0..1 | markdown | Use and/or publishing restrictions
caseSensitive | ? | 1..1 | boolean | If code comparison is case sensitive
valueSet | ? | 0..1 | uri | Canonical URL for value set with entire code system
hierarchyMeaning | ? | 0..1 | code | grouped-by | is-a | part-of | classified-with Binding: CodeSystemHierarchyMeaning (required)
compositional | ? | 0..1 | boolean | If code system defines a post-composition grammar
versionNeeded | ? | 0..1 | boolean | If definitions are not stable
content | ? | 1..1 | code | not-present | example | fragment | complete Binding: CodeSystemContentMode (required)
count | ? | 0..1 | unsignedInt | Total concepts in the code system
filter | ?I | 0..* | BackboneElement | Filter that can be used in a value set
id | | 0..1 | string | xml:id (or equivalent in JSON)
extension | | 0..* | Extension | Additional Content defined by implementations
modifierExtension | ?!? | 0..* | Extension | Extensions that cannot be ignored
code | ? | 1..1 | code | Code that identifies the filter
description | ? | 0..1 | string | How or why the filter is used
operator | ? | 1..* | code | Operators that can be used with filter Binding: FilterOperator (required)
value | ? | 1..1 | string | What to use for the value
property | ?I | 0..* | BackboneElement | Additional information supplied about each concept
id | | 0..1 | string | xml:id (or equivalent in JSON)
extension | | 0..* | Extension | Additional Content defined by implementations
modifierExtension | ?!? | 0..* | Extension | Extensions that cannot be ignored
code | ? | 1..1 | code | Identifies the property on the concepts, and when referred to in operations
uri | ? | 0..1 | uri | Formal identifier for the property
description | ? | 0..1 | string | Why the property is defined, and/or what it conveys
type | ? | 1..1 | code | code | Coding | string | integer | boolean | dateTime Binding: PropertyType (required)
concept | I | 1..* | BackboneElement | Concepts in the code system
id | | 0..1 | string | xml:id (or equivalent in JSON)
extension | | 0..* | Extension | Additional Content defined by implementations
modifierExtension | ?!? | 0..* | Extension | Extensions that cannot be ignored
code | | 1..1 | code | Code that identifies concept
display | | 0..1 | string | Text to display to the user
definition | | 0..1 | string | Formal definition
designation | I | 0..* | BackboneElement | Additional representations for the concept
id | | 0..1 | string | xml:id (or equivalent in JSON)
extension | | 0..* | Extension | Additional Content defined by implementations
modifierExtension | ?!? | 0..* | Extension | Extensions that cannot be ignored
language | | 0..1 | code | Human language of the designation Binding: Common Languages (extensible)
use | | 0..1 | Coding | Details how this designation would be used Binding: Designation Use (extensible)
value | | 1..1 | string | The text value for this designation

property | I | 0..* | BackboneElement | Property value for the concept
id | | 0..1 | string | xml:id (or equivalent in JSON)
extension | | 0..* | Extension | Additional Content defined by implementations
modifierExtension | ?!? | 0..* | Extension | Extensions that cannot be ignored
code | | 1..1 | code | Reference to CodeSystem.property.code
value[x] | | 1..1 | code, Coding, string, integer, boolean, dateTime | Value of the property for this concept
concept | | 0..* | | Unknown reference to #CodeSystem.concept Child Concepts (is-a/contains/categorizes)
Documentation for this format

XML Template

```
<!-- Shareable CodeSystem -->

<CodeSystem xmlns="http://hl7.org/fhir"
>
  <!-- from Element: extension -->
 <id value="[id]"/><!-- 0..1 Logical id of this artifact -->
 <meta><!-- 0..1 Meta Metadata about the resource --></meta>
 <implicitRules value="[uri]"/><!-- 0..1 A set of rules under which this content was created -->
 <language value="[code]"/><!-- 0..1 Language of the resource content  -->
 <text><!-- 0..1 Narrative
     Text summary of the resource, for human interpretation --></text>
 <contained><!-- 0..* Resource Contained, inline Resources --></contained>
 <modifierExtension><!-- 0..* Extension  Extensions that cannot be ignored  --></modifierExtension>
 <url value="[uri]"/><!-- 1..1 Logical URI to reference this code system (globally unique) (Coding.system) -->
 <identifier><!-- 0..1 Identifier
     Additional identifier for the code system --></identifier>
 <version value="[string]"/><!-- 1..1 Business version of the code system (Coding.version) -->
 <name value="[string]"/><!-- 1..1 Name for this code system (computer friendly) -->
 <title value="[string]"/><!-- 0..1 Name for this code system (human friendly) -->
 <status value="[code]"/><!-- 1..1 draft | active | retired | unknown  -->
 <experimental value="[boolean]"/><!-- 1..1 For testing purposes, not real usage -->
 <date value="[dateTime]"/><!-- 0..1 Date this was last changed -->
 <publisher value="[string]"/><!-- 1..1 Name of the publisher (organization or individual) -->
 <contact><!-- 0..* ContactDetail Contact details for the publisher --></contact>
 <description value="[markdown]"/><!-- 1..1 Natural language description of the code system -->
 <useContext><!-- 0..* UsageContext
     Context the content is intended to support --></useContext>
 <jurisdiction><!-- 0..* CodeableConcept Intended jurisdiction for code system (if applicable)  --></jurisdiction>
 <purpose value="[markdown]"/><!-- 0..1 Why this code system is defined -->
 <copyright value="[markdown]"/><!-- 0..1 Use and/or publishing restrictions -->
 <caseSensitive value="[boolean]"/><!-- 1..1 If code comparison is case sensitive -->
 <valueSet value="[uri]"/><!-- 0..1 Canonical URL for value set with entire code system -->
 <hierarchyMeaning value="[code]"/><!-- 0..1 grouped-by | is-a | part-of | classified-with  -->
 <compositional value="[boolean]"/><!-- 0..1 If code system defines a post-composition grammar -->
 <versionNeeded value="[boolean]"/><!-- 0..1 If definitions are not stable -->
 <content value="[code]"/><!-- 1..1 not-present | example | fragment | complete  -->
 <count value="[unsignedInt]"/><!-- 0..1 Total concepts in the code system -->
 <filter>  0..* BackboneElement  <!--  0..* Filter that can be used in a value set -->
  <modifierExtension><!-- 0..* Extension  Extensions that cannot be ignored  --></modifierExtension>
  <code value="[code]"/><!-- 1..1 Code that identifies the filter -->
  <description value="[string]"/><!-- 0..1 How or why the filter is used -->
  <operator value="[code]"/><!-- 1..* Operators that can be used with filter  -->
  <value value="[string]"/><!-- 1..1 What to use for the value -->
 </filter>
 <property>  0..* BackboneElement  <!--  0..* Additional information supplied about each concept -->
  <modifierExtension><!-- 0..* Extension  Extensions that cannot be ignored  --></modifierExtension>
  <code value="[code]"/><!-- 1..1
      Identifies the property on the concepts, and when referred to in operations -->
  <uri value="[uri]"/><!-- 0..1 Formal identifier for the property -->
  <description value="[string]"/><!-- 0..1 Why the property is defined, and/or what it conveys -->
  <type value="[code]"/><!-- 1..1 code | Coding | string | integer | boolean | dateTime  -->
 </property>
 <concept>  1..* BackboneElement  <!--  1..* Concepts in the code system -->
  <modifierExtension><!-- 0..* Extension  Extensions that cannot be ignored  --></modifierExtension>
  <code value="[code]"/><!-- 1..1 Code that identifies concept -->
  <display value="[string]"/><!-- 0..1 Text to display to the user -->
  <definition value="[string]"/><!-- 0..1 Formal definition -->
  <designation>  0..* BackboneElement  <!--  0..* Additional representations for the concept -->
   <modifierExtension><!-- 0..* Extension  Extensions that cannot be ignored  --></modifierExtension>
   <language value="[code]"/><!-- 0..1 Human language of the designation  -->
   <use><!-- 0..1 Coding Details how this designation would be used  --></use>
   <value value="[string]"/><!-- 1..1 The text value for this designation -->
  </designation>
  <property>  0..* BackboneElement  <!--  0..* Property value for the concept -->
   <modifierExtension><!-- 0..* Extension  Extensions that cannot be ignored  --></modifierExtension>
   <code value="[code]"/><!-- 1..1 Reference to CodeSystem.property.code -->
   <value[x]><!-- 1..1 code|Coding|string|integer|
     boolean|dateTime Value of the property for this concept --></value[x]>
  </property>
  <concept><!-- See #CodeSystem.concept  Child Concepts (is-a/contains/categorizes) --></concept>
 </concept>
</CodeSystem>
```

JSON Template

```
{ // Shareable CodeSystem
  // from Element: extension
    "meta" : { Meta }, //Metadata about the resource
```

```
  "implicitRules" : "<uri>", //A set of rules under which this content was created
  "language" : "<code>", //Language of the resource content
  "text" : { Narrative }, //Text summary of the resource, for human interpretation
  "contained" : [{ Resource }], //Contained, inline Resources
  "modifierExtension" : [{ Extension }], //Extensions that cannot be ignored
  "url" : "<uri>", // R! Logical URI to reference this code system (globally unique) (Coding.system)
  "identifier" : { Identifier }, //Additional identifier for the code system
  "version" : "<string>", // R! Business version of the code system (Coding.version)
  "name" : "<string>", // R! Name for this code system (computer friendly)
  "title" : "<string>", //Name for this code system (human friendly)
  "status" : "<code>", // R! draft | active | retired | unknown
  "experimental" : <boolean>, // R! For testing purposes, not real usage
  "date" : "<dateTime>", //Date this was last changed
  "publisher" : "<string>", // R! Name of the publisher (organization or individual)
  "contact" : [{ ContactDetail }], //Contact details for the publisher
  "description" : "<markdown>", // R! Natural language description of the code system
  "useContext" : [{ UsageContext }], //Context the content is intended to support
  "jurisdiction" : [{ CodeableConcept }], //Intended jurisdiction for code system (if applicable)
  "purpose" : "<markdown>", //Why this code system is defined
  "copyright" : "<markdown>", //Use and/or publishing restrictions
  "caseSensitive" : <boolean>, // R! If code comparison is case sensitive
  "valueSet" : "<uri>", //Canonical URL for value set with entire code system
  "hierarchyMeaning" : "<code>", //grouped-by | is-a | part-of | classified-with
  "compositional" : <boolean>, //If code system defines a post-composition grammar
  "versionNeeded" : <boolean>, //If definitions are not stable
  "content" : "<code>", // R! not-present | example | fragment | complete
  "count" : "<unsignedInt>", //Total concepts in the code system
  "filter" : [{ BackboneElement }], // C?Filter that can be used in a value set
  "property" : [{ BackboneElement }], // C?Additional information supplied about each concept
  "concept" : [{ BackboneElement }] // C? R! Concepts in the code system
}
```

Other representations of profile: Schematron

4.7.14.2.2 Terminology Bindings

Path | Name | Conformance | ValueSet
CodeSystem.language | Common Languages | extensible | Common Languages
CodeSystem.status | PublicationStatus | required | PublicationStatus
CodeSystem.jurisdiction | Jurisdiction ValueSet | extensible | Jurisdiction ValueSet
CodeSystem.hierarchyMeaning | CodeSystemHierarchyMeaning | required | CodeSystemHierarchyMeaning
CodeSystem.content | CodeSystemContentMode | required | CodeSystemContentMode
CodeSystem.filter.operator | FilterOperator | required | FilterOperator
CodeSystem.property.type | PropertyType | required | PropertyType
CodeSystem.concept.designation.language | Common Languages | extensible | Common Languages
CodeSystem.concept.designation.use | Designation Use | extensible | Designation Use

4.7.15 Resource CodeSystem - Operations

URL: https://hl7.org/fhir/STU3/codesystem-operations.html

This page is part of the FHIR Specification (v3.0.2: STU 3). The current version which supercedes this version is 4.0.1. For a full list of available versions, see the Directory of published versions

4.7.15 Resource CodeSystem - Operations

Vocabulary Work Group | Maturity Level: 5 | Trial Use | Compartments: Not linked to any defined compartments

This resource has 3 operations associated with it:

$lookup | Concept Look Up & Decomposition
$subsumes | Subsumption Testing
$compose | Code Composition based on supplied properties

For more information about operations, including how they are invoked, see Operations.

4.7.15.1 Concept Look Up & Decomposition

Given a code/system, or a Coding, get additional details about the concept, including definition, status, designations, and properties. One of the products of this operation is a full decomposition of a code from a structure terminology

The official URL for this operation definition is

```
http://hl7.org/fhir/OperationDefinition/CodeSystem-lookup
```

Formal Definition (as a OperationDefinition).

URL: [base]/CodeSystem/$lookup

This is an idempotent operation

In Parameters:
Name | Cardinality | Type | Binding | Profile | Documentation
code | 0..1 | code | | | The code that is to be located. If a code is provided, a system must be provided
system | 0..1 | uri | | | The system for the code that is to be located
version | 0..1 | string | | | The version of the system, if one was provided in the source data
coding | 0..1 | Coding | | | A coding to look up

date | 0..1 | dateTime | | | The date for which the information should be returned. Normally, this is the current conditions (which is the default value) but under some circumstances, systems need to acccess this information as it would have been in the past. A typical example of this would be where code selection is constrained to the set of codes that were available when the patient was treated, not when the record is being edited. Note that which date is appropriate is a matter for implementation policy.
displayLanguage | 0..1 | code | | | The requested language for display (see ExpansionProfile.displayLanguage)
property | 0..* | code | | | A property that the client wishes to be returned in the output. If no properties are specified, the server chooses what to return. The following properties are defined for all code systems: url, name, version (code system info) and code information: display, definition, designation, parent and child, and for designations, lang.X where X is a designation language code. Some of the properties are returned explicit in named parameters (when the names match), and the rest (except for lang.X) in the property parameter group
Out Parameters:
Name | Cardinality | Type | Binding | Profile | Documentation
name | 1..1 | string | | | A display name for the code system
version | 0..1 | string | | | The version that these details are based on
display | 1..1 | string | | | The preferred display for this concept
designation | 0..* | | | | Additional representations for this concept
designation.language | 0..1 | code | | | The language this designation is defined for
designation.use | 0..1 | Coding | | | A code that details how this designation would be used
designation.value | 1..1 | string | | | The text value for this designation
property | 0..* | | | | One or more properties that contain additional information about the code, including status. For complex terminologies (e.g. SNOMED CT, LOINC, medications), these properties serve to decompose the code
property.code | 1..1 | code | | | Identifies the property returned
property.value | 0..1 | code | Coding | string | integer | boolean | dateTime | | | The value of the property returned
property.description | 0..1 | string | | | Human Readable representation of the property value (e.g. display for a code)
property.subproperty | 0..* | | | | Nested Properties (mainly used for SNOMED CT decomposition, for relationship Groups)
property.subproperty.code | 1..1 | code | | | Identifies the sub-property returned
property.subproperty.value | 1..1 | code | Coding | string | integer | boolean | dateTime | | | The value of the sub-property returned
property.subproperty.description | 0..1 | string | | | Human Readable representation of the property value (e.g. display for a code)

Note that the $lookup operation is more than just a code system search - the server finds the concept, and gathers the return information from the underlying code system definitions.

4.7.15.1.1 Examples

Looking up a code/system (Request):

```
GET [base]/CodeSystem/$lookup?system=http://loinc.org&code=1963-8
```

Lookup using a Coding (Request):

```
POST [base]/CodeSystem/$lookup
[other headers]

<Parameters xmlns="http://hl7.org/fhir">
  <parameter>
    <name value="coding"/>
  <valueCoding>
    <system value="http://loinc.org"/>
    <code value="1963-8"/>
  </valueCoding>
  </parameter>
</Parameters>
```

Response:

```
HTTP/1.1 200 OK
[other headers]

{
  "resourceType" : "Parameters",
  "parameter" : [
    {
    "name" : "name",
    "valueString" : "LOINC"
  },
  {
    "name" : "version",
    "valueString" : "2.48"
  },
  {
    "name" : "designation",
    "valueString" : "Bicarbonate [Moles/volume] in Serum"
  },
  {
    "name" : "abstract",
    "valueString" : "false"
  },
  {
      "name" : "designation",
    "part" : [
    {
      "name" : "value",
      "valueString" : "Bicarbonate [Moles/volume] in Serum "
    }
    ]
  }
  ]
```

```
}
```

4.7.15.2 Subsumption Testing

Test the subsumption relationship between code/Coding A and code/Coding B given the semantics of subsumption in the underlying code system (see hierarchyMeaning)

The official URL for this operation definition is

```
http://hl7.org/fhir/OperationDefinition/CodeSystem-subsumes
```

Formal Definition (as a OperationDefinition).

URL: [base]/CodeSystem/$subsumes

URL: [base]/CodeSystem/[id]/$subsumes

This is an idempotent operation

In Parameters:

Name | Cardinality | Type | Binding | Profile | Documentation

codeA | 0..1 | code | | | The "A" code that is to be tested. If a code is provided, a system must be provided

codeB | 0..1 | code | | | The "B" code that is to be tested. If a code is provided, a system must be provided

system | 0..1 | uri | | | The code system in which subsumption testing is to be performed. This must be provided unless the operation is invoked on a code system instance

version | 0..1 | string | | | The version of the code system, if one was provided in the source data

codingA | 0..1 | Coding | | | The "A" Coding that is to be tested. The code system does not have to match the specified subsumption code system, but the relationships between the code systems must be well established

codingB | 0..1 | Coding | | | The "B" Coding that is to be tested. The code system does not have to match the specified subsumption code system, but the relationships between the code systems must be well established

Out Parameters:

Name | Cardinality | Type | Binding | Profile | Documentation

outcome | 1..1 | code | | | The subsumption relationship between code/Coding "A" and code/Coding "B". There are 4 possible codes to be returned: equivalent, subsumes, subsumed-by, and not-subsumed. If the server is unable to determine the relationship between the codes/Codings, then it returns an error (i.e. an OperationOutcome)

4.7.15.2.1 Examples

Using simple parameters: is 'Viral hepatitis' (3738000) a 'Disorder of liver' (235856003)? (Request):

```
GET [base]/CodeSystem/$subsumes?system=http://snomed.info/sct&codeA=3738000&codeB=235856003
```

Using Codings (Request):

```
POST [base]/CodeSystem/$subsumes
[other headers]

<Parameters xmlns="http://hl7.org/fhir">
  <!-- Subsumption testing - use SNOMED CT rules -->
  <parameter>
    <name value="system"/>
    <valuUri value="http://snomed.info/sct"/>
  </parameter>
  <!-- Australian distribution -->
  <parameter>
    <name value="version"/>
    <valuString value="http://snomed.info/sct/32506021000036107/version/20160430"/>
  </parameter>
  <parameter>
    <name value="codingA"/>
    <valueCoding>
      <system value="http://snomed.info/sct"/>
      <code value="3738000"/>
    </valueCoding>
  </parameter>
  <parameter>
    <name value="codingB"/>
    <valueCoding>
      <system value="http://snomed.info/sct"/>
      <code value="235856003"/>
    </valueCoding>
  </parameter>
</Parameters>
```

Response:

```
HTTP/1.1 200 OK
[other headers]

{
  "resourceType" : "Parameters",
  "parameter" : [
    {
    "name" : "outcome",
    "valueCode" : "subsumed-by"
  }
}
```

4.7.15.3 Code Composition based on supplied properties

Given a set of properties, return one or more possible matching codes

This operation takes a set of properties, and examines the code system looking for codes in the code system that match a set of known properties.

When looking for matches, there are 3 possible types of match: * a complete match - a code that represents all the provided properties correctly * a partial match - a code that represents some of the provided properties correctly, and not others * a possible match - a code that may represent the provided properties closely, but may capture less or more precise informationfor some of the properties

The $compose operation can be called in one of 2 modes: * By a human, looking for the best match for a set of properties. In this mode, the server returns a list of complete, possible or partial matches (possibly with comments), so that the user can choose (or not) the most appropriate code * By a machine (typically in a system interface performing a transformation). In this mode, the server returns only a list of complete and partial matches, but no possible matches. The machine can choose a code from the list (or not) based on what properties are not coded

These modes are differentiated by the 'exact' parameter, so the client can indicate whether it only wants exact matches (including partial matches) or whether potential matches based on text matching are desired

The compose operation is still preliminary. The interface can be expected to change as more experience is gained from implementations.

The official URL for this operation definition is

`http://hl7.org/fhir/OperationDefinition/CodeSystem-compose`

Formal Definition (as a OperationDefinition).

URL: [base]/CodeSystem/$compose

URL: [base]/CodeSystem/[id]/$compose

This is an idempotent operation

In Parameters:

Name | Cardinality | Type | Binding | Profile | Documentation
system | 0..1 | uri | | | The system in which composition is to be performed. This must be provided unless the operation is invoked on a code system instance
version | 0..1 | string | | | The version of the system for the inferencing to be performed
property | 0..* | | | | One or more properties that contain information to be composed into the code
property.code | 1..1 | code | | | Identifies the property provided
property.value | 0..1 | code | Coding | string | integer | boolean | dateTime | | | The value of the property provided
property.subproperty | 0..* | | | | Nested Properties (mainly used for SNOMED CT composition, for relationship Groups)
property.subproperty.code | 1..1 | code | | | Identifies the sub-property provided
property.subproperty.value | 1..1 | code | Coding | string | integer | boolean | dateTime | | | The value of the sub-property provided
exact | 1..1 | boolean | | | Whether the operation is being used by a human, or a machine. If the operation is being used by a human, the terminology server can return a list of possible matches, with commentary. For a machine, the server returns sure matches, or none at all
compositional | 0..1 | boolean | | | Post-coordinated expressions are allowed to be returned in the matching codes (mainly for SNOMED CT). Default = false

Out Parameters:

Name | Cardinality | Type | Binding | Profile | Documentation
match | 0..* | | | | Concepts returned by the server as a result of the inferencing operation
match.code | 1..1 | Coding | | | A code that matches the properties provided
match.unmatched | 0..* | | | | One or more properties that contain properties that could not be matched into the code
match.unmatched.code | 1..1 | code | | | Identifies the property provided
match.unmatched.value | 1..1 | code | Coding | string | integer | boolean | dateTime | | | The value of the property provided
match.unmatched.property | 0..* | | | | Nested Properties (mainly used for SNOMED CT composition, for relationship Groups)
match.unmatched.property.code | 1..1 | code | | | Identifies the sub-property provided
match.unmatched.property.value | 1..1 | code | Coding | string | integer | boolean | dateTime | | | The value of the sub-property provided
match.comment | 0..1 | string | | | Information about the quality of the match, if operation is for a human

4.7.15.3.1 Examples

Request:

```
<Parameters xmlns="http://hl7.org/fhir">
  <parameter>
    <name value="system"/>
    <valueUri value="http://snomed.info/sct"/>
  </parameter>
  <parameter>
    <name value="exact"/>
    <valueBoolean value="true"/>
  </parameter>
  <parameter>
    <name value="property"/>
    <part>
      <name value="code"/>
      <valueCode value="focus"/>
    </part>
    <part>
      <name value="value"/>
      <!-- Measurement finding -->
      <valueCode value="118245000"/>
    </part>
  </parameter>
```

```
  <parameter>
    <name value="property"/>
    <part>
      <name value="code"/>
      <!-- Interprets -->
      <valueCode value="363714003"/>
    </part>
    <part>
      <name value="value"/>
      <!-- Bilirubin -->
      <valueCode value="302787001"/>
    </part>
  </parameter>
</Parameters>
```

SNOMED Composition - provide 2 properties, and ask for a single code for the whole (Response):

```
HTTP/1.1 200 OK
[other headers]

<Parameters xmlns="http://hl7.org/fhir">
    <parameter>
        <name value="match" />
        <part>
            <name value="code" />
            <valueCoding>
                <system value="http://snomed.info/sct" />
                <code value="365786009" />
                <display value="Bilirubin level - finding" />
            </valueCoding>
        </part>
    </parameter>
</Parameters>
```

4.8 Resource ValueSet - Content

URL: https://hl7.org/fhir/STU3/valueset.html

This page is part of the FHIR Specification (v3.0.2: STU 3). The current version which supercedes this version is 4.0.1. For a full list of available versions, see the Directory of published versions

Vocabulary Work Group | Maturity Level: 5 | Trial Use | Compartments: Not linked to any defined compartments

A value set specifies a set of codes drawn from one or more code systems.

4.8.1 Scope and Usage

The FHIR terminology specification is based on two key concepts, originally defined in HL7 v3 Core Principles :

* CodeSystem - defines a set of codes with meanings (also known as enumeration, terminology, classification, and/or ontology) - e.g. define which codes (symbols and/or expressions) exist, and how they are understood

* ValueSet - selects a set of codes from those defined by one or more code systems to specify which codes can be used in a particular context

Value sets have 2 aspects:

* .compose: A definition of which codes are intended to be in the value set ("intension")

* .expansion: The list of codes that are actually in the value set under a given set of conditions ("extension")

The ValueSet resource can carry either the .compose or the .expansion, or both. There is a "$expand" operation which can be used to ask a server to generate an expansion given the composition rules.

4.8.2 Boundaries and Relationships

* Value sets use CodeSystem resources by referring to them via their canonical URLs

* Value sets are used in ElementDefinition and Questionnaire resources to specify the allowable contents for coded elements

* Concept Maps describe mappings between value sets

* The ValueSet resource design is based on the functionality described in the OMG CTS 2 specification, along with metadata in the HL7 Value Set Definition specification. Value set resources can be converted to CTS2 value set and code system resources.

* The value set resource is aligned with the Value Set Definition (VSD) project. Not all of the elements defined by the VSD are part of the base resource - some are defined as part of the ValueSet Extensions. In the ValueSet resource, the compose element is the VSD "Content Logical definition".

4.8.3 Background and Context

When using value sets, proper differentiation between a code system and a value set is important. This is one very common area where significant clinical safety risks occur in practice. Implementers should be familiar with the content in Using Codes in resources.

4.8.3.1 ValueSet Identification

A value set has 3 identifiers:

* ValueSet.id: the logical id on the system that holds the value set - this changes as it moves from server to server (this id, with the server address prepended, is called the 'literal identity' of the resource)

* ValueSet.url: the canonical URL that never changes for this value set - it is the same in every copy. Ideally, the URL should also be the location of the master version of the value set, though this is not always possible

* ValueSet.identifier: A system/value pair that is used to identify the value set in other contexts (such as an OID in an HL7 v3 specification)

For further information regarding resource identification, see Resource Identity.

This means that each value set has 2 different URLs that can be used to reference it - its canonical url, and its local location from which it may be retrieved. Because it is common practice to copy (cache) value sets locally, most references to value sets use the canonical URL.

For example, the value sets published as part of FHIR all have a canonical URL which is also a location by which they may be accessed in the FHIR specification itself. Note, though, that while a new version of the FHIR Specification is being prepared, value sets that are published in the drafts will not be found in the published FHIR specification at their canonical URL.

Alternatively, the identifier and version elements may be used to reference this value set in a design, a profile, a CDA template or HL7 v3 message (in the CD data type valueSet and valueSetVersion properties). These different contexts may make additional restrictions on the possible values of these elements. The identifier is generally not needed when using value sets in a FHIR context, where the canonical URL is always the focus.

This resource is referenced by ConceptMap, OperationDefinition and Questionnaire

4.8.4 Resource Content

* Structure

* UML

* XML

* JSON

* Turtle

* R2 Diff

* All

Structure

Name | Flags | Card. | Type | Description & Constraints
ValueSet | I | | DomainResource | A set of codes drawn from one or more code systems + Value set SHALL contain at least one of a compose or an expansion element Elements defined in Ancestors: id, meta, implicitRules, language, text, contained, extension, modifierExtension
url | ? | 0..1 | uri | Logical URI to reference this value set (globally unique)
identifier | ? | 0..* | Identifier | Additional identifier for the value set
version | ? | 0..1 | string | Business version of the value set
name | ? | 0..1 | string | Name for this value set (computer friendly)
title | ? | 0..1 | string | Name for this value set (human friendly)
status | ?!? | 1..1 | code | draft | active | retired | unknown PublicationStatus (Required)
experimental | ?!? | 0..1 | boolean | For testing purposes, not real usage
date | ? | 0..1 | dateTime | Date this was last changed
publisher | ? | 0..1 | string | Name of the publisher (organization or individual)
contact | ? | 0..* | ContactDetail | Contact details for the publisher
description | | 0..1 | markdown | Natural language description of the value set
useContext | ? | 0..* | UsageContext | Context the content is intended to support
jurisdiction | ? | 0..* | CodeableConcept | Intended jurisdiction for value set (if applicable) Jurisdiction ValueSet (Extensible)
immutable | ? | 0..1 | boolean | Indicates whether or not any change to the content logical definition may occur
purpose | | 0..1 | markdown | Why this value set is defined
copyright | | 0..1 | markdown | Use and/or publishing restrictions
extensible | ? | 0..1 | boolean | Whether this is intended to be used with an extensible binding
compose | I | 0..1 | BackboneElement | Definition of the content of the value set (CLD)
lockedDate | ? | 0..1 | date | Fixed date for version-less references (transitive)
inactive | ? | 0..1 | boolean | Whether inactive codes are in the value set
include | ?I | 1..* | BackboneElement | Include one or more codes from a code system or other value set(s) + A value set with concepts or filters SHALL include a system + Cannot have both concept and filter + A value set include/exclude SHALL have a value set or a system
system | ?I | 0..1 | uri | The system the codes come from
version | ? | 0..1 | string | Specific version of the code system referred to
concept | I | 0..* | BackboneElement | A concept defined in the system
code | | 1..1 | code | Code or expression from system
display | | 0..1 | string | Text to display for this code for this value set in this valueset
designation | | 0..* | BackboneElement | Additional representations for this concept
language | | 0..1 | code | Human language of the designation Common Languages (Extensible but limited to All Languages)
use | | 0..1 | Coding | Details how this designation would be used Designation Use (Extensible)
value | | 1..1 | string | The text value for this designation
filter | ?!?I | 0..* | BackboneElement | Select codes/concepts by their properties (including relationships)
property | ? | 1..1 | code | A property defined by the code system

op | ? | 1..1 | code | = | is-a | descendent-of | is-not-a | regex | in | not-in | generalizes | exists FilterOperator (Required)
value | ? | 1..1 | code | Code from the system, or regex criteria, or boolean value for exists
valueSet | ?I | 0..* | uri | Select only contents included in this value set
exclude | I | 0..* | see include | Explicitly exclude codes from a code system or other value sets
expansion | I | 0..1 | BackboneElement | Used when the value set is "expanded"
identifier | | 1..1 | uri | Uniquely identifies this expansion
timestamp | | 1..1 | dateTime | Time ValueSet expansion happened
total | | 0..1 | integer | Total number of codes in the expansion
offset | | 0..1 | integer | Offset at which this resource starts
parameter | | 0..* | BackboneElement | Parameter that controlled the expansion process
name | | 1..1 | string | Name as assigned by the server
value[x] | | 0..1 | | Value of the named parameter
valueString | | | string
valueBoolean | | | boolean
valueInteger | | | integer
valueDecimal | | | decimal
valueUri | | | uri
valueCode | | | code
contains | I | 0..* | BackboneElement | Codes in the value set + SHALL have a code or a display + Must have a code if not abstract + Must have a system if a code is present
system | | 0..1 | uri | System value for the code
abstract | | 0..1 | boolean | If user cannot select this entry
inactive | | 0..1 | boolean | If concept is inactive in the code system
version | | 0..1 | string | Version in which this code/display is defined
code | I | 0..1 | code | Code - if blank, this is not a selectable code
display | I | 0..1 | string | User display for the concept
designation | | 0..* | see designation | Additional representations for this item
contains | | 0..* | see contains | Codes contained under this entry
Documentation for this format

UML Diagram (Legend)

XML Template

```
<ValueSet xmlns="http://hl7.org/fhir">
 <!-- from Resource: id, meta, implicitRules, and language -->
 <!-- from DomainResource: text, contained, extension, and modifierExtension -->
 <url value="[uri]"/><!-- 0..1 Logical URI to reference this value set (globally unique) -->
 <identifier><!-- 0..* Identifier Additional identifier for the value set --></identifier>
 <version value="[string]"/><!-- 0..1 Business version of the value set -->
 <name value="[string]"/><!-- 0..1 Name for this value set (computer friendly) -->
 <title value="[string]"/><!-- 0..1 Name for this value set (human friendly) -->
 <status value="[code]"/><!-- 1..1 draft | active | retired | unknown -->
 <experimental value="[boolean]"/><!-- 0..1 For testing purposes, not real usage -->
 <date value="[dateTime]"/><!-- 0..1 Date this was last changed -->
 <publisher value="[string]"/><!-- 0..1 Name of the publisher (organization or individual) -->
 <contact><!-- 0..* ContactDetail Contact details for the publisher --></contact>
 <description value="[markdown]"/><!-- 0..1 Natural language description of the value set -->
 <useContext><!-- 0..* UsageContext Context the content is intended to support --></useContext>
 <jurisdiction><!-- 0..* CodeableConcept Intended jurisdiction for value set (if applicable) --></jurisdiction>
 <immutable value="[boolean]"/><!-- 0..1 Indicates whether or not any change to the content logical definition may occur
     -->
 <purpose value="[markdown]"/><!-- 0..1 Why this value set is defined -->
 <copyright value="[markdown]"/><!-- 0..1 Use and/or publishing restrictions -->
 <extensible value="[boolean]"/><!-- 0..1 Whether this is intended to be used with an extensible binding -->
 <compose>  <!--  0..1 Definition of the content of the value set (CLD) -->
  <lockedDate value="[date]"/><!-- 0..1 Fixed date for version-less references (transitive) -->
  <inactive value="[boolean]"/><!-- 0..1 Whether inactive codes are in the value set -->
  <include>  <!-- 1..* Include one or more codes from a code system or other value set(s) -->
   <system value="[uri]"/><!--  0..1 The system the codes come from -->
   <version value="[string]"/><!-- 0..1 Specific version of the code system referred to -->
   <concept>  <!--  0..* A concept defined in the system -->
    <code value="[code]"/><!-- 1..1 Code or expression from system -->
    <display value="[string]"/><!-- 0..1 Text to display for this code for this value set in this valueset -->
    <designation>  <!-- 0..* Additional representations for this concept -->
     <language value="[code]"/><!-- 0..1 Human language of the designation -->
     <use><!-- 0..1 Coding Details how this designation would be used --></use>
     <value value="[string]"/><!-- 1..1 The text value for this designation -->
    </designation>
   </concept>
   <filter>  <!--  0..* Select codes/concepts by their properties (including relationships) -->
    <property value="[code]"/><!-- 1..1 A property defined by the code system -->
    <op value="[code]"/><!-- 1..1 = | is-a | descendent-of | is-not-a | regex | in | not-in | generalizes | exists -->
    <value value="[code]"/><!-- 1..1 Code from the system, or regex criteria, or boolean value for exists -->
   </filter>
   <valueSet value="[uri]"/><!--  0..* Select only contents included in this value set -->
  </include>
  <exclude><!--  0..* Content as for ValueSet.compose.include Explicitly exclude codes from a code system or other value
     sets --></exclude>
 </compose>
 <expansion>  <!--  0..1 Used when the value set is "expanded" -->
  <identifier value="[uri]"/><!-- 1..1 Uniquely identifies this expansion -->
  <timestamp value="[dateTime]"/><!-- 1..1 Time ValueSet expansion happened -->
  <total value="[integer]"/><!-- 0..1 Total number of codes in the expansion -->
```

```
  <offset value="[integer]"/><!-- 0..1 Offset at which this resource starts -->
  <parameter>  <!-- 0..* Parameter that controlled the expansion process -->
   <name value="[string]"/><!-- 1..1 Name as assigned by the server -->
   <value[x]><!-- 0..1 string|boolean|integer|decimal|uri|code Value of the named parameter --></value[x]>
  </parameter>
  <contains>  <!-- 0..* Codes in the value set -->
   <system value="[uri]"/><!-- 0..1 System value for the code -->
   <abstract value="[boolean]"/><!-- 0..1 If user cannot select this entry -->
   <inactive value="[boolean]"/><!-- 0..1 If concept is inactive in the code system -->
   <version value="[string]"/><!-- 0..1 Version in which this code/display is defined -->
   <code value="[code]"/><!--  0..1 Code - if blank, this is not a selectable code -->
   <display value="[string]"/><!--  0..1 User display for the concept -->
   <designation><!-- 0..* Content as for ValueSet.compose.include.concept.designation Additional representations for
    this item --></designation>
   <contains><!-- 0..* Content as for ValueSet.expansion.contains Codes contained under this entry --></contains>
  </contains>
 </expansion>
</ValueSet>
```

JSON Template

```
{
  "resourceType" : "ValueSet",
  // from Resource: id, meta, implicitRules, and language
  // from DomainResource: text, contained, extension, and modifierExtension
  "url" : "<uri>", // Logical URI to reference this value set (globally unique)
  "identifier" : [{ Identifier }], // Additional identifier for the value set
  "version" : "<string>", // Business version of the value set
  "name" : "<string>", // Name for this value set (computer friendly)
  "title" : "<string>", // Name for this value set (human friendly)
  "status" : "<code>", // R!  draft | active | retired | unknown
  "experimental" : <boolean>, // For testing purposes, not real usage
  "date" : "<dateTime>", // Date this was last changed
  "publisher" : "<string>", // Name of the publisher (organization or individual)
  "contact" : [{ ContactDetail }], // Contact details for the publisher
  "description" : "<markdown>", // Natural language description of the value set
  "useContext" : [{ UsageContext }], // Context the content is intended to support
  "jurisdiction" : [{ CodeableConcept }], // Intended jurisdiction for value set (if applicable)
  "immutable" : <boolean>, // Indicates whether or not any change to the content logical definition may occur
  "purpose" : "<markdown>", // Why this value set is defined
  "copyright" : "<markdown>", // Use and/or publishing restrictions
  "extensible" : <boolean>, // Whether this is intended to be used with an extensible binding
  "compose" : { // C? Definition of the content of the value set (CLD)
    "lockedDate" : "<date>", // Fixed date for version-less references (transitive)
    "inactive" : <boolean>, // Whether inactive codes are in the value set
    "include" : [{ // R!  Include one or more codes from a code system or other value set(s)
      "system" : "<uri>", // C? The system the codes come from
      "version" : "<string>", // Specific version of the code system referred to
      "concept" : [{ // C? A concept defined in the system
        "code" : "<code>", // R!  Code or expression from system
        "display" : "<string>", // Text to display for this code for this value set in this valueset
        "designation" : [{ // Additional representations for this concept
          "language" : "<code>", // Human language of the designation
          "use" : { Coding }, // Details how this designation would be used
          "value" : "<string>" // R!  The text value for this designation
        }]
      }],
      "filter" : [{ // C? Select codes/concepts by their properties (including relationships)
        "property" : "<code>", // R!  A property defined by the code system
        "op" : "<code>", // R!  = | is-a | descendent-of | is-not-a | regex | in | not-in | generalizes | exists
        "value" : "<code>" // R!  Code from the system, or regex criteria, or boolean value for exists
      }],
      "valueSet" : ["<uri>"] // C? Select only contents included in this value set
    }],
    "exclude" : [{ Content as for ValueSet.compose.include }] // C? Explicitly exclude codes from a code system or other
     value sets
  },
  "expansion" : { // C? Used when the value set is "expanded"
    "identifier" : "<uri>", // R!  Uniquely identifies this expansion
    "timestamp" : "<dateTime>", // R!  Time ValueSet expansion happened
    "total" : <integer>, // Total number of codes in the expansion
    "offset" : <integer>, // Offset at which this resource starts
    "parameter" : [{ // Parameter that controlled the expansion process
      "name" : "<string>", // R!  Name as assigned by the server
      // value[x]: Value of the named parameter. One of these 6:
      "valueString" : "<string>"
      "valueBoolean" : <boolean>
      "valueInteger" : <integer>
      "valueDecimal" : <decimal>
      "valueUri" : "<uri>"
      "valueCode" : "<code>"
    }],
    "contains" : [{ // Codes in the value set
      "system" : "<uri>", // System value for the code
      "abstract" : <boolean>, // If user cannot select this entry
      "inactive" : <boolean>, // If concept is inactive in the code system
      "version" : "<string>", // Version in which this code/display is defined
      "code" : "<code>", // C? Code - if blank, this is not a selectable code
      "display" : "<string>", // C? User display for the concept
      "designation" : [{ Content as for ValueSet.compose.include.concept.designation }], // Additional representations
```

```
    for this item
      "contains" : [{ Content as for ValueSet.expansion.contains }] // Codes contained under this entry
    }]
  }
}
```

Turtle Template

```
@prefix fhir: <http://hl7.org/fhir/> .


[ a fhir:ValueSet;
  fhir:nodeRole fhir:treeRoot; # if this is the parser root

  # from Resource: .id, .meta, .implicitRules, and .language
  # from DomainResource: .text, .contained, .extension, and .modifierExtension
  fhir:ValueSet.url [ uri ]; # 0..1 Logical URI to reference this value set (globally unique)
  fhir:ValueSet.identifier [ Identifier ], ... ; # 0..* Additional identifier for the value set
  fhir:ValueSet.version [ string ]; # 0..1 Business version of the value set
  fhir:ValueSet.name [ string ]; # 0..1 Name for this value set (computer friendly)
  fhir:ValueSet.title [ string ]; # 0..1 Name for this value set (human friendly)
  fhir:ValueSet.status [ code ]; # 1..1 draft | active | retired | unknown
  fhir:ValueSet.experimental [ boolean ]; # 0..1 For testing purposes, not real usage
  fhir:ValueSet.date [ dateTime ]; # 0..1 Date this was last changed
  fhir:ValueSet.publisher [ string ]; # 0..1 Name of the publisher (organization or individual)
  fhir:ValueSet.contact [ ContactDetail ], ... ; # 0..* Contact details for the publisher
  fhir:ValueSet.description [ markdown ]; # 0..1 Natural language description of the value set
  fhir:ValueSet.useContext [ UsageContext ], ... ; # 0..* Context the content is intended to support
  fhir:ValueSet.jurisdiction [ CodeableConcept ], ... ; # 0..* Intended jurisdiction for value set (if applicable)
  fhir:ValueSet.immutable [ boolean ]; # 0..1 Indicates whether or not any change to the content logical definition may
    occur
  fhir:ValueSet.purpose [ markdown ]; # 0..1 Why this value set is defined
  fhir:ValueSet.copyright [ markdown ]; # 0..1 Use and/or publishing restrictions
  fhir:ValueSet.extensible [ boolean ]; # 0..1 Whether this is intended to be used with an extensible binding
  fhir:ValueSet.compose [ # 0..1 Definition of the content of the value set (CLD)
    fhir:ValueSet.compose.lockedDate [ date ]; # 0..1 Fixed date for version-less references (transitive)
    fhir:ValueSet.compose.inactive [ boolean ]; # 0..1 Whether inactive codes are in the value set
    fhir:ValueSet.compose.include [ # 1..* Include one or more codes from a code system or other value set(s)
      fhir:ValueSet.compose.include.system [ uri ]; # 0..1 The system the codes come from
      fhir:ValueSet.compose.include.version [ string ]; # 0..1 Specific version of the code system referred to
      fhir:ValueSet.compose.include.concept [ # 0..* A concept defined in the system
        fhir:ValueSet.compose.include.concept.code [ code ]; # 1..1 Code or expression from system
        fhir:ValueSet.compose.include.concept.display [ string ]; # 0..1 Text to display for this code for this value
    set in this valueset
        fhir:ValueSet.compose.include.concept.designation [ # 0..* Additional representations for this concept
          fhir:ValueSet.compose.include.concept.designation.language [ code ]; # 0..1 Human language of the designation
          fhir:ValueSet.compose.include.concept.designation.use [ Coding ]; # 0..1 Details how this designation would be
     used
          fhir:ValueSet.compose.include.concept.designation.value [ string ]; # 1..1 The text value for this designation
        ], ...;
      ], ...;
      fhir:ValueSet.compose.include.filter [ # 0..* Select codes/concepts by their properties (including relationships)
        fhir:ValueSet.compose.include.filter.property [ code ]; # 1..1 A property defined by the code system
        fhir:ValueSet.compose.include.filter.op [ code ]; # 1..1 = | is-a | descendent-of | is-not-a | regex | in | not-
    in | generalizes | exists
        fhir:ValueSet.compose.include.filter.value [ code ]; # 1..1 Code from the system, or regex criteria, or boolean
    value for exists
      ], ...;
      fhir:ValueSet.compose.include.valueSet [ uri ], ... ; # 0..* Select only contents included in this value set
    ], ...;
    fhir:ValueSet.compose.exclude [ See ValueSet.compose.include ], ... ; # 0..* Explicitly exclude codes from a code
    system or other value sets
  ];
  fhir:ValueSet.expansion [ # 0..1 Used when the value set is "expanded"
    fhir:ValueSet.expansion.identifier [ uri ]; # 1..1 Uniquely identifies this expansion
    fhir:ValueSet.expansion.timestamp [ dateTime ]; # 1..1 Time ValueSet expansion happened
    fhir:ValueSet.expansion.total [ integer ]; # 0..1 Total number of codes in the expansion
    fhir:ValueSet.expansion.offset [ integer ]; # 0..1 Offset at which this resource starts
    fhir:ValueSet.expansion.parameter [ # 0..* Parameter that controlled the expansion process
      fhir:ValueSet.expansion.parameter.name [ string ]; # 1..1 Name as assigned by the server
      # ValueSet.expansion.parameter.value[x] : 0..1 Value of the named parameter. One of these 6
        fhir:ValueSet.expansion.parameter.valueString [ string ]
        fhir:ValueSet.expansion.parameter.valueBoolean [ boolean ]
        fhir:ValueSet.expansion.parameter.valueInteger [ integer ]
        fhir:ValueSet.expansion.parameter.valueDecimal [ decimal ]
        fhir:ValueSet.expansion.parameter.valueUri [ uri ]
        fhir:ValueSet.expansion.parameter.valueCode [ code ]
    ], ...;
    fhir:ValueSet.expansion.contains [ # 0..* Codes in the value set
      fhir:ValueSet.expansion.contains.system [ uri ]; # 0..1 System value for the code
      fhir:ValueSet.expansion.contains.abstract [ boolean ]; # 0..1 If user cannot select this entry
      fhir:ValueSet.expansion.contains.inactive [ boolean ]; # 0..1 If concept is inactive in the code system
      fhir:ValueSet.expansion.contains.version [ string ]; # 0..1 Version in which this code/display is defined
      fhir:ValueSet.expansion.contains.code [ code ]; # 0..1 Code - if blank, this is not a selectable code
      fhir:ValueSet.expansion.contains.display [ string ]; # 0..1 User display for the concept
      fhir:ValueSet.expansion.contains.designation [ See ValueSet.compose.include.concept.designation ], ... ; # 0..*
    Additional representations for this item
      fhir:ValueSet.expansion.contains.contains [ See ValueSet.expansion.contains ], ... ; # 0..* Codes contained under
    this entry
    ], ...;
```

```
  ];
]
```

Changes since DSTU2

ValueSet
ValueSet.identifier | Max Cardinality changed from 1 to *
ValueSet.title | Added Element
ValueSet.status | Change value set from http://hl7.org/fhir/ValueSet/conformance-resource-status to http://hl7.org/fhir/ValueSet/publication-status
ValueSet.experimental | Now marked as Modifier
ValueSet.contact | Type changed from BackboneElement to ContactDetail
ValueSet.description | Type changed from string to markdown
ValueSet.useContext | Type changed from CodeableConcept to UsageContext Remove Binding http://hl7.org/fhir/ValueSet/use-context (extensible)
ValueSet.jurisdiction | Added Element
ValueSet.purpose | Renamed from requirements to purpose Type changed from string to markdown
ValueSet.copyright | Type changed from string to markdown
ValueSet.compose.lockedDate | Added Element
ValueSet.compose.inactive | Added Element
ValueSet.compose.include | Min Cardinality changed from 0 to 1
ValueSet.compose.include.system | Min Cardinality changed from 1 to 0
ValueSet.compose.include.concept.designation.language | Added Element
ValueSet.compose.include.concept.designation.use | Added Element
ValueSet.compose.include.concept.designation.value | Added Element
ValueSet.compose.include.filter | Now marked as Modifier
ValueSet.compose.include.valueSet | Added Element
ValueSet.expansion.contains.abstract | Default Value "false" added
ValueSet.expansion.contains.inactive | Added Element
ValueSet.expansion.contains.designation | Added Element
ValueSet.contact.name | deleted
ValueSet.contact.telecom | deleted
ValueSet.lockedDate | deleted
ValueSet.codeSystem | deleted
ValueSet.compose.import | deleted

See the Full Difference for further information

This analysis is available as XML or JSON.

See R2 <--> R3 Conversion Maps (status = 11 tests that all execute ok. 5 fail round-trip testing and 4 r3 resources are invalid (4 errors).).

Structure

Name | Flags | Card. | Type | Description & Constraints
ValueSet | I | | DomainResource | A set of codes drawn from one or more code systems + Value set SHALL contain at least one of a compose or an expansion element Elements defined in Ancestors: id, meta, implicitRules, language, text, contained, extension, modifierExtension
url | ? | 0..1 | uri | Logical URI to reference this value set (globally unique)
identifier | ? | 0..* | Identifier | Additional identifier for the value set
version | ? | 0..1 | string | Business version of the value set
name | ? | 0..1 | string | Name for this value set (computer friendly)
title | ? | 0..1 | string | Name for this value set (human friendly)
status | ?!? | 1..1 | code | draft | active | retired | unknown PublicationStatus (Required)
experimental | ?!? | 0..1 | boolean | For testing purposes, not real usage
date | ? | 0..1 | dateTime | Date this was last changed
publisher | ? | 0..1 | string | Name of the publisher (organization or individual)
contact | ? | 0..* | ContactDetail | Contact details for the publisher
description | | 0..1 | markdown | Natural language description of the value set
useContext | ? | 0..* | UsageContext | Context the content is intended to support
jurisdiction | ? | 0..* | CodeableConcept | Intended jurisdiction for value set (if applicable) Jurisdiction ValueSet (Extensible)
immutable | ? | 0..1 | boolean | Indicates whether or not any change to the content logical definition may occur
purpose | | 0..1 | markdown | Why this value set is defined
copyright | | 0..1 | markdown | Use and/or publishing restrictions
extensible | ? | 0..1 | boolean | Whether this is intended to be used with an extensible binding
compose | I | 0..1 | BackboneElement | Definition of the content of the value set (CLD)
lockedDate | ? | 0..1 | date | Fixed date for version-less references (transitive)
inactive | ? | 0..1 | boolean | Whether inactive codes are in the value set
include | ?I | 1..* | BackboneElement | Include one or more codes from a code system or other value set(s) + A value set with concepts or filters SHALL include a system + Cannot have both concept and filter + A value set include/exclude SHALL have a value set or a system
system | ?I | 0..1 | uri | The system the codes come from
version | ? | 0..1 | string | Specific version of the code system referred to
concept | I | 0..* | BackboneElement | A concept defined in the system
code | | 1..1 | code | Code or expression from system
display | | 0..1 | string | Text to display for this code for this value set in this valueset
designation | | 0..* | BackboneElement | Additional representations for this concept
language | | 0..1 | code | Human language of the designation Common Languages (Extensible but limited to All Languages)
use | | 0..1 | Coding | Details how this designation would be used Designation Use (Extensible)
value | | 1..1 | string | The text value for this designation

filter | ?!?I | 0..* | BackboneElement | Select codes/concepts by their properties (including relationships)
property | ? | 1..1 | code | A property defined by the code system
op | ? | 1..1 | code | = | is-a | descendent-of | is-not-a | regex | in | not-in | generalizes | exists FilterOperator (Required)
value | ? | 1..1 | code | Code from the system, or regex criteria, or boolean value for exists
valueSet | ?I | 0..* | uri | Select only contents included in this value set
exclude | I | 0..* | see include | Explicitly exclude codes from a code system or other value sets
expansion | I | 0..1 | BackboneElement | Used when the value set is "expanded"
identifier | | 1..1 | uri | Uniquely identifies this expansion
timestamp | | 1..1 | dateTime | Time ValueSet expansion happened
total | | 0..1 | integer | Total number of codes in the expansion
offset | | 0..1 | integer | Offset at which this resource starts
parameter | | 0..* | BackboneElement | Parameter that controlled the expansion process
name | | 1..1 | string | Name as assigned by the server
value[x] | | 0..1 | | Value of the named parameter
valueString | | | string
valueBoolean | | | boolean
valueInteger | | | integer
valueDecimal | | | decimal
valueUri | | | uri
valueCode | | | code
contains | I | 0..* | BackboneElement | Codes in the value set + SHALL have a code or a display + Must have a code if not abstract + Must have a system if a code is present
system | | 0..1 | uri | System value for the code
abstract | | 0..1 | boolean | If user cannot select this entry
inactive | | 0..1 | boolean | If concept is inactive in the code system
version | | 0..1 | string | Version in which this code/display is defined
code | I | 0..1 | code | Code - if blank, this is not a selectable code
display | I | 0..1 | string | User display for the concept
designation | | 0..* | see designation | Additional representations for this item
contains | | 0..* | see contains | Codes contained under this entry
Documentation for this format

UML Diagram (Legend)

XML Template

```
<ValueSet xmlns="http://hl7.org/fhir">
 <!-- from Resource: id, meta, implicitRules, and language -->
 <!-- from DomainResource: text, contained, extension, and modifierExtension -->
 <url value="[uri]"/><!-- 0..1 Logical URI to reference this value set (globally unique) -->
 <identifier><!-- 0..* Identifier Additional identifier for the value set --></identifier>
 <version value="[string]"/><!-- 0..1 Business version of the value set -->
 <name value="[string]"/><!-- 0..1 Name for this value set (computer friendly) -->
 <title value="[string]"/><!-- 0..1 Name for this value set (human friendly) -->
 <status value="[code]"/><!-- 1..1 draft | active | retired | unknown -->
 <experimental value="[boolean]"/><!-- 0..1 For testing purposes, not real usage -->
 <date value="[dateTime]"/><!-- 0..1 Date this was last changed -->
 <publisher value="[string]"/><!-- 0..1 Name of the publisher (organization or individual) -->
 <contact><!-- 0..* ContactDetail Contact details for the publisher --></contact>
 <description value="[markdown]"/><!-- 0..1 Natural language description of the value set -->
 <useContext><!-- 0..* UsageContext Context the content is intended to support --></useContext>
 <jurisdiction><!-- 0..* CodeableConcept Intended jurisdiction for value set (if applicable) --></jurisdiction>
 <immutable value="[boolean]"/><!-- 0..1 Indicates whether or not any change to the content logical definition may occur
     -->
 <purpose value="[markdown]"/><!-- 0..1 Why this value set is defined -->
 <copyright value="[markdown]"/><!-- 0..1 Use and/or publishing restrictions -->
 <extensible value="[boolean]"/><!-- 0..1 Whether this is intended to be used with an extensible binding -->
 <compose>  <!--  0..1 Definition of the content of the value set (CLD) -->
  <lockedDate value="[date]"/><!-- 0..1 Fixed date for version-less references (transitive) -->
  <inactive value="[boolean]"/><!-- 0..1 Whether inactive codes are in the value set -->
  <include>  <!-- 1..* Include one or more codes from a code system or other value set(s) -->
   <system value="[uri]"/><!--  0..1 The system the codes come from -->
   <version value="[string]"/><!-- 0..1 Specific version of the code system referred to -->
   <concept>  <!--  0..* A concept defined in the system -->
    <code value="[code]"/><!-- 1..1 Code or expression from system -->
    <display value="[string]"/><!-- 0..1 Text to display for this code for this value set in this valueset -->
    <designation>  <!-- 0..* Additional representations for this concept -->
     <language value="[code]"/><!-- 0..1 Human language of the designation -->
     <use><!-- 0..1 Coding Details how this designation would be used --></use>
     <value value="[string]"/><!-- 1..1 The text value for this designation -->
    </designation>
   </concept>
   <filter>  <!--  0..* Select codes/concepts by their properties (including relationships) -->
    <property value="[code]"/><!-- 1..1 A property defined by the code system -->
    <op value="[code]"/><!-- 1..1 = | is-a | descendent-of | is-not-a | regex | in | not-in | generalizes | exists -->
    <value value="[code]"/><!-- 1..1 Code from the system, or regex criteria, or boolean value for exists -->
   </filter>
   <valueSet value="[uri]"/><!--  0..* Select only contents included in this value set -->
  </include>
  <exclude><!--  0..* Content as for ValueSet.compose.include Explicitly exclude codes from a code system or other value
     sets --></exclude>
 </compose>
 <expansion>  <!--  0..1 Used when the value set is "expanded" -->
```

```
  <identifier value="[uri]"/><!-- 1..1 Uniquely identifies this expansion -->
  <timestamp value="[dateTime]"/><!-- 1..1 Time ValueSet expansion happened -->
  <total value="[integer]"/><!-- 0..1 Total number of codes in the expansion -->
  <offset value="[integer]"/><!-- 0..1 Offset at which this resource starts -->
  <parameter>  <!-- 0..* Parameter that controlled the expansion process -->
   <name value="[string]"/><!-- 1..1 Name as assigned by the server -->
   <value[x]><!-- 0..1 string|boolean|integer|decimal|uri|code Value of the named parameter --></value[x]>
  </parameter>
  <contains>  <!-- 0..* Codes in the value set -->
   <system value="[uri]"/><!-- 0..1 System value for the code -->
   <abstract value="[boolean]"/><!-- 0..1 If user cannot select this entry -->
   <inactive value="[boolean]"/><!-- 0..1 If concept is inactive in the code system -->
   <version value="[string]"/><!-- 0..1 Version in which this code/display is defined -->
   <code value="[code]"/><!--  0..1 Code - if blank, this is not a selectable code -->
   <display value="[string]"/><!--  0..1 User display for the concept -->
   <designation><!-- 0..* Content as for ValueSet.compose.include.concept.designation Additional representations for
    this item --></designation>
   <contains><!-- 0..* Content as for ValueSet.expansion.contains Codes contained under this entry --></contains>
  </contains>
 </expansion>
</ValueSet>
```

JSON Template

```
{
  "resourceType" : "ValueSet",
  // from Resource: id, meta, implicitRules, and language
  // from DomainResource: text, contained, extension, and modifierExtension
  "url" : "<uri>", // Logical URI to reference this value set (globally unique)
  "identifier" : [{ Identifier }], // Additional identifier for the value set
  "version" : "<string>", // Business version of the value set
  "name" : "<string>", // Name for this value set (computer friendly)
  "title" : "<string>", // Name for this value set (human friendly)
  "status" : "<code>", // R!  draft | active | retired | unknown
  "experimental" : <boolean>, // For testing purposes, not real usage
  "date" : "<dateTime>", // Date this was last changed
  "publisher" : "<string>", // Name of the publisher (organization or individual)
  "contact" : [{ ContactDetail }], // Contact details for the publisher
  "description" : "<markdown>", // Natural language description of the value set
  "useContext" : [{ UsageContext }], // Context the content is intended to support
  "jurisdiction" : [{ CodeableConcept }], // Intended jurisdiction for value set (if applicable)
  "immutable" : <boolean>, // Indicates whether or not any change to the content logical definition may occur
  "purpose" : "<markdown>", // Why this value set is defined
  "copyright" : "<markdown>", // Use and/or publishing restrictions
  "extensible" : <boolean>, // Whether this is intended to be used with an extensible binding
  "compose" : { // C? Definition of the content of the value set (CLD)
    "lockedDate" : "<date>", // Fixed date for version-less references (transitive)
    "inactive" : <boolean>, // Whether inactive codes are in the value set
    "include" : [{ // R!  Include one or more codes from a code system or other value set(s)
      "system" : "<uri>", // C? The system the codes come from
      "version" : "<string>", // Specific version of the code system referred to
      "concept" : [{ // C? A concept defined in the system
        "code" : "<code>", // R!  Code or expression from system
        "display" : "<string>", // Text to display for this code for this value set in this valueset
        "designation" : [{ // Additional representations for this concept
          "language" : "<code>", // Human language of the designation
          "use" : { Coding }, // Details how this designation would be used
          "value" : "<string>" // R!  The text value for this designation
        }]
      }],
      "filter" : [{ // C? Select codes/concepts by their properties (including relationships)
        "property" : "<code>", // R!  A property defined by the code system
        "op" : "<code>", // R!  = | is-a | descendent-of | is-not-a | regex | in | not-in | generalizes | exists
        "value" : "<code>" // R!  Code from the system, or regex criteria, or boolean value for exists
      }],
      "valueSet" : ["<uri>"] // C? Select only contents included in this value set
    }],
    "exclude" : [{ Content as for ValueSet.compose.include }] // C? Explicitly exclude codes from a code system or other
     value sets
  },
  "expansion" : { // C? Used when the value set is "expanded"
    "identifier" : "<uri>", // R!  Uniquely identifies this expansion
    "timestamp" : "<dateTime>", // R!  Time ValueSet expansion happened
    "total" : <integer>, // Total number of codes in the expansion
    "offset" : <integer>, // Offset at which this resource starts
    "parameter" : [{ // Parameter that controlled the expansion process
      "name" : "<string>", // R!  Name as assigned by the server
      // value[x]: Value of the named parameter. One of these 6:
      "valueString" : "<string>"
      "valueBoolean" : <boolean>
      "valueInteger" : <integer>
      "valueDecimal" : <decimal>
      "valueUri" : "<uri>"
      "valueCode" : "<code>"
    }],
    "contains" : [{ // Codes in the value set
      "system" : "<uri>", // System value for the code
      "abstract" : <boolean>, // If user cannot select this entry
      "inactive" : <boolean>, // If concept is inactive in the code system
      "version" : "<string>", // Version in which this code/display is defined
```

```
      "code" : "<code>", // C? Code - if blank, this is not a selectable code
      "display" : "<string>", // C? User display for the concept
      "designation" : [{ Content as for ValueSet.compose.include.concept.designation }], // Additional representations
    for this item
      "contains" : [{ Content as for ValueSet.expansion.contains }] // Codes contained under this entry
    }]
  }
}
```

Turtle Template

```
@prefix fhir: <http://hl7.org/fhir/> .


[ a fhir:ValueSet;
  fhir:nodeRole fhir:treeRoot; # if this is the parser root

  # from Resource: .id, .meta, .implicitRules, and .language
  # from DomainResource: .text, .contained, .extension, and .modifierExtension
  fhir:ValueSet.url [ uri ]; # 0..1 Logical URI to reference this value set (globally unique)
  fhir:ValueSet.identifier [ Identifier ], ... ; # 0..* Additional identifier for the value set
  fhir:ValueSet.version [ string ]; # 0..1 Business version of the value set
  fhir:ValueSet.name [ string ]; # 0..1 Name for this value set (computer friendly)
  fhir:ValueSet.title [ string ]; # 0..1 Name for this value set (human friendly)
  fhir:ValueSet.status [ code ]; # 1..1 draft | active | retired | unknown
  fhir:ValueSet.experimental [ boolean ]; # 0..1 For testing purposes, not real usage
  fhir:ValueSet.date [ dateTime ]; # 0..1 Date this was last changed
  fhir:ValueSet.publisher [ string ]; # 0..1 Name of the publisher (organization or individual)
  fhir:ValueSet.contact [ ContactDetail ], ... ; # 0..* Contact details for the publisher
  fhir:ValueSet.description [ markdown ]; # 0..1 Natural language description of the value set
  fhir:ValueSet.useContext [ UsageContext ], ... ; # 0..* Context the content is intended to support
  fhir:ValueSet.jurisdiction [ CodeableConcept ], ... ; # 0..* Intended jurisdiction for value set (if applicable)
  fhir:ValueSet.immutable [ boolean ]; # 0..1 Indicates whether or not any change to the content logical definition may
    occur
  fhir:ValueSet.purpose [ markdown ]; # 0..1 Why this value set is defined
  fhir:ValueSet.copyright [ markdown ]; # 0..1 Use and/or publishing restrictions
  fhir:ValueSet.extensible [ boolean ]; # 0..1 Whether this is intended to be used with an extensible binding
  fhir:ValueSet.compose [ # 0..1 Definition of the content of the value set (CLD)
    fhir:ValueSet.compose.lockedDate [ date ]; # 0..1 Fixed date for version-less references (transitive)
    fhir:ValueSet.compose.inactive [ boolean ]; # 0..1 Whether inactive codes are in the value set
    fhir:ValueSet.compose.include [ # 1..* Include one or more codes from a code system or other value set(s)
      fhir:ValueSet.compose.include.system [ uri ]; # 0..1 The system the codes come from
      fhir:ValueSet.compose.include.version [ string ]; # 0..1 Specific version of the code system referred to
      fhir:ValueSet.compose.include.concept [ # 0..* A concept defined in the system
        fhir:ValueSet.compose.include.concept.code [ code ]; # 1..1 Code or expression from system
        fhir:ValueSet.compose.include.concept.display [ string ]; # 0..1 Text to display for this code for this value
    set in this valueset
        fhir:ValueSet.compose.include.concept.designation [ # 0..* Additional representations for this concept
          fhir:ValueSet.compose.include.concept.designation.language [ code ]; # 0..1 Human language of the designation
          fhir:ValueSet.compose.include.concept.designation.use [ Coding ]; # 0..1 Details how this designation would be
     used
          fhir:ValueSet.compose.include.concept.designation.value [ string ]; # 1..1 The text value for this designation
        ], ...;
      ], ...;
      fhir:ValueSet.compose.include.filter [ # 0..* Select codes/concepts by their properties (including relationships)
        fhir:ValueSet.compose.include.filter.property [ code ]; # 1..1 A property defined by the code system
        fhir:ValueSet.compose.include.filter.op [ code ]; # 1..1 = | is-a | descendent-of | is-not-a | regex | in | not-
    in | generalizes | exists
        fhir:ValueSet.compose.include.filter.value [ code ]; # 1..1 Code from the system, or regex criteria, or boolean
    value for exists
      ], ...;
      fhir:ValueSet.compose.include.valueSet [ uri ], ... ; # 0..* Select only contents included in this value set
    ], ...;
    fhir:ValueSet.compose.exclude [ See ValueSet.compose.include ], ... ; # 0..* Explicitly exclude codes from a code
    system or other value sets
  ];
  fhir:ValueSet.expansion [ # 0..1 Used when the value set is "expanded"
    fhir:ValueSet.expansion.identifier [ uri ]; # 1..1 Uniquely identifies this expansion
    fhir:ValueSet.expansion.timestamp [ dateTime ]; # 1..1 Time ValueSet expansion happened
    fhir:ValueSet.expansion.total [ integer ]; # 0..1 Total number of codes in the expansion
    fhir:ValueSet.expansion.offset [ integer ]; # 0..1 Offset at which this resource starts
    fhir:ValueSet.expansion.parameter [ # 0..* Parameter that controlled the expansion process
      fhir:ValueSet.expansion.parameter.name [ string ]; # 1..1 Name as assigned by the server
      # ValueSet.expansion.parameter.value[x] : 0..1 Value of the named parameter. One of these 6
        fhir:ValueSet.expansion.parameter.valueString [ string ]
        fhir:ValueSet.expansion.parameter.valueBoolean [ boolean ]
        fhir:ValueSet.expansion.parameter.valueInteger [ integer ]
        fhir:ValueSet.expansion.parameter.valueDecimal [ decimal ]
        fhir:ValueSet.expansion.parameter.valueUri [ uri ]
        fhir:ValueSet.expansion.parameter.valueCode [ code ]
    ], ...;
    fhir:ValueSet.expansion.contains [ # 0..* Codes in the value set
      fhir:ValueSet.expansion.contains.system [ uri ]; # 0..1 System value for the code
      fhir:ValueSet.expansion.contains.abstract [ boolean ]; # 0..1 If user cannot select this entry
      fhir:ValueSet.expansion.contains.inactive [ boolean ]; # 0..1 If concept is inactive in the code system
      fhir:ValueSet.expansion.contains.version [ string ]; # 0..1 Version in which this code/display is defined
      fhir:ValueSet.expansion.contains.code [ code ]; # 0..1 Code - if blank, this is not a selectable code
      fhir:ValueSet.expansion.contains.display [ string ]; # 0..1 User display for the concept
      fhir:ValueSet.expansion.contains.designation [ See ValueSet.compose.include.concept.designation ], ... ; # 0..*
    Additional representations for this item
```

```
      fhir:ValueSet.expansion.contains.contains [ See ValueSet.expansion.contains ], ... ; # 0..* Codes contained under
    this entry
    ], ...;
  ];
]
```

Changes since DSTU2

ValueSet
ValueSet.identifier | Max Cardinality changed from 1 to *
ValueSet.title | Added Element
ValueSet.status | Change value set from http://hl7.org/fhir/ValueSet/conformance-resource-status to http://hl7.org/fhir/ValueSet/publication-status
ValueSet.experimental | Now marked as Modifier
ValueSet.contact | Type changed from BackboneElement to ContactDetail
ValueSet.description | Type changed from string to markdown
ValueSet.useContext | Type changed from CodeableConcept to UsageContext Remove Binding http://hl7.org/fhir/ValueSet/use-context (extensible)
ValueSet.jurisdiction | Added Element
ValueSet.purpose | Renamed from requirements to purpose Type changed from string to markdown
ValueSet.copyright | Type changed from string to markdown
ValueSet.compose.lockedDate | Added Element
ValueSet.compose.inactive | Added Element
ValueSet.compose.include | Min Cardinality changed from 0 to 1
ValueSet.compose.include.system | Min Cardinality changed from 1 to 0
ValueSet.compose.include.concept.designation.language | Added Element
ValueSet.compose.include.concept.designation.use | Added Element
ValueSet.compose.include.concept.designation.value | Added Element
ValueSet.compose.include.filter | Now marked as Modifier
ValueSet.compose.include.valueSet | Added Element
ValueSet.expansion.contains.abstract | Default Value "false" added
ValueSet.expansion.contains.inactive | Added Element
ValueSet.expansion.contains.designation | Added Element
ValueSet.contact.name | deleted
ValueSet.contact.telecom | deleted
ValueSet.lockedDate | deleted
ValueSet.codeSystem | deleted
ValueSet.compose.import | deleted

See the Full Difference for further information

This analysis is available as XML or JSON.

See R2 <--> R3 Conversion Maps (status = 11 tests that all execute ok. 5 fail round-trip testing and 4 r3 resources are invalid (4 errors).).

Alternate definitions: Master Definition (XML, JSON), XML Schema/Schematron (for) + JSON Schema, ShEx (for Turtle)

4.8.4.1 Terminology Bindings

Path | Definition | Type | Reference
ValueSet.status | The lifecycle status of a Value Set or Concept Map. | Required | PublicationStatus
ValueSet.jurisdiction | Countries and regions within which this artifact is targeted for use | Extensible | Jurisdiction ValueSet
ValueSet.compose.include.concept.designation.language | A human language. | Extensible, but limited to All Languages | Common Languages
ValueSet.compose.include.concept.designation.use | Details of how a designation would be used. | Extensible | Designation Use
ValueSet.compose.include.filter.op | The kind of operation to perform as a part of a property based filter. | Required | FilterOperator

4.8.4.2 Constraints

* vsd-1: On ValueSet.compose.include: A value set include/exclude SHALL have a value set or a system (expression on ValueSet.compose.include: valueSet.exists() or system.exists())

* vsd-10: On ValueSet.expansion.contains: Must have a system if a code is present (expression on ValueSet.expansion.contains: code.empty() or system.exists())

* vsd-2: On ValueSet.compose.include: A value set with concepts or filters SHALL include a system (expression on ValueSet.compose.include: (concept.exists() or filter.exists()) implies system.exists())

* vsd-3: On ValueSet.compose.include: Cannot have both concept and filter (expression on ValueSet.compose.include: concept.empty() or filter.empty())

* vsd-5: Value set SHALL contain at least one of a compose or an expansion element (expression : compose.exists() or expansion.exists())

* vsd-6: On ValueSet.expansion.contains: SHALL have a code or a display (expression on ValueSet.expansion.contains: code.exists() or display.exists())

* vsd-9: On ValueSet.expansion.contains: Must have a code if not abstract (expression on ValueSet.expansion.contains: code.exists() or abstract = true)

4.8.5 Composition Rules

A value set can be a simple list of included codes, or it can be some kind of general selection criteria using the facilities provided by the code system. For these value sets:

* Multiple include statements are cumulative - e.g. the value set contains the union of all the includes

* Within an include, all the criterion apply -e.g. the value set contains the intersection of the criterion

* Within an , a single system with selection criteria may be listed, and/or one or more value sets may be listed. Rules for interpretation:

include

* System only: Codes are 'selected' for inclusion if they are selected by the code system selection (see next point)

* valueSet only: Codes are 'selected' for inclusion if they are in all the referenced value sets

* System and valueSet: Codes are 'selected' for inclusion if they are selected by the code system selection and if they are in all the referenced value sets

* If a system is specified, the following rules apply:

* no concept or filter: All codes in the system are included

* concept: Only the enumerated codes are selected

* filter: Any codes meeting the filter criteria are selected

* If the system reference is not version specific and filters are present, then the contents of the value set are open and change over time as the underlying code systems are updated

* Using the property filters is only possible where the code system in use defines the relevant properties. Note that in some cases the underlying code system defines the logical concepts but not the syntax for exercising them. In such cases, the literal definitions may be provided by a third party

* In addition to include rules, codes may be excluded. Rules for interpretation of exclude statements match those for includes, but codes in the exlude statements are never in the value set

* Value sets may include abstract codes - that is, codes designated by the underlying code system as not for use as a selectable concept in a particular context. These abstract codes are typically used as a grouping/searching mechanism, and can be included either by enumerating them, or by using a filter.

When a value set enumerates codes, it is sometimes useful to define an alternative display for the code that is to be used wherever the value set is expanded and used in a UI. This facility is provided to cover the following circumstances:

* The system that defines the code or expression doesn't provide a display for this code (or any codes).

* The system that defines the code or expression defines multiple choices for display.

* The system provides a very long display name that is unnecessary or inappropriate in the context of this value set (e.g. a display name of "Glucose [Mass/volume] in Serum or Plasma --10 PM specimen" for LOINC code 48991-4, when the value set only includes Glucose mass/vol in serum/plasma codes). As the display names get longer, this becomes more important.

Note that care must be taken in order to avoid "changing the meaning" of the concept by implying that it means something other than the explicit definition of the concept in the underlying code system (e.g., in the case above, using a display of "Glucose Concentration at 10pm"). For this reason, some contexts of use do not allow a display to be associated with a specific code in a value set.

Any display name for a concept provided in the value set is only used in the UI. The display in a Coding must be taken from the underlying code system definition, even if a value set is referenced explicitly in the Coding (e.g. by an extension). The alternative display specified in the value set would go in CodeableConcept.text, perhaps appended to the UI label for the matching data element.

4.8.6 Value Sets with multiple code systems

Value sets may select codes from multiple code systems - either by including codes from different systems, or importing other value sets that include them. A typical use for crossing code systems is when including a set of codes, and adding a few additional codes to cover cases not catered to by the included codes (e.g. Data missing or workflow error codes).

Best Practice Note: Mixing definitional systems offers the potential for confusing, overlapping, and inconsistent definitions. Creating value sets that cross code systems should be done with care to avoid creating definitional confusion.

4.8.6.1 Code systems Note

Each Code System defines which filters can be used in ValueSet.compose.include.filter. All code systems have base filters and any additional filters defined in in (CodeSystem.filter).

This specification also defines filters for various published code systems:

* LOINC Filters

* Using CT Filters

* RxNorm Filters

* UCUM Filters

* Using Metathesaurus Filters

* CPT Filters

* NDF-RT Filters

4.8.7 Value Set Expansion

A value set can be "expanded", where the definition of the value set is used to create a simple collection of codes suitable for use for data entry or validation. There is a defined operation $expand to ask a server to perform this expansion. Expansions are most useful when a value set includes all the codes in a code system, or a set of codes by filter.

A resource that represents a value set expansion includes the same identification details as the definition of the value set, and MAY include the definition of the value set (.compose). In addition, it has an .expansion element which contains the list of codes that constitute the value set expansion. If the expansion has nested contains elements, there is no implication about the logical relationship between them, and the structure cannot be used for logical inferencing. The structure exists to provide navigational assistance for helping human users to locate codes in the expansion.

When a request for an expansion is received (e.g., for the $expand operation), the following process should be followed:

* If the value set already has an expansion (e.g., a stored expansion), simply take the existing expansion as it is. If not, then:

* For each :

compose.include

* If there is a system, identify the correct version of the code system, and then:

* If there are no codes or filters, add every code in the code system to the result set.

* If codes are listed, check that they are valid, and check their active status, and if ok, add them to the result set (the profile parameter to the $expand operation may be used to control whether active codes are included).

* If any filters are present, process them in order (as explained above), and add the intersection of their results to the result set.

* For each valueSet, find the referenced value set by ValueSet.url, expand that (e.g., using the $expand operation: GET [base]/ValueSet/$expand$url=[compose.include.valueSet]), and add it to the result set. This means that expansion across imports is a recursive process.

* Add the intersection of the result set from the system and the result sets from the value sets to the expansion

* For each compose.exclude, follow the same process as for compose.include, but remove any codes from the result set, instead of adding them.

The final "result set" is then represented in expansion. Note that the expansion structure is inherently ordered, and also provides support for a hierarchical tree of items. This specification does not fix the meaning of use of either the order or the hierarchy, and the conceptual approach described should not be understood to prohibit any implementation approach in these regards. In addition, note that the method described above is a conceptual approach; individual servers may choose to follow alternative approaches that are more efficient, as long as the outcome is the same.

An expansion may include entries in the expansion that only serve an arbitrary grouping purpose, to make it easier for a human to use the list. These entries have no system or code, and must be marked as abstract. Note that the CodeSystem resource and ValueSet.compose offer no support for defining hierarchies and groups, but this does not exclude servers from using extensions or other knowledge to introduce such groups as an implementation feature.

The codes in the expansion should be treated as case sensitive - implementers should use the correct case. Implementers can consult the definition of the underlying code systems to determine whether the code system that defines the code is case sensitive or not.

It is important that expansions be identified properly. Any value set definition may produce an infinite number of expansions, depending on the expansion profile and $expand operation parameters. Any expansions produced must be clearly identified so that there is no confusion. The following rules apply:

* The canonical URL for the expansion is the same as the value set it was expanded from

* Each expansion SHALL have a unique identifier in ValueSet.expansion.identifier

* The result of an $expand operation may use the same identifier in ValueSet.expansion.identifier as a previous expansion, but if it does, the canonical representation of the value set expansion SHALL be identical (e.g. a cached response)

Whether to store expanded value sets, or simply to store their definitions and expand on the fly is a matter for system deployment. Some servers, including public value sets servers, only store expansions. However any system that stores an expansion must be concerned with how to determine whether the expansion is still current, and this requires deep knowledge of how the expansion was created. A system with a dedicated terminology server that returns expansions on demand avoids this problem, but leaves open the question of how to audit the specific expansion that was used for a particular case. One solution to this is to use a dedicated terminology server, and have the clients ask for expansions on demand based on the value set definitions, and for the server to store (and reuse as appropriate) the returned expansion (when it reuses the expansion, ValueSet.expansion.identifier will be the same). If expansions are shared, users need to be aware of how expansion identifiers (which may be server specific) work.

4.8.8 Search Parameters

Search parameters for this resource. The common parameters also apply. See Searching for more information about searching in REST, messaging, and services.

Name | Type | Description | Expression | In Common
date | date | The value set publication date | ValueSet.date
description | string | The description of the value set | ValueSet.description

expansion | uri | Uniquely identifies this expansion | ValueSet.expansion.identifier
identifier | token | External identifier for the value set | ValueSet.identifier
jurisdiction | token | Intended jurisdiction for the value set | ValueSet.jurisdiction
name | string | Computationally friendly name of the value set | ValueSet.name
publisher | string | Name of the publisher of the value set | ValueSet.publisher
reference | uri | A code system included or excluded in the value set or an imported value set | ValueSet.compose.include.system
status | token | The current status of the value set | ValueSet.status
title | string | The human-friendly name of the value set | ValueSet.title
url | uri | The uri that identifies the value set | ValueSet.url
version | token | The business version of the value set | ValueSet.version

4.8.9 Resource ValueSet - Examples

URL: https://hl7.org/fhir/STU3/valueset-examples.html

This page is part of the FHIR Specification (v3.0.2: STU 3). The current version which supercedes this version is 4.0.1. For a full list of available versions, see the Directory of published versions

4.8.9 Resource ValueSet - Examples

Vocabulary Work Group | Maturity Level: N/A | Ballot Status: Informative | Compartments: Not linked to any defined compartments

As well as the specific example below, there are many value sets published as part of defining other resources. See:

* FHIR Valuesets

* HL7 v2 Tables

* HL7 v3 Code systems and Value sets

Example List:

ValueSet Example using enumeration of codes (extensional) | example-extensional | XML | JSON | Turtle
ValueSet Example using code filter (intensional) | example-intensional | XML | JSON | Turtle
ValueSet Example using a prepared expansion | example-expansion | XML | JSON | Turtle
Common UCUM codes | ucum-common | XML | JSON | Turtle
All CPT codes | cpt-all | XML | JSON | Turtle
Yes/No/Don't know, for capturing a common answer set in questionnaires | yesnodontknow | XML | JSON | Turtle
NHIN Purpose of Use | nhin-purposeofuse | XML | JSON | Turtle
Valueset including inactive concepts | inactive | XML | JSON | Turtle

Usage note: every effort has been made to ensure that the examples are correct and useful, but they are not a normative part of the specification.

4.8.10 Resource ValueSet - Detailed Descriptions

URL: https://hl7.org/fhir/STU3/valueset-definitions.html

This page is part of the FHIR Specification (v3.0.2: STU 3). The current version which supercedes this version is 4.0.1. For a full list of available versions, see the Directory of published versions

4.8.10 Resource ValueSet - Detailed Descriptions

Vocabulary Work Group | Maturity Level: 5 | Trial Use | Compartments: Not linked to any defined compartments

Detailed Descriptions for the elements in the ValueSet resource.

ValueSet
Definition | A value set specifies a set of codes drawn from one or more code systems.
Control | 1..1
Invariants | Defined on this element vsd-5: Value set SHALL contain at least one of a compose or an expansion element (expression : compose.exists() or expansion.exists(), xpath: exists(f:compose) or exists(f:expansion))
ValueSet.url
Definition | An absolute URI that is used to identify this value set when it is referenced in a specification, model, design or an instance. This SHALL be a URL, SHOULD be globally unique, and SHOULD be an address at which this value set is (or will be) published. The URL SHOULD include the major version of the value set. For more information see Technical and Business Versions.
Control | 0..1
Type | uri
Requirements | Allows the value set to be referenced by a single globally unique identifier.
Summary | true
Comments | Can be a urn:uuid: or a urn:oid:, but real http: addresses are preferred. Multiple instances may share the same url if they have a distinct version.
ValueSet.identifier
Definition | A formal identifier that is used to identify this value set when it is represented in other formats, or referenced in a specification, model, design or an instance.
Note | This is a business identifer, not a resource identifier (see discussion)
Control | 0..*
Type | Identifier
Requirements | Allows externally provided and/or usable business identifiers to be easily associated with the module.
Summary | true

Comments | Typically, this is used for identifiers that can go in an HL7 V3 II (instance identifier) data type, e.g., to identify this value set outside of FHIR, where it is not possible to use the logical URI.

ValueSet.version

Definition | The identifier that is used to identify this version of the value set when it is referenced in a specification, model, design or instance. This is an arbitrary value managed by the value set author and is not expected to be globally unique. For example, it might be a timestamp (e.g. yyyymmdd) if a managed version is not available. There is also no expectation that versions can be placed in a lexicographical sequence.

Note | This is a business versionId, not a resource version id (see discussion)

Control | 0..1

Type | string

Summary | true

Comments | There may be different value set instances that have the same identifier but different versions. The version can be appended to the url in a reference to allow a refrence to a particular business version of the value set with the format [url]|[version].

ValueSet.name

Definition | A natural language name identifying the value set. This name should be usable as an identifier for the module by machine processing applications such as code generation.

Control | 0..1

Type | string

Requirements | Support human navigation and code generation.

Summary | true

Comments | The name is not expected to be globally unique. The name should be a simple alpha-numeric type name to ensure that it is computable friendly. A name should be provided unless the value set is a contained resource (e.g. an anonymous value set in a profile). Most registries will require a name.

ValueSet.title

Definition | A short, descriptive, user-friendly title for the value set.

Control | 0..1

Type | string

Summary | true

Comments | This name does not need to be machine-processing friendly and may contain punctuation, white-space, etc.

ValueSet.status

Definition | The status of this value set. Enables tracking the life-cycle of the content.

Control | 1..1

Terminology Binding | PublicationStatus (Required)

Type | code

Is Modifier | true

Summary | true

Comments | Allows filtering of value sets that are appropriate for use vs. not. This is labeled as "Is Modifier" because applications should not use a retired value set without due consideration.

ValueSet.experimental

Definition | A boolean value to indicate that this value set is authored for testing purposes (or education/evaluation/marketing), and is not intended to be used for genuine usage.

Control | 0..1

Type | boolean

Is Modifier | true

Requirements | Enables experimental content to be developed following the same lifecycle that would be used for a production-level value set.

Summary | true

Comments | Allows filtering of value set that are appropriate for use vs. not. This is labeled as "Is Modifier" because applications should not use an experimental value set in production.

ValueSet.date

Definition | The date (and optionally time) when the value set was published. The date must change if and when the business version changes and it must change if the status code changes. In addition, it should change when the substantive content of the value set changes. (e.g. the 'content logical definition').

Control | 0..1

Type | dateTime

Alternate Names | Revision Date

Summary | true

Comments | Note that this is not the same as the resource last-modified-date, since the resource may be a secondary representation of the value set. Additional specific dates may be added as extensions or be found by consulting Provenances associated with past versions of the resource.

ValueSet.publisher

Definition | The name of the individual or organization that published the value set.

Control | 0..1

Type | string

Requirements | Helps establish the "authority/credibility" of the value set. May also allow for contact.

Summary | true

Comments | Usually an organization, but may be an individual. The publisher (or steward) of the value set is the organization or individual primarily responsible for the maintenance and upkeep of the value set. This is not necessarily the same individual or organization that developed and initially authored the content. The publisher is the primary point of contact for questions or issues with the value set. This item SHOULD be populated unless the information is available from context.

ValueSet.contact

Definition | Contact details to assist a user in finding and communicating with the publisher.

Control | 0..*

Type | ContactDetail

Summary | true

Comments | May be a web site, an email address, a telephone number, etc.

ValueSet.description

Definition | A free text natural language description of the value set from a consumer's perspective.
Control | 0..1
Type | markdown
Alternate Names | Scope; Purpose
Comments | This description can be used to capture details such as why the value set was built, comments about misuse, instructions for clinical use and interpretation, literature references, examples from the paper world, etc. It is not a rendering of the value set as conveyed in the 'text' field of the resource itself. This item SHOULD be populated unless the information is available from context (e.g. the language of the profile is presumed to be the predominant language in the place the profile was created). The description is not intended to describe the semantics of the Value Set - there are no intrinsic semantics separate from the codes contained in its expansion. The description should capture its intended use, which is needed for ensuring integrity for its use in models across future changes. A description should be provided unless the value set is a contained resource (e.g. an anonymous value set in a profile). Most registries will require a description.
ValueSet.useContext
Definition | The content was developed with a focus and intent of supporting the contexts that are listed. These terms may be used to assist with indexing and searching for appropriate value set instances.
Control | 0..*
Type | UsageContext
Requirements | Assist in searching for appropriate content.
Summary | true
Comments | When multiple useContexts are specified, there is no expectation whether all or any of the contexts apply.
ValueSet.jurisdiction
Definition | A legal or geographic region in which the value set is intended to be used.
Control | 0..*
Terminology Binding | Jurisdiction ValueSet (Extensible)
Type | CodeableConcept
Summary | true
Comments | It may be possible for the value set to be used in jurisdictions other than those for which it was originally designed or intended.
ValueSet.immutable
Definition | If this is set to 'true', then no new versions of the content logical definition can be created. Note: Other metadata might still change.
Control | 0..1
Type | boolean
Summary | true
Comments | Normally immutability is set to 'false', which is the default assumption if it is not populated. Note that the implication is that if this is set to 'true', there may be only one ValueSet version for this definition. Immutability tends to be set to 'true' in one of two cases: - Where the value set, by the nature of its usage, cannot change. For example "All specializations of ACT in ActClassCode" - Where there's no safe way to express the "Purpose" such that someone else could safely make changes to the value set definition. Source workflow control must guarantee that the same URI always yields the same definition.
ValueSet.purpose
Definition | Explaination of why this value set is needed and why it has been designed as it has.
Control | 0..1
Type | markdown
Comments | This element does not describe the usage of the value set Instead it provides traceability of "why" the resource is either needed or "why" it is defined as it is. This may be used to point to source materials or specifications that drove the structure of this value set.
ValueSet.copyright
Definition | A copyright statement relating to the value set and/or its contents. Copyright statements are generally legal restrictions on the use and publishing of the value set.
Control | 0..1
Type | markdown
Requirements | Consumers must be able to determine any legal restrictions on the use of the value set and/or its content.
Alternate Names | License; Restrictions
Comments | null Frequently, the copyright differs between the value set and the codes that are included. The copyright statement should clearly differentiate between these when required.
ValueSet.extensible
Definition | Whether this is intended to be used with an extensible binding or not.
Control | 0..1
Type | boolean
Requirements | It is not required to say whether this intent applies.
Summary | true
ValueSet.compose
Definition | A set of criteria that define the content logical definition of the value set by including or excluding codes from outside this value set. This I also known as the "Content Logical Definition" (CLD).
Control | 0..1
Alternate Names | Content Logical Definition
Invariants | Affect this element vsd-5: Value set SHALL contain at least one of a compose or an expansion element (expression : compose.exists() or expansion.exists(), xpath: exists(f:compose) or exists(f:expansion))
ValueSet.compose.lockedDate
Definition | If a locked date is defined, then the Content Logical Definition must be evaluated using the current version as of the locked date for referenced code system(s) and value set instances where ValueSet.compose.include.version is not defined.
Control | 0..1
Type | date
Summary | true
Comments | With a defined lockedDate the value set is considered "Locked". Otherwise, the value set may have different expansions as underlying code systems and/or value sets evolve. The interpretation of lockedDate is often dependent on the context - e.g. a SNOMED CT derived value set with a lockedDate will have a different expansion in USA than in UK. If a value set specifies a version for include and exclude statements, and also specifies a locked date, the specified versions need to be available that date, or the value set will not be usable.

ValueSet.compose.inactive

Definition | Whether inactive codes - codes that are not approved for current use - are in the value set. If inactive = true, inactive codes are to be included in the expansion, if inactive = false, the inactive codes will not be included in the expansion. If absent, the behavior is determined by the implementation, or by the applicable ExpansionProfile (but generally, inactive codes would be expected to be included).

Control | 0..1

Type | boolean

Summary | true

Comments | Note that in the FHIR terminology framework, "deprecated" does not mean inactive, but in some code systems (e.g. LOINC, deprecated means inactive). Code systems should define what codes are considered to be inactive. If this is not clearly defined (including in the FHIR code system resource), then all codes are assumed to be active.

ValueSet.compose.include

Definition | Include one or more codes from a code system or other value set(s).

Control | 1..*

Summary | true

Comments | All the conditions in an include must be true. If a system is listed, all the codes from the system are listed. If one or more filters are listed, all of the filters must apply. If one or more value sets are listed, the codes must be in all the value sets. E.g. each include is 'include all the codes that meet all these conditions'.

Invariants | Defined on this element vsd-1: A value set include/exclude SHALL have a value set or a system (expression : valueSet.exists() or system.exists(), xpath: exists(f:valueSet) or exists(f:system)) vsd-2: A value set with concepts or filters SHALL include a system (expression : (concept.exists() or filter.exists()) implies system.exists(), xpath: not(exists(f:concept) or exists(f:filter)) or exists(f:system)) vsd-3: Cannot have both concept and filter (expression : concept.empty() or filter.empty(), xpath: not(exists(f:concept)) or not(exists(f:filter)))

ValueSet.compose.include.system

Definition | An absolute URI which is the code system from which the selected codes come from.

Control | 0..1

Type | uri

Summary | true

Comments | If there are no codes or filters, the entire code system is included. Note that the set of codes that are included may contain abstract codes. See "Coding.system" for further documentation about the correct value for the system element.

Invariants | Affect this element vsd-1: A value set include/exclude SHALL have a value set or a system (expression : valueSet.exists() or system.exists(), xpath: exists(f:valueSet) or exists(f:system)) vsd-2: A value set with concepts or filters SHALL include a system (expression : (concept.exists() or filter.exists()) implies system.exists(), xpath: not(exists(f:concept) or exists(f:filter)) or exists(f:system))

ValueSet.compose.include.version

Definition | The version of the code system that the codes are selected from.

Note | This is a business versionId, not a resource version id (see discussion)

Control | 0..1

Type | string

Summary | true

Comments | This is used when selecting the descendants of a concept - they may change between versions. If no version is specified, then the exact contents of the value set may not be known until a context of use binds it to a particular version.

ValueSet.compose.include.concept

Definition | Specifies a concept to be included or excluded.

Control | 0..*

Comments | The list of concepts is considered ordered, though the order may not have any particular significance. Typically, the order of an expansion follows that defined in the compose element.

Invariants | Affect this element vsd-3: Cannot have both concept and filter (expression : concept.empty() or filter.empty(), xpath: not(exists(f:concept)) or not(exists(f:filter)))

ValueSet.compose.include.concept.code

Definition | Specifies a code for the concept to be included or excluded.

Control | 1..1

Type | code

Comments | Expressions are allowed if defined by the underlying code system.

ValueSet.compose.include.concept.display

Definition | The text to display to the user for this concept in the context of this valueset. If no display is provided, then applications using the value set use the display specified for the code by the system.

Control | 0..1

Type | string

Comments | The value set resource allows for an alternative display to be specified for when this concept is used in this particular value set. See notes in the value set narrative about the correct use of this element.

ValueSet.compose.include.concept.designation

Definition | Additional representations for this concept when used in this value set - other languages, aliases, specialized purposes, used for particular purposes, etc.

Control | 0..*

ValueSet.compose.include.concept.designation.language

Definition | The language this designation is defined for.

Control | 0..1

Terminology Binding | Common Languages (Extensible but limited to ??)

Type | code

Comments | In the absence of a language, the resource language applies.

ValueSet.compose.include.concept.designation.use

Definition | A code that details how this designation would be used.

Control | 0..1

Terminology Binding | Designation Use (Extensible)

Type | Coding

Comments | If no use is provided, the designation can be assumed to be suitable for general display to a human user.

ValueSet.compose.include.concept.designation.value
Definition | The text value for this designation.
Control | 1..1
Type | string
ValueSet.compose.include.filter
Definition | Select concepts by specify a matching criteria based on the properties (including relationships) defined by the system. If multiple filters are specified, they SHALL all be true.
Control | 0..*
Is Modifier | true
Summary | true
Comments | Selecting codes by specifying filters based on properties is only possible where the underlying code system defines appropriate properties. Note that in some cases, the underlying code system defines the logical concepts but not the literal codes for the concepts. In such cases, the literal definitions may be provided by a third party.
Invariants | Affect this element vsd-3: Cannot have both concept and filter (expression : concept.empty() or filter.empty(), xpath: not(exists(f:concept)) or not(exists(f:filter)))
ValueSet.compose.include.filter.property
Definition | A code that identifies a property defined in the code system.
Control | 1..1
Type | code
Summary | true
ValueSet.compose.include.filter.op
Definition | The kind of operation to perform as a part of the filter criteria.
Control | 1..1
Terminology Binding | FilterOperator (Required)
Type | code
Summary | true
ValueSet.compose.include.filter.value
Definition | The match value may be either a code defined by the system, or a string value, which is a regex match on the literal string of the property value when the operation is 'regex', or one of the values (true and false), when the operation is 'exists'.
Control | 1..1
Type | code
Summary | true
Comments | Use regex matching with care - full regex matching on every SNOMED CT term is prohibitive, for example.
ValueSet.compose.include.valueSet
Definition | Selects concepts found in this value set. This is an absolute URI that is a reference to ValueSet.url.
Control | 0..*
Type | uri
Summary | true
Comments | The value set URI is either a logical reference to a defined value set such as a [SNOMED CT reference set]{snomedct.html#implicit}, or a direct reference to a value set definition using ValueSet.url. The reference may not refer to an actual FHIR ValueSet resource; in this case, whatever is referred to is an implicit definition of a value set that needs to be clear about how versions are resolved.
Invariants | Affect this element vsd-1: A value set include/exclude SHALL have a value set or a system (expression : valueSet.exists() or system.exists(), xpath: exists(f:valueSet) or exists(f:system))
ValueSet.compose.exclude
Definition | Exclude one or more codes from the value set based on code system filters and/or other value sets.
Control | 0..*
Type | See ValueSet.compose.include
Comments | Usually this is used to selectively exclude codes that were included by subsumption in the inclusions. Any display names specified for the codes are ignored.
Invariants | Affect this element vsd-2: A value set with concepts or filters SHALL include a system (expression : (concept.exists() or filter.exists()) implies system.exists(), xpath: not(exists(f:concept) or exists(f:filter)) or exists(f:system))
ValueSet.expansion
Definition | A value set can also be "expanded", where the value set is turned into a simple collection of enumerated codes. This element holds the expansion, if it has been performed.
Control | 0..1
Comments | Expansion is performed to produce a collection of codes that are ready to use for data entry or validation.
Invariants | Affect this element vsd-5: Value set SHALL contain at least one of a compose or an expansion element (expression : compose.exists() or expansion.exists(), xpath: exists(f:compose) or exists(f:expansion))
ValueSet.expansion.identifier
Definition | An identifier that uniquely identifies this expansion of the valueset. Systems may re-use the same identifier as long as the expansion and the definition remain the same, but are not required to do so.
Note | This is a business identifer, not a resource identifier (see discussion)
Control | 1..1
Type | uri
Comments | Typically, this uri is a UUID (e.g. urn:uuid:8230ff20-c97a-4167-a59d-dc2cb9df16dd).
ValueSet.expansion.timestamp
Definition | The time at which the expansion was produced by the expanding system.
Control | 1..1
Type | dateTime
Comments | This SHOULD be a fully populated instant, but in some circumstances, value sets are expanded by hand, and the expansion is published without that precision.
ValueSet.expansion.total
Definition | The total number of concepts in the expansion. If the number of concept nodes in this resource is less than the stated number, then the server can return more using the offset parameter.

Control | 0..1
Type | integer
Comments | Paging only applies to flat expansions.
ValueSet.expansion.offset
Definition | If paging is being used, the offset at which this resource starts. I.e. this resource is a partial view into the expansion. If paging is not being used, this element SHALL not be present.
Control | 0..1
Type | integer
Meaning if Missing | Paging is not being used
Comments | Paging only applies to flat expansions. If a filter is applied, the count is the number of concepts that matched the filter, not the number of concepts in an unfiltered view of the expansion.
ValueSet.expansion.parameter
Definition | A parameter that controlled the expansion process. These parameters may be used by users of expanded value sets to check whether the expansion is suitable for a particular purpose, or to pick the correct expansion.
Control | 0..*
Comments | The server decides which parameters to include here, but at a minimum, the list SHOULD include the date, filter, and profile parameters passed to the $expand operation (if any).
ValueSet.expansion.parameter.name
Definition | The name of the parameter.
Control | 1..1
Type | string
Comments | The names are assigned at the discretion of the server.
ValueSet.expansion.parameter.value[x]
Definition | The value of the parameter.
Control | 0..1
Type | string|boolean|integer|decimal|uri|code
[x] Note | See Choice of Data Types for further information about how to use [x]
ValueSet.expansion.contains
Definition | The codes that are contained in the value set expansion.
Control | 0..*
Invariants | Defined on this element vsd-10: Must have a system if a code is present (expression : code.empty() or system.exists(), xpath: exists(f:system) or not(exists(f:code))) vsd-6: SHALL have a code or a display (expression : code.exists() or display.exists(), xpath: exists(f:code) or exists(f:display)) vsd-9: Must have a code if not abstract (expression : code.exists() or abstract = true, xpath: exists(f:code) or (f:abstract/@value = true()))
ValueSet.expansion.contains.system
Definition | An absolute URI which is the code system in which the code for this item in the expansion is defined.
Control | 0..1
Type | uri
ValueSet.expansion.contains.abstract
Definition | If true, this entry is included in the expansion for navigational purposes, and the user cannot select the code directly as a proper value.
Control | 0..1
Type | boolean
Default Value | false
Comments | This should not be understood to exclude its use for searching (e.g. by subsumption testing). The client should know whether it is appropriate for the user to select an abstract code or not.
ValueSet.expansion.contains.inactive
Definition | If the concept is inactive in the code system that defines it. Inactive codes are those that are no longer to be used, but are maintained by the code system for understanding legacy data.
Control | 0..1
Type | boolean
Default Value | false
Comments | This should only have a value if the concept is inactive.
ValueSet.expansion.contains.version
Definition | The version of this code system that defined this code and/or display. This should only be used with code systems that do not enforce concept permanence.
Note | This is a business versionId, not a resource version id (see discussion)
Control | 0..1
Type | string
Comments | The exact value of the version string is specified by the system from which the code is derived.
ValueSet.expansion.contains.code
Definition | The code for this item in the expansion hierarchy. If this code is missing the entry in the hierarchy is a place holder (abstract) and does not represent a valid code in the value set.
Control | 0..1
Type | code
Invariants | Affect this element vsd-6: SHALL have a code or a display (expression : code.exists() or display.exists(), xpath: exists(f:code) or exists(f:display))
ValueSet.expansion.contains.display
Definition | The recommended display for this item in the expansion.
Control | 0..1
Type | string
Invariants | Affect this element vsd-6: SHALL have a code or a display (expression : code.exists() or display.exists(), xpath: exists(f:code) or exists(f:display))
ValueSet.expansion.contains.designation

Definition | Additional representations for this item - other languages, aliases, specialized purposes, used for particular purposes, etc. These are relevant when the conditions of the expansion do not fix to a single correct representation.
Control | 0..*
Type | See ValueSet.compose.include.concept.designation
Comments | The designations provided must be based on the value set and code system definitions.
ValueSet.expansion.contains.contains
Definition | Other codes and entries contained under this entry in the hierarchy.
Control | 0..*
Type | See ValueSet.expansion.contains
Comments | If the expansion uses this element, there is no implication about the logical relationship between them, and the structure cannot be used for logical inferencing. The structure exists to provide navigational assistance for helping human users to locate codes in the expansion.

4.8.11 Resource ValueSet - Mappings

URL: https://hl7.org/fhir/STU3/valueset-mappings.html

This page is part of the FHIR Specification (v3.0.2: STU 3). The current version which supercedes this version is 4.0.1. For a full list of available versions, see the Directory of published versions

4.8.11 Resource ValueSet - Mappings

Vocabulary Work Group | Maturity Level: N/A | Ballot Status: Informative | Compartments: Not linked to any defined compartments

Mappings:

RIM Mapping

CDISC Define XML 2.0 metadata standard

Mappings for the valueset resource.

4.8.11.1 Mappings for RIM Mapping (http://hl7.org/v3)

ValueSet | N/A

4.8.11.2 Mappings for CDISC Define XML 2.0 metadata standard (http://www.cdisc.org/define-xml)

ValueSet
url
identifier | Identifier part
version
name
title
status
experimental
date
publisher
contact
description
useContext
jurisdiction
immutable
purpose
copyright
extensible
compose
lockedDate
inactive
include
system | ODM/Study/MetaDataVersion/CodeList/ExternalCodeList/Href
version | ODM/Study/MetaDataVersion/CodeList/ExternalCodeList/Version
concept
code
display
designation
language
use
value
filter
property
op
value
valueSet
exclude
expansion
identifier
timestamp

total
offset
parameter
name
value[x]
contains
system
abstract
inactive
version
code
display
designation
contains

4.8.12 Resource ValueSet - Design Notes

URL: https://hl7.org/fhir/STU3/valueset-explanations.html

This page is part of the FHIR Specification (v3.0.2: STU 3). The current version which supercedes this version is 4.0.1. For a full list of available versions, see the Directory of published versions

4.8.12 Resource ValueSet - Design Notes

to do

4.8.13 Resource ValueSet - Extensions & Profiles

URL: https://hl7.org/fhir/STU3/valueset-profiles.html

This page is part of the FHIR Specification (v3.0.2: STU 3). The current version which supercedes this version is 4.0.1. For a full list of available versions, see the Directory of published versions

4.8.13 Resource ValueSet - Extensions & Profiles

Vocabulary Work Group | Maturity Level: N/A | Ballot Status: Informative

This table lists profiles and extensions for the ValueSet resource. For background information, see Profiling Resources and Extensibility. Additional profiles and resources may be found in published Implementation Guides , or in the Conformance resource registry .

4.8.13.1 Profiles

ShareableValueSet | Enforces the minimum information set for the value set metadata required by HL7 and other organisations that share and publish value sets | for Shareable ValueSet

4.8.13.2 Extensions

resource-approvalDate | approvalDate | for Resource HL7 Extensions
resource-effectivePeriod | effectivePeriod | for Resource HL7 Extensions
resource-lastReviewDate | lastReviewDate | for Resource HL7 Extensions
valueset-author | author | for ValueSet HL7 Extensions
valueset-caseSensitive | caseSensitive | for ValueSet HL7 Extensions
valueset-comment | comment | for ValueSet HL7 Extensions
valueset-comments | comments | for ValueSet HL7 Extensions
valueset-conceptOrder | conceptOrder | for ValueSet HL7 Extensions
valueset-definition | definition | for ValueSet HL7 Extensions
valueset-effectiveDate | effectiveDate | for ValueSet HL7 Extensions
valueset-expansionSource | expansionSource | for ValueSet HL7 Extensions
valueset-expirationDate | expirationDate | for ValueSet HL7 Extensions
valueset-history | history | for ValueSet HL7 Extensions
valueset-keyWord | keyWord | for ValueSet HL7 Extensions
valueset-label | label | for ValueSet HL7 Extensions
valueset-map | map | for ValueSet HL7 Extensions
valueset-ordinalValue | ordinalValue | for ValueSet HL7 Extensions
valueset-otherName | otherName | for ValueSet HL7 Extensions
valueset-sourceReference | sourceReference | for ValueSet HL7 Extensions
valueset-system | system | for ValueSet HL7 Extensions
valueset-systemName | systemName | for ValueSet HL7 Extensions
valueset-systemRef | systemRef | for ValueSet HL7 Extensions
valueset-toocostly | toocostly | for ValueSet HL7 Extensions
valueset-trusted-expansion | trusted-expansion | for ValueSet HL7 Extensions
valueset-unclosed | unclosed | for ValueSet HL7 Extensions
valueset-usage | usage | for ValueSet HL7 Extensions
valueset-warning | warning | for ValueSet HL7 Extensions
valueset-workflowStatus | workflowStatus | for ValueSet HL7 Extensions

Extensions that reference this resource:

11179-permitted-value-valueset | permitted-value-valueset | for ISO 11179 Element Definition Profile
elementdefinition-allowedUnits | allowedUnits | for Common extensions for ElementDefinition data type
elementdefinition-inheritedExtensibleValueSet | inheritedExtensibleValueSet | for Common extensions for ElementDefinition data type
elementdefinition-maxValueSet | maxValueSet | for Common extensions for ElementDefinition data type
elementdefinition-minValueSet | minValueSet | for Common extensions for ElementDefinition data type

4.8.13.3 Search Extensions

No Search Extensions defined for this resource

4.8.14 ValueSet HL7 Extensions

URL: https://hl7.org/fhir/STU3/valueset-extensions.html

Defines common extensions used with or related to the ValueSet resource

This page is part of the FHIR Specification (v3.0.2: STU 3). The current version which supercedes this version is 4.0.1. For a full list of available versions, see the Directory of published versions

4.8.14 ValueSet HL7 Extensions

(No assigned work group) | Maturity Level: N/A | Ballot Status: Informative

4.8.14.1 Content

Extensions:

valueset-definition | definition : A display name that describes the meaning of this code when used as part of this value set.
valueset-comments | comments : A comment that explains how this code is used in this context (where the value set is expected to be used).
valueset-otherName | otherName : Human readable names for the valueset.
valueset-sourceReference | sourceReference : This text is intended to act as a citation to work done elsewhere that is not part of the current stewarding process where the referenced source is in some way a basis of the current value set definition.
valueset-keyWord | keyWord : Word or words used in an information retrieval system to indicate the content of the value set.
valueset-usage | usage : Consumers of the value set and the implementations, projects or standards that the author has utilized the value set in.
valueset-workflowStatus | workflowStatus : Workflow Status is used to represent details of the value set development process while the value set has an Activity Status of Preliminary. The development of a value set often follows a formal workflow process from initiation to completion, and this element carries the state variable for this state machine. The assumption is that when first created a value set would have a workflow state of Draft. Additional workflow states may be used.
valueset-effectiveDate | effectiveDate : This is the first date-time when the value set version becomes active, so this value is present on Inactive value set versions as well. The start Date_time is expected to be as of 0001 UTC of the Effective Date.
valueset-expirationDate | expirationDate : The date when the value set version is no longer expected to be used to create new content. This is the first date-time when the value set version becomes Inactive, so this value SHALL present on all Inactive value set versions. The start Date_time is expected to be as of 0001 UTC of the Expiration Date.
valueset-author | author : User or Org actually involved in creating the value set content.
valueset-comment | comment : Each comment is a time-stamped entry of arbitrary length that is not editable except by anyone in the author group.
valueset-trusted-expansion | trusted-expansion : Indicates an authoritative source for performing value set expansions.
valueset-history | history : Information on changes made to the Value Set Definition over time and a contained audit trail of all such changes.
valueset-label | label : The label to list in front of a code when presenting a list of possible values in a questionnaire-like fashion.
valueset-ordinalValue | ordinalValue : A numeric value that allows the comparison (less than, greater than) or other numerical manipulation of a concept (e.g. Adding up components of a score).
valueset-conceptOrder | conceptOrder : Identifies the relative order in which concepts within the value set should be presented to a user.
valueset-systemName | systemName : The human-readable name for the code system.
valueset-systemRef | systemRef : The formal URI for the code system. I.e. ValueSet.codeSystem.system (or its equivalent).
valueset-caseSensitive | caseSensitive : If this a case sensitive code.
valueset-reference | reference : A logical reference (e.g. a reference to ValueSet.url) that identifies the value set/version that identifies the set of possible coded values this coding was chosen from or constrained by.
valueset-expansionSource | expansionSource : The logical URL of the ValueSet definition that was used to generate this expansion.
valueset-unclosed | unclosed : Marks that the expansion is incomplete, and values other than those listed may be valid. This may be used because post-coordinated codes are allowed, and no practical expansion can be produced.
valueset-toocostly | toocostly : Marks that the expansion is incomplete, because the full value set is too large to represent, and the client asked for an incomplete fragment.
valueset-map | map : A reference to a concept map that is relevant for the interpretation of this value set.
valueset-warning | warning : An extra warning about the correct use of the value set.
valueset-system | system : Allows a direct reference to the code system for FHIR query.

4.8.14.2 Search Parameters

Search parameters defined by this package. See Searching for more information about searching in REST, messaging, and services.

Name | Type | Description | Paths | Source
author | string | Optional Extensions Element | f:ValueSet/f:extension[@url='http://hl7.org/fhir/StructureDefinition/valueset-author'] | /f:#author | XML / JSON
effective | date | Optional Extensions Element | f:ValueSet/f:extension[@url='http://hl7.org/fhir/StructureDefinition/valueset-effectiveDate'] | /f:#effectiveDate | XML / JSON
end | date | Optional Extensions Element | f:ValueSet/f:extension[@url='http://hl7.org/fhir/StructureDefinition/valueset-expirationDate'] | /f:#expirationDate | XML / JSON

keyword | string | Optional Extensions Element | f:ValueSet/f:extension[@url='http://hl7.org/fhir/StructureDefinition/valueset-keyWord'] | /f:#keyWord | XML / JSON
workflow | token | Optional Extensions Element | f:ValueSet/f:extension[@url='http://hl7.org/fhir/StructureDefinition/valueset-workflowStatus'] | /f:#workflowStatus | XML / JSON

4.8.14.3 Valueset-extensions-ValueSet-keyword

URL: https://hl7.org/fhir/STU3/valueset-extensions-ValueSet-keyword.html

This page is part of the FHIR Specification (v3.0.2: STU 3). The current version which supercedes this version is 4.0.1. For a full list of available versions, see the Directory of published versions

4.8.14.3 Valueset-extensions-ValueSet-keyword

Search Parameter keyword (type: string) defined as part of the valueset-extensions Profile.

Optional Extensions Element

Other Details:

* Full URL : http://hl7.org/fhir/SearchParameter/valueset-extensions-ValueSet-keyword

* Paths : f:ValueSet/f:extension[@url='http://hl7.org/fhir/StructureDefinition/valueset-keyWord'] | /f:#keyWord

* Targets :

4.8.14.4 Valueset-extensions-ValueSet-workflow

URL: https://hl7.org/fhir/STU3/valueset-extensions-ValueSet-workflow.html

This page is part of the FHIR Specification (v3.0.2: STU 3). The current version which supercedes this version is 4.0.1. For a full list of available versions, see the Directory of published versions

4.8.14.4 Valueset-extensions-ValueSet-workflow

Search Parameter workflow (type: token) defined as part of the valueset-extensions Profile.

Optional Extensions Element

Other Details:

* Full URL : http://hl7.org/fhir/SearchParameter/valueset-extensions-ValueSet-workflow

* Paths : f:ValueSet/f:extension[@url='http://hl7.org/fhir/StructureDefinition/valueset-workflowStatus'] | /f:#workflowStatus

* Targets :

4.8.14.5 Valueset-extensions-ValueSet-effective

URL: https://hl7.org/fhir/STU3/valueset-extensions-ValueSet-effective.html

This page is part of the FHIR Specification (v3.0.2: STU 3). The current version which supercedes this version is 4.0.1. For a full list of available versions, see the Directory of published versions

4.8.14.5 Valueset-extensions-ValueSet-effective

Search Parameter effective (type: date) defined as part of the valueset-extensions Profile.

Optional Extensions Element

Other Details:

* Full URL : http://hl7.org/fhir/SearchParameter/valueset-extensions-ValueSet-effective

* Paths : f:ValueSet/f:extension[@url='http://hl7.org/fhir/StructureDefinition/valueset-effectiveDate'] | /f:#effectiveDate

* Targets :

4.8.14.6 Valueset-extensions-ValueSet-end

URL: https://hl7.org/fhir/STU3/valueset-extensions-ValueSet-end.html

This page is part of the FHIR Specification (v3.0.2: STU 3). The current version which supercedes this version is 4.0.1. For a full list of available versions, see the Directory of published versions

4.8.14.6 Valueset-extensions-ValueSet-end

Search Parameter end (type: date) defined as part of the valueset-extensions Profile.

Optional Extensions Element

Other Details:

* Full URL : http://hl7.org/fhir/SearchParameter/valueset-extensions-ValueSet-end

* Paths : f:ValueSet/f:extension[@url='http://hl7.org/fhir/StructureDefinition/valueset-expirationDate'] | /f:#expirationDate

* Targets :

4.8.14.7 Valueset-extensions-ValueSet-author

URL: https://hl7.org/fhir/STU3/valueset-extensions-ValueSet-author.html

This page is part of the FHIR Specification (v3.0.2: STU 3). The current version which supercedes this version is 4.0.1. For a full list of available versions, see the Directory of published versions

4.8.14.7 Valueset-extensions-ValueSet-author

Search Parameter author (type: string) defined as part of the valueset-extensions Profile.

Optional Extensions Element

Other Details:

* Full URL : http://hl7.org/fhir/SearchParameter/valueset-extensions-ValueSet-author

* Paths : f:ValueSet/f:extension[@url='http://hl7.org/fhir/StructureDefinition/valueset-author'] | /f:#author

* Targets :

4.8.15 Shareable ValueSet

URL: https://hl7.org/fhir/STU3/valueset-shareable.html

Enforces the minimum information set for the value set metadata required by HL7 and other organisations that share and publish value sets

This page is part of the FHIR Specification (v3.0.2: STU 3). The current version which supercedes this version is 4.0.1. For a full list of available versions, see the Directory of published versions

4.8.15 Shareable ValueSet

(No assigned work group) | Maturity Level: N/A | Ballot Status: Informative

4.8.15.1 Content

Profiles:

ShareableValueSet | Enforces the minimum information set for the value set metadata required by HL7 and other organisations that share and publish value sets

4.8.15.2 StructureDefinition: ShareableValueSet

URL: https://hl7.org/fhir/STU3/shareablevalueset.html

This page is part of the FHIR Specification (v3.0.2: STU 3). The current version which supercedes this version is 4.0.1. For a full list of available versions, see the Directory of published versions

4.8.15.2 StructureDefinition: ShareableValueSet

(No assigned work group) | Maturity Level: 1 | Informative | Use Context: Any

The official URL for this profile is:

`http://hl7.org/fhir/StructureDefinition/shareablevalueset`

Enforces the minimum information set for the value set metadata required by HL7 and other organisations that share and publish value sets

This profile was published on [no date] as a draft by HL7.

4.8.15.2.1 Formal Views of Profile Content

Description of Profiles, Differentials, Snapshots, and how the XML and JSON presentations work.

* Text Summary

* Differential Table

* Snapshot Table

* XML Template

* JSON Template

* All

This structure is derived from ValueSet.

Summary

Mandatory: 7 elements

This structure is derived from ValueSet.

Name | Flags | Card. | Type | Description & Constraints
ValueSet | | 1..1
url | | 1..1 | uri
version | | 1..1 | string
name | | 1..1 | string
status | | 1..1 | code
experimental | | 1..1 | boolean
publisher | | 1..1 | string

description | | 1..1 | markdown
immutable | | 0..1 | boolean
Documentation for this format

Name | Flags | Card. | Type | Description & Constraints
ValueSet | I | 1..1 | | A set of codes drawn from one or more code systems
id | ? | 0..1 | id | Logical id of this artifact
meta | ? | 0..1 | Meta | Metadata about the resource
implicitRules | ?!? | 0..1 | uri | A set of rules under which this content was created
language | | 0..1 | code | Language of the resource content Binding: Common Languages (extensible)
text | I | 0..1 | Narrative | Text summary of the resource, for human interpretation
contained | | 0..* | Resource | Contained, inline Resources
extension | | 0..* | Extension | Additional Content defined by implementations
modifierExtension | ?! | 0..* | Extension | Extensions that cannot be ignored
url | ? | 1..1 | uri | Logical URI to reference this value set (globally unique)
identifier | ? | 0..* | Identifier | Additional identifier for the value set
version | ? | 1..1 | string | Business version of the value set
name | ? | 1..1 | string | Name for this value set (computer friendly)
title | ? | 0..1 | string | Name for this value set (human friendly)
status | ?!? | 1..1 | code | draft | active | retired | unknown Binding: PublicationStatus (required)
experimental | ?!? | 1..1 | boolean | For testing purposes, not real usage
date | ? | 0..1 | dateTime | Date this was last changed
publisher | ? | 1..1 | string | Name of the publisher (organization or individual)
contact | ? | 0..* | ContactDetail | Contact details for the publisher
description | | 1..1 | markdown | Natural language description of the value set
useContext | ? | 0..* | UsageContext | Context the content is intended to support
jurisdiction | ? | 0..* | CodeableConcept | Intended jurisdiction for value set (if applicable) Binding: Jurisdiction ValueSet (extensible)
immutable | ? | 0..1 | boolean | Indicates whether or not any change to the content logical definition may occur
purpose | | 0..1 | markdown | Why this value set is defined
copyright | | 0..1 | markdown | Use and/or publishing restrictions
extensible | ? | 0..1 | boolean | Whether this is intended to be used with an extensible binding
compose | I | 0..1 | BackboneElement | Definition of the content of the value set (CLD)
id | | 0..1 | string | xml:id (or equivalent in JSON)
extension | | 0..* | Extension | Additional Content defined by implementations
modifierExtension | ?!? | 0..* | Extension | Extensions that cannot be ignored
lockedDate | ? | 0..1 | date | Fixed date for version-less references (transitive)
inactive | ? | 0..1 | boolean | Whether inactive codes are in the value set
include | ?I | 1..* | BackboneElement | Include one or more codes from a code system or other value set(s) vsd-2: A value set with concepts or filters SHALL include a system vsd-3: Cannot have both concept and filter vsd-1: A value set include/exclude SHALL have a value set or a system
id | | 0..1 | string | xml:id (or equivalent in JSON)
extension | | 0..* | Extension | Additional Content defined by implementations
modifierExtension | ?!? | 0..* | Extension | Extensions that cannot be ignored
system | ?I | 0..1 | uri | The system the codes come from
version | ? | 0..1 | string | Specific version of the code system referred to
concept | I | 0..* | BackboneElement | A concept defined in the system
id | | 0..1 | string | xml:id (or equivalent in JSON)
extension | | 0..* | Extension | Additional Content defined by implementations
modifierExtension | ?!? | 0..* | Extension | Extensions that cannot be ignored
code | | 1..1 | code | Code or expression from system
display | | 0..1 | string | Text to display for this code for this value set in this valueset
designation | I | 0..* | BackboneElement | Additional representations for this concept
id | | 0..1 | string | xml:id (or equivalent in JSON)
extension | | 0..* | Extension | Additional Content defined by implementations
modifierExtension | ?!? | 0..* | Extension | Extensions that cannot be ignored
language | | 0..1 | code | Human language of the designation Binding: Common Languages (extensible)
use | | 0..1 | Coding | Details how this designation would be used Binding: Designation Use (extensible)
value | | 1..1 | string | The text value for this designation
filter | ?!?I | 0..* | BackboneElement | Select codes/concepts by their properties (including relationships)
id | | 0..1 | string | xml:id (or equivalent in JSON)
extension | | 0..* | Extension | Additional Content defined by implementations
modifierExtension | ?!? | 0..* | Extension | Extensions that cannot be ignored
property | ? | 1..1 | code | A property defined by the code system
op | ? | 1..1 | code | = | is-a | descendent-of | is-not-a | regex | in | not-in | generalizes | exists Binding: FilterOperator (required)
value | ? | 1..1 | code | Code from the system, or regex criteria, or boolean value for exists
valueSet | ?I | 0..* | uri | Select only contents included in this value set
exclude | I | 0..* | | Unknown reference to #ValueSet.compose.include Explicitly exclude codes from a code system or other value sets
expansion | I | 0..1 | BackboneElement | Used when the value set is "expanded"
id | | 0..1 | string | xml:id (or equivalent in JSON)
extension | | 0..* | Extension | Additional Content defined by implementations
modifierExtension | ?!? | 0..* | Extension | Extensions that cannot be ignored
identifier | | 1..1 | uri | Uniquely identifies this expansion
timestamp | | 1..1 | dateTime | Time ValueSet expansion happened
total | | 0..1 | integer | Total number of codes in the expansion

offset | | 0..1 | integer | Offset at which this resource starts
parameter | I | 0..* | BackboneElement | Parameter that controlled the expansion process
id | | 0..1 | string | xml:id (or equivalent in JSON)
extension | | 0..* | Extension | Additional Content defined by implementations
modifierExtension | ?!? | 0..* | Extension | Extensions that cannot be ignored
name | | 1..1 | string | Name as assigned by the server
value[x] | | 0..1 | string, boolean, integer, decimal, uri, code | Value of the named parameter
contains | I | 0..* | BackboneElement | Codes in the value set vsd-6: SHALL have a code or a display vsd-9: Must have a code if not abstract vsd-10: Must have a system if a code is present
id | | 0..1 | string | xml:id (or equivalent in JSON)
extension | | 0..* | Extension | Additional Content defined by implementations
modifierExtension | ?!? | 0..* | Extension | Extensions that cannot be ignored
system | | 0..1 | uri | System value for the code
abstract | | 0..1 | boolean | If user cannot select this entry
inactive | | 0..1 | boolean | If concept is inactive in the code system
version | | 0..1 | string | Version in which this code/display is defined
code | I | 0..1 | code | Code - if blank, this is not a selectable code
display | I | 0..1 | string | User display for the concept
designation | | 0..* | | Unknown reference to #ValueSet.compose.include.concept.designation Additional representations for this item
contains | | 0..* | | Unknown reference to #ValueSet.expansion.contains Codes contained under this entry
Documentation for this format

```
<!-- Shareable ValueSet -->

<ValueSet xmlns="http://hl7.org/fhir"
>
  <!-- from Element: extension -->
 <id value="[id]"/><!-- 0..1 Logical id of this artifact -->
 <meta><!-- 0..1 Meta Metadata about the resource --></meta>
 <implicitRules value="[uri]"/><!-- 0..1 A set of rules under which this content was created -->
 <language value="[code]"/><!-- 0..1 Language of the resource content  -->
 <text><!-- 0..1 Narrative
     Text summary of the resource, for human interpretation --></text>
 <contained><!-- 0..* Resource Contained, inline Resources --></contained>
 <modifierExtension><!-- 0..* Extension  Extensions that cannot be ignored  --></modifierExtension>
 <url value="[uri]"/><!-- 1..1 Logical URI to reference this value set (globally unique) -->
 <identifier><!-- 0..* Identifier
     Additional identifier for the value set --></identifier>
 <version value="[string]"/><!-- 1..1 Business version of the value set -->
 <name value="[string]"/><!-- 1..1 Name for this value set (computer friendly) -->
 <title value="[string]"/><!-- 0..1 Name for this value set (human friendly) -->
 <status value="[code]"/><!-- 1..1 draft | active | retired | unknown  -->
 <experimental value="[boolean]"/><!-- 1..1 For testing purposes, not real usage -->
 <date value="[dateTime]"/><!-- 0..1 Date this was last changed -->
 <publisher value="[string]"/><!-- 1..1 Name of the publisher (organization or individual) -->
 <contact><!-- 0..* ContactDetail Contact details for the publisher --></contact>
 <description value="[markdown]"/><!-- 1..1 Natural language description of the value set -->
 <useContext><!-- 0..* UsageContext
     Context the content is intended to support --></useContext>
 <jurisdiction><!-- 0..* CodeableConcept Intended jurisdiction for value set (if applicable)  --></jurisdiction>
 <immutable value="[boolean]"/><!-- 0..1 Indicates whether or not any change to the content logical definition may occur
     -->
 <purpose value="[markdown]"/><!-- 0..1 Why this value set is defined -->
 <copyright value="[markdown]"/><!-- 0..1 Use and/or publishing restrictions -->
 <extensible value="[boolean]"/><!-- 0..1 Whether this is intended to be used with an extensible binding -->
 <compose>  0..1 BackboneElement  <!--  0..1 Definition of the content of the value set (CLD) -->
  <modifierExtension><!-- 0..* Extension  Extensions that cannot be ignored  --></modifierExtension>
  <lockedDate value="[date]"/><!-- 0..1 Fixed date for version-less references (transitive) -->
  <inactive value="[boolean]"/><!-- 0..1 Whether inactive codes are in the value set -->
  <include>  1..* BackboneElement  <!--  1..* Include one or more codes from a code system or other value set(s) -->
   <modifierExtension><!-- 0..* Extension  Extensions that cannot be ignored  --></modifierExtension>
   <system value="[uri]"/><!-- 0..1 The system the codes come from -->
   <version value="[string]"/><!-- 0..1 Specific version of the code system referred to -->
   <concept>  0..* BackboneElement  <!--  0..* A concept defined in the system -->
    <modifierExtension><!-- 0..* Extension  Extensions that cannot be ignored  --></modifierExtension>
    <code value="[code]"/><!-- 1..1 Code or expression from system -->
    <display value="[string]"/><!-- 0..1
        Text to display for this code for this value set in this valueset -->
    <designation>  0..* BackboneElement  <!--  0..* Additional representations for this concept -->
     <modifierExtension><!-- 0..*
       Extension  Extensions that cannot be ignored  --></modifierExtension>
     <language value="[code]"/><!-- 0..1 Human language of the designation  -->
     <use><!-- 0..1 Coding Details how this designation would be used  --></use>
     <value value="[string]"/><!-- 1..1 The text value for this designation -->
    </designation>
   </concept>
   <filter>  0..* BackboneElement  <!--  0..* Select codes/concepts by their properties (including relationships) -->
    <modifierExtension><!-- 0..* Extension  Extensions that cannot be ignored  --></modifierExtension>
    <property value="[code]"/><!-- 1..1 A property defined by the code system -->
    <op value="[code]"/><!-- 1..1 = | is-a | descendent-of | is-not-a | regex | in | not-in | generalizes | exists  -->
    <value value="[code]"/><!-- 1..1
        Code from the system, or regex criteria, or boolean value for exists -->
   </filter>
   <valueSet value="[uri]"/><!-- 0..* Select only contents included in this value set -->
  </include>
```

```
  <exclude><!-- See #ValueSet.compose.include  Explicitly exclude codes from a code system or other value sets
    --></exclude>
 </compose>
 <expansion>  0..1 BackboneElement  <!--  0..1 Used when the value set is "expanded" -->
  <modifierExtension><!-- 0..* Extension  Extensions that cannot be ignored  --></modifierExtension>
  <identifier value="[uri]"/><!-- 1..1 Uniquely identifies this expansion -->
  <timestamp value="[dateTime]"/><!-- 1..1 Time ValueSet expansion happened -->
  <total value="[integer]"/><!-- 0..1 Total number of codes in the expansion -->
  <offset value="[integer]"/><!-- 0..1 Offset at which this resource starts -->
  <parameter>  0..* BackboneElement  <!--  0..* Parameter that controlled the expansion process -->
   <modifierExtension><!-- 0..* Extension  Extensions that cannot be ignored  --></modifierExtension>
   <name value="[string]"/><!-- 1..1 Name as assigned by the server -->
   <value[x]><!-- 0..1 string|boolean|integer|
     decimal|uri|code Value of the named parameter --></value[x]>
  </parameter>
  <contains>  0..* BackboneElement  <!--  0..* Codes in the value set -->
   <modifierExtension><!-- 0..* Extension  Extensions that cannot be ignored  --></modifierExtension>
   <system value="[uri]"/><!-- 0..1 System value for the code -->
   <abstract value="[boolean]"/><!-- 0..1 If user cannot select this entry -->
   <inactive value="[boolean]"/><!-- 0..1 If concept is inactive in the code system -->
   <version value="[string]"/><!-- 0..1 Version in which this code/display is defined -->
   <code value="[code]"/><!-- 0..1 Code - if blank, this is not a selectable code -->
   <display value="[string]"/><!-- 0..1 User display for the concept -->
   <designation><!-- See #ValueSet.compose.include.concept.designation  Additional representations for this item
    --></designation>
   <contains><!-- See #ValueSet.expansion.contains  Codes contained under this entry --></contains>
  </contains>
 </expansion>
</ValueSet>
```

```
{ // Shareable ValueSet
  // from Element: extension
    "meta" : { Meta }, //Metadata about the resource
    "implicitRules" : "<uri>", //A set of rules under which this content was created
    "language" : "<code>", //Language of the resource content
    "text" : { Narrative }, //Text summary of the resource, for human interpretation
    "contained" : [{ Resource }], //Contained, inline Resources
    "modifierExtension" : [{ Extension }], //Extensions that cannot be ignored
    "url" : "<uri>", // R! Logical URI to reference this value set (globally unique)
    "identifier" : [{ Identifier }], //Additional identifier for the value set
    "version" : "<string>", // R! Business version of the value set
    "name" : "<string>", // R! Name for this value set (computer friendly)
    "title" : "<string>", //Name for this value set (human friendly)
    "status" : "<code>", // R! draft | active | retired | unknown
    "experimental" : <boolean>, // R! For testing purposes, not real usage
    "date" : "<dateTime>", //Date this was last changed
    "publisher" : "<string>", // R! Name of the publisher (organization or individual)
    "contact" : [{ ContactDetail }], //Contact details for the publisher
    "description" : "<markdown>", // R! Natural language description of the value set
    "useContext" : [{ UsageContext }], //Context the content is intended to support
    "jurisdiction" : [{ CodeableConcept }], //Intended jurisdiction for value set (if applicable)
    "immutable" : <boolean>, //Indicates whether or not any change to the content logical definition may occur
    "purpose" : "<markdown>", //Why this value set is defined
    "copyright" : "<markdown>", //Use and/or publishing restrictions
    "extensible" : <boolean>, //Whether this is intended to be used with an extensible binding
    "compose" : { BackboneElement }, // C?Definition of the content of the value set (CLD)
    "expansion" : { BackboneElement } // C?Used when the value set is "expanded"
  }
```

This structure is derived from ValueSet.

Summary

Mandatory: 7 elements

Differential View

This structure is derived from ValueSet.

Name	Flags	Card.	Type	Description & Constraints
ValueSet		1..1		
url		1..1	uri	
version		1..1	string	
name		1..1	string	
status		1..1	code	
experimental		1..1	boolean	
publisher		1..1	string	
description		1..1	markdown	
immutable		0..1	boolean	
Documentation for this format				

Snapshot View

Name	Flags	Card.	Type	Description & Constraints
ValueSet	I	1..1		A set of codes drawn from one or more code systems
id	?	0..1	id	Logical id of this artifact
meta	?	0..1	Meta	Metadata about the resource
implicitRules	?!?	0..1	uri	A set of rules under which this content was created
language		0..1	code	Language of the resource content Binding: Common Languages (extensible)

text | I | 0..1 | Narrative | Text summary of the resource, for human interpretation
contained | | 0..* | Resource | Contained, inline Resources
extension | | 0..* | Extension | Additional Content defined by implementations
modifierExtension | ?! | 0..* | Extension | Extensions that cannot be ignored
url | ? | 1..1 | uri | Logical URI to reference this value set (globally unique)
identifier | ? | 0..* | Identifier | Additional identifier for the value set
version | ? | 1..1 | string | Business version of the value set
name | ? | 1..1 | string | Name for this value set (computer friendly)
title | ? | 0..1 | string | Name for this value set (human friendly)
status | ?!? | 1..1 | code | draft | active | retired | unknown Binding: PublicationStatus (required)
experimental | ?!? | 1..1 | boolean | For testing purposes, not real usage
date | ? | 0..1 | dateTime | Date this was last changed
publisher | ? | 1..1 | string | Name of the publisher (organization or individual)
contact | ? | 0..* | ContactDetail | Contact details for the publisher
description | | 1..1 | markdown | Natural language description of the value set
useContext | ? | 0..* | UsageContext | Context the content is intended to support
jurisdiction | ? | 0..* | CodeableConcept | Intended jurisdiction for value set (if applicable) Binding: Jurisdiction ValueSet (extensible)
immutable | ? | 0..1 | boolean | Indicates whether or not any change to the content logical definition may occur
purpose | | 0..1 | markdown | Why this value set is defined
copyright | | 0..1 | markdown | Use and/or publishing restrictions
extensible | ? | 0..1 | boolean | Whether this is intended to be used with an extensible binding
compose | I | 0..1 | BackboneElement | Definition of the content of the value set (CLD)
id | | 0..1 | string | xml:id (or equivalent in JSON)
extension | | 0..* | Extension | Additional Content defined by implementations
modifierExtension | ?!? | 0..* | Extension | Extensions that cannot be ignored
lockedDate | ? | 0..1 | date | Fixed date for version-less references (transitive)
inactive | ? | 0..1 | boolean | Whether inactive codes are in the value set
include | ?I | 1..* | BackboneElement | Include one or more codes from a code system or other value set(s) vsd-2: A value set with concepts or filters SHALL include a system vsd-3: Cannot have both concept and filter vsd-1: A value set include/exclude SHALL have a value set or a system
id | | 0..1 | string | xml:id (or equivalent in JSON)
extension | | 0..* | Extension | Additional Content defined by implementations
modifierExtension | ?!? | 0..* | Extension | Extensions that cannot be ignored
system | ?I | 0..1 | uri | The system the codes come from
version | ? | 0..1 | string | Specific version of the code system referred to
concept | I | 0..* | BackboneElement | A concept defined in the system
id | | 0..1 | string | xml:id (or equivalent in JSON)
extension | | 0..* | Extension | Additional Content defined by implementations
modifierExtension | ?!? | 0..* | Extension | Extensions that cannot be ignored
code | | 1..1 | code | Code or expression from system
display | | 0..1 | string | Text to display for this code for this value set in this valueset
designation | I | 0..* | BackboneElement | Additional representations for this concept
id | | 0..1 | string | xml:id (or equivalent in JSON)
extension | | 0..* | Extension | Additional Content defined by implementations
modifierExtension | ?!? | 0..* | Extension | Extensions that cannot be ignored
language | | 0..1 | code | Human language of the designation Binding: Common Languages (extensible)
use | | 0..1 | Coding | Details how this designation would be used Binding: Designation Use (extensible)
value | | 1..1 | string | The text value for this designation
filter | ?!?I | 0..* | BackboneElement | Select codes/concepts by their properties (including relationships)
id | | 0..1 | string | xml:id (or equivalent in JSON)
extension | | 0..* | Extension | Additional Content defined by implementations
modifierExtension | ?!? | 0..* | Extension | Extensions that cannot be ignored
property | ? | 1..1 | code | A property defined by the code system
op | ? | 1..1 | code | = | is-a | descendent-of | is-not-a | regex | in | not-in | generalizes | exists Binding: FilterOperator (required)
value | ? | 1..1 | code | Code from the system, or regex criteria, or boolean value for exists
valueSet | ?I | 0..* | uri | Select only contents included in this value set
exclude | I | 0..* | | Unknown reference to #ValueSet.compose.include Explicitly exclude codes from a code system or other value sets
expansion | I | 0..1 | BackboneElement | Used when the value set is "expanded"
id | | 0..1 | string | xml:id (or equivalent in JSON)
extension | | 0..* | Extension | Additional Content defined by implementations
modifierExtension | ?!? | 0..* | Extension | Extensions that cannot be ignored
identifier | | 1..1 | uri | Uniquely identifies this expansion
timestamp | | 1..1 | dateTime | Time ValueSet expansion happened
total | | 0..1 | integer | Total number of codes in the expansion
offset | | 0..1 | integer | Offset at which this resource starts
parameter | I | 0..* | BackboneElement | Parameter that controlled the expansion process
id | | 0..1 | string | xml:id (or equivalent in JSON)
extension | | 0..* | Extension | Additional Content defined by implementations
modifierExtension | ?!? | 0..* | Extension | Extensions that cannot be ignored
name | | 1..1 | string | Name as assigned by the server
value[x] | | 0..1 | string, boolean, integer, decimal, uri, code | Value of the named parameter
contains | I | 0..* | BackboneElement | Codes in the value set vsd-6: SHALL have a code or a display vsd-9: Must have a code if not abstract vsd-10: Must have a system if a code is present

id | | 0..1 | string | xml:id (or equivalent in JSON)
extension | | 0..* | Extension | Additional Content defined by implementations
modifierExtension | ?!? | 0..* | Extension | Extensions that cannot be ignored
system | | 0..1 | uri | System value for the code
abstract | | 0..1 | boolean | If user cannot select this entry
inactive | | 0..1 | boolean | If concept is inactive in the code system
version | | 0..1 | string | Version in which this code/display is defined
code | I | 0..1 | code | Code - if blank, this is not a selectable code
display | I | 0..1 | string | User display for the concept
designation | | 0..* | | Unknown reference to #ValueSet.compose.include.concept.designation Additional representations for this item
contains | | 0..* | | Unknown reference to #ValueSet.expansion.contains Codes contained under this entry
Documentation for this format

XML Template

```
<!-- Shareable ValueSet -->

<ValueSet xmlns="http://hl7.org/fhir"
>
  <!-- from Element: extension -->
 <id value="[id]"/><!-- 0..1 Logical id of this artifact -->
 <meta><!-- 0..1 Meta Metadata about the resource --></meta>
 <implicitRules value="[uri]"/><!-- 0..1 A set of rules under which this content was created -->
 <language value="[code]"/><!-- 0..1 Language of the resource content  -->
 <text><!-- 0..1 Narrative
     Text summary of the resource, for human interpretation --></text>
 <contained><!-- 0..* Resource Contained, inline Resources --></contained>
 <modifierExtension><!-- 0..* Extension  Extensions that cannot be ignored  --></modifierExtension>
 <url value="[uri]"/><!-- 1..1 Logical URI to reference this value set (globally unique) -->
 <identifier><!-- 0..* Identifier
     Additional identifier for the value set --></identifier>
 <version value="[string]"/><!-- 1..1 Business version of the value set -->
 <name value="[string]"/><!-- 1..1 Name for this value set (computer friendly) -->
 <title value="[string]"/><!-- 0..1 Name for this value set (human friendly) -->
 <status value="[code]"/><!-- 1..1 draft | active | retired | unknown  -->
 <experimental value="[boolean]"/><!-- 1..1 For testing purposes, not real usage -->
 <date value="[dateTime]"/><!-- 0..1 Date this was last changed -->
 <publisher value="[string]"/><!-- 1..1 Name of the publisher (organization or individual) -->
 <contact><!-- 0..* ContactDetail Contact details for the publisher --></contact>
 <description value="[markdown]"/><!-- 1..1 Natural language description of the value set -->
 <useContext><!-- 0..* UsageContext
     Context the content is intended to support --></useContext>
 <jurisdiction><!-- 0..* CodeableConcept Intended jurisdiction for value set (if applicable)  --></jurisdiction>
 <immutable value="[boolean]"/><!-- 0..1 Indicates whether or not any change to the content logical definition may occur
     -->
 <purpose value="[markdown]"/><!-- 0..1 Why this value set is defined -->
 <copyright value="[markdown]"/><!-- 0..1 Use and/or publishing restrictions -->
 <extensible value="[boolean]"/><!-- 0..1 Whether this is intended to be used with an extensible binding -->
 <compose>  0..1 BackboneElement  <!--  0..1 Definition of the content of the value set (CLD) -->
  <modifierExtension><!-- 0..* Extension  Extensions that cannot be ignored  --></modifierExtension>
  <lockedDate value="[date]"/><!-- 0..1 Fixed date for version-less references (transitive) -->
  <inactive value="[boolean]"/><!-- 0..1 Whether inactive codes are in the value set -->
  <include>  1..* BackboneElement  <!--  1..* Include one or more codes from a code system or other value set(s) -->
   <modifierExtension><!-- 0..* Extension  Extensions that cannot be ignored  --></modifierExtension>
   <system value="[uri]"/><!-- 0..1 The system the codes come from -->
   <version value="[string]"/><!-- 0..1 Specific version of the code system referred to -->
   <concept>  0..* BackboneElement  <!--  0..* A concept defined in the system -->
    <modifierExtension><!-- 0..* Extension  Extensions that cannot be ignored  --></modifierExtension>
    <code value="[code]"/><!-- 1..1 Code or expression from system -->
    <display value="[string]"/><!-- 0..1
        Text to display for this code for this value set in this valueset -->
    <designation>  0..* BackboneElement  <!--  0..* Additional representations for this concept -->
     <modifierExtension><!-- 0..*
       Extension  Extensions that cannot be ignored  --></modifierExtension>
     <language value="[code]"/><!-- 0..1 Human language of the designation  -->
     <use><!-- 0..1 Coding Details how this designation would be used  --></use>
     <value value="[string]"/><!-- 1..1 The text value for this designation -->
    </designation>
   </concept>
   <filter>  0..* BackboneElement  <!--  0..* Select codes/concepts by their properties (including relationships) -->
    <modifierExtension><!-- 0..* Extension  Extensions that cannot be ignored  --></modifierExtension>
    <property value="[code]"/><!-- 1..1 A property defined by the code system -->
    <op value="[code]"/><!-- 1..1 = | is-a | descendent-of | is-not-a | regex | in | not-in | generalizes | exists  -->
    <value value="[code]"/><!-- 1..1
        Code from the system, or regex criteria, or boolean value for exists -->
   </filter>
   <valueSet value="[uri]"/><!-- 0..* Select only contents included in this value set -->
  </include>
  <exclude><!-- See #ValueSet.compose.include  Explicitly exclude codes from a code system or other value sets
    --></exclude>
 </compose>
 <expansion>  0..1 BackboneElement  <!--  0..1 Used when the value set is "expanded" -->
  <modifierExtension><!-- 0..* Extension  Extensions that cannot be ignored  --></modifierExtension>
  <identifier value="[uri]"/><!-- 1..1 Uniquely identifies this expansion -->
  <timestamp value="[dateTime]"/><!-- 1..1 Time ValueSet expansion happened -->
  <total value="[integer]"/><!-- 0..1 Total number of codes in the expansion -->
  <offset value="[integer]"/><!-- 0..1 Offset at which this resource starts -->
```

```
  <parameter>  0..* BackboneElement  <!--  0..* Parameter that controlled the expansion process -->
   <modifierExtension><!-- 0..* Extension  Extensions that cannot be ignored  --></modifierExtension>
   <name value="[string]"/><!-- 1..1 Name as assigned by the server -->
   <value[x]><!-- 0..1 string|boolean|integer|
     decimal|uri|code Value of the named parameter --></value[x]>
  </parameter>
  <contains>  0..* BackboneElement  <!--  0..* Codes in the value set -->
   <modifierExtension><!-- 0..* Extension  Extensions that cannot be ignored  --></modifierExtension>
   <system value="[uri]"/><!-- 0..1 System value for the code -->
   <abstract value="[boolean]"/><!-- 0..1 If user cannot select this entry -->
   <inactive value="[boolean]"/><!-- 0..1 If concept is inactive in the code system -->
   <version value="[string]"/><!-- 0..1 Version in which this code/display is defined -->
   <code value="[code]"/><!-- 0..1 Code - if blank, this is not a selectable code -->
   <display value="[string]"/><!-- 0..1 User display for the concept -->
   <designation><!-- See #ValueSet.compose.include.concept.designation  Additional representations for this item
    --></designation>
   <contains><!-- See #ValueSet.expansion.contains  Codes contained under this entry --></contains>
  </contains>
 </expansion>
</ValueSet>
```

JSON Template

```
{ // Shareable ValueSet
  // from Element: extension
    "meta" : { Meta }, //Metadata about the resource
    "implicitRules" : "<uri>", //A set of rules under which this content was created
    "language" : "<code>", //Language of the resource content
    "text" : { Narrative }, //Text summary of the resource, for human interpretation
    "contained" : [{ Resource }], //Contained, inline Resources
    "modifierExtension" : [{ Extension }], //Extensions that cannot be ignored
    "url" : "<uri>", // R! Logical URI to reference this value set (globally unique)
    "identifier" : [{ Identifier }], //Additional identifier for the value set
    "version" : "<string>", // R! Business version of the value set
    "name" : "<string>", // R! Name for this value set (computer friendly)
    "title" : "<string>", //Name for this value set (human friendly)
    "status" : "<code>", // R! draft | active | retired | unknown
    "experimental" : <boolean>, // R! For testing purposes, not real usage
    "date" : "<dateTime>", //Date this was last changed
    "publisher" : "<string>", // R! Name of the publisher (organization or individual)
    "contact" : [{ ContactDetail }], //Contact details for the publisher
    "description" : "<markdown>", // R! Natural language description of the value set
    "useContext" : [{ UsageContext }], //Context the content is intended to support
    "jurisdiction" : [{ CodeableConcept }], //Intended jurisdiction for value set (if applicable)
    "immutable" : <boolean>, //Indicates whether or not any change to the content logical definition may occur
    "purpose" : "<markdown>", //Why this value set is defined
    "copyright" : "<markdown>", //Use and/or publishing restrictions
    "extensible" : <boolean>, //Whether this is intended to be used with an extensible binding
    "compose" : { BackboneElement }, // C?Definition of the content of the value set (CLD)
    "expansion" : { BackboneElement } // C?Used when the value set is "expanded"
  }
```

Other representations of profile: Schematron

4.8.15.2.2 Terminology Bindings

Path | Name | Conformance | ValueSet

ValueSet.language | Common Languages | extensible | Common Languages

ValueSet.status | PublicationStatus | required | PublicationStatus

ValueSet.jurisdiction | Jurisdiction ValueSet | extensible | Jurisdiction ValueSet

ValueSet.compose.include.concept.designation.language | Common Languages | extensible | Common Languages

ValueSet.compose.include.concept.designation.use | Designation Use | extensible | Designation Use

ValueSet.compose.include.filter.op | FilterOperator | required | FilterOperator

4.8.15.2.3 Constraints

Id | Path | Details | Requirements

vsd-2 | ValueSet.compose.include | A value set with concepts or filters SHALL include a system Expression : (concept.exists() or filter.exists()) implies system.exists()

vsd-3 | ValueSet.compose.include | Cannot have both concept and filter Expression : concept.empty() or filter.empty()

vsd-1 | ValueSet.compose.include | A value set include/exclude SHALL have a value set or a system Expression : valueSet.exists() or system.exists()

vsd-6 | ValueSet.expansion.contains | SHALL have a code or a display Expression : code.exists() or display.exists()

vsd-9 | ValueSet.expansion.contains | Must have a code if not abstract Expression : code.exists() or abstract = true

vsd-10 | ValueSet.expansion.contains | Must have a system if a code is present Expression : code.empty() or system.exists()

4.8.16 Resource ValueSet - Operations

URL: https://hl7.org/fhir/STU3/valueset-operations.html

This page is part of the FHIR Specification (v3.0.2: STU 3). The current version which supercedes this version is 4.0.1. For a full list of available versions, see the Directory of published versions

4.8.16 Resource ValueSet - Operations

Vocabulary Work Group | Maturity Level: 5 | Trial Use | Compartments: Not linked to any defined compartments

This resource has 2 operations associated with it:

$expand | Value Set Expansion
$validate-code | Value Set based Validation

For more information about operations, including how they are invoked, see Operations.

4.8.16.1 Value Set Expansion

The definition of a value set is used to create a simple collection of codes suitable for use for data entry or validation. If the operation is not called at the instance level, one of the in parameters identifier, context or valueset must be provided. An expanded value set will be returned, or an OperationOutcome with an error message.

The official URL for this operation definition is

```
http://hl7.org/fhir/OperationDefinition/ValueSet-expand
```

Formal Definition (as a OperationDefinition).

URL: [base]/ValueSet/$expand

URL: [base]/ValueSet/[id]/$expand

This is an idempotent operation

In Parameters:

Name | Cardinality | Type | Binding | Profile | Documentation
url | 0..1 | uri | | | A canonical url for a value set. The server must know the value set (e.g. it is defined explicitly in the server's value sets, or it is defined implicitly by some code system known to the server
valueSet | 0..1 | ValueSet | | | The value set is provided directly as part of the request. Servers may choose not to accept value sets in this fashion
context | 0..1 | uri | | | The context of the value set, so that the server can resolve this to a value set to expand. The recommended format for this URI is [Structure Definition URL]#[name or path into structure definition] e.g. http://hl7.org/fhir/StructureDefinition/observation-hspc-height-hspcheight#Observation.interpretation. Other forms may be used but are not defined. This form is only usable if the terminology server also has access to the profile registry that the server is using, but can be used to delegate the mapping from an application context to a binding at run-time
filter | 0..1 | string | | | A text filter that is applied to restrict the codes that are returned (this is useful in a UI context). The interpretation of this is delegated to the server in order to allow to determine the most optimal search approach for the context
profile | 0..1 | uri | | | A reference to an external definition that provides additional control information about how the expansion is performed. At this time, there is no agreed format or functionality for the target of this URI. The VSAC Documentation provides one example of the use of this parameter. Implementers using this element will need to agree on an appropriate mechanism for use within their interoperability community. Known uses for profile include: * whether to return the value set content logical definition with the expansion * whether to include inactive concepts
date | 0..1 | dateTime | | | The date for which the expansion should be generated. if a date is provided, it means that the server should use the value set / code system definitions as they were on the given date, or return an error if this is not possible. Normally, the date is the current conditions (which is the default value) but under some circumstances, systems need to generate an expansion as it would have been in the past. A typical example of this would be where code selection is constrained to the set of codes that were available when the patient was treated, not when the record is being edited. Note that which date is appropriate is a matter for implementation policy.
offset | 0..1 | integer | | | Paging support - where to start if a subset is desired (default = 0). Offset is number of records (not number of pages)
count | 0..1 | integer | | | Paging support - how many codes should be provided in a partial page view. Paging only applies to flat expansions - servers ignore paging if the expansion is not flat. If count = 0, the client is asking how large the expansion is. Servers SHOULD honor this request for hierarchical expansions as well, and simply return the overall count
includeDesignations | 0..1 | boolean | | | Controls whether concept designations are to be included or excluded in value set expansions. Overrides the value in the expansion profile if there is one
includeDefinition | 0..1 | boolean | | | Controls whether the value set definition is included or excluded in value set expansions. Overrides the value in the expansion profile if there is one
activeOnly | 0..1 | boolean | | | Controls whether inactive concepts are included or excluded in value set expansions. Overrides the value in the expansion profile if there is one. Note that if the value set explicitly specifies that inactive codes are included, this parameter can still remove them from a specific expansion, but this parameter cannot include them if the value set excludes them
excludeNested | 0..1 | boolean | | | Controls whether or not the value set expansion nests codes or not (i.e. ValueSet.expansion.contains.contains). Overrides the value in the expansion profile if there is one
excludeNotForUI | 0..1 | boolean | | | Controls whether or not the value set expansion includes codes which cannot be displayed in user interfaces. Overrides the value in the expansion profile if there is one
excludePostCoordinated | 0..1 | boolean | | | Controls whether or not the value set expansion includes post coordinated codes. Overrides the value in the expansion profile if there is one
displayLanguage | 0..1 | code | | | Specifies the language to be used for description in the expansions i.e. the language to be used for ValueSet.expansion.contains.display. Overrides the value in the expansion profile if there is one
limitedExpansion | 0..1 | boolean | | | If the value set being expanded is incomplete (because it is too big to expand), return a limited expansion (a subset) with an indicator that expansion is incomplete. Overrides the value in the expansion profile if there is one

Out Parameters:

Name | Cardinality | Type | Binding | Profile | Documentation
return | 1..1 | ValueSet | | | The result of the expansion Note: as this the only out parameter, it is a resource, and it has the name 'return', the result of this operation is returned directly as a resource

The value set expansion returned by this query should be treated as a transient result that will change over time (whether it does or not depends on how the value set is specified), so applications should repeat the operation each time the value set is used.

If the expansion is too large (at the discretion of the server), the server will return an error (OperationOutcome with code too-costly). Clients can work through large flat expansions in a set of pages (partial views of the full expansion) instead of just getting the full expansion in a single exchange by using offset and count parameters. Servers are not obliged to support paging, but if they do, SHALL support both the offset and count parameters. Hierarchical expansions are not subject to paging and servers simply return the entire expansion.

Different servers may return different results from expanding a value set for the following reasons:

* The underlying code systems are different (e.g. different versions, possibly with different defined behavior)

* The server optimizes filter includes differently, such as sorting by code frequency

* Servers introduce arbitrary groups to assist a user to navigate the lists based either on extensions in the definition, or additional knowledge available to the server

When a server cannot correctly expand a value set because it does not fully understand the code systems (e.g. it has the wrong version, or incomplete definitions) then it SHALL return an error. If the value set itself is unbounded due to the inclusion of post-coordinated value sets (e.g. SNOMED CT, UCUM), then the extension http://hl7.org/fhir/StructureDefinition/valueset-unclosed can be used to indicate that the expansion is incomplete

4.8.16.1.1 Examples

Expanding a value set that is already registered on the server as "23", with a text filter of "abdo" (Request):

```
GET [base]/ValueSet/23/$expand?filter=abdo
```

Expanding a value set that is specififed by the client (using JSON) (Request):

```
POST [base]/ValueSet/23/$expand
[other headers]

{
  "resourceType" : "Parameters",
  "parameter" : [
     {
     "name" : "valueSet",
     "resource" : {
       "resourceType" : "ValueSet",
     [value set details]
     }
   }
  ]
}
```

Response:

```
HTTP/1.1 200 OK
[other headers]

<ValueSet xmlns="http://hl7.org/fhir">
  <!-- the server SHOULD populate the id with a newly created UUID
    so clients can easily track a particular expansion  -->
  <id value="43770626-f685-4ba8-8d66-fb63e674c467"/>
  <!-- no need for meta, though it is allowed for security labels, profiles -->

  <!-- other value set details -->
  <expansion>
    <!-- when expanded -->
    <timestamp value="20141203T08:50:00+11:00"/>
  <contains>
    <!-- expansion contents -->
  </contains>
  </expansion>
</ValueSet>
```

4.8.16.2 Value Set based Validation

Validate that a coded value is in the set of codes allowed by a value set. If the operation is not called at the instance level, one of the in parameters "identifier" or "valueset" must be provided. One (and only one) of the in parameters (code, coding, codeableConcept) must be provided. The operation returns a result (true / false), an error message, and the recommended display for the code

The official URL for this operation definition is

```
http://hl7.org/fhir/OperationDefinition/ValueSet-validate-code
```

Formal Definition (as a OperationDefinition).

URL: [base]/ValueSet/$validate-code

URL: [base]/ValueSet/[id]/$validate-code

This is an idempotent operation

In Parameters:

Name | Cardinality | Type | Binding | Profile | Documentation

url | 0..1 | uri | | | Value set Canonical URL. The server must know the value set (e.g. it is defined explicitly in the server's value sets, or it is defined implicitly by some code system known to the server

context | 0..1 | uri | | | The context of the value set, so that the server can resolve this to a value set to validate against. The recommended format for this URI is [Structure Definition URL]#[name or path into structure definition] e.g. http://hl7.org/fhir/StructureDefinition/observation-hspc-height-hspcheight#Observation.interpretation. Other forms may be used but are not defined. This form is only usable if the terminology server also has access to the profile registry that the server is using, but can be used to delegate the mapping from an application context to a binding at run-time

valueSet | 0..1 | ValueSet | | | The value set is provided directly as part of the request. Servers may choose not to accept value sets in this fashion. This parameter is used when the client wants the server to expand a value set that is not stored on the server

code | 0..1 | code | | | The code that is to be validated. If a code is provided, a system must be provided

system | 0..1 | uri | | | The system for the code that is to be validated

version | 0..1 | string | | | The version of the system, if one was provided in the source data

display | 0..1 | string | | | The display associated with the code, if provided. If a display is provided a code must be provided. If no display is provided, the server cannot validate the display value, but may choose to return a recommended display name in an extension in the outcome. Whether displays are case sensitive is code system dependent

coding | 0..1 | Coding | | | A coding to validate

codeableConcept | 0..1 | CodeableConcept | | | A full codeableConcept to validate. The server returns true if one of the coding values is in the value set, and may also validate that the codings are not in conflict with each other if more than one is present

date | 0..1 | dateTime | | | The date for which the validation should be checked. Normally, this is the current conditions (which is the default values) but under some circumstances, systems need to validate that a correct code was used at some point in the past. A typical example of this would be where code selection is constrained to the set of codes that were available when the patient was treated, not when the record is being edited. Note that which date is appropriate is a matter for implementation policy.

abstract | 0..1 | boolean | | | if true, then an abstract code is allowed to be used in the context of the code that is being validated. Typically, abstract codes are allowed to be used in value set specifications (e.g. any code that is subsumed by an abstract code). If false (which is the default value), then only concrete codes as defined by the value set are allowed

displayLanguage | 0..1 | code | | | Specifies the language to be used for description when validating the display property

Out Parameters:

Name | Cardinality | Type | Binding | Profile | Documentation

result | 1..1 | boolean | | | True if the concept details supplied are valid

message | 0..1 | string | | | Error details, if result = false. If this is provided when result = true, the message carries hints and warnings

display | 0..1 | string | | | A valid display for the concept if the system wishes to display this to a user

4.8.16.2.1 Examples

Simple validation of a code/system against a known value set (Request):

```
GET [base]/ValueSet/23/$validate-code?system=http://loinc.org&code=1963-8&display=test
```

Validate a CodeableConcept against a client specified value set (Request):

```
POST [base]/ValueSet/$validate-code
[other headers]

{
  "ResourceType" : "Parameters",
  "parameter" : [
    {
    "name" : "coding",
    "valueCodeableConcept" : {
      "coding" : {
        "system" : "http://loinc.org",
          "code" : "1963-8",
      "display" : "test"
      }
    }
  },
  {
    "name" : "valueSet",
    "resource": {
      "resourceType" : "ValueSet",
    [etc]
    }
  }
  ]
}
```

Test whether a Snomed Concept 399211009 (History of myocardial infarction) is subsumed by 22298006 (Myocardial infarction) (Request):

```
GET [base]/ValueSet/$validate-
    code?system=http://snomed.info/sct&code=399211009&identifier=http://snomed.info/sct?fhir_vs%3Disa/22298006
```

Response:

```
HTTP/1.1 200 OK
[other headers]

{
  "resourceType" : "Parameters",
  "parameter" : [
    {
    "name" : "result",
    "valueBoolean" : "false"
  },
  {
    "name" : "message",
    "valueString" : "The display \"test\" is incorrect"
  },
  {
    "name" : "display",
    "valueString" : "Bicarbonate [Moles/volume] in Serum"
  }
  ]
}
```

4.8.17 Resource ValueSet - Detailed Descriptions

This page is part of the FHIR Specification (v3.0.2: STU 3). The current version which supercedes this version is 4.0.1. For a full list of available versions, see the Directory of published versions

4.8.17 Resource ValueSet - Detailed Descriptions

Vocabulary Work Group | Maturity Level: N/A | Ballot Status: Informative | Compartments: Not linked to any defined compartments

R2 : R3 Converson maps for ValueSet.

Functional status for this map: 11 tests that all execute ok. 5 fail round-trip testing and 4 r3 resources are invalid (4 errors). (see documentation)

4.8.17.1 R2 to R3

```
map "http://hl7.org/fhir/StructureMap/ValueSet2to3" = "R2 to R3 Conversions for ValueSet"

uses "http://hl7.org/fhir/DSTU2/StructureDefinition/ValueSet" alias ValueSetR2 as source
uses "http://hl7.org/fhir/StructureDefinition/ValueSet" alias ValueSet as target

imports "http://hl7.org/fhir/StructureMap/*2to3"

group for type+types  ValueSet extends DomainResource
  input src : ValueSetR2 as source
  input tgt : ValueSet as target

  "ValueSet-url" : for src.url make tgt.url
  "ValueSet-identifier" : for src.identifier make tgt.identifier
  "ValueSet-version" : for src.version make tgt.version
  "ValueSet-name" : for src.name make tgt.name
  "ValueSet-status" : for src.status make tgt.status
  "ValueSet-experimental" : for src.experimental make tgt.experimental
  "ValueSet-publisher" : for src.publisher make tgt.publisher
  "ValueSet-contact" : for src.contact as vs0 make tgt.contact as vt0 then {
    "ContactDetail-name" : for vs0.name make vt0.name
    "ContactDetail-telecom" : for vs0.telecom make vt0.telecom
  }

  "ValueSet-date" : for src.date make tgt.date
  "ValueSet-description" : for src.description make tgt.description
  "ValueSet-purpose" : for src.requirements make tgt.purpose
  "ValueSet-copyright" : for src.copyright make tgt.copyright
  "ValueSet-jurisdiction" : for src.useContext where coding.system = 'urn:iso:std:iso:3166' make tgt.jurisdiction
  "ValueSet-useContext" : for src.useContext as vs where (coding.system = 'urn:iso:std:iso:3166').not() make
    tgt.useContext as uc,  uc.code as ucc,  ucc.system = "http://hl7.org/fhir/usage-context-type",  ucc.code = "task",
    uc.value as vt then CodeableConcept(vs, vt)

  "ValueSet-immutable" : for src.immutable make tgt.immutable
  "ValueSet-extensible" : for src.extensible make tgt.extensible
  "ValueSet-codeSystem" : for src.codeSystem as vs0 make create("CodeSystem") as vt0 then codeSystem(src, tgt, vs0, vt0)
  "ValueSet-compose" : for src.compose as vs0 make tgt.compose as vt0 then compose(src, vs0, vt0)
  "ValueSet-expansion" : for src.expansion as vs0 make tgt.expansion as vt0 then expansion(vs0, vt0)
endgroup

group codeSystem extends Element
  input vs as source
  input vstgt as target
  input src as source
  input tgt as target

  "CodeSystem-modifierExtension" : for src.modifierExtension make tgt.modifierExtension
  "CodeSystem-reference": for src.system as v make vstgt.compose as c, c.include as i, i.system = v
  "CodeSystem-text" : for vs.text make tgt.text
  "CodeSystem-url" : for src.system make tgt.url
  "CodeSystem-identifier" : for vs.identifier make tgt.identifier // not sure whether it's right to copy the identifier?
  "CodeSystem-version" : for src.version make tgt.version
  "CodeSystem-name" : for vs.name make tgt.name
  "CodeSystem-status" : for vs.status make tgt.status
  "CodeSystem-experimental" : for vs.experimental make tgt.experimental
  "CodeSystem-publisher" : for vs.publisher make tgt.publisher
  "CodeSystem-contact" : for vs.contact as vs0 make tgt.contact as vt0 then {
    "ContactDetail-name" : for vs0.name make vt0.name
    "ContactDetail-telecom" : for vs0.telecom make vt0.telecom
  }
  "CodeSystem-abstract" : for vs where codeSystem.descendants().abstract make tgt.property as p, p.code =
    'notSelectable', p.uri = 'http://todo', p.description = 'Indicates that the code is abstract - only intended to be
    used as a selector for other concepts'
  "CodeSystem-date" : for vs.date make tgt.date
  "CodeSystem-description" : for vs.description make tgt.description
  "CodeSystem-jurisdiction" : for vs.useContext where coding.system = 'urn:iso:std:iso:3166' make tgt.jurisdiction
  "CodeSystem-useContext" : for vs.useContext as vs where (coding.system = 'urn:iso:std:iso:3166').not() make
    tgt.useContext as uc,  uc.code as ucc,  ucc.system = "http://hl7.org/fhir/usage-context-type",  ucc.code = "task",
    uc.value as vt then CodeableConcept(vs, vt)
  "CodeSystem-purpose" : for vs.requirements make tgt.purpose
  "CodeSystem-copyright" : for vs.copyright make tgt.copyright
  "CodeSystem-valueSet" : for vs.url make tgt.valueSet
  "CodeSystem-caseSensitive" : for src.caseSensitive make tgt.caseSensitive
  "CodeSystem-content" : for src make tgt.content = 'complete'
  "CodeSystem-concept" : for src.concept as vs make tgt.concept as vt then csconcept(vs, vt)
```

```
endgroup

group csconcept extends BackboneElement
  input src as source
  input tgt as target

  "cs-concept-code" : for src.code make tgt.code
  "cs-concept-abstract" : for src.abstract as v make tgt.property as p, p.code = 'notSelectable', p.value = v
  "cs-concept-display" : for src.display make tgt.display
  "cs-concept-definition" : for src.definition make tgt.definition
  "cs-concept-designation" : for src.designation as vs make tgt.designation as vt then designation(vs, vt)
  "cs-concept-concept" : for src.concept as vs make tgt.concept as vt then csconcept(vs, vt)
endgroup

group compose extends BackboneElement
  input vs as source
  input src as source
  input tgt as target

  "vs-compose-ld" : for vs.lockedDate make tgt.lockedDate
  "vs-compose-imp" : for src.import as v make tgt.include as ti, ti.valueSet = v
  "vs-compose-incl" : for src.include as vs make tgt.include as vt then include(vs, vt)
  "vs-compose-excl" : for src.exclude as vs make tgt.exclude as vt then include(vs, vt)
endgroup

group include extends BackboneElement
  input src as source
  input tgt as target

  "vs-incl-system" : for src.system make tgt.system
  "vs-incl-version" : for src.version make tgt.version
  "vs-incl-concept" : for src.concept as vs make tgt.concept as vt then concept(vs, vt)
  "vs-incl-filter" : for src.filter as vs make tgt.filter as vt then filter(vs, vt)
endgroup

group concept extends BackboneElement
  input src as source
  input tgt as target

  "vs-concept-code" : for src.code make tgt.code
  "vs-concept-display" : for src.display make tgt.display
  "vs-concept-designation" : for src.designation as vs make tgt.designation as vt then designation(vs, vt)
endgroup

group designation extends BackboneElement
  input src as source
  input tgt as target

  "vs-designation-language" : for src.language make tgt.language
  "vs-designation-use" : for src.use make tgt.use
  "vs-designation-value" : for src.value make tgt.value
endgroup

group filter extends BackboneElement
  input src as source
  input tgt as target

  "vs-filter-property" : for src.property make tgt.property
  "vs-filter-op" : for src.op make tgt.op
  "vs-filter-value" : for src.value make tgt.value
endgroup

group expansion extends BackboneElement
  input src as source
  input tgt as target

  "ValueSet.expansion-identifier" : for src.identifier make tgt.identifier
  "ValueSet.expansion-timestamp" : for src.timestamp make tgt.timestamp
  "ValueSet.expansion-total" : for src.total make tgt.total
  "ValueSet.expansion-offset" : for src.offset make tgt.offset
  "ValueSet.expansion-parameter" : for src.parameter as vs make tgt.parameter as vt then parameter(vs, vt)
  "ValueSet.expansion-contains" : for src.contains as vs make tgt.contains as vt then contains(vs, vt)
endgroup

group parameter extends BackboneElement
  input src as source
  input tgt as target

  "vs-parameter-name" : for src.name make tgt.name
  "vs-parameter-value" : for src.value make tgt.value
endgroup

group contains extends BackboneElement
  input src as source
  input tgt as target

  "ValueSet.contains-system" : for src.system make tgt.system
  "ValueSet.contains-abstract" : for src.abstract make tgt.abstract
  "ValueSet.contains-version" : for src.version make tgt.version
```

```
  "ValueSet.contains-code" : for src.code make tgt.code
  "ValueSet.contains-display" : for src.display make tgt.display
  "ValueSet.contains-contains" : for src.contains as vs make tgt.contains as vt then contains(vs, vt)
endgroup
```

4.8.17.2 R3 to R2

```
map "http://hl7.org/fhir/StructureMap/ValueSet3to2" = "R3 to R2 Conversion for ValueSet"

uses "http://hl7.org/fhir/StructureDefinition/ValueSet" alias ValueSet as source
uses "http://hl7.org/fhir/DSTU2/StructureDefinition/ValueSet" alias ValueSetR2 as target

imports "http://hl7.org/fhir/StructureMap/*3to2"

group for type+types  ValueSet extends DomainResource
  input src : ValueSet as source
  input tgt : ValueSetR2 as target

  "ValueSet-url" : for src.url make tgt.url
  "ValueSet-identifier" : for src.identifier make tgt.identifier
  "ValueSet-version" : for src.version make tgt.version
  "ValueSet-name" : for src.name make tgt.name
  "ValueSet-status" : for src.status make tgt.status
  "ValueSet-experimental" : for src.experimental make tgt.experimental
  "ValueSet-publisher" : for src.publisher make tgt.publisher
  "ValueSet-contact" : for src.contact as vs0 make tgt.contact as vt0 then {
    "ValueSet.contact-name" : for vs0.name make vt0.name
    "ValueSet.contact-telecom" : for vs0.telecom make vt0.telecom
  }

  "ValueSet-date" : for src.date make tgt.date
  "ValueSet-useContext" : for src.jurisdiction make tgt.useContext
  "ValueSet-description" : for src.description make tgt.description
  "ValueSet-requirements" : for src.purpose make tgt.requirements
  "ValueSet-copyright" : for src.copyright make tgt.copyright

  "ValueSet-immutable" : for src.immutable make tgt.immutable
  "ValueSet-extensible" : for src.extensible make tgt.extensible
  "ValueSet-compose" : for src.compose as vs0 make tgt.compose as vt0 then compose(src, tgt, vs0, vt0)
  "ValueSet-expansion" : for src.expansion as vs0 make tgt.expansion as vt0 then expansion(vs0, vt0)
endgroup

group compose extends BackboneElement
  input vs as source
  input vst as target
  input src as source
  input tgt as target

  "vs-compose-ld" : for src.lockedDate make vst.lockedDate
  "vs-compose-incl-cs" : for src.include as vs where (system.exists() and valueSet.empty() and concept.empty() and
    filter.empty()) and (system.resolve().valueSet = vs.url)
    make vst.codeSystem as vt, (vs.system.resolve()) as cs then codeSystem(cs, vt)

  "vs-compose-incl" : for src.include as vs where ((system.exists() and valueSet.empty() and concept.empty() and
    filter.empty()) and (system.resolve().valueSet = vs.url)).not() make tgt.include as vt then include(vs, vt, tgt)
  "vs-compose-excl" : for src.exclude as vs check valueSet.empty() make tgt.exclude as vt then include(vs, vt, tgt)
endgroup

group codeSystem extends Element // choice of Element is deliberate here; avoid all other resource overhead
  input src as source
  input tgt as target

  "CodeSystem-modifierExtension" : for src.modifierExtension make tgt.modifierExtension
  "CodeSystem-system" : for src.url make tgt.system
  "CodeSystem-version" : for src.version make tgt.version
  "CodeSystem-caseSensitive" : for src.caseSensitive make tgt.caseSensitive
  "CodeSystem-concept" : for src.concept as vs make tgt.concept as vt then csconcept(vs, vt)
endgroup

group csconcept extends BackboneElement
  input src as source
  input tgt as target

  "cs-concept-code" : for src.code make tgt.code
  "cs-concept-abstract" : for src where property.where(code = 'notSelectable') make tgt.abstract =
    (src.property.where(code = 'notSelectable').value)
  "cs-concept-display" : for src.display make tgt.display
  "cs-concept-definition" : for src.definition make tgt.definition
  "cs-concept-designation" : for src.designation as vs make tgt.designation as vt then designation(vs, vt)
  "cs-concept-concept" : for src.concept as vs make tgt.concept as vt then csconcept(vs, vt)
endgroup

group include extends BackboneElement
  input src as source
  input tgt as target
  input comp as target

  "vs-incl-valueSet" : for src.valueSet make comp.import
  "vs-incl-system" : for src.system make tgt.system
  "vs-incl-version" : for src.version make tgt.version
```

```
  "vs-incl-concept" : for src.concept as vs make tgt.concept as vt then concept(vs, vt)
  "vs-incl-filter" : for src.filter as vs make tgt.filter as vt then filter(vs, vt)
endgroup

group concept extends BackboneElement
  input src as source
  input tgt as target

  "vs-concept-code" : for src.code make tgt.code
  "vs-concept-display" : for src.display make tgt.display
  "vs-concept-designation" : for src.designation as vs make tgt.designation as vt then designation(vs, vt)
endgroup

group designation extends BackboneElement
  input src as source
  input tgt as target

  "vs-designation-language" : for src.language make tgt.language
  "vs-designation-use" : for src.use make tgt.use
  "vs-designation-value" : for src.value make tgt.value
endgroup

group filter extends BackboneElement
  input src as source
  input tgt as target

  "vs-filter-property" : for src.property make tgt.property
  "vs-filter-op" : for src.op make tgt.op
  "vs-filter-value" : for src.value make tgt.value
endgroup

group expansion extends BackboneElement
  input src as source
  input tgt as target

  "ValueSet.expansion-identifier" : for src.identifier make tgt.identifier
  "ValueSet.expansion-timestamp" : for src.timestamp make tgt.timestamp
  "ValueSet.expansion-total" : for src.total make tgt.total
  "ValueSet.expansion-offset" : for src.offset make tgt.offset
  "ValueSet.expansion-parameter" : for src.parameter as vs make tgt.parameter as vt then parameter(vs, vt)
  "ValueSet.expansion-contains" : for src.contains as vs make tgt.contains as vt then contains(vs, vt)
endgroup

group parameter extends BackboneElement
  input src as source
  input tgt as target

  "vs-parameter-name" : for src.name make tgt.name
  "vs-parameter-value" : for src.value make tgt.value
endgroup

group contains extends BackboneElement
  input src as source
  input tgt as target

  "ValueSet.contains-system" : for src.system make tgt.system
  "ValueSet.contains-abstract" : for src.abstract make tgt.abstract
  "ValueSet.contains-version" : for src.version make tgt.version
  "ValueSet.contains-code" : for src.code make tgt.code
  "ValueSet.contains-display" : for src.display make tgt.display
  "ValueSet.contains-contains" : for src.contains as vs make tgt.contains as vt then contains(vs, vt)
endgroup
```

4.8.17.3 R3 Validation Errors

example-extensional | WARNING @ ValueSet.meta.profile[0]: StructureDefinition reference "http://hl7.org/fhir/StructureDefinition/valueset-shareable-definition" could not be resolved (src = InstanceValidator)
example-expansion | WARNING @ ValueSet.meta.profile[0]: StructureDefinition reference "http://hl7.org/fhir/StructureDefinition/valueset-shareable-definition" could not be resolved (src = InstanceValidator)
example-inline | WARNING @ ValueSet.meta.profile[0]: StructureDefinition reference "http://hl7.org/fhir/StructureDefinition/valueset-shareable-definition" could not be resolved (src = InstanceValidator)
example-intensional | WARNING @ ValueSet.meta.profile[0]: StructureDefinition reference "http://hl7.org/fhir/StructureDefinition/valueset-shareable-definition" could not be resolved (src = InstanceValidator)

4.9 Resource ConceptMap - Content

URL: https://hl7.org/fhir/STU3/conceptmap.html

This page is part of the FHIR Specification (v3.0.2: STU 3). The current version which supercedes this version is 4.0.1. For a full list of available versions, see the Directory of published versions

Vocabulary Work Group | Maturity Level: 3 | Trial Use | Compartments: Not linked to any defined compartments

A statement of relationships from one set of concepts to one or more other concepts - either code systems or data elements, or classes in class models.

4.9.1 Scope and Usage

A concept map defines a mapping from a set of concepts defined in a code system to one or more concepts defined in other code systems. Mappings are one way - from the source to the destination. In many cases, the reverse mappings are valid, but this cannot be assumed to be the case.

Mappings between code systems are only defined in the context of the specified source and destination value sets - they are specific to a particular context of use. The mappings may be useful in other contexts, but this must be determined based on the context of use and meaning; it cannot be taken for granted automatically. Note that all code systems have value sets that include the entire code system, and these value sets can be used for mappings that are valid in all contexts.

Each mapping for a concept from source to target includes an equivalence property that specifies how similar the mapping is (or, in some cases, that there is no valid mapping). There is one element for each concept or field in the source that needs to be mapped. Each source concept may have multiple targets:

* because there are multiple possible mappings (e.g., ambiguous)

* to specify a correct map, and specify other mappings as invalid

* when there are multiple mappings depending on the values of other elements (dependsOn)

There SHOULD be at least one target for each element, but some incomplete concept maps may not have a target for each concept.

4.9.2 Boundaries and Relationships

While ConceptMap resources are not referred to directly from any other resource, they may be included and used in ImplementationGuide resources, and provide background knowledge that is in many contexts, including operations defined in this specification.

In addition to ConceptMap, there is also the StructureMap resource. The ConceptMap resource defines relationships between concepts in their own right, along with grading of their equivalencies, while the StructureMap defines an exectuable transform for instances that conform to a known structure.

4.9.3 Background and Context

Further discussion of the issues involved in mapping between concept definition systems can be found in the HL7 v3 Core Principles document and the functionality described in the OMG CTS 2 specification.

4.9.4 Resource Content

* Structure

* UML

* XML

* JSON

* Turtle

* R2 Diff

* All

Structure

Name | Flags | Card. | Type | Description & Constraints
ConceptMap | | | DomainResource | A map from one set of concepts to one or more other concepts Elements defined in Ancestors: id, meta, implicitRules, language, text, contained, extension, modifierExtension
url | ? | 0..1 | uri | Logical URI to reference this concept map (globally unique)
identifier | ? | 0..1 | Identifier | Additional identifier for the concept map
version | ? | 0..1 | string | Business version of the concept map
name | ? | 0..1 | string | Name for this concept map (computer friendly)
title | ? | 0..1 | string | Name for this concept map (human friendly)
status | ?!? | 1..1 | code | draft | active | retired | unknown PublicationStatus (Required)
experimental | ?!? | 0..1 | boolean | For testing purposes, not real usage
date | ? | 0..1 | dateTime | Date this was last changed
publisher | ? | 0..1 | string | Name of the publisher (organization or individual)
contact | ? | 0..* | ContactDetail | Contact details for the publisher
description | | 0..1 | markdown | Natural language description of the concept map
useContext | ? | 0..* | UsageContext | Context the content is intended to support
jurisdiction | ? | 0..* | CodeableConcept | Intended jurisdiction for concept map (if applicable) Jurisdiction ValueSet (Extensible)
purpose | | 0..1 | markdown | Why this concept map is defined
copyright | | 0..1 | markdown | Use and/or publishing restrictions
source[x] | ? | 0..1 | | Identifies the source of the concepts which are being mapped
sourceUri | | | uri
sourceReference | | | Reference(ValueSet)
target[x] | ? | 0..1 | | Provides context to the mappings
targetUri | | | uri
targetReference | | | Reference(ValueSet)
group | | 0..* | BackboneElement | Same source and target systems

source | | 0..1 | uri | Code System (if value set crosses code systems)
sourceVersion | | 0..1 | string | Specific version of the code system
target | | 0..1 | uri | System of the target (if necessary)
targetVersion | | 0..1 | string | Specific version of the code system
element | | 1..* | BackboneElement | Mappings for a concept from the source set
code | | 0..1 | code | Identifies element being mapped
display | | 0..1 | string | Display for the code
target | I | 0..* | BackboneElement | Concept in target system for element + If the map is narrower or inexact, there SHALL be some comments
code | | 0..1 | code | Code that identifies the target element
display | | 0..1 | string | Display for the code
equivalence | ?! | 0..1 | code | relatedto | equivalent | equal | wider | subsumes | narrower | specializes | inexact | unmatched | disjoint ConceptMapEquivalence (Required)
comment | I | 0..1 | string | Description of status/issues in mapping
dependsOn | | 0..* | BackboneElement | Other elements required for this mapping (from context)
property | | 1..1 | uri | Reference to property mapping depends on
system | | 0..1 | uri | Code System (if necessary)
code | | 1..1 | string | Value of the referenced element
display | | 0..1 | string | Display for the code
product | | 0..* | see dependsOn | Other concepts that this mapping also produces
unmapped | I | 0..1 | BackboneElement | When no match in the mappings + If the mode is 'other-map', a code must be provided + If the mode is 'fixed', a code must be provided
mode | | 1..1 | code | provided | fixed | other-map ConceptMapGroupUnmappedMode (Required)
code | | 0..1 | code | Fixed code when mode = fixed
display | | 0..1 | string | Display for the code
url | | 0..1 | uri | Canonical URL for other concept map
Documentation for this format

UML Diagram (Legend)

XML Template

```
<ConceptMap xmlns="http://hl7.org/fhir">
 <!-- from Resource: id, meta, implicitRules, and language -->
 <!-- from DomainResource: text, contained, extension, and modifierExtension -->
 <url value="[uri]"/><!-- 0..1 Logical URI to reference this concept map (globally unique) -->
 <identifier><!-- 0..1 Identifier Additional identifier for the concept map --></identifier>
 <version value="[string]"/><!-- 0..1 Business version of the concept map -->
 <name value="[string]"/><!-- 0..1 Name for this concept map (computer friendly) -->
 <title value="[string]"/><!-- 0..1 Name for this concept map (human friendly) -->
 <status value="[code]"/><!-- 1..1 draft | active | retired | unknown -->
 <experimental value="[boolean]"/><!-- 0..1 For testing purposes, not real usage -->
 <date value="[dateTime]"/><!-- 0..1 Date this was last changed -->
 <publisher value="[string]"/><!-- 0..1 Name of the publisher (organization or individual) -->
 <contact><!-- 0..* ContactDetail Contact details for the publisher --></contact>
 <description value="[markdown]"/><!-- 0..1 Natural language description of the concept map -->
 <useContext><!-- 0..* UsageContext Context the content is intended to support --></useContext>
 <jurisdiction><!-- 0..* CodeableConcept Intended jurisdiction for concept map (if applicable) --></jurisdiction>
 <purpose value="[markdown]"/><!-- 0..1 Why this concept map is defined -->
 <copyright value="[markdown]"/><!-- 0..1 Use and/or publishing restrictions -->
 <source[x]><!-- 0..1 uri|Reference(ValueSet) Identifies the source of the concepts which are being mapped
    --></source[x]>
 <target[x]><!-- 0..1 uri|Reference(ValueSet) Provides context to the mappings --></target[x]>
 <group>  <!-- 0..* Same source and target systems -->
  <source value="[uri]"/><!-- 0..1 Code System (if value set crosses code systems) -->
  <sourceVersion value="[string]"/><!-- 0..1 Specific version of the  code system -->
  <target value="[uri]"/><!-- 0..1 System of the target (if necessary) -->
  <targetVersion value="[string]"/><!-- 0..1 Specific version of the  code system -->
  <element>  <!-- 1..* Mappings for a concept from the source set -->
   <code value="[code]"/><!-- 0..1 Identifies element being mapped -->
   <display value="[string]"/><!-- 0..1 Display for the code -->
   <target>  <!-- 0..* Concept in target system for element -->
    <code value="[code]"/><!-- 0..1 Code that identifies the target element -->
    <display value="[string]"/><!-- 0..1 Display for the code -->
    <equivalence value="[code]"/><!-- 0..1 relatedto | equivalent | equal | wider | subsumes | narrower | specializes |
    inexact | unmatched | disjoint -->
    <comment value="[string]"/><!--  0..1 Description of status/issues in mapping -->
    <dependsOn>  <!-- 0..* Other elements required for this mapping (from context) -->
     <property value="[uri]"/><!-- 1..1 Reference to property mapping depends on -->
     <system value="[uri]"/><!-- 0..1 Code System (if necessary) -->
     <code value="[string]"/><!-- 1..1 Value of the referenced element -->
     <display value="[string]"/><!-- 0..1 Display for the code -->
    </dependsOn>
    <product><!-- 0..* Content as for ConceptMap.group.element.target.dependsOn Other concepts that this mapping also
    produces --></product>
   </target>
  </element>
  <unmapped>  <!-- 0..1 When no match in the mappings -->
   <mode value="[code]"/><!-- 1..1 provided | fixed | other-map -->
   <code value="[code]"/><!-- 0..1 Fixed code when mode = fixed -->
   <display value="[string]"/><!-- 0..1 Display for the code -->
   <url value="[uri]"/><!-- 0..1 Canonical URL for other concept map -->
  </unmapped>
 </group>
</ConceptMap>
```

JSON Template

```
{
  "resourceType" : "ConceptMap",
  // from Resource: id, meta, implicitRules, and language
  // from DomainResource: text, contained, extension, and modifierExtension
  "url" : "<uri>", // Logical URI to reference this concept map (globally unique)
  "identifier" : { Identifier }, // Additional identifier for the concept map
  "version" : "<string>", // Business version of the concept map
  "name" : "<string>", // Name for this concept map (computer friendly)
  "title" : "<string>", // Name for this concept map (human friendly)
  "status" : "<code>", // R!  draft | active | retired | unknown
  "experimental" : <boolean>, // For testing purposes, not real usage
  "date" : "<dateTime>", // Date this was last changed
  "publisher" : "<string>", // Name of the publisher (organization or individual)
  "contact" : [{ ContactDetail }], // Contact details for the publisher
  "description" : "<markdown>", // Natural language description of the concept map
  "useContext" : [{ UsageContext }], // Context the content is intended to support
  "jurisdiction" : [{ CodeableConcept }], // Intended jurisdiction for concept map (if applicable)
  "purpose" : "<markdown>", // Why this concept map is defined
  "copyright" : "<markdown>", // Use and/or publishing restrictions
  // source[x]: Identifies the source of the concepts which are being mapped. One of these 2:
  "sourceUri" : "<uri>",
  "sourceReference" : { Reference(ValueSet) },
  // target[x]: Provides context to the mappings. One of these 2:
  "targetUri" : "<uri>",
  "targetReference" : { Reference(ValueSet) },
  "group" : [{ // Same source and target systems
    "source" : "<uri>", // Code System (if value set crosses code systems)
    "sourceVersion" : "<string>", // Specific version of the  code system
    "target" : "<uri>", // System of the target (if necessary)
    "targetVersion" : "<string>", // Specific version of the  code system
    "element" : [{ // R!  Mappings for a concept from the source set
      "code" : "<code>", // Identifies element being mapped
      "display" : "<string>", // Display for the code
      "target" : [{ // Concept in target system for element
        "code" : "<code>", // Code that identifies the target element
        "display" : "<string>", // Display for the code
        "equivalence" : "<code>", // relatedto | equivalent | equal | wider | subsumes | narrower | specializes |
    inexact | unmatched | disjoint
        "comment" : "<string>", // C? Description of status/issues in mapping
        "dependsOn" : [{ // Other elements required for this mapping (from context)
          "property" : "<uri>", // R!  Reference to property mapping depends on
          "system" : "<uri>", // Code System (if necessary)
          "code" : "<string>", // R!  Value of the referenced element
          "display" : "<string>" // Display for the code
        }],
        "product" : [{ Content as for ConceptMap.group.element.target.dependsOn }] // Other concepts that this mapping
    also produces
      }]
    }],
    "unmapped" : { // When no match in the mappings
      "mode" : "<code>", // R!  provided | fixed | other-map
      "code" : "<code>", // Fixed code when mode = fixed
      "display" : "<string>", // Display for the code
      "url" : "<uri>" // Canonical URL for other concept map
    }
  }]
}
```

Turtle Template

```
@prefix fhir: <http://hl7.org/fhir/> .


[ a fhir:ConceptMap;
  fhir:nodeRole fhir:treeRoot; # if this is the parser root

  # from Resource: .id, .meta, .implicitRules, and .language
  # from DomainResource: .text, .contained, .extension, and .modifierExtension
  fhir:ConceptMap.url [ uri ]; # 0..1 Logical URI to reference this concept map (globally unique)
  fhir:ConceptMap.identifier [ Identifier ]; # 0..1 Additional identifier for the concept map
  fhir:ConceptMap.version [ string ]; # 0..1 Business version of the concept map
  fhir:ConceptMap.name [ string ]; # 0..1 Name for this concept map (computer friendly)
  fhir:ConceptMap.title [ string ]; # 0..1 Name for this concept map (human friendly)
  fhir:ConceptMap.status [ code ]; # 1..1 draft | active | retired | unknown
  fhir:ConceptMap.experimental [ boolean ]; # 0..1 For testing purposes, not real usage
  fhir:ConceptMap.date [ dateTime ]; # 0..1 Date this was last changed
  fhir:ConceptMap.publisher [ string ]; # 0..1 Name of the publisher (organization or individual)
  fhir:ConceptMap.contact [ ContactDetail ], ... ; # 0..* Contact details for the publisher
  fhir:ConceptMap.description [ markdown ]; # 0..1 Natural language description of the concept map
  fhir:ConceptMap.useContext [ UsageContext ], ... ; # 0..* Context the content is intended to support
  fhir:ConceptMap.jurisdiction [ CodeableConcept ], ... ; # 0..* Intended jurisdiction for concept map (if applicable)
  fhir:ConceptMap.purpose [ markdown ]; # 0..1 Why this concept map is defined
  fhir:ConceptMap.copyright [ markdown ]; # 0..1 Use and/or publishing restrictions
  # ConceptMap.source[x] : 0..1 Identifies the source of the concepts which are being mapped. One of these 2
    fhir:ConceptMap.sourceUri [ uri ]
    fhir:ConceptMap.sourceReference [ Reference(ValueSet) ]
  # ConceptMap.target[x] : 0..1 Provides context to the mappings. One of these 2
    fhir:ConceptMap.targetUri [ uri ]
```

```
    fhir:ConceptMap.targetReference [ Reference(ValueSet) ]
  fhir:ConceptMap.group [ # 0..* Same source and target systems
    fhir:ConceptMap.group.source [ uri ]; # 0..1 Code System (if value set crosses code systems)
    fhir:ConceptMap.group.sourceVersion [ string ]; # 0..1 Specific version of the  code system
    fhir:ConceptMap.group.target [ uri ]; # 0..1 System of the target (if necessary)
    fhir:ConceptMap.group.targetVersion [ string ]; # 0..1 Specific version of the  code system
    fhir:ConceptMap.group.element [ # 1..* Mappings for a concept from the source set
      fhir:ConceptMap.group.element.code [ code ]; # 0..1 Identifies element being mapped
      fhir:ConceptMap.group.element.display [ string ]; # 0..1 Display for the code
      fhir:ConceptMap.group.element.target [ # 0..* Concept in target system for element
        fhir:ConceptMap.group.element.target.code [ code ]; # 0..1 Code that identifies the target element
        fhir:ConceptMap.group.element.target.display [ string ]; # 0..1 Display for the code
        fhir:ConceptMap.group.element.target.equivalence [ code ]; # 0..1 relatedto | equivalent | equal | wider |
    subsumes | narrower | specializes | inexact | unmatched | disjoint
        fhir:ConceptMap.group.element.target.comment [ string ]; # 0..1 Description of status/issues in mapping
        fhir:ConceptMap.group.element.target.dependsOn [ # 0..* Other elements required for this mapping (from context)
          fhir:ConceptMap.group.element.target.dependsOn.property [ uri ]; # 1..1 Reference to property mapping depends
    on
          fhir:ConceptMap.group.element.target.dependsOn.system [ uri ]; # 0..1 Code System (if necessary)
          fhir:ConceptMap.group.element.target.dependsOn.code [ string ]; # 1..1 Value of the referenced element
          fhir:ConceptMap.group.element.target.dependsOn.display [ string ]; # 0..1 Display for the code
        ], ...;
        fhir:ConceptMap.group.element.target.product [ See ConceptMap.group.element.target.dependsOn ], ... ; # 0..*
    Other concepts that this mapping also produces
      ], ...;
    ], ...;
    fhir:ConceptMap.group.unmapped [ # 0..1 When no match in the mappings
      fhir:ConceptMap.group.unmapped.mode [ code ]; # 1..1 provided | fixed | other-map
      fhir:ConceptMap.group.unmapped.code [ code ]; # 0..1 Fixed code when mode = fixed
      fhir:ConceptMap.group.unmapped.display [ string ]; # 0..1 Display for the code
      fhir:ConceptMap.group.unmapped.url [ uri ]; # 0..1 Canonical URL for other concept map
    ];
  ], ...;
]
```

Changes since DSTU2

ConceptMap
ConceptMap.title | Added Element
ConceptMap.status | Change value set from http://hl7.org/fhir/ValueSet/conformance-resource-status to http://hl7.org/fhir/ValueSet/publication-status
ConceptMap.experimental | Now marked as Modifier
ConceptMap.contact | Type changed from BackboneElement to ContactDetail
ConceptMap.description | Type changed from string to markdown
ConceptMap.useContext | Type changed from CodeableConcept to UsageContext Remove Binding http://hl7.org/fhir/ValueSet/use-context (extensible)
ConceptMap.jurisdiction | Renamed from useContext to jurisdiction Change value set from http://hl7.org/fhir/ValueSet/use-context to http://hl7.org/fhir/ValueSet/jurisdiction
ConceptMap.purpose | Renamed from requirements to purpose Type changed from string to markdown
ConceptMap.copyright | Type changed from string to markdown
ConceptMap.source[x] | Min Cardinality changed from 1 to 0 Remove Reference(StructureDefinition)
ConceptMap.target[x] | Min Cardinality changed from 1 to 0 Remove Reference(StructureDefinition)
ConceptMap.group | Added Element
ConceptMap.group.source | Added Element
ConceptMap.group.sourceVersion | Added Element
ConceptMap.group.target | Added Element
ConceptMap.group.targetVersion | Added Element
ConceptMap.group.element | Min Cardinality changed from 0 to 1
ConceptMap.group.element.display | Added Element
ConceptMap.group.element.target.display | Added Element
ConceptMap.group.element.target.equivalence | Min Cardinality changed from 1 to 0 Default Value "equivalent" added
ConceptMap.group.element.target.comment | Added Element
ConceptMap.group.element.target.dependsOn.property | Added Element
ConceptMap.group.element.target.dependsOn.system | Added Element
ConceptMap.group.element.target.dependsOn.display | Added Element
ConceptMap.group.unmapped | Added Element
ConceptMap.group.unmapped.mode | Added Element
ConceptMap.group.unmapped.code | Added Element
ConceptMap.group.unmapped.display | Added Element
ConceptMap.group.unmapped.url | Added Element
ConceptMap.contact.name | deleted
ConceptMap.contact.telecom | deleted
ConceptMap.element.codeSystem | deleted
ConceptMap.element.target.codeSystem | deleted
ConceptMap.element.target.comments | deleted
ConceptMap.element.target.dependsOn.element | deleted
ConceptMap.element.target.dependsOn.codeSystem | deleted

See the Full Difference for further information

This analysis is available as XML or JSON.

See R2 <--> R3 Conversion Maps (status = 2 tests that all execute ok. All tests pass round-trip testing and 1 r3 resources are invalid (1 errors).).

Structure

Name | Flags | Card. | Type | Description & Constraints
ConceptMap | | | DomainResource | A map from one set of concepts to one or more other concepts Elements defined in Ancestors: id, meta, implicitRules, language, text, contained, extension, modifierExtension
url | ? | 0..1 | uri | Logical URI to reference this concept map (globally unique)
identifier | ? | 0..1 | Identifier | Additional identifier for the concept map
version | ? | 0..1 | string | Business version of the concept map
name | ? | 0..1 | string | Name for this concept map (computer friendly)
title | ? | 0..1 | string | Name for this concept map (human friendly)
status | ?!? | 1..1 | code | draft | active | retired | unknown PublicationStatus (Required)
experimental | ?!? | 0..1 | boolean | For testing purposes, not real usage
date | ? | 0..1 | dateTime | Date this was last changed
publisher | ? | 0..1 | string | Name of the publisher (organization or individual)
contact | ? | 0..* | ContactDetail | Contact details for the publisher
description | | 0..1 | markdown | Natural language description of the concept map
useContext | ? | 0..* | UsageContext | Context the content is intended to support
jurisdiction | ? | 0..* | CodeableConcept | Intended jurisdiction for concept map (if applicable) Jurisdiction ValueSet (Extensible)
purpose | | 0..1 | markdown | Why this concept map is defined
copyright | | 0..1 | markdown | Use and/or publishing restrictions
source[x] | ? | 0..1 | | Identifies the source of the concepts which are being mapped
sourceUri | | | uri
sourceReference | | | Reference(ValueSet)
target[x] | ? | 0..1 | | Provides context to the mappings
targetUri | | | uri
targetReference | | | Reference(ValueSet)
group | | 0..* | BackboneElement | Same source and target systems
source | | 0..1 | uri | Code System (if value set crosses code systems)
sourceVersion | | 0..1 | string | Specific version of the code system
target | | 0..1 | uri | System of the target (if necessary)
targetVersion | | 0..1 | string | Specific version of the code system
element | | 1..* | BackboneElement | Mappings for a concept from the source set
code | | 0..1 | code | Identifies element being mapped
display | | 0..1 | string | Display for the code
target | I | 0..* | BackboneElement | Concept in target system for element + If the map is narrower or inexact, there SHALL be some comments
code | | 0..1 | code | Code that identifies the target element
display | | 0..1 | string | Display for the code
equivalence | ?! | 0..1 | code | relatedto | equivalent | equal | wider | subsumes | narrower | specializes | inexact | unmatched | disjoint ConceptMapEquivalence (Required)
comment | I | 0..1 | string | Description of status/issues in mapping
dependsOn | | 0..* | BackboneElement | Other elements required for this mapping (from context)
property | | 1..1 | uri | Reference to property mapping depends on
system | | 0..1 | uri | Code System (if necessary)
code | | 1..1 | string | Value of the referenced element
display | | 0..1 | string | Display for the code
product | | 0..* | see dependsOn | Other concepts that this mapping also produces
unmapped | I | 0..1 | BackboneElement | When no match in the mappings + If the mode is 'other-map', a code must be provided + If the mode is 'fixed', a code must be provided
mode | | 1..1 | code | provided | fixed | other-map ConceptMapGroupUnmappedMode (Required)
code | | 0..1 | code | Fixed code when mode = fixed
display | | 0..1 | string | Display for the code
url | | 0..1 | uri | Canonical URL for other concept map
Documentation for this format

UML Diagram (Legend)

XML Template

```
<ConceptMap xmlns="http://hl7.org/fhir">
 <!-- from Resource: id, meta, implicitRules, and language -->
 <!-- from DomainResource: text, contained, extension, and modifierExtension -->
 <url value="[uri]"/><!-- 0..1 Logical URI to reference this concept map (globally unique) -->
 <identifier><!-- 0..1 Identifier Additional identifier for the concept map --></identifier>
 <version value="[string]"/><!-- 0..1 Business version of the concept map -->
 <name value="[string]"/><!-- 0..1 Name for this concept map (computer friendly) -->
 <title value="[string]"/><!-- 0..1 Name for this concept map (human friendly) -->
 <status value="[code]"/><!-- 1..1 draft | active | retired | unknown -->
 <experimental value="[boolean]"/><!-- 0..1 For testing purposes, not real usage -->
 <date value="[dateTime]"/><!-- 0..1 Date this was last changed -->
 <publisher value="[string]"/><!-- 0..1 Name of the publisher (organization or individual) -->
 <contact><!-- 0..* ContactDetail Contact details for the publisher --></contact>
 <description value="[markdown]"/><!-- 0..1 Natural language description of the concept map -->
 <useContext><!-- 0..* UsageContext Context the content is intended to support --></useContext>
 <jurisdiction><!-- 0..* CodeableConcept Intended jurisdiction for concept map (if applicable) --></jurisdiction>
 <purpose value="[markdown]"/><!-- 0..1 Why this concept map is defined -->
 <copyright value="[markdown]"/><!-- 0..1 Use and/or publishing restrictions -->
```

```
 <source[x]><!-- 0..1 uri|Reference(ValueSet) Identifies the source of the concepts which are being mapped
    --></source[x]>
 <target[x]><!-- 0..1 uri|Reference(ValueSet) Provides context to the mappings --></target[x]>
 <group>  <!-- 0..* Same source and target systems -->
  <source value="[uri]"/><!-- 0..1 Code System (if value set crosses code systems) -->
  <sourceVersion value="[string]"/><!-- 0..1 Specific version of the  code system -->
  <target value="[uri]"/><!-- 0..1 System of the target (if necessary) -->
  <targetVersion value="[string]"/><!-- 0..1 Specific version of the  code system -->
  <element>  <!-- 1..* Mappings for a concept from the source set -->
   <code value="[code]"/><!-- 0..1 Identifies element being mapped -->
   <display value="[string]"/><!-- 0..1 Display for the code -->
   <target>  <!-- 0..* Concept in target system for element -->
    <code value="[code]"/><!-- 0..1 Code that identifies the target element -->
    <display value="[string]"/><!-- 0..1 Display for the code -->
    <equivalence value="[code]"/><!-- 0..1 relatedto | equivalent | equal | wider | subsumes | narrower | specializes |
    inexact | unmatched | disjoint -->
    <comment value="[string]"/><!--  0..1 Description of status/issues in mapping -->
    <dependsOn>  <!-- 0..* Other elements required for this mapping (from context) -->
     <property value="[uri]"/><!-- 1..1 Reference to property mapping depends on -->
     <system value="[uri]"/><!-- 0..1 Code System (if necessary) -->
     <code value="[string]"/><!-- 1..1 Value of the referenced element -->
     <display value="[string]"/><!-- 0..1 Display for the code -->
    </dependsOn>
    <product><!-- 0..* Content as for ConceptMap.group.element.target.dependsOn Other concepts that this mapping also
    produces --></product>
   </target>
  </element>
  <unmapped>  <!-- 0..1 When no match in the mappings -->
   <mode value="[code]"/><!-- 1..1 provided | fixed | other-map -->
   <code value="[code]"/><!-- 0..1 Fixed code when mode = fixed -->
   <display value="[string]"/><!-- 0..1 Display for the code -->
   <url value="[uri]"/><!-- 0..1 Canonical URL for other concept map -->
  </unmapped>
 </group>
</ConceptMap>
```

JSON Template

```
{
  "resourceType" : "ConceptMap",
  // from Resource: id, meta, implicitRules, and language
  // from DomainResource: text, contained, extension, and modifierExtension
  "url" : "<uri>", // Logical URI to reference this concept map (globally unique)
  "identifier" : { Identifier }, // Additional identifier for the concept map
  "version" : "<string>", // Business version of the concept map
  "name" : "<string>", // Name for this concept map (computer friendly)
  "title" : "<string>", // Name for this concept map (human friendly)
  "status" : "<code>", // R!  draft | active | retired | unknown
  "experimental" : <boolean>, // For testing purposes, not real usage
  "date" : "<dateTime>", // Date this was last changed
  "publisher" : "<string>", // Name of the publisher (organization or individual)
  "contact" : [{ ContactDetail }], // Contact details for the publisher
  "description" : "<markdown>", // Natural language description of the concept map
  "useContext" : [{ UsageContext }], // Context the content is intended to support
  "jurisdiction" : [{ CodeableConcept }], // Intended jurisdiction for concept map (if applicable)
  "purpose" : "<markdown>", // Why this concept map is defined
  "copyright" : "<markdown>", // Use and/or publishing restrictions
  // source[x]: Identifies the source of the concepts which are being mapped. One of these 2:
  "sourceUri" : "<uri>",
  "sourceReference" : { Reference(ValueSet) },
  // target[x]: Provides context to the mappings. One of these 2:
  "targetUri" : "<uri>",
  "targetReference" : { Reference(ValueSet) },
  "group" : [{ // Same source and target systems
    "source" : "<uri>", // Code System (if value set crosses code systems)
    "sourceVersion" : "<string>", // Specific version of the  code system
    "target" : "<uri>", // System of the target (if necessary)
    "targetVersion" : "<string>", // Specific version of the  code system
    "element" : [{ // R!  Mappings for a concept from the source set
      "code" : "<code>", // Identifies element being mapped
      "display" : "<string>", // Display for the code
      "target" : [{ // Concept in target system for element
        "code" : "<code>", // Code that identifies the target element
        "display" : "<string>", // Display for the code
        "equivalence" : "<code>", // relatedto | equivalent | equal | wider | subsumes | narrower | specializes |
    inexact | unmatched | disjoint
        "comment" : "<string>", // C? Description of status/issues in mapping
        "dependsOn" : [{ // Other elements required for this mapping (from context)
          "property" : "<uri>", // R!  Reference to property mapping depends on
          "system" : "<uri>", // Code System (if necessary)
          "code" : "<string>", // R!  Value of the referenced element
          "display" : "<string>" // Display for the code
        }],
        "product" : [{ Content as for ConceptMap.group.element.target.dependsOn }] // Other concepts that this mapping
    also produces
      }]
    }],
    "unmapped" : { // When no match in the mappings
      "mode" : "<code>", // R!  provided | fixed | other-map
      "code" : "<code>", // Fixed code when mode = fixed
```

```
      "display" : "<string>", // Display for the code
      "url" : "<uri>" // Canonical URL for other concept map
    }
  }]
}
```

Turtle Template

```
@prefix fhir: <http://hl7.org/fhir/> .


[ a fhir:ConceptMap;
  fhir:nodeRole fhir:treeRoot; # if this is the parser root

  # from Resource: .id, .meta, .implicitRules, and .language
  # from DomainResource: .text, .contained, .extension, and .modifierExtension
  fhir:ConceptMap.url [ uri ]; # 0..1 Logical URI to reference this concept map (globally unique)
  fhir:ConceptMap.identifier [ Identifier ]; # 0..1 Additional identifier for the concept map
  fhir:ConceptMap.version [ string ]; # 0..1 Business version of the concept map
  fhir:ConceptMap.name [ string ]; # 0..1 Name for this concept map (computer friendly)
  fhir:ConceptMap.title [ string ]; # 0..1 Name for this concept map (human friendly)
  fhir:ConceptMap.status [ code ]; # 1..1 draft | active | retired | unknown
  fhir:ConceptMap.experimental [ boolean ]; # 0..1 For testing purposes, not real usage
  fhir:ConceptMap.date [ dateTime ]; # 0..1 Date this was last changed
  fhir:ConceptMap.publisher [ string ]; # 0..1 Name of the publisher (organization or individual)
  fhir:ConceptMap.contact [ ContactDetail ], ... ; # 0..* Contact details for the publisher
  fhir:ConceptMap.description [ markdown ]; # 0..1 Natural language description of the concept map
  fhir:ConceptMap.useContext [ UsageContext ], ... ; # 0..* Context the content is intended to support
  fhir:ConceptMap.jurisdiction [ CodeableConcept ], ... ; # 0..* Intended jurisdiction for concept map (if applicable)
  fhir:ConceptMap.purpose [ markdown ]; # 0..1 Why this concept map is defined
  fhir:ConceptMap.copyright [ markdown ]; # 0..1 Use and/or publishing restrictions
  # ConceptMap.source[x] : 0..1 Identifies the source of the concepts which are being mapped. One of these 2
    fhir:ConceptMap.sourceUri [ uri ]
    fhir:ConceptMap.sourceReference [ Reference(ValueSet) ]
  # ConceptMap.target[x] : 0..1 Provides context to the mappings. One of these 2
    fhir:ConceptMap.targetUri [ uri ]
    fhir:ConceptMap.targetReference [ Reference(ValueSet) ]
  fhir:ConceptMap.group [ # 0..* Same source and target systems
    fhir:ConceptMap.group.source [ uri ]; # 0..1 Code System (if value set crosses code systems)
    fhir:ConceptMap.group.sourceVersion [ string ]; # 0..1 Specific version of the  code system
    fhir:ConceptMap.group.target [ uri ]; # 0..1 System of the target (if necessary)
    fhir:ConceptMap.group.targetVersion [ string ]; # 0..1 Specific version of the  code system
    fhir:ConceptMap.group.element [ # 1..* Mappings for a concept from the source set
      fhir:ConceptMap.group.element.code [ code ]; # 0..1 Identifies element being mapped
      fhir:ConceptMap.group.element.display [ string ]; # 0..1 Display for the code
      fhir:ConceptMap.group.element.target [ # 0..* Concept in target system for element
        fhir:ConceptMap.group.element.target.code [ code ]; # 0..1 Code that identifies the target element
        fhir:ConceptMap.group.element.target.display [ string ]; # 0..1 Display for the code
        fhir:ConceptMap.group.element.target.equivalence [ code ]; # 0..1 relatedto | equivalent | equal | wider |
    subsumes | narrower | specializes | inexact | unmatched | disjoint
        fhir:ConceptMap.group.element.target.comment [ string ]; # 0..1 Description of status/issues in mapping
        fhir:ConceptMap.group.element.target.dependsOn [ # 0..* Other elements required for this mapping (from context)
          fhir:ConceptMap.group.element.target.dependsOn.property [ uri ]; # 1..1 Reference to property mapping depends
    on
          fhir:ConceptMap.group.element.target.dependsOn.system [ uri ]; # 0..1 Code System (if necessary)
          fhir:ConceptMap.group.element.target.dependsOn.code [ string ]; # 1..1 Value of the referenced element
          fhir:ConceptMap.group.element.target.dependsOn.display [ string ]; # 0..1 Display for the code
        ], ...;
        fhir:ConceptMap.group.element.target.product [ See ConceptMap.group.element.target.dependsOn ], ... ; # 0..*
    Other concepts that this mapping also produces
      ], ...;
    ], ...;
    fhir:ConceptMap.group.unmapped [ # 0..1 When no match in the mappings
      fhir:ConceptMap.group.unmapped.mode [ code ]; # 1..1 provided | fixed | other-map
      fhir:ConceptMap.group.unmapped.code [ code ]; # 0..1 Fixed code when mode = fixed
      fhir:ConceptMap.group.unmapped.display [ string ]; # 0..1 Display for the code
      fhir:ConceptMap.group.unmapped.url [ uri ]; # 0..1 Canonical URL for other concept map
    ];
  ], ...;
]
```

Changes since DSTU2

ConceptMap

ConceptMap.title | Added Element

ConceptMap.status | Change value set from http://hl7.org/fhir/ValueSet/conformance-resource-status to http://hl7.org/fhir/ValueSet/publication-status

ConceptMap.experimental | Now marked as Modifier

ConceptMap.contact | Type changed from BackboneElement to ContactDetail

ConceptMap.description | Type changed from string to markdown

ConceptMap.useContext | Type changed from CodeableConcept to UsageContext Remove Binding http://hl7.org/fhir/ValueSet/use-context (extensible)

ConceptMap.jurisdiction | Renamed from useContext to jurisdiction Change value set from http://hl7.org/fhir/ValueSet/use-context to http://hl7.org/fhir/ValueSet/jurisdiction

ConceptMap.purpose | Renamed from requirements to purpose Type changed from string to markdown

ConceptMap.copyright | Type changed from string to markdown

ConceptMap.source[x] | Min Cardinality changed from 1 to 0 Remove Reference(StructureDefinition)

ConceptMap.target[x] | Min Cardinality changed from 1 to 0 Remove Reference(StructureDefinition)

ConceptMap.group | Added Element

ConceptMap.group.source | Added Element
ConceptMap.group.sourceVersion | Added Element
ConceptMap.group.target | Added Element
ConceptMap.group.targetVersion | Added Element
ConceptMap.group.element | Min Cardinality changed from 0 to 1
ConceptMap.group.element.display | Added Element
ConceptMap.group.element.target.display | Added Element
ConceptMap.group.element.target.equivalence | Min Cardinality changed from 1 to 0 Default Value "equivalent" added
ConceptMap.group.element.target.comment | Added Element
ConceptMap.group.element.target.dependsOn.property | Added Element
ConceptMap.group.element.target.dependsOn.system | Added Element
ConceptMap.group.element.target.dependsOn.display | Added Element
ConceptMap.group.unmapped | Added Element
ConceptMap.group.unmapped.mode | Added Element
ConceptMap.group.unmapped.code | Added Element
ConceptMap.group.unmapped.display | Added Element
ConceptMap.group.unmapped.url | Added Element
ConceptMap.contact.name | deleted
ConceptMap.contact.telecom | deleted
ConceptMap.element.codeSystem | deleted
ConceptMap.element.target.codeSystem | deleted
ConceptMap.element.target.comments | deleted
ConceptMap.element.target.dependsOn.element | deleted
ConceptMap.element.target.dependsOn.codeSystem | deleted

See the Full Difference for further information

This analysis is available as XML or JSON.

See R2 <--> R3 Conversion Maps (status = 2 tests that all execute ok. All tests pass round-trip testing and 1 r3 resources are invalid (1 errors).).

Alternate definitions: Master Definition (XML, JSON), XML Schema/Schematron (for) + JSON Schema, ShEx (for Turtle)

4.9.4.1 Terminology Bindings

Path | Definition | Type | Reference
ConceptMap.status | The lifecycle status of a Value Set or Concept Map. | Required | PublicationStatus
ConceptMap.jurisdiction | Countries and regions within which this artifact is targeted for use | Extensible | Jurisdiction ValueSet
ConceptMap.group.element.target.equivalence | The degree of equivalence between concepts. | Required | ConceptMapEquivalence
ConceptMap.group.unmapped.mode | Defines which action to take if there is no match in the group. | Required | ConceptMapGroupUnmappedMode

4.9.4.2 Constraints

* cmd-1: On ConceptMap.group.element.target: If the map is narrower or inexact, there SHALL be some comments (expression on ConceptMap.group.element.target: comment.exists() or equivalence.empty() or ((equivalence != 'narrower') and (equivalence != 'inexact')))

* cmd-2: On ConceptMap.group.unmapped: If the mode is 'fixed', a code must be provided (expression on ConceptMap.group.unmapped: (mode = 'fixed') implies code.exists())

* cmd-3: On ConceptMap.group.unmapped: If the mode is 'other-map', a code must be provided (expression on ConceptMap.group.unmapped: (mode = 'other-map') implies url.exists())

4.9.5 Notes

* The value of the system, version and code elements are the same as used by the Coding data type

* When a mapping equivalence is characterized as "narrower", some explanation of the scope difference SHALL be provided in the comments

* The concept map is a statement of mapping in a single direction. The existence of a matching mapping in the reverse direction cannot be assumed to exist automatically, but only through human review.

* There should be only one element for each source concept. If there is more than one, the target statements are cumulative across them

4.9.6 Grouping Mappings

The concept mappings in element are arranged into groups that share common source/target systems. These groups have no semantic signficance; they exist to make the representation more concise. Concept maps may contain more than one group with the same source and target - this would be a less concise representation but may be useful in order to maintain a fixed order for the concepts that are mapped.

Concepts that are labeled as 'unmatched' are considered to be unmatched in the target value set, irrespective of whether they are contained in a group with a stated target system or not. Groups that contain no target system may only contained 'unmatched' concepts. There is no difference in the meaning of an unmatched target whether or not there is a stated target system.

4.9.7 Implicit Code Systems

The ConceptMap resource is intended to map between concepts defined in a code system. It can also be useful to use the ConceptMap resource to define relationships between concepts defined in other kinds of resources. Here are some common kind of conceptual maps:

* Between two elements in different structure definitions (e.g. between CDA and FHIR v2)

* Between a question in a Questionnaire and a DataElement

* Between a code system and a Medication resource

Though these resources are not explicitly defining code systems, they do define 'concept's that can still usefully be treated as code systems for the sake of subsetting (e.g. ValueSet) and defining relationships (e.g. ConceptMap). Note that this is different from StructureMap because that is intended to define an executional transform between structures, not a conceptual model.

This table summarizes how to treat these items as a terminology:

StructureDefinition | The StructureDefinition.url (canonical URL) is the system. Each .snapshot.element.id in the snapshot is a code in the code system
Questionnaire | The Questionnaire.url (canonical URL) is the system. Each .item.linkId in the snapshot is a code in the code system. Items with no linkId cannot be addressed
DataElement | The DataElement.url (canonical URL) is the system. Each .element.id in the snapshot is a code in the code system. Elements with no id cannot be addressed
Medication | Medication resources are a bit different, since they don't have a canonical URL, and there are not multiple items in a resource. So to refer to a medication resource, the system is [base]/Medication, where base is the server address. The Logical Id of the resource is the code

4.9.8 Search Parameters

Search parameters for this resource. The common parameters also apply. See Searching for more information about searching in REST, messaging, and services.

Name | Type | Description | Expression | In Common
date | date | The concept map publication date | ConceptMap.date
dependson | uri | Reference to property mapping depends on | ConceptMap.group.element.target.dependsOn.property
description | string | The description of the concept map | ConceptMap.description
identifier | token | External identifier for the concept map | ConceptMap.identifier
jurisdiction | token | Intended jurisdiction for the concept map | ConceptMap.jurisdiction
name | string | Computationally friendly name of the concept map | ConceptMap.name
other | uri | Canonical URL for other concept map | ConceptMap.group.unmapped.url
product | uri | Reference to property mapping depends on | ConceptMap.group.element.target.product.property
publisher | string | Name of the publisher of the concept map | ConceptMap.publisher
source | reference | Identifies the source of the concepts which are being mapped | ConceptMap.source.as(Reference) (ValueSet)
source-code | token | Identifies element being mapped | ConceptMap.group.element.code
source-system | uri | Code System (if value set crosses code systems) | ConceptMap.group.source
source-uri | reference | Identifies the source of the concepts which are being mapped | ConceptMap.source.as(Uri) (ValueSet)
status | token | The current status of the concept map | ConceptMap.status
target | reference | Provides context to the mappings | ConceptMap.target.as(Reference) (ValueSet)
target-code | token | Code that identifies the target element | ConceptMap.group.element.target.code
target-system | uri | System of the target (if necessary) | ConceptMap.group.target
target-uri | reference | Provides context to the mappings | ConceptMap.target.as(Uri) (ValueSet)
title | string | The human-friendly name of the concept map | ConceptMap.title
url | uri | The uri that identifies the concept map | ConceptMap.url
version | token | The business version of the concept map | ConceptMap.version

4.9.9 Resource ConceptMap - Examples

URL: https://hl7.org/fhir/STU3/conceptmap-examples.html

This page is part of the FHIR Specification (v3.0.2: STU 3). The current version which supercedes this version is 4.0.1. For a full list of available versions, see the Directory of published versions

4.9.9 Resource ConceptMap - Examples

Vocabulary Work Group | Maturity Level: N/A | Ballot Status: Informative | Compartments: Not linked to any defined compartments

Example List:

General ConceptMap Example | 101 | XML | JSON | Turtle
SNOMED CT / ICD-10 mapping example | 103 | XML | JSON | Turtle
Specimen Type v2 -> SNOMED CT Mapping | 102 | XML | JSON | Turtle
Additional ConceptMap Example | example2 | XML | JSON | Turtle

Usage note: every effort has been made to ensure that the examples are correct and useful, but they are not a normative part of the specification.

4.9.10 Resource ConceptMap - Detailed Descriptions

URL: https://hl7.org/fhir/STU3/conceptmap-definitions.html

This page is part of the FHIR Specification (v3.0.2: STU 3). The current version which supercedes this version is 4.0.1. For a full list of available versions, see the Directory of published versions

4.9.10 Resource ConceptMap - Detailed Descriptions

Vocabulary Work Group | Maturity Level: 3 | Trial Use | Compartments: Not linked to any defined compartments

Detailed Descriptions for the elements in the ConceptMap resource.

ConceptMap

Definition | A statement of relationships from one set of concepts to one or more other concepts - either code systems or data elements, or classes in class models.

Control | 1..1

ConceptMap.url

Definition | An absolute URI that is used to identify this concept map when it is referenced in a specification, model, design or an instance. This SHALL be a URL, SHOULD be globally unique, and SHOULD be an address at which this concept map is (or will be) published. The URL SHOULD include the major version of the concept map. For more information see Technical and Business Versions.

Control | 0..1

Type | uri

Requirements | Allows the concept map to be referenced by a single globally unique identifier.

Summary | true

Comments | Can be a urn:uuid: or a urn:oid:, but real http: addresses are preferred. Multiple instances may share the same url if they have a distinct version.

ConceptMap.identifier

Definition | A formal identifier that is used to identify this concept map when it is represented in other formats, or referenced in a specification, model, design or an instance.

Note | This is a business identifer, not a resource identifier (see discussion)

Control | 0..1

Type | Identifier

Requirements | Allows externally provided and/or usable business identifiers to be easily associated with the module.

Summary | true

Comments | Typically, this is used for identifiers that can go in an HL7 V3 II (instance identifier) data type, e.g., to identify this concept map outside of FHIR, where it is not possible to use the logical URI.

ConceptMap.version

Definition | The identifier that is used to identify this version of the concept map when it is referenced in a specification, model, design or instance. This is an arbitrary value managed by the concept map author and is not expected to be globally unique. For example, it might be a timestamp (e.g. yyyymmdd) if a managed version is not available. There is also no expectation that versions can be placed in a lexicographical sequence.

Note | This is a business versionId, not a resource version id (see discussion)

Control | 0..1

Type | string

Summary | true

Comments | There may be different concept map instances that have the same identifier but different versions. The version can be appended to the url in a reference to allow a refrence to a particular business version of the concept map with the format [url]|[version].

ConceptMap.name

Definition | A natural language name identifying the concept map. This name should be usable as an identifier for the module by machine processing applications such as code generation.

Control | 0..1

Type | string

Requirements | Support human navigation and code generation.

Summary | true

Comments | The name is not expected to be globally unique. The name should be a simple alpha-numeric type name to ensure that it is computable friendly.

ConceptMap.title

Definition | A short, descriptive, user-friendly title for the concept map.

Control | 0..1

Type | string

Summary | true

Comments | This name does not need to be machine-processing friendly and may contain punctuation, white-space, etc.

ConceptMap.status

Definition | The status of this concept map. Enables tracking the life-cycle of the content.

Control | 1..1

Terminology Binding | PublicationStatus (Required)

Type | code

Is Modifier | true

Summary | true

Comments | Allows filtering of concept maps that are appropriate for use vs. not. This is labeled as "Is Modifier" because applications should not use a retired concept map without due consideration.

ConceptMap.experimental

Definition | A boolean value to indicate that this concept map is authored for testing purposes (or education/evaluation/marketing), and is not intended to be used for genuine usage.

Control | 0..1

Type | boolean

Is Modifier | true

Requirements | Enables experimental content to be developed following the same lifecycle that would be used for a production-level concept map.

Summary | true
Comments | Allows filtering of concept map that are appropriate for use vs. not. This is labeled as "Is Modifier" because applications should not use an experimental concept map in production.
ConceptMap.date
Definition | The date (and optionally time) when the concept map was published. The date must change if and when the business version changes and it must change if the status code changes. In addition, it should change when the substantive content of the concept map changes.
Control | 0..1
Type | dateTime
Alternate Names | Revision Date
Summary | true
Comments | Note that this is not the same as the resource last-modified-date, since the resource may be a secondary representation of the concept map. Additional specific dates may be added as extensions or be found by consulting Provenances associated with past versions of the resource.
ConceptMap.publisher
Definition | The name of the individual or organization that published the concept map.
Control | 0..1
Type | string
Requirements | Helps establish the "authority/credibility" of the concept map. May also allow for contact.
Summary | true
Comments | Usually an organization, but may be an individual. The publisher (or steward) of the concept map is the organization or individual primarily responsible for the maintenance and upkeep of the concept map. This is not necessarily the same individual or organization that developed and initially authored the content. The publisher is the primary point of contact for questions or issues with the concept map. This item SHOULD be populated unless the information is available from context.
ConceptMap.contact
Definition | Contact details to assist a user in finding and communicating with the publisher.
Control | 0..*
Type | ContactDetail
Summary | true
Comments | May be a web site, an email address, a telephone number, etc.
ConceptMap.description
Definition | A free text natural language description of the concept map from a consumer's perspective.
Control | 0..1
Type | markdown
Comments | The description is not intended to describe the semantics of the concept map. The description should capture its intended use, which is needed for ensuring integrity for its use in models across future changes.
ConceptMap.useContext
Definition | The content was developed with a focus and intent of supporting the contexts that are listed. These terms may be used to assist with indexing and searching for appropriate concept map instances.
Control | 0..*
Type | UsageContext
Requirements | Assist in searching for appropriate content.
Summary | true
Comments | When multiple useContexts are specified, there is no expectation whether all or any of the contexts apply.
ConceptMap.jurisdiction
Definition | A legal or geographic region in which the concept map is intended to be used.
Control | 0..*
Terminology Binding | Jurisdiction ValueSet (Extensible)
Type | CodeableConcept
Summary | true
Comments | It may be possible for the concept map to be used in jurisdictions other than those for which it was originally designed or intended.
ConceptMap.purpose
Definition | Explaination of why this concept map is needed and why it has been designed as it has.
Control | 0..1
Type | markdown
Comments | This element does not describe the usage of the concept map Instead it provides traceability of "why" the resource is either needed or "why" it is defined as it is. This may be used to point to source materials or specifications that drove the structure of this concept map.
ConceptMap.copyright
Definition | A copyright statement relating to the concept map and/or its contents. Copyright statements are generally legal restrictions on the use and publishing of the concept map.
Control | 0..1
Type | markdown
Requirements | Consumers must be able to determine any legal restrictions on the use of the concept map and/or its content.
Alternate Names | License; Restrictions
Comments | null Frequently, the copyright differs between the concept map, and codes that are included. The copyright statement should clearly differentiate between these when required.
ConceptMap.source[x]
Definition | The source value set that specifies the concepts that are being mapped.
Control | 0..1
Type | uri|Reference(ValueSet)
[x] Note | See Choice of Data Types for further information about how to use [x]
Summary | true
Comments | Should be a version specific reference. URIs SHOULD be absolute. If there is no source or target value set, the is no specified context for the map.
ConceptMap.target[x]

Definition | The target value set provides context to the mappings. Note that the mapping is made between concepts, not between value sets, but the value set provides important context about how the concept mapping choices are made.
Control | 0..1
Type | uri|Reference(ValueSet)
[x] Note | See Choice of Data Types for further information about how to use [x]
Summary | true
Comments | Should be a version specific reference. URIs SHOULD be absolute. If there is no source or target value set, the is no specified context for the map.
ConceptMap.group
Definition | A group of mappings that all have the same source and target system.
Control | 0..*
ConceptMap.group.source
Definition | An absolute URI that identifies the Code System (if the source is a value set that crosses more than one code system).
Control | 0..1
Type | uri
ConceptMap.group.sourceVersion
Definition | The specific version of the code system, as determined by the code system authority.
Control | 0..1
Type | string
Comments | The specification of a particular code system version may be required for code systems which lack concept permanence.
ConceptMap.group.target
Definition | An absolute URI that identifies the code system of the target code (if the target is a value set that cross code systems).
Control | 0..1
Type | uri
Comments | Target may be omitted if all the targget element equivalence values are 'unmatched'.
ConceptMap.group.targetVersion
Definition | The specific version of the code system, as determined by the code system authority.
Control | 0..1
Type | string
Comments | The specification of a particular code system version may be required for code systems which lack concept permanence.
ConceptMap.group.element
Definition | Mappings for an individual concept in the source to one or more concepts in the target.
Control | 1..*
Alternate Names | code; concept; item
Comments | Generally, the ideal is that there would only be one mapping for each concept in the source value set, but a given concept may be mapped multiple times with different comments or dependencies.
ConceptMap.group.element.code
Definition | Identity (code or path) or the element/item being mapped.
Control | 0..1
Type | code
ConceptMap.group.element.display
Definition | The display for the code. The display is only provided to help editors when editing the concept map.
Control | 0..1
Type | string
Comments | The display is ignored when processing the map.
ConceptMap.group.element.target
Definition | A concept from the target value set that this concept maps to.
Control | 0..*
Comments | Ideally there would only be one map, with equal or equivalent mapping. But multiple maps are allowed for several narrower options, or to assert that other concepts are unmatched.
Invariants | Defined on this element cmd-1: If the map is narrower or inexact, there SHALL be some comments (expression : comment.exists() or equivalence.empty() or ((equivalence != 'narrower') and (equivalence != 'inexact')), xpath: exists(f:comment) or not(exists(f:equivalence)) or ((f:equivalence/@value != 'narrower') and (f:equivalence/@value != 'inexact')))
ConceptMap.group.element.target.code
Definition | Identity (code or path) or the element/item that the map refers to.
Control | 0..1
Type | code
ConceptMap.group.element.target.display
Definition | The display for the code. The display is only provided to help editors when editing the concept map.
Control | 0..1
Type | string
Comments | The display is ignored when processing the map.
ConceptMap.group.element.target.equivalence
Definition | The equivalence between the source and target concepts (counting for the dependencies and products). The equivalence is read from target to source (e.g. the target is 'wider' than the source).
Control | 0..1
Terminology Binding | ConceptMapEquivalence (Required)
Type | code
Is Modifier | true
Default Value | equivalent
Comments | This element is labeled as a modifier because it may indicate that a target does not apply.
ConceptMap.group.element.target.comment
Definition | A description of status/issues in mapping that conveys additional information not represented in the structured data.

Control | 0..1
Type | string
Invariants | Affect this element cmd-1: If the map is narrower or inexact, there SHALL be some comments (expression : comment.exists() or equivalence.empty() or ((equivalence != 'narrower') and (equivalence != 'inexact')), xpath: exists(f:comment) or not(exists(f:equivalence)) or ((f:equivalence/@value != 'narrower') and (f:equivalence/@value != 'inexact')))
ConceptMap.group.element.target.dependsOn
Definition | A set of additional dependencies for this mapping to hold. This mapping is only applicable if the specified element can be resolved, and it has the specified value.
Control | 0..*
ConceptMap.group.element.target.dependsOn.property
Definition | A reference to an element that holds a coded value that corresponds to a code system property. The idea is that the information model carries an element somwhere that is labeled to correspond with a code system property.
Control | 1..1
Type | uri
ConceptMap.group.element.target.dependsOn.system
Definition | An absolute URI that identifies the code system of the dependency code (if the source/dependency is a value set that crosses code systems).
Control | 0..1
Type | uri
Meaning if Missing | The code is in the source (dependsOn) or target (product) system
ConceptMap.group.element.target.dependsOn.code
Definition | Identity (code or path) or the element/item/ValueSet that the map depends on / refers to.
Control | 1..1
Type | string
ConceptMap.group.element.target.dependsOn.display
Definition | The display for the code. The display is only provided to help editors when editing the concept map.
Control | 0..1
Type | string
Comments | The display is ignored when processing the map.
ConceptMap.group.element.target.product
Definition | A set of additional outcomes from this mapping to other elements. To properly execute this mapping, the specified element must be mapped to some data element or source that is in context. The mapping may still be useful without a place for the additional data elements, but the equivalence cannot be relied on.
Control | 0..*
Type | See ConceptMap.group.element.target.dependsOn
ConceptMap.group.unmapped
Definition | What to do when there is no match in the mappings in the group.
Control | 0..1
Comments | This only applies if the source code is in the system defined for the group.
Invariants | Defined on this element cmd-2: If the mode is 'fixed', a code must be provided (expression : (mode = 'fixed') implies code.exists(), xpath: (f:mode/@value != 'fixed') or exists(f:code)) cmd-3: If the mode is 'other-map', a code must be provided (expression : (mode = 'other-map') implies url.exists(), xpath: (f:mode/@value != 'other-map') or exists(f:url))
ConceptMap.group.unmapped.mode
Definition | Defines which action to take if there is no match in the group. One of 3 actions is possible: use the unmapped code (this is useful when doing a mapping between versions, and only a few codes have changed), use a fixed code (a default code), or alternatively, a reference to a different concept map can be provided (by canonical URL).
Control | 1..1
Terminology Binding | ConceptMapGroupUnmappedMode (Required)
Type | code
ConceptMap.group.unmapped.code
Definition | The fixed code to use when the mode = 'fixed' - all unmapped codes are mapped to a single fixed code.
Control | 0..1
Type | code
ConceptMap.group.unmapped.display
Definition | The display for the code. The display is only provided to help editors when editing the concept map.
Control | 0..1
Type | string
Comments | The display is ignored when processing the map.
ConceptMap.group.unmapped.url
Definition | The canonical URL of the map to use if this map contains no mapping.
Control | 0..1
Type | uri

4.9.11 Resource ConceptMap - Mappings

URL: https://hl7.org/fhir/STU3/conceptmap-mappings.html

This page is part of the FHIR Specification (v3.0.2: STU 3). The current version which supercedes this version is 4.0.1. For a full list of available versions, see the Directory of published versions

4.9.11 Resource ConceptMap - Mappings

Vocabulary Work Group | Maturity Level: N/A | Ballot Status: Informative | Compartments: Not linked to any defined compartments

Mappings:

RIM Mapping

Mappings for the conceptmap resource.

4.9.11.1 Mappings for RIM Mapping (http://hl7.org/v3)

ConceptMap | N/A

4.9.12 Resource ConceptMap - Design Notes

URL: https://hl7.org/fhir/STU3/conceptmap-explanations.html

This page is part of the FHIR Specification (v3.0.2: STU 3). The current version which supercedes this version is 4.0.1. For a full list of available versions, see the Directory of published versions

4.9.12 Resource ConceptMap - Design Notes

to do

4.9.13 Resource ConceptMap - Extensions & Profiles

URL: https://hl7.org/fhir/STU3/conceptmap-profiles.html

This page is part of the FHIR Specification (v3.0.2: STU 3). The current version which supercedes this version is 4.0.1. For a full list of available versions, see the Directory of published versions

4.9.13 Resource ConceptMap - Extensions & Profiles

Vocabulary Work Group | Maturity Level: N/A | Ballot Status: Informative

This table lists profiles and extensions for the ConceptMap resource. For background information, see Profiling Resources and Extensibility. Additional profiles and resources may be found in published Implementation Guides , or in the Conformance resource registry .

4.9.13.1 Profiles

No Profiles defined for this resource

4.9.13.2 Extensions

concept-bidirectional | bidirectional | for ConceptMap HL7 Extensions
resource-approvalDate | approvalDate | for Resource HL7 Extensions
resource-effectivePeriod | effectivePeriod | for Resource HL7 Extensions
resource-lastReviewDate | lastReviewDate | for Resource HL7 Extensions

Extensions that reference this resource:

11179-permitted-value-conceptmap | permitted-value-conceptmap | for ISO 11179 Element Definition Profile
codesystem-map | map | for CodeSystem HL7 Extensions
questionnaire-deMap | deMap | for Core extensions for Questionnaire
valueset-map | map | for ValueSet HL7 Extensions

4.9.13.3 Search Extensions

No Search Extensions defined for this resource

4.9.14 ConceptMap HL7 Extensions

URL: https://hl7.org/fhir/STU3/conceptmap-extensions.html

Defines common extensions used with or related to the ConceptMap resource

This page is part of the FHIR Specification (v3.0.2: STU 3). The current version which supercedes this version is 4.0.1. For a full list of available versions, see the Directory of published versions

4.9.14 ConceptMap HL7 Extensions

(No assigned work group) | Maturity Level: N/A | Ballot Status: Informative

4.9.14.1 Content

Extensions:
concept-bidirectional | bidirectional : Set to true of the concept map can be safely intepreted in reversse.

4.9.15 Resource ConceptMap - Operations

URL: https://hl7.org/fhir/STU3/conceptmap-operations.html

This page is part of the FHIR Specification (v3.0.2: STU 3). The current version which supercedes this version is 4.0.1. For a full list of available versions, see the Directory of published versions

4.9.15 Resource ConceptMap - Operations

Vocabulary Work Group | Maturity Level: 3 | Trial Use | Compartments: Not linked to any defined compartments

This resource has 2 operations associated with it:

$translate | Concept Translation
$closure | Closure Table Maintenance

For more information about operations, including how they are invoked, see Operations.

4.9.15.1 Concept Translation

Translate a code from one value set to another, based on the existing value set and concept maps resources, and/or other additional knowledge available to the server.

One (and only one) of the in parameters (code, coding, codeableConcept) must be provided, to identify the code that is to be translated.

The operation returns a set of parameters including a 'result' for whether there is an acceptable match, and a list of possible matches. Note that the list of matches may include notes of codes for which mapping is specifically excluded, so implementers have to check the match.equivalence for each match

The official URL for this operation definition is

```
http://hl7.org/fhir/OperationDefinition/ConceptMap-translate
```

Formal Definition (as a OperationDefinition).

URL: [base]/ConceptMap/$translate

URL: [base]/ConceptMap/[id]/$translate

This is an idempotent operation

In Parameters:

Name | Cardinality | Type | Binding | Profile | Documentation
code | 0..1 | code | | | The code that is to be translated. If a code is provided, a system must be provided
system | 0..1 | uri | | | The system for the code that is to be translated
version | 0..1 | string | | | The version of the system, if one was provided in the source data
source | 0..1 | uri | | | Identifies the value set used when the concept (system/code pair) was chosen. May be a logical id, or an absolute or relative location. The source value set is an optional parameter because in some cases, the client cannot know what the source value set is. However, without a source value set, the server may be unable to safely identify an applicable concept map, and would return an error. For this reason, a source value set SHOULD always be provided. Note that servers may be able to identify an appropriate concept map without a source value set if there is a full mapping for the entire code system in the concept map, or by manual intervention
coding | 0..1 | Coding | | | A coding to translate
codeableConcept | 0..1 | CodeableConcept | | | A full codeableConcept to validate. The server can translate any of the coding values (e.g. existing translations) as it chooses
target | 0..1 | uri | | | Identifies the value set in which a translation is sought. May be a logical id, or an absolute or relative location. If there's no target specified, the server should return all known translations, along with their source
targetsystem | 0..1 | uri | | | identifies a target code system in which a mapping is sought. This parameter is an alternative to the target parameter - only one is required. Searching for any translation to a target code system irrespective of the context (e.g. target valueset) may lead to unsafe results, and it is at the discretion of the server to decide when to support this operation
dependency | 0..* | | | | Another element that may help produce the correct mapping
dependency.element | 0..1 | uri | | | The element for this dependency
dependency.concept | 0..1 | CodeableConcept | | | The value for this dependency
reverse | 0..1 | boolean | | | if this is true, then the operation should return all the codes that might be mapped to this code. This parameter reverses the meaning of the source and target parameters

Out Parameters:

Name | Cardinality | Type | Binding | Profile | Documentation
result | 1..1 | boolean | | | True if the concept could be translated successfully. The value can only be true if at least one returned match has an equivalence which is not unmatched or disjoint
message | 0..1 | string | | | Error details, for display to a human. If this is provided when result = true, the message carries hints and warnings (e.g. a note that the matches could be improved by providing additional detail)
match | 0..* | | | | A concept in the target value set with an equivalence. Note that there may be multiple matches of equal or differing equivalence, and the matches may include equivalence values that mean that there is no match
match.equivalence | 0..1 | code | | | A code indicating the equivalence of the translation, using values from [ConceptMapEquivalence]{concept-map-equivalence.html}
match.concept | 0..1 | Coding | | | The translation outcome. Note that this would never have userSelected = true, since the process of translations implies that the user is not selecting the code (and only the client could know differently)
match.product | 0..* | | | | Another element that is the product of this mapping
match.product.element | 0..1 | uri | | | The element for this product
match.product.concept | 0..1 | Coding | | | The value for this product
match.source | 0..1 | uri | | | The canonical URI for the concept map from which this mapping comes from

4.9.15.1.1 Examples

Request:

```
GET [base]/ConceptMap/$translate?system=http://hl7.org/fhir/composition-status
  &code=preliminary&valueSet= http://hl7.org/fhir/ValueSet/composition-status
  &target=http://hl7.org/fhir/ValueSet/v3-ActStatus
```

Response:

```
HTTP/1.1 200 OK
[other headers]
```

```
{
  "resourceType": "Parameters",
  "parameter": [
    {
      "name": "result",
      "valueBoolean": true
    },
    {
      "name": "match",
      "part": [
        {
          "name": "equivalence",
          "valueCode": "equivalent"
        },
        {
          "name": "concept",
          "valueCoding": {
            "system": "http://hl7.org/fhir/v3/ActStatus",
            "code": "active",
            "userSelected": false
          }
        }
      ]
    }
  ]
}
```

4.9.15.2 Closure Table Maintenance

This operation provides support for ongoing maintenance of a client-side transitive closure table based on server-side terminological logic. For details of how this is used, see Maintaining a Closure Table

The official URL for this operation definition is

```
http://hl7.org/fhir/OperationDefinition/ConceptMap-closure
```

Formal Definition (as a OperationDefinition).

URL: [base]/$closure

This is not an idempotent operation

In Parameters:

Name | Cardinality | Type | Binding | Profile | Documentation

name | 1..1 | string | | | The name that defines the particular context for the subsumption based closure table

concept | 0..* | Coding | | | Concepts to add to the closure table

version | 0..1 | id | | | A request to resynchronise - request to send all new entries since the nominated version was sent by the server

Out Parameters:

Name | Cardinality | Type | Binding | Profile | Documentation

return | 1..1 | ConceptMap | | | A list of new entries (code / system --> code/system) that the client should add to its closure table. The only kind of entry mapping equivalences that can be returned are equal, specializes, subsumes and unmatched Note: as this the only out parameter, it is a resource, and it has the name 'return', the result of this operation is returned directly as a resource

4.9.15.2.1 Examples

Request:

```
POST [base]/$closure

{
  "resourceType" : "Parameters",
  "parameter" : [
    {
      "name" : "name",
      "valueString" : "patient-problems"
    },
    {
      "name" : "concept",
      "valueCoding" : {
        "system" : "http://snomed.info/sct",
        "code" : "22298006",
      }
    }
  ]
}
```

Response:

```
HTTP/1.1 200 OK
[other headers]

{
  "resourceType": "ConceptMap",
  "identifier": "49088976-d54d-4d19-b868-3d4c18cebabb",
  "version": "8",
  "status": "active",
  "experimental": true,
  "date": "2012-06-13",
  "element": [
    {
```

```
      "codeSystem": "http://snomed.info/sct",
      "code": "22298006",
      "map": [
        {
          "codeSystem": "http://snomed.info/sct",
          "code": "128599005",
          "equivalence": "subsumes"
        }
      ]
    },
  ]
}
```

4.9.16 Resource ConceptMap - Detailed Descriptions

URL: https://hl7.org/fhir/STU3/conceptmap-version-maps.html

This page is part of the FHIR Specification (v3.0.2: STU 3). The current version which supercedes this version is 4.0.1. For a full list of available versions, see the Directory of published versions

4.9.16 Resource ConceptMap - Detailed Descriptions

Vocabulary Work Group | Maturity Level: N/A | Ballot Status: Informative | Compartments: Not linked to any defined compartments

R2 : R3 Converson maps for ConceptMap.

Functional status for this map: 2 tests that all execute ok. All tests pass round-trip testing and 1 r3 resources are invalid (1 errors). (see documentation)

4.9.16.1 R2 to R3

```
map "http://hl7.org/fhir/StructureMap/ConceptMap2to3" = "R2 to R3 Conversions for ConceptMap"

uses "http://hl7.org/fhir/DSTU2/StructureDefinition/ConceptMap" alias ConceptMapR2 as source
uses "http://hl7.org/fhir/StructureDefinition/ConceptMap" alias ConceptMap as target

imports "http://hl7.org/fhir/StructureMap/primitives2to3"
imports "http://hl7.org/fhir/StructureMap/DomainResource2to3"
imports "http://hl7.org/fhir/StructureMap/CodeableConcept2to3"
imports "http://hl7.org/fhir/StructureMap/ContactPoint2to3"
imports "http://hl7.org/fhir/StructureMap/Identifier2to3"
imports "http://hl7.org/fhir/StructureMap/Reference2to3"

group for type+types  ConceptMap extends DomainResource
  input src : ConceptMapR2 as source
  input tgt : ConceptMap as target

  "ConceptMap-url" : for src.url make tgt.url
  "ConceptMap-identifier" : for src.identifier make tgt.identifier
  "ConceptMap-version" : for src.version make tgt.version
  "ConceptMap-name" : for src.name make tgt.name
  "ConceptMap-status" : for src.status make tgt.status
  "ConceptMap-experimental" : for src.experimental make tgt.experimental
  "ConceptMap-publisher" : for src.publisher make tgt.publisher
  "ConceptMap-contact" : for src.contact as vs0 make tgt.contact as vt0 then {
    "ContactDetail-name" : for vs0.name make vt0.name
    "ContactDetail-telecom" : for vs0.telecom make vt0.telecom
  }

  "ConceptMap-date" : for src.date make tgt.date
  "ConceptMap-description" : for src.description make tgt.description
  "ConceptMap-purpose" : for src.requirements make tgt.purpose
  "ConceptMap-copyright" : for src.copyright make tgt.copyright
  "ConceptMap-jurisdiction" : for src.useContext where coding.system = 'urn:iso:std:iso:3166' make tgt.jurisdiction
  "ConceptMap-useContext" : for src.useContext as vs where (coding.system = 'urn:iso:std:iso:3166').not() make
    tgt.useContext as uc,  uc.code as ucc,  ucc.system = "http://hl7.org/fhir/usage-context-type",  ucc.code = "task",
    uc.value = create("CodeableConcept") as vt then CodeableConcept(vs, vt)
  "ConceptMap-source" : for src.source make tgt.source
  "ConceptMap-target" : for src.target make tgt.target

  // ConceptMap-backbone:     group src.element as srcE by srcE.codeSystem as srcSCs, inner srcE.target as srcT by
    srcT.codeSystem as srcTCs make tgt.group as tgtGrp, tgtGrp.source = srcSCs, tgtGrp.target = srcTCs then {
  "ConceptMap-element-1" : for src.element as srcE then {
    "ConceptMap-element-2" : for srcE.target as srcT make tgt.group as tgtGrp, tgtGrp.element as tgtE, tgtE.target as
    tgtT then {
      "ConceptMap-element-3" : for srcE.codeSystem make tgtGrp.source
      "ConceptMap-element-4" : for srcT.codeSystem make tgtGrp.target
      "ConceptMap-element-code":  for srcE.code make tgtE.code
      "ConceptMap-target-element":  for srcT.code make tgtT.code
      "ConceptMap-target-equivalence":  for srcT.equivalence make tgtT.equivalence
      "ConceptMap-target-comments":  for srcT.comments make tgtT.comment
      "ConceptMap-target-dependsOn":  for srcT.dependsOn as vs make tgtT.dependsOn as vt then {
        "ConceptMap-target-dependsOn-element": for vs.element make vt.property
        "ConceptMap-target-dependsOn-codeSystem": for vs.codeSystem make vt.system
        "ConceptMap-target-dependsOn-code": for vs.code make vt.code
      }
      "ConceptMap-target-product":  for srcT.product as vs make tgtT.product as vt then {
        "ConceptMap-target-product-element": for vs.element make vt.property
        "ConceptMap-target-product-codeSystem": for vs.codeSystem make vt.system
```

```
        "ConceptMap-target-product-code": for vs.code make vt.code
      }
    }
  }

endgroup
```

4.9.16.2 R3 to R2

```
map "http://hl7.org/fhir/StructureMap/ConceptMap3to2" = "R3 to R2 Conversion for ConceptMap"

uses "http://hl7.org/fhir/StructureDefinition/ConceptMap" alias ConceptMap as source
uses "http://hl7.org/fhir/DSTU2/StructureDefinition/ConceptMap" alias ConceptMapR2 as target

imports "http://hl7.org/fhir/StructureMap/primitives3to2"
imports "http://hl7.org/fhir/StructureMap/DomainResource3to2"
imports "http://hl7.org/fhir/StructureMap/ContactPoint3to2"
imports "http://hl7.org/fhir/StructureMap/Identifier3to2"
imports "http://hl7.org/fhir/StructureMap/Reference3to2"
imports "http://hl7.org/fhir/StructureMap/CodeableConcept3to2"

group for type+types  ConceptMap extends DomainResource
  input src : ConceptMap as source
  input tgt : ConceptMapR2 as target

  "ConceptMap-url" : for src.url make tgt.url
  "ConceptMap-identifier" : for src.identifier make tgt.identifier
  "ConceptMap-version" : for src.version make tgt.version
  "ConceptMap-name" : for src.name make tgt.name
  "ConceptMap-status" : for src.status make tgt.status
  "ConceptMap-experimental" : for src.experimental make tgt.experimental
  "ConceptMap-publisher" : for src.publisher make tgt.publisher
  "ConceptMap-contact" : for src.contact as vs0 make tgt.contact as vt0 then {
    "ConceptMap.contact-name" : for vs0.name make vt0.name
    "ConceptMap.contact-telecom" : for vs0.telecom make vt0.telecom
  }

  "ConceptMap-date" : for src.date make tgt.date
  "ConceptMap-description" : for src.description make tgt.description
  "ConceptMap-useContext-1" : for src.jurisdiction make tgt.useContext
  "ConceptMap-useContext" : for src.useContext as vs then {
    "ConceptMap-useContext-value" : for vs.value make tgt.useContext
  }
  "ConceptMap-requirements" : for src.purpose make tgt.requirements
  "ConceptMap-copyright" : for src.copyright make tgt.copyright

  "ConceptMap-source" : for src.source make tgt.source
  "ConceptMap-target" : for src.target make tgt.target

  "ConceptMap-group" : for src.group as grp then {
    "ConceptMap-group-element" : for grp.element as els make tgt.element as elt then {
      "ConceptMap-element-code" : for grp.source make elt.codeSystem
      "ConceptMap-element-code" : for els.code make elt.code
      "ConceptMap-element-target" : for els.target as srcT make elt.target as tgtT then  {
        "ConceptMap-target-codeSystem":  for grp.target make tgtT.codeSystem
        "ConceptMap-target-code":  for srcT.code make tgtT.code
        "ConceptMap-target-equivalence":  for srcT.equivalence make tgtT.equivalence
        "ConceptMap-target-comments":  for srcT.comment make tgtT.comments
        "ConceptMap-target-dependsOn":  for srcT.dependsOn as vs make tgtT.dependsOn as vt then {
          "ConceptMap-target-dependsOn-element": for vs.property make vt.element
          "ConceptMap-target-dependsOn-codeSystem": for vs.system make vt.codeSystem
          "ConceptMap-target-dependsOn-code": for vs.code make vt.code
        }
        "ConceptMap-target-product":  for srcT.product as vs make tgtT.product as vt then {
          "ConceptMap-target-product-element": for vs.property make vt.element
          "ConceptMap-target-product-codeSystem": for vs.system make vt.codeSystem
          "ConceptMap-target-product-code": for vs.code make vt.code
        }
      }
    }
  }
endgroup
```

4.9.16.3 R3 Validation Errors

102 | WARNING @ ConceptMap.group[41].element.target.comment: value should not start or finish with whitespace (src = InstanceValidator)

4.10 Resource NamingSystem - Content

URL: https://hl7.org/fhir/STU3/namingsystem.html

This page is part of the FHIR Specification (v3.0.2: STU 3). The current version which supercedes this version is 4.0.1. For a full list of available versions, see the Directory of published versions

FHIR Infrastructure Work Group | Maturity Level: 1 | Trial Use | Compartments: Not linked to any defined compartments

A curated namespace that issues unique symbols within that namespace for the identification of concepts, people, devices, etc. Represents a "System" used within the Identifier and Coding data types.

4.10.1 Scope and Usage

Defines a specific code system or identifier system, so that it can be noted in a registry for other systems to find and understand an identifier.

4.10.2 Boundaries and Relationships

The CodeSystem resource defines the content of a code system, and also its preferred identifier. The NamingSystem resource identifies the existence of a code or identifier system, and its possible and preferred identifiers. The key difference between the resources is who creates and manages them - CodeSystem resources are managed by the owner of the code system resource, who can properly define the features and content of the code system. NamingSystem resources, on the other hand, are frequently defined by 3rd parties that encounter the code system in use, and need to describe the use, but do not have the authority to define the features and content. Additionally, there may be multiple authoritative NamingSystem resources for a code system, but there should only be one CodeSystem resource.

4.10.3 Background and Context

For discussion of policy for creating well maintained OIDs and URIs for resources, see The HL7 WIKI .

4.10.4 Resource Content

* Structure

* UML

* XML

* JSON

* Turtle

* R2 Diff

* All

Structure

Name | Flags | Card. | Type | Description & Constraints
NamingSystem | I | | DomainResource | System of unique identification + Root systems cannot have uuid identifiers + Can only have replacedBy if naming system is retired + Can't have more than one preferred identifier for a type Elements defined in Ancestors: id, meta, implicitRules, language, text, contained, extension, modifierExtension
name | ? | 1..1 | string | Name for this naming system (computer friendly)
status | ?!? | 1..1 | code | draft | active | retired | unknown PublicationStatus (Required)
kind | | 1..1 | code | codesystem | identifier | root NamingSystemType (Required)
date | ? | 1..1 | dateTime | Date this was last changed
publisher | ? | 0..1 | string | Name of the publisher (organization or individual)
contact | ? | 0..* | ContactDetail | Contact details for the publisher
responsible | | 0..1 | string | Who maintains system namespace?
type | | 0..1 | CodeableConcept | e.g. driver, provider, patient, bank etc. Identifier Type Codes (Extensible)
description | | 0..1 | markdown | Natural language description of the naming system
useContext | ? | 0..* | UsageContext | Context the content is intended to support
jurisdiction | ? | 0..* | CodeableConcept | Intended jurisdiction for naming system (if applicable) Jurisdiction ValueSet (Extensible)
usage | | 0..1 | string | How/where is it used
uniqueId | | 1..* | BackboneElement | Unique identifiers used for system
type | | 1..1 | code | oid | uuid | uri | other NamingSystemIdentifierType (Required)
value | | 1..1 | string | The unique identifier
preferred | | 0..1 | boolean | Is this the id that should be used for this type
comment | | 0..1 | string | Notes about identifier usage
period | | 0..1 | Period | When is identifier valid?
replacedBy | I | 0..1 | Reference(NamingSystem) | Use this instead
Documentation for this format

UML Diagram (Legend)

XML Template

```
<NamingSystem xmlns="http://hl7.org/fhir">
 <!-- from Resource: id, meta, implicitRules, and language -->
 <!-- from DomainResource: text, contained, extension, and modifierExtension -->
 <name value="[string]"/><!-- 1..1 Name for this naming system (computer friendly) -->
 <status value="[code]"/><!-- 1..1 draft | active | retired | unknown -->
 <kind value="[code]"/><!-- 1..1 codesystem | identifier | root -->
 <date value="[dateTime]"/><!-- 1..1 Date this was last changed -->
 <publisher value="[string]"/><!-- 0..1 Name of the publisher (organization or individual) -->
 <contact><!-- 0..* ContactDetail Contact details for the publisher --></contact>
 <responsible value="[string]"/><!-- 0..1 Who maintains system namespace? -->
 <type><!-- 0..1 CodeableConcept e.g. driver,  provider,  patient, bank etc. --></type>
 <description value="[markdown]"/><!-- 0..1 Natural language description of the naming system -->
 <useContext><!-- 0..* UsageContext Context the content is intended to support --></useContext>
 <jurisdiction><!-- 0..* CodeableConcept Intended jurisdiction for naming system (if applicable) --></jurisdiction>
 <usage value="[string]"/><!-- 0..1 How/where is it used -->
 <uniqueId>  <!-- 1..* Unique identifiers used for system -->
  <type value="[code]"/><!-- 1..1 oid | uuid | uri | other -->
```

```
  <value value="[string]"/><!-- 1..1 The unique identifier -->
  <preferred value="[boolean]"/><!-- 0..1 Is this the id that should be used for this type -->
  <comment value="[string]"/><!-- 0..1 Notes about identifier usage -->
  <period><!-- 0..1 Period When is identifier valid? --></period>
 </uniqueId>
 <replacedBy><!--  0..1 Reference(NamingSystem) Use this instead --></replacedBy>
</NamingSystem>
```

JSON Template

```
{
  "resourceType" : "NamingSystem",
  // from Resource: id, meta, implicitRules, and language
  // from DomainResource: text, contained, extension, and modifierExtension
  "name" : "<string>", // R!  Name for this naming system (computer friendly)
  "status" : "<code>", // R!  draft | active | retired | unknown
  "kind" : "<code>", // R!  codesystem | identifier | root
  "date" : "<dateTime>", // R!  Date this was last changed
  "publisher" : "<string>", // Name of the publisher (organization or individual)
  "contact" : [{ ContactDetail }], // Contact details for the publisher
  "responsible" : "<string>", // Who maintains system namespace?
  "type" : { CodeableConcept }, // e.g. driver,  provider,  patient, bank etc.
  "description" : "<markdown>", // Natural language description of the naming system
  "useContext" : [{ UsageContext }], // Context the content is intended to support
  "jurisdiction" : [{ CodeableConcept }], // Intended jurisdiction for naming system (if applicable)
  "usage" : "<string>", // How/where is it used
  "uniqueId" : [{ // R!  Unique identifiers used for system
    "type" : "<code>", // R!  oid | uuid | uri | other
    "value" : "<string>", // R!  The unique identifier
    "preferred" : <boolean>, // Is this the id that should be used for this type
    "comment" : "<string>", // Notes about identifier usage
    "period" : { Period } // When is identifier valid?
  }],
  "replacedBy" : { Reference(NamingSystem) } // C? Use this instead
}
```

Turtle Template

```
@prefix fhir: <http://hl7.org/fhir/> .


[ a fhir:NamingSystem;
  fhir:nodeRole fhir:treeRoot; # if this is the parser root

  # from Resource: .id, .meta, .implicitRules, and .language
  # from DomainResource: .text, .contained, .extension, and .modifierExtension
  fhir:NamingSystem.name [ string ]; # 1..1 Name for this naming system (computer friendly)
  fhir:NamingSystem.status [ code ]; # 1..1 draft | active | retired | unknown
  fhir:NamingSystem.kind [ code ]; # 1..1 codesystem | identifier | root
  fhir:NamingSystem.date [ dateTime ]; # 1..1 Date this was last changed
  fhir:NamingSystem.publisher [ string ]; # 0..1 Name of the publisher (organization or individual)
  fhir:NamingSystem.contact [ ContactDetail ], ... ; # 0..* Contact details for the publisher
  fhir:NamingSystem.responsible [ string ]; # 0..1 Who maintains system namespace?
  fhir:NamingSystem.type [ CodeableConcept ]; # 0..1 e.g. driver,  provider,  patient, bank etc.
  fhir:NamingSystem.description [ markdown ]; # 0..1 Natural language description of the naming system
  fhir:NamingSystem.useContext [ UsageContext ], ... ; # 0..* Context the content is intended to support
  fhir:NamingSystem.jurisdiction [ CodeableConcept ], ... ; # 0..* Intended jurisdiction for naming system (if
    applicable)
  fhir:NamingSystem.usage [ string ]; # 0..1 How/where is it used
  fhir:NamingSystem.uniqueId [ # 1..* Unique identifiers used for system
    fhir:NamingSystem.uniqueId.type [ code ]; # 1..1 oid | uuid | uri | other
    fhir:NamingSystem.uniqueId.value [ string ]; # 1..1 The unique identifier
    fhir:NamingSystem.uniqueId.preferred [ boolean ]; # 0..1 Is this the id that should be used for this type
    fhir:NamingSystem.uniqueId.comment [ string ]; # 0..1 Notes about identifier usage
    fhir:NamingSystem.uniqueId.period [ Period ]; # 0..1 When is identifier valid?
  ], ...;
  fhir:NamingSystem.replacedBy [ Reference(NamingSystem) ]; # 0..1 Use this instead
]
```

Changes since DSTU2

NamingSystem

NamingSystem.status | Change value set from http://hl7.org/fhir/ValueSet/conformance-resource-status to http://hl7.org/fhir/ValueSet/publication-status

NamingSystem.contact | Type changed from BackboneElement to ContactDetail

NamingSystem.description | Type changed from string to markdown

NamingSystem.useContext | Type changed from CodeableConcept to UsageContext Remove Binding http://hl7.org/fhir/ValueSet/use-context (extensible)

NamingSystem.jurisdiction | Added Element

NamingSystem.uniqueId.comment | Added Element

NamingSystem.contact.name | deleted

NamingSystem.contact.telecom | deleted

See the Full Difference for further information

This analysis is available as XML or JSON.

See R2 <--> R3 Conversion Maps (status = 3 tests that all execute ok. All tests pass round-trip testing and all r3 resources are valid.).

Structure

Name | Flags | Card. | Type | Description & Constraints

NamingSystem | I | | DomainResource | System of unique identification + Root systems cannot have uuid identifiers + Can only have replacedBy if naming system is retired + Can't have more than one preferred identifier for a type Elements defined in Ancestors: id, meta, implicitRules, language, text, contained, extension, modifierExtension

name | ? | 1..1 | string | Name for this naming system (computer friendly)

status | ?!? | 1..1 | code | draft | active | retired | unknown PublicationStatus (Required)

kind | | 1..1 | code | codesystem | identifier | root NamingSystemType (Required)

date | ? | 1..1 | dateTime | Date this was last changed

publisher | ? | 0..1 | string | Name of the publisher (organization or individual)

contact | ? | 0..* | ContactDetail | Contact details for the publisher

responsible | | 0..1 | string | Who maintains system namespace?

type | | 0..1 | CodeableConcept | e.g. driver, provider, patient, bank etc. Identifier Type Codes (Extensible)

description | | 0..1 | markdown | Natural language description of the naming system

useContext | ? | 0..* | UsageContext | Context the content is intended to support

jurisdiction | ? | 0..* | CodeableConcept | Intended jurisdiction for naming system (if applicable) Jurisdiction ValueSet (Extensible)

usage | | 0..1 | string | How/where is it used

uniqueId | | 1..* | BackboneElement | Unique identifiers used for system

type | | 1..1 | code | oid | uuid | uri | other NamingSystemIdentifierType (Required)

value | | 1..1 | string | The unique identifier

preferred | | 0..1 | boolean | Is this the id that should be used for this type

comment | | 0..1 | string | Notes about identifier usage

period | | 0..1 | Period | When is identifier valid?

replacedBy | I | 0..1 | Reference(NamingSystem) | Use this instead

Documentation for this format

UML Diagram (Legend)

XML Template

```
<NamingSystem xmlns="http://hl7.org/fhir">
 <!-- from Resource: id, meta, implicitRules, and language -->
 <!-- from DomainResource: text, contained, extension, and modifierExtension -->
 <name value="[string]"/><!-- 1..1 Name for this naming system (computer friendly) -->
 <status value="[code]"/><!-- 1..1 draft | active | retired | unknown -->
 <kind value="[code]"/><!-- 1..1 codesystem | identifier | root -->
 <date value="[dateTime]"/><!-- 1..1 Date this was last changed -->
 <publisher value="[string]"/><!-- 0..1 Name of the publisher (organization or individual) -->
 <contact><!-- 0..* ContactDetail Contact details for the publisher --></contact>
 <responsible value="[string]"/><!-- 0..1 Who maintains system namespace? -->
 <type><!-- 0..1 CodeableConcept e.g. driver,  provider,  patient, bank etc. --></type>
 <description value="[markdown]"/><!-- 0..1 Natural language description of the naming system -->
 <useContext><!-- 0..* UsageContext Context the content is intended to support --></useContext>
 <jurisdiction><!-- 0..* CodeableConcept Intended jurisdiction for naming system (if applicable) --></jurisdiction>
 <usage value="[string]"/><!-- 0..1 How/where is it used -->
 <uniqueId>  <!-- 1..* Unique identifiers used for system -->
  <type value="[code]"/><!-- 1..1 oid | uuid | uri | other -->
  <value value="[string]"/><!-- 1..1 The unique identifier -->
  <preferred value="[boolean]"/><!-- 0..1 Is this the id that should be used for this type -->
  <comment value="[string]"/><!-- 0..1 Notes about identifier usage -->
  <period><!-- 0..1 Period When is identifier valid? --></period>
 </uniqueId>
 <replacedBy><!--  0..1 Reference(NamingSystem) Use this instead --></replacedBy>
</NamingSystem>
```

JSON Template

```
{
  "resourceType" : "NamingSystem",
  // from Resource: id, meta, implicitRules, and language
  // from DomainResource: text, contained, extension, and modifierExtension
  "name" : "<string>", // R!  Name for this naming system (computer friendly)
  "status" : "<code>", // R!  draft | active | retired | unknown
  "kind" : "<code>", // R!  codesystem | identifier | root
  "date" : "<dateTime>", // R!  Date this was last changed
  "publisher" : "<string>", // Name of the publisher (organization or individual)
  "contact" : [{ ContactDetail }], // Contact details for the publisher
  "responsible" : "<string>", // Who maintains system namespace?
  "type" : { CodeableConcept }, // e.g. driver,  provider,  patient, bank etc.
  "description" : "<markdown>", // Natural language description of the naming system
  "useContext" : [{ UsageContext }], // Context the content is intended to support
  "jurisdiction" : [{ CodeableConcept }], // Intended jurisdiction for naming system (if applicable)
  "usage" : "<string>", // How/where is it used
  "uniqueId" : [{ // R!  Unique identifiers used for system
    "type" : "<code>", // R!  oid | uuid | uri | other
    "value" : "<string>", // R!  The unique identifier
    "preferred" : <boolean>, // Is this the id that should be used for this type
    "comment" : "<string>", // Notes about identifier usage
    "period" : { Period } // When is identifier valid?
  }],
  "replacedBy" : { Reference(NamingSystem) } // C? Use this instead
}
```

Turtle Template

```
@prefix fhir: <http://hl7.org/fhir/> .
```

```
[ a fhir:NamingSystem;
  fhir:nodeRole fhir:treeRoot; # if this is the parser root

  # from Resource: .id, .meta, .implicitRules, and .language
  # from DomainResource: .text, .contained, .extension, and .modifierExtension
  fhir:NamingSystem.name [ string ]; # 1..1 Name for this naming system (computer friendly)
  fhir:NamingSystem.status [ code ]; # 1..1 draft | active | retired | unknown
  fhir:NamingSystem.kind [ code ]; # 1..1 codesystem | identifier | root
  fhir:NamingSystem.date [ dateTime ]; # 1..1 Date this was last changed
  fhir:NamingSystem.publisher [ string ]; # 0..1 Name of the publisher (organization or individual)
  fhir:NamingSystem.contact [ ContactDetail ], ... ; # 0..* Contact details for the publisher
  fhir:NamingSystem.responsible [ string ]; # 0..1 Who maintains system namespace?
  fhir:NamingSystem.type [ CodeableConcept ]; # 0..1 e.g. driver,  provider,  patient, bank etc.
  fhir:NamingSystem.description [ markdown ]; # 0..1 Natural language description of the naming system
  fhir:NamingSystem.useContext [ UsageContext ], ... ; # 0..* Context the content is intended to support
  fhir:NamingSystem.jurisdiction [ CodeableConcept ], ... ; # 0..* Intended jurisdiction for naming system (if
    applicable)
  fhir:NamingSystem.usage [ string ]; # 0..1 How/where is it used
  fhir:NamingSystem.uniqueId [ # 1..* Unique identifiers used for system
    fhir:NamingSystem.uniqueId.type [ code ]; # 1..1 oid | uuid | uri | other
    fhir:NamingSystem.uniqueId.value [ string ]; # 1..1 The unique identifier
    fhir:NamingSystem.uniqueId.preferred [ boolean ]; # 0..1 Is this the id that should be used for this type
    fhir:NamingSystem.uniqueId.comment [ string ]; # 0..1 Notes about identifier usage
    fhir:NamingSystem.uniqueId.period [ Period ]; # 0..1 When is identifier valid?
  ], ...;
  fhir:NamingSystem.replacedBy [ Reference(NamingSystem) ]; # 0..1 Use this instead
]
```

Changes since DSTU2

NamingSystem

NamingSystem.status | Change value set from http://hl7.org/fhir/ValueSet/conformance-resource-status to http://hl7.org/fhir/ValueSet/publication-status

NamingSystem.contact | Type changed from BackboneElement to ContactDetail

NamingSystem.description | Type changed from string to markdown

NamingSystem.useContext | Type changed from CodeableConcept to UsageContext Remove Binding http://hl7.org/fhir/ValueSet/use-context (extensible)

NamingSystem.jurisdiction | Added Element

NamingSystem.uniqueId.comment | Added Element

NamingSystem.contact.name | deleted

NamingSystem.contact.telecom | deleted

See the Full Difference for further information

This analysis is available as XML or JSON.

See R2 <--> R3 Conversion Maps (status = 3 tests that all execute ok. All tests pass round-trip testing and all r3 resources are valid.).

Alternate definitions: Master Definition (XML, JSON), XML Schema/Schematron (for) + JSON Schema, ShEx (for Turtle)

4.10.4.1 Terminology Bindings

Path | Definition | Type | Reference

NamingSystem.status | The lifecycle status of a Value Set or Concept Map. | Required | PublicationStatus

NamingSystem.kind | Identifies the purpose of the naming system. | Required | NamingSystemType

NamingSystem.type | A coded type for an identifier that can be used to determine which identifier to use for a specific purpose. | Extensible | Identifier Type Codes

NamingSystem.jurisdiction | Countries and regions within which this artifact is targeted for use | Extensible | Jurisdiction ValueSet

NamingSystem.uniqueId.type | Identifies the style of unique identifier used to identify a namespace. | Required | NamingSystemIdentifierType

4.10.4.2 Constraints

* nsd-1: Root systems cannot have uuid identifiers (expression : kind != 'root' or uniqueId.type = 'uuid')

* nsd-2: Can't have more than one preferred identifier for a type (expression : uniqueId.where(preferred = true).select(type).isDistinct())

* nsd-3: Can only have replacedBy if naming system is retired (expression : replacedBy.empty() or status = 'retired')

4.10.4.3 Dealing with duplicate entries

In some cases, the same code or identifier system might accidentally be created more than once in a registry, for example because someone failed to check for an existing entry before adding a new one or knows the same concept with a different name. If this occurs, one of the system entries should be deleted and the remaining entry should have its uniqueId updated to include any identifiers present on the original entry (and possibly have its descriptive information modified to include additional information from the duplicate entry).

4.10.5 Search Parameters

Search parameters for this resource. The common parameters also apply. See Searching for more information about searching in REST, messaging, and services.

Name | Type | Description | Expression | In Common

contact | string | Name of an individual to contact | NamingSystem.contact.name

date | date | The naming system publication date | NamingSystem.date
description | string | The description of the naming system | NamingSystem.description
id-type | token | oid | uuid | uri | other | NamingSystem.uniqueId.type
jurisdiction | token | Intended jurisdiction for the naming system | NamingSystem.jurisdiction
kind | token | codesystem | identifier | root | NamingSystem.kind
name | string | Computationally friendly name of the naming system | NamingSystem.name
period | date | When is identifier valid? | NamingSystem.uniqueId.period
publisher | string | Name of the publisher of the naming system | NamingSystem.publisher
replaced-by | reference | Use this instead | NamingSystem.replacedBy (NamingSystem)
responsible | string | Who maintains system namespace? | NamingSystem.responsible
status | token | The current status of the naming system | NamingSystem.status
telecom | token | Contact details for individual or organization | NamingSystem.contact.telecom
type | token | e.g. driver, provider, patient, bank etc. | NamingSystem.type
value | string | The unique identifier | NamingSystem.uniqueId.value

4.10.6 Resource NamingSystem - Examples

URL: https://hl7.org/fhir/STU3/namingsystem-examples.html

This page is part of the FHIR Specification (v3.0.2: STU 3). The current version which supercedes this version is 4.0.1. For a full list of available versions, see the Directory of published versions

4.10.6 Resource NamingSystem - Examples

FHIR Infrastructure Work Group | Maturity Level: N/A | Ballot Status: Informative | Compartments: Not linked to any defined compartments

Example List:

Example of how to use Naming System for a code system | example | XML | JSON | Turtle
Example of naming system for an identifier | example-id | XML | JSON | Turtle
Example of a deprecated naming system | example-replaced | XML | JSON | Turtle
Common US Driver's license identification | registry | XML | JSON | Turtle
Defined Code systems | terminologies | XML | JSON | Turtle

Usage note: every effort has been made to ensure that the examples are correct and useful, but they are not a normative part of the specification.

4.10.7 Resource NamingSystem - Detailed Descriptions

URL: https://hl7.org/fhir/STU3/namingsystem-definitions.html

This page is part of the FHIR Specification (v3.0.2: STU 3). The current version which supercedes this version is 4.0.1. For a full list of available versions, see the Directory of published versions

4.10.7 Resource NamingSystem - Detailed Descriptions

FHIR Infrastructure Work Group | Maturity Level: 1 | Trial Use | Compartments: Not linked to any defined compartments

Detailed Descriptions for the elements in the NamingSystem resource.

NamingSystem
Definition | A curated namespace that issues unique symbols within that namespace for the identification of concepts, people, devices, etc. Represents a "System" used within the Identifier and Coding data types.
Control | 1..1
Invariants | Defined on this element nsd-1: Root systems cannot have uuid identifiers (expression : kind != 'root' or uniqueId.type = 'uuid', xpath: not(f:kind/@value='root' and f:uniqueId/f:type/@value='uuid')) nsd-2: Can't have more than one preferred identifier for a type (expression : uniqueId.where(preferred = true).select(type).isDistinct(), xpath: not(exists(for $type in distinct-values(f:uniqueId/f:type/@value) return if (count(f:uniqueId[f:type/@value=$type and f:preferred/@value=true()])>1) then $type else ()))) nsd-3: Can only have replacedBy if naming system is retired (expression : replacedBy.empty() or status = 'retired', xpath: not(f:replacedBy) or f:status/@value='retired')
NamingSystem.name
Definition | A natural language name identifying the naming system. This name should be usable as an identifier for the module by machine processing applications such as code generation.
Control | 1..1
Type | string
Requirements | Support human navigation and code generation.
Summary | true
Comments | The name is not expected to be globally unique. The name should be a simple alpha-numeric type name to ensure that it is computable friendly. The"symbolic name" for an OID would be captured as an extension.
NamingSystem.status
Definition | The status of this naming system. Enables tracking the life-cycle of the content.
Control | 1..1
Terminology Binding | PublicationStatus (Required)
Type | code
Is Modifier | true
Summary | true
Comments | Allows filtering of naming systems that are appropriate for use vs. not. This is labeled as "Is Modifier" because applications should not use a retired naming system without due consideration.
NamingSystem.kind

Definition | Indicates the purpose for the naming system - what kinds of things does it make unique?
Control | 1..1
Terminology Binding | NamingSystemType (Required)
Type | code
NamingSystem.date
Definition | The date (and optionally time) when the naming system was published. The date must change if and when the business version changes and it must change if the status code changes. In addition, it should change when the substantive content of the naming system changes.
Control | 1..1
Type | dateTime
Alternate Names | Revision Date
Summary | true
Comments | Note that this is not the same as the resource last-modified-date, since the resource may be a secondary representation of the naming system. Additional specific dates may be added as extensions or be found by consulting Provenances associated with past versions of the resource.
NamingSystem.publisher
Definition | The name of the individual or organization that published the naming system.
Control | 0..1
Type | string
Requirements | Helps establish the "authority/credibility" of the naming system. May also allow for contact.
Summary | true
Comments | Usually an organization, but may be an individual. The publisher (or steward) of the naming system is the organization or individual primarily responsible for the maintenance and upkeep of the naming system. This is not necessarily the same individual or organization that developed and initially authored the content. The publisher is the primary point of contact for questions or issues with the naming system. This item SHOULD be populated unless the information is available from context.
NamingSystem.contact
Definition | Contact details to assist a user in finding and communicating with the publisher.
Control | 0..*
Type | ContactDetail
Summary | true
Comments | May be a web site, an email address, a telephone number, etc.
NamingSystem.responsible
Definition | The name of the organization that is responsible for issuing identifiers or codes for this namespace and ensuring their non-collision.
Control | 0..1
Type | string
Comments | This is the primary organization. Responsibility for some aspects of a namespace may be delegated.
NamingSystem.type
Definition | Categorizes a naming system for easier search by grouping related naming systems.
Control | 0..1
Terminology Binding | Identifier Type Codes (Extensible)
Type | CodeableConcept
Comments | This will most commonly be used for identifier namespaces, but categories could potentially be useful for code systems and authorities as well.
NamingSystem.description
Definition | A free text natural language description of the naming system from a consumer's perspective. Details about what the namespace identifies including scope, granularity, version labeling, etc.
Control | 0..1
Type | markdown
Comments | This description can be used to capture details such as why the naming system was built, comments about misuse, instructions for clinical use and interpretation, literature references, examples from the paper world, etc. It is not a rendering of the naming system as conveyed in the 'text' field of the resource itself. This item SHOULD be populated unless the information is available from context (e.g. the language of the profile is presumed to be the predominant language in the place the profile was created).
NamingSystem.useContext
Definition | The content was developed with a focus and intent of supporting the contexts that are listed. These terms may be used to assist with indexing and searching for appropriate naming system instances.
Control | 0..*
Type | UsageContext
Requirements | Assist in searching for appropriate content.
Summary | true
Comments | When multiple useContexts are specified, there is no expectation whether all or any of the contexts apply.
NamingSystem.jurisdiction
Definition | A legal or geographic region in which the naming system is intended to be used.
Control | 0..*
Terminology Binding | Jurisdiction ValueSet (Extensible)
Type | CodeableConcept
Summary | true
Comments | It may be possible for the naming system to be used in jurisdictions other than those for which it was originally designed or intended.
NamingSystem.usage
Definition | Provides guidance on the use of the namespace, including the handling of formatting characters, use of upper vs. lower case, etc.
Control | 0..1
Type | string
NamingSystem.uniqueId
Definition | Indicates how the system may be identified when referenced in electronic exchange.
Control | 1..*
Comments | Multiple identifiers may exist, either due to duplicate registration, regional rules, needs of different communication technologies, etc.

NamingSystem.uniqueId.type
Definition | Identifies the unique identifier scheme used for this particular identifier.
Control | 1..1
Terminology Binding | NamingSystemIdentifierType (Required)
Type | code
Comments | Different identifier types may be used in different types of communications (OIDs for v3, URIs for FHIR, etc.). Other includes RUIDs from v3, standard v2 code name strings, etc.
NamingSystem.uniqueId.value
Definition | The string that should be sent over the wire to identify the code system or identifier system.
Control | 1..1
Type | string
Comments | If the value is a URI intended for use as FHIR system identifier, the URI should not contain "\" or "?" or "," since this makes escaping very difficult.
NamingSystem.uniqueId.preferred
Definition | Indicates whether this identifier is the "preferred" identifier of this type.
Control | 0..1
Type | boolean
Meaning if Missing | If there are multiple ids, and one is labeled "preferred", then the assumption is that the others are not preferred. In the absence of any id marked as preferred, no inference can be drawn
NamingSystem.uniqueId.comment
Definition | Notes about the past or intended usage of this identifier.
Control | 0..1
Type | string
Comments | e.g. "must be used in Germany" or "was initially published in error with this value".
NamingSystem.uniqueId.period
Definition | Identifies the period of time over which this identifier is considered appropriate to refer to the naming system. Outside of this window, the identifier might be non-deterministic.
Control | 0..1
Type | Period
Comments | Within a registry, a given identifier should only be "active" for a single namespace at a time. (Ideally, an identifier should only ever be associated with a single namespace across all time).
NamingSystem.replacedBy
Definition | For naming systems that are retired, indicates the naming system that should be used in their place (if any).
Control | 0..1
Type | Reference(NamingSystem)
Invariants | Affect this element nsd-3: Can only have replacedBy if naming system is retired (expression : replacedBy.empty() or status = 'retired', xpath: not(f:replacedBy) or f:status/@value='retired')

4.10.8 Resource NamingSystem - Mappings

URL: https://hl7.org/fhir/STU3/namingsystem-mappings.html

This page is part of the FHIR Specification (v3.0.2: STU 3). The current version which supercedes this version is 4.0.1. For a full list of available versions, see the Directory of published versions

4.10.8 Resource NamingSystem - Mappings

FHIR Infrastructure Work Group | Maturity Level: N/A | Ballot Status: Informative | Compartments: Not linked to any defined compartments

Mappings:

RIM Mapping

HL7 v2 Mapping

Mappings for the namingsystem resource.

4.10.8.1 Mappings for RIM Mapping (http://hl7.org/v3)

NamingSystem | N/A

4.10.8.2 Mappings for HL7 v2 Mapping (http://hl7.org/v2)

NamingSystem | N/A

4.10.9 Resource NamingSystem - Design Notes

URL: https://hl7.org/fhir/STU3/namingsystem-explanations.html

This page is part of the FHIR Specification (v3.0.2: STU 3). The current version which supercedes this version is 4.0.1. For a full list of available versions, see the Directory of published versions

4.10.9 Resource NamingSystem - Design Notes

to do

4.10.10 Resource NamingSystem - Extensions & Profiles

URL: https://hl7.org/fhir/STU3/namingsystem-profiles.html

This page is part of the FHIR Specification (v3.0.2: STU 3). The current version which supercedes this version is 4.0.1. For a full list of available versions, see the Directory of published versions

4.10.10 Resource NamingSystem - Extensions & Profiles

FHIR Infrastructure Work Group | Maturity Level: N/A | Ballot Status: Informative

This table lists profiles and extensions for the NamingSystem resource. For background information, see Profiling Resources and Extensibility. Additional profiles and resources may be found in published Implementation Guides , or in the Conformance resource registry .

4.10.10.1 Profiles

No Profiles defined for this resource

4.10.10.2 Extensions

resource-approvalDate | approvalDate | for Resource HL7 Extensions
resource-effectivePeriod | effectivePeriod | for Resource HL7 Extensions
resource-lastReviewDate | lastReviewDate | for Resource HL7 Extensions

Extensions that reference this resource:

No Extensions refer to this resource

4.10.10.3 Search Extensions

No Search Extensions defined for this resource

4.10.11 Resource NamingSystem - Detailed Descriptions

URL: https://hl7.org/fhir/STU3/namingsystem-version-maps.html

This page is part of the FHIR Specification (v3.0.2: STU 3). The current version which supercedes this version is 4.0.1. For a full list of available versions, see the Directory of published versions

4.10.11 Resource NamingSystem - Detailed Descriptions

FHIR Infrastructure Work Group | Maturity Level: N/A | Ballot Status: Informative | Compartments: Not linked to any defined compartments

R2 : R3 Converson maps for NamingSystem.

Functional status for this map: 3 tests that all execute ok. All tests pass round-trip testing and all r3 resources are valid. (see documentation)

4.10.11.1 R2 to R3

```
map "http://hl7.org/fhir/StructureMap/NamingSystem2to3" = "R2 to R3 Conversions for NamingSystem"

uses "http://hl7.org/fhir/DSTU2/StructureDefinition/NamingSystem" alias NamingSystemR2 as source
uses "http://hl7.org/fhir/StructureDefinition/NamingSystem" alias NamingSystem as target

imports "http://hl7.org/fhir/StructureMap/primitives2to3"
imports "http://hl7.org/fhir/StructureMap/DomainResource2to3"
imports "http://hl7.org/fhir/StructureMap/ContactPoint2to3"
imports "http://hl7.org/fhir/StructureMap/Reference2to3"
imports "http://hl7.org/fhir/StructureMap/Period2to3"
imports "http://hl7.org/fhir/StructureMap/CodeableConcept2to3"

group for type+types  NamingSystem extends DomainResource
  input src : NamingSystemR2 as source
  input tgt : NamingSystem as target

  "NamingSystem-name" : for src.name make tgt.name
  "NamingSystem-status" : for src.status make tgt.status
  "NamingSystem-kind" : for src.kind make tgt.kind
  "NamingSystem-date" : for src.date make tgt.date
  "NamingSystem-publisher" : for src.publisher make tgt.publisher
  "NamingSystem-contact" : for src.contact as vs0 make tgt.contact as vt0 then {
    "ContactDetail-name" : for vs0.name make vt0.name
    "ContactDetail-telecom" : for vs0.telecom make vt0.telecom
  }

  "NamingSystem-responsible" : for src.responsible make tgt.responsible
  "NamingSystem-type" : for src.type make tgt.type
  "NamingSystem-description" : for src.description make tgt.description
  "NamingSystem-usage" : for src.usage make tgt.usage
  "NamingSystem-uniqueId" : for src.uniqueId as vs0 make tgt.uniqueId as vt0 then {
    "NamingSystem.uniqueId-type" : for vs0.type make vt0.type
    "NamingSystem.uniqueId-value" : for vs0.value make vt0.value
    "NamingSystem.uniqueId-preferred" : for vs0.preferred make vt0.preferred
    "NamingSystem.uniqueId-period" : for vs0.period make vt0.period
  }

  "NamingSystem-replacedBy" : for src.replacedBy make tgt.replacedBy
  "NamingSystem-jurisdiction" : for src.useContext where coding.system = 'urn:iso:std:iso:3166' make tgt.jurisdiction
```

```
endgroup
```

4.10.11.2 R3 to R2

```
map "http://hl7.org/fhir/StructureMap/NamingSystem3to2" = "R3 to R2 Conversion for NamingSystem"

uses "http://hl7.org/fhir/StructureDefinition/NamingSystem" alias NamingSystem as source
uses "http://hl7.org/fhir/DSTU2/StructureDefinition/NamingSystem" alias NamingSystemR2 as target

imports "http://hl7.org/fhir/StructureMap/primitives3to2"
imports "http://hl7.org/fhir/StructureMap/DomainResource3to2"
imports "http://hl7.org/fhir/StructureMap/ContactPoint3to2"
imports "http://hl7.org/fhir/StructureMap/Reference3to2"
imports "http://hl7.org/fhir/StructureMap/Period3to2"
imports "http://hl7.org/fhir/StructureMap/CodeableConcept3to2"

group for type+types  NamingSystem extends DomainResource
  input src : NamingSystem as source
  input tgt : NamingSystemR2 as target

  "NamingSystem-name" : for src.name make tgt.name
  "NamingSystem-status" : for src.status make tgt.status
  "NamingSystem-kind" : for src.kind make tgt.kind
  "NamingSystem-publisher" : for src.publisher make tgt.publisher
  "NamingSystem-contact" : for src.contact as vs0 make tgt.contact as vt0 then {
    "NamingSystem.contact-name" : for vs0.name make vt0.name
    "NamingSystem.contact-telecom" : for vs0.telecom make vt0.telecom
  }

  "NamingSystem-responsible" : for src.responsible make tgt.responsible
  "NamingSystem-date" : for src.date make tgt.date
  "NamingSystem-type" : for src.type make tgt.type
  "NamingSystem-description" : for src.description make tgt.description
  "NamingSystem-useContext" : for src.jurisdiction make tgt.useContext
  "NamingSystem-usage" : for src.usage make tgt.usage
  "NamingSystem-uniqueId" : for src.uniqueId as vs0 make tgt.uniqueId as vt0 then {
    "NamingSystem.uniqueId-type" : for vs0.type make vt0.type
    "NamingSystem.uniqueId-value" : for vs0.value make vt0.value
    "NamingSystem.uniqueId-preferred" : for vs0.preferred make vt0.preferred
    "NamingSystem.uniqueId-period" : for vs0.period make vt0.period
  }

  "NamingSystem-replacedBy" : for src.replacedBy make tgt.replacedBy

endgroup
```

4.10.11.3 R3 Validation Errors

4.11 Resource ExpansionProfile - Content

URL: https://hl7.org/fhir/STU3/expansionprofile.html

This page is part of the FHIR Specification (v3.0.2: STU 3). The current version which supercedes this version is 4.0.1. For a full list of available versions, see the Directory of published versions

Vocabulary Work Group | Maturity Level: 2 | Trial Use | Compartments: Not linked to any defined compartments

Resource to define constraints on the Expansion of a FHIR ValueSet.

4.11.1 Scope and Usage

The purpose of the expansion profile is to allow a client that is using a terminology service to configure the behaviour of the terminology server in regard to how it builds expansions - and, in a similar manner, how it validates codes in value set. ExpansionProfiles are used for the following operations:

* Value Set Expansion

* Value Set based Validation

The ExpansionProfile can be passed either directly, or as a reference by its canonical URL.

4.11.2 Boundaries and Relationships

The ExpansionProfile is used to configure the behaviour of a terminology server when it processes ValueSet resources. As such, there is a tight relationship between the two resources; ValueSets specify what codes are in the value set, while ExpansionProfile affect run time behaviour.

ExpansionProfiles do not change what codes are in a defined value set. They can never add codes to the value set. They can be used to reduce the number of codes returned in an expansion, but this is a reduced view of the value set, not a change in the value set itself. Note, though, the discussion about overriding versions below.

4.11.3 Resource Content

* Structure

* UML

* XML

* JSON
* Turtle
* R2 Diff
* All

Structure

Name | Flags | Card. | Type | Description & Constraints
ExpansionProfile | | | DomainResource | Defines behaviour and contraints on the ValueSet Expansion operation Elements defined in Ancestors: id, meta, implicitRules, language, text, contained, extension, modifierExtension
url | ? | 0..1 | uri | Logical URI to reference this expansion profile (globally unique)
identifier | ? | 0..1 | Identifier | Additional identifier for the expansion profile
version | ? | 0..1 | string | Business version of the expansion profile
name | ? | 0..1 | string | Name for this expansion profile (computer friendly)
status | ?!? | 1..1 | code | draft | active | retired | unknown PublicationStatus (Required)
experimental | ?!? | 0..1 | boolean | For testing purposes, not real usage
date | ? | 0..1 | dateTime | Date this was last changed
publisher | ? | 0..1 | string | Name of the publisher (organization or individual)
contact | ? | 0..* | ContactDetail | Contact details for the publisher
description | | 0..1 | markdown | Natural language description of the expansion profile
useContext | ? | 0..* | UsageContext | Context the content is intended to support
jurisdiction | ? | 0..* | CodeableConcept | Intended jurisdiction for expansion profile (if applicable) Jurisdiction ValueSet (Extensible)
fixedVersion | ? | 0..* | BackboneElement | Fix use of a code system to a particular version
system | ? | 1..1 | uri | System to have its version fixed
version | ? | 1..1 | string | Specific version of the code system referred to
mode | ? | 1..1 | code | default | check | override SystemVersionProcessingMode (Required)
excludedSystem | ? | 0..1 | BackboneElement | Systems/Versions to be exclude
system | ? | 1..1 | uri | The specific code system to be excluded
version | ? | 0..1 | string | Specific version of the code system referred to
includeDesignations | ? | 0..1 | boolean | Whether the expansion should include concept designations
designation | ? | 0..1 | BackboneElement | When the expansion profile imposes designation contraints
include | ? | 0..1 | BackboneElement | Designations to be included
designation | ?I | 0..* | BackboneElement | The designation to be included + SHALL have at least one of language or use
language | ? | 0..1 | code | Human language of the designation to be included Common Languages (Extensible but limited to All Languages)
use | ? | 0..1 | Coding | What kind of Designation to include Designation Use (Required)
exclude | ? | 0..1 | BackboneElement | Designations to be excluded
designation | ?I | 0..* | BackboneElement | The designation to be excluded + SHALL have at least one of language or use
language | ? | 0..1 | code | Human language of the designation to be excluded Common Languages (Extensible but limited to All Languages)
use | ? | 0..1 | Coding | What kind of Designation to exclude Designation Use (Required)
includeDefinition | ? | 0..1 | boolean | Include or exclude the value set definition in the expansion
activeOnly | ? | 0..1 | boolean | Include or exclude inactive concepts in the expansion
excludeNested | ? | 0..1 | boolean | Nested codes in the expansion or not
excludeNotForUI | ? | 0..1 | boolean | Include or exclude codes which cannot be rendered in user interfaces in the value set expansion
excludePostCoordinated | ? | 0..1 | boolean | Include or exclude codes which are post coordinated expressions in the value set expansion
displayLanguage | ? | 0..1 | code | Specify the language for the display element of codes in the value set expansion Common Languages (Extensible but limited to All Languages)
limitedExpansion | ? | 0..1 | boolean | Controls behaviour of the value set expand operation when value sets are too large to be completely expanded
Documentation for this format

UML Diagram (Legend)

XML Template

```
<ExpansionProfile xmlns="http://hl7.org/fhir">
 <!-- from Resource: id, meta, implicitRules, and language -->
 <!-- from DomainResource: text, contained, extension, and modifierExtension -->
 <url value="[uri]"/><!-- 0..1 Logical URI to reference this expansion profile (globally unique) -->
 <identifier><!-- 0..1 Identifier Additional identifier for the expansion profile --></identifier>
 <version value="[string]"/><!-- 0..1 Business version of the expansion profile -->
 <name value="[string]"/><!-- 0..1 Name for this expansion profile (computer friendly) -->
 <status value="[code]"/><!-- 1..1 draft | active | retired | unknown -->
 <experimental value="[boolean]"/><!-- 0..1 For testing purposes, not real usage -->
 <date value="[dateTime]"/><!-- 0..1 Date this was last changed -->
 <publisher value="[string]"/><!-- 0..1 Name of the publisher (organization or individual) -->
 <contact><!-- 0..* ContactDetail Contact details for the publisher --></contact>
 <description value="[markdown]"/><!-- 0..1 Natural language description of the expansion profile -->
 <useContext><!-- 0..* UsageContext Context the content is intended to support --></useContext>
 <jurisdiction><!-- 0..* CodeableConcept Intended jurisdiction for expansion profile (if applicable) --></jurisdiction>
 <fixedVersion>  <!-- 0..* Fix use of a code system to a particular version -->
  <system value="[uri]"/><!-- 1..1 System to have its version fixed -->
  <version value="[string]"/><!-- 1..1 Specific version of the code system referred to -->
  <mode value="[code]"/><!-- 1..1 default | check | override -->
 </fixedVersion>
 <excludedSystem>  <!-- 0..1 Systems/Versions to be exclude -->
  <system value="[uri]"/><!-- 1..1 The specific code system to be excluded -->
  <version value="[string]"/><!-- 0..1 Specific version of the code system referred to -->
 </excludedSystem>
 <includeDesignations value="[boolean]"/><!-- 0..1 Whether the expansion should include concept designations -->
 <designation>  <!-- 0..1 When the expansion profile imposes designation contraints -->
```

```
  <include>  <!-- 0..1 Designations to be included -->
   <designation>  <!-- 0..* The designation to be included -->
    <language value="[code]"/><!-- 0..1 Human language of the designation to be included -->
    <use><!-- 0..1 Coding What kind of Designation to include --></use>
   </designation>
  </include>
  <exclude>  <!-- 0..1 Designations to be excluded -->
   <designation>  <!-- 0..* The designation to be excluded -->
    <language value="[code]"/><!-- 0..1 Human language of the designation to be excluded -->
    <use><!-- 0..1 Coding What kind of Designation to exclude --></use>
   </designation>
  </exclude>
 </designation>
 <includeDefinition value="[boolean]"/><!-- 0..1 Include or exclude the value set definition in the expansion -->
 <activeOnly value="[boolean]"/><!-- 0..1 Include or exclude inactive concepts in the expansion -->
 <excludeNested value="[boolean]"/><!-- 0..1 Nested codes in the expansion or not -->
 <excludeNotForUI value="[boolean]"/><!-- 0..1 Include or exclude codes which cannot be rendered in user interfaces in
    the value set expansion -->
 <excludePostCoordinated value="[boolean]"/><!-- 0..1 Include or exclude codes which are post coordinated expressions in
     the value set expansion -->
 <displayLanguage value="[code]"/><!-- 0..1 Specify the language for the display element of codes in the value set
    expansion -->
 <limitedExpansion value="[boolean]"/><!-- 0..1 Controls behaviour of the value set expand operation when value sets are
     too large to be completely expanded -->
</ExpansionProfile>
```

JSON Template

```
{
  "resourceType" : "ExpansionProfile",
  // from Resource: id, meta, implicitRules, and language
  // from DomainResource: text, contained, extension, and modifierExtension
  "url" : "<uri>", // Logical URI to reference this expansion profile (globally unique)
  "identifier" : { Identifier }, // Additional identifier for the expansion profile
  "version" : "<string>", // Business version of the expansion profile
  "name" : "<string>", // Name for this expansion profile (computer friendly)
  "status" : "<code>", // R!  draft | active | retired | unknown
  "experimental" : <boolean>, // For testing purposes, not real usage
  "date" : "<dateTime>", // Date this was last changed
  "publisher" : "<string>", // Name of the publisher (organization or individual)
  "contact" : [{ ContactDetail }], // Contact details for the publisher
  "description" : "<markdown>", // Natural language description of the expansion profile
  "useContext" : [{ UsageContext }], // Context the content is intended to support
  "jurisdiction" : [{ CodeableConcept }], // Intended jurisdiction for expansion profile (if applicable)
  "fixedVersion" : [{ // Fix use of a code system to a particular version
    "system" : "<uri>", // R!  System to have its version fixed
    "version" : "<string>", // R!  Specific version of the code system referred to
    "mode" : "<code>" // R!  default | check | override
  }],
  "excludedSystem" : { // Systems/Versions to be exclude
    "system" : "<uri>", // R!  The specific code system to be excluded
    "version" : "<string>" // Specific version of the code system referred to
  },
  "includeDesignations" : <boolean>, // Whether the expansion should include concept designations
  "designation" : { // When the expansion profile imposes designation contraints
    "include" : { // Designations to be included
      "designation" : [{ // The designation to be included
        "language" : "<code>", // Human language of the designation to be included
        "use" : { Coding } // What kind of Designation to include
      }]
    },
    "exclude" : { // Designations to be excluded
      "designation" : [{ // The designation to be excluded
        "language" : "<code>", // Human language of the designation to be excluded
        "use" : { Coding } // What kind of Designation to exclude
      }]
    }
  },
  "includeDefinition" : <boolean>, // Include or exclude the value set definition in the expansion
  "activeOnly" : <boolean>, // Include or exclude inactive concepts in the expansion
  "excludeNested" : <boolean>, // Nested codes in the expansion or not
  "excludeNotForUI" : <boolean>, // Include or exclude codes which cannot be rendered in user interfaces in the value
    set expansion
  "excludePostCoordinated" : <boolean>, // Include or exclude codes which are post coordinated expressions in the value
    set expansion
  "displayLanguage" : "<code>", // Specify the language for the display element of codes in the value set expansion
  "limitedExpansion" : <boolean> // Controls behaviour of the value set expand operation when value sets are too large
    to be completely expanded
}
```

Turtle Template

```
@prefix fhir: <http://hl7.org/fhir/> .


[ a fhir:ExpansionProfile;
  fhir:nodeRole fhir:treeRoot; # if this is the parser root

  # from Resource: .id, .meta, .implicitRules, and .language
  # from DomainResource: .text, .contained, .extension, and .modifierExtension
  fhir:ExpansionProfile.url [ uri ]; # 0..1 Logical URI to reference this expansion profile (globally unique)
```

```
  fhir:ExpansionProfile.identifier [ Identifier ]; # 0..1 Additional identifier for the expansion profile
  fhir:ExpansionProfile.version [ string ]; # 0..1 Business version of the expansion profile
  fhir:ExpansionProfile.name [ string ]; # 0..1 Name for this expansion profile (computer friendly)
  fhir:ExpansionProfile.status [ code ]; # 1..1 draft | active | retired | unknown
  fhir:ExpansionProfile.experimental [ boolean ]; # 0..1 For testing purposes, not real usage
  fhir:ExpansionProfile.date [ dateTime ]; # 0..1 Date this was last changed
  fhir:ExpansionProfile.publisher [ string ]; # 0..1 Name of the publisher (organization or individual)
  fhir:ExpansionProfile.contact [ ContactDetail ], ... ; # 0..* Contact details for the publisher
  fhir:ExpansionProfile.description [ markdown ]; # 0..1 Natural language description of the expansion profile
  fhir:ExpansionProfile.useContext [ UsageContext ], ... ; # 0..* Context the content is intended to support
  fhir:ExpansionProfile.jurisdiction [ CodeableConcept ], ... ; # 0..* Intended jurisdiction for expansion profile (if
    applicable)
  fhir:ExpansionProfile.fixedVersion [ # 0..* Fix use of a code system to a particular version
    fhir:ExpansionProfile.fixedVersion.system [ uri ]; # 1..1 System to have its version fixed
    fhir:ExpansionProfile.fixedVersion.version [ string ]; # 1..1 Specific version of the code system referred to
    fhir:ExpansionProfile.fixedVersion.mode [ code ]; # 1..1 default | check | override
  ], ...;
  fhir:ExpansionProfile.excludedSystem [ # 0..1 Systems/Versions to be exclude
    fhir:ExpansionProfile.excludedSystem.system [ uri ]; # 1..1 The specific code system to be excluded
    fhir:ExpansionProfile.excludedSystem.version [ string ]; # 0..1 Specific version of the code system referred to
  ];
  fhir:ExpansionProfile.includeDesignations [ boolean ]; # 0..1 Whether the expansion should include concept
    designations
  fhir:ExpansionProfile.designation [ # 0..1 When the expansion profile imposes designation contraints
    fhir:ExpansionProfile.designation.include [ # 0..1 Designations to be included
      fhir:ExpansionProfile.designation.include.designation [ # 0..* The designation to be included
        fhir:ExpansionProfile.designation.include.designation.language [ code ]; # 0..1 Human language of the
    designation to be included
        fhir:ExpansionProfile.designation.include.designation.use [ Coding ]; # 0..1 What kind of Designation to include
      ], ...;
    ];
    fhir:ExpansionProfile.designation.exclude [ # 0..1 Designations to be excluded
      fhir:ExpansionProfile.designation.exclude.designation [ # 0..* The designation to be excluded
        fhir:ExpansionProfile.designation.exclude.designation.language [ code ]; # 0..1 Human language of the
    designation to be excluded
        fhir:ExpansionProfile.designation.exclude.designation.use [ Coding ]; # 0..1 What kind of Designation to exclude
      ], ...;
    ];
  ];
  fhir:ExpansionProfile.includeDefinition [ boolean ]; # 0..1 Include or exclude the value set definition in the
    expansion
  fhir:ExpansionProfile.activeOnly [ boolean ]; # 0..1 Include or exclude inactive concepts in the expansion
  fhir:ExpansionProfile.excludeNested [ boolean ]; # 0..1 Nested codes in the expansion or not
  fhir:ExpansionProfile.excludeNotForUI [ boolean ]; # 0..1 Include or exclude codes which cannot be rendered in user
    interfaces in the value set expansion
  fhir:ExpansionProfile.excludePostCoordinated [ boolean ]; # 0..1 Include or exclude codes which are post coordinated
    expressions in the value set expansion
  fhir:ExpansionProfile.displayLanguage [ code ]; # 0..1 Specify the language for the display element of codes in the
    value set expansion
  fhir:ExpansionProfile.limitedExpansion [ boolean ]; # 0..1 Controls behaviour of the value set expand operation when
    value sets are too large to be completely expanded
]
```

Changes since DSTU2

This resource did not exist in Release 2

This analysis is available as XML or JSON.

Structure

Name | Flags | Card. | Type | Description & Constraints

ExpansionProfile | | | DomainResource | Defines behaviour and contraints on the ValueSet Expansion operation Elements defined in Ancestors: id, meta, implicitRules, language, text, contained, extension, modifierExtension

url | ? | 0..1 | uri | Logical URI to reference this expansion profile (globally unique)

identifier | ? | 0..1 | Identifier | Additional identifier for the expansion profile

version | ? | 0..1 | string | Business version of the expansion profile

name | ? | 0..1 | string | Name for this expansion profile (computer friendly)

status | ?!? | 1..1 | code | draft | active | retired | unknown PublicationStatus (Required)

experimental | ?!? | 0..1 | boolean | For testing purposes, not real usage

date | ? | 0..1 | dateTime | Date this was last changed

publisher | ? | 0..1 | string | Name of the publisher (organization or individual)

contact | ? | 0..* | ContactDetail | Contact details for the publisher

description | | 0..1 | markdown | Natural language description of the expansion profile

useContext | ? | 0..* | UsageContext | Context the content is intended to support

jurisdiction | ? | 0..* | CodeableConcept | Intended jurisdiction for expansion profile (if applicable) Jurisdiction ValueSet (Extensible)

fixedVersion | ? | 0..* | BackboneElement | Fix use of a code system to a particular version

system | ? | 1..1 | uri | System to have its version fixed

version | ? | 1..1 | string | Specific version of the code system referred to

mode | ? | 1..1 | code | default | check | override SystemVersionProcessingMode (Required)

excludedSystem | ? | 0..1 | BackboneElement | Systems/Versions to be exclude

system | ? | 1..1 | uri | The specific code system to be excluded

version | ? | 0..1 | string | Specific version of the code system referred to

includeDesignations | ? | 0..1 | boolean | Whether the expansion should include concept designations

designation | ? | 0..1 | BackboneElement | When the expansion profile imposes designation contraints

include | ? | 0..1 | BackboneElement | Designations to be included
designation | ?I | 0..* | BackboneElement | The designation to be included + SHALL have at least one of language or use
language | ? | 0..1 | code | Human language of the designation to be included Common Languages (Extensible but limited to All Languages)
use | ? | 0..1 | Coding | What kind of Designation to include Designation Use (Required)
exclude | ? | 0..1 | BackboneElement | Designations to be excluded
designation | ?I | 0..* | BackboneElement | The designation to be excluded + SHALL have at least one of language or use
language | ? | 0..1 | code | Human language of the designation to be excluded Common Languages (Extensible but limited to All Languages)
use | ? | 0..1 | Coding | What kind of Designation to exclude Designation Use (Required)
includeDefinition | ? | 0..1 | boolean | Include or exclude the value set definition in the expansion
activeOnly | ? | 0..1 | boolean | Include or exclude inactive concepts in the expansion
excludeNested | ? | 0..1 | boolean | Nested codes in the expansion or not
excludeNotForUI | ? | 0..1 | boolean | Include or exclude codes which cannot be rendered in user interfaces in the value set expansion
excludePostCoordinated | ? | 0..1 | boolean | Include or exclude codes which are post coordinated expressions in the value set expansion
displayLanguage | ? | 0..1 | code | Specify the language for the display element of codes in the value set expansion Common Languages (Extensible but limited to All Languages)
limitedExpansion | ? | 0..1 | boolean | Controls behaviour of the value set expand operation when value sets are too large to be completely expanded
Documentation for this format

UML Diagram (Legend)

XML Template

```
<ExpansionProfile xmlns="http://hl7.org/fhir">
 <!-- from Resource: id, meta, implicitRules, and language -->
 <!-- from DomainResource: text, contained, extension, and modifierExtension -->
 <url value="[uri]"/><!-- 0..1 Logical URI to reference this expansion profile (globally unique) -->
 <identifier><!-- 0..1 Identifier Additional identifier for the expansion profile --></identifier>
 <version value="[string]"/><!-- 0..1 Business version of the expansion profile -->
 <name value="[string]"/><!-- 0..1 Name for this expansion profile (computer friendly) -->
 <status value="[code]"/><!-- 1..1 draft | active | retired | unknown -->
 <experimental value="[boolean]"/><!-- 0..1 For testing purposes, not real usage -->
 <date value="[dateTime]"/><!-- 0..1 Date this was last changed -->
 <publisher value="[string]"/><!-- 0..1 Name of the publisher (organization or individual) -->
 <contact><!-- 0..* ContactDetail Contact details for the publisher --></contact>
 <description value="[markdown]"/><!-- 0..1 Natural language description of the expansion profile -->
 <useContext><!-- 0..* UsageContext Context the content is intended to support --></useContext>
 <jurisdiction><!-- 0..* CodeableConcept Intended jurisdiction for expansion profile (if applicable) --></jurisdiction>
 <fixedVersion>  <!-- 0..* Fix use of a code system to a particular version -->
  <system value="[uri]"/><!-- 1..1 System to have its version fixed -->
  <version value="[string]"/><!-- 1..1 Specific version of the code system referred to -->
  <mode value="[code]"/><!-- 1..1 default | check | override -->
 </fixedVersion>
 <excludedSystem>  <!-- 0..1 Systems/Versions to be exclude -->
  <system value="[uri]"/><!-- 1..1 The specific code system to be excluded -->
  <version value="[string]"/><!-- 0..1 Specific version of the code system referred to -->
 </excludedSystem>
 <includeDesignations value="[boolean]"/><!-- 0..1 Whether the expansion should include concept designations -->
 <designation>  <!-- 0..1 When the expansion profile imposes designation contraints -->
  <include>  <!-- 0..1 Designations to be included -->
   <designation>  <!-- 0..* The designation to be included -->
    <language value="[code]"/><!-- 0..1 Human language of the designation to be included -->
    <use><!-- 0..1 Coding What kind of Designation to include --></use>
   </designation>
  </include>
  <exclude>  <!-- 0..1 Designations to be excluded -->
   <designation>  <!-- 0..* The designation to be excluded -->
    <language value="[code]"/><!-- 0..1 Human language of the designation to be excluded -->
    <use><!-- 0..1 Coding What kind of Designation to exclude --></use>
   </designation>
  </exclude>
 </designation>
 <includeDefinition value="[boolean]"/><!-- 0..1 Include or exclude the value set definition in the expansion -->
 <activeOnly value="[boolean]"/><!-- 0..1 Include or exclude inactive concepts in the expansion -->
 <excludeNested value="[boolean]"/><!-- 0..1 Nested codes in the expansion or not -->
 <excludeNotForUI value="[boolean]"/><!-- 0..1 Include or exclude codes which cannot be rendered in user interfaces in
    the value set expansion -->
 <excludePostCoordinated value="[boolean]"/><!-- 0..1 Include or exclude codes which are post coordinated expressions in
     the value set expansion -->
 <displayLanguage value="[code]"/><!-- 0..1 Specify the language for the display element of codes in the value set
    expansion -->
 <limitedExpansion value="[boolean]"/><!-- 0..1 Controls behaviour of the value set expand operation when value sets are
     too large to be completely expanded -->
</ExpansionProfile>
```

JSON Template

```
{
  "resourceType" : "ExpansionProfile",
  // from Resource: id, meta, implicitRules, and language
  // from DomainResource: text, contained, extension, and modifierExtension
  "url" : "<uri>", // Logical URI to reference this expansion profile (globally unique)
  "identifier" : { Identifier }, // Additional identifier for the expansion profile
  "version" : "<string>", // Business version of the expansion profile
  "name" : "<string>", // Name for this expansion profile (computer friendly)
  "status" : "<code>", // R!  draft | active | retired | unknown
  "experimental" : <boolean>, // For testing purposes, not real usage
  "date" : "<dateTime>", // Date this was last changed
```

```
  "publisher" : "<string>", // Name of the publisher (organization or individual)
  "contact" : [{ ContactDetail }], // Contact details for the publisher
  "description" : "<markdown>", // Natural language description of the expansion profile
  "useContext" : [{ UsageContext }], // Context the content is intended to support
  "jurisdiction" : [{ CodeableConcept }], // Intended jurisdiction for expansion profile (if applicable)
  "fixedVersion" : [{ // Fix use of a code system to a particular version
    "system" : "<uri>", // R!  System to have its version fixed
    "version" : "<string>", // R!  Specific version of the code system referred to
    "mode" : "<code>" // R!  default | check | override
  }],
  "excludedSystem" : { // Systems/Versions to be exclude
    "system" : "<uri>", // R!  The specific code system to be excluded
    "version" : "<string>" // Specific version of the code system referred to
  },
  "includeDesignations" : <boolean>, // Whether the expansion should include concept designations
  "designation" : { // When the expansion profile imposes designation contraints
    "include" : { // Designations to be included
      "designation" : [{ // The designation to be included
        "language" : "<code>", // Human language of the designation to be included
        "use" : { Coding } // What kind of Designation to include
      }]
    },
    "exclude" : { // Designations to be excluded
      "designation" : [{ // The designation to be excluded
        "language" : "<code>", // Human language of the designation to be excluded
        "use" : { Coding } // What kind of Designation to exclude
      }]
    }
  },
  "includeDefinition" : <boolean>, // Include or exclude the value set definition in the expansion
  "activeOnly" : <boolean>, // Include or exclude inactive concepts in the expansion
  "excludeNested" : <boolean>, // Nested codes in the expansion or not
  "excludeNotForUI" : <boolean>, // Include or exclude codes which cannot be rendered in user interfaces in the value
    set expansion
  "excludePostCoordinated" : <boolean>, // Include or exclude codes which are post coordinated expressions in the value
    set expansion
  "displayLanguage" : "<code>", // Specify the language for the display element of codes in the value set expansion
  "limitedExpansion" : <boolean> // Controls behaviour of the value set expand operation when value sets are too large
    to be completely expanded
}
```

Turtle Template

```
@prefix fhir: <http://hl7.org/fhir/> .


[ a fhir:ExpansionProfile;
  fhir:nodeRole fhir:treeRoot; # if this is the parser root

  # from Resource: .id, .meta, .implicitRules, and .language
  # from DomainResource: .text, .contained, .extension, and .modifierExtension
  fhir:ExpansionProfile.url [ uri ]; # 0..1 Logical URI to reference this expansion profile (globally unique)
  fhir:ExpansionProfile.identifier [ Identifier ]; # 0..1 Additional identifier for the expansion profile
  fhir:ExpansionProfile.version [ string ]; # 0..1 Business version of the expansion profile
  fhir:ExpansionProfile.name [ string ]; # 0..1 Name for this expansion profile (computer friendly)
  fhir:ExpansionProfile.status [ code ]; # 1..1 draft | active | retired | unknown
  fhir:ExpansionProfile.experimental [ boolean ]; # 0..1 For testing purposes, not real usage
  fhir:ExpansionProfile.date [ dateTime ]; # 0..1 Date this was last changed
  fhir:ExpansionProfile.publisher [ string ]; # 0..1 Name of the publisher (organization or individual)
  fhir:ExpansionProfile.contact [ ContactDetail ], ... ; # 0..* Contact details for the publisher
  fhir:ExpansionProfile.description [ markdown ]; # 0..1 Natural language description of the expansion profile
  fhir:ExpansionProfile.useContext [ UsageContext ], ... ; # 0..* Context the content is intended to support
  fhir:ExpansionProfile.jurisdiction [ CodeableConcept ], ... ; # 0..* Intended jurisdiction for expansion profile (if
    applicable)
  fhir:ExpansionProfile.fixedVersion [ # 0..* Fix use of a code system to a particular version
    fhir:ExpansionProfile.fixedVersion.system [ uri ]; # 1..1 System to have its version fixed
    fhir:ExpansionProfile.fixedVersion.version [ string ]; # 1..1 Specific version of the code system referred to
    fhir:ExpansionProfile.fixedVersion.mode [ code ]; # 1..1 default | check | override
  ], ...;
  fhir:ExpansionProfile.excludedSystem [ # 0..1 Systems/Versions to be exclude
    fhir:ExpansionProfile.excludedSystem.system [ uri ]; # 1..1 The specific code system to be excluded
    fhir:ExpansionProfile.excludedSystem.version [ string ]; # 0..1 Specific version of the code system referred to
  ];
  fhir:ExpansionProfile.includeDesignations [ boolean ]; # 0..1 Whether the expansion should include concept
    designations
  fhir:ExpansionProfile.designation [ # 0..1 When the expansion profile imposes designation contraints
    fhir:ExpansionProfile.designation.include [ # 0..1 Designations to be included
      fhir:ExpansionProfile.designation.include.designation [ # 0..* The designation to be included
        fhir:ExpansionProfile.designation.include.designation.language [ code ]; # 0..1 Human language of the
    designation to be included
        fhir:ExpansionProfile.designation.include.designation.use [ Coding ]; # 0..1 What kind of Designation to include
      ], ...;
    ];
    fhir:ExpansionProfile.designation.exclude [ # 0..1 Designations to be excluded
      fhir:ExpansionProfile.designation.exclude.designation [ # 0..* The designation to be excluded
        fhir:ExpansionProfile.designation.exclude.designation.language [ code ]; # 0..1 Human language of the
    designation to be excluded
        fhir:ExpansionProfile.designation.exclude.designation.use [ Coding ]; # 0..1 What kind of Designation to exclude
      ], ...;
    ];
```

```
  ];
  fhir:ExpansionProfile.includeDefinition [ boolean ]; # 0..1 Include or exclude the value set definition in the
    expansion
  fhir:ExpansionProfile.activeOnly [ boolean ]; # 0..1 Include or exclude inactive concepts in the expansion
  fhir:ExpansionProfile.excludeNested [ boolean ]; # 0..1 Nested codes in the expansion or not
  fhir:ExpansionProfile.excludeNotForUI [ boolean ]; # 0..1 Include or exclude codes which cannot be rendered in user
    interfaces in the value set expansion
  fhir:ExpansionProfile.excludePostCoordinated [ boolean ]; # 0..1 Include or exclude codes which are post coordinated
    expressions in the value set expansion
  fhir:ExpansionProfile.displayLanguage [ code ]; # 0..1 Specify the language for the display element of codes in the
    value set expansion
  fhir:ExpansionProfile.limitedExpansion [ boolean ]; # 0..1 Controls behaviour of the value set expand operation when
    value sets are too large to be completely expanded
]
```

Changes since DSTU2

This resource did not exist in Release 2

This analysis is available as XML or JSON.

Alternate definitions: Master Definition (XML, JSON), XML Schema/Schematron (for) + JSON Schema, ShEx (for Turtle)

4.11.3.1 Terminology Bindings

Path | Definition | Type | Reference

ExpansionProfile.status | The lifecycle status of a Value Set or Concept Map. | Required | PublicationStatus

ExpansionProfile.jurisdiction | Countries and regions within which this artifact is targeted for use | Extensible | Jurisdiction ValueSet

ExpansionProfile.fixedVersion.mode | How to manage the intersection between a fixed version in a value set, and a fixed version of the system in the expansion profile | Required | SystemVersionProcessingMode

ExpansionProfile.designation.include.designation.language ExpansionProfile.designation.exclude.designation.language

ExpansionProfile.displayLanguage | A human language. | Extensible, but limited to All Languages | Common Languages

ExpansionProfile.designation.include.designation.use ExpansionProfile.designation.exclude.designation.use | Details of how a designation would be used. | Required | Designation Use

4.11.3.2 Constraints

* exp-3: On ExpansionProfile.designation.include.designation: SHALL have at least one of language or use (expression on ExpansionProfile.designation.include.designation: language.exists() or use.exists())

* exp-4: On ExpansionProfile.designation.exclude.designation: SHALL have at least one of language or use (expression on ExpansionProfile.designation.exclude.designation: language.exists() or use.exists())

4.11.3.3 Overriding Versions

The ExpansionProfile resources allows a client to specify a particular version to use for a given code system, and that this version is used irrespective of any version stated in any value set. This has obvious safety issues, in that it may result in a value set expansion giving a different list of codes that is both wrong and unsafe, and implementers should only use this capability reluctantly. This feature is primarily defined to allow implementers to deal with situations where specifications have fallen into decay as time passes, and the specified versions of code systems can no longer be used at all.

In principle, well designed specifications should not be authored in a fashion that allows them to decay in this fashion, but the technical infrastructure, eco-system, and community are not yet in a position to make this a reality. For this reason, clients are allowed to override versions. Clients setting the ExpansionProfile.fixedVersion.mode to override need to ensure that this action is not unsafe in their context.

4.11.3.4 Excluding Codes

Some fields in the ExpansionProfile can result in the return of an expansion that contains a reduced set of information in the expansion. if any of these fields may alter the expansion, terminology servers SHALL mark their use in the ValueSet.expansion.parameters with the matching parameter name:

ExpansionProfile.fixedVersion | fixedVersion (in addition to the normal 'version' parameter)

ExpansionProfile.activeOnly | activeOnly

ExpansionProfile.excludeNotForUI | excludeNotForUI

ExpansionProfile.excludePostCoordinated | excludePostCoordinated

ExpansionProfile.limitedExpansion | limitedExpansion (in addition to the extension http://hl7.org/fhir/StructureDefinition/valueset-toocostly)

4.11.4 Search Parameters

Search parameters for this resource. The common parameters also apply. See Searching for more information about searching in REST, messaging, and services.

Name | Type | Description | Expression | In Common

date | date | The expansion profile publication date | ExpansionProfile.date

description | string | The description of the expansion profile | ExpansionProfile.description

identifier | token | External identifier for the expansion profile | ExpansionProfile.identifier

jurisdiction | token | Intended jurisdiction for the expansion profile | ExpansionProfile.jurisdiction

name | string | Computationally friendly name of the expansion profile | ExpansionProfile.name

publisher | string | Name of the publisher of the expansion profile | ExpansionProfile.publisher

status | token | The current status of the expansion profile | ExpansionProfile.status

url | uri | The uri that identifies the expansion profile | ExpansionProfile.url

version | token | The business version of the expansion profile | ExpansionProfile.version

4.11.5 Resource ExpansionProfile - Examples

URL: https://hl7.org/fhir/STU3/expansionprofile-examples.html

This page is part of the FHIR Specification (v3.0.2: STU 3). The current version which supercedes this version is 4.0.1. For a full list of available versions, see the Directory of published versions

4.11.5 Resource ExpansionProfile - Examples

Vocabulary Work Group | Maturity Level: N/A | Ballot Status: Informative | Compartments: Not linked to any defined compartments

Example List:

Example of expansionprofile | example | XML | JSON | Turtle

Usage note: every effort has been made to ensure that the examples are correct and useful, but they are not a normative part of the specification.

4.11.6 Resource ExpansionProfile - Detailed Descriptions

URL: https://hl7.org/fhir/STU3/expansionprofile-definitions.html

This page is part of the FHIR Specification (v3.0.2: STU 3). The current version which supercedes this version is 4.0.1. For a full list of available versions, see the Directory of published versions

4.11.6 Resource ExpansionProfile - Detailed Descriptions

Vocabulary Work Group | Maturity Level: 2 | Trial Use | Compartments: Not linked to any defined compartments

Detailed Descriptions for the elements in the ExpansionProfile resource.

ExpansionProfile
Definition | Resource to define constraints on the Expansion of a FHIR ValueSet.
Control | 1..1
Alternate Names | ValueSetExpansionProfile
ExpansionProfile.url
Definition | An absolute URI that is used to identify this expansion profile when it is referenced in a specification, model, design or an instance. This SHALL be a URL, SHOULD be globally unique, and SHOULD be an address at which this expansion profile is (or will be) published. The URL SHOULD include the major version of the expansion profile. For more information see Technical and Business Versions.
Control | 0..1
Type | uri
Requirements | Allows the expansion profile to be referenced by a single globally unique identifier.
Summary | true
Comments | Can be a urn:uuid: or a urn:oid:, but real http: addresses are preferred. Multiple instances may share the same url if they have a distinct version.
ExpansionProfile.identifier
Definition | A formal identifier that is used to identify this expansion profile when it is represented in other formats, or referenced in a specification, model, design or an instance.
Note | This is a business identifer, not a resource identifier (see discussion)
Control | 0..1
Type | Identifier
Requirements | Allows externally provided and/or usable business identifiers to be easily associated with the module.
Summary | true
Comments | Typically, this is used for identifiers that can go in an HL7 V3 II (instance identifier) data type, e.g., to identify this expansion profile outside of FHIR, where it is not possible to use the logical URI.
ExpansionProfile.version
Definition | The identifier that is used to identify this version of the expansion profile when it is referenced in a specification, model, design or instance. This is an arbitrary value managed by the expansion profile author and is not expected to be globally unique. For example, it might be a timestamp (e.g. yyyymmdd) if a managed version is not available. There is also no expectation that versions can be placed in a lexicographical sequence.
Note | This is a business versionId, not a resource version id (see discussion)
Control | 0..1
Type | string
Summary | true
Comments | There may be different expansion profile instances that have the same identifier but different versions. The version can be appended to the url in a reference to allow a refrence to a particular business version of the expansion profile with the format [url]|[version].
ExpansionProfile.name
Definition | A natural language name identifying the expansion profile. This name should be usable as an identifier for the module by machine processing applications such as code generation.
Control | 0..1
Type | string
Requirements | Support human navigation and code generation.
Summary | true
Comments | The name is not expected to be globally unique. The name should be a simple alpha-numeric type name to ensure that it is computable friendly.
ExpansionProfile.status

Definition | The status of this expansion profile. Enables tracking the life-cycle of the content.
Control | 1..1
Terminology Binding | PublicationStatus (Required)
Type | code
Is Modifier | true
Summary | true
Comments | Allows filtering of expansion profiles that are appropriate for use vs. not. This is labeled as "Is Modifier" because applications should not use a retired expansion profile without due consideration.
ExpansionProfile.experimental
Definition | A boolean value to indicate that this expansion profile is authored for testing purposes (or education/evaluation/marketing), and is not intended to be used for genuine usage.
Control | 0..1
Type | boolean
Is Modifier | true
Requirements | Enables experimental content to be developed following the same lifecycle that would be used for a production-level expansion profile.
Summary | true
Comments | Allows filtering of expansion profile that are appropriate for use vs. not. This is labeled as "Is Modifier" because applications should not use an experimental expansion profile in production.
ExpansionProfile.date
Definition | The date (and optionally time) when the expansion profile was published. The date must change if and when the business version changes and it must change if the status code changes. In addition, it should change when the substantive content of the expansion profile changes.
Control | 0..1
Type | dateTime
Alternate Names | Revision Date
Summary | true
Comments | Note that this is not the same as the resource last-modified-date, since the resource may be a secondary representation of the expansion profile. Additional specific dates may be added as extensions or be found by consulting Provenances associated with past versions of the resource.
ExpansionProfile.publisher
Definition | The name of the individual or organization that published the expansion profile.
Control | 0..1
Type | string
Requirements | Helps establish the "authority/credibility" of the expansion profile. May also allow for contact.
Summary | true
Comments | Usually an organization, but may be an individual. The publisher (or steward) of the expansion profile is the organization or individual primarily responsible for the maintenance and upkeep of the expansion profile. This is not necessarily the same individual or organization that developed and initially authored the content. The publisher is the primary point of contact for questions or issues with the expansion profile. This item SHOULD be populated unless the information is available from context.
ExpansionProfile.contact
Definition | Contact details to assist a user in finding and communicating with the publisher.
Control | 0..*
Type | ContactDetail
Summary | true
Comments | May be a web site, an email address, a telephone number, etc.
ExpansionProfile.description
Definition | A free text natural language description of the expansion profile from a consumer's perspective.
Control | 0..1
Type | markdown
Comments | This description can be used to capture details such as why the expansion profile was built, comments about misuse, instructions for clinical use and interpretation, literature references, examples from the paper world, etc. It is not a rendering of the expansion profile as conveyed in the 'text' field of the resource itself. This item SHOULD be populated unless the information is available from context (e.g. the language of the profile is presumed to be the predominant language in the place the profile was created).
ExpansionProfile.useContext
Definition | The content was developed with a focus and intent of supporting the contexts that are listed. These terms may be used to assist with indexing and searching for appropriate expansion profile instances.
Control | 0..*
Type | UsageContext
Requirements | Assist in searching for appropriate content.
Summary | true
Comments | When multiple useContexts are specified, there is no expectation whether all or any of the contexts apply.
ExpansionProfile.jurisdiction
Definition | A legal or geographic region in which the expansion profile is intended to be used.
Control | 0..*
Terminology Binding | Jurisdiction ValueSet (Extensible)
Type | CodeableConcept
Summary | true
Comments | It may be possible for the expansion profile to be used in jurisdictions other than those for which it was originally designed or intended.
ExpansionProfile.fixedVersion
Definition | Fix use of a particular code system to a particular version.
Control | 0..*
Summary | true
ExpansionProfile.fixedVersion.system

Definition | The specific system for which to fix the version.
Control | 1..1
Type | uri
Summary | true
Comments | See ''Coding.system'' for further documentation.
ExpansionProfile.fixedVersion.version
Definition | The version of the code system from which codes in the expansion should be included.
Note | This is a business versionId, not a resource version id (see discussion)
Control | 1..1
Type | string
Summary | true
ExpansionProfile.fixedVersion.mode
Definition | How to manage the intersection between a fixed version in a value set, and this fixed version of the system in the expansion profile.
Control | 1..1
Terminology Binding | SystemVersionProcessingMode (Required)
Type | code
Summary | true
ExpansionProfile.excludedSystem
Definition | Code system, or a particular version of a code system to be excluded from value set expansions.
Control | 0..1
Summary | true
Comments | When a system is excluded, and this makes a material difference to the expansion, the exclusion SHALL be noted in the expansion parameters using a parameter 'excluded'.
ExpansionProfile.excludedSystem.system
Definition | An absolute URI which is the code system to be excluded.
Control | 1..1
Type | uri
Summary | true
Comments | See ''Coding.system'' for further documentation.
ExpansionProfile.excludedSystem.version
Definition | The version of the code system from which codes in the expansion should be excluded.
Note | This is a business versionId, not a resource version id (see discussion)
Control | 0..1
Type | string
Meaning if Missing | Exclusion is not version specific
Summary | true
Comments | This is used to apply version specifc exclusion contraints. If no version is specified, then all codes from the code system present in the expansion (prior to application of the expansion profile) will be excluded.
ExpansionProfile.includeDesignations
Definition | Controls whether concept designations are to be included or excluded in value set expansions.
Control | 0..1
Type | boolean
Summary | true
Comments | ExpansionProfile.designation.include and ExpansionProfile.designation.exclude are only evaluated if includeDesignations is present and set to "true". If includeDesignations is present with a value of "true" and both ExpansionProfile.designation.include and ExpansionProfile.designation.exclude are absent, then all designations are returned in the expansion.
ExpansionProfile.designation
Definition | A set of criteria that provide the constraints imposed on the value set expansion by including or excluding designations.
Control | 0..1
Summary | true
ExpansionProfile.designation.include
Definition | Designations to be included.
Control | 0..1
Summary | true
ExpansionProfile.designation.include.designation
Definition | A data group for each designation to be included.
Control | 0..*
Summary | true
Comments | At least one of designation.language or designation.use must be provided for each include.designation element.
Invariants | Defined on this element exp-3: SHALL have at least one of language or use (expression : language.exists() or use.exists(), xpath: exists(f:language) or exists(f:use))
ExpansionProfile.designation.include.designation.language
Definition | The language this designation is defined for.
Control | 0..1
Terminology Binding | Common Languages (Extensible but limited to ??)
Type | code
Summary | true
Comments | In the absence of a language, all designations are retained which match the designation.use parameter for this include.designation.
ExpansionProfile.designation.include.designation.use
Definition | Which kinds of designation to include in the expansion.
Control | 0..1
Terminology Binding | Designation Use (Required)
Type | Coding

Summary | true
Comments | In the absence of a use, all designations are retained which match the designation.language parameter for this include.designation element.
ExpansionProfile.designation.exclude
Definition | Designations to be excluded.
Control | 0..1
Summary | true
ExpansionProfile.designation.exclude.designation
Definition | A data group for each designation to be excluded.
Control | 0..*
Summary | true
Comments | At least one of designation.language or designation.use must be provided for each exclude.designation element.
Invariants | Defined on this element exp-4: SHALL have at least one of language or use (expression : language.exists() or use.exists(), xpath: exists(f:language) or exists(f:use))
ExpansionProfile.designation.exclude.designation.language
Definition | The language this designation is defined for.
Control | 0..1
Terminology Binding | Common Languages (Extensible but limited to ??)
Type | code
Summary | true
Comments | In the absence of a language, all designations are excluded which match the designation.use parameter for this exclude.designation element.
ExpansionProfile.designation.exclude.designation.use
Definition | Which kinds of designation to exclude from the expansion.
Control | 0..1
Terminology Binding | Designation Use (Required)
Type | Coding
Summary | true
Comments | In the absence of a use, all designations are retained which match the designation.language parameter for this exclude.designation element.
ExpansionProfile.includeDefinition
Definition | Controls whether the value set definition is included or excluded in value set expansions.
Control | 0..1
Type | boolean
Default Value | false
Summary | true
Comments | The ValueSet defintion refers to all fields in the ValueSet definition apart from ValueSet.contains. The definition is only included if includeDefinition is present and has a value of "true".
ExpansionProfile.activeOnly
Definition | Controls whether inactive concepts are included or excluded in value set expansions.
Control | 0..1
Type | boolean
Default Value | false
Summary | true
Comments | Inactive codes are included if activeOnly is present and has a value of "true". Note that if the value set explicitly specifies that inactive codes are included, this property can still remove them from a specific expansion, but this parameter cannot include them if the value set excludes them.
ExpansionProfile.excludeNested
Definition | Controls whether or not the value set expansion nests codes or not (i.e. ValueSet.expansion.contains.contains).
Control | 0..1
Type | boolean
Requirements | Heirahical contains are useful for UI use, but not when validating. Code Generation etc. may depend on context.
Summary | true
Comments | Nesting of codes is excluded if excludeNested is present and has a value of "true".
ExpansionProfile.excludeNotForUI
Definition | Controls whether or not the value set expansion includes codes which cannot be displayed in user interfaces.
Control | 0..1
Type | boolean
Summary | true
Comments | Codes which cannot be used in user interfaces will be excluded if excludeNotForUI is present and has a value of "true".
ExpansionProfile.excludePostCoordinated
Definition | Controls whether or not the value set expansion includes post coordinated codes.
Control | 0..1
Type | boolean
Summary | true
Comments | Post coordinated codes are excluded if excludePostCoordinated is present and has a value of "true".
ExpansionProfile.displayLanguage
Definition | Specifies the language to be used for description in the expansions i.e. the language to be used for ValueSet.expansion.contains.display.
Control | 0..1
Terminology Binding | Common Languages (Extensible but limited to ??)
Type | code
Summary | true
ExpansionProfile.limitedExpansion

Definition | If the value set being expanded is incomplete (because it is too big to expand), return a limited expansion (a subset) with an indicator that expansion is incomplete, using the extension http://hl7.org/fhir/StructureDefinition/valueset-toocostly.
Control | 0..1
Type | boolean
Summary | true
Comments | This field overides the default behaviour (which is to return an error). This does not apply to expansions which are unbounded. Clients SHALL process the extension http://hl7.org/fhir/StructureDefinition/valueset-toocostly correctly if limitedExpansion = true.

4.11.7 Resource ExpansionProfile - Mappings

URL: https://hl7.org/fhir/STU3/expansionprofile-mappings.html

This page is part of the FHIR Specification (v3.0.2: STU 3). The current version which supercedes this version is 4.0.1. For a full list of available versions, see the Directory of published versions

4.11.7 Resource ExpansionProfile - Mappings

Vocabulary Work Group | Maturity Level: N/A | Ballot Status: Informative | Compartments: Not linked to any defined compartments

Mappings:

RIM Mapping

Mappings for the expansionprofile resource.

4.11.7.1 Mappings for RIM Mapping (http://hl7.org/v3)

ExpansionProfile | N/A

4.11.8 Resource ExpansionProfile - Design Notes

URL: https://hl7.org/fhir/STU3/expansionprofile-explanations.html

This page is part of the FHIR Specification (v3.0.2: STU 3). The current version which supercedes this version is 4.0.1. For a full list of available versions, see the Directory of published versions

4.11.8 Resource ExpansionProfile - Design Notes

to do

4.11.9 Resource ExpansionProfile - Extensions & Profiles

URL: https://hl7.org/fhir/STU3/expansionprofile-profiles.html

This page is part of the FHIR Specification (v3.0.2: STU 3). The current version which supercedes this version is 4.0.1. For a full list of available versions, see the Directory of published versions

4.11.9 Resource ExpansionProfile - Extensions & Profiles

Vocabulary Work Group | Maturity Level: N/A | Ballot Status: Informative

This table lists profiles and extensions for the ExpansionProfile resource. For background information, see Profiling Resources and Extensibility. Additional profiles and resources may be found in published Implementation Guides , or in the Conformance resource registry .

4.11.9.1 Profiles

No Profiles defined for this resource

4.11.9.2 Extensions

resource-approvalDate | approvalDate | for Resource HL7 Extensions
resource-effectivePeriod | effectivePeriod | for Resource HL7 Extensions
resource-lastReviewDate | lastReviewDate | for Resource HL7 Extensions

Extensions that reference this resource:

No Extensions refer to this resource

4.11.9.3 Search Extensions

No Search Extensions defined for this resource