Oracle-FHIR â€” Bulk-Data (sections bulk-data-v10/index.html â€“ bulk-data-v10/op-patient-export-post.html)

Source: Oracle Health Millennium FHIR R4 REST API Guide v32, Bulk Data Access Guide v10 and API guides (oracle-fhir-docs.zip). Text-only edition for AI ingestion (NotebookLM); pages follow the source order (its table of contents when one exists).

About the REST APIs

File: bulk-data-v10/index.html

These HL7 FHIR R4 APIs with Bulk Data Access allow a registered user to access the EHR data in Oracle Health Millennium Platform for which they are authorized.

You can view a list of all REST Endpoints.

Title and Copyright Information

FHIR R4 APIs with Bulk Data Access

G63689-01

Copyright © 2024, 2026 Oracle and/or its affiliates.

This software and related documentation are provided under a license agreement containing restrictions on use and disclosure and are protected by intellectual property laws. Except as expressly permitted in your license agreement or allowed by law, you may not use, copy, reproduce, translate, broadcast, modify, license, transmit, distribute, exhibit, perform, publish, or display any part, in any form, or by any means. Reverse engineering, disassembly, or decompilation of this software, unless required by law for interoperability, is prohibited.

The information contained herein is subject to change without notice and is not warranted to be error-free. If you find any errors, please report them to us in writing.

If this is software, software documentation, data (as defined in the Federal Acquisition Regulation), or related documentation that is delivered to the U.S. Government or anyone licensing it on behalf of the U.S. Government, then the following notice is applicable:

U.S. GOVERNMENT END USERS: Oracle programs (including any operating system, integrated software, any programs embedded, installed, or activated on delivered hardware, and modifications of such programs) and Oracle computer documentation or other Oracle data delivered to or accessed by U.S. Government end users are "commercial computer software," "commercial computer software documentation," or "limited rights data" pursuant to the applicable Federal Acquisition Regulation and agency-specific supplemental regulations. As such, the use, reproduction, duplication, release, display, disclosure, modification, preparation of derivative works, and/or adaptation of i) Oracle programs (including any operating system, integrated software, any programs embedded, installed, or activated on delivered hardware, and modifications of such programs), ii) Oracle computer documentation and/or iii) other Oracle data, is subject to the rights and limitations specified in the license contained in the applicable contract. The terms governing the U.S. Government's use of Oracle cloud services are defined by the applicable contract for such services. No other rights are granted to the U.S. Government.

This software or hardware is developed for general use in a variety of information management applications. It is not developed or intended for use in any inherently dangerous applications, including applications that may create a risk of personal injury. If you use this software or hardware in dangerous applications, then you shall be responsible to take all appropriate fail-safe, backup, redundancy, and other measures to ensure its safe use. Oracle Corporation and its affiliates disclaim any liability for any damages caused by use of this software or hardware in dangerous applications.

Oracle®, Java, MySQL, and NetSuite are registered trademarks of Oracle and/or its affiliates. Other names may be trademarks of their respective owners.

Intel and Intel Inside are trademarks or registered trademarks of Intel Corporation. All SPARC trademarks are used under license and are trademarks or registered trademarks of SPARC International, Inc. AMD, Epyc, and the AMD logo are trademarks or registered trademarks of Advanced Micro Devices. UNIX is a registered trademark of The Open Group.

This software or hardware and documentation may provide access to or information about content, products, and services from third parties. Oracle Corporation and its affiliates are not responsible for and expressly disclaim all warranties of any kind with respect to third-party content, products, and services unless otherwise set forth in an applicable agreement between you and Oracle. Oracle Corporation and its affiliates will not be responsible for any loss, costs, or damages incurred due to your access to or use of third-party content, products, or services, except as set forth in an applicable agreement between you and Oracle.

NOT FOR PUBLIC DISTRIBUTION: 2026-11-09

This documentation is in pre-General Availability status and is intended for demonstration and preliminary use only. It may not be specific to the hardware on which you are using the software. Oracle Corporation and its affiliates are not responsible for and expressly disclaim all warranties of any kind with respect to this documentation and will not be responsible for any loss, costs, or damages incurred due to the use of this documentation.

All REST Endpoints

File: bulk-data-v10/rest-endpoints.html

Bulk Export

The operations from the Bulk Export category.

Delete a bulk data export job

Method: delete Path: /bulk-export/jobs/{Job_ID}

Get file URLs to download the exported resources

Method: get Path: /bulk-export/files/{File_ID}

Get the status of the export job

Method: get Path: /bulk-export/jobs/{Job_ID}

Kick off a bulk export request for a group of patients

Method: get Path: /Group/{Group_ID}/$export

Kick off a bulk export request for the provided list of patients

Method: post Path: /Patient/$export

Bulk Data Access

File: bulk-data-v10/bulk_data_access.html

Bulk Data Access

NOT FOR PUBLIC DISTRIBUTION: 2026-11-09

The Oracle Cerner Ignite APIs for Millennium with Bulk Data Access allows system applications to access large volumes of core clinical data for a group of individuals in alignment with standards cited in 21st Century Cures Act regulations.

FHIR bulk data requests are run against an organization's database asynchronously. When implementing an interface between a Millennium Platform domain and a bulk data application, ensure that the queries inherent in the bulk data request capture only the data necessary for the application.

Several factors affect the amount of time required to complete a bulk API export, such as the following examples:

* The size of the population for which data is requested

* The number of requested resource types

* The time range of the requested activity

* The inherent latency due to network issues and effects from concurrent requests to the system

Example Use Cases

* Creation of an internal clinical data warehouse for study purposes

* Machine learning applications that obtain training data from the electronic health record (EHR)

* Integration of population health system with an EHR system

* Data transfer to payer database for care quality assessment

* Submission to reportable disease (or other) registries

Implemented Exports

Oracle Cerner supports the Group Export operation and the Patient Export operation (for more information, see Bulk Export.

Note:

* For the Group Export operation, Oracle Cerner supports v1.0.1 of the FHIR Bulk Data Access (Flat FHIR) Implementation Guide and supports several experimental parameters from v2.0.0.

* For the Patient Export operation, Oracle Cerner supports v2.0.0 of the FHIR Bulk Data Access (Flat FHIR) Implementation Guide.

* The Patient Export operation does not support an export of all patients. A list of patients IDs must be provided in the request.

Service Root URL

The FHIR Bulk Data server uses the FHIR base URL as the service root URL (for more information, see the Service Root URL topic in FHIR R4 APIs for Oracle Health Millennium Platform).

Media Types

For file retrievals, application/fhir+ndjson is supported. All other requests support application/fhir+json.

Authorization

The bulk data endpoints are secured with OAuth 2.0 with support for SMART applications. See the extensions on the Conformance.rest.security element in our server metadata.

See the Authorization Framework documentation for details on how to authorize with our server.

Registering Client Applications

To be granted access to the Bulk Data Access API, you must register a Millennium Bulk Data SMART application through code Console (for more information, see the SMART documentation on Oracle Help Center). See the Authorization Framework documentation for additional details on registering client applications and authorizing with the server.

In the case of Group Export, client application developers must work with healthcare organizations to identify the available groups to be exported. Organizations can manage groups in Ignite Management Tooling.

Note:

* Authentication is required. Open endpoints do not support bulk export workflows.

* Consider the performance impact because bulk data runs against an organization's database and uses the same services running other applications. Bulk data exports large amounts of data for large groups of patients, and the time to complete the export increases with larger data sets or patient populations.

Sandbox

Testing can be done in sandbox for applications that have authorization (for more information, see the Authorization Framework documentation).

https://fhir-ehr.cerner.com/r4/ec2458f2-1e24-41c8-b71b-0e701af7583d

Client Errors

The following client errors can be received for API requests:

* Failing to send a required search parameter or sending a parameter with an invalid value returns a status code.

400 (Bad Request)

```
HTTP/1.1 400 Bad Request
```

* Making a request without valid credentials returns a status code.

401 (Unauthorized)

```
HTTP/1.1 401 Unauthorized
```

* Requesting data from an unknown instance or an instance where the application is not authorized returns a status code.

403 (Forbidden)

```
HTTP/1.1 403 Forbidden
```

* Requesting a resource that does not exist returns a status code.

404 (Not Found)

```
HTTP/1.1 404 Not Found
```

* Requesting a media type other than JSON returns a status code.

406 (Not Acceptable)

```
HTTP/1.1 406 Not Acceptable

Content-Length: 0
```

* Providing a media type other than JSON in the parameter for patient exports returns a status code.

Content-Type

415 (Unsupported Media Type)

```
HTTP/1.1 415 Unsupported Media Type
```

* Performing an export kick-off using unsupported search parameter values returns a status code.

422 (Unprocessable Entity)

```
HTTP/1.1 422 Unprocessable Entity
```

Lenient Workflow

When the optional header of Prefer: handling=lenient is passed to the export kick-off request, any unknown or unsupported parameters are ignored as specified in the v.2.0.0 FHIR Bulk Data Access (Flat FHIR) Implementation Guide, and the request is processed instead of returning an error.

Operation Outcomes

An operation outcome may be returned to provide additional context for an error.

The following table describes common operation outcomes and their causes:

HTTP Status	Cause	Severity	Code
400	The request has an invalid search parameter or a parameter with an invalid value	error	invalid
401	Invalid credentials were sent in the request	error	login, expired
403	The client is not authorized to access the information	error	forbidden
404	The resource being requested cannot be found	error	not-found
406	The value supplied to the Accept header is not supported	error	invalid
415	The value supplied to the Content-Type header is not supported	error	invalid
429	Too many requests have been sent	error	throttled
500	An internal error occurred	fatal	exception

Bulk Export

File: bulk-data-v10/api-bulk-export.html

Description

Bulk Export

The following topic describes the Group Export and Patient Export operations.

Group Export

Overview

The Group Export operation is used to obtain FHIR resources for all members of a specified group of patients.

An export process uses the FHIR Asynchronous Request Pattern to kick off the export job for a group of patients. Once the export job is kicked off, you can check the status of the job using the URL returned in the Content-Location header from the kick-off response. Once the job is complete, the status request returns a list of file URLs that may be requested to download the content of the file. After the appropriate ndjson files are downloaded, use the delete request to clean up the files that are no longer needed.

The Group Export operation exports resources required for United States Core Data for Interoperability V3 (USCDI). For a full list of resources, see the US Core Profiles. When the _type parameter is used, it returns only the FHIR resources specified. Use the _type parameter to filter the resources required for a specific use case. Limiting the number of requested resources in the _type parameter is recommended to decrease response times.

The examples provided here are non-normative and replaying them in the public sandbox is not guaranteed to yield the results shown on the site.

Note:

Recommendations

* Use the _type parameter whenever possible to improve response times and minimize storage requirements. You can use _typeFilter to further refine the returned results.

* Use the _since parameter to limit the export to only the relevant date range.

* Customers should follow an Exponential Backoff approach when polling for status as outlined in the FHIR Bulk Data Access IG.

* Retrieve files promptly because the exported content expires after 30 days.

* Once the files are retrieved, use the delete request to clean up the data from your request.

* Healthcare organizations may create groups containing up to 20,000 patients. However, the recommended group size for optimal performance is 10,000 patients or less.

Testing in Sandbox

To request bulk data endpoints in the sandbox environment, use one of the following group IDs to kick off a group export and then perform the subsequent requests:

* Group with 3 patients: 11ec-d16a-c763b73e-98e8-a31715e6a2bf

* Group with 10 patients: 11ec-d16a-b40370f8-9d31-577f11a339c5

Example

```
GET https://fhir-
    ehr.cerner.com/r4/ec2458f2-1e24-41c8-b71b-0e701af7583d/Group/11ec-d16a-c763b73e-98e8-
    a31715e6a2bf/$export?_type=Patient
```

Patient Export

Overview

The Patient Export operation is used to obtain FHIR resources for the list of patients provided in the request as an alternative to creating a group.

The current implementation does not support an export of all patients. A maximum of 20,000 patients may be provided in the export kick-off request.

Note:

An export process uses the FHIR Asynchronous Request Pattern to kick off the export job for the provided list of patients. Once the export job is kicked off, you can check the status of the job using the URL returned in the Content-Location header from the kick-off response. Once the job is complete, the status request returns a list of file URLs that may be requested to download the content of the file. After the appropriate ndjson files are downloaded, use the delete request to clean up the files that are no longer needed.

The Patient Export operation supports exporting the following clinical resources:

* AllergyIntolerance

* CarePlan

* CareTeam

* Condition

* Coverage

* Device

* DiagnosticReport

* DocumentReference

* Encounter

* Goal

* Immunization

* MedicationDispense

* MedicationRequest

* Observation

* Patient

* Procedure

* ServiceRequest

You can also export Location, Organization, Practitioner, Provenance, RelatedPerson, and Specimen if at least one clinical resource is being exported as well.

When the _type parameter is used, only the FHIR resources specified are returned. Use the _type parameter to filter the resources required for a specific use case. Limiting the number of requested resources in the _type parameter is recommended to decrease response times.

The examples provided here are non-normative and replaying them in the public sandbox is not guaranteed to yield the results shown on the site.

Note:

Recommendations

* Use the _type parameter whenever possible to improve response times and minimize storage requirements. You can also use _typeFilter to further refine the returned results.

* Use the _since parameter to limit the export to only the relevant date range.

* Customers should follow an Exponential Backoff approach when polling for status as outlined in the FHIR Bulk Data Access IG.

* Retrieve files promptly because the exported content expires after 30 days.

* Once the files are retrieved, use the delete request to clean up the data from your request.

* The Patient Export operation supports a list of up to 20,000 patients. However, the recommended size for optimal performance is 10,000 patients or less.

Bulk Export

The operations from the Bulk Export category.

Delete a bulk data export job

Method: delete Path: /bulk-export/jobs/{Job_ID}

Get file URLs to download the exported resources

Method: get Path: /bulk-export/files/{File_ID}

Get the status of the export job

Method: get Path: /bulk-export/jobs/{Job_ID}

Kick off a bulk export request for a group of patients

Method: get Path: /Group/{Group_ID}/$export

Kick off a bulk export request for the provided list of patients

Method: post Path: /Patient/$export

Delete a bulk data export job

File: bulk-data-v10/op-bulk-export-jobs-job_id-delete.html

Use the URL returned in the Content-Location header from the kick-off request to delete a bulk data export job (whether the status is in-progress or complete) and any associated files. See the example response for the group export operation.

Note: Scopes are not checked in this request. The authorization token must be valid, and the client in the token must match the client that requested the export.

Request

Path Parameters

* Job_ID(required): string The logical resource ID.

Header Parameters

Accept(required): string

The media type to be requested. Refer to what the resource's operation produces for what is supported.

Example: application/fhir+json

* Authorization(required): string Contains the credentials to authenticate a consumer to the service. This should be the OAuth2 Bearer Token.

Back to Top

Response

Supported Media Types

* application/fhir+json

Default Response

This operation supports the authorization type.

System

Example Request:

```
DELETE https://fhir-ehr.cerner.com/r4/ec2458f2-1e24-41c8-b71b-0e701af7583d/bulk-export/jobs/<Job_ID>
```

Example Response:

```
Status: 202 Accepted
```

Headers

* X-Request-Id: string Unique Oracle-assigned identifier for the request. If you need to contact Oracle about a particular request, provide the X-Request-Id, if present.

* opc-request-id: string Unique Oracle-assigned identifier for the request. If you need to contact Oracle about a particular request, provide the opc-request-id, if present.

Back to Top

Get file URLs to download the exported resources

File: bulk-data-v10/op-bulk-export-files-file_id-get.html

Once an export is complete, the status request returns file URLs that you can use to download the exported resources. See the x-complete example response for the bulk export operation.

```
GET <File URL from status response>
```

Note:

* The file retrieval request returns a 307 (Temporary Redirect) status code with a Location header. The Location header must be followed to download the file.

* An exported ndjson file contains only a single resource type and the same resource type can have multiple files. The number of resources per file has no limit. An exported file has a maximum size of 50 MB when gzip compressed.

* Files expire after 30 days.

* The initial file retrieval request requires the authorization header to be sent. When following the redirect, sending the authorization header is no longer appropriate. Ensure that the authorization header is not perpetuated.

Retrieval of Attachments

* Binary resources are not returned by bulk data operations.

* Attachment references must be retrieved separately using the Binary resource URL from the DocumentReference.content.attachment and DiagnosticReport.presentedForm fields from the export files.

Request

Path Parameters

* File_ID(required): string The logical resource ID.

Header Parameters

Accept(required): string

The media type to be requested. Refer to what the resource's operation produces for what is supported.

Example: application/fhir+json

* Authorization(required): string Contains the credentials to authenticate a consumer to the service. This should be the OAuth2 Bearer Token.

Back to Top

Response

Supported Media Types

* application/fhir+ndjson

Default Response

This operation supports the authorization type.

System

Example Request:

```
GET https://fhir-ehr.cerner.com/r4/ec2458f2-1e24-41c8-b71b-0e701af7583d/bulk-export/files/<File_ID>
```

Example Response:

```
Status: 307 Temporary Redirect
Location: https://cerner-opensvc-bulkfhir-processed.s3.us-west-2.amazonaws.com
```

Headers

* Location: string Indicates the redirect URL that must be followed to download the files.

* X-Request-Id: string Unique Oracle-assigned identifier for the request. If you need to contact Oracle about a particular request, provide the X-Request-Id, if present.

* opc-request-id: string Unique Oracle-assigned identifier for the request. If you need to contact Oracle about a particular request, provide the opc-request-id, if present.

x-following-redirect Response

Note:

* When following the redirect link from the Location header, an Authorization header should not be set as the URL is presigned.

* Redirect links are short-lived.

* Files are deleted 30 days after creation.

Example Request:

```
GET https://cerner-opensvc-bulkfhir-processed.s3.us-west-2.amazonaws.com
```

Example Response:

```
Status: 200 OK
Content-Type: application/fhir+ndjson
```


```
{
  "resourceType": "Patient",
  "id": "12783127",
  "meta": {
    "versionId": "7",
    "lastUpdated": "2022-07-01T20:12:56.000Z"
  },
  "text": {
    "status": "extensions",
    "div": "<div xmlns="http://www.w3.org/1999/xhtml"><p><b>Patient</b></p><p><b>Name</b>: FHIRONE,
    BULKDATAONE</p><p><b>Status</b>: Active</p><p><b>DOB</b>: Apr 18, 1988</p><p><b>Birth Sex</b>:
    Female</p><p><b>Administrative Gender</b>: Female</p><p><b>Marital Status</b>: Married</p></div>"
  },
  "extension": [
    {
      "valueCode": "F",
      "url": "http://hl7.org/fhir/us/core/StructureDefinition/us-core-birthsex"
    },
    {
      "extension": [
        {
          "valueCoding": {
            "system": "urn:oid:2.16.840.1.113883.6.238",
            "code": "2106-3",
            "display": "White",
            "userSelected": false
          },
          "url": "ombCategory"
        },
        {
          "valueString": "White",
          "url": "text"
        }
      ],
      "url": "http://hl7.org/fhir/us/core/StructureDefinition/us-core-race"
    },
    {
      "extension": [
        {
          "valueCoding": {
            "system": "urn:oid:2.16.840.1.113883.6.238",
            "code": "2186-5",
            "display": "Not Hispanic or Latino",
            "userSelected": false
          },
          "url": "ombCategory"
        },
        {
          "valueString": "Not Hispanic, Latino, or Spanish Origin",
          "url": "text"
        }
      ],
      "url": "http://hl7.org/fhir/us/core/StructureDefinition/us-core-ethnicity"
```

```
  }
],
"identifier": [
  {
    "id": "CI-490689587-0",
    "use": "usual",
    "type": {
      "coding": [
        {
          "system": "https://fhir.cerner.com/ec2458f2-1e24-41c8-b71b-0e701af7583d/codeSet/4",
          "code": "2",
          "display": "Community Medical Record Number",
          "userSelected": true
        },
        {
          "system": "http://terminology.hl7.org/CodeSystem/v2-0203",
          "code": "MR",
          "display": "Medical record number",
          "userSelected": false
        }
      ],
      "text": "Community Medical Record Number"
    },
    "system": "urn:oid:2.16.840.1.113883.3.787.0.0",
    "value": "490689587",
    "_value": {
      "extension": [
        {
          "valueString": "490689587",
          "url": "http://hl7.org/fhir/StructureDefinition/rendered-value"
        }
      ]
    },
    "period": {
      "start": "2022-03-08T17:07:02.000Z"
    }
  },
  {
    "id": "CI-490689586-1",
    "use": "usual",
    "type": {
      "coding": [
        {
          "system": "https://fhir.cerner.com/ec2458f2-1e24-41c8-b71b-0e701af7583d/codeSet/4",
          "code": "10",
          "display": "MRN",
          "userSelected": true
        },
        {
          "system": "http://terminology.hl7.org/CodeSystem/v2-0203",
          "code": "MR",
          "display": "Medical record number",
          "userSelected": false
        }
      ],
      "text": "MRN"
    },
    "system": "urn:oid:2.16.840.1.113883.6.1000",
    "value": "490689586",
    "_value": {
      "extension": [
        {
          "valueString": "00490689586",
          "url": "http://hl7.org/fhir/StructureDefinition/rendered-value"
        }
      ]
    },
    "period": {
      "start": "2022-03-08T17:07:02.000Z"
    }
  },
  {
    "id": "CI-490689589-3",
    "use": "usual",
    "type": {
      "coding": [
        {
          "system": "https://fhir.cerner.com/ec2458f2-1e24-41c8-b71b-0e701af7583d/codeSet/4",
          "code": "670843",
          "display": "Messaging",
          "userSelected": true
        },
        {
          "system": "http://terminology.hl7.org/CodeSystem/v2-0203",
          "code": "U",
          "display": "Unspecified identifier",
          "userSelected": false
        }
      ],
```

```
      "text": "Messaging"
    },
    "system": "urn:oid:2.16.840.1.113883.3.13.8",
    "value": "FED810ECAD834ABC88E88F3223B3133D",
    "_value": {
      "extension": [
        {
          "valueString": "FED810ECAD834ABC88E88F3223B3133D",
          "url": "http://hl7.org/fhir/StructureDefinition/rendered-value"
        }
      ]
    },
    "period": {
      "start": "2022-03-08T17:14:16.000Z"
    }
  },
  {
    "id": "CI-490689585-4",
    "use": "usual",
    "type": {
      "coding": [
        {
          "system": "https://fhir.cerner.com/ec2458f2-1e24-41c8-b71b-0e701af7583d/codeSet/4",
          "code": "2553236771",
          "display": "Federated Person Principal",
          "userSelected": true
        },
        {
          "system": "http://terminology.hl7.org/CodeSystem/v2-0203",
          "code": "AN",
          "display": "Account number",
          "userSelected": false
        }
      ],
      "text": "Federated Person Principal"
    },
    "system": "urn:oid:2.16.840.1.113883.3.13.6",
    "value": "URN:CERNER:IDENTITY-
FEDERATION:REALM:EC2458F2-1E24-41C8-B71B-0E701AF7583D-CH:PRINCIPAL:SN7HR6J27QX8WM5H",
    "_value": {
      "extension": [
        {
          "valueString": "URN:CERNER:IDENTITY-
FEDERATION:REALM:EC2458F2-1E24-41C8-B71B-0E701AF7583D-CH:PRINCIPAL:SN7HR6J27QX8WM5H",
          "url": "http://hl7.org/fhir/StructureDefinition/rendered-value"
        }
      ]
    },
    "period": {
      "start": "2022-03-08T17:14:15.000Z"
    }
  },
  {
    "id": "CI-490689588-5",
    "use": "usual",
    "type": {
      "coding": [
        {
          "system": "https://fhir.cerner.com/ec2458f2-1e24-41c8-b71b-0e701af7583d/codeSet/4",
          "code": "2553236785",
          "display": "MIllennium Person Identifier",
          "userSelected": true
        }
      ],
      "text": "MIllennium Person Identifier"
    },
    "_system": {
      "extension": [
        {
          "valueCode": "unknown",
          "url": "http://hl7.org/fhir/StructureDefinition/data-absent-reason"
        }
      ]
    },
    "value": "50946",
    "_value": {
      "extension": [
        {
          "valueString": "50946",
          "url": "http://hl7.org/fhir/StructureDefinition/rendered-value"
        }
      ]
    },
    "period": {
      "start": "2022-03-08T17:07:07.000Z"
    }
  }
],
"active": true,
```

```
"name": [
  {
    "id": "CI-12783127-0",
    "use": "official",
    "text": "FHIRONE, BULKDATAONE",
    "family": "FHIRONE",
    "given": [
      "BULKDATAONE"
    ],
    "period": {
      "start": "2022-03-08T17:07:03.000Z"
    }
  }
],
"telecom": [
  {
    "id": "CI-PH-29913336-0",
    "extension": [
      {
        "valueUrl": "(816)204-1030",
        "url": "http://hl7.org/fhir/StructureDefinition/iso21090-TEL-address"
      }
    ],
    "system": "phone",
    "value": "8162041030",
    "use": "work",
    "rank": 1,
    "period": {
      "start": "2022-03-08T17:07:02.000Z"
    }
  },
  {
    "id": "CI-PH-29913334-1",
    "extension": [
      {
        "valueUrl": "(913)224-2321",
        "url": "http://hl7.org/fhir/StructureDefinition/iso21090-TEL-address"
      }
    ],
    "system": "phone",
    "value": "9132242321",
    "use": "home",
    "rank": 1,
    "period": {
      "start": "2022-03-08T17:07:02.000Z"
    }
  },
  {
    "id": "CI-PH-29913337-2",
    "extension": [
      {
        "valueUrl": "(913)268-4302",
        "url": "http://hl7.org/fhir/StructureDefinition/iso21090-TEL-address"
      }
    ],
    "system": "phone",
    "value": "9132684302",
    "use": "mobile",
    "rank": 1,
    "period": {
      "start": "2022-03-08T17:07:02.000Z"
    }
  }
],
"gender": "female",
"birthDate": "1988-04-18",
"address": [
  {
    "id": "CI-24415338-0",
    "use": "home",
    "text": "2804 S Elm Street\\nOverland Park, KS 66216\\nUS",
    "line": [
      "2804 S Elm Street"
    ],
    "city": "Overland Park",
    "district": "Johnson",
    "state": "KS",
    "postalCode": "66216",
    "country": "US",
    "period": {
      "start": "2022-03-08T16:55:27.000Z"
    }
  }
],
"maritalStatus": {
  "coding": [
    {
      "system": "https://fhir.cerner.com/ec2458f2-1e24-41c8-b71b-0e701af7583d/codeSet/38",
      "code": "309237",
```

```
      "display": "Married",
      "userSelected": true
    },
    {
      "system": "http://terminology.hl7.org/CodeSystem/v3-MaritalStatus",
      "code": "M",
      "display": "Married",
      "userSelected": false
    }
  ],
  "text": "Married"
},
"contact": [
  {
    "relationship": [
      {
        "coding": [
          {
            "system": "https://fhir.cerner.com/ec2458f2-1e24-41c8-b71b-0e701af7583d/codeSet/351",
            "code": "1153",
            "display": "Family Member",
            "userSelected": true
          }
        ],
        "text": "Family Member"
      }
    ],
    "name": {
      "id": "CI-12800368-0",
      "use": "official",
      "text": "FHIRELEVEN, BULKDATAPEDIATRIC",
      "family": "FHIRELEVEN",
      "given": [
        "BULKDATAPEDIATRIC"
      ],
      "period": {
        "start": "2022-07-01T20:12:56.000Z"
      }
    },
    "telecom": [
      {
        "extension": [
          {
            "valueUrl": "(913)524-1874",
            "url": "http://hl7.org/fhir/StructureDefinition/iso21090-TEL-address"
          }
        ],
        "system": "phone",
        "value": "9135241874",
        "use": "home",
        "rank": 1,
        "period": {
          "start": "2022-07-01T20:12:56.000Z"
        }
      }
    ],
    "address": {
      "use": "home",
      "text": "2804 S Elm Street\\nOverland Park, KS 66216\\nUS",
      "line": [
        "2804 S Elm Street"
      ],
      "city": "Overland Park",
      "district": "Johnson",
      "state": "KS",
      "postalCode": "66216",
      "country": "US",
      "period": {
        "start": "2022-07-01T20:05:24.000Z"
      }
    },
    "gender": "female",
    "period": {
      "start": "2022-07-01T20:12:56.000Z"
    }
  }
],
"communication": [
  {
    "language": {
      "coding": [
        {
          "system": "https://fhir.cerner.com/ec2458f2-1e24-41c8-b71b-0e701af7583d/codeSet/36",
          "code": "151",
          "display": "English",
          "userSelected": true
        },
        {
          "system": "urn:ietf:bcp:47",
```

```
            "code": "en",
            "display": "English",
            "userSelected": false
          }
        ],
        "text": "English"
      },
      "preferred": true
    }
  ],
  "generalPractitioner": [
    {
      "id": "CI-490689630-0",
      "reference": "Practitioner/3332086",
      "display": "Cerner Test, Physician - Primary Care Eight Cerner"
    }
  ]
}
{
  "resourceType": "Patient",
  "id": "12783128",
  "meta": {
    "versionId": "5",
    "lastUpdated": "2022-05-27T20:32:48.000Z"
  },
  "text": {
    "status": "extensions",
    "div": "<div xmlns="http://www.w3.org/1999/xhtml"><p><b>Patient</b></p><p><b>Name</b>: FHIRTWO,
    BULKDATATWO</p><p><b>Status</b>: Active</p><p><b>DOB</b>: May 31, 1993</p><p><b>Birth Sex</b>:
    Female</p><p><b>Administrative Gender</b>: Male</p><p><b>Marital Status</b>: Married</p></div>"
  },
  "extension": [
    {
      "valueCode": "F",
      "url": "http://hl7.org/fhir/us/core/StructureDefinition/us-core-birthsex"
    },
    {
      "extension": [
        {
          "valueCoding": {
            "system": "urn:oid:2.16.840.1.113883.6.238",
            "code": "2106-3",
            "display": "White",
            "userSelected": false
          },
          "url": "ombCategory"
        },
        {
          "valueString": "White",
          "url": "text"
        }
      ],
      "url": "http://hl7.org/fhir/us/core/StructureDefinition/us-core-race"
    },
    {
      "extension": [
        {
          "valueCoding": {
            "system": "urn:oid:2.16.840.1.113883.6.238",
            "code": "2186-5",
            "display": "Not Hispanic or Latino",
            "userSelected": false
          },
          "url": "ombCategory"
        },
        {
          "valueString": "Not Hispanic, Latino, or Spanish Origin",
          "url": "text"
        }
      ],
      "url": "http://hl7.org/fhir/us/core/StructureDefinition/us-core-ethnicity"
    }
  ],
  "identifier": [
    {
      "id": "CI-490689642-0",
      "use": "usual",
      "type": {
        "coding": [
          {
            "system": "https://fhir.cerner.com/ec2458f2-1e24-41c8-b71b-0e701af7583d/codeSet/4",
            "code": "2",
            "display": "Community Medical Record Number",
            "userSelected": true
          },
          {
            "system": "http://terminology.hl7.org/CodeSystem/v2-0203",
            "code": "MR",
            "display": "Medical record number",
```

```
        "userSelected": false
      }
    ],
    "text": "Community Medical Record Number"
  },
  "system": "urn:oid:2.16.840.1.113883.3.787.0.0",
  "value": "490689642",
  "_value": {
    "extension": [
      {
        "valueString": "490689642",
        "url": "http://hl7.org/fhir/StructureDefinition/rendered-value"
      }
    ]
  },
  "period": {
    "start": "2022-03-08T17:07:02.000Z"
  }
},
{
  "id": "CI-490689641-1",
  "use": "usual",
  "type": {
    "coding": [
      {
        "system": "https://fhir.cerner.com/ec2458f2-1e24-41c8-b71b-0e701af7583d/codeSet/4",
        "code": "10",
        "display": "MRN",
        "userSelected": true
      },
      {
        "system": "http://terminology.hl7.org/CodeSystem/v2-0203",
        "code": "MR",
        "display": "Medical record number",
        "userSelected": false
      }
    ],
    "text": "MRN"
  },
  "system": "urn:oid:2.16.840.1.113883.6.1000",
  "value": "490689641",
  "_value": {
    "extension": [
      {
        "valueString": "00490689641",
        "url": "http://hl7.org/fhir/StructureDefinition/rendered-value"
      }
    ]
  },
  "period": {
    "start": "2022-03-08T17:07:02.000Z"
  }
},
{
  "id": "CI-490689644-3",
  "use": "usual",
  "type": {
    "coding": [
      {
        "system": "https://fhir.cerner.com/ec2458f2-1e24-41c8-b71b-0e701af7583d/codeSet/4",
        "code": "670843",
        "display": "Messaging",
        "userSelected": true
      },
      {
        "system": "http://terminology.hl7.org/CodeSystem/v2-0203",
        "code": "U",
        "display": "Unspecified identifier",
        "userSelected": false
      }
    ],
    "text": "Messaging"
  },
  "system": "urn:oid:2.16.840.1.113883.3.13.8",
  "value": "FED810ECAD834ABC88E88F3223B3133D",
  "_value": {
    "extension": [
      {
        "valueString": "FED810ECAD834ABC88E88F3223B3133D",
        "url": "http://hl7.org/fhir/StructureDefinition/rendered-value"
      }
    ]
  },
  "period": {
    "start": "2022-03-08T17:14:16.000Z"
  }
},
{
  "id": "CI-490689640-4",
```

```
    "use": "usual",
    "type": {
      "coding": [
        {
          "system": "https://fhir.cerner.com/ec2458f2-1e24-41c8-b71b-0e701af7583d/codeSet/4",
          "code": "2553236771",
          "display": "Federated Person Principal",
          "userSelected": true
        },
        {
          "system": "http://terminology.hl7.org/CodeSystem/v2-0203",
          "code": "AN",
          "display": "Account number",
          "userSelected": false
        }
      ],
      "text": "Federated Person Principal"
    },
    "system": "urn:oid:2.16.840.1.113883.3.13.6",
    "value": "URN:CERNER:IDENTITY-
  FEDERATION:REALM:EC2458F2-1E24-41C8-B71B-0E701AF7583D-CH:PRINCIPAL:SN7HR6J27QX8WM5H",
    "_value": {
      "extension": [
        {
          "valueString": "URN:CERNER:IDENTITY-
  FEDERATION:REALM:EC2458F2-1E24-41C8-B71B-0E701AF7583D-CH:PRINCIPAL:SN7HR6J27QX8WM5H",
          "url": "http://hl7.org/fhir/StructureDefinition/rendered-value"
        }
      ]
    },
    "period": {
      "start": "2022-03-08T17:14:15.000Z"
    }
  },
  {
    "id": "CI-490689643-5",
    "use": "usual",
    "type": {
      "coding": [
        {
          "system": "https://fhir.cerner.com/ec2458f2-1e24-41c8-b71b-0e701af7583d/codeSet/4",
          "code": "2553236785",
          "display": "MIllennium Person Identifier",
          "userSelected": true
        }
      ],
      "text": "MIllennium Person Identifier"
    },
    "_system": {
      "extension": [
        {
          "valueCode": "unknown",
          "url": "http://hl7.org/fhir/StructureDefinition/data-absent-reason"
        }
      ]
    },
    "value": "50946",
    "_value": {
      "extension": [
        {
          "valueString": "50946",
          "url": "http://hl7.org/fhir/StructureDefinition/rendered-value"
        }
      ]
    },
    "period": {
      "start": "2022-03-08T17:07:07.000Z"
    }
  }
],
"active": true,
"name": [
  {
    "id": "CI-12783128-0",
    "use": "official",
    "text": "FHIRTWO, BULKDATATWO",
    "family": "FHIRTWO",
    "given": [
      "BULKDATATWO"
    ],
    "period": {
      "start": "2022-03-08T17:07:03.000Z"
    }
  }
],
"telecom": [
  {
    "id": "CI-PH-29913344-0",
    "extension": [
```

```
      {
        "valueUrl": "(816)204-1030",
        "url": "http://hl7.org/fhir/StructureDefinition/iso21090-TEL-address"
      }
    ],
    "system": "phone",
    "value": "8162041030",
    "use": "work",
    "rank": 1,
    "period": {
      "start": "2022-03-08T17:07:02.000Z"
    }
  },
  {
    "id": "CI-PH-29913342-1",
    "extension": [
      {
        "valueUrl": "(913)224-2321",
        "url": "http://hl7.org/fhir/StructureDefinition/iso21090-TEL-address"
      }
    ],
    "system": "phone",
    "value": "9132242321",
    "use": "home",
    "rank": 1,
    "period": {
      "start": "2022-03-08T17:07:02.000Z"
    }
  },
  {
    "id": "CI-PH-29913345-2",
    "extension": [
      {
        "valueUrl": "(913)268-4302",
        "url": "http://hl7.org/fhir/StructureDefinition/iso21090-TEL-address"
      }
    ],
    "system": "phone",
    "value": "9132684302",
    "use": "mobile",
    "rank": 1,
    "period": {
      "start": "2022-03-08T17:07:02.000Z"
    }
  }
],
"gender": "male",
"birthDate": "1993-05-31",
"address": [
  {
    "id": "CI-24415346-0",
    "use": "home",
    "text": "2804 S Elm Street\\nOverland Park, KS 66216\\nUS",
    "line": [
      "2804 S Elm Street"
    ],
    "city": "Overland Park",
    "district": "Johnson",
    "state": "KS",
    "postalCode": "66216",
    "country": "US",
    "period": {
      "start": "2022-03-08T16:55:27.000Z"
    }
  }
],
"maritalStatus": {
  "coding": [
    {
      "system": "https://fhir.cerner.com/ec2458f2-1e24-41c8-b71b-0e701af7583d/codeSet/38",
      "code": "309237",
      "display": "Married",
      "userSelected": true
    },
    {
      "system": "http://terminology.hl7.org/CodeSystem/v3-MaritalStatus",
      "code": "M",
      "display": "Married",
      "userSelected": false
    }
  ],
  "text": "Married"
},
"communication": [
  {
    "language": {
      "coding": [
        {
          "system": "https://fhir.cerner.com/ec2458f2-1e24-41c8-b71b-0e701af7583d/codeSet/36",
```

```
            "code": "151",
            "display": "English",
            "userSelected": true
          },
          {
            "system": "urn:ietf:bcp:47",
            "code": "en",
            "display": "English",
            "userSelected": false
          }
        ],
        "text": "English"
      },
      "preferred": true
    }
  ],
  "generalPractitioner": [
    {
      "id": "CI-490689685-0",
      "reference": "Practitioner/3332086",
      "display": "Cerner Test, Physician - Primary Care Eight Cerner"
    }
  ]
}
{
  "resourceType": "Patient",
  "id": "12783129",
  "meta": {
    "versionId": "5",
    "lastUpdated": "2022-05-27T20:33:37.000Z"
  },
  "text": {
    "status": "extensions",
    "div": "<div xmlns="http://www.w3.org/1999/xhtml"><p><b>Patient</b></p><p><b>Name</b>: FHIRTHREE,
    BULKDATATHREE</p><p><b>Status</b>: Active</p><p><b>DOB</b>: May 22, 1978</p><p><b>Birth Sex</b>:
    Female</p><p><b>Administrative Gender</b>: Female</p><p><b>Marital Status</b>: Married</p></div>"
  },
  "extension": [
    {
      "valueCode": "F",
      "url": "http://hl7.org/fhir/us/core/StructureDefinition/us-core-birthsex"
    },
    {
      "extension": [
        {
          "valueCoding": {
            "system": "urn:oid:2.16.840.1.113883.6.238",
            "code": "2106-3",
            "display": "White",
            "userSelected": false
          },
          "url": "ombCategory"
        },
        {
          "valueString": "White",
          "url": "text"
        }
      ],
      "url": "http://hl7.org/fhir/us/core/StructureDefinition/us-core-race"
    },
    {
      "extension": [
        {
          "valueCoding": {
            "system": "urn:oid:2.16.840.1.113883.6.238",
            "code": "2186-5",
            "display": "Not Hispanic or Latino",
            "userSelected": false
          },
          "url": "ombCategory"
        },
        {
          "valueString": "Not Hispanic, Latino, or Spanish Origin",
          "url": "text"
        }
      ],
      "url": "http://hl7.org/fhir/us/core/StructureDefinition/us-core-ethnicity"
    }
  ],
  "identifier": [
    {
      "id": "CI-490689697-0",
      "use": "usual",
      "type": {
        "coding": [
          {
            "system": "https://fhir.cerner.com/ec2458f2-1e24-41c8-b71b-0e701af7583d/codeSet/4",
            "code": "2",
            "display": "Community Medical Record Number",
```

```
        "userSelected": true
      },
      {
        "system": "http://terminology.hl7.org/CodeSystem/v2-0203",
        "code": "MR",
        "display": "Medical record number",
        "userSelected": false
      }
    ],
    "text": "Community Medical Record Number"
  },
  "system": "urn:oid:2.16.840.1.113883.3.787.0.0",
  "value": "490689697",
  "_value": {
    "extension": [
      {
        "valueString": "490689697",
        "url": "http://hl7.org/fhir/StructureDefinition/rendered-value"
      }
    ]
  },
  "period": {
    "start": "2022-03-08T17:07:02.000Z"
  }
},
{
  "id": "CI-490689696-1",
  "use": "usual",
  "type": {
    "coding": [
      {
        "system": "https://fhir.cerner.com/ec2458f2-1e24-41c8-b71b-0e701af7583d/codeSet/4",
        "code": "10",
        "display": "MRN",
        "userSelected": true
      },
      {
        "system": "http://terminology.hl7.org/CodeSystem/v2-0203",
        "code": "MR",
        "display": "Medical record number",
        "userSelected": false
      }
    ],
    "text": "MRN"
  },
  "system": "urn:oid:2.16.840.1.113883.6.1000",
  "value": "490689696",
  "_value": {
    "extension": [
      {
        "valueString": "00490689696",
        "url": "http://hl7.org/fhir/StructureDefinition/rendered-value"
      }
    ]
  },
  "period": {
    "start": "2022-03-08T17:07:02.000Z"
  }
},
{
  "id": "CI-490689699-3",
  "use": "usual",
  "type": {
    "coding": [
      {
        "system": "https://fhir.cerner.com/ec2458f2-1e24-41c8-b71b-0e701af7583d/codeSet/4",
        "code": "670843",
        "display": "Messaging",
        "userSelected": true
      },
      {
        "system": "http://terminology.hl7.org/CodeSystem/v2-0203",
        "code": "U",
        "display": "Unspecified identifier",
        "userSelected": false
      }
    ],
    "text": "Messaging"
  },
  "system": "urn:oid:2.16.840.1.113883.3.13.8",
  "value": "FED810ECAD834ABC88E88F3223B3133D",
  "_value": {
    "extension": [
      {
        "valueString": "FED810ECAD834ABC88E88F3223B3133D",
        "url": "http://hl7.org/fhir/StructureDefinition/rendered-value"
      }
    ]
  },
```

```
    "period": {
      "start": "2022-03-08T17:14:16.000Z"
    }
  },
  {
    "id": "CI-490689695-4",
    "use": "usual",
    "type": {
      "coding": [
        {
          "system": "https://fhir.cerner.com/ec2458f2-1e24-41c8-b71b-0e701af7583d/codeSet/4",
          "code": "2553236771",
          "display": "Federated Person Principal",
          "userSelected": true
        },
        {
          "system": "http://terminology.hl7.org/CodeSystem/v2-0203",
          "code": "AN",
          "display": "Account number",
          "userSelected": false
        }
      ],
      "text": "Federated Person Principal"
    },
    "system": "urn:oid:2.16.840.1.113883.3.13.6",
    "value": "URN:CERNER:IDENTITY-
FEDERATION:REALM:EC2458F2-1E24-41C8-B71B-0E701AF7583D-CH:PRINCIPAL:SN7HR6J27QX8WM5H",
    "_value": {
      "extension": [
        {
          "valueString": "URN:CERNER:IDENTITY-
FEDERATION:REALM:EC2458F2-1E24-41C8-B71B-0E701AF7583D-CH:PRINCIPAL:SN7HR6J27QX8WM5H",
          "url": "http://hl7.org/fhir/StructureDefinition/rendered-value"
        }
      ]
    },
    "period": {
      "start": "2022-03-08T17:14:15.000Z"
    }
  },
  {
    "id": "CI-490689698-5",
    "use": "usual",
    "type": {
      "coding": [
        {
          "system": "https://fhir.cerner.com/ec2458f2-1e24-41c8-b71b-0e701af7583d/codeSet/4",
          "code": "2553236785",
          "display": "MIllennium Person Identifier",
          "userSelected": true
        }
      ],
      "text": "MIllennium Person Identifier"
    },
    "_system": {
      "extension": [
        {
          "valueCode": "unknown",
          "url": "http://hl7.org/fhir/StructureDefinition/data-absent-reason"
        }
      ]
    },
    "value": "50946",
    "_value": {
      "extension": [
        {
          "valueString": "50946",
          "url": "http://hl7.org/fhir/StructureDefinition/rendered-value"
        }
      ]
    },
    "period": {
      "start": "2022-03-08T17:07:07.000Z"
    }
  }
],
"active": true,
"name": [
  {
    "id": "CI-12783129-0",
    "use": "official",
    "text": "FHIRTHREE, BULKDATATHREE",
    "family": "FHIRTHREE",
    "given": [
      "BULKDATATHREE"
    ],
    "period": {
      "start": "2022-03-08T17:07:03.000Z"
    }
```

```
  }
],
"telecom": [
  {
    "id": "CI-PH-29913352-0",
    "extension": [
      {
        "valueUrl": "(816)204-1030",
        "url": "http://hl7.org/fhir/StructureDefinition/iso21090-TEL-address"
      }
    ],
    "system": "phone",
    "value": "8162041030",
    "use": "work",
    "rank": 1,
    "period": {
      "start": "2022-03-08T17:07:02.000Z"
    }
  },
  {
    "id": "CI-PH-29913350-1",
    "extension": [
      {
        "valueUrl": "(913)224-2321",
        "url": "http://hl7.org/fhir/StructureDefinition/iso21090-TEL-address"
      }
    ],
    "system": "phone",
    "value": "9132242321",
    "use": "home",
    "rank": 1,
    "period": {
      "start": "2022-03-08T17:07:02.000Z"
    }
  },
  {
    "id": "CI-PH-29913353-2",
    "extension": [
      {
        "valueUrl": "(913)268-4302",
        "url": "http://hl7.org/fhir/StructureDefinition/iso21090-TEL-address"
      }
    ],
    "system": "phone",
    "value": "9132684302",
    "use": "mobile",
    "rank": 1,
    "period": {
      "start": "2022-03-08T17:07:02.000Z"
    }
  }
],
"gender": "female",
"birthDate": "1978-05-22",
"address": [
  {
    "id": "CI-24415354-0",
    "use": "home",
    "text": "2804 S Elm Street\\nOverland Park, KS 66216\\nUS",
    "line": [
      "2804 S Elm Street"
    ],
    "city": "Overland Park",
    "district": "Johnson",
    "state": "KS",
    "postalCode": "66216",
    "country": "US",
    "period": {
      "start": "2022-03-08T16:55:27.000Z"
    }
  }
],
"maritalStatus": {
  "coding": [
    {
      "system": "https://fhir.cerner.com/ec2458f2-1e24-41c8-b71b-0e701af7583d/codeSet/38",
      "code": "309237",
      "display": "Married",
      "userSelected": true
    },
    {
      "system": "http://terminology.hl7.org/CodeSystem/v3-MaritalStatus",
      "code": "M",
      "display": "Married",
      "userSelected": false
    }
  ],
  "text": "Married"
},
```

```
  "communication": [
    {
      "language": {
        "coding": [
          {
            "system": "https://fhir.cerner.com/ec2458f2-1e24-41c8-b71b-0e701af7583d/codeSet/36",
            "code": "151",
            "display": "English",
            "userSelected": true
          },
          {
            "system": "urn:ietf:bcp:47",
            "code": "en",
            "display": "English",
            "userSelected": false
          }
        ],
        "text": "English"
      },
      "preferred": true
    }
  ],
  "generalPractitioner": [
    {
      "id": "CI-490689740-0",
      "reference": "Practitioner/3332086",
      "display": "Cerner Test, Physician - Primary Care Eight Cerner"
    }
  ]
}
```


Headers

* Content-Type: string Indicates the media type of the response body.

Back to Top

Get the status of the export job

File: bulk-data-v10/op-bulk-export-jobs-job_id-get.html

Use the URL returned in the Content-Location header from the kick-off request to retrieve the status of a bulk data export. See the example response for the group export operation.

Note:

* Follow an exponential backoff approach when polling for the status as outlined in the bulk data export specification.

* Scopes are not checked in this request. The authorization token must be valid, and the client in the token must match the client that requested the export.

Request

Path Parameters

* Job_ID(required): string The logical resource ID.

Header Parameters

Accept(required): string

The media type to be requested. Refer to what the resource's operation produces for what is supported.

Example: application/fhir+json

* Authorization(required): string Contains the credentials to authenticate a consumer to the service. This should be the OAuth2 Bearer Token.

Back to Top

Response

Supported Media Types

* application/fhir+json

Default Response

This operation supports the authorization type.

System

Example Request:

```
GET https://fhir-ehr.cerner.com/r4/ec2458f2-1e24-41c8-b71b-0e701af7583d/bulk-export/jobs/<Job_ID>
```

Example Response:

```
Status: 202 Accepted
X-Progress: in-progress
Retry-After: 600
```

Headers

* Retry-After: integer A number representing the number of seconds the client should wait before polling this endpoint again.

* X-Progress: string Indicates the status of the export. Possible values are in-progress and completed.

* X-Request-Id: string Unique Oracle-assigned identifier for the request. If you need to contact Oracle about a particular request, provide the X-Request-Id, if present.

* opc-request-id: string Unique Oracle-assigned identifier for the request. If you need to contact Oracle about a particular request, provide the opc-request-id, if present.

x-complete Response

This operation supports the authorization type.

System

Example Request:

```
GET https://fhir-ehr.cerner.com/r4/ec2458f2-1e24-41c8-b71b-0e701af7583d/bulk-export/jobs/<Job_ID>
```

Example Response:

```
Status: 200 OK
Expires: Mon, 22 Jul 2025 23:59:59 GMT
Content-Type: application/json
```

```
{
  "transactionTime": "2022-01-04T17:42:25.000Z",
  "request": "https://fhir-ehr.cerner.com/r4/ec2458f2-1e24-41c8-b71b-0e701af7583d/Group/252a42c0-5844-11ec-
    bf63-0242ac130002/$export?_type=Patient,Observation",
  "requiresAccessToken": true,
  "output": [
    {
      "type": "Patient",
      "url": "https://fhir-ehr.cerner.com/r4/ec2458f2-1e24-41c8-b71b-0e701af7583d/bulk-export/files/96295b8c-584e-11ec-
    bf63-0242ac130002"
    },
    {
      "type": "Patient",
      "url": "https://fhir-ehr.cerner.com/r4/ec2458f2-1e24-41c8-b71b-0e701af7583d/bulk-export/files/96295b8c-584e-11ec-
    bf63-0242ac130003"
    },
    {
      "type": "Observation",
      "url": "https://fhir-ehr.cerner.com/r4/ec2458f2-1e24-41c8-b71b-0e701af7583d/bulk-export/files/96295b8c-584e-11ec-
    bf63-0242ac130004"
    }
  ],
  "error": [
    {
      "type": "OperationOutcome",
      "url": "https://fhir-ehr.cerner.com/r4/ec2458f2-1e24-41c8-b71b-0e701af7583d/bulk-export/files/96295b8c-584e-11ec-
    bf63-0242ac130005"
    }
  ]
}
```

Headers

* Content-Type: string Indicates the media type of the response body.

* Expires: string Specifies when the exported files will become expired.

* X-Request-Id: string Unique Oracle-assigned identifier for the request. If you need to contact Oracle about a particular request, provide the X-Request-Id, if present.

* opc-request-id: string Unique Oracle-assigned identifier for the request. If you need to contact Oracle about a particular request, provide the opc-request-id, if present.

Back to Top

Kick off a bulk export request for a group of patients

File: bulk-data-v10/op-group-group_id-export-get.html

The operation is defined at:

```
GET https://fhir-ehr.cerner.com/r4/OperationDefinition/group-export?_format=json
```

Note:

* Bulk data export requests do not currently recognize the Accept-Language header; en-US is used instead.

* Only one bulk export request for a client application and tenant combination may be in-progress at a single time.

* The authorization token does not require the Group.read scope.

* The authorization token must contain system read scopes for all resources requested in the _type parameter.

* The following experimental parameters are not supported: _elements and patient.

Provenance Behavior

* Provenances for the Location, Organization, and Practitioner resources cannot be exported.

* When the _type parameter is not provided and the authorization token includes the Provenance read scope, all relevant Provenance resources associated with each of the non-Provenance resources are exported by default. You may use the includeAssociatedData parameter to export only the latest provenance.

* When the _type parameter is provided with specific resources and includes Provenance, all relevant Provenance resources associated with each of the non-Provenance resources are exported by default.

* When both the includeAssociatedData parameter and the _type parameter are provided, the _type parameter must include Provenance.

Optional Header

When the Prefer: handling=lenient header is provided, any unknown or unsupported parameters are ignored as specified in the Bulk Data Export query parameters.

Request

Path Parameters

* Group_ID(required): string The logical resource ID.

Query Parameters

* _outputFormat: string The format for the requested bulk data files to be generated. Valid parameters are application/fhir+ndjson, application/ndjson, and ndjson. Defaults to application/fhir+ndjson when not provided. Example: _outputFormat=application/ndjson

* _since: string Resources updated after this time are included in the response. Example: 2021-03-18T19:19:42.000Z

_type: string

A string of comma-delimited FHIR resource types. Example:

* The following values are valid:

* AllergyIntolerance

* CarePlan

* CareTeam

* Condition

* Coverage

* Device

* DiagnosticReport

* DocumentReference

* Encounter

* Goal

* Immunization

* Location

* MedicationDispense

* MedicationRequest

* Patient

* Procedure

* Observation

* Organization

* Practitioner

* Provenance

* RelatedPerson

* ServiceRequest

* Specimen

* When the parameter contains a reference resource (, , , , or) or an associated resource (), at least one of the following resources must also be provided:

_type

Location

Organization

Practitioner

RelatedPerson

Specimen

Provenance

* AllergyIntolerance

* CarePlan
* CareTeam
* Condition
* Coverage
* Device
* DiagnosticReport
* DocumentReference
* Encounter
* Goal
* Immunization
* MedicationDispense
* MedicationRequest
* Observation
* Patient
* Procedure
* ServiceRequest
* When the _type parameter is not provided, the resources to be exported are determined by the scopes provided in the authorization token.

_type=Patient,Encounter,Location

_typeFilter: string

A string of comma-delimited FHIR REST queries provided in combination with . Example:

_type

* When the _typeFilter parameter is provided, the _type parameter must be provided and must only have queries for the resources provided in _type.
* does not support queries for the following resources:

_typeFilter

* Location
* Organization
* Patient
* Practitioner
* Provenance
* RelatedPerson
* Specimen
* supports queries with the search parameters supported for the resources with the exception of the following search parameters:

_typeFilter

* _count
* _contained
* _containedType
* _elements
* _id
* _include
* _lastUpdated
* _revinclude
* _sort
* _summary
* _total
* encounter
* identifier
* patient
* subject
* date
* Supplying _typeFilter with the same resource multiple times is not supported.

_typeFilter=Condition?clinical-status=active,Encounter?status=planned

* includeAssociatedData: string When provided, the group export returns or omits a predefined set of FHIR resources associated with the request. A string of comma-delimited values. Valid parameters are LatestProvenanceResources and RelevantProvenanceResources. Example: includeAssociatedData=LatestProvenanceResources

Header Parameters

Accept(required): string

The media type to be requested. Refer to what the resource's operation produces for what is supported.

Example: application/fhir+json

* Authorization(required): string Contains the credentials to authenticate a consumer to the service. This should be the OAuth2 Bearer Token.

* Prefer(required): string Specifies whether the response is immediate or asynchronous. respond-async is supported. A client must provide this header.

Back to Top

Response

Supported Media Types

* application/fhir+json

Default Response

This operation supports the authorization type.

System

Example Request:

```
GET https://fhir-
    ehr.cerner.com/r4/ec2458f2-1e24-41c8-b71b-0e701af7583d/Group/11ec-d16a-c763b73e-98e8-a31715e6a2bf/$export
```

Example Response:

```
Status: 202 Accepted
Content-Location: https://fhir-ehr.cerner.com/r4/ec2458f2-1e24-41c8-b71b-0e701af7583d/bulk-export/jobs/<Job_ID>
```

Headers

* Content-Location: string Indicates the url to access the status of the export request.

* X-Request-Id: string Unique Oracle-assigned identifier for the request. If you need to contact Oracle about a particular request, provide the X-Request-Id, if present.

* opc-request-id: string Unique Oracle-assigned identifier for the request. If you need to contact Oracle about a particular request, provide the opc-request-id, if present.

Back to Top

Kick off a bulk export request for the provided list of patients

File: bulk-data-v10/op-patient-export-post.html

The operation is defined at:

```
GET https://fhir-ehr.cerner.com/r4/OperationDefinition/patient-export?_format=json
```

Note:

* With the current implementation, the patient parameter must be provided at least once.

* Bulk data export requests do not currently recognize the Accept-Language header; en-US is used instead.

* Only one bulk export request for a client application and tenant combination may be in-progress at a single time.

* The authorization token must contain system read scopes for all resources requested in the _type parameter.

* The experimental _elements parameter is not supported.

Provenance Behavior

* Provenances for the Location, Organization, and Practitioner resources cannot be exported.

* When the _type parameter is not provided and the authorization token includes the Provenance read scope, all relevant Provenance resources associated with each of the non-Provenance resources are exported by default. You may use the includeAssociatedData parameter to export only the latest provenance.

* When the _type parameter is provided with specific resources and includes Provenance, all relevant Provenance resources associated with each of the non-Provenance resources are exported by default.

* When both the includeAssociatedData parameter and the _type parameter are provided, the _type parameter must include Provenance.

Optional Header

When the Prefer: handling=lenient header is provided, any unknown or unsupported parameters are ignored as specified in the Bulk Data Export parameters.

Request

Header Parameters

Accept(required): string

The media type to be requested. Refer to what the resource's operation produces for what is supported.

Example: application/fhir+json

* Authorization(required): string Contains the credentials to authenticate a consumer to the service. This should be the OAuth2 Bearer Token.

* Content-Type(required): string Specifies the content type of the request entity body. Accepted values are application/fhir+json, application/json+fhir, and application/json.

* Prefer(required): string Specifies whether the response is immediate or asynchronous. respond-async is supported. A client must provide this header.

Body ()

The body of the patient export operation.

Root Schema : PatientExport

Type:

object

A summary representation of the patient export (POST) operation.

Show Source

parameter(required): array

parameter

Parameters supported by the operation.

* The patient parameter is required and must be provided at least once.

* The _type, _typeFilter, includeAssociatedData, _since, and _outputFormat parameters are optional and may be provided in the request body.

Details of the supported parameters:

* :

patient

* A maximum of 20,000 values may be provided for patient.

* When the parameter name is patient, the parameter value must be in the form of valueReference.

* :

_type

* A string of comma-delimited FHIR resource types.

* When the parameter name is _type, the parameter value must be in the form of valueString.

* The following values are valid:

* AllergyIntolerance

* CarePlan

* CareTeam

* Condition

* Coverage

* Device

* DiagnosticReport

* DocumentReference

* Encounter

* Goal

* Immunization

* Location

* MedicationDispense

* MedicationRequest

* Patient

* Procedure

* Observation

* Organization

* Practitioner

* Provenance
* RelatedPerson
* ServiceRequest
* Specimen
* When the parameter contains a reference resource (, , , , or) or an associated resource (), at least one of the following resources must also be provided:
_type
Location
Organization
Practitioner
RelatedPerson
Specimen
Provenance
* AllergyIntolerance
* CarePlan
* CareTeam
* Condition
* Coverage
* Device
* DiagnosticReport
* DocumentReference
* Encounter
* Goal
* Immunization
* MedicationDispense
* MedicationRequest
* Observation
* Patient
* Procedure
* ServiceRequest
* When the _type parameter is not provided, the resources to be exported are determined by the scopes provided in the authorization token.
* Example: Condition, Provenance
* :
_typeFilter
* A string of comma-delimited FHIR REST queries provided in combination with _type.
* When the parameter name is _typeFilter, the parameter value must be in the form of valueString.
* When the _typeFilter parameter is provided, the _type parameter must be provided and must only have queries for the resources provided in _type.
* does not support queries for the following resources:
_typeFilter
* Location
* Organization
* Patient
* Practitioner
* Provenance
* RelatedPerson
* Specimen
* supports queries with the search parameters supported for the resources with the exception of the following search parameters:
_typeFilter
* _count
* _contained

* _containedType
* _elements
* _id
* _include
* _lastUpdated
* _revinclude
* _sort
* _summary
* _total
* encounter
* identifier
* patient
* subject
* date
* Supplying _typeFilter with the same resource multiple times is not supported.
* Example: Condition?clinical-status=active,Encounter?status=planned
* :

includeAssociatedData

* When the parameter name is includeAssociatedData, the parameter value must be in the form of valueCode.
* When provided, the patient export returns or omits a predefined set of FHIR resources associated with the request.
* A string of comma-delimited values. Valid values are LatestProvenanceResources and RelevantProvenanceResources.
* :

_since

* Resources updated after this time are included in the response.
* When the parameter name is _since, the parameter value must be in the form of valueInstant.
* Example: 2021-03-18T19:19:42.000Z
* :

_outputFormat

* The format for the requested bulk data files to be generated.
* When the parameter name is _outputFormat, the parameter value must be in the form of valueString.
* Valid values are application/fhir+ndjson, application/ndjson, and ndjson.
* Defaults to application/fhir+ndjson when not provided.

```
{
  "parameter": [
    {
      "name": "patient",
      "valueReference": { "reference": "Patient/12783127" }
    },
    {
      "name": "patient",
      "valueReference": { "reference": "Patient/12783128" }
    },
    {
      "name": "patient",
      "valueReference": { "reference": "Patient/12783129" }
    },
    {
      "name": "_type",
      "valueString": "Condition,Provenance"
    },
    {
      "name": "_typeFilter",
      "valueString": "Condition?category=problem-list-item"
    },
    {
      "name": "includeAssociatedData",
      "valueCode": "RelevantProvenanceResources"
    },
    {
      "name": "_since",
      "valueInstant": "2021-03-18T19:19:42.000Z"
    },
    {
      "name": "_outputFormat",
      "valueString": "application/fhir+ndjson"
    }
  ]
```

```
}
```

resourceType(required): string

Allowed Values:

["Parameters"]

The type of the FHIR resource.

```
{
  "resourceType": "Parameters",
}
{
    "description":"A summary representation of the patient export (POST) operation.",
    "type":"object",
    "required":[
        "resourceType",
        "parameter"
    ],
    "properties":{
        "resourceType":{
            "description":"<p>The type of the FHIR resource.</p>\n<pre>\n<code>{\n  \"resourceType\":
    \"Parameters\",\n}</code>\n</pre>\n",
            "type":"string",
            "enum":[
                "Parameters"
            ]
        },
        "parameter":{
            "description":"<p>Parameters supported by the operation.</p>\n<ul>\n  <li>The <code>patient</code> parameter
     is required and must be provided at least once.</li>\n  <li>The <code>_type</code>, <code>_typeFilter</code>,
    <code>includeAssociatedData</code>, <code>_since</code>, and <code>_outputFormat</code> parameters are optional and
    may be provided in the request body.</li>\n</ul>\n<p>Details of the supported parameters:\n  <ul>\n
    <li><code>patient</code>:\n      <ul>\n        <li>A maximum of 20,000 values may be provided for
    <code>patient</code>.</li>\n        <li>When the parameter name is <code>patient</code>, the parameter value must be
     in the form of <code>valueReference</code>.</li>\n      </ul>\n    </li>\n    <li><code>_type</code>:\n      <ul>\n
            <li>A string of comma-delimited FHIR resource types.</li>\n        <li> When the parameter name is
    <code>_type</code>, the parameter value must be in the form of <code>valueString</code>.</li>\n        <li>The
    following values are valid:</li>\n          <ul>\n            <li><code>AllergyIntolerance</code></li>\n
    <li><code>CarePlan</code></li>\n            <li><code>CareTeam</code></li>\n
    <li><code>Condition</code></li>\n            <li><code>Coverage</code></li>\n
    <li><code>Device</code></li>\n           <li><code>DiagnosticReport</code></li>\n
    <li><code>DocumentReference</code></li>\n            <li><code>Encounter</code></li>\n
    <li><code>Goal</code></li>\n            <li><code>Immunization</code></li> \n
    <li><code>Location</code></li>\n            <li><code>MedicationDispense</code></li>\n
    <li><code>MedicationRequest</code></li>\n            <li><code>Patient</code></li>\n
    <li><code>Procedure</code></li>\n            <li><code>Observation</code></li>\n
    <li><code>Organization</code></li>\n            <li><code>Practitioner</code></li>\n
    <li><code>Provenance</code></li>\n            <li><code>RelatedPerson</code></li>\n
    <li><code>ServiceRequest</code></li>\n            <li><code>Specimen</code></li>\n          </ul>\n        <li>When
    the <code>_type</code> parameter contains a reference resource (<code>Location</code>, <code>Organization</code>,
    <code>Practitioner</code>, <code>RelatedPerson</code>, or <code>Specimen</code>) or an associated resource
    (<code>Provenance</code>), at least one of the following resources must also be provided: \n          <ul>\n
              <li><code>AllergyIntolerance</code></li>\n            <li><code>CarePlan</code></li>\n
    <li><code>CareTeam</code></li>\n            <li><code>Condition</code></li>\n
    <li><code>Coverage</code></li>\n            <li><code>Device</code></li>\n
    <li><code>DiagnosticReport</code></li>\n            <li><code>DocumentReference</code></li>\n
    <li><code>Encounter</code></li>\n            <li><code>Goal</code></li>\n
    <li><code>Immunization</code></li>\n            <li><code>MedicationDispense</code></li>\n
    <li><code>MedicationRequest</code></li>\n            <li><code>Observation</code></li>\n
    <li><code>Patient</code></li>\n           <li><code>Procedure</code></li>\n
    <li><code>ServiceRequest</code></li>\n          </ul>\n        <li>When the <code>_type</code> parameter is not
    provided, the resources to be exported are determined by the scopes provided in the authorization token.</li>\n
            <li>Example: <code>Condition, Provenance</code></li>\n      </ul>\n    </li>\n
    <li><code>_typeFilter</code>:\n      <ul>\n        <li>A string of comma-delimited FHIR REST queries provided in
    combination with <code>_type</code>.</li>\n        <li>When the parameter name is <code>_typeFilter</code>, the
    parameter value must be in the form of <code>valueString</code>.</li>\n        <li>When the <code>_typeFilter</code>
     parameter is provided, the <code>_type</code> parameter must be provided and must only have queries for the
    resources provided in <code>_type</code>.</li>\n        <li><code>_typeFilter</code> does not support queries for
    the following resources: \n          <ul>\n            <li><code>Location</code></li>\n
    <li><code>Organization</code></li>\n            <li><code>Patient</code></li>\n
    <li><code>Practitioner</code></li>\n            <li><code>Provenance</code></li>\n
    <li><code>RelatedPerson</code></li>\n           <li><code>Specimen</code></li>\n          </ul>\n
    <li><code>_typeFilter</code> supports queries with the search parameters supported for the <a
    href=\"https://docs.oracle.com/en/industries/health/millennium-platform-apis/mfrap/resource_info.html\">R4</a>
    resources with the exception of the following search parameters:\n          <ul>\n
    <li><code>_count</code></li>\n            <li><code>_contained</code></li>\n
    <li><code>_containedType</code></li>\n            <li><code>_elements</code></li>\n
    <li><code>_id</code></li>\n           <li><code>_include</code></li>\n
    <li><code>_lastUpdated</code></li>\n            <li><code>_revinclude</code></li>\n
    <li><code>_sort</code></li>\n           <li><code>_summary</code></li>\n            <li><code>_total</code></li>\n
              <li><code>encounter</code></li>\n            <li><code>identifier</code></li>\n
    <li><code>patient</code></li>\n           <li><code>subject</code></li>\n            <li><code>date</code></li>\n
             </ul>\n        <li>Supplying <code>_typeFilter</code> with the same resource multiple times is not
    supported.</li>\n        <li>Example: <code>Condition?clinical-status=active,Encounter?status=planned</code></li>\n
          </ul>\n    </li>\n    <li><code>includeAssociatedData</code>:\n      <ul>\n        <li>When the parameter name
     is <code>includeAssociatedData</code>, the parameter value must be in the form of <code>valueCode</code>.</li>\n
            <li>When provided, the patient export returns or omits a predefined set of FHIR resources associated with
    the request.</li>\n        <li>A string of comma-delimited values. Valid values are
```

```
    <code>LatestProvenanceResources</code> and <code>RelevantProvenanceResources</code>.</li>\n      </ul>\n    </li>\n
        <li><code>_since</code>:\n      <ul>\n        <li>Resources updated after this time are included in the
    response.</li>\n        <li>When the parameter name is <code>_since</code>, the parameter value must be in the form
    of <code>valueInstant</code>.</li>\n        <li>Example: <code>2021-03-18T19:19:42.000Z</code></li>\n      </ul>\n
        </li>\n    <li><code>_outputFormat</code>:\n      <ul>\n        <li>The format for the requested bulk data files
     to be generated.</li>\n        <li>When the parameter name is <code>_outputFormat</code>, the parameter value must
    be in the form of <code>valueString</code>.</li>\n        <li>Valid values are <code>application/fhir+ndjson</code>,
     <code>application/ndjson</code>, and <code>ndjson</code>.</li>\n        <li>Defaults to
    <code>application/fhir+ndjson</code> when not provided.</li>\n      </ul>\n    </li>\n
    </ul>\n</p>\n\n<pre>\n<code>{\n  \"parameter\": [\n    {\n      \"name\": \"patient\",\n      \"valueReference\": {
    \"reference\": \"Patient/12783127\" }\n    },\n    {\n      \"name\": \"patient\",\n      \"valueReference\": {
    \"reference\": \"Patient/12783128\" }\n    },\n    {\n      \"name\": \"patient\",\n      \"valueReference\": {
    \"reference\": \"Patient/12783129\" }\n    },\n    {\n      \"name\": \"_type\",\n      \"valueString\":
    \"Condition,Provenance\"\n    },\n    {\n      \"name\": \"_typeFilter\",\n      \"valueString\":
    \"Condition?category=problem-list-item\"\n    },\n    {\n      \"name\": \"includeAssociatedData\",\n
    \"valueCode\": \"RelevantProvenanceResources\"\n    },\n    {\n      \"name\": \"_since\",\n      \"valueInstant\":
    \"2021-03-18T19:19:42.000Z\"\n    },\n    {\n      \"name\": \"_outputFormat\",\n      \"valueString\":
    \"application/fhir+ndjson\"\n    }\n  ]\n}</code>\n</pre>\n",
            "type":"array",
            "items":{
                "type":"object",
                "properties":{
                    "name":{
                        "description":"The name of the parameter\n",
                        "type":"string"
                    },
                    "value[x]":{
                        "description":"The value of the parameter\n",
                        "type":"string"
                    }
                }
            }
        }
    }
}
```


Nested Schema : parameter

Type:

array

Parameters supported by the operation.

* The patient parameter is required and must be provided at least once.

* The _type, _typeFilter, includeAssociatedData, _since, and _outputFormat parameters are optional and may be provided in the request body.

Details of the supported parameters:

* :

patient

* A maximum of 20,000 values may be provided for patient.

* When the parameter name is patient, the parameter value must be in the form of valueReference.

* :

_type

* A string of comma-delimited FHIR resource types.

* When the parameter name is _type, the parameter value must be in the form of valueString.

* The following values are valid:

* AllergyIntolerance

* CarePlan

* CareTeam

* Condition

* Coverage

* Device

* DiagnosticReport

* DocumentReference

* Encounter

* Goal

* Immunization

* Location

* MedicationDispense

* MedicationRequest

* Patient

* Procedure
* Observation
* Organization
* Practitioner
* Provenance
* RelatedPerson
* ServiceRequest
* Specimen
* When the parameter contains a reference resource (, , , , or) or an associated resource (), at least one of the following resources must also be provided:
_type
Location
Organization
Practitioner
RelatedPerson
Specimen
Provenance
* AllergyIntolerance
* CarePlan
* CareTeam
* Condition
* Coverage
* Device
* DiagnosticReport
* DocumentReference
* Encounter
* Goal
* Immunization
* MedicationDispense
* MedicationRequest
* Observation
* Patient
* Procedure
* ServiceRequest
* When the _type parameter is not provided, the resources to be exported are determined by the scopes provided in the authorization token.
* Example: Condition, Provenance
* :
_typeFilter
* A string of comma-delimited FHIR REST queries provided in combination with _type.
* When the parameter name is _typeFilter, the parameter value must be in the form of valueString.
* When the _typeFilter parameter is provided, the _type parameter must be provided and must only have queries for the resources provided in _type.
* does not support queries for the following resources:
_typeFilter
* Location
* Organization
* Patient
* Practitioner
* Provenance
* RelatedPerson
* Specimen

* supports queries with the search parameters supported for the resources with the exception of the following search parameters:

_typeFilter

* _count
* _contained
* _containedType
* _elements
* _id
* _include
* _lastUpdated
* _revinclude
* _sort
* _summary
* _total
* encounter
* identifier
* patient
* subject
* date
* Supplying _typeFilter with the same resource multiple times is not supported.
* Example: Condition?clinical-status=active,Encounter?status=planned
* :

includeAssociatedData

* When the parameter name is includeAssociatedData, the parameter value must be in the form of valueCode.
* When provided, the patient export returns or omits a predefined set of FHIR resources associated with the request.
* A string of comma-delimited values. Valid values are LatestProvenanceResources and RelevantProvenanceResources.
* :

_since

* Resources updated after this time are included in the response.
* When the parameter name is _since, the parameter value must be in the form of valueInstant.
* Example: 2021-03-18T19:19:42.000Z
* :

_outputFormat

* The format for the requested bulk data files to be generated.
* When the parameter name is _outputFormat, the parameter value must be in the form of valueString.
* Valid values are application/fhir+ndjson, application/ndjson, and ndjson.
* Defaults to application/fhir+ndjson when not provided.


```
{
  "parameter": [
    {
      "name": "patient",
      "valueReference": { "reference": "Patient/12783127" }
    },
    {
      "name": "patient",
      "valueReference": { "reference": "Patient/12783128" }
    },
    {
      "name": "patient",
      "valueReference": { "reference": "Patient/12783129" }
    },
    {
      "name": "_type",
      "valueString": "Condition,Provenance"
    },
    {
      "name": "_typeFilter",
      "valueString": "Condition?category=problem-list-item"
    },
    {
      "name": "includeAssociatedData",
      "valueCode": "RelevantProvenanceResources"
    },
```

```
    {
      "name": "_since",
      "valueInstant": "2021-03-18T19:19:42.000Z"
    },
    {
      "name": "_outputFormat",
      "valueString": "application/fhir+ndjson"
    }
  ]
}
```


Show Source

* Array of: object items


```
{
    "description":"<p>Parameters supported by the operation.</p>\n<ul>\n  <li>The <code>patient</code> parameter is
    required and must be provided at least once.</li>\n  <li>The <code>_type</code>, <code>_typeFilter</code>,
    <code>includeAssociatedData</code>, <code>_since</code>, and <code>_outputFormat</code> parameters are optional and
    may be provided in the request body.</li>\n</ul>\n<p>Details of the supported parameters:\n  <ul>\n
    <li><code>patient</code>:\n      <ul>\n        <li>A maximum of 20,000 values may be provided for
    <code>patient</code>.</li>\n        <li>When the parameter name is <code>patient</code>, the parameter value must be
     in the form of <code>valueReference</code>.</li>\n      </ul>\n    </li>\n    <li><code>_type</code>:\n      <ul>\n
           <li>A string of comma-delimited FHIR resource types.</li>\n        <li> When the parameter name is
    <code>_type</code>, the parameter value must be in the form of <code>valueString</code>.</li>\n        <li>The
    following values are valid:</li>\n          <ul>\n            <li><code>AllergyIntolerance</code></li>\n
    <li><code>CarePlan</code></li>\n            <li><code>CareTeam</code></li>\n
    <li><code>Condition</code></li>\n            <li><code>Coverage</code></li>\n
    <li><code>Device</code></li>\n            <li><code>DiagnosticReport</code></li>\n
    <li><code>DocumentReference</code></li>\n            <li><code>Encounter</code></li>\n
    <li><code>Goal</code></li>\n            <li><code>Immunization</code></li> \n
    <li><code>Location</code></li>\n            <li><code>MedicationDispense</code></li>\n
    <li><code>MedicationRequest</code></li>\n            <li><code>Patient</code></li>\n
    <li><code>Procedure</code></li>\n            <li><code>Observation</code></li>\n
    <li><code>Organization</code></li>\n            <li><code>Practitioner</code></li>\n
    <li><code>Provenance</code></li>\n            <li><code>RelatedPerson</code></li>\n
    <li><code>ServiceRequest</code></li>\n            <li><code>Specimen</code></li>\n          </ul>\n        <li>When
    the <code>_type</code> parameter contains a reference resource (<code>Location</code>, <code>Organization</code>,
    <code>Practitioner</code>, <code>RelatedPerson</code>, or <code>Specimen</code>) or an associated resource
    (<code>Provenance</code>), at least one of the following resources must also be provided: \n          <ul>\n
              <li><code>AllergyIntolerance</code></li>\n            <li><code>CarePlan</code></li>\n
    <li><code>CareTeam</code></li>\n            <li><code>Condition</code></li>\n
    <li><code>Coverage</code></li>\n            <li><code>Device</code></li>\n
    <li><code>DiagnosticReport</code></li>\n            <li><code>DocumentReference</code></li>\n
    <li><code>Encounter</code></li>\n            <li><code>Goal</code></li>\n
    <li><code>Immunization</code></li>\n            <li><code>MedicationDispense</code></li>\n
    <li><code>MedicationRequest</code></li>\n            <li><code>Observation</code></li>\n
    <li><code>Patient</code></li>\n            <li><code>Procedure</code></li>\n
    <li><code>ServiceRequest</code></li>\n          </ul>\n        <li>When the <code>_type</code> parameter is not
    provided, the resources to be exported are determined by the scopes provided in the authorization token.</li>\n
           <li>Example: <code>Condition, Provenance</code></li>\n      </ul>\n    </li>\n
    <li><code>_typeFilter</code>:\n      <ul>\n        <li>A string of comma-delimited FHIR REST queries provided in
    combination with <code>_type</code>.</li>\n        <li>When the parameter name is <code>_typeFilter</code>, the
    parameter value must be in the form of <code>valueString</code>.</li>\n        <li>When the <code>_typeFilter</code>
     parameter is provided, the <code>_type</code> parameter must be provided and must only have queries for the
    resources provided in <code>_type</code>.</li>\n        <li><code>_typeFilter</code> does not support queries for
    the following resources: \n          <ul>\n            <li><code>Location</code></li>\n
    <li><code>Organization</code></li>\n            <li><code>Patient</code></li>\n
    <li><code>Practitioner</code></li>\n            <li><code>Provenance</code></li>\n
    <li><code>RelatedPerson</code></li>\n            <li><code>Specimen</code></li>\n          </ul>\n
    <li><code>_typeFilter</code> supports queries with the search parameters supported for the <a
    href=\"https://docs.oracle.com/en/industries/health/millennium-platform-apis/mfrap/resource_info.html\">R4</a>
    resources with the exception of the following search parameters:\n          <ul>\n
    <li><code>_count</code></li>\n            <li><code>_contained</code></li>\n
    <li><code>_containedType</code></li>\n            <li><code>_elements</code></li>\n
    <li><code>_id</code></li>\n            <li><code>_include</code></li>\n
    <li><code>_lastUpdated</code></li>\n            <li><code>_revinclude</code></li>\n
    <li><code>_sort</code></li>\n            <li><code>_summary</code></li>\n            <li><code>_total</code></li>\n
            <li><code>encounter</code></li>\n            <li><code>identifier</code></li>\n
    <li><code>patient</code></li>\n            <li><code>subject</code></li>\n            <li><code>date</code></li>\n
          </ul>\n        <li>Supplying <code>_typeFilter</code> with the same resource multiple times is not
    supported.</li>\n        <li>Example: <code>Condition?clinical-status=active,Encounter?status=planned</code></li>\n
          </ul>\n    </li>\n    <li><code>includeAssociatedData</code>:\n      <ul>\n        <li>When the parameter name
     is <code>includeAssociatedData</code>, the parameter value must be in the form of <code>valueCode</code>.</li>\n
           <li>When provided, the patient export returns or omits a predefined set of FHIR resources associated with
    the request.</li>\n        <li>A string of comma-delimited values. Valid values are
    <code>LatestProvenanceResources</code> and <code>RelevantProvenanceResources</code>.</li>\n      </ul>\n    </li>\n
        <li><code>_since</code>:\n      <ul>\n        <li>Resources updated after this time are included in the
    response.</li>\n        <li>When the parameter name is <code>_since</code>, the parameter value must be in the form
    of <code>valueInstant</code>.</li>\n        <li>Example: <code>2021-03-18T19:19:42.000Z</code></li>\n      </ul>\n
        </li>\n    <li><code>_outputFormat</code>:\n      <ul>\n        <li>The format for the requested bulk data files
     to be generated.</li>\n        <li>When the parameter name is <code>_outputFormat</code>, the parameter value must
    be in the form of <code>valueString</code>.</li>\n        <li>Valid values are <code>application/fhir+ndjson</code>,
     <code>application/ndjson</code>, and <code>ndjson</code>.</li>\n        <li>Defaults to
    <code>application/fhir+ndjson</code> when not provided.</li>\n      </ul>\n    </li>\n
    </ul>\n</p>\n\n<pre>\n<code>{\n  \"parameter\": [\n    {\n      \"name\": \"patient\",\n      \"valueReference\": {
    \"reference\": \"Patient/12783127\" }\n    },\n    {\n      \"name\": \"patient\",\n      \"valueReference\": {
    \"reference\": \"Patient/12783128\" }\n    },\n    {\n      \"name\": \"patient\",\n      \"valueReference\": {
    \"reference\": \"Patient/12783129\" }\n    },\n    {\n      \"name\": \"_type\",\n      \"valueString\":
    \"Condition,Provenance\"\n    },\n    {\n      \"name\": \"_typeFilter\",\n      \"valueString\":
```

```
    \"Condition?category=problem-list-item\"\n    },\n    {\n      \"name\": \"includeAssociatedData\",\n
    \"valueCode\": \"RelevantProvenanceResources\"\n    },\n    {\n      \"name\": \"_since\",\n      \"valueInstant\":
    \"2021-03-18T19:19:42.000Z\"\n    },\n    {\n      \"name\": \"_outputFormat\",\n      \"valueString\":
    \"application/fhir+ndjson\"\n    }\n  ]\n}</code>\n</pre>\n",
    "type":"array",
    "items":{
        "type":"object",
        "properties":{
            "name":{
                "description":"The name of the parameter\n",
                "type":"string"
            },
            "value[x]":{
                "description":"The value of the parameter\n",
                "type":"string"
            }
        }
    }
}
```


Nested Schema : items

Type:

object

Show Source

* name: string The name of the parameter

* value[x]: string The value of the parameter


```
{
    "type":"object",
    "properties":{
        "name":{
            "description":"The name of the parameter\n",
            "type":"string"
        },
        "value[x]":{
            "description":"The value of the parameter\n",
            "type":"string"
        }
    }
}
```


Back to Top

Response

Supported Media Types

* application/fhir+json

Default Response

This operation supports the authorization type.

System

Example Request:

```
POST https://fhir-ehr.cerner.com/r4/ec2458f2-1e24-41c8-b71b-0e701af7583d/Patient/$export
```

Example Request Body:


```
{
  "resourceType": "Parameters",
  "parameter": [
    {
      "name": "patient",
      "valueReference": { "reference": "Patient/12783127" }
    },
    {
      "name": "patient",
      "valueReference": { "reference": "Patient/12783128" }
    },
    {
      "name": "patient",
      "valueReference": { "reference": "Patient/12783129" }
    },
    {
      "name": "_type",
      "valueString": "Condition,Provenance"
    },
    {
      "name": "_typeFilter",
      "valueString": "Condition?category=problem-list-item"
    },
    {
      "name": "includeAssociatedData",
      "valueCode": "RelevantProvenanceResources"
    },
    {
```

```
      "name": "_since",
      "valueInstant": "2021-03-18T19:19:42.000Z"
    },
    {
      "name": "_outputFormat",
      "valueString": "application/fhir+ndjson"
    }
  ]
}
```

Example Response:

```
Status: 202 Accepted
Content-Location: https://fhir-ehr.cerner.com/r4/ec2458f2-1e24-41c8-b71b-0e701af7583d/bulk-export/jobs/<Job_ID>
```

Headers

* Content-Location: string Indicates the url to access the status of the export request.

* X-Request-Id: string Unique Oracle-assigned identifier for the request. If you need to contact Oracle about a particular request, provide the X-Request-Id, if present.

* opc-request-id: string Unique Oracle-assigned identifier for the request. If you need to contact Oracle about a particular request, provide the opc-request-id, if present.

Back to Top