

01TXFSM - Machine Learning and Deep Learning

Final Project First Person Action Recognition

Eros Fani - s269781
Politecnico di Torino

eros.fani@studenti.polito.it

Gabriele Trivigno - s276807
Politecnico di Torino

gabriele.trivigno@studenti.polito.it

Cristiano Gerbino - s277058
Politecnico di Torino

s277058@studenti.polito.it

Abstract

1. Introduction and data exploration

The first goal of the project is to replicate some of the experiments performed in [2] and [1]. The objective of these studies is the First Person Action Recognition: they tried to implement a deep learning model capable to extract meaningful features to automatically predict the action filmed by a wearable camera.

The dataset under analysis is a modified version of GTEA61¹. The dataset contains the videos in form of frames, and also two kind of preprocessed images: *motion maps* and *optical flows*. The folder schema of the dataset is shown in Figure 1.

At last we have tried to improve the performances of the results of [2] and [1] with some innovative ideas.

The optical flow methods try to calculate the motion between two image frames which are taken at

times t and $t + \Delta t$ at every voxel position. The warp flow methods try also to remove the motion of the wearable camera. We have two kind of these last representations in our dataset: one computed in the horizontal axis (folder *flow_x_processed*) and one other computed in the vertical axis (folder *flow_y_processed*).

The motion maps are special black-and-white images which represent the spatial location in which the Motion Segmentation task of [1] focuses its attention per each frame. The mmaps present large similarities with the warp flows.

The difference between the kind of available images in our dataset are shown in Figure 2.

References

- [1] M. Planamente, A. Bottino, and B. Caputo. Joint encoding of appearance and motion features with self-supervision for first person action recognition, 2020.
- [2] S. Sudhakaran and O. Lanz. Attention is all we need: Nailing down object-centric attention for egocentric activity recognition, 2018.

¹Georgia Tech Egocentric Activity Datasets: <http://cbs.ic.gatech.edu/fpv/>




Figure 1: Folder schema of our GTEA61




Figure 2: Types of images in our dataset. In this example is shown a sample of images from the *close_chocolate* action. From the left column to the right column: rgbs, warp flows x, warp flows y, motion maps