

Project Name: IMAP Client

Technical Documentation

Author: Slabik Yaroslav

Login: xslabi01

Contents

1. *Introduction*
 2. *Assignment Description*
 3. *Application Design*
 - 3.1 *Program Architecture*
 - 3.2 *Code Structure*
 4. *Implementation Description*
 - 4.1 *Command Line Argument Parsing*
 - 4.2 *Establishing Server Connection*
 - 4.3 *User Authentication*
 - 4.4 *Mailbox Selection*
 - 4.5 *Downloading and Saving Messages*
 - 4.6 *Working with SSL/TLS Certificates*
 5. *User Manual*
 - 5.1 *Authentication File Format*
 - 5.2 *Examples of Program Execution*
 6. *Application Testing*
 - 6.1 *Description of Tests Performed*
 - 6.2 *Testing Results*
 7. *References*
-

1. Introduction

This documentation covers the **imapcl** IMAP client developed as part of the ISA course project at the Faculty of Information Technology, Brno University of Technology. The goal was to implement a client for the IMAP4rev1 protocol (RFC 3501), enabling email downloading from a specified server and saving messages to a designated directory.

2. Assignment Description

The **imapcl** program provides:

- Connection to a specified IMAP server using IMAP4rev1.
- User authentication with provided credentials.
- Downloading messages from a specified mailbox (default "INBOX") and saving them to a specified directory.
- Displaying the number of downloaded messages on standard output.
- Ability to set additional parameters to modify functionality (e.g., use of SSL/TLS, port selection, downloading only new messages, downloading only headers, etc.).

3. Application Design

3.1 Program Architecture

The program is designed modularly with emphasis on clarity and maintainability. Main components:

- **Command Line Argument Parser:** Processes input parameters and configures program behavior.
- **Network Module:** Establishes connection to the server and communicates using IMAP.
- **Authentication Module:** Logs the user into the server.
- **Message Processing Module:** Handles downloading, processing, and saving messages.
- **SSL/TLS Module:** Ensures secure server connection.

3.2 Code Structure

Code is divided into functions, each serving a specific purpose:

- **initialize_ssl, create_context, cleanup_ssl:** Functions for OpenSSL operations.
- **connect_to_server:** Connects to the server.
- **send_command, receive_response:** Communicates with the server using IMAP commands.
- **login, select_mailbox, fetch_messages:** Implements main IMAP functions.
- **read_credentials, directory_exists:** Helper functions for file and directory operations.
- **base64_encode, base64_decode, decode_encoded_word:** Functions for message encoding and decoding.

4. Implementation Description

4.1 Command Line Argument Parsing

The program uses the **getopt** library for parameter parsing:

- **server**: Server address (required).
- **-p port**: Port number (default 143 or 993 with TLS).
- **-T**: Use SSL/TLS.
- **-c certfile**: Certificate file for SSL/TLS verification.
- **-C certaddr**: Certificate directory (default "/etc/ssl/certs").
- **-n**: Download only new messages.
- **-h**: Download only message headers.
- **-a auth_file**: Authentication file (required).
- **-b MAILBOX**: Mailbox name (default "INBOX").
- **-o out_dir**: Output directory (required).

4.2 Establishing Server Connection

Function **connect_to_server**:

- Retrieves server info using **getaddrinfo**.
- Creates a socket and establishes a TCP connection.
- If TLS is used, initializes SSL context and establishes a secure connection.
- Verifies server certificate using OpenSSL.

4.3 User Authentication

Function **login**:

- Receives server's greeting.
- Determines supported authentication methods.
- Logs in using LOGIN or PLAIN method.

4.4 Mailbox Selection

Function **select_mailbox**:

- Sends **SELECT** command to choose the mailbox.
- Processes response to get the message count.

4.5 Downloading and Saving Messages

Function **fetch_messages**:

- Determines which messages to download.
- Sends **FETCH** commands to download messages or headers.
- Processes responses including literals.
- Saves messages to the specified directory with necessary processing.

4.6 Working with SSL/TLS Certificates

- Loads certificates from file or directory.
- Sets server certificate verification mode.
- Verifies the certificate after establishing SSL connection.

5. User Manual

5.1 Authentication File Format

The file must contain:

username = your_username
password = your_password

5.2 Examples of Program Execution

1. Download all messages without TLS:

./imapcl server -a auth.txt -o zpravy

2. Download new messages with TLS and certificate:

./imapcl server -T -c cert.pem -n -a auth.txt -o zpravy

3. Download message headers:

./imapcl server -h -a auth.txt -o hlavicky

6. Application Testing

6.1 Description of Tests Performed

- **Connection tests** with and without TLS.
- **Authentication tests** with valid and invalid credentials.
- **Downloading various types of messages.**
- **Certificate handling tests.**
- **Saving messages** to different directories.

6.2 Testing Results

- **Connection** succeeded with correct settings.
- **Authentication** was successful with valid credentials.
- **Message downloading** worked in all modes.
- **Certificates** were correctly handled.
- **Saving messages** succeeded to accessible directories.

7. References

1. **RFC 3501** - IMAP4rev1
2. **RFC 5322** - Internet Message Format
3. **OpenSSL Documentation**
4. **Standard C/C++ Libraries**