

How to crack archive password faster

by Milosz Galazka on May 25, 2015 and tagged with [Debian](#), [Jessie](#), [Command-line](#), [John the Ripper](#), [Software recommendation](#)

A week ago I wrote about couple of interesting applications to crack archive password, but they were not as fast as I thought. After investigating this topic further I ended up using community-enhanced version of [John the Ripper](#).

Requirements

Install packages required to compile source code.

```
$ sudo apt-get install build-essential libssl-dev
```

Compilation

Create temporary directory which will be used to compile source code.

```
$ mkdir temp
```

Change working directory.

```
$ cd temp
```

Download most recent community-enhanced version.

```
$ wget http://www.openwall.com/john/j/john-1.8.0-jumbo-1.tar.gz
```

Extract downloaded archive.

```
$ tar xzf john-1.8.0-jumbo-1.tar.gz
```

Change working directory.

```
$ cd john-1.8.0-jumbo-1/src/
```

Execute configuration script.

```
$ ./configure
```

Compile source code.

```
$ make -s
```

Compiled software is available in the *run* directory.

```
$ cd ../run
```

You can execute commands directly from that directory.

Simple installation

Create destination directory for application.

```
$ mkdir -p ~/apps/john
```

Copy application to the destination directory.

```
$ cp ~/temp/john-1.8.0-jumbo-1/run/* ~/apps/john/
```

You can execute commands directly from that directory.

```
$ cd ~/apps/john/ && ./john --test
```

Advanced installation

Pass `JOHN_SYSTEMWIDE` parameter in `CFLAGS` during configuration phase.

```
$ ./configure CFLAGS="-DJOHN_SYSTEMWIDE=1"
```

Create destination directory and copy application after compilation process.

```
$ mkdir -p ~/apps/john
```

```
$ cp ~/temp/john-1.8.0-jumbo-1/run/* ~/apps/john/
```

Create configuration directory and move configuration files.

```
$ mkdir ~/.john
```

```
$ mv ~/apps/john/*.conf ~/.john/  
$ mv ~/apps/john/password.lst ~/.john/  
$ mv ~/apps/john/*.chr ~/.john/
```

Alter configuration files to use shared location.

```
$ sed -i -e "s|\$JOHN|~/.john|" ~/.john/john.conf
```

```
$ sed -i -e "/.include/ s|<\(.*\)>|\"~/.john/\1\"|" ~/.john/*.conf
```

Extend `PATH` variable to include application directory.

```
$ echo "export PATH=\$PATH:~/apps/john" >> ~/.bashrc
```

You can use recently compiled utilities after you login again, alternatively evaluate `~/ .bashrc` file to expand `PATH` in current shell.

```
$ source ~/.bashrc
```

Usage

Use `zip2john` utility to get hashed password out of *zip* archive.

```
$ zip2john encrypted.zip > encrypted.hash$
```

Use `john` to crack password.

```
$ john --show encrypted.hash
encrypted.zip:@3ncPa5Sword@::::encrypted.zip

1 password hash cracked, 0 left
```

`rar2john` utility will work in the same way for *rar* archives.

Additional notes

There are other interesting utilities in community-enhanced version which you may like to examine.

```
~/apps/john$ ls -1 *2john
```

```
dmg2john
gpg2john
hccap2john
keepass2john
keychain2john
keyring2john
keystore2john
kwallet2john
```

- luks2john
- pfx2john
- putty2john
- pwsafe2john
- racf2john
- rar2john
- ssh2john
- truecrypt_volume2john
- uaf2john
- wpa2john
- zip2john

Use `strace` command in case of problems with the location of configuration files.

Post navigation

← [How to crack archive password](#) May 18, 2015
[How to lock Linux console session](#) June 1, 2015 →

Related Posts

[How to strace PHP-FPM processes](#) 14 Oct 2019

[How to count TCP connections](#) 07 Aug 2019

[How to generate sequence of numbers](#) 05 Aug 2019

[How to determine how long specified remote server or device was offline](#) 29 Jul 2019

[How to configure sysfs during system boot](#) 22 Jul 2019

sleeplessbeastie's notes

Personal notes about Linux, applications and programming.

[Home](#) [Archives](#) [Search](#) [Tags](#) [About](#)

Milosz Galazka

milosz (at) sleeplessbeastie (dot) eu

Updated on 2019-11-16

© 2019. All rights reserved.