



INTEGRATION MANUAL

The following document has been designed to make the disbursement API integration swift and easy, making sure possible case scenarios are covered with sample codes and guides.

Introduction

Make Your Transactions Quick and Easy. Experience fast, secure, and hassle-free payments with Assan Pay—designed to simplify your financial transactions anytime, anywhere.

Cross-Browser

Assan Pay ensures seamless performance across all major web browsers, providing a consistent and reliable user experience for everyone.

Amazing Features

Secure, fast, and user-friendly payment solutions—all in one platform.

Easy Payment

Simplify transactions with secure and hassle-free payments

Workflow Is What We Do

- **Trusted Company**
Reliable, secure, and committed to your payment needs.
- **Fast Support**
Quick and reliable assistance whenever you need it.
- **Fast Process**
Swift and seamless transactions every time.

- **Easy to Use**

Intuitive and simple payment solutions for everyone.

- **Take It Anywhere**

Access seamless payments on the go, anytime, anywhere.

Redirect User to Payment Page (Redirectional/Cashier Model)

POST **payment-request/qr/{merchantId}** Initiate a Payment Request

This API endpoint is used to initiate a payment request by generating a unique payment link. The client (merchant) sends the order details (amount, store name, and order ID), and the API responds with a manage-payments URL, which can be shared with users for completing the payment. This is ideal for generating dynamic links for customer payments.

Base URL

<https://api.assanpay.com>

Endpoint: Initiate a Payment Request

POST **payment-request/qr/{merchantId}**

Initiate a payment request by generating a unique payment link.

Full Example:

POST
<https://api.assanpay.com/payment-request/qr/{merchantId}>

Parameters

Parameter	Type	Required	Description
merchantId	<i>String</i>	<i>yes</i>	Unique Merchant ID

Request Body

Name	Type	Required	Description
amount	<i>String</i>	<i>yes</i>	Payment amount (natural numbers or float with two decimal number)
order_id	<i>String</i>	<i>optional</i>	Unique order reference for tracking
store_name	<i>String</i>	<i>yes</i>	Name of the storemaking the payment request.
link	<i>String</i>	<i>optional</i>	URL to redirect afterpayment (success/failure)

Example

```
{  
  
  "amount": "10",  
  
  "order_id": "12340", // must be unique  
  
  "store_name": "Your store"  
  
  "link": "google.com"  
}
```

Responses

Code	Description	Links
200	Payment Request created successfully	No Links
500	Internal Server Error(Error for Required fields)	No Links
500	Internal Server Error(Unique constraint failed on the fields:Tried to	No Links

	insert a duplicate transactionId into the database)	
--	---	--

Successful Response:

```
{
  "status": "true",
  "message": "Payment request created successfully",
  "data": {
    "id": "ddc6b617-3126-4866-9782-c68f535034b6",
    "transactionId": "T202512181151100kr4f",
    "amount": "10",
    "description": "null",
    "dueDate": "null",
    "status": "pending",
    "link": "/pay/ddc6b617-3126-4866-9782-c68f535034b6",
    "metadata": {
      "return_url": "yourUrl.com"
    },
    "provider": "null",
    "userId": "5",
    "createdAt": "2025-12-18T06:51:10.839Z",
    "updatedAt": "2025-12-18T06:51:10.848Z",
    "deletedAt": "null",
    "merchant_transaction_id": "12340",
    "completeLink": "https://merchant.assanpay.com/aik-qr/ddc6b617-3126-4866-9782-c68f535034b6",
    "order_id": "12340"
  },
}
```

Note:

You should focus on the completeLink parameter in the response body for redirecting the user to the payment page

Failure Responses:

Example failure 200 Order Id already exists

```

{
    "success": true
    "message": "Order Id already exists"
    "data": "{}"
    "statusCode": "200"
}

```

Example failure 500 Internal Server Error (Required field missing)

```

{
    "statusText": "error",
    "status": 400,
    "message": "\nInvalid `prisma.paymentRequest.create() `
invocation:\n\n{\n  data: {\n    userId: 522,\n    status: \"pending\",\n    email: \"example@example.com\",\n    description: \"Clone payment request
test\",\n    transactionId: \"T202505262028570staz\",\n    dueDate: \"2025-06-
01T00:00:00.000Z\",\n    provider: \"Easypaisa\",\n    link: \"\",\n    metadata: {\n
  orderNumber: \"order_clone_7856909\"\n  },\n    createdAt: new Date(\"2025-05-
27T09:53:36.312Z\"),\n    updatedAt: new Date(\"2025-05-27T09:53:36.312Z\"),\n
  merchant_transaction_id: \"445u08755i45ii78-CLONE01\",\n    amount:
Decimal\n  }\n}\n\nArgument `amount` is missing."
}

```

Example failure 400 Transaction Not Created

```

{
    "statusText": "fail",
    "status": "400",
    "message": "Transaction not Created"
}

```

Example failure 500 Internal Server Error

```

{
    "status": "error",
    "message": "Something went wrong"
}

```

GET **payment/all-inquiry/**

Status Inquiry

This endpoint allows you to inquire about the payment status of the payment using the order ID.

Base URL

<https://api.assanpay.com/>

Endpoint: Status Inquiry

GET /payment/all-inquiry/

Retrieve the status of a payment.

Full Example:

GET

<https://api.assanpay.com/payment/all-inquiry/{merchnatId}?transactionId=orderId>

Note: Replace transactionId with the actual order ID in the URL.

Parameters

Parameter	Type	Required	Description
transactionId	<i>String</i>	<i>yes</i>	The order ID of the payment.

No Request Body

Responses

Code	Description	Links
200	Payment status retrieved successfully	No Links
404	Payment Data Not Found	No Links

Successful Response:

```
{
  "status": "true",
  "message": "Payment status retrieved successfully"
  "data": {
    "orderId": "12340",
    "transactionStaus": "Pending",

    "transactionAmount": "10",

    "transactionDateTime": "2025-12-18T06:51:10.836Z",

    "responseDesc": null,
    "responseMode": "MA",
  },

}
```

Example failure 404 (Payment Data Not Found)

```
{
  "status": "error",
  "message": "Failed to retrieve payout status",
  "data": {
    "status": 404,
    "message": "Payment data not found",

    "errrcode": "validation"
  }
}
```