Yet Another Graph System

Version 0.0.1

16 February 2016

R. MacKinney-Romero M.A. Pizaña R. Villarroel-Flores

 $\pmb{R.\ MacKinney\text{-}Romero\ Email: rene@xanum.uam.mx}\\$

M.A. Pizaña Email: mpizana@gmail.com Homepage: http://xamanek.izt.uam.mx/map/

R. Villarroel-Flores Email: rvf0068@gmail.com Homepage: http://rvf0068.github.io

Copyright

YAGS - Yet Another Graph System

Copyright © 2016 R. MacKinney-Romero, M.A. Pizaña and R. Villarroel-Flores.

This program is free software: you can redistribute it and/or modify it under the terms of the GNU General Public License as published by the Free Software Foundation, either version 3 of the License, or (at your option) any later version.

This program is distributed in the hope that it will be useful, but WITHOUT ANY WARRANTY; without even the implied warranty of MERCHANTABILITY or FITNESS FOR A PARTICULAR PURPOSE. See the GNU General Public License for more details.

For details, see the file GPL in the installation directory of YAGS typically under GAP-Dir/pkg/yags/GPL or see http://www.gnu.org/licenses/gpl-3.0.html. For contact information see also Section 1.4 in this

CONTACT INFORMATION:

M.A. Pizaña

yags@xamanek.izt.uam.mx

mpizana@gmail.com

Departamento de Ingeniería Eléctrica Universidad Autónoma Metropolitana Av. San Rafael Atlixco 186. Col. Vicentina, Del. Iztapalapa Ciudad de México 09340 MEXICO.

Contents

1	Pref	ace 5			
	1.1	Disclaimer			
	1.2	Welcome to YAGS			
	1.3	Citing YAGS			
	1.4	Copyright			
	1.5	Authors			
	1.6	More Information			
2	Getting Started 8				
	2.1	What is YAGS?			
	2.2	Installing YAGS			
	2.3	Testing the Installation			
	2.4	A Gentle Tutorial			
	2.5	An Overview of the Manual			
	2.6	Cheatsheet			
3	Cliq	ues 9			
	3.1	Cliques and Clique Number			
	3.2	Clique Graphs			
	3.3	Basements, Stars and Neckties			
	3.4	Clique Behavior			
4	Gra	ph Categories 10			
	4.1	The Default Graph Category			
	4.2	The Target Graph Category			
	4.3	Changing the Target Graph Category Temporaryly			
	4.4	Digraphs, Tournaments, etc			
5	Morphisms of Graphs				
	5.1	A Quick Start			
	5.2	Main Procedures			
	5.3	User-Defined Types of Morphisms			
	5 4	Predefined Types of Morphisms 11			

6	Backtracking	12		
	6.1 A Simple Example	12		
	6.2 How Does it Work?	12		
	6.3 Backtracking in Depth	12		
A	YAGS Functions by Topic			
	A.1 Most Common Functions	13		
	A.2 Drawing	13		
	A.3 Constructing Graphs	13		
	A.4 Families of Graphs	13		
	A.5 Small Graphs	13		
	A.6 Attributes and Properties	13		
	A.7 Unary Operators	13		
	A.8 Binary Operators	13		
	A.9 Cliques	13		
	A.10 Morphisms and Isomorphisms	14		
	A.11 Graphs Categories	14		
	A.12 Digraphs	14		
	A.13 Groups and Rings	14		
	A.14 Backtracking	14		
	A.15 Miscellaneous	14		
	A.16 Undocumented	14		
В	YAGS Functions Reference	15		
	B.1 Primera seccion	15		
Re	eferences	20		
In	index 2			

Preface

Ejemplo de cita: [1]

1.1 Disclaimer

THIS IS NOT AN OFFICIAL RELEASE YET, this is a version in development. This particular version, 0.0.1, changes from one day to another without warning and even without a change in the version number. Also, the operations and global variables can still change name or even disappear without warning. No commitment is made at the moment concerning compatibility of this version of the software with any future version.

As of this writing (16/Feb/2016) there are only two trustable chapters in this manual: Appendixes 'YAGS Functions by Topic' and 'YAGS Functions Reference'; also the file cheatsheet-yags.pdf (within directory: YAGSDIR/doc/) may be useful. All other chapters may contain errors, broken links and misleading information (with higher probability).

The first official version will be 0.0.2 and is scheduled to be ready this year (2016), so come back soon.

1.2 Welcome to YAGS

YAGS - Yet Another Graph System is a computing system for dealing with graphs, in the sense of Graph Theory (not bar graphs, pie charts nor graphs of functions). Hence our graphs are ordered pairs G = (V, E), where V is a finite set of vertices and E is a finite set of edges which are (ordered or unordered) pairs of vertices.

YAGS was initiated by M.A. Pizaña in May 2003, and soon incorporated the work of R. MacKinney-Romero and R. Villarroel-Flores.

Our motivation here was this and that.

Our Pourposes and Aim.

authors, contacts

1.3 Citing YAGS

If you publish a result and you used YAGS during your research, please cite us as you would normally do with a research paper:

```
R. MacKinney-Romero, M.A. Pizaña and R. Villarroel-Flores.
YAGS - Yet Another Graph System, Version 0.0.1 (2016)
http://xamanek.izt.uam.mx/yags/

@manual{YAGS, author = {R. MacKinney-Romero and M.A. Pizaña and R.
Villarroel-Flores}, title = {YAGS - Yet Another Graph System, Version 0.0.1},
year = {2016}, note = {http://xamanek.izt.uam.mx/yags/}, }
```

1.4 Copyright

YAGS - Yet Another Graph System

Copyright © 2016 R. MacKinney-Romero, M.A. Pizaña and R. Villarroel-Flores.

This program is free software: you can redistribute it and/or modify it under the terms of the GNU General Public License as published by the Free Software Foundation, either version 3 of the License, or (at your option) any later version.

This program is distributed in the hope that it will be useful, but WITHOUT ANY WARRANTY; without even the implied warranty of MERCHANTABILITY or FITNESS FOR A PARTICULAR PURPOSE. See the GNU General Public License for more details.

For details, see the file GPL in the installation directory of YAGS typically under GAP-Dir/pkg/yags/GPL or see http://www.gnu.org/licenses/gpl-3.0.html.

CONTACT INFORMATION:

```
M.A. Pizaña
```

yags@xamanek.izt.uam.mx mpizana@gmail.com Departamento de Ingeniería Eléctrica Universidad Autónoma Metropolitana Av. San Rafael Atlixco 186. Col. Vicentina, Del. Iztapalapa Ciudad de México 09340 MEXICO.

1.5 Authors

The authors of YAGS in the chronological order of their first contribution are as follows:

M.A. Pizaña
Departamento de Ingeniería Eléctrica
Universidad Autónoma Metropolitana
map@xanum.uam.mx

R. MacKinney-Romero Departamento de Ingeniería Eléctrica Universidad Autónoma Metropolitana rene@xanum.uam.mx

R. Villarroel-Flores

Centro de Investigación en Matemáticas Universidad Autónoma del Estado de Hidalgo rafaelv@uaeh.edu.mx

1.6 More Information

More information about YAGS can be found on its official web page:

'http://xamanek.izt.uam.mx/yags/'

You can receive notifications about YAGS (i.e. new releases, bug fixes, etc.) by subscribing to its email distribution list:

'http://xamanek.izt.uam.mx/cgi-bin/mailman/listinfo/yagsnews/'

If you are a developer, you may contribute to our project on public repository:

'https://github.com/yags/main/'

Getting Started

- 2.1 What is YAGS?
- 2.2 Installing YAGS
- **2.3** Testing the Installation
- 2.4 A Gentle Tutorial
- 2.5 An Overview of the Manual
- 2.6 Cheatsheet

Cliques

- 3.1 Cliques and Clique Number
- 3.2 Clique Graphs
- 3.3 Basements, Stars and Neckties
- 3.4 Clique Behavior

Graph Categories

- **4.1** The Default Graph Category
- **4.2** The Target Graph Category
- 4.3 Changing the Target Graph Category Temporaryly
- 4.4 Digraphs, Tournaments, etc.

Morphisms of Graphs

- 5.1 A Quick Start
- **5.2** Main Procedures
- **5.3** User-Defined Types of Morphisms
- **5.4** Predefined Types of Morphisms

Backtracking

- **6.1** A Simple Example
- 6.2 How Does it Work?
- **6.3** Backtracking in Depth

Appendix A

YAGS Functions by Topic

- **A.1** Most Common Functions
- A.2 Drawing
- **A.3** Constructing Graphs
- **A.4** Families of Graphs
- A.5 Small Graphs
- A.6 Attributes and Properties
- **A.7** Unary Operators
- **A.8** Binary Operators
- A.9 Cliques

Functions dealing with cliques.

- Basement(G, KnG, x)
 Basement(G, KnG, V)
 Returns the basement of vertex x (vertex set V) of the iterated clique graph KnG with respect to
- CliqueGraph(G)
 CliqueGraph(G, maxNumCli)
 Returns the intersection graph of the (maximal) cliques of G; aborts if maxNumCli cliques are found.
- CliqueNumber(G) Returns the order, $\omega(G)$, of a maximum clique of G.

```
• Cliques( G )
Cliques( G, maxNumCli )
Returns the list of (maximal) cliques of G; aborts if maxNumCli cliques are found.
```

- CompletesOfGivenOrder(G, Ord)
 Returns the list of vertex sets of all complete subgraphs of order Ord of G.
- IsCliqueGated(G)
 Returns 'true' if G is a clique gated graph.
- IsCliqueHelly(*G*)
 Returns 'true' if the set of (maximal) cliques *G* satisfy the *Helly* property.
- IsComplete(*G*, *L*)
 Returns 'true' if *L* induces a complete subgraph of *G*.
- IsCompleteGraph(*G*)
 Returns 'true' if graph *G* is a complete graph, 'false' otherwise.
- NumberOfCliques(G)
 NumberOfCliques(G, maxNumCli)
 Returns the number of (maximal) cliques of G.

A.10 Morphisms and Isomorphisms

A.11 Graphs Categories

- A.12 Digraphs
- A.13 Groups and Rings
- A.14 Backtracking
- A.15 Miscellaneous
- A.16 Undocumented

Appendix B

YAGS Functions Reference


This chapter contains a complete list of all YAGS's functions, with definitions, in alphabetical order.

B.1 Primera seccion

B.1.1 GraphCategory

```
▷ GraphCategory([G, ...]) (function)
```

For internal use. Returns the minimal common category to a list of graphs. If the list of graphs is empty, the default category is returned. The partial order (by inclusion) among graph categories is as follows:



```
_ Example -
gap> g1:=CompleteGraph(2:GraphCategory:=SimpleGraphs);
Graph( Category := SimpleGraphs, Order := 2, Size := 1, Adjacencies :=
[[2],[1]])
gap> g2:=CompleteGraph(2:GraphCategory:=OrientedGraphs);
Graph( Category := OrientedGraphs, Order := 2, Size := 1, Adjacencies :=
[[2],[]])
gap> g3:=CompleteGraph(2:GraphCategory:=UndirectedGraphs);
Graph( Category := UndirectedGraphs, Order := 2, Size := 3, Adjacencies :=
[[1, 2], [1, 2]])
gap> GraphCategory([g1,g2,g3]);
<Operation "Graphs">
gap> GraphCategory([g1,g2]);
<Operation "LooplessGraphs">
gap> GraphCategory([g1,g3]);
<Operation "UndirectedGraphs">
```

B.1.2 Graphs

▷ Graphs (filter)

Graphs is the most general graph category in YAGS. This category contains all graphs that can be represented in YAGS. A graph in this category may contain loops, arrows and edges (which in YAGS are exactly the same as two opposite arrows between some pair of vertices). This graph category has no parent category.

```
Example

gap> GraphByWalks([1,1],[1,2],[2,1],[3,2]:GraphCategory:=Graphs);

Graph( Category := Graphs, Order := 3, Size := 4, Adjacencies :=

[ [ 1, 2 ], [ 1 ], [ 2 ] ])

gap> GraphByWalks([1,1],[1,2],[2,1],[3,2]:GraphCategory:=SimpleGraphs);

Graph( Category := SimpleGraphs, Order := 3, Size := 2, Adjacencies :=

[ [ 2 ], [ 1, 3 ], [ 2 ] ])
```

B.1.3 LooplessGraphs

LooplessGraphs is a graph category in YAGS. A graph in this category may contain arrows and edges but no loops. The parent of this category is Graphs.

```
gap> GraphByWalks([1,1],[1,2],[2,1],[3,2]:GraphCategory:=Graphs);
Graph( Category := Graphs, Order := 3, Size := 4, Adjacencies :=
[ [ 1, 2 ], [ 1 ], [ 2 ] ] )
gap> GraphByWalks([1,1],[1,2],[2,1],[3,2]:GraphCategory:=LooplessGraphs);
Graph( Category := LooplessGraphs, Order := 3, Size := 3, Adjacencies :=
[ [ 2 ], [ 1 ], [ 2 ] ] )
```

B.1.4 Order

 \triangleright Order(G) (attribute)

Returns: the number of vertices, of graph G.

```
gap> Order(Icosahedron);
12
```

B.1.5 OrientedGraphs

```
▷ OrientedGraphs (filter)
```

OrientedGraphs is a graph category in YAGS. A graph in this category may contain arrows, but no loops or edges. The parent of this category is LooplessGraphs.

```
Example

gap> GraphByWalks([1,1],[1,2],[2,1],[3,2]:GraphCategory:=Graphs);

Graph( Category := Graphs, Order := 3, Size := 4, Adjacencies :=

[ [ 1, 2 ], [ 1 ], [ 2 ] ])
```

```
gap> GraphByWalks([1,1],[1,2],[2,1],[3,2]:GraphCategory:=OrientedGraphs);
Graph( Category := OrientedGraphs, Order := 3, Size := 2, Adjacencies :=
[ [ 2 ], [ ], [ 2 ] ] )
```

B.1.6 SetDefaulGraphCategory

```
▷ SetDefaulGraphCategory(Catgy)
```

(function)

Sets the default graph category to *Catgy*. The default graph category is used when constructing new graphs when no other graph category is indicated. New graphs are always forced to comply with the TargetGraphCategory, so loops may be removed, and arrows may replaced by edges or viceversa, depending on the category that the new graph belongs to. The available graph categories are: SimpleGraphs, OrientedGraphs, UndirectedGraphs, LooplessGraphs, and Graphs.

```
Example
gap> SetDefaultGraphCategory(Graphs);
gap> GraphByWalks([1,1],[1,2],[2,1],[3,2]);
Graph( Category := Graphs, Order := 3, Size := 4, Adjacencies :=
[[1,2],[1],[2]])
gap> SetDefaultGraphCategory(LooplessGraphs);
gap> GraphByWalks([1,1],[1,2],[2,1],[3,2]);
Graph( Category := LooplessGraphs, Order := 3, Size := 3, Adjacencies :=
[[2],[1],[2]])
gap> SetDefaultGraphCategory(UndirectedGraphs);
gap> GraphByWalks([1,1],[1,2],[2,1],[3,2]);
Graph( Category := UndirectedGraphs, Order := 3, Size := 3, Adjacencies :=
[[1, 2], [1, 3], [2]])
gap> SetDefaultGraphCategory(SimpleGraphs);
gap> GraphByWalks([1,1],[1,2],[2,1],[3,2]);
Graph( Category := SimpleGraphs, Order := 3, Size := 2, Adjacencies :=
[[2],[1,3],[2]])
gap> SetDefaultGraphCategory(OrientedGraphs);
gap> GraphByWalks([1,1],[1,2],[2,1],[3,2]);
Graph( Category := OrientedGraphs, Order := 3, Size := 2, Adjacencies :=
[[2],[],[2]])
```

B.1.7 SimpleGraphs


SimpleGraphs is a graph category in YAGS. A graph in this category may contain edges, but no loops or arrows. The category has two parents: LooplessGraphs and UndirectedGraphs.

B.1.8 TargetGraphCategory

```
▷ TargetGraphCategory([G, ...])

(function)
```

For internal use. Returns the graph category indicated in the *options stack* if any, otherwise if the list of graphs provided is not empty, returns the minimal common graph category for the graphs in the list, else returns the default graph category. The partial order (by inclusion) among graph categories is as follows:



This function is internally called by all graph constructing operations in YAGS to decide the graph category that the newly constructed graph is going to belong to. New graphs are always forced to comply with the TargetGraphCategory, so loops may be removed, and arrows may replaced by edges or viceversa, depending on the category that the new graph belongs to.

The *options stack* is a mechanism provided by GAP to pass implicit parameters and is used by TargetGraphCategory so that the user may indicate the graph category she/he wants for the new graph.

```
gap> SetDefaultGraphCategory(SimpleGraphs);
gap> g1:=CompleteGraph(2);
Graph( Category := SimpleGraphs, Order := 2, Size := 1, Adjacencies :=
[ [ 2 ], [ 1 ] ] )
gap> g2:=CompleteGraph(2:GraphCategory:=OrientedGraphs);
Graph( Category := OrientedGraphs, Order := 2, Size := 1, Adjacencies :=
[ [ 2 ], [ ] ] )
gap> DisjointUnion(g1,g2);
Graph( Category := LooplessGraphs, Order := 4, Size := 3, Adjacencies :=
[ [ 2 ], [ 1 ], [ 4 ], [ ] ] )
gap> DisjointUnion(g1,g2:GraphCategory:=UndirectedGraphs);
Graph( Category := UndirectedGraphs, Order := 4, Size := 2, Adjacencies :=
[ [ 2 ], [ 1 ], [ 4 ], [ 3 ] ] )
```

In the previous examples, TargetGraphCategory was called internally exactly once for each new graph constructed with the following parameters:

B.1.9 UndirectedGraphs

UndirectedGraphs is a graph category in YAGS. A graph in this category may contain edges and loops, but no arrows. The parent of this category is Graphs.

```
gap> GraphByWalks([1,1],[1,2],[2,1],[3,2]:GraphCategory:=Graphs);
Graph( Category := Graphs, Order := 3, Size := 4, Adjacencies :=
[ [ 1, 2 ], [ 1 ], [ 2 ] ] )
gap> GraphByWalks([1,1],[1,2],[2,1],[3,2]:GraphCategory:=UndirectedGraphs);
Graph( Category := UndirectedGraphs, Order := 3, Size := 3, Adjacencies :=
[ [ 1, 2 ], [ 1, 3 ], [ 2 ] ] )
```

References

[1] F. Larrión, V. Neumann-Lara and M.A. Pizaña. *Clique divergent clockwork graphs and partial orders*. Discrete Appl. Math. **141** (2004) 195–207. 5

Index

```
GraphCategory, 15
Graphs, 16

LooplessGraphs, 16

Order, 16
OrientedGraphs, 16

SetDefaulGraphCategory, 17
SimpleGraphs, 17

TargetGraphCategory, 18

UndirectedGraphs, 19
```