

# **Arguments**

Arguments are possible settings that can be applied to each instance of an attribute in Addepar. Use the Arguments API in confunction with the Attributes API to discover available attribute arguments for making Portfolio Query API requests.

Base Route	/v1/arguments
Endpoints	GET /v1/arguments /v1/arguments/:id
Produces	JSON
Pagination	No
Application Permissions Required	"API Access: Create, edit, and delete" is required to retrieve available arguments.
OAuth Scopes	PORTFOLIO

## **Resource Overview**

Arguments are described by the below resource object attributes and will appear in successful **GET** responses.

ATTRIBUTE	DESCRIPTION	EXAMPLE
values	Values supported by the argument. [Boolean or String.]	[true, false]
default_value	Default argument value. Boolean or String.	false
arg_type	The argument type which is determined by its output type. String.	"discrete"

# **Get All Arguments**

Retrieves all attribute arguments supported by the Portfolio Query API.

**GET** /v1/arguments

## Example:



#### **Response Codes:**

- 200 OK : Success
- 403 Forbidden: Insufficient application permissions or appropriate scope not granted

## **Get Argument By ID**

Retrieves the attribute argument with the given ID.

**GET** /v1/arguments/:id

#### **Example:**

REQUEST JSON

GET https://examplefirm.addepar.com/api/v1/arguments/cost\_basis\_type

#### **Response Codes:**

- 200 OK: Success
- 403 Forbidden: Insufficient application permissions or appropriate scope not granted
- 404 Not Found: Argument does not exist

### What's Next

Time to try it out for yourself:

## **API Explorer: Arguments**

