

PRISMS-plasticity installation manual

Srihari Sundar, Mohammadreza Yaghoobi, Aaditya Lakshmanan

Installing deal.ii

The plasticity code is built upon the deal.ii open source finite element library. The dependencies are CMake, MPI, PETSc and p4est.

CMake

CMake can be downloaded at: <https://cmake.org/download>, which also has installation instructions. It is also available through package managers such as homebrew, yum, and apt. Once installed, be sure to add CMake to your path by entering:

```
$ PATH="/path/to/cmake/Contents/bin": "$PATH"
```

PETSc

<https://www.dealii.org/developer/external-libs/petsc.html>

<http://www.mcs.anl.gov/petsc/download/index.html>

```
tar xzvf petsc-3.9.3.tar.gz
```

```
cd petsc-3.9.3.tar.gz
```

```
export PETSC_DIR=$PWD
```

```
export PETSC_ARCH=August2018
```

```
./config/configure.py --with-cc=gcc --with-cxx=g++ --with-fc=gfortran \
--with-shared=1 --with-x=0 --with-mpi=1 --download-hypre=1 \
--download-fblaslapack --download-mpich
```

```
make PETSC_DIR=$PETSC_DIR PETSC_ARCH=$PETSC_ARCH all
```

```
make PETSC_DIR=/afs/umich.edu/user/s/r/sriharis/Public/petsc-3.9.3 PETSC_ARCH=A
```

```
export PATH=$PATH:$PETSC_DIR/$PETSC_ARCH/bin
```

p4est

<https://www.dealii.org/developer/external-libs/p4est.html>

<http://www.p4est.org/> - Download latest tarball

Use the installation script and install with:

```
wget https://www.dealii.org/developer/external-libs/p4est-setup.sh
```

```
chmod u+x p4est-setup.sh
```

```
./p4est-setup.sh p4est-2.0.tar.gz $PWD/p4est-install
```

```
export P4EST_DIR=$PWD/p4est-install
```

deal.ii

Once all the dependencies are installed, the library can be compiled using the following steps. Download the tarball from <https://www.dealii.org/download.html>.

```
tar xzvf dealii-9.0.0.tar.gz
mkdir build
```

```
cd build
```

```
cmake -DCMAKE_INSTALL_PREFIX=$HOME/deal_II_AUG18 ../dealii-9.0.0 \
-DDEAL_II_WITH_PETSC=ON -DPETSC_DIR=$PETSC_DIR -DPETSC_ARCH=$PETSC_ARCH \
-DDEAL_II_WITH_P4EST=ON -DP4EST_DIR=$P4EST_DIR \
-DDEAL_II_WITH_MPI=ON
```

‘make’ works in parallel and you can use multiple cores on the CPU to complete installation, using:

```
make -jN install
```

where N is the number of processor cores on your system. Otherwise, the installation takes a lot of time.

If you used the above install prefix then setup the `DEAL_II_DIR` environment variable needed for running projects built upon deal.ii.

Setup plasticity code

```
git clone https://github.com/prisms-center/plasticity.git
```

```
cd plasticity
export PRISMSplas=$PWD
```

```
cmake .
make -j N
```

```
cd applications/crystalPlasticity
cmake .
make release
```

Running an example simulation

```
cd $PRISMSplas/applications/crystalPlasticity/fcc/simpleTension
```

Running the simple tension example case:

```
mkdir results
mpirun -n 8 $PRISMSplas/applications/main prm.in
```

A detailed explanation of all the user parameters and other example cases is discussed in the PRISMS-plasticity user manual.