

Spring MVC Tag Library & Formatter

Do Less and Accomplish More

Spring MVC Form Tag Library

- ▶ Facilitates the development of JSP pages
- ▶ Integrated with Spring MVC data binding features
- ▶ Each tag provides support for the set of attributes of its corresponding HTML tag counterpart, making the tags familiar and intuitive to use.
- ▶ Access Form Tag Library:

```
<%@ taglib prefix="form"  
uri="http://www.springframework.org/tags/form" %>
```

Spring MVC data binding

- ▶ Built-in Data Binding handles simple String to data type conversions
- ▶ HTTP request parameters [String types] are converted to model object properties of varying data types.
- ▶ As a result:
 - ▶ Data binding makes form beans obsolete
 - ▶ Any object can be a command AKA a form-backing object
 - ▶ Can bind directly to **business domain objects**.
 - ▶ Domain objects exist as POJOs
- ▶ **The Spring MVC Form tag library makes it easy to bind form elements to model data with JSP pages As Binding function is ALREADY there.**

Form Tag Library

Tag Name	Description
form	Renders an HTML form tag and exposes the binding path to the other form tags.
input	Renders an input element with the default type of text. The type of the input element can be (optionally) specified (like email, date etc.) . Note that you can't use radiobutton or checkbox for those types.
password	Renders an input element of type password.
hidden	Renders an input element of type hidden.
select	Renders an HTML select element. The option and/or options tag are used to specify the options to render.
option	Renders a single HTML option element inside a select element.
options	Renders a collection of HTML option elements inside a select element.
radiobutton	Renders an HTML input element of the type radio button.
radiobuttons	Renders multiple HTML input elements of the type radio button.
checkbox	Renders an HTML input element of the type checkbox.
checkboxes	Renders multiple HTML input elements of the type checkbox.
textarea	Renders an HTML Textarea element.
errors	Displays binding and/or validation errors to the user. It can be used to either specify the path for field-specific error messages or to specify an * to display all error messages.
label	Renders a HTML Label and associate it with an input element.
button	Renders an HTML Button element.

[Spring Form Tag Library](#)

Form Tag

- ▶ This tag renders an HTML 'form' tag and exposes a **binding path** to inner tags for binding. *All the other tags in this library are nested tags of the form tag.*

1. From controller forward to JSP page which contains Spring Form Tag

```
@RequestMapping(value = "/addBook", method = RequestMethod.GET)  
public String inputBook(@ModelAttribute("newBook") Book book, Model model) {  
    return "BookAddForm";  
}
```

2. Use Spring Form tag in JSP page: [BookAddForm.jsp](#)

```
<form:form modelAttribute="newBook" action="addBook" method="post">
```

OR

```
<form:form commandName="newBook" action="addBook" method="post">
```

3. Save data in Controller

```
@RequestMapping(value = "/addBook", method = RequestMethod.POST)  
public String saveBook(@ModelAttribute("newBook") Book book) {  
    bookService.save(book);  
    return "redirect:/book_list";  
}
```

Form Tag (cont.)

```
@RequestMapping(value = "/add", method = RequestMethod.GET)  
public String getAddNewProductForm(@ModelAttribute("newProduct") Product  
product) {
```

Request Mapping can be differentiated by RequestMethod Type

```
@RequestMapping(value = "/add", method = RequestMethod.POST)  
public String processAddNewProductForm(@ModelAttribute("newProduct")  
Product productToBeAdded ) {
```

```
<form:form modelAttribute="book">
```

No need for Method as Post is “assumed” [Spring]

No need for Action as long as GET & Post have same URI [HTML 4]

ALSO, by default, Spring IGNORES Suffixes

/add.do will match to

```
@RequestMapping(value = "/add", method = RequestMethod.POST)
```

Form Tag Binding Algorithm

- ▶ For “Get” Method, Looks in model map for key: “newBook”
- ▶ If it doesn’t find the key – error is thrown.

```
@RequestMapping(value = "/addBook", method = RequestMethod.GET)  
public String inputBook(@ModelAttribute("newBook") Book book, Model  
    model) {  
    return "BookAddForm";  
}
```

```
<form:form modelAttribute="newBook" action="addBook" method="post">
```

- ▶ For “Post” Method, Looks in model map for key: “newBook”
- ▶ If it doesn’t find the key, does “best match” on other attributes...

```
@RequestMapping(value = "/addBook", method = RequestMethod.POST)  
public String inputBook(@ModelAttribute("newBook") Book book, Model model)
```

OR

```
public String inputBook(Book book, Model model)
```

@ModelAttribute

- ▶ **Can be placed on a method parameter:**

```
@RequestMapping(value = "/addBook", method = RequestMethod.POST)  
public String saveBook(@ModelAttribute("newBook") Book book) {}
```

- ▶ The Object should be retrieved from the model or instantiated if doesn't exist. The Object fields should be populated from all request parameters that have matching names.

- ▶ **Can be placed on method. Method invoked before methods annotated with @RequestMapping**

```
@ModelAttribute("books")  
List<Book> addBookList(Model model) {  
    return bookService.getAllBooks();  
}
```

- ▶ Object is added to Model – in this example the List of books is added

Form examples with HTML output

```
<form:input id="title" path="title"/>
```

► Generated HTML:

```
<input id="title" name="title" type="text" value=""/>
```

If category.id already has a value,
Then it will be market as selected

► When *categories* is a LIST

```
<form:select id="category" path="category.id"
items="${categories}" itemValue="id" itemLabel="name" />
```

► Generated HTML:

```
<select id="category" name="category.id">
  <option value="1" selected="selected">Computing</option>
  <option value="2">Travel</option >
  <option value="3">Health</option >
</select>
```

► **NOTE:** *path* is the “binding Path” defined previously

Form example with HTML output [Cont.]

```
<form:select id="category" path="category.id">
  <form:option value="0" label="--Select Category"/>
  <form:options items="${categories}" itemLabel="name" itemValue="id"/>
</form:select>
```

► Generated HTML:

```
<select id="category" name="category.id">
  <option value="0" selected="selected">--Select Category</ option >
  <option value="1">Computing</ option >
  <option value="2">Travel</ option >
  <option value="3">Health</option>
</select>
```

► When categories is a MAP

```
<form:select path="category.id" items="${categoriesMap}" />
```

► Automatically Yields:

```
<option value="1">Computing</ option >
```



Where "1" is the Map key

General Purpose Spring Tag Library

- ▶ Not Spring MVC specific
- ▶ Available to any Java Server Page used in the Spring Framework
- ▶ Tags for evaluating errors, setting themes and outputting internationalized messages.

```
<%@ taglib prefix="spring" uri="http://www.springframework.org/tags"%>
```

Spring Tag Library

Tag Name	Description
<code>htmlEscape</code>	Sets the default HTML escape value for the current page. If set, this tag overrides the value set in the default <code>htmlEscape</code> context-parameter.
<code>escapeBody</code>	Escapes the enclosed body.
<code>message</code>	Displays a message with the given code and for the selected locale. (See the section about internationalization (I18N) later in this chapter for more information.)
<code>theme</code>	Uses the variable from the currently selected theme. (See Chapter 9 for more information.)
<code>hasBindErrors</code>	Shows or hides part of the page (or element) based on whether an model attribute has bind (or validation) errors.
<code>nestedPath</code>	Selects a nested path to be used by the <code>bind</code> tag's path. For example, it can be used to bind <code>customer.address</code> to <code>street</code> instead of to <code>customer.address.street</code> .
<code>bind</code>	Binds an attribute of the model (attribute) to the enclosed input element.
<code>transform</code>	Transforms the bound attribute using Spring's type-conversion system. This tag must be used inside a <code>spring:bind</code> tag.
<code>url</code>	Similar to the <code>jstl core URL</code> tag. It is enhanced so the URL can contain URL template parameters.
<code>param</code>	Specifies a parameter and value to be assigned to the URL. This tag is used inside an <code>url</code> tag.
<code>eval</code>	Evaluates a SpEL expression and prints the result or assigns it to a variable.

Message Tag

- ▶ Internationalization support through externalization of messages
- ▶ Text from `MessageSource` configured in `WebApplicationContext`

```
<spring:message code="greeting" text="Hi" />
```

- ▶ “code” isn’t set or cannot be resolved, “text” will be used as default message.
- ▶ Also, the `spring:message`- tag, works with the locale support that comes with Spring. [Internationalization]

Spring [externalize] message tag example

- ▶ Dispatcher Servletconfiguration file declares message source bean. “messages” file is messages.properties and must reside in the source class path in order to be discovered.

- ▶ `springmvc-config.xml`

```
<bean id= "messageSource"  
      class="org.springframework.context.support.ResourceBundleMessageSource">  
    <property name="basenames" value="message2,messages"/>  
</bean>
```

- ▶ `WebApplicationContextConfig.java`

@Bean

```
public MessageSource messageSource() {  
    ResourceBundleMessageSource resource = new ResourceBundleMessageSource();  
    resource.setBasename("messages");  
    return resource;  
}
```

- ▶ Spring message tag accesses label name from resource file messages.properties

```
<label for="bookList"><spring:message code="book.book" /> </label>
```

Spring URL Tag

Spring URL tag

- ▶ Access static resources: Resolves the path from context root - irrespective of current URL.

```
<link rel="stylesheet" type="text/css" href="<spring:url value="/css/main.css"/>">
```

- ▶ Resolved to:

```
<link rel="stylesheet" type="text/css" href="/Book_Tag_Formatter/css/main.css">
```

- ▶ Query Parameter Passing:

```
<spring:url value="/addBook" var="addBook_url" >  
  <spring:param name="ISBN" value="1234"/>  
</spring:url>  
<a href="${addBook_url}">Add Book</a>
```

Just Like JSTL URL

- ▶ Resolved to:

```
<a href="/Book05a/addBook?ISBN=1234">Add Book</a>
```

- ▶ Spring Template /@PathVariable

```
<spring:url value="/book_edit/{id}" var="edit" >  
  <spring:param name="id" value="${book.id}" />  
</spring:url>  
<a href="${edit}">Edit</a>
```

- ▶ Resolved to:

```
<a href="/Book05a/book_edit/2">Edit</a>
```

Main Point

The Spring MVC tag library facilitates JSP development with specialized Form tags.

The practice of the TM technique, by structuring the laws of nature in one's life makes everything go more smoothly.

Excluding Fields from Data Binding

- ▶ We don't always want to bind our ENTIRE domain object. For example, an internal Customer or Product ID
- ▶ Need to explicitly restrict binding on specific fields
- ▶ WebDataBinder object used by the binding function
- ▶ `@InitBinder` annotation identifies Controller method that accesses WebDataBinder

```
@InitBinder
```

```
public void initialiseBinder(WebDataBinder binder) {  
    //binder.setDisallowedFields("title");  
    binder.setAllowedFields("isbn", "title", "category.id",  
        "author", "publishDate");  
}
```

Custom Data Binding

- ▶ Built-in Data Binding handles simple String to data type conversions.
- ▶ Custom Binding is needed to handle more complex cases.
- ▶ Three Options in Spring MVC:
 - ▶ CustomPropertyEditor
 - ▶ Old-style [“retro”] ,heavyweight based on entire java.beans package
 - ▶ Converter
 - ▶ General-purpose type conversion system introduced Spring 3.0. used internally by Spring. One way conversion, locale agnostic
 - ▶ Formatter
 - ▶ Designed for Spring MVC form conversion. 2 way conversion - to & from String. Locale aware. More lightweight than Converter.

Out-of-the-box Spring Formatters

- ▶ The Number Package:
 NumberFormatter,
 CurrencyFormatter
 PercentFormatter
- ▶ The DateTime Package:
 [DateFormatter API](#)
- ▶ Custom Examples [NOT out-of-the-box]:
 ISBN Number
 Multiple Select List – collection of Objects

ISBN Formatter Example

```
public class ISBNFormatter implements Formatter<ISBNNumber> {

    public String print(ISBNNumber isbn, Locale locale) {
        return isbn.getStart() + "-" +
               isbn.getMiddle() + "-" + isbn.getEnd();
    }

    public ISBNNumber parse(String source, Locale locale)
        throws ParseException {
        int start = Integer.parseInt(source.substring(0, 3));
        int middle = Integer.parseInt(source.substring(4, 7));
        int end = Integer.parseInt(source.substring(8, 11));
        return new ISBNNumber(start, middle, end);
    }
}
```

Formatter Configuration

```
<mvc:annotation-driven conversion-service="conversionService"/>

<bean id="conversionService" class=
"org.springframework.format.support.FormattingConversionServiceFactoryBean">
  <property name="formatters">
    <set>
      <bean class="mum.edu.formatter.ISBNFormatter"> </bean>
    </set>
  </property>
</bean>
```

Multiple Select Formatter

```
/**
 * If a Book referenced in a Form by the String value of its ID
 * it is converted into an Object & Vice-versa
 */
@Component
public class BookFormatter implements Formatter<Book> {

    @Autowired
    private BookService bookService;

    public Book parse(String text, Locale locale) throws ParseException {
        return bookService.get(Long.valueOf(text));
    }

    @Override
    public String print(Book object, Locale locale) {
        return String.valueOf(object.getId());
    }
}
```

Main Point

- ▶ Spring Data binding automatically binds form elements to Model data. Spring MVC tag library makes this easy with JSP Form tags. For specialized [complex] cases, Spring MVC provides the custom Formatter interface
- ▶ *The practice of the TM technique, in a simple automatic way structures communication between outer and inner values enlivening all aspects of life.*