SIMATS ENGINEERING
ASSESSMENT TOOL 3

COURSE NAME: Artificial Intelligence **COURSE CODE: CSA17**

COURSE OUTCOME COVERED

CO2: *Experiment search and game-solving techniques such as Greedy Search, A*, CSP, Minimax, and Alpha-Beta pruning with heuristic functions for solving complex AI problems efficiently. (BL3)*

Assessment Tool Weightage: 40%

Duration: 1 Hour

QUESTIONS: 3 **Total Marks:30**

Annexure A

Dry Run Evaluation

Code of Conduct:

I **Eshwanth C / 192321062** *(Name / Reg No) certify that this submission is my original work and that I have adhered to the guidelines specified for this assessment.*
I understand that any violation of academic integrity rules will result in disciplinary action.


Signature of the student:

Annexure A

Dry Run Evaluation

1. Question 1 – Breadth-First Search (BFS)

Consider the following graph:




Task: Starting from node **A**, perform a **Breadth-First Search (BFS)**. Complete the following table.

Iteration	Queue	Visited Node *(queue shown after expanding the visited node)*
1	B, C	**A**
2	C, D, E	**B**
3	D, E, F, G	**C**
4	E, F, G	**D**
5	F, G	**E**
6	G	**F**
7	(empty)	**G**

Questions:

1. Write the BFS traversal order. **A → B → C → D → E → F → G**
2. Show the queue contents after each iteration. See the Queue column of the table above.

2. Depth-First Search (DFS) Using the same graph,



Iter	Stack (top at left)	Visited
1	B, C	**A**
2	D, E, C	**B**
3	E, C	**D**
4	C	**E**
5	F, G	**C**
6	G	**F**
7	(empty)	**G**

Perform **Depth-First Search (DFS)** starting from **A**.

Complete the table. **DFS order: A → B → D → E → C → F → G**

3. **Initial State :**
   1 3 6
   5 0 2
   4 7 8

Goal State :

1 2 3
4 5 6
7 8 0

Task

Trace **Breadth-First Search (BFS)** until the goal state is reached.
Fill in the table.

Iteration	Current State	Queue Before Expansion	Queue After Expansion
1	S0 = 136/502/478	S0	S1,S2,S3,S4
2	S1 = 106/532/478	S1,S2,S3,S4	S2,S3,S4,S5,S6
3	S2 = 136/572/408	S2,S3,S4,S5,S6	S3,S4,S5,S6,S7,S8
4	S3 = 136/052/478	S3,S4,S5,S6,S7,S8	S4,S5,S6,S7,S8,S9,S10
5	S4 = 136/520/478	S4,S5,S6,S7,S8,S9,S10	S5,S6,S7,S8,S9,S10,S11,S12

Questions

1. Which node is expanded in each iteration?
2. How many states are generated in total?
3. Write the complete solution path from the initial state to the goal state.
4. Why does BFS always find the shortest solution in an unweighted 8-puzzle problem?


Notation: each state is written row by row (0 = blank), e.g. 136/502/478. Moves of the blank are tried in the order Up, Down, Left, Right; the parent state and already-seen states are not added again.

States generated: S0 = 136/502/478; S1 = 106/532/478; S2 = 136/572/408; S3 = 136/052/478; S4 = 136/520/478; S5 = 016/532/478; S6 = 160/532/478; S7 = 136/572/048; S8 = 136/572/480; S9 = 036/152/478; S10 = 136/452/078; S11 = 130/526/478; S12 = 136/528/470.

Ans 1: Iteration 1 → S0, 2 → S1, 3 → S2, 4 → S3, 5 → S4 (nodes leave the queue in FIFO order; the goal is reached later at depth 8).

Ans 2: 13 states after 5 iterations (1 + 4 + 2 + 2 + 2 + 2). Running BFS until the goal is selected: about 500 distinct states generated (about 310 expanded, the goal is the 311th node removed from the queue).

Ans 3: Solution path (8 moves of the blank: Right, Up, Left, Down, Left, Down, Right, Right)



Ans 4: BFS expands nodes level by level using a FIFO queue, so every node at depth d is expanded before any node at depth d+1. In the unweighted 8-puzzle every move costs 1, so path cost = depth. The first time the goal is reached it is therefore at the smallest possible depth, i.e. with the fewest moves. The state space is finite, so BFS is also complete.

RUBRICS FOR CALCULATION

Criteria	Weightage (%)	Level 4 – Exemplary (4)	Level 3 – Proficient (3)	Level 2 – Developing (2)	Level 1 – Beginning (1)
Understanding of Search Problem	**20**	Clearly understands the search problem, initial state, goal state, and search strategy.	Understands the problem with minor misunderstandings.	Demonstrates partial understanding of the search problem.	Shows little or no understanding of the search problem.

Criteria	Weightage (%)	Level 4 – Exemplary (4)	Level 3 – Proficient (3)	Level 2 – Developing (2)	Level 1 – Beginning (1)
State Expansion and Dry Run Execution	**30**	Correctly traces every iteration, expands nodes accurately, and maintains the Queue/Stack/Priority Queue without errors.	Performs most iterations correctly with minor mistakes in state expansion or data structure updates.	Performs only some iterations correctly; several errors in tracing or node expansion.	Unable to correctly perform the dry run or expand states.
Application of Search Algorithm	**20**	Applies the selected algorithm (BFS/DFS/UCS) correctly, following all algorithmic rules.	Applies the algorithm correctly with a few procedural errors.	Applies only basic algorithm steps with noticeable mistakes.	Fails to apply the correct search algorithm.
Accuracy of Solution Path	**20**	Identifies the correct traversal order/solution path and goal state with proper justification.	Solution path is mostly correct with minor errors.	Partially correct solution path; goal may not be reached correctly.	Incorrect or incomplete solution path.
Presentation and Logical Reasoning	**10**	Queue/Stack/Priority Queue updates, state diagrams, and explanations are neat, organized, and logically presented.	Presentation is clear with minor organizational issues.	Limited explanation and organization; reasoning is partially clear.	Poor presentation with unclear or missing reasoning.