


# Questions


Physics

Sanjeev\*

- If the charge on a capacitor is doubled, the value of its capacitance  $C$  will be :
  - Doubled
  - Halved
  - Remains Unchanged
  - None of these
- The maximum electric field that a dielectric medium of a capacitor can withstand without breakdown (of its insulating property) is called its :
  - Polarization*
  - Capacitance*
  - Dielectric strength*
  - Dielectric constant*
- Consider a parallel plate capacitor of  $10 \mu\text{F}$  (microfarad) with air filled in the gap between the plates. Now, exactly one-half of the space between the plates is filled with a dielectric of dielectric constant 4, as shown in the figure. The capacity of the capacitor changes to :



- $25 \mu\text{F}$
  - $20 \mu\text{F}$
  - $40 \mu\text{F}$
  - $5 \mu\text{F}$
- Two large metal plates are placed parallel to each other. The inner surfaces of plates are charged by  $+\sigma$  and  $-\sigma \text{ C/m}^2$ . The electric field between the plates and outside the plates :




- $\sigma/2\epsilon_o, \sigma/\epsilon_o$
- $\sigma/\epsilon_o, 0$
- $\sigma/2\epsilon_o, 0$
- $2\sigma/\epsilon_o, \sigma/\epsilon_o$


---

\* Academy Of Physics.

5. Two identical capacitors  $C_1$  and  $C_2$  (equal in value) are connected in series with a battery of *e.m.f*  $V_o$ . They are fully charged. Now, a dielectric slab is inserted between the plates of  $C_2$ . The potential diff. across  $C_1$  will :
- a) Increase  
b) Decrease  
c) Remains Same  
d) Depends on internal resistance of the cell
6. A smooth parabolic wire track lies in the vertical plane ( $x - y$  plane). The shape of track is defined by the equation  $y = x^2/a$  (where  $a$  is constant). A bead of mass  $m$  which can slide freely on the wire track, is placed at the position  $A(a, a)$ . The track is rotated with constant angular speed  $\omega$  about  $y - axis$ , such that there is no relative slipping between the ring and the track. Then  $\omega$  is equal to :
- a)  $\sqrt{g/a}$   
b)  $\sqrt{2g/a}$   
c)  $\sqrt{g/2a}$   
d)  $\sqrt{\sqrt{2}g/a}$
7. A uniform circular ring of mass per unit length  $\lambda$  and radius  $R$  is rotating with angular velocity  $\omega$  about its own axis in a gravity free space. Tension in the ring is :
- a) Zero  
b)  $\lambda \omega^2 R^2/2$   
c)  $\lambda \omega^2 R^2$   
d)  $2\lambda \omega^2 R^2$
8. A chain of mass per unit length  $\lambda$  and length  $1.5 m$  rests on a fixed smooth sphere of radius  $R = (2/\pi) m$  such that end  $A$  of chain is at the top of sphere while the other end is hanging freely as shown. The chain is held stationary by a horizontal thread  $PA$ . The tension in this thread is :




- a)  $\lambda g \left( \frac{1}{2} + \frac{2}{\pi} \right)$   
b)  $\lambda g \left( \frac{\pi}{2} + \frac{2}{\pi} \right)$   
c)  $\lambda g \left( \frac{2}{\pi} \right)$   
d) None of These
9. An ideal gas with adiabatic exponent  $\gamma = 2$  goes through a cycle as shown in figure, in which absolute temperature varies  $\tau = 4$  times. Find efficiency of this cycle :




- a)  $\frac{1}{9}$   
b)  $\frac{1}{8}$   
c)  $\frac{1}{6}$   
d)  $\frac{1}{5}$

10. The potential energy of a  $4\text{ kg}$  particle free to move along the  $x$ -axis is given by  $U(x) = \frac{x^3}{3} - \frac{5x^2}{2} + 6x + 3$ . Total mechanical energy of the particle is  $17J$ . Then the maximum kinetic energy is :
  - a)  $10 J$
  - b)  $2 J$
  - c)  $9.5 J$
  - d)  $0.5 J$
11. If a mercury droplet of radius  $R$  and surface tension  $S$  is broken into 8 smaller droplets of equal size. Then the work done by the external agency is :
  - a)  $\frac{4}{3}\pi R^3 S$
  - b)  $\pi R^2 S$
  - c)  $8\pi R^2 S$
  - d)  $4\pi R^2 S$
12. If  $n$  drops of a liquid, each with surface energy  $E$ , join to form a single drop then :
  - a) energy released in the process will be  $E(n - n^{1/3})$
  - b) energy absorbed in the process will be  $E(n - n^{1/3})$
  - c) energy released in the process will be  $E(n - n^{2/3})$
  - d) energy absorbed in the process will be  $E(n - n^{2/3})$
13. A soap bubble of radius  $R$  is surrounded by another soap bubble of radius  $2R$ , as shown. If surface tension =  $S$ , then the pressure inside the smaller soap bubble, in excess of the atmospheric pressure, will be :







## Atmosphere

- a)  $4S/R$   
c)  $6S/R$
- b)  $3S/R$   
d) *None of these*
14. Two soap bubbles of radii  $R_1$  and  $R_2$  equal to  $4\text{ cm}$  and  $5\text{ cm}$  are touching each other over a common surface  $S_1 S_2$  (shown in figure). Radius of the common surface will be :




- a) 4 cm    b) 20 cm  
c) 5 cm    d) 4.5 cm
15. Graph between the mass of liquid inside the capillary and the radius of capillary :






16. A particle of mass  $2\text{ kg}$  moves in a straight line. If  $v$  is the velocity at a distance  $x$  from a fixed point on the line and  $v^2 = 3 - 4x^2$ , then :
- a) The motion continues along  $+x$ -direction only      b) The graph of  $v$  versus  $x$  would be a straight line  
 c) The angular frequency of oscillation is  $4\text{ rad/s}$       d) The total energy of oscillation is  $3\text{ J}$
17. A particle moves along the  $z$ -axis according to the equation  $z = 5 + 12 \cos\left(2\pi t + \frac{\pi}{2}\right)$ , where  $z$  is in  $\text{cm}$  and  $t$  is in seconds. Select the correct alternative :
- a) The motion of the particle is SHM with mean position at  $z = 12\text{ cm}$       b) The motion of the particle is SHM with one extreme position as  $-7\text{ cm}$   
 c) The motion of the particle is Oscillatory but not SHM      d) Amplitude of SHM is  $17\text{ cm}$
18. The amplitude of a particle in SHM is  $5\text{ cm}$  and its time period is  $\pi$ . At a displacement of  $3\text{ cm}$  from its mean position the velocity in  $\text{cm/sec}$  will be :
- a) 8      b) 12  
 c) 2      d) 16
19. At a particular position the velocity of a particle in SHM with amplitude  $A$  is  $\sqrt{3}/2$  of that at its mean position. In this position, its displacement is :
- a)  $A/2$       b)  $\sqrt{3}A/2$   
 c)  $A/\sqrt{2}$       d)  $\sqrt{2}A$
20. If the maximum velocity of a particle in SHM is  $v_o$ , then its velocity at half the amplitude from position of rest will be :
- a)  $v_o/2$       b)  $v_o$   
 c)  $v_o\sqrt{3}/2$       d)  $v_o\sqrt{3}/2$
21. The velocities of a particle executing S.H.M. are  $30\text{ cm/s}$  and  $16\text{ cm/s}$  when its displacements are  $8\text{ cm}$  and  $15\text{ cm}$  from the equilibrium position. Then its amplitude of oscillation in  $\text{cm}$  is :
- a) 25      b) 21  
 c) 17      d) 13
22. The figure shows two coherent microwave sources  $S_1$  and  $S_2$  emitting waves of wavelength  $\lambda$  and separated by a distance  $3\lambda$ . The minimum non-zero value of  $y$  for point  $P$  to be an intensity maximum is ( $D \gg \lambda$ ) :









- a)  $\sqrt{2}$                       b) 4  
c)  $4\sqrt{2}$                       d) 2

27. A solid sphere of mass  $2 \text{ kg}$  and radius  $1 \text{ m}$  is moving on a smooth ground with linear velocity  $v_o = 4 \text{ m/s}$  and angular velocity  $\omega_o = 9 \text{ rad/s}$  as shown in figure. It collides elastically with a rough wall of coefficient of friction  $\mu$  and after collision with the wall rolls without slipping in opposite direction. Find the coefficient of friction  $\mu$  :




- a)  $\frac{3}{4}$                       b)  $\frac{3}{5}$   
c)  $\frac{1}{4}$                       d)  $\frac{1}{2}$

28. The disc rolls without slipping on a smooth horizontal surface as shown. The speed of the centre  $C$  is  $v$ . The speed of point  $A$  on the disc at the instant shown is :




- a)  $v$                       b)  $v \cos \theta$   
c)  $\sqrt{2}v$                       d)  $v \sec \theta$

29. A small sphere of mass  $1 \text{ kg}$  is rolling without slipping with linear speed  $v = \sqrt{\frac{200}{7}} \text{ m/s}$ . It leaves the inclined plane at point  $C$ . Find the kinetic energy at the top just before leaving the inclined plane, neglecting any impact at  $B$  and assuming no slipping anywhere :



- a)  $20 \text{ J}$                       b)  $100/7 \text{ J}$   
c)  $10 \text{ J}$                       d)  $15 \text{ J}$

30. Initial angular velocity of the system shown is  $\omega_o$  and frame length is  $a$ . System is rotating about the vertical axle and frame has negligible mass compared to the four point masses each of mass  $m$ . Due to an internal mechanism the spokes in the frame lengthen to  $2a$ . Find new angular velocity of the system :



- a)  $\omega_0$   
c)  $\frac{\omega_0}{2}$
- b)  $\frac{3\omega_0}{4}$   
d)  $\frac{\omega_0}{4}$





31. A current in circuit is given by  $i = 3 + 4 \sin \omega t$ . Then the effective value of current is :

- |                |                |
|----------------|----------------|
| a) 5           | b) $\sqrt{7}$  |
| c) $\sqrt{17}$ | d) $\sqrt{10}$ |

32. The incorrect statement is :

- a) A.C. meters can be used to measure D.C.                      b) D.C. meters cannot be used to measure A.C.
- c) A.C. and D.C. meters are based on the heating effect of current                      d) A.C. meter reads rms value of current

33. If  $I_1, I_2, I_3$  and  $I_4$  are the respective r.m.s. values of the time-varying currents as shown in the four cases I, II, III, and IV. Then identify the correct relations :



- a)  $I_1 = I_2 = I_3 = I_4$                       b)  $I_3 > I_1 = I_2 > I_4$   
c)  $I_3 > I_4 > I_2 = I_1$                       d)  $I_3 > I_2 > I_1 > I_4$

34. The effective value of current  $i = 2 \sin 100\pi t + 2 \sin(100\pi t + 30^\circ)$  is :

- a)  $\sqrt{2}$  A                      b)  $2\sqrt{2} + \sqrt{3}$  A  
c) 4 A                          d) None

35. If  $I = 2\sqrt{t}$  ampere then calculate rms values over  $t = 2$  to  $4$  s :

- a)  $\frac{\sqrt{3}}{2}$                       b)  $2\sqrt{3}$   
c)  $\sqrt{3}$                       d)  $4\sqrt{3}$

36. In an AC circuit an alternating voltage  $\varepsilon = 200\sqrt{2}\sin 100t$  volts is connected to a capacitor of capacity  $1\mu F$ . The r.m.s. value of the current in the circuit is :

- a) 10 mA
- b) 100 mA
- c) 200 mA
- d) 20 mA

37. In an AC circuit containing a pure capacitor, across which an AC emf  $\varepsilon = 100 \sin(1000t)$  volt is applied. If the peak value of the current is 200 mA, then the value of the capacitor is :

- a)  $2 \mu F$
- b)  $20 \mu F$
- c)  $5 \mu F$
- d)  $500 \mu F$

38. A student connects a long air cored – coil of manganin wire to a 100 V D.C. supply and records a current of 25 amp. When the same coil is connected across 100 V, 50 Hz a.c. the current reduces to 20 A. The reactance of the coil is :

- a)  $4 \Omega$
- b)  $3 \Omega$
- c)  $5 \Omega$
- d) None

39. In a purely inductive circuit, the applied voltage  $V = 50\sqrt{2} \sin(100 \pi t)$  volt and ammeter reading is 2A then calculate value of  $L$  :

- a)  $\frac{1}{2\pi} H$
- b)  $\frac{1}{4\pi} H$
- c)  $\frac{1}{\pi} H$
- d) None

40. If the power factor of an R-L series circuit is  $\frac{1}{2}$  when applied voltage is  $V = 100 \sin(100\pi t)$  volt and resistance of circuit is  $200 \Omega$ , then calculate the inductance of the circuit :

- a)  $2\sqrt{3}\pi H$
- b)  $\frac{2\sqrt{3}}{\pi} H$
- c)  $\frac{\pi}{2\sqrt{3}} H$
- d)  $\frac{\sqrt{3}}{2\pi} H$