

# LAB2

## 1. Configure apache to use Worker MPM

```
• (base) eslam@eslam-Latitude-E7450:/etc/apache2$ apache2ctl -M | grep mpm
AH00558: apache2: Could not reliably determine the server's fully qualified domain name, using 127.0.1.1. Set
the 'ServerName' directive globally to suppress this message
mpm_event_module (shared)
• (base) eslam@eslam-Latitude-E7450:/etc/apache2$ sudo a2dismod mpm_event
[sudo] password for eslam:
Module mpm_event disabled.
To activate the new configuration, you need to run:
systemctl restart apache2
• (base) eslam@eslam-Latitude-E7450:/etc/apache2$ systemctl restart apache2
• (base) eslam@eslam-Latitude-E7450:/etc/apache2$ sudo a2enmod mpm_worker
Considering conflict mpm_event for mpm_worker:
Considering conflict mpm_prefork for mpm_worker:
Module mpm_worker already enabled
• (base) eslam@eslam-Latitude-E7450:/etc/apache2$ apache2ctl -M | grep mpm
AH00558: apache2: Could not reliably determine the server's fully qualified domain name, using 127.0.1.1. Set
the 'ServerName' directive globally to suppress this message
mpm_worker_module (shared)
○ (base) eslam@eslam-Latitude-E7450:/etc/apache2$
```

check the status of `rewrite_mod` and enable it if it is disabled.


```
• (base) eslam@eslam-Latitude-E7450:/etc/apache2$ apache2ctl -M | grep rewrite
AH00558: apache2: Could not reliably determine the server's fully qualified domain name, using 127.0.1.1. Set
the 'ServerName' directive globally to suppress this message
rewrite_module (shared)
○ (base) eslam@eslam-Latitude-E7450:/etc/apache2$
```

3. Write RewriteCond and RewriteRules for:
  - a. Deny access to `http://localhost/page?queryString` if `queryString` contains the string `forbidden`.

```

32
33 #lap2
34
35 RewriteEngine on #important
36
37 #Q3.a
38
39 RewriteCond %{QUERY_STRING} forbidden
40 RewriteRule .+ - [F]
41

```



## Forbidden

You don't have permission to access this resource.

Apache/2.4.58 (Ubuntu) Server at 192.168.1.7 Port 80


## b. Remove the Query String

```

#Q3.b

RewriteCond %{QUERY_STRING} (state)=(.+)
RewriteRule ^/TASKS/(.+)/(.+) /TODO/$2/$1/%2.html? [R]

```




## Not Found

The requested URL was not found on this server.

Apache/2.4.58 (Ubuntu) Server at 192.168.1.7 Port 80


- c. Rewrite URLs like `http://localhost/page1?var=val` to `http://localhost/page2?var=val` but do not rewrite if `val` isn't present.

```
46  
47 #Q3.c  
48 RewriteCond %{QUERY_STRING} (.+)=(.+)  
49 RewriteRule ^/page1 /page2?%1=%2 [R]  
50  
51
```



- d. Take a URL of the form <http://localhost/path?var=val> and transform it into <http://localhost/path/var/val>.

```
51  
52 #Q3.d  
53 RewriteCond %{QUERY_STRING} (.+)=(.+)  
54 RewriteRule ^/page1 /page2/%1/%2? [R]  
55  
56
```



- e. Map <http://localhost/example/one/two> to <http://localhost/something.cgiarg=one&otho>

```
55  
56 #Q3.e  
57 RewriteRule ^/(.+)/(.+)/(.+)$ /something.cgi?arg=$2&other=$3 [R]  
58  
59  
60
```




f. **(Bonus)** Display a goodevening.html page if the time is after 6:00 PM and

g

```
#Bounse  
RewriteCond %{TIME_HOUR} >=18  
RewriteRule .+ /bouns/goodevening.html [L]  
  
RewriteCond %{TIME_HOUR} <18  
RewriteRule .+ /bouns/goodmooring.html [L]
```

ng.html page if the time is before that



**Good Morning!**