

Make Down API — Mobile Endpoint Reference

Customer-facing endpoints used by the mobile app and website: auth, schools, live game engine, profile, store and packages.

Generated from the live Swagger/JSdoc source in makedown-api. Base URL: <https://back.makedown.online/api> (see /swagger on the server for the interactive version).

Every response is wrapped the same way — success: { success: true, message, data }, error: { success: false, message, details? }. Check response.success (or the HTTP status code) before reading data . Some list-style fields (addresses, orders, packages) come back with raw database column names in snake_case rather than camelCase — this is called out where it applies.

Contents

Auth (9)

Schools (6)

Me (11)

Play (21)

Packages (6)

Orders (2)

Products (13)

Coupons (1)

Currency (1)

Game Categories (5)

Appendix — Data Types

Auth

Register, verify OTP, log in, refresh/revoke tokens, password reset.

POST /auth/register

no auth

Create a new account and send an email OTP

REQUEST BODY **REQUIRED** — APPLICATION/JSON

```
{
  "fullName": "Sara Al-Fahad",
  "email": "sara@example.com",
  "phone": "+96555512345",
  "password": ""
}
```

RESPONSES

201 Account created

```
{
  "success": true,
  "message": "",
  "data": {}
}
```

↳ derived from schema — illustrative shape, not a literal example

409 Email already registered

```
{
  "success": false,
  "message": "",
  "details": [
    ""
  ]
}
```

↳ derived from schema — illustrative shape, not a literal example

POST /auth/verify-otp

no auth

Verify an OTP code (email verification, password reset confirmation, etc.)

REQUEST BODY **REQUIRED** — APPLICATION/JSON

```
{
  "email": "",
  "code": "482913",
  "purpose": ""
}
```

RESPONSES

200 Verified. For purpose=register, returns an authenticated session.

```
{
  "success": true,
  "message": "",
  "data": {}
}
```

↳ derived from schema — illustrative shape, not a literal example

400 Invalid or expired code

```
{
  "success": false,
  "message": "",
  "details": [
    ""
  ]
}
```

↳ derived from schema — illustrative shape, not a literal example

POST /auth/resend-otp

no auth

Resend an OTP code

REQUEST BODY **REQUIRED** — APPLICATION/JSON

```
{
  "email": "",
  "purpose": ""
}
```

RESPONSES

200 Sent if the account exists

```
{
  "success": true,
  "message": "",
  "data": {}
}
```

↳ derived from schema — illustrative shape, not a literal example

POST /auth/login

no auth

Log in with email and password

REQUEST BODY **REQUIRED** — APPLICATION/JSON

```
{
  "email": "",
  "password": "",
  "rememberMe": false
}
```

RESPONSES

200 Authenticated session

```
{
  "success": true,
  "message": "",
  "data": {
    "user": {
      "id": 0,
      "uuid": "",
      "fullName": "",
      "email": "",
      "phone": "",
      "avatarUrl": "",
      "emailVerified": false,
      "createdAt": "2026-01-01T00:00:00.000Z"
    },
    "accessToken": "",
    "refreshToken": ""
  }
}
```

↳ derived from schema — illustrative shape, not a literal example

401 Invalid credentials

```
{
  "success": false,
  "message": "",
  "details": [
    ""
  ]
}
```

↳ derived from schema — illustrative shape, not a literal example

403 Email not verified

```
{
  "success": false,
  "message": "",
  "details": [
    ""
  ]
}
```

↳ derived from schema — illustrative shape, not a literal example

POST /auth/refresh

no auth

Exchange a refresh token for a new access/refresh token pair

REQUEST BODY **REQUIRED** — APPLICATION/JSON

```
{
  "refreshToken": ""
}
```

RESPONSES

200 New session issued

401 Invalid or revoked refresh token

POST /auth/logout

no auth

Revoke a refresh token

REQUEST BODY **OPTIONAL** — APPLICATION/JSON

```
{
  "refreshToken": ""
}
```

RESPONSES

200 Logged out

POST /auth/forgot-password

no auth

Request a password reset OTP

REQUEST BODY **REQUIRED** — APPLICATION/JSON

```
{
  "email": ""
}
```

RESPONSES

200 Sent if the account exists

POST /auth/reset-password

no auth

Reset password using a valid OTP code

REQUEST BODY **REQUIRED** — APPLICATION/JSON

```
{
  "email": "",
  "code": "",
  "newPassword": ""
}
```

RESPONSES

200 Password reset

400 Invalid or expired code

GET /auth/me

 auth required

Get the current authenticated user's profile

RESPONSES

200 Current user

```
{
  "success": true,
  "message": "",
  "data": {
    "id": 0,
    "uuid": "",
    "fullName": "",
    "email": "",
    "phone": "",
    "avatarUrl": "",
    "emailVerified": false,
    "createdAt": "2026-01-01T00:00:00.000Z"
  }
}
```

↳ derived from schema — illustrative shape, not a literal example

401 Missing or invalid token

Schools

Public, unauthenticated browsing of schools and their open games. Joining a game is done through Play → POST /play/sessions/join with the code a teacher hands out — there is no separate "join school" endpoint.

GET /admin/schools

auth required

List schools

RESPONSES

200 List of schools

POST /admin/schools

auth required

Create a school

contactEmail and password are both required on create (password has no "current value" to fall back on for a brand-new school, and contactEmail is how it logs in) — omitting either is rejected with 400. contactEmail must also be unique across schools. isActive defaults to true when omitted, since an inactive school can't log in or appear on the public site.

REQUEST BODY **REQUIRED** — APPLICATION/JSON

```
{
  "nameEn": "",
  "nameAr": "",
  "contactEmail": "",
  "password": "",
  "contactPhone": "",
  "logoUrl": "",
  "address": "",
  "isActive": false
}
```

RESPONSES

201 Created

400 Missing/duplicate contactEmail, missing password, or password under 6 characters

PATCH /admin/schools/{id}

auth required

Update a school

password is optional here — leave it out to keep the school's current password. contactEmail, if sent, is still checked for uniqueness against other schools.

Param	In	Required	Type	Notes
id	path	yes	integer	

RESPONSES

200 Updated

DELETE /admin/schools/{id}

auth required

Delete a school

Param	In	Required	Type	Notes
id	path	yes	integer	

RESPONSES

200 Deleted

GET /schools

no auth

List active schools (public — the education "Schools" browsing page)

RESPONSES

200 List of active schools

```
{
  "success": true,
  "message": "OK",
  "data": [
    {
      "id": 4,
      "nameEn": "Al Manar International School",
      "nameAr": "مدرسة المنار العالمية",
      "logoUrl": "https://back.makedown.online/uploads/school-4.png"
    },
    {
      "id": 7,
      "nameEn": "Gulf British Academy",
      "nameAr": "أكاديمية الخليج البريطانية",
      "logoUrl": null
    }
  ]
}
```

List a school's currently open games (public — the "<School> Games" page)

Param	In	Required	Type	Notes
id	path	yes	integer	

RESPONSES

200 Open (waiting or active) games hosted by this school

```
{
  "success": true,
  "message": "OK",
  "data": [
    {
      "id": 91,
      "title": "Grade 6 Science Trivia",
      "titleAr": "مسابقة العلوم للمف السادس",
      "mode": "team",
      "audience": "mixed",
      "status": "waiting",
      "scheduledDate": "2026-10-01",
      "scheduledTime": "10:30:00",
      "teams": [
        {
          "name": "Team A",
          "capacity": 5
        },
        {
          "name": "Team B",
          "capacity": 5
        }
      ],
      "categories": [
        {
          "titleEn": "Science",
          "titleAr": "العلوم",
          "coverImageUrl": "https://back.makedown.online/uploads/science.png"
        }
      ]
    }
  ]
}
```

404 School not found or inactive

```
{
  "success": false,
  "message": "School not found"
}
```

Me

The logged-in player's own profile, avatar, saved addresses, product orders, purchased game-credit packages, and game history.

PATCH /me

 auth required

Update my profile info

Every field is optional — send only what changed. Omitted fields are left untouched.

REQUEST BODY OPTIONAL — APPLICATION/JSON

```
{
  "firstName": "Sara",
  "lastName": "Al-Fahad",
  "phone": "+96555512345",
  "avatarUrl": "https://back.makedown.online/uploads/avatar-3f2c1a.jpg",
  "bio": "Trivia night regular."
}
```

RESPONSES

200 Profile updated — returns the full updated profile

```
{
  "success": true,
  "message": "Profile updated",
  "data": {
    "id": 501,
    "uuid": "b6f2c8b0-9e2e-4f0a-8b8e-2b1a3e9c4a11",
    "fullName": "Sara Al-Fahad",
    "firstName": "Sara",
    "lastName": "Al-Fahad",
    "email": "sara@example.com",
    "phone": "+96555512345",
    "avatarUrl": null,
    "bio": "Trivia night regular.",
    "emailVerified": true,
    "createdAt": "2026-01-14T09:12:00.000Z"
  }
}
```

401 Missing or invalid access token

```
{
  "success": false,
  "message": "Unauthorized"
}
```

Upload a new profile picture

multipart/form-data with a single file field named "file" (PNG, JPG, WEBP or GIF, max 5MB). Saves the file, sets it as the account's avatarUrl, and returns the full updated profile — same shape as PATCH /me.

REQUEST BODY **REQUIRED** — MULTIPART/FORM-DATA

```
{
  "file": ""
}
```

RESPONSES

200 Avatar updated — returns the full updated profile

```
{
  "success": true,
  "message": "Avatar updated",
  "data": {
    "id": 501,
    "uuid": "b6f2c8b0-9e2e-4f0a-8b8e-2b1a3e9c4a11",
    "fullName": "Sara Al-Fahad",
    "firstName": "Sara",
    "lastName": "Al-Fahad",
    "email": "sara@example.com",
    "phone": "+96555512345",
    "avatarUrl": "https://back.makedown.online/uploads/avatar-3f2c1a.jpg",
    "bio": null,
    "emailVerified": true,
    "createdAt": "2026-01-14T09:12:00.000Z"
  }
}
```

400 No file, wrong type, or file too large**noFile**

```
{
  "success": false,
  "message": "No file uploaded"
}
```

tooLarge

```
{
  "success": false,
  "message": "Image is too large. Max size is 5MB."
}
```

badType

```
{
  "success": false,
  "message": "Unsupported image type. Use PNG, JPG, WEBP or GIF."
}
```

401 Missing or invalid access token

```
{
  "success": false,
```

```
"message": "Unauthorized"
}
```

POST /me/change-password

 auth required

Change my password

REQUEST BODY **REQUIRED** — APPLICATION/JSON

```
{
  "currentPassword": "",
  "newPassword": ""
}
```

RESPONSES

200 Password changed

```
{
  "success": true,
  "message": "Password changed",
  "data": {
    "changed": true
  }
}
```

400 Missing fields, newPassword too short, or currentPassword wrong

wrongCurrent

```
{
  "success": false,
  "message": "Current password is incorrect"
}
```

tooShort

```
{
  "success": false,
  "message": "newPassword must be at least 8 characters"
}
```

GET /me/addresses

auth required

List my saved addresses

RESPONSES

200 My addresses, default first

```
{
  "success": true,
  "message": "",
  "data": [
    {
      "id": 12,
      "user_id": 501,
      "label": "Home",
      "full_name": "Sara Al-Fahad",
      "phone": "+96555512345",
      "country": "Kuwait",
      "city": "Kuwait City",
      "area": "Salmiya",
      "block": "3",
      "street": "Street 12",
      "building": "44",
      "floor": "2",
      "apartment": "7",
      "is_default": 1,
      "created_at": "2026-01-01T00:00:00.000Z",
      "updated_at": "2026-01-01T00:00:00.000Z"
    }
  ]
}
```

↳ derived from schema — illustrative shape, not a literal example

POST /me/addresses

auth required

Add a saved address

REQUEST BODY **REQUIRED** — APPLICATION/JSON

```
{
  "label": "Home",
  "fullName": "Sara Al-Fahad",
  "phone": "+96555512345",
  "country": "",
  "city": "Kuwait City",
  "area": "Salmiya",
  "block": "3",
  "street": "Street 12",
  "building": "44",
  "floor": "2",
  "apartment": "7",
  "isDefault": false
}
```

RESPONSES

201 Address created

```
{
  "success": true,
  "message": "",
  "data": {
    "id": 12,
    "user_id": 501,
    "label": "Home",
    "full_name": "Sara Al-Fahad",
    "phone": "+96555512345",
    "country": "Kuwait",
    "city": "Kuwait City",
    "area": "Salmiya",
    "block": "3",
    "street": "Street 12",
    "building": "44",
    "floor": "2",
    "apartment": "7",
    "is_default": 1,
    "created_at": "2026-01-01T00:00:00.000Z",
    "updated_at": "2026-01-01T00:00:00.000Z"
  }
}
```

↳ derived from schema — illustrative shape, not a literal example

400 fullName or phone missing

```
{
  "success": false,
  "message": "fullName and phone are required"
}
```

PATCH /me/addresses/{id}

auth required

Update a saved address

Param	In	Required	Type	Notes
id	path	yes	integer	

REQUEST BODY OPTIONAL — APPLICATION/JSON

```
{}
```

RESPONSES

200 Address updated

```
{
  "success": true,
  "message": "",
  "data": {
    "id": 12,
    "user_id": 501,
    "label": "Home",
    "full_name": "Sara Al-Fahad",
    "phone": "+96555512345",
    "country": "Kuwait",
    "city": "Kuwait City",
    "area": "Salmiya",
    "block": "3",
    "street": "Street 12",
    "building": "44",
    "floor": "2",
    "apartment": "7",
    "is_default": 1,
    "created_at": "2026-01-01T00:00:00.000Z",
    "updated_at": "2026-01-01T00:00:00.000Z"
  }
}
```

↳ derived from schema — illustrative shape, not a literal example

404 Address doesn't exist or belongs to another account

```
{
  "success": false,
  "message": "Address not found"
}
```

DELETE /me/addresses/{id}

 auth required

Delete a saved address

Param	In	Required	Type	Notes
id	path	yes	integer	

RESPONSES

200 Address deleted

```
{
  "success": true,
  "message": "Deleted",
  "data": null
}
```

404 Address doesn't exist or belongs to another account

```
{
  "success": false,
  "message": "Address not found"
}
```

List my product orders (paginated)

Param	In	Required	Type	Notes
page	query	no	integer	
pageSize	query	no	integer	

RESPONSES

200 Paginated list of my orders

```
{
  "success": true,
  "message": "",
  "data": {
    "rows": [
      {
        "id": 233,
        "order_number": "MD-20261001-0233",
        "status": "processing",
        "payment_status": "paid",
        "payment_method": "knet",
        "subtotal": "12.500",
        "discount_total": "0.000",
        "shipping_total": "1.500",
        "grand_total": "14.000",
        "currency": "KWD",
        "coupon_code": "WELCOME10",
        "notes": null,
        "created_at": "2026-01-01T00:00:00.000Z",
        "updated_at": "2026-01-01T00:00:00.000Z"
      }
    ],
    "total": 42,
    "page": 1,
    "pageSize": 20
  }
}
```

↳ derived from schema — illustrative shape, not a literal example

GET /me/orders/{id}

auth required

Get one of my orders with its line items

Param	In	Required	Type	Notes
id	path	yes	integer	

RESPONSES

200 Order detail

```
{
  "success": true,
  "message": "",
  "data": {
    "id": 233,
    "order_number": "MD-20261001-0233",
    "status": "processing",
    "payment_status": "paid",
    "payment_method": "knet",
    "subtotal": "12.500",
    "discount_total": "0.000",
    "shipping_total": "1.500",
    "grand_total": "14.000",
    "currency": "KWD",
    "coupon_code": "WELCOME10",
    "notes": "",
    "created_at": "2026-01-01T00:00:00.000Z",
    "updated_at": "2026-01-01T00:00:00.000Z",
    "items": [
      {
        "id": 501,
        "product_id": 9,
        "variant_id": 22,
        "product_name_snapshot": "Trivia Royale Starter Pack",
        "quantity": 2,
        "unit_price": "6.250",
        "line_total": "12.500",
        "thumbnail_url": "https://back.makedown.online/uploads/product-9.jpg",
        "attributes_json": {
          "color": "Red",
          "size": "M"
        }
      }
    ]
  }
}
```

↳ derived from schema — illustrative shape, not a literal example

404 Not your order, or it doesn't exist

```
{
  "success": false,
  "message": "Order not found"
}
```

GET /me/packages

auth required

List packages I've purchased (current + history)

RESPONSES

200 My purchased packages, most recent first

```
{
  "success": true,
  "message": "",
  "data": [
    {
      "id": 88,
      "package_id": 3,
      "order_id": 233,
      "credits_remaining": 4,
      "purchased_at": "2026-01-01T00:00:00.000Z",
      "expires_at": "2026-01-01T00:00:00.000Z",
      "status": "active",
      "package_name_en": "5-Game Pack",
      "package_name_ar": "باقة 5 ألعاب",
      "package_credits": 5,
      "package_free_credits": 0
    }
  ]
}
```

↳ derived from schema — illustrative shape, not a literal example

List games I've played (paginated)

Param	In	Required	Type	Notes
page	query	no	integer	
pageSize	query	no	integer	

RESPONSES

200 Paginated game history

```
{
  "success": true,
  "message": "",
  "data": {
    "rows": [
      {
        "sessionId": 91,
        "mode": "team",
        "status": "finished",
        "startedAt": "2026-01-01T00:00:00.000Z",
        "endedAt": null,
        "participants": null,
        "teams": null,
        "quizzes": null,
        "lifelinesUsed": null
      }
    ],
    "total": 42,
    "page": 1,
    "pageSize": 20
  }
}
```

↳ derived from schema — illustrative shape, not a literal example

Play

The live multiplayer game engine: create/join a game, pick tiles off the points board, answer, lifelines, invites. Most of this is also mirrored over Socket.io for real-time updates — see the note under each endpoint.

GET

/play/quizzes

no auth

List quizzes (categories) that have at least one question, for board selection

Param	In	Required	Type	Notes
category_id	query	no	integer	
mode	query	no	string	Only return quizzes the admin marked as supporting this mode (or 'both')

RESPONSES

200

List of quizzes



POST /play/sessions auth required**Create a game (host) — pick mode + categories, get a join code**REQUEST BODY **REQUIRED** — APPLICATION/JSON

```
{
  "mode": "team",
  "quizIds": [
    12,
    15,
    19
  ],
  "title": "Grade 6 Science Trivia",
  "isPublic": false,
  "maxPlayers": 0,
  "team1Name": "Team A",
  "team2Name": "Team B",
  "team1Players": [
    "Ali",
    "Reem"
  ],
  "team2Players": [
    "Fatima"
  ]
}
```

RESPONSES

201 Game created — the host is participant

```
{
  "success": true,
  "message": "",
  "data": {
    "id": 91,
    "title": "Grade 6 Science Trivia",
    "host_user_id": 501,
    "school_id": 4,
    "mode": "team",
    "is_public": 0,
    "max_players": 0,
    "join_code": "7F3KQ2",
    "qr_code_url": "...",
    "status": "waiting",
    "current_turn_index": 0,
    "current_question_id": 0,
    "turn_started_at": "2026-01-01T00:00:00.000Z",
    "turn_ends_at": "2026-01-01T00:00:00.000Z",
    "started_at": "2026-01-01T00:00:00.000Z",
    "ended_at": "2026-01-01T00:00:00.000Z",
    "created_at": "2026-01-01T00:00:00.000Z",
    "turnOrder": [
      0
    ],
    "currentTurnParticipantId": 0,
    "currentQuestion": {},
    "awaitingScan": false,
    "participants": [
      {
        "id": 0,
        "user_id": 0,

```

```
    "guest_name": "",
    "team_id": 0,
    "score": 0,
    "full_name": "",
    "avatar_url": ""
  }
],
"teams": [
  {
    "id": 0,
    "name": "",
    "color": "",
    "score": 0
  }
],
"board": [
  {}
]
}
```

↳ derived from schema — illustrative shape, not a literal example

400 No category selected, or team names missing for team mode

```
{
  "success": false,
  "message": "Select at least one category"
}
```

402 Free game already used and no active package

```
{
  "success": false,
  "message": "You've used your free game. Subscribe to a package to keep playing."
}
```

POST /play/sessions/join auth required**Join a game by its join code**

Consumes the joining player's free game / package credit — unless the session is school-hosted (schools/game-sessions.controller.js "Create Game"), in which case joining is free for the player; the school hosts the event, so a student shouldn't burn their own credit to attend it. A school's own join code (from its "My Games") works the same way here as any other game's — there's no separate endpoint for it, and it's never returned by GET /schools/{id}/games (a teacher hands it out separately, outside the app). A school-scheduled game (scheduledDate/scheduledTime set) only opens 10 minutes before its start time — joining earlier than that with an otherwise-valid code returns 400, not 404.

REQUEST BODY **REQUIRED** — APPLICATION/JSON

```
{
  "joinCode": "7F3KQ2"
}
```

RESPONSES

200 Joined — returns full game state

```
{
  "success": true,
  "message": "Joined",
  "data": {
    "id": 91,
    "title": "Grade 6 Science Trivia",
    "host_user_id": 501,
    "school_id": 4,
    "mode": "team",
    "is_public": 0,
    "join_code": "7F3KQ2",
    "status": "waiting",
    "current_turn_index": 0,
    "current_question_id": null,
    "awaitingScan": false,
    "turnOrder": [],
    "currentTurnParticipantId": null,
    "currentQuestion": null,
    "participants": [],
    "teams": [],
    "board": []
  }
}
```

400 Game not joinable right now (e.g. a scheduled school game that hasn't opened yet)

```
{
  "success": false,
  "message": "This game opens 10 minutes before its start time (10:30)."
}
```

402 No game credits remaining (not applicable to school-hosted sessions)

```
{
  "success": false,
  "message": "You've used your free game. Subscribe to a package to keep playing."
}
```

404 Invalid join code

```
{
  "success": false,
  "message": "No game found with that code"
}
```

409 The session is full, or has already started/finished (mapped from SESSION_FULL / SESSION_NOT_JOINABLE)

full

```
{
  "success": false,
  "message": "session full"
}
```

notJoinable

```
{
  "success": false,
  "message": "session not joinable"
}
```

GET /play/sessions/public

 auth required

Browse public "random" games open for matchmaking

RESPONSES

200 List of public waiting games

GET /play/sessions/{id}

 auth required

Get full game state (lobby / live board / scores)

Poll this (or listen for the `game:state` Socket.io event, same shape) to keep the lobby/live screen in sync between actions.

Param	In	Required	Type	Notes
id	path	yes	integer	

RESPONSES

200 Full game state

```
{
  "success": true,
  "message": "",
  "data": {
    "id": 91,
    "title": "Grade 6 Science Trivia",
    "host_user_id": 501,
    "school_id": 4,
    "mode": "team",
    "is_public": 0,
    "max_players": 0,
    "join_code": "7F3KQ2",
    "qr_code_url": "...",
    "status": "waiting",
    "current_turn_index": 0,
    "current_question_id": 0,
    "turn_started_at": "2026-01-01T00:00:00.000Z",
    "turn_ends_at": "2026-01-01T00:00:00.000Z",
    "started_at": "2026-01-01T00:00:00.000Z",
    "ended_at": "2026-01-01T00:00:00.000Z",
    "created_at": "2026-01-01T00:00:00.000Z",
    "turnOrder": [
      0
    ],
    "currentTurnParticipantId": 0,
    "currentQuestion": {},
    "awaitingScan": false,
    "participants": [
      {
        "id": 0,
        "user_id": 0,
        "guest_name": "",
        "team_id": 0,
        "score": 0,
        "full_name": "",
        "avatar_url": ""
      }
    ],
    "teams": [
      {
        "id": 0,
        "name": "",
        "color": "",
        "score": 0
      }
    ],
    "board": [
      {}
    ]
  }
}
```

```
]
}
}
```

↳ derived from schema — illustrative shape, not a literal example

404 Session doesn't exist

```
{
  "success": false,
  "message": "Game not found"
}
```

POST /play/sessions/{id}/start

🔒 auth required

Host starts the game

RESPONSES

200 Started

POST /play/sessions/{id}/leave

🔒 auth required

Leave a game

RESPONSES

200 Left

POST /play/sessions/{id}/match-random

🔒 auth required

Start Play With Random User — join an existing open public game or open this one for matching

RESPONSES

200 Matched

POST /play/sessions/{id}/pick-tile

auth required

Current-turn player picks a category + point tile from the board

Param	In	Required	Type	Notes
id	path	yes	integer	

REQUEST BODY **REQUIRED** — APPLICATION/JSON

```
{
  "questionId": 305
}
```

RESPONSES

200 Tile opened. For a text/image question, awaitingScan is false and timeLimitSeconds is the answer window that already started. For a qr/audio question, awaitingScan is true and nothing starts until /scan or /reveal is called — for qr, scanUrl/scanQrDataUrl are also included so the mobile app can show a real QR code, not just a URL.

textOrImage

```
{
  "success": true,
  "message": "OK",
  "data": {
    "question": {
      "id": 305,
      "question_type": "text",
      "question_text_en": "Capital of Japan?",
      "options_json_en": "[\"Tokyo\", \"Osaka\", \"Kyoto\", \"Nagoya\"]",
      "points": 200
    },
    "awaitingScan": false,
    "timeLimitSeconds": 20
  }
}
```

qr

```
{
  "success": true,
  "message": "OK",
  "data": {
    "question": {
      "id": 306,
      "question_type": "qr",
      "points": 400
    },
    "awaitingScan": true,
    "scanToken": "9f1c...",
    "scanUrl": "https://www.makedown.online/play/scan/91/9f1c...",
    "scanQrDataUrl": "..."
  }
}
```

403 Not this player's turn

```
{
  "success": false,
```

```
"message": "not your turn"
}
```

409 A tile is already open

```
{
  "success": false,
  "message": "tile already in progress"
}
```

POST /play/sessions/{id}/scan

 auth required

Confirm the QR code was scanned for a QR-gated question, starting its timer

Called from the scan-confirmation page a second device opens — see GET-by-link flow at /play/scan/{sessionId}/{token} on the website. Can be called any number of times with the same token.

Param	In	Required	Type	Notes
id	path	yes	integer	

REQUEST BODY **REQUIRED** — APPLICATION/JSON

```
{
  "token": ""
}
```

RESPONSES

200 Question revealed

```
{
  "success": true,
  "message": "OK",
  "data": {
    "question": {
      "id": 306,
      "question_type": "qr"
    },
    "timeLimitSeconds": 20
  }
}
```

400 Wrong/expired token

```
{
  "success": false,
  "message": "invalid scan token"
}
```

POST /play/sessions/{id}/reveal

auth required

Reveal an audio question after its clip finished playing, starting its timer (no scan token needed)

Param	In	Required	Type	Notes
id	path	yes	integer	

RESPONSES

200 Question revealed

```
{
  "success": true,
  "message": "OK",
  "data": {
    "question": {
      "id": 307,
      "question_type": "audio"
    },
    "timeLimitSeconds": 20
  }
}
```

409 No audio question is currently awaiting reveal

```
{
  "success": false,
  "message": "no active question"
}
```

POST /play/sessions/{id}/answer

auth required

Submit an answer for the active tile (text/image/audio — not qr, see qr-answer)

Param	In	Required	Type	Notes
id	path	yes	integer	

REQUEST BODY **REQUIRED** — APPLICATION/JSON

```
{
  "questionId": 305,
  "selectedOptionIndex": 0,
  "timeTakenMs": 4200
}
```

RESPONSES

200 Whether the pick was right. In team mode, when a first team just answers, the fuller game:answer_result / game:next_team_turn Socket.io events (not this HTTP response) carry whether the tile is fully settled yet.

```
{
  "success": true,
  "message": "OK",
  "data": {
    "isCorrect": true,
    "correctOptionIndex": 0
  }
}
```

409 Awaiting a qr/audio reveal first, time already expired, or no active question

awaitingScan

```
{
  "success": false,
  "message": "awaiting scan"
}
```

timeExpired

```
{
  "success": false,
  "message": "time expired"
}
```

POST /play/sessions/{id}/qr-answer auth required

Host-only: grade a QR-gated question — pick which team (participantId) answered correctly, or none, settling the tile

Param	In	Required	Type	Notes
id	path	yes	integer	

REQUEST BODY **REQUIRED** — APPLICATION/JSON

```
{
  "questionId": 306,
  "winnerParticipantId": 812
}
```

RESPONSES

200 Tile settled

```
{
  "success": true,
  "message": "OK",
  "data": {
    "winnerParticipantId": 812,
    "points": 400
  }
}
```

403 Caller isn't this game's host

```
{
  "success": false,
  "message": "not host"
}
```

POST /play/sessions/{id}/lifelines/fifty-fifty auth required

Use the 50/50 lifeline (once per game) — hides two wrong options

RESPONSES

200 Options to hide**POST** /play/sessions/{id}/lifelines/skip auth required

Use the Skip lifeline (once per game) — passes the tile with no score

RESPONSES

200 Skipped

POST /play/sessions/{id}/lifelines/phone-a-friend

 auth required

Use the Phone-a-Friend lifeline (once per game) — pings another participant live

RESPONSES

 **200** Friend notified

POST /play/lifeline-requests/{requestId}/respond

 auth required

The pinged friend suggests an answer back to the requester

RESPONSES

 **200** Sent

GET /play/sessions/{id}/invite-search

 auth required

Search users by name to invite into the game

RESPONSES

 **200** Matching users

POST /play/sessions/{id}/invite

 auth required

Send an invite to a user

RESPONSES

 **201** Invited

POST /play/invites/{inviteId}/respond

 auth required

Accept or decline an invite

RESPONSES

 **200** Responded

POST /play/sessions/{id}/score-adjustment

 auth required

Host manually adjusts a participant's score (+/- controls on the board)

RESPONSES

 **200** Adjusted

Packages

Game-credit packages available for purchase.

GET /admin/packages

 auth required

List packages

RESPONSES

200 List

POST /admin/packages

 auth required

Create a package

RESPONSES

201 Created

PATCH /admin/packages/{id}

 auth required

Update a package

Param	In	Required	Type	Notes
id	path	yes	integer	

RESPONSES

200 Updated

DELETE /admin/packages/{id}

 auth required

Delete a package

Param	In	Required	Type	Notes
id	path	yes	integer	

RESPONSES

200 Deleted

GET /packages

no auth

List active packages (public)

RESPONSES

200 List of packages

POST /packages/{id}/purchase

 auth required

Buy a package (requires login)

Param	In	Required	Type	Notes
id	path	yes	integer	

REQUEST BODY **REQUIRED** — APPLICATION/JSON

```
{
  "paymentMethod": ""
}
```

RESPONSES

201 For cash, the package is granted immediately. For knet/credit_card, returnUrl is a MyFatoorah hosted payment page.

Orders

Placing and tracking product orders (the merch/store side of the app).

POST /orders

no auth

Place an order (checkout) — works for a logged-in user or a guest

REQUEST BODY **REQUIRED** — APPLICATION/JSON

```
{
  "items": [
    {
      "productId": 0,
      "variantId": 0,
      "quantity": 0
    }
  ],
  "shippingAddress": {},
  "paymentMethod": "",
  "discountCode": "",
  "guestName": "",
  "guestEmail": "",
  "guestPhone": ""
}
```

RESPONSES

- 201** Order placed
- 400** Validation error

GET /orders/track/{orderNumber}

no auth

Look up an order by its order number (public — the order-confirmation page, including after a MyFatoorah redirect)

Param	In	Required	Type	Notes
orderNumber	path	yes	string	

RESPONSES

- 200** Order with items
- 404** Not found

Products

Browsing the product catalog.

GET /admin/products

auth required

List products

RESPONSES

200 Paginated list

POST /admin/products

auth required

Create a product

RESPONSES

201 Created

GET /admin/products/{id}

auth required

Get a product with its variants and images

Param	In	Required	Type	Notes
id	path	yes	integer	

RESPONSES

200 Product detail

PATCH /admin/products/{id}

auth required

Update a product

Param	In	Required	Type	Notes
id	path	yes	integer	

RESPONSES

200 Updated

DELETE /admin/products/{id}

auth required

Delete a product

Param	In	Required	Type	Notes
id	path	yes	integer	

RESPONSES

200 Deleted

POST /admin/products/{id}/variants auth required

Add a variant to a product

Param	In	Required	Type	Notes
id	path	yes	integer	

REQUEST BODY OPTIONAL — APPLICATION/JSON

```
{
  "sku": "",
  "attributes": {
    "size": "M",
    "color": "Pink"
  },
  "price": 0,
  "compareAtPrice": 0,
  "stockQuantity": 0
}
```

RESPONSES

 **201** Created**POST** /admin/products/{id}/variants/generate auth required

Generate variant combinations from selected variant types + values

Param	In	Required	Type	Notes
id	path	yes	integer	

REQUEST BODY OPTIONAL — APPLICATION/JSON

```
{
  "selections": [
    {
      "typeId": 0,
      "valueIds": [
        0
      ]
    }
  ],
  "price": 0,
  "compareAtPrice": 0,
  "stockQuantity": 0
}
```

RESPONSES

 **200** Created variants + skipped count

PATCH /admin/products/{id}/variants/{variantId}

auth required

Update a variant

Param	In	Required	Type	Notes
id	path	yes	integer	
variantId	path	yes	integer	

RESPONSES

200 Updated

DELETE /admin/products/{id}/variants/{variantId}

auth required

Delete a variant

Param	In	Required	Type	Notes
id	path	yes	integer	
variantId	path	yes	integer	

RESPONSES

200 Deleted

POST /admin/products/{id}/images

auth required

Add a gallery image to a product

Param	In	Required	Type	Notes
id	path	yes	integer	

REQUEST BODY OPTIONAL — APPLICATION/JSON

```
{
  "imageUrl": "",
  "sortOrder": 0
}
```

RESPONSES

201 Created

DELETE /admin/products/{id}/images/{imageId}

auth required

Remove a gallery image from a product

Param	In	Required	Type	Notes
id	path	yes	integer	
imageId	path	yes	integer	

RESPONSES

200 Deleted

GET /products

no auth

Browse active products (public)

Param	In	Required	Type	Notes
categoryId	query	no	integer	
page	query	no	integer	

RESPONSES

200 Paginated list

GET /products/{slug}

no auth

Get a product by slug (public)

Param	In	Required	Type	Notes
slug	path	yes	string	

RESPONSES

200 Product with active variants and images

404 Not found

Coupons

Validating a discount code before checkout.

GET

/coupons/validate/{code}

no auth

Preview a coupon's discount for a given subtotal (public — cart/checkout "Apply")

Param	In	Required	Type	Notes
code	path	yes	string	
subtotal	query	yes	number	

RESPONSES

- 200

Coupon is valid — discount preview
- 400

Invalid

Currency

Exchange rates for displaying prices in other currencies.

GET **/currency/rates**

no auth

Current KWD-based exchange rates for the site's supported currencies (public)

RESPONSES

200 Rates

Game Categories

Top-level game categories shown on the board-selection screen.

GET /admin/game-categories

 auth required

List game categories

Each row also includes quiz_count — the number of global-catalog games (school_id IS NULL) tagged to that category — used by the admin table's "Has Games" column.

RESPONSES

 **200** List

POST /admin/game-categories

 auth required

Create a game category

RESPONSES

 **201** Created

PATCH /admin/game-categories/{id}

 auth required

Update a game category

Param	In	Required	Type	Notes
id	path	yes	integer	

RESPONSES

 **200** Updated

DELETE /admin/game-categories/{id}

 auth required

Delete a game category

Param	In	Required	Type	Notes
id	path	yes	integer	

RESPONSES

 **200** Deleted

GET /game-categories

no auth

List active game categories (public)

RESPONSES

 **200** List of categories

Appendix — Data Types

Every response is wrapped in the standard envelope shown below. The tables after it describe the shape of each named object referenced above.

Standard success envelope

```
{
  "success": true,
  "message": "OK",
  "data": "..."
```

Standard error envelope

```
{
  "success": false,
  "message": "Human-readable error message",
  "details": "optional, present for some validation errors"
```

SchoolListItem

Field	Type	Notes
id	integer	e.g. 4
nameEn	string	e.g. "Al Manar International School"
nameAr	string	e.g. "مدرسة المنار العالمية"
logoUrl	string (nullable)	e.g. "https://back.makedown.online/uploads/school-4.png"

SchoolOpenGame

A school's currently open/live game (game_sessions row). This is the browse view only — it never includes the join code. The student enters the code their teacher gave them separately, through POST /play/sessions/join.

Field	Type	Notes
id	integer	e.g. 91
title	string (nullable)	e.g. "Grade 6 Science Trivia"
titleAr	string (nullable)	e.g. "مسابقة العلوم للصف السادس"
mode	string	e.g. "team"
audience	string (nullable)	e.g. "mixed"
status	string	e.g. "waiting"
scheduledDate	string (nullable)	e.g. "2026-10-01"
scheduledTime	string (nullable)	e.g. "10:30:00"
teams	array<object>	
categories	array<object>	

GameSessionDetail

Full game state — returned by create, join, get, and re-broadcast over Socket.io as ``game:state`` on every change. Top-level session fields are raw ``game_sessions`` columns (snake_case); the fields listed explicitly below are computed extras added on top.

Field	Type	Notes
id	integer	e.g. 91
title	string (nullable)	e.g. "Grade 6 Science Trivia"
host_user_id	integer	e.g. 501
school_id	integer (nullable)	e.g. 4
mode	string	e.g. "team"
is_public	integer	e.g. 0
max_players	integer (nullable)	
join_code	string	e.g. "7F3KQ2"
qr_code_url	string (nullable)	e.g. "..."
status	string	e.g. "waiting"
current_turn_index	integer	e.g. 0
current_question_id	integer (nullable)	
turn_started_at	string (nullable)	
turn_ends_at	string (nullable)	
started_at	string (nullable)	
ended_at	string (nullable)	
created_at	string	
turnOrder	array<integer>	Ordered list of game_participants.id — whose turn is next
currentTurnParticipantId	integer (nullable)	
currentQuestion	object (nullable)	The active tile's question, answer key stripped, or null between tiles
awaitingScan	boolean	True while a QR/audio question is waiting to be revealed (see /play/sessions/{id}/scan and /reveal)

Field	Type	Notes
participants	array<object>	
teams	array<object>	Empty array outside team mode.
board	array<object>	One entry per chosen category/quiz, each with its 6 point tiles.

ProfileUser

Returned by every /me profile endpoint (update profile, upload avatar). Field names are camelCase here — note this is a different, fuller shape than the /auth/* User schema (adds firstName/lastName/bio).

Field	Type	Notes
id	integer	e.g. 501
uuid	string	e.g. "b6f2c8b0-9e2e-4f0a-8b8e-2b1a3e9c4a11"
fullName	string	e.g. "Sara Al-Fahad"
firstName	string (nullable)	e.g. "Sara"
lastName	string (nullable)	e.g. "Al-Fahad"
email	string	e.g. "sara@example.com"
phone	string (nullable)	e.g. "+96555512345"
avatarUrl	string (nullable)	e.g. "https://back.makedown.online/uploads/avatar-3f2c1a.jpg"
bio	string (nullable)	e.g. "Trivia night regular."
emailVerified	boolean	e.g. true
createdAt	string	e.g. "2026-01-14T09:12:00.000Z"

Address

Note: unlike ProfileUser, address fields come straight from the database and are snake_case in the response — full_name, is_default, created_at, etc. — NOT camelCase.

Field	Type	Notes
id	integer	e.g. 12
user_id	integer	e.g. 501
label	string (nullable)	e.g. "Home"
full_name	string	e.g. "Sara Al-Fahad"
phone	string	e.g. "+96555512345"
country	string	e.g. "Kuwait"
city	string (nullable)	e.g. "Kuwait City"
area	string (nullable)	e.g. "Salmiya"
block	string (nullable)	e.g. "3"
street	string (nullable)	e.g. "Street 12"
building	string (nullable)	e.g. "44"
floor	string (nullable)	e.g. "2"
apartment	string (nullable)	e.g. "7"
is_default	integer	MySQL TINYINT — 0 or 1, not a real boolean e.g. 1
created_at	string	
updated_at	string	

OrderSummary

A row from `orders` — also raw snake_case, same as Address.

Field	Type	Notes
id	integer	e.g. 233
order_number	string	e.g. "MD-20261001-0233"
status	string	e.g. "processing"
payment_status	string	e.g. "paid"
payment_method	string (nullable)	e.g. "knet"
subtotal	string	DECIMAL columns come back as strings — parse before doing math e.g. "12.500"
discount_total	string	e.g. "0.000"
shipping_total	string	e.g. "1.500"
grand_total	string	e.g. "14.000"
currency	string	e.g. "KWD"
coupon_code	string (nullable)	e.g. "WELCOME10"
notes	string (nullable)	
created_at	string	
updated_at	string	

OrderDetail

Field	Type	Notes
items	array<object>	

MyPackage

A row from `user\_packages` joined with its package info — snake_case.

Field	Type	Notes
id	integer	e.g. 88
package_id	integer	e.g. 3
order_id	integer (nullable)	e.g. 233
credits_remaining	integer	e.g. 4
purchased_at	string	
expires_at	string (nullable)	
status	string	e.g. "active"
package_name_en	string	e.g. "5-Game Pack"
package_name_ar	string	e.g. "باقة 5 ألعاب"
package_credits	integer	e.g. 5
package_free_credits	integer	e.g. 0

GameHistoryEntry

One played session, camelCase (unlike addresses/orders/packages above).

Field	Type	Notes
sessionId	integer	e.g. 91
mode	string	e.g. "team"
status	string	e.g. "finished"
startedAt	string	
endedAt	string (nullable)	
participants	array<object>	Empty for team-mode sessions — see `teams` instead.
teams	array<object>	
quizzes	array<object>	
lifelinesUsed	array<string>	

PaginatedList

Field	Type	Notes
rows	array<object>	
total	integer	e.g. 42
page	integer	e.g. 1
pageSize	integer	e.g. 20

RegisterInput

Field	Type	Notes
fullName	string	e.g. "Sara Al-Fahad"
email	string	e.g. "sara@example.com"
phone	string	e.g. "+96555512345"
password	string	

LoginInput

Field	Type	Notes
email	string	
password	string	
rememberMe	boolean	

VerifyOtpInput

Field	Type	Notes
email	string	
code	string	e.g. "482913"
purpose	string	

User

Field	Type	Notes
id	integer	
uuid	string	
fullName	string	
email	string	
phone	string (nullable)	
avatarUrl	string (nullable)	
emailVerified	boolean	
createdAt	string	

AuthSession

Field	Type	Notes
user	User	
accessToken	string	
refreshToken	string	