



30-Day Android Challenge

Mastering Android Programming Interviews Globally
(Junior-Mid-Senior-Architect-Level Deconstruction 📱)

Day 17:

Performance Optimization & Profiling

Part 1 of 2



Esmaeeil Moradi

@esmaeeil-moradi700

Day 17



of #30DayAndroidChallenge: Comprehensive Answers for "Day 17: Performance Optimization & Profiling" part 1 of 2

Hello everyone!

In the competitive world of mobile applications, where speed and efficiency matter as much as features, a slow app plagued with memory issues will quickly lose its users. Performance Optimization is no longer a luxury; it's a necessity. This key skill enables you to build applications that are not only feature-rich but also run smoothly, use device resources efficiently, and provide a fluid and enjoyable user experience.

In this section of the #30DaysOfAndroidChallenge, we're diving into this vital topic, aiming to provide you with the knowledge and tools needed to diagnose and solve performance issues. Given the depth and breadth of this subject, we have split the content into two distinct parts.



Esmaeeil Moradi
@esmaeeil-moradi700




This article is **Part 1** of this comprehensive discussion. In this part, we will focus on fundamental concepts and common questions at the Junior and Mid-Level. From understanding the root causes of Memory Leaks and how to use the Android Studio Profiling tools, to implementing memory management strategies for large datasets and optimizing image loading, we will lay the necessary groundwork for building efficient applications.

Get ready to build apps that perform at a high level by delving into the world of optimization. Join us as we enter the realm of building fast and stable applications!



Esmaeel Moradi
@esmaeel-moradi700



Junior Level Questions



Esmaeeil Moradi
@esmaeeil-moradi700

What are common causes of memory leaks in Android?

A memory leak in Android occurs when an object that is no longer needed by the application (and should have been garbage collected) is still being referenced by an active object. This prevents the garbage collector from freeing up its memory, leading to a gradual increase in memory consumption. Over time, this can cause the app to slow down, become unstable, or even crash with an `OutOfMemoryError`.

Here are some of the most common causes of memory leaks in Android:

1. Static References to Context:

- **Problem:** Storing an Activity or View context in a static field. Static fields live for the entire lifetime of the application process. If you hold a static reference to an Activity, that activity will never be garbage collected, even when the user navigates away from it. This leaks the entire activity's view hierarchy and resources.
- **Example:**



Esmaeel Moradi
@esmaeel-moradi700



```
object MySingleton {  
    private var context: Context? = null  
  
    fun init(context: Context) {  
        this.context = context.applicationContext // Incorrect, but better  
        // Using 'context' directly here is a leak.  
    }  
}  
  
class MyActivity : AppCompatActivity() {  
    override fun onCreate(savedInstanceState: Bundle?) {  
        super.onCreate(savedInstanceState)  
        // BAD: This leaks MyActivity  
        MySingleton.init(this)  
    }  
}
```

- **Solution:**

- Always use the applicationContext when a global Context is needed, as it has a lifecycle tied to the app process, not a specific activity.
- Avoid using static fields for Activity or View objects. If you must, use a WeakReference to allow garbage collection.



Esmaeel Moradi

@esmaeeil-moradi700

2.Unregistered Listeners and Callbacks:



- **Problem:** Registering a listener (e.g., a BroadcastReceiver, SensorEventListener) in an Activity or Fragment but failing to unregister it. The system component holding the listener will have a strong reference to your Activity/Fragment, preventing it from being garbage collected.
- **Example:**

```
class MyActivity : AppCompatActivity() {  
    private val sensorManager: SensorManager by lazy {  
        getSystemService(SENSOR_SERVICE) as SensorManager  
    }  
    private val sensorEventListener = object : SensorEventListener {  
        // ...  
    }  
  
    override fun onResume() {  
        super.onResume()  
        sensorManager.registerListener(sensorEventListener, ...)  
    }  
  
    // BAD: onPause() doesn't unregister the listener.  
    // When MyActivity is destroyed, sensorManager still holds a reference.  
}
```

- **Solution:**
 - Always register listeners in a lifecycle method like onResume() and un-register them in the corresponding onPause() or onDestroy() method. This is a classic symmetrical pattern.



Esmaeel Moradi
@esmaeeil-moradi700

3.Non-Static Inner Classes:

- **Problem:** A non-static inner class (or an anonymous inner class) implicitly holds a strong reference to its outer class instance. If this inner class instance outlives its outer class, it will prevent the outer class (e.g., an Activity) from being garbage collected. This is very common with Handlers, Runnables, and AsyncTasks.
- **Example (Kotlin):**

```
class MyActivity : AppCompatActivity() {  
    private val handler = Handler(Looper.getMainLooper())  
  
    private val delayedTask = Runnable {  
        // Do something that might be delayed  
    }  
  
    override fun onCreate(savedInstanceState: Bundle?) {  
        super.onCreate(savedInstanceState)  
        handler.postDelayed(delayedTask, 10000) // Delay of 10s  
        // If MyActivity is destroyed before 10s, handler holds a reference to it.  
    }  
}
```



Esmaeel Moradi
@esmaeeil-moradi700

- **Solution:**

- Use static inner classes (or top-level classes) for listeners, handlers, and tasks.
- If the inner class needs to reference the outer class, use a WeakReference to avoid a strong reference.
- For Handlers, always remove any pending messages in onDestroy() or a similar lifecycle method.
- Modern Solution: Use ViewModels and Kotlin Coroutines. Coroutines launched in a viewModelScope are automatically cancelled when the ViewModel is cleared, preventing leaks.



Esmaeel Moradi

@esmaeeil-moradi700

4.Improper Use of Bitmaps:



- **Problem:** Bitmaps are large and can consume a significant amount of memory. If they are not handled correctly (e.g., not recycled on older Android versions, or a reference is held after they are no longer needed), they can quickly lead to an OutOfMemoryError.
- **Solution:**
 - Use image loading libraries like Glide or Coil. They handle caching, efficient loading, and memory management for you.
 - If you must handle bitmaps manually, use `Bitmap.recycle()` on older APIs (pre-API 11) to free memory, and manage your own memory pools.
 - Downsample large images to the required size before loading them into memory.



Esmaeel Moradi

@esmaeel-moradi700




In modern Android development, using ViewModels, LiveData (or Flow), and lifecycle-aware components greatly reduces the risk of these leaks, but a developer must always be vigilant and understand these underlying principles.



Esmaeeil Moradi
@esmaeeil-moradi700

How do you use Android Studio's profiling tools?



Intelligent task scheduling goes beyond basic WorkManager constraints to dynamically adapt to various device conditions, aiming to optimize for battery life, performance, and user experience. This involves a more nuanced approach to how and when background work is executed.

Here's how to use the main components of the Android Profiler:

1. Opening the Profiler:

- With your app running on a device or emulator, go to View > Tool Windows > Profiler.
- Select the process for your app from the top left dropdown.



Esmaeel Moradi

@esmaeel-moradi700

2.Memory Profiler:

- **Purpose:** To track memory allocation, identify memory leaks, and analyze the heap to understand which objects are consuming the most memory.
- **How to Use:**
- **Live Memory Graph:** The main graph shows your app's memory usage over time. Watch for a saw-tooth pattern (memory usage increases and then drops sharply) which is normal garbage collection (GC). A steadily increasing graph that never drops can indicate a memory leak.
- **Capture Heap Dump:** Click the "Dump Java heap" button. This captures a snapshot of all objects in memory at that moment. The heap dump view is invaluable for debugging leaks:
 - Organize by Class: Sort by class to see which object types are taking up the most memory (e.g., a large number of Bitmaps or Views).
 - Inspect References: Select a class and a specific instance to see its References. This shows what's holding a reference to the object. If a leaked Activity is being held by a static field, this will show you the path to the leak.
- **Record Allocations:** Click "Record" to track every new object allocated in your app. This is useful for identifying "chatter" or excessive object creation in a tight loop, which can cause frequent, expensive GC pauses.



Esmaeel Moradi

@esmaeeil-moradi700

3.CPU Profiler:

- **Purpose:** To analyze your app's CPU usage, identify expensive methods, and understand where your code is spending the most time.
- **How to Use:**
 - **Record CPU Activity:** Click the "Record" button to begin recording. Interact with your app to perform the action you want to profile. Stop the recording.
 - **Flame Chart:** The flame chart is a visual representation of your call stack. The horizontal width of a bar represents the time spent in that method. A long, wide bar at the top of the stack indicates a "hot" method that's a good candidate for optimization.
 - **Top Down / Bottom Up View:** These views provide a more structured list of methods, sorted by time spent.
 - **Top Down:** Start from the top of the call stack (e.g., Thread.run()) and see which child methods are taking the most time.
 - **Bottom Up:** Start from the methods at the bottom of the stack that are consuming the most time, and see their call paths. This is great for finding specific, expensive methods that are called from different places.
 - **Trace Events:** Android 10+ supports custom trace events (Trace.beginSection() / Trace.endSection()). These appear as distinct blocks in the profiler, allowing you to easily profile specific sections of your code.



Esmaeel Moradi

@esmaeel-moradi700

4. Energy Profiler:

- **Purpose:** To analyze your app's power consumption and identify components that are draining the battery, such as CPU, network, location, and wake locks.
- **How to Use:**
- **Real-time Chart:** The chart shows energy usage over time, categorized by CPU, Network, and Location.
- **System Events:** The timeline shows system events like wake locks, alarms, and jobs.
- **Network Usage:** The network section shows a list of network requests, their size, and timestamps. You can see if your app is performing excessive network activity in the background.
- **Wake Locks:** Identify if your app is holding a wake lock for too long, preventing the device from going into deep sleep and draining the battery.



Esmaeeil Moradi
@esmaeeil-moradi700

General Best Practices for Profiling:


- **Use a Release Build Variant:** Profile a release or debuggable release build, as it's closer to the production version (e.g., with ProGuard/R8 optimizations enabled).
- **Target a Specific Workflow:** Don't just profile the entire app. Focus on a specific user flow (e.g., scrolling a list, launching a camera, performing a data sync) to get a clear, actionable profile.
- **Profile on a Real Device:** Profiling on a physical device is always better than an emulator, as it gives a more accurate representation of real-world performance.
- **Profile After an Action:** To find leaks, often you'll perform an action (e.g., rotate the device, open/close an activity), and then take a heap dump to see if the old objects were garbage collected.

The Android Profiler is an indispensable tool for every Android developer to build high-quality, performant applications.



Esmaeel Moradi
@esmaeel-moradi700

Explain the importance of app startup time optimization.



App startup time is the period from when the user taps an app icon to when the application is ready for user interaction. Optimizing this time is one of the most critical aspects of application performance, directly impacting user experience, retention, and business success.



Esmaeeil Moradi

@esmaeeil-moradi700

Why is a fast startup so critical?



1. First Impressions & User Experience:

- Startup is the first interaction a user has with your app. A slow, laggy startup can create a negative first impression, making the user feel the app is unreliable or poorly made.
- A fast startup makes the app feel responsive, polished, and lightweight.

2. User Retention and Engagement:

- Research has shown that users are more likely to abandon an app if it takes too long to load. A long startup time (e.g., > 2-3 seconds) can lead to users uninstalling the app.
- Apps that are fast to start are used more frequently.

3. App Store Ratings:

- App speed and responsiveness are often mentioned in user reviews and ratings. A slow app can lead to poor ratings, hurting your app's visibility and download numbers.

4. Compliance with Android Vitals:

- Google's "Android Vitals" program, which monitors app performance and stability, includes startup time as a key metric. Apps that consistently have poor startup performance may receive less visibility in the Play Store.



Esmaeel Moradi

@esmaeel-moradi700

How to Measure Startup Time:

You can measure startup time in two main ways:

- **Cold Start:** The app's process is not running in memory. This is the slowest type of startup as the system must create the process, load the app into memory, initialize the Application object, and create the main Activity.
- **Warm Start:** The app's process is already in memory, but the Activity is being recreated.
- **Hot Start:** The app's Activity is still in memory. This is the fastest, as the system just needs to bring it to the foreground.

Measurement Tools:

- **Logcat:** The system reports startup time in Logcat. Look for lines like `Displayed com.example.app/.MainActivity: +456ms`. This is the time from launch to when the first frame is drawn.
- **Macrobenchmarks:** The official Jetpack library for measuring app performance. It provides a reliable and automated way to measure cold, warm, and hot startup times, and run these tests in a CI/CD pipeline.
- **Firebase Performance Monitoring:** A great way to get real-world startup time metrics from your user base in production. It automatically tracks cold and warm startup times.



Esmaeel Moradi
@esmaeel-moradi700

Key Optimization Techniques:



1. Lazy Initialization:

- **Concept:** Only initialize objects and perform expensive operations when they are absolutely needed.
- **Example:** Don't initialize a heavy library or a database connection in your `Application.onCreate()`. Instead, initialize it the first time the relevant Activity or Fragment is created.
- **Modern Solution:** Use `lazy` in Kotlin for properties that don't need to be initialized immediately.

2. Reduce Dependencies and Code in `Application.onCreate()`:

- **Problem:** `Application.onCreate()` runs before anything else. A large amount of code here directly impacts cold startup time.
- **Solution:** Move any non-critical initialization out of the Application class. For example, database initialization, analytics SDK setup, or complex network clients.



3. App Startup Library:

- **Concept:** The Jetpack App Startup library provides a way to initialize components at app startup in a more efficient and declarative way.
- **Benefits:** It allows you to define initializers for libraries (e.g., analytics SDKs) and specify their dependencies. The library then initializes them on a background thread, preventing blocking the main thread. It also allows you to initialize multiple components in parallel, reducing overall startup time.

4. Optimize Layouts and View Hierarchy:

- A complex, deep view hierarchy can cause the system to spend more time measuring and laying out views during startup.
- Use flat layouts like ConstraintLayout to reduce nesting.
- Use the View Stub to lazily inflate complex parts of the UI that aren't immediately visible.



Esmaeel Moradi
@esmaeel-moradi700



5. Use Splash Screen API:

The new Splash Screen API (Android 12+) provides a standardized way to manage the splash screen, including the transition to the first activity. It is faster and more consistent than custom, traditional splash screen implementations.


6. Avoid Blocking Operations on the Main Thread:

Never perform I/O (disk reads, network calls), heavy computations, or database operations on the main thread during startup. Use Coroutines or a dedicated Executor to move these tasks to a background thread.

7. Profile and Iterate:

Use the Android Profiler to identify exactly what is taking time during startup. Analyze the CPU trace and the call stack to find the "hot" methods, optimize them, and then re-measure to confirm your changes had an effect.






By focusing on these techniques, you can significantly improve your app's startup performance, leading to a better user experience and stronger app retention.



Esmaeeil Moradi
@esmaeeil-moradi700



Mid-Level Questions



Esmaeel Moradi
@esmaeeil-moradi700



Implement memory management strategies for large datasets.

Handling large datasets without running into `OutOfMemoryError` is a common challenge in Android development. Efficient memory management is key to maintaining a smooth user experience, especially when dealing with lists, images, or extensive local data.



Esmaeel Moradi
@esmaeel-moradi700

→

Here are the key strategies for managing large datasets:

1. Pagination (Loading Data in Chunks):

- **Concept:** Instead of loading the entire dataset into memory at once, load a small, manageable chunk of data at a time. As the user scrolls to the end of the current data, you load the next chunk.
- **Implementation:**
 - **Backend:** Your API should support pagination (e.g., using offset and limit, or a next_page_token).
 - **Client (RecyclerView with Paging3):** The Jetpack Paging 3 library is the modern, recommended solution for this.
 - A PagingSource handles fetching data from the local database or network.
 - A Pager manages the stream of PagingData.
 - A PagingDataAdapter handles displaying the data in a RecyclerView, automatically requesting more data when needed.
- **Benefit:** Reduces memory footprint dramatically by only holding a small portion of the data in memory. Improves performance by only loading what is necessary.



Esmaeel Moradi
@esmaeel-moradi700



2.Using RecyclerView (Virtual Lists):

- **Concept:** RecyclerView is a fundamental component for displaying lists. It's a "virtual list" because it reuses (recycles) a small number of View objects. It only creates enough views to fill the screen and then recycles them as the user scrolls, binding new data to them.
- **Implementation:**
 - Always use a RecyclerView for lists of any significant size. Avoid ListView or ScrollView with many nested views, as they create a view for every item, leading to high memory usage.
 - Use DiffUtil within your RecyclerView.Adapter to efficiently calculate the differences between old and new lists. This allows for smooth animations and prevents unnecessary view updates.
 - For Compose, LazyColumn and LazyRow provide the same virtualization benefits, only recomposing and drawing the visible items.



Esmaeel Moradi
@esmaeeil-moradi700



3. Efficient Data Structures and Object Pooling:

- **Concept:** Minimize object allocations, especially in tight loops or for frequently created temporary objects. Each object creation has a memory overhead and adds to the workload of the garbage collector.
- **Object Pooling:** For objects that are created and destroyed frequently (e.g., temporary Point objects in a custom drawing method), create a pool of pre-allocated objects. Instead of creating a new object, you get one from the pool, use it, and then "return" it to the pool for reuse.
- **Primitive Types:** Use primitive types (Int, Double, Boolean) instead of their boxed counterparts (Integer, Double, Boolean) when possible to reduce object allocation overhead.
- **SparseArray / SparseBooleanArray:** For mapping Int keys to objects, these collections are more memory-efficient than a standard `HashMap<Int, T>`, as they avoid the overhead of boxed Integer objects.



Esmaeel Moradi
@esmaeel-moradi700

4. Handling Large Images:



- **Problem:** Loading large, high-resolution images (e.g., from a camera) directly into a Bitmap can easily cause an OutOfMemoryError.
- **Strategies:**
 - **Downsampling:** Use BitmapFactory.Options with inJustDecodeBounds = true to get the image's dimensions without loading it into memory. Then, calculate an appropriate inSampleSize to scale the image down to the size of the ImageView and load the downsampled version.
 - **Image Loading Libraries:** Use libraries like Coil or Glide. They handle this automatically, managing in-memory caching (using a LruCache), disk caching, and downsampling to the correct size.
 - **Avoid Bitmap.createScaledBitmap():** This method creates a new bitmap from an existing one, doubling the memory usage temporarily. It's better to downsample directly from the source.



Esmaeel Moradi
@esmaeeil-moradi700



5.Using onTrimMemory():

- **Concept:** The onTrimMemory() callback (in Application and Activity) is a system-level notification about the device's memory state.
- **Implementation:**
 - Override onTrimMemory() and use the provided level (TRIM_MEMORY_RUNNING_LOW, TRIM_MEMORY_UI_HIDDEN, etc.) to selectively release memory.
 - When the system is running low on memory (TRIM_MEMORY_RUNNING_CRITICAL), you can clear less-critical caches (e.g., a large image cache).
 - Image loading libraries often tie into this automatically, but for custom caches, this is a key optimization point.



Esmaeel Moradi

@esmaeel-moradi700



By combining these strategies, you can design a robust system that handles large datasets gracefully, ensuring your app remains performant and stable even on resource-constrained devices.



Esmaeeil Moradi
@esmaeeil-moradi700

How do you optimize app performance for low-end devices?

Optimizing for low-end devices is crucial for reaching a broader user base and ensuring a consistent experience across the Android ecosystem. These devices have less RAM, slower CPUs, and often older Android versions. A developer must be proactive in reducing resource consumption to avoid jank and crashes.



Esmaeail Moradi

@esmaeail-moradi700

Here are key strategies for optimizing for low-end devices:

1.Reduce Memory Footprint:

- **Minimize Object Allocations:** Avoid creating new objects in tight loops or during animations. Use object pooling if necessary.
- **Use Efficient Data Structures:** Prefer SparseArray and ArrayMap over HashMap for mapping integers to objects to reduce memory overhead.
- **Downsample Images:** As discussed, always load images at the size they are displayed, not their original resolution. Use image loading libraries like Coil or Glide which handle this automatically.
- **Manage Memory Aggressively:** Implement onTrimMemory() to clear non-essential caches when the system notifies you of low memory.
- **Use largeHeap=true only when necessary:** This flag in the manifest increases the app's heap size, but it's a brute-force approach. A well-optimized app shouldn't need it.



Esmaeel Moradi

@esmaeel-moradi700



2. Optimize Layouts and Views:

- **Flatten View Hierarchy:** A deep, nested view hierarchy is expensive to measure and draw. Use ConstraintLayout to create flat, complex layouts with fewer nested views.
- **Avoid Overdraw:** Overdraw is when the system draws the same pixel on the screen multiple times. Use the "Debug GPU Overdraw" developer option to find overdraw and fix it by removing unnecessary background colors or transparent views.
- **Use ViewStub:** For UI components that are rarely visible (e.g., an error screen, a settings panel), use a ViewStub to load the layout only when it's needed, saving memory and layout time during startup.
- **Reduce Animations:** Limit complex, resource-intensive animations, especially for lists.



Esmaeel Moradi

@esmaeel-moradi700



3. Optimize CPU Usage:

- **Move Work Off the Main Thread:** This is the most important rule. Never perform heavy computations, disk I/O, or network requests on the main thread. Use Kotlin Coroutines with Dispatchers.IO or Dispatchers.Default for these tasks.
- **Batch Background Work:** Use WorkManager to defer and batch background tasks (e.g., analytics uploads, data syncs) to run when the device is idle or charging.
- **Optimize Algorithms:** Use efficient algorithms and data structures. A simple for loop is often faster than a complex stream operation.



Esmaeel Moradi

@esmaeeil-moradi700



4. Manage Resources & Device State:

- **Resource Qualifiers:** Provide different resources (drawable-hdpi, layout-sw360dp) for different screen densities and sizes. Loading a 10MB image on an hdpi device is wasteful.
- **Low-Memory Variants:** You can use resource qualifiers like -small or -xlarge to provide a simpler UI for low-end devices, or use a bools.xml to enable/disable complex features.
- **Adapt to Device RAM:** Programmatically check `ActivityManager.isLowRamDevice()` and adapt your app's behavior. On a low-RAM device, you might disable a complex GIF animation or pre-caching of images.
- **Check Network State:** On slower networks, download smaller image previews or defer large downloads.

5. Use Performance-Optimized Libraries:

Image Loading: Use libraries like Glide or Coil, which are heavily optimized for memory and performance.

Database: Room is an excellent, performant database layer. It avoids some of the overhead of lower-level APIs and handles threading for you.

Serialization: Use lightweight and fast serialization libraries like Moshi or Gson.



Esmaeel Moradi

@esmaeel-moradi700



By focusing on these optimizations, you can create a fast, stable, and responsive app that performs well even on low-end devices, expanding your app's reach to a wider audience.



Esmaeeil Moradi
@esmaeeil-moradi700

Design efficient image loading and caching mechanisms.

Efficiently loading and caching images is a cornerstone of modern Android app development. Improper handling of images can lead to severe performance issues, including memory leaks, janky scrolling, and `OutOfMemoryError` crashes. The best practice is to leverage a dedicated image loading library.



Esmaeel Moradi
@esmaeel-moradi700

Benefits of Using an Image Loading Library (e.g., Glide, Coil):




- **Automatic Downsampling:** The library automatically loads the image at the size of the ImageView, saving a huge amount of memory.
- **In-Memory Caching:** A highly-optimized LruCache (Least Recently Used) is used to store recently-used image bitmaps in memory, preventing redundant decoding. This makes scrolling through lists of the same images incredibly fast.
- **Disk Caching:** Images are saved to the device's disk, so they don't have to be downloaded from the network again.
- **Request Management:** The library handles the lifecycle of image requests. If an Activity is destroyed, pending image loads for that Activity are automatically cancelled, preventing memory leaks.
- **Threading:** All network requests and image decoding are handled on background threads, freeing the main thread from blocking operations.
- **Placeholders & Error Handling:** Libraries provide easy ways to show a placeholder while an image is loading and display an error image if the load fails.



Esmaeel Moradi
@esmaeel-moradi700

Core Concepts in Image Loading & Caching:



1. In-Memory Cache (L1 Cache):

- Purpose: Stores the decoded Bitmap objects in RAM for immediate access. This is the fastest form of caching.
- Mechanism: Typically implemented as an LruCache, a data structure that discards the least recently used item when the cache becomes full.
- Optimization: The cache size is carefully managed to avoid causing an OutOfMemoryError. Libraries use `onTrimMemory()` to gracefully reduce the cache size when the system needs more memory.

2. Disk Cache (L2 Cache):

- Purpose: Stores the compressed, raw image files on the device's storage. It's slower than the in-memory cache but faster than a network request.
- Mechanism: Libraries like Glide and Coil use a dedicated disk cache to save downloaded images.
- Optimization: The cache has a size limit and can be configured to evict old files to save space.



Esmaeel Moradi

@esmaeel-moradi700



3.Loading from Network (L3 Cache):

- Purpose: The final fallback. If an image is not in the in-memory or disk cache, it's downloaded from the network.
- Mechanism: Libraries use OkHttp or other network clients to download images on a background thread.
- Optimization: The libraries intelligently handle network requests, retries, and network connectivity changes.



Esmaeeil Moradi
@esmaeeil-moradi700

Implementation with Coil (Modern, Kotlin-first):



Coil is an excellent modern alternative to Glide, built with Kotlin Coroutines. It's lightweight and uses a simple, modern API.

```
// Add dependency:
// implementation("io.coil-kt:coil:2.6.0")

// In a Fragment or Activity:
// In the view, the ImageView has a width/height set in XML
imageView.load("https://example.com/image.jpg") {
    // Optional: Configure the request
    placeholder(R.drawable.placeholder) // Show a placeholder image
    error(R.drawable.error)             // Show an error image on failure
    crossfade(true)                     // Simple fade-in animation
    size(ViewSizeResolver(imageView)) // Coil automatically sizes to ImageView
    diskCachePolicy(CachePolicy.ENABLED) // Enable disk caching
    memoryCachePolicy(CachePolicy.ENABLED) // Enable memory caching
}

// In Jetpack Compose:
@Composable
fun MyImage() {
    val painter = rememberImagePainter(
        data = "https://example.com/image.jpg",
        builder = {
            crossfade(true)
            placeholder(R.drawable.placeholder)
        }
    )
    Image(
        painter = painter,
        contentDescription = "My Image",
        modifier = Modifier.fillMaxWidth()
    )
}
```



Esmaeel Moradi

@esmaeeil-moradi700

Handling Large Bitmaps Manually (When a Library is Not an Option):



While not recommended, if you must handle images manually (e.g., for custom drawing or a specific use case), follow these steps:

1. Get Image Dimensions:

```
val options = BitmapFactory.Options().apply {  
    inJustDecodeBounds = true  
}  
BitmapFactory.decodeResource(resources, R.id.my_image, options)  
val imageHeight = options.outHeight  
val imageWidth = options.outWidth
```



Esmaeeil Moradi
@esmaeeil-moradi700

2. Calculate inSampleSize:




```
val scaleFactor = (imageWidth / targetWidth).coerceAtLeast(imageHeight / targetHeight)
```

3. Load the Downsampled Bitmap:

```
options.inJustDecodeBounds = false  
options.inSampleSize = scaleFactor  
val bitmap = BitmapFactory.decodeResource(resources, R.id.my_image, options)
```



Esmaeel Moradi
@esmaeeil-moradi700



Conclusion:

For all but the most specialized cases, the best and most efficient way to handle images and caching is by using a well-maintained image loading library like Glide or Coil. They provide a robust, performant, and memory-safe solution out of the box, freeing developers to focus on application logic.



Esmaeel Moradi
@esmaeeil-moradi700

✨ These comprehensive answers aim to equip you with the knowledge required for Architect-level and Senior-level interviews, and to make informed architectural decisions in your real-world projects. Good luck. ✨



Esmaeeil Moradi

@esmaeeil-moradi700