



30-Day Android Challenge

Mastering Android Programming Interviews Globally
(Junior-Mid-Senior-Architect-Level Deconstruction 📱)

Day 19:

Security Best Practices & Implementation

Part 1 of 2



Esmaeeil Moradi

@esmaeeil-moradi700

Day 19



of #30DayAndroidChallenge:

Comprehensive Answers for "Day 19: P: Security Best Practices & Implementation"

part 1 of 2

Hello to all my dear friends and companions! 🙌

I'm very happy to be with you on Day 19 of the #30DaysOfAndroidChallenge. With each passing day, I become prouder of our energetic and passionate Android developer community.

Today, we're diving into one of the most important and sensitive topics in software development: Security. From understanding its basic principles to implementing key mechanisms, this knowledge is vital for every developer who values building trustworthy applications.



Esmaeeil Moradi

@esmaeeil-moradi700




Given the breadth of the security topic, we've divided it into two parts to cover each aspect in more detail. This article is Part 1 of this comprehensive discussion. In this section, we will focus on fundamental concepts and common questions at the Junior and Mid-Levels. From understanding the Sandbox and Permissions system to implementing secure data storage methods and authentication mechanisms, we will provide the necessary foundations for building secure applications.

Get ready to dive deeper into the world of security and build apps that are not only high-performing but also completely trustworthy. Join us as we enter the world of building secure and stable applications!



Esmaeel Moradi
@esmaeel-moradi700



Junior Level Questions



Esmaeeil Moradi
@esmaeeil-moradi700

What are basic Android security principles?



Android's security model is built on a few fundamental principles that work together to protect the device, user data, and other applications from malicious behavior.

1.Application Sandboxing:

- **Concept:** This is the cornerstone of Android security. Every application runs in its own isolated process, with its own unique User ID (UID). This sandbox prevents one app from accessing the data or resources of another app without explicit permission.
- **How it Works:** When an app is installed, the Android OS creates a new Linux process for it and assigns a unique UID. All of the app's files and data are stored in a private directory that is only accessible by that UID. This means that by default, one app cannot read or write to another app's files.
- **Implication:** This principle means that even if a malicious app is installed, it can't directly harm other apps or the system unless it exploits a vulnerability or is granted a dangerous permission by the user.



Esmaeel Moradi
@esmaeel-moradi700

2.Principle of Least Privilege:



- **Concept:** This principle dictates that an application should only be granted the minimum permissions necessary to perform its functions. A flashlight app, for example, should not have access to a user's contacts.
- **How it Works:** Developers must explicitly declare the permissions their app needs in the AndroidManifest.xml. The Android system then enforces these permissions. Permissions are categorized into different levels (e.g., normal, dangerous, signature), which determine how and when they are granted.
- **Implication:** This limits the potential damage an app can cause. By requesting only the necessary permissions, a developer signals trust to the user and reduces the app's attack surface.



Esmaeeil Moradi

@esmaeeil-moradi700

3. Secure Data Storage:



- **Concept:** Android provides built-in mechanisms to help developers store data securely, whether it's local app data, sensitive user information, or cryptographic keys.
- **How it Works:**
 - **Internal Storage:** By default, files created in an app's internal storage directory are private to that app and cannot be accessed by others.
 - **Android Keystore System:** This is a hardware-backed or software-based container for storing cryptographic keys. Keys stored here are inaccessible to other apps and can be configured to require user authentication (e.g., fingerprint) for use.
 - **Encrypted Shared Preferences/Files:** The Jetpack Security library provides `EncryptedSharedPreferences` and `EncryptedFile` for securely storing key-value pairs and files using master keys from the Keystore.



Esmaeel Moradi

@esmaeel-moradi700



Together, these principles create a strong foundation. The sandboxing model isolates apps, the least privilege principle minimizes their potential for harm, and the secure storage mechanisms provide developers with the tools to protect sensitive information on the device.



Esmaeeil Moradi
@esmaeeil-moradi700



How do you implement secure data storage?

Securely storing sensitive data (like authentication tokens, user preferences, or small files) is a fundamental requirement. Relying on simple SharedPreferences or plaintext files is a significant security risk. The modern, recommended approach is to use the Jetpack Security library, which leverages the **Android Keystore System**.



Esmaeeil Moradi
@esmaeeil-moradi700

1. Using EncryptedSharedPreferences:

EncryptedSharedPreferences is a drop-in replacement for the standard SharedPreferences that encrypts keys and values automatically. This is ideal for storing small, sensitive data like user session tokens or API keys.

Step 1: Add the Dependency Add the security-crypto dependency to your build.gradle file:

```
implementation("androidx.security:security-crypto:1.1.0-alpha06")
```

Step 2: Generate a Master Key First, you need to create a master key, which will be used to encrypt all the data. The master key is stored securely in the Android Keystore.

```
val masterKeyAlias = MasterKeys.getOrCreate(MasterKeys.AES256_GCM_SPEC)
```



Esmaeel Moradi
@esmaeeil-moradi700

Step 3: Initialize and Use EncryptedSharedPreferences

Now, you can create and use EncryptedSharedPreferences just like you would with a regular SharedPreferences instance.

```
import androidx.security.crypto.EncryptedSharedPreferences
import androidx.security.crypto.MasterKeys

fun getSecurePrefs(context: Context): SharedPreferences {
    val masterKeyAlias = MasterKeys.getOrCreate(MasterKeys.AES256_GCM_SPEC)
    return EncryptedSharedPreferences.create(
        "secure_prefs_file",
        masterKeyAlias,
        context,
        EncryptedSharedPreferences.PrefKeyEncryptionScheme.AES256_SIV,
        EncryptedSharedPreferences.PrefValueEncryptionScheme.AES256_GCM
    )
}

// Example Usage:
fun saveToken(context: Context, token: String) {
    val securePrefs = getSecurePrefs(context)
    with(securePrefs.edit()) {
        putString("auth_token", token)
        apply()
    }
}

fun getToken(context: Context): String? {
    val securePrefs = getSecurePrefs(context)
    return securePrefs.getString("auth_token", null)
}
```



Esmaeel Moradi

@esmaeeil-moradi700

2. Using EncryptedFile:



For storing larger, sensitive files (e.g., a local user database, a configuration file), EncryptedFile is the right choice. It provides a secure file-based storage solution, also backed by the Android Keystore.

- **Step 1:** Generate a Master Key (same as above)
- **Step 2:** Initialize and Use EncryptedFile
EncryptedFile provides a FileOutputStream to write encrypted data and an FileInputStream to read it.



Esmaeel Moradi
@esmaeel-moradi700

```

import androidx.security.crypto.EncryptedFile
import androidx.security.crypto.MasterKeys
import java.io.File

fun writeSecureFile(context: Context) {
    val masterKeyAlias = MasterKeys.getOrCreate(MasterKeys.AES256_GCM_SPEC)
    val file = File(context.filesDir, "secure_data.txt")

    val encryptedFile = EncryptedFile.Builder(
        file,
        context,
        masterKeyAlias,
        EncryptedFile.FileEncryptionScheme.AES256_GCM_HKDF_4KB
    ).build()

    encryptedFile.openFileOutput().use { outputStream ->
        outputStream.write("This is a secret message.".toByteArray(Charsets.UTF_8))
    }
}

fun readSecureFile(context: Context): String {
    val masterKeyAlias = MasterKeys.getOrCreate(MasterKeys.AES256_GCM_SPEC)
    val file = File(context.filesDir, "secure_data.txt")

    val encryptedFile = EncryptedFile.Builder(
        file,
        context,
        masterKeyAlias,
        EncryptedFile.FileEncryptionScheme.AES256_GCM_HKDF_4KB
    ).build()

    encryptedFile.openFileInput().use { inputStream ->
        return inputStream.bufferedReader().use { it.readText() }
    }
}

```



Esmaeel Moradi
 @esmaeeil-moradi700

Key Advantages of this Approach:



- **Simple and Safe:** The developer doesn't need to implement encryption logic themselves, reducing the risk of human error.
- **Hardware-Backed:** The master key can be stored in the hardware-backed keystore, making it extremely difficult to extract.
- **Modern and Maintained:** This is the officially recommended, modern approach from the Android team.



Esmaeel Moradi

@esmaeel-moradi700

Explain the Android permission system and runtime permissions.



The Android permission system is a core component of the platform's security model, controlling an application's access to sensitive user data and system resources. It is divided into two main categories: install-time permissions and runtime permissions.



Esmaeiel Moradi
@esmaeiel-moradi700

1. Install-Time Permissions (Normal Permissions):

- **Definition:** These are permissions that don't pose a significant risk to the user's privacy or the device's operation. They are granted automatically by the system when the app is installed.
- **Examples:** INTERNET, VIBRATE, ACCESS_NETWORK_STATE.
- **How it Works:** The user sees a list of all permissions the app requests at the time of installation. Since these permissions are considered safe, the system grants them without any further action from the user. A flashlight app needs the CAMERA permission, for example, to turn on the flash. If a flashlight app also requested contacts and messages permissions, this would be a warning sign to a user, but it would not prevent installation.



Esmaeeil Moradi
@esmaeeil-moradi700

2. Runtime Permissions (Dangerous Permissions):

- **Definition:** These are permissions that grant access to sensitive user data or system resources, such as the camera, microphone, or user's location.
- **Examples:** CAMERA, READ_CONTACTS, ACCESS_FINE_LOCATION, RECORD_AUDIO.
- **How it Works:**
 - The developer must still declare the permission in the AndroidManifest.xml.
 - Unlike install-time permissions, the system does not grant these permissions automatically.
 - The app must explicitly request the permission from the user at runtime, in a contextually relevant moment, using a standard system dialog.
 - The user can choose to grant or deny the permission. The app's code must handle both scenarios.
 - The user can also revoke the permission at any time from the app's settings.



Esmaeel Moradi
@esmaeel-moradi700



The Importance of Requesting Permissions When Needed:

- **User Trust:** Requesting a permission in context (e.g., asking for CAMERA permission only when the user taps the "Take Photo" button) builds user trust. Requesting all dangerous permissions at app launch can seem suspicious and may lead the user to deny them.
- **Improved UX:** The user understands why the app needs a particular permission, leading to a higher likelihood of the permission being granted.
- **Principle of Least Privilege:** This system directly supports the principle of least privilege. The app only gets access to sensitive resources when it truly needs them, and the user is in control.



Esmaeeil Moradi
@esmaeeil-moradi700

Code Snippet for Requesting a Runtime Permission:

Here's a modern Kotlin example using the new Activity Result APIs to request the CAMERA permission.

```
import android.Manifest
import android.content.pm.PackageManager
import android.os.Bundle
import androidx.activity.result.contract.ActivityResultContracts
import androidx.appcompat.app.AppCompatActivity
import androidx.core.content.ContextCompat

class CameraActivity : AppCompatActivity() {

    // Define a contract to request a single permission
    private val requestPermissionLauncher =
        registerForActivityResult(ActivityResultContracts.RequestPermission()) { isGranted: Boolean ->
            if (isGranted) {
                // Permission is granted. Start the camera.
                startCamera()
            } else {
                // Permission is denied. Handle the error gracefully.
                // e.g., show a message explaining why the permission is needed.
            }
        }

    override fun onCreate(savedInstanceState: Bundle?) {
        super.onCreate(savedInstanceState)
        // ...
        checkAndRequestCameraPermission()
    }
}
```



Esmaeel Moradi
@esmaeel-moradi700

```

private fun checkAndRequestCameraPermission() {
    when {
        ContextCompat.checkSelfPermission(
            this,
            Manifest.permission.CAMERA
        ) == PackageManager.PERMISSION_GRANTED -> {
            // Permission is already granted. You can proceed.
            startCamera()
        }
        shouldShowRequestPermissionRationale(Manifest.permission.CAMERA) -> {
            // In an educational UI, explain to the user why your app needs this permission
            // and provide a button to request it again.
        }
        else -> {
            // Request the permission.
            requestPermissionLauncher.launch(Manifest.permission.CAMERA)
        }
    }
}


private fun startCamera() {
    // Your camera-related logic goes here.
}
}

```

This approach is clean, boilerplate-free, and handles the permission result in a more elegant way than the deprecated `onRequestPermissionsResult` method.



Esmaeel Moradi
 @esmaeel-moradi700



Mid-Level Questions



Esmaeel Moradi
@esmaeeil-moradi700

Implement certificate pinning and network security.

Certificate pinning is a security mechanism that binds a mobile app to a specific SSL/TLS certificate or public key. Instead of trusting any certificate signed by a trusted Certificate Authority (CA), the app is hardcoded to only accept the specific certificate(s) you have "pinned" to it.

Why is it important?

- **Prevents Man-in-the-Middle (MITM) Attacks:** The primary goal of certificate pinning is to prevent a sophisticated attacker from performing a MITM attack. In a standard TLS connection, an attacker can get a certificate from a rogue CA and intercept traffic. With pinning, the app will reject the fake certificate because it doesn't match the one hardcoded in the app.
- **Protects Against Rogue CAs:** If a trusted CA is compromised and starts issuing fraudulent certificates, your app will still be safe because it doesn't rely on the CA's chain of trust.



Esmaeel Moradi
@esmaeeil-moradi700

Implementing Certificate Pinning with Network Security Configuration:

Android provides a declarative way to manage network security settings in the manifest, which is the recommended modern approach. This is much safer and more maintainable than hardcoding the logic in your code.

Step 1: Create the Network Security Configuration XML File

Create a new XML file, for example, res/xml/network_security_config.xml:

```
<?xml version="1.0" encoding="utf-8"?>
<network-security-config>
  <domain-config>
    <domain includeSubdomains="true">api.example.com</domain>
    <pin-set expiration="2026-01-01">
      <pin digest="sha256">AAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAA= </pin>
      <pin digest="sha256">BBBBBBBBBBBBBBBBBBBBBBBBBBBBBBBBBBBBBBBBBBBB= </pin>
    </pin-set>
  </domain-config>
  <base-config cleartextTrafficPermitted="false">
    <trust-anchors>
      <certificates src="system"/>
      <certificates src="user"/>
    </trust-anchors>
  </base-config>
</network-security-config>
```



Esmaeel Moradi
@esmaeeil-moradi700



Key elements in the configuration:

- `<domain-config>`: Specifies the domain(s) to which the pinning applies. `includeSubdomains="true"` is a good practice.
- `<pin-set>`: Contains the list of public key hashes (pins).
 - `expiration`: A critical, mandatory attribute. It ensures that the pins expire, forcing you to update them. This prevents a forgotten pin from breaking your app when the server's certificate is legitimately renewed.
 - `pin digest="sha256"`: The SHA-256 hash of the public key's Subject Public Key Info (SPKI).
- `<base-config cleartextTrafficPermitted="false">`: This is a best practice. It blocks all non-HTTPS traffic, a security requirement for modern apps.



Esmaeeil Moradi
@esmaeeil-moradi700

Step 2: Add the Configuration to the Manifest Add the android:

networkSecurityConfig attribute to your application tag in AndroidManifest.xml:

```
<application
...
    android:networkSecurityConfig="@xml/network_security_config">
    ...
</application>
```

How to get the SHA-256 pin:

You can obtain the pin using openssl. For example:

Bash:

```
openssl s_client -servername api.example.com -connect
api.example.com:443 < /dev/null | openssl x509 -pubkey -
noout | openssl pkey -pubin -outform der | openssl dgst -
sha256 -binary | openssl enc -base64
```



Esmaeel Moradi

@esmaeeil-moradi700

It's a best practice to pin at least two keys: the primary server certificate's public key and a backup. The backup could be from a different CA or a pre-issued certificate for emergencies.

Disadvantages and Considerations:

- **Deployment Risk:** If you forget to update the pins before the server's certificate is renewed, your app will be unable to communicate with the server, effectively bricking the network functionality for all users until an update is deployed.
- **Security vs. Flexibility:** Pinning provides strong security but reduces flexibility. If your infrastructure changes, you must release an app update.

Despite the risks, for apps that handle sensitive data like financial apps, a properly implemented certificate pinning strategy is a highly recommended security measure.



Esmaeel Moradi
@esmaeeil-moradi700



How do you secure sensitive data in memory?

Sensitive data in memory is a common but often overlooked attack vector. An attacker who has gained access to a device (e.g., via root access or a vulnerability) could perform a memory dump to extract sensitive information like passwords, API keys, or private keys that are stored in plaintext in the application's memory.



Esmaeel Moradi
@esmaeel-moradi700

Here's how to mitigate this risk:



1.Minimize Lifetime of Sensitive Data:

- **Concept:** The less time sensitive data spends in memory, the smaller the window of opportunity for an attacker.
- **Implementation:** Do not store sensitive data in global variables or static fields. Instead, load the data, use it for a specific operation (e.g., signing a transaction), and then immediately clear it from memory.
- **Example:** A password entered by a user should be used to authenticate and then immediately cleared.

2.Clear Buffers and Arrays:

- **Concept:** When you are done with a sensitive value, overwrite the memory location with zeros or some other non-sensitive data. The Garbage Collector (GC) in Android is not deterministic; you can't guarantee when a String object will be collected.
- **Implementation:**
 - String objects: Strings in Java/Kotlin are immutable, so you cannot overwrite them. This makes them a poor choice for storing sensitive data.
 - Char or Byte arrays: Use mutable data structures like CharArray or ByteArray. After using the data, loop through the array and set all values to 0.



Esmaeel Moradi

@esmaeel-moradi700

Example:



```
fun processPassword(password: CharArray) {  
    // Use the password for some operation (e.g., authentication)  
    // ...  
  
    // Immediately clear the array after use  
    password.fill('0')  
}
```



Esmaeel Moradi
@esmaeeil-moradi700

3. Avoid Storing Sensitive Data in Primitive Types or Objects:

- **Concept:** Storing sensitive data in a String or other standard objects allows the system to make copies of that data, making it difficult to fully clear it from memory.
- **Implementation:** Use a custom data structure that encapsulates the sensitive data in a ByteArray and provides methods for a specific operation, and a method to clear the data.
- **Example:** A SecureString class that holds a ByteArray and automatically zeroes out its contents when the clear() method is called.



Esmaeel Moradi
@esmaeeil-moradi700



4. Use Hardware-Backed Key Storage:

- **Concept:** For cryptographic keys, the ultimate solution is to store them in a secure, hardware-backed environment like the Android Keystore.
- **How it Works:** The private key is generated and stored in a secure element (e.g., a TrustZone). The key material never leaves this secure environment. The Android system simply sends data to the secure element for cryptographic operations (e.g., signing), and the secure element returns the result. An attacker dumping the app's memory would never find the private key material.
- **Benefit:** This is the most robust solution for securing cryptographic keys. It's a requirement for many financial and cryptocurrency applications.

5. Obfuscation and Anti-Tampering:

- **Concept:** While not directly related to memory, obfuscation (with ProGuard/R8) and anti-tampering measures make it harder for an attacker to understand your code, find where sensitive data is handled, and inject malicious code to intercept it.
- **Implementation:** Enable ProGuard/R8 in your release build configuration. For advanced apps, use a commercial obfuscator like DexGuard for stronger protection.



Esmaeel Moradi

@esmaeel-moradi700



In summary, securing data in memory is a proactive effort. You must assume that an attacker may have access to the device and build your app with defensive measures like minimizing the lifetime of sensitive data and using mutable data structures that can be explicitly cleared.



Esmaeel Moradi
@esmaeeil-moradi700



Design secure authentication flows.

A secure authentication flow is a multi-step process that ensures the identity of the user is verified, protects sensitive credentials, and prevents common attacks. The modern approach is to use industry-standard protocols like OAuth 2.0 and OpenID Connect (OIDC), rather than building a custom authentication system from scratch.



Esmaeail Moradi
@esmaeail-moradi700



1. Principles of a Secure Authentication Flow:

- **OAuth 2.0 (Authorization):** This protocol is for granting an application (client) access to protected resources on behalf of a user. It doesn't handle authentication itself but provides a secure way to delegate authorization.
- **OpenID Connect (Authentication):** OIDC is a layer on top of OAuth 2.0 that handles user authentication. It provides an ID Token (usually a JWT) that contains claims about the authenticated user.
- **Statelessness:** The authentication process should be stateless. The server doesn't maintain session information for the user; instead, it relies on a token provided by the client.

2. The Modern Authentication Flow (Authorization Code Grant with PKCE):

This is the most secure and recommended flow for mobile applications. It's a key part of OIDC.



Esmaeel Moradi
@esmaeel-moradi700

1. **User Initiation:** The user taps a "Sign In" button in your app. →
2. **Redirect to Authorization Server:** The app redirects the user to the Authorization Server's login page (e.g., Google, your company's IdP).
3. **User Authentication:** The user enters their credentials (username/password) directly on the Authorization Server's page, not your app. This protects their credentials from your app.
4. **Consent and Authorization Code:** The user consents to your app accessing their data. The Authorization Server then redirects the user back to your app with a one-time-use Authorization Code.
5. **Token Exchange (PKCE):** Your app, on a secure backend, exchanges the Authorization Code for an Access Token (for accessing resources) and an ID Token (the JWT). The use of Proof Key for Code Exchange (PKCE) is critical here to prevent code interception attacks. PKCE ensures that only the original app that requested the code can exchange it for tokens.
6. **Token Usage:**
 - ID Token (JWT): The app receives the JWT, which contains claims like user_id, email, etc. It should be used to verify the user's identity on the client-side.
 - Access Token: This is a short-lived token used to make API calls to your backend. The app sends this token in the Authorization header of network requests.



Esmaeel Moradi

@esmaeeil-moradi700



3. Securing Tokens and Preventing Attacks:

- **Secure Storage of Tokens:**

- Tokens should never be stored in plain text.
- Use EncryptedSharedPreferences (from the Jetpack Security library) to store the tokens securely.

- **Handling ID Token and Access Token:**

- ID Token (JWT): The client should verify the JWT's signature to ensure it hasn't been tampered with. It should not be used for authorization on the backend.
- Access Token: The access token should be short-lived. A long-lived Refresh Token should be used to get new access tokens without forcing the user to log in again. The refresh token should be stored as securely as possible.

- **Preventing Common Attacks:**

- CSRF (Cross-Site Request Forgery): Using the PKCE flow mitigates CSRF attacks. The code_verifier and code_challenge prevent an attacker from replaying the authorization code.
- Replay Attacks: A one-time Authorization Code is used, and the token exchange is performed over a secure HTTPS connection, which prevents replay attacks.



Esmaeel Moradi

@esmaeeil-moradi700

4. Modern Implementation with AppAuth:

Instead of implementing this complex flow yourself, the best practice is to use a library like AppAuth for Android. It handles the Authorization Code Grant with PKCE, JWT verification, and token refreshing, reducing the risk of security vulnerabilities.



Esmaeeil Moradi
@esmaeeil-moradi700



By adopting these principles and using a robust library, you can design a secure authentication flow that is both user-friendly and highly resilient to common attacks.



Esmaeeil Moradi
@esmaeeil-moradi700

✨ These comprehensive answers aim to equip you with the knowledge required for Architect-level and Senior-level interviews, and to make informed architectural decisions in your real-world projects. Good luck. ✨



Esmaeeil Moradi

@esmaeeil-moradi700